

Open Source Used In DNAC SDA and Switching Automation catc_2379

Cisco Systems, Inc.
www.cisco.com

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco website at www.cisco.com/go/offices.

Text Part Number: 78EE117C99-2246298011

This document contains licenses and notices for open source software used in this product. With respect to the free/open source software listed in this document, if you have any questions or wish to receive a copy of any source code to which you may be entitled under the applicable free/open source license(s) (such as the GNU Lesser/General Public License), please submit this form.

In your requests please include the following reference number 78EE117C99-2246298011

Contents

1.1 objenesis 1.2
1.1.1 Available under license
1.2 velocity 1.7
1.2.1 Available under license
1.3 hibernate-core 3.6.9.Final
1.3.1 Available under license
1.4 hibernate-entitymanager 3.6.7.Final
1.4.1 Available under license
1.5 commons-pool 1.6
1.5.1 Available under license
1.6 commons-beanutils 1.8.3
1.6.1 Available under license
1.7 httpmime 4.2.3
1.7.1 Available under license
1.8 json4s-core 3.2.5
1.9 json4s-ext 3.2.5
1.10 json4s-jackson 3.2.5
1.11 json4s-ast 3.2.5
1.12 json4s-native 3.2.5
1.13 metrics-core 3.1.0
1.13.1 Available under license
1.14 commons-pool 2.2
1.14.1 Available under license
1.15 commons-cli 1.2
1.15.1 Available under license
1.16 httpclient 4.4.1

1.16.1 Available under license
1.17 httpmime 4.3.6
1.17.1 Available under license
1.18 joda-time 2.7
1.18.1 Available under license
1.19 commons-logging 1.2
1.19.1 Available under license
1.20 commons-collections 3.2.2
1.20.1 Available under license
1.21 httpcore 4.4.1
1.21.1 Available under license
1.22 metrics-json 3.1.0
1.22.1 Available under license
1.23 metrics-jvm 3.1.0
1.23.1 Available under license
1.24 commons-io 2.4
1.24.1 Available under license
1.25 joda-convert 1.2
1.25.1 Available under license
1.26 antlr-runtime 4.5.1
1.26.1 Available under license
1.27 copy-concurrently 1.0.5
1.27.1 Available under license
1.28 move-concurrently 1.0.1
1.28.1 Available under license
1.29 run-queue 1.0.3
1.29.1 Available under license
1.30 commons-net 3.0
1.30.1 Available under license
1.31 javax-servlet-api 3.1.0
1.31.1 Available under license
1.32 hibernate-validator 5.0.0.Final
1.33 spring-boot-autoconfigure 1.5.12.RELEASE
1.33.1 Available under license
1.34 spring-boot 1.5.12.RELEASE
1.34.1 Available under license
1.35 commons-validator 1.4.1
1.35.1 Available under license
1.36 javax-annotation-api 1.3.2

1.36.1 Available under license
1.37 stax-ex 1.8
1.38 httpcore-nio 4.4.1
1.38.1 Available under license
1.39 commons-collections 4.1
1.39.1 Available under license
1.40 httpasyncclient 4.1
1.40.1 Available under license
1.41 commons-configuration 1.10
1.41.1 Available under license
1.42 commons-codec 1.9
1.42.1 Available under license
1.43 commons-fileupload 1.4
1.43.1 Available under license
1.44 commons-digester 1.8.1
1.44.1 Available under license
1.45 xmlsec 1.5.7
1.45.1 Available under license
1.46 reflections 0.9.11
1.46.1 Available under license
1.47 resourcelocator 1.0.1
1.47.1 Available under license
1.48 stax-api 1.0-2
1.49 grpc-context 1.9.0
1.49.1 Available under license
1.50 opentracing-noop 0.31.0
1.50.1 Available under license
1.51 grpc-protobuf-lite 1.9.0
1.52 opencensus-api 0.10.0
1.53 opencensus-contrib-grpc-metrics 0.10.0
1.54 okio 1.15.0
1.55 scalap 2.10.0
1.56 okio 1.12.0
1.57 opentracing-web-servlet-filter 0.1.0
1.57.1 Available under license
1.58 reflectasm 1.07
1.59 opentracing-util 0.31.0
1.59.1 Available under license
1.60 javaip 0.16

1.60.1 Available under license
1.61 bson4jackson 2.7.0
1.62 jtoml 1.0.0
1.63 wsdl4j 1.6.2
1.63.1 Available under license
1.64 classmate 0.8.0
1.65 android-json 0.0.20131108.vaadin1
1.66 jzlib 1.0.7
1.67 jeromq 0.3.2
1.67.1 Available under license
1.68 typetools 0.3.1
1.69 paranamer 2.5.6
1.70 redline 1.2.6
1.71 diffutils 1.2.1
1.71.1 Available under license
1.72 jakarta xml bind api 2.3.2
1.72.1 Available under license
1.73 apiguardian-api 1.0.0
1.74 minio 4.0.0
1.75 animal-sniffer-annotation 1.14
1.76 jcip-annotation 1.0
1.76.1 Available under license
1.77 jcip-annotation 1.0-1
1.78 javax-inject 1
1.78.1 Available under license
1.79 jackson-mapper-asl 1.9.13
1.79.1 Available under license
1.80 tiger-types 1.4
1.80.1 Available under license
1.81 qdox 1.12
1.82 xpp 1.1.4c
1.83 hamcrest-all 1.3
1.84 javax-ws-rs-api 2.0.1
1.84.1 Available under license
1.85 asm 5.0.4
1.85.1 Available under license
1.86 annotations 3.0.1
1.87 jcl-over-slf4j 1.7.21
1.88 asm 4.0

1.89 antlr 2.7.6
1.90 protobuf-java 3.5.1
1.90.1 Available under license
1.91 geronimo-javamail 1.7.1
1.91.1 Available under license
1.92 checker-compat-qual 2.0.0
1.92.1 Available under license
1.93 protobuf-java-util 3.5.1
1.94 minimal-json 0.9.4
1.95 grpc-core 1.9.0
1.96 instrumentation-api 0.4.3
1.97 slf4j 1.7.21
1.97.1 Available under license
1.98 hazelcast-client-protocol 1.4.1
1.98.1 Available under license
1.99 scala-compiler 2.10.0
1.99.1 Available under license
1.100 jaxen 1.1.6
1.100.1 Available under license
1.101 scala-reflect 2.10.4
1.102 swagger-annotations 1.3.12
1.103 swagger-jersey2-jaxrs 1.5.0
1.104 commons-compiler 2.6.1
1.105 proto-google-common-protos 1.0.0
1.106 minlog 1.2
1.107 hazelcast 3.8.9
1.107.1 Available under license
1.108 unirest-java 1.4.5
1.108.1 Available under license
1.109 jul-to-slf4j 1.7.21
1.109.1 Available under license
1.110 open-csv 4.1
1.111 asm-util 4.0
1.112 not-yet-commons-ssl 0.3.11
1.112.1 Available under license
1.113 asm-tree 4.0
1.114 castor-core 1.3.1
1.114.1 Available under license
1.115 quartz 2.2.1

1.116 commons-pool 1.5.3
1.116.1 Available under license
1.117 quartz 1.6.0
1.118 woodstox-core-asl 4.1.4
1.118.1 Available under license
1.119 jersey-bean-validation 2.5.1
1.120 cxf-rt-frontend-jaxrs 2.7.3
1.120.1 Available under license
1.121 jersey-media-jaxb 2.24.1
1.122 javax-el 2.2.4
1.123 swagger-springmvc 0.8.8
1.124 castor-xml 1.3.1
1.124.1 Available under license
1.125 swagger-models 0.8.8
1.126 config 1.0.2
1.127 jersey-client 2.5.1
1.128 cxf-rt-transports-http 2.7.3
1.128.1 Available under license
1.129 javax-el-api 2.2.4
1.130 jersey-container-servlet-core 2.5.1
1.131 freemarker 2.3.23
1.132 jersey-media-multipart 2.5.1
1.133 cassandra-driver-core 2.1.0
1.134 jersey-common 2.24.1
1.135 cxf-rt-core 2.7.3
1.135.1 Available under license
1.136 jersey-server 2.5.1
1.137 cassandra-driver-mapping 2.1.0
1.138 jersey-guava 2.24.1
1.139 cglib-nodep 3.1
1.139.1 Available under license
1.140 cxf-rt-bindings-xml 2.7.3
1.140.1 Available under license
1.141 ant 1.7.1
1.142 jersey-server 2.24.1
1.143 snmp-4j 1.11
1.143.1 Available under license
1.144 gson 2.2.3
1.145 jersey-client 2.24.1

1.146 jersey-common 2.5.1
1.147 jersey-container-servlet 2.5.1
1.148 cxf-api 2.7.3
1.148.1 Available under license
1.149 avro 1.7.5
1.149.1 Available under license
1.150 ant-launcher 1.7.1
1.150.1 Available under license
1.151 jetty-http-spi 9.3.27.v20190418
1.152 websocket-servlet 9.3.27.v20190418
1.153 websocket-common 9.3.27.v20190418
1.154 websocket-api 9.3.27.v20190418
1.155 websocket-client 9.3.27.v20190418
1.156 websocket-server 9.3.27.v20190418
1.157 java-concurrent-hash-trie-map 0.2.23
1.158 xstream 1.2.2
1.159 hibernatejpa2.0api 1.0.1.Final
1.159.1 Available under license
1.160 profiler 1.0.2
1.161 swagger-annotations 1.5.22
1.161.1 Available under license
1.162 jedis 2.10.2
1.163 jetty-xml 9.4.18.v20190429
1.163.1 Available under license
1.164 jetty-continuation 9.4.18.v20190429
1.164.1 Available under license
1.165 jetty-webapp 9.4.18.v20190429
1.165.1 Available under license
1.166 jetty-util 9.4.18.v20190429
1.166.1 Available under license
1.167 jetty 9.4.18.v20190429
1.167.1 Available under license
1.168 jetty-servlets 9.4.18.v20190429
1.168.1 Available under license
1.169 jetty-security 9.4.18.v20190429
1.169.1 Available under license
1.170 jetty-client 9.4.18.v20190429
1.170.1 Available under license
1.171 swagger-core 1.5.22

1.172 swagger-jaxrs 1.5.22
1.173 babel-polyfill 6.26.0
1.174 opentracing-spring-web-autoconfigure 0.3.2
1.174.1 Available under license
1.175 opentracing-api 0.31.0
1.175.1 Available under license
1.176 opentracing-tracerresolver 0.1.4
1.176.1 Available under license
1.177 opentracing-spring-web 0.3.2
1.177.1 Available under license
1.178 esprima 3.1.3
1.178.1 Available under license
1.179 postcss 6.0.23
1.179.1 Available under license
1.180 c3p0 0.9.1.1
1.180.1 Available under license
1.181 jsqlparser 2.1
1.181.1 Available under license
1.182 reactive-streams 1.0.3
1.182.1 Available under license
1.183 java-jwt 3.8.3
1.183.1 Available under license
1.184 javax-json 1.1.4
1.184.1 Available under license
1.185 justify 0.17.0
1.185.1 Available under license
1.186 jsesc 0.5.0
1.186.1 Available under license
1.187 gulp 4.0.2
1.187.1 Available under license
1.188 mongo-jackson-codec 3.2.2__0.5
1.188.1 Available under license
1.189 junit-platform-commons 1.1.0
1.189.1 Available under license
1.190 junit-jupiter-api 5.1.0
1.190.1 Available under license
1.191 swagger-models 1.5.22
1.191.1 Available under license
1.192 http-signature 1.2.0

1.192.1 Available under license
1.193 babel-plugin-syntax-nullish-coalescing-operator 7.8.3
1.193.1 Available under license
1.194 babel-plugin-syntax-optional-chaining 7.8.3
1.194.1 Available under license
1.195 ejs 2.7.4
1.195.1 Available under license
1.196 xerces 2.9.1
1.196.1 Available under license
1.197 vavr 0.10.2
1.197.1 Available under license
1.198 vavr-match 0.10.2
1.198.1 Available under license
1.199 commons-lang3 2.6
1.199.1 Available under license
1.200 commons-compress 1.20
1.200.1 Available under license
1.201 request 2.88.2
1.201.1 Available under license
1.202 commons-lang3 2.4.0
1.202.1 Available under license
1.203 dbcp 1.2.2.osgi
1.203.1 Available under license
1.204 jms 1.1.0
1.204.1 Available under license
1.205 servlet 2.5.0
1.205.1 Available under license
1.206 commons-lang3 3.9
1.206.1 Available under license
1.207 javax-servlet-api 2.5.0
1.207.1 Available under license
1.208 bluebird 3.7.2
1.208.1 Available under license
1.209 mkdirp 0.5.5
1.209.1 Available under license
1.210 spring-retry 1.2.5.RELEASE
1.210.1 Available under license
1.211 reactor-core 3.3.5.RELEASE
1.211.1 Available under license

1.212 netty-tcnative 2.0.9.Final
1.212.1 Available under license
1.213 spring-framework 4.3.20.RELEASE
1.213.1 Available under license
1.214 reactor-netty 0.9.7.RELEASE
1.214.1 Available under license
1.215 google-http-client 1.15.0-rc
1.215.1 Available under license
1.216 sizeof-agent 1.0.1
1.216.1 Available under license
1.217 spring-expression 4.3.20.RELEASE
1.217.1 Available under license
1.218 spring-orm 4.3.20.RELEASE
1.218.1 Available under license
1.219 spring-aop 4.3.20.RELEASE
1.219.1 Available under license
1.220 spring-context 4.3.20.RELEASE
1.220.1 Available under license
1.221 spring-aspects 4.3.20.RELEASE
1.221.1 Available under license
1.222 spring-tx 4.3.20.RELEASE
1.222.1 Available under license
1.223 spring-beans 4.3.20.RELEASE
1.223.1 Available under license
1.224 spring-web 4.3.20.RELEASE
1.224.1 Available under license
1.225 spring-jdbc 4.3.20.RELEASE
1.225.1 Available under license
1.226 spring-jms 4.3.20.RELEASE
1.226.1 Available under license
1.227 netty 4.1.48.Final
1.227.1 Available under license
1.228 lodash.restparam 3.6.1
1.228.1 Available under license
1.229 lodash._getnative 3.9.1
1.229.1 Available under license
1.230 lodash-root 3.0.1
1.230.1 Available under license
1.231 lodash.isplainobject 4.0.6

1.231.1 Available under license

1.232 lodash.keys 3.1.2

1.232.1 Available under license

1.233 lodash.isarguments 3.1.0

1.233.1 Available under license

1.234 lodash-escape 3.2.0

1.234.1 Available under license

1.235 lodash._isiterateecall 3.0.9

1.235.1 Available under license

1.236 lodash-templatesettings 3.1.1

1.236.1 Available under license

1.237 lodash-basevalues 3.0.0

1.237.1 Available under license

1.238 lodash.isarray 3.0.4

1.238.1 Available under license

1.239 lodash-template 3.6.2

1.239.1 Available under license

1.240 lodash-reescape 3.0.0

1.240.1 Available under license

1.241 lodash-basetostring 3.0.1

1.241.1 Available under license

1.242 lodash._basecopy 3.0.1

1.242.1 Available under license

1.243 lodash-reevaluate 3.0.0

1.243.1 Available under license

1.244 lodash-reinterpolate 3.0.0

1.244.1 Available under license

1.245 lodash.get 4.4.2

1.245.1 Available under license

1.246 lodash.debounce 4.0.8

1.246.1 Available under license

1.247 bson 3.12.4

1.247.1 Available under license

1.248 mongodb-driver 3.12.4

1.248.1 Available under license

1.249 mongodb-driver-core 3.12.4

1.249.1 Available under license

1.250 colors.js 1.4.0

1.250.1 Available under license

1.251 spring-web-mvc 4.3.20.RELEASE
1.251.1 Available under license
1.252 messageformat 0.1.2
1.252.1 Available under license
1.253 camel-core 2.15.2
1.253.1 Available under license
1.254 commons-dbcp 1.4
1.254.1 Available under license
1.255 rsocket-transport-netty 1.0.0-RC7
1.255.1 Available under license
1.256 rsocket-core 1.0.0-RC7
1.256.1 Available under license
1.257 form-data 2.3.3
1.257.1 Available under license
1.258 import-fresh 2.0.0
1.258.1 Available under license
1.259 lcid 1.0.0
1.259.1 Available under license
1.260 for-in 1.0.2
1.260.1 Available under license
1.261 extglob 2.0.4
1.261.1 Available under license
1.262 is-wsl 1.1.0
1.262.1 Available under license
1.263 isarray 1.0.0
1.263.1 Available under license
1.264 hoist-non-react-statics 2.5.5
1.264.1 Available under license
1.265 pump 2.0.1
1.265.1 Available under license
1.266 opentest4j 1.0.0
1.266.1 Available under license
1.267 loud-rejection 1.6.0
1.267.1 Available under license
1.268 extend-shallow 3.0.2
1.268.1 Available under license
1.269 async-foreach 0.1.3
1.269.1 Available under license
1.270 get-stream 4.1.0

1.270.1 Available under license
1.271 scss-tokenizer 0.2.3
1.271.1 Available under license
1.272 gaze 1.1.3
1.272.1 Available under license
1.273 callsites 2.0.0
1.273.1 Available under license
1.274 cosmiconfig 5.2.1
1.274.1 Available under license
1.275 collection-visit 1.0.0
1.275.1 Available under license
1.276 ansi-gray 0.1.1
1.276.1 Available under license
1.277 mississippi 3.0.0
1.277.1 Available under license
1.278 typedarray 0.0.6
1.278.1 Available under license
1.279 for-own 1.0.0
1.279.1 Available under license
1.280 bcrypt-pbkdf 1.0.2
1.280.1 Available under license
1.281 strip-indent 1.0.1
1.281.1 Available under license
1.282 commondir 1.0.1
1.282.1 Available under license
1.283 pumpify 1.5.1
1.283.1 Available under license
1.284 get-stdin 4.0.1
1.284.1 Available under license
1.285 true-case-path 1.0.3
1.285.1 Available under license
1.286 amdefine 1.0.1
1.286.1 Available under license
1.287 har-schema 2.0.0
1.287.1 Available under license
1.288 unique-filename 1.1.1
1.288.1 Available under license
1.289 delegates 1.0.0
1.289.1 Available under license

1.290 path-is-absolute 1.0.1

1.290.1 Available under license

1.291 fancy-log 1.3.3

1.291.1 Available under license

1.292 which-module 1.0.0

1.292.1 Available under license

1.293 normalize-package-data 2.5.0

1.293.1 Available under license

1.294 remove-trailing-separator 1.1.0

1.294.1 Available under license

1.295 parse-node-version 1.0.1

1.295.1 Available under license

1.296 cross-spawn 3.0.1

1.296.1 Available under license

1.297 wrappy 1.0.2

1.297.1 Available under license

1.298 path-type 1.1.0

1.298.1 Available under license

1.299 isexe 2.0.0

1.299.1 Available under license

1.300 is-extglob 2.1.1

1.300.1 Available under license

1.301 iferr 0.1.5

1.301.1 Available under license

1.302 is-arrayish 0.2.1

1.302.1 Available under license

1.303 aproba 1.2.0

1.303.1 Available under license

1.304 redent 1.0.0

1.304.1 Available under license

1.305 fstream 1.0.12

1.305.1 Available under license

1.306 caller-callsite 2.0.0

1.306.1 Available under license

1.307 util-deprecate 1.0.2

1.307.1 Available under license

1.308 commander 2.17.1

1.308.1 Available under license

1.309 which 1.3.1

1.309.1 Available under license
1.310 ecc-jsbn 0.1.2
1.310.1 Available under license
1.311 tunnel-agent 0.6.0
1.311.1 Available under license
1.312 concat-stream 1.6.2
1.312.1 Available under license
1.313 asn1.js 4.10.1
1.313.1 Available under license
1.314 ansi-wrap 0.1.0
1.314.1 Available under license
1.315 babel-runtime 6.26.0
1.315.1 Available under license
1.316 caseless 0.12.0
1.316.1 Available under license
1.317 cookie-signature 1.0.6
1.317.1 Available under license
1.318 class-utils 0.3.6
1.318.1 Available under license
1.319 camelcase-keys 2.1.0
1.319.1 Available under license
1.320 define-property 2.0.2
1.320.1 Available under license
1.321 deep-extend 0.6.0
1.321.1 Available under license
1.322 number-is-nan 1.0.1
1.322.1 Available under license
1.323 json-loader 0.5.7
1.323.1 Available under license
1.324 isomorphic-fetch 2.2.1
1.324.1 Available under license
1.325 arr-flatten 1.1.0
1.325.1 Available under license
1.326 arr-union 3.1.0
1.326.1 Available under license
1.327 error-ex 1.3.2
1.327.1 Available under license
1.328 oauth-sign 0.9.0
1.328.1 Available under license

1.329 forever-agent 0.6.1
1.329.1 Available under license
1.330 symbol-observable 1.2.0
1.330.1 Available under license
1.331 osenv 0.1.5
1.331.1 Available under license
1.332 wordwrap 1.0.0
1.332.1 Available under license
1.333 getpass 0.1.7
1.333.1 Available under license
1.334 css-what 2.1.3
1.334.1 Available under license
1.335 isstream 0.1.2
1.335.1 Available under license
1.336 code-point-at 1.1.0
1.336.1 Available under license
1.337 meow 3.7.0
1.337.1 Available under license
1.338 time-stamp 1.1.0
1.338.1 Available under license
1.339 os-homedir 1.0.2
1.339.1 Available under license
1.340 read-pkg 1.1.0
1.340.1 Available under license
1.341 fragment-cache 0.2.1
1.341.1 Available under license
1.342 esutils 2.0.3
1.342.1 Available under license
1.343 read-pkg-up 1.0.1
1.343.1 Available under license
1.344 component-emitter 1.3.0
1.344.1 Available under license
1.345 copy-descriptor 0.1.1
1.345.1 Available under license
1.346 load-json-file 1.1.0
1.346.1 Available under license
1.347 strip-bom 2.0.0
1.347.1 Available under license
1.348 decamelize 1.2.0

1.348.1 Available under license

1.349 ms 2.1.2

1.349.1 Available under license

1.350 json-parse-better-errors 1.0.2

1.350.1 Available under license

1.351 performance-now 2.1.0

1.351.1 Available under license

1.352 gauge 2.7.4

1.352.1 Available under license

1.353 extsprintf 1.3.0

1.353.1 Available under license

1.354 asap 2.0.6

1.354.1 Available under license

1.355 caller-path 2.0.0

1.355.1 Available under license

1.356 assert-plus 1.0.0

1.356.1 Available under license

1.357 array-find-index 1.0.2

1.357.1 Available under license

1.358 currently-unhandled 0.4.1

1.358.1 Available under license

1.359 os-locale 1.4.0

1.359.1 Available under license

1.360 expand-brackets 2.1.4

1.360.1 Available under license

1.361 os-tmpdir 1.0.2

1.361.1 Available under license

1.362 ci-info 2.0.0

1.362.1 Available under license

1.363 abbrev 1.1.1

1.363.1 Available under license

1.364 trim-newlines 1.0.0

1.364.1 Available under license

1.365 verror 1.10.0

1.365.1 Available under license

1.366 arr-diff 4.0.0

1.366.1 Available under license

1.367 stdout-stream 1.4.1

1.367.1 Available under license

1.368 invert-kv 1.0.0
1.368.1 Available under license
1.369 fs-write-stream-atomic 1.0.10
1.369.1 Available under license
1.370 brace-expansion 1.1.11
1.370.1 Available under license
1.371 archy 1.0.0
1.371.1 Available under license
1.372 inflight 1.0.6
1.372.1 Available under license
1.373 cliui 3.2.0
1.373.1 Available under license
1.374 map-obj 1.0.1
1.374.1 Available under license
1.375 repeating 2.0.1
1.375.1 Available under license
1.376 is-typedarray 1.0.0
1.376.1 Available under license
1.377 is-directory 0.3.1
1.377.1 Available under license
1.378 get-value 2.0.6
1.378.1 Available under license
1.379 indent-string 2.1.0
1.379.1 Available under license
1.380 lru-cache 5.1.1
1.380.1 Available under license
1.381 html-comment-regex 1.1.2
1.381.1 Available under license
1.382 cache-base 1.0.1
1.382.1 Available under license
1.383 tweetnacl 0.14.5
1.383.1 Available under license
1.384 array-unique 0.3.2
1.384.1 Available under license
1.385 assign-symbols 1.0.0
1.385.1 Available under license
1.386 through 2.3.8
1.386.1 Available under license
1.387 extend 3.0.2

1.387.1 Available under license
1.388 npmlog 4.1.2
1.388.1 Available under license
1.389 netty 3.10.5.Final
1.389.1 Available under license
1.390 hibernate-commons-annotations 3.2.0.Final
1.390.1 Available under license
1.391 guava 25.0-jre
1.391.1 Available under license
1.392 deep-diff 0.3.8
1.392.1 Available under license
1.393 netty-codec-http 4.1.17.Final
1.393.1 Available under license
1.394 jackson-core-asl 1.9.13
1.394.1 Available under license
1.395 javassist 3.12.0.GA
1.395.1 Available under license
1.396 bean-validation-api 1.0.0.GA
1.396.1 Available under license
1.397 xml-commons 1.3.4
1.397.1 Available under license
1.398 springsourceapachexmlresolver 1.2.0
1.398.1 Available under license
1.399 springsource-org-apache-xerces 2.9.1
1.399.1 Available under license
1.400 jsonfile 4.0.0
1.400.1 Available under license
1.401 aws-sign2 0.7.0
1.401.1 Available under license
1.402 apache-log4j 1.2.15
1.402.1 Available under license
1.403 httpcore 4.4.5
1.403.1 Available under license
1.404 istack-commons-runtime 2.21
1.404.1 Available under license
1.405 hk2-api 2.5.0-b05
1.405.1 Available under license
1.406 aopalliance-repackaged 2.5.0-b05
1.406.1 Available under license

1.407 javax-inject 2.5.0-b05
1.407.1 Available under license
1.408 hk2-utils 2.5.0-b05
1.408.1 Available under license
1.409 hk2-locator 2.5.0-b05
1.409.1 Available under license
1.410 recompose 0.30.0
1.410.1 Available under license
1.411 stylis-rule-sheet 0.0.10
1.411.1 Available under license
1.412 stylis 3.5.4
1.412.1 Available under license
1.413 change-emitter 0.1.6
1.413.1 Available under license
1.414 jsesc 2.5.2
1.414.1 Available under license
1.415 ehcache-core 2.6.5
1.415.1 Available under license
1.416 jackson-module-scala 2.1.5
1.416.1 Available under license
1.417 swagger-core 1.3.5
1.417.1 Available under license
1.418 infer-owner 1.0.4
1.418.1 Available under license
1.419 p-try 2.2.0
1.419.1 Available under license
1.420 chownr 1.1.4
1.420.1 Available under license
1.421 onetime 1.1.0
1.421.1 Available under license
1.422 xml-schema-core 2.0.3
1.422.1 Available under license
1.423 jetty-server 9.4.18.v20190429
1.423.1 Available under license
1.424 libthrift 0.9.2
1.424.1 Available under license
1.425 pkg-dir 4.2.0
1.425.1 Available under license
1.426 postcss-loader 3.0.0

1.426.1 Available under license

1.427 eslint-scope 4.0.3

1.427.1 Available under license

1.428 import-cwd 2.1.0

1.428.1 Available under license

1.429 clone 2.1.2

1.429.1 Available under license

1.430 stream-each 1.2.3

1.430.1 Available under license

1.431 import-from 2.1.0

1.431.1 Available under license

1.432 cglib 2.2.0-b21

1.432.1 Available under license

1.433 javax-inject 2.2.0-b21

1.433.1 Available under license

1.434 hk2-utils 2.2.0-b21

1.434.1 Available under license

1.435 hk2-api 2.2.0-b21

1.435.1 Available under license

1.436 hk2-locator 2.2.0-b21

1.436.1 Available under license

1.437 asm-all-repackaged 2.2.0-b21

1.437.1 Available under license

1.438 netty-codec-socks 4.1.17.Final

1.438.1 Available under license

1.439 netty-handler-proxy 4.1.17.Final

1.439.1 Available under license

1.440 netty-transport 4.1.17.Final

1.440.1 Available under license

1.441 d3-delaunay 5.3.0

1.441.1 Available under license

1.442 okhttp 3.12.1

1.442.1 Available under license

1.443 spring-security-cas 3.2.4.RELEASE

1.443.1 Available under license

1.444 xmltooling 1.4.4

1.444.1 Available under license

1.445 yang-common 0.8.4-Beryllium-SR4

1.445.1 Available under license

1.446 mibble-commercial-mibs 2.9.3
1.446.1 Available under license
1.447 json 20090211
1.447.1 Available under license
1.448 yang-parser-api 0.8.4-Beryllium-SR4
1.448.1 Available under license
1.449 javassist 3.17.1-GA
1.449.1 Available under license
1.450 commons-http-client 3.0.1
1.450.1 Available under license
1.451 spring-security-taglibs 3.2.4.RELEASE
1.451.1 Available under license
1.452 scala-library 2.10.4
1.452.1 Available under license
1.453 concepts 0.8.4-Beryllium-SR4
1.453.1 Available under license
1.454 spring-security-web 3.2.4.RELEASE
1.454.1 Available under license
1.455 object-cache-api 0.8.4-Beryllium-SR4
1.455.1 Available under license
1.456 spring-security-core 3.2.4.RELEASE
1.456.1 Available under license
1.457 yang-parser-impl 0.8.4-Beryllium-SR4
1.457.1 Available under license
1.458 spring-security-config 3.2.4.RELEASE
1.458.1 Available under license
1.459 util 0.8.4-Beryllium-SR4
1.459.1 Available under license
1.460 mibble-commercial-parser 2.9.3
1.460.1 Available under license
1.461 springsource-javax-jms 1.1.0
1.461.1 Available under license
1.462 yang-model-api 0.8.4-Beryllium-SR4
1.462.1 Available under license
1.463 spring-security-acl 3.2.4.RELEASE
1.463.1 Available under license
1.464 springsourcehibernatevalidator 4.1.0.GA
1.464.1 Available under license
1.465 yang-model-util 0.8.4-Beryllium-SR4

1.465.1 Available under license

1.466 jakarta-json-api 1.1.5

1.466.1 Available under license

1.467 bean-validation-api 1.1.0.Final

1.467.1 Available under license

1.468 jta 1.1

1.468.1 Available under license

1.469 jms 1.1

1.469.1 Available under license

1.470 aspectj-tools 1.9.6

1.470.1 Available under license

1.471 aop-alliance 1.0

1.471.1 Available under license

1.472 spring-messaging 4.3.30.RELEASE

1.472.1 Available under license

1.473 from2 2.3.0

1.473.1 Available under license

1.474 universalify 0.1.2

1.474.1 Available under license

1.475 tough-cookie 2.5.0

1.475.1 Available under license

1.476 springsource-javax-validation 1.0.0.GA

1.476.1 Available under license

1.477 js-base64 2.6.4

1.477.1 Available under license

1.478 errno 0.1.8

1.478.1 Available under license

1.479 fs-extra 7.0.1

1.479.1 Available under license

1.480 exit-on-epipe 1.0.1

1.480.1 Available under license

1.481 preserve 0.2.0

1.481.1 Available under license

1.482 acorn 6.4.2

1.482.1 Available under license

1.483 braces 3.0.2

1.483.1 Available under license

1.484 tryer 1.0.1

1.484.1 Available under license

1.485 braces 1.8.5

1.485.1 Available under license

1.486 bfj 6.1.2

1.486.1 Available under license

1.487 minimatch 2.0.10

1.487.1 Available under license

1.488 har-validator 5.1.5

1.488.1 Available under license

1.489 uri-js 4.4.1

1.489.1 Available under license

1.490 xpp3-min 1.1.4c

1.490.1 Available under license

1.491 commons-lang3 2.4

1.491.1 Available under license

1.492 array-differ 1.0.0

1.492.1 Available under license

1.493 ansi-escapes 1.4.0

1.493.1 Available under license

1.494 beeper 1.1.1

1.494.1 Available under license

1.495 cli-cursor 1.0.2

1.495.1 Available under license

1.496 coffee-loader 0.7.3

1.496.1 Available under license

1.497 date-format 2.2.0

1.497.1 Available under license

1.498 duplexify 3.7.1

1.498.1 Available under license

1.499 duplexer2 0.0.2

1.499.1 Available under license

1.500 figures 1.7.0

1.500.1 Available under license

1.501 expand-range 1.8.2

1.501.1 Available under license

1.502 exit-hook 1.1.1

1.502.1 Available under license

1.503 flush-write-stream 1.1.1

1.503.1 Available under license

1.504 growly 1.3.0

1.504.1 Available under license
1.505 gulp-util 3.0.8
1.505.1 Available under license
1.506 gulplog 1.0.0
1.506.1 Available under license
1.507 glogg 1.0.2
1.507.1 Available under license
1.508 has-gulplog 0.1.0
1.508.1 Available under license
1.509 in-publish 2.0.1
1.509.1 Available under license
1.510 is-finite 1.1.0
1.510.1 Available under license
1.511 is-utf8 0.2.1
1.511.1 Available under license
1.512 log-update 1.0.2
1.512.1 Available under license
1.513 math-random 1.0.4
1.513.1 Available under license
1.514 mute-stream 0.0.4
1.514.1 Available under license
1.515 multipipe 0.1.2
1.515.1 Available under license
1.516 parallel-transform 1.2.0
1.516.1 Available under license
1.517 p-limit 2.3.0
1.517.1 Available under license
1.518 pretty-hrtime 1.0.3
1.518.1 Available under license
1.519 randomatic 3.1.1
1.519.1 Available under license
1.520 redux-mock-store 1.5.4
1.520.1 Available under license
1.521 sass-graph 2.2.5
1.521.1 Available under license
1.522 restore-cursor 1.0.1
1.522.1 Available under license
1.523 run-async 0.1.0
1.523.1 Available under license

1.524 rx-lite 3.1.2
1.524.1 Available under license
1.525 shellwords 0.1.1
1.525.1 Available under license
1.526 sparkles 1.0.1
1.526.1 Available under license
1.527 spdx-expression-parse 3.0.1
1.527.1 Available under license
1.528 string-template 1.0.0
1.528.1 Available under license
1.529 through2 2.0.5
1.529.1 Available under license
1.530 stream-shift 1.0.1
1.530.1 Available under license
1.531 unique-slug 2.0.2
1.531.1 Available under license
1.532 worker-loader 2.0.0
1.532.1 Available under license
1.533 commons-dbcp 2.0.1
1.533.1 Available under license
1.534 kryo 2.17
1.534.1 Available under license
1.535 annotations 13.0
1.535.1 Available under license
1.536 woodstox-core 6.2.4
1.536.1 Available under license
1.537 lodash 4.17.21
1.537.1 Available under license
1.538 error_prone_annotations 2.1.3
1.538.1 Available under license
1.539 j2objc-annotations 1.1
1.539.1 Available under license
1.540 jsr305 1.3.9
1.540.1 Available under license
1.541 log4j-over-slf4j 1.7.21
1.541.1 Available under license
1.542 spring-binding 2.5.1.RELEASE
1.542.1 Available under license
1.543 spring-webmvc-portlet 4.3.19.RELEASE

1.543.1 Available under license

1.544 spring-oxm 4.3.19.RELEASE

1.544.1 Available under license

1.545 spring-context-support 4.3.19.RELEASE

1.545.1 Available under license

1.546 commons-dbcp 1.2.2.osgi

1.546.1 Available under license

1.547 commons-logging 1.1.1

1.547.1 Available under license

1.548 dom4j 1.6.1

1.548.1 Available under license

1.549 txw2 2.2.11

1.549.1 Available under license

1.550 react 17.0.2

1.550.1 Available under license

1.551 y18n 3.2.2

1.551.1 Available under license

1.552 event-emitter 0.3.5

1.552.1 Available under license

1.553 acorn-walk 7.2.0

1.553.1 Available under license

1.554 type-fest 0.8.1

1.554.1 Available under license

1.555 make-dir 3.1.0

1.555.1 Available under license

1.556 fill-range 7.0.1

1.556.1 Available under license

1.557 es6-iterator 2.0.3

1.557.1 Available under license

1.558 camelcase 5.3.1

1.558.1 Available under license

1.559 is-number 7.0.0

1.559.1 Available under license

1.560 is-ci 2.0.0

1.560.1 Available under license

1.561 slash 2.0.0

1.561.1 Available under license

1.562 dot-prop 4.2.1

1.562.1 Available under license

1.563 aspectj-weaver 1.9.6
1.563.1 Available under license
1.564 eventemitter3 4.0.7
1.564.1 Available under license
1.565 escalade 3.1.1
1.565.1 Available under license
1.566 enhanced-resolve 4.5.0
1.566.1 Available under license
1.567 eslint-visitor-keys 1.3.0
1.567.1 Available under license
1.568 es6-weak-map 2.0.3
1.568.1 Available under license
1.569 clone-deep 4.0.1
1.569.1 Available under license
1.570 d 1.0.1
1.570.1 Available under license
1.571 figgy-pudding 3.5.2
1.571.1 Available under license
1.572 sass-loader 8.0.2
1.572.1 Available under license
1.573 shallow-clone 3.0.1
1.573.1 Available under license
1.574 es6-symbol 3.1.3
1.574.1 Available under license
1.575 filter-obj 1.1.0
1.575.1 Available under license
1.576 jta 1.1.0
1.576.1 Available under license
1.577 commander 4.1.1
1.577.1 Available under license
1.578 semver-diff 3.1.1
1.578.1 Available under license
1.579 is-installed-globally 0.3.2
1.579.1 Available under license
1.580 is-npm 4.0.0
1.580.1 Available under license
1.581 is-path-inside 3.0.3
1.581.1 Available under license
1.582 pbkdf2 3.1.2

1.582.1 Available under license
1.583 pupa 2.1.1
1.583.1 Available under license
1.584 is-yarn-global 0.3.0
1.584.1 Available under license
1.585 update-notifier 4.1.3
1.585.1 Available under license
1.586 latest-version 5.1.0
1.586.1 Available under license
1.587 write-file-atomic 3.0.3
1.587.1 Available under license
1.588 has-yarn 2.1.0
1.588.1 Available under license
1.589 escape-goat 2.1.1
1.589.1 Available under license
1.590 glob-parent 5.1.2
1.590.1 Available under license
1.591 global-dirs 2.1.0
1.591.1 Available under license
1.592 hoopy 0.1.4
1.592.1 Available under license
1.593 duplexer 0.1.2
1.593.1 Available under license
1.594 readdirp 3.2.0
1.594.1 Available under license
1.595 chokidar 3.3.0
1.595.1 Available under license
1.596 lz4 1.2.0
1.596.1 Available under license
1.597 normalize-url 4.5.1
1.597.1 Available under license
1.598 log4j-rolling-appender 20131024-2017
1.598.1 Available under license
1.599 forwarded 0.2.0
1.599.1 Available under license
1.600 glob-stream 6.1.0
1.600.1 Available under license
1.601 unique-stream 2.3.1
1.601.1 Available under license

1.602 is-negated-glob 1.0.0

1.602.1 Available under license

1.603 to-absolute-glob 2.0.2

1.603.1 Available under license

1.604 through2-filter 3.0.0

1.604.1 Available under license

1.605 ordered-read-streams 1.0.1

1.605.1 Available under license

1.606 hosted-git-info 2.8.9

1.606.1 Available under license

1.607 ws 6.2.2

1.607.1 Available under license

1.608 postcss-load-config 2.1.2

1.608.1 Available under license

1.609 internmap 1.0.1

1.609.1 Available under license

1.610 accessors-smart 1.2

1.610.1 Available under license

1.611 xsdlib 2013.6.1

1.611.1 Available under license

1.612 cglib 3.0

1.612.1 Available under license

1.613 json-smart 2.3

1.613.1 Available under license

1.614 jctools-core 3.0.0

1.614.1 Available under license

1.615 babel-plugin-syntax-top-level-await 7.14.5

1.615.1 Available under license

1.616 memoize-one 5.2.1

1.616.1 Available under license

1.617 fs-readdir-recursive 1.1.0

1.617.1 Available under license

1.618 node-notifier 5.4.5

1.618.1 Available under license

1.619 sinon 11.1.2

1.619.1 Available under license

1.620 httpclient 3.10.0

1.620.1 Available under license

1.621 groovy 3.0.8

1.621.1 Available under license

1.622 groovy-json 3.0.8

1.622.1 Available under license

1.623 are-we-there-yet 1.1.7

1.623.1 Available under license

1.624 delaunator 4.0.1

1.624.1 Available under license

1.625 available-typed-arrays 1.0.5

1.625.1 Available under license

1.626 ansi-html-community 0.0.8

1.626.1 Available under license

1.627 ansi-colors 1.1.0

1.627.1 Available under license

1.628 ansi-cyan 0.1.1

1.628.1 Available under license

1.629 arr-map 2.0.2

1.629.1 Available under license

1.630 append-buffer 1.0.2

1.630.1 Available under license

1.631 arr-filter 1.1.2

1.631.1 Available under license

1.632 ansi-red 0.1.1

1.632.1 Available under license

1.633 array-initial 1.1.0

1.633.1 Available under license

1.634 array-last 1.3.0

1.634.1 Available under license

1.635 array-sort 1.0.0

1.635.1 Available under license

1.636 async-done 1.3.2

1.636.1 Available under license

1.637 async-settle 1.0.0

1.637.1 Available under license

1.638 bach 1.2.0

1.638.1 Available under license

1.639 clone-buffer 1.0.0

1.639.1 Available under license

1.640 cloneable-readable 1.1.3

1.640.1 Available under license

1.641 clone-stats 1.0.0

1.641.1 Available under license

1.642 collection-map 1.0.0

1.642.1 Available under license

1.643 default-compare 1.0.0

1.643.1 Available under license

1.644 default-resolution 2.0.0

1.644.1 Available under license

1.645 each-props 1.3.2

1.645.1 Available under license

1.646 fast-levenshtein 1.1.4

1.646.1 Available under license

1.647 find-cache-dir 3.3.2

1.647.1 Available under license

1.648 fs-mkdirp-stream 1.0.0

1.648.1 Available under license

1.649 glob-watcher 5.0.5

1.649.1 Available under license

1.650 is-valid-glob 1.0.0

1.650.1 Available under license

1.651 is-what 3.14.1

1.651.1 Available under license

1.652 last-run 1.1.1

1.652.1 Available under license

1.653 lead 1.0.0

1.653.1 Available under license

1.654 matchdep 2.0.0

1.654.1 Available under license

1.655 mute-stdout 1.0.1

1.655.1 Available under license

1.656 now-and-later 2.0.1

1.656.1 Available under license

1.657 object-reduce 1.0.1

1.657.1 Available under license

1.658 plugin-error 0.1.2

1.658.1 Available under license

1.659 remove-bom-buffer 3.0.0

1.659.1 Available under license

1.660 replace-ext 1.0.1

1.660.1 Available under license

1.661 remove-bom-stream 1.2.0

1.661.1 Available under license

1.662 replace-homedir 1.0.0

1.662.1 Available under license

1.663 resolve-options 1.1.0

1.663.1 Available under license

1.664 semver-greatest-satisfied-range 1.1.0

1.664.1 Available under license

1.665 stream-exhaust 1.0.2

1.665.1 Available under license

1.666 sver-compat 1.5.0

1.666.1 Available under license

1.667 to-through 2.0.0

1.667.1 Available under license

1.668 unicode-canonical-property-names-ecmascript 2.0.0

1.668.1 Available under license

1.669 unicode-match-property-ecmascript 2.0.0

1.669.1 Available under license

1.670 undertaker-registry 1.0.1

1.670.1 Available under license

1.671 undertaker 1.3.0

1.671.1 Available under license

1.672 vinyl-fs 3.0.3

1.672.1 Available under license

1.673 value-or-function 3.0.0

1.673.1 Available under license

1.674 vinyl 2.2.1

1.674.1 Available under license

1.675 vinyl-sourcemap 1.1.0

1.675.1 Available under license

1.676 ansi-align 3.0.1

1.676.1 Available under license

1.677 ip-address 5.3.3

1.677.1 Available under license

1.678 slf4j 1.5.8-PATCHED

1.678.1 Available under license

1.679 xz 1.4

1.679.1 Available under license

1.680 ehcache-core 2.6.10

1.680.1 Available under license

1.681 autoprefixer 9.8.8

1.681.1 Available under license

1.682 fbjs 0.8.18

1.682.1 Available under license

1.683 asn1 0.2.6

1.683.1 Available under license

1.684 postcss 7.0.39

1.684.1 Available under license

1.685 clean-css 4.2.4

1.685.1 Available under license

1.686 swagger-models 2.1.11

1.686.1 Available under license

1.687 snapdragon 0.8.2

1.687.1 Available under license

1.688 rc 1.2.8

1.688.1 Available under license

1.689 strip-json-comments 2.0.1

1.689.1 Available under license

1.690 to-object-path 0.3.0

1.690.1 Available under license

1.691 snapdragon-node 2.1.1

1.691.1 Available under license

1.692 has-value 1.0.0

1.692.1 Available under license

1.693 repeat-element 1.1.4

1.693.1 Available under license

1.694 union-value 1.0.1

1.694.1 Available under license

1.695 source-map-resolve 0.5.3

1.695.1 Available under license

1.696 split-string 3.1.0

1.696.1 Available under license

1.697 json-stable-stringify-without-jsonify 1.0.1

1.697.1 Available under license

1.698 http-proxy 1.18.1

1.698.1 Available under license

1.699 pascalcase 0.1.1

1.699.1 Available under license

1.700 has-values 1.0.0

1.700.1 Available under license

1.701 object-copy 0.1.0

1.701.1 Available under license

1.702 is-extendable 0.1.1

1.702.1 Available under license

1.703 requires-port 1.0.0

1.703.1 Available under license

1.704 map-cache 0.2.2

1.704.1 Available under license

1.705 is-descriptor 0.1.6

1.705.1 Available under license

1.706 mixin-deep 1.3.2

1.706.1 Available under license

1.707 require-directory 2.1.1

1.707.1 Available under license

1.708 posix-character-classes 0.1.1

1.708.1 Available under license

1.709 static-extend 0.1.2

1.709.1 Available under license

1.710 kind-of 6.0.3

1.710.1 Available under license

1.711 object.pick 1.3.0

1.711.1 Available under license

1.712 is-buffer 1.1.6

1.712.1 Available under license

1.713 js-yaml 3.14.1

1.713.1 Available under license

1.714 is-windows 1.0.2

1.714.1 Available under license

1.715 nanomatch 1.2.13

1.715.1 Available under license

1.716 use 3.1.1

1.716.1 Available under license

1.717 is-stream 1.1.0

1.717.1 Available under license

1.718 unset-value 1.0.0

1.718.1 Available under license

1.719 is-data-descriptor 0.1.4

1.719.1 Available under license

1.720 ret 0.1.15

1.720.1 Available under license

1.721 repeat-string 1.6.1

1.721.1 Available under license

1.722 to-regex 3.0.2

1.722.1 Available under license

1.723 micromatch 3.1.10

1.723.1 Available under license

1.724 type-detect 4.0.8

1.724.1 Available under license

1.725 mime 1.6.0

1.725.1 Available under license

1.726 is-accessor-descriptor 0.1.6

1.726.1 Available under license

1.727 object-visit 1.0.1

1.727.1 Available under license

1.728 regex-not 1.0.2

1.728.1 Available under license

1.729 map-visit 1.0.0

1.729.1 Available under license

1.730 set-value 2.0.1

1.730.1 Available under license

1.731 resolve-url 0.2.1

1.731.1 Available under license

1.732 safe-regex 1.1.0

1.732.1 Available under license

1.733 ini 1.3.8

1.733.1 Available under license

1.734 source-map-url 0.4.1

1.734.1 Available under license

1.735 snapdragon-util 3.0.1

1.735.1 Available under license

1.736 urix 0.1.0

1.736.1 Available under license

1.737 tapable 1.1.3

1.737.1 Available under license

1.738 prr 1.0.1

1.738.1 Available under license

1.739 pify 2.3.0

1.739.1 Available under license

1.740 setimmediate 1.0.5

1.740.1 Available under license

1.741 next-tick 1.1.0

1.741.1 Available under license

1.742 lowercase-keys 1.0.1

1.742.1 Available under license

1.743 pify 4.0.1

1.743.1 Available under license

1.744 type 1.2.0

1.744.1 Available under license

1.745 make-dir 2.1.0

1.745.1 Available under license

1.746 worker-farm 1.7.0

1.746.1 Available under license

1.747 buffer-xor 1.0.3

1.747.1 Available under license

1.748 tty-browserify 0.0.0

1.748.1 Available under license

1.749 nth-check 1.0.2

1.749.1 Available under license

1.750 homedir-polyfill 1.0.3

1.750.1 Available under license

1.751 is-relative 1.0.0

1.751.1 Available under license

1.752 parse-filepath 1.0.2

1.752.1 Available under license

1.753 hash.js 1.1.7

1.753.1 Available under license

1.754 array-uniq 1.0.3

1.754.1 Available under license

1.755 https-browserify 1.0.0

1.755.1 Available under license

1.756 console-browserify 1.2.0

1.756.1 Available under license

1.757 create-hmac 1.1.7

1.757.1 Available under license

1.758 path-root-regex 0.1.2

1.758.1 Available under license

1.759 util 0.11.1

1.759.1 Available under license

1.760 ripemd160 2.0.2

1.760.1 Available under license

1.761 detect-file 1.0.0

1.761.1 Available under license

1.762 cssesc 3.0.0

1.762.1 Available under license

1.763 react-lifecycles-compat 3.0.4

1.763.1 Available under license

1.764 object-map 1.0.1

1.764.1 Available under license

1.765 crypto-browserify 3.12.0

1.765.1 Available under license

1.766 parse-json 2.2.0

1.766.1 Available under license

1.767 hmac-drbg 1.0.1

1.767.1 Available under license

1.768 pseudomap 1.0.2

1.768.1 Available under license

1.769 html-loader 0.5.5

1.769.1 Available under license

1.770 sha.js 2.4.11

1.770.1 Available under license

1.771 stream-browserify 2.0.2

1.771.1 Available under license

1.772 upath 1.2.0

1.772.1 Available under license

1.773 glob-parent 3.1.0

1.773.1 Available under license

1.774 vm-browserify 1.1.2

1.774.1 Available under license

1.775 browserify-zlib 0.2.0

1.775.1 Available under license

1.776 block-stream 0.0.9

1.776.1 Available under license

1.777 promise 7.3.1

1.777.1 Available under license

1.778 pinkie-promise 2.0.1

1.778.1 Available under license

1.779 num2fraction 1.2.2

1.779.1 Available under license

1.780 os-browserify 0.3.0

1.780.1 Available under license

1.781 md5.js 1.3.5

1.781.1 Available under license

1.782 rechoir 0.6.2

1.782.1 Available under license

1.783 global-prefix 1.0.2

1.783.1 Available under license

1.784 relateurl 0.2.7

1.784.1 Available under license

1.785 pinkie 2.0.4

1.785.1 Available under license

1.786 miller-rabin 4.0.1

1.786.1 Available under license

1.787 randomfill 1.0.4

1.787.1 Available under license

1.788 normalize-range 0.1.2

1.788.1 Available under license

1.789 buffer 4.9.2

1.789.1 Available under license

1.790 builtin-status-codes 3.0.0

1.790.1 Available under license

1.791 cipher-base 1.0.4

1.791.1 Available under license

1.792 array-slice 1.1.0

1.792.1 Available under license

1.793 constants-browserify 1.0.0

1.793.1 Available under license

1.794 loader-runner 2.4.0

1.794.1 Available under license

1.795 browserify-aes 1.2.0

1.795.1 Available under license

1.796 fastparse 1.1.2

1.796.1 Available under license

1.797 is-unc-path 1.0.0

1.797.1 Available under license

1.798 path-browserify 0.0.1

1.798.1 Available under license

1.799 evp_bytestokey 1.0.3

1.799.1 Available under license

1.800 path-dirname 1.0.2

1.800.1 Available under license

1.801 node-gyp 3.8.0

1.801.1 Available under license

1.802 fined 1.2.0

1.802.1 Available under license

1.803 shallowequal 1.1.0

1.803.1 Available under license

1.804 lower-case 1.1.4

1.804.1 Available under license

1.805 array-each 1.0.1

1.805.1 Available under license

1.806 querystring-es3 0.2.1

1.806.1 Available under license

1.807 minimalistic-assert 1.0.1

1.807.1 Available under license

1.808 global-modules 1.0.0

1.808.1 Available under license

1.809 resolve-dir 1.0.1

1.809.1 Available under license

1.810 object-defaults 1.1.0

1.810.1 Available under license

1.811 to-arraybuffer 1.0.1

1.811.1 Available under license

1.812 ajv-errors 1.0.1

1.812.1 Available under license

1.813 domain-browser 1.2.0

1.813.1 Available under license

1.814 create-hash 1.2.0

1.814.1 Available under license

1.815 stream-http 2.8.3

1.815.1 Available under license

1.816 node-libs-browser 2.2.1

1.816.1 Available under license

1.817 is-absolute 1.0.0

1.817.1 Available under license

1.818 flagged-respawn 1.0.1

1.818.1 Available under license

1.819 ast-types 0.9.6

1.819.1 Available under license

1.820 make-iterator 1.0.1

1.820.1 Available under license

1.821 param-case 2.1.1

1.821.1 Available under license

1.822 expand-tilde 2.0.2

1.822.1 Available under license

1.823 public-encrypt 4.0.3

1.823.1 Available under license

1.824 import-lazy 2.1.0

1.824.1 Available under license

1.825 upper-case 1.1.3

1.825.1 Available under license

1.826 unc-path-regex 0.1.2

1.826.1 Available under license

1.827 es6-templates 0.2.3

1.827.1 Available under license

1.828 brorand 1.1.0

1.828.1 Available under license

1.829 boolbase 1.0.0

1.829.1 Available under license

1.830 recast 0.11.23

1.830.1 Available under license

1.831 browserify-des 1.0.2

1.831.1 Available under license

1.832 private 0.1.8

1.832.1 Available under license

1.833 async-limiter 1.0.1

1.833.1 Available under license

1.834 minimalistic-crypto-utils 1.0.1

1.834.1 Available under license

1.835 nopt 3.0.6

1.835.1 Available under license

1.836 browserify-cipher 1.0.1

1.836.1 Available under license

1.837 path-root 0.1.1

1.837.1 Available under license

1.838 no-case 2.3.2

1.838.1 Available under license

1.839 diffie-hellman 5.0.3

1.839.1 Available under license

1.840 yargs-parser 13.1.2

1.840.1 Available under license

1.841 camel-case 3.0.0

1.841.1 Available under license

1.842 memory-fs 0.4.1

1.842.1 Available under license

1.843 parse-passwd 1.0.0

1.843.1 Available under license

1.844 registry-url 5.1.0

1.844.1 Available under license

1.845 xdg-basedir 4.0.0

1.845.1 Available under license

1.846 widest-line 3.1.0

1.846.1 Available under license

1.847 got 9.6.0

1.847.1 Available under license

1.848 core-js 2.6.12

1.848.1 Available under license

1.849 strict-uri-encode 2.0.0

1.849.1 Available under license

1.850 sindresorhus-is 0.14.0

1.850.1 Available under license

1.851 cli-boxes 2.2.1

1.851.1 Available under license

1.852 cacheable-request 6.1.0

1.852.1 Available under license

1.853 decompress-response 3.3.0

1.853.1 Available under license

1.854 split-on-first 1.1.0

1.854.1 Available under license

1.855 dot-prop 5.3.0

1.855.1 Available under license

1.856 responselike 1.0.2

1.856.1 Available under license

1.857 pako 1.0.11

1.857.1 Available under license

1.858 szmarczak-http-timer 1.1.2

1.858.1 Available under license

1.859 defer-to-connect 1.1.3

1.859.1 Available under license

1.860 is-obj 2.0.0

1.860.1 Available under license

1.861 unique-string 2.0.0

1.861.1 Available under license

1.862 json-buffer 3.0.0

1.862.1 Available under license

1.863 p-cancelable 1.1.0

1.863.1 Available under license

1.864 to-readable-stream 1.0.0

1.864.1 Available under license

1.865 package-json 6.5.0

1.865.1 Available under license

1.866 crypto-random-string 2.0.0

1.866.1 Available under license

1.867 keyv 3.1.0

1.867.1 Available under license

1.868 prepend-http 2.0.0

1.868.1 Available under license

1.869 configstore 5.0.1

1.869.1 Available under license

1.870 url-parse-lax 3.0.0

1.870.1 Available under license

1.871 cacache 12.0.4

1.871.1 Available under license

1.872 interpret 1.4.0

1.872.1 Available under license

1.873 chalk 3.0.0

1.873.1 Available under license

1.874 timers-browserify 2.0.12

1.874.1 Available under license

1.875 webpack-log 2.0.0

1.875.1 Available under license

1.876 asn1.js 5.4.1

1.876.1 Available under license

1.877 parse-asn1 5.1.6

1.877.1 Available under license

1.878 browserify-rsa 4.1.0

1.878.1 Available under license

1.879 hash-base 3.1.0

1.879.1 Available under license

1.880 @emotion/unitless 0.7.5

1.880.1 Available under license

1.881 watchpack 1.7.5

1.881.1 Available under license

1.882 findup-sync 3.0.0

1.882.1 Available under license

1.883 serialize-javascript 4.0.0

1.883.1 Available under license

1.884 value-equal 1.0.1

1.884.1 Available under license

1.885 create-ecdh 4.0.4

1.885.1 Available under license

1.886 babel-eslint 10.1.0

1.886.1 Available under license

1.887 history 4.10.1

1.887.1 Available under license

1.888 resolve-pathname 3.0.0

1.888.1 Available under license

1.889 tiny-warning 1.0.3

1.889.1 Available under license

1.890 resolve-from 3.0.0

1.890.1 Available under license

1.891 schema-utils 2.7.1

1.891.1 Available under license

1.892 css-color-keywords 1.0.0

1.892.1 Available under license

1.893 @emotion/is-prop-valid 0.8.8

1.893.1 Available under license

1.894 @emotion/stylis 0.8.5

1.894.1 Available under license

1.895 @emotion/memoize 0.7.4

1.895.1 Available under license

1.896 just-extend 4.2.1

1.896.1 Available under license

1.897 path-parse 1.0.7

1.897.1 Available under license

1.898 balanced-match 1.0.2

1.898.1 Available under license

1.899 is-fullwidth-code-point 3.0.0

1.899.1 Available under license

1.900 sprintf-js 1.0.3

1.900.1 Available under license

1.901 ansi-regex 5.0.1

1.901.1 Available under license

1.902 find-up 4.1.0

1.902.1 Available under license

1.903 min-document 2.19.0

1.903.1 Available under license

1.904 normalize-path 3.0.0

1.904.1 Available under license

1.905 p-locate 4.1.0

1.905.1 Available under license

1.906 es-to-primitive 1.2.1

1.906.1 Available under license

1.907 xtend 4.0.2

1.907.1 Available under license

1.908 ssri 6.0.2

1.908.1 Available under license

1.909 path-exists 4.0.0

1.909.1 Available under license

1.910 locate-path 5.0.0

1.910.1 Available under license

1.911 mimic-response 1.0.1

1.911.1 Available under license

1.912 has-ansi 2.0.0

1.912.1 Available under license

1.913 object-keys 1.1.1

1.913.1 Available under license

1.914 end-of-stream 1.4.4
1.914.1 Available under license
1.915 global 4.4.0
1.915.1 Available under license
1.916 argparse 1.0.10
1.916.1 Available under license
1.917 string-width 4.2.3
1.917.1 Available under license
1.918 which-boxed-primitive 1.0.2
1.918.1 Available under license
1.919 get-symbol-description 1.0.0
1.919.1 Available under license
1.920 is-date-object 1.0.5
1.920.1 Available under license
1.921 is-string 1.0.7
1.921.1 Available under license
1.922 wrap-ansi 2.1.0
1.922.1 Available under license
1.923 has-tostringtag 1.0.0
1.923.1 Available under license
1.924 is-regex 1.1.4
1.924.1 Available under license
1.925 core-util-is 1.0.3
1.925.1 Available under license
1.926 is-symbol 1.0.4
1.926.1 Available under license
1.927 for-each 0.3.3
1.927.1 Available under license
1.928 get-caller-file 1.0.3
1.928.1 Available under license
1.929 is-boolean-object 1.1.2
1.929.1 Available under license
1.930 is-bigint 1.0.4
1.930.1 Available under license
1.931 tslib 1.14.1
1.931.1 Available under license
1.932 require-main-filename 1.0.1
1.932.1 Available under license
1.933 term-size 2.2.1

1.933.1 Available under license

1.934 boxen 4.2.0

1.934.1 Available under license

1.935 v8flags 3.2.0

1.935.1 Available under license

1.936 liftoff 3.1.0

1.936.1 Available under license

1.937 lazystream 1.0.1

1.937.1 Available under license

1.938 is-negative-zero 2.0.2

1.938.1 Available under license

1.939 is-weakref 1.0.2

1.939.1 Available under license

1.940 snake-yaml 1.21

1.940.1 Available under license

1.941 log4j-api 2.17.1

1.941.1 Available under license

1.942 apache-log4j 2.17.1

1.942.1 Available under license

1.943 log4j-slf4j-impl 2.17.1

1.943.1 Available under license

1.944 chokidar 3.5.3

1.944.1 Available under license

1.945 transform-runtime 0.0.0

1.945.1 Available under license

1.946 redux-logger 4.0.0

1.946.1 Available under license

1.947 babel-plugin-transform-remove-strict-mode 0.0.2

1.947.1 Available under license

1.948 ramda 0.27.2

1.948.1 Available under license

1.949 reflectasm:shaded shaded:1.07

1.949.1 Available under license

1.950 springsource-org-quartz 1.6.0

1.950.1 Available under license

1.951 springframework-core 3.1.3.RELEASE

1.951.1 Available under license

1.952 springframework-asm 3.1.3.RELEASE

1.952.1 Available under license

1.953 springframework-jdbc 3.1.3.RELEASE
1.953.1 Available under license
1.954 spring-framework-beans 3.1.3.RELEASE
1.954.1 Available under license
1.955 springframework-transaction 3.1.3.RELEASE
1.955.1 Available under license
1.956 netty-buffer 4.1.48.Final
1.956.1 Available under license
1.957 source-map-js 1.0.2
1.957.1 Available under license
1.958 netty-codec-socks 4.1.49.Final
1.958.1 Available under license
1.959 netty-codec 4.1.49.Final
1.959.1 Available under license
1.960 netty-transport-native-epoll 4.1.49.Final
1.960.1 Available under license
1.961 netty-handler 4.1.49.Final
1.961.1 Available under license
1.962 netty-transport-native-unix-common 4.1.49.Final
1.962.1 Available under license
1.963 netty-codec-http 4.1.49.Final
1.963.1 Available under license
1.964 netty-transport 4.1.49.Final
1.964.1 Available under license
1.965 netty-resolver 4.1.49.Final
1.965.1 Available under license
1.966 netty-handler-proxy 4.1.49.Final
1.966.1 Available under license
1.967 negotiator 0.6.3
1.967.1 Available under license
1.968 json-path 2.7.0
1.968.1 Available under license
1.969 minimatch 3.1.2
1.969.1 Available under license
1.970 cookie 0.4.2
1.970.1 Available under license
1.971 loadash 1.0.0
1.971.1 Available under license
1.972 react-merge-refs 1.1.0

1.972.1 Available under license

1.973 ansi-regex 4.1.1

1.973.1 Available under license

1.974 debug 4.3.4

1.974.1 Available under license

1.975 sshpk 1.17.0

1.975.1 Available under license

1.976 metrics-servlets 4.1.0

1.976.1 Available under license

1.977 metrics-jetty 4.1.0

1.977.1 Available under license

1.978 metrics-health-checks 4.1.0

1.978.1 Available under license

1.979 is-shared-array-buffer 1.0.2

1.979.1 Available under license

1.980 is-number-object 1.0.7

1.980.1 Available under license

1.981 copy-anything 2.0.6

1.981.1 Available under license

1.982 crc-32 1.2.2

1.982.1 Available under license

1.983 has-property-descriptors 1.0.0

1.983.1 Available under license

1.984 has-bigints 1.0.2

1.984.1 Available under license

1.985 functions-have-names 1.2.3

1.985.1 Available under license

1.986 unbox-primitive 1.0.2

1.986.1 Available under license

1.987 send 0.18.0

1.987.1 Available under license

1.988 globalthis 1.0.3

1.988.1 Available under license

1.989 bn.js 5.2.1

1.989.1 Available under license

1.990 async 3.2.4

1.990.1 Available under license

1.991 resilience4j-circuitbreaker 1.7.1

1.991.1 Available under license

1.992 resilience4j-core 1.7.1

1.992.1 Available under license

1.993 jaeger-thrift 0.28.0

1.993.1 Available under license

1.994 jaeger-core 0.28.0

1.994.1 Available under license

1.995 jackson-datatype-hibernate 2.12.7

1.995.1 Available under license

1.996 registry-auth-token 4.2.2

1.996.1 Available under license

1.997 qs 6.11.0

1.997.1 Available under license

1.998 babel-plugin-proposal-nullish-coalescing-operator 7.18.6

1.998.1 Available under license

1.999 @babel/plugin-proposal-json-strings 7.18.6

1.999.1 Available under license

1.1000 clone-response 1.0.3

1.1000.1 Available under license

1.1001 @sinonjs/text-encoding 0.7.2

1.1001.1 Available under license

1.1002 es5-ext 0.10.62

1.1002.1 Available under license

1.1003 type 2.7.2

1.1003.1 Available under license

1.1004 object.assign 4.1.4

1.1004.1 Available under license

1.1005 jackson-annotations 2.12.7

1.1005.1 Available under license

1.1006 jackson-dataformat-yaml 2.12.7

1.1006.1 Available under license

1.1007 jackson-dataformat-smile 2.12.7

1.1007.1 Available under license

1.1008 jackson-jaxrs 2.12.7

1.1008.1 Available under license

1.1009 jackson-dataformat-xml 2.12.7

1.1009.1 Available under license

1.1010 jackson-module-jsonschema 2.12.7

1.1010.1 Available under license

1.1011 jackson-xc 2.12.7

1.1011.1 Available under license

1.1012 jackson-jaxrs-base 2.12.7

1.1012.1 Available under license

1.1013 ext 1.7.0

1.1013.1 Available under license

1.1014 follow-redirects 1.15.2

1.1014.1 Available under license

1.1015 regjsparser 0.9.1

1.1015.1 Available under license

1.1016 unicode-property-aliases-ecmascript 2.1.0

1.1016.1 Available under license

1.1017 spring-instrument 4.3.20.RELEASE

1.1017.1 Available under license

1.1018 logback-core 1.2.9

1.1018.1 Available under license

1.1019 logback-classic 1.2.9

1.1019.1 Available under license

1.1020 underscore 1.13.6

1.1020.1 Available under license

1.1021 he 1.2.0

1.1021.1 Available under license

1.1022 emoji-regex 8.0.0

1.1022.1 Available under license

1.1023 d3-interpolate 2.0.1

1.1023.1 Available under license

1.1024 d3-color 2.0.0

1.1024.1 Available under license

1.1025 d3-array 2.12.1

1.1025.1 Available under license

1.1026 react-dom 17.0.2

1.1026.1 Available under license

1.1027 d3-shape 2.1.0

1.1027.1 Available under license

1.1028 d3-scale-chromatic 2.0.0

1.1028.1 Available under license

1.1029 d3-time 2.1.1

1.1029.1 Available under license

1.1030 coffee-script 1.12.7

1.1030.1 Available under license

1.1031 filesize 3.6.1

1.1031.1 Available under license

1.1032 d3-scale 3.3.0

1.1032.1 Available under license

1.1033 d3-time-format 3.0.0

1.1033.1 Available under license

1.1034 d3-path 2.0.0

1.1034.1 Available under license

1.1035 lodash-es 4.17.21

1.1035.1 Available under license

1.1036 redux 3.7.2

1.1036.1 Available under license

1.1037 convert-source-map 1.9.0

1.1037.1 Available under license

1.1038 base 0.11.2

1.1038.1 Available under license

1.1039 codepage 1.15.0

1.1039.1 Available under license

1.1040 adler-32 1.2.0

1.1040.1 Available under license

1.1041 cfb 1.2.2

1.1041.1 Available under license

1.1042 frac 1.1.2

1.1042.1 Available under license

1.1043 react-router-dom 5.3.4

1.1043.1 Available under license

1.1044 tiny-invariant 1.3.1

1.1044.1 Available under license

1.1045 react-router 5.3.4

1.1045.1 Available under license

1.1046 d3-force 2.1.1

1.1046.1 Available under license

1.1047 d3-timer 2.0.0

1.1047.1 Available under license

1.1048 d3-dispatch 2.0.0

1.1048.1 Available under license

1.1049 d3-quadtree 2.0.0

1.1049.1 Available under license

1.1050 amdi18n-loader 0.9.4

1.1050.1 Available under license

1.1051 babel-loader 8.3.0

1.1051.1 Available under license

1.1052 regenerator-runtime 0.13.11

1.1052.1 Available under license

1.1053 apache-commons-text 1.10.0

1.1053.1 Available under license

1.1054 xlsx 0.17.5

1.1054.1 Available under license

1.1055 d3-fetch 2.0.0

1.1055.1 Available under license

1.1056 d3-zoom 2.0.0

1.1056.1 Available under license

1.1057 d3-brush 2.1.0

1.1057.1 Available under license

1.1058 d3-hierarchy 2.0.0

1.1058.1 Available under license

1.1059 d3-random 2.2.2

1.1059.1 Available under license

1.1060 d3-selection 2.0.0

1.1060.1 Available under license

1.1061 d3-transition 2.0.0

1.1061.1 Available under license

1.1062 d3-polygon 2.0.0

1.1062.1 Available under license

1.1063 d3-axis 2.1.0

1.1063.1 Available under license

1.1064 d3-geo 2.0.2

1.1064.1 Available under license

1.1065 d3-dsv 2.0.0

1.1065.1 Available under license

1.1066 d3 6.7.0

1.1066.1 Available under license

1.1067 d3-chord 2.0.0

1.1067.1 Available under license

1.1068 d3-ease 2.0.0

1.1068.1 Available under license

1.1069 d3-drag 2.0.0

1.1069.1 Available under license

1.1070 d3-contour 2.0.0

1.1070.1 Available under license

1.1071 d3-format 2.0.0

1.1071.1 Available under license

1.1072 loader-utils 1.4.2

1.1072.1 Available under license

1.1073 camelize 1.0.1

1.1073.1 Available under license

1.1074 safe-regex-test 1.0.0

1.1074.1 Available under license

1.1075 is-callable 1.2.7

1.1075.1 Available under license

1.1076 react-redux 7.2.9

1.1076.1 Available under license

1.1077 unicode-match-property-value-ecmascript 2.1.0

1.1077.1 Available under license

1.1078 @sinonjs/commons 1.8.6

1.1078.1 Available under license

1.1079 redux-thunk 2.4.2

1.1079.1 Available under license

1.1080 decode-uri-component 0.2.2

1.1080.1 Available under license

1.1081 styled-components 4.4.1

1.1081.1 Available under license

1.1082 dna-ui-utils 1.0.29

1.1082.1 Available under license

1.1083 react-list 0.8.17

1.1083.1 Available under license

1.1084 yargs 7.1.2

1.1084.1 Available under license

1.1085 less 3.13.1

1.1085.1 Available under license

1.1086 jackson-databind 2.12.7.1

1.1086.1 Available under license

1.1087 query-string 7.1.3

1.1087.1 Available under license

1.1088 json5 2.2.3

1.1088.1 Available under license

1.1089 regenerate 1.4.2

1.1089.1 Available under license

1.1090 typedarray-to-buffer 3.1.5

1.1090.1 Available under license

1.1091 react-is 16.13.1

1.1091.1 Available under license

1.1092 scheduler 0.20.2

1.1092.1 Available under license

1.1093 typed-array-length 1.0.4

1.1093.1 Available under license

1.1094 es-set-tostringtag 2.0.1

1.1094.1 Available under license

1.1095 camel-api 3.8.0

1.1095.1 Available under license

1.1096 camel-base 3.8.0

1.1096.1 Available under license

1.1097 camel-base-engine 3.8.0

1.1097.1 Available under license

1.1098 camel-core-engine 3.8.0

1.1098.1 Available under license

1.1099 camel-core-model 3.8.0

1.1099.1 Available under license

1.1100 camel-core-processor 3.8.0

1.1100.1 Available under license

1.1101 camel-core-reifier 3.8.0

1.1101.1 Available under license

1.1102 camel-endpointdsl 3.8.0

1.1102.1 Available under license

1.1103 camel-management-api 3.8.0

1.1103.1 Available under license

1.1104 camel-rabbitmq 3.8.0

1.1104.1 Available under license

1.1105 camel-support 3.8.0

1.1105.1 Available under license

1.1106 camel-util 3.8.0

1.1106.1 Available under license

1.1107 printj 1.1.2

1.1107.1 Available under license

1.1108 punycode 2.3.0

1.1108.1 Available under license

1.1109 http-cache-semantics 4.1.1

1.1109.1 Available under license

1.1110 jackson-datatype-jsr310 2.12.7

1.1110.1 Available under license

1.1111 ssf 0.11.2

1.1111.1 Available under license

1.1112 wmf 1.0.2

1.1112.1 Available under license

1.1113 internal-slot 1.0.5

1.1113.1 Available under license

1.1114 minimist 1.2.8

1.1114.1 Available under license

1.1115 babel-plugin-proposal-optional-chaining 7.21.0

1.1115.1 Available under license

1.1116 is-array-buffer 3.0.2

1.1116.1 Available under license

1.1117 css-to-react-native 3.2.0

1.1117.1 Available under license

1.1118 classmate 1.0.0

1.1118.1 Available under license

1.1119 spdx-correct 3.2.0

1.1119.1 Available under license

1.1120 checker-qual 3.31.0

1.1120.1 Available under license

1.1121 spdx-license-ids 3.0.13

1.1121.1 Available under license

1.1122 handlebars-loader 1.7.3

1.1122.1 Available under license

1.1123 regexpu-core 5.3.2

1.1123.1 Available under license

1.1124 array-buffer-byte-length 1.0.0

1.1124.1 Available under license

1.1125 grpc-protobuf 1.9.0

1.1125.1 Available under license

1.1126 grpc-netty 1.9.0

1.1126.1 Available under license

1.1127 uuid-creator 5.2.0

1.1127.1 Available under license

1.1128 update-browserslist-db 1.0.11

1.1128.1 Available under license

1.1129 immutability-helper 3.1.1

1.1129.1 Available under license

1.1130 date-fns 2.30.0

1.1130.1 Available under license

1.1131 postcss-selector-parser 6.0.13

1.1131.1 Available under license

1.1132 postgre-sql 42.6.0

1.1132.1 Available under license

1.1133 resilience4j-ratelimiter 1.7.1

1.1133.1 Available under license

1.1134 babel-plugin-syntax-flow 7.22.5

1.1134.1 Available under license

1.1135 babel-plugin-transform-property-literals 7.22.5

1.1135.1 Available under license

1.1136 babel-plugin-transform-reserved-words 7.22.5

1.1136.1 Available under license

1.1137 babel-plugin-syntax-typescript 7.22.5

1.1137.1 Available under license

1.1138 babel-plugin-transform-member-expression-literals 7.22.5

1.1138.1 Available under license

1.1139 babel-plugin-transform-flow-strip-types 7.22.5

1.1139.1 Available under license

1.1140 html-entities 2.4.0

1.1140.1 Available under license

1.1141 semver 5.7.2

1.1141.1 Available under license

1.1142 typed-array-byte-offset 1.0.0

1.1142.1 Available under license

1.1143 babel-plugin-styled-components 2.1.4

1.1143.1 Available under license

1.1144 styled-components 5.3.11

1.1144.1 Available under license

1.1145 semver 6.3.1

1.1145.1 Available under license

1.1146 is-typed-array 1.1.12

1.1146.1 Available under license

1.1147 which-typed-array 1.1.11

1.1147.1 Available under license

1.1148 typed-array-byte-length 1.0.0

1.1148.1 Available under license

1.1149 typed-array-buffer 1.0.0

1.1149.1 Available under license

1.1150 browserslist 4.21.10

1.1150.1 Available under license

1.1151 webpack-hot-middleware 2.25.4

1.1151.1 Available under license

1.1152 is-core-module 2.13.0

1.1152.1 Available under license

1.1153 @babel/plugin-transform-regenerator 7.22.10

1.1153.1 Available under license

1.1154 @babel/plugin-transform-unicode-escapes 7.22.10

1.1154.1 Available under license

1.1155 @babel/preset-modules 0.1.6-no-external-plugins

1.1155.1 Available under license

1.1156 regenerator-transform 0.15.2

1.1156.1 Available under license

1.1157 babel-plugin-syntax-decorators 7.22.10

1.1157.1 Available under license

1.1158 handlebarsjs 4.7.8

1.1158.1 Available under license

1.1159 @babel/plugin-transform-dynamic-import 7.22.11

1.1159.1 Available under license

1.1160 @babel/plugin-transform-nullish-coalescing-operator 7.22.11

1.1160.1 Available under license

1.1161 @babel/plugin-transform-export-namespace-from 7.22.11

1.1161.1 Available under license

1.1162 @babel/plugin-transform-json-strings 7.22.11

1.1162.1 Available under license

1.1163 @babel/plugin-transform-optional-catch-binding 7.22.11

1.1163.1 Available under license

1.1164 @babel/plugin-transform-class-static-block 7.22.11

1.1164.1 Available under license

1.1165 @babel/plugin-transform-private-property-in-object 7.22.11

1.1165.1 Available under license

1.1166 @babel/plugin-transform-numeric-separator 7.22.11

1.1166.1 Available under license

1.1167 @babel/plugin-transform-logical-assignment-operators 7.22.11

1.1167.1 Available under license

1.1168 @babel/highlight 7.22.13

1.1168.1 Available under license

1.1169 object.entries 1.1.7

1.1169.1 Available under license

1.1170 function.prototype.name 1.1.6

1.1170.1 Available under license

1.1171 string-prototype-trimstart 1.0.7

1.1171.1 Available under license

1.1172 @babel/helpers 7.22.15

1.1172.1 Available under license

1.1173 @babel/generator 7.22.15

1.1173.1 Available under license

1.1174 @babel/plugin-transform-classes 7.22.15

1.1174.1 Available under license

1.1175 @babel/plugin-bugfix-safari-id-destructuring-collision-in-function-expression 7.22.15

1.1175.1 Available under license

1.1176 @babel/plugin-transform-react-jsx 7.22.15

1.1176.1 Available under license

1.1177 @babel/plugin-transform-modules-commonjs 7.22.15

1.1177.1 Available under license

1.1178 @babel/plugin-transform-for-of 7.22.15

1.1178.1 Available under license

1.1179 babel-helper-create-class-features-plugin 7.22.15

1.1179.1 Available under license

1.1180 @babel/plugin-transform-parameters 7.22.15

1.1180.1 Available under license

1.1181 @babel/plugin-transform-object-rest-spread 7.22.15

1.1181.1 Available under license

1.1182 babel-preset-typescript 7.22.15

1.1182.1 Available under license

1.1183 @babel/helper-member-expression-to-functions 7.22.15

1.1183.1 Available under license

1.1184 babel-helper-create-regexp-features-plugin 7.22.15

1.1184.1 Available under license

1.1185 babel-plugin-transform-typescript 7.22.15

1.1185.1 Available under license

1.1186 @babel/helper-builder-binary-assignment-operator-visitor 7.22.15

1.1186.1 Available under license

1.1187 @babel/plugin-bugfix-v8-spread-parameters-in-optional-chaining 7.22.15

1.1187.1 Available under license

1.1188 immutable 4.3.4

1.1188.1 Available under license

1.1189 arraybuffer.prototype.slice 1.0.2

1.1189.1 Available under license

1.1190 safe-array-concat 1.0.1

1.1190.1 Available under license

1.1191 @babel/parser 7.22.16

1.1191.1 Available under license

1.1192 string-prototype-trim 1.2.8

1.1192.1 Available under license

1.1193 string-prototype-trimend 1.0.7

1.1193.1 Available under license

1.1194 cookie 0.5.0

1.1194.1 Available under license

1.1195 debounce 1.2.1

1.1195.1 Available under license

1.1196 @babel/plugin-syntax-class-properties 7.12.13

1.1196.1 Available under license

1.1197 @babel/plugin-syntax-async-generators 7.8.4

1.1197.1 Available under license

1.1198 @babel/plugin-syntax-optional-catch-binding 7.8.3

1.1198.1 Available under license

1.1199 @babel/plugin-syntax-numeric-separator 7.10.4

1.1199.1 Available under license

1.1200 @babel/plugin-syntax-logical-assignment-operators 7.10.4

1.1200.1 Available under license

1.1201 @babel/plugin-syntax-json-strings 7.8.3

1.1201.1 Available under license

1.1202 @babel/plugin-syntax-import-meta 7.10.4

1.1202.1 Available under license

1.1203 @babel/plugin-syntax-object-rest-spread 7.8.3

1.1203.1 Available under license

1.1204 node-fetch 1.7.3

1.1204.1 Available under license

1.1205 @babel/plugin-proposal-private-methods 7.18.6

1.1205.1 Available under license

1.1206 @babel/plugin-syntax-private-property-in-object 7.14.5

1.1206.1 Available under license

1.1207 @babel/plugin-proposal-class-properties 7.18.6

1.1207.1 Available under license

1.1208 @babel/plugin-proposal-numeric-separator 7.18.6

1.1208.1 Available under license

1.1209 @babel/plugin-syntax-class-static-block 7.14.5

1.1209.1 Available under license

1.1210 @babel/regjsgen 0.8.0

1.1210.1 Available under license

1.1211 @babel/plugin-transform-spread 7.22.5

1.1211.1 Available under license

1.1212 @babel/plugin-transform-template-literals 7.22.5

1.1212.1 Available under license

1.1213 @babel/plugin-transform-computed-properties 7.22.5

1.1213.1 Available under license

1.1214 @babel/plugin-transform-arrow-functions 7.22.5

1.1214.1 Available under license

1.1215 @babel/helper-optimise-call-expression 7.22.5

1.1215.1 Available under license

1.1216 @babel/plugin-transform-shorthand-properties 7.22.5

1.1216.1 Available under license

1.1217 @babel/plugin-transform-sticky-regex 7.22.5

1.1217.1 Available under license

1.1218 @babel/helper-skip-transparent-expression-wrappers 7.22.5

1.1218.1 Available under license

1.1219 @babel/plugin-transform-dotall-regex 7.22.5

1.1219.1 Available under license

1.1220 @babel/plugin-transform-async-to-generator 7.22.5

1.1220.1 Available under license

1.1221 @babel/helper-annotate-as-pure 7.22.5

1.1221.1 Available under license

1.1222 @babel/plugin-syntax-jsx 7.22.5

1.1222.1 Available under license

1.1223 @babel/plugin-syntax-import-attributes 7.22.5

1.1223.1 Available under license

1.1224 @babel/plugin-transform-unicode-regex 7.22.5

1.1224.1 Available under license

1.1225 @babel/plugin-transform-exponentiation-operator 7.22.5

1.1225.1 Available under license

1.1226 @babel/plugin-transform-class-properties 7.22.5

1.1226.1 Available under license

1.1227 @babel/plugin-transform-modules-umd 7.22.5

1.1227.1 Available under license

1.1228 @babel/helper-environment-visitor 7.22.5

1.1228.1 Available under license

1.1229 @babel/plugin-transform-function-name 7.22.5

1.1229.1 Available under license

1.1230 @babel/plugin-transform-literals 7.22.5

1.1230.1 Available under license

1.1231 @babel/plugin-transform-react-display-name 7.22.5

1.1231.1 Available under license

1.1232 @babel/plugin-transform-unicode-sets-regex 7.22.5

1.1232.1 Available under license

1.1233 @babel/plugin-transform-duplicate-keys 7.22.5

1.1233.1 Available under license

1.1234 @babel/plugin-transform-object-super 7.22.5

1.1234.1 Available under license

1.1235 @babel/helper-function-name 7.22.5

1.1235.1 Available under license

1.1236 @babel/plugin-transform-named-capturing-groups-regex 7.22.5

1.1236.1 Available under license

1.1237 @babel/plugin-syntax-unicode-sets-regex 7.18.6

1.1237.1 Available under license

1.1238 @babel/plugin-syntax-import-assertions 7.22.5

1.1238.1 Available under license

1.1239 @babel/plugin-transform-typeof-symbol 7.22.5

1.1239.1 Available under license

1.1240 @babel/compat-data 7.22.9

1.1240.1 Available under license

1.1241 @babel/plugin-transform-new-target 7.22.5

1.1241.1 Available under license

1.1242 @babel/helper-replace-supers 7.22.9

1.1242.1 Available under license

1.1243 @babel/plugin-transform-block-scoped-functions 7.22.5

1.1243.1 Available under license

1.1244 @babel/plugin-transform-unicode-property-regex 7.22.5

1.1244.1 Available under license

1.1245 @babel/plugin-transform-private-methods 7.22.5

1.1245.1 Available under license

1.1246 nan 2.18.0

1.1246.1 Available under license

1.1247 @babel/plugin-transform-react-jsx-development 7.22.5

1.1247.1 Available under license

1.1248 @babel/plugin-transform-react-pure-annotations 7.22.5

1.1248.1 Available under license

1.1249 regexp-prototype-flags 1.5.1

1.1249.1 Available under license

1.1250 define-properties 1.2.1

1.1250.1 Available under license

1.1251 define-data-property 1.1.0

1.1251.1 Available under license

1.1252 set-function-name 2.0.1

1.1252.1 Available under license

1.1253 @babel/types 7.22.19

1.1253.1 Available under license

1.1254 regenerate-unicode-properties 10.1.1

1.1254.1 Available under license

1.1255 sass 1.67.0

1.1255.1 Available under license

1.1256 es-abstract 1.22.2

1.1256.1 Available under license

1.1257 types-json-schema 7.0.13

1.1257.1 Available under license

1.1258 @babel/helper-remap-async-to-generator 7.22.20

1.1258.1 Available under license

1.1259 @babel/helper-member-expression-to-functions 7.23.0

1.1259.1 Available under license

1.1260 @babel/helper-wrap-function 7.22.20

1.1260.1 Available under license

1.1261 @babel/helper-replace-supers 7.22.20

1.1261.1 Available under license

1.1262 @babel/preset-react 7.22.15

1.1262.1 Available under license

1.1263 stax-api 4.2.1

1.1263.1 Available under license

1.1264 log4javascript 1.4.16

1.1264.1 Available under license

1.1265 atob 2.1.2

1.1265.1 Available under license

1.1266 ajv 6.12.6

1.1266.1 Available under license

1.1267 express 4.18.2

1.1267.1 Available under license

1.1268 node-fetch 2.7.0

1.1268.1 Available under license

1.1269 ramda 0.28.0

1.1269.1 Available under license

1.1270 webpack 4.47.0

1.1270.1 Available under license

1.1271 merge 1.2.1

1.1271.1 Available under license

1.1272 y18n 4.0.3

1.1272.1 Available under license

1.1273 terser 4.8.1

1.1273.1 Available under license

1.1274 netmask 2.0.2

1.1274.1 Available under license

1.1275 hoek 2.16.3

1.1275.1 Available under license

1.1276 html-minifier 3.5.21

1.1276.1 Available under license

1.1277 is-svg 2.1.0

1.1277.1 Available under license

1.1278 color-string 0.3.0

1.1278.1 Available under license

1.1279 combined-stream 1.0.8

1.1279.1 Available under license

1.1280 delayed-stream 1.0.0

1.1280.1 Available under license

1.1281 ansi-styles 3.2.1

1.1281.1 Available under license

1.1282 side-channel 1.0.4

1.1282.1 Available under license

1.1283 function-bind 1.1.1

1.1283.1 Available under license

1.1284 gensync 1.0.0-beta.2

1.1284.1 Available under license

1.1285 js-tokens 4.0.0

1.1285.1 Available under license

1.1286 @jridgewell/set-array 1.1.2

1.1286.1 Available under license

1.1287 globals 11.12.0

1.1287.1 Available under license

1.1288 has-flag 3.0.0

1.1288.1 Available under license

1.1289 has-proto 1.0.1

1.1289.1 Available under license

1.1290 escape-string-regexp 1.0.5

1.1290.1 Available under license

1.1291 raw-body 2.5.1

1.1291.1 Available under license

1.1292 object-inspect 1.12.3

1.1292.1 Available under license

1.1293 isobject 3.0.1

1.1293.1 Available under license

1.1294 array-flatten 1.1.1

1.1294.1 Available under license

1.1295 utils-merge 1.0.1

1.1295.1 Available under license

1.1296 yallist 3.1.1

1.1296.1 Available under license

1.1297 ee-first 1.1.1

1.1297.1 Available under license

1.1298 is-plain-object 2.0.4

1.1298.1 Available under license

1.1299 chalk 2.4.2

1.1299.1 Available under license

1.1300 depd 2.0.0

1.1300.1 Available under license

1.1301 to-fast-properties 2.0.0

1.1301.1 Available under license

1.1302 object-assign 4.1.1

1.1302.1 Available under license

1.1303 call-bind 1.0.2

1.1303.1 Available under license

1.1304 @babel/helper-validator-identifier 7.22.20

1.1304.1 Available under license

1.1305 @babel/code-frame 7.22.13

1.1305.1 Available under license

1.1306 get-intrinsic 1.2.1

1.1306.1 Available under license

1.1307 loose-envify 1.4.0

1.1307.1 Available under license

1.1308 node-releases 2.0.13

1.1308.1 Available under license

1.1309 @babel/helper-environment-visitor 7.22.20

1.1309.1 Available under license

1.1310 @jridgewell/gen-mapping 0.3.3

1.1310.1 Available under license

1.1311 @ampproject/remapping 2.2.1

1.1311.1 Available under license

1.1312 @babel/helper-simple-access 7.22.5

1.1312.1 Available under license

1.1313 @babel/helper-split-export-declaration 7.22.6

1.1313.1 Available under license

1.1314 babel-helper-compilation-targets 7.22.15

1.1314.1 Available under license

1.1315 @jridgewell/resolve-uri 3.1.1

1.1315.1 Available under license

1.1316 @jridgewell/sourcemap-codec 1.4.15

1.1316.1 Available under license

1.1317 @babel/helper-function-name 7.23.0

1.1317.1 Available under license

1.1318 @babel/helper-validator-option 7.22.15

1.1318.1 Available under license

1.1319 @babel/helper-string-parser 7.22.5

1.1319.1 Available under license

1.1320 convert-source-map 2.0.0

1.1320.1 Available under license

1.1321 @babel/helper-module-imports 7.22.15

1.1321.1 Available under license

1.1322 @babel/helper-hoist-variables 7.22.5

1.1322.1 Available under license

1.1323 @babel/template 7.22.15

1.1323.1 Available under license

1.1324 @babel/plugin-proposal-export-namespace-from 7.18.9

1.1324.1 Available under license

1.1325 @babel/plugin-syntax-export-namespace-from 7.8.3

1.1325.1 Available under license

1.1326 @babel/plugin-syntax-dynamic-import 7.8.3

1.1326.1 Available under license

1.1327 prop-types 15.8.1

1.1327.1 Available under license

1.1328 @babel/helper-plugin-utils 7.22.5

1.1328.1 Available under license

1.1329 word 0.3.0

1.1329.1 Available under license

1.1330 @jridgewell/trace-mapping 0.3.19

1.1330.1 Available under license

1.1331 emojis-list 3.0.0

1.1331.1 Available under license

1.1332 @types/prop-types 15.7.5

1.1332.1 Available under license

1.1333 @babel/runtime 7.22.15

1.1333.1 Available under license

1.1334 csstype 3.1.2

1.1334.1 Available under license

1.1335 fresh 0.5.2

1.1335.1 Available under license

1.1336 types-hoist-non-react-statics 3.3.1

1.1336.1 Available under license

1.1337 ua-parser-js 0.7.36

1.1337.1 Available under license

1.1338 @emotion/memoize 0.8.1

1.1338.1 Available under license

1.1339 asynckit 0.4.0

1.1339.1 Available under license

1.1340 supports-color 5.5.0

1.1340.1 Available under license

1.1341 function-bind 1.1.2

1.1341.1 Available under license

1.1342 janino 2.6.1

1.1342.1 Available under license

1.1343 punycode 2.3.1

1.1343.1 Available under license

1.1344 jackson-jaxrs-xml-provider 2.12.7

1.1344.1 Available under license

1.1345 amqp-client 4.12.0

1.1345.1 Available under license

1.1346 resolver 1.2.0

1.1346.1 Available under license

1.1347 spring-amqp 1.7.15.RELEASE

1.1347.1 Available under license

1.1348 spring-rabbit 1.7.15.RELEASE

1.1348.1 Available under license

1.1349 transaction 1.1.0

1.1349.1 Available under license

1.1350 node-sass 4.14.1

1.1350.1 Available under license

1.1351 copy-props 2.0.5

1.1351.1 Available under license

1.1352 json-schema 0.2.5

1.1352.1 Available under license

1.1353 yargs-parser 5.0.1

1.1353.1 Available under license

1.1354 async 3.2.5

1.1354.1 Available under license

1.1355 @babel/plugin-syntax-jsx 7.23.3

1.1355.1 Available under license

1.1356 @babel/helper-module-transforms 7.23.3

1.1356.1 Available under license

1.1357 babel-plugin-syntax-typescript 7.23.3

1.1357.1 Available under license

1.1358 babel-preset-typescript 7.23.3

1.1358.1 Available under license

1.1359 @babel/plugin-transform-react-display-name 7.23.3

1.1359.1 Available under license

1.1360 @babel/plugin-transform-modules-commonjs 7.23.3

1.1360.1 Available under license

1.1361 @babel/helper-string-parser 7.23.4

1.1361.1 Available under license

1.1362 @babel/highlight 7.23.4

1.1362.1 Available under license

1.1363 component-emitter 1.3.1

1.1363.1 Available under license

1.1364 react-window 1.8.10

1.1364.1 Available under license

1.1365 @babel/plugin-transform-private-property-in-object 7.23.4

1.1365.1 Available under license

1.1366 @babel/plugin-transform-class-properties 7.23.3

1.1366.1 Available under license

1.1367 @babel/plugin-syntax-import-assertions 7.23.3

1.1367.1 Available under license

1.1368 @babel/plugin-bugfix-safari-id-destructuring-collision-in-function-expression 7.23.3

1.1368.1 Available under license

1.1369 @babel/plugin-transform-optional-catch-binding 7.23.4

1.1369.1 Available under license

1.1370 @babel/plugin-transform-destructuring 7.23.3

1.1370.1 Available under license

1.1371 @babel/plugin-transform-sticky-regex 7.23.3

1.1371.1 Available under license

1.1372 @babel/plugin-transform-unicode-property-regex 7.23.3

1.1372.1 Available under license

1.1373 @babel/plugin-transform-logical-assignment-operators 7.23.4

1.1373.1 Available under license

1.1374 @babel/plugin-bugfix-v8-spread-parameters-in-optional-chaining 7.23.3

1.1374.1 Available under license

1.1375 @babel/plugin-transform-react-jsx 7.23.4

1.1375.1 Available under license

1.1376 @babel/plugin-transform-exponentiation-operator 7.23.3

1.1376.1 Available under license

1.1377 @babel/plugin-transform-modules-umd 7.23.3

1.1377.1 Available under license

1.1378 @babel/plugin-transform-export-namespace-from 7.23.4

1.1378.1 Available under license

1.1379 babel-plugin-transform-member-expression-literals 7.23.3

1.1379.1 Available under license

1.1380 @babel/plugin-transform-class-static-block 7.23.4

1.1380.1 Available under license

1.1381 @babel/plugin-transform-optional-chaining 7.23.4

1.1381.1 Available under license

1.1382 @babel/plugin-transform-nullish-coalescing-operator 7.23.4

1.1382.1 Available under license

1.1383 @babel/plugin-transform-shorthand-properties 7.23.3

1.1383.1 Available under license

1.1384 babel-plugin-transform-property-literals 7.23.3

1.1384.1 Available under license

1.1385 @babel/plugin-transform-block-scoped-functions 7.23.3

1.1385.1 Available under license

1.1386 @babel/plugin-transform-template-literals 7.23.3

1.1386.1 Available under license

1.1387 @babel/plugin-transform-parameters 7.23.3

1.1387.1 Available under license

1.1388 @babel/plugin-transform-new-target 7.23.3

1.1388.1 Available under license

1.1389 @babel/plugin-transform-unicode-sets-regex 7.23.3

1.1389.1 Available under license

1.1390 @babel/plugin-syntax-import-attributes 7.23.3

1.1390.1 Available under license

1.1391 @babel/plugin-transform-unicode-escapes 7.23.3

1.1391.1 Available under license

1.1392 @babel/plugin-transform-arrow-functions 7.23.3

1.1392.1 Available under license

1.1393 @babel/plugin-transform-async-to-generator 7.23.3

1.1393.1 Available under license

1.1394 @babel/plugin-transform-unicode-regex 7.23.3

1.1394.1 Available under license

1.1395 @babel/plugin-transform-modules-amd 7.23.3

1.1395.1 Available under license

1.1396 @babel/plugin-transform-computed-properties 7.23.3

1.1396.1 Available under license

1.1397 @babel/plugin-transform-spread 7.23.3

1.1397.1 Available under license

1.1398 @babel/plugin-transform-literals 7.23.3

1.1398.1 Available under license

1.1399 @babel/plugin-transform-typeof-symbol 7.23.3

1.1399.1 Available under license

1.1400 @babel/plugin-transform-dynamic-import 7.23.4

1.1400.1 Available under license

1.1401 @babel/plugin-transform-object-super 7.23.3

1.1401.1 Available under license

1.1402 @babel/plugin-transform-duplicate-keys 7.23.3

1.1402.1 Available under license

1.1403 @babel/plugin-transform-dotall-regex 7.23.3

1.1403.1 Available under license

1.1404 babel-plugin-transform-reserved-words 7.23.3

1.1404.1 Available under license

1.1405 @babel/plugin-transform-numeric-separator 7.23.4

1.1405.1 Available under license

1.1406 @babel/plugin-transform-function-name 7.23.3

1.1406.1 Available under license

1.1407 @babel/plugin-transform-private-methods 7.23.3

1.1407.1 Available under license

1.1408 @babel/plugin-transform-block-scoping 7.23.4

1.1408.1 Available under license

1.1409 @babel/plugin-transform-regenerator 7.23.3

1.1409.1 Available under license

1.1410 @babel/plugin-transform-json-strings 7.23.4

1.1410.1 Available under license

1.1411 validation 1.0.0.GA

1.1411.1 Available under license

1.1412 @babel/helper-validator-option 7.23.5

1.1412.1 Available under license

1.1413 @babel/compat-data 7.23.5

1.1413.1 Available under license

1.1414 @babel/code-frame 7.23.5

1.1414.1 Available under license

1.1415 @babel/preset-react 7.23.3

1.1415.1 Available under license

1.1416 @babel/plugin-transform-react-pure-annotations 7.23.3

1.1416.1 Available under license

1.1417 object.assign 4.1.5

1.1417.1 Available under license

1.1418 netty-transport-native-epoll:linux-x86_64 linux-x86_64:4.1.49.Final

1.1418.1 Available under license

1.1419 ua-parser-js 0.7.37

1.1419.1 Available under license

1.1420 figlet 1.7.0

1.1420.1 Available under license

1.1421 babel-helper-compilation-targets 7.23.6

1.1421.1 Available under license

1.1422 @babel/generator 7.23.6

1.1422.1 Available under license

1.1423 @babel/plugin-transform-for-of 7.23.6

1.1423.1 Available under license

1.1424 babel-plugin-transform-typescript 7.23.6

1.1424.1 Available under license

1.1425 whatwg-fetch 3.6.20

1.1425.1 Available under license

1.1426 regenerator-runtime 0.14.1

1.1426.1 Available under license

1.1427 moment 2.30.1

1.1427.1 Available under license

1.1428 @babel/plugin-transform-classes 7.23.8

1.1428.1 Available under license

1.1429 @babel/plugin-bugfix-v8-static-class-fields-redefine-readonly 7.23.7

1.1429.1 Available under license

1.1430 @babel/plugin-transform-modules-systemjs 7.23.9

1.1430.1 Available under license

1.1431 @babel/plugin-transform-async-generator-functions 7.23.9

1.1431.1 Available under license

1.1432 immutable 4.3.5

1.1432.1 Available under license

1.1433 stream-shift 1.0.3

1.1433.1 Available under license

1.1434 has-tostringtag 1.0.2

1.1434.1 Available under license

1.1435 is-array-buffer 3.0.4

1.1435.1 Available under license

1.1436 is-typed-array 1.1.13

1.1436.1 Available under license

1.1437 arraybuffer.prototype.slice 1.0.3

1.1437.1 Available under license

1.1438 array-buffer-byte-length 1.0.1

1.1438.1 Available under license

1.1439 escalade 3.1.2

1.1439.1 Available under license

1.1440 internal-slot 1.0.7

1.1440.1 Available under license

1.1441 safe-regex-test 1.0.3

1.1441.1 Available under license

1.1442 webpack-hot-middleware 2.26.1

1.1442.1 Available under license

1.1443 get-symbol-description 1.0.2

1.1443.1 Available under license

1.1444 babel-plugin-polyfill-regenerator 0.5.5

1.1444.1 Available under license

1.1445 babel-plugin-polyfill-corejs3 0.9.0

1.1445.1 Available under license

1.1446 babel-plugin-polyfill-corejs2 0.4.5

1.1446.1 Available under license

1.1447 babel-plugin-polyfill-corejs3 0.8.3

1.1447.1 Available under license

1.1448 babel-plugin-polyfill-regenerator 0.5.2

1.1448.1 Available under license

1.1449 browserify-sign 4.2.1

1.1449.1 Available under license

1.1450 regexp-prototype-flags 1.5.2

1.1450.1 Available under license

1.1451 spdx-license-ids 3.0.17

1.1451.1 Available under license

1.1452 browserslist 4.23.0

1.1452.1 Available under license

1.1453 spdx-exceptions 2.5.0

1.1453.1 Available under license

1.1454 core-js-compat 3.36.0

1.1454.1 Available under license

1.1455 available-typed-arrays 1.0.7

1.1455.1 Available under license

1.1456 possible-typed-array-names 1.0.0

1.1456.1 Available under license

1.1457 typed-array-byte-offset 1.0.2

1.1457.1 Available under license

1.1458 typed-array-buffer 1.0.2

1.1458.1 Available under license

1.1459 typed-array-byte-length 1.0.1

1.1459.1 Available under license

1.1460 is-shared-array-buffer 1.0.3

1.1460.1 Available under license

1.1461 es-set-tostringtag 2.0.3

1.1461.1 Available under license

1.1462 is-negative-zero 2.0.3

1.1462.1 Available under license

1.1463 typed-array-length 1.0.5

1.1463.1 Available under license

1.1464 set-function-name 2.0.2

1.1464.1 Available under license

1.1465 jackson-core 2.12.7

1.1465.1 Available under license

1.1466 istack-commons-runtime 3.0.7

1.1466.1 Available under license

1.1467 esniff 2.0.1

1.1467.1 Available under license

1.1468 @babel/types 7.24.0

1.1468.1 Available under license

1.1469 @babel/traverse 7.24.0

1.1469.1 Available under license

1.1470 @babel/parser 7.24.0

1.1470.1 Available under license

1.1471 @babel/template 7.24.0

1.1471.1 Available under license

1.1472 @babel/runtime 7.24.0

1.1472.1 Available under license

1.1473 es-abstract 1.22.5

1.1473.1 Available under license

1.1474 @emotion/is-prop-valid 1.2.2

1.1474.1 Available under license

1.1475 express 4.18.3

1.1475.1 Available under license

1.1476 @babel/preset-env 7.24.0

1.1476.1 Available under license

1.1477 @babel/core 7.24.0

1.1477.1 Available under license

1.1478 @ampproject/remapping 2.3.0

1.1478.1 Available under license

1.1479 @babel/helper-plugin-utils 7.24.0

1.1479.1 Available under license

1.1480 babel-helper-create-class-features-plugin 7.24.0

1.1480.1 Available under license

1.1481 @babel/plugin-transform-object-rest-spread 7.24.0

1.1481.1 Available under license

1.1482 @babel/helpers 7.24.0

1.1482.1 Available under license

1.1483 fast-infoset 1.2.15

1.1483.1 Available under license

1.1484 txw2 2.3.1

1.1484.1 Available under license

1.1485 jaxb-runtime 2.3.1

1.1485.1 Available under license

1.1486 es5-ext 0.10.64

1.1486.1 Available under license

1.1487 es6-symbol 3.1.4

1.1487.1 Available under license

1.1488 d 1.0.2

1.1488.1 Available under license

1.1489 browserify-sign 4.2.3

1.1489.1 Available under license

1.1490 html-entities 2.5.2

1.1490.1 Available under license

1.1491 parse-asn1 5.1.7

1.1491.1 Available under license

1.1492 javax activation api 1.2.0

1.1492.1 Available under license

1.1493 which-typed-array 1.1.15

1.1493.1 Available under license

1.1494 safe-array-concat 1.1.2

1.1494.1 Available under license

1.1495 caniuse-lite 1.0.30001597

1.1495.1 Available under license

1.1496 jsonassert 1.5.0

1.1496.1 Available under license

1.1497 follow-redirects 1.15.6

1.1497.1 Available under license

1.1498 sass 1.72.0

1.1498.1 Available under license

1.1499 @babel/helper-define-polyfill-provider 0.6.1

1.1499.1 Available under license

1.1500 babel-plugin-polyfill-corejs2 0.4.10

1.1500.1 Available under license

1.1501 itu 1.8.0

1.1501.1 Available under license

1.1502 jakarta activation api 1.2.1

1.1502.1 Available under license

1.1503 json-schema-validator 1.3.3

1.1503.1 Available under license

1.1504 resilience4j-timelimiter 1.7.1

1.1504.1 Available under license

1.1505 resilience4j-bulkhead 1.7.1

1.1505.1 Available under license

1.1506 resilience4j-retry 1.7.1

1.1506.1 Available under license

1.1507 squiggly-filter-jackson 1.3.18

1.1507.1 Available under license

1.1508 resilience4j-framework-common 1.7.1

1.1508.1 Available under license

1.1509 aspectjrt 1.9.6

1.1509.1 Available under license

1.1510 electron-to-chromium 1.4.708

1.1510.1 Available under license

1.1511 bcpg-jdk15on 1.50

1.1511.1 Available under license

1.1512 bcprov-jdk15on 1.50

1.1512.1 Available under license

1.1513 collections 3.2.2

1.1513.1 Available under license

1.1514 cas-client-core 3.2.1

1.1514.1 Available under license

1.1515 google-http-client-xml 1.20.0

1.1515.1 Available under license

1.1516 easymock 3.1

1.1516.1 Available under license

1.1517 hazelcast-client 3.8.9

1.1517.1 Available under license

1.1518 hazelcast 3.8.9

1.1518.1 Available under license

1.1519 icu4j 63.1

1.1519.1 Available under license

1.1520 javax-activation 1.2.0

1.1520.1 Available under license

1.1521 jaxb-api 2.3.0

1.1521.1 Available under license

1.1522 jaxb-core 2.2.11

1.1522.1 Available under license

1.1523 javax-xml-soap-api 1.4.0

1.1523.1 Available under license

1.1524 jboss-logging 3.1.1.GA

1.1524.1 Available under license

1.1525 jaxb-runtime 2.2.11

1.1525.1 Available under license

1.1526 jax-ws-api 2.3.0

1.1526.1 Available under license

1.1527 mime-pull 1.9.3

1.1527.1 Available under license

1.1528 logging 1.1.1

1.1528.1 Available under license

1.1529 lang 2.4.0

1.1529.1 Available under license

1.1530 netty-all 4.1.49.Final

1.1530.1 Available under license

1.1531 nimbus-jose-jwt 8.9

1.1531.1 Available under license

1.1532 pool 1.5.3

1.1532.1 Available under license

1.1533 shiro-config-ogdl 1.6.0

1.1533.1 Available under license

1.1534 shiro-cache 1.6.0

1.1534.1 Available under license

1.1535 shiro-core 1.6.0

1.1535.1 Available under license

1.1536 shiro-config-core 1.6.0

1.1536.1 Available under license

1.1537 shiro-crypto-hash 1.6.0

1.1537.1 Available under license

1.1538 shiro-event 1.6.0

1.1538.1 Available under license

1.1539 shiro-crypto-cipher 1.6.0

1.1539.1 Available under license

1.1540 shiro-lang 1.6.0

1.1540.1 Available under license

1.1541 shiro-crypto-core 1.6.0

1.1541.1 Available under license

1.1542 camel-jackson 2.15.2

1.1542.1 Available under license

1.1543 ipaddr.js 1.9.1

1.1543.1 Available under license

1.1544 cors 2.8.5

1.1544.1 Available under license

1.1545 string_decoder 1.1.1

1.1545.1 Available under license

1.1546 is-binary-path 2.1.0

1.1546.1 Available under license

1.1547 process-nextick-args 2.0.1

1.1547.1 Available under license

1.1548 readable-stream 2.3.8

1.1548.1 Available under license

1.1549 binary-extensions 2.2.0

1.1549.1 Available under license

1.1550 just-debounce 1.1.0

1.1550.1 Available under license

1.1551 async-each 1.0.6

1.1551.1 Available under license

1.1552 buffer-equal 1.0.1

1.1552.1 Available under license

1.1553 ip-address 9.0.5

1.1553.1 Available under license

1.1554 merge-anything 2.4.4

1.1554.1 Available under license

1.1555 css-to-react-native 2.3.2

1.1555.1 Available under license

1.1556 @babel/plugin-transform-optional-chaining 7.22.15

1.1556.1 Available under license

1.1557 diff 1.4.0

1.1557.1 Available under license

1.1558 @webassemblyjs/helper-module-context 1.9.0

1.1558.1 Available under license

1.1559 @babel/plugin-transform-destructuring 7.22.15

1.1559.1 Available under license

1.1560 @types/react 18.2.21

1.1560.1 Available under license

1.1561 @babel/plugin-proposal-private-property-in-object 7.21.11

1.1561.1 Available under license

1.1562 react-deep-force-update 1.1.2

1.1562.1 Available under license

1.1563 icss-utils 4.1.1

1.1563.1 Available under license

1.1564 @babel/plugin-syntax-function-sent 7.22.5

1.1564.1 Available under license

1.1565 rx 2.5.3

1.1565.1 Available under license

1.1566 @babel/plugin-proposal-throw-expressions 7.22.5

1.1566.1 Available under license

1.1567 @babel/plugin-transform-modules-amd 7.22.5

1.1567.1 Available under license

1.1568 @babel/helper-define-polyfill-provider 0.4.2

1.1568.1 Available under license

1.1569 postcss-modules-values 3.0.0

1.1569.1 Available under license

1.1570 @babel/plugin-syntax-pipeline-operator 7.22.5

1.1570.1 Available under license

1.1571 @webassemblyjs/helper-wasm-section 1.9.0

1.1571.1 Available under license

1.1572 @webassemblyjs/helper-api-error 1.9.0

1.1572.1 Available under license

1.1573 @babel/plugin-proposal-pipeline-operator 7.22.15

1.1573.1 Available under license

1.1574 @babel/plugin-proposal-logical-assignment-operators 7.20.7

1.1574.1 Available under license

1.1575 @babel/plugin-proposal-export-default-from 7.22.17

1.1575.1 Available under license

1.1576 @babel/plugin-proposal-do-expressions 7.22.5

1.1576.1 Available under license

1.1577 transform-loader 0.2.4

1.1577.1 Available under license

1.1578 @webassemblyjs/helper-wasm-bytecode 1.9.0

1.1578.1 Available under license

1.1579 @sinonjs/samsam 6.1.3

1.1579.1 Available under license

1.1580 @babel/helper-validator-identifier 7.22.19

1.1580.1 Available under license

1.1581 cyclist 1.0.2

1.1581.1 Available under license

1.1582 webpack-bundle-analyzer 3.9.0

1.1582.1 Available under license

1.1583 dom-walk 0.1.2

1.1583.1 Available under license

1.1584 file-loader 4.3.0

1.1584.1 Available under license

1.1585 @webassemblyjs/wasm-parser 1.9.0

1.1585.1 Available under license

1.1586 @webassemblyjs/ieee754 1.9.0

1.1586.1 Available under license

1.1587 babel-plugin-proposal-decorators 7.22.15

1.1587.1 Available under license

1.1588 css-loader 3.6.0

1.1588.1 Available under license

1.1589 @babel/core 7.22.19

1.1589.1 Available under license

1.1590 @babel/helper-wrap-function 7.22.17

1.1590.1 Available under license

1.1591 @babel/cli 7.22.15

1.1591.1 Available under license

1.1592 globule 1.3.4

1.1592.1 Available under license

1.1593 @webassemblyjs/helper-buffer 1.9.0

1.1593.1 Available under license

1.1594 @babel/plugin-syntax-do-expressions 7.22.5

1.1594.1 Available under license

1.1595 webpack-inject-plugin 1.5.5

1.1595.1 Available under license

1.1596 babel-plugin-add-module-exports 1.0.4

1.1596.1 Available under license

1.1597 style-loader 1.3.0

1.1597.1 Available under license

1.1598 postcss-modules-local-by-default 3.0.3

1.1598.1 Available under license

1.1599 nise 5.1.4

1.1599.1 Available under license

1.1600 caniuse-lite 1.0.30001534

1.1600.1 Available under license

1.1601 webpack-manifest-plugin 2.2.0

1.1601.1 Available under license

1.1602 terser-webpack-plugin 1.4.5

1.1602.1 Available under license

1.1603 react-transform-catch-errors 1.0.2

1.1603.1 Available under license

1.1604 @webassemblyjs/helper-fsm 1.9.0

1.1604.1 Available under license

1.1605 harbor-elements-utils 0.0.7

1.1605.1 Available under license

1.1606 @webassemblyjs/wasm-gen 1.9.0

1.1606.1 Available under license

1.1607 @babel/plugin-syntax-throw-expressions 7.22.5

1.1607.1 Available under license

1.1608 @babel/plugin-transform-modules-systemjs 7.22.11

1.1608.1 Available under license

1.1609 postcss-modules-scope 2.2.0

1.1609.1 Available under license

1.1610 resolve 1.22.5

1.1610.1 Available under license

1.1611 @babel/plugin-proposal-function-sent 7.22.5

1.1611.1 Available under license

1.1612 @babel/preset-env 7.22.15

1.1612.1 Available under license

1.1613 cli-width 1.1.1

1.1613.1 Available under license

1.1614 des.js 1.1.0

1.1614.1 Available under license

1.1615 prepend 1.0.2

1.1615.1 Available under license

1.1616 @babel/plugin-syntax-export-default-from 7.22.5

1.1616.1 Available under license

1.1617 types-react-redux 7.1.26

1.1617.1 Available under license

1.1618 @types/scheduler 0.16.3

1.1618.1 Available under license

1.1619 figlet 1.6.0

1.1619.1 Available under license

1.1620 @babel/helper-module-transforms 7.22.19

1.1620.1 Available under license

1.1621 gulp-conflict 0.4.0

1.1621.1 Available under license

1.1622 react-transform-hmr 1.0.4

1.1622.1 Available under license

1.1623 @sinonjs/fake-timers 7.1.2

1.1623.1 Available under license

1.1624 electron-to-chromium 1.4.523

1.1624.1 Available under license

1.1625 postcss-modules-extract-imports 2.0.0

1.1625.1 Available under license

1.1626 @webassemblyjs/wasm-edit 1.9.0

1.1626.1 Available under license

1.1627 and 0.0.3

1.1627.1 Available under license

1.1628 whatwg-fetch 3.6.19

1.1628.1 Available under license

1.1629 raw-loader 3.1.0

1.1629.1 Available under license

1.1630 @babel/plugin-transform-async-generator-functions 7.22.15

1.1630.1 Available under license

1.1631 babel-plugin-transform-runtime 7.22.15

1.1631.1 Available under license

1.1632 @webassemblyjs/wast-parser 1.9.0

1.1632.1 Available under license

1.1633 @webassemblyjs/utf8 1.9.0

1.1633.1 Available under license

1.1634 @webassemblyjs/helper-code-frame 1.9.0

1.1634.1 Available under license

1.1635 url-loader 2.3.0

1.1635.1 Available under license

1.1636 vorpal 1.12.0

1.1636.1 Available under license

1.1637 core-js-compat 3.32.2

1.1637.1 Available under license

1.1638 less-loader 5.0.0

1.1638.1 Available under license

1.1639 @babel/plugin-transform-block-scoping 7.22.15

1.1639.1 Available under license

1.1640 @webassemblyjs/wast-printer 1.9.0

1.1640.1 Available under license

1.1641 @babel/polyfill 7.12.1

1.1641.1 Available under license

1.1642 @babel/helper-remap-async-to-generator 7.22.17

1.1642.1 Available under license

1.1643 check-types 8.0.3

1.1643.1 Available under license

1.1644 assert 1.5.1

1.1644.1 Available under license

1.1645 @webassemblyjs/wasm-opt 1.9.0

1.1645.1 Available under license

1.1646 inquirer 0.8.5

1.1646.1 Available under license

1.1647 @babel/plugin-proposal-function-bind 7.22.5

1.1647.1 Available under license

1.1648 @webassemblyjs/leb128 1.9.0

1.1648.1 Available under license

1.1649 @babel/plugin-syntax-function-bind 7.22.5

1.1649.1 Available under license

1.1650 @webassemblyjs/ast 1.9.0

1.1650.1 Available under license

1.1651 @webassemblyjs/floating-point-hex-parser 1.9.0

1.1651.1 Available under license

1.1652 webpack-dev-middleware 3.7.3

1.1652.1 Available under license

1.1653 react-proxy 1.1.8

1.1653.1 Available under license

1.1654 gzip-size 5.1.1

1.1654.1 Available under license

1.1655 readline2 0.1.1

1.1655.1 Available under license

1.1656 @babel/traverse 7.22.19

1.1656.1 Available under license

1.1657 node-localstorage 0.6.0

1.1657.1 Available under license

1.1658 gulp-template 5.0.0

1.1658.1 Available under license

1.1659 react-vtree 3.0.0-beta.3

1.1659.1 Available under license

1.1660 @jridgewell/resolve-uri 3.1.2

1.1660.1 Available under license

1.1661 hazelcast-client-protocol 1.4.1

1.1661.1 Available under license

1.1662 @jridgewell/set-array 1.2.1

1.1662.1 Available under license

1.1663 @jridgewell/gen-mapping 0.3.5

1.1663.1 Available under license

1.1664 @jridgewell/trace-mapping 0.3.25

1.1664.1 Available under license

1.1665 accepts 1.3.8

1.1665.1 Available under license

1.1666 anymatch 3.1.3

1.1666.1 Available under license

1.1667 destroy 1.2.0

1.1667.1 Available under license

1.1668 fs.realpath 1.0.0

1.1668.1 Available under license

1.1669 opener 1.5.2

1.1669.1 Available under license

1.1670 set-blocking 2.0.0

1.1670.1 Available under license

1.1671 stack-trace 0.0.10

1.1671.1 Available under license

1.1672 path-to-regexp 0.1.7

1.1672.1 Available under license

1.1673 type-is 1.6.18

1.1673.1 Available under license

1.1674 es-errors 1.3.0

1.1674.1 Available under license

1.1675 methods 1.1.2

1.1675.1 Available under license

1.1676 imurmurhash 0.1.4

1.1676.1 Available under license

1.1677 fast-deep-equal 3.1.3

1.1677.1 Available under license

1.1678 content-type 1.0.5

1.1678.1 Available under license

1.1679 hasown 2.0.2

1.1679.1 Available under license

1.1680 big.js 5.2.2

1.1680.1 Available under license

1.1681 dashdash 1.14.1

1.1681.1 Available under license

1.1682 json-stringify-safe 5.0.1

1.1682.1 Available under license

1.1683 glob 7.2.3

1.1683.1 Available under license

1.1684 on-finished 2.4.1

1.1684.1 Available under license

1.1685 once 1.4.0

1.1685.1 Available under license

1.1686 process 0.11.10

1.1686.1 Available under license

1.1687 unpipe 1.0.0

1.1687.1 Available under license

1.1688 validate-npm-package-license 3.0.4

1.1688.1 Available under license

1.1689 color-name 1.1.3

1.1689.1 Available under license

1.1690 fast-json-stable-stringify 2.1.0

1.1690.1 Available under license

1.1691 media-typer 0.3.0

1.1691.1 Available under license

1.1692 range-parser 1.2.1

1.1692.1 Available under license

1.1693 es-define-property 1.0.0

1.1693.1 Available under license

1.1694 has-unicode 2.0.1

1.1694.1 Available under license

1.1695 tr46 0.0.3

1.1695.1 Available under license

1.1696 iconv-lite 0.4.24

1.1696.1 Available under license

1.1697 ajv-keywords 3.5.2

1.1697.1 Available under license

1.1698 vary 1.1.2

1.1698.1 Available under license

1.1699 strip-ansi 6.0.1

1.1699.1 Available under license

1.1700 proxy-addr 2.0.7

1.1700.1 Available under license

1.1701 statuses 2.0.1

1.1701.1 Available under license

1.1702 has-symbols 1.0.3

1.1702.1 Available under license

1.1703 base64-js 1.5.1

1.1703.1 Available under license

1.1704 url 0.11.3

1.1704.1 Available under license

1.1705 json-schema-traverse 0.4.1

1.1705.1 Available under license

1.1706 rw 1.3.3

1.1706.1 Available under license

1.1707 encoding 0.1.13

1.1707.1 Available under license

1.1708 etag 1.8.1

1.1708.1 Available under license

1.1709 rimraf 3.0.2

1.1709.1 Available under license

1.1710 psl 1.9.0

1.1710.1 Available under license

1.1711 finalhandler 1.2.0

1.1711.1 Available under license

1.1712 content-disposition 0.5.4

1.1712.1 Available under license
1.1713 define-data-property 1.1.4
1.1713.1 Available under license
1.1714 mime-types 2.1.35
1.1714.1 Available under license
1.1715 ieee754 1.2.1
1.1715.1 Available under license
1.1716 safe-buffer 5.2.1
1.1716.1 Available under license
1.1717 set-function-length 1.2.2
1.1717.1 Available under license
1.1718 has-property-descriptors 1.0.2
1.1718.1 Available under license
1.1719 color-convert 1.9.3
1.1719.1 Available under license
1.1720 escape-html 1.0.3
1.1720.1 Available under license
1.1721 merge-descriptors 1.0.1
1.1721.1 Available under license
1.1722 raw-body 2.5.2
1.1722.1 Available under license
1.1723 es6-promise 4.2.8
1.1723.1 Available under license
1.1724 has 1.0.3
1.1724.1 Available under license
1.1725 encodeurl 1.0.2
1.1725.1 Available under license
1.1726 jsbn 0.1.1
1.1726.1 Notifications
1.1726.2 Available under license
1.1727 mime-db 1.52.0
1.1727.1 Available under license
1.1728 concat-map 0.0.1
1.1728.1 Available under license
1.1729 whatwg-url 5.0.0
1.1729.1 Available under license
1.1730 bytes 3.1.2
1.1730.1 Available under license
1.1731 express-http-proxy 1.6.3

1.1731.1 Available under license

1.1732 call-bind 1.0.7

1.1732.1 Available under license

1.1733 spdx-exceptions 2.3.0

1.1733.1 Available under license

1.1734 jsprim 1.4.2

1.1734.1 Available under license

1.1735 has-proto 1.0.3

1.1735.1 Available under license

1.1736 signal-exit 3.0.7

1.1736.1 Available under license

1.1737 color-support 1.1.3

1.1737.1 Available under license

1.1738 console-control-strings 1.1.0

1.1738.1 Available under license

1.1739 inherits 2.0.4

1.1739.1 Available under license

1.1740 object-inspect 1.13.1

1.1740.1 Available under license

1.1741 get-intrinsic 1.2.4

1.1741.1 Available under license

1.1742 webidl-conversions 3.0.1

1.1742.1 Available under license

1.1743 wide-align 1.1.5

1.1743.1 Available under license

1.1744 parseurl 1.3.3

1.1744.1 Available under license

1.1745 setprototypeof 1.2.0

1.1745.1 Available under license

1.1746 promise-inflight 1.0.1

1.1746.1 Available under license

1.1747 toidentifier 1.0.1

1.1747.1 Available under license

1.1748 side-channel 1.0.6

1.1748.1 Available under license

1.1749 http-errors 2.0.0

1.1749.1 Available under license

1.1750 readdirp 3.6.0

1.1750.1 Available under license

1.1751 to-regex-range 5.0.1

1.1751.1 Available under license

1.1752 neo-async 2.6.2

1.1752.1 Available under license

1.1753 supports-preserve-symlinks-flag 1.0.0

1.1753.1 Available under license

1.1754 source-map-support 0.5.21

1.1754.1 Available under license

1.1755 update-browserslist-db 1.0.13

1.1755.1 Available under license

1.1756 source-map 0.6.1

1.1756.1 Available under license

1.1757 is-glob 4.0.3

1.1757.1 Available under license

1.1758 postcss-value-parser 4.2.0

1.1758.1 Available under license

1.1759 randombytes 2.1.0

1.1759.1 Available under license

1.1760 is-core-module 2.13.1

1.1760.1 Available under license

1.1761 events 3.3.0

1.1761.1 Available under license

1.1762 picomatch 2.3.1

1.1762.1 Available under license

1.1763 esrecurse 4.3.0

1.1763.1 Available under license

1.1764 picocolors 1.0.0

1.1764.1 Available under license

1.1765 node-releases 2.0.14

1.1765.1 Available under license

1.1766 resolve 1.22.8

1.1766.1 Available under license

1.1767 buffer-from 1.1.2

1.1767.1 Available under license

1.1768 graceful-fs 4.2.11

1.1768.1 Available under license

1.1769 jsr305 3.0.1

1.1769.1 Available under license

1.1770 estraverse 4.3.0

1.1770.1 Available under license

1.1771 webpack-sources 1.4.3

1.1771.1 Available under license

1.1772 chrome-trace-event 1.0.3

1.1772.1 Available under license

1.1773 source-list-map 2.0.1

1.1773.1 Available under license

1.1774 postcss-selector-parser 6.0.16

1.1774.1 Available under license

1.1775 isorelax 20090621

1.1775.1 Available under license

1.1776 types-json-schema 7.0.15

1.1776.1 Available under license

1.1777 xml-apis 1.4.01

1.1777.1 Available under license

1.1778 json-simple 1.1.1

1.1778.1 Available under license

1.1779 safer-buffer 2.1.2

1.1779.1 Available under license

1.1780 is-accessor-descriptor 1.0.1

1.1780.1 Available under license

1.1781 is-data-descriptor 1.0.1

1.1781.1 Available under license

1.1782 is-descriptor 0.1.7

1.1782.1 Available under license

1.1783 binary-extensions 2.3.0

1.1783.1 Available under license

1.1784 ip 2.0.0

1.1784.1 Available under license

1.1785 serve-static 1.15.0

1.1785.1 Available under license

1.1786 body-parser 1.20.1

1.1786.1 Available under license

1.1787 body-parser 1.20.2

1.1787.1 Available under license

1.1788 gopd 1.0.1

1.1788.1 Available under license

1.1789 @xtuc/ieee754 1.2.0

1.1789.1 Available under license

1.1790 @xtuc/long 4.2.2
1.1790.1 Available under license
1.1791 uuid 8.3.2
1.1791.1 Available under license
1.1792 swagger-annotations 2.2.12
1.1792.1 Available under license
1.1793 elliptic 6.5.4
1.1793.1 Available under license
1.1794 elliptic 6.5.5
1.1794.1 Available under license
1.1795 duplexer3 0.1.5
1.1795.1 Available under license
1.1796 aws4 1.12.0
1.1796.1 Available under license

1.1 objenesis 1.2

1.1.1 Available under license :

/**
* Copyright 2006-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
// --
// NOTICE file corresponding to the section 4d of The Apache License,
// Version 2.0, in this case for Objenesis
// --

Objenesis
Copyright 2006-2009 Joe Walnes, Henri Tremblay, Leonardo Mesquita

Apache License
Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or
(iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from)
the Work and for which the
editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including

the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication
on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant
of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as
of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained
within such NOTICE file, excluding those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names

of the Licensor,
except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your
sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a

file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.2 velocity 1.7

1.2.1 Available under license :

Apache Velocity

Copyright (C) 2000-2007 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).
Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or

otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership of such
entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the

editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source
code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the
terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the
attribution notices contained
within such NOTICE file, excluding those notices that do not
pertain to any part of the Derivative Works, in at least one

of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications
and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as
required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly

negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License,
Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.3 hibernate-core 3.6.9.Final

1.3.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who decide to use
it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations
below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis
or

for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.
^L
Finally, software patents
pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking
only if the
entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain

special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes
a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.
^L

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated

straightforwardly into another language.
(Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that
you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this
License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility

is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably
considered independent and separate works in
themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU
General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.
^L
Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6,

whether or not they are linked directly with the Library itself.
^L
6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the
work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly
with a modified version of the library, if
the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything that is
normally
distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.
^L
7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined with any other
library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or
distribute the Library is void, and will automatically terminate your
rights under this License. However, parties who have received copies,
or rights, from you under this License will not have their licenses
terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not
signed it. However, nothing else grants you permission to modify or
distribute the Library or its derivative works. These actions are
prohibited by law if you

do not accept this License. Therefore, by
modifying or distributing the Library (or any work based on the
Library), you indicate your acceptance of this License to do so, and
all its terms and conditions for copying, distributing or modifying
the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the
Library), the recipient automatically receives a license from the
original licensor to copy, distribute, link with or modify the Library
subject to these terms and conditions. You may not impose any further
restrictions on the recipients' exercise of the rights granted herein.
You are not responsible for enforcing compliance by third parties with
this License.
^L
11. If, as a consequence of a court judgment or allegation of patent
infringement or for any other reason (not limited to patent issues),
conditions are imposed on you (whether by court order, agreement or
otherwise) that contradict the conditions of this License, they do not
excuse
you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this
License and any other pertinent obligations, then as a consequence you
may not distribute the Library at all. For example, if a patent
license would not permit royalty-free redistribution of the Library by
all those who receive copies directly or indirectly through you, then
the only way you could satisfy both it and this License would be to
refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any
particular circumstance, the balance of the section is intended to apply,
and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any
patents or other property right claims or to contest validity of any
such claims; this section has the sole purpose of protecting the
integrity of the free software distribution system
which is
implemented by public license practices. Many people have made
generous contributions to the wide range of software distributed
through that system in reliance on consistent application of that
system; it is up to the author/donor to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in

certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.
^L
14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR

CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

^L

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston,

MA 02110-1301, USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if

necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random
Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!
* Hibernate, Relational Persistence for Idiomatic Java
*
* Copyright (c) 2010, Red Hat Inc. or third-party contributors as
* indicated by the @author tags or express copyright attribution
* statements applied by the authors. All third-party contributions are
* distributed under license by Red Hat Inc.
*
* This copyrighted material is made available to anyone wishing to use, modify,
* copy, or redistribute it subject to the terms and conditions of the GNU
* Lesser General Public License, as published by the Free Software Foundation.
*
* This program is distributed in the hope that it will be useful,
* but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY
* or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License
* for more details.
*
* You should have received a copy of the GNU Lesser General Public License
* along with this distribution; if not, write to:
* Free Software Foundation, Inc.
* 51 Franklin
 Street, Fifth Floor
* Boston, MA 02110-1301 USA

1.4 hibernate-entitymanager 3.6.7.Final

1.4.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You
can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or
for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be

introduced by others.
^L
Finally, software patents
pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library. The ordinary
General Public License therefore permits such linking
only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it
does Less to protect the user's freedom than the ordinary General
Public License. It also provides other free software developers Less
of an advantage over competing non-free programs. These disadvantages
are the reason we use the ordinary General Public License for many
libraries. However, the Lesser license provides advantages in certain
special circumstances.

For example, on rare occasions, there may be a special need to
encourage the widest possible use of a certain library, so that it
becomes
a de-facto standard. To achieve this, non-free programs must be
allowed to use the library. A more frequent case is that a free
library does the same job as widely used non-free libraries. In this
case, there is little to gain by limiting the free library
to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free
programs enables a greater number of people to use a large body of
free software. For example, permission to use the GNU C Library in
non-free programs enables many more people to use the whole GNU

operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.
^L

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language.
(Hereinafter, translation is
included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does

and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that
you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably

considered independent and separate works in
themselves, then this License, and its terms, do not apply to those
sections when you distribute them as separate works. But when you
distribute the same sections as part of a whole which is a work based
on the Library, the distribution of the whole must be on the terms of
this License, whose permissions for other licensees extend to the
entire whole, and thus to each and every part regardless of who wrote
it.

Thus, it is not the intent of this section to claim rights or contest
your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or
collective works based on the Library.

In addition, mere aggregation of another work not based on the Library
with the Library (or with a work based on the Library) on a volume of
a storage or distribution medium does not bring the other work under
the scope of this License.

3. You may opt to apply the terms of the ordinary GNU
General Public
License instead of this License to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so
that they refer to the ordinary GNU General Public License, version 2,
instead of to this License. (If a newer version than version 2 of the
ordinary GNU General Public License has appeared, then you can specify
that version instead if you wish.) Do not make any other change in
these notices.
^L
Once this change is made in a given copy, it is irreversible for
that copy, so the ordinary GNU General Public License applies to all
subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of
the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or
derivative of it, under Section 2) in object code or executable form
under the terms of Sections 1 and 2 above provided that you accompany
it with the complete corresponding
machine-readable source code, which
must be distributed under the terms of Sections 1 and 2 above on a
medium customarily used for software interchange.

If distribution of object code is made by offering access to copy
from a designated place, then offering equivalent access to copy the
source code from the same place satisfies the requirement to
distribute the source code, even though third parties are not

compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library".
The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code
for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.
^L
6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one

of these things:

a) Accompany the
work with the complete corresponding
machine-readable source code for the Library including whatever
changes were used in the work (which must be distributed under
Sections 1 and 2 above); and, if the work is an executable linked
with the Library, with the complete machine-readable "work that
uses the Library", as object code and/or source code, so that the
user can modify the Library and then relink to produce a modified
executable containing the modified Library. (It is understood
that the user who changes the contents of definitions files in the
Library will not necessarily be able to recompile the application
to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the
Library. A suitable mechanism is one that (1) uses at run time a
copy of the library already present on the user's computer system,
rather than copying library functions into the executable, and (2)
will operate properly
with a modified version of the library, if
the user installs one, as long as the modified version is
interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at
least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything that is
normally
distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally

accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.
^L
7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.
^L
11. If, as a consequence of a court judgment or allegation of patent

infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse
you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system
which is
implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish
revised and/or new
versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and

"any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

^L

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision

will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,

BE LIABLE TO YOU

FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

^L

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms

of the ordinary General Public License).

To apply these terms, attach the following notices to the library.
It is safest to attach them to the start of each source file to most
effectively
convey the exclusion of warranty; and each file should
have at least the "copyright" line and a pointer to where the full
notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston,

MA 02110-1301, USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random
Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.5 commons-pool 1.6

1.5.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of,

the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without

modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names
of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole
responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"

replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed
under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Commons Pool
Copyright 2001-2012 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

1.6 commons-beanutils 1.8.3

1.6.1 Available under license :

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the

editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists,
source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to
the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of
the attribution notices contained
within such NOTICE file, excluding those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications
and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade

names, trademarks, service marks, or product names of the Licensor,
except
as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the

same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License,
Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Commons BeanUtils
Copyright 2000-2010 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

1.7 httpmime 4.2.3

1.7.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii)

beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the
Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication
on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of

this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant
of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as
of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed

as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names
of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be

liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

Apache HttpComponents HttpMime
Copyright 1999-2013 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

1.8 json4s-core 3.2.5

1.9 json4s-ext 3.2.5

1.10 json4s-jackson 3.2.5

1.11 json4s-ast 3.2.5

1.12 json4s-native 3.2.5

1.13 metrics-core 3.1.0

1.13.1 Available under license :

Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source"
form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or

merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall
mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed
by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and
You must cause any modified files to carry prominent notices stating that You changed the files; and
You must retain, in the Source form of any Derivative Works that
You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or

as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant
permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as
deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.14 commons-pool 2.2

1.14.1 Available under license :

Apache Commons Pool
Copyright 2001-2014 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

The LinkedBlockingDeque implementation is based on an implementation written by
Doug Lea with assistance from members of JCP JSR-166 Expert Group and released
to the public domain, as explained at
http://creativecommons.org/licenses/publicdomain

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or
(iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or

Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s)

with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as
of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or

for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your

sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.15 commons-cli 1.2

1.15.1 Available under license :

Apache Commons CLI
Copyright 2001-2009 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or
(iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from)
the Work and for which the
editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally

submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained
within such NOTICE file, excluding those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names
of the Licensor,
except as required for reasonable and customary use in describing the

origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your
sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier

identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.16 httpclient 4.4.1

1.16.1 Available under license :

Apache HttpComponents Client
Copyright 1999-2015 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii)

beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the
Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication
on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of

this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant
of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as
of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed

as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names
of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be

liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

==========

This project includes Public Suffix List copied from
<https://publicsuffix.org/list/effective_tld_names.dat>
licensed under the terms of the Mozilla Public License, v. 2.0

Full license text: <http://mozilla.org/MPL/2.0/>

Mozilla Public License Version 2.0
==========

1. Definitions

1.1. "Contributor"
means each individual or legal entity that creates, contributes to the creation of, or owns Covered Software.

1.2. "Contributor Version"
means the combination of the Contributions of others (if any) used by a Contributor and that particular Contributor's Contribution.

1.3. "Contribution"
means Covered Software of a particular Contributor.

1.4. "Covered Software"
means Source Code Form to which the initial Contributor has attached the notice in Exhibit A, the Executable Form of such Source Code Form, and Modifications of such Source Code Form, in each case including portions thereof.

1.5. "Incompatible With Secondary Licenses"
means

(a) that the initial Contributor has attached the notice described in Exhibit B to the Covered Software; or

(b) that the Covered Software was made available under the terms of version 1.1 or earlier of the License, but not also under the terms of a Secondary License.

1.6. "Executable Form"
means any form of the work other than Source Code Form.

1.7. "Larger Work"
means a work that combines Covered Software with other material, in a separate file or
files, that is not Covered Software.

1.8. "License"
means this document.

1.9. "Licensable"
means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently, any and all of the rights conveyed by this License.

1.10. "Modifications"
means any of the following:

(a) any file in Source Code Form that results from an addition to, deletion from, or modification of the contents of Covered Software; or

(b) any new file in Source Code Form that contains any Covered Software.

1.11. "Patent Claims" of a Contributor
means any patent claim(s), including without limitation, method, process, and apparatus claims, in any patent Licensable by such Contributor that would be infringed, but for the grant of the License, by the making, using, selling, offering for sale, having made, import, or transfer of either its Contributions or its

Contributor
Version.

1.12. "Secondary License"
means either the GNU General Public License, Version 2.0, the GNU Lesser General Public License, Version 2.1, the GNU Affero General Public License, Version 3.0, or any later versions of those licenses.

1.13. "Source Code Form"
means the form of the work preferred for making modifications.

1.14. "You" (or "Your")
means an individual or a legal entity exercising rights under this License. For legal entities, "You" includes any entity that controls, is controlled by, or is under common control with You. For purposes of this definition, "control" means (a) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (b) ownership of more than fifty percent (50%) of the outstanding shares or beneficial ownership of such entity.

2. License Grants and Conditions

2.1. Grants

Each
Contributor hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under intellectual property rights (other than patent or trademark)
Licensable by such Contributor to use, reproduce, make available, modify, display, perform, distribute, and otherwise exploit its Contributions, either on an unmodified basis, with Modifications, or as part of a Larger Work; and

(b) under Patent Claims of such Contributor to make, use, sell, offer for sale, have made, import, and otherwise transfer either its Contributions or its Contributor Version.

2.2. Effective Date

The licenses granted in Section 2.1 with respect to any Contribution become effective for each Contribution on the date the Contributor first distributes such Contribution.

2.3. Limitations on Grant Scope

The licenses granted in this Section 2 are the only rights granted under this License. No additional rights or licenses will be implied from the distribution or licensing
of Covered Software under this License.
Notwithstanding Section 2.1(b) above, no patent license is granted by a Contributor:

(a) for any code that a Contributor has removed from Covered Software; or

(b) for infringements caused by: (i) Your and any other third party's modifications of Covered Software, or (ii) the combination of its Contributions with other software (except as part of its Contributor Version); or

(c) under Patent Claims infringed by Covered Software in the absence of its Contributions.

This License does not grant any rights in the trademarks, service marks, or logos of any Contributor (except as may be necessary to comply with the notice requirements in Section 3.4).

2.4. Subsequent Licenses

No Contributor makes additional grants as a result of Your choice to distribute the Covered Software under a subsequent version of this License (see Section 10.2) or under the terms of a Secondary License (if permitted under the
terms of Section 3.3).

2.5. Representation

Each Contributor represents that the Contributor believes its Contributions are its original creation(s) or it has sufficient rights to grant the rights to its Contributions conveyed by this License.

2.6. Fair Use

This License is not intended to limit any rights You have under applicable copyright doctrines of fair use, fair dealing, or other equivalents.

2.7. Conditions

Sections 3.1, 3.2, 3.3, and 3.4 are conditions of the licenses granted in Section 2.1.

3. Responsibilities

3.1. Distribution of Source Form

All distribution of Covered Software in Source Code Form, including any Modifications that You create or to which You contribute, must be under the terms of this License. You must inform recipients that the Source Code Form of the Covered Software is governed by the terms of this License, and how they can obtain a copy of this License. You may not attempt to alter or restrict the
recipients' rights in the Source Code
Form.

3.2. Distribution of Executable Form

If You distribute Covered Software in Executable Form then:

(a) such Covered Software must also be made available in Source Code Form, as described in Section 3.1, and You must inform recipients of the Executable Form how they can obtain a copy of such Source Code Form by reasonable means in a timely manner, at a charge no more than the cost of distribution to the recipient; and

(b) You may distribute such Executable Form under the terms of this License, or sublicense it under different terms, provided that the license for the Executable Form does not attempt to limit or alter the recipients' rights in the Source Code Form under this License.

3.3. Distribution of a Larger Work

You may create and distribute a Larger Work under terms of Your choice, provided that You also comply with the requirements of this License for the Covered Software. If the Larger
Work is a combination of Covered
Software with a work governed by one or more Secondary Licenses, and the Covered Software is not Incompatible With Secondary Licenses, this License permits You to additionally distribute such Covered Software under the terms of such Secondary License(s), so that the recipient of the Larger Work may, at their option, further distribute the Covered Software under the terms of either this License or such Secondary License(s).

3.4. Notices

You may not remove or alter the substance of any license notices (including copyright notices, patent notices, disclaimers of warranty, or limitations of liability) contained within the Source Code Form of

the Covered Software, except that You may alter any license notices to the extent required to remedy known factual inaccuracies.

3.5. Application of Additional Terms

You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, You may do so only on Your own behalf, and not on behalf of any Contributor. You must make it absolutely clear that any such warranty, support, indemnity, or liability obligation is offered by You alone, and You hereby agree to indemnify every Contributor for any liability incurred by such Contributor as a result of warranty, support, indemnity or liability terms You offer. You may include additional disclaimers of warranty and limitations of liability specific to any jurisdiction.

4. Inability to Comply Due to Statute or Regulation

If it is impossible for You to comply with any of the terms of this License with respect to some or all of the Covered Software due to statute, judicial order, or regulation then You must: (a) comply with the terms of this License to the maximum extent possible; and (b) describe the limitations and the code they affect. Such description must be placed in a text file included with all distributions of the Covered Software under this License. Except to the extent prohibited by statute or regulation, such description must be sufficiently detailed for a recipient of ordinary skill to be able to understand it.

5. Termination

5.1. The rights granted under this License will terminate automatically if You fail to comply with any of its terms. However, if You become compliant, then the rights granted under this License from a particular Contributor are reinstated (a) provisionally, unless and until such Contributor explicitly and finally terminates Your grants, and (b) on an ongoing basis, if such Contributor fails to notify You of the non-compliance by some reasonable means prior to 60 days after You have come back into compliance. Moreover, Your grants from a particular Contributor are reinstated on an ongoing basis if such Contributor notifies You of the non-compliance by some reasonable means, this is the first time You have received notice of non-compliance with this License from such Contributor, and You become compliant prior to 30 days after Your receipt of the notice.

5.2. If You initiate litigation against any entity by asserting a patent infringement claim (excluding declaratory judgment actions, counter-claims, and cross-claims) alleging that a Contributor Version directly or indirectly infringes any patent, then the rights granted to You by any and all Contributors for the Covered Software under Section 2.1 of this License shall terminate.

5.3. In the event of termination under Sections 5.1 or 5.2 above, all end user license agreements (excluding distributors and resellers) which have been validly granted by You or Your distributors under this License prior to termination shall survive termination.

```
************************************************************************
*                                                                      *
*  6. Disclaimer
 of Warranty                                  *
*  -------------------------                                           *
*                                                                      *
*  Covered Software is provided under this License on an "as is"       *
*  basis, without warranty of any kind, either expressed, implied, or  *
*  statutory, including, without limitation, warranties that the       *
*  Covered Software is free of defects, merchantable, fit for a        *
*  particular purpose or non-infringing. The entire risk as to the     *
*  quality and performance of the Covered Software is with You.        *
*  Should any Covered Software prove defective in any respect, You     *
*  (not any Contributor) assume the cost of any necessary servicing,   *
*  repair, or correction. This disclaimer of warranty constitutes an   *
*  essential part of this License. No use of any Covered Software is   *
*  authorized under this License except under this disclaimer.
       *
*                                                                      *
************************************************************************

************************************************************************
*                                                                      *
*  7. Limitation of Liability                                          *
*  -------------------------                                           *
*                                                                      *
*  Under no circumstances and under no legal theory, whether tort      *
*  (including negligence), contract, or otherwise, shall any           *
*  Contributor, or anyone who distributes Covered Software as          *
*  permitted above, be liable to You for any direct, indirect,         *
*  special, incidental, or consequential damages of any character      *
*  including, without limitation, damages for lost profits, loss of    *
*  goodwill, work
 stoppage, computer failure or malfunction, or any    *
*  and all other commercial damages or losses, even if such party      *
```

* shall have been informed of the possibility of such damages. This *
* limitation of liability shall not apply to liability for death or *
* personal injury resulting from such party's negligence to the *
* extent applicable law prohibits such limitation. Some *
* jurisdictions do not allow the exclusion or limitation of *
* incidental or consequential damages, so this exclusion and *
* limitation may not apply to You. *
* *
****

8. Litigation

Any litigation relating to this License may be brought only in the
courts of a jurisdiction where the defendant maintains its principal
place of business and such litigation
shall be governed by laws of that
jurisdiction, without reference to its conflict-of-law provisions.
Nothing in this Section shall prevent a party's ability to bring
cross-claims or counter-claims.

9. Miscellaneous

This License represents the complete agreement concerning the subject
matter hereof. If any provision of this License is held to be
unenforceable, such provision shall be reformed only to the extent
necessary to make it enforceable. Any law or regulation which provides
that the language of a contract shall be construed against the drafter
shall not be used to construe this License against a Contributor.

10. Versions of the License

10.1. New Versions

Mozilla Foundation is the license steward. Except as provided in Section
10.3, no one other than the license steward has the right to modify or
publish new versions of this License. Each version will be given a
distinguishing version number.

10.2.
Effect of New Versions

You may distribute the Covered Software under the terms of the version
of the License under which You originally received the Covered Software,
or under the terms of any subsequent version published by the license
steward.

10.3. Modified Versions

If you create software not governed by this License, and you want to create a new license for such software, you may create and use a modified version of this License if you rename the license and remove any references to the name of the license steward (except to note that such modified license differs from this License).

10.4. Distributing Source Code Form that is Incompatible With Secondary Licenses

If You choose to distribute Source Code Form that is Incompatible With Secondary Licenses under the terms of this version of the License, the notice described in Exhibit B of this License must be attached.

Exhibit A - Source Code Form License Notice

This Source Code Form is subject to the terms of the Mozilla Public License, v. 2.0. If a copy of the MPL was not distributed with this file, You can obtain one at http://mozilla.org/MPL/2.0/.

If it is not possible or desirable to put the notice in a particular file, then You may include the notice in a location (such as a LICENSE file in a relevant directory) where a recipient would be likely to look for such a notice.

You may add additional accurate notices of copyright ownership.

Exhibit B - "Incompatible With Secondary Licenses" Notice

This Source Code Form is "Incompatible With Secondary Licenses", as defined by the Mozilla Public License, v. 2.0.

```
/*
* ========================================================================
* Licensed to the Apache Software Foundation (ASF) under one
* or more contributor license agreements.  See the NOTICE file
* distributed with this work for additional information
* regarding copyright ownership.  The ASF licenses this file
* to you under the Apache License, Version 2.0 (the
* "License"); you may not use this file except in compliance
* with the License.  You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing,
```

* software distributed under the License is distributed on an
* "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY
* KIND, either express or implied. See the License for the
* specific language governing permissions and limitations
* under the License.
* ==
*
* This software consists of voluntary
 contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

1.17 httpmime 4.3.6

1.17.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation

source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this

License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided

that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache HttpClient Mime
Copyright 1999-2014 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.18 joda-time 2.7

1.18.1 Available under license :

```
=========================================================================
= NOTICE file corresponding to section 4d of the Apache License Version 2.0 =
=========================================================================
```

This product includes software developed by
Joda.org (http://www.joda.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object

form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate

as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work

by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.19 commons-logging 1.2

1.19.1 Available under license :

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Apache License
Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or
(iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from)
the Work and for which the
editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including

the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication
on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant
of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as
of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained
within such NOTICE file, excluding those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names

of the Licensor,
except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your
sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a

file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Commons Logging
Copyright 2003-2014 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.20 commons-collections 3.2.2

1.20.1 Available under license :

Apache Commons Collections
Copyright 2001-2015 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its

distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,

WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.21 httpcore 4.4.1

1.21.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct

or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

==========

This project contains annotations in the package org.apache.http.annotation
which are derived from JCIP-ANNOTATIONS
Copyright (c) 2005 Brian Goetz and Tim Peierls.
See http://www.jcip.net and the Creative Commons Attribution License
(http://creativecommons.org/licenses/by/2.5)
Full text: http://creativecommons.org/licenses/by/2.5/legalcode

License

THE WORK (AS DEFINED BELOW) IS PROVIDED UNDER THE TERMS OF THIS CREATIVE COMMONS PUBLIC LICENSE ("CCPL" OR "LICENSE"). THE WORK IS PROTECTED BY COPYRIGHT AND/OR OTHER APPLICABLE LAW. ANY USE OF THE WORK OTHER THAN AS AUTHORIZED UNDER THIS LICENSE OR COPYRIGHT LAW IS PROHIBITED.

BY EXERCISING ANY RIGHTS TO THE WORK PROVIDED HERE, YOU ACCEPT AND AGREE TO BE BOUND BY THE TERMS OF THIS LICENSE. THE LICENSOR GRANTS YOU THE RIGHTS CONTAINED HERE IN CONSIDERATION OF YOUR ACCEPTANCE OF SUCH TERMS AND CONDITIONS.

1. Definitions

"Collective Work" means a work, such as a periodical issue, anthology or encyclopedia, in which the Work in its entirety in unmodified form, along with a number of other contributions, constituting separate and independent works in themselves, are assembled into a collective whole. A work that constitutes a Collective Work will not be considered a Derivative Work (as defined below) for the purposes of this License.

"Derivative Work" means a work based upon the Work or upon the Work and other pre-existing works, such as a translation, musical arrangement, dramatization, fictionalization, motion picture version, sound recording, art reproduction, abridgment, condensation,

or any other form in which the Work may be recast, transformed, or adapted, except that a work that constitutes a Collective Work will not be considered a Derivative Work for the purpose of this License. For the avoidance of doubt, where the Work is a musical composition or sound recording, the synchronization of the Work in timed-relation with a moving image ("synching") will be considered a Derivative Work for the purpose of this License.

"Licensor" means the individual or entity that offers the Work under the terms of this License.

"Original Author" means the individual or entity who created the Work.

"Work" means the copyrightable work of authorship offered under the terms of this License.

"You" means an individual or entity exercising rights under this License who has not previously violated the terms of this License with respect to the Work, or who has received express permission from the Licensor to exercise rights under this License despite a previous violation.

2.

Fair Use Rights. Nothing in this license is intended to reduce, limit, or restrict any rights arising from fair use, first sale or other limitations on the exclusive rights of the copyright owner under copyright law or other applicable laws.

3. License Grant. Subject to the terms and conditions of this License, Licensor hereby grants You a worldwide, royalty-free, non-exclusive, perpetual (for the duration of the applicable copyright) license to exercise the rights in the Work as stated below:

to reproduce the Work, to incorporate the Work into one or more Collective Works, and to reproduce the Work as incorporated in the Collective Works;

to create and reproduce Derivative Works;

to distribute copies or phonorecords of, display publicly, perform publicly, and perform publicly by means of a digital audio transmission the Work including as incorporated in Collective Works;

to distribute copies or phonorecords of, display publicly, perform publicly, and perform publicly

by means of a digital audio transmission Derivative Works.

For the avoidance of doubt, where the work is a musical composition:

Performance Royalties Under Blanket Licenses. Licensor waives the exclusive right to collect, whether individually or via a performance rights society (e.g. ASCAP, BMI, SESAC), royalties for the public performance or public digital performance (e.g. webcast) of the Work.

Mechanical Rights and Statutory Royalties. Licensor waives the exclusive right to collect, whether individually or via a music rights agency or designated agent (e.g. Harry Fox Agency), royalties for any phonorecord You create from the Work ("cover version") and distribute, subject to the compulsory license created by 17 USC Section 115 of the US Copyright Act (or the equivalent in other jurisdictions).

Webcasting Rights and Statutory Royalties. For the avoidance of doubt, where the Work is a sound recording, Licensor waives the exclusive right to collect, whether

individually or via a performance-rights society (e.g. SoundExchange), royalties for the public digital performance (e.g. webcast) of the Work, subject to the compulsory license created by 17 USC Section 114 of the US Copyright Act (or the equivalent in other jurisdictions).

The above rights may be exercised in all media and formats whether now known or hereafter devised. The above rights include the right to make such modifications as are technically necessary to exercise the rights in other media and formats. All rights not expressly granted by Licensor are hereby reserved.

4. Restrictions.The license granted in Section 3 above is expressly made subject to and limited by the following restrictions:

You may distribute, publicly display, publicly perform, or publicly digitally perform the Work only under the terms of this License, and You must include a copy of, or the Uniform Resource Identifier for, this License with every copy or phonorecord of the Work You distribute, publicly
display, publicly perform, or publicly digitally perform. You may not offer or impose any terms on the Work that alter or restrict the terms of this License or the recipients' exercise of the rights granted hereunder. You may not sublicense the Work. You must keep intact all notices that refer to this License and to the disclaimer of warranties. You may not distribute, publicly display, publicly perform, or publicly digitally perform the Work with any technological measures that control access or use of the Work in a manner inconsistent with the terms of this License Agreement. The above applies to the Work as incorporated in a Collective Work, but this does not require the Collective Work apart from the Work itself to be made subject to the terms of this License. If You create a Collective Work, upon notice from any Licensor You must, to the extent practicable, remove from the Collective Work any credit as required by clause 4(b), as requested. If You create a Derivative Work, upon
notice from any Licensor You must, to the extent practicable, remove from the Derivative Work any credit as required by clause 4(b), as requested.
If you distribute, publicly display, publicly perform, or publicly digitally perform the Work or any Derivative Works or Collective Works, You must keep intact all copyright notices for the Work and provide, reasonable to the medium or means You are utilizing: (i) the name of the Original Author (or pseudonym, if applicable) if supplied, and/or (ii) if the Original Author and/or Licensor designate another party or parties (e.g. a sponsor institute, publishing entity, journal) for attribution in Licensor's copyright notice, terms of service or by other reasonable means, the name of such party or parties; the title of the Work if supplied; to the extent reasonably practicable, the Uniform Resource Identifier, if any, that Licensor specifies to be associated with the Work, unless such URI does not refer to the copyright notice or licensing
information for the Work; and in the case of a Derivative Work, a credit identifying the use of the Work in the Derivative Work (e.g., "French translation of the Work by Original Author," or "Screenplay based on original Work by Original Author"). Such credit may be implemented in any reasonable manner; provided, however, that in the case of a Derivative Work or Collective Work, at a minimum such credit will appear where any other comparable authorship credit appears and in a manner at least as prominent as such other comparable authorship credit.

5. Representations, Warranties and Disclaimer

UNLESS OTHERWISE MUTUALLY AGREED TO BY THE PARTIES IN WRITING, LICENSOR OFFERS THE WORK AS-IS AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE WORK, EXPRESS, IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTIBILITY, FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT, OR THE ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE
OF ABSENCE OF ERRORS, WHETHER OR NOT DISCOVERABLE. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES, SO SUCH EXCLUSION MAY NOT APPLY TO YOU.

6. Limitation on Liability. EXCEPT TO THE EXTENT REQUIRED BY APPLICABLE LAW, IN NO EVENT WILL LICENSOR BE LIABLE TO YOU ON ANY LEGAL THEORY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES ARISING OUT OF THIS LICENSE OR THE USE OF THE WORK, EVEN IF LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. Termination

This License and the rights granted hereunder will terminate automatically upon any breach by You of the terms of this License. Individuals or entities who have received Derivative Works or Collective Works from You under this License, however, will not have their licenses terminated provided such individuals or entities remain in full compliance with those licenses. Sections 1, 2, 5, 6, 7, and 8 will survive any termination of this License.

Subject to the above terms and conditions, the license granted here is perpetual (for the duration of the applicable copyright in the Work). Notwithstanding the above, Licensor reserves the right to release the Work under different license terms or to stop distributing the Work at any time; provided, however that any such election will not serve to withdraw this License (or any other license that has been, or is required to be, granted under the terms of this License), and this License will continue in full force and effect unless terminated as stated above.

8. Miscellaneous

Each time You distribute or publicly digitally perform the Work or a Collective Work, the Licensor offers to the recipient a license to the Work on the same terms and conditions as the license granted to You under this License.

Each time You distribute or publicly digitally perform a Derivative Work, Licensor offers to the recipient a license to the original Work on the same terms and conditions as the license granted to You under this License.

If any provision of this License is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this License, and without further action by the parties to this agreement, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

No term or provision of this License shall be deemed waived and no breach consented to unless such waiver or consent shall be in writing and signed by the party to be charged with such waiver or consent.

This License constitutes the entire agreement between the parties with respect to the Work licensed here. There are no understandings, agreements or representations with respect to the Work not specified here. Licensor shall not be bound by any additional provisions that may appear in any communication from You. This License may not be modified without the mutual written agreement of the Licensor and You.

Apache HttpCore
Copyright 2005-2015 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

This project contains annotations derived from JCIP-ANNOTATIONS
Copyright (c) 2005 Brian Goetz and Tim Peierls. See http://www.jcip.net

1.22 metrics-json 3.1.0

1.22.1 Available under license :

Apache License 2.0
http://www.apache.org/licenses/LICENSE-2.0.html

1.23 metrics-jvm 3.1.0

1.23.1 Available under license :

Apache License 2.0
http://www.apache.org/licenses/LICENSE-2.0.html

1.24 commons-io 2.4

1.24.1 Available under license :

Apache Commons IO
Copyright 2002-2012 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity

exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the

Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents

of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,

work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.25 joda-convert 1.2

1.25.1 Available under license :

```
=========================================================================
= NOTICE file corresponding to section 4d of the Apache License Version 2.0 =
=========================================================================
```

This product includes software developed by
Joda.org (http://www.joda.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object

form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate

as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work

by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.26 antlr-runtime 4.5.1

1.26.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* [The "BSD license"]
* Copyright (c) 2014 Terence Parr
* Copyright (c) 2014 Sam Harwell
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above copyright
* notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.
* 3. The name of the author may not be used to endorse or promote products
* derived from this software without specific prior written permission.

*
* THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR
* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO,
 THE IMPLIED WARRANTIES
* OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
* IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
* INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
* NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
* THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
* (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
* THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/DecisionInfo.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ParseInfo.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/PredicateEvalInfo.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/RuntimeMetaData.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/DecisionEventInfo.java
*
 /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ErrorInfo.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/VocabularyImpl.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/AmbiguityInfo.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/Vocabulary.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ContextSensitivityInfo.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LookaheadEventInfo.java
No license file was found, but licenses were detected in source scan.

/*
* [The "BSD license"]
* Copyright (c) 2013 Terence Parr
* Copyright (c) 2013 Sam Harwell
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. The name of the author may not be used to endorse or promote products
*   derived from this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR

* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED WARRANTIES
* OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
* IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
* INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
* NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
* THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
* (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
* THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ATNSimulator.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LexerActionExecutor.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ATNDeserializer.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LexerChannelAction.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LexerTypeAction.java
*
/antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LexerIndexedCustomAction.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LexerPopModeAction.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LexerMoreAction.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LexerPushModeAction.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LexerAction.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LexerModeAction.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LexerSkipAction.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ATNDeserializationOptions.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LexerActionType.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ATNType.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ProfilingATNSimulator.java
*
/antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LexerCustomAction.java
No license file was found, but licenses were detected in source scan.

/*
* [The "BSD license"]
* Copyright (c) 2012 Terence Parr
* Copyright (c) 2012 Sam Harwell
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above copyright
* notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the

```
*     documentation and/or other materials provided with the distribution.
*  3. The name of the author may not be used to endorse or promote products
*     derived from this software without specific prior written permission.
*
*  THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR
*  IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO,
 THE IMPLIED WARRANTIES
*  OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
*  IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
*  INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
*  NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
*  DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
*  THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
*  (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
*  THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/BasicBlockStartState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/NotSetTransition.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/ParseCancellationException.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/FailedPredicateException.java
*
 /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/ConsoleErrorListener.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ATNSerializer.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/ObjectEqualityComparator.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/dfa/DFAState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/Pair.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/EmptyPredictionContext.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/RangeTransition.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/RuleTransition.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/BasicState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/Utils.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/RuleStartState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/DiagnosticErrorListener.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/FlexibleHashMap.java
*
 /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/PredictionMode.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/PlusBlockStartState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/ANTLRErrorStrategy.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/BlockEndState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/DefaultErrorStrategy.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/Array2DHashSet.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/ParserRuleContext.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/BlockStartState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/Triple.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/ParseTreeVisitor.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/IntegerStack.java
```

* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/NotNull.java
*
 /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LoopEndState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/SyntaxTree.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LexerATNSimulator.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ATNConfig.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/dfa/DFA.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/PredictionContextCache.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LL1Analyzer.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/Recognizer.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/UnbufferedCharStream.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/AbstractEqualityComparator.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/ErrorNode.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/BaseErrorListener.java
*
 /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/AbstractParseTreeVisitor.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ParserATNSimulator.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ArrayPredictionContext.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/Trees.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/RuleNode.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/TokenSource.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/StarBlockStartState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ATNConfigSet.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/BailErrorStrategy.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/EqualityComparator.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/Tree.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ActionTransition.java
*
 /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/LexerATNConfig.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/InputMismatchException.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/Parser.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/StarLoopEntryState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/TokenStream.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/PrecedencePredicateTransition.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/SetTransition.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/LexerNoViableAltException.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/RuleContext.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/MurmurHash.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/SingletonPredictionContext.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/ANTLRFileStream.java
*
 /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/ParseTreeWalker.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/RecognitionException.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/RuleStopState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ATN.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/MultiMap.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/CharStream.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/TokenStreamRewriter.java

* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/IntStream.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/IntSet.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/LogManager.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/dfa/DFASerializer.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/TerminalNodeImpl.java
*
 /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/StarLoopbackState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/IntervalSet.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/AtomTransition.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/CommonTokenFactory.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/ATNState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/TokenFactory.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/Token.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/NoViableAltException.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/CommonTokenStream.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/ANTLRInputStream.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/ANTLRErrorListener.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/IntegerList.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/PredictionContext.java
*
 /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/SemanticContext.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/dfa/LexerDFASerializer.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/ParseTreeListener.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/TerminalNode.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/ErrorNodeImpl.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/PlusLoopbackState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/WritableToken.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/OrderedHashSet.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/DecisionState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/ParseTree.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/TokensStartState.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/EpsilonTransition.java
*
 /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/UnbufferedTokenStream.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/ProxyErrorListener.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/PredicateTransition.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/BufferedTokenStream.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/CommonToken.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/OrderedATNConfigSet.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/LexerInterpreter.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/AbstractPredicateTransition.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/Lexer.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/Transition.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/DoubleKeyMap.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/misc/Interval.java
*
 /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/ParseTreeProperty.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/atn/WildcardTransition.java

No license file was found, but licenses were detected in source scan.

/*
* [The "BSD license"]
* Copyright (c) 2013 Terence Parr
* Copyright (c) 2013 Sam Harwell
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. The name of the author may not be used to endorse or promote products
*   derived from this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR
* IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
 * OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
* IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT,
* INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT
* NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
* DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
* THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
* (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
* THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/pattern/RuleTagToken.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/pattern/TokenTagToken.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/InterpreterRuleContext.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/pattern/Chunk.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/pattern/ParseTreePattern.java
*
 /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/pattern/ParseTreeMatch.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/pattern/ParseTreePatternMatcher.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/ParserInterpreter.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/pattern/TagChunk.java
* /antlr4-runtime-4-5-1-sources-2-jar/org/antlr/v4/runtime/tree/pattern/TextChunk.java

1.27 copy-concurrently 1.0.5

1.27.1 Available under license :

Copyright (c) 2017, Rebecca Turner <me@re-becca.org>

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.28 move-concurrently 1.0.1

1.28.1 Available under license :

Copyright (c) 2017, Rebecca Turner <me@re-becca.org>

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.29 run-queue 1.0.3

1.29.1 Available under license :

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED “AS IS” AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR

CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.30 commons-net 3.0

1.30.1 Available under license :

Apache Commons Net
Copyright 2001-2011 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation,

and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable

by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only

on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.31 javax-servlet-api 3.1.0

1.31.1 Available under license :

COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL) Version 1.0

1. Definitions.

1.1. Contributor. means each individual or entity that creates or contributes to the creation of Modifications.

1.2. Contributor Version. means the combination of the Original Software, prior Modifications used by a Contributor (if any), and the Modifications made by that particular Contributor.

1.3. Covered Software. means (a) the Original Software, or (b) Modifications, or (c) the combination of files containing Original Software with files containing Modifications, in each case including portions thereof.

1.4. Executable. means the Covered Software in any form other than Source Code.

1.5. Initial Developer. means the individual or entity that first makes Original Software available under this License.

1.6. Larger Work. means a work which combines Covered Software or portions thereof with code not governed by the terms of this License.

1.7. License. means this document.

1.8. Licensable. means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently acquired, any and all of the rights conveyed herein.

1.9. Modifications. means the Source Code and Executable form of any of the following:

A. Any file that results from an addition to, deletion from or modification of the contents of a file containing Original Software or previous Modifications;

B. Any new file that contains any part of the Original Software or previous Modification; or

C. Any new file that is contributed or otherwise made available under the terms of this License.

1.10. Original Software. means the Source Code and Executable form of computer software code that is originally released under this License.

1.11. Patent Claims. means any patent claim(s), now owned or hereafter acquired, including without limitation, method, process, and apparatus claims, in any patent Licensable
by grantor.

1.12. Source Code. means (a) the common form of computer software code in which modifications are made and (b) associated documentation included in or with such code.

1.13. You. (or .Your.) means an individual or a legal entity exercising rights under, and complying with all of the terms of, this License. For legal entities, .You. includes any entity which controls, is controlled by, or is under common control with You. For purposes of this definition, .control. means (a) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (b) ownership of more than fifty percent (50%) of the outstanding shares or beneficial ownership of such entity.

2. License Grants.

2.1. The Initial Developer Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, the Initial Developer hereby grants You a world-wide, royalty-free, non-exclusive
license:

(a) under intellectual property rights (other than patent or trademark) Licensable by Initial Developer, to use,

reproduce, modify, display, perform, sublicense and distribute the Original Software (or portions thereof), with or without Modifications, and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using or selling of Original Software, to make, have made, use, practice, sell, and offer for sale, and/or otherwise dispose of the Original Software (or portions thereof).

(c) The licenses granted in Sections 2.1(a) and (b) are effective on the date Initial Developer first distributes or otherwise makes the Original Software available to a third party under the terms of this License.

(d) Notwithstanding Section 2.1(b) above, no patent license is granted: (1) for code that You delete from the Original Software, or (2) for infringements caused by: (i) the modification of the Original Software, or (ii) the combination of the Original Software with other software or devices.

2.2. Contributor Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, each Contributor hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under intellectual property rights (other than patent or trademark) Licensable by Contributor to use, reproduce, modify, display, perform, sublicense and distribute the Modifications created by such Contributor (or portions thereof), either on an unmodified basis, with other Modifications, as Covered Software and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using, or selling of Modifications made by that Contributor either alone and/or in combination with its Contributor Version (or portions of such combination), to make, use, sell, offer for sale, have made, and/or otherwise dispose of: (1) Modifications made by that Contributor (or portions thereof); and (2) the combination of Modifications made by that Contributor with its Contributor Version (or portions of such combination).

(c) The licenses granted in Sections 2.2(a) and 2.2(b) are effective on the date Contributor first distributes or otherwise makes the Modifications available to a third party.

(d) Notwithstanding Section 2.2(b) above, no patent license is granted: (1) for any code that Contributor has deleted from the Contributor Version; (2) for infringements caused by: (i) third party modifications of Contributor Version, or (ii) the combination of Modifications made by that Contributor with other software (except as part of the Contributor Version) or other devices; or (3) under Patent Claims infringed by Covered Software in the absence of Modifications made by that Contributor.

3. Distribution Obligations.

3.1. Availability of Source Code.

Any Covered Software that You distribute or otherwise make available in Executable form must also be made available in Source Code form and that Source Code form must be distributed only under the terms of this License. You must include a copy of this License with every copy of the Source Code form of the Covered Software You distribute or otherwise make available. You must inform recipients of any such Covered Software in Executable form as to how they can obtain such Covered Software in Source Code form in a reasonable manner on or through a medium customarily used for software exchange.

3.2. Modifications.

The Modifications that You create or to which You contribute are governed by the terms of this License. You represent that You believe Your Modifications are Your original creation(s) and/or You have sufficient rights to grant the rights conveyed by this License.

3.3. Required Notices.

You must include a notice in each of Your Modifications that identifies You as the Contributor of the Modification.

You may not remove or alter any copyright, patent or trademark notices contained within the Covered Software, or any notices of licensing or any descriptive text giving attribution to any Contributor or the Initial Developer.

3.4. Application of Additional Terms.

You may not offer or impose any terms on any Covered Software in Source Code form that alters or restricts the applicable version of this License or the recipients. rights hereunder. You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, you may do so only on Your own behalf, and not on behalf of the Initial Developer or any Contributor. You must make it absolutely clear that any such warranty, support, indemnity or liability obligation is offered by You alone, and You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor

as a result of warranty, support, indemnity or liability terms You offer.

3.5. Distribution of Executable Versions.

You may distribute the Executable form of the Covered Software under the terms of this License or under the terms of a license of Your choice, which may contain terms different from this License, provided that You are in compliance with the terms of this License and that the license for the Executable form does not attempt to limit or alter the recipient.s rights in the Source Code form from the rights set forth in this License. If You distribute the Covered Software in Executable form under a different license, You must make it absolutely clear that any terms which differ from this License are offered by You alone, not by the Initial Developer or Contributor. You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of any such terms You offer.

3.6. Larger Works.

You may create a Larger Work by combining Covered Software with other code not governed by the terms of this License and distribute the Larger Work as a single product. In such a case, You must make sure the requirements of this License are fulfilled for the Covered Software.

4. Versions of the License.

4.1. New Versions.

Sun Microsystems, Inc. is the initial license steward and may publish revised and/or new versions of this License from time to time. Each version will be given a distinguishing version number. Except as provided in Section 4.3, no one other than the license steward has the right to modify this License.

4.2. Effect of New Versions.

You may always continue to use, distribute or otherwise make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. If the Initial Developer includes a notice in the Original Software prohibiting it

from being distributed or otherwise made available under any subsequent version of the License, You must distribute and make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. Otherwise, You may also choose to use, distribute or otherwise make the Covered Software available under the terms of any subsequent version of the License published by the license steward.

4.3. Modified Versions.

When You are an Initial Developer and You want to create a new license for Your Original Software, You may create and use a modified version of this License if You: (a) rename the license and remove any references to the name of the license steward (except to note that the license differs from this License); and (b) otherwise make it clear that the license contains terms which differ from this License.

5. DISCLAIMER OF WARRANTY.

COVERED SOFTWARE IS PROVIDED UNDER THIS LICENSE ON AN .AS IS. BASIS, WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES THAT THE COVERED SOFTWARE IS FREE OF DEFECTS, MERCHANTABLE, FIT FOR A PARTICULAR PURPOSE OR NON-INFRINGING. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE COVERED SOFTWARE IS WITH YOU. SHOULD ANY COVERED SOFTWARE PROVE DEFECTIVE IN ANY RESPECT, YOU (NOT THE INITIAL DEVELOPER OR ANY OTHER CONTRIBUTOR) ASSUME THE COST OF ANY NECESSARY SERVICING, REPAIR OR CORRECTION. THIS DISCLAIMER OF WARRANTY CONSTITUTES AN ESSENTIAL PART OF THIS LICENSE. NO USE OF ANY COVERED SOFTWARE IS AUTHORIZED HEREUNDER EXCEPT UNDER THIS DISCLAIMER.

6. TERMINATION.

6.1. This License and the rights granted hereunder will terminate automatically if You fail to comply with terms herein and fail to cure such breach within 30 days of becoming aware of the breach. Provisions which, by their nature, must remain in effect beyond the termination of this License shall survive.

6.2. If You assert

a patent infringement claim (excluding declaratory judgment actions) against Initial Developer or a Contributor (the Initial Developer or Contributor against whom You assert such claim is referred to as .Participant.) alleging that the Participant Software (meaning the Contributor Version where the Participant is a Contributor or the Original Software where the Participant is the Initial Developer) directly or indirectly infringes any patent, then any and all rights granted directly or indirectly to You by such Participant, the Initial Developer (if the Initial Developer is not the Participant) and all Contributors under Sections 2.1 and/or 2.2 of this License shall, upon 60 days notice from Participant terminate prospectively and automatically at the expiration of such 60 day notice period, unless if within such 60 day period You withdraw Your claim with respect to the Participant Software against such Participant either unilaterally or pursuant to a written agreement with Participant.

6.3. In the event of termination under Sections 6.1 or 6.2 above, all end user licenses that have been validly granted by You or any distributor hereunder prior to termination (excluding licenses granted to You by any distributor) shall survive termination.

7. LIMITATION OF LIABILITY.

UNDER NO CIRCUMSTANCES AND UNDER NO LEGAL THEORY, WHETHER TORT (INCLUDING NEGLIGENCE), CONTRACT, OR OTHERWISE, SHALL YOU, THE INITIAL DEVELOPER, ANY OTHER CONTRIBUTOR, OR ANY DISTRIBUTOR OF COVERED SOFTWARE, OR ANY SUPPLIER OF ANY OF SUCH PARTIES, BE LIABLE TO ANY PERSON FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY CHARACTER INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOST PROFITS, LOSS OF GOODWILL, WORK STOPPAGE, COMPUTER FAILURE OR MALFUNCTION, OR ANY AND ALL OTHER COMMERCIAL DAMAGES OR LOSSES, EVEN IF SUCH PARTY SHALL HAVE BEEN INFORMED OF THE POSSIBILITY OF SUCH DAMAGES. THIS LIMITATION OF LIABILITY SHALL NOT APPLY TO LIABILITY FOR DEATH OR PERSONAL INJURY RESULTING FROM SUCH PARTY.S NEGLIGENCE TO THE EXTENT APPLICABLE LAW PROHIBITS SUCH LIMITATION. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS EXCLUSION AND LIMITATION MAY NOT APPLY TO YOU.

8. U.S. GOVERNMENT END USERS.

The Covered Software is a .commercial item,. as that term is defined in 48 C.F.R. 2.101 (Oct. 1995), consisting of .commercial computer software. (as that term is defined at 48 C.F.R. ? 252.227-7014(a)(1)) and .commercial computer software documentation. as such terms are used in 48 C.F.R. 12.212 (Sept. 1995). Consistent with 48 C.F.R. 12.212 and 48 C.F.R. 227.7202-1 through 227.7202-4 (June 1995), all U.S. Government End Users acquire Covered Software with only those rights set forth herein. This U.S. Government Rights clause is in lieu of, and supersedes, any other FAR, DFAR, or other clause or provision that addresses Government rights in computer software under this License.

9. MISCELLANEOUS.

This License represents the complete agreement concerning subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable. This License shall be governed by the law of the jurisdiction specified in a notice contained within the Original Software (except to the extent applicable law, if any, provides otherwise), excluding such jurisdiction.s conflict-of-law provisions. Any litigation relating to this License shall be subject to the jurisdiction of the courts located in the jurisdiction and venue specified in a notice contained within the Original Software, with the losing party responsible for costs, including, without limitation, court costs and reasonable attorneys. fees and expenses. The application of the United Nations Convention on Contracts for the International Sale of Goods is expressly excluded. Any law or regulation which provides that the language of a contract
shall be construed against the drafter shall not apply to this License. You agree that You alone are responsible for compliance with the United States export administration regulations (and the export control laws and regulation of any other countries) when You use, distribute or otherwise make available any Covered Software.

10. RESPONSIBILITY FOR CLAIMS.

As between Initial Developer and the Contributors, each party is responsible for claims and damages arising, directly or indirectly, out of its utilization of rights under this License and You agree to work with Initial Developer and Contributors to distribute such responsibility on an equitable basis. Nothing herein is intended or shall be deemed to constitute any admission of liability.

NOTICE PURSUANT TO SECTION 9 OF THE COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL)

The code released under the CDDL shall be governed by the laws of the State of California (excluding conflict-of-law provisions). Any litigation
relating to this License shall be subject to the jurisdiction of the Federal Courts of the Northern District of California and the state courts of the State of California, with venue lying in Santa Clara County, California.

The GNU General Public License (GPL) Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software
is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code.
And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To

prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions
for copying, distribution and modification follow.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based
on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified
files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply

to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution
medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed
only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts
as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you

permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions
for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute
the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it
is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each
version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE,
THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD
PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

One line to give the program's name and a brief idea of what it does.

Copyright (C)

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software
Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General

Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'. This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands
`show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.

signature of Ty Coon, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

"CLASSPATH"
EXCEPTION TO THE GPL VERSION 2

Certain source files distributed by Sun Microsystems, Inc. are subject to the following clarification and special exception to the GPL Version 2, but only where Sun has expressly included in the particular source file's header the words

"Sun designates this particular file as subject to the "Classpath" exception as provided by Sun in the License file that accompanied this code."

Linking this library statically or dynamically with other modules is making a combined work based on this library. Thus, the terms and conditions of the GNU General Public License Version 2 cover the whole combination.

As a special exception, the copyright holders of this library give you permission to link this library with independent modules to produce an executable, regardless of the license terms of these independent modules, and to copy and distribute the resulting executable under terms of your choice, provided that you also meet, for each linked

independent module, the terms and conditions of the license of that module.? An independent module is a module which is not derived from or based on this library.? If you modify this library, you may extend this exception to your version of the library, but you are not obligated to do so.? If you do not wish to do so, delete this exception statement from your version.

1.32 hibernate-validator 5.0.0.Final

1.33 spring-boot-autoconfigure 1.5.12.RELEASE

1.33.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2012-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/SecurityPrerequisite.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/jpa/JpaRepositoriesAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/ConditionalOnNotWebApplication.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/batch/JobExecutionExitCodeGenerator.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/batch/JobExecutionEvent.java

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jdbc/DataSourceInitializerPostProcessor.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/template/TemplateLocation.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/data/elasticsearch/ElasticsearchRepositoriesAutoConfiguration.java
*
 /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/gson/GsonAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/websocket/JettyWebSocketContainerCustomizer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/data/elasticsearch/ElasticsearchRepositoriesRegistrar.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/websocket/UndertowWebSocketContainerCustomizer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/data/solr/SolrRepositoriesRegistrar.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jdbc/DataSourceInitializedEvent.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/package-info.java
*
 /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/websocket/TomcatWebSocketContainerCustomizer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/solr/SolrProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jdbc/metadata/HikariDataSourcePoolMetadata.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012-2018 the original author or authors.

*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jdbc/EmbeddedDatabaseConnection.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/security/SecurityProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/web/ResourceProperties.java
*
 /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/cache/CacheCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/data/cassandra/CassandraDataAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/session/RedisSessionConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/session/SessionAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/web/ServerProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/web/BasicErrorController.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/security/oauth2/client/OAuth2RestOperationsConfiguration.java
*
 /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/web/WebMvcAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/security/oauth2/client/EnableOAuth2SsoCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/session/SessionCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jms/artemis/ArtemisXAConnectionFactoryConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/condition/BeanTypeRegistry.java
* /spring-boot-autoconfigure-1-5-12-release-sources-

jar/org/springframework/boot/autoconfigure/web/AbstractErrorController.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/cache/CacheType.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/condition/SearchStrategy.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jms/activemq/ActiveMQConnectionFactoryFactory.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/flyway/FlywayAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/condition/OnPropertyCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/data/redis/RedisAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/context/MessageSourceAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/cache/CouchbaseCacheConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/batch/BatchAutoConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/web/ServerPropertiesAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/condition/OnBeanCondition.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/security/AuthenticationManagerConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/elasticsearch/jest/HttpClientConfigBuilderCustomizer.java

*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/AbstractDatabaseInitializer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/hazelcast/HazelcastAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/artemis/ArtemisConnectionFactoryFactory.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/resource/PrincipalExtractor.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/thymeleaf/AbstractThymeleafViewResolverConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/redis/RedisProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/JdbcTemplateAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/session/package-info.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cache/GuavaCacheConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/domain/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cache/GenericCacheConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/groovy/template/GroovyTemplateAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cache/InfinispanCacheConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/WebMvcRegistrations.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/metadata/DataSourcePoolMetadataProvidersConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/transaction/jta/JndiJtaConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/resource/SpringSocialTokenServices.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/FallbackWebSecurityAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/ConditionalOnMissingClass.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/logging/AutoConfigurationReportLoggingInitializer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/DefaultErrorViewResolver.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/JmsAutoConfiguration.java
*

/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/websocket/WebSocketContainerCustomizer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/integration/IntegrationAutoConfigurationScanRegistrar.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/ConditionalOnProperty.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/domain/EntityScanner.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mongo/MongoAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/transaction/jta/JtaProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/HttpEncodingProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/elasticsearch/jest/JestAutoConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/solr/SolrRepositoriesAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/session/HashMapSessionConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/kafka/KafkaAnnotationDrivenConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cassandra/ClusterBuilderCustomizer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/couchbase/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/OnJndiCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/redis/RedisRepositoriesAutoConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mobile/DeviceDelegatingViewResolverFactory.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/OnWebApplicationCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/client/OAuth2SsoCustomConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/session/HazelcastSessionConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/social/TwitterAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/liquibase/LiquibaseDataSource.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/HttpEncodingAutoConfiguration.java
*

/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/websocket/WebSocketAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/elasticsearch/ElasticsearchAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/aop/AopAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cache/EhCacheCacheConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/sendgrid/SendGridProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/social/SocialProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/HttpMessageConverters.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/redis/RedisRepositoriesAutoConfigureRegistrar.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/resource/FixedPrincipalExtractor.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/ConditionalOnCloudPlatform.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/metadata/CommonsDbcpDataSourcePoolMetadata.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/neo4j/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/WebMvcRegistrationsAdapter.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/DispatcherServletAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/ResourceCondition.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/social/FacebookAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/EmbeddedDataSourceConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/resource/UserInfoRestTemplateCustomizer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/JspTemplateAvailabilityProvider.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/HttpMessageConvertersAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/couchbase/SpringBootCouchbaseDataConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/h2/H2ConsoleAutoConfiguration.java
*

/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jackson/JacksonProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/condition/ConditionalOnExpression.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/websocket/WebSocketMessagingAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/logging/ConditionEvaluationReportMessage.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/cassandra/CassandraProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/data/couchbase/SpringBootCouchbaseConfigurer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/data/neo4j/Neo4jRepositoriesAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/session/NoOpSessionConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/template/TemplateAvailabilityProviders.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/mustache/MustacheAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/data/couchbase/CouchbaseRepositoriesRegistrar.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/hazelcast/HazelcastConfigResourceCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/condition/OnExpressionCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/BackgroundPreinitializer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/session/JdbcSessionDatabaseInitializer.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/thymeleaf/AbstractTemplateResolverConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/mongo/embedded/EmbeddedMongoProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jdbc/XADataSourceAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/validation/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jdbc/HikariDriverConfigurationFailureAnalyzer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/template/AbstractViewResolverProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/cache/CacheConfigurations.java
*

/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/condition/OnJavaCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/social/LinkedInAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/integration/IntegrationAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jdbc/DataSourceBeanCreationFailureAnalyzer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/SharedMetadataReaderFactoryContextInitializer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/webservices/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/cache/HazelcastInstanceConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jms/artemis/ArtemisEmbeddedConfigurationFactory.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/condition/AbstractNestedCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/data/rest/RepositoryRestMvcAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/security/oauth2/client/SsoSecurityConfigurer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/web/MultipartAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/batch/JobLauncherCommandLineRunner.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/cassandra/CassandraAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/AbstractDependsOnBeanFactoryPostProcessor.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/domain/EntityScanPackages.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/session/JdbcSessionConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/kafka/KafkaAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/cache/CacheManagerCustomizer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/data/mongo/MongoRepositoriesAutoConfigureRegistrar.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/couchbase/CouchbaseProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/social/SocialAutoConfigurerAdapter.java
*

/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/thymeleaf/ThymeleafAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/session/StoreType.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/transaction/PlatformTransactionManagerCustomizer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/condition/OnCloudPlatformCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/web/ConditionalOnEnabledResourceChain.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jms/JndiConnectionFactoryAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/sendgrid/SendGridAutoConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/session/SessionStoreMappings.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/web/ErrorMvcAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/elasticsearch/jest/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/batch/BatchDatabaseInitializer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jackson/Jackson2ObjectMapperBuilderCustomizer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/hateoas/HypermediaAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/couchbase/OnBootstrapHostsCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/domain/EntityScan.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/mail/MailSenderAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/cache/RedisCacheConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/data/neo4j/Neo4jRepositoriesAutoConfigureRegistrar.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/info/ProjectInfoAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jackson/JacksonAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jms/DefaultJmsListenerContainerFactoryConfigurer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jms/artemis/ArtemisProperties.java
*

/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/orm/jpa/HibernateVersion.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/couchbase/CouchbaseConfigurerAdapterConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mail/MailSenderValidatorAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/client/OAuth2SsoDefaultConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/hazelcast/HazelcastJpaDependencyAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mail/JndiSessionConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/WebClientAutoConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/couchbase/CouchbaseRepositoriesAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/ConditionOutcome.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/metadata/AbstractDataSourcePoolMetadata.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/couchbase/CouchbaseDataAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/webservices/WebServicesAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/SecurityFilterAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/kafka/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/ErrorViewResolver.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/artemis/ArtemisEmbeddedServerConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jersey/ResourceConfigCustomizer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/transaction/jta/JtaAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/ConditionalOnWebApplication.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/kafka/ConcurrentKafkaListenerContainerFactoryConfigurer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/JmsAnnotationDrivenConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/IgnoredRequestCustomizer.java
*

/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mobile/DeviceDelegatingViewResolverAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/ConditionEvaluationReport.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/resource/FixedAuthoritiesExtractor.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/jpa/JpaRepositoriesAutoConfigureRegistrar.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/freemarker/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/session/MongoSessionConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cache/CaffeineCacheConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/DataSourceBuilder.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cache/HazelcastCacheConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/couchbase/CouchbaseDataProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/cassandra/CassandraRepositoriesAutoConfigureRegistrar.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/diagnostics/analyzer/NoSuchBeanDefinitionFailureAnalyzer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jersey/JerseyAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/JmsProperties.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cache/CacheAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/kafka/KafkaProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cache/SimpleCacheConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/OnResourceCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mobile/DeviceResolverAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/couchbase/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/amqp/RabbitAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/AutoConfigurationExcludeFilter.java
*

/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mustache/web/MustacheViewResolver.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/OAuth2AutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mobile/SitePreferenceAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/transaction/jta/AtomikosJtaConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/solr/SolrAutoConfiguration.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mustache/MustacheTemplateAvailabilityProvider.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/artemis/ArtemisConfigurationCustomizer.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/thymeleaf/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/NonRecursivePropertyPlaceholderHelper.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/websocket/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/artemis/ArtemisNoOpBindingRegistry.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/freemarker/FreeMarkerProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/activemq/ActiveMQAutoConfiguration.java

* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/admin/package-info.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/solr/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/AutoConfigureOrder.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/elasticsearch/ElasticsearchProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/groovy/template/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jmx/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/mongo/MongoClientDependsOnBeanFactoryPostProcessor.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cache/NoOpCacheConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cache/package-info.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/dao/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/metadata/DataSourcePoolMetadataProvider.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/AutoConfigurationPackage.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/DefaultErrorAttributes.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/jpa/EntityManagerFactoryDependsOnPostProcessor.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/logging/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/ConditionalOnResource.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/ConditionalOnJava.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/metadata/TomcatDataSourcePoolMetadata.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/resource/JwtAccessTokenConverterConfigurer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/GsonHttpMessageConvertersConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-

jar/org/springframework/boot/autoconfigure/flyway/FlywayMigrationStrategy.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/gson/package-info.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/thymeleaf/ThymeleafTemplateAvailabilityProvider.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jooq/SpringTransactionProvider.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cloud/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/web/SpringDataWebAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/artemis/ArtemisMode.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/jpa/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jooq/JooqProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cassandra/package-info.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/ErrorProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/flyway/FlywayMigrationInitializer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/ErrorAttributes.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/metadata/CommonsDbcp2DataSourcePoolMetadata.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/rest/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/artemis/ArtemisConnectionFactoryConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/solr/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/transaction/jta/package-info.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/liquibase/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/SecurityDataConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/client/EnableOAuth2Sso.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/groovy/template/GroovyTemplateProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/artemis/ArtemisAutoConfiguration.java

* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/mongo/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jmx/ParentAwareNamingStrategy.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/transaction/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mustache/MustacheEnvironmentCollector.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/artemis/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cloud/CloudAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/AutoConfigureAfter.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/aop/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/metadata/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mustache/web/MustacheView.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/reactor/ReactorAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/reactor/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/metadata/DataSourcePoolMetadataProviders.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/SecurityAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jersey/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/social/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mustache/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/hateoas/HateoasProperties.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/metadata/DataSourcePoolMetadata.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/JacksonHttpMessageConvertersConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/elasticsearch/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-

jar/org/springframework/boot/autoconfigure/condition/ConditionalOnJndi.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jooq/SpringTransaction.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/hazelcast/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/AutoConfigureBefore.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cache/JCacheManagerCustomizer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/orm/jpa/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/ErrorController.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/activemq/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/SecurityAuthorizeMode.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/hateoas/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/batch/package-info.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mail/MailProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/context/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/template/AbstractTemplateViewResolverProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jooq/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/cassandra/CassandraRepositoriesAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mobile/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mustache/MustacheResourceTemplateLoader.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/web/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/context/ConfigurationPropertiesAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/template/TemplateAvailabilityProvider.java

* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/template/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mongo/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/amqp/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jmx/JmxAutoConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/cassandra/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mail/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/flyway/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/redis/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mustache/web/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jackson/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/flyway/FlywayDataSource.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/integration/package-info.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/resource/AuthoritiesExtractor.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/hazelcast/HazelcastInstanceFactory.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/BootGlobalAuthenticationConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/AbstractRepositoryConfigurationSourceSupport.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jooq/JooqAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cache/CacheProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mustache/MustacheCompilerFactoryBean.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/ConditionalOnBean.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/batch/BasicBatchConfigurer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/EmbeddedServletContainerAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/resource/UserInfoRestTemplateFactory.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/ConditionalOnClass.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/AllNestedConditions.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/transaction/TransactionProperties.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/authserver/AuthorizationServerProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/social/LinkedInProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/AutoConfigurationMetadata.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/session/SessionProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/transaction/TransactionManagerCustomizers.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/transaction/jta/BitronixJtaConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/activemq/ActiveMQProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/Http401AuthenticationEntryPoint.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cache/JCachePropertiesCustomizer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/client/OAuth2SsoProperties.java

* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jooq/JooqExceptionTranslator.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/ImportAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/ldap/LdapRepositoriesAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/ConditionalOnSingleCandidate.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/neo4j/Neo4jDataAutoConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/social/TwitterProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/AutoConfigurationImportListener.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/dao/PersistenceExceptionTranslationAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/authserver/OAuth2AuthorizationServerConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/MultipartProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/elasticsearch/ElasticsearchDataAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/transaction/jta/NarayanaJtaConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/mobile/DeviceDelegatingViewResolverProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/liquibase/LiquibaseAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/AutoConfigurationImportFilter.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/resource/DefaultUserInfoRestTemplateFactory.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jms/activemq/ActiveMQConnectionFactoryConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/neo4j/Neo4jProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/ldap/package-info.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/OnEnabledResourceChainCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/DataSourceAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/JndiDataSourceAutoConfiguration.java

* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/social/SocialWebAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/mongo/MongoDataAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/ldap/embedded/EmbeddedLdapAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/orm/jpa/HibernateJpaAutoConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/elasticsearch/jest/JestProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/ldap/LdapProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jersey/JerseyProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/DataSourceTransactionManagerAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/amqp/RabbitAnnotationDrivenConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/resource/OAuth2ResourceServerConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/resource/ResourceServerProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/cache/HazelcastJCacheCustomizationConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/method/OAuth2MethodSecurityConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/AutoConfigurationImportEvent.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/freemarker/FreeMarkerTemplateAvailabilityProvider.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/jdbc/DataSourceInitializer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/AutoConfigurationPackages.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/hateoas/HypermediaHttpMessageConverterConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/ImportAutoConfigurationImportSelector.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/validation/ValidationAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/NoneNestedConditions.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/amqp/RabbitProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-

jar/org/springframework/boot/autoconfigure/EnableAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/validation/PrimaryDefaultValidatorPostProcessor.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/security/oauth2/resource/JwtAccessTokenConverterRestTemplateCustomizer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/cache/CacheManagerCustomizers.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/security/SpringBootWebSecurityConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/orm/jpa/DatabaseLookup.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/AutoConfigurationSorter.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/template/PathBasedTemplateAvailabilityProvider.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jms/activemq/ActiveMQXAConnectionFactoryConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/condition/OnClassCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/amqp/SimpleRabbitListenerContainerFactoryConfigurer.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/data/ldap/LdapDataAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/web/WebMvcProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/condition/ConditionEvaluationReportAutoConfigurationImportListener.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/SpringBootApplication.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/flyway/FlywayProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/cache/JCacheCacheConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/data/ldap/LdapRepositoriesRegistrar.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jdbc/DataSourceConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/security/oauth2/resource/ResourceServerTokenServicesConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/groovy/template/GroovyTemplateAvailabilityProvider.java
* /spring-boot-autoconfigure-1-5-12-release-sources-

jar/org/springframework/boot/autoconfigure/condition/ConditionalOnMissingBean.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/condition/SpringBootCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/h2/H2ConsoleProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jms/activemq/ActiveMQConnectionFactoryCustomizer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/condition/ConditionMessage.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/orm/jpa/DataSourceInitializedPublisher.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/thymeleaf/ThymeleafProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/mongo/MongoProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/admin/SpringApplicationAdminJmxAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/context/PropertyPlaceholderAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/jdbc/DataSourceProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/liquibase/LiquibaseProperties.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/orm/jpa/JpaProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/mongo/embedded/EmbeddedMongoAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/security/oauth2/resource/UserInfoTokenServices.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/transaction/TransactionAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/AutoConfigurationMetadataLoader.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/mustache/MustacheProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/social/FacebookProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/PropertyPlaceholderAutoConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/batch/BatchProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/data/rest/SpringBootRepositoryRestConfigurer.java
* /spring-boot-autoconfigure-1-5-12-release-sources-
jar/org/springframework/boot/autoconfigure/ldap/LdapAutoConfiguration.java

* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/hazelcast/HazelcastProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/freemarker/FreeMarkerAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/web/WebMvcValidator.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/EnableAutoConfigurationImportSelector.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/OAuth2ClientProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/rest/RepositoryRestProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/couchbase/CouchbaseAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/info/ProjectInfoProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/ldap/embedded/EmbeddedLdapProperties.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/data/mongo/MongoRepositoriesAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/ldap/package-info.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/security/oauth2/client/OAuth2ProtectedResourceDetailsConfiguration.java
*
/spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/MessageSourceAutoConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/orm/jpa/JpaBaseConfiguration.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/condition/AnyNestedCondition.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/AutoConfigurationImportSelector.java
* /spring-boot-autoconfigure-1-5-12-release-sources-jar/org/springframework/boot/autoconfigure/webservices/WebServicesProperties.java

1.34 spring-boot 1.5.12.RELEASE

1.34.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/properties/ConfigurationPropertiesBindingPostProcessorRegistrar.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/config/DelegatingApplicationContextInitializer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/java/SimpleFormatter.java
*
 /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/logback/WhitespaceThrowableProxyConverter.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/jetty/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/tomcat/TomcatContextCustomizer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/tomcat/TomcatConnectorCustomizer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/tomcat/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/logback/ExtendedWhitespaceThrowableProxyConverter.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/json/YamlJsonParser.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/LogLevel.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/EmbeddedServletContainerException.java
*
 /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/WebApplicationContextServletContextAwareProcessor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/ConfigurationWarningsApplicationContextInitializer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/ErrorPage.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/log4j2/ColorConverter.java
*
 /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/diagnostics/analyzer/BeanCurrentlyInCreationFailureAnalyzer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/config/ConfigFileApplicationListener.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/TypeExcludeFilter.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ansi/AnsiPropertySource.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/cloud/CloudFoundryVcapEnvironmentPostProcessor.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jta/atomikos/AtomikosProperties.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ExitCodeGenerator.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/undertow/UndertowEmbeddedServletContainer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/admin/SpringApplicationAdminMXBean.java
*
 /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/undertow/CompositeResourceManager.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/AbstractLoggingSystem.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/builder/SpringApplicationBuilder.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/event/EventPublishingRunListener.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jta/narayana/NarayanaRecoveryManagerBean.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/logback/ColorConverter.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/annotation/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/support/ErrorPageFilterConfiguration.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/builder/ParentContextApplicationContextInitializer.java
*
 /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/undertow/JarResourceManager.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/json/JacksonJsonParser.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/diagnostics/FailureAnalyzers.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/properties/ConfigurationProperties.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/LoggerConfigurationComparator.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/config/DelegatingApplicationListener.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/EnvironmentConverter.java

* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/YamlConfigurationFactory.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/log4j2/Log4J2LoggingSystem.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/web/support/ServletContextApplicationContextInitializer.java
*
/spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jta/narayana/NarayanaProperties.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/tomcat/SkipPatternJarScanner.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/tomcat/TomcatEmbeddedWebappClassLoader.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/LoggerConfiguration.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/ServletContextInitializerBeans.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/yaml/SpringProfileDocumentMatcher.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/support/SpringBootServletInitializer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/SpringApplication.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/validation/MessageInterpolatorFactory.java
*
/spring-boot-1-5-12-release-sources-jar/org/springframework/boot/validation/package-info.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/properties/NestedConfigurationProperty.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/annotation/DeterminableImports.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/diagnostics/analyzer/BindFailureAnalyzer.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/EmbeddedServletContainerCustomizerBeanPostProcessor.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/logback/LogbackLoggingSystem.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/web/servlet/ErrorPageRegistrarBeanPostProcessor.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/info/GitProperties.java
*
/spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/jetty/JettyEmbeddedErrorHandler.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/web/servlet/ServletComponentRegisteringPostProcessor.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jackson/JsonComponentModule.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/tomcat/LazySessionIdGenerator.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/diagnostics/LoggingFailureAnalysisReporter.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/java/JavaLoggingSystem.java
*
 /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/diagnostics/FailureAnalysisReporter.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jta/narayana/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/orm/jpa/hibernate/SpringPhysicalNamingStrategy.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/PortInUseException.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/type/classreading/ConcurrentReferenceCachingMetadataReaderFactory.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ExitCodeExceptionMapper.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/client/RootUriTemplateHandler.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/YamlJavaBeanPropertyConstructor.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/package-info.java
*
 /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/diagnostics/analyzer/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/config/RandomValuePropertySource.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/diagnostics/analyzer/NoUniqueBeanDefinitionFailureAnalyzer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/ServletContextInitializer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/RelaxedPropertyResolver.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/diagnostics/FailureAnalysis.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ExitCodeEvent.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/SpringApplicationBannerPrinter.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/filter/OrderedCharacterEncodingFilter.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/AbstractFilterRegistrationBean.java
*
 /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jackson/JsonComponent.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/filter/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/LocalServerPort.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/diagnostics/analyzer/ConnectorStartFailureAnalyzer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/info/BuildProperties.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/AbstractConfigurableEmbeddedServletContainer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/SpringBootExceptionHandler.java
* /spring-boot-1-5-12-release-sources-

jar/org/springframework/boot/context/embedded/ConfigurableEmbeddedServletContainer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/WebServletHandler.java
*
/spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/WebListenerHandler.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/Slf4JLoggingSystem.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/jta/narayana/NarayanaXAConnectionFactoryWrapper.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/diagnostics/analyzer/AbstractInjectionFailureAnalyzer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/lang/UsesUnsafeJava.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jta/bitronix/PoolingDataSourceBean.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/PropertySourceUtils.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ResourceBanner.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/SpringApplicationRunListeners.java
*
/spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/diagnostics/analyzer/ValidationExceptionFailureAnalyzer.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/logging/ClasspathLoggingApplicationListener.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/tomcat/TldSkipPatterns.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/ErrorPageRegistrar.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/JspServlet.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jta/narayana/NarayanaDataSourceBean.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/SpringBootConfiguration.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/Ssl.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/jta/bitronix/PoolingConnectionFactoryBean.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/logging/logback/LevelRemappingAppender.java
*
/spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/jta/narayana/NarayanaXADataSourceWrapper.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/FilterRegistrationBean.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/diagnostics/analyzer/BeanNotOfRequiredTypeFailureAnalyzer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/SslStoreProvider.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/tomcat/SslStoreProviderUrlStreamHandlerFactory.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/tomcat/TomcatStarter.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/EmbeddedWebApplicationContext.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/env/EnvironmentPostProcessor.java
*
/spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/ServletComponentHandler.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/LoggingSystemProperties.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/web/filter/OrderedHttpPutFormContentFilter.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ExitCodeGenerators.java

* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/SpringApplicationRunListener.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/tomcat/TomcatErrorPage.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/DefaultApplicationArguments.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/event/ApplicationStartingEvent.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jackson/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ImageBanner.java
*
/spring-boot-1-5-12-release-sources-jar/org/springframework/boot/system/SystemProperties.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/tomcat/TomcatEmbeddedContext.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/env/PropertiesPropertySourceLoader.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/diagnostics/FailureAnalyzer.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/InitParameterConfiguringServletContextInitializer.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/orm/jpa/hibernate/SpringImplicitNamingStrategy.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/MimeMappings.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/BeanDefinitionLoader.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/web/servlet/DelegatingFilterProxyRegistrationBean.java
*
/spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/Compression.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/diagnostics/AbstractFailureAnalyzer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/RelaxedDataBinder.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/LogFile.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/ContextIdApplicationContextInitializer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/info/InfoProperties.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/diagnostics/analyzer/PortInUseFailureAnalyzer.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/admin/SpringApplicationAdminMXBeanRegistrar.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/EmbeddedServletContainerFactory.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/undertow/FileSessionPersistence.java
*
/spring-boot-1-5-12-release-sources-jar/org/springframework/boot/env/YamlPropertySourceLoader.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/client/RestTemplateCustomizer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/orm/jpa/hibernate/SpringJtaPlatform.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/config/ResourceNotFoundException.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/ErrorPageRegistry.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/jetty/ServletContextInitializerConfiguration.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jackson/JsonObjectSerializer.java
* /spring-boot-1-5-12-release-sources-

jar/org/springframework/boot/jta/narayana/DataSourceXAResourceRecoveryHelper.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/json/GsonJsonParser.java
*
/spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/ServletComponentScan.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/event/ApplicationStartedEvent.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/WebFilterHandler.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/ServerPortInfoApplicationContextInitializer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/jetty/JasperInitializer.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/jta/narayana/NarayanaBeanFactoryPostProcessor.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ClearCachesApplicationListener.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/diagnostics/package-info.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/properties/EnableConfigurationPropertiesImportSelector.java
*
/spring-boot-1-5-12-release-sources-jar/org/springframework/boot/orm/jpa/hibernate/SpringNamingStrategy.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/PropertySourcesBinder.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/logging/log4j2/SpringBootConfigurationFactory.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/logging/logback/DefaultLogbackConfiguration.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ansi/AnsiColors.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/logback/SpringPropertyAction.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/system/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/FileEncodingApplicationListener.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/web/filter/OrderedHiddenHttpMethodFilter.java
*
/spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/tomcat/ConnectorStartFailedException.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/orm/jpa/EntityManagerFactoryBuilder.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/ServletRegistrationBean.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/LoggingSystem.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/filter/OrderedRequestContextFilter.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ansi/AnsiElement.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ApplicationHome.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/RegistrationBean.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/web/servlet/ServletListenerRegistrationBean.java
*
/spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jta/narayana/NarayanaConfigurationBean.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012-2018 the original author or authors.
*

* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/RelaxedNames.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jdbc/DatabaseDriver.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/RelaxedConversionService.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/client/RestTemplateBuilder.java
*
 /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/json/BasicJsonParser.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/tomcat/TomcatEmbeddedServletContainerFactory.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/undertow/UndertowEmbeddedServletContainerFactory.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/tomcat/TomcatEmbeddedServletContainer.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/properties/ConfigurationPropertiesBindingPostProcessor.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jackson/JsonObjectDeserializer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/servlet/MultipartConfigFactory.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/jetty/JettyEmbeddedServletContainer.java
*
 /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/web/servlet/ServletComponentScanRegistrar.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/tomcat/TomcatResources.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/env/PropertySourcesLoader.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/PropertiesConfigurationFactory.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/jetty/JettyEmbeddedServletContainerFactory.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/AbstractEmbeddedServletContainerFactory.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/PropertySourcesPropertyValues.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ansi/AnsiOutput.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/LoggingApplicationListener.java
*

/spring-boot-1-5-12-release-sources-jar/org/springframework/boot/system/ApplicationPidFileWriter.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/support/ErrorPageFilter.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/liquibase/LiquibaseServiceLocatorApplicationListener.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/web/filter/ApplicationContextHeaderFilter.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/config/AnsiOutputApplicationListener.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/system/EmbeddedServerPortFileWriter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/bind/DefaultPropertyNamePatternsMatcher.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/json/package-info.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/jta/bitronix/BitronixXADataSourceWrapper.java
*
/spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/undertow/UndertowBuilderCustomizer.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/jta/atomikos/AtomikosDependsOnBeanFactoryPostProcessor.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/yaml/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/json/JsonSimpleJsonParser.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/java/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/env/package-info.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/liquibase/SpringPackageScanClassResolver.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/env/EnumerableCompositePropertySource.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/jta/bitronix/BitronixXAConnectionFactoryWrapper.java
*

/spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/event/ApplicationPreparedEvent.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/jetty/JettyServerCustomizer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jta/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/logback/LogbackConfigurator.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/logback/package-info.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/jta/bitronix/BitronixDependentBeanFactoryPostProcessor.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/config/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/PatternPropertyNamePatternsMatcher.java
*
/spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/PropertyNamePatternsMatcher.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/log4j2/package-info.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/jta/atomikos/AtomikosXADataSourceWrapper.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/event/SpringApplicationEvent.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/liquibase/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/package-info.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/undertow/UndertowDeploymentInfoCustomizer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/Banner.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/properties/package-info.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/event/ApplicationEnvironmentPreparedEvent.java
*
/spring-boot-1-5-12-release-sources-jar/org/springframework/boot/orm/jpa/package-info.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/jetty/JettyEmbeddedWebAppContext.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/builder/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/StringToCharArrayConverter.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ansi/package-info.java
* /spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/jta/atomikos/AtomikosXAConnectionFactoryWrapper.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/StartupInfoLogger.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/undertow/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/package-info.java
*
/spring-boot-1-5-12-release-sources-
jar/org/springframework/boot/context/embedded/EmbeddedServletContainerInitializedEvent.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at

*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ApplicationPid.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/EmbeddedServletContainerCustomizer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/liquibase/CommonsLoggingLiquibaseLogger.java
*
 /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/log4j2/ExtendedWhitespaceThrowablePatternConverter.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/PropertyOrigin.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jta/bitronix/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jta/atomikos/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/properties/DeprecatedConfigurationProperty.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/cloud/CloudPlatform.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ApplicationArguments.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/event/ApplicationReadyEvent.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/event/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/properties/ConfigurationPropertiesBinding.java
*
 /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/json/JsonParser.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/OriginCapablePropertyValue.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ApplicationTemp.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/env/PropertySourceLoader.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/json/JsonJsonParser.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jta/atomikos/AtomikosConnectionFactoryBean.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/orm/jpa/hibernate/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/json/JsonParserFactory.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/properties/ConfigurationBeanFactoryMetaData.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jta/XAConnectionFactoryWrapper.java
*
 /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/AnnotationConfigEmbeddedWebApplicationContext.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ansi/AnsiBackground.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/admin/package-info.java

* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/SpringBootBanner.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/logback/SpringBootJoranConfigurator.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/cloud/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/RelaxedBindingNotWritablePropertyException.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/SpringBootVersion.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/EmbeddedServletContainer.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jta/atomikos/AtomikosDataSourceBean.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/properties/EnableConfigurationProperties.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/lang/package-info.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/event/ApplicationFailedEvent.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/env/SpringApplicationJsonEnvironmentPostProcessor.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ApplicationRunner.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/DeferredLog.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/bind/InetAddressEditor.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/log4j2/WhitespaceThrowablePatternConverter.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ansi/AnsiStyle.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/context/embedded/XmlEmbeddedWebApplicationContext.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/builder/ParentContextCloserApplicationListener.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/jta/XADataSourceWrapper.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/LoggingInitializationContext.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/CommandLineRunner.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/ansi/AnsiColor.java
* /spring-boot-1-5-12-release-sources-jar/org/springframework/boot/logging/logback/SpringProfileAction.java

1.35 commons-validator 1.4.1

1.35.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,

and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to

communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and

attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or

implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Commons Validator
Copyright 2001-2014 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.36 javax-annotation-api 1.3.2

1.36.1 Available under license :

COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL) Version 1.0

1. Definitions.

1.1. Contributor. means each individual or entity that creates or contributes to the creation of Modifications.

1.2. Contributor Version. means the combination of the Original Software, prior Modifications used by a Contributor (if any), and the Modifications made by that particular Contributor.

1.3. Covered Software. means (a) the Original Software, or (b) Modifications, or (c) the combination of files containing Original Software with files containing Modifications, in each case including portions thereof.

1.4. Executable. means the Covered Software in any form other than Source Code.

1.5. Initial Developer. means the individual or entity that first makes Original Software available under this License.

1.6. Larger Work. means a work which combines Covered Software or portions thereof with code not governed by the terms of this License.

1.7. License. means this document.

1.8.
Licensable. means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently acquired, any and all of the rights conveyed herein.

1.9. Modifications. means the Source Code and Executable form of any of the following:

A. Any file that results from an addition to, deletion from or modification of the contents of a file containing Original Software or previous Modifications;

B. Any new file that contains any part of the Original Software or previous Modification; or

C. Any new file that is contributed or otherwise made available under the terms of this License.

1.10. Original Software. means the Source Code and Executable form of computer software code that is originally released under this License.

1.11. Patent Claims. means any patent claim(s), now owned or hereafter acquired, including without limitation, method, process, and apparatus claims, in any patent Licensable by grantor.

1.12.
Source Code. means (a) the common form of computer software code in which modifications are made and (b) associated documentation included in or with such code.

1.13. You. (or .Your.) means an individual or a legal entity exercising rights under, and complying with all of the terms of, this License. For legal entities, .You. includes any entity which controls, is controlled by, or is under common control with You. For purposes of this definition, .control. means (a) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (b) ownership of more than fifty percent (50%) of the outstanding shares or beneficial ownership of such entity.

2. License Grants.

2.1. The Initial Developer Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, the Initial Developer hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under
intellectual property rights (other than patent or trademark) Licensable by Initial Developer, to use, reproduce, modify, display, perform, sublicense and distribute the Original Software (or portions thereof), with or without Modifications, and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using or selling of Original Software, to make, have made, use, practice, sell, and offer for sale, and/or otherwise dispose of the Original Software (or portions thereof).

(c) The licenses granted in Sections 2.1(a) and (b) are effective on the date Initial Developer first distributes or otherwise makes the Original Software available to a third party under the terms of this License.

(d) Notwithstanding Section 2.1(b) above, no patent license is granted: (1) for code that You delete from the Original Software, or (2) for infringements caused by: (i) the modification of the Original Software, or (ii) the combination of the Original Software
with other software or devices.

2.2. Contributor Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, each Contributor hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under intellectual property rights (other than patent or trademark) Licensable by Contributor to use, reproduce, modify, display, perform, sublicense and distribute the Modifications created by such Contributor (or portions thereof), either on an unmodified basis, with other Modifications, as Covered Software and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using, or selling of Modifications made by that Contributor either alone and/or in combination with its Contributor Version (or portions of such combination), to make, use, sell, offer for sale, have made, and/or otherwise dispose of: (1) Modifications made by that Contributor (or portions thereof); and (2) the
combination of Modifications made by that Contributor with its Contributor Version (or portions of such combination).

(c) The licenses granted in Sections 2.2(a) and 2.2(b) are effective on the date Contributor first distributes or otherwise makes the Modifications available to a third party.

(d) Notwithstanding Section 2.2(b) above, no patent license is granted: (1) for any code that Contributor has deleted from the Contributor Version; (2) for infringements caused by: (i) third party modifications of Contributor Version, or (ii) the combination of Modifications made by that Contributor with other software (except as part of the Contributor Version) or other devices; or (3) under Patent Claims infringed by Covered Software in the absence of Modifications made by that Contributor.

3. Distribution Obligations.

3.1. Availability of Source Code.
Any Covered Software that You distribute or otherwise make available in Executable form must also be made available
in Source Code form and that Source Code form must be distributed only under the terms of this License. You must include a copy of this License with every copy of the Source Code form of the Covered Software You distribute or otherwise make available. You must inform recipients of any such Covered Software in Executable form as to how they can obtain such Covered Software in Source Code form in a reasonable manner on or through a medium customarily used for software exchange.

3.2. Modifications.
The Modifications that You create or to which You contribute are governed by the terms of this License. You represent that You believe Your Modifications are Your original creation(s) and/or You have sufficient rights to grant the rights conveyed by this License.

3.3. Required Notices.
You must include a notice in each of Your Modifications that identifies You as the Contributor of the Modification. You may not remove or alter any copyright, patent or trademark notices
contained within the Covered Software, or any notices of licensing or any descriptive text giving attribution to any Contributor or the Initial Developer.

3.4. Application of Additional Terms.
You may not offer or impose any terms on any Covered Software in Source Code form that alters or restricts the applicable version of this License or the recipients. rights hereunder. You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However,

you may do so only on Your own behalf, and not on behalf of the Initial Developer or any Contributor. You must make it absolutely clear that any such warranty, support, indemnity or liability obligation is offered by You alone, and You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of warranty, support, indemnity or liability terms You offer.

3.5. Distribution of Executable Versions.

You may distribute the Executable form of the Covered Software under the terms of this License or under the terms of a license of Your choice, which may contain terms different from this License, provided that You are in compliance with the terms of this License and that the license for the Executable form does not attempt to limit or alter the recipient.s rights in the Source Code form from the rights set forth in this License. If You distribute the Covered Software in Executable form under a different license, You must make it absolutely clear that any terms which differ from this License are offered by You alone, not by the Initial Developer or Contributor. You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of any such terms You offer.

3.6. Larger Works.

You may create a Larger Work by combining Covered Software with other code not governed by the terms of this License and distribute the Larger Work as a single product. In such a case, You must make sure the requirements of this License are fulfilled for the Covered Software.

4. Versions of the License.

4.1. New Versions.

Sun Microsystems, Inc. is the initial license steward and may publish revised and/or new versions of this License from time to time. Each version will be given a distinguishing version number. Except as provided in Section 4.3, no one other than the license steward has the right to modify this License.

4.2. Effect of New Versions.

You may always continue to use, distribute or otherwise make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. If the Initial Developer includes a notice in the Original Software prohibiting it from being distributed or otherwise made available under any subsequent version of the License, You must distribute and make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. Otherwise, You may also choose to use, distribute or otherwise make the Covered Software available under the terms of any subsequent version of the License published by the license steward.

4.3. Modified Versions.

When You are an Initial Developer and You want to create a new license for Your Original Software, You may create and use a modified version of this License if You: (a) rename the license and remove any references to the name of the license steward (except to note that the license differs from this License); and (b) otherwise make it clear that the license contains terms which differ from this License.

5. DISCLAIMER OF WARRANTY.

COVERED SOFTWARE IS PROVIDED UNDER THIS LICENSE ON AN .AS IS. BASIS, WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION,

WARRANTIES
THAT THE COVERED SOFTWARE IS FREE OF DEFECTS, MERCHANTABLE, FIT FOR A PARTICULAR PURPOSE OR NON-INFRINGING. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE COVERED SOFTWARE IS WITH YOU. SHOULD ANY COVERED SOFTWARE PROVE DEFECTIVE IN ANY RESPECT, YOU (NOT THE INITIAL DEVELOPER OR ANY OTHER CONTRIBUTOR) ASSUME THE COST OF ANY NECESSARY SERVICING, REPAIR OR CORRECTION. THIS DISCLAIMER OF WARRANTY CONSTITUTES AN ESSENTIAL PART OF THIS LICENSE. NO USE OF ANY COVERED SOFTWARE IS AUTHORIZED HEREUNDER EXCEPT UNDER THIS DISCLAIMER.

6. TERMINATION.

6.1. This License and the rights granted hereunder will terminate automatically if You fail to comply with terms herein and fail to cure such breach within 30 days of becoming aware of the breach. Provisions which, by their nature, must remain in effect beyond the termination of this License shall survive.

6.2. If You assert a patent infringement claim (excluding declaratory judgment actions) against Initial Developer or a Contributor (the Initial Developer or Contributor against whom You assert such claim is referred to as .Participant.) alleging that the Participant Software (meaning the Contributor Version where the Participant is a Contributor or the Original Software where the Participant is the Initial Developer) directly or indirectly infringes any patent, then any and all rights granted directly or indirectly to You by such Participant, the Initial Developer (if the Initial Developer is not the Participant) and all Contributors under Sections 2.1 and/or 2.2 of this License shall, upon 60 days notice from Participant terminate prospectively and automatically at the expiration of such 60 day notice period, unless if within such 60 day period You withdraw Your claim with respect to the Participant Software against such Participant either unilaterally or pursuant to a written agreement with Participant.

6.3. In the event of termination under Sections 6.1 or 6.2 above, all end user licenses
that have been validly granted by You or any distributor hereunder prior to termination (excluding licenses granted to You by any distributor) shall survive termination.

7. LIMITATION OF LIABILITY.

UNDER NO CIRCUMSTANCES AND UNDER NO LEGAL THEORY, WHETHER TORT (INCLUDING NEGLIGENCE), CONTRACT, OR OTHERWISE, SHALL YOU, THE INITIAL DEVELOPER, ANY OTHER CONTRIBUTOR, OR ANY DISTRIBUTOR OF COVERED SOFTWARE, OR ANY SUPPLIER OF ANY OF SUCH PARTIES, BE LIABLE TO ANY PERSON FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY CHARACTER INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOST PROFITS, LOSS OF GOODWILL, WORK STOPPAGE, COMPUTER FAILURE OR MALFUNCTION, OR ANY AND ALL OTHER COMMERCIAL DAMAGES OR LOSSES, EVEN IF SUCH PARTY SHALL HAVE BEEN INFORMED OF THE POSSIBILITY OF SUCH DAMAGES. THIS LIMITATION OF LIABILITY SHALL NOT APPLY TO LIABILITY FOR DEATH OR PERSONAL INJURY RESULTING FROM SUCH PARTY.S NEGLIGENCE TO THE EXTENT APPLICABLE LAW PROHIBITS SUCH LIMITATION. SOME JURISDICTIONS
DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS EXCLUSION AND LIMITATION MAY NOT APPLY TO YOU.

8. U.S. GOVERNMENT END USERS.

The Covered Software is a .commercial item,. as that term is defined in 48 C.F.R. 2.101 (Oct. 1995), consisting of

.commercial computer software. (as that term is defined at 48 C.F.R. ? 252.227-7014(a)(1)) and .commercial computer software documentation. as such terms are used in 48 C.F.R. 12.212 (Sept. 1995). Consistent with 48 C.F.R. 12.212 and 48 C.F.R. 227.7202-1 through 227.7202-4 (June 1995), all U.S. Government End Users acquire Covered Software with only those rights set forth herein. This U.S. Government Rights clause is in lieu of, and supersedes, any other FAR, DFAR, or other clause or provision that addresses Government rights in computer software under this License.

9. MISCELLANEOUS.

This License represents the complete agreement concerning subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable. This License shall be governed by the law of the jurisdiction specified in a notice contained within the Original Software (except to the extent applicable law, if any, provides otherwise), excluding such jurisdiction.s conflict-of-law provisions. Any litigation relating to this License shall be subject to the jurisdiction of the courts located in the jurisdiction and venue specified in a notice contained within the Original Software, with the losing party responsible for costs, including, without limitation, court costs and reasonable attorneys. fees and expenses. The application of the United Nations Convention on Contracts for the International Sale of Goods is expressly excluded. Any law or regulation which provides that the language of a contract shall be construed against the drafter shall not apply to this License. You agree that You alone are responsible for compliance with the United States export administration regulations (and the export control laws and regulation of any other countries) when You use, distribute or otherwise make available any Covered Software.

10. RESPONSIBILITY FOR CLAIMS.

As between Initial Developer and the Contributors, each party is responsible for claims and damages arising, directly or indirectly, out of its utilization of rights under this License and You agree to work with Initial Developer and Contributors to distribute such responsibility on an equitable basis. Nothing herein is intended or shall be deemed to constitute any admission of liability.

NOTICE PURSUANT TO SECTION 9 OF THE COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL)

The code released under the CDDL shall be governed by the laws of the State of California (excluding conflict-of-law provisions). Any litigation relating to this License shall be subject to the jurisdiction of the Federal Courts of the Northern District of California and the state courts of the State of California, with venue lying in Santa Clara County, California.

The GNU General Public License (GPL) Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software,
we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer
you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any
program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its

contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute
verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that
in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works
in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or
executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under

the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code
for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute
the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives
a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only
way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear
what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY

COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These
Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

One line to give the program's name and a brief idea of what it does.

Copyright (C)

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY
or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'. This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits

your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.

signature of Ty Coon, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

"CLASSPATH" EXCEPTION TO THE GPL VERSION 2

Certain source files distributed by Sun Microsystems, Inc. are subject to the following clarification and special exception to the GPL Version 2, but only where Sun has expressly included in the particular
source file's header the words

"Sun designates this particular file as subject to the "Classpath" exception as provided by Sun in the License file that accompanied this code."

Linking this library statically or dynamically with other modules is making a combined work based on this library. Thus, the terms and conditions of the GNU General Public License Version 2 cover the whole combination.

As a special exception, the copyright holders of this library give you permission to link this library with independent modules to produce an executable, regardless of the license terms of these independent modules, and to copy and distribute the resulting executable under terms of your choice, provided that you also meet, for each linked independent module, the terms and conditions of the license of that module.? An independent module is a module which is not derived from or based on this library.? If you modify this library, you may extend this exception to your version of the library, but
you are not obligated to do so.? If you do not wish to do so, delete this exception statement from your version.

1.37 stax-ex 1.8

1.38 httpcore-nio 4.4.1

1.38.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions

to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the

content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache HttpCore NIO
Copyright 2005-2015 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.39 commons-collections 4.1

1.39.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership

of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual,

worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or

documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,

indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache Commons Collections
Copyright 2001-2015 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.40 httpasyncclient 4.1

1.40.1 Available under license :

Apache HttpAsyncClient
Copyright 2010-2015 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their

Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf

of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.41 commons-configuration 1.10

1.41.1 Available under license :

Apache Commons Configuration
Copyright 2001-2013 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of

the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or

agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.42 commons-codec 1.9

1.42.1 Available under license :

Apache Commons Codec
Copyright 2002-2013 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

src/test/org/apache/commons/codec/language/DoubleMetaphoneTest.java
contains test data from http://aspell.net/test/orig/batch0.tab.
Copyright (C) 2002 Kevin Atkinson (kevina@gnu.org)
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or
(iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from)
the Work and for which the
editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of

the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication
on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant
of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as
of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices

stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names
of the Licensor,
except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your
sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or
(iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,

and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work,

where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as

of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own

copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names
of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this

License. However, in accepting such obligations, You may act only
on Your own behalf and on Your
sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.43 commons-fileupload 1.4

1.43.1 Available under license :

Apache Commons FileUpload
Copyright 2002-2018 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including

the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or

Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the

origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier

identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.44 commons-digester 1.8.1

1.44.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,

including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of

this
License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside

or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Commons Digester
Copyright 2001-2008 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

1.45 xmlsec 1.5.7

1.45.1 Available under license :

Apache XML Security for Java
Copyright 2000-2014 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses

granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,

any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.46 reflections 0.9.11

1.46.1 Available under license :

No license file was found, but licenses were detected in source scan.

<name>The New BSD License</name>

Found in path(s):
* /reflections-0-9-11-sources-jar/META-INF/maven/org.reflections/reflections/pom.xml

1.47 resourcelocator 1.0.1

1.47.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright 2009 Sun Microsystems, Inc. All rights reserved.
*

* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can obtain
* a copy of the License at https://glassfish.dev.java.net/public/CDDL+GPL.html
* or glassfish/bootstrap/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at glassfish/bootstrap/legal/LICENSE.txt.
* Sun designates this particular file as subject to the "Classpath" exception
* as provided by Sun in the GPL Version
 2 section of the License file that
* accompanied this code. If applicable, add the following below the License
* Header, with the fields enclosed by brackets [] replaced by your own
* identifying information: "Portions Copyrighted [year]
* [name of copyright owner]"
*
* Contributor(s):
*
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
* holder.
*/

Found
 in path(s):
* /osgi-resource-locator-1-0-1-sources-jar/org/glassfish/hk2/osgiresourcelocator/ResourceFinderImpl.java
* /osgi-resource-locator-1-0-1-sources-jar/org/glassfish/hk2/osgiresourcelocator/ServiceLoaderImpl.java
* /osgi-resource-locator-1-0-1-sources-jar/org/glassfish/hk2/osgiresourcelocator/Activator.java
* /osgi-resource-locator-1-0-1-sources-jar/org/glassfish/hk2/osgiresourcelocator/ServiceLoader.java
* /osgi-resource-locator-1-0-1-sources-jar/org/glassfish/hk2/osgiresourcelocator/ResourceFinder.java

1.48 stax-api 1.0-2

1.49 grpc-context 1.9.0

1.49.1 Available under license :

```
/*
* Copyright 2016, gRPC Authors All rights reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation

source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this

License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided

that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.50 opentracing-noop 0.31.0

1.50.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016-2018 The OpenTracing Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except

* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /opentracing-noop-0-31-0-sources-jar/io/opentracing/noop/NoopTracer.java
* /opentracing-noop-0-31-0-sources-jar/io/opentracing/noop/NoopSpan.java
* /opentracing-noop-0-31-0-sources-jar/io/opentracing/noop/NoopSpanContext.java
* /opentracing-noop-0-31-0-sources-jar/io/opentracing/noop/NoopSpanBuilder.java
*
 /opentracing-noop-0-31-0-sources-jar/io/opentracing/noop/NoopScopeManager.java
* /opentracing-noop-0-31-0-sources-jar/io/opentracing/noop/NoopTracerFactory.java
No license file was found, but licenses were detected in source scan.

2018 The OpenTracing Authors

  Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
  in compliance with the License. You may obtain a copy of the License at

  http://www.apache.org/licenses/LICENSE
2.0

  Unless required by applicable law or agreed to in writing, software distributed under the License
  is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
  or implied. See the License for the specific language governing permissions and limitations under
  the License.

Found in path(s):
* /opentracing-noop-0-31-0-sources-jar/META-INF/maven/io.opentracing/opentracing-noop/pom.xml

1.51 grpc-protobuf-lite 1.9.0

1.52 opencensus-api 0.10.0

1.53 opencensus-contrib-grpc-metrics 0.10.0

1.54 okio 1.15.0

1.55 scalap 2.10.0

1.56 okio 1.12.0

1.57 opentracing-web-servlet-filter 0.1.0

1.57.1 Available under license :

Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source"

form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely
link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean
Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and
You must cause any modified files to carry prominent notices stating that You changed the files; and
You must retain, in the Source form of any Derivative Works that You distribute,
all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the
NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.
5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the
trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend,

and hold each Contributor
harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: HOW TO APPLY THE APACHE LICENSE TO YOUR WORK
To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless
required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.58 reflectasm 1.07

1.59 opentracing-util 0.31.0

1.59.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016-2018 The OpenTracing Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either

express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /opentracing-util-0-31-0-sources-jar/io/opentracing/util/AutoFinishScopeManager.java
* /opentracing-util-0-31-0-sources-jar/io/opentracing/util/ThreadLocalScope.java
* /opentracing-util-0-31-0-sources-jar/io/opentracing/util/ThreadLocalScopeManager.java
* /opentracing-util-0-31-0-sources-jar/io/opentracing/util/GlobalTracer.java
*
/opentracing-util-0-31-0-sources-jar/io/opentracing/util/AutoFinishScope.java
No license file was found, but licenses were detected in source scan.

2018 The OpenTracing Authors

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
in compliance with the License. You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE
2.0

Unless required by applicable law or agreed to in writing, software distributed under the License
is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
or implied. See the License for the specific language governing permissions and limitations under
the License.

Found in path(s):
* /opentracing-util-0-31-0-sources-jar/META-INF/maven/io.opentracing/opentracing-util/pom.xml

1.60 javaip 0.16

1.60.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by

the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but

excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the

appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Java IPv6
Copyright 2013 Jan Van Besien

1.61 bson4jackson 2.7.0

1.62 jtoml 1.0.0

1.63 wsdl4j 1.6.2

1.63.1 Available under license :

THE ACCOMPANYING PROGRAM IS PROVIDED UNDER THE TERMS OF THIS COMMON PUBLIC LICENSE ("AGREEMENT"). ANY USE, REPRODUCTION OR DISTRIBUTION OF THE PROGRAM CONSTITUTES RECIPIENT'S ACCEPTANCE OF THIS AGREEMENT.

1. DEFINITIONS

"Contribution" means:

a) in the case of the initial Contributor, the initial code and documentation distributed under this Agreement, and

b) in the case of each subsequent Contributor:

i) changes to the Program, and

ii) additions to the Program;

where such changes and/or additions to the Program originate from and are distributed by that particular Contributor. A Contribution 'originates' from a Contributor if it was added to the Program by such Contributor itself or anyone acting on such Contributor's behalf. Contributions do not include additions to the Program which: (i) are separate modules of software distributed in conjunction with the Program under their own license agreement, and (ii) are not derivative works of the Program.

"Contributor"

means any person or entity that distributes the Program.

"Licensed Patents " mean patent claims licensable by a Contributor which are necessarily infringed by the use or sale of its Contribution alone or when combined with the Program.

"Program" means the Contributions distributed in accordance with this Agreement.

"Recipient" means anyone who receives the Program under this Agreement, including all Contributors.

2. GRANT OF RIGHTS

a) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free copyright license to reproduce, prepare derivative works of, publicly display, publicly perform, distribute and sublicense the Contribution of such Contributor, if any, and such derivative works, in source code and object code form.

b) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free patent license under Licensed Patents to make, use, sell, offer
to sell, import and otherwise transfer the
Contribution of such Contributor, if any, in source code and object code form. This patent license shall apply to the combination of the Contribution and the Program if, at the time the Contribution is added by the Contributor, such addition of the Contribution causes such combination to be covered by the Licensed Patents. The patent license shall not apply to any other combinations which include the Contribution. No hardware per se is licensed hereunder.

c) Recipient understands that although each Contributor grants the licenses to its Contributions set forth herein, no assurances are provided by any Contributor that the Program does not infringe the patent or other intellectual property rights of any other entity. Each Contributor disclaims any liability to Recipient for claims brought by any other entity based on infringement of intellectual property rights or otherwise. As a condition to exercising the rights and licenses granted hereunder,
each Recipient hereby assumes sole
responsibility to secure any other intellectual property rights needed, if any. For example, if a third party patent license is required to allow Recipient to distribute the Program, it is Recipient's responsibility to acquire that license before distributing the Program.

d) Each Contributor represents that to its knowledge it has sufficient copyright rights in its Contribution, if any, to grant the copyright license set forth in this Agreement.

3. REQUIREMENTS

A Contributor may choose to distribute the Program in object code form under its own license agreement, provided that:

a) it complies with the terms and conditions of this Agreement; and

b) its license agreement:

i) effectively disclaims on behalf of all Contributors all warranties and conditions, express and implied, including warranties or conditions of title and non-infringement, and implied warranties or conditions of merchantability and fitness for a particular
purpose;

ii) effectively excludes on behalf of all Contributors all liability for damages, including direct, indirect, special, incidental and consequential damages, such as lost profits;

iii) states that any provisions which differ from this Agreement are offered by that Contributor alone and not by any other party; and

iv) states that source code for the Program is available from such Contributor, and informs licensees how to obtain it in a reasonable manner on or through a medium customarily used for software exchange.

When the Program is made available in source code form:

a) it must be made available under this Agreement; and

b) a copy of this Agreement must be included with each copy of the Program.

Contributors may not remove or alter any copyright notices contained within the Program.

Each Contributor must identify itself as the originator of its Contribution, if any, in a manner that reasonably allows subsequent Recipients to identify the originator
of the Contribution.

4. COMMERCIAL DISTRIBUTION

Commercial distributors of software may accept certain responsibilities with respect to end users, business partners and the like. While this license is intended to facilitate the commercial use of the Program, the Contributor who includes the Program in a commercial product offering should do so in a manner which does not create potential liability for other Contributors. Therefore, if a Contributor includes the Program in a commercial product offering, such Contributor ("Commercial Contributor") hereby agrees to defend and indemnify

every other Contributor ("Indemnified Contributor") against any losses, damages and costs (collectively "Losses") arising from claims, lawsuits and other legal actions brought by a third party against the Indemnified Contributor to the extent caused by the acts or omissions of such Commercial Contributor in connection with its distribution of the Program in a commercial product offering. The obligations
in this section do not apply to any claims or Losses
relating to any actual or alleged intellectual property infringement. In order to qualify, an Indemnified Contributor must: a) promptly notify the Commercial Contributor in writing of such claim, and b) allow the Commercial Contributor to control, and cooperate with the Commercial Contributor in, the defense and any related settlement negotiations. The Indemnified Contributor may participate in any such claim at its own expense.

For example, a Contributor might include the Program in a commercial product offering, Product X. That Contributor is then a Commercial Contributor. If that Commercial Contributor then makes performance claims, or offers warranties related to Product X, those performance claims and warranties are such Commercial Contributor's responsibility alone. Under this section, the Commercial Contributor would have to defend claims against the other Contributors related to those performance claims and warranties, and
if a court
requires any other Contributor to pay any damages as a result, the Commercial Contributor must pay those damages.

5. NO WARRANTY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, THE PROGRAM IS PROVIDED ON AN "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, EITHER EXPRESS OR IMPLIED INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OR CONDITIONS OF TITLE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each Recipient is solely responsible for determining the appropriateness of using and distributing the Program and assumes all risks associated with its exercise of rights under this Agreement, including but not limited to the risks and costs of program errors, compliance with applicable laws, damage to or loss of data, programs or equipment, and unavailability or interruption of operations.

6. DISCLAIMER OF LIABILITY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, NEITHER RECIPIENT NOR ANY CONTRIBUTORS SHALL HAVE ANY LIABILITY FOR ANY DIRECT,
INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION LOST PROFITS), HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OR DISTRIBUTION OF THE PROGRAM OR THE EXERCISE OF ANY RIGHTS GRANTED HEREUNDER, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. GENERAL

If any provision of this Agreement is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this Agreement, and without further action by the parties hereto, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

If Recipient institutes patent litigation against a Contributor with respect to a patent applicable to software (including a cross-claim or counterclaim in a lawsuit), then any patent licenses granted by that Contributor to such Recipient under this Agreement shall terminate as of the date such litigation is filed. In addition, if Recipient institutes patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Program itself (excluding combinations of the Program with other software or hardware) infringes such Recipient's patent(s), then such Recipient's rights granted under Section 2(b) shall terminate as of the date such litigation is filed.

All Recipient's rights under this Agreement shall terminate if it fails to comply with any of the material terms or conditions of this Agreement and does not cure such failure in a reasonable period of time after becoming aware of such noncompliance. If all Recipient's rights under this Agreement terminate, Recipient agrees to cease use and distribution of the Program as soon as reasonably practicable. However, Recipient's obligations under this Agreement and any licenses granted by Recipient relating to the Program shall continue and survive.

Everyone is permitted to copy and distribute copies of this Agreement, but in order to avoid inconsistency the Agreement is copyrighted and may only be modified in the following manner. The Agreement Steward reserves the right to publish new versions (including revisions) of this Agreement from time to time. No one other than the Agreement Steward has the right to modify this Agreement. IBM is the initial Agreement Steward. IBM may assign the responsibility to serve as the Agreement Steward to a suitable separate entity. Each new version of the Agreement will be given a distinguishing version number. The Program (including Contributions) may always be distributed subject to the version of the Agreement under which it was received. In addition, after a new version of the Agreement is published, Contributor may elect to distribute the Program (including its Contributions) under the new version. Except as expressly stated in Sections 2(a) and 2(b) above, Recipient receives no rights or licenses to the intellectual property of any Contributor under this Agreement, whether expressly, by implication, estoppel or otherwise. All rights in the Program not expressly granted under this Agreement are reserved.

This Agreement is governed by the laws of the State of New York and the

intellectual property laws of the United States of America. No party to this Agreement will bring a legal action under this Agreement more than one year after the cause of action arose. Each party waives its rights to a jury trial in any resulting litigation.

1.64 classmate 0.8.0

1.65 android-json 0.0.20131108.vaadin1

1.66 jzlib 1.0.7

1.67 jeromq 0.3.2

1.67.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <http://fsf.org/>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser General Public License, and the "GNU GPL" refers to version 3 of the GNU General Public License.

"The Library" refers to a covered work governed by this License, other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library. Defining a subclass of a class defined by the

Library is deemed a mode
of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the "Linked Version".

The "Minimal Corresponding Source" for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or

b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters,
data structure
layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would

otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall

apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

1.68 typetools 0.3.1

1.69 paranamer 2.5.6

1.70 redline 1.2.6

1.71 diffutils 1.2.1

1.71.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form
shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely
link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean
Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and

You must cause any modified files to carry prominent notices stating that You changed the files; and

You must retain, in the Source form of any Derivative Works that You distribute,

all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum
to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.
You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.
5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use
the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor
harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.72 jakarta xml bind api 2.3.2

1.72.1 Available under license :

Notices for Eclipse Project for JAXB

This content is produced and maintained by the Eclipse Project for JAXB project.

* Project home: https://projects.eclipse.org/projects/ee4j.jaxb

Trademarks

Eclipse Project for JAXB is a trademark of the Eclipse Foundation.

Copyright

All content is the property of the respective authors or their employers. For
more information regarding authorship of content, please consult the listed
source code repository logs.

Declared Project Licenses

This program and the accompanying materials are made available under the terms
of the Eclipse Distribution License v. 1.0 which is available
at http://www.eclipse.org/org/documents/edl-v10.php.

SPDX-License-Identifier: BSD-3-Clause

Source Code

The project maintains the following source code repositories:

* https://github.com/eclipse-ee4j/jaxb-api

Third-party Content

This project leverages the following third party content.

None

Cryptography

Content may contain encryption software.
The country in which you are currently
may have restrictions on the import, possession, and use, and/or re-export to
another country, of encryption software. BEFORE using any encryption software,
please check the country's laws, regulations and policies concerning the import,
possession, or use, and re-export of encryption software, to see if this is
permitted.

Copyright (c) 2017, 2018 Oracle and/or its affiliates. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

- Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

- Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

- Neither the name of the Eclipse Foundation, Inc. nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO,

THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.73 apiguardian-api 1.0.0

1.74 minio 4.0.0

1.75 animal-sniffer-annotation 1.14

1.76 jcip-annotation 1.0

1.76.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2005 Brian Goetz and Tim Peierls
* Released under the Creative Commons Attribution License
* (http://creativecommons.org/licenses/by/2.5)
* Official home: http://www.jcip.net
*
* Any republication or derived work distributed in source code form
* must include this copyright and license notice.
*/

Found in path(s):
* /jcip-annotations-1-0-sources-jar/net/jcip/annotations/ThreadSafe.java
* /jcip-annotations-1-0-sources-jar/net/jcip/annotations/NotThreadSafe.java
* /jcip-annotations-1-0-sources-jar/net/jcip/annotations/Immutable.java
* /jcip-annotations-1-0-sources-jar/net/jcip/annotations/GuardedBy.java
No license file was found, but licenses were detected in source scan.

<html>
<body>

Class, field, and method level annotations for describing thread-safety policies.

Three class-level annotations describe the intended thread-safety promises of a class:
<code>@Immutable</code>, <code>@ThreadSafe</code>, and <code>@NotThreadSafe</code>.
<code>@Immutable</code> means that the class is immutable,
and implies <code>@ThreadSafe</code>.
<code>@NotThreadSafe</code> is optional;
if a class is not annotated as thread-safe, it should be presumed not to be
thread-safe, but if you want to make it extra clear, use
<code>@NotThreadSafe</code>.

These annotations are relatively unintrusive and are beneficial to
both users and maintainers. Users can see immediately whether a class
is thread-safe, and maintainers can see immediately whether
thread-safety guarantees must be preserved. Annotations are also
useful to a third
constituency: tools. Static code-analysis tools may
be able to verify that the code complies with the contract indicated
by the annotation, such as verifying that a class annotated with
<code>@Immutable</code> actually is immutable.

<h2>Field and method annotations</h2>

The class-level annotations above are part of the public documentation
for the class. Other aspects of a class's thread-safety strategy are
entirely for maintainers and are not part of its public documentation.

Classes that use locking should document which state variables are
guarded with which locks, and which locks are used to guard those
variables. A common source of inadvertent non-thread-safety is when a
thread-safe class consistently uses locking to guard its state, but is
later modified to add either new state variables that are not
adequately guarded by locking, or new methods that do not use locking
properly to guard the existing state variables.
 Documenting which
variables are guarded by which locks can help prevent both types of
omissions.

The <code>@GuardedBy(lock)</code> annotation documents that a field or method should
be accessed only with a specific lock held.

<h2>Copyright and license</h2>

This software is copyright (c) 2005 Brian Goetz and Tim Peierls
and is released under the Creative Commons Attribution License
(http://creativecommons.org/licenses/by/2.5). The official home
for this software is http://www.jcip.net.
Any republication or derived work distributed in source code form
must include the copyright and license notice.

</body>
</html>

Found in path(s):
* /jcip-annotations-1-0-sources-jar/net/jcip/annotations/package.html

1.77 jcip-annotation 1.0-1

1.78 javax-inject 1

1.78.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2009 The JSR-330 Expert Group
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.

*/

Found in path(s):
* /javax-inject-1-sources-jar/javax/inject/Singleton.java
* /javax-inject-1-sources-jar/javax/inject/Inject.java
* /javax-inject-1-sources-jar/javax/inject/Scope.java
* /javax-inject-1-sources-jar/javax/inject/Qualifier.java
* /javax-inject-1-sources-jar/javax/inject/Named.java
* /javax-inject-1-sources-jar/javax/inject/Provider.java
*
/javax-inject-1-sources-jar/javax/inject/package-info.java

1.79 jackson-mapper-asl 1.9.13

1.79.1 Available under license :

No license file was found, but licenses were detected in source scan.

/* Jackson JSON-processor.
*
* Copyright (c) 2007- Tatu Saloranta, tatu.saloranta@iki.fi
*
* Licensed under the License specified in file LICENSE, included with
* the source code and binary code bundles.
* You may not use this file except in compliance with the License.
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /jackson-mapper-asl-1-9-13-sources-jar/org/codehaus/jackson/map/MappingJsonFactory.java

1.80 tiger-types 1.4

1.80.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2010 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU

* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
 subject to such option by the copyright
* holder.
*/

Found in path(s):
* /tiger-types-1-4-sources-jar/org/jvnet/tiger_types/WildcardTypeImpl.java
* /tiger-types-1-4-sources-jar/org/jvnet/tiger_types/TypeVisitor.java
* /tiger-types-1-4-sources-jar/org/jvnet/tiger_types/Lister.java
* /tiger-types-1-4-sources-jar/org/jvnet/tiger_types/Types.java
* /tiger-types-1-4-sources-jar/org/jvnet/tiger_types/ParameterizedTypeImpl.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2010 Oracle and/or its affiliates. All rights reserved.

```
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License").  You
* may not use this file except in compliance with the License.  You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt.  See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license."  If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above.  However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject
 to such option by the copyright
* holder.
*/
```

Found in path(s):
* /tiger-types-1-4-sources-jar/org/jvnet/tiger_types/GenericArrayTypeImpl.java

1.81 qdox 1.12

1.82 xpp 1.1.4c

1.83 hamcrest-all 1.3

1.84 javax-ws-rs-api 2.0.1

1.84.1 Available under license :

COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL) Version 1.1

1. Definitions.

1.1. "Contributor" means each individual or entity that creates or contributes to the creation of Modifications.

1.2. "Contributor Version" means the combination of the Original Software, prior Modifications used by a Contributor (if any), and the Modifications made by that particular Contributor.

1.3. "Covered Software" means (a) the Original Software, or (b) Modifications, or (c) the combination of files containing Original Software with files containing Modifications, in each case including portions thereof.

1.4. "Executable" means the Covered Software in any form other than Source Code.

1.5. "Initial Developer" means the individual or entity that first makes Original Software available under this License.

1.6. "Larger Work" means a work which combines Covered Software or portions thereof with code not governed by the terms of this License.

1.7. "License" means this document.

1.8. "Licensable" means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently acquired, any and all of the rights conveyed herein.

1.9. "Modifications" means the Source Code and Executable form of any of the following:

A. Any file that results from an addition to, deletion from or

modification of the contents of a file containing Original Software or previous Modifications;

B. Any new file that contains any part of the Original Software or previous Modification; or

C. Any new file that is contributed or otherwise made available under the terms of this License.

1.10. "Original Software" means the Source Code and Executable form of computer software code that is originally released under this License.

1.11. "Patent Claims" means any patent claim(s), now owned or hereafter acquired, including without limitation, method, process, and apparatus claims, in any patent Licensable by grantor.

1.12. "Source Code" means (a) the common form of computer software code in which modifications are made and (b) associated documentation included in or with such code.

1.13. "You" (or "Your") means an individual or a legal entity exercising rights under, and complying with all of the terms of, this License. For legal entities, "You" includes any entity which controls, is controlled by, or is under common control with You. For purposes of this definition, "control" means (a) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (b) ownership of more than fifty percent (50%) of the outstanding shares or beneficial ownership of such entity.

2. License Grants.

2.1. The Initial Developer Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, the Initial Developer hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under intellectual property rights (other than patent or trademark) Licensable by Initial Developer, to use, reproduce, modify, display, perform, sublicense and distribute the Original Software (or portions thereof), with or without Modifications, and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using or selling of

Original Software, to make, have made, use, practice, sell, and offer for sale, and/or otherwise dispose of the Original Software (or portions thereof).

(c) The licenses granted in Sections 2.1(a) and (b) are effective on the date Initial Developer first distributes or otherwise makes the Original Software available to a third party under the terms of this License.

(d) Notwithstanding Section 2.1(b) above, no patent license is granted: (1) for code that You delete from the Original Software, or (2) for infringements caused by: (i) the modification of the Original Software, or (ii) the combination of the Original Software with other software or devices.

2.2. Contributor Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, each Contributor hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under intellectual property rights (other than patent or trademark) Licensable by Contributor to use, reproduce, modify, display, perform, sublicense and distribute the Modifications created by such Contributor (or portions thereof), either on an unmodified basis, with other Modifications, as Covered Software and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using, or selling of Modifications made by that Contributor either alone and/or in combination with its Contributor Version (or portions of such combination), to make, use, sell, offer for sale, have made, and/or otherwise dispose of: (1) Modifications made by that Contributor (or portions thereof); and (2) the combination of Modifications made by that Contributor with its Contributor Version (or portions of such combination).

(c) The licenses granted in Sections 2.2(a) and 2.2(b) are effective on the date Contributor first distributes or otherwise makes the Modifications available to a third party.

(d) Notwithstanding Section 2.2(b) above, no patent license is granted: (1) for any code that Contributor has deleted from the Contributor Version; (2) for infringements caused by: (i) third party modifications of Contributor Version, or (ii) the combination of Modifications made by that Contributor with other software

(except as part of the Contributor Version) or other devices; or (3) under Patent Claims infringed by Covered Software in the absence of Modifications made by that Contributor.

3. Distribution Obligations.

3.1. Availability of Source Code.

Any Covered Software that You distribute or otherwise make available
in Executable form must also be made available in Source Code form and that Source Code form must be distributed only under the terms of this License. You must include a copy of this License with every copy of the Source Code form of the Covered Software You distribute or otherwise make available. You must inform recipients of any such Covered Software in Executable form as to how they can obtain such Covered Software in Source Code form in a reasonable manner on or through a medium customarily used for software exchange.

3.2. Modifications.

The Modifications that You create or to which You contribute are governed by the terms of this License. You represent that You believe Your Modifications are Your original creation(s) and/or You have sufficient rights to grant the rights conveyed by this License.

3.3. Required Notices.

You must include a notice in each of Your Modifications that identifies You as the Contributor of the Modification. You
may not
remove or alter any copyright, patent or trademark notices contained within the Covered Software, or any notices of licensing or any descriptive text giving attribution to any Contributor or the Initial Developer.

3.4. Application of Additional Terms.

You may not offer or impose any terms on any Covered Software in Source Code form that alters or restricts the applicable version of this License or the recipients' rights hereunder. You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, you may do so only on Your own behalf, and not on behalf of the Initial Developer or any Contributor. You must make it absolutely clear that any such warranty, support, indemnity or liability obligation is offered by You alone, and You hereby agree to indemnify the Initial Developer and every Contributor for any

liability incurred by the Initial Developer or such
Contributor as a
result of warranty, support, indemnity or liability terms You offer.

3.5. Distribution of Executable Versions.

You may distribute the Executable form of the Covered Software under the terms of this License or under the terms of a license of Your choice, which may contain terms different from this License, provided that You are in compliance with the terms of this License and that the license for the Executable form does not attempt to limit or alter the recipient's rights in the Source Code form from the rights set forth in this License. If You distribute the Covered Software in Executable form under a different license, You must make it absolutely clear that any terms which differ from this License are offered by You alone, not by the Initial Developer or Contributor. You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of any such terms You offer.

3.6. Larger Works.

You may create a Larger Work by combining Covered Software with other code not governed by the terms of this License and distribute the Larger Work as a single product. In such a case, You must make sure the requirements of this License are fulfilled for the Covered Software.

4. Versions of the License.

4.1. New Versions.

Oracle is the initial license steward and may publish revised and/or new versions of this License from time to time. Each version will be given a distinguishing version number. Except as provided in Section 4.3, no one other than the license steward has the right to modify this License.

4.2. Effect of New Versions.

You may always continue to use, distribute or otherwise make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. If the Initial Developer includes a notice in the Original Software prohibiting it
from being distributed or otherwise made available
under any subsequent version of the License, You must distribute and

make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. Otherwise, You may also choose to use, distribute or otherwise make the Covered Software available under the terms of any subsequent version of the License published by the license steward.

4.3. Modified Versions.

When You are an Initial Developer and You want to create a new license for Your Original Software, You may create and use a modified version of this License if You: (a) rename the license and remove any references to the name of the license steward (except to note that the license differs from this License); and (b) otherwise make it clear that the license contains terms which differ from this License.

5. DISCLAIMER OF WARRANTY.

COVERED SOFTWARE IS PROVIDED UNDER THIS LICENSE ON AN "AS IS" BASIS,
WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES THAT THE COVERED SOFTWARE IS FREE OF DEFECTS, MERCHANTABLE, FIT FOR A PARTICULAR PURPOSE OR NON-INFRINGING. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE COVERED SOFTWARE IS WITH YOU. SHOULD ANY COVERED SOFTWARE PROVE DEFECTIVE IN ANY RESPECT, YOU (NOT THE INITIAL DEVELOPER OR ANY OTHER CONTRIBUTOR) ASSUME THE COST OF ANY NECESSARY SERVICING, REPAIR OR CORRECTION. THIS DISCLAIMER OF WARRANTY CONSTITUTES AN ESSENTIAL PART OF THIS LICENSE. NO USE OF ANY COVERED SOFTWARE IS AUTHORIZED HEREUNDER EXCEPT UNDER THIS DISCLAIMER.

6. TERMINATION.

6.1. This License and the rights granted hereunder will terminate automatically if You fail to comply with terms herein and fail to cure such breach within 30 days of becoming aware of the breach. Provisions which, by their nature, must remain in effect beyond the termination of this License shall survive.

6.2. If You assert a patent infringement claim (excluding declaratory judgment actions) against Initial Developer or a Contributor (the Initial Developer or Contributor against whom You assert such claim is referred to as "Participant") alleging that the Participant Software (meaning the Contributor Version where the Participant is a Contributor or the Original Software where the Participant is the Initial Developer) directly or indirectly infringes any patent, then any and all rights granted directly or indirectly to You by such Participant, the Initial Developer (if the

Initial Developer is not the Participant) and all Contributors under Sections 2.1 and/or 2.2 of this License shall, upon 60 days notice from Participant terminate prospectively and automatically at the expiration of such 60 day notice period, unless if within such 60 day period You withdraw Your claim with respect to the Participant Software against such Participant either unilaterally or pursuant to a written agreement with Participant.

6.3. If You assert a patent infringement claim against Participant alleging that the Participant Software directly or indirectly infringes any patent where such claim is resolved (such as by license or settlement) prior to the initiation of patent infringement litigation, then the reasonable value of the licenses granted by such Participant under Sections 2.1 or 2.2 shall be taken into account in determining the amount or value of any payment or license.

6.4. In the event of termination under Sections 6.1 or 6.2 above, all end user licenses that have been validly granted by You or any distributor hereunder prior to termination (excluding licenses granted to You by any distributor) shall survive termination.

7. LIMITATION OF LIABILITY.

UNDER NO CIRCUMSTANCES AND UNDER NO LEGAL THEORY, WHETHER TORT (INCLUDING NEGLIGENCE), CONTRACT, OR OTHERWISE, SHALL YOU, THE INITIAL DEVELOPER, ANY OTHER CONTRIBUTOR, OR ANY DISTRIBUTOR OF COVERED SOFTWARE, OR ANY SUPPLIER OF ANY OF SUCH PARTIES, BE LIABLE TO ANY PERSON FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY CHARACTER INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF GOODWILL, WORK STOPPAGE, COMPUTER FAILURE OR MALFUNCTION, OR ANY AND ALL OTHER COMMERCIAL DAMAGES OR LOSSES, EVEN IF SUCH PARTY SHALL HAVE BEEN INFORMED OF THE POSSIBILITY OF SUCH DAMAGES. THIS LIMITATION OF LIABILITY SHALL NOT APPLY TO LIABILITY FOR DEATH OR PERSONAL INJURY RESULTING FROM SUCH PARTY'S NEGLIGENCE TO THE EXTENT APPLICABLE LAW PROHIBITS SUCH LIMITATION. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS EXCLUSION AND LIMITATION MAY NOT APPLY TO YOU.

8. U.S. GOVERNMENT END USERS.

The Covered Software is a "commercial item," as that term is defined in 48 C.F.R. 2.101 (Oct. 1995), consisting of "commercial computer software" (as that term is defined

at 48 C.F.R. §
252.227-7014(a)(1)) and "commercial computer software documentation"
as such terms are used in 48 C.F.R. 12.212 (Sept. 1995). Consistent
with 48 C.F.R. 12.212 and 48 C.F.R. 227.7202-1 through 227.7202-4
(June 1995), all U.S. Government End Users acquire Covered Software
with only those rights set forth herein. This U.S. Government Rights
clause is in lieu of, and supersedes, any other FAR, DFAR, or other
clause or provision that addresses Government rights in computer
software under this License.

9. MISCELLANEOUS.

This License represents the complete agreement concerning subject
matter hereof. If any provision of this License is held to be
unenforceable, such provision shall be reformed only to the extent
necessary to make it enforceable. This License shall be governed by
the law of the jurisdiction specified in a notice contained within
the Original Software (except to the extent applicable law, if any,
provides otherwise), excluding such
jurisdiction's conflict-of-law
provisions. Any litigation relating to this License shall be subject
to the jurisdiction of the courts located in the jurisdiction and
venue specified in a notice contained within the Original Software,
with the losing party responsible for costs, including, without
limitation, court costs and reasonable attorneys' fees and expenses.
The application of the United Nations Convention on Contracts for
the International Sale of Goods is expressly excluded. Any law or
regulation which provides that the language of a contract shall be
construed against the drafter shall not apply to this License. You
agree that You alone are responsible for compliance with the United
States export administration regulations (and the export control
laws and regulation of any other countries) when You use, distribute
or otherwise make available any Covered Software.

10. RESPONSIBILITY FOR CLAIMS.

As between Initial Developer and the Contributors,
each party is
responsible for claims and damages arising, directly or indirectly,
out of its utilization of rights under this License and You agree to
work with Initial Developer and Contributors to distribute such
responsibility on an equitable basis. Nothing herein is intended or
shall be deemed to constitute any admission of liability.
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*

* Copyright (c) 2010-2013 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* http://glassfish.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject
 to such option by the copyright
* holder.
*/

Found in path(s):
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/ext/FactoryFinder.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/core/Request.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/GET.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/MatrixParam.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/OPTIONS.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/core/UriInfo.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/ext/RuntimeDelegate.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/CookieParam.java

* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/ext/MessageBodyReader.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/HEAD.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/core/NewCookie.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/core/UriBuilder.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/POST.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/DefaultValue.java
*
/javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/ApplicationPath.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/DELETE.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/package-info.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/core/Application.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/QueryParam.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/PathParam.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/PUT.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/core/Cookie.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/core/Variant.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/Consumes.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/client/FactoryFinder.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/core/HttpHeaders.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/FormParam.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/core/EntityTag.java
* /javax-ws-rs-api-2-0-1-sources-jar/javax/ws/rs/Produces.java

1.85 asm 5.0.4

1.85.1 Available under license :

No license file was found, but licenses were detected in source scan.

/***
* ASM: a very small and fast Java bytecode manipulation framework
* Copyright (c) 2000-2011 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*   contributors may be used to endorse or promote products derived from
*   this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS

"AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/
/**
   * Creates a new JSRInliner. Subclasses must not use this
   * constructor. Instead, they must use the
   * {@link #JSRInlinerAdapter(int, MethodVisitor, int, String, String, String, String[])}
   * version.
   *
   * @param mv
   *
  the <code>MethodVisitor</code> to send the resulting inlined
   *   method code to (use <code>null</code> for none).
   * @param access
   *   the method's access flags (see {@link Opcodes}). This
   *   parameter also indicates if the method is synthetic and/or
   *   deprecated.
   * @param name
   *   the method's name.
   * @param desc
   *   the method's descriptor (see {@link Type}).
   * @param signature
   *   the method's signature. May be <tt>null</tt>.
   * @param exceptions
   *   the internal names of the method's exception classes (see
   *   {@link Type#getInternalName() getInternalName}). May be
   *   <tt>null</tt>.
   * @throws IllegalStateException
   *   If a subclass calls this constructor.
   */

Found in path(s):
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/JSRInlinerAdapter.java
No license file was found, but licenses were detected in source scan.

/***
* ASM: a very small and fast Java bytecode manipulation framework
* Copyright (c) 2000-2011 INRIA, France Telecom
* All rights reserved.

```
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*    notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following disclaimer in the
*    documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*    contributors may be used to endorse or promote products derived from
*    this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
 "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/
/**
   * Constructs a new {@link Textifier}. <i>Subclasses must not use this
   * constructor</i>. Instead, they must use the {@link #Textifier(int)}
   * version.
   *
   * @throws IllegalStateException
   *             If a subclass calls this constructor.
    */

Found in path(s):
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/Textifier.java
No license file was found, but licenses were detected in source scan.

#All rights reserved.
#Redistribution and use in source and binary forms, with or without
#modification, are permitted provided that the following conditions
#are met:
#1. Redistributions of source code must retain the above copyright
#   notice, this list of conditions and the following disclaimer.
#2. Redistributions in binary form must reproduce the above copyright
#   notice, this list of conditions and the following disclaimer in the
#   documentation and/or other materials provided with the distribution.
```

#3. Neither the name of the copyright holders nor the names of its
this software without specific prior written permission.

Found in path(s):
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/shrink-resize.properties
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/shrink.properties
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/shrink-signatures.properties
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/shrink-writer.properties
*
 /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/shrink-frames.properties
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/shrink-annotations.properties
No license file was found, but licenses were detected in source scan.

/***
* ASM XML Adapter
* Copyright (c) 2004-2011, Eugene Kuleshov
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*   contributors may be used to endorse or promote products derived from
*   this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES,
 INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /asm-5-0-4-sources-jar/org/objectweb/asm/xml/Processor.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/xml/SAXFieldAdapter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/xml/ASMContentHandler.java

* /asm-5-0-4-sources-jar/org/objectweb/asm/xml/SAXClassAdapter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/xml/SAXCodeAdapter.java
*
/asm-5-0-4-sources-jar/org/objectweb/asm/xml/SAXAdapter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/xml/SAXAnnotationAdapter.java
No license file was found, but licenses were detected in source scan.

2011, Eugene Kuleshov
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. Neither the name of the copyright holders nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
THE POSSIBILITY OF SUCH DAMAGE.

Found in path(s):
* /asm-5-0-4-sources-jar/org/objectweb/asm/xml/asm-xml.dtd
No license file was found, but licenses were detected in source scan.

/***
* ASM: a very small and fast Java bytecode manipulation framework
* Copyright (c) 2000-2011 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright

```
*    notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following disclaimer in the
*    documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*    contributors may be used to endorse or promote products derived from
*    this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
 "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/IntInsnNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/TraceAnnotationVisitor.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/FrameNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/ClassConstantsCollector.java
*
 /asm-5-0-4-sources-jar/org/objectweb/asm/commons/TableSwitchGenerator.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/FieldInsnNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/FieldConstantsCollector.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/FieldWriter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/SimpleRemapper.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/CodeSizeEvaluator.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/Attribute.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/TraceMethodVisitor.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/AnnotationNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/ClassOptimizer.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/analysis/SimpleVerifier.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/CheckSignatureAdapter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/CheckClassAdapter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/CheckFieldAdapter.java
*
 /asm-5-0-4-sources-jar/org/objectweb/asm/FieldVisitor.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/VarInsnNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/LabelNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/TryCatchBlockNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/AdviceAdapter.java
```

* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/analysis/Value.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/analysis/BasicValue.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/ASMifier.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/analysis/BasicVerifier.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/analysis/SmallSet.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/analysis/AnalyzerException.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/signature/SignatureWriter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/TryCatchBlockSorter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/TraceFieldVisitor.java
*
/asm-5-0-4-sources-jar/org/objectweb/asm/tree/InvokeDynamicInsnNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/CheckAnnotationAdapter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/RemappingClassAdapter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/Constant.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/AnnotationVisitor.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/JumpInsnNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/RemappingFieldAdapter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/MethodVisitor.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/Method.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/Frame.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/StaticInitMerger.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/TypeInsnNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/AnnotationConstantsCollector.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/MethodNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/ParameterNode.java
*
/asm-5-0-4-sources-jar/org/objectweb/asm/tree/MultiANewArrayInsnNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/Type.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/TraceSignatureVisitor.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/TypeAnnotationNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/analysis/Subroutine.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/NameMapping.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/Context.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/CheckMethodAdapter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/ClassWriter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/analysis/SourceValue.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/Item.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/ConstantPool.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/Handler.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/MethodOptimizer.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/JarOptimizer.java
*
/asm-5-0-4-sources-jar/org/objectweb/asm/signature/SignatureVisitor.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/Label.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/ByteVector.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/signature/SignatureReader.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/InnerClassNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/Handle.java

* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/RemappingMethodAdapter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/IincInsnNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/analysis/Analyzer.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/TraceClassVisitor.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/SerialVersionUIDAdder.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/MethodInsnNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/RemappingAnnotationAdapter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/FieldNode.java
*
 /asm-5-0-4-sources-jar/org/objectweb/asm/AnnotationWriter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/TableSwitchInsnNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/analysis/Interpreter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/LocalVariableNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/InsnList.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/analysis/Frame.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/Remapper.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/Printer.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/AbstractInsnNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/Shrinker.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/InsnNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/InstructionAdapter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/LookupSwitchInsnNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/analysis/SourceInterpreter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/ClassVisitor.java
*
 /asm-5-0-4-sources-jar/org/objectweb/asm/tree/LineNumberNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/MethodWriter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/LdcInsnNode.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/optimizer/MethodConstantsCollector.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/analysis/BasicInterpreter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/LocalVariablesSorter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/RemappingSignatureAdapter.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/ClassReader.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/Edge.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/Opcodes.java
No license file was found, but licenses were detected in source scan.

/***
* ASM: a very small and fast Java bytecode manipulation framework
* Copyright (c) 2000-2011 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright

```
*    notice, this list of conditions and the following disclaimer in the
*    documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*    contributors may be used to endorse or promote products derived from
*    this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
 "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/
/**
   * Constructs a new {@link LocalVariableAnnotationNode}. <i>Subclasses must
   * not use this constructor</i>. Instead, they must use the
   * {@link #LocalVariableAnnotationNode(int, TypePath, LabelNode[], LabelNode[], int[], String)}
   * version.
   *

   * @param typeRef
   *          a reference to the annotated type. See {@link TypeReference}.
   * @param typePath
   *          the path to the annotated type argument, wildcard bound, array
   *          element type, or static inner type within 'typeRef'. May be
   *          <tt>null</tt> if the annotation targets 'typeRef' as a whole.
   * @param start
   *          the fist instructions corresponding to the continuous ranges
   *          that make the scope of this local variable (inclusive).
   * @param end
   *          the last instructions corresponding to the continuous ranges
   *          that make the scope of this local variable (exclusive). This
   *          array must have the same size as the 'start' array.
   * @param index
   *          the local variable's index in each range. This array must have
   *          the same size as the 'start' array.
   * @param desc
   *          the class descriptor of
 the annotation class.
   */
```

Found in path(s):

* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/LocalVariableAnnotationNode.java
No license file was found, but licenses were detected in source scan.

/**
* ASM: a very small and fast Java bytecode manipulation framework
* Copyright (c) 2000-2011 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*   contributors may be used to endorse or promote products derived from
*   this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
 "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/Textifiable.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/ASMifiable.java
No license file was found, but licenses were detected in source scan.

/***
* ASM: a very small and fast Java bytecode manipulation framework
* Copyright (c) 2000-2013 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright

* notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
* contributors may be used to endorse or promote products derived from
* this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /asm-5-0-4-sources-jar/org/objectweb/asm/TypePath.java
* /asm-5-0-4-sources-jar/org/objectweb/asm/TypeReference.java
No license file was found, but licenses were detected in source scan.

/***
* ASM: a very small and fast Java bytecode manipulation framework
* Copyright (c) 2000-2011 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
* notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
* contributors may be used to endorse or promote products derived from
* this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE

```
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/
/**
   * Creates a new {@link GeneratorAdapter}. <i>Subclasses must not use this
   * constructor</i>. Instead, they must use the
   * {@link #GeneratorAdapter(int, MethodVisitor, int, String, String)}
   * version.
   *
   * @param mv
   *            the
 method visitor to which this adapter delegates calls.
   * @param access
   *            the method's access flags (see {@link Opcodes}).
   * @param name
   *            the method's name.
   * @param desc
   *            the method's descriptor (see {@link Type Type}).
   * @throws IllegalStateException
   *             If a subclass calls this constructor.
   */

Found in path(s):
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/GeneratorAdapter.java
No license file was found, but licenses were detected in source scan.

/***
* ASM: a very small and fast Java bytecode manipulation framework
* Copyright (c) 2000-2011 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*    notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following disclaimer in the
*    documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*    contributors may be used to endorse or promote products derived from
*    this software without specific prior written permission.
```

```
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
 "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/
/**
   * Creates a new {@link AnalyzerAdapter}. <i>Subclasses must not use this
   * constructor</i>. Instead, they must use the
   * {@link #AnalyzerAdapter(int, String, int, String, String, MethodVisitor)}
   * version.
   *
   * @param owner
   *
     the owner's class name.
   * @param access
   *          the method's access flags (see {@link Opcodes}).
   * @param name
   *          the method's name.
   * @param desc
   *          the method's descriptor (see {@link Type Type}).
   * @param mv
   *          the method visitor to which this adapter delegates calls. May
   *          be <tt>null</tt>.
   * @throws IllegalStateException
   *           If a subclass calls this constructor.
   */
```

Found in path(s):
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/AnalyzerAdapter.java
No license file was found, but licenses were detected in source scan.

```
2011 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*    notice, this list of conditions and the following disclaimer.
```

* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*   contributors may be used to endorse or promote products derived from
*   this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
 * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.

Found in path(s):
* /asm-5-0-4-sources-jar/org/objectweb/asm/signature/package.html
* /asm-5-0-4-sources-jar/org/objectweb/asm/util/package.html
* /asm-5-0-4-sources-jar/org/objectweb/asm/package.html
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/analysis/package.html
* /asm-5-0-4-sources-jar/org/objectweb/asm/commons/package.html
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/package.html
No license file was found, but licenses were detected in source scan.

/***
* ASM: a very small and fast Java bytecode manipulation framework
* Copyright (c) 2000-2011 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*   contributors may be used to endorse or promote products derived from
*   this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
 "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE

```
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/
/**
   * Constructs a new {@link ClassNode}. <i>Subclasses must not use this
   * constructor</i>. Instead, they must use the {@link #ClassNode(int)}
   * version.
   *
   * @throws IllegalStateException
   *             If a subclass calls this constructor.
    */
```

Found in path(s):
* /asm-5-0-4-sources-jar/org/objectweb/asm/tree/ClassNode.java
No license file was found, but licenses were detected in source scan.

```
2011, Eugene Kuleshov
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*    notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following disclaimer in the
*    documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*    contributors may be used to endorse or promote products derived from
*    this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED
 WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
```

* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.

Found in path(s):
* /asm-5-0-4-sources-jar/org/objectweb/asm/xml/package.html

1.86 annotations 3.0.1

1.87 jcl-over-slf4j 1.7.21

1.88 asm 4.0

1.89 antlr 2.7.6

1.90 protobuf-java 3.5.1

1.90.1 Available under license :

No license file was found, but licenses were detected in source scan.

// Copyright 2008 Google Inc. All rights reserved.
// Redistribution and use in source and binary forms, with or without
// modification, are permitted provided that the following conditions are
//   * Redistributions of source code must retain the above copyright
// notice, this list of conditions and the following disclaimer.
//   * Redistributions in binary form must reproduce the above
// copyright notice, this list of conditions and the following disclaimer
// in the documentation and/or other materials provided with the
//   * Neither the name of Google Inc. nor the names of its
// this software without specific prior written permission.

Found in path(s):
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/LongArrayList.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/AbstractParser.java
* /protobuf-java-3-5-1-sources-jar/google/protobuf/api.proto
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/Internal.java
*

/protobuf-java-3-5-1-sources-jar/com/google/protobuf/Service.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/Descriptors.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/ServiceException.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/TextFormat.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/Utf8.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/ExtensionLite.java
* /protobuf-java-3-5-1-sources-jar/google/protobuf/type.proto
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/ProtobufArrayList.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/ExtensionRegistryLite.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/SingleFieldBuilder.java
* /protobuf-java-3-5-1-sources-jar/google/protobuf/source_context.proto
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/TextFormatEscaper.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/TextFormatParseLocation.java
* /protobuf-java-3-5-1-sources-jar/google/protobuf/timestamp.proto
*
/protobuf-java-3-5-1-sources-jar/com/google/protobuf/LazyFieldLite.java
* /protobuf-java-3-5-1-sources-jar/google/protobuf/struct.proto
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/CodedInputStream.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/FloatArrayList.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/MessageLiteToString.java
* /protobuf-java-3-5-1-sources-jar/google/protobuf/empty.proto
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/ExtensionRegistry.java
* /protobuf-java-3-5-1-sources-jar/google/protobuf/duration.proto
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/Parser.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/MapEntry.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/LazyField.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/LazyStringList.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/UninitializedMessageException.java
*
/protobuf-java-3-5-1-sources-jar/com/google/protobuf/RopeByteString.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/UnmodifiableLazyStringList.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/RpcController.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/InvalidProtocolBufferException.java
* /protobuf-java-3-5-1-sources-jar/google/protobuf/any.proto
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/Extension.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/NioByteString.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/MessageOrBuilder.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/GeneratedMessageV3.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/ByteBufferWriter.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/ByteString.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/AbstractMessageLite.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/SmallSortedMap.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/MapField.java
*
/protobuf-java-3-5-1-sources-jar/com/google/protobuf/MapEntryLite.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/UnsafeByteOperations.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/AbstractMessage.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/ByteOutput.java

* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/ExtensionRegistryFactory.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/UnknownFieldSetLite.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/RpcUtil.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/MapFieldLite.java
* /protobuf-java-3-5-1-sources-jar/google/protobuf/wrappers.proto
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/DynamicMessage.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/BlockingRpcChannel.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/PrimitiveNonBoxingCollection.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/ExperimentalApi.java
*
 /protobuf-java-3-5-1-sources-jar/com/google/protobuf/ProtocolMessageEnum.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/GeneratedMessageLite.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/BlockingService.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/RepeatedFieldBuilder.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/TextFormatParseInfoTree.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/WireFormat.java
* /protobuf-java-3-5-1-sources-jar/google/protobuf/compiler/plugin.proto
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/ProtocolStringList.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/MessageLiteOrBuilder.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/BooleanArrayList.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/CodedOutputStream.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/DiscardUnknownFieldsParser.java
*
 /protobuf-java-3-5-1-sources-jar/com/google/protobuf/RpcChannel.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/LazyStringArrayList.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/DoubleArrayList.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/RepeatedFieldBuilderV3.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/AbstractProtobufList.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/SingleFieldBuilderV3.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/MessageLite.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/RpcCallback.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/FieldSet.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/MutabilityOracle.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/Message.java
* /protobuf-java-3-5-1-sources-jar/google/protobuf/descriptor.proto
* /protobuf-java-3-5-1-sources-jar/google/protobuf/field_mask.proto
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/UnsafeUtil.java
*
 /protobuf-java-3-5-1-sources-jar/com/google/protobuf/IterableByteBufferInputStream.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/UnknownFieldSet.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/IntArrayList.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/MessageReflection.java
* /protobuf-java-3-5-1-sources-jar/com/google/protobuf/GeneratedMessage.java

1.91 geronimo-javamail 1.7.1

1.91.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain

separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without

modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include

the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

JavaMail 1.4
Copyright 2003-2010 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.92 checker-compat-qual 2.0.0

1.92.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE

Version 3, 29 June 2007

Copyright © 2007 Free Software Foundation, Inc. <https://fsf.org/>

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates the terms and conditions of version 3 of the GNU General Public License, supplemented by the additional permissions listed below.
0. Additional Definitions.

As used herein, “this License” refers to version 3 of the GNU Lesser General Public License, and the “GNU GPL” refers to version 3 of the GNU General Public License.

“The Library” refers to a covered work governed by this License, other than an Application or a Combined Work as

defined below.

An “Application” is any work that makes use of an interface provided by the Library, but which is not otherwise based on the Library. Defining a subclass of a class defined by the Library is deemed a mode of using an interface provided
by the Library.

A “Combined Work” is a work produced by combining or linking an Application with the Library. The particular version of the Library with which the Combined Work was made is also called the “Linked Version”.

The “Minimal Corresponding Source” for a Combined Work means the Corresponding Source for the Combined Work, excluding any source code for portions of the Combined Work that, considered in isolation, are based on the Application, and not on the Linked Version.

The “Corresponding Application Code” for a Combined Work means the object code and/or source code for the Application, including any data and utility programs needed for reproducing the Combined Work from the Application, but excluding the System Libraries of the Combined Work.
1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.
2. Conveying Modified Versions.

If you modify a copy of the Library,
and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or
b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates
(ten or fewer lines in length), you do both of the following:

a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.
b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging

such modifications, if you also do each of the following:

a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.

b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices,
as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL,
and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms
of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License “or any later version” applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License,

you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.

1.93 protobuf-java-util 3.5.1

1.94 minimal-json 0.9.4

1.95 grpc-core 1.9.0

1.96 instrumentation-api 0.4.3

1.97 slf4j 1.7.21

1.97.1 Available under license :

Copyright (c) 2004-2007 QOS.ch
All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE

LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial

revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.

Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright 1999-2005 The Apache Software Foundation

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Copyright (c) 2004-2013 QOS.ch
All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Copyright (c) 2004-2014 QOS.ch
All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,

including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of

this License,
each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside

or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.98 hazelcast-client-protocol 1.4.1

1.98.1 Available under license :

```
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

import java.security.Permission;
import java.security.PermissionCollection;
import java.util.Enumeration;

public final class AllPermissions extends ClusterPermission {

  public AllPermissions() {
     super("<all permissions>");
  }

  @Override
  public boolean implies(Permission permission) {
```

```
    return true;
 }

@Override
public String getActions() {
    return "<all actions>";
}

 @Override
public PermissionCollection newPermissionCollection() {
    return new AllPermissionsCollection();
}

@Override
public String toString() {
    return "<allow all permissions>";
}

@Override
public boolean equals(Object obj) {
    return obj instanceof AllPermissions;
}

@Override
public int hashCode() {
    return 111;
}

public static final class AllPermissionsCollection extends PermissionCollection {
    private static final AllPermissions ALL_PERMISSIONS = new AllPermissions();
    private boolean all;

    public AllPermissionsCollection() {
    }

    public AllPermissionsCollection(boolean all) {
        this.all = all;
    }

    @Override
    public void add(Permission permission) {
        if (permission instanceof AllPermissions) {
            all = true;

  }
    }

    @Override
```

```
    public boolean implies(Permission permission) {
        return all;
    }

    @Override
    public Enumeration<Permission> elements() {
        return new Enumeration<Permission>() {
            boolean more = all;

            @Override
            public boolean hasMoreElements() {
                return more;
            }

            @Override
            public Permission nextElement() {
                more = false;
                return ALL_PERMISSIONS;
            }
        };
    }

    @Override
    public int hashCode() {
        return all ? 13 : -13;
    }

     @Override
    public boolean equals(Object obj) {
        if (this == obj) {
            return true;
        }
        if (obj == null) {
            return false;
        }
        if (getClass() != obj.getClass()) {
            return false;

       }
        AllPermissionsCollection other = (AllPermissionsCollection) obj;
        return all == other.all;
    }

    @Override
    public String toString() {
        return "<allow all permissions>";
    }
}
```

```
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class QueuePermission extends InstancePermission {

  private static final int ADD = 4;
  private static final int READ = 8;
  private static final int REMOVE = 16;
  private static final int LISTEN = 32;
  private static final int ALL = ADD | REMOVE | READ | CREATE | DESTROY | LISTEN;

  public QueuePermission(String
 name, String... actions) {
    super(name, actions);
  }

  @Override
  protected int initMask(String[] actions) {
    int mask = NONE;
    for (String action : actions) {
      if (ActionConstants.ACTION_ALL.equals(action)) {
        return ALL;
      }

      if (ActionConstants.ACTION_CREATE.equals(action)) {
        mask |= CREATE;
      } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
        mask |= DESTROY;
      } else if (ActionConstants.ACTION_ADD.equals(action)) {
        mask |= ADD;
      } else if (ActionConstants.ACTION_READ.equals(action)) {
        mask |= READ;
```

```
        } else if (ActionConstants.ACTION_REMOVE.equals(action)) {
            mask |= REMOVE;
        } else if (ActionConstants.ACTION_LISTEN.equals(action)) {
            mask |= LISTEN;
        }
      }
      return mask;
    }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class ReplicatedMapPermission extends InstancePermission {

    private static final int PUT = 4;
    private static final int REMOVE = 8;
    private static final int READ = 16;
    private static final int LISTEN = 32;
    private static final int LOCK = 64;
    private static final int INDEX = 128;
    private static final
 int INTERCEPT = 256;
    private static final int ALL = CREATE | DESTROY | PUT | REMOVE | READ | LISTEN | LOCK | INDEX |
INTERCEPT;

    public ReplicatedMapPermission(String name, String... actions) {
        super(name, actions);
    }

    @Override
    protected int initMask(String[] actions) {
        int mask = NONE;
        for (String action : actions) {
```

```
        if (ActionConstants.ACTION_ALL.equals(action)) {
            return ALL;
        }

        if (ActionConstants.ACTION_CREATE.equals(action)) {
            mask |= CREATE;
        } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
            mask |= DESTROY;
        } else if (ActionConstants.ACTION_PUT.equals(action)) {
            mask |= PUT;
        } else if (ActionConstants.ACTION_REMOVE.equals(action)) {
            mask |= REMOVE;
        } else if (ActionConstants.ACTION_READ.equals(action)) {
            mask |= READ;
        } else if (ActionConstants.ACTION_LISTEN.equals(action))
{
            mask |= LISTEN;
        } else if (ActionConstants.ACTION_LOCK.equals(action)) {
            mask |= LOCK;
        } else if (ActionConstants.ACTION_INDEX.equals(action)) {
            mask |= INDEX;
        } else if (ActionConstants.ACTION_INTERCEPT.equals(action)) {
            mask |= INTERCEPT;
        }
      }
      return mask;
    }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class AtomicReferencePermission extends InstancePermission {
```

```
  private static final int READ = 4;
  private static final int MODIFY = 8;

  private static final int ALL = READ | MODIFY | CREATE | DESTROY;

  public AtomicReferencePermission(String name, String... actions) {
     super(name, actions);
  }


  @Override
  protected int initMask(String[] actions) {
     int mask = NONE;
     for (String action : actions) {
        if (ActionConstants.ACTION_ALL.equals(action)) {
           return ALL;
        }

        if (ActionConstants.ACTION_CREATE.equals(action)) {
           mask |= CREATE;
        } else if (ActionConstants.ACTION_READ.equals(action)) {
           mask |= READ;
        } else if (ActionConstants.ACTION_MODIFY.equals(action)) {
           mask |= MODIFY;
        } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
           mask |= DESTROY;
        }
     }
     return mask;
  }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;
```

```
import com.hazelcast.config.matcher.WildcardConfigPatternMatcher;

import java.security.Permission;

/**
* TODO: Object Permission
*/
public abstract class InstancePermission extends ClusterPermission {

  protected static final int NONE = 0;
  protected static final int CREATE = 1;
  protected static final int DESTROY =
 2;

  private static final WildcardConfigPatternMatcher CONFIG_PATTERN_MATCHER = new
WildcardConfigPatternMatcher();

  protected final int mask;
  protected final String actions;

  public InstancePermission(String name, String... actions) {
     super(name);
     if (name == null || "".equals(name)) {
        throw new IllegalArgumentException("Permission name is mandatory!");
     }
     mask = initMask(actions);

     final StringBuilder s = new StringBuilder();
     for (String action : actions) {
        s.append(action).append(" ");
     }
     this.actions = s.toString();
  }

  /**
   * init mask
   */
  protected abstract int initMask(String[] actions);

  @Override
  public boolean implies(Permission permission) {
     if (this.getClass() != permission.getClass()) {
        return false;
     }

     InstancePermission that = (InstancePermission) permission;
```

```
        boolean maskTest = ((this.mask & that.mask)
    == that.mask);
        if (!maskTest) {
            return false;
        }

        return CONFIG_PATTERN_MATCHER.matches(getName(), that.getName());
    }

    @Override
    public String getActions() {
        return actions;
    }

    @Override
    public int hashCode() {
        int result = super.hashCode();
        result = 31 * result + mask;
        result = 31 * result + actions.hashCode();
        return result;
    }

    @Override
    public boolean equals(Object obj) {
        if (this == obj) {
            return true;
        }
        if (obj == null) {
            return false;
        }
        if (getClass() != obj.getClass()) {
            return false;
        }
        InstancePermission other = (InstancePermission) obj;
        if (getName() == null && other.getName() != null) {
            return false;
        }
        if (!getName().equals(other.getName())) {
            return false;
        }
        if (mask != other.mask) {
            return false;
         }
        return true;
    }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
```

```
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class MapPermission extends InstancePermission {

  private static final int PUT = 4;
  private static final int REMOVE = 8;
  private static final int READ = 16;
  private static final int LISTEN = 32;
  private static final int LOCK = 64;
  private static final int INDEX = 128;
  private static final int INTERCEPT
 = 256;
  private static final int ALL = CREATE | DESTROY | PUT | REMOVE | READ | LISTEN | LOCK | INDEX |
INTERCEPT;

  public MapPermission(String name, String... actions) {
     super(name, actions);
  }

  @Override
  protected int initMask(String[] actions) {
     int mask = NONE;
     for (String action : actions) {
        if (ActionConstants.ACTION_ALL.equals(action)) {
           return ALL;
        }

        if (ActionConstants.ACTION_CREATE.equals(action)) {
           mask |= CREATE;
        } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
           mask |= DESTROY;
        } else if (ActionConstants.ACTION_PUT.equals(action)) {
           mask |= PUT;
        } else if (ActionConstants.ACTION_REMOVE.equals(action)) {
```

```
            mask |= REMOVE;
        } else if (ActionConstants.ACTION_READ.equals(action)) {
            mask |= READ;
        } else if (ActionConstants.ACTION_LISTEN.equals(action))
 {
            mask |= LISTEN;
        } else if (ActionConstants.ACTION_LOCK.equals(action)) {
            mask |= LOCK;
        } else if (ActionConstants.ACTION_INDEX.equals(action)) {
            mask |= INDEX;
        } else if (ActionConstants.ACTION_INTERCEPT.equals(action)) {
            mask |= INTERCEPT;
        }
      }
      return mask;
   }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class CachePermission extends InstancePermission {

   private static final int PUT = 4;
   private static final int REMOVE = 8;
   private static final int READ = 16;
   private static final int LISTEN = 32;
   private static final int ALL = CREATE | DESTROY | PUT | REMOVE | READ | LISTEN;

   public CachePermission(String
 name, String... actions) {
      super(name, actions);
   }
```

```
  @Override
  protected int initMask(String[] actions) {
     int mask = NONE;
     for (String action : actions) {
        if (ActionConstants.ACTION_ALL.equals(action)) {
           return ALL;
        }

        if (ActionConstants.ACTION_CREATE.equals(action)) {
           mask |= CREATE;
        } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
           mask |= DESTROY;
        } else if (ActionConstants.ACTION_PUT.equals(action)) {
           mask |= PUT;
        } else if (ActionConstants.ACTION_REMOVE.equals(action)) {
           mask |= REMOVE;
        } else if (ActionConstants.ACTION_READ.equals(action)) {
           mask |= READ;
        } else if (ActionConstants.ACTION_LISTEN.equals(action)) {
           mask |= LISTEN;
        }
     }
     return mask;
  }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class CardinalityEstimatorPermission extends InstancePermission {

  private static final int READ = 4;
  private static final int MODIFY = 8;
```

```
  private static final int ALL = READ | MODIFY | CREATE | DESTROY;

  public CardinalityEstimatorPermission(String name, String... actions) {
     super(name, actions);
   }

  @Override
  protected int initMask(String[] actions) {
     int mask = NONE;
     for (String action : actions) {
        if (ActionConstants.ACTION_ALL.equals(action)) {
           return ALL;
        }

        if (ActionConstants.ACTION_CREATE.equals(action)) {
           mask |= CREATE;
        } else if (ActionConstants.ACTION_READ.equals(action)) {
           mask |= READ;
        } else if (ActionConstants.ACTION_MODIFY.equals(action)) {
           mask |= MODIFY;
        } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
           mask |= DESTROY;
        }
     }
     return mask;
  }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class ListPermission extends InstancePermission {

  private static final int ADD = 4;
```

```
  private static final int READ = 8;
  private static final int REMOVE = 16;
  private static final int LISTEN = 32;
  private static final int ALL = ADD | REMOVE | READ | CREATE | DESTROY | LISTEN;

  public ListPermission(String
 name, String... actions) {
    super(name, actions);
  }

  @Override
  protected int initMask(String[] actions) {
    int mask = NONE;
    for (String action : actions) {
      if (ActionConstants.ACTION_ALL.equals(action)) {
        return ALL;
      }

      if (ActionConstants.ACTION_CREATE.equals(action)) {
        mask |= CREATE;
      } else if (ActionConstants.ACTION_ADD.equals(action)) {
        mask |= ADD;
      } else if (ActionConstants.ACTION_REMOVE.equals(action)) {
        mask |= REMOVE;
      } else if (ActionConstants.ACTION_READ.equals(action)) {
        mask |= READ;
      } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
        mask |= DESTROY;
      } else if (ActionConstants.ACTION_LISTEN.equals(action)) {
        mask |= LISTEN;
      }
    }
    return mask;
  }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
```

```
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class TopicPermission extends InstancePermission {

  private static final int PUBLISH = 4;
  private static final int LISTEN = 8;
  private static final int ALL = CREATE | DESTROY | LISTEN | PUBLISH;

  public TopicPermission(String name, String... actions) {
     super(name, actions);
  }

  @Override

 protected int initMask(String[] actions) {
     int mask = NONE;
     for (String action : actions) {
        if (ActionConstants.ACTION_ALL.equals(action)) {
           return ALL;
        }

        if (ActionConstants.ACTION_CREATE.equals(action)) {
           mask |= CREATE;
        } else if (ActionConstants.ACTION_PUBLISH.equals(action)) {
           mask |= PUBLISH;
        } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
           mask |= DESTROY;
        } else if (ActionConstants.ACTION_LISTEN.equals(action)) {
           mask |= LISTEN;
        }
     }
     return mask;
  }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
```

```
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class ExecutorServicePermission extends InstancePermission {

  private static final int ALL = CREATE | DESTROY;

  public ExecutorServicePermission(String name, String... actions) {
     super(name, actions);
  }

  @Override
  protected int initMask(String[] actions) {
     int mask = NONE;
     for (String
 action : actions) {
        if (ActionConstants.ACTION_ALL.equals(action)) {
           return ALL;
        }

        if (ActionConstants.ACTION_CREATE.equals(action)) {
           mask |= CREATE;
        } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
           mask |= DESTROY;
        }
     }
     return mask;
  }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

```
package com.hazelcast.security.permission;

import com.hazelcast.cache.impl.CacheService;
import com.hazelcast.cardinality.impl.CardinalityEstimatorService;
import com.hazelcast.collection.impl.list.ListService;
import com.hazelcast.collection.impl.queue.QueueService;
import com.hazelcast.collection.impl.set.SetService;
import com.hazelcast.concurrent.atomiclong.AtomicLongService;
import
 com.hazelcast.concurrent.atomicreference.AtomicReferenceService;
import com.hazelcast.concurrent.countdownlatch.CountDownLatchService;
import com.hazelcast.concurrent.idgen.IdGeneratorService;
import com.hazelcast.concurrent.lock.LockService;
import com.hazelcast.concurrent.semaphore.SemaphoreService;
import com.hazelcast.durableexecutor.impl.DistributedDurableExecutorService;
import com.hazelcast.executor.impl.DistributedExecutorService;
import com.hazelcast.map.impl.MapService;
import com.hazelcast.mapreduce.impl.MapReduceService;
import com.hazelcast.multimap.impl.MultiMapService;
import com.hazelcast.replicatedmap.impl.ReplicatedMapService;
import com.hazelcast.ringbuffer.impl.RingbufferService;
import com.hazelcast.topic.impl.TopicService;

import java.security.Permission;
import java.util.HashMap;
import java.util.Map;

public final class ActionConstants {

   public static final String ACTION_ALL = "all";
   public static final String ACTION_CREATE = "create";
    public static final String ACTION_DESTROY = "destroy";
   public static final String ACTION_MODIFY = "modify";
   public static final String ACTION_READ = "read";
   public static final String ACTION_REMOVE = "remove";
   public static final String ACTION_LOCK = "lock";
   public static final String ACTION_LISTEN = "listen";
   public static final String ACTION_RELEASE = "release";
   public static final String ACTION_ACQUIRE = "acquire";
   public static final String ACTION_PUT = "put";
   public static final String ACTION_ADD = "add";
   public static final String ACTION_INDEX = "index";
   public static final String ACTION_INTERCEPT = "intercept";
   public static final String ACTION_PUBLISH = "publish";
   public static final String ACTION_AGGREGATE = "aggregate";
   public static final String ACTION_PROJECTION = "projection";
```

```
  public static final String LISTENER_INSTANCE = "instance";
  public static final String LISTENER_MEMBER = "member";
  public static
 final String LISTENER_MIGRATION = "migration";

  private static final Map<String, PermissionFactory> PERMISSION_FACTORY_MAP = new HashMap<String,
PermissionFactory>();

  static {
     PERMISSION_FACTORY_MAP.put(QueueService.SERVICE_NAME, new PermissionFactory() {
        @Override
        public Permission create(String name, String... actions) {
           return new QueuePermission(name, actions);
        }
     });
     PERMISSION_FACTORY_MAP.put(MapService.SERVICE_NAME, new PermissionFactory() {
        @Override
        public Permission create(String name, String... actions) {
           return new MapPermission(name, actions);
        }
     });
     PERMISSION_FACTORY_MAP.put(MultiMapService.SERVICE_NAME, new PermissionFactory() {
        @Override
        public Permission create(String name, String... actions) {
           return new MultiMapPermission(name, actions);
        }
     });
     PERMISSION_FACTORY_MAP.put(ListService.SERVICE_NAME,
 new PermissionFactory() {
        @Override
        public Permission create(String name, String... actions) {
           return new ListPermission(name, actions);
        }
     });
     PERMISSION_FACTORY_MAP.put(SetService.SERVICE_NAME, new PermissionFactory() {
        @Override
        public Permission create(String name, String... actions) {
           return new SetPermission(name, actions);
        }
     });
     PERMISSION_FACTORY_MAP.put(AtomicLongService.SERVICE_NAME, new PermissionFactory() {
        @Override
        public Permission create(String name, String... actions) {
           return new AtomicLongPermission(name, actions);
        }
     });
     PERMISSION_FACTORY_MAP.put(CountDownLatchService.SERVICE_NAME, new PermissionFactory() {
        @Override
```

```
        public Permission create(String name, String... actions) {
            return
 new CountDownLatchPermission(name, actions);
        }
      });
      PERMISSION_FACTORY_MAP.put(SemaphoreService.SERVICE_NAME, new PermissionFactory() {
        @Override
        public Permission create(String name, String... actions) {
          return new SemaphorePermission(name, actions);
        }
      });
      PERMISSION_FACTORY_MAP.put(TopicService.SERVICE_NAME, new PermissionFactory() {
        @Override
        public Permission create(String name, String... actions) {
          return new TopicPermission(name, actions);
        }
      });
      PERMISSION_FACTORY_MAP.put(LockService.SERVICE_NAME, new PermissionFactory() {
        @Override
        public Permission create(String name, String... actions) {
          return new LockPermission(name, actions);
        }
      });
      PERMISSION_FACTORY_MAP.put(DistributedExecutorService.SERVICE_NAME, new
PermissionFactory() {
        @Override
         public Permission create(String name, String... actions) {
          return new ExecutorServicePermission(name, actions);
        }
      });
      PERMISSION_FACTORY_MAP.put(IdGeneratorService.SERVICE_NAME, new PermissionFactory() {
        @Override
        public Permission create(String name, String... actions) {
          return new AtomicLongPermission(IdGeneratorService.ATOMIC_LONG_NAME + name, actions);
        }
      });
      PERMISSION_FACTORY_MAP.put(MapReduceService.SERVICE_NAME, new PermissionFactory() {
        @Override
        public Permission create(String name, String... actions) {
          return new MapReducePermission(name, actions);
        }
      });
      PERMISSION_FACTORY_MAP.put(ReplicatedMapService.SERVICE_NAME, new PermissionFactory() {
        @Override
        public Permission create(String name, String... actions) {
          return new ReplicatedMapPermission(name,
 actions);
        }
```

```
        });
        PERMISSION_FACTORY_MAP.put(AtomicReferenceService.SERVICE_NAME, new PermissionFactory() {
            @Override
            public Permission create(String name, String... actions) {
                return new AtomicReferencePermission(name, actions);
            }
        });
        PERMISSION_FACTORY_MAP.put(CacheService.SERVICE_NAME, new PermissionFactory() {
            @Override
            public Permission create(String name, String... actions) {
                return new CachePermission(name, actions);
            }
        });
        PERMISSION_FACTORY_MAP.put(RingbufferService.SERVICE_NAME, new PermissionFactory() {
            @Override
            public Permission create(String name, String... actions) {
                return new RingBufferPermission(name, actions);
            }
        });
        PERMISSION_FACTORY_MAP.put(DistributedDurableExecutorService.SERVICE_NAME, new
PermissionFactory() {
            @Override

            public Permission create(String name, String... actions) {
                return new DurableExecutorServicePermission(name, actions);
            }
        });
        PERMISSION_FACTORY_MAP.put(CardinalityEstimatorService.SERVICE_NAME, new
PermissionFactory() {
            @Override
            public Permission create(String name, String... actions) {
                return new CardinalityEstimatorPermission(name, actions);
            }
        });
    }

    private ActionConstants() {
    }

    private interface PermissionFactory {
        Permission create(String name, String... actions);
    }

    /**
     * Creates a permission
     *
     * @param name
     * @param serviceName
```

```
     * @param actions
     * @return the created Permission
     * @throws java.lang.IllegalArgumentException if there is no service found with the given serviceName.
     */
    public static Permission getPermission(String name, String serviceName, String... actions) {
        PermissionFactory
   permissionFactory = PERMISSION_FACTORY_MAP.get(serviceName);
        if (permissionFactory == null) {
            throw new IllegalArgumentException("No permissions found for service: " + serviceName);
        }

        return permissionFactory.create(name, actions);
    }

}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class RingBufferPermission extends InstancePermission {

    private static final int PUT = 4;
    private static final int READ = 8;
    private static final int ALL = PUT | READ;

    public RingBufferPermission(String name, String... actions) {
        super(name, actions);
    }

    @Override
    protected int initMask(String[]
   actions) {
        int mask = NONE;
        for (String action : actions) {
```

```
            if (ActionConstants.ACTION_ALL.equals(action)) {
                return ALL;
            }

            if (ActionConstants.ACTION_CREATE.equals(action)) {
                mask |= CREATE;
            } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
                mask |= DESTROY;
            } else if (ActionConstants.ACTION_PUT.equals(action)) {
                mask |= PUT;
            } else if (ActionConstants.ACTION_READ.equals(action)) {
                mask |= READ;
            }
        }
        return mask;
    }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

import java.security.Permission;
import java.security.PermissionCollection;
import java.util.Collections;
import java.util.Enumeration;
import java.util.HashSet;
import java.util.Iterator;
import java.util.Set;

public class ClusterPermissionCollection extends PermissionCollection {

    final Set<Permission> perms = new HashSet<Permission>();
     final Class<? extends Permission> permClass;
```

```
  public ClusterPermissionCollection() {
     permClass = null;
  }

  public ClusterPermissionCollection(Class<? extends Permission> permClass) {
     this.permClass = permClass;
  }

  @Override
  public void add(Permission permission) {
     if (isReadOnly()) {
        throw new SecurityException("ClusterPermissionCollection is read-only!");
     }
     boolean shouldAdd = (permClass != null && permClass.equals(permission.getClass()))
           || (permission instanceof ClusterPermission);

     if (shouldAdd && !implies(permission)) {
        perms.add(permission);
     }
  }

  public void add(PermissionCollection permissions) {
     if (isReadOnly()) {
        throw new SecurityException("ClusterPermissionCollection is read-only!");
     }
     if (permissions instanceof ClusterPermissionCollection) {
        for (Permission p : ((ClusterPermissionCollection)
permissions).perms) {
           add(p);
        }
     }
  }

  @Override
  public boolean implies(Permission permission) {
     for (Permission p : perms) {
        if (p.implies(permission)) {
           return true;
        }
     }
     return false;
  }

  public void compact() {
     if (isReadOnly()) {
        throw new SecurityException("ClusterPermissionCollection is read-only!");
     }
     final Iterator<Permission> iter = perms.iterator();
```

```
      while (iter.hasNext()) {
         final Permission perm = iter.next();
         boolean implies = false;
         for (Permission p : perms) {
            if (p != perm && p.implies(perm)) {
               implies = true;
               break;
            }
         }
         if (implies) {
            iter.remove();
         }
      }
      setReadOnly();
   }

   @Override
   public Enumeration<Permission> elements()
  {
      return Collections.enumeration(perms);
   }

   public Set<Permission> getPermissions() {
      return Collections.unmodifiableSet(perms);
   }

   @Override
   public String toString() {
      return "ClusterPermissionCollection [permClass=" + permClass + "]";
   }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;
```

```
public class SemaphorePermission extends InstancePermission {

  private static final int ACQUIRE = 4;
  private static final int RELEASE = 8;
  private static final int READ = 16;

  private static final int ALL = CREATE | DESTROY | ACQUIRE | RELEASE | READ;

   public SemaphorePermission(String name, String... actions) {
       super(name, actions);
   }

   @Override
   protected int initMask(String[] actions) {
      int mask = NONE;
      for (String action : actions) {
         if (ActionConstants.ACTION_ALL.equals(action)) {
            return ALL;
         }

         if (ActionConstants.ACTION_CREATE.equals(action)) {
            mask |= CREATE;
         } else if (ActionConstants.ACTION_ACQUIRE.equals(action)) {
            mask |= ACQUIRE;
         } else if (ActionConstants.ACTION_RELEASE.equals(action)) {
            mask |= RELEASE;
         } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
            mask |= DESTROY;
         } else if (ActionConstants.ACTION_READ.equals(action)) {
            mask |= READ;
         }
      }
      return mask;
   }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
```

```
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class MultiMapPermission extends MapPermission {

  public MultiMapPermission(String name, String... actions) {
     super(name, actions);
  }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class AtomicLongPermission extends InstancePermission {

  private static final int READ = 4;
  private static final int MODIFY = 8;

  private static final int ALL = READ | MODIFY | CREATE | DESTROY;

  public AtomicLongPermission(String name, String... actions) {
     super(name, actions);
  }

  @Override
   protected int initMask(String[] actions) {
     int mask = NONE;
     for (String action : actions) {
        if (ActionConstants.ACTION_ALL.equals(action)) {
           return ALL;
        }
```

```
            if (ActionConstants.ACTION_CREATE.equals(action)) {
                mask |= CREATE;
            } else if (ActionConstants.ACTION_READ.equals(action)) {
                mask |= READ;
            } else if (ActionConstants.ACTION_MODIFY.equals(action)) {
                mask |= MODIFY;
            } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
                mask |= DESTROY;
            }
        }
        return mask;
    }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

import java.security.Permission;
import java.security.PermissionCollection;
import java.util.Enumeration;

public class DenyAllPermissionCollection extends PermissionCollection {

    public DenyAllPermissionCollection() {
    }

    @Override
    public void add(Permission permission) {
    }

    @Override
    public boolean implies(Permission
```

```
 permission) {
      return false;
   }

   @Override
   public Enumeration<Permission> elements() {
      return new Enumeration<Permission>() {
         @Override
         public boolean hasMoreElements() {
            return false;
         }

         @Override
         public Permission nextElement() {
            return null;
         }
      };
   }

   @Override
   public int hashCode() {
      return 37;
   }

   @Override
   public String toString() {
      return "<deny all permissions>";
   }

   @Override
   public boolean equals(Object obj) {
      return obj instanceof DenyAllPermissionCollection;
   }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
```

```
*/

package com.hazelcast.security.permission;

public class SetPermission extends ListPermission {

  public SetPermission(String name, String... actions) {
     super(name, actions);
  }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

import java.security.Permission;

public class TransactionPermission extends ClusterPermission {

  public TransactionPermission() {
     super("<transaction>");
  }

  @Override
  public boolean implies(Permission permission) {
     return getClass() == permission.getClass();
  }

  @Override
  public String
 getActions() {
     return "transaction";
  }
}
```

```
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

import java.security.Permission;
import java.security.PermissionCollection;

public abstract class ClusterPermission extends Permission {

  private int hashcode;

  public ClusterPermission(String name) {
     super(name);
  }

  @Override
  public PermissionCollection newPermissionCollection() {
     return new
 ClusterPermissionCollection(getClass());
  }

  @Override
  public int hashCode() {
     if (hashcode == 0) {
        final int prime = 31;
        int result = 1;
        if (getName() == null) {
           result = prime * result + 13;
        } else {
           result = prime * result + getName().hashCode();
        }
        hashcode = result;
     }
     return hashcode;
```

```
  }

  @Override
  public boolean equals(Object obj) {
     if (this == obj) {
        return true;
     }
     if (obj == null) {
        return false;
     }
     if (getClass() != obj.getClass()) {
        return false;
     }
     ClusterPermission other = (ClusterPermission) obj;
     if (getName() == null && other.getName() != null) {
        return false;
     }
     if (!getName().equals(other.getName())) {
        return false;
     }
     return true;
  }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class ScheduledExecutorPermission
      extends InstancePermission {

  private static final int READ = 4;
  private static final int MODIFY = 8;

  private static final int ALL = READ | MODIFY | CREATE | DESTROY;
```

```
  public ScheduledExecutorPermission(String name, String... actions) {
     super(name, actions);
   }

  @Override
  protected int initMask(String[] actions) {
     int mask = NONE;
     for (String action : actions) {
        if (ActionConstants.ACTION_ALL.equals(action)) {
           return ALL;
        }

        if (ActionConstants.ACTION_CREATE.equals(action)) {
           mask |= CREATE;
        } else if (ActionConstants.ACTION_READ.equals(action)) {
           mask |= READ;
        } else if (ActionConstants.ACTION_MODIFY.equals(action)) {
           mask |= MODIFY;
        } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
           mask |= DESTROY;
        }
     }
     return mask;
  }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class LockPermission extends InstancePermission {

  private static final  int LOCK = 4;
  private static final  int READ = 8;
```

```
  private static final  int ALL = CREATE | DESTROY | LOCK | READ;

  public LockPermission(String key, String... actions) {
     super(key, actions);
  }

  @Override
  protected
 int initMask(String[] actions) {
     int mask = NONE;
     for (String action : actions) {
        if (ActionConstants.ACTION_ALL.equals(action)) {
           return ALL;
        }

        if (ActionConstants.ACTION_CREATE.equals(action)) {
           mask |= CREATE;
        } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
           mask |= DESTROY;
        } else if (ActionConstants.ACTION_LOCK.equals(action)) {
           mask |= LOCK;
        } else if (ActionConstants.ACTION_READ.equals(action)) {
           mask |= READ;
        }
     }
     return mask;
  }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class CountDownLatchPermission extends InstancePermission {
```

```
  private static final int READ = 4;
  private static final int MODIFY = 8;
  private static final int ALL = CREATE | DESTROY | READ | MODIFY;

  public CountDownLatchPermission(String name, String... actions) {
     super(name, actions);
  }

  @Override
   protected int initMask(String[] actions) {
     int mask = NONE;
     for (String action : actions) {
        if (ActionConstants.ACTION_ALL.equals(action)) {
           return ALL;
        }

        if (ActionConstants.ACTION_CREATE.equals(action)) {
           mask |= CREATE;
        } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
           mask |= DESTROY;
        } else if (ActionConstants.ACTION_READ.equals(action)) {
           mask |= READ;
        } else if (ActionConstants.ACTION_MODIFY.equals(action)) {
           mask |= MODIFY;
        }
     }
     return mask;
  }
}
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

/**
* Contains all the security permissions
*/
```

```
package com.hazelcast.security.permission;
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

/**
* To be able to map-reduce from a client in a secure environment
*/
public class MapReducePermission extends InstancePermission {

  private static final int ALL = CREATE | DESTROY;

  public MapReducePermission(String name, String... actions) {
     super(name, actions);
  }

  @Override
  protected int initMask(String[]
 actions) {
     int mask = NONE;
     for (String action : actions) {
        if (ActionConstants.ACTION_ALL.equals(action)) {
           return ALL;
        }

        if (ActionConstants.ACTION_CREATE.equals(action)) {
           mask |= CREATE;
        } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
           mask |= DESTROY;
        }
     }
     return mask;
  }
}
```

```
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

package com.hazelcast.security.permission;

public class DurableExecutorServicePermission extends InstancePermission {

  private static final int ALL = CREATE | DESTROY;

  public DurableExecutorServicePermission(String name, String... actions) {
     super(name, actions);
  }

  @Override
  protected int initMask(String[] actions) {
     int mask = NONE;
      for (String action : actions) {
        if (ActionConstants.ACTION_ALL.equals(action)) {
           return ALL;
        }

        if (ActionConstants.ACTION_CREATE.equals(action)) {
           mask |= CREATE;
        } else if (ActionConstants.ACTION_DESTROY.equals(action)) {
           mask |= DESTROY;
        }
     }
     return mask;
  }
}
```

1.99 scala-compiler 2.10.0

1.99.1 Available under license :

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY
WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.100 jaxen 1.1.6

1.100.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1247 $
* $Date: 2006-11-08 11:06:30 -0800 (Wed, 08 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived

```
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: UnaryExpr.java 1247 2006-11-08 19:06:30Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/UnaryExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1168 $
* $Date: 2006-07-03 04:58:31 -0700 (Mon, 03 Jul 2006) $
*
* ================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
```

```
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: NamespaceContext.java 1168 2006-07-03 11:58:31Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/NamespaceContext.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
```

*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: IdFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/IdFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.

* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultNumberExpr.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultNumberExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$

```
* $Revision: 1161 $
* $Date: 2006-06-03 13:36:00 -0700 (Sat, 03 Jun 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: XPathSyntaxException.java 1161 2006-06-03 20:36:00Z elharo $
*/
```

Found in path(s):

* /jaxen-1-1-6-sources-jar/org/jaxen/XPathSyntaxException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.

*
* $Id: StringFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/StringFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1159 $
* $Date: 2006-06-03 13:25:34 -0700 (Sat, 03 Jun 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many

* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: SimpleNamespaceContext.java 1159 2006-06-03 20:25:34Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/SimpleNamespaceContext.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1300 $
* $Date: 2007-05-02 07:27:46 -0700 (Wed, 02 May 2007) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING

* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: Predicate.java 1300 2007-05-02 14:27:46Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/Predicate.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1245 $
* $Date: 2006-11-08 10:52:02 -0800 (Wed, 08 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER

* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: TextNodeStep.java 1245 2006-11-08 18:52:02Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/TextNodeStep.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1161 $
* $Date: 2006-06-03 13:36:00 -0700 (Sat, 03 Jun 2006) $
*
* ==
*
* Copyright 2000-2003 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from

this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: XOMXPath.java 1161 2006-06-03 20:36:00Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/xom/XOMXPath.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1255 $
* $Date: 2006-11-09 10:20:12 -0800 (Thu, 09 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the

```
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: AncestorAxisIterator.java 1255 2006-11-09 18:20:12Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/util/AncestorAxisIterator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1255 $
* $Date: 2006-11-09 10:20:12 -0800 (Thu, 09 Nov 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
```

```
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: LinkedIterator.java 1255 2006-11-09 18:20:12Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/util/LinkedIterator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
```

```
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: EvaluateFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/ext/EvaluateFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
```

```
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: LocaleFunctionSupport.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/ext/LocaleFunctionSupport.java
```

No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1162 $
* $Date: 2006-06-03 13:52:26 -0700 (Sat, 03 Jun 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
```

* $Id: Dom4jXPath.java 1162 2006-06-03 20:52:26Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/dom4j/Dom4jXPath.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1386 $
* $Date: 2012-07-29 09:29:13 -0400 (Sun, 29 Jul 2012) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals

on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: NumberFunction.java 1386 2012-07-29 13:29:13Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/NumberFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1396 $
* $Date: 2013-01-13 07:22:49 -0500 (Sun, 13 Jan 2013) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS

* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultGreaterThanExpr.java 1396 2013-01-13 12:22:49Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultGreaterThanExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1321 $
* $Date: 2008-04-26 17:30:06 -0700 (Sat, 26 Apr 2008) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,

* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: BaseXPath.java 1321 2008-04-27 00:30:06Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/BaseXPath.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*

* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: StackedIterator.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/util/StackedIterator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*

*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: LowerFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/ext/LowerFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1162 $
* $Date: 2006-06-03 13:52:26 -0700 (Sat, 03 Jun 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.

```
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: IterablePrecedingAxis.java 1162 2006-06-03 20:52:26Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/iter/IterablePrecedingAxis.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1193 $
* $Date: 2006-09-15 13:41:38 -0700 (Fri, 15 Sep 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
```

* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: XPathReaderFactory.java 1193 2006-09-15 20:41:38Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/saxpath/helpers/XPathReaderFactory.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*

```
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultPlusExpr.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultPlusExpr.java
No license file was found, but licenses were detected in source scan.
```

```
/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: StartsWithFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/
```

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/StartsWithFunction.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
```

on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultModExpr.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultModExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1332 $
* $Date: 2008-10-18 06:29:28 -0700 (Sat, 18 Oct 2008) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS

* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultEqualityExpr.java 1332 2008-10-18 13:29:28Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultEqualityExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,

* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: SubstringBeforeFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/SubstringBeforeFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from

this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultMinusExpr.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultMinusExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the

```
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultFilterExpr.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultFilterExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
```

```
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultRelativeLocationPath.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultRelativeLocationPath.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1345 $
* $Date: 2009-10-22 07:25:23 -0400 (Thu, 22 Oct 2009) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
```

*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultLocationPath.java 1345 2009-10-22 11:25:23Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultLocationPath.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1277 $

```
* $Date: 2007-01-05 10:25:43 -0800 (Fri, 05 Jan 2007) $
*
* ========================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ========================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultBinaryExpr.java 1277 2007-01-05 18:25:43Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultBinaryExpr.java
```

No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1161 $
* $Date: 2006-06-03 13:36:00 -0700 (Sat, 03 Jun 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
```

*
* $Id: SAXPathException.java 1161 2006-06-03 20:36:00Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/saxpath/SAXPathException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1161 $
* $Date: 2006-06-03 13:36:00 -0700 (Sat, 03 Jun 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many

* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: JDOMXPath.java 1161 2006-06-03 20:36:00Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/jdom/JDOMXPath.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1162 $
* $Date: 2006-06-03 13:52:26 -0700 (Sat, 03 Jun 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING

* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: IterableFollowingSiblingAxis.java 1162 2006-06-03 20:52:26Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/iter/IterableFollowingSiblingAxis.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1396 $
* $Date: 2013-01-13 07:22:49 -0500 (Sun, 13 Jan 2013) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER

* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultEqualsExpr.java 1396 2013-01-13 12:22:49Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultEqualsExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1222 $
* $Date: 2006-11-08 05:59:38 -0800 (Wed, 08 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from

this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: XPathFunctionContext.java 1222 2006-11-08 13:59:38Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/XPathFunctionContext.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1237 $
* $Date: 2006-11-08 09:17:32 -0800 (Wed, 08 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright

```
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*    * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: NumberExpr.java 1237 2006-11-08 17:17:32Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/NumberExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1133 $
* $Date: 2006-03-30 05:56:36 -0800 (Thu, 30 Mar 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
```

* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: Axis.java 1133 2006-03-30 13:56:36Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/saxpath/Axis.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*

* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultRelationalExpr.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultRelationalExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$

```
* $Revision: 1257 $
* $Date: 2006-11-13 14:10:09 -0800 (Mon, 13 Nov 2006) $
*
* ============================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ============================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: PrecedingSiblingAxisIterator.java 1257 2006-11-13 22:10:09Z elharo $
*/
```

Found in path(s):

* /jaxen-1-1-6-sources-jar/org/jaxen/util/PrecedingSiblingAxisIterator.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ============================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ============================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
```

*
* $Id: ContainsFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/ContainsFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1168 $
* $Date: 2006-07-03 04:58:31 -0700 (Mon, 03 Jul 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many

* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: VariableContext.java 1168 2006-07-03 11:58:31Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/VariableContext.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING

* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: FloorFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/FloorFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1334 $
* $Date: 2008-11-29 09:58:48 -0800 (Sat, 29 Nov 2008) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A

* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: XPathReader.java 1334 2008-11-29 17:58:48Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/saxpath/base/XPathReader.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1255 $
* $Date: 2006-11-09 10:20:12 -0800 (Thu, 09 Nov 2006) $
*
* ==
*
* Copyright 2000-2005 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived

```
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: FollowingAxisIterator.java 1255 2006-11-09 18:20:12Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/util/FollowingAxisIterator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
```

```
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*    * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: SimpleFunctionContext.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/SimpleFunctionContext.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1157 $
* $Date: 2006-06-03 13:07:37 -0700 (Sat, 03 Jun 2006) $
*
* ====================================================================
*
* Copyright 2000-2005 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
```

* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: Navigator.java 1157 2006-06-03 20:07:37Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/Navigator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*

* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: ConcatFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/ConcatFunction.java
No license file was found, but licenses were detected in source scan.

/*
$Id: IterableAttributeAxis.java 1162 2006-06-03 20:52:26Z elharo $

Copyright 2003 The Werken Company. All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

 * Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.

 * Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

 * Neither the name of the Jaxen Project nor the names of its
   contributors may be used to endorse or promote products derived
   from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
IS" AND ANY EXPRESS OR IMPLIED WARRANTIES,
 INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/iter/IterableAttributeAxis.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1162 $
* $Date: 2006-06-03 13:52:26 -0700 (Sat, 03 Jun 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without

* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: IterableDescendantOrSelfAxis.java 1162 2006-06-03 20:52:26Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/iter/IterableDescendantOrSelfAxis.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ==

*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultAbsoluteLocationPath.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultAbsoluteLocationPath.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultStep.java 1128 2006-02-05 21:49:04Z elharo $
*/
```

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultStep.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1162 $
* $Date: 2006-06-03 13:52:26 -0700 (Sat, 03 Jun 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
```

* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultXPathExpr.java 1162 2006-06-03 20:52:26Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultXPathExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1252 $
* $Date: 2006-11-09 08:21:05 -0800 (Thu, 09 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*

* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: EqualityExpr.java 1252 2006-11-09 16:21:05Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/EqualityExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1134 $
* $Date: 2006-04-07 10:11:52 -0700 (Fri, 07 Apr 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR

* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: Pattern.java 1134 2006-04-07 17:11:52Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/pattern/Pattern.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED

* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: NamespaceUriFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/NamespaceUriFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1154 $
* $Date: 2006-06-01 06:19:30 -0700 (Thu, 01 Jun 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived

```
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: QualifiedName.java 1154 2006-06-01 13:19:30Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/QualifiedName.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1324 $
* $Date: 2008-04-26 18:48:59 -0700 (Sat, 26 Apr 2008) $
*
* ================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
```

```
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*    * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: StringLengthFunction.java 1324 2008-04-27 01:48:59Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/StringLengthFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
```

```
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: PatternParser.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/pattern/PatternParser.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
```

* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultAdditiveExpr.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultAdditiveExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$

* $Revision: 1161 $
* $Date: 2006-06-03 13:36:00 -0700 (Sat, 03 Jun 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: XPathSyntaxException.java 1161 2006-06-03 20:36:00Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/saxpath/XPathSyntaxException.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
```

* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: Function.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/Function.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1234 $
* $Date: 2006-11-08 08:47:30 -0800 (Wed, 08 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==

* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: LiteralExpr.java 1234 2006-11-08 16:47:30Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/LiteralExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF

* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: LocalNameFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/LocalNameFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1302 $
* $Date: 2007-05-02 07:33:29 -0700 (Wed, 02 May 2007) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A

* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: SelfAxisIterator.java 1302 2007-05-02 14:33:29Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/util/SelfAxisIterator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1235 $
* $Date: 2006-11-08 09:02:21 -0800 (Wed, 08 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from

this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: LocationPath.java 1235 2006-11-08 17:02:21Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/LocationPath.java
No license file was found, but licenses were detected in source scan.

/*
$Id: Context.java 1219 2006-10-15 21:08:16Z elharo $

Copyright 2003 The Werken Company. All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

 * Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.

 * Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

 * Neither the name of the Jaxen Project nor the names of its
   contributors may be used to endorse or promote products derived
   from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING,
BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/Context.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1300 $
* $Date: 2007-05-02 07:27:46 -0700 (Wed, 02 May 2007) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED

* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: PathExpr.java 1300 2007-05-02 14:27:46Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/PathExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1255 $
* $Date: 2006-11-09 10:20:12 -0800 (Thu, 09 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived

* from
this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: SingleObjectIterator.java 1255 2006-11-09 18:20:12Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/util/SingleObjectIterator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright

```
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*    * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: UnionPattern.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/pattern/UnionPattern.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
```

* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: Operator.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/saxpath/Operator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1366 $
* $Date: 2012-05-05 12:17:35 -0400 (Sat, 05 May 2012) $
*
* ==
*

* Copyright 2000-2004 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultFunctionCallExpr.java 1366 2012-05-05 16:17:35Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultFunctionCallExpr.java
No license file was found, but licenses were detected in source scan.

/*

```
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultPredicate.java 1261 2006-11-30 18:49:27Z elharo $
*/
```

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultPredicate.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the

* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: FalseFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/FalseFunction.java
No license file was found, but licenses were detected in source scan.

/*
$Id: IterableAxis.java 1128 2006-02-05 21:49:04Z elharo $

Copyright 2003 The Werken Company. All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

 * Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.

 * Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

 * Neither the name of the Jaxen Project nor the names of its
   contributors may be used to endorse or promote products derived
   from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
IS" AND ANY EXPRESS OR IMPLIED WARRANTIES,
 INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/iter/IterableAxis.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultUnaryExpr.java 1261 2006-11-30 18:49:27Z elharo $
*/
```

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultUnaryExpr.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1255 $
* $Date: 2006-11-09 10:20:12 -0800 (Thu, 09 Nov 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
```

* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: FollowingSiblingAxisIterator.java 1255 2006-11-09 18:20:12Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/util/FollowingSiblingAxisIterator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1252 $
* $Date: 2006-11-09 08:21:05 -0800 (Thu, 09 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*

```
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: BinaryExpr.java 1252 2006-11-09 16:21:05Z elharo $
*/
```

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/BinaryExpr.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
```

* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultAllNodeStep.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultAllNodeStep.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1326 $
* $Date: 2008-04-26 18:56:10 -0700 (Sat, 26 Apr 2008) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED

* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: FilterExpr.java 1326 2008-04-27 01:56:10Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/FilterExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived

```
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: RoundFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/RoundFunction.java
No license file was found, but licenses were detected in source scan.

/*
$Id: ContextSupport.java 1157 2006-06-03 20:07:37Z elharo $

Copyright 2003 The Werken Company. All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

 * Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.

 * Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

 * Neither the name of the Jaxen Project nor the names of its
   contributors may be used to endorse or promote products derived
```

from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/ContextSupport.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS

* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: Expr.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/Expr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*

```
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultPathExpr.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultPathExpr.java
No license file was found, but licenses were detected in source scan.

/*
$Id: DefaultNameStep.java 1290 2007-04-17 01:26:35Z bewins $

Copyright 2003 The Werken Company. All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

 * Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.

 * Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
```

```
 * Neither the name of the Jaxen Project nor the names of its
   contributors may be used to endorse or promote products derived
   from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
IS" AND ANY EXPRESS OR IMPLIED WARRANTIES,
 INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultNameStep.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
```

this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/SubstringFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.

*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: SumFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/SumFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1232 $
* $Date: 2006-11-08 08:37:59 -0800 (Wed, 08 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright

```
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: FunctionCallExpr.java 1232 2006-11-08 16:37:59Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/FunctionCallExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1252 $
* $Date: 2006-11-09 08:21:05 -0800 (Thu, 09 Nov 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
```

* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: LogicalExpr.java 1252 2006-11-09 16:21:05Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/LogicalExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*

```
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: TranslateFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/TranslateFunction.java
No license file was found, but licenses were detected in source scan.
```

```
/*
* $Header$
* $Revision: 1171 $
* $Date: 2006-07-03 06:17:30 -0700 (Mon, 03 Jul 2006) $
*
* ====================================================================
*
* Copyright 2000-2005 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DocumentNavigator.java 1171 2006-07-03 13:17:30Z elharo $
```

*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/dom4j/DocumentNavigator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1226 $
* $Date: 2006-11-08 07:44:33 -0800 (Wed, 08 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals

on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: ProcessingInstructionNodeStep.java 1226 2006-11-08 15:44:33Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/ProcessingInstructionNodeStep.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS

* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: NodeTypeTest.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/pattern/NodeTypeTest.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,

* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: NameFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/NameFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1159 $
* $Date: 2006-06-03 13:25:34 -0700 (Sat, 03 Jun 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*

* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: UnresolvableException.java 1159 2006-06-03 20:25:34Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/UnresolvableException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1251 $
* $Date: 2006-11-09 08:11:38 -0800 (Thu, 09 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.

*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultXPathFactory.java 1251 2006-11-09 16:11:38Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultXPathFactory.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1334 $
* $Date: 2008-11-29 09:58:48 -0800 (Sat, 29 Nov 2008) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*

```
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: XPathLexer.java 1334 2008-11-29 17:58:48Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/saxpath/base/XPathLexer.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
```

```
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: AnyNodeTest.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/pattern/AnyNodeTest.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
```

```
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: NotFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/NotFunction.java
```

No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
```

* $Id: TrueFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/TrueFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1252 $
* $Date: 2006-11-09 08:21:05 -0800 (Thu, 09 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many

* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: AdditiveExpr.java 1252 2006-11-09 16:21:05Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/AdditiveExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: $
* $Revision: $
* $Date: $
*
* ==
*
* Copyright 2000-2005 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from this software without specific prior written
 permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF

* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals on behalf of the Jaxen Project and was originally
 * created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/JaxenRuntimeException.java
* /jaxen-1-1-6-sources-jar/org/jaxen/JaxenConstants.java
No license file was found, but licenses were detected in source scan.

/*
$Id: IterableChildAxis.java 1162 2006-06-03 20:52:26Z elharo $

Copyright 2003 The Werken Company. All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

 * Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.

 * Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

 * Neither the name of the Jaxen Project nor the names of its
   contributors may be used to endorse or promote products derived
   from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
IS" AND ANY EXPRESS OR IMPLIED WARRANTIES,
 INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF

LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/iter/IterableChildAxis.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1268 $
* $Date: 2006-12-10 07:32:14 -0800 (Sun, 10 Dec 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*

* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: Step.java 1268 2006-12-10 15:32:14Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/Step.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR

* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultCommentNodeStep.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultCommentNodeStep.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED

* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: LocationPathPattern.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/pattern/LocationPathPattern.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1162 $
* $Date: 2006-06-03 13:52:26 -0700 (Sat, 03 Jun 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived

```
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DOMXPath.java 1162 2006-06-03 20:52:26Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/dom/DOMXPath.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1258 $
* $Date: 2006-11-13 14:38:17 -0800 (Mon, 13 Nov 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
```

```
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: PredicateSet.java 1258 2006-11-13 22:38:17Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/PredicateSet.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1162 $
* $Date: 2006-06-03 13:52:26 -0700 (Sat, 03 Jun 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
```

* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: IterableNamespaceAxis.java 1162 2006-06-03 20:52:26Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/iter/IterableNamespaceAxis.java
No license file was found, but licenses were detected in source scan.

/*
$Id: XPath.java 1304 2007-05-02 15:00:13Z elharo $

Copyright 2003 The Werken Company. All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are

met:

 * Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.

 * Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

 * Neither the name of the Jaxen Project nor the names of its
   contributors may be used to endorse or promote products derived
   from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING,
 BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/XPath.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1334 $
* $Date: 2008-11-29 09:58:48 -0800 (Sat, 29 Nov 2008) $
*
* ==
*
* Copyright 2000-2004 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright

```
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: TokenTypes.java 1334 2008-11-29 17:58:48Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/saxpath/base/TokenTypes.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1162 $
* $Date: 2006-06-03 13:52:26 -0700 (Sat, 03 Jun 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
```

```
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: IterableDescendantAxis.java 1162 2006-06-03 20:52:26Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/iter/IterableDescendantAxis.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1370 $
* $Date: 2012-05-06 19:52:12 -0400 (Sun, 06 May 2012) $
*
```

```
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: NamespaceNode.java 1370 2012-05-06 23:52:12Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/dom/NamespaceNode.java
No license file was found, but licenses were detected in source scan.
```

```
/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultLogicalExpr.java 1128 2006-02-05 21:49:04Z elharo $
*/
```

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultLogicalExpr.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1162 $
* $Date: 2006-06-03 13:52:26 -0700 (Sat, 03 Jun 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
```

* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: IterableFollowingAxis.java 1162 2006-06-03 20:52:26Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/iter/IterableFollowingAxis.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1252 $
* $Date: 2006-11-09 08:21:05 -0800 (Thu, 09 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*

```
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: RelationalExpr.java 1252 2006-11-09 16:21:05Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/RelationalExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
```

* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultGreaterThanEqualExpr.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultGreaterThanEqualExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED

* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultUnionExpr.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultUnionExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived

*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: TextNodeTest.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/pattern/TextNodeTest.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright

```
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*    * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: XPathNamespace.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/jdom/XPathNamespace.java
No license file was found, but licenses were detected in source scan.

/*
$Id: DocumentNavigator.java 1161 2006-06-03 20:36:00Z elharo $

Copyright 2003 The Werken Company. All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

 * Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.

 * Redistributions in binary form must reproduce the above copyright
```

notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

* Neither the name of the Jaxen Project nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/javabean/DocumentNavigator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its

*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: NamespaceTest.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/pattern/NamespaceTest.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1257 $
* $Date: 2006-11-13 14:10:09 -0800 (Mon, 13 Nov 2006) $
*
* ==
*
* Copyright 2000-2005 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.

```
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: PrecedingAxisIterator.java 1257 2006-11-13 22:10:09Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/util/PrecedingAxisIterator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
```

* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultAndExpr.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultAndExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==

```
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DocumentFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/xslt/DocumentFunction.java
No license file was found, but licenses were detected in source scan.

/*
```

```
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: LangFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/
```

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/LangFunction.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1160 $
* $Date: 2006-06-03 13:26:02 -0700 (Sat, 03 Jun 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
```

* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: UnsupportedAxisException.java 1160 2006-06-03 20:26:02Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/UnsupportedAxisException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1253 $
* $Date: 2006-11-09 08:39:19 -0800 (Thu, 09 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==

* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: SingletonList.java 1253 2006-11-09 16:39:19Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/util/SingletonList.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1156 $
* $Date: 2006-06-03 13:04:05 -0700 (Sat, 03 Jun 2006) $
*
* ==
*
* Copyright 2000-2003 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR

* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DocumentNavigator.java 1156 2006-06-03 20:04:05Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/xom/DocumentNavigator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1159 $
* $Date: 2006-06-03 13:25:34 -0700 (Sat, 03 Jun 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED

* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: SimpleVariableContext.java 1159 2006-06-03 20:25:34Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/SimpleVariableContext.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived

```
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: FunctionContext.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/FunctionContext.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
```

```
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: XPathReader.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/saxpath/XPathReader.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
```

* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: CeilingFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/CeilingFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1162 $
* $Date: 2006-06-03 13:52:26 -0700 (Sat, 03 Jun 2006) $
*
* ==
*

* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: IterablePrecedingSiblingAxis.java 1162 2006-06-03 20:52:26Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/iter/IterablePrecedingSiblingAxis.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$

```
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ============================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ============================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: NodeTest.java 1128 2006-02-05 21:49:04Z elharo $
*/
```

Found in path(s):

* /jaxen-1-1-6-sources-jar/org/jaxen/pattern/NodeTest.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1161 $
* $Date: 2006-06-03 13:36:00 -0700 (Sat, 03 Jun 2006) $
*
* ============================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ============================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
```

*
* $Id: JaxenException.java 1161 2006-06-03 20:36:00Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/JaxenException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1179 $
* $Date: 2006-07-16 04:07:25 -0700 (Sun, 16 Jul 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many

* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: FunctionCallException.java 1179 2006-07-16 11:07:25Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/FunctionCallException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING

* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: EndsWithFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/ext/EndsWithFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1248 $
* $Date: 2006-11-08 11:20:29 -0800 (Wed, 08 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER

* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: VariableReferenceExpr.java 1248 2006-11-08 19:20:29Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/VariableReferenceExpr.java
No license file was found, but licenses were detected in source scan.

/*
$Id: NamedAccessNavigator.java 1128 2006-02-05 21:49:04Z elharo $

Copyright 2003 The Werken Company. All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

 * Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.

 * Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

 * Neither the name of the Jaxen Project nor the names of its
   contributors may be used to endorse or promote products derived
   from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
IS" AND ANY EXPRESS OR IMPLIED WARRANTIES,
 INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER

OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/NamedAccessNavigator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1364 $
* $Date: 2011-07-30 05:46:45 -0400 (Sat, 30 Jul 2011) $
*
* ==
*
* Copyright 2000-2005 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR

* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DocumentNavigator.java 1364 2011-07-30 09:46:45Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/dom/DocumentNavigator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS

* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultMultiplyExpr.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultMultiplyExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its

*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultMultiplicativeExpr.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultMultiplicativeExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*

* * Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.
*
* * Neither the name of the Jaxen Project nor the names of its
* contributors may be used to endorse or promote products derived
* from
this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultDivExpr.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultDivExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1198 $
* $Date: 2006-09-21 04:48:05 -0700 (Thu, 21 Sep 2006) $
*
* ==
*
* Copyright 2000-2005 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without

* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DocumentNavigator.java 1198 2006-09-21 11:48:05Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/jdom/DocumentNavigator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1255 $
* $Date: 2006-11-09 10:20:12 -0800 (Thu, 09 Nov 2006) $
*
* ==

```
*
* Copyright 2000-2005 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DescendantOrSelfAxisIterator.java 1255 2006-11-09 18:20:12Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/util/DescendantOrSelfAxisIterator.java
No license file was found, but licenses were detected in source scan.
```

```
/*
* $Header$
* $Revision: 1161 $
* $Date: 2006-06-03 13:36:00 -0700 (Sat, 03 Jun 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: JavaBeanXPath.java 1161 2006-06-03 20:36:00Z elharo $
*/
```

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/javabean/JavaBeanXPath.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
```

* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: UpperFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/ext/UpperFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*

* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: PositionFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/PositionFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1325 $
* $Date: 2008-04-26 18:55:05 -0700 (Sat, 26 Apr 2008) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR

* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: MultiplicativeExpr.java 1325 2008-04-27 01:55:05Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/MultiplicativeExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1273 $
* $Date: 2007-01-03 12:47:42 -0800 (Wed, 03 Jan 2007) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED

* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultLiteralExpr.java 1273 2007-01-03 20:47:42Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultLiteralExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its

```
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultXPathHandler.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/saxpath/helpers/DefaultXPathHandler.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
```

```
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: NoNodeTest.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/pattern/NoNodeTest.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
```

* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: Token.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/saxpath/base/Token.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==

```
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: SAXPathEventSource.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/saxpath/SAXPathEventSource.java
No license file was found, but licenses were detected in source scan.
```

```
/*
* $Header$
* $Revision: 1162 $
* $Date: 2006-06-03 13:52:26 -0700 (Sat, 03 Jun 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: IterableParentAxis.java 1162 2006-06-03 20:52:26Z elharo $
*/
```

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/iter/IterableParentAxis.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
```

* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: LastFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/LastFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1225 $
* $Date: 2006-11-08 07:42:39 -0800 (Wed, 08 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*

```
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: AllNodeStep.java 1225 2006-11-08 15:42:39Z elharo $
*/
```

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/AllNodeStep.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1236 $
* $Date: 2006-11-08 09:10:02 -0800 (Wed, 08 Nov 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
```

* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: NameStep.java 1236 2006-11-08 17:10:02Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/NameStep.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1279 $
* $Date: 2007-01-06 04:21:12 -0800 (Sat, 06 Jan 2007) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED

* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultProcessingInstructionNodeStep.java 1279 2007-01-06 12:21:12Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultProcessingInstructionNodeStep.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1306 $
* $Date: 2007-05-02 08:04:46 -0700 (Wed, 02 May 2007) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived

*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: XPathExpr.java 1306 2007-05-02 15:04:46Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/XPathExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright

```
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*    * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: CountFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/CountFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
```

*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultExpr.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1162 $
* $Date: 2006-06-03 13:52:26 -0700 (Sat, 03 Jun 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.

* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: IterableSelfAxis.java 1162 2006-06-03 20:52:26Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/iter/IterableSelfAxis.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1241 $

```
* $Date: 2006-11-08 10:07:25 -0800 (Wed, 08 Nov 2006) $
*
* ========================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ========================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: Predicated.java 1241 2006-11-08 18:07:25Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/Predicated.java
```

No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
```

* $Id: PatternHandler.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/pattern/PatternHandler.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1335 $
* $Date: 2008-11-30 06:20:38 -0800 (Sun, 30 Nov 2008) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals

on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultTruthExpr.java 1335 2008-11-30 14:20:38Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultTruthExpr.java
No license file was found, but licenses were detected in source scan.

/*--
*
* Id
*
* Copyright 2000-2004 Jason Hunter & Brett McLaughlin.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY
 EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==

* This software consists of voluntary contributions made by many
* individuals on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.
 For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/saxpath/base/Verifier.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1255 $
* $Date: 2006-11-09 10:20:12 -0800 (Thu, 09 Nov 2006) $
*
* ==
*
* Copyright 2000-2005 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF

* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DescendantAxisIterator.java 1255 2006-11-09 18:20:12Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/util/DescendantAxisIterator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A

* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: SubstringAfterFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/SubstringAfterFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1132 $
* $Date: 2006-03-30 05:53:11 -0800 (Thu, 30 Mar 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from

this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: JaxenHandler.java 1132 2006-03-30 13:53:11Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/JaxenHandler.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1255 $
* $Date: 2006-11-09 10:20:12 -0800 (Thu, 09 Nov 2006) $
*
* ==
*
* Copyright 2000-2005 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright

```
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*    * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: AncestorOrSelfAxisIterator.java 1255 2006-11-09 18:20:12Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/util/AncestorOrSelfAxisIterator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1396 $
* $Date: 2013-01-13 07:22:49 -0500 (Sun, 13 Jan 2013) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
```

```
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultLessThanExpr.java 1396 2013-01-13 12:22:49Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultLessThanExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
```

* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: AnyChildNodeTest.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/pattern/AnyChildNodeTest.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $

```
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: BooleanFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/BooleanFunction.java
```

No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
```

*
* $Id: XPathHandler.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/saxpath/XPathHandler.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many

* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultArithExpr.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultArithExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1396 $
* $Date: 2013-01-13 07:22:49 -0500 (Sun, 13 Jan 2013) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING

* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultLessThanEqualExpr.java 1396 2013-01-13 12:22:49Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultLessThanEqualExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1225 $
* $Date: 2006-11-08 07:42:39 -0800 (Wed, 08 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER

* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: CommentNodeStep.java 1225 2006-11-08 15:42:39Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/CommentNodeStep.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1367 $
* $Date: 2012-05-05 12:31:33 -0400 (Sat, 05 May 2012) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from

this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultVariableReferenceExpr.java 1367 2012-05-05 16:31:33Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultVariableReferenceExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the

```
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultNavigator.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/DefaultNavigator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1228 $
* $Date: 2006-11-08 08:00:22 -0800 (Wed, 08 Nov 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
```

```
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: UnionExpr.java 1228 2006-11-08 16:00:22Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/UnionExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1396 $
* $Date: 2013-01-13 07:22:49 -0500 (Sun, 13 Jan 2013) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
```

*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultNotEqualsExpr.java 1396 2013-01-13 12:22:49Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultNotEqualsExpr.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $

```
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultOrExpr.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultOrExpr.java
```

No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision$
* $Date$
*
* ====================================================================
*
* Copyright 2005 Elliotte Rusty Harold.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from this software without specific prior written permission.
*
* THIS
 SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals on behalf of the Jaxen Project and was originally
* created
 by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
```

```
* $Id$
*/
```

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/NodeComparator.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ============================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ============================================================================
* This software consists of voluntary contributions made by many
* individuals
```

on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: NameTest.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/pattern/NameTest.java
No license file was found, but licenses were detected in source scan.

/*
Id

Copyright 2005 Elliotte Rusty Harold. All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

 * Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.

 * Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.

 * Neither the name of the Jaxen Project nor the names of its
   contributors may be used to endorse or promote products derived
   from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES
 OF MERCHANTABILITY AND FITNESS FOR A
PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

Found in path(s):

* /jaxen-1-1-6-sources-jar/org/jaxen/expr/IdentitySet.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header$
* $Revision: 1162 $
* $Date: 2006-06-03 13:52:26 -0700 (Sat, 03 Jun 2006) $
*
* ====================================================================
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*     notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*     notice, this list of conditions and the following disclaimer in the
*     documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*     contributors may be used to endorse or promote products derived
*     from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ====================================================================
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>.  For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
```

*
* $Id: IterableAncestorOrSelfAxis.java 1162 2006-06-03 20:52:26Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/iter/IterableAncestorOrSelfAxis.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1128 $
* $Date: 2006-02-05 13:49:04 -0800 (Sun, 05 Feb 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many

* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: NormalizeSpaceFunction.java 1128 2006-02-05 21:49:04Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/function/NormalizeSpaceFunction.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1337 $
* $Date: 2008-12-02 17:58:10 -0800 (Tue, 02 Dec 2008) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF

* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: XPathFactory.java 1337 2008-12-03 01:58:10Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/XPathFactory.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1162 $
* $Date: 2006-06-03 13:52:26 -0700 (Sat, 03 Jun 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from
 this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A

* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: IterableAncestorAxis.java 1162 2006-06-03 20:52:26Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/iter/IterableAncestorAxis.java
No license file was found, but licenses were detected in source scan.

/*
* $Header$
* $Revision: 1261 $
* $Date: 2006-11-30 10:49:27 -0800 (Thu, 30 Nov 2006) $
*
* ==
*
* Copyright 2000-2002 bob mcwhirter & James Strachan.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
*   * Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
*   * Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
*   * Neither the name of the Jaxen Project nor the names of its
*   contributors may be used to endorse or promote products derived
*   from

this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
* PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER
* OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*
* ==
* This software consists of voluntary contributions made by many
* individuals
 on behalf of the Jaxen Project and was originally
* created by bob mcwhirter <bob@werken.com> and
* James Strachan <jstrachan@apache.org>. For more information on the
* Jaxen Project, please see <http://www.jaxen.org/>.
*
* $Id: DefaultTextNodeStep.java 1261 2006-11-30 18:49:27Z elharo $
*/

Found in path(s):
* /jaxen-1-1-6-sources-jar/org/jaxen/expr/DefaultTextNodeStep.java

1.101 scala-reflect 2.10.4

1.102 swagger-annotations 1.3.12

1.103 swagger-jersey2-jaxrs 1.5.0

1.104 commons-compiler 2.6.1

1.105 proto-google-common-protos 1.0.0

1.106 minlog 1.2

1.107 hazelcast 3.8.9

1.107.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 Viktor Gamov

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Copyright (c) 2013, 2014 EclipseSource

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all

copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a

copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a

cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with

the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
**
** NOTICE file corresponding to the section 4 (d) of the Apache License,
** Version 2.0, in this case for the Hazelcast distribution.
**

The end-user documentation included with a redistribution, if any,
must include the following acknowledgement:

"This product includes software developed by the Hazelcast
Project (http://www.hazelcast.com)."

Alternately, this acknowledgement may appear in the software itself,
if and wherever such third-party acknowledgements normally appear.

The name "Hazelcast" must not be used to endorse or promote products
derived from this software without prior written permission. For
written permission, please contact talip@hazelcast.com or fuad@hazelcast.com

Copyright (c) 2008-2016 Hazelcast Inc. All rights reserved.

1.108 unirest-java 1.4.5

1.108.1 Available under license :

/*
The MIT License

Copyright (c) 2013 Mashape (http://mashape.com)

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
 OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/
//Copyright 2003-2010 Christian d'Heureuse, Inventec Informatik AG, Zurich, Switzerland
//www.source-code.biz, www.inventec.ch/chdh
//
//This module is multi-licensed and may be used under the terms
//of any of the following licenses:
//
//EPL, Eclipse Public License, V1.0 or later, http://www.eclipse.org/legal
//LGPL, GNU Lesser General Public License, V2.1 or later, http://www.gnu.org/licenses/lgpl.html
//GPL, GNU General Public License, V2 or later, http://www.gnu.org/licenses/gpl.html
//AL, Apache License, V2.0 or later, http://www.apache.org/licenses
//BSD, BSD License, http://www.opensource.org/licenses/bsd-license.php
//MIT, MIT License, http://www.opensource.org/licenses/MIT
//
//Please contact the author if you need another license.
//This module is provided "as is", without warranties of any kind.

1.109 jul-to-slf4j 1.7.21

1.109.1 Available under license :

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
IN THE SOFTWARE.

1.110 open-csv 4.1

1.111 asm-util 4.0

1.112 not-yet-commons-ssl 0.3.11

1.112.1 Available under license :

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

The PKCS12 key derivation function was developed by BouncyCastle
(bouncycastle.org). (Look for the "pkcs12()" method inside PKCS8.java).

Some of this software was originally developed by
Credit Union Central of British Columbia (http://www.cucbc.com/).
The CUCBC code was licensed to the Apache Software Foundation on
August 23rd, 2006.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally

submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the

content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but

not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work,

where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and

may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this

License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.113 asm-tree 4.0

1.114 castor-core 1.3.1

1.114.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or
(iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from)
the Work and for which the
editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication
on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant
of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual,

worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as

of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed

as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names
of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing

the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your
sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Copyright 1999-2004 (C) Intalio Inc., and others. All Rights Reserved.

Redistribution and use of this software and associated documentation
("Software"), with or without modification, are permitted provided
that the following conditions are met:

1. Redistributions of source code must retain copyright statements
and notices. Redistributions must also contain a copy of this
document.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

3. The name "ExoLab" must not be used to endorse or promote products
derived from this Software without prior written permission of
Intalio Inc. For written permission, please contact info@exolab.org.

4. Products derived from this Software may not be called "Castor"
nor may "Castor" appear in their names without prior written
permission of Intalio Inc. Exolab,
Castor and Intalio are
trademarks of Intalio Inc.

5. Due credit should be given to the ExoLab Project
(http://www.exolab.org/).

THIS SOFTWARE IS PROVIDED BY INTALIO AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL INTALIO OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.115 quartz 2.2.1

1.116 commons-pool 1.5.3

1.116.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,

and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to

communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and

attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or

implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Commons Pool
Copyright 1999-2009 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

1.117 quartz 1.6.0

1.118 woodstox-core-asl 4.1.4

1.118.1 Available under license :

No license file was found, but licenses were detected in source scan.

/* Woodstox XML processor
*
* Copyright (c) 2004- Tatu Saloranta, tatu.saloranta@iki.fi
*
* Licensed under the License specified in the file LICENSE,
* included with the source code.
* You may not use this file except in compliance with the License.
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sw/BaseNsStreamWriter.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sw/SimpleNsStreamWriter.java
No license file was found, but licenses were detected in source scan.

/* Woodstox XML processor
*
* Copyright (c) 2004- Tatu Saloranta, tatu.saloranta@iki.fi
*

* Licensed under the License specified in the file LICENSE,
* included with the source code.
* You may not use this file except in compliance with the License.
*
* Unless required by applicable law or agreed to in writing, softwar
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sw/RepairingNsStreamWriter.java
No license file was found, but licenses were detected in source scan.

/* Woodstox XML processor
*
* Copyright (c) 2005 Tatu Saloranta, tatu.saloranta@iki.fi
*
* Licensed under the License specified in file LICENSE, included with
* the source code.
* You may not use this file except in compliance with the License.
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sw/OutputElementBase.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/util/BijectiveNsMap.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sw/SimpleOutputElement.java
No license file was found, but licenses were detected in source scan.

/* Woodstox XML processor
*
* Copyright (c) 2004 Tatu Saloranta, tatu.saloranta@iki.fi
*
* Licensed under the License specified in the file LICENSE which is
* included with the source code.
* You may not use this file except in compliance with the License.
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
*/

Found in path(s):
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/DFAState.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/ContentSpec.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/DFAValidator.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/StructValidator.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2004- Tatu Saloranta, tatu.saloranta@iki.fi
*
* Licensed under the License specified in file LICENSE, included with
* the source code.
* You may not use this file except in compliance with the License.
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sax/WstxSAXParser.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sax/WstxSAXParserFactory.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sax/SAXProperty.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sax/SAXFeature.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sax/WrappedSaxException.java
No license file was found, but licenses were detected in source scan.

/* Woodstox XML processor
*
* Copyright (c) 2004 Tatu Saloranta, tatu.saloranta@iki.fi
*
* Licensed under the License specified in file LICENSE, included with
* the source code.
* You may not use this file except in compliance with the License.
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):

* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/util/PrefixedName.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/io/AsciiReader.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/evt/BaseStartElement.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/io/EBCDICCodec.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/io/UTF32Reader.java
*
 /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/exc/WstxException.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/exc/WstxLazyException.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/evt/DefaultEventAllocator.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/PrefixedNameSet.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/io/UTF8Reader.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/stax/WstxEventFactory.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/ent/EntityDecl.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/io/WstxInputLocation.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/io/WstxInputData.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/util/BaseNsContext.java
No license file was found, but licenses were detected in source scan.

/* Woodstox XML processor
*
* Copyright (c) 2004- Tatu Saloranta, tatu.saloranta@iki.fi
*
* Licensed under the License specified in file LICENSE, included with
* the source code.
* You may not use this file except in compliance with the License.
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/DTDValidatorBase.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sr/AttributeCollector.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sr/TypedStreamReader.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sw/XmlWriter.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/DTDValidator.java
*
 /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sr/BasicStreamReader.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sw/EncodingXmlWriter.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/DTDEventListener.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sw/TypedStreamWriter.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sw/AsciiXmlWriter.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sr/InputElementStack.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/DTDSubsetImpl.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sr/StreamScanner.java

* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sw/ISOLatin1XmlWriter.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sr/Element.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sw/XmlWriterWrapper.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sr/NsDefaultProvider.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/FullDTDReader.java
*
 /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sw/BufferingXmlWriter.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/io/ReaderBootstrapper.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/MinimalDTDReader.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/io/ISOLatinReader.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sr/Attribute.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/io/WstxInputSource.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sw/BaseStreamWriter.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/DTDTypingNonValidator.java
No license file was found, but licenses were detected in source scan.

/* Woodstox XML processor
*
* Copyright (c) 2004- Tatu Saloranta, tatu.saloranta@iki.fi
*
* Licensed under the License specified in the file LICENSE which is
* included with the source code.
* You may not use this file except in compliance with the License.
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/msv/GenericMsvValidator.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/DTDSchemaFactory.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/stax/WstxOutputFactory.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/msv/BaseSchemaFactory.java
*
 /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/DTDElement.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/DefaultAttrValue.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/DTDAttribute.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/msv/RelaxNGSchema.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/msv/RelaxNGSchemaFactory.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sw/NonNsStreamWriter.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/util/SymbolTable.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/stax/WstxInputFactory.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/DTDSubset.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/dtd/DTDId.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/sr/ValidatingStreamReader.java

* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/msv/W3CSchema.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/msv/W3CSchemaFactory.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/msv/AttributeProxy.java
*
/woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/evt/WstxEventReader.java
* /woodstox-core-asl-4-1-4-sources-jar/com/ctc/wstx/util/ElementIdMap.java

1.119 jersey-bean-validation 2.5.1

1.120 cxf-rt-frontend-jaxrs 2.7.3

1.120.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but

not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work,

where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and

may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this

License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache CXF
Copyright 2006-2013 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.121 jersey-media-jaxb 2.24.1

1.122 javax-el 2.2.4

1.123 swagger-springmvc 0.8.8

1.124 castor-xml 1.3.1

1.124.1 Available under license :

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Copyright 1999-2003 (C) Intalio Inc. All Rights Reserved.

Redistribution and use of this software and associated documentation
("Software"), with or without modification, are permitted provided
that the following conditions are met:

1. Redistributions of source code must retain copyright statements
and notices. Redistributions must also contain a copy of this
document.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

3. The name "ExoLab" must not be used to endorse or promote products
derived from this Software without prior written permission of
Intalio Inc. For written permission, please contact info@exolab.org.

4. Products derived from this Software may not be called "Castor"
nor may "Castor" appear in their names without prior written
permission of Intalio Inc. Exolab, Castor and
Intalio are
trademarks of Intalio Inc.

5. Due credit should be given to the ExoLab Project
(http://www.exolab.org/).

THIS SOFTWARE IS PROVIDED BY INTALIO AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL INTALIO OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.125 swagger-models 0.8.8

1.126 config 1.0.2

1.127 jersey-client 2.5.1

1.128 cxf-rt-transports-http 2.7.3

1.128.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise

designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any

risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache CXF
Copyright 2006-2013 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.129 javax-el-api 2.2.4

1.130 jersey-container-servlet-core 2.5.1

1.131 freemarker 2.3.23

1.132 jersey-media-multipart 2.5.1

1.133 cassandra-driver-core 2.1.0

1.134 jersey-common 2.24.1

1.135 cxf-rt-core 2.7.3

1.135.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions

to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the

content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache CXF
Copyright 2006-2013 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.136 jersey-server 2.5.1

1.137 cassandra-driver-mapping 2.1.0

1.138 jersey-guava 2.24.1

1.139 cglib-nodep 3.1

1.139.1 Available under license :

```
 ============================================================================
==  NOTICE file corresponding to the section 4 d of                ==
==  the Apache License, Version 2.0,                               ==
==  in this case for the Apache Ant distribution.                  ==
============================================================================
```

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

This product includes also software developed by :
- the W3C consortium (http://www.w3c.org) ,
- the SAX project (http://www.saxproject.org)

Please read the different LICENSE files present in the root directory of this distribution.

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

```
/*****************************************************************************
/* MessagesBundle.properties -- English language error messages
/*
/* Copyright (c) 1998 by William King (wrking@eng.sun.com) and
/*                    Aaron M. Renn (arenn@urbanophile.com)
/*
/* This program is free software; you can redistribute it and/or modify
/* it under the terms of the GNU Library General Public License as published
/* by  the Free Software Foundation; either version 2 of the License or
/* (at your option) any later version.
/*
/* This program is distributed in the hope that it will be useful, but
/* WITHOUT ANY WARRANTY; without even the implied warranty of
/* MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
/* GNU Library General Public License for more details.
/*
/* You should have received a copy of the GNU Library General Public License
/* along with this program; see the file COPYING.LIB.  If not, write to
/* the Free Software Foundation Inc., 59 Temple Place - Suite
 330,
/* Boston, MA  02111-1307 USA
/*****************************************************************************/
/*
*                              Apache License
*                        Version 2.0, January 2004
*                     http://www.apache.org/licenses/
*
*   TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION
*
*   1. Definitions.
*
*      "License" shall mean the terms and conditions for use, reproduction,
*      and distribution as defined by Sections 1 through 9 of this document.
*
*      "Licensor" shall mean the copyright owner or entity authorized by
*      the copyright owner that is granting the License.
*
*      "Legal Entity" shall mean the union of the acting entity and all
*      other entities that control, are controlled by, or are under common
*      control with that entity. For the purposes of this definition,
```

```
*      "control" means (i) the power, direct or indirect, to cause the
*      direction or management of such entity, whether by contract or
*      otherwise, or (ii) ownership of fifty percent (50%) or more of the
*
 outstanding shares, or (iii) beneficial ownership of such entity.
*
*      "You" (or "Your") shall mean an individual or Legal Entity
*      exercising permissions granted by this License.
*
*      "Source" form shall mean the preferred form for making modifications,
*      including but not limited to software source code, documentation
*      source, and configuration files.
*
*      "Object" form shall mean any form resulting from mechanical
*      transformation or translation of a Source form, including but
*      not limited to compiled object code, generated documentation,
*      and conversions to other media types.
*
*      "Work" shall mean the work of authorship, whether in Source or
*      Object form, made available under the License, as indicated by a
*      copyright notice that is included in or attached to the work
*      (an example is provided in the Appendix below).
*
*      "Derivative Works" shall mean any work, whether in Source or Object
*
    form, that is based on (or derived from) the Work and for which the
*      editorial revisions, annotations, elaborations, or other modifications
*      represent, as a whole, an original work of authorship. For the purposes
*      of this License, Derivative Works shall not include works that remain
*      separable from, or merely link (or bind by name) to the interfaces of,
*      the Work and Derivative Works thereof.
*
*      "Contribution" shall mean any work of authorship, including
*      the original version of the Work and any modifications or additions
*      to that Work or Derivative Works thereof, that is intentionally
*      submitted to Licensor for inclusion in the Work by the copyright owner
*      or by an individual or Legal Entity authorized to submit on behalf of
*      the copyright owner. For the purposes of this definition, "submitted"
*      means any form of electronic, verbal, or written communication sent
*      to the Licensor or its representatives,
 including but not limited to
*      communication on electronic mailing lists, source code control systems,
*      and issue tracking systems that are managed by, or on behalf of, the
*      Licensor for the purpose of discussing and improving the Work, but
*      excluding communication that is conspicuously marked or otherwise
*      designated in writing by the copyright owner as "Not a Contribution."
*
*      "Contributor" shall mean Licensor and any individual or Legal Entity
```

```
*      on behalf of whom a Contribution has been received by Licensor and
*      subsequently incorporated within the Work.
*
*    2. Grant of Copyright License. Subject to the terms and conditions of
*      this License, each Contributor hereby grants to You a perpetual,
*      worldwide, non-exclusive, no-charge, royalty-free, irrevocable
*      copyright license to reproduce, prepare Derivative Works of,
*      publicly display, publicly perform, sublicense, and distribute the
*
      Work and such Derivative Works in Source or Object form.
*
*    3. Grant of Patent License. Subject to the terms and conditions of
*      this License, each Contributor hereby grants to You a perpetual,
*      worldwide, non-exclusive, no-charge, royalty-free, irrevocable
*      (except as stated in this section) patent license to make, have made,
*      use, offer to sell, sell, import, and otherwise transfer the Work,
*      where such license applies only to those patent claims licensable
*      by such Contributor that are necessarily infringed by their
*      Contribution(s) alone or by combination of their Contribution(s)
*      with the Work to which such Contribution(s) was submitted. If You
*      institute patent litigation against any entity (including a
*      cross-claim or counterclaim in a lawsuit) alleging that the Work
*      or a Contribution incorporated within the Work constitutes direct
*      or contributory patent infringement, then any patent licenses
 *      granted to You under this License for that Work shall terminate
*      as of the date such litigation is filed.
*
*    4. Redistribution. You may reproduce and distribute copies of the
*      Work or Derivative Works thereof in any medium, with or without
*      modifications, and in Source or Object form, provided that You
*      meet the following conditions:
*
*      (a) You must give any other recipients of the Work or
*          Derivative Works a copy of this License; and
*
*      (b) You must cause any modified files to carry prominent notices
*          stating that You changed the files; and
*
*      (c) You must retain, in the Source form of any Derivative Works
*          that You distribute, all copyright, patent, trademark, and
*          attribution notices from the Source form of the Work,
*          excluding those notices that do not pertain to any part of
*          the Derivative Works; and
*
*      (d) If the Work includes a "NOTICE"
 text file as part of its
*          distribution, then any Derivative Works that You distribute must
*          include a readable copy of the attribution notices contained
```

* within such NOTICE file, excluding those notices that do not
* pertain to any part of the Derivative Works, in at least one
* of the following places: within a NOTICE text file distributed
* as part of the Derivative Works; within the Source form or
* documentation, if provided along with the Derivative Works; or,
* within a display generated by the Derivative Works, if and
* wherever such third-party notices normally appear. The contents
* of the NOTICE file are for informational purposes only and
* do not modify the License. You may add Your own attribution
* notices within Derivative Works that You distribute, alongside
* or as an addendum to the NOTICE text from the Work, provided
* that
such additional attribution notices cannot be construed
* as modifying the License.
*
* You may add Your own copyright statement to Your modifications and
* may provide additional or different license terms and conditions
* for use, reproduction, or distribution of Your modifications, or
* for any such Derivative Works as a whole, provided Your use,
* reproduction, and distribution of the Work otherwise complies with
* the conditions stated in this License.
*
* 5. Submission of Contributions. Unless You explicitly state otherwise,
* any Contribution intentionally submitted for inclusion in the Work
* by You to the Licensor shall be under the terms and conditions of
* this License, without any additional terms or conditions.
* Notwithstanding the above, nothing herein shall supersede or modify
* the terms of any separate license agreement you may have executed
* with Licensor regarding such Contributions.
*
* 6. Trademarks. This License does not grant permission to use the trade
* names, trademarks, service marks, or product names of the Licensor,
* except as required for reasonable and customary use in describing the
* origin of the Work and reproducing the content of the NOTICE file.
*
* 7. Disclaimer of Warranty. Unless required by applicable law or
* agreed to in writing, Licensor provides the Work (and each
* Contributor provides its Contributions) on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
* implied, including, without limitation, any warranties or conditions
* of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
* PARTICULAR PURPOSE. You are solely responsible for determining the
* appropriateness of using or redistributing the Work and assume any
* risks associated with Your exercise of permissions under this License.
*
* 8. Limitation of Liability.
In no event and under no legal theory,
* whether in tort (including negligence), contract, or otherwise,

```
*      unless required by applicable law (such as deliberate and grossly
*      negligent acts) or agreed to in writing, shall any Contributor be
*      liable to You for damages, including any direct, indirect, special,
*      incidental, or consequential damages of any character arising as a
*      result of this License or out of the use or inability to use the
*      Work (including but not limited to damages for loss of goodwill,
*      work stoppage, computer failure or malfunction, or any and all
*      other commercial damages or losses), even if such Contributor
*      has been advised of the possibility of such damages.
*
*    9. Accepting Warranty or Additional Liability. While redistributing
*      the Work or Derivative Works thereof, You may choose to offer,
*      and charge a fee for, acceptance of support, warranty, indemnity,
*      or other
 liability obligations and/or rights consistent with this
*      License. However, in accepting such obligations, You may act only
*      on Your own behalf and on Your sole responsibility, not on behalf
*      of any other Contributor, and only if You agree to indemnify,
*      defend, and hold each Contributor harmless for any liability
*      incurred by, or claims asserted against, such Contributor by reason
*      of your accepting any such warranty or additional liability.
*
*    END OF TERMS AND CONDITIONS
*
*    APPENDIX: How to apply the Apache License to your work.
*
*      To apply the Apache License to your work, attach the following
*      boilerplate notice, with the fields enclosed by brackets "[]"
*      replaced with your own identifying information. (Don't include
*      the brackets!)  The text should be enclosed in the appropriate
*      comment syntax for the file format. We also recommend that a
*      file or class name and description of purpose
 be included on the
*      same "printed page" as the copyright notice for easier
*      identification within third-party archives.
*
*    Copyright [yyyy] [name of copyright owner]
*
*    Licensed under the Apache License, Version 2.0 (the "License");
*    you may not use this file except in compliance with the License.
*    You may obtain a copy of the License at
*
*       http://www.apache.org/licenses/LICENSE-2.0
*
*    Unless required by applicable law or agreed to in writing, software
*    distributed under the License is distributed on an "AS IS" BASIS,
*    WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*    See the License for the specific language governing permissions and
```

* limitations under the License.
*/
ASM: a very small and fast Java bytecode manipulation framework
Copyright (c) 2000,2002,2003 INRIA, France Telecom
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. Neither the name of the copyright holders nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
THE POSSIBILITY OF SUCH DAMAGE.

1.140 cxf-rt-bindings-xml 2.7.3

1.140.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by

the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but

excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the

appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache CXF
Copyright 2006-2013 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.141 ant 1.7.1

1.142 jersey-server 2.24.1

1.143 snmp-4j 1.11

1.143.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - UsmSecurityStateReference.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):

*
/snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/UsmSecurityStateReference.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - MessageDispatcherImpl.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/MessageDispatcherImpl.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - CommonTimer.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/CommonTimer.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - SecurityLevel.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/SecurityLevel.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - Opaque.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/Opaque.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - OctetString.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/OctetString.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - TreeListener.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/TreeListener.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - Priv3DES.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/Priv3DES.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - TimeoutModel.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/TimeoutModel.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - AuthSHA.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/AuthSHA.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - TransportMapping.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/TransportMapping.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - StateReference.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/mp/StateReference.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - AssignableFromLong.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/AssignableFromLong.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - AssignableFromIntArray.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/AssignableFromIntArray.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - DefaultThreadFactory.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/DefaultThreadFactory.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - TimeTicks.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/TimeTicks.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - ThreadPool.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/ThreadPool.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - MPv1.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/mp/MPv1.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - AbstractSnmpUtility.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/AbstractSnmpUtility.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - ByteArrayWindow.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/ByteArrayWindow.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - TreeUtils.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/TreeUtils.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - DefaultPDUFactory.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/DefaultPDUFactory.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - LogControl.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/tools/console/LogControl.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - ScopedPDU.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/ScopedPDU.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - JavaLogAdapter.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/log/JavaLogAdapter.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - ThreadFactory.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/ThreadFactory.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - TreeEvent.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/TreeEvent.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - PrivAES192.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/PrivAES192.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - SnmpEngineEvent.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/event/SnmpEngineEvent.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - MutablePDU.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/MutablePDU.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - Integer32.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/Integer32.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - SecurityModel.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/SecurityModel.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - JavaLogFactory.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/log/JavaLogFactory.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - SNMP4JSettings.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/SNMP4JSettings.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - SecurityModels.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/SecurityModels.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - BitString.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/BitString.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - Null.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/Null.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - PrivacyProtocol.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/PrivacyProtocol.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - LogFactory.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/log/LogFactory.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - VariantVariableCallback.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
*
 /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/VariantVariableCallback.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - Counter64.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/Counter64.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - SecurityProtocols.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/SecurityProtocols.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - CounterSupport.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/mp/CounterSupport.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - SnmpRequest.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/tools/console/SnmpRequest.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - PrivDES.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/PrivDES.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - MutableStateReference.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/mp/MutableStateReference.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - TcpTransportMapping.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/transport/TcpTransportMapping.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - PduHandleCallback.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/mp/PduHandleCallback.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - UnsignedInteger32.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/UnsignedInteger32.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - AssignableFromInteger.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/AssignableFromInteger.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - CommandResponderEvent.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/CommandResponderEvent.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - BEROutputStream.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/asn1/BEROutputStream.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - Counter32.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/Counter32.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - CounterEvent.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/event/CounterEvent.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - OID.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/OID.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - UsmUserEvent.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/event/UsmUserEvent.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - EnumerationIterator.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/EnumerationIterator.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - Session.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/Session.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - Salt.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/Salt.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - WorkerTask.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/WorkerTask.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - PDU.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/PDU.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - TableUtils.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/TableUtils.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - MessageProcessingModel.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/mp/MessageProcessingModel.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - TransportMappings.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/transport/TransportMappings.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - DecryptParams.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/DecryptParams.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - ConsoleLogAdapter.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/log/ConsoleLogAdapter.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - RetrievalEvent.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/RetrievalEvent.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - Target.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/Target.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - SchedulerTask.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/SchedulerTask.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - VariantVariable.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/VariantVariable.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - MultiThreadedMessageDispatcher.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/MultiThreadedMessageDispatcher.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - GenericAddress.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/GenericAddress.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - PrivAES.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/PrivAES.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - SimpleVariableTextFormat.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/SimpleVariableTextFormat.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - User.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/User.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - TransportListener.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/transport/TransportListener.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - Log4jLogFactory.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/log/Log4jLogFactory.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - ResponseListener.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/event/ResponseListener.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - VersionInfo.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/version/VersionInfo.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - ArgumentParser.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/ArgumentParser.java
No license file was found, but licenses were detected in source scan.

```
/*_############################################################################
 _##
 _##  SNMP4J - TaskScheduler.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _############################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/TaskScheduler.java
No license file was found, but licenses were detected in source scan.

2004 Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _## Licensed under the Apache License, Version 2.0 (the "License");
 _## you may not use this file except in compliance with the License.
 _## You may obtain a copy of the License at
 _##
 _##   http://www.apache.org/licenses/LICENSE
2.0
 _##
 _## Unless required by applicable law or agreed to in writing, software
 _## distributed under the License is distributed on an "AS IS" BASIS,
 _## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _## See the License for the specific language governing permissions and
 _## limitations under the License.
 _##
 _##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/event/package.html
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/package.html
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/package.html
*
 /snmp4j-1-11-3-sources-2-jar/org/snmp4j/asn1/package.html
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/transport/package.html
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/mp/package.html
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/package.html
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/package.html
No license file was found, but licenses were detected in source scan.

/*_##
 _##
 _## SNMP4J - PrivAES128.java
 _##
 _## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _## Licensed under the Apache License, Version 2.0 (the "License");
 _## you may not use this file except in compliance with the License.
 _## You may obtain a copy of the License at
 _##
 _##   http://www.apache.org/licenses/LICENSE-2.0
 _##
 _## Unless required by applicable law or agreed to in writing, software
 _## distributed under the License is distributed on an "AS IS" BASIS,

```
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/PrivAES128.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - SecurityParameters.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/SecurityParameters.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - MessageLength.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
```

_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/transport/MessageLength.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - BERInputStream.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/asn1/BERInputStream.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - USM.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,

_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/USM.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - CounterListener.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/event/CounterListener.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - NoLogger.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,

_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/log/NoLogger.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - SecurityProtocol.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/SecurityProtocol.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - ReadonlyVariableCallback.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,

```
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):

```
*
 /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/ReadonlyVariableCallback.java
```

No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - UdpTransportMapping.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):

```
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/transport/UdpTransportMapping.java
```

No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - UsmUserListener.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
```

_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/event/UsmUserListener.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - AbstractVariable.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/AbstractVariable.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - MessageException.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software

```
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/MessageException.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - DefaultTcpTransportMapping.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/transport/DefaultTcpTransportMapping.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - SnmpConstants.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
```

_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/mp/SnmpConstants.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - WorkerPool.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/WorkerPool.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - Snmp.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software

```
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/Snmp.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - BERSerializable.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/asn1/BERSerializable.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - VariableTextFormat.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
```

_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/VariableTextFormat.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - AbstractTransportMapping.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
*
/snmp4j-1-11-3-sources-2-jar/org/snmp4j/transport/AbstractTransportMapping.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - VariableBinding.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##

_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/VariableBinding.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - MPv2c.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/mp/MPv2c.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - AuthMD5.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##

```
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/AuthMD5.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - PduHandle.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/mp/PduHandle.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - UnsupportedAddressClassException.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
```

_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_###*/

Found in path(s):
*
/snmp4j-1-11-3-sources-2-jar/org/snmp4j/transport/UnsupportedAddressClassException.java
No license file was found, but licenses were detected in source scan.

/*_###
_##
_## SNMP4J - TransportIpAddress.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_###*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/TransportIpAddress.java
No license file was found, but licenses were detected in source scan.

/*_###
_##
_## SNMP4J - OIDTextFormat.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0

```
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/OIDTextFormat.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - SecurityStateReference.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
*
 /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/SecurityStateReference.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - LogAdapter.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
```

```
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/log/LogAdapter.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - SMIConstants.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/SMIConstants.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - MessageLengthDecoder.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
```

```
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/transport/MessageLengthDecoder.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - Gauge32.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/Gauge32.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - UsmTimeTable.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
```

```
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/UsmTimeTable.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - UsmUser.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/UsmUser.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - AuthenticationFailureEvent.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
```

```
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/event/AuthenticationFailureEvent.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - MPv3.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/mp/MPv3.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - AuthenticationFailureListener.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
```

```
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/event/AuthenticationFailureListener.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - DefaultCounterListener.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
*
 /snmp4j-1-11-3-sources-2-jar/org/snmp4j/mp/DefaultCounterListener.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - BER.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
```

```
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/asn1/BER.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - SecureTarget.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/SecureTarget.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - TcpAddress.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
```

```
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/TcpAddress.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - SimpleOIDTextFormat.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/SimpleOIDTextFormat.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - DefaultTimerFactory.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
```

```
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/DefaultTimerFactory.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - AssignableFromByteArray.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
*
 /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/AssignableFromByteArray.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - MessageDispatcher.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
```

```
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/MessageDispatcher.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - SMIAddress.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/SMIAddress.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - UsmSecurityParameters.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
```

```
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/UsmSecurityParameters.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - TableEvent.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/TableEvent.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - ResponseEvent.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
```

_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/event/ResponseEvent.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - TransportStateListener.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
*
/snmp4j-1-11-3-sources-2-jar/org/snmp4j/transport/TransportStateListener.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - Address.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");

```
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/Address.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - UsmTimeEntry.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/UsmTimeEntry.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - CommunityTarget.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
```

```
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/CommunityTarget.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - TimerFactory.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/TimerFactory.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - DefaultTimeoutModel.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
```

```
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/DefaultTimeoutModel.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - MultiThreadedTrapReceiver.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
*
 /snmp4j-1-11-3-sources-2-jar/org/snmp4j/test/MultiThreadedTrapReceiver.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - StatusInformation.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
```

```
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/mp/StatusInformation.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - Log4jLogAdapter.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/log/Log4jLogAdapter.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - Variable.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
```

```
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/Variable.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - AssignableFromString.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/AssignableFromString.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - UserTarget.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
```

```
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/UserTarget.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - UsmUserTable.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/UsmUserTable.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - LogLevel.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
```

```
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/log/LogLevel.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - UdpAddress.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/UdpAddress.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - TransportStateEvent.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
```

```
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/transport/TransportStateEvent.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - SnmpConfigurator.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/SnmpConfigurator.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - UsmUserEntry.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
```

```
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##     http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/UsmUserEntry.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - AbstractTarget.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##     http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/AbstractTarget.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - PrivAES256.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
```

```
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/PrivAES256.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - LogProxy.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/log/LogProxy.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - CommandResponder.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
```

```
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/CommandResponder.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - PDUFactory.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/PDUFactory.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - AuthGeneric.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
```

```
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##     http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/AuthGeneric.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - AuthenticationProtocol.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##     http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
*
 /snmp4j-1-11-3-sources-2-jar/org/snmp4j/security/AuthenticationProtocol.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - PDUv1.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
```

```
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/PDUv1.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - IpAddress.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/smi/IpAddress.java
No license file was found, but licenses were detected in source scan.

```
/*_########################################################################
 _##
 _##  SNMP4J - SnmpEngineListener.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
```

```
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/event/SnmpEngineListener.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - ConsoleLogFactory.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
 _##
 _##  Licensed under the Apache License, Version 2.0 (the "License");
 _##  you may not use this file except in compliance with the License.
 _##  You may obtain a copy of the License at
 _##
 _##      http://www.apache.org/licenses/LICENSE-2.0
 _##
 _##  Unless required by applicable law or agreed to in writing, software
 _##  distributed under the License is distributed on an "AS IS" BASIS,
 _##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 _##  See the License for the specific language governing permissions and
 _##  limitations under the License.
 _##
 _##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/log/ConsoleLogFactory.java
No license file was found, but licenses were detected in source scan.

```
/*_##########################################################################
 _##
 _##  SNMP4J - ConnectionOrientedTransportMapping.java
 _##
 _##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
```

_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in
path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/transport/ConnectionOrientedTransportMapping.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - TableListener.java
_##
_## Copyright (C) 2003-2009 Frank Fock and Jochen Katz (SNMP4J.org)
_##
_## Licensed under the Apache License, Version 2.0 (the "License");
_## you may not use this file except in compliance with the License.
_## You may obtain a copy of the License at
_##
_## http://www.apache.org/licenses/LICENSE-2.0
_##
_## Unless required by applicable law or agreed to in writing, software
_## distributed under the License is distributed on an "AS IS" BASIS,
_## WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_## See the License for the specific language governing permissions and
_## limitations under the License.
_##
_##*/

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/util/TableListener.java
No license file was found, but licenses were detected in source scan.

/*_##
_##
_## SNMP4J - DefaultUdpTransportMapping.java
_##

```
_##  Copyright (C) 2003-2009  Frank Fock and Jochen Katz (SNMP4J.org)
_##
_##  Licensed under the Apache License, Version 2.0 (the "License");
_##  you may not use this file except in compliance with the License.
_##  You may obtain a copy of the License at
_##
_##      http://www.apache.org/licenses/LICENSE-2.0
_##
_##  Unless required by applicable law or agreed to in writing, software
_##  distributed under the License is distributed on an "AS IS" BASIS,
_##  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
_##  See the License for the specific language governing permissions and
_##  limitations under the License.
_##
_##########################################################################*/
```

Found in path(s):
* /snmp4j-1-11-3-sources-2-jar/org/snmp4j/transport/DefaultUdpTransportMapping.java

1.144 gson 2.2.3

1.145 jersey-client 2.24.1

1.146 jersey-common 2.5.1

1.147 jersey-container-servlet 2.5.1

1.148 cxf-api 2.7.3

1.148.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner

or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices

stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache CXF
Copyright 2006-2013 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.149 avro 1.7.5

1.149.1 Available under license :

Apache Avro
Copyright 2009-2013 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the

direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding

those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise,

unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.150 ant-launcher 1.7.1

1.150.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form
shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely
link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the

Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean
Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and

You must cause any modified files to carry prominent notices stating that You changed the files; and

You must retain, in the Source form of any Derivative Works that You distribute,
all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum
to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.
You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use
the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor
harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.151 jetty-http-spi 9.3.27.v20190418

1.152 websocket-servlet 9.3.27.v20190418

1.153 websocket-common 9.3.27.v20190418

1.154 websocket-api 9.3.27.v20190418

1.155 websocket-client 9.3.27.v20190418

1.156 websocket-server 9.3.27.v20190418

1.157 java-concurrent-hash-trie-map 0.2.23

1.158 xstream 1.2.2

1.159 hibernatejpa2.0api 1.0.1.Final

1.159.1 Available under license :

Eclipse Distribution License - v 1.0

Copyright (c) 2007, Eclipse Foundation, Inc. and its licensors.

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
Neither the name of the Eclipse Foundation, Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.
THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.160 profiler 1.0.2

1.161 swagger-annotations 1.5.22

1.161.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the
preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name)
to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the

Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual
or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination
of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and
You must cause any modified files to carry prominent notices stating that You changed the files; and
You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that
such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works

as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.
5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any
Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims
asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

```
/**
* Copyright 2016 SmartBear Software
* <p>
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* <p>
* http://www.apache.org/licenses/LICENSE-2.0
* <p>
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
```

```
*/

package io.swagger.annotations;

import java.lang.annotation.ElementType;
import java.lang.annotation.Retention;
import java.lang.annotation.RetentionPolicy;
import java.lang.annotation.Target;

/**
* License metadata available within the info section of a Swagger definition, see
* https://github.com/OAI/OpenAPI-Specification/blob/master/versions/2.0.md#licenseObject
*
* @since 1.5.0
 */

@Target(ElementType.ANNOTATION_TYPE)
@Retention(RetentionPolicy.RUNTIME)
public @interface License {

  /**
   * The name of the license.
   *
   * @return the name of the license
   */
  String name();

  /**
   * An optional URL for the license.
   *
   * @return an optional URL for the license.
   */
  String url() default "";
}
```

1.162 jedis 2.10.2

1.163 jetty-xml 9.4.18.v20190429

1.163.1 Available under license :

This program and the accompanying materials are made available under the terms of the Eclipse Public License 2.0 which is available at http://www.eclipse.org/legal/epl-2.0, or the Apache Software License 2.0 which is available at https://www.apache.org/licenses/LICENSE-2.0.

Eclipse Public License - v 1.0

THE ACCOMPANYING PROGRAM IS PROVIDED UNDER THE TERMS OF THIS ECLIPSE PUBLIC LICENSE ("AGREEMENT"). ANY USE, REPRODUCTION OR DISTRIBUTION OF THE PROGRAM CONSTITUTES RECIPIENT'S ACCEPTANCE OF THIS AGREEMENT.

1. DEFINITIONS

"Contribution" means:

a) in the case of the initial Contributor, the initial code and documentation distributed under this Agreement, and
b) in the case of each subsequent Contributor:
i) changes to the Program, and
ii) additions to the Program;

where such changes and/or additions to the Program originate from and are distributed by that particular Contributor. A Contribution 'originates' from a Contributor if it was added to the Program by such Contributor itself or anyone acting on such Contributor's behalf. Contributions do not include additions to the Program which: (i) are separate modules of software distributed in conjunction with the Program under their own license agreement, and (ii) are not derivative works of the Program.

"Contributor" means any person or entity that distributes the Program.

"Licensed Patents" mean patent claims licensable by a Contributor which are necessarily infringed by the use or sale of its Contribution alone or when combined with the Program.

"Program" means the Contributions distributed in accordance with this Agreement.

"Recipient" means anyone who receives the Program under this Agreement, including all Contributors.

2. GRANT OF RIGHTS
a) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free copyright license to reproduce, prepare derivative works of, publicly display, publicly perform, distribute and sublicense the Contribution of such Contributor, if any, and such derivative works, in source code and object code form.
b) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free patent license under

Licensed Patents to make, use, sell, offer to sell, import and otherwise transfer the Contribution of such Contributor, if any, in source code and object code form. This patent license shall apply to the combination of the Contribution and the Program if, at the time the Contribution is added by the Contributor, such addition of the Contribution causes such combination to be covered by the Licensed Patents. The patent license shall not apply to any other combinations which include the Contribution. No hardware per se is licensed hereunder.

c) Recipient understands that although each Contributor grants the licenses to its Contributions set forth herein,

no assurances are provided by any

Contributor that the Program does not infringe the patent or other intellectual property rights of any other entity. Each Contributor disclaims any liability to Recipient for claims brought by any other entity based on infringement of intellectual property rights or otherwise. As a condition to exercising the rights and licenses granted hereunder, each Recipient hereby assumes sole responsibility to secure any other intellectual property rights needed, if any. For example, if a third party patent license is required to allow Recipient to distribute the Program, it is Recipient's responsibility to acquire that license before distributing the Program.

d) Each Contributor represents that to its knowledge it has sufficient copyright rights in its Contribution, if any, to grant the copyright license set forth in this Agreement.

3. REQUIREMENTS

A Contributor may choose to distribute the Program

in object code form under

its own license agreement, provided that:

a) it complies with the terms and conditions of this Agreement; and

b) its license agreement:

i) effectively disclaims on behalf of all Contributors all warranties and conditions, express and implied, including warranties or conditions of title and non-infringement, and implied warranties or conditions of merchantability and fitness for a particular purpose;

ii) effectively excludes on behalf of all Contributors all liability for damages, including direct, indirect, special, incidental and consequential damages, such as lost profits;

iii) states that any provisions which differ from this Agreement are offered by that Contributor alone and not by any other party; and

iv) states that source code for the Program is available from such Contributor, and informs licensees how to obtain it in a reasonable manner on or through a

medium customarily used for software exchange.

When the Program is made available in source code form:

a) it must be made available under this Agreement; and
b) a copy of this Agreement must be included with each copy of the Program.
Contributors may not remove or alter any copyright notices contained
within the Program.

Each Contributor must identify itself as the originator of its Contribution,
if
any, in a manner that reasonably allows subsequent Recipients to identify the
originator of the Contribution.

4. COMMERCIAL DISTRIBUTION

Commercial distributors of software may accept certain responsibilities with
respect to end users, business partners and the like. While this license is
intended to facilitate the commercial use of the Program, the Contributor who
includes the Program in a commercial product offering should do so in a manner
which does not create potential liability for other Contributors. Therefore,
if a Contributor includes the Program in a commercial
product offering, such
Contributor ("Commercial Contributor") hereby agrees to defend and indemnify
every other Contributor ("Indemnified Contributor") against any losses,
damages and costs (collectively "Losses") arising from claims, lawsuits and
other legal actions brought by a third party against the Indemnified
Contributor to the extent caused by the acts or omissions of such Commercial
Contributor in connection with its distribution of the Program in a commercial
product offering. The obligations in this section do not apply to any claims
or Losses relating to any actual or alleged intellectual property
infringement. In order to qualify, an Indemnified Contributor must:
a) promptly notify the Commercial Contributor in writing of such claim, and
b) allow the Commercial Contributor to control, and cooperate with the
Commercial Contributor in, the defense and any related settlement
negotiations. The Indemnified Contributor may participate in any such claim at
its own expense.

For example,
a Contributor might include the Program in a commercial product
offering, Product X. That Contributor is then a Commercial Contributor. If
that Commercial Contributor then makes performance claims, or offers
warranties related to Product X, those performance claims and warranties are
such Commercial Contributor's responsibility alone. Under this section, the
Commercial Contributor would have to defend claims against the other
Contributors related to those performance claims and warranties, and if a
court requires any other Contributor to pay any damages as a result, the
Commercial Contributor must pay those damages.

5. NO WARRANTY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, THE PROGRAM IS PROVIDED ON AN "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, EITHER EXPRESS OR IMPLIED INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OR CONDITIONS OF TITLE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each Recipient is solely responsible for determining
the appropriateness of using
and distributing the Program and assumes all risks associated with its exercise of rights under this Agreement , including but not limited to the risks and costs of program errors, compliance with applicable laws, damage to or loss of data, programs or equipment, and unavailability or interruption of operations.

6. DISCLAIMER OF LIABILITY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, NEITHER RECIPIENT NOR ANY CONTRIBUTORS SHALL HAVE ANY LIABILITY FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION LOST PROFITS), HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OR DISTRIBUTION OF THE PROGRAM OR THE EXERCISE OF ANY RIGHTS GRANTED HEREUNDER, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. GENERAL

If any provision of this Agreement is invalid or unenforceable under applicable
law, it shall not affect the validity or enforceability of the remainder of the terms of this Agreement, and without further action by the parties hereto, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

If Recipient institutes patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Program itself (excluding combinations of the Program with other software or hardware) infringes such Recipient's patent(s), then such Recipient's rights granted under Section 2(b) shall terminate as of the date such litigation is filed.

All Recipient's rights under this Agreement shall terminate if it fails to comply with any of the material terms or conditions of this Agreement and does not cure such failure in a reasonable period of time after becoming aware of such noncompliance. If all Recipient's rights under this Agreement terminate, Recipient agrees to cease use and distribution
of the Program as soon as
reasonably practicable. However, Recipient's obligations under this Agreement and any licenses granted by Recipient relating to the Program shall continue and survive.

Everyone is permitted to copy and distribute copies of this Agreement, but in order to avoid inconsistency the Agreement is copyrighted and may only be modified in the following manner. The Agreement Steward reserves the right to publish new versions (including revisions) of this Agreement from time to time. No one other than the Agreement Steward has the right to modify this Agreement. The Eclipse Foundation is the initial Agreement Steward. The Eclipse Foundation may assign the responsibility to serve as the Agreement Steward to a suitable separate entity. Each new version of the Agreement will be given a distinguishing version number. The Program (including Contributions) may always be distributed subject to the version of the Agreement under which it was received. In addition, after
a new version of the
Agreement is published, Contributor may elect to distribute the Program (including its Contributions) under the new version. Except as expressly stated in Sections 2(a) and 2(b) above, Recipient receives no rights or licenses to the intellectual property of any Contributor under this Agreement, whether expressly, by implication, estoppel or otherwise. All rights in the Program not expressly granted under this Agreement are reserved.

This Agreement is governed by the laws of the State of New York and the intellectual property laws of the United States of America. No party to this Agreement will bring a legal action under this Agreement more than one year after the cause of action arose. Each party waives its rights to a jury trial in any resulting litigation.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the

outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works
that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously
marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of

this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative

Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions)
on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a

result of this License or out of the use or inability to use the
Work (including but not limited
to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache
License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS
OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
==========
Jetty Web Container

Copyright 1995-2018 Mort Bay Consulting Pty Ltd.
==========

The Jetty Web Container is Copyright Mort Bay Consulting Pty Ltd
unless otherwise noted.

Jetty is dual licensed under both

 * The Apache 2.0 License
   http://www.apache.org/licenses/LICENSE-2.0.html

     and

 * The Eclipse Public 1.0 License
   http://www.eclipse.org/legal/epl-v10.html

Jetty may be distributed under either license.

Eclipse

The following artifacts are EPL.
* org.eclipse.jetty.orbit:org.eclipse.jdt.core

The following artifacts are EPL and ASL2.
* org.eclipse.jetty.orbit:javax.security.auth.message

The following artifacts are EPL and CDDL 1.0.
* org.eclipse.jetty.orbit:javax.mail.glassfish

Oracle

The following artifacts are CDDL + GPLv2 with classpath exception.
https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

* javax.servlet:javax.servlet-api
 * javax.annotation:javax.annotation-api
* javax.transaction:javax.transaction-api
* javax.websocket:javax.websocket-api

Oracle OpenJDK

If ALPN is used to negotiate HTTP/2 connections, then the following
artifacts may be included in the distribution or downloaded when ALPN

module is selected.

* java.sun.security.ssl

These artifacts replace/modify OpenJDK classes. The modifications
are hosted at github and both modified and original are under GPL v2 with
classpath exceptions.
http://openjdk.java.net/legal/gplv2+ce.html

OW2

The following artifacts are licensed by the OW2 Foundation according to the
terms of http://asm.ow2.org/license.html

org.ow2.asm:asm-commons
org.ow2.asm:asm

Apache

The following artifacts are ASL2 licensed.

org.apache.taglibs:taglibs-standard-spec
org.apache.taglibs:taglibs-standard-impl

MortBay

The following artifacts are ASL2 licensed. Based on selected classes from
following Apache Tomcat jars, all ASL2
 licensed.

org.mortbay.jasper:apache-jsp
 org.apache.tomcat:tomcat-jasper
 org.apache.tomcat:tomcat-juli
 org.apache.tomcat:tomcat-jsp-api
 org.apache.tomcat:tomcat-el-api
 org.apache.tomcat:tomcat-jasper-el
 org.apache.tomcat:tomcat-api
 org.apache.tomcat:tomcat-util-scan
 org.apache.tomcat:tomcat-util

org.mortbay.jasper:apache-el
 org.apache.tomcat:tomcat-jasper-el

org.apache.tomcat:tomcat-el-api

Mortbay

The following artifacts are CDDL + GPLv2 with classpath exception.

https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

org.eclipse.jetty.toolchain:jetty-schemas

Assorted

The UnixCrypt.java code implements the one way cryptography used by
Unix systems for simple password protection. Copyright 1996 Aki Yoshida,
modified April 2001 by Iris Van den Broeke, Daniel Deville.
Permission to use, copy, modify and distribute UnixCrypt
for non-commercial or commercial purposes and without fee is
granted provided that the copyright notice appears in all
copies.

1.164 jetty-continuation 9.4.18.v20190429

1.164.1 Available under license :

This program and the accompanying materials are made available under the
terms of the Eclipse Public License 2.0 which is available at
http://www.eclipse.org/legal/epl-2.0, or the Apache Software License
2.0 which is available at https://www.apache.org/licenses/LICENSE-2.0.

Eclipse Public License - v 1.0

THE ACCOMPANYING PROGRAM IS PROVIDED UNDER THE TERMS OF THIS ECLIPSE PUBLIC LICENSE ("AGREEMENT"). ANY USE, REPRODUCTION OR DISTRIBUTION OF THE PROGRAM CONSTITUTES RECIPIENT'S ACCEPTANCE OF THIS AGREEMENT.

1. DEFINITIONS

"Contribution" means:

a) in the case of the initial Contributor, the initial code and documentation
  distributed under this Agreement, and
b) in the case of each subsequent Contributor:
  i) changes to the Program, and

ii) additions to the Program;

where such changes and/or additions to the Program originate from and are distributed by that particular Contributor. A Contribution 'originates' from a Contributor if it was added to the Program by such Contributor itself or anyone acting on such Contributor's behalf. Contributions do not include additions to the Program which: (i) are separate modules of software distributed in conjunction with the Program under their own license agreement, and (ii) are not derivative works of the Program.

"Contributor" means any person or entity that distributes the Program.

"Licensed Patents" mean patent claims licensable by a Contributor which are necessarily infringed by the use or sale of its Contribution alone or when combined with the Program.

"Program" means the Contributions distributed in accordance with this Agreement.

"Recipient" means anyone who receives the Program under this Agreement, including all Contributors.

2. GRANT OF RIGHTS

a) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free copyright license to reproduce, prepare derivative works of, publicly display, publicly perform, distribute and sublicense the Contribution of such Contributor, if any, and such derivative works, in source code and object code form.

b) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free patent license under Licensed Patents to make, use, sell, offer to sell, import and otherwise transfer the Contribution of such Contributor, if any, in source code and object code form. This patent license shall apply to the combination of the Contribution and the Program if, at the time the Contribution is added by the Contributor, such addition of the Contribution causes such combination to be covered by the Licensed Patents. The patent license shall not apply to any other combinations which include the Contribution. No hardware per se is licensed hereunder.

c) Recipient understands that although each Contributor grants the licenses to its Contributions set forth herein, no assurances are provided by any Contributor that the Program does not infringe the patent or other intellectual property rights of any other entity. Each Contributor disclaims any liability to Recipient for claims brought by any other entity based on infringement of intellectual property rights or otherwise. As a condition to exercising the rights and licenses granted

hereunder, each Recipient hereby assumes sole responsibility to secure any other intellectual property rights needed, if any. For example, if a third party patent license is required to allow Recipient to distribute the Program, it is Recipient's responsibility to acquire that license before distributing the Program.

d) Each Contributor represents that to its knowledge it has sufficient copyright rights in its Contribution, if any, to grant the copyright license set forth in this Agreement.

3. REQUIREMENTS

A Contributor may choose to distribute the Program in object code form under its own license agreement, provided that:

a) it complies with the terms and conditions of this Agreement; and

b) its license agreement:

i) effectively disclaims on behalf of all Contributors all warranties and conditions, express and implied, including warranties or conditions of title and non-infringement, and implied warranties or conditions of merchantability and fitness for a particular purpose;

ii) effectively excludes on behalf of all Contributors all liability for damages, including direct, indirect, special, incidental and consequential damages, such as lost profits;

iii) states that any provisions which differ from this Agreement are offered by that Contributor alone and not by any other party; and

iv) states that source code for the Program is available from such Contributor, and informs licensees how to obtain it in a reasonable manner on or through a medium customarily used for software exchange.

When the Program is made available in source code form:

a) it must be made available under this Agreement; and

b) a copy of this Agreement must be included with each copy of the Program. Contributors may not remove or alter any copyright notices contained within the Program.

Each Contributor must identify itself as the originator of its Contribution, if any, in a manner that reasonably allows subsequent Recipients to identify the originator of the Contribution.

4. COMMERCIAL DISTRIBUTION

Commercial distributors of software may accept certain responsibilities with respect to end users, business partners and the like. While this license is intended to facilitate the commercial use of the Program, the Contributor who

includes the Program in a commercial product offering should do so in a manner which does not create potential liability for other Contributors. Therefore, if a Contributor includes the Program in a commercial product offering, such Contributor ("Commercial Contributor") hereby agrees to defend and indemnify every other Contributor ("Indemnified Contributor") against any losses, damages and costs (collectively "Losses") arising from claims, lawsuits and other legal actions brought by a third party against the Indemnified Contributor to the extent caused by the acts or omissions of such Commercial Contributor in connection with its distribution of the Program in a commercial product offering. The obligations in this section do not apply to any claims or Losses relating to any actual or alleged intellectual property infringement. In order to qualify, an Indemnified Contributor must:
a) promptly notify the Commercial Contributor in writing of such claim, and
b) allow the Commercial Contributor to control, and cooperate with the Commercial Contributor in, the defense and any related settlement negotiations. The Indemnified Contributor may participate in any such claim at its own expense.

For example, a Contributor might include the Program in a commercial product offering, Product X. That Contributor is then a Commercial Contributor. If that Commercial Contributor then makes performance claims, or offers warranties related to Product X, those performance claims and warranties are such Commercial Contributor's responsibility alone. Under this section, the Commercial Contributor would have to defend claims against the other Contributors related to those performance claims and warranties, and if a court requires any other Contributor to pay any damages as a result, the Commercial Contributor must pay those damages.

5. NO WARRANTY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, THE PROGRAM IS PROVIDED ON AN "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, EITHER EXPRESS OR IMPLIED INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OR CONDITIONS OF TITLE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each Recipient is solely responsible for determining the appropriateness of using and distributing the Program and assumes all risks associated with its exercise of rights under this Agreement , including but not limited to the risks and costs of program errors, compliance with applicable laws, damage to or loss of data, programs or equipment, and unavailability or interruption of operations.

6. DISCLAIMER OF LIABILITY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, NEITHER RECIPIENT NOR ANY CONTRIBUTORS SHALL HAVE ANY LIABILITY FOR ANY DIRECT, INDIRECT, INCIDENTAL,

SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION LOST PROFITS), HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OR DISTRIBUTION OF THE PROGRAM OR THE EXERCISE OF ANY RIGHTS GRANTED HEREUNDER, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. GENERAL

If any provision of this Agreement is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this Agreement, and without further action by the parties hereto, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

If Recipient institutes patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Program itself (excluding combinations of the Program with other software or hardware) infringes such Recipient's patent(s), then such Recipient's rights granted under Section 2(b) shall terminate as of the date such litigation is filed.

All Recipient's rights under this Agreement shall terminate if it fails to comply with any of the material terms or conditions of this Agreement and does not cure such failure in a reasonable period of time after becoming aware of such noncompliance. If all Recipient's rights under this Agreement terminate, Recipient agrees to cease use and distribution of the Program as soon as reasonably practicable. However, Recipient's obligations under this Agreement and any licenses granted by Recipient relating to the Program shall continue and survive.

Everyone is permitted to copy and distribute copies of this Agreement, but in order to avoid inconsistency the Agreement is copyrighted and may only be modified in the following manner. The Agreement Steward reserves the right to publish new versions (including revisions) of this Agreement from time to time. No one other than the Agreement Steward has the right to modify this Agreement. The Eclipse Foundation is the initial Agreement Steward. The Eclipse Foundation may assign the responsibility to serve as the Agreement Steward to a suitable separate entity. Each new version of the Agreement will be given a distinguishing version number. The Program (including Contributions) may always be distributed subject to the version of the Agreement under which it was received. In addition, after a new version of the Agreement is published, Contributor may elect to distribute the Program (including its Contributions) under the new version. Except as expressly stated in Sections 2(a) and 2(b) above, Recipient receives no rights or licenses to the intellectual property of any Contributor under this Agreement,

whether expressly, by implication, estoppel or otherwise. All rights in the Program not expressly granted under this Agreement are reserved.

This Agreement is governed by the laws of the State of New York and the intellectual property laws of the United States of America. No party to this Agreement will bring a legal action under this Agreement more than one year after the cause of action arose. Each party waives its rights to a jury trial in any resulting litigation.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a

copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works
that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously
marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a

cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative
Works; within the Source form or
documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with

the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions)
on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited
to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason

of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache
License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS
OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

==========

Jetty Web Container
Copyright 1995-2018 Mort Bay Consulting Pty Ltd.

==========

The Jetty Web Container is Copyright Mort Bay Consulting Pty Ltd
unless otherwise noted.

Jetty is dual licensed under both

* The Apache 2.0 License
http://www.apache.org/licenses/LICENSE-2.0.html

and

* The Eclipse Public 1.0 License
http://www.eclipse.org/legal/epl-v10.html

Jetty may be distributed under either license.

Eclipse

The following artifacts are EPL.
* org.eclipse.jetty.orbit:org.eclipse.jdt.core

The following artifacts are EPL and ASL2.
* org.eclipse.jetty.orbit:javax.security.auth.message

The following artifacts are EPL and CDDL 1.0.
* org.eclipse.jetty.orbit:javax.mail.glassfish

Oracle

The following artifacts are CDDL + GPLv2 with classpath exception.
https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

* javax.servlet:javax.servlet-api
 * javax.annotation:javax.annotation-api
* javax.transaction:javax.transaction-api
* javax.websocket:javax.websocket-api

Oracle OpenJDK

If ALPN is used to negotiate HTTP/2 connections, then the following
artifacts may be included in the distribution or downloaded when ALPN
module is selected.

* java.sun.security.ssl

These artifacts replace/modify OpenJDK classes. The modifications
are hosted at github and both modified and original are under GPL v2 with
classpath exceptions.
http://openjdk.java.net/legal/gplv2+ce.html

OW2

The following artifacts are licensed by the OW2 Foundation according to the
terms of http://asm.ow2.org/license.html

org.ow2.asm:asm-commons
org.ow2.asm:asm

Apache

The following artifacts are ASL2 licensed.

org.apache.taglibs:taglibs-standard-spec
org.apache.taglibs:taglibs-standard-impl

MortBay

The following artifacts are ASL2 licensed. Based on selected classes from
following Apache Tomcat jars, all ASL2
 licensed.

org.mortbay.jasper:apache-jsp
 org.apache.tomcat:tomcat-jasper
 org.apache.tomcat:tomcat-juli
 org.apache.tomcat:tomcat-jsp-api
 org.apache.tomcat:tomcat-el-api
 org.apache.tomcat:tomcat-jasper-el
 org.apache.tomcat:tomcat-api
 org.apache.tomcat:tomcat-util-scan
 org.apache.tomcat:tomcat-util

org.mortbay.jasper:apache-el
 org.apache.tomcat:tomcat-jasper-el
 org.apache.tomcat:tomcat-el-api

Mortbay

The following artifacts are CDDL + GPLv2 with classpath exception.

https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

org.eclipse.jetty.toolchain:jetty-schemas

Assorted

The UnixCrypt.java code implements the one way cryptography used by

Unix systems for simple password protection. Copyright 1996 Aki Yoshida,
modified April 2001 by Iris Van den Broeke, Daniel Deville.
Permission to use, copy, modify and distribute UnixCrypt
for non-commercial or commercial purposes and without fee is
granted provided that the copyright notice appears in all
copies.

1.165 jetty-webapp 9.4.18.v20190429

1.165.1 Available under license :

This program and the accompanying materials are made available under the
terms of the Eclipse Public License 2.0 which is available at
http://www.eclipse.org/legal/epl-2.0, or the Apache Software License
2.0 which is available at https://www.apache.org/licenses/LICENSE-2.0.

Eclipse Public License - v 1.0

THE ACCOMPANYING PROGRAM IS PROVIDED UNDER THE TERMS OF THIS ECLIPSE PUBLIC LICENSE ("AGREEMENT"). ANY USE, REPRODUCTION OR DISTRIBUTION OF THE PROGRAM CONSTITUTES RECIPIENT'S ACCEPTANCE OF THIS AGREEMENT.

1. DEFINITIONS

"Contribution" means:

a) in the case of the initial Contributor, the initial code and documentation
  distributed under this Agreement, and
b) in the case of each subsequent Contributor:
   i) changes to the Program, and
  ii) additions to the Program;

  where such changes and/or additions to the Program originate from and are
  distributed by that particular Contributor. A Contribution 'originates'
  from a Contributor if it was added to the Program by such
 Contributor
  itself or anyone acting on such Contributor's behalf. Contributions do not
  include additions to the Program which: (i) are separate modules of
  software distributed in conjunction with the Program under their own
  license agreement, and (ii) are not derivative works of the Program.

"Contributor" means any person or entity that distributes the Program.

"Licensed Patents" mean patent claims licensable by a Contributor which are
necessarily infringed by the use or sale of its Contribution alone or when
combined with the Program.

"Program" means the Contributions distributed in accordance with this Agreement.

"Recipient" means anyone who receives the Program under this Agreement, including all Contributors.

2. GRANT OF RIGHTS

a) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free copyright license to reproduce, prepare derivative works of, publicly display, publicly perform,
distribute and sublicense the Contribution of such Contributor, if any, and such derivative works, in source code and object code form.

b) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free patent license under Licensed Patents to make, use, sell, offer to sell, import and otherwise transfer the Contribution of such Contributor, if any, in source code and object code form. This patent license shall apply to the combination of the Contribution and the Program if, at the time the Contribution is added by the Contributor, such addition of the Contribution causes such combination to be covered by the Licensed Patents. The patent license shall not apply to any other combinations which include the Contribution. No hardware per se is licensed hereunder.

c) Recipient understands that although each Contributor grants the licenses to its Contributions set forth herein,
no assurances are provided by any
Contributor that the Program does not infringe the patent or other intellectual property rights of any other entity. Each Contributor disclaims any liability to Recipient for claims brought by any other entity based on infringement of intellectual property rights or otherwise. As a condition to exercising the rights and licenses granted hereunder, each Recipient hereby assumes sole responsibility to secure any other intellectual property rights needed, if any. For example, if a third party patent license is required to allow Recipient to distribute the Program, it is Recipient's responsibility to acquire that license before distributing the Program.

d) Each Contributor represents that to its knowledge it has sufficient copyright rights in its Contribution, if any, to grant the copyright license set forth in this Agreement.

3. REQUIREMENTS

A Contributor may choose to distribute the Program
in object code form under
its own license agreement, provided that:

a) it complies with the terms and conditions of this Agreement; and

b) its license agreement:

i) effectively disclaims on behalf of all Contributors all warranties and conditions, express and implied, including warranties or conditions of title and non-infringement, and implied warranties or conditions of merchantability and fitness for a particular purpose;

ii) effectively excludes on behalf of all Contributors all liability for damages, including direct, indirect, special, incidental and consequential damages, such as lost profits;

iii) states that any provisions which differ from this Agreement are offered by that Contributor alone and not by any other party; and

iv) states that source code for the Program is available from such Contributor, and informs licensees how to obtain it in a reasonable manner on or through a medium customarily used for software exchange.

When the Program is made available in source code form:

a) it must be made available under this Agreement; and

b) a copy of this Agreement must be included with each copy of the Program. Contributors may not remove or alter any copyright notices contained within the Program.

Each Contributor must identify itself as the originator of its Contribution, if any, in a manner that reasonably allows subsequent Recipients to identify the originator of the Contribution.

4. COMMERCIAL DISTRIBUTION

Commercial distributors of software may accept certain responsibilities with respect to end users, business partners and the like. While this license is intended to facilitate the commercial use of the Program, the Contributor who includes the Program in a commercial product offering should do so in a manner which does not create potential liability for other Contributors. Therefore, if a Contributor includes the Program in a commercial product offering, such Contributor ("Commercial Contributor") hereby agrees to defend and indemnify every other Contributor ("Indemnified Contributor") against any losses, damages and costs (collectively "Losses") arising from claims, lawsuits and other legal actions brought by a third party against the Indemnified Contributor to the extent caused by the acts or omissions of such Commercial Contributor in connection with its distribution of the Program in a commercial product offering. The obligations in this section do not apply to any claims or Losses relating to any actual or alleged intellectual property infringement. In order to qualify, an Indemnified Contributor must:

a) promptly notify the Commercial Contributor in writing of such claim, and

b) allow the Commercial Contributor to control, and cooperate with the Commercial Contributor in, the defense and any related settlement

negotiations. The Indemnified Contributor may participate in any such claim at its own expense.

For example,
a Contributor might include the Program in a commercial product offering, Product X. That Contributor is then a Commercial Contributor. If that Commercial Contributor then makes performance claims, or offers warranties related to Product X, those performance claims and warranties are such Commercial Contributor's responsibility alone. Under this section, the Commercial Contributor would have to defend claims against the other Contributors related to those performance claims and warranties, and if a court requires any other Contributor to pay any damages as a result, the Commercial Contributor must pay those damages.

5. NO WARRANTY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, THE PROGRAM IS PROVIDED ON AN "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, EITHER EXPRESS OR IMPLIED INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OR CONDITIONS OF TITLE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each Recipient is solely responsible for determining
the appropriateness of using
and distributing the Program and assumes all risks associated with its exercise of rights under this Agreement , including but not limited to the risks and costs of program errors, compliance with applicable laws, damage to or loss of data, programs or equipment, and unavailability or interruption of operations.

6. DISCLAIMER OF LIABILITY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, NEITHER RECIPIENT NOR ANY CONTRIBUTORS SHALL HAVE ANY LIABILITY FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION LOST PROFITS), HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OR DISTRIBUTION OF THE PROGRAM OR THE EXERCISE OF ANY RIGHTS GRANTED HEREUNDER, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. GENERAL

If any provision of this Agreement is invalid or unenforceable under applicable
law, it shall not affect the validity or enforceability of the remainder of the terms of this Agreement, and without further action by the parties hereto, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

If Recipient institutes patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Program itself (excluding combinations of the Program with other software or hardware) infringes such Recipient's patent(s), then such Recipient's rights granted under Section 2(b) shall terminate as of the date such litigation is filed.

All Recipient's rights under this Agreement shall terminate if it fails to comply with any of the material terms or conditions of this Agreement and does not cure such failure in a reasonable period of time after becoming aware of such noncompliance. If all Recipient's rights under this Agreement terminate, Recipient agrees to cease use and distribution of the Program as soon as reasonably practicable. However, Recipient's obligations under this Agreement and any licenses granted by Recipient relating to the Program shall continue and survive.

Everyone is permitted to copy and distribute copies of this Agreement, but in order to avoid inconsistency the Agreement is copyrighted and may only be modified in the following manner. The Agreement Steward reserves the right to publish new versions (including revisions) of this Agreement from time to time. No one other than the Agreement Steward has the right to modify this Agreement. The Eclipse Foundation is the initial Agreement Steward. The Eclipse Foundation may assign the responsibility to serve as the Agreement Steward to a suitable separate entity. Each new version of the Agreement will be given a distinguishing version number. The Program (including Contributions) may always be distributed subject to the version of the Agreement under which it was received. In addition, after a new version of the Agreement is published, Contributor may elect to distribute the Program (including its Contributions) under the new version. Except as expressly stated in Sections 2(a) and 2(b) above, Recipient receives no rights or licenses to the intellectual property of any Contributor under this Agreement, whether expressly, by implication, estoppel or otherwise. All rights in the Program not expressly granted under this Agreement are reserved.

This Agreement is governed by the laws of the State of New York and the intellectual property laws of the United States of America. No party to this Agreement will bring a legal action under this Agreement more than one year after the cause of action arose. Each party waives its rights to a jury trial in any resulting litigation.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND

DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner

or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously
marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices

stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each

Contributor provides its Contributions)
on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited
to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache
License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS
OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

==========

Jetty Web Container
Copyright 1995-2018 Mort Bay Consulting Pty Ltd.

==========

The Jetty Web Container is Copyright Mort Bay Consulting Pty Ltd
unless otherwise noted.

Jetty is dual licensed under both

* The Apache 2.0 License
http://www.apache.org/licenses/LICENSE-2.0.html

and

* The Eclipse Public 1.0 License
http://www.eclipse.org/legal/epl-v10.html

Jetty may be distributed under either license.

Eclipse

The following artifacts are EPL.
* org.eclipse.jetty.orbit:org.eclipse.jdt.core

The following artifacts are EPL and ASL2.
* org.eclipse.jetty.orbit:javax.security.auth.message

The following artifacts are EPL and CDDL 1.0.
* org.eclipse.jetty.orbit:javax.mail.glassfish

Oracle

The following artifacts are CDDL + GPLv2 with classpath exception.
https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

* javax.servlet:javax.servlet-api
 * javax.annotation:javax.annotation-api
* javax.transaction:javax.transaction-api
* javax.websocket:javax.websocket-api

Oracle OpenJDK

If ALPN is used to negotiate HTTP/2 connections, then the following
artifacts may be included in the distribution or downloaded when ALPN
module is selected.

* java.sun.security.ssl

These artifacts replace/modify OpenJDK classes. The modifications
are hosted at github and both modified and original are under GPL v2 with
classpath exceptions.
http://openjdk.java.net/legal/gplv2+ce.html

OW2

The following artifacts are licensed by the OW2 Foundation according to the
terms of http://asm.ow2.org/license.html

org.ow2.asm:asm-commons
org.ow2.asm:asm

Apache

The following artifacts are ASL2 licensed.

org.apache.taglibs:taglibs-standard-spec
org.apache.taglibs:taglibs-standard-impl

MortBay

The following artifacts are ASL2 licensed. Based on selected classes from

following Apache Tomcat jars, all ASL2
licensed.

org.mortbay.jasper:apache-jsp
org.apache.tomcat:tomcat-jasper
org.apache.tomcat:tomcat-juli
org.apache.tomcat:tomcat-jsp-api
org.apache.tomcat:tomcat-el-api
org.apache.tomcat:tomcat-jasper-el
org.apache.tomcat:tomcat-api
org.apache.tomcat:tomcat-util-scan
org.apache.tomcat:tomcat-util

org.mortbay.jasper:apache-el
org.apache.tomcat:tomcat-jasper-el
org.apache.tomcat:tomcat-el-api

Mortbay

The following artifacts are CDDL + GPLv2 with classpath exception.

https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

org.eclipse.jetty.toolchain:jetty-schemas

Assorted

The UnixCrypt.java code implements the one way cryptography used by
Unix systems for simple password protection. Copyright 1996 Aki Yoshida,
modified April 2001 by Iris Van den Broeke, Daniel Deville.
Permission to use, copy, modify and distribute UnixCrypt
for non-commercial or commercial purposes and without fee is
granted provided that the copyright notice appears in all
copies.

1.166 jetty-util 9.4.18.v20190429

1.166.1 Available under license :

This program and the accompanying materials are made available under the
terms of the Eclipse Public License 2.0 which is available at
http://www.eclipse.org/legal/epl-2.0, or the Apache Software License
2.0 which is available at https://www.apache.org/licenses/LICENSE-2.0.

Eclipse Public License - v 1.0

THE ACCOMPANYING PROGRAM IS PROVIDED UNDER THE TERMS OF THIS ECLIPSE PUBLIC LICENSE ("AGREEMENT"). ANY USE, REPRODUCTION OR DISTRIBUTION OF THE PROGRAM CONSTITUTES RECIPIENT'S ACCEPTANCE OF THIS AGREEMENT.

1. DEFINITIONS

"Contribution" means:

a) in the case of the initial Contributor, the initial code and documentation
distributed under this Agreement, and
b) in the case of each subsequent Contributor:
i) changes to the Program, and
ii) additions to the Program;

where such changes and/or additions to the Program originate from and are distributed by that particular Contributor. A Contribution 'originates' from a Contributor if it was added to the Program by such Contributor
itself or anyone acting on such Contributor's behalf. Contributions do not include additions to the Program which: (i) are separate modules of software distributed in conjunction with the Program under their own license agreement, and (ii) are not derivative works of the Program.

"Contributor" means any person or entity that distributes the Program.

"Licensed Patents" mean patent claims licensable by a Contributor which are necessarily infringed by the use or sale of its Contribution alone or when combined with the Program.

"Program" means the Contributions distributed in accordance with this Agreement.

"Recipient" means anyone who receives the Program under this Agreement, including all Contributors.

2. GRANT OF RIGHTS
a) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free copyright license to reproduce, prepare derivative works of, publicly display, publicly perform,
distribute and sublicense the Contribution of such Contributor, if any, and such derivative works, in source code and object code form.
b) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free patent license under Licensed Patents to make, use, sell, offer to sell, import and otherwise

transfer the Contribution of such Contributor, if any, in source code and object code form. This patent license shall apply to the combination of the Contribution and the Program if, at the time the Contribution is added by the Contributor, such addition of the Contribution causes such combination to be covered by the Licensed Patents. The patent license shall not apply to any other combinations which include the Contribution. No hardware per se is licensed hereunder.

c) Recipient understands that although each Contributor grants the licenses to its Contributions set forth herein,
no assurances are provided by any
Contributor that the Program does not infringe the patent or other intellectual property rights of any other entity. Each Contributor disclaims any liability to Recipient for claims brought by any other entity based on infringement of intellectual property rights or otherwise. As a condition to exercising the rights and licenses granted hereunder, each Recipient hereby assumes sole responsibility to secure any other intellectual property rights needed, if any. For example, if a third party patent license is required to allow Recipient to distribute the Program, it is Recipient's responsibility to acquire that license before distributing the Program.

d) Each Contributor represents that to its knowledge it has sufficient copyright rights in its Contribution, if any, to grant the copyright license set forth in this Agreement.

3. REQUIREMENTS

A Contributor may choose to distribute the Program
in object code form under
its own license agreement, provided that:

a) it complies with the terms and conditions of this Agreement; and
b) its license agreement:
i) effectively disclaims on behalf of all Contributors all warranties and conditions, express and implied, including warranties or conditions of title and non-infringement, and implied warranties or conditions of merchantability and fitness for a particular purpose;
ii) effectively excludes on behalf of all Contributors all liability for damages, including direct, indirect, special, incidental and consequential damages, such as lost profits;
iii) states that any provisions which differ from this Agreement are offered by that Contributor alone and not by any other party; and
iv) states that source code for the Program is available from such Contributor, and informs licensees how to obtain it in a reasonable manner on or through a
medium customarily used for software exchange.

When the Program is made available in source code form:

a) it must be made available under this Agreement; and
b) a copy of this Agreement must be included with each copy of the Program.
Contributors may not remove or alter any copyright notices contained within the Program.

Each Contributor must identify itself as the originator of its Contribution, if
any, in a manner that reasonably allows subsequent Recipients to identify the originator of the Contribution.

4. COMMERCIAL DISTRIBUTION

Commercial distributors of software may accept certain responsibilities with respect to end users, business partners and the like. While this license is intended to facilitate the commercial use of the Program, the Contributor who includes the Program in a commercial product offering should do so in a manner which does not create potential liability for other Contributors. Therefore, if a Contributor includes the Program in a commercial product offering, such
Contributor ("Commercial Contributor") hereby agrees to defend and indemnify every other Contributor ("Indemnified Contributor") against any losses, damages and costs (collectively "Losses") arising from claims, lawsuits and other legal actions brought by a third party against the Indemnified Contributor to the extent caused by the acts or omissions of such Commercial Contributor in connection with its distribution of the Program in a commercial product offering. The obligations in this section do not apply to any claims or Losses relating to any actual or alleged intellectual property infringement. In order to qualify, an Indemnified Contributor must:
a) promptly notify the Commercial Contributor in writing of such claim, and
b) allow the Commercial Contributor to control, and cooperate with the Commercial Contributor in, the defense and any related settlement negotiations. The Indemnified Contributor may participate in any such claim at its own expense.

For example, a Contributor might include the Program in a commercial product offering, Product X. That Contributor is then a Commercial Contributor. If that Commercial Contributor then makes performance claims, or offers warranties related to Product X, those performance claims and warranties are such Commercial Contributor's responsibility alone. Under this section, the Commercial Contributor would have to defend claims against the other Contributors related to those performance claims and warranties, and if a court requires any other Contributor to pay any damages as a result, the Commercial Contributor must pay those damages.

5. NO WARRANTY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, THE PROGRAM IS PROVIDED ON AN

"AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, EITHER EXPRESS OR IMPLIED INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OR CONDITIONS OF TITLE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each Recipient is solely responsible for determining
the appropriateness of using
and distributing the Program and assumes all risks associated with its exercise of rights under this Agreement , including but not limited to the risks and costs of program errors, compliance with applicable laws, damage to or loss of data, programs or equipment, and unavailability or interruption of operations.

6. DISCLAIMER OF LIABILITY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, NEITHER RECIPIENT NOR ANY CONTRIBUTORS SHALL HAVE ANY LIABILITY FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION LOST PROFITS), HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OR DISTRIBUTION OF THE PROGRAM OR THE EXERCISE OF ANY RIGHTS GRANTED HEREUNDER, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. GENERAL

If any provision of this Agreement is invalid or unenforceable under
applicable
law, it shall not affect the validity or enforceability of the remainder of the terms of this Agreement, and without further action by the parties hereto, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

If Recipient institutes patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Program itself (excluding combinations of the Program with other software or hardware) infringes such Recipient's patent(s), then such Recipient's rights granted under Section 2(b) shall terminate as of the date such litigation is filed.

All Recipient's rights under this Agreement shall terminate if it fails to comply with any of the material terms or conditions of this Agreement and does not cure such failure in a reasonable period of time after becoming aware of such noncompliance. If all Recipient's rights under this Agreement terminate, Recipient agrees to cease use and distribution
of the Program as soon as
reasonably practicable. However, Recipient's obligations under this Agreement and any licenses granted by Recipient relating to the Program shall continue and survive.

Everyone is permitted to copy and distribute copies of this Agreement, but in

order to avoid inconsistency the Agreement is copyrighted and may only be modified in the following manner. The Agreement Steward reserves the right to publish new versions (including revisions) of this Agreement from time to time. No one other than the Agreement Steward has the right to modify this Agreement. The Eclipse Foundation is the initial Agreement Steward. The Eclipse Foundation may assign the responsibility to serve as the Agreement Steward to a suitable separate entity. Each new version of the Agreement will be given a distinguishing version number. The Program (including Contributions) may always be distributed subject to the version of the Agreement under which it was received. In addition, after
a new version of the
Agreement is published, Contributor may elect to distribute the Program (including its Contributions) under the new version. Except as expressly stated in Sections 2(a) and 2(b) above, Recipient receives no rights or licenses to the intellectual property of any Contributor under this Agreement, whether expressly, by implication, estoppel or otherwise. All rights in the Program not expressly granted under this Agreement are reserved.

This Agreement is governed by the laws of the State of New York and the intellectual property laws of the United States of America. No party to this Agreement will bring a legal action under this Agreement more than one year after the cause of action arose. Each party waives its rights to a jury trial in any resulting litigation.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works
that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously
marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,

worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative
Works; within the Source form or
documentation, if provided along with the Derivative Works; or,

within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions)
on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited

to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache
License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS
OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

==========

Jetty Web Container
Copyright 1995-2018 Mort Bay Consulting Pty Ltd.

==========

The Jetty Web Container is Copyright Mort Bay Consulting Pty Ltd
unless otherwise noted.

Jetty is dual licensed under both

 * The Apache 2.0 License
   http://www.apache.org/licenses/LICENSE-2.0.html

     and

 * The Eclipse Public 1.0 License
   http://www.eclipse.org/legal/epl-v10.html

Jetty may be distributed under either license.

Eclipse

The following artifacts are EPL.
* org.eclipse.jetty.orbit:org.eclipse.jdt.core

The following artifacts are EPL and ASL2.
* org.eclipse.jetty.orbit:javax.security.auth.message

The following artifacts are EPL and CDDL 1.0.
* org.eclipse.jetty.orbit:javax.mail.glassfish

Oracle

The following artifacts are CDDL + GPLv2 with classpath exception.
https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

* javax.servlet:javax.servlet-api
 * javax.annotation:javax.annotation-api
* javax.transaction:javax.transaction-api
* javax.websocket:javax.websocket-api

Oracle OpenJDK

If ALPN is used to negotiate HTTP/2 connections, then the following
artifacts may be included in the distribution or downloaded when ALPN
module is selected.

* java.sun.security.ssl

These artifacts replace/modify OpenJDK classes. The modifications
are hosted at github and both modified and original are under GPL v2 with
classpath exceptions.
http://openjdk.java.net/legal/gplv2+ce.html

OW2

The following artifacts are licensed by the OW2 Foundation according to the
terms of http://asm.ow2.org/license.html

org.ow2.asm:asm-commons
org.ow2.asm:asm

Apache

The following artifacts are ASL2 licensed.

org.apache.taglibs:taglibs-standard-spec
org.apache.taglibs:taglibs-standard-impl

MortBay

The following artifacts are ASL2 licensed. Based on selected classes from
following Apache Tomcat jars, all ASL2
 licensed.

org.mortbay.jasper:apache-jsp
 org.apache.tomcat:tomcat-jasper
 org.apache.tomcat:tomcat-juli
 org.apache.tomcat:tomcat-jsp-api
 org.apache.tomcat:tomcat-el-api
 org.apache.tomcat:tomcat-jasper-el
 org.apache.tomcat:tomcat-api
 org.apache.tomcat:tomcat-util-scan
 org.apache.tomcat:tomcat-util

org.mortbay.jasper:apache-el
 org.apache.tomcat:tomcat-jasper-el
 org.apache.tomcat:tomcat-el-api

Mortbay

The following artifacts are CDDL + GPLv2 with classpath exception.

https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

org.eclipse.jetty.toolchain:jetty-schemas

Assorted

The UnixCrypt.java code implements the one way cryptography used by
Unix systems for simple password protection. Copyright 1996 Aki Yoshida,
modified April 2001 by Iris Van den Broeke, Daniel Deville.
Permission to use, copy, modify and distribute UnixCrypt
for non-commercial or commercial purposes and without fee is
granted provided that the copyright notice appears in all
 copies.

1.167 jetty 9.4.18.v20190429

1.167.1 Available under license :

This program and the accompanying materials are made available under the
terms of the Eclipse Public License 2.0 which is available at
http://www.eclipse.org/legal/epl-2.0, or the Apache Software License
2.0 which is available at https://www.apache.org/licenses/LICENSE-2.0.

Eclipse Public License - v 1.0

THE ACCOMPANYING PROGRAM IS PROVIDED UNDER THE TERMS OF THIS ECLIPSE PUBLIC LICENSE ("AGREEMENT"). ANY USE, REPRODUCTION OR DISTRIBUTION OF THE PROGRAM CONSTITUTES RECIPIENT'S ACCEPTANCE OF THIS AGREEMENT.

1. DEFINITIONS

"Contribution" means:

a) in the case of the initial Contributor, the initial code and documentation
  distributed under this Agreement, and
b) in the case of each subsequent Contributor:
   i) changes to the Program, and
  ii) additions to the Program;

where such changes and/or additions to the Program originate from and are distributed by that particular Contributor. A Contribution 'originates' from a Contributor if it was added to the Program by such Contributor itself or anyone acting on such Contributor's behalf. Contributions do not include additions to the Program which: (i) are separate modules of software distributed in conjunction with the Program under their own license agreement, and (ii) are not derivative works of the Program.

"Contributor" means any person or entity that distributes the Program.

"Licensed Patents" mean patent claims licensable by a Contributor which are necessarily infringed by the use or sale of its Contribution alone or when combined with the Program.

"Program" means the Contributions distributed in accordance with this Agreement.

"Recipient" means anyone who receives the Program under this Agreement, including all Contributors.

2. GRANT OF RIGHTS

a) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free copyright license to reproduce, prepare derivative works of, publicly display, publicly perform, distribute and sublicense the Contribution of such Contributor, if any, and such derivative works, in source code and object code form.

b) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free patent license under Licensed Patents to make, use, sell, offer to sell, import and otherwise transfer the Contribution of such Contributor, if any, in source code and object code form. This patent license shall apply to the combination of the Contribution and the Program if, at the time the Contribution is added by the Contributor, such addition of the Contribution causes such combination to be covered by the Licensed Patents. The patent license shall not apply to any other combinations which include the Contribution. No hardware per se is licensed hereunder.

c) Recipient understands that although each Contributor grants the licenses to its Contributions set forth herein, no assurances are provided by any Contributor that the Program does not infringe the patent or other intellectual property rights of any other entity. Each Contributor disclaims any liability to Recipient for claims brought by any other entity based on infringement of intellectual property rights or otherwise. As a condition to exercising the rights and licenses granted hereunder, each Recipient hereby assumes sole responsibility to secure any other intellectual property rights needed, if any. For example, if a

third party patent license is required to allow Recipient to distribute the Program, it is Recipient's responsibility to acquire that license before distributing the Program.

d) Each Contributor represents that to its knowledge it has sufficient copyright rights in its Contribution, if any, to grant the copyright license set forth in this Agreement.

3. REQUIREMENTS

A Contributor may choose to distribute the Program in object code form under its own license agreement, provided that:

a) it complies with the terms and conditions of this Agreement; and

b) its license agreement:

i) effectively disclaims on behalf of all Contributors all warranties and conditions, express and implied, including warranties or conditions of title and non-infringement, and implied warranties or conditions of merchantability and fitness for a particular purpose;

ii) effectively excludes on behalf of all Contributors all liability for damages, including direct, indirect, special, incidental and consequential damages, such as lost profits;

iii) states that any provisions which differ from this Agreement are offered by that Contributor alone and not by any other party; and

iv) states that source code for the Program is available from such Contributor, and informs licensees how to obtain it in a reasonable manner on or through a medium customarily used for software exchange.

When the Program is made available in source code form:

a) it must be made available under this Agreement; and

b) a copy of this Agreement must be included with each copy of the Program. Contributors may not remove or alter any copyright notices contained within the Program.

Each Contributor must identify itself as the originator of its Contribution, if any, in a manner that reasonably allows subsequent Recipients to identify the originator of the Contribution.

4. COMMERCIAL DISTRIBUTION

Commercial distributors of software may accept certain responsibilities with respect to end users, business partners and the like. While this license is intended to facilitate the commercial use of the Program, the Contributor who includes the Program in a commercial product offering should do so in a manner which does not create potential liability for other Contributors. Therefore,

if a Contributor includes the Program in a commercial
product offering, such
Contributor ("Commercial Contributor") hereby agrees to defend and indemnify every other Contributor ("Indemnified Contributor") against any losses, damages and costs (collectively "Losses") arising from claims, lawsuits and other legal actions brought by a third party against the Indemnified Contributor to the extent caused by the acts or omissions of such Commercial Contributor in connection with its distribution of the Program in a commercial product offering. The obligations in this section do not apply to any claims or Losses relating to any actual or alleged intellectual property infringement. In order to qualify, an Indemnified Contributor must:
a) promptly notify the Commercial Contributor in writing of such claim, and
b) allow the Commercial Contributor to control, and cooperate with the Commercial Contributor in, the defense and any related settlement negotiations. The Indemnified Contributor may participate in any such claim at its own expense.

For example,
a Contributor might include the Program in a commercial product offering, Product X. That Contributor is then a Commercial Contributor. If that Commercial Contributor then makes performance claims, or offers warranties related to Product X, those performance claims and warranties are such Commercial Contributor's responsibility alone. Under this section, the Commercial Contributor would have to defend claims against the other Contributors related to those performance claims and warranties, and if a court requires any other Contributor to pay any damages as a result, the Commercial Contributor must pay those damages.

5. NO WARRANTY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, THE PROGRAM IS PROVIDED ON AN "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, EITHER EXPRESS OR IMPLIED INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OR CONDITIONS OF TITLE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each Recipient is solely responsible for determining
the appropriateness of using
and distributing the Program and assumes all risks associated with its exercise of rights under this Agreement , including but not limited to the risks and costs of program errors, compliance with applicable laws, damage to or loss of data, programs or equipment, and unavailability or interruption of operations.

6. DISCLAIMER OF LIABILITY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, NEITHER RECIPIENT NOR ANY CONTRIBUTORS SHALL HAVE ANY LIABILITY FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION LOST PROFITS), HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN

CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OR DISTRIBUTION OF THE PROGRAM OR THE EXERCISE OF ANY RIGHTS GRANTED HEREUNDER, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. GENERAL

If any provision of this Agreement is invalid or unenforceable under applicable
law, it shall not affect the validity or enforceability of the remainder of the terms of this Agreement, and without further action by the parties hereto, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

If Recipient institutes patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Program itself (excluding combinations of the Program with other software or hardware) infringes such Recipient's patent(s), then such Recipient's rights granted under Section 2(b) shall terminate as of the date such litigation is filed.

All Recipient's rights under this Agreement shall terminate if it fails to comply with any of the material terms or conditions of this Agreement and does not cure such failure in a reasonable period of time after becoming aware of such noncompliance. If all Recipient's rights under this Agreement terminate, Recipient agrees to cease use and distribution
of the Program as soon as
reasonably practicable. However, Recipient's obligations under this Agreement and any licenses granted by Recipient relating to the Program shall continue and survive.

Everyone is permitted to copy and distribute copies of this Agreement, but in order to avoid inconsistency the Agreement is copyrighted and may only be modified in the following manner. The Agreement Steward reserves the right to publish new versions (including revisions) of this Agreement from time to time. No one other than the Agreement Steward has the right to modify this Agreement. The Eclipse Foundation is the initial Agreement Steward. The Eclipse Foundation may assign the responsibility to serve as the Agreement Steward to a suitable separate entity. Each new version of the Agreement will be given a distinguishing version number. The Program (including Contributions) may always be distributed subject to the version of the Agreement under which it was received. In addition, after
a new version of the
Agreement is published, Contributor may elect to distribute the Program (including its Contributions) under the new version. Except as expressly stated in Sections 2(a) and 2(b) above, Recipient receives no rights or licenses to the intellectual property of any Contributor under this Agreement, whether expressly, by implication, estoppel or otherwise. All rights in the Program not expressly granted under this Agreement are reserved.

This Agreement is governed by the laws of the State of New York and the intellectual property laws of the United States of America. No party to this Agreement will bring a legal action under this Agreement more than one year after the cause of action arose. Each party waives its rights to a jury trial in any resulting litigation.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works
that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously
marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct

or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative
Works; within the Source form or
documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,

any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions)
on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited
to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache
License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS
OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL) Version 1.0

1. Definitions.

1.1. Contributor. means each individual or entity that creates or contributes to the creation of Modifications.

1.2. Contributor Version. means the combination of the Original Software, prior Modifications used by a Contributor (if any), and the Modifications made by that particular Contributor.

1.3. Covered Software. means (a) the Original Software, or (b) Modifications, or (c) the combination of files containing Original Software with files containing Modifications, in each case including portions thereof.

1.4. Executable. means the Covered Software in any form other than Source Code.

1.5. Initial Developer. means the individual or entity that first makes Original Software available under this License.

1.6. Larger Work. means a work which combines Covered Software or portions thereof with code not governed by the terms of this License.

1.7. License. means this document.

1.8.
Licensable. means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently acquired, any and all of the rights conveyed herein.

1.9. Modifications. means the Source Code and Executable form of any of the following:

A. Any file that results from an addition to, deletion from or modification of the contents of a file containing Original Software or previous Modifications;

B. Any new file that contains any part of the Original Software or previous Modification; or

C. Any new file that is contributed or otherwise made available under the terms of this License.

1.10. Original Software. means the Source Code and Executable form of computer software code that is originally released under this License.

1.11. Patent Claims. means any patent claim(s), now owned or hereafter acquired, including without limitation, method, process, and apparatus claims, in any patent Licensable by grantor.

1.12.
Source Code. means (a) the common form of computer software code in which modifications are made and (b) associated documentation included in or with such code.

1.13. You. (or .Your.) means an individual or a legal entity exercising rights under, and complying with all of the terms of, this License. For legal entities, .You. includes any entity which controls, is controlled by, or is under common control with You. For purposes of this definition, .control. means (a) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (b) ownership of more than fifty percent (50%) of the outstanding shares or beneficial ownership of such entity.

2. License Grants.

2.1. The Initial Developer Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, the Initial Developer hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under
intellectual property rights (other than patent or trademark) Licensable by Initial Developer, to use, reproduce, modify, display, perform, sublicense and distribute the Original Software (or portions thereof), with or without Modifications, and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using or selling of Original Software, to make, have made, use, practice, sell, and offer for sale, and/or otherwise dispose of the Original Software (or portions thereof).

(c) The licenses granted in Sections 2.1(a) and (b) are effective on the date Initial Developer first distributes or otherwise makes the Original Software available to a third party under the terms of this License.

(d) Notwithstanding Section 2.1(b) above, no patent license is granted: (1) for code that You delete from the Original Software, or (2) for infringements caused by: (i) the modification of the Original Software, or (ii) the combination of the Original Software
with other software or devices.

2.2. Contributor Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, each Contributor hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under intellectual property rights (other than patent or trademark) Licensable by Contributor to use, reproduce, modify, display, perform, sublicense and distribute the Modifications created by such Contributor (or portions thereof), either on an unmodified basis, with other Modifications, as Covered Software and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using, or selling of Modifications made by that Contributor either alone and/or in combination with its Contributor Version (or portions of such combination), to make, use, sell, offer for sale, have made, and/or otherwise dispose of: (1) Modifications made by that Contributor (or portions thereof); and (2) the
combination of Modifications made by that Contributor with its Contributor Version (or portions of such combination).

(c) The licenses granted in Sections 2.2(a) and 2.2(b) are effective on the date Contributor first distributes or otherwise makes the Modifications available to a third party.

(d) Notwithstanding Section 2.2(b) above, no patent license is granted: (1) for any code that Contributor has deleted from the Contributor Version; (2) for infringements caused by: (i) third party modifications of Contributor Version, or (ii) the combination of Modifications made by that Contributor with other software (except as part of the Contributor Version) or other devices; or (3) under Patent Claims infringed by Covered Software in the absence of Modifications made by that Contributor.

3. Distribution Obligations.

3.1. Availability of Source Code.
Any Covered Software that You distribute or otherwise make available in Executable form must also be made available
in Source Code form and that Source Code form must be distributed only under the terms of this License. You must include a copy of this License with every copy of the Source Code form of the Covered Software You distribute or otherwise make available. You must inform recipients of any such Covered Software in Executable form as to how they can obtain such Covered Software in Source Code form in a reasonable manner on or through a medium customarily used for software exchange.

3.2. Modifications.
The Modifications that You create or to which You contribute are governed by the terms of this License. You represent that You believe Your Modifications are Your original creation(s) and/or You have sufficient rights to grant the rights conveyed by this License.

3.3. Required Notices.

You must include a notice in each of Your Modifications that identifies You as the Contributor of the Modification. You may not remove or alter any copyright, patent or trademark notices contained within the Covered Software, or any notices of licensing or any descriptive text giving attribution to any Contributor or the Initial Developer.

3.4. Application of Additional Terms.

You may not offer or impose any terms on any Covered Software in Source Code form that alters or restricts the applicable version of this License or the recipients. rights hereunder. You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, you may do so only on Your own behalf, and not on behalf of the Initial Developer or any Contributor. You must make it absolutely clear that any such warranty, support, indemnity or liability obligation is offered by You alone, and You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of warranty, support, indemnity or liability terms You offer.

3.5. Distribution of Executable Versions.

You may distribute the Executable form of the Covered Software under the terms of this License or under the terms of a license of Your choice, which may contain terms different from this License, provided that You are in compliance with the terms of this License and that the license for the Executable form does not attempt to limit or alter the recipient.s rights in the Source Code form from the rights set forth in this License. If You distribute the Covered Software in Executable form under a different license, You must make it absolutely clear that any terms which differ from this License are offered by You alone, not by the Initial Developer or Contributor. You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of any such terms You offer.

3.6. Larger Works.

You may create a Larger Work by combining Covered Software with other code not governed by the terms of this License and distribute the Larger Work as a single product. In such a case, You must make sure the requirements of this License are fulfilled for the Covered Software.

4. Versions of the License.

4.1. New Versions.

Sun Microsystems, Inc. is the initial license steward and may publish revised and/or new versions of this License from time to time. Each version will be given a distinguishing version number. Except as provided in Section 4.3, no one other than the license steward has the right to modify this License.

4.2. Effect of New Versions.

You may always continue to use, distribute or otherwise make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. If the Initial Developer includes a notice in the Original Software prohibiting it from being distributed or otherwise made available under any subsequent version of the License, You must distribute and make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. Otherwise, You may also choose to use, distribute or otherwise make the Covered Software available under the terms of any subsequent version of the License published by the license steward.

4.3. Modified Versions.

When You are an Initial Developer and You want to create a new license for Your Original Software, You may create and use a modified version of this License if You: (a) rename the license and remove any references to the name of the license steward (except to note that the license differs from this License); and (b) otherwise make it clear that the license contains terms which differ from this License.

5. DISCLAIMER OF WARRANTY.

COVERED SOFTWARE IS PROVIDED UNDER THIS LICENSE ON AN .AS IS. BASIS, WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES
THAT THE COVERED SOFTWARE IS FREE OF DEFECTS, MERCHANTABLE, FIT FOR A PARTICULAR PURPOSE OR NON-INFRINGING. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE COVERED SOFTWARE IS WITH YOU. SHOULD ANY COVERED SOFTWARE PROVE DEFECTIVE IN ANY RESPECT, YOU (NOT THE INITIAL DEVELOPER OR ANY OTHER CONTRIBUTOR) ASSUME THE COST OF ANY NECESSARY SERVICING, REPAIR OR CORRECTION. THIS DISCLAIMER OF WARRANTY CONSTITUTES AN ESSENTIAL PART OF THIS LICENSE. NO USE OF ANY COVERED SOFTWARE IS AUTHORIZED HEREUNDER EXCEPT UNDER THIS DISCLAIMER.

6. TERMINATION.

6.1. This License and the rights granted hereunder will terminate automatically if You fail to comply with terms herein and fail to cure such breach within 30 days of becoming aware of the breach. Provisions which, by their nature, must remain in effect beyond the termination of this License shall survive.

6.2. If You assert a patent infringement claim (excluding declaratory judgment actions) against Initial Developer or a Contributor (the Initial Developer or Contributor against whom You assert such claim is referred to as .Participant.) alleging that the Participant Software (meaning the Contributor Version where the Participant is a Contributor or the Original Software where the Participant is the Initial Developer) directly or indirectly infringes any patent, then any and all rights granted directly or indirectly to You by such Participant, the Initial Developer (if the Initial Developer is not the Participant) and all Contributors under Sections 2.1 and/or 2.2 of this License shall, upon 60 days notice from Participant terminate prospectively and automatically at the expiration of such 60 day notice period, unless if within such 60 day period You withdraw Your claim with respect to the Participant Software against such Participant either unilaterally or pursuant to a written agreement with Participant.

6.3. In the event of termination under Sections 6.1 or 6.2 above, all end user licenses
that have been validly granted by You or any distributor hereunder prior to termination (excluding licenses granted to You by any distributor) shall survive termination.

7. LIMITATION OF LIABILITY.

UNDER NO CIRCUMSTANCES AND UNDER NO LEGAL THEORY, WHETHER TORT (INCLUDING NEGLIGENCE), CONTRACT, OR OTHERWISE, SHALL YOU, THE INITIAL DEVELOPER, ANY OTHER CONTRIBUTOR, OR ANY DISTRIBUTOR OF COVERED SOFTWARE, OR ANY SUPPLIER OF ANY OF SUCH PARTIES, BE LIABLE TO ANY PERSON FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY CHARACTER INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOST PROFITS, LOSS OF GOODWILL, WORK STOPPAGE, COMPUTER FAILURE OR MALFUNCTION, OR ANY AND ALL OTHER COMMERCIAL DAMAGES OR LOSSES, EVEN IF SUCH PARTY SHALL HAVE BEEN INFORMED OF THE POSSIBILITY OF SUCH DAMAGES. THIS LIMITATION

OF LIABILITY SHALL NOT APPLY TO LIABILITY FOR DEATH OR PERSONAL INJURY RESULTING FROM SUCH PARTY.S NEGLIGENCE TO THE EXTENT APPLICABLE LAW PROHIBITS SUCH LIMITATION. SOME JURISDICTIONS
DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS EXCLUSION AND LIMITATION MAY NOT APPLY TO YOU.

8. U.S. GOVERNMENT END USERS.

The Covered Software is a .commercial item,. as that term is defined in 48 C.F.R. 2.101 (Oct. 1995), consisting of .commercial computer software. (as that term is defined at 48 C.F.R. ? 252.227-7014(a)(1)) and .commercial computer software documentation. as such terms are used in 48 C.F.R. 12.212 (Sept. 1995). Consistent with 48 C.F.R. 12.212 and 48 C.F.R. 227.7202-1 through 227.7202-4 (June 1995), all U.S. Government End Users acquire Covered Software with only those rights set forth herein. This U.S. Government Rights clause is in lieu of, and supersedes, any other FAR, DFAR, or other clause or provision that addresses Government rights in computer software under this License.

9. MISCELLANEOUS.

This License represents the complete agreement concerning subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable. This License shall be governed by the law of the jurisdiction specified in a notice contained within the Original Software (except to the extent applicable law, if any, provides otherwise), excluding such jurisdiction.s conflict-of-law provisions. Any litigation relating to this License shall be subject to the jurisdiction of the courts located in the jurisdiction and venue specified in a notice contained within the Original Software, with the losing party responsible for costs, including, without limitation, court costs and reasonable attorneys. fees and expenses. The application of the United Nations Convention on Contracts for the International Sale of Goods is expressly excluded. Any law or regulation which provides that the language of a contract shall be construed against the drafter shall not apply to this License. You agree that You alone are responsible for
compliance with the United States export administration regulations (and the export control laws and regulation of any other countries) when You use, distribute or otherwise make available any Covered Software.

10. RESPONSIBILITY FOR CLAIMS.

As between Initial Developer and the Contributors, each party is responsible for claims and damages arising, directly or indirectly, out of its utilization of rights under this License and You agree to work with Initial Developer and Contributors to distribute such responsibility on an equitable basis. Nothing herein is intended or shall be deemed to constitute any admission of liability.

NOTICE PURSUANT TO SECTION 9 OF THE COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL)

The code released under the CDDL shall be governed by the laws of the State of California (excluding conflict-of-law provisions). Any litigation relating to this License shall be subject to the jurisdiction of the Federal Courts of the Northern District of California
and the state courts of the State of California, with venue lying in Santa Clara County, California.

The GNU General Public License (GPL) Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software,
we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer
you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any

program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute
verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that
in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works
in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear
what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE

STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These
Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

One line to give the program's name and a brief idea of what it does.

Copyright (C)

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY
or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'. This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits
your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.

signature of Ty Coon, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

"CLASSPATH" EXCEPTION TO THE GPL VERSION 2

Certain source files distributed by Sun Microsystems, Inc. are subject to the following clarification and special exception to the GPL Version 2, but only where Sun has expressly included in the particular
source file's header the words

"Sun designates this particular file as subject to the "Classpath" exception as provided by Sun in the License file that accompanied this code."

Linking this library statically or dynamically with other modules is making a combined work based on this library. Thus, the terms and conditions of the GNU General Public License Version 2 cover the whole combination.

As a special exception, the copyright holders of this library give you permission to link this library with independent modules to produce an executable, regardless of the license terms of these independent modules, and to copy and distribute the resulting executable under terms of your choice, provided that you also meet, for each linked independent module, the terms and conditions of the license of that module.? An independent module is a module which is not derived from or based on this library.? If you modify this library, you may extend this exception to your version of the library, but
you are not obligated to do so.? If you do not wish to do so, delete this exception statement from your version.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally

submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the

content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Java Authentication SPI for Containers
Copyright 2003-2009 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).
==========
Jetty Web Container
Copyright 1995-2018 Mort Bay Consulting Pty Ltd.
==========

The Jetty Web Container is Copyright Mort Bay Consulting Pty Ltd
unless otherwise noted.

Jetty is dual licensed under both

* The Apache 2.0 License
http://www.apache.org/licenses/LICENSE-2.0.html

and

* The Eclipse Public 1.0 License
http://www.eclipse.org/legal/epl-v10.html

Jetty may be distributed under either license.

Eclipse

The following artifacts are EPL.
* org.eclipse.jetty.orbit:org.eclipse.jdt.core

The following artifacts are EPL and ASL2.
* org.eclipse.jetty.orbit:javax.security.auth.message

The following artifacts are EPL and CDDL 1.0.
* org.eclipse.jetty.orbit:javax.mail.glassfish

Oracle

The following artifacts are CDDL + GPLv2 with classpath exception.
https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

* javax.servlet:javax.servlet-api
 * javax.annotation:javax.annotation-api
* javax.transaction:javax.transaction-api
* javax.websocket:javax.websocket-api

Oracle OpenJDK

If ALPN is used to negotiate HTTP/2 connections, then the following
artifacts may be included in the distribution or downloaded when ALPN
module is selected.

* java.sun.security.ssl

These artifacts replace/modify OpenJDK classes. The modifications
are hosted at github and both modified and original are under GPL v2 with
classpath exceptions.
http://openjdk.java.net/legal/gplv2+ce.html

OW2

The following artifacts are licensed by the OW2 Foundation according to the
terms of http://asm.ow2.org/license.html

org.ow2.asm:asm-commons
org.ow2.asm:asm

Apache

The following artifacts are ASL2 licensed.

org.apache.taglibs:taglibs-standard-spec

org.apache.taglibs:taglibs-standard-impl

MortBay

The following artifacts are ASL2 licensed. Based on selected classes from
following Apache Tomcat jars, all ASL2
licensed.

org.mortbay.jasper:apache-jsp
org.apache.tomcat:tomcat-jasper
org.apache.tomcat:tomcat-juli
org.apache.tomcat:tomcat-jsp-api
org.apache.tomcat:tomcat-el-api
org.apache.tomcat:tomcat-jasper-el
org.apache.tomcat:tomcat-api
org.apache.tomcat:tomcat-util-scan
org.apache.tomcat:tomcat-util

org.mortbay.jasper:apache-el
org.apache.tomcat:tomcat-jasper-el
org.apache.tomcat:tomcat-el-api

Mortbay

The following artifacts are CDDL + GPLv2 with classpath exception.

https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

org.eclipse.jetty.toolchain:jetty-schemas

Assorted

The UnixCrypt.java code implements the one way cryptography used by
Unix systems for simple password protection. Copyright 1996 Aki Yoshida,
modified April 2001 by Iris Van den Broeke, Daniel Deville.
Permission to use, copy, modify and distribute UnixCrypt
for non-commercial or commercial purposes and without fee is
granted provided that the copyright notice appears in all
copies.

1.168 jetty-servlets 9.4.18.v20190429

1.168.1 Available under license :

This program and the accompanying materials are made available under the
terms of the Eclipse Public License 2.0 which is available at
http://www.eclipse.org/legal/epl-2.0, or the Apache Software License
2.0 which is available at https://www.apache.org/licenses/LICENSE-2.0.

Eclipse Public License - v 1.0

THE ACCOMPANYING PROGRAM IS PROVIDED UNDER THE TERMS OF THIS ECLIPSE PUBLIC LICENSE ("AGREEMENT"). ANY USE, REPRODUCTION OR DISTRIBUTION OF THE PROGRAM CONSTITUTES RECIPIENT'S ACCEPTANCE OF THIS AGREEMENT.

1. DEFINITIONS

"Contribution" means:

a) in the case of the initial Contributor, the initial code and documentation
distributed under this Agreement, and
b) in the case of each subsequent Contributor:
i) changes to the Program, and
ii) additions to the Program;

where such changes and/or additions to the Program originate from and are
distributed by that particular Contributor. A Contribution 'originates'
from a Contributor if it was added to the Program by such
Contributor
itself or anyone acting on such Contributor's behalf. Contributions do not
include additions to the Program which: (i) are separate modules of
software distributed in conjunction with the Program under their own
license agreement, and (ii) are not derivative works of the Program.

"Contributor" means any person or entity that distributes the Program.

"Licensed Patents" mean patent claims licensable by a Contributor which are
necessarily infringed by the use or sale of its Contribution alone or when
combined with the Program.

"Program" means the Contributions distributed in accordance with this
Agreement.

"Recipient" means anyone who receives the Program under this Agreement,
including all Contributors.

2. GRANT OF RIGHTS

a) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free copyright license to reproduce, prepare derivative works of, publicly display, publicly perform,
distribute and sublicense the Contribution of such Contributor, if any, and such derivative works, in source code and object code form.

b) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free patent license under Licensed Patents to make, use, sell, offer to sell, import and otherwise transfer the Contribution of such Contributor, if any, in source code and object code form. This patent license shall apply to the combination of the Contribution and the Program if, at the time the Contribution is added by the Contributor, such addition of the Contribution causes such combination to be covered by the Licensed Patents. The patent license shall not apply to any other combinations which include the Contribution. No hardware per se is licensed hereunder.

c) Recipient understands that although each Contributor grants the licenses to its Contributions set forth herein,
no assurances are provided by any
Contributor that the Program does not infringe the patent or other intellectual property rights of any other entity. Each Contributor disclaims any liability to Recipient for claims brought by any other entity based on infringement of intellectual property rights or otherwise. As a condition to exercising the rights and licenses granted hereunder, each Recipient hereby assumes sole responsibility to secure any other intellectual property rights needed, if any. For example, if a third party patent license is required to allow Recipient to distribute the Program, it is Recipient's responsibility to acquire that license before distributing the Program.

d) Each Contributor represents that to its knowledge it has sufficient copyright rights in its Contribution, if any, to grant the copyright license set forth in this Agreement.

3. REQUIREMENTS

A Contributor may choose to distribute the Program
in object code form under
its own license agreement, provided that:

a) it complies with the terms and conditions of this Agreement; and

b) its license agreement:

i) effectively disclaims on behalf of all Contributors all warranties and conditions, express and implied, including warranties or conditions of title and non-infringement, and implied warranties or conditions of merchantability and fitness for a particular purpose;

ii) effectively excludes on behalf of all Contributors all liability for damages, including direct, indirect, special, incidental and

consequential damages, such as lost profits;
iii) states that any provisions which differ from this Agreement are offered by that Contributor alone and not by any other party; and
iv) states that source code for the Program is available from such Contributor, and informs licensees how to obtain it in a reasonable manner on or through a
medium customarily used for software exchange.

When the Program is made available in source code form:

a) it must be made available under this Agreement; and
b) a copy of this Agreement must be included with each copy of the Program. Contributors may not remove or alter any copyright notices contained within the Program.

Each Contributor must identify itself as the originator of its Contribution, if
any, in a manner that reasonably allows subsequent Recipients to identify the originator of the Contribution.

4. COMMERCIAL DISTRIBUTION

Commercial distributors of software may accept certain responsibilities with respect to end users, business partners and the like. While this license is intended to facilitate the commercial use of the Program, the Contributor who includes the Program in a commercial product offering should do so in a manner which does not create potential liability for other Contributors. Therefore, if a Contributor includes the Program in a commercial
product offering, such
Contributor ("Commercial Contributor") hereby agrees to defend and indemnify every other Contributor ("Indemnified Contributor") against any losses, damages and costs (collectively "Losses") arising from claims, lawsuits and other legal actions brought by a third party against the Indemnified Contributor to the extent caused by the acts or omissions of such Commercial Contributor in connection with its distribution of the Program in a commercial product offering. The obligations in this section do not apply to any claims or Losses relating to any actual or alleged intellectual property infringement. In order to qualify, an Indemnified Contributor must:
a) promptly notify the Commercial Contributor in writing of such claim, and
b) allow the Commercial Contributor to control, and cooperate with the Commercial Contributor in, the defense and any related settlement negotiations. The Indemnified Contributor may participate in any such claim at its own expense.

For example,
a Contributor might include the Program in a commercial product offering, Product X. That Contributor is then a Commercial Contributor. If that Commercial Contributor then makes performance claims, or offers

warranties related to Product X, those performance claims and warranties are such Commercial Contributor's responsibility alone. Under this section, the Commercial Contributor would have to defend claims against the other Contributors related to those performance claims and warranties, and if a court requires any other Contributor to pay any damages as a result, the Commercial Contributor must pay those damages.

5. NO WARRANTY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, THE PROGRAM IS PROVIDED ON AN "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, EITHER EXPRESS OR IMPLIED INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OR CONDITIONS OF TITLE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each Recipient is solely responsible for determining
the appropriateness of using
and distributing the Program and assumes all risks associated with its exercise of rights under this Agreement , including but not limited to the risks and costs of program errors, compliance with applicable laws, damage to or loss of data, programs or equipment, and unavailability or interruption of operations.

6. DISCLAIMER OF LIABILITY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, NEITHER RECIPIENT NOR ANY CONTRIBUTORS SHALL HAVE ANY LIABILITY FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION LOST PROFITS), HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OR DISTRIBUTION OF THE PROGRAM OR THE EXERCISE OF ANY RIGHTS GRANTED HEREUNDER, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. GENERAL

If any provision of this Agreement is invalid or unenforceable under applicable
law, it shall not affect the validity or enforceability of the remainder of the terms of this Agreement, and without further action by the parties hereto, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

If Recipient institutes patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Program itself (excluding combinations of the Program with other software or hardware) infringes such Recipient's patent(s), then such Recipient's rights granted under Section 2(b) shall terminate as of the date such litigation is filed.

All Recipient's rights under this Agreement shall terminate if it fails to

comply with any of the material terms or conditions of this Agreement and does not cure such failure in a reasonable period of time after becoming aware of such noncompliance. If all Recipient's rights under this Agreement terminate, Recipient agrees to cease use and distribution
of the Program as soon as
reasonably practicable. However, Recipient's obligations under this Agreement and any licenses granted by Recipient relating to the Program shall continue and survive.

Everyone is permitted to copy and distribute copies of this Agreement, but in order to avoid inconsistency the Agreement is copyrighted and may only be modified in the following manner. The Agreement Steward reserves the right to publish new versions (including revisions) of this Agreement from time to time. No one other than the Agreement Steward has the right to modify this Agreement. The Eclipse Foundation is the initial Agreement Steward. The Eclipse Foundation may assign the responsibility to serve as the Agreement Steward to a suitable separate entity. Each new version of the Agreement will be given a distinguishing version number. The Program (including Contributions) may always be distributed subject to the version of the Agreement under which it was received. In addition, after
a new version of the
Agreement is published, Contributor may elect to distribute the Program (including its Contributions) under the new version. Except as expressly stated in Sections 2(a) and 2(b) above, Recipient receives no rights or licenses to the intellectual property of any Contributor under this Agreement, whether expressly, by implication, estoppel or otherwise. All rights in the Program not expressly granted under this Agreement are reserved.

This Agreement is governed by the laws of the State of New York and the intellectual property laws of the United States of America. No party to this Agreement will bring a legal action under this Agreement more than one year after the cause of action arose. Each party waives its rights to a jury trial in any resulting litigation.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works
that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but

excluding communication that is conspicuously
marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any

risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited
to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache
License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS
OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
==========

Jetty Web Container
Copyright 1995-2018 Mort Bay Consulting Pty Ltd.
==========

The Jetty Web Container is Copyright Mort Bay Consulting Pty Ltd
unless otherwise noted.

Jetty is dual licensed under both

* The Apache 2.0 License
http://www.apache.org/licenses/LICENSE-2.0.html

and

* The Eclipse Public 1.0 License
http://www.eclipse.org/legal/epl-v10.html

Jetty may be distributed under either license.

Eclipse

The following artifacts are EPL.
* org.eclipse.jetty.orbit:org.eclipse.jdt.core

The following artifacts are EPL and ASL2.
* org.eclipse.jetty.orbit:javax.security.auth.message

The following artifacts are EPL and CDDL 1.0.
* org.eclipse.jetty.orbit:javax.mail.glassfish

Oracle

The following artifacts are CDDL + GPLv2 with classpath exception.
https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

* javax.servlet:javax.servlet-api

* javax.annotation:javax.annotation-api
* javax.transaction:javax.transaction-api
* javax.websocket:javax.websocket-api

Oracle OpenJDK

If ALPN is used to negotiate HTTP/2 connections, then the following
artifacts may be included in the distribution or downloaded when ALPN
module is selected.

* java.sun.security.ssl

These artifacts replace/modify OpenJDK classes. The modifications
are hosted at github and both modified and original are under GPL v2 with
classpath exceptions.
http://openjdk.java.net/legal/gplv2+ce.html

OW2

The following artifacts are licensed by the OW2 Foundation according to the
terms of http://asm.ow2.org/license.html

org.ow2.asm:asm-commons
org.ow2.asm:asm

Apache

The following artifacts are ASL2 licensed.

org.apache.taglibs:taglibs-standard-spec
org.apache.taglibs:taglibs-standard-impl

MortBay

The following artifacts are ASL2 licensed. Based on selected classes from
following Apache Tomcat jars, all ASL2
licensed.

org.mortbay.jasper:apache-jsp
org.apache.tomcat:tomcat-jasper
org.apache.tomcat:tomcat-juli

org.apache.tomcat:tomcat-jsp-api
org.apache.tomcat:tomcat-el-api
org.apache.tomcat:tomcat-jasper-el
org.apache.tomcat:tomcat-api
org.apache.tomcat:tomcat-util-scan
org.apache.tomcat:tomcat-util

org.mortbay.jasper:apache-el
org.apache.tomcat:tomcat-jasper-el
org.apache.tomcat:tomcat-el-api

Mortbay

The following artifacts are CDDL + GPLv2 with classpath exception.

https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

org.eclipse.jetty.toolchain:jetty-schemas

Assorted

The UnixCrypt.java code implements the one way cryptography used by
Unix systems for simple password protection. Copyright 1996 Aki Yoshida,
modified April 2001 by Iris Van den Broeke, Daniel Deville.
Permission to use, copy, modify and distribute UnixCrypt
for non-commercial or commercial purposes and without fee is
granted provided that the copyright notice appears in all
copies.

1.169 jetty-security 9.4.18.v20190429

1.169.1 Available under license :

This program and the accompanying materials are made available under the
terms of the Eclipse Public License 2.0 which is available at
http://www.eclipse.org/legal/epl-2.0, or the Apache Software License
2.0 which is available at https://www.apache.org/licenses/LICENSE-2.0.

Eclipse Public License - v 1.0

THE ACCOMPANYING PROGRAM IS PROVIDED UNDER THE TERMS OF THIS ECLIPSE PUBLIC LICENSE ("AGREEMENT"). ANY USE, REPRODUCTION OR DISTRIBUTION OF THE PROGRAM CONSTITUTES RECIPIENT'S ACCEPTANCE OF THIS AGREEMENT.

1. DEFINITIONS

"Contribution" means:

a) in the case of the initial Contributor, the initial code and documentation distributed under this Agreement, and
b) in the case of each subsequent Contributor:
i) changes to the Program, and
ii) additions to the Program;

where such changes and/or additions to the Program originate from and are distributed by that particular Contributor. A Contribution 'originates' from a Contributor if it was added to the Program by such Contributor itself or anyone acting on such Contributor's behalf. Contributions do not include additions to the Program which: (i) are separate modules of software distributed in conjunction with the Program under their own license agreement, and (ii) are not derivative works of the Program.

"Contributor" means any person or entity that distributes the Program.

"Licensed Patents" mean patent claims licensable by a Contributor which are necessarily infringed by the use or sale of its Contribution alone or when combined with the Program.

"Program" means the Contributions distributed in accordance with this Agreement.

"Recipient" means anyone who receives the Program under this Agreement, including all Contributors.

2. GRANT OF RIGHTS

a) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free copyright license to reproduce, prepare derivative works of, publicly display, publicly perform, distribute and sublicense the Contribution of such Contributor, if any, and such derivative works, in source code and object code form.
b) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free patent license under Licensed Patents to make, use, sell, offer to sell, import and otherwise transfer the Contribution of such Contributor, if any, in source code and object code form. This patent license shall apply to the combination of the Contribution and the Program if, at the time the Contribution is added by the Contributor, such addition of the Contribution causes such combination to be covered by the Licensed Patents. The patent license shall not apply to any other combinations which include the Contribution.

No hardware per se is licensed hereunder.

c) Recipient understands that although each Contributor grants the licenses to its Contributions set forth herein, no assurances are provided by any Contributor that the Program does not infringe the patent or other intellectual property rights of any other entity. Each Contributor disclaims any liability to Recipient for claims brought by any other entity based on infringement of intellectual property rights or otherwise. As a condition to exercising the rights and licenses granted hereunder, each Recipient hereby assumes sole responsibility to secure any other intellectual property rights needed, if any. For example, if a third party patent license is required to allow Recipient to distribute the Program, it is Recipient's responsibility to acquire that license before distributing the Program.

d) Each Contributor represents that to its knowledge it has sufficient copyright rights in its Contribution, if any, to grant the copyright license set forth in this Agreement.

3. REQUIREMENTS

A Contributor may choose to distribute the Program in object code form under its own license agreement, provided that:

a) it complies with the terms and conditions of this Agreement; and

b) its license agreement:

i) effectively disclaims on behalf of all Contributors all warranties and conditions, express and implied, including warranties or conditions of title and non-infringement, and implied warranties or conditions of merchantability and fitness for a particular purpose;

ii) effectively excludes on behalf of all Contributors all liability for damages, including direct, indirect, special, incidental and consequential damages, such as lost profits;

iii) states that any provisions which differ from this Agreement are offered by that Contributor alone and not by any other party; and

iv) states that source code for the Program is available from such Contributor, and informs licensees how to obtain it in a reasonable manner on or through a medium customarily used for software exchange.

When the Program is made available in source code form:

a) it must be made available under this Agreement; and

b) a copy of this Agreement must be included with each copy of the Program. Contributors may not remove or alter any copyright notices contained within the Program.

Each Contributor must identify itself as the originator of its Contribution,

if
any, in a manner that reasonably allows subsequent Recipients to identify the originator of the Contribution.

4. COMMERCIAL DISTRIBUTION

Commercial distributors of software may accept certain responsibilities with respect to end users, business partners and the like. While this license is intended to facilitate the commercial use of the Program, the Contributor who includes the Program in a commercial product offering should do so in a manner which does not create potential liability for other Contributors. Therefore, if a Contributor includes the Program in a commercial
product offering, such
Contributor ("Commercial Contributor") hereby agrees to defend and indemnify every other Contributor ("Indemnified Contributor") against any losses, damages and costs (collectively "Losses") arising from claims, lawsuits and other legal actions brought by a third party against the Indemnified Contributor to the extent caused by the acts or omissions of such Commercial Contributor in connection with its distribution of the Program in a commercial product offering. The obligations in this section do not apply to any claims or Losses relating to any actual or alleged intellectual property infringement. In order to qualify, an Indemnified Contributor must:
a) promptly notify the Commercial Contributor in writing of such claim, and
b) allow the Commercial Contributor to control, and cooperate with the Commercial Contributor in, the defense and any related settlement negotiations. The Indemnified Contributor may participate in any such claim at its own expense.

For example,
a Contributor might include the Program in a commercial product offering, Product X. That Contributor is then a Commercial Contributor. If that Commercial Contributor then makes performance claims, or offers warranties related to Product X, those performance claims and warranties are such Commercial Contributor's responsibility alone. Under this section, the Commercial Contributor would have to defend claims against the other Contributors related to those performance claims and warranties, and if a court requires any other Contributor to pay any damages as a result, the Commercial Contributor must pay those damages.

5. NO WARRANTY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, THE PROGRAM IS PROVIDED ON AN "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, EITHER EXPRESS OR IMPLIED INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OR CONDITIONS OF TITLE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each Recipient is solely responsible for determining
the appropriateness of using
and distributing the Program and assumes all risks associated with its

exercise of rights under this Agreement , including but not limited to the risks and costs of program errors, compliance with applicable laws, damage to or loss of data, programs or equipment, and unavailability or interruption of operations.

6. DISCLAIMER OF LIABILITY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, NEITHER RECIPIENT NOR ANY CONTRIBUTORS SHALL HAVE ANY LIABILITY FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION LOST PROFITS), HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OR DISTRIBUTION OF THE PROGRAM OR THE EXERCISE OF ANY RIGHTS GRANTED HEREUNDER, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. GENERAL

If any provision of this Agreement is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this Agreement, and without further action by the parties hereto, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

If Recipient institutes patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Program itself (excluding combinations of the Program with other software or hardware) infringes such Recipient's patent(s), then such Recipient's rights granted under Section 2(b) shall terminate as of the date such litigation is filed.

All Recipient's rights under this Agreement shall terminate if it fails to comply with any of the material terms or conditions of this Agreement and does not cure such failure in a reasonable period of time after becoming aware of such noncompliance. If all Recipient's rights under this Agreement terminate, Recipient agrees to cease use and distribution of the Program as soon as reasonably practicable. However, Recipient's obligations under this Agreement and any licenses granted by Recipient relating to the Program shall continue and survive.

Everyone is permitted to copy and distribute copies of this Agreement, but in order to avoid inconsistency the Agreement is copyrighted and may only be modified in the following manner. The Agreement Steward reserves the right to publish new versions (including revisions) of this Agreement from time to time. No one other than the Agreement Steward has the right to modify this Agreement. The Eclipse Foundation is the initial Agreement Steward. The Eclipse Foundation may assign the responsibility to serve as the Agreement

Steward to a suitable separate entity. Each new version of the Agreement will be given a distinguishing version number. The Program (including Contributions) may always be distributed subject to the version of the Agreement under which it was received. In addition, after
a new version of the
Agreement is published, Contributor may elect to distribute the Program (including its Contributions) under the new version. Except as expressly stated in Sections 2(a) and 2(b) above, Recipient receives no rights or licenses to the intellectual property of any Contributor under this Agreement, whether expressly, by implication, estoppel or otherwise. All rights in the Program not expressly granted under this Agreement are reserved.

This Agreement is governed by the laws of the State of New York and the intellectual property laws of the United States of America. No party to this Agreement will bring a legal action under this Agreement more than one year after the cause of action arose. Each party waives its rights to a jury trial in any resulting litigation.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,

including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative
Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside

or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions)
on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited
to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache
License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS
OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

==========

Jetty Web Container
Copyright 1995-2018 Mort Bay Consulting Pty Ltd.

==========

The Jetty Web Container is Copyright Mort Bay Consulting Pty Ltd
unless otherwise noted.

Jetty is dual licensed under both

* The Apache 2.0 License
  http://www.apache.org/licenses/LICENSE-2.0.html

    and

* The Eclipse Public 1.0 License
  http://www.eclipse.org/legal/epl-v10.html

Jetty may be distributed under either license.

Eclipse

The following artifacts are EPL.
* org.eclipse.jetty.orbit:org.eclipse.jdt.core

The following artifacts are EPL and ASL2.
* org.eclipse.jetty.orbit:javax.security.auth.message

The following artifacts are EPL and CDDL 1.0.
* org.eclipse.jetty.orbit:javax.mail.glassfish

Oracle

The following artifacts are CDDL + GPLv2 with classpath exception.
https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

* javax.servlet:javax.servlet-api
 * javax.annotation:javax.annotation-api
* javax.transaction:javax.transaction-api
* javax.websocket:javax.websocket-api

Oracle OpenJDK

If ALPN is used to negotiate HTTP/2 connections, then the following
artifacts may be included in the distribution or downloaded when ALPN
module is selected.

* java.sun.security.ssl

These artifacts replace/modify OpenJDK classes. The modifications
are hosted at github and both modified and original are under GPL v2 with
classpath exceptions.

http://openjdk.java.net/legal/gplv2+ce.html

OW2

The following artifacts are licensed by the OW2 Foundation according to the
terms of http://asm.ow2.org/license.html

org.ow2.asm:asm-commons
org.ow2.asm:asm

Apache

The following artifacts are ASL2 licensed.

org.apache.taglibs:taglibs-standard-spec
org.apache.taglibs:taglibs-standard-impl

MortBay

The following artifacts are ASL2 licensed. Based on selected classes from
following Apache Tomcat jars, all ASL2
licensed.

org.mortbay.jasper:apache-jsp
org.apache.tomcat:tomcat-jasper
org.apache.tomcat:tomcat-juli
org.apache.tomcat:tomcat-jsp-api
org.apache.tomcat:tomcat-el-api
org.apache.tomcat:tomcat-jasper-el
org.apache.tomcat:tomcat-api
org.apache.tomcat:tomcat-util-scan
org.apache.tomcat:tomcat-util

org.mortbay.jasper:apache-el
org.apache.tomcat:tomcat-jasper-el
org.apache.tomcat:tomcat-el-api

Mortbay

The following artifacts are CDDL + GPLv2 with classpath exception.

https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

org.eclipse.jetty.toolchain:jetty-schemas

Assorted

The UnixCrypt.java code implements the one way cryptography used by
Unix systems for simple password protection. Copyright 1996 Aki Yoshida,
modified April 2001 by Iris Van den Broeke, Daniel Deville.
Permission to use, copy, modify and distribute UnixCrypt
for non-commercial or commercial purposes and without fee is
granted provided that the copyright notice appears in all
 copies.

1.170 jetty-client 9.4.18.v20190429

1.170.1 Available under license :

This program and the accompanying materials are made available under the
terms of the Eclipse Public License 2.0 which is available at
http://www.eclipse.org/legal/epl-2.0, or the Apache Software License
2.0 which is available at https://www.apache.org/licenses/LICENSE-2.0.

Eclipse Public License - v 1.0

THE ACCOMPANYING PROGRAM IS PROVIDED UNDER THE TERMS OF THIS ECLIPSE PUBLIC LICENSE ("AGREEMENT"). ANY USE, REPRODUCTION OR DISTRIBUTION OF THE PROGRAM CONSTITUTES RECIPIENT'S ACCEPTANCE OF THIS AGREEMENT.

1. DEFINITIONS

"Contribution" means:

a) in the case of the initial Contributor, the initial code and documentation
  distributed under this Agreement, and
b) in the case of each subsequent Contributor:
   i) changes to the Program, and
  ii) additions to the Program;

  where such changes and/or additions to the Program originate from and are
  distributed by that particular Contributor. A Contribution 'originates'
  from a Contributor if it was added to the Program by such
 Contributor
  itself or anyone acting on such Contributor's behalf. Contributions do not

include additions to the Program which: (i) are separate modules of software distributed in conjunction with the Program under their own license agreement, and (ii) are not derivative works of the Program.

"Contributor" means any person or entity that distributes the Program.

"Licensed Patents" mean patent claims licensable by a Contributor which are necessarily infringed by the use or sale of its Contribution alone or when combined with the Program.

"Program" means the Contributions distributed in accordance with this Agreement.

"Recipient" means anyone who receives the Program under this Agreement, including all Contributors.

2. GRANT OF RIGHTS

a) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free copyright license to reproduce, prepare derivative works of, publicly display, publicly perform,
distribute and sublicense the Contribution of such Contributor, if any, and such derivative works, in source code and object code form.

b) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free patent license under Licensed Patents to make, use, sell, offer to sell, import and otherwise transfer the Contribution of such Contributor, if any, in source code and object code form. This patent license shall apply to the combination of the Contribution and the Program if, at the time the Contribution is added by the Contributor, such addition of the Contribution causes such combination to be covered by the Licensed Patents. The patent license shall not apply to any other combinations which include the Contribution. No hardware per se is licensed hereunder.

c) Recipient understands that although each Contributor grants the licenses to its Contributions set forth herein,
no assurances are provided by any
Contributor that the Program does not infringe the patent or other intellectual property rights of any other entity. Each Contributor disclaims any liability to Recipient for claims brought by any other entity based on infringement of intellectual property rights or otherwise. As a condition to exercising the rights and licenses granted hereunder, each Recipient hereby assumes sole responsibility to secure any other intellectual property rights needed, if any. For example, if a third party patent license is required to allow Recipient to distribute the Program, it is Recipient's responsibility to acquire that license before distributing the Program.

d) Each Contributor represents that to its knowledge it has sufficient copyright rights in its Contribution, if any, to grant the copyright

license set forth in this Agreement.

3. REQUIREMENTS

A Contributor may choose to distribute the Program
in object code form under
its own license agreement, provided that:

a) it complies with the terms and conditions of this Agreement; and
b) its license agreement:
i) effectively disclaims on behalf of all Contributors all warranties
and conditions, express and implied, including warranties or
conditions of title and non-infringement, and implied warranties or
conditions of merchantability and fitness for a particular purpose;
ii) effectively excludes on behalf of all Contributors all liability for
damages, including direct, indirect, special, incidental and
consequential damages, such as lost profits;
iii) states that any provisions which differ from this Agreement are
offered by that Contributor alone and not by any other party; and
iv) states that source code for the Program is available from such
Contributor, and informs licensees how to obtain it in a reasonable
manner on or through a
medium customarily used for software exchange.

When the Program is made available in source code form:

a) it must be made available under this Agreement; and
b) a copy of this Agreement must be included with each copy of the Program.
Contributors may not remove or alter any copyright notices contained
within the Program.

Each Contributor must identify itself as the originator of its Contribution,
if
any, in a manner that reasonably allows subsequent Recipients to identify the
originator of the Contribution.

4. COMMERCIAL DISTRIBUTION

Commercial distributors of software may accept certain responsibilities with
respect to end users, business partners and the like. While this license is
intended to facilitate the commercial use of the Program, the Contributor who
includes the Program in a commercial product offering should do so in a manner
which does not create potential liability for other Contributors. Therefore,
if a Contributor includes the Program in a commercial
product offering, such
Contributor ("Commercial Contributor") hereby agrees to defend and indemnify
every other Contributor ("Indemnified Contributor") against any losses,
damages and costs (collectively "Losses") arising from claims, lawsuits and

other legal actions brought by a third party against the Indemnified Contributor to the extent caused by the acts or omissions of such Commercial Contributor in connection with its distribution of the Program in a commercial product offering. The obligations in this section do not apply to any claims or Losses relating to any actual or alleged intellectual property infringement. In order to qualify, an Indemnified Contributor must:
a) promptly notify the Commercial Contributor in writing of such claim, and
b) allow the Commercial Contributor to control, and cooperate with the Commercial Contributor in, the defense and any related settlement negotiations. The Indemnified Contributor may participate in any such claim at its own expense.

For example,
a Contributor might include the Program in a commercial product offering, Product X. That Contributor is then a Commercial Contributor. If that Commercial Contributor then makes performance claims, or offers warranties related to Product X, those performance claims and warranties are such Commercial Contributor's responsibility alone. Under this section, the Commercial Contributor would have to defend claims against the other Contributors related to those performance claims and warranties, and if a court requires any other Contributor to pay any damages as a result, the Commercial Contributor must pay those damages.

5. NO WARRANTY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, THE PROGRAM IS PROVIDED ON AN "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, EITHER EXPRESS OR IMPLIED INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OR CONDITIONS OF TITLE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each Recipient is solely responsible for determining
the appropriateness of using
and distributing the Program and assumes all risks associated with its exercise of rights under this Agreement , including but not limited to the risks and costs of program errors, compliance with applicable laws, damage to or loss of data, programs or equipment, and unavailability or interruption of operations.

6. DISCLAIMER OF LIABILITY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, NEITHER RECIPIENT NOR ANY CONTRIBUTORS SHALL HAVE ANY LIABILITY FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION LOST PROFITS), HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OR DISTRIBUTION OF THE PROGRAM OR THE EXERCISE OF ANY RIGHTS GRANTED HEREUNDER, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. GENERAL

If any provision of this Agreement is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this Agreement, and without further action by the parties hereto, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

If Recipient institutes patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Program itself (excluding combinations of the Program with other software or hardware) infringes such Recipient's patent(s), then such Recipient's rights granted under Section 2(b) shall terminate as of the date such litigation is filed.

All Recipient's rights under this Agreement shall terminate if it fails to comply with any of the material terms or conditions of this Agreement and does not cure such failure in a reasonable period of time after becoming aware of such noncompliance. If all Recipient's rights under this Agreement terminate, Recipient agrees to cease use and distribution of the Program as soon as reasonably practicable. However, Recipient's obligations under this Agreement and any licenses granted by Recipient relating to the Program shall continue and survive.

Everyone is permitted to copy and distribute copies of this Agreement, but in order to avoid inconsistency the Agreement is copyrighted and may only be modified in the following manner. The Agreement Steward reserves the right to publish new versions (including revisions) of this Agreement from time to time. No one other than the Agreement Steward has the right to modify this Agreement. The Eclipse Foundation is the initial Agreement Steward. The Eclipse Foundation may assign the responsibility to serve as the Agreement Steward to a suitable separate entity. Each new version of the Agreement will be given a distinguishing version number. The Program (including Contributions) may always be distributed subject to the version of the Agreement under which it was received. In addition, after a new version of the Agreement is published, Contributor may elect to distribute the Program (including its Contributions) under the new version. Except as expressly stated in Sections 2(a) and 2(b) above, Recipient receives no rights or licenses to the intellectual property of any Contributor under this Agreement, whether expressly, by implication, estoppel or otherwise. All rights in the Program not expressly granted under this Agreement are reserved.

This Agreement is governed by the laws of the State of New York and the intellectual property laws of the United States of America. No party to this Agreement will bring a legal action under this Agreement more than one year after the cause of action arose. Each party waives its rights to a jury trial in

any resulting litigation.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes

of this License, Derivative Works shall not include works
that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously
marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the

Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative
Works; within the Source form or
documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed

with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions)
on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited
to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache
License to your work.

To apply the Apache License to your work, attach the following

boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS
OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

==========

Jetty Web Container
Copyright 1995-2018 Mort Bay Consulting Pty Ltd.

==========

The Jetty Web Container is Copyright Mort Bay Consulting Pty Ltd
unless otherwise noted.

Jetty is dual licensed under both

* The Apache 2.0 License
http://www.apache.org/licenses/LICENSE-2.0.html

and

* The Eclipse Public 1.0 License
http://www.eclipse.org/legal/epl-v10.html

Jetty may be distributed under either license.

Eclipse

The following artifacts are EPL.
* org.eclipse.jetty.orbit:org.eclipse.jdt.core

The following artifacts are EPL and ASL2.
* org.eclipse.jetty.orbit:javax.security.auth.message

The following artifacts are EPL and CDDL 1.0.
* org.eclipse.jetty.orbit:javax.mail.glassfish

Oracle

The following artifacts are CDDL + GPLv2 with classpath exception.
https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

* javax.servlet:javax.servlet-api
 * javax.annotation:javax.annotation-api
* javax.transaction:javax.transaction-api
* javax.websocket:javax.websocket-api

Oracle OpenJDK

If ALPN is used to negotiate HTTP/2 connections, then the following
artifacts may be included in the distribution or downloaded when ALPN
module is selected.

* java.sun.security.ssl

These artifacts replace/modify OpenJDK classes. The modifications
are hosted at github and both modified and original are under GPL v2 with
classpath exceptions.
http://openjdk.java.net/legal/gplv2+ce.html

OW2

The following artifacts are licensed by the OW2 Foundation according to the
terms of http://asm.ow2.org/license.html

org.ow2.asm:asm-commons
org.ow2.asm:asm

Apache

The following artifacts are ASL2 licensed.

org.apache.taglibs:taglibs-standard-spec
org.apache.taglibs:taglibs-standard-impl

MortBay

The following artifacts are ASL2 licensed. Based on selected classes from
following Apache Tomcat jars, all ASL2
licensed.

org.mortbay.jasper:apache-jsp
org.apache.tomcat:tomcat-jasper
org.apache.tomcat:tomcat-juli
org.apache.tomcat:tomcat-jsp-api
org.apache.tomcat:tomcat-el-api
org.apache.tomcat:tomcat-jasper-el
org.apache.tomcat:tomcat-api
org.apache.tomcat:tomcat-util-scan
org.apache.tomcat:tomcat-util

org.mortbay.jasper:apache-el
org.apache.tomcat:tomcat-jasper-el
org.apache.tomcat:tomcat-el-api

Mortbay

The following artifacts are CDDL + GPLv2 with classpath exception.

https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

org.eclipse.jetty.toolchain:jetty-schemas

Assorted

The UnixCrypt.java code implements the one way cryptography used by
Unix systems for simple password protection. Copyright 1996 Aki Yoshida,
modified April 2001 by Iris Van den Broeke, Daniel Deville.
Permission to use, copy, modify and distribute UnixCrypt
for non-commercial or commercial purposes and without fee is
granted provided that the copyright notice appears in all
copies.

1.171 swagger-core 1.5.22

1.172 swagger-jaxrs 1.5.22

1.173 babel-polyfill 6.26.0

1.174 opentracing-spring-web-autoconfigure 0.3.2

1.174.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form
shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as

indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely
link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean
Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and

You must cause any modified files to carry prominent notices stating that You changed the files; and

You must retain, in the Source form of any Derivative Works that You distribute,
all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum
to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.
You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.
5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use
the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor
harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.175 opentracing-api 0.31.0

1.175.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form
shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely
link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean

Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and

You must cause any modified files to carry prominent notices stating that You changed the files; and

You must retain, in the Source form of any Derivative Works that You distribute,
all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum
to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.
You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.
5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use
the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor
harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.176 opentracing-tracerresolver 0.1.4

1.176.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form

shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely
link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean
Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and

You must cause any modified files to carry prominent notices stating that You changed the files; and

You must retain, in the Source form of any Derivative Works that You distribute,
all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum
to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.
You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.
5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use
the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or

rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor
harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.177 opentracing-spring-web 0.3.2

1.177.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form
shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely
link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the

Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean
Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and

You must cause any modified files to carry prominent notices stating that You changed the files; and

You must retain, in the Source form of any Derivative Works that You distribute,
all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum
to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.
You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use
the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor
harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.178 esprima 3.1.3

1.178.1 Available under license :

BSD-2-Clause
Copyright JS Foundation and other contributors, https://js.foundation/

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL <COPYRIGHT HOLDER> BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES

(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.179 postcss 6.0.23

1.179.1 Available under license :

The MIT License (MIT)

Copyright 2013 Andrey Sitnik <andrey@sitnik.ru>

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS
FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR
COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER
IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.180 c3p0 0.9.1.1

1.180.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be

introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and

is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the
reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU

operating system, as well as its variant, the GNU/Linux operating

system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does

and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in

themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution
of derivative or
collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for

that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties

are not
compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the
Library even though the source code is not.
Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference

directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license

restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided
that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However,
parties who have received copies,
or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library

subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status
of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR
REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that

everyone can redistribute and change. You can do so by permitting
redistribution under these terms (or, alternatively, under the terms of the
ordinary General Public License).

To apply these terms, attach the following notices to the library. It is
safest to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least the
"copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See
the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library 'Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.181 jsqlparser 2.1

1.181.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who
decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these

rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link other code with the library, you must provide
complete object files to the recipients, so that they can relink them
with the library after making changes to the library and recompiling
it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the
library, and (2) we offer you this license, which gives you legal
permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that
there is no warranty for the free library. Also, if the library is
modified by someone else and passed on, the recipients should know
that what they have is not the original version, so that the original
author's reputation will not be affected by problems that might be
introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot
effectively restrict the users of a free program by obtaining a
restrictive license from a patent holder. Therefore, we insist that
any patent license obtained for a version of the library must be
consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the
ordinary GNU General Public License. This license, the GNU Lesser
General Public License, applies to certain designated libraries, and
is quite different from the ordinary General Public License. We use
this license for certain libraries in order to permit linking those
libraries into non-free programs.

When a program is linked with a library, whether statically or using
a shared library, the combination of the two is legally speaking a
combined work, a derivative of the original library. The ordinary
General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General
Public License permits more lax criteria for linking other code with
the library.

We call this license the "Lesser" General Public License because it

does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the

terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can
be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the
ordinary GNU General Public
License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute
the object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6,
whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if
the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law
if you do not accept this License. Therefore, by
modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do
not
excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution
system which is
implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED
ABOVE, BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most
effectively
convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston,
MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a

copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a

cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with

the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

```
/*-
* #%L
* JSQLParser library
* %%
* Copyright (C) 2004 - 2019 JSQLParser
* %%
* Dual licensed under GNU LGPL 2.1 or Apache License 2.0
* #L%
*/
```

1.182 reactive-streams 1.0.3

1.182.1 Available under license :

Public Domain

1.183 java-jwt 3.8.3

1.183.1 Available under license :

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.184 javax-json 1.1.4

1.184.1 Available under license :

COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL)
Version 1.0

*

1. Definitions.
   o

   1.1. ?Contributor? means each individual or entity that creates or contributes to the creation of Modifications.

   o

   1.2. ?Contributor Version? means the combination of the Original Software, prior Modifications used by a Contributor (if any), and the Modifications made by that particular Contributor.
   o

   1.3. ?Covered Software? means (a) the Original Software, or (b) Modifications, or (c) the combination of files containing Original Software with files containing Modifications, in each case including portions thereof.
   o

1.4. ?Executable? means the Covered Software in any form other than Source Code.

o

1.5. ?Initial Developer? means the individual or entity that first makes Original Software available under this License.

o

1.6. ?Larger Work? means a work which combines Covered Software or portions thereof with code not governed by the terms of this License.

o

1.7. ?License? means this document.

o

1.8. ?Licensable? means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently acquired, any and all of the rights conveyed herein.

o

1.9. ?Modifications? means the Source Code and Executable form of any of the following:

+

A. Any file that results from an addition to, deletion from or modification of the contents of a file containing Original Software or previous Modifications;

+

B. Any new file that contains any part of the Original Software or previous Modification; or

+

C. Any new file that is contributed
or otherwise made available under the terms of this License.

o

1.10. ?Original Software? means the Source Code and Executable form of computer software code that is originally released under this License.

o

1.11. ?Patent Claims? means any patent claim(s), now owned or hereafter acquired, including without limitation, method, process, and apparatus claims, in any patent Licensable by grantor.

o

1.12. ?Source Code? means (a) the common form of computer software code in which modifications are made and (b) associated documentation included in or with such code.

o

1.13. ?You? (or ?Your?) means an individual or a legal entity exercising rights under, and complying with all of the terms of, this License. For legal entities, ?You? includes any entity which controls, is controlled by, or is under common control with You. For purposes of this definition, ?control?

means (a) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (b) ownership of more than fifty percent (50%) of the outstanding shares or beneficial ownership of such entity.

*

2. License Grants.

o

2.1. The Initial Developer Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, the Initial Developer hereby grants You a world-wide, royalty-free, non-exclusive license:

+

(a) under intellectual property rights (other than patent or trademark) Licensable by Initial Developer, to use, reproduce, modify, display, perform, sublicense and distribute the Original Software (or portions thereof), with or without Modifications, and/or as part of a Larger Work; and

+

(b) under Patent Claims infringed by
the making, using or selling of Original Software, to make, have made, use, practice, sell, and offer for sale, and/or otherwise dispose of the Original Software (or portions thereof).

+

(c) The licenses granted in Sections 2.1(a) and (b) are effective on the date Initial Developer first distributes or otherwise makes the Original Software available to a third party under the terms of this License.

+

(d) Notwithstanding Section 2.1(b) above, no patent license is granted: (1) for code that You delete from the Original Software, or (2) for infringements caused by: (i) the modification of the Original Software, or (ii) the combination of the Original Software with other software or devices.

o

2.2. Contributor Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, each Contributor hereby
grants You a world-wide, royalty-free, non-exclusive license:

+

(a) under intellectual property rights (other than patent or trademark) Licensable by Contributor to use, reproduce, modify, display, perform, sublicense and distribute the Modifications created by such Contributor (or portions thereof), either on an unmodified basis, with other Modifications, as Covered Software and/or as part of a Larger Work; and

+

(b) under Patent Claims infringed by the making, using, or selling of Modifications made by that Contributor either alone and/or in combination with its Contributor Version (or portions of such combination), to

make, use, sell, offer for sale, have made, and/or otherwise dispose of: (1) Modifications made by that Contributor (or portions thereof); and (2) the combination of Modifications made by that Contributor with its Contributor Version (or portions of such combination).

+

(c) The licenses granted in Sections 2.2(a) and 2.2(b) are effective on the date Contributor first distributes or otherwise makes the Modifications available to a third party.

+

(d) Notwithstanding Section 2.2(b) above, no patent license is granted: (1) for any code that Contributor has deleted from the Contributor Version; (2) for infringements caused by: (i) third party modifications of Contributor Version, or (ii) the combination of Modifications made by that Contributor with other software (except as part of the Contributor Version) or other devices; or (3) under Patent Claims infringed by Covered Software in the absence of Modifications made by that Contributor.

*

3. Distribution Obligations.

o

3.1. Availability of Source Code.

Any Covered Software that You distribute or otherwise make available in Executable form must also be made available

in Source Code form and that Source Code form must be distributed only under the terms of this License. You must include a copy of this License with every copy of the Source Code form of the Covered Software You distribute or otherwise make available. You must inform recipients of any such Covered Software in Executable form as to how they can obtain such Covered Software in Source Code form in a reasonable manner on or through a medium customarily used for software exchange.

o

3.2. Modifications.

The Modifications that You create or to which You contribute are governed by the terms of this License. You represent that You believe Your Modifications are Your original creation(s) and/or You have sufficient rights to grant the rights conveyed by this License.

o

3.3. Required Notices.

You must include a notice in each of Your Modifications that identifies You as the Contributor of the Modification. You may not remove or alter any copyright, patent or trademark notices contained within the Covered Software, or any notices of licensing or any descriptive text giving attribution to any Contributor or the Initial Developer.

o

3.4. Application of Additional Terms.

You may not offer or impose any terms on any Covered Software in Source Code form that alters or restricts the applicable version of this License or the recipients? rights hereunder. You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, you may do so only on Your own behalf, and not on behalf of the Initial Developer or any Contributor. You must make it absolutely clear that any such warranty, support, indemnity or liability obligation is offered by You alone, and You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of warranty, support, indemnity or liability terms You offer.

o

3.5. Distribution of Executable Versions.

You may distribute the Executable form of the Covered Software under the terms of this License or under the terms of a license of Your choice, which may contain terms different from this License, provided that You are in compliance with the terms of this License and that the license for the Executable form does not attempt to limit or alter the recipient?s rights in the Source Code form from the rights set forth in this License. If You distribute the Covered Software in Executable form under a different license, You must make it absolutely clear that any terms which differ from this License are offered by You alone, not by the Initial Developer or Contributor. You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of any such terms You offer.

o

3.6. Larger Works.

You may create a Larger Work by combining Covered Software with other code not governed by the terms of this License and distribute the Larger Work as a single product. In such a case, You must make sure the requirements of this License are fulfilled for the Covered Software.

*

4. Versions of the License.

o

4.1. New Versions.

Sun Microsystems, Inc. is the initial license steward and may publish revised and/or new versions of this License from time to time. Each version will be given a distinguishing version number. Except as provided in Section 4.3, no one other than the license steward has the right to modify this License.

o

4.2. Effect of New Versions.

You may always continue to use, distribute or otherwise make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. If the Initial Developer includes a notice in the Original Software prohibiting it from being distributed or otherwise made available under any subsequent version of the License, You must distribute and make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. Otherwise, You may also choose to use, distribute or otherwise make the Covered Software available under the terms of any subsequent version of the License published by the license steward.

o

4.3. Modified Versions.

When You are an Initial Developer and You want to create a new license for Your Original Software, You may create and use a modified version of this License if You: (a) rename the license and remove any references to the name of the license steward (except to
note that the license differs from this License); and (b) otherwise make it clear that the license contains terms which differ from this License.

*

5. DISCLAIMER OF WARRANTY.

COVERED SOFTWARE IS PROVIDED UNDER THIS LICENSE ON AN ?AS IS? BASIS, WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES THAT THE COVERED SOFTWARE IS FREE OF DEFECTS, MERCHANTABLE, FIT FOR A PARTICULAR PURPOSE OR NON-INFRINGING. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE COVERED SOFTWARE IS WITH YOU. SHOULD ANY COVERED SOFTWARE PROVE DEFECTIVE IN ANY RESPECT, YOU (NOT THE INITIAL DEVELOPER OR ANY OTHER CONTRIBUTOR) ASSUME THE COST OF ANY NECESSARY SERVICING, REPAIR OR CORRECTION. THIS DISCLAIMER OF WARRANTY CONSTITUTES AN ESSENTIAL PART OF THIS LICENSE. NO USE OF ANY COVERED SOFTWARE IS AUTHORIZED HEREUNDER EXCEPT UNDER THIS DISCLAIMER.

*

6. TERMINATION.

o

6.1. This
License and the rights granted hereunder will terminate automatically if You fail to comply with terms herein and fail to cure such breach within 30 days of becoming aware of the breach. Provisions which, by their nature, must remain in effect beyond the termination of this License shall survive.

o

6.2. If You assert a patent infringement claim (excluding declaratory judgment actions) against Initial Developer or a Contributor (the Initial Developer or Contributor against whom You assert such claim is referred to as ?Participant?) alleging that the Participant Software (meaning the Contributor Version where the Participant is a Contributor or the Original Software where the Participant is the Initial Developer) directly or indirectly infringes any patent, then any and all rights granted directly or indirectly to You by such Participant, the Initial Developer (if the Initial Developer is not the Participant) and all Contributors under Sections 2.1 and/or
2.2 of this License shall, upon 60 days notice from Participant terminate prospectively and automatically at the expiration of such 60 day notice period, unless if within such 60 day period You withdraw Your claim with respect to the Participant Software against such Participant either unilaterally or pursuant to a written agreement with Participant.

o

6.3. In the event of termination under Sections 6.1 or 6.2 above, all end user licenses that have been validly granted by You or any distributor hereunder prior to termination (excluding licenses granted to You by any distributor) shall survive termination.

*

7. LIMITATION OF LIABILITY.

UNDER NO CIRCUMSTANCES AND UNDER NO LEGAL THEORY, WHETHER TORT (INCLUDING NEGLIGENCE), CONTRACT, OR OTHERWISE, SHALL YOU, THE INITIAL DEVELOPER, ANY OTHER CONTRIBUTOR, OR ANY DISTRIBUTOR OF COVERED SOFTWARE, OR ANY SUPPLIER OF ANY OF SUCH PARTIES, BE LIABLE TO ANY PERSON FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY CHARACTER INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOST PROFITS, LOSS OF GOODWILL, WORK STOPPAGE, COMPUTER FAILURE OR MALFUNCTION, OR ANY AND ALL OTHER COMMERCIAL DAMAGES OR LOSSES, EVEN IF SUCH PARTY SHALL HAVE BEEN INFORMED OF THE POSSIBILITY OF SUCH DAMAGES. THIS LIMITATION OF LIABILITY SHALL NOT APPLY TO LIABILITY FOR DEATH OR PERSONAL INJURY RESULTING FROM SUCH PARTY?S NEGLIGENCE TO THE EXTENT APPLICABLE LAW PROHIBITS SUCH LIMITATION. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS EXCLUSION AND LIMITATION MAY NOT APPLY TO YOU.

*

8. U.S. GOVERNMENT END USERS.

The Covered Software is a ?commercial item,? as that term is defined in 48 C.F.R. 2.101 (Oct. 1995), consisting of ?commercial computer software? (as that term is defined at 48 C.F.R. ? 252.227-7014(a)(1)) and ?commercial computer software documentation? as such terms are used in 48 C.F.R. 12.212 (Sept. 1995). Consistent with 48 C.F.R. 12.212 and 48 C.F.R. 227.7202-1 through 227.7202-4 (June 1995), all U.S. Government End Users acquire Covered Software with only those rights set forth herein. This U.S. Government Rights clause is in lieu of, and supersedes, any other FAR, DFAR, or other clause or provision that addresses Government rights in computer software under this License.

*

9. MISCELLANEOUS.

This License represents the complete agreement concerning subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable. This License shall be governed by the law of the jurisdiction specified in a notice contained within the Original Software (except to the extent applicable law, if any, provides otherwise), excluding such jurisdiction?s conflict-of-law provisions. Any litigation relating to this License shall be subject to the jurisdiction of the courts located in the jurisdiction and venue specified in a notice contained within the Original Software, with the losing party responsible for costs, including, without limitation, court costs and reasonable attorneys? fees and expenses. The application of the United Nations Convention on Contracts for the International Sale of Goods is expressly excluded. Any law or regulation which provides that the language of a contract shall be construed against the drafter shall not apply to this License. You agree that You alone are responsible for compliance with the United States export administration regulations (and the export control laws and regulation of any other countries) when You use, distribute or otherwise make available any Covered Software.

*

10. RESPONSIBILITY FOR CLAIMS.

As between Initial Developer and the Contributors, each party is responsible for claims and damages arising, directly or indirectly, out of its utilization of
rights under this License and You agree to work with Initial Developer and Contributors to distribute such responsibility on an equitable basis. Nothing herein is intended or shall be deemed to constitute any admission of liability.

1.185 justify 0.17.0

1.185.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form
shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely
link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean
Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and

You must cause any modified files to carry prominent notices stating that You changed the files; and

You must retain, in the Source form of any Derivative Works that You distribute,
all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum

to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.
You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.
5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use
the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor
harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.186 jsesc 0.5.0

1.186.1 Available under license :

Copyright Mathias Bynens <http://mathiasbynens.be/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.187 gulp 4.0.2

1.187.1 Available under license :

The MIT License (MIT)

Copyright (c) 2013-2018 Blaine Bublitz <blaine.bublitz@gmail.com>, Eric Schoffstall <yo@contra.io> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.188 mongo-jackson-codec 3.2.2__0.5

1.188.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the

direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding

those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise,

unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright 2014 Yann Le Moigne

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.189 junit-platform-commons 1.1.0

1.189.1 Available under license :

Eclipse Public License - v 2.0
==========

THE ACCOMPANYING PROGRAM IS PROVIDED UNDER THE TERMS OF THIS ECLIPSE PUBLIC LICENSE (AGREEMENT). ANY USE, REPRODUCTION OR DISTRIBUTION OF THE PROGRAM CONSTITUTES RECIPIENT'S ACCEPTANCE OF THIS AGREEMENT.

1. Definitions

Contribution means:
* **a)** in the case of the initial Contributor, the initial content Distributed under this Agreement, and
* **b)** in the case of each subsequent Contributor:
 * **i)** changes to the Program, and
 * **ii)** additions to the Program;
where such changes and/or additions to the Program originate from and are Distributed by that particular Contributor. A Contribution originates from a Contributor if it was added to the Program by such Contributor itself or anyone acting on such Contributor's behalf. Contributions do not include changes or additions to the Program that are not Modified Works.

Contributor means any person or entity that Distributes the Program.

Licensed Patents mean patent
 claims licensable by a Contributor which are necessarily infringed by the use or sale of its Contribution alone or when combined with the Program.

Program means the Contributions Distributed in accordance with this Agreement.

Recipient means anyone who receives the Program under this Agreement or any Secondary License (as applicable), including Contributors.

Derivative Works shall mean any work, whether in Source Code or other form, that is based on (or derived from) the Program and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship.

Modified Works shall mean any work in Source Code or other form that results from an addition to, deletion from, or modification of the contents of the Program, including, for purposes of clarity any new file in Source Code form that contains any contents of the Program. Modified Works shall not include works that contain only declarations, interfaces, types, classes,
 structures, or files of the Program solely in each case in order to link to, bind by name, or subclass the Program or Modified Works thereof.

Distribute means the acts of **a)** distributing or **b)** making available in any manner that enables the transfer of a copy.

Source Code means the form of a Program preferred for making modifications, including but not limited to software source code, documentation source, and configuration files.

Secondary License means either the GNU General Public License, Version 2.0, or any later versions of that license, including any exceptions or additional permissions as identified by the initial Contributor.

2. Grant of Rights

a) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, Distribute and sublicense the Contribution of such Contributor, if any, and such Derivative Works.

b) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free patent license under Licensed Patents to make, use, sell, offer to sell, import and otherwise transfer the Contribution of such Contributor, if any, in Source Code or other form. This patent license shall apply to the combination of the Contribution and the Program if, at the time the Contribution is added by the Contributor, such addition of the Contribution causes such combination to be covered by the Licensed Patents. The patent license shall not apply to any other combinations which include the Contribution. No hardware per se is licensed hereunder.

c) Recipient understands that although each Contributor grants the licenses to its Contributions set forth herein, no assurances are provided by any Contributor that the Program does not infringe the patent or other intellectual property rights of any other entity. Each Contributor disclaims any liability to Recipient for claims brought by any other entity based on infringement of intellectual property rights or otherwise. As a condition to exercising the rights and licenses granted hereunder, each Recipient hereby assumes sole responsibility to secure any other intellectual property rights needed, if any. For example, if a third party patent license is required to allow Recipient to Distribute the Program, it is Recipient's responsibility to acquire that license before distributing the Program.

d) Each Contributor represents that to its knowledge it has sufficient copyright rights in its Contribution, if any, to grant the copyright license set forth in this Agreement.

e) Notwithstanding the terms of any Secondary License, no Contributor makes additional grants to any Recipient (other than those set forth in this Agreement) as a result of such Recipient's receipt of the Program under the terms of a Secondary License (if permitted under the terms of Section 3).

3. Requirements

3.1 If a Contributor Distributes the Program in any form, then:

* **a)** the Program must also be made available as Source Code, in accordance with section 3.2, and the Contributor must accompany the Program with a statement that the Source Code for the Program is available under this Agreement, and informs Recipients how to obtain it in a reasonable manner on or through a medium customarily used for software exchange; and

* **b)** the Contributor may Distribute the Program under a license different than this Agreement, provided that

such license:
 * **i)** effectively disclaims on behalf of all other Contributors all warranties and conditions, express and implied, including warranties or conditions of title and non-infringement, and implied warranties or conditions of merchantability and fitness for a particular purpose;
 * **ii)** effectively excludes on behalf of all other Contributors all liability for damages, including direct, indirect, special, incidental
 and consequential damages, such as lost profits;
 * **iii)** does not attempt to limit or alter the recipients' rights in the Source Code under section 3.2; and
 * **iv)** requires any subsequent distribution of the Program by any party to be under a license that satisfies the requirements of this section 3.

3.2 When the Program is Distributed as Source Code:

* **a)** it must be made available under this Agreement, or if the Program **(i)** is combined with other material in a separate file or files made available under a Secondary License, and **(ii)** the initial Contributor attached to the Source Code the notice described in Exhibit A of this Agreement, then the Program may be made available under the terms of such Secondary Licenses, and
* **b)** a copy of this Agreement must be included with each copy of the Program.

3.3 Contributors may not remove or alter any copyright, patent, trademark, attribution notices, disclaimers of warranty, or limitations of liability (notices)
 contained within the Program from any copy of the Program which they Distribute, provided that Contributors may add their own appropriate notices.

4. Commercial Distribution

Commercial distributors of software may accept certain responsibilities with respect to end users, business partners and the like. While this license is intended to facilitate the commercial use of the Program, the Contributor who includes the Program in a commercial product offering should do so in a manner which does not create potential liability for other Contributors. Therefore, if a Contributor includes the Program in a commercial product offering, such Contributor (Commercial Contributor) hereby agrees to defend and indemnify every other Contributor (Indemnified Contributor) against any losses, damages and costs (collectively Losses) arising from claims, lawsuits and other legal actions brought by a third party against the Indemnified Contributor to the extent caused by the acts or omissions of such
 Commercial Contributor in connection with its distribution of the Program in a commercial product offering. The obligations in this section do not apply to any claims or Losses relating to any actual or alleged intellectual property infringement. In order to qualify, an Indemnified Contributor must: **a)** promptly notify the Commercial Contributor in writing of such claim, and **b)** allow the Commercial Contributor to control, and cooperate with the Commercial Contributor in, the defense and any related settlement negotiations. The Indemnified Contributor may participate in any such claim at its own expense.

For example, a Contributor might include the Program in a commercial product offering, Product X. That Contributor is then a Commercial Contributor. If that Commercial Contributor then makes performance claims, or offers warranties related to Product X, those performance claims and warranties are such Commercial Contributor's responsibility alone. Under this section, the Commercial
 Contributor would have to defend claims against the other Contributors related to those performance claims and warranties, and if a court requires any other Contributor to pay any damages as a result, the Commercial Contributor must pay those damages.

5. No Warranty

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, AND TO THE EXTENT PERMITTED BY APPLICABLE LAW, THE PROGRAM IS PROVIDED ON AN AS IS BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, EITHER EXPRESS OR IMPLIED INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OR CONDITIONS OF TITLE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each Recipient is solely responsible for determining the appropriateness of using and distributing the Program and assumes all risks associated with its exercise of rights under this Agreement, including but not limited to the risks and costs of program errors, compliance with applicable laws, damage to or loss of data, programs or equipment, and unavailability or
interruption of operations.

6. Disclaimer of Liability

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, AND TO THE EXTENT PERMITTED BY APPLICABLE LAW, NEITHER RECIPIENT NOR ANY CONTRIBUTORS SHALL HAVE ANY LIABILITY FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION LOST PROFITS), HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OR DISTRIBUTION OF THE PROGRAM OR THE EXERCISE OF ANY RIGHTS GRANTED HEREUNDER, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. General

If any provision of this Agreement is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this Agreement, and without further action by the parties hereto, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

If
Recipient institutes patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Program itself (excluding combinations of the Program with other software or hardware) infringes such Recipient's patent(s), then such Recipient's rights granted under Section 2(b) shall terminate as of the date such litigation is filed.

All Recipient's rights under this Agreement shall terminate if it fails to comply with any of the material terms or conditions of this Agreement and does not cure such failure in a reasonable period of time after becoming aware of such noncompliance. If all Recipient's rights under this Agreement terminate, Recipient agrees to cease use and distribution of the Program as soon as reasonably practicable. However, Recipient's obligations under this Agreement and any licenses granted by Recipient relating to the Program shall continue and survive.

Everyone is permitted to copy and distribute copies of this Agreement,
but in order to avoid inconsistency the Agreement is copyrighted and may only be modified in the following manner. The Agreement Steward reserves the right to publish new versions (including revisions) of this Agreement from time to time. No one other than the Agreement Steward has the right to modify this Agreement. The Eclipse Foundation is the initial Agreement Steward. The Eclipse Foundation may assign the responsibility to serve as the Agreement Steward to a suitable separate entity. Each new version of the Agreement will be given a distinguishing

version number. The Program (including Contributions) may always be Distributed subject to the version of the Agreement under which it was received. In addition, after a new version of the Agreement is published, Contributor may elect to Distribute the Program (including its Contributions) under the new version.

Except as expressly stated in Sections 2(a) and 2(b) above, Recipient receives no rights or licenses to the intellectual property
of any Contributor under this Agreement, whether expressly, by implication, estoppel or otherwise. All rights in the Program not expressly granted under this Agreement are reserved. Nothing in this Agreement is intended to be enforceable by any entity that is not a Contributor or Recipient. No third-party beneficiary rights are created under this Agreement.

Exhibit A - Form of Secondary Licenses Notice

> This Source Code may also be made available under the following Secondary Licenses when the conditions for such availability set forth in the Eclipse Public License, v. 2.0 are satisfied: {name license(s), version(s), and exceptions or additional permissions here}.

Simply including a copy of this Agreement, including this Exhibit A is not sufficient to license the Source Code under Secondary Licenses.

If it is not possible or desirable to put the notice in a particular file, then You may include the notice in a location (such as a LICENSE file in a relevant directory)
where a recipient would be likely to look for such a notice.

You may add additional accurate notices of copyright ownership.
Open Source Licenses
==========

This product may include a number of subcomponents with separate
copyright notices and license terms. Your use of the source code for
these subcomponents is subject to the terms and conditions of the
subcomponent's license, as noted in the LICENSE-<subcomponent>.md
files.

1.190 junit-jupiter-api 5.1.0

1.190.1 Available under license :

Eclipse Public License - v 2.0
==========

THE ACCOMPANYING PROGRAM IS PROVIDED UNDER THE TERMS OF THIS ECLIPSE PUBLIC LICENSE (AGREEMENT). ANY USE, REPRODUCTION OR DISTRIBUTION OF THE PROGRAM CONSTITUTES RECIPIENT'S ACCEPTANCE OF THIS AGREEMENT.

1. Definitions

Contribution means:

* **a)** in the case of the initial Contributor, the initial content Distributed under this Agreement, and
* **b)** in the case of each subsequent Contributor:
 * **i)** changes to the Program, and
 * **ii)** additions to the Program;
where such changes and/or additions to the Program originate from and are Distributed by that particular Contributor. A Contribution originates from a Contributor if it was added to the Program by such Contributor itself or anyone acting on such Contributor's behalf. Contributions do not include changes or additions to the Program that are not Modified Works.

Contributor means any person or entity that Distributes the Program.

Licensed Patents mean patent
 claims licensable by a Contributor which are necessarily infringed by the use or sale of its Contribution alone or when combined with the Program.

Program means the Contributions Distributed in accordance with this Agreement.

Recipient means anyone who receives the Program under this Agreement or any Secondary License (as applicable), including Contributors.

Derivative Works shall mean any work, whether in Source Code or other form, that is based on (or derived from) the Program and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship.

Modified Works shall mean any work in Source Code or other form that results from an addition to, deletion from, or modification of the contents of the Program, including, for purposes of clarity any new file in Source Code form that contains any contents of the Program. Modified Works shall not include works that contain only declarations, interfaces, types, classes,
 structures, or files of the Program solely in each case in order to link to, bind by name, or subclass the Program or Modified Works thereof.

Distribute means the acts of **a)** distributing or **b)** making available in any manner that enables the transfer of a copy.

Source Code means the form of a Program preferred for making modifications, including but not limited to software source code, documentation source, and configuration files.

Secondary License means either the GNU General Public License, Version 2.0, or any later versions of that license, including any exceptions or additional permissions as identified by the initial Contributor.

2. Grant of Rights

a) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, Distribute and sublicense the Contribution of such Contributor, if any, and such Derivative
 Works.

b) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive,

worldwide, royalty-free patent license under Licensed Patents to make, use, sell, offer to sell, import and otherwise transfer the Contribution of such Contributor, if any, in Source Code or other form. This patent license shall apply to the combination of the Contribution and the Program if, at the time the Contribution is added by the Contributor, such addition of the Contribution causes such combination to be covered by the Licensed Patents. The patent license shall not apply to any other combinations which include the Contribution. No hardware per se is licensed hereunder.

c) Recipient understands that although each Contributor grants the licenses to its Contributions set forth herein, no assurances are provided by any Contributor that the Program does not infringe the patent or other intellectual property rights of any other entity. Each Contributor disclaims any
liability to Recipient for claims brought by any other entity based on infringement of intellectual property rights or otherwise. As a condition to exercising the rights and licenses granted hereunder, each Recipient hereby assumes sole responsibility to secure any other intellectual property rights needed, if any. For example, if a third party patent license is required to allow Recipient to Distribute the Program, it is Recipient's responsibility to acquire that license before distributing the Program.

d) Each Contributor represents that to its knowledge it has sufficient copyright rights in its Contribution, if any, to grant the copyright license set forth in this Agreement.

e) Notwithstanding the terms of any Secondary License, no Contributor makes additional grants to any Recipient (other than those set forth in this Agreement) as a result of such Recipient's receipt of the Program under the terms of a Secondary License (if permitted under the terms of Section 3).

###
3. Requirements

3.1 If a Contributor Distributes the Program in any form, then:

* **a)** the Program must also be made available as Source Code, in accordance with section 3.2, and the Contributor must accompany the Program with a statement that the Source Code for the Program is available under this Agreement, and informs Recipients how to obtain it in a reasonable manner on or through a medium customarily used for software exchange; and

* **b)** the Contributor may Distribute the Program under a license different than this Agreement, provided that such license:
* **i)** effectively disclaims on behalf of all other Contributors all warranties and conditions, express and implied, including warranties or conditions of title and non-infringement, and implied warranties or conditions of merchantability and fitness for a particular purpose;
* **ii)** effectively excludes on behalf of all other Contributors all liability for damages, including direct, indirect, special, incidental
and consequential damages, such as lost profits;
* **iii)** does not attempt to limit or alter the recipients' rights in the Source Code under section 3.2; and
* **iv)** requires any subsequent distribution of the Program by any party to be under a license that satisfies the requirements of this section 3.

3.2 When the Program is Distributed as Source Code:

* **a)** it must be made available under this Agreement, or if the Program **(i)** is combined with other material in a separate file or files made available under a Secondary License, and **(ii)** the initial Contributor attached to

the Source Code the notice described in Exhibit A of this Agreement, then the Program may be made available under the terms of such Secondary Licenses, and
* **b)** a copy of this Agreement must be included with each copy of the Program.

3.3 Contributors may not remove or alter any copyright, patent, trademark, attribution notices, disclaimers of warranty, or limitations of liability (notices)
contained within the Program from any copy of the Program which they Distribute, provided that Contributors may add their own appropriate notices.

4. Commercial Distribution

Commercial distributors of software may accept certain responsibilities with respect to end users, business partners and the like. While this license is intended to facilitate the commercial use of the Program, the Contributor who includes the Program in a commercial product offering should do so in a manner which does not create potential liability for other Contributors. Therefore, if a Contributor includes the Program in a commercial product offering, such Contributor (Commercial Contributor) hereby agrees to defend and indemnify every other Contributor (Indemnified Contributor) against any losses, damages and costs (collectively Losses) arising from claims, lawsuits and other legal actions brought by a third party against the Indemnified Contributor to the extent caused by the acts or omissions of such
Commercial Contributor in connection with its distribution of the Program in a commercial product offering. The obligations in this section do not apply to any claims or Losses relating to any actual or alleged intellectual property infringement. In order to qualify, an Indemnified Contributor must: **a)** promptly notify the Commercial Contributor in writing of such claim, and **b)** allow the Commercial Contributor to control, and cooperate with the Commercial Contributor in, the defense and any related settlement negotiations. The Indemnified Contributor may participate in any such claim at its own expense.

For example, a Contributor might include the Program in a commercial product offering, Product X. That Contributor is then a Commercial Contributor. If that Commercial Contributor then makes performance claims, or offers warranties related to Product X, those performance claims and warranties are such Commercial Contributor's responsibility alone. Under this section, the Commercial
Contributor would have to defend claims against the other Contributors related to those performance claims and warranties, and if a court requires any other Contributor to pay any damages as a result, the Commercial Contributor must pay those damages.

5. No Warranty

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, AND TO THE EXTENT PERMITTED BY APPLICABLE LAW, THE PROGRAM IS PROVIDED ON AN AS IS BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, EITHER EXPRESS OR IMPLIED INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OR CONDITIONS OF TITLE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each Recipient is solely responsible for determining the appropriateness of using and distributing the Program and assumes all risks associated with its exercise of rights under this Agreement, including but not limited to the risks and costs of program errors, compliance with applicable laws, damage to or loss of data, programs or equipment, and unavailability or
interruption of operations.

6. Disclaimer of Liability

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, AND TO THE EXTENT PERMITTED BY APPLICABLE LAW, NEITHER RECIPIENT NOR ANY CONTRIBUTORS SHALL HAVE ANY LIABILITY FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION LOST PROFITS), HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OR DISTRIBUTION OF THE PROGRAM OR THE EXERCISE OF ANY RIGHTS GRANTED HEREUNDER, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. General

If any provision of this Agreement is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this Agreement, and without further action by the parties hereto, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

If
Recipient institutes patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Program itself (excluding combinations of the Program with other software or hardware) infringes such Recipient's patent(s), then such Recipient's rights granted under Section 2(b) shall terminate as of the date such litigation is filed.

All Recipient's rights under this Agreement shall terminate if it fails to comply with any of the material terms or conditions of this Agreement and does not cure such failure in a reasonable period of time after becoming aware of such noncompliance. If all Recipient's rights under this Agreement terminate, Recipient agrees to cease use and distribution of the Program as soon as reasonably practicable. However, Recipient's obligations under this Agreement and any licenses granted by Recipient relating to the Program shall continue and survive.

Everyone is permitted to copy and distribute copies of this Agreement,
but in order to avoid inconsistency the Agreement is copyrighted and may only be modified in the following manner. The Agreement Steward reserves the right to publish new versions (including revisions) of this Agreement from time to time. No one other than the Agreement Steward has the right to modify this Agreement. The Eclipse Foundation is the initial Agreement Steward. The Eclipse Foundation may assign the responsibility to serve as the Agreement Steward to a suitable separate entity. Each new version of the Agreement will be given a distinguishing version number. The Program (including Contributions) may always be Distributed subject to the version of the Agreement under which it was received. In addition, after a new version of the Agreement is published, Contributor may elect to Distribute the Program (including its Contributions) under the new version.

Except as expressly stated in Sections 2(a) and 2(b) above, Recipient receives no rights or licenses to the intellectual property
of any Contributor under this Agreement, whether expressly, by implication, estoppel or otherwise. All rights in the Program not expressly granted under this Agreement are reserved. Nothing in this Agreement is intended to be enforceable by any entity that is not a Contributor or Recipient. No third-party beneficiary rights are created under this Agreement.

Exhibit A - Form of Secondary Licenses Notice

> This Source Code may also be made available under the following Secondary Licenses when the conditions for such availability set forth in the Eclipse Public License, v. 2.0 are satisfied: {name license(s), version(s), and

exceptions or additional permissions here}.

Simply including a copy of this Agreement, including this Exhibit A is not sufficient to license the Source Code under Secondary Licenses.

If it is not possible or desirable to put the notice in a particular file, then You may include the notice in a location (such as a LICENSE file in a relevant directory)
where a recipient would be likely to look for such a notice.

You may add additional accurate notices of copyright ownership.
Open Source Licenses
==========

This product may include a number of subcomponents with separate
copyright notices and license terms. Your use of the source code for
these subcomponents is subject to the terms and conditions of the
subcomponent's license, as noted in the LICENSE-<subcomponent>.md
files.

1.191 swagger-models 1.5.22

1.191.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
package io.swagger.models;

import com.fasterxml.jackson.annotation.JsonAnyGetter;
import com.fasterxml.jackson.annotation.JsonAnySetter;

import java.util.LinkedHashMap;
import java.util.Map;

public class Info {
  private String description;
  private String version;
  private String title;
  private String termsOfService;
  private Contact contact;
  private License license;
  private Map<String, Object> vendorExtensions = new LinkedHashMap<String, Object>();

  public Info version(String version) {
    this.setVersion(version);
    return this;
  }

  public Info title(String title) {
```

```
    this.setTitle(title);
    return this;
  }

  public Info description(String description) {
    this.setDescription(description);
    return this;
  }

  public Info termsOfService(String termsOfService) {
    this.setTermsOfService(termsOfService);
    return this;

  }

  public Info contact(Contact contact) {
    this.setContact(contact);
    return this;
  }

  public Info license(License license) {
    this.setLicense(license);
    return this;
  }

  public String getDescription() {
    return description;
  }

  public void setDescription(String description) {
    this.description = description;
  }

  public String getVersion() {
    return version;
  }

  public void setVersion(String version) {
    this.version = version;
  }

  public String getTitle() {
    return title;
  }

  public void setTitle(String title) {
    this.title = title;
  }
```

```
public String getTermsOfService() {
    return termsOfService;
}

public void setTermsOfService(String termsOfService) {
    this.termsOfService = termsOfService;
}

public Contact getContact() {
    return contact;
}

public void setContact(Contact contact) {
    this.contact = contact;
 }

public License getLicense() {
    return license;
}

public void setLicense(License license) {
    this.license = license;
}

public Info mergeWith(Info info) {
    if (info != null) {
        if (this.description == null) {
            this.description = info.description;
        }
        if (this.version == null) {
            this.version = info.version;
        }
        if (this.title == null) {
            this.title = info.title;
        }
        if (this.termsOfService == null) {
            this.termsOfService = info.termsOfService;
        }
        if (this.contact == null) {
            this.contact = info.contact;
        }
        if (this.license == null) {
            this.license = info.license;
        }
        if (this.vendorExtensions == null) {
            this.vendorExtensions = info.vendorExtensions;
        }
```

```
    }
    return this;
  }

  @JsonAnyGetter
  public Map<String, Object> getVendorExtensions() {
    return vendorExtensions;
  }

  @JsonAnySetter
  public void setVendorExtension(String name, Object value) {
    if (name.startsWith("x-")) {
      vendorExtensions.put(name, value);
    }
  }

public void setVendorExtensions(Map<String, Object> vendorExtensions) {
    this.vendorExtensions = vendorExtensions;
  }

  @Override
  public int hashCode() {
    final int prime = 31;
    int result = 1;
    result = prime * result + ((contact == null) ? 0 : contact.hashCode());
    result = prime * result
        + ((description == null) ? 0 : description.hashCode());
    result = prime * result + ((license == null) ? 0 : license.hashCode());
    result = prime * result
        + ((termsOfService == null) ? 0 : termsOfService.hashCode());
    result = prime * result + ((title == null) ? 0 : title.hashCode());
    result
= prime * result
        + ((vendorExtensions == null) ? 0 : vendorExtensions.hashCode());
    result = prime * result + ((version == null) ? 0 : version.hashCode());
    return result;
  }

  @Override
  public boolean equals(Object obj) {
    if (this == obj) {
      return true;
    }
    if (obj == null) {
      return false;
    }
    if (getClass() != obj.getClass()) {
      return false;
```

```
}
Info other = (Info) obj;
if (contact == null) {
    if (other.contact != null) {
        return false;
    }
} else if (!contact.equals(other.contact)) {
    return false;
}
if (description == null) {
    if (other.description != null) {
        return false;
    }
} else if (!description.equals(other.description)) {
    return false;
}
if (license == null) {
    if (other.license != null) {
         return false;
    }
} else if (!license.equals(other.license)) {
    return false;
}
if (termsOfService == null) {
    if (other.termsOfService != null) {
        return false;
    }
} else if (!termsOfService.equals(other.termsOfService)) {
    return false;
}
if (title == null) {
    if (other.title != null) {
        return false;
    }
} else if (!title.equals(other.title)) {
    return false;
}
if (vendorExtensions == null) {
    if (other.vendorExtensions != null) {
        return false;
    }
} else if (!vendorExtensions.equals(other.vendorExtensions)) {
    return false;
}
if (version == null) {
    if (other.version != null) {
        return false;
    }
```

```
    } else if (!version.equals(other.version)) {
      return false;
     }
    return true;
  }
}
```

Found in path(s):
* /swagger-models-1-5-22-sources-jar/io/swagger/models/Info.java
No license file was found, but licenses were detected in source scan.

```
package io.swagger.models;

import com.fasterxml.jackson.annotation.JsonAnyGetter;
import com.fasterxml.jackson.annotation.JsonAnySetter;

import java.util.LinkedHashMap;
import java.util.Map;

public class License {
  private Map<String, Object> vendorExtensions = new LinkedHashMap<String, Object>();
  private String name;
  private String url;

  public License name(String name) {
    setName(name);
    return this;
  }

  public License url(String url) {
    setUrl(url);
    return this;
  }

  public String getName() {
    return name;
  }

  public void setName(String name) {
    this.name = name;
  }

  public String getUrl() {
    return url;
  }

  public void setUrl(String url) {
    this.url = url;
```

```
  }

  @JsonAnyGetter
  public Map<String, Object> getVendorExtensions() {
     return vendorExtensions;
  }

  @JsonAnySetter
  public void
setVendorExtension(String name, Object value) {
     if (name.startsWith("x-")) {
        vendorExtensions.put(name, value);
     }
  }

  public void setVendorExtensions(Map<String, Object> vendorExtensions) {
     this.vendorExtensions = vendorExtensions;
  }

  @Override
  public int hashCode() {
     final int prime = 31;
     int result = 1;
     result = prime * result + ((name == null) ? 0 : name.hashCode());
     result = prime * result + ((url == null) ? 0 : url.hashCode());
     result = prime * result + ((vendorExtensions == null) ? 0 : vendorExtensions.hashCode());
     return result;
  }

  @Override
  public boolean equals(Object obj) {
     if (this == obj) {
        return true;
     }
     if (obj == null) {
        return false;
     }
     if (getClass() != obj.getClass()) {
        return false;
     }
     License other = (License) obj;
     if (name == null) {
        if (other.name
!= null) {
           return false;
        }
     } else if (!name.equals(other.name)) {
        return false;
```

```
        }
        if (url == null) {
            if (other.url != null) {
                return false;
            }
        } else if (!url.equals(other.url)) {
            return false;
        }
        if (vendorExtensions == null) {
            if (other.vendorExtensions != null) {
                return false;
            }
        } else if (!vendorExtensions.equals(other.vendorExtensions)) {
            return false;
        }
        return true;
    }
}
```

Found in path(s):
* /swagger-models-1-5-22-sources-jar/io/swagger/models/License.java

1.192 http-signature 1.2.0

1.192.1 Available under license :

Copyright Joyent, Inc. All rights reserved.
Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
 WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
IN THE SOFTWARE.
MIT

1.193 babel-plugin-syntax-nullish-coalescing-operator 7.8.3

1.193.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.194 babel-plugin-syntax-optional-chaining 7.8.3

1.194.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to

the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.195 ejs 2.7.4

1.195.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this

License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided

that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.196 xerces 2.9.1

1.196.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2001 World Wide Web Consortium,
* (Massachusetts Institute of Technology, Institut National de
* Recherche en Informatique et en Automatique, Keio University). All

* Rights Reserved. This program is distributed under the W3C's Software
* Intellectual Property License. This program is distributed in the
* hope that it will be useful, but WITHOUT ANY WARRANTY; without even
* the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
* PURPOSE.
* See W3C License http://www.w3.org/Consortium/Legal/ for more details.
*/

Found in path(s):
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/DocumentAS.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/DocumentEditAS.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/DOMASBuilder.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASEntityDeclaration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASObject.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASNamedObjectMap.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/ElementEditAS.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASDataType.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASContentModel.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASNotationDeclaration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/DOMASException.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/CharacterDataEditAS.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASElementDeclaration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASModel.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/DOMImplementationAS.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASObjectList.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASAttributeDeclaration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/NodeEditAS.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom3/as/DOMASWriter.java
No license file was found, but licenses were detected in source scan.

Licensed to the Apache Software Foundation (ASF) under one or more
 contributor license agreements. See the NOTICE file distributed with
 this work for additional information regarding copyright ownership.
 The ASF licenses this file to You under the Apache License, Version 2.0
 (the "License"); you may not use this file except in compliance with
 the License. You may obtain a copy of the License at

     http://www.apache.org/licenses/LICENSE
2.0

 Unless required by applicable law or agreed to in writing, software
 distributed under the License is distributed on an "AS IS" BASIS,
 WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 See the License for the specific language governing permissions and
 limitations under the License.

Found in path(s):
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/package.html
No license file was found, but licenses were detected in source scan.

cos-nonambig = cos-nonambig: {0} and {1} (or elements from their substitution group) violate \"Unique Particle Attribution\". During validation against this schema, ambiguity would be created for those two particles.

Found in path(s):
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/msg/XMLSchemaMessages.properties
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
    * used to check the 3 constraints against each complex type
    * (should be each model group):
    * Unique Particle
 Attribution, Particle Derivation (Restriction),
    * Element Declrations Consistent.
    */
```

Found in path(s):
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSConstraints.java
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
```

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/validation/ValidationManager.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/XMLResourceIdentifierImpl.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/io/ASCIIReader.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/TextImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/SecuritySupport.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLPostfieldElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLOptgroupElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/XML11Char.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLNoopElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/ObjectFactory.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DocumentTypeImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/StringDatatypeValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/SimpleXMLSchema.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/UnionDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLFontElementImpl.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLDoElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/XMLSchemaFactory.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/DTDGrammarBucket.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/BMPattern.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/LSInputList.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLNoopElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/SoftReferenceSymbolTableConfiguration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/SAXMessageFormatter.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/SecurityManager.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSModelGroupDefinition.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/EncodingMap.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/DOMParserImpl.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/NodeIteratorImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/ShortListImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/SchemaDateTimeException.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DOMStringListImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSFacet.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/XSSimpleType.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/CMUniOp.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDNotationTraverser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/DefaultText.java

* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSNamespaceItemList.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xpointer/XPointerMessageFormatter.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/PSVIElementNSImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/AbstractXMLDocumentParser.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLNSDTDValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/StandardParserConfiguration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/DefaultXMLDocumentHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLFrameElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/EncodingInfo.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLStyleElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/msg/XMLMessageFormatter.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSDDescription.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/PSVIProvider.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLTableCaptionElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/XMLDTDHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLDTDValidator.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLGoElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLTableCellElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSNamespaceItem.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLHeadElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/io/MalformedByteSequenceException.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XMLEntityDescription.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/UnparsedEntityHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/util/ByteListImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DOMImplementationSourceImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLOptionElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/XSFloat.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/SAXLocatorWrapper.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSAttributeGroupDefinition.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/SecuritySupport.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/ElementPSVI.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDAbstractParticleTraverser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredCDATASectionImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/IDDatatypeValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/TextSerializer.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/SimpleLocator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLOptgroupElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLAnchorElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/Method.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLDTDContentModelSource.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLEmElement.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XMLNamespaceBinder.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/NSItemListImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XMLEntityManager.java

* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DOMXSImplementationSourceImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/EntityResolverWrapper.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSNamedMap.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/HexBinaryDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLTrElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/BaseDVFactory.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/XSNamedMap4Types.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/Token.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/ObjectList.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/EntityImpl.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/BasicParserConfiguration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/CMNode.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DOMNormalizer.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDocumentInfo.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xinclude/XIncludeHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/ParseException.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLEmElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/InvalidDatatypeValueException.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/IntStack.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLDOMImplementationImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/ObjectFactory.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/TextImpl.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/SynchronizedSymbolTable.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XML11EntityScanner.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLAreaElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLParserConfiguration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLOneventElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/FieldActivator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLHeadingElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/DefaultElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/MixedContentModel.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/SubstitutionGroupHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSTerm.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/XMLStringBuffer.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/ElementPSVImpl.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/AbstractSAXParser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/ElementNSImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLComponentManager.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSAnnotationImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/ObjectFactory.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLDTDSource.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/XMLString.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/PSVIDocumentImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/NodeImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSAnnotationInfo.java

* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/XML11Configurable.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLDocumentImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/RangeImpl.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/XSDateTime.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/DocumentBuilderImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLDTDProcessor.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xinclude/XInclude11TextReader.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/XMLLocatorWrapper.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLTrElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/HTTPInputSource.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XMLSchemaLoader.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/SchemaGrammar.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/AnyURIDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLTableColElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/validation/EntityState.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLInputElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DOMImplementationImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/SimpleContentModel.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLHRElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredProcessingInstructionImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/grammars/XMLGrammarPool.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xinclude/MultipleScopeNamespaceSupport.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSAttributeUseImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/XIncludeAwareParserConfiguration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/ValidationContext.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/validation/ConfigurableValidationState.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredEntityImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredCommentImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLPElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSParticle.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/ErrorHandlerProxy.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/XMLErrorCode.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/CoreDocumentImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLBuilder.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSIDCDefinition.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredNode.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/XMLSerializer.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSConstants.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/XMLLocator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/XMLDocumentParser.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/ParentNode.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/XHTMLSerializer.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/SchemaValidatorConfiguration.java

* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/XMLEntityDescriptionImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLDTDFilter.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLMetaElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLOptionElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLDirectoryElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/NodeImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLCardElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/XMLSymbols.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/ElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/ValueStore.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XML11DTDProcessor.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLAElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/OutputFormat.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSNotationDeclaration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSComplexTypeDefinition.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/ElementState.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLImageElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLBodyElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLAccessElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/LocatorProxy.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/io/Latin1Reader.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/JAXPValidatorComponent.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLBrElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLStrongElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/XMLSchemaValidatorComponentManager.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/JAXPValidationMessageFormatter.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLUElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSElementDeclaration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XMLDocumentScannerImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/ASModelImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLPElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/XMLAttributesImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XML11NSDTDValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLBaseElementImpl.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/XMLGrammarPoolImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/WeakReferenceXMLSchema.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLLinkElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLNotationDecl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredAttrImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLConfigurationException.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/HTMLSerializer.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLLegendElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLDocument.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/NameNodeListImpl.java

* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLAnchorElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredElementDefinitionImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/XMLChar.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/JAXPConstants.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/AttributesProxy.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSLoader.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLTableRowElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLFrameSetElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/DOMValidatorHelper.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLModElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/IntegerDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLPrevElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/ElementDefinitionImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/TypeValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/XSCMBinOp.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/XMLAttributes.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredElementNSImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/SerializerFactory.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xpath/XPath.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/XSGrammarPoolContainer.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/XMLGrammarParser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/InvalidDatatypeFacetException.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLIsIndexElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLBigElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLBElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/LineSeparator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/CMAny.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLDOMImplementation.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLSmallElement.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/BalancedDTDGrammar.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLEntityResolver.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/XMLParser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/SAXParser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLDocumentSource.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLCardElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/XSCMRepeatingLeaf.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xpointer/XPointerPart.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLDTDContentModelFilter.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/XSObjectListImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/StringList.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSElementDecl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/ParserForXMLSchema.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/DOMResultAugmentor.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/CachingParserPool.java

* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLDTDValidatorFilter.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredAttrNSImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLLIElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/HTMLdtd.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xpath/XPathException.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSObjectList.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/ValidatorHandlerImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/DefaultValidationErrorHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xpointer/XPointerErrorHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xinclude/XIncludeNamespaceSupport.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLElementDecl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/DFAContentModel.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/CMNodeFactory.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLButtonElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/ItemPSVI.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/XSCMUniOp.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSAttributeDeclaration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLPrevElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDAbstractTraverser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/DefaultDocument.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/IDDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/StringDV.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/NamespaceSupport.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLStrongElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/NotationImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLEntityDecl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/SymbolTable.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/XML11IDREFDatatypeValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/events/EventImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLHeadElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLDocumentFilter.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/SoftReferenceGrammarPool.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLMetaElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLHtmlElementImpl.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredDocumentTypeImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/TreeWalkerImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/DoubleDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLMetaElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DOMConfigurationImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLParseException.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/SchemaDVFactoryImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/EntityDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSImplementation.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DOMInputImpl.java

* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/ShortList.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/NonValidatingConfiguration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLTemplateElementImpl.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/XML11NMTOKENDatatypeValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeepNodeListImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DOMMessageFormatter.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/DOMInputSource.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/NOTATIONDatatypeValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/grammars/Grammar.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/SAXParserFactoryImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLIFrameElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/XMLCatalogResolver.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/ParserConfigurationSettings.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLTdElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLCollectionImpl.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/ListDatatypeValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/SchemaDOM.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDAbstractIDConstraintTraverser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xinclude/ObjectFactory.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/Printer.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLSimpleType.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/datatype/XMLGregorianCalendarImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xpointer/XPointerProcessor.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/XSDecimal.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSAttributeUse.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/ElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/DOMEntityResolverWrapper.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/IntegratedParserConfiguration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLBrElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/JAXPNamespaceContextWrapper.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLPreElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLOListElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/SAXParserImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/DOMSerializerImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredTextImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/QNameDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/XMLDocumentFragmentHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/AnySimpleDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DOMErrorImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/datatype/DurationImpl.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredEntityReferenceImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/XSDouble.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLMapElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLDTDDescription.java

* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/YearMonthDurationDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLInputElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLBigElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredDocumentImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/DatatypeException.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DocumentImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLDOMImplementationImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/StringListImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSModel.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/SchemaParsingConfig.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLTitleElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/DefaultErrorHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/CMBuilder.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/SchemaDOMParser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/AttributePSVImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDElementTraverser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/AttributePSVI.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/NMTOKENDatatypeValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XMLVersionDetector.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLAnchorElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xpointer/ShortHandPointer.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLSetvarElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/XML11Configuration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLTdElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/MessageFormatter.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/DOMResultBuilder.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XMLNSDocumentScannerImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/XML11DTDConfiguration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/DOMASBuilderImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLParagraphElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/ExternalSubsetResolver.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/Op.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLHeadElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/XIntPool.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/AttributeMap.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/validation/ValidationState.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/REUtil.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/StreamValidatorHelper.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/AttrNSImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/DOMErrorHandlerWrapper.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLTableElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLSelectElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XMLDocumentFragmentScannerImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSAnnotation.java

* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSGrammarBucket.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLUElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/LCount.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/grammars/XMLGrammarDescription.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xinclude/XIncludeMessageFormatter.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/EmptyXMLSchema.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/XML11DTDDVFactoryImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/Util.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/IndentPrinter.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSSimpleTypeDefinition.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/SchemaContentHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/DayTimeDurationDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLDListElementImpl.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XMLEntityHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/IDREFDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLDoElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/DatatypeValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/IDREFDatatypeValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XML11DTDValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/PSVIDOMImplementationImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDGroupTraverser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLBaseFontElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/XMLGrammarCachingConfiguration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/FloatDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/RevalidationHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLRefreshElementImpl.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSWildcardDecl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLObjectElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XML11DTDScannerImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/DatatypeMessageFormatter.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/ASDOMImplementationImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLWmlElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/SerializerFactoryImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/AbstractDOMParser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/XNIException.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDSimpleTypeTraverser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/NamedNodeMapImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLFormElementImpl.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLPullParserConfiguration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/XSAllCM.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLAttributeDecl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLTableElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/XSFacets.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/XML11IDDatatypeValidator.java

* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XMLErrorReporter.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLAppletElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/grammars/XMLGrammarLoader.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/ContentModelValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/ByteList.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/DTDDVFactory.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/SymbolHash.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/DOMDocumentHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/DVFactoryException.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/PSVIAttrNSImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/ENTITYDatatypeValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLErrorHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/XMLGrammarPreparser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/SecuritySupport.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/BooleanDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/BaseMarkupSerializer.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/DTDDVFactoryImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/TeeXMLDocumentFilterImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLSmallElementImpl.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DOMOutputImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/util/HexBin.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSLoaderImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/RegexParser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/util/Base64.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLFormControl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/XML11Serializer.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLImgElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLQuoteElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLGoElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLDTDScanner.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLBRElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DocumentFragmentImpl.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLInputSource.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSComplexTypeDecl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLComponent.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSImplementationImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XMLDTDScannerImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/CharacterDataImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLDocumentScanner.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/ChildNode.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLScriptElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/Augmentations.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLInputElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/DocumentBuilderFactoryImpl.java
*

/xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/SoftReferenceSymbolTable.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLTimerElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLLabelElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLFieldSetElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/SAXInputSource.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLSelectElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/SchemaNamespaceSupport.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/Serializer.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/SchemaSymbols.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/Match.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/io/UCSReader.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDComplexTypeTraverser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLAccessElement.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/xerces/xpointer/ElementSchemePointer.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSException.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XMLSchemaException.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/ListDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DOMLocatorImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/grammars/XMLDTDDescription.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDWildcardTraverser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/DOMParser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xinclude/XIncludeTextReader.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLOneventElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/AttrImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/CommentImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/Version.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/DTDConfiguration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/Constants.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/CDATASectionImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSDeclarationPool.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSNotationDecl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/FullDVFactory.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLFieldsetElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/DecimalDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSAttributeGroupDecl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLOptGroupElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLUListElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLSelectElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/events/MouseEventImpl.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/DOMUtil.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLIElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLRefreshElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLDocumentImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/QName.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/ReadOnlyGrammarPool.java

* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/RangeExceptionImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLContentSpec.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/SecuritySupport.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/PrecisionDecimalDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/EntityResolver2Wrapper.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSParticleDecl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSGroupDecl.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSModelGroup.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/ObjectFactory.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/RegularExpression.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSObject.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xpointer/XPointerHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/AugmentationsImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/ValidatorHelper.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/grammars/XSGrammar.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSWildcard.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/DTDParser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/events/MutationEventImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDAttributeTraverser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/CMLeaf.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/AbstractXMLSchema.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/XMLResourceIdentifier.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/grammars/XMLSchemaDescription.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/DOMSerializer.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredNotationImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/XML11NonValidatingConfiguration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/XMLDocumentHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/SecurityConfiguration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/NamespaceContext.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/KeyRef.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLMenuElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/Base64BinaryDV.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/EntityReferenceImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLOptionElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/CMStateSet.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/AnyAtomicDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/URI.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/XSEmptyCM.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/io/UTF8Reader.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/XInt.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/NamedNodeMapImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/ObjectFactory.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/ProcessingInstructionImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/UniqueOrKey.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XML11NamespaceBinder.java

*
/xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLTemplateElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/ShadowedSymbolTable.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLBElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLDTDLoader.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLTextAreaElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSModelImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/XMLSchema.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLWmlElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLFieldsetElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DeferredDOMImplementationImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLDivElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/DTDGrammar.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XML11NSDocumentScannerImpl.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/XSGrammarPool.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDAttributeGroupTraverser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/XIncludeParserConfiguration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/Field.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSMultiValueFacet.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xml/serialize/Encodings.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLTableElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLTableSectionElementImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/XPathMatcher.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xni/XMLDTDContentModelHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/DraconianErrorHandler.java
* /xercesimpl-2-9-1-sources-jar/org/apache/html/dom/HTMLParamElementImpl.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/Selector.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/DefaultNode.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/XSTypeDefinition.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/AttrImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLTimerElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/IdentityConstraint.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XMLEntityScanner.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XMLScanner.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/CMBinOp.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xinclude/SecuritySupport.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/XSCMLeaf.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/util/ErrorHandlerWrapper.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLSetvarElementImpl.java
*
/xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/events/UIEventImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/XSNamedMapImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLImgElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/RangeToken.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/parsers/XPointerParserConfiguration.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/NodeListCache.java

* /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLAElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/ValidatedInfo.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/ValidatorImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/XML11DocumentScannerImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/jaxp/datatype/DatatypeFactoryImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/SchemaDVFactory.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/wml/WMLPostfieldElement.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSAttributeDecl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSMessageFormatter.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/XSQName.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/SecuritySupport.java
* /xercesimpl-2-9-1-sources-jar/org/apache/wml/dom/WMLIElementImpl.java
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
    * Checks if this content model has had its min/maxOccurs values reduced for
    * purposes of speeding up UPA. If
 so, this content model should not be used
    * for any purpose other than checking unique particle attribution
    *
    * @return a boolean that says whether this content has been compacted for UPA
    */

Found in path(s):
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/XSCMValidator.java
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.

* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSAttributeChecker.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/MonthDV.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/XSSimpleTypeDecl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/YearMonthDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/DateDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/DayDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDUniqueOrKeyTraverser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XMLSchemaValidator.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/DateTimeDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/AbstractDateTimeDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/YearDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDKeyrefTraverser.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSModelGroupImpl.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDHandler.java
*
 /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/DurationDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/TimeDV.java
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/MonthDayDV.java
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/DOMImplementationListImpl.java
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
  * DOM Level 3 LS CR - Experimental.
    * Create a new <code>LSParser</code>. The newly constructed parser may
    *
 then be configured by means of its <code>DOMConfiguration</code>
    * object, and used to parse documents by means of its <code>parse</code>
    * method.
    * @param mode The <code>mode</code> argument is either
    *   <code>MODE_SYNCHRONOUS</code> or <code>MODE_ASYNCHRONOUS</code>, if
    *   <code>mode</code> is <code>MODE_SYNCHRONOUS</code> then the
    *   <code>LSParser</code> that is created will operate in synchronous
    *   mode, if it's <code>MODE_ASYNCHRONOUS</code> then the
    *   <code>LSParser</code> that is created will operate in asynchronous
    *   mode.
    * @param schemaType An absolute URI representing the type of the schema
    *   language used during the load of a <code>Document</code> using the
    *   newly created <code>LSParser</code>. Note that no lexical checking
    *   is done on the absolute URI. In order to create a
    *   <code>LSParser</code> for any kind of schema types (i.e. the
    *   LSParser will be free to use any schema
 found), use the value
    *   <code>null</code>.
    * <p >Note: For W3C XML Schema [XML Schema Part 1]

```
    *   , applications must use the value
    *   <code>"http://www.w3.org/2001/XMLSchema"</code>. For XML DTD [<a
href='http://www.w3.org/TR/2000/REC-xml-20001006'>XML 1.0</a>],
    *   applications must use the value
    *   <code>"http://www.w3.org/TR/REC-xml"</code>. Other Schema languages
    *   are outside the scope of the W3C and therefore should recommend an
    *   absolute URI in order to use this method.
    * @return  The newly created <code>LSParser</code> object. This
    *   <code>LSParser</code> is either synchronous or asynchronous
    *   depending on the value of the <code>mode</code> argument.
    * <p ><b>Note:</b>     By default, the newly created <code>LSParser</code>
    *    does not contain a <code>DOMErrorHandler</code>, i.e. the value of
    *   the "<a href='http://www.w3.org/TR/2003/WD-DOM-Level-3-Core-20030609/core.html#parameter-error-
handler'>
     *   error-handler</a>" configuration parameter is <code>null</code>. However, implementations
    *   may provide a default error handler at creation time. In that case,
    *   the initial value of the <code>"error-handler"</code> configuration
    *   parameter on the new created <code>LSParser</code> contains a
    *   reference to the default error handler.
    * @exception DOMException
    *    NOT_SUPPORTED_ERR: Raised if the requested mode or schema type is
    *   not supported.
   */
```

Found in path(s):
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/dom/CoreDOMImplementationImpl.java
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
// Unique Particle Attribution
```

Found in path(s):
* /xercesimpl-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/XSDFACM.java

No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2000 World Wide Web Consortium,
* (Massachusetts Institute of Technology, Institut National de
* Recherche en Informatique et en Automatique, Keio University). All
* Rights Reserved. This program is distributed under the W3C's Software
* Intellectual Property License. This program is distributed in the
* hope that it will be useful, but WITHOUT ANY WARRANTY; without even
* the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
* PURPOSE. See W3C License http://www.w3.org/Consortium/Legal/ for more
* details.
*/

Found in path(s):
* /xercesimpl-2-9-1-sources-jar/org/w3c/dom/html/HTMLDOMImplementation.java

1.197 vavr 0.10.2

1.197.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form
shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely
link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean
Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and

You must cause any modified files to carry prominent notices stating that You changed the files; and

You must retain, in the Source form of any Derivative Works that You distribute,

all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum
to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.
You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.
5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use
the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor
harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.198 vavr-match 0.10.2

1.198.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form
shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely
link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean
Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and

You must cause any modified files to carry prominent notices stating that You changed the files; and

You must retain, in the Source form of any Derivative Works that You distribute,
all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum
to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.
You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.
5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use
the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has

been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor
harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.199 commons-lang3 2.6

1.199.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or
(iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work

(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from)
the Work and for which the
editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication
on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant
of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a

cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as
of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with

the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names
of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your
sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Commons Lang
Copyright 2001-2011 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

1.200 commons-compress 1.20

1.200.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent

to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works

that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS,

WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.

You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Commons Compress
Copyright 2002-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (https://www.apache.org/).

The files in the package org.apache.commons.compress.archivers.sevenz
were derived from the LZMA SDK, version 9.20 (C/ and CPP/7zip/),
which has been placed in the public domain:

"LZMA SDK is placed in the public domain." (http://www.7-zip.org/sdk.html)

The test file lbzip2_32767.bz2 has been copied from libbzip2's source
repository:

This program, "bzip2", the associated library "libbzip2", and all
documentation, are copyright (C) 1996-2019 Julian R Seward. All
rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

2. The origin of this software must not be misrepresented;
you must
not claim that you wrote the original software. If you use this
software in a product, an acknowledgment in the product
documentation would be appreciated but is not required.

3. Altered source versions must be plainly marked as such, and must
not be misrepresented as being the original software.

4. The name of the author may not be used to endorse or promote
products derived from this software without specific prior written
permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS
OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER
IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Julian Seward, jseward@acm.org

1.201 request 2.88.2

1.201.1 Available under license :

Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean
the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name)
to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual
or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by
combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and

You must cause any modified files to carry prominent notices stating that You changed the files; and

You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed as modifying the License. You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall
any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims

asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.202 commons-lang3 2.4.0

1.202.1 Available under license :

Apache Commons Lang
Copyright 2001-2008 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their

Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf

of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.203 dbcp 1.2.2.osgi

1.203.1 Available under license :

Apache Jakarta Commons DBCP
Copyright 1999-2007 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of

the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or

agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.204 jms 1.1.0

1.204.1 Available under license :

```
 =========================================================================
==  NOTICE file corresponding to the section 4 d of                    ==
==  the Apache License, Version 2.0,                                   ==
==  in this case for the Apache Camel distribution.                    ==
=========================================================================
```

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Please read the different LICENSE files present in the licenses directory of
this distribution.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the

outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of

this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed

as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,

indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.205 servlet 2.5.0

1.205.1 Available under license :

No license file was found, but licenses were detected in source scan.

Licensed to the Apache Software Foundation (ASF) under one
or more contributor license agreements. See the NOTICE file
distributed with this work for additional information
regarding copyright ownership. The ASF licenses this file
to you under the Apache License, Version 2.0 (the
"License"); you may not use this file except in compliance
with the License. You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE
2.0

Unless required by applicable law or agreed to in writing,
software distributed under the License is distributed on an
"AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY
KIND, either express or implied. See the License for the
specific language governing permissions and limitations
under the License.

Found in path(s):
* /groovy-servlet-2-5-0-sources-jar/groovy/servlet/package.html
No license file was found, but licenses were detected in source scan.

```
/*
*  Licensed to the Apache Software Foundation (ASF) under one
*  or more contributor license agreements.  See the NOTICE file
*  distributed with this work for additional information
*  regarding copyright ownership.  The ASF licenses this file
*  to you under the Apache License, Version 2.0 (the
*  "License"); you may not use this file except in compliance
*  with the License.  You may obtain a copy of the License at
*
*    http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing,
*  software distributed under the License is distributed on an
*  "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY
*  KIND, either express or implied.  See the License for the
*  specific language governing permissions and limitations
*  under the License.
*/
```

Found in path(s):

* /groovy-servlet-2-5-0-sources-jar/groovy/servlet/ServletCategory.java
* /groovy-servlet-2-5-0-sources-jar/groovy/servlet/GroovyServlet.java
*
/groovy-servlet-2-5-0-sources-jar/groovy/servlet/TemplateServlet.java
* /groovy-servlet-2-5-0-sources-jar/groovy/servlet/ServletBinding.java
* /groovy-servlet-2-5-0-sources-jar/groovy/servlet/AbstractHttpServlet.java

1.206 commons-lang3 3.9

1.206.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or

Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You

institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,

reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Commons Lang
Copyright 2001-2018 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.207 javax-servlet-api 2.5.0

1.207.1 Available under license :

No license file was found, but licenses were detected in source scan.

Licensed to the Apache Software Foundation (ASF) under one or more
contributor license agreements. See the NOTICE file distributed with
this work for additional information regarding copyright ownership.
The ASF licenses this file to You under the Apache License, Version 2.0
(the "License"); you may not use this file except in compliance with
the License. You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE
2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
guarantee element specifies that the communication
between client and server should be NONE, INTEGRAL, or
CONFIDENTIAL. NONE means that the application does
not require any
transport guarantees. A value of INTEGRAL means that the application
requires that the data sent between the client and server be sent in
such a way that it can't be changed in transit. CONFIDENTIAL means
that the application requires that the data be transmitted in a
fashion that prevents other entities from observing the contents of
the transmission. In most cases, the presence of the INTEGRAL or
CONFIDENTIAL flag will indicate that the use of SSL is required.

Found in path(s):
* /com-springsource-javax-servlet-2-5-0-jar/javax/servlet/resources/web-app_2_2.dtd
No license file was found, but licenses were detected in source scan.

<!--
Licensed to the Apache Software Foundation (ASF) under one or more
contributor license agreements. See the NOTICE file distributed with
this work for additional information regarding copyright ownership.
The ASF licenses this file to You under the Apache License, Version 2.0
(the "License"); you may not use this file except in compliance with
the License. You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
-->

Found in path(s):
* /com-springsource-javax-servlet-2-5-0-jar/javax/servlet/resources/j2ee_1_4.xsd
* /com-springsource-javax-servlet-2-5-0-jar/javax/servlet/resources/xml.xsd
*
/com-springsource-javax-servlet-2-5-0-jar/javax/servlet/resources/j2ee_web_services_client_1_1.xsd
* /com-springsource-javax-servlet-2-5-0-jar/javax/servlet/resources/web-app_2_5.xsd
* /com-springsource-javax-servlet-2-5-0-jar/javax/servlet/resources/j2ee_web_services_1_1.xsd

* /com-springsource-javax-servlet-2-5-0-jar/javax/servlet/resources/web-app_2_4.xsd
No license file was found, but licenses were detected in source scan.

The ASF licenses this file to You under the Apache License, Version 2.0
(the "License"); you may not use this file except in compliance with
the License. You may obtain a copy of the License at
http://www.apache.org/licenses/LICENSE-2.0
distributed under the License is distributed on an "AS IS" BASIS,

Found in path(s):
* /com-springsource-javax-servlet-2-5-0-jar/javax/servlet/http/LocalStrings.properties
* /com-springsource-javax-servlet-2-5-0-jar/javax/servlet/LocalStrings.properties
No license file was found, but licenses were detected in source scan.

Licensed to the Apache Software Foundation (ASF) under one or more
 contributor license agreements. See the NOTICE file distributed with
 this work for additional information regarding copyright ownership.
 The ASF licenses this file to You under the Apache License, Version 2.0
 (the "License"); you may not use this file except in compliance with
 the License. You may obtain a copy of the License at

    http://www.apache.org/licenses/LICENSE
2.0

 Unless required by applicable law or agreed to in writing, software
 distributed under the License is distributed on an "AS IS" BASIS,
 WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 See the License for the specific language governing permissions and
 limitations under the License.
2001 Sun Microsystems, Inc. 901 San Antonio Road,
Palo Alto, CA 94303, U.S.A. All rights reserved.

This product or document is protected by copyright
 and distributed
under licenses restricting its use, copying, distribution, and
decompilation. No part of this product or documentation may be
reproduced in any form by any means without prior written authorization
of Sun and its licensors, if any.

Third party software, including font technology, is copyrighted and
licensed from Sun suppliers.

Sun, Sun Microsystems, the Sun Logo, Solaris, Java, JavaServer Pages, Java
Naming and Directory Interface, JDBC, JDK, JavaMail and Enterprise JavaBeans,
are trademarks or registered trademarks of Sun Microsystems, Inc in the U.S.
and other countries.

All SPARC trademarks are used under license and are trademarks

or registered trademarks of SPARC International, Inc.
in the U.S. and other countries. Products bearing SPARC
trademarks are based upon an architecture developed by Sun Microsystems, Inc.

PostScript is a registered trademark of Adobe Systems, Inc.

Federal Acquisitions: Commercial Software
guarantee element specifies that the communication
between
 client and server should be NONE, INTEGRAL, or
CONFIDENTIAL. NONE means that the application does not require any
transport guarantees. A value of INTEGRAL means that the application
requires that the data sent between the client and server be sent in
such a way that it can't be changed in transit. CONFIDENTIAL means
that the application requires that the data be transmitted in a
fashion that prevents other entities from observing the contents of
the transmission. In most cases, the presence of the INTEGRAL or
CONFIDENTIAL flag will indicate that the use of SSL is required.

Used in: user

Found in path(s):
* /com-springsource-javax-servlet-2-5-0-jar/javax/servlet/resources/web-app_2_3.dtd
No license file was found, but licenses were detected in source scan.

Licensed to the Apache Software Foundation (ASF) under one or more
 contributor license agreements. See the NOTICE file distributed with
 this work for additional information regarding copyright ownership.
 The ASF licenses this file to You under the Apache License, Version 2.0
 (the "License"); you may not use this file except in compliance with
 the License. You may obtain a copy of the License at

     http://www.apache.org/licenses/LICENSE
2.0

 Unless required by applicable law or agreed to in writing, software
 distributed under the License is distributed on an "AS IS" BASIS,
 WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 See the License for the specific language governing permissions and
 limitations under the License.

Found in path(s):
* /com-springsource-javax-servlet-2-5-0-jar/javax/servlet/resources/datatypes.dtd

1.208 bluebird 3.7.2

1.208.1 Available under license :

The MIT License (MIT)

Copyright (c) 2013-2018 Petka Antonov

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
 OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.209 mkdirp 0.5.5

1.209.1 Available under license :

Copyright 2010 James Halliday (mail@substack.net)

This project is free software released under the MIT/X11 license:

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION

OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.210 spring-retry 1.2.5.RELEASE

1.210.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2013-2019 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/annotation/RecoverAnnotationRecoveryHandler.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-retry-1-2-5-release-sources-jar/org/springframework/classify/util/MethodInvoker.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/classify/util/AnnotationMethodResolver.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/classify/util/MethodResolver.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/annotation/Backoff.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/annotation/Recover.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/annotation/EnableRetry.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2006-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
* https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on
* an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the
* specific language governing permissions and limitations under the License.
*/

Found in path(s):
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/interceptor/RetryOperationsInterceptor.java
No license file was found, but licenses were detected in source scan.

/*

* Copyright 2006-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-retry-1-2-5-release-sources-
jar/org/springframework/retry/interceptor/StatefulRetryOperationsInterceptor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2006-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/policy/SimpleRetryPolicy.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/classify/SubclassClassifier.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/classify/BinaryExceptionClassifier.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at

*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/interceptor/FixedKeyGenerator.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/policy/CircuitBreakerRetryPolicy.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/policy/ExpressionRetryPolicy.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2006-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/backoff/ExponentialRandomBackOffPolicy.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/stats/MutableRetryStatistics.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/stats/ExponentialAverageRetryStatistics.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/stats/StatisticsRepository.java
*
/spring-retry-1-2-5-release-sources-jar/org/springframework/retry/stats/DefaultStatisticsRepository.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/stats/RetryStatisticsFactory.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/stats/DefaultRetryStatisticsFactory.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/stats/DefaultRetryStatistics.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/stats/StatisticsListener.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-retry-1-2-5-release-sources-jar/org/springframework/classify/util/MethodInvokerUtils.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2006-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-retry-1-2-5-release-sources-jar/org/springframework/classify/annotation/Classifier.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/backoff/SleepingBackOffPolicy.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/backoff/NoBackOffPolicy.java
*
 /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/backoff/StatelessBackOffPolicy.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/classify/ClassifierSupport.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/interceptor/MethodInvocationRecoverer.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/backoff/BackOffInterruptedException.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/backoff/BackOffContext.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/RetryState.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/policy/MapRetryContextCache.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/RetryListener.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/policy/RetryContextCache.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/listener/RetryListenerSupport.java
* /spring-retry-1-2-5-release-sources-
jar/org/springframework/retry/interceptor/NewMethodArgumentsIdentifier.java
*
 /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/ExhaustedRetryException.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/classify/Classifier.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/policy/TimeoutRetryPolicy.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/RetryContext.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/RetryPolicy.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/RetryStatistics.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/support/RetrySimulation.java
* /spring-retry-1-2-5-release-sources-
jar/org/springframework/retry/policy/RetryCacheCapacityExceededException.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/RetryCallback.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/RetryException.java
*
 /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/RetryOperations.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/policy/NeverRetryPolicy.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/backoff/BackOffPolicy.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/support/DefaultRetryState.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/TerminatedRetryException.java
* /spring-retry-1-2-5-release-sources-
jar/org/springframework/retry/interceptor/MethodArgumentsKeyGenerator.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/classify/ClassifierAdapter.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/backoff/Sleeper.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/support/RetrySynchronizationManager.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/policy/ExceptionClassifierRetryPolicy.java
*
 /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/RecoveryCallback.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/policy/CompositeRetryPolicy.java

* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/policy/AlwaysRetryPolicy.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/backoff/ObjectWaitSleeper.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/classify/PatternMatchingClassifier.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/support/RetrySimulator.java
* /spring-retry-1-2-5-release-sources-
jar/org/springframework/retry/policy/SoftReferenceMapRetryContextCache.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/classify/BackToBackPatternClassifier.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/classify/PatternMatcher.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2006-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/backoff/UniformRandomBackOffPolicy.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/context/RetryContextSupport.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/support/RetryTemplate.java
*
 /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/backoff/ExponentialBackOffPolicy.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/backoff/FixedBackOffPolicy.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
*/

Found in path(s):
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/annotation/CircuitBreaker.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-retry-1-2-5-release-sources-
jar/org/springframework/retry/annotation/AnnotationAwareRetryOperationsInterceptor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/annotation/Retryable.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/backoff/ThreadWaitSleeper.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/annotation/RetryConfiguration.java

*
/spring-retry-1-2-5-release-sources-jar/org/springframework/classify/util/SimpleMethodInvoker.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/interceptor/RetryInterceptorBuilder.java
* /spring-retry-1-2-5-release-sources-jar/org/springframework/retry/interceptor/Retryable.java

1.211 reactor-core 3.3.5.RELEASE

1.211.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2011-Present Pivotal Software Inc, All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxBufferTimeout.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxCreate.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoCollect.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoCreate.java
*
/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/Flux.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/BoundedElasticScheduler.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxPublish.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoSink.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2011-Present Pivotal Software Inc, All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/context/CoreContext.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2011-2018 Pivotal Software Inc, All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSwitchOnFirst.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxMetrics.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoBridges.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxFilterFuseable.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxExtensions.kt
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoProcessor.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoCacheTime.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/InstantPeriodicWorkerTask.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoExtensions.kt
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoPeekTerminal.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxOnBackpressureBufferTimeout.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/NonBlocking.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxBufferPredicate.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxReplay.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoFunctions.kt
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxBufferWhen.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxConcatMap.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxBufferBoundary.java

* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/EmitterProcessor.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoZip.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxFilter.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxWindowPredicate.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/Operators.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoWhen.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxBuffer.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoMetrics.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/concurrent/MpscLinkedQueue.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/SchedulerMetricDecorator.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoMetricsFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxCombineLatest.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoCompletionStage.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ReplayProcessor.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/Mono.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2011-2019 Pivotal Software Inc, All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   https://www.apache.org/licenses/LICENSE-2.0
 *
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/RingBuffer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2011-2019 Pivotal Software Inc, All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/concurrent/SpscArrayQueue.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/EventLoopProcessor.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/WorkQueueProcessor.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/concurrent/WaitStrategy.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/CorePublisher.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/TopicProcessor.java
No license file was found, but licenses were detected in source scan.

Copyright (c) 2019-Present Pivotal Software Inc, All Rights Reserved.
#
Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at
#
https://www.apache.org/licenses/LICENSE-2.0
#
Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
reactor.core.scheduler.ReactorBlockHoundIntegration

Found in path(s):
* /reactor-core-3-3-5-release-sources-1-jar/META-

INF/services/reactor.blockhound.integration.BlockHoundIntegration
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2011-2017 Pivotal Software Inc, All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/OperatorDisposables.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoSingleMono.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/OnNextFailureStrategy.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/util/context/Context4.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/BlockingOptionalMonoSubscriber.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxLimitRequest.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/context/Context2.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxIndex.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/context/Context5.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxIndexFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/context/Context3.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoExpand.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDelaySequence.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2011-Present VMware Inc. or its affiliates, All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/retry/ImmutableRetrySignal.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/retry/Retry.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/retry/RetrySpec.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/retry/RetryBackoffSpec.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxRetryWhen.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoRetryWhen.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2011-2017 Pivotal Software Inc, All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxTakeLastOne.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/InnerProducer.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSubscribeOnValue.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoToCompletableFuture.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxOnBackpressureLatest.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxError.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoRunnable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDematerialize.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxGenerate.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/BufferOverflowStrategy.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxLift.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxNameFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoPublishMulticast.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/context/Context0.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxHandleFuseable.java
*

/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoPublishOn.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxTakeUntilOther.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/SignalPeek.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoPeekFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSwitchIfEmpty.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/Disposables.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxGroupBy.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/GroupedFlux.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxContextStart.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxPublishMulticast.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/Disposable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoCancelOn.java
*
/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxArray.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelMergeSequential.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoOperator.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDistinct.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDetach.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoCollectList.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/ImmediateScheduler.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxWithLatestFrom.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelFluxOnAssembly.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxFlattenIterable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxTakeFuseable.java
*
/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDoOnEach.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/BlockingFirstSubscriber.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxGroupJoin.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxLogFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelMap.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelFlux.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoCurrentContext.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoSubscriberContext.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoDefaultIfEmpty.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelLog.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/SingleWorkerScheduler.java
*
/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoDelay.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/function/Tuple8.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxOnBackpressureBuffer.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/DelegateProcessor.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSampleTimeout.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxScanSeed.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoDoFinally.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/BlockingSingleSubscriber.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/SynchronousSink.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelLift.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSkip.java

* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoSource.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxMap.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/ElasticScheduler.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/context/ContextN.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoFlatMapMany.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxRetryPredicate.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoNameFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoTakeUntilOther.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxAutoConnect.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/function/Tuple3.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxRefCount.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSubscribeOnCallable.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/adapter/JdkFlowAdapter.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxRepeatWhen.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoRepeatWhen.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoSingle.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxOperator.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/WorkerTask.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxPeekFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDoFinally.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelThen.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDistinctUntilChanged.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoPeek.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoMap.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxFromMonoOperator.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSample.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxName.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDelaySubscription.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSubscribeOn.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/Logger.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/Hooks.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/SchedulerTask.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSink.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/Schedulers.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoIgnorePublisher.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxOnBackpressureBufferStrategy.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/PeriodicSchedulerTask.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxTakeWhile.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoDematerialize.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/CoreSubscriber.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoReduce.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoReduceSeed.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/function/Tuple7.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/context/Context.java

* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxNever.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxTakeUntil.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/function/Tuple4.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxRetry.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxStream.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/DelegateServiceScheduler.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoEmpty.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoHasElements.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoFlattenIterable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/DrainUtils.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSourceFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxMerge.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxFirstEmitting.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoDoFinallyFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxTake.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/PeriodicWorkerTask.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/SignalType.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoTimeout.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxMapSignal.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoCallableOnAssembly.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoFilterFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelArraySource.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/function/Tuple5.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/ParallelScheduler.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoCount.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoName.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoCallable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/BlockingLastSubscriber.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoNext.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoRetry.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxOnAssembly.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/Scannable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/package-info.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxMergeSequential.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoLift.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoFromFluxOperator.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxJust.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/ExecutorServiceWorker.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxRefCountGrace.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/function/Tuples.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/BlockingMonoSubscriber.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoSupplier.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoSequenceEqual.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxMapFuseable.java

* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelFluxName.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelPeek.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoSourceFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/UnicastProcessor.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ConnectableFluxOnAssembly.java
*
/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoDelaySubscription.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoHide.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoFromPublisher.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxTimeout.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoLog.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxMaterialize.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSkipUntil.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDefer.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoSubscribeOnCallable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxRepeatPredicate.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSource.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/SerializedSubscriber.java
*
/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoAny.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/concurrent/Queues.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoIgnoreElement.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/context/package-info.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/function/package-info.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSourceMonoFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoMapFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelRunOn.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/concurrent/package-info.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxFlatMap.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoRetryPredicate.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/BlockingIterable.java
*
/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxZip.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDistinctFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/concurrent/SpscLinkedArrayQueue.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelConcatMap.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxPublishOn.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxInterval.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxFilterWhen.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxConcatIterable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/Signal.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ConnectableFlux.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSkipWhile.java
*
/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxHandle.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoElapsed.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/DirectProcessor.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoOnErrorResume.java

* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoSourceFlux.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxZipIterable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoJust.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/package-info.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoSubscribeOn.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/SingleScheduler.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoElementAt.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxPeek.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/LambdaMonoSubscriber.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoAll.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/InternalMonoOperator.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/LambdaSubscriber.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoSwitchIfEmpty.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoDetach.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoMaterialize.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxOnBackpressureDrop.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoStreamCollector.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxAutoConnectFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxProcessor.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoRepeatPredicate.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxErrorOnRequest.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxUsing.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxJoin.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelFlatMap.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelMergeSort.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxElapsed.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxOnErrorResume.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/function/TupleExtensions.kt
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoIgnoreElements.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelFilter.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelGroup.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxHide.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoTakeLastOne.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/SignalLogger.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/package-info.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/function/Tuple6.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxWindowTimeout.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSkipLast.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoFilterWhen.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/package-info.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxScan.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelReduceSeed.java
*
 /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/ExecutorScheduler.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/InnerConsumer.java

* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSkipUntilOther.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelMergeReduce.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/context/Context1.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxCancelOn.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxConcatArray.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/adapter/package-info.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoNever.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoUsing.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxIterable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxTakeLast.java
*
/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/StrictSubscriber.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxRepeat.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSampleFirst.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/Exceptions.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoHasElement.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoDefer.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/InnerOperator.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoRepeat.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoSourceFluxFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoDelayUntil.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoFirst.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelSource.java
*
/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoFlatMap.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSwitchMap.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoIgnoreThen.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxRange.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxExpand.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoFilter.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDoFinallyFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoOnAssembly.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoHandle.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxLog.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ImmutableSignal.java
*
/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoLogFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoDelayElement.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoSubscribeOnValue.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxWindowBoundary.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/Loggers.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/Fuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxEmpty.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoHandleFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxWindow.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxSourceMono.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/function/Tuple2.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxWindowWhen.java

*
/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxCallableOnAssembly.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxCallable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelCollect.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/Scheduler.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/BaseSubscriber.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelFluxHide.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDefaultIfEmpty.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoError.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2019-Present Pivotal Software Inc, All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDeferWithContext.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoDeferWithContext.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelDoOnEach.java
*
/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/InternalFluxOperator.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/OptimizableOperator.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/InternalConnectableFluxOperator.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/ReactorBlockHoundIntegration.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ContextTrackingFunctionWrapper.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/annotation/NonNull.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/annotation/NonNullApi.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/annotation/Nullable.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2011-2019 Pivotal Software Inc, All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDoFirst.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDoFirstFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoDoFirst.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoDoFirstFuseable.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2011-2018 Pivotal Software Inc, All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/
/*
* Copyright (c) 2011-2017 Pivotal Software Inc, All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
 *
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoErrorSupplied.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxErrorSupplied.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/SourceProducer.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxLiftFuseable.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2011-2018 Pivotal Software Inc, All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelLiftFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/util/Metrics.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ConnectableFluxHide.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/scheduler/ReactorThreadFactory.java
*

/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoUsingWhen.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ConnectableLift.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ParallelMergeOrdered.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoLiftFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxUsingWhen.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/ConnectableLiftFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxMetricsFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxDoOnEachFuseable.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/FluxMergeOrdered.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/Traces.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/GroupedLiftFuseable.java
*
/reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/GroupedLift.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/QueueDrainSubscriber.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoDoOnEach.java
* /reactor-core-3-3-5-release-sources-1-jar/reactor/core/publisher/MonoDoOnEachFuseable.java

1.212 netty-tcnative 2.0.9.Final

1.212.1 Available under license :

No license file was found, but licenses were detected in source scan.

Bundle-License: http://www.apache.org/licenses/LICENSE-2.0

Found in path(s):
* /netty-tcnative-2-0-9-final-sources-1-jar/META-INF/MANIFEST.MF
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-tcnative-2-0-9-final-sources-1-jar/io/netty/internal/tcnative/CertificateVerifier.java

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/*
*  Licensed to the Apache Software Foundation (ASF) under one or more
*  contributor license agreements.  See the NOTICE file distributed with
*  this work for additional information regarding copyright ownership.
*  The ASF licenses this file to You under the Apache License, Version 2.0
 *  (the "License"); you may not use this file except in compliance with
*  the License.  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*/
```

Found in path(s):
* /netty-tcnative-2-0-9-final-sources-1-jar/io/netty/internal/tcnative/SSLContext.java
* /netty-tcnative-2-0-9-final-sources-1-jar/io/netty/internal/tcnative/SSL.java
* /netty-tcnative-2-0-9-final-sources-1-jar/io/netty/internal/tcnative/Buffer.java
* /netty-tcnative-2-0-9-final-sources-1-jar/io/netty/internal/tcnative/Library.java

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
```

* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-tcnative-2-0-9-final-sources-1-jar/io/netty/internal/tcnative/SniHostNameMatcher.java
* /netty-tcnative-2-0-9-final-sources-1-jar/io/netty/internal/tcnative/NativeStaticallyReferencedJniMethods.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-tcnative-2-0-9-final-sources-1-jar/io/netty/internal/tcnative/SessionTicketKey.java
* /netty-tcnative-2-0-9-final-sources-1-jar/io/netty/internal/tcnative/CertificateRequestedCallback.java

1.213 spring-framework 4.3.20.RELEASE

1.213.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/AlternativeJdkIdGenerator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/PatternMatchUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/AnnotationMetadata.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/VfsResource.java
*
 /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/AnnotatedTypeMetadata.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/annotation/SynthesizedAnnotation.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/annotation/AnnotationConfigurationException.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/SystemEnvironmentPropertySource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/JdkVersion.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/comparator/InstanceComparator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/converter/GenericConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/serializer/DefaultSerializer.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/AliasRegistry.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/converter/ConditionalGenericConverter.java
*
 /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/StringToCurrencyConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/StreamConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/support/ResourcePropertySource.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/annotation/SynthesizedAnnotationInvocationHandler.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/serializer/support/SerializationDelegate.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/StringToTimeZoneConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/serializer/support/SerializingConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/IdGenerator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/serializer/support/DeserializingConverter.java
*
 /spring-core-4-3-20-release-sources-jar/org/springframework/objenesis/SpringObjenesis.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/StringToLocaleConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/UpdateMessageDigestInputStream.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/MethodMetadata.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/Ordered.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/FallbackObjectToStringConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/InputStreamResource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/annotation/AliasFor.java

* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/StandardMethodMetadata.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/SimpleNamespaceContext.java
*
 /spring-core-4-3-20-release-sources-jar/org/springframework/util/JdkIdGenerator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/StringToCharsetConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/DefaultParameterNameDiscoverer.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/SimpleIdGenerator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/PriorityOrdered.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/EnumerablePropertySource.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/type/classreading/AnnotationMetadataReadingVisitor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/serializer/DefaultDeserializer.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/converter/Converter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/ResizableByteArrayOutputStream.java
*
 /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/StringToUUIDConverter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/classreading/MetadataReader.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/ConvertingPropertyEditorAdapter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/SimpleCommandLineArgsParser.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/ConfigurableConversionService.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/PropertySources.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/CommandLineArgs.java
No license file was found, but licenses were detected in source scan.

/***
* ASM: a very small and fast Java bytecode manipulation framework
* Copyright (c) 2000-2013 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*   contributors may be used to endorse or promote products derived from
*   this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
 "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/TypePath.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/TypeReference.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/classreading/ClassMetadataReadingVisitor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/AbstractConditionalEnumConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/GenericCollectionTypeResolver.java
*
 /spring-core-4-3-20-release-sources-jar/org/springframework/core/StandardReflectionParameterNameDiscoverer.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/task/SimpleAsyncTaskExecutor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/StringToNumberConverterFactory.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/ResolvableTypeProvider.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/FileCopyUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/NestedRuntimeException.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/NestedExceptionUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/support/PathMatchingResourcePatternResolver.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/VfsUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/FastByteArrayOutputStream.java
*
 /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/Resource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/MissingRequiredPropertiesException.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/annotation/AnnotationAttributes.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/CollectionFactory.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/ClassPathResource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/concurrent/FutureAdapter.java

* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/type/classreading/AnnotationReadingVisitorUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/WeakReferenceMonitor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/ReadOnlySystemAttributesMap.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/concurrent/ListenableFutureTask.java
*
/spring-core-4-3-20-release-sources-jar/org/springframework/core/io/UrlResource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/StreamUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/ControlFlowFactory.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/type/classreading/AbstractRecursiveAnnotationVisitor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/Conventions.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/comparator/CompoundComparator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/ResourceEditor.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/type/classreading/MethodMetadataReadingVisitor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/AbstractStaxHandler.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/ControlFlow.java
*
/spring-core-4-3-20-release-sources-jar/org/springframework/util/ConcurrencyThrottleSupport.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/SpringAsmInfo.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/util/concurrent/CompletableToListenableFutureAdapter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/StaxStreamXMLReader.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/StandardClassMetadata.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/PropertySource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/ErrorCoded.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/MethodClassKey.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/TypeUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/AntPathMatcher.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/CollectionToObjectConverter.java
*
/spring-core-4-3-20-release-sources-jar/org/springframework/core/env/CompositePropertySource.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/StringToCharacterConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/annotation/Order.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/ObjectUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/EnvironmentCapable.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/InputStreamSource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/ByteBufferConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/concurrent/SettableListenableFuture.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/MethodInvoker.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/ByteArrayResource.java
*
/spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/CollectionToArrayConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/DefaultConversionService.java

* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/support/PropertiesLoaderSupport.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/LinkedCaseInsensitiveMap.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/LocalVariableTableParameterNameDiscoverer.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/InvalidMimeTypeException.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/StandardAnnotationMetadata.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/StaxResult.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/concurrent/ListenableFuture.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/StaxSource.java
*
/spring-core-4-3-20-release-sources-jar/org/springframework/core/PrioritizedParameterNameDiscoverer.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/Base64Utils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/ResourceUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/converter/ConvertingComparator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/NestedCheckedException.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/PropertyPlaceholderHelper.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/ClassMetadata.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/StringToEnumConverterFactory.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/Assert.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/FileSystemUtils.java
*
/spring-core-4-3-20-release-sources-jar/org/springframework/core/env/AbstractPropertyResolver.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/ObjectToOptionalConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/Constants.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/MutablePropertySources.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/classreading/SimpleMetadataReader.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/StandardEnvironment.java

* /spring-core-4-3-20-release-sources-jar/org/springframework/core/task/AsyncListenableTaskExecutor.java
*
 /spring-core-4-3-20-release-sources-jar/org/springframework/util/SystemPropertyUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/DomUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/task/AsyncTaskExecutor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/PropertySourcesPropertyResolver.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/Log4jConfigurer.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/lang/UsesSunHttpServer.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/cglib/SpringCglibInfo.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/filter/AspectJTypeFilter.java

*
/spring-core-4-3-20-release-sources-jar/org/springframework/util/CompositeIterator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/ExceptionTypeFilter.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/type/filter/AbstractTypeHierarchyTraversingFilter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/support/ResourceArrayPropertyEditor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/backoff/BackOffExecution.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/type/classreading/RecursiveAnnotationArrayVisitor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/StaxUtils.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/ArrayToCollectionConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/filter/AssignableTypeFilter.java
*
/spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/StaxStreamHandler.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/converter/ConditionalConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/NestedIOException.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/ObjectToArrayConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/PropertiesPropertySource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/lang/UsesJava8.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/XmlValidationModeDetector.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/StringToCollectionConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/IdToEntityConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/ArrayToStringConverter.java
*
/spring-core-4-3-20-release-sources-jar/org/springframework/util/CustomizableThreadCreator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/ConversionServiceFactory.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/SerializationUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/MapToMapConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/filter/AbstractClassTestingTypeFilter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/backoff/BackOff.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/PropertiesToStringConverter.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/ZoneIdToTimeZoneConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/lang/UsesJava7.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/cglib/core/SpringNamingPolicy.java
*
/spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/ObjectToCollectionConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/ObjectToStringConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/ArrayToObjectConverter.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/ZonedDateTimeToCalendarConverter.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/CollectionToCollectionConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/ArrayToArrayConverter.java

* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/MapPropertySource.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/ParameterizedTypeReference.java
No license file was found, but licenses were detected in source scan.

/***
* ASM: a very small and fast Java bytecode manipulation framework
* Copyright (c) 2000-2011 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*   contributors may be used to endorse or promote products derived from
*   this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
 "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS

* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/FieldVisitor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/Label.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/Item.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/Frame.java
*
 /spring-core-4-3-20-release-sources-jar/org/springframework/asm/ClassReader.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/AnnotationVisitor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/ModuleWriter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/Context.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/MethodVisitor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/Edge.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/Type.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/Attribute.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/MethodWriter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/Handler.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/CurrentFrame.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/Handle.java
*
 /spring-core-4-3-20-release-sources-jar/org/springframework/asm/ModuleVisitor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/Opcodes.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/ClassWriter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/ByteVector.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/ClassVisitor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/FieldWriter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/asm/AnnotationWriter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.

*/

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/NamedThreadLocal.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/NamedInheritableThreadLocal.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/annotation/AnnotationUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/AbstractEnvironment.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/DomContentHandler.java
*
 /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/StaxEventXMLReader.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/SimpleAliasRegistry.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/support/LocalizedResourceHelper.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/support/SpringFactoriesLoader.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/AbstractXMLStreamReader.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/SimpleCommandLinePropertySource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/BridgeMethodResolver.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/TransformerUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/task/support/ExecutorServiceAdapter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/filter/AnnotationTypeFilter.java
*
 /spring-core-4-3-20-release-sources-
jar/org/springframework/core/type/classreading/AnnotationAttributesReadingVisitor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/ClassUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/JOptCommandLinePropertySource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/XMLEventStreamWriter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/TypeDescriptor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/StringUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/AbstractResource.java
* /spring-core-4-3-20-release-sources-

jar/org/springframework/core/type/classreading/SimpleMetadataReaderFactory.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/ReflectionUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/GenericTypeResolver.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/ResolvableType.java
*
/spring-core-4-3-20-release-sources-jar/org/springframework/core/io/AbstractFileResolvingResource.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/util/concurrent/ListenableFutureCallbackRegistry.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/AbstractStaxXMLReader.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/StaxEventHandler.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/MimeType.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/ConcurrentReferenceHashMap.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/PathResource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/AttributeAccessorSupport.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/ConfigurableEnvironment.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/annotation/AnnotatedElementUtils.java
*
/spring-core-4-3-20-release-sources-
jar/org/springframework/core/annotation/AnnotationAwareOrderComparator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/ConversionUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/MimeTypeUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/Property.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/XMLEventStreamReader.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/SerializableTypeWrapper.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/MethodParameter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/ConversionException.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/support/VfsPatternUtils.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/filter/RegexPatternTypeFilter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/filter/TypeFilter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/ContextResource.java
*
 /spring-core-4-3-20-release-sources-jar/org/springframework/core/style/ValueStyler.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/support/ResourcePatternResolver.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/serializer/Deserializer.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/NumberToCharacterConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/serializer/Serializer.java
*

/spring-core-4-3-20-release-sources-jar/org/springframework/core/SpringVersion.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/PathMatcher.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/style/DefaultToStringStyler.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/InfrastructureProxy.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/DescriptiveResource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/WritableResource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/ErrorHandler.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/task/SyncTaskExecutor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/comparator/InvertibleComparator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/comparator/NullSafeComparator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/comparator/BooleanComparator.java
*
/spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/CharacterToNumberFactory.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/task/TaskRejectedException.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/CommonsLogWriter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/ConstantException.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/StringToBooleanConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/style/StylerUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/task/TaskTimeoutException.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/AttributeAccessor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/SimpleTransformErrorListener.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/StringToArrayConverter.java
*
/spring-core-4-3-20-release-sources-jar/org/springframework/core/style/DefaultValueStyler.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/ExceptionDepthComparator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/MultiValueMap.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/FileSystemResourceLoader.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/SimpleSaxErrorHandler.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/StringToPropertiesConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/style/ToStringStyler.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/task/TaskExecutor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/task/support/ConcurrentExecutorAdapter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/classreading/MetadataReaderFactory.java
*
/spring-core-4-3-20-release-sources-jar/org/springframework/core/SmartClassLoader.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/comparator/ComparableComparator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/ParameterNameDiscoverer.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/ClassRelativeResourceLoader.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/serializer/support/SerializationFailedException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/backoff/FixedBackOff.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/PropertiesPersister.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/convert/support/NumberToNumberConverterFactory.java
*
 /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/EnumToStringConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/annotation/AnnotationAttributeExtractor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/support/EncodedResource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/DecoratingProxy.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/SocketUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/support/PropertySourceFactory.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/CollectionUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/CommandLinePropertySource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/ObjectToObjectConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/task/TaskDecorator.java
*
 /spring-core-4-3-20-release-sources-jar/org/springframework/core/OverridingClassLoader.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/StringValueResolver.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/InstanceFilter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/DecoratingClassLoader.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/concurrent/ListenableFutureCallback.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/Environment.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/concurrent/SuccessCallback.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/ConverterNotFoundException.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/ConversionFailedException.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/StopWatch.java
* /spring-core-4-3-20-release-sources-
jar/org/springframework/core/type/classreading/RecursiveAnnotationAttributesVisitor.java
*
 /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/support/ResourceRegion.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/task/support/TaskExecutorAdapter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/DefaultResourceLoader.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/GenericConversionService.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/OrderComparator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/annotation/SynthesizingMethodParameter.java

* /spring-core-4-3-20-release-sources-jar/org/springframework/core/env/ConfigurablePropertyResolver.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/DigestUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/LinkedMultiValueMap.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/xml/AbstractXMLReader.java
*
/spring-core-4-3-20-release-sources-jar/org/springframework/core/annotation/DefaultAnnotationAttributeExtractor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/support/ResourcePatternUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/concurrent/ListenableFutureAdapter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/annotation/MapAnnotationAttributeExtractor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/converter/ConverterFactory.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/lang/UsesSunMisc.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/CollectionToStringConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/ConversionService.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/backoff/ExponentialBackOff.java
*
/spring-core-4-3-20-release-sources-jar/org/springframework/core/env/PropertyResolver.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/type/classreading/CachingMetadataReaderFactory.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/support/DefaultPropertySourceFactory.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/support/PropertiesLoaderUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/AutoPopulatingList.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/NumberUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/concurrent/FailureCallback.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/MethodIntrospector.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/util/DefaultPropertiesPersister.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/ProtocolResolver.java
*
/spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/converter/ConverterRegistry.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/style/ToStringCreator.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/ConfigurableObjectInputStream.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/FileSystemResource.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/annotation/OrderUtils.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/SpringProperties.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/IntegerToEnumConverterFactory.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/annotation/AbstractAliasAwareAnnotationAttributeExtractor.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/convert/support/EnumToIntegerConverter.java
* /spring-core-4-3-20-release-sources-jar/org/springframework/core/io/ResourceLoader.java

1.214 reactor-netty 0.9.7.RELEASE

1.214.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (c) 2011-Present VMware, Inc. or its affiliates, All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*       https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):

* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpServer.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/WebsocketClientSpecImpl.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpClientBootstrap.java
*
 /reactor-netty-0-9-7-release-sources-jar/reactor/netty/ConnectionObserver.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/channel/MonoSendMany.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/channel/AbortedException.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/WebsocketServerSpec.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/FutureMono.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpServerBootstrap.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpServerDoOn.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpClientDoOn.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpClientUnsecure.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpConnection.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpServerHandle.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpClientUnproxy.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientForm.java
*
 /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientFinalizer.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpServerTcpConfig.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpServerSecure.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpServerObserve.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/DisposableChannel.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpClientSecure.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/package-info.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/channel/ChannelMetricsHandler.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpClientOperator.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/HttpMetricsRecorder.java

* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/DefaultHttpServerRoutes.java
*
 /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientMetricsHandler.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpClientRunOn.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpClient.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/resources/package-info.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/AccessLog.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/channel/FluxReceive.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/resources/PooledConnectionProvider.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/SimpleCompressionHandler.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/websocket/WebsocketSpecImpl.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpClientRunOn.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/resources/DefaultLoopEpoll.java
*
 /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpClientOperator.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpServerOperator.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/ReactorNetty.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpServerBind.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientObserve.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/Connection.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/WebsocketClientOperations.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpClientConnect.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpServerMetricsRecorder.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpServerConfiguration.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/ConnectionInfo.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/websocket/WebsocketSpec.java
*
 /reactor-netty-0-9-7-release-sources-jar/reactor/netty/resources/ConnectionProvider.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpServerOperator.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/package-info.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/Metrics.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpServer.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpClientBootstrap.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpServerBind.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpResponseDecoderSpec.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpServerDoOnConnection.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpClientDoOn.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/resources/DefaultLoop.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpServerUnsecure.java
*
 /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpResources.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/package-info.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpInbound.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpRequestDecoderSpec.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/AccessLogHandlerH2.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/WebsocketFinalizer.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/AccessLogHandler.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/ProxyProvider.java

* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/resources/NewConnectionProvider.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientConfiguration.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpServerDoOn.java
*
 /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientConnect.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientOnConnectMap.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/channel/ChannelOperationsHandler.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientOperator.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/resources/DefaultLoopKQueue.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpServerHandle.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/HttpDecoderSpec.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/websocket/WebsocketInbound.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/HttpProtocol.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/NettyInbound.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/HttpInfos.java
*
 /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpClientObserve.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/ByteBufFlux.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientHeadersWhen.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpClientObserve.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/UriEndpointFactory.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpServerChannelGroup.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientMetricsRecorder.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpServerMetricsHandler.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/channel/MonoSend.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpServerState.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/channel/package-info.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpClientProxy.java
*
 /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpServerRequest.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/HttpResources.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/InetSocketAddressUtil.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/UriEndpoint.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/channel/ChannelOperations.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/resources/ColocatedEventLoopGroup.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientCookieWhen.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpServer.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/channel/BootstrapHandlers.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/NettyPipeline.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HAProxyMessageReader.java
*
 /reactor-netty-0-9-7-release-sources-jar/reactor/netty/ChannelBindException.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpPredicate.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/RedirectClientException.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/package-info.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientResponse.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpOperations.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientState.java

* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/NettyOutbound.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/package-info.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/WebsocketServerSpecImpl.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpServerRunOn.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientCookie.java
*
 /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/HttpOperations.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientDoOnError.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientHeaders.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpServerRoutes.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/MicrometerHttpServerMetricsRecorder.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientTcpConfig.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/ByteBufMono.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClient.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/Http2StreamBridgeHandler.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/websocket/WebsocketOutbound.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/SslProvider.java
*
 /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/WebsocketClientSpec.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/resources/DefaultLoopNativeDetector.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/channel/MicrometerChannelMetricsRecorder.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpServerOperations.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientDoOn.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/resources/PooledConnectionProviderMetrics.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpServerBind.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/MicrometerHttpMetricsRecorder.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpClient.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/WebsocketServerOperations.java
*
 /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpClientConnect.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpResources.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpServerRunOn.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpServerSecure.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/DisposableServer.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpOutbound.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpServerObserve.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpServerOperator.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientOperations.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/channel/MeterKey.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpServerObserve.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/resources/LoopResources.java
*
 /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/ProxyProtocolSupportType.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/channel/AddressResolverGroupMetrics.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/channel/ChannelMetricsRecorder.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientInfos.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/PrematureCloseException.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/udp/UdpServerBootstrap.java

* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/channel/ByteBufAllocatorMetrics.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/MicrometerHttpClientMetricsRecorder.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientRequest.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientSecure.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/package-info.java
*
 /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpTrafficHandler.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/client/HttpClientFormEncoder.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HttpServerResponse.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/resources/DefaultLoopResources.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/server/HAProxyMessageDetector.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/tcp/TcpUtils.java
* /reactor-netty-0-9-7-release-sources-jar/reactor/netty/http/Cookies.java

1.215 google-http-client 1.15.0-rc

1.215.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2012 Google Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/LoggingInputStream.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/StreamingContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/ByteCountingOutputStream.java
* /google-http-client-1-15-0-rc-sources-1-
jar/com/google/api/client/testing/http/javanet/MockHttpURLConnection.java
*
 /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/http/FixedClock.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/EmptyContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/json/JsonObjectParser.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/json/webtoken/JsonWebSignature.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/http/json/MockJsonFactory.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpEncoding.java

* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/LoggingByteArrayOutputStream.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/json/webtoken/JsonWebToken.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/util/LogRecordingHandler.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/http/json/MockJsonGenerator.java
*
 /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/LoggingOutputStream.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/ByteArrayStreamingContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/IOUtils.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/http/json/MockJsonParser.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/ObjectParser.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/SslUtils.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Base64.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/StringUtils.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpMediaType.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Clock.java
*
 /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/http/javanet/package-info.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/GZipEncoding.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/util/package-info.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpEncodingStreamingContent.java
No license file was found, but licenses were detected in source scan.

/*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/apache/HttpExtensionMethod.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpMethods.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2013 Google Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/http/apache/package-info.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/util/TestableByteArrayInputStream.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpBackOffIOExceptionHandler.java
*
 /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/http/apache/MockHttpClient.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Sets.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/util/MockBackOff.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Joiner.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/util/TestableByteArrayOutputStream.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Maps.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Beta.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Collections2.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpBackOffUnsuccessfulResponseHandler.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Strings.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/json/package-info.java
*
 /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/json/MockJsonParser.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/util/SecurityTestUtils.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/SecurityUtils.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/apache/SSLSocketFactoryExtension.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/json/MockJsonGenerator.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/util/MockSleeper.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Lists.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/MultipartContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Sleeper.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/BackOffUtils.java
*
 /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/json/MockJsonFactory.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Objects.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Charsets.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpIOExceptionHandler.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Throwables.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/json/webtoken/package-info.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Preconditions.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/ByteStreams.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/NanoClock.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/PemReader.java

No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2010 Google Inc.J
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/json/JsonFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2010 Google Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/json/rpc2/JsonRpcRequest.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpRequest.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/LoggingStreamingContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/GenericData.java
*
/google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/FieldInfo.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/apache/package-info.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/xml/atom/Atom.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/UrlEncodedContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpExecuteInterceptor.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/xml/package-info.java

* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/DateTime.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/DataMap.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/ClassInfo.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/xml/Xml.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpResponseInterceptor.java
*
/google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/http/MockLowLevelHttpResponse.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/apache/ApacheHttpResponse.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpResponseException.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/http/MockLowLevelHttpRequest.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/escape/package-info.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/escape/CharEscapers.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/json/GenericJson.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Key.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/escape/Escaper.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/json/Json.java
*
/google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/json/package-info.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/http/MockHttpTransport.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/xml/XmlObjectParser.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/json/rpc2/package-info.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/escape/PercentEscaper.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/package-info.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/xml/XmlHttpContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/json/package-info.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/javanet/NetHttpRequest.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/xml/XmlNamespaceDictionary.java
*
/google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/escape/UnicodeEscaper.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/LowLevelHttpResponse.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/InputStreamContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpTransport.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/javanet/NetHttpTransport.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/json/CustomizeJsonParser.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/javanet/NetHttpResponse.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpUnsuccessfulResponseHandler.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpHeaders.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/GenericUrl.java
*
/google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/xml/atom/AtomFeedParser.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/UrlEncodedParser.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/xml/AbstractXmlHttpContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpResponse.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/escape/Platform.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/ArrayMap.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/javanet/package-info.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/xml/atom/package-info.java

* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/apache/ContentEntity.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/xml/atom/AbstractAtomFeedParser.java
*
/google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/json/JsonToken.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/http/MockHttpContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/json/JsonParser.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/json/JsonGenerator.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/xml/GenericXml.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/LowLevelHttpRequest.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/apache/ApacheHttpRequest.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/json/JsonHttpContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/xml/package-info.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/apache/ApacheHttpTransport.java
*
/google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/package-info.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2011 Google Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /google-http-client-1-15-0-rc-sources-1-
jar/com/google/api/client/testing/http/MockHttpUnsuccessfulResponseHandler.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/ExponentialBackOff.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/AbstractHttpContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/BackOff.java
*
/google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Types.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/ArrayValueMap.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/http/json/package-info.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/BasicAuthentication.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/NullValue.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpStatusCodes.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/json/JsonString.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Value.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/ExponentialBackOffPolicy.java

* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpRequestInitializer.java
*
/google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/xml/atom/package-info.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/ByteArrayContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/http/HttpTesting.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/xml/atom/AtomContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/testing/http/package-info.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/AbstractInputStreamContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/util/Data.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/BackOffPolicy.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/FileContent.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/UriTemplate.java
* /google-http-client-1-15-0-rc-sources-1-jar/com/google/api/client/http/HttpRequestFactory.java

1.216 sizeof-agent 1.0.1

1.216.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this

License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided

that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.217 spring-expression 4.3.20.RELEASE

1.217.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/EvaluationException.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/standard/TokenKind.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/BooleanLiteral.java
*
 /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/SpelParseException.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OpNE.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/FloatLiteral.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/ExpressionException.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/LongLiteral.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/IntLiteral.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/ParseException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/TypeCode.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/Indexer.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/SpelEvaluationException.java
*

/spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/support/ReflectivePropertyAccessor.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OpEQ.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/SpelNodeImpl.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/support/ReflectiveMethodResolver.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/standard/Tokenizer.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/EvaluationContext.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/ValueRef.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/ast/ConstructorReference.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/CodeFlow.java
*
/spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/Operator.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OperatorMatches.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/FormatHelper.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/Elvis.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/MethodReference.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/support/StandardEvaluationContext.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/support/SimpleEvaluationContext.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/TypeReference.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/support/DataBindingMethodResolver.java
*
/spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/standard/SpelExpression.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/FunctionReference.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/support/DataBindingPropertyAccessor.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OpPlus.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/StringLiteral.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/SpelMessage.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/BeanResolver.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OpDivide.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/Selection.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OpMinus.java
*
/spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OpModulus.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OpMultiply.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/support/StandardOperatorOverloader.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/InternalParseException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
*/

Found in path(s):
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/standard/SpelExpressionParser.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/SpelCompilerMode.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OpLT.java
*
/spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/QualifiedIdentifier.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/RealLiteral.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/PropertyAccessor.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/CompilablePropertyAccessor.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OpLE.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OpOr.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/VariableReference.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/standard/Token.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/InlineList.java
*
/spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/InlineMap.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/AstUtils.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/SpelNode.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/support/ReflectiveConstructorResolver.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/TypedValue.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OperatorNot.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/Identifier.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/CompiledExpression.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/support/StandardTypeLocator.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OperatorPower.java
*
/spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OpGE.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/support/StandardTypeComparator.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/common/ExpressionUtils.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/Assign.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OperatorBetween.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OpGT.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/Literal.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/support/ReflectiveConstructorExecutor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2009 the original author or authors.
*

* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/ExpressionParser.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/common/TemplateAwareExpressionParser.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OpDec.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/BeanReference.java
*
 /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/ast/PropertyOrFieldReference.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/Expression.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/common/CompositeStringExpression.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/standard/SpelCompiler.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ExpressionState.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/Ternary.java
* /spring-expression-4-3-20-release-sources-1-

jar/org/springframework/expression/spel/SpelParserConfiguration.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OpInc.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/NullLiteral.java
*
/spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/standard/InternalSpelExpressionParser.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/AccessException.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/support/ReflectionHelper.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OperatorInstanceof.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/support/StandardTypeConverter.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/common/LiteralExpression.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/ast/CompoundExpression.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/support/ReflectiveMethodExecutor.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/Projection.java
*
/spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/spel/ast/OpAnd.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/OperatorOverloader.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/ConstructorResolver.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/spel/support/BooleanTypedValue.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/ParserContext.java
*
/spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/MethodResolver.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/TypeLocator.java
* /spring-expression-4-3-20-release-sources-1-

jar/org/springframework/expression/ExpressionInvocationTargetException.java
* /spring-expression-4-3-20-release-sources-1-
jar/org/springframework/expression/common/TemplateParserContext.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/ConstructorExecutor.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/Operation.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/MethodExecutor.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/MethodFilter.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/TypeConverter.java
* /spring-expression-4-3-20-release-sources-1-jar/org/springframework/expression/TypeComparator.java

1.218 spring-orm 4.3.20.RELEASE

1.218.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/EntityManagerHolder.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/PersistenceManagerHolder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/vendor/SpringHibernateJpaPersistenceProvider.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/HibernateTemplate.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/support/OpenEntityManagerInViewFilter.java
*
/spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/support/AsyncRequestInterceptor.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/SpringSessionSynchronization.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/support/OpenEntityManagerInViewInterceptor.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/support/OpenSessionInViewFilter.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/support/AsyncRequestInterceptor.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/HibernateTemplate.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/support/OpenSessionInViewFilter.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/support/OpenPersistenceManagerInViewFilter.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/support/AsyncRequestInterceptor.java
*
/spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/persistenceunit/MutablePersistenceUnitInfo.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/support/PersistenceAnnotationBeanPostProcessor.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/persistenceunit/ClassFileTransformerAdapter.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/HibernateCallback.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/persistenceunit/PersistenceUnitReader.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/JpaSystemException.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/HibernateTransactionManager.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/HibernateCallback.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/support/SpringPersistenceManagerProxyBean.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/persistenceunit/SpringPersistenceUnitInfo.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/TransactionAwarePersistenceManagerFactoryProxy.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/LocalRegionFactoryProxy.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/LocalPersistenceManagerFactoryBean.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/FilterDefinitionFactoryBean.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/DefaultJdoDialect.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/support/OpenPersistenceManagerInViewInterceptor.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/PersistenceManagerFactoryUtils.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/JdoDialect.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/HibernateOptimisticLockingFailureException.java

* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/HibernateOptimisticLockingFailureException.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
  * Create a transactional EntityManager proxy for the given EntityManagerFactory.
  * @param emf the EntityManagerFactory to obtain EntityManagers from as needed
  * @param properties the properties to be passed into the
  * {@code createEntityManager} call (may be {@code null})
  * @param entityManagerInterfaces
 the interfaces to be implemented by the
  * EntityManager. Allows the addition or specification of proprietary interfaces.
  * @return a shareable transactional EntityManager proxy
  */
```

Found in path(s):
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/SharedEntityManagerCreator.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
```

*/

Found in path(s):
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/HibernateSystemException.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/EntityManagerFactoryInfo.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/LocalDataSourceConnectionProvider.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/LocalJtaDataSourceConnectionProvider.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/support/BlobStringType.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/SpringTransactionFactory.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/support/ScopedBeanInterceptor.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/JdoSystemException.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/HibernateExceptionTranslator.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/support/BlobSerializableType.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/support/AbstractLobType.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/SpringJtaSessionContext.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/SpringSessionContext.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/support/BlobByteArrayType.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/SessionHolder.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/JpaObjectRetrievalFailureException.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/HibernateExceptionTranslator.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/HibernateQueryException.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/persistenceunit/PersistenceUnitManager.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/SpringSessionSynchronization.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/JpaOptimisticLockingFailureException.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/HibernateJdbcException.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/support/IdTransferringMergeEventListener.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/JdoObjectRetrievalFailureException.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/EntityManagerProxy.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/HibernateSystemException.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/SessionHolder.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/vendor/Database.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/HibernateJdbcException.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/support/ClobStringType.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/TypeDefinitionBean.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/persistenceunit/PersistenceUnitPostProcessor.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/AbstractSessionFactoryBean.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/JdoResourceFailureException.java

* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/JdoUsageException.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/TransactionAwareDataSourceConnectionProvider.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/HibernateObjectRetrievalFailureException.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/HibernateQueryException.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/HibernateObjectRetrievalFailureException.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/LocalTransactionManagerLookup.java
*
/spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/JdoOptimisticLockingFailureException.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either exprShess or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/support/StandardPersistenceManagerProxyBean.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
```

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/support/OpenSessionInViewInterceptor.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/JpaDialect.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/ConfigurableJtaPlatform.java
*
/spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/vendor/OpenJpaDialect.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/persistenceunit/SmartPersistenceUnitInfo.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/HibernateAccessor.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/LocalSessionFactoryBuilder.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/LocalSessionFactoryBean.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/DefaultJpaDialect.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/SpringFlushSynchronization.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/support/OpenSessionInterceptor.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/HibernateInterceptor.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/HibernateOperations.java
*
/spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/LocalSessionFactoryBean.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/vendor/SpringHibernateEjbPersistenceProvider.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/support/HibernateDaoSupport.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/EntityManagerFactoryAccessor.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/vendor/EclipseLinkJpaDialect.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/support/OpenSessionInterceptor.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/support/HibernateDaoSupport.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/annotation/AnnotationSessionFactoryBean.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/LocalEntityManagerFactoryBean.java
*
/spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/SessionFactoryUtils.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/JpaTransactionManager.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/HibernateOperations.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/SpringSessionContext.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/vendor/OpenJpaVendorAdapter.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate4/SessionFactoryUtils.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/hibernate3/HibernateTransactionManager.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jdo/JdoTransactionManager.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.

*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/EntityManagerFactoryUtils.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/vendor/HibernateJpaDialect.java
* /spring-orm-4-3-20-release-sources-1-
jar/org/springframework/orm/ObjectOptimisticLockingFailureException.java
*
 /spring-orm-4-3-20-release-sources-1-
jar/org/springframework/orm/jpa/vendor/HibernateJpaSessionFactoryBean.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/support/SharedEntityManagerBean.java
* /spring-orm-4-3-20-release-sources-1-
jar/org/springframework/orm/jpa/LocalContainerEntityManagerFactoryBean.java
* /spring-orm-4-3-20-release-sources-1-
jar/org/springframework/orm/hibernate4/support/OpenSessionInViewInterceptor.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/JpaVendorAdapter.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/ObjectRetrievalFailureException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):

* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/AbstractEntityManagerFactoryBean.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/vendor/EclipseLinkJpaVendorAdapter.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/persistenceunit/DefaultPersistenceUnitManager.java
*
/spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/vendor/AbstractJpaVendorAdapter.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/vendor/HibernateJpaVendorAdapter.java
* /spring-orm-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/ExtendedEntityManagerCreator.java

1.219 spring-aop 4.3.20.RELEASE

1.219.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/config/AdvisorComponentDefinition.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/scope/ScopedObject.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/dynamic/BeanFactoryRefreshableTargetSource.java
*
/spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/DynamicMethodMatcherPointcut.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/adapter/DefaultAdvisorAdapterRegistry.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/interceptor/ConcurrencyThrottleInterceptor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/AspectJAopUtils.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/config/ConfigBeanDefinitionParser.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/PointcutAdvisor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/PoolingConfig.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/StaticMethodMatcherPointcut.java

* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/HotSwappableTargetSource.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/config/AspectJAutoProxyBeanDefinitionParser.java
*
/spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/autoproxy/TargetSourceCreator.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/config/PointcutComponentDefinition.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/support/DelegatePerTargetObjectIntroductionInterceptor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/interceptor/DebugInterceptor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/AbstractGenericPointcutAdvisor.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/autoproxy/ProxyCreationContext.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/AopProxyFactory.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/autoproxy/InfrastructureAdvisorAutoProxyCreator.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/JdkRegexpMethodPointcut.java
*
/spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/AspectInstanceFactory.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/config/AdviceEntry.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/AbstractPointcutAdvisor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/config/MethodLocatingFactoryBean.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/DefaultPointcutAdvisor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/DynamicIntroductionAdvice.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/AopInvocationException.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/aspectj/annotation/NotAnAtAspectException.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/AspectJProxyUtils.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/IntroductionInfo.java
*
/spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/LazyInitTargetSource.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/AopConfigException.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/AopContext.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/SingletonTargetSource.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/MethodBeforeAdvice.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/adapter/MethodBeforeAdviceAdapter.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/adapter/ThrowsAdviceAdapter.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/config/SpringConfiguredBeanDefinitionParser.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/AfterReturningAdvice.java
*
/spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/interceptor/ExposeBeanNameAdvisors.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/config/PointcutEntry.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/ProxyConfig.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/adapter/UnknownAdviceTypeException.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/adapter/AdvisorAdapter.java
* /spring-aop-4-3-20-release-sources-1-

jar/org/springframework/aop/framework/adapter/AfterReturningAdviceAdapter.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/TruePointcut.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/ThreadLocalTargetSourceStats.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/config/AdvisorEntry.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/scope/DefaultScopedObject.java
*
/spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/IntroductionAdvisor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/AopProxy.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/support/DefaultBeanFactoryPointcutAdvisor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/DelegatingIntroductionInterceptor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/dynamic/Refreshable.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/TrueClassFilter.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/AbstractExpressionPointcut.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/Pointcut.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/EmptyTargetSource.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/AbstractLazyCreationTargetSource.java
*
/spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/config/ScopedProxyBeanDefinitionDecorator.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/adapter/GlobalAdvisorAdapterRegistry.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/adapter/AdvisorAdapterRegistrationManager.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/SimpleBeanTargetSource.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/Advisor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/config/AopNamespaceHandler.java
No license file was found, but licenses were detected in source scan.

/*<
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/TargetSource.java

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/BeforeAdvice.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/RawTargetAccess.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/config/AspectEntry.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/AopInfrastructureBean.java
*
 /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/IntroductionInterceptor.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/InterceptorAndDynamicMethodMatcher.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/SpringProxy.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/ClassFilter.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/AdvisedSupportListener.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/AfterAdvice.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/config/AspectComponentDefinition.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.

*/

Found in path(s):
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/DefaultIntroductionAdvisor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/AbstractAspectJAdvice.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/aspectj/annotation/InstantiationModelAwarePointcutAdvisorImpl.java
*
/spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/ProxyCreatorSupport.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/scope/ScopedProxyFactoryBean.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/RootClassFilter.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/AdvisedSupport.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/adapter/AdvisorAdapterRegistry.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/adapter/ThrowsAdviceInterceptor.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/autoproxy/BeanFactoryAdvisorRetrievalHelper.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/adapter/MethodBeforeAdviceInterceptor.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/aspectj/annotation/AbstractAspectJAdvisorFactory.java
*
/spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/annotation/AspectJProxyFactory.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/target/AbstractPrototypeBasedTargetSource.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/interceptor/SimpleAsyncUncaughtExceptionHandler.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/config/AopConfigUtils.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/autoproxy/target/AbstractBeanFactoryBasedTargetSourceCreator.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/DeclareParentsAdvisor.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/aspectj/annotation/ReflectiveAspectJAdvisorFactory.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/ProxyProcessorSupport.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/aspectj/MethodInvocationProceedingJoinPoint.java
*
/spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/DynamicMethodMatcher.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/SimpleAspectInstanceFactory.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/config/AopNamespaceUtils.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/IntroductionInfoSupport.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/support/StaticMethodMatcherPointcutAdvisor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/CglibAopProxy.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/AbstractAdvisingBeanPostProcessor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/AbstractRegexpMethodPointcut.java

* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/AbstractBeanFactoryBasedTargetSource.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/autoproxy/AbstractAutoProxyCreator.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/StaticMethodMatcher.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/adapter/AfterReturningAdviceInterceptor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/MethodMatcher.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/DefaultAdvisorChainFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2006 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/ExpressionPointcut.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/InstantiationModelAwarePointcutAdvisor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/AspectJPrecedenceInformation.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
*/

Found in path(s):
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/ThrowsAdvice.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/TrueMethodMatcher.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/CommonsPool2TargetSource.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/AspectJAfterAdvice.java
*
 /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/ObjenesisCglibAopProxy.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/Advised.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/AbstractPoolingTargetSource.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/aspectj/autoproxy/AspectJPrecedenceComparator.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/autoproxy/target/QuickTargetSourceCreator.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/ReflectiveMethodInvocation.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/AspectJMethodBeforeAdvice.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/AbstractSingletonProxyFactoryBean.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/MethodMatchers.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/AspectJAroundAdvice.java
*
 /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/annotation/AspectJAdvisorFactory.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/autoproxy/AbstractBeanFactoryAwareAdvisingPostProcessor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/CommonsPoolTargetSource.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/aspectj/annotation/PrototypeAspectInstanceFactory.java

* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/AspectJAfterThrowingAdvice.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/SingletonAspectInstanceFactory.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/ProxyMethodInvocation.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/autoproxy/AutoProxyUtils.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/DefaultAopProxyFactory.java
*
/spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/Pointcuts.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/TargetClassAware.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/ControlFlowPointcut.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/scope/ScopedProxyUtils.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/ComposablePointcut.java
*
/spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/interceptor/AsyncExecutionAspectSupport.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/interceptor/JamonPerformanceMonitorInterceptor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/NameMatchMethodPointcut.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/interceptor/AbstractTraceInterceptor.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/autoproxy/AbstractAdvisorAutoProxyCreator.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/config/SimpleBeanFactoryAwareAspectInstanceFactory.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/aspectj/AspectJAdviceParameterNameDiscoverer.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/support/annotation/AnnotationMatchingPointcut.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/interceptor/PerformanceMonitorInterceptor.java
*

/spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/interceptor/CustomizableTraceInterceptor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/AspectJPointcutAdvisor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/ProxyFactoryBean.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/interceptor/SimpleTraceInterceptor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/TypePatternClassFilter.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/interceptor/AbstractMonitoringInterceptor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/AopProxyUtils.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/interceptor/AsyncUncaughtExceptionHandler.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/autoproxy/target/LazyInitTargetSourceCreator.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/RegexpMethodPointcutAdvisor.java
*
/spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/support/NameMatchMethodPointcutAdvisor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/interceptor/ExposeInvocationInterceptor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/PrototypeTargetSource.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/autoproxy/BeanNameAutoProxyCreator.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/AdvisorChainFactory.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/target/ThreadLocalTargetSource.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at

*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/aspectj/annotation/BeanFactoryAspectInstanceFactory.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/framework/autoproxy/DefaultAdvisorAutoProxyCreator.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/target/dynamic/AbstractRefreshableTargetSource.java
*
 /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/AopUtils.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/aspectj/annotation/MetadataAwareAspectInstanceFactory.java
* /spring-aop-4-3-20-release-sources-1-jar/org/aopalliance/intercept/Interceptor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/aopalliance/intercept/MethodInvocation.java
* /spring-aop-4-3-20-release-sources-1-jar/org/aopalliance/intercept/MethodInterceptor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/aopalliance/intercept/Invocation.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/aspectj/AspectJExpressionPointcutAdvisor.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/aspectj/annotation/LazySingletonAspectInstanceFactoryDecorator.java
* /spring-aop-4-3-20-release-sources-1-jar/org/aopalliance/intercept/Joinpoint.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/aspectj/annotation/BeanFactoryAspectJAdvisorsBuilder.java
*
 /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/ProxyFactory.java
* /spring-aop-4-3-20-release-sources-1-jar/org/aopalliance/intercept/ConstructorInterceptor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/AspectJAfterReturningAdvice.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/interceptor/AsyncExecutionInterceptor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/framework/JdkDynamicAopProxy.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/annotation/AspectMetadata.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/support/AbstractBeanFactoryPointcutAdvisor.java
* /spring-aop-4-3-20-release-sources-1-jar/org/aopalliance/aop/Advice.java
* /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/aspectj/annotation/SingletonMetadataAwareAspectInstanceFactory.java
*
 /spring-aop-4-3-20-release-sources-1-
jar/org/springframework/aop/aspectj/annotation/SimpleMetadataAwareAspectInstanceFactory.java
* /spring-aop-4-3-20-release-sources-1-jar/org/aopalliance/aop/AspectException.java

* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/config/AbstractInterceptorDrivenBeanDefinitionDecorator.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/AspectJExpressionPointcut.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/annotation/AnnotationAwareAspectJAutoProxyCreator.java
* /spring-aop-4-3-20-release-sources-1-jar/org/aopalliance/intercept/ConstructorInvocation.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/AspectJWeaverMessageHandler.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/RuntimeTestWalker.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/annotation/AnnotationMethodMatcher.java
*
 /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/IntroductionAwareMethodMatcher.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/ClassFilters.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/support/annotation/AnnotationClassFilter.java
* /spring-aop-4-3-20-release-sources-1-jar/org/springframework/aop/aspectj/autoproxy/AspectJAwareAdvisorAutoProxyCreator.java

1.220 spring-context 4.3.20.RELEASE

1.220.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at

```
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* Abstract the invocation of a cache operation.
*
* <p>Does not provide a way to transmit checked exceptions but
* provide a special exception that should be used to wrap any
* exception that was thrown by the underlying invocation.
* Callers are expected to handle this issue type specifically.
*
 * @author Stephane Nicoll
* @since 4.1
*/
```

Found in path(s):
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/CacheOperationInvoker.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/beanvalidation/SpringValidatorAdapter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/assembler/AbstractReflectiveMBeanInfoAssembler.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ConfigurationClassPostProcessor.java

*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/validation/beanvalidation/MethodValidationInterceptor.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/expression/StandardBeanExpressionResolver.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/DefaultMessageSourceResolvable.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/annotation/AnnotationCacheOperationSource.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/annotation/EnableAsync.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scripting/support/ScriptFactoryPostProcessor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/DirectFieldBindingResult.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/DataBinder.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/AbstractErrors.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/EnableAspectJAutoProxy.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/event/EventListenerMethodProcessor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/annotation/CacheAnnotationParser.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/validation/beanvalidation/LocalValidatorFactoryBean.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/ejb/access/AbstractSlsbInvokerInterceptor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/CacheResolver.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/Lifecycle.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/ReloadableResourceBundleMessageSource.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/FieldError.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/event/SimpleApplicationEventMulticaster.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/CacheProxyFactoryBean.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/event/GenericApplicationListener.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/BindingResult.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/AbstractCacheResolver.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/DefaultBindingErrorProcessor.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/ComponentScanBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/MessageCodeFormatter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/remoting/support/RemoteInvocationBasedExporter.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/support/AbstractValueAdaptingCache.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/AnnotationConfigApplicationContext.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/annotation/CachingConfigurerSupport.java

* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/concurrent/ThreadPoolTaskExecutor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/rmi/RmiServiceExporter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/ConfigurationClassUtils.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/support/DefaultLifecycleProcessor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/BeanAnnotationHelper.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/context/support/AbstractMessageSource.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/AdviceMode.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/event/AbstractApplicationEventMulticaster.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/Scope.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/expression/BeanFactoryResolver.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/AdviceModeImportSelector.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/ConfigurableApplicationContext.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/MBeanExporter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/annotation/AsyncConfigurationSelector.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/interceptor/AbstractFallbackCacheOperationSource.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/annotation/SpringCacheAnnotationParser.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/annotation/ScheduledAnnotationBeanPostProcessor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/annotation/Scheduled.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/annotation/CachingConfigurer.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/AutoProxyRegistrar.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/ObjectError.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/ConfigurationClassBeanDefinitionReader.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/support/MBeanRegistrationSupport.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/BeanPropertyBindingResult.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/interceptor/VariableNotAvailableException.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/concurrent/ExecutorConfigurationSupport.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/support/JmxUtils.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/concurrent/ThreadPoolExecutorFactoryBean.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/event/DefaultEventListenerFactory.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/event/SmartApplicationListener.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/weaving/DefaultContextLoadTimeWeaver.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/AnnotationConfigUtils.java

*
 /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/ConfigurationClassEnhancer.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/CacheAspectSupport.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/SmartLifecycle.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/PropertySourcesPlaceholderConfigurer.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/ConfigurationClassParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/PropertySource.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/annotation/CachingConfigurationSelector.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/config/AnnotationDrivenCacheBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/ResourceBundleMessageSource.java
*
 /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/concurrent/ConcurrentMapCache.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/annotation/ProxyCachingConfiguration.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/datetime/joda/DurationFormatter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/annotation/AbstractAsyncConfiguration.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/ApplicationListener.java
*
 /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/support/StandardScriptUtils.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/number/money/MonetaryAmountFormatter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jndi/support/SimpleJndiBeanFactory.java

* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/support/CronTrigger.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/RemoteTimeoutException.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/annotation/ProxyAsyncConfiguration.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/ApplicationEvent.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/access/ConnectorDelegate.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/number/money/CurrencyUnitFormatter.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/annotation/ManagedAttribute.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/number/PercentFormatter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/standard/YearMonthFormatter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ComponentScans.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/ApplicationEventPublisher.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/validation/support/BindingAwareModelMap.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/datetime/joda/YearMonthFormatter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/annotation/ManagedOperationParameters.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/datetime/standard/PeriodFormatter.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/config/AnnotationDrivenBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/number/CurrencyFormatter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/event/EventExpressionRootObject.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/support/DefaultFormattingConversionService.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/ScriptEvaluator.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scripting/support/StandardScriptEvalException.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/number/PercentStyleFormatter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/number/money/Jsr354NumberFormatAnnotationFormatterFactory.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/number/NumberFormatter.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/support/AbstractCacheManager.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/datetime/joda/PeriodFormatter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jndi/JndiObjectFactoryBean.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/jboss/JBossLoadTimeWeaver.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/validation/beanvalidation/SpringConstraintValidatorFactory.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/annotation/ManagedResource.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/bsh/BshScriptEvaluator.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/annotation/ManagedOperationParameter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ImportResource.java

*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/ui/context/support/ResourceBundleThemeSource.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/concurrent/ScheduledExecutorFactoryBean.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/config/LangNamespaceHandler.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/annotation/ManagedMetric.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/standard/DateTimeConverters.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/datetime/joda/MonthDayFormatter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/annotation/AbstractCachingConfiguration.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/support/NoOpCacheManager.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/annotation/CacheConfig.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/standard/MonthDayFormatter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/event/SourceFilteringListener.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/concurrent/DefaultManagedAwareThreadFactory.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/annotation/ManagedNotification.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/PayloadApplicationEvent.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/standard/DurationFormatter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/event/EventListenerFactory.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/annotation/ManagedOperation.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/support/StandardScriptEvaluator.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/ScriptCompilationException.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/Role.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/ui/ExtendedModelMap.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.

*/

Found in path(s):
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jndi/JndiLocatorSupport.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/support/StaticMessageSource.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/FileSystemXmlApplicationContext.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/ClassPathXmlApplicationContext.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/RemoteAccessException.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/config/MBeanServerBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/assembler/AbstractConfigurableMBeanInfoAssembler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

```
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* {@link FactoryBean} that obtains a WebSphere {@link javax.management.MBeanServer}
* reference through WebSphere's proprietary {@code AdminServiceFactory} API,
* available on WebSphere 5.1 and higher.
*
* <p>Exposes the {@code MBeanServer} for bean references.
* This FactoryBean is a direct alternative
 to {@link MBeanServerFactoryBean},
* which uses standard JMX 1.2 API to access the platform's MBeanServer.
*
* <p>See the javadocs for WebSphere's
* <a href="http://bit.ly/UzccDt">{@code AdminServiceFactory}</a>
* and <a href="http://bit.ly/TRlX2r">{@code MBeanFactory}</a>.
*
* @author Juergen Hoeller
* @author Rob Harrop
* @since 2.0.3
* @see javax.management.MBeanServer
* @see MBeanServerFactoryBean
*/
```

Found in path(s):
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/support/WebSphereMBeanServerFactoryBean.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/assembler/MetadataMBeanInfoAssembler.java

* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/ApplicationListenerDetector.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/config/CacheNamespaceHandler.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/DefaultMessageCodesResolver.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/event/EventExpressionEvaluator.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/event/ApplicationListenerMethodAdapter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/CacheOperation.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/annotation/EnableCaching.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/stereotype/Service.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/naming/KeyNamingStrategy.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/standard/DateTimeFormatterFactory.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/AbstractApplicationContext.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/tomcat/TomcatLoadTimeWeaver.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/metadata/ManagedMetric.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/support/NullValue.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/MBeanExportConfiguration.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/annotation/AsyncAnnotationAdvisor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/support/SimpleThreadScope.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/support/RemoteExporter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/assembler/InterfaceBasedMBeanInfoAssembler.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/joda/JodaTimeFormatterRegistrar.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/number/NumberFormatAnnotationFormatterFactory.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/support/CronSequenceGenerator.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/config/CacheAdviceParser.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/concurrent/ConcurrentTaskScheduler.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/metadata/JmxMetadataUtils.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/ComponentScanAnnotationParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/AbstractCacheInvoker.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/stereotype/Repository.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/jboss/JBossModulesAdapter.java
*

/spring-context-4-3-20-release-sources-1-jar/org/springframework/jndi/TypeMismatchNamingException.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/remoting/rmi/RemoteInvocationSerializingExporter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/concurrent/ScheduledExecutorTask.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/annotation/NumberFormat.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/websphere/WebSphereClassPreDefinePlugin.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/Profile.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/stereotype/Component.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/websphere/WebSphereClassLoaderAdapter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/stereotype/Controller.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ConditionContext.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/weblogic/WebLogicClassLoaderAdapter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/expression/AnnotatedElementKey.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/jruby/JRubyScriptFactory.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/validation/beanvalidation/MethodValidationPostProcessor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/number/CurrencyStyleFormatter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/Bean.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/ShadowingClassLoader.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/Configuration.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/event/GenericApplicationListenerAdapter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/standard/DateTimeFormatterFactoryBean.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/annotation/DateTimeFormat.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/support/NotificationListenerHolder.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/interceptor/CacheOperationExpressionEvaluator.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/access/MBeanClientInterceptor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/support/SimpleCacheManager.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/event/ApplicationEventMulticaster.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/support/MessageSourceAccessor.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/context/event/EventPublicationInterceptor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/support/MetricType.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/weblogic/WebLogicClassPreProcessorAdapter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/support/MessageSourceSupport.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/PostProcessorRegistrationDelegate.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/number/NumberStyleFormatter.java

* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/NamedCacheResolver.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/expression/MapAccessor.java
*
 /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/EnvironmentAware.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/datetime/DateFormatter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/MessageSource.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/glassfish/GlassFishLoadTimeWeaver.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/ContextAnnotationAutowireCandidateResolver.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/ClassPathScanningCandidateComponentProvider.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/support/PeriodicTrigger.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/jruby/JRubyScriptUtils.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/websphere/WebSphereLoadTimeWeaver.java
*
 /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/support/NoOpCache.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/jboss/JBossMCTranslatorAdapter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/concurrent/ThreadPoolTaskScheduler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/annotation/Cacheable.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jndi/JndiLocatorDelegate.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/expression/MethodBasedEvaluationContext.java
*
 /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/annotation/Schedules.java
* /spring-context-4-3-20-release-sources-1-

jar/org/springframework/instrument/classloading/weblogic/WebLogicLoadTimeWeaver.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/ClassPathBeanDefinitionScanner.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ComponentScan.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/config/PropertyPlaceholderBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/AbstractResourceBasedMessageSource.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/CacheEvaluationContext.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/config/PropertyOverrideBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/CommonAnnotationBeanPostProcessor.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/config/TaskExecutorFactoryBean.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/ReflectiveLoadTimeWeaver.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/support/ConnectorServerFactoryBean.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/config/LoadTimeWeaverBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/EmbeddedValueResolverAware.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/ApplicationContextAwareProcessor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/Cache.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/config/TriggerTask.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ConfigurationClass.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/concurrent/ConcurrentMapCacheManager.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/annotation/EnableScheduling.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/groovy/GroovyScriptEvaluator.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/support/StandardScriptFactory.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/Primary.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/AspectJAutoProxyRegistrar.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/support/FormatterPropertyEditorAdapter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/GenericApplicationContext.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/standard/DateTimeFormatterRegistrar.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/context/i18n/LocaleContextHolder.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ParserStrategyUtils.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/annotation/SchedulingConfiguration.java
* /spring-context-4-3-20-release-sources-1-

jar/org/springframework/scheduling/annotation/AnnotationAsyncExecutionInterceptor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/annotation/CachePut.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/standard/Jsr310DateTimeFormatAnnotationFormatterFactory.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/config/ScriptingDefaultsParser.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/assembler/MethodNameBasedMBeanInfoAssembler.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/EnableLoadTimeWeaving.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/annotation/Async.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/datetime/standard/InstantFormatter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/AnnotationScopeMetadataResolver.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/config/ScheduledTaskRegistrar.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/groovy/GroovyScriptFactory.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/annotation/Caching.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/config/ExecutorBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/support/LiveBeansView.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/annotation/CacheEvict.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/annotation/AnnotationJmxAttributeSource.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/annotation/AsyncAnnotationBeanPostProcessor.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/joda/JodaTimeContextHolder.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/annotation/AsyncResult.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/event/EventListener.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/GenericXmlApplicationContext.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/datetime/DateFormatterRegistrar.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/CacheableOperation.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/config/ScriptBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/annotation/ManagedNotifications.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/weaving/AspectJWeavingEnabler.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/concurrent/ConcurrentTaskExecutor.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/standard/DateTimeContextHolder.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/AnnotatedBeanDefinitionReader.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/LoadTimeWeavingConfiguration.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/bsh/BshScriptFactory.java

* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/AbstractPropertyBindingResult.java
*
 /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/config/AbstractPropertyLoadingBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/CachePutOperation.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/expression/CachedExpressionEvaluator.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/SimpleKey.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ImportRegistry.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ConfigurationCondition.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jndi/JndiPropertySource.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/ConversionServiceFactoryBean.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/config/ScheduledTask.java
*
 /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/support/FormattingConversionService.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/Import.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/CacheEvictOperation.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/CacheManager.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/config/CacheManagementConfigUtils.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/validation/beanvalidation/MessageSourceResourceBundleLocator.java
*
 /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/metadata/ManagedNotification.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/AnnotationConfigRegistry.java
* /spring-context-4-3-20-release-sources-1-

jar/org/springframework/scheduling/config/ContextLifecycleScheduledTaskRegistrar.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/BasicOperation.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/CacheErrorHandler.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/datetime/joda/JodaTimeConverters.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/support/RemoteInvocation.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/standard/TemporalAccessorParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/annotation/Validated.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/support/CompositeCacheManager.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/support/FormattingConversionServiceFactoryBean.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/AbstractRefreshableConfigApplicationContext.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/support/RemoteInvocationResult.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/joda/JodaDateTimeFormatAnnotationFormatterFactory.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/GenericGroovyApplicationContext.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/PropertySources.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/SimpleThrowawayClassLoader.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/SimpleCacheErrorHandler.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/ContextTypeMatchClassLoader.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/AnnotationBeanNameGenerator.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/standard/DateTimeContext.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/DateTimeFormatAnnotationFormatterFactory.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/SimpleCacheResolver.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/FormatterRegistry.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ConditionEvaluator.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/annotation/AsyncConfigurerSupport.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/EmbeddedValueResolutionSupport.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/concurrent/ForkJoinPoolFactoryBean.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/interceptor/CacheOperationInvocationContext.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/remoting/support/SimpleHttpServerFactoryBean.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/annotation/AsyncConfigurer.java
* /spring-context-4-3-20-release-sources-1-

jar/org/springframework/format/datetime/standard/TemporalAccessorPrinter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/ValidationUtils.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/expression/BeanFactoryAccessor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/DefaultKeyGenerator.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/SimpleInstrumentableClassLoader.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/ApplicationContext.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/ScannedGenericBeanDefinition.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/SimpleKeyGenerator.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/config/TaskManagementConfigUtils.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/assembler/MethodExclusionMBeanInfoAssembler.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/AnnotationFormatterFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2006 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/MapBindingResult.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ScopedProxyCreator.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/LifecycleProcessor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/MBeanExportOperations.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/SpringModelMBean.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/metadata/AbstractJmxAttribute.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jndi/JndiAccessor.java
*
 /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/WeavingTransformer.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/remoting/support/RemoteInvocationFactory.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/remoting/support/RemoteInvocationExecutor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/config/LangNamespaceUtils.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/metadata/ManagedAttribute.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/metadata/ManagedOperationParameter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/ejb/config/AbstractJndiLocatingBeanDefinitionParser.java
No license file was found, but licenses were detected in source scan.

/*

* Copyright 2002-2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/ConflictingBeanDefinitionException.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/MessageSourceAware.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/ApplicationContextInitializer.java
*
 /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/jboss/JBossClassLoaderAdapter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/ApplicationEventPublisherAware.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ImportAware.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/notification/NotificationPublisherAware.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/BeanMethod.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* Indicates that a component is only eligible for registration when all
* {@linkplain #value specified conditions} match.

```
*
* <p>A <em>condition</em> is any state that can be determined programmatically
* before the bean definition is due to be registered (see {@link Condition} for details).
*
* <p>The
 {@code @Conditional} annotation may be used in any of the following ways:
* <ul>
* <li>as a type-level annotation on any class directly or indirectly annotated with
* {@code @Component}, including {@link Configuration @Configuration} classes</li>
* <li>as a meta-annotation, for the purpose of composing custom stereotype
* annotations</li>
* <li>as a method-level annotation on any {@link Bean @Bean} method</li>
* </ul>
*
* <p>If a {@code @Configuration} class is marked with {@code @Conditional},
* all of the {@code @Bean} methods, {@link Import @Import} annotations, and
* {@link ComponentScan @ComponentScan} annotations associated with that
* class will be subject to the conditions.
*
* <p><strong>NOTE</strong>: Inheritance of {@code @Conditional} annotations
* is not supported; any conditions from superclasses or from overridden
* methods will not be considered. In order to enforce these semantics,
* {@code @Conditional} itself is not declared as
* {@link java.lang.annotation.Inherited
 @Inherited}; furthermore, any
* custom <em>composed annotation</em> that is meta-annotated with
* {@code @Conditional} must not be declared as {@code @Inherited}.
*
* @author Phillip Webb
* @author Sam Brannen
* @since 4.0
* @see Condition
*/
```

Found in path(s):
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/Conditional.java
No license file was found, but licenses were detected in source scan.


```
/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
```

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/concurrent/DefaultManagedTaskExecutor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/support/StaticApplicationContext.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/support/ResourceScriptSource.java
*
 /spring-context-4-3-20-release-sources-1-
jar/org/springframework/ejb/interceptor/SpringBeanAutowiringInterceptor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/rmi/RmiRegistryFactoryBean.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/i18n/SimpleTimeZoneAwareLocaleContext.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/concurrent/DefaultManagedTaskScheduler.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/config/CronTask.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/bsh/BshScriptUtils.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/joda/LocalDateTimeParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/config/IntervalTask.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/AbstractRefreshableApplicationContext.java
*
 /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/support/MethodInvokingRunnable.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ImportSelector.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/DeferredImportSelector.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/datetime/joda/LocalDateParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/Condition.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/rmi/JndiRmiClientInterceptor.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/config/ScheduledTasksBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/ImportBeanDefinitionRegistrar.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/joda/ReadableInstantPrinter.java
*
 /spring-context-4-3-20-release-sources-1-jar/org/springframework/ui/ModelMap.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/SchedulingTaskExecutor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ScopedProxyMode.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/i18n/LocaleContext.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/jboss/JBossMCAdapter.java
* /spring-context-4-3-20-release-sources-1-

jar/org/springframework/cache/interceptor/CacheExpressionRootObject.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/joda/DateTimeFormatterFactoryBean.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/KeyGenerator.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/rmi/RmiClientInterceptorUtils.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ConfigurationMethod.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/joda/ReadablePartialPrinter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/datetime/joda/LocalTimeParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/Description.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/datetime/joda/DateTimeParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/FilterType.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/Lazy.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/support/SimpleTriggerContext.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/joda/MillisecondInstantPrinter.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/ScriptFactory.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/expression/EnvironmentAccessor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/i18n/SimpleLocaleContext.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/datetime/joda/JodaTimeContext.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/i18n/TimeZoneAwareLocaleContext.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/support/TaskUtils.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/concurrent/CustomizableThreadFactory.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/format/datetime/joda/DateTimeFormatterFactory.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ProfileCondition.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/MessageSourceResourceBundle.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/validation/beanvalidation/OptionalValidatorFactoryBean.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2005 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/metadata/ManagedOperation.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/notification/ModelMBeanNotificationPublisher.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/remoting/support/DefaultRemoteInvocationExecutor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/TaskScheduler.java
*
 /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/rmi/RmiClientInterceptor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/rmi/RmiInvocationWrapper.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/MBeanExportException.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/config/ContextNamespaceHandler.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/validation/beanvalidation/BeanValidationPostProcessor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/ui/context/ThemeSource.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/Jsr330ScopeMetadataResolver.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/ui/context/Theme.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/access/NotificationListenerRegistrar.java
*
 /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/rmi/RmiInvocationHandler.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/ScopeMetadataResolver.java
* /spring-context-4-3-20-release-sources-1-

jar/org/springframework/jmx/export/naming/IdentityNamingStrategy.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jndi/JndiObjectLocator.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/support/SimpleValueWrapper.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/support/ApplicationObjectSupport.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/CacheInterceptor.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/config/SchedulerBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/Parser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/support/ObjectNameManager.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/context/event/ApplicationContextEvent.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/ui/context/support/DelegatingThemeSource.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jndi/JndiTemplate.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/NoSuchMessageException.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/ejb/access/SimpleRemoteSlsbInvokerInterceptor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/RemoteProxyFailureException.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/MessageSourceResolvable.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/naming/ObjectNamingStrategy.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/AbstractBindingResult.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/annotation/SchedulingConfigurer.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/JmxException.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/ui/context/support/SimpleTheme.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/expression/BeanExpressionContextAccessor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/Errors.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/concurrent/ConcurrentMapCacheFactoryBean.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/remoting/support/UrlBasedRemoteAccessor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/ApplicationContextAware.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/ejb/access/EjbAccessException.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/config/TaskNamespaceHandler.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/access/MBeanInfoRetrievalException.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/Printer.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/rmi/RmiProxyFactoryBean.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/number/AbstractNumberFormatter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/BindingResultUtils.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/interceptor/CacheOperationSourcePointcut.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/support/StaticScriptSource.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/ScopeMetadata.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/rmi/RmiBasedExporter.java
*

/spring-context-4-3-20-release-sources-1-jar/org/springframework/context/Phased.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jndi/JndiLookupFailureException.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/InstrumentationLoadTimeWeaver.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/AnnotationConfigBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/support/AbstractXmlApplicationContext.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/access/MBeanConnectFailureException.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/interceptor/BeanFactoryCacheOperationSourceAdvisor.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/validation/beanvalidation/LocaleContextMessageInterpolator.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/support/MBeanServerFactoryBean.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/ScriptSource.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jndi/JndiObjectTargetSource.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/MBeanExporterListener.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/instrument/classloading/LoadTimeWeaver.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/support/RemoteAccessor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/RemoteConnectFailureException.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/remoting/support/DefaultRemoteInvocationFactory.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/metadata/ManagedResource.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/assembler/MBeanInfoAssembler.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/scripting/support/RefreshableScriptTargetSource.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/config/MBeanExportBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/notification/NotificationPublisher.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/UnableToRegisterMBeanException.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/event/ContextStoppedEvent.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/support/RegistrationPolicy.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/SchedulingException.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/BindingErrorProcessor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/SmartValidator.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/access/ContextBeanFactoryReference.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/event/ContextClosedEvent.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/ejb/access/LocalStatelessSessionProxyFactoryBean.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/rmi/JndiRmiProxyFactoryBean.java

* /spring-context-4-3-20-release-sources-1-jar/org/springframework/ui/Model.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/annotation/AnnotationMBeanExporter.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/TriggerContext.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/assembler/SimpleReflectiveMBeanInfoAssembler.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/RemoteLookupFailureException.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/access/InvocationFailureException.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/assembler/AutodetectCapableMBeanInfoAssembler.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/access/MBeanProxyFactoryBean.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/naming/MetadataNamingStrategy.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/SchedulingAwareRunnable.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/ui/context/support/UiApplicationContextUtils.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/remoting/rmi/CodebaseAwareObjectInputStream.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/ejb/access/LocalSlsbInvokerInterceptor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/Formatter.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/interceptor/NameMatchCacheOperationSource.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/rmi/JndiRmiServiceExporter.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/ejb/config/RemoteStatelessSessionBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/support/RemoteInvocationUtils.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/event/ContextRefreshedEvent.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/event/ContextStartedEvent.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/support/ScheduledMethodRunnable.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/ejb/config/JeeNamespaceHandler.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/BindException.java
*
/spring-context-4-3-20-release-sources-1-
jar/org/springframework/jmx/export/assembler/AbstractMBeanInfoAssembler.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/access/InvalidInvocationException.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/ResourceOverridingShadowingClassLoader.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/remoting/support/RemoteInvocationBasedAccessor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jndi/JndiCallback.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/instrument/classloading/SimpleLoadTimeWeaver.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/cache/interceptor/CacheOperationSource.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/DependsOn.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/ResourceLoaderAware.java

*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/metadata/JmxAttributeSource.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/MBeanServerNotFoundException.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/access/ContextSingletonBeanFactoryLocator.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/scheduling/support/DelegatingErrorHandlingRunnable.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/soap/SoapFaultException.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/NotificationListenerBean.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/ejb/config/LocalStatelessSessionBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/weaving/LoadTimeWeaverAwareProcessor.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/access/ContextJndiBeanFactoryLocator.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/context/HierarchicalMessageSource.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jndi/JndiTemplateEditor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/ApplicationContextException.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/naming/SelfNaming.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/context/config/SpringConfiguredBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/config/Task.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/validation/beanvalidation/CustomValidatorBean.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/cache/interceptor/CompositeCacheOperationSource.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/Validator.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/scripting/groovy/GroovyObjectCustomizer.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/ejb/access/AbstractRemoteSlsbInvokerInterceptor.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/validation/MessageCodesResolver.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/ejb/config/JndiLookupBeanDefinitionParser.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/EnableMBeanExport.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/format/FormatterRegistrar.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/ui/context/HierarchicalThemeSource.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/remoting/RemoteInvocationFailureException.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/remoting/support/RemotingSupport.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/context/access/DefaultLocatorFactory.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/support/DelegatingMessageSource.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/ejb/access/SimpleRemoteStatelessSessionProxyFactoryBean.java
* /spring-context-4-3-20-release-sources-1-
jar/org/springframework/remoting/support/RemoteInvocationTraceInterceptor.java

* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/concurrent/ReschedulingRunnable.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/annotation/LoadTimeWeavingConfigurer.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/metadata/InvalidMetadataException.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/support/LiveBeansViewMBean.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/export/notification/UnableToSendNotificationException.java
*
/spring-context-4-3-20-release-sources-1-jar/org/springframework/jmx/support/MBeanServerConnectionFactoryBean.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/scheduling/Trigger.java
* /spring-context-4-3-20-release-sources-1-jar/org/springframework/context/weaving/LoadTimeWeaverAware.java

1.221 spring-aspects 4.3.20.RELEASE

1.221.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/beans/factory/aspectj/GenericInterfaceDrivenDependencyInjectionAspect.aj
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/transaction/aspectj/AbstractTransactionAspect.aj
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/cache/aspectj/AnnotationCacheAspect.aj
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*

* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-aspects-4-3-20-release-sources-1-
jar/org/springframework/cache/aspectj/AspectJCachingConfiguration.java
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/cache/aspectj/AspectJJCacheConfiguration.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-aspects-4-3-20-release-sources-1-
jar/org/springframework/context/annotation/aspectj/SpringConfiguredConfiguration.java
* /spring-aspects-4-3-20-release-sources-1-
jar/org/springframework/transaction/aspectj/JtaAnnotationTransactionAspect.aj
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/cache/aspectj/AnyThrow.java
*
 /spring-aspects-4-3-20-release-sources-1-
jar/org/springframework/transaction/aspectj/AnnotationTransactionAspect.aj
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.

*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/scheduling/aspectj/AnnotationAsyncExecutionAspect.aj
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/scheduling/aspectj/AbstractAsyncExecutionAspect.aj
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/context/annotation/aspectj/EnableSpringConfigured.java
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/beans/factory/aspectj/ConfigurableObject.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.

* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/transaction/aspectj/AspectJTransactionManagementConfiguration.java
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/beans/factory/aspectj/AbstractInterfaceDrivenDependencyInjectionAspect.aj
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/mock/staticmock/AbstractMethodMockingControl.aj
*
 /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/cache/aspectj/AbstractCacheAspect.aj
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/scheduling/aspectj/AspectJAsyncConfiguration.java
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/mock/staticmock/AnnotationDrivenStaticEntityMockingControl.aj
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/cache/aspectj/JCacheCacheAspect.aj
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/beans/factory/aspectj/AnnotationBeanConfigurerAspect.aj
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/orm/jpa/aspectj/JpaExceptionTranslatorAspect.aj
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/mock/staticmock/MockStaticEntityMethods.java
* /spring-aspects-4-3-20-release-sources-1-jar/org/springframework/beans/factory/aspectj/AbstractDependencyInjectionAspect.aj

1.222 spring-tx 4.3.20.RELEASE

1.222.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/annotation/Transactional.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/annotation/Ejb3TransactionAnnotationParser.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/annotation/TransactionAnnotationParser.java
*
/spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/endpoint/AbstractMessageEndpointFactory.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/endpoint/GenericMessageEndpointFactory.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/TransactionStatus.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/annotation/AnnotationTransactionAttributeSource.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/endpoint/GenericMessageEndpointManager.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/annotation/TransactionManagementConfigurationSelector.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/annotation/SpringTransactionAnnotationParser.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/interceptor/DefaultTransactionAttribute.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/support/AbstractTransactionStatus.java
*
/spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/support/SimpleTransactionStatus.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/jta/JtaTransactionManager.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/support/TransactionTemplate.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/interceptor/AbstractFallbackTransactionAttributeSource.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/support/DefaultTransactionStatus.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/annotation/JtaTransactionAnnotationParser.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/support/DefaultTransactionDefinition.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/event/TransactionalEventListenerFactory.java
*
/spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/support/AbstractPlatformTransactionManager.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2008 the original author or authors.

*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/core/CciOperations.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/support/ResourceHolder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/InvalidResultSetAccessException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/support/TransactionOperations.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/context/ResourceAdapterApplicationContext.java
*
 /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/support/DelegatingTransactionDefinition.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/TransactionTimedOutException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/interceptor/TransactionAttribute.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/interceptor/NoRollbackRuleAttribute.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/dao/support/ChainedPersistenceExceptionTranslator.java

* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/interceptor/TransactionAttributeSourceAdvisor.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/DataIntegrityViolationException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/InvalidDataAccessResourceUsageException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/interceptor/DelegatingTransactionAttribute.java
*
/spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/RecoverableDataAccessException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/IncorrectResultSizeDataAccessException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/core/CciTemplate.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/support/ResourceHolderSynchronization.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/DataAccessResourceFailureException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/TransactionUsageException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/InvalidDataAccessApiUsageException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/jta/UserTransactionAdapter.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/connection/TransactionAwareConnectionFactoryProxy.java
*
/spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/TransactionSuspensionNotSupportedException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/ConcurrencyFailureException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/CciOperationNotSupportedException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/CleanupFailureDataAccessException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/UnexpectedRollbackException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/NestedTransactionNotSupportedException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/work/DelegatingWork.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/RecordTypeNotSupportedException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/PessimisticLockingFailureException.java
*
/spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/support/ResourceTransactionManager.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/CannotCreateRecordException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/IllegalTransactionStateException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/support/LocalConnectionFactoryBean.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/interceptor/CompositeTransactionAttributeSource.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/InvalidIsolationLevelException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/connection/ConnectionFactoryUtils.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/CannotGetCciConnectionException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/support/SimpleBootstrapContext.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/annotation/Isolation.java
*
/spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/PlatformTransactionManager.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/TransactionException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/interceptor/TransactionAttributeSource.java

* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/NoTransactionException.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/interceptor/BeanFactoryTransactionAttributeSourceAdvisor.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/connection/ConnectionHolder.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/CannotSerializeTransactionException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/OptimisticLockingFailureException.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/dao/NonTransientDataAccessResourceException.java
*
/spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/object/MappingRecordOperation.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/interceptor/RuleBasedTransactionAttribute.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/DataAccessException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/connection/SingleConnectionFactory.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/UncategorizedDataAccessException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/work/SimpleTaskWorkManager.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/object/SimpleRecordOperation.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/DuplicateKeyException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/connection/NotSupportedRecordFactory.java
*
/spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/jta/SpringJtaSynchronizationAdapter.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/context/BootstrapContextAware.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/dao/IncorrectUpdateSemanticsDataAccessException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/EmptyResultDataAccessException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/CannotCreateTransactionException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/HeuristicCompletionException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/jta/ManagedTransactionAdapter.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/TransientDataAccessException.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/jta/JtaAfterCompletionSynchronization.java
*
/spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/support/TransactionSynchronizationAdapter.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/jca/cci/connection/DelegatingConnectionFactory.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/TypeMismatchDataAccessException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/jta/TransactionFactory.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/jta/SimpleTransactionFactory.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/config/TxNamespaceHandler.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/core/RecordCreator.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/object/MappingCommAreaOperation.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/interceptor/MethodMapTransactionAttributeSource.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/NonTransientDataAccessException.java
*
/spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/support/DaoSupport.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/core/support/CciDaoSupport.java

* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/QueryTimeoutException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/PermissionDeniedDataAccessException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/TransactionSystemException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/CannotAcquireLockException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/InvalidTimeoutException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/TransientDataAccessResourceException.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/dao/annotation/PersistenceExceptionTranslationAdvisor.java
*
/spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/interceptor/TransactionAttributeSourceEditor.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/interceptor/TransactionAttributeEditor.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/DataRetrievalFailureException.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/core/RecordExtractor.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/support/PersistenceExceptionTranslator.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/context/BootstrapContextAwareProcessor.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/support/TransactionSynchronizationUtils.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/support/CallbackPreferringPlatformTransactionManager.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/DeadlockLoserDataAccessException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/support/TransactionSynchronization.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/interceptor/TransactionInterceptor.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/config/JtaTransactionManagerFactoryBean.java
*
/spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/config/JtaTransactionManagerBeanDefinitionParser.java

* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/SavepointManager.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/config/TxAdviceBeanDefinitionParser.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/work/jboss/JBossWorkManagerUtils.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/interceptor/NameMatchTransactionAttributeSource.java
*
 /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/support/SmartTransactionObject.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/context/SpringContextResourceAdapter.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/jta/WebLogicJtaTransactionManager.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/jca/work/glassfish/GlassFishWorkManagerTaskExecutor.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/dao/support/PersistenceExceptionTranslationInterceptor.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/interceptor/MatchAlwaysTransactionAttributeSource.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/jca/work/jboss/JBossWorkManagerTaskExecutor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/jta/JtaTransactionObject.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/core/InteractionCallback.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/support/TransactionCallback.java
*
 /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/core/ConnectionCallback.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/annotation/TransactionManagementConfigurer.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/support/SimpleTransactionScope.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/work/WorkManagerTaskExecutor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/config/AnnotationDrivenBeanDefinitionParser.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/interceptor/TransactionalProxy.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/config/TransactionManagementConfigUtils.java
*
 /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/annotation/Propagation.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/interceptor/TransactionProxyFactoryBean.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/dao/annotation/PersistenceExceptionTranslationPostProcessor.java

* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/interceptor/RollbackRuleAttribute.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/annotation/AbstractTransactionManagementConfiguration.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/annotation/ProxyTransactionManagementConfiguration.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/connection/CciLocalTransactionManager.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/jca/cci/connection/ConnectionSpecConnectionFactoryAdapter.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/event/TransactionalEventListener.java
*
 /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/interceptor/TransactionAspectSupport.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/jta/WebSphereUowTransactionManager.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/support/TransactionSynchronizationManager.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/support/ResourceAdapterFactoryBean.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/annotation/EnableTransactionManagement.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/TransactionDefinition.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/event/ApplicationListenerMethodTransactionalAdapter.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/event/TransactionPhase.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/object/EisOperation.java
*
 /spring-tx-4-3-20-release-sources-1-jar/org/springframework/transaction/support/ResourceHolderSupport.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/jca/cci/core/support/CommAreaRecord.java
* /spring-tx-4-3-20-release-sources-1-
jar/org/springframework/transaction/interceptor/TransactionAttributeSourcePointcut.java
* /spring-tx-4-3-20-release-sources-1-

jar/org/springframework/transaction/support/TransactionCallbackWithoutResult.java
* /spring-tx-4-3-20-release-sources-1-jar/org/springframework/dao/support/DataAccessUtils.java

1.223 spring-beans 4.3.20.RELEASE

1.223.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/BeanExpressionContext.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/annotation/Autowire.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):

* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/AbstractFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/annotation/Autowired.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/annotation/InjectionMetadata.java
*
 /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/xml/ParserContext.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/YamlProcessor.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/DestructionAwareBeanPostProcessor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/BeanDefinitionStoreException.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/groovy/GroovyBeanDefinitionWrapper.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/DirectFieldAccessor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/DependencyDescriptor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/AbstractBeanFactory.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/support/PagedListHolder.java
*
 /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/DefaultListableBeanFactory.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/InitializingBean.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/Mergeable.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/TypeMismatchException.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/xml/DefaultNamespaceHandlerResolver.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/MutablePropertyValues.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/annotation/QualifierAnnotationAutowireCandidateResolver.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/BeanWrapperImpl.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/BeanUtils.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/xml/PluggableSchemaResolver.java
*
 /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/FactoryBeanRegistrySupport.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/StaticListableBeanFactory.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/xml/XmlBeanDefinitionReader.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/URIEditor.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/DefaultSingletonBeanRegistry.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/DisposableBean.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/AbstractAutowireCapableBeanFactory.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/PropertyMatches.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/BeanDefinitionRegistry.java
*

/spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/groovy/GroovyBeanDefinitionReader.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/BeanFactoryUtils.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/Aware.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/annotation/AutowiredAnnotationBeanPostProcessor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/TypeConverterDelegate.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/annotation/RequiredAnnotationBeanPostProcessor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/ExtendedBeanInfo.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/xml/BeansDtdResolver.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/PropertyEditorRegistrySupport.java
*
/spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/GenericTypeAwarePropertyDescriptor.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/xml/BeanDefinitionDocumentReader.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/ConfigurableListableBeanFactory.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/BeanPostProcessor.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/annotation/InitDestroyAnnotationBeanPostProcessor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/annotation/Lookup.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/CustomBooleanEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/annotation/AnnotationBeanUtils.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/SingletonBeanRegistry.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.

*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/MapFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/ListFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/PropertyAccessException.java
*
 /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/CannotLoadBeanClassException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/BeanDefinition.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/InstantiationAwareBeanPostProcessor.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/MethodInvokingFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/SimpleAutowireCandidateResolver.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/ServiceLocatorFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/CustomScopeConfigurer.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/parsing/BeanComponentDefinition.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/ObjectFactory.java
*
 /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/parsing/Problem.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/PropertyAccessor.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/BeanDefinitionDefaults.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/BeanDefinitionBuilder.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/AbstractNestablePropertyAccessor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/SetFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/propertyeditors/ResourceBundleEditor.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/xml/AbstractBeanDefinitionParser.java

* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/xml/BeanDefinitionParserDelegate.java
*
 /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/InjectionPoint.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/BeanFactory.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/GenericTypeAwareAutowireCandidateResolver.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/parsing/ReaderContext.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/CachedIntrospectionResults.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/annotation/Qualifier.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/xml/BeanDefinitionParser.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/BeanDefinitionVisitor.java
*
 /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/BeanNameAware.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
*/

Found in path(s):
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/GenericBeanDefinition.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/CustomMapEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/PropertyValue.java
*
 /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/ObjectProvider.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/xml/DefaultBeanDefinitionDocumentReader.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/YamlMapFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/RootBeanDefinition.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/NamedBean.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/FactoryBean.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/MethodOverrides.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/PropertyPlaceholderConfigurer.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/PlaceholderConfigurerSupport.java
*
 /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/ReaderEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/MergedBeanDefinitionPostProcessor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/UnsatisfiedDependencyException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/TypeConverterSupport.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/CglibSubclassingInstantiationStrategy.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/DisposableBeanAdapter.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/BeanNotOfRequiredTypeException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/NoUniqueBeanDefinitionException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/FileEditor.java
*
 /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/EmbeddedValueResolver.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/NamedBeanHolder.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/xml/UtilNamespaceHandler.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/ConfigurableBeanFactory.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/PathEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/CustomCollectionEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/ChildBeanDefinition.java

* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/FieldRetrievingFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/AutowireUtils.java
*
 /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/BeanCreationException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/YamlPropertiesFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/ConstructorArgumentValues.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/InputStreamEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/NoSuchBeanDefinitionException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/ListableBeanFactory.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/InstantiationAwareBeanPostProcessorAdapter.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/BeanDefinitionReaderUtils.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/SimpleInstantiationStrategy.java
*
 /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/URLEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/BeanInitializationException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/AutowireCapableBeanFactory.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/ConstructorResolver.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/support/ResourceEditorRegistrar.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/PropertiesFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/BeanWrapper.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/annotation/BeanFactoryAnnotationUtils.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/NullValueInNestedPathException.java
*
 /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/BeanInstantiationException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/AbstractBeanDefinition.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/Scope.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/NotReadablePropertyException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/PropertyDescriptorUtils.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/LookupOverride.java
*
/spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/InstantiationStrategy.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/ConfigurablePropertyAccessor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/MethodOverride.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/annotation/AnnotatedBeanDefinition.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/MethodInvokingBean.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/annotation/AnnotatedGenericBeanDefinition.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/access/el/SpringBeanELResolver.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/ZoneIdEditor.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/BeanDefinitionValueResolver.java
*
/spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/SmartInitializingSingleton.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/xml/AbstractSimpleBeanDefinitionParser.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/AbstractPropertyAccessor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/CharacterEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/ReplaceOverride.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/xml/XmlReaderContext.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/xml/SimpleConstructorNamespaceHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/PropertyAccessorFactory.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/BeanExpressionResolver.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/serviceloader/ServiceListFactoryBean.java
*
 /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/access/el/SimpleSpringBeanELResolver.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/BeanDefinitionRegistryPostProcessor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/PropertyOverrideConfigurer.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/AbstractBeanDefinitionReader.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/AutowireCandidateResolver.java
*
 /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/groovy/GroovyDynamicElementReader.groovy
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/wiring/BeanConfigurerSupport.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/TypeConverter.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/CustomEditorConfigurer.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/ExtendedBeanInfoFactory.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/SimpleTypeConverter.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/BeanInfoFactory.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/BeanDefinitionReader.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/PropertiesBeanDefinitionReader.java
*
 /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/TimeZoneEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/TypedStringValue.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/access/BeanFactoryReference.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):

* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/BeanNameGenerator.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/serviceloader/ServiceFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/parsing/ReaderEventListener.java
*
/spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/serviceloader/AbstractServiceLoaderBasedFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/parsing/DefaultsDefinition.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/PropertyValuesEditor.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/serviceloader/ServiceLoaderFactoryBean.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/BeanCurrentlyInCreationException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/PropertiesEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/InputSourceEditor.java
*
/spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/HierarchicalBeanFactory.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/parsing/EmptyReaderEventListener.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/parsing/PassThroughSourceExtractor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/xml/XmlBeanFactory.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/MethodInvocationException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/BeanMetadataAttributeAccessor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/CurrencyEditor.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/AutowireCandidateQualifier.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/RuntimeBeanNameReference.java

*
/spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/xml/DocumentLoader.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/BeanDefinitionValidationException.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/wiring/ClassNameBeanWiringInfoResolver.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/DeprecatedBeanWarner.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/ObjectFactoryCreatingFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/BeanFactoryAware.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/propertyeditors/StringArrayPropertyEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/ClassEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/ManagedMap.java
*
/spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/ConversionNotSupportedException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/PropertyBatchUpdateException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/ManagedSet.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/ProviderCreatingFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/parsing/AbstractComponentDefinition.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/SimpleBeanDefinitionRegistry.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/xml/NamespaceHandlerSupport.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/BeanClassLoaderAware.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/support/ArgumentConvertingMethodInvoker.java
*
/spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/annotation/CustomAutowireConfigurer.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/parsing/ImportDefinition.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/access/BeanFactoryLocator.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/PropertyPathFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/CustomNumberEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/BeanReference.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/xml/NamespaceHandler.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/SimpleSecurityContextProvider.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/InvalidPropertyException.java
*
/spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/parsing/ProblemReporter.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/SmartInstantiationAwareBeanPostProcessor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/CustomDateEditor.java

* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/BeanExpressionException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/LocaleEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/annotation/Required.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/BeansException.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/xml/AbstractSingleBeanDefinitionParser.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/StringTrimmerEditor.java
*
/spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/annotation/AnnotationBeanWiringInfoResolver.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/PreferencesPlaceholderConfigurer.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/UUIDEditor.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/PropertyResourceConfigurer.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/xml/SimplePropertyNamespaceHandler.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/annotation/Value.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/support/PropertyComparator.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/xml/ResourceEntityResolver.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/parsing/ComponentDefinition.java
*
/spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/BeanMetadataAttribute.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/RuntimeBeanReference.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/parsing/NullSourceExtractor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/ClassArrayEditor.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/parsing/BeanDefinitionParsingException.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/BeanDefinitionResource.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/PropertyEditorRegistrar.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/support/MutableSortDefinition.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/config/BeanDefinitionHolder.java
*
/spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/SmartFactoryBean.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/config/BeanFactoryPostProcessor.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/BeanCreationNotAllowedException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/CharsetEditor.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/FactoryBeanNotInitializedException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/PropertyAccessorUtils.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/support/SortDefinition.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/parsing/ParseState.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/BeanIsAbstractException.java
*

/spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/xml/NamespaceHandlerResolver.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/xml/DocumentDefaultsDefinition.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/parsing/QualifierEntry.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/PatternEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/parsing/SourceExtractor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/xml/BeanDefinitionDecorator.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/FatalBeanException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/PropertyValues.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/annotation/Configurable.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/access/SingletonBeanFactoryLocator.java
*
/spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/SecurityContextProvider.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/ManagedList.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/parsing/CompositeComponentDefinition.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/BeanIsNotAFactoryException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/xml/DefaultDocumentLoader.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/support/DefaultBeanNameGenerator.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/MethodReplacer.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/access/BootstrapException.java
*
/spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/PropertyEditorRegistry.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/xml/XmlBeanDefinitionStoreException.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/wiring/BeanWiringInfoResolver.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/xml/DelegatingEntityResolver.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/parsing/Location.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/parsing/FailFastProblemReporter.java
* /spring-beans-4-3-20-release-sources-1-
jar/org/springframework/beans/factory/parsing/ConstructorArgumentEntry.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/parsing/PropertyEntry.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/parsing/AliasDefinition.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/wiring/BeanWiringInfo.java
*
/spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/NotWritablePropertyException.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/ManagedArray.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/BeanMetadataElement.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/support/ManagedProperties.java
No license file was found, but licenses were detected in source scan.

/*

* Copyright 2002-2006 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/ByteArrayPropertyEditor.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/factory/parsing/BeanEntry.java
* /spring-beans-4-3-20-release-sources-1-jar/org/springframework/beans/propertyeditors/CharArrayPropertyEditor.java

1.224 spring-web 4.3.20.RELEASE

1.224.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/ServletRequestParameterPropertyValues.java
* /spring-web-4-3-20-release-sources-1-

jar/org/springframework/web/bind/MissingServletRequestParameterException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/support/WebArgumentResolver.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/AbstractClientHttpResponse.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/bind/support/ConfigurableWebBindingInitializer.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/remoting/jaxws/JaxWsSoapFaultException.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/bind/support/DefaultSessionAttributeStore.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/RestClientException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/IntrospectorCleanupListener.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/ValueConstants.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/ResourceAccessException.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/remoting/httpinvoker/HttpInvokerClientConfiguration.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/async/AsyncWebRequest.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/bind/MethodArgumentNotValidException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/WebAppRootListener.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/ServletRequestBindingException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/RequestScope.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/NestedServletException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/WebApplicationInitializer.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/SpringBeanAutowiringSupport.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/jsf/DecoratingNavigationHandler.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/ServletRequestDataBinder.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/RequestContextHolder.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/Log4jConfigListener.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/remoting/jaxws/JaxWsPortProxyFactoryBean.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/request/Log4jNestedDiagnosticContextInterceptor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/support/SimpleSessionStatus.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/ServletContextAttributeFactoryBean.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/SessionScope.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/WebRequestInterceptor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/multipart/MultipartException.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/TagUtils.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/remoting/jaxws/LocalJaxWsServiceFactoryBean.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/support/RequestHandledEvent.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/WebApplicationContext.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/jsf/DelegatingPhaseListenerMulticaster.java
* /spring-web-4-3-20-release-sources-1-

jar/org/springframework/web/context/support/ServletContextLiveBeansView.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/ServletConfigAware.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/support/SessionAttributeStore.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/MediaTypeEditor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/InitBinder.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/ContextCleanupListener.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/bind/annotation/support/HandlerMethodInvocationException.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/HttpRequestHandlerServlet.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/multipart/support/StringMultipartFileEditor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/jsf/DelegatingNavigationHandlerProxy.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/HttpMediaTypeNotAcceptableException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/multipart/MultipartRequest.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/ServletContextParameterFactoryBean.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/support/WebDataBinderFactory.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/ServletContextAware.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/support/ServletContextScope.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/ConfigurableWebEnvironment.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/request/AsyncWebRequestInterceptor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/ServletRequestUtils.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/RelativeRedirectFilter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/xml/Jaxb2CollectionHttpMessageConverter.java

* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/ClientHttpRequestInterceptor.java
*
/spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/annotation/SessionAttributesHandler.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/method/annotation/ModelFactory.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/json/MappingJackson2HttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/AnnotationConfigWebApplicationContext.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/UriComponentsBuilder.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/CrossOrigin.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/multipart/commons/CommonsMultipartResolver.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/PathVariable.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/json/GsonHttpMessageConverter.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/FormHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/RequestMapping.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/server/ServletServerHttpRequest.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/support/ModelAndViewContainer.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/ServletWebRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/ShallowEtagHeaderFilter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/protobuf/ExtensionRegistryInitializer.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/request/async/WebAsyncManager.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/remoting/jaxws/SimpleHttpServerJaxWsServiceExporter.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/AbstractHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/multipart/support/StandardMultipartHttpServletRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/cors/CorsProcessor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/cors/CorsConfiguration.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/HttpInputMessage.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/CacheControl.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/HiddenHttpMethodFilter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/RelativeRedirectResponseWrapper.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/annotation/InitBinderDataBinderFactory.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/accept/ContentNegotiationManagerFactoryBean.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/RequestBody.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/SimpleBufferingClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-

jar/org/springframework/http/converter/xml/AbstractXmlHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/json/AbstractJackson2HttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/UrlPathHelper.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/client/MessageBodyClientHttpResponseWrapper.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/SimpleClientHttpResponse.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/HttpRequest.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/client/BufferingClientHttpRequestFactory.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/Netty4ClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/OkHttp3ClientHttpRequestFactory.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/multipart/support/StandardServletMultipartResolver.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/HttpMethod.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/bind/annotation/support/HandlerMethodInvoker.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/xml/Jaxb2RootElementHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/DefaultResponseErrorHandler.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/HttpHeaders.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/multipart/support/AbstractMultipartHttpServletRequest.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/WebUtils.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/GroovyWebApplicationContext.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/MissingPathVariableException.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/accept/MappingMediaTypeFileExtensionResolver.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/remoting/httpinvoker/SimpleHttpInvokerRequestExecutor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/HttpPutFormContentFilter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/HtmlCharacterEntityReferences.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/StreamingHttpOutputMessage.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/xml/AbstractJaxb2HttpMessageConverter.java
*
/spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/jsf/el/WebApplicationContextFacesELResolver.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/json/MappingJacksonValue.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/annotation/AbstractWebArgumentResolverAdapter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/support/InvocableHandlerMethod.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/MediaType.java
* /spring-web-4-3-20-release-sources-1-

jar/org/springframework/http/client/SimpleBufferingAsyncClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/HierarchicalUriComponents.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/BufferedImageHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/HttpRange.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/client/HttpComponentsClientHttpRequestFactory.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/ForwardedHeaderFilter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/HttpOutputMessage.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/InterceptingClientHttpRequest.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/request/AbstractRequestAttributes.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/ContextExposingHttpServletRequest.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/multipart/support/ByteArrayMultipartFileEditor.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/Log4jNestedDiagnosticContextFilter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/support/WebBindingInitializer.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/support/SessionStatus.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/HttpMediaTypeNotSupportedException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/remoting/jaxws/JaxWsPortClientInterceptor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/jsf/el/SpringBeanFacesELResolver.java
*
 /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/InvalidMediaTypeException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/remoting/caucho/HessianProxyFactoryBean.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/xml/XmlAwareFormHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/ServletContextPropertyUtils.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/server/ServerHttpResponse.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/RequestAttributes.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/remoting/caucho/BurlapServiceExporter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/StandardServletEnvironment.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/remoting/caucho/BurlapExporter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/HttpMediaTypeException.java
*

/spring-web-4-3-20-release-sources-1-jar/org/springframework/remoting/caucho/BurlapClientInterceptor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/remoting/caucho/BurlapProxyFactoryBean.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/AbstractRefreshableWebApplicationContext.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/remoting/caucho/HessianServiceExporter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/remoting/caucho/HessianClientInterceptor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/AsyncRequestCallback.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/ServletContextAwareProcessor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/HttpRequestHandler.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/annotation/SessionStatusMethodArgumentResolver.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/ResponseBody.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/CompositeFilter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/annotation/ExpressionValueMethodArgumentResolver.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/multipart/support/DefaultMultipartHttpServletRequest.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/remoting/caucho/SimpleHessianServiceExporter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/ServletRequestHandledEvent.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/ServletConfigPropertySource.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/support/HandlerMethodReturnValueHandler.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/ClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-

jar/org/springframework/web/method/annotation/ModelMethodProcessor.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/AbstractClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/method/annotation/MapMethodProcessor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/Log4jWebConfigurer.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/ConfigurableWebApplicationContext.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/support/HandlerMethodArgumentResolver.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/remoting/caucho/SimpleBurlapServiceExporter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/GenericWebApplicationContext.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/annotation/ErrorsMethodArgumentResolver.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/AsyncClientHttpRequest.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/jsf/FacesContextUtils.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/feed/AtomFeedHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/AsyncClientHttpRequestFactory.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/XmlWebApplicationContext.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/server/ServerHttpAsyncRequestControl.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/async/WebAsyncTask.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/remoting/jaxws/AbstractJaxWsServiceExporter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/ServletContextPropertySource.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/remoting/jaxws/LocalJaxWsServiceFactory.java
*
/spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/StaticWebApplicationContext.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
*/

Found in path(s):
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/GenericHttpMessageConverter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/ServletContextResourceLoader.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/HttpMessageNotReadableException.java
* /spring-web-4-3-20-release-sources-1-

jar/org/springframework/web/context/request/async/NoSupportAsyncWebRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/multipart/MultipartResolver.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/ExceptionHandler.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/HttpEntity.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/ServletContextResourcePatternResolver.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/cors/UrlBasedCorsConfigurationSource.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/request/DestructionCallbackBindingListener.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/ContextLoaderListener.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/request/async/DeferredResultProcessingInterceptor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/RequestHeader.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/HttpMessageNotWritableException.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/RequestContextListener.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/SessionAttributes.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/annotation/MethodArgumentConversionNotSupportedException.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/client/AbstractClientHttpRequestFactoryWrapper.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/support/CompositeUriComponentsContributor.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/annotation/RequestHeaderMethodArgumentResolver.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/request/async/CallableProcessingInterceptorAdapter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/multipart/MaxUploadSizeExceededException.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/ContentCachingResponseWrapper.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/support/WebApplicationObjectSupport.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/json/GsonBuilderUtils.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/request/async/DeferredResultInterceptorChain.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/request/async/StandardServletAsyncWebRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/CookieValue.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/support/DefaultDataBinderFactory.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/annotation/MethodArgumentTypeMismatchException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/OncePerRequestFilter.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/accept/FixedContentNegotiationStrategy.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/RequestContextFilter.java

* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/HttpMessage.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/request/async/CallableInterceptorChain.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/json/MappingJacksonInputMessage.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/MatrixVariable.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/request/async/DeferredResultProcessingInterceptorAdapter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/bind/annotation/support/HandlerMethodResolver.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/cors/CorsUtils.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/annotation/RequestParamMapMethodArgumentResolver.java
*
/spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/bind/support/SpringWebConstraintValidatorFactory.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/remoting/httpinvoker/HttpInvokerRequestExecutor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/HttpSessionMutexListener.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/HttpMessageConversionException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/method/HandlerMethodSelector.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/FacesWebRequest.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/support/AsyncHandlerMethodReturnValueHandler.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/RequestParam.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/support/ProxyFactoryBean.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/RequestMethod.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/client/BufferingClientHttpRequestWrapper.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/CommonsRequestLoggingFilter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/support/HttpRequestWrapper.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/client/BufferingClientHttpResponseWrapper.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/OpaqueUriComponents.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/ResourceHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/EscapedErrors.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/json/GsonFactoryBean.java
*
 /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/client/InterceptingAsyncClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/ResponseEntity.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/remoting/httpinvoker/SimpleHttpInvokerServiceExporter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/support/UriComponentsContributor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/method/HandlerMethod.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/client/UnknownHttpStatusCodeException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/UriTemplate.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/server/ServletServerHttpAsyncRequestControl.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/ResponseStatus.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/ContentCachingRequestWrapper.java
*
 /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/CookieGenerator.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/RestTemplate.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/bind/UnsatisfiedServletRequestParameterException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/WebDataBinder.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/ContextLoader.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/support/AsyncHttpAccessor.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/remoting/httpinvoker/HttpInvokerClientInterceptor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/GenericFilterBean.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/HttpStatus.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/multipart/support/MultipartResolutionDelegate.java
*
 /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/accept/AbstractMappingContentNegotiationStrategy.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/client/HttpComponentsAsyncClientHttpRequestFactory.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/request/async/CallableProcessingInterceptor.java

* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/method/annotation/ModelAttributeMethodProcessor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/AbstractGenericHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/multipart/commons/CommonsFileUploadSupport.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/ResourceRegionHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/AbstractRequestLoggingFilter.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/feed/RssChannelHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/NativeWebRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/HttpRequestMethodNotSupportedException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/ClientHttpResponse.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/ControllerAdvice.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/AsyncRestTemplate.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/HtmlCharacterEntityDecoder.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/multipart/commons/CommonsMultipartFile.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/AbstractRequestAttributesScope.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/UriComponents.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/xml/MappingJackson2XmlHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/remoting/httpinvoker/AbstractHttpInvokerRequestExecutor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/SimpleClientHttpRequestFactory.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/CharacterEncodingFilter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/InterceptingClientHttpRequestFactory.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/accept/ServletPathExtensionContentNegotiationStrategy.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/HttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/UriUtils.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/accept/ContentNegotiationManager.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/HttpComponentsStreamingClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/support/ServletContextAttributeExporter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/HttpMessageConverterExtractor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/support/LiveBeansViewServlet.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/OkHttp3ClientHttpResponse.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/feed/AbstractWireFeedHttpMessageConverter.java

* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/async/WebAsyncUtils.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/remoting/httpinvoker/HttpComponentsHttpInvokerRequestExecutor.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/RestController.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/annotation/AbstractNamedValueMethodArgumentResolver.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/multipart/MultipartFile.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/support/AllEncompassingFormHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/JavaScriptUtils.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/accept/PathExtensionContentNegotiationStrategy.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/remoting/httpinvoker/HttpInvokerServiceExporter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/ResponseErrorHandler.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/DelegatingFilterProxy.java
*
/spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/annotation/ExceptionHandlerMethodResolver.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/StringHttpMessageConverter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/support/RestGatewaySupport.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/RequestCallback.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/ResponseExtractor.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/ClientHttpRequestFactory.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/Mapping.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/multipart/MultipartHttpServletRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/server/ServerHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/support/InterceptingHttpAccessor.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2005 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/filter/ServletContextRequestLoggingFilter.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
```

* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/AbstractContextLoaderInitializer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/ActivationMediaTypeFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
*/

Found in path(s):
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/UriTemplateHandler.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/SessionAttribute.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/xml/SourceHttpMessageConverter.java
*
 /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/accept/MediaTypeFileExtensionResolver.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/json/Jackson2ObjectMapperFactoryBean.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/remoting/caucho/HessianExporter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/request/async/TimeoutCallableProcessingInterceptor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/HttpServerErrorException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/PostMapping.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/HttpStatusCodeException.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/client/AsyncClientHttpRequestInterceptor.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/annotation/RequestParamMethodArgumentResolver.java
*
 /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/HttpComponentsClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/OkHttpClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/RequestEntity.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/async/DeferredResult.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/OkHttp3AsyncClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/GetMapping.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/RestClientResponseException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/OkHttp3ClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/WebRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/PutMapping.java
*
 /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/json/Jackson2ObjectMapperBuilder.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/protobuf/ProtobufHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/request/async/TimeoutDeferredResultProcessingInterceptor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/support/WebRequestDataBinder.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/HtmlUtils.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/method/ControllerAdviceBean.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/DeleteMapping.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/HttpSessionRequiredException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/server/ServletServerHttpResponse.java
*

/spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/SimpleStreamingClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/client/HttpComponentsAsyncClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/annotation/AbstractCookieValueMethodArgumentResolver.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/support/HttpAccessor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/RestControllerAdvice.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/context/request/async/AsyncRequestTimeoutException.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/method/annotation/RequestHeaderMapMethodArgumentResolver.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/converter/ByteArrayHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/cors/DefaultCorsProcessor.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/FacesRequestAttributes.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/RequestPart.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/SpringServletContainerInitializer.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/RestOperations.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/multipart/support/RequestPartServletServerHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/HttpClientErrorException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/ClientHttpRequestExecution.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/json/SpringHandlerInstantiator.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/Netty4ClientHttpRequestFactory.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/ModelAttribute.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/accept/HeaderContentNegotiationStrategy.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/multipart/support/MissingServletRequestPartException.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/AsyncClientHttpRequestExecution.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/web/accept/ParameterContentNegotiationStrategy.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/request/ServletRequestAttributes.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/client/support/BasicAuthorizationInterceptor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/multipart/support/MultipartFilter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/client/AsyncRestOperations.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/PatchMapping.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/OkHttpClientHttpResponse.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/Netty4ClientHttpResponse.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/http/client/support/InterceptingAsyncHttpAccessor.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/remoting/jaxws/SimpleJaxWsServiceExporter.java
* /spring-web-4-3-20-release-sources-1-
jar/org/springframework/remoting/httpinvoker/HttpInvokerProxyFactoryBean.java

* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/accept/ContentNegotiationStrategy.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/AbstractUriTemplateHandler.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/filter/CorsFilter.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/web/method/support/HandlerMethodReturnValueHandlerComposite.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/annotation/ApplicationScope.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/OkHttpClientHttpRequestFactory.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/SimpleStreamingAsyncClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/HttpComponentsAsyncClientHttpResponse.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/cors/CorsConfigurationSource.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/AbstractAsyncClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/HttpComponentsClientHttpResponse.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/util/DefaultUriTemplateHandler.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/AbstractBufferingClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/annotation/SessionScope.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/method/support/HandlerMethodArgumentResolverComposite.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/support/WebApplicationContextUtils.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/xml/MarshallingHttpMessageConverter.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/AbstractBufferingAsyncClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/OkHttpAsyncClientHttpRequest.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/bind/annotation/RequestAttribute.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/support/ServletContextResource.java
*
/spring-web-4-3-20-release-sources-1-jar/org/springframework/http/client/InterceptingAsyncClientHttpRequestFactory.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/web/context/annotation/RequestScope.java
* /spring-web-4-3-20-release-sources-1-jar/org/springframework/http/converter/ObjectToStringHttpMessageConverter.java

1.225 spring-jdbc 4.3.20.RELEASE

1.225.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/RowMapper.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/DataSourceUtils.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/init/DataSourceInitializer.java
*
 /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/namedparam/NamedParameterJdbcOperations.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/DataSourceTransactionManager.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/DatabaseStartupValidator.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/BeanPropertyRowMapper.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/embedded/EmbeddedDatabaseFactory.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/JdbcTransactionObjectSupport.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/namedparam/NamedParameterBatchUpdateUtils.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/SqlParameterValue.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/BatchUpdateUtils.java
*
 /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/metadata/CallMetaDataProvider.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/SqlOutParameter.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/init/DatabasePopulatorUtils.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/incrementer/MySQLMaxValueIncrementer.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/SimpleDriverDataSource.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/simple/SimpleJdbcInsert.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/object/RdbmsOperation.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/JdbcTemplate.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/simple/SimpleJdbcInsertOperations.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/metadata/PostgresCallMetaDataProvider.java
*
 /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/support/SqlLobValue.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/ConnectionProxy.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/support/JdbcBeanDefinitionReader.java

* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/init/ResourceDatabasePopulator.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/ParameterDisposer.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/namedparam/SqlParameterSourceUtils.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/metadata/OracleCallMetaDataProvider.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/RowCountCallbackHandler.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/TransactionAwareDataSourceProxy.java
*
/spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/JdbcOperations.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/SingleConnectionDataSource.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/metadata/TableMetaDataProvider.java
No license file was found, but licenses were detected in source scan.

/**
* The classes in this package make JDBC easier to use and
* reduce the likelihood of common errors. In particular, they:
*
* Simplify error handling, avoiding the need for try/catch/finally
* blocks in application code.
* Present exceptions to application code in a generic hierarchy of
* unchecked exceptions, enabling applications to catch data access
* exceptions without being dependent on JDBC, and to ignore fatal
* exceptions there is no value in catching.
* Allow the implementation of error handling to be modified
* to target different RDBMSes without introducing proprietary
* dependencies into application code.
*
*
* <p>This package and related packages are discussed in Chapter 9 of
* Expert One-On-One J2EE Design and Development
* by Rod Johnson (Wrox, 2002).
*/

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/package-info.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*

*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/UserCredentialsDataSourceAdapter.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/ConnectionHolder.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/StatementCallback.java
*
 /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/SQLErrorCodes.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/config/DatabasePopulatorConfigUtils.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/ConnectionCallback.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/AbstractDriverBasedDataSource.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/PreparedStatementCallback.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/ConnectionHandle.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/DatabaseMetaDataCallback.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/init/CompositeDatabasePopulator.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/object/GenericSqlQuery.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/IsolationLevelDataSourceAdapter.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/LobRetrievalFailureException.java

* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/ResultSetExtractor.java
*
/spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/nativejdbc/C3P0NativeJdbcExtractor.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/RowMapperResultSetExtractor.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/lookup/AbstractRoutingDataSource.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/xml/XmlBinaryStreamProvider.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/xml/SqlXmlObjectMappingHandler.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/object/SqlFunction.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/xml/XmlCharacterStreamProvider.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/lob/JtaLobCreatorSynchronization.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/IncorrectResultSetColumnCountException.java
*
/spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/support/AbstractLobStreamingResultSetExtractor.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/namedparam/SqlParameterSource.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/incrementer/AbstractSequenceMaxValueIncrementer.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/xml/SqlXmlFeatureNotImplementedException.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/support/AbstractSqlTypeValue.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/lookup/JndiDataSourceLookup.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/incrementer/AbstractDataFieldMaxValueIncrementer.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/support/JdbcDaoSupport.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/InterruptibleBatchPreparedStatementSetter.java
*
/spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/JdbcUpdateAffectedIncorrectNumberOfRowsException.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/support/AbstractInterruptibleBatchPreparedStatementSetter.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/namedparam/AbstractSqlParameterSource.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/xml/XmlResultProvider.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/embedded/OutputStreamFactory.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/BatchPreparedStatementSetter.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/lookup/MapDataSourceLookup.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/SqlReturnType.java
*

/spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/lob/LobCreatorUtils.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/config/SortedResourcesFactoryBean.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/BadSqlGrammarException.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/lob/PassThroughBlob.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/nativejdbc/OracleJdbc4NativeJdbcExtractor.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/lob/PassThroughClob.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/CustomSQLExceptionTranslatorRegistrar.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/object/SqlQuery.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/lookup/SingleDataSourceLookup.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/SqlProvider.java
*
/spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/nativejdbc/Jdbc4NativeJdbcExtractor.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/SQLWarningException.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/object/GenericStoredProcedure.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/SqlValue.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/SqlTypeValue.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/object/UpdatableSqlQuery.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/lookup/DataSourceLookup.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/PreparedStatementSetter.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/PreparedStatementCreator.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/InvalidResultSetAccessException.java
*
/spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/CustomSQLExceptionTranslatorRegistry.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/DelegatingDataSource.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/namedparam/NamedParameterJdbcDaoSupport.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/SmartDataSource.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/lookup/DataSourceLookupFailureException.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/object/MappingSqlQueryWithParameters.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/object/SqlUpdate.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/config/JdbcNamespaceHandler.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/CallableStatementCallback.java
*
/spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/object/SqlCall.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/UncategorizedSQLException.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/CallableStatementCreator.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/nativejdbc/NativeJdbcExtractorAdapter.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/AbstractDataSource.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/embedded/EmbeddedDatabaseType.java

* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/RowCallbackHandler.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/lob/SpringLobCreatorSynchronization.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/lookup/BeanFactoryDataSourceLookup.java
*
/spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/nativejdbc/JBossNativeJdbcExtractor.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/object/SqlOperation.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/MetaDataAccessException.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/embedded/SimpleDriverDataSourceFactory.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/SimpleConnectionHandle.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
  * Close this LobCreator session and free its temporarily created BLOBs and CLOBs.
  * Will not need to do anything if using PreparedStatement's standard methods,
  * but might be necessary to free database resources if using proprietary means.
  * <p>NOTE: Needs to be invoked after the involved
 PreparedStatements have
  * been executed or the affected O/R mapping sessions have been flushed.
  * Otherwise, the database resources for the temporary BLOBs might stay allocated.
  */

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/lob/LobCreator.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/xml/SqlXmlValue.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/object/MappingSqlQuery.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/DisposableSqlTypeValue.java
*
 /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/namedparam/ParsedSql.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/incrementer/DB2SequenceMaxValueIncrementer.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/incrementer/DB2MainframeSequenceMaxValueIncrementer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/metadata/SqlServerCallMetaDataProvider.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/metadata/SybaseCallMetaDataProvider.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/incrementer/DataFieldMaxValueIncrementer.java

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/ParameterizedPreparedStatementSetter.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/incrementer/HsqlMaxValueIncrementer.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/namedparam/MapSqlParameterSource.java
*
 /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/incrementer/AbstractColumnMaxValueIncrementer.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/SQLStateSQLExceptionTranslator.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/rowset/SqlRowSetMetaData.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/incrementer/SqlServerMaxValueIncrementer.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/SQLExceptionSubclassTranslator.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/init/ScriptParseException.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/init/DatabasePopulator.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/incrementer/AbstractIdentityColumnMaxValueIncrementer.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/embedded/EmbeddedDatabaseFactoryBean.java
*
 /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/rowset/ResultSetWrappingSqlRowSetMetaData.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/embedded/DataSourceFactory.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/embedded/ConnectionProperties.java

* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/CustomSQLErrorCodesTranslation.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/init/UncategorizedScriptException.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/init/CannotReadScriptException.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/rowset/ResultSetWrappingSqlRowSet.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/init/ScriptException.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/object/StoredProcedure.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/incrementer/DerbyMaxValueIncrementer.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/lob/DefaultLobHandler.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/lookup/IsolationLevelDataSourceRouter.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
```

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/config/InitializeDatabaseBeanDefinitionParser.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/metadata/GenericTableMetaDataProvider.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/object/BatchSqlUpdate.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/embedded/DerbyEmbeddedDatabaseConfigurer.java
*
 /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/incrementer/PostgreSQLSequenceMaxValueIncrementer.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/SQLErrorCodesFactory.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/lob/TemporaryLobCreator.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/embedded/H2EmbeddedDatabaseConfigurer.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/incrementer/Db2MainframeMaxValueIncrementer.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/PreparedStatementCreatorFactory.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/ColumnMapRowMapper.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/KeyHolder.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/CallableStatementCreatorFactory.java
*
 /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/incrementer/Db2LuwMaxValueIncrementer.java

* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/ArgumentTypePreparedStatementSetter.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/StatementCreatorUtils.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/namedparam/NamedParameterUtils.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/namedparam/BeanPropertySqlParameterSource.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/WebSphereDataSourceAdapter.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/metadata/CallParameterMetaData.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/metadata/CallMetaDataProviderFactory.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/metadata/PostgresTableMetaDataProvider.java
*
/spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/embedded/EmbeddedDatabaseConfigurerFactory.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/namedparam/NamedParameterJdbcTemplate.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/metadata/TableMetaDataContext.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/JdbcAccessor.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/incrementer/OracleSequenceMaxValueIncrementer.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/LazyConnectionDataSourceProxy.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/simple/SimpleJdbcCall.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/SQLErrorCodeSQLExceptionTranslator.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/incrementer/PostgresSequenceMaxValueIncrementer.java
*
/spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/metadata/OracleTableMetaDataProvider.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/metadata/CallMetaDataContext.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/incrementer/HsqlSequenceMaxValueIncrementer.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/rowset/SqlRowSet.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/metadata/HanaCallMetaDataProvider.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/init/ScriptUtils.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/AbstractFallbackSQLExceptionTranslator.java
* /spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/support/incrementer/H2SequenceMaxValueIncrementer.java
*
/spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/core/metadata/TableMetaDataProviderFactory.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/ArgumentPreparedStatementSetter.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/SqlReturnResultSet.java

* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/metadata/DerbyCallMetaDataProvider.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/embedded/HsqlEmbeddedDatabaseConfigurer.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/embedded/EmbeddedDatabaseConfigurer.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/SqlParameter.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/incrementer/SybaseMaxValueIncrementer.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/metadata/TableParameterMetaData.java
*
 /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/incrementer/HanaSequenceMaxValueIncrementer.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/ResultSetSupportingSqlParameter.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/GeneratedKeyHolder.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/simple/AbstractJdbcCall.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/JdbcUtils.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/metadata/Db2CallMetaDataProvider.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/metadata/DerbyTableMetaDataProvider.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/metadata/GenericCallMetaDataProvider.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/simple/AbstractJdbcInsert.java
*
 /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/SqlInOutParameter.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/metadata/HsqlTableMetaDataProvider.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/SqlReturnUpdateCount.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/incrementer/SybaseAnywhereMaxValueIncrementer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/nativejdbc/WebSphereNativeJdbcExtractor.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/nativejdbc/WebLogicNativeJdbcExtractor.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/namedparam/EmptySqlParameterSource.java
*
/spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/support/AbstractLobCreatingPreparedStatementCallback.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/lob/AbstractLobHandler.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/CannotGetJdbcConnectionException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/nativejdbc/CommonsDbcpNativeJdbcExtractor.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/embedded/EmbeddedDatabase.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/nativejdbc/SimpleNativeJdbcExtractor.java
*
/spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/embedded/AbstractEmbeddedDatabaseConfigurer.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/nativejdbc/NativeJdbcExtractor.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/embedded/EmbeddedDatabaseBuilder.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/xml/Jdbc4SqlXmlHandler.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/config/EmbeddedDatabaseBeanDefinitionParser.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/datasource/DriverManagerDataSource.java

* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/SingleColumnRowMapper.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/xml/SqlXmlHandler.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/SqlRowSetResultSetExtractor.java
*
/spring-jdbc-4-3-20-release-sources-1-
jar/org/springframework/jdbc/datasource/init/ScriptStatementFailedException.java
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/simple/SimpleJdbcCallOperations.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* Strategy interface for translating between {@link SQLException SQLExceptions}
* and Spring's data access strategy-agnostic {@link DataAccessException}
* hierarchy.
*
* <p>Implementations can be generic (for example, using
* {@link java.sql.SQLException#getSQLState() SQLState} codes for JDBC) or wholly
 * proprietary (for example, using Oracle error codes) for greater precision.
*
* @author Rod Johnson
* @author Juergen Hoeller
* @see org.springframework.dao.DataAccessException
*/

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/SQLExceptionTranslator.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at

```
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* {@link LobHandler} implementation for Oracle databases. Uses proprietary API
* to create {@code oracle.sql.BLOB} and {@code oracle.sql.CLOB}
* instances, as necessary when working with Oracle's JDBC driver.
* Note that this LobHandler requires Oracle JDBC driver 9i or higher!
*
* <p>While most databases
 are able to work with {@link DefaultLobHandler},
* Oracle 9i (or more specifically, the Oracle 9i JDBC driver) just accepts
* Blob/Clob instances created via its own proprietary BLOB/CLOB API,
* and additionally doesn't accept large streams for PreparedStatement's
* corresponding setter methods. Therefore, you need to use a strategy like
* this LobHandler implementation, or upgrade to the Oracle 10g/11g driver
* (which still supports access to Oracle 9i databases).
*
* <p><b>NOTE: As of Oracle 10.2, {@link DefaultLobHandler} should work equally
* well out of the box. On Oracle 11g, JDBC 4.0 based options such as
* {@link DefaultLobHandler#setStreamAsLob} and {@link DefaultLobHandler#setCreateTemporaryLob}
* are available as well, rendering this proprietary OracleLobHandler obsolete.</b>
* Also, consider upgrading to a new driver even when accessing an older database.
* See the {@link LobHandler} interface javadoc for a summary of recommendations.
*
* <p>Needs to
 work on a native JDBC Connection, to be able to cast it to
* {@code oracle.jdbc.OracleConnection}. If you pass in Connections from a
* connection pool (the usual case in a Java EE environment), you need to set an
* appropriate {@link org.springframework.jdbc.support.nativejdbc.NativeJdbcExtractor}
* to allow for automatic retrieval of the underlying native JDBC Connection.
* LobHandler and NativeJdbcExtractor are separate concerns, therefore they
* are represented by separate strategy interfaces.
*
* <p>Coded via reflection to avoid dependencies on Oracle classes.
* Even reads in Oracle constants via reflection because of different Oracle
* drivers (classes12, ojdbc14, ojdbc5, ojdbc6) having different constant values!
* As this LobHandler initializes Oracle classes on instantiation, do not define
* this as eager-initializing singleton if you do not want to depend on the Oracle
* JAR being in the class path: use "lazy-init=true" to avoid this issue.
*
* @author Juergen Hoeller
```

* @author Thomas Risberg
* @since 04.12.2003
* @see DefaultLobHandler
* @see #setNativeJdbcExtractor
* @deprecated in favor of {@link DefaultLobHandler} for the Oracle 10g driver and
* higher. Consider using the 10g/11g driver even against an Oracle 9i database!
* {@link DefaultLobHandler#setCreateTemporaryLob} is the direct equivalent of this
* OracleLobHandler's implementation strategy, just using standard JDBC 4.0 API.
* That said, in most cases, regular DefaultLobHandler setup will work fine as well.
*/

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/lob/OracleLobHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* Implement this interface when parameters need to be customized based
* on the connection. We might need to do this to make use of proprietary
* features, available only with a specific Connection type.
*
* @author Rod Johnson
* @author Thomas Risberg
* @see CallableStatementCreatorFactory#newCallableStatementCreator(ParameterMapper)
 * @see org.springframework.jdbc.object.StoredProcedure#execute(ParameterMapper)
*/
/**
  * Create a Map of input parameters, keyed by name.
  * @param con JDBC connection. This is useful (and the purpose of this interface)
  * if we need to do something RDBMS-specific with a proprietary Connection
  * implementation class. This class conceals such proprietary details. However,
  * it is best to avoid using such proprietary RDBMS features if possible.
  * @throws SQLException if a SQLException is encountered setting
  * parameter values (that is, there's no need to catch SQLException)

```
 * @return Map of input parameters, keyed by name (never {@code null})
 */
```

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/core/ParameterMapper.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* Abstraction for handling large binary fields and large text fields in
* specific databases, no matter if represented as simple types or Large OBjects.
* Its main purpose is to isolate Oracle 9i's peculiar handling of LOBs in
* {@link OracleLobHandler}; most other databases should be able to work
*
 with the provided {@link DefaultLobHandler}.
*
* <p>Provides accessor methods for BLOBs and CLOBs, and acts as factory for
* LobCreator instances, to be used as sessions for creating BLOBs or CLOBs.
* LobCreators are typically instantiated for each statement execution or for
* each transaction; they are not thread-safe because they might track
* allocated database resources in order to free them after execution.
*
* <p>Most databases/drivers should be able to work with {@link DefaultLobHandler},
* which by default delegates to JDBC's direct accessor methods, avoiding the
* {@code java.sql.Blob} and {@code java.sql.Clob} API completely.
* {@link DefaultLobHandler} can also be configured to access LOBs using
* {@code PreparedStatement.setBlob/setClob} (e.g. for PostgreSQL), through
* setting the {@link DefaultLobHandler#setWrapAsLob "wrapAsLob"} property.
*
* <p>Unfortunately, Oracle 9i just accepts Blob/Clob instances created via its own
* proprietary BLOB/CLOB API, and
 additionally doesn't accept large streams for
* PreparedStatement's corresponding setter methods. Therefore, you need to use
* {@link OracleLobHandler} there, which uses Oracle's BLOB/CLOB API for both types
```

```
* of access. The Oracle 10g+ JDBC driver will work with {@link DefaultLobHandler}
* as well, with some limitations in terms of LOB sizes depending on DBMS setup;
* as of Oracle 11g (or actually, using the 11g driver even against older databases),
* there should be no need to use {@link OracleLobHandler} at all anymore.
*
* <p>Of course, you need to declare different field types for each database.
* In Oracle, any binary content needs to go into a BLOB, and all character content
* beyond 4000 bytes needs to go into a CLOB. In MySQL, there is no notion of a
* CLOB type but rather a LONGTEXT type that behaves like a VARCHAR. For complete
* portability, use a LobHandler for fields that might typically require LOBs on
* some database because of the field size (take Oracle's
 numbers as a guideline).
*
* <p><b>Summarizing the recommended options (for actual LOB fields):</b>
* <ul>
* <li><b>JDBC 4.0 driver (including Oracle 11g driver):</b> Use {@link DefaultLobHandler},
* potentially with {@code streamAsLob=true} if your database driver requires that
* hint when populating a LOB field. Fall back to {@code createTemporaryLob=true}
* if you happen to run into LOB size limitations with your (Oracle) database setup.
* <li><b>Oracle 10g driver:</b> Use {@link DefaultLobHandler} with standard setup.
* On Oracle 10.1, set the "SetBigStringTryClob" connection property; as of Oracle 10.2,
* DefaultLobHandler should work with standard setup out of the box. Alternatively,
* consider using the proprietary {@link OracleLobHandler} (see below).
* <li><b>Oracle 9i driver:</b> Use {@link OracleLobHandler} with a connection-pool-specific
* {@link OracleLobHandler#setNativeJdbcExtractor NativeJdbcExtractor}.
* <li><b>PostgreSQL:</b> Configure {@link DefaultLobHandler}
 with {@code wrapAsLob=true},
* and use that LobHandler to access OID columns (but not BYTEA) in your database tables.
* <li>For all other database drivers (and for non-LOB fields that might potentially
* turn into LOBs on some databases): Simply use a plain {@link DefaultLobHandler}.
* </ul>
*
* @author Juergen Hoeller
* @since 23.12.2003
* @see DefaultLobHandler
* @see OracleLobHandler
* @see java.sql.ResultSet#getBlob
* @see java.sql.ResultSet#getClob
* @see java.sql.ResultSet#getBytes
* @see java.sql.ResultSet#getBinaryStream
* @see java.sql.ResultSet#getString
* @see java.sql.ResultSet#getAsciiStream
* @see java.sql.ResultSet#getCharacterStream
*/
```

Found in path(s):
* /spring-jdbc-4-3-20-release-sources-1-jar/org/springframework/jdbc/support/lob/LobHandler.java

1.226 spring-jms 4.3.20.RELEASE

1.226.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/core/JmsMessagingTemplate.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/listener/AbstractMessageListenerContainer.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/listener/AbstractPollingMessageListenerContainer.java
*
 /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/config/JmsListenerEndpointRegistrar.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/connection/JmsTransactionManager.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/core/ProducerCallback.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/connection/JmsResourceHolder.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/core/BrowserCallback.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/support/JmsHeaders.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/listener/adapter/AbstractAdaptableMessageListener.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/support/destination/BeanFactoryDestinationResolver.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/core/SessionCallback.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/connection/ConnectionFactoryUtils.java
*
 /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/listener/endpoint/StandardJmsActivationSpecFactory.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/config/AbstractJmsListenerEndpoint.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2006 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/support/destination/CachingDestinationResolver.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2005 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/core/MessagePostProcessor.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
```

* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/listener/SubscriptionNameProvider.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/listener/LocallyExposedJmsResourceHolder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/support/destination/DynamicDestinationResolver.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/annotation/JmsListenerConfigurer.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/config/JmsNamespaceHandler.java
*
 /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/config/SimpleJmsListenerContainerFactory.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/config/DefaultJmsListenerContainerFactory.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/config/SimpleJmsListenerEndpoint.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/connection/DelegatingConnectionFactory.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/listener/adapter/ReplyFailureException.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/config/JmsListenerEndpoint.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/core/JmsMessageOperations.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/config/DefaultJcaListenerContainerFactory.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/config/JmsListenerContainerFactory.java

*
/spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/core/JmsOperations.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/config/JmsListenerConfigUtils.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/listener/endpoint/DefaultJmsActivationSpecFactory.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/support/converter/MarshallingMessageConverter.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/config/AnnotationDrivenJmsBeanDefinitionParser.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/support/converter/MessageConverter.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/listener/endpoint/JmsActivationSpecFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/config/JcaListenerContainerParser.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/core/JmsTemplate.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/listener/adapter/MessageListenerAdapter.java
*
/spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/support/converter/SmartMessageConverter.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/support/converter/MappingJackson2MessageConverter.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/listener/adapter/MessagingMessageListenerAdapter.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/annotation/JmsListeners.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/support/converter/MessagingMessageConverter.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/support/destination/JmsDestinationAccessor.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/UncategorizedJmsException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/support/converter/MessageType.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/support/JmsUtils.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/listener/adapter/ListenerExecutionFailedException.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/connection/ChainedExceptionListener.java
*
/spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/support/destination/JndiDestinationResolver.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/connection/UserCredentialsConnectionFactoryAdapter.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/IllegalStateException.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/InvalidDestinationException.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/remoting/JmsInvokerProxyFactoryBean.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/MessageEOFException.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/ResourceAllocationException.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/JmsException.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/MessageNotWriteableException.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/MessageFormatException.java
*
/spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/JmsSecurityException.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/MessageNotReadableException.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/connection/SynchedLocalTransactionFailedException.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/support/destination/DestinationResolutionException.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/connection/SessionProxy.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/core/support/JmsGatewaySupport.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/TransactionInProgressException.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/core/MessageCreator.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/remoting/JmsInvokerServiceExporter.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/TransactionRolledBackException.java
*
/spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/connection/SmartConnectionFactory.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/InvalidClientIDException.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/InvalidSelectorException.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/listener/SessionAwareMessageListener.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/support/converter/MessageConversionException.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/support/destination/DestinationResolver.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/connection/CachedMessageConsumer.java

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/listener/endpoint/JmsMessageEndpointManager.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/remoting/JmsInvokerClientInterceptor.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/annotation/JmsBootstrapConfiguration.java
*
 /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/listener/SimpleMessageListenerContainer.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/support/JmsAccessor.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/listener/MessageListenerContainer.java
* /spring-jms-4-3-20-release-sources-1-
jar/org/springframework/jms/listener/endpoint/JmsActivationSpecConfig.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/connection/CachedMessageProducer.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/listener/adapter/JmsResponse.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/annotation/JmsListenerAnnotationBeanPostProcessor.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/support/SimpleJmsHeaderMapper.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/support/converter/SimpleMessageConverter.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/config/AbstractListenerContainerParser.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/config/AbstractJmsListenerContainerFactory.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/config/JmsListenerContainerParser.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/config/MethodJmsListenerEndpoint.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/listener/DefaultMessageListenerContainer.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/support/JmsHeaderMapper.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/connection/CachingConnectionFactory.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/connection/TransactionAwareConnectionFactoryProxy.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/annotation/EnableJms.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/config/JmsListenerEndpointRegistry.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/listener/AbstractJmsListeningContainer.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/support/JmsMessageHeaderAccessor.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/listener/endpoint/JmsMessageEndpointFactory.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/connection/SingleConnectionFactory.java
* /spring-jms-4-3-20-release-sources-1-jar/org/springframework/jms/annotation/JmsListener.java

1.227 netty 4.1.48.Final

1.227.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.

*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/DefaultHeadersImpl.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/InboundHttp2ToHttpAdapterBuilder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DecoratingHttp2ConnectionDecoder.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/WeightedFairQueueByteDistributor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/StreamByteDistributor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/MathUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/ByteProcessor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2PromisedRequestVerifier.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/ValueConverter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DecoratingHttp2ConnectionEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/CharSequenceValueConverter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2StreamVisitor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/CoalescingBufferQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/AbstractInboundHttp2ToHttpAdapterBuilder.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/UniformStreamByteDistributor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/StreamBufferingEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DecoratingHttp2FrameWriter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/RedisMessageType.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/IntegerRedisMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/DefaultLastBulkStringRedisContent.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/RedisCodecUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/AbstractStringRedisMessage.java

* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/ErrorRedisMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/RedisMessagePool.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/redis/RedisClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/LastBulkStringRedisContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/BulkStringRedisContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/frame/server/HelloWorldHttp2Handler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/RedisCodecException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/FullBulkStringRedisMessage.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/SimpleStringRedisMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/RedisDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/RedisBulkStringAggregator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/frame/server/Http2OrHttpHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/multiplex/server/Http2OrHttpHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/BulkStringHeaderRedisMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/FixedRedisMessagePool.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/DefaultBulkStringRedisContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/RedisArrayAggregator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/ArrayRedisMessage.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/RedisConstants.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/ArrayHeaderRedisMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/RedisMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/RedisEncoder.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/example/http2/helloworld/multiplex/server/HelloWorldHttp2Handler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2FrameReader.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2ConnectionDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameTypes.java

*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/collection/ShortObjectMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Connection.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2DataWriter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2Connection.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/collection/ShortObjectHashMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2EventAdapter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ServerUpgradeCodec.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/ObjectUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/collection/CharObjectHashMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Error.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttQoS.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameWriter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/collection/LongObjectMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ConnectionHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2LocalFlowController.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ConnectionAdapter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameListener.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/EmptyHeaders.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2HeadersDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2NoMoreStreamIdsException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/client/Http2SettingsHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/server/Http2OrHttpHandler.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/EmptyHttp2Headers.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/CompressorHttp2ConnectionEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HttpToHttp2ConnectionHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2LifecycleManager.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpServerUpgradeHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2RemoteFlowController.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2CodecUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Flags.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameReader.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/collection/LongCollections.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/InboundHttp2ToHttpAdapter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2RemoteFlowController.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ConnectionEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2ConnectionEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/collection/CharCollections.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/client/Http2Client.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/collection/ByteObjectHashMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/collection/ShortCollections.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/Headers.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/client/Http2ClientInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2FrameWriter.java

*
 /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/Http2ExampleUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/client/HttpResponseHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/collection/CharObjectMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/DefaultHeaders.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ClientUpgradeCodec.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Settings.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/collection/IntObjectHashMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/collection/ByteObjectMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameSizePolicy.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameAdapter.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/server/HelloWorldHttp2Handler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2HeadersDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2HeadersEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2HeadersEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/collection/ByteCollections.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FlowController.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Headers.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/collection/IntObjectMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Exception.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DelegatingDecompressorFrameListener.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameListenerDecorator.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ConnectionDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2LocalFlowController.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/collection/IntCollections.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Stream.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/collection/LongObjectHashMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpClientUpgradeHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2Headers.java
No license file was found, but licenses were detected in source scan.

~ Copyright 2012 The Netty Project
 ~
 ~ The Netty Project licenses this file to you under the Apache License,
 ~ version 2.0 (the "License"); you may not use this file except in compliance
 ~ with the License. You may obtain a copy of the License at:
 ~
 ~   http://www.apache.org/licenses/LICENSE
2.0
 ~
 ~ Unless required by applicable law or agreed to in writing, software
 ~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
 ~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
 ~ License for the specific language governing permissions and limitations
 ~ under the License.

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/META-INF/maven/io.netty/netty-all/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/rxtx/RxtxChannelOption.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/rxtx/RxtxDeviceAddress.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/oio/OioByteStreamChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/SctpChannelOption.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/channel/rxtx/DefaultRxtxChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/rxtx/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/rxtx/RxtxChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/UdtServerChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/rxtx/RxtxChannelConfig.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.

```
*/
/*
* Written by Robert Harder and released to the public domain, as explained at
* http://creativecommons.org/licenses/publicdomain
*/
/**
* Utility class for {@link ByteBuf} that encodes and decodes to and from
* <a href="http://en.wikipedia.org/wiki/Base64">Base64</a> notation.
* <p>
*
 The encoding and decoding algorithm in this class has been derived from
* <a href="http://iharder.sourceforge.net/current/java/base64/">Robert Harder's Public Domain
* Base64 Encoder/Decoder</a>.
*/
```

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/base64/Base64.java
No license file was found, but licenses were detected in source scan.

```
/*
  Stomp Over WebSocket http://www.jmesnil.net/stomp-websocket/doc/ | Apache License V2.0
  Copyright (C) 2010-2013 [Jeff Mesnil](http://jmesnil.net/)
  Copyright (C) 2012 [FuseSource, Inc.](http://fusesource.com)
*/
```

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/example/stomp/websocket/stomp.js
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
* Copyright (c) 2004-2011 QOS.ch
* All rights reserved.
*
```

* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without
limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be
* included in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
* NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
* LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
* OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
* WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/JdkLogger.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/CommonsLogger.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/Log4JLogger.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/InternalLogger.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2020 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/util/DomainWildcardMappingBuilder.java

* /netty-all-4-1-49-final-sources-jar/io/netty/example/stomp/websocket/StompVersion.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/SslHandshakeTimeoutException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/search/package-info.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/example/haproxy/HAProxyHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/stomp/websocket/StompWebSocketClientPageHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/stomp/websocket/StompWebSocketChatServerInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/stomp/websocket/StompWebSocketChatServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/haproxy/HAProxyClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/stomp/websocket/StompSubscription.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/haproxy/HAProxyServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/stomp/websocket/StompWebSocketProtocolCodec.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/address/ResolveAddressHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/haproxy/HAProxyMessageEncoder.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/example/stomp/websocket/StompChatHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/logging/ByteBufFormat.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/traffic/GlobalChannelTrafficShapingHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2018 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DefaultAuthoritativeDnsServerCache.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslKeyMaterialProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslX509KeyManagerFactory.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslPrivateKey.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/AuthoritativeDnsServerCache.java
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/CertificateCallback.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/AuthoritativeDnsServerCacheAdapter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/PreferredDirectByteBufAllocator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslKeyMaterial.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslCachingKeyMaterialProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsRecordResolveContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DirContextUtils.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/SignatureAlgorithmConverter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsCnameCache.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/SimpleUserEventChannelHandler.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/nio/NioChannelOption.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslX509TrustManagerWrapper.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsAddressDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/Buffer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/NoopAuthoritativeDnsServerCache.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslSession.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/Cache.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/NameServerComparator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslCachingX509KeyManagerFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/DefaultOpenSslKeyMaterial.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslTlsv13X509ExtendedTrustManager.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsAddressResolveContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DefaultDnsCnameCache.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/NoopDnsCnameCache.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/SuppressJava6Requirement.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/ExtendedOpenSslSession.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,

* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/*
* Adaptation of http://bjoern.hoehrmann.de/utf-8/decoder/dfa/
*
* Copyright (c) 2008-2009 Bjoern Hoehrmann <bjoern@hoehrmann.de>
*
* Permission is hereby granted, free of charge, to any person obtaining a copy of this software
* and associated documentation files (the "Software"), to deal
 in the Software without restriction,
* including without limitation the rights to use, copy, modify, merge, publish, distribute,
* sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is
* furnished to do so, subject to the following conditions:
*
* The above copyright notice and this permission notice shall be included in all copies or
* substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING
* BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
* NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
* DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
* OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/Utf8Validator.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2018 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:

*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/ResourcesUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/redis/InlineCommandRedisMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/ByteProcessorUtils.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelFlushPromiseNotifier.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/SingleThreadEventLoop.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/message/MsgEchoClientHandler.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/example/factorial/FactorialClientInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5CommandResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/FileUpload.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/JdkLoggerFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/rendezvousBytes/ByteEchoPeerBase.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelInboundHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/timeout/WriteTimeoutException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/ByteBufOutputStream.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/upload/HttpUploadClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/CompleteChannelFuture.java

* /netty-all-4-1-49-final-sources-jar/io/netty/util/package-info.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/BlockingOperationException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/local/LocalEventLoopGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/DefaultLastHttpContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5PasswordAuthResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/Log4JLoggerFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/snoop/HttpSnoopClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/rendezvousBytes/ByteEchoPeerOne.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/rendezvousBytes/ByteEchoPeerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/oio/package-info.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/MarshallingDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/sctp/SctpEchoClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/FailedChannelFuture.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/CodecException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/Delimiters.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/NotSslRecordException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/LastHttpContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/CharsetUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/DefaultHttpRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/HttpPostMultipartRequestDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/DefaultSocks4CommandRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/MarshallerProvider.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/rtsp/RtspObjectEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/websocketx/server/WebSocketServerIndexPage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/proxy/HexDumpProxyFrontendHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/HttpData.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/ChannelBufferByteInput.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdySession.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4ServerDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpContentDecompressor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/MemoryAttribute.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ObjectEncoderOutputStream.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/FixedRecvByteBufAllocator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/sctp/SctpEchoServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ClassLoaderClassResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/echo/EchoServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/uptime/UptimeClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/stream/ChunkedNioStream.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/factorial/FactorialClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpResponseDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ClassResolvers.java

* /netty-all-4-1-49-final-sources-jar/io/netty/bootstrap/Bootstrap.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/CommonsLoggerFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpResponseEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/group/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/timeout/WriteTimeoutHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/nio/NioEventLoop.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/bytes/ByteEchoServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/TextWebSocketFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/EventExecutorGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/DelimiterBasedFrameDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PoolChunkList.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/package-info.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshaker13.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelPromise.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/factorial/FactorialClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/QueryStringEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/worldclock/WorldClockServerInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/stream/ChunkedNioFile.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/UnknownSocksResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PooledByteBufAllocator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/HttpPostRequestEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/rtsp/RtspResponseStatuses.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PooledDirectByteBuf.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/bytes/ByteEchoClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/SocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/VoidChannelPromise.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/oio/AbstractOioMessageChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/NetUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/factorial/NumberEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyHttpHeaders.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshaker00.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/ServerSocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/SlicedByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelOutboundHandlerAdapter.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/PongWebSocketFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/UnpooledHeapByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/bytes/ByteEchoServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/HttpPostRequestDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/EventExecutor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/oio/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/qotm/QuoteOfTheMomentClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/worldclock/WorldClockServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/socksproxy/SocksServerInitializer.java

* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/InternalLogLevel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/qotm/QuoteOfTheMomentClient.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/rtsp/RtspVersions.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/DefaultHttpObject.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/qotm/QuoteOfTheMomentServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/ByteToMessageDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyHttpEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpObjectEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/ByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/InternalLoggerFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/telnet/TelnetServerInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/rtsp/RtspRequestEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/package-info.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/LengthFieldPrepender.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/telnet/TelnetServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/upload/HttpUploadServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ClassResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/securechat/SecureChatClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/DefaultChannelPromise.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/MessageAggregator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/ContinuationWebSocketFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/oio/OioServerSocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpResponse.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/example/discard/DiscardClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/Signal.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpContentDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/message/MsgEchoServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/ByteBufAllocator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/JZlibEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/MultithreadEventLoopGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/snoop/HttpSnoopClientInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpHeaderDateFormat.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/DatagramChannel.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/CorruptedFrameException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/SoftReferenceMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/AbstractChannelHandlerContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/SingleThreadEventExecutor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/oio/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/rendezvous/MsgEchoPeerOne.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/telnet/TelnetClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/UnpooledUnsafeDirectByteBuf.java

* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/AbstractByteBufAllocator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/DefaultEventLoopGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/AbstractByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpRequestEncoder.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/channel/SucceededChannelFuture.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/oio/AbstractOioByteChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/group/CombinedIterator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/ByteBufUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4CommandResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/CompatibleMarshallingEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/bootstrap/ServerBootstrap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/websocketx/server/WebSocketServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/worldclock/WorldClockServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/sctp/SctpOutboundByteStreamHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ReferenceMap.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/CompressionException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/rendezvous/Config.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/group/DefaultChannelGroupFuture.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksAuthResponseDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/IllegalReferenceCountException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5CommandRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/InternetProtocolFamily.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/AbstractServerChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/group/ChannelGroupFutureListener.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/example/http/snoop/HttpSnoopServerInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/EventLoopGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ServerChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/DiskFileUpload.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/ZlibEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/message/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/rtsp/RtspObjectDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/EventLoop.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/AttributeMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/Attribute.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/DefaultUdtChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelInitializer.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/logging/LogLevel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5InitialResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/timeout/ReadTimeoutException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/stream/ChunkedStream.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/MultithreadEventExecutorGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PoolArena.java

* /netty-all-4-1-49-final-sources-jar/io/netty/example/securechat/SecureChatClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/cors/HttpCorsServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/bytes/ByteArrayDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/SslHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/FixedLengthFrameDecoder.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksInitResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/PrematureChannelClosureException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/ThreadLocalUnmarshallerProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4CommandRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/HttpPostBodyUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/upload/HttpUploadServerInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ObjectDecoderInputStream.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/LimitingByteInput.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/websocketx/server/WebSocketIndexPageHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocket00FrameEncoder.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/DefaultEventExecutor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksCommonUtils.java
* /netty-all-4-1-49-final-sources-jar/io/netty/bootstrap/AbstractBootstrap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/MarshallingEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/nio/NioDatagramChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/AttributeKey.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/DefaultChannelPipeline.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelMetadata.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/DefaultHttpDataFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/embedded/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/DefaultCookie.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/channel/embedded/EmbeddedChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/telnet/TelnetClientInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelPipelineException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksInitResponseDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/nio/NioDatagramChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/AbstractConstant.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/DecoderException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/securechat/SecureChatServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/securechat/SecureChatClientInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpObject.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/ZlibCodecFactory.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/channel/EventLoopException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/stream/ChunkedWriteHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/AbstractInternalLogger.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/snoop/HttpSnoopClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/ReplayingDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpObjectDecoder.java

* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/SwappedByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/TimerTask.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/HttpDataFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/JZlibDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5CommandResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/bootstrap/package-info.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/example/factorial/BigIntegerDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshaker07.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5InitialRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/DefaultMarshallerProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/echo/EchoClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/factorial/FactorialServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/MessageToMessageEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/DuplicatedByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/ChannelBufferByteOutput.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/oio/OioSctpServerChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshaker08.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/logging/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/ZlibDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/MixedAttribute.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/SocksMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/DiskAttribute.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelFuture.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5PasswordAuthRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/stream/ChunkedFile.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpVersion.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/UnpooledDirectByteBuf.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/DefaultHttpMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/factorial/FactorialServerInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/UnmarshallerProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/websocketx/server/WebSocketFrameHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5CommandRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/message/MsgEchoServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/socksproxy/RelayHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/oio/AbstractOioChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelOption.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/ByteToMessageCodec.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/SocketChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/upload/HttpUploadClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/timeout/IdleStateHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/package-info.java

* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4CommandType.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/local/LocalAddress.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/Timer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksAuthResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/snoop/HttpSnoopServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/PingWebSocketFrame.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelPromiseAggregator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ThreadPerChannelEventLoop.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/oio/OioSctpChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpRequestDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/TooLongFrameException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/socksproxy/SocksServerUtils.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/sctp/SctpEchoClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/Constant.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/DecompressionException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelInboundHandlerAdapter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/proxy/HexDumpProxyBackendHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/package-info.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/DecoderResult.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/objectecho/ObjectEchoServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksCmdResponseDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/DefaultServerSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PooledByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpContentCompressor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/ServerSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/base64/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/DefaultSpdySettingsFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/bytes/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/package-info.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/rtsp/RtspRequestDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/DefaultHttpResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelHandlerContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/CompatibleObjectEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpObjectAggregator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5InitialRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/cors/HttpCorsServerInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/nio/AbstractNioByteChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/FileRegion.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/nio/NioTask.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/example/http/websocketx/server/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/UnknownSocksRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/nio/NioEventLoopGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/MessageToByteEncoder.java

* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/file/HttpStaticFileServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/discard/DiscardClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/nio/AbstractNioMessageChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/localecho/LocalEchoServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/objectecho/ObjectEchoClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/DefaultDatagramChannelConfig.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/Timeout.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/file/HttpStaticFileServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpConstants.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/ContextBoundUnmarshallerProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksInitRequestDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/echo/EchoClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/securechat/SecureChatServerInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/rtsp/RtspMethods.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/timeout/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/localecho/LocalEchoClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/rendezvous/package-info.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/example/worldclock/WorldClockClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/ThreadLocalMarshallerProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/worldclock/WorldClockClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/discard/DiscardServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/bytes/ByteEchoClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/local/LocalChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksAuthRequestDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/protobuf/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksInitRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/snoop/HttpSnoopServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/Channel.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/channel/local/LocalServerChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/nio/ProtocolFamilyConverter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/ReadOnlyByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/SnappyFrameEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/LineBasedFrameDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/socksproxy/SocksServerConnectHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/timeout/ReadTimeoutHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/objectecho/ObjectEchoClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/MixedFileUpload.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelDuplexHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/timeout/TimeoutException.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/UdtChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/localecho/LocalEcho.java

* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/nio/NioServerSocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpServerCodec.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/bytes/ByteArrayEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/CombinedChannelDuplexHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/string/StringEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Snappy.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/PlatformDependent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/AdaptiveRecvByteBufAllocator.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpMethod.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/DefaultSocks4CommandResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PoolSubpage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ObjectEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/DefaultHttpHeaders.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/telnet/TelnetServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4ClientDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/Slf4JLoggerFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/GlobalEventExecutor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/Attribute.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/DatagramChannelConfig.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyHttpResponseStreamIdHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/HttpPostStandardRequestDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/DefaultUnmarshallerProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/Unpooled.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/upload/HttpUploadClientInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/string/StringDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5InitialResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ObjectDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/DefaultSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/socksproxy/DirectClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/factorial/FactorialServer.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/CaseIgnoringComparator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpResponseStatus.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4CommandStatus.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelOutboundHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/UdtMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksAuthRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/Slf4JLogger.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/StringUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/ChannelInputShutdownEvent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/BinaryWebSocketFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/socksproxy/SocksServer.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/example/discard/DiscardServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/stream/package-info.java

* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/websocketx/server/WebSocketServerInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/CachingClassResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/echo/EchoServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/worldclock/WorldClockClientInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/portunification/PortUnificationServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/uptime/UptimeClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/DefaultHttpContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/DefaultEventLoop.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/HashedWheelTimer.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/example/telnet/TelnetClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/EncoderException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/nio/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/message/MsgEchoClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/DefaultFileRegion.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/ReplayingDecoderByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ThreadPerChannelEventLoopGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/AbstractHttpData.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/timeout/IdleStateEvent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/file/FileServer.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/util/DefaultAttributeMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/CompactObjectOutputStream.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/QueryStringDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelFutureListener.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshaker.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/embedded/EmbeddedEventLoop.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/qotm/QuoteOfTheMomentServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/CompatibleMarshallingDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/UnpooledByteBufAllocator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/CookieDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/AbstractDiskHttpData.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpHeaders.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/MessageToMessageDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/timeout/IdleState.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/MessageToMessageCodec.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/AbstractMemoryHttpData.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketVersion.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/local/LocalChannelRegistry.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PoolChunk.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/sctp/SctpEchoServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/logging/LoggingHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/rendezvousBytes/ByteEchoPeerTwo.java
*

/netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/nio/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/base64/Base64Encoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/socksproxy/SocksServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksCmdRequestDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/WeakReferenceMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/nio/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/FailedFuture.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/portunification/PortUnificationServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/oio/OioDatagramChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/bytes/package-info.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/channel/RecvByteBufAllocator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/CompactObjectInputStream.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/DatagramPacket.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/UnsupportedMessageTypeException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/AbstractChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/InterfaceHttpPostRequestDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/SystemPropertyUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/SucceededFuture.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/rendezvous/MsgEchoPeerBase.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/upload/HttpUploadServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketHandshakeException.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/rtsp/RtspResponseDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/SnappyFrameDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/nio/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/embedded/EmbeddedSocketAddress.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/InternalAttribute.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/rtsp/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/oio/OioEventLoopGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelPromiseNotifier.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/objectecho/ObjectEchoServerHandler.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/channel/nio/AbstractNioChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/rendezvous/MsgEchoPeerTwo.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/string/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/Cookie.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/DefaultEventExecutorGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelPipeline.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PoolThreadCache.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/oio/OioSocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/rendezvous/MsgEchoPeerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/JdkZlibEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/securechat/SecureChatServer.java

*
/netty-all-4-1-49-final-sources-jar/io/netty/buffer/ByteBufInputStream.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpContentEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/proxy/HexDumpProxyInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/InterfaceHttpData.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/DefaultChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/proxy/HexDumpProxy.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/file/HttpStaticFileServerInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/nio/NioSocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksCmdResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksMessageEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/package-info.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksCmdRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/base64/Base64Decoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollDatagramChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpClientCodec.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/udt/echo/rendezvousBytes/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/MemoryFileUpload.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/rtsp/RtspResponseEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/stream/ChunkedInput.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/helloworld/HttpHelloWorldServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/util/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/ZlibWrapper.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/local/package-info.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/buffer/CompositeByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/group/ChannelGroupFuture.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/ZlibUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/rtsp/RtspHeaders.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshakerFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.

```
*/
/*
* Written by Robert Harder and released to the public domain, as explained at
* http://creativecommons.org/licenses/publicdomain
*/
/**
* Enumeration of supported Base64 dialects.
* <p>
* The internal lookup tables in this class has been derived from
* <a href="http://iharder.sourceforge.net/current/java/base64/">Robert
 Harder's Public Domain
* Base64 Encoder/Decoder</a>.
*/
```

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/base64/Base64Dialect.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
// (BSD License: http://www.opensource.org/licenses/bsd-license)
// All rights reserved.
// Redistribution and use in source and binary forms, with or
// * Redistributions of source code must retain the above
// copyright notice, this list of conditions and the
// following disclaimer.
// * Redistributions
 in binary form must reproduce the above
// following disclaimer in the documentation and/or other
// * Neither the name of the Webbit nor the names of
```

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocket08FrameEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocket13FrameEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocket07FrameEncoder.java

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2020 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/search/AhoCorasicSearchProcessorFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/search/MultiSearchProcessorFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/search/AbstractMultiSearchProcessorFactory.java
*
/netty-all-4-1-49-final-sources-
jar/io/netty/example/http2/helloworld/frame/client/Http2ClientStreamFrameResponseHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/frame/client/Http2FrameClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/frame/client/Http2ClientFrameInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/search/BitapSearchProcessorFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/search/MultiSearchProcessor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/search/AbstractSearchProcessorFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/search/KmpSearchProcessorFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/search/SearchProcessor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/search/SearchProcessorFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations

* under the License.
*/
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
 * (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/Library.java
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/SSL.java
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/SSLContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/Buffer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2011 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/DefaultSctpServerChannelConfig.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project

*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/AbstractCoalescingBufferQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ConnectionPrefaceAndSettingsFrameWrittenEvent.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PooledHeapByteBuf.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/CleanerJava9.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/Cleaner.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/FastThreadLocalRunnable.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/SslHandshakeCompletionEvent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/DefaultAddressedEnvelope.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyHeadersFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/binary/package-info.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheClientCodec.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/AbstractMemcacheObjectDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/binary/FullBinaryMemcacheRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketFrameAggregator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/MemcacheMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/ImmediateEventExecutor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthStatus.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/rxtx/RxtxClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/rxtx/RxtxClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/DefaultChannelId.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5AuthMethod.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/memcache/binary/AbstractBinaryMemcacheDecoder.java

* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdySessionHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelId.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/WebSocketClientProtocolHandshakeHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlFrameDecoder.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheResponseEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/DefaultSpdyHeaders.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/ConstantPool.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/group/ChannelMatchers.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/NoOpTypeParameterMatcher.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockRawEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/FullHttpMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksAuthScheme.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/Recycler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/ImmediateExecutor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksResponseType.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ConnectTimeoutException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyGoAwayFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/DefaultMemcacheContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/Promise.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockJZlibEncoder.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/DefaultThreadFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/AbstractEventExecutor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/AbstractReferenceCountedByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/SimpleLeakAwareByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/DefaultFullHttpRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelProgressivePromise.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/DefaultChannelProgressivePromise.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/UdtServerChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/FullHttpRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/DefaultFullHttpResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/DefaultSpdySynStreamFrame.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/LastMemcacheContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/UnreleasableByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/DefaultSpdyDataFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/FullHttpResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5AddressType.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/DefaultMessageSizeEstimator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyHttpDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/DefaultByteBufHolder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/AbstractMemcacheObjectAggregator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/DefaultProgressivePromise.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/FullMemcacheMessage.java
*

/netty-all-4-1-49-final-sources-jar/io/netty/channel/MessageSizeEstimator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/AbstractMemcacheObject.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/memcache/binary/DefaultFullBinaryMemcacheRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheServerCodec.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/EmptyByteBuf.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/memcache/binary/DefaultBinaryMemcacheResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/ResourceLeakException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/DefaultSpdyGoAwayFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Crc32c.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/oio/OioSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/GenericProgressiveFutureListener.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheRequestEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/DefaultSpdyHeadersFrame.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheResponseDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheOpcodes.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyHeaders.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/SocksVersion.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/SimpleChannelInboundHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelOutboundBuffer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/group/ChannelGroupException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/Native.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/PlatformDependent0.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/AbstractFuture.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/worldclock/WorldClockProtocol.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/helloworld/HttpHelloWorldServerInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/FutureListener.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdySynReplyFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheRequestDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyHttpCodec.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketFrameDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockZlibEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/UdtChannelOption.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/channel/AddressedEnvelope.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/DefaultPromise.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyVersion.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksProtocolVersion.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/ReadOnlyIterator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/WrappedByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/FixedCompositeByteBuf.java
* /netty-all-4-1-49-final-sources-

jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheObjectAggregator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/DefaultSpdyPingFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketClientProtocolHandler.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/buffer/AdvancedLeakAwareByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/ReadOnlyByteBufferBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/binary/FullBinaryMemcacheResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/DefaultSpdyStreamFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/helloworld/HttpHelloWorldServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketProtocolHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/AppendableCharSequence.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/ScheduledFutureTask.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/GenericFutureListener.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/ByteBufProcessor.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5CommandType.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/AbstractEventLoopGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/RecyclableArrayList.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksCmdStatus.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/AbstractEventExecutorGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksAuthStatus.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/oio/DefaultOioServerSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketFrameEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/ComposedLastHttpContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelProgressiveFuture.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheResponseStatus.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/Future.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/DefaultUdtServerChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/ConcurrentSet.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/ReferenceCountUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/CompleteFuture.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/oio/OioServerSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdySessionStatus.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/group/ChannelGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksMessageType.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/DefaultFutureListeners.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/PromiseTask.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/DefaultSpdyRstStreamFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/group/ChannelMatcher.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyWindowUpdateFrame.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/memcache/binary/AbstractBinaryMemcacheMessage.java

* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/MemcacheContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/DefaultLastMemcacheContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyRstStreamFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/ReadOnlyUnsafeDirectByteBuf.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/ProgressiveFuture.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyCodecUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/cors/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyStreamFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/Version.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksSubnegotiationVersion.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksCmdType.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/ReferenceCounted.java
* /netty-all-4-1-49-final-sources-jar/io/netty/bootstrap/ChannelFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/AbstractMemcacheObjectEncoder.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/PendingWrite.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/TypeParameterMatcher.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/DefaultSpdySynReplyFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/ByteBufHolder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyStreamStatus.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/ProgressivePromise.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/memcache/binary/DefaultFullBinaryMemcacheResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyPingFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/ScheduledFuture.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/AbstractReferenceCounted.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/ResourceLeak.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/group/DefaultChannelGroup.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/ResourceLeakDetector.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksAddressType.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/AbstractDerivedByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelHandlerAdapter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/ThreadPerTaskExecutor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/nio/SelectedSelectionKeySet.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/oio/DefaultOioSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/DefaultSpdyWindowUpdateFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/JdkZlibDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PooledUnsafeDirectByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5CommandStatus.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/EmptyArrays.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/binary/DefaultBinaryMemcacheRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdySettingsFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelProgressiveFutureListener.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksRequestType.java

* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/memcache/binary/AbstractBinaryMemcacheEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/memcache/MemcacheObject.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyDataFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdySynStreamFrame.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/sctp/SctpMessageCompletionHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/sctp/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/nio/NioUdtByteRendezvousChannel.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/traffic/GlobalTrafficShapingHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/nio/NioUdtProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/nio/NioUdtByteConnectorChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/traffic/ChannelTrafficShapingHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/UdtChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/nio/NioUdtMessageAcceptorChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/traffic/TrafficCounter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/nio/NioUdtAcceptorChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/sctp/SctpInboundByteStreamHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/traffic/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/nio/NioUdtMessageConnectorChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/nio/NioUdtMessageRendezvousChannel.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/sctp/SctpMessageToMessageDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/udt/nio/NioUdtByteAcceptorChannel.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project

*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
// Try the OpenJDK's proprietary implementation.

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/util/SelfSignedCertificate.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version
* 2.0 (the "License"); you may not use this file except in compliance with the
* License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/cors/CorsConfigBuilder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/smtp/DefaultSmtpResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/flow/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/SessionTicketKey.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ResetFrame.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DefaultDnsOptEcsRecord.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/smtp/SmtpCommand.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2DataFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/RoundRobinInetAddressResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/SelectStrategyFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2WindowUpdateFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/CertificateRequestedCallback.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2PingFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/UnpooledUnsafeNoCleanerDirectByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Frame.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/UnaryPromiseNotifier.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2SettingsFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/ReferenceCountedOpenSslEngine.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/PemX509Certificate.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/DatagramPacketEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2StreamFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/ResourceLeakTracker.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/DatagramPacketDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2StreamFrameToHttpObjectCodec.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/MacAddressUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsCache.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/multipart/FileUploadUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameCodec.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2MultiplexCodec.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/PemPrivateKey.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/smtp/DefaultSmtpContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueSocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/RejectedExecutionHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/SimpleLeakAwareCompositeByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/ReadOnlyHttp2Headers.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/UnstableApi.java

*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/CompressionUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/WrappedCompositeByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/frame/server/Http2ServerInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/BooleanSupplier.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/AbstractKQueueStreamChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PooledSlicedByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/smtp/LastSmtpContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/flush/FlushConsolidationHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PooledDuplicatedByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/ResourceLeakDetectorFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpServerKeepAliveHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/group/VoidChannelGroupFuture.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/buffer/WrappedUnpooledUnsafeDirectByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/string/LineEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/AbstractKQueueServerChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/PemEncoded.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/haproxy/HAProxyTLV.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/SelectStrategy.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2ResetFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueStaticallyReferencedJniMethods.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/DefaultEventExecutorChooserFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/ThrowableUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/DefaultSelectStrategyFactory.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2GoAwayFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/EventExecutorChooserFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/multiplex/server/Http2ServerInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/OrderedEventExecutor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/bootstrap/AbstractBootstrapConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/redis/RedisClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/SocketUtils.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/smtp/DefaultLastSmtpContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/NativeLongArray.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/InflightNameResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelInboundInvoker.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueDatagramChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/Limits.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/AbstractKQueueChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/smtp/SmtpUtils.java
* /netty-all-4-1-49-final-sources-jar/io/netty/bootstrap/BootstrapConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/AbstractDnsOptPseudoRrRecord.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/smtp/SmtpRequests.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2WindowUpdateFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/OutOfDirectMemoryError.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/DateFormatter.java

* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketChunkedInput.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameStream.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/LinuxSocket.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/flush/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/ReferenceCountedOpenSslClientContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/frame/server/Http2Server.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/smtp/SmtpResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2SettingsFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/NativeStaticallyReferencedJniMethods.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/RoundRobinDnsAddressResolverGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/bootstrap/ServerBootstrapConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/smtp/SmtpRequestEncoder.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslCertificateException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2DataFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueEventLoop.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/string/LineSeparator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/NonStickyEventExecutorGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/AbstractHttp2StreamFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/WriteBufferWaterMark.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/smtp/DefaultSmtpRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueServerChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/Log4J2LoggerFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsOptPseudoRecord.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/ConstantTimeUtils.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueDomainSocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslKeyMaterialManager.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueServerDomainSocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/DuplexChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/AbstractPooledDerivedByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameStreamVisitor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/InboundHttpToHttp2Adapter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/smtp/SmtpRequest.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueRecvByteAllocatorHandle.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/PromiseNotificationUtil.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/channel/DefaultSelectStrategy.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/NativeLibraryUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/SocketWritableByteChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueEventArray.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/multiplex/server/Http2Server.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/smtp/SmtpContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueDatagramChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/ReferenceCountedOpenSslServerContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/CodecOutputList.java

* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/PemValue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/smtp/SmtpResponseDecoder.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/Native.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/ReferenceCountedOpenSslContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/NoopDnsCache.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/AcceptFilter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/PromiseCombiner.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueChannelOption.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/ErrorsStaticallyReferencedJniMethods.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/ByteBufChecksum.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/AdvancedLeakAwareCompositeByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/util/X509TrustManagerWrapper.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/Log4J2Logger.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/DomainNameMappingBuilder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/PeerCredentials.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueServerSocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameStreamException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsPtrRecord.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelOutboundInvoker.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueDomainSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/IntSupplier.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DefaultDnsCache.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/haproxy/HAProxySSLTLV.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/BsdSocket.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/Java8SslUtils.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsOptEcsRecord.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/LimitsStaticallyReferencedJniMethods.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2HeadersFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/RejectedExecutionHandlers.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ChannelDuplexHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/UnorderedThreadPoolEventExecutor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/PreferHeapByteBufAllocator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueServerSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2PingFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2HeadersFrame.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DefaultDnsPtrRecord.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/smtp/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2GoAwayFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/DelegatingSslContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/AbstractUnpooledSlicedByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/kqueue/KQueueEventLoopGroup.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
* A decoder that splits the received {@link ByteBuf}s dynamically by the
* value of the length field in the message.  It is particularly useful when you
* decode a binary message which has an integer header field that represents the
* length of the message body or the whole message.
*
 <p>
* {@link LengthFieldBasedFrameDecoder} has many configuration parameters so
* that it can decode any message with a length field, which is often seen in
* proprietary client-server protocols. Here are some example that will give
* you the basic idea on which option does what.
*
* <h3>2 bytes length field at offset 0, do not strip header</h3>
*
* The value of the length field in this example is <tt>12 (0x0C)</tt> which
* represents the length of "HELLO, WORLD".  By default, the decoder assumes
* that the length field represents the number of the bytes that follows the
* length field.  Therefore, it can be decoded with the simplistic parameter
* combination.
* <pre>
* <b>lengthFieldOffset</b>   = <b>0</b>
* <b>lengthFieldLength</b>   = <b>2</b>
* lengthAdjustment    = 0
* initialBytesToStrip = 0 (= do not strip header)
*
* BEFORE DECODE (14 bytes)         AFTER DECODE (14 bytes)
* +--------+----------------+      +--------+----------------+
* | Length | Actual Content
 |----->| Length | Actual Content |
* | 0x000C | "HELLO, WORLD" |      | 0x000C | "HELLO, WORLD" |
* +--------+----------------+      +--------+----------------+
* </pre>
*
```

```
* <h3>2 bytes length field at offset 0, strip header</h3>
*
* Because we can get the length of the content by calling
* {@link ByteBuf#readableBytes()}, you might want to strip the length
* field by specifying <tt>initialBytesToStrip</tt>.  In this example, we
* specified <tt>2</tt>, that is same with the length of the length field, to
* strip the first two bytes.
* <pre>
* lengthFieldOffset   = 0
* lengthFieldLength   = 2
* lengthAdjustment    = 0
* <b>initialBytesToStrip</b> = <b>2</b> (= the length of the Length field)
*
* BEFORE DECODE (14 bytes)         AFTER DECODE (12 bytes)
* +--------+----------------+      +----------------+
* | Length | Actual Content |----->| Actual Content |
* | 0x000C | "HELLO, WORLD" |      | "HELLO, WORLD" |
* +--------+----------------+      +----------------+
 * </pre>
*
* <h3>2 bytes length field at offset 0, do not strip header, the length field
*     represents the length of the whole message</h3>
*
* In most cases, the length field represents the length of the message body
* only, as shown in the previous examples.  However, in some protocols, the
* length field represents the length of the whole message, including the
* message header.  In such a case, we specify a non-zero
* <tt>lengthAdjustment</tt>.  Because the length value in this example message
* is always greater than the body length by <tt>2</tt>, we specify <tt>-2</tt>
* as <tt>lengthAdjustment</tt> for compensation.
* <pre>
* lengthFieldOffset   =  0
* lengthFieldLength   =  2
* <b>lengthAdjustment</b>    = <b>-2</b> (= the length of the Length field)
* initialBytesToStrip =  0
*
* BEFORE DECODE (14 bytes)         AFTER DECODE (14 bytes)
* +--------+----------------+      +--------+----------------+
* | Length | Actual Content |----->| Length | Actual
 Content |
* | 0x000E | "HELLO, WORLD" |      | 0x000E | "HELLO, WORLD" |
* +--------+----------------+      +--------+----------------+
* </pre>
*
* <h3>3 bytes length field at the end of 5 bytes header, do not strip header</h3>
*
* The following message is a simple variation of the first example.  An extra
* header value is prepended to the message.  <tt>lengthAdjustment</tt> is zero
```

```
* again because the decoder always takes the length of the prepended data into
* account during frame length calculation.
* <pre>
* <b>lengthFieldOffset</b>   = <b>2</b> (= the length of Header 1)
* <b>lengthFieldLength</b>   = <b>3</b>
* lengthAdjustment    = 0
* initialBytesToStrip = 0
*
* BEFORE DECODE (17 bytes)                  AFTER DECODE (17 bytes)
* +----------+----------+----------------+      +----------+----------+----------------+
* | Header 1 |  Length  | Actual Content |----->| Header 1 |  Length  | Actual Content |
* |  0xCAFE  | 0x00000C | "HELLO, WORLD" |      |
  0xCAFE  | 0x00000C | "HELLO, WORLD" |
* +----------+----------+----------------+      +----------+----------+----------------+
* </pre>
*
* <h3>3 bytes length field at the beginning of 5 bytes header, do not strip header</h3>
*
* This is an advanced example that shows the case where there is an extra
* header between the length field and the message body.  You have to specify a
* positive <tt>lengthAdjustment</tt> so that the decoder counts the extra
* header into the frame length calculation.
* <pre>
* lengthFieldOffset   = 0
* lengthFieldLength   = 3
* <b>lengthAdjustment</b>    = <b>2</b> (= the length of Header 1)
* initialBytesToStrip = 0
*
* BEFORE DECODE (17 bytes)                  AFTER DECODE (17 bytes)
* +----------+----------+----------------+      +----------+----------+----------------+
* |  Length  | Header 1 | Actual Content |----->|  Length  | Header 1 | Actual Content |
* | 0x00000C |  0xCAFE  | "HELLO, WORLD" |      | 0x00000C |  0xCAFE  | "HELLO,
 WORLD" |
* +----------+----------+----------------+      +----------+----------+----------------+
* </pre>
*
* <h3>2 bytes length field at offset 1 in the middle of 4 bytes header,
*     strip the first header field and the length field</h3>
*
* This is a combination of all the examples above.  There are the prepended
* header before the length field and the extra header after the length field.
* The prepended header affects the <tt>lengthFieldOffset</tt> and the extra
* header affects the <tt>lengthAdjustment</tt>.  We also specified a non-zero
* <tt>initialBytesToStrip</tt> to strip the length field and the prepended
* header from the frame.  If you don't want to strip the prepended header, you
* could specify <tt>0</tt> for <tt>initialBytesToSkip</tt>.
* <pre>
* lengthFieldOffset   = 1 (= the length of HDR1)
```

```
* lengthFieldLength   = 2
* <b>lengthAdjustment</b>    = <b>1</b> (= the length of HDR2)
* <b>initialBytesToStrip</b> = <b>3</b> (= the length of HDR1 + LEN)
 *
* BEFORE DECODE (16 bytes)                  AFTER DECODE (13 bytes)
* +------+--------+------+----------------+      +------+----------------+
* | HDR1 | Length | HDR2 | Actual Content |----->| HDR2 | Actual Content |
* | 0xCA | 0x000C | 0xFE | "HELLO, WORLD" |      | 0xFE | "HELLO, WORLD" |
* +------+--------+------+----------------+      +------+----------------+
* </pre>
*
* <h3>2 bytes length field at offset 1 in the middle of 4 bytes header,
*     strip the first header field and the length field, the length field
*     represents the length of the whole message</h3>
*
* Let's give another twist to the previous example.  The only difference from
* the previous example is that the length field represents the length of the
* whole message instead of the message body, just like the third example.
* We have to count the length of HDR1 and Length into <tt>lengthAdjustment</tt>.
* Please note that we don't need to take the length of HDR2 into account
* because
 the length field already includes the whole header length.
* <pre>
* lengthFieldOffset   =  1
* lengthFieldLength   =  2
* <b>lengthAdjustment</b>    = <b>-3</b> (= the length of HDR1 + LEN, negative)
* <b>initialBytesToStrip</b> = <b> 3</b>
*
* BEFORE DECODE (16 bytes)                  AFTER DECODE (13 bytes)
* +------+--------+------+----------------+      +------+----------------+
* | HDR1 | Length | HDR2 | Actual Content |----->| HDR2 | Actual Content |
* | 0xCA | 0x0010 | 0xFE | "HELLO, WORLD" |      | 0xFE | "HELLO, WORLD" |
* +------+--------+------+----------------+      +------+----------------+
* </pre>
* @see LengthFieldPrepender
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/LengthFieldBasedFrameDecoder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
```

*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/*
* Copyright 2014 Twitter, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable
 law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackHuffmanDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackHeaderField.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackHuffmanEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackDynamicTable.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackStaticTable.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the

* License for the specific language governing permissions and limitations
* under the License.
*/
/*
* Written by Doug Lea with assistance from members of JCP JSR-166
* Expert Group and released to the public domain, as explained at
* http://creativecommons.org/publicdomain/zero/1.0/
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/ThreadLocalRandom.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2011 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/nio/NioSctpServerChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/SctpMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/SctpChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/SctpNotificationHandler.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/traffic/AbstractTrafficShapingHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/SctpServerChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/worldclock/WorldClockProtocol.proto
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/DefaultSctpChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/SctpChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/SctpServerChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/sctp/nio/NioSctpChannel.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,

* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/FastThreadLocalThread.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/DefaultChannelHandlerContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/UnsafeHeapSwappedByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/UnsafeDirectSwappedByteBuf.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/CleanerJava6.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerFrameDeflateDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsServerAddresses.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/package-info.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttIdentifierRejectedException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/spdy/client/SpdyClientInitializer.java

* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Lz4Constants.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/StompContentSubframe.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/spdy/server/SpdyOrHttpHandler.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/LzfEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5ServerEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslClientContext.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyFrameCodec.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/spdy/client/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/haproxy/HAProxyMessageDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttMessageIdVariableHeader.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttConnAckVariableHeader.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/traffic/GlobalChannelTrafficCounter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/memcache/binary/MemcacheClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ipfilter/IpSubnetFilterRule.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/rtsp/RtspHeaderValues.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/proxy/ProxyConnectException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/PendingWriteQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/SniHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/ApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/haproxy/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsQueryContext.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketClientExtensionHandshaker.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/websocketx/client/WebSocketClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/server/Http2ServerInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttSubscribeMessage.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2HuffmanStageEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttConnectMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5Message.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2Decoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/AbstractSocksMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/spdy/client/SpdyFrameLogger.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/DefaultLastStompContentSubframe.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Crc32.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/example/http/websocketx/benchmarkserver/WebSocketServerBenchmarkPage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/ThreadDeathWatcher.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlSpace.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/IovArray.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4ServerEncoder.java

* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/Utf8FrameValidator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2SecurityUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4ClientEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollSocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockZlibDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlContent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsNameResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkBaseApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslEngine.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/proxy/Socks5ProxyHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/AsciiString.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/Java7SslParametersUtils.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2BitReader.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/haproxy/HAProxyMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttSubscribePayload.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollEventLoop.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/StompSubframeDecoder.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionData.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollServerSocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/util/FingerprintTrustManagerFactory.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2InboundFrameLogger.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyFrameEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/CertificateVerifier.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/NoopAddressResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/haproxy/HAProxyProxiedProtocol.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerMessageDeflateDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSsl.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/file/FileServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyFrameDecoderDelegate.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttMessageType.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/DomainNameMapping.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpMessageUtil.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerFrameDeflateEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2Constants.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/websocketx/benchmarkserver/WebSocketServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslSessionContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/FastLzFrameDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/haproxy/HAProxyProtocolVersion.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpHeaderValues.java

*
 /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerMessageDeflateEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5ClientEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/spdy/server/SpdyServer.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketServerExtension.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2Encoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2MoveToFrontTable.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ipfilter/IpFilterRuleType.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/proxy/ProxyHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlDocumentEnd.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/json/JsonObjectDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/spdy/server/SpdyServerInitializer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsResolveContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/StompSubframeAggregator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/InternalThreadLocalMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/SimpleNameResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlComment.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/example/http/websocketx/benchmarkserver/WebSocketServerHandler.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/DeflateEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpHeaderNames.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameLogger.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/ipfilter/RuleBasedIpFilter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlElement.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/SupportedCipherSuiteFilter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlNamespace.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2DivSufSort.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/StompSubframe.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/WebSocketServerCompressionHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkAlpnApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketClientExtensionHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/CipherSuiteConverter.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttPublishVariableHeader.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/util/InsecureTrustManagerFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkDefaultApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/DeflateFrameServerExtensionHandshaker.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/LzfDecoder.java

* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtension.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/spdy/client/SpdyClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttConnectVariableHeader.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2BlockCompressor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/AddressResolverGroup.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2Rand.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/extensions/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/Mapping.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlProcessingInstruction.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollTcpInfo.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslX509Certificate.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ipfilter/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4Message.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ipfilter/IpFilterRule.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkSslContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/ServerCookieEncoder.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Lz4FrameEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/ApplicationProtocolUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/StompConstants.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttConnAckMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttSubAckMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2BlockDecompressor.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttConnectReturnCode.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/JettyNpnSslEngine.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/haproxy/HAProxyConstants.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlElementStart.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttUnsubscribePayload.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttUnsubscribeMessage.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/WebSocketClientCompressionHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/rtsp/RtspHeaderNames.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlElementEnd.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketServerExtensionHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslEngineMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkSslEngine.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlCharacters.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/DecoderResultProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Lz4FrameDecoder.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/example/http/websocketx/benchmarkserver/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/FastThreadLocal.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/PromiseAggregator.java

* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2BitWriter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockRawDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/NameResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/memcache/binary/MemcacheClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5CommandRequestDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/SslUtils.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/StompFrame.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerMessageDeflateClientExtensionHandshaker.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslServerSessionContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/LzmaFrameEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttFixedHeader.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5InitialRequestDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlAttribute.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/SnappyFramedEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkSslServerContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttEncoder.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/StompSubframeEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/NativeDatagramPacketArray.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5InitialResponseDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2OutboundFrameLogger.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpChunkedInput.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/extensions/compression/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlEntityReference.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2HuffmanStageDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslSessionStats.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkSslClientContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttPubAckMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/proxy/Socks4ProxyHandler.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/DeflateDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/server/Http2Server.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslNpnApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/FastLzFrameEncoder.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerMessageDeflateServerExtensionHandshaker.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/PromiseNotifier.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/AsciiHeadersEncoder.java
*

/netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/CipherSuiteFilter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/MessageAggregationException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlCdata.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/AbstractEventLoop.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/spdy/server/SpdyServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthResponseDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlDocumentStart.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttTopicSubscription.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/stomp/StompClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5CommandResponseDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/DefaultStompHeaders.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsAddressResolverGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttConnectPayload.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ipfilter/AbstractRemoteAddressFilter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/SslProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollDatagramChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslServerContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/NoopAddressResolverGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttUnsubAckMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyFrameDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/SslContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/StompCommand.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/LastStompContentSubframe.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketServerExtensionHandshaker.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/proxy/HttpProxyHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/json/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2MTFAndRLE2StageEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/IntegerHolder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/proxy/ProxyConnectionEvent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslDefaultApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttMessageFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/haproxy/HAProxyCommand.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ReflectiveChannelFactory.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/util/BouncyCastleSelfSignedCertGenerator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttCodecUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/DefaultStompContentSubframe.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/ApplicationProtocolConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttSubAckPayload.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/stomp/StompClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/server/HelloWorldHttp1Handler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/AbstractSocks4Message.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/UnpaddedInternalThreadLocalMap.java
* /netty-all-4-1-49-final-sources-

jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketClientExtension.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/StompHeaders.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/ResourceLeakHint.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/AbstractEpollChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/DefaultStompHeadersSubframe.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/example/http/websocketx/benchmarkserver/WebSocketServerInitializer.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/UnixChannelOption.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/Epoll.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/IdentityCipherSuiteFilter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/embedded/EmbeddedChannelId.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttUnacceptableProtocolVersionException.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/haproxy/HAProxyProtocolException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/util/SimpleTrustManagerFactory.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/DeflateFrameClientExtensionHandshaker.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/util/ThreadLocalInsecureRandom.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/PemReader.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/proxy/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlDTD.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/util/OpenJdkSelfSignedCertGenerator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/JettyAlpnSslEngine.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2HuffmanAllocator.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpHeadersEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/NativeLibraryLoader.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/spdy/SpdyProtocolException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ipfilter/UniqueIpFilter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/DefaultStompFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/spdy/client/HttpResponseClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/stomp/StompHeadersSubframe.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollChannelOption.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttVersion.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttPublishMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/spdy/server/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/AbstractSocks5Message.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/FastLz.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthRequestDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/ClientCookieEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollEventLoopGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/spdy/client/SpdyClientStreamIdHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkNpnApplicationProtocolNegotiator.java

* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpStatusClass.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/SnappyFramedDecoder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2EmptyDataFrameConnectionDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2SettingsReceivedConsumer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2EmptyDataFrameListener.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ControlFrameLimitEncoder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
* Copyright (c) 2004-2011 QOS.ch
* All rights reserved.
*
* Permission is hereby granted, free of charge, to any person obtaining

* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without
limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be
* included in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
* NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
* LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
* OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
* WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/FormattingTuple.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/MessageFormatter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version
* 2.0 (the "License"); you may not use this file except in compliance with the
* License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/flow/FlowControlHandler.java
No license file was found, but licenses were detected in source scan.

/*

* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HttpToHttp2ConnectionHandlerBuilder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/cookie/ClientCookieEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/ApplicationProtocolAccessor.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpScheme.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/HeadersUtils.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/ShuffledDnsServerAddressStream.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/AddressResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsSection.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/HostsFileParser.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/SingletonDnsServerAddresses.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollMode.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsServerAddressStream.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/protobuf/ProtobufVarint32LengthFieldPrepender.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/AbstractDnsRecord.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/DefaultHostsFileEntriesResolver.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DefaultDnsRawRecord.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/ProtocolDetectionState.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslSessionTicketKey.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/rtsp/RtspDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/SocksPortUnificationServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/InetNameResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/HeapByteBufUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5AddressDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollDomainSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/cookie/CookieEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/cookie/ServerCookieEncoder.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/channel/pool/AbstractChannelPoolMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/cookie/CookieHeaderNames.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/FileDescriptor.java

* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollServerChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/DefaultMaxBytesRecvByteBufAllocator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/protobuf/ProtobufVarint32FrameDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/ProtocolDetectionResult.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/DefaultAddressResolverGroup.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/SequentialDnsServerAddressStream.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsRecordEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/tiles/Http2OrHttpHandler.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/channel/pool/ChannelPoolHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/UnixChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/helloworld/server/HelloWorldHttp2HandlerBuilder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/cookie/CookieUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/cookie/ClientCookieDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/tiles/Launcher.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/SslContextBuilder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/pool/ChannelPool.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/pool/AbstractChannelPoolHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollRecvByteAllocatorStreamingHandle.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpExpectationFailedEvent.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/protobuf/ProtobufEncoderNano.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/DefaultMaxMessagesRecvByteBufAllocator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/cookie/ServerCookieDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/UnpooledUnsafeHeapByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsRecordType.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/TcpMd5Util.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/tiles/HttpServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/UnpooledSlicedByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DatagramDnsQuery.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/UnsafeByteBufUtil.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/ThreadProperties.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/tiles/ImageCache.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsResponseCode.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/DefaultNameResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsMessageUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsNameResolverException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/ClientAuth.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/pool/ChannelHealthChecker.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/UnpooledDuplicatedByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/AbstractEpollStreamChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/cookie/DefaultCookie.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/tiles/Html.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/ServerDomainSocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DatagramDnsResponseEncoder.java

* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/protobuf/ProtobufDecoderNano.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PoolSubpageMetric.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/AbstractUnsafeSwappedByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/sctp/multihoming/SctpMultiHomingEchoClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsQuery.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollEventArray.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/PriorityQueueNode.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PooledUnsafeHeapByteBuf.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/concurrent/AbstractScheduledEventExecutor.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsNameResolverBuilder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DefaultDnsQuestion.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DatagramDnsResponse.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/AbstractHttp2ConnectionHandlerBuilder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DatagramDnsResponseDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DefaultDnsRecordEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/MaxMessagesRecvByteBufAllocator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/tiles/FallbackRequestHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/protobuf/ProtobufDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/cookie/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/HashingStrategy.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/cookie/Cookie.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/DomainSocketAddress.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsRawRecord.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/DomainSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/CombinedHttpHeaders.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/InetSocketAddressResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/tiles/Http1RequestHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/AbstractEpollServerChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/pool/SimpleChannelPool.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/MaxBytesRecvByteBufAllocator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollServerDomainSocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/EmptyHttpHeaders.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/DomainSocketReadMode.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DefaultDnsQuery.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PoolArenaMetric.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsQuestion.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/protobuf/ProtobufEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/DomainSocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/HostsFileEntriesResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/Errors.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/rtsp/RtspEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/pool/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/CookieUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DefaultDnsResponse.java
*

/netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/ApplicationProtocolNames.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsOpCode.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/AsyncMapping.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DefaultDnsRecordDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslJavaxX509Certificate.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/pool/ChannelPoolMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/tiles/Http2Server.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/AbstractAddressResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/AbstractDnsMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/LongCounter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DatagramDnsQueryDecoder.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/DatagramSocketAddress.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ConnectionHandlerBuilder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsQueryContextManager.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/RotationalDnsServerAddresses.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollDomainSocketChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PoolChunkMetric.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/NativeInetAddress.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/DomainMappingBuilder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DatagramDnsQueryEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollRecvByteAllocatorHandle.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PoolChunkListMetric.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/channel/pool/FixedChannelPool.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/ApplicationProtocolNegotiationHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/sctp/multihoming/SctpMultiHomingEchoServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/Socket.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/DefaultPriorityQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5AddressEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsRecordDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsRecord.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DefaultDnsServerAddresses.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http2/tiles/Http2RequestHandler.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/resolver/CompositeNameResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/CharSequenceMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/cookie/CookieDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsMessage.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/UnsupportedValueConverter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 The Netty Project
*

* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/svm/CleanerJava6Substitution.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshaker00.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2MultiplexHandler.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/example/mqtt/heartBeat/MqttHeartBeatBroker.java
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/CertificateVerifierTask.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/CloseWebSocketFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/svm/UnsafeRefArrayAccessSubstitution.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/mqtt/heartBeat/MqttHeartBeatClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsResponseDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/macos/DnsResolver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/ThreadExecutorMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/util/X509KeyManagerWrapper.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/macos/MacOSDnsServerAddressStreamProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsCodecUtil.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/SSLTask.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelHandlerMask.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/SslMasterKeyHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/address/DynamicAddressConnectHandler.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/CorruptedWebSocketFrameException.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshakerFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/SSLPrivateKeyMethodDecryptTask.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/address/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocket00FrameDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/MaxCapacityQueue.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Lz4XXHash32.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/Hidden.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/EventLoopTaskQueueFactory.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionFilter.java

* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/KeyManagerFactoryWrapper.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/TcpDnsQueryEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/PseudoRandomFunction.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshaker13.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/svm/PlatformDependentSubstitution.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/PreferredAddressTypeComparator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/util/SimpleKeyManagerFactory.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/ObjectPool.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2SettingsAckFrame.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionFilterProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/SSLPrivateKeyMethodSignTask.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketServerProtocolConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/DnsQueryEncoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/ReferenceCountUpdater.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DatagramDnsQueryContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketClientProtocolConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshaker.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/TcpDnsQueryContext.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslPrivateKeyMethod.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2SettingsAckFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/macos/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/mqtt/heartBeat/MqttHeartBeatBrokerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/AbstractHttp2StreamChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/TrustManagerFactoryWrapper.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/mqtt/heartBeat/MqttHeartBeatClient.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/svm/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketDecoderConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshaker08.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/dns/TcpDnsResponseDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ExtendedClosedChannelException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshaker07.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/handler/codec/http/websocketx/WebSocketServerProtocolHandshakeHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/SSLPrivateKeyMethodTask.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketCloseStatus.java
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/SSLPrivateKeyMethod.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketServerProtocolHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/CertificateCallbackTask.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/svm/PlatformDependent0Substitution.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 The Netty Project
*

* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
// (BSD License: http://www.opensource.org/licenses/bsd-license)
// All rights reserved.
// Redistribution and use in source and binary forms, with or
// * Redistributions of source code must retain the above
// copyright notice, this list of conditions and the
// following disclaimer.
// * Redistributions
 in binary form must reproduce the above
// following disclaimer in the documentation and/or other
// * Neither the name of the Webbit nor the names of

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocket08FrameDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocket07FrameDecoder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocket13FrameDecoder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
    * Set the {@code TCP_MD5SIG} option on the socket. See {@code linux/tcp.h} for more details.
    * Keys can only be set on, not read to prevent a potential leak, as they are confidential.
    * Allowing them being read would mean anyone with access to the channel could get them.

*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollServerSocketChannelConfig.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version
* 2.0 (the "License"); you may not use this file except in compliance with the
* License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/cors/CorsHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/cors/OkResponseHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/cors/CorsConfig.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version
* 2.0 (the "License"); you may not use this file except in compliance with the
* License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/example/ocsp/OcspUtils.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/ocsp/OcspClientExample.java

* /netty-all-4-1-49-final-sources-jar/io/netty/example/ocsp/Digester.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/ocsp/OcspServerExample.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/example/ocsp/OcspRequestBuilder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
//The MIT License
//Permission is hereby granted, free of charge, to any person obtaining a copy
//of this software and associated documentation files (the "Software"), to deal
//to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
//furnished to do so, subject to the following
conditions:
//The above copyright notice and this permission notice shall be included in
//all copies or substantial portions of the Software.

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/example/http/websocketx/client/WebSocketClientHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.

```
*/
/**
* Handles an I/O event or intercepts an I/O operation, and forwards it to its next handler in
* its {@link ChannelPipeline}.
*
* <h3>Sub-types</h3>
* <p>
* {@link ChannelHandler} itself does not provide many methods, but you usually have to implement one of its
subtypes:
* <ul>
* <li>{@link
 ChannelInboundHandler} to handle inbound I/O events, and</li>
* <li>{@link ChannelOutboundHandler} to handle outbound I/O operations.</li>
* </ul>
* </p>
* <p>
* Alternatively, the following adapter classes are provided for your convenience:
* <ul>
* <li>{@link ChannelInboundHandlerAdapter} to handle inbound I/O events,</li>
* <li>{@link ChannelOutboundHandlerAdapter} to handle outbound I/O operations, and</li>
* <li>{@link ChannelDuplexHandler} to handle both inbound and outbound events</li>
* </ul>
* </p>
* <p>
* For more information, please refer to the documentation of each subtype.
* </p>
*
* <h3>The context object</h3>
* <p>
* A {@link ChannelHandler} is provided with a {@link ChannelHandlerContext}
* object.  A {@link ChannelHandler} is supposed to interact with the
* {@link ChannelPipeline} it belongs to via a context object.  Using the
* context object, the {@link ChannelHandler} can pass events upstream or
* downstream, modify the pipeline dynamically,
 or store the information
* (using {@link AttributeKey}s) which is specific to the handler.
*
* <h3>State management</h3>
*
* A {@link ChannelHandler} often needs to store some stateful information.
* The simplest and recommended approach is to use member variables:
* <pre>
* public interface Message {
*     // your methods here
* }
*
* public class DataServerHandler extends {@link SimpleChannelInboundHandler}&lt;Message&gt; {
*
```

```
*     <b>private boolean loggedIn;</b>
*
*     {@code @Override}
*     public void channelRead0({@link ChannelHandlerContext} ctx, Message message) {
*         if (message instanceof LoginMessage) {
*             authenticate((LoginMessage) message);
*             <b>loggedIn = true;</b>
*         } else (message instanceof GetDataMessage) {
*             if (<b>loggedIn</b>) {
*                 ctx.writeAndFlush(fetchSecret((GetDataMessage) message));
*             } else {
*                 fail();
*             }
*         }
 *     }
*     ...
* }
* </pre>
* Because the handler instance has a state variable which is dedicated to
* one connection, you have to create a new handler instance for each new
* channel to avoid a race condition where a unauthenticated client can get
* the confidential information:
* <pre>
* // Create a new handler instance per channel.
* // See {@link ChannelInitializer#initChannel(Channel)}.
* public class DataServerInitializer extends {@link ChannelInitializer}&lt;{@link Channel}&gt; {
*     {@code @Override}
*     public void initChannel({@link Channel} channel) {
*         channel.pipeline().addLast("handler", <b>new DataServerHandler()</b>);
*     }
* }
*
* </pre>
*
* <h4>Using {@link AttributeKey}s</h4>
*
* Although it's recommended to use member variables to store the state of a
* handler, for some reason you might not want to create many handler instances.
* In such a case, you can use {@link AttributeKey}s which is provided by
* {@link ChannelHandlerContext}:
 * <pre>
* public interface Message {
*     // your methods here
* }
*
* {@code @Sharable}
* public class DataServerHandler extends {@link SimpleChannelInboundHandler}&lt;Message&gt; {
*     private final {@link AttributeKey}&lt;{@link Boolean}&gt; auth =
```

```
*          {@link AttributeKey#valueOf(String) AttributeKey.valueOf("auth")};
*
*     {@code @Override}
*     public void channelRead({@link ChannelHandlerContext} ctx, Message message) {
*         {@link Attribute}&lt;{@link Boolean}&gt; attr = ctx.attr(auth);
*         if (message instanceof LoginMessage) {
*             authenticate((LoginMessage) o);
*             <b>attr.set(true)</b>;
*         } else (message instanceof GetDataMessage) {
*             if (<b>Boolean.TRUE.equals(attr.get())</b>) {
*                 ctx.writeAndFlush(fetchSecret((GetDataMessage) o));
*             } else {
*                 fail();
*             }
*         }
*     }
*     ...
* }
* </pre>
* Now that the state
 of the handler is attached to the {@link ChannelHandlerContext}, you can add the
* same handler instance to different pipelines:
* <pre>
* public class DataServerInitializer extends {@link ChannelInitializer}&lt;{@link Channel}&gt; {
*
*     private static final DataServerHandler <b>SHARED</b> = new DataServerHandler();
*
*     {@code @Override}
*     public void initChannel({@link Channel} channel) {
*         channel.pipeline().addLast("handler", <b>SHARED</b>);
*     }
* }
* </pre>
*
*
* <h4>The {@code @Sharable} annotation</h4>
* <p>
* In the example above which used an {@link AttributeKey},
* you might have noticed the {@code @Sharable} annotation.
* <p>
* If a {@link ChannelHandler} is annotated with the {@code @Sharable}
* annotation, it means you can create an instance of the handler just once and
* add it to one or more {@link ChannelPipeline}s multiple times without
* a race condition.
* <p>
* If this annotation is not specified, you have to create
 a new handler
* instance every time you add it to a pipeline because it has unshared state
```

* such as member variables.
* <p>
* This annotation is provided for documentation purpose, just like
* the JCIP annotations.
*
* <h3>Additional resources worth reading</h3>
* <p>
* Please refer to the {@link ChannelHandler}, and
* {@link ChannelPipeline} to find out more about inbound and outbound operations,
* what fundamental differences they have, how they flow in a pipeline, and how to handle
* the operation in your application.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/ChannelHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
   * Set the {@code TCP_MD5SIG} option on the socket. See {@code linux/tcp.h} for more details.
   * Keys can only be set on, not read to prevent a potential leak, as they are confidential.
   * Allowing them being read would mean anyone with access to the channel could get them.

  */
/**
   * Set the {@code TCP_QUICKACK} option on the socket. See <a
href="http://linux.die.net/man/7/tcp">TCP_QUICKACK
   * for more details.
   */

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollSocketChannelConfig.java
No license file was found, but licenses were detected in source scan.

/*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/MpscAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/MpmcUnboundedXaddArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/SpscUnboundedArrayQueue.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/util/InternalAPI.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/maps/NonBlockingSetInt.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/SupportsIterator.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/BaseSpscLinkedAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/BaseMpscLinkedArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/BaseLinkedAtomicQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/LinkedQueueAtomicNode.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/maps/ConcurrentAutoTable.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/BaseSpscLinkedArrayQueue.java
*
 /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/SpscUnboundedAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/MpscChunkedArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/maps/NonBlockingIdentityHashMap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/MpscUnboundedAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/SpscLinkedQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/IndexedQueueSizeUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/MpscLinkedQueue.java
* /netty-all-4-1-49-final-sources-

jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/BaseMpscLinkedAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/SpscChunkedAtomicArrayQueue.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/spec/ConcurrentQueueSpec.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/MpscGrowableAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/util/UnsafeRefArrayAccess.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/util/internal/shaded/org/jctools/queues/ConcurrentCircularArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/QueueFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/maps/AbstractEntry.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/spec/Ordering.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/MpscCompoundQueue.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/MpscUnboundedXaddChunk.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/util/internal/shaded/org/jctools/queues/MpscUnboundedArrayQueue.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/SequencedAtomicReferenceArrayQueue.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/SpscLinkedAtomicQueue.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/util/internal/shaded/org/jctools/queues/MpscBlockingConsumerArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/MessagePassingQueueUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/util/Pow2.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/maps/NonBlockingHashMapLong.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/util/UnsafeLongArrayAccess.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/maps/NonBlockingHashSet.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/SpmcArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/SpscGrowableArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/MpmcArrayQueue.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/util/internal/shaded/org/jctools/queues/ConcurrentSequencedCircularArrayQueue.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/util/internal/shaded/org/jctools/queues/MpscUnboundedXaddArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/util/UnsafeJvmInfo.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/maps/NonBlockingHashMap.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/SpmcAtomicArrayQueue.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/MpscArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/util/RangeUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/SpscArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/util/UnsafeAccess.java
* /netty-all-4-1-49-final-sources-
jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/SpscGrowableAtomicArrayQueue.java

* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/MpmcAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/MpscGrowableArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/MpscChunkedAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/spec/Preference.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/BaseLinkedQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/AtomicQueueFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/MessagePassingQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/SpscAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/AtomicReferenceArrayQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/LinkedQueueNode.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/SpscChunkedArrayQueue.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/MpmcUnboundedXaddChunk.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/util/PortableJvmInfo.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/MpscLinkedAtomicQueue.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/ByteBufAllocatorMetricProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/TraceDnsQueryLifeCycleObserverFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/PriorityQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/bootstrap/FailedChannel.java
*

/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/ReadOnlyHttpHeaders.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/LongAdderCounter.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/ChannelOutputShutdownException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/uptime/UptimeServerHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/MultiDnsServerAddressStreamProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/ocsp/OcspClientHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/ocsp/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/Conscrypt.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/NoopDnsQueryLifecycleObserver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2UnknownFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/UncheckedBooleanSupplier.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/TraceDnsQueryLifecycleObserver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/BiDnsQueryLifecycleObserver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/oio/OioDatagramChannelConfig.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/ObjectCleaner.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/HostsFileEntries.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/internal/ChannelUtils.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/SniCompletionEvent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2StreamChannel.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/ByteBufAllocatorMetric.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/ConscryptAlpnSslEngine.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/ChannelInputShutdownReadComplete.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameCodecBuilder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/OptionalSslHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/HttpServerExpectContinueHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2StreamChannelBootstrap.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/NoopDnsQueryLifecycleObserverFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/ReflectionUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/BiDnsQueryLifecycleObserverFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/EmptyPriorityQueue.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsServerAddressStreamProviders.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsServerAddressStreamProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/oio/DefaultOioDatagramChannelConfig.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http/websocketx/WebSocketScheme.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/PendingBytesTracker.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/internal/package-info.java
* /netty-all-4-1-49-final-sources-jar/io/netty/buffer/PooledByteBufAllocatorMetric.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DefaultDnsServerAddressStreamProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsQueryLifecycleObserver.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/SuppressForbidden.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkAlpnSslUtils.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/mqtt/MqttMessageBuilders.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/socket/ChannelOutputShutdownEvent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/SslCompletionEvent.java
*

/netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/UnixResolverDnsServerAddressStreamProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameStreamEvent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/SslClientHelloHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/SslCloseCompletionEvent.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/SequentialDnsServerAddressStreamProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/ResolvedAddressTypes.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsCacheEntry.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2StreamChannelId.java
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/SniHostNameMatcher.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsNameResolverTimeoutException.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/UniSequentialDnsServerAddressStreamProvider.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/channel/unix/UnixChannelUtil.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2MultiplexCodecBuilder.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/DelegatingChannelPromiseNotifier.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/AbstractSniHandler.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/DnsQueryLifecycleObserverFactory.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/NettyRuntime.java
* /netty-all-4-1-49-final-sources-jar/io/netty/resolver/dns/SingletonDnsServerAddressStreamProvider.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2UnknownFrame.java
* /netty-all-4-1-49-final-sources-jar/io/netty/example/uptime/UptimeServer.java
* /netty-all-4-1-49-final-sources-jar/io/netty/channel/nio/SelectedSelectionKeySetSelector.java
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/CleartextHttp2ServerUpgradeHandler.java
*
/netty-all-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkAlpnSslEngine.java
* /netty-all-4-1-49-final-sources-jar/io/netty/util/internal/logging/LocationAwareSlf4JLogger.java
* /netty-all-4-1-49-final-sources-jar/io/netty/internal/tcnative/NativeStaticallyReferencedJniMethods.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/
// https://tools.ietf.org/html/rfc7540#section-8.1.2.2 makes a special exception for TE

Found in path(s):
* /netty-all-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HttpConversionUtil.java

1.228 lodash.restparam 3.6.1

1.228.1 Available under license :

No license file was found, but licenses were detected in source scan.

/**
* lodash 3.6.1 (Custom Build) <https://lodash.com/>
* Build: `lodash modern modularize exports="npm" -o ./`
* Copyright 2012-2015 The Dojo Foundation <http://dojofoundation.org/>
* Based on Underscore.js 1.8.3 <http://underscorejs.org/LICENSE>
* Copyright 2009-2015 Jeremy Ashkenas, DocumentCloud and Investigative Reporters & Editors
* Available under MIT license <https://lodash.com/license>
*/

Found in path(s):
* /fis-components-lodash-restparam-3-6-1-0-g4b84b80-tar-gz/fis-components-lodash.restparam-3692f6f/index.js

1.229 lodash._getnative 3.9.1

1.229.1 Available under license :

No license file was found, but licenses were detected in source scan.

/**
* lodash 3.9.1 (Custom Build) <https://lodash.com/>
* Build: `lodash modern modularize exports="npm" -o ./`
* Copyright 2012-2015 The Dojo Foundation <http://dojofoundation.org/>
* Based on Underscore.js 1.8.3 <http://underscorejs.org/LICENSE>
* Copyright 2009-2015 Jeremy Ashkenas, DocumentCloud and Investigative Reporters & Editors
* Available under MIT license <https://lodash.com/license>
*/

Found in path(s):
* /fis-components-lodash-getnative-3-9-1-0-g99a6587-tar-gz/fis-components-lodash._getnative-20042e8/index.js

1.230 lodash-root 3.0.1

1.230.1 Available under license :

The MIT License (MIT)

Copyright 2012-2016 The Dojo Foundation <http://dojofoundation.org/>
Based on Underscore.js, copyright 2009-2016 Jeremy Ashkenas,
DocumentCloud and Investigative Reporters & Editors <http://underscorejs.org/>

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO
EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.231 lodash.isplainobject 4.0.6

1.231.1 Available under license :

Copyright jQuery Foundation and other contributors <https://jquery.org/>

Based on Underscore.js, copyright Jeremy Ashkenas,
DocumentCloud and Investigative Reporters & Editors <http://underscorejs.org/>

This software consists of voluntary contributions made by many
individuals. For exact contribution history, see the revision history
available at https://github.com/lodash/lodash

The following license applies to all parts of this software except as
documented below:

====

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or

substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

====

Copyright and related rights for sample code are waived via CC0. Sample code is defined as all source code displayed within the prose of the documentation.

CC0: http://creativecommons.org/publicdomain/zero/1.0/

====

Files located in the node_modules and vendor directories are externally maintained libraries used by this software which have their own licenses; we recommend you read them, as their terms may differ from the terms above.
MIT

1.232 lodash.keys 3.1.2

1.232.1 Available under license :

No license file was found, but licenses were detected in source scan.

lodash v4.5.1

The [lodash](https://lodash.com/) library exported as a [UMD](https://github.com/umdjs/umd) module.

Generated using [lodash-cli](https://www.npmjs.com/package/lodash-cli):
```bash
$ npm run build
$ lodash -o ./dist/lodash.js
$ lodash core -o ./dist/lodash.core.js
```

Community

[![Gitter](https://badges.gitter.im/lodash/lodash.svg)](https://gitter.im/lodash/lodash)

Documentation

* [API Documentation](https://lodash.com/docs)
* [FP Guide](https://github.com/lodash/lodash/wiki/FP-Guide)

Download

Lodash is released under the [MIT license](https://raw.githubusercontent.com/lodash/lodash/4.5.1/LICENSE) & supports [modern environments](#support).
Review the [build differences](https://github.com/lodash/lodash/wiki/build-differences) & pick one thatâ€™s right for you.

* [Core build](https://raw.githubusercontent.com/lodash/lodash/4.5.1/dist/lodash.core.js) ([~4 kB gzipped](https://raw.githubusercontent.com/lodash/lodash/4.5.1/dist/lodash.core.min.js))
* [Full build](https://raw.githubusercontent.com/lodash/lodash/4.5.1/dist/lodash.js) ([~21 kB gzipped](https://raw.githubusercontent.com/lodash/lodash/4.5.1/dist/lodash.min.js))
* [CDN copies](https://www.jsdelivr.com/projects/lodash)

Why Lodash?

Lodash makes JavaScript easier by taking the hassle out of working with arrays,
numbers, objects, strings, etc. Lodashâ€™s modular methods are great for:

* Iterating arrays, objects, & strings
* Manipulating & testing values
* Creating composite functions

Module Formats

Lodash is available in a [variety of builds](https://lodash.com/custom-builds) & module formats.

* [lodash](https://www.npmjs.com/package/lodash) & [per method packages](https://www.npmjs.com/browse/keyword/lodash-modularized)
* [lodash-amd](https://www.npmjs.com/package/lodash-amd)
* [lodash-es](https://www.npmjs.com/package/lodash-es) & [babel-plugin-lodash](https://www.npmjs.com/package/babel-plugin-lodash)
* [lodash/fp](https://github.com/lodash/lodash/tree/4.5.1-npm/fp)

Further Reading

* [Contributing](https://github.com/lodash/lodash/blob/4.5.1/.github/CONTRIBUTING.md)
* [Release Notes](https://github.com/lodash/lodash/releases/tag/4.0.0)
* [Wiki (Changelog, Roadmap, etc.)](https://github.com/lodash/lodash/wiki)

Found in path(s):
* /fis-components-lodash-keys-3-1-2-0-gc47407a-tar-gz/fis-components-lodash.keys-9efd785/README.md
No license file was found, but licenses were detected in source scan.

/**

```
* lodash 3.1.2 (Custom Build) <https://lodash.com/>
* Build: `lodash modern modularize exports="npm" -o ./`
* Copyright 2012-2015 The Dojo Foundation <http://dojofoundation.org/>
* Based on Underscore.js 1.8.3 <http://underscorejs.org/LICENSE>
* Copyright 2009-2015 Jeremy Ashkenas, DocumentCloud and Investigative Reporters & Editors
* Available under MIT license <https://lodash.com/license>
*/
/**
* Creates an array of the own enumerable property names of `object`.
*
* **Note:** Non-object values are coerced to objects. See the
* [ES spec](http://ecma-international.org/ecma-262/6.0/#sec-object.keys)
* for more details.
*
* @static
* @memberOf _
* @category Object
* @param {Object} object The object to query.
* @returns {Array} Returns the array of property names.
* @example
*
* function Foo() {
*   this.a = 1;
*   this.b = 2;
* }
*
* Foo.prototype.c = 3;
*
* _.keys(new Foo);
* // => ['a',
 'b'] (iteration order is not guaranteed)
*
* _.keys('hi');
* // => ['0', '1']
*/
```

Found in path(s):
* /fis-components-lodash-keys-3-1-2-0-gc47407a-tar-gz/fis-components-lodash.keys-9efd785/index.js

1.233 lodash.isarguments 3.1.0

1.233.1 Available under license :

```
Copyright jQuery Foundation and other contributors <https://jquery.org/>

Based on Underscore.js, copyright Jeremy Ashkenas,
DocumentCloud and Investigative Reporters & Editors <http://underscorejs.org/>
```

This software consists of voluntary contributions made by many
individuals. For exact contribution history, see the revision history
available at https://github.com/lodash/lodash

The following license applies to all parts of this software except as
documented below:

====

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or
 substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

====

Copyright and related rights for sample code are waived via CC0. Sample
code is defined as all source code displayed within the prose of the
documentation.

CC0: http://creativecommons.org/publicdomain/zero/1.0/

====

Files located in the node_modules and vendor directories are externally
maintained libraries used by this software which have their own
licenses; we recommend you read them, as their terms may differ from the
terms above.
MIT

1.234 lodash-escape 3.2.0

1.234.1 Available under license :

MIT
Copyright 2012-2016 The Dojo Foundation <http://dojofoundation.org/>
Based on Underscore.js, copyright 2009-2016 Jeremy Ashkenas,
DocumentCloud and Investigative Reporters & Editors <http://underscorejs.org/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS
 OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.235 lodash._isiterateecall 3.0.9

1.235.1 Available under license :

No license file was found, but licenses were detected in source scan.

/**
* lodash 3.0.9 (Custom Build) <https://lodash.com/>
* Build: `lodash modern modularize exports="npm" -o ./`
* Copyright 2012-2015 The Dojo Foundation <http://dojofoundation.org/>
* Based on Underscore.js 1.8.3 <http://underscorejs.org/LICENSE>
* Copyright 2009-2015 Jeremy Ashkenas, DocumentCloud and Investigative Reporters & Editors
* Available under MIT license <https://lodash.com/license>
*/

Found in path(s):
* /fis-components-lodash-isiterateecall-3-0-9-0-g7360657-tar-gz/fis-components-lodash._isiterateecall-7f1d9ce/index.js

1.236 lodash-templatesettings 3.1.1

1.236.1 Available under license :

MIT
Copyright 2012-2016 The Dojo Foundation <http://dojofoundation.org/>
Based on Underscore.js, copyright 2009-2016 Jeremy Ashkenas,
DocumentCloud and Investigative Reporters & Editors <http://underscorejs.org/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS
OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.237 lodash-basevalues 3.0.0

1.237.1 Available under license :

Copyright 2012-2015 The Dojo Foundation <http://dojofoundation.org/>
Based on Underscore.js 1.7.0, copyright 2009-2015 Jeremy Ashkenas,
DocumentCloud and Investigative Reporters & Editors <http://underscorejs.org/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.238 lodash.isarray 3.0.4

1.238.1 Available under license :

No license file was found, but licenses were detected in source scan.

/**
* lodash 3.0.4 (Custom Build) <https://lodash.com/>
* Build: `lodash modern modularize exports="npm" -o ./`
* Copyright 2012-2015 The Dojo Foundation <http://dojofoundation.org/>
* Based on Underscore.js 1.8.3 <http://underscorejs.org/LICENSE>
* Copyright 2009-2015 Jeremy Ashkenas, DocumentCloud and Investigative Reporters & Editors
* Available under MIT license <https://lodash.com/license>
*/

Found in path(s):
* /fis-components-lodash-isarray-3-0-4-0-gbfe7f4f-tar-gz/fis-components-lodash.isarray-e18427d/index.js

1.239 lodash-template 3.6.2

1.239.1 Available under license :

MIT
Copyright 2012-2015 The Dojo Foundation <http://dojofoundation.org/>
Based on Underscore.js, copyright 2009-2015 Jeremy Ashkenas,
DocumentCloud and Investigative Reporters & Editors <http://underscorejs.org/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS
OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.240 lodash-reescape 3.0.0

1.240.1 Available under license :

Copyright 2012-2015 The Dojo Foundation <http://dojofoundation.org/>
Based on Underscore.js 1.7.0, copyright 2009-2015 Jeremy Ashkenas,
DocumentCloud and Investigative Reporters & Editors <http://underscorejs.org/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.241 lodash-basetostring 3.0.1

1.241.1 Available under license :

Copyright 2012-2015 The Dojo Foundation <http://dojofoundation.org/>
Based on Underscore.js, copyright 2009-2015 Jeremy Ashkenas,
DocumentCloud and Investigative Reporters & Editors <http://underscorejs.org/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including

without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS
OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.242 lodash._basecopy 3.0.1

1.242.1 Available under license :

No license file was found, but licenses were detected in source scan.

/**
* lodash 3.0.1 (Custom Build) <https://lodash.com/>
* Build: `lodash modern modularize exports="npm" -o ./`
* Copyright 2012-2015 The Dojo Foundation <http://dojofoundation.org/>
* Based on Underscore.js 1.8.3 <http://underscorejs.org/LICENSE>
* Copyright 2009-2015 Jeremy Ashkenas, DocumentCloud and Investigative Reporters & Editors
* Available under MIT license <https://lodash.com/license>
*/

Found in path(s):
* /fis-components-lodash-basecopy-3-0-1-0-gf3b51bf-tar-gz/fis-components-lodash._basecopy-8843e24/index.js

1.243 lodash-reevaluate 3.0.0

1.243.1 Available under license :

Copyright 2012-2015 The Dojo Foundation <http://dojofoundation.org/>
Based on Underscore.js 1.7.0, copyright 2009-2015 Jeremy Ashkenas,
DocumentCloud and Investigative Reporters & Editors <http://underscorejs.org/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,

distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.244 lodash-reinterpolate 3.0.0

1.244.1 Available under license :

Copyright 2012-2015 The Dojo Foundation <http://dojofoundation.org/>
Based on Underscore.js 1.7.0, copyright 2009-2015 Jeremy Ashkenas,
DocumentCloud and Investigative Reporters & Editors <http://underscorejs.org/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.245 lodash.get 4.4.2

1.245.1 Available under license :

Copyright jQuery Foundation and other contributors <https://jquery.org/>

Based on Underscore.js, copyright Jeremy Ashkenas,
DocumentCloud and Investigative Reporters & Editors <http://underscorejs.org/>

This software consists of voluntary contributions made by many
individuals. For exact contribution history, see the revision history
available at https://github.com/lodash/lodash

The following license applies to all parts of this software except as
documented below:

====

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or
 substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

====

Copyright and related rights for sample code are waived via CC0. Sample
code is defined as all source code displayed within the prose of the
documentation.

CC0: http://creativecommons.org/publicdomain/zero/1.0/

====

Files located in the node_modules and vendor directories are externally
maintained libraries used by this software which have their own
licenses; we recommend you read them, as their terms may differ from the

terms above.
MIT

1.246 lodash.debounce 4.0.8

1.246.1 Available under license :

Copyright jQuery Foundation and other contributors <https://jquery.org/>

Based on Underscore.js, copyright Jeremy Ashkenas,
DocumentCloud and Investigative Reporters & Editors <http://underscorejs.org/>

This software consists of voluntary contributions made by many
individuals. For exact contribution history, see the revision history
available at https://github.com/lodash/lodash

The following license applies to all parts of this software except as
documented below:

====

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or
 substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

====

Copyright and related rights for sample code are waived via CC0. Sample
code is defined as all source code displayed within the prose of the
documentation.

CC0: http://creativecommons.org/publicdomain/zero/1.0/

====

Files located in the node_modules and vendor directories are externally
maintained libraries used by this software which have their own
licenses; we recommend you read them, as their terms may differ from the
terms above.
MIT

1.247 bson 3.12.4

1.247.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2008-present MongoDB, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /bson-3-12-4-sources-jar/org/bson/BsonRegularExpression.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonNullCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonDocumentWrapperCodec.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonInt32Converter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/annotations/BsonDiscriminator.java
*
 /bson-3-12-4-sources-jar/org/bson/codecs/pojo/MapPropertyCodecProvider.java
* /bson-3-12-4-sources-jar/org/bson/UuidRepresentation.java
* /bson-3-12-4-sources-jar/org/bson/codecs/FloatCodec.java
* /bson-3-12-4-sources-jar/org/bson/internal/UuidHelper.java
* /bson-3-12-4-sources-jar/org/bson/codecs/ObjectIdGenerator.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonStringBuffer.java
* /bson-3-12-4-sources-jar/org/bson/BsonDocumentWrapper.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/LazyPojoCodec.java
* /bson-3-12-4-sources-jar/org/bson/RawBsonDocument.java
* /bson-3-12-4-sources-jar/org/bson/types/CodeWScope.java

* /bson-3-12-4-sources-jar/org/bson/NoOpFieldNameValidator.java
* /bson-3-12-4-sources-jar/org/bson/codecs/DocumentCodecProvider.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/PojoCodec.java
* /bson-3-12-4-sources-jar/org/bson/json/ShellObjectIdConverter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/OverridableUuidRepresentationCodec.java
*
/bson-3-12-4-sources-jar/org/bson/json/JsonDoubleConverter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/DiscriminatorLookup.java
* /bson-3-12-4-sources-jar/org/bson/json/Converter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/AutomaticPojoCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/PropertyCodecProvider.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/PropertyCodecRegistry.java
* /bson-3-12-4-sources-jar/org/bson/AbstractBsonWriter.java
* /bson-3-12-4-sources-jar/org/bson/BsonBinaryReader.java
* /bson-3-12-4-sources-jar/org/bson/BSONObject.java
* /bson-3-12-4-sources-jar/org/bson/codecs/configuration/package-info.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/PropertySerialization.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonStringConverter.java
* /bson-3-12-4-sources-jar/org/bson/internal/CodecCache.java
* /bson-3-12-4-sources-jar/org/bson/LazyBSONObject.java
* /bson-3-12-4-sources-jar/org/bson/BasicBSONEncoder.java
* /bson-3-12-4-sources-jar/org/bson/BSONEncoder.java
*
/bson-3-12-4-sources-jar/org/bson/codecs/BsonTypeCodecMap.java
* /bson-3-12-4-sources-jar/org/bson/json/package-info.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonRegularExpressionCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/annotations/BsonIgnore.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/LazyMissingCodec.java
* /bson-3-12-4-sources-jar/org/bson/json/ShellTimestampConverter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/jsr310/DateTimeBasedCodec.java
* /bson-3-12-4-sources-jar/org/bson/types/Code.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonUndefinedCodec.java
* /bson-3-12-4-sources-jar/org/bson/package-info.java
* /bson-3-12-4-sources-jar/org/bson/BasicBSONDecoder.java
* /bson-3-12-4-sources-jar/org/bson/BsonWriter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonDoubleCodec.java
* /bson-3-12-4-sources-jar/org/bson/internal/Base64.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonMinKeyCodec.java
*
/bson-3-12-4-sources-jar/org/bson/codecs/pojo/ConventionUseGettersAsSettersImpl.java
* /bson-3-12-4-sources-jar/org/bson/codecs/DecoderContext.java
* /bson-3-12-4-sources-jar/org/bson/json/ExtendedJsonMaxKeyConverter.java
* /bson-3-12-4-sources-jar/org/bson/json/ExtendedJsonTimestampConverter.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonStreamBuffer.java
* /bson-3-12-4-sources-jar/org/bson/codecs/UuidCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/MinKeyCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/PropertyMetadata.java
* /bson-3-12-4-sources-jar/org/bson/io/BsonInputMark.java

* /bson-3-12-4-sources-jar/org/bson/types/Binary.java
* /bson-3-12-4-sources-jar/org/bson/json/ExtendedJsonInt64Converter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/StringCodec.java
* /bson-3-12-4-sources-jar/org/bson/json/RelaxedExtendedJsonDoubleConverter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonBinaryCodec.java
* /bson-3-12-4-sources-jar/org/bson/BSONCallbackAdapter.java
*
/bson-3-12-4-sources-jar/org/bson/codecs/BsonJavaScriptCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/SymbolCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/annotations/BsonProperty.java
* /bson-3-12-4-sources-jar/org/bson/util/ComputingMap.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/PropertyReflectionUtils.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/PropertyModel.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BooleanCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/configuration/CodecRegistry.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonScanner.java
* /bson-3-12-4-sources-jar/org/bson/codecs/IdGenerator.java
* /bson-3-12-4-sources-jar/org/bson/json/ExtendedJsonMinKeyConverter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/package-info.java
* /bson-3-12-4-sources-jar/org/bson/io/package-info.java
* /bson-3-12-4-sources-jar/org/bson/types/ObjectId.java
* /bson-3-12-4-sources-jar/org/bson/util/package-info.java
* /bson-3-12-4-sources-jar/org/bson/EmptyBSONCallback.java
*
/bson-3-12-4-sources-jar/org/bson/json/ShellMaxKeyConverter.java
* /bson-3-12-4-sources-jar/org/bson/internal/LazyCodec.java
* /bson-3-12-4-sources-jar/org/bson/ByteBuf.java
* /bson-3-12-4-sources-jar/org/bson/json/ShellBinaryConverter.java
* /bson-3-12-4-sources-jar/org/bson/json/ExtendedJsonRegularExpressionConverter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/configuration/CodecConfigurationException.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/PojoBuilderHelper.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/InstanceCreatorFactoryImpl.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonDocumentCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonDBPointerCodec.java
* /bson-3-12-4-sources-jar/org/bson/FieldNameValidator.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/ClassModel.java
* /bson-3-12-4-sources-jar/org/bson/Transformer.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/TypeWithTypeParameters.java
*
/bson-3-12-4-sources-jar/org/bson/BsonJavaScriptWithScope.java
* /bson-3-12-4-sources-jar/org/bson/codecs/ObjectIdCodec.java
* /bson-3-12-4-sources-jar/org/bson/diagnostics/Logger.java
* /bson-3-12-4-sources-jar/org/bson/codecs/Decimal128Codec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BigDecimalCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonTypeClassMap.java
* /bson-3-12-4-sources-jar/org/bson/io/BsonOutput.java
* /bson-3-12-4-sources-jar/org/bson/diagnostics/SLF4JLogger.java
* /bson-3-12-4-sources-jar/org/bson/json/ExtendedJsonInt32Converter.java

* /bson-3-12-4-sources-jar/org/bson/conversions/Bson.java
* /bson-3-12-4-sources-jar/org/bson/LazyBSONCallback.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonWriterSettings.java
* /bson-3-12-4-sources-jar/org/bson/BsonInt32.java
* /bson-3-12-4-sources-jar/org/bson/BsonDocument.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/EnumPropertyCodecProvider.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/ConventionSetPrivateFieldImpl.java
*
 /bson-3-12-4-sources-jar/org/bson/RawBsonValueHelper.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/CreatorExecutable.java
* /bson-3-12-4-sources-jar/org/bson/BsonTimestamp.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/Convention.java
* /bson-3-12-4-sources-jar/org/bson/io/BasicOutputBuffer.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonBuffer.java
* /bson-3-12-4-sources-jar/org/bson/BsonMaximumSizeExceededException.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/FallbackPropertyCodecProvider.java
* /bson-3-12-4-sources-jar/org/bson/codecs/jsr310/package-info.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/PropertyAccessor.java
* /bson-3-12-4-sources-jar/org/bson/codecs/ByteArrayCodec.java
* /bson-3-12-4-sources-jar/org/bson/internal/CycleDetectingCodecRegistry.java
* /bson-3-12-4-sources-jar/org/bson/conversions/package-info.java
* /bson-3-12-4-sources-jar/org/bson/json/ShellInt64Converter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/MapCodec.java
*
 /bson-3-12-4-sources-jar/org/bson/json/StrictCharacterStreamJsonWriter.java
* /bson-3-12-4-sources-jar/org/bson/json/ShellDateTimeConverter.java
* /bson-3-12-4-sources-jar/org/bson/BsonBinary.java
* /bson-3-12-4-sources-jar/org/bson/json/ShellMinKeyConverter.java
* /bson-3-12-4-sources-jar/org/bson/json/RelaxedExtendedJsonDateTimeConverter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/AtomicLongCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonValueCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/DoubleCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonObjectIdCodec.java
* /bson-3-12-4-sources-jar/org/bson/LazyBSONDecoder.java
* /bson-3-12-4-sources-jar/org/bson/LazyBSONList.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonDecimal128Codec.java
* /bson-3-12-4-sources-jar/org/bson/json/ExtendedJsonUndefinedConverter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/PropertyAccessorImpl.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonNullConverter.java
*
 /bson-3-12-4-sources-jar/org/bson/BsonUndefined.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonInt32Codec.java
* /bson-3-12-4-sources-jar/org/bson/BsonDbPointer.java
* /bson-3-12-4-sources-jar/org/bson/util/Function.java
* /bson-3-12-4-sources-jar/org/bson/types/BSONTimestamp.java
* /bson-3-12-4-sources-jar/org/bson/codecs/LongCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/MapCodecProvider.java
* /bson-3-12-4-sources-jar/org/bson/BSONException.java

* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/PropertyCodecRegistryImpl.java
* /bson-3-12-4-sources-jar/org/bson/BsonNumber.java
* /bson-3-12-4-sources-jar/org/bson/codecs/Decoder.java
* /bson-3-12-4-sources-jar/org/bson/Document.java
* /bson-3-12-4-sources-jar/org/bson/codecs/configuration/CodecRegistries.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonBooleanConverter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/AtomicIntegerCodec.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonJavaScriptConverter.java
* /bson-3-12-4-sources-jar/org/bson/types/package-info.java
*
 /bson-3-12-4-sources-jar/org/bson/json/DateTimeFormatter.java
* /bson-3-12-4-sources-jar/org/bson/types/MinKey.java
* /bson-3-12-4-sources-jar/org/bson/BasicBSONCallback.java
* /bson-3-12-4-sources-jar/org/bson/io/ByteBufferBsonInput.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/ConventionDefaultsImpl.java
* /bson-3-12-4-sources-jar/org/bson/BsonDouble.java
* /bson-3-12-4-sources-jar/org/bson/codecs/IterableCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/UuidCodecProvider.java
* /bson-3-12-4-sources-jar/org/bson/codecs/UuidCodecHelper.java
* /bson-3-12-4-sources-jar/org/bson/assertions/package-info.java
* /bson-3-12-4-sources-jar/org/bson/BsonDateTime.java
* /bson-3-12-4-sources-jar/org/bson/json/LegacyExtendedJsonDateTimeConverter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/InstanceCreatorFactory.java
* /bson-3-12-4-sources-jar/org/bson/codecs/CollectibleCodec.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonTokenType.java
*
 /bson-3-12-4-sources-jar/org/bson/types/MaxKey.java
* /bson-3-12-4-sources-jar/org/bson/BsonString.java
* /bson-3-12-4-sources-jar/org/bson/json/ShellRegularExpressionConverter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/Conventions.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/PojoCodecImpl.java
* /bson-3-12-4-sources-jar/org/bson/BsonType.java
* /bson-3-12-4-sources-jar/org/bson/BsonMaxKey.java
* /bson-3-12-4-sources-jar/org/bson/types/BasicBSONList.java
* /bson-3-12-4-sources-jar/org/bson/codecs/Encoder.java
* /bson-3-12-4-sources-jar/org/bson/BsonMinKey.java
* /bson-3-12-4-sources-jar/org/bson/codecs/NumberCodecHelper.java
* /bson-3-12-4-sources-jar/org/bson/BsonDocumentWriter.java
* /bson-3-12-4-sources-jar/org/bson/BsonWriterSettings.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/PropertyModelSerializationImpl.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonMaxKeyCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/EncoderContext.java
*
 /bson-3-12-4-sources-jar/org/bson/BsonReader.java
* /bson-3-12-4-sources-jar/org/bson/json/ExtendedJsonBinaryConverter.java
* /bson-3-12-4-sources-jar/org/bson/json/ExtendedJsonDoubleConverter.java
* /bson-3-12-4-sources-jar/org/bson/BSON.java
* /bson-3-12-4-sources-jar/org/bson/codecs/ShortCodec.java

* /bson-3-12-4-sources-jar/org/bson/codecs/BsonSymbolCodec.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonToken.java
* /bson-3-12-4-sources-jar/org/bson/BSONDecoder.java
* /bson-3-12-4-sources-jar/org/bson/internal/CodecRegistryHelper.java
* /bson-3-12-4-sources-jar/org/bson/codecs/DateCodec.java
* /bson-3-12-4-sources-jar/org/bson/BsonSerializationException.java
* /bson-3-12-4-sources-jar/org/bson/BsonContextType.java
* /bson-3-12-4-sources-jar/org/bson/BsonReaderMark.java
* /bson-3-12-4-sources-jar/org/bson/json/StrictCharacterStreamJsonWriterSettings.java
* /bson-3-12-4-sources-jar/org/bson/internal/OverridableUuidRepresentationCodecRegistry.java
* /bson-3-12-4-sources-jar/org/bson/codecs/CodeWithScopeCodec.java
*
/bson-3-12-4-sources-jar/org/bson/codecs/CharacterCodec.java
* /bson-3-12-4-sources-jar/org/bson/BasicBSONObject.java
* /bson-3-12-4-sources-jar/org/bson/BsonBoolean.java
* /bson-3-12-4-sources-jar/org/bson/BsonArray.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/ClassModelBuilder.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonParseException.java
* /bson-3-12-4-sources-jar/org/bson/util/ClassMap.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonDateTimeCodec.java
* /bson-3-12-4-sources-jar/org/bson/json/LegacyExtendedJsonBinaryConverter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/MaxKeyCodec.java
* /bson-3-12-4-sources-jar/org/bson/json/ShellUndefinedConverter.java
* /bson-3-12-4-sources-jar/org/bson/BsonBinaryWriterSettings.java
* /bson-3-12-4-sources-jar/org/bson/codecs/RawBsonDocumentCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonTimestampCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/annotations/BsonId.java
*
/bson-3-12-4-sources-jar/org/bson/codecs/IntegerCodec.java
* /bson-3-12-4-sources-jar/org/bson/types/Decimal128.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonWriter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/PojoCodecProvider.java
* /bson-3-12-4-sources-jar/org/bson/json/ExtendedJsonDecimal128Converter.java
* /bson-3-12-4-sources-jar/org/bson/json/ExtendedJsonObjectIdConverter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonJavaScriptWithScopeCodec.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonReader.java
* /bson-3-12-4-sources-jar/org/bson/BsonNull.java
* /bson-3-12-4-sources-jar/org/bson/BsonBinarySubType.java
* /bson-3-12-4-sources-jar/org/bson/json/LegacyExtendedJsonRegularExpressionConverter.java
* /bson-3-12-4-sources-jar/org/bson/BsonInvalidOperationException.java
* /bson-3-12-4-sources-jar/org/bson/BsonJavaScript.java
* /bson-3-12-4-sources-jar/org/bson/types/Symbol.java
* /bson-3-12-4-sources-jar/org/bson/BsonSymbol.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/annotations/package-info.java
*
/bson-3-12-4-sources-jar/org/bson/RawBsonArray.java
* /bson-3-12-4-sources-jar/org/bson/codecs/configuration/CodecProvider.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/ConventionAnnotationImpl.java

* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/PropertyModelBuilder.java
* /bson-3-12-4-sources-jar/org/bson/codecs/PatternCodec.java
* /bson-3-12-4-sources-jar/org/bson/json/ExtendedJsonDateTimeConverter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonBooleanCodec.java
* /bson-3-12-4-sources-jar/org/bson/util/ClassAncestry.java
* /bson-3-12-4-sources-jar/org/bson/json/StrictJsonWriter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/IterableCodecProvider.java
* /bson-3-12-4-sources-jar/org/bson/codecs/DocumentCodec.java
* /bson-3-12-4-sources-jar/org/bson/diagnostics/Loggers.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonInt64Codec.java
* /bson-3-12-4-sources-jar/org/bson/internal/ProvidersCodecRegistry.java
* /bson-3-12-4-sources-jar/org/bson/json/ShellDecimal128Converter.java
*
 /bson-3-12-4-sources-jar/org/bson/codecs/ByteCodec.java
* /bson-3-12-4-sources-jar/org/bson/BsonDocumentReader.java
* /bson-3-12-4-sources-jar/org/bson/internal/Optional.java
* /bson-3-12-4-sources-jar/org/bson/internal/ChildCodecRegistry.java
* /bson-3-12-4-sources-jar/org/bson/codecs/configuration/MapOfCodecsProvider.java
* /bson-3-12-4-sources-jar/org/bson/io/BsonInput.java
* /bson-3-12-4-sources-jar/org/bson/BsonElement.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonStringCodec.java
* /bson-3-12-4-sources-jar/org/bson/io/Bits.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonSymbolConverter.java
* /bson-3-12-4-sources-jar/org/bson/types/StringRangeSet.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BinaryCodec.java
* /bson-3-12-4-sources-jar/org/bson/BsonInt64.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonValueCodecProvider.java
* /bson-3-12-4-sources-jar/org/bson/BSONCallback.java
* /bson-3-12-4-sources-jar/org/bson/json/RelaxedExtendedJsonInt64Converter.java
*
 /bson-3-12-4-sources-jar/org/bson/BsonDecimal128.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/annotations/BsonCreator.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/InstanceCreator.java
* /bson-3-12-4-sources-jar/org/bson/codecs/AtomicBooleanCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/InstanceCreatorImpl.java
* /bson-3-12-4-sources-jar/org/bson/codecs/OverridableUuidRepresentationUuidCodec.java
* /bson-3-12-4-sources-jar/org/bson/types/CodeWithScope.java
* /bson-3-12-4-sources-jar/org/bson/codecs/ValueCodecProvider.java
* /bson-3-12-4-sources-jar/org/bson/json/JsonMode.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/TypeParameterMap.java
* /bson-3-12-4-sources-jar/org/bson/BsonBinaryWriter.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/TypeData.java
* /bson-3-12-4-sources-jar/org/bson/codecs/CodeCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/CollectionPropertyCodecProvider.java
* /bson-3-12-4-sources-jar/org/bson/io/OutputBuffer.java
*
 /bson-3-12-4-sources-jar/org/bson/diagnostics/JULLogger.java
* /bson-3-12-4-sources-jar/org/bson/diagnostics/package-info.java

* /bson-3-12-4-sources-jar/org/bson/StringUtils.java
* /bson-3-12-4-sources-jar/org/bson/AbstractBsonReader.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonArrayCodec.java
* /bson-3-12-4-sources-jar/org/bson/BsonValue.java
* /bson-3-12-4-sources-jar/org/bson/ByteBufNIO.java
* /bson-3-12-4-sources-jar/org/bson/BsonObjectId.java
* /bson-3-12-4-sources-jar/org/bson/codecs/package-info.java
* /bson-3-12-4-sources-jar/org/bson/codecs/Codec.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2008-present MongoDB, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*/
```

Found in path(s):
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/IdGenerators.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/IdGenerator.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/IdPropertyModelHolder.java
* /bson-3-12-4-sources-jar/org/bson/codecs/BsonCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/pojo/ConventionObjectIdGeneratorsImpl.java
*
 /bson-3-12-4-sources-jar/org/bson/codecs/BsonCodecProvider.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2008-present MongoDB, Inc.
* Copyright 2010 The Guava Authors
* Copyright 2011 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
```

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /bson-3-12-4-sources-jar/org/bson/internal/UnsignedLongs.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2008-present MongoDB, Inc.
* Copyright (c) 2008-2014 Atlassian Pty Ltd
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /bson-3-12-4-sources-jar/org/bson/util/AbstractCopyOnWriteMap.java
* /bson-3-12-4-sources-jar/org/bson/util/CopyOnWriteMap.java
* /bson-3-12-4-sources-jar/org/bson/assertions/Assertions.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2008-present MongoDB, Inc.
* Copyright 2018 Cezary Bartosiak
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.

*/

Found in path(s):
* /bson-3-12-4-sources-jar/org/bson/codecs/jsr310/Jsr310CodecProvider.java
* /bson-3-12-4-sources-jar/org/bson/codecs/jsr310/InstantCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/jsr310/LocalDateTimeCodec.java
* /bson-3-12-4-sources-jar/org/bson/codecs/jsr310/LocalDateCodec.java
*
 /bson-3-12-4-sources-jar/org/bson/codecs/jsr310/LocalTimeCodec.java

1.248 mongodb-driver 3.12.4

1.248.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2008-present MongoDB, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/Java8ChangeStreamIterableImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/MongoIterables.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/ClientSessionImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/ClientSessionClock.java
*
 /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/MongoIterableFactory.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/Java8AggregateIterableImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/FallbackMongoIterableFactory.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/ClientSession.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/Java8ListDatabasesIterableImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/Java8ListCollectionsIterableImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/TransactionBody.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/Java8ForEachHelper.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/Java8FindIterableImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/Java8MapReduceIterableImpl.java

* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/Java8MongoIterableFactory.java
*
 /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/package-info.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/Java8ListIndexesIterableImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/Java8DistinctIterableImpl.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2008-present MongoDB, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/util/JSONCallback.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/MongoClientImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/MapReduceOutput.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/Crypts.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/MongoClients.java
*
 /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/MongoChangeStreamCursorImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/MongoClient.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/model/DBCollectionCountOptions.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/model/DBCollectionUpdateOptions.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/BulkWriteException.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/MongoClientDelegate.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/ListCollectionsIterableImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/WriteResult.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/InsertOptions.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/gridfs/GridFSFindIterable.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/CommandMarker.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/Mongo.java
*
 /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/MongoChangeStreamCursor.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DefaultDBDecoder.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/MongoOptions.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/gridfs/GridFSDownloadStream.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/util/JSONSerializers.java

* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/gridfs/GridFSDownloadStreamImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/MongoCursorAdapter.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/package-info.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/OperationExecutor.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/LazyDBCallback.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/util/AbstractObjectSerializer.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/ParallelScanOptions.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/MongoIterableImpl.java
*
 /mongodb-driver-3-12-4-sources-jar/com/mongodb/WriteConcernError.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/BulkWriteError.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/MongoDatabase.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/gridfs/GridFSDBFile.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/BulkWriteRequestBuilder.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/MongoClientOptions.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/BulkWriteUpsert.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DBCollectionObjectFactory.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/LazyDBObject.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/ClientEncryptionImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/AggregationOutput.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/model/DBCreateViewOptions.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/QueryOperators.java
*
 /mongodb-driver-3-12-4-sources-jar/com/mongodb/BulkWriteHelper.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/DistinctIterableImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/FindIterable.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/Cursor.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/AcknowledgedBulkWriteResult.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DBObjectCollationHelper.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/MappingIterable.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/ListCollectionsIterable.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/model/DBCollectionFindAndModifyOptions.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/CollectionInfoRetriever.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/UpdateRequest.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/util/Util.java
*
 /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/ListIndexesIterableImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/MongoIterable.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DBCollection.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/MapReduceIterableImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/GroupCommand.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/BulkUpdateRequestBuilder.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/MongoClientFactory.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/ReflectionDBObject.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/util/package-info.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DBDecoder.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DBCallback.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/FindIterableImpl.java

* /mongodb-driver-3-12-4-sources-jar/com/mongodb/CompoundDBObjectCodec.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/gridfs/GridFSFindIterableImpl.java
*
 /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/gridfs/GridFSBucket.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/QueryBuilder.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/MongoCursor.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/MongoBatchCursorAdapter.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/BulkWriteResult.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DBObjects.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/util/JSONParseException.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DBEncoderAdapter.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/model/DBCollectionFindOptions.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/gridfs/GridFSFile.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/gridfs/GridFS.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/MongoCollection.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/InsertRequest.java
*
 /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/MongoDatabaseImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/jndi/MongoClientFactory.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/ChangeStreamIterableImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DBCursor.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DefaultDBCallback.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/Crypt.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DefaultDBEncoder.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/ListDatabasesIterableImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/RemoveRequest.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/DistinctIterable.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/gridfs/package-info.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/MongoURI.java
*
 /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/ListDatabasesIterable.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/AggregationOptions.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/gridfs/GridFSUploadStreamImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DBDecoderFactory.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/MongoClientURI.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/ListIndexesIterable.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/gridfs/GridFSInputFile.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/MapReduceCommand.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/AggregateIterableImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/Bytes.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/KeyManagementService.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/vault/ClientEncryptions.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/ReplaceRequest.java
*
 /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/gridfs/GridFSBucketImpl.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/SimpleMongoClients.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DBEncoderFactory.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/ClientSessionBinding.java

* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/gridfs/GridFSBuckets.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/WriteRequest.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/CryptConnection.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/ReplicaSetStatus.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/CryptBinding.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/CommandResult.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/UnacknowledgedBulkWriteResult.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/model/DBCollectionDistinctOptions.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/ChangeStreamIterable.java
*
/mongodb-driver-3-12-4-sources-jar/com/mongodb/client/jndi/package-info.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/util/JSON.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/util/ObjectSerializer.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/SimpleMongoClient.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DBAddress.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/MapReduceIterable.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/KeyRetriever.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/vault/package-info.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/AggregateIterable.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/MongoMappingCursor.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DBDecoderAdapter.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/vault/ClientEncryption.java
*
/mongodb-driver-3-12-4-sources-jar/com/mongodb/client/MongoClient.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DB.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/util/ClassMapBasedObjectSerializer.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DBEncoderFactoryAdapter.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/BulkWriteOperation.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DBEncoder.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/LazyDBList.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/gridfs/package-info.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/LazyDBDecoder.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/model/DBCollectionRemoveOptions.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/client/gridfs/GridFSUploadStream.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/gridfs/CLI.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/LazyDBEncoder.java
* /mongodb-driver-3-12-4-sources-jar/com/mongodb/DBCallbackFactory.java
*
/mongodb-driver-3-12-4-sources-jar/com/mongodb/client/internal/MongoCollectionImpl.java

1.249 mongodb-driver-core 3.12.4

1.249.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*

* Copyright 2008-present MongoDB, Inc.

* Copyright 2017 Tom Bentley
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/authentication/SaslPrep.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2008-present MongoDB, Inc.
* Copyright (c) 2008-2014 Atlassian Pty Ltd
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/assertions/Assertions.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2008-present MongoDB, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0

```
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
* Original Work: MIT License, Copyright (c) [2015-2018] all contributors
* https://github.com/marianobarrios/tls-channel
*/
/**
   * Writes a sequence of bytesProduced to this channel from a subsequence of the
   * given buffers.
   *
   * <p>
   * See {@link GatheringByteChannel#write(ByteBuffer[], int, int)} for
 more
   * details of the meaning of this signature.
   *
   * <p>
   * This method behaves slightly different than the interface specification,
   * with respect to non-blocking responses, see {@link #write(ByteBuffer)}
   * for more details.
   *
   * @param srcs   The buffers from which bytesProduced are to be retrieved
   * @param offset The offset within the buffer array of the first buffer from
   *               which bytesProduced are to be retrieved; must be non-negative and no
   *               larger than <tt>srcs.length</tt>
   * @param length The maximum number of buffers to be accessed; must be
   *               non-negative and no larger than <tt>srcs.length</tt>
   *                - <tt>offset</tt>
   * @return The number of bytesProduced written, contrary to the behavior specified
   * in {@link ByteChannel}, this method never returns 0, but throws
   * {@link WouldBlockException}
   * @throws IndexOutOfBoundsException If
 the preconditions on the <tt>offset</tt> and
   *                                   <tt>length</tt> parameters do not hold
   * @throws WouldBlockException       if the channel is in non-blocking mode and the IO operation
   *                                   cannot be completed immediately
   * @throws NeedsTaskException        if the channel is not configured to run tasks automatically
   *                                   and a task needs to be executed to complete the operation
   * @throws SSLException              if the {@link SSLEngine} throws a SSLException
   * @throws IOException               if the underlying channel throws an IOException
   */
/**
   * Reads a sequence of bytesProduced from this channel into a subsequence of the
   * given buffers.
   *
```

```
   * <p>
   * See {@link ScatteringByteChannel#read(ByteBuffer[], int, int)} for more
   * details of the meaning of this signature.
   *
   * <p>
   * This method behaves slightly different
 than the interface specification,
   * with respect to non-blocking responses, see {@link #read(ByteBuffer)} for
   * more details.
   *
   * @param dsts   The buffers into which bytesProduced are to be transferred
   * @param offset The offset within the buffer array of the first buffer into
   *               which bytesProduced are to be transferred; must be non-negative and no
   *               larger than <tt>dsts.length</tt>
   * @param length The maximum number of buffers to be accessed; must be
   *               non-negative and no larger than <tt>dsts.length</tt>
   *                - <tt>offset</tt>
   * @return The number of bytesProduced read, or <tt>-1</tt> if the channel has
   * reached end-of-stream; contrary to the behavior specified in
   * {@link ByteChannel}, this method never returns 0, but throws
   * {@link WouldBlockException}
   * @throws IndexOutOfBoundsException If the preconditions on the <tt>offset</tt> and
    *                                   <tt>length</tt> parameters do not hold
   * @throws WouldBlockException       if the channel is in non-blocking mode and the IO operation
   *                                   cannot be completed immediately
   * @throws NeedsTaskException        if the channel is not configured to run tasks automatically
   *                                   and a task needs to be executed to complete the operation
   * @throws SSLException              if the {@link SSLEngine} throws a SSLException
   * @throws IOException               if the underlying channel throws an IOException
   */
```

Found in path(s):
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/TlsChannel.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2008-present MongoDB, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
```

* limitations under the License.
*/

Found in path(s):
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/AsyncConnection.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/internal/connection/UsageTrackingInternalConnection.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/FsyncUnlockOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/WriteProtocol.java
*
 /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoClientException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ClusterType.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/internal/connection/DefaultDnsSrvRecordMonitorFactory.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/client/model/geojson/codecs/GeometryEncoderHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/async/AsyncAggregateResponseBatchCursor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/SnappyCompressor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/event/ServerMonitorListenerMulticaster.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/BsonDocumentWrapperHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/netty/NettyStream.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/CommandSucceededEvent.java
*
 /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/InsertManyOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/codecs/MultiPointCodec.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/codecs/GeoJsonCodecProvider.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ClusterClock.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/ValidationLevel.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/CommandReadOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/GetMoreProtocol.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/WriteError.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/session/BaseClientSessionImpl.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ChangeEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/ValidationAction.java
*
 /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/WriteConcernResult.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/BucketGranularity.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/CommandResultArrayCodec.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/selector/ServerAddressSelector.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/DBRefCodec.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/AggregateOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/CommandFailedEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/async/SingleResultCallback.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DefaultClusterableServerFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ClusterListener.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/SplittablePayloadBsonWriter.java
*

/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/bulk/InsertRequest.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/client/model/geojson/CoordinateReferenceSystemType.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/InternalConnectionFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/MessageSettings.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/bulk/IndexRequest.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/FindOneAndReplaceOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/UpdateMessage.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionPoolWaitQueueEnteredEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/MultiPolygon.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/AsyncQueryBatchCursor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ClusterConnectionMode.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/Authenticator.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ConnectionId.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/result/DeleteResult.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ZlibCompressor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/SocketStream.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/ReplaceOneModel.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/Tag.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoQueryException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DecimalFormatHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoSocketWriteException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/IndexMap.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/client/model/CountStrategy.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/Time.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ServerHeartbeatFailedEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/MapReduceWithInlineResultsOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/management/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/SocketSettings.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/FieldTrackingBsonWriter.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/Field.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/Compressor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/CommandResultBaseCallback.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ClusterFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/selector/PrimaryServerSelector.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ClusterDescription.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/changestream/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DefaultAuthenticator.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/ReadOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/BucketAutoOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/MergeOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/StreamFactoryFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/AsyncClusterBinding.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoClientSettings.java

* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/UpdateUserOperation.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/codecs/MultiLineStringCodec.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/operation/Operations.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/BucketOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/UpdateOneModel.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoServerException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionListener.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ServerHeartbeatStartedEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/DeleteOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/netty/NettyStreamFactoryFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionPoolEventMulticaster.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/ClusterBinding.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/ReadWriteBinding.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/Sorts.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/FindAndModifyHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionPoolClosedEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionAddedEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/ExplainVerbosity.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/codecs/PolygonCodec.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/event/EventListenerHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoGridFSException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/ExplainHelper.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ServerDescription.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/IndexOptionDefaults.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/gridfs/model/package-info.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/client/model/geojson/codecs/GeometryCollectionCodec.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/UpdateOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/ServerCursor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/ClientSessionOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/Filters.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/UserExistsOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/MapReduceBatchCursor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DefaultConnectionFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ServerAddressHelper.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoExecutionTimeoutException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/LineString.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/CountOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/MapReduceAsyncBatchCursor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoSecurityException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/dns/DnsResolver.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/AsyncConnectionSource.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DefaultServerMonitor.java

* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/CollationMaxVariable.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/bulk/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/UnwindOptions.java
*
/mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/connection/AsynchronousSocketChannelStreamFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/CompressedHeader.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/RenameCollectionOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/BSONTimestampCodec.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/Aggregates.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/internal/connection/MongoWriteConcernWithResponseException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/ListDatabasesOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/DBRef.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/AutoEncryptionSettings.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/connection/AsynchronousSocketChannelStreamFactoryFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/codecs/GeometryCodec.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/management/NullMBeanServer.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/event/CommandListenerMulticaster.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/internal/connection/AsynchronousSocketChannelStream.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/ErrorCategory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/Pool.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionCheckedInEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/SaslAuthenticator.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ServerEventMulticaster.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/BatchCursor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/MapReduceHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/Updates.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ServerSettings.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/netty/NettyStreamFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DefaultServerMonitorFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/DBObjectCodec.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ServerMonitorEventMulticaster.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/internal/connection/ExponentiallyWeightedMovingAverage.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/InternalStreamConnection.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/AbstractByteBufBsonDocument.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/PushOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/IndexOptions.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/CoordinateReferenceSystem.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ServerMonitorListenerAdapter.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ServerListenerAdapter.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionPoolOpenedEvent.java

* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/CollationStrength.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/async/package-info.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/internal/binding/AsyncClusterAwareReadWriteBinding.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/ReadConcern.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/codecs/PointCodec.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/changestream/UpdateDescription.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/ReplaceOptions.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/Stream.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/BuildersHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/ValidationOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoInternalException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DefaultServer.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/bulk/BulkWriteUpsert.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/Block.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/authentication/NativeAuthenticationHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/session/ServerSession.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/CommandMessage.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/Point.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/CommandResultDocumentCodec.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/BaseFindAndModifyOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/FutureAsyncCompletionHandler.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/SslSettings.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/bulk/BulkWriteError.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ClusterableServer.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ElementExtendingBsonWriter.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/BaseCluster.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/SendMessageCallback.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/ReferenceCounted.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoSocketClosedException.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/MapReduceInlineResultsCursor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DefaultConnectionPool.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ZstdCompressor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/changestream/ChangeStreamDocument.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/ChangeStreamBatchCursorHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ResponseCallback.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/NoOpCommandEventSender.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/ChangeStreamOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/CommandListener.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/LoggingCommandEventSender.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/QueryMessage.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/KillCursorProtocol.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/StreamFactory.java

* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/CreateIndexOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/selector/ReadPreferenceServerSelector.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/gridfs/model/GridFSUploadOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/SplittablePayload.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ServerMonitorListener.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/LegacyMessage.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ServerListener.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/CommandResultCallback.java
*
 /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/AsyncWriteOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/CommandOperationHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ServerHeartbeatSucceededEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/DBObject.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/AggregateResponseBatchCursor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionCheckedOutEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/UpdateProtocol.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/ParallelCollectionScanOperation.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/internal/connection/InternalStreamConnectionInitializer.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/codecs/LineStringCodec.java
*
 /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DnsSrvRecordMonitorFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ServerOpeningEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/bulk/BulkWriteResult.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/DeleteManyModel.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/bulk/WriteRequest.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/CommandProtocolImpl.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ServerClosedEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/OperationExecutor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/AsyncSingleServerBinding.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/vault/DataKeyOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/TlsChannelStreamFactoryFactory.java
*
 /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/ListCollectionsOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/GraphLookupOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DnsSrvRecordInitializer.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/diagnostics/logging/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/CommandResultCodecProvider.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/PowerOfTwoBufferPool.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ConnectionPoolSettings.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ConnectionDescription.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/TagSet.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionPoolListenerAdapter.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/ReturnDocument.java
*
 /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/QueryBatchCursor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionOpenedEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/BulkWriteOptions.java

* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/AbstractReferenceCounted.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/FindAndReplaceOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/UserOperationHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/WriteConcernException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/validator/MappedFieldNameValidator.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ClusterEventMulticaster.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/changestream/FullDocument.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DeleteMessage.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionRemovedEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/operation/IndexHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/binding/ClusterAwareReadWriteBinding.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/CompositeByteBuf.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/FindOneAndDeleteOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/BsonWriterDecorator.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/OrderBy.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoInterruptedException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/AsyncSingleConnectionReadBinding.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ServerConnectionState.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/GetMoreMessage.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/AsyncWriteBinding.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/Collation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionMessagesSentEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/DefaultClusterFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/changestream/OperationTypeCodec.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/MapReduceInlineResultsAsyncCursor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/PolygonCoordinates.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/DropIndexOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ConnectionPool.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/QueryProtocol.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/ReadBinding.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/BsonWriterHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/InternalConnection.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/client/model/changestream/ChangeStreamDocumentCodec.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/GeoJsonObjectType.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/GeometryCollection.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoDriverInformation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/DeleteOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/CursorHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/vault/EncryptOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/DBRefCodecProvider.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/TaggableReadPreference.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoNamespace.java

* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/LegacyProtocol.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DefaultDnsSrvRecordMonitor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoTimeoutException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/QueryHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/WriteOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/Variable.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/gridfs/model/GridFSDownloadOptions.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/client/model/geojson/codecs/GeometryDecoderHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/CreateCollectionOptions.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/Java8SniSslHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/UpdateOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/vault/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/EstimatedDocumentCountOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ConcurrentPool.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/annotations/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/result/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/bulk/UpdateRequest.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ClusterableServerFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/FindOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/DBObjectCodecProvider.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ClientMetadataHelper.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/internal/connection/ClusterClockAdvancingSessionContext.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ServerVersion.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/AsyncReadWriteBinding.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/CursorType.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoSocketOpenException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/InsertOneModel.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ByteBufferBsonOutput.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/HexUtils.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/management/MBeanServer.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoCommandException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoChangeStreamException.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/Facet.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/MongoCredentialWithCache.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ClusterListenerAdapter.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ProtocolExecutor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/gridfs/model/GridFSFile.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/AbstractMultiServerCluster.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/MultiServerCluster.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/BasicDBObjectBuilder.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DefaultServerConnection.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/package-info.java
*

/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/AuthenticationMechanism.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/BulkWriteBatch.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoSocketReadException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/CreateIndexesOperation.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/client/model/geojson/NamedCoordinateReferenceSystem.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/management/MBeanServerFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ServerMonitor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/AggregateExplainOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/BasicDBList.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoCompressor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/diagnostics/logging/Logger.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/NoOpSessionContext.java
*
/mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/internal/validator/CollectibleDocumentFieldNameValidator.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/CommandEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/CommandWriteOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoSocketException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/dns/DefaultDnsResolver.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/UnixSocketChannelStream.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/DropCollectionOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/WriteBinding.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/BasicDBObjectFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/UpdateManyModel.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/FindOneAndUpdateOptions.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoSocketReadTimeoutException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/AsynchronousChannelStream.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/MultiLineString.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/assertions/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/X509Authenticator.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/MapReduceAction.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/ReadPreference.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/bulk/WriteConcernError.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/CreateViewOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/AsyncChangeStreamBatchCursor.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionPoolListener.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/DropDatabaseOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/CommandHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/management/ConnectionPoolStatisticsMBean.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/CommandListenerMulticaster.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ServerDescriptionChangedEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/async/AsyncBatchCursor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/management/jmx/JMXMBeanServer.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/package-info.java

* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/event/ConnectionPoolListenerMulticaster.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/selector/CompositeServerSelector.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/AsyncWritableByteChannel.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ReplyHeader.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/ConnectionString.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/OperationHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/MapReduceToCollectionOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/SocketStreamHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/bulk/DeleteRequest.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/InsertProtocol.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/internal/connection/InternalStreamConnectionFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/codecs/MultiPolygonCodec.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/event/ServerListenerMulticaster.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/FindAndUpdateOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/CommandStartedEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/changestream/ChangeStreamLevel.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoWaitQueueFullException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/session/ServerSessionPool.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/CreateCollectionOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ServerType.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/ServerAddress.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/AggregateToCollectionOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ScramShaAuthenticator.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ByteBufBsonDocument.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/InternalConnectionInitializer.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/result/UpdateResult.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/SniSslHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionPoolWaitQueueExitedEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoNotPrimaryException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/LevelCountingBsonWriter.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/PlainAuthenticator.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/changestream/OperationType.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/client/model/geojson/codecs/NamedCoordinateReferenceSystemCodec.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoWriteException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/BaseWriteOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/KillCursorsMessage.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/DropIndexOptions.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/client/gridfs/model/GridFSDownloadByNameOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/operation/SyncOperations.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/CommandEventSender.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/MessageHeader.java

* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/Server.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/Geometry.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/CompressedMessage.java
*
 /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/async/ErrorHandlingResultCallback.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/SimpleExpression.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/ReadConcernLevel.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/DuplicateKeyException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DnsMultiServerCluster.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoWriteConcernException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/BsonArrayWrapper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/CreateViewOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/Cluster.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/BasicDBObject.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/DistinctOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/AsyncReadOperation.java
*
 /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/BufferProvider.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/selector/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoConfigurationException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/ChangeStreamBatchCursor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/validator/UpdateFieldNameValidator.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/GSSAPIAuthenticator.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/CountOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/RequestMessage.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/SingleServerCluster.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/SocketStreamFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/DBObjectFactory.java
*
 /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/CollationAlternate.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoCredential.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ProtocolHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ClusterOpeningEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/IndexModel.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/netty/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/InsertMessage.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/TextSearchOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/binding/AbstractReferenceCounted.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/NativeAuthenticator.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/ListIndexesOperation.java
*
 /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/management/JMXConnectionPoolListener.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/FindOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DescriptionHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/MapReduceStatistics.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/client/model/CountOptionsHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionMessageReceivedEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/RenameCollectionOperation.java

* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/ParallelCollectionScanOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DnsSrvRecordMonitor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/diagnostics/logging/Loggers.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/DocumentToDBRefTransformer.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/Projections.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ConnectionFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/session/ClientSession.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/InsertOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/UnixServerAddress.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/AggregateOperationImpl.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ChangeListener.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/Accumulators.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/diagnostics/logging/JULLogger.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/operation/AsyncOperations.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/management/ConnectionPoolStatistics.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/ConnectionSource.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/selector/LatencyMinimizingServerSelector.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/netty/NettyByteBuf.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/SingleServerBinding.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/CreateUserOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/DocumentHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/Position.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoIncompatibleDriverException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/Indexes.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/AsyncReadBinding.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/AsyncCompletionHandler.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoBulkWriteException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/session/ClientSessionContext.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/selector/WritableServerSelector.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/WriteModel.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/QueryResult.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/netty/NettyBufferProvider.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/gridfs/codecs/GridFSFileCodecProvider.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/selector/ServerSelector.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/MultiPoint.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/BaseQueryMessage.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/gridfs/codecs/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ReplyMessage.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/capi/MongoCryptHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/MixedBulkWriteOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ClusterId.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/FindAndDeleteOperation.java
* /mongodb-driver-core-3-12-4-sources-

jar/com/mongodb/client/model/geojson/codecs/AbstractGeometryCodec.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/CommandProtocol.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/diagnostics/logging/SLF4JLogger.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/CollationCaseFirst.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/codecs/package-info.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/CommandEventMulticaster.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ServerMonitorFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/DropUserOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/session/SessionContext.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/gridfs/codecs/GridFSFileCodec.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/InsertOneOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ClusterClosedEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/DeleteProtocol.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/thread/DaemonThreadFactory.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoNodeIsRecoveringException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/DeleteOneModel.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/geojson/Polygon.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/Function.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/AsyncSingleBatchQueryCursor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/event/ClusterListenerMulticaster.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/AsyncOperationExecutor.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ServerId.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/MongoCursorNotFoundException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/session/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/CurrentOpOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/validator/NoOpFieldNameValidator.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/binding/SingleConnectionReadBinding.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/WriteConcern.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ClusterDescriptionChangedEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/BsonField.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/event/ConnectionClosedEvent.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/ClusterSettings.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/GroupOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ResponseBuffers.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/BulkWriteBatchCombiner.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/SslHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/Connection.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/OpCode.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/ClientEncryptionSettings.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2008-present MongoDB, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/client/model/AggregationLevel.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2008-present MongoDB, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
* Original Work: MIT License, Copyright (c) [2015-2018] all contributors
* https://github.com/marianobarrios/tls-channel
*/

Found in path(s):
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/internal/connection/tlschannel/TlsChannelFlowControlException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/impl/ByteBufferSet.java
*
 /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/WouldBlockException.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/internal/connection/ExtendedAsynchronousByteChannel.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/NeedsWriteException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/ClientTlsChannel.java
* /mongodb-driver-core-3-12-4-sources-
jar/com/mongodb/internal/connection/tlschannel/async/AsynchronousTlsChannelGroup.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/BufferAllocator.java

* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/util/TlsChannelCallbackException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/TlsChannelBuilder.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/NeedsTaskException.java
*
/mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/impl/BufferHolder.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/TrackingAllocator.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/impl/TlsChannelImpl.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/util/Util.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/async/AsynchronousTlsChannel.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/NeedsReadException.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/tlschannel/impl/ByteBufferUtil.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2005 Brian Goetz and Tim Peierls
* Released under the Creative Commons Attribution License
*   (http://creativecommons.org/licenses/by/2.5)
* Official home: http://www.jcip.net
*
* Any republication or derived work distributed in source code form
* must include this copyright and license notice.
*/

Found in path(s):
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/annotations/NotThreadSafe.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/annotations/Immutable.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/annotations/ThreadSafe.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2008-present MongoDB, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/*
* Written by Doug Lea with assistance from members of JCP JSR-166

```
* Expert Group and released to the public domain, as explained at
* http://creativecommons.org/publicdomain/zero/1.0/
*/
/**
    * Returns an array containing all of the elements in this deque, in
    * proper sequence (from first to last element).

   *
    * <p>The returned array will be "safe" in that no references to it are
    * maintained by this deque.  (In other words, this method must allocate
    * a new array).  The caller is thus free to modify the returned array.
    *
    * <p>This method acts as bridge between array-based and collection-based
    * APIs.
    *
    * @return an array containing all of the elements in this deque
    */
```

Found in path(s):
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ConcurrentLinkedDeque.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2008-present MongoDB, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*    http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/OperationReadConcernHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ReadConcernHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/lang/package-info.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/AbortTransactionOperation.java
*
 /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/operation/WriteConcernHelper.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/CommitTransactionOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/lang/NonNull.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/operation/ServerVersionHelper.java

* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/lang/NonNullApi.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/operation/TransactionOperation.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/internal/connection/ReadConcernAwareNoOpSessionContext.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/TransactionOptions.java
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/lang/Nullable.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2008-present MongoDB, Inc.
* Copyright 2012 The Netty Project
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/connection/netty/ReadTimeoutHandler.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2008-present MongoDB, Inc.
* Copyright 2010 The Guava Authors
* Copyright 2011 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):

* /mongodb-driver-core-3-12-4-sources-jar/com/mongodb/annotations/Beta.java

1.250 colors.js 1.4.0

1.250.1 Available under license :

MIT License

Original Library
 - Copyright (c) Marak Squires

Additional Functionality
- Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
 DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.251 spring-web-mvc 4.3.20.RELEASE

1.251.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/condition/ParamsRequestCondition.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/DispatcherServlet.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/ResponseBodyEmitterReturnValueHandler.java
*
 /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/config/annotation/ContentNegotiationConfigurer.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/config/annotation/ViewControllerRegistry.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/config/ViewResolversBeanDefinitionParser.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/resource/AppCacheManifestTransformer.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/config/ViewControllerBeanDefinitionParser.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/Param.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/freemarker/FreeMarkerConfig.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/condition/NameValueExpression.java
*
 /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/WebContentInterceptor.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/ModelAndViewMethodReturnValueHandler.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/ServletModelAttributeMethodProcessor.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/RequestMappingInfo.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/RequestResponseBodyAdviceChain.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/i18n/SessionLocaleResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/HttpHeadersReturnValueHandler.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/condition/HeadersRequestCondition.java
*
 /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/config/annotation/RedirectViewControllerRegistration.java

* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/support/RequestContext.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/ServletInvocableHandlerMethod.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/annotation/PathMatchConfigurer.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/HttpServletBean.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/script/ScriptTemplateView.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/groovy/GroovyMarkupConfigurer.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/handler/HandlerExceptionResolverComposite.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/SseEmitter.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/tags/form/SelectedValueComparator.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/annotation/DefaultServletHandlerConfigurer.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/i18n/CookieLocaleResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/ServletRequestMethodArgumentResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/StreamingResponseBodyReturnValueHandler.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/MessageTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/annotation/CorsRegistry.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/annotation/ViewResolverRegistry.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/resource/ResourceTransformerSupport.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/support/AbstractFlashMapManager.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/resource/WebJarsResourceResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/annotation/ResourceHandlerRegistration.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/handler/AbstractHandlerMethodMapping.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/ModelAndView.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/document/AbstractXlsView.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/annotation/AsyncSupportConfigurer.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/AbstractMessageConverterMethodArgumentResolver.

java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/RequestPartMethodArgumentResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/support/JspAwareRequestContext.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/freemarker/FreeMarkerView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/EscapeBodyTag.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/handler/AbstractUrlHandlerMapping.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/condition/AbstractNameValueExpression.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/DeferredResultMethodReturnValueHandler.java
*
 /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/config/MvcNamespaceUtils.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/HandlerExecutionChain.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/ContentNegotiatingViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/ResponseBodyAdvice.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/support/RedirectAttributesModelMap.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/UriComponentsBuilderMethodArgumentResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/config/annotation/InterceptorRegistry.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/AbstractMessageConverterMethodProcessor.java
*
 /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/feed/AbstractRssFeedView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/resource/ResourceUrlProvider.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/AbstractUrlBasedView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/ExtendedServletRequestDataBinder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0

```
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* A contract for inspecting and potentially modifying request data values such
* as URL query parameters or form field values before they are rendered by a
* view or before a redirect.
*
* <p>Implementations may use this contract for example as part of a solution
* to provide data integrity, confidentiality,
 protection against cross-site
* request forgery (CSRF), and others or for other tasks such as automatically
* adding a hidden field to all forms and URLs.
*
* <p>View technologies that support this contract can obtain an instance to
* delegate to via {@link RequestContext#getRequestDataValueProcessor()}.
*
* @author Rossen Stoyanchev
* @since 3.1
*/
```

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/support/RequestDataValueProcessor.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-

jar/org/springframework/web/servlet/mvc/support/ControllerTypePredicate.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/ResponseBodyEmitterAdapter.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/RedirectView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/AbstractController.java
*
 /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/ServletCookieValueMethodArgumentResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/annotation/EnableWebMvc.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/condition/AbstractMediaTypeExpression.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/resource/DefaultResourceResolverChain.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/annotation/WebMvcConfigurer.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/RequestResponseBodyMethodProcessor.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/RequestAttributeMethodArgumentResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/ResourceServlet.java
*
 /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/AsyncHandlerInterceptor.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/handler/SimpleServletPostProcessor.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/MatrixVariableMethodArgumentResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/annotation/ResourceChainRegistration.java

* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/config/annotation/DelegatingWebMvcConfiguration.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/handler/AbstractHandlerMethodExceptionResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/ListenableFutureReturnValueHandler.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/DeferredResultAdapter.java
*
 /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/groovy/GroovyMarkupView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/condition/AbstractRequestCondition.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/config/annotation/WebMvcConfigurerAdapter.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/resource/AbstractVersionStrategy.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/jasperreports/AbstractJasperReportsView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/config/annotation/WebMvcConfigurerComposite.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/handler/HandlerInterceptorAdapter.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/condition/RequestMethodsRequestCondition.java
*
 /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/condition/RequestCondition.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/LocaleResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/ServletWrappingController.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/handler/RequestMatchResult.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/HandlerInterceptor.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/CompletionStageReturnValueHandler.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/resource/CssLinkResourceTransformer.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/tiles3/TilesConfigurer.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/annotation/ServletAnnotationMappingUtils.java
*
 /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/handler/BeanNameUrlHandlerMapping.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/AbstractHtmlElementBodyTag.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/DefaultRequestToViewNameTranslator.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/resource/VersionedResource.java

* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/resource/ResourceUrlEncodingFilter.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/PathVariableMethodArgumentResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/JsonViewResponseBodyAdvice.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/resource/ResourceTransformer.java
*
 /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/SessionAttributeMethodArgumentResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/handler/MatchableHandlerMapping.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/tiles3/SpringLocaleResolver.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/UrlFilenameViewController.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/RequestMappingInfoHandlerMethodMappingNamingStrategy.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/support/AbstractControllerUrlHandlerMapping.java
*
 /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/tiles3/TilesViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/RedirectAttributesMethodArgumentResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/jasperreports/JasperReportsCsvView.java
* /spring-webmvc-4-3-20-release-sources-1-

jar/org/springframework/web/servlet/handler/UserRoleAuthorizationInterceptor.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/xslt/XsltViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/EvalTag.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/InternalResourceView.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/ModelAndViewResolverMethodReturnValueHandler.j
ava
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/jasperreports/JasperReportsPdfView.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/jasperreports/JasperReportsViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/multiaction/ParameterMethodNameResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/handler/HandlerMethodMappingNamingStrategy.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/feed/AbstractAtomFeedView.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/jasperreports/JasperReportsHtmlView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/tiles2/TilesView.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/tiles3/SpringWildcardServletTilesApplicationContext.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/jasperreports/ConfigurableJasperReportsView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/FlashMapManager.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/support/SessionFlashMapManager.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/ViewResolverComposite.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/condition/RequestConditionHolder.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/GroovyMarkupConfigurerBeanDefinitionParser.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/jasperreports/AbstractJasperReportsSingleFormatView.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/VelocityConfigurerBeanDefinitionParser.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/resource/CachingResourceTransformer.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/ParameterizableViewController.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/Controller.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/tiles2/TilesConfigurer.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/tiles3/TilesView.java
* /spring-webmvc-4-3-20-release-sources-1-

jar/org/springframework/web/servlet/mvc/method/annotation/AbstractMappingJacksonResponseBodyAdvice.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/jasperreports/JasperReportsXlsView.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/annotation/UrlBasedViewResolverRegistration.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/PasswordInputTag.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/PathVariableMapMethodArgumentResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/tiles2/TilesViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/xml/MarshallingView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/feed/AbstractFeedView.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/ViewMethodReturnValueHandler.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/tiles2/SpringWildcardServletTilesApplicationContext.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/ServletResponseMethodArgumentResolver.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/velocity/VelocityToolboxView.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/handler/DispatcherServletWebRequest.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/ServletRequestDataBinderFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/config/InterceptorsBeanDefinitionParser.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/HandlerAdapter.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/i18n/AbstractLocaleContextResolver.java
*
 /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/i18n/AbstractLocaleResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/AbstractHtmlInputElementTag.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/ThemeResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/document/AbstractJExcelView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/velocity/VelocityView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/support/JstlUtils.java

* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/theme/ThemeChangeInterceptor.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/AbstractFormTag.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/ThemeTag.java
*
/spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/HtmlEscapeTag.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/i18n/FixedLocaleResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/BindTag.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/theme/CookieThemeResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/theme/FixedThemeResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/BindErrorsTag.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/LocaleContextResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/theme/SessionThemeResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/AbstractCachingViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/HiddenInputTag.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/json/AbstractJackson2View.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/handler/HandlerMappingIntrospector.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/config/AnnotationDrivenBeanDefinitionParser.java
*
/spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/MatrixVariableMapMethodArgumentResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/HandlerExceptionResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/BeanNameViewResolver.java

* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/UrlBasedViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/SelectTag.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/ButtonTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/resource/VersionResourceResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/ResourceBundleViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/ExceptionHandlerExceptionResolver.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/condition/ProducesRequestCondition.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/RequestMappingHandlerAdapter.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/ResourcesBeanDefinitionParser.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/ResponseBodyEmitter.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/FormTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/MvcUriComponentsBuilder.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/document/AbstractPdfView.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/tags/form/AbstractDataBoundFormElementTag.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/RequestMappingHandlerMapping.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/TagWriter.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/annotation/ResourceHandlerRegistry.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/support/DefaultHandlerExceptionResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/resource/ResourceHttpRequestHandler.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/tags/form/AbstractHtmlElementTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/AbstractHandlerMethodAdapter.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/annotation/CorsRegistration.java
*
/spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/UrlTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/support/WebContentGenerator.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/xml/MappingJackson2XmlView.java
* /spring-webmvc-4-3-20-release-sources-1-

jar/org/springframework/web/servlet/handler/AbstractHandlerMapping.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/condition/ConsumesRequestCondition.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/AbstractView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/LabelTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/AbstractJsonpResponseBodyAdvice.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/OptionTag.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/handler/SimpleMappingExceptionResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/OptionsTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/annotation/ResponseStatusExceptionResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/RequestMappingInfoHandlerMapping.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/handler/AbstractHandlerExceptionResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/document/AbstractPdfStamperView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/XmlViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/TilesConfigurerBeanDefinitionParser.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/ResponseEntityExceptionHandler.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/resource/GzipResourceResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/support/ServletUriComponentsBuilder.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/View.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/json/MappingJackson2JsonView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/CheckboxTag.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/TextareaTag.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/CheckboxesTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/annotation/WebMvcConfigurationSupport.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/annotation/InterceptorRegistration.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/ScriptTemplateConfigurerBeanDefinitionParser.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/support/BindStatus.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/condition/CompositeRequestCondition.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/i18n/AcceptHeaderLocaleResolver.java

* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/InputTag.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/FrameworkServlet.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/HttpEntityMethodProcessor.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/resource/PathResourceResolver.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/FreeMarkerConfigurerBeanDefinitionParser.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/handler/MappedInterceptor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/InternalResourceViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/resource/ResourceTransformerChain.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/ArgumentAware.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/annotation/AnnotationMethodHandlerAdapter.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/resource/VersionPathStrategy.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/document/AbstractXlsxStreamingView.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/resource/ResourceResolverChain.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/annotation/ViewControllerRegistration.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/script/ScriptTemplateConfig.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/AbstractTemplateView.java
* /spring-webmvc-4-3-20-release-sources-1-

jar/org/springframework/web/servlet/resource/DefaultServletHttpRequestHandler.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/CallableMethodReturnValueHandler.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/resource/AbstractResourceResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/annotation/AnnotationMethodHandlerExceptionResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/resource/CachingResourceResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/script/ScriptTemplateViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/jasperreports/JasperReportsMultiFormatView.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/AsyncTaskMethodReturnValueHandler.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/StreamingResponseBody.java
*
/spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/ViewRendererServlet.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/document/AbstractExcelView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/resource/ResourceResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/CorsBeanDefinitionParser.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/ViewNameMethodReturnValueHandler.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/MvcNamespaceHandler.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/NoHandlerFoundException.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/RequestBodyAdvice.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/i18n/LocaleChangeInterceptor.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/annotation/ModelAndViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/ParamTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/handler/SimpleUrlHandlerMapping.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/resource/EncodedResource.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/FlashMap.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/resource/ResourceUrlProviderExposingInterceptor.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/document/AbstractXlsxView.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/groovy/GroovyMarkupConfig.java

* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/support/AbstractDispatcherServletInitializer.java
*
 /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/resource/DefaultResourceTransformerChain.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/condition/PatternsRequestCondition.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/jasperreports/JasperReportsXlsxView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/support/RequestContextUtils.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/RequestBodyAdviceAdapter.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/annotation/DefaultAnnotationHandlerMapping.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/ServletForwardingController.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/resource/VersionStrategy.java
*
 /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/groovy/GroovyMarkupViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/resource/TransformedResource.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/TransformTag.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/HtmlEscapingAwareTag.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/method/annotation/JsonViewRequestBodyAdvice.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/multiaction/MultiActionController.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/script/ScriptTemplateConfigurer.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/ArgumentTag.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/ErrorsTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/velocity/VelocityConfigurer.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/JstlView.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/RequestToViewNameTranslator.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/support/RedirectAttributes.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/multiaction/PropertiesMethodNameResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/tags/form/AbstractMultiCheckedElementTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/multiaction/InternalPathMethodNameResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/velocity/VelocityViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/support/AnnotationControllerTypePredicate.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/tiles2/SimpleSpringPreparerFactory.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/AbstractUrlViewController.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/handler/AbstractDetectingUrlHandlerMapping.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/mvc/LastModified.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/support/ControllerBeanNameHandlerMapping.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/OptionWriter.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/EditorAwareTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/handler/SimpleServletHandlerAdapter.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/NestedPathTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/handler/ConversionServiceExposingInterceptor.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/method/annotation/ServletWebArgumentResolverAdapter.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/condition/MediaTypeExpression.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/SmartView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/TagIdGenerator.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/multiaction/AbstractUrlMethodNameResolver.java
* /spring-webmvc-4-3-20-release-sources-1-

jar/org/springframework/web/servlet/view/tiles3/AbstractSpringPreparerFactory.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/tags/RequestContextAwareTag.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/ViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/handler/WebRequestHandlerInterceptorAdapter.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/multiaction/NoSuchRequestHandlingMethodException.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/support/ControllerClassNameHandlerMapping.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/RadioButtonTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/tags/form/AbstractSingleCheckedElementTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/tiles3/SimpleSpringPreparerFactory.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/tiles3/SpringBeanPreparerFactory.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/multiaction/MethodNameResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/velocity/VelocityLayoutViewResolver.java
*
/spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/ParamAware.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/SimpleControllerHandlerAdapter.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/freemarker/FreeMarkerConfigurer.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/tiles2/AbstractSpringPreparerFactory.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/RadioButtonsTag.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/config/DefaultServletHandlerBeanDefinitionParser.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/velocity/VelocityLayoutView.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/velocity/VelocityConfig.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/tags/form/AbstractCheckedElementTag.java
*
/spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/ModelAndViewDefiningException.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/mvc/HttpRequestHandlerAdapter.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/HandlerMapping.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/tags/form/ValueFormatter.java
No license file was found, but licenses were detected in source scan.

/*

```
* Copyright 2002-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/freemarker/FreeMarkerViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/tiles2/SpringLocaleResolver.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/tiles2/SpringBeanPreparerFactory.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*  http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/resource/FixedVersionStrategy.java
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/resource/ContentVersionStrategy.java
No license file was found, but licenses were detected in source scan.

```
/*
```

* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/view/AbstractTemplateViewResolver.java
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/theme/AbstractThemeResolver.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-
jar/org/springframework/web/servlet/support/AbstractAnnotationConfigDispatcherServletInitializer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.

```
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* XSLT-driven View that allows for response context to be rendered as the
* result of an XSLT transformation.
*
* <p>The XSLT Source object is supplied as a parameter in the model and then
* {@link #locateSource detected} during response rendering. Users can either specify
* a specific entry in the
 model via the {@link #setSourceKey sourceKey} property or
* have Spring locate the Source object. This class also provides basic conversion
* of objects into Source implementations. See {@link #getSourceTypes() here}
* for more details.
*
* <p>All model parameters are passed to the XSLT Transformer as parameters.
* In addition the user can configure {@link #setOutputProperties output properties}
* to be passed to the Transformer.
*
* @author Rob Harrop
* @author Juergen Hoeller
* @since 2.0
*/
```

Found in path(s):
* /spring-webmvc-4-3-20-release-sources-1-jar/org/springframework/web/servlet/view/xslt/XsltView.java

1.252 messageformat 0.1.2

1.252.1 Available under license :

Found license 'Eclipse Public License 1.0' in '<name>Eclipse Public License</name>'
Found license 'Eclipse Public License 1.0' in ':license {:name "Eclipse Public License"'
Found license 'Eclipse Public License 1.0' in 'Distributed under the Eclipse Public License either version 1.0 or (at your option) any later version.'

1.253 camel-core 2.15.2

1.253.1 Available under license :

```
 ========================================================================
 ==  NOTICE file corresponding to the section 4 d of                 ==
 ==  the Apache License, Version 2.0,                                ==
 ==  in this case for the Apache Camel distribution.                 ==
 ========================================================================
```

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Please read the different LICENSE files present in the licenses directory of
this distribution.

Camel :: Core
Copyright 2007-2015 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this

License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided

that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.254 commons-dbcp 1.4

1.254.1 Available under license :

Apache Commons DBCP
Copyright 2001-2010 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of,

the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You

meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate

comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.255 rsocket-transport-netty 1.0.0-RC7

1.255.1 Available under license :

Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/
TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION
1. Definitions.
"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.
"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.
"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.
"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.
"Source" form shall mean the preferred
form for making modifications, including but not limited to software source code, documentation source, and configuration files.
"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.
"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).
"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole,

an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the
interfaces of, the Work and Derivative Works thereof.
"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."
"Contributor" shall mean Licensor and any individual or Legal
Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.
2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.
3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of
their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.
4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:
1. You must give any other recipients of the Work or Derivative Works a copy of this License; and
2. You must cause any modified files to carry prominent notices stating that You changed the files; and
3. You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution
notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
4. If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that
such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works

as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.
5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.
6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.
7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.
8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor
be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.
9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted
against, such Contributor by reason of your accepting any such warranty or additional liability.
END OF TERMS AND CONDITIONS

1.256 rsocket-core 1.0.0-RC7

1.256.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/package-info.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/lease/package-info.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/transport/ClientTransport.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/transport/Transport.java
*
 /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/util/EmptyPayload.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/metadata/CompositeMetadataFlyweight.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/util/DisposableUtils.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/package-info.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/util/package-info.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/Closeable.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/AbstractRSocket.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/metadata/WellKnownMimeType.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/transport/package-info.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/core/StreamIdSupplier.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/SocketAcceptor.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/util/NumberUtils.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/LimitableRequestPublisher.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/util/RecyclerFactory.java
*
 /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/plugins/DuplexConnectionInterceptor.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/core/RSocketRequester.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/util/RSocketProxy.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/DuplexConnection.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/plugins/RSocketInterceptor.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/Payload.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/util/Clock.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/util/ByteBufPayload.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/package-info.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/metadata/security/WellKnownAuthType.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/ClientServerInputMultiplexer.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/RSocket.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/Retryable.java
*
 /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/util/DefaultPayload.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/metadata/CompositeMetadata.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/transport/ServerTransport.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/frame/VersionFlyweight.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/Availability.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/UnboundedProcessor.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/SwitchTransformFlux.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/core/RSocketResponder.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/transport/TransportHeaderAware.java

* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/frame/FrameType.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/package-info.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015-2020 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/RejectedException.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/lease/MissingLeaseException.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/RejectedSetupException.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/ApplicationErrorException.java
*
 /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/CustomRSocketException.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/InvalidSetupException.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/core/ReconnectMono.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/core/ServerSetup.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/plugins/InterceptorRegistry.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/CanceledException.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/SetupException.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/Exceptions.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/RejectedResumeException.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/core/package-info.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/fragmentation/FrameFragmenter.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/ClientRSocketSession.java
*
 /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/InvalidException.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/ConnectionCloseException.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/fragmentation/ReassemblyDuplexConnection.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/ResumeStrategy.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/plugins/InitializingInterceptorRegistry.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/UnsupportedSetupException.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/core/DefaultConnectionSetupPayload.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/RSocketException.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/fragmentation/FrameReassembler.java

* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/exceptions/ConnectionErrorException.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/RSocketErrorException.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/fragmentation/FragmentationDuplexConnection.java
*
 /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/fragmentation/package-info.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015-2019 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/plugins/SocketAcceptorInterceptor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014-2019 Real Logic Ltd.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/BitUtil.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/Hashing.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/CollectionUtil.java

No license file was found, but licenses were detected in source scan.

/*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/jctools/util/UnsafeAccess.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/jctools/queues/MpscUnboundedArrayQueue.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/jctools/queues/IndexedQueueSizeUtil.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/jctools/util/UnsafeRefArrayAccess.java
*
 /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/jctools/queues/BaseLinkedQueue.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/jctools/util/InternalAPI.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/jctools/queues/MessagePassingQueue.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/jctools/queues/LinkedArrayQueueUtil.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/jctools/queues/BaseMpscLinkedArrayQueue.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/jctools/queues/CircularArrayOffsetCalculator.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/jctools/util/Pow2.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/jctools/queues/LinkedQueueNode.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/jctools/queues/QueueProgressIndicators.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/jctools/util/RangeUtil.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/jctools/util/PortableJvmInfo.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under

* the License.
*/

Found in path(s):
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/SynchronizedIntObjectHashMap.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015-2020 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/core/RSocketServer.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/core/RSocketConnector.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/RSocketFactory.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/ConnectionSetupPayload.java
*
 /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/core/Resume.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015-2019 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/frame/ResumeFrameFlyweight.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/lease/RequesterLeaseHandler.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/ResumableDuplexConnection.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/InMemoryResumableFramesStore.java
*
/rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/internal/UnicastMonoProcessor.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/lease/LeaseImpl.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/ExponentialBackoffResumeStrategy.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/util/Function3.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/keepalive/KeepAliveSupport.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/SessionManager.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/ResumableFramesStore.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/ResumeStateHolder.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/util/DuplexConnectionProxy.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/RSocketSession.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/lease/Lease.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/lease/ResponderLeaseHandler.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/lease/Leases.java
*
/rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/util/OnceConsumer.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/lease/LeaseStats.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/RequestListener.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/ClientResume.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/ServerRSocketSession.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/PeriodicResumeStrategy.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/util/MultiSubscriberRSocket.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/ResumeFramesSubscriber.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/UpstreamFramesSubscriber.java
* /rsocket-core-1-0-0-rc7-sources-jar/io/rsocket/resume/ResumeStateException.java

1.257 form-data 2.3.3

1.257.1 Available under license :

Copyright (c) 2012 Felix Geisendrfer (felix@debuggable.com) and contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.258 import-fresh 2.0.0

1.258.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.259 lcid 1.0.0

1.259.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights

to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.260 for-in 1.0.2

1.260.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.261 extglob 2.0.4

1.261.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.262 is-wsl 1.1.0

1.262.1 Available under license :

MIT License

Copyright (c) 2020 Anand Chowdhary <mail@anandchowdhary.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.263 isarray 1.0.0

1.263.1 Available under license :

MIT

1.264 hoist-non-react-statics 2.5.5

1.264.1 Available under license :

Software License Agreement (BSD License)
==========

Copyright (c) 2015, Yahoo! Inc. All rights reserved.

Redistribution and use of this software in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Yahoo! Inc. nor the names of YUI's contributors may be used to endorse or promote products derived from this software without specific prior written permission of Yahoo! Inc.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

BSD-3-Clause

1.265 pump 2.0.1

1.265.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Mathias Buus

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.266 opentest4j 1.0.0

1.266.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /opentest4j-1-0-0-sources-1-jar/org/opentest4j/TestSkippedException.java
* /opentest4j-1-0-0-sources-1-jar/org/opentest4j/ValueWrapper.java
* /opentest4j-1-0-0-sources-1-jar/org/opentest4j/MultipleFailuresError.java
* /opentest4j-1-0-0-sources-1-jar/org/opentest4j/AssertionFailedError.java
*
/opentest4j-1-0-0-sources-1-jar/org/opentest4j/TestAbortedException.java
* /opentest4j-1-0-0-sources-1-jar/org/opentest4j/IncompleteExecutionException.java

1.267 loud-rejection 1.6.0

1.267.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.268 extend-shallow 3.0.2

1.268.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2015, 2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.269 async-foreach 0.1.3

1.269.1 Available under license :

Copyright (c) 2011 "Cowboy" Ben Alman

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

1.270 get-stream 4.1.0

1.270.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.271 scss-tokenizer 0.2.3

1.271.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 sasstools

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.272 gaze 1.1.3

1.272.1 Available under license :

MIT
Copyright (c) 2018 Kyle Robinson Young

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

1.273 callsites 2.0.0

1.273.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is

furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.274 cosmiconfig 5.2.1

1.274.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 David Clark

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.275 collection-visit 1.0.0

1.275.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015-2016, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.276 ansi-gray 0.1.1

1.276.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) <%= year() %>, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.277 mississippi 3.0.0

1.277.1 Available under license :

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-2-Clause

1.278 typedarray 0.0.6

1.278.1 Available under license :

/*
Copyright (c) 2010, Linden Research, Inc.
Copyright (c) 2012, Joshua Bell

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
$/LicenseInfo$
*/

// Original can be found at:
//   https://bitbucket.org/lindenlab/llsd
// Modifications by Joshua Bell inexorabletash@gmail.com
//   https://github.com/inexorabletash/polyfill

// ES3/ES5 implementation of the Krhonos Typed Array Specification
//   Ref: http://www.khronos.org/registry/typedarray/specs/latest/
//   Date: 2011-02-01
//
// Variations:
// * Allows typed_array.get/set() as alias for subscripts (typed_array[])

1.279 for-own 1.0.0

1.279.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2015, 2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT

OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.280 bcrypt-pbkdf 1.0.2

1.280.1 Available under license :

The Blowfish portions are under the following license:

Blowfish block cipher for OpenBSD
Copyright 1997 Niels Provos <provos@physnet.uni-hamburg.de>
All rights reserved.

Implementation advice by David Mazieres <dm@lcs.mit.edu>.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
3. The name of the author may not be used to endorse or promote products
  derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The bcrypt_pbkdf portions are under the following license:

Copyright (c) 2013 Ted Unangst <tedu@openbsd.org>

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING
ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Performance improvements (Javascript-specific):

Copyright 2016, Joyent Inc
Author: Alex Wilson <alex.wilson@joyent.com>

Permission to use, copy, modify, and distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER
RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
BSD-3-Clause

1.281 strip-indent 1.0.1

1.281.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.282 commondir 1.0.1

1.282.1 Available under license :

The MIT License

Copyright (c) 2013 James Halliday (mail@substack.net)

Permission is hereby granted, free of charge,
to any person obtaining a copy of this software and
associated documentation files (the "Software"), to
deal in the Software without restriction, including
without limitation the rights to use, copy, modify,
merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom
the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice
shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR
ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.283 pumpify 1.5.1

1.283.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Mathias Buus

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.284 get-stdin 4.0.1

1.284.1 Available under license :

MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (https://sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.285 true-case-path 1.0.3

1.285.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial

revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.

Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "{}"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright {yyyy} {name of copyright owner}

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache License 2.0

1.286 amdefine 1.0.1

1.286.1 Available under license :

Dojo is available under *either* the terms of the modified BSD license *or* the
Academic Free License version 2.1. As a recipient of Dojo, you may choose which
license to receive this code under (except as noted in per-module LICENSE
files). Some modules may not be the copyright of the Dojo Foundation. These
modules contain explicit declarations of copyright in both the LICENSE files in
the directories in which they reside and in the code itself. No external
contributions are allowed under licenses which are fundamentally incompatible
with the AFL or BSD licenses that Dojo is distributed under.

The text of the AFL and BSD licenses is reproduced below.

The "New" BSD License:
****

Copyright (c) 2005-2009, The Dojo Foundation
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
  list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,
  this list of conditions and the following disclaimer in the documentation
  and/or other materials provided with the distribution.
* Neither the name of the Dojo Foundation nor the names of its contributors
  may be used to endorse or promote products derived from this software
  without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The Academic Free License, v. 2.1:
****

This Academic Free License (the "License") applies to any original work of authorship (the "Original Work") whose owner (the "Licensor") has placed the following notice immediately following the copyright notice for the Original Work:

Licensed under the Academic Free License version 2.1

1) Grant of Copyright License. Licensor hereby grants You a world-wide, royalty-free, non-exclusive, perpetual, sublicenseable license to do the following:

a) to reproduce the Original Work in copies;

b) to prepare derivative works ("Derivative Works")
based upon the Original
Work;

c) to distribute copies of the Original Work and Derivative Works to the public;

d) to perform the Original Work publicly; and

e) to display the Original Work publicly.

2) Grant of Patent License. Licensor hereby grants You a world-wide, royalty-free, non-exclusive, perpetual, sublicenseable license, under patent claims owned or controlled by the Licensor that are embodied in the Original Work as furnished by the Licensor, to make, use, sell and offer for sale the Original Work and Derivative Works.

3) Grant of Source Code License. The term "Source Code" means the preferred form of the Original Work for making modifications to it and all available documentation describing how to modify the Original Work. Licensor hereby agrees to provide a machine-readable copy of the Source Code of the Original Work along with each copy of the Original Work that Licensor distributes. Licensor reserves the right to satisfy this obligation by placing a machine-readable
copy of the Source Code in an information repository
reasonably calculated to permit inexpensive and convenient access by You for as long as Licensor continues to distribute the Original Work, and by publishing the address of that information repository in a notice immediately following the copyright notice that applies to the Original Work.

4) Exclusions From License Grant. Neither the names of Licensor, nor the names of any contributors to the Original Work, nor any of their trademarks or service marks, may be used to endorse or promote products derived from this Original Work without express prior written permission of the Licensor. Nothing in this License shall be deemed to grant any rights to trademarks, copyrights, patents, trade secrets or any other intellectual property of Licensor except as expressly stated herein. No patent license is granted to make, use, sell or offer to sell embodiments of any patent claims other than the licensed claims defined in Section 2. No right is
granted to the trademarks of Licensor even if
such marks are included in the Original Work. Nothing in this License shall be interpreted to prohibit Licensor from licensing under different terms from this License any Original Work that Licensor otherwise would have a right to license.

5) This section intentionally omitted.

6) Attribution Rights. You must retain, in the Source Code of any Derivative Works that You create, all copyright, patent or trademark notices from the Source Code of the Original Work, as well as any notices of licensing and any descriptive text identified therein as an "Attribution Notice." You must cause the Source Code for any Derivative Works that You create to carry a prominent Attribution Notice reasonably calculated to inform recipients that You have modified the Original Work.

7) Warranty of Provenance and Disclaimer of Warranty. Licensor warrants that the copyright in and to the Original Work and the patent rights granted herein

by Licensor are owned by
the Licensor or are sublicensed to You under the terms
of this License with the permission of the contributor(s) of those copyrights
and patent rights. Except as expressly stated in the immediately proceeding
sentence, the Original Work is provided under this License on an "AS IS" BASIS
and WITHOUT WARRANTY, either express or implied, including, without limitation,
the warranties of NON-INFRINGEMENT, MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE. THE ENTIRE RISK AS TO THE QUALITY OF THE ORIGINAL WORK IS WITH YOU.
This DISCLAIMER OF WARRANTY constitutes an essential part of this License. No
license to Original Work is granted hereunder except under this disclaimer.

8) Limitation of Liability. Under no circumstances and under no legal theory,
whether in tort (including negligence), contract, or otherwise, shall the
Licensor be liable to any person for any direct, indirect, special, incidental,
or consequential damages of any character arising as a result of this License
or the use
of the Original Work including, without limitation, damages for loss
of goodwill, work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses. This limitation of liability shall not
apply to liability for death or personal injury resulting from Licensor's
negligence to the extent applicable law prohibits such limitation. Some
jurisdictions do not allow the exclusion or limitation of incidental or
consequential damages, so this exclusion and limitation may not apply to You.

9) Acceptance and Termination. If You distribute copies of the Original Work or
a Derivative Work, You must make a reasonable effort under the circumstances to
obtain the express assent of recipients to the terms of this License. Nothing
else but this License (or another written agreement between Licensor and You)
grants You permission to create Derivative Works based upon the Original Work
or to exercise any of the rights granted in Section 1 herein, and any attempt
to do so
except under the terms of this License (or another written agreement
between Licensor and You) is expressly prohibited by U.S. copyright law, the
equivalent laws of other countries, and by international treaty. Therefore, by
exercising any of the rights granted to You in Section 1 herein, You indicate
Your acceptance of this License and all of its terms and conditions.

10) Termination for Patent Action. This License shall terminate automatically
and You may no longer exercise any of the rights granted to You by this License
as of the date You commence an action, including a cross-claim or counterclaim,
against Licensor or any licensee alleging that the Original Work infringes a
patent. This termination provision shall not apply for an action alleging
patent infringement by combinations of the Original Work with other software or
hardware.

11) Jurisdiction, Venue and Governing Law. Any action or suit relating to this
License may be brought only in the courts of a jurisdiction wherein

the
Licensor resides or in which Licensor conducts its primary business, and under the laws of that jurisdiction excluding its conflict-of-law provisions. The application of the United Nations Convention on Contracts for the International Sale of Goods is expressly excluded. Any use of the Original Work outside the scope of this License or after its termination shall be subject to the requirements and penalties of the U.S. Copyright Act, 17 U.S.C. 101 et seq., the equivalent laws of other countries, and international treaty. This section shall survive the termination of this License.

12) Attorneys Fees. In any action to enforce the terms of this License or seeking damages relating thereto, the prevailing party shall be entitled to recover its costs and expenses, including, without limitation, reasonable attorneys' fees and costs incurred in connection with such action, including any appeal of such action. This section shall survive the termination of this License.

13) Miscellaneous.
This License represents the complete agreement concerning the subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable.

14) Definition of "You" in This License. "You" throughout this License, whether in upper or lower case, means an individual or a legal entity exercising rights under, and complying with all of the terms of, this License. For legal entities, "You" includes any entity that controls, is controlled by, or is under common control with you. For purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

15) Right to Use. You may use the Original Work in all ways not otherwise restricted or conditioned by this License or by law, and Licensor promises not
to interfere with or be responsible for such uses by You.

This license is Copyright (C) 2003-2004 Lawrence E. Rosen. All rights reserved. Permission is hereby granted to copy and distribute this license without modification. This license may not be modified without the express written permission of its copyright owner.
amdefine is released under two licenses: new BSD, and MIT. You may pick the license that best suits your development needs. The text of both licenses are provided below.

The "New" BSD License:

Copyright (c) 2011-2016, The Dojo Foundation
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
  list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,
  this list of conditions and the following disclaimer in the documentation
  and/or other materials provided with the distribution.
* Neither the name of the Dojo Foundation nor the names of its contributors
  may be used to endorse or promote products derived from this software
  without specific prior written permission.

THIS SOFTWARE IS PROVIDED
BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

MIT License

Copyright (c) 2011-2016, The Dojo Foundation

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including
without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.287 har-schema 2.0.0

1.287.1 Available under license :

Copyright (c) 2015, Ahmad Nassri <ahmad@ahmadnassri.com>

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.288 unique-filename 1.1.1

1.288.1 Available under license :

Copyright npm, Inc

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.289 delegates 1.0.0

1.289.1 Available under license :

Copyright (c) 2015 TJ Holowaychuk <tj@vision-media.ca>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.290 path-is-absolute 1.0.1

1.290.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN

THE SOFTWARE.
MIT

1.291 fancy-log 1.3.3

1.291.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014, 2015, 2018 Blaine Bublitz <blaine.bublitz@gmail.com> and Eric Schoffstall <yo@contra.io>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.292 which-module 1.0.0

1.292.1 Available under license :

Copyright (c) 2016, Contributors

Permission to use, copy, modify, and/or distribute this software for any purpose
with or without fee is hereby granted, provided that the above copyright notice
and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS
OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF

THIS SOFTWARE.
ISC

1.293 normalize-package-data 2.5.0

1.293.1 Available under license :

This package contains code originally written by Isaac Z. Schlueter.
Used with permission.

Copyright (c) Meryn Stol ("Author")
All rights reserved.

The BSD License

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS
BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY,
 OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE
OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN
IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-2-Clause

1.294 remove-trailing-separator 1.1.0

1.294.1 Available under license :

ISC
Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.295 parse-node-version 1.0.1

1.295.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2018 Blaine Bublitz <blaine.bublitz@gmail.com> and Eric Schoffstall <yo@contra.io>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN
ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.296 cross-spawn 3.0.1

1.296.1 Available under license :

Copyright (c) 2014 IndigoUnited

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is furnished
to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.297 wrappy 1.0.2

1.297.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.298 path-type 1.1.0

1.298.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.299 isexe 2.0.0

1.299.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.300 is-extglob 2.1.1

1.300.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2016, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is

furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.301 iferr 0.1.5

1.301.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Nadav Ivgi

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.302 is-arrayish 0.2.1

1.302.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 JD Ballard

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.303 aproba 1.2.0

1.303.1 Available under license :

ISC
Copyright (c) 2015, Rebecca Turner <me@re-becca.org>

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.304 redent 1.0.0

1.304.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.305 fstream 1.0.12

1.305.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.306 caller-callsite 2.0.0

1.306.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.307 util-deprecate 1.0.2

1.307.1 Available under license :

(The MIT License)

Copyright (c) 2014 Nathan Rajlich <nathan@tootallnate.net>

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.308 commander 2.17.1

1.308.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2011 TJ Holowaychuk <tj@vision-media.ca>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the 'Software'), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.309 which 1.3.1

1.309.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR
IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.310 ecc-jsbn 0.1.2

1.310.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Jeremie Miller

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
Licensing

This software is covered under the following copyright:

/*
* Copyright (c) 2003-2005 Tom Wu
* All Rights Reserved.
*

* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be
* included in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND,
* EXPRESS, IMPLIED OR OTHERWISE, INCLUDING WITHOUT LIMITATION, ANY
* WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.
*
* IN NO EVENT SHALL TOM WU BE LIABLE FOR ANY SPECIAL,
 INCIDENTAL,
* INDIRECT OR CONSEQUENTIAL DAMAGES OF ANY KIND, OR ANY DAMAGES WHATSOEVER
* RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER OR NOT ADVISED OF
* THE POSSIBILITY OF DAMAGE, AND ON ANY THEORY OF LIABILITY, ARISING OUT
* OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
*
* In addition, the following condition applies:
*
* All redistributions must retain an intact copy of this copyright notice
* and disclaimer.
*/

Address all questions regarding this license to:

 Tom Wu
 tjw@cs.Stanford.EDU
MIT

1.311 tunnel-agent 0.6.0

1.311.1 Available under license :

Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean
the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name)
to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual
or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to

You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by
combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and

You must cause any modified files to carry prominent notices stating that You changed the files; and

You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark,
and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed as modifying the License. You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks,
or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and

assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall
any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims
asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.312 concat-stream 1.6.2

1.312.1 Available under license :

The MIT License

Copyright (c) 2013 Max Ogden

Permission is hereby granted, free of charge,
to any person obtaining a copy of this software and
associated documentation files (the "Software"), to
deal in the Software without restriction, including
without limitation the rights to use, copy, modify,
merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom
the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice
shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR
ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.313 asn1.js 4.10.1

1.313.1 Available under license :

MIT

1.314 ansi-wrap 0.1.0

1.314.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.315 babel-runtime 6.26.0

1.315.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 Jed Watson

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Copyright (C) 2012-2014 by various contributors (see AUTHORS)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
The << Software identified by reference to the Ecma Standard* ("Software)">> is protected by copyright and is being
made available under the "BSD License", included below. This Software may be subject to third party rights (rights from parties other than Ecma International), including patent rights, and no licenses under such third party rights are granted under this license even if the third party concerned is a member of Ecma International. SEE THE ECMA
CODE OF CONDUCT IN PATENT MATTERS AVAILABLE AT http://www.ecma-international.org/memento/codeofconduct.htm FOR
INFORMATION REGARDING THE LICENSING OF PATENT CLAIMS THAT ARE REQUIRED TO IMPLEMENT ECMA INTERNATIONAL STANDARDS*.

Copyright (C) 2012-2013 Ecma International
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following
disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the authors nor Ecma International may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE ECMA INTERNATIONAL "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT
SHALL ECMA INTERNATIONAL BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

* Ecma International Standards hereafter means Ecma International Standards as well as Ecma Technical Reports
Copyright (c) 2014-2015 Jason Quense <jason@quense.me>
Original work by respective rule authors; copywrites noted in files.

MIT License

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION

WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Copyright (c) jQuery Foundation, Inc. and Contributors, All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL <COPYRIGHT HOLDER> BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.316 caseless 0.12.0

1.316.1 Available under license :

Apache License 2.0

Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred

form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces

of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity

on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such

license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of
their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.
4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:
You must give any other recipients of the Work or Derivative Works a copy of this License; and
You must cause any modified files to carry prominent notices stating that You changed the files; and
You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices
from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional
attribution notices cannot be construed as modifying the License. You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.
5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.
6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the
Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.
7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.
8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable
to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such
Contributor by reason of your accepting any such warranty or additional liability.
END OF TERMS AND CONDITIONS

1.317 cookie-signature 1.0.6

1.317.1 Available under license :

MIT

1.318 class-utils 0.3.6

1.318.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, 2017-2018, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.319 camelcase-keys 2.1.0

1.319.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.320 define-property 2.0.2

1.320.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015-2018, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.321 deep-extend 0.6.0

1.321.1 Available under license :

The MIT License (MIT)

Copyright (c) 2013-2018, Viacheslav Lotsmanov

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.322 number-is-nan 1.0.1

1.322.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.323 json-loader 0.5.7

1.323.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.324 isomorphic-fetch 2.2.1

1.324.1 Available under license :

No license file was found, but licenses were detected in source scan.

isomorphic-fetch [![Build Status](https://travis-ci.org/matthew-andrews/isomorphic-fetch.svg?branch=master)](https://travis-ci.org/matthew-andrews/isomorphic-fetch)
==========

Fetch for node and Browserify. Built on top of [GitHub's WHATWG Fetch polyfill](https://github.com/github/fetch).

Warnings

- This adds `fetch` as a global so that its API is consistent between client and server.
- You must bring your own ES6 Promise compatible polyfill, I suggest [es6-promise](https://github.com/jakearchibald/es6-promise).

For [ease-of-maintenance and backward-compatibility reasons][why polyfill], this library will always be a polyfill. As a "safe" alternative, which does not modify the global, consider [fetch-ponyfill][].

[why polyfill]: https://github.com/matthew-andrews/isomorphic-fetch/issues/31#issuecomment-149668361
[fetch-ponyfill]: https://github.com/qubyte/fetch-ponyfill

Installation

NPM

```sh
npm
 install --save isomorphic-fetch es6-promise
```

Bower

```sh
bower install --save isomorphic-fetch es6-promise
```

Usage

```js
require('es6-promise').polyfill();
require('isomorphic-fetch');

fetch('//offline-news-api.herokuapp.com/stories')
 .then(function(response) {
  if (response.status >= 400) {
   throw new Error("Bad response from server");
  }
  return response.json();
 })
 .then(function(stories) {
  console.log(stories);
 });
```

License

All open source code released by FT Labs is licenced under the MIT licence. Based on [the fine work by](https://github.com/github/fetch/pull/31) **[jxck](https://github.com/Jxck)**.

Found in path(s):
* /fis-components-isomorphic-fetch-2-2-1-0-g4801b9c-1-tar-gz/fis-components-isomorphic-fetch-9599403/README.md

1.325 arr-flatten 1.1.0

1.325.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
 OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.326 arr-union 3.1.0

1.326.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2016, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights

to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.327 error-ex 1.3.2

1.327.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 JD Ballard

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.328 oauth-sign 0.9.0

1.328.1 Available under license :

Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean
the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name)
to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic

mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual
or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by
combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and

You must cause any modified files to carry prominent notices stating that You changed the files; and

You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark,
and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed as modifying the License. You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.329 forever-agent 0.6.1

1.329.1 Available under license :

Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1

through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean
the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name)
to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual
or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section)

patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by
combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and

You must cause any modified files to carry prominent notices stating that You changed the files; and

You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed as modifying the License. You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall
any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims
asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.330 symbol-observable 1.2.0

1.330.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)
Copyright (c) Ben Lesh <ben@benlesh.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.331 osenv 0.1.5

1.331.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR
IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.332 wordwrap 1.0.0

1.332.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity

exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the

Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents

of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,

work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "{}" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright 2018 Colin Arenz

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.333 getpass 0.1.7

1.333.1 Available under license :

Copyright Joyent, Inc. All rights reserved.
Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
IN THE SOFTWARE.
MIT

1.334 css-what 2.1.3

1.334.1 Available under license :

BSD-2-Clause
Copyright (c) Felix Bhm
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS;
OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)

ARISING IN ANY WAY OUT OF THE USE OF THIS,
EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.335 isstream 0.1.2

1.335.1 Available under license :

The MIT License (MIT)
==========

Copyright (c) 2015 Rod Vagg

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.336 code-point-at 1.1.0

1.336.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.337 meow 3.7.0

1.337.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.338 time-stamp 1.1.0

1.338.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 Maxime Chaisse-Leal

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights

to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.339 os-homedir 1.0.2

1.339.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.340 read-pkg 1.1.0

1.340.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.341 fragment-cache 0.2.1

1.341.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016-2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.342 esutils 2.0.3

1.342.1 Available under license :

BSD-2-Clause
Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL <COPYRIGHT HOLDER> BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.343 read-pkg-up 1.0.1

1.343.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.344 component-emitter 1.3.0

1.344.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2014 Component contributors <dev@component.io>

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

1.345 copy-descriptor 0.1.1

1.345.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015-2016, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.346 load-json-file 1.1.0

1.346.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT

OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.347 strip-bom 2.0.0

1.347.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.348 decamelize 1.2.0

1.348.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.349 ms 2.1.2

1.349.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2016 Zeit, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.350 json-parse-better-errors 1.0.2

1.350.1 Available under license :

Copyright 2017 Kat Marchn

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated

documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.351 performance-now 2.1.0

1.351.1 Available under license :

MIT
Copyright (c) 2013 Braveg1rl

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.352 gauge 2.7.4

1.352.1 Available under license :

ISC
Copyright (c) 2014, Rebecca Turner <me@re-becca.org>

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above

copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.353 extsprintf 1.3.0

1.353.1 Available under license :

Copyright (c) 2012, Joyent, Inc. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE
MIT

1.354 asap 2.0.6

1.354.1 Available under license :

MIT

Copyright 20092014 Contributors. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or

sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
IN THE SOFTWARE.

1.355 caller-path 2.0.0

1.355.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.356 assert-plus 1.0.0

1.356.1 Available under license :

MIT

1.357 array-find-index 1.0.2

1.357.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.358 currently-unhandled 0.4.1

1.358.1 Available under license :

The MIT License (MIT)

Copyright (c) James Talmage <james@talmage.io> (github.com/jamestalmage)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.359 os-locale 1.4.0

1.359.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.360 expand-brackets 2.1.4

1.360.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015-2016, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.361 os-tmpdir 1.0.2

1.361.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.362 ci-info 2.0.0

1.362.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016-2018 Thomas Watson Steen

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.363 abbrev 1.1.1

1.363.1 Available under license :

This software is dual-licensed under the ISC and MIT licenses.
You may use this software under EITHER of the following licenses.

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR

ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Copyright Isaac Z. Schlueter and Contributors
All rights reserved.

Permission is
hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE
SOFTWARE.
ISC

1.364 trim-newlines 1.0.0

1.364.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.365 verror 1.10.0

1.365.1 Available under license :

Copyright (c) 2016, Joyent, Inc. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE
MIT

1.366 arr-diff 4.0.0

1.366.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.367 stdout-stream 1.4.1

1.367.1 Available under license :

Copyright 2013 Mathias Buus

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.368 invert-kv 1.0.0

1.368.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.369 fs-write-stream-atomic 1.0.10

1.369.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.370 brace-expansion 1.1.11

1.370.1 Available under license :

MIT
MIT License

Copyright (c) 2013 Julian Gruber <julian@juliangruber.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.371 archy 1.0.0

1.371.1 Available under license :

This software is released under the MIT license:

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS
FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR

COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.372 inflight 1.0.6

1.372.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.373 cliui 3.2.0

1.373.1 Available under license :

Copyright (c) 2015, Contributors

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.374 map-obj 1.0.1

1.374.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.375 repeating 2.0.1

1.375.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.376 is-typedarray 1.0.0

1.376.1 Available under license :

This software is released under the MIT license:

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.377 is-directory 0.3.1

1.377.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2016, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in

all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.378 get-value 2.0.6

1.378.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2016, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.379 indent-string 2.1.0

1.379.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.380 lru-cache 5.1.1

1.380.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.381 html-comment-regex 1.1.2

1.381.1 Available under license :

Copyright 2018 Steve Mao

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the

rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.382 cache-base 1.0.1

1.382.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.383 tweetnacl 0.14.5

1.383.1 Available under license :

This is free and unencumbered software released into the public domain.

Anyone is free to copy, modify, publish, use, compile, sell, or
distribute this software, either in source code form or as a compiled
binary, for any purpose, commercial or non-commercial, and by any
means.

In jurisdictions that recognize copyright laws, the author or authors
of this software dedicate any and all copyright interest in the
software to the public domain. We make this dedication for the benefit
of the public at large and to the detriment of our heirs and
successors. We intend this dedication to be an overt act of
relinquishment in perpetuity of all present and future rights to this
software under copyright law.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS BE LIABLE FOR ANY CLAIM, DAMAGES OR
OTHER LIABILITY, WHETHER
IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

For more information, please refer to <http://unlicense.org>

1.384 array-unique 0.3.2

1.384.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2016, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.385 assign-symbols 1.0.0

1.385.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.386 through 2.3.8

1.386.1 Available under license :

The MIT License

Copyright (c) 2011 Dominic Tarr

Permission is hereby granted, free of charge,
to any person obtaining a copy of this software and
associated documentation files (the "Software"), to
deal in the Software without restriction, including
without limitation the rights to use, copy, modify,

merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom
the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice
shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR
ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT
Apache License, Version 2.0

Copyright (c) 2011 Dominic Tarr

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.387 extend 3.0.2

1.387.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Stefan Thomas

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to

the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.388 npmlog 4.1.2

1.388.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR
IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.389 netty 3.10.5.Final

1.389.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts

as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who decide to use it. You
can use it too,
but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid
distributors to deny you these rights or to ask you to surrender these
rights. These restrictions translate to certain responsibilities for
you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis
or for a fee, you must give
the recipients all the rights that we gave
you. You must make sure that they, too, receive or can get the source
code. If you link other code with the library, you must provide
complete object files to the recipients, so that they can relink them
with the library after making changes to the library and recompiling
it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the
library, and (2) we offer you this license, which gives you legal
permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that
there is no warranty for the free library. Also, if the library is
modified by someone else and passed on, the recipients should know
that what they have is not the original version, so that the original

author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU

operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included
without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for

writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works

in
themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this
License to a given copy of the Library. To do
this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must
be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not

compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License.
Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one

of these things:

a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.

e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot

use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.

b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues),

conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and

conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is
safest to attach them to the start of each source file to most effectively
convey the exclusion of warranty; and each file should have at least the
"copyright"
line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or
modify it under the terms of the GNU Lesser General Public
License as published by the Free Software Foundation; either
version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public
License along with this library; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, 5th Floor, Boston, MA 02110-1301 USA

Also add information on how to contact you by electronic and paper mail.

You
should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

The Netty Project
==========

Please visit the Netty web site for more information:

* http://netty.io/

Copyright 2011 The Netty Project

The Netty Project licenses this file to you under the Apache License,
version 2.0 (the "License"); you may not use this file except in compliance
with the License. You may obtain a copy of the License at:

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
License for the specific language governing permissions and limitations
under the License.

Also, please refer to each LICENSE.<component>.txt file, which is located in
the 'license' directory of the distribution file, for the license terms of the
components that this product depends on.

This
 product contains the extensions to Java Collections Framework which has
been derived from the works by JSR-166 EG, Doug Lea, and Jason T. Greene:

 * LICENSE:
   * license/LICENSE.jsr166y.txt (Public Domain)
 * HOMEPAGE:
   * http://gee.cs.oswego.edu/cgi-bin/viewcvs.cgi/jsr166/
   * http://viewvc.jboss.org/cgi-bin/viewvc.cgi/jbosscache/experimental/jsr166/

This product contains a modified version of Robert Harder's Public Domain
Base64 Encoder and Decoder, which can be obtained at:

 * LICENSE:
   * license/LICENSE.base64.txt (Public Domain)
 * HOMEPAGE:
   * http://iharder.sourceforge.net/current/java/base64/

This product contains a modified version of 'JZlib', a re-implementation of
zlib in pure Java, which can be obtained at:

 * LICENSE:
   * license/LICENSE.jzlib.txt (BSD Style License)
 * HOMEPAGE:
   * http://www.jcraft.com/jzlib/

This product contains a modified version of 'Webbit', a Java event based
WebSocket and HTTP
 server:

 * LICENSE:

  * license/LICENSE.webbit.txt (BSD License)
 * HOMEPAGE:
  * https://github.com/joewalnes/webbit

This product optionally depends on 'Protocol Buffers', Google's data
interchange format, which can be obtained at:

 * LICENSE:
  * license/LICENSE.protobuf.txt (New BSD License)
 * HOMEPAGE:
  * http://code.google.com/p/protobuf/

This product optionally depends on 'Bouncy Castle Crypto APIs' to generate
a temporary self-signed X.509 certificate when the JVM does not provide the
equivalent functionality. It can be obtained at:

 * LICENSE:
  * license/LICENSE.bouncycastle.txt (MIT License)
 * HOMEPAGE:
  * http://www.bouncycastle.org/

This product optionally depends on 'SLF4J', a simple logging facade for Java,
which can be obtained at:

 * LICENSE:
  * license/LICENSE.slf4j.txt (MIT License)
 * HOMEPAGE:
  * http://www.slf4j.org/

This product optionally depends on 'Apache Commons Logging', a logging
framework, which can be obtained at:

  * LICENSE:
  * license/LICENSE.commons-logging.txt (Apache License 2.0)
 * HOMEPAGE:
  * http://commons.apache.org/logging/

This product optionally depends on 'Apache Log4J', a logging framework,
which can be obtained at:

 * LICENSE:
  * license/LICENSE.log4j.txt (Apache License 2.0)
 * HOMEPAGE:
  * http://logging.apache.org/log4j/

This product optionally depends on 'JBoss Logging', a logging framework,
which can be obtained at:

* LICENSE:
  * license/LICENSE.jboss-logging.txt (GNU LGPL 2.1)
* HOMEPAGE:
  * http://anonsvn.jboss.org/repos/common/common-logging-spi/

This product optionally depends on 'Apache Felix', an open source OSGi framework implementation, which can be obtained at:

* LICENSE:
  * license/LICENSE.felix.txt (Apache License 2.0)
* HOMEPAGE:
  * http://felix.apache.org/

The person or persons who have associated work with this document (the "Dedicator" or "Certifier") hereby either (a) certifies that, to the best of his knowledge, the work of authorship identified is in the public domain of the country from which the work is published, or (b) hereby dedicates whatever copyright the dedicators holds in the work of authorship identified below (the "Work") to the public domain. A certifier, moreover, dedicates any copyright interest he may have in the associated work, and for these purposes, is described as a "dedicator" below.

A certifier has taken reasonable steps to verify the copyright status of this work. Certifier recognizes that his good faith efforts may not shield him from liability if in fact the work certified is not in the public domain.

Dedicator makes this dedication for the benefit of the public at large and to the detriment of the Dedicator's heirs and successors. Dedicator intends this dedication to be an overt act of relinquishment in perpetuate
 of all present
and future rights under copyright law, whether vested or contingent, in the Work. Dedicator understands that such relinquishment of all rights includes the relinquishment of all rights to enforce (by lawsuit or otherwise) those copyrights in the Work.

Dedicator recognizes that, once placed in the public domain, the Work may be freely reproduced, distributed, transmitted, used, modified, built upon, or otherwise exploited by anyone for any purpose, commercial or non-commercial, and in any way, including by methods that have not yet been invented or conceived.

The MIT License (MIT)

Copyright (c) 2000 - 2013 The Legion of the Bouncy Castle Inc.
(http://www.bouncycastle.org)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell

copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,

and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable

by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only

on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Copyright 2008, Google Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Code generated by the Protocol Buffer compiler is owned by the owner
of the input file used when generating it. This code is not
standalone and requires a support library to be linked with it. This
support library is itself covered by the above license.
The person or persons who have associated work with this document (the
"Dedicator" or "Certifier") hereby either (a) certifies that, to the best of
his knowledge, the work of authorship identified is in the public domain of
the country from which the work is published, or (b) hereby dedicates whatever
copyright the dedicators holds in the work of authorship identified below (the
"Work") to the public domain. A certifier, moreover, dedicates any copyright
interest he may have in the associated work, and for these purposes, is
described as a "dedicator" below.

A certifier has taken reasonable steps to verify the copyright status of this
work. Certifier recognizes that his good faith efforts may not shield him from
liability if in fact the work certified is not in the public domain.

Dedicator makes this dedication for the benefit of the public at large and to
the detriment of the Dedicator's heirs and successors. Dedicator intends this
dedication to be an overt act of relinquishment in perpetuity
of all present
and future rights under copyright law, whether vested or contingent, in the
Work. Dedicator understands that such relinquishment of all rights includes
the relinquishment of all rights to enforce (by lawsuit or otherwise) those
copyrights in the Work.

Dedicator recognizes that, once placed in the public domain, the Work may be
freely reproduced, distributed, transmitted, used, modified, built upon, or
otherwise exploited by anyone for any purpose, commercial or non-commercial,
and in any way, including by methods that have not yet been invented or
conceived.
(BSD License: http://www.opensource.org/licenses/bsd-license)

Copyright (c) 2011, Joe Walnes, Aslak Hellesy and contributors

All rights reserved.

Redistribution and use in source and binary forms, with or
without modification, are permitted provided that the
following conditions are met:

* Redistributions of source code must retain the above
 copyright notice, this list of conditions and the
 following disclaimer.

* Redistributions in binary form must reproduce the above
 copyright notice, this list of conditions and the
 following disclaimer in the documentation and/or other
 materials provided with the distribution.

* Neither the name of the Webbit nor the names of
 its contributors may be used to endorse or promote products
 derived from this software without specific prior written
 permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND
CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF

MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT
OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.
/*
* Copyright (c) 2004-2007 QOS.ch
* All rights reserved.
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be

* included in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
* NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
* LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
* OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
* WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/
Copyright (c) 2000,2001,2002,2003,2004 ymnk, JCraft,Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in
the documentation and/or other materials provided with the distribution.

3. The names of the authors may not be used to endorse or promote products
derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESSED OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND
FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL JCRAFT,
INC. OR ANY CONTRIBUTORS TO THIS SOFTWARE
BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA,
OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE,
EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work,

excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions

of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.390 hibernate-commons-annotations 3.2.0.Final

1.390.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Hibernate, Relational Persistence for Idiomatic Java
*
* Copyright (c) 2008, Red Hat Middleware LLC or third-party contributors as
* indicated by the @author tags or express copyright attribution
* statements applied by the authors. All third-party contributions are
* distributed under license by Red Hat Middleware LLC.
*
* This copyrighted material is made available to anyone wishing to use, modify,

* copy, or redistribute it subject to the terms and conditions of the GNU
* Lesser General Public License, as published by the Free Software Foundation.
*
* This program is distributed in the hope that it will be useful,
* but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY
* or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License
* for more details.
*
* You should have received a copy of the GNU Lesser General Public License
* along with this distribution;
 if not, write to:
* Free Software Foundation, Inc.
* 51 Franklin Street, Fifth Floor
* Boston, MA 02110-1301 USA
*/

Found in path(s):
* /hibernate-commons-annotations-3-2-0-final-sources-2-
jar/org/hibernate/annotations/common/reflection/XMember.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-
jar/org/hibernate/annotations/common/reflection/java/generics/SimpleTypeEnvironment.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-
jar/org/hibernate/annotations/common/annotationfactory/AnnotationProxy.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-
jar/org/hibernate/annotations/common/reflection/java/generics/CompoundTypeEnvironment.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-
jar/org/hibernate/annotations/common/reflection/XClass.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-
jar/org/hibernate/annotations/common/reflection/java/JavaXProperty.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-
jar/org/hibernate/annotations/common/reflection/java/generics/TypeFactory.java
*
 /hibernate-commons-annotations-3-2-0-final-sources-2-
jar/org/hibernate/annotations/common/reflection/AnnotationReader.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-
jar/org/hibernate/annotations/common/reflection/java/JavaXAnnotatedElement.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-
jar/org/hibernate/annotations/common/reflection/XProperty.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-
jar/org/hibernate/annotations/common/reflection/XMethod.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-
jar/org/hibernate/annotations/common/reflection/java/JavaXArrayType.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-
jar/org/hibernate/annotations/common/reflection/java/JavaXSimpleType.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-
jar/org/hibernate/annotations/common/reflection/java/JavaXPackage.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-
jar/org/hibernate/annotations/common/reflection/java/JavaXMethod.java

*
/hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/java/generics/TypeEnvironment.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/annotationfactory/AnnotationDescriptor.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/XPackage.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/java/Pair.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/java/generics/IdentityTypeEnvironment.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/java/JavaXCollectionType.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/java/generics/TypeSwitch.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/ReflectionUtil.java
*
/hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/java/generics/ApproximatingTypeEnvironment.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/annotationfactory/AnnotationFactory.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/ReflectionManager.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/java/JavaXClass.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/java/generics/TypeUtils.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/java/generics/TypeEnvironmentFactory.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/java/JavaXMember.java
*
/hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/java/JavaReflectionManager.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/java/JavaAnnotationReader.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/AssertionFailure.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/java/JavaXType.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/Filter.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/util/StringHelper.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/Version.java
* /hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/util/ReflectHelper.java

*
/hibernate-commons-annotations-3-2-0-final-sources-2-jar/org/hibernate/annotations/common/reflection/XAnnotatedElement.java

1.391 guava 25.0-jre

1.391.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2011 The Guava Authors.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/package-info.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2012 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/
/*
  * This method was rewritten in Java from an intermediate step of the Murmur hash function in
  * http://code.google.com/p/smhasher/source/browse/trunk/MurmurHash3.cpp, which contained the
  * following header:
  *

```
 * MurmurHash3 was written by Austin Appleby, and is placed in the public domain. The author
 * hereby disclaims
copyright to this source code.
 */
```

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/base/SmallCharMatcher.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (C) 2017 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/
```

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/ImmutableLongArray.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/ImmutableDoubleArray.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/AbstractHashFunction.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ForwardingLock.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ForwardingCondition.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/ImmutableIntArray.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (C) 2009 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/
```

```
/**
* Outer class that exists solely to let us write {@code Partially.GwtIncompatible} instead of plain
* {@code GwtIncompatible}. This is more accurate for {@link Futures#catching}, which is available
* under GWT but with a slightly different signature.
*
* <p>We can't use {@code PartiallyGwtIncompatible} because then the GWT compiler
 wouldn't recognize
* it as a {@code GwtIncompatible} annotation. And for {@code Futures.catching}, we need the GWT
* compiler to autostrip the normal server method in order to expose the special, inherited GWT
* version.
*/
```

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/Partially.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (C) 2014 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/
```

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/math/Quantiles.java
* /guava-25-0-jre-sources-4-jar/com/google/common/eventbus/SubscriberRegistry.java
* /guava-25-0-jre-sources-4-jar/com/google/common/eventbus/Subscriber.java
* /guava-25-0-jre-sources-4-jar/com/google/common/eventbus/Dispatcher.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ListenerCallQueue.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/TrustedListenableFutureTask.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/MoreObjects.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (C) 2009 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
```

```
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
  * Not supported. <b>You are attempting to create a map that may contain a non-{@code Comparable}
  * key.</b> Proper calls will resolve to the version in {@code ImmutableSortedMap}, not this dummy
  * version.
  *
  * @throws UnsupportedOperationException always
  * @deprecated <b>Pass a key of type {@code Comparable}
 to use {@link
  *     ImmutableSortedMap#of(Comparable, Object)}.</b>
  */
```

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableSortedMapFauxverideShim.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (C) 2016 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/NetworkBuilder.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/MoreCollectors.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/AbstractValueGraph.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/ConfigurableMutableNetwork.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/graph/ElementOrder.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/ValueGraph.java

* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableMultisetGwtSerializationDependencies.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/GraphConnections.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/ConfigurableMutableValueGraph.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ArrayListMultimapGwtSerializationDependencies.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/MutableValueGraph.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/MapRetrievalCache.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/ConfigurableNetwork.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/ImmutableValueGraph.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/DirectedGraphConnections.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/UndirectedMultiNetworkConnections.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/graph/AbstractUndirectedNetworkConnections.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/HashMultimapGwtSerializationDependencies.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/ForwardingValueGraph.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/AbstractNetwork.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/ForwardingNetwork.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/AbstractGraph.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/ForwardingGraph.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/AbstractGraphBuilder.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/CollectCollectors.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/AbstractDirectedNetworkConnections.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/NetworkConnections.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/GraphBuilder.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/graph/GraphConstants.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/EndpointPairIterator.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/DirectedNetworkConnections.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/ValueGraphBuilder.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/ConfigurableValueGraph.java
* /guava-25-0-jre-sources-4-
jar/com/google/common/collect/LinkedHashMultimapGwtSerializationDependencies.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/MultiEdgesConnecting.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/ConfigurableMutableGraph.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/EndpointPair.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/EdgesConnecting.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/RangeGwtSerializationDependencies.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/MapIteratorCache.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/graph/UndirectedNetworkConnections.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Comparators.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/UndirectedGraphConnections.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/DirectedMultiNetworkConnections.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2015 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/CollectSpliterators.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/package-info.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableBiMapFauxverideShim.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2011 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/AtomicLongMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/WellBehavedMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/GwtTransient.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2008 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Joiner.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/Doubles.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/Shorts.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/MultiReader.java
* /guava-25-0-jre-sources-4-jar/com/google/thirdparty/publicsuffix/TrieParser.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/base/internal/Finalizer.java
* /guava-25-0-jre-sources-4-jar/com/google/common/escape/UnicodeEscaper.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/CharMatcher.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/FluentIterable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Converter.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/FileBackedOutputStream.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/AbstractCheckedFuture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/CheckedFuture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/Booleans.java
* /guava-25-0-jre-sources-4-jar/com/google/common/net/InetAddresses.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Stopwatch.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/Bytes.java
* /guava-25-0-jre-sources-4-jar/com/google/common/escape/Escaper.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/primitives/Chars.java
* /guava-25-0-jre-sources-4-jar/com/google/common/net/PercentEscaper.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/SequentialExecutor.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ListenableFutureTask.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/Longs.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/Ints.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/Floats.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2007 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
  * Returns an array containing all of the elements in the specified collection. This method
  * returns the elements in the order they are returned by the collection's iterator. The returned
  * array is "safe" in that no references to it are maintained by the collection. The caller is
  * thus free to modify the returned
 array.
  *
  * <p>This method assumes that the collection size doesn't change while the method is running.
  *
  * <p>TODO(kevinb): support concurrently modified collections?
  *
  * @param c the collection for which to return an array of elements
  */

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ObjectArrays.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2014 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/io/RecursiveDeleteOption.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/PredecessorsFunction.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/InsecureRecursiveDeleteException.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/ImmutableNetwork.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/graph/SuccessorsFunction.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/MutableGraph.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/Network.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/MutableNetwork.java

* /guava-25-0-jre-sources-4-jar/com/google/common/collect/TopKSelector.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/ImmutableGraph.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/Graph.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/Graphs.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (C) 2008 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/*
  * This method was rewritten in Java from an intermediate step of the Murmur hash function in
  * http://code.google.com/p/smhasher/source/browse/trunk/MurmurHash3.cpp, which contained the
  * following header:
  *
  * MurmurHash3 was written by Austin Appleby, and is placed in the public domain. The author
  * hereby
 disclaims copyright to this source code.
  */
```

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Hashing.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (C) 2018 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
```

* limitations under the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/JdkBackedImmutableMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/JdkBackedImmutableBiMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/IndexedImmutableSet.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2007 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/Primitives.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/LineReader.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Predicates.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Objects.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Function.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/base/Defaults.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/package-info.java
* /guava-25-0-jre-sources-4-jar/com/google/common/eventbus/AsyncEventBus.java
* /guava-25-0-jre-sources-4-jar/com/google/common/eventbus/Subscribe.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/ByteStreams.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/EnumMultiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/LittleEndianDataInputStream.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Predicate.java
* /guava-25-0-jre-sources-4-jar/com/google/common/eventbus/package-info.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/CountingOutputStream.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/MultiInputStream.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/FinalizableReference.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/FinalizableReferenceQueue.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/eventbus/AllowConcurrentEvents.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/Resources.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ListenableFuture.java

* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Interners.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Supplier.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/LineBuffer.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/FinalizableSoftReference.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/Closeables.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/AbstractFuture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/Flushables.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/CharStreams.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Suppliers.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/LittleEndianDataOutputStream.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/base/AbstractIterator.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Functions.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Throwables.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/package-info.java
* /guava-25-0-jre-sources-4-jar/com/google/common/eventbus/DeadEvent.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ExecutionList.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/FinalizablePhantomReference.java
* /guava-25-0-jre-sources-4-jar/com/google/common/eventbus/EventBus.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/HashBiMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/package-info.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/Files.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Charsets.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Preconditions.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/CountingInputStream.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/base/FinalizableWeakReference.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2008 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableMapKeySet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Tables.java

* /guava-25-0-jre-sources-4-jar/com/google/common/collect/RegularImmutableMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/EmptyImmutableListMultimap.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableMapEntrySet.java
* /guava-25-0-jre-sources-4-jar/com/google/thirdparty/publicsuffix/PublicSuffixPatterns.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableMultiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableEntry.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/CollectPreconditions.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/StandardTable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/HashBasedTable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableCollection.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/UnmodifiableIterator.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/PeekingIterator.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableListMultimap.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/collect/Range.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/TreeBasedTable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Serialization.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableMapValues.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableSortedSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/SingletonImmutableBiMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/RegularImmutableBiMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Platform.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Collections2.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/StandardRowSortedTable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableBiMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Table.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2015 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you
* may not use this file except in compliance with the License. You may
* obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
* implied. See the License for the specific language governing
* permissions and limitations under the License.
*/

Found in path(s):

* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Streams.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2011 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not
* use this file except in compliance with the License. You may obtain a copy of
* the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/SortedMultiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/SortedMultisets.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2011 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/
/*
  * This method was written by Doug Lea with assistance from members of JCP JSR-166 Expert Group
  * and released to the public domain, as explained at
  * http://creativecommons.org/licenses/publicdomain
  *
  * As of 2010/06/11, this method is identical to the (package private) hash method in OpenJDK 7's
  * java.util.HashMap
 class.
  */

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/Striped.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2017 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/BaseGraph.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/AbstractBaseGraph.java
* /guava-25-0-jre-sources-4-jar/com/google/common/graph/Traverser.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2018 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/JdkBackedImmutableMultiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/ImmutableSupplier.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/JdkBackedImmutableSet.java
No license file was found, but licenses were detected in source scan.

/*

* Written by Doug Lea with assistance from members of JCP JSR-166
* Expert Group and released to the public domain, as explained at
* http://creativecommons.org/publicdomain/zero/1.0/
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/AtomicDoubleArray.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/Striped64.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/LongAdder.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/Striped64.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/LongAdder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2015 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/MacHashFunction.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/AsyncCallable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/LittleEndianByteArray.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/InterruptibleTask.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/CombinedFuture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/AggregateFutureState.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/FarmHashFingerprint64.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/ReaderInputStream.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ConsumingQueueIterator.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/Platform.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2016 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*

* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/
/**
* Holder for extra methods of {@code Objects} only in web. Intended to be empty for regular
* version.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/base/ExtraObjectsMethodsForWeb.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2005 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/Reflection.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2010 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under

* the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ForwardingBlockingQueue.java
* /guava-25-0-jre-sources-4-jar/com/google/common/annotations/package-info.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/package-info.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Equivalence.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ThreadFactoryBuilder.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Strings.java
* /guava-25-0-jre-sources-4-jar/com/google/common/net/package-info.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/SortedLists.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/UncaughtExceptionHandlers.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ContiguousSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/Atomics.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/Monitor.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ListeningExecutorService.java
* /guava-25-0-jre-sources-4-jar/com/google/common/annotations/Beta.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Ascii.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2011 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/UncheckedExecutionException.java
* /guava-25-0-jre-sources-4-jar/com/google/common/math/LongMath.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/WrappingExecutorService.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/AbstractScheduledService.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/net/HttpHeaders.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ExecutionError.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/AbstractListeningExecutorService.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Present.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/RegularImmutableMultiset.java

* /guava-25-0-jre-sources-4-jar/com/google/common/net/MediaType.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/EmptyContiguousSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/BloomFilterStrategies.java
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/Types.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ForwardingListeningExecutorService.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/ForwardingLoadingCache.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Ticker.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/hash/AbstractNonStreamingHashFunction.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Absent.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/RemovalCause.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/AbstractLoadingCache.java
* /guava-25-0-jre-sources-4-jar/com/google/common/math/BigIntegerMath.java
* /guava-25-0-jre-sources-4-jar/com/google/common/math/MathPreconditions.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/AbstractCompositeHashFunction.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/Hashing.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/RemovalListener.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/UnsignedLongs.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/BoundType.java
* /guava-25-0-jre-sources-4-jar/com/google/common/net/HostAndPort.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/TreeRangeSet.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/primitives/UnsignedInteger.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/UnsignedLong.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/HashingOutputStream.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractSortedMultiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/HashFunction.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/AsyncFunction.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/RemovalNotification.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/Murmur3_128HashFunction.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/CacheLoader.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/Cache.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ForwardingExecutorService.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/LoadingCache.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/PrimitiveSink.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/Uninterruptibles.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/CacheStats.java
* /guava-25-0-jre-sources-4-jar/com/google/common/math/package-info.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/DescendingImmutableSortedMultiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/Funnel.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/CycleDetectingLockFactory.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/ForwardingCache.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ListeningScheduledExecutorService.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/package-info.java
* /guava-25-0-jre-sources-4-jar/com/google/common/math/DoubleUtils.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/Funnels.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/Crc32cHashFunction.java

*
/guava-25-0-jre-sources-4-jar/com/google/common/hash/AbstractStreamingHasher.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/UnsignedInts.java
* /guava-25-0-jre-sources-4-jar/com/google/common/math/IntMath.java
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/TypeParameter.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/FutureCallback.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/AbstractHasher.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/RemovalListeners.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/Hasher.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/HashCode.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/AbstractCache.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Optional.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Enums.java
* /guava-25-0-jre-sources-4-jar/com/google/common/math/DoubleMath.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/CacheBuilderSpec.java
*
/guava-25-0-jre-sources-4-jar/com/google/common/cache/Weigher.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Queues.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/ParseRequest.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/Murmur3_32HashFunction.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/BloomFilter.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ForwardingCheckedFuture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/PairwiseEquivalence.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/RegularContiguousSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/FunctionalEquivalence.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/MessageDigestHashFunction.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2009 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the
* License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND,
either
* express or implied. See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableSortedAsList.java
No license file was found, but licenses were detected in source scan.

/*

* Copyright (C) 2009 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableTable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableSortedSetFauxverideShim.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/SingletonImmutableList.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/RegularImmutableList.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/collect/ArrayTable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractIndexedListIterator.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableAsList.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ComputationException.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ComparisonChain.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingTable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableSetMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableEnumSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/EmptyImmutableSetMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/RegularImmutableSortedSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableClassToInstanceMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/DiscreteDomain.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/collect/SingletonImmutableTable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableSortedMap.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2009 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either

express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/io/ByteArrayDataInput.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/CacheBuilder.java
* /guava-25-0-jre-sources-4-jar/com/google/common/annotations/GwtCompatible.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/LocalCache.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/ByteArrayDataOutput.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/AbstractIdleService.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Splitter.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/SparseImmutableTable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/escape/Escapers.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/SettableFuture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/net/HostSpecifier.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/DenseImmutableTable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/SignedBytes.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ForwardingListenableFuture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/TypeResolver.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/AbstractExecutionThreadService.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/LineProcessor.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/Service.java
* /guava-25-0-jre-sources-4-jar/com/google/common/primitives/UnsignedBytes.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ForwardingFluentFuture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/net/InternetDomainName.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/Callables.java
* /guava-25-0-jre-sources-4-jar/com/google/common/html/HtmlEscapers.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/MapMakerInternalMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Cut.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/JdkFutureAdapters.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/AbstractService.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/ByteProcessor.java
* /guava-25-0-jre-sources-4-jar/com/google/common/net/UrlEscapers.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/escape/ArrayBasedUnicodeEscaper.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Platform.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/ReferenceEntry.java
* /guava-25-0-jre-sources-4-jar/com/google/common/annotations/GwtIncompatible.java
* /guava-25-0-jre-sources-4-jar/com/google/common/escape/ArrayBasedEscaperMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/xml/XmlEscapers.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/MapMaker.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ForwardingFuture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/escape/ArrayBasedCharEscaper.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/RegularImmutableTable.java

* /guava-25-0-jre-sources-4-jar/com/google/common/escape/Platform.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2013 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/WrappingScheduledExecutorService.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/CharSequenceReader.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/Utf8.java
* /guava-25-0-jre-sources-4-jar/com/google/common/eventbus/SubscriberExceptionContext.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/base/Verify.java
* /guava-25-0-jre-sources-4-jar/com/google/thirdparty/publicsuffix/PublicSuffixType.java
* /guava-25-0-jre-sources-4-jar/com/google/common/eventbus/SubscriberExceptionHandler.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractTable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/FilteredMultimapValues.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/HashingInputStream.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/VerifyException.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/Runnables.java
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/TypeVisitor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2011 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the
* License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND,
either
* express or implied. See the License for the specific language governing permissions and
* limitations under the License.

*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Count.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/SortedIterables.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingSortedMultiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/RangeSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/GeneralRange.java
*
/guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableSortedMultisetFauxverideShim.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/RegularImmutableSortedMultiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractRangeSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/SortedIterable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableSortedMultiset.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2012 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractNavigableMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/EvictingQueue.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/FilteredEntryMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/UnmodifiableSortedMultiset.java
*
/guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractSortedKeySortedSetMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/FilteredMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/CompactHashSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/TreeRangeMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingDeque.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/TransformedIterator.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/CompactLinkedHashMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingImmutableList.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/TransformedListIterator.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingBlockingDeque.java

* /guava-25-0-jre-sources-4-jar/com/google/common/collect/TreeTraverser.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/CompactHashMap.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/collect/FilteredEntrySetMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/DescendingMultiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/RangeMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/DescendingImmutableSortedSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableEnumMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/FilteredSetMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/CompactLinkedHashSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingNavigableSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingImmutableSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/FilteredKeyListMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/SortedMultisetBridge.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ForwardingBlockingDeque.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/RegularImmutableAsList.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AllEqualOrdering.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingImmutableMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/FilteredKeySetMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingNavigableMap.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2007 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/CompoundOrdering.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ConcurrentHashMultiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ComparatorOrdering.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractMultiset.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/collect/ReverseNaturalOrdering.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableSet.java

* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingSortedSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingListIterator.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/TreeMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/LinkedListMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingSortedMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Iterators.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ExplicitOrdering.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/LexicographicalOrdering.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Multiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/LinkedHashMultiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/SetMultimap.java
*
/guava-25-0-jre-sources-4-jar/com/google/common/collect/package-info.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/UsingToStringOrdering.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/HashMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/NaturalOrdering.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/SortedSetMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/NullsLastOrdering.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Multisets.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/LinkedHashMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Maps.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingConcurrentMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingMultiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Interner.java
*
/guava-25-0-jre-sources-4-jar/com/google/common/collect/RegularImmutableSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Iterables.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingCollection.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/MapDifference.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractBiMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/EnumHashBiMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/BiMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ArrayListMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingMapEntry.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractIterator.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractListMultimap.java
*
/guava-25-0-jre-sources-4-jar/com/google/common/collect/HashMultiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableList.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Synchronized.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ListMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingIterator.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/MutableClassToInstanceMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractSortedSetMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ClassToInstanceMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractSetMultimap.java

* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingQueue.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/NullsFirstOrdering.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Multimaps.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingObject.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/collect/Multimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Ordering.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractMapBasedMultiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Sets.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/SingletonImmutableSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/Lists.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ByFunctionOrdering.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractMapBasedMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/TreeMultiset.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractMapEntry.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingList.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/collect/EnumBiMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ReverseOrdering.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2007 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/
/*
  * This following method is a modified version of one found in
  * http://gee.cs.oswego.edu/cgi-bin/viewcvs.cgi/jsr166/src/test/tck/AbstractExecutorServiceTest.java?revision=1.30
  * which contained the following notice:
  *
  * Written by Doug Lea with assistance from members of JCP JSR-166 Expert Group and released to
  *
 the public domain, as explained at http://creativecommons.org/publicdomain/zero/1.0/
  *
  * Other contributors include Andrew Wright, Jeffrey Hayes, Pat Fisher, Mike Judd.
  */

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/MoreExecutors.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2016 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/base/PatternCompiler.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/CommonPattern.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/CommonMatcher.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/JdkPattern.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2012 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/math/PairedStats.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/RateLimiter.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableRangeMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/TypeToInstanceMap.java
*

/guava-25-0-jre-sources-4-jar/com/google/common/math/PairedStatsAccumulator.java
* /guava-25-0-jre-sources-4-jar/com/google/common/math/StatsAccumulator.java
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/Parameter.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/SipHashFunction.java
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/AbstractInvocationHandler.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/ByteSource.java
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/ClassPath.java
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/Element.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/FileWriteMode.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/SmoothRateLimiter.java
* /guava-25-0-jre-sources-4-jar/com/google/common/html/package-info.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/ByteSink.java
* /guava-25-0-jre-sources-4-jar/com/google/common/math/Stats.java
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/MutableTypeToInstanceMap.java
*
/guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableRangeSet.java
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/package-info.java
* /guava-25-0-jre-sources-4-jar/com/google/common/cache/LongAddable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/CharSink.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/LongAddable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ServiceManager.java
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/Invokable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/FilteredKeyMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/BaseEncoding.java
* /guava-25-0-jre-sources-4-jar/com/google/common/escape/package-info.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/StandardSystemProperty.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ListenableScheduledFuture.java
*
/guava-25-0-jre-sources-4-jar/com/google/common/cache/LongAddables.java
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/ImmutableTypeToInstanceMap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/xml/package-info.java
* /guava-25-0-jre-sources-4-jar/com/google/common/math/LinearTransformation.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/AbstractByteHasher.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/Closer.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/ChecksumHashFunction.java
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/TypeCapture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/CartesianList.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/CharSource.java
* /guava-25-0-jre-sources-4-jar/com/google/common/hash/LongAddables.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2010 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*

* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/UnmodifiableListIterator.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/RowSortedTable.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/AbstractSequentialIterator.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingSortedSetMultimap.java
*
 /guava-25-0-jre-sources-4-jar/com/google/common/collect/SortedMapDifference.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingImmutableCollection.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/MinMaxPriorityQueue.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingSetMultimap.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ForwardingListMultimap.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2013 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/io/MoreFiles.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/ImmutableMapEntry.java
* /guava-25-0-jre-sources-4-jar/com/google/common/collect/MultimapBuilder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2006 The Guava Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except

* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/FuturesGetChecked.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/ImmediateFuture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/escape/CharEscaperBuilder.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/AbstractCatchingFuture.java
*
/guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/SimpleTimeLimiter.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/UncheckedTimeoutException.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/AggregateFuture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/annotations/VisibleForTesting.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/PatternFilenameFilter.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/GwtFluentFutureCatchingSpecialization.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/FakeTimeLimiter.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/FluentFuture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/escape/CharEscaper.java
* /guava-25-0-jre-sources-4-jar/com/google/common/base/CaseFormat.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/CollectionFuture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/GwtFuturesCatchingSpecialization.java
*
/guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/TimeLimiter.java
* /guava-25-0-jre-sources-4-jar/com/google/common/reflect/TypeToken.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/AbstractTransformFuture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/TimeoutFuture.java
* /guava-25-0-jre-sources-4-jar/com/google/common/io/AppendableWriter.java
* /guava-25-0-jre-sources-4-jar/com/google/common/util/concurrent/Futures.java

1.392 deep-diff 0.3.8

1.392.1 Available under license :

Copyright (c) 2011-2013 Phillip Clark

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.393 netty-codec-http 4.1.17.Final

1.393.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/cookie/CookieUtil.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/CookieUtil.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpUtil.java
*
/netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/cookie/ServerCookieEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpScheme.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/cookie/ServerCookieDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/cookie/ClientCookieDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/cookie/package-info.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/cookie/CookieHeaderNames.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/EmptyHttpHeaders.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/cookie/Cookie.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/cookie/CookieDecoder.java

* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/cookie/ClientCookieEncoder.java
*
 /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/cookie/CookieEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpExpectationFailedEvent.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/CombinedHttpHeaders.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/rtsp/RtspEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/cookie/DefaultCookie.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/rtsp/RtspDecoder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyFrameDecoderDelegate.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/ClientCookieEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyFrameEncoder.java
*
 /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/DeflateEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/DeflateFrameServerExtensionHandshaker.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/rtsp/RtspHeaderNames.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpHeaderValues.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionUtil.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpHeadersEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketClientExtensionHandler.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockZlibDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpMessageUtil.java
*
 /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/DeflateDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-

jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerFrameDeflateEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerMessageDeflateClientExtensionHandshaker.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketServerExtensionHandler.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyFrameDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerMessageDeflateServerExtensionHandshaker.java
*
/netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/rtsp/RtspHeaderValues.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/package-info.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerMessageDeflateDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketServerExtensionHandshaker.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketClientExtensionHandshaker.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerFrameDeflateDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/extensions/package-info.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/WebSocketClientCompressionHandler.java
*
/netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/WebSocketServerCompressionHandler.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtension.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpHeaderNames.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpStatusClass.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerMessageDeflateEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyProtocolException.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketServerExtension.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionDecoder.java
*
/netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionData.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketClientExtension.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpChunkedInput.java

* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockRawDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/extensions/compression/DeflateFrameClientExtensionHandshaker.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyFrameCodec.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/Utf8FrameValidator.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/ServerCookieEncoder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
// (BSD License: http://www.opensource.org/licenses/bsd-license)
// All rights reserved.
// Redistribution and use in source and binary forms, with or
// * Redistributions of source code must retain the above
// copyright notice, this list of conditions and the
// following disclaimer.
// * Redistributions
 in binary form must reproduce the above
// following disclaimer in the documentation and/or other
// * Neither the name of the Webbit nor the names of

Found in path(s):
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/WebSocket13FrameDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/WebSocket07FrameDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/WebSocket08FrameDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/WebSocket07FrameEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/WebSocket08FrameEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/WebSocket13FrameEncoder.java

No license file was found, but licenses were detected in source scan.

~ Copyright 2012 The Netty Project
~
~ The Netty Project licenses this file to you under the Apache License,
~ version 2.0 (the "License"); you may not use this file except in compliance
~ with the License. You may obtain a copy of the License at:
~
~ http://www.apache.org/licenses/LICENSE
2.0
~
~ Unless required by applicable law or agreed to in writing, software
~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
~ License for the specific language governing permissions and limitations
~ under the License.

Found in path(s):
* /netty-codec-http-4-1-17-final-sources-1-jar/META-INF/maven/io.netty/netty-codec-http/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpServerKeepAliveHandler.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/FileUploadUtil.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketChunkedInput.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,

* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketFrameDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyVersion.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/DefaultSpdyStreamFrame.java
*
 /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyStreamFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyFrame.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketProtocolHandler.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/DefaultSpdyHeadersFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/DefaultSpdyGoAwayFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyPingFrame.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketFrameAggregator.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/DefaultSpdySynReplyFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/DefaultSpdyWindowUpdateFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdySessionHandler.java
*
 /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/FullHttpResponse.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdySettingsFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockRawEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/ComposedLastHttpContent.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyDataFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyCodecUtil.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/DefaultSpdyPingFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyHttpDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/DefaultSpdyDataFrame.java
*
 /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketClientProtocolHandler.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/FullHttpRequest.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockZlibEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/DefaultSpdyHeaders.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdySynReplyFrame.java

* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/DefaultFullHttpResponse.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyGoAwayFrame.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketClientProtocolHandshakeHandler.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdySessionStatus.java
*
/netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/DefaultFullHttpRequest.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyHeadersFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyHeaders.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyRstStreamFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyStreamStatus.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockJZlibEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdySynStreamFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/DefaultSpdyRstStreamFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/DefaultSpdySynStreamFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/cors/package-info.java
*
/netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyWindowUpdateFrame.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketFrameEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyHttpCodec.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/FullHttpMessage.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version
* 2.0 (the "License"); you may not use this file except in compliance with the
* License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/cors/CorsConfig.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/cors/CorsHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*

* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpClientUpgradeHandler.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpServerUpgradeHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/InterfaceHttpPostRequestDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/HttpPostMultipartRequestDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/CookieDecoder.java
*
 /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpContentDecompressor.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/rtsp/RtspVersions.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/DefaultHttpDataFactory.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/WebSocket00FrameEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/WebSocketVersion.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/QueryStringDecoder.java

* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/PingWebSocketFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/BinaryWebSocketFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpContentDecoder.java
*
/netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyHttpResponseStreamIdHandler.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpRequest.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpObject.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpConstants.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/Cookie.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/DefaultHttpMessage.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/rtsp/RtspObjectEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/rtsp/package-info.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/multipart/HttpPostStandardRequestDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpResponseEncoder.java
*
/netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshaker.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/ContinuationWebSocketFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/InterfaceHttpData.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshaker00.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpObjectDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/rtsp/RtspRequestEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/AbstractDiskHttpData.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/WebSocketFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/HttpPostRequestDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/FileUpload.java
*
/netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/package-info.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshaker08.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/rtsp/RtspHeaders.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/CaseIgnoringComparator.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketHandshakeException.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketServerProtocolHandshakeHandler.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/QueryStringEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshakerFactory.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshaker07.java
*
/netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpRequestEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/PongWebSocketFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/HttpData.java

* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/package-info.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/DiskFileUpload.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/MemoryFileUpload.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/Attribute.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/DefaultLastHttpContent.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshaker00.java
*
/netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/package-info.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/rtsp/RtspMethods.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/TextWebSocketFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/DefaultSpdySettingsFrame.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshaker.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpMessage.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshaker07.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyHttpHeaders.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpHeaderDateFormat.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocket00FrameDecoder.java
*
/netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketServerProtocolHandler.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpContentEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshaker13.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/HttpPostRequestEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpObjectEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpClientCodec.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/rtsp/RtspResponseStatuses.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/DefaultHttpObject.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/DiskAttribute.java
*
/netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/DefaultHttpRequest.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/DefaultHttpHeaders.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/DefaultCookie.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpVersion.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/MemoryAttribute.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/AbstractMemoryHttpData.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdyHttpEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/AbstractHttpData.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/DefaultHttpContent.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/DefaultHttpResponse.java
*
/netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/package-info.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/rtsp/RtspObjectDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-

jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshaker13.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/rtsp/RtspResponseEncoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/MixedFileUpload.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/HttpDataFactory.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/InternalAttribute.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpResponseStatus.java
* /netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshaker08.java
*
/netty-codec-http-4-1-17-final-sources-1-
jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshakerFactory.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/rtsp/RtspResponseDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/WebSocketUtil.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpMethod.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/CloseWebSocketFrame.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpHeaders.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpServerCodec.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/spdy/SpdySession.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/LastHttpContent.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/HttpPostBodyUtil.java
*
/netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpResponseDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/multipart/MixedAttribute.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpContent.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpResponse.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpContentCompressor.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpObjectAggregator.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/rtsp/RtspRequestDecoder.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpRequestDecoder.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
```

Found in path(s):

* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/HttpServerExpectContinueHandler.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/WebSocketScheme.java
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/ReadOnlyHttpHeaders.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/*
* Adaptation of http://bjoern.hoehrmann.de/utf-8/decoder/dfa/
*
* Copyright (c) 2008-2009 Bjoern Hoehrmann <bjoern@hoehrmann.de>
*
* Permission is hereby granted, free of charge, to any person obtaining a copy of this software
* and associated documentation files (the "Software"), to deal
 in the Software without restriction,
* including without limitation the rights to use, copy, modify, merge, publish, distribute,
* sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is
* furnished to do so, subject to the following conditions:
*
* The above copyright notice and this permission notice shall be included in all copies or
* substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING
* BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
* NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
* DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
* OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/

Found in path(s):

* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/websocketx/Utf8Validator.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version
* 2.0 (the "License"); you may not use this file except in compliance with the
* License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-codec-http-4-1-17-final-sources-1-jar/io/netty/handler/codec/http/cors/CorsConfigBuilder.java

1.394 jackson-core-asl 1.9.13

1.394.1 Available under license :

This product currently only contains code developed by authors
of specific components, as identified by the source code files;
if such notes are missing files have been created by
Tatu Saloranta.

For additional credits (generally to people who reported problems)
see CREDITS file.
This copy of Jackson JSON processor is licensed under the
Apache (Software) License, version 2.0 ("the License").
See the License for details about distribution rights, and the
specific rights regarding derivate works.

You may obtain a copy of the License at:

http://www.apache.org/licenses/

A copy is also included with both the the downloadable source code package
and jar that contains class bytecodes, as file "ASL 2.0". In both cases,
that file should be located next to this file: in source distribution
the location should be "release-notes/asl"; and in jar "META-INF/"

1.395 javassist 3.12.0.GA

1.395.1 Available under license :

Found license 'GNU Lesser General Public License' in '* Copyright (C) 1999-2007 Shigeru Chiba. All Rights Reserved. * The contents of this file are subject to the Mozilla Public License Version * 1.1 (the "License"); you may not use this file except in compliance with * the License. Alternatively, the contents of this file may be used under * the terms of the GNU Lesser General Public License Version 2.1 or later. * Software distributed under the License is distributed on an "AS IS" basis, + " All Rights Reserved.");'

Found license 'GNU Lesser General Public License' in '* Copyright (C) 2004 Bill Burke. All Rights Reserved. * The contents of this file are subject to the Mozilla Public License Version * 1.1 (the "License"); you may not use this file except in compliance with * the License. Alternatively, the contents of this file may be used under * the terms of the GNU Lesser General Public License Version 2.1 or later. * Software distributed under the License is distributed on an "AS IS" basis,'

Found license 'GNU Lesser General Public License' in '* Copyright (C) 1999-2009 Shigeru Chiba. All Rights Reserved. * The contents of this file are subject to the Mozilla Public License Version * 1.1 (the "License"); you may not use this file except in compliance with * the License. Alternatively, the contents of this file may be used under * the terms of the GNU Lesser General Public License Version 2.1 or later. * Software distributed under the License is distributed on an "AS IS" basis,'

Found license 'GNU Lesser General Public License' in '* Copyright (C) 1999-2010 Shigeru Chiba. All Rights Reserved. * The contents of this file are subject to the Mozilla Public License Version * 1.1 (the "License"); you may not use this file except in compliance with * the License. Alternatively, the contents of this file may be used under * the terms of the GNU Lesser General Public License Version 2.1 or later. * Software distributed under the License is distributed on an "AS IS" basis,'

Found license 'GNU Lesser General Public License' in '* Copyright (C) 1999-2007 Shigeru Chiba, and others. All Rights Reserved. * The contents of this file are subject to the Mozilla Public License Version * 1.1 (the "License"); you may not use this file except in compliance with * the License. Alternatively, the contents of this file may be used under * the terms of the GNU Lesser General Public License Version 2.1 or later. * Software distributed under the License is distributed on an "AS IS" basis,'

Found license 'GNU Lesser General Public License' in '* Copyright (C) 1999-2007 Shigeru Chiba. All Rights Reserved. * The contents of this file are subject to the Mozilla Public License Version * 1.1 (the "License"); you may not use this file except in compliance with * the License. Alternatively, the contents of this file may be used under * the terms of the GNU Lesser General Public License Version 2.1 or later. * Software distributed under the License is distributed on an "AS IS" basis,'

1.396 bean-validation-api 1.0.0.GA

1.396.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*

* JBoss, Home of Professional Open Source

* Copyright 2009, Red Hat, Inc. and/or its affiliates, and individual contributors

* by the @authors tag. See the copyright.txt in the distribution for a

* full listing of individual contributors.

*

* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/constraints/Size.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/constraints/AssertFalse.java
*
 /validation-api-1-0-0-ga-sources-1-jar/javax/validation/ConstraintValidatorContext.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/Constraint.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/metadata/BeanDescriptor.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/UnexpectedTypeException.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/ConstraintValidatorFactory.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/ConstraintDeclarationException.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/constraints/AssertTrue.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/Configuration.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/ConstraintValidator.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/constraints/Digits.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/Path.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/GroupDefinitionException.java
*
 /validation-api-1-0-0-ga-sources-1-jar/javax/validation/groups/package-info.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/Payload.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/TraversableResolver.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/bootstrap/ProviderSpecificBootstrap.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/constraints/NotNull.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/ValidationException.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/ReportAsSingleViolation.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/constraints/Max.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/constraints/Past.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/MessageInterpolator.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/constraints/Pattern.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/constraints/Null.java
*
 /validation-api-1-0-0-ga-sources-1-jar/javax/validation/Validation.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/groups/Default.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/metadata/ElementDescriptor.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/metadata/Scope.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/spi/BootstrapState.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/ValidatorFactory.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/spi/ConfigurationState.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/Valid.java

* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/constraints/DecimalMax.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/OverridesAttribute.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/constraints/DecimalMin.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/constraints/Min.java
*
/validation-api-1-0-0-ga-sources-1-jar/javax/validation/ConstraintViolationException.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/metadata/PropertyDescriptor.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/ValidatorContext.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/ConstraintDefinitionException.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/spi/ValidationProvider.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/ConstraintViolation.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/Validator.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/bootstrap/GenericBootstrap.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/ValidationProviderResolver.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/constraints/Future.java
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/metadata/ConstraintDescriptor.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2009, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-0-0-ga-sources-1-jar/javax/validation/GroupSequence.java

1.397 xml-commons 1.3.4

1.397.1 Available under license :

Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source"
form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely
link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean
Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce,

prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and
You must cause any modified files to carry prominent notices stating that You changed the files; and
You must retain, in the Source form of any Derivative Works that You distribute,
all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the
NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.
5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the
trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR

CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor
harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: HOW TO APPLY THE APACHE LICENSE TO YOUR WORK
To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless
required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.398 springsourceapachexmlresolver 1.2.0

1.398.1 Available under license :

Apache XML Commons Resolver
Copyright 2006 The Apache Software Foundation.

This product includes software developed at
The Apache Software Foundation http://www.apache.org/

Portions of this code are derived from classes placed in the
public domain by Arbortext on 10 Apr 2000. See:
http://www.arbortext.com/customer_support/updates_and_technical_notes/catalogs/docs/README.htm

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii)
beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their

Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as
of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained
within such NOTICE file, excluding those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names
of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole

responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed
under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.399 springsource-org-apache-xerces 2.9.1

1.399.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*

```
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
   * Checks if this content model has had its min/maxOccurs values reduced for
   * purposes of speeding up UPA.  If
 so, this content model should not be used
   * for any purpose other than checking unique particle attribution
   *
   * @return a boolean that says whether this content has been compacted for UPA
   */
```

Found in path(s):
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/XSCMValidator.java
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/DayDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/xs/traversers/XSDKeyrefTraverser.java
*
 /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSModelGroupImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/DateTimeDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/xs/traversers/XSDUniqueOrKeyTraverser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/XSSimpleTypeDecl.java

* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XMLSchemaValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/xs/traversers/XSAttributeChecker.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/TimeDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/DurationDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/YearMonthDV.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/MonthDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/MonthDayDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/AbstractDateTimeDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/YearDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/DateDV.java
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
  * DOM Level 3 LS CR - Experimental.
    * Create a new <code>LSParser</code>. The newly constructed parser may
    *
 then be configured by means of its <code>DOMConfiguration</code>
    * object, and used to parse documents by means of its <code>parse</code>
    *  method.
    * @param mode  The <code>mode</code> argument is either
    *   <code>MODE_SYNCHRONOUS</code> or <code>MODE_ASYNCHRONOUS</code>, if
    *   <code>mode</code> is <code>MODE_SYNCHRONOUS</code> then the
    *   <code>LSParser</code> that is created will operate in synchronous
    *   mode, if it's <code>MODE_ASYNCHRONOUS</code> then the
    *   <code>LSParser</code> that is created will operate in asynchronous
    *   mode.
    * @param schemaType  An absolute URI representing the type of the schema
    *   language used during the load of a <code>Document</code> using the
    *   newly created <code>LSParser</code>. Note that no lexical checking
```

```
    *   is done on the absolute URI. In order to create a
    *   <code>LSParser</code> for any kind of schema types (i.e. the
    *   LSParser will be free to use any schema
 found), use the value
    *   <code>null</code>.
    * <p ><b>Note:</b>    For W3C XML Schema [<a href='http://www.w3.org/TR/2001/REC-xmlschema-1-
20010502/'>XML Schema Part 1</a>]
    *   , applications must use the value
    *   <code>"http://www.w3.org/2001/XMLSchema"</code>. For XML DTD [<a
href='http://www.w3.org/TR/2000/REC-xml-20001006'>XML 1.0</a>],
    *   applications must use the value
    *   <code>"http://www.w3.org/TR/REC-xml"</code>. Other Schema languages
    *   are outside the scope of the W3C and therefore should recommend an
    *   absolute URI in order to use this method.
    * @return  The newly created <code>LSParser</code> object. This
    *   <code>LSParser</code> is either synchronous or asynchronous
    *   depending on the value of the <code>mode</code> argument.
    * <p ><b>Note:</b>    By default, the newly created <code>LSParser</code>
    *    does not contain a <code>DOMErrorHandler</code>, i.e. the value of
    *   the "<a href='http://www.w3.org/TR/2003/WD-DOM-Level-3-Core-20030609/core.html#parameter-error-
handler'>
     *   error-handler</a>" configuration parameter is <code>null</code>. However, implementations
    *   may provide a default error handler at creation time. In that case,
    *   the initial value of the <code>"error-handler"</code> configuration
    *   parameter on the new created <code>LSParser</code> contains a
    *   reference to the default error handler.
    * @exception DOMException
    *    NOT_SUPPORTED_ERR: Raised if the requested mode or schema type is
    *   not supported.
  */
```

Found in path(s):
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/CoreDOMImplementationImpl.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (c) 2001 World Wide Web Consortium,
* (Massachusetts Institute of Technology, Institut National de
* Recherche en Informatique et en Automatique, Keio University). All
* Rights Reserved. This program is distributed under the W3C's Software
* Intellectual Property License. This program is distributed in the
* hope that it will be useful, but WITHOUT ANY WARRANTY; without even
* the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
* PURPOSE.
* See W3C License http://www.w3.org/Consortium/Legal/ for more details.
*/
```

Found in path(s):
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASAttributeDeclaration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/DOMASBuilder.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/DOMASWriter.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASEntityDeclaration.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/DOMASException.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASNotationDeclaration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASObjectList.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/DOMImplementationAS.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASContentModel.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASNamedObjectMap.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/ElementEditAS.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/NodeEditAS.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASDataType.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/DocumentAS.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASObject.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/CharacterDataEditAS.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASElementDeclaration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/DocumentEditAS.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom3/as/ASModel.java
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
    * used to check the 3 constraints against each complex type
    * (should be each model group):
    * Unique Particle
 Attribution, Particle Derivation (Restriction),
    * Element Declrations Consistent.
    */
```

Found in path(s):
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSConstraints.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2000 World Wide Web Consortium,
* (Massachusetts Institute of Technology, Institut National de
* Recherche en Informatique et en Automatique, Keio University). All
* Rights Reserved. This program is distributed under the W3C's Software
* Intellectual Property License. This program is distributed in the
* hope that it will be useful, but WITHOUT ANY WARRANTY; without even
* the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
* PURPOSE. See W3C License http://www.w3.org/Consortium/Legal/ for more
* details.
*/

Found in path(s):
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/w3c/dom/html/HTMLDOMImplementation.java
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
// Unique Particle Attribution

Found in path(s):
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/XSDFACM.java
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with

* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLDocumentImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/html/dom/HTMLTableSectionElementImpl.java
*
 /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSAttributeDecl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLSimpleType.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/AttrImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/SAXInputSource.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/jaxp/validation/WeakReferenceXMLSchema.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLMenuElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/xs/models/XSCMRepeatingLeaf.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/SchemaDOM.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/validation/EntityState.java
*
 /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLFontElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLOneventElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/jaxp/validation/XSGrammarPoolContainer.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/RangeExceptionImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/NotationImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLTableElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/xni/XMLDocumentFragmentHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLBElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/XSDateTime.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/PSVIProvider.java
*
 /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/xinclude/MultipleScopeNamespaceSupport.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XML11NSDTDValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/LocatorProxy.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/jaxp/datatype/XMLGregorianCalendarImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLDoElement.java

* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLSelectElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/NOTATIONDatatypeValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xpointer/XPointerMessageFormatter.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/SchemaDOMParser.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/SchemaDateTimeException.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/CMBuilder.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLFrameElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/XSFacets.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLAttributeDecl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DeferredAttrNSImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLFieldSetElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSImplementationImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/AbstractDOMParser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/PSVIDocumentImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/io/UCSReader.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLEmElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLPElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSNamespaceItem.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/SerializerFactory.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/IDDatatypeValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLHeadElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/XIncludeParserConfiguration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DeferredTextImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/DefaultDocument.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/XMLDocumentParser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSLoaderImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/XML11DocumentScannerImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSAttributeGroupDecl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLBodyElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/AttrNSImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/DFAContentModel.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/SecurityConfiguration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLNSDTDValidator.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLOptionElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/Field.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSAttributeUseImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/DTDDVFactory.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/XMLSerializer.java

* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/DOMEntityResolverWrapper.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/XMLScanner.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/xni/grammars/XMLGrammarDescription.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/NamedNodeMapImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/parsers/StandardParserConfiguration.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/EmptyXMLSchema.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSMessageFormatter.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/DayTimeDurationDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/TypeValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/FullDVFactory.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/jaxp/validation/JAXPValidationMessageFormatter.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/dom/PSVIDOMImplementationImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/XMLSymbols.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLDoElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLBRElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/DTDDVFactoryImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLOptgroupElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/Util.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSComplexTypeDefinition.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/DVFactoryException.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/HTTPInputSource.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/AbstractSAXParser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/NamespaceSupport.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLIsIndexElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSModel.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLRefreshElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/io/MalformedByteSequenceException.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLTableElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/xs/traversers/XSDElementTraverser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/KeyRef.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/Augmentations.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/SAXParser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLTrElement.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/XSDecimal.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DOMLocatorImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/BasicParserConfiguration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/XMLErrorReporter.java

* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/grammars/XSGrammar.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DeferredNode.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/UnparsedEntityHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLTitleElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xinclude/XInclude11TextReader.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLTableCellElementImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSIDCDefinition.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/dom/DOMImplementationSourceImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/XMLString.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/SimpleLocator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XML11DTDProcessor.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/xs/SchemaNamespaceSupport.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/XML11Configurable.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/ValidatedInfo.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLHeadElement.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/EntityResolverWrapper.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/dom/DeferredDOMImplementationImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/AttributePSVImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLBigElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/AttributesProxy.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DeepNodeListImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DocumentTypeImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DOMErrorImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSDDescription.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/XML11NamespaceBinder.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/AnyURIDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/xs/traversers/XSDAttributeGroupTraverser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLMapElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/Version.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/DOMSerializerImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/events/MutationEventImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLAccessElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DocumentImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/SchemaDVFactory.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/SAXParserImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xpath/XPathException.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/DTDParser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/util/HexBin.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/PSVIElementNSImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-

jar/org/apache/xerces/jaxp/SchemaValidatorConfiguration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/TextSerializer.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLDocumentImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/ExternalSubsetResolver.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/IDDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/XSNamedMapImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/XML11Char.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLMetaElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/html/dom/HTMLTableCaptionElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/xinclude/XIncludeMessageFormatter.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DeferredEntityImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xinclude/XIncludeTextReader.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/ValidatorImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/XML11EntityScanner.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/ProcessingInstructionImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/XSNamedMap4Types.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLAreaElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/AttrImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/XML11Configuration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLStrongElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLParseException.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/events/EventImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/XMLGrammarPoolImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLIElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLDListElementImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/StringList.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xpath/XPath.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/NamedNodeMapImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLBuilder.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLBaseFontElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/dv/dtd/StringDatatypeValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLAppletElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/ValidationContext.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLGoElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLTdElementImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/jaxp/validation/DOMDocumentHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSElementDeclaration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/RangeImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/io/Latin1Reader.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLPrevElementImpl.java

* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/UnionDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLAnchorElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLBaseElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/DOMSerializer.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/AttributeMap.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/jaxp/validation/StreamValidatorHelper.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/XML11DTDConfiguration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/DOMErrorHandlerWrapper.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/EncodingInfo.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLInputElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/XMLAttributesImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/ErrorHandlerProxy.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/StringListImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/REUtil.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/xni/parser/XMLParserConfiguration.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DOMStringListImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/SecuritySupport.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/XML11NSDocumentScannerImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/XPathMatcher.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/XSObjectListImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSParticleDecl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLCardElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DOMOutputImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DOMInputImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/dv/dtd/XML11DTDDVFactoryImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLDTDValidatorFilter.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/HTMLdtd.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/xni/XMLDTDContentModelHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSAnnotationImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/HTMLSerializer.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLInputElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLObjectElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/XInt.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/SubstitutionGroupHandler.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLSelectElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/XMLDocumentScannerImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/util/JAXPNamespaceContextWrapper.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSObjectList.java

* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLOptionElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/XMLEntityHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLDOMImplementation.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/xs/traversers/XSDComplexTypeTraverser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/xs/traversers/XSDWildcardTraverser.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/SchemaSymbols.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/XSDouble.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSModelImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/CDATASectionImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLSetvarElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/IntStack.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/DefaultNode.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/jaxp/validation/DOMResultBuilder.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xpointer/ShortHandPointer.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLAElementImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/io/ASCIIReader.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/jaxp/validation/XMLSchemaValidatorComponentManager.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLDocument.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/dv/dtd/ENTITYDatatypeValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/xni/parser/XMLPullParserConfiguration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/CachingParserPool.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DOMNormalizer.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLHeadingElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/ParseException.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/jaxp/validation/SimpleXMLSchema.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/CharacterDataImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/XSAllCM.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XML11DTDValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLErrorHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DOMConfigurationImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/XMLCatalogResolver.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/SAXLocatorWrapper.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLPElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/jaxp/validation/AbstractXMLSchema.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLUElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/AugmentationsImpl.java

* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/TextImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/DefaultXMLDocumentHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDGroupTraverser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSAttributeDeclaration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/CMNode.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/ValidatorHandlerImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLTextAreaElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDAbstractParticleTraverser.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSAttributeGroupDefinition.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLEntityResolver.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/SchemaGrammar.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/XMLResourceIdentifierImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/XML11DTDScannerImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/ElementDefinitionImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/IntegratedParserConfiguration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/SchemaParsingConfig.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLIFrameElementImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSNamespaceItemList.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLSmallElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/SecuritySupport.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLDocumentSource.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/EntityReferenceImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/RegularExpression.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/LCount.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLWmlElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/ItemPSVI.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLComponent.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DOMMessageFormatter.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSElementDecl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/CommentImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/datatype/DatatypeFactoryImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/ObjectFactory.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLPrevElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/XMLDocumentHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/PSVIAttrNSImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/XSQName.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLDTDScanner.java

*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/DefaultErrorHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLPostfieldElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/UniqueOrKey.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLAccessElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/XMLDTDScannerImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/IndentPrinter.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLGoElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/DefaultElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLStrongElementImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xpointer/ElementSchemePointer.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/SynchronizedSymbolTable.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/jaxp/DocumentBuilderFactoryImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/XMLChar.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/XMLVersionDetector.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/xni/grammars/XMLDTDDescription.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/XMLEntityScanner.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/events/UIEventImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/XNIException.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/ErrorHandlerWrapper.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLMetaElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/ShortListImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSNotationDecl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/URI.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLLIElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLSmallElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/dom/DeferredProcessingInstructionImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLOListElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/Serializer.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLAElement.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DeferredElementNSImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLUElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSGroupDecl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/ListDatatypeValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/util/ByteListImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSException.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/LSInputList.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/jaxp/validation/DOMResultAugmentor.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLOptgroupElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSGrammarBucket.java
*

/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLInputSource.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/QName.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/SchemaDVFactoryImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/DatatypeException.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/XMLNSDocumentScannerImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLSetvarElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLDTDFilter.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/Selector.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/IDREFDatatypeValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSNotationDeclaration.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/DOMValidatorHelper.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/CMNodeFactory.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLCollectionImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/ByteList.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLContentSpec.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/NameNodeListImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDocumentInfo.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSConstants.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/DecimalDV.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/SymbolTable.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLDivElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLQuoteElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/CMAny.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/ParserForXMLSchema.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/XMLEntityDescription.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/ShortList.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/SoftReferenceSymbolTableConfiguration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xinclude/XIncludeNamespaceSupport.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLNoopElement.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xpointer/XPointerPart.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDAbstractIDConstraintTraverser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DeferredNotationImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLModElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/grammars/XMLSchemaDescription.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/TeeXMLDocumentFilterImpl.java

* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/ObjectFactory.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLHRElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DOMImplementationImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLBElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/IdentityConstraint.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/dom/DeferredElementDefinitionImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/CMLeaf.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/ElementState.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/BMPattern.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/DTDGrammar.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLMetaElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/jaxp/validation/DraconianErrorHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/NodeIteratorImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/grammars/Grammar.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/jaxp/DefaultValidationErrorHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/XSSimpleType.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/ChildNode.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/dtd/models/ContentModelValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLDocumentFilter.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLTableElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/DOMParser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xinclude/XIncludeHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/XHTMLSerializer.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/FloatDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/TextImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/SecuritySupport.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/grammars/XMLGrammarPool.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLTemplateElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/XMLEntityManager.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/XSEmptyCM.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLDTDValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSLoader.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/validation/ConfigurableValidationState.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/XSGrammarPool.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/Printer.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSSimpleTypeDefinition.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xpointer/XPointerErrorHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLNoopElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLTimerElementImpl.java

* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/ReadOnlyGrammarPool.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/ValidatorHelper.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSModelGroupDefinition.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLTimerElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DOMXSImplementationSourceImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/RevalidationHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLTableRowElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/grammars/XMLGrammarLoader.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLDTDProcessor.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/StringDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/NodeImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/NMTOKENDatatypeValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/MessageFormatter.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSNamedMap.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLDTDDescription.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/XMLNamespaceBinder.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLImgElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/Token.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/YearMonthDurationDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLEntityDecl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/XSCMBinOp.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/EntityImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/SymbolHash.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSComplexTypeDecl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/XSFloat.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/ValueStore.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/NonValidatingConfiguration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DeferredCDATASectionImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/XMLEntityDescriptionImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLComponentManager.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/ParentNode.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLIElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSDNotationTraverser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/SecurityManager.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLBrElement.java

* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/XMLGrammarPreparser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XMLSchemaException.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLPostfieldElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DeferredDocumentImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/DTDGrammarBucket.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLDTDLoader.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/XPointerParserConfiguration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/XMLLocator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/ElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/SoftReferenceSymbolTable.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xinclude/SecuritySupport.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/Op.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/IDREFDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/CMBinOp.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/ElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/ListDV.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/dtd/XML11IDDatatypeValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/XSCMLeaf.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLInputElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/XMLErrorCode.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/CMUniOp.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/XMLAttributes.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/LineSeparator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSModelGroup.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xinclude/ObjectFactory.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/ParserConfigurationSettings.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLPreElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/DOMASBuilderImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DocumentFragmentImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLScriptElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLUListElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/models/CMStateSet.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/RangeToken.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/traversers/XSAnnotationInfo.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/Encodings.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/NamespaceContext.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/RegexParser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLDocumentScanner.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/XMLSchemaFactory.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/AnySimpleDV.java

* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/DOMInputSource.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/PrecisionDecimalDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLFormElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/html/dom/HTMLDOMImplementationImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/BalancedDTDGrammar.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSMultiValueFacet.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/parsers/AbstractXMLDocumentParser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/XMLResourceIdentifier.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLEmElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/NSItemListImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLOneventElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/wml/dom/WMLDOMImplementationImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/parsers/XMLGrammarCachingConfiguration.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/ObjectFactory.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/DOMParserImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/Constants.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/NodeImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/events/MouseEventImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/util/XIntPool.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/ObjectList.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/dv/dtd/XML11NMTOKENDatatypeValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/DoubleDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/ASModelImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/xs/traversers/XSDSimpleTypeTraverser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSParticle.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XMLSchemaLoader.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLButtonElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/AnyAtomicDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/datatype/DurationImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/EntityResolver2Wrapper.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/ElementPSVI.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLLegendElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/io/UTF8Reader.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLSelectElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xpath/regex/Match.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLHeadElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/SecuritySupport.java

* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/BooleanDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/HexBinaryDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DeferredElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSTypeDefinition.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSWildcard.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLTrElementImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/xni/parser/XMLConfigurationException.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/dv/InvalidDatatypeValueException.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/ShadowedSymbolTable.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLFieldsetElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLTemplateElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLLabelElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/JAXPConstants.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/parser/XMLDTDSource.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSImplementation.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLLinkElementImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLOptionElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/validation/XMLSchema.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/EntityDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLImgElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLFormControl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/XMLParser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/ElementNSImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLHtmlElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/DTDConfiguration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/DatatypeMessageFormatter.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/ASDOMImplementationImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/opti/DefaultText.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/XML11Serializer.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/ObjectFactory.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/util/Base64.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DeferredCommentImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLAnchorElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/msg/XMLMessageFormatter.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/dv/dtd/XML11IDREFDatatypeValidator.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLBrElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/DOMUtil.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLNotationDecl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/parsers/XIncludeAwareParserConfiguration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-

jar/org/apache/xerces/impl/validation/ValidationManager.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLDirectoryElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/QNameDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/jaxp/validation/SoftReferenceGrammarPool.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSObject.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/xs/traversers/XSDAbstractTraverser.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/XMLDocumentFragmentScannerImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/DatatypeValidator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLParagraphElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/identity/FieldActivator.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSFacet.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLOptGroupElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/ElementPSVImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/CoreDocumentImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/xni/parser/XMLDTDContentModelFilter.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/BaseMarkupSerializer.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLParamElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xpointer/XPointerHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSWildcardDecl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/dtd/models/MixedContentModel.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLWmlElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLRefreshElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLAnchorElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLFieldsetElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/DocumentBuilderImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/IntegerDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DeferredAttrImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DeferredEntityReferenceImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/SecuritySupport.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/parsers/XMLGrammarParser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/dtd/models/SimpleContentModel.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLStyleElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xni/XMLDTDHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/XMLStringBuffer.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/BaseDVFactory.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLFrameSetElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/NodeListCache.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/SAXParserFactoryImpl.java

* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSAnnotation.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/AttributePSVI.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSTerm.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLTdElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/XSDeclarationPool.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/WMLCardElement.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/validation/ValidationState.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/XSAttributeUse.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/parsers/XML11NonValidatingConfiguration.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/ObjectFactory.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dv/xs/Base64BinaryDV.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLImageElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/SAXMessageFormatter.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/xs/models/XSCMUniOp.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/wml/dom/WMLBigElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xpointer/XPointerProcessor.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/XMLLocatorWrapper.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/xni/parser/XMLDTDContentModelSource.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/impl/dtd/XMLElementDecl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/util/EncodingMap.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/jaxp/JAXPValidatorComponent.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/html/dom/HTMLTableColElementImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/OutputFormat.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/xs/traversers/XSDAttributeTraverser.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/SerializerFactoryImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/TreeWalkerImpl.java
*
/com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/dv/InvalidDatatypeFacetException.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/dom/DeferredDocumentTypeImpl.java
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/xs/traversers/SchemaContentHandler.java
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xml/serialize/Method.java
No license file was found, but licenses were detected in source scan.

cos-nonambig = cos-nonambig: {0} and {1} (or elements from their substitution group) violate \"Unique Particle Attribution\". During validation against this schema, ambiguity would be created for those two particles.

Found in path(s):
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/impl/msg/XMLSchemaMessages.properties
No license file was found, but licenses were detected in source scan.

Licensed to the Apache Software Foundation (ASF) under one or more
 contributor license agreements. See the NOTICE file distributed with
 this work for additional information regarding copyright ownership.
 The ASF licenses this file to You under the Apache License, Version 2.0
 (the "License"); you may not use this file except in compliance with
 the License. You may obtain a copy of the License at

     http://www.apache.org/licenses/LICENSE
2.0

 Unless required by applicable law or agreed to in writing, software
 distributed under the License is distributed on an "AS IS" BASIS,
 WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 See the License for the specific language governing permissions and
 limitations under the License.

Found in path(s):
* /com-springsource-org-apache-xerces-2-9-1-sources-jar/org/apache/xerces/xs/datatypes/package.html
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /com-springsource-org-apache-xerces-2-9-1-sources-
jar/org/apache/xerces/dom/DOMImplementationListImpl.java

1.400 jsonfile 4.0.0

1.400.1 Available under license :

(The MIT License)

Copyright (c) 2012-2015, JP Richardson <jprichardson@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files
(the 'Software'), to deal in the Software without restriction, including without limitation the rights to use, copy, modify,
merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE
WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS
OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
 ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.401 aws-sign2 0.7.0

1.401.1 Available under license :

Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean
the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name)
to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual
or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by
combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and

You must cause any modified files to carry prominent notices stating that You changed the files; and

You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed as modifying the License. You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall
any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or

rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.402 apache-log4j 1.2.15

1.402.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or

Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You

institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use,

reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright 1999-2005 The Apache Software Foundation

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache log4j
Copyright 2007 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.403 httpcore 4.4.5

1.403.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted"

means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each

Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");

you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

==========

This project contains annotations in the package org.apache.http.annotation
which are derived from JCIP-ANNOTATIONS
Copyright (c) 2005 Brian Goetz and Tim Peierls.
See http://www.jcip.net and the Creative Commons Attribution License
(http://creativecommons.org/licenses/by/2.5)
Full text: http://creativecommons.org/licenses/by/2.5/legalcode

License

THE WORK (AS DEFINED BELOW) IS PROVIDED UNDER THE TERMS OF THIS CREATIVE COMMONS PUBLIC LICENSE ("CCPL" OR "LICENSE"). THE WORK IS PROTECTED BY COPYRIGHT AND/OR OTHER APPLICABLE LAW. ANY USE OF THE WORK OTHER THAN AS
AUTHORIZED UNDER THIS LICENSE OR COPYRIGHT LAW IS PROHIBITED.

BY EXERCISING ANY RIGHTS TO THE WORK PROVIDED HERE, YOU ACCEPT AND AGREE TO BE BOUND BY THE TERMS OF THIS LICENSE. THE LICENSOR GRANTS YOU THE RIGHTS CONTAINED HERE IN CONSIDERATION OF YOUR ACCEPTANCE OF SUCH TERMS AND CONDITIONS.

1. Definitions

"Collective Work" means a work, such as a periodical issue, anthology or encyclopedia, in which the Work in its entirety in unmodified form, along with a number of other contributions, constituting separate and independent works in themselves, are assembled into a collective whole. A work that constitutes a Collective Work will not be considered a Derivative Work (as defined below) for the purposes of this License.
"Derivative Work" means a work based upon the Work or upon the Work and other pre-existing works, such as a translation, musical arrangement, dramatization, fictionalization, motion picture version, sound recording, art reproduction, abridgment, condensation,
or any other form in which the Work may be recast, transformed, or adapted, except that a work that constitutes a Collective Work will not be considered a Derivative Work for the purpose of this License. For the avoidance of doubt, where the Work is a musical composition or sound recording, the synchronization of the Work in timed-relation with a moving image ("synching") will be considered a Derivative Work for the purpose of this License.
"Licensor" means the individual or entity that offers the Work under the terms of this License.
"Original Author" means the individual or entity who created the Work.
"Work" means the copyrightable work of authorship offered under the terms of this License.
"You" means an individual or entity exercising rights under this License who has not previously violated the terms

of this License with respect to the Work, or who has received express permission from the Licensor to exercise rights under this License despite a previous violation.

2.
Fair Use Rights. Nothing in this license is intended to reduce, limit, or restrict any rights arising from fair use, first sale or other limitations on the exclusive rights of the copyright owner under copyright law or other applicable laws.

3. License Grant. Subject to the terms and conditions of this License, Licensor hereby grants You a worldwide, royalty-free, non-exclusive, perpetual (for the duration of the applicable copyright) license to exercise the rights in the Work as stated below:

to reproduce the Work, to incorporate the Work into one or more Collective Works, and to reproduce the Work as incorporated in the Collective Works;
to create and reproduce Derivative Works;
to distribute copies or phonorecords of, display publicly, perform publicly, and perform publicly by means of a digital audio transmission the Work including as incorporated in Collective Works;
to distribute copies or phonorecords of, display publicly, perform publicly, and perform publicly
by means of a digital audio transmission Derivative Works.

For the avoidance of doubt, where the work is a musical composition:
Performance Royalties Under Blanket Licenses. Licensor waives the exclusive right to collect, whether individually or via a performance rights society (e.g. ASCAP, BMI, SESAC), royalties for the public performance or public digital performance (e.g. webcast) of the Work.
Mechanical Rights and Statutory Royalties. Licensor waives the exclusive right to collect, whether individually or via a music rights agency or designated agent (e.g. Harry Fox Agency), royalties for any phonorecord You create from the Work ("cover version") and distribute, subject to the compulsory license created by 17 USC Section 115 of the US Copyright Act (or the equivalent in other jurisdictions).
Webcasting Rights and Statutory Royalties. For the avoidance of doubt, where the Work is a sound recording, Licensor waives the exclusive right to collect, whether
individually or via a performance-rights society (e.g. SoundExchange), royalties for the public digital performance (e.g. webcast) of the Work, subject to the compulsory license created by 17 USC Section 114 of the US Copyright Act (or the equivalent in other jurisdictions).

The above rights may be exercised in all media and formats whether now known or hereafter devised. The above rights include the right to make such modifications as are technically necessary to exercise the rights in other media and formats. All rights not expressly granted by Licensor are hereby reserved.

4. Restrictions.The license granted in Section 3 above is expressly made subject to and limited by the following restrictions:

You may distribute, publicly display, publicly perform, or publicly digitally perform the Work only under the terms of this License, and You must include a copy of, or the Uniform Resource Identifier for, this License with every copy or phonorecord of the Work You distribute, publicly
display, publicly perform, or publicly digitally perform. You may not offer or impose any terms on the Work that alter or restrict the terms of this License or the recipients' exercise of the rights granted hereunder. You may not sublicense the Work. You must keep intact all notices that refer to this License and to the disclaimer of warranties. You may not distribute, publicly display, publicly perform, or publicly digitally perform the Work with any technological measures that control access or use of the Work in a manner inconsistent with the terms of this

License Agreement. The above applies to the Work as incorporated in a Collective Work, but this does not require the Collective Work apart from the Work itself to be made subject to the terms of this License. If You create a Collective Work, upon notice from any Licensor You must, to the extent practicable, remove from the Collective Work any credit as required by clause 4(b), as requested. If You create a Derivative Work, upon notice from any Licensor You must, to the extent practicable, remove from the Derivative Work any credit as required by clause 4(b), as requested.

If you distribute, publicly display, publicly perform, or publicly digitally perform the Work or any Derivative Works or Collective Works, You must keep intact all copyright notices for the Work and provide, reasonable to the medium or means You are utilizing: (i) the name of the Original Author (or pseudonym, if applicable) if supplied, and/or (ii) if the Original Author and/or Licensor designate another party or parties (e.g. a sponsor institute, publishing entity, journal) for attribution in Licensor's copyright notice, terms of service or by other reasonable means, the name of such party or parties; the title of the Work if supplied; to the extent reasonably practicable, the Uniform Resource Identifier, if any, that Licensor specifies to be associated with the Work, unless such URI does not refer to the copyright notice or licensing information for the Work; and in the case of a Derivative Work, a credit identifying the use of the Work in the Derivative Work (e.g., "French translation of the Work by Original Author," or "Screenplay based on original Work by Original Author"). Such credit may be implemented in any reasonable manner; provided, however, that in the case of a Derivative Work or Collective Work, at a minimum such credit will appear where any other comparable authorship credit appears and in a manner at least as prominent as such other comparable authorship credit.

5. Representations, Warranties and Disclaimer

UNLESS OTHERWISE MUTUALLY AGREED TO BY THE PARTIES IN WRITING, LICENSOR OFFERS THE WORK AS-IS AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE WORK, EXPRESS, IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTIBILITY, FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT, OR THE ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE OF ABSENCE OF ERRORS, WHETHER OR NOT DISCOVERABLE. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES, SO SUCH EXCLUSION MAY NOT APPLY TO YOU.

6. Limitation on Liability. EXCEPT TO THE EXTENT REQUIRED BY APPLICABLE LAW, IN NO EVENT WILL LICENSOR BE LIABLE TO YOU ON ANY LEGAL THEORY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES ARISING OUT OF THIS LICENSE OR THE USE OF THE WORK, EVEN IF LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. Termination

This License and the rights granted hereunder will terminate automatically upon any breach by You of the terms of this License. Individuals or entities who have received Derivative Works or Collective Works from You under this License, however, will not have their licenses terminated provided such individuals or entities remain in full compliance with those licenses. Sections 1, 2, 5, 6, 7, and 8 will survive any termination of this License.

Subject to the above terms and conditions, the license granted here is perpetual (for the duration of the applicable copyright in the Work). Notwithstanding the above, Licensor reserves the right to release the Work under different license terms or to stop distributing the Work at any time; provided, however that any such election will not serve to withdraw this License

(or any other license that has been, or is required to be, granted under the terms of this License), and this License will continue in full force and effect unless terminated as stated above.

8. Miscellaneous

Each time You distribute or publicly digitally perform the Work or a Collective Work, the Licensor offers to the recipient a license to the Work on the same terms and conditions as the license granted to You under this License.

Each time You distribute or publicly digitally perform a Derivative Work, Licensor offers to the recipient a license to the original Work on the same terms and conditions as the license granted to You under this License.

If any provision of this License is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this License, and without further action by the parties to this agreement, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

No term or provision of this License shall be deemed waived and no breach consented to unless such waiver or consent shall be in writing and signed by the party to be charged with such waiver or consent.

This License constitutes the entire agreement between the parties with respect to the Work licensed here. There are no understandings, agreements or representations with respect to the Work not specified here. Licensor shall not be bound by any additional provisions that may appear in any communication from You. This License may not be modified without the mutual written agreement of the Licensor and You.

Apache HttpCore
Copyright 2005-2016 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

This project contains annotations derived from JCIP-ANNOTATIONS
Copyright (c) 2005 Brian Goetz and Tim Peierls. See http://www.jcip.net

1.404 istack-commons-runtime 2.21

1.404.1 Available under license :

Found license 'General Public License 2.0' in '* Copyright (c) 1997-2014 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 1997-2012 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

1.405 hk2-api 2.5.0-b05

1.405.1 Available under license :

Found license 'General Public License 2.0' in '* Copyright (c) 2016 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2014-2015 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2007-2015 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2015 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'Common Development and Distribution License (CDDL) 1.1' in 'Copyright (c) 2010-2016 Oracle and/or its affiliates. All rights reserved. The contents of this file are subject to the terms of either the GNU General Public License Version 2 only ("GPL") or the Common Development and Distribution License("CDDL") (collectively, the "License"). You may not use this file except in compliance with the License. You can Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2011-2015 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2007-2016 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2012-2016 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2014 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use

this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2013-2015 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in 'Copyright (c) 2010-2016 Oracle and/or its affiliates. All rights reserved. The contents of this file are subject to the terms of either the GNU General Public License Version 2 only ("GPL") or the Common Development and Distribution License("CDDL") (collectively, the "License"). You may not use this file except in compliance with the License. You can Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2012-2015 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

1.406 aopalliance-repackaged 2.5.0-b05

1.406.1 Available under license :

No license file was found, but licenses were detected in source scan.

2016 Oracle and/or its affiliates. All rights reserved.

The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
obtain a copy of the License at
https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
or packager/legal/LICENSE.txt. See the License for the specific
language governing permissions and limitations under the License.

When distributing the software, include this License Header Notice in each
file and include the License file at packager/legal/LICENSE.txt.

GPL Classpath Exception:
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section of the License
file that
accompanied this code.

Modifications:
If applicable, add the following below the License Header, with the fields
enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"

Contributor(s):
If you wish your version of this file to be governed by only the CDDL or only the GPL Version 2, indicate your decision by adding "[Contributor] elects to include this software in this distribution under the [CDDL or GPL Version 2] license." If you don't indicate a single choice of license, a recipient has the option to distribute your version of this file under either the CDDL, the GPL Version 2 or to extend the choice of license to its licensees as provided above. However, if you add GPL Version 2 code and therefore, elected the GPL Version 2 license, then the option applies only if the new code is made subject to such option by the copyright holder.

Found in path(s):
*
/aopalliance-repackaged-2-5-0-b05-sources-1-jar/pom.xml

1.407 javax-inject 2.5.0-b05

1.407.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (C) 2009 The JSR-330 Expert Group
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /javax-inject-2-5-0-b05-sources-2-jar/javax/inject/Provider.java
* /javax-inject-2-5-0-b05-sources-2-jar/javax/inject/Named.java
* /javax-inject-2-5-0-b05-sources-2-jar/javax/inject/Scope.java
* /javax-inject-2-5-0-b05-sources-2-jar/javax/inject/Qualifier.java
* /javax-inject-2-5-0-b05-sources-2-jar/javax/inject/Singleton.java
*
/javax-inject-2-5-0-b05-sources-2-jar/javax/inject/Inject.java
* /javax-inject-2-5-0-b05-sources-2-jar/javax/inject/package-info.java

No license file was found, but licenses were detected in source scan.

2016 Oracle and/or its affiliates. All rights reserved.

The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
obtain a copy of the License at
https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
or packager/legal/LICENSE.txt. See the License for the specific
language governing permissions and limitations under the License.

When distributing the software, include this License Header Notice in each
file and include the License file at packager/legal/LICENSE.txt.

GPL Classpath Exception:
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section of the License
file that
accompanied this code.

Modifications:
If applicable, add the following below the License Header, with the fields
enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"

Contributor(s):
If you wish your version of this file to be governed by only the CDDL or
only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if the new code is made subject to such option by the copyright
holder.

Found in path(s):
*
/javax-inject-2-5-0-b05-sources-2-jar/pom.xml

1.408 hk2-utils 2.5.0-b05

1.408.1 Available under license :

Found license 'General Public License 2.0' in '* Copyright (c) 2014-2015 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'General Public License 2.0' in '* Copyright (c) 2007-2015 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'General Public License 2.0' in '* Copyright (c) 2015 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'Common Development and Distribution License (CDDL) 1.1' in 'Copyright (c) 2010-2016 Oracle and/or its affiliates. All rights reserved. The contents of this file are subject to the terms of either the GNU General Public License Version 2 only ("GPL") or the Common Development and Distribution License("CDDL") (collectively, the "License"). You may not use this file except in compliance with the License. You can Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'General Public License 2.0' in '* Copyright (c) 2012-2016 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'General Public License 2.0' in '* Copyright (c) 2014 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'General Public License 2.0' in '* Copyright (c) 2013-2015 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'General Public License 2.0' in 'Copyright (c) 2010-2016 Oracle and/or its affiliates. All rights reserved. The contents of this file are subject to the terms of either the GNU General Public License Version 2 only ("GPL") or the Common Development and Distribution License("CDDL") (collectively, the "License"). You may not use this file except in compliance with the License. You can Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'General Public License 2.0' in '* Copyright (c) 2012-2015 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

1.409 hk2-locator 2.5.0-b05

1.409.1 Available under license :

Found license 'General Public License 2.0' in '* Copyright (c) 2014-2015 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2015 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'Common Development and Distribution License (CDDL) 1.1' in 'Copyright (c) 2010-2016 Oracle and/or its affiliates. All rights reserved. The contents of this file are subject to the terms of either the GNU General Public License Version 2 only ("GPL") or the Common Development and Distribution License("CDDL") (collectively, the "License"). You may not use this file except in compliance with the License. You can Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2012-2016 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2014 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2013-2015 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in 'Copyright (c) 2010-2016 Oracle and/or its affiliates. All rights reserved. The contents of this file are subject to the terms of either the GNU General Public License Version 2 only ("GPL") or the Common Development and Distribution License("CDDL") (collectively, the "License"). You may not use this file except in compliance with the License. You can Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2012-2015 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

1.410 recompose 0.30.0

1.410.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015-2018 Andrew Clark

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.411 stylis-rule-sheet 0.0.10

1.411.1 Available under license :

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
IN THE SOFTWARE.

1.412 stylis 3.5.4

1.412.1 Available under license :

MIT
MIT License

Copyright (c) 2016 Sultan Tarimo

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.413 change-emitter 0.1.6

1.413.1 Available under license :

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS

IN THE SOFTWARE.

1.414 jsesc 2.5.2

1.414.1 Available under license :

Copyright Mathias Bynens <https://mathiasbynens.be/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.415 ehcache-core 2.6.5

1.415.1 Available under license :

No license file was found, but licenses were detected in source scan.

/**
* Copyright Terracotta, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

```
*  limitations under the License.
*/
/**
   * Returns a list of all element keys in the cache, whether or not they are expired.
   * <p/>
   * The returned keys are unique and can almost be considered a set. See {@link net.sf.ehcache.store.CacheKeySet
CacheKeySet} for
   * more details.
   * <p/>
   * The List returned is not live. It is a copy.
    * <p/>
   * The time taken is O(n). On a single CPU 1.8Ghz P4, approximately 8ms is required
   * for each 1000 entries.
   *
   * @return a list of {@link Object} keys
   * @throws IllegalStateException if the cache is not {@link Status#STATUS_ALIVE}
   * @see net.sf.ehcache.store.CacheKeySet
   */
```

Found in path(s):
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/Cache.java
No license file was found, but licenses were detected in source scan.

```
/**
*  Copyright Terracotta, Inc.
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*/
```

Found in path(s):
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/InvalidConfigurationException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/PreferTCCLObjectInputStream.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/WriteBehindManager.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/event/NotificationScope.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/event/TerracottaCacheEventReplication.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/counter/sampled/SampledRateCounter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/statistics/NullLiveCacheStatisticsData.java

* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/WriteBehind.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/management/impl/BaseEmitterBean.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/AlwaysMatch.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/ccs/EhcacheReadOnlyCache.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/event/NonstopCacheEventListener.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/EhcacheXAException.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/strategy/ReadWriteEhcacheEntityRegionAccessStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/statistics/LiveCacheStatisticsWrapper.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/aggregator/Aggregators.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/FactoryConfigurationElement.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/CircularLossyQueue.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/TerracottaConfigurationElement.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/impl/ResultsImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/manager/selector/AtomikosSelector.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/constructs/nonstop/store/NonstopTimeoutBehaviorStoreResolver.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/manager/selector/BitronixSelector.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/ClusterOperationCallable.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/LessThan.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/generator/model/XMLGeneratorVisitor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/EhcacheJtaTransactionManagerLookup.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/CacheReplicator.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/strategy/TransactionalEhcacheCollectionRegionAccessStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/Status.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/impl/AbstractBalancedAccessEvictor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/sampled/ComprehensiveCacheSampler.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/provider/NullMBeanRegistrationProvider.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/PropertyUtil.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/PersistenceConfigurationElement.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/ratestatistics/UnlockedRateStatistic.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonstopExecutorService.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/management/provider/MBeanRegistrationProviderException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/aggregator/Aggregator.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/attribute/JavaBeanAttributeExtractor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/RMICacheManagerPeerListener.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/ReflectionSizeOf.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/nonstop/NonstopAwareCollectionRegionAccessStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/OperationConverter.java

* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/ComparableValue.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/MemoryUnit.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/cluster/CacheCluster.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/ResourceClassLoader.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/terracotta/TerracottaCacheCluster.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/DiskStorePathManager.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/Criteria.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/CacheManagerExecutorServiceFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/impl/BalancedAccessOnHeapPoolEvictor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/concurrency/NonstopSync.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/SingleOperation.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/impl/AtomicPoolAccessor.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/AbstractSoftLockManager.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/generator/ConfigurationGenerator.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/AbstractCacheWriter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/sampled/CacheSamplerImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/ConfigurationHelper.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/strategy/NonStrictReadWriteEhcacheEntityRegionAccessStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/ClusterOperationCallableImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/event/CacheEventListenerFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/management/impl/AggregateCacheRegionStats.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/strategy/ReadOnlyEhcacheEntityRegionAccessStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/RMICacheManagerPeerProviderFactory.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/NonstopConfiguration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/counter/CounterConfig.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/ObjectExistsException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/MaxDepthExceededException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/AgentLoader.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/CachePeer.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/generator/model/AbstractDepthFirstVisitor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/impl/AggregateOnlyResult.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/terracotta/TerracottaBootstrapCacheLoaderFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/cluster/ClusterSchemeNotAvailableException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/ManagementService.java
*
 /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/NonstopConfigurationElement.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/statistics/LiveCacheStatisticsImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/CopyStrategyConfiguration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/SearchAttribute.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/CacheTransactionHelper.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/ClassLoaderUtil.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/Decision.java

* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/ConfigurableRMIClientSocketFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/CacheConfigurationListener.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/aggregator/Sum.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/CacheConfiguration.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/CacheManagerPeerListener.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/local/JtaLocalTransactionStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/statistics/LiveCacheStatistics.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/Cache.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/manager/selector/Selector.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/strategy/EhcacheAccessStrategyFactoryImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/cluster/ClusterNode.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/strategy/AbstractReadWriteEhcacheAccessStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/SoftLockFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/blocking/BlockingCache.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/TerracottaClientConfiguration.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/CacheManagerPeerListenerFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/CoalesceKeysFilter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/ThrowTimeoutException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/counter/CounterManager.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/CacheManager.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/PersistenceConfiguration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/classloader/InternalClassLoaderAwareCache.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/TransactionIDImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/provider/MBeanRegistrationProvider.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/attribute/KeyObjectAttributeExtractor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/SerializableXid.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/EhCache.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/ExceptionOnTimeoutStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/EhcacheCoreInit.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/MimeTypeByteArray.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonstopTimeoutBehaviorFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/disk/DiskSizeOfEngine.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/DiskStoreConfiguration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/TierableStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/manager/TransactionManagerLookup.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/CacheStatistics.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/TimeoutBehaviorConfigurationElement.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/Store.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/NoOpOnTimeoutStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/TransactionException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/JvmInformation.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/statistics/sampled/NullSampledCacheStatistics.java

* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/strategy/AbstractEhcacheAccessStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/TransactionIDNotFoundException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/regions/EhcacheQueryResultsRegion.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/sampled/SampledCache.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/XidTransactionIDImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/compound/ImmutableValueElementCopyStrategy.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/CacheManagerPeerProvider.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/XidTransactionID.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/manager/selector/NullSelector.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/counter/sampled/TimeStampedCounterValue.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/LongSequence.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/impl/FromLargestCacheOnDiskPoolEvictor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/Attribute.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/provider/MBeanRegistrationProviderImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/CastingOperationConverter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/exceptionhandler/CacheExceptionHandlerFactory.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/XAExecutionListener.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/PayloadUtil.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/SingleOperationType.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/manager/DefaultTransactionManagerLookup.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/extension/CacheExtensionFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/generator/model/SimpleNodeElement.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/regions/EhcacheGeneralDataRegion.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/terracotta/ClusteredInstanceFactoryWrapper.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/TransactionIDSerializedForm.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/bootstrap/BootstrapCacheLoader.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/DefaultCacheConfigurationElement.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/impl/DefaultSizeOfEngine.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/strategy/TransactionalEhcacheEntityRegionAccessStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/counter/sampled/SampledCounterImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/LruMemoryStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/concurrency/ExplicitLockingContext.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/FindBugsSuppressWarnings.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/ccs/EhcacheNonstrictReadWriteCache.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/DiskStoreConfigurationElement.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/nonstop/NonstopAwareEntityRegionAccessStrategy.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/Timestamper.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonstopThread.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/bootstrap/BootstrapCacheLoaderFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/Or.java

* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/ReadCommittedSoftLockImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/BaseCriteria.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/management/impl/BeanUtils.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/TerracottaConfiguration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/aggregator/Min.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/RMIAsynchronousCacheReplicator.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/Result.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/manager/selector/JndiSelector.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/RMICacheReplicatorFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/CacheConfigError.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/aggregator/AggregatorInstance.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/GreaterThanOrEqual.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/compound/ReadWriteSerializationCopyStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/SizeOfPolicyConfiguration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/CacheMBean.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/NotILike.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/blocking/UpdatingSelfPopulatingCache.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/blocking/SelfPopulatingCache.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/EhcacheDecoratorAdapter.java
*
/ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/management/impl/EhcacheHibernateMBeanRegistrationImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/ElementValueComparator.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/DynamicSearchListener.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/TransactionInterruptedException.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/strategy/ReadWriteEhcacheCollectionRegionAccessStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/ClusterOperation.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/commands/Command.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/filter/CombinationSizeOfFilter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/XidTransactionIDSerializedForm.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/statistics/sampled/SampledCacheStatistics.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/WriteBehindQueueManager.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/AbstractStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/MemoryStoreEvictionPolicy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/commands/AbstractStoreCommand.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/FrontEndCacheTier.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/AbstractTransactionIDFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/impl/SearchManager.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/sampled/CacheSampler.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/sampled/SampledMBeanRegistrationProvider.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/statistics/CacheUsageListener.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/AbstractWriteBehindQueue.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/CacheEntry.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/event/RegisteredEventListeners.java

* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/TransactionID.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/CacheManagerPeerProviderFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/SearchException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/TerracottaStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/manager/selector/ClassSelector.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/EhcacheXAResourceImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/filter/PassThroughFilter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/HibernateUtil.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/sampled/SampledEhcacheMBeans.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/impl/BalancedAccessOnDiskPoolEvictor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/local/TransactionListener.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/management/impl/CollectionStats.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/disk/Segment.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/KeyBasedOperation.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/CacheWriterConfigurationElement.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/SearchableConfigurationElement.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/LoaderTimeoutException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/WeakIdentityConcurrentMap.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/impl/AbstractPool.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/attribute/AttributeExtractor.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/terracotta/KeySnapshotter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/concurrent/LockType.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/WriteOperation.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/management/impl/NullHibernateStats.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/MemorySizeParser.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/exceptionhandler/ExceptionHandlingDynamicCacheProxy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/event/CacheEventListenerAdapter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/Size.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/attribute/ReflectionAttributeExtractor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/counter/sampled/SampledCounter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/cluster/NoopCacheCluster.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/generator/model/NodeAttribute.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/RMICacheManagerPeerListenerFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/terracotta/InternalEhcache.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/counter/sampled/SampledCounterConfig.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/loader/CacheLoaderFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/concurrent/Sync.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/event/TerracottaCacheEventReplicationFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/counter/sampled/SampledRateCounterImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/DefaultElementValueComparator.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/AbstractTransactionStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/NonstopStoreImpl.java
*

/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/StoreQuery.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/CacheConfiguration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/SoftLockManagerImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/CacheWriterFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/management/impl/EntityStats.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/constructs/nonstop/concurrency/InvalidLockStateAfterRejoinException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/attribute/ValueObjectAttributeExtractor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/Direction.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/disk/DiskStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/blocking/LockTimeoutException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/Policy.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/FifoPolicy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/CacheStatisticsMBean.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/CacheStoreHelper.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/TransactionalRMICachePeer.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/aggregator/Max.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/CacheConfigurationMBean.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/management/api/HibernateStats.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/EhCacheRegionFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/counter/CounterManagerImpl.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/TerracottaConfigConfigurationElement.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/ExpiredTransactionIDImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/impl/BaseQueryInterpreter.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/AbstractPolicy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/ratestatistics/AbstractRateStatistic.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/NotifyingMemoryStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/concurrent/ReadWriteLockSync.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/impl/UnboundedPool.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/web/ShutdownListener.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/MulticastKeepaliveHeartbeatReceiver.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/filter/ResourceSizeOfFilter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/impl/OrderComparator.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/sampled/SampledCacheManagerMBean.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/Results.java
*
/ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/constructs/nonstop/concurrency/CacheOperationUnderExplicitLockCallable.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/RMIBootstrapCacheLoader.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/concurrent/ConcurrencyUtil.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/TransactionIDFactoryImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/impl/GroupedResultImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/ccs/AbstractEhcacheConcurrencyStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/sampled/ComprehensiveCacheSamplerImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/ReadCommittedSoftLockFactory.java

* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/ExpiredXidTransactionIDImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/disk/ods/RegionSet.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/NullStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/commands/StoreRemoveCommand.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/management/impl/EhcacheHibernateMbeanNames.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/ConfigError.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/RMICachePeer.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/ManagementServer.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/CacheManagerMBean.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/generator/model/AbstractNodeElement.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonstopExecutorServiceFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/terracotta/DisconnectedClusterNode.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/attribute/AttributeType.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/CacheQuery.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/WriteAllOperation.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/DeleteOperation.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/RMICacheManagerPeerProvider.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/CacheException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/counter/CounterImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/chm/SelectableConcurrentHashMap.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/attribute/AttributeExtractorException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/manager/selector/GlassfishSelector.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/CacheWriterManagerException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/FailSafeTimer.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/TransactionAwareAttributeExtractor.java
*
 /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/ElementValueComparatorConfigurationElement.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/counter/sampled/SampledRateCounterConfig.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/LargeCollection.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/MulticastKeepaliveHeartbeatSender.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/Disposable.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/constructs/nonstop/concurrency/ExplicitLockingClusterOperation.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/UnsafeSizeOf.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/EhcacheInit.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/management/api/EhcacheStats.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/manager/selector/FactorySelector.java
*
 /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/TimeoutBehaviorConfiguration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/ManagementRESTServiceConfiguration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/generator/model/NodeElementVisitor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/RejoinAwareBlockingOperation.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/exceptionhandler/CacheExceptionHandler.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/OperationsFilter.java

* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/disk/ods/FileAllocationTree.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/PoolableStore.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/strategy/ReadOnlyEhcacheCollectionRegionAccessStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/PoolEvictor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/StoreListener.java
*
/ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/ManagementRESTServiceConfigurationElement.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/EqualTo.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/processor/XAThreadPool.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/DelegatingTransactionIDFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/Configuration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/ratestatistics/AtomicRateStatistic.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/impl/AbstractFromLargestCachePoolEvictor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/MergedEnumeration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/commands/StorePutCommand.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/DeadLockException.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonstopExecutorServiceImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/LegacyEventMessage.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/SingletonEhCacheRegionFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/compound/CopyStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/CacheWriterConfiguration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/impl/FromLargestCacheOnHeapPoolEvictor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/generator/model/SimpleNodeAttribute.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/event/CacheManagerEventListener.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/disk/DiskStorageFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/PrimitiveType.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/disk/StoreUpdateException.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/RMISynchronousCacheReplicator.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/FlyweightType.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/XATransactionContext.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/event/CacheManagerEventListenerFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/DiskStoreBootstrapCacheLoader.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/ElementIdAssigningStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/generator/model/elements/ConfigurationElement.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/EventMessage.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/ratestatistics/package-info.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/statistics/sampled/SampledCacheStatisticsWrapper.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/annotations/IgnoreSizeOf.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/management/impl/CacheRegionStats.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/RMIBootstrapCacheLoaderFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/local/LocalTransactionStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/CacheManager.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/filter/AnnotationProxyFactory.java

* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/EhCacheProvider.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/statistics/LiveCacheStatisticsData.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonstopThreadPool.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/PinningConfiguration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/RmiEventMessage.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/sampled/CacheManagerSamplerImpl.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/regions/EhcacheTimestampsRegion.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/TransactionController.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/blocking/UpdatingCacheEntryFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/statistics/sampled/SampledCacheStatisticsImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/local/LocalTransactionContext.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/TransactionIDFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonStopCacheException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/LfuPolicy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/XATransactionStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/aggregator/Average.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/Ehcache.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/concurrent/StripedReadWriteLockSync.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/terracotta/TerracottaNotRunningException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/ManagementServerLoader.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/terracotta/TerracottaClusteredInstanceHelper.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/ratestatistics/RateStatistic.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/DiskStoreBootstrapCacheLoaderFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/LibraryInit.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/LegacyStoreWrapper.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/Between.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/SizeOf.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/DeleteAllOperation.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/constructs/nonstop/concurrency/LockOperationTimedOutNonstopException.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/UpdateChecker.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/BatchOperation.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/NullResults.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/counter/Counter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writebehind/WriteBehindQueue.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/compound/SerializationCopyStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/concurrent/CacheLockProvider.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/LessThanOrEqual.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/CacheWriter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/strategy/EhcacheAccessStrategyFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/generator/ConfigurationSource.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/terracotta/TerracottaBootstrapCacheLoader.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/compound/ReadWriteCopyStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/sampled/SampledCacheMBean.java

* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/Element.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/constructs/nonstop/concurrency/ExplicitLockingContextThreadLocal.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/TransactionTimeoutException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/ElementEvictionData.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/filter/AnnotationSizeOfFilter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/AbstractCacheConfigurationListener.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/constructs/nonstop/concurrency/NonstopThreadUniqueIdProvider.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/DefaultElementEvictionData.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/processor/XARequestProcessor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/GreaterThan.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/TransactionalExecutorServiceStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/event/CacheEventListener.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/loader/CacheLoader.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/terracotta/TerracottaClient.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/impl/StrictlyBoundedPool.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/classloader/ClassLoaderAwareCache.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/ConfigurationFactory.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/PinningConfigurationElement.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/StripedReadWriteLockProvider.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/impl/BoundedPool.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/ElementValueComparatorConfiguration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/aggregator/AggregatorException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/RejoinAwareNonstopStore.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/management/provider/MBeanRegistrationProviderFactoryImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/NotEqualTo.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/concurrent/StripedReadWriteLock.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/SizeOfPolicyConfigurationElement.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/TimeProviderLoader.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/AbstractEhcacheProvider.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/generator/model/NodeElement.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/sampled/CacheManagerSampler.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/regions/EhcacheTransactionalDataRegion.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/AgentSizeOf.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/MemoryStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/sampled/Utils.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/blocking/CacheEntryFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/ProductInfo.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/MulticastRMICacheManagerPeerProvider.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/terracotta/TerracottaClientRejoinListener.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/ccs/EhcacheReadWriteCache.java

*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/event/CacheManagerEventListenerRegistry.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/impl/ResultImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/NonstopStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/cluster/ClusterTopologyListener.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/impl/BaseResult.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/FeaturesManager.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/ExecutorServiceStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/aggregator/Count.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/nonstop/HibernateNonstopCacheExceptionHandler.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/management/impl/ProviderMBeanRegistrationHelper.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/MemoryEfficientByteArrayOutputStream.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/Query.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/cluster/ClusterScheme.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/compound/LegacyCopyStrategyAdapter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/CacheInitializationHelper.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/disk/ods/Region.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/terracotta/ClusteredInstanceFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/manager/selector/GenericJndiSelector.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/CacheDecoratorFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/Searchable.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonstopActiveDelegateHolder.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/statistics/sampled/CacheStatisticsSampler.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/Store.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/constructs/nonstop/concurrency/NonstopCacheLockProvider.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/AggregateIterator.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/sampled/SampledCacheManager.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/CacheKeySet.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/disk/ods/AATreeSet.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/extension/CacheExtension.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/disk/ElementSubstituteFilter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/terracotta/SerializationHelper.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/provider/MBeanRegistrationProviderFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/NamedThreadFactory.java
*
/ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/strategy/NonStrictReadWriteEhcacheCollectionRegionAccessStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/BeanHandler.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/concurrency/NonStopCacheKeySet.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/And.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/generator/ConfigurationUtil.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/management/impl/QueryStats.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/processor/XARequest.java

* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/OptimisticLockFailureException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/management/impl/EhcacheStatsImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/SlewClock.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/manager/selector/WeblogicSelector.java
*
/ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/CacheConfigurationElement.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/SoftLock.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/AtomicLongSequence.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/nonstop/NonstopAccessStrategyFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/TaskNotSubmittedTimeoutException.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/Pool.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/util/OverrideCheck.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/MemoryOnlyStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/InCollection.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/xa/EhcacheXAResource.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/RemoteCacheException.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/ElementIdHelper.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/impl/DynamicSearchChecker.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/SetAsList.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/SoftLockManager.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/management/ManagedCacheManagerPeerProvider.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/Not.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/disk/HashEntry.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/MemoryLimitedCacheLoader.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/PoolAccessor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/config/FactoryConfiguration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/distribution/ManualRMICacheManagerPeerProvider.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/SingletonEhCacheProvider.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/management/impl/EhcacheHibernate.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/regions/EhcacheCollectionRegion.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/TimeUtil.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/AbstractEhcacheRegionFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/DiskBackedMemoryStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/management/api/EhcacheHibernateMBean.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/Statistics.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/regions/EhcacheEntityRegion.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/LruPolicy.java
* /ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/hibernate/management/impl/EhcacheHibernateMBeanRegistration.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/management/impl/CacheRegionUtils.java
*
/ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/util/CountingThreadFactory.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/SoftLockID.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/store/compound/NullReadWriteCopyStrategy.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/CacheWriterManager.java

* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/writer/writethrough/WriteThroughManager.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/regions/EhcacheDataRegion.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/LocalReadsOnTimeoutStore.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/transaction/local/LocalRecoveryManager.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/hibernate/management/impl/HibernateStatsImpl.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/impl/AbstractPoolAccessor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/expression/ILike.java
*
/ehcache-core-2-6-5-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/CopyStrategyConfigurationElement.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/VmUtils.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/ObjectGraphWalker.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/LargeSet.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/terracotta/RotatingSnapshotFile.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/SizeOfEngine.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/impl/LockedPoolAccessor.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/pool/sizeof/filter/SizeOfFilter.java
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/search/attribute/DynamicAttributesExtractor.java
No license file was found, but licenses were detected in source scan.

/**
* Copyright 2006 Thomas Hawtin
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /ehcache-core-2-6-5-sources-1-jar/net/sf/ehcache/util/lang/VicariousThreadLocal.java

1.416 jackson-module-scala 2.1.5

1.416.1 Available under license :

No license file was found, but licenses were detected in source scan.

import AssemblyKeys._
import PgpKeys._
import ReleaseKeys._

```
import sbtrelease._
import ReleaseStateTransformations._

// Basic facts
name := "jackson-module-scala"

organization := "com.fasterxml.jackson.module"

crossScalaVersions := Seq("2.9.1", "2.9.2", "2.10.0")

libraryDependencies <++= (version) { (v) => Seq(
  // These are "provided" so that sbt-assembly doesn't include them (we'll fix the pom later)
  "com.fasterxml.jackson.core" % "jackson-core" % v % "provided",
  "com.fasterxml.jackson.core" % "jackson-annotations" % v % "provided",
  "com.fasterxml.jackson.core" % "jackson-databind" % v % "provided"
) }

libraryDependencies ++= Seq(
  // saying this is intransitive prevents the deps from being included in the jar
  "com.fasterxml.jackson.module" %% "scalabeans" % "0.4-SNAPSHOT" intransitive(),
  // but now we need to add scalabeans deps explicitly (also as "provided")
  "com.thoughtworks.paranamer"
 % "paranamer" % "2.3" % "provided",
  "com.google.guava" % "guava" % "13.0.1" % "provided",
  // test dependencies
  "org.scalatest" %% "scalatest" % "2.0.M5" % "test" cross CrossVersion.binaryMapped {
     case "2.10" => "2.10.0"
     case x => x
  },
  "junit" % "junit" % "4.11" % "test",
  "com.fasterxml.jackson.datatype" % "jackson-datatype-joda" % "2.1.2" % "test"
)

// Another scalabeans dependency, for 2.10 only
libraryDependencies <++= (scalaBinaryVersion, scalaVersion) { (sbv,sv) => sbv match {
 // again, "provided" so that it is not included in the jar
 case "2.10" => Seq("org.scala-lang" % "scala-reflect" % sv % "provided")
 case _ => Seq()
} }

// Change the classifier of the main jar
artifact in (Compile, packageBin) ~= { (art: Artifact) =>
 art.copy(`classifier` = Some("base"))
}

// Disable publishing the main jar
publishArtifact in (Compile, packageBin) := false
```

```
// setup sbt-assembly settings
assemblySettings

// don't assembly the scala
 dependency
assembleArtifact in packageScala := false

// don't add "assembly" to the jar name
jarName in assembly <<= (name, version, scalaBinaryVersion) { (name, version, sbv) =>
 name + "_" + sbv + "-" + version + ".jar"
}

// place the assembly in the versioned path
outputPath in assembly <<= (target in assembly, jarName in assembly, scalaBinaryVersion) { (t,s,v) =>
  t / ("scala-" + v) / s
}

// don't have a classifier on the assembly
artifact in (Compile, assembly) ~= { (art: Artifact) =>
 art.copy(`classifier` = None)
}

// add the assembly as an artifact
addArtifact(artifact in (Compile, assembly), assembly)

// add the assembly signature as an artifact
packagedArtifacts <<= (packagedArtifacts, pgpSigner, skip in pgpSigner, streams) map { (artifacts,r,skipZ,s) =>
 if (!skipZ) {
  artifacts flatMap {
    // This works because the assembly has already been declared with no classifer
    case (art @ Artifact(_,"jar","jar",None,_,_,_), file) =>
      Seq(art
                        -> file,
        art.copy(extension = art.extension + ".asc") -> r.sign(file, new File(file.getAbsolutePath + ".asc"), s))
    case (art, file) => Seq(art -> file)
  }
 } else artifacts
}

// pom re-writing:
//   * remove the scalabeans dependency, as it's included
//   * remove the 'provided' annotation on others, as they're not
pomPostProcess := {
  import xml.transform._
  new RuleTransformer(new RewriteRule {
     override def transform(node: xml.Node) = node match {
        case n if ((n \ "artifactId").text.startsWith("scalabeans")) => xml.NodeSeq.Empty
        case n @ <scope>{_*}</scope> if n.text == "provided" => xml.NodeSeq.Empty
```

```
        case _ => node
      }
  })
}

// publishing
publishMavenStyle := true

publishTo <<= version { v =>
 val nexus = "https://oss.sonatype.org/"
 if (v.trim.endsWith("SNAPSHOT"))
  Some("snapshots" at nexus + "content/repositories/snapshots")
 else
  Some("releases" at nexus +
 "service/local/staging/deploy/maven2")
}

publishArtifact in Test := false

pomIncludeRepository := { _ => false }

pomExtra := {
 <url>http://wiki.fasterxml.com/JacksonModuleScala</url>
 <licenses>
  <license>
   <name>The Apache Software License, Version 2.0</name>
   <url>http://www.apache.org/licenses/LICENSE-2.0.txt</url>
   <distribution>repo</distribution>
  </license>
 </licenses>
 <scm>
  <connection>scm:git:git@github.com:FasterXML/jackson-module-scala.git</connection>
  <developerConnection>scm:git:git@github.com:FasterXML/jackson-module-scala.git</developerConnection>
  <url>http://github.com/FasterXML/jackson-module-scala</url>
 </scm>
 <developers>
  <developer>
   <id>tatu</id>
   <name>Tatu Saloranta</name>
   <email>tatu@fasterxml.com</email>
  </developer>
  <developer>
   <id>christopher</id>
   <name>Christopher Currie</name>
   <email>christopher@currie.com</email>
  </developer>
 </developers>
 <contributors>
```

```
    <contributor>
     <name>Nathaniel Bauernfeind</name>
    </contributor>
    <contributor>
     <name>Anton Panasenko</name>
    </contributor>
  </contributors>
}

// credentials
credentials += Credentials(Path.userHome / ".ivy2" / ".credentials")

// release
releaseSettings

// bump bugfix on release
nextVersion := { ver => Version(ver).map(_.bumpBugfix.asSnapshot.string).getOrElse(versionFormatError) }

// use maven style tag name
tagName <<= (name, version in ThisBuild) map { (n,v) => n + "-" + v }

// don't publish on release, it doesn't work with cross version publishing
// TODO: see about defining multiple release processes, to do prepare/perform
// split processes similar to the Maven release plugin
releaseProcess := Seq(
 // TODO remove when scalabeans isn't a custom build
 // checkSnapshotDependencies,
 inquireVersions,
 runTest,
 setReleaseVersion,
 commitReleaseVersion,
 tagRelease,
 setNextVersion,
 commitNextVersion
)
```

Found in path(s):
* /jackson-module-scala-2-1-5-zip/jackson-module-scala-jackson-module-scala-2.1.5/build.sbt

1.417 swagger-core 1.3.5

1.417.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/**
*  Copyright 2013 Wordnik, Inc.
*
```

```
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*/
```

Found in path(s):
* /swagger-core-2-10-1-3-5-sources-1-jar/com/wordnik/swagger/core/util/JsonSerializer.scala
* /swagger-core-2-10-1-3-5-sources-1-jar/com/wordnik/swagger/core/filter/SpecFilter.scala
* /swagger-core-2-10-1-3-5-sources-1-jar/com/wordnik/swagger/model/AuthorizationModels.scala
* /swagger-core-2-10-1-3-5-sources-1-jar/com/wordnik/swagger/core/util/ReaderUtil.scala
*
 /swagger-core-2-10-1-3-5-sources-1-jar/com/wordnik/swagger/core/util/ModelUtil.scala
* /swagger-core-2-10-1-3-5-sources-1-jar/com/wordnik/swagger/core/util/TypeUtil.scala
* /swagger-core-2-10-1-3-5-sources-1-jar/com/wordnik/swagger/core/util/JsonUtil.scala
* /swagger-core-2-10-1-3-5-sources-1-jar/com/wordnik/swagger/model/SwaggerModels.scala

1.418 infer-owner 1.0.4

1.418.1 Available under license :

The ISC License

Copyright (c) npm, Inc. and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR
IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.419 p-try 2.2.0

1.419.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.420 chownr 1.1.4

1.420.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.421 onetime 1.1.0

1.421.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.422 xml-schema-core 2.0.3

1.422.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the

direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding

those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise,

unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache WebServices - XmlSchema
Copyright 2004-2012 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Portions Copyright 2006 International Business Machines Corp.

Portions Copyright (C) World Wide Web Consortium 2006, 2007 and licensed under the three-part BSD license.

1.423 jetty-server 9.4.18.v20190429

1.423.1 Available under license :

This program and the accompanying materials are made available under the terms of the Eclipse Public License 2.0 which is available at http://www.eclipse.org/legal/epl-2.0, or the Apache Software License 2.0 which is available at https://www.apache.org/licenses/LICENSE-2.0.

Eclipse Public License - v 1.0

THE ACCOMPANYING PROGRAM IS PROVIDED UNDER THE TERMS OF THIS ECLIPSE PUBLIC LICENSE ("AGREEMENT"). ANY USE, REPRODUCTION OR DISTRIBUTION OF THE PROGRAM CONSTITUTES RECIPIENT'S ACCEPTANCE OF THIS AGREEMENT.

1. DEFINITIONS

"Contribution" means:

a) in the case of the initial Contributor, the initial code and documentation distributed under this Agreement, and
b) in the case of each subsequent Contributor:
i) changes to the Program, and
ii) additions to the Program;

where such changes and/or additions to the Program originate from and are distributed by that particular Contributor. A Contribution 'originates' from a Contributor if it was added to the Program by such Contributor itself or anyone acting on such Contributor's behalf. Contributions do not include additions to the Program which: (i) are separate modules of software distributed in conjunction with the Program under their own

license agreement, and (ii) are not derivative works of the Program.

"Contributor" means any person or entity that distributes the Program.

"Licensed Patents" mean patent claims licensable by a Contributor which are necessarily infringed by the use or sale of its Contribution alone or when combined with the Program.

"Program" means the Contributions distributed in accordance with this Agreement.

"Recipient" means anyone who receives the Program under this Agreement, including all Contributors.

2. GRANT OF RIGHTS

a) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free copyright license to reproduce, prepare derivative works of, publicly display, publicly perform,
distribute and sublicense the Contribution of such Contributor, if any, and such derivative works, in source code and object code form.

b) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free patent license under Licensed Patents to make, use, sell, offer to sell, import and otherwise transfer the Contribution of such Contributor, if any, in source code and object code form. This patent license shall apply to the combination of the Contribution and the Program if, at the time the Contribution is added by the Contributor, such addition of the Contribution causes such combination to be covered by the Licensed Patents. The patent license shall not apply to any other combinations which include the Contribution. No hardware per se is licensed hereunder.

c) Recipient understands that although each Contributor grants the licenses to its Contributions set forth herein,
no assurances are provided by any
Contributor that the Program does not infringe the patent or other intellectual property rights of any other entity. Each Contributor disclaims any liability to Recipient for claims brought by any other entity based on infringement of intellectual property rights or otherwise. As a condition to exercising the rights and licenses granted hereunder, each Recipient hereby assumes sole responsibility to secure any other intellectual property rights needed, if any. For example, if a third party patent license is required to allow Recipient to distribute the Program, it is Recipient's responsibility to acquire that license before distributing the Program.

d) Each Contributor represents that to its knowledge it has sufficient copyright rights in its Contribution, if any, to grant the copyright license set forth in this Agreement.

3. REQUIREMENTS

A Contributor may choose to distribute the Program
in object code form under
its own license agreement, provided that:

a) it complies with the terms and conditions of this Agreement; and
b) its license agreement:
i) effectively disclaims on behalf of all Contributors all warranties
and conditions, express and implied, including warranties or
conditions of title and non-infringement, and implied warranties or
conditions of merchantability and fitness for a particular purpose;
ii) effectively excludes on behalf of all Contributors all liability for
damages, including direct, indirect, special, incidental and
consequential damages, such as lost profits;
iii) states that any provisions which differ from this Agreement are
offered by that Contributor alone and not by any other party; and
iv) states that source code for the Program is available from such
Contributor, and informs licensees how to obtain it in a reasonable
manner on or through a
medium customarily used for software exchange.

When the Program is made available in source code form:

a) it must be made available under this Agreement; and
b) a copy of this Agreement must be included with each copy of the Program.
Contributors may not remove or alter any copyright notices contained
within the Program.

Each Contributor must identify itself as the originator of its Contribution,
if
any, in a manner that reasonably allows subsequent Recipients to identify the
originator of the Contribution.

4. COMMERCIAL DISTRIBUTION

Commercial distributors of software may accept certain responsibilities with
respect to end users, business partners and the like. While this license is
intended to facilitate the commercial use of the Program, the Contributor who
includes the Program in a commercial product offering should do so in a manner
which does not create potential liability for other Contributors. Therefore,
if a Contributor includes the Program in a commercial
product offering, such
Contributor ("Commercial Contributor") hereby agrees to defend and indemnify
every other Contributor ("Indemnified Contributor") against any losses,
damages and costs (collectively "Losses") arising from claims, lawsuits and
other legal actions brought by a third party against the Indemnified
Contributor to the extent caused by the acts or omissions of such Commercial

Contributor in connection with its distribution of the Program in a commercial product offering. The obligations in this section do not apply to any claims or Losses relating to any actual or alleged intellectual property infringement. In order to qualify, an Indemnified Contributor must:
a) promptly notify the Commercial Contributor in writing of such claim, and
b) allow the Commercial Contributor to control, and cooperate with the Commercial Contributor in, the defense and any related settlement negotiations. The Indemnified Contributor may participate in any such claim at its own expense.

For example,
a Contributor might include the Program in a commercial product offering, Product X. That Contributor is then a Commercial Contributor. If that Commercial Contributor then makes performance claims, or offers warranties related to Product X, those performance claims and warranties are such Commercial Contributor's responsibility alone. Under this section, the Commercial Contributor would have to defend claims against the other Contributors related to those performance claims and warranties, and if a court requires any other Contributor to pay any damages as a result, the Commercial Contributor must pay those damages.

5. NO WARRANTY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, THE PROGRAM IS PROVIDED ON AN "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, EITHER EXPRESS OR IMPLIED INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OR CONDITIONS OF TITLE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each Recipient is solely responsible for determining
the appropriateness of using
and distributing the Program and assumes all risks associated with its exercise of rights under this Agreement , including but not limited to the risks and costs of program errors, compliance with applicable laws, damage to or loss of data, programs or equipment, and unavailability or interruption of operations.

6. DISCLAIMER OF LIABILITY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, NEITHER RECIPIENT NOR ANY CONTRIBUTORS SHALL HAVE ANY LIABILITY FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION LOST PROFITS), HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OR DISTRIBUTION OF THE PROGRAM OR THE EXERCISE OF ANY RIGHTS GRANTED HEREUNDER, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. GENERAL

If any provision of this Agreement is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this Agreement, and without further action by the parties hereto, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

If Recipient institutes patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Program itself (excluding combinations of the Program with other software or hardware) infringes such Recipient's patent(s), then such Recipient's rights granted under Section 2(b) shall terminate as of the date such litigation is filed.

All Recipient's rights under this Agreement shall terminate if it fails to comply with any of the material terms or conditions of this Agreement and does not cure such failure in a reasonable period of time after becoming aware of such noncompliance. If all Recipient's rights under this Agreement terminate, Recipient agrees to cease use and distribution of the Program as soon as reasonably practicable. However, Recipient's obligations under this Agreement and any licenses granted by Recipient relating to the Program shall continue and survive.

Everyone is permitted to copy and distribute copies of this Agreement, but in order to avoid inconsistency the Agreement is copyrighted and may only be modified in the following manner. The Agreement Steward reserves the right to publish new versions (including revisions) of this Agreement from time to time. No one other than the Agreement Steward has the right to modify this Agreement. The Eclipse Foundation is the initial Agreement Steward. The Eclipse Foundation may assign the responsibility to serve as the Agreement Steward to a suitable separate entity. Each new version of the Agreement will be given a distinguishing version number. The Program (including Contributions) may always be distributed subject to the version of the Agreement under which it was received. In addition, after a new version of the Agreement is published, Contributor may elect to distribute the Program (including its Contributions) under the new version. Except as expressly stated in Sections 2(a) and 2(b) above, Recipient receives no rights or licenses to the intellectual property of any Contributor under this Agreement, whether expressly, by implication, estoppel or otherwise. All rights in the Program not expressly granted under this Agreement are reserved.

This Agreement is governed by the laws of the State of New York and the intellectual property laws of the United States of America. No party to this Agreement will bring a legal action under this Agreement more than one year after the cause of action arose. Each party waives its rights to a jury trial in any resulting litigation.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works

that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously
marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without

modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions)
on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited
to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache
License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"

replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS
OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

//
// ==
// Copyright (c) 1995-2019 Mort Bay Consulting Pty. Ltd.
// --
// All rights reserved. This program and the accompanying materials
// are made available under the terms of the Eclipse Public License v1.0
// and Apache License v2.0 which accompanies this distribution.
//
// The Eclipse Public License is available at
// http://www.eclipse.org/legal/epl-v10.html
//
// The Apache License v2.0 is available at
// http://www.opensource.org/licenses/apache2.0.php
//
// You may elect to redistribute this code under either of these licenses.
// ==
//

==
Jetty Web Container
Copyright 1995-2018 Mort Bay Consulting Pty Ltd.
==

The Jetty Web Container is Copyright Mort Bay Consulting Pty Ltd
unless otherwise noted.

Jetty is dual licensed under both

* The Apache 2.0 License
  http://www.apache.org/licenses/LICENSE-2.0.html

    and

* The Eclipse Public 1.0 License
  http://www.eclipse.org/legal/epl-v10.html

Jetty may be distributed under either license.

Eclipse

The following artifacts are EPL.
* org.eclipse.jetty.orbit:org.eclipse.jdt.core

The following artifacts are EPL and ASL2.
* org.eclipse.jetty.orbit:javax.security.auth.message

The following artifacts are EPL and CDDL 1.0.
* org.eclipse.jetty.orbit:javax.mail.glassfish

Oracle

The following artifacts are CDDL + GPLv2 with classpath exception.
https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

* javax.servlet:javax.servlet-api
 * javax.annotation:javax.annotation-api
* javax.transaction:javax.transaction-api
* javax.websocket:javax.websocket-api

Oracle OpenJDK

If ALPN is used to negotiate HTTP/2 connections, then the following
artifacts may be included in the distribution or downloaded when ALPN
module is selected.

* java.sun.security.ssl

These artifacts replace/modify OpenJDK classes. The modifications
are hosted at github and both modified and original are under GPL v2 with
classpath exceptions.
http://openjdk.java.net/legal/gplv2+ce.html

OW2

The following artifacts are licensed by the OW2 Foundation according to the
terms of http://asm.ow2.org/license.html

org.ow2.asm:asm-commons
org.ow2.asm:asm

Apache

The following artifacts are ASL2 licensed.

org.apache.taglibs:taglibs-standard-spec
org.apache.taglibs:taglibs-standard-impl

MortBay

The following artifacts are ASL2 licensed. Based on selected classes from
following Apache Tomcat jars, all ASL2
licensed.

org.mortbay.jasper:apache-jsp
org.apache.tomcat:tomcat-jasper
org.apache.tomcat:tomcat-juli
org.apache.tomcat:tomcat-jsp-api
org.apache.tomcat:tomcat-el-api
org.apache.tomcat:tomcat-jasper-el
org.apache.tomcat:tomcat-api
org.apache.tomcat:tomcat-util-scan
org.apache.tomcat:tomcat-util

org.mortbay.jasper:apache-el
org.apache.tomcat:tomcat-jasper-el
org.apache.tomcat:tomcat-el-api

Mortbay

The following artifacts are CDDL + GPLv2 with classpath exception.

https://glassfish.dev.java.net/nonav/public/CDDL+GPL.html

org.eclipse.jetty.toolchain:jetty-schemas

Assorted

The UnixCrypt.java code implements the one way cryptography used by
Unix systems for simple password protection. Copyright 1996 Aki Yoshida,
modified April 2001 by Iris Van den Broeke, Daniel Deville.
Permission to use, copy, modify and distribute UnixCrypt
for non-commercial or commercial purposes and without fee is
granted provided that the copyright notice appears in all
copies.

1.424 libthrift 0.9.2

1.424.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,

each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided

that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
   the Work or Derivative Works thereof, You may choose to offer,
   and charge a fee for, acceptance of support, warranty, indemnity,
   or other liability obligations and/or rights consistent with this
   License. However, in accepting such obligations, You may act only
   on Your own behalf and on Your sole responsibility, not on behalf
   of any other Contributor, and only if You agree to indemnify,
   defend, and hold each Contributor harmless for any liability
    incurred by, or claims asserted against, such Contributor by reason
   of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

   To apply the Apache License to your work, attach the following
   boilerplate notice, with the fields enclosed by brackets "{}"
   replaced with your own identifying information. (Don't include
   the brackets!) The text should be enclosed in the appropriate
   comment syntax for the file format. We also recommend that a
   file or class name and description of purpose be included on the
   same "printed page" as the copyright notice for easier
   identification within third-party archives.

Copyright {yyyy} {name of copyright owner}

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

    http://www.apache.org/licenses/LICENSE-2.0

 Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.425 pkg-dir 4.2.0

1.425.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated

documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.426 postcss-loader 3.0.0

1.426.1 Available under license :

MIT
License (MIT)

Copyright 2017 Andrey Sitnik <andrey@sitnik.ru>

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS
FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR
COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER
IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.427 eslint-scope 4.0.3

1.427.1 Available under license :

Copyright JS Foundation and other contributors, https://js.foundation
Copyright (C) 2012-2013 Yusuke Suzuki (twitter: @Constellation) and other contributors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL <COPYRIGHT HOLDER> BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-2-Clause

1.428 import-cwd 2.1.0

1.428.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.429 clone 2.1.2

1.429.1 Available under license :

Copyright 2011-2015 Paul Vorbach <paul@vorba.ch>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the Software), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED AS IS, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.430 stream-each 1.2.3

1.430.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 Mathias Buus

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.431 import-from 2.1.0

1.431.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.432 cglib 2.2.0-b21

1.432.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2004 The Apache Software Foundation
*

* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/MethodInfo.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/RejectModifierPredicate.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/InterfaceMaker.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/impl/AddInitTransformer.java
*
 /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/CallbackInfo.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/MixinEverythingEmitter.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/AbstractClassFilterTransformer.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/impl/AbstractInterceptFieldCallback.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/CallbackHelper.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/MethodInfoTransformer.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/ClassInfo.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2003 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/Customizer.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/reflect/FastMember.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/ClassTransformerTee.java

* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/ClassGenerator.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/InvocationHandler.java
*
 /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/ProcessArrayCallback.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/Local.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/util/StringSwitcher.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/Dispatcher.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/impl/AddDelegateTransformer.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/AbstractProcessTask.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/impl/FieldProviderTransformer.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/NoOp.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/beans/BulkBeanException.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/impl/UndeclaredThrowableTransformer.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/TransformingClassGenerator.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/impl/AddPropertyTransformer.java
*
 /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/ClassVisitorTee.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/MethodFilter.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/impl/UndeclaredThrowableStrategy.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/impl/InterceptFieldTransformer.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/FieldVisitorTee.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/util/ParallelSorterEmitter.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/impl/AccessFieldTransformer.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/ProxyRefDispatcher.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/DefaultGeneratorStrategy.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/Constants.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/beans/FixedKeySet.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/TinyBitSet.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/Signature.java
*
 /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/util/SorterTemplate.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/ProcessSwitchCallback.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/AbstractClassTransformer.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/NamingPolicy.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/ClassNameReader.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/ClassTransformerFactory.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/LazyLoader.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/MethodVisitorTee.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/beans/BulkBean.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/ClassEmitterTransformer.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/reflect/FastConstructor.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/impl/FieldProvider.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/MixinBeanEmitter.java
*
 /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/DuplicatesPredicate.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/reflect/ConstructorDelegate.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/ClassEmitter.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/MethodFilterTransformer.java

* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/ClassTransformer.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/ClassFilter.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/GeneratorStrategy.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/ObjectSwitchCallback.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/beans/BeanGenerator.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/Callback.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/TransformingClassLoader.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/impl/InterceptFieldFilter.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/impl/InterceptFieldCallback.java
*
/cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/ClassesKey.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/AnnotationVisitorTee.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/Transformer.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/ClassReaderGenerator.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/CodeGenerationException.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/impl/InterceptFieldEnabled.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/FixedValue.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/Predicate.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/util/ParallelSorter.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/Block.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/Converter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2003,2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not
* use this file except in compliance with the License. You may obtain a copy of
* the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/AbstractTransformTask.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002,2003,2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.

* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/Enhancer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2003,2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/ClassFilterTransformer.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/DefaultNamingPolicy.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/InvocationHandlerGenerator.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/CallbackGenerator.java
*
 /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/reflect/FastMethod.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/Mixin.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/ClassTransformerChain.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/impl/AddStaticInitTransformer.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/ReflectUtils.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/beans/BeanCopier.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/beans/BeanMapEmitter.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/VisibilityPredicate.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/beans/ImmutableBean.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/CallbackFilter.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/reflect/MulticastDelegate.java

* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/MethodProxy.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/transform/AbstractClassLoader.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/reflect/FastClass.java
*
 /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/FixedValueGenerator.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/TypeUtils.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/MixinEmitter.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/CollectionUtils.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/EmitUtils.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/LazyLoaderGenerator.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/CodeEmitter.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/MethodInterceptorGenerator.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/MethodWrapper.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/DispatcherGenerator.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/NoOpGenerator.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/beans/BulkBeanEmitter.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/AbstractClassGenerator.java
*
 /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/Proxy.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/beans/BeanMap.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/reflect/MethodDelegate.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/reflect/FastClassEmitter.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/KeyFactory.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/DebuggingClassWriter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002,2003 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/UndeclaredThrowableException.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/MethodInterceptor.java
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/proxy/Factory.java
No license file was found, but licenses were detected in source scan.

```
/***
* ASM: a very small and fast Java bytecode manipulation framework
* Copyright (c) 2000-2005 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*    notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following disclaimer in the
*    documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*    contributors may be used to endorse or promote products derived from
*    this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
 "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/
```

Found in path(s):
* /cglib-2-2-0-b21-sources-1-jar/net/sf/cglib/core/LocalVariablesSorter.java
No license file was found, but licenses were detected in source scan.

2012 Oracle and/or its affiliates. All rights reserved.

```
  The contents of this file are subject to the terms of either the GNU
  General Public License Version 2 only ("GPL") or the Common Development
  and Distribution License("CDDL") (collectively, the "License").  You
  may not use this file except in compliance with the License.  You can
  obtain a copy of the License at
  https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
  or packager/legal/LICENSE.txt.  See the License for the specific
  language governing permissions and limitations under the License.

  When distributing the software, include this License Header Notice in each
  file and include the License file at packager/legal/LICENSE.txt.
```

GPL Classpath Exception:
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section of the License
file that
accompanied this code.

Modifications:
If applicable, add the following below the License Header, with the fields
enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"

Contributor(s):
If you wish your version of this file to be governed by only the CDDL or
only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if the new code is made subject to such option by the copyright
holder.

Found in path(s):
*
/cglib-2-2-0-b21-sources-1-jar/pom.xml

1.433 javax-inject 2.2.0-b21

1.433.1 Available under license :

No license file was found, but licenses were detected in source scan.

2011 Oracle and/or its affiliates. All rights reserved.

The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
obtain a copy of the License at
https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
or packager/legal/LICENSE.txt. See the License for the specific
language governing permissions and limitations under the License.

When distributing the software, include this License Header Notice in each
file and include the License file at packager/legal/LICENSE.txt.

GPL Classpath Exception:
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section of the License
file that
accompanied this code.

Modifications:
If applicable, add the following below the License Header, with the fields
enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"

Contributor(s):
If you wish your version of this file to be governed by only the CDDL or
only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if the new code is made subject to such option by the copyright
holder.

Found in path(s):
*
/javax-inject-2-2-0-b21-sources-1-jar/pom.xml
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (C) 2009 The JSR-330 Expert Group
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /javax-inject-2-2-0-b21-sources-1-jar/javax/inject/Named.java
* /javax-inject-2-2-0-b21-sources-1-jar/javax/inject/Inject.java
* /javax-inject-2-2-0-b21-sources-1-jar/javax/inject/Qualifier.java

* /javax-inject-2-2-0-b21-sources-1-jar/javax/inject/Singleton.java
* /javax-inject-2-2-0-b21-sources-1-jar/javax/inject/Scope.java
*
/javax-inject-2-2-0-b21-sources-1-jar/javax/inject/package-info.java
* /javax-inject-2-2-0-b21-sources-1-jar/javax/inject/Provider.java

1.434 hk2-utils 2.2.0-b21

1.434.1 Available under license :

Found license 'Common Development and Distribution License (CDDL) 1.1' in 'Copyright (c) 2010-2011 Oracle and/or its affiliates. All rights reserved. The contents of this file are subject to the terms of either the GNU General Public License Version 2 only ("GPL") or the Common Development and Distribution License("CDDL") (collectively, the "License"). You may not use this file except in compliance with the License. You can Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in 'Copyright (c) 2010-2011 Oracle and/or its affiliates. All rights reserved. The contents of this file are subject to the terms of either the GNU General Public License Version 2 only ("GPL") or the Common Development and Distribution License("CDDL") (collectively, the "License"). You may not use this file except in compliance with the License. You can Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2013 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2007-2011 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2012-2013 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2012 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

1.435 hk2-api 2.2.0-b21

1.435.1 Available under license :

Found license 'Common Development and Distribution License (CDDL) 1.1' in 'Copyright (c) 2010-2011 Oracle and/or its affiliates. All rights reserved. The contents of this file are subject to the terms of either the GNU General Public License Version 2 only ("GPL") or the Common Development and Distribution License("CDDL") (collectively, the "License"). You may not use this file except in compliance with the License. You can Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'General Public License 2.0' in 'Copyright (c) 2010-2011 Oracle and/or its affiliates. All rights reserved. The contents of this file are subject to the terms of either the GNU General Public License Version 2 only ("GPL") or the Common Development and Distribution License("CDDL") (collectively, the "License"). You may not use this file except in compliance with the License. You can Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'General Public License 2.0' in '* Copyright (c) 2013 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'General Public License 2.0' in '* Copyright (c) 2007-2011 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'General Public License 2.0' in '* Copyright (c) 2011 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'General Public License 2.0' in '* Copyright (c) 2011-2012 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'General Public License 2.0' in '# Copyright (c) 2010-2011 Oracle and/or its affiliates. All rights reserved. # The contents of this file are subject to the terms of either the GNU # General Public License Version 2 only ("GPL") or the Common Development # and Distribution License("CDDL") (collectively, the "License"). You # may not use this file except in compliance with the License. You can # Oracle designates this particular file as subject to the "Classpath" # exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'General Public License 2.0' in '* Copyright (c) 2007-2012 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

Found license 'General Public License 2.0' in '* Copyright (c) 2012 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

1.436 hk2-locator 2.2.0-b21

1.436.1 Available under license :

Found license 'Common Development and Distribution License (CDDL) 1.1' in 'Copyright (c) 2010-2011 Oracle and/or its affiliates. All rights reserved. The contents of this file are subject to the terms of either the GNU General Public License Version 2 only ("GPL") or the Common Development and Distribution License("CDDL") (collectively, the "License"). You may not use this file except in compliance with the License. You can Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in 'Copyright (c) 2010-2011 Oracle and/or its affiliates. All rights reserved. The contents of this file are subject to the terms of either the GNU General Public License Version 2 only ("GPL") or the Common Development and Distribution License("CDDL") (collectively, the "License"). You may not use this file except in compliance with the License. You can Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2013 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2012 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

1.437 asm-all-repackaged 2.2.0-b21

1.437.1 Available under license :

No license file was found, but licenses were detected in source scan.

/**
* ASM: a very small and fast Java bytecode manipulation framework
* Copyright (c) 2000-2007 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*   contributors may be used to endorse or promote products derived from

* this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/Traceable.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/ASMifiable.java
No license file was found, but licenses were detected in source scan.

/***
* ASM XML Adapter
* Copyright (c) 2004, Eugene Kuleshov
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*   contributors may be used to endorse or promote products derived from
*   this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)

* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/xml/ASMContentHandler.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/xml/SAXClassAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/xml/SAXCodeAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/xml/SAXAnnotationAdapter.java
*
/asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/xml/SAXAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/xml/Processor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/xml/SAXFieldAdapter.java
No license file was found, but licenses were detected in source scan.

/***
* ASM: a very small and fast Java bytecode manipulation framework
* Copyright (c) 2000-2007 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*   contributors may be used to endorse or promote products derived from
*   this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/ASMifierClassVisitor.java

* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/AnnotationVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/LocalVariablesSorter.java
*
/asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/analysis/BasicVerifier.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/analysis/Subroutine.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/GeneratorAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/CheckFieldAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/ASMifierAnnotationVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/AnnotationNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/Item.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/ClassNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/CheckMethodAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/AbstractInsnNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/ClassAdapter.java
*
/asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/MethodInsnNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/analysis/Frame.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/Frame.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/LdcInsnNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/AnnotationWriter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/TraceSignatureVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/TraceAnnotationVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/analysis/BasicValue.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/Type.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/InsnNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/signature/SignatureReader.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/MethodNode.java
*
/asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/analysis/BasicInterpreter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/FieldNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/EmptyVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/ASMifierMethodVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/ClassWriter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/MemberNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/AnalyzerAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/RemappingFieldAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/TableSwitchInsnNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/MethodAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/RemappingSignatureAdapter.java
*
/asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/JSRInlinerAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/LineNumberNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/AdviceAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/CheckClassAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/SerialVersionUIDAdder.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/Opcodes.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/CodeSizeEvaluator.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/TraceMethodVisitor.java

* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/FieldWriter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/JumpInsnNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/Label.java
*
 /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/Edge.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/InnerClassNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/Attribute.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/AbstractVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/ASMifierFieldVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/analysis/SourceInterpreter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/analysis/Value.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/TraceAbstractVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/TraceFieldVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/TraceClassVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/RemappingClassAdapter.java
*
 /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/TryCatchBlockNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/ASMifierAbstractVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/Handler.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/analysis/AnalyzerException.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/MethodWriter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/TypeInsnNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/SimpleRemapper.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/TableSwitchGenerator.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/VarInsnNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/IincInsnNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/Method.java
*
 /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/analysis/Interpreter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/RemappingAnnotationAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/Remapper.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/LookupSwitchInsnNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/MethodVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/InsnList.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/IntInsnNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/ClassReader.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/analysis/SimpleVerifier.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/ClassVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/MultiANewArrayInsnNode.java
*
 /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/analysis/SmallSet.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/CheckAnnotationAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/RemappingMethodAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/analysis/SourceValue.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/CheckSignatureAdapter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/signature/SignatureWriter.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/FieldVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/analysis/Analyzer.java

* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/FieldInsnNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/StaticInitMerger.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/ByteVector.java
*
/asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/FrameNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/LabelNode.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/signature/SignatureVisitor.java
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/LocalVariableNode.java
No license file was found, but licenses were detected in source scan.

2005 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*   contributors may be used to endorse or promote products derived from
*   this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
 * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.

Found in path(s):
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/analysis/package.html
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/package.html
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/package.html
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/tree/package.html
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/signature/package.html
*
/asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/util/package.html
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/attrs/package.html
No license file was found, but licenses were detected in source scan.

```
/***
* ASM: a very small and fast Java bytecode manipulation framework
* Copyright (c) 2000-2005 INRIA, France Telecom
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*    notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following disclaimer in the
*    documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
*    contributors may be used to endorse or promote products derived from
*    this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
 "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/commons/InstructionAdapter.java
No license file was found, but licenses were detected in source scan.

* ASM XML Adapter
* Copyright (c) 2004, Eugene Kuleshov
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
* 1. Redistributions of source code must retain the above copyright
*    notice, this list of conditions and the following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright
*    notice, this list of conditions and the following disclaimer in the
*    documentation and/or other materials provided with the distribution.
* 3. Neither the name of the copyright holders nor the names of its
```

* contributors may be used to endorse or promote products derived from
* this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
* AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING,
BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
* THE POSSIBILITY OF SUCH DAMAGE.

Found in path(s):
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/xml/package.html
No license file was found, but licenses were detected in source scan.

ASM XML Adapter
Copyright (c) 2004, Eugene Kuleshov
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
   notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
   notice, this list of conditions and the following disclaimer in the
   documentation and/or other materials provided with the distribution.
3. Neither the name of the copyright holders nor the names of its
   contributors may be used to endorse or promote products derived from
   this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
THE POSSIBILITY OF SUCH DAMAGE.

Found in path(s):
* /asm-all-repackaged-2-2-0-b21-sources-2-jar/org/objectweb/asm/xml/asm-xml.dtd
No license file was found, but licenses were detected in source scan.

2011 Oracle and/or its affiliates. All rights reserved.

The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
obtain a copy of the License at
https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
or packager/legal/LICENSE.txt. See the License for the specific
language governing permissions and limitations under the License.

When distributing the software, include this License Header Notice in each
file and include the License file at packager/legal/LICENSE.txt.

GPL Classpath Exception:
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section of the License
file that
accompanied this code.

Modifications:
If applicable, add the following below the License Header, with the fields
enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"

Contributor(s):
If you wish your version of this file to be governed by only the CDDL or
only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if the new code is made subject to such option by the copyright
holder.

Found in path(s):
*
/asm-all-repackaged-2-2-0-b21-sources-2-jar/pom.xml

1.438 netty-codec-socks 4.1.17.Final

1.438.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
```

Found in path(s):
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5AddressDecoder.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/SocksPortUnificationServerHandler.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5AddressEncoder.java

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
```

Found in path(s):
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/SocksVersion.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksAuthScheme.java

* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksCmdType.java
*
 /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksAuthStatus.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5AddressType.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5CommandType.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksMessageType.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthStatus.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksProtocolVersion.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksCmdStatus.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksSubnegotiationVersion.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5AuthMethod.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5CommandStatus.java
*
 /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksResponseType.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksAddressType.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksRequestType.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-socks-4-1-17-final-sources-1-
jar/io/netty/handler/codec/socksx/v5/Socks5CommandRequestDecoder.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v4/package-info.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5ClientEncoder.java
*
 /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/AbstractSocksMessage.java
* /netty-codec-socks-4-1-17-final-sources-1-
jar/io/netty/handler/codec/socksx/v5/Socks5CommandResponseDecoder.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5InitialRequestDecoder.java
* /netty-codec-socks-4-1-17-final-sources-1-
jar/io/netty/handler/codec/socksx/v5/Socks5InitialResponseDecoder.java
* /netty-codec-socks-4-1-17-final-sources-1-
jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthRequestDecoder.java

* /netty-codec-socks-4-1-17-final-sources-1-
jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthResponseDecoder.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v4/AbstractSocks4Message.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5Message.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v4/Socks4ClientEncoder.java
*
/netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v4/Socks4ServerEncoder.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/AbstractSocks5Message.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5ServerEncoder.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/package-info.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v4/Socks4Message.java
No license file was found, but licenses were detected in source scan.

~ Copyright 2012 The Netty Project
~
~ The Netty Project licenses this file to you under the Apache License,
~ version 2.0 (the "License"); you may not use this file except in compliance
~ with the License. You may obtain a copy of the License at:
~
~ http://www.apache.org/licenses/LICENSE
2.0
~
~ Unless required by applicable law or agreed to in writing, software
~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
~ License for the specific language governing permissions and limitations
~ under the License.

Found in path(s):
* /netty-codec-socks-4-1-17-final-sources-1-jar/META-INF/maven/io.netty/netty-codec-socks/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v4/Socks4ServerDecoder.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksAuthResponseDecoder.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/UnknownSocksResponse.java
*
/netty-codec-socks-4-1-17-final-sources-1-
jar/io/netty/handler/codec/socksx/v5/DefaultSocks5CommandRequest.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksCmdRequest.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v4/Socks4CommandStatus.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthRequest.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5CommandRequest.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5InitialRequest.java
* /netty-codec-socks-4-1-17-final-sources-1-
jar/io/netty/handler/codec/socksx/v4/DefaultSocks4CommandRequest.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksResponse.java
* /netty-codec-socks-4-1-17-final-sources-1-
jar/io/netty/handler/codec/socksx/v5/DefaultSocks5CommandResponse.java
*
/netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5InitialResponse.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5InitialRequest.java
* /netty-codec-socks-4-1-17-final-sources-1-
jar/io/netty/handler/codec/socksx/v4/DefaultSocks4CommandResponse.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksAuthRequest.java
* /netty-codec-socks-4-1-17-final-sources-1-
jar/io/netty/handler/codec/socksx/v5/DefaultSocks5PasswordAuthRequest.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v4/Socks4CommandType.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksCmdResponse.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksInitRequest.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksAuthResponse.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksCmdResponseDecoder.java
*
/netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v4/Socks4CommandResponse.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksRequest.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/SocksMessage.java
* /netty-codec-socks-4-1-17-final-sources-1-
jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthResponse.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksInitResponse.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5CommandResponse.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v4/Socks4ClientDecoder.java
* /netty-codec-socks-4-1-17-final-sources-1-
jar/io/netty/handler/codec/socksx/v5/DefaultSocks5PasswordAuthResponse.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksInitResponseDecoder.java
*
/netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksMessage.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/package-info.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksInitRequestDecoder.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v4/Socks4CommandRequest.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/UnknownSocksRequest.java

* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socksx/v5/Socks5InitialResponse.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksMessageEncoder.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksCommonUtils.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/package-info.java
* /netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksCmdRequestDecoder.java
*
/netty-codec-socks-4-1-17-final-sources-1-jar/io/netty/handler/codec/socks/SocksAuthRequestDecoder.java

1.439 netty-handler-proxy 4.1.17.Final

1.439.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-handler-proxy-4-1-17-final-sources-jar/io/netty/handler/proxy/ProxyConnectException.java
* /netty-handler-proxy-4-1-17-final-sources-jar/io/netty/handler/proxy/ProxyConnectionEvent.java
* /netty-handler-proxy-4-1-17-final-sources-jar/io/netty/handler/proxy/package-info.java
*
/netty-handler-proxy-4-1-17-final-sources-jar/io/netty/handler/proxy/Socks4ProxyHandler.java
* /netty-handler-proxy-4-1-17-final-sources-jar/io/netty/handler/proxy/Socks5ProxyHandler.java
* /netty-handler-proxy-4-1-17-final-sources-jar/io/netty/handler/proxy/ProxyHandler.java
* /netty-handler-proxy-4-1-17-final-sources-jar/io/netty/handler/proxy/HttpProxyHandler.java
No license file was found, but licenses were detected in source scan.

~ Copyright 2014 The Netty Project
~
~ The Netty Project licenses this file to you under the Apache License,
~ version 2.0 (the "License"); you may not use this file except in compliance
~ with the License. You may obtain a copy of the License at:
~
~   http://www.apache.org/licenses/LICENSE

2.0
~
~ Unless required by applicable law or agreed to in writing, software
~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
~ License for the specific language governing permissions and limitations
~ under the License.

Found in path(s):
* /netty-handler-proxy-4-1-17-final-sources-jar/META-INF/maven/io.netty/netty-handler-proxy/pom.xml

1.440 netty-transport 4.1.17.Final

1.440.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
* Handles an I/O event or intercepts an I/O operation, and forwards it to its next handler in
* its {@link ChannelPipeline}.
*
* <h3>Sub-types</h3>
* <p>
* {@link ChannelHandler} itself does not provide many methods, but you usually have to implement one of its
subtypes:
* <ul>
* <li>{@link
 ChannelInboundHandler} to handle inbound I/O events, and</li>
* <li>{@link ChannelOutboundHandler} to handle outbound I/O operations.</li>
* </ul>
* </p>
* <p>
* Alternatively, the following adapter classes are provided for your convenience:
```

```
* <ul>
* <li>{@link ChannelInboundHandlerAdapter} to handle inbound I/O events,</li>
* <li>{@link ChannelOutboundHandlerAdapter} to handle outbound I/O operations, and</li>
* <li>{@link ChannelDuplexHandler} to handle both inbound and outbound events</li>
* </ul>
* </p>
* <p>
* For more information, please refer to the documentation of each subtype.
* </p>
*
* <h3>The context object</h3>
* <p>
* A {@link ChannelHandler} is provided with a {@link ChannelHandlerContext}
* object.  A {@link ChannelHandler} is supposed to interact with the
* {@link ChannelPipeline} it belongs to via a context object.  Using the
* context object, the {@link ChannelHandler} can pass events upstream or
* downstream, modify the pipeline dynamically,
 or store the information
* (using {@link AttributeKey}s) which is specific to the handler.
*
* <h3>State management</h3>
*
* A {@link ChannelHandler} often needs to store some stateful information.
* The simplest and recommended approach is to use member variables:
* <pre>
* public interface Message {
*     // your methods here
* }
*
* public class DataServerHandler extends {@link SimpleChannelInboundHandler}&lt;Message&gt; {
*
*     <b>private boolean loggedIn;</b>
*
*     {@code @Override}
*     public void channelRead0({@link ChannelHandlerContext} ctx, Message message) {
*         {@link Channel} ch = e.getChannel();
*         if (message instanceof LoginMessage) {
*             authenticate((LoginMessage) message);
*             <b>loggedIn = true;</b>
*         } else (message instanceof GetDataMessage) {
*             if (<b>loggedIn</b>) {
*                 ch.write(fetchSecret((GetDataMessage) message));
*             } else {
*
   fail();
*             }
*         }
*     }
```

```
*     ...
* }
* </pre>
* Because the handler instance has a state variable which is dedicated to
* one connection, you have to create a new handler instance for each new
* channel to avoid a race condition where a unauthenticated client can get
* the confidential information:
* <pre>
* // Create a new handler instance per channel.
* // See {@link ChannelInitializer#initChannel(Channel)}.
* public class DataServerInitializer extends {@link ChannelInitializer}&lt;{@link Channel}&gt; {
*     {@code @Override}
*     public void initChannel({@link Channel} channel) {
*         channel.pipeline().addLast("handler", <b>new DataServerHandler()</b>);
*     }
* }
*
* </pre>
*
* <h4>Using {@link AttributeKey}s</h4>
*
* Although it's recommended to use member variables to store the state of a
* handler, for some reason you might not want to create many handler instances.
* In such a case, you can use {@link AttributeKey}s which
 is provided by
* {@link ChannelHandlerContext}:
* <pre>
* public interface Message {
*     // your methods here
* }
*
* {@code @Sharable}
* public class DataServerHandler extends {@link SimpleChannelInboundHandler}&lt;Message&gt; {
*     private final {@link AttributeKey}&lt;{@link Boolean}&gt; auth =
*           {@link AttributeKey#valueOf(String) AttributeKey.valueOf("auth")};
*
*     {@code @Override}
*     public void channelRead({@link ChannelHandlerContext} ctx, Message message) {
*         {@link Attribute}&lt;{@link Boolean}&gt; attr = ctx.attr(auth);
*         {@link Channel} ch = ctx.channel();
*         if (message instanceof LoginMessage) {
*             authenticate((LoginMessage) o);
*             <b>attr.set(true)</b>;
*         } else (message instanceof GetDataMessage) {
*             if (<b>Boolean.TRUE.equals(attr.get())</b>) {
*                 ch.write(fetchSecret((GetDataMessage) o));
*             } else {
*                 fail();
```

```
*
         }
*        }
*     }
*     ...
* }
* </pre>
* Now that the state of the handler is attached to the {@link ChannelHandlerContext}, you can add the
* same handler instance to different pipelines:
* <pre>
* public class DataServerInitializer extends {@link ChannelInitializer}&lt;{@link Channel}&gt; {
*
*     private static final DataServerHandler <b>SHARED</b> = new DataServerHandler();
*
*     {@code @Override}
*     public void initChannel({@link Channel} channel) {
*         channel.pipeline().addLast("handler", <b>SHARED</b>);
*     }
* }
* </pre>
*
*
* <h4>The {@code @Sharable} annotation</h4>
* <p>
* In the example above which used an {@link AttributeKey},
* you might have noticed the {@code @Sharable} annotation.
* <p>
* If a {@link ChannelHandler} is annotated with the {@code @Sharable}
* annotation, it means you can create an instance of the handler just once and
* add it to one or more {@link ChannelPipeline}s multiple times without
* a race
 condition.
* <p>
* If this annotation is not specified, you have to create a new handler
* instance every time you add it to a pipeline because it has unshared state
* such as member variables.
* <p>
* This annotation is provided for documentation purpose, just like
* <a href="http://www.javaconcurrencyinpractice.com/annotations/doc/">the JCIP annotations</a>.
*
* <h3>Additional resources worth reading</h3>
* <p>
* Please refer to the {@link ChannelHandler}, and
* {@link ChannelPipeline} to find out more about inbound and outbound operations,
* what fundamental differences they have, how they flow in a  pipeline,  and how to handle
* the operation in your application.
*/
```

Found in path(s):
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/oio/DefaultOioDatagramChannelConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/oio/OioDatagramChannelConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/ChannelOutputShutdownEvent.java
*
 /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/ChannelInputShutdownReadComplete.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DelegatingChannelPromiseNotifier.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/PendingBytesTracker.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/nio/SelectedSelectionKeySetSelector.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/ChannelOutputShutdownException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/pool/AbstractChannelPoolMap.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/MaxBytesRecvByteBufAllocator.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/MaxMessagesRecvByteBufAllocator.java
*
/netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DefaultMaxMessagesRecvByteBufAllocator.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/pool/SimpleChannelPool.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/pool/ChannelPoolMap.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/pool/ChannelHealthChecker.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/pool/ChannelPool.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DefaultMaxBytesRecvByteBufAllocator.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/pool/ChannelPoolHandler.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/pool/AbstractChannelPoolHandler.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/pool/package-info.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/pool/FixedChannelPool.java
No license file was found, but licenses were detected in source scan.

~ Copyright 2012 The Netty Project
~
~ The Netty Project licenses this file to you under the Apache License,
~ version 2.0 (the "License"); you may not use this file except in compliance
~ with the License. You may obtain a copy of the License at:
~
~ http://www.apache.org/licenses/LICENSE
2.0
~
~ Unless required by applicable law or agreed to in writing, software
~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
~ License for the specific language governing permissions and limitations
~ under the License.

Found in path(s):
* /netty-transport-4-1-17-final-sources-1-jar/META-INF/maven/io.netty/netty-transport/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the

* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelProgressiveFutureListener.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DefaultChannelId.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/group/ChannelMatcher.java
*
 /netty-transport-4-1-17-final-sources-1-jar/io/netty/bootstrap/ChannelFactory.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/group/DefaultChannelGroup.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelProgressiveFuture.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/group/ChannelGroupException.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelProgressivePromise.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/group/ChannelGroup.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/oio/DefaultOioSocketChannelConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelHandlerAdapter.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/AddressedEnvelope.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/SimpleChannelInboundHandler.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ConnectTimeoutException.java
*
 /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/oio/OioSocketChannelConfig.java
* /netty-transport-4-1-17-final-sources-1-
jar/io/netty/channel/socket/oio/DefaultOioServerSocketChannelConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DefaultMessageSizeEstimator.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelId.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/AbstractEventLoopGroup.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/oio/OioServerSocketChannelConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DefaultChannelProgressivePromise.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/group/ChannelMatchers.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/MessageSizeEstimator.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DefaultAddressedEnvelope.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/nio/SelectedSelectionKeySet.java
*
 /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelOutboundBuffer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT

* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/embedded/EmbeddedChannelId.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ReflectiveChannelFactory.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelFactory.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/AbstractEventLoop.java
*
 /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/PendingWriteQueue.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/bootstrap/AbstractBootstrapConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DefaultSelectStrategyFactory.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/group/VoidChannelGroupFuture.java
*
 /netty-transport-4-1-17-final-sources-1-jar/io/netty/bootstrap/BootstrapConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/SelectStrategyFactory.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DefaultSelectStrategy.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/bootstrap/ServerBootstrapConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelInboundInvoker.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/PreferHeapByteBufAllocator.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/WriteBufferWaterMark.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelOutboundInvoker.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/SelectStrategy.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/DuplexChannel.java
No license file was found, but licenses were detected in source scan.

/*

* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/oio/OioByteStreamChannel.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DefaultEventLoopGroup.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DefaultChannelPromise.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/FixedRecvByteBufAllocator.java
*
 /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/nio/NioServerSocketChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/embedded/package-info.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/MultithreadEventLoopGroup.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/group/ChannelGroupFuture.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/local/LocalServerChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelException.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/nio/AbstractNioByteChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/local/LocalChannel.java

* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/oio/OioServerSocketChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/EventLoopException.java
*
 /netty-transport-4-1-17-final-sources-1-jar/io/netty/bootstrap/AbstractBootstrap.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/DatagramPacket.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/local/LocalEventLoopGroup.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DefaultFileRegion.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelHandlerContext.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ThreadPerChannelEventLoop.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/package-info.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/DefaultDatagramChannelConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/bootstrap/Bootstrap.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/oio/AbstractOioByteChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/package-info.java
*
 /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelPipeline.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelInboundHandlerAdapter.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/group/ChannelGroupFutureListener.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelOutboundHandlerAdapter.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/oio/OioEventLoopGroup.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/Channel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/DatagramChannelConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/group/CombinedIterator.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/oio/package-info.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/AbstractServerChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ServerChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DefaultChannelPipeline.java
*
 /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/CombinedChannelDuplexHandler.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/nio/NioDatagramChannelConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/nio/package-info.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/InternetProtocolFamily.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/CompleteChannelFuture.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelFlushPromiseNotifier.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/oio/OioDatagramChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/oio/AbstractOioChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/EventLoopGroup.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/bootstrap/package-info.java
*
 /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/DefaultSocketChannelConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/DefaultServerSocketChannelConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/nio/NioSocketChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelInboundHandler.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/ServerSocketChannelConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DefaultChannelConfig.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelMetadata.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/bootstrap/ServerBootstrap.java

* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/embedded/EmbeddedChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelFuture.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelDuplexHandler.java
*
/netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/embedded/EmbeddedSocketAddress.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/ChannelInputShutdownEvent.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/nio/AbstractNioMessageChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/EventLoop.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/ServerSocketChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/SucceededChannelFuture.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/oio/AbstractOioMessageChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelPromise.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/VoidChannelPromise.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/oio/OioSocketChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/AdaptiveRecvByteBufAllocator.java
*
/netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/SingleThreadEventLoop.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/AbstractChannelHandlerContext.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/FileRegion.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/group/DefaultChannelGroupFuture.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/local/LocalChannelRegistry.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/local/package-info.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/FailedChannelFuture.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/SocketChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelOption.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelPromiseNotifier.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/nio/NioEventLoop.java
*
/netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/DatagramChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelFutureListener.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelOutboundHandler.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/nio/NioDatagramChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelPipelineException.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelPromiseAggregator.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/nio/ProtocolFamilyConverter.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/group/package-info.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/nio/NioTask.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ChannelInitializer.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/embedded/EmbeddedEventLoop.java
*
/netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/ThreadPerChannelEventLoopGroup.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/oio/package-info.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/nio/NioEventLoopGroup.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/local/LocalAddress.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DefaultEventLoop.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/AbstractChannel.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/nio/package-info.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/socket/SocketChannelConfig.java

* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/RecvByteBufAllocator.java
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/nio/AbstractNioChannel.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/DefaultChannelHandlerContext.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/CoalescingBufferQueue.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the

* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-transport-4-1-17-final-sources-1-jar/io/netty/channel/AbstractCoalescingBufferQueue.java

1.441 d3-delaunay 5.3.0

1.441.1 Available under license :

ISC
Copyright 2018 Observable, Inc.

Permission to use, copy, modify, and/or distribute this software for any purpose
with or without fee is hereby granted, provided that the above copyright notice
and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND
FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS
OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER
TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF
THIS SOFTWARE.

1.442 okhttp 3.12.1

1.442.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 Twitter, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*

```
*     http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http2/Huffman.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (C) 2010 The Android Open Source Project
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /okhttp-3-12-1-sources-1-jar/okhttp3/Cache.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (C) 2013 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http/RequestLine.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http2/Http2.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http2/ErrorCode.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/Response.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/Handshake.java
*
 /okhttp-3-12-1-sources-1-jar/okhttp3/Route.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http/StatusLine.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/connection/RouteDatabase.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/cache/InternalCache.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/cache/CacheStrategy.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/Request.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/Dispatcher.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/NamedRunnable.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/MediaType.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http2/Hpack.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2012 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okhttp-3-12-1-sources-1-jar/okhttp3/Dns.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http2/Settings.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/connection/RouteSelector.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/OkHttpClient.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2018 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.

* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/annotations/EverythingIsNonNull.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/proxy/NullProxySelector.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2012 Square, Inc.
* Copyright (C) 2012 The Android Open Source Project
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/platform/Platform.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2016 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http/RetryAndFollowUpInterceptor.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http2/ConnectionShutdownException.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http2/StreamResetException.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/cache2/FileOperator.java
*
 /okhttp-3-12-1-sources-1-jar/okhttp3/internal/ws/RealWebSocket.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/platform/Jdk9Platform.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/WebSocketListener.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/tls/TrustRootIndex.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http/CallServerInterceptor.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/tls/BasicCertificateChainCleaner.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/platform/JdkWithJettyBootPlatform.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http/RealInterceptorChain.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http/UnrepeatableRequestBody.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/WebSocket.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/platform/AndroidPlatform.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/tls/BasicTrustRootIndex.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/cache2/Relay.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2015 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/io/FileSystem.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/CookieJar.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/connection/StreamAllocation.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/connection/ConnectionSpecSelector.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/cache/FaultHidingSink.java

*
 /okhttp-3-12-1-sources-1-jar/okhttp3/Authenticator.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/Cookie.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/HttpUrl.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/connection/RouteException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2014 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okhttp-3-12-1-sources-1-jar/okhttp3/MultipartBody.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http2/PushObserver.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/ResponseBody.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/cache/CacheRequest.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/Challenge.java
*
 /okhttp-3-12-1-sources-1-jar/okhttp3/Call.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/CertificatePinner.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http2/Header.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/ws/WebSocketReader.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/Credentials.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/Protocol.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/ws/WebSocketProtocol.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/RealCall.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/ConnectionSpec.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http/RealResponseBody.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/Version.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/FormBody.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/Interceptor.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/TlsVersion.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/CipherSuite.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/Callback.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http/HttpMethod.java
*

/okhttp-3-12-1-sources-1-jar/okhttp3/internal/Internal.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/ws/WebSocketWriter.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/RequestBody.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/platform/ConscryptPlatform.java
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/connection/RealConnection.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/ConnectionPool.java
*
/okhttp-3-12-1-sources-1-jar/okhttp3/Headers.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/tls/DistinguishedNameParser.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/tls/OkHostnameVerifier.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/tls/CertificateChainCleaner.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/platform/OptionalMethod.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/connection/ConnectInterceptor.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http/BridgeInterceptor.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/Connection.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/cache/CacheInterceptor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2011 The Android Open Source Project
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/cache/DiskLruCache.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http2/Http2Reader.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http2/Http2Connection.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http2/Http2Stream.java
*
 /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http/HttpDate.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http2/Http2Writer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2017 Square, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/publicsuffix/PublicSuffixDatabase.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/EventListener.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (C) 2012 The Android Open Source Project
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/Util.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http/HttpHeaders.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/Address.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http2/Http2Codec.java
* /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http1/Http1Codec.java
*
 /okhttp-3-12-1-sources-1-jar/okhttp3/internal/http/HttpCodec.java

1.443 spring-security-cas 3.2.4.RELEASE

1.443.1 Available under license :

No license file was found, but licenses were detected in source scan.

/* Copyright 2004, 2005, 2006 Acegi Technology Pty Limited
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-cas-3-2-4-release-sources-jar/org/springframework/security/cas/authentication/EhCacheBasedTicketCache.java
* /spring-security-cas-3-2-4-release-sources-jar/org/springframework/security/cas/web/CasAuthenticationFilter.java
* /spring-security-cas-3-2-4-release-sources-jar/org/springframework/security/cas/SamlServiceProperties.java
*
 /spring-security-cas-3-2-4-release-sources-jar/org/springframework/security/cas/ServiceProperties.java
* /spring-security-cas-3-2-4-release-sources-jar/org/springframework/security/cas/authentication/NullStatelessTicketCache.java
* /spring-security-cas-3-2-4-release-sources-jar/org/springframework/security/cas/userdetails/GrantedAuthorityFromAssertionAttributesUserDetailsService.java
* /spring-security-cas-3-2-4-release-sources-jar/org/springframework/security/cas/authentication/CasAuthenticationProvider.java

* /spring-security-cas-3-2-4-release-sources-jar/org/springframework/security/cas/web/CasAuthenticationEntryPoint.java
* /spring-security-cas-3-2-4-release-sources-jar/org/springframework/security/cas/userdetails/AbstractCasAssertionUserDetailsService.java
* /spring-security-cas-3-2-4-release-sources-jar/org/springframework/security/cas/authentication/CasAuthenticationToken.java
* /spring-security-cas-3-2-4-release-sources-jar/org/springframework/security/cas/authentication/CasAssertionAuthenticationToken.java
No license file was found, but licenses were detected in source scan.

```
/* Copyright 2004 Acegi Technology Pty Limited
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-security-cas-3-2-4-release-sources-jar/org/springframework/security/cas/authentication/StatelessTicketCache.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-security-cas-3-2-4-release-sources-

jar/org/springframework/security/cas/web/authentication/ServiceAuthenticationDetails.java
* /spring-security-cas-3-2-4-release-sources-
jar/org/springframework/security/cas/web/authentication/ServiceAuthenticationDetailsSource.java
* /spring-security-cas-3-2-4-release-sources-
jar/org/springframework/security/cas/web/authentication/DefaultServiceAuthenticationDetails.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-cas-3-2-4-release-sources-
jar/org/springframework/security/cas/authentication/SpringCacheBasedTicketCache.java

1.444 xmltooling 1.4.4

1.444.1 Available under license :

No license file was found, but licenses were detected in source scan.

Schema for XML Signatures
  http://www.w3.org/2000/09/xmldsig#
  $Revision: 1.2 $ on $Date: 2005/06/03 03:09:54 $ by $Author: cantor $

  Copyright 2001 The Internet Society and W3C (Massachusetts Institute
  of Technology, Institut National de Recherche en Informatique et en
  Automatique, Keio University). All Rights Reserved.
  http://www.w3.org/Consortium/Legal/

  This document is governed by the W3C Software License [1] as described
  in the FAQ [2].

  [1] http://www.w3.org/Consortium/Legal/copyright

Found in path(s):

* /xmltooling-1-4-4-sources-2-jar/schema/xmldsig-core-schema.xsd
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the University Corporation for Advanced Internet Development,
* Inc. (UCAID) under one or more contributor license agreements. See the
* NOTICE file distributed with this work for additional information regarding
* copyright ownership. The UCAID licenses this file to You under the Apache
* License, Version 2.0 (the "License"); you may not use this file except in
* compliance with the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/NamespaceManager.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/X509SKI.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/X509CredentialNameEvaluator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptedTypeImpl.java
* /xmltooling-1-4-4-sources-2-
jar/org/opensaml/xml/security/credential/criteria/EvaluableEntityIDCredentialCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/Resolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/OriginatorKeyInfo.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/TransformMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptionPropertyMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/io/UnmarshallerFactory.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/LazyList.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/X509DigestCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/AbstractElementExtensibleXMLObjectMarshaller.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/Exponent.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/IndexingObjectStore.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/io/BaseXMLObjectMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/KeyInfoReferenceSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/UsageType.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509CertificateBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/StaticKeyInfoGenerator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/DigestMethodBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/parse/XMLParserException.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/SPKISexpBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptedTypeMarshaller.java

*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/DataReferenceImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/X509IssuerSerial.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/SignatureTrustEngine.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/XMLObjectBuilderFactory.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/InlineEncryptedKeyResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/KANonce.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/NamedCurveImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/TransformsUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/RecipientKeyInfoBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/PgenCounter.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/XMLObjectHelper.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/PGPKeyPacketImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/Pair.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/EncryptionMethod.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/criteria/EntityIDCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/SecurityHelper.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/PGPDataSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/CollectionCredentialResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/RecipientKeyInfoImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/DataReference.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/KeySizeBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/URIContentReference.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/RecipientKeyInfoMarshaller.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/ReferenceListImpl.java
* /xmltooling-1-4-4-sources-2-
jar/org/opensaml/xml/security/credential/criteria/EvaluableKeyAlgorithmCredentialCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/XMLObjectChildrenList.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/PGPKeyPacketBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/DigestMethod.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/KeyInfoCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/XMLConfigurator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/Version.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/EncryptionProperties.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/CipherReferenceMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/DatatypeHelper.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyInfoReferenceMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/ExplicitKeySignatureTrustEngine.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/X509IssuerSerialSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/XSInteger.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/PImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/PublicKeyImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/JImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/CryptoBinarySchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/DHKeyValueBuilder.java

* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/DigestMethodUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/trust/ExplicitX509CertificateTrustEngine.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSStringBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/X500DNHandler.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/StaticCredentialResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/CriteriaSet.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/XMLConstants.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/X509SubjectKeyIdentifierCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509CRLBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/DigestMethodImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/AbstractSimpleSingletonFactory.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSBooleanUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/KeyInfoCredentialResolver.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/AbstractXMLEncryptionUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/SecurityConfiguration.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyInfoTypeImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyValueImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/KeyInfoHelper.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/io/AbstractXMLObjectMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/validator/AgreementMethodSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/KeyInfoProvider.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSBooleanBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptionMethodImpl.java
* /xmltooling-1-4-4-sources-2-
jar/org/opensaml/xml/security/credential/criteria/EvaluableX509SubjectKeyIdentifierCredentialCriteria.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/Modulus.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/XMLEncryptionBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/RetrievalMethodSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptionPropertiesBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/TransformsImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/LazySet.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptionPropertyUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/Namespace.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/ECPointTypeImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/TransformsMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/SPKIData.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSURIImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/trust/ExplicitX509CertificateTrustEvaluator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/SignatureConstants.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/LocalKeyInfoCredentialResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptedKeyBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptionMethodUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/SPKIDataImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/Transforms.java

* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/Signer.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/OriginatorKeyInfoMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/ExponentBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/PKIXTrustEvaluator.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/SeedImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/PGPDataUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509SerialNumberMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/KeyReferenceImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptedDataImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/SignatureException.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/EncryptedType.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/CredentialContextSet.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/KANonceBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSURIUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/DEREncodedKeyValue.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/SignableXMLObject.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/QBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/AbstractExtensibleXMLObjectUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509SerialNumberImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/AbstractSingletonFactory.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/AbstractCredentialResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/XSDateTime.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/validator/XSIntegerSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/parse/LoggingErrorHandler.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/X509IssuerSerialCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/RecipientKeyInfo.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSDateTimeUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509IssuerSerialUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSQNameImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/XPathImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/Signature.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/BasicX509CredentialNameEvaluator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/ReferenceListMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/NamedCurveBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSIntegerMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/DEREncodedKeyValueBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/validator/EncryptedTypeSchemaValidator.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/io/UnmarshallingException.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509SubjectNameImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/RSAKeyValueUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/CredentialResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptionPropertiesMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/SimpleRetrievalMethodEncryptedKeyResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/TransformBuilder.java

* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/X509KeyManagerX509CredentialAdapter.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/criteria/EvaluableX509DigestCredentialCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509IssuerSerialMarshaller.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/tls/StrictHostnameVerifier.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/Criteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/TransformsMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/CertPathPKIXValidationOptions.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/validator/ReferenceListSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/P.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/AbstractElementExtensibleXMLObject.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/validator/CipherDataSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyInfoTypeMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSAnyMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/AttributeMap.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/CipherValue.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/SignatureUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/NamedCurveUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/KeyInfoGeneratorManager.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/OAEPparamsImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/CipherReferenceImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/CarriedKeyNameImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/IdBearing.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509CertificateImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/parse/StaticBasicParserPool.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyNameBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/PGPDataImpl.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/PKIXValidationInformationResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/OriginatorKeyInfoBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/Transforms.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/provider/KeyInfoReferenceProvider.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptedKeyImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509SubjectNameBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/validation/Validator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/SeedBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/PublicKey.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/validator/TransformsSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptionMethodMarshaller.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/X509Certificate.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/EncryptionProperty.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509CRLImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/FilesystemCredentialResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/KeySizeImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/AgreementMethodBuilder.java

* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/CipherReferenceUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/BasicSecurityConfiguration.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/KeyReferenceBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/KeyInfoTypeSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/SeedImpl.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/PGPDataMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/EncryptedData.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyInfoUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/Encrypter.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/IPAddressHelper.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSBooleanImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/AbstractElementExtensibleXMLObjectUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509DigestImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/PgenCounterImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/PublicBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/StaticKeyInfoCredentialResolver.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/validator/EncryptionPropertySchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSStringMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/DecryptionException.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/ReferenceTypeMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/PgenCounterBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/PKIXValidationOptions.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/criteria/KeyLengthCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/DSAKeyValueMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptedKeyUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/ModulusBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSStringImpl.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/BasicCredential.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/Y.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/GeneratorBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/PgenCounterBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyInfoTypeUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/PGPData.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/XMLSignatureBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/KeyInfoGeneratorFactory.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/NamedKeyInfoGeneratorManager.java
* /xmltooling-1-4-4-sources-2-
jar/org/opensaml/xml/encryption/validator/EncryptionPropertiesSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/LazyMap.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/YBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/KeyEncryptionParameters.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/ReferenceType.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/CredentialContext.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509SerialNumberUnmarshaller.java

* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/SigningUtil.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/DHKeyValueMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSStringUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/EncryptionConstants.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/CriteriaFilteringIterable.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/DSAKeyValueUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/MgmtData.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/ReferenceTypeUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/KeyInfoCredentialContext.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptedDataMarshaller.java
* /xmltooling-1-4-4-sources-2-
jar/org/opensaml/xml/security/credential/criteria/EvaluableCredentialCriteriaRegistry.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/criteria/KeyAlgorithmCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/criteria/KeyNameCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSURIBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/AbstractXMLObjectBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/QImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyValueMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/GeneratorImpl.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/KeyReference.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/KeyInfo.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/XSString.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/RSAKeyValueMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyValueUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/RSAKeyValueImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/PGPKeyIDBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/XPathBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/CertPathPKIXTrustEvaluator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/EncryptionException.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/criteria/PeerEntityIDCriteria.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSIntegerUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/PKIXValidationInformation.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/validator/CipherReferenceSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/ECKeyValueSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509SKIImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/KeyInfoReference.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/DHKeyValue.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/XSAny.java
* /xmltooling-1-4-4-sources-2-
jar/org/opensaml/xml/security/credential/AbstractCriteriaFilteringCredentialResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/PKIXX509CredentialTrustEngine.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/provider/AbstractKeyInfoProvider.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/ReferenceList.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/StaticPKIXValidationInformationResolver.java

* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyValueBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/CipherReference.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/JBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/CryptoBinaryMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/CipherDataMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/validation/ValidationException.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/CipherValueBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/SPKISexpImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/ExponentImpl.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/io/MarshallingException.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/RetrievalMethodImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/XMLAttributeHelper.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyInfoMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/TransformsUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/ContentReference.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/X509Data.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptedKeyMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/KeyInfoType.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/J.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/validation/AbstractValidatingXMLObject.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/PGPKeyID.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSURIMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/RetrievalMethodMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/PKIXSignatureTrustEngine.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/ValueTypeIndexedMap.java
* /xmltooling-1-4-4-sources-2-
jar/org/opensaml/xml/security/credential/criteria/EvaluablePublicKeyCredentialCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/DSAKeyValueImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/ReferenceTypeImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/criteria/EvaluableCredentialCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509IssuerNameImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/KeyReferenceMarshaller.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509IssuerSerialImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/SPKISexp.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/X509DigestSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509IssuerSerialBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/ConfigurationException.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/Transform.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/DSAKeyValueBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/TransformsBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSDateTimeMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/validation/ValidatorSuite.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/CipherDataUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/CryptoBinaryUnmarshaller.java
*

/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/parse/BasicParserPool.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/P.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptionPropertiesUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/KeyInfoGenerator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/criteria/UsageCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/SecurityTestHelper.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/XMLHelper.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/SignatureImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/XMLObjectBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/DEREncodedKeyValueImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/SchemaBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/io/Unmarshaller.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509DataImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/trust/ExplicitKeyTrustEvaluator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSAnyUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/PImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/OAEPparamsBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/AgreementMethodImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/DHKeyValueImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/KeyStoreCredentialResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/DHKeyValueUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/TransformSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/LangBearing.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSDateTimeImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/AbstractExtensibleXMLObjectMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/ApacheXMLSecurityConstants.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSIntegerBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/X509DataSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/CipherDataBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/ECPointType.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyNameImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptionPropertyBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSQNameMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/TransformsBuilder.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/SignatureValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/ModulusImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/validator/XSStringSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptionMethodBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyInfoImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/Decrypter.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/XSURI.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/RecipientKeyInfoUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/Configuration.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/SeedBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/ECKeyValueUnmarshaller.java

* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/KeySize.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/AgreementMethodUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptionPropertiesImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/ChainingCredentialResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/BasicPKIXValidationInformation.java
* /xmltooling-1-4-4-sources-2-
jar/org/opensaml/xml/security/credential/criteria/EvaluableKeyLengthCredentialCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/CipherDataImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/CryptoBinaryImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/TransformImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/AbstractXMLObject.java
* /xmltooling-1-4-4-sources-2-
jar/org/opensaml/xml/security/credential/criteria/EvaluableUsageCredentialCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/QBuilder.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509DigestUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/SecurityException.java
* /xmltooling-1-4-4-sources-2-
jar/org/opensaml/xml/security/credential/criteria/EvaluableX509IssuerSerialCredentialCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/G.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/validator/XSDateTimeSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/OriginatorKeyInfoImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/EvaluableCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyInfoBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSBase64BinaryMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/MgmtDataImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/ECKeyValueImpl.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/X509Digest.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/XPath.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509SerialNumberBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/validator/XSBase64BinarySchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/trust/ExplicitKeyTrustEngine.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509DataMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/RetrievalMethod.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/Q.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/io/MarshallerFactory.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/YImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/ReferenceListUnmarshaller.java
*
 /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/OAEPparams.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptedDataUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSAnyBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/ClassIndexedSet.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptionPropertyImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/validation/ValidatingXMLObject.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509DigestBuilder.java

* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/InternalX500DNHandler.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/AbstractEncryptedKeyResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/PgenCounterImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/AgreementMethodMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/ECKeyValueMarshaller.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/AbstractXMLEncryptionMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509DataUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/XMLObject.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/ChainingSignatureTrustEngine.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/Generator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/RetrievalMethodBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/validator/ReferenceTypeSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/parse/ParserPool.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/BaseSignatureTrustEngine.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/X509SubjectNameCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptedTypeUnmarshaller.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/provider/InlineX509DataProvider.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/DataReferenceBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/EncryptedKey.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509DataBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/CriteriaFilteringIterator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/KeyStoreX509CredentialAdapter.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/PGPDataBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/ChainingEncryptedKeyResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/AbstractXMLSignatureUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/SingletonFactory.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/DEREncodedKeyValueUnmarshaller.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/trust/TrustEngine.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509IssuerNameBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/X509IssuerName.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/PublicImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/EncryptedKeyResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/ECKeyValue.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/Credential.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/SignatureMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/SpaceBearing.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/IDIndex.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509SKIBuilder.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSAnyImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/provider/DSAKeyValueProvider.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSQNameUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/io/BaseXMLObjectUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/CryptoBinaryBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/KeyValueSchemaValidator.java

* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/ECKeyValueBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/X509DigestMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/GBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/X509KeyInfoGeneratorFactory.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/AbstractCredential.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/EncryptionParameters.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/NamedCurveSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/validator/EncryptionMethodSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/OriginatorKeyInfoUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSIntegerImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/DigestMethodMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/io/Marshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/XMLRuntimeException.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/PublicKeyBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/provider/DEREncodedKeyValueProvider.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/TransformsImpl.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/AbstractExtensibleXMLObject.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/DocumentInternalIDContentReference.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/CipherValueImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/RSAKeyValue.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/parse/ClasspathResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/CipherReferenceBuilder.java
* /xmltooling-1-4-4-sources-2-
jar/org/opensaml/xml/security/credential/criteria/EvaluableX509CertSelectorCredentialCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/CarriedKeyNameBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/KANonceImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/AbstractWrappedSingletonFactory.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/NamedCurve.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSBase64BinaryUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/EncryptedDataBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/X509CRL.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/ReferenceListBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/ElementExtensibleXMLObject.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/XSBoolean.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/CarriedKeyName.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/KeyInfoResolutionContext.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/DSAKeyValueSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/RSAKeyValueBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/X509SerialNumber.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/SignatureBuilder.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/DSAKeyValue.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/AttributeExtensibleXMLObject.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSDateTimeBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/DataReferenceMarshaller.java

* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/DefaultSecurityConfigurationBootstrap.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/SPKIDataSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/X509Util.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/Q.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/CollectionKeyInfoCredentialResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/PKIXTrustEngine.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/KeyReferenceUnmarshaller.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyInfoReferenceImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSBase64BinaryBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/PgenCounter.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/AbstractSignableXMLObject.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSBooleanMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/io/AbstractXMLObjectUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/PGPKeyIDImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/AgreementMethod.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/MgmtDataBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/X509SubjectName.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/X509SerialNumberSchemaValidator.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/X509Credential.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/Public.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/PBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/criteria/PublicKeyCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSQNameBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/SignatureSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/Seed.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/RetrievalMethodUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/provider/RSAKeyValueProvider.java
* /xmltooling-1-4-4-sources-2-
jar/org/opensaml/xml/encryption/SimpleKeyInfoReferenceEncryptedKeyResolver.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/SPKIDataMarshaller.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/GImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/SPKIDataUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/QImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/impl/DataReferenceUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/PBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/CryptoBinary.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/AbstractValidatingSignableXMLObject.java
* /xmltooling-1-4-4-sources-2-
jar/org/opensaml/xml/security/credential/criteria/EvaluableX509SubjectNameCredentialCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/BaseBearing.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/trust/ChainingTrustEngine.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/keyinfo/BasicProviderKeyInfoCredentialResolver.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/Seed.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/validator/KeySizeSchemaValidator.java

* /xmltooling-1-4-4-sources-2-
jar/org/opensaml/xml/security/credential/criteria/EvaluableKeyNameCredentialCriteria.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/KeyName.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/XSQName.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/XMLSignatureCredentialContext.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/DEREncodedKeyValueMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/AbstractXMLSignatureMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyInfoReferenceUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/impl/XSBase64BinaryImpl.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/x509/BasicX509Credential.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/XSBase64Binary.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/encryption/CipherData.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/PGPKeyPacket.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/credential/BasicKeyInfoGeneratorFactory.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/TransformUnmarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/KeyValue.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/IndexedXMLObjectChildrenList.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/KeyInfoReferenceBuilder.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/RSAKeyValueSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/validator/TransformsSchemaValidator.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/SPKIDataBuilder.java
*
/xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/security/trust/TrustedCredentialTrustEngine.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/signature/impl/NamedCurveMarshaller.java
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/schema/XSBooleanValue.java
No license file was found, but licenses were detected in source scan.

#
Copyright ©[2011] World Wide Web Consortium
(Massachusetts Institute of Technology,
European Research Consortium for Informatics and Mathematics,
Keio University). All Rights Reserved.
This work is distributed under the W3C® Software License [1] in the
hope that it will be useful, but WITHOUT ANY WARRANTY; without even
the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR
PURPOSE.
[1] http://www.w3.org/Consortium/Legal/2002/copyright

Found in path(s):
* /xmltooling-1-4-4-sources-2-jar/schema/xenc11-schema.xsd
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the University Corporation for Advanced Internet Development,
* Inc. (UCAID) under one or more contributor license agreements. See the
* NOTICE file distributed with this work for additional information regarding
* copyright ownership. The UCAID licenses this file to You under the Apache

```
* License, Version 2.0 (the "License"); you may not use this file except in
* compliance with the License.  You may obtain a copy of the License at
*
*    http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* Encodes and decodes to and from Base64 notation.
*
* <p>
* Change Log:
*
 </p>
* <ul>
* <li>v2.1 - Cleaned up javadoc comments and unused variables and methods. Added some convenience methods
for reading
* and writing to and from files.</li>
* <li>v2.0.2 - Now specifies UTF-8 encoding in places where the code fails on systems with other encodings (like
* EBCDIC).</li>
* <li>v2.0.1 - Fixed an error when decoding a single byte, that is, when the encoded data was a single byte.</li>
* <li>v2.0 - I got rid of methods that used booleans to set options. Now everything is more consolidated and cleaner.
* The code now detects when data that's being decoded is gzip-compressed and will decompress it automatically.
* Generally things are cleaner. You'll probably have to change some method calls that you were making to support
the
* new options format (<tt>int</tt>s that you "OR" together).</li>
* <li>v1.5.1 - Fixed bug when decompressing and decoding to a byte[] using
* <tt>decode( String s, boolean gzipCompressed )</tt>. Added the ability to "suspend" encoding
 in the Output Stream
* so you can turn on and off the encoding if you need to embed base64 data in an otherwise "normal" stream (like an
XML
* file).</li>
* <li>v1.5 - Output stream pases on flush() command but doesn't do anything itself. This helps when using GZIP
* streams. Added the ability to GZip-compress objects before encoding them.</li>
* <li>v1.4 - Added helper methods to read/write files.</li>
* <li>v1.3.6 - Fixed OutputStream.flush() so that 'position' is reset.</li>
* <li>v1.3.5 - Added flag to turn on and off line breaks. Fixed bug in input stream where last buffer being read, if
* not completely full, was not returned.</li>
* <li>v1.3.4 - Fixed when "improperly padded stream" error was thrown at the wrong time.</li>
* <li>v1.3.3 - Fixed I/O streams which were totally messed up.</li>
* </ul>
*
* <p>
* I am placing this code in the Public Domain. Do with it as you will. This software comes with no guarantees or
```

* warranties but with plenty of well-wishing
instead! Please visit <a
* href="http://iharder.net/base64">http://iharder.net/base64 periodically to check for updates or to contribute
* improvements.
* </p>
*
* @author Robert Harder
* @author rob@iharder.net
* @version 2.1
*/

Found in path(s):
* /xmltooling-1-4-4-sources-2-jar/org/opensaml/xml/util/Base64.java

1.445 yang-common 0.8.4-Beryllium-SR4

1.445.1 Available under license :

Found license 'Eclipse Public License 1.0' in 'Copyright (c) 2013 Cisco Systems, Inc. and others. All rights reserved. This program and the accompanying materials are made available under the terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2013 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2015 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2014 Brocade Communications Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'

1.446 mibble-commercial-mibs 2.9.3

1.446.1 Available under license :

No license file was found, but licenses were detected in source scan.

RFC1213-MIB DEFINITIONS ::= BEGIN

IMPORTS
    mgmt, NetworkAddress, IpAddress, Counter, Gauge,
        TimeTicks
      FROM RFC1155-SMI
    OBJECT-TYPE
        FROM RFC-1212;

-- This MIB module uses the extended OBJECT-TYPE macro as
-- defined in [14];

```
--  MIB-II (same prefix as MIB-I)

mib-2      OBJECT IDENTIFIER ::= { mgmt 1 }

-- textual conventions

DisplayString ::=
  OCTET STRING
-- This data type is used to model textual information taken
-- from the NVT ASCII character set.  By convention, objects
-- with this syntax are declared as having

--
--      SIZE (0..255)

PhysAddress ::=
  OCTET STRING
-- This data type is used to model media addresses.  For many
-- types of media, this will be in a binary representation.
-- For example, an ethernet address would be represented as
-- a string of 6 octets.


-- groups in MIB-II

system       OBJECT IDENTIFIER ::= { mib-2 1 }

interfaces
  OBJECT IDENTIFIER ::= { mib-2 2 }

at          OBJECT IDENTIFIER ::= { mib-2 3 }

ip          OBJECT IDENTIFIER ::= { mib-2 4 }

icmp        OBJECT IDENTIFIER ::= { mib-2 5 }

tcp         OBJECT IDENTIFIER ::= { mib-2 6 }

udp         OBJECT IDENTIFIER ::= { mib-2 7 }

egp         OBJECT IDENTIFIER ::= { mib-2 8 }

-- historical (some say hysterical)
-- cmot      OBJECT IDENTIFIER ::= { mib-2 9 }

transmission OBJECT IDENTIFIER ::= { mib-2 10 }
```

```
snmp        OBJECT IDENTIFIER ::= { mib-2 11 }


-- the System group

-- Implementation of the System group is mandatory for all
-- systems.  If an agent is not configured to have a value
-- for any of these variables, a string of length 0 is
-- returned.

sysDescr OBJECT-TYPE
  SYNTAX  DisplayString (SIZE (0..255))
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "A textual description of the entity.  This value
        should include the full name and version
        identification of the
 system's hardware type,
        software operating-system, and networking
        software.  It is mandatory that this only contain
        printable ASCII characters."
  ::= { system 1 }

sysObjectID OBJECT-TYPE
  SYNTAX  OBJECT IDENTIFIER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The vendor's authoritative identification of the
        network management subsystem contained in the
        entity.  This value is allocated within the SMI
        enterprises subtree (1.3.6.1.4.1) and provides an
        easy and unambiguous means for determining `what
        kind of box' is being managed.  For example, if
        vendor `Flintstones, Inc.' was assigned the
        subtree 1.3.6.1.4.1.4242, it could assign the
        identifier 1.3.6.1.4.1.4242.1.1 to its `Fred
        Router'."
  ::= { system 2 }

sysUpTime OBJECT-TYPE
  SYNTAX  TimeTicks
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
```

"The time (in hundredths of a second) since the
network management portion of the system was last
re-initialized."
::= { system 3 }

sysContact OBJECT-TYPE
SYNTAX DisplayString (SIZE (0..255))
ACCESS read-write
STATUS mandatory
DESCRIPTION
"The textual identification of the contact person
for this managed node, together with information
on how to contact this person."
::= { system 4 }

sysName OBJECT-TYPE
SYNTAX DisplayString (SIZE (0..255))
ACCESS read-write
STATUS mandatory
DESCRIPTION
"An administratively-assigned name for this
managed node. By convention, this is the node's
fully-qualified domain name."
::= { system 5 }

sysLocation OBJECT-TYPE
SYNTAX DisplayString (SIZE (0..255))
ACCESS read-write
STATUS mandatory
DESCRIPTION
"The physical location of this node (e.g.,
`telephone closet,
3rd floor')."
::= { system 6 }

sysServices OBJECT-TYPE
SYNTAX INTEGER (0..127)
ACCESS read-only
STATUS mandatory
DESCRIPTION
"A value which indicates the set of services that
this entity primarily offers.

The value is a sum. This sum initially takes the
value zero, Then, for each layer, L, in the range
1 through 7, that this node performs transactions
for, 2 raised to (L - 1) is added to the sum. For
example, a node which performs primarily routing

```
        functions would have a value of 4 (2^(3-1)).  In
        contrast, a node which is a host offering
        application services would have a value of 72
        (2^(4-1) + 2^(7-1)).  Note that in the context of
        the Internet suite of protocols, values should be
        calculated accordingly:

            layer  functionality
                1  physical (e.g., repeaters)

             2  datalink/subnetwork (e.g., bridges)
                3  internet (e.g., IP gateways)
                4  end-to-end  (e.g., IP hosts)
                7  applications (e.g., mail relays)

        For systems including OSI protocols, layers 5 and
        6 may also be counted."
    ::= { system 7 }

-- the Interfaces group

-- Implementation of the Interfaces group is mandatory for
-- all systems.

ifNumber OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The number of network interfaces (regardless of
        their current state) present on this system."
    ::= { interfaces 1 }


-- the Interfaces table

-- The Interfaces table contains information on the entity's
-- interfaces.  Each interface is thought of as being
-- attached to a `subnetwork'.  Note that this term should
-- not be confused with `subnet' which refers to an
-- addressing partitioning scheme used in the Internet suite
-- of
 protocols.

ifTable OBJECT-TYPE
    SYNTAX  SEQUENCE OF IfEntry
    ACCESS  not-accessible
    STATUS  mandatory
```

```
  DESCRIPTION
        "A list of interface entries.  The number of
        entries is given by the value of ifNumber."
  ::= { interfaces 2 }

ifEntry OBJECT-TYPE
  SYNTAX  IfEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "An interface entry containing objects at the
        subnetwork layer and below for a particular
        interface."
  INDEX   { ifIndex }
  ::= { ifTable 1 }

IfEntry ::=
  SEQUENCE {
    ifIndex
       INTEGER,
    ifDescr
       DisplayString,
    ifType
       INTEGER,
    ifMtu
       INTEGER,
    ifSpeed
       Gauge,
    ifPhysAddress
       PhysAddress,
    ifAdminStatus
       INTEGER,
    ifOperStatus
       INTEGER,
    ifLastChange
       TimeTicks,
    ifInOctets
       Counter,
    ifInUcastPkts
        Counter,
    ifInNUcastPkts
       Counter,
    ifInDiscards
       Counter,
    ifInErrors
       Counter,
    ifInUnknownProtos
       Counter,
```

```
      ifOutOctets
         Counter,
      ifOutUcastPkts
         Counter,
      ifOutNUcastPkts
         Counter,
      ifOutDiscards
         Counter,
      ifOutErrors
         Counter,
      ifOutQLen
         Gauge,
      ifSpecific
         OBJECT IDENTIFIER
   }

ifIndex OBJECT-TYPE
   SYNTAX  INTEGER
   ACCESS  read-only
   STATUS  mandatory
   DESCRIPTION
         "A unique value for each interface.  Its value
         ranges between 1 and the value of ifNumber.  The
         value for each interface must remain constant at
         least from one re-initialization of the entity's
         network management system to the next re-
         initialization."
   ::= { ifEntry 1 }

ifDescr OBJECT-TYPE
   SYNTAX  DisplayString
 (SIZE (0..255))
   ACCESS  read-only
   STATUS  mandatory
   DESCRIPTION
         "A textual string containing information about the
         interface.  This string should include the name of
         the manufacturer, the product name and the version
         of the hardware interface."
   ::= { ifEntry 2 }

ifType OBJECT-TYPE
   SYNTAX  INTEGER {
            other(1),         -- none of the following
            regular1822(2),
            hdh1822(3),
            ddn-x25(4),
            rfc877-x25(5),
```

```
            ethernet-csmacd(6),
            iso88023-csmacd(7),
            iso88024-tokenBus(8),
            iso88025-tokenRing(9),
            iso88026-man(10),
            starLan(11),
            proteon-10Mbit(12),
            proteon-80Mbit(13),
            hyperchannel(14),
            fddi(15),
            lapb(16),
            sdlc(17),
            ds1(18),          -- T-1

        e1(19),           -- european equiv. of T-1
            basicISDN(20),
            primaryISDN(21),   -- proprietary serial
            propPointToPointSerial(22),
            ppp(23),
            softwareLoopback(24),
            eon(25),           -- CLNP over IP [11]
            ethernet-3Mbit(26),
            nsip(27),          -- XNS over IP
            slip(28),          -- generic SLIP
            ultra(29),         -- ULTRA technologies
            ds3(30),           -- T-3
            sip(31),           -- SMDS
            frame-relay(32)
          }
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
          "The type of interface, distinguished according to
          the physical/link protocol(s) immediately `below'
          the network layer in the protocol stack."
    ::= { ifEntry 3 }

  ifMtu OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION

        "The size of the largest datagram which can be
          sent/received on the interface, specified in
          octets.  For interfaces that are used for
          transmitting network datagrams, this is the size
          of the largest network datagram that can be sent
```

```
        on the interface."
  ::= { ifEntry 4 }

ifSpeed OBJECT-TYPE
  SYNTAX  Gauge
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "An estimate of the interface's current bandwidth
        in bits per second.  For interfaces which do not
        vary in bandwidth or for those where no accurate
        estimation can be made, this object should contain
        the nominal bandwidth."
  ::= { ifEntry 5 }

ifPhysAddress OBJECT-TYPE
  SYNTAX  PhysAddress
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The interface's address at the protocol layer
        immediately `below' the network layer in the
        protocol stack.  For
 interfaces which do not have
        such an address (e.g., a serial line), this object
        should contain an octet string of zero length."
  ::= { ifEntry 6 }

ifAdminStatus OBJECT-TYPE
  SYNTAX  INTEGER {
            up(1),       -- ready to pass packets
            down(2),
            testing(3)   -- in some test mode
          }
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "The desired state of the interface.  The
        testing(3) state indicates that no operational
        packets can be passed."
  ::= { ifEntry 7 }

ifOperStatus OBJECT-TYPE
  SYNTAX  INTEGER {
            up(1),       -- ready to pass packets
            down(2),
            testing(3)   -- in some test mode
          }
```

```
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The current operational state of the interface.
        The testing(3) state indicates that no operational
        packets can
 be passed."
  ::= { ifEntry 8 }

ifLastChange OBJECT-TYPE
  SYNTAX  TimeTicks
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The value of sysUpTime at the time the interface
        entered its current operational state.  If the
        current state was entered prior to the last re-
        initialization of the local network management
        subsystem, then this object contains a zero
        value."
  ::= { ifEntry 9 }

ifInOctets OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of octets received on the
        interface, including framing characters."
  ::= { ifEntry 10 }

ifInUcastPkts OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of subnetwork-unicast packets
        delivered to a higher-layer protocol."
  ::= { ifEntry 11 }

ifInNUcastPkts OBJECT-TYPE
  SYNTAX  Counter
   ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of non-unicast (i.e., subnetwork-
        broadcast or subnetwork-multicast) packets
        delivered to a higher-layer protocol."
```

::= { ifEntry 12 }

ifInDiscards OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of inbound packets which were chosen to be discarded even though no errors had been detected to prevent their being deliverable to a higher-layer protocol. One possible reason for discarding such a packet could be to free up buffer space."
::= { ifEntry 13 }

ifInErrors OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of inbound packets that contained errors preventing them from being deliverable to a higher-layer protocol."
::= { ifEntry 14 }

ifInUnknownProtos
OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of packets received via the interface which were discarded because of an unknown or unsupported protocol."
::= { ifEntry 15 }

ifOutOctets OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The total number of octets transmitted out of the interface, including framing characters."
::= { ifEntry 16 }

ifOutUcastPkts OBJECT-TYPE
SYNTAX Counter
ACCESS read-only

```
  STATUS  mandatory
  DESCRIPTION
        "The total number of packets that higher-level
        protocols requested be transmitted to a
        subnetwork-unicast address, including those that
        were discarded or not sent."
  ::= { ifEntry 17 }

ifOutNUcastPkts OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number
 of packets that higher-level
        protocols requested be transmitted to a non-
        unicast (i.e., a subnetwork-broadcast or
        subnetwork-multicast) address, including those
        that were discarded or not sent."
  ::= { ifEntry 18 }

ifOutDiscards OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of outbound packets which were chosen
        to be discarded even though no errors had been
        detected to prevent their being transmitted.  One
        possible reason for discarding such a packet could
        be to free up buffer space."
  ::= { ifEntry 19 }

ifOutErrors OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of outbound packets that could not be
        transmitted because of errors."
  ::= { ifEntry 20 }

ifOutQLen OBJECT-TYPE
  SYNTAX  Gauge
  ACCESS  read-only
  STATUS  mandatory
   DESCRIPTION
        "The length of the output packet queue (in
```

```
        packets)."
    ::= { ifEntry 21 }

ifSpecific OBJECT-TYPE
    SYNTAX  OBJECT IDENTIFIER
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "A reference to MIB definitions specific to the
        particular media being used to realize the
        interface.  For example, if the interface is
        realized by an ethernet, then the value of this
        object refers to a document defining objects
        specific to ethernet.  If this information is not
        present, its value should be set to the OBJECT
        IDENTIFIER { 0 0 }, which is a syntatically valid
        object identifier, and any conformant
        implementation of ASN.1 and BER must be able to
        generate and recognize this value."
    ::= { ifEntry 22 }


-- the Address Translation group

-- Implementation of the Address Translation group is
-- mandatory for all
 systems.  Note however that this group
-- is deprecated by MIB-II. That is, it is being included

-- solely for compatibility with MIB-I nodes, and will most
-- likely be excluded from MIB-III nodes.  From MIB-II and
-- onwards, each network protocol group contains its own
-- address translation tables.

-- The Address Translation group contains one table which is
-- the union across all interfaces of the translation tables
-- for converting a NetworkAddress (e.g., an IP address) into
-- a subnetwork-specific address.  For lack of a better term,
-- this document refers to such a subnetwork-specific address
-- as a `physical' address.

-- Examples of such translation tables are: for broadcast
-- media where ARP is in use, the translation table is
-- equivalent to the ARP cache; or, on an X.25 network where
-- non-algorithmic translation to X.121 addresses is
-- required, the translation table contains the
-- NetworkAddress to X.121 address equivalences.
```

```
atTable OBJECT-TYPE
  SYNTAX
 SEQUENCE OF AtEntry
  ACCESS  not-accessible
  STATUS  deprecated
  DESCRIPTION
        "The Address Translation tables contain the
        NetworkAddress to `physical' address equivalences.
        Some interfaces do not use translation tables for
        determining address equivalences (e.g., DDN-X.25
        has an algorithmic method); if all interfaces are
        of this type, then the Address Translation table
        is empty, i.e., has zero entries."
  ::= { at 1 }

atEntry OBJECT-TYPE
  SYNTAX  AtEntry
  ACCESS  not-accessible
  STATUS  deprecated
  DESCRIPTION
        "Each entry contains one NetworkAddress to
        `physical' address equivalence."
  INDEX   { atIfIndex,
            atNetAddress }
  ::= { atTable 1 }

AtEntry ::=
  SEQUENCE {
     atIfIndex
        INTEGER,
     atPhysAddress
        PhysAddress,
     atNetAddress
        NetworkAddress
  }

atIfIndex OBJECT-TYPE
  SYNTAX
 INTEGER
  ACCESS  read-write
  STATUS  deprecated
  DESCRIPTION
        "The interface on which this entry's equivalence
        is effective.  The interface identified by a
        particular value of this index is the same
        interface as identified by the same value of
        ifIndex."
  ::= { atEntry 1 }
```

```
atPhysAddress OBJECT-TYPE
  SYNTAX  PhysAddress
  ACCESS  read-write
  STATUS  deprecated
  DESCRIPTION
          "The media-dependent `physical' address.

          Setting this object to a null string (one of zero
          length) has the effect of invaliding the
          corresponding entry in the atTable object.  That
          is, it effectively dissasociates the interface
          identified with said entry from the mapping
          identified with said entry.  It is an
          implementation-specific matter as to whether the
          agent removes an invalidated entry from the table.
          Accordingly,
 management stations must be prepared
          to receive tabular information from agents that
          corresponds to entries not currently in use.
          Proper interpretation of such entries requires
          examination of the relevant atPhysAddress object."
  ::= { atEntry 2 }

atNetAddress OBJECT-TYPE
  SYNTAX  NetworkAddress
  ACCESS  read-write
  STATUS  deprecated
  DESCRIPTION
          "The NetworkAddress (e.g., the IP address)
          corresponding to the media-dependent `physical'
          address."
  ::= { atEntry 3 }


-- the IP group

-- Implementation of the IP group is mandatory for all
-- systems.

ipForwarding OBJECT-TYPE
  SYNTAX  INTEGER {
             forwarding(1),    -- acting as a gateway
             not-forwarding(2) -- NOT acting as a gateway
          }
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
```

"The indication of whether this entity is acting
as an IP gateway in respect
to the forwarding of
datagrams received by, but not addressed to, this
entity. IP gateways forward datagrams. IP hosts
do not (except those source-routed via the host).

Note that for some managed nodes, this object may
take on only a subset of the values possible.
Accordingly, it is appropriate for an agent to
return a `badValue' response if a management
station attempts to change this object to an
inappropriate value."
::= { ip 1 }

ipDefaultTTL OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-write
STATUS mandatory
DESCRIPTION
"The default value inserted into the Time-To-Live
field of the IP header of datagrams originated at
this entity, whenever a TTL value is not supplied
by the transport layer protocol."
::= { ip 2 }

ipInReceives OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The total number of input datagrams received from
interfaces, including those received in error."
::= { ip 3 }

ipInHdrErrors OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of input datagrams discarded due to
errors in their IP headers, including bad
checksums, version number mismatch, other format
errors, time-to-live exceeded, errors discovered
in processing their IP options, etc."
::= { ip 4 }

ipInAddrErrors OBJECT-TYPE

```
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of input datagrams discarded because
        the IP address in their IP header's destination
        field was not a valid address to be received at
        this entity.  This count includes invalid
        addresses (e.g., 0.0.0.0) and addresses of
        unsupported Classes (e.g.,
 Class E).  For entities
        which are not IP Gateways and therefore do not
        forward datagrams, this counter includes datagrams
        discarded because the destination address was not
        a local address."
  ::= { ip 5 }

ipForwDatagrams OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of input datagrams for which this
        entity was not their final IP destination, as a
        result of which an attempt was made to find a
        route to forward them to that final destination.
        In entities which do not act as IP Gateways, this
        counter will include only those packets which were
        Source-Routed via this entity, and the Source-
        Route option processing was successful."
  ::= { ip 6 }

ipInUnknownProtos OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of locally-addressed
 datagrams
        received successfully but discarded because of an
        unknown or unsupported protocol."
  ::= { ip 7 }

ipInDiscards OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
```

```
        "The number of input IP datagrams for which no
        problems were encountered to prevent their
        continued processing, but which were discarded
        (e.g., for lack of buffer space).  Note that this
        counter does not include any datagrams discarded
        while awaiting re-assembly."
    ::= { ip 8 }

ipInDelivers OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The total number of input datagrams successfully
        delivered to IP user-protocols (including ICMP)."
    ::= { ip 9 }

ipOutRequests OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The total number of IP datagrams
 which local IP
        user-protocols (including ICMP) supplied to IP in
        requests for transmission.  Note that this counter
        does not include any datagrams counted in
        ipForwDatagrams."
    ::= { ip 10 }

ipOutDiscards OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The number of output IP datagrams for which no
        problem was encountered to prevent their
        transmission to their destination, but which were
        discarded (e.g., for lack of buffer space).  Note
        that this counter would include datagrams counted
        in ipForwDatagrams if any such packets met this
        (discretionary) discard criterion."
    ::= { ip 11 }

ipOutNoRoutes OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
```

```
  DESCRIPTION
        "The number of IP datagrams discarded because no
        route could be found to transmit them
 to their
        destination.  Note that this counter includes any
        packets counted in ipForwDatagrams which meet this
        `no-route' criterion.  Note that this includes any
        datagarms which a host cannot route because all of
        its default gateways are down."
  ::= { ip 12 }

ipReasmTimeout OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The maximum number of seconds which received
        fragments are held while they are awaiting
        reassembly at this entity."
  ::= { ip 13 }

ipReasmReqds OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of IP fragments received which needed
        to be reassembled at this entity."
  ::= { ip 14 }

ipReasmOKs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of IP datagrams successfully re-

       assembled."
  ::= { ip 15 }

ipReasmFails OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of failures detected by the IP re-
        assembly algorithm (for whatever reason: timed
        out, errors, etc).  Note that this is not
```

```
        necessarily a count of discarded IP fragments
        since some algorithms (notably the algorithm in
        RFC 815) can lose track of the number of fragments
        by combining them as they are received."
  ::= { ip 16 }

ipFragOKs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of IP datagrams that have been
        successfully fragmented at this entity."
  ::= { ip 17 }

ipFragFails OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of IP datagrams that have been
        discarded because they needed to
 be fragmented at
        this entity but could not be, e.g., because their
        Don't Fragment flag was set."
  ::= { ip 18 }

ipFragCreates OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of IP datagram fragments that have
        been generated as a result of fragmentation at
        this entity."
  ::= { ip 19 }

-- the IP address table

-- The IP address table contains this entity's IP addressing
-- information.

ipAddrTable OBJECT-TYPE
  SYNTAX  SEQUENCE OF IpAddrEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "The table of addressing information relevant to
```

```
        this entity's IP addresses."
  ::= { ip 20 }

ipAddrEntry OBJECT-TYPE
  SYNTAX  IpAddrEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "The addressing information for one of this
        entity's IP addresses."
  INDEX   { ipAdEntAddr }
  ::=
 { ipAddrTable 1 }

IpAddrEntry ::=
  SEQUENCE {
     ipAdEntAddr
        IpAddress,
     ipAdEntIfIndex
        INTEGER,
     ipAdEntNetMask
        IpAddress,
     ipAdEntBcastAddr
        INTEGER,
     ipAdEntReasmMaxSize
        INTEGER (0..65535)
  }

ipAdEntAddr OBJECT-TYPE
  SYNTAX  IpAddress
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The IP address to which this entry's addressing
        information pertains."
  ::= { ipAddrEntry 1 }

ipAdEntIfIndex OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The index value which uniquely identifies the
        interface to which this entry is applicable.  The
        interface identified by a particular value of this
        index is the same interface as identified by the
        same value of ifIndex."
  ::= { ipAddrEntry 2 }
```

```
ipAdEntNetMask OBJECT-TYPE
  SYNTAX  IpAddress
  ACCESS
 read-only
  STATUS  mandatory
  DESCRIPTION
        "The subnet mask associated with the IP address of
        this entry.  The value of the mask is an IP
        address with all the network bits set to 1 and all
        the hosts bits set to 0."
  ::= { ipAddrEntry 3 }

ipAdEntBcastAddr OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The value of the least-significant bit in the IP
        broadcast address used for sending datagrams on
        the (logical) interface associated with the IP
        address of this entry.  For example, when the
        Internet standard all-ones broadcast address is
        used, the value will be 1.  This value applies to
        both the subnet and network broadcasts addresses
        used by the entity on this (logical) interface."
  ::= { ipAddrEntry 4 }

ipAdEntReasmMaxSize OBJECT-TYPE
  SYNTAX  INTEGER (0..65535)
  ACCESS  read-only
   STATUS  mandatory
  DESCRIPTION
        "The size of the largest IP datagram which this
        entity can re-assemble from incoming IP fragmented
        datagrams received on this interface."
  ::= { ipAddrEntry 5 }

-- the IP routing table

-- The IP routing table contains an entry for each route
-- presently known to this entity.

ipRouteTable OBJECT-TYPE
  SYNTAX  SEQUENCE OF IpRouteEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
```

```
        "This entity's IP Routing table."
    ::= { ip 21 }

ipRouteEntry OBJECT-TYPE
    SYNTAX  IpRouteEntry
    ACCESS  not-accessible
    STATUS  mandatory
    DESCRIPTION
        "A route to a particular destination."
    INDEX   { ipRouteDest }
    ::= { ipRouteTable 1 }

IpRouteEntry ::=
    SEQUENCE {
        ipRouteDest
            IpAddress,
        ipRouteIfIndex
            INTEGER,
        ipRouteMetric1
            INTEGER,
        ipRouteMetric2
            INTEGER,
        ipRouteMetric3
             INTEGER,
        ipRouteMetric4
            INTEGER,
        ipRouteNextHop
            IpAddress,
        ipRouteType
            INTEGER,
        ipRouteProto
            INTEGER,
        ipRouteAge
            INTEGER,
        ipRouteMask
            IpAddress,
        ipRouteMetric5
            INTEGER,
        ipRouteInfo
            OBJECT IDENTIFIER
    }

ipRouteDest OBJECT-TYPE
    SYNTAX  IpAddress
    ACCESS  read-write
    STATUS  mandatory
    DESCRIPTION
        "The destination IP address of this route.  An
```

entry with a value of 0.0.0.0 is considered a
default route. Multiple routes to a single
destination can appear in the table, but access to
such multiple entries is dependent on the table-
access mechanisms defined by the network
management protocol in use."
::= { ipRouteEntry 1 }

ipRouteIfIndex OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-write
STATUS mandatory

DESCRIPTION
"The index value which uniquely identifies the
local interface through which the next hop of this
route should be reached. The interface identified
by a particular value of this index is the same
interface as identified by the same value of
ifIndex."
::= { ipRouteEntry 2 }

ipRouteMetric1 OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-write
STATUS mandatory
DESCRIPTION
"The primary routing metric for this route. The
semantics of this metric are determined by the
routing-protocol specified in the route's
ipRouteProto value. If this metric is not used,
its value should be set to -1."
::= { ipRouteEntry 3 }

ipRouteMetric2 OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-write
STATUS mandatory
DESCRIPTION
"An alternate routing metric for this route. The
semantics of this metric are determined
by the
routing-protocol specified in the route's
ipRouteProto value. If this metric is not used,
its value should be set to -1."
::= { ipRouteEntry 4 }

ipRouteMetric3 OBJECT-TYPE

```
  SYNTAX  INTEGER
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "An alternate routing metric for this route.  The
        semantics of this metric are determined by the
        routing-protocol specified in the route's
        ipRouteProto value.  If this metric is not used,
        its value should be set to -1."
  ::= { ipRouteEntry 5 }

ipRouteMetric4 OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "An alternate routing metric for this route.  The
        semantics of this metric are determined by the
        routing-protocol specified in the route's
        ipRouteProto value.  If this metric is not used,
        its value should be set to -1."
   ::= { ipRouteEntry 6 }

ipRouteNextHop OBJECT-TYPE
  SYNTAX  IpAddress
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "The IP address of the next hop of this route.
        (In the case of a route bound to an interface
        which is realized via a broadcast media, the value
        of this field is the agent's IP address on that
        interface.)"
  ::= { ipRouteEntry 7 }

ipRouteType OBJECT-TYPE
  SYNTAX  INTEGER {
            other(1),       -- none of the following

            invalid(2),     -- an invalidated route

                            -- route to directly
            direct(3),      -- connected (sub-)network

                            -- route to a non-local
            indirect(4)     -- host/network/sub-network
          }
  ACCESS  read-write
```

```
  STATUS  mandatory
  DESCRIPTION
          "The type of route.  Note that the values
          direct(3) and indirect(4) refer
to the notion of
          direct and indirect routing in the IP
          architecture.

          Setting this object to the value invalid(2) has
          the effect of invalidating the corresponding entry
          in the ipRouteTable object.  That is, it
          effectively dissasociates the destination
          identified with said entry from the route
          identified with said entry.  It is an
          implementation-specific matter as to whether the
          agent removes an invalidated entry from the table.
          Accordingly, management stations must be prepared
          to receive tabular information from agents that
          corresponds to entries not currently in use.
          Proper interpretation of such entries requires
          examination of the relevant ipRouteType object."
  ::= { ipRouteEntry 8 }

ipRouteProto OBJECT-TYPE
  SYNTAX  INTEGER {
              other(1),       -- none of the following


               -- non-protocol information,
                        -- e.g., manually configured
              local(2),       -- entries

                        -- set via a network
              netmgmt(3),     -- management protocol

                        -- obtained via ICMP,
              icmp(4),        -- e.g., Redirect

                        -- the remaining values are
                        -- all gateway routing
                        -- protocols
              egp(5),
              ggp(6),
              hello(7),
              rip(8),
              is-is(9),
              es-is(10),
              ciscoIgrp(11),
```

```
            bbnSpfIgp(12),
            ospf(13),
            bgp(14)
          }
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
          "The routing mechanism via which this route was
          learned.  Inclusion of values for gateway routing
          protocols
   is not intended to imply that hosts
          should support those protocols."
    ::= { ipRouteEntry 9 }

ipRouteAge OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-write
    STATUS  mandatory
    DESCRIPTION
          "The number of seconds since this route was last
          updated or otherwise determined to be correct.
          Note that no semantics of `too old' can be implied
          except through knowledge of the routing protocol
          by which the route was learned."
    ::= { ipRouteEntry 10 }

ipRouteMask OBJECT-TYPE
    SYNTAX  IpAddress
    ACCESS  read-write
    STATUS  mandatory
    DESCRIPTION
          "Indicate the mask to be logical-ANDed with the
          destination address before being compared to the
          value in the ipRouteDest field.  For those systems
          that do not support arbitrary subnet masks, an
          agent constructs the value of the ipRouteMask by
          determining whether the value of the correspondent
           ipRouteDest field belong to a class-A, B, or C
          network, and then using one of:

              mask           network
              255.0.0.0      class-A
              255.255.0.0    class-B
              255.255.255.0  class-C
          If the value of the ipRouteDest is 0.0.0.0 (a
          default route), then the mask value is also
          0.0.0.0.  It should be noted that all IP routing
          subsystems implicitly use this mechanism."
```

```
  ::= { ipRouteEntry 11 }

ipRouteMetric5 OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "An alternate routing metric for this route.  The
        semantics of this metric are determined by the
        routing-protocol specified in the route's
        ipRouteProto value.  If this metric is not used,
        its value should be set to -1."
  ::= { ipRouteEntry 12 }

ipRouteInfo OBJECT-TYPE
  SYNTAX  OBJECT IDENTIFIER
   ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "A reference to MIB definitions specific to the
        particular routing protocol which is responsible
        for this route, as determined by the value
        specified in the route's ipRouteProto value.  If
        this information is not present, its value should
        be set to the OBJECT IDENTIFIER { 0 0 }, which is
        a syntatically valid object identifier, and any
        conformant implementation of ASN.1 and BER must be
        able to generate and recognize this value."
  ::= { ipRouteEntry 13 }


-- the IP Address Translation table

-- The IP address translation table contain the IpAddress to
-- `physical' address equivalences.  Some interfaces do not
-- use translation tables for determining address
-- equivalences (e.g., DDN-X.25 has an algorithmic method);
-- if all interfaces are of this type, then the Address
-- Translation table is empty, i.e., has zero
 entries.

ipNetToMediaTable OBJECT-TYPE
  SYNTAX  SEQUENCE OF IpNetToMediaEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "The IP Address Translation table used for mapping
        from IP addresses to physical addresses."
```

```
  ::= { ip 22 }

ipNetToMediaEntry OBJECT-TYPE
  SYNTAX  IpNetToMediaEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "Each entry contains one IpAddress to `physical'
        address equivalence."
  INDEX   { ipNetToMediaIfIndex,
          ipNetToMediaNetAddress }
  ::= { ipNetToMediaTable 1 }

IpNetToMediaEntry ::=
  SEQUENCE {
     ipNetToMediaIfIndex
        INTEGER,
     ipNetToMediaPhysAddress
        PhysAddress,
     ipNetToMediaNetAddress
        IpAddress,
     ipNetToMediaType
        INTEGER
  }

ipNetToMediaIfIndex OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "The interface
 on which this entry's equivalence
        is effective.  The interface identified by a
        particular value of this index is the same
        interface as identified by the same value of
        ifIndex."
  ::= { ipNetToMediaEntry 1 }

ipNetToMediaPhysAddress OBJECT-TYPE
  SYNTAX  PhysAddress
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "The media-dependent `physical' address."
  ::= { ipNetToMediaEntry 2 }

ipNetToMediaNetAddress OBJECT-TYPE
  SYNTAX  IpAddress
```

```
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "The IpAddress corresponding to the media-
        dependent `physical' address."
  ::= { ipNetToMediaEntry 3 }

ipNetToMediaType OBJECT-TYPE
  SYNTAX  INTEGER {
            other(1),       -- none of the following
            invalid(2),     -- an invalidated mapping
            dynamic(3),
            static(4)
          }
  ACCESS  read-write
  STATUS  mandatory
   DESCRIPTION
        "The type of mapping.

        Setting this object to the value invalid(2) has
        the effect of invalidating the corresponding entry
        in the ipNetToMediaTable.  That is, it effectively
        dissasociates the interface identified with said
        entry from the mapping identified with said entry.
        It is an implementation-specific matter as to
        whether the agent removes an invalidated entry
        from the table.  Accordingly, management stations
        must be prepared to receive tabular information
        from agents that corresponds to entries not
        currently in use.  Proper interpretation of such
        entries requires examination of the relevant
        ipNetToMediaType object."
  ::= { ipNetToMediaEntry 4 }


-- additional IP objects

ipRoutingDiscards OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number
 of routing entries which were chosen
        to be discarded even though they are valid.  One
        possible reason for discarding such an entry could
        be to free-up buffer space for other routing
        entries."
```

```
  ::= { ip 23 }


-- the ICMP group

-- Implementation of the ICMP group is mandatory for all
-- systems.

icmpInMsgs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of ICMP messages which the
        entity received.  Note that this counter includes
        all those counted by icmpInErrors."
  ::= { icmp 1 }

icmpInErrors OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP messages which the entity
        received but determined as having ICMP-specific
        errors (bad ICMP checksums, bad length, etc.)."
  ::= { icmp 2 }

icmpInDestUnreachs OBJECT-TYPE
  SYNTAX  Counter

  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Destination Unreachable
        messages received."
  ::= { icmp 3 }

icmpInTimeExcds OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Time Exceeded messages
        received."
  ::= { icmp 4 }

icmpInParmProbs OBJECT-TYPE
```

```
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Parameter Problem messages
        received."
  ::= { icmp 5 }

icmpInSrcQuenchs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Source Quench messages
        received."
  ::= { icmp 6 }

icmpInRedirects OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Redirect messages received."
  ::= { icmp 7 }

icmpInEchos OBJECT-TYPE
   SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Echo (request) messages
        received."
  ::= { icmp 8 }

icmpInEchoReps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Echo Reply messages received."
  ::= { icmp 9 }

icmpInTimestamps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Timestamp (request) messages
```

```
        received."
  ::= { icmp 10 }

icmpInTimestampReps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Timestamp Reply messages
        received."
  ::= { icmp 11 }

icmpInAddrMasks OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Address Mask Request messages
        received."
  ::= {
 icmp 12 }

icmpInAddrMaskReps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Address Mask Reply messages
        received."
  ::= { icmp 13 }

icmpOutMsgs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of ICMP messages which this
        entity attempted to send.  Note that this counter
        includes all those counted by icmpOutErrors."
  ::= { icmp 14 }

icmpOutErrors OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP messages which this entity did
        not send due to problems discovered within ICMP
```

such as a lack of buffers. This value should not include errors discovered outside the ICMP layer such as the inability of IP to route the resultant datagram. In some implementations there may be no types of error which contribute to this counter's value."
::= { icmp 15 }

icmpOutDestUnreachs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of ICMP Destination Unreachable messages sent."
::= { icmp 16 }

icmpOutTimeExcds OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of ICMP Time Exceeded messages sent."
::= { icmp 17 }

icmpOutParmProbs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of ICMP Parameter Problem messages sent."
::= { icmp 18 }

icmpOutSrcQuenchs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of ICMP Source Quench messages sent."
::= { icmp 19 }

icmpOutRedirects OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS

```
  mandatory
  DESCRIPTION
        "The number of ICMP Redirect messages sent.  For a
        host, this object will always be zero, since hosts
        do not send redirects."
  ::= { icmp 20 }

icmpOutEchos OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Echo (request) messages sent."
  ::= { icmp 21 }

icmpOutEchoReps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Echo Reply messages sent."
  ::= { icmp 22 }

icmpOutTimestamps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Timestamp (request) messages
        sent."
  ::= { icmp 23 }

icmpOutTimestampReps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Timestamp Reply messages
        sent."
  ::= {
 icmp 24 }

icmpOutAddrMasks OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Address Mask Request messages
```

```
        sent."
  ::= { icmp 25 }

icmpOutAddrMaskReps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Address Mask Reply messages
        sent."
  ::= { icmp 26 }


-- the TCP group

-- Implementation of the TCP group is mandatory for all
-- systems that implement the TCP.

-- Note that instances of object types that represent
-- information about a particular TCP connection are
-- transient; they persist only as long as the connection
-- in question.

tcpRtoAlgorithm OBJECT-TYPE
  SYNTAX  INTEGER {
            other(1),    -- none of the following

            constant(2), -- a constant rto
            rsre(3),     -- MIL-STD-1778, Appendix B
            vanj(4)      -- Van Jacobson's algorithm [10]

          }
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The algorithm used to determine the timeout value
        used for retransmitting unacknowledged octets."
  ::= { tcp 1 }

tcpRtoMin OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The minimum value permitted by a TCP
        implementation for the retransmission timeout,
        measured in milliseconds.  More refined semantics
        for objects of this type depend upon the algorithm
```

used to determine the retransmission timeout. In particular, when the timeout algorithm is rsre(3), an object of this type has the semantics of the LBOUND quantity described in RFC 793."
::= { tcp 2 }

tcpRtoMax OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The maximum value permitted by a TCP implementation for the retransmission
timeout,
measured in milliseconds. More refined semantics for objects of this type depend upon the algorithm used to determine the retransmission timeout. In particular, when the timeout algorithm is rsre(3), an object of this type has the semantics of the UBOUND quantity described in RFC 793."
::= { tcp 3 }

tcpMaxConn OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The limit on the total number of TCP connections the entity can support. In entities where the maximum number of connections is dynamic, this object should contain the value -1."
::= { tcp 4 }

tcpActiveOpens OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of times TCP connections have made a direct transition to the SYN-SENT state from the CLOSED state."
::= { tcp 5 }

tcpPassiveOpens OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory

```
  DESCRIPTION
        "The number of times TCP connections have made a
        direct transition to the SYN-RCVD state from the
        LISTEN state."
  ::= { tcp 6 }

tcpAttemptFails OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of times TCP connections have made a
        direct transition to the CLOSED state from either
        the SYN-SENT state or the SYN-RCVD state, plus the
        number of times TCP connections have made a direct
        transition to the LISTEN state from the SYN-RCVD
        state."
  ::= { tcp 7 }

tcpEstabResets OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of times TCP connections have made a
        direct transition to the CLOSED state from either
        the
 ESTABLISHED state or the CLOSE-WAIT state."
  ::= { tcp 8 }

tcpCurrEstab OBJECT-TYPE
  SYNTAX  Gauge
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of TCP connections for which the
        current state is either ESTABLISHED or CLOSE-
        WAIT."
  ::= { tcp 9 }

tcpInSegs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of segments received, including
        those received in error.  This count includes
        segments received on currently established
```

```
        connections."
    ::= { tcp 10 }

tcpOutSegs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The total number of segments sent, including
        those on current connections but excluding those
        containing only retransmitted octets."
    ::= { tcp 11 }

tcpRetransSegs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
     STATUS  mandatory
    DESCRIPTION
        "The total number of segments retransmitted - that
        is, the number of TCP segments transmitted
        containing one or more previously transmitted
        octets."
    ::= { tcp 12 }


-- the TCP Connection table

-- The TCP connection table contains information about this
-- entity's existing TCP connections.

tcpConnTable OBJECT-TYPE
    SYNTAX  SEQUENCE OF TcpConnEntry
    ACCESS  not-accessible
    STATUS  mandatory
    DESCRIPTION
        "A table containing TCP connection-specific
        information."
    ::= { tcp 13 }

tcpConnEntry OBJECT-TYPE
    SYNTAX  TcpConnEntry
    ACCESS  not-accessible
    STATUS  mandatory
    DESCRIPTION
        "Information about a particular current TCP
        connection.  An object of this type is transient,
        in that it ceases to exist when (or soon after)
        the connection makes the transition to the CLOSED
```

```
        state."
    INDEX
    { tcpConnLocalAddress,
            tcpConnLocalPort,
            tcpConnRemAddress,
            tcpConnRemPort }
    ::= { tcpConnTable 1 }

TcpConnEntry ::=
    SEQUENCE {
      tcpConnState
        INTEGER,
      tcpConnLocalAddress
        IpAddress,
      tcpConnLocalPort
        INTEGER (0..65535),
      tcpConnRemAddress
        IpAddress,
      tcpConnRemPort
        INTEGER (0..65535)
    }

tcpConnState OBJECT-TYPE
    SYNTAX  INTEGER {
              closed(1),
              listen(2),
              synSent(3),
              synReceived(4),
              established(5),
              finWait1(6),
              finWait2(7),
              closeWait(8),
              lastAck(9),
              closing(10),
              timeWait(11),
              deleteTCB(12)
            }
    ACCESS  read-write
    STATUS  mandatory
    DESCRIPTION
            "The state of this TCP connection.

            The only value which may
 be set by a management
            station is deleteTCB(12).  Accordingly, it is
            appropriate for an agent to return a `badValue'
            response if a management station attempts to set
            this object to any other value.
```

If a management station sets this object to the
value deleteTCB(12), then this has the effect of
deleting the TCB (as defined in RFC 793) of the
corresponding connection on the managed node,
resulting in immediate termination of the
connection.

As an implementation-specific option, a RST
segment may be sent from the managed node to the
other TCP endpoint (note however that RST segments
are not sent reliably)."
::= { tcpConnEntry 1 }

tcpConnLocalAddress OBJECT-TYPE
SYNTAX IpAddress
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The local IP address for this TCP connection. In

the case of a connection in the listen state which
is willing to accept connections for any IP
interface associated with the node, the value
0.0.0.0 is used."
::= { tcpConnEntry 2 }

tcpConnLocalPort OBJECT-TYPE
SYNTAX INTEGER (0..65535)
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The local port number for this TCP connection."
::= { tcpConnEntry 3 }

tcpConnRemAddress OBJECT-TYPE
SYNTAX IpAddress
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The remote IP address for this TCP connection."
::= { tcpConnEntry 4 }

tcpConnRemPort OBJECT-TYPE
SYNTAX INTEGER (0..65535)
ACCESS read-only
STATUS mandatory
DESCRIPTION

```
        "The remote port number for this TCP connection."
  ::= { tcpConnEntry 5 }


-- additional TCP objects

tcpInErrs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number
 of segments received in error
        (e.g., bad TCP checksums)."
  ::= { tcp 14 }

tcpOutRsts OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of TCP segments sent containing the
        RST flag."
  ::= { tcp 15 }


-- the UDP group

-- Implementation of the UDP group is mandatory for all
-- systems which implement the UDP.

udpInDatagrams OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of UDP datagrams delivered to
        UDP users."
  ::= { udp 1 }

udpNoPorts OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of received UDP datagrams for
        which there was no application at the destination
        port."
```

```
  ::= { udp 2 }

udpInErrors OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION

 "The number of received UDP datagrams that could
        not be delivered for reasons other than the lack
        of an application at the destination port."
  ::= { udp 3 }

udpOutDatagrams OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of UDP datagrams sent from this
        entity."
  ::= { udp 4 }


-- the UDP Listener table

-- The UDP listener table contains information about this
-- entity's UDP end-points on which a local application is
-- currently accepting datagrams.

udpTable OBJECT-TYPE
  SYNTAX  SEQUENCE OF UdpEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "A table containing UDP listener information."
  ::= { udp 5 }

udpEntry OBJECT-TYPE
  SYNTAX  UdpEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "Information about a particular current UDP
        listener."
  INDEX   { udpLocalAddress, udpLocalPort
 }
  ::= { udpTable 1 }
```

```
UdpEntry ::=
  SEQUENCE {
     udpLocalAddress
        IpAddress,
     udpLocalPort
        INTEGER (0..65535)
  }

udpLocalAddress OBJECT-TYPE
  SYNTAX  IpAddress
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The local IP address for this UDP listener.  In
        the case of a UDP listener which is willing to
        accept datagrams for any IP interface associated
        with the node, the value 0.0.0.0 is used."
  ::= { udpEntry 1 }

udpLocalPort OBJECT-TYPE
  SYNTAX  INTEGER (0..65535)
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The local port number for this UDP listener."
  ::= { udpEntry 2 }


-- the EGP group

-- Implementation of the EGP group is mandatory for all
-- systems which implement the EGP.

egpInMsgs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of EGP messages received without
         error."
  ::= { egp 1 }

egpInErrors OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of EGP messages received that proved
```

```
        to be in error."
  ::= { egp 2 }

egpOutMsgs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of locally generated EGP
        messages."
  ::= { egp 3 }

egpOutErrors OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of locally generated EGP messages not
        sent due to resource limitations within an EGP
        entity."
  ::= { egp 4 }


-- the EGP Neighbor table

-- The EGP neighbor table contains information about this
-- entity's EGP neighbors.

egpNeighTable OBJECT-TYPE
  SYNTAX  SEQUENCE OF EgpNeighEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "The EGP neighbor table."
   ::= { egp 5 }

egpNeighEntry OBJECT-TYPE
  SYNTAX  EgpNeighEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "Information about this entity's relationship with
        a particular EGP neighbor."
  INDEX   { egpNeighAddr }
  ::= { egpNeighTable 1 }

EgpNeighEntry ::=
  SEQUENCE {
```

```
    egpNeighState
        INTEGER,
    egpNeighAddr
        IpAddress,
    egpNeighAs
        INTEGER,
    egpNeighInMsgs
        Counter,
    egpNeighInErrs
        Counter,
    egpNeighOutMsgs
        Counter,
    egpNeighOutErrs
        Counter,
    egpNeighInErrMsgs
        Counter,
    egpNeighOutErrMsgs
        Counter,
    egpNeighStateUps
        Counter,
    egpNeighStateDowns
        Counter,
    egpNeighIntervalHello
        INTEGER,
    egpNeighIntervalPoll
        INTEGER,
    egpNeighMode
        INTEGER,
    egpNeighEventTrigger

      INTEGER
  }

egpNeighState OBJECT-TYPE
  SYNTAX  INTEGER {
            idle(1),
            acquisition(2),
            down(3),
            up(4),
            cease(5)
          }
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The EGP state of the local system with respect to
        this entry's EGP neighbor.  Each EGP state is
        represented by a value that is one greater than
        the numerical value associated with said state in
```

RFC 904."
::= { egpNeighEntry 1 }

egpNeighAddr OBJECT-TYPE
SYNTAX IpAddress
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The IP address of this entry's EGP neighbor."
::= { egpNeighEntry 2 }

egpNeighAs OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The autonomous system of this EGP peer. Zero
should be specified if the autonomous system
number
of the neighbor is not yet known."
::= { egpNeighEntry 3 }

egpNeighInMsgs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of EGP messages received without error
from this EGP peer."
::= { egpNeighEntry 4 }

egpNeighInErrs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of EGP messages received from this EGP
peer that proved to be in error (e.g., bad EGP
checksum)."
::= { egpNeighEntry 5 }

egpNeighOutMsgs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of locally generated EGP messages to
this EGP peer."

::= { egpNeighEntry 6 }

egpNeighOutErrs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of locally generated EGP messages not
sent to this
EGP peer due to resource limitations
within an EGP entity."
::= { egpNeighEntry 7 }

egpNeighInErrMsgs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of EGP-defined error messages received
from this EGP peer."
::= { egpNeighEntry 8 }

egpNeighOutErrMsgs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of EGP-defined error messages sent to
this EGP peer."
::= { egpNeighEntry 9 }

egpNeighStateUps OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of EGP state transitions to the UP
state with this EGP peer."
::= { egpNeighEntry 10 }

egpNeighStateDowns OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of EGP state transitions from the UP
state to any

other state with this EGP peer."
::= { egpNeighEntry 11 }

egpNeighIntervalHello OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The interval between EGP Hello command retransmissions (in hundredths of a second). This represents the t1 timer as defined in RFC 904."
::= { egpNeighEntry 12 }

egpNeighIntervalPoll OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The interval between EGP poll command retransmissions (in hundredths of a second). This represents the t3 timer as defined in RFC 904."
::= { egpNeighEntry 13 }

egpNeighMode OBJECT-TYPE
SYNTAX INTEGER { active(1), passive(2) }
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The polling mode of this EGP entity, either passive or active."
::= { egpNeighEntry 14 }

egpNeighEventTrigger OBJECT-TYPE
SYNTAX INTEGER
{ start(1), stop(2) }
ACCESS read-write
STATUS mandatory
DESCRIPTION
"A control variable used to trigger operator-initiated Start and Stop events. When read, this variable always returns the most recent value that egpNeighEventTrigger was set to. If it has not been set since the last initialization of the network management subsystem on the node, it returns a value of `stop'.

When set, this variable causes a Start or Stop event on the specified neighbor, as specified on

```
        pages 8-10 of RFC 904.  Briefly, a Start event
        causes an Idle peer to begin neighbor acquisition
        and a non-Idle peer to reinitiate neighbor
        acquisition.  A stop event causes a non-Idle peer
        to return to the Idle state until a Start event
        occurs, either via egpNeighEventTrigger or
        otherwise."
  ::= { egpNeighEntry
 15 }


-- additional EGP objects

egpAs OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The autonomous system number of this EGP entity."
  ::= { egp 6 }

-- the Transmission group

-- Based on the transmission media underlying each interface
-- on a system, the corresponding portion of the Transmission
-- group is mandatory for that system.

-- When Internet-standard definitions for managing
-- transmission media are defined, the transmission group is
-- used to provide a prefix for the names of those objects.

-- Typically, such definitions reside in the experimental
-- portion of the MIB until they are "proven", then as a
-- part of the Internet standardization process, the
-- definitions are accordingly elevated and a new object
-- identifier, under the transmission group is defined. By
-- convention, the name assigned is:
--
--     type OBJECT IDENTIFIER    ::= { transmission number }
--
-- where "type" is the symbolic
 value used for the media in
-- the ifType column of the ifTable object, and "number" is
-- the actual integer value corresponding to the symbol.


-- the SNMP group
```

```
-- Implementation of the SNMP group is mandatory for all
-- systems which support an SNMP protocol entity.  Some of
-- the objects defined below will be zero-valued in those
-- SNMP implementations that are optimized to support only
-- those functions specific to either a management agent or
-- a management station.  In particular, it should be
-- observed that the objects below refer to an SNMP entity,
-- and there may be several SNMP entities residing on a
-- managed node (e.g., if the node is hosting acting as
-- a management station).

snmpInPkts OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of Messages delivered to the
        SNMP entity from the transport service."
  ::= { snmp 1 }

snmpOutPkts OBJECT-TYPE
  SYNTAX  Counter
  ACCESS
 read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Messages which were
        passed from the SNMP protocol entity to the
        transport service."
  ::= { snmp 2 }

snmpInBadVersions OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Messages which were
        delivered to the SNMP protocol entity and were for
        an unsupported SNMP version."
  ::= { snmp 3 }

snmpInBadCommunityNames OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Messages delivered to
        the SNMP protocol entity which used a SNMP
```

community name not known to said entity."
::= { snmp 4 }

snmpInBadCommunityUses OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The total number of SNMP Messages delivered to

the SNMP protocol entity which represented an SNMP
operation which was not allowed by the SNMP
community named in the Message."
::= { snmp 5 }

snmpInASNParseErrs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The total number of ASN.1 or BER errors
encountered by the SNMP protocol entity when
decoding received SNMP Messages."
::= { snmp 6 }

-- { snmp 7 } is not used

snmpInTooBigs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The total number of SNMP PDUs which were
delivered to the SNMP protocol entity and for
which the value of the error-status field is
`tooBig'."
::= { snmp 8 }

snmpInNoSuchNames OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The total number of SNMP PDUs which were
delivered to the
SNMP protocol entity and for
which the value of the error-status field is
`noSuchName'."

::= { snmp 9 }

snmpInBadValues OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The total number of SNMP PDUs which were
delivered to the SNMP protocol entity and for
which the value of the error-status field is
`badValue'."
::= { snmp 10 }

snmpInReadOnlys OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The total number valid SNMP PDUs which were
delivered to the SNMP protocol entity and for
which the value of the error-status field is
`readOnly'. It should be noted that it is a
protocol error to generate an SNMP PDU which
contains the value `readOnly' in the error-status
field, as such this object is provided as a means
of detecting
incorrect implementations of the
SNMP."
::= { snmp 11 }

snmpInGenErrs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The total number of SNMP PDUs which were
delivered to the SNMP protocol entity and for
which the value of the error-status field is
`genErr'."
::= { snmp 12 }

snmpInTotalReqVars OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The total number of MIB objects which have been
retrieved successfully by the SNMP protocol entity

```
        as the result of receiving valid SNMP Get-Request
        and Get-Next PDUs."
  ::= { snmp 13 }

snmpInTotalSetVars OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of MIB objects which have been
        altered successfully by the SNMP protocol entity
        as the result
 of receiving valid SNMP Set-Request
        PDUs."
  ::= { snmp 14 }

snmpInGetRequests OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Get-Request PDUs which
        have been accepted and processed by the SNMP
        protocol entity."
  ::= { snmp 15 }

snmpInGetNexts OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Get-Next PDUs which have
        been accepted and processed by the SNMP protocol
        entity."
  ::= { snmp 16 }

snmpInSetRequests OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Set-Request PDUs which
        have been accepted and processed by the SNMP
        protocol entity."
  ::= { snmp 17 }

snmpInGetResponses OBJECT-TYPE
  SYNTAX  Counter
```

```
  ACCESS  read-only
  STATUS  mandatory
   DESCRIPTION
        "The total number of SNMP Get-Response PDUs which
        have been accepted and processed by the SNMP
        protocol entity."
  ::= { snmp 18 }

snmpInTraps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Trap PDUs which have
        been accepted and processed by the SNMP protocol
        entity."
  ::= { snmp 19 }

snmpOutTooBigs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP PDUs which were
        generated by the SNMP protocol entity and for
        which the value of the error-status field is
        `tooBig.'"
  ::= { snmp 20 }

snmpOutNoSuchNames OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP PDUs which were
        generated by the SNMP protocol entity and for
         which the value of the error-status is
        `noSuchName'."
  ::= { snmp 21 }

snmpOutBadValues OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP PDUs which were
        generated by the SNMP protocol entity and for
        which the value of the error-status field is
```

```
        `badValue'."
  ::= { snmp 22 }

-- { snmp 23 } is not used

snmpOutGenErrs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP PDUs which were
        generated by the SNMP protocol entity and for
        which the value of the error-status field is
        `genErr'."
  ::= { snmp 24 }

snmpOutGetRequests OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Get-Request PDUs which
        have been generated by the SNMP protocol entity."
   ::= { snmp 25 }

snmpOutGetNexts OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Get-Next PDUs which have
        been generated by the SNMP protocol entity."
  ::= { snmp 26 }

snmpOutSetRequests OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Set-Request PDUs which
        have been generated by the SNMP protocol entity."
  ::= { snmp 27 }

snmpOutGetResponses OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
```

```
        "The total number of SNMP Get-Response PDUs which
        have been generated by the SNMP protocol entity."
  ::= { snmp 28 }

snmpOutTraps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Trap PDUs which have
        been generated by the SNMP protocol entity."
   ::= { snmp 29 }

snmpEnableAuthenTraps OBJECT-TYPE
  SYNTAX  INTEGER { enabled(1), disabled(2) }
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "Indicates whether the SNMP agent process is
        permitted to generate authentication-failure
        traps.  The value of this object overrides any
        configuration information; as such, it provides a
        means whereby all authentication-failure traps may
        be disabled.

        Note that it is strongly recommended that this
        object be stored in non-volatile memory so that it
        remains constant between re-initializations of the
        network management system."
  ::= { snmp 30 }

END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/RFC1213-MIB
No license file was found, but licenses were detected in source scan.

```
IANAifType-MIB DEFINITIONS ::= BEGIN

 IMPORTS
    MODULE-IDENTITY, mib-2      FROM SNMPv2-SMI
    TEXTUAL-CONVENTION          FROM SNMPv2-TC;

 ianaifType MODULE-IDENTITY
    LAST-UPDATED "200709130000Z"  -- September 13, 2007
    ORGANIZATION "IANA"
    CONTACT-INFO "        Internet Assigned Numbers Authority
```

Postal: ICANN
4676 Admiralty Way, Suite 330
Marina del Rey, CA 90292

Tel: +1 310 823 9358
E-Mail: iana&iana.org"

DESCRIPTION "This MIB module defines the IANAifType Textual
Convention, and thus the enumerated values of
the ifType object defined in MIB-II's ifTable."

REVISION "200709130000Z" -- September 13, 2007
DESCRIPTION "Registration of new IANAifTypes 243 and 244."

REVISION "200705290000Z"
-- May 29, 2007
DESCRIPTION "Changed the description for IANAifType 228."

REVISION "200703080000Z" -- March 08, 2007
DESCRIPTION "Registration of new IANAifType 242."

REVISION "200701230000Z" -- January 23, 2007
DESCRIPTION "Registration of new IANAifTypes 239, 240, and 241."

REVISION "200610170000Z" -- October 17, 2006
DESCRIPTION "Deprecated/Obsoleted IANAifType 230. Registration of
IANAifType 238."

REVISION "200609250000Z" -- September 25, 2006
DESCRIPTION "Changed the description for IANA ifType
184 and added new IANA ifType 237."

REVISION "200608170000Z" -- August 17, 2006
DESCRIPTION "Changed the descriptions for IANAifTypes
20 and 21."

REVISION "200608110000Z" -- August 11, 2006
DESCRIPTION "Changed the descriptions for IANAifTypes
7, 11, 62,
69, and 117."

REVISION "200607250000Z" -- July 25, 2006
DESCRIPTION "Registration of new IANA ifType 236."

REVISION "200606140000Z" -- June 14, 2006
DESCRIPTION "Registration of new IANA ifType 235."

REVISION "200603310000Z" -- March 31, 2006

```
    DESCRIPTION  "Registration of new IANA ifType 234."

    REVISION     "200603300000Z"  -- March 30, 2006
    DESCRIPTION  "Registration of new IANA ifType 233."

    REVISION     "200512220000Z"  -- December 22, 2005
    DESCRIPTION  "Registration of new IANA ifTypes 231 and 232."

    REVISION     "200510100000Z"  -- October 10, 2005
    DESCRIPTION  "Registration of new IANA ifType 230."

    REVISION     "200509090000Z"  -- September 09, 2005
    DESCRIPTION  "Registration of new IANA ifType 229."

    REVISION     "200505270000Z"  -- May 27, 2005
    DESCRIPTION  "Registration of new IANA ifType 228."

    REVISION     "200503030000Z"
  -- March 3, 2005
    DESCRIPTION  "Added the IANAtunnelType TC and deprecated
            IANAifType sixToFour (215) per RFC4087."

    REVISION     "200411220000Z"  -- November 22, 2004
    DESCRIPTION  "Registration of new IANA ifType 227 per RFC4631."

    REVISION     "200406170000Z"  -- June 17, 2004
    DESCRIPTION  "Registration of new IANA ifType 226."

    REVISION     "200405120000Z"  -- May 12, 2004
    DESCRIPTION  "Added description for IANAifType 6, and
            changed the descriptions for IANAifTypes
             180, 181, and 182."

    REVISION     "200405070000Z"  -- May 7, 2004
    DESCRIPTION  "Registration of new IANAifType 225."

    REVISION     "200308250000Z"  -- Aug 25, 2003
    DESCRIPTION  "Deprecated IANAifTypes 7 and 11. Obsoleted
            IANAifTypes 62, 69, and 117.  ethernetCsmacd (6)
            should be used instead of these values"

    REVISION     "200308180000Z"
  -- Aug 18, 2003
    DESCRIPTION  "Registration of new IANAifType
            224."

    REVISION     "200308070000Z"  -- Aug 7, 2003
    DESCRIPTION  "Registration of new IANAifTypes
```

222 and 223."

REVISION "200303180000Z" -- Mar 18, 2003
DESCRIPTION "Registration of new IANAifType
221."

REVISION "200301130000Z" -- Jan 13, 2003
DESCRIPTION "Registration of new IANAifType
220."

REVISION "200210170000Z" -- Oct 17, 2002
DESCRIPTION "Registration of new IANAifType
219."

REVISION "200207160000Z" -- Jul 16, 2002
DESCRIPTION "Registration of new IANAifTypes
217 and 218."

REVISION "200207100000Z" -- Jul 10, 2002
DESCRIPTION "Registration of new IANAifTypes
215 and 216."

REVISION "200206190000Z" -- Jun 19, 2002
DESCRIPTION "Registration
of new IANAifType
214."

REVISION "200201040000Z" -- Jan 4, 2002
DESCRIPTION "Registration of new IANAifTypes
211, 212 and 213."

REVISION "200112200000Z" -- Dec 20, 2001
DESCRIPTION "Registration of new IANAifTypes
209 and 210."

REVISION "200111150000Z" -- Nov 15, 2001
DESCRIPTION "Registration of new IANAifTypes
207 and 208."

REVISION "200111060000Z" -- Nov 6, 2001
DESCRIPTION "Registration of new IANAifType
206."

REVISION "200111020000Z" -- Nov 2, 2001
DESCRIPTION "Registration of new IANAifType
205."

REVISION "200110160000Z" -- Oct 16, 2001
DESCRIPTION "Registration of new IANAifTypes
199, 200, 201, 202, 203, and 204."

REVISION "200109190000Z" -- Sept 19, 2001
DESCRIPTION "Registration
of new IANAifType
198."

REVISION "200105110000Z" -- May 11, 2001
DESCRIPTION "Registration of new IANAifType
197."

REVISION "200101120000Z" -- Jan 12, 2001
DESCRIPTION "Registration of new IANAifTypes
195 and 196."

REVISION "200012190000Z" -- Dec 19, 2000
DESCRIPTION "Registration of new IANAifTypes
193 and 194."

REVISION "200012070000Z" -- Dec 07, 2000
DESCRIPTION "Registration of new IANAifTypes
191 and 192."

REVISION "200012040000Z" -- Dec 04, 2000
DESCRIPTION "Registration of new IANAifType
190."

REVISION "200010170000Z" -- Oct 17, 2000
DESCRIPTION "Registration of new IANAifTypes
188 and 189."

REVISION "200010020000Z" -- Oct 02, 2000
DESCRIPTION "Registration of new IANAifType
187."

REVISION "200009010000Z" -- Sept 01, 2000
DESCRIPTION "Registration of new IANAifTypes
184, 185, and 186."

REVISION "200008240000Z" -- Aug 24, 2000
DESCRIPTION "Registration of new IANAifType 183."

```
    REVISION     "200008230000Z"  -- Aug 23, 2000
    DESCRIPTION  "Registration of new IANAifTypes
                 174-182."

    REVISION     "200008220000Z"  -- Aug 22, 2000
    DESCRIPTION  "Registration of new IANAifTypes 170,
                 171, 172 and 173."

    REVISION     "200004250000Z"  -- Apr 25, 2000
    DESCRIPTION  "Registration of new IANAifTypes 168 and 169."

    REVISION     "200003060000Z"  -- Mar 6, 2000
    DESCRIPTION  "Fixed a missing semi-colon in the IMPORT.
                 Also cleaned up the REVISION log a bit.
                 It is not complete, but from now on it will
                 be maintained and kept up to date with
each
                 change to this MIB module."

    REVISION     "199910081430Z"  -- Oct 08, 1999
    DESCRIPTION  "Include new name assignments up to cnr(85).
                 This is the first version available via the WWW
                 at: ftp://ftp.isi.edu/mib/ianaiftype.mib"

    REVISION     "199401310000Z"  -- Jan 31, 1994
    DESCRIPTION  "Initial version of this MIB as published in
                 RFC 1573."

    ::= { mib-2 30 }


 IANAifType ::= TEXTUAL-CONVENTION
    STATUS       current
    DESCRIPTION
         "This data type is used as the syntax of the ifType
         object in the (updated) definition of MIB-II's
         ifTable.

         The definition of this textual convention with the
         addition of newly assigned values is published
         periodically by the IANA, in either the Assigned
         Numbers RFC, or some derivative of it specific to
         Internet
Network Management number assignments.  (The
         latest arrangements can be obtained by contacting the
         IANA.)

         Requests for new values should be made to IANA via
```

```
        email (iana&iana.org).

        The relationship between the assignment of ifType
        values and of OIDs to particular media-specific MIBs
        is solely the purview of IANA and is subject to change
        without notice.  Quite often, a media-specific MIB's
        OID-subtree assignment within MIB-II's 'transmission'
        subtree will be the same as its ifType value.
        However, in some circumstances this will not be the
        case, and implementors must not pre-assume any
        specific relationship between ifType values and
        transmission subtree OIDs."
    SYNTAX  INTEGER {
            other(1),          -- none of the following
            regular1822(2),
             hdh1822(3),
            ddnX25(4),
            rfc877x25(5),
            ethernetCsmacd(6), -- for all ethernet-like interfaces,
                        -- regardless of speed, as per RFC3635
            iso88023Csmacd(7), -- Deprecated via RFC3635
                        -- ethernetCsmacd (6) should be used instead
            iso88024TokenBus(8),
            iso88025TokenRing(9),
            iso88026Man(10),
            starLan(11), -- Deprecated via RFC3635
                    -- ethernetCsmacd (6) should be used instead
            proteon10Mbit(12),
            proteon80Mbit(13),
            hyperchannel(14),
            fddi(15),
            lapb(16),
            sdlc(17),
            ds1(18),            -- DS1-MIB
            e1(19),             -- Obsolete see DS1-MIB
            basicISDN(20),
      -- no longer used
                                -- see also RFC2127
            primaryISDN(21),            -- no longer used
                                -- see also RFC2127
            propPointToPointSerial(22), -- proprietary serial
            ppp(23),
            softwareLoopback(24),
            eon(25),            -- CLNP over IP
            ethernet3Mbit(26),
            nsip(27),           -- XNS over IP
            slip(28),           -- generic SLIP
            ultra(29),          -- ULTRA technologies
```

```
            ds3(30),           -- DS3-MIB
            sip(31),           -- SMDS, coffee
            frameRelay(32),    -- DTE only.
            rs232(33),
            para(34),          -- parallel-port
            arcnet(35),        -- arcnet
            arcnetPlus(36),    -- arcnet plus
            atm(37),
        -- ATM cells
            miox25(38),
            sonet(39),         -- SONET or SDH
            x25ple(40),
            iso88022llc(41),
            localTalk(42),
            smdsDxi(43),
            frameRelayService(44),  -- FRNETSERV-MIB
            v35(45),
            hssi(46),
            hippi(47),
            modem(48),         -- Generic modem
            aal5(49),          -- AAL5 over ATM
            sonetPath(50),
            sonetVT(51),
            smdsIcip(52),      -- SMDS InterCarrier Interface
            propVirtual(53),   -- proprietary virtual/internal
            propMultiplexor(54),-- proprietary multiplexing
            ieee80212(55),     -- 100BaseVG
            fibreChannel(56),  -- Fibre Channel
            hippiInterface(57), -- HIPPI interfaces
            frameRelayInterconnect(58), --
Obsolete use either
                        -- frameRelay(32) or
                        -- frameRelayService(44).
            aflane8023(59),    -- ATM Emulated LAN for 802.3
            aflane8025(60),    -- ATM Emulated LAN for 802.5
            cctEmul(61),       -- ATM Emulated circuit
            fastEther(62),     -- Obsoleted via RFC3635
                        -- ethernetCsmacd (6) should be used instead
            isdn(63),          -- ISDN and X.25
            v11(64),           -- CCITT V.11/X.21
            v36(65),           -- CCITT V.36
            g703at64k(66),     -- CCITT G703 at 64Kbps
            g703at2mb(67),     -- Obsolete see DS1-MIB
            qllc(68),          -- SNA QLLC
            fastEtherFX(69),   -- Obsoleted via RFC3635

           -- ethernetCsmacd (6) should be used instead
            channel(70),       -- channel
```

```
            ieee80211(71),      -- radio spread spectrum
            ibm370parChan(72),  -- IBM System 360/370 OEMI Channel
            escon(73),          -- IBM Enterprise Systems Connection
            dlsw(74),           -- Data Link Switching
            isdns(75),          -- ISDN S/T interface
            isdnu(76),          -- ISDN U interface
            lapd(77),           -- Link Access Protocol D
            ipSwitch(78),       -- IP Switching Objects
            rsrb(79),           -- Remote Source Route Bridging
            atmLogical(80),     -- ATM Logical Port
            ds0(81),            -- Digital Signal Level 0
            ds0Bundle(82),      -- group of ds0s on the same ds1
            bsc(83),            -- Bisynchronous Protocol

           async(84),          -- Asynchronous Protocol
            cnr(85),            -- Combat Net Radio
            iso88025Dtr(86),    -- ISO 802.5r DTR
            eplrs(87),          -- Ext Pos Loc Report Sys
            arap(88),           -- Appletalk Remote Access Protocol
            propCnls(89),       -- Proprietary Connectionless Protocol
            hostPad(90),        -- CCITT-ITU X.29 PAD Protocol
            termPad(91),        -- CCITT-ITU X.3 PAD Facility
            frameRelayMPI(92),  -- Multiproto Interconnect over FR
            x213(93),           -- CCITT-ITU X213
            adsl(94),           -- Asymmetric Digital Subscriber Loop
            radsl(95),          -- Rate-Adapt. Digital Subscriber Loop
            sdsl(96),           -- Symmetric Digital Subscriber Loop
            vdsl(97),           -- Very H-Speed Digital Subscrib. Loop
            iso88025CRFPInt(98),
-- ISO 802.5 CRFP
            myrinet(99),        -- Myricom Myrinet
            voiceEM(100),       -- voice recEive and transMit
            voiceFXO(101),      -- voice Foreign Exchange Office
            voiceFXS(102),      -- voice Foreign Exchange Station
            voiceEncap(103),    -- voice encapsulation
            voiceOverIp(104),   -- voice over IP encapsulation
            atmDxi(105),        -- ATM DXI
            atmFuni(106),       -- ATM FUNI
            atmIma (107),       -- ATM IMA
            pppMultilinkBundle(108), -- PPP Multilink Bundle
            ipOverCdlc (109),   -- IBM ipOverCdlc
            ipOverClaw (110),   -- IBM Common Link Access to Workstn
            stackToStack (111), -- IBM stackToStack
            virtualIpAddress (112), -- IBM VIPA
            mpc (113),          -- IBM multi-protocol channel support

ipOverAtm (114),    -- IBM ipOverAtm
            iso88025Fiber (115), -- ISO 802.5j Fiber Token Ring
```

tdlc (116), -- IBM twinaxial data link control
gigabitEthernet (117), -- Obsoleted via RFC3635
-- ethernetCsmacd (6) should be used instead
hdlc (118), -- HDLC
lapf (119), -- LAP F
v37 (120), -- V.37
x25mlp (121), -- Multi-Link Protocol
x25huntGroup (122), -- X25 Hunt Group
trasnpHdlc (123), -- Transp HDLC
interleave (124), -- Interleave channel
fast (125), -- Fast channel
ip (126), -- IP (for APPN HPR in IP networks)
docsCableMaclayer (127), -- CATV Mac Layer
docsCableDownstream (128), -- CATV Downstream interface
docsCableUpstream
(129), -- CATV Upstream interface
a12MppSwitch (130), -- Avalon Parallel Processor
tunnel (131), -- Encapsulation interface
coffee (132), -- coffee pot
ces (133), -- Circuit Emulation Service
atmSubInterface (134), -- ATM Sub Interface
l2vlan (135), -- Layer 2 Virtual LAN using 802.1Q
l3ipvlan (136), -- Layer 3 Virtual LAN using IP
l3ipxvlan (137), -- Layer 3 Virtual LAN using IPX
digitalPowerline (138), -- IP over Power Lines
mediaMailOverIp (139), -- Multimedia Mail over IP
dtm (140), -- Dynamic syncronous Transfer Mode
dcn (141), -- Data Communications Network
ipForward (142), -- IP Forwarding Interface
msdsl (143), -- Multi-rate Symmetric DSL

ieee1394 (144), -- IEEE1394 High Performance Serial Bus
if-gsn (145), -- HIPPI-6400
dvbRccMacLayer (146), -- DVB-RCC MAC Layer
dvbRccDownstream (147), -- DVB-RCC Downstream Channel
dvbRccUpstream (148), -- DVB-RCC Upstream Channel
atmVirtual (149), -- ATM Virtual Interface
mplsTunnel (150), -- MPLS Tunnel Virtual Interface
srp (151), -- Spatial Reuse Protocol
voiceOverAtm (152), -- Voice Over ATM
voiceOverFrameRelay (153), -- Voice Over Frame Relay
idsl (154), -- Digital Subscriber Loop over ISDN
compositeLink (155), -- Avici Composite Link Interface
ss7SigLink (156), -- SS7 Signaling Link
propWirelessP2P (157), -- Prop. P2P wireless interface
frForward (158), -- Frame Forward Interface
rfc1483 (159), -- Multiprotocol over ATM AAL5
usb (160), -- USB Interface

ieee8023adLag (161), -- IEEE 802.3ad Link Aggregate
bgppolicyaccounting (162), -- BGP Policy Accounting
frf16MfrBundle (163), -- FRF .16 Multilink Frame Relay
h323Gatekeeper (164), -- H323 Gatekeeper
h323Proxy (165), -- H323 Voice and Video Proxy
mpls (166), -- MPLS
mfSigLink (167), -- Multi-frequency signaling link
hdsl2 (168), -- High Bit-Rate DSL - 2nd generation
shdsl (169), -- Multirate HDSL2
ds1FDL (170), -- Facility Data Link 4Kbps on a DS1
pos (171), -- Packet over SONET/SDH Interface
dvbAsiIn (172), -- DVB-ASI Input
dvbAsiOut (173), -- DVB-ASI Output
plc (174), -- Power Line Communtications
nfas (175), -- Non Facility Associated Signaling
tr008 (176), -- TR008
gr303RDT (177), -- Remote Digital Terminal
gr303IDT (178), -- Integrated Digital Terminal
isup (179), -- ISUP
propDocsWirelessMaclayer (180), -- Cisco proprietary Maclayer
propDocsWirelessDownstream (181), -- Cisco proprietary Downstream
propDocsWirelessUpstream (182), -- Cisco proprietary Upstream
hiperlan2 (183), -- HIPERLAN Type 2 Radio Interface
propBWAp2Mp (184), -- PropBroadbandWirelessAccesspt2multipt
-- use of this iftype for IEEE 802.16 WMAN
-- interfaces as per IEEE Std 802.16f is
-- deprecated and ifType 237 should be used instead.
sonetOverheadChannel (185), -- SONET Overhead Channel
digitalWrapperOverheadChannel
(186), -- Digital Wrapper
aal2 (187), -- ATM adaptation layer 2
radioMAC (188), -- MAC layer over radio links
atmRadio (189), -- ATM over radio links
imt (190), -- Inter Machine Trunks
mvl (191), -- Multiple Virtual Lines DSL
reachDSL (192), -- Long Reach DSL
frDlciEndPt (193), -- Frame Relay DLCI End Point
atmVciEndPt (194), -- ATM VCI End Point
opticalChannel (195), -- Optical Channel
opticalTransport (196), -- Optical Transport
propAtm (197), -- Proprietary ATM
voiceOverCable (198), -- Voice Over Cable Interface
infiniband (199), -- Infiniband
teLink (200), -- TE Link
q2931 (201), -- Q.2931
virtualTg (202), -- Virtual Trunk Group

sipTg (203), -- SIP Trunk Group
sipSig (204), -- SIP Signaling
docsCableUpstreamChannel (205), -- CATV Upstream Channel
econet (206), -- Acorn Econet
pon155 (207), -- FSAN 155Mb Symetrical PON interface
pon622 (208), -- FSAN622Mb Symetrical PON interface
bridge (209), -- Transparent bridge interface
linegroup (210), -- Interface common to multiple lines
voiceEMFGD (211), -- voice E&M Feature Group D
voiceFGDEANA (212), -- voice FGD Exchange Access North American
voiceDID (213), -- voice Direct Inward Dialing
mpegTransport (214), -- MPEG transport interface
sixToFour (215), -- 6to4 interface (DEPRECATED)
gtp (216), -- GTP (GPRS Tunneling Protocol)
pdnEtherLoop1 (217), -- Paradyne EtherLoop 1
pdnEtherLoop2
(218), -- Paradyne EtherLoop 2
opticalChannelGroup (219), -- Optical Channel Group
homepna (220), -- HomePNA ITU-T G.989
gfp (221), -- Generic Framing Procedure (GFP)
ciscoISLvlan (222), -- Layer 2 Virtual LAN using Cisco ISL
actelisMetaLOOP (223), -- Acteleis proprietary MetaLOOP High Speed Link
fcipLink (224), -- FCIP Link
rpr (225), -- Resilient Packet Ring Interface Type
qam (226), -- RF Qam Interface
lmp (227), -- Link Management Protocol
cblVectaStar (228), -- Cambridge Broadband Networks Limited VectaStar
docsCableMCmtsDownstream (229), -- CATV Modular CMTS Downstream Interface
adsl2 (230), -- Asymmetric Digital Subscriber Loop Version 2
-- (DEPRECATED/OBSOLETED - please use adsl2plus 238 instead)

macSecControlledIF (231), -- MACSecControlled
macSecUncontrolledIF (232), -- MACSecUncontrolled
aviciOpticalEther (233), -- Avici Optical Ethernet Aggregate
atmbond (234), -- atmbond
voiceFGDOS (235), -- voice FGD Operator Services
mocaVersion1 (236), -- MultiMedia over Coax Alliance (MoCA) Interface
-- as documented in information provided privately to IANA
ieee80216WMAN (237), -- IEEE 802.16 WMAN interface
adsl2plus (238), -- Asymmetric Digital Subscriber Loop Version 2,
-- Version 2 Plus and all variants
dvbRcsMacLayer (239), -- DVB-RCS MAC Layer
dvbTdm (240), -- DVB Satellite TDM
dvbRcsTdma (241), -- DVB-RCS TDMA
x86Laps (242), -- LAPS based on ITU-T X.86/Y.1323
wwanPP (243), -- 3GPP
WWAN
wwanPP2 (244) -- 3GPP2 WWAN

```
        }

IANAtunnelType ::= TEXTUAL-CONVENTION
  STATUS     current
  DESCRIPTION
        "The encapsulation method used by a tunnel. The value
        direct indicates that a packet is encapsulated
        directly within a normal IP header, with no
        intermediate header, and unicast to the remote tunnel
        endpoint (e.g., an RFC 2003 IP-in-IP tunnel, or an RFC
        1933 IPv6-in-IPv4 tunnel). The value minimal indicates
        that a Minimal Forwarding Header (RFC 2004) is
        inserted between the outer header and the payload
        packet. The value UDP indicates that the payload
        packet is encapsulated within a normal UDP packet
        (e.g., RFC 1234).

        The values sixToFour, sixOverFour, and isatap
        indicates that an IPv6 packet is encapsulated directly
        within an IPv4 header, with no intermediate header,

        and unicast to the destination determined by the 6to4,
        6over4, or ISATAP protocol.

        The remaining protocol-specific values indicate that a
        header of the protocol of that name is inserted
        between the outer header and the payload header.

        The assignment policy for IANAtunnelType values is
        identical to the policy for assigning IANAifType
        values."
  SYNTAX     INTEGER {
              other(1),       -- none of the following
              direct(2),      -- no intermediate header
              gre(3),         -- GRE encapsulation
              minimal(4),     -- Minimal encapsulation
              l2tp(5),        -- L2TP encapsulation
              pptp(6),        -- PPTP encapsulation
              l2f(7),         -- L2F encapsulation
              udp(8),         -- UDP encapsulation
              atmp(9),        -- ATMP encapsulation

             msdp(10),        -- MSDP encapsulation
              sixToFour(11),  -- 6to4 encapsulation
              sixOverFour(12), -- 6over4 encapsulation
              isatap(13),     -- ISATAP encapsulation
              teredo(14)      -- Teredo encapsulation
             }
```

```
 END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/iana/IANAifType-MIB
No license file was found, but licenses were detected in source scan.

```
APM-MIB DEFINITIONS ::= BEGIN
IMPORTS
  MODULE-IDENTITY, OBJECT-TYPE,
  NOTIFICATION-TYPE,
  Counter32, Unsigned32                  FROM SNMPv2-SMI
  TEXTUAL-CONVENTION, RowStatus, TimeStamp,
  TimeInterval, TruthValue, DateAndTime,
  StorageType                            FROM SNMPv2-TC
  MODULE-COMPLIANCE, OBJECT-GROUP,
  NOTIFICATION-GROUP                     FROM SNMPv2-CONF
  SnmpAdminString                        FROM SNMP-FRAMEWORK-MIB
  rmon, OwnerString                      FROM RMON-MIB
  protocolDirLocalIndex                  FROM RMON2-MIB;

--  Application Performance Measurement MIB

apm MODULE-IDENTITY
  LAST-UPDATED "200402190000Z"  -- February 19, 2004
  ORGANIZATION "IETF RMON MIB Working Group"
  CONTACT-INFO
     "Author:
             Steve Waldbusser




          Phone:  +1-650-948-6500
          Fax :   +1-650-745-0671
           Email:  waldbusser@nextbeacon.com

       Working Group Chair:
             Andy Bierman
             Cisco Systems, Inc.
          Postal: 170 West Tasman Drive
             San Jose, CA USA 95134
            Tel: +1 408 527-3711
          E-mail: abierman@cisco.com

       Working Group Mailing List: <rmonmib@ietf.org>
       To subscribe send email to: <rmonmib-request@ietf.org>
      "
  DESCRIPTION
```

```
      "The MIB module for measuring application performance
      as experienced by end-users.

      Copyright (C) The Internet Society (2004). This version of
      this MIB module is part of RFC 3729; see the RFC itself for
      full legal notices."

    REVISION "200402190000Z"    -- February 19, 2004
    DESCRIPTION
      "The original version of this MIB Module, published as
      RFC3729."

    ::= { rmon 23 }

apmMibObjects OBJECT IDENTIFIER ::= { apm 1 }
apmConformance OBJECT IDENTIFIER ::= { apm 2 }
apmCompliances
     OBJECT IDENTIFIER ::= { apmConformance 1 }
apmGroups         OBJECT IDENTIFIER ::= { apmConformance 2 }


AppLocalIndex ::= TEXTUAL-CONVENTION
    STATUS       current
    DESCRIPTION
      "A locally arbitrary unique identifier associated with an
      application or application verb.

      All objects of type AppLocalIndex are assigned by the agent
      out of a common number space. In other words, AppLocalIndex
      values assigned to entries in one table must not overlap with
      AppLocalIndex values assigned to entries in another
      table. Further, every protocolDirLocalIndex value registered
      by the agent automatically assigns the same value out of the



      AppLocalIndex number space.

      For example, if the protocolDirLocalIndex values { 1, 3, 5, 7 }
      have been assigned, and the apmHttpFilterAppLocalIndex values
      { 6, 8, 9 } have been assigned:

          - Assignment of new AppLocalIndex values must not use
 the
            values { 1, 3, 5, 6, 7, 8, 9 }.
          - AppLocalIndex values { 1, 3, 5, 7 } are automatically
            assigned and are associated with the identical value of
            protocolDirLocalIndex. In particular, an entry in the
```

apmAppDirTable indexed by a value provides further
information about a protocol indexed by the same value
in the protocolDirTable of RMON2.

The value for each supported application must remain constant
at least from one re-initialization of the entity's network
management system to the next re-initialization, except that
if an application is deleted and re-created, it must be
re-created with a new value that has not been used since the
last re-initialization.

The specific value is meaningful only within a given SNMP
entity. An AppLocalIndex value must not be re-used until the
next agent restart."
SYNTAX Unsigned32
(1..2147483647)

ProtocolDirNetworkAddress ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
"A network level address whose semantics and encoding are
specified by an associated protocolDirLocalIndex
value. Objects of this type must specify which
protocolDirLocalIndex value is used. This value is encoded
according to the encoding rules for the identified
protocolDirectory entry.

For example, if the associated protocolDirLocalIndex indicates
an encapsulation of ip, this object is encoded as a length
octet of 4, followed by the 4 octets of the ip address,
in network byte order.

Objects of this type may allow this value to be the zero
length string. If so, they must identify they meaning of this
value."
SYNTAX OCTET STRING (SIZE(0..255))

DataSourceOrZero ::= TEXTUAL-CONVENTION

STATUS current
DESCRIPTION
"Identifies the source of
the data that the associated
function is configured to analyze. This source can be any
interface on this device.

In order to identify a particular interface, this
object shall identify the instance of the ifIndex
object, defined in [4], for the desired interface.

For example, if an entry were to receive data from
interface #1, this object would be set to ifIndex.1.

If the source of the data isn't an interface or cannot be
localized to an interface, this object would be set to 0.0"

REFERENCE "The DataSource textual convention is defined in
RFC 2021 [5]."
SYNTAX OBJECT IDENTIFIER

RmonClientID ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
"A long-lived unique ID assigned to an end-system. This ID is
assigned by the agent using an implementation-specific
algorithm.

Because a client machine may be assigned multiple addresses

over any time period it can be difficult to attribute
behavior to a particular client based solely on its
address. A ClientID may be assigned to provide a more
stable handle for referencing that client. The entity that
assigns the ClientID may use various implementation
techniques to keep track of a client but if the assigning
entity is unable to track client address mappings, it may map
client identifiers to client addresses rather than to
distinct client machines.

This is named ClientID because it helps to solve a problem
seen in network clients (servers usually have well-known,
long-lived addresses). However, ClientID's may be assigned to
any end-system regardless of its role on the network."
SYNTAX Unsigned32 (0..4294967295)

TransactionAggregationType ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION

"Specifies one of 4 different techniques

for aggregating
transactions.

The metrics for a single transaction are the responsiveness of the transaction and whether the transaction succeeded (a boolean). When such metrics are aggregated in this MIB Module, these metrics are replaced by averages and distributions of responsiveness and availability. The metrics describing aggregates are constant no matter which type of aggregation is being performed. These metrics may be found in the apmReportTable.

The flows(1) aggregation is the simplest. All transactions that share common application/server/client 3-tuples are aggregated together, resulting in a set of metrics for all such unique 3-tuples.

The clients(2) aggregation results in somewhat more aggregation (i.e., fewer resulting records). All transactions that share common application/client tuples are aggregated together, resulting in a
set of metrics for all such unique
tuples.

The servers(3) aggregation usually results in still more aggregation (i.e., fewer resulting records). All transactions that share common application/server tuples are aggregated together, resulting in a set of metrics for all such unique tuples.

The applications(4) aggregation results in the most aggregation (i.e., the fewest resulting records). All transactions that share a common application are aggregated together, resulting in a set of metrics for all such unique applications.

Note that it is not meaningful to aggregate applications, as different applications have widely varying characteristics. As a result, this set of aggregations is complete."

```
  SYNTAX      INTEGER {
                flows(1),    -- Least Aggregation
                clients(2),
                servers(3),
                applications(4) -- Most Aggregation
               }

-- The APM Application Directory Group
```

```
-- The Application Directory Table contains a record for every

-- application monitored by this agent. This table is also used to
-- configure whether or not an application will be measured and which
-- bucket boundaries will be used for the application.
--
-- The bucket boundaries define the break-points between bins of a
-- histogram analysis for that application. As an example of how this
-- works, consider an entry representing response-time for http.
-- If the boundaries are set as follows:
-- Boundary1: 500 milliseconds
-- Boundary2: 1 second
-- Boundary3: 2 seconds
-- Boundary4: 5
-- Boundary5: 15
-- Boundary6: 60
--
-- If the following measurements are made (all in milliseconds):
-- 377, 8645, 1300, 487, 1405, 775, 1115, 850, 945, 1054, 7745, 9380
--
-- A report run during this interval would report the following
-- counts:
-- Bucket1: 2
-- Bucket2: 3
-- Bucket3: 4
-- Bucket4: 0
-- Bucket5: 3
-- Bucket6: 0
--
 Bucket7: 0

apmAppDirTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ApmAppDirEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The APM MIB directory of applications and application
     verbs. The agent will populate this table with all
     applications/verbs of any responsivenessType it has the
     capability to monitor. Since the agent populates this table
     with every entry it has the capability to monitor, the
     entries in this table are read-write, allowing the management
     station to modify parameters in this table but not to add new
     entries or delete entries (however, entries may be
     disabled). If new entries are added to the apmHttpFilterTable
     or the apmUserDefinedAppTable, the agent will add the
```

corresponding entries to this table.

It is an implementation-dependent matter as to how the agent sets these default parameters. For example, it may leave certain entries
in this table 'off(0)' if the agent developer

believes that combination will be infrequently used, allowing a manager that needs that capability to set it to 'on(1)'.

Some applications are registered in the RMON2 protocol directory and some are registered in other tables in this MIB Module. Regardless of where an application is originally registered, it is assigned an AppLocalIndex value that is the primary index for this table.

The contents of this table affect all reports and exceptions generated by this agent. Accordingly, modification of this table should be performed by a manager acting in the role of administrator. In particular, management software should not require or enforce particular configuration of this table - it should reflect the preferences of the site administrator, not the software author. As a practical matter, this requires management
software to allow the administrator to configure
the values it will use so that it can be adapted to the site policy."
::= { apmMibObjects 1 }

```
apmAppDirEntry OBJECT-TYPE
  SYNTAX      ApmAppDirEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The APM MIB directory of applications and application
     verbs. An entry will exist in this table for all applications
     for which application performance measurement is supported."
  INDEX { apmAppDirAppLocalIndex,
          apmAppDirResponsivenessType }
  ::= { apmAppDirTable 1 }

ApmAppDirEntry ::= SEQUENCE {
  apmAppDirAppLocalIndex           AppLocalIndex,
  apmAppDirResponsivenessType      INTEGER,
  apmAppDirConfig                  INTEGER,
  apmAppDirResponsivenessBoundary1  Unsigned32,
```

```
  apmAppDirResponsivenessBoundary2  Unsigned32,
  apmAppDirResponsivenessBoundary3  Unsigned32,
  apmAppDirResponsivenessBoundary4  Unsigned32,
  apmAppDirResponsivenessBoundary5
 Unsigned32,
  apmAppDirResponsivenessBoundary6  Unsigned32
}

apmAppDirAppLocalIndex OBJECT-TYPE
  SYNTAX      AppLocalIndex
  MAX-ACCESS  not-accessible



  STATUS      current
  DESCRIPTION
     "The AppLocalIndex assigned for this application Directory
     entry."
  ::= { apmAppDirEntry 1 }

apmAppDirResponsivenessType OBJECT-TYPE
  SYNTAX      INTEGER {
                transactionOriented(1),
                throughputOriented(2),
                streamingOriented(3)
              }
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "This object describes and configures the agent's support for
     application performance measurement for this application.
     There are 3 types of measurements for different types of
     applications:

     Transaction-Oriented applications have a fairly constant
     workload to perform for all transactions. The responsiveness
     metric for transaction-oriented
 applications is application
     response time (from first request to final delivery of
     service) and is measured in milliseconds. This is
     commonly referred to as end-user response time.

     Throughput-Oriented applications have widely varying workloads
     based on the nature of the client request. In particular,
     throughput-oriented applications vary widely in the amount of
     data that must be transported to satisfy the request. The
     responsiveness metric for throughput-oriented applications is
     kilobits per second.
```

Streaming-Oriented applications deliver data at a constant metered rate of speed regardless of the responsiveness of the networking and computing infrastructure. This constant rate of speed is generally specified to be below (sometimes well below) the nominal capability of the infrastructure. However, when the infrastructures cannot deliver data at this speed, interruption of service or degradation of service can result. The responsiveness metric for streaming-oriented applications is the ratio of time that the service is degraded or interrupted to the total service time. This metric is measured in parts per million.

Note that for some applications, measuring more than one responsiveness type may be interesting. For agents that wish

to support more than one measurement for a application, they will populate this table with multiple entries for that application, one for each type."
::= { apmAppDirEntry 2 }

apmAppDirConfig OBJECT-TYPE
SYNTAX INTEGER {
off(1),
on(2)
}
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"This object describes and configures support for application performance measurement for this application.

If the value of this object is on(2),
the agent supports
measurement of application performance metrics for this application and is configured to measure such metrics for all APM MIB functions and all interfaces. If the value of this object is off(1), the agent supports measurement of application performance for this application but is configured to not measure these metrics for any APM MIB functions or interfaces. Whenever this value changes from on(2) to off(1), the agent shall delete all related entries in all tables in this MIB Module.

The value of this object must persist across reboots."
::= { apmAppDirEntry 3 }

```
apmAppDirResponsivenessBoundary1 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     "The boundary value between bucket1 and bucket 2. If this
     value is modified, all entries in the apmReportTable must be
     deleted by the agent.

     The value
 of this object must persist across reboots."
  ::= { apmAppDirEntry 4 }

apmAppDirResponsivenessBoundary2 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     "The boundary value between bucket2 and bucket 3. If this



     value is modified, all entries in the apmReportTable must be
     deleted by the agent.

     The value of this object must persist across reboots."
  ::= { apmAppDirEntry 5 }

apmAppDirResponsivenessBoundary3 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     "The boundary value between bucket3 and bucket 4. If this
     value is modified, all entries in the apmReportTable must be
     deleted by the agent.

     The value of this object must persist across reboots."
  ::= { apmAppDirEntry 6 }

apmAppDirResponsivenessBoundary4 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-write
  STATUS      current
   DESCRIPTION
     "The boundary value between bucket4 and bucket 5. If this
     value is modified, all entries in the apmReportTable must be
```

deleted by the agent.

The value of this object must persist across reboots."
::= { apmAppDirEntry 7 }

apmAppDirResponsivenessBoundary5 OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"The boundary value between bucket5 and bucket 6. If this
value is modified, all entries in the apmReportTable must be
deleted by the agent.

The value of this object must persist across reboots."
::= { apmAppDirEntry 8 }

apmAppDirResponsivenessBoundary6 OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"The boundary value between bucket6 and bucket 7. If this

value is modified, all entries in the apmReportTable must be
deleted by the agent.

The value of
this object must persist across reboots."
::= { apmAppDirEntry 9 }

-- Scalars related to the Application Directory table

apmBucketBoundaryLastChange OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime the last time that any bucket boundary
in any appDirEntry was changed. This object can help to
determine if two managers are both trying to enforce different
configurations of this table."
::= { apmMibObjects 2 }

apmAppDirID OBJECT-TYPE
SYNTAX OBJECT IDENTIFIER

MAX-ACCESS read-write
STATUS current
DESCRIPTION
"This object allows managers to avoid downloading application directory information when the directory is set to a known (usually fixed) configuration.

If the value of this object isn't 0.0, it signifies that the entire contents of the apmAppDirTable, apmHttpFilterTable, apmUserDefinedAppTable and protocolDirTable are equal to a known state identified by the value of this object. If a manager recognizes this value as identifying a directory configuration it has a local copy of, it may use this local copy rather than downloading these tables. Note that it may have downloaded this local copy (and the ID) from another agent and used this copy for all other agents that advertised the same ID.

If an agent recognizes that the entire contents of the apmAppDirTable, apmHttpFilterTable, apmUserDefinedAppTable and protocolDirTable are equal to a known state to which an ID has been assigned, it should set this object to that ID.

In many cases when this feature is used, the application directory information will be in read-only memory and thus the tables may not be modified via SNMP requests. In the event

that the tables are writable and a modification is made, the
agent is responsible for setting this object to 0.0 if it cannot determine that the state is equal to a known state.

An agent is not obligated to recognize and advertise all such registered states as it may not have knowledge of all states. Thus, a manager may encounter agents whose DirectoryID value is 0.0 even though the contents of the directory were equal to a registered state.

Note that the contents of those tables includes the protocolDirLocalIndex and appLocalIndex values. In other words, these values can't be assigned randomly on each agent, but must be equal to values that are part of the known state. While it is possible for a manager to download application directory details using SNMP and to set the appropriate directoryID, the manager would need to have some

scheme to ensure consistent values of LocalIndex variables
from agent to agent.
Such schemes are outside the scope of
this specification.

Application directory registrations are unique within an
administrative domain.

Typically these registrations will be made by an agent
software developer who will set the application directory
tables to a read-only state and assign a DirectoryID to that
state. Thus, all agents running this software would share the
same DirectoryID. As the application directory might change
from one software release to the next, the developer may
register different DirectoryID's for each software release.

A customer could also create a site-wide application directory
configuration and assign a DirectoryID to that configuration
as long as consistent values of LocalIndex variables can be
ensured.

The value of this object must persist across reboots."
::= { apmMibObjects 3 }

-- APM HTTP Filter Table

-- The HTTP Filter Table
creates virtual applications which measure the
-- performance of certain web pages or sets of web pages. Some
-- circumstances where this is particularly useful are:
--
-- - An Intranet or ASP scenario where a business application is
-- running on one or more web pages or scripts.

-- (i.e., /expense/submit.cgi?employeeID=3426&...)
-- - A web-hosting scenario where one wants to measure the
-- service level for a particular customer
-- - An e-commerce scenario where the performance of certain
-- pages needs to be monitored more closely.
-- (i.e., shopping cart, shipping, credit card authorization)

apmHttpFilterTable OBJECT-TYPE
SYNTAX SEQUENCE OF ApmHttpFilterEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION

"A table that creates virtual applications which measure the performance of certain web pages or sets of web pages.

When an entry is added to this table, the agent will automatically create one or more entries in the apmAppDirTable (one for each responsivenessType it is capable of measuring).

Note that when entries exist in this table some HTTP transactions will be summarized twice: in applications represented here as well as the HTTP application. If entries in this table overlap, these transactions may be summarized additional times.

The contents of this table affect all reports and exceptions generated by this agent. Accordingly, modification of this table should be performed by a manager acting in the role of administrator. In particular, management software should not require or enforce particular configuration of this table - it should reflect the preferences of the site administrator, not the software author."
::= { apmMibObjects 4 }

apmHttpFilterEntry OBJECT-TYPE
SYNTAX ApmHttpFilterEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"A virtual application which measure the performance of certain web pages or sets of web pages."
INDEX { apmHttpFilterIndex }
::= { apmHttpFilterTable 1 }

ApmHttpFilterEntry ::= SEQUENCE {
apmHttpFilterIndex Unsigned32,
apmHttpFilterAppLocalIndex AppLocalIndex,

apmHttpFilterServerProtocol Unsigned32,
apmHttpFilterServerAddress ProtocolDirNetworkAddress,
apmHttpFilterURLPath OCTET STRING,
apmHttpFilterMatchType INTEGER,
apmHttpFilterOwner OwnerString,
apmHttpFilterStorageType StorageType,
apmHttpFilterRowStatus RowStatus
}

```
apmHttpFilterIndex OBJECT-TYPE
  SYNTAX      Unsigned32 (0..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "An index that uniquely identifies an entry in the
     apmHttpFilterTable."
  ::= { apmHttpFilterEntry 1 }

apmHttpFilterAppLocalIndex
 OBJECT-TYPE
  SYNTAX      AppLocalIndex
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The AppLocalIndex that represents HTTP transactions
     that match this entry.

     This object is read-only. A value is created by the agent from
     an unused AppLocalIndex value when this apmHttpFilterEntry is
     created."
  ::= { apmHttpFilterEntry 2 }

apmHttpFilterServerProtocol OBJECT-TYPE
  SYNTAX      Unsigned32 (1..2147483647)
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The protocolDirLocalIndex value of the network level protocol
     of the apmHttpFilterServerAddress."
  ::= { apmHttpFilterEntry 3 }

apmHttpFilterServerAddress OBJECT-TYPE
  SYNTAX      ProtocolDirNetworkAddress
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This entry will only represent transactions coming from the
     network address specified in this object.




     This is represented
 as an octet string with
     specific semantics and length as identified
     by the associated apmHttpFilterServerProtocol object.
```

```
      If this object is the zero-length string, then this entry will
      match one of the addresses represented by the 'host' component
      of the associated apmHttpFilterURLPath object, where the
      format if a URL [9] is
      http://<host>:<port>/<path>?<searchpart>."
    ::= { apmHttpFilterEntry 4 }

apmHttpFilterURLPath OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE(0..65535))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "This entry will only represent HTTP transactions
      where the URL path component in the request matches this
      value. This value represents the requested path regardless of
      any substitution that the server might perform.

      Prior to the matching, the URL is stripped of any server
      address or DNS name and consists solely of the path name on

      that server.

      If the length of this object is zero, then this entry will
      match if the associated apmHttpFilterServerAddress match. If
      the length of that object is also zero, then this entry will
      match nothing.

      The value of the associated apmHttpFilterMatchType dictates
      the type of matching that will be attempted."
    ::= { apmHttpFilterEntry 5 }

apmHttpFilterMatchType OBJECT-TYPE
    SYNTAX      INTEGER {
                  exact(1),
                  stripTrailingSlash(2),
                  prefix(3)
                }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "The matching algorithm used to compare the URL pathname.

      If the value is exact(1), then the pathname component will be
      compared with the associated apmHttpFilterURLPath and
      will only be associated with this entry if it matches exactly.
```

If the value is stripTrailingSlash(2), then the pathname

component will be compared with the associated
apmHttpFilterURLPath and will only be associated with this
entry if it matches exactly or if the pathname ends with a '/'
symbol and matches apmHttpFilterURLPath if the '/' symbol is
removed from the pathname. This option exists for those paths
where an optional trailing slash is possible but for which a
prefix match would be too broad.

If the value is prefix(3), then the pathname component will be
compared with the associated apmHttpFilterURLPath and will
only be associated with this entry if the beginning of the
pathname matches every octet of this value. Octets that extend
beyond the length of this value are ignored."
::= { apmHttpFilterEntry 6 }

apmHttpFilterOwner OBJECT-TYPE
SYNTAX OwnerString
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The entity that configured this entry and is
therefore using
the resources assigned to it."
::= { apmHttpFilterEntry 7 }

apmHttpFilterStorageType OBJECT-TYPE
SYNTAX StorageType
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The storage type of this apmHttpFilterEntry. If the value of
this object is 'permanent', no objects in this row need to be
writable."
::= { apmHttpFilterEntry 8 }

apmHttpFilterRowStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The status of this apmHttpFilterEntry. No objects in this row
may be modified while the row's status is 'active'."
::= { apmHttpFilterEntry 9 }

apmHttpIgnoreUnregisteredURLs OBJECT-TYPE

SYNTAX TruthValue
MAX-ACCESS read-write
STATUS current

DESCRIPTION
"When true, APM measurements of HTTP transactions will only measure transactions relating to URLs that match a filter in the apmHttpFilterTable. Thus,
measurements for the HTTP
application will present aggregated statistics for URL-matching HTTP transactions and measurements for the HTTP GET application verb will present aggregated statistics for URL-matching HTTP GET transactions.

This will be used in environments that wish to monitor only targeted URLs and to ignore large volumes of internet web browsing traffic.

This object affects all APM reports and exceptions generated by this agent. Accordingly, modification of this object should be performed by a manager acting in the role of administrator. In particular, management software should not require or enforce particular configuration of this object - it should reflect the preferences of the site administrator, not the software author.

The value of this object must persist across reboots."
::= { apmMibObjects 5 }

apmHttp4xxIsFailure OBJECT-TYPE
SYNTAX
TruthValue
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"When true, this agent will recognize HTTP errors in the range of 400 through 499 and will treat them as unavailable transactions. When false or when this object isn't supported, they will be treated as successful transactions.

This object allows such error pages to be tracked at the possible expense of having user typos treated as poor service on the part of the web server.

This object affects all reports and exceptions generated by this agent. Accordingly, modification of this object should be

```
      performed by a manager acting in the role of administrator. In
      particular, management software should not require or enforce
      particular configuration of this object - it should reflect
      the preferences of the site administrator, not the software
      author.

      The value of this object must persist
 across reboots."
  ::= { apmMibObjects 6 }



-- The APM User-Defined Application Table

-- Many application protocols will never be registered with a
-- standards body (and thus included in a protocol directory standard)
-- because they are custom, in-house or proprietary
-- applications. Nevertheless, implementation strategies exist for
-- monitoring the end-user experience of these applications.
--
-- This read-only table provides a means for the agent to advertise
-- which user-defined applications it is monitoring and to associate
-- each with an AppLocalIndex value. It is an implementation-dependent
-- matter as to how the agent learns how to monitor these
-- applications.

apmUserDefinedAppTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ApmUserDefinedAppEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A table that advertises user-defined applications that the
      agent is measuring.

      The agent will automatically create one or more
 entries in the
      apmAppDirTable (one for each responsivenessType it is
      capable of measuring) for each entry in this table.

      Note that when entries exist in this table some
      transactions can be summarized more than once if there is
      overlap between applications defined here and applications
      defined in the protocol directory or in the httpFilter table."
  ::= { apmMibObjects 7 }

apmUserDefinedAppEntry OBJECT-TYPE
  SYNTAX      ApmUserDefinedAppEntry
  MAX-ACCESS  not-accessible
```

```
  STATUS      current
  DESCRIPTION
     "A user-defined application that the agent is measuring, along
     with its AppLocalIndex assignment.

     The apmAppDirAppLocalIndex value in the index identifies
     the agent-assigned AppLocalIndex value for this user-defined
     application."
  INDEX { apmAppDirAppLocalIndex }
  ::= { apmUserDefinedAppTable 1 }

ApmUserDefinedAppEntry ::= SEQUENCE {
  apmUserDefinedAppParentIndex    Unsigned32,



   apmUserDefinedAppApplication    SnmpAdminString
}

apmUserDefinedAppParentIndex OBJECT-TYPE
  SYNTAX      Unsigned32 (1..2147483647)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The protocolDirLocalIndex value of the highest-layer
     protocol defined in the protocolDirTable that this
     application is a child of."
  ::= { apmUserDefinedAppEntry 1 }

apmUserDefinedAppApplication OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "A human readable descriptive tag for this application."
  ::= { apmUserDefinedAppEntry 2 }

-- The APM Name Table

apmNameTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ApmNameEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A client machine may have multiple addresses during a period
     of monitoring. The apmNameTable assigns a long-lived
     identifier to a client and records what addresses
```

were
assigned to that client for periods of time. Various implementation techniques exist for tracking this mapping but if an agent is unable to track client address mappings, it may map client identifiers to client addresses rather than to distinct client machines.

A particular apmNameClientID should be a constant attribute of a particular client. When available, the agent may also record the machine name and/or user name which may be valuable for displaying to humans. The apmNameMachineName and apmNameUserName are relatively constant, changing only if these attributes actually change on the client.

The agent will store a historical log of these entries, aging out old entries as the log becomes too large. Since this table contains information vital to the interpretation of other tables (e.g., the apmReportTable), the agent should ensure that

the log doesn't
age out entries that would be referenced by
data in those tables.

Note that an entry for a clientID is active from its StartTime until the StartTime of another entry (for the same clientID) that supersedes it, or 'now' if none supersede it. Therefore, if a clientID only has a single entry, it is by definition very new and should never be aged out. No entry for a clientID should be aged out unless it has been updated by a new entry for the client (i.e., with an updated address) and only if the new entry is 'old' enough.

To determine how old is old enough, compute the maximum value of Interval * (NumReports + 1) of all entries in the apmReportControlTable (the '+ 1' is to allow a reasonable period of time for the report to be downloaded). Then take the larger of this value and the age in seconds of the oldest entry in the current transaction table. If an entry for
a
clientID is superseded by another entry whose StartTime is more than this many seconds ago, then the older entry may be deleted."
::= { apmMibObjects 8 }

apmNameEntry OBJECT-TYPE
SYNTAX ApmNameEntry

```
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "An entry in the APM name table. An entry exists for each
     period of time that a client has been associated with a
     particular address.

     The protocolDirLocalIndex value in the index identifies
     the network layer protocol for the ClientAddress for this
     entry.

     Note that some combinations of index values may result in an
     index that exceeds 128 sub-identifiers in length which exceeds
     the maximum for the SNMP protocol. Implementations should take
     care to avoid such combinations."
  INDEX { apmNameClientID,
          protocolDirLocalIndex, apmNameClientAddress,
          apmNameMappingStartTime }
  ::=
 { apmNameTable 1 }

ApmNameEntry ::= SEQUENCE {
  apmNameClientID               RmonClientID,
  apmNameClientAddress          ProtocolDirNetworkAddress,



  apmNameMappingStartTime       DateAndTime,
  apmNameMachineName            SnmpAdminString,
  apmNameUserName               SnmpAdminString
}

apmNameClientID OBJECT-TYPE
  SYNTAX      RmonClientID
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A unique ID assigned to the machine represented by this
      mapping. This ID is assigned by the agent using an
      implementation-specific algorithm."
  ::= { apmNameEntry 1 }

apmNameClientAddress OBJECT-TYPE
  SYNTAX      ProtocolDirNetworkAddress (SIZE(1..255))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The network client address for this client when this mapping
```

was active.

This is represented as an octet string with specific semantics
and length as
identified by the protocolDirLocalIndex
component of the index. This object may not be the zero length
string.

Since this object is an index variable, it is encoded in the
index according to the index encoding rules. For example, if
the protocolDirLocalIndex component of the index indicates an
encapsulation of ip, this object is encoded as a length octet
of 4, followed by the 4 octets of the ip address, in network
byte order. Care should be taken to avoid values of this
object that, in conjunction with the other index variables,
would result in an index longer than SNMP's maximum of 128
subidentifiers."
::= { apmNameEntry 2 }

apmNameMappingStartTime OBJECT-TYPE
SYNTAX DateAndTime
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The time that the agent first discovered this mapping
as active."
::= { apmNameEntry 3 }

apmNameMachineName OBJECT-TYPE
SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The human readable name of the client machine.

If the client has no machine name or the agent is
unable to learn the machine name, this object will be
a zero-length string."
::= { apmNameEntry 4 }

apmNameUserName OBJECT-TYPE
SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current
DESCRIPTION

```
      "The human readable name of a human user using the client
      machine. If more than one user name are available
      simultaneously, it is an implementation-dependent matter as to
      which is used here. However, if the user name changes, this
      object should change to reflect that change.

      Non-human user names like 'root' or 'administrator' aren't
      intended as values for this object. If the client has no
      recorded user name or the agent is unable to learn a user
      name, this
 object will be a zero-length string."
  ::= { apmNameEntry 5 }

-- The APM Report Group

apmReportControlTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ApmReportControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "Parameters that control the creation of a set of reports that
     aggregate application performance."
  ::= { apmMibObjects 9 }

apmReportControlEntry OBJECT-TYPE
  SYNTAX      ApmReportControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A conceptual row in the apmReportControlTable.

      An example of the indexing of this table is




      apmReportControlInterval.3"
  INDEX { apmReportControlIndex }
  ::= { apmReportControlTable 1 }

ApmReportControlEntry ::= SEQUENCE {
  apmReportControlIndex           Unsigned32,
  apmReportControlDataSource      DataSourceOrZero,
  apmReportControlAggregationType  TransactionAggregationType,
  apmReportControlInterval
 Unsigned32,
  apmReportControlRequestedSize    Unsigned32,
  apmReportControlGrantedSize      Unsigned32,
  apmReportControlRequestedReports Unsigned32,
```

```
  apmReportControlGrantedReports   Unsigned32,
  apmReportControlStartTime        TimeStamp,
  apmReportControlReportNumber     Unsigned32,
  apmReportControlDeniedInserts    Counter32,
  apmReportControlDroppedFrames    Counter32,
  apmReportControlOwner            OwnerString,
  apmReportControlStorageType      StorageType,
  apmReportControlStatus           RowStatus
}


apmReportControlIndex OBJECT-TYPE
  SYNTAX      Unsigned32 (1..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "An index that uniquely identifies an entry in the
     apmReportControlTable.  Each such entry defines a unique
     report whose results are placed in the apmReportTable on
     behalf of this apmReportControlEntry."
  ::= { apmReportControlEntry 1 }

apmReportControlDataSource OBJECT-TYPE
   SYNTAX      DataSourceOrZero
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The source of the data for APM Reports generated on
     behalf of this apmReportControlEntry.

     If the measurement is being performed by a probe, this should
     be set to interface or port where data was received for
     analysis. If the measurement isn't being performed by a probe,
     this should be set to the primary interface over which the
     measurement is being performed. If the measurement isn't being
     performed by a probe and there is no primary interface or this



     information isn't known, this object should be set to 0.0.

     This object may not be modified if the associated
     apmReportControlStatus object is equal to active(1)."
  ::= { apmReportControlEntry 2 }

apmReportControlAggregationType OBJECT-TYPE
  SYNTAX      TransactionAggregationType
        --    INTEGER {
```

```
        --      flows(1),
        --      clients(2),
        --      servers(3),
        --      applications(4)
        --    }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The type of aggregation being performed for this set of
        reports.

        The metrics for a single transaction are the responsiveness of
        the transaction and whether the transaction succeeded (a
        boolean). When such metrics are aggregated in this MIB Module,
        these metrics are replaced by averages and distributions of
        responsiveness and availability. The metrics describing
        aggregates are constant no matter which type of aggregation is
        being performed. These metrics may be found in the
        apmReportTable.

        The flows(1) aggregation is the simplest. All transactions
        that share common application/server/client 3-tuples are
        aggregated together, resulting in a set of metrics for all
        such unique 3-tuples.

        The clients(2) aggregation results in somewhat more
        aggregation (i.e., fewer resulting records). All transactions
        that share common application/client tuples are aggregated
        together, resulting in a set of metrics for all such unique
        tuples.

        The servers(3) aggregation usually results in still more
        aggregation (i.e., fewer resulting records). All transactions
        that share common application/server tuples are aggregated
        together, resulting in a set of metrics for all such unique
        tuples.

        The applications(4) aggregation results in the most
        aggregation (i.e., the fewest resulting records). All

        transactions that share a common application are aggregated
        together, resulting in a set of metrics for all such unique
        applications.

        Note that it is not meaningful to aggregate applications, as
        different applications have widely varying characteristics.
```

As
a result, this set of aggregations is complete.

This object may not be modified if the associated
apmReportControlStatus object is equal to active(1)."
::= { apmReportControlEntry 3 }

apmReportControlInterval OBJECT-TYPE
SYNTAX Unsigned32
UNITS "Seconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The interval in seconds over which data is accumulated before
being aggregated into a report in the apmReportTable. All
reports with the same apmReportControlIndex will be based on
the same interval. This object must be greater than zero.

Many users desire that these reports be synchronized to within
seconds of the beginning of the hour because the results may
be correlated more meaningfully to business behavior and so
that data from multiple agents is aggregated over the same
time periods. Thus management software may take extra effort
to synchronize
reports to the beginning of the hour and to one
another. However, the agent must not allow reports to 'drift'
over time as they will quickly become unsynchronized. In
particular, if there is any fixed processing delay between
reports, the reports should deduct this time from the interval
so that reports don't drift.

This object may not be modified if the associated
apmReportControlStatus object is equal to active(1)."
DEFVAL { 3600 }
::= { apmReportControlEntry 4 }

apmReportControlRequestedSize OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The number of entries requested to be allocated for each
report generated on behalf of this entry."
::= { apmReportControlEntry 5 }

apmReportControlGrantedSize OBJECT-TYPE

```
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The number of entries per
 report the agent has allocated
      based on the requested amount in apmReportControlRequestedSize.
      Since multiple reports are saved, the total number of entries
      allocated will be this number multiplied by the value of
      apmReportControlGrantedReports, or 1 if that object doesn't
      exist.

      When the associated apmReportControlRequestedSize object is
      created or modified, the agent should set this object as
      closely to the requested value as is possible for the
      particular implementation and available resources. When
      considering resources available, the agent must consider its
      ability to allocate this many entries for all reports.

      Note that while the actual number of entries stored in the
      reports may fluctuate due to changing conditions, the agent
      must continue to have storage available to satisfy the full
      report size for all reports when necessary. Further, the agent
      must
 not lower this value except as a result of a set to the
      associated apmReportControlRequestedSize object."
  ::= { apmReportControlEntry 6 }

apmReportControlRequestedReports OBJECT-TYPE
  SYNTAX      Unsigned32 (0..65535)
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "The number of saved reports requested to be allocated on
      behalf of this entry."
  ::= { apmReportControlEntry 7 }

apmReportControlGrantedReports OBJECT-TYPE
  SYNTAX      Unsigned32 (0..65535)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The number of saved reports the agent has allocated
      based on the requested amount in
      apmReportControlRequestedReports. Since each report can have
      many entries, the total number of entries allocated will be
      this number multiplied by the value of
      apmReportControlGrantedSize, or 1 if that object doesn't
```

exist.

When the associated apmReportControlRequestedReports
object is
created or modified, the agent should set this object as
closely to the requested value as is possible for the
particular implementation and available resources. When
considering resources available, the agent must consider its
ability to allocate this many reports each with the number of
entries represented by apmReportControlGrantedSize, or 1 if
that object doesn't exist.

Note that while the storage required for each report may
fluctuate due to changing conditions, the agent must continue
to have storage available to satisfy the full report size for
all reports when necessary. Further, the agent must not lower
this value except as a result of a set to the associated
apmReportControlRequestedSize object."
::= { apmReportControlEntry 8 }

apmReportControlStartTime OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current

DESCRIPTION
"The value of sysUpTime when the system began processing the
report in progress. Note that the report in progress is not
available.

This object may be used by the management station to figure
out the start time for all previous reports saved for this
apmReportControlEntry, as reports are started at fixed
intervals."
::= { apmReportControlEntry 9 }

apmReportControlReportNumber OBJECT-TYPE
SYNTAX Unsigned32 (1..4294967295)
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of the report in progress. When an
apmReportControlEntry is activated, the first report will be
numbered one."
::= { apmReportControlEntry 10 }

```
apmReportControlDeniedInserts OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of failed attempts to add an entry to reports for




     this apmReportControlEntry
 because the number of entries
     would have exceeded apmReportControlGrantedSize.

     This number is valuable in determining if enough entries have
     been allocated for reports in light of fluctuating network
     usage. Note that since an entry that is denied will often be
     attempted again, this number will not predict the exact number
     of additional entries needed, but can be used to understand
     the relative magnitude of the problem.

     Also note that there is no ordering specified for the entries
     in the report, thus there are no rules for which entries will
     be omitted when not enough entries are available. As a
     consequence, the agent is not required to delete 'least
     valuable' entries first."
  ::= { apmReportControlEntry 11 }

apmReportControlDroppedFrames OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The total number of frames which were
 received by the agent
     and therefore not accounted for in the *StatsDropEvents, but
     for which the agent chose not to count for this entry for
     whatever reason.  Most often, this event occurs when the agent
     is out of some resources and decides to shed load from this
     collection.

     This count does not include packets that were not counted
     because they had MAC-layer errors.

     This counter is only relevant if this apm report is based on
     a data source whose collection methodology is based on
     analyzing network traffic.

     Note that if the apmReportTables are inactive because no
```

applications are enabled in the application directory, this
value should be 0.

Note that, unlike the dropEvents counter, this number is the
exact number of frames dropped."
::= { apmReportControlEntry 12 }

apmReportControlOwner OBJECT-TYPE
SYNTAX OwnerString
MAX-ACCESS read-create

STATUS current

DESCRIPTION
"The entity that configured this entry and is
therefore using the resources assigned to it."
::= { apmReportControlEntry 13 }

apmReportControlStorageType OBJECT-TYPE
SYNTAX StorageType
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The storage type of this apmReportControlEntry. If the value
of this object is 'permanent', no objects in this row need to
be writable."
::= { apmReportControlEntry 14 }

apmReportControlStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The status of this apmReportControlEntry.

An entry may not exist in the active state unless all
objects in the entry have an appropriate value. The only
objects in the entry that may be modified while the entry is
in the active state are apmReportControlRequestedSize and
apmReportControlRequestedReports.

If this object is not equal to active(1), all
associated entries in the apmReportTable shall be deleted
by the agent."
::= { apmReportControlEntry 15 }

```
-- The APM Report Table

apmReportTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ApmReportEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The data resulting from aggregated APM reports. Consult the
     definition of apmReportControlAggregationType for the
     definition of the various types of aggregations."
  ::= { apmMibObjects 10 }

apmReportEntry OBJECT-TYPE
  SYNTAX      ApmReportEntry
  MAX-ACCESS  not-accessible



  STATUS      current
  DESCRIPTION
     "A conceptual row in the apmReportTable.
     The apmReportControlIndex value in the index identifies the
     apmReportControlEntry on whose behalf this entry was created.
     The apmReportIndex value in the index identifies which report
     (in the series of reports) this
 entry is a part of.
     The apmAppDirAppLocalIndex value in the index identifies
     the common application of the transactions aggregated in this
     entry.
     The apmAppDirResponsivenessType value in the index
     identifies the type of responsiveness metric reported by
     this entry and uniquely identifies this entry when more
     than one responsiveness metric is measured for a flow.
     Entries will only exist in this table for those
     combinations of AppLocalIndex and ResponsivenessType
     that are configured 'on(1)'.
     The protocolDirLocalIndex value in the index identifies
     the network layer protocol of the apmReportServerAddress.
     When the associated apmReportControlAggregationType value is
     equal to applications(4) or clients(2), this
     protocolDirLocalIndex value will equal 0.
     The apmReportServerAddress value in the index identifies the
     network layer address of the server in transactions
 aggregated
     in this entry.
     The apmNameClientID value in the index identifies the
     client in transactions aggregated in this entry. If the
     associated apmReportControlAggregationType is equal to
```

```
      applications(4) or servers(3), then this protocolDirLocalIndex
      value will equal 0.

      An example of the indexing of this entry is
      apmReportTransactionCount.3.15.3.1.8.4.192.168.1.2.3232235788

      Note that some combinations of index values may result in an
      index that exceeds 128 sub-identifiers in length which exceeds
      the maximum for the SNMP protocol. Implementations should take
      care to avoid such combinations."
  INDEX { apmReportControlIndex, apmReportIndex,
          apmAppDirAppLocalIndex,
          apmAppDirResponsivenessType,
          protocolDirLocalIndex, apmReportServerAddress,
          apmNameClientID }
  ::= { apmReportTable 1 }

ApmReportEntry ::= SEQUENCE {
  apmReportIndex
              Unsigned32,
  apmReportServerAddress         ProtocolDirNetworkAddress,



  apmReportTransactionCount       Unsigned32,
  apmReportSuccessfulTransactions Unsigned32,
  apmReportResponsivenessMean     Unsigned32,
  apmReportResponsivenessMin      Unsigned32,
  apmReportResponsivenessMax      Unsigned32,
  apmReportResponsivenessB1       Unsigned32,
  apmReportResponsivenessB2       Unsigned32,
  apmReportResponsivenessB3       Unsigned32,
  apmReportResponsivenessB4       Unsigned32,
  apmReportResponsivenessB5       Unsigned32,
  apmReportResponsivenessB6       Unsigned32,
  apmReportResponsivenessB7       Unsigned32
}

apmReportIndex OBJECT-TYPE
  SYNTAX      Unsigned32 (1..4294967295)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The value of apmReportControlReportNumber for the report to
     which this entry belongs."
  ::= { apmReportEntry 1 }

apmReportServerAddress OBJECT-TYPE
```

```
  SYNTAX
   ProtocolDirNetworkAddress
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The network server address for this apmReportEntry.

     This is represented as an octet string with
     specific semantics and length as identified
     by the protocolDirLocalIndex component of the index.

     Since this object is an index variable, it is encoded in the
     index according to the index encoding rules.  For example, if
     the protocolDirLocalIndex indicates an encapsulation of ip,
     this object is encoded as a length octet of 4, followed by the
     4 octets of the ip address, in network byte order. Care
     should be taken to avoid values of this object that, in
     conjunction with the other index variables, would result in an
     index longer than SNMP's maximum of 128 subidentifiers.

     If the associated apmReportControlAggregationType is equal to
     applications(4) or clients(2), then this object will
 be a null
     string and will be encoded simply as a length octet of 0."
  ::= { apmReportEntry 2 }




apmReportTransactionCount OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The total number of transactions aggregated into this record."
  ::= { apmReportEntry 3 }

apmReportSuccessfulTransactions OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The total number of successful transactions aggregated into
     this record."
  ::= { apmReportEntry 4 }

apmReportResponsivenessMean OBJECT-TYPE
  SYNTAX      Unsigned32
```

```
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The arithmetic mean of the responsiveness metrics for all
     successful transactions aggregated into this record."
  ::= { apmReportEntry 5 }

apmReportResponsivenessMin OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS
   current
  DESCRIPTION
     "The minimum of the responsiveness metrics for all
     successful transactions aggregated into this record."
  ::= { apmReportEntry 6 }

apmReportResponsivenessMax OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The maximum of the responsiveness metrics for all
     successful transactions aggregated into this record."
  ::= { apmReportEntry 7 }

-- Note that when updating a report entry, a transaction will not be
-- counted in more than 1 bucket in an entry. It will be counted in
-- the first bucket that matches, starting with Bucket 1 (B1). Note
-- that if a transaction matches 2 application types, it will update




-- one bucket in each of 2 entries in this table.

apmReportResponsivenessB1 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of successful transactions aggregated into this
     record
 whose responsiveness was less than boundary1 value for
     this application."
  ::= { apmReportEntry 8 }

apmReportResponsivenessB2 OBJECT-TYPE
  SYNTAX      Unsigned32
```

```
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of successful transactions aggregated into this
     record whose responsiveness did not fall into Bucket 1 and was
     greater than or equal to the boundary1 value for this
     application and less than the boundary2 value for this
     application."
  ::= { apmReportEntry 9 }

apmReportResponsivenessB3 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of successful transactions aggregated into this
     record whose responsiveness did not fall into Bucket 1 or 2
     and as greater than or equal to the boundary2 value for this
     application and less than the boundary3 value for this
     application."
  ::= { apmReportEntry
 10 }

apmReportResponsivenessB4 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of successful transactions aggregated into this
     record whose responsiveness did not fall into Buckets 1
     through 3 and was greater than or equal to the boundary3 value
     for this application and less than the boundary4 value for
     this application."
  ::= { apmReportEntry 11 }




apmReportResponsivenessB5 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of successful transactions aggregated into this
     record whose responsiveness did not fall into Buckets 1
     through 4 and was greater than or equal to the boundary4 value
     for this application and less than the boundary5 value for
     this application."
```

```
  ::= { apmReportEntry 12 }

apmReportResponsivenessB6 OBJECT-TYPE
  SYNTAX      Unsigned32
   MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of successful transactions aggregated into this
     record whose responsiveness did not fall into Buckets 1
     through 5 and was greater than or equal to the
     boundary5 value for this application and less than the
     boundary6 value for this application."
  ::= { apmReportEntry 13 }

apmReportResponsivenessB7 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of successful transactions aggregated into this
     record whose responsiveness did not fall into Buckets 1
     through 6 and was greater than or equal to the boundary6 value
     for this application."
  ::= { apmReportEntry 14 }

-- APM Transaction Table

apmTransactionTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ApmTransactionEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "This table contains transactions
 that are currently running
     or have recently finished."
  ::= { apmMibObjects 11 }

apmTransactionEntry OBJECT-TYPE
  SYNTAX      ApmTransactionEntry




  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A conceptual row in the apmTransactionTable.

     The apmAppDirAppLocalIndex value in the index identifies
```

the application of the transaction represented by this entry.
The apmAppDirResponsivenessType value in the index
identifies the type of responsiveness metric reported by
this entry and uniquely identifies this entry when more
than one responsiveness metric is measured for a flow.
Entries will only exist in this table for those
combinations of AppLocalIndex and ResponsivenessType
that are configured 'on(1)'.
The protocolDirLocalIndex value in the index identifies
the network layer protocol of the apmTransactionServerAddress.
The apmTransactionServerAddress
value in the index identifies
the network layer address of the server in the transaction
represented by this entry.
The apmNameClientID value in the index identifies the
client in the transaction represented by this entry.

An example of the indexing of this entry is
apmTransactionCount.3.1.8.4.192.168.1.2.3232235788.2987

Note that some combinations of index values may result in an
index that exceeds 128 sub-identifiers in length which exceeds
the maximum for the SNMP protocol. Implementations should take
care to avoid such combinations."
INDEX { apmAppDirAppLocalIndex,
apmAppDirResponsivenessType,
protocolDirLocalIndex, apmTransactionServerAddress,
apmNameClientID, apmTransactionID }
::= { apmTransactionTable 1 }

ApmTransactionEntry ::= SEQUENCE {
apmTransactionServerAddress ProtocolDirNetworkAddress,
apmTransactionID
Unsigned32,
apmTransactionResponsiveness Unsigned32,
apmTransactionAge TimeInterval,
apmTransactionSuccess TruthValue
}

apmTransactionServerAddress OBJECT-TYPE
SYNTAX ProtocolDirNetworkAddress (SIZE (1..255))
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION

"The network server address for this apmTransactionEntry.

```
      This is represented as an octet string with specific semantics
      and length as identified by the protocolDirLocalIndex
      component of the index. This object may not be the zero length
      string.

      For example, if the protocolDirLocalIndex indicates an
      encapsulation of ip, this object is encoded as a length octet
      of 4, followed by the 4 octets of the ip address, in network
      byte order. Care should be taken to avoid values of this
      object that, in conjunction with the other index variables,
      would result in an index longer than
 SNMP's maximum of 128
      subidentifiers."
  ::= { apmTransactionEntry 1 }

apmTransactionID OBJECT-TYPE
  SYNTAX      Unsigned32 (0..4294967295)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A unique value for this transaction amongst other
      transactions sharing the same application layer protocol and
      server and client addresses. Implementations may choose to use
      the value of the client's source port, when possible."
  ::= { apmTransactionEntry 2 }

apmTransactionResponsiveness OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The current value of the responsiveness metric for this
      transaction. If this transaction has completed, the final
      value of the metric will be available.

      Note that this value may change over the lifetime of the
      transaction and it is the final value of this metric that is
      recorded as the responsiveness
 of the transaction for use in
      other APM MIB functions."
  ::= { apmTransactionEntry 3 }

apmTransactionAge OBJECT-TYPE
  SYNTAX      TimeInterval
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
```

```
      "If this transaction is still executing, this value shall be



      the length of time since it was started. If it has completed,
      this value shall be the length of time it was executing."
    ::= { apmTransactionEntry 4 }

apmTransactionSuccess OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "The success of this transaction up to this time. Once a
      transaction has been marked as failed, it cannot move back
      into the successful state."
    ::= { apmTransactionEntry 5 }

apmTransactionsRequestedHistorySize OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
      "The maximum number of completed transactions
   desired to be
      retained in the apmTransactionTable. If the agent doesn't have
      enough resources to retain this many, it will retain as many as
      possible. Regardless of this value, the agent must attempt to
      keep records for all current transactions it is monitoring.

      The value of this object must persist across reboots."
    ::= { apmMibObjects 12 }

-- The APM Exception table
-- The APM Exception Table creates filters so that a management
-- station can get immediate notification of a transaction that has
-- had poor availability or responsiveness.
--
-- This function is particularly helpful in unaggregated situations
-- where the numbers of agents is relatively high and the transaction
-- rate per agent is relatively low (such as agents for desktops or
-- dedicated to small workgroups). Polling agents in such an
-- environment would either cause scalability problems (high rate) or
-- lead to long notification delays (low rate).


apmExceptionTable
```

```
 OBJECT-TYPE
   SYNTAX      SEQUENCE OF ApmExceptionEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "This table creates filters so that a management station can
      get immediate notification of a transaction that has had poor



      availability or responsiveness.

      Each apmExceptionEntry is associated with a particular type of
      transaction and is applied to all transactions of that
      type. Multiple apmExceptionEntries may be associated with a
      particular type of transaction. A transaction type is
      identified by the value of the apmAppDirAppLocalIndex
      component of the index.

      Because the quality of a transaction is not known until it is
      completed, these thresholds are only applied after the
      transaction has completed."
   ::= { apmMibObjects 13 }

apmExceptionEntry OBJECT-TYPE
   SYNTAX      ApmExceptionEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
       "A conceptual row in the apmExceptionTable.

      The apmAppDirAppLocalIndex value in the index identifies
      the application this entry will monitor.
      The apmAppDirResponsivenessType value in the index
      identifies the type of responsiveness metric this entry will
      monitor."

   INDEX { apmAppDirAppLocalIndex,
           apmAppDirResponsivenessType, apmExceptionIndex }
   ::= { apmExceptionTable 1 }

ApmExceptionEntry ::= SEQUENCE {
   apmExceptionIndex                    Unsigned32,
   apmExceptionResponsivenessComparison    INTEGER,
   apmExceptionResponsivenessThreshold     Unsigned32,
   apmExceptionUnsuccessfulException       INTEGER,
   apmExceptionResponsivenessEvents        Counter32,
   apmExceptionUnsuccessfulEvents          Counter32,
```

```
  apmExceptionOwner                OwnerString,
  apmExceptionStorageType          StorageType,
  apmExceptionStatus               RowStatus
}

apmExceptionIndex
 OBJECT-TYPE
  SYNTAX      Unsigned32 (1..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION


      "An index that uniquely identifies an entry in the
      apmExceptionTable amongst other entries with equivalent index
      values for apmAppDirAppLocalIndex and
      apmAppDirResponsivenessType. Each such entry sets up
      thresholds for a particular measurement of a particular
      application."
  ::= { apmExceptionEntry 1 }

apmExceptionResponsivenessComparison OBJECT-TYPE
  SYNTAX      INTEGER {
                 none(1),
                 greater(2),
                 less(3)
              }
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "If this value is greater(2) or less(3), the associated
      apmExceptionResponsivenessThreshold will be compared to this
      value and an exception will be created if the responsiveness
      is greater than the threshold (greater(2)) or less than the
       threshold (less(3))."
  ::= { apmExceptionEntry 2 }

apmExceptionResponsivenessThreshold OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "The threshold that responsiveness metrics are compared to."
  ::= { apmExceptionEntry 3 }

apmExceptionUnsuccessfulException OBJECT-TYPE
  SYNTAX      INTEGER {
```

```
            off(1),
            on(2)
          }
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "If this value is on(2), an exception will be created if a
     transaction of the associated type is unsuccessful."
  ::= { apmExceptionEntry 4 }

apmExceptionResponsivenessEvents OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current



  DESCRIPTION
     "The total number of responsiveness exceptions generated. This
     counter will be incremented even if no notification was sent
     due to notifications not being
 configured or due to exceeding
     the apmNotificationMaxRate value."
  ::= { apmExceptionEntry 5 }

apmExceptionUnsuccessfulEvents OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The total number of unsuccessful exceptions generated. This
     counter will be incremented even if no notification was sent
     due to notifications not being configured or due to exceeding
     the apmNotificationMaxRate value."
  ::= { apmExceptionEntry 6 }

apmExceptionOwner OBJECT-TYPE
  SYNTAX      OwnerString
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The entity that configured this entry and is
     therefore using the resources assigned to it."
  ::= { apmExceptionEntry 7 }

apmExceptionStorageType OBJECT-TYPE
  SYNTAX     StorageType
  MAX-ACCESS read-create
```

```
  STATUS     current
  DESCRIPTION
     "The storage type of this apmReportControlEntry. If the value

   of this object is 'permanent', no objects in this row need to
     be writable."
  ::= { apmExceptionEntry 8 }

apmExceptionStatus OBJECT-TYPE
  SYNTAX     RowStatus
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "The status of this apmExceptionEntry. The only objects in the
     entry that may be modified while the entry is in the active
     state are apmExceptionResponsivenessComparison,
     apmExceptionResponsivenessThreshold and
     apmExceptionUnsuccessfulException."
  ::= { apmExceptionEntry 9 }



apmThroughputExceptionMinTime OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "seconds"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     "Because the responsiveness for throughput-oriented
     transactions is divided by the elapsed time, it can be very
     sensitive to short-term performance variations for
     transactions that take a short period of time. For example,
     when downloading
 a very short file, a single dropped packet
     could double or triple the total response time.

     Further, throughput is usually examined for applications that
     transfer a lot of data, and when doing so it is helpful to
     conceptualize transaction costs that are proportional to the
     amount of data separately from those costs that are relatively
     fixed (i.e., independent of the amount of data).  For very
     short transactions, these fixed transaction costs (handshake,
     setup time, authentication, round-trip time) may dominate the
     total response time for the transaction, resulting in
     throughput measurements that aren't really proportional to the
     network's, server's and client's combined data throughput
     capability.
```

```
      This object controls the minimum number of seconds that an
      throughput-based transaction must exceed before an exception
      can be generated for it. If this object is set
 to zero, then
      all throughput-based transactions are candidates for
      exceptions.

      The value of this object must persist across reboots."
  DEFVAL     { 10 }
  ::= { apmMibObjects 14 }

apmNotificationMaxRate OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
      "The maximum number of notifications that can be generated
      from this agent by the apmExceptionTable in any 60 second
      period.

      The value of this object must persist across reboots."
  DEFVAL { 1 }
  ::= { apmMibObjects 15 }




-- APM Notifications

apmNotifications OBJECT IDENTIFIER ::= { apm 0 }

apmTransactionResponsivenessAlarm NOTIFICATION-TYPE
  OBJECTS     { apmExceptionResponsivenessThreshold,
                apmTransactionResponsiveness }
  STATUS      current
  DESCRIPTION
      "Notification sent when a transaction exceeds a threshold
      defined in the apmException table. The index of the

      included apmExceptionResponsivenessThreshold object identifies
      the apmExceptionEntry that specified the threshold. The
      apmTransactionResponsiveness variable identifies the actual
      transaction and its responsiveness.

      Agent implementors are urged to include additional data
      objects in the alarm that may explain the reason for the
      alarm. It is helpful to include such data in the alarm because
      it describes the situation at the time the alarm was
```

```
      generated, where polls after the fact may not provide
      meaningful information. Examples of such information are CPU
      load, memory utilization, network utilization, and transaction
      statistics."
  ::= { apmNotifications 1 }

apmTransactionUnsuccessfulAlarm NOTIFICATION-TYPE
  OBJECTS     { apmExceptionResponsivenessThreshold }
  STATUS      current
  DESCRIPTION
      "Notification sent when a transaction is unsuccessful.
      The index of the included
 apmExceptionResponsivenessThreshold
      object identifies both the type of the transaction that caused
      this notification as well as the apmExceptionEntry that
      specified the threshold.

      Agent implementors are urged to include additional data
      objects in the alarm that may explain the reason for the
      alarm. It is helpful to include such data in the alarm because
      it describes the situation at the time the alarm was
      generated, where polls after the fact may not provide
      meaningful information. Examples of such information are CPU
      load, memory utilization, network utilization, and transaction
      statistics."
  ::= { apmNotifications 2 }

apmCompliance MODULE-COMPLIANCE
  STATUS  current



  DESCRIPTION
      "Describes the requirements for conformance to
      the APM MIB"
  MODULE  -- this module
      MANDATORY-GROUPS { apmAppDirGroup, apmReportGroup }

      GROUP apmUserDefinedApplicationsGroup
        DESCRIPTION
          "Implementation of the apmUserDefinedApplicationsGroup
          is optional."

      GROUP apmTransactionGroup
       DESCRIPTION
          "Implementation of the apmTransactionGroup is optional."

      GROUP apmExceptionGroup
```

```
        DESCRIPTION
            "Implementation of the apmExceptionGroup is optional."

        GROUP apmNotificationGroup
        DESCRIPTION
            "Implementation of the apmNotificationGroup is optional."

    ::= { apmCompliances 1 }

apmAppDirGroup OBJECT-GROUP
    OBJECTS { apmAppDirConfig,
              apmAppDirResponsivenessBoundary1,
              apmAppDirResponsivenessBoundary2,
              apmAppDirResponsivenessBoundary3,
              apmAppDirResponsivenessBoundary4,
              apmAppDirResponsivenessBoundary5,
              apmAppDirResponsivenessBoundary6,
              apmBucketBoundaryLastChange, apmAppDirID,
              apmNameMachineName, apmNameUserName }
    STATUS
   current
    DESCRIPTION
       "The APM MIB directory of applications and application verbs."
    ::=  { apmGroups 1 }

apmUserDefinedApplicationsGroup OBJECT-GROUP
    OBJECTS {     apmHttpFilterAppLocalIndex,
                  apmHttpFilterServerProtocol,
                  apmHttpFilterServerAddress, apmHttpFilterURLPath,
                  apmHttpFilterMatchType, apmHttpFilterOwner,
                  apmHttpFilterStorageType, apmHttpFilterRowStatus,
                  apmHttpIgnoreUnregisteredURLs, apmHttp4xxIsFailure,
                  apmUserDefinedAppParentIndex,




                  apmUserDefinedAppApplication }
    STATUS  current
    DESCRIPTION
       "Objects used for creating and managing user-defined
       applications."
    ::= { apmGroups 2 }

apmReportGroup OBJECT-GROUP
    OBJECTS { apmReportControlDataSource,
              apmReportControlAggregationType,
              apmReportControlInterval,
              apmReportControlRequestedSize,
```

```
            apmReportControlGrantedSize,
             apmReportControlRequestedReports,
            apmReportControlGrantedReports,
            apmReportControlStartTime,
            apmReportControlReportNumber,
            apmReportControlDeniedInserts,
            apmReportControlDroppedFrames,
            apmReportControlOwner,
            apmReportControlStorageType,
            apmReportControlStatus,
            apmReportTransactionCount,
            apmReportSuccessfulTransactions,
            apmReportResponsivenessMean,
            apmReportResponsivenessMin,
            apmReportResponsivenessMax,
            apmReportResponsivenessB1,
            apmReportResponsivenessB2,
            apmReportResponsivenessB3,
            apmReportResponsivenessB4,
            apmReportResponsivenessB5,
            apmReportResponsivenessB6,
            apmReportResponsivenessB7 }
    STATUS  current
    DESCRIPTION
        "The apm report group controls the creation
   and retrieval of
        reports that aggregate application performance."
    ::=  { apmGroups 3 }

apmTransactionGroup OBJECT-GROUP
    OBJECTS { apmTransactionResponsiveness,
            apmTransactionAge, apmTransactionSuccess,
            apmTransactionsRequestedHistorySize }
    STATUS  current
    DESCRIPTION
        "The apm transaction group contains statistics for
        individual transactions."



    ::=  { apmGroups 4 }

apmExceptionGroup OBJECT-GROUP
    OBJECTS { apmExceptionResponsivenessComparison,
            apmExceptionResponsivenessThreshold,
            apmExceptionUnsuccessfulException,
            apmExceptionResponsivenessEvents,
            apmExceptionUnsuccessfulEvents,
```

```
          apmExceptionOwner, apmExceptionStorageType,
          apmExceptionStatus, apmThroughputExceptionMinTime,
          apmNotificationMaxRate }
  STATUS  current
  DESCRIPTION
     "The apm exception group causes notifications to be sent
     whenever
 transactions are detected that had poor availability
     or responsiveness."
  ::=  { apmGroups 5 }

apmNotificationGroup NOTIFICATION-GROUP
  NOTIFICATIONS { apmTransactionResponsivenessAlarm,
                apmTransactionUnsuccessfulAlarm }
  STATUS       current
  DESCRIPTION
     "Notifications sent by an APM MIB agent."
  ::= { apmGroups 6 }

END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/APM-MIB
No license file was found, but licenses were detected in source scan.

```
DOCS-IF-MIB DEFINITIONS ::= BEGIN

 IMPORTS
   MODULE-IDENTITY,
   OBJECT-TYPE,
   Unsigned32,
   Integer32,
   Counter32,
   Counter64,
   TimeTicks,
   IpAddress,
   transmission
         FROM SNMPv2-SMI       -- [RFC2578]
   TEXTUAL-CONVENTION,
   MacAddress,
   RowStatus,
   TruthValue,
   TimeInterval,
   TimeStamp,
   StorageType
         FROM SNMPv2-TC        -- [RFC2579]
   OBJECT-GROUP,
```

```
    MODULE-COMPLIANCE
        FROM SNMPv2-CONF       -- [RFC2580]
    ifIndex, InterfaceIndexOrZero
        FROM IF-MIB            -- [RFC2863]
    InetAddressType,
    InetAddress
        FROM INET-ADDRESS-MIB  -- [RFC4001]
    IANAifType
        FROM IANAifType-MIB;   -- [IANA]

docsIfMib MODULE-IDENTITY
    LAST-UPDATED    "200605240000Z" -- May 24, 2006
    ORGANIZATION    "IETF IPCDN Working Group"
    CONTACT-INFO



          "       David Raftus
           Postal: ATI Technologies Inc.
                   340 Terry Fox Drive, Suite 202
                   Ottawa Ontario
                   Canada
          Phone:  +1 613 592 1052 ext.222
          E-mail: david.raftus@ati.com

                   Eduardo Cardona
          Postal: Cable Television Laboratories, Inc.
                   858 Coal Creek Circle
                   Louisville, CO 80027-9750
                   U.S.A.
          Phone:  Tel:    +1 303 661 9100
                   Fax:    +1 303 661 9199
          E-mail: e.cardona@cablelabs.com;mibs@cablelabs.com

          IETF IPCDN Working Group
          General Discussion: ipcdn@ietf.org
          Subscribe: http://www.ietf.org/mailman/listinfo/ipcdn
          Archive: ftp://ftp.ietf.org/ietf-mail-archive/ipcdn
          Co-chairs: Richard Woundy, Richard_Woundy@cable.comcast.com
                     Jean-Francois Mule, jf.mule@cablelabs.com"
    DESCRIPTION
        "This is the MIB Module for DOCSIS 2.0-compliant Radio

       Frequency (RF) interfaces in Cable Modems and
        Cable Modem Termination Systems.

        Copyright (C) The Internet Society (2006).  This
        version of this MIB module is part of RFC 4546; see
```

```
        the RFC itself for full legal notices."

    REVISION        "200605240000Z"
    DESCRIPTION
       "Revision of the IETF RF MIB module for DOCSIS 2.0.
        This version published as RFC 4546.
        This MIB module revision includes the following
        among others:
        Usage of ifType (205) for upstream logical channels.
        Addition of downstream and upstream utilization
        counters.
        Additional statistics per upstream interface.
        Upstream channel offline configuration mechanism.
        Added MIB support for new DOCSIS 2.0 modulation
        attributes.
        Euro-DOCSIS downstream interleave values.
        Adjustments to RFC 2670 definitions based on
        the MIB review guidelines from the IETF



         Operations and Management Area (OPS)."

    REVISION "199908190000Z"
    DESCRIPTION
       "Initial version, published as RFC 2670.
        Modified by Mike St. Johns to fix problems identified by
        the first pass of the MIB doctor.  Of special note,
        docsIfRangingResp and docsIfCmtsInsertionInterval were
        obsoleted and replaced by other objects with the same
        functionality, but with more appropriate syntax."
    ::= { transmission 127 }


-- Textual Conventions

TenthdBmV ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d-1"
    STATUS       current
    DESCRIPTION
       "This data type represents power levels that are normally
        expressed in dBmV.  Units are in tenths of a dBmV;
        for example, 5.1 dBmV will be represented as 51."
    SYNTAX       Integer32

TenthdB ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d-1"
    STATUS       current
```

```
    DESCRIPTION
        "This data type represents power levels that are
 normally
         expressed in dB.  Units are in tenths of a dB;
         for example, 5.1 dB will be represented as 51."
    SYNTAX       Integer32

DocsisVersion ::= TEXTUAL-CONVENTION
    STATUS         current
    DESCRIPTION
        "Indicates the DOCSIS Radio Frequency specification being
         referenced.
         'docsis10' indicates DOCSIS 1.0.
         'docsis11' indicates DOCSIS 1.1.
         'docsis20' indicates DOCSIS 2.0."
    SYNTAX       INTEGER {
         docsis10 (1),
         docsis11 (2),
         docsis20 (3)
    }

DocsisQosVersion ::= TEXTUAL-CONVENTION




    STATUS         current
    DESCRIPTION
        "Indicates the referenced quality-of-service
         level.
         'docsis10 refers to DOCSIS 1.0 Class of
         Service queuing services, and 'docsis11' refers
         to DOCSIS 1.1 Quality of Service."
    SYNTAX       INTEGER {
        docsis10 (1),
        docsis11 (2)
    }

DocsisUpstreamType ::= TEXTUAL-CONVENTION
    STATUS         current
    DESCRIPTION
        "Indicates the DOCSIS Upstream Channel Type.
         'unknown' means information not available.
         'tdma' is related to TDMA, Time Division
         Multiple Access; 'atdma' is related to A-TDMA,
         Advanced Time Division Multiple Access,
         'scdma' is related to S-CDMA, Synchronous
         Code Division Multiple Access.
         'tdmaAndAtdma is related to simultaneous support of
```

```
        TDMA and A-TDMA modes."
    SYNTAX          INTEGER {
        unknown(0),
        tdma(1),
        atdma(2),
        scdma(3),
        tdmaAndAtdma(4)
    }

DocsEqualizerData ::= TEXTUAL-CONVENTION
    STATUS       current
    DESCRIPTION
        "This data type represents the equalizer data
         as measured at the receiver interface.
         The format of the equalizer follows the structure of the
         Transmit Equalization Adjust RNG-RSP TLV of DOCSIS RFI
         v2.0 :
         1 byte Main tap location 1..(n + m)
          1 byte Number of forward taps per symbol
         1 byte Number of forward taps: n
         1 byte Number of reverse taps: m

         Following are the equalizer coefficients:
         First, forward taps coefficients:
         2 bytes F1 (real),  2 bytes  F1 (imag)



         ...
         2 bytes Fn (real),  2 bytes  Fn (imag)

         Then, reverse taps coefficients:
         2 bytes D1 (real),  2 bytes  D1 (imag)
         ...

         2 bytes Dm (real),  2 bytes  Dm (imag)

         The equalizer coefficients are considered signed 16-bit
         integers in the range from -32768 (0x8000) to 32767
         (0x7FFF).

         DOCSIS specifications require up to a maximum of
         64 equalizer taps (n + m); therefore, this object size
          can get up 260 bytes (4 + 4x64).
         The minimum object size (other than zero) for a t-spaced
         tap with a minimum of 8 symbols will be 36 (4 + 4x8)."
    REFERENCE
```

```
   "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Figure 8-23."
    SYNTAX       OCTET STRING(SIZE (0 | 36..260))


docsIfMibObjects  OBJECT IDENTIFIER ::= { docsIfMib 1 }
docsIfBaseObjects OBJECT IDENTIFIER ::= { docsIfMibObjects 1 }
docsIfCmObjects   OBJECT IDENTIFIER ::= { docsIfMibObjects 2 }
docsIfCmtsObjects OBJECT IDENTIFIER ::= { docsIfMibObjects 3 }

--
-- BASE GROUP
--

--
-- The following table is implemented on both the Cable Modem
-- and the Cable Modem Termination System.  This table is
-- read only for the CM.
--

docsIfDownstreamChannelTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF DocsIfDownstreamChannelEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "This table describes the attributes of downstream
       channels (frequency bands)."
   REFERENCE



       "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface
 Specification SP-RFIv2.0-I10-051209,
       Tables 6-16, and 6-17."
   ::= { docsIfBaseObjects 1 }

docsIfDownstreamChannelEntry OBJECT-TYPE
   SYNTAX      DocsIfDownstreamChannelEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "An entry provides a list of attributes for a single
       downstream channel.
       An entry in this table exists for each ifEntry with an
       ifType of docsCableDownstream(128)."
   INDEX { ifIndex }
```

```
    ::= { docsIfDownstreamChannelTable 1 }

DocsIfDownstreamChannelEntry ::= SEQUENCE {
        docsIfDownChannelId             Integer32,
        docsIfDownChannelFrequency      Integer32,
        docsIfDownChannelWidth          Integer32,
        docsIfDownChannelModulation     INTEGER,
        docsIfDownChannelInterleave     INTEGER,
        docsIfDownChannelPower          TenthdBmV,
        docsIfDownChannelAnnex          INTEGER,
        docsIfDownChannelStorageType
      StorageType
    }

docsIfDownChannelId OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The Cable Modem Termination System identification of the
        downstream channel within this particular MAC interface.
        if the interface is down, the object returns the most
        current value.  If the downstream channel ID is unknown,
        this object returns a value of 0."
    ::= { docsIfDownstreamChannelEntry 1 }

docsIfDownChannelFrequency OBJECT-TYPE
    SYNTAX      Integer32 (0..1000000000)
    UNITS       "hertz"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The center of the downstream frequency associated with
        this channel.  This object will return the current tuner




        frequency.  If a CMTS provides IF output, this object
        will return 0, unless this CMTS is in control of the
        final downstream frequency.  See
 the associated
        compliance object for a description of valid frequencies
        that may be written to this object."

    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.3.3."
```

```
    ::= { docsIfDownstreamChannelEntry 2 }

docsIfDownChannelWidth OBJECT-TYPE
    SYNTAX      Integer32 (0..16000000)
    UNITS       "hertz"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The bandwidth of this downstream channel.  Most
         implementations are expected to support a channel width
         of 6 MHz (North America) and/or 8 MHz (Europe).  See the
         associated compliance object for a description of the
         valid channel widths for this object."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Table 6-17."

 ::= { docsIfDownstreamChannelEntry 3 }

docsIfDownChannelModulation OBJECT-TYPE
    SYNTAX      INTEGER {
        unknown(1),
        other(2),
        qam64(3),
        qam256(4)
    }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The modulation type associated with this downstream
         channel.  If the interface is down, this object either
         returns the configured value (CMTS), the most current
         value (CM), or the value of unknown(1).  See the
         associated conformance object for write conditions and
         limitations.  See the reference for specifics on the
         modulation profiles implied by qam64 and qam256."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio




         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Table 6-17."
    ::= { docsIfDownstreamChannelEntry 4 }

docsIfDownChannelInterleave OBJECT-TYPE
    SYNTAX      INTEGER {
```

```
        unknown(1),
        other(2),
        taps8Increment16(3),
        taps16Increment8(4),
        taps32Increment4(5),
        taps64Increment2(6),
        taps128Increment1(7),
        taps12increment17(8)
    }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The Forward Error Correction (FEC) interleaving used
        for this downstream channel.
        Values are defined as follows:
        taps8Increment16(3):   protection 5.9/4.1 usec,
                               latency .22/.15 msec
        taps16Increment8(4):   protection 12/8.2 usec,
                               latency .48/.33 msec
        taps32Increment4(5):   protection 24/16 usec,
                               latency .98/.68 msec
        taps64Increment2(6):   protection 47/33 usec,
                               latency 2/1.4 msec
        taps128Increment1(7):  protection 95/66 usec,
                               latency 4/2.8 msec
        taps12increment17(8):
    protection 18/14 usec,
                               latency 0.43/0.32 msec

        The value 'taps12increment17' is supported by EuroDOCSIS
        cable systems only, and the others by DOCSIS cable systems.

        If the interface is down, this object either returns
        the configured value (CMTS), the most current value (CM),
        or the value of unknown(1).
        The value of other(2) is returned if the interleave
        is known but not defined in the above list.
        See the associated conformance object for write
        conditions and limitations.  See the reference for the FEC
        configuration described by the setting of this object."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,




        Table 6-15."
    ::= { docsIfDownstreamChannelEntry 5 }
```

```
docsIfDownChannelPower OBJECT-TYPE
   SYNTAX      TenthdBmV
   UNITS
  "dBmV"
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION
      "At the CMTS, the operational transmit power.  At the CM,
       the received power level.
       If the interface is down, this object either returns
       the configured value (CMTS), the most current value (CM)
       or the value of 0.  See the associated conformance object
       for write conditions and limitations.  See the reference
       for recommended and required power levels."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Tables 6-16, 6-17."
   ::= { docsIfDownstreamChannelEntry 6 }

docsIfDownChannelAnnex OBJECT-TYPE
   SYNTAX      INTEGER {
      unknown(1),
      other(2),
      annexA(3),
      annexB(4),
      annexC(5)
   }
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The value of this object indicates
 the conformance of
       the implementation to important regional cable standards.
       annexA : Annex A from ITU-T J.83 is used.
             (equivalent to EN 300 429)
       annexB : Annex B from ITU-T J.83 is used.
       annexC : Annex C from ITU-T J.83 is used."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Sections 6.3.1, and H.3.1."
   ::= { docsIfDownstreamChannelEntry 7 }

docsIfDownChannelStorageType OBJECT-TYPE
   SYNTAX      StorageType
   MAX-ACCESS   read-only
```

```
    STATUS       current
    DESCRIPTION
        "The storage type for this conceptual row.
         Entries with this object set to permanent(4)
         do not require write operations for read-write
         objects."
    ::= { docsIfDownstreamChannelEntry 8 }

--
-- The following table is implemented on both the CM and the CMTS.
-- For the CM, only attached channels
 appear in the table.  For the
-- CM, this table is read-only as well.
--

docsIfUpstreamChannelTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfUpstreamChannelEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table describes the attributes of attached upstream
         channels."
    ::= { docsIfBaseObjects 2 }

docsIfUpstreamChannelEntry OBJECT-TYPE
    SYNTAX      DocsIfUpstreamChannelEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "List of attributes for a single upstream channel.  For
         DOCSIS 2.0 CMTSs, an entry in this table exists for
         each ifEntry with an ifType of docsCableUpstreamChannel
         (205).
         For DOCSIS 1.x CM/CMTSs and DOCSIS 2.0 CMs, an entry in
         this table exists for each ifEntry with an ifType of
         docsCableUpstream (129).

         For DOCSIS 2.0 CMTSs, two classes of interfaces can be
         defined for this table:
           o Upstream Physical Interfaces: The traditional DOCSIS
             1.x CMTS upstream interface ifType 129 and the DOCSIS
             2.0 ifType 205 that are functional.  In other words,
             interfaces that represent upstream receivers within
             an RF MAC interface.
             Entries of physical interfaces are exposed to the
```

management interface with their corresponding
ifStack hierarchy and are not administratively
created by this table.

o Upstream Temporary Interfaces: A fictitious
interface created for the purpose of manipulating
physical interface parameters offline, then
validating prior to updating the target physical
interface.

In case of a reinitialization of the managed system,
physical interfaces values persist while the temporary
interfaces are not recreated.

This mechanism helps to minimize
service disruptions
originating in situations where a group of interface
parameter values need to be consistent with each other
in SET operations. A temporary buffer
(temporary interface) is provided to allow the CMTS
to validate the parameters offline."
INDEX { ifIndex }
::= { docsIfUpstreamChannelTable 1 }

```
DocsIfUpstreamChannelEntry ::= SEQUENCE {
    docsIfUpChannelId                   Integer32,
    docsIfUpChannelFrequency            Integer32,
    docsIfUpChannelWidth                Integer32,
    docsIfUpChannelModulationProfile    Unsigned32,
    docsIfUpChannelSlotSize             Unsigned32,
    docsIfUpChannelTxTimingOffset       Unsigned32,
    docsIfUpChannelRangingBackoffStart  Integer32,
    docsIfUpChannelRangingBackoffEnd    Integer32,
    docsIfUpChannelTxBackoffStart       Integer32,
    docsIfUpChannelTxBackoffEnd         Integer32,

    docsIfUpChannelScdmaActiveCodes     Unsigned32,
    docsIfUpChannelScdmaCodesPerSlot    Integer32,
    docsIfUpChannelScdmaFrameSize       Unsigned32,
    docsIfUpChannelScdmaHoppingSeed     Unsigned32,
    docsIfUpChannelType                 DocsisUpstreamType,
    docsIfUpChannelCloneFrom            InterfaceIndexOrZero,
    docsIfUpChannelUpdate               TruthValue,
    docsIfUpChannelStatus               RowStatus,
    docsIfUpChannelPreEqEnable          TruthValue
```

```
    }

docsIfUpChannelId OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The CMTS identification of the upstream channel."
    ::= { docsIfUpstreamChannelEntry 1 }



docsIfUpChannelFrequency OBJECT-TYPE
    SYNTAX      Integer32 (0..1000000000)
    UNITS       "hertz"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The center of the frequency
 band associated with this
         upstream interface.  This object returns 0 if the frequency
         is undefined or unknown.  Minimum permitted upstream
         frequency is 5,000,000 Hz for current technology.  See
         the associated conformance object for write conditions
         and limitations."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Table 4-2."
    ::= { docsIfUpstreamChannelEntry 2 }

docsIfUpChannelWidth OBJECT-TYPE
    SYNTAX      Integer32 (0..64000000)
    UNITS       "hertz"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The bandwidth of this upstream interface.  This object
         returns 0 if the interface width is undefined or unknown.
         Minimum permitted interface width is currently 200,000 Hz.
         See the associated conformance object for write conditions
         and limitations."
     REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Table 6-5."
    ::= { docsIfUpstreamChannelEntry 3 }
```

```
docsIfUpChannelModulationProfile OBJECT-TYPE
   SYNTAX      Unsigned32
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "An entry identical to the docsIfModIndex in the
       docsIfCmtsModulationTable that describes this channel.
       This channel is further instantiated there by a grouping
       of interval usage codes (IUCs) that, together, fully
       describe the channel modulation.  This object returns 0 if
       the docsIfCmtsModulationTable entry does not exist or is
       empty.  See the associated conformance object for write
       conditions and limitations.



       Setting this object returns an 'inconsistentValue'
       error if the following conditions are not satisfied:
       1. All the
 IUC entries in the selected modulation profile
       MUST have the same value of docsIfCmtsModChannelType.
       2. All of the Modulation parameters in the selected
       modulation profile MUST be consistent with the other
       parameters in this docsIfUpstreamChannelEntry."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Table 8-19."
   ::= { docsIfUpstreamChannelEntry 4 }

docsIfUpChannelSlotSize OBJECT-TYPE
   SYNTAX      Unsigned32
   UNITS       "ticks"
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "Applicable to TDMA and ATDMA channel types only.
       The number of 6.25 microsecond ticks in each upstream
       mini-slot.  Returns zero if the value is undefined or
       unknown or in case of an SCDMA channel.
       See the associated conformance object for write
       conditions and limitations."
    REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Section 8.1.2.4."
   ::= { docsIfUpstreamChannelEntry 5 }
```

```
docsIfUpChannelTxTimingOffset OBJECT-TYPE
   SYNTAX      Unsigned32
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "At the CM, a measure of the current round trip time
       obtained from the ranging offset (initial ranging offset +
       ranging offset adjustments).
       At the CMTS, the maximum of timing offset, among all the
       CMs that are/were present on the channel, taking into
       account all ( initial + periodic ) timing offset
       corrections that were sent for each of the CMs.  Generally,
       these measurements are positive, but if the measurements
       are negative, the value of this object is zero.  Used for
       timing of CM upstream transmissions to ensure synchronized

      arrivals at the CMTS.
       Units are one 64th fraction of 6.25 microseconds."



   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Section 6.2.19."
   ::= { docsIfUpstreamChannelEntry 6 }

docsIfUpChannelRangingBackoffStart OBJECT-TYPE
   SYNTAX      Integer32 (0..16)
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "The initial random backoff window to use when retrying
       Ranging Requests.  Expressed as a power of 2.  A value of
       16 at the CMTS indicates that a proprietary adaptive retry
       mechanism is to be used.  See the associated conformance
       object for write conditions and limitations."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Sections 8.3.4, and 9.4."
   ::= { docsIfUpstreamChannelEntry
 7 }

docsIfUpChannelRangingBackoffEnd OBJECT-TYPE
   SYNTAX      Integer32 (0..16)
   MAX-ACCESS  read-create
   STATUS      current
```

```
    DESCRIPTION
        "The final random backoff window to use when retrying
        Ranging Requests.  Expressed as a power of 2.  A value of
        16 at the CMTS indicates that a proprietary adaptive retry
        mechanism is to be used.  See the associated conformance
        object for write conditions and limitations."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 8.3.4, and 9.4."
    ::= { docsIfUpstreamChannelEntry 8 }

docsIfUpChannelTxBackoffStart OBJECT-TYPE
    SYNTAX      Integer32 (0..16)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The initial random backoff window to use when retrying
        transmissions.  Expressed as a power of 2.  A value of 16

       at the CMTS indicates that a proprietary adaptive retry
        mechanism is to be used.  See the associated conformance
        object for write conditions and limitations."



    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 8.3.4, and 9.4."
    ::= { docsIfUpstreamChannelEntry 9 }

docsIfUpChannelTxBackoffEnd OBJECT-TYPE
    SYNTAX      Integer32 (0..16)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The final random backoff window to use when retrying
        transmissions.  Expressed as a power of 2.  A value of 16
        at the CMTS indicates that a proprietary adaptive retry
        mechanism is to be used.  See the associated conformance
        object for write conditions and limitations."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification
  SP-RFIv2.0-I10-051209,
        Section 8.3.4, and 9.4."
    ::= { docsIfUpstreamChannelEntry 10 }
```

```
docsIfUpChannelScdmaActiveCodes OBJECT-TYPE
   SYNTAX     Unsigned32 (0|64..66|68..70|72|74..78|80..82|84..88
                        |90..96|98..100|102|104..106|108
                        |110..112|114..126|128)
   MAX-ACCESS read-create
   STATUS     current
   DESCRIPTION
      "Applicable for SCDMA channel types only.
       Number of active codes.  Returns zero for
       Non-SCDMA channel types.  Note that legal
       values from 64..128 MUST be non-prime."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Section 6.2.11.2.1."
   ::= { docsIfUpstreamChannelEntry 11 }

docsIfUpChannelScdmaCodesPerSlot OBJECT-TYPE
   SYNTAX      Integer32(0 | 2..32)
   UNITS       "codesperMinislots"
   MAX-ACCESS  read-create
   STATUS      current
    DESCRIPTION
      "Applicable for SCDMA channel types only.
       The number of SCDMA codes per mini-slot.
       Returns zero if the value is undefined or unknown or in




       case of a TDMA or ATDMA channel."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Section 6.2.11.2.1."
   ::= { docsIfUpstreamChannelEntry 12 }

docsIfUpChannelScdmaFrameSize OBJECT-TYPE
   SYNTAX      Unsigned32 (0..32)
   UNITS       "spreadIntervals"
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "Applicable for SCDMA channel types only.
       SCDMA Frame size in units of spreading intervals.
       This value returns zero for non-SCDMA Profiles."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
```

```
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.12."
    ::= {
 docsIfUpstreamChannelEntry 13 }

docsIfUpChannelScdmaHoppingSeed OBJECT-TYPE
    SYNTAX     Unsigned32 (0..32767)
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
        "Applicable for SCDMA channel types only.
        15-bit seed used for code hopping sequence initialization.
        Returns zero for non-SCDMA channel types.
        Setting this value to a value different than zero for
        non-SCDMA channel types returns the error 'wrongValue'."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.14.1."
    ::= { docsIfUpstreamChannelEntry 14 }

docsIfUpChannelType OBJECT-TYPE
    SYNTAX      DocsisUpstreamType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Reflects the Upstream channel type.
        This object returns the value of docsIfCmtsModChannelType
        for the modulation profile selected
 in
        docsIfUpChannelModulationProfile for this row."
    REFERENCE




        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.1."
    ::= { docsIfUpstreamChannelEntry 15 }

docsIfUpChannelCloneFrom OBJECT-TYPE
    SYNTAX      InterfaceIndexOrZero
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This object contains the ifIndex value of the physical
        interface row entry whose parameters are to be adjusted.
```

Upon setting this object to the ifIndex value of a
physical interface, the following interface objects values
are copied to this entry:
docsIfUpChannelFrequency,
docsIfUpChannelWidth,
docsIfUpChannelModulationProfile,
docsIfUpChannelSlotSize,
docsIfUpChannelRangingBackoffStart,
docsIfUpChannelRangingBackoffEnd,
docsIfUpChannelTxBackoffStart,
docsIfUpChannelTxBackoffEnd,
docsIfUpChannelScdmaActiveCodes,
docsIfUpChannelScdmaCodesPerSlot,
docsIfUpChannelScdmaFrameSize,
docsIfUpChannelScdmaHoppingSeed,
docsIfUpChannelType, and
docsIfUpChannelPreEqEnable
Setting this object to the value of a non-existent or
a temporary upstream interface returns the error
'wrongValue'.
This object MUST contain a value of zero for physical
interfaces entries.
Setting this object in row entries that correspond to
physical interfaces returns the error 'wrongValue'."
::= { docsIfUpstreamChannelEntry 16 }

docsIfUpChannelUpdate OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"Used to perform the copy of adjusted parameters from the
temporary interface entry to the physical interface
indicated by the docsIfUpChannelCloneFrom
object. The
transfer is initiated through an SNMP SET to 'true' of

this object.
A SET to 'true' fails and returns error 'commitFailed'
if docsIfUpChannelStatus value is 'notInService', which
means that the interface parameters values are not
compatible with each other or have not been validated yet.
Reading this object always returns 'false'."
::= { docsIfUpstreamChannelEntry 17 }

docsIfUpChannelStatus OBJECT-TYPE

SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This object is only used for the creation of a temporary upstream row with the purpose of updating the parameters of a physical upstream channel entry.

The following restrictions apply to this object:
1. This object is not writable for physical interfaces.
2. Temporary interface entries are only created by a SET

of this object to createandWait(5).
3. ifAdminStatus from the Interface MIB RFC 2863 is used to take a physical upstream channel offline, to be consistent with DOCSIS 1.x operation, as indicated in RFC 2670.
In addition,
o ifAdminStatus 'down' is reflected in this object as 'notInService'.
o ifOperStatus 'down' while ifAdminStatus 'up' is reflected in this object as 'notInservice'.
4. Temporary created rows MUST be set to 'active' with the purpose of validating upstream parameter consistency prior to transferring the parameters to the physical interface.

Below is a mandatory procedure for adjusting the values of a physical interface:
1. Create a temporary interface entry through an SNMP SET using 'createAndWait'. At this point, the RowStatus reports 'notReady'.
The Manager entity uses an ifIndex value outside the operational range of the physical interfaces for the creation of a temporary interface.
2. Set the docsIfUpChannelCloneFrom object to the ifIndex value of the physical row to update. Now docsIfUpChannelStatus reports 'notInService'.
3. Change the upstream parameters to the desired values in the temporary row.

4. Validate that all parameters are consistent by setting docsIfUpChannelStatus to 'active'. A failure to set the RowStatus to 'active' returns the error 'commitFailed', which means the parameters are not compatible with the target physical interface.

```
        5. With docsIfUpChannelStatus 'active', transfer the
           parameters to the target physical interface by setting
           the object docsIfUpChannelUpdate to 'true'.
        6. Delete the temporary
 row by setting
           docsIfUpChannelStatus to 'destroy'."
    ::= { docsIfUpstreamChannelEntry 18 }

docsIfUpChannelPreEqEnable OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "At the CMTS, this object is used to enable or disable
        pre-equalization on the upstream channel represented by
        this table instance.  At the CM, this object is read-only
        and reflects the status of pre-equalization as represented
        in the RNG-RSP.  Pre-equalization is considered enabled at
        the CM if a RNG-RSP with pre-equalization data has been
        received at least once since the last mac
        reinitialization."
    DEFVAL {false}
    ::= { docsIfUpstreamChannelEntry 19 }

-- The following table describes the attributes of each class of
-- service.  The entries in this table are referenced from the
-- docsIfServiceEntries.  They exist as a separate table in order to
--
 reduce redundant information in docsIfServiceTable.
--
-- This table is implemented at both the CM and the CMTS.
-- The CM need only maintain entries for the classes of service
-- referenced by its docsIfCmServiceTable.
--

docsIfQosProfileTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfQosProfileEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Describes the attributes for each class of service."
    ::= { docsIfBaseObjects 3 }

docsIfQosProfileEntry OBJECT-TYPE
    SYNTAX      DocsIfQosProfileEntry
```

```
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Describes the attributes for a single class of service.
        If implemented as read-create in the Cable Modem
        Termination System, creation of entries in this table is
        controlled by the value of
        docsIfCmtsQosProfilePermissions.

        If implemented as read-only, entries are created based
        on information in REG-REQ
  MAC messages received from
        cable modems (for Cable Modem Termination System), or
        based on information extracted from the TFTP option file
        (for Cable Modem).
        In the Cable Modem Termination System, read-only entries
        are removed if no longer referenced by
        docsIfCmtsServiceTable.

        An entry in this table MUST not be removed while it is
        referenced by an entry in docsIfCmServiceTable (Cable
        Modem) or docsIfCmtsServiceTable (Cable Modem Termination
        System).

        An entry in this table SHOULD NOT be changeable while
        it is referenced by an entry in docsIfCmtsServiceTable.

        If this table is created automatically, there SHOULD only
        be a single entry for each Class of Service.  Multiple
        entries with the same Class of Service parameters are NOT
        RECOMMENDED."
    INDEX { docsIfQosProfIndex }
    ::= { docsIfQosProfileTable 1 }

DocsIfQosProfileEntry
  ::= SEQUENCE {
        docsIfQosProfIndex              Integer32,
        docsIfQosProfPriority           Integer32,
        docsIfQosProfMaxUpBandwidth     Integer32,
        docsIfQosProfGuarUpBandwidth    Integer32,
        docsIfQosProfMaxDownBandwidth   Integer32,
        docsIfQosProfMaxTxBurst         Integer32,  -- deprecated
        docsIfQosProfBaselinePrivacy    TruthValue,
        docsIfQosProfStatus             RowStatus,
        docsIfQosProfMaxTransmitBurst   Integer32,
        docsIfQosProfStorageType        StorageType
    }
```

```
docsIfQosProfIndex OBJECT-TYPE
   SYNTAX      Integer32 (1..16383)



   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "The index value that uniquely identifies an entry
       in the docsIfQosProfileTable."
   ::= { docsIfQosProfileEntry 1 }

docsIfQosProfPriority OBJECT-TYPE
   SYNTAX      Integer32 (0..7)
   MAX-ACCESS  read-create
   STATUS      current

  DESCRIPTION
      "A relative priority assigned to this service when
       allocating bandwidth.  Zero indicates lowest priority
       and seven indicates highest priority.
       Interpretation of priority is device-specific.
       MUST NOT be changed while this row is active."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Annex C.1.1.4."
   DEFVAL { 0 }
   ::= { docsIfQosProfileEntry 2 }

docsIfQosProfMaxUpBandwidth OBJECT-TYPE
   SYNTAX      Integer32 (0..100000000)
   UNITS "bits per second"
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "The maximum upstream bandwidth, in bits per second,
       allowed for a service with this service class.
       Zero if there is no restriction of upstream bandwidth.
       MUST NOT be changed while this row is active."
   REFERENCE
      "Data-Over-Cable Service
 Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Annex C.1.1.4."
   DEFVAL { 0 }
   ::= { docsIfQosProfileEntry 3 }
```

```
docsIfQosProfGuarUpBandwidth OBJECT-TYPE
   SYNTAX      Integer32 (0..100000000)
   UNITS "bits per second"
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "Minimum guaranteed upstream bandwidth, in bits per second,




       allowed for a service with this service class.
       MUST NOT be changed while this row is active."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Annex C.1.1.4."
   DEFVAL { 0 }
   ::= { docsIfQosProfileEntry 4 }

docsIfQosProfMaxDownBandwidth OBJECT-TYPE
   SYNTAX      Integer32 (0..100000000)
   UNITS "bits per second"
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "The maximum downstream bandwidth,
 in bits per second,
       allowed for a service with this service class.
       Zero if there is no restriction of downstream bandwidth.
       MUST NOT be changed while this row is active."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Annex C.1.1.4."

   DEFVAL { 0 }
   ::= { docsIfQosProfileEntry 5 }

docsIfQosProfMaxTxBurst OBJECT-TYPE
   SYNTAX      Integer32 (0..255)
   UNITS "mini-slots"
   MAX-ACCESS  read-create
   STATUS      deprecated
   DESCRIPTION
      "The maximum number of mini-slots that may be requested
       for a single upstream transmission.
       A value of zero means there is no limit.
       MUST NOT be changed while this row is active.
```

```
        This object has been deprecated and replaced by
        docsIfQosProfMaxTransmitBurst, to fix a mismatch
        of the units and value range with respect to
 the DOCSIS
        Maximum Upstream Channel Transmit Burst Configuration
        Setting."
    REFERENCE
       "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        C.1.1.4."
    DEFVAL { 0 }
    ::= { docsIfQosProfileEntry 6 }



docsIfQosProfBaselinePrivacy OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
       "Indicates whether Baseline Privacy is enabled for this
        service class.
        MUST NOT be changed while this row is active."
    DEFVAL { false }
    ::= { docsIfQosProfileEntry 7 }

docsIfQosProfStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
       "This is object is used to create or delete rows in
        this table.  This object MUST NOT be changed from active
        while the row is referenced by any entry in either
        docsIfCmServiceTable
 (on the CM) or
        docsIfCmtsServiceTable (on the CMTS)."
    ::= { docsIfQosProfileEntry 8 }

docsIfQosProfMaxTransmitBurst OBJECT-TYPE
    SYNTAX      Integer32 (0..65535)
    UNITS       "bytes"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
       "The maximum number of bytes that may be requested for a
        single upstream transmission.  A value of zero means there
        is no limit.  Note: This value does not include any
```

```
        physical layer overhead.
        MUST NOT be changed while this row is active."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Annex C.1.1.4."
    DEFVAL { 0 }
    ::= { docsIfQosProfileEntry 9 }

docsIfQosProfStorageType OBJECT-TYPE
    SYNTAX       StorageType
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The storage type for this conceptual
 row.
        Entries with this object set to permanent(4)



        do not require write operations for writable
        objects."
    ::= { docsIfQosProfileEntry 10 }

docsIfSignalQualityTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfSignalQualityEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "At the CM, describes the PHY signal quality of downstream
        channels.  At the CMTS, this object describes the PHY
        signal quality of upstream channels.  At the CMTS, this
        table MAY exclude contention intervals."
    ::= { docsIfBaseObjects 4 }

docsIfSignalQualityEntry OBJECT-TYPE
    SYNTAX      DocsIfSignalQualityEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "At the CM, this object describes the PHY characteristics of
        a downstream channel.  At the CMTS, it describes the PHY
        signal quality of an upstream channel.
        An entry in this table exists
 for each ifEntry with an
        ifType of docsCableDownstream(128) for Cable Modems.
        For DOCSIS 1.1 Cable Modem Termination Systems, an entry
        exists for each ifEntry with an ifType of
```

```
        docsCableUpstream (129).
        For DOCSIS 2.0 Cable Modem Termination Systems, an entry
        exists for each ifEntry with an ifType of
        docsCableUpstreamChannel (205)."
    INDEX { ifIndex }
    ::= { docsIfSignalQualityTable 1 }

DocsIfSignalQualityEntry ::= SEQUENCE {
        docsIfSigQIncludesContention  TruthValue,
        docsIfSigQUnerroreds          Counter32,
        docsIfSigQCorrecteds          Counter32,
        docsIfSigQUncorrectables      Counter32,
        docsIfSigQSignalNoise         TenthdB,
        docsIfSigQMicroreflections    Integer32,
        docsIfSigQEqualizationData    DocsEqualizerData,
        docsIfSigQExtUnerroreds       Counter64,
        docsIfSigQExtCorrecteds       Counter64,
        docsIfSigQExtUncorrectables
   Counter64
    }

docsIfSigQIncludesContention OBJECT-TYPE



    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "true(1) if this CMTS includes contention intervals in
        the counters in this table.  Always false(2) for CMs."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.4.1"
    ::= { docsIfSignalQualityEntry 1 }

docsIfSigQUnerroreds OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "codewords"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Codewords received on this channel without error.
        This includes all codewords, whether or not they
        were part of frames destined for this device.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
```

```
        times as indicated
 by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
       "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Sections 6.2.4, and 6.3.6."
    ::= { docsIfSignalQualityEntry 2 }

docsIfSigQCorrecteds OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "codewords"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       "Codewords received on this channel with correctable
        errors.  This includes all codewords, whether or not
        they were part of frames destined for this device.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
       "Data-Over-Cable Service Interface Specifications: Radio
        Frequency
 Interface Specification SP-RFIv2.0-I10-051209,
        Sections 6.2.4, and 6.3.6."



    ::= { docsIfSignalQualityEntry 3 }

docsIfSigQUncorrectables OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "codewords"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       "Codewords received on this channel with uncorrectable
        errors.  This includes all codewords, whether or not
        they were part of frames destined for this device.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
       "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
```

```
        Sections 6.2.4, and 6.3.6."
    ::= { docsIfSignalQualityEntry 4 }

docsIfSigQSignalNoise OBJECT-TYPE
    SYNTAX      TenthdB
    UNITS       "TenthdB"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Signal/Noise ratio as perceived for this channel.
        At the CM, this object  describes the Signal/Noise of the
        downstream channel.  At the CMTS, it describes the
        average Signal/Noise of the upstream channel."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Tables 4-1 and 4-2"
    ::= { docsIfSignalQualityEntry 5 }

docsIfSigQMicroreflections OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    UNITS       "-dBc"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Microreflections, including in-channel response
        as perceived on this interface, measured in dBc below
        the signal level.
        This object is not assumed to return an absolutely
        accurate value, but it gives a rough indication




        of microreflections received on this interface.
        It is up to the implementer to provide information
        as accurately as possible."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Tables 4-1 and 4-2"
    ::= { docsIfSignalQualityEntry 6 }

docsIfSigQEqualizationData OBJECT-TYPE
      SYNTAX      DocsEqualizerData
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
          "At the CM, this object returns the equalization data for
```

the downstream channel.

At the CMTS, this object is not applicable and is not instantiated. Note that previous CMTS implementations may instantiate this object in two ways:
- An equalization value indicating an equalization average for the upstream channel. Those values have vendor-dependent
interpretations.
- Return a zero-length OCTET STRING to indicate that the value is unknown or if there is no equalization data available or defined."
REFERENCE
"DOCSIS Radio Frequency Interface Specification, Figure 6-23."
::= { docsIfSignalQualityEntry 7 }

docsIfSigQExtUnerroreds OBJECT-TYPE
SYNTAX Counter64
UNITS "codewords"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Codewords received on this channel without error. This includes all codewords, whether or not they were part of frames destined for this device. This is the 64-bit version of docsIfSigQUnerroreds. Discontinuities in the value of this counter can occur at reinitialization of the managed system, and at other times as indicated by the value of ifCounterDiscontinuityTime for the associated ifIndex."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio Frequency Interface Specification SP-RFIv2.0-I10-051209, Sections 6.2.4, and 6.3.6."
::= { docsIfSignalQualityEntry 8 }

docsIfSigQExtCorrecteds OBJECT-TYPE
SYNTAX Counter64
UNITS "codewords"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Codewords received on this channel with correctable

```
        errors.  This includes all codewords, whether or not
        they were part of frames destined for this device.
        This is the 64-bit version of docsIfSigQCorrecteds.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Sections 6.2.4, and 6.3.6."
    ::= { docsIfSignalQualityEntry 9 }

docsIfSigQExtUncorrectables OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "codewords"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Codewords received on this channel with uncorrectable
        errors.  This includes all codewords, whether or not
        they were part of frames destined for this device.
        This is the 64-bit version of docsIfSigQUncorrectables.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Sections 6.2.4, 6.3.6."
    ::= { docsIfSignalQualityEntry 10 }

--
-- DOCSIS Version of
 the device
--



docsIfDocsisBaseCapability OBJECT-TYPE
      SYNTAX      DocsisVersion
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
          "Indication of the DOCSIS capability of the device."
      REFERENCE
```

```
          "Data-Over-Cable Service Interface Specifications: Radio
           Frequency Interface Specification SP-RFIv2.0-I10-051209,
           Annex G."
      ::= { docsIfBaseObjects 5 }

--
-- CABLE MODEM GROUP
--

--
-- The CM MAC Table
--

docsIfCmMacTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF DocsIfCmMacEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "Describes the attributes of each CM MAC interface,
       extending the information available from ifEntry."
   ::= { docsIfCmObjects 1 }

docsIfCmMacEntry OBJECT-TYPE
   SYNTAX      DocsIfCmMacEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "An entry containing objects describing attributes
 of
       each MAC entry, extending the information in ifEntry.
       An entry in this table exists for each ifEntry with an
       ifType of docsCableMaclayer(127)."
   INDEX { ifIndex }
   ::= { docsIfCmMacTable 1 }

DocsIfCmMacEntry ::= SEQUENCE {
       docsIfCmCmtsAddress          MacAddress,
       docsIfCmCapabilities         BITS,
       docsIfCmRangingRespTimeout   TimeTicks,
       docsIfCmRangingTimeout       TimeInterval
    }




docsIfCmCmtsAddress OBJECT-TYPE
   SYNTAX      MacAddress
   MAX-ACCESS  read-only
```

```
    STATUS      current
    DESCRIPTION
        "Identifies the CMTS that is believed to control this MAC
         domain.  At the CM, this will be the source address from
         SYNC, MAP, and other MAC-layer messages.  If the CMTS is
         unknown, returns 00-00-00-00-00-00."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
          Section 8.2.2."
    ::= { docsIfCmMacEntry 1 }

docsIfCmCapabilities OBJECT-TYPE
    SYNTAX      BITS {
        atmCells(0),
        concatenation(1)
    }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Identifies the capabilities of the MAC implementation
         at this interface.  Note that packet transmission is
         always supported.  Therefore, there is no specific bit
         required to explicitly indicate this capability.
         Note that BITS objects are encoded most significant bit
         first.  For example, if bit 1 is set, the value of this
         object is the octet string '40'H."
    ::= { docsIfCmMacEntry 2 }

docsIfCmRangingRespTimeout OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-write
    STATUS      obsolete
    DESCRIPTION
        "Waiting time for a Ranging Response packet.
         This object has been obsoleted and replaced by
         docsIfCmRangingTimeout to correct
 the typing to
         TimeInterval."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Section 9.1.6."
    DEFVAL { 20 }
    ::= { docsIfCmMacEntry 3 }
```

```
docsIfCmRangingTimeout OBJECT-TYPE
   SYNTAX      TimeInterval
   UNITS       "HundredOfSeconds"
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION
      "Waiting time for a Ranging Response packet.
       This object MUST NOT persist at reinitialization
       of the managed system."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Section 9.1.6, timer T3."
   DEFVAL { 20 }
   ::= { docsIfCmMacEntry 4 }

--
-- CM status table.
-- This table is implemented only at the CM.
--

docsIfCmStatusTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF DocsIfCmStatusEntry
   MAX-ACCESS  not-accessible
    STATUS      current
   DESCRIPTION
      "This table maintains a number of status objects
       and counters for Cable Modems."
   ::= { docsIfCmObjects 2 }

docsIfCmStatusEntry OBJECT-TYPE
   SYNTAX      DocsIfCmStatusEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "A set of status objects and counters for a single MAC
       layer instance in Cable Modem.
       An entry in this table exists for each ifEntry with an
       ifType of docsCableMaclayer(127)."
   INDEX { ifIndex }
   ::= { docsIfCmStatusTable 1 }

DocsIfCmStatusEntry ::= SEQUENCE {
      docsIfCmStatusValue          INTEGER,
      docsIfCmStatusCode           OCTET STRING,
      docsIfCmStatusTxPower          TenthdBmV,
      docsIfCmStatusResets         Counter32,
```

```
      docsIfCmStatusLostSyncs          Counter32,



      docsIfCmStatusInvalidMaps        Counter32,
      docsIfCmStatusInvalidUcds
    Counter32,
      docsIfCmStatusInvalidRangingResponses   Counter32,
      docsIfCmStatusInvalidRegistrationResponses Counter32,
      docsIfCmStatusT1Timeouts         Counter32,
      docsIfCmStatusT2Timeouts         Counter32,
      docsIfCmStatusT3Timeouts         Counter32,
      docsIfCmStatusT4Timeouts         Counter32,
      docsIfCmStatusRangingAborteds    Counter32,
      docsIfCmStatusDocsisOperMode     DocsisQosVersion,
      docsIfCmStatusModulationType     DocsisUpstreamType,
      docsIfCmStatusEqualizationData   DocsEqualizerData,
      docsIfCmStatusUCCs               Counter32,
      docsIfCmStatusUCCFails           Counter32
    }

docsIfCmStatusValue OBJECT-TYPE
    SYNTAX     INTEGER {
      other(1),
      notReady(2),
      notSynchronized(3),
      phySynchronized(4),
      usParametersAcquired(5),
      rangingComplete(6),
      ipComplete(7),
      todEstablished(8),
      securityEstablished(9),
       paramTransferComplete(10),
      registrationComplete(11),
      operational(12),
      accessDenied(13)
    }
    MAX-ACCESS  read-only
    STATUS     current
    DESCRIPTION
      "Current Cable Modem connectivity state, as specified
       in the RF Interface Specification.  Interpretations for
       state values 1-12 are clearly outlined in the SP-RFI
       reference given below.
       The state value accessDenied(13) indicates the CMTS has
       sent a Registration Aborted message to the CM.  The same
       state is reported as accessDenied(7) by the CMTS object
       docsIfCmtsCmStatusValue."
```

```
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 11.2.
        Data-Over-Cable Service Interface Specifications:



        Operations Support System Interface Specification
        SP-OSSIv2.0-I09-050812,
 Section 6.3.4.2."
    ::= { docsIfCmStatusEntry 1 }

docsIfCmStatusCode OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE( 0 | 5 | 6 ))
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Status code for a Cable Modem as defined in the
        OSSI Specification.  The status code consists
        of a single character indicating error groups, followed
        by a two- or three-digit number indicating the status
        condition, followed by a decimal.
        An example of a returned value could be 'T101.0'.
        The zero-length OCTET STRING indicates no status code yet
        registered."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications:
        Operations Support System Interface Specification
        SP-OSSIv2.0-I09-050812, Annex D."
    ::= { docsIfCmStatusEntry 2 }


docsIfCmStatusTxPower OBJECT-TYPE
    SYNTAX      TenthdBmV
    UNITS       "TenthdBmV"
    MAX-ACCESS  read-only
    STATUS      current
     DESCRIPTION
        "The operational transmit power for the attached upstream
        channel."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.18."
    ::= { docsIfCmStatusEntry 3 }

docsIfCmStatusResets OBJECT-TYPE
```

```
    SYNTAX      Counter32
    UNITS       "resets"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of times the CM reset or initialized this
        interface.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmStatusEntry 4 }

docsIfCmStatusLostSyncs OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of times the CM
 lost synchronization with
        the downstream channel.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 8.3.2."
    ::= { docsIfCmStatusEntry 5 }

docsIfCmStatusInvalidMaps OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "maps"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of times the CM received invalid MAP messages.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
```

```
 "Data-Over-Cable Service Interface Specifications: Radio
      Frequency Interface Specification SP-RFIv2.0-I10-051209,
      Section 8.3.4."
   ::= { docsIfCmStatusEntry 6 }

docsIfCmStatusInvalidUcds OBJECT-TYPE
   SYNTAX      Counter32
   UNITS       "messages"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "Number of times the CM received invalid UCD messages.
      Discontinuities in the value of this counter can occur
      at reinitialization of the managed system, and at other
      times as indicated by the value of




      ifCounterDiscontinuityTime for the associated ifIndex."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
      Frequency Interface Specification SP-RFIv2.0-I10-051209,
      Section 8.3.3."
   ::= { docsIfCmStatusEntry 7 }

docsIfCmStatusInvalidRangingResponses OBJECT-TYPE
   SYNTAX      Counter32
   UNITS       "messages"
   MAX-ACCESS  read-only
    STATUS      current
   DESCRIPTION
      "Number of times the CM received invalid ranging response
      messages.
      Discontinuities in the value of this counter can occur
      at reinitialization of the managed system, and at other
      times as indicated by the value of
      ifCounterDiscontinuityTime for the associated ifIndex."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
      Frequency Interface Specification SP-RFIv2.0-I10-051209,
      Section 8.3.6."
   ::= { docsIfCmStatusEntry 8 }

docsIfCmStatusInvalidRegistrationResponses OBJECT-TYPE
   SYNTAX      Counter32
   UNITS       "messages"
   MAX-ACCESS  read-only
   STATUS      current
```

```
    DESCRIPTION
        "Number of times the CM received invalid registration
        response messages.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as
 indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 8.3.8."
    ::= { docsIfCmStatusEntry 9 }

docsIfCmStatusT1Timeouts OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "timeouts"
    MAX-ACCESS  read-only
    STATUS      current



    DESCRIPTION
        "Number of times counter T1 expired in the CM.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Figure 9-2."
    ::= { docsIfCmStatusEntry 10 }

docsIfCmStatusT2Timeouts OBJECT-TYPE
     SYNTAX      Counter32
    UNITS       "timeouts"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of times counter T2 expired in the CM.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
```

```
        Figure 9-2."
    ::= { docsIfCmStatusEntry 11 }

docsIfCmStatusT3Timeouts OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "timeouts"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of times counter T3 expired in the CM.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times
 as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Figure 9-2."
    ::= { docsIfCmStatusEntry 12 }

docsIfCmStatusT4Timeouts OBJECT-TYPE
    SYNTAX      Counter32



    UNITS       "timeouts"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of times counter T4 expired in the CM.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Figure 9-2."
    ::= { docsIfCmStatusEntry 13 }

docsIfCmStatusRangingAborteds
 OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "attempts"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
```

```
        "Number of times the ranging process was aborted
        by the CMTS.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.3.3."
    ::= { docsIfCmStatusEntry 14 }

docsIfCmStatusDocsisOperMode OBJECT-TYPE
    SYNTAX      DocsisQosVersion
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Indication of whether the device has registered using 1.0
        Class of Service or 1.1 Quality of Service.
        An unregistered CM SHOULD indicate 'docsis11'
 for a
        docsIfDocsisBaseCapability value of DOCSIS 1.1/2.0.  An
        unregistered CM SHOULD indicate 'docsis10'  for a
        docsIfDocsisBaseCapability value of DOCSIS 1.0."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Annex G."



    ::= { docsIfCmStatusEntry 15 }

docsIfCmStatusModulationType OBJECT-TYPE
    SYNTAX      DocsisUpstreamType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Indicates modulation type status currently used by the
        CM.  Since this object specifically identifies PHY mode,
        the shared upstream channel type is not permitted."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.1."

    ::= { docsIfCmStatusEntry 16 }
```

```
docsIfCmStatusEqualizationData OBJECT-TYPE
    SYNTAX      DocsEqualizerData
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "Pre-equalization data for this CM after convolution with
       data indicated in the RNG-RSP.  This data is valid when
       docsIfUpChannelPreEqEnable is set to true."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Figure 8-23."
   ::= { docsIfCmStatusEntry 17 }

docsIfCmStatusUCCs OBJECT-TYPE
   SYNTAX         Counter32
   UNITS          "attempts"
   MAX-ACCESS     read-only
   STATUS         current
   DESCRIPTION
      "The number of successful Upstream Channel Change
       transactions.
       Discontinuities in the value of this counter can occur
       at reinitialization of the managed system, and at other
       times as indicated by the value of
       ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmStatusEntry 18 }

docsIfCmStatusUCCFails OBJECT-TYPE
   SYNTAX         Counter32
   UNITS          "attempts"



   MAX-ACCESS     read-only
   STATUS         current
   DESCRIPTION
      "The number of failed Upstream Channel Change
       transactions.
       Discontinuities in the value of this counter can occur
       at reinitialization of the managed system, and at other
       times as indicated by the value of
       ifCounterDiscontinuityTime for the associated ifIndex."
   ::= { docsIfCmStatusEntry 19 }

--
-- The Cable Modem Service Table
--
```

```
docsIfCmServiceTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF DocsIfCmServiceEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "Describes the attributes of each upstream service queue
       on a CM."
   ::= { docsIfCmObjects 3 }

docsIfCmServiceEntry OBJECT-TYPE
   SYNTAX      DocsIfCmServiceEntry
   MAX-ACCESS  not-accessible
   STATUS
    current
   DESCRIPTION
      "Describes the attributes of an upstream bandwidth service
       queue.
       An entry in this table exists for each Service ID.
       The primary index is an ifIndex with an ifType of
       docsCableMaclayer(127)."
   INDEX { ifIndex, docsIfCmServiceId }
   ::= { docsIfCmServiceTable 1 }

DocsIfCmServiceEntry ::= SEQUENCE {
       docsIfCmServiceId              Integer32,
       docsIfCmServiceQosProfile      Integer32,
       docsIfCmServiceTxSlotsImmed    Counter32,
       docsIfCmServiceTxSlotsDed      Counter32,
       docsIfCmServiceTxRetries       Counter32,
       docsIfCmServiceTxExceededs     Counter32,
       docsIfCmServiceRqRetries       Counter32,
       docsIfCmServiceRqExceededs     Counter32,
       docsIfCmServiceExtTxSlotsImmed Counter64,
       docsIfCmServiceExtTxSlotsDed   Counter64



    }

docsIfCmServiceId OBJECT-TYPE
   SYNTAX      Integer32 (1..16383)
   MAX-ACCESS
  not-accessible
   STATUS      current
   DESCRIPTION
      "Identifies a service queue for upstream bandwidth.  The
       attributes of this service queue are shared between the
```

CM and the CMTS. The CMTS allocates upstream bandwidth
to this service queue based on requests from the CM and
on the class of service associated with this queue."
::= { docsIfCmServiceEntry 1 }

docsIfCmServiceQosProfile OBJECT-TYPE
SYNTAX Integer32 (0..16383)
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The index in docsIfQosProfileTable describing the quality
of service attributes associated with this particular
service. If no associated entry in docsIfQosProfileTable
exists, this object returns a value of zero."
::= { docsIfCmServiceEntry 2 }

docsIfCmServiceTxSlotsImmed OBJECT-TYPE
SYNTAX Counter32
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS
current
DESCRIPTION
"The number of upstream mini-slots that have been used to
transmit data PDUs in immediate (contention) mode. This
includes only those PDUs that are presumed to have
arrived at the head-end (i.e., those that were explicitly
acknowledged). It does not include retransmission attempts
or mini-slots used by requests.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 9.4."
::= { docsIfCmServiceEntry 3 }

docsIfCmServiceTxSlotsDed OBJECT-TYPE

SYNTAX Counter32
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS

current
DESCRIPTION
"The number of upstream mini-slots that have been used to
transmit data PDUs in dedicated mode (i.e., as a result
of a unicast Data Grant).
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 9.4."
::= { docsIfCmServiceEntry 4 }

docsIfCmServiceTxRetries OBJECT-TYPE
SYNTAX Counter32
UNITS "attempts"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of attempts to transmit data PDUs containing
requests for acknowledgment that did not result in
acknowledgment.
Discontinuities in the value of
this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 9.4."
::= { docsIfCmServiceEntry 5 }

docsIfCmServiceTxExceededs OBJECT-TYPE
SYNTAX Counter32
UNITS "attempts"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of data PDU transmission failures due to
excessive retries without acknowledgment.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of

```
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications:
 Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.4."
    ::= { docsIfCmServiceEntry 6 }

docsIfCmServiceRqRetries OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "attempts"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of attempts to transmit bandwidth requests
        that did not result in acknowledgment.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.4."
    ::= { docsIfCmServiceEntry 7 }

docsIfCmServiceRqExceededs OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "attempts"
    MAX-ACCESS  read-only
    STATUS
      current
    DESCRIPTION
        "The number of requests for bandwidth that failed due to
        excessive retries without acknowledgment.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.4."
    ::= { docsIfCmServiceEntry 8 }

docsIfCmServiceExtTxSlotsImmed OBJECT-TYPE
    SYNTAX      Counter64
```

```
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current



    DESCRIPTION
        "The number of upstream mini-slots that have been used to
        transmit data PDUs in immediate (contention) mode.  This
        includes only those PDUs that are presumed to have
        arrived at the head-end
 (i.e., those that were explicitly
        acknowledged).  It does not include retransmission attempts
        or mini-slots used by requests.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.4."
    ::= { docsIfCmServiceEntry 9 }

docsIfCmServiceExtTxSlotsDed OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of upstream mini-slots that have been used to
        transmit data PDUs in dedicated mode (i.e., as a result
        of a unicast Data Grant).
        Discontinuities in the value of this counter can occur

        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.4."
    ::= { docsIfCmServiceEntry 10 }

--
-- CMTS GROUP
--
```

```
--
-- The CMTS MAC Table
--

docsIfCmtsMacTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF DocsIfCmtsMacEntry
   MAX-ACCESS  not-accessible
   STATUS      current



   DESCRIPTION
      "Describes the attributes of each CMTS MAC interface,
       extending the information available from ifEntry.
       Mandatory for all CMTS devices."
   ::= { docsIfCmtsObjects 1 }

docsIfCmtsMacEntry OBJECT-TYPE
   SYNTAX      DocsIfCmtsMacEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "An entry containing objects describing attributes of each
        MAC entry, extending the information in ifEntry.
       An entry in this table exists for each ifEntry with an
       ifType of docsCableMaclayer(127)."
   INDEX { ifIndex }
   ::= { docsIfCmtsMacTable 1 }

DocsIfCmtsMacEntry ::= SEQUENCE {
      docsIfCmtsCapabilities           BITS,
      docsIfCmtsSyncInterval           Integer32,
      docsIfCmtsUcdInterval            Integer32,
      docsIfCmtsMaxServiceIds          Integer32,
      docsIfCmtsInsertionInterval      TimeTicks,   -- Obsolete
      docsIfCmtsInvitedRangingAttempts  Integer32,
      docsIfCmtsInsertInterval         TimeInterval,
      docsIfCmtsMacStorageType         StorageType
   }

docsIfCmtsCapabilities OBJECT-TYPE
   SYNTAX      BITS {
      atmCells(0),
      concatenation(1)
   }
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
```

```
        "Identifies the capabilities of the CMTS MAC
        implementation at this interface.  Note
 that packet
        transmission is always supported.  Therefore, there
        is no specific bit required to explicitly indicate
        this capability.
        Note that BITS objects are encoded most significant bit
        first.  For example, if bit 1 is set, the value of this
        object is the octet string '40'H."
    ::= { docsIfCmtsMacEntry 1 }

docsIfCmtsSyncInterval OBJECT-TYPE



    SYNTAX      Integer32 (1..200)
    UNITS       "Milliseconds"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The interval between CMTS transmission of successive SYNC
        messages at this interface."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.3."
    ::= { docsIfCmtsMacEntry 2 }

docsIfCmtsUcdInterval OBJECT-TYPE
    SYNTAX      Integer32 (1..2000)
    UNITS       "Milliseconds"
    MAX-ACCESS  read-write

  STATUS      current
    DESCRIPTION
        "The interval between CMTS transmission of successive
        Upstream Channel Descriptor messages for each upstream
        channel at this interface."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.3"
    ::= { docsIfCmtsMacEntry 3 }

docsIfCmtsMaxServiceIds OBJECT-TYPE
    SYNTAX     Integer32 (1..16383)
    UNITS      "SIDs"
    MAX-ACCESS read-only
```

```
    STATUS     current
    DESCRIPTION
        "The maximum number of service IDs that may be
        simultaneously active."
    ::= { docsIfCmtsMacEntry 4 }

docsIfCmtsInsertionInterval OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-write
    STATUS      obsolete
    DESCRIPTION
        "The amount of time to elapse between each broadcast
        initial maintenance grant.  Broadcast initial maintenance
        grants are used to allow
 new cable modems to join the
        network.  Zero indicates that a vendor-specific algorithm
        is used instead of a fixed time.  The maximum amount of




        time permitted by the specification is 2 seconds.
        This object has been obsoleted and replaced by
        docsIfCmtsInsertInterval to fix a SYNTAX typing problem."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Annex B."
    ::= { docsIfCmtsMacEntry 5 }

docsIfCmtsInvitedRangingAttempts OBJECT-TYPE
    SYNTAX      Integer32 (0..1024)
    UNITS       "attempts"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The maximum number of attempts to make on invitations
        for ranging requests.  A value of zero means the system
        SHOULD attempt to range forever."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency
 Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.3.3 and Annex B."
    ::= { docsIfCmtsMacEntry 6 }

docsIfCmtsInsertInterval OBJECT-TYPE
    SYNTAX      TimeInterval
    UNITS       "HundredOfSeconds"
```

```
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The amount of time to elapse between each broadcast
        initial maintenance grant.  Broadcast initial maintenance
        grants are used to allow new cable modems to join the
        network.  Zero indicates that a vendor-specific algorithm
        is used instead of a fixed time.  The maximum amount of
        time permitted by the specification is 2 seconds."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Annex B."
    ::= { docsIfCmtsMacEntry 7 }

docsIfCmtsMacStorageType OBJECT-TYPE
    SYNTAX       StorageType
    MAX-ACCESS   read-only
    STATUS
      current
    DESCRIPTION
        "The storage type for this conceptual row.



        Entries with this object set to permanent(4)
        do not require write operations for read-write
        objects."
    ::= { docsIfCmtsMacEntry 8 }

--
--
-- CMTS status table.
--

docsIfCmtsStatusTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfCmtsStatusEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "For the MAC layer, this group maintains a number of
        status objects and counters."
    ::= { docsIfCmtsObjects 2 }

docsIfCmtsStatusEntry OBJECT-TYPE
    SYNTAX      DocsIfCmtsStatusEntry
    MAX-ACCESS  not-accessible
    STATUS      current
```

```
    DESCRIPTION
      "Status entry for a single MAC layer.
       An entry in this table exists for each ifEntry with an
       ifType of docsCableMaclayer(127)."
    INDEX { ifIndex }
    ::= { docsIfCmtsStatusTable 1 }

DocsIfCmtsStatusEntry ::= SEQUENCE {
       docsIfCmtsStatusInvalidRangeReqs
       Counter32,
       docsIfCmtsStatusRangingAborteds        Counter32,
       docsIfCmtsStatusInvalidRegReqs         Counter32,
       docsIfCmtsStatusFailedRegReqs          Counter32,
       docsIfCmtsStatusInvalidDataReqs        Counter32,
       docsIfCmtsStatusT5Timeouts             Counter32
    }

docsIfCmtsStatusInvalidRangeReqs OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "messages"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       "This object counts invalid RNG-REQ messages received on
        this interface.
        Discontinuities in the value of this counter can occur



        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
       "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Section 8.3.5."
    ::= { docsIfCmtsStatusEntry 1 }

docsIfCmtsStatusRangingAborteds OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "attempts"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       "This object counts ranging attempts that were explicitly
        aborted by the CMTS.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
```

```
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 8.3.6."
    ::= { docsIfCmtsStatusEntry 2 }

docsIfCmtsStatusInvalidRegReqs OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "messages"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object counts invalid REG-REQ messages
 received on
        this interface; that is, syntax, out of range parameters,
        or erroneous requests.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 8.3.7."
    ::= { docsIfCmtsStatusEntry 3 }

docsIfCmtsStatusFailedRegReqs OBJECT-TYPE
    SYNTAX      Counter32



    UNITS       "attempts"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object counts failed registration attempts.  Included
        are docsIfCmtsStatusInvalidRegReqs, authentication, and
        class of service failures.
        Discontinuities in the value of this counter can occur
        at reinitialization
 of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
```

```
        Section 8.3.7."
    ::= { docsIfCmtsStatusEntry 4 }

docsIfCmtsStatusInvalidDataReqs OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "messages"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object counts invalid data request messages
        received on this interface.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsStatusEntry 5 }

docsIfCmtsStatusT5Timeouts OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "timeouts"
     MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object counts the number of times counter T5
        expired on this interface.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Figure 9-2."
    ::= { docsIfCmtsStatusEntry 6 }




--
-- CM status table (within CMTS).
-- This table is implemented only at the CMTS.
-- It contains per-CM status information available in the CMTS.
--

docsIfCmtsCmStatusTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfCmtsCmStatusEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
```

```
        "A set of objects in the CMTS, maintained for each
         cable modem connected to this CMTS."
    ::= { docsIfCmtsObjects 3 }

docsIfCmtsCmStatusEntry OBJECT-TYPE
    SYNTAX      DocsIfCmtsCmStatusEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Status information for a single cable modem.
         An entry in this table exists for each cable modem
         that is connected to the CMTS implementing this table."
    INDEX { docsIfCmtsCmStatusIndex }
    ::= { docsIfCmtsCmStatusTable 1 }

DocsIfCmtsCmStatusEntry ::= SEQUENCE {
        docsIfCmtsCmStatusIndex             Integer32,
        docsIfCmtsCmStatusMacAddress        MacAddress,
        docsIfCmtsCmStatusIpAddress         IpAddress, -- deprecated
        docsIfCmtsCmStatusDownChannelIfIndex  InterfaceIndexOrZero,
        docsIfCmtsCmStatusUpChannelIfIndex    InterfaceIndexOrZero,
        docsIfCmtsCmStatusRxPower           TenthdBmV,
        docsIfCmtsCmStatusTimingOffset      Unsigned32,
        docsIfCmtsCmStatusEqualizationData
    DocsEqualizerData,
        docsIfCmtsCmStatusValue             INTEGER,
        docsIfCmtsCmStatusUnerroreds        Counter32,
        docsIfCmtsCmStatusCorrecteds        Counter32,
        docsIfCmtsCmStatusUncorrectables    Counter32,
        docsIfCmtsCmStatusSignalNoise       TenthdB,
        docsIfCmtsCmStatusMicroreflections  Integer32,
        docsIfCmtsCmStatusExtUnerroreds     Counter64,
        docsIfCmtsCmStatusExtCorrecteds     Counter64,
        docsIfCmtsCmStatusExtUncorrectables Counter64,
        docsIfCmtsCmStatusDocsisRegMode     DocsisQosVersion,
        docsIfCmtsCmStatusModulationType    DocsisUpstreamType,
        docsIfCmtsCmStatusInetAddressType   InetAddressType,
        docsIfCmtsCmStatusInetAddress       InetAddress,



        docsIfCmtsCmStatusValueLastUpdate   TimeStamp,
        docsIfCmtsCmStatusHighResolutionTimingOffset Unsigned32
    }

docsIfCmtsCmStatusIndex OBJECT-TYPE
    SYNTAX
```

Integer32 (1..2147483647)
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Index value to uniquely identify an entry in this table.
For an individual cable modem, this index value SHOULD
NOT change during CMTS uptime."
::= { docsIfCmtsCmStatusEntry 1 }

docsIfCmtsCmStatusMacAddress OBJECT-TYPE
SYNTAX MacAddress
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"MAC address of the cable modem. If the cable modem has
multiple MAC addresses, this is the MAC address associated
with the Cable interface."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 8.2.2."
::= { docsIfCmtsCmStatusEntry 2 }

docsIfCmtsCmStatusIpAddress OBJECT-TYPE
SYNTAX IpAddress
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
"IP address
of this cable modem. If the cable modem has no
IP address assigned, or the IP address is unknown, this
object returns a value of 0.0.0.0. If the cable modem has
multiple IP addresses, this object returns the IP address
associated with the Cable interface.
This object has been deprecated and replaced by
docsIfCmtsCmStatusInetAddressType and
docsIfCmtsCmStatusInetAddress, to enable IPv6 addressing
in the future."
::= { docsIfCmtsCmStatusEntry 3 }

docsIfCmtsCmStatusDownChannelIfIndex OBJECT-TYPE
SYNTAX InterfaceIndexOrZero
MAX-ACCESS read-only
STATUS current

DESCRIPTION

```
        "IfIndex of the downstream channel that this CM is
         connected to.  If the downstream channel is unknown, this
         object returns a value of zero."
    ::= { docsIfCmtsCmStatusEntry 4 }

docsIfCmtsCmStatusUpChannelIfIndex OBJECT-TYPE
    SYNTAX      InterfaceIndexOrZero
    MAX-ACCESS
  read-only
    STATUS      current
    DESCRIPTION
       "For DOCSIS 2.0, indicates the ifIndex of the logical
        upstream channel (ifType 205) this CM is connected to.
        For DOCSIS 1.x, indicates the ifIndex of the upstream
         channel (ifType 129) this CM is connected to.
         If the upstream channel is unknown, this object
         returns a value of zero."
    ::= { docsIfCmtsCmStatusEntry 5 }

docsIfCmtsCmStatusRxPower OBJECT-TYPE
    SYNTAX      TenthdBmV
    UNITS       "ThenthdBmV"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       "The receive power as perceived for upstream data from
        this cable modem.
        If the receive power is unknown, this object returns
        a value of zero."
    REFERENCE
       "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.18."
    ::= { docsIfCmtsCmStatusEntry 6
  }

docsIfCmtsCmStatusTimingOffset OBJECT-TYPE
    SYNTAX      Unsigned32 (0..4294967295)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       "A measure of the current round trip time for this CM.
        Used for timing of CM upstream transmissions to ensure
        synchronized arrivals at the CMTS.  Units are in terms
        of (6.25 microseconds/64).  Returns zero if the value
        is unknown.
        For channels requiring finer resolution, please refer to
        object docsIfCmtsCmStatusHighResolutionTimingOffset."
```

```
    REFERENCE


        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.17."
    ::= { docsIfCmtsCmStatusEntry 7 }

docsIfCmtsCmStatusEqualizationData OBJECT-TYPE
    SYNTAX      DocsEqualizerData
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Equalization data for this CM, as measured by the CMTS.
         Returns the zero-length OCTET STRING if the value is
        unknown or if there is no equalization data available
        or defined."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Figure 8-23."
    ::= { docsIfCmtsCmStatusEntry 8 }

docsIfCmtsCmStatusValue OBJECT-TYPE
    SYNTAX      INTEGER {
        other(1),
        ranging(2),
        rangingAborted(3),
        rangingComplete(4),
        ipComplete(5),
        registrationComplete(6),
        accessDenied(7),
        operational(8),
        -- value 8 should not be used
        registeredBPIInitializing(9)
    }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Current cable modem connectivity state, as specified
        in the RF Interface Specification.  Returned status
        information is the CM status, as assumed by the CMTS,
        and indicates
 the following events:
        other(1)
           Any state other than below.
        ranging(2)
```

The CMTS has received an Initial Ranging Request
message from the CM, and the ranging process is not
yet complete.
rangingAborted(3)
The CMTS has sent a Ranging Abort message to the CM.

rangingComplete(4)
The CMTS has sent a Ranging Complete message to the CM.
ipComplete(5)
The CMTS has received a DHCP reply message and
forwarded it to the CM.
registrationComplete(6)
The CMTS has sent a Registration Response message to
the CM.
accessDenied(7)
The CMTS has sent a Registration Aborted message
to the CM.
operational(8)
Value 8 is considered reserved and should not be defined
in future revisions of this MIB module to avoid conflict
with documented
implementations that support value 8 to
indicate operational state after completing the BPI
initialization process.
registeredBPIInitializing(9)
Baseline Privacy (BPI) is enabled and the CMTS is in the
process of completing BPI initialization. This state
MAY last for a significant length of time if failures
occur during the initialization process. After
completion of BPI initialization, the CMTS will report
registrationComplete(6).
The CMTS only needs to report states it is able to
detect."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 11.2."
::= { docsIfCmtsCmStatusEntry 9 }

docsIfCmtsCmStatusUnerroreds OBJECT-TYPE
SYNTAX Counter32
UNITS "codewords"
MAX-ACCESS read-only
STATUS current

```
 DESCRIPTION
      "Codewords received without error from this cable modem.
       Discontinuities in the value of this counter can occur
       at reinitialization of the managed system, and at other
       times as indicated by the value of
       ifCounterDiscontinuityTime for the associated ifIndex."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Section 6.2.4."
   ::= { docsIfCmtsCmStatusEntry 10 }



docsIfCmtsCmStatusCorrecteds OBJECT-TYPE
   SYNTAX      Counter32
   UNITS       "codewords"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "Codewords received with correctable errors from this
       cable modem.
       Discontinuities in the value of this counter can occur
       at reinitialization of the managed system, and at other
       times as indicated by the value of
       ifCounterDiscontinuityTime
 for the associated ifIndex."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Section 6.2.4."
   ::= { docsIfCmtsCmStatusEntry 11 }

docsIfCmtsCmStatusUncorrectables OBJECT-TYPE
   SYNTAX      Counter32
   UNITS       "codewords"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "Codewords received with uncorrectable errors from this
       cable modem.
       Discontinuities in the value of this counter can occur
       at reinitialization of the managed system, and at other
       times as indicated by the value of
       ifCounterDiscontinuityTime for the associated ifIndex."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
```

```
        Section 6.2.4."
    ::= { docsIfCmtsCmStatusEntry 12 }

docsIfCmtsCmStatusSignalNoise OBJECT-TYPE
     SYNTAX      TenthdB
    UNITS       "TenthdB"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Signal/Noise ratio as perceived for upstream data from
        this cable modem.
        If the Signal/Noise is unknown, this object returns
        a value of zero."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio



        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Tables 4-1 and 4-2."
    ::= { docsIfCmtsCmStatusEntry 13 }

docsIfCmtsCmStatusMicroreflections OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    UNITS       "-dBc"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Total microreflections, including in-channel response
        as perceived on this interface, measured in dBc below
        the signal level.
        This object is not assumed to return an absolutely
        accurate value, but it gives a rough indication
        of microreflections
 received on this interface.
        It is up to the implementer to provide information
        as accurately as possible.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Tables 4-1 and 4-2"
    ::= { docsIfCmtsCmStatusEntry 14 }

docsIfCmtsCmStatusExtUnerroreds OBJECT-TYPE
```

```
    SYNTAX      Counter64
    UNITS       "codewords"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Codewords received without error from this cable modem.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the
 value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.5."
    ::= { docsIfCmtsCmStatusEntry 15 }

docsIfCmtsCmStatusExtCorrecteds OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "codewords"



    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Codewords received with correctable errors from this
        cable modem.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.5."
    ::= { docsIfCmtsCmStatusEntry
 16 }

docsIfCmtsCmStatusExtUncorrectables OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "codewords"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Codewords received with uncorrectable errors from this
        cable modem.
        Discontinuities in the value of this counter can occur
```

```
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.5."
    ::= { docsIfCmtsCmStatusEntry 17 }

docsIfCmtsCmStatusDocsisRegMode OBJECT-TYPE
      SYNTAX      DocsisQosVersion
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
          "Indication of whether the CM has registered using 1.0
          Class of Service or 1.1 Quality of Service."
     REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Annex G."
    ::= { docsIfCmtsCmStatusEntry 18 }

docsIfCmtsCmStatusModulationType OBJECT-TYPE
     SYNTAX      DocsisUpstreamType



     MAX-ACCESS  read-only
     STATUS      current
     DESCRIPTION
         "Indicates modulation type currently used by the CM.  Since
         this object specifically identifies PHY mode, the shared
         type is not permitted.  If the upstream channel is
         unknown, this object returns a value of zero."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Table 8-19."
    ::= { docsIfCmtsCmStatusEntry 19 }

docsIfCmtsCmStatusInetAddressType OBJECT-TYPE
      SYNTAX      InetAddressType
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
          "The type of internet address of
          docsIfCmtsCmStatusInetAddress.  If the cable modem
          internet address is unassigned or unknown, then the
```

```
            value of this object is unknown(0)."
        ::= { docsIfCmtsCmStatusEntry 20 }

docsIfCmtsCmStatusInetAddress OBJECT-TYPE
        SYNTAX      InetAddress
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
            "Internet address of this cable modem.  If the Cable
             Modem has no Internet address assigned, or the Internet
             address is unknown, the value of this object is the
             zero-length OCTET STRING.  If the cable modem has
             multiple Internet addresses, this object returns the
             Internet address associated with the Cable
             (i.e., RF MAC) interface."
        ::= { docsIfCmtsCmStatusEntry 21 }

docsIfCmtsCmStatusValueLastUpdate OBJECT-TYPE
        SYNTAX      TimeStamp
        MAX-ACCESS  read-only
         STATUS      current
        DESCRIPTION
            "The value of sysUpTime when docsIfCmtsCmStatusValue
             was last updated."
        ::= { docsIfCmtsCmStatusEntry 22 }

docsIfCmtsCmStatusHighResolutionTimingOffset OBJECT-TYPE



    SYNTAX      Unsigned32 (0..4294967295)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A measure of the current round trip time for this CM.
         Used for timing of CM upstream transmissions to ensure
         synchronized arrivals at the CMTS.  Units are in terms
         of (6.25 microseconds/(64*256)).  Returns zero if the value
         is unknown.
         This is the high resolution version of object
         docsIfCmtsCmStatusTimingOffset, for channels requiring
         finer resolution."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Section 6.2.17."
    ::= { docsIfCmtsCmStatusEntry
```

```
 23 }

--
-- The CMTS Service Table.
--

docsIfCmtsServiceTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF DocsIfCmtsServiceEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "Describes the attributes of upstream service queues
       in a Cable Modem Termination System."
   ::= { docsIfCmtsObjects 4 }

docsIfCmtsServiceEntry OBJECT-TYPE
   SYNTAX      DocsIfCmtsServiceEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "Describes the attributes of a single upstream bandwidth
       service queue.
       Entries in this table exist for each ifEntry with an
       ifType of docsCableMaclayer(127), and for each service
       queue (Service ID) within this MAC layer.
       Entries in this table are created with the creation of
       individual Service IDs by the MAC layer and removed
       when a Service ID is removed."
   INDEX { ifIndex, docsIfCmtsServiceId }
   ::= { docsIfCmtsServiceTable
 1 }

DocsIfCmtsServiceEntry ::= SEQUENCE {



      docsIfCmtsServiceId             Integer32,
      docsIfCmtsServiceCmStatusIndex    Integer32,  -- deprecated
      docsIfCmtsServiceAdminStatus      INTEGER,
      docsIfCmtsServiceQosProfile       Integer32,
      docsIfCmtsServiceCreateTime       TimeStamp,
      docsIfCmtsServiceInOctets         Counter32,
      docsIfCmtsServiceInPackets        Counter32,
      docsIfCmtsServiceNewCmStatusIndex Integer32
   }

docsIfCmtsServiceId OBJECT-TYPE
   SYNTAX      Integer32 (1..16383)
```

```
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Identifies a service queue for upstream bandwidth.  The
         attributes of this service queue are shared between the
         Cable Modem and the Cable Modem Termination System.
         The CMTS allocates upstream bandwidth to this service
         queue based on requests from the CM and on the class of
         service
 associated with this queue."
    ::= { docsIfCmtsServiceEntry 1 }

docsIfCmtsServiceCmStatusIndex OBJECT-TYPE
    SYNTAX      Integer32 (0..65535)
    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
        "Pointer to an entry in docsIfCmtsCmStatusTable identifying
         the cable modem using this Service Queue.  If multiple
         cable modems are using this Service Queue, the value of
         this object is zero.
         This object has been deprecated and replaced by
         docsIfCmtsServiceNewCmStatusIndex, to fix a mismatch
         of the value range with respect to docsIfCmtsCmStatusIndex
         (1..2147483647)."
    ::= { docsIfCmtsServiceEntry 2 }

docsIfCmtsServiceAdminStatus OBJECT-TYPE
    SYNTAX      INTEGER {
        enabled(1),
        disabled(2),
        destroyed(3) }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "Allows a service class for a particular modem to be
         suppressed,
 (re-)enabled, or deleted altogether."



    ::= { docsIfCmtsServiceEntry 3 }

docsIfCmtsServiceQosProfile OBJECT-TYPE
    SYNTAX      Integer32 (0..16383)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
```

"The index in docsIfQosProfileTable describing the quality
of service attributes associated with this particular
service. If no associated docsIfQosProfileTable entry
exists, this object returns a value of zero."
::= { docsIfCmtsServiceEntry 4 }

docsIfCmtsServiceCreateTime OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime when this entry was created."
::= { docsIfCmtsServiceEntry 5 }

docsIfCmtsServiceInOctets OBJECT-TYPE
SYNTAX Counter32
UNITS "Bytes"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The cumulative number of Packet Data octets received
on this Service
ID. The count does not include the
size of the Cable MAC header.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsServiceEntry 6 }

docsIfCmtsServiceInPackets OBJECT-TYPE
SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The cumulative number of Packet Data packets received
on this Service ID.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."

::= { docsIfCmtsServiceEntry 7 }

docsIfCmtsServiceNewCmStatusIndex OBJECT-TYPE

```
    SYNTAX      Integer32 (0..2147483647)
    MAX-ACCESS
  read-only
    STATUS      current
    DESCRIPTION
        "Pointer (via docsIfCmtsCmStatusIndex) to an entry in
         docsIfCmtsCmStatusTable identifying the cable modem
         using this Service Queue.  If multiple cable modems are
         using this Service Queue, the value of this object is
         zero."
    ::= { docsIfCmtsServiceEntry 8 }

--
-- The following table provides upstream channel modulation profiles.
-- Entries in this table can be
-- re-used by one or more upstream channels.  An upstream channel
-- will have a modulation profile for each value of
-- docsIfModIntervalUsageCode.
--

docsIfCmtsModulationTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfCmtsModulationEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Describes a modulation profile associated with one or more
         upstream channels."
    ::= { docsIfCmtsObjects 5 }

docsIfCmtsModulationEntry OBJECT-TYPE
    SYNTAX      DocsIfCmtsModulationEntry
     MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Describes a modulation profile for an Interval Usage Code
         for one or more upstream channels.
         Entries in this table are created by the operator.

         Initial default entries MAY be created at system
         initialization time, which could report a value of
         'permanent' or 'readOnly' for docsIfCmtsModStorageType.
         A CMTS MAY reject the creation of additional Interval
         Usage Codes for a modulation profile being defined at
         Initialization time.
         No individual objects have to be specified in order
         to create an entry in this table.
```

```
        Note that some objects do not have DEFVAL clauses
        but do have calculated defaults and need not be specified
        during row creation."
    INDEX { docsIfCmtsModIndex, docsIfCmtsModIntervalUsageCode}
   ::= { docsIfCmtsModulationTable 1 }

DocsIfCmtsModulationEntry
 ::= SEQUENCE {
       docsIfCmtsModIndex                Integer32,
       docsIfCmtsModIntervalUsageCode    INTEGER,
       docsIfCmtsModControl              RowStatus,
       docsIfCmtsModType                 INTEGER,
       docsIfCmtsModPreambleLen          Integer32,
       docsIfCmtsModDifferentialEncoding TruthValue,
       docsIfCmtsModFECErrorCorrection   Integer32,
       docsIfCmtsModFECCodewordLength    Integer32,
       docsIfCmtsModScramblerSeed        Integer32,
       docsIfCmtsModMaxBurstSize         Integer32,
       docsIfCmtsModGuardTimeSize        Unsigned32,
       docsIfCmtsModLastCodewordShortened TruthValue,
       docsIfCmtsModScrambler            TruthValue,
       docsIfCmtsModByteInterleaverDepth Unsigned32,
       docsIfCmtsModByteInterleaverBlockSize Unsigned32,
       docsIfCmtsModPreambleType         INTEGER,
       docsIfCmtsModTcmErrorCorrectionOn TruthValue,
        docsIfCmtsModScdmaInterleaverStepSize Unsigned32,
       docsIfCmtsModScdmaSpreaderEnable  TruthValue,
       docsIfCmtsModScdmaSubframeCodes   Unsigned32,
       docsIfCmtsModChannelType          DocsisUpstreamType,
       docsIfCmtsModStorageType          StorageType
   }

docsIfCmtsModIndex OBJECT-TYPE
   SYNTAX      Integer32 (1..2147483647)
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
       "An index into the Channel Modulation table representing
        a group of Interval Usage Codes, all associated with the
        same channel."
   ::= { docsIfCmtsModulationEntry 1 }

docsIfCmtsModIntervalUsageCode OBJECT-TYPE
   SYNTAX      INTEGER {
       request(1),
       requestData(2),
       initialRanging(3),
```

```
        periodicRanging(4),
        shortData(5),



        longData(6),
        advPhyShortData(9),
        advPhyLongData(10),
        ugs(11)
    }
    MAX-ACCESS  not-accessible
     STATUS      current
    DESCRIPTION
        "An index into the Channel Modulation table that, when
         grouped with other Interval Usage Codes, fully
         instantiates all modulation sets for a given upstream
         channel."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Table 8-20."
    ::= { docsIfCmtsModulationEntry 2 }

docsIfCmtsModControl OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Controls and reflects the status of rows in this table.
         There is no restriction on the changing of values in this
         table while their associated rows are active, with the
         exception of:

         1. If a modulation profile is being referenced by one
            or more upstream channels, an attempt to set the value
            of docsIfCmtsModChannelType returns
 an
            'inconsistentValue' error.

         2. If a modulation profile is being referenced by one
            or more upstream channels, an attempt to set
            docsIfCmtsModControl to destroy(6) or notInService(2)
            returns an 'inconsistentValue' error."
    ::= { docsIfCmtsModulationEntry 3 }

docsIfCmtsModType OBJECT-TYPE
    SYNTAX      INTEGER {
        other(1),
```

```
        qpsk(2),
        qam16(3),
        qam8(4),
        qam32(5),
        qam64(6),
        qam128(7)



    }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The modulation type used on this channel.  Returns
         other(1) if the modulation type is not
         qpsk, qam16, qam8, qam32, qam64, or qam128.
         Type qam128 is used for SCDMA channels only.
         See the reference for the modulation profiles
         implied by different modulation types."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications:
 Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
    DEFVAL { qpsk }
    ::= { docsIfCmtsModulationEntry 4 }

docsIfCmtsModPreambleLen OBJECT-TYPE
    SYNTAX      Integer32 (0..1536)
    UNITS       "bits"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The preamble length for this modulation profile in bits.
         Default value is the minimum needed by the implementation
         at the CMTS for the given modulation profile."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
    ::= { docsIfCmtsModulationEntry 5 }

docsIfCmtsModDifferentialEncoding OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies whether or not differential encoding is used
```

```
        on this channel."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Tables 6-7, and 8-19."
    DEFVAL { false }
    ::= { docsIfCmtsModulationEntry 6 }

docsIfCmtsModFECErrorCorrection OBJECT-TYPE
    SYNTAX      Integer32 (0..16)



    UNITS       "Bytes"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The number of correctable errored bytes (t) used in
        forward error correction code.  The value of 0 indicates
        that no correction is employed.  The number of check bytes
        appended will be twice this value."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Tables 6-7, and 8-19."
    DEFVAL { 0 }
    ::= { docsIfCmtsModulationEntry 7 }

docsIfCmtsModFECCodewordLength OBJECT-TYPE
    SYNTAX      Integer32 (1..255)
    UNITS       "Bytes"
     MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The number of data bytes (k) in the forward error
        correction codeword.
        This object is not used if docsIfCmtsModFECErrorCorrection
        is zero."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Tables 6-7, and 8-19."
    DEFVAL { 32 }
    ::= { docsIfCmtsModulationEntry 8 }

docsIfCmtsModScramblerSeed OBJECT-TYPE
    SYNTAX      Integer32 (0..32767)
    MAX-ACCESS  read-create
```

```
    STATUS      current
    DESCRIPTION
        "The 15-bit seed value for the scrambler polynomial."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Table 8-19."
    DEFVAL { 0 }
    ::= { docsIfCmtsModulationEntry 9 }

docsIfCmtsModMaxBurstSize OBJECT-TYPE
    SYNTAX      Integer32
(0..255)
    UNITS       "mini-slots"



    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The maximum number of mini-slots that can be transmitted
         during this channel's burst time.  Returns zero if the
         burst length is bounded by the allocation MAP rather than
         by this profile.
         Default value is 0, except for shortData, where it is 8."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Table 8-19."
    ::= { docsIfCmtsModulationEntry 10 }

docsIfCmtsModGuardTimeSize OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "Symbol-times"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of symbol-times that MUST follow the end of
         this channel's burst.  Default value is the minimum time
         needed by the implementation for this modulation profile."

 REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
    ::= { docsIfCmtsModulationEntry 11 }

docsIfCmtsModLastCodewordShortened OBJECT-TYPE
```

```
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Indicates whether the last FEC codeword is truncated."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
    DEFVAL { true }
    ::= { docsIfCmtsModulationEntry 12 }

docsIfCmtsModScrambler OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Indicates whether the scrambler is employed."




    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
          Tables 6-7, and 8-19."
    DEFVAL { false }
    ::= { docsIfCmtsModulationEntry 13 }

docsIfCmtsModByteInterleaverDepth OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "ATDMA Byte Interleaver Depth (Ir).  This object returns 1
         for non-ATDMA profiles."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
    DEFVAL { 1 }
    ::= { docsIfCmtsModulationEntry 14 }

docsIfCmtsModByteInterleaverBlockSize OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "ATDMA Byte Interleaver Block size (Br).  This object
```

```
        returns zero for non-ATDMA profiles "
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
    DEFVAL { 18 }
    ::= { docsIfCmtsModulationEntry 15 }

docsIfCmtsModPreambleType OBJECT-TYPE
    SYNTAX      INTEGER {
        unknown(0),
        qpsk0(1),
        qpsk1(2)
    }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Preamble type for DOCSIS 2.0 bursts.  The value
        'unknown(0)' represents a row entry consisting only of
        DOCSIS 1.x bursts"
    REFERENCE



        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Tables 6-7, and 8-19."
    DEFVAL { qpsk0 }
    ::= { docsIfCmtsModulationEntry 16 }

docsIfCmtsModTcmErrorCorrectionOn OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Trellis Code Modulation (TCM) On/Off.  This value returns
        false for non-S-CDMA profiles."
    REFERENCE
        "Data-Over-Cable
 Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Tables 6-7, and 8-19."
    DEFVAL { false }
    ::= { docsIfCmtsModulationEntry 17 }

docsIfCmtsModScdmaInterleaverStepSize OBJECT-TYPE
    SYNTAX      Unsigned32 (0 | 1..32)
    MAX-ACCESS  read-create
```

```
    STATUS      current
    DESCRIPTION
        " S-CDMA Interleaver step size.  This value returns zero
          for non-S-CDMA profiles."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
    DEFVAL { 1 }
    ::= { docsIfCmtsModulationEntry 18 }

docsIfCmtsModScdmaSpreaderEnable OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        " S-CDMA spreader.  This value returns false for non-S-CDMA
          profiles.  Default value for IUC 3 and 4 is OFF; for

       all other IUCs it is ON."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
    ::= { docsIfCmtsModulationEntry 19 }




docsIfCmtsModScdmaSubframeCodes OBJECT-TYPE
    SYNTAX      Unsigned32 (0 | 1..128)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        " S-CDMA sub-frame size.  This value returns zero
          for non-S-CDMA profiles."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Table 6-7, and 8-19."
    DEFVAL { 1 }
    ::= { docsIfCmtsModulationEntry 20 }

docsIfCmtsModChannelType OBJECT-TYPE
    SYNTAX      DocsisUpstreamType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
```

```
        "Describes the modulation channel type for this modulation
         entry.
         All the active
 entries in a modulation profile (that is all
         active entries that share a common docsIfCmtsModIndex)
         MUST have the same value of docsIfCmtsModChannelType."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Table 8-19."
    DEFVAL { tdma }
    ::= { docsIfCmtsModulationEntry 21 }

docsIfCmtsModStorageType OBJECT-TYPE
    SYNTAX       StorageType
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The storage type for this conceptual row.
         Entries with this object set to permanent(4)
         do not require write operations for read-write
         objects."
    DEFVAL      { nonVolatile }
::= { docsIfCmtsModulationEntry 22 }

docsIfCmtsQosProfilePermissions OBJECT-TYPE
    SYNTAX      BITS {
        createByManagement(0),
        updateByManagement(1),
        createByModems(2)




    }
    MAX-ACCESS  read-write
     STATUS      current
    DESCRIPTION
        "This object specifies permitted methods of creating
         entries in docsIfQosProfileTable.
         createByManagement(0) is set if entries can be created
         using SNMP.  updateByManagement(1) is set if updating
         entries using SNMP is permitted.  createByModems(2)
         is set if entries can be created based on information
         in REG-REQ MAC messages received from cable modems.
         Information in this object is only applicable if
         docsIfQosProfileTable is implemented as read-create.
         Otherwise, this object is implemented as read-only
         and returns createByModems(2).
```

```
        Either createByManagement(0) or updateByManagement(1)
        MUST be set when writing to this object.
        Note that BITS objects are encoded most significant bit
        first.  For example, if bit 2 is set, the value of this
        object is the octet string '20'H."
    ::= { docsIfCmtsObjects
 6 }

docsIfCmtsMacToCmTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfCmtsMacToCmEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This is a table to provide a quick access index into the
        docsIfCmtsCmStatusTable.  There is exactly one row in this
        table for each row in the docsIfCmtsCmStatusTable.  In
        general, the management station SHOULD use this table only
        to get a pointer into the docsIfCmtsCmStatusTable (which
        corresponds to the CM's RF interface MAC address) and
        SHOULD not iterate (e.g., GetNext through) this table."
    ::= { docsIfCmtsObjects 7 }

docsIfCmtsMacToCmEntry OBJECT-TYPE
    SYNTAX      DocsIfCmtsMacToCmEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A row in the docsIfCmtsMacToCmTable.
        An entry in this table exists for each cable modem
        that is connected to the CMTS implementing this table."
     INDEX   { docsIfCmtsCmMac }
    ::= {docsIfCmtsMacToCmTable 1 }

DocsIfCmtsMacToCmEntry ::= SEQUENCE {



          docsIfCmtsCmMac     MacAddress,
          docsIfCmtsCmPtr     Integer32
    }

docsIfCmtsCmMac OBJECT-TYPE
    SYNTAX      MacAddress
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The RF side MAC address for the referenced CM (e.g., the
        interface on the CM that has docsCableMacLayer(127) as
```

```
        its ifType)."
    ::= { docsIfCmtsMacToCmEntry 1 }

docsIfCmtsCmPtr OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "An row index into docsIfCmtsCmStatusTable.  When queried
         with the correct instance value (e.g., a CM's MAC address),
         returns the index in docsIfCmtsCmStatusTable that
         represents that CM."
    ::= { docsIfCmtsMacToCmEntry 2 }

-- The following independent object and associated table
 provide
-- operators with a mechanism to evaluate the load/utilization of
-- both upstream and downstream physical channels.  This information
-- may be used for capacity planning and incident analysis and may
-- be particularly helpful in provisioning of high value QOS.
--
-- Utilization is expressed as an index representing the calculated
-- percentage utilization of the upstream or downstream channel in
-- the most recent sampling interval (i.e., utilization interval).
-- Refer to the DESCRIPTION field of the
-- docsIfCmtsChannelUtUtilization object for definitions and
-- calculation details.

docsIfCmtsChannelUtilizationInterval OBJECT-TYPE
    SYNTAX      Integer32 (0..86400)
    UNITS       "seconds"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The time interval in seconds over which the channel
         utilization index is calculated.  All upstream/downstream
         channels use the same
         docsIfCmtsChannelUtilizationInterval.



          Setting a value of zero disables utilization reporting.
         A channel utilization index is calculated over a fixed
         window applying to the most recent
         docsIfCmtsChannelUtilizationInterval.  It would therefore
         be prudent to use a relatively short
         docsIfCmtsChannelUtilizationInterval.
         It is a vendor decision whether to reset the timer when
```

```
        docsIfCmtsChannelUtilizationInterval is changed during a
        utilization sampling period."
    ::= { docsIfCmtsObjects 8 }

docsIfCmtsChannelUtilizationTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfCmtsChannelUtilizationEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Reports utilization statistics for attached upstream and
        downstream physical channels."
    ::= { docsIfCmtsObjects 9 }

docsIfCmtsChannelUtilizationEntry OBJECT-TYPE
    SYNTAX      DocsIfCmtsChannelUtilizationEntry
    MAX-ACCESS  not-accessible
     STATUS      current
    DESCRIPTION
        "Utilization statistics for a single upstream or downstream
        physical channel.  An entry exists in this table for each
        ifEntry with an ifType equal to
        docsCableDownstream (128)
        or docsCableUpstream (129)."
    INDEX  { ifIndex, docsIfCmtsChannelUtIfType,
        docsIfCmtsChannelUtId }
    ::= { docsIfCmtsChannelUtilizationTable 1 }

DocsIfCmtsChannelUtilizationEntry ::= SEQUENCE {
        docsIfCmtsChannelUtIfType         IANAifType,
        docsIfCmtsChannelUtId             Integer32,
        docsIfCmtsChannelUtUtilization    Integer32
    }

docsIfCmtsChannelUtIfType OBJECT-TYPE
    SYNTAX       IANAifType
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "The secondary index into this table.  Indicates the IANA
        interface type associated with this physical channel.
        Only docsCableDownstream (128) and




        docsCableUpstream
 (129) are valid."
    ::= { docsIfCmtsChannelUtilizationEntry 1 }
```

```
docsIfCmtsChannelUtId OBJECT-TYPE
   SYNTAX       Integer32 (0..255)
   MAX-ACCESS   not-accessible
   STATUS       current
   DESCRIPTION
       "The tertiary index into this table.  Indicates the CMTS
        identifier for this physical channel."
   ::= { docsIfCmtsChannelUtilizationEntry 2 }

docsIfCmtsChannelUtUtilization OBJECT-TYPE
   SYNTAX       Integer32 (0..100)
   UNITS        "percent"
   MAX-ACCESS   read-only
   STATUS       current
   DESCRIPTION
      "The calculated and truncated utilization index for this
       physical upstream or downstream channel, accurate as of
       the most recent docsIfCmtsChannelUtilizationInterval.

       Upstream Channel Utilization Index:

       The upstream channel utilization index is expressed as a
       percentage of mini-slots utilized on the physical channel,
       regardless of burst type.  For an Initial Maintenance
        region, the mini-slots for the complete region are
       considered utilized if the CMTS received an upstream
       burst within the region from any CM on the physical
       channel.  For contention REQ and REQ/DATA regions, the
       mini-slots for a transmission opportunity within the
       region are considered utilized if the CMTS received an
       upstream burst within the opportunity from any CM on the
       physical channel.  For all other regions, utilized
       mini-slots are those in which the CMTS granted
       bandwidth to any unicast SID on the physical channel.

       For an upstream interface that has multiple logical
       upstream channels enabled, the utilization index is a
       weighted sum of utilization indices for the logical
       channels.  The weight for each utilization index is the
       percentage of upstream mini-slots allocated for the
       corresponding logical channel.

     Example:
       If 75% of bandwidth is allocated to the first logical
       channel and 25% to the second, and the utilization
       indices for each are 60 and 40, respectively, the
```

utilization index for the upstream physical channel is
(60 * 0.75) + (40 * 0.25) = 55. This figure
applies to the most recent utilization interval.

Downstream Channel Utilization Index:

The downstream channel utilization index is a percentage
expressing the ratio between bytes used to transmit data
versus the total number of bytes transmitted in the raw
bandwidth of the MPEG channel. As with the upstream
utilization index, the calculated value represents
the most recent utilization interval.
Formula:
Downstream utilization index =
(100 * (data bytes / raw bytes))

Definitions:
Data bytes: Number of bytes transmitted as data in the

docsIfCmtsChannelUtilizationInterval.
Identical to docsIfCmtsDownChannelCtrUsed
Bytes measured over the utilization
interval.
Raw bandwidth: Total number of bytes available for
transmitting data, not including bytes
used for headers and other overhead.
Raw bytes: (raw bandwidth *
docsIfCmtsChannelUtilizationInterval).
Identical to docsIfCmtsDownChannelCtrTotal
Bytes measured over the utilization
interval."
::= { docsIfCmtsChannelUtilizationEntry 3 }

-- The following table provides operators with input data
-- appropriate for calculating downstream channel utilization.
-- Operators may use the docsIfCmtsChannelUtilizationTable or
-- perform their own polling of the
-- docsIfCmtsDownChannelCounterTable objects to characterize
--
their downstream channel usage. The 32-bit counter objects are
-- included to provide backward compatibility with SNMPv1 managers,
-- which cannot access 64-bit counter objects.

docsIfCmtsDownChannelCounterTable OBJECT-TYPE
SYNTAX SEQUENCE OF DocsIfCmtsDownChannelCounterEntry
MAX-ACCESS not-accessible
STATUS current

```
    DESCRIPTION
        "This table is implemented at the CMTS to collect
         downstream channel statistics for utilization




         calculations."
    ::= { docsIfCmtsObjects 10 }

docsIfCmtsDownChannelCounterEntry OBJECT-TYPE
    SYNTAX      DocsIfCmtsDownChannelCounterEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry provides a list of traffic counters for a single
         downstream channel.
         An entry in this table exists for each ifEntry with an
         ifType of docsCableDownstream(128)."
    INDEX { ifIndex }
    ::= { docsIfCmtsDownChannelCounterTable
  1 }

DocsIfCmtsDownChannelCounterEntry ::= SEQUENCE {
        docsIfCmtsDownChnlCtrId             Integer32,
        docsIfCmtsDownChnlCtrTotalBytes     Counter32,
        docsIfCmtsDownChnlCtrUsedBytes      Counter32,
        docsIfCmtsDownChnlCtrExtTotalBytes  Counter64,
        docsIfCmtsDownChnlCtrExtUsedBytes   Counter64
    }

docsIfCmtsDownChnlCtrId OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The Cable Modem Termination System identification
         of the downstream channel within this particular MAC
         interface.  If the interface is down, the object returns
         the most current value.  If the downstream channel ID is
         unknown, this object returns a value of 0."
    ::= { docsIfCmtsDownChannelCounterEntry 1 }

docsIfCmtsDownChnlCtrTotalBytes OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "Bytes"
    MAX-ACCESS  read-only
    STATUS      current
```

```
    DESCRIPTION
      "At the CMTS, the total number of bytes in the Payload
       portion of MPEG Packets (i.e., not including MPEG header
       or pointer_field) transported by this downstream channel.
       This is the 32-bit version of
       docsIfCmtsDownChnlCtrExtTotalBytes, included to provide
       back compatibility with SNMPv1 managers.
       Discontinuities in the value of this counter can occur




       at reinitialization of the managed system, and at other
       times as indicated by the value of
       ifCounterDiscontinuityTime for the associated ifIndex."
  ::= { docsIfCmtsDownChannelCounterEntry 2 }

docsIfCmtsDownChnlCtrUsedBytes OBJECT-TYPE
  SYNTAX     Counter32
  UNITS      "Bytes"
  MAX-ACCESS  read-only
  STATUS     current
  DESCRIPTION
      "At the CMTS, the total number of DOCSIS data bytes
       transported by this downstream channel.
       The number of data bytes is defined as the total
 number
       of bytes transported in DOCSIS payloads minus the number
       of stuff bytes transported in DOCSIS payloads.
       This is the 32-bit version of
       docsIfCmtsDownChnlCtrExtUsedBytes, included to provide
       back compatibility with SNMPv1 managers.
       Discontinuities in the value of this counter can occur
       at reinitialization of the managed system, and at other
       times as indicated by the value of
       ifCounterDiscontinuityTime for the associated ifIndex."
  ::= { docsIfCmtsDownChannelCounterEntry 3 }

docsIfCmtsDownChnlCtrExtTotalBytes OBJECT-TYPE
  SYNTAX     Counter64
  UNITS      "Bytes"
  MAX-ACCESS  read-only
  STATUS     current
  DESCRIPTION
      "At the CMTS, the total number of bytes in the Payload
       portion of MPEG Packets (i.e., not including MPEG header
       or pointer_field) transported by this downstream
       channel.
       This is the 64-bit version of
```

```
        docsIfCmtsDownChnlCtrTotalBytes and will not be
        accessible to SNMPv1 managers.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsDownChannelCounterEntry 4 }

docsIfCmtsDownChnlCtrExtUsedBytes OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "Bytes"
    MAX-ACCESS  read-only



    STATUS      current
    DESCRIPTION
        "At the CMTS, the total number of DOCSIS data bytes
        transported by this downstream channel.  The number
        of data bytes is defined as the total number of bytes
        transported in DOCSIS payloads minus the number of
        stuff bytes transported in DOCSIS payloads.
        This is the 64-bit version of
        docsIfCmtsDownChnlCtrUsedBytes and will not be accessible
        to SNMPv1 managers.
         Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsDownChannelCounterEntry 5 }

-- The following table provides operators with input data appropriate
-- for calculating upstream channel utilization, and for determining
-- the traffic characteristics of upstream channels.  Operators may
-- use the docsIfCmtsChannelUtilizationTable or perform their own
-- polling of the docsIfCmtsUpChannelCounterTable objects for
-- utilization determination.
-- The first four 32 and 64 objects in this table are mandatory.
-- Vendors may choose to implement the remaining optional objects to
-- provide operators with finer characterization of upstream channel
-- traffic patterns.  The 32-bit counter objects are included to
-- provide backward compatibility with SNMPv1 managers, which cannot
-- access
 64-bit counter objects.

docsIfCmtsUpChannelCounterTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfCmtsUpChannelCounterEntry
```

```
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table is implemented at the CMTS to provide upstream
         channel statistics appropriate for channel utilization
         calculations."
    ::= { docsIfCmtsObjects 11 }

docsIfCmtsUpChannelCounterEntry OBJECT-TYPE
    SYNTAX      DocsIfCmtsUpChannelCounterEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "List of traffic statistics for a single upstream channel.
         For DOCSIS 2.0 CMTSs, an entry in this table
         exists for each ifEntry with an ifType of
         docsCableUpstreamChannel (205).



         For DOCSIS 1.x CMTSs, an entry in this table
         exists for each ifEntry with an ifType of
         docsCableUpstream (129)."
    INDEX { ifIndex }
    ::= { docsIfCmtsUpChannelCounterTable 1 }

DocsIfCmtsUpChannelCounterEntry
 ::= SEQUENCE {
       docsIfCmtsUpChnlCtrId                    Integer32,
       docsIfCmtsUpChnlCtrTotalMslots           Counter32,
       docsIfCmtsUpChnlCtrUcastGrantedMslots    Counter32,
       docsIfCmtsUpChnlCtrTotalCntnMslots       Counter32,
       docsIfCmtsUpChnlCtrUsedCntnMslots        Counter32,
       docsIfCmtsUpChnlCtrExtTotalMslots        Counter64,
       docsIfCmtsUpChnlCtrExtUcastGrantedMslots Counter64,
       docsIfCmtsUpChnlCtrExtTotalCntnMslots    Counter64,
       docsIfCmtsUpChnlCtrExtUsedCntnMslots     Counter64,
       docsIfCmtsUpChnlCtrCollCntnMslots        Counter32,
       docsIfCmtsUpChnlCtrTotalCntnReqMslots    Counter32,
       docsIfCmtsUpChnlCtrUsedCntnReqMslots     Counter32,
       docsIfCmtsUpChnlCtrCollCntnReqMslots     Counter32,
       docsIfCmtsUpChnlCtrTotalCntnReqDataMslots Counter32,
       docsIfCmtsUpChnlCtrUsedCntnReqDataMslots
      Counter32,
       docsIfCmtsUpChnlCtrCollCntnReqDataMslots  Counter32,
       docsIfCmtsUpChnlCtrTotalCntnInitMaintMslots Counter32,
       docsIfCmtsUpChnlCtrUsedCntnInitMaintMslots Counter32,
       docsIfCmtsUpChnlCtrCollCntnInitMaintMslots Counter32,
```

```
      docsIfCmtsUpChnlCtrExtCollCntnMslots          Counter64,
      docsIfCmtsUpChnlCtrExtTotalCntnReqMslots      Counter64,
      docsIfCmtsUpChnlCtrExtUsedCntnReqMslots       Counter64,
      docsIfCmtsUpChnlCtrExtCollCntnReqMslots       Counter64,
      docsIfCmtsUpChnlCtrExtTotalCntnReqDataMslots  Counter64,
      docsIfCmtsUpChnlCtrExtUsedCntnReqDataMslots   Counter64,
      docsIfCmtsUpChnlCtrExtCollCntnReqDataMslots   Counter64,
      docsIfCmtsUpChnlCtrExtTotalCntnInitMaintMslots Counter64,
      docsIfCmtsUpChnlCtrExtUsedCntnInitMaintMslots  Counter64,
      docsIfCmtsUpChnlCtrExtCollCntnInitMaintMslots  Counter64
   }

docsIfCmtsUpChnlCtrId
 OBJECT-TYPE
   SYNTAX      Integer32 (0..255)
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The CMTS identification of the upstream channel."
   ::= { docsIfCmtsUpChannelCounterEntry 1 }

docsIfCmtsUpChnlCtrTotalMslots OBJECT-TYPE
   SYNTAX      Counter32



   UNITS       "mini-slots"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "Current count, from CMTS initialization, of all mini-slots
       defined for this upstream logical channel.  This count
       includes all IUCs and SIDs, even those allocated to the
       NULL SID for a 2.0 logical channel that is inactive.  This
       is the 32-bit version of docsIfCmtsUpChnlCtrExtTotalMslots
       and is included for back compatibility with SNMPv1
       managers.  Support for this object is mandatory.
       Discontinuities in the value of this counter can occur
       at reinitialization of the managed system, and at
 other
       times as indicated by the value of
       ifCounterDiscontinuityTime for the associated ifIndex."
   ::= { docsIfCmtsUpChannelCounterEntry 2 }

docsIfCmtsUpChnlCtrUcastGrantedMslots OBJECT-TYPE
   SYNTAX      Counter32
   UNITS       "mini-slots"
   MAX-ACCESS  read-only
```

STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of unicast
granted mini-slots on the upstream logical channel,
regardless of burst type. Unicast granted mini-slots are
those in which the CMTS assigned bandwidth to any unicast
SID on the logical channel. However, this object does not
include minis-lots for reserved IUCs, or grants to SIDs
designated as meaning 'no CM'. This is the 32-bit version
of docsIfCmtsUpChnlCtrExtUcastGrantedMslots, and is
included for back compatibility with SNMPv1 managers.
Support for this object is mandatory.
Discontinuities
in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 3 }

docsIfCmtsUpChnlCtrTotalCntnMslots OBJECT-TYPE
SYNTAX Counter32
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention
mini-slots defined for this upstream logical channel. This
count includes all mini-slots assigned to a broadcast or

multicast SID on the logical channel. This is the 32-bit
version of docsIfCmtsUpChnlCtrExtTotalCntnMslots, and is
included for back compatibility with SNMPv1 managers.
Support for this object is mandatory.
Discontinuities in the value of this counter can occur
at reinitialization of the managed
system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 4 }

docsIfCmtsUpChnlCtrUsedCntnMslots OBJECT-TYPE
SYNTAX Counter32
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"Current count, from CMTS initialization, of contention
mini-slots utilized on the upstream logical channel. For
contention regions, utilized mini-slots are those in which
the CMTS correctly received an upstream burst from any CM
on the upstream logical channel. This is the 32-bit
version of docsIfCmtsUpChnlCtrExtUsedCntnMslots and is
included for back compatibility with SNMPv1 managers.
Support for this object is mandatory.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other

times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 5 }

docsIfCmtsUpChnlCtrExtTotalMslots OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of all mini-slots
defined for this upstream logical channel. This count
includes all IUCs and SIDs, even those allocated to the
NULL SID for a 2.0 logical channel that is inactive. This
is the 64-bit version of docsIfCmtsUpChnlCtrTotalMslots
and will not be accessible to SNMPv1 managers.
Support for this object is mandatory.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated
ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 6 }

docsIfCmtsUpChnlCtrExtUcastGrantedMslots OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of unicast
granted mini-slots on the upstream logical channel,
regardless of burst type. Unicast granted mini-slots are
those in which the CMTS assigned bandwidth to any unicast
SID on the logical channel. However, this object does not

include mini-slots for reserved IUCs, or grants to SIDs
designated as meaning 'no CM'. This is the 64-bit version
of docsIfCmtsUpChnlCtrUcastGrantedMslots and will not be
accessible to SNMPv1 managers.
Support for this object is mandatory.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other

times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 7 }

docsIfCmtsUpChnlCtrExtTotalCntnMslots OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention
mini-slots defined for this upstream logical channel. This
count includes all mini-slots assigned to a broadcast or
multicast SID on the logical channel. This is the 64-bit
version of docsIfCmtsUpChnlCtrTotalCntnMslots and will
not be accessible to SNMPv1 managers.
Support for this object is mandatory.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."

::= { docsIfCmtsUpChannelCounterEntry 8 }

docsIfCmtsUpChnlCtrExtUsedCntnMslots OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention

mini-slots utilized on the upstream logical channel. For
contention regions, utilized mini-slots are those in which
the CMTS correctly received an upstream burst from any CM
on the upstream logical channel. This is the 64-bit
version of docsIfCmtsUpChnlCtrUsedCntnMslots and will not
be accessible to SNMPv1 managers.

```
        Support for this object is mandatory.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry
 9 }

docsIfCmtsUpChnlCtrCollCntnMslots OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Current count, from CMTS initialization, of contention
        mini-slots subjected to collisions on the upstream logical
        channel.  For contention regions, these are the mini-slots
        applicable to bursts that the CMTS detected but could not
        correctly receive.  This is the 32-bit version of
        docsIfCmtsUpChnlCtrExtCollCntnMslots and is included for
        back compatibility with SNMPv1 managers.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry 10 }

docsIfCmtsUpChnlCtrTotalCntnReqMslots OBJECT-TYPE
    SYNTAX      Counter32

  UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Current count, from CMTS initialization, of contention
        request mini-slots defined for this upstream logical
        channel.  This count includes all mini-slots for IUC1
        assigned to a broadcast or multicast SID on the logical
        channel.  This is the 32-bit version of
        docsIfCmtsUpChnlCtrExtTotalCntnReqMslots and is included
        for back compatibility with SNMPv1 managers.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of



        ifCounterDiscontinuityTime for the associated ifIndex."
```

```
    ::= { docsIfCmtsUpChannelCounterEntry 11 }

docsIfCmtsUpChnlCtrUsedCntnReqMslots OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION

    "Current count, from CMTS initialization, of contention
        request mini-slots utilized on this upstream logical
        channel.  This count includes all contention mini-slots for
        IUC1 applicable to bursts that the CMTS correctly
        received.  This is the 32-bit version of
        docsIfCmtsUpChnlCtrExtUsedCntnReqMslots and is included
        for back compatibility with SNMPv1 managers.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry 12 }

docsIfCmtsUpChnlCtrCollCntnReqMslots OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       "Current count, from CMTS initialization, of contention
        request mini-slots subjected to collisions
 on this upstream
        logical channel.  This includes all contention mini-slots
        for IUC1 applicable to bursts that the CMTS detected but
        could not correctly receive.  This is the 32-bit version of
        docsIfCmtsUpChnlCtrExtCollCntnReqMslots and is included
        for back compatibility with SNMPv1 managers.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry 13 }

docsIfCmtsUpChnlCtrTotalCntnReqDataMslots OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
```

"Current count, from CMTS initialization, of contention

request data mini-slots defined for this upstream logical
channel. This count includes all
mini-slots for IUC2
assigned to a broadcast or multicast SID on the logical
channel. This is the 32-bit version of
docsIfCmtsUpChnlCtrExtTotalCntnReqDataMslots and is
included for back compatibility with SNMPv1 managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 14 }

docsIfCmtsUpChnlCtrUsedCntnReqDataMslots OBJECT-TYPE
SYNTAX Counter32
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention
request data mini-slots utilized on this upstream logical
channel. This includes all contention mini-slots for IUC2
applicable to bursts that the CMTS correctly received.

This is the 32-bit version of
docsIfCmtsUpChnlCtrExtUsedCntnReqDataMslots and is
included for back compatibility with SNMPv1 managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 15 }

docsIfCmtsUpChnlCtrCollCntnReqDataMslots OBJECT-TYPE
SYNTAX Counter32
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention
request data mini-slots subjected to collisions on this
upstream logical channel. This includes all contention
mini-slots for IUC2 applicable to bursts that the CMTS
detected, but could not correctly receive. This is the

32-bit version of
docsIfCmtsUpChnlCtrExtCollCntnReqDataMslots
and is
included for back compatibility with SNMPv1 managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of

ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 16 }

docsIfCmtsUpChnlCtrTotalCntnInitMaintMslots OBJECT-TYPE
SYNTAX Counter32
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention
initial maintenance mini-slots defined for this upstream
logical channel. This includes all mini-slots for IUC3
assigned to a broadcast or multicast SID on the logical
channel. This is the 32-bit version of
docsIfCmtsUpChnlCtrExtTotalCntnInitMaintMslots
and is included for back compatibility
with SNMPv1
managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 17 }

docsIfCmtsUpChnlCtrUsedCntnInitMaintMslots OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention
initial maintenance mini-slots utilized on this upstream
logical channel. This includes all contention mini-slots
for IUC3 applicable to bursts that the CMTS correctly
received. This is the 32-bit version of
docsIfCmtsUpChnlCtrExtUsedCntnInitMaintMslots
and is included for back compatibility with SNMPv1
managers.
Discontinuities in the value of this counter can occur

at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 18 }

docsIfCmtsUpChnlCtrCollCntnInitMaintMslots OBJECT-TYPE
SYNTAX Counter32
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"Current count, from CMTS initialization, of contention
initial maintenance mini-slots subjected to collisions on
this upstream logical channel. This includes all
contention mini-slots for IUC3 applicable to bursts that
the CMTS detected, but could not correctly receive.
This is the 32-bit version of
docsIfCmtsUpChnlCtrExtCollCntnInitMaintMslots
and is included for back compatibility with SNMPv1
managers.
Discontinuities in the value of this counter can occur
at reinitialization
of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 19 }

docsIfCmtsUpChnlCtrExtCollCntnMslots OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of collision
contention mini-slots on the upstream logical channel.
For contention regions, these are the mini-slots applicable
to bursts that the CMTS detected, but could not correctly
receive. This is the 64-bit version of
docsIfCmtsUpChnlCtrCollCntnMslots and will not be
accessible to SNMPv1 managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime

```
 for the associated ifIndex."
   ::= { docsIfCmtsUpChannelCounterEntry 20 }

docsIfCmtsUpChnlCtrExtTotalCntnReqMslots OBJECT-TYPE
   SYNTAX      Counter64
   UNITS       "mini-slots"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "Current count, from CMTS initialization, of contention
       request mini-slots defined for this upstream logical
       channel.  This count includes all mini-slots for IUC1
       assigned to a broadcast or multicast SID on the logical
       channel.  This is the 64-bit version of
       docsIfCmtsUpChnlCtrTotalCntnReqMslots and will not be
       accessible to SNMPv1 managers.
       Discontinuities in the value of this counter can occur



       at reinitialization of the managed system, and at other
       times as indicated by the value of
       ifCounterDiscontinuityTime for the associated ifIndex."
   ::= { docsIfCmtsUpChannelCounterEntry 21 }

docsIfCmtsUpChnlCtrExtUsedCntnReqMslots
 OBJECT-TYPE
   SYNTAX      Counter64
   UNITS       "mini-slots"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "Current count, from CMTS initialization, of contention
       request mini-slots utilized on this upstream logical
       channel.  This count includes all contention mini-slots for
       IUC1 applicable to bursts that the CMTS correctly
       received.  This is the 64-bit version of
       docsIfCmtsUpChnlCtrUsedCntnReqMslots and will not be
       accessible to SNMPv1 managers.
       Discontinuities in the value of this counter can occur
       at reinitialization of the managed system, and at other
       times as indicated by the value of
       ifCounterDiscontinuityTime for the associated ifIndex."
   ::= { docsIfCmtsUpChannelCounterEntry 22 }

docsIfCmtsUpChnlCtrExtCollCntnReqMslots OBJECT-TYPE
   SYNTAX      Counter64
   UNITS       "mini-slots"
```

```
    MAX-ACCESS  read-only
    STATUS
     current
    DESCRIPTION
       "Current count, from CMTS initialization, of contention
        request mini-slots subjected to collisions on this upstream
        logical channel.  This includes all contention mini-slots
        for IUC1 applicable to bursts that the CMTS detected,
        but could not correctly receive.  This is the 64-bit
        version of docsIfCmtsUpChnlCtrCollCntnReqMslots and will
        not be accessible to SNMPv1 managers.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry 23 }

docsIfCmtsUpChnlCtrExtTotalCntnReqDataMslots OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current



    DESCRIPTION
       "Current count, from CMTS initialization,
 of contention
        request data mini-slots defined for this upstream logical
        channel.  This count includes all mini-slots for IUC2
        assigned to a broadcast or multicast SID on the logical
        channel.  This is the 64-bit version of
        docsIfCmtsUpChnlCtrTotalCntnReqDataMslots and will not be
        accessible to SNMPv1 managers.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry 24 }

docsIfCmtsUpChnlCtrExtUsedCntnReqDataMslots OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       "Current count, from CMTS initialization, of contention
        request data mini-slots utilized on this upstream logical
```

channel. This
includes all contention mini-slots for IUC2
applicable to bursts that the CMTS correctly received.
This is the 64-bit version of
docsIfCmtsUpChnlCtrUsedCntnReqDataMslots and will not be
accessible to SNMPv1 managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 25 }

docsIfCmtsUpChnlCtrExtCollCntnReqDataMslots OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention
request data mini-slots subjected to collisions on this
upstream logical channel. This includes all contention
mini-slots for IUC2 applicable to bursts that the CMTS

detected, but could not correctly receive. This is the
64-bit version of
docsIfCmtsUpChnlCtrCollCntnReqDataMslots
and will not be accessible to SNMPv1 managers.
Discontinuities in the value of this counter can occur

at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 26 }

docsIfCmtsUpChnlCtrExtTotalCntnInitMaintMslots OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of initial
maintenance mini-slots defined for this upstream logical
channel. This count includes all mini-slots for IUC3
assigned to a broadcast or multicast SID on the logical
channel. This is the 64-bit version of
docsIfCmtsUpChnlCtrTotalCntnInitMaintMslots

```
        and will not be accessible to SNMPv1 managers.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry 27 }

docsIfCmtsUpChnlCtrExtUsedCntnInitMaintMslots OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Current count, from CMTS initialization, of initial
        maintenance mini-slots utilized on this upstream logical
        channel.  This includes all contention mini-slots for IUC3
        applicable to bursts that the CMTS correctly received.
        This is the 64-bit version of
        docsIfCmtsUpChnlCtrUsedCntnInitMaintMslots
        and will not be accessible to SNMPv1 managers.
        Discontinuities
 in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry 28 }

docsIfCmtsUpChnlCtrExtCollCntnInitMaintMslots OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current



    DESCRIPTION
        "Current count, from CMTS initialization, of contention
        initial maintenance mini-slots subjected to collisions on
        this upstream logical channel.  This includes all
        contention mini-slots for IUC3 applicable to bursts that
        the CMTS detected, but could not correctly receive.
        This is the 64-bit version of
        docsIfCmtsUpChnlCtrCollCntnInitMaintMslots and will not
        be accessible to SNMPv1 managers.
        Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
```

```
    ::= { docsIfCmtsUpChannelCounterEntry 29 }

--
-- notification group is for future extension.
--

docsIfNotification OBJECT IDENTIFIER     ::= { docsIfMib 2 }

--
-- MIB Compliance statements.
--


--
-- Conformance definitions
--

docsIfConformance  OBJECT IDENTIFIER     ::= { docsIfMib 3 }
docsIfCompliances  OBJECT IDENTIFIER     ::= { docsIfConformance 1 }
docsIfGroups       OBJECT IDENTIFIER     ::= { docsIfConformance 2 }

docsIfBasicCompliance MODULE-COMPLIANCE
    STATUS      deprecated
    DESCRIPTION
        "The compliance statement for devices that implement
         DOCSIS 1.x compliant Radio Frequency Interfaces."

MODULE  -- docsIfMib

-- unconditionally mandatory groups
MANDATORY-GROUPS {
    docsIfBasicGroup
    }

-- conditionally mandatory group
GROUP docsIfCmGroup



    DESCRIPTION
        "This group is implemented only in cable modems, not in
        cable modem termination systems."

-- conditionally mandatory group
GROUP docsIfCmtsGroup
    DESCRIPTION
        "This group is implemented only in cable modem termination
         systems, not in cable modems."
```

```
OBJECT  docsIfDownChannelFrequency
   WRITE-SYNTAX Integer32 (54000000..860000000)
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-write in cable modem termination systems;
       read-only in cable modems.  The values above are
       appropriate for a cable plant using a Sub-Split channel
       plan.  If DOCSIS is extended to cover other types of
       channel plans (and frequency allocations), this object
       will be modified accordingly."

OBJECT  docsIfDownChannelWidth
   WRITE-SYNTAX Integer32 (6000000)
   MIN-ACCESS  read-only
   DESCRIPTION
      "It is important to implement this object as read-only.
       In cable modems, this object is always
 implemented as
       read-only.  The above value is appropriate for cable
       plants running under NTSC (National Television
       Standards Committee) standards.  If DOCSIS is extended to
       work with other standards (e.g., European standards), this
       object will be modified accordingly."

OBJECT  docsIfDownChannelModulation
   WRITE-SYNTAX INTEGER {
                  qam64 (3),
                  qam256 (4)
                 }
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-write in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfDownChannelInterleave
   WRITE-SYNTAX INTEGER {
           taps8Increment16(3),
           taps16Increment8(4),
           taps32Increment4(5),



           taps64Increment2(6),
           taps128Increment1(7)
            }
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-write in cable modem termination
```

systems;
read-only in cable modems."

OBJECT docsIfDownChannelPower
MIN-ACCESS read-only
DESCRIPTION
"Read-write in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfUpChannelFrequency
WRITE-SYNTAX Integer32 (5000000..42000000)
MIN-ACCESS read-only
DESCRIPTION
"Read-write in cable modem termination systems;
read-only in cable modems. The values above are
appropriate for a cable plant using a Sub-Split channel
plan. If DOCSIS is extended to cover other types of
channel plans (and frequency allocations), this object
will be modified accordingly."

OBJECT docsIfUpChannelWidth
WRITE-SYNTAX Integer32 (200000..3200000)
MIN-ACCESS read-only
DESCRIPTION
"Read-write in cable modem termination systems;
read-only in cable modems. The above value is appropriate
for cable plants running under NTSC (National Television
Standards Committee) standards. If DOCSIS is extended to
work with other standards (e.g., European standards), this
object will be modified accordingly."

OBJECT docsIfUpChannelModulationProfile
MIN-ACCESS read-only
DESCRIPTION
"Read-write in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfUpChannelSlotSize
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfUpChannelRangingBackoffStart
MIN-ACCESS read-only

DESCRIPTION
"Read-write in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfUpChannelRangingBackoffEnd
MIN-ACCESS read-only
DESCRIPTION
"Read-write in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfUpChannelTxBackoffStart
MIN-ACCESS read-only
DESCRIPTION
"Read-write in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfUpChannelTxBackoffEnd
MIN-ACCESS read-only
DESCRIPTION
"Read-write in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfQosProfPriority
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfQosProfMaxUpBandwidth
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfQosProfGuarUpBandwidth
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant
to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfQosProfMaxDownBandwidth
MIN-ACCESS read-only
DESCRIPTION

"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfQosProfMaxTxBurst
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfQosProfBaselinePrivacy
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfQosProfStatus
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant
to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfCmtsServiceAdminStatus
MIN-ACCESS read-only
DESCRIPTION
"It is compliant to implement this object as read-only."

OBJECT docsIfCmtsSyncInterval
MIN-ACCESS read-only
DESCRIPTION
"It is compliant to implement this object as read-only."

OBJECT docsIfCmtsUcdInterval
MIN-ACCESS read-only
DESCRIPTION
"It is compliant to implement this object as read-only."

OBJECT docsIfCmtsInsertInterval
MIN-ACCESS read-only
DESCRIPTION
"It is compliant to implement this object as read-only."

```
OBJECT  docsIfCmtsInvitedRangingAttempts
   MIN-ACCESS  read-only
   DESCRIPTION



       "It is compliant to implement this object as read-only."

OBJECT  docsIfCmtsQosProfilePermissions
   WRITE-SYNTAX     BITS {
      createByManagement(0),
      updateByManagement(1)
     }
   MIN-ACCESS  read-only
   DESCRIPTION
       "It is compliant to implement this object as read-only."

OBJECT docsIfCmtsModType
   WRITE-SYNTAX INTEGER {
                qpsk (2),
                qam16 (3)
                 }
   DESCRIPTION
      "A management station MAY only set 16QAM or QPSK modulation,
       but others might be possible, based on device
       configuration."

OBJECT  docsIfCmtsModPreambleLen
   SYNTAX Integer32 (0..1024)
   DESCRIPTION
      "The range of the values for this MODULE-COMPLIANCE
       is 0..1024."

OBJECT  docsIfCmtsModFECErrorCorrection
      SYNTAX Integer32 (0..10)
      DESCRIPTION
         "The range of the values for this MODULE-COMPLIANCE
          is 0..10."

   ::= { docsIfCompliances 1 }

docsIfBasicComplianceV2 MODULE-COMPLIANCE
   STATUS      current
   DESCRIPTION
      "The compliance statement for devices that implement
       DOCSIS 2.0 Radio Frequency Interfaces."

MODULE  -- docsIfMib
```

```
-- unconditionally
 mandatory groups
MANDATORY-GROUPS {
   docsIfBasicGroupV2
   }



-- conditionally mandatory group
GROUP docsIfCmGroupV2
   DESCRIPTION
      "This group is implemented only in cable modems, not in
       cable modem termination systems."

-- conditionally mandatory group
GROUP docsIfCmtsGroupV2
   DESCRIPTION
      "This group is implemented only in cable modem termination
       systems, not in cable modems."


OBJECT  docsIfDownChannelFrequency
   WRITE-SYNTAX Integer32 (47000000..862000000)
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-write in cable modem termination systems;
       read-only in cable modems.
       A range of 54MHz to 860MHz is appropriate for a cable
       plant using a North American Sub-Split channel plan.
       The spectrum range has been expanded to accommodate
       a lower edge of 47MHz and an upper edge of 862MHz
       for some European channel plans.
       If DOCSIS is extended to cover other
 types of channel
       plans (and frequency allocations), this object will be
       modified accordingly."

OBJECT  docsIfDownChannelWidth
   WRITE-SYNTAX Integer32 (6000000 | 8000000)
   MIN-ACCESS  read-only
   DESCRIPTION
      "It is important to implement this object as read-only.
       In cable modems, this object is always implemented as
       read-only.  The value of 6 MHz is appropriate for cable
       plants running under NTSC (National Television
       Standards Committee) standards.  The value of 8 MHz is
```

```
        appropriate for cable plants running under ETSI
        standards.  For other regional standards, this
        object will be modified accordingly."

OBJECT  docsIfDownChannelModulation
   WRITE-SYNTAX INTEGER {
                    qam64 (3),
                    qam256 (4)
                  }
   MIN-ACCESS  read-only
   DESCRIPTION



       "Read-write in cable modem termination systems;

      read-only in cable modems."

OBJECT  docsIfDownChannelInterleave
   WRITE-SYNTAX INTEGER {
            taps8Increment16(3),
            taps16Increment8(4),
            taps32Increment4(5),
            taps64Increment2(6),
            taps128Increment1(7),
            taps12increment17(8)
             }
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-write in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfDownChannelPower
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-write in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelFrequency
   WRITE-SYNTAX Integer32 (5000000..65000000)
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems.
       A range of 5MHz to 42MHz is appropriate for a cable
       plant using a North American Sub-Split channel plan.
        The spectrum range has been expanded to accommodate
       an upper edge of 65MHz for some European channel plans.
```

If DOCSIS is extended to cover other types of channel
plans (and frequency allocations), this object will
be modified accordingly."

OBJECT docsIfUpChannelWidth
WRITE-SYNTAX Integer32 (200000..6400000)
MIN-ACCESS read-only
DESCRIPTION
"Read-create in cable modem termination systems,
read-only in cable modems. The above value is appropriate
for cable plants running under NTSC (National Television
Standards Committee) standards. If DOCSIS is extended to
work with other standards (e.g., European standards), this
object will be modified accordingly."

OBJECT docsIfUpChannelModulationProfile
MIN-ACCESS read-only
DESCRIPTION
"Read-create in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfUpChannelSlotSize
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfUpChannelRangingBackoffStart
MIN-ACCESS read-only
DESCRIPTION
"Read-create in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfUpChannelRangingBackoffEnd
MIN-ACCESS read-only
DESCRIPTION
"Read-create in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfUpChannelTxBackoffStart
MIN-ACCESS read-only
DESCRIPTION
"Read-create in cable modem termination systems;
read-only in cable modems."

```
OBJECT  docsIfUpChannelTxBackoffEnd
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelScdmaActiveCodes
   MIN-ACCESS
 read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems.
       The number of active codes when SCDMA is in use MUST range
       from 64 to 128 and MUST be a non-Prime value.
       Providing this range allows for the following features
       and capabilities:
         1) Power management in S-CDMA spreader-on frames
           (with a 3 dB spread).



         2) Avoidance of code 0.
         3) Flexible mini-slot sizes with and without the use of
           code 0."

OBJECT  docsIfUpChannelScdmaCodesPerSlot
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelScdmaFrameSize
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelScdmaHoppingSeed
   MIN-ACCESS  read-only
    DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelCloneFrom
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
```

read-only in cable modems."

OBJECT docsIfUpChannelUpdate
MIN-ACCESS read-only
DESCRIPTION
"Read-create in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfUpChannelStatus
MIN-ACCESS read-only
DESCRIPTION
"Read-create in Cable Modem Termination Systems;
read-only in Cable Modems.
Entries associated to physical interfaces only support
the read-only value 'active'."

OBJECT docsIfUpChannelPreEqEnable
MIN-ACCESS read-only
DESCRIPTION
"Read-create in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfQosProfPriority
MIN-ACCESS read-only

DESCRIPTION
"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfQosProfMaxUpBandwidth
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfQosProfGuarUpBandwidth
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfQosProfMaxDownBandwidth

```
    MIN-ACCESS  read-only
    DESCRIPTION
        "This object is always read-only in cable modems.
         It is compliant to implement this object as read-only
         in cable modem termination systems."

OBJECT  docsIfQosProfBaselinePrivacy
    MIN-ACCESS  read-only
     DESCRIPTION
        "This object is always read-only in cable modems.
         It is compliant to implement this object as read-only
         in cable modem termination systems."

OBJECT  docsIfQosProfStatus
    MIN-ACCESS  read-only
    DESCRIPTION
        "This object is always read-only in cable modems.
         It is compliant to implement this object as read-only
         in cable modem termination systems."

OBJECT  docsIfQosProfMaxTransmitBurst
    MIN-ACCESS  read-only
    DESCRIPTION
        "This object is always read-only in cable modems.
         It is compliant to implement this object as read-only
         in cable modem termination systems."



OBJECT  docsIfCmRangingTimeout
    MIN-ACCESS  read-only
    DESCRIPTION
        "It is compliant to implement this object as read-only."

OBJECT docsIfCmStatusModulationType
   SYNTAX         INTEGER {
      unknown(0),
      tdma(1),
      atdma(2),
      scdma(3)
   }
    DESCRIPTION

    "CM does not use both modulation burst profiles of a
        'tdmAndAtdma' ChannelType; therefore, 'tdmAndAtdma'is
        not supported."

OBJECT  docsIfCmtsServiceAdminStatus
```

```
    MIN-ACCESS  read-only
    DESCRIPTION
        "It is compliant to implement this object as read-only."

OBJECT  docsIfCmtsSyncInterval
    MIN-ACCESS  read-only
    DESCRIPTION
        "It is compliant to implement this object as read-only."

OBJECT  docsIfCmtsUcdInterval
    MIN-ACCESS  read-only
    DESCRIPTION
        "It is compliant to implement this object as read-only."

OBJECT  docsIfCmtsInsertInterval
    MIN-ACCESS  read-only
    DESCRIPTION
        "It is compliant to implement this object as read-only."

OBJECT  docsIfCmtsInvitedRangingAttempts
    MIN-ACCESS  read-only
    DESCRIPTION
        "It is compliant to implement this object as read-only."

OBJECT  docsIfCmtsQosProfilePermissions
    WRITE-SYNTAX     BITS {
        createByManagement(0),
        updateByManagement(1)
        }
    MIN-ACCESS  read-only



    DESCRIPTION
        "It is compliant to implement this object as read-only."

OBJECT docsIfCmtsModType
    WRITE-SYNTAX      INTEGER {
        qpsk(2),
        qam16(3),
        qam64(6)
    }
    DESCRIPTION
        "A management station MAY only set 64QAM, 16QAM, or QPSK
         modulation for Time or Code division Multiple Access,
         but others might be possible based on device
         configuration."
```

```
OBJECT docsIfCmtsCmStatusModulationType
  SYNTAX        INTEGER {
     unknown(0),
     tdma(1),
     atdma(2),
     scdma(3)
  }
   DESCRIPTION
      "CM does not use both modulation burst profiles of a
       'tdmAndAtdma' ChannelType; therefore, 'tdmAndAtdma'is
       not supported."

   ::= { docsIfCompliances 2 }

docsIfBasicGroup OBJECT-GROUP
   OBJECTS {
      docsIfDownChannelId,
      docsIfDownChannelFrequency,
      docsIfDownChannelWidth,
      docsIfDownChannelModulation,
       docsIfDownChannelInterleave,
      docsIfDownChannelPower,
      docsIfUpChannelId,
      docsIfUpChannelFrequency,
      docsIfUpChannelWidth,
      docsIfUpChannelModulationProfile,
      docsIfUpChannelSlotSize,
      docsIfUpChannelTxTimingOffset,
      docsIfUpChannelRangingBackoffStart,
      docsIfUpChannelRangingBackoffEnd,
      docsIfUpChannelTxBackoffStart,
      docsIfUpChannelTxBackoffEnd,
      docsIfQosProfPriority,



      docsIfQosProfMaxUpBandwidth,
      docsIfQosProfGuarUpBandwidth,
      docsIfQosProfMaxDownBandwidth,
      docsIfQosProfMaxTxBurst,
      docsIfQosProfBaselinePrivacy,
      docsIfQosProfStatus,
      docsIfSigQIncludesContention,
      docsIfSigQUnerroreds,
      docsIfSigQCorrecteds,
      docsIfSigQUncorrectables,
      docsIfSigQSignalNoise,
      docsIfSigQMicroreflections,
```

```
        docsIfSigQEqualizationData
    }
    STATUS      deprecated
    DESCRIPTION
        "Group of objects implemented in both cable modems and
        cable modem termination systems."
    ::= { docsIfGroups 1 }

docsIfCmGroup OBJECT-GROUP
    OBJECTS {
        docsIfCmCmtsAddress,
        docsIfCmCapabilities,
        docsIfCmRangingTimeout,
        docsIfCmStatusValue,
        docsIfCmStatusCode,
        docsIfCmStatusTxPower,
        docsIfCmStatusResets,
        docsIfCmStatusLostSyncs,
        docsIfCmStatusInvalidMaps,
        docsIfCmStatusInvalidUcds,
        docsIfCmStatusInvalidRangingResponses,
        docsIfCmStatusInvalidRegistrationResponses,
        docsIfCmStatusT1Timeouts,
        docsIfCmStatusT2Timeouts,
        docsIfCmStatusT3Timeouts,
        docsIfCmStatusT4Timeouts,
        docsIfCmStatusRangingAborteds,
        docsIfCmServiceQosProfile,
        docsIfCmServiceTxSlotsImmed,
        docsIfCmServiceTxSlotsDed,
        docsIfCmServiceTxRetries,
        docsIfCmServiceTxExceededs,
        docsIfCmServiceRqRetries,
        docsIfCmServiceRqExceededs
    }
    STATUS      deprecated



    DESCRIPTION
        "Group of objects implemented in cable modems."
    ::= { docsIfGroups 2 }

docsIfCmtsGroup OBJECT-GROUP
    OBJECTS {
        docsIfCmtsCapabilities,
        docsIfCmtsSyncInterval,
        docsIfCmtsUcdInterval,
```

```
    docsIfCmtsMaxServiceIds,
    docsIfCmtsInvitedRangingAttempts,
    docsIfCmtsInsertInterval,
    docsIfCmtsStatusInvalidRangeReqs,
    docsIfCmtsStatusRangingAborteds,
    docsIfCmtsStatusInvalidRegReqs,
    docsIfCmtsStatusFailedRegReqs,
    docsIfCmtsStatusInvalidDataReqs,
    docsIfCmtsStatusT5Timeouts,
    docsIfCmtsCmStatusMacAddress,
    docsIfCmtsCmStatusIpAddress,
    docsIfCmtsCmStatusDownChannelIfIndex,
    docsIfCmtsCmStatusUpChannelIfIndex,
    docsIfCmtsCmStatusRxPower,
    docsIfCmtsCmStatusTimingOffset,
    docsIfCmtsCmStatusEqualizationData,
    docsIfCmtsCmStatusValue,
     docsIfCmtsCmStatusUnerroreds,
    docsIfCmtsCmStatusCorrecteds,
    docsIfCmtsCmStatusUncorrectables,
    docsIfCmtsCmStatusSignalNoise,
    docsIfCmtsCmStatusMicroreflections,
    docsIfCmtsServiceCmStatusIndex,
    docsIfCmtsServiceAdminStatus,
    docsIfCmtsServiceQosProfile,
    docsIfCmtsServiceCreateTime,
    docsIfCmtsServiceInOctets,
    docsIfCmtsServiceInPackets,
    docsIfCmtsModType,
    docsIfCmtsModControl,
    docsIfCmtsModPreambleLen,
    docsIfCmtsModDifferentialEncoding,
    docsIfCmtsModFECErrorCorrection,
    docsIfCmtsModFECCodewordLength,
    docsIfCmtsModScramblerSeed,
    docsIfCmtsModMaxBurstSize,
    docsIfCmtsModGuardTimeSize,
    docsIfCmtsModLastCodewordShortened,
    docsIfCmtsModScrambler,



    docsIfCmtsQosProfilePermissions,
    docsIfCmtsCmPtr
  }
  STATUS      deprecated
  DESCRIPTION
    "Group of objects
```

```
 implemented in Cable Modem Termination
        Systems."
    ::= { docsIfGroups 3 }

-- obsolete group
-- RFC 2670 already had a obsolete group, even though RFC2670
-- was the first version of this MIB Module.

docsIfObsoleteGroup OBJECT-GROUP
    OBJECTS {
        docsIfCmRangingRespTimeout,
        docsIfCmtsInsertionInterval
    }
    STATUS      obsolete
    DESCRIPTION
        "Group of objects obsoleted."
    ::= { docsIfGroups 4 }

docsIfBasicGroupV2 OBJECT-GROUP
    OBJECTS {
        docsIfDownChannelId,
        docsIfDownChannelFrequency,
        docsIfDownChannelWidth,
        docsIfDownChannelModulation,
        docsIfDownChannelInterleave,
        docsIfDownChannelPower,
        docsIfDownChannelAnnex,
        docsIfUpChannelId,
        docsIfUpChannelFrequency,
        docsIfUpChannelWidth,
        docsIfUpChannelModulationProfile,
        docsIfUpChannelSlotSize,
        docsIfUpChannelTxTimingOffset,
        docsIfUpChannelRangingBackoffStart,
         docsIfUpChannelRangingBackoffEnd,
        docsIfUpChannelTxBackoffStart,
        docsIfUpChannelTxBackoffEnd,
        docsIfUpChannelScdmaActiveCodes,
        docsIfUpChannelScdmaCodesPerSlot,
        docsIfUpChannelScdmaFrameSize,
        docsIfUpChannelScdmaHoppingSeed,
        docsIfUpChannelType,
        docsIfUpChannelCloneFrom,



        docsIfUpChannelUpdate,
        docsIfUpChannelStatus,
```

```
        docsIfUpChannelPreEqEnable,
        docsIfQosProfPriority,
        docsIfQosProfMaxUpBandwidth,
        docsIfQosProfGuarUpBandwidth,
        docsIfQosProfMaxDownBandwidth,
        docsIfQosProfBaselinePrivacy,
        docsIfQosProfStatus,
        docsIfQosProfMaxTransmitBurst,
        docsIfSigQIncludesContention,
        docsIfSigQUnerroreds,
        docsIfSigQCorrecteds,
        docsIfSigQUncorrectables,
        docsIfSigQSignalNoise,
        docsIfSigQMicroreflections,
        docsIfSigQExtUnerroreds,
        docsIfSigQExtCorrecteds,
        docsIfSigQExtUncorrectables,
        docsIfDocsisBaseCapability
    }
    STATUS      current
    DESCRIPTION
        "Group of objects implemented in both cable modems and
         cable modem termination systems."
    ::= { docsIfGroups 5 }

docsIfCmGroupV2 OBJECT-GROUP
    OBJECTS {
        docsIfCmCmtsAddress,
        docsIfCmCapabilities,
        docsIfCmRangingTimeout,
        docsIfCmStatusValue,
        docsIfCmStatusCode,
        docsIfCmStatusTxPower,
        docsIfCmStatusResets,
        docsIfCmStatusLostSyncs,
        docsIfCmStatusInvalidMaps,
        docsIfCmStatusInvalidUcds,
        docsIfCmStatusInvalidRangingResponses,
        docsIfCmStatusInvalidRegistrationResponses,
        docsIfCmStatusT1Timeouts,
        docsIfCmStatusT2Timeouts,
        docsIfCmStatusT3Timeouts,
        docsIfCmStatusT4Timeouts,
        docsIfCmStatusRangingAborteds,
        docsIfCmStatusDocsisOperMode,
        docsIfCmStatusModulationType,
```

```
        docsIfCmStatusEqualizationData,
         docsIfCmStatusUCCs,
        docsIfCmStatusUCCFails,
        docsIfCmServiceQosProfile,
        docsIfCmServiceTxSlotsImmed,
        docsIfCmServiceTxSlotsDed,
        docsIfCmServiceTxRetries,
        docsIfCmServiceTxExceededs,
        docsIfCmServiceRqRetries,
        docsIfCmServiceRqExceededs,
        docsIfCmServiceExtTxSlotsImmed,
        docsIfCmServiceExtTxSlotsDed,
        docsIfSigQEqualizationData
    }
    STATUS      current
    DESCRIPTION
        "Group of objects implemented in cable modems."
    ::= { docsIfGroups 6 }

docsIfCmtsGroupV2 OBJECT-GROUP
    OBJECTS {
        docsIfCmtsCapabilities,
        docsIfCmtsSyncInterval,
        docsIfCmtsUcdInterval,
        docsIfCmtsMaxServiceIds,
        docsIfCmtsInvitedRangingAttempts,
        docsIfCmtsInsertInterval,
        docsIfCmtsMacStorageType,
        docsIfCmtsStatusInvalidRangeReqs,
        docsIfCmtsStatusRangingAborteds,
        docsIfCmtsStatusInvalidRegReqs,
         docsIfCmtsStatusFailedRegReqs,
        docsIfCmtsStatusInvalidDataReqs,
        docsIfCmtsStatusT5Timeouts,
        docsIfCmtsCmStatusMacAddress,
        docsIfCmtsCmStatusDownChannelIfIndex,
        docsIfCmtsCmStatusUpChannelIfIndex,
        docsIfCmtsCmStatusRxPower,
        docsIfCmtsCmStatusTimingOffset,
        docsIfCmtsCmStatusEqualizationData,
        docsIfCmtsCmStatusValue,
        docsIfCmtsCmStatusUnerroreds,
        docsIfCmtsCmStatusCorrecteds,
        docsIfCmtsCmStatusUncorrectables,
        docsIfCmtsCmStatusSignalNoise,
        docsIfCmtsCmStatusMicroreflections,
        docsIfCmtsCmStatusExtUnerroreds,
```

docsIfCmtsCmStatusExtCorrecteds,

docsIfCmtsCmStatusExtUncorrectables,
docsIfCmtsCmStatusDocsisRegMode,
docsIfCmtsCmStatusModulationType,
docsIfCmtsCmStatusInetAddressType,
docsIfCmtsCmStatusInetAddress,
docsIfCmtsCmStatusValueLastUpdate,
docsIfCmtsCmStatusHighResolutionTimingOffset,
docsIfCmtsServiceAdminStatus,
docsIfCmtsServiceQosProfile,
docsIfCmtsServiceCreateTime,
docsIfCmtsServiceInOctets,
docsIfCmtsServiceInPackets,
docsIfCmtsServiceNewCmStatusIndex,
docsIfCmtsModType,
docsIfCmtsModControl,
docsIfCmtsModPreambleLen,
docsIfCmtsModDifferentialEncoding,
docsIfCmtsModFECErrorCorrection,
docsIfCmtsModFECCodewordLength,
docsIfCmtsModScramblerSeed,
docsIfCmtsModMaxBurstSize,
docsIfCmtsModGuardTimeSize,
docsIfCmtsModLastCodewordShortened,
docsIfCmtsModScrambler,
docsIfCmtsModByteInterleaverDepth,
docsIfCmtsModByteInterleaverBlockSize,
docsIfCmtsModPreambleType,
docsIfCmtsModTcmErrorCorrectionOn,
docsIfCmtsModScdmaInterleaverStepSize,
docsIfCmtsModScdmaSpreaderEnable,
docsIfCmtsModScdmaSubframeCodes,
docsIfCmtsModChannelType,

docsIfCmtsModStorageType,
docsIfCmtsQosProfilePermissions,
docsIfCmtsCmPtr,
docsIfCmtsChannelUtilizationInterval,
docsIfCmtsChannelUtUtilization,
docsIfCmtsDownChnlCtrId,
docsIfCmtsDownChnlCtrTotalBytes,
docsIfCmtsDownChnlCtrUsedBytes,
docsIfCmtsDownChnlCtrExtTotalBytes,
docsIfCmtsDownChnlCtrExtUsedBytes,
docsIfCmtsUpChnlCtrId,

```
        docsIfCmtsUpChnlCtrTotalMslots,
        docsIfCmtsUpChnlCtrUcastGrantedMslots,
        docsIfCmtsUpChnlCtrTotalCntnMslots,
        docsIfCmtsUpChnlCtrUsedCntnMslots,
        docsIfCmtsUpChnlCtrExtTotalMslots,



        docsIfCmtsUpChnlCtrExtUcastGrantedMslots,
        docsIfCmtsUpChnlCtrExtTotalCntnMslots,
        docsIfCmtsUpChnlCtrExtUsedCntnMslots,
        docsIfCmtsUpChnlCtrCollCntnMslots,
        docsIfCmtsUpChnlCtrTotalCntnReqMslots,
        docsIfCmtsUpChnlCtrUsedCntnReqMslots,
        docsIfCmtsUpChnlCtrCollCntnReqMslots,
        docsIfCmtsUpChnlCtrTotalCntnReqDataMslots,
         docsIfCmtsUpChnlCtrUsedCntnReqDataMslots,
        docsIfCmtsUpChnlCtrCollCntnReqDataMslots,
        docsIfCmtsUpChnlCtrTotalCntnInitMaintMslots,
        docsIfCmtsUpChnlCtrUsedCntnInitMaintMslots,
        docsIfCmtsUpChnlCtrCollCntnInitMaintMslots,
        docsIfCmtsUpChnlCtrExtCollCntnMslots,
        docsIfCmtsUpChnlCtrExtTotalCntnReqMslots,
        docsIfCmtsUpChnlCtrExtUsedCntnReqMslots,
        docsIfCmtsUpChnlCtrExtCollCntnReqMslots,
        docsIfCmtsUpChnlCtrExtTotalCntnReqDataMslots,
        docsIfCmtsUpChnlCtrExtUsedCntnReqDataMslots,
        docsIfCmtsUpChnlCtrExtCollCntnReqDataMslots,
        docsIfCmtsUpChnlCtrExtTotalCntnInitMaintMslots,
        docsIfCmtsUpChnlCtrExtUsedCntnInitMaintMslots,
        docsIfCmtsUpChnlCtrExtCollCntnInitMaintMslots,
        docsIfDownChannelStorageType,
        docsIfQosProfStorageType

    }
    STATUS      current
    DESCRIPTION
        "Group of objects implemented in Cable Modem
 Termination
         Systems."
    ::= { docsIfGroups 7 }

END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/DOCS-IF-MIB
No license file was found, but licenses were detected in source scan.
```

```
SNMP-FRAMEWORK-MIB DEFINITIONS ::= BEGIN

IMPORTS
  MODULE-IDENTITY, OBJECT-TYPE,
  OBJECT-IDENTITY,
  snmpModules                    FROM SNMPv2-SMI
  TEXTUAL-CONVENTION             FROM SNMPv2-TC
  MODULE-COMPLIANCE, OBJECT-GROUP      FROM SNMPv2-CONF;

snmpFrameworkMIB MODULE-IDENTITY
  LAST-UPDATED "200210140000Z"
  ORGANIZATION "SNMPv3 Working Group"
  CONTACT-INFO "WG-EMail:   snmpv3@lists.tislabs.com
               Subscribe:  snmpv3-request@lists.tislabs.com

               Co-Chair:   Russ Mundy
                       Network Associates Laboratories
               postal:     15204 Omega Drive, Suite 300
                       Rockville, MD 20850-4601
                       USA
               EMail:      mundy@tislabs.com
               phone:      +1 301-947-7107

               Co-Chair &
               Co-editor:  David Harrington

                       Enterasys Networks
               postal:     35 Industrial Way
                       P. O. Box 5005
                       Rochester, New Hampshire 03866-5005
                       USA
               EMail:      dbh@enterasys.com
               phone:      +1 603-337-2614

               Co-editor:  Randy Presuhn
                       BMC Software, Inc.
               postal:     2141 North First Street
                       San Jose, California 95131
                       USA
               EMail:      randy_presuhn@bmc.com
               phone:      +1 408-546-1006

               Co-editor:  Bert Wijnen
                       Lucent Technologies
               postal:     Schagen 33
                       3461 GL Linschoten
                       Netherlands
```

```
            EMail:      bwijnen@lucent.com
            phone:      +31 348-680-485

          "
    DESCRIPTION  "The SNMP Management Architecture MIB

                  Copyright (C) The Internet Society (2002). This
                  version of this MIB module is part of RFC 3411;
                  see the RFC itself for full legal notices.
                 "

    REVISION     "200210140000Z"        -- 14 October 2002
    DESCRIPTION  "Changes in this revision:
                  - Updated various administrative information.
                  - Corrected some typos.
                  - Corrected typo in description of SnmpEngineID
                    that led to range overlap for 127.
                  - Changed '255a' to '255t' in definition of
                    SnmpAdminString to align with current SMI.
                  - Reworded 'reserved' for value zero in
                    DESCRIPTION of SnmpSecurityModel.
                  - The algorithm for allocating security models
                    should give
 256 per enterprise block, rather
                    than 255.
                  - The example engine ID of 'abcd' is not
                    legal. Replaced with '800002b804616263'H based
                    on example enterprise 696, string 'abc'.
                  - Added clarification that engineID should
                    persist across re-initializations.
                  This revision published as RFC 3411.
                 "
    REVISION     "199901190000Z"        -- 19 January 1999
    DESCRIPTION  "Updated editors' addresses, fixed typos.
                  Published as RFC 2571.
                 "
    REVISION     "199711200000Z"        -- 20 November 1997
    DESCRIPTION  "The initial version, published in RFC 2271.
                 "
    ::= { snmpModules 10 }

  -- Textual Conventions used in the SNMP Management Architecture ***

 SnmpEngineID ::= TEXTUAL-CONVENTION
   STATUS       current
   DESCRIPTION "An SNMP engine's
```

administratively-unique identifier.

Objects of this type are for identification, not for addressing, even though it is possible that an address may have been used in the generation of a specific value.

The value for this object may not be all zeros or all 'ff'H or the empty (zero length) string.

The initial value for this object may be configured via an operator console entry or via an algorithmic function. In the latter case, the following example algorithm is recommended.

In cases where there are multiple engines on the same system, the use of this algorithm is NOT appropriate, as it would result in all of those engines ending up with the same ID value.

1) The very first bit is used to indicate how the

rest of the data is composed.

0 - as defined by enterprise using former methods that existed before SNMPv3. See item 2 below.

1 - as defined by this architecture, see item 3 below.

Note that this allows existing uses of the engineID (also known as AgentID [RFC1910]) to co-exist with any new uses.

2) The snmpEngineID has a length of 12 octets.

The first four octets are set to the binary equivalent of the agent's SNMP management private enterprise number as assigned by the Internet Assigned Numbers Authority (IANA). For example, if Acme Networks has been assigned { enterprises 696 }, the first four octets would be assigned '000002b8'H.

The remaining eight octets

are determined via

one or more enterprise-specific methods. Such

methods must be designed so as to maximize the
possibility that the value of this object will
be unique in the agent's administrative domain.
For example, it may be the IP address of the SNMP
entity, or the MAC address of one of the
interfaces, with each address suitably padded
with random octets. If multiple methods are
defined, then it is recommended that the first
octet indicate the method being used and the
remaining octets be a function of the method.

3) The length of the octet string varies.

The first four octets are set to the binary
equivalent of the agent's SNMP management
private enterprise number as assigned by the
Internet Assigned Numbers Authority (IANA).
For example, if Acme Networks has been assigned
{ enterprises 696 }, the first four octets would
be assigned '000002b8'H.

The very first bit is set to 1. For example, the
above value for Acme Networks now changes to be
'800002b8'H.

The fifth octet indicates how the rest (6th and
following octets) are formatted. The values for
the fifth octet are:

0 - reserved, unused.

1 - IPv4 address (4 octets)
lowest non-special IP address

2 - IPv6 address (16 octets)
lowest non-special IP address

3 - MAC address (6 octets)
lowest IEEE MAC address, canonical

order

4 - Text, administratively assigned
Maximum remaining length 27

5 - Octets, administratively assigned

Maximum remaining length 27

6-127 - reserved, unused

128-255 - as defined by the enterprise
Maximum remaining length 27
"
SYNTAX OCTET STRING (SIZE(5..32))

SnmpSecurityModel ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION "An identifier that uniquely identifies a
Security Model of the Security Subsystem within
this SNMP Management Architecture.

The values for securityModel are allocated as
follows:

- The zero value does not identify any particular
security model.

- Values between 1 and 255, inclusive,
are reserved
for standards-track Security Models and are
managed by the Internet Assigned Numbers Authority
(IANA).
- Values greater than 255 are allocated to
enterprise-specific Security Models. An
enterprise-specific securityModel value is defined
to be:

enterpriseID * 256 + security model within
enterprise

For example, the fourth Security Model defined by
the enterprise whose enterpriseID is 1 would be
259.

This scheme for allocation of securityModel
values allows for a maximum of 255 standards-

based Security Models, and for a maximum of
256 Security Models per enterprise.

It is believed that the assignment of new
securityModel values will be rare in
practice
because the larger the number of simultaneously
utilized Security Models, the larger the
chance that interoperability will suffer.
Consequently, it is believed that such a range
will be sufficient. In the unlikely event that
the standards committee finds this number to be
insufficient over time, an enterprise number
can be allocated to obtain an additional 256
possible values.

Note that the most significant bit must be zero;
hence, there are 23 bits allocated for various
organizations to design and define non-standard

securityModels. This limits the ability to
define new proprietary implementations of Security
Models to the first 8,388,608 enterprises.

It is worthwhile to note that, in its encoded

form, the securityModel value will normally
require only a single byte since, in practice,
the leftmost bits will be zero for most messages
and sign extension is suppressed by the encoding
rules.

As of this writing, there are several values
of securityModel defined for use with SNMP or
reserved for use with supporting MIB objects.
They are as follows:

0 reserved for 'any'
1 reserved for SNMPv1
2 reserved for SNMPv2c
3 User-Based Security Model (USM)
"
SYNTAX INTEGER(0 .. 2147483647)

SnmpMessageProcessingModel ::= TEXTUAL-CONVENTION

STATUS current
DESCRIPTION "An identifier that uniquely identifies a Message
Processing Model of the Message Processing
Subsystem within this SNMP Management
Architecture.

The values for messageProcessingModel are
allocated as follows:

- Values between 0 and 255, inclusive, are
reserved for standards-track Message Processing
Models and are managed by the Internet Assigned
Numbers Authority (IANA).

- Values greater than 255 are allocated to
enterprise-specific Message Processing Models.
An enterprise messageProcessingModel value is
defined to be:

enterpriseID * 256 +
messageProcessingModel within enterprise

For example, the fourth Message Processing Model
defined by the enterprise whose enterpriseID

is 1 would be 259.

This scheme for allocating messageProcessingModel
values allows for a maximum of 255 standards-
based Message Processing Models, and for a
maximum of 256 Message Processing Models per
enterprise.

It is believed that the assignment of new
messageProcessingModel values will be rare
in practice because the larger the number of
simultaneously utilized Message Processing Models,
the larger the chance that interoperability
will suffer. It is believed that such a range
will be sufficient. In the unlikely event that
the standards committee finds this number to be
insufficient over time, an enterprise number
can be allocated to obtain an additional 256
possible values.

Note that the most significant bit must be zero;

```
            hence, there are 23 bits allocated for various
            organizations to design and define non-standard
             messageProcessingModels.  This limits the ability
            to define new proprietary implementations of
            Message Processing Models to the first 8,388,608
            enterprises.

            It is worthwhile to note that, in its encoded
            form, the messageProcessingModel value will
            normally require only a single byte since, in
            practice, the leftmost bits will be zero for
            most messages and sign extension is suppressed
            by the encoding rules.

            As of this writing, there are several values of
            messageProcessingModel defined for use with SNMP.
            They are as follows:

               0  reserved for SNMPv1
               1  reserved for SNMPv2c
               2  reserved for SNMPv2u and SNMPv2*
               3  reserved for SNMPv3
           "
  SYNTAX       INTEGER(0 .. 2147483647)




SnmpSecurityLevel
 ::= TEXTUAL-CONVENTION
  STATUS       current
  DESCRIPTION "A Level of Security at which SNMP messages can be
            sent or with which operations are being processed;
            in particular, one of:

              noAuthNoPriv - without authentication and
                          without privacy,
              authNoPriv   - with authentication but
                          without privacy,
              authPriv     - with authentication and
                          with privacy.

            These three values are ordered such that
            noAuthNoPriv is less than authNoPriv and
            authNoPriv is less than authPriv.
           "
```

```
  SYNTAX      INTEGER { noAuthNoPriv(1),
                        authNoPriv(2),
                        authPriv(3)
                      }

SnmpAdminString ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "255t"
  STATUS
    current
  DESCRIPTION "An octet string containing administrative
          information, preferably in human-readable form.

          To facilitate internationalization, this
          information is represented using the ISO/IEC
          IS 10646-1 character set, encoded as an octet
          string using the UTF-8 transformation format
          described in [RFC2279].

          Since additional code points are added by
          amendments to the 10646 standard from time
          to time, implementations must be prepared to
          encounter any code point from 0x00000000 to
          0x7fffffff.  Byte sequences that do not
          correspond to the valid UTF-8 encoding of a
          code point or are outside this range are
          prohibited.

          The use of control codes should be avoided.

          When it is necessary to represent a newline,

         the control code sequence CR LF should be used.



          The use of leading or trailing white space should
          be avoided.

          For code points not directly supported by user
          interface hardware or software, an alternative
          means of entry and display, such as hexadecimal,
          may be provided.

          For information encoded in 7-bit US-ASCII,
          the UTF-8 encoding is identical to the
          US-ASCII encoding.
```

```
            UTF-8 may require multiple bytes to represent a
            single character / code point; thus the length
            of this object in octets may be different from
            the number of characters encoded.  Similarly,
            size constraints refer to the number of encoded
            octets, not the number of characters represented
            by an encoding.

            Note that when this
 TC is used for an object that
            is used or envisioned to be used as an index, then
            a SIZE restriction MUST be specified so that the
            number of sub-identifiers for any object instance
            does not exceed the limit of 128, as defined by
            [RFC3416].

            Note that the size of an SnmpAdminString object is
            measured in octets, not characters.
           "
  SYNTAX       OCTET STRING (SIZE (0..255))


-- Administrative assignments ****************************************

snmpFrameworkAdmin
  OBJECT IDENTIFIER ::= { snmpFrameworkMIB 1 }
snmpFrameworkMIBObjects
  OBJECT IDENTIFIER ::= { snmpFrameworkMIB 2 }
snmpFrameworkMIBConformance
  OBJECT IDENTIFIER ::= { snmpFrameworkMIB 3 }

-- the snmpEngine Group **********************************************

snmpEngine OBJECT IDENTIFIER ::= { snmpFrameworkMIBObjects 1 }




snmpEngineID     OBJECT-TYPE
  SYNTAX       SnmpEngineID
   MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION "An SNMP engine's administratively-unique identifier.

            This information SHOULD be stored in non-volatile
            storage so that it remains constant across
```

```
            re-initializations of the SNMP engine.
           "
  ::= { snmpEngine 1 }

snmpEngineBoots  OBJECT-TYPE
  SYNTAX       INTEGER (1..2147483647)
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION "The number of times that the SNMP engine has
            (re-)initialized itself since snmpEngineID
            was last configured.
           "
  ::= { snmpEngine 2 }

snmpEngineTime   OBJECT-TYPE
  SYNTAX       INTEGER (0..2147483647)
  UNITS        "seconds"
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION "The number of seconds since the value of
            the snmpEngineBoots object last changed.
            When incrementing this object's value would
             cause it to exceed its maximum,
            snmpEngineBoots is incremented as if a
            re-initialization had occurred, and this
            object's value consequently reverts to zero.
           "
  ::= { snmpEngine 3 }

snmpEngineMaxMessageSize OBJECT-TYPE
  SYNTAX       INTEGER (484..2147483647)
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION "The maximum length in octets of an SNMP message
            which this SNMP engine can send or receive and
            process, determined as the minimum of the maximum
            message size values supported among all of the
            transports available to and supported by the engine.
           "
  ::= { snmpEngine 4 }



-- Registration Points for Authentication and Privacy Protocols **

snmpAuthProtocols OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION  "Registration point for standards-track
```

```
            authentication protocols
 used in SNMP Management
            Frameworks.
           "
  ::= { snmpFrameworkAdmin 1 }

snmpPrivProtocols OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION  "Registration point for standards-track privacy
            protocols used in SNMP Management Frameworks.
           "
  ::= { snmpFrameworkAdmin 2 }

-- Conformance information ****************************************

snmpFrameworkMIBCompliances
          OBJECT IDENTIFIER ::= {snmpFrameworkMIBConformance 1}
snmpFrameworkMIBGroups
          OBJECT IDENTIFIER ::= {snmpFrameworkMIBConformance 2}

-- compliance statements

snmpFrameworkMIBCompliance MODULE-COMPLIANCE
  STATUS       current
  DESCRIPTION "The compliance statement for SNMP engines which
            implement the SNMP Management Framework MIB.
           "
  MODULE    -- this module
     MANDATORY-GROUPS { snmpEngineGroup }

  ::= { snmpFrameworkMIBCompliances 1 }

-- units of conformance

snmpEngineGroup
 OBJECT-GROUP
  OBJECTS {
          snmpEngineID,
          snmpEngineBoots,
          snmpEngineTime,
          snmpEngineMaxMessageSize
         }
  STATUS       current
  DESCRIPTION "A collection of objects for identifying and
            determining the configuration and current timeliness
```

```
            values of an SNMP engine.
           "
  ::= { snmpFrameworkMIBGroups 1 }

END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/SNMP-FRAMEWORK-MIB
No license file was found, but licenses were detected in source scan.

```
IPSEC-SPD-MIB DEFINITIONS ::= BEGIN

IMPORTS
  MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE, Integer32,
  Unsigned32, mib-2           FROM SNMPv2-SMI
                              -- [RFC2578]

  TEXTUAL-CONVENTION, RowStatus, TruthValue,
  TimeStamp, StorageType, VariablePointer
                              FROM SNMPv2-TC
                              -- [RFC2579]




  MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
                              FROM SNMPv2-CONF
                              -- [RFC2580]

  InterfaceIndex
                              FROM IF-MIB
                              -- [RFC2863]

  diffServMIBMultiFieldClfrGroup, IfDirection,
  diffServMultiFieldClfrNextFree
                              FROM DIFFSERV-MIB
                              -- [RFC3289]

  InetAddressType, InetAddress
                               FROM INET-ADDRESS-MIB
                              -- [RFC4001]

  SnmpAdminString                   FROM SNMP-FRAMEWORK-MIB
                              -- [RFC3411]

  ;

--
```

```
-- module identity
--

spdMIB MODULE-IDENTITY
  LAST-UPDATED "200702070000Z"    -- 7 February 2007
  ORGANIZATION "IETF IP Security Policy Working Group"
  CONTACT-INFO "Michael Baer
               P.O. Box 72682
               Davis, CA 95617
               Phone: +1 530 902 3131
               Email: baerm@tislabs.com

               Ricky Charlet
               Email: rcharlet@alumni.calpoly.edu

               Wes Hardaker
               Sparta, Inc.
               P.O. Box 382
               Davis, CA  95617
               Phone: +1 530 792 1913
               Email: hardaker@tislabs.com

               Robert Story
               Revelstone Software
               PO Box 1812




             Tucker, GA 30085
               Phone: +1 770 617 3722
               Email: rstory@ipsp.revelstone.com

               Cliff Wang
               ARO
               4300 S. Miami Blvd.
               Durham, NC 27703
               E-Mail: cliffwangmail@yahoo.com"
  DESCRIPTION
   "This MIB module defines configuration objects for managing
    IPsec Security Policies.  In general, this MIB can be
    implemented anywhere IPsec security services exist (e.g.,
    bump-in-the-wire, host, gateway, firewall, router, etc.).

    Copyright (C) The IETF Trust (2007).  This version of
    this MIB module is part of RFC 4807; see the RFC itself for
    full legal notices."
```

```
-- Revision History

  REVISION     "200702070000Z"    -- 7 February 2007
  DESCRIPTION  "Initial version, published as RFC 4807."

  ::= { mib-2 153 }

--
-- groups of related objects
--

spdConfigObjects        OBJECT IDENTIFIER
   ::= { spdMIB 1 }
spdNotificationObjects
  OBJECT IDENTIFIER
   ::= { spdMIB 2 }
spdConformanceObjects    OBJECT IDENTIFIER
   ::= { spdMIB 3 }
spdActions              OBJECT IDENTIFIER
   ::= { spdMIB 4 }

--
-- Textual Conventions
--

SpdBooleanOperator ::= TEXTUAL-CONVENTION
  STATUS   current
  DESCRIPTION
      "The SpdBooleanOperator operator is used to specify
       whether sub-components in a decision-making process are




       ANDed or ORed together to decide if the resulting
       expression is true or false."
  SYNTAX      INTEGER { or(1), and(2) }

SpdAdminStatus ::= TEXTUAL-CONVENTION
  STATUS   current
  DESCRIPTION
      "The SpdAdminStatus is used to specify the administrative
       status of an object.  Objects that are disabled MUST NOT
       be used by the packet processing engine."
  SYNTAX      INTEGER { enabled(1), disabled(2) }

SpdIPPacketLogging ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "d"
  STATUS   current
```

DESCRIPTION
"SpdIPPacketLogging specifies
whether an audit message
SHOULD be logged if a packet is passed through a Security
Association (SA) and if some of that packet is included in
the log event. A value of '-1' indicates no logging. A
value of '0' or greater indicates that logging SHOULD be
done and indicates the number of bytes starting at the
beginning of the packet to place in the log. Values greater
than the size of the packet being processed indicate that
the entire packet SHOULD be sent.

Examples:
'-1' no logging
'0' log but do not include any of the packet in the log
'20' log and include the first 20 bytes of the packet
in the log."

SYNTAX Integer32 (-1..65535)

SpdTimePeriod ::= TEXTUAL-CONVENTION
DISPLAY-HINT "31t"
STATUS current
DESCRIPTION
"This property identifies an overall range of calendar dates
and time. In a boolean context, a value
within this time
range, inclusive, is considered true.

This information is encoded as an octet string using
the UTF-8 transformation format described in STD 63,
RFC 3629.

It uses the format suggested in RFC 3060. An octet string

represents a start date and time and an end date and time.
For example:

yyyymmddThhmmss/yyyymmddThhmmss

Where: yyyy = year mm = month dd = day
hh = hour mm = minute ss = second

The first 'yyyymmddThhmmss' sub-string indicates the start
date and time. The second 'yyyymmddThhmmss' sub-string

indicates the end date and time. The character 'T' within these sub-strings indicates the beginning of the time portion of each sub-string. The solidus character '/' separates the start from the end date and time. The end date and time MUST be subsequent to the start date and

time.

There are also two allowed substitutes for a 'yyyymmddThhmmss' sub-string: one for the start date and time, and one for the end date and time.

If the start date and time are replaced with the string 'THISANDPRIOR', this sub-string would indicate the current date and time and the previous dates and time.

If the end date and time are replaced with the string 'THISANDFUTURE', this sub-string would indicate the current date and time and the subsequent dates and time.

Any of the following SHOULD be considered a 'wrongValue' error:
- Setting a value with the end date and time earlier than or equal to the start date and time.
- Setting the start date and time to 'THISANDFUTURE'.
- Setting the end date and time to 'THISANDPRIOR'."

```
  REFERENCE "RFC 3060, 3269"
  SYNTAX      OCTET STRING (SIZE (0..31))
--
-- Policy group definitions
--

spdLocalConfigObjects
 OBJECT IDENTIFIER
   ::= { spdConfigObjects 1 }

spdIngressPolicyGroupName OBJECT-TYPE
  SYNTAX      SnmpAdminString (SIZE(0..32))
  MAX-ACCESS  read-write
  STATUS      current



  DESCRIPTION
      "This object indicates the global system policy group that
      is to be applied on ingress packets (i.e., arriving at an
      interface from a network) when a given endpoint does not
      contain a policy definition in the spdEndpointToGroupTable.
```

```
      Its value can be used as an index into the
      spdGroupContentsTable to retrieve a list of policies.  A
      zero length string indicates that no system-wide policy exists
      and the default policy of 'drop' SHOULD be executed for
      ingress packets until one is imposed by either this object
      or by the endpoint processing a given packet.

      This object MUST be persistent"
  DEFVAL { "" }
  ::= { spdLocalConfigObjects 1 }

spdEgressPolicyGroupName OBJECT-TYPE
  SYNTAX
   SnmpAdminString (SIZE(0..32))
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     "This object indicates the policy group containing the
      global system policy that is to be applied on egress
      packets (i.e., packets leaving an interface and entering a
      network) when a given endpoint does not contain a policy
      definition in the spdEndpointToGroupTable.  Its value can
      be used as an index into the spdGroupContentsTable to
      retrieve a list of policies.  A zero length string
      indicates that no system-wide policy exists and the default
      policy of 'drop' SHOULD be executed for egress packets
      until one is imposed by either this object or by the
      endpoint processing a given packet.

      This object MUST be persistent"
  DEFVAL { "" }
  ::= { spdLocalConfigObjects 2 }


spdEndpointToGroupTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SpdEndpointToGroupEntry
  MAX-ACCESS  not-accessible
   STATUS      current
  DESCRIPTION
     "This table maps policies (groupings) onto an endpoint
      (interface).  A policy group assigned to an endpoint is then
      used to control access to the network traffic passing
      through that endpoint.




      If an endpoint has been configured with a policy group and
```

```
        no rule within that policy group matches that packet, the
        default action in this case SHALL be to drop the packet.

        If no policy group has been assigned to an endpoint, then
        the policy group specified by spdIngressPolicyGroupName MUST
        be used on traffic inbound from the network through that
        endpoint, and the policy group specified by
        spdEgressPolicyGroupName MUST be used for traffic outbound
        to the network through that endpoint."
    ::= { spdConfigObjects 2 }

spdEndpointToGroupEntry OBJECT-TYPE
    SYNTAX      SpdEndpointToGroupEntry
    MAX-ACCESS  not-accessible
    STATUS
      current
    DESCRIPTION
       "A mapping assigning a policy group to an endpoint."

    INDEX { spdEndGroupDirection, spdEndGroupInterface }
    ::= { spdEndpointToGroupTable 1 }

SpdEndpointToGroupEntry ::= SEQUENCE {
    spdEndGroupDirection                IfDirection,
    spdEndGroupInterface                InterfaceIndex,
    spdEndGroupName                     SnmpAdminString,
    spdEndGroupLastChanged               TimeStamp,
    spdEndGroupStorageType               StorageType,
    spdEndGroupRowStatus                 RowStatus
}

spdEndGroupDirection OBJECT-TYPE
    SYNTAX      IfDirection
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
       "This object indicates which direction of packets crossing
        the interface are associated with which spdEndGroupName
        object.  Ingress packets, or packets into the device match
        when this value is inbound(1).  Egress packets or packets
        out
 of the device match when this value is outbound(2)."
    ::= { spdEndpointToGroupEntry 1 }

spdEndGroupInterface OBJECT-TYPE
    SYNTAX      InterfaceIndex
    MAX-ACCESS  not-accessible
    STATUS      current
```

```
    DESCRIPTION


        "This value matches the IF-MIB's ifTable's ifIndex column
         and indicates the interface associated with a given
         endpoint.  This object can be used to uniquely identify an
         endpoint that a set of policy groups are applied to."
    ::= { spdEndpointToGroupEntry 2 }

spdEndGroupName OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(1..32))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The policy group name to apply at this endpoint.  The
         value of the spdEndGroupName object is then used as an
         index into the spdGroupContentsTable to come up with a list
         of rules that MUST be applied at this endpoint."
    ::= { spdEndpointToGroupEntry 3 }

spdEndGroupLastChanged OBJECT-TYPE

    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime when this row was last modified
         or created either through SNMP SETs or by some other
         external means.

         If this row has not been modified since the last
         re-initialization of the network management subsystem, this
         object SHOULD have a zero value."
    ::= { spdEndpointToGroupEntry 4 }

spdEndGroupStorageType OBJECT-TYPE
    SYNTAX      StorageType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The storage type for this row.  Rows in this table that
         were created through an external process MAY have a storage
         type of readOnly or permanent.

         For a storage type of permanent, none of the columns have
         to be writable."
    DEFVAL { nonVolatile }
```

::= { spdEndpointToGroupEntry 5 }

spdEndGroupRowStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create

STATUS current
DESCRIPTION
"This object indicates the conceptual status of this row.

The value of this object has no effect on whether other
objects in this conceptual row can be modified.

This object is considered 'notReady' and MUST NOT be set to
active until one or more active rows exist within the
spdGroupContentsTable for the group referenced by the
spdEndGroupName object."
::= { spdEndpointToGroupEntry 6 }

--
-- policy group definition table
--

spdGroupContentsTable OBJECT-TYPE
SYNTAX SEQUENCE OF SpdGroupContentsEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"This table contains a list of rules and/or subgroups
contained within a given policy group. For a given value
of spdGroupContName, the set of rows sharing that value
forms a 'group'. The rows in a group MUST be processed
according to the value of the spdGroupContPriority
object
in each row. The processing MUST be executed starting with
the lowest value of spdGroupContPriority and in ascending
order thereafter.

If an action is executed as the result of the processing of
a row in a group, the processing of further rows in that
group MUST stop. Iterating to the next policy group row by
finding the next largest spdGroupContPriority object SHALL
only be done if no actions were run while processing the
current row for a given packet."
::= { spdConfigObjects 3 }

```
spdGroupContentsEntry OBJECT-TYPE
  SYNTAX      SpdGroupContentsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "Defines a given sub-component within a policy group.  A
      sub-component is either a rule or another group as
      indicated by spdGroupContComponentType and referenced by
      spdGroupContComponentName."



  INDEX   { spdGroupContName,
 spdGroupContPriority }
  ::= { spdGroupContentsTable 1 }

SpdGroupContentsEntry ::= SEQUENCE {
  spdGroupContName                  SnmpAdminString,
  spdGroupContPriority              Integer32,
  spdGroupContFilter                VariablePointer,
  spdGroupContComponentType             INTEGER,
  spdGroupContComponentName             SnmpAdminString,
  spdGroupContLastChanged           TimeStamp,
  spdGroupContStorageType           StorageType,
  spdGroupContRowStatus             RowStatus
}

spdGroupContName OBJECT-TYPE
  SYNTAX      SnmpAdminString (SIZE(1..32))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The administrative name of the group associated with this
     row.  A 'group' is formed by all the rows in this table that
     have the same value of this object."
  ::= { spdGroupContentsEntry 1 }

spdGroupContPriority OBJECT-TYPE
  SYNTAX      Integer32 (0..65535)

 MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The priority (sequence number) of the sub-component in
      a group that this row represents.  This value indicates
      the order that each row of this table MUST be processed
      from low to high.  For example, a row with a priority of 0
      is processed before a row with a priority of 1, a 1 before
```

a 2, etc."
::= { spdGroupContentsEntry 2 }

spdGroupContFilter OBJECT-TYPE
SYNTAX VariablePointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"spdGroupContFilter points to a filter that is evaluated
to determine whether the spdGroupContComponentName within
this row is exercised. Managers can use this object to
classify groups of rules, or subgroups, together in order to
achieve a greater degree of control and optimization over
the execution order of the items within the group. If the

filter evaluates to false, the rule or subgroup will be
skipped and the next rule or subgroup will be evaluated
instead. This value can be used to indicate a scalar or
row in a table. When indicating a row in a table, this
value MUST point to the first column instance in that row.

An example usage of this object would be to limit a
group of rules to executing only when the IP packet
being processed is designated to be processed by IKE.
This effectively creates a group of IKE-specific rules.

The following tables and scalars can be pointed to by this
column. All but diffServMultiFieldClfrTable are defined in
this MIB:

diffServMultiFieldClfrTable
spdIpOffsetFilterTable
spdTimeFilterTable
spdCompoundFilterTable
spdTrueFilter
spdIpsoHeaderFilterTable

Implementations MAY choose to provide
support for other
filter tables or scalars.

If this column is set to a VariablePointer value, which
references a non-existent row in an otherwise supported
table, the inconsistentName exception MUST be returned. If
the table or scalar pointed to by the VariablePointer is

not supported at all, then an inconsistentValue exception
MUST be returned.

If, during packet processing, a row in this table is applied
to a packet and the value of this column in that row
references a non-existent or non-supported object, the
packet MUST be dropped."
REFERENCE "RFC 3289"
DEFVAL { spdTrueFilterInstance }
::= { spdGroupContentsEntry 3 }

spdGroupContComponentType OBJECT-TYPE
SYNTAX INTEGER { group(1), rule(2) }
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"Indicates whether the spdGroupContComponentName object
is the name of another group
defined within the
spdGroupContentsTable or is the name of a rule defined

within the spdRuleDefinitionTable."
DEFVAL { rule }
::= { spdGroupContentsEntry 4 }

spdGroupContComponentName OBJECT-TYPE
SYNTAX SnmpAdminString (SIZE(1..32))
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The name of the policy rule or subgroup contained within
this row, as indicated by the spdGroupContComponentType
object."
::= { spdGroupContentsEntry 5 }

spdGroupContLastChanged OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime when this row was last modified
or created either through SNMP SETs or by some other
external means.

If this row has not been modified since the last
re-initialization of the network management subsystem,

```
      this object SHOULD have a zero value."
  ::= { spdGroupContentsEntry
 6 }

spdGroupContStorageType OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The storage type for this row.  Rows in this table that
      were created through an external process MAY have a storage
      type of readOnly or permanent.

      For a storage type of permanent, none of the columns have
      to be writable."
  DEFVAL { nonVolatile }
  ::= { spdGroupContentsEntry 7 }

spdGroupContRowStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object indicates the conceptual status of this row.



      The value of this object has no effect on whether other
      objects in this conceptual row can be modified.

      This object MUST NOT be set to active until the row to
      which the spdGroupContComponentName points to exists and is
      active.

      If active, this object MUST remain active
 unless one of the
      following two conditions are met:

      I.  No active row in spdEndpointToGroupTable exists that
          references this row's group (i.e., indicate this row's
          spdGroupContName).

      II. Or at least one other active row in this table has a
          matching spdGroupContName.

      If neither condition is met, an attempt to set this row to
      something other than active MUST result in an
      inconsistentValue error."
```

```
  ::= { spdGroupContentsEntry 8 }


--
-- policy definition table
--

spdRuleDefinitionTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SpdRuleDefinitionEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "This table defines a rule by associating a filter
       or a set of filters to an action to be executed."
  ::= { spdConfigObjects 4 }

spdRuleDefinitionEntry OBJECT-TYPE
  SYNTAX      SpdRuleDefinitionEntry
  MAX-ACCESS  not-accessible
  STATUS      current
   DESCRIPTION
      "A row defining a particular rule definition.  A rule
       definition binds a filter pointer to an action pointer."
  INDEX   { spdRuleDefName }
  ::= { spdRuleDefinitionTable 1 }

SpdRuleDefinitionEntry ::= SEQUENCE {
  spdRuleDefName                SnmpAdminString,



  spdRuleDefDescription          SnmpAdminString,
  spdRuleDefFilter              VariablePointer,
  spdRuleDefFilterNegated        TruthValue,
  spdRuleDefAction              VariablePointer,
  spdRuleDefAdminStatus          SpdAdminStatus,
  spdRuleDefLastChanged          TimeStamp,
  spdRuleDefStorageType          StorageType,
  spdRuleDefRowStatus            RowStatus
}

spdRuleDefName OBJECT-TYPE
  SYNTAX      SnmpAdminString (SIZE(1..32))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "spdRuleDefName is the administratively assigned name of
```

```
    the rule referred to by the spdGroupContComponentName
      object."
  ::= { spdRuleDefinitionEntry 1 }

spdRuleDefDescription OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "A user defined string.  This field MAY be used for
      administrative tracking purposes."
  DEFVAL { "" }
  ::= { spdRuleDefinitionEntry 2 }

spdRuleDefFilter OBJECT-TYPE
  SYNTAX      VariablePointer
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "spdRuleDefFilter points to a filter that is used to
      evaluate whether the action associated with this row is
      executed or not.  The action will only execute if the
      filter referenced by this object evaluates to TRUE after
      first applying any negation required by the
      spdRuleDefFilterNegated object.

      The following tables and scalars can be pointed to by this
      column.  All but diffServMultiFieldClfrTable
 are defined in
      this MIB.  Implementations MAY choose to provide support
      for other filter tables or scalars as well:

           diffServMultiFieldClfrTable



           spdIpOffsetFilterTable
           spdTimeFilterTable
           spdCompoundFilterTable
           spdTrueFilter

      If this column is set to a VariablePointer value, which
      references a non-existent row in an otherwise supported
      table, the inconsistentName exception MUST be returned.  If
      the table or scalar pointed to by the VariablePointer is
      not supported at all, then an inconsistentValue exception
      MUST be returned.
```

```
        If, during packet processing, this column has a value that
        references a non-existent or non-supported object, the
        packet MUST be dropped."
    REFERENCE "RFC 3289"
    ::= { spdRuleDefinitionEntry 3 }

spdRuleDefFilterNegated OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS
   read-create
    STATUS      current
    DESCRIPTION
       "spdRuleDefFilterNegated specifies whether or not the results of
        the filter referenced by the spdRuleDefFilter object is
        negated."
    DEFVAL { false }
    ::= { spdRuleDefinitionEntry 4 }

spdRuleDefAction OBJECT-TYPE
    SYNTAX      VariablePointer
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
       "This column points to the action to be taken.  It MAY,
        but is not limited to, point to a row in one of the
        following tables:

          spdCompoundActionTable
          ipsaSaPreconfiguredActionTable
          ipiaIkeActionTable
          ipiaIpsecActionTable

        It MAY also point to one of the scalar objects beneath
        spdStaticActions.

        If this object is set to a pointer to a row in an
        unsupported (or unknown) table, an inconsistentValue




        error MUST be returned.

        If this object is set to point to a non-existent
   row in an
        otherwise supported table, an inconsistentName error MUST
        be returned.

        If, during packet processing, this column has a value that
```

```
        references a non-existent or non-supported object, the
        packet MUST be dropped."
    ::= { spdRuleDefinitionEntry 5 }

spdRuleDefAdminStatus OBJECT-TYPE
    SYNTAX      SpdAdminStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Indicates whether the current rule definition is considered
        active.  If the value is enabled, the rule MUST be evaluated
        when processing packets.  If the value is disabled, the
        packet processing MUST continue as if this rule's filter
        had effectively failed."
    DEFVAL { enabled }
    ::= { spdRuleDefinitionEntry 6 }

spdRuleDefLastChanged OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime when this row was last modified

       or created either through SNMP SETs or by some other
        external means.

        If this row has not been modified since the last
        re-initialization of the network management subsystem, this
        object SHOULD have a zero value."
    ::= { spdRuleDefinitionEntry 7 }

spdRuleDefStorageType OBJECT-TYPE
    SYNTAX      StorageType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The storage type for this row.  Rows in this table that
        were created through an external process MAY have a
        storage type of readOnly or permanent.

        For a storage type of permanent, none of the columns have




        to be writable."
    DEFVAL { nonVolatile }
    ::= { spdRuleDefinitionEntry 8 }
```

```
spdRuleDefRowStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "This object indicates the conceptual status of this row.

       The value of this object has no effect on
 whether other
       objects in this conceptual row can be modified.

       This object MUST NOT be set to active until the containing
       conditions, filters, and actions have been defined.  Once
       active, it MUST remain active until no active
       policyGroupContents entries are referencing it.  A failed
       attempt to do so MUST return an inconsistentValue error."
  ::= { spdRuleDefinitionEntry 9 }

--
-- Policy compound filter definition table
--

spdCompoundFilterTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SpdCompoundFilterEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A table defining compound filters and their associated
       parameters.  A row in this table can be pointed to by a
       spdRuleDefFilter object."
  ::= { spdConfigObjects 5 }

spdCompoundFilterEntry OBJECT-TYPE
  SYNTAX      SpdCompoundFilterEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "An entry
 in the spdCompoundFilterTable.  Each entry in this
       table represents a compound filter.  A filter defined by
       this table is considered to have a TRUE return value if and
       only if:

       spdCompFiltLogicType is AND and all of the sub-filters
       associated with it, as defined in the spdSubfiltersTable,
       are all true themselves (after applying any required
```

```
        negation, as defined by the ficFilterIsNegated object).

        spdCompFiltLogicType is OR and at least one of the
        sub-filters associated with it, as defined in the
        spdSubfiltersTable, is true itself (after applying any
        required negation, as defined by the ficFilterIsNegated
        object."
    INDEX       { spdCompFiltName }
    ::= { spdCompoundFilterTable 1 }

SpdCompoundFilterEntry ::= SEQUENCE {
    spdCompFiltName                 SnmpAdminString,
    spdCompFiltDescription          SnmpAdminString,
    spdCompFiltLogicType
                SpdBooleanOperator,
    spdCompFiltLastChanged          TimeStamp,
    spdCompFiltStorageType          StorageType,
    spdCompFiltRowStatus            RowStatus
}

spdCompFiltName OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(1..32))
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A user definable string.  This value is used as an index
        into this table."
    ::= { spdCompoundFilterEntry 1 }

spdCompFiltDescription OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "A user definable string.  This field MAY be used for
        your administrative tracking purposes."
    DEFVAL { "" }
    ::= { spdCompoundFilterEntry 2 }

spdCompFiltLogicType OBJECT-TYPE
    SYNTAX      SpdBooleanOperator
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Indicates whether the sub-component filters of this
        compound
```

filter are functionally ANDed or ORed together."
DEFVAL { and }
::= { spdCompoundFilterEntry 3 }

spdCompFiltLastChanged OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime when this row was last modified
or created either through SNMP SETs or by some other
external means.

If this row has not been modified since the last
re-initialization of the network management subsystem, this
object SHOULD have a zero value."
::= { spdCompoundFilterEntry 4 }

spdCompFiltStorageType OBJECT-TYPE
SYNTAX StorageType
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The storage type for this row. Rows in this table that
were created through an external process MAY have a
storage type of readOnly or permanent.

For a storage type of permanent, none of the columns have
to be writable."

DEFVAL { nonVolatile }
::= { spdCompoundFilterEntry 5 }

spdCompFiltRowStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This object indicates the conceptual status of this row.

The value of this object has no effect on whether other
objects in this conceptual row can be modified.

Once active, it MUST NOT have its value changed if any
active rows in the spdRuleDefinitionTable are currently

```
        pointing at this row."
    ::= { spdCompoundFilterEntry 6 }

--
-- Policy filters in a cf table
--

spdSubfiltersTable OBJECT-TYPE



    SYNTAX      SEQUENCE OF SpdSubfiltersEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table defines a list of filters contained within a
         given compound filter defined in the
         spdCompoundFilterTable."
    ::= { spdConfigObjects 6 }

spdSubfiltersEntry OBJECT-TYPE
    SYNTAX      SpdSubfiltersEntry
     MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry in the spdSubfiltersTable.  There is an entry in
         this table for each sub-filter of all compound filters
         present in the spdCompoundFilterTable."
    INDEX       {  spdCompFiltName, spdSubFiltPriority }
    ::= { spdSubfiltersTable 1 }

SpdSubfiltersEntry ::= SEQUENCE {
    spdSubFiltPriority                  Integer32,
    spdSubFiltSubfilter                 VariablePointer,
    spdSubFiltSubfilterIsNegated            TruthValue,
    spdSubFiltLastChanged               TimeStamp,
    spdSubFiltStorageType               StorageType,
    spdSubFiltRowStatus                 RowStatus
}

spdSubFiltPriority OBJECT-TYPE
    SYNTAX      Integer32 (0..65535)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The priority of a given filter within a compound filter.
         The order of execution is from lowest to highest priority
```

value (i.e., priority 0 before priority 1, 1 before 2,
etc.). Implementations MAY choose to follow this ordering,
as set by the manager that created the rows. This can allow
a manager to intelligently construct filter lists such that
faster filters are evaluated first."
::= { spdSubfiltersEntry 1 }

spdSubFiltSubfilter OBJECT-TYPE
SYNTAX VariablePointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION

"The OID of the contained filter. The value of this
object is a VariablePointer that references the filter to
be included in this compound filter.

The following tables and scalars can be pointed to by this
column. All but diffServMultiFieldClfrTable are defined in
this MIB. Implementations MAY choose to provide support
for other filter tables or scalars as well:

diffServMultiFieldClfrTable
spdIpsoHeaderFilterTable
spdIpOffsetFilterTable
spdTimeFilterTable
spdCompoundFilterTable
spdTrueFilter

If this column is set to a VariablePointer value that
references a non-existent row in an otherwise supported
table, the inconsistentName exception MUST be returned. If
the table or scalar pointed to by the VariablePointer is
not supported at all, then an inconsistentValue exception
MUST be returned.

If, during packet processing, this column has a value that
references a non-existent or non-supported object, the
packet MUST be dropped."
REFERENCE "RFC 3289"
::= { spdSubfiltersEntry 2 }

spdSubFiltSubfilterIsNegated OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-create
STATUS current

```
  DESCRIPTION
      "Indicates whether or not the result of applying this sub-filter
       is negated."
  DEFVAL { false }
  ::= { spdSubfiltersEntry
 3 }

spdSubFiltLastChanged OBJECT-TYPE
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The value of sysUpTime when this row was last modified
       or created either through SNMP SETs or by some other
       external means.




       If this row has not been modified since the last
       re-initialization of the network management subsystem, this
       object SHOULD have a zero value."
  ::= { spdSubfiltersEntry 4 }

spdSubFiltStorageType OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "The storage type for this row.  Rows in this table that
       were created through an external process MAY have a
       storage type of readOnly or permanent.

       For a storage type of permanent, none of the columns have
       to be writable."
  DEFVAL { nonVolatile }
  ::= { spdSubfiltersEntry 5 }

spdSubFiltRowStatus OBJECT-TYPE
  SYNTAX
    RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "This object indicates the conceptual status of this row.

       The value of this object has no effect on whether other
       objects in this conceptual row can be modified.
```

```
        This object cannot be made active until a filter
        referenced by the spdSubFiltSubfilter object is both
        defined and active.  An attempt to do so MUST result in
        an inconsistentValue error.

        If active, this object MUST remain active unless one of the
        following two conditions are met:

        I.  No active row in the SpdCompoundFilterTable exists
            that has a matching spdCompFiltName.

        II. Or, at least one other active row in this table has a
            matching spdCompFiltName.

        If neither condition is met, an attempt to set this row to
        something other than active MUST result in an
        inconsistentValue error."
    ::=
  { spdSubfiltersEntry 6 }



--
-- Static Filters
--

spdStaticFilters OBJECT IDENTIFIER ::= { spdConfigObjects 7 }

spdTrueFilter OBJECT-TYPE
      SYNTAX      Integer32 (1)
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
          "This scalar indicates a (automatic) true result for
           a filter.  That is, this is a filter that is always
           true; it is useful for adding as a default filter for a
           default action or a set of actions."
      ::= { spdStaticFilters 1 }


spdTrueFilterInstance OBJECT IDENTIFIER ::= { spdTrueFilter 0 }



--
-- Policy IP Offset filter definition table
--
```

```
spdIpOffsetFilterTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SpdIpOffsetFilterEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "This table contains a list of filter definitions to be
       used within the spdRuleDefinitionTable or the
       spdSubfiltersTable.

       This type of filter is used
 to compare an administrator
       specified octet string to the octets at a particular
       location in a packet."
  ::= { spdConfigObjects 8 }

spdIpOffsetFilterEntry OBJECT-TYPE
  SYNTAX      SpdIpOffsetFilterEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A definition of a particular filter."
  INDEX       {  spdIpOffFiltName }
  ::= { spdIpOffsetFilterTable 1 }




SpdIpOffsetFilterEntry ::= SEQUENCE {
  spdIpOffFiltName                SnmpAdminString,
  spdIpOffFiltOffset              Unsigned32,
  spdIpOffFiltType                INTEGER,
  spdIpOffFiltValue               OCTET STRING,
  spdIpOffFiltLastChanged         TimeStamp,
  spdIpOffFiltStorageType         StorageType,
  spdIpOffFiltRowStatus           RowStatus
}

spdIpOffFiltName OBJECT-TYPE
  SYNTAX      SnmpAdminString (SIZE(1..32))
  MAX-ACCESS  not-accessible
  STATUS      current
   DESCRIPTION
     "The administrative name for this filter."
  ::= { spdIpOffsetFilterEntry 1 }

spdIpOffFiltOffset OBJECT-TYPE
  SYNTAX      Unsigned32 (0..65535)
```

```
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This is the byte offset from the front of the entire IP
      packet where the value or arithmetic comparison is done.  A
      value of '0' indicates the first byte of the packet header.
      If this value is greater than the length of the packet, the
      filter represented by this row should be considered to
      fail."
  ::= { spdIpOffsetFilterEntry 2 }

spdIpOffFiltType OBJECT-TYPE
  SYNTAX INTEGER { equal(1),
                   notEqual(2),
                   arithmeticLess(3),
                   arithmeticGreaterOrEqual(4),
                   arithmeticGreater(5),
                   arithmeticLessOrEqual(6) }
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This defines the
 various tests that are used when
      evaluating a given filter.

      The various tests definable in this table are as follows:

      equal:
        - Tests if the OCTET STRING, 'spdIpOffFiltValue', matches



          a value in the packet starting at the given offset in
          the packet and comparing the entire OCTET STRING of
          'spdIpOffFiltValue'.  Any values compared this way are
          assumed to be unsigned integer values in network byte
          order of the same length as 'spdIpOffFiltValue'.

      notEqual:
        - Tests if the OCTET STRING, 'spdIpOffFiltValue', does
          not match a value in the packet starting at the given
          offset in the packet and comparing to the entire OCTET
          STRING of 'spdIpOffFiltValue'.  Any values compared
          this way are assumed to be unsigned integer values in
          network byte order of the same length as
          'spdIpOffFiltValue'.
```

arithmeticLess:
- Tests if the OCTET STRING, 'spdIpOffFiltValue', is arithmetically less than ('<') the value starting at the given offset within the packet. The value in the packet is assumed to be an unsigned integer in network byte order of the same length as 'spdIpOffFiltValue'.

arithmeticGreaterOrEqual:
- Tests if the OCTET STRING, 'spdIpOffFiltValue', is arithmetically greater than or equal to ('>=') the value starting at the given offset within the packet. The value in the packet is assumed to be an unsigned integer in network byte order of the same length as 'spdIpOffFiltValue'.

arithmeticGreater:
- Tests if the OCTET STRING, 'spdIpOffFiltValue', is arithmetically greater than ('>') the value starting at the given offset within the packet. The value in the packet is
assumed to be an unsigned integer in network
byte order of the same length as 'spdIpOffFiltValue'.

arithmeticLessOrEqual:
- Tests if the OCTET STRING, 'spdIpOffFiltValue', is arithmetically less than or equal to ('<=') the value starting at the given offset within the packet. The value in the packet is assumed to be an unsigned integer in network byte order of the same length as 'spdIpOffFiltValue'."

::= { spdIpOffsetFilterEntry 3 }

spdIpOffFiltValue OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(1..1024))
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"spdIpOffFiltValue is used for match comparisons of a packet at spdIpOffFiltOffset."
::= { spdIpOffsetFilterEntry 4 }

spdIpOffFiltLastChanged OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only

```
  STATUS      current
  DESCRIPTION
      "The value of sysUpTime when this
 row was last modified
      or created either through SNMP SETs or by some other
      external means.

      If this row has not been modified since the last
      re-initialization of the network management subsystem, this
      object SHOULD have a zero value."
  ::= { spdIpOffsetFilterEntry 5 }


spdIpOffFiltStorageType OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "The storage type for this row.  Rows in this table that
      were created through an external process MAY have a
      storage type of readOnly or permanent.

      For a storage type of permanent, none of the columns have
      to be writable."
  DEFVAL { nonVolatile }
  ::= { spdIpOffsetFilterEntry 6 }

spdIpOffFiltRowStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "This object indicates the conceptual status of this row.

      The value of
 this object has no effect on whether other
      objects in this conceptual row can be modified.

      If active, this object MUST remain active if it is



      referenced by an active row in another table.  An attempt
      to set it to anything other than active while it is
      referenced by an active row in another table MUST result in
      an inconsistentValue error."
  ::= { spdIpOffsetFilterEntry 7 }
```

```
--
-- Time/scheduling filter table
--

spdTimeFilterTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SpdTimeFilterEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "Defines a table of filters that can be used to
      effectively enable or disable policies based on a valid
      time range."
  ::= { spdConfigObjects 9 }

spdTimeFilterEntry OBJECT-TYPE
  SYNTAX      SpdTimeFilterEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A row describing a given time frame for which a policy
       is filtered on to activate or deactivate the rule.

      If all the column objects in a row are true for the current
      time, the row evaluates as 'true'.  More explicitly, the
      time matching column objects in a row MUST be logically
      ANDed together to form the boolean true/false for the row."
  INDEX   { spdTimeFiltName }
  ::= { spdTimeFilterTable 1 }

SpdTimeFilterEntry ::= SEQUENCE {
  spdTimeFiltName               SnmpAdminString,
  spdTimeFiltPeriod             SpdTimePeriod,
  spdTimeFiltMonthOfYearMask      BITS,
  spdTimeFiltDayOfMonthMask       OCTET STRING,
  spdTimeFiltDayOfWeekMask        BITS,
  spdTimeFiltTimeOfDayMask       SpdTimePeriod,
  spdTimeFiltLastChanged          TimeStamp,
  spdTimeFiltStorageType          StorageType,
  spdTimeFiltRowStatus            RowStatus
}




spdTimeFiltName OBJECT-TYPE
  SYNTAX      SnmpAdminString (SIZE(1..32))
  MAX-ACCESS  not-accessible
```

```
  STATUS      current
   DESCRIPTION
      "An administratively assigned name for this filter."
  ::= { spdTimeFilterEntry 1 }


spdTimeFiltPeriod OBJECT-TYPE
  SYNTAX      SpdTimePeriod
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The valid time period for this filter.  This column is
      considered 'true' if the current time is within the range of
      this object."
  DEFVAL { "THISANDPRIOR/THISANDFUTURE" }
  ::= { spdTimeFilterEntry 2 }


spdTimeFiltMonthOfYearMask OBJECT-TYPE
  SYNTAX      BITS { january(0), february(1), march(2),
                     april(3), may(4), june(5), july(6),
                     august(7), september(8), october(9),
                     november(10), december(11) }
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "A bit mask that indicates acceptable months of the year.
      This column evaluates to 'true' if the current month's bit
      is set."
  DEFVAL { { january, february, march,
 april, may, june, july,
           august, september, october, november, december } }
  ::= { spdTimeFilterEntry 3 }

spdTimeFiltDayOfMonthMask OBJECT-TYPE
  SYNTAX      OCTET STRING (SIZE(8))
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "Defines which days of the month the current time is
      valid for.  It is a sequence of 64 BITS, where each BIT
      represents a corresponding day of the month in forward or
      reverse order.  Starting from the left-most bit, the first
      31 bits identify the day of the month, counting from the
      beginning of the month.  The following 31 bits (bits 32-62)
      indicate the day of the month, counting from the end of the
```

```
        month.  For months with fewer than 31 days, the bits that
        correspond to the non-existent days of that month are
        ignored (e.g., for non-leap year Februarys, bits 29-31 and
        60-62 are ignored).

        This column evaluates
 to 'true' if the current day of the
        month's bit is set.

        For example, a value of 0X'80 00 00 01 00 00 00 00'
        indicates that this column evaluates to true on the first
        and last days of the month.

        The last two bits in the string MUST be zero."
    DEFVAL { 'fffffffffffffffe'H }
    ::= { spdTimeFilterEntry 4 }

spdTimeFiltDayOfWeekMask OBJECT-TYPE
    SYNTAX      BITS { sunday(0), monday(1), tuesday(2),
                       wednesday(3), thursday(4), friday(5),
                       saturday(6) }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
       "A bit mask that defines which days of the week that the current
        time is valid for.  This column evaluates to 'true' if the
        current day of the week's bit is set."
    DEFVAL { { monday, tuesday, wednesday, thursday, friday,
             saturday, sunday } }
    ::= { spdTimeFilterEntry 5 }

spdTimeFiltTimeOfDayMask OBJECT-TYPE
    SYNTAX      SpdTimePeriod
     MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
       "Indicates the start and end time of the day for which this
        filter evaluates to true.  The date portions of the
        spdTimePeriod TC are ignored for purposes of evaluating this
        mask, and only the time-specific portions are used.

        This column evaluates to 'true' if the current time of day
        is within the range of the start and end times of the day
        indicated by this object."
    DEFVAL { "00000000T000000/00000000T240000" }
    ::= { spdTimeFilterEntry 6 }
```

```
spdTimeFiltLastChanged OBJECT-TYPE
  SYNTAX      TimeStamp



  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The value of sysUpTime when this row was last modified
      or created either through SNMP SETs or by some other
      external means.

      If this row has not been modified since the last
      re-initialization of the network management subsystem, this

     object SHOULD have a zero value."
  ::= { spdTimeFilterEntry 7 }

spdTimeFiltStorageType OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The storage type for this row.  Rows in this table that
      were created through an external process MAY have a storage
      type of readOnly or permanent.

      For a storage type of permanent, none of the columns have
      to be writable."
  DEFVAL { nonVolatile }
  ::= { spdTimeFilterEntry 8 }

spdTimeFiltRowStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object indicates the conceptual status of this
      row.

      The value of this object has no effect on whether other
      objects in this conceptual row can be modified.

      If active, this object MUST remain active if it is
      referenced by an active row in another table.  An attempt
      to set
 it to anything other than active while it is
      referenced by an active row in another table MUST result in
```

```
        an inconsistentValue error."
    ::= { spdTimeFilterEntry 9 }

--
-- IPSO protection authority filtering
--



spdIpsoHeaderFilterTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF SpdIpsoHeaderFilterEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains a list of IPSO header filter
        definitions to be used within the spdRuleDefinitionTable or
        the spdSubfiltersTable.  IPSO headers and their values are
        described in RFC 1108."
    REFERENCE "RFC 1108"
    ::= { spdConfigObjects 10 }

spdIpsoHeaderFilterEntry OBJECT-TYPE
    SYNTAX      SpdIpsoHeaderFilterEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A definition of a particular filter."
    INDEX       {  spdIpsoHeadFiltName }
    ::= { spdIpsoHeaderFilterTable 1 }

SpdIpsoHeaderFilterEntry ::= SEQUENCE
 {
    spdIpsoHeadFiltName                 SnmpAdminString,
    spdIpsoHeadFiltType                 BITS,
    spdIpsoHeadFiltClassification       INTEGER,
    spdIpsoHeadFiltProtectionAuth       INTEGER,
    spdIpsoHeadFiltLastChanged          TimeStamp,
    spdIpsoHeadFiltStorageType          StorageType,
    spdIpsoHeadFiltRowStatus            RowStatus
}

spdIpsoHeadFiltName OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(1..32))
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The administrative name for this filter."
```

```
  ::= { spdIpsoHeaderFilterEntry 1 }

spdIpsoHeadFiltType OBJECT-TYPE
  SYNTAX      BITS { classificationLevel(0),
                     protectionAuthority(1) }
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object indicates which of the IPSO header field a
      packet is filtered on for this row.  If this object is set
      to classification(0), the spdIpsoHeadFiltClassification



       object indicates how the packet is filtered.  If this object
      is set to protectionAuthority(1), the
      spdIpsoHeadFiltProtectionAuth object indicates how the
      packet is filtered."
  ::= { spdIpsoHeaderFilterEntry 2 }

spdIpsoHeadFiltClassification OBJECT-TYPE
  SYNTAX      INTEGER { topSecret(61), secret(90),
                        confidential(150), unclassified(171) }
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object indicates the IPSO classification header field
      value that the packet MUST have for this row to evaluate to
      'true'.

      The values of these enumerations are defined by RFC 1108."
  REFERENCE "RFC 1108"
  ::= { spdIpsoHeaderFilterEntry 3 }

spdIpsoHeadFiltProtectionAuth OBJECT-TYPE
  SYNTAX      INTEGER { genser(0), siopesi(1), sci(2),
                        nsa(3), doe(4) }
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "This object indicates the IPSO protection authority header
      field value that the packet MUST have for this row to
      evaluate to 'true'.

      The values of these enumerations are defined by RFC 1108.
      Hence the reason the SMIv2 convention of not using 0 in
      enumerated lists is violated here."
  REFERENCE "RFC 1108"
```

```
  ::= { spdIpsoHeaderFilterEntry 4 }

spdIpsoHeadFiltLastChanged OBJECT-TYPE
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The value of sysUpTime when this row was last modified
      or created either through SNMP SETs or by some other
      external means.

      If this row has not been modified since the last
      re-initialization of the network management subsystem, this
      object SHOULD have a zero value."



  ::= { spdIpsoHeaderFilterEntry 5 }

spdIpsoHeadFiltStorageType OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS
    current
  DESCRIPTION
     "The storage type for this row.  Rows in this table that
      were created through an external process MAY have a storage
      type of readOnly or permanent.

      For a storage type of permanent, none of the columns have
      to be writable."
  DEFVAL { nonVolatile }
  ::= { spdIpsoHeaderFilterEntry 6 }

spdIpsoHeadFiltRowStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object indicates the conceptual status of this row.

      The value of this object has no effect on whether other
      objects in this conceptual row can be modified.

      However, this object MUST NOT be set to active if the
      requirements of the spdIpsoHeadFiltType object are not met.
      Specifically, if the spdIpsoHeadFiltType bit for
      classification(0) is set, the spdIpsoHeadFiltClassification
```

```
        column MUST have a valid value for the row
 status to be set
        to active.  If the spdIpsoHeadFiltType bit for
        protectionAuthority(1) is set, the
        spdIpsoHeadFiltProtectionAuth column MUST have a valid
        value for the row status to be set to active.

        If active, this object MUST remain active if it is
        referenced by an active row in another table.  An attempt
        to set it to anything other than active while it is
        referenced by an active row in another table MUST result in
        an inconsistentValue error."
  ::= { spdIpsoHeaderFilterEntry 7 }

--
-- compound actions table
--

spdCompoundActionTable OBJECT-TYPE



  SYNTAX      SEQUENCE OF SpdCompoundActionEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "Table used to allow multiple actions to be associated
       with a rule.  It uses the spdSubactionsTable to do this.
       The rows from spdSubactionsTable that are partially indexed
       by spdCompActName form the
 set of compound actions to be
       performed.  The spdCompActExecutionStrategy column in this
       table indicates how those actions are processed."
  ::= { spdConfigObjects 11 }

spdCompoundActionEntry OBJECT-TYPE
  SYNTAX      SpdCompoundActionEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A row in the spdCompoundActionTable."
  INDEX   { spdCompActName }
  ::= { spdCompoundActionTable 1 }

SpdCompoundActionEntry ::= SEQUENCE {
  spdCompActName                  SnmpAdminString,
  spdCompActExecutionStrategy        INTEGER,
  spdCompActLastChanged              TimeStamp,
```

```
  spdCompActStorageType             StorageType,
  spdCompActRowStatus               RowStatus
}

spdCompActName OBJECT-TYPE
  SYNTAX      SnmpAdminString (SIZE(1..32))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "This is an administratively assigned name of this
      compound action."
  ::= { spdCompoundActionEntry
 1 }

spdCompActExecutionStrategy OBJECT-TYPE
  SYNTAX      INTEGER { doAll(1),
                        doUntilSuccess(2),
                        doUntilFailure(3) }
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object indicates how the sub-actions are executed
      based on the success of the actions as they finish
      executing.



      doAll          - run each sub-action regardless of the
                       exit status of the previous action.
                       This parent action is always
                       considered to have acted successfully.

      doUntilSuccess  - run each sub-action until one succeeds,
                       at which point stop processing the
                       sub-actions within this parent
                       compound action.  If one of the
                       sub-actions did execute successfully,
                       this parent
 action is also considered
                       to have executed successfully.

      doUntilFailure  - run each sub-action until one fails,
                       at which point stop processing the
                       sub-actions within this compound
                       action.  If any sub-action fails, the
                       result of this parent action is
                       considered to have failed."
  DEFVAL { doUntilSuccess }
```

```
  ::= { spdCompoundActionEntry 2 }

spdCompActLastChanged OBJECT-TYPE
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The value of sysUpTime when this row was last modified
      or created either through SNMP SETs or by some other
      external means.

      If this row has not been modified since the last
      re-initialization of the network management subsystem, this
      object SHOULD have a zero value."
  ::= { spdCompoundActionEntry
 3 }

spdCompActStorageType OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The storage type for this row.  Rows in this table that
      were created through an external process MAY have a storage
      type of readOnly or permanent.

      For a storage type of permanent, none of the columns have
      to be writable."
  DEFVAL { nonVolatile }



  ::= { spdCompoundActionEntry 4 }

spdCompActRowStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object indicates the conceptual status of this row.

      The value of this object has no effect on whether other
      objects in this conceptual row can be modified.

      Once a row in the spdCompoundActionTable has been made
      active, this object MUST NOT be set to destroy without
      first destroying all the contained rows listed in the
      spdSubactionsTable."
```

```
    ::= { spdCompoundActionEntry 5 }


--
-- actions contained within a compound action
--

spdSubactionsTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SpdSubactionsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "This table contains a list of the sub-actions within a
       given compound action.  Compound actions executing these
       actions MUST execute them in series based on the
       spdSubActPriority value, with the lowest value executing
       first."
  ::= { spdConfigObjects 12 }

spdSubactionsEntry OBJECT-TYPE
  SYNTAX      SpdSubactionsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A row containing a reference to a given compound-action
       sub-action."
  INDEX   { spdCompActName, spdSubActPriority }
  ::= { spdSubactionsTable 1 }

SpdSubactionsEntry ::= SEQUENCE {
  spdSubActPriority                   Integer32,
  spdSubActSubActionName
  VariablePointer,



  spdSubActLastChanged                 TimeStamp,
  spdSubActStorageType                 StorageType,
  spdSubActRowStatus                   RowStatus
}

spdSubActPriority OBJECT-TYPE
  SYNTAX      Integer32 (0..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "The priority of a given sub-action within a compound
       action.  The order in which sub-actions MUST be executed
```

are based on the value from this column, with the lowest
numeric value executing first (i.e., priority 0 before
priority 1, 1 before 2, etc.)."
::= { spdSubactionsEntry 1 }

spdSubActSubActionName OBJECT-TYPE
SYNTAX VariablePointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This column points to the action to be taken. It MAY,
but is not limited to, point to a row in one of the
following tables:

spdCompoundActionTable
- Allowing recursion
ipsaSaPreconfiguredActionTable
ipiaIkeActionTable
ipiaIpsecActionTable

It MAY also point to one of the scalar objects beneath
spdStaticActions.

If this object is set to a pointer to a row in an
unsupported (or unknown) table, an inconsistentValue
error MUST be returned.

If this object is set to point to a non-existent row in
an otherwise supported table, an inconsistentName error
MUST be returned.

If, during packet processing, this column has a value that
references a non-existent or non-supported object, the
packet MUST be dropped."
::= { spdSubactionsEntry 2 }

spdSubActLastChanged OBJECT-TYPE

SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime when this row was last modified
or created either through SNMP SETs or by some other
external

means.

If this row has not been modified since the last
re-initialization of the network management subsystem, this
object SHOULD have a zero value."
::= { spdSubactionsEntry 3 }

spdSubActStorageType OBJECT-TYPE
SYNTAX StorageType
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The storage type for this row. Rows in this table that
were created through an external process MAY have a storage
type of readOnly or permanent.

For a storage type of permanent, none of the columns have
to be writable."
DEFVAL { nonVolatile }
::= { spdSubactionsEntry 4 }

spdSubActRowStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This object indicates the conceptual status of this row.

The value of this object has no effect on whether other
objects in this conceptual row can be modified.

If active, this object MUST remain active unless one of the
following two conditions are met. An attempt to set it to
anything other than active while the following conditions
are not met MUST result in an inconsistentValue error. The
two conditions are:

I. No active row in the spdCompoundActionTable exists
which has a matching spdCompActName.

II. Or, at least one other active row in this table has a
matching spdCompActName."

::= { spdSubactionsEntry 5 }

```
--
-- Static Actions
--

-- these are static actions that can be pointed to by the
-- spdRuleDefAction or the spdSubActSubActionName objects to
-- drop, accept, or reject packets.

spdStaticActions OBJECT IDENTIFIER ::= { spdConfigObjects 13 }

spdDropAction    OBJECT-TYPE
  SYNTAX      Integer32 (1)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "This scalar indicates that a packet MUST be dropped
       and SHOULD
 NOT have action/packet logging."
  ::= { spdStaticActions 1 }

spdDropActionLog OBJECT-TYPE
  SYNTAX      Integer32 (1)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "This scalar indicates that a packet MUST be dropped
       and SHOULD have action/packet logging."
  ::= { spdStaticActions 2 }

spdAcceptAction OBJECT-TYPE
  SYNTAX      Integer32 (1)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "This Scalar indicates that a packet MUST be accepted
       (pass-through) and SHOULD NOT have action/packet logging."
  ::= { spdStaticActions 3 }

spdAcceptActionLog OBJECT-TYPE
  SYNTAX      Integer32 (1)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "This scalar indicates that a packet MUST be accepted
       (pass-through) and SHOULD have action/packet logging."
  ::= { spdStaticActions 4 }
```

```
--
--
-- Notification objects information
--
--

spdNotificationVariables OBJECT IDENTIFIER
 ::=
  { spdNotificationObjects 1 }

spdNotifications OBJECT IDENTIFIER ::=
  { spdNotificationObjects 0 }

spdActionExecuted OBJECT-TYPE
   SYNTAX      VariablePointer
   MAX-ACCESS  accessible-for-notify
   STATUS      current
   DESCRIPTION
       "Points to the action instance that was executed that
        resulted in the notification being sent."
   ::= { spdNotificationVariables 1 }

spdIPEndpointAddType OBJECT-TYPE
   SYNTAX      InetAddressType
   MAX-ACCESS  accessible-for-notify
   STATUS      current
   DESCRIPTION
       "Contains the address type for the interface that the
        notification triggering packet is passing through."
   ::= { spdNotificationVariables 2 }

spdIPEndpointAddress OBJECT-TYPE
   SYNTAX      InetAddress
   MAX-ACCESS  accessible-for-notify
   STATUS      current
   DESCRIPTION
       "Contains the interface address for the interface that the
        notification triggering packet is passing through.

        The format of
 this object is specified by the
        spdIPEndpointAddType object."
   ::= { spdNotificationVariables 3 }

spdIPSourceType OBJECT-TYPE
   SYNTAX      InetAddressType
```

```
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
     "Contains the source address type of the packet that




      triggered the notification."
  ::= { spdNotificationVariables 4 }

spdIPSourceAddress OBJECT-TYPE
  SYNTAX      InetAddress
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
     "Contains the source address of the packet that
      triggered the notification.

      The format of this object is specified by the
      spdIPSourceType object."
  ::= { spdNotificationVariables 5 }

spdIPDestinationType OBJECT-TYPE
  SYNTAX      InetAddressType
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
     "Contains the destination address type of the packet
      that triggered the notification."
   ::= { spdNotificationVariables 6 }

spdIPDestinationAddress OBJECT-TYPE
  SYNTAX      InetAddress
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
     "Contains the destination address of the packet that
      triggered the notification.

      The format of this object is specified by the
      spdIPDestinationType object."
  ::= { spdNotificationVariables 7 }

spdPacketDirection OBJECT-TYPE
  SYNTAX      IfDirection
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
```

```
      "Indicates if the packet that triggered the action in
       questions was ingress (inbound) or egress (outbound)."
  ::= { spdNotificationVariables 8 }

spdPacketPart OBJECT-TYPE
  SYNTAX      OCTET STRING (SIZE (0..65535))
  MAX-ACCESS  accessible-for-notify



  STATUS      current
  DESCRIPTION
      "spdPacketPart is the front part of the full IP packet that
       triggered this notification.  The initial size limit
is
       determined by the smaller of the size, indicated by:

       I.  The value of the object with the TC syntax
          'SpdIPPacketLogging' that indicated the packet SHOULD be
          logged and

       II. The size of the triggering packet.

       The final limit is determined by the SNMP packet size when
       sending the notification.  The maximum size that can be
       included will be the smaller of the initial size, given the
       above, and the length that will fit in a single SNMP
       notification packet after the rest of the notification's
       objects and any other necessary packet data (headers encoding,
       etc.) have been included in the packet."
  ::= { spdNotificationVariables 9 }

spdActionNotification NOTIFICATION-TYPE
  OBJECTS { spdActionExecuted, spdIPEndpointAddType,
            spdIPEndpointAddress,
            spdIPSourceType, spdIPSourceAddress,
            spdIPDestinationType,
            spdIPDestinationAddress,
             spdPacketDirection }
  STATUS  current
  DESCRIPTION
      "Notification that an action was executed by a rule.
       Only actions with logging enabled will result in this
       notification getting sent.  The object includes the
       spdActionExecuted object, which will indicate which action
       was executed within the scope of the rule.  Additionally,
       the spdIPSourceType, spdIPSourceAddress,
       spdIPDestinationType, and spdIPDestinationAddress objects
```

```
        are included to indicate the packet source and destination
        of the packet that triggered the action.  Finally, the
        spdIPEndpointAddType, spdIPEndpointAddress, and
        spdPacketDirection objects indicate which interface the
        executed action was associated with, and if the packet was
        ingress or egress through the endpoint.

        A spdActionNotification SHOULD be limited to a maximum of
        one notification sent per minute
    for any action
        notifications that do not have any other configuration
        controlling their send rate.



        Note that compound actions with multiple executed
        sub-actions may result in multiple notifications being sent
        from a single rule execution."
    ::= { spdNotifications 1 }

spdPacketNotification NOTIFICATION-TYPE
    OBJECTS { spdActionExecuted, spdIPEndpointAddType,
              spdIPEndpointAddress,
              spdIPSourceType, spdIPSourceAddress,
              spdIPDestinationType,
              spdIPDestinationAddress,
              spdPacketDirection,
              spdPacketPart }
    STATUS  current
    DESCRIPTION
       "Notification that a packet passed through a Security
        Association (SA).  Only SAs created by actions with packet
        logging enabled will result in this notification getting
        sent.  The objects sent MUST include the spdActionExecuted,
        which will indicate which action was executed
    within the
        scope of the rule.  Additionally, the spdIPSourceType,
        spdIPSourceAddress, spdIPDestinationType, and
        spdIPDestinationAddress objects MUST be included to
        indicate the packet source and destination of the packet
        that triggered the action.  The spdIPEndpointAddType,
        spdIPEndpointAddress, and spdPacketDirection objects are
        included to indicate which endpoint the packet was
        associated with.  Finally, spdPacketPart is included to
        enable sending a variable sized part of the front of the
        packet with the size dependent on the value of the object of
        TC syntax 'SpdIPPacketLogging', which indicated that logging
        should be done.
```

```
        A spdPacketNotification SHOULD be limited to a maximum of
        one notification sent per minute for any action
        notifications that do not have any other configuration
        controlling their send rate.

        An action notification
 SHOULD be limited to a maximum of
        one notification sent per minute for any action
        notifications that do not have any other configuration
        controlling their send rate."
   ::= { spdNotifications 2 }


--
--
-- Conformance information



--
--

spdCompliances OBJECT IDENTIFIER
   ::= { spdConformanceObjects 1 }
spdGroups OBJECT IDENTIFIER
   ::= { spdConformanceObjects 2 }

--
-- Compliance statements
--
--
spdRuleFilterFullCompliance MODULE-COMPLIANCE
   STATUS      current
   DESCRIPTION
       "The compliance statement for SNMP entities that include
        an IPsec MIB implementation with Endpoint, Rules, and
        filters support.

        When this MIB is implemented with support for read-create,
        then such an implementation can claim full compliance.  Such
        devices can then be both monitored and configured with this
        MIB."

   MODULE -- This Module
      MANDATORY-GROUPS { spdEndpointGroup,
```

```
spdGroupContentsGroup,
                spdRuleDefinitionGroup,
                spdStaticFilterGroup,
                spdStaticActionGroup ,
                diffServMIBMultiFieldClfrGroup }

 GROUP spdIpsecSystemPolicyNameGroup
 DESCRIPTION
    "This group is mandatory for IPsec Policy
     implementations that support a system policy group
     name."

 GROUP spdCompoundFilterGroup
 DESCRIPTION
    "This group is mandatory for IPsec Policy
     implementations that support compound filters."

 GROUP spdIPOffsetFilterGroup
 DESCRIPTION
    "This group is mandatory for IPsec Policy
     implementations that support IP Offset filters.  In
     general, this SHOULD be supported by a compliant IPsec



     Policy implementation."

 GROUP spdTimeFilterGroup
 DESCRIPTION
    "This group is mandatory for IPsec Policy
      implementations that support time filters."

 GROUP spdIpsoHeaderFilterGroup
 DESCRIPTION
    "This group is mandatory for IPsec Policy
     implementations that support IPSO Header filters."

 GROUP  spdCompoundActionGroup
 DESCRIPTION
    "This group is mandatory for IPsec Policy
     implementations that support compound actions."

 OBJECT      spdEndGroupLastChanged
 MIN-ACCESS  not-accessible
 DESCRIPTION
    "This object not required for compliance."

 OBJECT      spdGroupContComponentType
```

```
SYNTAX      INTEGER {
       rule(2)
}
DESCRIPTION
    "Support of the value group(1) is only required for
     implementations that support Policy Groups within
     Policy Groups."

OBJECT      spdGroupContLastChanged
MIN-ACCESS  not-accessible
DESCRIPTION
    "This object not required for compliance."

 OBJECT      spdRuleDefLastChanged
MIN-ACCESS  not-accessible
DESCRIPTION
    "This object not required for compliance."

OBJECT      spdCompFiltLastChanged
MIN-ACCESS  not-accessible
DESCRIPTION
    "This object not required for compliance."

OBJECT      spdSubFiltLastChanged
MIN-ACCESS  not-accessible



DESCRIPTION
     "This object not required for compliance."

OBJECT      spdIpOffFiltLastChanged
MIN-ACCESS  not-accessible
DESCRIPTION
    "This object not required for compliance."

OBJECT      spdTimeFiltLastChanged
MIN-ACCESS  not-accessible
DESCRIPTION
    "This object not required for compliance."

OBJECT      spdIpsoHeadFiltLastChanged
MIN-ACCESS  not-accessible
DESCRIPTION
    "This object not required for compliance."

OBJECT      spdCompActLastChanged
MIN-ACCESS
```

```
  not-accessible
      DESCRIPTION
          "This object not required for compliance."

      OBJECT      spdSubActLastChanged
      MIN-ACCESS  not-accessible
      DESCRIPTION
          "This object not required for compliance."

      OBJECT      diffServMultiFieldClfrNextFree
      MIN-ACCESS  not-accessible
      DESCRIPTION
          "This object is not required for compliance."

  ::= { spdCompliances 1 }


spdLoggingCompliance MODULE-COMPLIANCE
  STATUS      current
  DESCRIPTION
      "The compliance statement for SNMP entities that support
       sending notifications when actions are invoked."
  MODULE -- This Module
      MANDATORY-GROUPS { spdActionLoggingObjectGroup,
                         spdActionNotificationGroup }

  ::= { spdCompliances 2 }

--



-- ReadOnly Compliances
--
spdRuleFilterReadOnlyCompliance MODULE-COMPLIANCE
  STATUS      current
  DESCRIPTION
      "The compliance statement for SNMP entities that include
       an IPsec MIB implementation with Endpoint, Rules, and
       filters support.

       If this MIB is implemented without support for read-create
       (i.e., in read-only), it is not in full compliance, but it
       can claim read-only compliance.  Such a device can then be
       monitored, but cannot be configured with this MIB."

  MODULE -- This Module
      MANDATORY-GROUPS { spdEndpointGroup,
```

```
                spdGroupContentsGroup,
                spdRuleDefinitionGroup,
                spdStaticFilterGroup,
                spdStaticActionGroup ,
                diffServMIBMultiFieldClfrGroup }

    GROUP spdIpsecSystemPolicyNameGroup
    DESCRIPTION
      "This group is mandatory for IPsec Policy
       implementations that support a system policy group
       name."

    GROUP spdCompoundFilterGroup
    DESCRIPTION
      "This group is mandatory for IPsec Policy
        implementations that support compound filters."

    GROUP spdIPOffsetFilterGroup
    DESCRIPTION
      "This group is mandatory for IPsec Policy
       implementations that support IP Offset filters.  In
       general, this SHOULD be supported by a compliant IPsec
       Policy implementation."

    GROUP spdTimeFilterGroup
    DESCRIPTION
      "This group is mandatory for IPsec Policy
       implementations that support time filters."

    GROUP spdIpsoHeaderFilterGroup
    DESCRIPTION
      "This group is mandatory for IPsec Policy




       implementations that support IPSO Header filters."

    GROUP  spdCompoundActionGroup
    DESCRIPTION
      "This group is mandatory for IPsec Policy
       implementations that support compound actions."

    OBJECT      spdCompActExecutionStrategy
    MIN-ACCESS   read-only
    DESCRIPTION
      "Write access is not
required."
```

OBJECT spdCompActLastChanged
DESCRIPTION
"This object is not required for compliance."

OBJECT spdCompActRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdCompActStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdCompFiltDescription
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdCompFiltLastChanged
DESCRIPTION
"This object is not required for compliance."

OBJECT spdCompFiltLogicType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdCompFiltRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdCompFiltStorageType

MIN-ACCESS read-only
DESCRIPTION

"Write access is not required."

OBJECT spdEgressPolicyGroupName
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdEndGroupLastChanged

DESCRIPTION
"This object is not required for compliance."

OBJECT spdEndGroupName
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdEndGroupRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdEndGroupStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdGroupContComponentName
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdGroupContComponentType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdGroupContFilter
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdGroupContLastChanged
DESCRIPTION
"This object is not required for compliance."

OBJECT spdGroupContRowStatus
MIN-ACCESS read-only
DESCRIPTION

"Write access is not required."

OBJECT spdGroupContStorageType
MIN-ACCESS read-only
DESCRIPTION

"Write access is not required."

OBJECT spdIngressPolicyGroupName
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpOffFiltLastChanged
DESCRIPTION
"This object is not required for compliance."

OBJECT spdIpOffFiltOffset
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpOffFiltRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpOffFiltStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpOffFiltType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpOffFiltValue
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpsoHeadFiltClassification
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpsoHeadFiltLastChanged
DESCRIPTION

"This object is not required for compliance."

OBJECT spdIpsoHeadFiltProtectionAuth
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpsoHeadFiltRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpsoHeadFiltStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpsoHeadFiltType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdRuleDefAction
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdRuleDefAdminStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdRuleDefDescription
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdRuleDefFilter
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdRuleDefFilterNegated
MIN-ACCESS
read-only
DESCRIPTION
"Write access is not required."

OBJECT spdRuleDefLastChanged

DESCRIPTION
"This object is not required for compliance."

OBJECT spdRuleDefRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdRuleDefStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdSubActLastChanged
DESCRIPTION
"This object is not required for compliance."

OBJECT spdSubActRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdSubActStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdSubActSubActionName
MIN-ACCESS read-only
DESCRIPTION
"Write access
is not required."

OBJECT spdSubFiltLastChanged
DESCRIPTION
"This object is not required for compliance."

OBJECT spdSubFiltRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdSubFiltStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdSubFiltSubfilter
MIN-ACCESS read-only

DESCRIPTION
"Write access is not required."

OBJECT spdSubFiltSubfilterIsNegated
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdTimeFiltDayOfMonthMask
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdTimeFiltDayOfWeekMask
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT
spdTimeFiltLastChanged
DESCRIPTION
"This object is not required for compliance."

OBJECT spdTimeFiltMonthOfYearMask
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdTimeFiltPeriod
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdTimeFiltRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdTimeFiltTimeOfDayMask
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

```
        OBJECT       spdTimeFiltStorageType
        MIN-ACCESS   read-only
        DESCRIPTION
            "Write access is not required."

    ::= { spdCompliances 3 }



--
--
-- Compliance Groups Definitions
--

--
-- Endpoint, Rule, Filter Compliance Groups
--

spdEndpointGroup OBJECT-GROUP
    OBJECTS {
        spdEndGroupName,
   spdEndGroupLastChanged,
        spdEndGroupStorageType, spdEndGroupRowStatus
    }
    STATUS current
    DESCRIPTION
        "This group is made up of objects from the IPsec Policy
         Endpoint Table."
    ::= { spdGroups 1 }

spdGroupContentsGroup OBJECT-GROUP
    OBJECTS {
        spdGroupContComponentType, spdGroupContFilter,
        spdGroupContComponentName, spdGroupContLastChanged,
        spdGroupContStorageType, spdGroupContRowStatus
    }
    STATUS current
    DESCRIPTION
        "This group is made up of objects from the IPsec Policy
         Group Contents Table."
    ::= { spdGroups 2 }

spdIpsecSystemPolicyNameGroup OBJECT-GROUP
    OBJECTS {
        spdIngressPolicyGroupName,
        spdEgressPolicyGroupName
    }
```

```
  STATUS current
  DESCRIPTION
      "This group is made up of objects represent the System
       Policy Group Names."
  ::= { spdGroups 3}

spdRuleDefinitionGroup OBJECT-GROUP
  OBJECTS {
      spdRuleDefDescription, spdRuleDefFilter,
       spdRuleDefFilterNegated, spdRuleDefAction,
      spdRuleDefAdminStatus, spdRuleDefLastChanged,




      spdRuleDefStorageType, spdRuleDefRowStatus
  }
  STATUS current
  DESCRIPTION
      "This group is made up of objects from the IPsec Policy Rule
      Definition Table."
  ::= { spdGroups 4 }

spdCompoundFilterGroup OBJECT-GROUP
  OBJECTS {
      spdCompFiltDescription, spdCompFiltLogicType,
      spdCompFiltLastChanged, spdCompFiltStorageType,
      spdCompFiltRowStatus, spdSubFiltSubfilter,
      spdSubFiltSubfilterIsNegated, spdSubFiltLastChanged,
      spdSubFiltStorageType, spdSubFiltRowStatus
  }
  STATUS current
  DESCRIPTION
      "This group is made up of objects from the IPsec Policy
       Compound Filter Table and Sub-Filter Table Group."
  ::= { spdGroups 5 }

spdStaticFilterGroup OBJECT-GROUP
      OBJECTS { spdTrueFilter }
   STATUS current
   DESCRIPTION
       "The static filter group.  Currently this is just
 a true
        filter."
  ::= { spdGroups 6 }

spdIPOffsetFilterGroup OBJECT-GROUP
  OBJECTS {
      spdIpOffFiltOffset, spdIpOffFiltType,
```

```
        spdIpOffFiltValue, spdIpOffFiltLastChanged,
        spdIpOffFiltStorageType, spdIpOffFiltRowStatus
    }

    STATUS current
    DESCRIPTION
        "This group is made up of objects from the IPsec Policy IP
         Offset Filter Table."
    ::= { spdGroups 7 }

spdTimeFilterGroup OBJECT-GROUP
    OBJECTS {
        spdTimeFiltPeriod,
        spdTimeFiltMonthOfYearMask, spdTimeFiltDayOfMonthMask,
        spdTimeFiltDayOfWeekMask, spdTimeFiltTimeOfDayMask,




        spdTimeFiltLastChanged,
        spdTimeFiltStorageType, spdTimeFiltRowStatus
    }
    STATUS current
    DESCRIPTION
        "This group is made up of objects from the IPsec Policy Time
         Filter Table."
    ::= { spdGroups 8 }

spdIpsoHeaderFilterGroup OBJECT-GROUP
    OBJECTS {
        spdIpsoHeadFiltType, spdIpsoHeadFiltClassification,
        spdIpsoHeadFiltProtectionAuth,
   spdIpsoHeadFiltLastChanged,
        spdIpsoHeadFiltStorageType, spdIpsoHeadFiltRowStatus
    }
    STATUS current
    DESCRIPTION
        "This group is made up of objects from the IPsec Policy IPSO
         Header Filter Table."
    ::= { spdGroups 9 }

--
-- action compliance groups
--

spdStaticActionGroup OBJECT-GROUP
    OBJECTS {
        spdDropAction, spdAcceptAction,
        spdDropActionLog, spdAcceptActionLog
```

```
  }
  STATUS current
  DESCRIPTION
     "This group is made up of objects from the IPsec Policy
      Static Actions."
  ::= { spdGroups 10 }

spdCompoundActionGroup OBJECT-GROUP
  OBJECTS {
     spdCompActExecutionStrategy, spdCompActLastChanged,
     spdCompActStorageType,

     spdCompActRowStatus, spdSubActSubActionName,
     spdSubActLastChanged, spdSubActStorageType,
     spdSubActRowStatus
  }
  STATUS current
  DESCRIPTION
     "The IPsec Policy Compound Action Table and Actions In




      Compound Action Table
 Group."
  ::= { spdGroups 11 }

spdActionLoggingObjectGroup OBJECT-GROUP
  OBJECTS {
     spdActionExecuted,
     spdIPEndpointAddType,   spdIPEndpointAddress,
     spdIPSourceType,        spdIPSourceAddress,
     spdIPDestinationType,   spdIPDestinationAddress,
     spdPacketDirection,     spdPacketPart
  }
  STATUS current
  DESCRIPTION
     "This group is made up of all the Notification objects for
     this MIB."
  ::= { spdGroups 12 }

spdActionNotificationGroup NOTIFICATION-GROUP
  NOTIFICATIONS {
     spdActionNotification,
     spdPacketNotification
  }
  STATUS current
  DESCRIPTION
     "This group is made up of all the Notifications for this MIB."
```

```
  ::= { spdGroups 13 }


END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/IPSEC-SPD-MIB
No license file was found, but licenses were detected in source scan.

```
DOCS-CABLE-DEVICE-MIB DEFINITIONS ::= BEGIN

IMPORTS
    MODULE-IDENTITY,
    OBJECT-TYPE,
    IpAddress,
    Unsigned32,
    Counter32,
    Integer32,
    zeroDotZero,
    mib-2
        FROM SNMPv2-SMI          -- RFC 2578
    RowStatus,
    RowPointer,
    DateAndTime,
    TruthValue,
    StorageType
        FROM SNMPv2-TC           -- RFC 2579
    InetAddressType,
    InetAddress
        FROM INET-ADDRESS-MIB    -- RFC 4001
    OBJECT-GROUP,
    MODULE-COMPLIANCE
        FROM SNMPv2-CONF         -- RFC 2580
    SnmpAdminString
        FROM SNMP-FRAMEWORK-MIB  -- RFC 3411
    InterfaceIndexOrZero
        FROM IF-MIB              -- RFC 2863
    ZeroBasedCounter32
        FROM RMON2-MIB           -- RFC 4502
    diffServMIBDataPathGroup,
    diffServMIBClfrGroup,

   diffServMIBClfrElementGroup,
    diffServMIBMultiFieldClfrGroup,
    diffServMIBActionGroup,
    diffServMIBDscpMarkActGroup,
    diffServMIBCounterGroup,
    diffServMIBAlgDropGroup,
```

```
        diffServDataPathStatus,
        diffServClfrStatus,
        diffServClfrElementStatus,
        diffServMultiFieldClfrAddrType,
        diffServMultiFieldClfrSrcAddr,
        diffServMultiFieldClfrDstAddr,
        diffServAlgDropStatus,
        diffServDataPathStorage,
        diffServClfrStorage,
        diffServClfrElementStorage,
        diffServMultiFieldClfrStorage,
        diffServActionStorage,
        diffServCountActStorage,
        diffServAlgDropStorage,
        diffServAlgDropType
            FROM DIFFSERV-MIB;        -- RFC 3289


docsDev MODULE-IDENTITY
        LAST-UPDATED    "200612200000Z" -- December 20, 2006
        ORGANIZATION    "IETF IP over Cable Data Network
                         Working Group"
        CONTACT-INFO
          "       Rich
 Woundy
            Postal: Comcast Cable
                    27 Industrial Avenue
                    Chelmsford, MA 01824 U.S.A.
            Phone:  +1 978 244 4010
            E-mail: richard_woundy@cable.comcast.com

                    Kevin Marez
            Postal: Motorola Corporation
                    6450 Sequence Drive
                    San Diego, CA 92121 U.S.A.
            Phone:  +1 858 404 3785
            E-mail: kevin.marez@motorola.com

            IETF IPCDN Working Group
            General Discussion: ipcdn@ietf.org
            Subscribe: http://www.ietf.org/mailman/listinfo/ipcdn
            Archive: ftp://ftp.ietf.org/ietf-mail-archive/ipcdn
            Co-chairs: Richard Woundy,
                       richard_woundy@cable.comcast.com
                       Jean-Francois Mule,
```

jf.mule@cablelabs.com"

DESCRIPTION
"This is the MIB Module for DOCSIS-compliant cable modems

and cable-modem
termination systems.

Copyright (C) The IETF Trust (2006). This version
of this MIB module was published in RFC 4639; for full
legal notices see the RFC itself."

REVISION "200612200000Z" -- December 20, 2006
DESCRIPTION
"Second version, published as RFC 4639.

Modifications to this MIB module since RFC 2669 include:
- Deprecation of the docsDevFilter group in favor of the
DiffServ MIB groups, to enable support for IPv6
filtering and DiffServ Code Point (DSCP) marking.
- Deprecation of the docsDevCpeGroup in favor of the
docsDevCpeInetGroup, to enable support of IPv6.
- Addition of various InetAddress objects to enable
support of IPv6.
- Deprecation of docsDevNmAccessTable in favor of SNMP
Coexistence and SNMPv3 -- yet adding
docsDevNmAccessTrapVersion and clarifying
docsDevNmAccessIp for current use of this table,
- Addition of docsDevIgmpModeControl for management and
control of the IGMP mode of operation,
- Addition of docsDevMaxCpe for management of the
maxmium number of CPEs permitted access through a
cable modem,
- Addition of docsDevSwServerTransportProtocol, and
modifications to docsDevSoftware object DESCRIPTIONS,
to enable software downloads via either TFTP or HTTP,
- Replacement of docsDevEvThrottleInhibited with
docsDevEvThrottleThresholdExceeded to simplify
event threshold management,
- Modification of docsDevEvReporting to enable local
logging to the internal volatile log, and not to the
internal non-volatile log,
- Modification of the compliance statement to make the
docsDevCpe objects optional
- Created placeholders for two OIDs in the
docsDevFilterPolicyTable that were never used

- Modified the DESCRIPTION of
  docsDevSwServerTransportProtocol and
  docsDevSwServerAddressType to address the
  dependence between each object
- Added a reference to docsDevServerConfigTftpAddress
- Clarified the scope of notifications that are covered
  by docsDevEvThrottleThreshold
- Clarified an error condition that could occur when

  doing a SET to docsDevEvReporting
- Defined each of the enumerated types for both
  docsDevEvLevel and docsDevEvPriority
- Added UNITS clause to docsDevFilterLLCMatches,
  docsDevFilterIpMatches, docsDevMaxCpe,
  docsDevEvThrottleThreshold and docsDevEvCounts.
- Added REFERENCE clause to docsDevFilterIpProtocol
- Modified DESCRIPTION
of docsDevCpeInetAddr to be
  more protocol-neutral
- Removed the enumerated value (1) from both
  docsDevCpeInetSource and docsDevCpeSource
- Covered additional read-write and read-create objects
  in the Security Considerations section
- Modified the default value of docsDevNmAccessIpMask
  to be consistent with OSSI specification
- Modified the SYNTAX of docsDevNmAccessCommunity and
  docsDevNmAccessInterfaces in the Conformance
  Statement section
- Added SYNTAX clause to docsDevEvReporting in the
  Conformance Statement section
- Modified SYNTAX clause of docsDevEvReporting to
  move new enumerated type to byte boundary
- Added references to DOCSIS 2.0 specifications to
  multiple objects
- Clarified non-persistency across reboots for
  all
tables
- Clarified functionality of docsDevSw objects as
  they relate to docsDevSwOperStatus
- Clarified enumerated types (9) and (10) for
  docsDevServerBootState
- Defined the state of unknown(0) for the following
  objects: docsDevServerDhcpAddressType,
  docsDevServerTimeAddressType,
  docsDevServerConfigTftpAddressType and
  docsDevServerConfigTftpAddressType

- Modified the value in docsDevFilterIpDaddr to be
  consistent with the SYNTAX
- Specified which rows could be modified in an
  active row for docsDevFilterPolicyStatus
- Defined the term 'manually' in docsDevCpeEnroll
- Clarified the description for
  docsDevFilterTosOrMask
- Covered the case of a non-existent row for
  docsDevFilterPolicyPtr
- Added DEFVAL clauses for multiple
objects
- Replaced docsDevNotification OBJECT IDENTIFIER
  with docsDevNotifications to address possible
  compatibility issues

- Added support for the usage of RFC 3413 and RFC 3014
  as event notification mechanisms
- Removed docsDevFilterPolicyObsoleteGroup
- Added stdInterface(9) type to docsDevEvReporting to
  support the usage of RFC3413 and RFC3014
- Modified DESCRIPTION for docsDevMaxCpe"

    REVISION "199908190000Z"
    DESCRIPTION
      "Initial version, published as RFC 2669."

    ::= { mib-2 69 }

docsDevMIBObjects OBJECT IDENTIFIER ::= { docsDev 1 }

docsDevBase OBJECT IDENTIFIER ::= { docsDevMIBObjects 1 }

--
-- For the following object, there is no concept in the
-- RFI specification corresponding to a backup CMTS. The
-- enumeration is provided here in case someone is able
-- to define such a role or device.
--

docsDevRole OBJECT-TYPE
     SYNTAX INTEGER {
       cm(1),
       cmtsActive(2),
       cmtsBackup(3)
     }
     MAX-ACCESS read-only

STATUS current
DESCRIPTION
"Defines the current role of this device. cm(1) is a
Cable Modem, cmtsActive(2) is a Cable Modem Termination
System that is controlling the system of cable modems,
and cmtsBackup(3) is a CMTS that is currently connected
but is not controlling the system (not currently used).

In general, if this device is a 'cm', its role will not
change during operation or between reboots. If the
device is a 'cmts' it may change between cmtsActive and
cmtsBackup and back again during normal operation. NB:
At this time, the DOCSIS standards do not support the
concept of a backup CMTS, but cmtsBackup is included for
completeness."
::= { docsDevBase 1 }

docsDevDateTime
OBJECT-TYPE
SYNTAX DateAndTime
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"The current date and time, with time zone information
(if known).

If the real data and time cannot be determined, this
shall represent elapsed time from boot relative to
the standard epoch '1970-1-1,0:0:0.0'. In other
words, if this agent has been up for 3 minutes and
not been able to determine what the actual date and
time are, this object will return the value
'1970-1-1,0:03:0.0'."
::= { docsDevBase 2 }

docsDevResetNow OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"Setting this object to true(1) causes the device to
reset. Reading this object always returns false(2)."
::= { docsDevBase 3 }

docsDevSerialNumber

```
 OBJECT-TYPE
      SYNTAX      SnmpAdminString
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "The manufacturer's serial number for this device."
      ::= { docsDevBase 4 }

docsDevSTPControl OBJECT-TYPE
      SYNTAX INTEGER {
         stEnabled(1),
         noStFilterBpdu(2),
         noStPassBpdu(3)
      }
      MAX-ACCESS  read-write
      STATUS      current
      DESCRIPTION
         "This object controls operation of the spanning tree
          protocol (as distinguished from transparent bridging).

          If set to stEnabled(1), then the spanning tree protocol
          is enabled, subject to bridging constraints.



          If noStFilterBpdu(2), then spanning tree is not active,
          and Bridge PDUs received are discarded.

          If noStPassBpdu(3), then spanning tree is not active,
          and Bridge PDUs are transparently forwarded.

          Note that a device need
 not implement all of these
          options, but that noStFilterBpdu(2) is required."
      DEFVAL { noStFilterBpdu }
      ::= { docsDevBase 5 }

docsDevIgmpModeControl OBJECT-TYPE
      SYNTAX INTEGER {
         passive(1),
         active(2)
      }
      MAX-ACCESS  read-write
      STATUS      current
      DESCRIPTION
         "This object controls the IGMP mode of operation for
          the CM or CMTS.  In passive mode, the device forwards
          IGMP between interfaces as based on knowledge of
```

```
            Multicast Session activity on the subscriber side
            interface and the rules defined in the DOCSIS RFI
            specification.  In active mode, the device terminates
            at and initiates IGMP through its interfaces as based
            on the knowledge of Multicast Session activity on the
            subscriber side interface."
        REFERENCE
           "DOCSIS RFI 1.1 Specification, Section 3.3.1. and

         DOCSIS RFI 2.0 Specification, Section 5.3.1."
        DEFVAL { passive }
        ::= { docsDevBase 6 }

docsDevMaxCpe OBJECT-TYPE
        SYNTAX      Unsigned32 (0..255)
        UNITS       "CPEs"
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
           "The maximum number of CPEs that can be granted access
            through a CM during a CM epoch.  This value can be
            obtained from the CM configuration file; however,
            it may be adjusted by the CM according to hardware or
            software limitations that have been imposed on the
            implementation."
        REFERENCE
           "DOCSIS RFI 1.0 Specification, Appendix C.7.20., and




            DOCSIS RFI 1.1 Specification, Appendix C.1.1.7. and
            DOCSIS RFI 2.0 Specification, Appendix C.1.1.7."
        ::= { docsDevBase 7 }



--
-- The following table provides one level of security for access
-- to the device by network management stations.
--
 Note that access is also constrained by the
-- community strings and any vendor-specific security.
--

docsDevNmAccessTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF DocsDevNmAccessEntry
        MAX-ACCESS  not-accessible
        STATUS      deprecated
        DESCRIPTION
```

```
            "This table controls access to SNMP objects by network
             management stations.  If the table is empty, access to
             SNMP objects is unrestricted.  The objects in this table
             MUST NOT persist across reboots.  The objects in this
             table are only accessible from cable devices that are
             not capable of operating in SNMP Coexistence mode
             (RFC 3584) or in SNMPv3 mode (RFC 3410).
             See the conformance section for
             details.  Note that some devices are required by other
             specifications (e.g., the DOCSIS OSSIv1.1 specification)
             to support the legacy SNMPv1/v2c docsDevNmAccess mode
             for
 backward compatibility.

             This table is deprecated.  Instead, use the SNMP
             coexistence MIBs from RFC 3584, the TARGET and
             NOTIFICATION MIBs from RFC 3413, and
             the View-Based Access Control Model (VACM) MIBs for
             all SNMP protocol versions from RFC 3415."
        ::= { docsDevMIBObjects 2 }

docsDevNmAccessEntry OBJECT-TYPE
        SYNTAX      DocsDevNmAccessEntry
        MAX-ACCESS  not-accessible
        STATUS      deprecated
        DESCRIPTION
            "An entry describing access to SNMP objects by a
             particular network management station.  An entry in
             this table is not readable unless the management station
             has read-write permission (either implicit if the table
             is empty, or explicit through an entry in this table).
             Entries are ordered by docsDevNmAccessIndex.  The first




             matching entry (e.g., matching IP address and community

   string) is used to derive access."
        INDEX { docsDevNmAccessIndex }
        ::= {  docsDevNmAccessTable 1 }

DocsDevNmAccessEntry ::= SEQUENCE {
            docsDevNmAccessIndex         Integer32,
            docsDevNmAccessIp            IpAddress,
            docsDevNmAccessIpMask        IpAddress,
            docsDevNmAccessCommunity     OCTET STRING,
            docsDevNmAccessControl       INTEGER,
            docsDevNmAccessInterfaces    OCTET STRING,
```

```
        docsDevNmAccessStatus       RowStatus,
        docsDevNmAccessTrapVersion  INTEGER
    }

docsDevNmAccessIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
        "Index used to order the application of access
        entries."
    ::= { docsDevNmAccessEntry 1 }

docsDevNmAccessIp OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
        "The IP address (or subnet) of the network management
        station.  The address 0.0.0.0 is defined to mean
        any Network Management Station (NMS).  If traps are
        enabled for this entry, then the value must be the
        address of a specific device.  Implementations MAY
        recognize 255.255.255.255 as equivalent to 0.0.0.0."
    DEFVAL { '00000000'h }
    ::= { docsDevNmAccessEntry 2 }

docsDevNmAccessIpMask OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
        "The IP subnet mask of the network management stations.
        If traps are enabled for this entry, then the value must
        be 0.0.0.0.  Implementations MAY recognize
        255.255.255.255 as equivalent to 0.0.0.0."



    DEFVAL { '00000000'h }
    ::= { docsDevNmAccessEntry 3 }

docsDevNmAccessCommunity OBJECT-TYPE
    SYNTAX      OCTET
 STRING
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
```

```
            "The community string to be matched for access by this
             entry.  If set to a zero-length string, then any
             community string will match.  When read, this object
             SHOULD return a zero-length string."
        DEFVAL { "public" }
        ::= { docsDevNmAccessEntry 4 }

docsDevNmAccessControl OBJECT-TYPE
        SYNTAX        INTEGER {
            none(1),
            read(2),
            readWrite(3),
            roWithTraps(4),
            rwWithTraps(5),
            trapsOnly(6)
        }
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "Specifies the type of access allowed to this NMS.
             Setting this object to none(1) causes the table entry
             to be destroyed.  Read(2) allows access by 'get' and
             'get-next' PDUs.  ReadWrite(3) allows access by 'set' as
             well.
  RoWithtraps(4), rwWithTraps(5), and trapsOnly(6)
             control distribution of Trap PDUs transmitted by this
             device."
        DEFVAL { read }
        ::= { docsDevNmAccessEntry 5 }

-- The syntax of the following object was copied from RFC 1493,
-- dot1dStaticAllowedToGoTo.

docsDevNmAccessInterfaces OBJECT-TYPE
        SYNTAX      OCTET STRING (SIZE (1..32))
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "Specifies the set of interfaces from which requests from
             this NMS will be accepted.  Each octet within
             the value of this object specifies a set of eight




             interfaces, the first octet specifying ports 1
             through 8, the second octet specifying interfaces 9
             through 16, etc.  Within each octet, the most
             significant bit represents the lowest numbered
```

interface, and the least significant bit represents the
highest numbered
interface. Thus, each interface is
represented by a single bit within the value of this
object. If that bit has a value of '1' then that
interface is included in the set.

Note that entries in this table apply only to link-layer
interfaces (e.g., Ethernet and CATV MAC). Bits
representing upstream and downstream channel interfaces
MUST NOT be set to '1'.

Note that if bits corresponding to non-existing
interfaces are set, the result is implementation
specific.

Note that according to the DOCSIS OSSIv1.1
specification, when ifIndex '1' is included in the
set, then this row applies to all CPE
(customer-facing) interfaces.

The size of this object is the minimum required to
represent all configured interfaces for this device."
::= { docsDevNmAccessEntry 6 }

docsDevNmAccessStatus
OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS deprecated
DESCRIPTION
"Controls and reflects the status of rows in this
table. Rows in this table may be created by either the
create-and-go or create-and-wait paradigm. There is no
restriction on changing values in a row of this table
while the row is active.

The following objects MUST have valid values before this
object can be set to active: docsDevNmAccessIp,
docsDevNmAccessStatus, docsDevNmAccessIpMask,
docsDevNmAccessCommunity, docsDevNmAccessControl, and
docsDevNmAccessInterfaces."
::= { docsDevNmAccessEntry 7 }

docsDevNmAccessTrapVersion OBJECT-TYPE
SYNTAX INTEGER {

```
            disableSNMPv2trap(1),
            enableSNMPv2trap(2)
        }
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "Specifies the TRAP version that is sent to this NMS.
            Setting this object to disableSNMPv2trap (1) causes the
            trap in SNMPv1 format to be sent to a particular NMS.
            Setting this object to enableSNMPv2trap (2) causes the
            trap in SNMPv2 format be sent to a particular NMS."
        DEFVAL { disableSNMPv2trap }
        ::= { docsDevNmAccessEntry 8 }

--
-- The following group describes control objects used for downloading
-- firmware to a cable device.  Procedures for software download are
-- described in Section 3.2.1 of the RFC containing this MIB module.
--

docsDevSoftware OBJECT IDENTIFIER ::= { docsDevMIBObjects 3 }

docsDevSwServer OBJECT-TYPE
        SYNTAX      IpAddress
        MAX-ACCESS  read-write
        STATUS      deprecated
        DESCRIPTION
            "The address of the TFTP server used for software
            upgrades.  If the TFTP server is unknown or is a
            non-IPv4 address, return
 0.0.0.0.

            This object is deprecated.  See docsDevSwServerAddress
            for its replacement.  This object will have its value
            modified, given a valid SET to docsDevSwServerAddress."
        ::= { docsDevSoftware 1 }

docsDevSwFilename OBJECT-TYPE
        SYNTAX      SnmpAdminString (SIZE (0..64))
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
            "The filename of the software image to be downloaded via
            TFTP, or the abs_path (as defined in RFC 2616) of the
            software image to be downloaded via HTTP.

            Unless set via SNMP, this is the filename or abs_path
```

specified by the provisioning server during the boot
process that corresponds to the software version that

is desired for this device.

If unknown, the value of this object is the zero-length
string."
::= { docsDevSoftware 2 }

docsDevSwAdminStatus OBJECT-TYPE
SYNTAX INTEGER {
upgradeFromMgt(1),
allowProvisioningUpgrade(2),
ignoreProvisioningUpgrade(3)
}
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"If set to upgradeFromMgt(1), the device will initiate a
TFTP or HTTP software image download. After
successfully receiving an image, the device will set
its state to ignoreProvisioningUpgrade(3) and reboot.
If the download process is interrupted (e.g., by a reset
or power failure), the device will load the previous
image and, after re-initialization, continue to attempt
loading the image specified in docsDevSwFilename.

If set to allowProvisioningUpgrade(2), the device will
use the software version information supplied by the
provisioning server when next rebooting (this does not
cause a reboot).

When set to ignoreProvisioningUpgrade(3), the device
will disregard software image upgrade information
from the provisioning server.

Note that reading this object can return
upgradeFromMgt(1). This indicates that a software
download is currently in progress, and that the device
will reboot after successfully receiving an image."
DEFVAL { allowProvisioningUpgrade }
::= { docsDevSoftware 3 }

docsDevSwOperStatus OBJECT-TYPE
SYNTAX INTEGER {

```
            inProgress(1),
            completeFromProvisioning(2),
            completeFromMgt(3),
            failed(4),
            other(5)
        }



        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
            "InProgress(1) indicates that a TFTP or HTTP download is
             underway, either as a result of a version mismatch at
             provisioning or as a result of a upgradeFromMgt request.

             No other docsDevSw* objects can be modified in
             this state.

             CompleteFromProvisioning(2) indicates that the last
             software upgrade was a result of version mismatch at
             provisioning.

             CompleteFromMgt(3) indicates that the last software
             upgrade was a result of setting docsDevSwAdminStatus to
             upgradeFromMgt.

             Failed(4) indicates that the last attempted download
             failed, ordinarily due to TFTP or HTTP timeout."
        REFERENCE
            "DOCSIS RFI 1.0 Specification, Section 8.2., and
             DOCSIS RFI 1.1 Specification, Section 10.1. and
             DOCSIS RFI 2.0 Specification, Section 12.1."
        ::= { docsDevSoftware 4 }

    docsDevSwCurrentVers OBJECT-TYPE
        SYNTAX      SnmpAdminString
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
            "The software version currently operating in this device.
             This
     string's syntax is that used by the
             individual vendor to identify software versions.
             For a CM, this string will describe the current
             software load.  For a CMTS, this object SHOULD contain
             a human-readable representation either of the vendor
             specific designation of the software for the chassis,
```

```
            or of the software for the control processor.  If
            neither of these is applicable, the value MUST be a
            zero-length string."
        ::= { docsDevSoftware 5 }

    docsDevSwServerAddressType OBJECT-TYPE
        SYNTAX      InetAddressType
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
            "The type of address of the TFTP or HTTP server used for




            software upgrades.

            If docsDevSwServerTransportProtocol is currently set to
            tftp(1), attempting to set this object to dns(16) MUST
            result in an error."
        ::=
     { docsDevSoftware 6 }

    docsDevSwServerAddress OBJECT-TYPE
        SYNTAX      InetAddress
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
            "The address of the TFTP or HTTP server used for software
            upgrades.

            If the TFTP/HTTP server is unknown, return the zero-
            length address string (see the TextualConvention).

            If docsDevSwServer is also implemented in this agent,
            this object is tied to it.  A set of this object to an
            IPv4 address will result in also setting the value of
            docsDevSwServer to that address.  If this object is set
            to an IPv6 address, docsDevSwServer is set to 0.0.0.0.
            If docsDevSwServer is set, this object is also set to
            that value.  Note that if both are set in the same
            action, the order of which one sets the other is
            undefined."
        ::= { docsDevSoftware 7 }

    docsDevSwServerTransportProtocol
     OBJECT-TYPE
        SYNTAX INTEGER {
            tftp(1),
```

```
        http(2)
    }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "This object specifies the transport protocol (TFTP or
        HTTP) to be used for software upgrades.

        If the value of this object is tftp(1), then the cable
        device uses TFTP (RFC 1350) read request packets to
        download the docsDevSwFilename from the
        docsDevSwServerAddress in octet mode.

        If the value of this object is http(2), then the cable
        device uses HTTP 1.0 (RFC 1945) or HTTP 1.1 (RFC 2616)
        GET requests sent to host docsDevSwServerAddress to



        download the software image from path docsDevSwFilename.

        If docsDevSwServerAddressType is currently set to
        dns(16), attempting to set this object to tftp(1) MUST
        result in an error."
    DEFVAL
{ tftp }
    ::= { docsDevSoftware 8 }

--
-- The following group describes server access and parameters used
-- for initial provisioning and bootstrapping.
--

docsDevServer OBJECT IDENTIFIER ::= { docsDevMIBObjects 4 }

docsDevServerBootState OBJECT-TYPE
    SYNTAX INTEGER {
        operational(1),
        disabled(2),
        waitingForDhcpOffer(3),
        waitingForDhcpResponse(4),
        waitingForTimeServer(5),
        waitingForTftp(6),
        refusedByCmts(7),
        forwardingDenied(8),
        other(9),
        unknown(10)
    }
```

MAX-ACCESS read-only
STATUS current
DESCRIPTION
"If operational(1), the device has completed loading and
processing of configuration parameters, and the CMTS has
completed the Registration exchange.

If disabled(2), then the device was administratively
disabled, possibly by being refused network access
in
the configuration file.

If waitingForDhcpOffer(3), then a Dynamic Host
Configuration Protocol (DHCP) Discover has been
transmitted, and no offer has yet been received.

If waitingForDhcpResponse(4), then a DHCP Request has
been transmitted, and no response has yet been received.

If waitingForTimeServer(5), then a Time Request has been
transmitted, and no response has yet been received.

If waitingForTftp(6), then a request to the TFTP
parameter server has been made, and no response
received.

If refusedByCmts(7), then the Registration
Request/Response exchange with the CMTS failed.

If forwardingDenied(8), then the registration process
was completed, but the network access option in the
received configuration file prohibits forwarding.

If other(9), then the registration
process reached a
point that does not fall into one of the above
categories.

If unknown(10), then the device has not yet begun the
registration process or is in some other indeterminate
state."
REFERENCE
"DOCSIS RFI 1.0 Specification, Figure 7-1, and
DOCSIS RFI 1.1 Specification, Figure 9-1 and
DOCSIS RFI 2.0 Specification, Figure 11-1."
::= { docsDevServer 1 }

```
docsDevServerDhcp OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
        "The IP address of the DHCP server that assigned an IP
         address to this device.  Returns 0.0.0.0 if DHCP is not
         used for IP address assignment, or if this agent is
         not assigned an IPv4 address.

         This object is deprecated and is replaced by
         docsDevServerDhcpAddress."
    ::= { docsDevServer
 2 }

docsDevServerTime OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
        "The IP address of the Time server (RFC 0868).  Returns
         0.0.0.0 if the time server IP address is unknown, or if
         the time server is not an IPv4 server.

         This object is deprecated and is replaced by




         docsDevServerTimeAddress."
    ::= { docsDevServer 3 }

docsDevServerTftp OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
        "The IP address of the TFTP server responsible for
         downloading provisioning and configuration parameters
         to this device.  Returns 0.0.0.0 if the TFTP server
         address is unknown or is not an IPv4 address.

         This object is deprecated and is replaced by
         docsDevServerConfigTftpAddress."
    ::= { docsDevServer
 4 }

docsDevServerConfigFile OBJECT-TYPE
```

```
        SYNTAX      SnmpAdminString
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
           "The name of the device configuration file read from
            the TFTP server.  Returns a zero-length string if
            the configuration file name is unknown."
        ::= { docsDevServer 5 }

docsDevServerDhcpAddressType OBJECT-TYPE
        SYNTAX      InetAddressType
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
           "The type of address of docsDevServerDhcpAddress.  If
            DHCP was not used, this value should return
            unknown(0)."
        ::= { docsDevServer 6 }

docsDevServerDhcpAddress OBJECT-TYPE
        SYNTAX      InetAddress
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
           "The internet address of the DHCP server that assigned
            an IP address to this device.  Returns the zero length

          octet string if DHCP was not used for IP address
            assignment."
        ::= { docsDevServer 7 }




docsDevServerTimeAddressType OBJECT-TYPE
        SYNTAX      InetAddressType
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
           "The type of address of docsDevServerTimeAddress.  If
            no time server exists, this value should return
            unknown(0)."
        ::= { docsDevServer 8 }

docsDevServerTimeAddress OBJECT-TYPE
        SYNTAX      InetAddress
        MAX-ACCESS  read-only
        STATUS      current
```

```
    DESCRIPTION
       "The Internet address of the RFC 868 Time server,
        as provided by DHCP option 4.

        Note that if multiple values are provided to the
        CM in DHCP option 4, the value of this MIB object
        MUST be the Time server address from which the Time
        of Day reference was acquired as based on the DOCSIS
        RFI specification.
 During the period of time where
        the Time of Day have not been acquired, the Time
        server address reported by the CM may report the
        first address value in the DHCP option value or the
        last server address the CM attempted to get the Time
        of day value.

        Returns the zero-length octet string if the time server
        IP address is not provisioned."
    REFERENCE
       "DOCSIS RFI 1.1 Specification, Section 9.2.7. and
        DOCSIS RFI 2.0 Specification, Section 11.2.7."
    ::= { docsDevServer 9 }

docsDevServerConfigTftpAddressType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       "The type of address of docsDevServerConfigTftpAddress.
        If no TFTP server exists, this value should return
        unknown(0)."
    ::= { docsDevServer 10 }

docsDevServerConfigTftpAddress OBJECT-TYPE
     SYNTAX      InetAddress



    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       "The internet address of the TFTP server responsible for
        downloading provisioning and configuration parameters
        to this device.  Returns the zero-length octet string if
        the config server address is unknown.  There are certain
        security risks that are involved with using TFTP."
    REFERENCE
       "RFC 3617, Section 5"
```

```
    ::= { docsDevServer 11 }


--
-- Event Reporting
--

docsDevEvent OBJECT IDENTIFIER ::= { docsDevMIBObjects 5 }

docsDevEvControl OBJECT-TYPE
    SYNTAX INTEGER {
       resetLog(1),
       useDefaultReporting(2)
    }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
       "Setting this object to resetLog(1) empties the event
        log.  All data is deleted.  Setting it to
        useDefaultReporting(2) returns all event
 priorities to
        their factory-default reporting.  Reading this object
        always returns useDefaultReporting(2)."
    ::= { docsDevEvent 1 }

docsDevEvSyslog OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  read-write
    STATUS      deprecated
    DESCRIPTION
       "The IP address of the Syslog server.  If 0.0.0.0, either
        syslog transmission is inhibited, or the Syslog server
        address is not an IPv4 address.

        This object is deprecated and is replaced by
        docsDevEvSyslogAddress."
    ::= { docsDevEvent 2 }

docsDevEvThrottleAdminStatus OBJECT-TYPE



    SYNTAX INTEGER {
       unconstrained(1),
       maintainBelowThreshold(2),
       stopAtThreshold(3),
       inhibited(4)
    }
```

```
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
            "Controls the transmission of traps and syslog messages
             with respect
    to the trap pacing threshold.

             unconstrained(1) causes traps and syslog messages to be
             transmitted without regard to the threshold settings.

             maintainBelowThreshold(2) causes trap transmission and
             syslog messages to be suppressed if the number of traps
             would otherwise exceed the threshold.

             stopAtThreshold(3) causes trap transmission to cease at
             the threshold and not to resume until directed to do so.

             inhibited(4) causes all trap transmission and syslog
             messages to be suppressed.

             A single event is always treated as a single event for
             threshold counting.  That is, an event causing both a
             trap and a syslog message is still treated as a single
             event.

             Writing to this object resets the thresholding state."
        DEFVAL { unconstrained }
        ::= { docsDevEvent 3 }

    docsDevEvThrottleInhibited OBJECT-TYPE
         SYNTAX      TruthValue
        MAX-ACCESS  read-only
        STATUS      deprecated
        DESCRIPTION
            "If true(1), trap and syslog transmission is currently
             inhibited due to thresholds and/or the current setting
             of docsDevEvThrottleAdminStatus.  In addition, this is
             true(1) when transmission is inhibited because no
             syslog (docsDevEvSyslog) or trap (docsDevNmAccessEntry)
             destinations have been set.

             This object is deprecated and is replaced by
             docsDevEvThrottleThresholdExceeded."



        ::= { docsDevEvent 4 }
```

```
docsDevEvThrottleThreshold OBJECT-TYPE
      SYNTAX      Unsigned32
      UNITS       "events"
      MAX-ACCESS  read-write
      STATUS      current
      DESCRIPTION
         "Number of events per docsDevEvThrottleInterval permitted
          before throttling is to occur.

          A single event, whether the notification could result in

        messages transmitted using syslog, SNMP, or both
          protocols, and regardless of the number of destinations,
          (including zero) is always treated as a single event for
          threshold counting.  For example, an event causing both
          a trap and a syslog message is still treated as a single
          event.

          All system notifications that occur within the device
          should be taken into consideration when calculating
          and monitoring the threshold."
      DEFVAL { 0 }
      ::= { docsDevEvent 5 }

docsDevEvThrottleInterval OBJECT-TYPE
      SYNTAX      Integer32 (1..2147483647)
      UNITS       "seconds"
      MAX-ACCESS  read-write
      STATUS      current
      DESCRIPTION
         "The interval over which docsDevEvThrottleThreshold
          applies."
      DEFVAL { 1 }
      ::= { docsDevEvent 6 }

--
-- The following table controls the reporting of the various classes
-- of events.
--

docsDevEvControlTable
 OBJECT-TYPE
      SYNTAX      SEQUENCE OF DocsDevEvControlEntry
      MAX-ACCESS  not-accessible
      STATUS      current
      DESCRIPTION
         "This table allows control of the reporting of event
          classes.  For each event priority, a combination of
```

```
            logging and reporting mechanisms may be chosen.  The
            mapping of event types to priorities is
            vendor dependent.  Vendors may also choose to allow
            the user to control that mapping through proprietary
            means.  Table entries MUST persist across reboots for
            CMTS devices and MUST NOT persist across reboots for CM
            devices."
        ::= {  docsDevEvent 7 }

docsDevEvControlEntry OBJECT-TYPE
        SYNTAX      DocsDevEvControlEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
            "Allows configuration of the reporting mechanisms for a
            particular
 event priority."
        INDEX { docsDevEvPriority }
        ::= { docsDevEvControlTable 1 }

DocsDevEvControlEntry ::= SEQUENCE {
            docsDevEvPriority       INTEGER,
            docsDevEvReporting      BITS
        }

docsDevEvPriority OBJECT-TYPE
        SYNTAX INTEGER {
            emergency(1),
            alert(2),
            critical(3),
            error(4),
            warning(5),
            notice(6),
            information(7),
            debug(8)
        }
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
            "The priority level that is controlled by this
            entry.  These are ordered from most (emergency) to least
            (debug) critical.  Each event with a CM or CMTS has a
            particular priority level associated with it (as defined
            by the vendor).
```

```
            emergency(1) events indicate vendor-specific fatal
            hardware or software errors that prevent normal system
             operation.



            alert(2) events indicate a serious failure that causes
            the reporting system to reboot but is not caused by
            hardware or software malfunctioning.

            critical(3) events indicate a serious failure that
            requires attention and prevents the device from
            transmitting data but that could be recovered without
            rebooting the system.

            error(4) and warning(5) events indicate that a failure
            occurred that could interrupt the normal data flow but
            that does not cause the device to re-register.

            notice(6) and information(7) events indicate a
            milestone or checkpoint in normal operation that could
            be of particular importance for troubleshooting.

            debug(8) events are reserved for vendor-specific
            events.

            During normal operation, no event more
            critical than notice(6)
 should be generated.  Events
            between warning and emergency should be generated at
            appropriate levels of problems (e.g., emergency when the
            box is about to crash)."
        ::= { docsDevEvControlEntry 1 }

docsDevEvReporting OBJECT-TYPE
        SYNTAX BITS {
            local(0),
            traps(1),
            syslog(2),
            -- The following are extensions to the original set of
            -- labels.  The extensions start at an octet boundary.
            -- So for bits 3 - 7, one MUST set them to zero on send
            -- and one MUST ignore them on receipt.
            localVolatile(8),
            stdInterface(9)
        }
        MAX-ACCESS  read-write
```

```
        STATUS      current
        DESCRIPTION
            "Defines the action to be taken on occurrence of this
             event class.  Implementations may not necessarily
             support all options for all event classes but at
             minimum must allow traps and
 syslogging to be
             disabled.




             If the local(0) bit is set, then log to the internal
             log and update non-volatile store, for backward
             compatibility with the original RFC 2669 definition.
             If the traps(1) bit is set, then generate
             an SNMP trap; if the syslog(2) bit is set, then
             send a syslog message (assuming that the syslog address
             is set).  If the localVolatile(8) bit is set, then
             log to the internal log without updating non-volatile
             store.  If the stdInterface(9) bit is set, then the
             agent ignores all other bits except the local(0),
             syslog(2), and localVolatile(8) bits.  Setting the
             stdInterface(9) bit indicates that RFC3413 and
             RFC3014 are being used to control event reporting
             mechanisms."
        ::= { docsDevEvControlEntry 2 }

docsDevEventTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF DocsDevEventEntry
         MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
            "Contains a log of network and device events that may be
             of interest in fault isolation and troubleshooting.
             If the local(0) bit is set in docsDevEvReporting,
             entries in this table MUST persist across reboots."
        ::= {  docsDevEvent 8 }

docsDevEventEntry OBJECT-TYPE
        SYNTAX      DocsDevEventEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
            "Describes a network or device event that may be of
             interest in fault isolation and troubleshooting.
             Multiple sequential identical events are represented by
             incrementing docsDevEvCounts and setting
```

```
            docsDevEvLastTime to the current time rather than
            creating multiple rows.

            Entries are created with the first occurrence of an
            event.  docsDevEvControl can
 be used to clear the
            table.  Individual events cannot be deleted."
        INDEX { docsDevEvIndex }
        ::= { docsDevEventTable 1 }

DocsDevEventEntry ::= SEQUENCE {
            docsDevEvIndex          Integer32,
            docsDevEvFirstTime      DateAndTime,



            docsDevEvLastTime       DateAndTime,
            docsDevEvCounts         Counter32,
            docsDevEvLevel          INTEGER,
            docsDevEvId             Unsigned32,
            docsDevEvText           SnmpAdminString
        }

docsDevEvIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
            "Provides relative ordering of the objects in the event
            log.  This object will always increase except when
            (a) the log is reset via docsDevEvControl,
            (b) the device reboots and does not implement
            non-volatile storage for this log, or (c)
 it reaches
            the value 2^31.  The next entry for all the above
            cases is 1."
        ::= { docsDevEventEntry 1 }

docsDevEvFirstTime OBJECT-TYPE
        SYNTAX      DateAndTime
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
            "The value of docsDevDateTime at the time this entry was
            created."
        ::= { docsDevEventEntry 2 }

docsDevEvLastTime OBJECT-TYPE
```

```
        SYNTAX      DateAndTime
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
           "When an entry reports only one event, this object will
            have the same value as the corresponding instance of
            docsDevEvFirstTime.  When an entry reports multiple
            events, this object will record the value that
            docsDevDateTime had when the most recent event for this
            entry occurred."
        ::= { docsDevEventEntry 3 }

-- This object was renamed from docsDevEvCount to meet naming
--
 requirements for Counter32
docsDevEvCounts OBJECT-TYPE
        SYNTAX      Counter32
        UNITS       "events"



        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
           "The number of consecutive event instances reported by
            this entry.  This starts at 1 with the creation of this
            row and increments by 1 for each subsequent duplicate
            event."
        ::= { docsDevEventEntry 4 }
docsDevEvLevel OBJECT-TYPE
        SYNTAX INTEGER {
           emergency(1),
           alert(2),
           critical(3),
           error(4),
           warning(5),
           notice(6),
           information(7),
           debug(8)
        }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
           "The priority level of this event, as defined by the
            vendor.  These are ordered from most serious (emergency)
            to least serious (debug).

            emergency(1) events
```

```
 indicate vendor-specific fatal
         hardware or software errors that prevent normal system
         operation.

         alert(2) events indicate a serious failure that causes
         the reporting system to reboot but that is not caused by
         hardware or software malfunctioning.

         critical(3) events indicate a serious failure that
         requires attention and prevents the device from
         transmitting data but that could be recovered without
         rebooting the system.

         error(4) and warning(5) events indicate that a failure
         occurred that could interrupt the normal data flow but
         that does not cause the device to re-register.

         notice(6) and information(7) events indicate a
         milestone or checkpoint in normal operation that could
         be of particular importance for troubleshooting.

         debug(8) events are reserved for vendor-specific




        events.

         During normal operation, no event more
         critical than notice(6) should be generated.  Events
         between warning and emergency should be generated at
         appropriate levels of problems (e.g., emergency when the
         box is about to crash)."
      ::= { docsDevEventEntry 5 }

--
-- It is strongly recommended that implementors follow the CableLabs
-- enumerations for docsDevEvId, per the DOCSIS OSSIv1.1 spec
-- and follow-on specifications.
--

docsDevEvId OBJECT-TYPE
      SYNTAX      Unsigned32
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "For this product, uniquely identifies the type of event
         that is reported by this entry."
```

```
        REFERENCE
           "DOCSIS OSSI 1.1 Specification, Appendix H and
            DOCSIS OSSI 2.0 Specification, Annex D."
        ::= { docsDevEventEntry 6 }

docsDevEvText OBJECT-TYPE
        SYNTAX      SnmpAdminString

       MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
           "Provides a human-readable description of the event,
            including all relevant context (interface numbers,
            etc.)."
        ::= { docsDevEventEntry 7 }

docsDevEvSyslogAddressType OBJECT-TYPE
        SYNTAX      InetAddressType
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
           "The type of address of docsDevEvSyslogAddress.  If
            no syslog server exists, this value should return
            unknown(0)."
        DEFVAL { unknown }
        ::= { docsDevEvent 9 }




docsDevEvSyslogAddress OBJECT-TYPE
        SYNTAX      InetAddress
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
           "The Internet address of the Syslog server, as provided
            by DHCP option 7 or set via SNMP management.  If the
            address of the server is set to the zero-length
            string, the 0.0.0.0
 IPv4 address, or the 0: IPv6
            address, Syslog transmission is inhibited.

            Note that if multiple values are provided to the CM in
            DHCP option 7, the value of this MIB object MUST be the
            first Syslog server address received.

            By default at agent boot, this object returns the zero
            length string."
```

```
    ::= { docsDevEvent 10 }

docsDevEvThrottleThresholdExceeded OBJECT-TYPE
    SYNTAX TruthValue
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
       "If true(1), trap and syslog transmission is currently
        inhibited due to exceeding the trap/syslog event
        threshold in the current interval."
    ::= { docsDevEvent 11 }

--
-- Link Level Control Filtering
--

docsDevFilter OBJECT IDENTIFIER ::= { docsDevMIBObjects 6 }

docsDevFilterLLCUnmatchedAction OBJECT-TYPE
    SYNTAX INTEGER {
       discard(1),
       accept(2)
    }
    MAX-ACCESS
 read-write
    STATUS      current
    DESCRIPTION
       "LLC (Link Level Control) filters can be defined on an
        inclusive or exclusive basis: CMs can be configured to
        forward only packets matching a set of layer three
        protocols, or to drop packets matching a set of layer
        three protocols.  Typical use of these filters is to



        filter out possibly harmful (given the context of a
        large metropolitan LAN) protocols.

        If set to discard(1), any L2 packet that does not match
        at least one filter in the docsDevFilterLLCTable will be
        discarded.  If set to accept(2), any L2 packet that
        does not match at least one filter in the
        docsDevFilterLLCTable will be accepted for further
        processing (e.g., bridging).  In other words, if the
        packet does not match an entry in the table, it takes
        this action;
 if it does match an entry in the table, it
        takes the opposite of this action."
```

```
    DEFVAL { accept }
    ::= { docsDevFilter 1 }

docsDevFilterLLCTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsDevFilterLLCEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
       "A list of filters to apply to (bridged) LLC
        traffic.  The filters in this table are applied to
        incoming traffic on the appropriate interface(s)  prior
        to any further processing (e.g., before the packet
        is handed off for level 3 processing, or for bridging).
        The specific action taken when no filter is matched is
        controlled by docsDevFilterLLCUnmatchedAction.  Table
        entries MUST NOT persist across reboots for any device."
    ::= { docsDevFilter 2 }

docsDevFilterLLCEntry OBJECT-TYPE
    SYNTAX      DocsDevFilterLLCEntry
    MAX-ACCESS  not-accessible

   STATUS      current
    DESCRIPTION
       "Describes a single filter to apply to (bridged) LLC
        traffic received on a specified interface. "
    INDEX { docsDevFilterLLCIndex }
    ::= { docsDevFilterLLCTable 1 }

DocsDevFilterLLCEntry ::= SEQUENCE {
        docsDevFilterLLCIndex             Integer32,
        docsDevFilterLLCStatus            RowStatus,
        docsDevFilterLLCIfIndex           InterfaceIndexOrZero,
        docsDevFilterLLCProtocolType      INTEGER,
        docsDevFilterLLCProtocol          Integer32,
        docsDevFilterLLCMatches           Counter32
    }



docsDevFilterLLCIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
       "Index used for the identification of filters (note that
        LLC filter order is irrelevant)."
    ::= { docsDevFilterLLCEntry 1 }
```

```
docsDevFilterLLCStatus
 OBJECT-TYPE
      SYNTAX      RowStatus
      MAX-ACCESS  read-create
      STATUS      current
      DESCRIPTION
         "Controls and reflects the status of rows in this
          table.  There is no restriction on changing any of the
          associated columns for this row while this object is set
          to active.

          Specifying only this object (with the
          appropriate index) on a CM is sufficient to create a
          filter row that matches all inbound packets on the
          ethernet interface and results in the packets being
          discarded.  docsDevFilterLLCIfIndex (at least) must be
          specified on a CMTS to create a row."
      ::= { docsDevFilterLLCEntry 2}

docsDevFilterLLCIfIndex OBJECT-TYPE
      SYNTAX      InterfaceIndexOrZero
      MAX-ACCESS  read-create
      STATUS      current
      DESCRIPTION
         "The entry interface to which this filter applies.  The
          value corresponds
 to ifIndex for either a CATV MAC or
          another network interface.  If the value is zero, the
          filter applies to all interfaces.  In Cable Modems, the
          default value is the customer side interface(s).  In
          CMTSs, this object has to be specified to
          create a row in this table.

          Note that according to the DOCSIS OSSIv1.1
          specification, ifIndex '1' in the CM means that this
          row applies to all Cable Modem-to-CPE Interfaces
          (CMCI)."
      REFERENCE
         "DOCSIS OSSI 1.1 Specification, Section 3.3.4.1. and
          DOCSIS OSSI 2.0 Specification, Section 6.3.4.1."
      ::= { docsDevFilterLLCEntry 3 }




docsDevFilterLLCProtocolType OBJECT-TYPE
      SYNTAX INTEGER {
         ethertype(1),
```

```
        dsap(2)
    }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The format of the value in docsDevFilterLLCProtocol:
         either a two-byte Ethernet Ethertype, or a one-byte
         802.2 Service Access Point (SAP) value.  ethertype(1)
         also applies to Standard Network Access Protocol
         (SNAP) encapsulated frames."
    DEFVAL { ethertype }
    ::= { docsDevFilterLLCEntry 4 }

docsDevFilterLLCProtocol OBJECT-TYPE
    SYNTAX      Integer32 (0..65535)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The layer-three protocol for which this filter applies.
         The protocol value format depends on
         docsDevFilterLLCProtocolType.  Note that for SNAP
         frames, ethertype filtering is performed rather than
         Destination Service Access Point (DSAP) =0xAA."
    DEFVAL { 0 }
    ::= { docsDevFilterLLCEntry 5 }

docsDevFilterLLCMatches OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "matches"
    MAX-ACCESS  read-only
    STATUS      current

   DESCRIPTION
        "Counts the number of times this filter was matched."
    ::= { docsDevFilterLLCEntry 6 }

--
-- IPv4 Filtering
--

docsDevFilterIpDefault OBJECT-TYPE
    SYNTAX INTEGER {
        discard(1),
        accept(2)
    }
    MAX-ACCESS  read-write
```

STATUS deprecated
DESCRIPTION
"The default behavior for (bridged) packets that do not match IP filters (or Internet filters, if implemented) is defined by docsDevFilterIpDefault.

If set to discard(1), all packets not matching an IP filter in docsDevFilterIpTable will be discarded. If set to accept(2), all packets not matching an IP filter or an Internet filter will be accepted for further processing (e.g., bridging)."
DEFVAL { accept }
::= { docsDevFilter 3 }

docsDevFilterIpTable OBJECT-TYPE
SYNTAX SEQUENCE OF DocsDevFilterIpEntry
MAX-ACCESS
not-accessible
STATUS deprecated
DESCRIPTION
"An ordered list of filters or classifiers to apply to IP traffic. Filter application is ordered by the filter index, rather than by a best match algorithm (note that this implies that the filter table may have gaps in the index values). Packets that match no filters will have policy 0 in the docsDevFilterPolicyTable applied to them, if it exists. Otherwise, Packets that match no filters are discarded or forwarded according to the setting of docsDevFilterIpDefault.

Any IP packet can theoretically match multiple rows of this table. When considering a packet, the table is scanned in row index order (e.g., filter 10 is checked before filter 20). If the packet matches that filter (which means that it matches ALL criteria for that row),
actions appropriate to docsDevFilterIpControl and docsDevFilterPolicyId are taken. If the packet was discarded processing is complete. If docsDevFilterIpContinue is set to true, the filter comparison continues with the next row in the table, looking for additional matches.

If the packet matches no filter in the table, the packet is accepted or dropped for further processing according to the setting of docsDevFilterIpDefault. If the packet is accepted, the actions specified by

policy group 0 (e.g., the rows in
docsDevFilterPolicyTable that have a value of 0 for
docsDevFilterPolicyId) are taken, if that policy

group exists.

Logically, this table is consulted twice during the
processing of any IP packet: once upon its acceptance
from the L2 entity, and once upon
its transmission to
the L2 entity. In actuality, for cable modems, IP
filtering is generally the only IP processing done for
transit traffic. This means that inbound and outbound
filtering can generally be done at the same time with
one pass through the filter table.

The objects in this table are only accessible from cable
devices that are not operating in DiffServ MIB mode
(RFC 3289). See the conformance section for details.

Note that some devices are required by other
specifications (e.g., the DOCSIS OSSIv1.1 specification)
to support the legacy SNMPv1/v2c docsDevFilter mode
for backward compatibility.

Table entries MUST NOT persist across reboots for any
device.

This table is deprecated. Instead, use the DiffServ MIB
from RFC 3289."
::= { docsDevFilter 4 }

docsDevFilterIpEntry
OBJECT-TYPE
SYNTAX DocsDevFilterIpEntry
MAX-ACCESS not-accessible
STATUS deprecated
DESCRIPTION
"Describes a filter to apply to IP traffic received on a
specified interface. All identity objects in this table
(e.g., source and destination address/mask, protocol,
source/dest port, TOS/mask, interface and direction)
must match their respective fields in the packet for
any given filter to match.

To create an entry in this table, docsDevFilterIpIfIndex

```
            must be specified."
        INDEX { docsDevFilterIpIndex }
        ::= { docsDevFilterIpTable 1 }

DocsDevFilterIpEntry ::= SEQUENCE {
            docsDevFilterIpIndex            Integer32,
            docsDevFilterIpStatus           RowStatus,
            docsDevFilterIpControl          INTEGER,



            docsDevFilterIpIfIndex          InterfaceIndexOrZero,

       docsDevFilterIpDirection         INTEGER,
            docsDevFilterIpBroadcast        TruthValue,
            docsDevFilterIpSaddr            IpAddress,
            docsDevFilterIpSmask            IpAddress,
            docsDevFilterIpDaddr            IpAddress,
            docsDevFilterIpDmask            IpAddress,
            docsDevFilterIpProtocol         Integer32,
            docsDevFilterIpSourcePortLow    Integer32,
            docsDevFilterIpSourcePortHigh   Integer32,
            docsDevFilterIpDestPortLow      Integer32,
            docsDevFilterIpDestPortHigh     Integer32,
            docsDevFilterIpMatches          ZeroBasedCounter32,
            docsDevFilterIpTos              OCTET STRING,
            docsDevFilterIpTosMask          OCTET STRING,
            docsDevFilterIpContinue         TruthValue,
            docsDevFilterIpPolicyId         Integer32
        }

docsDevFilterIpIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)

 MAX-ACCESS  not-accessible
        STATUS      deprecated
        DESCRIPTION
            "Index used to order the application of filters.
             The filter with the lowest index is always applied
             first."
        ::= { docsDevFilterIpEntry 1 }

docsDevFilterIpStatus OBJECT-TYPE
        SYNTAX      RowStatus
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "Controls and reflects the status of rows in this
```

table. Specifying only this object (with the
appropriate index) on a CM is sufficient to create a
filter row that matches all inbound packets on the
ethernet interface and results in the packets being
discarded. docsDevFilterIpIfIndex (at least) must be
specified on a CMTS to create a row. Creation of the
rows may be done via either create-and-wait or
create-and-go, but the filter is not applied until this

object is set to (or changes to) active. There is no
restriction in changing any object in a row while this
object is set to active."
::= { docsDevFilterIpEntry 2 }

docsDevFilterIpControl OBJECT-TYPE
SYNTAX INTEGER {
discard(1),
accept(2),
policy(3)
}
MAX-ACCESS read-create
STATUS deprecated
DESCRIPTION
"If set to discard(1), all packets matching this filter
will be discarded, and scanning of the remainder of the
filter list will be aborted. If set to accept(2), all
packets matching this filter will be accepted for
further processing (e.g., bridging). If
docsDevFilterIpContinue is set to true, see if there
are other matches; otherwise, done. If set to
policy (3), execute the policy entries
matched by docsDevFilterIpPolicyId in
docsDevFilterPolicyTable.

If docsDevFilterIpContinue is set to true, continue
scanning the table for other matches; otherwise, done."
DEFVAL { discard }
::= { docsDevFilterIpEntry 3 }

docsDevFilterIpIfIndex OBJECT-TYPE
SYNTAX InterfaceIndexOrZero
MAX-ACCESS read-create
STATUS deprecated
DESCRIPTION
"The entry interface to which this filter applies. The

```
            value corresponds to ifIndex for either a CATV MAC or
            another interface.  If the value is zero, the
            filter applies to all interfaces.  Default value in CMs
            is the index of the customer-side (e.g., ethernet)
            interface(s).  In CMTSes, this object MUST be
            specified to create a row in this table.

            Note that according to the DOCSIS OSSIv1.1
            specification, ifIndex '1' in the Cable Modem means
            that this row applies to all CMCI (customer-facing)
             interfaces."
        REFERENCE
           "DOCSIS OSSI 1.1 Specification, Section 3.3.4.1. and
            DOCSIS OSSI 2.0 Specification, Section 6.3.4.1."
        ::= { docsDevFilterIpEntry 4 }

docsDevFilterIpDirection OBJECT-TYPE



        SYNTAX INTEGER {
           inbound(1),
           outbound(2),
           both(3)
        }
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "Determines whether the filter is applied to inbound(1)
            traffic, outbound(2) traffic, or traffic in both(3)
            directions."
        DEFVAL { inbound }
        ::= { docsDevFilterIpEntry 5 }

docsDevFilterIpBroadcast OBJECT-TYPE
        SYNTAX      TruthValue
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "If set to true(1), the filter only applies to multicast
            and broadcast traffic.  If set to false(2), the filter
            applies to all traffic."

       DEFVAL { false }
        ::= { docsDevFilterIpEntry 6 }

docsDevFilterIpSaddr OBJECT-TYPE
        SYNTAX      IpAddress
```

```
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "The source IP address, or portion thereof, that is to be
            matched for this filter.  The source address is first
            masked (ANDed) against docsDevFilterIpSmask before
            being compared to this value.  A value of 0 for this
            object and 0 for the mask matches all IP addresses."
        DEFVAL { '00000000'h }
        ::= { docsDevFilterIpEntry 7 }

    docsDevFilterIpSmask OBJECT-TYPE
        SYNTAX      IpAddress
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "A bit mask that is to be applied to the source address
            prior to matching.  This mask is not necessarily the
            same as a subnet mask, but 1s bits must be leftmost and
            contiguous."
        DEFVAL
     { '00000000'h }



        ::= { docsDevFilterIpEntry 8 }

    docsDevFilterIpDaddr OBJECT-TYPE
        SYNTAX      IpAddress
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "The destination IP address, or portion thereof, that is
            to be matched for this filter.  The destination address
            is first masked (ANDed) against docsDevFilterIpDmask
            before being compared to this value.  A value of
            00000000 for this object and 00000000 for the mask
            matches all IP addresses."
        DEFVAL { '00000000'h }
        ::= { docsDevFilterIpEntry 9 }

    docsDevFilterIpDmask OBJECT-TYPE
        SYNTAX      IpAddress
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "A bit mask that is to be applied to the destination
            address prior to matching.  This mask is not necessarily
```

```
            the same as a subnet mask, but 1s bits MUST be leftmost

            and contiguous."
        DEFVAL { '00000000'h }
        ::= { docsDevFilterIpEntry 10 }

docsDevFilterIpProtocol OBJECT-TYPE
        SYNTAX Integer32 (0..256)
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "The IP protocol value that is to be matched.  For
            example, icmp is 1, tcp is 6, and udp is 17.  A value of
            256 matches ANY protocol."
        REFERENCE "www.iana.org/assignments/protocol-numbers"
        DEFVAL { 256 }
        ::= { docsDevFilterIpEntry 11 }

docsDevFilterIpSourcePortLow OBJECT-TYPE
        SYNTAX      Integer32 (0..65535)
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "This is the inclusive lower bound of the transport-layer
            source port range that is to be matched.  If the IP
            protocol of the packet is neither UDP nor TCP, this

            object is ignored during matching."
        REFERENCE "www.iana.org/assignments/port-numbers"
         DEFVAL { 0 }
        ::= { docsDevFilterIpEntry 12 }

docsDevFilterIpSourcePortHigh OBJECT-TYPE
        SYNTAX      Integer32 (0..65535)
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "This is the inclusive upper bound of the transport-layer
            source port range that is to be matched.  If the IP
            protocol of the packet is neither UDP nor TCP, this
            object is ignored during matching."
        REFERENCE "www.iana.org/assignments/port-numbers"
        DEFVAL { 65535 }
        ::= { docsDevFilterIpEntry 13 }

docsDevFilterIpDestPortLow OBJECT-TYPE
```

```
        SYNTAX      Integer32 (0..65535)
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "This is the inclusive lower bound of the transport-layer
             destination port range that is to be matched.  If the IP
             protocol of the packet is neither UDP nor TCP, this

           object is ignored during matching."
        REFERENCE "www.iana.org/assignments/port-numbers"
        DEFVAL { 0 }
        ::= { docsDevFilterIpEntry 14 }

    docsDevFilterIpDestPortHigh OBJECT-TYPE
        SYNTAX      Integer32 (0..65535)
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "This is the inclusive upper bound of the transport-layer
             destination port range that is to be matched.  If the IP
             protocol of the packet is neither UDP nor TCP, this
             object is ignored during matching."
        REFERENCE "www.iana.org/assignments/port-numbers"
        DEFVAL { 65535 }
        ::= { docsDevFilterIpEntry 15 }

    docsDevFilterIpMatches OBJECT-TYPE
        SYNTAX      ZeroBasedCounter32
        UNITS       "matches"
        MAX-ACCESS  read-only




        STATUS      deprecated
        DESCRIPTION
            "Counts the number of times this filter was matched.
             This object is initialized
     to 0 at boot, or at row
             creation, and is reset only upon reboot."
        ::= { docsDevFilterIpEntry 16 }

    docsDevFilterIpTos  OBJECT-TYPE
        SYNTAX      OCTET STRING (SIZE (1))
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "This is the value to be matched to the packet's
             TOS (Type of Service) value (after the TOS value
```

```
            is ANDed with docsDevFilterIpTosMask).  A value for this
            object of 0 and a mask of 0 matches all TOS values."
        DEFVAL { '00'h }
        ::= { docsDevFilterIpEntry 17 }

    docsDevFilterIpTosMask OBJECT-TYPE
        SYNTAX      OCTET STRING (SIZE (1))
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "The mask to be applied to the packet's TOS value before
            matching."
        DEFVAL { '00'h }
        ::= { docsDevFilterIpEntry 18 }

    docsDevFilterIpContinue OBJECT-TYPE
        SYNTAX      TruthValue

     MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "If this value is set to true and docsDevFilterIpControl
            is anything but discard (1), continue scanning and
            applying policies.  See Section 3.3.3 for more
            details."
        DEFVAL { false }
        ::= { docsDevFilterIpEntry 19 }

    docsDevFilterIpPolicyId OBJECT-TYPE
        SYNTAX      Integer32 (0..2147483647)
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "This object points to an entry in
            docsDevFilterPolicyTable.  If docsDevFilterIpControl




            is set to policy (3), execute all matching policies
            in docsDevFilterPolicyTable.  If no matching policy
            exists, treat as if docsDevFilterIpControl were set
            to accept (1).  If this object is set to the value of
            0, there is no matching policy, and
            docsDevFilterPolicyTable MUST NOT be consulted."
         DEFVAL { 0 }
        ::= { docsDevFilterIpEntry 20 }

    --
```

```
-- Policy Mapping Table
--

docsDevFilterPolicyTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsDevFilterPolicyEntry
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
       "A Table that maps between a policy group ID and a set
        of pointers to policies to be applied.  All rows with
        the same docsDevFilterPolicyId are part of the same
        group of policy pointers and are applied in the order
        in this table.  docsDevFilterPolicyTable exists to
        allow multiple policy actions (referenced by policy
        pointers) to be applied to any given classified packet.
        The policy actions are applied in index order.
        For example:

        Index   ID    Type    Action
         1      1     TOS     1
         9      5     TOS     1
         12     1     IPSEC   3


    This says that a packet that matches a filter with
        policy id 1 first has TOS policy 1 applied (which might
        set the TOS bits to enable a higher priority) and next
        has the IPSEC policy 3 applied (which may result in the
        packets being dumped into a secure VPN to a remote
        encryptor).

        Policy ID 0 is reserved for default actions and is
        applied only to packets that match no filters in
        docsDevFilterIpTable.

        Table entries MUST NOT persist across reboots for any
        device.

        This table is deprecated.  Instead, use the DiffServ MIB




        from RFC 3289."
    ::= { docsDevFilter 5 }

docsDevFilterPolicyEntry OBJECT-TYPE
    SYNTAX      DocsDevFilterPolicyEntry
    MAX-ACCESS  not-accessible
```

```
        STATUS      deprecated
        DESCRIPTION
            "An entry in the docsDevFilterPolicyTable.  Entries are
             created by Network
    Management.  To create an entry,
             docsDevFilterPolicyId MUST be specified."
        INDEX { docsDevFilterPolicyIndex }
        ::= { docsDevFilterPolicyTable 1 }

DocsDevFilterPolicyEntry ::= SEQUENCE {
            docsDevFilterPolicyIndex   Integer32,
            docsDevFilterPolicyId      Integer32,
--          docsDevFilterPolicyType    INTEGER,
--          docsDevFilterPolicyAction  Integer32,
            docsDevFilterPolicyStatus  RowStatus,
            docsDevFilterPolicyPtr     RowPointer
        }

docsDevFilterPolicyIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      deprecated
        DESCRIPTION "Index value for the table."
        ::= { docsDevFilterPolicyEntry 1 }

docsDevFilterPolicyId OBJECT-TYPE
        SYNTAX      Integer32 (0..2147483647)
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "Policy ID for this entry.  If a policy ID can apply
    to
             multiple rows of this table, all relevant policies are
             executed.  Policy 0 (if populated) is applied to all
             packets that do not match any of the filters.  N.B. If
             docsDevFilterIpPolicyId is set to 0, it DOES NOT match
             policy 0 of this table."
        ::= { docsDevFilterPolicyEntry 2 }

-- The following two objects were removed and never used; however,
-- to preserve OID numbering, they are simply commented out to
-- to ensure that they are not used again.
-- docsDevFilterPolicyType ::= { docsDevFilterPolicyEntry 3 }
-- docsDevFilterPolicyAction ::= { docsDevFilterPolicyEntry 4 }



docsDevFilterPolicyStatus OBJECT-TYPE
```

```
        SYNTAX      RowStatus
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "Object used to create an entry in this table.  There is
            no restriction in changing any object in a row while
            this object is set to active.
            The
    following object MUST have a valid value before this
            object can be set to active:  docsDevFilterPolicyPtr."
        ::= { docsDevFilterPolicyEntry 5 }

docsDevFilterPolicyPtr OBJECT-TYPE
        SYNTAX      RowPointer
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "This object points to a row in an applicable filter
            policy table.  Currently, the only standard policy
            table is docsDevFilterTosTable.

            Per the textual convention, this object points to the
            first accessible object in the row; e.g., to point to a
            row in docsDevFilterTosTable with an index of 21, the
            value of this object would be the object identifier
            docsDevTosStatus.21.

            Vendors are recommended to adhere to the same convention
            when adding vendor-specific policy table extensions.

            If this pointer references an empty or non-existent

           row, then no policy action is taken.

            The default upon row creation is a null pointer that
            results in no policy action being taken."
        DEFVAL { zeroDotZero }
        ::= { docsDevFilterPolicyEntry 6 }

--
-- TOS Policy action table
--

docsDevFilterTosTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF DocsDevFilterTosEntry
        MAX-ACCESS  not-accessible
        STATUS      deprecated
        DESCRIPTION
```

```
        "Table used to describe Type of Service (TOS) bits



        processing.

        This table is an adjunct to the docsDevFilterIpTable
        and the docsDevFilterPolicy table.  Entries in the
        latter table can point to specific rows in this (and
        other) tables and cause specific actions to be taken.
        This table permits the manipulation of the value of the
        Type of Service bits in the IP header of the matched
        packet as follows:

        Set the tosBits
 of the packet to
          (tosBits & docsDevFilterTosAndMask) |
          docsDevFilterTosOrMask

        This construct allows you to do a clear and set of all
        the TOS bits in a flexible manner.

        Table entries MUST NOT persist across reboots for any
        device.

        This table is deprecated.  Instead, use the DiffServ MIB
        from RFC 3289."
    ::= { docsDevFilter 6 }

docsDevFilterTosEntry OBJECT-TYPE
    SYNTAX      DocsDevFilterTosEntry
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
      "A TOS policy entry."
    INDEX { docsDevFilterTosIndex }
    ::= { docsDevFilterTosTable 1 }

DocsDevFilterTosEntry ::= SEQUENCE {
        docsDevFilterTosIndex   Integer32,
        docsDevFilterTosStatus  RowStatus,
        docsDevFilterTosAndMask OCTET STRING,
        docsDevFilterTosOrMask  OCTET STRING
    }

docsDevFilterTosIndex OBJECT-TYPE
     SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
```

```
        STATUS      deprecated
        DESCRIPTION
            "The unique index for this row.  There are no ordering
             requirements for this table, and any valid index may be
             specified."



        ::= { docsDevFilterTosEntry 1 }

docsDevFilterTosStatus OBJECT-TYPE
        SYNTAX      RowStatus
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "The object used to create and delete entries in this
             table.  A row created by specifying just this object
             results in a row that specifies no change to the TOS
             bits.  A row may be created using either the
             create-and-go or create-and-wait paradigms.  There is
             no restriction on the ability to change values in this
             row while the row is active."
        ::= { docsDevFilterTosEntry 2 }

docsDevFilterTosAndMask OBJECT-TYPE
         SYNTAX      OCTET STRING (SIZE (1))
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "This value is bitwise ANDed with the matched packet's
             TOS bits."
        DEFVAL { 'ff'h }
        ::= { docsDevFilterTosEntry 3 }

docsDevFilterTosOrMask OBJECT-TYPE
        SYNTAX      OCTET STRING (SIZE (1))
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "This value is bitwise ORed with the result from the
             AND procedure (tosBits & docsDevFilterTosAndMask).
             The result then replaces the packet's TOS bits."
        DEFVAL { '00'h }
        ::= { docsDevFilterTosEntry 4 }

--
-- CPE IP Management and anti-spoofing group.  Only implemented on
-- Cable Modems.
```

```
--

docsDevCpe OBJECT IDENTIFIER ::= { docsDevMIBObjects 7 }

docsDevCpeEnroll OBJECT-TYPE
      SYNTAX      INTEGER {
         none(1),
         any(2)




      }
      MAX-ACCESS  read-write

     STATUS      current
      DESCRIPTION
         "This object controls the population of
          docsDevFilterCpeTable.
          If set to none, the filters must be set manually
          by a network management action (either configuration
          or SNMP set).
          If set to any, the CM wiretaps the packets originating
          from the ethernet and enrolls up to docsDevCpeIpMax
          addresses as based on the source IPv4 or v6 addresses of
          those packets."
      DEFVAL { any }
      ::= { docsDevCpe 1 }

docsDevCpeIpMax OBJECT-TYPE
      SYNTAX      Integer32 (-1..2147483647)
      MAX-ACCESS  read-write
      STATUS      current
      DESCRIPTION
         "This object controls the maximum number of CPEs allowed
          to be learned behind this device.  If set to zero, any
          number of CPEs may connect up to the maximum permitted
          for the device.
          If set to -1, no filtering
 is done on CPE source
          addresses, and no entries are made in the
          docsDevFilterCpeTable via learning.  If an attempt is
          made to set this to a number greater than that
          permitted for the device, it is set to that maximum."
      DEFVAL { -1 }
      ::= { docsDevCpe 2 }

docsDevCpeTable OBJECT-TYPE
      SYNTAX      SEQUENCE OF DocsDevCpeEntry
```

MAX-ACCESS not-accessible
STATUS   deprecated
DESCRIPTION
"This table lists the IPv4 addresses seen (or permitted)
as source addresses in packets originating from the
customer interface on this device. In addition, this
table can be provisioned with the specific addresses
permitted for the CPEs via the normal row creation
mechanisms. Table entries MUST NOT persist across
reboots for any device.

N.B. Management action can add entries in this table
and
in docsDevCpeIpTable past the value of

docsDevCpeIpMax. docsDevCpeIpMax ONLY restricts the
ability of the CM to add learned addresses
automatically.

This table is deprecated and is replaced by
docsDevCpeInetTable."
::= { docsDevCpe 3 }

docsDevCpeEntry OBJECT-TYPE
SYNTAX   DocsDevCpeEntry
MAX-ACCESS not-accessible
STATUS   deprecated
DESCRIPTION
"An entry in the docsDevFilterCpeTable. There is one
entry for each IPv4 CPE seen or provisioned. If
docsDevCpeIpMax is set to -1, this table is ignored;
otherwise, upon receipt of an IP packet from the
customer interface of the CM, the source IP address is
checked against this table. If the address is in the
table, packet processing continues. If the address is
not in the table but docsDevCpeEnroll is set to any

and the sum of the table sizes of docsDevCpeTable and
docsDevCpeInetTable is less than docsDevCpeIpMax, the
address is added to the table, and packet processing
continues. Otherwise, the packet is dropped.

The filtering actions specified by this table occur
after any LLC filtering (docsDevFilterLLCTable), but
prior to any IP filtering (docsDevFilterIpTable,
docsDevNmAccessTable)."

```
    INDEX   { docsDevCpeIp }
    ::= {docsDevCpeTable 1 }

DocsDevCpeEntry ::= SEQUENCE {
        docsDevCpeIp      IpAddress,
        docsDevCpeSource  INTEGER,
        docsDevCpeStatus  RowStatus
    }

docsDevCpeIp OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
        "The IPv4 address to which this entry applies.

         N.B.  Attempts to set all zeros or all ones address
         values MUST
 be rejected."



    ::= { docsDevCpeEntry 1 }

docsDevCpeSource OBJECT-TYPE
    SYNTAX      INTEGER {
        other(1),
        manual(2),
        learned(3)
    }

    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
        "This object describes how this entry was created.  If
         the value is manual(2), this row was created by a
         network management action (either configuration or
         SNMP set).  If set to learned(3), then it was found via
         looking at the source IPv4 address of a received packet.
         The value other(1) is used for any entries that do not
         meet manual(2) or learned(3) criteria."
    ::= { docsDevCpeEntry 2 }

docsDevCpeStatus OBJECT-TYPE
    SYNTAX  RowStatus
    MAX-ACCESS  read-create
    STATUS  deprecated
    DESCRIPTION
```

"Standard object to manipulate rows. To create a row in
this table, one only needs
to specify this object.
Management stations SHOULD use the create-and-go
mechanism for creating rows in this table."
::= { docsDevCpeEntry 3 }

--
-- Internet CPE Management and anti spoofing group, for support of
-- non-IPv4 CPEs.
--

docsDevCpeInetTable OBJECT-TYPE
SYNTAX SEQUENCE OF DocsDevCpeInetEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"This table lists the IP addresses seen (or permitted) as
source addresses in packets originating from the
customer interface on this device. In addition, this
table can be provisioned with the specific addresses
permitted for the CPEs via the normal row creation
mechanisms.

N.B. Management action can add entries in this table
and in docsDevCpeIpTable past the value of
docsDevCpeIpMax. docsDevCpeIpMax ONLY restricts the

ability of the CM to add learned addresses
automatically.

Table entries MUST NOT persist across reboots for any
device.

This table exactly mirrors docsDevCpeTable and applies
to IPv4 and IPv6 addresses."
::= { docsDevCpe 4 }

docsDevCpeInetEntry OBJECT-TYPE
SYNTAX DocsDevCpeInetEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"An entry in the docsDevFilterCpeInetTable. There is one
entry for each IP CPE seen or provisioned. If
docsDevCpeIpMax is set to -1, this table is ignored;

```
            otherwise, upon receipt of an IP packet from the
            customer interface of the CM, the source IP address is
            checked against this table.  If the address is in the
            table, packet processing continues.  If the address is
            not in the table but docsDevCpeEnroll is set to any and
            the
 sum of the table sizes for docsDevCpeTable and
            docsDevCpeInetTable is less than docsDevCpeIpMax, the
            address is added to the table, and packet processing
            continues.  Otherwise, the packet is dropped.

            The filtering actions specified by this table occur
            after any LLC filtering (docsDevFilterLLCTable), but
            prior to any IP filtering (docsDevFilterIpTable,
            docsDevNmAccessTable).

            When an agent (cable modem) restarts, then all
            dynamically created rows are lost."
        INDEX   { docsDevCpeInetType, docsDevCpeInetAddr }
        ::= { docsDevCpeInetTable 1 }

DocsDevCpeInetEntry ::= SEQUENCE {
            docsDevCpeInetType      InetAddressType,
            docsDevCpeInetAddr      InetAddress,
            docsDevCpeInetSource    INTEGER,
            docsDevCpeInetRowStatus RowStatus
        }




docsDevCpeInetType OBJECT-TYPE
        SYNTAX      InetAddressType
        MAX-ACCESS
  not-accessible
        STATUS      current
        DESCRIPTION
            "The type of internet address of docsDevCpeInetAddr."
        ::= { docsDevCpeInetEntry 1 }

docsDevCpeInetAddr OBJECT-TYPE
        SYNTAX      InetAddress
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
            "The Internet address to which this entry applies.

            Implementors need to be aware that if the size of
```

```
            docsDevCpeInetAddr exceeds 114 octets OIDs of
            instances of columns in this row will have more
            than 128 sub-identifiers and cannot be accessed
            using SNMPv1, SNMPv2c, or SNMPv3.  Only unicast
            address are allowed for this object."
        ::= { docsDevCpeInetEntry 2 }

docsDevCpeInetSource OBJECT-TYPE
        SYNTAX      INTEGER {
           manual(2),
           learned(3)
        }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
           "This object
 describes how this entry was created.  If
            the value is manual(2), this row was created by a
            network management action (either configuration or
            SNMP set).  If set to learned(3), then it was found
            via looking at the source IP address of a received
            packet."
        ::= { docsDevCpeInetEntry 3 }

docsDevCpeInetRowStatus OBJECT-TYPE
        SYNTAX  RowStatus
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
           "Standard object to manipulate rows.  To create a row in
            this table, one only needs to specify this object.
            Management stations SHOULD use the create-and-go
            mechanism for creating rows in this table."



        ::= { docsDevCpeInetEntry 4 }



--
-- Placeholder for notifications/traps.
--

-- erroneous, DO NOT USE docsDevNotification
docsDevNotification OBJECT IDENTIFIER   ::= { docsDev 2 }
-- erroneous, DO NOT USE docsDevNotification

docsDevNotifications
```

```
 OBJECT IDENTIFIER   ::= { docsDev 0 }


--
-- RFC 2669 Conformance definitions
--

docsDevConformance  OBJECT IDENTIFIER   ::= { docsDev 3 }
docsDevGroups       OBJECT IDENTIFIER   ::= { docsDevConformance 1 }
docsDevCompliances  OBJECT IDENTIFIER   ::= { docsDevConformance 2 }

docsDevBasicCompliance MODULE-COMPLIANCE
      STATUS  deprecated
      DESCRIPTION
         "The RFC 2669 compliance statement for MCNS/DOCSIS
          Cable Modems and Cable Modem Termination Systems."

MODULE  -- docsDev

-- conditionally mandatory groups

GROUP docsDevBaseGroup
      DESCRIPTION
         "Mandatory in Cable Modems, optional in Cable Modem
          Termination Systems."

GROUP docsDevEventGroup
      DESCRIPTION
         "Mandatory in Cable Modems, optional in Cable Modem
          Termination Systems."

GROUP docsDevFilterGroup
      DESCRIPTION
         "Mandatory in Cable Modems, optional in Cable Modem
          Termination Systems."

GROUP
 docsDevNmAccessGroup



      DESCRIPTION
         "This group is only implemented in devices that do not
          implement the SNMPv3 User Security Model.  It SHOULD NOT
          be implemented by devices that conform to SNMPv3.

          For devices that do not implement SNMPv3 or later, this
          group is Mandatory in Cable Modems and is optional
```

```
        in Cable Modem Termination Systems."

GROUP docsDevServerGroup
    DESCRIPTION
      "This group is implemented only in Cable Modems, and is
       not implemented in Cable Modem Termination Systems."

GROUP docsDevSoftwareGroup
    DESCRIPTION
      "This group is Mandatory in Cable Modems and optional in
       Cable Modem Termination Systems."

GROUP docsDevCpeGroup
    DESCRIPTION
      "This group is Mandatory in Cable Modems, and is
       not implemented in Cable Modem Termination Systems."

OBJECT docsDevSTPControl
    MIN-ACCESS read-only
     DESCRIPTION
      "It is compliant to implement this object as read-only.
       Devices need only support noStFilterBpdu(2)."

OBJECT docsDevNmAccessIp
    DESCRIPTION
      "It is compliant to recognize the IP address
       255.255.255.255 as referring to any NMS."

OBJECT docsDevEvReporting
     MIN-ACCESS read-only
     DESCRIPTION
      "It is compliant to implement this object as read-only.
       Devices need only support local(0).  An agent need not
       enforce that trap or syslog logging be accompanied
       by local(0) or localVolatile(3) logging."
    ::= { docsDevCompliances 1 }

docsDevBaseGroup OBJECT-GROUP
    OBJECTS {
        docsDevRole,
        docsDevDateTime,




        docsDevResetNow,
        docsDevSerialNumber,
        docsDevSTPControl
    }
```

```
    STATUS      current
    DESCRIPTION
        "A collection of objects providing device status
and
        control."
    ::= { docsDevGroups 1 }

docsDevNmAccessGroup OBJECT-GROUP
    OBJECTS {
        docsDevNmAccessIp,
        docsDevNmAccessIpMask,
        docsDevNmAccessCommunity,
        docsDevNmAccessControl,
        docsDevNmAccessInterfaces,
        docsDevNmAccessStatus
    }
    STATUS      deprecated
    DESCRIPTION
        "A collection of objects for controlling access to SNMP
        objects on cable devices.

        This group has been deprecated because all the
        objects have been deprecated in favor of SNMPv3 and
        Coexistence MIBs."
    ::= { docsDevGroups 2 }

docsDevSoftwareGroup OBJECT-GROUP
    OBJECTS {
        docsDevSwServer,
        docsDevSwFilename,
        docsDevSwAdminStatus,
        docsDevSwOperStatus,
        docsDevSwCurrentVers
    }
    STATUS      deprecated
    DESCRIPTION
        "A collection of objects
for controlling software
        downloads.

        This group has been deprecated and replaced by
        docsDevSoftwareGroupV2.  Object docsDevSwServer
        has been replaced by docsDevSwServerAddressType
        and docsDevSwServerAddress, and
        docsDevSwServerTransportProtocol has been added to
        support TFTP and HTTP firmware downloads."
```

```
    ::= { docsDevGroups 3 }

docsDevServerGroup OBJECT-GROUP
    OBJECTS {
      docsDevServerBootState,
      docsDevServerDhcp,
      docsDevServerTime,
      docsDevServerTftp,
      docsDevServerConfigFile
    }
    STATUS      deprecated
    DESCRIPTION
      "A collection of objects providing status about server
       provisioning.

       This group has been deprecated and replaced by
       docsDevServerGroupV2.  The objects docsDevServerDhcp,
       docsDevServerTime, and docsDevServerTftp have

    been replaced by docsDevServerDhcpAddressType,
       docsDevServerDhcpAddress, docsDevServerTimeAddressType,
       docsDevServerTimeAddress,
       docsDevServerConfigTftpAddressType, and
       docsDevServerConfigTftpAddress."
    ::= { docsDevGroups 4 }

docsDevEventGroup OBJECT-GROUP
    OBJECTS {
      docsDevEvControl,
      docsDevEvSyslog,
      docsDevEvThrottleAdminStatus,
      docsDevEvThrottleInhibited,
      docsDevEvThrottleThreshold,
      docsDevEvThrottleInterval,
      docsDevEvReporting,
      docsDevEvFirstTime,
      docsDevEvLastTime,
      docsDevEvCounts,
      docsDevEvLevel,
      docsDevEvId,
      docsDevEvText
    }
    STATUS      deprecated
    DESCRIPTION
      "A collection of objects used to control and monitor
       events.
```

```
            This group has been deprecated and replaced by
            docsDevEventGroupV2.
    The object docsDevEvSyslog has



            been replaced by docsDevEvSyslogAddressType and
            docsDevEvSyslogAddress, and docsDevEvThrottleInhibited
            has been replaced by
            docsDevEvThrottleThresholdExceeded."
        ::= { docsDevGroups 5 }

docsDevFilterGroup OBJECT-GROUP
        OBJECTS {
            docsDevFilterLLCUnmatchedAction,
            docsDevFilterIpDefault,
            docsDevFilterLLCStatus,
            docsDevFilterLLCIfIndex,
            docsDevFilterLLCProtocolType,
            docsDevFilterLLCProtocol,
            docsDevFilterLLCMatches,
            docsDevFilterIpControl,
            docsDevFilterIpIfIndex,
            docsDevFilterIpStatus,
            docsDevFilterIpDirection,
            docsDevFilterIpBroadcast,
            docsDevFilterIpSaddr,
            docsDevFilterIpSmask,
            docsDevFilterIpDaddr,
            docsDevFilterIpDmask,
            docsDevFilterIpProtocol,
            docsDevFilterIpSourcePortLow,
             docsDevFilterIpSourcePortHigh,
            docsDevFilterIpDestPortLow,
            docsDevFilterIpDestPortHigh,
            docsDevFilterIpMatches,
            docsDevFilterIpTos,
            docsDevFilterIpTosMask,
            docsDevFilterIpContinue,
            docsDevFilterIpPolicyId,
            docsDevFilterPolicyId,
            docsDevFilterPolicyStatus,
            docsDevFilterPolicyPtr,
            docsDevFilterTosStatus,
            docsDevFilterTosAndMask,
            docsDevFilterTosOrMask
        }
        STATUS      deprecated
```

```
        DESCRIPTION
            "A collection of objects to specify filters at the link
             layer and IPv4 layer.

             This group has been deprecated and replaced by various
             groups from the DiffServ MIB."



        ::= { docsDevGroups 6 }

docsDevCpeGroup OBJECT-GROUP
        OBJECTS {
          docsDevCpeEnroll,
          docsDevCpeIpMax,
          docsDevCpeSource,
          docsDevCpeStatus
         }
        STATUS      deprecated
        DESCRIPTION
            "A collection of objects used to control the number
             and specific values of IPv4 addresses allowed for
             associated Customer Premises Equipment (CPE).

             This group has been deprecated and replaced by
             docsDevInetCpeGroup.  The object docsDevCpeSource has
             been replaced by docsDevCpeInetSource, and
             docsDevCpeStatus has been replaced by
             docsDevCpeInetRowStatus."
        ::= { docsDevGroups 7 }

--
-- RFC 4639 Conformance definitions
--

docsDevGroupsV2       OBJECT IDENTIFIER  ::= { docsDevConformance 3 }
docsDevCompliancesV2  OBJECT IDENTIFIER  ::= { docsDevConformance 4 }

docsDevCmCompliance MODULE-COMPLIANCE
        STATUS  current
        DESCRIPTION
            "The compliance statement for DOCSIS Cable Modems.

             This compliance statement applies to implementations
             of DOCSIS versions that are not
 IPv6 capable."

MODULE DIFFSERV-MIB -- RFC 3289
```

```
MANDATORY-GROUPS {
        diffServMIBDataPathGroup,
        diffServMIBClfrGroup,
        diffServMIBClfrElementGroup,
        diffServMIBMultiFieldClfrGroup,
        diffServMIBActionGroup,
        diffServMIBDscpMarkActGroup,
        diffServMIBCounterGroup,
        diffServMIBAlgDropGroup



        }

OBJECT diffServDataPathStatus  -- same as RFC 3289
      SYNTAX RowStatus { active(1) }
      WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
      DESCRIPTION
         "Support for createAndWait and notInService is not
          required."

OBJECT diffServClfrStatus  -- same as RFC 3289
      SYNTAX RowStatus { active(1) }
      WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
      DESCRIPTION
         "Support for createAndWait and notInService is not
          required."

OBJECT diffServClfrElementStatus  -- same as RFC 3289
      SYNTAX RowStatus { active(1)
 }
      WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
      DESCRIPTION
         "Support for createAndWait and notInService is not
          required."

OBJECT diffServMultiFieldClfrAddrType
      SYNTAX  InetAddressType { ipv4(1) }
      DESCRIPTION
         "An implementation is only required to support IPv4
          addresses."

OBJECT diffServMultiFieldClfrSrcAddr
      SYNTAX  InetAddress (SIZE(4))
      DESCRIPTION
         "An implementation is only required to support IPv4
          addresses."
```

```
OBJECT diffServMultiFieldClfrDstAddr
      SYNTAX  InetAddress (SIZE(4))
      DESCRIPTION
         "An implementation is only required to support IPv4
          addresses."

OBJECT diffServAlgDropStatus  -- same as RFC 3289
      SYNTAX RowStatus { active(1) }
      WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
      DESCRIPTION
         "Support for createAndWait and notInService is not

    required."




OBJECT diffServDataPathStorage
      SYNTAX StorageType { volatile(2) }
      DESCRIPTION
         "An implementation is only required to support
          volatile storage."

OBJECT diffServClfrStorage
      SYNTAX StorageType { volatile(2) }
      DESCRIPTION
         "An implementation is only required to support
          volatile storage."

OBJECT diffServClfrElementStorage
      SYNTAX StorageType { volatile(2) }
      DESCRIPTION
         "An implementation is only required to support
          volatile storage."

OBJECT diffServMultiFieldClfrStorage
      SYNTAX StorageType { volatile(2) }
      DESCRIPTION
         "An implementation is only required to support
          volatile storage."

OBJECT diffServActionStorage
      SYNTAX StorageType { volatile(2) }
      DESCRIPTION
         "An implementation is only required to support
          volatile storage."
```

```
OBJECT diffServCountActStorage
        SYNTAX StorageType { volatile(2) }
        DESCRIPTION
            "An implementation is only required to support
             volatile storage."

OBJECT diffServAlgDropStorage
        SYNTAX StorageType { volatile(2) }
        DESCRIPTION
            "An implementation is only required to support
             volatile storage."

OBJECT diffServAlgDropType
        SYNTAX  INTEGER { alwaysDrop(5) }
        DESCRIPTION
            "This object is only used to provide packet
             filtering.  Implementations need not support other
             values of this enumeration."



MODULE  -- docsDev

MANDATORY-GROUPS {
          docsDevBaseGroup,
          docsDevBaseIgmpGroup,
          docsDevBaseMaxCpeGroup,
          docsDevSoftwareGroupV2,
          docsDevServerGroupV2,
          docsDevEventGroupV2,
          docsDevFilterLLCGroup
          }

-- conditionally mandatory groups

GROUP docsDevInetCpeGroup
       DESCRIPTION
           "This group is
 optional in Cable Modems."

OBJECT docsDevDateTime
        MIN-ACCESS read-only
        DESCRIPTION
            "It is compliant to implement this object as read-only."

OBJECT docsDevSTPControl
        SYNTAX INTEGER { noStFilterBpdu(2) }
        MIN-ACCESS read-only
```

```
        DESCRIPTION
            "It is compliant to implement this object as read-only.
             Devices need only support noStFilterBpdu(2)."

    OBJECT docsDevIgmpModeControl
        SYNTAX INTEGER { passive(1) }
        MIN-ACCESS read-only
        DESCRIPTION
            "It is compliant to implement this object as read-only.
             Devices need only support passive(1)."

    OBJECT docsDevSwServerAddressType
        SYNTAX InetAddressType { ipv4(1) }
        DESCRIPTION
            "An implementation is only required to support IPv4
             addresses."

    OBJECT docsDevSwServerAddress
        SYNTAX  InetAddress (SIZE(4))
        DESCRIPTION
            "An implementation is only required to
     support IPv4
             addresses."



    OBJECT docsDevServerDhcpAddressType
        SYNTAX InetAddressType { ipv4(1) }
        DESCRIPTION
            "An implementation is only required to support IPv4
             addresses."

    OBJECT docsDevServerDhcpAddress
        SYNTAX  InetAddress (SIZE(4))
        DESCRIPTION
            "An implementation is only required to support IPv4
             addresses."

    OBJECT docsDevServerTimeAddressType
        SYNTAX InetAddressType { ipv4(1) }
        DESCRIPTION
            "An implementation is only required to support IPv4
             addresses."

    OBJECT docsDevServerTimeAddress
        SYNTAX  InetAddress (SIZE(4))
        DESCRIPTION
            "An implementation is only required to support IPv4
```

addresses."

OBJECT docsDevServerConfigTftpAddressType
SYNTAX InetAddressType { ipv4(1) }
DESCRIPTION
"An implementation is only required to support IPv4
addresses."

OBJECT
docsDevServerConfigTftpAddress
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4
addresses."

OBJECT docsDevEvReporting
MIN-ACCESS read-only
DESCRIPTION
"It is compliant to implement this object as read-only.
Devices need only support local(0)."

OBJECT docsDevEvSyslogAddressType
SYNTAX InetAddressType { ipv4(1) }
DESCRIPTION
"An implementation is only required to support IPv4
addresses."

OBJECT docsDevEvSyslogAddress
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4
addresses."

OBJECT docsDevSwServerTransportProtocol
SYNTAX INTEGER { tftp(1) }
DESCRIPTION
"An implementation is only required to support TFTP
software image downloads."

::= { docsDevCompliancesV2
1 }

docsDevCmtsCompliance MODULE-COMPLIANCE
STATUS current
DESCRIPTION

"The compliance statement for DOCSIS Cable Modem
Termination Systems.

This compliance statement applies to implementations
of DOCSIS versions that are not IPv6 capable."

MODULE -- docsDev

-- conditionally mandatory groups

GROUP docsDevBaseGroup
DESCRIPTION
"Optional in Cable Modem Termination Systems."

GROUP docsDevBaseIgmpGroup
DESCRIPTION
"Optional in Cable Modem Termination Systems."

GROUP docsDevBaseMaxCpeGroup
DESCRIPTION
"This group MUST NOT be implemented in Cable Modem
Termination Systems."

GROUP docsDevSoftwareGroupV2
DESCRIPTION
"Optional in Cable Modem Termination Systems."

GROUP docsDevServerGroupV2
DESCRIPTION
"This group MUST NOT be implemented in Cable Modem
Termination Systems."

GROUP docsDevEventGroupV2
DESCRIPTION
"Optional in Cable Modem Termination Systems."

GROUP docsDevFilterLLCGroup
DESCRIPTION
"This group MUST NOT be implemented in Cable Modem
Termination Systems. See the Subscriber Management
MIB for similar CMTS capability."

GROUP docsDevInetCpeGroup
DESCRIPTION
"This group MUST NOT be implemented in Cable Modem
Termination Systems. See the Subscriber Management

MIB for similar CMTS capability."

OBJECT docsDevDateTime
MIN-ACCESS read-only
DESCRIPTION
"It is compliant to implement this object as read-only."

OBJECT docsDevSTPControl
SYNTAX INTEGER { noStFilterBpdu(2) }
MIN-ACCESS read-only
DESCRIPTION
"It is compliant to implement this object as read-only.
Devices need only support noStFilterBpdu(2)."

OBJECT docsDevIgmpModeControl
SYNTAX INTEGER { passive(1)
}
MIN-ACCESS read-only
DESCRIPTION
"It is compliant to implement this object as read-only.
Devices need only support passive(1)."

OBJECT docsDevSwServerAddressType
SYNTAX InetAddressType { ipv4(1) }
DESCRIPTION
"An implementation is only required to support IPv4
addresses."

OBJECT docsDevSwServerAddress
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4
addresses."

OBJECT docsDevEvReporting

MIN-ACCESS read-only
DESCRIPTION
"It is compliant to implement this object as read-only.
Devices need only support local(0)."

OBJECT docsDevEvSyslogAddressType
SYNTAX InetAddressType { ipv4(1) }
DESCRIPTION
"An implementation is only required to support IPv4
addresses."

```
OBJECT docsDevEvSyslogAddress
      SYNTAX  InetAddress
 (SIZE(4))
      DESCRIPTION
         "An implementation is only required to support IPv4
          addresses."

OBJECT docsDevSwServerTransportProtocol
      SYNTAX INTEGER { tftp(1) }
      DESCRIPTION
         "An implementation is only required to support TFTP
          software image downloads."

      ::= { docsDevCompliancesV2 2 }

docsDevBaseIgmpGroup OBJECT-GROUP
     OBJECTS {
        docsDevIgmpModeControl
     }
     STATUS      current
     DESCRIPTION
        "An object providing cable device IGMP status and
         control."
     ::= { docsDevGroupsV2 1 }

docsDevBaseMaxCpeGroup OBJECT-GROUP
     OBJECTS {
        docsDevMaxCpe
     }
     STATUS      current
     DESCRIPTION
        "An object providing management of the maximum number of
         CPEs permitted access through a cable modem."
     ::= { docsDevGroupsV2 2 }

docsDevNmAccessExtGroup OBJECT-GROUP
     OBJECTS {

       docsDevNmAccessTrapVersion



     }
     STATUS      deprecated
     DESCRIPTION
        "An object, in addition to the objects in
         docsDevNmAccessGroup, for controlling access to
```

SNMP objects on cable devices.

This group is included in this MIB due to existing implementations of docsDevNmAccessTrapVersion in DOCSIS cable modems.

This group has been deprecated because the object has been deprecated in favor of SNMPv3 and Coexistence MIBs."

::= { docsDevGroupsV2 3 }

docsDevSoftwareGroupV2 OBJECT-GROUP
OBJECTS {
docsDevSwFilename,
docsDevSwAdminStatus,
docsDevSwOperStatus,
docsDevSwCurrentVers,
docsDevSwServerAddressType,
docsDevSwServerAddress,
docsDevSwServerTransportProtocol
}
STATUS current
DESCRIPTION
"A collection of
objects for controlling software
downloads. This group replaces docsDevSoftwareGroup."
::= { docsDevGroupsV2 4 }

docsDevServerGroupV2 OBJECT-GROUP
OBJECTS {
docsDevServerBootState,
docsDevServerDhcpAddressType,
docsDevServerDhcpAddress,
docsDevServerTimeAddressType,
docsDevServerTimeAddress,
docsDevServerConfigTftpAddressType,
docsDevServerConfigTftpAddress,
docsDevServerConfigFile
}
STATUS current
DESCRIPTION
"A collection of objects providing status about server
provisioning. This group replaces docsDevServerGroup."
::= { docsDevGroupsV2 5 }

docsDevEventGroupV2 OBJECT-GROUP

```
    OBJECTS {
       docsDevEvControl,
       docsDevEvThrottleAdminStatus,
       docsDevEvThrottleThreshold,
       docsDevEvThrottleInterval,
       docsDevEvReporting,
       docsDevEvFirstTime,
        docsDevEvLastTime,
       docsDevEvCounts,
       docsDevEvLevel,
       docsDevEvId,
       docsDevEvText,
       docsDevEvSyslogAddressType,
       docsDevEvSyslogAddress,
       docsDevEvThrottleThresholdExceeded
    }
    STATUS      current
    DESCRIPTION
       "A collection of objects used to control and monitor
        events.  This group replaces docsDevEventGroup.
        The event reporting mechanism, and more specifically
        docsDevEvReporting, can be used to take advantage of
        the event reporting features of RFC3413 and RFC3014."
    ::= { docsDevGroupsV2 6 }

docsDevFilterLLCGroup OBJECT-GROUP
    OBJECTS {
       docsDevFilterLLCUnmatchedAction,
       docsDevFilterLLCStatus,
       docsDevFilterLLCIfIndex,
       docsDevFilterLLCProtocolType,
       docsDevFilterLLCProtocol,
       docsDevFilterLLCMatches
    }
    STATUS
   current
    DESCRIPTION
       "A collection of objects to specify link layer filters."
    ::= { docsDevGroupsV2 7 }

docsDevInetCpeGroup OBJECT-GROUP
    OBJECTS {
      docsDevCpeEnroll,
      docsDevCpeIpMax,
      docsDevCpeInetSource,
      docsDevCpeInetRowStatus
    }
    STATUS     current
```

```
      DESCRIPTION
         "A collection of objects used to control the number
          and specific values of Internet (e.g., IPv4 and IPv6)
          addresses allowed for associated Customer Premises
          Equipment (CPE)."
      ::= { docsDevGroupsV2 8 }

END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/DOCS-CABLE-DEVICE-MIB
No license file was found, but licenses were detected in source scan.

```
DIFFSERV-MIB DEFINITIONS ::= BEGIN

  IMPORTS
  Unsigned32, Counter64, MODULE-IDENTITY, OBJECT-TYPE,
  OBJECT-IDENTITY, zeroDotZero, mib-2
      FROM SNMPv2-SMI
  TEXTUAL-CONVENTION, RowStatus, RowPointer,
  StorageType, AutonomousType
      FROM SNMPv2-TC
  MODULE-COMPLIANCE, OBJECT-GROUP
      FROM SNMPv2-CONF
  ifIndex, InterfaceIndexOrZero
     FROM IF-MIB
  InetAddressType, InetAddress, InetAddressPrefixLength,
  InetPortNumber
     FROM INET-ADDRESS-MIB
  BurstSize
     FROM INTEGRATED-SERVICES-MIB
  Dscp, DscpOrAny
     FROM DIFFSERV-DSCP-TC;

diffServMib MODULE-IDENTITY
  LAST-UPDATED "200202070000Z"
  ORGANIZATION "IETF Differentiated Services WG"
  CONTACT-INFO
     "       Fred Baker
             Cisco Systems
             1121 Via Del Rey
             Santa Barbara, CA 93117, USA
             E-mail: fred@cisco.com

             Kwok Ho Chan
```

Nortel Networks
600 Technology Park Drive
Billerica, MA 01821, USA
E-mail: khchan@nortelnetworks.com

Andrew Smith
Harbour Networks
Jiuling Building

21 North Xisanhuan Ave.
Beijing, 100089, PRC
E-mail: ah_smith@acm.org

Differentiated Services Working Group:
diffserv@ietf.org"

```
  DESCRIPTION
    "This MIB defines the objects necessary to manage a device that
    uses the Differentiated Services Architecture described in RFC
    2475. The Conceptual Model of a Differentiated Services Router
    provides supporting information on how such a router is modeled."
  REVISION "200202070000Z"
  DESCRIPTION
    "Initial version, published as RFC 3289."
  ::= { mib-2 97 }

diffServMIBObjects     OBJECT IDENTIFIER ::= { diffServMib 1 }
diffServMIBConformance OBJECT IDENTIFIER ::= { diffServMib 2 }
diffServMIBAdmin
      OBJECT IDENTIFIER ::= { diffServMib 3 }

IndexInteger ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "d"
  STATUS   current
  DESCRIPTION
    "An integer which may be used as a table index."
  SYNTAX   Unsigned32 (1..4294967295)

IndexIntegerNextFree ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "d"
  STATUS   current
  DESCRIPTION
    "An integer which may be used as a new Index in a table.

    The special value of 0 indicates that no more new entries can be
    created in the relevant table.
```

```
      When a MIB is used for configuration, an object with this SYNTAX
      always contains a legal value (if non-zero) for an index that is
      not currently used in the relevant table. The Command Generator
      (Network Management Application) reads this variable and uses the
      (non-zero) value read when creating a new row with an SNMP SET.
      When the SET is performed, the Command Responder (agent) must
      determine whether the value is indeed
 still unused; Two Network
      Management Applications may attempt to create a row
      (configuration entry) simultaneously and use the same value. If
      it is currently unused, the SET succeeds and the Command
      Responder (agent) changes the value of this object, according to
      an implementation-specific algorithm.  If the value is in use,



      however, the SET fails.  The Network Management Application must
      then re-read this variable to obtain a new usable value.

      An OBJECT-TYPE definition using this SYNTAX MUST specify the
      relevant table for which the object is providing this
      functionality."
    SYNTAX   Unsigned32 (0..4294967295)

IfDirection ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
      "IfDirection specifies a direction of data travel on an
      interface. 'inbound' traffic is operated on during reception from
      the interface, while 'outbound' traffic is operated on prior to
      transmission on
 the interface."
    SYNTAX  INTEGER {
              inbound(1),     -- ingress interface
              outbound(2)     -- egress interface
}

--
-- Data Path
--

diffServDataPath       OBJECT IDENTIFIER ::= { diffServMIBObjects 1 }

--
-- Data Path Table
--
-- The Data Path Table enumerates the Differentiated Services
-- Functional Data Paths within this device.  Each entry in this table
```

```
-- is indexed by ifIndex and ifDirection.  Each entry provides the
-- first Differentiated Services Functional Data Path Element to
-- process data flowing along specific data path.  This table should
-- have at most two entries for each interface capable of
-- Differentiated Services processing on this device: ingress and
-- egress.

-- Note that Differentiated Services Functional Data Path Elements
-- linked together using their individual next pointers and anchored by
-- an entry of the diffServDataPathTable constitute a functional data
-- path.
--

diffServDataPathTable OBJECT-TYPE
  SYNTAX
    SEQUENCE OF DiffServDataPathEntry
  MAX-ACCESS   not-accessible
  STATUS       current



  DESCRIPTION
    "The data path table contains RowPointers indicating the start of
    the functional data path for each interface and traffic direction
    in this device. These may merge, or be separated into parallel
    data paths."
  ::= { diffServDataPath 1 }

diffServDataPathEntry OBJECT-TYPE
  SYNTAX       DiffServDataPathEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An entry in the data path table indicates the start of a single
    Differentiated Services Functional Data Path in this device.

    These are associated with individual interfaces, logical or
    physical, and therefore are instantiated by ifIndex. Therefore,
    the interface index must have been assigned, according to the
    procedures applicable to that, before it can be meaningfully
    used. Generally, this means that the interface must
 exist.

    When diffServDataPathStorage is of type nonVolatile, however,
    this may reflect the configuration for an interface whose ifIndex
    has been assigned but for which the supporting implementation is
    not currently present."
  INDEX { ifIndex, diffServDataPathIfDirection }
```

```
  ::= { diffServDataPathTable 1 }

DiffServDataPathEntry ::= SEQUENCE  {
  diffServDataPathIfDirection    IfDirection,
  diffServDataPathStart          RowPointer,
  diffServDataPathStorage        StorageType,
  diffServDataPathStatus         RowStatus
}

diffServDataPathIfDirection OBJECT-TYPE
  SYNTAX       IfDirection
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "IfDirection specifies whether the reception or transmission path
    for this interface is in view."
  ::= { diffServDataPathEntry 1 }

diffServDataPathStart OBJECT-TYPE
  SYNTAX       RowPointer
  MAX-ACCESS   read-create
  STATUS       current



  DESCRIPTION
     "This selects the first Differentiated Services Functional Data
    Path Element to handle traffic for this data path. This
    RowPointer should point to an instance of one of:
      diffServClfrEntry
      diffServMeterEntry
      diffServActionEntry
      diffServAlgDropEntry
      diffServQEntry

    A value of zeroDotZero in this attribute indicates that no
    Differentiated Services treatment is performed on traffic of this
    data path. A pointer with the value zeroDotZero normally
    terminates a functional data path.

    Setting this to point to a target that does not exist results in
    an inconsistentValue error.  If the row pointed to is removed or
    becomes inactive by other means, the treatment is as if this
    attribute contains a value of zeroDotZero."
  ::= { diffServDataPathEntry 2 }

diffServDataPathStorage OBJECT-TYPE
  SYNTAX       StorageType
```

```
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
      "The storage type for this conceptual row.  Conceptual rows
     having the value 'permanent' need not allow write-access to any
     columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServDataPathEntry 3 }

diffServDataPathStatus OBJECT-TYPE
  SYNTAX       RowStatus
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
     "The status of this conceptual row. All writable objects in this
     row may be modified at any time."
  ::= { diffServDataPathEntry 4 }

--
-- Classifiers
--

diffServClassifier     OBJECT IDENTIFIER ::= { diffServMIBObjects 2 }

--



-- Classifier Table
--
-- The Classifier Table allows multiple classifier elements, of same or
-- different types, to be used together. A classifier must completely
-- classify all packets presented to it. This means that all traffic
-- presented to a classifier must match at least one classifier element
-- within the classifier, with the classifier element parameters
--
 specified by a filter.

-- If there is ambiguity between classifier elements of different
-- classifier, classifier linkage order indicates their precedence; the
-- first classifier in the link is applied to the traffic first.

-- Entries in the classifier element table serves as the anchor for
-- each classification pattern, defined in filter table entries.  Each
-- classifier element table entry also specifies the subsequent
-- downstream Differentiated Services Functional Data Path Element when
-- the classification pattern is satisfied. Each entry in the
-- classifier element table describes one branch of the fan-out
```

```
-- characteristic of a classifier indicated in the Informal
-- Differentiated Services Model section 4.1.  A classifier is composed
-- of one or more classifier elements.

diffServClfrNextFree OBJECT-TYPE
  SYNTAX       IndexIntegerNextFree
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
    "This object contains an unused value for diffServClfrId,
 or a
    zero to indicate that none exist."
  ::= { diffServClassifier 1 }

diffServClfrTable OBJECT-TYPE
  SYNTAX       SEQUENCE OF DiffServClfrEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "This table enumerates all the diffserv classifier functional
    data path elements of this device.  The actual classification
    definitions are defined in diffServClfrElementTable entries
    belonging to each classifier.

    An entry in this table, pointed to by a RowPointer specifying an
    instance of diffServClfrStatus, is frequently used as the name
    for a set of classifier elements, which all use the index
    diffServClfrId. Per the semantics of the classifier element
    table, these entries constitute one or more unordered sets of
    tests which may be simultaneously applied to a message to



    classify it.

    The primary function of this table is to ensure that the value of
    diffServClfrId
 is unique before attempting to use it in creating
    a diffServClfrElementEntry. Therefore, the diffServClfrEntry must
    be created on the same SET as the diffServClfrElementEntry, or
    before the diffServClfrElementEntry is created."
  ::= { diffServClassifier 2 }

diffServClfrEntry OBJECT-TYPE
  SYNTAX       DiffServClfrEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
```

```
    "An entry in the classifier table describes a single classifier.
    All classifier elements belonging to the same classifier use the
    classifier's diffServClfrId as part of their index."
  INDEX { diffServClfrId }
  ::= { diffServClfrTable 1 }

DiffServClfrEntry ::= SEQUENCE  {
  diffServClfrId             IndexInteger,
  diffServClfrStorage        StorageType,
  diffServClfrStatus         RowStatus
}

diffServClfrId OBJECT-TYPE
  SYNTAX       IndexInteger
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION

    "An index that enumerates the classifier entries.  Managers
    should obtain new values for row creation in this table by
    reading diffServClfrNextFree."
  ::= { diffServClfrEntry 1 }

diffServClfrStorage OBJECT-TYPE
  SYNTAX       StorageType
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The storage type for this conceptual row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServClfrEntry 2 }

diffServClfrStatus OBJECT-TYPE



  SYNTAX       RowStatus
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The status of this conceptual row. All writable objects in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
```

```
    ::= { diffServClfrEntry 3 }

--
-- Classifier Element Table
--
diffServClfrElementNextFree OBJECT-TYPE
  SYNTAX       IndexIntegerNextFree
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
    "This object contains an unused value for diffServClfrElementId,
    or a zero to indicate that none exist."
  ::= { diffServClassifier 3 }

diffServClfrElementTable OBJECT-TYPE
  SYNTAX       SEQUENCE OF DiffServClfrElementEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "The classifier element table enumerates the relationship between
    classification patterns and subsequent downstream Differentiated
    Services Functional Data Path elements.
    diffServClfrElementSpecific points to a filter that specifies the
    classification parameters. A classifier may use filter tables of
    different types together.

    One example of a filter table defined in this MIB is
    diffServMultiFieldClfrTable, for
 IP Multi-Field Classifiers
    (MFCs). Such an entry might identify anything from a single
    micro-flow (an identifiable sub-session packet stream directed
    from one sending transport to the receiving transport or
    transports), or aggregates of those such as the traffic from a
    host, traffic for an application, or traffic between two hosts
    using an application and a given DSCP. The standard Behavior
    Aggregate used in the Differentiated Services Architecture is
    encoded as a degenerate case of such an aggregate - the traffic
    using a particular DSCP value.

    Filter tables for other filter types may be defined elsewhere."



  ::= { diffServClassifier 4 }

diffServClfrElementEntry OBJECT-TYPE
  SYNTAX       DiffServClfrElementEntry
  MAX-ACCESS   not-accessible
```

```
  STATUS       current
  DESCRIPTION
    "An entry in the classifier element table describes a single
    element of the classifier."
  INDEX { diffServClfrId,
 diffServClfrElementId }
  ::= { diffServClfrElementTable 1 }

DiffServClfrElementEntry ::= SEQUENCE  {
  diffServClfrElementId          IndexInteger,
  diffServClfrElementPrecedence  Unsigned32,
  diffServClfrElementNext        RowPointer,
  diffServClfrElementSpecific    RowPointer,
  diffServClfrElementStorage     StorageType,
  diffServClfrElementStatus      RowStatus
}

diffServClfrElementId OBJECT-TYPE
  SYNTAX       IndexInteger
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An index that enumerates the Classifier Element entries.
    Managers obtain new values for row creation in this table by
    reading diffServClfrElementNextFree."
  ::= { diffServClfrElementEntry 1 }

diffServClfrElementPrecedence OBJECT-TYPE
  SYNTAX       Unsigned32  (1..4294967295)
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The relative order in which classifier elements are applied:
    higher numbers
 represent classifier element with higher
    precedence.  Classifier elements with the same order must be
    unambiguous i.e. they must define non-overlapping patterns, and
    are considered to be applied simultaneously to the traffic
    stream. Classifier elements with different order may overlap in
    their filters:  the classifier element with the highest order
    that matches is taken.

    On a given interface, there must be a complete classifier in
    place at all times in the ingress direction.  This means one or
    more filters must match any possible pattern. There is no such
```

requirement in the egress direction."
::= { diffServClfrElementEntry 2 }

diffServClfrElementNext OBJECT-TYPE
SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This attribute provides one branch of the fan-out functionality
of a classifier described in the Informal Differentiated Services

Model section 4.1.

This selects the next Differentiated Services Functional Data
Path Element to handle traffic for this data path. This
RowPointer should point to an instance of one of:
diffServClfrEntry
diffServMeterEntry
diffServActionEntry
diffServAlgDropEntry
diffServQEntry

A value of zeroDotZero in this attribute indicates no further
Differentiated Services treatment is performed on traffic of this
data path. The use of zeroDotZero is the normal usage for the
last functional data path element of the current data path.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or
becomes inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."

::= { diffServClfrElementEntry 3 }

diffServClfrElementSpecific OBJECT-TYPE
SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"A pointer to a valid entry in another table, filter table, that
describes the applicable classification parameters, e.g. an entry
in diffServMultiFieldClfrTable.

The value zeroDotZero is interpreted to match anything not
matched by another classifier element - only one such entry may
exist for each classifier.

Setting this to point to a target that does not exist results in

```
      an inconsistentValue error.  If the row pointed to is removed or

      becomes inactive by other means, the element is ignored."
    ::= { diffServClfrElementEntry 4 }

diffServClfrElementStorage OBJECT-TYPE
    SYNTAX      StorageType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "The storage type for this conceptual row.  Conceptual rows
      having the value 'permanent' need not allow write-access to any
      columnar objects in the row."
    DEFVAL
  { nonVolatile }
    ::= { diffServClfrElementEntry 5 }

diffServClfrElementStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "The status of this conceptual row. All writable objects in this
      row may be modified at any time. Setting this variable to
      'destroy' when the MIB contains one or more RowPointers pointing
      to it results in destruction being delayed until the row is no
      longer used."
    ::= { diffServClfrElementEntry 6 }

--
-- IP Multi-field Classification Table
--
-- Classification based on six different fields in the IP header.
-- Functional Data Paths may share definitions by using the same entry.
--

diffServMultiFieldClfrNextFree OBJECT-TYPE
    SYNTAX      IndexIntegerNextFree
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "This object contains an unused value for
      diffServMultiFieldClfrId, or a zero to indicate that none exist."
    ::= {
  diffServClassifier 5 }
```

```
diffServMultiFieldClfrTable OBJECT-TYPE
  SYNTAX   SEQUENCE OF DiffServMultiFieldClfrEntry
  MAX-ACCESS   not-accessible
  STATUS   current
  DESCRIPTION
    "A table of IP Multi-field Classifier filter entries that a




    system may use to identify IP traffic."
  ::= { diffServClassifier 6 }

diffServMultiFieldClfrEntry OBJECT-TYPE
  SYNTAX       DiffServMultiFieldClfrEntry
  MAX-ACCESS   not-accessible
  STATUS   current
  DESCRIPTION
    "An IP Multi-field Classifier entry describes a single filter."
  INDEX { diffServMultiFieldClfrId }
  ::= { diffServMultiFieldClfrTable 1 }

DiffServMultiFieldClfrEntry ::= SEQUENCE {
  diffServMultiFieldClfrId          IndexInteger,
  diffServMultiFieldClfrAddrType    InetAddressType,
  diffServMultiFieldClfrDstAddr     InetAddress,
  diffServMultiFieldClfrDstPrefixLength InetAddressPrefixLength,
  diffServMultiFieldClfrSrcAddr     InetAddress,
  diffServMultiFieldClfrSrcPrefixLength
 InetAddressPrefixLength,
  diffServMultiFieldClfrDscp        DscpOrAny,
  diffServMultiFieldClfrFlowId      Unsigned32,
  diffServMultiFieldClfrProtocol    Unsigned32,
  diffServMultiFieldClfrDstL4PortMin InetPortNumber,
  diffServMultiFieldClfrDstL4PortMax InetPortNumber,
  diffServMultiFieldClfrSrcL4PortMin InetPortNumber,
  diffServMultiFieldClfrSrcL4PortMax InetPortNumber,
  diffServMultiFieldClfrStorage     StorageType,
  diffServMultiFieldClfrStatus      RowStatus
}

diffServMultiFieldClfrId OBJECT-TYPE
  SYNTAX        IndexInteger
  MAX-ACCESS    not-accessible
  STATUS    current
  DESCRIPTION
    "An index that enumerates the MultiField Classifier filter
    entries.  Managers obtain new values for row creation in this
    table by reading diffServMultiFieldClfrNextFree."
```

```
  ::= { diffServMultiFieldClfrEntry 1 }

diffServMultiFieldClfrAddrType OBJECT-TYPE
  SYNTAX        InetAddressType
  MAX-ACCESS    read-create

  STATUS        current
  DESCRIPTION
    "The type of IP address used by this classifier entry.  While
    other types of addresses are defined in the InetAddressType




    textual convention, and DNS names, a classifier can only look at
    packets on the wire. Therefore, this object is limited to IPv4
    and IPv6 addresses."
  ::= { diffServMultiFieldClfrEntry 2 }

diffServMultiFieldClfrDstAddr OBJECT-TYPE
  SYNTAX        InetAddress
  MAX-ACCESS    read-create
  STATUS        current
  DESCRIPTION
    "The IP address to match against the packet's destination IP
    address. This may not be a DNS name, but may be an IPv4 or IPv6
    prefix.  diffServMultiFieldClfrDstPrefixLength indicates the
    number of bits that are relevant."
  ::= { diffServMultiFieldClfrEntry 3 }

diffServMultiFieldClfrDstPrefixLength OBJECT-TYPE
  SYNTAX        InetAddressPrefixLength
  UNITS         "bits"
  MAX-ACCESS    read-create
  STATUS
 current
  DESCRIPTION
    "The length of the CIDR Prefix carried in
    diffServMultiFieldClfrDstAddr. In IPv4 addresses, a length of 0
    indicates a match of any address; a length of 32 indicates a
    match of a single host address, and a length between 0 and 32
    indicates the use of a CIDR Prefix. IPv6 is similar, except that
    prefix lengths range from 0..128."
  DEFVAL        { 0 }
  ::= { diffServMultiFieldClfrEntry 4 }

diffServMultiFieldClfrSrcAddr OBJECT-TYPE
  SYNTAX        InetAddress
```

```
    MAX-ACCESS     read-create
    STATUS         current
    DESCRIPTION
      "The IP address to match against the packet's source IP address.
      This may not be a DNS name, but may be an IPv4 or IPv6 prefix.
      diffServMultiFieldClfrSrcPrefixLength indicates the number of
      bits that are relevant."
    ::= { diffServMultiFieldClfrEntry 5 }

diffServMultiFieldClfrSrcPrefixLength OBJECT-TYPE
    SYNTAX         InetAddressPrefixLength
    UNITS
          "bits"
    MAX-ACCESS     read-create
    STATUS         current
    DESCRIPTION



      "The length of the CIDR Prefix carried in
      diffServMultiFieldClfrSrcAddr. In IPv4 addresses, a length of 0
      indicates a match of any address; a length of 32 indicates a
      match of a single host address, and a length between 0 and 32
      indicates the use of a CIDR Prefix. IPv6 is similar, except that
      prefix lengths range from 0..128."
    DEFVAL         { 0 }
    ::= { diffServMultiFieldClfrEntry 6 }

diffServMultiFieldClfrDscp OBJECT-TYPE
    SYNTAX         DscpOrAny
    MAX-ACCESS     read-create
    STATUS         current
    DESCRIPTION
      "The value that the DSCP in the packet must have to match this
      entry. A value of -1 indicates that a specific DSCP value has not
      been defined and thus all DSCP values are considered a match."
    DEFVAL         { -1 }
    ::= { diffServMultiFieldClfrEntry 7 }

diffServMultiFieldClfrFlowId OBJECT-TYPE

   SYNTAX         Unsigned32 (0..1048575)
    MAX-ACCESS     read-create
    STATUS         current
    DESCRIPTION
      "The flow identifier in an IPv6 header."
    ::= { diffServMultiFieldClfrEntry 8 }
```

```
diffServMultiFieldClfrProtocol OBJECT-TYPE
  SYNTAX        Unsigned32 (0..255)
  MAX-ACCESS    read-create
  STATUS        current
  DESCRIPTION
    "The IP protocol to match against the IPv4 protocol number or the
    IPv6 Next- Header number in the packet. A value of 255 means
    match all.  Note the protocol number of 255 is reserved by IANA,
    and Next-Header number of 0 is used in IPv6."
  DEFVAL        { 255 }
  ::= { diffServMultiFieldClfrEntry 9 }

diffServMultiFieldClfrDstL4PortMin OBJECT-TYPE
  SYNTAX        InetPortNumber
  MAX-ACCESS    read-create
  STATUS        current
  DESCRIPTION
    "The minimum value that the layer-4 destination port number in
    the packet must have in order to match this classifier entry."
  DEFVAL
      { 0 }



  ::= { diffServMultiFieldClfrEntry 10 }

diffServMultiFieldClfrDstL4PortMax OBJECT-TYPE
  SYNTAX        InetPortNumber
  MAX-ACCESS    read-create
  STATUS        current
  DESCRIPTION
    "The maximum value that the layer-4 destination port number in
    the packet must have in order to match this classifier entry.
    This value must be equal to or greater than the value specified
    for this entry in diffServMultiFieldClfrDstL4PortMin."
  DEFVAL        { 65535 }
  ::= { diffServMultiFieldClfrEntry 11 }

diffServMultiFieldClfrSrcL4PortMin OBJECT-TYPE
  SYNTAX        InetPortNumber
  MAX-ACCESS    read-create
  STATUS        current
  DESCRIPTION
    "The minimum value that the layer-4 source port number in the
    packet must have in order to match this classifier entry."
  DEFVAL        { 0 }
  ::= { diffServMultiFieldClfrEntry 12 }
```

```
diffServMultiFieldClfrSrcL4PortMax OBJECT-TYPE
  SYNTAX        InetPortNumber
   MAX-ACCESS     read-create
  STATUS        current
  DESCRIPTION
    "The maximum value that the layer-4 source port number in the
    packet must have in order to match this classifier entry. This
    value must be equal to or greater than the value specified for
    this entry in diffServMultiFieldClfrSrcL4PortMin."
  DEFVAL        { 65535 }
  ::= { diffServMultiFieldClfrEntry 13 }

diffServMultiFieldClfrStorage OBJECT-TYPE
  SYNTAX       StorageType
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The storage type for this conceptual row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServMultiFieldClfrEntry 14 }

diffServMultiFieldClfrStatus OBJECT-TYPE



  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The status of this conceptual row. All writable objects
 in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
  ::= { diffServMultiFieldClfrEntry 15 }

--
-- Meters
--

diffServMeter         OBJECT IDENTIFIER ::= { diffServMIBObjects 3 }

--
-- This MIB supports a variety of Meters.  It includes a specific
-- definition for Token Bucket Meter, which are but one type of
```

```
-- specification. Other metering parameter sets can be defined in other
-- MIBs.

-- Multiple meter elements may be logically cascaded using their
-- diffServMeterSucceedNext and diffServMeterFailNext pointers if
-- required. One example of this might be for an AF PHB implementation
-- that uses multiple level conformance meters.

-- Cascading of individual meter elements in the MIB is intended to be
-- functionally equivalent to multiple level conformance determination
-- of a packet.
 The sequential nature of the representation is merely
-- a notational convenience for this MIB.

-- srTCM meters (RFC 2697) can be specified using two sets of
-- diffServMeterEntry and diffServTBParamEntry. The first set specifies
-- the Committed Information Rate and Committed Burst Size
-- token-bucket.  The second set specifies the Excess Burst Size
-- token-bucket.

-- trTCM meters (RFC 2698) can be specified using two sets of
-- diffServMeterEntry and diffServTBParamEntry. The first set specifies
-- the Committed Information Rate and Committed Burst Size
-- token-bucket.  The second set specifies the Peak Information Rate
-- and Peak Burst Size token-bucket.

-- tswTCM meters (RFC 2859) can be specified using two sets of
-- diffServMeterEntry and diffServTBParamEntry. The first set specifies
-- the Committed Target Rate token-bucket.  The second set specifies




-- the Peak Target Rate token-bucket. diffServTBParamInterval in each
-- token bucket reflects the Average Interval.
--

diffServMeterNextFree
 OBJECT-TYPE
   SYNTAX       IndexIntegerNextFree
   MAX-ACCESS   read-only
   STATUS       current
   DESCRIPTION
     "This object contains an unused value for diffServMeterId, or a
     zero to indicate that none exist."
   ::= { diffServMeter 1 }

diffServMeterTable OBJECT-TYPE
   SYNTAX       SEQUENCE OF DiffServMeterEntry
```

```
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "This table enumerates specific meters that a system may use to
    police a stream of traffic. The traffic stream to be metered is
    determined by the Differentiated Services Functional Data Path
    Element(s) upstream of the meter i.e. by the object(s) that point
    to each entry in this table.  This may include all traffic on an
    interface.

    Specific meter details are to be found in table entry referenced
    by diffServMeterSpecific."
  ::= { diffServMeter 2 }

diffServMeterEntry OBJECT-TYPE
  SYNTAX       DiffServMeterEntry
   MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An entry in the meter table describes a single conformance level
    of a meter."
  INDEX { diffServMeterId }
  ::= { diffServMeterTable 1 }

DiffServMeterEntry ::= SEQUENCE  {
  diffServMeterId              IndexInteger,
  diffServMeterSucceedNext      RowPointer,
  diffServMeterFailNext         RowPointer,
  diffServMeterSpecific         RowPointer,
  diffServMeterStorage          StorageType,
  diffServMeterStatus           RowStatus
}




diffServMeterId OBJECT-TYPE
  SYNTAX       IndexInteger
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An index that enumerates the Meter entries.  Managers obtain new
    values for row creation in this table by reading
    diffServMeterNextFree."
  ::= { diffServMeterEntry 1 }

diffServMeterSucceedNext OBJECT-TYPE
  SYNTAX       RowPointer
```

```
  MAX-ACCESS   read-create
  STATUS
   current
  DESCRIPTION
    "If the traffic does conform, this selects the next
    Differentiated Services Functional Data Path element to handle
    traffic for this data path. This RowPointer should point to an
    instance of one of:
      diffServClfrEntry
      diffServMeterEntry
      diffServActionEntry
      diffServAlgDropEntry
      diffServQEntry

    A value of zeroDotZero in this attribute indicates that no
    further Differentiated Services treatment is performed on traffic
    of this data path. The use of zeroDotZero is the normal usage for
    the last functional data path element of the current data path.

    Setting this to point to a target that does not exist results in
    an inconsistentValue error.  If the row pointed to is removed or
    becomes inactive by other means, the treatment is as if this
    attribute contains a value of zeroDotZero."
  DEFVAL      { zeroDotZero }
  ::= { diffServMeterEntry
 2 }

diffServMeterFailNext OBJECT-TYPE
  SYNTAX       RowPointer
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "If the traffic does not conform, this selects the next
    Differentiated Services Functional Data Path element to handle
    traffic for this data path. This RowPointer should point to an
    instance of one of:
      diffServClfrEntry
      diffServMeterEntry




      diffServActionEntry
      diffServAlgDropEntry
      diffServQEntry

    A value of zeroDotZero in this attribute indicates no further
    Differentiated Services treatment is performed on traffic of this
    data path. The use of zeroDotZero is the normal usage for the
```

```
      last functional data path element of the current data path.

      Setting this to point to a target that does not exist results in
      an inconsistentValue error.  If the row pointed to is removed or
      becomes inactive by other means, the treatment is as if this
       attribute contains a value of zeroDotZero."
    DEFVAL      { zeroDotZero }
    ::= { diffServMeterEntry 3 }

diffServMeterSpecific OBJECT-TYPE
    SYNTAX       RowPointer
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
      "This indicates the behavior of the meter by pointing to an entry
      containing detailed parameters. Note that entries in that
      specific table must be managed explicitly.

      For example, diffServMeterSpecific may point to an entry in
      diffServTBParamTable, which contains an instance of a single set
      of Token Bucket parameters.

      Setting this to point to a target that does not exist results in
      an inconsistentValue error.  If the row pointed to is removed or
      becomes inactive by other means, the meter always succeeds."
    ::= { diffServMeterEntry 4 }

diffServMeterStorage OBJECT-TYPE
    SYNTAX       StorageType
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
      "The
   storage type for this conceptual row.  Conceptual rows
      having the value 'permanent' need not allow write-access to any
      columnar objects in the row."
    DEFVAL { nonVolatile }
    ::= { diffServMeterEntry 5 }

diffServMeterStatus OBJECT-TYPE
    SYNTAX       RowStatus
    MAX-ACCESS   read-create




    STATUS       current
    DESCRIPTION
      "The status of this conceptual row. All writable objects in this
```

```
      row may be modified at any time. Setting this variable to
      'destroy' when the MIB contains one or more RowPointers pointing
      to it results in destruction being delayed until the row is no
      longer used."
    ::= { diffServMeterEntry 6 }

--
-- Token Bucket Parameter Table
--

diffServTBParam        OBJECT IDENTIFIER ::= { diffServMIBObjects 4 }

-- Each entry in the Token Bucket Parameter Table parameterize a single
-- token bucket.  Multiple token buckets can be used together to
-- parameterize multiple levels of conformance.

-- Note that
 an entry in the Token Bucket Parameter Table can be shared
-- by multiple diffServMeterTable entries.
--

diffServTBParamNextFree OBJECT-TYPE
    SYNTAX       IndexIntegerNextFree
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
      "This object contains an unused value for diffServTBParamId, or a
      zero to indicate that none exist."
    ::= { diffServTBParam 1 }

diffServTBParamTable OBJECT-TYPE
    SYNTAX       SEQUENCE OF DiffServTBParamEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
      "This table enumerates a single set of token bucket meter
      parameters that a system may use to police a stream of traffic.
      Such meters are modeled here as having a single rate and a single
      burst size. Multiple entries are used when multiple rates/burst
      sizes are needed."
    ::= { diffServTBParam 2 }

diffServTBParamEntry OBJECT-TYPE
    SYNTAX       DiffServTBParamEntry
    MAX-ACCESS   not-accessible
    STATUS
        current
```

```
  DESCRIPTION
    "An entry that describes a single set of token bucket
    parameters."
  INDEX { diffServTBParamId }
  ::= { diffServTBParamTable 1 }

DiffServTBParamEntry ::= SEQUENCE  {
  diffServTBParamId             IndexInteger,
  diffServTBParamType           AutonomousType,
  diffServTBParamRate           Unsigned32,
  diffServTBParamBurstSize      BurstSize,
  diffServTBParamInterval       Unsigned32,
  diffServTBParamStorage        StorageType,
  diffServTBParamStatus         RowStatus
}

diffServTBParamId OBJECT-TYPE
  SYNTAX       IndexInteger
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An index that enumerates the Token Bucket Parameter entries.
    Managers obtain new values for row creation in this table by
    reading diffServTBParamNextFree."
  ::= { diffServTBParamEntry 1 }

diffServTBParamType OBJECT-TYPE
  SYNTAX       AutonomousType
  MAX-ACCESS   read-create

  STATUS       current
  DESCRIPTION
    "The Metering algorithm associated with the Token Bucket
    parameters.  zeroDotZero indicates this is unknown.

    Standard values for generic algorithms:
    diffServTBParamSimpleTokenBucket, diffServTBParamAvgRate,
    diffServTBParamSrTCMBlind, diffServTBParamSrTCMAware,
    diffServTBParamTrTCMBlind, diffServTBParamTrTCMAware, and
    diffServTBParamTswTCM are specified in this MIB as OBJECT-
    IDENTITYs; additional values may be further specified in other
    MIBs."
  ::= { diffServTBParamEntry 2 }

diffServTBParamRate OBJECT-TYPE
  SYNTAX       Unsigned32  (1..4294967295)
```

```
  UNITS       "kilobits per second"
  MAX-ACCESS  read-create
  STATUS      current



  DESCRIPTION
    "The token-bucket rate, in kilobits per second (kbps). This
    attribute is used for:
    1. CIR in RFC 2697 for srTCM
    2. CIR and PIR in RFC 2698 for trTCM
    3. CTR and PTR in RFC 2859 for TSWTCM

    4. AverageRate in RFC 3290."
  ::= { diffServTBParamEntry 3 }

diffServTBParamBurstSize OBJECT-TYPE
  SYNTAX      BurstSize
  UNITS       "Bytes"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The maximum number of bytes in a single transmission burst. This
    attribute is used for:
    1. CBS and EBS in RFC 2697 for srTCM
    2. CBS and PBS in RFC 2698 for trTCM
    3. Burst Size in RFC 3290."
  ::= { diffServTBParamEntry 4 }

diffServTBParamInterval OBJECT-TYPE
  SYNTAX      Unsigned32 (1..4294967295)
  UNITS       "microseconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The time interval used with the token bucket.  For:
    1. Average Rate Meter, the Informal Differentiated Services Model
      section 5.2.1, - Delta.
    2. Simple Token Bucket Meter, the Informal Differentiated
      Services Model section 5.1, - time interval t.
    3. RFC 2859 TSWTCM, - AVG_INTERVAL.
     4. RFC 2697 srTCM, RFC 2698 trTCM, - token bucket update time
      interval."
  ::= { diffServTBParamEntry 5 }

diffServTBParamStorage OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
```

```
  STATUS       current
  DESCRIPTION
    "The storage type for this conceptual row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServTBParamEntry 6 }



diffServTBParamStatus OBJECT-TYPE
  SYNTAX       RowStatus
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The status of this conceptual row. All writable objects in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
  ::= { diffServTBParamEntry 7 }

--
-- OIDs for diffServTBParamType
 definitions.
--

diffServTBMeters  OBJECT IDENTIFIER ::= { diffServMIBAdmin 1 }

diffServTBParamSimpleTokenBucket OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "Two Parameter Token Bucket Meter as described in the Informal
    Differentiated Services Model section 5.2.3."
  ::= { diffServTBMeters 1 }

diffServTBParamAvgRate OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "Average Rate Meter as described in the Informal Differentiated
    Services Model section 5.2.1."
  ::= { diffServTBMeters 2 }

diffServTBParamSrTCMBlind OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "Single Rate Three Color Marker Metering as defined by RFC 2697,
    in the `Color Blind' mode as described by the RFC."
```

```
  REFERENCE
     "RFC 2697"
  ::= { diffServTBMeters 3 }

diffServTBParamSrTCMAware OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "Single Rate Three Color Marker Metering as defined by RFC 2697,
    in the
 `Color Aware' mode as described by the RFC."
  REFERENCE
     "RFC 2697"



  ::= { diffServTBMeters 4 }

diffServTBParamTrTCMBlind OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "Two Rate Three Color Marker Metering as defined by RFC 2698, in
    the `Color Blind' mode as described by the RFC."
  REFERENCE
     "RFC 2698"
  ::= { diffServTBMeters 5 }

diffServTBParamTrTCMAware OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "Two Rate Three Color Marker Metering as defined by RFC 2698, in
    the `Color Aware' mode as described by the RFC."
  REFERENCE
     "RFC 2698"
  ::= { diffServTBMeters 6 }

diffServTBParamTswTCM OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "Time Sliding Window Three Color Marker Metering as defined by
    RFC 2859."
  REFERENCE
     "RFC 2859"
  ::= { diffServTBMeters 7 }

--
-- Actions
--
```

```
diffServAction        OBJECT IDENTIFIER ::= { diffServMIBObjects 5 }

--
-- The Action
 Table allows enumeration of the different types of
-- actions to be applied to a traffic flow.
--

diffServActionNextFree OBJECT-TYPE
  SYNTAX       IndexIntegerNextFree
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
    "This object contains an unused value for diffServActionId, or a
    zero to indicate that none exist."
  ::= { diffServAction 1 }



diffServActionTable OBJECT-TYPE
  SYNTAX       SEQUENCE OF DiffServActionEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "The Action Table enumerates actions that can be performed to a
    stream of traffic. Multiple actions can be concatenated. For
    example, traffic exiting from a meter may be counted, marked, and
    potentially dropped before entering a queue.

    Specific actions are indicated by diffServActionSpecific which
    points to an entry of a specific action type parameterizing the
    action in detail."
  ::= { diffServAction
 2 }

diffServActionEntry OBJECT-TYPE
  SYNTAX       DiffServActionEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "Each entry in the action table allows description of one
    specific action to be applied to traffic."
  INDEX { diffServActionId }
  ::= { diffServActionTable 1 }

DiffServActionEntry ::= SEQUENCE  {
  diffServActionId              IndexInteger,
  diffServActionInterface       InterfaceIndexOrZero,
```

```
  diffServActionNext          RowPointer,
  diffServActionSpecific      RowPointer,
  diffServActionStorage       StorageType,
  diffServActionStatus        RowStatus
}

diffServActionId OBJECT-TYPE
  SYNTAX      IndexInteger
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An index that enumerates the Action entries.  Managers obtain
    new values for row creation in this table by reading
    diffServActionNextFree."
  ::= { diffServActionEntry 1 }

diffServActionInterface
 OBJECT-TYPE
   SYNTAX      InterfaceIndexOrZero
   MAX-ACCESS  read-create
   STATUS      current



   DESCRIPTION
     "The interface index (value of ifIndex) that this action occurs
     on. This may be derived from the diffServDataPathStartEntry's
     index by extension through the various RowPointers. However, as
     this may be difficult for a network management station, it is
     placed here as well.  If this is indeterminate, the value is
     zero.

     This is of especial relevance when reporting the counters which
     may apply to traffic crossing an interface:
       diffServCountActOctets,
       diffServCountActPkts,
       diffServAlgDropOctets,
       diffServAlgDropPkts,
       diffServAlgRandomDropOctets, and
       diffServAlgRandomDropPkts.

     It is also especially relevant to the queue and scheduler which
     may be subsequently applied."
   ::= { diffServActionEntry 2 }

diffServActionNext
 OBJECT-TYPE
  SYNTAX      RowPointer
```

```
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
      "This selects the next Differentiated Services Functional Data
      Path Element to handle traffic for this data path. This
      RowPointer should point to an instance of one of:
        diffServClfrEntry
        diffServMeterEntry
        diffServActionEntry
        diffServAlgDropEntry
        diffServQEntry

      A value of zeroDotZero in this attribute indicates no further
      Differentiated Services treatment is performed on traffic of this
      data path. The use of zeroDotZero is the normal usage for the
      last functional data path element of the current data path.

      Setting this to point to a target that does not exist results in
      an inconsistentValue error.  If the row pointed to is removed or
      becomes inactive by other means, the treatment is as if this
      attribute contains a value of zeroDotZero."
    DEFVAL
      { zeroDotZero }
    ::= { diffServActionEntry 3 }

diffServActionSpecific OBJECT-TYPE



    SYNTAX       RowPointer
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
      "A pointer to an object instance providing additional information
      for the type of action indicated by this action table entry.

      For the standard actions defined by this MIB module, this should
      point to either a diffServDscpMarkActEntry or a
      diffServCountActEntry. For other actions, it may point to an
      object instance defined in some other MIB.

      Setting this to point to a target that does not exist results in
      an inconsistentValue error.  If the row pointed to is removed or
      becomes inactive by other means, the Meter should be treated as
      if it were not present.  This may lead to incorrect policy
      behavior."
    ::= { diffServActionEntry 4 }
```

```
diffServActionStorage OBJECT-TYPE
  SYNTAX       StorageType
  MAX-ACCESS   read-create
   STATUS      current
  DESCRIPTION
    "The storage type for this conceptual row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServActionEntry 5 }

diffServActionStatus OBJECT-TYPE
  SYNTAX       RowStatus
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The status of this conceptual row. All writable objects in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
  ::= { diffServActionEntry 6 }

-- DSCP Mark Action Table
--
-- Rows of this table are pointed to by diffServActionSpecific to
-- provide detailed parameters specific to the DSCP Mark action.
--
-- A single entry in this table can be shared by multiple




-- diffServActionTable entries.
--

diffServDscpMarkActTable
 OBJECT-TYPE
  SYNTAX       SEQUENCE OF DiffServDscpMarkActEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "This table enumerates specific DSCPs used for marking or
    remarking the DSCP field of IP packets. The entries of this table
    may be referenced by a diffServActionSpecific attribute."
  ::= { diffServAction 3 }

diffServDscpMarkActEntry OBJECT-TYPE
  SYNTAX       DiffServDscpMarkActEntry
```

```
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An entry in the DSCP mark action table that describes a single
    DSCP used for marking."
  INDEX { diffServDscpMarkActDscp }
  ::= { diffServDscpMarkActTable 1 }

DiffServDscpMarkActEntry ::= SEQUENCE  {
  diffServDscpMarkActDscp          Dscp
}

diffServDscpMarkActDscp OBJECT-TYPE
  SYNTAX       Dscp
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
    "The DSCP that this Action will store into
 the DSCP field of the
    subject. It is quite possible that the only packets subject to
    this Action are already marked with this DSCP. Note also that
    Differentiated Services processing may result in packet being
    marked on both ingress to a network and on egress from it, and
    that ingress and egress can occur in the same router."
  ::= { diffServDscpMarkActEntry 1 }

--
-- Count Action Table
--
-- Because the MIB structure allows multiple cascading
-- diffServActionEntry be used to describe multiple actions for a data
-- path, the counter became an optional action type.  In normal
-- implementation, either a data path has counters or it does not, as
-- opposed to being configurable. The management entity may choose to




-- read the counter or not.  Hence it is recommended for implementation
-- that have counters to always configure the count action as the first
-- of multiple actions.
--

diffServCountActNextFree OBJECT-TYPE
  SYNTAX       IndexIntegerNextFree
   MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
    "This object contains an unused value for
```

```
    diffServCountActId, or a zero to indicate that none exist."
  ::= { diffServAction 4 }

diffServCountActTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF DiffServCountActEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains counters for all the traffic passing through
    an action element."
  ::= { diffServAction 5 }

diffServCountActEntry OBJECT-TYPE
  SYNTAX      DiffServCountActEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An entry in the count action table describes a single set of
    traffic counters."
  INDEX { diffServCountActId }
  ::= { diffServCountActTable 1 }

DiffServCountActEntry ::= SEQUENCE  {
  diffServCountActId          IndexInteger,
  diffServCountActOctets      Counter64,
  diffServCountActPkts        Counter64,

  diffServCountActStorage     StorageType,
  diffServCountActStatus      RowStatus
}

diffServCountActId OBJECT-TYPE
  SYNTAX      IndexInteger
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An index that enumerates the Count Action entries.  Managers
    obtain new values for row creation in this table by reading




    diffServCountActNextFree."
  ::= { diffServCountActEntry 1 }

diffServCountActOctets OBJECT-TYPE
  SYNTAX      Counter64
  MAX-ACCESS  read-only
  STATUS      current
```

```
  DESCRIPTION
    "The number of octets at the Action data path element.

    Discontinuities in the value of this counter can occur at re-
    initialization of the management system and at other times as
    indicated by the value of ifCounterDiscontinuityTime on the
    relevant interface."
  ::= { diffServCountActEntry 2 }

diffServCountActPkts OBJECT-TYPE
  SYNTAX      Counter64
  MAX-ACCESS  read-only
  STATUS
 current
  DESCRIPTION
    "The number of packets at the Action data path element.

    Discontinuities in the value of this counter can occur at re-
    initialization of the management system and at other times as
    indicated by the value of ifCounterDiscontinuityTime on the
    relevant interface."
  ::= { diffServCountActEntry 3 }

diffServCountActStorage OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The storage type for this conceptual row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServCountActEntry 4 }

diffServCountActStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The status of this conceptual row. All writable objects in this
    row may be modified at any time. Setting this variable to
     'destroy' when the MIB contains one or more RowPointers pointing

    to it results in destruction being delayed until the row is no
    longer used."
  ::= { diffServCountActEntry 5 }
```

```
--
-- Algorithmic Drop Table
--

diffServAlgDrop       OBJECT IDENTIFIER ::= { diffServMIBObjects 6 }

diffServAlgDropNextFree OBJECT-TYPE
  SYNTAX       IndexIntegerNextFree
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
    "This object contains an unused value for diffServAlgDropId, or a
    zero to indicate that none exist."
  ::= { diffServAlgDrop 1 }

diffServAlgDropTable OBJECT-TYPE
  SYNTAX       SEQUENCE OF DiffServAlgDropEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "The algorithmic drop table contains entries describing an
    element that drops packets according to some algorithm."
  ::= { diffServAlgDrop 2 }

diffServAlgDropEntry OBJECT-TYPE
  SYNTAX       DiffServAlgDropEntry
  MAX-ACCESS
  not-accessible
  STATUS       current
  DESCRIPTION
    "An entry describes a process that drops packets according to
    some algorithm. Further details of the algorithm type are to be
    found in diffServAlgDropType and with more detail parameter entry
    pointed to by diffServAlgDropSpecific when necessary."
  INDEX { diffServAlgDropId }
  ::= { diffServAlgDropTable 1 }

DiffServAlgDropEntry ::= SEQUENCE  {
  diffServAlgDropId             IndexInteger,
  diffServAlgDropType           INTEGER,
  diffServAlgDropNext           RowPointer,
  diffServAlgDropQMeasure       RowPointer,
  diffServAlgDropQThreshold     Unsigned32,
  diffServAlgDropSpecific       RowPointer,
  diffServAlgDropOctets         Counter64,
```

```
  diffServAlgDropPkts            Counter64,
  diffServAlgRandomDropOctets    Counter64,
  diffServAlgRandomDropPkts      Counter64,
  diffServAlgDropStorage         StorageType,
  diffServAlgDropStatus
 RowStatus
}

diffServAlgDropId OBJECT-TYPE
  SYNTAX      IndexInteger
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An index that enumerates the Algorithmic Dropper entries.
    Managers obtain new values for row creation in this table by
    reading diffServAlgDropNextFree."
  ::= { diffServAlgDropEntry 1 }

diffServAlgDropType OBJECT-TYPE
  SYNTAX      INTEGER {
                other(1),
                tailDrop(2),
                headDrop(3),
                randomDrop(4),
                alwaysDrop(5)
}
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The type of algorithm used by this dropper. The value other(1)
    requires further specification in some other MIB module.

    In the tailDrop(2) algorithm, diffServAlgDropQThreshold
    represents the maximum depth of the queue, pointed to by
    diffServAlgDropQMeasure, beyond which all newly arriving packets

 will be dropped.

    In the headDrop(3) algorithm, if a packet arrives when the
    current depth of the queue, pointed to by
    diffServAlgDropQMeasure, is at diffServAlgDropQThreshold, packets
    currently at the head of the queue are dropped to make room for
    the new packet to be enqueued at the tail of the queue.

    In the randomDrop(4) algorithm, on packet arrival, an Active
    Queue Management algorithm is executed which may randomly drop a
    packet. This algorithm may be proprietary, and it may drop either
```

the arriving packet or another packet in the queue.
diffServAlgDropSpecific points to a diffServRandomDropEntry that
describes the algorithm. For this algorithm,

diffServAlgDropQThreshold is understood to be the absolute
maximum size of the queue and additional parameters are described
in diffServRandomDropTable.

The alwaysDrop(5) algorithm is as its name specifies; always
drop. In
this case, the other configuration values in this Entry
are not meaningful; There is no useful 'next' processing step,
there is no queue, and parameters describing the queue are not
useful. Therefore, diffServAlgDropNext, diffServAlgDropMeasure,
and diffServAlgDropSpecific are all zeroDotZero."
::= { diffServAlgDropEntry 2 }

diffServAlgDropNext OBJECT-TYPE
SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This selects the next Differentiated Services Functional Data
Path Element to handle traffic for this data path. This
RowPointer should point to an instance of one of:
diffServClfrEntry
diffServMeterEntry
diffServActionEntry
diffServQEntry

A value of zeroDotZero in this attribute indicates no further
Differentiated Services treatment is performed on traffic of this
data path. The use of zeroDotZero is the normal usage for the
last functional data path element of the current data path.

When diffServAlgDropType is alwaysDrop(5), this object is
ignored.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or
becomes inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."
::= { diffServAlgDropEntry 3 }

diffServAlgDropQMeasure OBJECT-TYPE
SYNTAX RowPointer

MAX-ACCESS read-create
STATUS current
DESCRIPTION
"Points to an entry in the diffServQTable to indicate the queue
that a drop algorithm is to monitor when deciding whether to drop
a packet. If the row pointed to does not exist, the algorithmic
dropper element is considered inactive.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or
becomes
inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."
::= { diffServAlgDropEntry 4 }

diffServAlgDropQThreshold OBJECT-TYPE
SYNTAX Unsigned32 (1..4294967295)
UNITS "Bytes"
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"A threshold on the depth in bytes of the queue being measured at
which a trigger is generated to the dropping algorithm, unless
diffServAlgDropType is alwaysDrop(5) where this object is
ignored.

For the tailDrop(2) or headDrop(3) algorithms, this represents
the depth of the queue, pointed to by diffServAlgDropQMeasure, at
which the drop action will take place. Other algorithms will need
to define their own semantics for this threshold."
::= { diffServAlgDropEntry 5 }

diffServAlgDropSpecific OBJECT-TYPE
SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION

"Points to a table entry that provides further detail regarding a
drop algorithm.

Entries with diffServAlgDropType equal to other(1) may have this
point to a table defined in another MIB module.

Entries with diffServAlgDropType equal to randomDrop(4) must have
this point to an entry in diffServRandomDropTable.

For all other algorithms specified in this MIB, this should take
the value zeroDotZero.

The diffServAlgDropType is authoritative for the type of the drop
algorithm and the specific parameters for the drop algorithm
needs to be evaluated based on the diffServAlgDropType.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or
becomes inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."

::= { diffServAlgDropEntry 6 }

diffServAlgDropOctets OBJECT-TYPE
SYNTAX
Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of octets that have been deterministically dropped by
this drop process.

Discontinuities in the value of this counter can occur at re-
initialization of the management system and at other times as
indicated by the value of ifCounterDiscontinuityTime on the
relevant interface."
::= { diffServAlgDropEntry 7 }

diffServAlgDropPkts OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of packets that have been deterministically dropped
by this drop process.

Discontinuities in the value of this counter can occur at re-
initialization of the management system and at other times as
indicated by the value of ifCounterDiscontinuityTime on the
relevant interface."
::= { diffServAlgDropEntry 8 }

diffServAlgRandomDropOctets OBJECT-TYPE

```
 SYNTAX      Counter64
  MAX-ACCESS   read-only
  STATUS      current
  DESCRIPTION
    "The number of octets that have been randomly dropped by this
    drop process.  This counter applies, therefore, only to random
    droppers.

    Discontinuities in the value of this counter can occur at re-
    initialization of the management system and at other times as
    indicated by the value of ifCounterDiscontinuityTime on the
    relevant interface."
  ::= { diffServAlgDropEntry 9 }

diffServAlgRandomDropPkts OBJECT-TYPE
  SYNTAX      Counter64
  MAX-ACCESS   read-only



  STATUS      current
  DESCRIPTION
    "The number of packets that have been randomly dropped by this
    drop process. This counter applies, therefore, only to random
    droppers.

    Discontinuities in the value of this counter can occur at re-
    initialization of the management system and at other times as
    indicated by the value of ifCounterDiscontinuityTime
 on the
    relevant interface."
  ::= { diffServAlgDropEntry 10 }

diffServAlgDropStorage OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS   read-create
  STATUS      current
  DESCRIPTION
    "The storage type for this conceptual row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServAlgDropEntry 11 }

diffServAlgDropStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS   read-create
  STATUS      current
```

```
  DESCRIPTION
    "The status of this conceptual row. All writable objects in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
  ::= { diffServAlgDropEntry 12 }

--
-- Random Drop Table
--

diffServRandomDropNextFree OBJECT-TYPE
  SYNTAX
    IndexIntegerNextFree
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
    "This object contains an unused value for diffServRandomDropId,
    or a zero to indicate that none exist."
  ::= { diffServAlgDrop 3 }



diffServRandomDropTable OBJECT-TYPE
  SYNTAX       SEQUENCE OF DiffServRandomDropEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "The random drop table contains entries describing a process that
    drops packets randomly. Entries in this table are pointed to by
    diffServAlgDropSpecific."
  ::= { diffServAlgDrop 4 }

diffServRandomDropEntry OBJECT-TYPE
  SYNTAX       DiffServRandomDropEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An entry describes a process that drops packets according to a
    random algorithm."
  INDEX { diffServRandomDropId }
  ::= { diffServRandomDropTable 1 }

DiffServRandomDropEntry ::= SEQUENCE  {
  diffServRandomDropId
```

```
            IndexInteger,
  diffServRandomDropMinThreshBytes   Unsigned32,
  diffServRandomDropMinThreshPkts    Unsigned32,
  diffServRandomDropMaxThreshBytes   Unsigned32,
  diffServRandomDropMaxThreshPkts    Unsigned32,
  diffServRandomDropProbMax          Unsigned32,
  diffServRandomDropWeight           Unsigned32,
  diffServRandomDropSamplingRate     Unsigned32,
  diffServRandomDropStorage          StorageType,
  diffServRandomDropStatus           RowStatus
}

diffServRandomDropId OBJECT-TYPE
  SYNTAX       IndexInteger
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An index that enumerates the Random Drop entries.  Managers
    obtain new values for row creation in this table by reading
    diffServRandomDropNextFree."
  ::= { diffServRandomDropEntry 1 }

diffServRandomDropMinThreshBytes OBJECT-TYPE
  SYNTAX       Unsigned32  (1..4294967295)
  UNITS        "bytes"
  MAX-ACCESS   read-create
  STATUS       current



   DESCRIPTION
    "The average queue depth in bytes, beyond which traffic has a
    non-zero probability of being dropped. Changes in this variable
    may or may not be reflected in the reported value of
    diffServRandomDropMinThreshPkts."
  ::= { diffServRandomDropEntry 2 }

diffServRandomDropMinThreshPkts OBJECT-TYPE
  SYNTAX       Unsigned32  (1..4294967295)
  UNITS        "packets"
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The average queue depth in packets, beyond which traffic has a
    non-zero probability of being dropped. Changes in this variable
    may or may not be reflected in the reported value of
    diffServRandomDropMinThreshBytes."
  ::= { diffServRandomDropEntry 3 }
```

```
diffServRandomDropMaxThreshBytes OBJECT-TYPE
  SYNTAX      Unsigned32  (1..4294967295)
  UNITS       "bytes"
  MAX-ACCESS   read-create
  STATUS      current
  DESCRIPTION
    "The average queue depth beyond which
 traffic has a probability
    indicated by diffServRandomDropProbMax of being dropped or
    marked. Note that this differs from the physical queue limit,
    which is stored in diffServAlgDropQThreshold. Changes in this
    variable may or may not be reflected in the reported value of
    diffServRandomDropMaxThreshPkts."
  ::= { diffServRandomDropEntry 4 }

diffServRandomDropMaxThreshPkts OBJECT-TYPE
  SYNTAX      Unsigned32  (1..4294967295)
  UNITS       "packets"
  MAX-ACCESS   read-create
  STATUS      current
  DESCRIPTION
    "The average queue depth beyond which traffic has a probability
    indicated by diffServRandomDropProbMax of being dropped or
    marked. Note that this differs from the physical queue limit,
    which is stored in diffServAlgDropQThreshold. Changes in this
    variable may or may not be reflected in the reported value of
    diffServRandomDropMaxThreshBytes."
  ::= { diffServRandomDropEntry 5 }

diffServRandomDropProbMax
 OBJECT-TYPE



  SYNTAX      Unsigned32 (0..1000)
  MAX-ACCESS   read-create
  STATUS      current
  DESCRIPTION
    "The worst case random drop probability, expressed in drops per
    thousand packets.

    For example, if in the worst case every arriving packet may be
    dropped (100%) for a period, this has the value 1000.
    Alternatively, if in the worst case only one percent (1%) of
    traffic may be dropped, it has the value 10."
  ::= { diffServRandomDropEntry 6 }
```

```
diffServRandomDropWeight OBJECT-TYPE
  SYNTAX       Unsigned32 (0..65536)
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The weighting of past history in affecting the Exponentially
    Weighted Moving Average function that calculates the current
    average queue depth.  The equation uses
    diffServRandomDropWeight/65536 as the coefficient for the new
    sample in the equation, and (65536 -
    diffServRandomDropWeight)/65536
 as the coefficient of the old
    value.

    Implementations may limit the values of diffServRandomDropWeight
    to a subset of the possible range of values, such as powers of
    two. Doing this would facilitate implementation of the
    Exponentially Weighted Moving Average using shift instructions or
    registers."
  ::= { diffServRandomDropEntry 7 }

diffServRandomDropSamplingRate OBJECT-TYPE
  SYNTAX       Unsigned32 (0..1000000)
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The number of times per second the queue is sampled for queue
    average calculation.  A value of zero is used to mean that the
    queue is sampled approximately each time a packet is enqueued (or
    dequeued)."
  ::= { diffServRandomDropEntry 8 }

diffServRandomDropStorage OBJECT-TYPE
  SYNTAX       StorageType
  MAX-ACCESS   read-create
  STATUS       current



  DESCRIPTION
    "The storage type for this conceptual
 row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServRandomDropEntry 9 }

diffServRandomDropStatus OBJECT-TYPE
```

```
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The status of this conceptual row. All writable objects in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
  ::= { diffServRandomDropEntry 10 }

--
-- Queue Table
--

diffServQueue         OBJECT IDENTIFIER ::= { diffServMIBObjects 7 }

--
-- An entry of diffServQTable represents a FIFO queue Differentiated
-- Services Functional Data Path element as described in the Informal
-- Differentiated Services Model section 7.1.1. Note that the
-- specification of scheduling
 parameters for a queue as part of the
-- input to a scheduler functional data path element as described in
-- the Informal Differentiated Services Model section 7.1.2. This
-- allows building of hierarchical queuing/scheduling. A queue
-- therefore has these attributes:
--
-- 1. Which scheduler will service this queue, diffServQNext.
-- 2. How the scheduler will service this queue, with respect
--    to all the other queues the same scheduler needs to service,
--    diffServQMinRate.
--
-- Note that upstream Differentiated Services Functional Data Path
-- elements may point to a shared diffServQTable entry as described
-- in the Informal Differentiated Services Model section 7.1.1.
--

diffServQNextFree OBJECT-TYPE
  SYNTAX      IndexIntegerNextFree
  MAX-ACCESS  read-only



  STATUS      current
  DESCRIPTION
    "This object contains an unused value for diffServQId, or a zero
    to indicate that none exist."
```

```
  ::= { diffServQueue 1 }

diffServQTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF DiffServQEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "The Queue Table enumerates the individual queues.  Note that the
    MIB models queuing systems as composed of individual queues, one
    per class of traffic, even though they may in fact be structured
    as classes of traffic scheduled using a common calendar queue, or
    in other ways."
  ::= { diffServQueue 2 }

diffServQEntry OBJECT-TYPE
  SYNTAX       DiffServQEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An entry in the Queue Table describes a single queue or class of
    traffic."
  INDEX { diffServQId }
  ::= { diffServQTable 1 }

DiffServQEntry ::= SEQUENCE  {
  diffServQId                 IndexInteger,
  diffServQNext               RowPointer,
  diffServQMinRate            RowPointer,
  diffServQMaxRate            RowPointer,
  diffServQStorage
  StorageType,
  diffServQStatus             RowStatus
}

diffServQId OBJECT-TYPE
  SYNTAX       IndexInteger
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An index that enumerates the Queue entries.  Managers obtain new
    values for row creation in this table by reading
    diffServQNextFree."
  ::= { diffServQEntry 1 }

diffServQNext OBJECT-TYPE
```

SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This selects the next Differentiated Services Scheduler. The
RowPointer must point to a diffServSchedulerEntry.

A value of zeroDotZero in this attribute indicates an incomplete
diffServQEntry instance. In such a case, the entry has no
operational effect, since it has no parameters to give it
meaning.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or

becomes inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."
::= { diffServQEntry 2 }

diffServQMinRate OBJECT-TYPE
SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This RowPointer indicates the diffServMinRateEntry that the
scheduler, pointed to by diffServQNext, should use to service
this queue.

If the row pointed to is zeroDotZero, the minimum rate and
priority is unspecified.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or
becomes inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."
::= { diffServQEntry 3 }

diffServQMaxRate OBJECT-TYPE
SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This RowPointer indicates the diffServMaxRateEntry
that the
scheduler, pointed to by diffServQNext, should use to service
this queue.

If the row pointed to is zeroDotZero, the maximum rate is the

```
      line speed of the interface.



      Setting this to point to a target that does not exist results in
      an inconsistentValue error.  If the row pointed to is removed or
      becomes inactive by other means, the treatment is as if this
      attribute contains a value of zeroDotZero."
    ::= { diffServQEntry 4 }

diffServQStorage OBJECT-TYPE
    SYNTAX       StorageType
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
      "The storage type for this conceptual row.  Conceptual rows
      having the value 'permanent' need not allow write-access to any
      columnar objects in the row."
    DEFVAL { nonVolatile }
    ::= { diffServQEntry 5 }

diffServQStatus OBJECT-TYPE
    SYNTAX       RowStatus
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION

   "The status of this conceptual row. All writable objects in this
      row may be modified at any time. Setting this variable to
      'destroy' when the MIB contains one or more RowPointers pointing
      to it results in destruction being delayed until the row is no
      longer used."
    ::= { diffServQEntry 6 }

--
-- Scheduler Table
--

diffServScheduler      OBJECT IDENTIFIER ::= { diffServMIBObjects 8 }

--
-- A Scheduler Entry represents a packet scheduler, such as a priority
-- scheduler or a WFQ scheduler. It provides flexibility for multiple
-- scheduling algorithms, each servicing multiple queues, to be used on
-- the same logical/physical interface.
--
-- Note that upstream queues or schedulers specify several of the
```

```
-- scheduler's parameters. These must be properly specified if the
-- scheduler is to behave as expected.
--
-- The diffServSchedulerMaxRate attribute specifies the parameters when
-- a scheduler's output is sent to another scheduler. This is used in
-- building
 hierarchical queues or schedulers.




--
-- More discussion of the scheduler functional data path element is in
-- the Informal Differentiated Services Model section 7.1.2.
--

diffServSchedulerNextFree OBJECT-TYPE
  SYNTAX       IndexIntegerNextFree
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
    "This object contains an unused value for diffServSchedulerId, or
    a zero to indicate that none exist."
  ::= { diffServScheduler 1 }

diffServSchedulerTable OBJECT-TYPE
  SYNTAX       SEQUENCE OF DiffServSchedulerEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "The Scheduler Table enumerates packet schedulers. Multiple
    scheduling algorithms can be used on a given data path, with each
    algorithm described by one diffServSchedulerEntry."
  ::= { diffServScheduler 2 }

diffServSchedulerEntry OBJECT-TYPE
  SYNTAX       DiffServSchedulerEntry
  MAX-ACCESS   not-accessible
  STATUS       current
   DESCRIPTION
    "An entry in the Scheduler Table describing a single instance of
    a scheduling algorithm."
  INDEX { diffServSchedulerId }
  ::= { diffServSchedulerTable 1 }

DiffServSchedulerEntry ::= SEQUENCE  {
  diffServSchedulerId                IndexInteger,
  diffServSchedulerNext               RowPointer,
  diffServSchedulerMethod              AutonomousType,
```

```
  diffServSchedulerMinRate            RowPointer,
  diffServSchedulerMaxRate            RowPointer,
  diffServSchedulerStorage            StorageType,
  diffServSchedulerStatus             RowStatus
}

diffServSchedulerId OBJECT-TYPE
  SYNTAX       IndexInteger
  MAX-ACCESS   not-accessible
  STATUS       current



  DESCRIPTION
    "An index that enumerates the Scheduler entries.  Managers obtain
    new values for row creation in this table by reading
    diffServSchedulerNextFree."
  ::= { diffServSchedulerEntry 1 }

diffServSchedulerNext OBJECT-TYPE

  SYNTAX       RowPointer
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "This selects the next Differentiated Services Functional Data
    Path Element to handle traffic for this data path. This normally
    is null (zeroDotZero), or points to a diffServSchedulerEntry or a
    diffServQEntry.

    However, this RowPointer may also point to an instance of:
      diffServClfrEntry,
      diffServMeterEntry,
      diffServActionEntry,
      diffServAlgDropEntry.

    It would point another diffServSchedulerEntry when implementing
    multiple scheduler methods for the same data path, such as having
    one set of queues scheduled by WRR and that group participating
    in a priority scheduling system in which other queues compete
    with it in that way.  It might also point to a second scheduler
    in a hierarchical scheduling system.

    If the row pointed to is zeroDotZero, no further Differentiated
    Services
 treatment is performed on traffic of this data path.

    Setting this to point to a target that does not exist results in
```

an inconsistentValue error. If the row pointed to is removed or
becomes inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."
DEFVAL { zeroDotZero }
::= { diffServSchedulerEntry 2 }

diffServSchedulerMethod OBJECT-TYPE
SYNTAX AutonomousType
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The scheduling algorithm used by this Scheduler. zeroDotZero
indicates that this is unknown. Standard values for generic
algorithms: diffServSchedulerPriority, diffServSchedulerWRR, and
diffServSchedulerWFQ are specified in this MIB; additional values

may be further specified in other MIBs."
::= { diffServSchedulerEntry 3 }

diffServSchedulerMinRate OBJECT-TYPE
SYNTAX RowPointer
MAX-ACCESS read-create

STATUS current
DESCRIPTION
"This RowPointer indicates the entry in diffServMinRateTable
which indicates the priority or minimum output rate from this
scheduler. This attribute is used only when there is more than
one level of scheduler.

When it has the value zeroDotZero, it indicates that no minimum
rate or priority is imposed.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or
becomes inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."
DEFVAL { zeroDotZero }
::= { diffServSchedulerEntry 4 }

diffServSchedulerMaxRate OBJECT-TYPE
SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This RowPointer indicates the entry in diffServMaxRateTable

```
      which indicates the maximum output rate from this scheduler.
      When
 more than one maximum rate applies (eg, when a multi-rate
      shaper is in view), it points to the first of those rate entries.
      This attribute is used only when there is more than one level of
      scheduler.

      When it has the value zeroDotZero, it indicates that no maximum
      rate is imposed.

      Setting this to point to a target that does not exist results in
      an inconsistentValue error.  If the row pointed to is removed or
      becomes inactive by other means, the treatment is as if this
      attribute contains a value of zeroDotZero."
    DEFVAL      { zeroDotZero }
    ::= { diffServSchedulerEntry 5 }

diffServSchedulerStorage OBJECT-TYPE
    SYNTAX       StorageType
    MAX-ACCESS   read-create




    STATUS       current
    DESCRIPTION
      "The storage type for this conceptual row.  Conceptual rows
      having the value 'permanent' need not allow write-access to any
      columnar objects in the row."
    DEFVAL { nonVolatile }
    ::=
 { diffServSchedulerEntry 6 }

diffServSchedulerStatus OBJECT-TYPE
    SYNTAX       RowStatus
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
      "The status of this conceptual row. All writable objects in this
      row may be modified at any time. Setting this variable to
      'destroy' when the MIB contains one or more RowPointers pointing
      to it results in destruction being delayed until the row is no
      longer used."
    ::= { diffServSchedulerEntry 7 }

--
-- OIDs for diffServTBParamType definitions.
--
```

```
diffServSchedulers  OBJECT IDENTIFIER ::= { diffServMIBAdmin 2 }

diffServSchedulerPriority OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "For use with diffServSchedulerMethod to indicate the Priority
    scheduling method.  This is defined as an algorithm in which the
    presence of data in a queue or set of queues absolutely precludes
    dequeue from another queue or set of queues of lower priority.
    Note
 that attributes from diffServMinRateEntry of the
    queues/schedulers feeding this scheduler are used when
    determining the next packet to schedule."
  ::= { diffServSchedulers 1 }

diffServSchedulerWRR OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "For use with diffServSchedulerMethod to indicate the Weighted
    Round Robin scheduling method, defined as any algorithm in which
    a set of queues are visited in a fixed order, and varying amounts
    of traffic are removed from each queue in turn to implement an
    average output rate by class. Notice attributes from
    diffServMinRateEntry of the queues/schedulers feeding this
    scheduler are used when determining the next packet to schedule."



  ::= { diffServSchedulers 2 }

diffServSchedulerWFQ OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "For use with diffServSchedulerMethod to indicate the Weighted
    Fair Queuing scheduling method, defined as any algorithm
 in which
    a set of queues are conceptually visited in some order, to
    implement an average output rate by class. Notice attributes from
    diffServMinRateEntry of the queues/schedulers feeding this
    scheduler are used when determining the next packet to schedule."
  ::= { diffServSchedulers 3 }

--
-- Minimum Rate Parameters Table
--
-- The parameters used by a scheduler for its inputs or outputs are
-- maintained separately from the Queue or Scheduler table entries for
-- reusability reasons and so that they may be used by both queues and
```

```
-- schedulers.  This follows the approach for separation of data path
-- elements from parameterization that is used throughout this MIB.
-- Use of these Minimum Rate Parameter Table entries by Queues and
-- Schedulers allows the modeling of hierarchical scheduling systems.
--
-- Specifically, a Scheduler has one or more inputs and one output.
-- Any queue feeding a scheduler, or any scheduler which feeds a second
-- scheduler,
 might specify a minimum transfer rate by pointing to an
-- Minimum Rate Parameter Table entry.
--
-- The diffServMinRatePriority/Abs/Rel attributes are used as
-- parameters to the work-conserving portion of a scheduler:
-- "work-conserving" implies that the scheduler can continue to emit
-- data as long as there is data available at its input(s).  This has
-- the effect of guaranteeing a certain priority relative to other
-- scheduler inputs and/or a certain minimum proportion of the
-- available output bandwidth. Properly configured, this means a
-- certain minimum rate, which may be exceeded should traffic be
-- available should there be spare bandwidth after all other classes
-- have had opportunities to consume their own minimum rates.
--

diffServMinRateNextFree OBJECT-TYPE
  SYNTAX      IndexIntegerNextFree
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object contains an unused value for diffServMinRateId, or a
    zero to indicate
 that none exist."



  ::= { diffServScheduler 3 }

diffServMinRateTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF DiffServMinRateEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "The Minimum Rate Parameters Table enumerates individual sets of
    scheduling parameter that can be used/reused by Queues and
    Schedulers."
  ::= { diffServScheduler 4 }

diffServMinRateEntry OBJECT-TYPE
  SYNTAX      DiffServMinRateEntry
```

```
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An entry in the Minimum Rate Parameters Table describes a single
    set of scheduling parameters for use by one or more queues or
    schedulers."
  INDEX { diffServMinRateId }
  ::= { diffServMinRateTable 1 }

DiffServMinRateEntry ::= SEQUENCE  {
  diffServMinRateId             IndexInteger,
  diffServMinRatePriority       Unsigned32,
  diffServMinRateAbsolute       Unsigned32,
  diffServMinRateRelative       Unsigned32,
   diffServMinRateStorage       StorageType,
  diffServMinRateStatus         RowStatus
}

diffServMinRateId OBJECT-TYPE
  SYNTAX       IndexInteger
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An index that enumerates the Scheduler Parameter entries.
    Managers obtain new values for row creation in this table by
    reading diffServMinRateNextFree."
  ::= { diffServMinRateEntry 1 }

diffServMinRatePriority OBJECT-TYPE
  SYNTAX       Unsigned32  (1..4294967295)
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The priority of this input to the associated scheduler, relative




    to the scheduler's other inputs. A queue or scheduler with a
    larger numeric value will be served before another with a smaller
    numeric value."
  ::= { diffServMinRateEntry 2 }

diffServMinRateAbsolute OBJECT-TYPE
  SYNTAX       Unsigned32  (1..4294967295)
  UNITS        "kilobits per second"
  MAX-ACCESS
  read-create
  STATUS       current
```

```
    DESCRIPTION
      "The minimum absolute rate, in kilobits/sec, that a downstream
      scheduler element should allocate to this queue. If the value is
      zero, then there is effectively no minimum rate guarantee. If the
      value is non-zero, the scheduler will assure the servicing of
      this queue to at least this rate.

      Note that this attribute value and that of
      diffServMinRateRelative are coupled: changes to one will affect
      the value of the other. They are linked by the following
      equation, in that setting one will change the other:

        diffServMinRateRelative =
              (diffServMinRateAbsolute*1000000)/ifSpeed

      or, if appropriate:

        diffServMinRateRelative = diffServMinRateAbsolute/ifHighSpeed"
    REFERENCE
       "ifSpeed, ifHighSpeed, Interface MIB, RFC 2863"
    ::= { diffServMinRateEntry 3 }

  diffServMinRateRelative OBJECT-TYPE
    SYNTAX       Unsigned32  (1..4294967295)
     MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
      "The minimum rate that a downstream scheduler element should
      allocate to this queue, relative to the maximum rate of the
      interface as reported by ifSpeed or ifHighSpeed, in units of
      1/1000 of 1. If the value is zero, then there is effectively no
      minimum rate guarantee. If the value is non-zero, the scheduler
      will assure the servicing of this queue to at least this rate.

      Note that this attribute value and that of
      diffServMinRateAbsolute are coupled: changes to one will affect
      the value of the other. They are linked by the following
      equation, in that setting one will change the other:



        diffServMinRateRelative =
              (diffServMinRateAbsolute*1000000)/ifSpeed

      or, if appropriate:

        diffServMinRateRelative = diffServMinRateAbsolute/ifHighSpeed"
    REFERENCE
```

```
      "ifSpeed, ifHighSpeed, Interface MIB,
 RFC 2863"
  ::= { diffServMinRateEntry 4 }

diffServMinRateStorage OBJECT-TYPE
  SYNTAX       StorageType
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The storage type for this conceptual row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServMinRateEntry 5 }

diffServMinRateStatus OBJECT-TYPE
  SYNTAX       RowStatus
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The status of this conceptual row. All writable objects in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
  ::= { diffServMinRateEntry 6 }

--
-- Maximum Rate Parameter Table
--
-- The parameters used by a scheduler for its inputs or outputs are
-- maintained
 separately from the Queue or Scheduler table entries for
-- reusability reasons and so that they may be used by both queues and
-- schedulers.  This follows the approach for separation of data path
-- elements from parameterization that is used throughout this MIB.
-- Use of these Maximum Rate Parameter Table entries by Queues and
-- Schedulers allows the modeling of hierarchical scheduling systems.
--
-- Specifically, a Scheduler has one or more inputs and one output.
-- Any queue feeding a scheduler, or any scheduler which feeds a second
-- scheduler, might specify a maximum transfer rate by pointing to a
-- Maximum Rate Parameter Table entry. Multi-rate shapers, such as a




-- Dual Leaky Bucket algorithm, specify their rates using multiple
-- Maximum Rate Parameter Entries with the same diffServMaxRateId but
```

```
-- different diffServMaxRateLevels.
--
-- The diffServMaxRateLevel/Abs/Rel attributes are used as
-- parameters to the non-work-conserving portion of a scheduler:
-- non-work-conserving
 implies that the scheduler may sometimes not
-- emit a packet, even if there is data available at its input(s).
-- This has the effect of limiting the servicing of the queue/scheduler
-- input or output, in effect performing shaping of the packet stream
-- passing through the queue/scheduler, as described in the Informal
-- Differentiated Services Model section 7.2.
--

diffServMaxRateNextFree OBJECT-TYPE
  SYNTAX       IndexIntegerNextFree
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
    "This object contains an unused value for diffServMaxRateId, or a
    zero to indicate that none exist."
  ::= { diffServScheduler 5 }

diffServMaxRateTable OBJECT-TYPE
  SYNTAX       SEQUENCE OF DiffServMaxRateEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "The Maximum Rate Parameter Table enumerates individual sets of
    scheduling parameter that can be used/reused by Queues and
    Schedulers."
  ::=
 { diffServScheduler 6 }

diffServMaxRateEntry OBJECT-TYPE
  SYNTAX       DiffServMaxRateEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An entry in the Maximum Rate Parameter Table describes a single
    set of scheduling parameters for use by one or more queues or
    schedulers."
  INDEX { diffServMaxRateId, diffServMaxRateLevel }
  ::= { diffServMaxRateTable 1 }

DiffServMaxRateEntry ::= SEQUENCE  {
  diffServMaxRateId             IndexInteger,
  diffServMaxRateLevel          Unsigned32,
  diffServMaxRateAbsolute       Unsigned32,
```

```
  diffServMaxRateRelative       Unsigned32,
  diffServMaxRateThreshold      BurstSize,
  diffServMaxRateStorage        StorageType,
  diffServMaxRateStatus         RowStatus
}

diffServMaxRateId OBJECT-TYPE
  SYNTAX      IndexInteger
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An index that enumerates the Maximum Rate Parameter entries.

    Managers obtain new values for row creation in this table by
    reading diffServMaxRateNextFree."
  ::= { diffServMaxRateEntry 1 }

diffServMaxRateLevel OBJECT-TYPE
  SYNTAX      Unsigned32 (1..32)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An index that indicates which level of a multi-rate shaper is
    being given its parameters. A multi-rate shaper has some number
    of rate levels. Frame Relay's dual rate specification refers to a
    'committed' and an 'excess' rate; ATM's dual rate specification
    refers to a 'mean' and a 'peak' rate. This table is generalized
    to support an arbitrary number of rates. The committed or mean
    rate is level 1, the peak rate (if any) is the highest level rate
    configured, and if there are other rates they are distributed in
    monotonically increasing order between them."
  ::= { diffServMaxRateEntry 2 }

diffServMaxRateAbsolute OBJECT-TYPE
  SYNTAX      Unsigned32
 (1..4294967295)
  UNITS       "kilobits per second"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The maximum rate in kilobits/sec that a downstream scheduler
    element should allocate to this queue. If the value is zero, then
    there is effectively no maximum rate limit and that the scheduler
    should attempt to be work conserving for this queue. If the value
    is non-zero, the scheduler will limit the servicing of this queue
```

to, at most, this rate in a non-work-conserving manner.

Note that this attribute value and that of
diffServMaxRateRelative are coupled: changes to one will affect
the value of the other. They are linked by the following

equation, in that setting one will change the other:

diffServMaxRateRelative =
(diffServMaxRateAbsolute*1000000)/ifSpeed

or, if appropriate:

diffServMaxRateRelative = diffServMaxRateAbsolute/ifHighSpeed"
REFERENCE
"ifSpeed, ifHighSpeed, Interface MIB, RFC 2863"
::= { diffServMaxRateEntry 3 }

diffServMaxRateRelative OBJECT-TYPE
SYNTAX Unsigned32 (1..4294967295)
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The maximum rate that a downstream scheduler element should
allocate to this queue, relative to the maximum rate of the
interface as reported by ifSpeed or ifHighSpeed, in units of
1/1000 of 1. If the value is zero, then there is effectively no
maximum rate limit and the scheduler should attempt to be work
conserving for this queue. If the value is non-zero, the
scheduler will limit the servicing of this queue to, at most,
this rate in a non-work-conserving manner.

Note that this attribute value and that of
diffServMaxRateAbsolute are coupled: changes to one will affect
the value of the other. They are linked by the following
equation, in that setting
one will change the other:

diffServMaxRateRelative =
(diffServMaxRateAbsolute*1000000)/ifSpeed

or, if appropriate:

diffServMaxRateRelative = diffServMaxRateAbsolute/ifHighSpeed"
REFERENCE
"ifSpeed, ifHighSpeed, Interface MIB, RFC 2863"

```
  ::= { diffServMaxRateEntry 4 }

diffServMaxRateThreshold OBJECT-TYPE
  SYNTAX      BurstSize
  UNITS       "Bytes"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The number of bytes of queue depth at which the rate of a




    multi-rate scheduler will increase to the next output rate. In
    the last conceptual row for such a shaper, this threshold is
    ignored and by convention is zero."
  REFERENCE
     "Adaptive rate Shaper, RFC 2963"
  ::= { diffServMaxRateEntry 5 }

diffServMaxRateStorage OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The storage type for this
 conceptual row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServMaxRateEntry 6 }

diffServMaxRateStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The status of this conceptual row. All writable objects in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
  ::= { diffServMaxRateEntry 7 }

--
-- MIB Compliance statements.
--

diffServMIBCompliances OBJECT IDENTIFIER ::=
```

```
                        { diffServMIBConformance 1 }
diffServMIBGroups       OBJECT IDENTIFIER ::=
                        { diffServMIBConformance 2 }

diffServMIBFullCompliance MODULE-COMPLIANCE
  STATUS current

  DESCRIPTION
    "When this MIB is implemented with support for read-create, then
    such an implementation can claim full compliance. Such devices
    can then be both monitored and configured with this MIB."

  MODULE IF-MIB -- The interfaces MIB, RFC2863
  MANDATORY-GROUPS {



    ifCounterDiscontinuityGroup
  }

  MODULE -- This Module
  MANDATORY-GROUPS {
     diffServMIBDataPathGroup, diffServMIBClfrGroup,
     diffServMIBClfrElementGroup, diffServMIBMultiFieldClfrGroup,
     diffServMIBActionGroup, diffServMIBAlgDropGroup,
     diffServMIBQGroup, diffServMIBSchedulerGroup,
     diffServMIBMaxRateGroup, diffServMIBMinRateGroup,
     diffServMIBCounterGroup
  }

  GROUP diffServMIBMeterGroup
  DESCRIPTION
    "This group is mandatory for devices that implement metering
    functions."

  GROUP diffServMIBTBParamGroup
  DESCRIPTION
    "This group is mandatory for devices that implement token-bucket
    metering functions."

   GROUP diffServMIBDscpMarkActGroup
  DESCRIPTION
    "This group is mandatory for devices that implement DSCP-Marking
    functions."

  GROUP diffServMIBRandomDropGroup
  DESCRIPTION
    "This group is mandatory for devices that implement Random Drop
```

functions."

OBJECT diffServDataPathStatus
SYNTAX RowStatus { active(1) }
WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
DESCRIPTION
"Support for createAndWait and notInService is not required."

OBJECT diffServClfrStatus
SYNTAX RowStatus { active(1) }
WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
DESCRIPTION
"Support for createAndWait and notInService is not required."

OBJECT diffServClfrElementStatus
SYNTAX RowStatus { active(1) }
WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }

DESCRIPTION
"Support for createAndWait and notInService is not required."

OBJECT diffServMultiFieldClfrAddrType
SYNTAX InetAddressType
{ unknown(0), ipv4(1), ipv6(2) }
DESCRIPTION
"An implementation is only required to support IPv4 and IPv6
addresses."

OBJECT diffServMultiFieldClfrDstAddr
SYNTAX InetAddress (SIZE(0|4|16))
DESCRIPTION
"An implementation is only required to support IPv4 and globally
unique IPv6 addresses."

OBJECT diffServAlgDropStatus
SYNTAX RowStatus { active(1) }
WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
DESCRIPTION
"Support for createAndWait and notInService is not required."

OBJECT diffServRandomDropStatus
SYNTAX RowStatus { active(1) }
WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
DESCRIPTION
"Support for createAndWait and notInService is not required."

```
  OBJECT diffServQStatus
  SYNTAX RowStatus { active(1) }
  WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
  DESCRIPTION
    "Support for createAndWait and notInService is not required."

  OBJECT diffServSchedulerStatus
   SYNTAX RowStatus { active(1) }
  WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
  DESCRIPTION
    "Support for createAndWait and notInService is not required."

  OBJECT diffServMinRateStatus
  SYNTAX RowStatus { active(1) }
  WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
  DESCRIPTION
    "Support for createAndWait and notInService is not required."

  OBJECT diffServMaxRateStatus
  SYNTAX RowStatus { active(1) }
  WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }



  DESCRIPTION
    "Support for createAndWait and notInService is not required."

  ::= { diffServMIBCompliances 1 }

--
-- Read-Only Compliance
--

diffServMIBReadOnlyCompliance MODULE-COMPLIANCE
  STATUS current
  DESCRIPTION
    "When this MIB is implemented without support for read-create
    (i.e. in read-only mode), then such an implementation can claim
    read-only compliance. Such a device can then be monitored but can
    not be configured
 with this MIB."

  MODULE IF-MIB -- The interfaces MIB, RFC2863
  MANDATORY-GROUPS {
    ifCounterDiscontinuityGroup
  }

  MODULE -- This Module
```

```
MANDATORY-GROUPS {
    diffServMIBDataPathGroup, diffServMIBClfrGroup,
    diffServMIBClfrElementGroup, diffServMIBMultiFieldClfrGroup,
    diffServMIBActionGroup, diffServMIBAlgDropGroup,
    diffServMIBQGroup, diffServMIBSchedulerGroup,
    diffServMIBMaxRateGroup, diffServMIBMinRateGroup,
    diffServMIBCounterGroup
}

GROUP diffServMIBMeterGroup
DESCRIPTION
   "This group is mandatory for devices that implement metering
   functions."

GROUP diffServMIBTBParamGroup
DESCRIPTION
   "This group is mandatory for devices that implement token-bucket
   metering functions."

GROUP       diffServMIBDscpMarkActGroup
DESCRIPTION
   "This group is mandatory for devices that implement DSCP-Marking
   functions."

GROUP       diffServMIBRandomDropGroup



 DESCRIPTION
   "This group is mandatory for devices that implement Random Drop
   functions."

OBJECT      diffServDataPathStart
MIN-ACCESS   read-only
DESCRIPTION
   "Write access is not required."

OBJECT      diffServDataPathStorage
MIN-ACCESS   read-only
DESCRIPTION
   "Write access is not required."

OBJECT      diffServDataPathStatus
SYNTAX       RowStatus { active(1) }
MIN-ACCESS   read-only
DESCRIPTION
   "Write access is not required, and active is the only status that
   needs to be supported."
```

OBJECT diffServClfrNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object not needed when diffServClfrTable is implemented read-only"

OBJECT diffServClfrStorage
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServClfrStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that needs to be supported."

OBJECT diffServClfrElementNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object not needed when diffServClfrelementTable is implemented read-only"

OBJECT diffServClfrElementPrecedence
MIN-ACCESS read-only
DESCRIPTION

"Write access is not required."

OBJECT diffServClfrElementNext
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServClfrElementSpecific
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServClfrElementStorage
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServClfrElementStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that
needs to be supported."

OBJECT diffServMultiFieldClfrNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServMultiFieldClfrTable is
implemented in read-only mode."

OBJECT diffServMultiFieldClfrAddrType
SYNTAX InetAddressType { unknown(0), ipv4(1), ipv6(2) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required. An implementation is only required
to support IPv4 and IPv6 addresses."

OBJECT diffServMultiFieldClfrDstAddr
SYNTAX InetAddress (SIZE(0|4|16))
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required. An implementation is only required
to support IPv4 and globally unique IPv6 addresses."

OBJECT diffServMultiFieldClfrDstPrefixLength
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrSrcAddr
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required. An implementation is only required
to support IPv4 and globally unique IPv6 addresses."

OBJECT diffServMultiFieldClfrSrcPrefixLength
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrDscp
MIN-ACCESS read-only
DESCRIPTION

"Write access is not required."

OBJECT diffServMultiFieldClfrFlowId
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrProtocol
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrDstL4PortMin
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrDstL4PortMax
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrSrcL4PortMin
MIN-ACCESS
read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrSrcL4PortMax
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrStorage
MIN-ACCESS read-only

DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, createAndWait and notInService
support is not required."

OBJECT diffServMeterNextFree

MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServMultiFieldClfrTable is
implemented in read-only mode."

OBJECT diffServMeterSucceedNext
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMeterFailNext
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMeterSpecific
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMeterStorage
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMeterStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that
needs to be supported."

OBJECT diffServTBParamNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServTBParamTable is implemented in
read-only mode."

OBJECT diffServTBParamType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServTBParamRate
MIN-ACCESS read-only

DESCRIPTION
"Write access is not required."

OBJECT diffServTBParamBurstSize
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT
diffServTBParamInterval
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServTBParamStorage
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServTBParamStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that
needs to be supported."

OBJECT diffServActionNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServActionTable is implemented in
read-only mode."

OBJECT diffServActionInterface
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServActionNext
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServActionSpecific
MIN-ACCESS read-only
DESCRIPTION

"Write access
is not required."

OBJECT diffServActionStorage
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServActionStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that
needs to be supported."

OBJECT diffServCountActNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServCountActTable is implemented
in read-only mode."

OBJECT diffServCountActStorage
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServCountActStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that
needs to be supported."

OBJECT diffServAlgDropNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServAlgDropTable is implemented in
read-only mode."

OBJECT diffServAlgDropType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServAlgDropNext
MIN-ACCESS read-only

```
    DESCRIPTION
      "Write access is not required."

    OBJECT      diffServAlgDropQMeasure
    MIN-ACCESS  read-only
    DESCRIPTION
      "Write access is not required."

    OBJECT      diffServAlgDropQThreshold
    MIN-ACCESS  read-only
    DESCRIPTION
      "Write access is not required."

    OBJECT      diffServAlgDropSpecific
    MIN-ACCESS  read-only
    DESCRIPTION
      "Write access is not required."

    OBJECT      diffServAlgDropStorage
    MIN-ACCESS  read-only
    DESCRIPTION
      "Write access is not required."

    OBJECT      diffServAlgDropStatus
    SYNTAX      RowStatus { active(1) }
    MIN-ACCESS  read-only
    DESCRIPTION
      "Write access is not required,
    and active is the only status that
      needs to be supported."

    OBJECT      diffServRandomDropNextFree
    MIN-ACCESS  not-accessible
    DESCRIPTION
      "Object is not needed when diffServRandomDropTable is implemented
      in read-only mode."

    OBJECT      diffServRandomDropMinThreshBytes
    MIN-ACCESS  read-only
    DESCRIPTION
      "Write access is not required."

    OBJECT      diffServRandomDropMinThreshPkts
    MIN-ACCESS  read-only
    DESCRIPTION
      "Write access is not required."
```

OBJECT diffServRandomDropMaxThreshBytes
MIN-ACCESS read-only

DESCRIPTION
"Write access is not required."

OBJECT diffServRandomDropMaxThreshPkts
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServRandomDropProbMax
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServRandomDropWeight
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServRandomDropSamplingRate
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServRandomDropStorage
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServRandomDropStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that
needs to be supported."

OBJECT diffServQNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServQTable is implemented in
read-only mode."

OBJECT diffServQNext
MIN-ACCESS read-only

DESCRIPTION
"Write access is not required."

OBJECT diffServQMinRate
MIN-ACCESS read-only

DESCRIPTION
"Write access is not required."

OBJECT diffServQMaxRate
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServQStorage
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServQStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that
needs to be supported."

OBJECT diffServSchedulerNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServSchedulerTable is implemented
in read-only mode."

OBJECT diffServSchedulerNext
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServSchedulerMethod
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServSchedulerMinRate
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServSchedulerMaxRate
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServSchedulerStorage
MIN-ACCESS read-only

DESCRIPTION
"Write access is not required."

OBJECT diffServSchedulerStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that
needs to be supported."

OBJECT diffServMinRateNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServMinRateTable is implemented in
read-only mode."

OBJECT diffServMinRatePriority
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMinRateAbsolute
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMinRateRelative
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMinRateStorage
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMinRateStatus

```
  SYNTAX      RowStatus { active(1) }
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access is not required, and active is the only status that
    needs to be supported."

  OBJECT      diffServMaxRateNextFree
  MIN-ACCESS  not-accessible
  DESCRIPTION
    "Object is not needed when diffServMaxrateTable is implemented in
    read-only mode."



  OBJECT      diffServMaxRateAbsolute
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access is not required."

  OBJECT      diffServMaxRateRelative
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access is not required."

  OBJECT      diffServMaxRateThreshold
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access is not required."

  OBJECT      diffServMaxRateStorage
  MIN-ACCESS  read-only
  DESCRIPTION
     "Write access is not required."

  OBJECT      diffServMaxRateStatus
  SYNTAX      RowStatus { active(1) }
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access is not required, and active is the only status that
    needs to be supported."

  ::= { diffServMIBCompliances 2 }

diffServMIBDataPathGroup OBJECT-GROUP
  OBJECTS {
          diffServDataPathStart, diffServDataPathStorage,
          diffServDataPathStatus
  }
```

```
  STATUS       current
  DESCRIPTION
    "The Data Path Group defines the MIB Objects that describe a
    functional data path."
  ::= { diffServMIBGroups 1 }

diffServMIBClfrGroup OBJECT-GROUP
  OBJECTS {
          diffServClfrNextFree, diffServClfrStorage,
          diffServClfrStatus
  }
  STATUS       current
  DESCRIPTION
    "The Classifier Group defines the MIB Objects that describe the




    list the starts of individual classifiers."
  ::= { diffServMIBGroups 2 }

diffServMIBClfrElementGroup
 OBJECT-GROUP
  OBJECTS {
          diffServClfrElementNextFree,
          diffServClfrElementPrecedence, diffServClfrElementNext,
          diffServClfrElementSpecific, diffServClfrElementStorage,
          diffServClfrElementStatus
  }
  STATUS       current
  DESCRIPTION
    "The Classifier Element Group defines the MIB Objects that
    describe the classifier elements that make up a generic
    classifier."
  ::= { diffServMIBGroups 3 }

diffServMIBMultiFieldClfrGroup OBJECT-GROUP
  OBJECTS {
          diffServMultiFieldClfrNextFree,
          diffServMultiFieldClfrAddrType,
          diffServMultiFieldClfrDstAddr,
          diffServMultiFieldClfrDstPrefixLength,
          diffServMultiFieldClfrFlowId,
          diffServMultiFieldClfrSrcAddr,
          diffServMultiFieldClfrSrcPrefixLength,
          diffServMultiFieldClfrDscp,
          diffServMultiFieldClfrProtocol,
          diffServMultiFieldClfrDstL4PortMin,
```

```
            diffServMultiFieldClfrDstL4PortMax,
            diffServMultiFieldClfrSrcL4PortMin,
            diffServMultiFieldClfrSrcL4PortMax,
            diffServMultiFieldClfrStorage,
            diffServMultiFieldClfrStatus
    }
    STATUS       current
    DESCRIPTION
      "The Multi-field Classifier Group defines the MIB Objects that
      describe a classifier element for matching on various fields of
      an IP and upper-layer protocol header."
    ::= { diffServMIBGroups 4 }

diffServMIBMeterGroup OBJECT-GROUP
    OBJECTS {
            diffServMeterNextFree, diffServMeterSucceedNext,
            diffServMeterFailNext, diffServMeterSpecific,
            diffServMeterStorage, diffServMeterStatus
    }



    STATUS       current
    DESCRIPTION
      "The Meter Group defines the objects used in describing a generic
      meter element."
    ::= { diffServMIBGroups 5 }

diffServMIBTBParamGroup OBJECT-GROUP
    OBJECTS {
            diffServTBParamNextFree,
 diffServTBParamType,
            diffServTBParamRate, diffServTBParamBurstSize,
            diffServTBParamInterval, diffServTBParamStorage,
            diffServTBParamStatus
    }
    STATUS       current
    DESCRIPTION
      "The Token-Bucket Meter Group defines the objects used in
      describing a token bucket meter element."
    ::= { diffServMIBGroups 6 }

diffServMIBActionGroup OBJECT-GROUP
    OBJECTS {
            diffServActionNextFree, diffServActionNext,
            diffServActionSpecific, diffServActionStorage,
            diffServActionInterface, diffServActionStatus
    }
```

```
  STATUS       current
  DESCRIPTION
    "The Action Group defines the objects used in describing a
    generic action element."
  ::= { diffServMIBGroups 7 }

diffServMIBDscpMarkActGroup OBJECT-GROUP
  OBJECTS {
          diffServDscpMarkActDscp
  }
  STATUS       current
  DESCRIPTION
    "The DSCP Mark Action Group defines the objects used in
     describing a DSCP Marking Action element."
  ::= { diffServMIBGroups 8 }

diffServMIBCounterGroup OBJECT-GROUP
  OBJECTS {
          diffServCountActOctets, diffServCountActPkts,
          diffServAlgDropOctets, diffServAlgDropPkts,
          diffServAlgRandomDropOctets, diffServAlgRandomDropPkts,
          diffServCountActStorage, diffServCountActStatus,
          diffServCountActNextFree




  }
  STATUS       current
  DESCRIPTION
    "A collection of objects providing information specific to
    packet-oriented network interfaces."
  ::= { diffServMIBGroups 9 }

diffServMIBAlgDropGroup OBJECT-GROUP
  OBJECTS {
          diffServAlgDropNextFree, diffServAlgDropType,
          diffServAlgDropNext, diffServAlgDropQMeasure,
          diffServAlgDropQThreshold, diffServAlgDropSpecific,
          diffServAlgDropStorage, diffServAlgDropStatus
  }
  STATUS       current
  DESCRIPTION
    "The Algorithmic Drop Group contains
 the objects that describe
    algorithmic dropper operation and configuration."
  ::= { diffServMIBGroups 10 }

diffServMIBRandomDropGroup OBJECT-GROUP
```

```
  OBJECTS {
          diffServRandomDropNextFree,
          diffServRandomDropMinThreshBytes,
          diffServRandomDropMinThreshPkts,
          diffServRandomDropMaxThreshBytes,
          diffServRandomDropMaxThreshPkts,
          diffServRandomDropProbMax,
          diffServRandomDropWeight,
          diffServRandomDropSamplingRate,
          diffServRandomDropStorage,
          diffServRandomDropStatus
  }
  STATUS      current
  DESCRIPTION
    "The Random Drop Group augments the Algorithmic Drop Group for
    random dropper operation and configuration."
  ::= { diffServMIBGroups 11 }

diffServMIBQGroup OBJECT-GROUP

  OBJECTS {
          diffServQNextFree, diffServQNext, diffServQMinRate,
          diffServQMaxRate, diffServQStorage, diffServQStatus

  }
  STATUS      current
  DESCRIPTION
    "The Queue Group contains the objects that describe an




    interface's queues."
  ::= { diffServMIBGroups 12 }

diffServMIBSchedulerGroup OBJECT-GROUP
  OBJECTS {
          diffServSchedulerNextFree, diffServSchedulerNext,
          diffServSchedulerMethod, diffServSchedulerMinRate,
          diffServSchedulerMaxRate, diffServSchedulerStorage,
          diffServSchedulerStatus
  }
  STATUS      current
  DESCRIPTION
    "The Scheduler Group contains the objects that describe packet
    schedulers on interfaces."
  ::= { diffServMIBGroups 13 }

diffServMIBMinRateGroup OBJECT-GROUP
```

```
  OBJECTS {
          diffServMinRateNextFree, diffServMinRatePriority,
          diffServMinRateAbsolute, diffServMinRateRelative,
          diffServMinRateStorage, diffServMinRateStatus
  }
  STATUS       current
  DESCRIPTION
    "The Minimum Rate Parameter Group contains the objects that

  describe packet schedulers' minimum rate or priority guarantees."
  ::= { diffServMIBGroups 14 }

diffServMIBMaxRateGroup OBJECT-GROUP
  OBJECTS {
          diffServMaxRateNextFree, diffServMaxRateAbsolute,
          diffServMaxRateRelative, diffServMaxRateThreshold,
          diffServMaxRateStorage, diffServMaxRateStatus
  }
  STATUS       current
  DESCRIPTION
    "The Maximum Rate Parameter Group contains the objects that
    describe packet schedulers' maximum rate guarantees."
  ::= { diffServMIBGroups 15 }

END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/DIFFSERV-MIB
No license file was found, but licenses were detected in source scan.

RADIUS-ACC-CLIENT-MIB DEFINITIONS ::= BEGIN

IMPORTS
    MODULE-IDENTITY, OBJECT-TYPE, OBJECT-IDENTITY,
    Counter32, Integer32, Gauge32,
    IpAddress, TimeTicks, mib-2      FROM SNMPv2-SMI
    SnmpAdminString                  FROM SNMP-FRAMEWORK-MIB
    InetAddressType, InetAddress,
    InetPortNumber                   FROM INET-ADDRESS-MIB
    MODULE-COMPLIANCE, OBJECT-GROUP  FROM SNMPv2-CONF;



radiusAccClientMIB MODULE-IDENTITY
    LAST-UPDATED "200608210000Z" -- 21 August 2006
    ORGANIZATION "IETF RADIUS Extensions Working Group."
    CONTACT-INFO
          " Bernard Aboba
            Microsoft
```

```
            One Microsoft Way



            Redmond, WA  98052
            US
            Phone: +1 425 936 6605
            EMail: bernarda@microsoft.com"
        DESCRIPTION
            "The MIB module for entities implementing the client
            side of the Remote
    Authentication Dial-In User Service
            (RADIUS) accounting protocol.  Copyright (C) The
            Internet Society (2006).  This version of this MIB
            module is part of RFC 4670; see the RFC itself for
            full legal notices."
        REVISION "200608210000Z"  -- 21 August 2006
        DESCRIPTION
            "Revised version as published in RFC 4670.
            This version obsoletes that of RFC 2620 by
            deprecating the MIB table containing IPv4-only
            address formats and defining a new table to add support
            for version-neutral IP address formats.  The remaining
            MIB objects from RFC 2620 are carried forward into this
            version."
        REVISION "199906110000Z"  -- 11 Jun 1999
        DESCRIPTION "Initial version as published in RFC 2620."
        ::= { radiusAccounting 2 }

    radiusMIB OBJECT-IDENTITY
        STATUS  current
        DESCRIPTION
            "The OID assigned to RADIUS MIB work by the IANA."
         ::= { mib-2 67 }

    radiusAccounting  OBJECT IDENTIFIER ::= {radiusMIB 2}

    radiusAccClientMIBObjects     OBJECT IDENTIFIER
        ::= { radiusAccClientMIB 1 }

    radiusAccClient  OBJECT IDENTIFIER
        ::= { radiusAccClientMIBObjects 1 }

    radiusAccClientInvalidServerAddresses OBJECT-TYPE
        SYNTAX Counter32
        UNITS "packets"
        MAX-ACCESS read-only
        STATUS current
```

```
    DESCRIPTION
        "The number of RADIUS Accounting-Response packets
         received from unknown addresses."
    ::= { radiusAccClient 1 }



radiusAccClientIdentifier OBJECT-TYPE
    SYNTAX SnmpAdminString
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The NAS-Identifier of the RADIUS accounting client.
         This is not necessarily the same as sysName in MIB
         II."
    REFERENCE "RFC 2865 section 5.32"
    ::= { radiusAccClient 2 }

radiusAccServerTable OBJECT-TYPE
    SYNTAX SEQUENCE OF RadiusAccServerEntry
    MAX-ACCESS not-accessible
     STATUS     deprecated
    DESCRIPTION
        "The (conceptual) table listing the RADIUS accounting
         servers with which the client shares a secret."
    ::= { radiusAccClient 3 }

radiusAccServerEntry OBJECT-TYPE
    SYNTAX     RadiusAccServerEntry
    MAX-ACCESS not-accessible
    STATUS     deprecated
    DESCRIPTION
        "An entry (conceptual row) representing a RADIUS
         accounting server with which the client shares a
         secret."
    INDEX      { radiusAccServerIndex }
    ::= { radiusAccServerTable 1 }

RadiusAccServerEntry ::= SEQUENCE {
    radiusAccServerIndex                    Integer32,
    radiusAccServerAddress                  IpAddress,
    radiusAccClientServerPortNumber             Integer32,
    radiusAccClientRoundTripTime                TimeTicks,
    radiusAccClientRequests                 Counter32,
    radiusAccClientRetransmissions
  Counter32,
    radiusAccClientResponses                 Counter32,
```

```
    radiusAccClientMalformedResponses            Counter32,
    radiusAccClientBadAuthenticators             Counter32,
    radiusAccClientPendingRequests               Gauge32,
    radiusAccClientTimeouts                      Counter32,
    radiusAccClientUnknownTypes                  Counter32,
    radiusAccClientPacketsDropped                Counter32
}




radiusAccServerIndex OBJECT-TYPE
    SYNTAX     Integer32 (1..2147483647)
    MAX-ACCESS not-accessible
    STATUS     deprecated
    DESCRIPTION
        "A number uniquely identifying each RADIUS
         Accounting server with which this client
         communicates."
    ::= { radiusAccServerEntry 1 }

radiusAccServerAddress OBJECT-TYPE
    SYNTAX     IpAddress
    MAX-ACCESS read-only
    STATUS     deprecated
    DESCRIPTION
        "The IP address of the RADIUS accounting server

    referred to in this table entry."
    ::= { radiusAccServerEntry 2 }

radiusAccClientServerPortNumber  OBJECT-TYPE
    SYNTAX Integer32 (0..65535)
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The UDP port the client is using to send requests to
         this server."
    REFERENCE "RFC 2866 section 3"
    ::= { radiusAccServerEntry 3 }

radiusAccClientRoundTripTime  OBJECT-TYPE
    SYNTAX TimeTicks
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
         "The time interval between the most recent
```

```
            Accounting-Response and the Accounting-Request that
            matched it from this RADIUS accounting server."
        REFERENCE "RFC 2866 section 2"
        ::= { radiusAccServerEntry 4 }

-- Request/Response statistics
--
-- Requests = Responses + PendingRequests + ClientTimeouts
--
-- Responses - MalformedResponses - BadAuthenticators -
-- UnknownTypes - PacketsDropped = Successfully received




radiusAccClientRequests
 OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
          "The number of RADIUS Accounting-Request packets
           sent.  This does not include retransmissions."
    REFERENCE "RFC 2866 section 4.1"
    ::= { radiusAccServerEntry 5 }

radiusAccClientRetransmissions OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
          "The number of RADIUS Accounting-Request packets
           retransmitted to this RADIUS accounting server.
           Retransmissions include retries where the
           Identifier and Acct-Delay have been updated, as
           well as those in which they remain the same."
    REFERENCE "RFC 2866 section 2"
    ::= { radiusAccServerEntry 6 }

radiusAccClientResponses OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS deprecated
```

```
     DESCRIPTION
         "The number of RADIUS packets received on the
          accounting port from this server."
     REFERENCE "RFC 2866 section 4.2"
     ::= { radiusAccServerEntry 7 }

radiusAccClientMalformedResponses OBJECT-TYPE
     SYNTAX Counter32
     UNITS "packets"
     MAX-ACCESS read-only
     STATUS deprecated
     DESCRIPTION
         "The number of malformed RADIUS Accounting-Response
          packets received from this server.  Malformed packets
          include packets with an invalid length.  Bad
          authenticators and unknown types are not included as
          malformed accounting responses."
     REFERENCE "RFC 2866 section 3"



     ::= { radiusAccServerEntry 8 }

radiusAccClientBadAuthenticators OBJECT-TYPE
     SYNTAX Counter32
     UNITS "packets"
     MAX-ACCESS read-only
     STATUS deprecated
     DESCRIPTION
         "The number of RADIUS Accounting-Response
          packets that contained invalid
 authenticators
          received from this server."
     REFERENCE "RFC 2866 section 3"
     ::= { radiusAccServerEntry 9 }

radiusAccClientPendingRequests OBJECT-TYPE
     SYNTAX Gauge32
     UNITS "packets"
     MAX-ACCESS read-only
     STATUS deprecated
     DESCRIPTION
         "The number of RADIUS Accounting-Request packets
          sent to this server that have not yet timed out or
          received a response.  This variable is incremented
          when an Accounting-Request is sent and decremented
          due to receipt of an Accounting-Response, a timeout,
          or a retransmission."
```

```
    REFERENCE "RFC 2866 section 2"
    ::= { radiusAccServerEntry 10 }

radiusAccClientTimeouts OBJECT-TYPE
   SYNTAX Counter32
   UNITS "timeouts"
   MAX-ACCESS read-only
   STATUS deprecated
   DESCRIPTION
       "The number of accounting timeouts to this server.
        After a timeout, the client may retry to the same

  server, send to a different server, or give up.
        A retry to the same server is counted as a
        retransmit as well as a timeout.  A send to a different
        server is counted as an Accounting-Request as well as
        a timeout."
    REFERENCE "RFC 2866 section 2"
    ::= { radiusAccServerEntry  11 }

radiusAccClientUnknownTypes OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"



    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
         "The number of RADIUS packets of unknown type that
          were received from this server on the accounting port."
    REFERENCE "RFC 2866 section 4"
    ::= { radiusAccServerEntry  12 }

radiusAccClientPacketsDropped OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
         "The number of RADIUS packets that were received from
          this server on the accounting port and dropped for some

     other reason."
    ::= { radiusAccServerEntry  13 }


-- New MIB objects added in this revision
```

```
radiusAccServerExtTable OBJECT-TYPE
    SYNTAX SEQUENCE OF RadiusAccServerExtEntry
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
        "The (conceptual) table listing the RADIUS accounting
         servers with which the client shares a secret."
    ::= { radiusAccClient 4 }

radiusAccServerExtEntry OBJECT-TYPE
    SYNTAX     RadiusAccServerExtEntry
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
        "An entry (conceptual row) representing a RADIUS
         accounting server with which the client shares a
         secret."
    INDEX      { radiusAccServerExtIndex }
    ::= { radiusAccServerExtTable 1 }

RadiusAccServerExtEntry ::= SEQUENCE {
    radiusAccServerExtIndex                 Integer32,
    radiusAccServerInetAddressType          InetAddressType,
    radiusAccServerInetAddress
            InetAddress,
    radiusAccClientServerInetPortNumber     InetPortNumber,
    radiusAccClientExtRoundTripTime         TimeTicks,



    radiusAccClientExtRequests              Counter32,
    radiusAccClientExtRetransmissions       Counter32,
    radiusAccClientExtResponses             Counter32,
    radiusAccClientExtMalformedResponses    Counter32,
    radiusAccClientExtBadAuthenticators     Counter32,
    radiusAccClientExtPendingRequests       Gauge32,
    radiusAccClientExtTimeouts              Counter32,
    radiusAccClientExtUnknownTypes          Counter32,
    radiusAccClientExtPacketsDropped        Counter32,
    radiusAccClientCounterDiscontinuity     TimeTicks
}

radiusAccServerExtIndex OBJECT-TYPE
    SYNTAX     Integer32 (1..2147483647)
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
```

```
        "A number uniquely identifying each RADIUS
         Accounting server
 with which this client
         communicates."
    ::= { radiusAccServerExtEntry 1 }


radiusAccServerInetAddressType OBJECT-TYPE
       SYNTAX     InetAddressType
       MAX-ACCESS read-only
       STATUS     current
       DESCRIPTION
            "The type of address format used for the
             radiusAccServerInetAddress object."
       ::= { radiusAccServerExtEntry 2 }


 radiusAccServerInetAddress OBJECT-TYPE
       SYNTAX     InetAddress
       MAX-ACCESS read-only
       STATUS     current
       DESCRIPTION
            "The IP address of the RADIUS accounting
             server referred to in this table entry, using
             the version-neutral IP address format."
       ::= { radiusAccServerExtEntry 3 }

 radiusAccClientServerInetPortNumber  OBJECT-TYPE
       SYNTAX InetPortNumber ( 1..65535 )
       MAX-ACCESS read-only
       STATUS current
       DESCRIPTION



            "The UDP port the client is using
 to send requests
             to this accounting server.  The value zero (0) is
             invalid."
       REFERENCE "RFC 2866 section 3"
       ::= { radiusAccServerExtEntry 4 }


radiusAccClientExtRoundTripTime  OBJECT-TYPE
    SYNTAX TimeTicks
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
```

```
            "The time interval between the most recent
            Accounting-Response and the Accounting-Request that
            matched it from this RADIUS accounting server."
        REFERENCE "RFC 2866 section 2"
        ::= { radiusAccServerExtEntry 5 }

-- Request/Response statistics
--
-- Requests = Responses + PendingRequests + ClientTimeouts
--
-- Responses - MalformedResponses - BadAuthenticators -
-- UnknownTypes - PacketsDropped = Successfully received

radiusAccClientExtRequests OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Accounting-Request
 packets
            sent.  This does not include retransmissions.
            This counter may experience a discontinuity when the
            RADIUS Accounting Client module within the managed
            entity is reinitialized, as indicated by the current
            value of radiusAccClientCounterDiscontinuity."
    REFERENCE "RFC 2866 section 4.1"
    ::= { radiusAccServerExtEntry 6 }

radiusAccClientExtRetransmissions OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Accounting-Request packets
            retransmitted to this RADIUS accounting server.



            Retransmissions include retries where the
            Identifier and Acct-Delay have been updated, as
            well as those in which they remain the same.
            This counter may experience a discontinuity when the
            RADIUS Accounting Client module within the managed

   entity is reinitialized, as indicated by the current
            value of radiusAccClientCounterDiscontinuity."
```

```
    REFERENCE "RFC 2866 section 2"
    ::= { radiusAccServerExtEntry 7 }

radiusAccClientExtResponses OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS packets received on the
         accounting port from this server.  This counter
         may experience a discontinuity when the RADIUS
         Accounting Client module within the managed entity is
         reinitialized, as indicated by the current value of
         radiusAccClientCounterDiscontinuity."
    REFERENCE "RFC 2866 section 4.2"
    ::= { radiusAccServerExtEntry 8 }

radiusAccClientExtMalformedResponses OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of malformed RADIUS Accounting-Response
         packets received from this server.  Malformed packets
         include packets with an invalid length.  Bad
         authenticators and unknown types are not included as
         malformed accounting responses.  This counter may
         experience a discontinuity when the RADIUS Accounting
         Client module within the managed entity is
         reinitialized, as indicated by the current
         value of radiusAccClientCounterDiscontinuity."
    REFERENCE "RFC 2866 section 3"
    ::= { radiusAccServerExtEntry 9 }

radiusAccClientExtBadAuthenticators OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current



    DESCRIPTION
        "The number of RADIUS Accounting-Response
         packets that contained invalid authenticators
         received from this server.  This counter may
```

```
            experience a discontinuity when the RADIUS
            Accounting Client
 module within the managed
            entity is reinitialized, as indicated by the
            current value of
            radiusAccClientCounterDiscontinuity."
    REFERENCE "RFC 2866 section 3"
    ::= { radiusAccServerExtEntry 10 }

radiusAccClientExtPendingRequests OBJECT-TYPE
    SYNTAX Gauge32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Accounting-Request packets
         sent to this server that have not yet timed out or
         received a response.  This variable is incremented
         when an Accounting-Request is sent and decremented
         due to receipt of an Accounting-Response, a timeout,
         or a retransmission.  This counter may experience a
         discontinuity when the RADIUS Accounting Client module
         within the managed entity is reinitialized, as
         indicated by the current value of
         radiusAccClientCounterDiscontinuity."
     REFERENCE "RFC 2866 section 2"
    ::= { radiusAccServerExtEntry 11 }

radiusAccClientExtTimeouts OBJECT-TYPE
   SYNTAX Counter32
   UNITS "timeouts"
   MAX-ACCESS read-only
   STATUS current
   DESCRIPTION
       "The number of accounting timeouts to this server.
        After a timeout, the client may retry to the same
        server, send to a different server, or give up.
        A retry to the same server is counted as a
        retransmit as well as a timeout.  A send to a different
        server is counted as an Accounting-Request as well as
        a timeout.  This counter may experience a discontinuity
        when the RADIUS Accounting Client module within the
        managed entity is reinitialized, as indicated by the
        current value of radiusAccClientCounterDiscontinuity."
    REFERENCE "RFC 2866 section 2"
```

```
    ::= { radiusAccServerExtEntry  12 }

radiusAccClientExtUnknownTypes OBJECT-TYPE
    SYNTAX
 Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS packets of unknown type that
         were received from this server on the accounting port.
         This counter may experience a discontinuity when the
         RADIUS Accounting Client module within the managed
         entity is reinitialized, as indicated by the current
         value of radiusAccClientCounterDiscontinuity."
    REFERENCE "RFC 2866 section 4"
    ::= { radiusAccServerExtEntry  13 }

radiusAccClientExtPacketsDropped OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS packets that were received from
         this server on the accounting port and dropped for some
         other reason.  This counter may experience a
         discontinuity when the RADIUS Accounting Client module
         within
 the managed entity is reinitialized, as indicated
         by the current value of
         radiusAccClientCounterDiscontinuity."
    ::= { radiusAccServerExtEntry  14 }

radiusAccClientCounterDiscontinuity OBJECT-TYPE
      SYNTAX TimeTicks
      UNITS "centiseconds"
      MAX-ACCESS read-only
      STATUS current
      DESCRIPTION
          "The number of centiseconds since the last
           discontinuity in the RADIUS Accounting Client
           counters.  A discontinuity may be the result of a
           reinitialization of the RADIUS Accounting Client
           module within the managed entity."
      ::= { radiusAccServerExtEntry 15 }
```

```
-- conformance information

radiusAccClientMIBConformance  OBJECT IDENTIFIER
    ::= { radiusAccClientMIB 2 }

radiusAccClientMIBCompliances  OBJECT IDENTIFIER
    ::= { radiusAccClientMIBConformance 1 }

radiusAccClientMIBGroups  OBJECT IDENTIFIER
    ::= { radiusAccClientMIBConformance
 2 }


-- units of conformance

radiusAccClientMIBCompliance MODULE-COMPLIANCE
   STATUS  deprecated
   DESCRIPTION
        "The compliance statement for accounting clients
         implementing the RADIUS Accounting Client MIB.
         Implementation of this module is for IPv4-only
         entities, or for backwards compatibility use with
         entities that support both IPv4 and IPv6."
   MODULE  -- this module
      MANDATORY-GROUPS { radiusAccClientMIBGroup }

   ::= { radiusAccClientMIBCompliances 1 }


radiusAccClientExtMIBCompliance MODULE-COMPLIANCE
   STATUS  current
   DESCRIPTION
        "The compliance statement for accounting
         clients implementing the RADIUS Accounting
         Client IPv6 Extensions MIB.  Implementation of
         this module is for entities that support IPv6,
         or support IPv4 and IPv6."
   MODULE  -- this module
      MANDATORY-GROUPS { radiusAccClientExtMIBGroup }

   OBJECT
 radiusAccServerInetAddressType
   SYNTAX InetAddressType { ipv4(1), ipv6(2) }
```

```
    DESCRIPTION
        "An implementation is only required to support
         IPv4 and globally unique IPv6 addresses."

    OBJECT radiusAccServerInetAddress
    SYNTAX InetAddress ( SIZE (4|16) )
    DESCRIPTION



        "An implementation is only required to support
         IPv4 and globally unique IPv6 addresses."

    ::= { radiusAccClientMIBCompliances 2 }


-- units of conformance

radiusAccClientMIBGroup OBJECT-GROUP
    OBJECTS { radiusAccClientIdentifier,
              radiusAccClientInvalidServerAddresses,
              radiusAccServerAddress,
              radiusAccClientServerPortNumber,
              radiusAccClientRoundTripTime,
              radiusAccClientRequests,
              radiusAccClientRetransmissions,
              radiusAccClientResponses,
              radiusAccClientMalformedResponses,
              radiusAccClientBadAuthenticators,

          radiusAccClientPendingRequests,
              radiusAccClientTimeouts,
              radiusAccClientUnknownTypes,
              radiusAccClientPacketsDropped
        }
    STATUS  deprecated
    DESCRIPTION
        "The basic collection of objects providing management of
         RADIUS Accounting Clients."
    ::= { radiusAccClientMIBGroups 1 }


radiusAccClientExtMIBGroup OBJECT-GROUP
    OBJECTS { radiusAccClientIdentifier,
              radiusAccClientInvalidServerAddresses,
              radiusAccServerInetAddressType,
              radiusAccServerInetAddress,
              radiusAccClientServerInetPortNumber,
```

```
            radiusAccClientExtRoundTripTime,
            radiusAccClientExtRequests,
            radiusAccClientExtRetransmissions,
            radiusAccClientExtResponses,
            radiusAccClientExtMalformedResponses,
            radiusAccClientExtBadAuthenticators,
            radiusAccClientExtPendingRequests,

    radiusAccClientExtTimeouts,
            radiusAccClientExtUnknownTypes,
            radiusAccClientExtPacketsDropped,
            radiusAccClientCounterDiscontinuity



        }
    STATUS  current
    DESCRIPTION
        "The basic collection of objects providing management of
         RADIUS Accounting Clients."
    ::= { radiusAccClientMIBGroups 2 }


END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/RADIUS-ACC-CLIENT-MIB
No license file was found, but licenses were detected in source scan.

MIOX25-MIB DEFINITIONS  ::= BEGIN

IMPORTS
      Counter,
      TimeTicks
            FROM RFC1155-SMI
      OBJECT-TYPE
            FROM RFC-1212
      DisplayString, transmission,
      ifIndex
            FROM RFC1213-MIB
      InstancePointer
            FROM RFC1316-MIB
      X121Address
            FROM RFC1382-MIB
      PositiveInteger
            FROM RFC1381-MIB;

            -- IP over X.25 MIB
```

```
miox    OBJECT IDENTIFIER ::= { transmission 38 }

mioxPle         OBJECT IDENTIFIER ::= { miox 1 }
mioxPeer        OBJECT IDENTIFIER ::= { miox 2 }

-- ###########################################################
--              Ple Table
-- ###########################################################

-- Systems that implement RFC 1356 must also implement
-- all objects in this group.

mioxPleTable    OBJECT-TYPE
      SYNTAX  SEQUENCE OF MioxPleEntry
      ACCESS  not-accessible
       STATUS  mandatory
      DESCRIPTION
            "This table contains information relative to
            an interface to an X.25 Packet Level Entity
            (PLE)."
      ::= { mioxPle 1   }

mioxPleEntry    OBJECT-TYPE
      SYNTAX  MioxPleEntry
      ACCESS  not-accessible
      STATUS  mandatory
      DESCRIPTION
            "These objects manage the encapsulation of
            other protocols within X.25."
      INDEX { ifIndex }
      ::= { mioxPleTable 1 }

MioxPleEntry ::= SEQUENCE {
      mioxPleMaxCircuits
            INTEGER,
      mioxPleRefusedConnections
            Counter,
      mioxPleEnAddrToX121LkupFlrs
            Counter,
      mioxPleLastFailedEnAddr
            OCTET STRING,
      mioxPleEnAddrToX121LkupFlrTime
            TimeTicks,
      mioxPleX121ToEnAddrLkupFlrs
            Counter,
      mioxPleLastFailedX121Address
            X121Address,
```

```
    mioxPleX121ToEnAddrLkupFlrTime
            TimeTicks,
    mioxPleQbitFailures
            Counter,
    mioxPleQbitFailureRemoteAddress
            X121Address,
    mioxPleQbitFailureTime
            TimeTicks,
    mioxPleMinimumOpenTimer
            PositiveInteger,
    mioxPleInactivityTimer
            PositiveInteger,
    mioxPleHoldDownTimer
            PositiveInteger,
    mioxPleCollisionRetryTimer
            PositiveInteger,
    mioxPleDefaultPeerId
            InstancePointer
    }

mioxPleMaxCircuits OBJECT-TYPE
    SYNTAX  INTEGER (0..2147483647)
    ACCESS  read-write
    STATUS  mandatory
    DESCRIPTION
            "The maximum number of X.25 circuits that
            can be open at one time for this interface.
            A value of zero indicates the interface will
            not allow any additional circuits (as it may
            soon be shutdown).  A value of 2147483647
             allows an unlimited number of circuits."
    ::= { mioxPleEntry 1 }

mioxPleRefusedConnections OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
            "The number of X.25 calls from a remote
            systems to this system that were cleared by
            this system.  The interface instance should
            identify the X.25 interface the call came in
            on."
    ::= { mioxPleEntry 2 }

mioxPleEnAddrToX121LkupFlrs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
```

```
        STATUS  mandatory
        DESCRIPTION
                "The number of times a translation from an
                Encapsulated Address to an X.121 address
                failed to find a corresponding X.121
                address.  Encapsulated addresses can be
                looked up in the mioxPeerTable or translated
                via an algorithm as for the DDN.  Addresses

                that are successfully recognized do not
                increment this counter.  Addresses that are
                not recognized (reflecting an abnormal
                packet delivery condition) increment this
                counter.

                If an address translation fails, it may be
                difficult to determine which PLE entry
                should count the failure.  In such cases the
                first likely entry in this table should be
                selected.  Agents should record the failure
                even if they are unsure which PLE should be
                associated with the failure."
        ::= { mioxPleEntry 3 }

    mioxPleLastFailedEnAddr OBJECT-TYPE
        SYNTAX  OCTET STRING (SIZE(2..128))
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
                "The last Encapsulated address that failed
                to find a corresponding X.121 address and
                caused mioxPleEnAddrToX121LkupFlrs
     to be
                incremented.  The first octet of this object
                contains the encapsulation type, the
                remaining octets contain the address of that
                type that failed.  Thus for an IP address,
                the length will be five octets, the first
                octet will contain 204 (hex CC), and the
                last four octets will contain the IP
                address.  For a snap encapsulation, the
                first byte would be 128 (hex 80) and the
                rest of the octet string would have the snap
                header."
        ::= { mioxPleEntry 4 }

    mioxPleEnAddrToX121LkupFlrTime OBJECT-TYPE
        SYNTAX  TimeTicks
```

```
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
            "The most recent value of sysUpTime when the
            translation from an Encapsulated Address to
            X.121 address failed to find a corresponding
            X.121 address."
        ::= { mioxPleEntry 5 }


mioxPleX121ToEnAddrLkupFlrs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
            "The number of times the translation from an
            X.121 address to an Encapsulated Address
            failed to find a corresponding Encapsulated
            Address.  Addresses successfully recognized
            by an algorithm do not increment this
            counter.  This counter reflects the number
            of times call acceptance encountered the
            abnormal condition of not recognizing the
            peer."
        ::= { mioxPleEntry 6 }

mioxPleLastFailedX121Address OBJECT-TYPE
        SYNTAX  X121Address
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
            "The last X.121 address that caused
            mioxPleX121ToEnAddrLkupFlrs to increase."
        ::= { mioxPleEntry 7 }

mioxPleX121ToEnAddrLkupFlrTime
 OBJECT-TYPE
        SYNTAX  TimeTicks
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
            "The most recent value of sysUpTime when the
            translation from an X.121 address to an
            Encapsulated Address failed to find a
            corresponding Encapsulated Address."
        ::= { mioxPleEntry 8 }

mioxPleQbitFailures OBJECT-TYPE
```

```
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
            "The number of times a connection was closed
            because of a Q-bit failure."
        ::= { mioxPleEntry 9 }

    mioxPleQbitFailureRemoteAddress OBJECT-TYPE
        SYNTAX  X121Address
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
            "The remote address of the most recent
            (last) connection that was closed because of
            a Q-bit failure."
        ::= { mioxPleEntry 10 }

    mioxPleQbitFailureTime OBJECT-TYPE

       SYNTAX  TimeTicks
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
            "The most recent value of sysUpTime when a
            connection was closed because of a Q-bit
            failure.  This will also be the last time
            that mioxPleQbitFailures was incremented."
        ::= { mioxPleEntry 11 }

    mioxPleMinimumOpenTimer OBJECT-TYPE
        SYNTAX  PositiveInteger
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
            "The minimum time in milliseconds this
            interface will keep a connection open before
            allowing it to be closed.  A value of zero
            indicates no timer."
        DEFVAL { 0 }
        ::= { mioxPleEntry 12 }

    mioxPleInactivityTimer OBJECT-TYPE
        SYNTAX  PositiveInteger
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
            "The amount of time time in milliseconds
```

```
            this interface will
 keep an idle connection
            open before closing it.  A value of
            2147483647 indicates no timer."
        DEFVAL { 10000 }
        ::= { mioxPleEntry 13 }

mioxPleHoldDownTimer    OBJECT-TYPE
        SYNTAX  PositiveInteger
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
            "The hold down timer in milliseconds.  This
            is the minimum amount of time to wait before
            trying another call to a host that was
            previously unsuccessful.  A value of
            2147483647 indicates the host will not be
            retried."
        DEFVAL { 0 }
        ::= { mioxPleEntry 14 }

mioxPleCollisionRetryTimer OBJECT-TYPE
        SYNTAX  PositiveInteger
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
            "The Collision Retry Timer in milliseconds.
            The time to delay between call attempts when
            the maximum number of circuits
 is exceeded
            in a call attempt."
        DEFVAL { 0 }
        ::= { mioxPleEntry 15 }


mioxPleDefaultPeerId OBJECT-TYPE
        SYNTAX  InstancePointer
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
            "This identifies the instance of the index
            in the mioxPeerTable for the default
            parameters to use with this interface.

            The entry identified by this object may have
            a zero length Encapsulation address and a
            zero length X.121 address.
```

```
            These default parameters are used with
            connections to hosts that do not have
            entries in the mioxPeerTable.  Such
            connections occur when using ddn-x25 IP-X.25
            address mapping or when accepting
            connections from other hosts not in the
            mioxPeerTable.

            The mioxPeerEncTable entry with the same

        index as the mioxPeerTable entry specifies
            the call encapsulation types this PLE will
            accept for peers not in the mioxPeerTable.
            If the mioxPeerEncTable doesn't contain any
            entries, this PLE will not accept calls from
            entries not in the mioxPeerTable."
        ::= { mioxPleEntry 16 }



-- ###############################################################
--              Peer Table
-- ###############################################################

-- Systems that implement RFC 1356 must also implement
-- all objects in this group.

mioxPeerTable OBJECT-TYPE
      SYNTAX  SEQUENCE OF MioxPeerEntry
      ACCESS  not-accessible
      STATUS  mandatory
      DESCRIPTION
            "This table contains information about the
            possible peers this machine may exchange
            packets with."
      ::= { mioxPeer 1 }

mioxPeerEntry OBJECT-TYPE
      SYNTAX  MioxPeerEntry

 ACCESS  not-accessible
      STATUS  mandatory
      DESCRIPTION
            "Per peer information."
      INDEX { mioxPeerIndex   }
      ::= { mioxPeerTable 1 }
```

```
MioxPeerEntry ::= SEQUENCE {
      mioxPeerIndex
            PositiveInteger,
      mioxPeerStatus
            INTEGER,
      mioxPeerMaxCircuits
            PositiveInteger,
      mioxPeerIfIndex
            PositiveInteger,
      mioxPeerConnectSeconds
            Counter,
      mioxPeerX25CallParamId
            InstancePointer,
      mioxPeerEnAddr
            OCTET STRING,
      mioxPeerX121Address
            X121Address,
      mioxPeerX25CircuitId
            InstancePointer,
      mioxPeerDescr
            DisplayString
      }

mioxPeerIndex   OBJECT-TYPE
      SYNTAX  PositiveInteger
      ACCESS  read-only
      STATUS  mandatory
      DESCRIPTION
            "An index value that distinguished one entry
            from another.
  This index is independent of
            any other index."
      ::= { mioxPeerEntry 1 }

-- Systems can claim conformance with this MIB without
-- implementing sets to mioxPeerStatus with a value of
-- clearCall or makeCall.
-- All other defined values must be accepted.
-- Implementors should realize that allowing these values
-- provides richer management, and implementations
-- are encouraged to accept these values.
mioxPeerStatus OBJECT-TYPE
      SYNTAX  INTEGER {
                  valid (1),
                  createRequest (2),
                  underCreation (3),
                  invalid (4),
                  clearCall (5),
```

makeCall (6)
}
ACCESS read-write
STATUS mandatory
DESCRIPTION
"This reports the status of a peer entry.
A value of valid indicates a normal entry
that is in use by the agent. A value of

underCreation indicates a newly created
entry which isn't yet in use because the
creating management station is still setting
values.

The value of invalid indicates the entry is
no longer in use and the agent is free to
delete the entry at any time. A management
station is also free to use an entry in the
invalid state.

Entries are created by setting a value of
createRequest. Only non-existent or invalid
entries can be set to createRequest. Upon
receiving a valid createRequest, the agent
will create an entry in the underCreation
state. This object can not be set to a
value of underCreation directly, entries can
only be created by setting a value of
createRequest. Entries that exist in other

than the invalid state can not be set to
createRequest.

Entries with a value of underCreation are
not used by the system and the management
station can change the values of other
objects in the table entry. Management
stations should also remember to configure
values in the mioxPeerEncTable with the same
peer index value as this peer entry.

An entry in the underCreation state can be
set to valid or invalid. Entries in the
underCreation state will stay in that state
until 1) the agent times them out, 2) they
are set to valid, 3) they are set to
invalid. If an agent notices an entry has
been in the underCreation state for an

abnormally long time, it may decide the
management station has failed and invalidate

the entry. A prudent agent will understand
that the management station may need to wait
for human input and will allow for that
possibility in its determination of this
abnormally long period.

Once a management station has completed all
fields of an entry, it will set a value of
valid. This causes the entry to be
activated.

Entries in the valid state may also be set
to makeCall or clearCall to make or clear
X.25 calls to the peer. After such a set
request the entry will still be in the valid
state. Setting a value of makeCall causes
the agent to initiate an X.25 call request
to the peer specified by the entry. Setting
a value of clearCall causes the agent to
initiate clearing one X.25 call present
to

the peer. Each set request will initiate
another call or clear request (up to the
maximum allowed); this means that management
stations that fail to get a response to a
set request should query to see if a call
was in fact placed or cleared before
retrying the request. Entries not in the
valid state can not be set to makeCall or
clearCall.

The values of makeCall and clearCall provide
for circuit control on devices which perform
Ethernet Bridging using static circuit
assignment without address recognition;
other devices which dynamically place calls
based on destination addresses may reject
such requests.

An agent that (re)creates a new entry
because of a set with createRequest, should

also (re)create a mioxPeerEncTable entry
with a mioxPeerEncIndex of 1, and a
mioxPeerEncType of 204 (hex CC)."

```
    ::= { mioxPeerEntry 2 }

mioxPeerMaxCircuits OBJECT-TYPE
    SYNTAX  PositiveInteger
    ACCESS  read-write
    STATUS    mandatory
    DESCRIPTION
        "The maximum number of X.25 circuits allowed
        to this peer."
    DEFVAL { 1 }
    ::= { mioxPeerEntry 3 }

mioxPeerIfIndex OBJECT-TYPE
    SYNTAX  PositiveInteger
    ACCESS  read-write
    STATUS  mandatory
    DESCRIPTION
        "The value of the ifIndex object for the
        interface to X.25 to use to call the peer."
    DEFVAL { 1 }
    ::= { mioxPeerEntry 4 }

mioxPeerConnectSeconds OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The number of seconds a call to this peer
        was active.  This counter
 will be
        incremented by one for every second a
        connection to a peer was open.  If two calls
        are open at the same time, one second of
        elapsed real time will results in two
        seconds of connect time."
    ::= { mioxPeerEntry 5 }

mioxPeerX25CallParamId OBJECT-TYPE
    SYNTAX  InstancePointer
    ACCESS  read-write
    STATUS  mandatory
    DESCRIPTION
        "The instance of the index object in the
        x25CallParmTable from RFC 1382 for the X.25
        call parameters used to communicate with the
        remote host.  The well known value {0 0}
        indicates no call parameters specified."
    DEFVAL { {0 0} }
```

```
        ::= { mioxPeerEntry 6 }

mioxPeerEnAddr  OBJECT-TYPE
        SYNTAX    OCTET STRING (SIZE (0..128))
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
                "The Encapsulation address of the remote
                 host mapped by this table entry.  A length
                of zero indicates the remote IP address is
                unknown or unspecified for use as a PLE
                default.

                The first octet of this object contains the
                encapsulation type, the remaining octets
                contain an address of that type.  Thus for
                an IP address, the length will be five
                octets, the first octet will contain 204
                (hex CC), and the last four octets will
                contain the IP address.  For a snap
                encapsulation, the first byte would be 128
                (hex 80) and the rest of the octet string
                would have the snap header."
        DEFVAL { "h }
        ::= { mioxPeerEntry 7 }

mioxPeerX121Address OBJECT-TYPE
        SYNTAX  X121Address
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
                "The X.25 address of the remote
 host mapped
                by this table entry.  A zero length string
                indicates the X.25 address is unspecified
                for use as the PLE default."
        DEFVAL { "h }
        ::= { mioxPeerEntry 8 }

-- Systems can claim conformance to this MIB without
-- implementing sets to mioxPeerX25CircuitId.
-- However systems that use PVCs with RFC1356
-- are encouraged to implement sets.
mioxPeerX25CircuitId OBJECT-TYPE
        SYNTAX  InstancePointer
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
```

```
            "This object identifies the instance of the
            index for the X.25 circuit open to the peer
            mapped by this table entry.  The well known
            value {0 0} indicates no connection
            currently active.  For multiple connections,
            this identifies the index of a multiplexing
            table entry for the connections.  This can
            only be written to configure
 use of PVCs
            which means the identified circuit table
            entry for a write must be a PVC."
        DEFVAL { {0 0} }
        ::= { mioxPeerEntry 9 }

mioxPeerDescr   OBJECT-TYPE
        SYNTAX  DisplayString (SIZE (0..255))
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
            "This object returns any identification
            information about the peer.  An agent may
            supply the comment information found in the
            configuration file entry for this peer.  A
            zero length string indicates no information
            available."
        DEFVAL { "h }
        ::= { mioxPeerEntry 10 }



-- ############################################################
--            Peer Encapsulation Table
-- ############################################################

mioxPeerEncTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF MioxPeerEncEntry
        ACCESS  not-accessible
        STATUS
  mandatory
        DESCRIPTION
            "This table contains the list of
            encapsulations used to communicate with a
            peer.  This table has two indexes, the first
            identifies the peer, the second
            distinguishes encapsulation types.

            The first index identifies the corresponding
            entry in the mioxPeerTable.  The second
```

index gives the priority of the different
encapsulations.

The encapsulation types are ordered in
priority order. For calling a peer, the
first entry (mioxPeerEncIndex of 1) is tried
first. If the call doesn't succeed because
the remote host clears the call due to
incompatible call user data, the next entry
in the list is tried. Each entry is tried
until the list is exhausted.

For answering a call, the
encapsulation type
requested by the peer must be found the list
or the call will be refused. If there are
no entries in this table for a peer, all
call requests from the peer will be refused.

Objects in this table can only be set when
the mioxPeerStatus object with the same
index has a value of underCreation. When
that status object is set to invalid and
deleted, the entry in this table with that
peer index must also be deleted."
::= { mioxPeer 2 }

mioxPeerEncEntry OBJECT-TYPE
SYNTAX MioxPeerEncEntry
ACCESS not-accessible
STATUS mandatory
DESCRIPTION
"Per connection information."
INDEX { mioxPeerIndex, mioxPeerEncIndex}
::= { mioxPeerEncTable 1 }

MioxPeerEncEntry ::= SEQUENCE {
mioxPeerEncIndex
PositiveInteger,
mioxPeerEncType
INTEGER
}

mioxPeerEncIndex OBJECT-TYPE
SYNTAX PositiveInteger
ACCESS read-only
STATUS mandatory
DESCRIPTION

```
            "The second index in the table which
            distinguishes different encapsulation
            types."
        ::= { mioxPeerEncEntry 1 }

    mioxPeerEncType OBJECT-TYPE
        SYNTAX  INTEGER (0..256)
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
            "The value of the encapsulation type.  For
            IP encapsulation this will have a value of
            204 (hex CC).  For SNAP encapsulated
            packets, this will have a value of 128 (hex
            80).  For CLNP, ISO 8473, this will have a
            value of 129 (hex 81).  For ES-ES, ISO 9542,
            this will have a value of 130 (hex 82).  A
            value of 197 (hex C5) identifies the Blacker
            X.25 encapsulation.  A value
     of 0,
            identifies the Null encapsulation.

            This value can only be written when the
            mioxPeerStatus object with the same
            mioxPeerIndex has a value of underCreation.
            Setting this object to a value of 256
            deletes the entry.  When deleting an entry,
            all other entries in the mioxPeerEncTable
            with the same mioxPeerIndex and with an
            mioxPeerEncIndex higher then the deleted
            entry, will all have their mioxPeerEncIndex
            values decremented by one."
        ::= { mioxPeerEncEntry 2 }

    -- ##############################################################

    END

    Found in path(s):
    * /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/MIOX25-MIB
    No license file was found, but licenses were detected in source scan.

    RFC1158-MIB DEFINITIONS ::= BEGIN

    IMPORTS
        mgmt, OBJECT-TYPE, NetworkAddress, IpAddress,
        Counter, Gauge, TimeTicks
            FROM RFC1155-SMI;
```

```
DisplayString ::=
        OCTET STRING

mib-2     OBJECT IDENTIFIER ::= { mgmt 1 }    -- MIB-II
       -- (same prefix as MIB-I)

system    OBJECT IDENTIFIER ::= { mib-2 1 }
interfaces OBJECT IDENTIFIER ::= { mib-2 2 }
at        OBJECT IDENTIFIER ::= { mib-2 3 }
ip        OBJECT IDENTIFIER ::= { mib-2 4 }
icmp      OBJECT IDENTIFIER ::= { mib-2 5 }
tcp       OBJECT IDENTIFIER ::= { mib-2 6 }
udp       OBJECT IDENTIFIER ::= { mib-2 7 }
egp       OBJECT IDENTIFIER ::= { mib-2 8 }
-- cmot   OBJECT IDENTIFIER ::= { mib-2 9 }
transmission OBJECT IDENTIFIER ::= { mib-2 10 }
snmp      OBJECT IDENTIFIER ::= { mib-2 11 }


-- object types

-- the System group

sysDescr OBJECT-TYPE
     SYNTAX  DisplayString (SIZE (0..255))
     ACCESS  read-only
      STATUS  mandatory
     ::= { system 1 }

sysObjectID OBJECT-TYPE
     SYNTAX  OBJECT IDENTIFIER
     ACCESS  read-only
     STATUS  mandatory
     ::= { system 2 }

sysUpTime OBJECT-TYPE
     SYNTAX  TimeTicks
     ACCESS  read-only
     STATUS  mandatory
     ::= { system 3 }

sysContact OBJECT-TYPE
     SYNTAX  DisplayString (SIZE (0..255))
     ACCESS  read-write
     STATUS  mandatory
     ::= { system 4 }
```

```
sysName OBJECT-TYPE
      SYNTAX  DisplayString (SIZE (0..255))
      ACCESS  read-write
      STATUS  mandatory
      ::= { system 5 }

sysLocation OBJECT-TYPE
      SYNTAX  DisplayString (SIZE (0..255))
      ACCESS  read-only
      STATUS  mandatory
      ::= { system 6 }

sysServices OBJECT-TYPE
      SYNTAX  INTEGER (0..127)
      ACCESS  read-only
      STATUS  mandatory
      ::= { system 7 }


-- the Interfaces group

ifNumber OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-only
      STATUS
  mandatory
      ::= { interfaces 1 }

-- the Interfaces table

ifTable OBJECT-TYPE
      SYNTAX  SEQUENCE OF IfEntry
      ACCESS  read-only
      STATUS  mandatory
      ::= { interfaces 2 }

ifEntry OBJECT-TYPE
      SYNTAX  IfEntry
      ACCESS  read-only
      STATUS  mandatory
      ::= { ifTable 1 }

IfEntry ::= SEQUENCE {
   ifIndex
      INTEGER,
   ifDescr
      DisplayString,
   ifType
```

```
      INTEGER,
  ifMtu
      INTEGER,
  ifSpeed
      Gauge,
  ifPhysAddress
      OCTET STRING,
  ifAdminStatus
      INTEGER,
  ifOperStatus
      INTEGER,
  ifLastChange
      TimeTicks,
  ifInOctets
      Counter,
  ifInUcastPkts
      Counter,
  ifInNUcastPkts
      Counter,
  ifInDiscards
      Counter,
  ifInErrors
      Counter,
  ifInUnknownProtos
      Counter,
  ifOutOctets
      Counter,
  ifOutUcastPkts
      Counter,
  ifOutNUcastPkts
      Counter,
  ifOutDiscards
      Counter,
  ifOutErrors
       Counter,
  ifOutQLen
      Gauge,
  ifSpecific
      OBJECT IDENTIFIER
}

ifIndex OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-only
      STATUS  mandatory
      ::= { ifEntry 1 }

ifDescr OBJECT-TYPE
```

```
    SYNTAX  DisplayString (SIZE (0..255))
    ACCESS  read-only
    STATUS  mandatory
    ::= { ifEntry 2 }

ifType OBJECT-TYPE
    SYNTAX  INTEGER {
            other(1),           -- none of the
                                -- following
            regular1822(2),
            hdh1822(3),
            ddn-x25(4),
            rfc877-x25(5),
            ethernet-csmacd(6),
            iso88023-csmacd(7),
            iso88024-tokenBus(8),
            iso88025-tokenRing(9),
            iso88026-man(10),
            starLan(11),
            proteon-10Mbit(12),
            proteon-80Mbit(13),
            hyperchannel(14),
             fddi(15),
            lapb(16),
            sdlc(17),
            t1-carrier(18),
            cept(19),       -- european
                           --equivalent of T-1
            basicISDN(20),
            primaryISDN(21),
                            -- proprietary
                            -- serial
            propPointToPointSerial(22),
            terminalServer-asyncPort(23),
            softwareLoopback(24),
            eon(25),            -- CLNP over IP
            ethernet-3Mbit(26),
            nsip(27),           -- XNS over IP
            slip(28)            -- generic SLIP
        }
    ACCESS  read-only
    STATUS  mandatory
    ::= { ifEntry 3 }

ifMtu OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-only
    STATUS  mandatory
```

```
    ::= { ifEntry 4 }

ifSpeed
 OBJECT-TYPE
    SYNTAX  Gauge
    ACCESS  read-only
    STATUS  mandatory
    ::= { ifEntry 5 }

ifPhysAddress OBJECT-TYPE
    SYNTAX  OCTET STRING
    ACCESS  read-only
    STATUS  mandatory
    ::= { ifEntry 6 }

ifAdminStatus OBJECT-TYPE
    SYNTAX  INTEGER {
            up(1),     -- ready to pass packets
            down(2),
            testing(3) -- in some test mode
          }
    ACCESS  read-write
    STATUS  mandatory
    ::= { ifEntry 7 }

ifOperStatus OBJECT-TYPE
    SYNTAX  INTEGER {
            up(1),     -- ready to pass packets
            down(2),
            testing(3) -- in some test mode
          }
    ACCESS  read-only
    STATUS  mandatory
    ::= { ifEntry 8 }

ifLastChange OBJECT-TYPE
    SYNTAX  TimeTicks
    ACCESS  read-only
    STATUS  mandatory
    ::= { ifEntry 9 }

ifInOctets OBJECT-TYPE
    SYNTAX  Counter
     ACCESS  read-only
    STATUS  mandatory
    ::= { ifEntry 10 }

ifInUcastPkts OBJECT-TYPE
```

SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { ifEntry 11 }

ifInNUcastPkts OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { ifEntry 12 }

ifInDiscards OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { ifEntry 13 }

ifInErrors OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { ifEntry 14 }

ifInUnknownProtos OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { ifEntry 15 }

ifOutOctets OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { ifEntry 16 }

ifOutUcastPkts OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { ifEntry 17 }

ifOutNUcastPkts
OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { ifEntry 18 }

```
ifOutDiscards OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { ifEntry 19 }

ifOutErrors OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { ifEntry 20 }

ifOutQLen OBJECT-TYPE
      SYNTAX  Gauge
      ACCESS  read-only
      STATUS  mandatory
      ::= { ifEntry 21 }

ifSpecific OBJECT-TYPE
      SYNTAX  OBJECT IDENTIFIER
      ACCESS  read-only
      STATUS  mandatory
      ::= { ifEntry 22 }

nullSpecific OBJECT IDENTIFIER ::= { 0 0 }

-- the Address Translation group (deprecated)

atTable OBJECT-TYPE
      SYNTAX  SEQUENCE OF AtEntry
      ACCESS  read-write
      STATUS  deprecated
      ::= { at 1 }

atEntry OBJECT-TYPE
      SYNTAX  AtEntry
      ACCESS  read-write
      STATUS  deprecated
      ::= { atTable 1 }

AtEntry ::=
 SEQUENCE {
  atIfIndex
     INTEGER,
  atPhysAddress
     OCTET STRING,
  atNetAddress
     NetworkAddress
```

```
}

atIfIndex OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-write
      STATUS  deprecated
      ::= { atEntry 1 }

atPhysAddress OBJECT-TYPE
      SYNTAX  OCTET STRING
      ACCESS  read-write
      STATUS  deprecated
      ::= { atEntry 2 }

atNetAddress OBJECT-TYPE
      SYNTAX  NetworkAddress
      ACCESS  read-write
      STATUS  deprecated
      ::= { atEntry 3 }


-- the IP group

ipForwarding OBJECT-TYPE
      SYNTAX  INTEGER {
                gateway(1), -- entity forwards
                        -- datagrams
                host(2)     -- entity does NOT
                        -- forward datagrams
              }
      ACCESS  read-write
      STATUS  mandatory
      ::= { ip 1 }

ipDefaultTTL OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-write
      STATUS  mandatory
      ::=
 { ip 2 }

ipInReceives OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { ip 3 }

ipInHdrErrors OBJECT-TYPE
```

```
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 4 }

ipInAddrErrors OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 5 }

ipForwDatagrams OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 6 }

ipInUnknownProtos OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 7 }

ipInDiscards OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 8 }

ipInDelivers OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 9 }

ipOutRequests OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= {
 ip 10 }

ipOutDiscards OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 11 }
```

```
ipOutNoRoutes OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { ip 12 }

ipReasmTimeout OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-only
    STATUS  mandatory
    ::= { ip 13 }

ipReasmReqds OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { ip 14 }

ipReasmOKs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { ip 15 }

ipReasmFails OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { ip 16 }

ipFragOKs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { ip 17 }

ipFragFails OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { ip 18 }

ipFragCreates
 OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { ip 19 }
```

```
-- the IP Interface table

ipAddrTable OBJECT-TYPE
      SYNTAX  SEQUENCE OF IpAddrEntry
      ACCESS  read-only
      STATUS  mandatory
      ::= { ip 20 }

ipAddrEntry OBJECT-TYPE
      SYNTAX  IpAddrEntry
      ACCESS  read-only
      STATUS  mandatory
      ::= { ipAddrTable 1 }

IpAddrEntry ::= SEQUENCE {
  ipAdEntAddr
      IpAddress,
  ipAdEntIfIndex
      INTEGER,
  ipAdEntNetMask
      IpAddress,
  ipAdEntBcastAddr
      INTEGER,
  ipAdEntReasmMaxSize
      INTEGER (0..65535)
}

ipAdEntAddr OBJECT-TYPE
      SYNTAX  IpAddress
      ACCESS  read-only
      STATUS  mandatory
      ::=  { ipAddrEntry 1 }

ipAdEntIfIndex OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-only
      STATUS  mandatory
      ::=  { ipAddrEntry 2 }

ipAdEntNetMask OBJECT-TYPE
      SYNTAX  IpAddress
      ACCESS  read-only
       STATUS  mandatory
      ::=  { ipAddrEntry 3 }

ipAdEntBcastAddr OBJECT-TYPE
      SYNTAX  INTEGER
```

```
        ACCESS  read-only
        STATUS  mandatory
        ::= { ipAddrEntry 4 }

ipAdEntReasmMaxSize OBJECT-TYPE
        SYNTAX  INTEGER (0..65535)
        ACCESS  read-only
        STATUS  mandatory
        ::= { ipAddrEntry 5 }

-- the IP Routing table

ipRoutingTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF IpRouteEntry
        ACCESS  read-write
        STATUS  mandatory
        ::= { ip 21 }

ipRouteEntry OBJECT-TYPE
        SYNTAX  IpRouteEntry
        ACCESS  read-write
        STATUS  mandatory
        ::= { ipRoutingTable 1 }

IpRouteEntry ::= SEQUENCE {
  ipRouteDest
      IpAddress,
  ipRouteIfIndex
      INTEGER,
  ipRouteMetric1
      INTEGER,
  ipRouteMetric2
      INTEGER,
  ipRouteMetric3
      INTEGER,
  ipRouteMetric4
      INTEGER,
  ipRouteNextHop
      IpAddress,
  ipRouteType
      INTEGER,
  ipRouteProto
      INTEGER,
   ipRouteAge
      INTEGER,
  ipRouteMask
      IpAddress
}
```

```
ipRouteDest OBJECT-TYPE
      SYNTAX  IpAddress
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipRouteEntry 1 }

ipRouteIfIndex  OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipRouteEntry 2 }

ipRouteMetric1 OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipRouteEntry 3 }

ipRouteMetric2 OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipRouteEntry 4 }

ipRouteMetric3 OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipRouteEntry 5 }

ipRouteMetric4 OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipRouteEntry 6 }

ipRouteNextHop OBJECT-TYPE
      SYNTAX  IpAddress
      ACCESS  read-write
      STATUS  mandatory

    ::= { ipRouteEntry 7 }

ipRouteType OBJECT-TYPE
      SYNTAX  INTEGER {
              other(1),    -- none of the following
```

```
                invalid(2),  -- an invalidated route

                        -- route to directly
                direct(3),   -- connected
                        -- (sub-)network

                        -- route to a non-local
                remote(4)    -- host/network/
                        -- sub-network
            }
        ACCESS  read-write
        STATUS  mandatory
        ::= { ipRouteEntry 8 }

    ipRouteProto OBJECT-TYPE
        SYNTAX  INTEGER {
                other(1),    -- none of the following

                        -- non-protocol
                        -- information

                        --   e.g., manually
                local(2),    --   configured entries

                        -- set via a network
                netmgmt(3),
     --   management protocol

                        -- obtained via ICMP,
                icmp(4),     --   e.g., Redirect

                        -- the following are
                        -- gateway routing
                        -- protocols
                egp(5),
                ggp(6),
                hello(7),
                rip(8),
                is-is(9),
                es-is(10),
                ciscoIgrp(11),
                bbnSpfIgp(12),
                ospf(13),
                bgp(14)
            }
        ACCESS  read-only
        STATUS  mandatory
        ::= { ipRouteEntry 9 }
```

```
ipRouteAge OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipRouteEntry 10 }

ipRouteMask OBJECT-TYPE
      SYNTAX  IpAddress
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipRouteEntry 11 }

-- the IP Address Translation tables

ipNetToMediaTable
 OBJECT-TYPE
      SYNTAX  SEQUENCE OF IpNetToMediaEntry
      ACCESS  read-write
      STATUS  mandatory
      ::= { ip 22 }

ipNetToMediaEntry OBJECT-TYPE
      SYNTAX  IpNetToMediaEntry
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipNetToMediaTable 1 }

IpNetToMediaEntry ::= SEQUENCE {
  ipNetToMediaIfIndex
     INTEGER,
  ipNetToMediaPhysAddress
     OCTET STRING,
  ipNetToMediaNetAddress
     IpAddress,
  ipNetToMediaType
     INTEGER
}

ipNetToMediaIfIndex OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipNetToMediaEntry 1 }

ipNetToMediaPhysAddress OBJECT-TYPE
      SYNTAX  OCTET STRING
      ACCESS  read-write
```

```
        STATUS  mandatory
        ::= { ipNetToMediaEntry 2 }

ipNetToMediaNetAddress OBJECT-TYPE
        SYNTAX  IpAddress
        ACCESS  read-write
        STATUS  mandatory
        ::= { ipNetToMediaEntry 3 }

ipNetToMediaType OBJECT-TYPE

      SYNTAX  INTEGER {
                other(1),   -- none of the following

                invalid(2), -- an invalidated mapping
                dynamic(3), -- connected (sub-)network

                static(4)
            }
        ACCESS  read-write
        STATUS  mandatory
        ::= { ipNetToMediaEntry 4 }

-- the ICMP group

icmpInMsgs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 1 }

icmpInErrors OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 2 }

icmpInDestUnreachs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 3 }

icmpInTimeExcds OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 4 }
```

```
icmpInParmProbs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 5 }

icmpInSrcQuenchs
 OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 6 }

icmpInRedirects OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 7 }

icmpInEchos OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 8 }

icmpInEchoReps OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 9 }

icmpInTimestamps OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 10 }

icmpInTimestampReps OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 11 }

icmpInAddrMasks OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
```

::= { icmp 12 }

icmpInAddrMaskReps OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory

::= { icmp 13 }

icmpOutMsgs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { icmp 14 }

icmpOutErrors OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { icmp 15 }

icmpOutDestUnreachs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { icmp 16 }

icmpOutTimeExcds OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { icmp 17 }

icmpOutParmProbs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { icmp 18 }

icmpOutSrcQuenchs OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
::= { icmp 19 }

icmpOutRedirects OBJECT-TYPE
SYNTAX Counter
ACCESS read-only

```
        STATUS  mandatory
        ::= { icmp 20 }

icmpOutEchos OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
         STATUS  mandatory
        ::= { icmp 21 }

icmpOutEchoReps OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 22 }

icmpOutTimestamps OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 23 }

icmpOutTimestampReps OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 24 }

icmpOutAddrMasks OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 25 }

icmpOutAddrMaskReps OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 26 }


-- the TCP group

tcpRtoAlgorithm OBJECT-TYPE
        SYNTAX  INTEGER {
                other(1),    -- none of the following
                constant(2), -- a constant rto
                rsre(3),     -- MIL-STD-1778,
                        -- Appendix B
```

```
        vanj(4)      -- Van Jacobson's
                     -- algorithm
            }
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcp 1 }

    tcpRtoMin OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcp 2 }

    tcpRtoMax OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcp 3 }

    tcpMaxConn OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcp 4 }

    tcpActiveOpens OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcp 5 }

    tcpPassiveOpens OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcp 6 }

    tcpAttemptFails OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcp 7 }

    tcpEstabResets OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
```

```
      STATUS  mandatory
      ::= { tcp 8 }

tcpCurrEstab OBJECT-TYPE
      SYNTAX  Gauge
      ACCESS  read-only
      STATUS  mandatory
      ::= { tcp 9 }

tcpInSegs OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { tcp 10 }

tcpOutSegs OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { tcp 11 }

tcpRetransSegs OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { tcp 12 }

-- the TCP connections table

tcpConnTable OBJECT-TYPE
      SYNTAX  SEQUENCE OF TcpConnEntry
      ACCESS  read-only
      STATUS  mandatory
      ::= { tcp 13 }

tcpConnEntry OBJECT-TYPE
      SYNTAX  TcpConnEntry
      ACCESS  read-only
      STATUS  mandatory
      ::= { tcpConnTable 1 }

TcpConnEntry ::= SEQUENCE {
  tcpConnState
      INTEGER,
  tcpConnLocalAddress
      IpAddress,
  tcpConnLocalPort
      INTEGER (0..65535),
```

```
    tcpConnRemAddress
      IpAddress,
   tcpConnRemPort
      INTEGER (0..65535)
}

tcpConnState OBJECT-TYPE
      SYNTAX  INTEGER {
                closed(1),
                listen(2),
                synSent(3),
                synReceived(4),
                established(5),
                finWait1(6),
                finWait2(7),
                closeWait(8),
                lastAck(9),
                closing(10),
                timeWait(11)
              }
      ACCESS  read-only
      STATUS  mandatory
      ::= { tcpConnEntry 1 }

tcpConnLocalAddress OBJECT-TYPE
      SYNTAX  IpAddress
      ACCESS  read-only
      STATUS  mandatory
      ::= { tcpConnEntry 2 }

tcpConnLocalPort OBJECT-TYPE
      SYNTAX  INTEGER (0..65535)
      ACCESS  read-only
      STATUS  mandatory
      ::= { tcpConnEntry 3 }

tcpConnRemAddress OBJECT-TYPE
      SYNTAX  IpAddress
      ACCESS  read-only
      STATUS  mandatory
       ::= { tcpConnEntry 4 }

tcpConnRemPort OBJECT-TYPE
      SYNTAX  INTEGER (0..65535)
      ACCESS  read-only
      STATUS  mandatory
      ::= { tcpConnEntry 5 }
```

```
-- additional TCP variables

tcpInErrs OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { tcp 14 }

tcpOutRsts OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { tcp 15 }


-- the UDP group

udpInDatagrams OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { udp 1 }

udpNoPorts OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { udp 2 }

udpInErrors OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { udp 3 }

udpOutDatagrams OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { udp 4 }

-- the UDP listener table

udpTable
 OBJECT-TYPE
      SYNTAX  SEQUENCE OF UdpEntry
      ACCESS  read-only
      STATUS  mandatory
```

```
        ::= { udp 5 }

udpEntry OBJECT-TYPE
        SYNTAX  UdpEntry
        ACCESS  read-only
        STATUS  mandatory
        ::= { udpTable 1 }

UdpEntry ::= SEQUENCE {
  udpLocalAddress
        IpAddress,
  udpLocalPort
        INTEGER (0..65535)
}

udpLocalAddress OBJECT-TYPE
        SYNTAX  IpAddress
        ACCESS  read-only
        STATUS  mandatory
        ::= { udpEntry 1 }

udpLocalPort OBJECT-TYPE
        SYNTAX  INTEGER (0..65535)
        ACCESS  read-only
        STATUS  mandatory
        ::= { udpEntry 2 }

-- the EGP group

egpInMsgs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { egp 1 }

egpInErrors OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { egp 2 }

egpOutMsgs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
         ::= { egp 3 }

egpOutErrors OBJECT-TYPE
```

```
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { egp 4 }

-- the EGP Neighbor table

egpNeighTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF EgpNeighEntry
        ACCESS  read-only
        STATUS  mandatory
        ::= { egp 5 }

egpNeighEntry OBJECT-TYPE
        SYNTAX  EgpNeighEntry
        ACCESS  read-only
        STATUS  mandatory
        ::= { egpNeighTable 1 }

EgpNeighEntry ::= SEQUENCE {
    egpNeighState
        INTEGER,
    egpNeighAddr
        IpAddress,
    egpNeighAs
        INTEGER,
    egpNeighInMsgs
        Counter,
    egpNeighInErrs
        Counter,
    egpNeighOutMsgs
        Counter,
    egpNeighOutErrs
        Counter,
    egpNeighInErrMsgs
        Counter,
    egpNeighOutErrMsgs
        Counter,
    egpNeighStateUps
        Counter,
    egpNeighStateDowns
        Counter,
    egpNeighIntervalHello
        INTEGER,
    egpNeighIntervalPoll
        INTEGER,
    egpNeighMode
```

```
      INTEGER,
  egpNeighEventTrigger
      INTEGER
}

egpNeighState OBJECT-TYPE
      SYNTAX  INTEGER {
                idle(1),
                acquisition(2),
                down(3),
                up(4),
                cease(5)
              }
      ACCESS  read-only
      STATUS  mandatory
      ::= { egpNeighEntry 1 }

egpNeighAddr OBJECT-TYPE
      SYNTAX  IpAddress
      ACCESS  read-only
      STATUS  mandatory
      ::= { egpNeighEntry 2 }

egpNeighAs OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-only
      STATUS  mandatory
      ::= { egpNeighEntry 3 }

egpNeighInMsgs OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { egpNeighEntry 4 }

egpNeighInErrs OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { egpNeighEntry 5 }

egpNeighOutMsgs OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS
  mandatory
      ::= { egpNeighEntry 6 }
```

```
egpNeighOutErrs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { egpNeighEntry 7 }

egpNeighInErrMsgs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { egpNeighEntry 8 }

egpNeighOutErrMsgs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { egpNeighEntry 9 }

egpNeighStateUps OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { egpNeighEntry 10 }

egpNeighStateDowns OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { egpNeighEntry 11 }

egpNeighIntervalHello OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-only
    STATUS  mandatory
    ::= { egpNeighEntry 12 }

egpNeighIntervalPoll OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-only
    STATUS  mandatory

   ::= { egpNeighEntry 13 }

egpNeighMode OBJECT-TYPE
    SYNTAX  INTEGER {
              active(1),
              passive(2)
            }
```

```
        ACCESS  read-only
        STATUS  mandatory
        ::= { egpNeighEntry 14 }

egpNeighEventTrigger OBJECT-TYPE
        SYNTAX  INTEGER {
                    start(1),
                    stop(2)
                }
        ACCESS  read-write
        STATUS  mandatory
        ::= { egpNeighEntry 15 }

-- additional EGP variables

egpAs OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-only
        STATUS  mandatory
        ::= { egp 6 }


-- the Transmission group (empty at present)

-- the SNMP group

snmpInPkts OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::=  { snmp 1 }

snmpOutPkts OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::=  { snmp 2 }

snmpInBadVersions OBJECT-TYPE
        SYNTAX  Counter
        ACCESS
 read-only
        STATUS  mandatory
        ::=  { snmp 3 }

snmpInBadCommunityNames OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
```

```
    STATUS  mandatory
    ::= { snmp 4 }

snmpInBadCommunityUses OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { snmp 5 }

snmpInASNParseErrs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { snmp 6 }

snmpInBadTypes OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { snmp 7 }

snmpInTooBigs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { snmp 8 }

snmpInNoSuchNames OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { snmp 9 }

snmpInBadValues OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { snmp 10 }

snmpInReadOnlys OBJECT-TYPE
     SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { snmp 11 }

snmpInGenErrs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
```

```
        STATUS  mandatory
        ::= { snmp 12 }

snmpInTotalReqVars OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { snmp 13 }

snmpInTotalSetVars OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { snmp 14 }

snmpInGetRequests OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { snmp 15 }

snmpInGetNexts OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { snmp 16 }

snmpInSetRequests OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { snmp 17 }

snmpInGetResponses OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
         ::= { snmp 18 }

snmpInTraps OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { snmp 19 }

snmpOutTooBigs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
```

```
        STATUS  mandatory
        ::= { snmp 20 }

snmpOutNoSuchNames OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { snmp 21 }

snmpOutBadValues OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { snmp 22 }

snmpOutReadOnlys OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { snmp 23 }

snmpOutGenErrs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { snmp 24 }

snmpOutGetRequests OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { snmp 25 }

snmpOutGetNexts OBJECT-TYPE
        SYNTAX  Counter

       ACCESS  read-only
        STATUS  mandatory
        ::= { snmp 26 }

snmpOutSetRequests OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { snmp 27 }

snmpOutGetResponses OBJECT-TYPE
        SYNTAX  Counter
```

```
        ACCESS  read-only
        STATUS  mandatory
        ::=  { snmp 28 }

snmpOutTraps OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::=  { snmp 29 }

snmpEnableAuthTraps OBJECT-TYPE
        SYNTAX  INTEGER {
                    enabled(1),
                    disabled(2)
                }
        ACCESS  read-write
        STATUS  mandatory
        ::=  { snmp 30 }

END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/RFC1158-MIB
No license file was found, but licenses were detected in source scan.

```
DLSW-MIB DEFINITIONS ::= BEGIN

IMPORTS
        DisplayString, RowStatus,
        RowPointer, TruthValue,
        TEXTUAL-CONVENTION              FROM SNMPv2-TC
        Counter32, Gauge32, TimeTicks,
        OBJECT-TYPE, MODULE-IDENTITY,
        NOTIFICATION-TYPE, mib-2        FROM SNMPv2-SMI
        MODULE-COMPLIANCE, OBJECT-GROUP,
        NOTIFICATION-GROUP              FROM SNMPv2-CONF
        ifIndex                     FROM IF-MIB
        sdlcLSAddress                   FROM SNA-SDLC-MIB;

dlsw MODULE-IDENTITY
    LAST-UPDATED  "9606040900Z"
    ORGANIZATION  "AIW DLSw MIB RIGLET and IETF DLSw MIB Working Group"
    CONTACT-INFO
              "David D. Chen
               IBM Corporation
               800 Park, Highway 54
               Research Triangle Park, NC 27709-9990
               Tel:    1 919 254 6182
```

```
                E-mail: dchen@vnet.ibm.com"
  DESCRIPTION

    "This MIB module contains objects to manage Data Link
       Switches."
::= { mib-2 46 }

dlswMIB         OBJECT IDENTIFIER ::= { dlsw 1 }
dlswDomains     OBJECT IDENTIFIER ::= { dlsw 2 }

-- ****************************************************************
-- Textual convention definitions
-- ****************************************************************

NBName ::= TEXTUAL-CONVENTION
  STATUS       current
  DESCRIPTION
     "Represents a single qualified NetBIOS name, which can include
      `don't care' and `wildcard' characters to represent a number
      of real NetBIOS names.  If an individual character position in
      the qualified name contains a `?', the corresponding character
      position in a real NetBIOS name is a `don't care'.  If the
      qualified name ends in `*', the remainder of a real NetBIOS
      name is a `don't care'. `*' is only considered a wildcard if it
      appears at the end of a name."
  SYNTAX  OCTET STRING (SIZE
 (0..16))

MacAddressNC ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "1x:"
  STATUS       current
  DESCRIPTION
     "Represents an 802 MAC address represented in
      non-canonical format.  That is, the most significant
      bit will be transmitted first.  If this information
      is not available, the value is a zero length string."
  SYNTAX       OCTET STRING (SIZE (0 | 6))

TAddress ::= TEXTUAL-CONVENTION
  STATUS  current
  DESCRIPTION
     "Denotes a transport service address.
      For dlswTCPDomain, a TAddress is 4 octets long,
      containing the IP-address in network-byte order."
  SYNTAX  OCTET STRING (SIZE (0..255))

EndStationLocation ::= TEXTUAL-CONVENTION
  STATUS  current
```

```
  DESCRIPTION
    "Representing the location of an end station related
     to the managed DLSw node."
  SYNTAX  INTEGER  {
            other         (1),
            internal      (2),  -- local virtual MAC address
            remote        (3),  -- via
 DLSw partner
            local         (4)   -- locally attached
          }

DlcType ::= TEXTUAL-CONVENTION
  STATUS  current
  DESCRIPTION
    "Representing the type of DLC of an end station, if
     applicable."
  SYNTAX  INTEGER  {
            other         (1),  -- not assigned yet
            na            (2),  -- not applicable
            llc           (3),  -- 802.2 Logical Link Control
            sdlc          (4),  -- SDLC
            qllc          (5)   -- QLLC
          }

LFSize  ::= TEXTUAL-CONVENTION
  STATUS  current
  DESCRIPTION
    "The largest size of the INFO field (including DLC header,
     not including any MAC-level or framing octets).
     64 valid values as defined by the IEEE 802.1D
     Addendum are acceptable."
  SYNTAX  INTEGER  {
            lfs516(516), lfs635(635), lfs754(754), lfs873(873),
            lfs993(993), lfs1112(1112), lfs1231(1231),
            lfs1350(1350), lfs1470(1470),
 lfs1542(1542),
            lfs1615(1615), lfs1688(1688), lfs1761(1761),
            lfs1833(1833), lfs1906(1906), lfs1979(1979),
            lfs2052(2052), lfs2345(2345), lfs2638(2638),
            lfs2932(2932), lfs3225(3225), lfs3518(3518),
            lfs3812(3812), lfs4105(4105), lfs4399(4399),
            lfs4865(4865), lfs5331(5331), lfs5798(5798),
            lfs6264(6264), lfs6730(6730), lfs7197(7197),
            lfs7663(7663), lfs8130(8130), lfs8539(8539),
            lfs8949(8949), lfs9358(9358), lfs9768(9768),
            lfs10178(10178), lfs10587(10587), lfs10997(10997),
            lfs11407(11407), lfs12199(12199), lfs12992(12992),
            lfs13785(13785), lfs14578(14578), lfs15370(15370),
```

```
            lfs16163(16163), lfs16956(16956), lfs17749(17749),
            lfs20730(20730), lfs23711(23711), lfs26693(26693),
            lfs29674(29674), lfs32655(32655), lfs38618(38618),
            lfs41600(41600), lfs44591(44591),
 lfs47583(47583),
            lfs50575(50575), lfs53567(53567), lfs56559(56559),
            lfs59551(59551), lfs65535(65535)
          }

null OBJECT IDENTIFIER ::= { 0 0 }


-- ************************************************************************
-- DLSw Transport Domain definitions
-- ************************************************************************

-- DLSw over TCP
dlswTCPDomain  OBJECT IDENTIFIER ::= { dlswDomains 1 }
-- for an IP address of length 4:
--
-- octets   contents        encoding
--  1-4     IP-address      network-byte order
--
DlswTCPAddress ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "1d.1d.1d.1d"
  STATUS       current
  DESCRIPTION
          "Represents the IP address of a DLSw which uses
           TCP as a transport protocol."
  SYNTAX       OCTET STRING (SIZE (4))


-- ************************************************************************
-- DLSw MIB Definition
-- ************************************************************************

-- The
 DLSw MIB module contains an object part and a conformance part.
-- Object part is organized in the following groups:
-- (1) dlswNode      -  information about this DLSw
-- (2) dlswTConn     -  about adjacent DLSw partners
-- (3) dlswInterface -  about which interfaces DLSw is active on
-- (4) dlswDirectory -  about any directory of local/remote resources
-- (5) dlswCircuit   -  about established circuits.
-- (6) dlswSdlc      -  about SDLC data link switched devices

dlswNode        OBJECT IDENTIFIER ::= { dlswMIB 1 }
dlswTConn       OBJECT IDENTIFIER ::= { dlswMIB 2 }
```

```
dlswInterface   OBJECT IDENTIFIER ::= { dlswMIB 3 }
dlswDirectory   OBJECT IDENTIFIER ::= { dlswMIB 4 }
dlswCircuit     OBJECT IDENTIFIER ::= { dlswMIB 5 }
dlswSdlc        OBJECT IDENTIFIER ::= { dlswMIB 6 }  -- SDLC

-- ****************************************************************
-- THE NODE GROUP
-- ****************************************************************

-- ----------------------------------------------------------------
--
 DLSw Node Identity
-- ----------------------------------------------------------------
dlswNodeVersion  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (2))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "This value identifies the particular version of the DLSw
      standard supported by this DLSw.  The first octet is a
      hexadecimal value representing the DLSw standard Version
      number of this DLSw, and the second is a hexadecimal value
      representing the DLSw standard Release number. This
      information is reported in DLSw Capabilities Exchange."
  REFERENCE
     "DLSW: Switch-to-Switch Protocol RFC 1795"
  ::= { dlswNode 1 }

dlswNodeVendorID  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (3))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The value identifies the manufacturer's IEEE-assigned
      organizationally Unique Identifier (OUI) of this DLSw.
      This information
 is reported in DLSw Capabilities
      Exchange."
  REFERENCE
     "DLSW: Switch-to-Switch Protocol RFC 1795"
  ::= { dlswNode 2 }

dlswNodeVersionString  OBJECT-TYPE
  SYNTAX     DisplayString
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "This string gives product-specific information about
```

```
      this DLSw (e.g., product name, code release and fix level).
      This flows in Capabilities Exchange messages."
    REFERENCE
      "DLSW: Switch-to-Switch Protocol RFC 1795"
    ::= { dlswNode 3 }

-- ---------------------------------------------------------------
-- DLSw Code Capability
-- ---------------------------------------------------------------
dlswNodeStdPacingSupport  OBJECT-TYPE
    SYNTAX     INTEGER  {
      none            (1),  -- does not support DLSw
                            -- Standard pacing scheme
      adaptiveRcvWindow (2),  -- the receive window size
                            -- varies
      fixedRcvWindow
     (3)   -- the receive window size
                            -- remains constant
    }
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
      "Circuit pacing, as defined in the DLSw Standard, allows each
       of the two DLSw nodes on a circuit to control the amount
       of data the other is permitted to send to them.  This object
       reflects the level of support the DLSw node has for this
       protocol.  (1) means the node has no support for the standard
       circuit pacing flows;  it may use RFC 1434+ methods only, or
       a proprietary flow control scheme.  (2) means the node supports
       the standard scheme and can vary the window sizes it grants as
       a data receiver.  (3) means the node supports the standard
       scheme but never varies its receive window size."
    ::= { dlswNode 4 }

-- ---------------------------------------------------------------
-- DLSw Node Operational Objects
-- ---------------------------------------------------------------
dlswNodeStatus
   OBJECT-TYPE
    SYNTAX     INTEGER  {
       active       (1),
       inactive      (2)
    }
    MAX-ACCESS read-write
    STATUS     current
    DESCRIPTION
      "The status of the DLSw part of the system.  Changing the
       value from active to inactive causes DLSw to take
```

```
        the following actions - (1) it disconnects all circuits
        through all DLSw partners, (2) it disconnects all
        transport connections to all DLSw partners, (3) it
        disconnects all local DLC connections, and (4) it stops
        processing all DLC connection set-up traffic.
        Since these are destructive actions, the user should
        query the circuit and transport connection tables in
        advance to understand the effect this action will have.
        Changing the value from inactive to active causes DLSw
        to come up in its initial state, i.e., transport
        connections established and ready to bring up circuits."
    ::= { dlswNode 5 }

dlswNodeUpTime  OBJECT-TYPE
    SYNTAX     TimeTicks
    UNITS      "hundredths of a second"
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
        "The amount of time (in hundredths of a second) since
        the DLSw portion of the system was last re-initialized.
        That is, if dlswState is in the active state,
        the time the dlswState entered the active state.
        It will remain zero if dlswState is in the
        inactive state."
    ::= { dlswNode 6 }

dlswNodeVirtualSegmentLFSize  OBJECT-TYPE
    SYNTAX     LFSize
    MAX-ACCESS read-write
    STATUS     current
    DESCRIPTION
        "The largest frame size (including DLC header and info field
        but not any MAC-level or framing octets) this DLSw can forward
        on any path through itself.  This object can represent any box-
        level frame size forwarding restriction (e.g., from the use
        of fixed-size buffers).  Some DLSw implementations will have
         no such restriction.

        This value will affect the LF size of circuits during circuit
        creation.  The LF size of an existing circuit can be found in
        the RIF (Routing Information Field)."
    DEFVAL  { lfs65535 }
    ::= { dlswNode 7 }

-- ..........................................................
-- NETBIOS Resources
-- ..........................................................
```

```
dlswNodeResourceNBExclusivity  OBJECT-TYPE
  SYNTAX     TruthValue
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
    "The value of true indicates that the NetBIOS Names
     configured in dlswDirNBTable are the only ones accessible
     via this DLSw.

     If a node supports sending run-time capabilities exchange
     messages, changes to this object should cause that action.
     It is up to the implementation exactly when to start the
     run-time capabilities exchange."
  ::= { dlswNode 8 }

-- ....................................................................
--
 MAC Address List
-- ....................................................................

dlswNodeResourceMacExclusivity  OBJECT-TYPE
  SYNTAX     TruthValue
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
    "The value of true indicates that the MAC addresses
     configured in the dlswDirMacTable are the only ones
     accessible via this DLSw.

     If a node supports sending run-time capabilities exchange
     messages, changes to this object should cause that action.
     It is up to the implementation exactly when to start the
     run-time capabilities exchange."
  ::= { dlswNode 9 }


-- ************************************************************************
-- TRANSPORT CONNECTION (aka: PARTNER DLSW)
-- ************************************************************************

-- ------------------------------------------------------------------

-- Transport Connection Statistics Objects
-- ------------------------------------------------------------------
dlswTConnStat
   OBJECT IDENTIFIER ::= { dlswTConn 1 }
```

```
dlswTConnStatActiveConnections  OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of transport connections that are not in
     `disconnected' state."
  ::= { dlswTConnStat 1 }

dlswTConnStatCloseIdles  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of times transport connections in this node
     exited the connected state with zero active circuits on
     the transport connection."
  ::= { dlswTConnStat 2 }

dlswTConnStatCloseBusys  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of times transport connections in this node
     exited the connected state with some non-zero number
     of active circuits on the transport connection.  Normally
      this means the transport connection failed unexpectedly."
  ::= { dlswTConnStat 3 }

-- ----------------------------------------------------------------
-- Transport Connection Configuration Table
-- ----------------------------------------------------------------
dlswTConnConfigTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswTConnConfigEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "This table defines the transport connections
     that will be initiated or accepted by this
     DLSw.  Structure of masks allows wildcard
     definition for a collection of transport
     connections by a conceptual row.  For a
     specific transport connection, there may
     be multiple of conceptual rows match the
     transport address.  The `best' match will
     the one to determine the characteristics
     of the transport connection."
```

```
  ::= { dlswTConn 2 }

dlswTConnConfigEntry  OBJECT-TYPE
  SYNTAX     DlswTConnConfigEntry
   MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "Each conceptual row defines a collection of
     transport connections."
  INDEX   { dlswTConnConfigIndex }
  ::= { dlswTConnConfigTable 1 }

DlswTConnConfigEntry ::= SEQUENCE {
  dlswTConnConfigIndex              INTEGER,
  dlswTConnConfigTDomain            OBJECT IDENTIFIER,
  dlswTConnConfigLocalTAddr         TAddress,
  dlswTConnConfigRemoteTAddr        TAddress,
  dlswTConnConfigLastModifyTime     TimeTicks,
  dlswTConnConfigEntryType          INTEGER,
  dlswTConnConfigGroupDefinition    RowPointer,
  dlswTConnConfigSetupType          INTEGER,
  dlswTConnConfigSapList            OCTET STRING,
  dlswTConnConfigAdvertiseMacNB     TruthValue,
  dlswTConnConfigInitCirRecvWndw    INTEGER,
  dlswTConnConfigOpens              Counter32,
  dlswTConnConfigRowStatus          RowStatus
  }

dlswTConnConfigIndex  OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS
 not-accessible
  STATUS     current
  DESCRIPTION
    "The index to the conceptual row of the table.
     Negative numbers are not allowed.  There
     are objects defined that point to conceptual
     rows of this table with this index value.
     Zero is used to denote that no corresponding
     row exists.

     Index values are assigned by the agent, and
     should not be reused but should continue to
     increase in value."
  ::= { dlswTConnConfigEntry 1 }

dlswTConnConfigTDomain  OBJECT-TYPE
  SYNTAX     OBJECT IDENTIFIER
```

```
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The object identifier which indicates the transport
     domain of this conceptual row."
  ::= { dlswTConnConfigEntry 2 }

dlswTConnConfigLocalTAddr  OBJECT-TYPE
  SYNTAX     TAddress
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The local transport address for this conceptual row
     of the transport connection
 definition."
  ::= { dlswTConnConfigEntry 3 }

dlswTConnConfigRemoteTAddr  OBJECT-TYPE
  SYNTAX     TAddress
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The remote transport address.  Together with
     dlswTConnConfigEntryType and dlswTConnConfigGroupDefinition,
     the object instance of this conceptual row identifies a
     collection of the transport connections that will be
     either initiated by this DLSw or initiated by a partner
     DLSw and accepted by this DLSw."
  ::= { dlswTConnConfigEntry 4 }

dlswTConnConfigLastModifyTime  OBJECT-TYPE
  SYNTAX     TimeTicks
  UNITS      "hundredths of a second"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The time (in hundredths of a second) since the value of
     any object in this conceptual row except for
     dlswTConnConfigOpens was last changed.  This value
     may be compared to dlswTConnOperConnectTime to
     determine whether
 values in this row are completely
     valid for a transport connection created using
     this row definition."
  ::= { dlswTConnConfigEntry 5 }

dlswTConnConfigEntryType  OBJECT-TYPE
  SYNTAX     INTEGER  {
```

```
      individual     (1),
      global         (2),
      group          (3)
    }
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
      "The object instance signifies the type of entry in the
      associated conceptual row.  The value of `individual'
      means that the entry applies to a specific partner DLSw
      node as identified by dlswTConnConfigRemoteTAddr and
      dlswTConnConfigTDomain.  The value of `global'
      means that the entry applies to all partner DLSw nodes
      of the TDomain.  The value of 'group' means that the entry
      applies to a specific set of DLSw nodes in the TDomain.
      Any group definitions are enterprise-specific and are pointed
      to by dlswTConnConfigGroupDefinition.  In the
   cases of
      `global' and `group', the value in dlswTConnConfigRemoteTAddr
      may not have any significance."
    ::= { dlswTConnConfigEntry 6 }

  dlswTConnConfigGroupDefinition OBJECT-TYPE
    SYNTAX     RowPointer
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
      "For conceptual rows of `individual' and `global' as
      specified in dlswTConnConfigEntryType, the instance
      of this object is  `0.0'.  For conceptual rows of
      `group', the instance points to the specific
      group definition."
    ::= { dlswTConnConfigEntry 7 }

  dlswTConnConfigSetupType  OBJECT-TYPE

    SYNTAX     INTEGER  {
      other             (1),
      activePersistent   (2),
      activeOnDemand     (3),
      passive           (4),
      excluded           (5)
    }
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
      "This value of the instance of a conceptual row
      identifies the behavior of the collection of
```

transport
connections that this conceptual row
defines. The value of activePersistent, activeOnDemand
and passive means this DLSw will accept any transport
connections, initiated by partner DLSw nodes, which
are defined by this conceptual row. The value of
activePersistent means this DLSw will also initiate
the transport connections of this conceptual row and
retry periodically if necessary. The value of
activeOnDemand means this DLSw will initiate a
transport connection of this conceptual row, if
there is a directory cache hits. The value of
other is implementation specific. The value of exclude
means that the specified node is not allowed to be
a partner to this DLSw node. To take a certain
conceptual row definition out of service, a value of
notInService for dlswTConnConfigRowStatus should be
used."
DEFVAL { passive }
::= { dlswTConnConfigEntry 8
}

dlswTConnConfigSapList OBJECT-TYPE
SYNTAX OCTET STRING (SIZE(16))
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The SAP list indicates which SAPs are advertised to
the transport connection defined by this conceptual
row. Only SAPs with even numbers are represented,
in the form of the most significant bit of the first
octet representing the SAP 0, the next most significant
bit representing the SAP 2, to the least significant
bit of the last octet representing the SAP 254. Data
link switching is allowed for those SAPs which have
one in its corresponding bit, not allowed otherwise.
The whole SAP list has to be changed together. Changing
the SAP list affects only new circuit establishments
and has no effect on established circuits.

This list can be used to restrict specific partners
from knowing about all the SAPs used by DLSw on all its

interfaces (these are represented in dlswIfSapList for
each interface). For instance, one may want to run NetBIOS
with some partners but not others.

If a node supports sending run-time capabilities exchange

```
      messages, changes to this object should cause that action.
      When to start the run-time capabilities exchange is
      implementation-specific.
      The DEFVAL below indicates support for SAPs 0, 4, 8, and C."
   DEFVAL  { 'AA000000000000000000000000000000'H }
   ::= { dlswTConnConfigEntry 9 }

dlswTConnConfigAdvertiseMacNB  OBJECT-TYPE
   SYNTAX     TruthValue
   MAX-ACCESS read-create
   STATUS     current
   DESCRIPTION
     "The value of true indicates that any defined local MAC
      addresses and NetBIOS names will be advertised to a
      partner node via initial and (if supported) run-time
      capabilities exchange messages.  The DLSw node should send
      the appropriate exclusivity control vector to accompany
       each list it sends, or to represent that the node is
      explicitly configured to have a null list.

      The value of false indicates that the DLSw node should not
      send a MAC address list or NetBIOS name list, and should
      also not send their corresponding exclusivity control
      vectors."
   DEFVAL  { true }
   ::= { dlswTConnConfigEntry 10 }

dlswTConnConfigInitCirRecvWndw  OBJECT-TYPE
   SYNTAX     INTEGER (0..65535)
   UNITS      "SSP messages"
   MAX-ACCESS read-create
   STATUS     current
   DESCRIPTION
     "The initial circuit receive pacing window size, in the unit
      of SSP messages, to be used for future transport connections
      activated using this table row.  The managed node sends this
      value as its initial receive pacing window in its initial
      capabilities exchange message.  Changing this value does not
      affect the initial circuit receive pacing window size of
      currently active
 transport connections.  If the standard window
      pacing scheme is not supported, the value is zero.

      A larger receive window value may be appropriate for partners
      that are reachable only via physical paths that have longer
      network delays."
   DEFVAL  { 1 }
   ::= { dlswTConnConfigEntry 11 }
```

```
dlswTConnConfigOpens  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "Number of times transport connections entered
     connected state according to the definition of
     this conceptual row."
  ::= { dlswTConnConfigEntry 12 }

dlswTConnConfigRowStatus  OBJECT-TYPE
  SYNTAX     RowStatus
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "This object is used by the manager to create
     or delete the row entry in the dlswTConnConfigTable
     following the RowStatus textual convention.  The value
     of notInService will be used to take a conceptual
     row
 definition out of use."
  ::= { dlswTConnConfigEntry 13 }

-- ---------------------------------------------------------------
-- Transport Connection Operation Table
-- ---------------------------------------------------------------
-- (1) At most one transport connection can be connected between
--     this DLSw and one of its DLSw partners at a given time.
-- (2) Multiple transport types are supported.
-- (3) Since the entries may be reused, dlswTConnOperEntryTime
--     needs to be consulted for the possibility of counter reset.
-- ---------------------------------------------------------------

dlswTConnOperTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswTConnOperEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "A list of transport connections.   It is optional but
     desirable for the agent to keep an entry for some
     period of time after the transport connection is
     disconnected.  This allows the manager to capture
      additional useful information about the connection, in
     particular, statistical information and the cause of the
     disconnection."
  ::= { dlswTConn 3 }
```

```
dlswTConnOperEntry  OBJECT-TYPE
  SYNTAX     DlswTConnOperEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    ""
  INDEX   { dlswTConnOperTDomain, dlswTConnOperRemoteTAddr }
  ::= { dlswTConnOperTable 1 }

DlswTConnOperEntry ::= SEQUENCE {
  dlswTConnOperTDomain               OBJECT IDENTIFIER,
  dlswTConnOperLocalTAddr             TAddress,
  dlswTConnOperRemoteTAddr            TAddress,

  dlswTConnOperEntryTime             TimeTicks,
  dlswTConnOperConnectTime            TimeTicks,
  dlswTConnOperState                 INTEGER,
  dlswTConnOperConfigIndex            INTEGER,
  dlswTConnOperFlowCntlMode           INTEGER,

  dlswTConnOperPartnerVersion         OCTET STRING,
  dlswTConnOperPartnerVendorID        OCTET STRING,
  dlswTConnOperPartnerVersionStr
     DisplayString,
  dlswTConnOperPartnerInitPacingWndw    INTEGER,

  dlswTConnOperPartnerSapList         OCTET STRING,
  dlswTConnOperPartnerNBExcl          TruthValue,
  dlswTConnOperPartnerMacExcl         TruthValue,
  dlswTConnOperPartnerNBInfo          INTEGER,
  dlswTConnOperPartnerMacInfo         INTEGER,

  dlswTConnOperDiscTime              TimeTicks,
  dlswTConnOperDiscReason             INTEGER,
  dlswTConnOperDiscActiveCir          INTEGER,

  dlswTConnOperInDataPkts            Counter32,
  dlswTConnOperOutDataPkts            Counter32,
  dlswTConnOperInDataOctets           Counter32,
  dlswTConnOperOutDataOctets          Counter32,

  dlswTConnOperInCntlPkts            Counter32,
  dlswTConnOperOutCntlPkts            Counter32,

  dlswTConnOperCURexSents             Counter32,
  dlswTConnOperICRexRcvds             Counter32,
  dlswTConnOperCURexRcvds             Counter32,
```

```
    dlswTConnOperICRexSents             Counter32,

  dlswTConnOperNQexSents              Counter32,
  dlswTConnOperNRexRcvds              Counter32,
  dlswTConnOperNQexRcvds              Counter32,
  dlswTConnOperNRexSents              Counter32,
  dlswTConnOperCirCreates             Counter32,
  dlswTConnOperCircuits               Gauge32
  }

dlswTConnOperTDomain  OBJECT-TYPE
  SYNTAX     OBJECT IDENTIFIER
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "The object identifier indicates the transport domain
      of this transport connection."
  ::= { dlswTConnOperEntry 1 }

dlswTConnOperLocalTAddr  OBJECT-TYPE
  SYNTAX     TAddress
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The local transport address for this transport connection.
      This value could be different from dlswTConnConfigLocalAddr,
      if the value of the latter were changed after this transport
      connection was
 established."
  ::= { dlswTConnOperEntry 2 }

dlswTConnOperRemoteTAddr  OBJECT-TYPE
  SYNTAX     TAddress
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "The remote transport address of this transport connection."
  ::= { dlswTConnOperEntry 3 }

dlswTConnOperEntryTime  OBJECT-TYPE
  SYNTAX     TimeTicks
  UNITS      "hundredths of a second"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The amount of time (in hundredths of a second) since this
      transport connection conceptual row was created."
  ::= { dlswTConnOperEntry 4 }
```

```
-- ...................................................................
-- DLSw Transport Connection Operational Objects
-- ...................................................................

dlswTConnOperConnectTime  OBJECT-TYPE
  SYNTAX     TimeTicks
  UNITS      "hundredths of a second"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The amount of time (in hundredths
 of a second) since this
      transport connection last entered the 'connected' state.
      A value of zero means this transport connection has never
      been established."
  ::= { dlswTConnOperEntry 5 }

dlswTConnOperState  OBJECT-TYPE
  SYNTAX     INTEGER  {
      connecting        (1),
      initCapExchange    (2),
      connected         (3),
      quiescing         (4),
      disconnecting      (5),
      disconnected       (6)
  }
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
     "The state of this transport connection.  The transport
      connection enters `connecting' state when DLSw makes
      a connection request to the transport layer.  Once initial
      Capabilities Exchange is sent, the transport connection
      enters enters `initCapExchange' state.  When partner
      capabilities have been determined and the transport
      connection is ready for sending CanUReach (CUR) messages,
      it moves
 to the `connected' state.  When DLSw is in the
      process of bringing down the connection, it is in the
      `disconnecting' state.  When the transport layer
      indicates one of its connections is disconnected, the
      transport connection moves to the `disconnected' state.

      Whereas all of the values will be returned in response
      to a management protocol retrieval operation, only two
      values may be specified in a management protocol set
      operation: `quiescing' and `disconnecting'.  Changing
```

```
      the value to `quiescing' prevents new circuits from being
      established, and will cause a transport disconnect when
      the last circuit on the connection goes away.  Changing
      the value to `disconnecting' will force off all circuits
      immediately and bring the connection to `disconnected'
      state."
  ::= { dlswTConnOperEntry 6 }

dlswTConnOperConfigIndex  OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS
 read-only
  STATUS     current
  DESCRIPTION
     "The value of dlswTConnConfigIndex of the dlswTConnConfigEntry
      that governs the configuration information used by this
      dlswTConnOperEntry.  The manager can therefore normally
      examine both configured and operational information
      for this transport connection.

      This value is zero if the corresponding dlswTConnConfigEntry
      was deleted after the creation of this dlswTConnOperEntry.
      If some fields in the former were changed but the conceptual
      row was not deleted, some configuration information may not
      be valid for this operational transport connection.  The
      manager can compare dlswTConnOperConnectTime and
      dlswTConnConfigLastModifyTime to determine if this condition
      exists."
  ::= { dlswTConnOperEntry 7 }

-- ..........................................................
-- Transport Connection Characteristics
-- ..........................................................

dlswTConnOperFlowCntlMode
 OBJECT-TYPE
  SYNTAX     INTEGER  {
    undetermined   (1),
    pacing         (2),   -- DLSw standard flow control
    other          (3)    -- non-DLSw standard flow control
  }
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The flow control mechanism in use on this transport connection.
      This value is undetermined (1) before the mode of flow control
      can be established on a new transport connection (i.e., after
      CapEx is sent but before Capex or other SSP control messages
```

```
      have been received).  Pacing (2) indicates that the standard
      RFC 1795 pacing mechanism is in use.  Other (3) may be either
      the RFC 1434+ xBusy mechanism operating to a back-level DLSw,
      or a vendor-specific flow control method.  Whether it is xBusy
      or not can be inferred from dlswTConnOperPartnerVersion."
  ::= { dlswTConnOperEntry 8 }

--
 ....................................................................

dlswTConnOperPartnerVersion  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (0 | 2))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "This value identifies which version (first octet) and release
     (second octet) of the DLSw standard is supported by this
     partner DLSw. This information is obtained from a DLSw
     capabilities exchange message received from the partner DLSw.
     A string of zero length is returned before a Capabilities
     Exchange message is received, or if one is never received.
     A conceptual row with a dlswTConnOperState of `connected' but
     a zero length partner version indicates that the partner is
     a non-standard DLSw partner.

     If an implementation chooses to keep dlswTConnOperEntrys in
     the `disconnected' state, this value should remain unchanged."
  REFERENCE
    "DLSW: Switch-to-Switch Protocol RFC 1795"

  ::= { dlswTConnOperEntry 9 }

dlswTConnOperPartnerVendorID  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (0 | 3))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "This value identifies the IEEE-assigned organizationally
     Unique Identifier (OUI) of the maker of this partner
     DLSw.  This information is obtained from a DLSw
     capabilities exchange message received from the partner DLSw.
     A string of zero length is returned before a Capabilities
     Exchange message is received, or if one is never received.

     If an implementation chooses to keep dlswTConnOperEntrys in
     the `disconnected' state, this value should remain unchanged."
  ::= { dlswTConnOperEntry 10 }
```

```
dlswTConnOperPartnerVersionStr  OBJECT-TYPE
  SYNTAX     DisplayString (SIZE (0..253))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "This value identifies the particular product version (e.g.,
     product name, code level, fix
 level) of this partner DLSw.
     The format of the actual version string is vendor-specific.
     This information is obtained from a DLSw capabilities exchange
     message received from the partner DLSw.
     A string of zero length is returned before a Capabilities
     Exchange message is received, if one is never received, or
     if one is received but it does not contain a version string.
     If an implementation chooses to keep dlswTConnOperEntrys in
     the `disconnected' state, this value should remain unchanged."
  REFERENCE
     "DLSW: Switch-to-Switch Protocol RFC 1795"
  ::= { dlswTConnOperEntry 11 }

dlswTConnOperPartnerInitPacingWndw  OBJECT-TYPE
  SYNTAX     INTEGER (0..65535)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The value of the partner initial receive pacing window.  This
     is our initial send pacing window for all new circuits on this
     transport connection, as modified and granted by
 the first flow
     control indication the partner sends on each circuit.
     This information is obtained from a DLSw capabilities exchange
     message received from the partner DLSw.
     A value of zero is returned before a Capabilities
     Exchange message is received, or if one is never received.

     If an implementation chooses to keep dlswTConnOperEntrys in
     the `disconnected' state, this value should remain unchanged."
  REFERENCE
     "DLSW: Switch-to-Switch Protocol RFC 1795"
  ::= { dlswTConnOperEntry 12 }

-- ..........................................................

dlswTConnOperPartnerSapList  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (0 | 16))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
```

"The Supported SAP List received in the capabilities
exchange message from the partner DLSw. This list has
the same format described for dlswTConnConfigSapList.
A string of zero length is
returned before a Capabilities
Exchange message is received, or if one is never received.

If an implementation chooses to keep dlswTConnOperEntrys in
the `disconnected' state, this value should remain unchanged."
::= { dlswTConnOperEntry 13 }

dlswTConnOperPartnerNBExcl OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of true signifies that the NetBIOS names received
from this partner in the NetBIOS name list in its capabilities
exchange message are the only NetBIOS names reachable by
that partner. `False' indicates that other NetBIOS names may
be reachable. `False' should be returned before a Capabilities
Exchange message is received, if one is never received, or if
one is received without a NB Name Exclusivity CV.

If an implementation chooses to keep dlswTConnOperEntrys in
the `disconnected' state, this value should remain
unchanged."
::= { dlswTConnOperEntry 14 }

dlswTConnOperPartnerMacExcl OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of true signifies that the MAC addresses received
from this partner in the MAC address list in its capabilities
exchange message are the only MAC addresses reachable by
that partner. `False' indicates that other MAC addresses may
be reachable. `False' should be returned before a Capabilities
Exchange message is received, if one is never received, or if
one is received without a MAC Address Exclusivity CV.

If an implementation chooses to keep dlswTConnOperEntrys in
the `disconnected' state, this value should remain unchanged."
::= { dlswTConnOperEntry 15 }

dlswTConnOperPartnerNBInfo OBJECT-TYPE
SYNTAX INTEGER {

```
      none          (1),  -- none is kept
      partial       (2),  -- partial list is kept

      complete      (3),  -- complete list is kept
      notApplicable  (4)
    }
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
      "It is up to this DSLw whether to keep either none, some,
       or all of the NetBIOS name list that was received in
       the capabilities exchange message sent by this partner DLSw.
       This object identifies how much information was kept by
       this DLSw.  These names are stored as userConfigured
       remote entries in dlswDirNBTable.
       A value of (4), notApplicable, should be returned before
       a Capabilities Exchange message is received, or if one is
       never received.
       If an implementation chooses to keep dlswTConnOperEntrys in
       the `disconnected' state, this value should remain unchanged."
    ::= { dlswTConnOperEntry 16 }

dlswTConnOperPartnerMacInfo  OBJECT-TYPE
    SYNTAX     INTEGER  {
      none          (1),  -- none is kept
      partial       (2),  -- partial list is kept
       complete      (3),  -- complete list is kept
      notApplicable  (4)
    }
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
      "It is up to this DLSw whether to keep either none, some,
       or all of the MAC address list that was received in the
       capabilities exchange message sent by this partner DLSw.
       This object identifies how much information was kept by
       this DLSw.  These names are stored as userConfigured
       remote entries in dlswDirMACTable.
       A value of (4), notApplicable, should be returned before
       a Capabilities Exchange message is received, or if one is
       never received.

       If an implementation chooses to keep dlswTConnOperEntrys in
       the `disconnected' state, this value should remain unchanged."
    ::= { dlswTConnOperEntry 17 }

-- ..........................................................................
-- Information about the last disconnect of this transport connection.
```

```
--   These objects
 make sense only for implementations that keep
--   transport connection information around after disconnection.
-- ..........................................................................
dlswTConnOperDiscTime  OBJECT-TYPE
  SYNTAX     TimeTicks
  UNITS      "hundredths of a second"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The amount of time (in hundredths of a second) since the
     dlswTConnOperState last entered `disconnected' state."
  ::= { dlswTConnOperEntry 18 }

dlswTConnOperDiscReason  OBJECT-TYPE
  SYNTAX     INTEGER  {
      other             (1),
      capExFailed       (2),
      transportLayerDisc (3),
      operatorCommand    (4),
      lastCircuitDiscd   (5),
      protocolError      (6)
  }
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "This object signifies the reason that either prevented the
     transport connection from entering the connected state, or
     caused the transport
 connection to enter the disconnected
     state."
  ::= { dlswTConnOperEntry 19 }

dlswTConnOperDiscActiveCir  OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of circuits active (not in DISCONNECTED state)
     at the time the transport connection was last disconnected.
     This value is zero if the transport connection has never
     been connected."
  ::= { dlswTConnOperEntry 20 }

-- ..........................................................................
-- Transport Connection Statistics
-- (1) Traffic counts
-- ..........................................................................
```

```
dlswTConnOperInDataPkts  OBJECT-TYPE
  SYNTAX     Counter32
  UNITS      "SSP messages"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of Switch-to-Switch Protocol (SSP) messages of
     type DGRMFRAME, DATAFRAME, or INFOFRAME received on this
     transport connection."
   ::= { dlswTConnOperEntry 21 }

dlswTConnOperOutDataPkts  OBJECT-TYPE
  SYNTAX     Counter32
  UNITS      "SSP messages"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of Switch-to-Switch Protocol (SSP) messages of
     type DGRMFRAME, DATAFRAME, or INFOFRAME transmitted on this
     transport connection."
  ::= { dlswTConnOperEntry 22 }

dlswTConnOperInDataOctets  OBJECT-TYPE
  SYNTAX     Counter32
  UNITS      "octets"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number octets in Switch-to-Switch Protocol (SSP) messages
     of type DGRMFRAME, DATAFRAME, or INFOFRAME received on this
     transport connection.  Each message is counted starting with
     the first octet following the SSP message header."
  ::= { dlswTConnOperEntry 23 }

dlswTConnOperOutDataOctets  OBJECT-TYPE
  SYNTAX     Counter32
  UNITS      "octets"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number octets in Switch-to-Switch Protocol (SSP) messages
     of type DGRMFRAME, DATAFRAME, or INFOFRAME transmitted on this
     transport connection.  Each message is counted starting with
     the first octet following the SSP message header."
  ::= { dlswTConnOperEntry 24 }

dlswTConnOperInCntlPkts  OBJECT-TYPE
  SYNTAX     Counter32
```

```
    UNITS      "SSP messages"
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
       "The number of Switch-to-Switch Protocol (SSP) messages
        received on this transport connection which were not of
        type DGRMFRAME, DATAFRAME, or INFOFRAME."
    ::= { dlswTConnOperEntry 25 }

dlswTConnOperOutCntlPkts  OBJECT-TYPE
    SYNTAX     Counter32
    UNITS      "SSP messages"
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
       "The number of Switch-to-Switch Protocol (SSP) messages of
        transmitted on this transport connection which were not of
        type DGRMFRAME, DATAFRAME,
 or INFOFRAME."
    ::= { dlswTConnOperEntry 26 }

-- ..........................................................
-- (2) Directory activities (Explorer messages)
-- ..........................................................

dlswTConnOperCURexSents  OBJECT-TYPE
    SYNTAX     Counter32
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
       "The number of CanUReach_ex messages sent on this transport
        connection."
    ::= { dlswTConnOperEntry 27 }

dlswTConnOperICRexRcvds  OBJECT-TYPE
    SYNTAX     Counter32
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
       "The number of ICanReach_ex messages received on this transport
        connection."
    ::= { dlswTConnOperEntry 28 }

dlswTConnOperCURexRcvds  OBJECT-TYPE
    SYNTAX     Counter32
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
```

```
      "The number of CanUReach_ex messages received on this transport
       connection."
   ::= { dlswTConnOperEntry 29 }

dlswTConnOperICRexSents
  OBJECT-TYPE
   SYNTAX     Counter32
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The number of ICanReach_ex messages sent on this transport
       connection."
   ::= { dlswTConnOperEntry 30 }

-- ..................................................................

dlswTConnOperNQexSents  OBJECT-TYPE
   SYNTAX     Counter32
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The number of NetBIOS_NQ_ex (NetBIOS Name Query-explorer)
       messages sent on this transport connection."
   ::= { dlswTConnOperEntry 31 }

dlswTConnOperNRexRcvds  OBJECT-TYPE
   SYNTAX     Counter32
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The number of NETBIOS_NR_ex (NetBIOS Name Recognized-explorer)
       messages received on this transport connection."
   ::= { dlswTConnOperEntry 32 }

dlswTConnOperNQexRcvds  OBJECT-TYPE
   SYNTAX     Counter32
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The number of NETBIOS_NQ_ex messages received on this
       transport connection."
   ::= { dlswTConnOperEntry 33 }

dlswTConnOperNRexSents  OBJECT-TYPE
   SYNTAX     Counter32
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
```

```
      "The number of NETBIOS_NR_ex messages sent on this transport
       connection."
  ::= { dlswTConnOperEntry 34 }

-- ..........................................................................
-- (3) Circuit activities on each transport connection
-- ..........................................................................
dlswTConnOperCirCreates  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of times that circuits entered `circuit_established'
      state (not counting transitions from `circuit_restart')."
  ::= { dlswTConnOperEntry 35 }

dlswTConnOperCircuits  OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
      "The number of currently active circuits on this transport
      connection, where `active' means not in `disconnected' state."
  ::= { dlswTConnOperEntry 36 }



-- ----------------------------------------------------------------------
-- Transport Connection Specific
-- ----------------------------------------------------------------------
dlswTConnSpecific OBJECT IDENTIFIER ::= { dlswTConn 4 }
dlswTConnTcp      OBJECT IDENTIFIER ::= { dlswTConnSpecific 1 }

-- ..........................................................................
-- TCP Transport Connection Specific -  Configuration
-- ..........................................................................
dlswTConnTcpConfigTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswTConnTcpConfigEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "This table defines the TCP transport connections that
      will be either initiated by or accepted by this DSLw.
      It augments the entries in dlswTConnConfigTable
 whose domain
      is dlswTCPDomain."
  ::= { dlswTConnTcp 1 }

dlswTConnTcpConfigEntry  OBJECT-TYPE
```

```
  SYNTAX     DlswTConnTcpConfigEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "Each conceptual row defines parameters that are
     specific to dlswTCPDomain transport connections."
  INDEX   { dlswTConnConfigIndex }
  ::= { dlswTConnTcpConfigTable 1 }

DlswTConnTcpConfigEntry ::= SEQUENCE {
  dlswTConnTcpConfigKeepAliveInt       INTEGER,
  dlswTConnTcpConfigTcpConnections     INTEGER,
  dlswTConnTcpConfigMaxSegmentSize     INTEGER
  }

dlswTConnTcpConfigKeepAliveInt  OBJECT-TYPE
  SYNTAX     INTEGER (0..1800)
  UNITS      "seconds"
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The time in seconds between TCP keepAlive messages when
     no traffic is flowing.  Zero signifies no keepAlive protocol.
     Changes take effect only for new TCP connections."
  DEFVAL  { 0 }
  ::= { dlswTConnTcpConfigEntry
 1 }

dlswTConnTcpConfigTcpConnections  OBJECT-TYPE
  SYNTAX     INTEGER (1..16)
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "This is our preferred number of TCP connections within a
     TCP transport connection.  The actual number used is negotiated
     at capabilities exchange time. Changes take effect only
     for new transport connections."
  DEFVAL  { 2 }
  ::= { dlswTConnTcpConfigEntry 2 }

dlswTConnTcpConfigMaxSegmentSize  OBJECT-TYPE
  SYNTAX     INTEGER (0..65535)
  UNITS      "packets"
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "This is the number of bytes that this node is
     willing to receive over the read TCP connection(s).
```

```
      Changes take effect for new transport connections."
   DEFVAL  { 4096 }
   ::= { dlswTConnTcpConfigEntry 3 }


-- ..........................................................................
-- TCP Transport Connection Specific -  Operation
-- ..........................................................................
dlswTConnTcpOperTable
  OBJECT-TYPE
   SYNTAX     SEQUENCE OF DlswTConnTcpOperEntry
   MAX-ACCESS not-accessible
   STATUS     current
   DESCRIPTION
      "A list of TCP transport connections.   It is optional
      but desirable for the agent to keep an entry for some
      period of time after the transport connection is
      disconnected.  This allows the manager to capture
      additional useful information about the connection, in
      particular, statistical information and the cause of the
      disconnection."
   ::= { dlswTConnTcp 2 }

dlswTConnTcpOperEntry  OBJECT-TYPE
   SYNTAX     DlswTConnTcpOperEntry
   MAX-ACCESS not-accessible
   STATUS     current
   DESCRIPTION
      ""
   INDEX   { dlswTConnOperTDomain, dlswTConnOperRemoteTAddr }
   ::= { dlswTConnTcpOperTable 1 }

DlswTConnTcpOperEntry ::= SEQUENCE {
   dlswTConnTcpOperKeepAliveInt            INTEGER,
   dlswTConnTcpOperPrefTcpConnections
      INTEGER,
   dlswTConnTcpOperTcpConnections          INTEGER
   }

dlswTConnTcpOperKeepAliveInt  OBJECT-TYPE
   SYNTAX     INTEGER (0..1800)
   UNITS      "seconds"
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The time in seconds between TCP keepAlive messages when
      no traffic is flowing.  Zero signifies no keepAlive protocol is
      operating."
```

```
  ::= { dlswTConnTcpOperEntry 1 }

dlswTConnTcpOperPrefTcpConnections  OBJECT-TYPE
  SYNTAX     INTEGER (1..16)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "This is the number of TCP connections preferred by this DLSw
     partner, as received in its capabilities exchange message."
  ::= { dlswTConnTcpOperEntry 2 }


dlswTConnTcpOperTcpConnections  OBJECT-TYPE
  SYNTAX     INTEGER (1..16)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "This is the actual current number of TCP connections within
     this transport connection."
   ::= { dlswTConnTcpOperEntry 3 }

-- ****************************************************************************
-- DLSW INTERFACE GROUP
-- ****************************************************************************

dlswIfTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswIfEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The list of interfaces on which DLSw is active."
  ::= { dlswInterface 1 }

dlswIfEntry  OBJECT-TYPE
  SYNTAX     DlswIfEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    ""
  INDEX   { ifIndex }
  ::= { dlswIfTable 1 }

DlswIfEntry ::= SEQUENCE {
  dlswIfRowStatus      RowStatus,
  dlswIfVirtualSegment INTEGER,
  dlswIfSapList        OCTET STRING
  }
```

```
dlswIfRowStatus  OBJECT-TYPE
  SYNTAX     RowStatus
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "This object is used by the manager to create
     or delete the row entry in the dlswIfTable
     following the
 RowStatus textual convention."
  ::= { dlswIfEntry 1 }

dlswIfVirtualSegment  OBJECT-TYPE
  SYNTAX     INTEGER (0..4095 | 65535)
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The segment number that uniquely identifies the virtual
     segment to which this DLSw interface is connected.
     Current source routing protocols limit this value to
     the range 0 - 4095. (The value 0 is used by some
     management applications for special test cases.)
     A value of 65535 signifies that no virtual segment
     is assigned to this interface.  For instance,
     in a non-source routing environment, segment number
     assignment is not required."
  DEFVAL { 65535 }
  ::= { dlswIfEntry 2 }

dlswIfSapList  OBJECT-TYPE
  SYNTAX     OCTET STRING  (SIZE(16))
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The SAP list indicates which SAPs are allowed to be
     data link switched through this interface.
 This list
     has the same format described for dlswTConnConfigSapList.

     When changes to this object take effect is implementation-
     specific.  Turning off a particular SAP can destroy
     active circuits that are using that SAP.  An agent
     implementation may reject such changes until there are no
     active circuits if it so chooses.  In this case, it is up
     to the manager to close the circuits first, using
     dlswCircuitState.

     The DEFVAL below indicates support for SAPs 0, 4, 8, and C."
  DEFVAL  { 'AA000000000000000000000000000000'H }
```

```
  ::= { dlswIfEntry 3 }


-- ********************************************************************
-- DIRECTORY
-- Directory services caches the locations of MAC addresses
-- and NetBIOS names.  For resources which are attached via
-- local interfaces, the ifIndex may be cached, and for
-- resources which are reachable via a DLSw partner, the
-- transport address of the DLSw partner is cached.
--
 ********************************************************************

-- ----------------------------------------------------------------
-- Directory Related Statistical Objects
-- ----------------------------------------------------------------
dlswDirStat     OBJECT IDENTIFIER ::= { dlswDirectory 1 }

dlswDirMacEntries  OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The current total number of entries in the dlswDirMacTable."
  ::= { dlswDirStat 1 }

dlswDirMacCacheHits  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of times a cache search for a particular MAC address
     resulted in success."
  ::= { dlswDirStat 2 }

dlswDirMacCacheMisses  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of times a cache search for a particular MAC address
     resulted in failure."
   ::= { dlswDirStat 3 }

dlswDirMacCacheNextIndex  OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS read-only
  STATUS     current
```

```
  DESCRIPTION
    "The next value of dlswDirMacIndex to be assigned by
     the agent.  A retrieval of this object atomically reserves
     the returned value for use by the manager to create a row
     in dlswDirMacTable.  This makes it possible for the agent
     to control the index space of the MAC address cache, yet
     allows the manager to administratively create new rows."
  ::= { dlswDirStat 4 }

dlswDirNBEntries  OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The current total number of entries in the dlswDirNBTable."
  ::= { dlswDirStat 5 }

dlswDirNBCacheHits  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of times a cache search for a particular NetBIOS
     name resulted
 in success."
  ::= { dlswDirStat 6 }

dlswDirNBCacheMisses  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of times a cache search for a particular NetBIOS
     name resulted in failure."
  ::= { dlswDirStat 7 }

dlswDirNBCacheNextIndex  OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The next value of dlswDirNBIndex to be assigned by the
     agent.  A retrieval of this object atomically reserves
     the returned value for use by the manager to create
     a row in dlswDirNBTable.  This makes it possible for the
     agent to control the index space for the NetBIOS name
     cache, yet allows the manager to administratively
     create new rows."
```

```
  ::= { dlswDirStat 8 }

-- ---------------------------------------------------------------
-- Directory Cache
-- ---------------------------------------------------------------
dlswDirCache
    OBJECT IDENTIFIER ::= { dlswDirectory 2 }

-- .....................................................................
-- Directory for MAC Addresses.
-- All Possible combinations of values of these objects.
--
--    EntryType   LocationType       Location        Status
--  -------------- ------------ ------------------ --------------
--  userConfigured    local     ifEntry or 0.0     reachable, or
--                                                 notReachable, or
--                                                 unknown
--  userConfigured    remote    TConnConfigEntry   reachable, or
--                                                 notReachable, or
--                                                 unknown
--  partnerCapExMsg   remote    TConnOperEntry     unknown
--  dynamic           local     ifEntry or 0.0     reachable
--  dynamic           remote    TConnOperEntry     reachable
--
-- .....................................................................
dlswDirMacTable
 OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswDirMacEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "This table contains locations of MAC addresses.
     They could be either verified or not verified,
     local or remote, and configured locally or learned
     from either Capabilities Exchange messages or
     directory searches."
  ::= { dlswDirCache 1 }

dlswDirMacEntry  OBJECT-TYPE
  SYNTAX     DlswDirMacEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "Indexed by dlswDirMacIndex."
  INDEX   { dlswDirMacIndex }
  ::= { dlswDirMacTable 1 }

DlswDirMacEntry ::= SEQUENCE {
```

```
  dlswDirMacIndex          INTEGER,
  dlswDirMacMac            MacAddressNC,
  dlswDirMacMask           MacAddressNC,
  dlswDirMacEntryType      INTEGER,
  dlswDirMacLocationType   INTEGER,
  dlswDirMacLocation       RowPointer,
  dlswDirMacStatus         INTEGER,
  dlswDirMacLFSize
   LFSize,
  dlswDirMacRowStatus      RowStatus
  }

dlswDirMacIndex  OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "Uniquely identifies a conceptual row of this table."
  ::= { dlswDirMacEntry 1 }

dlswDirMacMac  OBJECT-TYPE
  SYNTAX     MacAddressNC
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The MAC address, together with the dlswDirMacMask,
     specifies a set of MAC addresses that are defined or
     discovered through an interface or partner DLSw nodes."
  ::= { dlswDirMacEntry 2 }

dlswDirMacMask  OBJECT-TYPE
  SYNTAX     MacAddressNC
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The MAC address mask, together with the dlswDirMacMac,
     specifies a set of MAC addresses that are defined or
     discovered through an interface or partner DLSw nodes."
  DEFVAL { 'FFFFFFFFFFFF'H }
  ::= { dlswDirMacEntry 3 }

dlswDirMacEntryType
  OBJECT-TYPE
  SYNTAX     INTEGER  {
     other                 (1),
     userConfiguredPublic  (2),
     userConfiguredPrivate (3),
     partnerCapExMsg       (4),
```

```
      dynamic               (5)
    }
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
      "The cause of the creation of this conceptual row.
       It could be one of the three methods: (1) user
       configured, including via management protocol
       set operations, configuration file, command line
       or equivalent methods; (2) learned from the
       partner DLSw Capabilities Exchange messages;
       and (3) dynamic, e.g., learned from ICanReach
       messages, or LAN explorer frames.  Since only
       individual MAC addresses can be dynamically learned,
       dynamic entries will all have a mask of all FFs.

       The public versus private distinction for user-
       configured resources applies only to local resources
       (UC remote
 resources are private), and indicates
       whether that resource should be advertised in
       capabilities exchange messages sent by this node."
    DEFVAL { userConfiguredPublic }
    ::= { dlswDirMacEntry 4 }

dlswDirMacLocationType  OBJECT-TYPE
    SYNTAX     INTEGER  {
       other              (1),
       local              (2),
       remote               (3)
    }
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
      "The location of the resource (or a collection of
       resources using a mask) of this conceptual row
       is either (1) local - the resource is reachable
       via an interface, or (2) remote - the resource
       is reachable via a partner DLSw node (or a set
       of partner DLSw nodes)."
    DEFVAL { local }
    ::= { dlswDirMacEntry 5 }

dlswDirMacLocation  OBJECT-TYPE
    SYNTAX     RowPointer
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
```

```
      "Points to either the ifEntry, dlswTConnConfigEntry,
       dlswTConnOperEntry, 0.0, or something that is implementation
       specific.  It identifies the location of the MAC address
       (or the collection of MAC addresses.)"
    DEFVAL { null }
    ::= { dlswDirMacEntry 6 }

dlswDirMacStatus  OBJECT-TYPE
    SYNTAX     INTEGER  {
       unknown              (1),
       reachable            (2),
       notReachable         (3)
    }
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
      "This object specifies whether DLSw currently believes
       the MAC address to be accessible at the specified location.
       The value `notReachable' allows a configured resource
       definition to be taken out of service when a search to
       that resource fails (avoiding a repeat of the search)."
    DEFVAL { unknown }
    ::= { dlswDirMacEntry 7 }

dlswDirMacLFSize  OBJECT-TYPE
    SYNTAX     LFSize
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
      "The largest size of the MAC
 INFO field (LLC header and data)
       that a circuit to the MAC address can carry through this path."
    DEFVAL { lfs65535 }
    ::= { dlswDirMacEntry 8 }

dlswDirMacRowStatus  OBJECT-TYPE
    SYNTAX     RowStatus
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
      "This object is used by the manager to create
       or delete the row entry in the dlswDirMacTable
       following the RowStatus textual convention."
    ::= { dlswDirMacEntry 9 }

-- ..........................................................................
-- Directory for NetBIOS Names
-- All Possible combinations of values of these objects.
```

```
--
--    EntryType   LocationType       Location        Status
--  --------------- ------------ ------------------ --------------
-- userConfigured    local     ifEntry or 0.0     reachable, or
--                                    notReachable, or
--                                    unknown
-- userConfigured    remote    TConnConfigEntry
  reachable, or
--                                    notReachable, or
--                                    unknown
-- partnerCapExMsg   remote    TConnOperEntry     unknown
-- dynamic           local     ifEntry or 0.0     reachable
-- dynamic           remote    TConnOperEntry     reachable
--
-- ....................................................................
dlswDirNBTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswDirNBEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "This table contains locations of NetBIOS names.
     They could be either verified or not verified,
     local or remote, and configured locally or learned
     from either Capabilities Exchange messages or
     directory searches."
  ::= { dlswDirCache 2 }

dlswDirNBEntry  OBJECT-TYPE
  SYNTAX     DlswDirNBEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "Indexed by dlswDirNBIndex."
  INDEX   {
 dlswDirNBIndex }
  ::= { dlswDirNBTable 1 }

DlswDirNBEntry ::= SEQUENCE {
  dlswDirNBIndex          INTEGER,
  dlswDirNBName           NBName,
  dlswDirNBNameType       INTEGER,
  dlswDirNBEntryType      INTEGER,
  dlswDirNBLocationType   INTEGER,
  dlswDirNBLocation       RowPointer,
  dlswDirNBStatus         INTEGER,
  dlswDirNBLFSize         LFSize,
  dlswDirNBRowStatus      RowStatus
  }
```

```
dlswDirNBIndex  OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "Uniquely identifies a conceptual row of this table."
  ::= { dlswDirNBEntry 1 }

dlswDirNBName  OBJECT-TYPE
  SYNTAX     NBName
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The NetBIOS name (including `any char' and `wildcard'
     characters) specifies a set of NetBIOS names that are
     defined or discovered through an interface or partner
     DLSw nodes."
  ::= { dlswDirNBEntry
 2 }

dlswDirNBNameType  OBJECT-TYPE
  SYNTAX     INTEGER  {
     unknown       (1),
     individual    (2),
     group         (3)
  }
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "Whether dlswDirNBName represents an (or a set of) individual
     or group NetBIOS name(s)."
  DEFVAL { unknown }
  ::= { dlswDirNBEntry 3 }

dlswDirNBEntryType  OBJECT-TYPE
  SYNTAX     INTEGER  {
     other                 (1),
     userConfiguredPublic     (2),
     userConfiguredPrivate    (3),
     partnerCapExMsg          (4),
     dynamic               (5)
  }
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The cause of the creation of this conceptual row.
     It could be one of the three methods: (1) user
```

```
      configured, including via management protocol
      set operations, configuration file, command line,
      or equivalent methods; (2) learned from the
      partner DLSw Capabilities
 Exchange messages;
      and (3) dynamic, e.g., learned from ICanReach
      messages, or test frames.  Since only actual
      NetBIOS names can be dynamically learned, dynamic
      entries will not contain any char or wildcard
      characters.

      The public versus private distinction for user-
      configured resources applies only to local resources
      (UC remote resources are private), and indicates
      whether that resource should be advertised in
      capabilities exchange messages sent by this node."
  DEFVAL { userConfiguredPublic }
  ::= { dlswDirNBEntry 4 }

dlswDirNBLocationType  OBJECT-TYPE
  SYNTAX     INTEGER  {
      other              (1),
      local              (2),
      remote               (3)
  }
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "The location of the resource (or a collection of resources
      using any char/wildcard characters) of this conceptual row
      is either
 (1) local - the resource is reachable via an
      interface, or (2) remote - the resource is reachable via a
      a partner DLSw node (or a set of partner DLSw nodes)."
  DEFVAL { local }
  ::= { dlswDirNBEntry 5 }

dlswDirNBLocation  OBJECT-TYPE
  SYNTAX     RowPointer
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "Points to either the ifEntry, dlswTConnConfigEntry,
      dlswTConnOperEntry, 0.0, or something that is implementation
      specific.  It identifies the location of the NetBIOS name
      or the set of NetBIOS names."
  DEFVAL { null }
  ::= { dlswDirNBEntry 6 }
```

```
dlswDirNBStatus  OBJECT-TYPE
  SYNTAX     INTEGER  {
     unknown              (1),
     reachable            (2),
     notReachable         (3)
  }
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "This object specifies whether DLSw currently believes
     the NetBIOS name to be accessible at the specified location.
      The value `notReachable' allows a configured resource
     definition to be taken out of service when a search to
     that resource fails (avoiding a repeat of the search)."
  DEFVAL { unknown }
  ::= { dlswDirNBEntry 7 }

dlswDirNBLFSize  OBJECT-TYPE
  SYNTAX     LFSize
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The largest size of the MAC INFO field (LLC header and data)
     that a circuit to the NB name can carry through this path."
  DEFVAL { lfs65535 }
  ::= { dlswDirNBEntry 8 }

dlswDirNBRowStatus  OBJECT-TYPE
  SYNTAX     RowStatus
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "This object is used by manager to create
     or delete the row entry in the dlswDirNBTable
     following the RowStatus textual convention."
  ::= { dlswDirNBEntry 9 }



-- ---------------------------------------------------------------
-- Resource Locations
-- ---------------------------------------------------------------
dlswDirLocate
      OBJECT IDENTIFIER ::= { dlswDirectory 3 }

-- .....................................................................
-- Locate Entries in the dlswDirMacTable for a given MAC address
-- .....................................................................
```

```
dlswDirLocateMacTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswDirLocateMacEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "This table is used to retrieve all entries in the
     dlswDirMacTable that match a given MAC address,
     in the order of the best matched first, the
     second best matched second, and so on, till
     no more entries match the given MAC address."
  ::= { dlswDirLocate 1 }

dlswDirLocateMacEntry  OBJECT-TYPE
  SYNTAX     DlswDirLocateMacEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "Indexed by dlswDirLocateMacMac and dlswDirLocateMacMatch.
     The first object is the MAC address of interest,
 and
     the second object is the order in the list of all
     entries that match the MAC address."
  INDEX   { dlswDirLocateMacMac, dlswDirLocateMacMatch }
  ::= { dlswDirLocateMacTable 1 }

DlswDirLocateMacEntry ::= SEQUENCE {
  dlswDirLocateMacMac           MacAddressNC,
  dlswDirLocateMacMatch         INTEGER,
  dlswDirLocateMacLocation      RowPointer
  }

dlswDirLocateMacMac  OBJECT-TYPE
  SYNTAX     MacAddressNC
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The MAC address to be located."
  ::= { dlswDirLocateMacEntry 1 }

dlswDirLocateMacMatch  OBJECT-TYPE
  SYNTAX     INTEGER (1..255)
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The order of the entries of dlswDirMacTable
     that match dlswDirLocateMacMac.  A value of
     one represents the entry that best matches the
     MAC address.  A value of two represents the second
```

```
      best matched entry, and so on."

 ::= { dlswDirLocateMacEntry 2 }

dlswDirLocateMacLocation  OBJECT-TYPE
  SYNTAX     RowPointer
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "Points to the dlswDirMacEntry."
  ::= { dlswDirLocateMacEntry 3 }

-- ..........................................................................
-- Locate Entries in the dlswDirNBTable for a given NetBIOS name
-- ..........................................................................
dlswDirLocateNBTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswDirLocateNBEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "This table is used to retrieve all entries in the
     dlswDirNBTable that match a given NetBIOS name,
     in the order of the best matched first, the
     second best matched second, and so on, till
     no more entries match the given NetBIOS name."
  ::= { dlswDirLocate 2 }

dlswDirLocateNBEntry  OBJECT-TYPE
  SYNTAX     DlswDirLocateNBEntry
  MAX-ACCESS not-accessible

  STATUS     current
  DESCRIPTION
    "Indexed by dlswDirLocateNBName and dlswDirLocateNBMatch.
     The first object is the NetBIOS name of interest, and
     the second object is the order in the list of all
     entries that match the NetBIOS name."
  INDEX   { dlswDirLocateNBName, dlswDirLocateNBMatch }
  ::= { dlswDirLocateNBTable 1 }

DlswDirLocateNBEntry ::= SEQUENCE {
  dlswDirLocateNBName          NBName,
  dlswDirLocateNBMatch         INTEGER,
  dlswDirLocateNBLocation      RowPointer
  }

dlswDirLocateNBName  OBJECT-TYPE
  SYNTAX     NBName
```

```
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The NetBIOS name to be located (no any char or wildcards)."
  ::= { dlswDirLocateNBEntry 1 }

dlswDirLocateNBMatch  OBJECT-TYPE
  SYNTAX     INTEGER (1..255)
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The order of the entries of dlswDirNBTable
     that match dlswDirLocateNBName.  A value of
      one represents the entry that best matches the
     NetBIOS name.  A value of two represents the second
     best matched entry, and so on."
  ::= { dlswDirLocateNBEntry 2 }

dlswDirLocateNBLocation  OBJECT-TYPE
  SYNTAX     RowPointer
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "Points to the dlswDirNBEntry."
  ::= { dlswDirLocateNBEntry 3 }


-- ****************************************************************************
-- CIRCUIT
-- A circuit is the end-to-end association of two DLSw entities
-- through one or two DLSw nodes.  It is the concatenation of
-- two "data links", optionally with an intervening transport
-- connection. The origin of the circuit is the end station that
-- initiates the circuit.  The target of the circuit is the end
-- station that receives the initiation.
-- ****************************************************************************

-- ----------------------------------------------------------------
-- Statistics Related to
 Circuits
-- ----------------------------------------------------------------
dlswCircuitStat      OBJECT IDENTIFIER ::= { dlswCircuit 1 }

dlswCircuitStatActives  OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
```

```
      "The current number of circuits in dlswCircuitTable that are
       not in the disconnected state."
   ::= { dlswCircuitStat 1 }

dlswCircuitStatCreates  OBJECT-TYPE
   SYNTAX     Counter32
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The total number of entries ever added to dlswCircuitTable,
       or reactivated upon exiting `disconnected' state."
   ::= { dlswCircuitStat 2 }



-- ----------------------------------------------------------------
-- Circuit Table
--
-- This table is the DLSw entity's view of circuits.  There will be
-- a conceptual row in the table associated with each data link.
--
-- The chart below lists the various possible combinations of
-- origin and target MAC
 locations and the number of entries in
-- this Circuit Table:
--
--          number of       |    Origin End Station Location
--         entries in the    |---------------------------------------
--         Circuit Table     | internal     local       remote
--     ---------------------- |---------------------------------------
--     Target    | internal |     NA          2           1
--     End       | local    |     2           2           1
--     Station   | remote   |     1           1           NA
--     Location  |          |
--
--     NA: Not applicable
--
--  Note:
--  (a) IfIndex and RouteInfo are applied only if location is local.
--  (b) TDomain and TAddr are applied only if location is remote.
--
-- Most of statistics related to circuits can be collected
-- from LLC-2 Link Station Table.
-- ----------------------------------------------------------------
dlswCircuitTable  OBJECT-TYPE
   SYNTAX     SEQUENCE OF DlswCircuitEntry
   MAX-ACCESS not-accessible
   STATUS
```

```
    current
  DESCRIPTION
    "This table is the circuit representation in the DLSw
     entity. Virtual data links are used to represent any internal
     end stations.  There is a conceptual row associated with
     each data link.  Thus, for circuits without an intervening
     transport connection, there are two conceptual rows
     for each circuit.

     The table consists of the circuits being established,
     established, and as an implementation option, circuits that
     have been disconnected.  For circuits carried over
     transport connections, an entry is created after
     the CUR_cs was sent or received.  For circuits between
     two locally attached devices, or internal virtual MAC
     addresses, an entry is created when the equivalent of
     CUR_cs sent/received status is reached.

     End station 1 (S1) and End station 2 (S2) are used to
     represent the two end stations of the circuit.
     S1 is always
an end station which is locally attached.
     S2 may be locally attached or remote.  If it is locally
     attached, the circuit will be represented by two rows indexed
     by (A, B) and (B, A) where A & B are the relevant MACs/SAPs.

     The table may be used to store the causes of disconnection of
     circuits.  It is recommended that the oldest disconnected
     circuit entry be removed from this table when the memory
     space of disconnected circuits is needed."
  ::= { dlswCircuit 2 }

dlswCircuitEntry  OBJECT-TYPE
  SYNTAX     DlswCircuitEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    ""
  INDEX   { dlswCircuitS1Mac,
            dlswCircuitS1Sap,
            dlswCircuitS2Mac,
            dlswCircuitS2Sap }
  ::= { dlswCircuitTable 1 }

DlswCircuitEntry ::= SEQUENCE {
  dlswCircuitS1Mac              MacAddressNC,
  dlswCircuitS1Sap              OCTET STRING,
  dlswCircuitS1IfIndex          INTEGER,
```

```
    dlswCircuitS1DlcType          DlcType,
    dlswCircuitS1RouteInfo        OCTET STRING,
    dlswCircuitS1CircuitId        OCTET STRING,
    dlswCircuitS1Dlc              RowPointer,

    dlswCircuitS2Mac              MacAddressNC,
    dlswCircuitS2Sap              OCTET STRING,
    dlswCircuitS2Location         EndStationLocation,
    dlswCircuitS2TDomain          OBJECT IDENTIFIER,
    dlswCircuitS2TAddress         TAddress,
    dlswCircuitS2CircuitId        OCTET STRING,

    dlswCircuitOrigin             INTEGER,

    dlswCircuitEntryTime          TimeTicks,
    dlswCircuitStateTime          TimeTicks,
    dlswCircuitState              INTEGER,

    dlswCircuitPriority           INTEGER,

    dlswCircuitFCSendGrantedUnits   INTEGER,
    dlswCircuitFCSendCurrentWndw    INTEGER,
    dlswCircuitFCRecvGrantedUnits   INTEGER,
    dlswCircuitFCRecvCurrentWndw    INTEGER,
    dlswCircuitFCLargestRecvGranted Gauge32,
    dlswCircuitFCLargestSendGranted
   Gauge32,
    dlswCircuitFCHalveWndwSents     Counter32,
    dlswCircuitFCResetOpSents       Counter32,
    dlswCircuitFCHalveWndwRcvds     Counter32,
    dlswCircuitFCResetOpRcvds       Counter32,
    dlswCircuitDiscReasonLocal      INTEGER,
    dlswCircuitDiscReasonRemote     INTEGER,
    dlswCircuitDiscReasonRemoteData OCTET STRING
    }

-- ..........................................................................
-- Information related to the End Station 1 (S1).
-- ..........................................................................
dlswCircuitS1Mac  OBJECT-TYPE
    SYNTAX     MacAddressNC
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
       "The MAC Address of End Station 1 (S1) used for this circuit."
    ::= { dlswCircuitEntry 1 }

dlswCircuitS1Sap  OBJECT-TYPE
```

```
  SYNTAX     OCTET STRING (SIZE(1))
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The SAP at End Station 1 (S1) used for this circuit."
  ::= { dlswCircuitEntry 2 }

dlswCircuitS1IfIndex
 OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The ifEntry index of the local interface through which S1
     can be reached."
  ::= { dlswCircuitEntry 3 }

dlswCircuitS1DlcType  OBJECT-TYPE
  SYNTAX     DlcType
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The DLC protocol in use between the DLSw node and S1."
  ::= { dlswCircuitEntry 4 }

dlswCircuitS1RouteInfo  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (0..30))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "If source-route bridging is in use between the DLSw
     node and S1, this is the routing information field
     describing the path between the two devices.
     Otherwise the value will be an OCTET STRING of
     zero length."
  ::= { dlswCircuitEntry 5 }

dlswCircuitS1CircuitId  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (0 | 8))
  MAX-ACCESS read-only
   STATUS     current
  DESCRIPTION
    "The Circuit ID assigned by this DLSw node to this circuit.
     The first four octets are the DLC port Id, and
     the second four octets are the Data Link Correlator.
     If the DLSw SSP was not used to establish this circuit,
     the value will be a string of zero length."
  ::= { dlswCircuitEntry 6 }
```

```
dlswCircuitS1Dlc  OBJECT-TYPE
  SYNTAX     RowPointer
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "Points to a conceptual row of the underlying DLC MIB,
     which could either be the standard MIBs (e.g., the SDLC),
     or an enterprise-specific DLC MIB."
  ::= { dlswCircuitEntry 7 }

-- ..........................................................................
-- Information related to the End Station 2 (S2).
-- ..........................................................................
dlswCircuitS2Mac  OBJECT-TYPE
  SYNTAX     MacAddressNC
  MAX-ACCESS not-accessible
  STATUS     current

 DESCRIPTION
    "The MAC Address of End Station 2 (S2) used for this circuit."
  ::= { dlswCircuitEntry 8 }

dlswCircuitS2Sap  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE(1))
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The SAP at End Station 2 (S2) used for this circuit."
  ::= { dlswCircuitEntry 9 }

dlswCircuitS2Location  OBJECT-TYPE
  SYNTAX     EndStationLocation
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The location of End Station 2 (S2).
     If the location of End Station 2 is local, the
     interface information will be available in the
     conceptual row whose S1 and S2 are the S2 and
     the S1 of this conceptual row, respectively."
  ::= { dlswCircuitEntry 10 }

dlswCircuitS2TDomain  OBJECT-TYPE
  SYNTAX     OBJECT IDENTIFIER
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
```

```
      "If the location of End Station 2 is remote,
       this value is the transport domain
 of the
       transport protocol the circuit is running
       over.  Otherwise, the value is 0.0."
   ::= { dlswCircuitEntry 11 }

dlswCircuitS2TAddress  OBJECT-TYPE
   SYNTAX     TAddress
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "If the location of End Station 2 is remote,
       this object contains the address of the partner
       DLSw, else it will be an OCTET STRING of zero length."
   ::= { dlswCircuitEntry 12 }

dlswCircuitS2CircuitId  OBJECT-TYPE
   SYNTAX     OCTET STRING (SIZE (0 | 8))
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The Circuit ID assigned to this circuit by the partner
       DLSw node.  The first four octets are the DLC port Id, and
       the second four octets are the Data Link Correlator.
       If the DLSw SSP was not used to establish this circuit,
       the value will be a string of zero length."
   ::= { dlswCircuitEntry 13 }

-- ..........................................................
dlswCircuitOrigin
  OBJECT-TYPE
   SYNTAX     INTEGER  {
      s1           (1),
      s2           (2)
   }
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "This object specifies which of the two end stations
       initiated the establishment of this circuit."
   ::= { dlswCircuitEntry 14 }

-- ..........................................................
-- Operational information related to this circuit.
-- ..........................................................
dlswCircuitEntryTime  OBJECT-TYPE
   SYNTAX     TimeTicks
```

```
  UNITS      "hundredths of a second"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The amount of time (in hundredths of a second) since this
     circuit table conceptual row was created."
  ::= { dlswCircuitEntry 15 }

dlswCircuitStateTime  OBJECT-TYPE
  SYNTAX     TimeTicks
  UNITS      "hundredths of a second"
  MAX-ACCESS read-only
  STATUS     current
   DESCRIPTION
    "The amount of time (in hundredths of a second) since this
     circuit entered the current state."
  ::= { dlswCircuitEntry 16 }

dlswCircuitState  OBJECT-TYPE
  SYNTAX     INTEGER  {
      disconnected          (1),
      circuitStart          (2),
      resolvePending        (3),
      circuitPending        (4),
      circuitEstablished    (5),
      connectPending        (6),
      contactPending        (7),
      connected             (8),
      disconnectPending     (9),
      haltPending           (10),
      haltPendingNoack      (11),
      circuitRestart        (12),
      restartPending        (13)
  }
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
     "The current state of this circuit.  The agent, implementation
      specific, may choose to keep entries for some period of time
      after circuit disconnect, so the manager can gather the time
      and cause of disconnection.

       While all of the specified values may be returned from a GET
      operation, the only SETable value is `disconnectPending'.
      When this value is set, DLSw should perform the appropriate
      action given its previous state (e.g., send HALT_DL if the
      state was `connected') to bring the circuit down to the
      `disconnected' state.  Both the partner DLSw and local end
```

```
      station(s) should be notified as appropriate.

      This MIB provides no facility to re-establish a disconnected
      circuit, because in DLSw this should be an end station-driven
      function."
  ::= { dlswCircuitEntry 17 }

dlswCircuitPriority  OBJECT-TYPE
  SYNTAX     INTEGER  {
      unsupported     (1),
      low             (2),
      medium          (3),
      high            (4),
      highest         (5)
  }
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The transmission priority of this circuit as understood by
      this
 DLSw node.  This value is determined by the two DLSw
      nodes at circuit startup time.  If this DLSw node does not
      support DLSw circuit priority, the value `unsupported' should
      be returned."
  ::= { dlswCircuitEntry 18 }

-- ..........................................................................
-- Pacing Objects:
-- These objects are applicable if DLSw is using the SSP circuit
-- pacing protocol to control the flow between the two data links
-- in this circuit.
-- ..........................................................................
dlswCircuitFCSendGrantedUnits  OBJECT-TYPE
  SYNTAX     INTEGER (0..65535)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of paced SSP messages that this DLSw is currently
      authorized to send on this circuit before it must stop and
      wait for an additional flow control indication from the
      partner DLSw.

      The value zero should be returned if this circuit is not
      running
 the DLSw pacing protocol."
  ::= { dlswCircuitEntry 19 }

dlswCircuitFCSendCurrentWndw  OBJECT-TYPE
```

```
  SYNTAX     INTEGER (0..65535)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The current window size that this DLSw is using in its role
     as a data sender.  This is the value by which this DLSw would
     increase the number of messages it is authorized to send, if
     it were to receive a flow control indication with the bits
     specifying `repeat window'.
     The value zero should be returned if this circuit is not
     running the DLSw pacing protocol."
  ::= { dlswCircuitEntry 20 }

dlswCircuitFCRecvGrantedUnits  OBJECT-TYPE
  SYNTAX     INTEGER (0..65535)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The current number of paced SSP messages that this DLSw has
     authorized the partner DLSw to send on this circuit before
     the partner DLSw must stop and wait for an additional flow

    control indication from this DLSw.

     The value zero should be returned if this circuit is not
     running the DLSw pacing protocol."
  ::= { dlswCircuitEntry 21 }

dlswCircuitFCRecvCurrentWndw  OBJECT-TYPE
  SYNTAX     INTEGER (0..65535)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The current window size that this DLSw is using in its role
     as a data receiver.  This is the number of additional paced
     SSP messages that this DLSw would be authorizing its DLSw
     partner to send, if this DLSw were to send a flow control
     indication with the bits specifying `repeat window'.

     The value zero should be returned if this circuit is not
     running the DLSw pacing protocol."
  ::= { dlswCircuitEntry 22 }

dlswCircuitFCLargestRecvGranted  OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
```

"The largest receive window size granted by this DLSw during

the current activation of this circuit. This is not the
largest number of messages granted at any time, but the
largest window size as represented by FCIND operator bits.

The value zero should be returned if this circuit is not
running the DLSw pacing protocol."
::= { dlswCircuitEntry 23 }

dlswCircuitFCLargestSendGranted OBJECT-TYPE
SYNTAX Gauge32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The largest send (with respect to this DLSw) window size
granted by the partner DLSw during the current activation of
this circuit.

The value zero should be returned if this circuit is not
running the DLSw pacing protocol."
::= { dlswCircuitEntry 24 }

dlswCircuitFCHalveWndwSents OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of Halve Window operations this DLSw has sent on
this circuit, in its role as a data
receiver.

The value zero should be returned if this circuit is not
running the DLSw pacing protocol."
::= { dlswCircuitEntry 25 }

dlswCircuitFCResetOpSents OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of Reset Window operations this DLSw has sent on
this circuit, in its role as a data receiver.

The value zero should be returned if this circuit is not
running the DLSw pacing protocol."
::= { dlswCircuitEntry 26 }

```
dlswCircuitFCHalveWndwRcvds  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of Halve Window operations this DLSw has received on
     this circuit, in its role as a data sender.

     The value zero should be returned if this circuit is not
     running the DLSw pacing protocol."
  ::= { dlswCircuitEntry 27 }

dlswCircuitFCResetOpRcvds  OBJECT-TYPE
  SYNTAX     Counter32
   MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of Reset Window operations this DLSw has received on
     this circuit, in its role as a data sender.
     The value zero should be returned if this circuit is not
     running the DLSw pacing protocol."
  ::= { dlswCircuitEntry 28 }



-- ..........................................................................
-- Information about the circuit disconnection
-- ..........................................................................
dlswCircuitDiscReasonLocal  OBJECT-TYPE
  SYNTAX     INTEGER  {
     endStationDiscRcvd          (1),
     endStationDlcError          (2),
     protocolError               (3),
     operatorCommand             (4),
     haltDlRcvd                  (5),
     haltDlNoAckRcvd             (6),
     transportConnClosed         (7)
  }
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The reason why this circuit was last
 disconnected, as seen
     by this DLSw node.

     This object is present only if the agent keeps circuit
     table entries around for some period after circuit disconnect."
  ::= { dlswCircuitEntry 29 }
```

```
dlswCircuitDiscReasonRemote  OBJECT-TYPE
  SYNTAX     INTEGER  {
      unknown                   (1),
      endStationDiscRcvd          (2),
      endStationDlcError          (3),
      protocolError               (4),
      operatorCommand             (5)
  }
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The generic reason code why this circuit was last
      disconnected, as reported by the DLSw partner in a HALT_DL
      or HALT_DL_NOACK.  If the partner does not send a reason
      code in these messages, or the DLSw implementation does
      not report receiving one, the value `unknown' is returned.

      This object is present only if the agent keeps circuit table
      entries around for some period after
 circuit disconnect."
  ::= { dlswCircuitEntry 30 }

dlswCircuitDiscReasonRemoteData  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (0 | 4))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "Implementation-specific data reported by the DLSw partner in
      a HALT_DL or HALT_DL_NOACK, to help specify how and why this
      circuit was last disconnected.  If the partner does not send
      this data in these messages, or the DLSw implementation does
      not report receiving it, a string of zero length is returned.

      This object is present only if the agent keeps circuit table
      entries around for some period after circuit disconnect."
  ::= { dlswCircuitEntry 31 }



-- ..........................................................................
-- Statistics related to this circuit.
-- All statistics are in LLC-2 Link Station Statistical Table.
-- All SDLC statistics are in SDLC MIB
-- ..........................................................................



--
 ****************************************************************
-- DLSW SDLC EXTENSION
```

```
-- ********************************************************************
dlswSdlcLsEntries  OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of entries in dlswSdlcLsTable."
  ::= { dlswSdlc 1 }

-- ....................................................................
dlswSdlcLsTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswSdlcLsEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The table defines the virtual MAC addresses for those
     SDLC link stations that participate in data link switching."
  ::= { dlswSdlc 2 }

dlswSdlcLsEntry  OBJECT-TYPE
  SYNTAX     DlswSdlcLsEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The index of this table is the ifIndex value for the
     SDLC port which owns this link station and the poll
     address of
 the particular SDLC link station."
  INDEX  { ifIndex, sdlcLSAddress }
  ::= { dlswSdlcLsTable 1 }

DlswSdlcLsEntry ::= SEQUENCE {
  dlswSdlcLsLocalMac          MacAddressNC,
  dlswSdlcLsLocalSap          OCTET STRING,
  dlswSdlcLsLocalIdBlock      DisplayString,
  dlswSdlcLsLocalIdNum        DisplayString,
  dlswSdlcLsRemoteMac         MacAddressNC,
  dlswSdlcLsRemoteSap         OCTET STRING,
  dlswSdlcLsRowStatus         RowStatus
  }

dlswSdlcLsLocalMac    OBJECT-TYPE
  SYNTAX     MacAddressNC
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The virtual MAC address used to represent the SDLC-attached
     link station to the rest of the DLSw network."
```

```
  ::= { dlswSdlcLsEntry 1 }

dlswSdlcLsLocalSap    OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE(1))
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The SAP used to represent this link station."
  ::= { dlswSdlcLsEntry 2 }

dlswSdlcLsLocalIdBlock OBJECT-TYPE
   SYNTAX     DisplayString  (SIZE (0 | 3))
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The block number is the first three digits of the node_id,
     if available.  These 3 hexadecimal digits identify the
     product."
  DEFVAL { "H }
  ::= { dlswSdlcLsEntry 3 }

dlswSdlcLsLocalIdNum OBJECT-TYPE
  SYNTAX     DisplayString  (SIZE (0 | 5))
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The ID number is the last 5 digits of the node_id, if
     available.  These 5 hexadecimal digits are
     administratively defined and combined with the 3 digit
     block number form the node_id.  This node_id is used to
     identify the local node and is included in SNA XIDs."
  DEFVAL { "H }
  ::= { dlswSdlcLsEntry 4 }

dlswSdlcLsRemoteMac    OBJECT-TYPE
  SYNTAX     MacAddressNC
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The MAC address to which DLSw should attempt to
 connect
     this link station. If this information is not available,
     a length of zero for this object should be returned."
  DEFVAL { "H }
  ::= { dlswSdlcLsEntry 5 }

dlswSdlcLsRemoteSap    OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (0 | 1))
```

```
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The SAP of the remote station to which this link
     station should be connected.  If this information
     is not available, a length of zero for this object
     should be returned."
  DEFVAL { "H }
  ::= { dlswSdlcLsEntry 6 }

dlswSdlcLsRowStatus    OBJECT-TYPE
  SYNTAX     RowStatus
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "This object is used by the manager to create
     or delete the row entry in the dlswSdlcLsTable
     following the RowStatus textual convention."
  ::= { dlswSdlcLsEntry 7 }


-- ****************************************************************
-- TRAP GENERATION CONTROL
--
 ****************************************************************
dlswTrapControl OBJECT IDENTIFIER  ::= { dlswNode 10}

dlswTrapCntlTConnPartnerReject  OBJECT-TYPE
  SYNTAX     INTEGER  {
     enabled     (1),
     disabled    (2),
     partial     (3)
  }
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
    "Indicates whether the DLSw is permitted to emit partner
     reject related traps.  With the value of `enabled'
     the DLSw will emit all partner reject related traps.
     With the value of `disabled' the DLSw will not emit
     any partner reject related traps.  With the value
     of `partial' the DLSw will only emits partner reject
     traps for CapEx reject.  The changes take effect
     immediately."
  ::= { dlswTrapControl 1 }

dlswTrapCntlTConnProtViolation  OBJECT-TYPE
  SYNTAX     TruthValue
```

```
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
    "Indicates whether the DLSw is permitted to generate
     protocol-violation traps on the events such as
     window size violation.  The changes take effect
     immediately."
  ::= { dlswTrapControl 2 }

dlswTrapCntlTConn  OBJECT-TYPE
  SYNTAX     INTEGER {
     enabled     (1),
     disabled    (2),
     partial     (3)
  }
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
    "Indicates whether the DLSw is permitted to emit transport
     connection up and down traps.  With the value of `enabled'
     the DLSw will emit traps when connections enter `connected'
     and `disconnected' states.  With the value of `disabled'
     the DLSw will not emit traps when connections enter of
     `connected' and `disconnected' states.  With the value
     of `partial' the DLSw will only emits transport connection
     down traps when the connection is closed with busy.
     The changes take effect immediately."
  ::= { dlswTrapControl 3 }

dlswTrapCntlCircuit  OBJECT-TYPE
   SYNTAX     INTEGER {
     enabled     (1),
     disabled    (2),
     partial     (3)
  }
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
    "Indicates whether the DLSw is permitted to generate
     circuit up and down traps.  With the value of `enabled'
     the DLSw will emit traps when circuits enter `connected'
     and `disconnected' states.  With the value of `disabled'
     the DLSw will not emit traps when circuits enter of
     `connected' and `disconnected' states.  With the value
     of `partial' the DLSw will emit traps only for those
     circuits that are initiated by this DLSw, e.g.,
     originating the CUR_CS message.  The changes take effect
     immediately."
```

```
  ::= { dlswTrapControl 4 }

-- ****************************************************************
-- NOTIFICATIONS, i.e., TRAP DEFINITIONS
-- ****************************************************************
dlswTraps             OBJECT IDENTIFIER
 ::= { dlswMIB 0 }

-- ---------------------------------------------------------------
-- This section defines the well-known notifications sent by
-- DLSW agents.
-- Care must be taken to insure that no particular notification
-- is sent to a single receiving entity more often than once
-- every five seconds.
--
-- Traps includes:
-- (1) Partner rejected (capEx rejection, not in partner list, etc.)
-- (2) DLSw protocol violation (e.g., window size violation, etc.)
-- (3) Transport connection up/down

-- (4) Circuit up/down
-- ---------------------------------------------------------------
--

dlswTrapTConnPartnerReject NOTIFICATION-TYPE
  OBJECTS { dlswTConnOperTDomain, dlswTConnOperRemoteTAddr
  }
  STATUS     current
  DESCRIPTION
    "This trap is sent each time a transport connection
     is rejected by a partner DLSw during Capabilities
     Exchanges.  The emission of this trap is controlled
     by dlswTrapCntlTConnPartnerReject."
  ::= { dlswTraps
 1 }

dlswTrapTConnProtViolation NOTIFICATION-TYPE
  OBJECTS { dlswTConnOperTDomain, dlswTConnOperRemoteTAddr
  }
  STATUS     current
  DESCRIPTION
    "This trap is sent each time a protocol violation is
     detected for a transport connection.  The emission of this
     trap is controlled by dlswTrapCntlTConnProtViolation."
  ::= { dlswTraps 2 }

dlswTrapTConnUp NOTIFICATION-TYPE
  OBJECTS { dlswTConnOperTDomain, dlswTConnOperRemoteTAddr
```

```
  }
  STATUS     current
  DESCRIPTION
     "This trap is sent each time a transport connection
      enters `connected' state.  The emission of this trap
      is controlled by dlswTrapCntlTConn."
  ::= { dlswTraps 3 }

dlswTrapTConnDown NOTIFICATION-TYPE
  OBJECTS { dlswTConnOperTDomain, dlswTConnOperRemoteTAddr
  }
  STATUS     current
  DESCRIPTION
     "This trap is sent each time a transport connection
      enters `disconnected' state.  The emission of this trap
      is controlled by dlswTrapCntlTConn."
   ::= { dlswTraps 4 }

dlswTrapCircuitUp NOTIFICATION-TYPE
  OBJECTS { dlswCircuitS1Mac, dlswCircuitS1Sap,
            dlswCircuitS2Mac, dlswCircuitS2Sap
  }
  STATUS     current
  DESCRIPTION
     "This trap is sent each time a circuit enters `connected'
      state.  The emission of this trap is controlled by
      dlswTrapCntlCircuit."
  ::= { dlswTraps 5 }

dlswTrapCircuitDown NOTIFICATION-TYPE
  OBJECTS { dlswCircuitS1Mac, dlswCircuitS1Sap,
            dlswCircuitS2Mac, dlswCircuitS2Sap
  }
  STATUS     current
  DESCRIPTION
     "This trap is sent each time a circuit enters `disconnected'
      state.  The emission of this trap is controlled by
      dlswTrapCntlCircuit."
  ::= { dlswTraps 6 }


-- ****************************************************************
-- CONFORMANCE INFORMATION
-- ****************************************************************
dlswConformance       OBJECT IDENTIFIER ::= { dlsw 3 }

dlswCompliances
```

```
       OBJECT IDENTIFIER ::= { dlswConformance 1 }
dlswGroups          OBJECT IDENTIFIER ::= { dlswConformance 2 }

-- ----------------------------------------------------------------
-- COMPLIANCE STATEMENTS
-- ----------------------------------------------------------------

-- ..................................................................
-- Core compliance for all DLSw entities
-- ..................................................................
dlswCoreCompliance MODULE-COMPLIANCE
  STATUS current
  DESCRIPTION
    "The core compliance statement for all DLSw nodes."
  MODULE
     MANDATORY-GROUPS  {
           dlswNodeGroup,
           dlswTConnStatGroup,
           dlswTConnConfigGroup,
           dlswTConnOperGroup,
           dlswInterfaceGroup,
           dlswCircuitGroup,
           dlswCircuitStatGroup,
           dlswNotificationGroup }

     GROUP dlswNodeNBGroup
        DESCRIPTION

     "The DLSw NetBIOS Node group is mandatory only for
           those DLSw entities that implement NetBIOS."

     GROUP dlswTConnNBGroup
        DESCRIPTION
          "The DLSw NetBIOS Transport Connection group is
           mandatory only for those DLSw entities that
           implement NetBIOS."

     OBJECT  dlswNodeStatus
        MIN-ACCESS  read-only
        DESCRIPTION
           "Write access is not required."

     OBJECT  dlswNodeVirtualSegmentLFSize
        MIN-ACCESS  read-only
        DESCRIPTION
           "Write access is not required."

     OBJECT  dlswNodeResourceNBExclusivity
```

MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswNodeResourceMacExclusivity
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTrapCntlTConnPartnerReject
MIN-ACCESS
read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTrapCntlTConnProtViolation
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTrapCntlTConn
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."
OBJECT dlswTrapCntlCircuit
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigTDomain
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigLocalTAddr
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigRemoteTAddr
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigEntryType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigGroupDefinition
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigSetupType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigSapList
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigAdvertiseMacNB
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigInitCirRecvWndw
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is
not required."

OBJECT dlswTConnOperState
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswIfRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswIfVirtualSegment
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswIfSapList

```
        MIN-ACCESS  read-only
        DESCRIPTION
            "Write access is not required."

      OBJECT  dlswCircuitState
        MIN-ACCESS  read-only
        DESCRIPTION
            "Write access is not required."

  ::= { dlswCompliances 1 }

-- ..........................................................
-- Compliance for all DLSw entities that provide TCP transport.
-- ..........................................................
dlswTConnTcpCompliance MODULE-COMPLIANCE

 STATUS current
  DESCRIPTION
    "Compliance for DLSw nodes that use TCP as a
    transport connection protocol."
  MODULE
    MANDATORY-GROUPS  {
          dlswTConnTcpConfigGroup,
          dlswTConnTcpOperGroup }

    OBJECT  dlswTConnTcpConfigKeepAliveInt
      MIN-ACCESS  read-only
      DESCRIPTION
          "Write access is not required."

    OBJECT  dlswTConnTcpConfigTcpConnections
      MIN-ACCESS  read-only
      DESCRIPTION
          "Write access is not required."

    OBJECT  dlswTConnTcpConfigMaxSegmentSize
      MIN-ACCESS  read-only
      DESCRIPTION
          "Write access is not required."

  ::= { dlswCompliances 2 }

-- ..........................................................
-- Compliance for all DLSw Entities that implement a directory
-- ..........................................................
dlswDirCompliance MODULE-COMPLIANCE
  STATUS current
```

```
 DESCRIPTION
   "Compliance for DLSw nodes that provide a directory
   function."
MODULE
   MANDATORY-GROUPS  {
         dlswDirGroup }

   GROUP dlswDirNBGroup
      DESCRIPTION
        "The DLSw NetBIOS group is mandatory only for
         those DLSw entities that implement NetBIOS."

   OBJECT  dlswDirMacMac
      MIN-ACCESS  read-only
      DESCRIPTION
         "Write access is not required."

   OBJECT  dlswDirMacMask
      MIN-ACCESS  read-only
      DESCRIPTION
         "Write access is not required."

   OBJECT  dlswDirMacEntryType
      MIN-ACCESS  read-only
      DESCRIPTION
         "Write access is not required."
   OBJECT  dlswDirMacLocationType
      MIN-ACCESS  read-only
      DESCRIPTION
         "Write access is not required."

   OBJECT  dlswDirMacLocation
      MIN-ACCESS  read-only
      DESCRIPTION
          "Write access is not required."

   OBJECT  dlswDirMacStatus
      MIN-ACCESS  read-only
      DESCRIPTION
         "Write access is not required."

   OBJECT  dlswDirMacLFSize
      MIN-ACCESS  read-only
      DESCRIPTION
         "Write access is not required."

   OBJECT  dlswDirMacRowStatus
      MIN-ACCESS  read-only
```

```
        DESCRIPTION
            "Write access is not required."

        OBJECT  dlswDirNBName
            MIN-ACCESS  read-only
            DESCRIPTION
            "Write access is not required."

        OBJECT  dlswDirNBNameType
            MIN-ACCESS  read-only
            DESCRIPTION
            "Write access is not required."

        OBJECT  dlswDirNBEntryType
            MIN-ACCESS  read-only
            DESCRIPTION
            "Write access is not required."

        OBJECT  dlswDirNBLocationType
            MIN-ACCESS  read-only
            DESCRIPTION

      "Write access is not required."

        OBJECT  dlswDirNBLocation
            MIN-ACCESS  read-only
            DESCRIPTION
            "Write access is not required."

        OBJECT  dlswDirNBStatus
            MIN-ACCESS  read-only
            DESCRIPTION
            "Write access is not required."

        OBJECT  dlswDirNBLFSize
            MIN-ACCESS  read-only
            DESCRIPTION
            "Write access is not required."

        OBJECT  dlswDirNBRowStatus
            MIN-ACCESS  read-only
            DESCRIPTION
            "Write access is not required."

    ::= { dlswCompliances 3 }

-- ..........................................................................
-- Compliance for all DLSw entities that provide an ordered
```

```
-- list of directory entries that match a resource
-- ..................................................................
dlswDirLocateCompliance MODULE-COMPLIANCE
  STATUS current
  DESCRIPTION
    "Compliance for DLSw nodes that provide
 an ordered
     list of directory entries for a given resource."
  MODULE
     MANDATORY-GROUPS  {
          dlswDirLocateGroup }

     GROUP dlswDirLocateNBGroup
        DESCRIPTION
          "The DLSw NetBIOS group is mandatory only for
           those DLSw entities that implement NetBIOS."

  ::= { dlswCompliances 4 }

-- ..................................................................
-- Compliance for all DLSw entities that support SDLC end stations
-- ..................................................................
dlswSdlcCompliance MODULE-COMPLIANCE
  STATUS current
  DESCRIPTION
    "Compliance for DLSw nodes that support SDLC."
  MODULE
     MANDATORY-GROUPS  {
          dlswSdlcGroup }

     OBJECT  dlswSdlcLsLocalMac
        MIN-ACCESS  read-only
        DESCRIPTION
          "Write access is not required."

     OBJECT  dlswSdlcLsLocalSap
        MIN-ACCESS  read-only
        DESCRIPTION
           "Write access is not required."

     OBJECT  dlswSdlcLsLocalIdBlock
        MIN-ACCESS  read-only
        DESCRIPTION
          "Write access is not required."

     OBJECT  dlswSdlcLsLocalIdNum
        MIN-ACCESS  read-only
        DESCRIPTION
```

```
            "Write access is not required."

        OBJECT  dlswSdlcLsRemoteMac
          MIN-ACCESS  read-only
          DESCRIPTION
            "Write access is not required."

        OBJECT  dlswSdlcLsRemoteSap
          MIN-ACCESS  read-only
          DESCRIPTION
            "Write access is not required."

        OBJECT  dlswSdlcLsRowStatus
          MIN-ACCESS  read-only
          DESCRIPTION
            "Write access is not required."

    ::= { dlswCompliances 5 }

-- ---------------------------------------------------------------
-- CONFORMANCE GROUPS
-- ---------------------------------------------------------------

-- ..............................................................
--
 Node Conformance Group
-- ..............................................................
dlswNodeGroup  OBJECT-GROUP
    OBJECTS  {
        dlswNodeVersion,
        dlswNodeVendorID,
        dlswNodeVersionString,
        dlswNodeStdPacingSupport,
        dlswNodeStatus,
        dlswNodeUpTime,
        dlswNodeVirtualSegmentLFSize,
        dlswNodeResourceMacExclusivity,
        dlswTrapCntlTConnPartnerReject,
        dlswTrapCntlTConnProtViolation,
        dlswTrapCntlTConn,
        dlswTrapCntlCircuit
        }
    STATUS current
    DESCRIPTION
      "Conformance group for DLSw node general information."
    ::= { dlswGroups 1 }

-- ..............................................................
```

```
dlswNodeNBGroup  OBJECT-GROUP
  OBJECTS  {
     dlswNodeResourceNBExclusivity
     }
  STATUS current
  DESCRIPTION
    "Conformance group for DLSw node general information
     specifically for nodes that support NetBIOS."
  ::=
 { dlswGroups 2 }

-- ..........................................................................
dlswTConnStatGroup  OBJECT-GROUP
  OBJECTS  {
     dlswTConnStatActiveConnections,
     dlswTConnStatCloseIdles,
     dlswTConnStatCloseBusys
     }
  STATUS current
  DESCRIPTION
    "Conformance group for statistics for transport
     connections."
  ::= { dlswGroups 3 }

-- ..........................................................................
dlswTConnConfigGroup  OBJECT-GROUP
  OBJECTS  {
     dlswTConnConfigTDomain,
     dlswTConnConfigLocalTAddr,
     dlswTConnConfigRemoteTAddr,
     dlswTConnConfigLastModifyTime,
     dlswTConnConfigEntryType,
     dlswTConnConfigGroupDefinition,
     dlswTConnConfigSetupType,
     dlswTConnConfigSapList,
     dlswTConnConfigAdvertiseMacNB,
     dlswTConnConfigInitCirRecvWndw,
     dlswTConnConfigOpens,
     dlswTConnConfigRowStatus
     }
  STATUS current
  DESCRIPTION
    "Conformance
 group for the configuration of
     transport connections."
  ::= { dlswGroups 4 }

-- ..........................................................................
```

```
dlswTConnOperGroup  OBJECT-GROUP
  OBJECTS  {
     dlswTConnOperLocalTAddr,
     dlswTConnOperEntryTime,
     dlswTConnOperConnectTime,
     dlswTConnOperState,
     dlswTConnOperConfigIndex,
     dlswTConnOperFlowCntlMode,
     dlswTConnOperPartnerVersion,
     dlswTConnOperPartnerVendorID,
     dlswTConnOperPartnerVersionStr,
     dlswTConnOperPartnerInitPacingWndw,
     dlswTConnOperPartnerSapList,
     dlswTConnOperPartnerMacExcl,
     dlswTConnOperPartnerMacInfo,
     dlswTConnOperDiscTime,
     dlswTConnOperDiscReason,
     dlswTConnOperDiscActiveCir,
     dlswTConnOperInDataPkts,
     dlswTConnOperOutDataPkts,
     dlswTConnOperInDataOctets,
     dlswTConnOperOutDataOctets,
     dlswTConnOperInCntlPkts,
     dlswTConnOperOutCntlPkts,
     dlswTConnOperCURexSents,
      dlswTConnOperICRexRcvds,
     dlswTConnOperCURexRcvds,
     dlswTConnOperICRexSents,
     dlswTConnOperCirCreates,
     dlswTConnOperCircuits
     }
  STATUS current
  DESCRIPTION
    "Conformance group for operation information for
    transport connections."
  ::= { dlswGroups 5 }
-- ..........................................................
dlswTConnNBGroup  OBJECT-GROUP
  OBJECTS  {
     dlswTConnOperPartnerNBExcl,
     dlswTConnOperPartnerNBInfo,
     dlswTConnOperNQexSents,
     dlswTConnOperNRexRcvds,
     dlswTConnOperNQexRcvds,
     dlswTConnOperNRexSents
     }
  STATUS current
  DESCRIPTION
```

```
      "Conformance group for operation information for
       transport connections, specifically for nodes
       that support NetBIOS."
   ::= { dlswGroups 6 }

-- ..........................................................................
dlswTConnTcpConfigGroup  OBJECT-GROUP
   OBJECTS  {
       dlswTConnTcpConfigKeepAliveInt,
        dlswTConnTcpConfigTcpConnections,
       dlswTConnTcpConfigMaxSegmentSize
       }
   STATUS current
   DESCRIPTION
      "Conformance group for configuration information for
       transport connections using TCP."
   ::= { dlswGroups 7 }

-- ..........................................................................
dlswTConnTcpOperGroup  OBJECT-GROUP
   OBJECTS  {
       dlswTConnTcpOperKeepAliveInt,
       dlswTConnTcpOperPrefTcpConnections,
       dlswTConnTcpOperTcpConnections
       }
   STATUS current
   DESCRIPTION
      "Conformance group for operation information for
       transport connections using TCP."
   ::= { dlswGroups 8 }

-- ..........................................................................
dlswInterfaceGroup  OBJECT-GROUP
   OBJECTS  {
       dlswIfRowStatus,
       dlswIfVirtualSegment,
       dlswIfSapList
       }
   STATUS current
   DESCRIPTION
      "Conformance group for DLSw interfaces."
   ::= { dlswGroups
 9 }

-- ..........................................................................
dlswDirGroup  OBJECT-GROUP
   OBJECTS  {
       dlswDirMacEntries,
```

```
      dlswDirMacCacheHits,
      dlswDirMacCacheMisses,
      dlswDirMacCacheNextIndex,
      dlswDirMacMac,
      dlswDirMacMask,
      dlswDirMacEntryType,
      dlswDirMacLocationType,
      dlswDirMacLocation,
      dlswDirMacStatus,
      dlswDirMacLFSize,
      dlswDirMacRowStatus
      }
  STATUS current
  DESCRIPTION
    "Conformance group for DLSw directory using MAC
     addresses."
  ::= { dlswGroups 10 }

-- ..........................................................................
dlswDirNBGroup  OBJECT-GROUP
  OBJECTS  {
      dlswDirNBEntries,
      dlswDirNBCacheHits,
      dlswDirNBCacheMisses,
      dlswDirNBCacheNextIndex,
      dlswDirNBName,
      dlswDirNBNameType,
      dlswDirNBEntryType,
      dlswDirNBLocationType,
      dlswDirNBLocation,
      dlswDirNBStatus,
       dlswDirNBLFSize,
      dlswDirNBRowStatus
      }
  STATUS current
  DESCRIPTION
    "Conformance group for DLSw directory using NetBIOS
     names."
  ::= { dlswGroups 11 }

-- ..........................................................................
dlswDirLocateGroup  OBJECT-GROUP
  OBJECTS  {
      dlswDirLocateMacLocation
      }
  STATUS current
  DESCRIPTION
    "Conformance group for a node that can return directory
```

```
      entry order for a given MAC address."
  ::= { dlswGroups 12 }

-- ....................................................................
dlswDirLocateNBGroup  OBJECT-GROUP
  OBJECTS  {
     dlswDirLocateNBLocation
     }
  STATUS current
  DESCRIPTION
    "Conformance group for a node that can return directory
     entry order for a given NetBIOS name."
  ::= { dlswGroups 13 }

-- ....................................................................
dlswCircuitStatGroup  OBJECT-GROUP
  OBJECTS  {
     dlswCircuitStatActives,
      dlswCircuitStatCreates
     }
  STATUS current
  DESCRIPTION
    "Conformance group for statistics about circuits."
  ::= { dlswGroups 14 }

-- ....................................................................
dlswCircuitGroup  OBJECT-GROUP
  OBJECTS  {
     dlswCircuitS1IfIndex,
     dlswCircuitS1DlcType,
     dlswCircuitS1RouteInfo,
     dlswCircuitS1CircuitId,
     dlswCircuitS1Dlc,
     dlswCircuitS2Location,
     dlswCircuitS2TDomain,
     dlswCircuitS2TAddress,
     dlswCircuitS2CircuitId,
     dlswCircuitOrigin,
     dlswCircuitEntryTime,
     dlswCircuitStateTime,
     dlswCircuitState,
     dlswCircuitPriority,
     dlswCircuitFCSendGrantedUnits,
     dlswCircuitFCSendCurrentWndw,
     dlswCircuitFCRecvGrantedUnits,
     dlswCircuitFCRecvCurrentWndw,
     dlswCircuitFCLargestRecvGranted,
     dlswCircuitFCLargestSendGranted,
```

```
      dlswCircuitFCHalveWndwSents,
      dlswCircuitFCResetOpSents,
       dlswCircuitFCHalveWndwRcvds,
      dlswCircuitFCResetOpRcvds,
      dlswCircuitDiscReasonLocal,
      dlswCircuitDiscReasonRemote,
      dlswCircuitDiscReasonRemoteData
      }
  STATUS current
  DESCRIPTION
    "Conformance group for DLSw circuits."
  ::= { dlswGroups 15 }

-- ..........................................................
dlswSdlcGroup  OBJECT-GROUP
  OBJECTS  {
      dlswSdlcLsEntries,
      dlswSdlcLsLocalMac,
      dlswSdlcLsLocalSap,
      dlswSdlcLsLocalIdBlock,
      dlswSdlcLsLocalIdNum,
      dlswSdlcLsRemoteMac,
      dlswSdlcLsRemoteSap,
      dlswSdlcLsRowStatus
      }
  STATUS current
  DESCRIPTION
    "Conformance group for DLSw SDLC support."
  ::= { dlswGroups 16 }

-- ..........................................................
dlswNotificationGroup  NOTIFICATION-GROUP
  NOTIFICATIONS  {
      dlswTrapTConnPartnerReject,
      dlswTrapTConnProtViolation,

     dlswTrapTConnUp,
      dlswTrapTConnDown,
      dlswTrapCircuitUp,
      dlswTrapCircuitDown
      }
  STATUS current
  DESCRIPTION
    "Conformance group for DLSw notifications."
  ::= { dlswGroups 17 }

END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/DLSW-MIB
No license file was found, but licenses were detected in source scan.

```
SIP-COMMON-MIB DEFINITIONS ::= BEGIN

IMPORTS
  MODULE-IDENTITY,
  OBJECT-TYPE,
  NOTIFICATION-TYPE,
  Counter32,
  Gauge32,
  TimeTicks,
  Unsigned32,


  mib-2
      FROM SNMPv2-SMI            -- RFC 2578

  RowStatus,
  TimeStamp,
  TruthValue
      FROM SNMPv2-TC             -- RFC 2579

  MODULE-COMPLIANCE,
  OBJECT-GROUP,
  NOTIFICATION-GROUP
      FROM SNMPv2-CONF           -- RFC 2580

  SnmpAdminString
      FROM SNMP-FRAMEWORK-MIB    -- RFC 3411

  SipTCTransportProtocol,
  SipTCMethodName,
  SipTCEntityRole,
  SipTCOptionTagHeaders
      FROM SIP-TC-MIB            -- RFC 4780

  applIndex
      FROM NETWORK-SERVICES-MIB  -- RFC 2788

  InetPortNumber
      FROM INET-ADDRESS-MIB;     -- RFC 4001

sipCommonMIB MODULE-IDENTITY
  LAST-UPDATED "200704200000Z"
  ORGANIZATION "IETF Session Initiation Protocol Working Group"
  CONTACT-INFO
```

"SIP WG email: sip@ietf.org

Co-editor Kevin Lingle
Cisco Systems, Inc.
postal: 7025 Kit Creek Road
P.O. Box 14987
Research Triangle Park, NC 27709
USA
email: klingle@cisco.com
phone: +1 919 476 2029

Co-editor Joon Maeng
email: jmaeng@austin.rr.com

Co-editor Jean-Francois Mule
CableLabs

postal: 858 Coal Creek Circle
Louisville, CO 80027
USA
email: jf.mule@cablelabs.com
phone: +1 303 661 9100

Co-editor Dave Walker
email: drwalker@rogers.com"
DESCRIPTION
"Session Initiation Protocol (SIP) Common MIB module. This
module defines objects that may be common to all SIP entities.

SIP is an application-layer signaling protocol for creating,
modifying and terminating multimedia sessions with one or more
participants. These sessions include Internet multimedia
conferences and Internet telephone calls. SIP is defined in
RFC 3261 (June 2002).

This MIB is defined for managing objects that are common to
SIP User Agents (UAs), Proxy, Redirect, and Registrar servers.
Objects specific to each of these entities MAY be managed using
entity specific MIBs defined in other modules.

Copyright (C) The IETF Trust (2007). This version of
this MIB module is part of RFC 4780; see the RFC itself for
full legal notices."
REVISION "200704200000Z"
DESCRIPTION
"Initial version of the IETF SIP-COMMON-MIB module. This
version published as part of RFC 4780."

```
   ::= { mib-2 149 }

-- Top-Level Components of this MIB.
sipCommonMIBNotifications OBJECT IDENTIFIER
 ::= { sipCommonMIB 0 }
sipCommonMIBObjects       OBJECT IDENTIFIER ::= { sipCommonMIB 1 }
sipCommonMIBConformance   OBJECT IDENTIFIER ::= { sipCommonMIB 2 }

--
-- This MIB contains objects that are common to all SIP entities.
--

-- Common basic configuration
sipCommonCfgBase       OBJECT IDENTIFIER ::= { sipCommonMIBObjects 1 }

-- Protocol timer configuration
sipCommonCfgTimer      OBJECT IDENTIFIER ::= { sipCommonMIBObjects 2 }

-- SIP message summary statistics


sipCommonSummaryStats  OBJECT IDENTIFIER ::= { sipCommonMIBObjects 3 }

-- Per method statistics
sipCommonMethodStats   OBJECT IDENTIFIER ::= { sipCommonMIBObjects 4 }

-- Per Status code or status code class statistics
sipCommonStatusCode    OBJECT IDENTIFIER ::= { sipCommonMIBObjects 5 }

-- Transaction statistics
sipCommonStatsTrans    OBJECT IDENTIFIER ::= { sipCommonMIBObjects 6 }

-- Method retry statistics
sipCommonStatsRetry    OBJECT IDENTIFIER ::= { sipCommonMIBObjects 7 }

-- Other statistics
sipCommonOtherStats
   OBJECT IDENTIFIER ::= { sipCommonMIBObjects 8 }

-- Accessible-for-notify objects
sipCommonNotifObjects  OBJECT IDENTIFIER ::= { sipCommonMIBObjects 9 }

--
-- Common Configuration Objects
--
sipCommonCfgTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SipCommonCfgEntry
  MAX-ACCESS  not-accessible
```

```
  STATUS      current
  DESCRIPTION
    "This table contains the common configuration objects applicable
     to all SIP entities."
  ::= { sipCommonCfgBase 1 }

sipCommonCfgEntry OBJECT-TYPE
  SYNTAX      SipCommonCfgEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "A row of common configuration.

     Each row represents objects for a particular SIP entity
     instance present in this system.  applIndex is used to uniquely
     identify these instances of SIP entities and correlate them
     through the common framework of the NETWORK-SERVICES-MIB (RFC
     2788)."
  INDEX { applIndex }
  ::= { sipCommonCfgTable 1
 }

SipCommonCfgEntry ::= SEQUENCE {


     sipCommonCfgProtocolVersion      SnmpAdminString,
     sipCommonCfgServiceOperStatus    INTEGER,
     sipCommonCfgServiceStartTime     TimeTicks,
     sipCommonCfgServiceLastChange    TimeTicks,
     sipCommonCfgOrganization         SnmpAdminString,
     sipCommonCfgMaxTransactions      Unsigned32,
     sipCommonCfgServiceNotifEnable   BITS,
     sipCommonCfgEntityType           SipTCEntityRole
  }

sipCommonCfgProtocolVersion OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object will reflect the version of SIP supported by this
     SIP entity.  It will follow the same format as SIP version
     information contained in the SIP messages generated by this SIP
     entity.  For example, entities supporting SIP version 2 will
     return 'SIP/2.0' as dictated by the standard."
  REFERENCE
    "RFC 3261, Section 7.1"
  ::= { sipCommonCfgEntry
```

```
 1 }

sipCommonCfgServiceOperStatus OBJECT-TYPE
  SYNTAX      INTEGER {
                unknown(1),
                up(2),
                down(3),
                congested(4),
                restarting(5),
                quiescing(6),
                testing(7)
              }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object contains the current operational state of
     the SIP application.

     unknown    : The operational status cannot be determined
                  for some reason.
     up         : The application is operating normally and is
                  processing (receiving and possibly issuing) SIP
                  requests and responses.
     down       : The application is currently unable to process
                  SIP messages.
     congested  : The application is operational but no additional




                  inbound transactions can be accommodated at the
                   moment.
     restarting : The application is currently unavailable, but it
                  is in the process of restarting and will
                  presumably, soon be able to process SIP messages.
     quiescing  : The application is currently operational
                  but has been administratively put into
                  quiescence mode.  Additional inbound
                  transactions MAY be rejected.
     testing    : The application is currently in test mode
                  and MAY not be able to process SIP messages.

     The operational status values defined for this object are not
     based on any specific information contained in the SIP
     standard."
  ::= { sipCommonCfgEntry 2 }

sipCommonCfgServiceStartTime OBJECT-TYPE
  SYNTAX      TimeTicks
```

```
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The value of sysUpTime at the time the SIP entity was last
     started.  If
 started prior to the last re-initialization of the
     local network management subsystem, then this object contains a
     zero value."
  ::= { sipCommonCfgEntry 3 }

sipCommonCfgServiceLastChange OBJECT-TYPE
  SYNTAX      TimeTicks
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The value of sysUpTime at the time the SIP entity entered its
     current operational state.  If the current state was entered
     prior to the last re-initialization of the local network
     management subsystem, then this object contains a zero value."
  ::= { sipCommonCfgEntry 4 }

sipCommonCfgOrganization OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object contains the organization name that the SIP entity
     inserts into Organization headers of SIP messages processed by
     this system.  If the string is empty, no Organization header is
     to be generated."




  REFERENCE
    "RFC 3261, Section 20.25"
  ::= { sipCommonCfgEntry 5 }

sipCommonCfgMaxTransactions OBJECT-TYPE
  SYNTAX      Unsigned32 (1..4294967295)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object indicates the maximum number of simultaneous
     transactions per second that the SIP entity can manage.  In
     general, the value of this object SHOULD reflect a level of
     transaction processing per second that is considered high
     enough to impact the system's CPU and/or memory resources to
```

```
      the point of deteriorating SIP call processing but not high
      enough to cause catastrophic system failure."
    ::= { sipCommonCfgEntry 6 }

sipCommonCfgServiceNotifEnable OBJECT-TYPE
    SYNTAX      BITS {
                  sipCommonServiceColdStart(0),
                  sipCommonServiceWarmStart(1),
                  sipCommonServiceStatusChanged(2)
                }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
      "This object specifies which SIP service related notifications
      are enabled.  Each bit represents a specific notification.  If
      a bit has a value 1, the associated notification is enabled and
      will be generated by the SIP entity at the appropriate time.

      Support for these notifications is OPTIONAL: either none or all
      notification values are supported.  If an implementation does
      not support this object, it should return a 'noSuchObject'
      exception to an SNMP GET operation.  If notifications are
      supported, this object's default value SHOULD reflect
      sipCommonServiceColdStart and sipCommonServiceWarmStart enabled
      and sipCommonServiceStatusChanged disabled.

      This object value SHOULD persist across reboots."
    DEFVAL { { sipCommonServiceColdStart,
               sipCommonServiceWarmStart } }
    ::= { sipCommonCfgEntry 7 }

sipCommonCfgEntityType OBJECT-TYPE
    SYNTAX      SipTCEntityRole
    MAX-ACCESS  read-only



    STATUS      current
    DESCRIPTION
      "This object identifies the list of SIP entities to which this
      row is related.  It is defined as a bit map.  Each bit
      represents a type of SIP entity.  If a bit has value 1, the
      SIP entity represented by this row plays the role of this
      entity type.  If a bit has value 0, the SIP entity represented
      by this row does not act as this entity type.  Combinations
      of bits can be set when the SIP entity plays multiple SIP
      roles."
    ::= { sipCommonCfgEntry 8 }
```

```
--
-- Support for multiple ports
--
sipCommonPortTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SipCommonPortEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains the list of ports that each SIP entity in
     this system is allowed to use.  These ports can be advertised
     using the Contact header in a REGISTER request or response."
  ::= {
 sipCommonCfgBase 2 }

sipCommonPortEntry OBJECT-TYPE
  SYNTAX      SipCommonPortEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "Specification of a particular port.

     Each row represents those objects for a particular SIP entity
     present in this system.  applIndex is used to uniquely identify
     these instances of SIP entities and correlate them through
     the common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
  INDEX { applIndex, sipCommonPort }
  ::= { sipCommonPortTable 1 }

SipCommonPortEntry ::= SEQUENCE {
     sipCommonPort               InetPortNumber,
     sipCommonPortTransportRcv     SipTCTransportProtocol
  }

sipCommonPort OBJECT-TYPE
  SYNTAX      InetPortNumber (1..65535)
  MAX-ACCESS  not-accessible
  STATUS      current



  DESCRIPTION
    "This object reflects a particular port that can be used by the
     SIP application."
  ::= { sipCommonPortEntry 1 }

sipCommonPortTransportRcv
```

```
 OBJECT-TYPE
   SYNTAX      SipTCTransportProtocol
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
     "This object will specify the transport protocol the SIP entity
      will use to receive SIP messages.

      This object is a bit map.  Each bit represents a transport
      protocol.  If a bit has value 1, then that transport protocol
      is currently being used.  If a bit has value 0, then that
      transport protocol is currently not being used."
   ::= { sipCommonPortEntry 2 }

--
-- Support for SIP option tags (SIP extensions).
-- SIP extensions MAY be supported or required by SIP entities.
--

sipCommonOptionTagTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF SipCommonOptionTagEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
     "This table contains a list of the SIP option tags (SIP
      extensions) that are either required, supported, or
      unsupported by the SIP entity.  These option tags are
       used in the Require, Proxy-Require, Supported, and
      Unsupported header fields.

      Example: If a user agent client supports, and requires the
      server to support, reliability of provisional responses
      (RFC 3262), this table contains a row with the option tag string
      '100rel' in sipCommonOptionTag and the OCTET STRING value of
      '1010 0000' or '0xA0' in sipCommonOptionTagHeaderField.

      If a server does not support the required feature (indicated in
      a Require header to a UAS, or in a Proxy-Require to a Proxy
      Server), the server returns a 420 Bad Extension listing the
      feature in an Unsupported header.

      Normally, the list of such features supported by an entity is
      static (i.e., will not change over time)."



   REFERENCE
     "RFC 3261, Sections 19.2, 20.32, 20.29, 20.37, and 20.40"
```

```
  ::= { sipCommonCfgBase 3 }

sipCommonOptionTagEntry OBJECT-TYPE
  SYNTAX      SipCommonOptionTagEntry
  MAX-ACCESS
 not-accessible
  STATUS      current
  DESCRIPTION
     "A particular SIP option tag (extension) supported or
      unsupported by the SIP entity, and which may be supported or
      required by a peer.

      Each row represents those objects for a particular SIP entity
      present in this system.  applIndex is used to uniquely identify
      these instances of SIP entities and correlate them through the
      common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
  INDEX { applIndex, sipCommonOptionTagIndex }
  ::= { sipCommonOptionTagTable 1 }

SipCommonOptionTagEntry ::= SEQUENCE {
      sipCommonOptionTagIndex        Unsigned32,
      sipCommonOptionTag             SnmpAdminString,
      sipCommonOptionTagHeaderField  SipTCOptionTagHeaders
  }

sipCommonOptionTagIndex OBJECT-TYPE
  SYNTAX      Unsigned32 (1..4294967295)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "This object uniquely identifies a conceptual
 row in the table."
  ::= { sipCommonOptionTagEntry 1 }

sipCommonOptionTag OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "This object indicates the SIP option tag.  The option tag names
     are registered with IANA and available at http://www.iana.org."
  REFERENCE "RFC 3261, Section 27.1"
  ::= { sipCommonOptionTagEntry 2 }

sipCommonOptionTagHeaderField OBJECT-TYPE
  SYNTAX      SipTCOptionTagHeaders
  MAX-ACCESS  read-only
  STATUS      current
```

```
  DESCRIPTION
    "This object indicates whether the SIP option tag is supported
     (Supported header), unsupported (Unsupported header), or
     required (Require or Proxy-Require header) by the SIP entity.
     A SIP option tag may be both supported and required."
  ::= { sipCommonOptionTagEntry 3 }

--
-- Supported SIP Methods
--
sipCommonMethodSupportedTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SipCommonMethodSupportedEntry
   MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains a list of methods supported by each SIP
     entity in this system (see the standard set of SIP methods in
     Section 7.1 of RFC 3261).  Any additional methods that may be
     incorporated into the SIP protocol can be represented by this
     table without any requirement to update this MIB module.

     The table is informational in nature and conveys capabilities
     of the managed system to the SNMP Manager.

     From a protocol point of view, the list of methods advertised
     by the SIP entity in the Allow header (Section 20.5 of RFC
     3261) MUST be consistent with the methods reflected in this
     table."
::= { sipCommonCfgBase 4 }

sipCommonMethodSupportedEntry OBJECT-TYPE
  SYNTAX      SipCommonMethodSupportedEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "A particular method supported by the SIP entity.

     Each row represents those objects for a particular SIP entity
     present in this system.  applIndex is used to uniquely identify
     these instances of SIP entities and correlate them through
     the common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
  INDEX { applIndex, sipCommonMethodSupportedIndex }
  ::= { sipCommonMethodSupportedTable 1 }

SipCommonMethodSupportedEntry ::= SEQUENCE {
```

```
    sipCommonMethodSupportedIndex     Unsigned32,
    sipCommonMethodSupportedName      SipTCMethodName
  }



sipCommonMethodSupportedIndex OBJECT-TYPE
  SYNTAX      Unsigned32 (1..4294967295)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This object uniquely identifies a conceptual row in the table
    and reflects an assigned number used to identify a specific
    SIP method.

    This identifier is suitable for referencing the associated
    method throughout this and other MIBs supported by this managed
     system."
  ::= { sipCommonMethodSupportedEntry 1 }

sipCommonMethodSupportedName OBJECT-TYPE
  SYNTAX      SipTCMethodName
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the supported method's name.  The method
    name MUST be all upper case (e.g., 'INVITE')."
::= { sipCommonMethodSupportedEntry 2 }

--
-- SIP Timer Configuration
--
sipCommonCfgTimerTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SipCommonCfgTimerEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains timer configuration objects applicable to
    SIP user agent and SIP stateful Proxy Server entities."
  ::= { sipCommonCfgTimer 1 }

sipCommonCfgTimerEntry OBJECT-TYPE
  SYNTAX      SipCommonCfgTimerEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "A row of timer configuration.
```

```
      Each row represents those objects for a particular SIP entity
      present
 in this system.  applIndex is used to uniquely identify
      these instances of SIP entities and correlate them through
      the common framework of the NETWORK-SERVICES-MIB (RFC 2788).
      The objects in this table entry SHOULD be non-volatile and
      their value SHOULD be kept at reboot."



   INDEX { applIndex }
   ::= { sipCommonCfgTimerTable 1 }

SipCommonCfgTimerEntry ::= SEQUENCE {
      sipCommonCfgTimerA             Unsigned32,
      sipCommonCfgTimerB             Unsigned32,
      sipCommonCfgTimerC             Unsigned32,
      sipCommonCfgTimerD             Unsigned32,
      sipCommonCfgTimerE             Unsigned32,
      sipCommonCfgTimerF             Unsigned32,
      sipCommonCfgTimerG             Unsigned32,
      sipCommonCfgTimerH             Unsigned32,
      sipCommonCfgTimerI             Unsigned32,
      sipCommonCfgTimerJ             Unsigned32,
      sipCommonCfgTimerK             Unsigned32,

  sipCommonCfgTimerT1            Unsigned32,
      sipCommonCfgTimerT2            Unsigned32,
      sipCommonCfgTimerT4            Unsigned32
   }

sipCommonCfgTimerA OBJECT-TYPE
   SYNTAX      Unsigned32 (100..1000)
   UNITS       "milliseconds"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
     "This object reflects the initial value for the retransmit timer
      for the INVITE method.  The retransmit timer doubles after each
      retransmission, ensuring an exponential backoff in network
      traffic.  This object represents the initial time a SIP entity
      will wait to receive a provisional response to an INVITE before
      resending the INVITE request."
   REFERENCE
     "RFC 3261, Section 17.1.1.2"
   DEFVAL { 500 }
   ::= { sipCommonCfgTimerEntry 1 }
```

```
sipCommonCfgTimerB OBJECT-TYPE
  SYNTAX      Unsigned32 (32000..300000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION

  "This object reflects the maximum time a SIP entity will wait to
      receive a final response to an INVITE.  The timer is started
      upon transmission of the initial INVITE request."
  REFERENCE
    "RFC 3261, Section 17.1.1.2"



  DEFVAL { 32000 }
::= { sipCommonCfgTimerEntry 2 }

sipCommonCfgTimerC OBJECT-TYPE
  SYNTAX      Unsigned32 (180000..300000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the maximum time a SIP Proxy Server will
     wait to receive a provisional response to an INVITE.  The Timer
     C MUST be set for each client transaction when an INVITE
     request is proxied."
  REFERENCE
    "RFC 3261, Section 16.6"
  DEFVAL { 180000 }
  ::= { sipCommonCfgTimerEntry 3 }

sipCommonCfgTimerD OBJECT-TYPE
  SYNTAX      Unsigned32 (0..300000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object
 reflects the amount of time that the server
     transaction can remain in the 'Completed' state when unreliable
     transports are used.  The default value MUST be equal to or
     greater than 32000 for UDP transport, and its value MUST be 0
     for TCP/SCTP transport."
  REFERENCE
    "RFC 3261, Section 17.1.1.2"
  DEFVAL { 32000 }
```

```
  ::= { sipCommonCfgTimerEntry 4 }

sipCommonCfgTimerE OBJECT-TYPE
  SYNTAX      Unsigned32 (100..1000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the initial value for the retransmit timer
     for a non-INVITE method while in 'Trying' state.  The
     retransmit timer doubles after each retransmission until it
     reaches T2 to ensure an exponential backoff in network traffic.
     This object represents the initial time a SIP entity will wait
     to receive a provisional response to the request before
     resending the non-INVITE
 request."
  REFERENCE



    "RFC 3261, Section 17.1.2.2"
  DEFVAL { 500 }
  ::= { sipCommonCfgTimerEntry 5 }

sipCommonCfgTimerF  OBJECT-TYPE
  SYNTAX      Unsigned32 (32000..300000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the maximum time a SIP entity will wait to
     receive a final response to a non-INVITE request.  The timer is
     started upon transmission of the initial request."
  REFERENCE
    "RFC 3261, Section 17.1.2.2"
  DEFVAL { 32000 }

  ::= { sipCommonCfgTimerEntry 6 }

sipCommonCfgTimerG  OBJECT-TYPE
  SYNTAX      Unsigned32 (0..1000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the initial value for the retransmit timer
     for final responses to INVITE requests.  If timer G fires, the
     response is passed to the transport layer again for
```

```
      retransmission,
 and timer G is set to fire in MIN(2*T1, T2)
      seconds.  From then on, when timer G fires, the response is
      passed to the transport again for transmission, and timer G is
      reset with a value that doubles, unless that value exceeds T2,
      in which case, it is reset with the value of T2.  The default
      value MUST be T1 for UDP transport, and its value MUST be 0 for
      reliable transport like TCP/SCTP."
  REFERENCE
    "RFC 3261, Section 17.2.1"
  DEFVAL { 500 }
  ::= { sipCommonCfgTimerEntry 7 }

sipCommonCfgTimerH  OBJECT-TYPE
  SYNTAX      Unsigned32 (32000..300000)
  UNITS      "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the maximum time a server will wait to
     receive an ACK before it abandons retransmitting the response.



     The timer is started upon entering the 'Completed' state."
  REFERENCE
    "RFC 3261, Section 17.2.1"
  DEFVAL { 32000 }
  ::=
 { sipCommonCfgTimerEntry 8 }

sipCommonCfgTimerI  OBJECT-TYPE
  SYNTAX      Unsigned32 (0..10000)
  UNITS      "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the maximum time a SIP entity will wait to
     receive additional ACK message retransmissions.

     The timer is started upon entering the 'Confirmed' state.  The
     default value MUST be T4 for UDP transport and its value MUST
     be 0 for reliable transport like TCP/SCTP."
  REFERENCE
    "RFC 3261, Section 17.2.1"
  DEFVAL { 5000 }
  ::= { sipCommonCfgTimerEntry 9 }
```

```
sipCommonCfgTimerJ  OBJECT-TYPE
  SYNTAX      Unsigned32 (32000..300000)
  UNITS      "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the maximum time a SIP server will wait to
     receive retransmissions of non-INVITE requests.  The timer is
     started upon entering the 'Completed' state for non-INVITE
      transactions.  When timer J fires, the server MUST transition to
     the 'Terminated' state."
  REFERENCE
    "RFC 3261, Section 17.2.2"
  DEFVAL { 32000 }
  ::= { sipCommonCfgTimerEntry 10 }

sipCommonCfgTimerK  OBJECT-TYPE
  SYNTAX      Unsigned32 (0..10000)
  UNITS      "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the maximum time a SIP client will wait to
     receive retransmissions of responses to non-INVITE requests.
     The timer is started upon entering the 'Completed' state for



     non-INVITE transactions.  When timer K fires, the server MUST
     transition to the 'Terminated' state.  The default value MUST
     be T4 for UDP transport, and its value MUST be 0 for reliable
     transport like TCP/SCTP."
  REFERENCE
    "RFC 3261, Section 17.1.2.2"
  DEFVAL { 5000 }
  ::= { sipCommonCfgTimerEntry 11 }

sipCommonCfgTimerT1  OBJECT-TYPE
  SYNTAX
 Unsigned32 (200..10000)
  UNITS      "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the T1 timer for a SIP entity.  T1 is an
     estimate of the round-trip time (RTT) between the client and
     server transactions."
  REFERENCE
```

```
    "RFC 3261, Section 17"
  DEFVAL { 500 }
  ::= { sipCommonCfgTimerEntry 12 }

sipCommonCfgTimerT2  OBJECT-TYPE
  SYNTAX      Unsigned32 (200..10000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the T2 timer for a SIP entity.  T2 is the
     maximum retransmit interval for non-INVITE requests and INVITE
     responses.  It's used in various parts of the protocol to reset
     other Timer* objects to this value."
  REFERENCE
    "RFC 3261, Section 17"
  DEFVAL { 4000 }
  ::= { sipCommonCfgTimerEntry 13 }

sipCommonCfgTimerT4  OBJECT-TYPE
  SYNTAX      Unsigned32 (200..10000)
  UNITS
    "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the T4 timer for a SIP entity.  T4 is the
     maximum duration a message will remain in the network.  It
     represents the amount of time the network will take to clear
     messages between client and server transactions.  It's used in



     various parts of the protocol to reset other Timer* objects to
     this value."
  REFERENCE
    "RFC 3261, Section 17"
  DEFVAL { 5000 }
  ::= { sipCommonCfgTimerEntry 14 }

--
-- Common Statistics Objects
--

--
-- Summary Statistics
--
sipCommonSummaryStatsTable OBJECT-TYPE
```

```
  SYNTAX      SEQUENCE OF SipCommonSummaryStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains the summary statistics objects applicable
     to all SIP entities.  Each row represents those objects for a
     particular SIP entity present in this system."
  ::= {
 sipCommonSummaryStats 1 }

sipCommonSummaryStatsEntry OBJECT-TYPE
  SYNTAX      SipCommonSummaryStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "A row of summary statistics.

     Each row represents those objects for a particular SIP entity
     present in this system.  applIndex is used to uniquely identify
     these instances of SIP entities and correlate them through
     the common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
  INDEX { applIndex }
  ::= { sipCommonSummaryStatsTable 1 }

SipCommonSummaryStatsEntry ::= SEQUENCE {
     sipCommonSummaryInRequests         Counter32,
     sipCommonSummaryOutRequests        Counter32,
     sipCommonSummaryInResponses        Counter32,
     sipCommonSummaryOutResponses       Counter32,
     sipCommonSummaryTotalTransactions  Counter32,
     sipCommonSummaryDisconTime         TimeStamp
  }

sipCommonSummaryInRequests OBJECT-TYPE



  SYNTAX      Counter32
   MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object indicates the total number of SIP request messages
     received by the SIP entity, including retransmissions.

     Discontinuities in the value of this counter can occur at
     re-initialization of the SIP entity or service.  A Management
     Station can detect discontinuities in this counter by
     monitoring the sipCommonSummaryDisconTime object in the same
```

row."
::= { sipCommonSummaryStatsEntry 1 }

sipCommonSummaryOutRequests OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This object contains the total number of SIP request messages
sent out (originated and relayed) by the SIP entity. Where a
particular message is sent more than once, for example as a
retransmission or as a result of forking, each transmission is
counted separately.

Discontinuities in the value
of this counter can occur at
re-initialization of the SIP entity or service. A Management
Station can detect discontinuities in this counter by
monitoring the sipCommonSummaryDisconTime object in the same
row."
::= { sipCommonSummaryStatsEntry 2 }

sipCommonSummaryInResponses OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This object contains the total number of SIP response messages
received by the SIP entity, including retransmissions.

Discontinuities in the value of this counter can occur at
re-initialization of the SIP entity or service. A Management
Station can detect discontinuities in this counter by
monitoring the sipCommonSummaryDisconTime object in the same
row."
::= { sipCommonSummaryStatsEntry 3 }

sipCommonSummaryOutResponses OBJECT-TYPE

SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This object contains the total number of SIP response messages
sent (originated and relayed) by the SIP entity including
retransmissions.

Discontinuities in the value of this counter can occur at
re-initialization of the SIP entity or service. A Management
Station can detect discontinuities in this counter by
monitoring the sipCommonSummaryDisconTime object in the same
row."
::= { sipCommonSummaryStatsEntry 4 }

sipCommonSummaryTotalTransactions OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This object contains a count of the number of transactions that
are in progress and transactions that have reached the
'Terminated' state. It is not applicable to stateless SIP Proxy
Servers.

A SIP transaction occurs between a client and a server, and
comprises all messages from the first request sent from the
client to the server, up to a final (non-1xx) response sent
from the server to the client.

If the request is INVITE and the final response is a non-2xx,
the transaction also include an ACK to the response. The ACK
for a 2xx response to an INVITE request is a separate
transaction.

The branch ID parameter in the Via header field values serves
as a transaction identifier.

A transaction is identified by the CSeq sequence number within
a single call leg. The ACK request has the same CSeq number as
the corresponding INVITE request, but comprises a transaction
of its own.

In the case of a forked request, each branch counts as a single
transaction.

For a transaction stateless Proxy Server, this counter is
always 0.

Discontinuities in the value of this counter can occur at
re-initialization of the SIP entity or service. A Management

```
    Station can detect discontinuities in this counter by
        monitoring the sipCommonSummaryDisconTime object in the same
        row."
    ::= { sipCommonSummaryStatsEntry 5 }

sipCommonSummaryDisconTime  OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of the sysUpTime object when the counters for the
        summary statistics objects in this row last experienced a
        discontinuity."
    ::= { sipCommonSummaryStatsEntry 6 }

--
-- SIP Method Statistics
-- Total counts for each SIP method.
--
sipCommonMethodStatsTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF SipCommonMethodStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains the method statistics objects for SIP
        entities.  Each row represents those objects for a particular
        SIP entity present in this system."
    ::= { sipCommonMethodStats 1 }

sipCommonMethodStatsEntry OBJECT-TYPE

    SYNTAX      SipCommonMethodStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A row of per entity method statistics.

        Each row represents those objects for a particular SIP entity
        present in this system.  applIndex is used to uniquely identify
        these instances of SIP entities and correlate them through
        the common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
    INDEX { applIndex, sipCommonMethodStatsName }
    ::= { sipCommonMethodStatsTable 1 }

SipCommonMethodStatsEntry ::= SEQUENCE {
        sipCommonMethodStatsName    SipTCMethodName,
        sipCommonMethodStatsOutbounds    Counter32,
```

```
      sipCommonMethodStatsInbounds     Counter32,
      sipCommonMethodStatsDisconTime   TimeStamp

    }

sipCommonMethodStatsName OBJECT-TYPE
    SYNTAX      SipTCMethodName
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
      "This object uniquely identifies the SIP method related to the

       objects in a particular row."
    ::= { sipCommonMethodStatsEntry 1 }

sipCommonMethodStatsOutbounds OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "This object reflects the total number of requests sent by the
       SIP entity, excluding retransmissions.  Retransmissions are
       counted separately and are not reflected in this counter.  A
       Management Station can detect discontinuities in this counter
       by monitoring the sipCommonMethodStatsDisconTime object in the
       same row."
    REFERENCE
      "RFC 3261, Section 7.1"
    ::= { sipCommonMethodStatsEntry 2 }

sipCommonMethodStatsInbounds OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "This object reflects the total number of requests received by
       the SIP entity.  Retransmissions are counted separately and are
       not reflected in this counter.  A Management Station
   can detect
       discontinuities in this counter by monitoring the
       sipCommonMethodStatsDisconTime object in the same row."
    REFERENCE
      "RFC 3261, Section 7.1"
    ::= { sipCommonMethodStatsEntry 3 }

sipCommonMethodStatsDisconTime  OBJECT-TYPE
```

```
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION



      "The value of the sysUpTime object when the counters for the
       method statistics objects in this row last experienced a
       discontinuity."
  ::= { sipCommonMethodStatsEntry 4 }

--
-- Support for specific status codes
--
sipCommonStatusCodeTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SipCommonStatusCodeEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "This table contains the list of SIP status codes that each SIP
       entity in this system has been requested to monitor.  It is the
       mechanism by which specific status codes are monitored.
       Entries created in this table
 must not persist across reboots."
  ::= { sipCommonStatusCode 1 }

sipCommonStatusCodeEntry OBJECT-TYPE
  SYNTAX      SipCommonStatusCodeEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "This row contains information on a particular SIP status code
       that the SIP entity has been requested to monitor.  Entries
       created in this table must not persist across reboots.

       Each row represents those objects for a particular SIP entity
       present in this system.  applIndex is used to uniquely identify
       these instances of SIP entities and correlate them through
       the common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
  INDEX { applIndex, sipCommonStatusCodeMethod,
          sipCommonStatusCodeValue }
  ::= { sipCommonStatusCodeTable 1 }

SipCommonStatusCodeEntry ::= SEQUENCE {
      sipCommonStatusCodeMethod     SipTCMethodName,
      sipCommonStatusCodeValue      Unsigned32,
      sipCommonStatusCodeIns
```

```
      Counter32,
      sipCommonStatusCodeOuts       Counter32,
      sipCommonStatusCodeRowStatus  RowStatus,
      sipCommonStatusCodeDisconTime TimeStamp
    }

sipCommonStatusCodeMethod OBJECT-TYPE
    SYNTAX      SipTCMethodName
    MAX-ACCESS  not-accessible



    STATUS      current
    DESCRIPTION
      "This object uniquely identifies a conceptual row in the
      table."
    ::= { sipCommonStatusCodeEntry 1 }

sipCommonStatusCodeValue OBJECT-TYPE
    SYNTAX      Unsigned32 (100..999)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
      "This object contains a SIP status code value that the SIP
      entity has been requested to monitor.  All of the other
      information in the row is related to this value."
    ::= { sipCommonStatusCodeEntry 2 }

sipCommonStatusCodeIns OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "This object reflects the total number of response
 messages
      received by the SIP entity with the status code value contained
      in the sipCommonStatusCodeValue column.

      Discontinuities in the value of this counter can occur at
      re-initialization of the SIP entity or service, or when the
      monitoring of the status code is temporarily disabled.  A
      Management Station can detect discontinuities in this counter
      by monitoring the sipCommonStatusCodeDisconTime object in the
      same row."
    ::= { sipCommonStatusCodeEntry 3 }

sipCommonStatusCodeOuts OBJECT-TYPE
    SYNTAX      Counter32
```

```
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the total number of response messages sent
     by the SIP entity with the status code value contained in the
     sipCommonStatusCodeValue column.

     Discontinuities in the value of this counter can occur at
     re-initialization of the SIP entity or service, or when the
     monitoring of
 the Status code is temporarily disabled.  A
     Management Station can detect discontinuities in this counter
     by monitoring the sipCommonStatusCodeDisconTime object in the
     same row."



  ::= { sipCommonStatusCodeEntry 4 }

sipCommonStatusCodeRowStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The row augmentation in sipCommonStatusCodeNotifTable will be
     governed by the value of this RowStatus.

     The values 'createAndGo' and 'destroy' are the only valid
     values allowed for this object.  If a row exists, it will
     reflect a status of 'active' when queried."
  ::= { sipCommonStatusCodeEntry 5 }

sipCommonStatusCodeDisconTime  OBJECT-TYPE
  SYNTAX TimeStamp
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The value of the sysUpTime object when the counters for the
     status code statistics objects in this row last experienced
     a discontinuity."
   ::= { sipCommonStatusCodeEntry 6 }

--
-- Support for specific status code notifications
--

sipCommonStatusCodeNotifTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SipCommonStatusCodeNotifEntry
```

```
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains objects to control notifications related to
     particular status codes that each SIP entity in this system has
     been requested to monitor.

     There is an entry in this table corresponding to each entry in
     sipCommonStatusCodeTable.  Therefore, this table augments
     sipCommonStatusCodeTable and utilizes the same index
     methodology.

     The objects in this table are not included directly in the
     sipCommonStatusCodeTable simply to keep the status code
     notification control objects separate from the actual status
     code statistics."
  ::= { sipCommonStatusCode 2 }



sipCommonStatusCodeNotifEntry OBJECT-TYPE
  SYNTAX
 SipCommonStatusCodeNotifEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This row contains information controlling notifications for a
     particular SIP status code that the SIP entity has been
     requested to monitor."
  AUGMENTS { sipCommonStatusCodeEntry }
  ::= { sipCommonStatusCodeNotifTable 1 }

SipCommonStatusCodeNotifEntry ::= SEQUENCE {
     sipCommonStatusCodeNotifSend         TruthValue,
     sipCommonStatusCodeNotifEmitMode     INTEGER,
     sipCommonStatusCodeNotifThresh       Unsigned32,
     sipCommonStatusCodeNotifInterval     Unsigned32
  }

sipCommonStatusCodeNotifSend OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "This object controls whether a sipCommonStatusCodeNotif is
     emitted when the status code value specified by
     sipCommonStatusCodeValue is sent or received.  If the value of
     this object is 'true', then a notification
```

```
 is sent.  If it is
      'false', no notification is sent.
      Note well that a notification MAY be emitted for every message
      sent or received that contains the particular status code.
      Depending on the status code involved, this can cause a
      significant number of notification emissions that could be
      detrimental to network performance.  Managers are forewarned to
      be prudent in the use of this object to enable notifications.
      Look to sipCommonStatusCodeNotifEmitMode for alternative
      controls for sipCommonStatusCodeNotif emissions."
   DEFVAL { false }
   ::= { sipCommonStatusCodeNotifEntry 1 }

sipCommonStatusCodeNotifEmitMode OBJECT-TYPE
   SYNTAX      INTEGER {
                 normal(1),
                 oneShot(2),
                 triggered(3)  -- read-only
               }
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION



      "The object sipCommonStatusCodeNotifSend MUST be set to 'true'
       for the values of this object to have any effect.  It is
      RECOMMENDED that the desired emit mode be established by this
      object prior to setting sipCommonStatusCodeNotifSend to 'true'.
      This object and the sipCommonStatusCodeNotifSend object can
      obviously be set independently, but their respective values
      will have a dependency on each other and the resulting
      notifications.

      This object specifies the mode for emissions of
      sipCommonStatusCodeNotif notifications.

      normal    : sipCommonStatusCodeNotif notifications will be
                  emitted by the system for each SIP response
                  message sent or received that contains the
                  desired status code.

      oneShot   : Only one sipCommonStatusCodeNotif notification
                  will be emitted.  It will be the next SIP response
                  message sent or received that contains the
                  desired
 status code.
```

No more notifications are emitted until this
object is set to 'oneShot' again or set to
'normal'. This option is provided as a means of
quelling the potential promiscuous behavior that
can be associated with the
sipCommonStatusCodeNotif.

triggered : This value is only readable and cannot be set. It
reflects that the 'oneShot' case has occurred,
and indicates that the mode needs to be reset to
get further notifications. The mode is reset by
setting this object to 'oneShot' or 'normal'."
DEFVAL { oneShot }
::= { sipCommonStatusCodeNotifEntry 2 }

sipCommonStatusCodeNotifThresh OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"This object specifies the number of response messages sent or

received by this system that are considered excessive. Based
on crossing that threshold, a
sipCommonStatusCodeThreshExceededInNotif notification or a
sipCommonStatusCodeThreshExceededOutNotif will be sent. The
sipCommonStatusCodeThreshExceededInNotif and

sipCommonStatusCodeThreshExceededOutNotif notifications can be
used as an early warning mechanism in lieu of using
sipCommonStatusCodeNotif.

Note that the configuration applied by this object will be
applied equally to inbound and outbound response messages."
DEFVAL { 500 }
::= { sipCommonStatusCodeNotifEntry 3 }

sipCommonStatusCodeNotifInterval OBJECT-TYPE
SYNTAX Unsigned32
UNITS "seconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"This object specifies the time interval over which, if
sipCommonStatusCodeThresh is exceeded with respect to sent or
received messages, a sipCommonStatusCodeThreshExceededInNotif

```
       or sipCommonStatusCodeThreshExceededOutNotif notification will
       be sent.

       Note that the configuration applied by this object will be
       applied equally to inbound and outbound response messages."
   DEFVAL { 60 }
   ::= { sipCommonStatusCodeNotifEntry 4 }

--
-- Transaction Statistics
--
sipCommonTransCurrentTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF SipCommonTransCurrentEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "This table contains information on the transactions currently
       awaiting definitive responses by each SIP entity in this
       system.

       This table does not apply to transaction stateless Proxy
       Servers."
   ::= { sipCommonStatsTrans 1 }

sipCommonTransCurrentEntry OBJECT-TYPE
   SYNTAX      SipCommonTransCurrentEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "Information on a particular SIP entity's current transactions.



       Each row represents those objects for a particular SIP entity
       present in this system.  applIndex is used to uniquely identify
       these instances of SIP entities and correlate them through
       the common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
   INDEX { applIndex }
   ::= { sipCommonTransCurrentTable 1 }

SipCommonTransCurrentEntry ::= SEQUENCE {
       sipCommonTransCurrentactions  Gauge32
   }

sipCommonTransCurrentactions OBJECT-TYPE
   SYNTAX      Gauge32 (0..4294967295)
   MAX-ACCESS  read-only
   STATUS      current
```

```
  DESCRIPTION
     "This object contains the number of transactions awaiting
      definitive (non-1xx) response.  In the case of a forked
      request, each branch counts as a single transaction
      corresponding to the entity identified by applIndex."
::= { sipCommonTransCurrentEntry 1 }

--
-- SIP Retry Statistics
--
-- This group contains various statistics objects about
-- retransmission counts.
--
sipCommonStatsRetryTable
 OBJECT-TYPE
  SYNTAX      SEQUENCE OF SipCommonStatsRetryEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "This table contains retry statistics objects applicable to each
      SIP entity in this system."
  ::= { sipCommonStatsRetry 1 }

sipCommonStatsRetryEntry OBJECT-TYPE
  SYNTAX      SipCommonStatsRetryEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A row of retry statistics.

      Each row represents those objects for a particular SIP entity
      present in this system.  applIndex is used to uniquely identify
      these instances of SIP entities and correlate them through the
      common framework of the NETWORK-SERVICES-MIB (RFC 2788)."



  INDEX { applIndex, sipCommonStatsRetryMethod }
  ::= { sipCommonStatsRetryTable 1 }

SipCommonStatsRetryEntry ::= SEQUENCE {
      sipCommonStatsRetryMethod           SipTCMethodName,
      sipCommonStatsRetries
        Counter32,
      sipCommonStatsRetryFinalResponses    Counter32,
      sipCommonStatsRetryNonFinalResponses Counter32,
      sipCommonStatsRetryDisconTime        TimeStamp
  }
```

```
sipCommonStatsRetryMethod OBJECT-TYPE
  SYNTAX      SipTCMethodName
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This object uniquely identifies the SIP method related to the
     objects in a row."
  ::= { sipCommonStatsRetryEntry 1 }

sipCommonStatsRetries OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the total number of request
     retransmissions that have been sent by the SIP entity.  Note
     that there could be multiple retransmissions per request.

     Discontinuities in the value of this counter can occur at
     re-initialization of the SIP entity or service.  A Management
     Station can detect discontinuities in this counter by
     monitoring
 the sipCommonStatsRetryDisconTime object in the same
     row."
  ::= { sipCommonStatsRetryEntry 2 }

sipCommonStatsRetryFinalResponses OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the total number of Final Response retries
     that have been sent by the SIP entity.  Note that there could
     be multiple retransmissions per request.

     Discontinuities in the value of this counter can occur at
     re-initialization of the SIP entity or service.  A Management
     Station can detect discontinuities in this counter by




     monitoring the sipCommonStatsRetryDisconTime object in the same
     row."
  ::= { sipCommonStatsRetryEntry 3 }

sipCommonStatsRetryNonFinalResponses OBJECT-TYPE
  SYNTAX      Counter32
```

```
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "This object reflects the total number of non-Final Response
       retries that
   have been sent by the SIP entity.

       Discontinuities in the value of this counter can occur at
       re-initialization of the SIP entity or service.  A Management
       Station can detect discontinuities in this counter by
       monitoring the sipCommonStatsRetryDisconTime object in the same
       row."
    ::= { sipCommonStatsRetryEntry 4 }

  sipCommonStatsRetryDisconTime  OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "The value of the sysUpTime object when the counters for the
       retry statistics objects in this row last experienced a
       discontinuity."
    ::= { sipCommonStatsRetryEntry 5 }

  --
  -- Other Common Statistics
  --
  sipCommonOtherStatsTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF SipCommonOtherStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
      "This table contains other common statistics supported by each
       SIP entity in this system."
    ::= {
   sipCommonOtherStats 1 }

  sipCommonOtherStatsEntry OBJECT-TYPE
    SYNTAX      SipCommonOtherStatsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
      "Information on a particular SIP entity's other common
       statistics.



       Each row represents those objects for a particular SIP entity
```

```
      present in this system.  applIndex is used to uniquely identify
      these instances of SIP entities and correlate them through
      the common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
    INDEX { applIndex }
    ::= { sipCommonOtherStatsTable 1 }

SipCommonOtherStatsEntry ::= SEQUENCE {
      sipCommonOtherStatsNumUnsupportedUris     Counter32,
      sipCommonOtherStatsNumUnsupportedMethods  Counter32,
      sipCommonOtherStatsOtherwiseDiscardedMsgs Counter32,
      sipCommonOtherStatsDisconTime   TimeStamp
    }

sipCommonOtherStatsNumUnsupportedUris OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS
   current
    DESCRIPTION
      "Number of RequestURIs received with an unsupported scheme.
      A server normally responds to such requests with a 400 Bad
      Request status code.

      Discontinuities in the value of this counter can occur at
      re-initialization of the SIP entity or service.  A Management
      Station can detect discontinuities in this counter by
      monitoring the sipCommonOtherStatsDisconTime object in the same
      row."
    ::= { sipCommonOtherStatsEntry 1 }

sipCommonOtherStatsNumUnsupportedMethods OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "Number of SIP requests received with unsupported methods.  A
      server normally responds to such requests with a 501 (Not
      Implemented) or 405 (Method Not Allowed).

      Discontinuities in the value of this counter can occur at
      re-initialization of the SIP entity or service.  A Management
      Station can
   detect discontinuities in this counter by
      monitoring the sipCommonOtherStatsDisconTime object in the same
      row."
    ::= { sipCommonOtherStatsEntry 2 }

sipCommonOtherStatsOtherwiseDiscardedMsgs OBJECT-TYPE
```

```
  SYNTAX      Counter32



  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "Number of SIP messages received that, for any number of
     reasons, was discarded without a response.

     Discontinuities in the value of this counter can occur at
     re-initialization of the SIP entity or service.  A Management
     Station can detect discontinuities in this counter by
     monitoring the sipCommonOtherStatsDisconTime object in the same
     row."
  ::= { sipCommonOtherStatsEntry 3 }

sipCommonOtherStatsDisconTime OBJECT-TYPE
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The value of the sysUpTime object when the counters for the
     statistics objects in this row last
 experienced a
     discontinuity."
  ::= { sipCommonOtherStatsEntry 4 }

--
-- Notification related objects
--

--
-- Status code related notification objects.
--
sipCommonStatusCodeNotifTo OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
    "This object contains the value of the To header in the message
     containing the status code that caused the notification.  The
     header name will be part of this object value.  For example,
     'To: Watson <sip:watson@bell-telephone.com>'."
  ::= { sipCommonNotifObjects 1 }

sipCommonStatusCodeNotifFrom OBJECT-TYPE
  SYNTAX      SnmpAdminString
```

```
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
    "This object contains the value of the From header in the
     message containing the status code that caused the




     notification.  The header name will be part of this object
     value.  For example, 'From: Watson '."
  ::= { sipCommonNotifObjects
 2 }

sipCommonStatusCodeNotifCallId OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
    "This object contains the value of the Call-ID in the message
     containing the status code that caused the notification.  The
     header name will be part of this object value.  For example,
     'Call-ID: 5551212@example.com'."
  ::= { sipCommonNotifObjects 3 }

sipCommonStatusCodeNotifCSeq OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
    "This object contains the CSeq value in the message containing
     the status code that caused the notification.  The header name
     will be part of this object value.  For example, 'CSeq: 1722
     INVITE'."
  ::= { sipCommonNotifObjects 4 }

--
-- General notification related objects.
--
sipCommonNotifApplIndex OBJECT-TYPE
  SYNTAX      Unsigned32 (1..2147483647)

 MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
    "This object contains the applIndex as described in RFC 2788.
     This object is created in order to allow a variable binding
     containing a value of applIndex in a notification."
  ::= { sipCommonNotifObjects 5 }
```

```
sipCommonNotifSequenceNumber OBJECT-TYPE
  SYNTAX      Unsigned32 (1..2147483647)
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
    "This object contains a sequence number for each notification
     generated by this SIP entity.  Each notification SHOULD have a
     unique sequence number.  A network manager can use this
     information to determine whether notifications from a



     particular SIP entity have been missed.  The value of this
     object MUST start at 1 and increase by 1 with each generated
     notification.  If a system restarts, the sequence number MAY
     start again from 1."
  ::= { sipCommonNotifObjects
 6 }

--
-- Notifications
--
sipCommonStatusCodeNotif NOTIFICATION-TYPE
  OBJECTS {
    sipCommonNotifSequenceNumber,
    sipCommonNotifApplIndex,
    sipCommonStatusCodeNotifTo,
    sipCommonStatusCodeNotifFrom,
    sipCommonStatusCodeNotifCallId,
    sipCommonStatusCodeNotifCSeq,
    sipCommonStatusCodeIns,
    sipCommonStatusCodeOuts
  }
  STATUS      current
  DESCRIPTION
    "Signifies that a specific status code has been sent or received
     by the system."
  ::= { sipCommonMIBNotifications 1 }

sipCommonStatusCodeThreshExceededInNotif NOTIFICATION-TYPE
  OBJECTS {
    sipCommonNotifSequenceNumber,
    sipCommonNotifApplIndex,
    sipCommonStatusCodeIns
  }
  STATUS      current
  DESCRIPTION
```

```
      "Signifies that a specific status code was found to have been
       received by the system frequently enough to exceed the
       configured threshold.  This notification can be used as
       an early warning mechanism
 in lieu of using
       sipCommonStatusCodeNotif."
  ::= { sipCommonMIBNotifications 2 }

sipCommonStatusCodeThreshExceededOutNotif NOTIFICATION-TYPE
  OBJECTS {
    sipCommonNotifSequenceNumber,
    sipCommonNotifApplIndex,
    sipCommonStatusCodeOuts
  }
  STATUS      current



  DESCRIPTION
    "Signifies that a specific status code was found to have been
     sent by the system enough to exceed the configured threshold.
     This notification can be used as an early warning mechanism in
     lieu of using sipCommonStatusCodeNotif."
  ::= { sipCommonMIBNotifications 3 }

sipCommonServiceColdStart NOTIFICATION-TYPE
  OBJECTS {
    sipCommonNotifSequenceNumber,
    sipCommonNotifApplIndex,
    sipCommonCfgServiceStartTime
  }
  STATUS      current
  DESCRIPTION
    "Signifies that the SIP service has reinitialized itself or
     started for the first time.  This SHOULD result from a hard
     'down' to 'up' administrative status
 change.  The configuration
     or behavior of the service MAY be altered."
  ::= { sipCommonMIBNotifications 4 }

sipCommonServiceWarmStart NOTIFICATION-TYPE
  OBJECTS {
    sipCommonNotifSequenceNumber,
    sipCommonNotifApplIndex,
    sipCommonCfgServiceLastChange
  }
  STATUS      current
  DESCRIPTION
```

```
      "Signifies that the SIP service has reinitialized itself and is
       restarting after an administrative 'reset'.  The configuration
       or behavior of the service MAY be altered."
    ::= { sipCommonMIBNotifications 5 }

sipCommonServiceStatusChanged NOTIFICATION-TYPE
    OBJECTS {
      sipCommonNotifSequenceNumber,
      sipCommonNotifApplIndex,
      sipCommonCfgServiceLastChange,
      sipCommonCfgServiceOperStatus
    }
    STATUS      current
    DESCRIPTION
      "Signifies that the SIP service operational status has changed."
    ::= { sipCommonMIBNotifications 6 }

--
-- Conformance




--
sipCommonMIBCompliances
    OBJECT IDENTIFIER
  ::= { sipCommonMIBConformance 1 }
sipCommonMIBGroups
    OBJECT IDENTIFIER ::= { sipCommonMIBConformance 2 }

--
-- Compliance Statements
--
sipCommonCompliance MODULE-COMPLIANCE
    STATUS      current
    DESCRIPTION
      "The compliance statement for SIP entities."

    MODULE -- this module
      MANDATORY-GROUPS { sipCommonConfigGroup,
                         sipCommonStatsGroup
                       }

    OBJECT       sipCommonStatusCodeRowStatus
    SYNTAX       RowStatus { active(1) }
    WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
    DESCRIPTION
      "Support for createAndWait and notInService is not required."
```

```
 OBJECT      sipCommonCfgServiceNotifEnable
 MIN-ACCESS  not-accessible
 DESCRIPTION
   "This object is optional and does not need to be supported."

 GROUP       sipCommonInformationalGroup
 DESCRIPTION
   "This group is OPTIONAL.  A SIP entity can elect to not provide
    any support for these objects, as they
provide optional
    information."

 GROUP       sipCommonConfigTimerGroup
 DESCRIPTION
   "This group is OPTIONAL.  A SIP entity can elect to not provide
    any timer configuration."

 GROUP       sipCommonStatsRetryGroup
 DESCRIPTION
   "This group is OPTIONAL.  A SIP entity can elect to not provide
    any retry statistics."

 GROUP       sipCommonNotifGroup
 DESCRIPTION



   "This group is OPTIONAL.  A SIP entity can elect to not provide
    any notifications.  If implemented, the
    sipCommonStatusCodeNotifGroup and sipCommonNotifObjectsGroup
    MUST also be implemented."

 GROUP       sipCommonStatusCodeNotifGroup
 DESCRIPTION
   "This group is OPTIONAL.  A SIP entity can elect to not provide
    any notifications.  If implemented, the sipCommonNotifGroup and
    sipCommonNotifObjectsGroup MUST also be implemented."

 GROUP       sipCommonNotifObjectsGroup
 DESCRIPTION
   "This group is
OPTIONAL.  A SIP entity can elect to not provide
    any notifications.  If implemented, the
    sipCommonStatusCodeNotifGroup and sipCommonNotifGroup MUST also
    be implemented."

 ::= { sipCommonMIBCompliances 1 }
```

```
--
-- Units of Conformance
--
sipCommonConfigGroup OBJECT-GROUP
  OBJECTS {
        sipCommonCfgProtocolVersion,
        sipCommonCfgServiceOperStatus,
        sipCommonCfgServiceStartTime,
        sipCommonCfgServiceLastChange,
        sipCommonPortTransportRcv,
        sipCommonOptionTag,
        sipCommonOptionTagHeaderField,
        sipCommonCfgMaxTransactions,
        sipCommonCfgServiceNotifEnable,
        sipCommonCfgEntityType,
        sipCommonMethodSupportedName
  }
  STATUS  current
  DESCRIPTION
    "A collection of objects providing configuration common to all
     SIP entities."
  ::= { sipCommonMIBGroups 1 }

sipCommonInformationalGroup OBJECT-GROUP
  OBJECTS {
        sipCommonCfgOrganization
   }
  STATUS  current



  DESCRIPTION
    "A collection of objects providing configuration common to all
     SIP entities."
  ::= { sipCommonMIBGroups 2 }

sipCommonConfigTimerGroup OBJECT-GROUP
  OBJECTS {
        sipCommonCfgTimerA,
        sipCommonCfgTimerB,
        sipCommonCfgTimerC,
        sipCommonCfgTimerD,
        sipCommonCfgTimerE,
        sipCommonCfgTimerF,
        sipCommonCfgTimerG,
        sipCommonCfgTimerH,
        sipCommonCfgTimerI,
        sipCommonCfgTimerJ,
```

```
        sipCommonCfgTimerK,
        sipCommonCfgTimerT1,
        sipCommonCfgTimerT2,
        sipCommonCfgTimerT4
    }
    STATUS  current
    DESCRIPTION
      "A collection of objects providing timer configuration common to
       all SIP entities."
    ::= { sipCommonMIBGroups 3 }

sipCommonStatsGroup OBJECT-GROUP
    OBJECTS {
        sipCommonSummaryInRequests,
        sipCommonSummaryOutRequests,

       sipCommonSummaryInResponses,
        sipCommonSummaryOutResponses,
        sipCommonSummaryTotalTransactions,
        sipCommonSummaryDisconTime,
        sipCommonMethodStatsOutbounds,
        sipCommonMethodStatsInbounds,
        sipCommonMethodStatsDisconTime,
        sipCommonStatusCodeIns,
        sipCommonStatusCodeOuts,
        sipCommonStatusCodeRowStatus,
        sipCommonStatusCodeDisconTime,
        sipCommonTransCurrentactions,
        sipCommonOtherStatsNumUnsupportedUris,
        sipCommonOtherStatsNumUnsupportedMethods,
        sipCommonOtherStatsOtherwiseDiscardedMsgs,
        sipCommonOtherStatsDisconTime



    }
    STATUS  current
    DESCRIPTION
      "A collection of objects providing statistics common to all SIP
       entities."
    ::= { sipCommonMIBGroups 4 }

sipCommonStatsRetryGroup OBJECT-GROUP
    OBJECTS {
        sipCommonStatsRetries,
        sipCommonStatsRetryFinalResponses,
         sipCommonStatsRetryNonFinalResponses,
        sipCommonStatsRetryDisconTime
```

```
  }
  STATUS  current
  DESCRIPTION
    "A collection of objects providing retry statistics."
  ::= { sipCommonMIBGroups 5 }

sipCommonNotifGroup NOTIFICATION-GROUP
  NOTIFICATIONS {
        sipCommonStatusCodeNotif,
        sipCommonStatusCodeThreshExceededInNotif,
        sipCommonStatusCodeThreshExceededOutNotif,
        sipCommonServiceColdStart,
        sipCommonServiceWarmStart,
        sipCommonServiceStatusChanged
  }

  STATUS  current
  DESCRIPTION
    "A collection of notifications common to all SIP entities."
  ::= { sipCommonMIBGroups 6 }

sipCommonStatusCodeNotifGroup OBJECT-GROUP
  OBJECTS {
        sipCommonStatusCodeNotifSend,
        sipCommonStatusCodeNotifEmitMode,
        sipCommonStatusCodeNotifThresh,
        sipCommonStatusCodeNotifInterval
  }
  STATUS  current
  DESCRIPTION
    "A collection of
 objects related to the control and attribution
     of notifications common to all SIP entities."
  ::= { sipCommonMIBGroups 7 }

sipCommonNotifObjectsGroup OBJECT-GROUP




  OBJECTS {
        sipCommonStatusCodeNotifTo,
        sipCommonStatusCodeNotifFrom,
        sipCommonStatusCodeNotifCallId,
        sipCommonStatusCodeNotifCSeq,
        sipCommonNotifApplIndex,
        sipCommonNotifSequenceNumber
  }
  STATUS  current
```

```
  DESCRIPTION
     "A collection of accessible-for-notify objects related to the
      notification defined in this MIB module."
  ::= { sipCommonMIBGroups 8 }

END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/SIP-COMMON-MIB
No license file was found, but licenses were detected in source scan.

```
RMON2-MIB DEFINITIONS ::= BEGIN
IMPORTS
  MODULE-IDENTITY, OBJECT-TYPE, Counter32, Integer32,
  Gauge32, IpAddress, TimeTicks, mib-2        FROM SNMPv2-SMI
  TEXTUAL-CONVENTION, RowStatus, DisplayString, TimeStamp
                                  FROM SNMPv2-TC
  MODULE-COMPLIANCE, OBJECT-GROUP            FROM SNMPv2-CONF
  ifIndex                                FROM IF-MIB
  OwnerString, statistics, history, hosts,
  matrix, filter, etherStatsEntry, historyControlEntry,
  hostControlEntry, matrixControlEntry, filterEntry,
  channelEntry                FROM RMON-MIB
  tokenRing, tokenRingMLStatsEntry, tokenRingPStatsEntry,



  ringStationControlEntry, sourceRoutingStatsEntry
                           FROM TOKEN-RING-RMON-MIB;
--  Remote Network Monitoring MIB

rmon MODULE-IDENTITY
  LAST-UPDATED "200605020000Z"    -- May 2, 2006
  ORGANIZATION "IETF RMON
 MIB Working Group"
  CONTACT-INFO
     "Author:
             Steve Waldbusser
        Phone:  +1-650-948-6500
        Fax :   +1-650-745-0671
        Email:  waldbusser@nextbeacon.com

      Working Group Chair:
             Andy Bierman
        E-mail: ietf@andybierman.com

      Working Group Mailing List: <rmonmib@ietf.org>
      To subscribe send email to: <rmonmib-request@ietf.org>    "
```

DESCRIPTION
"The MIB module for managing remote monitoring
device implementations. This MIB module
extends the architecture introduced in the original
RMON MIB as specified in RFC 2819.

Copyright (C) The Internet Society (2006). This version of
this MIB module is part of RFC 4502; see the RFC itself for
full legal notices."

REVISION "200605020000Z" -- May 2, 2006
DESCRIPTION
"This version updates the proposed-standard version of the
RMON2 MIB (published
as RFC 2021) by adding 2 new
enumerations to the nlMatrixTopNControlRateBase object and
4 new enumerations to the alMatrixTopNControlRateBase object.
These new enumerations support the creation of high-capacity
topN reports in the High Capacity RMON MIB [RFC3273].

Additionally, the following objects have been deprecated, as
they have not had enough independent implementations to
demonstrate interoperability to meet the requirements of a
Draft Standard:

probeDownloadFile
probeDownloadTFTPServer
probeDownloadAction
probeDownloadStatus

serialMode
serialProtocol
serialTimeout
serialModemInitString
serialModemHangUpString
serialModemConnectResp
serialModemNoConnectResp
serialDialoutTimeout
serialStatus
serialConnectDestIpAddress
serialConnectType
serialConnectDialString
serialConnectSwitchConnectSeq
serialConnectSwitchDisconnectSeq
serialConnectSwitchResetSeq
serialConnectOwner

serialConnectStatus
netConfigIPAddress
netConfigSubnetMask
netConfigStatus
netDefaultGateway
tokenRingMLStats2DroppedFrames
tokenRingMLStats2CreateTime
tokenRingPStats2DroppedFrames
tokenRingPStats2CreateTime
ringStationControl2DroppedFrames
ringStationControl2CreateTime
sourceRoutingStats2DroppedFrames
sourceRoutingStats2CreateTime
trapDestIndex
trapDestCommunity
trapDestProtocol
trapDestAddress
trapDestOwner
trapDestStatus

In addition, two corrections were made. The LastCreateTime Textual Convention had been defined with a base type of another textual convention, which isn't allowed in SMIv2. The definition has been modified to use TimeTicks as the base type.

Further,
the SerialConfigEntry SEQUENCE definition included sub-typing information that is not allowed in SMIv2. This information has been deleted. Ranges were added to a number of objects and textual-conventions to constrain their maximum (and sometimes minimum) sizes. The addition of these ranges documents existing practice for these objects. These objects

are:
ControlString
protocolDirID
protocolDirParameters
addressMapNetworkAddress
nlHostAddress
nlMatrixSDSourceAddress
nlMatrixSDDestAddress
nlMatrixDSSourceAddress
nlMatrixDSDestAddress
nlMatrixTopNSourceAddress
nlMatrixTopNDestAddress

```
            alHostEntry
            alMatrixSDEntry
            alMatrixDSEntry
            alMatrixTopNSourceAddress
            alMatrixTopNDestAddress

        Finally, the TimeFilter TC has been updated to encourage agent
         implementations that allow a MIB walk to behave well even when
        performed by an application that is not aware of the special
        TimeFilter semantics."

    REVISION "200207080000Z"        -- 08 July, 2002
    DESCRIPTION
        "Added new enumerations to support the High-Capacity RMON
        MIB as defined in RFC 3273.  Also fixed some typos and
        added clarifications."

    REVISION "199605270000Z"    -- 27 May, 1996
    DESCRIPTION
        "Original version.  Published as RFC 2021."
    ::= { mib-2 16 }

-- { rmon 1 } through { rmon 10 } are defined in RMON and
-- the Token Ring RMON MIB [RFC1513]

    protocolDir     OBJECT IDENTIFIER ::= { rmon 11 }
    protocolDist    OBJECT IDENTIFIER ::= { rmon 12 }
    addressMap      OBJECT IDENTIFIER ::= { rmon 13 }
    nlHost          OBJECT IDENTIFIER ::= { rmon 14 }
    nlMatrix        OBJECT IDENTIFIER ::= { rmon 15 }
    alHost          OBJECT IDENTIFIER ::= { rmon 16 }
    alMatrix        OBJECT IDENTIFIER
  ::= { rmon 17 }
    usrHistory      OBJECT IDENTIFIER ::= { rmon 18 }
    probeConfig     OBJECT IDENTIFIER ::= { rmon 19 }
    rmonConformance OBJECT IDENTIFIER ::= { rmon 20 }




-- Textual Conventions

ZeroBasedCounter32 ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "This TC describes an object that counts events with the
        following semantics: objects of this type will be set to
        zero(0) on creation and will thereafter count appropriate
```

events, wrapping back to zero(0) when the value 2^32 is
reached.

Provided that an application discovers the new object within
the minimum time to wrap, it can use the initial value as a
delta since it last polled the table of which this object is
part. It is important for a management station to be aware of
this minimum time and the actual time between polls, and to
discard data if the actual time is too long or there is no
defined minimum time.

Typically, this TC is used in tables where the INDEX space is
constantly changing and/or the TimeFilter mechanism is in use."
SYNTAX Gauge32

LastCreateTime ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
"This TC describes an object that stores the value of the
sysUpTime object at the last time its entry was created.

This can be used for polling applications to determine that an
entry has been deleted and re-created between polls, causing
an otherwise undetectable discontinuity in the data.

If sysUpTime is reset to zero as a result of a re-
initialization of the network management (sub)system, then
the values of all LastCreateTime objects are also reset.
However, after approximately 497 days without a re-
initialization, the sysUpTime object will reach 2^^32-1 and
then increment to zero; in this case, existing values
of TimeStamp objects do not change.
This can lead to
ambiguities in the value of TimeStamp objects."
SYNTAX TimeTicks

TimeFilter ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
"To be used for the index to a table. Allows an application
to download only those rows changed since a particular time.

Note that this is not a history mechanism. Only current values
of underlying objects are returned; saved instance values
associated with particular values of sysUpTime are not.

An entry is considered changed if the value of any object in the
entry changes, if the row is created, or if any object in the
entry is created or deleted. Note that deleted entries cannot
be detected or downloaded.

A time-filtered conceptual table is created by inserting a
single object of SYNTAX TimeFilter as the first INDEX component
in a copy of an existing basic conceptual table (i.e., any
SEQUENCE without a TimeFilter INDEX component). Thus,
for
each conceptual entry 'I' in the basic table, there exists N
conceptual entries in the time-filtered version, indexed N.I,
where 'N' is equal to the value of sysUpTime.

When an application retrieves conceptual instances from a
time-filtered table, and an INDEX value is provided for the
TimeFilter INDEX component 'N', the agent will only consider
returning basic conceptual entries (e.g., 'fooColumn.N.I') if
any column within the basic conceptual entry has changed since
sysUpTime 'N'. If not, the basic conceptual entry will
be ignored for the particular retrieval operation.

When sysUpTime is equal to zero, this table shall be empty.

One conceptual entry exists for each past value of sysUpTime,
except that the whole table is purged should sysUpTime wrap.

As an entry in a time-filtered table is updated (i.e., one of
the columns in the basic conceptual table is changed), new
conceptual
entries are also created in the time-filtered version
(which still shares the now updated object values with all other
instances). The number of unique time-filtered instances that
are created is determined by the value of sysUpTime at which the
basic entry was last updated. One unique instance will exist
for each value of sysUpTime at the last update time for the row.
However, a new TimeFilter index instance is created for each new
sysUpTime value. The TimeFilter index values not associated
with entry updates are called duplicate time-filtered instances.

After some deployment experience, it has been determined that
a time-filtered table is more efficient if the agent
stops a MIB walk operation by skipping over rows with a
TimeFilter index value higher than the value in the received
GetNext/GetBulk request. That is, instead of incrementing a
TimeFilter index value, the agent will continue to the
next

object or table. As a consequence, GetNext or GetBulk operations will provide only one pass through a time-filtered table.

It is suggested that an agent implement a time-filtered table in this manner to improve performance and avoid a MIB walk getting stuck in time-filtered tables. It is, however, still acceptable for an agent to implement a time-filtered table in the traditional manner (i.e., every conceptual time-filtered instance is returned in GetNext and GetBulk PDU responses), and management applications must be able to deal with such traditional implementations.

See the appendix for further discussion of this textual convention.

The following example is provided to demonstrate TimeFilter behavior:

Consider the following basic conceptual table, basicFooTable. (Note that the basic version of a time-filtered table may not actually be defined.)

```
basicFooTable:

 basicFooTable ...
INDEX { fooIndex }

BasicFooEntry {
  fooIndex     Integer32,
  fooCounts    Counter32
}
```

For this example, the basicFooTable contains two static conceptual entries (fooIndex equals '1' and '2'), created at time zero. It also contains one dynamic conceptual entry (fooIndex equals '3'), which is created at time '3' and deleted at time '7'.

The time-filtered version of the basicFooTable could be defined as follows:

```
FooTable:

fooTable ...
INDEX { fooTimeMark, fooIndex }
```

```
    FooEntry {


      fooTimeMark  TimeFilter,
      fooIndex     Integer32,
      fooCounts    Counter32
    }
```

Note that entries exist in the time-filtered conceptual table only if they actually exist in the underlying (basic) table.

For this example, the fooTable will have three underlying basic entries (fooIndex == 1, 2, and 3), with the following activity (for sysUpTime equal 0 to 9):

- fooEntry.N.1 is created at time '0' and most recently updated at time '6' to the value '5'.
- fooEntry.N.2 is created at time '0' and most recently updated at time '8' to the value '9'.
- fooEntry.N.3 is created at time '3', updated at time '5' to the value '17', and deleted at time '7'.

The following tables show the values that would be returned for MIB walk operations with various TimeFilter values, done at different times. An application issues a retrieval request at time 'T', with a TimeFilter value, 'N' (typically set to a lower value, such as the value of sysUpTime at the last polling cycle).

The following values would be returned in a MIB walk of fooCounts.N if T equals '0' and N equals '0':

```
    fooCounts.N.I    Value
    ==========================
    fooCounts.0.1
0
    fooCounts.0.2    0
```

Note that nothing is returned for fooCounts.0.3, since that entry does not exist at sysUpTime equals '0'.

The following values would be returned in a full (traditional) MIB walk of fooCounts.N if T equals '3' and N equals '0':

```
    fooCounts.N.I    Value
```

```
=======================
fooCounts.0.1    0
fooCounts.0.2    0
fooCounts.0.3    0
fooCounts.1.3    0
fooCounts.2.3    0
fooCounts.3.3    0
```

Note that there are no instances for T equals 1 or 2 for the first two values of N, as these entries did not change since they were created at time '0'.

Note that the current value for 'fooCounts.N.3' is returned here, even for values of N less than '3' (when the entry was created). The agent only considers the current existence of an entry in the TimeFilter algorithm, not the time when the entry

was created.

Note that the instances 'fooCounts.0.3', 'fooCounts.1.3', and 'fooCounts.2.3' are duplicates and can be suppressed by the agent in a MIB walk.

The following values would be returned in a full (traditional) MIB walk of fooCounts.N if T equals '6' and N equals '3':

```
fooCounts.N.I    Value
=======================
fooCounts.3.1    5
fooCounts.3.3    17
fooCounts.4.1    5
fooCounts.4.3    17
fooCounts.5.1    5
fooCounts.5.3    17
fooCounts.6.1    5
```

Note that no instances for entry 'fooCounts.N.2' are returned, since it has not changed since time '3'.

Note that all instances except 'fooCounts.5.3' and 'fooCounts.6.1' are duplicates and can be suppressed by the agent in a MIB walk.

The following values would be returned in a full (traditional) MIB walk of fooCounts.N if T equals '9' and N equals

'6':

fooCounts.N.I Value
==========
fooCounts.6.1 5
fooCounts.6.2 9
fooCounts.7.2 9
fooCounts.8.2 9

Note that no instances for entry 'fooCounts.N.3' are returned,
since it was deleted at time '7'.

Note that instances 'fooCounts.6.2' and 'fooCounts.7.2'

are duplicates and can be suppressed by the agent in a MIB
walk."

SYNTAX TimeTicks

DataSource ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
"Identifies the source of the data that the associated
function is configured to analyze. This source can be any
interface on this device.

In order to identify a particular interface, this
object shall identify the instance of the ifIndex
object, defined in [RFC2863], for the desired interface.

For example, if an entry were to receive data from
interface #1, this object
would be set to ifIndex.1."
SYNTAX OBJECT IDENTIFIER

--
-- Protocol Directory Group
--
-- Lists the inventory of protocols the probe has the capability of
-- monitoring and allows the addition, deletion, and configuration of
-- entries in this list.

protocolDirLastChange OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current

```
  DESCRIPTION
      "The value of sysUpTime at the time the protocol directory
      was last modified, either through insertions or deletions,
      or through modifications of the
      protocolDirAddressMapConfig, protocolDirHostConfig, or
      protocolDirMatrixConfig."
  ::= { protocolDir 1 }

protocolDirTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ProtocolDirEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "This table lists the protocols that this agent has the
      capability to decode and count.  There is one entry in this
      table for each such protocol.
 These protocols represent
      different network-layer, transport-layer, and higher-layer



      protocols.  The agent should boot up with this table
      preconfigured with those protocols that it knows about and
      wishes to monitor.  Implementations are strongly encouraged to
      support protocols higher than the network layer (at least for
      the protocol distribution group), even for implementations
      that don't support the application-layer groups."
  ::= { protocolDir 2 }

protocolDirEntry OBJECT-TYPE
  SYNTAX      ProtocolDirEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A conceptual row in the protocolDirTable.

       An example of the indexing of this entry is
       protocolDirLocalIndex.8.0.0.0.1.0.0.8.0.2.0.0, which is the
       encoding of a length of 8, followed by 8 subids encoding the
       protocolDirID of 1.2048, followed by a length of 2 and the
       2 subids encoding zero-valued
 parameters.

       Note that some combinations of index values may result in an
       index that exceeds 128 sub-identifiers in length, which exceeds
       the maximum for the SNMP protocol.  Implementations should take
       care to avoid such combinations."
  INDEX { protocolDirID, protocolDirParameters }
```

```
  ::= { protocolDirTable  1 }

ProtocolDirEntry ::= SEQUENCE {
  protocolDirID                 OCTET STRING,
  protocolDirParameters         OCTET STRING,
  protocolDirLocalIndex         Integer32,
  protocolDirDescr              DisplayString,
  protocolDirType               BITS,
  protocolDirAddressMapConfig   INTEGER,
  protocolDirHostConfig         INTEGER,
  protocolDirMatrixConfig       INTEGER,
  protocolDirOwner              OwnerString,
  protocolDirStatus             RowStatus
}

protocolDirID OBJECT-TYPE
  SYNTAX     OCTET STRING  (SIZE (4..128))
  MAX-ACCESS  not-accessible
  STATUS     current
  DESCRIPTION
      "A unique identifier for a particular protocol.  Standard
      identifiers will be defined in such a manner that they



      can often be used as specifications for new protocols - i.e.,
      a tree-structured assignment mechanism that matches the
      protocol encapsulation 'tree' and that has algorithmic
      assignment mechanisms for certain subtrees.  See RFC 2074 for
      more details.

      Despite the algorithmic mechanism, the probe will only place
      entries in here for those protocols it chooses to collect.  In
      other words, it need not populate this table with all
      possible ethernet protocol types, nor need it create them on
      the fly when it sees them.  Whether it does these
      things is a matter of product definition (cost/benefit,
      usability) and is up to the designer of the product.

      If an entry is written to this table with a protocolDirID that
      the agent doesn't understand, either
 directly or
      algorithmically, the SET request will be rejected with an
      inconsistentName or badValue (for SNMPv1) error."
  ::= { protocolDirEntry 1 }

protocolDirParameters OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (1..32))
```

```
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A set of parameters for the associated protocolDirID.
      See the associated RMON2 Protocol Identifiers document
      for a description of the possible parameters.  There
      will be one octet in this string for each sub-identifier in
      the protocolDirID, and the parameters will appear here in the
      same order as the associated sub-identifiers appear in the
      protocolDirID.

      Every node in the protocolDirID tree has a different, optional
      set of parameters defined (that is, the definition of
      parameters for a node is optional).  The proper parameter
      value for each node is included in this string.  Note that
 the
      inclusion of a parameter value in this string for each node is
      not optional.  What is optional is that a node may have no
      parameters defined, in which case the parameter field for that
      node will be zero."
  ::= { protocolDirEntry 2 }

protocolDirLocalIndex OBJECT-TYPE
  SYNTAX      Integer32 (1..2147483647)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION



      "The locally arbitrary but unique identifier associated
      with this protocolDir entry.

      The value for each supported protocol must remain constant at
      least from one re-initialization of the entity's network
      management system to the next re-initialization, except that
      if a protocol is deleted and re-created, it must be re-created
      with a new value that has not been used since the last
      re-initialization.

      The specific value is meaningful only within a given SNMP
      entity.  A protocolDirLocalIndex must not
 be re-used until the
      next agent restart in the event that the protocol directory
      entry is deleted."
  ::= { protocolDirEntry 3 }

protocolDirDescr OBJECT-TYPE
```

```
  SYNTAX      DisplayString (SIZE (1..64))
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "A textual description of the protocol encapsulation.
     A probe may choose to describe only a subset of the
     entire encapsulation (e.g., only the highest layer).

     This object is intended for human consumption only.

     This object may not be modified if the associated
     protocolDirStatus object is equal to active(1)."
  ::= { protocolDirEntry 4 }

protocolDirType OBJECT-TYPE
  SYNTAX      BITS {
                 extensible(0),
                 addressRecognitionCapable(1)
              }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "This object describes 2 attributes of this protocol
      directory entry.


 The presence or absence of the 'extensible' bit describes
       whether this protocol directory entry can be extended
       by the user by creating protocol directory entries that are
       children of this protocol.

       An example of an entry that will often allow extensibility is



       'ip.udp'.  The probe may automatically populate some children
       of this node, such as 'ip.udp.snmp' and 'ip.udp.dns'.
       A probe administrator or user may also populate additional
       children via remote SNMP requests that create entries in this
       table.  When a child node is added for a protocol for which the
       probe has no built-in support extending a parent node (for
       which the probe does have built-in support),
       that child node is not extendable.  This is termed 'limited
       extensibility'.

       When a child node is added through this extensibility
       mechanism, the values of protocolDirLocalIndex and
       protocolDirType
```

shall be assigned by the agent.

The other objects in the entry will be assigned by the manager who is creating the new entry.

This object also describes whether this agent can recognize addresses for this protocol, should it be a network-level protocol. That is, while a probe may be able to recognize packets of a particular network-layer protocol and count them, it takes additional logic to be able to recognize the addresses in this protocol and to populate network-layer or application-layer tables with the addresses in this protocol. If this bit is set, the agent will recognize network-layer addresses for this protocol and populate the network- and application-layer host and matrix tables with these protocols.

Note that when an entry is created, the agent will supply values for the bits that match the capabilities of the agent

with respect to this protocol. Note that since row creations usually exercise the limited extensibility feature, these bits will usually be set to zero."
::= { protocolDirEntry 5 }

protocolDirAddressMapConfig OBJECT-TYPE
SYNTAX INTEGER {
notSupported(1),
supportedOff(2),
supportedOn(3)
}
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This object describes and configures the probe's support for address mapping for this protocol. When the probe creates entries in this table for all protocols that it understands,

it will set the entry to notSupported(1) if it doesn't have the capability to perform address mapping for the protocol or if this protocol is not a network-layer protocol. When an entry is created in this table by a management operation as part of the limited extensibility feature,
the probe must set
this value to notSupported(1), because limited extensibility of the protocolDirTable does not extend to interpreting

addresses of the extended protocols.

If the value of this object is notSupported(1), the probe
will not perform address mapping for this protocol and
shall not allow this object to be changed to any other value.
If the value of this object is supportedOn(3), the probe
supports address mapping for this protocol and is configured
to perform address mapping for this protocol for all
addressMappingControlEntries and all interfaces.
If the value of this object is supportedOff(2), the probe
supports address mapping for this protocol but is configured
to not perform address mapping for this protocol for any
addressMappingControlEntries and all interfaces.
Whenever this value changes from supportedOn(3) to
supportedOff(2), the probe
shall delete all related entries in
the addressMappingTable."
::= { protocolDirEntry 6 }

protocolDirHostConfig OBJECT-TYPE
SYNTAX INTEGER {
notSupported(1),
supportedOff(2),
supportedOn(3)
}
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This object describes and configures the probe's support for
the network-layer and application-layer host tables for this
protocol. When the probe creates entries in this table for
all protocols that it understands, it will set the entry to
notSupported(1) if it doesn't have the capability to track the
nlHostTable for this protocol or if the alHostTable is
implemented but doesn't have the capability to track this
protocol. Note that if the alHostTable is implemented, the
probe may only support a protocol if it is supported in both
the nlHostTable and the
alHostTable.

If the associated protocolDirType object has the
addressRecognitionCapable bit set, then this is a network-
layer protocol for which the probe recognizes addresses, and

thus the probe will populate the nlHostTable and alHostTable
with addresses it discovers for this protocol.

```
      If the value of this object is notSupported(1), the probe
      will not track the nlHostTable or alHostTable for this
      protocol and shall not allow this object to be changed to any
      other value.  If the value of this object is supportedOn(3),
      the probe supports tracking of the nlHostTable and alHostTable
      for this protocol and is configured to track both tables
      for this protocol for all control entries and all interfaces.
      If the value of this object is supportedOff(2), the probe
      supports tracking of the nlHostTable and alHostTable for this
      protocol but is configured to not track these
 tables
      for any control entries or interfaces.
      Whenever this value changes from supportedOn(3) to
      supportedOff(2), the probe shall delete all related entries in
      the nlHostTable and alHostTable.

      Note that since each alHostEntry references 2 protocol
      directory entries, one for the network address and one for the
      type of the highest protocol recognized, an entry will
      only be created in that table if this value is supportedOn(3)
      for both protocols."
   ::= { protocolDirEntry 7 }

protocolDirMatrixConfig OBJECT-TYPE
   SYNTAX      INTEGER {
                  notSupported(1),
                  supportedOff(2),
                  supportedOn(3)
               }
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "This object describes and configures the probe's support for
      the network-layer and application-layer matrix tables for this
      protocol.  When the probe creates entries
 in this table for
      all protocols that it understands, it will set the entry to
      notSupported(1) if it doesn't have the capability to track the
      nlMatrixTables for this protocol or if the alMatrixTables are
      implemented but don't have the capability to track this
      protocol.  Note that if the alMatrix tables are implemented,
      the probe may only support a protocol if it is supported in
      both of the nlMatrixTables and both of the
      alMatrixTables.

      If the associated protocolDirType object has the
      addressRecognitionCapable bit set, then this is a network-
```

layer protocol for which the probe recognizes addresses, and
thus the probe will populate both of the nlMatrixTables and
both of the alMatrixTables with addresses it discovers for
this protocol.

If the value of this object is notSupported(1), the probe
will not track either of the nlMatrixTables or the
alMatrixTables
for this protocol and shall not allow this
object to be changed to any other value. If the value of this
object is supportedOn(3), the probe supports tracking of both
of the nlMatrixTables and (if implemented) both of the
alMatrixTables for this protocol and is configured to track
these tables for this protocol for all control entries and all
interfaces. If the value of this object is supportedOff(2),
the probe supports tracking of both of the nlMatrixTables and
(if implemented) both of the alMatrixTables for this protocol
but is configured to not track these tables for this
protocol for any control entries or interfaces.
Whenever this value changes from supportedOn(3) to
supportedOff(2), the probe shall delete all related entries in
the nlMatrixTables and the alMatrixTables.

Note that since each alMatrixEntry references 2 protocol
directory entries, one for
the network address and one for the
type of the highest protocol recognized, an entry will
only be created in that table if this value is supportedOn(3)
for both protocols."
::= { protocolDirEntry 8 }

protocolDirOwner OBJECT-TYPE
SYNTAX OwnerString
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The entity that configured this entry and is
therefore using the resources assigned to it."
::= { protocolDirEntry 9 }

protocolDirStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION

"The status of this protocol directory entry.

An entry may not exist in the active state unless all
objects in the entry have an appropriate value.

If this object is not equal to active(1), all associated
entries in the nlHostTable, nlMatrixSDTable, nlMatrixDSTable,
alHostTable, alMatrixSDTable, and alMatrixDSTable shall be
deleted."
::= { protocolDirEntry 10 }

--
-- Protocol Distribution Group (protocolDist)
--
-- Collects the relative amounts of octets and packets for the
-- different protocols detected on a network segment.
-- protocolDistControlTable,
-- protocolDistStatsTable

protocolDistControlTable OBJECT-TYPE
SYNTAX SEQUENCE OF ProtocolDistControlEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Controls the setup of protocol type distribution statistics
tables.

Implementations are encouraged to add an entry per monitored
interface upon initialization so that a default collection
of protocol statistics is available.

Rationale:
This table controls collection of very basic statistics
for any or all of the protocols detected on a given interface.
An NMS can use this table to quickly determine bandwidth
allocation utilized by different protocols.

A media-specific
statistics collection could also
be configured (e.g., etherStats, trPStats) to easily obtain
total frame, octet, and droppedEvents for the same
interface."
::= { protocolDist 1 }

protocolDistControlEntry OBJECT-TYPE

```
  SYNTAX      ProtocolDistControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A conceptual row in the protocolDistControlTable.

      An example of the indexing of this entry is
      protocolDistControlDroppedFrames.7"
  INDEX { protocolDistControlIndex }



  ::= { protocolDistControlTable 1 }

ProtocolDistControlEntry ::= SEQUENCE {
  protocolDistControlIndex               Integer32,
  protocolDistControlDataSource          DataSource,
  protocolDistControlDroppedFrames       Counter32,
  protocolDistControlCreateTime          LastCreateTime,
  protocolDistControlOwner               OwnerString,
  protocolDistControlStatus              RowStatus
}

protocolDistControlIndex
 OBJECT-TYPE
  SYNTAX      Integer32 (1..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A unique index for this protocolDistControlEntry."
  ::= { protocolDistControlEntry 1 }

protocolDistControlDataSource OBJECT-TYPE
  SYNTAX      DataSource
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The source of data for the this protocol distribution.

     The statistics in this group reflect all packets
     on the local network segment attached to the
     identified interface.

     This object may not be modified if the associated
     protocolDistControlStatus object is equal to active(1)."
  ::= { protocolDistControlEntry 2 }

protocolDistControlDroppedFrames OBJECT-TYPE
```

```
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The total number of frames that were received by the probe
     and therefore not accounted for in the *StatsDropEvents,
but
     that the probe chose not to count for this entry for
     whatever reason.  Most often, this event occurs when the probe
     is out of some resources and decides to shed load from this
     collection.

     This count does not include packets that were not counted
     because they had MAC-layer errors.



     Note that, unlike the dropEvents counter, this number is the
     exact number of frames dropped."
  ::= { protocolDistControlEntry 3 }

protocolDistControlCreateTime OBJECT-TYPE
  SYNTAX     LastCreateTime
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The value of sysUpTime when this control entry was last
     activated.  This can be used by the management station to
     ensure that the table has not been deleted and recreated
     between polls."
  ::= { protocolDistControlEntry 4 }

protocolDistControlOwner OBJECT-TYPE
  SYNTAX      OwnerString
  MAX-ACCESS  read-create
  STATUS      current
   DESCRIPTION
     "The entity that configured this entry and is
     therefore using the resources assigned to it."
  ::= { protocolDistControlEntry 5 }

protocolDistControlStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The status of this row.
```

```
      An entry may not exist in the active state unless all
      objects in the entry have an appropriate value.

      If this object is not equal to active(1), all associated
      entries in the protocolDistStatsTable shall be deleted."
  ::= { protocolDistControlEntry 6 }

-- per interface protocol distribution statistics table
protocolDistStatsTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ProtocolDistStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "An entry is made in this table for every protocol in the
      protocolDirTable that has been seen in at least one packet.
      Counters are updated
 in this table for every protocol type
      that is encountered when parsing a packet, but no counters are




      updated for packets with MAC-layer errors.

      Note that if a protocolDirEntry is deleted, all associated
      entries in this table are removed."
  ::= { protocolDist 2 }

protocolDistStatsEntry OBJECT-TYPE
  SYNTAX      ProtocolDistStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A conceptual row in the protocolDistStatsTable.

      The index is composed of the protocolDistControlIndex of the
      associated protocolDistControlEntry, followed by the
      protocolDirLocalIndex of the associated protocol that this
      entry represents.  In other words, the index identifies the
      protocol distribution an entry is a part of and the
      particular protocol that it represents.

      An example of the indexing of this entry is
      protocolDistStatsPkts.1.18"
  INDEX { protocolDistControlIndex,
 protocolDirLocalIndex }
  ::= { protocolDistStatsTable 1 }

ProtocolDistStatsEntry ::= SEQUENCE {
```

```
  protocolDistStatsPkts                ZeroBasedCounter32,
  protocolDistStatsOctets              ZeroBasedCounter32
}

protocolDistStatsPkts OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The number of packets of this protocol type received
      without errors.  Note that this is the number of
      link-layer packets, so if a single network-layer packet
      is fragmented into several link-layer frames, this counter
      is incremented several times."
  ::= { protocolDistStatsEntry 1 }

protocolDistStatsOctets OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The number of octets in packets of this protocol type




      received since it was added to the protocolDistStatsTable
      (excluding framing bits,
 but including FCS octets), except for
      those octets in packets that contained errors.

      Note that this doesn't count just those octets in the
      particular protocol frames but includes the entire packet
      that contained the protocol."
  ::= { protocolDistStatsEntry 2 }

--
-- Address Map Group   (addressMap)
--
-- Lists MAC address to network address bindings discovered by the
-- probe and what interface they were last seen on.
--    addressMapControlTable
--    addressMapTable

addressMapInserts OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
```

"The number of times an address mapping entry has been
inserted into the addressMapTable. If an entry is inserted,
then deleted, and then inserted, this counter will be
incremented by 2.

Note that the table size can be determined by subtracting
addressMapDeletes from addressMapInserts."
::= { addressMap 1 }

addressMapDeletes
OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of times an address mapping entry has been
deleted from the addressMapTable (for any reason). If
an entry is deleted, then inserted, and then deleted, this
counter will be incremented by 2.

Note that the table size can be determined by subtracting
addressMapDeletes from addressMapInserts."
::= { addressMap 2 }

addressMapMaxDesiredEntries OBJECT-TYPE
SYNTAX Integer32 (-1..2147483647)
MAX-ACCESS read-write

STATUS current
DESCRIPTION
"The maximum number of entries that are desired in the
addressMapTable. The probe will not create more than
this number of entries in the table but may choose to create
fewer entries in this table for any reason, including the lack
of resources.

If this object is set to a value less than the current number
of entries, enough entries are chosen in an
implementation-dependent manner and deleted so that the number
of entries in the table equals the value of this object.

If this value is set to -1, the probe may create any number
of entries in this table.

This object may be used to control how resources are allocated
on the probe for the various RMON functions."

```
  ::= { addressMap 3 }

addressMapControlTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF AddressMapControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A table to control the collection of mappings from network
      layer address to physical address to interface.

     Note that this is not like the typical RMON
     controlTable and dataTable in which each entry creates
     its own data table.  Each entry in this table enables the
     discovery of addresses on a new interface and the placement
     of address
 mappings into the central addressMapTable.

     Implementations are encouraged to add an entry per monitored
     interface upon initialization so that a default collection
     of address mappings is available."
  ::= { addressMap 4 }

addressMapControlEntry OBJECT-TYPE
  SYNTAX      AddressMapControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A conceptual row in the addressMapControlTable.

     An example of the indexing of this entry is
     addressMapControlDroppedFrames.1"



  INDEX { addressMapControlIndex }
  ::= { addressMapControlTable 1 }

AddressMapControlEntry ::= SEQUENCE {
  addressMapControlIndex             Integer32,
  addressMapControlDataSource        DataSource,
  addressMapControlDroppedFrames     Counter32,
  addressMapControlOwner             OwnerString,
  addressMapControlStatus            RowStatus
}

addressMapControlIndex OBJECT-TYPE
  SYNTAX      Integer32 (1..65535)
  MAX-ACCESS
```

not-accessible
STATUS current
DESCRIPTION
"A unique index for this entry in the addressMapControlTable."
::= { addressMapControlEntry 1 }

addressMapControlDataSource OBJECT-TYPE
SYNTAX DataSource
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The source of data for this addressMapControlEntry."
::= { addressMapControlEntry 2 }

addressMapControlDroppedFrames OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The total number of frames that were received by the probe
and therefore not accounted for in the *StatsDropEvents, but
that the probe chose not to count for this entry for
whatever reason. Most often, this event occurs when the probe
is out of some resources and decides to shed load from this
collection.

This count does not include packets that were not counted
because they had MAC-layer errors.

Note that, unlike the dropEvents counter, this number is the
exact number of frames dropped."
::= { addressMapControlEntry 3 }

addressMapControlOwner OBJECT-TYPE
SYNTAX OwnerString

MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The entity that configured this entry and is
therefore using the resources assigned to it."
::= { addressMapControlEntry 4 }

addressMapControlStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create

```
  STATUS      current
  DESCRIPTION
     "The status of this addressMap control entry.

     An entry may not exist in the active state unless all
     objects in the entry have an appropriate value.

     If this object is not equal to active(1), all associated
     entries in the addressMapTable shall be deleted."
  ::= { addressMapControlEntry 5 }

addressMapTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF AddressMapEntry
  MAX-ACCESS  not-accessible
   STATUS      current
  DESCRIPTION
     "A table of mappings from network layer address to physical
     address to interface.

     The probe will add entries to this table based on the source
     MAC and network addresses seen in packets without MAC-level
     errors.  The probe will populate this table for all protocols
     in the protocol directory table whose value of
     protocolDirAddressMapConfig is equal to supportedOn(3), and
     will delete any entries whose protocolDirEntry is deleted or
     has a protocolDirAddressMapConfig value of supportedOff(2)."
  ::= { addressMap 5 }

addressMapEntry OBJECT-TYPE
  SYNTAX      AddressMapEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A conceptual row in the addressMapTable.

     The protocolDirLocalIndex in the index identifies the network
     layer protocol of the addressMapNetworkAddress.

     An example of the indexing of this entry is
      addressMapSource.783495.18.4.128.2.6.6.11.1.3.6.1.2.1.2.2.1.1.1.

     Note that some combinations of index values may result in an
     index that exceeds 128 sub-identifiers in length, which exceeds
     the maximum for the SNMP protocol.  Implementations should take
     care to avoid such combinations."
```

```
  INDEX { addressMapTimeMark, protocolDirLocalIndex,
          addressMapNetworkAddress, addressMapSource }
  ::= { addressMapTable 1 }

AddressMapEntry ::= SEQUENCE {
  addressMapTimeMark              TimeFilter,
  addressMapNetworkAddress          OCTET STRING,
  addressMapSource                OBJECT IDENTIFIER,
  addressMapPhysicalAddress         OCTET STRING,
  addressMapLastChange            TimeStamp
}

addressMapTimeMark OBJECT-TYPE
  SYNTAX      TimeFilter
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A TimeFilter for this entry.  See the TimeFilter textual
     convention to see how this
 works."
  ::= { addressMapEntry 1 }

addressMapNetworkAddress OBJECT-TYPE
  SYNTAX      OCTET STRING (SIZE (1..255))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The network address for this relation.

     This is represented as an octet string with
     specific semantics and length as identified
     by the protocolDirLocalIndex component of the
     index.

     For example, if the protocolDirLocalIndex indicates an
     encapsulation of ip, this object is encoded as a length
     octet of 4, followed by the 4 octets of the IP address,
     in network byte order."
  ::= { addressMapEntry 2 }

addressMapSource OBJECT-TYPE
  SYNTAX      OBJECT IDENTIFIER



  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
```

"The interface or port on which the associated network
address was most recently seen.

If this address mapping was discovered on an interface, this
object shall
identify the instance of the ifIndex
object, defined in [RFC2863], for the desired interface.
For example, if an entry were to receive data from
interface #1, this object would be set to ifIndex.1.

If this address mapping was discovered on a port, this
object shall identify the instance of the rptrGroupPortIndex
object, defined in [RFC2108], for the desired port.
For example, if an entry were to receive data from
group #1, port #1, this object would be set to
rptrGroupPortIndex.1.1.

Note that while the dataSource associated with this entry
may only point to index objects, this object may at times
point to repeater port objects. This situation occurs when
the dataSource points to an interface that is a locally
attached repeater and the agent has additional information
about the source port of traffic seen on that repeater."
::= { addressMapEntry 3 }

addressMapPhysicalAddress
OBJECT-TYPE
SYNTAX OCTET STRING
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The last source physical address on which the associated
network address was seen. If the protocol of the associated
network address was encapsulated inside of a network-level or
higher protocol, this will be the address of the next-lower
protocol with the addressRecognitionCapable bit enabled and
will be formatted as specified for that protocol."
::= { addressMapEntry 4 }

addressMapLastChange OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime at the time this entry was last
created or the values of the physical address changed.

```
      This can be used to help detect duplicate address problems, in
      which case this object will be updated frequently."
   ::= { addressMapEntry 5 }

--
-- Network Layer Host Group
--
--
 Counts the amount of traffic sent from and to each network address
-- discovered by the probe.
-- Note that while the hlHostControlTable also has objects that
-- control an optional alHostTable, implementation of the alHostTable is
-- not required to fully implement this group.

hlHostControlTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF HlHostControlEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "A list of higher-layer (i.e., non-MAC) host table control
      entries.

      These entries will enable the collection of the network- and
      application-level host tables indexed by network addresses.
      Both the network- and application-level host tables are
      controlled by this table so that they will both be created
      and deleted at the same time, further increasing the ease with
      which they can be implemented as a single datastore.  (Note that
      if an implementation stores application-layer host records
 in
      memory, it can derive network-layer host records from them.)

      Entries in the nlHostTable will be created on behalf of each
      entry in this table.  Additionally, if this probe implements
      the alHostTable, entries in the alHostTable will be created on
      behalf of each entry in this table.

      Implementations are encouraged to add an entry per monitored
      interface upon initialization so that a default collection
      of host statistics is available."
   ::= { nlHost 1 }

hlHostControlEntry OBJECT-TYPE
   SYNTAX      HlHostControlEntry
   MAX-ACCESS  not-accessible
   STATUS      current
```

```
  DESCRIPTION
      "A conceptual row in the hlHostControlTable.

      An example of the indexing of this entry is



      hlHostControlNlDroppedFrames.1"
  INDEX { hlHostControlIndex }
  ::= { hlHostControlTable 1 }

HlHostControlEntry ::= SEQUENCE {
  hlHostControlIndex              Integer32,
  hlHostControlDataSource
   DataSource,
  hlHostControlNlDroppedFrames    Counter32,
  hlHostControlNlInserts          Counter32,
  hlHostControlNlDeletes          Counter32,
  hlHostControlNlMaxDesiredEntries Integer32,
  hlHostControlAlDroppedFrames    Counter32,
  hlHostControlAlInserts          Counter32,
  hlHostControlAlDeletes          Counter32,
  hlHostControlAlMaxDesiredEntries Integer32,
  hlHostControlOwner              OwnerString,
  hlHostControlStatus             RowStatus
}

hlHostControlIndex OBJECT-TYPE
  SYNTAX      Integer32 (1..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "An index that uniquely identifies an entry in the
      hlHostControlTable.  Each such entry defines
      a function that discovers hosts on a particular
      interface and places statistics about them in the
      nlHostTable, and optionally in the alHostTable, on
      behalf of this hlHostControlEntry."
  ::= { hlHostControlEntry 1 }

hlHostControlDataSource
 OBJECT-TYPE
  SYNTAX      DataSource
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "The source of data for the associated host tables.
```

The statistics in this group reflect all packets
on the local network segment attached to the
identified interface.

This object may not be modified if the associated
hlHostControlStatus object is equal to active(1)."
::= { hlHostControlEntry 2 }

hlHostControlNlDroppedFrames OBJECT-TYPE

SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The total number of frames that were received by the probe
and therefore not accounted for in the *StatsDropEvents, but
that the probe chose not to count for the associated
nlHost entries for whatever reason. Most often, this event
occurs when the probe is out of some resources and decides to
shed load from this collection.

This count does not include packets that were not counted
because they had MAC-layer errors.

Note that if the nlHostTable is inactive because no protocols
are enabled in the protocol directory, this value should be 0.

Note that, unlike the dropEvents counter, this number is the
exact number of frames dropped."
::= { hlHostControlEntry 3 }

hlHostControlNlInserts OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of times an nlHost entry has been
inserted into the nlHost table. If an entry is inserted, then
deleted, and then inserted, this counter will be incremented
by 2.

To allow for efficient implementation strategies, agents may
delay updating this object for short periods of time. For
example, an implementation strategy may allow internal
data structures to differ from those visible via SNMP for

short
periods of time. This counter may reflect the internal
data structures for those short periods of time.

Note that the table size can be determined by subtracting
hlHostControlNlDeletes from hlHostControlNlInserts."
::= { hlHostControlEntry 4 }

hlHostControlNlDeletes OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of times an nlHost entry has been

deleted from the nlHost table (for any reason). If an entry
is deleted, then inserted, and then deleted, this counter will
be incremented by 2.

To allow for efficient implementation strategies, agents may
delay updating this object for short periods of time. For
example, an implementation strategy may allow internal
data structures to differ from those visible via SNMP for
short periods of time. This counter may reflect the internal
data structures for those short
periods of time.

Note that the table size can be determined by subtracting
hlHostControlNlDeletes from hlHostControlNlInserts."
::= { hlHostControlEntry 5 }

hlHostControlNlMaxDesiredEntries OBJECT-TYPE
SYNTAX Integer32 (-1..2147483647)
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The maximum number of entries that are desired in the
nlHostTable on behalf of this control entry. The probe will
not create more than this number of associated entries in the
table but may choose to create fewer entries in this table
for any reason, including the lack of resources.

If this object is set to a value less than the current number
of entries, enough entries are chosen in an
implementation-dependent manner and deleted so that the number
of entries in the table equals the value of this object.

If this value is set to -1, the probe may create any number

of entries in this table. If the associated
hlHostControlStatus object is equal to 'active', this
object may not be modified.

This object may be used to control how resources are allocated
on the probe for the various RMON functions."
::= { hlHostControlEntry 6 }

hlHostControlAlDroppedFrames OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The total number of frames that were received by the probe
and therefore not accounted for in the *StatsDropEvents, but
that the probe chose not to count for the associated

alHost entries for whatever reason. Most often, this event
occurs when the probe is out of some resources and decides to
shed load from this collection.

This count does not include packets that were not counted
because they had MAC-layer errors.

Note that if the alHostTable is not implemented or is inactive

because no protocols are enabled in the protocol directory,
this value should be 0.

Note that, unlike the dropEvents counter, this number is the
exact number of frames dropped."
::= { hlHostControlEntry 7 }

hlHostControlAlInserts OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of times an alHost entry has been
inserted into the alHost table. If an entry is inserted, then
deleted, and then inserted, this counter will be incremented
by 2.

To allow for efficient implementation strategies, agents may
delay updating this object for short periods of time. For
example, an implementation strategy may allow internal
data structures to differ from those visible via SNMP for
short periods of time. This counter may reflect the internal
data structures for those short periods of time.

Note that the table size can
be determined by subtracting
hlHostControlAlDeletes from hlHostControlAlInserts."
::= { hlHostControlEntry 8 }

hlHostControlAlDeletes OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of times an alHost entry has been
deleted from the alHost table (for any reason). If an entry
is deleted, then inserted, and then deleted, this counter will
be incremented by 2.

To allow for efficient implementation strategies, agents may
delay updating this object for short periods of time. For

example, an implementation strategy may allow internal
data structures to differ from those visible via SNMP for
short periods of time. This counter may reflect the internal
data structures for those short periods of time.

Note that the table size can be determined by subtracting
hlHostControlAlDeletes from hlHostControlAlInserts."

::= { hlHostControlEntry 9 }

hlHostControlAlMaxDesiredEntries OBJECT-TYPE
SYNTAX Integer32 (-1..2147483647)
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The maximum number of entries that are desired in the alHost
table on behalf of this control entry. The probe will not
create more than this number of associated entries in the
table but may choose to create fewer entries in this table
for any reason, including the lack of resources.

```
      If this object is set to a value less than the current number
      of entries, enough entries are chosen in an
      implementation-dependent manner and deleted so that the number
      of entries in the table equals the value of this object.

      If this value is set to -1, the probe may create any number
      of entries in this table.  If the associated
      hlHostControlStatus object is equal to 'active', this
      object may not be modified.


   This object may be used to control how resources are allocated
      on the probe for the various RMON functions."
   ::= { hlHostControlEntry 10 }

hlHostControlOwner OBJECT-TYPE
   SYNTAX      OwnerString
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "The entity that configured this entry and is
      therefore using the resources assigned to it."
   ::= { hlHostControlEntry 11 }

hlHostControlStatus OBJECT-TYPE
   SYNTAX      RowStatus
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION



      "The status of this hlHostControlEntry.

      An entry may not exist in the active state unless all
      objects in the entry have an appropriate value.

      If this object is not equal to active(1), all associated
      entries in the nlHostTable and alHostTable shall be deleted."
   ::= { hlHostControlEntry 12 }

nlHostTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF NlHostEntry
   MAX-ACCESS  not-accessible
   STATUS
   current
   DESCRIPTION
      "A collection of statistics for a particular network layer
```

```
        address that has been discovered on an interface of this
        device.

        The probe will populate this table for all network layer
        protocols in the protocol directory table whose value of
        protocolDirHostConfig is equal to supportedOn(3), and
        will delete any entries whose protocolDirEntry is deleted or
        has a protocolDirHostConfig value of supportedOff(2).

        The probe will add to this table all addresses seen
        as the source or destination address in all packets with no
        MAC errors, and will increment octet and packet counts in the
        table for all packets with no MAC errors."
::= { nlHost 2 }

nlHostEntry OBJECT-TYPE
   SYNTAX      NlHostEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "A conceptual row in the nlHostTable.

      The hlHostControlIndex value in the index identifies the
       hlHostControlEntry on whose behalf this entry was created.
      The protocolDirLocalIndex value in the index identifies the
      network layer protocol of the nlHostAddress.

      An example of the indexing of this entry is
      nlHostOutPkts.1.783495.18.4.128.2.6.6.

      Note that some combinations of index values may result in an
      index that exceeds 128 sub-identifiers in length, which exceeds
      the maximum for the SNMP protocol.  Implementations should take



      care to avoid such combinations."
   INDEX { hlHostControlIndex, nlHostTimeMark,
           protocolDirLocalIndex, nlHostAddress }
   ::= { nlHostTable 1 }

NlHostEntry ::= SEQUENCE {
   nlHostTimeMark            TimeFilter,
   nlHostAddress             OCTET STRING,
   nlHostInPkts              ZeroBasedCounter32,
   nlHostOutPkts             ZeroBasedCounter32,
   nlHostInOctets            ZeroBasedCounter32,
   nlHostOutOctets           ZeroBasedCounter32,
```

```
    nlHostOutMacNonUnicastPkts  ZeroBasedCounter32,
    nlHostCreateTime            LastCreateTime
}

nlHostTimeMark OBJECT-TYPE
    SYNTAX      TimeFilter
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A TimeFilter for this entry.  See the TimeFilter textual
        convention to see how this works."
    ::= { nlHostEntry 1 }

nlHostAddress OBJECT-TYPE
    SYNTAX      OCTET STRING  (SIZE (1..255))
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The network address for this nlHostEntry.

        This is represented as an octet string with
        specific semantics and length as identified
        by the protocolDirLocalIndex component of the index.

        For example, if the protocolDirLocalIndex indicates an
        encapsulation of IP, this object is encoded as a length
        octet of 4, followed by the 4 octets of the IP address,
        in network byte order."
    ::= { nlHostEntry 2 }

nlHostInPkts OBJECT-TYPE

    SYNTAX      ZeroBasedCounter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of packets without errors transmitted to




        this address since it was added to the nlHostTable.  Note that
        this is the number of link-layer packets, so if a single
        network-layer packet is fragmented into several link-layer
        frames, this counter is incremented several times."
    ::= { nlHostEntry 3 }

nlHostOutPkts OBJECT-TYPE
    SYNTAX      ZeroBasedCounter32
```

```
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of packets without errors transmitted by
     this address since it was added to the nlHostTable.  Note that
     this is the number of link-layer packets, so if a single
     network-layer packet is fragmented into several link-layer
     frames, this counter is incremented several times."
  ::= { nlHostEntry 4 }

nlHostInOctets OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS
 read-only
  STATUS      current
  DESCRIPTION
     "The number of octets transmitted to this address
     since it was added to the nlHostTable (excluding
     framing bits, but including FCS octets), excluding
     octets in packets that contained errors.

     Note that this doesn't count just those octets in the particular
     protocol frames but includes the entire packet that contained
     the protocol."
  ::= { nlHostEntry 5 }

nlHostOutOctets OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of octets transmitted by this address
     since it was added to the nlHostTable (excluding
     framing bits, but including FCS octets), excluding
     octets in packets that contained errors.

     Note that this doesn't count just those octets in the particular
     protocol frames but includes the entire packet that contained
     the protocol."
  ::=
 { nlHostEntry 6 }



nlHostOutMacNonUnicastPkts OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
```

```
  STATUS      current
  DESCRIPTION
      "The number of packets without errors transmitted by this
      address that were directed to any MAC broadcast addresses
      or to any MAC multicast addresses since this host was
      added to the nlHostTable.  Note that this is the number of
      link-layer packets, so if a single network-layer packet is
      fragmented into several link-layer frames, this counter is
      incremented several times."
  ::= { nlHostEntry 7 }

nlHostCreateTime OBJECT-TYPE
  SYNTAX     LastCreateTime
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
      "The value of sysUpTime when this entry was last activated.
      This can be used by the management station to ensure that the
      entry has not been deleted and recreated between polls."
  ::= { nlHostEntry 8 }

--
-- Network Layer Matrix
 Group
--
-- Counts the amount of traffic sent between each pair of network
-- addresses discovered by the probe.
-- Note that while the hlMatrixControlTable also has objects that
-- control optional alMatrixTables, implementation of the
-- alMatrixTables is not required to fully implement this group.

hlMatrixControlTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF HlMatrixControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A list of higher-layer (i.e., non-MAC) matrix control entries.

      These entries will enable the collection of the network- and
      application-level matrix tables containing conversation
      statistics indexed by pairs of network addresses.
      Both the network- and application-level matrix tables are
      controlled by this table so that they will both be created
      and deleted at the same time, further increasing the ease with
      which they can be implemented as a single datastore.  (Note that
       if an implementation stores application-layer matrix records
```

```
      in memory, it can derive network-layer matrix records from
      them.)

      Entries in the nlMatrixSDTable and nlMatrixDSTable will be
      created on behalf of each entry in this table.  Additionally,
      if this probe implements the alMatrix tables, entries in the
      alMatrix tables will be created on behalf of each entry in
      this table."
  ::= { nlMatrix 1 }

hlMatrixControlEntry OBJECT-TYPE
  SYNTAX      HlMatrixControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A conceptual row in the hlMatrixControlTable.

      An example of indexing of this entry is
      hlMatrixControlNlDroppedFrames.1"
  INDEX { hlMatrixControlIndex }
  ::= { hlMatrixControlTable 1 }

HlMatrixControlEntry ::= SEQUENCE {
  hlMatrixControlIndex              Integer32,
  hlMatrixControlDataSource         DataSource,
  hlMatrixControlNlDroppedFrames
      Counter32,
  hlMatrixControlNlInserts          Counter32,
  hlMatrixControlNlDeletes          Counter32,
  hlMatrixControlNlMaxDesiredEntries  Integer32,
  hlMatrixControlAlDroppedFrames    Counter32,
  hlMatrixControlAlInserts          Counter32,
  hlMatrixControlAlDeletes          Counter32,
  hlMatrixControlAlMaxDesiredEntries  Integer32,
  hlMatrixControlOwner              OwnerString,
  hlMatrixControlStatus             RowStatus
}

hlMatrixControlIndex OBJECT-TYPE
  SYNTAX      Integer32 (1..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "An index that uniquely identifies an entry in the
      hlMatrixControlTable.  Each such entry defines
      a function that discovers conversations on a particular
      interface and places statistics about them in the
```

nlMatrixSDTable and the nlMatrixDSTable, and optionally the
alMatrixSDTable and alMatrixDSTable, on
behalf of this

hlMatrixControlEntry."
::= { hlMatrixControlEntry 1 }

hlMatrixControlDataSource OBJECT-TYPE
SYNTAX DataSource
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The source of the data for the associated matrix tables.

The statistics in this group reflect all packets
on the local network segment attached to the
identified interface.

This object may not be modified if the associated
hlMatrixControlStatus object is equal to active(1)."
::= { hlMatrixControlEntry 2 }

hlMatrixControlNlDroppedFrames OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The total number of frames that were received by the probe
and therefore not accounted for in the *StatsDropEvents, but
that the probe chose not to count for this entry for
whatever reason. Most often, this event occurs when the probe
is out of
some resources and decides to shed load from this
collection.

This count does not include packets that were not counted
because they had MAC-layer errors.

Note that if the nlMatrixTables are inactive because no
protocols are enabled in the protocol directory, this value
should be 0.

Note that, unlike the dropEvents counter, this number is the
exact number of frames dropped."
::= { hlMatrixControlEntry 3 }

```
hlMatrixControlNlInserts OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of times an nlMatrix entry has been
     inserted into the nlMatrix tables.  If an entry is inserted,



     then deleted, and then inserted, this counter will be
     incremented by 2.  The addition of a conversation into both
     the nlMatrixSDTable and nlMatrixDSTable shall be counted as
     two insertions (even though every addition into one table must
      be accompanied by an insertion into the other).

     To allow for efficient implementation strategies, agents may
     delay updating this object for short periods of time.  For
     example, an implementation strategy may allow internal
     data structures to differ from those visible via SNMP for
     short periods of time.  This counter may reflect the internal
     data structures for those short periods of time.

     Note that the sum of then nlMatrixSDTable and nlMatrixDSTable
     sizes can be determined by subtracting
     hlMatrixControlNlDeletes from hlMatrixControlNlInserts."
  ::= { hlMatrixControlEntry 4 }

hlMatrixControlNlDeletes OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of times an nlMatrix entry has been
     deleted from the nlMatrix tables (for any reason).  If an
     entry is deleted, then inserted, and then deleted, this
     counter
 will be incremented by 2.  The deletion of a
     conversation from both the nlMatrixSDTable and nlMatrixDSTable
     shall be counted as two deletions (even though every deletion
     from one table must be accompanied by a deletion from the
     other).

     To allow for efficient implementation strategies, agents may
     delay updating this object for short periods of time.  For
     example, an implementation strategy may allow internal
     data structures to differ from those visible via SNMP for
     short periods of time.  This counter may reflect the internal
```

data structures for those short periods of time.

Note that the table size can be determined by subtracting
hlMatrixControlNlDeletes from hlMatrixControlNlInserts."
::= { hlMatrixControlEntry 5 }

hlMatrixControlNlMaxDesiredEntries OBJECT-TYPE
SYNTAX Integer32 (-1..2147483647)
MAX-ACCESS read-create
STATUS current
DESCRIPTION

"The
maximum number of entries that are desired in the
nlMatrix tables on behalf of this control entry. The probe
will not create more than this number of associated entries in
the table but may choose to create fewer entries in this
table for any reason, including the lack of resources.

If this object is set to a value less than the current number
of entries, enough entries are chosen in an
implementation-dependent manner and deleted so that the number
of entries in the table equals the value of this object.

If this value is set to -1, the probe may create any number
of entries in this table. If the associated
hlMatrixControlStatus object is equal to 'active', this
object may not be modified.

This object may be used to control how resources are allocated
on the probe for the various RMON functions."
::= { hlMatrixControlEntry 6 }

hlMatrixControlAlDroppedFrames OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The total number of frames that were received by the probe
and therefore not accounted for in the *StatsDropEvents, but
that the probe chose not to count for this entry for
whatever reason. Most often, this event occurs when the probe
is out of some resources and decides to shed load from this
collection.

This count does not include packets that were not counted

because they had MAC-layer errors.

Note that if the alMatrixTables are not implemented or are inactive because no protocols are enabled in the protocol directory, this value should be 0.

Note that, unlike the dropEvents counter, this number is the exact number of frames dropped."

::= { hlMatrixControlEntry 7 }

hlMatrixControlAlInserts OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"The number of times an alMatrix entry has been inserted into the alMatrix tables. If an entry is inserted, then deleted, and then inserted, this counter will be incremented by 2. The addition of a conversation into both the alMatrixSDTable and alMatrixDSTable shall be counted as two insertions (even though every addition into one table must be accompanied by an insertion into the other).

To allow for efficient implementation strategies, agents may delay updating this object for short periods of time. For example, an implementation strategy may allow internal data structures to differ from those visible via SNMP for short periods of time. This counter may reflect the internal data structures for those short periods of time.

Note that the table size can be determined by subtracting hlMatrixControlAlDeletes from hlMatrixControlAlInserts."

::= { hlMatrixControlEntry 8 }

hlMatrixControlAlDeletes OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"The number of times an alMatrix entry has been deleted from the alMatrix tables. If an entry is deleted, then inserted, and then deleted, this counter will be incremented by 2. The deletion of a conversation from both the alMatrixSDTable and alMatrixDSTable shall be counted as

two deletions (even though every deletion from one table must
be accompanied by a deletion from the other).

To allow for efficient implementation strategies, agents may
delay updating this object for short periods of time. For
example, an implementation strategy may allow internal
data structures to differ from those visible via SNMP for
short periods of time. This counter may reflect the internal
data structures for those short periods of time.

Note
that the table size can be determined by subtracting
hlMatrixControlAlDeletes from hlMatrixControlAlInserts."
::= { hlMatrixControlEntry 9 }

hlMatrixControlAlMaxDesiredEntries OBJECT-TYPE
SYNTAX Integer32 (-1..2147483647)
MAX-ACCESS read-create
STATUS current
DESCRIPTION

"The maximum number of entries that are desired in the
alMatrix tables on behalf of this control entry. The probe
will not create more than this number of associated entries in
the table but may choose to create fewer entries in this
table for any reason, including the lack of resources.

If this object is set to a value less than the current number
of entries, enough entries are chosen in an
implementation-dependent manner and deleted so that the number
of entries in the table equals the value of this object.

If this value is set to -1, the probe may create any number
of entries in this
table. If the associated
hlMatrixControlStatus object is equal to 'active', this
object may not be modified.

This object may be used to control how resources are allocated
on the probe for the various RMON functions."
::= { hlMatrixControlEntry 10 }

hlMatrixControlOwner OBJECT-TYPE
SYNTAX OwnerString
MAX-ACCESS read-create
STATUS current

```
  DESCRIPTION
      "The entity that configured this entry and is
      therefore using the resources assigned to it."
  ::= { hlMatrixControlEntry 11 }

hlMatrixControlStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "The status of this hlMatrixControlEntry.

      An entry may not exist in the active state unless all
      objects in the entry have an appropriate value.

      If this object is not equal to active(1), all
      associated entries in the nlMatrixSDTable,
      nlMatrixDSTable, alMatrixSDTable,
 and alMatrixDSTable
      shall be deleted by the agent."
  ::= { hlMatrixControlEntry 12 }

nlMatrixSDTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF NlMatrixSDEntry
  MAX-ACCESS  not-accessible



  STATUS      current
  DESCRIPTION
      "A list of traffic matrix entries that collect statistics for
      conversations between two network-level addresses.  This table
      is indexed first by the source address and then by the
      destination address to make it convenient to collect all
      conversations from a particular address.

      The probe will populate this table for all network layer
      protocols in the protocol directory table whose value of
      protocolDirMatrixConfig is equal to supportedOn(3), and
      will delete any entries whose protocolDirEntry is deleted or
      has a protocolDirMatrixConfig value of supportedOff(2).

      The probe will add to this table all pairs of addresses
      seen in all packets with no
 MAC errors and will increment
      octet and packet counts in the table for all packets with no
      MAC errors.
```

```
      Further, this table will only contain entries that have a
      corresponding entry in the nlMatrixDSTable with the same
      source address and destination address."
   ::= { nlMatrix 2 }

nlMatrixSDEntry OBJECT-TYPE
   SYNTAX      NlMatrixSDEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "A conceptual row in the nlMatrixSDTable.

      The hlMatrixControlIndex value in the index identifies the
      hlMatrixControlEntry on whose behalf this entry was created.
      The protocolDirLocalIndex value in the index identifies the
      network-layer protocol of the nlMatrixSDSourceAddress and
      nlMatrixSDDestAddress.

      An example of the indexing of this table is
      nlMatrixSDPkts.1.783495.18.4.128.2.6.6.4.128.2.6.7.

      Note that some combinations of index values may result in an

 index that exceeds 128 sub-identifiers in length, which exceeds
      the maximum for the SNMP protocol.  Implementations should take
      care to avoid such combinations."
   INDEX { hlMatrixControlIndex, nlMatrixSDTimeMark,
           protocolDirLocalIndex,
           nlMatrixSDSourceAddress, nlMatrixSDDestAddress }
   ::= { nlMatrixSDTable 1 }



NlMatrixSDEntry ::= SEQUENCE {
   nlMatrixSDTimeMark             TimeFilter,
   nlMatrixSDSourceAddress        OCTET STRING,
   nlMatrixSDDestAddress          OCTET STRING,
   nlMatrixSDPkts                 ZeroBasedCounter32,
   nlMatrixSDOctets               ZeroBasedCounter32,
   nlMatrixSDCreateTime           LastCreateTime
}

nlMatrixSDTimeMark OBJECT-TYPE
   SYNTAX      TimeFilter
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "A TimeFilter for this entry.  See the TimeFilter textual
```

convention to see how this works."
::= { nlMatrixSDEntry 1 }

nlMatrixSDSourceAddress OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (1..255))
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The network source address for this nlMatrixSDEntry.

This is represented as an octet string with
specific semantics and length as identified
by the protocolDirLocalIndex component of the index.

For example, if the protocolDirLocalIndex indicates an
encapsulation of IP, this object is encoded as a length
octet of 4, followed by the 4 octets of the IP address,
in network byte order."
::= { nlMatrixSDEntry 2 }

nlMatrixSDDestAddress OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (1..255))
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The network destination address for this
nlMatrixSDEntry.

This is represented as an octet string with
specific semantics and length as identified
by the protocolDirLocalIndex component of the index.

For example, if the protocolDirLocalIndex indicates an

encapsulation of IP, this object is encoded as a length
octet of 4, followed by the 4 octets of the IP address,
in network byte order."
::= { nlMatrixSDEntry 3 }

nlMatrixSDPkts OBJECT-TYPE
SYNTAX ZeroBasedCounter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of packets without errors transmitted from the
source address to the destination address since this entry was

added to the nlMatrixSDTable. Note that this is the number of
link-layer packets, so if a single network-layer packet is
fragmented into several link-layer frames, this counter is
incremented several times."
::= { nlMatrixSDEntry 4 }

nlMatrixSDOctets OBJECT-TYPE
SYNTAX ZeroBasedCounter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of octets transmitted from the source address to

the destination address since this entry was added to the
nlMatrixSDTable (excluding framing bits, but
including FCS octets), excluding octets in packets that
contained errors.

Note that this doesn't count just those octets in the particular
protocol frames but includes the entire packet that contained
the protocol."
::= { nlMatrixSDEntry 5 }

nlMatrixSDCreateTime OBJECT-TYPE
SYNTAX LastCreateTime
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime when this entry was last activated.
This can be used by the management station to ensure that the
entry has not been deleted and recreated between polls."
::= { nlMatrixSDEntry 6 }

-- Traffic matrix tables from destination to source

nlMatrixDSTable OBJECT-TYPE

SYNTAX SEQUENCE OF NlMatrixDSEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"A list of traffic matrix
entries that collect statistics for
conversations between two network-level addresses. This table
is indexed first by the destination address and then by the

source address to make it convenient to collect all
conversations to a particular address.

The probe will populate this table for all network layer
protocols in the protocol directory table whose value of
protocolDirMatrixConfig is equal to supportedOn(3), and
will delete any entries whose protocolDirEntry is deleted or
has a protocolDirMatrixConfig value of supportedOff(2).

The probe will add to this table all pairs of addresses
seen in all packets with no MAC errors and will increment
octet and packet counts in the table for all packets with no
MAC errors.

Further, this table will only contain entries that have a
corresponding entry in the nlMatrixSDTable with the same
source address and destination
address."
::= { nlMatrix 3 }

nlMatrixDSEntry OBJECT-TYPE
SYNTAX NlMatrixDSEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"A conceptual row in the nlMatrixDSTable.

The hlMatrixControlIndex value in the index identifies the
hlMatrixControlEntry on whose behalf this entry was created.
The protocolDirLocalIndex value in the index identifies the
network-layer protocol of the nlMatrixDSSourceAddress and
nlMatrixDSDestAddress.

An example of the indexing of this table is
nlMatrixDSPkts.1.783495.18.4.128.2.6.7.4.128.2.6.6.

Note that some combinations of index values may result in an
index that exceeds 128 sub-identifiers in length, which exceeds
the maximum for the SNMP protocol. Implementations should take
care to avoid such combinations."
INDEX { hlMatrixControlIndex, nlMatrixDSTimeMark,
protocolDirLocalIndex,

nlMatrixDSDestAddress,
nlMatrixDSSourceAddress }
::= { nlMatrixDSTable 1 }

```
NlMatrixDSEntry ::= SEQUENCE {
  nlMatrixDSTimeMark              TimeFilter,
  nlMatrixDSSourceAddress          OCTET STRING,
  nlMatrixDSDestAddress            OCTET STRING,
  nlMatrixDSPkts                 ZeroBasedCounter32,
  nlMatrixDSOctets                ZeroBasedCounter32,
  nlMatrixDSCreateTime            LastCreateTime
}

nlMatrixDSTimeMark OBJECT-TYPE
  SYNTAX      TimeFilter
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A TimeFilter for this entry.  See the TimeFilter textual
     convention to see how this works."
  ::= { nlMatrixDSEntry 1 }

nlMatrixDSSourceAddress OBJECT-TYPE
  SYNTAX      OCTET STRING  (SIZE (1..255))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The network source address for this nlMatrixDSEntry.

     This is represented as an octet string with
     specific semantics and
 length as identified
     by the protocolDirLocalIndex component of the index.

     For example, if the protocolDirLocalIndex indicates an
     encapsulation of IP, this object is encoded as a length
     octet of 4, followed by the 4 octets of the IP address,
     in network byte order."
  ::= { nlMatrixDSEntry 2 }

nlMatrixDSDestAddress OBJECT-TYPE
  SYNTAX      OCTET STRING  (SIZE (1..255))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The network destination address for this
     nlMatrixDSEntry.

     This is represented as an octet string with
     specific semantics and length as identified
```

```
      by the protocolDirLocalIndex component of the index.

      For example, if the protocolDirLocalIndex indicates an
      encapsulation of IP, this object is encoded as a length
      octet of 4, followed by the 4 octets of the IP address,
      in network byte order."
  ::= { nlMatrixDSEntry 3 }

nlMatrixDSPkts
 OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of packets without errors transmitted from the
     source address to the destination address since this entry was
     added to the nlMatrixDSTable.  Note that this is the number of
     link-layer packets, so if a single network-layer packet is
     fragmented into several link-layer frames, this counter is
     incremented several times."
  ::= { nlMatrixDSEntry 4 }

nlMatrixDSOctets OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of octets transmitted from the source address
     to the destination address since this entry was added to the
     nlMatrixDSTable (excluding framing bits, but
     including FCS octets), excluding octets in packets that
     contained errors.

     Note that this doesn't count just those octets in the particular
      protocol frames but includes the entire packet that contained
     the protocol."
  ::= { nlMatrixDSEntry 5 }

nlMatrixDSCreateTime OBJECT-TYPE
  SYNTAX     LastCreateTime
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The value of sysUpTime when this entry was last activated.
     This can be used by the management station to ensure that the
     entry has not been deleted and recreated between polls."
```

```
  ::= { nlMatrixDSEntry 6 }

nlMatrixTopNControlTable OBJECT-TYPE



  SYNTAX      SEQUENCE OF NlMatrixTopNControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A set of parameters that control the creation of a
     report of the top N matrix entries according to
     a selected metric."
  ::= { nlMatrix 4 }

nlMatrixTopNControlEntry OBJECT-TYPE
  SYNTAX      NlMatrixTopNControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A conceptual row
 in the nlMatrixTopNControlTable.

     An example of the indexing of this table is
     nlMatrixTopNControlDuration.3"
  INDEX { nlMatrixTopNControlIndex }
  ::= { nlMatrixTopNControlTable 1 }

NlMatrixTopNControlEntry ::= SEQUENCE {
  nlMatrixTopNControlIndex           Integer32,
  nlMatrixTopNControlMatrixIndex     Integer32,
  nlMatrixTopNControlRateBase        INTEGER,
  nlMatrixTopNControlTimeRemaining   Integer32,
  nlMatrixTopNControlGeneratedReports Counter32,
  nlMatrixTopNControlDuration        Integer32,
  nlMatrixTopNControlRequestedSize   Integer32,
  nlMatrixTopNControlGrantedSize     Integer32,
  nlMatrixTopNControlStartTime       TimeStamp,
  nlMatrixTopNControlOwner           OwnerString,
  nlMatrixTopNControlStatus          RowStatus
}

nlMatrixTopNControlIndex OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "An index that uniquely identifies an entry
```

```
      in the nlMatrixTopNControlTable.  Each such
      entry defines one topN report prepared for
      one interface."
   ::= { nlMatrixTopNControlEntry 1 }

nlMatrixTopNControlMatrixIndex OBJECT-TYPE
   SYNTAX     Integer32 (1..65535)



   MAX-ACCESS read-create
   STATUS     current
   DESCRIPTION
      "The nlMatrix[SD/DS] table for which a topN report will be
      prepared on behalf of this entry.  The nlMatrix[SD/DS] table
      is identified by the value of the hlMatrixControlIndex
      for that table - that value is used here to identify the
      particular table.

      This object may not be modified if the associated
      nlMatrixTopNControlStatus object is equal to active(1)."
   ::= { nlMatrixTopNControlEntry 2 }

nlMatrixTopNControlRateBase OBJECT-TYPE
   SYNTAX     INTEGER {
                 nlMatrixTopNPkts(1),
                 nlMatrixTopNOctets(2),
                 nlMatrixTopNHighCapacityPkts(3),
                 nlMatrixTopNHighCapacityOctets(4)
              }
   MAX-ACCESS read-create
   STATUS     current
   DESCRIPTION
      "The variable for each nlMatrix[SD/DS] entry that the
      nlMatrixTopNEntries are sorted by, as well as a control
      for the table that the results will be reported in.

      This object may not be modified if the associated
      nlMatrixTopNControlStatus object is equal to active(1).

      If this value is less than or equal to 2, when the report
      is prepared, entries are created in the nlMatrixTopNTable
      associated with this object.
      If this value is greater than or equal to 3, when the report
      is prepared, entries are created in the
      nlMatrixTopNHighCapacityTable associated with this object."
   ::= { nlMatrixTopNControlEntry 3 }
```

```
nlMatrixTopNControlTimeRemaining OBJECT-TYPE
  SYNTAX     Integer32 (0..2147483647)
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "The number of seconds left
 in the report currently
     being collected.  When this object is modified by
     the management station, a new collection is started,
     possibly aborting a currently running report.  The
     new value is used as the requested duration of this



     report and is immediately loaded into the associated
     nlMatrixTopNControlDuration object.

     When the report finishes, the probe will automatically
     start another collection with the same initial value
     of nlMatrixTopNControlTimeRemaining.  Thus, the management
     station may simply read the resulting reports repeatedly,
     checking the startTime and duration each time to ensure that a
     report was not missed or that the report parameters were not
     changed.

     While the value of this object is non-zero, it decrements
     by one per second until it reaches zero.  At the time
     that this object decrements to zero, the report is made
     accessible
 in the nlMatrixTopNTable, overwriting any report
     that may be there.

     When this object is modified by the management station, any
     associated entries in the nlMatrixTopNTable shall be deleted.

     (Note that this is a different algorithm than the one used
     in the hostTopNTable)."
  DEFVAL { 1800 }
  ::= { nlMatrixTopNControlEntry 4 }

nlMatrixTopNControlGeneratedReports OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of reports that have been generated by this entry."
  ::= { nlMatrixTopNControlEntry 5 }
```

```
nlMatrixTopNControlDuration OBJECT-TYPE
  SYNTAX     Integer32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of seconds that this report has collected
     during the last sampling interval.

     When the associated nlMatrixTopNControlTimeRemaining object is
     set, this object shall be set by the probe to the
     same
 value and shall not be modified until the next
     time the nlMatrixTopNControlTimeRemaining is set.

     This value shall be zero if no reports have been
     requested for this nlMatrixTopNControlEntry."



  ::= { nlMatrixTopNControlEntry 6 }

nlMatrixTopNControlRequestedSize OBJECT-TYPE
  SYNTAX     Integer32 (0..2147483647)
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "The maximum number of matrix entries requested for this report.

     When this object is created or modified, the probe
     should set nlMatrixTopNControlGrantedSize as closely to this
     object as possible for the particular probe
     implementation and available resources."
  DEFVAL { 150 }
  ::= { nlMatrixTopNControlEntry 7 }

nlMatrixTopNControlGrantedSize OBJECT-TYPE
  SYNTAX     Integer32 (0..2147483647)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The maximum number of matrix entries in this report.

     When
 the associated nlMatrixTopNControlRequestedSize object is
     created or modified, the probe should set this
     object as closely to the requested value as
     possible for the particular implementation and
     available resources.  The probe must not lower this
```

value except as a side-effect of a set to the associated
nlMatrixTopNControlRequestedSize object.

If the value of nlMatrixTopNControlRateBase is equal to
nlMatrixTopNPkts, when the next topN report is generated,
matrix entries with the highest value of nlMatrixTopNPktRate
shall be placed in this table in decreasing order of this rate
until there is no more room or until there are no more
matrix entries.

If the value of nlMatrixTopNControlRateBase is equal to
nlMatrixTopNOctets, when the next topN report is generated,
matrix entries with the highest value of nlMatrixTopNOctetRate
shall be placed in this table in decreasing
order of this rate
until there is no more room or until there are no more
matrix entries.

It is an implementation-specific matter how entries with the
same value of nlMatrixTopNPktRate or nlMatrixTopNOctetRate are
sorted. It is also an implementation-specific matter as to

whether zero-valued entries are available."
::= { nlMatrixTopNControlEntry 8 }

nlMatrixTopNControlStartTime OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime when this topN report was
last started. In other words, this is the time that
the associated nlMatrixTopNControlTimeRemaining object was
modified to start the requested report or the time
the report was last automatically (re)started.

This object may be used by the management station to
determine whether a report was missed."
::= { nlMatrixTopNControlEntry 9 }

nlMatrixTopNControlOwner
OBJECT-TYPE
SYNTAX OwnerString
MAX-ACCESS read-create
STATUS current
DESCRIPTION

```
      "The entity that configured this entry and is
      therefore using the resources assigned to it."
    ::= { nlMatrixTopNControlEntry 10 }

nlMatrixTopNControlStatus OBJECT-TYPE
    SYNTAX     RowStatus
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
      "The status of this nlMatrixTopNControlEntry.

      An entry may not exist in the active state unless all
      objects in the entry have an appropriate value.

      If this object is not equal to active(1), all
      associated entries in the nlMatrixTopNTable shall be deleted
      by the agent."
    ::= { nlMatrixTopNControlEntry 11 }

nlMatrixTopNTable OBJECT-TYPE
    SYNTAX     SEQUENCE OF NlMatrixTopNEntry
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
      "A set of statistics for those network-layer matrix entries




      that have
   counted the highest number of octets or packets."
    ::= { nlMatrix 5 }

nlMatrixTopNEntry OBJECT-TYPE
    SYNTAX     NlMatrixTopNEntry
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
      "A conceptual row in the nlMatrixTopNTable.

      The nlMatrixTopNControlIndex value in the index identifies the
      nlMatrixTopNControlEntry on whose behalf this entry was
      created.

      An example of the indexing of this table is
      nlMatrixTopNPktRate.3.10"
    INDEX { nlMatrixTopNControlIndex, nlMatrixTopNIndex }
    ::= { nlMatrixTopNTable 1 }
```

```
NlMatrixTopNEntry ::= SEQUENCE {
  nlMatrixTopNIndex               Integer32,
  nlMatrixTopNProtocolDirLocalIndex Integer32,
  nlMatrixTopNSourceAddress        OCTET STRING,
  nlMatrixTopNDestAddress          OCTET STRING,
  nlMatrixTopNPktRate              Gauge32,
  nlMatrixTopNReversePktRate       Gauge32,
  nlMatrixTopNOctetRate            Gauge32,
  nlMatrixTopNReverseOctetRate
    Gauge32
}

nlMatrixTopNIndex OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "An index that uniquely identifies an entry in
     the nlMatrixTopNTable among those in the same report.
     This index is between 1 and N, where N is the
     number of entries in this report.

     If the value of nlMatrixTopNControlRateBase is equal to
     nlMatrixTopNPkts, increasing values of nlMatrixTopNIndex shall
     be assigned to entries with decreasing values of
     nlMatrixTopNPktRate until index N is assigned or there are no
     more nlMatrixTopNEntries.

     If the value of nlMatrixTopNControlRateBase is equal to
     nlMatrixTopNOctets, increasing values of nlMatrixTopNIndex




     shall be assigned to entries with decreasing values of
     nlMatrixTopNOctetRate until index N is assigned or there are
     no more nlMatrixTopNEntries."
  ::= { nlMatrixTopNEntry 1 }

nlMatrixTopNProtocolDirLocalIndex
 OBJECT-TYPE
  SYNTAX     Integer32 (1..2147483647)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The protocolDirLocalIndex of the network-layer protocol of
     this entry's network address."
  ::= { nlMatrixTopNEntry 2 }
```

```
nlMatrixTopNSourceAddress OBJECT-TYPE
  SYNTAX     OCTET STRING  (SIZE (1..255))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The network-layer address of the source host in this
     conversation.

     This is represented as an octet string with
     specific semantics and length as identified
     by the associated nlMatrixTopNProtocolDirLocalIndex.

     For example, if the protocolDirLocalIndex indicates an
     encapsulation of IP, this object is encoded as a length
     octet of 4, followed by the 4 octets of the IP address,
     in network byte order."
  ::= { nlMatrixTopNEntry 3 }

nlMatrixTopNDestAddress OBJECT-TYPE
  SYNTAX     OCTET
 STRING  (SIZE (1..255))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The network-layer address of the destination host in this
     conversation.

     This is represented as an octet string with
     specific semantics and length as identified
     by the associated nlMatrixTopNProtocolDirLocalIndex.

     For example, if the nlMatrixTopNProtocolDirLocalIndex
     indicates an encapsulation of IP, this object is encoded as a
     length octet of 4, followed by the 4 octets of the IP address,
     in network byte order."



  ::= { nlMatrixTopNEntry 4 }

nlMatrixTopNPktRate OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of packets seen from the source host
     to the destination host during this sampling interval, counted
     using the rules for counting the nlMatrixSDPkts object.
```

```
      If the value of nlMatrixTopNControlRateBase is
      nlMatrixTopNPkts,
 this variable will be used to sort this
      report."
  ::= { nlMatrixTopNEntry 5 }

nlMatrixTopNReversePktRate OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
      "The number of packets seen from the destination host to the
      source host during this sampling interval, counted
      using the rules for counting the nlMatrixSDPkts object.  (Note
      that the corresponding nlMatrixSDPkts object selected is the
      one whose source address is equal to nlMatrixTopNDestAddress
      and whose destination address is equal to
      nlMatrixTopNSourceAddress.)

      Note that if the value of nlMatrixTopNControlRateBase is equal
      to nlMatrixTopNPkts, the sort of topN entries is based
      entirely on nlMatrixTopNPktRate, and not on the value of this
      object."
  ::= { nlMatrixTopNEntry 6 }

nlMatrixTopNOctetRate OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
   DESCRIPTION
      "The number of octets seen from the source host
      to the destination host during this sampling interval, counted
      using the rules for counting the nlMatrixSDOctets object.  If
      the value of nlMatrixTopNControlRateBase is
      nlMatrixTopNOctets, this variable will be used to sort this
      report."
  ::= { nlMatrixTopNEntry 7 }

nlMatrixTopNReverseOctetRate OBJECT-TYPE



  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
      "The number of octets seen from the destination host to the
      source host during this sampling interval, counted
```

using the rules for counting the nlMatrixDSOctets object. (Note
that the corresponding nlMatrixSDOctets object selected is the
one whose source address is equal to nlMatrixTopNDestAddress
and whose destination address is equal to
nlMatrixTopNSourceAddress.)

Note that if the value of nlMatrixTopNControlRateBase
is equal
to nlMatrixTopNOctets, the sort of topN entries is based
entirely on nlMatrixTopNOctetRate, and not on the value of
this object."
::= { nlMatrixTopNEntry 8 }

-- Application Layer Functions
--
-- The application layer host, matrix, and matrixTopN functions report
-- on protocol usage at the network layer or higher. Note that the
-- use of the term application layer does not imply that only
-- application-layer protocols are counted, rather it means that
-- protocols up to and including the application layer are supported.

--
-- Application Layer Host Group
--
-- Counts the amount of traffic, by protocol, sent from and to each
-- network address discovered by the probe.
-- Implementation of this group requires implementation of the Network
-- Layer Host Group.

alHostTable OBJECT-TYPE
SYNTAX SEQUENCE OF AlHostEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"A collection of statistics for a particular
protocol from a
particular network address that has been discovered on an
interface of this device.

The probe will populate this table for all protocols in the
protocol directory table whose value of
protocolDirHostConfig is equal to supportedOn(3), and
will delete any entries whose protocolDirEntry is deleted or
has a protocolDirHostConfig value of supportedOff(2).

The probe will add to this table all addresses

```
      seen as the source or destination address in all packets with
      no MAC errors and will increment octet and packet counts in
      the table for all packets with no MAC errors.  Further,
      entries will only be added to this table if their address
      exists in the nlHostTable and will be deleted from this table
      if their address is deleted from the nlHostTable."
  ::= { alHost 1 }

alHostEntry OBJECT-TYPE
  SYNTAX      AlHostEntry
  MAX-ACCESS  not-accessible
  STATUS
    current
  DESCRIPTION
      "A conceptual row in the alHostTable.

      The hlHostControlIndex value in the index identifies the
      hlHostControlEntry on whose behalf this entry was created.
      The first protocolDirLocalIndex value in the index identifies
      the network-layer protocol of the address.
      The nlHostAddress value in the index identifies the network-
      layer address of this entry.
      The second protocolDirLocalIndex value in the index identifies
      the protocol that is counted by this entry.

      An example of the indexing in this entry is
      alHostOutPkts.1.783495.18.4.128.2.6.6.34.

      Note that some combinations of index values may result in an
      index that exceeds 128 sub-identifiers in length, which exceeds
      the maximum for the SNMP protocol.  Implementations should take
      care to avoid such combinations."
  INDEX { hlHostControlIndex, alHostTimeMark,
          protocolDirLocalIndex,
 nlHostAddress,
          protocolDirLocalIndex }
  ::= { alHostTable 1 }

AlHostEntry ::= SEQUENCE {
  alHostTimeMark              TimeFilter,
  alHostInPkts               ZeroBasedCounter32,
  alHostOutPkts               ZeroBasedCounter32,
  alHostInOctets              ZeroBasedCounter32,
  alHostOutOctets             ZeroBasedCounter32,
  alHostCreateTime            LastCreateTime
}

alHostTimeMark OBJECT-TYPE
```

```
  SYNTAX      TimeFilter



  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A TimeFilter for this entry.  See the TimeFilter textual
      convention to see how this works."
  ::= { alHostEntry 1 }

alHostInPkts OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The number of packets of this protocol type without errors
      transmitted to this address since it was added to the
      alHostTable.  Note that this is the number
 of link-layer
      packets, so if a single network-layer packet is fragmented
      into several link-layer frames, this counter is incremented
      several times."
  ::= { alHostEntry 2 }

alHostOutPkts OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The number of packets of this protocol type without errors
      transmitted by this address since it was added to the
      alHostTable.  Note that this is the number of link-layer
      packets, so if a single network-layer packet is fragmented
      into several link-layer frames, this counter is incremented
      several times."
   ::= { alHostEntry 3 }

alHostInOctets OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The number of octets transmitted to this address
      of this protocol type since it was added to the
      alHostTable (excluding framing bits, but
 including
      FCS octets), excluding octets in packets that
```

```
      contained errors.

      Note that this doesn't count just those octets in the particular
      protocol frames but includes the entire packet that contained
      the protocol."
   ::= { alHostEntry 4 }



alHostOutOctets OBJECT-TYPE
   SYNTAX      ZeroBasedCounter32
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The number of octets transmitted by this address
      of this protocol type since it was added to the
      alHostTable (excluding framing bits, but including
      FCS octets), excluding octets in packets that
      contained errors.

      Note that this doesn't count just those octets in the particular
      protocol frames but includes the entire packet that contained
      the protocol."
   ::= { alHostEntry 5 }

alHostCreateTime OBJECT-TYPE
   SYNTAX     LastCreateTime
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The value
 of sysUpTime when this entry was last activated.
      This can be used by the management station to ensure that the
      entry has not been deleted and recreated between polls."
   ::= { alHostEntry 6 }

--
-- Application Layer Matrix Group
--
-- Counts the amount of traffic, by protocol, sent between each pair
-- of network addresses discovered by the probe.
-- Implementation of this group requires implementation of the Network
-- Layer Matrix Group.

alMatrixSDTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF AlMatrixSDEntry
   MAX-ACCESS  not-accessible
   STATUS      current
```

```
  DESCRIPTION
      "A list of application traffic matrix entries that collect
      statistics for conversations of a particular protocol between
      two network-level addresses.  This table is indexed first by
      the source address and then by the destination address to make
      it convenient to collect all statistics from a particular
      address.

      The probe will populate
 this table for all protocols in the
      protocol directory table whose value of



      protocolDirMatrixConfig is equal to supportedOn(3), and
      will delete any entries whose protocolDirEntry is deleted or
      has a protocolDirMatrixConfig value of supportedOff(2).

      The probe will add to this table all pairs of addresses for
      all protocols seen in all packets with no MAC errors and will
      increment octet and packet counts in the table for all packets
      with no MAC errors.  Further, entries will only be added to
      this table if their address pair exists in the nlMatrixSDTable
      and will be deleted from this table if the address pair is
      deleted from the nlMatrixSDTable."
  ::= { alMatrix 1 }

alMatrixSDEntry OBJECT-TYPE
  SYNTAX      AlMatrixSDEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A conceptual row in the alMatrixSDTable.

      The hlMatrixControlIndex value in the index
 identifies the
      hlMatrixControlEntry on whose behalf this entry was created.
      The first protocolDirLocalIndex value in the index identifies
      the network-layer protocol of the nlMatrixSDSourceAddress and
      nlMatrixSDDestAddress.
      The nlMatrixSDSourceAddress value in the index identifies the
      network-layer address of the source host in this conversation.
      The nlMatrixSDDestAddress value in the index identifies the
      network-layer address of the destination host in this
      conversation.
      The second protocolDirLocalIndex value in the index identifies
      the protocol that is counted by this entry.
```

```
      An example of the indexing of this entry is
      alMatrixSDPkts.1.783495.18.4.128.2.6.6.4.128.2.6.7.34.

      Note that some combinations of index values may result in an
      index that exceeds 128 sub-identifiers in length, which exceeds
      the maximum for the SNMP protocol.  Implementations should
 take
      care to avoid such combinations."
  INDEX { hlMatrixControlIndex, alMatrixSDTimeMark,
          protocolDirLocalIndex,
          nlMatrixSDSourceAddress, nlMatrixSDDestAddress,
          protocolDirLocalIndex }
  ::= { alMatrixSDTable 1 }

AlMatrixSDEntry ::= SEQUENCE {
  alMatrixSDTimeMark              TimeFilter,



  alMatrixSDPkts                  ZeroBasedCounter32,
  alMatrixSDOctets                ZeroBasedCounter32,
  alMatrixSDCreateTime            LastCreateTime
}

alMatrixSDTimeMark OBJECT-TYPE
  SYNTAX      TimeFilter
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A TimeFilter for this entry.  See the TimeFilter textual
      convention to see how this works."
  ::= { alMatrixSDEntry 1 }

alMatrixSDPkts OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The number of packets of this protocol type without errors
      transmitted
 from the source address to the destination address
      since this entry was added to the alMatrixSDTable.  Note that
      this is the number of link-layer packets, so if a single
      network-layer packet is fragmented into several link-layer
      frames, this counter is incremented several times."
  ::= { alMatrixSDEntry 2 }

alMatrixSDOctets OBJECT-TYPE
```

```
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of octets in packets of this protocol type
     transmitted from the source address to the destination address
     since this entry was added to the alMatrixSDTable (excluding
     framing bits, but including FCS octets), excluding octets
     in packets that contained errors.

     Note that this doesn't count just those octets in the particular
     protocol frames but includes the entire packet that contained
     the protocol."
  ::= { alMatrixSDEntry 3 }

alMatrixSDCreateTime
 OBJECT-TYPE
  SYNTAX     LastCreateTime
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION



     "The value of sysUpTime when this entry was last activated.
     This can be used by the management station to ensure that the
     entry has not been deleted and recreated between polls."
  ::= { alMatrixSDEntry 4 }

-- Traffic matrix tables from destination to source

alMatrixDSTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF AlMatrixDSEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A list of application traffic matrix entries that collect
     statistics for conversations of a particular protocol between
     two network-level addresses.  This table is indexed first by
     the destination address and then by the source address to make
     it convenient to collect all statistics to a particular
     address.

     The probe will populate this table for all protocols in the
     protocol directory
 table whose value of
     protocolDirMatrixConfig is equal to supportedOn(3), and
     will delete any entries whose protocolDirEntry is deleted or
```

```
      has a protocolDirMatrixConfig value of supportedOff(2).

      The probe will add to this table all pairs of addresses for
      all protocols seen in all packets with no MAC errors and will
      increment octet and packet counts in the table for all packets
      with no MAC errors.  Further, entries will only be added to
      this table if their address pair exists in the nlMatrixDSTable
      and will be deleted from this table if the address pair is
      deleted from the nlMatrixDSTable."
  ::= { alMatrix 2 }

alMatrixDSEntry OBJECT-TYPE
  SYNTAX      AlMatrixDSEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A conceptual row in the alMatrixDSTable.

      The hlMatrixControlIndex value in the index identifies the
      hlMatrixControlEntry on whose behalf
 this entry was created.
      The first protocolDirLocalIndex value in the index identifies
      the network-layer protocol of the alMatrixDSSourceAddress and
      alMatrixDSDestAddress.
      The nlMatrixDSDestAddress value in the index identifies the
      network-layer address of the destination host in this




      conversation.
      The nlMatrixDSSourceAddress value in the index identifies the
      network-layer address of the source host in this conversation.
      The second protocolDirLocalIndex value in the index identifies
      the protocol that is counted by this entry.

      An example of the indexing of this entry is
      alMatrixDSPkts.1.783495.18.4.128.2.6.7.4.128.2.6.6.34.

      Note that some combinations of index values may result in an
      index that exceeds 128 sub-identifiers in length, which exceeds
      the maximum for the SNMP protocol.  Implementations should take
      care to avoid such combinations."
  INDEX { hlMatrixControlIndex,
 alMatrixDSTimeMark,
          protocolDirLocalIndex,
          nlMatrixDSDestAddress, nlMatrixDSSourceAddress,
          protocolDirLocalIndex }
  ::= { alMatrixDSTable 1 }
```

```
AlMatrixDSEntry ::= SEQUENCE {
  alMatrixDSTimeMark              TimeFilter,
  alMatrixDSPkts                ZeroBasedCounter32,
  alMatrixDSOctets               ZeroBasedCounter32,
  alMatrixDSCreateTime            LastCreateTime
}

alMatrixDSTimeMark OBJECT-TYPE
  SYNTAX      TimeFilter
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A TimeFilter for this entry.  See the TimeFilter textual
     convention to see how this works."
  ::= { alMatrixDSEntry 1 }

alMatrixDSPkts OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of packets of this protocol type without errors
     transmitted from the source address to the destination address

    since this entry was added to the alMatrixDSTable.  Note that
     this is the number of link-layer packets, so if a single
     network-layer packet is fragmented into several link-layer
     frames, this counter is incremented several times."
  ::= { alMatrixDSEntry 2 }




alMatrixDSOctets OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of octets in packets of this protocol type
     transmitted from the source address to the destination address
     since this entry was added to the alMatrixDSTable (excluding
     framing bits, but including FCS octets), excluding octets
     in packets that contained errors.

     Note that this doesn't count just those octets in the particular
     protocol frames but includes the entire packet that contained
     the protocol."
```

```
  ::= { alMatrixDSEntry 3 }

alMatrixDSCreateTime OBJECT-TYPE
  SYNTAX     LastCreateTime
  MAX-ACCESS
 read-only
  STATUS     current
  DESCRIPTION
     "The value of sysUpTime when this entry was last activated.
     This can be used by the management station to ensure that the
     entry has not been deleted and recreated between polls."
  ::= { alMatrixDSEntry 4 }

alMatrixTopNControlTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF AlMatrixTopNControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A set of parameters that control the creation of a
     report of the top N matrix entries according to
     a selected metric."
  ::= { alMatrix 3 }

alMatrixTopNControlEntry OBJECT-TYPE
  SYNTAX      AlMatrixTopNControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A conceptual row in the alMatrixTopNControlTable.

     An example of the indexing of this table is
     alMatrixTopNControlDuration.3"
  INDEX { alMatrixTopNControlIndex }
  ::= { alMatrixTopNControlTable 1 }




AlMatrixTopNControlEntry
 ::= SEQUENCE {
  alMatrixTopNControlIndex           Integer32,
  alMatrixTopNControlMatrixIndex     Integer32,
  alMatrixTopNControlRateBase        INTEGER,
  alMatrixTopNControlTimeRemaining   Integer32,
  alMatrixTopNControlGeneratedReports Counter32,
  alMatrixTopNControlDuration        Integer32,
  alMatrixTopNControlRequestedSize   Integer32,
  alMatrixTopNControlGrantedSize     Integer32,
```

```
  alMatrixTopNControlStartTime       TimeStamp,
  alMatrixTopNControlOwner           OwnerString,
  alMatrixTopNControlStatus          RowStatus
}

alMatrixTopNControlIndex OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "An index that uniquely identifies an entry
     in the alMatrixTopNControlTable.  Each such
     entry defines one topN report prepared for
     one interface."
  ::= { alMatrixTopNControlEntry 1 }

alMatrixTopNControlMatrixIndex OBJECT-TYPE
   SYNTAX     Integer32 (1..65535)
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "The alMatrix[SD/DS] table for which a topN report will be
     prepared on behalf of this entry.  The alMatrix[SD/DS] table
     is identified by the value of the hlMatrixControlIndex
     for that table - that value is used here to identify the
     particular table.

     This object may not be modified if the associated
     alMatrixTopNControlStatus object is equal to active(1)."
  ::= { alMatrixTopNControlEntry 2 }

alMatrixTopNControlRateBase OBJECT-TYPE
  SYNTAX     INTEGER {
               alMatrixTopNTerminalsPkts(1),
               alMatrixTopNTerminalsOctets(2),
               alMatrixTopNAllPkts(3),
               alMatrixTopNAllOctets(4),
               alMatrixTopNTerminalsHighCapacityPkts(5),
               alMatrixTopNTerminalsHighCapacityOctets(6),



               alMatrixTopNAllHighCapacityPkts(7),

             alMatrixTopNAllHighCapacityOctets(8)
              }
  MAX-ACCESS read-create
  STATUS     current
```

```
  DESCRIPTION
      "This object controls which alMatrix[SD/DS] entry that the
      alMatrixTopNEntries are sorted by, which view of the matrix
      table that will be used, as well as which table the results
      will be reported in.

      The values alMatrixTopNTerminalsPkts,
      alMatrixTopNTerminalsOctets,
      alMatrixTopNTerminalsHighCapacityPkts, and
      alMatrixTopNTerminalsHighCapacityOctets cause collection
      only from protocols that have no child protocols that are
      counted.  The values alMatrixTopNAllPkts,
      alMatrixTopNAllOctets, alMatrixTopNAllHighCapacityPkts, and
      alMatrixTopNAllHighCapacityOctets cause collection from all
      alMatrix entries.

      This object may not be modified if the associated
      alMatrixTopNControlStatus object is equal to active(1)."
  ::= { alMatrixTopNControlEntry
 3 }

alMatrixTopNControlTimeRemaining OBJECT-TYPE
  SYNTAX     Integer32 (0..2147483647)
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
      "The number of seconds left in the report currently
      being collected.  When this object is modified by
      the management station, a new collection is started,
      possibly aborting a currently running report.  The
      new value is used as the requested duration of this
      report and is immediately loaded into the associated
      alMatrixTopNControlDuration object.

      When the report finishes, the probe will automatically
      start another collection with the same initial value
      of alMatrixTopNControlTimeRemaining.  Thus, the management
      station may simply read the resulting reports repeatedly,
      checking the startTime and duration each time to ensure that a
      report was not missed or that the report parameters were not
      changed.

      While the value
 of this object is non-zero, it decrements
      by one per second until it reaches zero.  At the time
```

```
      that this object decrements to zero, the report is made
      accessible in the alMatrixTopNTable, overwriting any report
      that may be there.

      When this object is modified by the management station, any
      associated entries in the alMatrixTopNTable shall be deleted.

      (Note that this is a different algorithm than the one used
      in the hostTopNTable)."
    DEFVAL { 1800 }
    ::= { alMatrixTopNControlEntry 4 }

alMatrixTopNControlGeneratedReports OBJECT-TYPE
    SYNTAX     Counter32
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
      "The number of reports that have been generated by this entry."
    ::= { alMatrixTopNControlEntry 5 }

alMatrixTopNControlDuration OBJECT-TYPE
    SYNTAX     Integer32
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
      "The number of seconds that this report has collected
       during the last sampling interval.

      When the associated alMatrixTopNControlTimeRemaining object
      is set, this object shall be set by the probe to the
      same value and shall not be modified until the next
      time the alMatrixTopNControlTimeRemaining is set.

      This value shall be zero if no reports have been
      requested for this alMatrixTopNControlEntry."
    ::= { alMatrixTopNControlEntry 6 }

alMatrixTopNControlRequestedSize OBJECT-TYPE
    SYNTAX     Integer32 (0..2147483647)
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
      "The maximum number of matrix entries requested for this report.

      When this object is created or modified, the probe
      should set alMatrixTopNControlGrantedSize as closely to this
      object as possible for the particular probe
      implementation and available resources."
```

```
  DEFVAL { 150 }
  ::= { alMatrixTopNControlEntry 7 }

alMatrixTopNControlGrantedSize OBJECT-TYPE
   SYNTAX     Integer32 (0..2147483647)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The maximum number of matrix entries in this report.

     When the associated alMatrixTopNControlRequestedSize object
     is created or modified, the probe should set this
     object as closely to the requested value as
     possible for the particular implementation and
     available resources. The probe must not lower this
     value except as a side-effect of a set to the associated
     alMatrixTopNControlRequestedSize object.

     If the value of alMatrixTopNControlRateBase is equal to
     alMatrixTopNTerminalsPkts or alMatrixTopNAllPkts, when the
     next topN report is generated, matrix entries with the highest
     value of alMatrixTopNPktRate shall be placed in this table in
     decreasing order of this rate until there is no more room or
     until there are no more matrix entries.

     If the value of alMatrixTopNControlRateBase
 is equal to
     alMatrixTopNTerminalsOctets or alMatrixTopNAllOctets, when the
     next topN report is generated, matrix entries with the highest
     value of alMatrixTopNOctetRate shall be placed in this table
     in decreasing order of this rate until there is no more room
     or until there are no more matrix entries.

     It is an implementation-specific matter how entries with the
     same value of alMatrixTopNPktRate or alMatrixTopNOctetRate are
     sorted.  It is also an implementation-specific matter as to
     whether zero-valued entries are available."
  ::= { alMatrixTopNControlEntry 8 }

alMatrixTopNControlStartTime OBJECT-TYPE
  SYNTAX     TimeStamp
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The value of sysUpTime when this topN report was
```

last started. In other words, this is the time that
the associated alMatrixTopNControlTimeRemaining object
was modified
to start the requested report or the time
the report was last automatically (re)started.

This object may be used by the management station to
determine whether a report was missed."
::= { alMatrixTopNControlEntry 9 }

alMatrixTopNControlOwner OBJECT-TYPE
SYNTAX OwnerString
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The entity that configured this entry and is
therefore using the resources assigned to it."
::= { alMatrixTopNControlEntry 10 }

alMatrixTopNControlStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The status of this alMatrixTopNControlEntry.

An entry may not exist in the active state unless all
objects in the entry have an appropriate value.

If this object is not equal to active(1), all
associated entries in the alMatrixTopNTable shall be
deleted by the agent."
::= { alMatrixTopNControlEntry
11 }

alMatrixTopNTable OBJECT-TYPE
SYNTAX SEQUENCE OF AlMatrixTopNEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"A set of statistics for those application-layer matrix
entries that have counted the highest number of octets or
packets."
::= { alMatrix 4 }

alMatrixTopNEntry OBJECT-TYPE

```
  SYNTAX     AlMatrixTopNEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "A conceptual row in the alMatrixTopNTable.

     The alMatrixTopNControlIndex value in the index identifies
     the alMatrixTopNControlEntry on whose behalf this entry was
     created.



     An example of the indexing of this table is
     alMatrixTopNPktRate.3.10"
  INDEX { alMatrixTopNControlIndex, alMatrixTopNIndex }
  ::= { alMatrixTopNTable 1 }

AlMatrixTopNEntry ::= SEQUENCE {
  alMatrixTopNIndex                  Integer32,
  alMatrixTopNProtocolDirLocalIndex      Integer32,

 alMatrixTopNSourceAddress             OCTET STRING,
  alMatrixTopNDestAddress               OCTET STRING,
  alMatrixTopNAppProtocolDirLocalIndex   Integer32,
  alMatrixTopNPktRate                 Gauge32,
  alMatrixTopNReversePktRate            Gauge32,
  alMatrixTopNOctetRate                Gauge32,
  alMatrixTopNReverseOctetRate          Gauge32
 }

alMatrixTopNIndex OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "An index that uniquely identifies an entry in
     the alMatrixTopNTable among those in the same report.

     This index is between 1 and N, where N is the
     number of entries in this report.

     If the value of alMatrixTopNControlRateBase is equal to
     alMatrixTopNTerminalsPkts or alMatrixTopNAllPkts, increasing
     values of alMatrixTopNIndex shall be assigned to entries with
     decreasing values of alMatrixTopNPktRate until index N is

    assigned or there are no more alMatrixTopNEntries.
```

```
      If the value of alMatrixTopNControlRateBase is equal to
      alMatrixTopNTerminalsOctets or alMatrixTopNAllOctets,
      increasing values of alMatrixTopNIndex shall be assigned to
      entries with decreasing values of alMatrixTopNOctetRate until
      index N is assigned or there are no more alMatrixTopNEntries."
    ::= { alMatrixTopNEntry 1 }

alMatrixTopNProtocolDirLocalIndex OBJECT-TYPE
    SYNTAX     Integer32 (1..2147483647)
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
      "The protocolDirLocalIndex of the network-layer protocol of
      this entry's network address."



    ::= { alMatrixTopNEntry 2 }

alMatrixTopNSourceAddress OBJECT-TYPE
    SYNTAX     OCTET STRING  (SIZE (1..255))
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
      "The network-layer address of the source host in this
      conversation.

      This is represented as an octet string with
       specific semantics and length as identified
      by the associated alMatrixTopNProtocolDirLocalIndex.

      For example, if the alMatrixTopNProtocolDirLocalIndex
      indicates an encapsulation of IP, this object is encoded as a
      length octet of 4, followed by the 4 octets of the IP address,
      in network byte order."
    ::= { alMatrixTopNEntry 3 }

alMatrixTopNDestAddress OBJECT-TYPE
    SYNTAX     OCTET STRING  (SIZE (1..255))
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
      "The network-layer address of the destination host in this
      conversation.

      This is represented as an octet string with
      specific semantics and length as identified
      by the associated alMatrixTopNProtocolDirLocalIndex.
```

```
      For example, if the alMatrixTopNProtocolDirLocalIndex
      indicates an encapsulation of IP, this object is encoded as a
      length octet of 4, followed by the 4 octets of the IP address,
      in network
 byte order."
  ::= { alMatrixTopNEntry 4 }

alMatrixTopNAppProtocolDirLocalIndex OBJECT-TYPE
  SYNTAX     Integer32 (1..2147483647)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The type of the protocol counted by this matrix entry."
  ::= { alMatrixTopNEntry 5 }

alMatrixTopNPktRate OBJECT-TYPE
  SYNTAX     Gauge32



  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of packets seen of this protocol from the source
     host to the destination host during this sampling interval,
     counted using the rules for counting the alMatrixSDPkts
     object.

     If the value of alMatrixTopNControlRateBase is
     alMatrixTopNTerminalsPkts or alMatrixTopNAllPkts, this
     variable will be used to sort this report."
  ::= { alMatrixTopNEntry 6 }

alMatrixTopNReversePktRate OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of packets
 seen of this protocol from the
     destination host to the source host during this sampling
     interval, counted using the rules for counting the
     alMatrixDSPkts object.  (Note that the corresponding
     alMatrixSDPkts object selected is the one whose source address
     is equal to alMatrixTopNDestAddress and whose destination
     address is equal to alMatrixTopNSourceAddress.)
```

```
      Note that if the value of alMatrixTopNControlRateBase is equal
      to alMatrixTopNTerminalsPkts or alMatrixTopNAllPkts, the sort
      of topN entries is based entirely on alMatrixTopNPktRate, and
      not on the value of this object."
  ::= { alMatrixTopNEntry 7 }

alMatrixTopNOctetRate OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
      "The number of octets seen of this protocol from the source
      host to the destination host during this sampling interval,
      counted using the rules for counting
 the alMatrixSDOctets
      object.

      If the value of alMatrixTopNControlRateBase is
      alMatrixTopNTerminalsOctets or alMatrixTopNAllOctets, this
      variable will be used to sort this report."
  ::= { alMatrixTopNEntry 8 }

alMatrixTopNReverseOctetRate OBJECT-TYPE



  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
      "The number of octets seen of this protocol from the
      destination host to the source host during this sampling
      interval, counted using the rules for counting the
      alMatrixDSOctets object.  (Note that the corresponding
      alMatrixSDOctets object selected is the one whose source
      address is equal to alMatrixTopNDestAddress and whose
      destination address is equal to alMatrixTopNSourceAddress.)

      Note that if the value of alMatrixTopNControlRateBase is equal
      to alMatrixTopNTerminalsOctets or alMatrixTopNAllOctets, the
      sort of topN entries is based
 entirely on
      alMatrixTopNOctetRate, and not on the value of this object."
  ::= { alMatrixTopNEntry 9 }

--
-- User History Collection Group (usrHistory)
--
```

-- The usrHistory group combines mechanisms seen in the alarm and
-- history groups to provide user-specified history collection,
-- utilizing two additional control tables and one additional data
-- table. This function has traditionally been done by NMS
-- applications, via periodic polling. The usrHistory group allows
-- this task to be offloaded to an RMON probe.
--
-- Data (an ASN.1 INTEGER based object) is collected in the same
-- manner as any history data table (e.g., etherHistoryTable) except
-- that the user specifies the MIB instances to be collected. Objects
-- are collected in bucket-groups, with the intent that all MIB
-- instances in the same bucket-group are collected as atomically as
-- possible by the RMON probe.
--
-- The usrHistoryControlTable is a one-dimensional read-create table.
-- Each row configures
 a collection of user history buckets, much
-- the same as a historyControlEntry, except that the creation of a
-- row in this table will cause one or more associated instances in
-- the usrHistoryObjectTable to be created. The user specifies the
-- number of bucket elements (rows in the usrHistoryObjectTable)
-- requested, as well as the number of buckets requested.
--
-- The usrHistoryObjectTable is a 2-d read-write table.
-- Each row configures a single MIB instance to be collected.
-- All rows with the same major index constitute a bucket-group.
--
-- The usrHistoryTable is a 3-d read-only table containing

-- the data of associated usrHistoryControlEntries. Each
-- entry represents the value of a single MIB instance
-- during a specific sampling interval (or the rate of
-- change during the interval).
--
-- A sample value is stored in two objects - an absolute value and
-- a status object. This allows numbers from -(2G-1) to +4G to be
-- stored. The status object also indicates
 whether a sample is
-- valid. This allows data collection to continue if periodic
-- retrieval of a particular instance fails for any reason.
--
-- Row Creation Order Relationships
--
-- The static nature of the usrHistoryObjectTable creates
-- some row creation/modification issues. The rows in this
-- table need to be set before the associated

```
-- usrHistoryControlEntry can be activated.
--
-- Note that the usrHistoryObject entries associated with a
-- particular usrHistoryControlEntry are not required to
-- be active before the control entry is activated.  However,
-- the usrHistory data entries associated with an inactive
-- usrHistoryObject entry will be inactive (i.e.,
-- usrHistoryValStatus == valueNotAvailable).
--

usrHistoryControlTable OBJECT-TYPE
  SYNTAX SEQUENCE OF UsrHistoryControlEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
     "A list of data-collection configuration entries."
  ::= { usrHistory 1 }

usrHistoryControlEntry OBJECT-TYPE
   SYNTAX UsrHistoryControlEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
     "A list of parameters that set up a group of user-defined
     MIB objects to be sampled periodically (called a
     bucket-group).

     For example, an instance of usrHistoryControlInterval
     might be named usrHistoryControlInterval.1"
  INDEX { usrHistoryControlIndex }
  ::= { usrHistoryControlTable 1 }




UsrHistoryControlEntry ::= SEQUENCE {
  usrHistoryControlIndex             Integer32,
  usrHistoryControlObjects           Integer32,
  usrHistoryControlBucketsRequested  Integer32,
  usrHistoryControlBucketsGranted    Integer32,
  usrHistoryControlInterval          Integer32,
  usrHistoryControlOwner             OwnerString,
  usrHistoryControlStatus            RowStatus
}

usrHistoryControlIndex OBJECT-TYPE
  SYNTAX Integer32 (1..65535)
  MAX-ACCESS not-accessible
```

```
  STATUS current
  DESCRIPTION
     "An index that uniquely
 identifies an entry in the
     usrHistoryControlTable.  Each such entry defines a
     set of samples at a particular interval for a specified
     set of MIB instances available from the managed system."
  ::= { usrHistoryControlEntry 1 }

usrHistoryControlObjects OBJECT-TYPE
  SYNTAX Integer32 (1..65535)
  MAX-ACCESS read-create
  STATUS current
  DESCRIPTION
     "The number of MIB objects to be collected
     in the portion of usrHistoryTable associated with this
     usrHistoryControlEntry.

     This object may not be modified if the associated instance
     of usrHistoryControlStatus is equal to active(1)."
  ::= { usrHistoryControlEntry 2 }

usrHistoryControlBucketsRequested OBJECT-TYPE
  SYNTAX Integer32 (1..65535)
  MAX-ACCESS read-create
  STATUS current
  DESCRIPTION
     "The requested number of discrete time intervals
     over which data is to be saved in the part of the
     usrHistoryTable associated with this usrHistoryControlEntry.

      When this object is created or modified, the probe
     should set usrHistoryControlBucketsGranted as closely to
     this object as possible for the particular probe
     implementation and available resources."
  DEFVAL { 50 }



  ::= { usrHistoryControlEntry 3 }

usrHistoryControlBucketsGranted OBJECT-TYPE
  SYNTAX Integer32 (1..65535)
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
     "The number of discrete sampling intervals
     over which data shall be saved in the part of
```

the usrHistoryTable associated with this
usrHistoryControlEntry.

When the associated usrHistoryControlBucketsRequested
object is created or modified, the probe should set
this object as closely to the requested value as
possible for the particular probe implementation and
available resources. The probe must not lower this
value except as a result of a modification to the associated
usrHistoryControlBucketsRequested object.

The associated usrHistoryControlBucketsRequested object
should be set before or at the same time as this object
to allow the probe to accurately estimate the resources
required for this usrHistoryControlEntry.

There will be times when the actual number of buckets
associated with this entry is less than the value of
this object. In this case, at the end of each sampling
interval, a new bucket will be added to the usrHistoryTable.

When the number of buckets reaches the value of this object
and a new bucket is to be added to the usrHistoryTable,
the oldest bucket associated with this usrHistoryControlEntry
shall be deleted by the agent so that the new bucket can be
added.

When the value of this object changes to a value less than
the current value, entries are deleted from the
usrHistoryTable associated with
this usrHistoryControlEntry.
Enough of the oldest of these entries shall be deleted by the
agent so that their number remains less than or equal to the
new value of this object.

When the value of this object changes to a value greater
than the current value, the number of associated usrHistory
entries may be allowed to grow."
::= { usrHistoryControlEntry 4 }

usrHistoryControlInterval OBJECT-TYPE
SYNTAX Integer32 (1..2147483647)
MAX-ACCESS read-create
STATUS current
DESCRIPTION

"The interval in seconds over which the data is
sampled for each bucket in the part of the usrHistory
table associated with this usrHistoryControlEntry.

Because the counters in a bucket may overflow at their
maximum value with no indication, a prudent manager will
take into account the possibility of overflow in any of
the associated counters. It is important to consider the

minimum time in which any counter could overflow on a
particular media type and to set the usrHistoryControlInterval
object to a value less than this interval.

This object may not be modified if the associated
usrHistoryControlStatus object is equal to active(1)."
DEFVAL { 1800 }
::= { usrHistoryControlEntry 5 }

usrHistoryControlOwner OBJECT-TYPE
SYNTAX OwnerString
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The entity that configured this entry and is
therefore using the resources assigned to it."
::= { usrHistoryControlEntry 6 }

usrHistoryControlStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The status of this variable history control entry.

An entry may not exist in the active state unless all
objects in the entry have an appropriate value.

If this object is not equal to active(1), all associated
entries
in the usrHistoryTable shall be deleted."
::= { usrHistoryControlEntry 7 }

-- Object table

usrHistoryObjectTable OBJECT-TYPE

```
  SYNTAX SEQUENCE OF UsrHistoryObjectEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "A list of data-collection configuration entries."
  ::= { usrHistory 2 }

usrHistoryObjectEntry OBJECT-TYPE
  SYNTAX UsrHistoryObjectEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "A list of MIB instances to be sampled periodically.

    Entries in this table are created when an associated
    usrHistoryControlObjects object is created.

    The usrHistoryControlIndex value in the index is
    that of the associated usrHistoryControlEntry.

    For example, an instance of usrHistoryObjectVariable might be
    usrHistoryObjectVariable.1.3"
  INDEX { usrHistoryControlIndex, usrHistoryObjectIndex }
  ::= { usrHistoryObjectTable 1 }

UsrHistoryObjectEntry ::= SEQUENCE {

  usrHistoryObjectIndex           Integer32,
  usrHistoryObjectVariable        OBJECT IDENTIFIER,
  usrHistoryObjectSampleType      INTEGER
}

usrHistoryObjectIndex OBJECT-TYPE
  SYNTAX Integer32 (1..65535)
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "An index used to uniquely identify an entry in the
    usrHistoryObject table.  Each such entry defines a
    MIB instance to be collected periodically."
  ::= { usrHistoryObjectEntry 1 }


usrHistoryObjectVariable OBJECT-TYPE
  SYNTAX OBJECT IDENTIFIER
  MAX-ACCESS read-create
  STATUS current
  DESCRIPTION
```

"The object identifier of the particular variable to be

sampled.

Only variables that resolve to an ASN.1 primitive type of Integer32 (Integer32, Counter, Gauge, or TimeTicks) may be sampled.

Because SNMP access control is articulated entirely in terms of the contents of MIB views, no access control mechanism

exists that can restrict the value of this object to identify only those objects that exist in a particular MIB view. Because there is thus no acceptable means of restricting the read access that could be obtained through the user history mechanism, the probe must only grant write access to this object in those views that have read access to all objects on the probe. See USM [RFC3414] and VACM [RFC3415] for more information.

During a set operation, if the supplied variable name is not available in the selected MIB view, a badValue error must be returned.

This object may not be modified if the associated usrHistoryControlStatus object is equal to active(1)."

::= { usrHistoryObjectEntry 2 }

```
usrHistoryObjectSampleType OBJECT-TYPE
  SYNTAX INTEGER {
          absoluteValue(1),
          deltaValue(2)
        }
  MAX-ACCESS read-create
  STATUS current
  DESCRIPTION
```

"The method of sampling the selected variable for storage in the usrHistoryTable.

If the value of this object is absoluteValue(1), the value of the selected variable will be copied directly into the history bucket.

If the value of this object is deltaValue(2), the value of the selected variable at the last sample will be subtracted from the current value, and the difference will be stored in the

```
      history bucket.  If the associated usrHistoryObjectVariable
      instance could not be obtained at the previous sample
      interval, then a delta sample is not possible, and the value
      of the associated usrHistoryValStatus object for this interval
      will be valueNotAvailable(1).



      This object may not be modified if the associated
      usrHistoryControlStatus object is equal to active(1)."
  ::= { usrHistoryObjectEntry 3 }

-- data table

usrHistoryTable OBJECT-TYPE
  SYNTAX SEQUENCE OF UsrHistoryEntry
   MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
     "A list of user-defined history entries."
  ::= { usrHistory 3 }

usrHistoryEntry OBJECT-TYPE
  SYNTAX UsrHistoryEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
     "A historical sample of user-defined variables.  This sample
     is associated with the usrHistoryControlEntry that set up the
     parameters for a regular collection of these samples.

     The usrHistoryControlIndex value in the index identifies the
     usrHistoryControlEntry on whose behalf this entry was created.
     The usrHistoryObjectIndex value in the index identifies the
     usrHistoryObjectEntry on whose behalf this entry was created.

     For example, an instance of usrHistoryAbsValue, which represents
     the 14th sample of a variable collected as specified by
     usrHistoryControlEntry.1 and usrHistoryObjectEntry.1.5,
     would be named usrHistoryAbsValue.1.14.5"
   INDEX { usrHistoryControlIndex, usrHistorySampleIndex,
           usrHistoryObjectIndex }
  ::= { usrHistoryTable 1 }

UsrHistoryEntry ::= SEQUENCE {
  usrHistorySampleIndex   Integer32,
  usrHistoryIntervalStart TimeStamp,
  usrHistoryIntervalEnd   TimeStamp,
```

```
  usrHistoryAbsValue      Gauge32,
  usrHistoryValStatus     INTEGER
}

usrHistorySampleIndex OBJECT-TYPE
  SYNTAX     Integer32 (1..2147483647)
  MAX-ACCESS not-accessible
  STATUS     current



  DESCRIPTION
      "An index that uniquely identifies the particular sample this
      entry represents among all samples associated with the same
      usrHistoryControlEntry.  This index starts at 1 and increases
      by one as each new sample is taken."
  ::= { usrHistoryEntry 1 }

usrHistoryIntervalStart OBJECT-TYPE
  SYNTAX TimeStamp
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
      "The value of sysUpTime at the start of the interval over
      which this sample was
 measured.  If the probe keeps track of
      the time of day, it should start the first sample of the
      history at a time such that when the next hour of the day
      begins, a sample is started at that instant.

      Note that following this rule may require that the probe delay
      collecting the first sample of the history, as each sample
      must be of the same interval.  Also note that the sample that
      is currently being collected is not accessible in this table
      until the end of its interval."
  ::= { usrHistoryEntry 2 }

usrHistoryIntervalEnd OBJECT-TYPE
  SYNTAX TimeStamp
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
      "The value of sysUpTime at the end of the interval over which
      this sample was measured."
  ::= { usrHistoryEntry 3 }

usrHistoryAbsValue OBJECT-TYPE
  SYNTAX Gauge32
```

```
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The absolute value (i.e., unsigned value) of the

    user-specified statistic during the last sampling period.  The
        value during the current sampling period is not made available
        until the period is completed.

        To obtain the true value for this sampling interval, the
        associated instance of usrHistoryValStatus must be checked,
        and usrHistoryAbsValue adjusted as necessary.




        If the MIB instance could not be accessed during the sampling
        interval, then this object will have a value of zero, and the
        associated instance of usrHistoryValStatus will be set to
        'valueNotAvailable(1)'.

        The access control check prescribed in the definition of
        usrHistoryObjectVariable SHOULD be checked for each sampling
        interval.  If this check determines that access should not be
        allowed, then this object will have a value of zero, and the
        associated instance of usrHistoryValStatus will be set to
        'valueNotAvailable(1)'."
    ::= { usrHistoryEntry
    4 }


usrHistoryValStatus OBJECT-TYPE
    SYNTAX INTEGER {
        valueNotAvailable(1),
        valuePositive(2),
        valueNegative(3)
    }
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "This object indicates the validity and sign of the data in
        the associated instance of usrHistoryAbsValue.

        If the MIB instance could not be accessed during the sampling
        interval, then 'valueNotAvailable(1)' will be returned.

        If the sample is valid and the actual value of the sample is
        greater than or equal to zero, then 'valuePositive(2)' is
```

```
      returned.

      If the sample is valid and the actual value of the sample is
      less than zero, 'valueNegative(3)' will be returned.  The
      associated instance of usrHistoryAbsValue should be multiplied
      by -1 to obtain the true sample value."
   ::= { usrHistoryEntry 5 }

-- The Probe Configuration Group
--
-- This group controls the configuration of various operating
--
 parameters of the probe.

ControlString ::= TEXTUAL-CONVENTION
   STATUS current
   DESCRIPTION
      "This data type is used to communicate with a modem or a




      serial data switch.  A ControlString contains embedded
      commands to control how the device will interact with the
      remote device through the serial interface.  Commands are
      represented as two-character sequences beginning with
      the '^' character.

      The following commands are recognized by the device (note
      that command characters are case sensitive):

        ^s  Send string that follows, which is terminated by the
            next command or the end of string.
        ^c  Delay for the number of seconds that follows.  Toss
            out any data received rather than store it in a
            buffer for parsing.
        ^t  Set timeout to the value represented by the decimal
            digits that follow.  The default timeout is 20

      seconds.  Note that this timeout may be overridden
            by a smaller serialTimeout configured for the
            associated serial interface (see serialConfigTable).
        ^w  Wait for the reply string that follows, which is
            terminated by the next command or the end of string.
            Partial and case-insensitive matching is applied, i.e.,
            if the reply string (any case combination) is found
            anywhere in the received string, then the a match is
            found.  If the current timeout elapses without a match,
            then the remaining control string is ignored.
```

^! The ^ character.
^d Delay the number of seconds specified by the decimal digits that follow.
^b Send break for the number of milliseconds specified by the decimal digits that follow. If no digits follow, break will be enforced for 250 milliseconds by default.

The following ASCII control characters may be inserted into the '^s' send string or the '^w' reply string:

^@ 0x00
^A 0x01
..
^M 0x0D
..
^Z 0x1A
^[0x1B
^ 0x1C
^] 0x1D
^^ 0x1E
^_ 0x1F

Binary data may also be inserted into the data stream. The control sequence for each byte of binary data is ^0x##, where ## is the hexadecimal representation of the data byte. Two ASCII characters (0-9, a-f, A-F) must follow the '^0x' control prefix. For example, '^0x0D^0x0A' is interpreted as a carriage return followed by a line feed."
SYNTAX OCTET STRING (SIZE (0..255))

probeCapabilities OBJECT-TYPE
SYNTAX BITS {
etherStats(0),
historyControl(1),
etherHistory(2),
alarm(3),
hosts(4),
hostTopN(5),
matrix(6),
filter(7),
capture(8),
event(9),
tokenRingMLStats(10),
tokenRingPStats(11),
tokenRingMLHistory(12),

```
      tokenRingPHistory(13),
      ringStation(14),
      ringStationOrder(15),
      ringStationConfig(16),
      sourceRouting(17),
      protocolDirectory(18),
      protocolDistribution(19),
      addressMapping(20),
      nlHost(21),
      nlMatrix(22),
      alHost(23),
      alMatrix(24),
      usrHistory(25),
      probeConfig(26)
    }
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
      "An indication of the RMON MIB groups supported
      on at least one interface by this probe."
    ::= { probeConfig 1 }

  probeSoftwareRev  OBJECT-TYPE
    SYNTAX     DisplayString (SIZE(0..15))
    MAX-ACCESS read-only



    STATUS     current
    DESCRIPTION
      "The software revision of this device.  This string will have
      a zero length if the revision is unknown."
    ::= { probeConfig 2 }

  probeHardwareRev
    OBJECT-TYPE
    SYNTAX     DisplayString (SIZE(0..31))
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
      "The hardware revision of this device.  This string will have
      a zero length if the revision is unknown."
    ::= { probeConfig 3 }

  probeDateTime  OBJECT-TYPE
    SYNTAX     OCTET STRING (SIZE (0 | 8 | 11))
    MAX-ACCESS read-write
    STATUS     current
```

DESCRIPTION
"Probe's current date and time.

field	octets	contents	range
1	1-2	year	0..65536
2	3	month	1..12
3	4	day	1..31
4	5	hour	0..23
5	6	minutes	0..59
6	7	seconds (use 60 for leap-second)	0..60
7	8	deci-seconds	0..9
8	9	direction from UTC	'+' / '-'
9	10	hours from UTC	0..11
10	11	minutes from UTC	0..59

For example, Tuesday May 26, 1992 at 1:30:15 PM
EDT would be displayed as:

1992-5-26,13:30:15.0,-4:0

Note that if only local time is known, then
time zone information (fields 8-10) is not
present, and that if no time information is known, the
null string is returned."
::= { probeConfig 4 }

probeResetControl OBJECT-TYPE

SYNTAX INTEGER {
running(1),
warmBoot(2),
coldBoot(3)
}

MAX-ACCESS read-write
STATUS current
DESCRIPTION
"Setting this object to warmBoot(2) causes the device to
restart the application software with current configuration
parameters saved in non-volatile memory. Setting this

object to coldBoot(3) causes the device to reinitialize
configuration parameters in non-volatile memory to default

```
      values and to restart the application software.  When the device
      is running normally, this variable has a value of
      running(1)."
  ::= { probeConfig 5 }

-- The following download objects do not restrict an implementation
-- from implementing additional download mechanisms (controlled in an
-- implementation-specific manner).  Further, in the case where the RMON
-- agent shares a processor with other types of systems, the
-- implementation is not required to download those non-RMON functions
-- with this mechanism.

probeDownloadFile  OBJECT-TYPE
  SYNTAX     DisplayString (SIZE(0..127))
  MAX-ACCESS read-write
  STATUS     deprecated
  DESCRIPTION
      "The file name to be downloaded from the TFTP server when a
      download is next requested via this MIB.  This value is set to
      the zero-length string when no file name
 has been specified.

      This object has been deprecated, as it has not had enough
      independent implementations to demonstrate interoperability to
      meet the requirements of a Draft Standard."
  ::= { probeConfig 6 }

probeDownloadTFTPServer  OBJECT-TYPE
  SYNTAX     IpAddress
  MAX-ACCESS read-write
  STATUS     deprecated
  DESCRIPTION
      "The IP address of the TFTP server that contains the boot
      image to load when a download is next requested via this MIB.
      This value is set to '0.0.0.0' when no IP address has been




      specified.

      This object has been deprecated, as it has not had enough
      independent implementations to demonstrate interoperability to
      meet the requirements of a Draft Standard."
  ::= { probeConfig 7 }

probeDownloadAction  OBJECT-TYPE
  SYNTAX     INTEGER {
               notDownloading(1),
```

```
            downloadToPROM(2),
            downloadToRAM(3)
          }
  MAX-ACCESS
read-write
  STATUS     deprecated
  DESCRIPTION
     "When this object is set to downloadToRAM(3) or
     downloadToPROM(2), the device will discontinue its
     normal operation and begin download of the image specified
     by probeDownloadFile from the server specified by
     probeDownloadTFTPServer using the TFTP protocol.  If
     downloadToRAM(3) is specified, the new image is copied
     to RAM only (the old image remains unaltered in the flash
     EPROM).  If downloadToPROM(2) is specified,
     the new image is written to the flash EPROM
     memory after its checksum has been verified to be correct.
     When the download process is completed, the device will
     warm boot to restart the newly loaded application.
     When the device is not downloading, this object will have
     a value of notDownloading(1).

     This object has been deprecated, as it has not had enough
     independent implementations to demonstrate
interoperability to
     meet the requirements of a Draft Standard."
  ::= { probeConfig 8 }

probeDownloadStatus  OBJECT-TYPE
  SYNTAX     INTEGER {
               downloadSuccess(1),
               downloadStatusUnknown(2),
               downloadGeneralError(3),
               downloadNoResponseFromServer(4),
               downloadChecksumError(5),
               downloadIncompatibleImage(6),
               downloadTftpFileNotFound(7),
               downloadTftpAccessViolation(8)
             }
  MAX-ACCESS read-only



  STATUS     deprecated
  DESCRIPTION
     "The status of the last download procedure, if any.  This
     object will have a value of downloadStatusUnknown(2) if no
     download process has been performed.
```

```
      This object has been deprecated, as it has not had enough
      independent implementations to demonstrate interoperability to
      meet the requirements of a Draft Standard."
    ::= { probeConfig 9 }

serialConfigTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF SerialConfigEntry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
      "A table of serial interface configuration entries.  This data
      will be stored in non-volatile memory and preserved across
      probe resets or power loss.

      This table has been deprecated, as it has not had enough
      independent implementations to demonstrate interoperability to
      meet the requirements of a Draft Standard."
  ::= { probeConfig 10 }

serialConfigEntry  OBJECT-TYPE
  SYNTAX     SerialConfigEntry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
      "A set of configuration parameters for a particular
      serial interface on this device.  If the device has no serial
      interfaces, this table is empty.

      The index is composed of the ifIndex assigned to this serial
      line interface."
  INDEX  { ifIndex }
  ::=
 { serialConfigTable 1 }

SerialConfigEntry ::= SEQUENCE {
  serialMode                INTEGER,
  serialProtocol            INTEGER,
  serialTimeout              Integer32,
  serialModemInitString       ControlString,
  serialModemHangUpString     ControlString,
  serialModemConnectResp      DisplayString,
  serialModemNoConnectResp    DisplayString,
  serialDialoutTimeout        Integer32,



  serialStatus              RowStatus
```

```
}

serialMode  OBJECT-TYPE
  SYNTAX     INTEGER {
               direct(1),
               modem(2)
             }
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "The type of incoming connection to be expected on this
      serial interface."
  DEFVAL { direct }
  ::= { serialConfigEntry 1 }

serialProtocol  OBJECT-TYPE
  SYNTAX     INTEGER {
               other(1),
               slip(2),
               ppp(3)
             }
  MAX-ACCESS read-create
  STATUS
    deprecated
  DESCRIPTION
     "The type of data link encapsulation to be used on this
     serial interface."
  DEFVAL { slip }
  ::= { serialConfigEntry 2 }

serialTimeout  OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "This timeout value is used when the Management Station has
     initiated the conversation over the serial link.  This variable
     represents the number of seconds of inactivity allowed before
     terminating the connection on this serial interface.  Use the
     serialDialoutTimeout in the case where the probe has initiated
     the connection for the purpose of sending a trap."
  DEFVAL { 300 }
  ::= { serialConfigEntry 3 }

serialModemInitString  OBJECT-TYPE
  SYNTAX     ControlString (SIZE (0..255))
  MAX-ACCESS read-create
  STATUS     deprecated
```

```
    DESCRIPTION
        "A control string that controls how a modem attached to this

   serial interface should be initialized.  The initialization
        is performed once during startup and again after each
        connection is terminated if the associated serialMode has the
        value of modem(2).

        A control string that is appropriate for a wide variety of
        modems is: '^s^MATE0Q0V1X4 S0=1 S2=43^M'."
    ::= { serialConfigEntry 4 }

serialModemHangUpString  OBJECT-TYPE
    SYNTAX     ControlString (SIZE (0..255))
    MAX-ACCESS read-create
    STATUS     deprecated
    DESCRIPTION
        "A control string that specifies how to disconnect a modem
         connection on this serial interface.  This object is only
         meaningful if the associated serialMode has the value
         of modem(2).

         A control string that is appropriate for a wide variety of
         modems is: '^d2^s+++^d2^sATH0^M^d2'."
    ::= { serialConfigEntry 5 }

serialModemConnectResp  OBJECT-TYPE
    SYNTAX     DisplayString (SIZE (0..255))
    MAX-ACCESS read-create

    STATUS     deprecated
    DESCRIPTION
        "An ASCII string containing substrings that describe the
        expected modem connection response code and associated bps
        rate.  The substrings are delimited by the first character
        in the string, for example:
          /CONNECT/300/CONNECT 1200/1200/CONNECT 2400/2400/
          CONNECT 4800/4800/CONNECT 9600/9600
        will be interpreted as:
           response code    bps rate
           CONNECT           300
           CONNECT 1200      1200
           CONNECT 2400      2400
           CONNECT 4800      4800
           CONNECT 9600      9600
```

```
      The agent will use the information in this string to adjust
      the bps rate of this serial interface once a modem connection
      is established.

      A value that is appropriate for a wide variety of modems is:



      '/CONNECT/300/CONNECT 1200/1200/CONNECT 2400/2400/
       CONNECT 4800/4800/CONNECT 9600/9600/CONNECT 14400/14400/
      CONNECT
 19200/19200/CONNECT 38400/38400/'."
  ::= { serialConfigEntry 6 }

serialModemNoConnectResp  OBJECT-TYPE
  SYNTAX     DisplayString (SIZE (0..255))
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
      "An ASCII string containing response codes that may be
      generated by a modem to report the reason why a connection
      attempt has failed.  The response codes are delimited by
      the first character in the string, for example:
        /NO CARRIER/BUSY/NO DIALTONE/NO ANSWER/ERROR/

      If one of these response codes is received via this serial
      interface while attempting to make a modem connection,
      the agent will issue the hang up command as specified by
      serialModemHangUpString.

      A value that is appropriate for a wide variety of modems is:
      '/NO CARRIER/BUSY/NO DIALTONE/NO ANSWER/ERROR/'."
  ::= { serialConfigEntry 7 }

serialDialoutTimeout  OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS
 read-create
  STATUS     deprecated
  DESCRIPTION
      "This timeout value is used when the probe initiates the
      serial connection with the intention of contacting a
      management station.  This variable represents the number
      of seconds of inactivity allowed before terminating the
      connection on this serial interface."
  DEFVAL { 20 }
  ::= { serialConfigEntry 8 }
```

```
serialStatus  OBJECT-TYPE
  SYNTAX     RowStatus
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "The status of this serialConfigEntry.

     An entry may not exist in the active state unless all
     objects in the entry have an appropriate value."
  ::= { serialConfigEntry 9 }



netConfigTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF NetConfigEntry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
     "A table of netConfigEntries.

     This table has been deprecated, as it has not had enough
     independent
 implementations to demonstrate interoperability to
     meet the requirements of a Draft Standard."
  ::= { probeConfig 11 }

netConfigEntry  OBJECT-TYPE
  SYNTAX     NetConfigEntry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
     "A set of configuration parameters for a particular
     network interface on this device.  If the device has no network
     interface, this table is empty.

     The index is composed of the ifIndex assigned to the
     corresponding interface."
  INDEX  { ifIndex }
  ::= { netConfigTable 1 }

NetConfigEntry ::= SEQUENCE {
  netConfigIPAddress         IpAddress,
  netConfigSubnetMask        IpAddress,
  netConfigStatus            RowStatus
}

netConfigIPAddress  OBJECT-TYPE
  SYNTAX     IpAddress
```

MAX-ACCESS read-create
STATUS deprecated
DESCRIPTION
"The IP address of this Net interface. The default value
for this object is 0.0.0.0. If either the netConfigIPAddress
or netConfigSubnetMask is 0.0.0.0, then when the device
boots, it may use BOOTP to try to figure out what these
values should be. If BOOTP fails before the device
can talk on the network, this value must be configured
(e.g., through a terminal attached to the device). If BOOTP is
used, care should be taken to not send BOOTP broadcasts too
frequently and to eventually send them very infrequently if no
replies are received."
::= { netConfigEntry 1 }

netConfigSubnetMask OBJECT-TYPE
SYNTAX IpAddress
MAX-ACCESS read-create
STATUS deprecated
DESCRIPTION
"The subnet mask of this Net interface. The default value
for this object is 0.0.0.0. If either the netConfigIPAddress
or netConfigSubnetMask is 0.0.0.0, then when the device
boots, it may use BOOTP to try to figure out what these
values should be. If BOOTP fails before the device
can talk on
the network, this value must be configured
(e.g., through a terminal attached to the device). If BOOTP is
used, care should be taken to not send BOOTP broadcasts too
frequently and to eventually send them very infrequently if no
replies are received."
::= { netConfigEntry 2 }

netConfigStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS deprecated
DESCRIPTION
"The status of this netConfigEntry.

An entry may not exist in the active state unless all
objects in the entry have an appropriate value."
::= { netConfigEntry 3 }

netDefaultGateway OBJECT-TYPE
SYNTAX IpAddress

```
  MAX-ACCESS read-write
  STATUS     deprecated
  DESCRIPTION
     "The IP Address of the default gateway.  If this value is
     undefined or unknown, it shall have the value 0.0.0.0."
  ::= { probeConfig 12 }

-- Trap Destination Table
--
-- This table defines the destination addresses for traps
 generated
-- from the device.  This table maps a community to one or more trap
-- destination entries.
--
-- The same trap will be sent to all destinations specified in the
-- entries that have the same trapDestCommunity as the eventCommunity
-- (as defined by RMON MIB), as long as no access control mechanism
-- (e.g., VACM) prohibits sending to one or more of the destinations.
-- Information in this table will be stored in non-volatile memory.



-- If the device has gone through a hard restart, this information
-- will be reset to its default state.

trapDestTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF TrapDestEntry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
     "A list of trap destination entries."
  ::= { probeConfig 13 }

trapDestEntry  OBJECT-TYPE
  SYNTAX     TrapDestEntry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
     "This entry includes a destination IP address to which
     traps are sent for this community."
   INDEX { trapDestIndex }
  ::= { trapDestTable 1 }

TrapDestEntry ::= SEQUENCE {
  trapDestIndex              Integer32,
  trapDestCommunity          OCTET STRING,
  trapDestProtocol           INTEGER,
  trapDestAddress            OCTET STRING,
```

```
  trapDestOwner             OwnerString,
  trapDestStatus            RowStatus
}

trapDestIndex  OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
     "A value that uniquely identifies this trapDestEntry."
  ::= { trapDestEntry 1 }

trapDestCommunity  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE(0..127))
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "A community to which this destination address belongs.
     This entry is associated with any eventEntries in the RMON
     MIB whose value of eventCommunity is equal to the value of
     this object.  Every time an associated event entry sends a

    trap due to an event, that trap will be sent to each



     address in the trapDestTable with a trapDestCommunity equal
     to eventCommunity, as long as no access control mechanism
     precludes it (e.g., VACM).

     This object may not be modified if the associated
     trapDestStatus object is equal to active(1)."
  ::= { trapDestEntry 2 }

trapDestProtocol OBJECT-TYPE
  SYNTAX     INTEGER {
                ip(1),
                ipx(2)
             }
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "The protocol with which this trap is to be sent."
  ::= { trapDestEntry 3 }

trapDestAddress  OBJECT-TYPE
  SYNTAX     OCTET STRING
  MAX-ACCESS read-create
```

```
  STATUS     deprecated
  DESCRIPTION
     "The destination address for traps on behalf of this entry.

     If the associated trapDestProtocol object is equal to ip(1),
     the encoding of this object is the same as the snmpUDPAddress
     textual
convention in RFC 3417, 'Transport Mappings for the
      Simple Network Management Protocol (SNMP)' [RFC3417]:
       -- for a SnmpUDPAddress of length 6:
       --
       -- octets   contents        encoding
       --  1-4     IP-address      network-byte order
       --  5-6     UDP-port        network-byte order

     If the associated trapDestProtocol object is equal to ipx(2),
     the encoding of this object is the same as the snmpIPXAddress
     textual convention in RFC 3417, 'Transport Mappings for the
      Simple Network Management Protocol (SNMP)' [RFC3417]:
       -- for a SnmpIPXAddress of length 12:
       --
       -- octets   contents           encoding
       --  1-4     network-number     network-byte order
       --  5-10    physical-address   network-byte order
       -- 11-12    socket-number      network-byte order

     This object may not be modified if the associated




     trapDestStatus object
 is equal to active(1)."
  ::= { trapDestEntry 4 }

trapDestOwner  OBJECT-TYPE
  SYNTAX     OwnerString
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "The entity that configured this entry and is
     therefore using the resources assigned to it."
  ::= { trapDestEntry 5 }

trapDestStatus  OBJECT-TYPE
  SYNTAX     RowStatus
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
```

```
      "The status of this trap destination entry.

      An entry may not exist in the active state unless all
      objects in the entry have an appropriate value."
   ::= { trapDestEntry 6 }

-- Serial Connection Table
--
-- The device may communicate with a management station using
-- SLIP.  In order for the device to send traps via SLIP, it must
-- be able to initiate a connection over the serial interface.  The
-- serialConnectionTable stores the parameters for such connection
-- initiation.

serialConnectionTable  OBJECT-TYPE
   SYNTAX     SEQUENCE
 OF SerialConnectionEntry
   MAX-ACCESS not-accessible
   STATUS     deprecated
   DESCRIPTION
      "A list of serialConnectionEntries.

      This table has been deprecated, as it has not had enough
      independent implementations to demonstrate interoperability
      to meet the requirements of a Draft Standard."
   ::= { probeConfig 14 }

serialConnectionEntry  OBJECT-TYPE
   SYNTAX     SerialConnectionEntry
   MAX-ACCESS not-accessible
   STATUS     deprecated
   DESCRIPTION




      "Configuration for a SLIP link over a serial line."
   INDEX { serialConnectIndex }
   ::= { serialConnectionTable 1 }

SerialConnectionEntry ::= SEQUENCE {
   serialConnectIndex                Integer32,
   serialConnectDestIpAddress        IpAddress,
   serialConnectType                 INTEGER,
   serialConnectDialString           ControlString,
   serialConnectSwitchConnectSeq     ControlString,
   serialConnectSwitchDisconnectSeq  ControlString,
    serialConnectSwitchResetSeq      ControlString,
   serialConnectOwner                OwnerString,
```

```
  serialConnectStatus               RowStatus
}

serialConnectIndex  OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
     "A value that uniquely identifies this serialConnection
     entry."
  ::= { serialConnectionEntry 1 }

serialConnectDestIpAddress  OBJECT-TYPE
  SYNTAX     IpAddress
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "The IP Address that can be reached at the other end of this
     serial connection.

     This object may not be modified if the associated
     serialConnectStatus object is equal to active(1)."
  ::= { serialConnectionEntry 2 }


serialConnectType  OBJECT-TYPE
  SYNTAX     INTEGER {
                direct(1),
                modem(2),
                switch(3),
                modemSwitch(4)

    }
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION



     "The type of outgoing connection to be made.  If this object
     has the value direct(1), then a direct serial connection
     is assumed.  If this object has the value modem(2),
     then serialConnectDialString will be used to make a modem
     connection.  If this object has the value switch(3),
     then serialConnectSwitchConnectSeq will be used to establish
     the connection over a serial data switch, and
     serialConnectSwitchDisconnectSeq will be used to terminate
     the connection.  If this object has the value
```

```
      modem-switch(4), then a modem connection will be made first,
      followed by the switch connection.

      This object may not be modified if the associated
      serialConnectStatus object is equal to active(1)."
   DEFVAL { direct }
   ::= { serialConnectionEntry 3 }

serialConnectDialString  OBJECT-TYPE
   SYNTAX     ControlString (SIZE(0..255))
    MAX-ACCESS read-create
   STATUS     deprecated
   DESCRIPTION
      "A control string that specifies how to dial the phone
      number in order to establish a modem connection.  The
      string should include the dialing prefix and suffix.  For
      example: '^s^MATD9,888-1234^M' will instruct the Probe
      to send a carriage return, followed by the dialing prefix
      'ATD', the phone number '9,888-1234', and a carriage
      return as the dialing suffix.

      This object may not be modified if the associated
      serialConnectStatus object is equal to active(1)."
   ::= { serialConnectionEntry 4 }

serialConnectSwitchConnectSeq  OBJECT-TYPE
   SYNTAX     ControlString (SIZE(0..255))
   MAX-ACCESS read-create
   STATUS     deprecated
   DESCRIPTION
      "A control string that specifies how to establish a
      data switch connection.

      This object may not be modified if the associated
      serialConnectStatus object is
 equal to active(1)."
    ::= { serialConnectionEntry 5 }

serialConnectSwitchDisconnectSeq  OBJECT-TYPE
   SYNTAX     ControlString (SIZE(0..255))



   MAX-ACCESS read-create
   STATUS     deprecated
   DESCRIPTION
      "A control string that specifies how to terminate a
      data switch connection.
```

```
      This object may not be modified if the associated
      serialConnectStatus object is equal to active(1)."
   ::= { serialConnectionEntry 6 }

serialConnectSwitchResetSeq  OBJECT-TYPE
   SYNTAX     ControlString (SIZE(0..255))
   MAX-ACCESS read-create
   STATUS     deprecated
   DESCRIPTION
      "A control string that specifies how to reset a data
      switch in the event of a timeout.

      This object may not be modified if the associated
      serialConnectStatus object is equal to active(1)."
   ::= { serialConnectionEntry 7 }

serialConnectOwner  OBJECT-TYPE
   SYNTAX     OwnerString
   MAX-ACCESS read-create
   STATUS     deprecated
   DESCRIPTION
       "The entity that configured this entry and is
      therefore using the resources assigned to it."
   ::= { serialConnectionEntry 8 }

serialConnectStatus  OBJECT-TYPE
   SYNTAX     RowStatus
   MAX-ACCESS read-create
   STATUS     deprecated
   DESCRIPTION
      "The status of this serialConnectionEntry.

      If the manager attempts to set this object to active(1) when
      the serialConnectType is set to modem(2) or modem-switch(4)
      and the serialConnectDialString is a zero-length string or
      cannot be correctly parsed as a ConnectString, the set
      request will be rejected with badValue(3).

      If the manager attempts to set this object to active(1) when
      the serialConnectType is set to switch(3) or modem-switch(4)
      and the serialConnectSwitchConnectSeq,
      the serialConnectSwitchDisconnectSeq, or




      the serialConnectSwitchResetSeq is a zero-length string
      or cannot be correctly parsed as a ConnectString,
```

```
 the set
      request will be rejected with badValue(3).

      An entry may not exist in the active state unless all
      objects in the entry have an appropriate value."
  ::= { serialConnectionEntry 9 }

--
-- Extensions to the RMON 1 MIB for RMON 2 devices
--
-- These extensions include the standard LastCreateTime Textual
-- Convention for all control tables, as well as an augmentation of
-- the filter entry that provides variable-length offsets into
-- packets.


-- Each of the following, except for filterDroppedFrames, is a
-- read-only object which, if implemented, automatically appears when
-- the RMON1 row it is associated with is created.

etherStats2Table  OBJECT-TYPE
  SYNTAX     SEQUENCE OF EtherStats2Entry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1."
  ::= { statistics 4 }

etherStats2Entry  OBJECT-TYPE
  SYNTAX     EtherStats2Entry
  MAX-ACCESS not-accessible
  STATUS
    current
  DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1."
  AUGMENTS { etherStatsEntry }
  ::= { etherStats2Table 1 }

EtherStats2Entry ::= SEQUENCE {
  etherStatsDroppedFrames     Counter32,
  etherStatsCreateTime        LastCreateTime
}

etherStatsDroppedFrames OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
```

```
      "The total number of frames that were received by the probe
       and therefore not accounted for in the *StatsDropEvents, but
       that the probe chose not to count for this entry for
       whatever reason.  Most often, this event occurs when the
       probe is out of some resources and decides to shed load from
       this collection.

       This count does not include packets that were not counted
       because they had MAC-layer errors.

       Note that, unlike the dropEvents counter, this number is the
       exact number of frames dropped."
   ::= { etherStats2Entry
 1 }

etherStatsCreateTime OBJECT-TYPE
   SYNTAX     LastCreateTime
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The value of sysUpTime when this control entry was last
       activated.  This can be used by the management station to
       ensure that the table has not been deleted and recreated
       between polls."
   ::= { etherStats2Entry 2 }

historyControl2Table  OBJECT-TYPE
   SYNTAX     SEQUENCE OF HistoryControl2Entry
   MAX-ACCESS not-accessible
   STATUS     current
   DESCRIPTION
      "Contains the RMON-2 augmentations to RMON-1."
   ::= { history 5 }

historyControl2Entry  OBJECT-TYPE
   SYNTAX     HistoryControl2Entry
   MAX-ACCESS not-accessible
   STATUS     current
   DESCRIPTION
      "Contains the RMON-2 augmentations to RMON-1."
   AUGMENTS { historyControlEntry }
   ::= { historyControl2Table 1 }

HistoryControl2Entry ::= SEQUENCE {
   historyControlDroppedFrames Counter32
```

```
}

historyControlDroppedFrames
 OBJECT-TYPE
   SYNTAX     Counter32



   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
     "The total number of frames that were received by the probe
      and therefore not accounted for in the *StatsDropEvents, but
      that the probe chose not to count for this entry for
      whatever reason.  Most often, this event occurs when the
      probe is out of some resources and decides to shed load from
      this collection.

      This count does not include packets that were not counted
      because they had MAC-layer errors.

      Note that, unlike the dropEvents counter, this number is the
      exact number of frames dropped."
   ::= { historyControl2Entry 1 }

hostControl2Table  OBJECT-TYPE
   SYNTAX     SEQUENCE OF HostControl2Entry
   MAX-ACCESS not-accessible
   STATUS     current
   DESCRIPTION
      "Contains the RMON-2 augmentations to RMON-1."
   ::= { hosts 4 }

hostControl2Entry  OBJECT-TYPE
   SYNTAX     HostControl2Entry
    MAX-ACCESS not-accessible
   STATUS     current
   DESCRIPTION
      "Contains the RMON-2 augmentations to RMON-1."
   AUGMENTS { hostControlEntry }
   ::= { hostControl2Table 1 }

HostControl2Entry ::= SEQUENCE {
   hostControlDroppedFrames    Counter32,
   hostControlCreateTime       LastCreateTime
}

hostControlDroppedFrames OBJECT-TYPE
```

```
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The total number of frames that were received by the probe
     and therefore not accounted for in the *StatsDropEvents, but
     that the probe chose not to count for this entry for
     whatever reason.  Most often, this event occurs when the



     probe is out of some resources and decides to shed load from
     this collection.

     This count does not include packets that were not counted
     because they had MAC-layer errors.

     Note that, unlike the dropEvents counter, this number is the
     exact number
 of frames dropped."
  ::= { hostControl2Entry 1 }

hostControlCreateTime OBJECT-TYPE
  SYNTAX     LastCreateTime
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The value of sysUpTime when this control entry was last
     activated.  This can be used by the management station to
     ensure that the table has not been deleted and recreated
     between polls."
  ::= { hostControl2Entry 2 }

matrixControl2Table  OBJECT-TYPE
  SYNTAX     SEQUENCE OF MatrixControl2Entry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1."
  ::= { matrix 4 }

matrixControl2Entry  OBJECT-TYPE
  SYNTAX     MatrixControl2Entry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1."
  AUGMENTS { matrixControlEntry }
```

::= { matrixControl2Table 1 }

MatrixControl2Entry ::= SEQUENCE {
matrixControlDroppedFrames Counter32,
matrixControlCreateTime LastCreateTime
}

matrixControlDroppedFrames OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"The total number of frames that were received by the probe
and therefore not accounted for in the *StatsDropEvents, but
that the probe chose not to count for this entry for
whatever reason. Most often, this event occurs when the
probe is out of some resources and decides to shed load from
this collection.

This count does not include packets that were not counted
because they had MAC-layer errors.

Note that, unlike the dropEvents counter, this number is the
exact number of frames dropped."
::= { matrixControl2Entry 1 }

matrixControlCreateTime OBJECT-TYPE
SYNTAX LastCreateTime
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime when this control entry was last

activated. This can be used by the management station to
ensure that the table has not been deleted and recreated
between polls."
::= { matrixControl2Entry 2 }

channel2Table OBJECT-TYPE
SYNTAX SEQUENCE OF Channel2Entry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Contains the RMON-2 augmentations to RMON-1."
::= { filter 3 }

```
channel2Entry  OBJECT-TYPE
  SYNTAX     Channel2Entry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1."
  AUGMENTS { channelEntry }
  ::= { channel2Table 1 }

Channel2Entry ::= SEQUENCE {
  channelDroppedFrames    Counter32,
  channelCreateTime       LastCreateTime
}

channelDroppedFrames OBJECT-TYPE



  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The total number of frames that were received by the probe
      and therefore not accounted for in the *StatsDropEvents,
but
      that the probe chose not to count for this entry for
      whatever reason.  Most often, this event occurs when the
      probe is out of some resources and decides to shed load from
      this collection.

      This count does not include packets that were not counted
      because they had MAC-layer errors.

      Note that, unlike the dropEvents counter, this number is the
      exact number of frames dropped."
  ::= { channel2Entry 1 }

channelCreateTime OBJECT-TYPE
  SYNTAX     LastCreateTime
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The value of sysUpTime when this control entry was last
      activated.  This can be used by the management station to
      ensure that the table has not been deleted and recreated
      between polls."
  ::= { channel2Entry 2 }
```

```
tokenRingMLStats2Table  OBJECT-TYPE
  SYNTAX     SEQUENCE OF TokenRingMLStats2Entry
  MAX-ACCESS not-accessible
  STATUS     deprecated

 DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1.

     This table has been deprecated, as it has not had enough
     independent implementations to demonstrate interoperability
     to meet the requirements of a Draft Standard."
  ::= { statistics 5 }

tokenRingMLStats2Entry  OBJECT-TYPE
  SYNTAX     TokenRingMLStats2Entry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1."
  AUGMENTS { tokenRingMLStatsEntry }



  ::= { tokenRingMLStats2Table 1 }

TokenRingMLStats2Entry ::= SEQUENCE {
  tokenRingMLStatsDroppedFrames       Counter32,
  tokenRingMLStatsCreateTime          LastCreateTime
}

tokenRingMLStatsDroppedFrames OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     deprecated
  DESCRIPTION
     "The total number of frames that were received by the probe
     and therefore not accounted for in the *StatsDropEvents, but
     that the probe
 chose not to count for this entry for
     whatever reason.  Most often, this event occurs when the
     probe is out of some resources and decides to shed load from
     this collection.

     This count does not include packets that were not counted
     because they had MAC-layer errors.

     Note that, unlike the dropEvents counter, this number is the
```

```
      exact number of frames dropped."
   ::= { tokenRingMLStats2Entry 1 }

tokenRingMLStatsCreateTime OBJECT-TYPE
   SYNTAX     LastCreateTime
   MAX-ACCESS read-only
   STATUS     deprecated
   DESCRIPTION
      "The value of sysUpTime when this control entry was last
      activated.  This can be used by the management station to
      ensure that the table has not been deleted and recreated
      between polls."
   ::= { tokenRingMLStats2Entry 2 }

tokenRingPStats2Table  OBJECT-TYPE
   SYNTAX     SEQUENCE OF TokenRingPStats2Entry
   MAX-ACCESS not-accessible
   STATUS     deprecated
   DESCRIPTION
       "Contains the RMON-2 augmentations to RMON-1.

      This table has been deprecated, as it has not had enough
      independent implementations to demonstrate interoperability
      to meet the requirements of a Draft Standard."
   ::= { statistics 6 }



tokenRingPStats2Entry  OBJECT-TYPE
   SYNTAX     TokenRingPStats2Entry
   MAX-ACCESS not-accessible
   STATUS     deprecated
   DESCRIPTION
      "Contains the RMON-2 augmentations to RMON-1."
   AUGMENTS {  tokenRingPStatsEntry }
   ::= { tokenRingPStats2Table 1 }

TokenRingPStats2Entry ::= SEQUENCE {
   tokenRingPStatsDroppedFrames    Counter32,
   tokenRingPStatsCreateTime       LastCreateTime
}

tokenRingPStatsDroppedFrames OBJECT-TYPE
   SYNTAX     Counter32
   MAX-ACCESS read-only
   STATUS     deprecated
   DESCRIPTION
     "The total number of frames that were received by the probe
```

and therefore not accounted for in the *StatsDropEvents, but
that the probe chose not to count
for this entry for
whatever reason. Most often, this event occurs when the
probe is out of some resources and decides to shed load from
this collection.

This count does not include packets that were not counted
because they had MAC-layer errors.

Note that, unlike the dropEvents counter, this number is the
exact number of frames dropped."
::= { tokenRingPStats2Entry 1 }

tokenRingPStatsCreateTime OBJECT-TYPE
SYNTAX LastCreateTime
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
"The value of sysUpTime when this control entry was last
activated. This can be used by the management station to
ensure that the table has not been deleted and recreated
between polls."
::= { tokenRingPStats2Entry 2 }

ringStationControl2Table OBJECT-TYPE
SYNTAX SEQUENCE OF RingStationControl2Entry
MAX-ACCESS not-accessible
STATUS deprecated

DESCRIPTION

"Contains the RMON-2 augmentations to RMON-1.

This table has been deprecated, as it has not had enough
independent implementations to demonstrate interoperability
to meet the requirements of a Draft Standard."
::= { tokenRing 7 }

ringStationControl2Entry OBJECT-TYPE
SYNTAX RingStationControl2Entry
MAX-ACCESS not-accessible
STATUS deprecated
DESCRIPTION
"Contains the RMON-2 augmentations to RMON-1."
AUGMENTS { ringStationControlEntry }

::= { ringStationControl2Table 1 }

RingStationControl2Entry ::= SEQUENCE {
ringStationControlDroppedFrames Counter32,
ringStationControlCreateTime LastCreateTime
}

ringStationControlDroppedFrames OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
"The total number of frames that were received by the probe
and therefore not accounted for in the *StatsDropEvents, but
that the probe chose not to
count for this entry for
whatever reason. Most often, this event occurs when the
probe is out of some resources and decides to shed load from
this collection.

This count does not include packets that were not counted
because they had MAC-layer errors.

Note that, unlike the dropEvents counter, this number is the
exact number of frames dropped."
::= { ringStationControl2Entry 1 }

ringStationControlCreateTime OBJECT-TYPE
SYNTAX LastCreateTime
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
"The value of sysUpTime when this control entry was last
activated. This can be used by the management station to

ensure that the table has not been deleted and recreated
between polls."
::= { ringStationControl2Entry 2 }

sourceRoutingStats2Table OBJECT-TYPE
SYNTAX SEQUENCE OF SourceRoutingStats2Entry
MAX-ACCESS not-accessible
STATUS deprecated
DESCRIPTION
"Contains the RMON-2 augmentations to RMON-1.

```
      This table has been deprecated, as it has not had enough
      independent implementations to demonstrate interoperability
      to meet the requirements of a Draft Standard."
   ::= { tokenRing 8 }

sourceRoutingStats2Entry  OBJECT-TYPE
   SYNTAX     SourceRoutingStats2Entry
   MAX-ACCESS not-accessible
   STATUS     deprecated
   DESCRIPTION
      "Contains the RMON-2 augmentations to RMON-1."
   AUGMENTS { sourceRoutingStatsEntry }
   ::= { sourceRoutingStats2Table 1 }

SourceRoutingStats2Entry ::= SEQUENCE {
   sourceRoutingStatsDroppedFrames Counter32,
   sourceRoutingStatsCreateTime    LastCreateTime
}

sourceRoutingStatsDroppedFrames OBJECT-TYPE
   SYNTAX     Counter32
   MAX-ACCESS read-only
   STATUS     deprecated
   DESCRIPTION
      "The total number of frames that were received by the probe
      and therefore not accounted for in the *StatsDropEvents, but
      that the probe chose
 not to count for this entry for
      whatever reason.  Most often, this event occurs when the
      probe is out of some resources and decides to shed load from
      this collection.

      This count does not include packets that were not counted
      because they had MAC-layer errors.

      Note that, unlike the dropEvents counter, this number is the
      exact number of frames dropped."
   ::= { sourceRoutingStats2Entry 1 }



sourceRoutingStatsCreateTime OBJECT-TYPE
   SYNTAX     LastCreateTime
   MAX-ACCESS read-only
   STATUS     deprecated
   DESCRIPTION
      "The value of sysUpTime when this control entry was last
      activated.  This can be used by the management station to
```

```
      ensure that the table has not been deleted and recreated
      between polls."
  ::= { sourceRoutingStats2Entry 2 }

filter2Table OBJECT-TYPE
  SYNTAX     SEQUENCE OF Filter2Entry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
      "Provides
 a variable-length packet filter feature to the
      RMON-1 filter table."
  ::= { filter 4 }

filter2Entry OBJECT-TYPE
  SYNTAX     Filter2Entry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
      "Provides a variable-length packet filter feature to the
      RMON-1 filter table."
  AUGMENTS { filterEntry }
  ::= { filter2Table 1 }

Filter2Entry ::= SEQUENCE {
  filterProtocolDirDataLocalIndex     Integer32,
  filterProtocolDirLocalIndex         Integer32
}

filterProtocolDirDataLocalIndex OBJECT-TYPE
  SYNTAX     Integer32 (0..2147483647)
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
      "When this object is set to a non-zero value, the filter that
      it is associated with performs the following operations on
      every packet:

      1) If the packet doesn't match the protocol directory entry
         identified by this object, discard the packet and exit
         (i.e., discard the packet if it
 is not of the identified
         protocol).



      2) If the associated filterProtocolDirLocalIndex is non-zero
         and the packet doesn't match the protocol directory
```

```
        entry identified by that object, discard the packet and
        exit.
      3) If the packet matches, perform the regular filter
        algorithm as if the beginning of this named protocol is
        the beginning of the packet, potentially applying the
        filterOffset value to move further into the packet."
  DEFVAL { 0 }
  ::= { filter2Entry 1 }

filterProtocolDirLocalIndex OBJECT-TYPE
  SYNTAX     Integer32 (0..2147483647)
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "When this object is set to a non-zero value, the filter that
     it is associated with will discard the packet if the packet
     doesn't match this protocol directory entry."
  DEFVAL { 0 }
  ::= { filter2Entry 2 }

-- Conformance Macros

rmon2MIBCompliances OBJECT
 IDENTIFIER ::= { rmonConformance 1 }
rmon2MIBGroups      OBJECT IDENTIFIER ::= { rmonConformance 2 }


rmon2MIBCompliance MODULE-COMPLIANCE
  STATUS  current
  DESCRIPTION
     "Describes the requirements for conformance to
     the RMON2 MIB"
  MODULE  -- this module
     MANDATORY-GROUPS { protocolDirectoryGroup,
                        protocolDistributionGroup,
                        addressMapGroup,
                        nlHostGroup,
                        nlMatrixGroup,
                        usrHistoryGroup,
                        probeInformationGroup }

     OBJECT nlMatrixTopNControlRateBase
        SYNTAX      INTEGER {
                      nlMatrixTopNPkts(1),
                      nlMatrixTopNOctets(2)
                    }
        DESCRIPTION
```

```
            "Conformance to RMON2 requires only support for these
            values of nlMatrixTopNControlRateBase."

        GROUP   rmon1EnhancementGroup
            DESCRIPTION
            "The rmon1EnhancementGroup is mandatory for systems
            that implement RMON [RFC2819]."
        GROUP  rmon1EthernetEnhancementGroup
          DESCRIPTION
            "The rmon1EthernetEnhancementGroup is optional and is
            appropriate for systems that implement the Ethernet
            group of RMON [RFC2819]."
    ::= { rmon2MIBCompliances 1 }

rmon2MIBApplicationLayerCompliance MODULE-COMPLIANCE
    STATUS  current
    DESCRIPTION
      "Describes the requirements for conformance to
      the RMON2 MIB with Application-Layer Enhancements."
    MODULE  -- this module
      MANDATORY-GROUPS { protocolDirectoryGroup,
                         protocolDistributionGroup,
                         addressMapGroup,
                         nlHostGroup,
                         nlMatrixGroup,
                         alHostGroup,
                         alMatrixGroup,
                         usrHistoryGroup,
                          probeInformationGroup }

      OBJECT nlMatrixTopNControlRateBase
        SYNTAX      INTEGER {
                      nlMatrixTopNPkts(1),
                      nlMatrixTopNOctets(2)
                    }
        DESCRIPTION
          "Conformance to RMON2 requires only support for these
          values of nlMatrixTopNControlRateBase."

      OBJECT alMatrixTopNControlRateBase
        SYNTAX     INTEGER {
                      alMatrixTopNTerminalsPkts(1),
                      alMatrixTopNTerminalsOctets(2),
                      alMatrixTopNAllPkts(3),
                      alMatrixTopNAllOctets(4)
                    }
```

```
        DESCRIPTION
            "Conformance to RMON2 requires only support for these




            values of alMatrixTopNControlRateBase."

        GROUP   rmon1EnhancementGroup
          DESCRIPTION
            "The rmon1EnhancementGroup is mandatory
 for systems
            that implement RMON [RFC2819]."
        GROUP  rmon1EthernetEnhancementGroup
          DESCRIPTION
            "The rmon1EthernetEnhancementGroup is optional and is
            appropriate for systems that implement the Ethernet
            group of RMON [RFC2819]."
    ::= { rmon2MIBCompliances 2 }


protocolDirectoryGroup OBJECT-GROUP
    OBJECTS { protocolDirLastChange,
              protocolDirLocalIndex, protocolDirDescr,
              protocolDirType, protocolDirAddressMapConfig,
              protocolDirHostConfig, protocolDirMatrixConfig,
              protocolDirOwner, protocolDirStatus }
    STATUS  current
    DESCRIPTION
        "Lists the inventory of protocols the probe has the
        capability of monitoring and allows the addition, deletion,
        and configuration of entries in this list."
    ::= { rmon2MIBGroups 1 }

protocolDistributionGroup OBJECT-GROUP
    OBJECTS { protocolDistControlDataSource,
              protocolDistControlDroppedFrames,
               protocolDistControlCreateTime,
              protocolDistControlOwner, protocolDistControlStatus,
              protocolDistStatsPkts, protocolDistStatsOctets }
    STATUS  current
    DESCRIPTION
        "Collects the relative amounts of octets and packets for the
        different protocols detected on a network segment."
    ::= { rmon2MIBGroups 2 }

addressMapGroup OBJECT-GROUP
    OBJECTS { addressMapInserts, addressMapDeletes,
              addressMapMaxDesiredEntries,
```

```
            addressMapControlDataSource,
            addressMapControlDroppedFrames,
            addressMapControlOwner, addressMapControlStatus,
            addressMapPhysicalAddress,
            addressMapLastChange }
    STATUS  current



    DESCRIPTION
        "Lists MAC address to network address bindings discovered by
        the probe and what interface they were last seen on."
    ::= { rmon2MIBGroups 3 }

nlHostGroup OBJECT-GROUP
    OBJECTS { hlHostControlDataSource,
              hlHostControlNlDroppedFrames, hlHostControlNlInserts,
              hlHostControlNlDeletes,
              hlHostControlNlMaxDesiredEntries,
              hlHostControlAlDroppedFrames, hlHostControlAlInserts,
              hlHostControlAlDeletes,
              hlHostControlAlMaxDesiredEntries, hlHostControlOwner,
              hlHostControlStatus, nlHostInPkts, nlHostOutPkts,
              nlHostInOctets, nlHostOutOctets,
              nlHostOutMacNonUnicastPkts, nlHostCreateTime }
    STATUS  current
    DESCRIPTION
        "Counts the amount of traffic sent from and to each network
        address discovered by the probe.  Note that while the
        hlHostControlTable also has objects that control an optional
        alHostTable, implementation of the alHostTable is not
        required to fully implement this group."
    ::= { rmon2MIBGroups 4 }

nlMatrixGroup OBJECT-GROUP
    OBJECTS { hlMatrixControlDataSource,
              hlMatrixControlNlDroppedFrames,
              hlMatrixControlNlInserts, hlMatrixControlNlDeletes,
              hlMatrixControlNlMaxDesiredEntries,
              hlMatrixControlAlDroppedFrames,
              hlMatrixControlAlInserts, hlMatrixControlAlDeletes,
              hlMatrixControlAlMaxDesiredEntries,
              hlMatrixControlOwner, hlMatrixControlStatus,
              nlMatrixSDPkts, nlMatrixSDOctets, nlMatrixSDCreateTime,
              nlMatrixDSPkts, nlMatrixDSOctets, nlMatrixDSCreateTime,
              nlMatrixTopNControlMatrixIndex,
              nlMatrixTopNControlRateBase,
              nlMatrixTopNControlTimeRemaining,
```

```
            nlMatrixTopNControlGeneratedReports,
            nlMatrixTopNControlDuration,
            nlMatrixTopNControlRequestedSize,
            nlMatrixTopNControlGrantedSize,
            nlMatrixTopNControlStartTime,
            nlMatrixTopNControlOwner, nlMatrixTopNControlStatus,
            nlMatrixTopNProtocolDirLocalIndex,
            nlMatrixTopNSourceAddress,
 nlMatrixTopNDestAddress,
            nlMatrixTopNPktRate, nlMatrixTopNReversePktRate,




            nlMatrixTopNOctetRate, nlMatrixTopNReverseOctetRate }
    STATUS  current
    DESCRIPTION
        "Counts the amount of traffic sent between each pair of
        network addresses discovered by the probe.  Note that while
        the hlMatrixControlTable also has objects that control
        optional alMatrixTables, implementation of the
        alMatrixTables is not required to fully implement this
        group."
    ::= { rmon2MIBGroups 5 }

alHostGroup OBJECT-GROUP
    OBJECTS { alHostInPkts, alHostOutPkts,
            alHostInOctets, alHostOutOctets, alHostCreateTime }
    STATUS  current
    DESCRIPTION
        "Counts the amount of traffic, by protocol, sent from and to
        each network address discovered by the probe.  Implementation
        of this group requires implementation of the Network-Layer
        Host Group."
    ::= { rmon2MIBGroups 6 }

alMatrixGroup
 OBJECT-GROUP
    OBJECTS { alMatrixSDPkts, alMatrixSDOctets, alMatrixSDCreateTime,
            alMatrixDSPkts, alMatrixDSOctets, alMatrixDSCreateTime,
            alMatrixTopNControlMatrixIndex,
            alMatrixTopNControlRateBase,
            alMatrixTopNControlTimeRemaining,
            alMatrixTopNControlGeneratedReports,
            alMatrixTopNControlDuration,
            alMatrixTopNControlRequestedSize,
            alMatrixTopNControlGrantedSize,
            alMatrixTopNControlStartTime,
            alMatrixTopNControlOwner, alMatrixTopNControlStatus,
```

```
            alMatrixTopNProtocolDirLocalIndex,
            alMatrixTopNSourceAddress, alMatrixTopNDestAddress,
            alMatrixTopNAppProtocolDirLocalIndex,
            alMatrixTopNPktRate, alMatrixTopNReversePktRate,
            alMatrixTopNOctetRate, alMatrixTopNReverseOctetRate }
    STATUS  current
    DESCRIPTION
       "Counts the amount of traffic, by protocol, sent between each
        pair of network addresses discovered by the
       probe.  Implementation of this group requires implementation
       of the Network-Layer Matrix Group."
    ::= { rmon2MIBGroups 7 }

usrHistoryGroup OBJECT-GROUP



    OBJECTS { usrHistoryControlObjects,
            usrHistoryControlBucketsRequested,
            usrHistoryControlBucketsGranted,
            usrHistoryControlInterval,
            usrHistoryControlOwner, usrHistoryControlStatus,
            usrHistoryObjectVariable, usrHistoryObjectSampleType,
            usrHistoryIntervalStart, usrHistoryIntervalEnd,
            usrHistoryAbsValue, usrHistoryValStatus }
    STATUS  current
    DESCRIPTION
       "The usrHistoryGroup provides user-defined collection of
       historical information from MIB objects on the probe."
    ::= { rmon2MIBGroups 8 }

probeInformationGroup OBJECT-GROUP
    OBJECTS { probeCapabilities,
            probeSoftwareRev, probeHardwareRev, probeDateTime }
    STATUS  current
     DESCRIPTION
       "This group describes various operating parameters of the
       probe and controls the local time of the probe."
    ::= { rmon2MIBGroups 9 }

probeConfigurationGroup OBJECT-GROUP
    OBJECTS { probeResetControl, probeDownloadFile,
            probeDownloadTFTPServer, probeDownloadAction,
            probeDownloadStatus,
            serialMode, serialProtocol, serialTimeout,
            serialModemInitString, serialModemHangUpString,
            serialModemConnectResp, serialModemNoConnectResp,
            serialDialoutTimeout, serialStatus,
```

```
            netConfigIPAddress, netConfigSubnetMask,
            netConfigStatus, netDefaultGateway,
            trapDestCommunity, trapDestProtocol, trapDestAddress,
            trapDestOwner, trapDestStatus,
            serialConnectDestIpAddress, serialConnectType,
            serialConnectDialString, serialConnectSwitchConnectSeq,
            serialConnectSwitchDisconnectSeq,
            serialConnectSwitchResetSeq,
             serialConnectOwner, serialConnectStatus }
    STATUS  deprecated
    DESCRIPTION
       "This group controls the configuration of various operating
       parameters of the probe.  This group is not referenced by any
       MODULE-COMPLIANCE macro because it is 'grandfathered' from
       more recent MIB review rules that would require it."
    ::= { rmon2MIBGroups 10 }



rmon1EnhancementGroup OBJECT-GROUP
    OBJECTS { historyControlDroppedFrames, hostControlDroppedFrames,
              hostControlCreateTime, matrixControlDroppedFrames,
              matrixControlCreateTime, channelDroppedFrames,
              channelCreateTime, filterProtocolDirDataLocalIndex,
              filterProtocolDirLocalIndex }
    STATUS  current
    DESCRIPTION
       "This group adds some enhancements to RMON-1 that help
       management stations."
    ::= { rmon2MIBGroups 11 }

rmon1EthernetEnhancementGroup OBJECT-GROUP
    OBJECTS { etherStatsDroppedFrames,
   etherStatsCreateTime }
    STATUS  current
    DESCRIPTION
       "This group adds some enhancements to RMON-1 that help
       management stations."
    ::= { rmon2MIBGroups 12 }

rmon1TokenRingEnhancementGroup OBJECT-GROUP
    OBJECTS { tokenRingMLStatsDroppedFrames,
              tokenRingMLStatsCreateTime,
              tokenRingPStatsDroppedFrames, tokenRingPStatsCreateTime,
              ringStationControlDroppedFrames,
              ringStationControlCreateTime,
              sourceRoutingStatsDroppedFrames,
```

```
          sourceRoutingStatsCreateTime }
  STATUS  deprecated
  DESCRIPTION
     "This group adds some enhancements to RMON-1 that help
     management stations.  This group is not referenced by any
     MODULE-COMPLIANCE macro because it is 'grandfathered' from
     more recent MIB review rules that would require it."
  ::= { rmon2MIBGroups 13 }
END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/RMON2-MIB
No license file was found, but licenses were detected in source scan.

```
SNA-NAU-MIB DEFINITIONS ::= BEGIN

-- This MIB module contains objects necessary
-- for management of the following SNA devices: PU types 1.0, 2.0, 2.1
-- and LU types 0, 1, 2, 3, 4, 7.  It also contains generic objects
-- which can be used to manage LU 6.2.

-- Naming conventions in this document:
-- The following names are used in object descriptors according to
-- SNA conventions.
-- The name 'PU' or 'Node' is used to describe Node type 1.0, 2.0 or
-- 2.1.
-- The name 'LU' is used to describe Logical Unit of type 0,1,2,3,
-- 4,7 or 6.2.



IMPORTS
     DisplayString, RowStatus, TimeStamp, InstancePointer
          FROM SNMPv2-TC

     Counter32, Gauge32, Integer32, mib-2,
     OBJECT-TYPE, MODULE-IDENTITY, NOTIFICATION-TYPE
          FROM SNMPv2-SMI

     MODULE-COMPLIANCE, OBJECT-GROUP
          FROM SNMPv2-CONF;


snanauMIB MODULE-IDENTITY
     LAST-UPDATED  "9405120900Z"

  ORGANIZATION  "IETF SNA NAU MIB Working Group"
     CONTACT-INFO
```

```
            "       Zbigniew Kielczewski
                    Eicon Technology Inc.
                    2196 32nd Avenue
                    Lachine, Que  H8T 3H7
                    Canada
                    Tel:    1 514 631 2592
                    E-mail: zbig@eicon.qc.ca

                    Deirdre Kostick
                    Bellcore
                    331 Newman Springs Road
                    Red Bank, NJ 07701
                    Tel:    1 908 758 2642
                    E-mail: dck2@mail.bellcore.com

                    Kitty Shih (editor)
                    Novell
                    890 Ross Drive
                    Sunnyvale, CA 94089
                    Tel:   1 408 747 4305
                    E-mail: kmshih@novell.com"
      DESCRIPTION
            "This is the MIB module for objects used to
             manage
 SNA devices."
::= { mib-2 34 }

-- The SNANAU MIB module contains an objects part and a conformance part.
-- Objects are organized into the following groups:
-- (1)snaNode group,
-- (2)snaLU group,
-- (3)snaMgtTools group.

snanauObjects   OBJECT IDENTIFIER ::= { snanauMIB 1 }

 snaNode       OBJECT IDENTIFIER ::= { snanauObjects 1 }
 snaLu         OBJECT IDENTIFIER ::= { snanauObjects 2 }
 snaMgtTools   OBJECT IDENTIFIER ::= { snanauObjects 3}



-- ****************************************************************
-- snaNode group
--
-- It contains Managed Objects related to any type of Node and
-- some specific objects for Node Type 2.0.
-- ****************************************************************
```

```
-- ****************************************************************
-- The following table contains generic Node configuration
-- parameters.
-- ****************************************************************

snaNodeAdminTable OBJECT-TYPE
     SYNTAX  SEQUENCE OF SnaNodeAdminEntry
      MAX-ACCESS  not-accessible
     STATUS  current
     DESCRIPTION
          "This table contains objects which describe the
          configuration parameters for an SNA Node.  Link
          specific configuration objects are contained in
          a separate MIB module (e.g., SNA DLC MIB)
          corresponding to the link type.
          The table snaNodeAdminLinkTable contains objects
          which identify the relationship between node instances
          and link instances.

          The entries (i.e., rows) in this table can be created
          by either an Agent or a Management Station.
          The Management Station can do this through setting
          the appropriate value in the snaNodeAdminRowStatus.

          The snaNodeAdminRowStatus object describes the
          status of an entry and is used to change the status
          of an entry.  The entry is deleted
by an Agent based
          on the value of the snaNodeAdminRowStatus.

          The snaNodeAdminState object describes the desired
          operational state of a Node and is used to change the
          operational state of a Node.  For example, such
          information may be obtained from a configuration file.

          How an Agent or a Management Station obtains the
          initial value of each object at creation time is an
          implementation specific issue.

          For each entry in this table, there is a corresponding
          entry in the snaNodeOperTable.
          While the objects in this table describe the desired
          or configured operational values of the SNA Node, the
          actual runtime values are contained in
          snaNodeOperTable."
     ::= { snaNode 1 }

snaNodeAdminEntry OBJECT-TYPE
```

```
        SYNTAX  SnaNodeAdminEntry
        MAX-ACCESS  not-accessible
         STATUS  current
        DESCRIPTION
            "An entry contains the configuration parameters for
            one SNA Node instance. The objects in the entry
            have read-create access.
            An entry can be created, modified or deleted.  The
            object snaNodeAdminRowStatus is used (i.e., set) to
            create or delete a row entry."
        INDEX  { snaNodeAdminIndex }
        ::= { snaNodeAdminTable 1 }

SnaNodeAdminEntry ::= SEQUENCE {
        snaNodeAdminIndex
            Integer32,
        snaNodeAdminName
            DisplayString,
        snaNodeAdminType
            INTEGER,
        snaNodeAdminXidFormat
            INTEGER,
        snaNodeAdminBlockNum
            DisplayString,
        snaNodeAdminIdNum
            DisplayString,
        snaNodeAdminEnablingMethod
            INTEGER,
        snaNodeAdminLuTermDefault
            INTEGER,
        snaNodeAdminMaxLu

       Integer32,
        snaNodeAdminHostDescription
            DisplayString,
        snaNodeAdminStopMethod
            INTEGER,
        snaNodeAdminState
            INTEGER,
        snaNodeAdminRowStatus
            RowStatus
        }

snaNodeAdminIndex OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
```

"Index used to uniquely identify each Node instance.
If an Agent creates the entry, then it will assign
this number otherwise a Management Station
generates a random number when it reserves the
entry for creation."
::= { snaNodeAdminEntry 1 }

snaNodeAdminName OBJECT-TYPE
SYNTAX DisplayString (SIZE(0..17))
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The value indicates the desired name of the
Node for use during Node activation.

In Type 2.1 networks, this is a fully-qualified name,
meaning that the Node name is preceded by the NetId (if
present) with a period as the delimiter.

A write operation to this object will
not change the operational value reflected
in snaNodeOperName until the Node has
been re-activated (e.g., after the next initialization
of the SNA services)."
::= { snaNodeAdminEntry 2 }

snaNodeAdminType OBJECT-TYPE
SYNTAX INTEGER {
other(1),
pu10(2),
pu20(3),
t21len(4),
endNode(5),
networkNode(6)
}
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The value indicates the type of SNA Node.

A write operation to this object will
not change the operational value reflected

in snaNodeOperType until the Node has
been re-activated (e.g., after the next initialization
of the SNA services)."
::= { snaNodeAdminEntry 3 }

```
snaNodeAdminXidFormat OBJECT-TYPE
    SYNTAX  INTEGER  {
        format0(1),
        format1(2),
        format3(3)
        }
    MAX-ACCESS  read-create
    STATUS  current
    DESCRIPTION
        "The value indicates the type of XID format used for
        this Node.  Note that there is no format type 2.

        A write operation to this object will
        not change the operational value reflected
        in snaNodeOperAdminXidFormat until the Node has
        been re-activated (e.g., after the next initialization
        of the SNA services)."
    ::= { snaNodeAdminEntry 4 }

snaNodeAdminBlockNum OBJECT-TYPE
    SYNTAX  DisplayString (SIZE(3))
    MAX-ACCESS  read-create
    STATUS
 current
    DESCRIPTION
        "The value indicates the block number for this Node
        instance.  It is the first 3 hexadecimal digits of the
        SNA Node id.

        A write operation to this object will
        not change the operational value reflected
        in snaNodeOperBlockNum until the Node has
        been re-activated (e.g., after the next initialization
        of the SNA services)."
    ::= { snaNodeAdminEntry 5 }

snaNodeAdminIdNum OBJECT-TYPE
    SYNTAX  DisplayString (SIZE(5))
    MAX-ACCESS  read-create
    STATUS  current
    DESCRIPTION
        "The value indicates the ID number for this Node
        instance.  This is the last 5 hexadecimal digits of
        the SNA Node id.

        A write operation to this object will
        not change the operational value reflected
        in snaNodeOperIdNum until the Node has
```

```
            been re-activated (e.g., after the next initialization
            of the SNA services)."
        ::= { snaNodeAdminEntry 6 }

snaNodeAdminEnablingMethod OBJECT-TYPE
        SYNTAX  INTEGER {
            other (1),
            startup (2),
            demand (3),
            onlyMS (4)
            }
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "The value indicates how the Node should be
            activated for the first time.
            The values have the following meanings:

            other (1)  - may be used for proprietary methods
              not listed in this enumeration,
            startup (2) - at SNA services' initialization time
              (this is the default),
            demand (3) - only when LU is requested by application,
                    or
            onlyMS (4) - by a Management Station only.

            A  write operation
 to this object may immediately
            change the operational value reflected
            in snaNodeOperEnablingMethod depending
            on the Agent implementation.  If the Agent
            implementation accepts immediate changes, then the
            behavior of the Node changes immediately and not only
            after the next system startup of the SNA services.
            An immediate change may only apply when the
            current value 'demand (3)' is changed to 'onlyMS (4)'
            and vice versa."
        ::= { snaNodeAdminEntry 7 }

snaNodeAdminLuTermDefault OBJECT-TYPE
        SYNTAX  INTEGER {
            unbind (1),
            termself (2),
            rshutd (3),
            poweroff(4)
            }
        MAX-ACCESS  read-create
        STATUS  current
```

```
        DESCRIPTION
            "The value indicates the desired default method
            used to deactivate LUs for this Node
             For LU6.2s, 'unbind(1)' is the only valid value.

            unbind(1) -   terminate the LU-LU session by sending
                an SNA UNBIND request.
            termself(2) - terminate the LU-LU session by sending
                an SNA TERM-SELF (Terminate Self) request on
                the SSCP-LU session. The SSCP will inform the
                remote session LU partner to send an UNBIND
                request to terminate the session.
            rshutd(3) -   terminate the LU-LU session by sending
                an SNA RSHUTD (Request ShutDown) request to
                the remote session LU partner. The remote LU
                will then send an UNBIND request to terminate
                the session.
            poweroff(4) - terminate the LU-LU session by sending
                either an SNA LUSTAT (LU Status) request on
                the LU-LU
 session or an SNA NOTIFY request on
                the SSCP-LU session indicating that the LU has
                been powered off. Sending both is also
                acceptable. The result should be that the
                remote session LU partner will send an UNBIND
                to terminate the session.

            The default behavior indicated by the value of this
            object may be overridden for an LU instance. The
            override is performed by setting the snaLuAdminTerm
            object instance in the snaLuAdminTable to the desired
            value.

            A write operation to this object may immediately
            change the operational value reflected
            in snaNodeOperLuTermDefault depending
            on the Agent implementation."
        ::= { snaNodeAdminEntry 8 }

snaNodeAdminMaxLu OBJECT-TYPE
      SYNTAX  Integer32
      MAX-ACCESS  read-create
       STATUS  current
      DESCRIPTION
            "The maximum number of LUs that may be
            activated for this Node. For PU2.1, this object
            refers to the number of dependent LUs.
```

```
            A write operation to this object will
            not change the operational value reflected
            in snaNodeOperMaxLu until the Node has
            been re-activated (e.g., after the next initialization
            of the SNA services)."
        ::= { snaNodeAdminEntry 9 }

snaNodeAdminHostDescription OBJECT-TYPE
        SYNTAX  DisplayString (SIZE(0..128))
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "The value identifies the remote host associated
            with this Node.
            Since SSCP Id's may not be unique
            across hosts, the host description
            is required to uniquely identify the SSCP.
            This object
 is only applicable to PU2.0 type
            Nodes. If the remote host is unknown, then the
            value is the null string.

            A write operation to this object may immediately
            change the operational value reflected
            in snaNodeOperHostDescription depending
            on the Agent implementation."
        ::= { snaNodeAdminEntry 10 }

snaNodeAdminStopMethod OBJECT-TYPE
        SYNTAX  INTEGER {
            other (1),
            normal (2),
            immed (3),
            force (4)
            }
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "The value indicates the desired method to be used
            by the Agent to stop a Node (i.e., change the Node's
            operational state to inactive(1) ).

            The values have the following meaning:

            other (1) - used for proprietary
                 methods not listed in this enumeration.
            normal(2) - deactivate only when there is no more
                activity on this Node (i.e., all data flows
```

```
                have been completed and all sessions
                have been terminated).
            immed(3)  - deactivate immediately regardless of
                current activities on this Node. Wait for
                deactivation responses (from remote Node)
                before changing the Node state to inactive.
            force(4)  - deactivate immediately regardless of
                current activities on this Node. Do not wait
                for deactivation responses (from remote Node)
                before changing the Node state to inactive.

            A write operation to this object may immediately
            change the operational value reflected
            in snaNodeOperStopMethod
 depending
            on the Agent implementation."
        ::= { snaNodeAdminEntry 11 }

snaNodeAdminState OBJECT-TYPE
        SYNTAX  INTEGER {
            inactive (1),
            active (2)
            }
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "The value indicates the desired operational
             state of the SNA Node. This object is used
             by the Management Station to
             activate or deactivate the Node.

            If the current value in snaNodeOperState is
            'active (2)', then setting this object to
            'inactive (1)' will initiate the Node shutdown
            process using the method indicated
            by snaNodeOperStopMethod.

            If the current value in snaNodeOperState is
            'inactive (1)', then setting this object to
            'active (2)'
 will initiate the
            Node's activation.

            A Management Station can always set this object to
            'active (2)' irrespective of the value in the
            snaOperEnablingMethod."
        ::= { snaNodeAdminEntry 12 }
```

```
snaNodeAdminRowStatus OBJECT-TYPE
        SYNTAX  RowStatus
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
                "This object is used by a Management Station to
                create or delete the row entry in the
                snaNodeAdminTable following
                the RowStatus textual convention.

                Upon successful creation of
                the row, an Agent automatically creates a
                corresponding entry in the snaNodeOperTable with
                snaNodeOperState equal to 'inactive (1)'.

                Row deletion can be Management Station or Agent
                initiated:
                (a) The Management
 Station can set the value to
                'destroy (6)' only when the value of
                snaNodeOperState of this Node instance is
                'inactive (1)'. The Agent will then delete the rows
                corresponding to this Node instance from the
                snaNodeAdminTable and the snaNodeOperTable.
                (b) The Agent detects that a row is in the
                'notReady (3)' state for greater than a
                default period of 5 minutes.
                (c) All rows with the snaNodeAdminRowStatus object's
                value of 'notReady (3)' will be removed upon the
                next initialization of the SNA services."
        ::= { snaNodeAdminEntry 13 }


-- ****************************************************************
-- The following object is updated when there is a change to
-- the value of any object in the snaNodeAdminTable.
-- ****************************************************************

snaNodeAdminTableLastChange
 OBJECT-TYPE
        SYNTAX  TimeStamp
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The value indicates the timestamp
                (e.g., the Agent's sysUpTime value) of the last
                change made to any object in the snaNodeAdminTable,
                including row deletions/additions (e.g., changes to
```

```
            snaNodeAdminRowStatus values).

            This object can be used to reduce frequent
            retrievals of the snaNodeAdminTable by a Management
            Station. It is expected that a Management Station
            will periodically poll this object and compare its
            current value with the previous one. A difference
            indicates that some Node configuration information
            has been changed. Only then will the Management
            Station retrieve the entire table."
        ::= { snaNode
 2 }


-- ****************************************************************
-- The following table contains Node operational parameters.
-- ****************************************************************

snaNodeOperTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF SnaNodeOperEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
            "This table contains the dynamic parameters which
            have read-only access. These objects reflect the
            actual status of the Node. The entries in this
            table cannot be created or modified by a
            Management Station.
            This table augments the snaNodeAdminTable."
        ::= { snaNode 3 }

snaNodeOperEntry OBJECT-TYPE
        SYNTAX  SnaNodeOperEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
            "The entry contains parameters which describe the
            state of
 one Node. The entries are created by the
            Agent. They have read-only access."
        AUGMENTS   { snaNodeAdminEntry }
        ::= { snaNodeOperTable 1 }

SnaNodeOperEntry ::= SEQUENCE {
        snaNodeOperName
            DisplayString,
        snaNodeOperType
            INTEGER,
```

```
        snaNodeOperXidFormat
            INTEGER,
        snaNodeOperBlockNum
            DisplayString,
        snaNodeOperIdNum
            DisplayString,
        snaNodeOperEnablingMethod
            INTEGER,
        snaNodeOperLuTermDefault
            INTEGER,
        snaNodeOperMaxLu
            Integer32,
        snaNodeOperHostDescription
            DisplayString,
        snaNodeOperStopMethod
            INTEGER,
        snaNodeOperState
            INTEGER,
        snaNodeOperHostSscpId
            OCTET STRING,
        snaNodeOperStartTime
            TimeStamp,
        snaNodeOperLastStateChange
             TimeStamp,
        snaNodeOperActFailures
            Counter32,
        snaNodeOperActFailureReason
            INTEGER
        }

snaNodeOperName OBJECT-TYPE
        SYNTAX  DisplayString (SIZE(0..17))
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value identifies the current name of the Node.
            In Type 2.1 networks, this
            is a fully-qualified name, meaning that the Node name
            is preceded by the NetId (if present) with a period
            as the delimiter."
        ::= { snaNodeOperEntry 1 }

snaNodeOperType OBJECT-TYPE
        SYNTAX  INTEGER {
            other(1),
            pu10(2),
            pu20(3),
            t21LEN(4),
```

```
            endNode(5),
            networkNode(6)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
             "The value identifies the current type of the Node."
        ::= { snaNodeOperEntry 2 }

snaNodeOperXidFormat OBJECT-TYPE
        SYNTAX  INTEGER  {
            format0 (1),
            format1 (2),
            format3 (3)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value identifies the type of XID format currently
             used for this Node.
             Note that there is no format type 2."
        ::= { snaNodeOperEntry 3 }

snaNodeOperBlockNum OBJECT-TYPE
        SYNTAX DisplayString (SIZE(3))
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value identifies the block number for this Node
            instance. It is the first 3 hexadecimal digits
            of the SNA Node id."
        ::= { snaNodeOperEntry 4 }

snaNodeOperIdNum OBJECT-TYPE
        SYNTAX  DisplayString (SIZE(5))
         MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value identifies the ID number for this Node
            instance.  This is the last 5 hexadecimal digits of
            the SNA Node id."
        ::= { snaNodeOperEntry 5 }

snaNodeOperEnablingMethod OBJECT-TYPE
        SYNTAX  INTEGER {
            other (1),
            startup (2),
            demand (3),
```

```
            onlyMS (4)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value indicates how the Node is activated for
            the first time.
            The values have the following meanings:
              other (1)   - not at boot time, LU activation
                or by a Management Station;
              startup (2) - at SNA services' initialization
                time (this is the default),

    demand (3)  - only when LU is requested by
                application,
              onlyMS (4) - by a network Management Station
                only."
        ::= { snaNodeOperEntry 6 }

snaNodeOperLuTermDefault OBJECT-TYPE
        SYNTAX  INTEGER {
            unbind (1),
            termself (2),
            rshutd (3),
            poweroff (4)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value identifies the default method used to
            deactivate LUs for this Node.
            For LU6.2s, 'unbind(1)' is the only valid value.

            unbind(1) -   terminate the LU-LU session by sending
                an SNA UNBIND request.
            termself(2) - terminate the LU-LU session by sending
                an SNA TERM-SELF (Terminate Self) request on
                the SSCP-LU session. The SSCP will inform
 the
                remote session LU partner to send an UNBIND
                request to terminate the session.
            rshutd(3) -   terminate the LU-LU session by sending
                an SNA RSHUTD (Request ShutDown) request to
                the remote session LU partner. The remote LU
                will then send an UNBIND request to terminate
                the session.
            poweroff(4) - terminate the LU-LU session by sending
                either an SNA LUSTAT (LU Status) request on
```

```
                the LU-LU session or an SNA NOTIFY request on
                the SSCP-LU session indicating that the LU has
                been powered off. Sending both is also
                acceptable. The result should be that the
                remote session LU partner will send an UNBIND
                to terminate the session.

            This object
 describes the default behavior for this
            Node; however, it is possible that for a specific LU
            the behavior indicated by the snaLuOperTerm object is
            different."
        ::= { snaNodeOperEntry 7 }

snaNodeOperMaxLu OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This value identifies the current, maximum number
            of LUs that are activated for this Node. For PU2.1,
            this object refers to the number of dependent LUs."
        ::= { snaNodeOperEntry 8 }

snaNodeOperHostDescription OBJECT-TYPE
        SYNTAX  DisplayString (SIZE(0..128))
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This value identifies the remote host currently
             associated with this Node.
             Since SSCP Id's may not be unique
             across hosts, the
 host description
             is required to uniquely identify the SSCP."
        ::= { snaNodeOperEntry 9 }

snaNodeOperStopMethod OBJECT-TYPE
        SYNTAX  INTEGER {
            other (1),
            normal (2),
            immed (3),
            force (4)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This value identifies the current Node shutdown
```

method to be used by the Agent to stop the Node.
When the Agent changes the Node's state to 'inactive
(1)', the Agent must use the shutdown method
indicated by this object.

The values have the following meaning:

other (1) - proprietary method not listed in this
enumeration
normal(2) - deactivate only when there is no more
activity on this Node (i.e., all
data flows
have been completed and all sessions have
been terminated).
immed(3) - deactivate immediately regardless of
current activities on this Node. Wait for
deactivation responses (from remote Node)
before changing the Node state to inactive.
force(4) - deactivate immediately regardless of
current activities on this Node. Do not wait
for deactivation responses (from remote Node)
before changing the Node state to inactive.

Note that a write operation to
snaNodeAdminOperStopMethod may immediately change
the value of snaNodeOperStopMethod depending on
the Agent implementation."
::= { snaNodeOperEntry 10 }

snaNodeOperState OBJECT-TYPE
SYNTAX INTEGER {

inactive (1),
active (2),
waiting (3),
stopping (4)
}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The current state of the Node.
The values have the following meanings:
inactive (1), a row representing the Node has
been created in the AdminTable
and, the Node is ready for activation -or-
an active Node has been stopped -or-
a waiting Node has returned to the inactive
state.

```
                waiting (3), a request to have the Node activated
                   has been issued, and the Node is pending
                   activation.
                active (2), the Node is ready and operating.
                stopping (4), the request to stop the Node has
                   been
 issued while the StopMethod normal
                   or immediate is used."
        ::= { snaNodeOperEntry 11 }

snaNodeOperHostSscpId OBJECT-TYPE
        SYNTAX  OCTET STRING (SIZE(0..6))
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
              "This value identifies the current SSCP Id
               associated with the Node. This object is only
               applicable to PU 2.0s. If the Node
               is not a PU 2.0 type, then this object contains a
               zero length string."
        ::= { snaNodeOperEntry 12 }

snaNodeOperStartTime OBJECT-TYPE
        SYNTAX  TimeStamp
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
              "The timestamp (e.g, the Agent's sysUpTime value)
               at the Node activation."
        ::= { snaNodeOperEntry 13 }

snaNodeOperLastStateChange OBJECT-TYPE
        SYNTAX  TimeStamp
        MAX-ACCESS  read-only

        STATUS  current
        DESCRIPTION
              "The timestamp (e.g., the Agent's sysUpTime value)
              at the last state change of the Node."
        ::= { snaNodeOperEntry 14 }

snaNodeOperActFailures OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
              "This value identifies the number of failed Node
              activation attempts."
```

```
        ::= { snaNodeOperEntry 15 }

snaNodeOperActFailureReason OBJECT-TYPE
        SYNTAX  INTEGER {
                other (1),
                linkFailure (2),
                noResources (3),
                badConfiguration (4),
                internalError (5)
                }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The value indicates the reason for the activation
                failure.  The value 'other (1)' indicates a reason
                not
 listed in the enumeration. This object
                will be sent in the trap snaNodeActFailTrap."
        ::= { snaNodeOperEntry 16 }


-- ****************************************************************
-- The following object is updated when there is a change to
-- the value of snaNodeOperState in any row or a row is
-- added/deleted from the snaNodeOperTable via the snaNodeAdminTable.
-- ****************************************************************

snaNodeOperTableLastChange OBJECT-TYPE
        SYNTAX  TimeStamp
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The timestamp (e.g., the Agent's sysUpTime value)
                at the last change made to any object in the
                snaNodeOperTable, including row deletions/additions
                made as a result of changes to the
                snaNodeAdminRowStatus object.

                This object can be used to reduce frequent
                retrievals
 of the snaNodeOperTable by a Management
                Station. It is expected that a Management Station
                will periodically poll this object and compare its
                current value with the previous one. A difference
                indicates that some Node operational information
                has been changed. Only then will the Management
                Station retrieve the entire table."
        ::= { snaNode 4 }
```

```
-- ****************************************************************
-- The following table contains PU 2.0 statistics dynamic parameters.
-- ****************************************************************

snaPu20StatsTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF SnaPu20StatsEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
                "This table contains the dynamic parameters which
                have read-only access. The entries in this table
                correspond
 to PU 2.0 entries in the snaNodeOperTable
                and cannot be created by a Management Station."
        ::= { snaNode 5 }

snaPu20StatsEntry OBJECT-TYPE
        SYNTAX  SnaPu20StatsEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
                "The entry contains parameters which describe the
                statistics for one PU 2.0. They have read-only
                access.
                The counters represent traffic for all kinds
                of sessions: LU-LU, SSCP-PU, SSCP-LU.

                Each Node of PU Type 2.0 from the snaNodeAdminTable
                has one entry in this table and the index used
                here has the same value as snaNodeAdminIndex of
                that PU.  The entry is created by the Agent."
        INDEX   { snaNodeAdminIndex }
        ::= { snaPu20StatsTable 1 }

SnaPu20StatsEntry ::= SEQUENCE {
        snaPu20StatsSentBytes
                Counter32,
         snaPu20StatsReceivedBytes
                Counter32,
        snaPu20StatsSentPius
                Counter32,
        snaPu20StatsReceivedPius
                Counter32,
        snaPu20StatsSentNegativeResps
                Counter32,
        snaPu20StatsReceivedNegativeResps
```

```
            Counter32,
        snaPu20StatsActLus
            Gauge32,
        snaPu20StatsInActLus
            Gauge32,
        snaPu20StatsBindLus
            Gauge32
        }

snaPu20StatsSentBytes OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of bytes sent by this Node."
        ::= { snaPu20StatsEntry 1 }

snaPu20StatsReceivedBytes OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of bytes received by this Node."
        ::= { snaPu20StatsEntry
 2 }

snaPu20StatsSentPius OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of PIUs sent by this Node."
        ::= { snaPu20StatsEntry 3 }

snaPu20StatsReceivedPius OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of PIUs received by this Node."
        ::= { snaPu20StatsEntry 4 }

snaPu20StatsSentNegativeResps OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of negative responses sent
```

```
            by this Node."
        ::= { snaPu20StatsEntry 5 }

snaPu20StatsReceivedNegativeResps OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of negative responses received

       by this Node."
        ::= { snaPu20StatsEntry 6 }

snaPu20StatsActLus OBJECT-TYPE
        SYNTAX  Gauge32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of LUs on this PU which have
            received and responded to ACTLU from the host."
        ::= { snaPu20StatsEntry 7 }

snaPu20StatsInActLus OBJECT-TYPE
        SYNTAX  Gauge32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of LUs on this PU which have
            not received an ACTLU from the host.  This is
            possible if the number of configured LUs exceeds
            that on the host."
        ::= { snaPu20StatsEntry 8 }

snaPu20StatsBindLus OBJECT-TYPE
        SYNTAX  Gauge32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of LUs on this PU which have
            received and acknowledged
 a BIND request from the
            host."
        ::= { snaPu20StatsEntry 9 }

-- ****************************************************************
-- The following table contains the association between Nodes and
-- link identifiers.
-- It is used for configuration purposes.
```

```
-- ****************************************************************

snaNodeLinkAdminTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF SnaNodeLinkAdminEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
                "This table contains the references to link
                specific tables. If a Node is configured for
                multiple links, then the Node will have
                multiple entries in this table.
                The entries in this table can be generated
                initially, after initialization of SNA service,
                by the Agent which uses information from
                Node configuration file.

             Subsequent modifications of parameters,
                creation of new Nodes link entries and deletion
                of entries is possible.
                The modification to this table can be
                saved in the Node configuration file for the
                next initialization of SNA service, but the mechanism
                for this function is not defined here."
        ::= { snaNode 6 }

snaNodeLinkAdminEntry OBJECT-TYPE
        SYNTAX  SnaNodeLinkAdminEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
                "Entry contains the configuration information that
                associates a Node instance to one link instance.
                The objects in the entry have read-create access.
                Entry can be created, modified or deleted.
                The object snaNodeLinkAdminRowStatus is used (set)
                to create or delete an entry.
                The object
     snaNodeLinkAdminSpecific can be set
                later, after the entry has been created."
        INDEX   { snaNodeAdminIndex,
                  snaNodeLinkAdminIndex }
        ::= { snaNodeLinkAdminTable 1 }

SnaNodeLinkAdminEntry ::= SEQUENCE {
        snaNodeLinkAdminIndex
                Integer32,
        snaNodeLinkAdminSpecific
                InstancePointer,
```

```
        snaNodeLinkAdminMaxPiu
            Integer32,
        snaNodeLinkAdminRowStatus
            RowStatus
        }

snaNodeLinkAdminIndex OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
            "This value is used to index the instances of objects.
            If an Agent creates the entry, then it will assign
            this number otherwise a Management Station
            generates a random number when it reserves the
            entry for creation."
        ::=
 { snaNodeLinkAdminEntry 1 }

snaNodeLinkAdminSpecific OBJECT-TYPE
        SYNTAX  InstancePointer
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "This value points to the row in the table
            containing information on the link instance.
            (e.g., the sdlcLSAdminTable of
            the SNA DLC MIB module)."
        ::= { snaNodeLinkAdminEntry 2 }

snaNodeLinkAdminMaxPiu OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "This value identifies the maximum number of octets
            that can be exchanged by this Node in one
            Path Information Unit (PIU)."
        ::= { snaNodeLinkAdminEntry 3 }

snaNodeLinkAdminRowStatus OBJECT-TYPE
        SYNTAX  RowStatus
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "This object is used by a
 Management Station to
            create or delete the row entry in the
```

```
            snaNodeLinkAdminTable.
            To activate a row, a Management Station sets the value
            to 'active (1)' or 'notReady (3)'.  Upon successful
            creation of the row, the Agent automatically creates
            a corresponding entry in the snaNodeLinkOperTable.

            Row deletion can be Management Station or Agent
            initiated:
            (a) The Management Station can set the value to
            'destroy (6)' only when the value of
            snaNodeLinkOperState of this Link
            instance is 'inactive (1)'. The Agent will then
            delete the row corresponding to this Link
            instance from snaNodeLinkOperTable and
            from snaNodeLinkAdminTable.
            (b) The Agent detects that a row is in the
            'notReady (3)' state for greater than a

  default period of 5 minutes.
            (c) The Agent will not include a row with RowStatus=
            'notReady (3)', after SNA system re-initialization
             (e.g., reboot)."
        ::= { snaNodeLinkAdminEntry 4 }


-- ****************************************************************
-- The following object is updated when there is a change to
-- the value of any object in the snaNodeLinkAdminTable.
-- ****************************************************************

snaNodeLinkAdminTableLastChange OBJECT-TYPE
        SYNTAX  TimeStamp
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The timestamp (e.g., the Agent's sysUpTime value)
            at the last
            change made to any object in the snaNodeLinkAdminTable,
            including row deletions/additions (i.e., changes
            to the snaNodeLinkAdminRowStatus object).

            This object can be used to reduce
 frequent
            retrievals of the snaNodeLinkAdminTable by a
            Management Station. It is expected that a
            Management Station will periodically poll this
            object and compare its current value with the
            previous one.
```

```
            A difference indicates that some Node operational
            information has been changed. Only then will the
            Management Station retrieve the entire table."
        ::= { snaNode 7 }


-- ****************************************************************
-- The following table contains the association between
-- Nodes and link identifiers.
-- It provides the current status.
-- ****************************************************************

snaNodeLinkOperTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF SnaNodeLinkOperEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
            "This table contains all references
 to link
            specific tables for operational parameters.
            If a Node is configured for multiple links,
            then the Node will have multiple entries in
            this table. This table augments the
            snaNodeLinkAdminTable."
        ::= { snaNode 8 }

snaNodeLinkOperEntry OBJECT-TYPE
        SYNTAX  SnaNodeLinkOperEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
            "Entry contains all current parameters for one
            Node link. The objects in the entry have
            read-only access."
        AUGMENTS   { snaNodeLinkAdminEntry }
        ::= { snaNodeLinkOperTable 1 }

SnaNodeLinkOperEntry ::= SEQUENCE {
        snaNodeLinkOperSpecific
            InstancePointer,
        snaNodeLinkOperMaxPiu
            Integer32
        }

snaNodeLinkOperSpecific OBJECT-TYPE
        SYNTAX  InstancePointer
        MAX-ACCESS
```

```
 read-only
        STATUS  current
        DESCRIPTION
                "This value points to the row in the table
                containing information on the link instance.
                (e.g., the sdlcLSOperTable of
                the SNA DLC MIB module)."
        ::= { snaNodeLinkOperEntry 1 }

snaNodeLinkOperMaxPiu OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "Maximum number of octets that can
                be exchanged by this Node in one Path
                Information Unit (PIU)."
        ::= { snaNodeLinkOperEntry 2 }


-- ****************************************************************
-- The following object is updated when a row is added/deleted
-- from the snaNodeLinkOperTable.
-- ****************************************************************

snaNodeLinkOperTableLastChange OBJECT-TYPE
        SYNTAX  TimeStamp
        MAX-ACCESS  read-only

 STATUS  current
        DESCRIPTION
                "The timestamp of the last
                change made to any object in the snaNodeLinkOperTable,
                including row deletions/additions.

                This object can be used to reduce frequent
                retrievals of the snaNodeLinkOperTable by a
                Management Station. It is expected that a
                Management Station will periodically poll this
                object and compare its current value with the
                previous one.
                A difference indicates that some Node operational
                information has been changed. Only then will the
                Management Station retrieve the entire table."
        ::= { snaNode 9 }

-- ****************************************************************
-- Traps
```

```
-- ****************************************************************

snaNodeTraps OBJECT IDENTIFIER ::= { snaNode 10 }

snaNodeStateChangeTrap
 NOTIFICATION-TYPE
       OBJECTS  { snaNodeOperName,
             snaNodeOperState }
       STATUS  current
       DESCRIPTION
             "This trap indicates that the operational state
             (i.e., value of the snaNodeOperState object) of a Node
              has changed. The following variables are returned:
               snaNodeOperName - current name of the Node,
                 with the instance identifying the Node; and,
               snaNodeOperState - current state after
                 the change."
       ::= { snaNodeTraps 1 }

snaNodeActFailTrap NOTIFICATION-TYPE
       OBJECTS  { snaNodeOperName,
             snaNodeOperState,
             snaNodeOperActFailureReason }
       STATUS  current
       DESCRIPTION
             "This trap indicates a Node activation failure.
             The value of snaNodeOperState indicates the current
             state after the activation attempt.
              The value of snaNodeOperActFailureReason indicates
             the failure reason."
       ::=  { snaNodeTraps 2 }


-- ****************************************************************
-- snaLu group
--
-- It contains Managed Objects related to LUs in general and some
-- specific for LUs of type 0, 1, 2, 3.
-- ****************************************************************


-- ****************************************************************
-- The following table contains LU configuration parameters.
-- ****************************************************************

snaLuAdminTable OBJECT-TYPE
     SYNTAX  SEQUENCE OF SnaLuAdminEntry
     MAX-ACCESS  not-accessible
```

```
        STATUS  current
        DESCRIPTION
                "This table contains LU configuration information.
                The rows in this table can be created and deleted
                by a Management Station.
                Only objects which are common to all types of LUs

                are included in this table."
        ::= { snaLu 1 }

snaLuAdminEntry OBJECT-TYPE
        SYNTAX  SnaLuAdminEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
                "Contains configuration variables for an LU."
        INDEX   { snaNodeAdminIndex, snaLuAdminLuIndex }
        ::= { snaLuAdminTable 1 }

SnaLuAdminEntry ::= SEQUENCE {
        snaLuAdminLuIndex
                Integer32,
        snaLuAdminName
                DisplayString,
        snaLuAdminSnaName
                DisplayString,
        snaLuAdminType
                INTEGER,
        snaLuAdminDepType
                INTEGER,
        snaLuAdminLocalAddress
                OCTET STRING,
        snaLuAdminDisplayModel
                INTEGER,
        snaLuAdminTerm
                INTEGER,
        snaLuAdminRowStatus
                RowStatus
        }

snaLuAdminLuIndex OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  not-accessible
        STATUS  current
         DESCRIPTION
                "This value identifies the unique index for an
                 LU instance within a Node."
        ::= { snaLuAdminEntry 1 }
```

```
snaLuAdminName OBJECT-TYPE
    SYNTAX  DisplayString (SIZE(0..48))
    MAX-ACCESS  read-create
    STATUS  current
    DESCRIPTION
        "This value identifies the user configurable
        name for this LU. If a name is not assigned to the LU,
        then this object contains a zero length string.

        A write operation to this object will
        not change the operational value reflected
        in snaLuOperName until the Node has
        been re-activated (e.g., after the next
        initialization of the SNA services)."
    ::= { snaLuAdminEntry 2 }

snaLuAdminSnaName OBJECT-TYPE
    SYNTAX  DisplayString (SIZE(1..17))
    MAX-ACCESS  read-create
    STATUS  current
    DESCRIPTION
        "This value identifies
 the SNA LU name
        used in exchange of SNA data.

        A write operation to this object will
        not change the operational value reflected
        in snaLuOperSnaName until the Node has
        been re-activated (e.g., after the next
        initialization of the SNA services)."
    ::= { snaLuAdminEntry 3 }

snaLuAdminType OBJECT-TYPE
    SYNTAX  INTEGER {
        other(1),
        lu0(2),
        lu1(3),
        lu2(4),
        lu3(5),
        lu4(6),
        lu62(7),
        lu7(8)
        }
    MAX-ACCESS  read-create
    STATUS  current
    DESCRIPTION
        "This value identifies the LU type.
```

```
            A write operation to this object will
            not change the operational value reflected
            in snaLuOperAdminType until the Node has
            been re-activated (e.g., after the next
             initialization of the SNA services)."
        ::= { snaLuAdminEntry 4 }

    snaLuAdminDepType OBJECT-TYPE
        SYNTAX  INTEGER {
            dependent(1),
            independent(2)
            }
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "This value identifies whether the LU is
            dependent or independent.

            A write operation to this object will
            not change the operational value reflected
            in snaLuOperDepType until the Node has
            been re-activated (e.g., after the next
            initialization of the SNA services)."
        ::= { snaLuAdminEntry 5 }

    snaLuAdminLocalAddress OBJECT-TYPE
        SYNTAX  OCTET STRING (SIZE(1))
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "The local address for this LU is a byte with a value
            ranging from 0 to 254.For dependent LUs, this value
             ranges from 1 to 254 and for independent LUs this
            value is always 0.

            A write operation to this object will not change the
            operational value reflected in snaLuOperLocalAddress
            until the Node has been re-activated (e.g., after the
            next initialization of the SNA services)."
        ::= { snaLuAdminEntry 6 }

    snaLuAdminDisplayModel OBJECT-TYPE
        SYNTAX  INTEGER {
            invalid(1),
            model2A(2),
            model2B(3),
            model3A(4),
```

```
            model3B(5),
            model4A(6),
            model4B(7),
            model5A(8),
            model5B(9),
            dynamic(10)
            }
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "The value of this object identifies the  model type
            and screen size of the terminal connected to the host.
            This
    is only valid for LU Type 2.  The values have
            the following meaning:

            model2A(2) - Model 2 (24 rows x 80 cols) with base
                attributes
            model2B(3) - Model 2 (24 rows x 80 cols) with
                extended attributes
            model3A(4) - Model 3 (32 rows x 80 cols) with base
                attributes
            model3B(5) - Model 3 (32 rows x 80 cols) with extended
                attributes
            model4A(6) - Model 4 (43 rows x 80 cols) with base
                attributes
            model4B(7) - Model 4 (43 rows x 80 cols) with extended
                                attributes
            model5A(8) - Model 5 (27 rows x 132 cols) with base
                attributes
            model5B(9) - Model 5 (27 rows x 132 cols) with
                extended attributes
            dynamic(10) - Screen size determine with
    BIND and Read
                                Partition Query.

            In case this LU is not Type 2, then this object
            should contain the invalid(1) value."
        ::= { snaLuAdminEntry 7 }

    snaLuAdminTerm OBJECT-TYPE
        SYNTAX  INTEGER {
            unbind (1),
            termself (2),
            rshutd (3),
            poweroff (4)
            }
        MAX-ACCESS  read-create
```

```
        STATUS  current
        DESCRIPTION
                "This value identifies the desired method for
                deactivation of this LU. This value overrides the
                default method (snaNodeOperLuTermDefault) for this
                Node.  For LU 6.2, only the value 'unbind (1)'
                applies.

                unbind(1) -   terminate the LU-LU session by sending
                        an SNA UNBIND request.
                termself(2) - terminate the LU-LU session by sending
                        an SNA TERM-SELF
    (Terminate Self) request on
                        the SSCP-LU session. The SSCP will inform the
                        remote session LU partner to send an UNBIND
                        request to terminate the session.
                rshutd(3) -   terminate the LU-LU session by sending
                        an SNA RSHUTD (Request ShutDown) request to
                        the remote session LU partner. The remote LU
                        will then send an UNBIND request to terminate
                        the session.
                poweroff(4) - terminate the LU-LU session by sending
                        either an SNA LUSTAT (LU Status) request on
                        the LU-LU session or an SNA NOTIFY request on
                        the SSCP-LU session indicating that the LU has
                        been powered off. Sending both is also
                        acceptable. The result should be that the
                        remote session LU partner
     will send an UNBIND
                        to terminate the session.

                A write operation to this object may immediately
                change the operational value reflected
                in snaLuOperTerm depending
                on the Agent implementation."
        ::= { snaLuAdminEntry 8 }

    snaLuAdminRowStatus OBJECT-TYPE
        SYNTAX  RowStatus
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
                "This object is used by a Management Station to
                create or delete the row entry in the
                snaLuAdminTable.
                To activate a row, the Management Station sets the
                value to 'active (1)' or 'notReady (3)'.
                Upon successful creation of the row, the Agent
```

automatically creates a corresponding entry in the
snaLuOperTable with snaLuOperState equal to
'inactive (1)'.
Row deletion can be Management Station
or Agent
initiated:
(a) The Management Station can set the value to
'destroy (6)' only when the value of snaLuOperState
of this LU instance is 'inactive (1)'. The Agent will
then delete the row corresponding to this LU
instance from snaLuAdminTable and
from snaLuOperTable.
(b) The Agent detects that a row is in the
'notReady (3)' state for greater than a
default period of 5 minutes.
(c) The Agent will not create a row with RowStatus
equal to 'notReady (3)', after SNA system
re-initialization (e.g., reboot)."
::= { snaLuAdminEntry 9 }

-- **
-- The following table contains LU state dynamic parameters.
-- **

snaLuOperTable OBJECT-TYPE
SYNTAX
SEQUENCE OF SnaLuOperEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"This table contains dynamic runtime information and
control variables relating to LUs.
Only objects which are common to all types of LUs are
included in this table. This table augments the
snaLuAdminTable."
::= { snaLu 2 }

snaLuOperEntry OBJECT-TYPE
SYNTAX SnaLuOperEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Contains objects reflecting current information
for an LU.
Each entry is created by the Agent. All entries
have read-only access."
AUGMENTS { snaLuAdminEntry }

```
    ::= { snaLuOperTable 1 }

SnaLuOperEntry ::= SEQUENCE {
    snaLuOperName
        DisplayString,
    snaLuOperSnaName
        DisplayString,
    snaLuOperType

      INTEGER,
    snaLuOperDepType
        INTEGER,
    snaLuOperLocalAddress
        OCTET STRING,
    snaLuOperDisplayModel
        INTEGER,
    snaLuOperTerm
        INTEGER,
    snaLuOperState
        INTEGER,
    snaLuOperSessnCount
        Gauge32
    }

snaLuOperName OBJECT-TYPE
    SYNTAX  DisplayString (SIZE(0..48))
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "User configurable name for this LU. If a name
        is not assigned, then this object contains a
        zero length string."
    ::= { snaLuOperEntry 1 }

snaLuOperSnaName OBJECT-TYPE
    SYNTAX  DisplayString (SIZE(1..17))
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The value identifies the current SNA LU name."
    ::= { snaLuOperEntry 2 }

snaLuOperType OBJECT-TYPE
    SYNTAX  INTEGER {
        other(1),
         lu0(2),
        lu1(3),
        lu2(4),
```

```
            lu3(5),
            lu4(6),
            lu62(7),
            lu7(8)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value identifies the current LU type."
        ::= { snaLuOperEntry 3 }

    snaLuOperDepType OBJECT-TYPE
        SYNTAX  INTEGER {
            dependent(1),
            independent(2)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value identifies whether the LU is currently
             dependent or independent.

            A write operation to this object will
            not change the operational value reflected
            in snaLuOperDepType until the Node has
            been re-activated (e.g., after the next
            initialization of the SNA services)."
        ::= { snaLuOperEntry 4 }

    snaLuOperLocalAddress
     OBJECT-TYPE
        SYNTAX  OCTET STRING (SIZE(1))
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The local address for this LU is a byte with a value
            ranging from 0 to 254. For dependent LUs, this value
            ranges from 1 to 254; for independent LUs this value
            is always 0.

            A write operation to this object will
            not change the operational value reflected
            in snaLuOperLocalAddress until the Node has
            been re-activated (e.g., after the next
            initialization of the SNA services)."
        ::= { snaLuOperEntry 5 }

    snaLuOperDisplayModel OBJECT-TYPE
```

```
        SYNTAX  INTEGER {
                invalid(1),
                model2A(2),
                model2B(3),
                model3A(4),
                model3B(5),
                model4A(6),
                model4B(7),
                model5A(8),
                model5B(9),
                 dynamic(10)
                }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The screen model type of the terminal connected to
                the host. If this LU is not Type 2, then this
                object should contain the 'invalid(1)' value."
        ::= { snaLuOperEntry 6 }

snaLuOperTerm OBJECT-TYPE
        SYNTAX  INTEGER {
                unbind (1),
                termself (2),
                rshutd (3),
                poweroff (4)
                }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The value identifies the current method for
                deactivation of this LU. This value overrides the
                default method (snaNodeOperLuTermDefault) for this
                Node.  For LU 6.2, only the value 'unbind (1)'
                applies.

                unbind(1) -   terminate the LU-LU session by sending
                        an SNA UNBIND request.
                 termself(2) - terminate the LU-LU session by sending
                        an SNA TERM-SELF (Terminate Self) request on
                        the SSCP-LU session. The SSCP will inform the
                        remote session LU partner to send an UNBIND
                        request to terminate the session.
                rshutd(3) -   terminate the LU-LU session by sending
                        an SNA RSHUTD (Request ShutDown) request to
                        the remote session LU partner. The remote LU
                        will then send an UNBIND request to terminate
                        the session.
```

```
            poweroff(4) - terminate the LU-LU session by sending
                either an SNA LUSTAT (LU Status) request on
                the LU-LU session or an SNA NOTIFY request on
                the SSCP-LU session indicating that the LU has
                been powered off. Sending both is also

              acceptable. The result should be that the
                remote session LU partner will send an UNBIND
                to terminate the session."
        ::= { snaLuOperEntry 7 }

    snaLuOperState OBJECT-TYPE
        SYNTAX  INTEGER {
            inactive (1),
            active (2)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value identifies the current operational state of
            this LU.
            It has different meanings for dependent and independent
            LUs.
            For dependent LUs the values indicate the following:
              inactive (1) - LU didn't receive ACTLU, or
                it received DACTLU, or received ACTLU and sent
                negative response.
              active (2) - LU received ACTLU and acknowledged
                positively.

            For independent LUs the values
     indicate the following:
              active (2) - the LU is defined and is able to send
                and receive BIND.
              inactive (1) - the LU has a session count equal
                to 0."
        ::= { snaLuOperEntry 8 }

    snaLuOperSessnCount OBJECT-TYPE
        SYNTAX  Gauge32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of currently active LU-LU sessions of
            this LU.
            For the independent LU, if this object has value 0,
            it indicates that LU is inactive."
        ::= { snaLuOperEntry 9 }
```

```
-- ****************************************************************
-- The following table contains LU session status parameters.
-- ****************************************************************

snaLuSessnTable OBJECT-TYPE
      SYNTAX  SEQUENCE OF SnaLuSessnEntry
      MAX-ACCESS  not-accessible
      STATUS  current
      DESCRIPTION

     "This is a table containing objects which describe the
           operational state of LU sessions.  Only objects which
           are common to all types of LU sessions are included
           in this table.

           When a session's snaLuSessnOperState value changes to
           'pendingBind (2)', then the corresponding entry
           in the session table is created by the Agent.

           When the session's snaLuSessnOperState value changes to
            'unbound (1)',  then the session will be removed from
           the session table by the Agent."
      ::= { snaLu 3 }

snaLuSessnEntry OBJECT-TYPE
      SYNTAX  SnaLuSessnEntry
      MAX-ACCESS  not-accessible
      STATUS  current
      DESCRIPTION
           "An entry contains dynamic parameters for an LU-LU
           session.
           The indices identify the Node, local LU, and remote LU
           for this session."
      INDEX   { snaNodeAdminIndex,
                 snaLuAdminLuIndex,
                snaLuSessnRluIndex,
                snaLuSessnIndex }
      ::= { snaLuSessnTable 1 }

SnaLuSessnEntry ::= SEQUENCE {
      snaLuSessnRluIndex
           Integer32,
      snaLuSessnIndex
           Integer32,
      snaLuSessnLocalApplName
           DisplayString,
```

```
        snaLuSessnRemoteLuName
            DisplayString,
        snaLuSessnMaxSndRuSize
            INTEGER,
        snaLuSessnMaxRcvRuSize
            INTEGER,
        snaLuSessnSndPacingSize
            INTEGER,
        snaLuSessnRcvPacingSize
            INTEGER,
        snaLuSessnActiveTime
            TimeStamp,
        snaLuSessnAdminState
            INTEGER,
        snaLuSessnOperState
            INTEGER,
        snaLuSessnSenseData
            OCTET STRING,
        snaLuSessnTerminationRu
            INTEGER,
        snaLuSessnUnbindType
            OCTET STRING,
        snaLuSessnLinkIndex
             Integer32
        }

    snaLuSessnRluIndex OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This value may be used to identify information about
            the session partner LU in a table of information about
            remote LUs.  Such a table is not defined in this
            document.  If a table of remote LU information is not
            implemented, or if the table is implemented but it does
            not contain information about the partner LU for a
            particular session (as for dependent LU-LU sessions)
            then this object will have a value of zero."
        ::= { snaLuSessnEntry 1 }

    snaLuSessnIndex OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This value identifies the unique index of the session.
            It is recommended
```

```
 that an Agent should not reuse the
            index of a deactivated session for a significant
            period of time (e.g., one week)."
      ::= { snaLuSessnEntry 2 }

snaLuSessnLocalApplName OBJECT-TYPE
      SYNTAX  DisplayString (SIZE(0..48))
      MAX-ACCESS  read-only
      STATUS  current
      DESCRIPTION
            "The name of the local application using this LU.
            If the local application is unknown, then this object
            contains a zero length string."
      ::= { snaLuSessnEntry 3 }

snaLuSessnRemoteLuName OBJECT-TYPE
      SYNTAX  DisplayString (SIZE(0..17))
      MAX-ACCESS  read-only
      STATUS  current
      DESCRIPTION
            "For dependent LUs which are indicated by the
            snaLuOperDepType object containing the value
            'dependent (1)', this object contains the Primary
            LU (PLU) name.  For independent LUs,
            this object contains the fully-qualified
 remote LU
            name of this 6.2 session.
            A fully qualified name is an SNA NAU entity name
            preceded by the NetId and a period as the delimiter."
      ::= { snaLuSessnEntry 4 }

snaLuSessnMaxSndRuSize OBJECT-TYPE
      SYNTAX  INTEGER (1..8192)
      MAX-ACCESS  read-only
      STATUS  current
      DESCRIPTION
            "The maximum RU size used on this session for sending
            RUs."
      ::= { snaLuSessnEntry 5 }

snaLuSessnMaxRcvRuSize OBJECT-TYPE
      SYNTAX  INTEGER (1..8192)
      MAX-ACCESS  read-only
      STATUS  current
      DESCRIPTION
            "The maximum RU size used on this session for
            receiving RUs."
      ::= { snaLuSessnEntry 6 }
```

```
snaLuSessnSndPacingSize OBJECT-TYPE
    SYNTAX  INTEGER (1..63)
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The size of the send pacing window on this session."
    ::= {
 snaLuSessnEntry 7 }

snaLuSessnRcvPacingSize OBJECT-TYPE
    SYNTAX  INTEGER (1..63)
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The size of the receive pacing window on this
        session."
    ::= { snaLuSessnEntry 8 }

snaLuSessnActiveTime OBJECT-TYPE
    SYNTAX  TimeStamp
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The timestamp (e.g., the Agent's sysUpTime value)
        when this session becomes active."
    ::= { snaLuSessnEntry 9 }

snaLuSessnAdminState OBJECT-TYPE
    SYNTAX  INTEGER {
        unbound (1),
        bound (3)
        }
    MAX-ACCESS  read-write
    STATUS  current
    DESCRIPTION
        "The value indicates the desired operational state of
        the session. This object is used to
        change the operational state of the session.
        A Management Station
 can only change the operational
        state of the session to 'unbound (1)'.

        Session deactivation:
          If a session is in the operational state
          'bound (3)' then setting the value of this
          object to 'unbound (1)' will initiate the
          session shutdown.
```

```
            If a session is in the operational state
            'pendingBind (2)' then setting the value of this
            object to 'unbound (1)' will initiate the session
            shutdown.
            If a session is in the operational state
            'pendingUnbind (4)' for an abnormally long period
            of time (e.g., three minutes) then setting the value
            of this object to 'unbound (1)' will change the
            session operational state to 'unbound (1)'.

            Note: for dependent LUs, deactivating the session is
            the same as deactivating
 the LU."
    ::= { snaLuSessnEntry 10 }

snaLuSessnOperState OBJECT-TYPE
    SYNTAX  INTEGER {
            unbound (1),
            pendingBind (2),
            bound (3),
            pendingUnbind (4)
            }
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "The value indicates the current operational state of
            the session.

             'unbound (1)' - session has been  unbound;
                 in this state it will be removed from the
                 session table by the Agent.

             'pendingBind (2)' - this state has different
                 meanings for dependent and independent LUs;
                 for dependent LU - waiting for BIND from
                 the host, for independent LU - waiting for
                 BIND response.  When a session enters this
                 state, the corresponding entry in the

              session table is created by the Agent.

             'bound (3)' - session has been successfully bound.

             'pendingUnbind (4)' - session enters this state
                 when an UNBIND is sent and before the
                 rsp(UNBIND) is received."
    ::= { snaLuSessnEntry 11 }
```

```
snaLuSessnSenseData OBJECT-TYPE
    SYNTAX  OCTET STRING (SIZE(0..8))
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The value identifies the sense code when there is
        a BIND failure. It is taken from the negative BIND
        response or UNBIND request.
        This is displayed as 8 hexadecimal digits."
    ::= { snaLuSessnEntry 12 }

snaLuSessnTerminationRu OBJECT-TYPE
    SYNTAX INTEGER {
        other (1),
        bindFailure (2),
        unbind (3)
        }
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
         "The value identifies the SNA RU that terminated the
        session.
        If the session is not in the unbound state, this object
        has a value of  'other (1)'."
    ::= { snaLuSessnEntry 13 }


snaLuSessnUnbindType OBJECT-TYPE
    SYNTAX  OCTET STRING (SIZE(0..1))
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "If the session is in the unbound state, and it was
        terminated by an UNBIND, then this object contains
        the UNBIND type value (byte 1 of the UNBIND RU);
        otherwise the string is null."
    ::= { snaLuSessnEntry 14 }

snaLuSessnLinkIndex OBJECT-TYPE
    SYNTAX  Integer32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "This value identifies the link over which the session
        passes.  It is an index into snaNodeLinkAdminTable.
        If the index value is not known,
```

```
 the value of this
            object shall be zero."
      ::= { snaLuSessnEntry 15 }


-- ****************************************************************
-- The following table contains LU sessions statistics dynamic
-- parameters.
-- ****************************************************************

snaLuSessnStatsTable OBJECT-TYPE
      SYNTAX  SEQUENCE OF SnaLuSessnStatsEntry
      MAX-ACCESS  not-accessible
      STATUS  current
      DESCRIPTION
            "This table contains dynamic statistics information
            relating to LU sessions.
            The entries in this table augment the entries in
            the snaLuSessnTable and cannot be created by
            a Management Station."
      ::= { snaLu 4 }

snaLuSessnStatsEntry OBJECT-TYPE
      SYNTAX  SnaLuSessnStatsEntry
      MAX-ACCESS  not-accessible
      STATUS  current
      DESCRIPTION
            "Contains statistics information for an LU session.

     Each entry is created by the Agent.
            Objects in this table have read-only access.
            Each session from snaLuSessnTable
            has one entry in this table."
      AUGMENTS   { snaLuSessnEntry }
      ::= { snaLuSessnStatsTable 1 }

SnaLuSessnStatsEntry ::= SEQUENCE {
      snaLuSessnStatsSentBytes
            Counter32,
      snaLuSessnStatsReceivedBytes
            Counter32,
      snaLuSessnStatsSentRus
            Counter32,
      snaLuSessnStatsReceivedRus
            Counter32,
      snaLuSessnStatsSentNegativeResps
            Counter32,
      snaLuSessnStatsReceivedNegativeResps
```

```
            Counter32
        }

    snaLuSessnStatsSentBytes OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of bytes sent by the local LU."
        ::= { snaLuSessnStatsEntry 1 }

    snaLuSessnStatsReceivedBytes OBJECT-TYPE
        SYNTAX
     Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of bytes received by the local LU."
        ::= { snaLuSessnStatsEntry 2 }

    snaLuSessnStatsSentRus OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of RUs sent by the local LU."
        ::= { snaLuSessnStatsEntry 3 }

    snaLuSessnStatsReceivedRus OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of RUs received by the local LU."
        ::= { snaLuSessnStatsEntry 4 }

    snaLuSessnStatsSentNegativeResps OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of negative responses sent by the
            local LU."
        ::= { snaLuSessnStatsEntry 5 }

    snaLuSessnStatsReceivedNegativeResps OBJECT-TYPE
        SYNTAX
```

```
 Counter32
     MAX-ACCESS  read-only
     STATUS  current
     DESCRIPTION
          "The number of negative responses received by the
          local LU."
     ::= { snaLuSessnStatsEntry 6 }


-- ****************************************************************
-- Traps
-- ****************************************************************

snaLuTraps OBJECT IDENTIFIER ::= { snaLu 5 }

snaLuStateChangeTrap NOTIFICATION-TYPE
     OBJECTS  {  snaLuOperName,
           snaLuOperSnaName,
          snaLuOperState }
     STATUS  current
     DESCRIPTION
          "This trap indicates that the operational state
          (i.e., snaLuOperState value) of the LU has changed.
          The value of snaLuOperName indicates the name of the
          LU.
          The value of snaLuOperSnaName indicates the SNA name
          of LU.
          The value of snaLuOperState indicates the current
          state after
 change."
     ::= { snaLuTraps 1 }

snaLuSessnBindFailTrap NOTIFICATION-TYPE
     OBJECTS  { snaLuSessnLocalApplName,
          snaLuSessnRemoteLuName,
          snaLuSessnOperState,
          snaLuSessnSenseData }
     STATUS  current
     DESCRIPTION
          "This trap indicates the failure of a BIND.
          The value of snaLuSessnLocalApplName indicates the local
          application name.
          The value of snaLuSessnPartnerName indicates the partner
          name.
          The value of snaLuSessnOperState indicates the current
          state after change.
          The value of snaLuSessnBindFailureReason
          indicates the failure reason.
```

```
            The Agent should not generate more than 1 trap of this
            type per minute to minimize the level of management
            traffic on the network."
        ::= { snaLuTraps 2 }

-- ****************************************************************
--
 snaMgtTools group
--
-- Currently this group contains only one table.
-- ****************************************************************


-- ****************************************************************
-- The following table contains Response Time Monitoring (RTM)
-- configuration information and statistics for LU Type 2s.
-- RTM supports the capability to measure and report end-user
-- response times for dependent LUs. When the RTM state of an LU
-- is 'on', response times for each LU transaction are monitored.
-- A set of ranges is defined (e.g., Range 1 includes the number of
-- transactions with response times less than 1 second) using the
-- "boundary" definitions (e.g., boundary #2 is defined as 3 seconds).
-- A set of counters (one per range) identifies
-- the number of transactions within each response time range.
-- ****************************************************************

snaLuRtmTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF SnaLuRtmEntry
         MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
            "This table contains Response Time Monitoring (RTM)
            information relating to an LU (Type 2). Each entry
            corresponds to an LU 2 entry in
            snaLuAdminTable."
        ::= { snaMgtTools 1 }

snaLuRtmEntry OBJECT-TYPE
        SYNTAX  SnaLuRtmEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
            "Contains RTM information for an LU (Type 2).
            Each entry is created by the Agent."
        INDEX   { snaLuRtmPuIndex, snaLuRtmLuIndex }
        ::= { snaLuRtmTable 1 }

SnaLuRtmEntry ::= SEQUENCE {
```

```
        snaLuRtmPuIndex
                Integer32,
        snaLuRtmLuIndex
                Integer32,
        snaLuRtmState
                INTEGER,
        snaLuRtmStateTime
                TimeStamp,
        snaLuRtmDef
                INTEGER,
        snaLuRtmBoundary1
                Integer32,
         snaLuRtmBoundary2
                Integer32,
        snaLuRtmBoundary3
                Integer32,
        snaLuRtmBoundary4
                Integer32,
        snaLuRtmCounter1
                Counter32,
        snaLuRtmCounter2
                Counter32,
        snaLuRtmCounter3
                Counter32,
        snaLuRtmCounter4
                Counter32,
        snaLuRtmOverFlows
                Counter32,
        snaLuRtmObjPercent
                Integer32,
        snaLuRtmObjRange
                INTEGER,
        snaLuRtmNumTrans
                Integer32,
        snaLuRtmLastRspTime
                Integer32,
        snaLuRtmAvgRspTime
                Integer32
        }

    snaLuRtmPuIndex OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS not-accessible
        STATUS  current
        DESCRIPTION
                "The value identifies the PU 2.0 with which this LU is
                associated."
        ::= { snaLuRtmEntry 1 }
```

```
snaLuRtmLuIndex OBJECT-TYPE
    SYNTAX
  Integer32
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
        "The value uniquely identifies an LU in a PU 2.0."
    ::= { snaLuRtmEntry 2 }

snaLuRtmState OBJECT-TYPE
    SYNTAX  INTEGER {
        off(1),
        on(2)
        }
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The value indicates the current RTM state of an LU."
    ::= { snaLuRtmEntry 3 }

snaLuRtmStateTime  OBJECT-TYPE
    SYNTAX  TimeStamp
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The timestamp (e.g., the Agent's sysUpTime value)
        when this session's RTM state (e.g., snaLuRtmState)
        changes value."
    ::= { snaLuRtmEntry 4 }

snaLuRtmDef OBJECT-TYPE
    SYNTAX  INTEGER {
        firstChar(1),
        kb(2),
        cdeb(3)
        }
    MAX-ACCESS  read-only

   STATUS  current
    DESCRIPTION
        "The value indicates the mode of measurement for this
        RTM request.  The values have following meaning:
          firstChar(1) - time to first character on screen
          kb(2) - time to keyboard usable by operator
          cdeb(3) - time to Change Direction/End Bracket."
    ::= { snaLuRtmEntry 5 }
```

```
snaLuRtmBoundary1 OBJECT-TYPE
    SYNTAX  Integer32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "This object contains the value of the first boundary
        in units of 1/10th of a second."
    ::= { snaLuRtmEntry 6 }

snaLuRtmBoundary2 OBJECT-TYPE
    SYNTAX  Integer32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "This object contains the value of the second boundary
         in units of 1/10th of a second."
    ::= { snaLuRtmEntry 7 }

snaLuRtmBoundary3 OBJECT-TYPE
     SYNTAX  Integer32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "This object contains the value of the third boundary
         in units of 1/10th of a second."
    ::= { snaLuRtmEntry 8 }

snaLuRtmBoundary4 OBJECT-TYPE
    SYNTAX  Integer32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "This object contains the value of the fourth boundary
        in units of 1/10th of a second."
    ::= { snaLuRtmEntry 9 }

snaLuRtmCounter1 OBJECT-TYPE
    SYNTAX  Counter32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "This value indicates the number of transactions which
        fall in the range specified by the first boundary."
    ::= { snaLuRtmEntry 10 }

snaLuRtmCounter2 OBJECT-TYPE
    SYNTAX  Counter32
    MAX-ACCESS  read-only
```

```
        STATUS  current
        DESCRIPTION
                "This value indicates
 the number of transactions which
                fall in the range specified by the second boundary."
        ::= { snaLuRtmEntry 11 }

snaLuRtmCounter3 OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "This value indicates the number of transactions which
                fall in the range specified by the third boundary."
        ::= { snaLuRtmEntry 12 }

snaLuRtmCounter4 OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "This value indicates the number of transactions which
                fall in the range specified by the fourth boundary."
        ::= { snaLuRtmEntry 13 }

snaLuRtmOverFlows OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "This value indicates the number of transactions which
                exceed the highest range specified by
 the
                boundaries."
        ::= { snaLuRtmEntry 14 }

snaLuRtmObjPercent OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "This value indicates the desired percentage of
                transactions which should be under a designated
                boundary range indicated by snaLuRtmObjRange."
        ::= { snaLuRtmEntry 15 }

snaLuRtmObjRange OBJECT-TYPE
         SYNTAX  INTEGER {
```

```
            other(1),
            range1(2),
            range2(3),
            range3(4),
            range4(5),
            range5(6)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This value indicates the designated boundary range to
            which the snaLuRtmObject refers.
            The values have the following meanings:
              other(1)   - not specified
              range1(2)  - less than boundary
1
              range2(3)  - between boundary 1 and 2
              range3(4)  - between boundary 2 and 3
              range4(5)  - between boundary 3 and 4
              range5(6)  - greater than boundary 4."
        ::= { snaLuRtmEntry 16 }

    snaLuRtmNumTrans OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This value indicates the total number of transactions
            executed since the RTM monitoring began (i.e.,
            snaLuRtmState changed to 'on(2)') for this LU."
        ::= { snaLuRtmEntry 17 }

    snaLuRtmLastRspTime OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This value indicates the response time for the last
            transaction in units of 1/10th of a second."
        ::= { snaLuRtmEntry 18 }

    snaLuRtmAvgRspTime OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  read-only
         STATUS  current
        DESCRIPTION
            "This value indicates the average response time for all
            transactions in units of 1/10th of a second."
```

```
    ::= { snaLuRtmEntry 19 }


-- ****************************************************************
-- Conformance information
-- ****************************************************************

snanauConformance       OBJECT IDENTIFIER ::= { snanauMIB 2 }

snanauCompliances       OBJECT IDENTIFIER ::= {snanauConformance 1 }
snanauGroups            OBJECT IDENTIFIER ::= {snanauConformance 2 }

-- Compliance statements
snanauCompliance  MODULE-COMPLIANCE
    STATUS  current
    DESCRIPTION
        "The compliance statement for the SNMPv2 entities
        which implement the snanau MIB."
    MODULE  -- this module

--    Unconditionally mandatory groups
        MANDATORY-GROUPS  { snaNodeGroup,
            snaLuGroup,
            snaSessionGroup
 }

--    Conditionally mandatory groups
        GROUP  snaPu20Group
        DESCRIPTION
            "The snaPu20Group is mandatory only for those
            entities which implement PU type 2.0"
        GROUP  snaMgtToolsRtmGroup
        DESCRIPTION
            "The snaMgtToolsGroup is mandatory only for
            those entities which implement LU type 2
            and RTM."

--    Refinement of requirements for objects access.
--    The Agent which does not implement row creation for
--    snaNodeAdminTable, snaNodeLinkAdminTable and
--    snaLuAdminTable must at least accept
--    objects modification (read-write access instead of
--    read-create).

        OBJECT  snaNodeAdminName
        MIN-ACCESS  read-write
        DESCRIPTION
            "An Agent is required to implement read-write
```

access to this object."

OBJECT snaNodeAdminType
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeAdminXidFormat
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeAdminBlockNum
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeAdminIdNum
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeAdminEnablingMethod
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeAdminLuTermDefault
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeAdminMaxLu
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeAdminHostDescription
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write

access to this object."

OBJECT snaNodeAdminStopMethod
MIN-ACCESS read-write
DESCRIPTION
"An
Agent is required to implement read-write
access to this object."

OBJECT snaNodeAdminState
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeLinkAdminSpecific
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeLinkAdminMaxPiu
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."
OBJECT snaLuAdminName
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this
object."

OBJECT snaLuAdminSnaName
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaLuAdminType
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaLuAdminDepType
MIN-ACCESS read-write
DESCRIPTION

```
                "An Agent is required to implement read-write
                access to this object."

            OBJECT  snaLuAdminLocalAddress
            MIN-ACCESS  read-write
            DESCRIPTION
                "An Agent is required to implement read-write
                access to this object."

            OBJECT  snaLuAdminDisplayModel
            MIN-ACCESS
 read-write
            DESCRIPTION
                "An Agent is required to implement read-write
                access to this object."

            OBJECT  snaLuAdminTerm
            MIN-ACCESS  read-write
            DESCRIPTION
                "An Agent is required to implement read-write
                access to this object."

      ::= {snanauCompliances 1 }


-- Units of conformance

snaNodeGroup  OBJECT-GROUP
      OBJECTS  { snaNodeAdminName,
            snaNodeAdminType,
            snaNodeAdminXidFormat,
            snaNodeAdminBlockNum,
            snaNodeAdminIdNum,
            snaNodeAdminEnablingMethod,
            snaNodeAdminLuTermDefault,
            snaNodeAdminMaxLu,
            snaNodeAdminHostDescription,
            snaNodeAdminStopMethod,
            snaNodeAdminState,
            snaNodeAdminRowStatus,
            snaNodeAdminTableLastChange,
            snaNodeOperName,
             snaNodeOperType,
            snaNodeOperXidFormat,
            snaNodeOperBlockNum,
            snaNodeOperIdNum,
            snaNodeOperEnablingMethod,
            snaNodeOperLuTermDefault,
```

```
            snaNodeOperMaxLu,
            snaNodeOperHostDescription,
            snaNodeOperStopMethod,
            snaNodeOperState,
            snaNodeOperHostSscpId,
            snaNodeOperStartTime,
            snaNodeOperLastStateChange,
            snaNodeOperActFailures,
            snaNodeOperActFailureReason,
            snaNodeOperTableLastChange,
            snaNodeLinkAdminSpecific,
            snaNodeLinkAdminMaxPiu,
            snaNodeLinkAdminRowStatus,
            snaNodeLinkAdminTableLastChange,
            snaNodeLinkOperSpecific,
            snaNodeLinkOperMaxPiu,
            snaNodeLinkOperTableLastChange }
        STATUS  current
        DESCRIPTION

        "A collection of objects providing the
            instrumentation of SNA nodes."
        ::= { snanauGroups 1 }

    snaLuGroup  OBJECT-GROUP
        OBJECTS  { snaLuAdminName,
            snaLuAdminSnaName,
            snaLuAdminType,
            snaLuAdminDepType,
            snaLuAdminLocalAddress,
            snaLuAdminDisplayModel,
            snaLuAdminTerm,
            snaLuAdminRowStatus,
            snaLuOperName,
            snaLuOperSnaName,
            snaLuOperType,
            snaLuOperDepType,
            snaLuOperLocalAddress,
            snaLuOperDisplayModel,
            snaLuOperTerm,
            snaLuOperState,
            snaLuOperSessnCount }
        STATUS  current
        DESCRIPTION
            "A collection of objects providing the
            instrumentation of SNA LUs."
        ::= { snanauGroups 2 }
```

```
snaSessionGroup  OBJECT-GROUP
      OBJECTS  { snaLuSessnRluIndex,

     snaLuSessnIndex,
           snaLuSessnLocalApplName,
           snaLuSessnRemoteLuName,
           snaLuSessnMaxSndRuSize,
           snaLuSessnMaxRcvRuSize,
           snaLuSessnSndPacingSize,
           snaLuSessnRcvPacingSize,
           snaLuSessnActiveTime,
           snaLuSessnAdminState,
           snaLuSessnOperState,
           snaLuSessnSenseData,
           snaLuSessnTerminationRu,
           snaLuSessnUnbindType,
           snaLuSessnLinkIndex,
           snaLuSessnStatsSentBytes,
           snaLuSessnStatsReceivedBytes,
           snaLuSessnStatsSentRus,
           snaLuSessnStatsReceivedRus,
           snaLuSessnStatsSentNegativeResps,
           snaLuSessnStatsReceivedNegativeResps }
      STATUS  current
      DESCRIPTION
           "A collection of objects providing the
           instrumentation of SNA sessions."
      ::= { snanauGroups 3 }

snaPu20Group
  OBJECT-GROUP
      OBJECTS  { snaPu20StatsSentBytes,
           snaPu20StatsReceivedBytes,
           snaPu20StatsSentPius,
           snaPu20StatsReceivedPius,
           snaPu20StatsSentNegativeResps,
           snaPu20StatsReceivedNegativeResps,
           snaPu20StatsActLus,
           snaPu20StatsInActLus,
           snaPu20StatsBindLus }
      STATUS  current
      DESCRIPTION
           "A collection of objects providing the
           instrumentation of PU 2.0."
      ::= { snanauGroups 4 }

snaMgtToolsRtmGroup  OBJECT-GROUP
      OBJECTS  { snaLuRtmState,
```

```
            snaLuRtmStateTime,
            snaLuRtmDef,
            snaLuRtmBoundary1,
            snaLuRtmBoundary2,
            snaLuRtmBoundary3,
            snaLuRtmBoundary4,
            snaLuRtmCounter1,
            snaLuRtmCounter2,
            snaLuRtmCounter3,
            snaLuRtmCounter4,
            snaLuRtmOverFlows,
             snaLuRtmObjPercent,
            snaLuRtmObjRange,
            snaLuRtmNumTrans,
            snaLuRtmLastRspTime,
            snaLuRtmAvgRspTime }
        STATUS  current
        DESCRIPTION
            "A collection of objects providing the
            instrumentation of RTM for SNA LU 2.0."
        ::= { snanauGroups 5 }

-- end of conformance statement


END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/SNA-NAU-MIB
No license file was found, but licenses were detected in source scan.

Modem-MIB DEFINITIONS ::= BEGIN


IMPORTS
  MODULE-IDENTITY, OBJECT-TYPE, OBJECT-IDENTITY,
  Counter32, Integer32 FROM SNMPv2-SMI
  DisplayString FROM SNMPv2-TC
  MODULE-COMPLIANCE, OBJECT-GROUP FROM SNMPv2-CONF
  mib-2 FROM RFC1213-MIB;


mdmMIB MODULE-IDENTITY
  LAST-UPDATED "9406120000Z"
  ORGANIZATION "IETF Modem Management Working Group"
  CONTACT-INFO
        "       Steven Waldbusser
         Postal: Carnegie Mellon University
```

```
                5000 Forbes Ave
                Pittsburgh, PA, 15213
                US

             Tel: +1 412 268 6628
             Fax: +1 412 268 4987
           E-mail: waldbusser@cmu.edu"
  DESCRIPTION
        "The MIB module for management of dial-up modems."
  ::= { mdmMib 1 }

mdmMib OBJECT IDENTIFIER ::= { mib-2 38 }

mdmMIBObjects OBJECT IDENTIFIER ::= { mdmMIB 1 }


-- conformance information

mdmConformance OBJECT IDENTIFIER
 ::= { mdmMIB 2 }

mdmCompliances OBJECT IDENTIFIER ::= { mdmConformance 1 }
mdmGroups      OBJECT IDENTIFIER ::= { mdmConformance 2 }

-- units of conformance

mdmIDGroup    OBJECT-GROUP
  OBJECTS   { mdmIDManufacturerOID, mdmIDProductDetails }
  STATUS    current
  DESCRIPTION
        "A collection of objects that identify the manufacturer and
        model information for a modem."
  ::= { mdmGroups 1 }

mdmLineInterfaceGroup    OBJECT-GROUP
  OBJECTS { mdmLineCarrierLossTime,
     mdmLineState, mdmLineCapabilitiesID,
     mdmLineCapabilitiesEnableRequested,
     mdmLineCapabilitiesEnableGranted }
  STATUS  current
  DESCRIPTION
        "A collection of objects that describe the configuration and
        state of the modem's line interface."
  ::= { mdmGroups 2 }

mdmDTEInterfaceGroup    OBJECT-GROUP
  OBJECTS { mdmDTEActionDTROnToOff, mdmDTEActionDTROffToOn,
            mdmDTESyncTimingSource, mdmDTESyncAsyncMode,
```

```
   mdmDTEInactivityTimeout }
  STATUS      current
  DESCRIPTION
          "A collection of objects that describe the configuration and
          state of the modem's DTE interface."
  ::= { mdmGroups 3 }

mdmCallControlGroup    OBJECT-GROUP
  OBJECTS { mdmCCRingsBeforeAnswer,
     mdmCCCallSetUpFailTimer, mdmCCResultCodeEnable,
     mdmCCEscapeAction, mdmCCCallDuration,
     mdmCCConnectionFailReason, mdmCCStoredDialString }
  STATUS  current
  DESCRIPTION
          "A collection of objects that describe the configuration of
          call control capabilities on the modem and the status of
          calls placed with this modem."
  ::= { mdmGroups 4 }

mdmErrorControlGroup   OBJECT-GROUP
  OBJECTS { mdmECErrorControlUsed }
  STATUS  current
  DESCRIPTION
          "A collection of objects that describe the configuration and
          state of error control on a modem."
  ::= { mdmGroups 5 }

mdmDataCompressionGroup   OBJECT-GROUP
  OBJECTS
 { mdmDCCompressionTypeUsed }
  STATUS  current
  DESCRIPTION
          "A collection of objects that describe the configuration and
          state of data compression on a modem."
  ::= { mdmGroups 6 }

mdmSignalConvertorGroup   OBJECT-GROUP
OBJECTS { mdmSCCurrentLineReceiveRate, mdmSCCurrentLineTransmitRate,
        mdmSCInitialLineReceiveRate, mdmSCInitialLineTransmitRate,
        mdmSCModulationSchemeUsed }
  STATUS  current
  DESCRIPTION
          "A collection of objects that describe the configuration and
          state of error control on a modem."
  ::= { mdmGroups 7 }

mdmStatisticsGroup  OBJECT-GROUP
```

```
  OBJECTS { mdmStatsRingNoAnswers,
     mdmStatsIncomingConnectionFailures,
     mdmStatsIncomingConnectionCompletions,
     mdmStatsFailedDialAttempts,
     mdmStatsOutgoingConnectionFailures,
     mdmStatsOutgoingConnectionCompletions,
     mdmStatsRetrains,
     mdmStats2400OrLessConnections, mdmStats2400To14400Connections,
      mdmStatsGreaterThan14400Connections,
     mdmStatsErrorControlledConnections,
     mdmStatsCompressedConnections,
     mdmStatsCompressionEfficiency,
     mdmStatsSentOctets, mdmStatsReceivedOctets,
     mdmStatsSentDataFrames, mdmStatsReceivedDataFrames,
     mdmStatsResentFrames, mdmStatsErrorFrames }
  STATUS  current
  DESCRIPTION
        "A collection of objects that describe the state of calls on
        this modem."
  ::= { mdmGroups 8 }

mdmNumber OBJECT-TYPE
  SYNTAX  Integer32
  MAX-ACCESS  read-only
  STATUS  current
  DESCRIPTION
        "The number of modem rows in the modem table.  This value
        defines the maximum value of the mdmIndex object."
  ::= { mdmMIBObjects 1 }

-- The modem ID table.

mdmIDTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmIDEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The base table for the modems managed by this MIB.  The
        mdmLineTable,
 mdmDTEInterfaceTable, mdmCallControlTable, and
        mdmStatsTable all augment the rows defined in this table."
  ::= { mdmMIBObjects 2 }

mdmIDEntry OBJECT-TYPE
  SYNTAX      MdmIDEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
```

```
        "Entries in this table are created only by the agent. One
        entry exists for each modem managed by the agent."
  INDEX       { mdmIndex }
  ::= { mdmIDTable 1 }

MdmIDEntry ::= SEQUENCE {
  mdmIndex              Integer32,
  mdmIDManufacturerOID    OBJECT IDENTIFIER,
  mdmIDProductDetails     DisplayString
}

mdmIndex OBJECT-TYPE
  SYNTAX      Integer32 (1..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "A unique number for each modem that ranges from 1 to
        mdmNumber.  The value must remain constant at least from one
        re-initialization of the network management agent to the
        next."
  ::= { mdmIDEntry 1
 }

mdmIDManufacturerOID OBJECT-TYPE
  SYNTAX      OBJECT IDENTIFIER
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "This value is intended to identify the manufacturer, model,
        and version of this modem.  This may be used to identify the
        existance of enterprise-specific functions and behaviours."
  REFERENCE
        "V.58 attribute manufacturerID subfield ManufacturerOI"
  ::= { mdmIDEntry 2 }

mdmIDProductDetails OBJECT-TYPE
  SYNTAX      DisplayString (SIZE (0..79))
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "A textual description of this device, including the
        manufacturer's name, modem model name, hardware revision,
        firmware revision, and optionally, its serial number.  The
        exact format of this description is defined by the vendor.
        This description may only contain characters from the NVT
        ASCII character set."
  REFERENCE
```

```
        "V.58 attribute manufacturerID subfield productDetails"
  ::= { mdmIDEntry 3 }

-- The modem Line Interface Table

mdmLineTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmLineEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The modem Line Table augments the modem ID table."
  ::= { mdmMIBObjects 3 }

mdmLineEntry OBJECT-TYPE
  SYNTAX      MdmLineEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "Entries in this table are created only by the agent. One
        entry exists for each modem managed by the agent."
  AUGMENTS    { mdmIDEntry }
  ::= { mdmLineTable 1 }

MdmLineEntry ::= SEQUENCE {
  mdmLineCarrierLossTime         Integer32,
  mdmLineState                   INTEGER
}

mdmLineCarrierLossTime OBJECT-TYPE
  SYNTAX      Integer32 (1..255)
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "Duration in 10ths of a second the modem waits after
 loss of
        carrier before hanging up.  If this value is set to `255',
        the modem will not hang up upon loss of carrier.  This
        allows the modem to distinguish between a momentary lapse in
        line quality and a true disconnect and can be useful to tune
        the tolerance of the modem to lines of poor quality."
  REFERENCE "V.58 lineSignalFailDisconnectTimer"
  ::= { mdmLineEntry 1 }

mdmLineState OBJECT-TYPE
  SYNTAX      INTEGER {
                unknown(1),
                onHook(2),
                offHook(3),  -- and not connected
```

```
            connected(4),
            busiedOut(5),
            reset(6)
          }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "Allows the inspection and alteration of the state of the
        modem.  Management commands may change the state to `on-
        hook', `busied-out', or `reset' from any state.  No other

       alterations are permitted from the management protocol.
        When this object is set to reset, the modem shall be reset
        and the value will change to the modem's new, implementation
        dependent state."
  ::= { mdmLineEntry 2 }

mdmLineCapabilitiesTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmLineCapabilitiesEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "A list of protocol capabilities for this modem."
  ::= { mdmMIBObjects 4 }

mdmLineCapabilitiesEntry OBJECT-TYPE
  SYNTAX      MdmLineCapabilitiesEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "A listing of the protocol(s) that this modem is capable of.
        Entries in this table are created only by the agent.  One
        entry exists for each protocol that the modem is capable of,
        regardless of whether that protocol is enabled or not.

        This table is useful for providing an
 inventory of the
        capabilities on a modem, and allowing the manager to enable
        or disable capabilities from the menu of available
        possibilities.  Row creation is not required to enable or
        disable capabilities."
  INDEX       { mdmIndex, mdmLineCapabilitiesIndex }
  ::= { mdmLineCapabilitiesTable 1 }

MdmLineCapabilitiesEntry ::= SEQUENCE {
  mdmLineCapabilitiesIndex           Integer32,
  mdmLineCapabilitiesID              OBJECT IDENTIFIER,
  mdmLineCapabilitiesEnableRequested  INTEGER,
```

```
  mdmLineCapabilitiesEnableGranted    INTEGER
}

mdmLineCapabilitiesIndex OBJECT-TYPE
  SYNTAX      Integer32
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "A unique index for this capabilities entry."
  ::= { mdmLineCapabilitiesEntry 1 }

mdmLineCapabilitiesID OBJECT-TYPE
  SYNTAX      OBJECT IDENTIFIER
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "An identifier for
 this capability.  Standard protocol
        capabilities will have identifiers registered in this
        document or other companion standards documents.
        Proprietary protocol capabilities will be registered by
        their respective organization.  All capabilities, standard
        or vendor-specific, shall be registered in this table."
  ::= { mdmLineCapabilitiesEntry 2 }

mdmLineCapabilitiesEnableRequested OBJECT-TYPE
  SYNTAX      INTEGER {
                disabled(1),
                optional(2),
                preferred(3)
              }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "The requested configuration of this capability.  If this
        value is 'disabled(1)', this is a request to disable this
        protocol.  If this value is 'preferred(3)', this is a
        request to enable this protocol, and to prefer it in any
        negotiation over other appropriate protocols
 that have a
        value of 'optional(2)'."
  DEFVAL      { preferred }
  ::= { mdmLineCapabilitiesEntry 3 }

mdmLineCapabilitiesEnableGranted OBJECT-TYPE
  SYNTAX      INTEGER {
                disabled(1),
                optional(2),
```

```
                preferred(3)
            }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The actual configuration of this capability.  The agent
        shall attempt to set this as close as possible to the
        associated mdmLineCapabilitiesEnableRequested value.  The
        agent shall make this determination in an implementation-
        specific manner that may take into account the configuration
        of other capabilities or other considerations.  The modem
        will choose in an implementation-specific manner between
        multiple mutually-exclusive capabilities that each have the
        same (non-disabled) value.  However, the modem must prefer
         all capabilities with a value of 'preferred(3)' over all
        capabilities with a value of 'optional(2)'.

        In other words, if there are one or more mutually-exclusive
        capabilities (e.g. V.32 and V.32bis) that are set to
        `preferred', the agent must choose one in an
        implementation-specific manner.  Otherwise, if there are one
        or more mutually-exclusive capabilities that are set to
        `optional', the agent must choose one in an implementation-
        specific manner."
  ::= { mdmLineCapabilitiesEntry 4 }

mdmLineCapabilities   OBJECT IDENTIFIER ::= { mdmMIBObjects 5 }

mdmLineCapabilitiesV21 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.21"
  ::= { mdmLineCapabilities 1 }

mdmLineCapabilitiesV22 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.22"
  ::= { mdmLineCapabilities 2 }

mdmLineCapabilitiesV22bis OBJECT-IDENTITY
  STATUS  current
   DESCRIPTION
        "ITU V.22bis"
  ::= { mdmLineCapabilities 3 }

mdmLineCapabilitiesV23CC OBJECT-IDENTITY
  STATUS  current
```

```
  DESCRIPTION
        "ITU V.23CC"
  ::= { mdmLineCapabilities 4 }

mdmLineCapabilitiesV23SC OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.23SC"
  ::= { mdmLineCapabilities 5 }

mdmLineCapabilitiesV25bis OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.25bis"
  ::= { mdmLineCapabilities 6 }

mdmLineCapabilitiesV26bis OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.26bis"
  ::= { mdmLineCapabilities 7 }

mdmLineCapabilitiesV26ter OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.26ter"
  ::= { mdmLineCapabilities 8 }

mdmLineCapabilitiesV27ter OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.27ter"
  ::= { mdmLineCapabilities 9 }

mdmLineCapabilitiesV32 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.32"
   ::= { mdmLineCapabilities 10 }

mdmLineCapabilitiesV32bis OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.32bis"
  ::= { mdmLineCapabilities 11 }

mdmLineCapabilitiesV32terbo OBJECT-IDENTITY
  STATUS  current
```

```
  DESCRIPTION
        "ITU V.32terbo"
  ::= { mdmLineCapabilities 12 }

mdmLineCapabilitiesVFC OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.FC"
  ::= { mdmLineCapabilities 13 }

mdmLineCapabilitiesV34 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.34"
  ::= { mdmLineCapabilities 14 }

mdmLineCapabilitiesV42 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.42"
  ::= { mdmLineCapabilities 15 }

mdmLineCapabilitiesV42bis OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.42bis"
  ::= { mdmLineCapabilities 16 }

mdmLineCapabilitiesMNP1 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP1"
  ::= { mdmLineCapabilities 17 }

mdmLineCapabilitiesMNP2
 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP2"
  ::= { mdmLineCapabilities 18 }

mdmLineCapabilitiesMNP3 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP3"
  ::= { mdmLineCapabilities 19 }

mdmLineCapabilitiesMNP4 OBJECT-IDENTITY
```

```
  STATUS  current
  DESCRIPTION
        "MNP4"
  ::= { mdmLineCapabilities 20 }

mdmLineCapabilitiesMNP5 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP5"
  ::= { mdmLineCapabilities 21 }

mdmLineCapabilitiesMNP6 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP6"
  ::= { mdmLineCapabilities 22 }

mdmLineCapabilitiesMNP7 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP7"
  ::= { mdmLineCapabilities 23 }

mdmLineCapabilitiesMNP8 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP8"
  ::= { mdmLineCapabilities 24 }

mdmLineCapabilitiesMNP9 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION

  "MNP9"
  ::= { mdmLineCapabilities 25 }

mdmLineCapabilitiesMNP10 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP10"
  ::= { mdmLineCapabilities 26 }

mdmLineCapabilitiesV29 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.29"
  ::= { mdmLineCapabilities 27 }
```

```
mdmLineCapabilitiesV33 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.33"
  ::= { mdmLineCapabilities 28 }

mdmLineCapabilitiesBell208 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "Bell 208"
  ::= { mdmLineCapabilities 29 }


-- DTE Interface Table

mdmDTEInterfaceTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmDTEInterfaceEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The modem DTE Interface Table augments the modem ID table."
  ::= { mdmMIBObjects 6 }

mdmDTEInterfaceEntry OBJECT-TYPE
  SYNTAX      MdmDTEInterfaceEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
         "Entries in this table are created only by the agent. One
        entry exists for each modem managed by the agent."
  AUGMENTS    { mdmIDEntry }
  ::= { mdmDTEInterfaceTable 1 }

MdmDTEInterfaceEntry ::= SEQUENCE {
  mdmDTEActionDTROnToOff      INTEGER,
  mdmDTEActionDTROffToOn      INTEGER,
  mdmDTESyncTimingSource      INTEGER,
  mdmDTESyncAsyncMode         INTEGER,
  mdmDTEInactivityTimeout     Integer32
}

mdmDTEActionDTROnToOff OBJECT-TYPE
  SYNTAX      INTEGER {
                ignore(1),
                escapeToCommandMode(2),
                disconnectCall(3),
                resetModem(4)
              }
```

```
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "Defines the action the modem will take when DTR drops.

        If the value is set to ignore(1), the modem takes no action
        when DTR drops.  Typically, mdmDTEActionDTROffToOn would
        also be set to ignore(1) if this object
 is set to ignore(1).

        If the value is escapeToCommandMode(2), the modem remains
        connected and enters command mode.  If the value is
        disconnectCall(3), the current call (if any) is terminated
        and the modem will not auto-answer while DTR is off.  If the
        value is resetModem(4), the current call (if any) is
        terminated and the modem is reset."
  DEFVAL      { disconnectCall }
  ::= { mdmDTEInterfaceEntry 1 }

mdmDTEActionDTROffToOn OBJECT-TYPE
  SYNTAX      INTEGER {
                ignore(1),
                enableDial(2),
                autoAnswerEnable(3),
                establishConnection(4)
              }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "Defines the action the modem will take when DTR is raised.

        If the value is set to ignore(1), the modem takes no action
        when DTR is raised.  Typically, mdmDTEActionDTROnToOff would
         also be set to ignore(1) if this object is set to ignore(1).

        If the value is set to enableDial(2), the modem prepares to
        dial an outgoing call.  If the value is set to
        autoAnswerEnable(3), the modem will be configured to answer
        any incoming call.  If the value is set to
        establishConnection(4), the modem dials an implementation
        specific number.

        Immediately after any reset or power-on of the modem, if the
        DTR is high, the action specified here will be executed."
  DEFVAL      { autoAnswerEnable }
  ::= { mdmDTEInterfaceEntry 2 }

mdmDTESyncTimingSource OBJECT-TYPE
```

```
  SYNTAX      INTEGER {
                internal(1),
                external(2),
                loopback(3),
                network(4)
              }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "The clock source for synchronous transmissions.  If set to
         internal(1), the modem is the clock source and sends the
        clock signals to the DTE.  If set to external(2), the
        transmit clock signals are provided by the DTE.  If
        loopback(3), the modem receiver clock is used for the
        transmit clock.  If network(4), the clock signals are
        supplied by the DCE interface.

        If the modem is not in synchronous mode, setting this object
        will have no effect on the current operations of the modem."
  REFERENCE   "V.58 transmitClockSource"
  DEFVAL      { internal }
  ::= { mdmDTEInterfaceEntry 3 }

mdmDTESyncAsyncMode OBJECT-TYPE
  SYNTAX      INTEGER {
                async(1),
                sync(2),
                syncAfterDial(3)
              }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "The operational mode of the modem.  If the value is
        syncAfterDial(3), the modem will accept commands in

       asynchronous mode and change to synchronous mode to pass
        data after a dial sequence has been executed."
  DEFVAL      { async }
  ::= { mdmDTEInterfaceEntry 4 }

mdmDTEInactivityTimeout OBJECT-TYPE
  SYNTAX      Integer32 (0..65535)
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "The amount of idle time in minutes that the modem will wait
        before disconnecting a connection.  When a call is connected
        and no data is transferred (continuous marking condition) on
```

```
        both circuits 103 and 104 for the specified time, the DCE
        disconnects the call. If the value is 0, no idle disconnect
        will occur.  This function applies to asynchronous dial
        operations only and is intended for administrative control
        over idle connections."
  REFERENCE   "V.58 inactivityTimerSelect"
  DEFVAL { 0 }
  ::= { mdmDTEInterfaceEntry 5 }


-- The Call Control Table

mdmCallControlTable
 OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmCallControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The modem Call Control Table augments the modem ID table."
  ::= { mdmMIBObjects 7 }

mdmCallControlEntry OBJECT-TYPE
  SYNTAX      MdmCallControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "Entries in this table are created only by the agent. One
        entry exists for each modem managed by the agent."
  AUGMENTS    { mdmIDEntry }
  ::= { mdmCallControlTable 1 }

MdmCallControlEntry ::= SEQUENCE {
  mdmCCRingsBeforeAnswer      Integer32,
  mdmCCCallSetUpFailTimer     Integer32,
  mdmCCResultCodeEnable       INTEGER,
  mdmCCEscapeAction           INTEGER,
  mdmCCCallDuration           Integer32,
  mdmCCConnectionFailReason   INTEGER
}

mdmCCRingsBeforeAnswer OBJECT-TYPE
  SYNTAX      Integer32
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION

       "Determines which ring the modem will wait to answer the
        phone on.  If this value is `0', the modem will not go
```

```
        offhook and answer a call when a ring signal is detected."
  REFERENCE   "V.58 ringsBeforeAnswer"
  DEFVAL      { 1 }
  ::= { mdmCallControlEntry 1 }

mdmCCCallSetUpFailTimer OBJECT-TYPE
  SYNTAX      Integer32 (0..255)
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "This parameter specifies the amount of time, in seconds,
        that the modem shall allow between either answering a call
        (automatically or manually) or completion of dialing, and
        establishment of a connection with the remote modem. If no
        connection is established during this time, the modem
        disconnects from the line and returns a result code
        indicating the cause of the disconnection. In TIA-602, this
        is controlled by the value in the S7 register."
  REFERENCE   "V.58
 callSetUpFailTimer"
  DEFVAL      { 30 }
  ::= { mdmCallControlEntry 2 }

mdmCCResultCodeEnable OBJECT-TYPE
  SYNTAX      INTEGER {
                disabled(1),
                numericEnabled(2),
                verboseEnabled(3)
              }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "When disabled, the DCE shall issue no 'result codes' of any
        kind to the DTE either in response to unsolicited events
        (eg. ring signal), or commands. In TIA-602, this is
        controlled by the ATQ command.  When numericEnabled, the DCE
        shall issue result codes in numeric form.  When
        verboseEnabled, the DCE shall issue result codes in a
        verbose, textual form."
  REFERENCE   "V.58 responseModeSelect"
  DEFVAL      { verboseEnabled }
  ::= { mdmCallControlEntry 3 }

mdmCCEscapeAction OBJECT-TYPE
  SYNTAX      INTEGER {
                ignoreEscape(1),
```

```
    hangUp(2),
            enterCommandMode(3)
          }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "The modem's action upon successfully recognizing the
        'escape to command mode' character sequence."
  DEFVAL { ignoreEscape }
  ::= { mdmCallControlEntry 4 }

-- Call status portion of the call control table

mdmCCCallDuration OBJECT-TYPE
  SYNTAX      Integer32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "Present or last completed connection time in seconds. If
        there have been no previous connections, this value should
        be -1."
  ::= { mdmCallControlEntry 5 }


mdmCCConnectionFailReason OBJECT-TYPE
  SYNTAX      INTEGER {
          -- General
                unknown(1),
                other(2),
                managementCommand(3),
                inactivityTimeout(4),
                mnpIncompatibility(5),

               protocolError(6),
          -- DCE
                powerLoss(10),
                equipmentFailure(11),
          -- DTE Interface
                dtrDrop(20),
          -- Line Interface
                noDialTone(30),
                lineBusy(31),
                noAnswer(32),
                voiceDetected(33),
          -- Signal Converter
                carrierLost(40),
                trainingFailed(41),
                faxDetected(42)
```

}
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"Indicates the reason that the last connection or attempt
failed. The meaning of each reason code is explained below.

unknown:
This code means the failure reason is unknown or
there has been no previous call.

other:
This code used when no other code is applicable.
Additional vendor information may be available
elsewhere.

managementCommand:
A management command terminated the call. These
commands include escaping to command mode, initiating
dialing, restoring lines, and disconnecting.

inactivityTimeout:
The call was terminated because it was inactive for
at the minimum duration specified.

mnpIncompatibility:
The modems are unable to resolve MNP protocol
differences.

protocolError:
An error occured in one of protocol in use. Further
information is required to determine in which
protocol the error occurred, and the exact nature of
the error.

powerLoss:
The modem lost power and disconnected the call.

equipmentFailure:
The modem equipment failed.

dtrDrop:

DTR has been turned off while the modem is to
disconnect on DTR drop. (Ref: V.58 cct108TurnedOff)

noDialTone:

If the modem is to monitor for call progress tones,
but the modem has failed to detect dial tone while
attempting to dial a number.

lineBusy:
Busy signal is detected while busy signal detection
is enabled, or while the 'W' or '@' dial modifier is
used. (Ref: V.58 engagedTone)

noAnswer:
The call was not answered.

voiceDetected:
A voice was detected on the call.

carrierLost:
Indicates that the modem has disconnected due to
detection of loss of carrier. In TIA-602, the S10
register determines the time that loss of carrier
must be detected before the modem disconnects.

trainingFailed:
Indicates that the modems did
not successfully train
and reach data mode on the previous connection.

faxDetected:
A fax was detected on the call."
REFERENCE "V.58 callCleared"
::= { mdmCallControlEntry 6 }

-- The Stored Dial String table

mdmCCStoredDialStringTable OBJECT-TYPE
SYNTAX SEQUENCE OF MdmCCStoredDialStringEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The table of stored dial strings."
REFERENCE "V.58 telephoneNumbers"
::= { mdmMIBObjects 8 }

mdmCCStoredDialStringEntry OBJECT-TYPE
SYNTAX MdmCCStoredDialStringEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"A stored dial string."

```
  INDEX  { mdmIndex, mdmCCStoredDialStringIndex }
  ::= { mdmCCStoredDialStringTable 1 }

MdmCCStoredDialStringEntry ::= SEQUENCE {
  mdmCCStoredDialStringIndex     Integer32,
  mdmCCStoredDialString          DisplayString
}

mdmCCStoredDialStringIndex OBJECT-TYPE
   SYNTAX      Integer32 (0..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The unique index of a particular dial string."
  ::= { mdmCCStoredDialStringEntry 1 }

mdmCCStoredDialString OBJECT-TYPE
  SYNTAX      DisplayString (SIZE(0..64))
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "A dial string stored in the modem."
  ::= { mdmCCStoredDialStringEntry 2 }

-- The modem Error Correcting Group

mdmECTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmECEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The modem error correcting table augments the modem ID
        table."
  ::= { mdmMIBObjects 9 }

mdmECEntry OBJECT-TYPE
  SYNTAX      MdmECEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "Entries in this table are created only by the agent. One
        entry exists for each modem managed by the agent."
  AUGMENTS
   { mdmIDEntry }
  ::= { mdmECTable 1 }

MdmECEntry ::= SEQUENCE {
  mdmECErrorControlUsed          OBJECT IDENTIFIER
```

```
}

mdmECErrorControlUsed OBJECT-TYPE
  SYNTAX      OBJECT IDENTIFIER
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "Indicates the error control method used during the current
        or previous call.  This shall be one of the values for error
        control protocols registered in the capabilities table for
        this modem.  If no error control protocol is in use, this
        object shall have the value '{0 0}'."
  REFERENCE   "V.58 errorControlActive"
  ::= { mdmECEntry 1 }

-- The modem Data Compression Group

mdmDCTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmDCEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The modem data compression table augments the modem ID
        table."
  ::= { mdmMIBObjects 10 }

mdmDCEntry OBJECT-TYPE
  SYNTAX      MdmDCEntry
   MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "Entries in this table are created only by the agent. One
        entry exists for each modem managed by the agent."
  AUGMENTS    { mdmIDEntry }
  ::= { mdmDCTable 1 }

MdmDCEntry ::= SEQUENCE {
  mdmDCCompressionTypeUsed        OBJECT IDENTIFIER
}

mdmDCCompressionTypeUsed OBJECT-TYPE
  SYNTAX      OBJECT IDENTIFIER
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "Indicates the data compression method used during the
        current or previous call.  This shall be one of the values
        for compression protocols registered in the capabilities
```

```
        table for this modem.  If no compression protocol is in use,
        this object shall have the value '{0 0}'."
  ::= { mdmDCEntry 1 }

-- The modem Signal Convertor Group

mdmSCTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmSCEntry
  MAX-ACCESS  not-accessible
  STATUS      current
   DESCRIPTION
        "The modem signal convertor table augments the modem ID
        table."
  ::= { mdmMIBObjects 11 }

mdmSCEntry OBJECT-TYPE
  SYNTAX      MdmSCEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "Entries in this table are created only by the agent. One
        entry exists for each modem managed by the agent."
  AUGMENTS    { mdmIDEntry }
  ::= { mdmSCTable 1 }

MdmSCEntry ::= SEQUENCE {
  mdmSCCurrentLineTransmitRate        Integer32,
  mdmSCCurrentLineReceiveRate         Integer32,
  mdmSCInitialLineTransmitRate        Integer32,
  mdmSCInitialLineReceiveRate         Integer32,
  mdmSCModulationSchemeUsed           OBJECT IDENTIFIER
}

mdmSCCurrentLineTransmitRate OBJECT-TYPE
  SYNTAX      Integer32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The current link transmit rate of a connection, or the last
        link transmit rate of the last connection
 in bits per
        second."
  REFERENCE   "V.58 transmissionSignallingRateActive"
  ::= { mdmSCEntry 1 }

mdmSCCurrentLineReceiveRate OBJECT-TYPE
  SYNTAX      Integer32
  MAX-ACCESS  read-only
```

```
  STATUS      current
  DESCRIPTION
        "The current link receive rate of a connection, or the last
        link receive rate of the last connection in bits per
        second."
  REFERENCE   "V.58 transmissionSignallingRateActive"
  ::= { mdmSCEntry 2 }

mdmSCInitialLineTransmitRate OBJECT-TYPE
  SYNTAX      Integer32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The initial link transmit rate of the current connection,
        or the initial link transmit rate of the last connection in
        bits per second."
  ::= { mdmSCEntry 3 }

mdmSCInitialLineReceiveRate OBJECT-TYPE
  SYNTAX      Integer32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The initial link receive rate of the
 current connection, or
        the initial link receive rate of the last connection in bits
        per second."
  ::= { mdmSCEntry 4 }

mdmSCModulationSchemeUsed OBJECT-TYPE
  SYNTAX      OBJECT IDENTIFIER
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The modulation scheme of the current or previous call.
        This shall be one of the values for modulation protocols
        registered in the capabilities table for this modem."
  REFERENCE   "V.58 gstnModulationSchemeActive"
  ::= { mdmSCEntry 5 }

-- The Modem Statistics Table

mdmStatsTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The modem statistics Table augments the modem ID table."
```

```
  ::= { mdmMIBObjects 12 }

mdmStatsEntry OBJECT-TYPE
  SYNTAX      MdmStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "Entries in this table are
 created only by the agent. One
        entry exists for each modem managed by the agent."
  AUGMENTS    { mdmIDEntry }
  ::= { mdmStatsTable 1 }

MdmStatsEntry ::= SEQUENCE {
  mdmStatsRingNoAnswers                 Counter32,
  mdmStatsIncomingConnectionFailures    Counter32,
  mdmStatsIncomingConnectionCompletions Counter32,
  mdmStatsFailedDialAttempts            Counter32,
  mdmStatsOutgoingConnectionFailures    Counter32,
  mdmStatsOutgoingConnectionCompletions Counter32,
  mdmStatsRetrains                      Counter32,
  mdmStats2400OrLessConnections         Counter32,
  mdmStats2400To14400Connections        Counter32,
  mdmStatsGreaterThan14400Connections   Counter32,
  mdmStatsErrorControlledConnections    Counter32,
  mdmStatsCompressedConnections         Counter32,
  mdmStatsCompressionEfficiency         Integer32,
  mdmStatsSentOctets                    Counter32,
  mdmStatsReceivedOctets
 Counter32,
  mdmStatsSentDataFrames                Counter32,
  mdmStatsReceivedDataFrames            Counter32,
  mdmStatsResentFrames                  Counter32,
  mdmStatsErrorFrames                   Counter32
}

mdmStatsRingNoAnswers OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of events in which ringing was detected but the
        call was not answered."
  ::= { mdmStatsEntry 1 }

mdmStatsIncomingConnectionFailures OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
```

```
  STATUS      current
  DESCRIPTION
        "The number of incoming connection requests that this modem
        answered in which it could not train with the other DCE."
  ::= { mdmStatsEntry 2 }

mdmStatsIncomingConnectionCompletions OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of incoming connection requests
 that this modem
        answered and successfully trained with the other DCE."
  ::= { mdmStatsEntry 3 }

mdmStatsFailedDialAttempts OBJECT-TYPE
      SYNTAX          Counter32
      MAX-ACCESS  read-only
      STATUS          current
      DESCRIPTION
            "The number of call attempts that failed because the modem
      didn't go off hook, or there was no dialtone."
      ::= { mdmStatsEntry 4 }

mdmStatsOutgoingConnectionFailures OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of outgoing calls from this modem which
        sucessfully went off hook and dialed, in which it could not
        train with the other DCE."
  ::= { mdmStatsEntry 5 }

mdmStatsOutgoingConnectionCompletions OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of outgoing calls from this modem which resulted

    in successfully training with the other DCE."
  ::= { mdmStatsEntry 6 }

mdmStatsRetrains OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
```

```
  STATUS      current
  DESCRIPTION
        "The number of retrains experienced on connections on this
        line."
  ::= { mdmStatsEntry 7 }


-- Utilization counters

mdmStats2400OrLessConnections OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of connections initially established at a
        modulation speed of 2400 bits per second or less."
  ::= { mdmStatsEntry 8 }


mdmStats2400To14400Connections OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of connections initially established at a
        modulation speed of greater than 2400 bits per second and
        less than 14400 bits per second."
  ::= { mdmStatsEntry 9 }

mdmStatsGreaterThan14400Connections
 OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of connections initially established at a
        modulation speed of greater than 14400 bits per second."
  ::= { mdmStatsEntry 10 }

mdmStatsErrorControlledConnections OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of established connections using an error
        control protocol."
  ::= { mdmStatsEntry 11 }
```

```
mdmStatsCompressedConnections OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of established connections using a compression
        protocol."
  ::= { mdmStatsEntry 12 }

mdmStatsCompressionEfficiency OBJECT-TYPE
  SYNTAX      Integer32 (0..65535)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of bytes transferred
 into the compression
        encoder divided by the number of bytes transferred out of
        the encoder, multiplied by 100 for either the current or
        last call.  If a data compression protocol is not in use,
        this value shall be `100'."
  REFERENCE   "V.58 compressionEfficiency"
  ::= { mdmStatsEntry 13 }

mdmStatsSentOctets OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of octets presented to the modem by the DTE."
  ::= { mdmStatsEntry 14 }

mdmStatsReceivedOctets OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of octets presented to the DTE by the modem."
  ::= { mdmStatsEntry 15 }

mdmStatsSentDataFrames OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of data frames sent on the line interface.  If

       there is no frame-oriented protocol in use on the line
        interface, this counter shall not increment."
```

```
  ::= { mdmStatsEntry 16 }

mdmStatsReceivedDataFrames OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of data frames received on the line interface.
        If there is no frame-oriented protocol in use on the line
        interface, this counter shall not increment."
  ::= { mdmStatsEntry 17 }

mdmStatsResentFrames OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of times this modem retransmits frames on the
        line interface.  If there is no frame-oriented protocol in
        use on the line interface, this counter shall not
        increment."
  ::= { mdmStatsEntry 18 }

mdmStatsErrorFrames OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
   DESCRIPTION
        "The number of block errors received on the link.  If there
        is no frame-oriented protocol in use on the line interface,
        this counter shall not increment."
  ::= { mdmStatsEntry 19 }


-- compliance statements

mdmCompliance MODULE-COMPLIANCE
  STATUS  current
  DESCRIPTION
        "The compliance statement for SNMPv2 entities which
        implement the modem MIB."

  MODULE  -- this module
     MANDATORY-GROUPS { mdmIDGroup, mdmLineInterfaceGroup,
          mdmDTEInterfaceGroup, mdmCallControlGroup,
          mdmSignalConvertorGroup, mdmStatisticsGroup }

     GROUP   mdmErrorControlGroup
```

```
        DESCRIPTION
            "This group is mandatory only for those modems that
            implement an error correction protocol."

        GROUP mdmDataCompressionGroup
        DESCRIPTION
            "This group is mandatory only for those modems that
            implement a data compression protocol."

    ::= { mdmCompliances 1 }


END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/Modem-MIB
No license file was found, but licenses were detected in source scan.

```
IANA-ITU-ALARM-TC-MIB DEFINITIONS ::= BEGIN

  IMPORTS
      MODULE-IDENTITY, mib-2       FROM SNMPv2-SMI
      TEXTUAL-CONVENTION           FROM SNMPv2-TC;

  ianaItuAlarmNumbers MODULE-IDENTITY
      LAST-UPDATED "200409090000Z"  -- September 09, 2004
      ORGANIZATION "IANA"
      CONTACT-INFO
          "Postal:    Internet Assigned Numbers Authority
                      Internet Corporation for Assigned Names
                      and Numbers
                      4676 Admiralty Way, Suite 330
                      Marina del Rey, CA 90292-6601
                      USA

          Tel:    +1  310-823-9358
          E-Mail: iana&iana.org"
      DESCRIPTION
          "The MIB module defines the ITU Alarm
          textual convention for objects expected to require
          regular extension.

          Copyright (C) The Internet Society (2004).  The
          initial version
    of this MIB module was published
          in RFC 3877. For full legal notices see the RFC
          itself. Supplementary information may be available on:
              http://www.ietf.org/copyrights/ianamib.html"
```

```
        REVISION    "200409090000Z"
        DESCRIPTION
            "Initial version, published as RFC 3877."
       ::= { mib-2 119 }


 IANAItuProbableCause ::= TEXTUAL-CONVENTION
     STATUS current
     DESCRIPTION
         "ITU-T probable cause values. Duplicate values defined in
          X.733 are appended with X733 to ensure syntactic uniqueness.
          Probable cause value 0 is reserved for special purposes.

          The Internet Assigned Number Authority (IANA) is responsible
          for the assignment of the enumerations in this TC.
          IANAItuProbableCause value of 0 is reserved for special
          purposes and MUST NOT be assigned.

          Values of IANAItuProbableCause in the range 1 to 1023 are
          reserved
for causes that correspond to ITU-T probable cause.

          All other requests for new causes will be handled on a
          first-come, first served basis and will be assigned
          enumeration values starting with 1025.

          Request should  come in the form of well-formed
          SMI [RFC2578] for enumeration names that are unique and
          sufficiently descriptive.

          While some effort will be taken to ensure that new probable
          causes do not conceptually duplicate existing probable
          causes it is acknowledged that the existence of conceptual
          duplicates in the starting probable cause list is an known
          industry reality.

          To aid IANA in the administration of probable cause names
          and values, the OPS Area Director will appoint one or more
          experts to help review requests.

          See http://www.iana.org"
     REFERENCE
         "ITU Recommendation M.3100,
'Generic Network Information
             Model', 1995
          ITU Recommendation X.733, 'Information Technology - Open
             Systems Interconnection - System Management: Alarm
             Reporting Function', 1992
```

```
        ITU Recommendation X.736, 'Information Technology - Open
          Systems Interconnection - System Management: Security
          Alarm Reporting Function', 1992"

    SYNTAX        INTEGER
          {
          -- The following probable causes were defined in M.3100
           aIS  (1),
           callSetUpFailure  (2),
           degradedSignal  (3),
           farEndReceiverFailure  (4),
           framingError  (5),
           lossOfFrame (6),
           lossOfPointer  (7),
           lossOfSignal  (8),
           payloadTypeMismatch (9),
           transmissionError (10),
           remoteAlarmInterface (11),
           excessiveBER  (12),

pathTraceMismatch  (13),
           unavailable  (14),
           signalLabelMismatch (15),
           lossOfMultiFrame (16),
           receiveFailure (17),
           transmitFailure (18),
           modulationFailure (19),
           demodulationFailure (20),
           broadcastChannelFailure (21),
           connectionEstablishmentError (22),
           invalidMessageReceived (23),
           localNodeTransmissionError (24),
           remoteNodeTransmissionError (25),
           routingFailure (26),
 --Values 27-50 are reserved for communications alarm related
 --probable causes
 -- The following are used with equipment alarm.
           backplaneFailure (51),
           dataSetProblem  (52),
           equipmentIdentifierDuplication  (53),
           externalIFDeviceProblem  (54),
           lineCardProblem (55),
           multiplexerProblem  (56),
           nEIdentifierDuplication
(57),
           powerProblem  (58),
           processorProblem  (59),
           protectionPathFailure  (60),
```

receiverFailure (61),
replaceableUnitMissing (62),
replaceableUnitTypeMismatch (63),
synchronizationSourceMismatch (64),
terminalProblem (65),
timingProblem (66),
transmitterFailure (67),
trunkCardProblem (68),
replaceableUnitProblem (69),
realTimeClockFailure (70),
--An equipment alarm to be issued if the system detects that the
--real time clock has failed
antennaFailure (71),
batteryChargingFailure (72),
diskFailure (73),
frequencyHoppingFailure (74),
iODeviceError (75),
lossOfSynchronisation (76),
lossOfRedundancy (77),
powerSupplyFailure (78),
signalQualityEvaluationFailure (79),
tranceiverFailure (80),
protectionMechanismFailure (81),
protectingResourceFailure (82),
-- Values 83-100 are reserved for equipment alarm related probable
-- causes
-- The following are used with environmental alarm.
airCompressorFailure (101),
airConditioningFailure (102),
airDryerFailure (103),
batteryDischarging (104),
batteryFailure (105),
commercialPowerFailure (106),
coolingFanFailure (107),
engineFailure (108),
fireDetectorFailure (109),
fuseFailure (110),
generatorFailure (111),
lowBatteryThreshold (112),
pumpFailure (113),
rectifierFailure (114),
rectifierHighVoltage (115),
rectifierLowFVoltage
(116),
ventilationsSystemFailure (117),
enclosureDoorOpen (118),
explosiveGas (119),
fire (120),

```
            flood   (121),
            highHumidity  (122),
            highTemperature  (123),
            highWind  (124),
            iceBuildUp  (125),
            intrusionDetection  (126),
            lowFuel  (127),
            lowHumidity  (128),
            lowCablePressure  (129),
            lowTemperatue  (130),
            lowWater  (131),
            smoke  (132),
            toxicGas  (133),
            coolingSystemFailure (134),
            externalEquipmentFailure (135),
            externalPointFailure (136),
  -- Values 137-150 are reserved for environmental alarm related
  -- probable causes
  -- The following are used with Processing error alarm.
            storageCapacityProblem (151),
            memoryMismatch  (152),

           corruptData  (153),
            outOfCPUCycles   (154),
            sfwrEnvironmentProblem  (155),
            sfwrDownloadFailure  (156),
            lossOfRealTimel (157),
  --A processing error alarm to be issued after the system has
  --reinitialised. This will indicate
  --to the management systems that the view they have of the managed
  --system may no longer
  --be valid. Usage example: The managed
  --system issues this alarm after a reinitialization with severity
  --warning to inform the
  --management system about the event. No clearing notification will
  --be sent.
            applicationSubsystemFailure (158),
            configurationOrCustomisationError (159),
            databaseInconsistency (160),
            fileError (161),
            outOfMemory (162),
            softwareError (163),
            timeoutExpired (164),
            underlayingResourceUnavailable (165),
            versionMismatch
(166),
  --Values 168-200 are reserved for processing error alarm related
  -- probable causes.
```

bandwidthReduced (201),
congestion (202),
excessiveErrorRate (203),
excessiveResponseTime (204),
excessiveRetransmissionRate (205),
reducedLoggingCapability (206),
systemResourcesOverload (207),
-- The following were defined X.733
adapterError (500),
applicationSubsystemFailture (501),
bandwidthReducedX733 (502),
callEstablishmentError (503),
communicationsProtocolError (504),
communicationsSubsystemFailure (505),
configurationOrCustomizationError (506),
congestionX733 (507),
coruptData (508),
cpuCyclesLimitExceeded (509),
dataSetOrModemError (510),
degradedSignalX733
(511),
dteDceInterfaceError (512),
enclosureDoorOpenX733 (513),
equipmentMalfunction (514),
excessiveVibration (515),
fileErrorX733 (516),
fireDetected (517),
framingErrorX733 (518),
heatingVentCoolingSystemProblem (519),
humidityUnacceptable (520),
inputOutputDeviceError (521),
inputDeviceError (522),
lanError (523),
leakDetected (524),
localNodeTransmissionErrorX733 (525),
lossOfFrameX733 (526),
lossOfSignalX733 (527),
materialSupplyExhausted (528),
multiplexerProblemX733 (529),
outOfMemoryX733 (530),
ouputDeviceError (531),
performanceDegraded (532),
powerProblems (533),
pressureUnacceptable (534),

processorProblems (535),
pumpFailureX733 (536),
queueSizeExceeded (537),

```
            receiveFailureX733 (538),
            receiverFailureX733 (539),
            remoteNodeTransmissionErrorX733 (540),
            resourceAtOrNearingCapacity (541),
            responseTimeExecessive (542),
            retransmissionRateExcessive (543),
            softwareErrorX733 (544),
            softwareProgramAbnormallyTerminated (545),
            softwareProgramError (546),
            storageCapacityProblemX733 (547),
            temperatureUnacceptable (548),
            thresholdCrossed (549),
            timingProblemX733 (550),
            toxicLeakDetected (551),
            transmitFailureX733 (552),
            transmiterFailure (553),
            underlyingResourceUnavailable (554),
            versionMismatchX733 (555),
            -- The following are defined in X.736

          authenticationFailure (600),
            breachOfConfidentiality (601),
            cableTamper (602),
            delayedInformation (603),
            denialOfService (604),
            duplicateInformation (605),
            informationMissing (606),
            informationModificationDetected (607),
            informationOutOfSequence (608),
            keyExpired (609),
            nonRepudiationFailure (610),
            outOfHoursActivity (611),
            outOfService (612),
            proceduralError (613),
            unauthorizedAccessAttempt (614),
            unexpectedInformation (615),

            other (1024)
            }

IANAItuEventType ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
          "The ITU event Type values.

          The Internet Assigned Number Authority (IANA) is
          responsible for the assignment of the enumerations
```

```
   in this TC.

           Request should  come in the form of well-formed
           SMI [RFC2578] for enumeration names that are unique
           and sufficiently descriptive.

           See http://www.iana.org "
     REFERENCE
          "ITU Recommendation X.736, 'Information Technology - Open
           Systems Interconnection - System Management: Security
           Alarm Reporting Function', 1992"
     SYNTAX        INTEGER
          {
          other (1),
          communicationsAlarm (2),
          qualityOfServiceAlarm (3),
          processingErrorAlarm (4),
          equipmentAlarm (5),
          environmentalAlarm (6),
          integrityViolation (7),
          operationalViolation (8),
          physicalViolation (9),
          securityServiceOrMechanismViolation (10),
          timeDomainViolation (11)
          }

  END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/iana/IANA-ITU-ALARM-TC-MIB
No license file was found, but licenses were detected in source scan.

SNMPv2-MIB DEFINITIONS ::= BEGIN

IMPORTS
   MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,
   TimeTicks, Counter32, snmpModules, mib-2
      FROM SNMPv2-SMI
   DisplayString, TestAndIncr, TimeStamp




      FROM SNMPv2-TC
   MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
      FROM SNMPv2-CONF;

snmpMIB MODULE-IDENTITY
   LAST-UPDATED "200210160000Z"
```

```
 ORGANIZATION "IETF SNMPv3 Working Group"
 CONTACT-INFO
       "WG-EMail:   snmpv3@lists.tislabs.com
        Subscribe:  snmpv3-request@lists.tislabs.com

        Co-Chair:   Russ Mundy
                    Network Associates Laboratories
        postal:     15204 Omega Drive, Suite 300
                    Rockville, MD 20850-4601
                    USA
        EMail:      mundy@tislabs.com
        phone:      +1 301 947-7107

        Co-Chair:   David Harrington
                    Enterasys
Networks
        postal:     35 Industrial Way
                    P. O. Box 5005
                    Rochester, NH 03866-5005
                    USA
        EMail:      dbh@enterasys.com
        phone:      +1 603 337-2614

        Editor:     Randy Presuhn
                    BMC Software, Inc.
        postal:     2141 North First Street
                    San Jose, CA 95131
                    USA
        EMail:      randy_presuhn@bmc.com
        phone:      +1 408 546-1006"
 DESCRIPTION
       "The MIB module for SNMP entities.

        Copyright (C) The Internet Society (2002). This
        version of this MIB module is part of RFC 3418;
        see the RFC itself for full legal notices.
       "
 REVISION      "200210160000Z"
 DESCRIPTION
       "This revision of this MIB module was published as
        RFC 3418."
 REVISION      "199511090000Z"
 DESCRIPTION
```

```
        "This revision of this MIB module was published as
         RFC 1907."
  REVISION      "199304010000Z"
  DESCRIPTION
        "The initial revision of this MIB module was published
        as RFC 1450."
  ::= { snmpModules 1 }

snmpMIBObjects OBJECT IDENTIFIER ::= { snmpMIB 1 }

--  ::= { snmpMIBObjects 1 }       this OID is obsolete
--  ::= { snmpMIBObjects 2 }       this OID is obsolete
--  ::= { snmpMIBObjects 3 }       this OID is obsolete

-- the System group
--
-- a collection of objects common to all managed systems.

system   OBJECT IDENTIFIER ::= { mib-2 1 }

sysDescr OBJECT-TYPE
  SYNTAX      DisplayString (SIZE (0..255))
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "A textual description of the entity.  This value should
        include the full name and version identification of
        the system's hardware type, software operating-system,
        and networking software."
  ::= { system 1 }

sysObjectID
 OBJECT-TYPE
  SYNTAX      OBJECT IDENTIFIER
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The vendor's authoritative identification of the
        network management subsystem contained in the entity.
        This value is allocated within the SMI enterprises
        subtree (1.3.6.1.4.1) and provides an easy and
        unambiguous means for determining `what kind of box' is
        being managed.  For example, if vendor `Flintstones,
        Inc.' was assigned the subtree 1.3.6.1.4.1.424242,
        it could assign the identifier 1.3.6.1.4.1.424242.1.1
        to its `Fred Router'."
  ::= { system 2 }
```

```
sysUpTime OBJECT-TYPE


  SYNTAX      TimeTicks
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The time (in hundredths of a second) since the
        network management portion of the system was last
        re-initialized."
  ::= { system 3 }

sysContact OBJECT-TYPE
   SYNTAX      DisplayString (SIZE (0..255))
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "The textual identification of the contact person for
        this managed node, together with information on how
        to contact this person.  If no contact information is
        known, the value is the zero-length string."
  ::= { system 4 }

sysName OBJECT-TYPE
  SYNTAX      DisplayString (SIZE (0..255))
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "An administratively-assigned name for this managed
        node.  By convention, this is the node's fully-qualified
        domain name.  If the name is unknown, the value is
        the zero-length string."
  ::= { system 5 }

sysLocation OBJECT-TYPE
  SYNTAX      DisplayString (SIZE (0..255))
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "The physical location of this node (e.g., 'telephone
        closet,
 3rd floor').  If the location is unknown, the
        value is the zero-length string."
  ::= { system 6 }

sysServices OBJECT-TYPE
  SYNTAX      INTEGER (0..127)
```

```
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "A value which indicates the set of services that this
        entity may potentially offer.  The value is a sum.



        This sum initially takes the value zero. Then, for
        each layer, L, in the range 1 through 7, that this node
        performs transactions for, 2 raised to (L - 1) is added
        to the sum.  For example, a node which performs only
        routing functions would have a value of 4 (2^(3-1)).
        In contrast, a node which is a host offering application
        services would have a value of 72 (2^(4-1) + 2^(7-1)).
        Note that in the context of the Internet suite of
        protocols, values should be calculated accordingly:

            layer     functionality
              1       physical (e.g., repeaters)
              2       datalink/subnetwork (e.g., bridges)
              3       internet (e.g., supports the IP)
              4       end-to-end  (e.g., supports the TCP)
              7       applications (e.g., supports the SMTP)

        For systems including OSI protocols, layers 5 and 6
        may also be counted."
  ::= { system 7 }

-- object resource information
--
-- a collection of objects which describe the SNMP entity's
-- (statically and dynamically configurable) support of
-- various MIB modules.

sysORLastChange OBJECT-TYPE
  SYNTAX     TimeStamp
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
        "The value of sysUpTime at the time of the most recent
        change in state or value of any instance of sysORID."
  ::= { system 8 }

sysORTable OBJECT-TYPE
  SYNTAX     SEQUENCE OF SysOREntry
  MAX-ACCESS not-accessible
  STATUS     current
```

```
    DESCRIPTION
            "The (conceptual) table listing the capabilities of
            the local SNMP application acting as a command
            responder with respect to various MIB modules.
            SNMP entities having dynamically-configurable support
            of MIB modules will have a dynamically-varying number
            of conceptual rows."
    ::= { system 9 }



sysOREntry OBJECT-TYPE
    SYNTAX      SysOREntry
    MAX-ACCESS not-accessible
    STATUS      current
    DESCRIPTION
            "An entry (conceptual row) in the sysORTable."
    INDEX       { sysORIndex }
    ::= { sysORTable 1 }

SysOREntry ::= SEQUENCE {
    sysORIndex      INTEGER,
    sysORID         OBJECT IDENTIFIER,
    sysORDescr      DisplayString,
    sysORUpTime     TimeStamp
}

sysORIndex OBJECT-TYPE
    SYNTAX      INTEGER (1..2147483647)
    MAX-ACCESS not-accessible
    STATUS      current
    DESCRIPTION
            "The auxiliary variable used for identifying instances
            of the columnar
 objects in the sysORTable."
    ::= { sysOREntry 1 }

sysORID OBJECT-TYPE
    SYNTAX      OBJECT IDENTIFIER
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
            "An authoritative identification of a capabilities
            statement with respect to various MIB modules supported
            by the local SNMP application acting as a command
            responder."
    ::= { sysOREntry 2 }
```

```
sysORDescr OBJECT-TYPE
  SYNTAX     DisplayString
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
        "A textual description of the capabilities identified
        by the corresponding instance of sysORID."
  ::= { sysOREntry 3 }

sysORUpTime OBJECT-TYPE
  SYNTAX     TimeStamp
  MAX-ACCESS read-only



  STATUS     current
  DESCRIPTION
        "The value of sysUpTime at the time this conceptual
        row was last instantiated."
  ::= { sysOREntry 4 }


-- the SNMP group
--
-- a collection of objects providing basic instrumentation
 and
-- control of an SNMP entity.

snmp     OBJECT IDENTIFIER ::= { mib-2 11 }

snmpInPkts OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
        "The total number of messages delivered to the SNMP
        entity from the transport service."
  ::= { snmp 1 }

snmpInBadVersions OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
        "The total number of SNMP messages which were delivered
        to the SNMP entity and were for an unsupported SNMP
        version."
  ::= { snmp 3 }
```

```
snmpInBadCommunityNames OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
        "The total number of community-based SNMP messages (for
        example,  SNMPv1) delivered to the SNMP entity which
        used an SNMP community name not known to said entity.
        Also, implementations which authenticate community-based
         SNMP messages using check(s) in addition to matching
        the community name (for example, by also checking
        whether the message originated from a transport address
        allowed to use a specified community name) MAY include
        in this value the number of messages which failed the
        additional check(s).  It is strongly RECOMMENDED that



        the documentation for any security model which is used
        to authenticate community-based SNMP messages specify
        the precise conditions that contribute to this value."
  ::= { snmp 4 }

snmpInBadCommunityUses OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
        "The total number of community-based SNMP messages (for
        example, SNMPv1) delivered to the SNMP entity which
        represented an SNMP operation that was not allowed for
        the SNMP community named in the message.  The precise
         conditions under which this counter is incremented
        (if at all) depend on how the SNMP entity implements
        its access control mechanism and how its applications
        interact with that access control mechanism.  It is
        strongly RECOMMENDED that the documentation for any
        access control mechanism which is used to control access
        to and visibility of MIB instrumentation specify the
        precise conditions that contribute to this value."
  ::= { snmp 5 }

snmpInASNParseErrs OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
```

"The total number of ASN.1 or BER errors encountered by
the SNMP entity when decoding received SNMP messages."
::= { snmp 6 }

snmpEnableAuthenTraps OBJECT-TYPE
SYNTAX INTEGER { enabled(1), disabled(2) }
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"Indicates whether the
SNMP entity is permitted to
generate authenticationFailure traps. The value of this
object overrides any configuration information; as such,
it provides a means whereby all authenticationFailure
traps may be disabled.

Note that it is strongly recommended that this object
be stored in non-volatile memory so that it remains
constant across re-initializations of the network
management system."

::= { snmp 30 }

snmpSilentDrops OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The total number of Confirmed Class PDUs (such as
GetRequest-PDUs, GetNextRequest-PDUs,
GetBulkRequest-PDUs, SetRequest-PDUs, and
InformRequest-PDUs) delivered to the SNMP entity which
were silently dropped because the size of a reply
containing an alternate Response Class PDU (such as a

Response-PDU) with an empty variable-bindings field
was greater than either a local constraint or the
maximum message size associated with the originator of
the request."
::= { snmp 31 }

snmpProxyDrops OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION

```
        "The total number of Confirmed Class PDUs
        (such as GetRequest-PDUs, GetNextRequest-PDUs,
        GetBulkRequest-PDUs, SetRequest-PDUs, and
        InformRequest-PDUs) delivered to the SNMP entity which
        were silently dropped because the transmission of
        the (possibly translated) message to a proxy target
        failed in a manner (other than a time-out) such that
        no Response Class PDU (such as a Response-PDU) could
        be returned."
  ::= { snmp 32 }

-- information for notifications
--
-- a collection of objects which allow the SNMP entity, when
-- supporting a notification
 originator application,
-- to be configured to generate SNMPv2-Trap-PDUs.

snmpTrap      OBJECT IDENTIFIER ::= { snmpMIBObjects 4 }

snmpTrapOID OBJECT-TYPE
  SYNTAX     OBJECT IDENTIFIER
  MAX-ACCESS accessible-for-notify
  STATUS     current
  DESCRIPTION



        "The authoritative identification of the notification
        currently being sent.  This variable occurs as
        the second varbind in every SNMPv2-Trap-PDU and
        InformRequest-PDU."
  ::= { snmpTrap 1 }

--  ::= { snmpTrap 2 }   this OID is obsolete

snmpTrapEnterprise OBJECT-TYPE
  SYNTAX     OBJECT IDENTIFIER
  MAX-ACCESS accessible-for-notify
  STATUS     current
  DESCRIPTION
        "The authoritative identification of the enterprise
        associated with the trap currently being sent.  When an
        SNMP proxy agent is mapping an RFC1157 Trap-PDU
        into a SNMPv2-Trap-PDU, this variable occurs as the
        last varbind."
  ::= { snmpTrap
```

```
 3 }

--  ::= { snmpTrap 4 }    this OID is obsolete


-- well-known traps

snmpTraps      OBJECT IDENTIFIER ::= { snmpMIBObjects 5 }

coldStart NOTIFICATION-TYPE
  STATUS  current
  DESCRIPTION
          "A coldStart trap signifies that the SNMP entity,
          supporting a notification originator application, is
          reinitializing itself and that its configuration may
          have been altered."
  ::= { snmpTraps 1 }

warmStart NOTIFICATION-TYPE
  STATUS  current
  DESCRIPTION
          "A warmStart trap signifies that the SNMP entity,
          supporting a notification originator application,
          is reinitializing itself such that its configuration
          is unaltered."
  ::= { snmpTraps 2 }

-- Note the linkDown NOTIFICATION-TYPE ::= { snmpTraps 3 }
-- and the linkUp NOTIFICATION-TYPE ::= { snmpTraps 4 }
-- are defined in RFC 2863 [RFC2863]



authenticationFailure NOTIFICATION-TYPE
  STATUS  current
  DESCRIPTION
          "An
 authenticationFailure trap signifies that the SNMP
           entity has received a protocol message that is not
           properly authenticated.  While all implementations
           of SNMP entities MAY be capable of generating this
           trap, the snmpEnableAuthenTraps object indicates
           whether this trap will be generated."
  ::= { snmpTraps 5 }

-- Note the egpNeighborLoss notification is defined
-- as { snmpTraps 6 } in RFC 1213
```

```
-- the set group
--
-- a collection of objects which allow several cooperating
-- command generator applications to coordinate their use of the
-- set operation.

snmpSet       OBJECT IDENTIFIER ::= { snmpMIBObjects 6 }

snmpSetSerialNo OBJECT-TYPE
  SYNTAX     TestAndIncr
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
          "An advisory lock used to allow several cooperating
          command generator applications to coordinate their
          use of the SNMP set operation.

          This
 object is used for coarse-grain coordination.
          To achieve fine-grain coordination, one or more similar
          objects might be defined within each MIB group, as
          appropriate."
  ::= { snmpSet 1 }

-- conformance information

snmpMIBConformance
            OBJECT IDENTIFIER ::= { snmpMIB 2 }

snmpMIBCompliances
            OBJECT IDENTIFIER ::= { snmpMIBConformance 1 }
snmpMIBGroups  OBJECT IDENTIFIER ::= { snmpMIBConformance 2 }

-- compliance statements




--    ::= { snmpMIBCompliances 1 }      this OID is obsolete
snmpBasicCompliance MODULE-COMPLIANCE
  STATUS  deprecated
  DESCRIPTION
          "The compliance statement for SNMPv2 entities which
          implement the SNMPv2 MIB.

          This compliance statement is replaced by
          snmpBasicComplianceRev2."
  MODULE  -- this module
```

```
      MANDATORY-GROUPS { snmpGroup, snmpSetGroup, systemGroup,
                         snmpBasicNotificationsGroup }

      GROUP   snmpCommunityGroup
       DESCRIPTION
         "This group is mandatory for SNMPv2 entities which
         support community-based authentication."

  ::= { snmpMIBCompliances 2 }

snmpBasicComplianceRev2 MODULE-COMPLIANCE
  STATUS  current
  DESCRIPTION
         "The compliance statement for SNMP entities which
         implement this MIB module."
  MODULE  -- this module
      MANDATORY-GROUPS { snmpGroup, snmpSetGroup, systemGroup,
                         snmpBasicNotificationsGroup }

      GROUP   snmpCommunityGroup
      DESCRIPTION
         "This group is mandatory for SNMP entities which
         support community-based authentication."

      GROUP   snmpWarmStartNotificationGroup
      DESCRIPTION
         "This group is mandatory for an SNMP entity which
         supports command responder applications, and is
         able to reinitialize itself such that its
         configuration is unaltered."

  ::= { snmpMIBCompliances
 3 }

-- units of conformance

--  ::= { snmpMIBGroups 1 }          this OID is obsolete
--  ::= { snmpMIBGroups 2 }          this OID is obsolete
--  ::= { snmpMIBGroups 3 }          this OID is obsolete



--  ::= { snmpMIBGroups 4 }          this OID is obsolete

snmpGroup OBJECT-GROUP
  OBJECTS { snmpInPkts,
            snmpInBadVersions,
            snmpInASNParseErrs,
```

```
            snmpSilentDrops,
            snmpProxyDrops,
            snmpEnableAuthenTraps }
    STATUS  current
    DESCRIPTION
            "A collection of objects providing basic instrumentation
            and control of an SNMP entity."
    ::= { snmpMIBGroups 8 }

snmpCommunityGroup OBJECT-GROUP
    OBJECTS { snmpInBadCommunityNames,
              snmpInBadCommunityUses }
    STATUS  current
    DESCRIPTION
            "A collection of objects providing basic instrumentation
            of a SNMP entity which supports community-based
            authentication."
    ::= { snmpMIBGroups 9 }

snmpSetGroup
 OBJECT-GROUP
    OBJECTS { snmpSetSerialNo }
    STATUS  current
    DESCRIPTION
            "A collection of objects which allow several cooperating
            command generator applications to coordinate their
            use of the set operation."
    ::= { snmpMIBGroups 5 }

systemGroup OBJECT-GROUP
    OBJECTS { sysDescr, sysObjectID, sysUpTime,
              sysContact, sysName, sysLocation,
              sysServices,
              sysORLastChange, sysORID,
              sysORUpTime, sysORDescr }
    STATUS  current
    DESCRIPTION
            "The system group defines objects which are common to all
            managed systems."
    ::= { snmpMIBGroups 6 }

snmpBasicNotificationsGroup NOTIFICATION-GROUP
    NOTIFICATIONS { coldStart, authenticationFailure }



    STATUS       current
    DESCRIPTION
```

```
      "The basic notifications implemented by an SNMP entity
       supporting command responder applications."
   ::= { snmpMIBGroups 7 }

snmpWarmStartNotificationGroup
 NOTIFICATION-GROUP
  NOTIFICATIONS { warmStart }
  STATUS        current
  DESCRIPTION
    "An additional notification for an SNMP entity supporting
    command responder applications, if it is able to reinitialize
    itself such that its configuration is unaltered."
 ::= { snmpMIBGroups 11 }

snmpNotificationGroup OBJECT-GROUP
   OBJECTS { snmpTrapOID, snmpTrapEnterprise }
   STATUS  current
   DESCRIPTION
           "These objects are required for entities
           which support notification originator applications."
   ::= { snmpMIBGroups 12 }

-- definitions in RFC 1213 made obsolete by the inclusion of a
-- subset of the snmp group in this MIB

snmpOutPkts OBJECT-TYPE
   SYNTAX      Counter32
   MAX-ACCESS  read-only
   STATUS      obsolete
   DESCRIPTION
           "The total number of SNMP Messages which were
           passed from the SNMP protocol entity to the
           transport service."
   ::= { snmp 2 }

-- { snmp 7 } is not used

snmpInTooBigs
 OBJECT-TYPE
   SYNTAX      Counter32
   MAX-ACCESS  read-only
   STATUS      obsolete
   DESCRIPTION
           "The total number of SNMP PDUs which were
           delivered to the SNMP protocol entity and for
           which the value of the error-status field was
           `tooBig'."
   ::= { snmp 8 }
```

```
snmpInNoSuchNames OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP PDUs which were
        delivered to the SNMP protocol entity and for
        which the value of the error-status field was
        `noSuchName'."
  ::= { snmp 9 }

snmpInBadValues OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP PDUs which were
        delivered to the SNMP protocol entity and for
        which the value of the error-status field was
        `badValue'."
  ::= { snmp 10 }

snmpInReadOnlys
 OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number valid SNMP PDUs which were delivered
        to the SNMP protocol entity and for which the value
        of the error-status field was `readOnly'.  It should
        be noted that it is a protocol error to generate an
        SNMP PDU which contains the value `readOnly' in the
        error-status field, as such this object is provided
        as a means of detecting incorrect implementations of
        the SNMP."
  ::= { snmp 11 }

snmpInGenErrs OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP PDUs which were delivered
        to the SNMP protocol entity and for which the value
```

```
        of the error-status field was `genErr'."
    ::= { snmp 12 }

snmpInTotalReqVars OBJECT-TYPE



    SYNTAX      Counter32
     MAX-ACCESS  read-only
    STATUS      obsolete
    DESCRIPTION
        "The total number of MIB objects which have been
        retrieved successfully by the SNMP protocol entity
        as the result of receiving valid SNMP Get-Request
        and Get-Next PDUs."
    ::= { snmp 13 }

snmpInTotalSetVars OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      obsolete
    DESCRIPTION
        "The total number of MIB objects which have been
        altered successfully by the SNMP protocol entity as
        the result of receiving valid SNMP Set-Request PDUs."
    ::= { snmp 14 }

snmpInGetRequests OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      obsolete
    DESCRIPTION
        "The total number of SNMP Get-Request PDUs which
        have been accepted and processed by the SNMP
        protocol entity."
    ::= { snmp 15 }

snmpInGetNexts OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS
   read-only
    STATUS      obsolete
    DESCRIPTION
        "The total number of SNMP Get-Next PDUs which have been
        accepted and processed by the SNMP protocol entity."
    ::= { snmp 16 }

snmpInSetRequests OBJECT-TYPE
```

```
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP Set-Request PDUs which
        have been accepted and processed by the SNMP protocol
        entity."
  ::= { snmp 17 }



snmpInGetResponses OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP Get-Response PDUs which
        have been accepted and processed by the SNMP protocol
        entity."
  ::= { snmp 18 }

snmpInTraps OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP Trap PDUs which have been
        accepted and
 processed by the SNMP protocol entity."
  ::= { snmp 19 }

snmpOutTooBigs OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP PDUs which were generated
        by the SNMP protocol entity and for which the value
        of the error-status field was `tooBig.'"
  ::= { snmp 20 }

snmpOutNoSuchNames OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP PDUs which were generated
        by the SNMP protocol entity and for which the value
```

```
        of the error-status was `noSuchName'."
  ::= { snmp 21 }

snmpOutBadValues OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP PDUs which were generated
        by the SNMP protocol entity and for which the value
        of the error-status field was
 `badValue'."
  ::= { snmp 22 }



-- { snmp 23 } is not used

snmpOutGenErrs OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP PDUs which were generated
        by the SNMP protocol entity and for which the value
        of the error-status field was `genErr'."
  ::= { snmp 24 }

snmpOutGetRequests OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP Get-Request PDUs which
        have been generated by the SNMP protocol entity."
  ::= { snmp 25 }

snmpOutGetNexts OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP Get-Next PDUs which have
        been generated by the SNMP protocol entity."
  ::= { snmp 26 }

snmpOutSetRequests OBJECT-TYPE
  SYNTAX      Counter32
```

```
  MAX-ACCESS  read-only
   STATUS      obsolete
  DESCRIPTION
          "The total number of SNMP Set-Request PDUs which
          have been generated by the SNMP protocol entity."
  ::= { snmp 27 }

snmpOutGetResponses OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
          "The total number of SNMP Get-Response PDUs which
          have been generated by the SNMP protocol entity."
  ::= { snmp 28 }




snmpOutTraps OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
          "The total number of SNMP Trap PDUs which have
          been generated by the SNMP protocol entity."
  ::= { snmp 29 }

snmpObsoleteGroup OBJECT-GROUP
  OBJECTS { snmpOutPkts, snmpInTooBigs, snmpInNoSuchNames,
            snmpInBadValues, snmpInReadOnlys, snmpInGenErrs,
            snmpInTotalReqVars, snmpInTotalSetVars,
            snmpInGetRequests, snmpInGetNexts, snmpInSetRequests,

    snmpInGetResponses, snmpInTraps, snmpOutTooBigs,
            snmpOutNoSuchNames, snmpOutBadValues,
            snmpOutGenErrs, snmpOutGetRequests, snmpOutGetNexts,
            snmpOutSetRequests, snmpOutGetResponses, snmpOutTraps
            }
  STATUS  obsolete
  DESCRIPTION
          "A collection of objects from RFC 1213 made obsolete
          by this MIB module."
  ::= { snmpMIBGroups 10 }

END
```

Found in path(s):

* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/SNMPv2-MIB
No license file was found, but licenses were detected in source scan.

```
SNMP-USM-DH-OBJECTS-MIB DEFINITIONS ::= BEGIN

IMPORTS
  MODULE-IDENTITY, OBJECT-TYPE,
  -- OBJECT-IDENTITY,
  experimental, Integer32
     FROM SNMPv2-SMI
  TEXTUAL-CONVENTION
     FROM SNMPv2-TC
  MODULE-COMPLIANCE, OBJECT-GROUP
     FROM SNMPv2-CONF
  usmUserEntry
     FROM SNMP-USER-BASED-SM-MIB
  SnmpAdminString
     FROM SNMP-FRAMEWORK-MIB;

snmpUsmDHObjectsMIB MODULE-IDENTITY
  LAST-UPDATED "200003060000Z"  -- 6 March 2000, Midnight
  ORGANIZATION "Excite@Home"
  CONTACT-INFO "Author: Mike StJohns
               Postal: Excite@Home
                    450 Broadway
                    Redwood City, CA 94063
               Email:  stjohns@corp.home.net
               Phone:  +1-650-556-5368"

  DESCRIPTION
     "The management information definitions for providing forward
  secrecy for key changes for the usmUserTable, and for providing a
  method
 for 'kickstarting' access to the agent via a Diffie-Helman
  key agreement."

  REVISION     "200003060000Z"
  DESCRIPTION
    "Initial version published as RFC 2786."



  ::= { experimental 101 }  -- IANA DHKEY-CHANGE 101

-- Administrative assignments

usmDHKeyObjects OBJECT IDENTIFIER ::= { snmpUsmDHObjectsMIB 1 }
usmDHKeyConformance OBJECT IDENTIFIER ::= { snmpUsmDHObjectsMIB 2 }
```

-- Textual conventions

DHKeyChange ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
"Upon initialization, or upon creation of a row containing an object of this type, and after any successful SET of this value, a GET of this value returns 'y' where y = g^xa MOD p, and where g is the base from usmDHParameters, p is the prime from usmDHParameters, and xa is a new random integer selected by the agent in the interval 2^(l-1) <= xa < 2^l < p-1. 'l' is the optional privateValueLength from usmDHParameters in bits. If 'l' is omitted,
then xa (and xr below) is selected in the interval 0 <= xa < p-1. y is expressed as an OCTET STRING 'PV' of length 'k' which satisfies

$$y = \sum_{i=1}^{k} 2^{(8(k-i))} PV'i$$

where PV1,...,PVk are the octets of PV from first to last, and where PV1 <> 0.

A successful SET consists of the value 'y' expressed as an OCTET STRING as above concatenated with the value 'z'(expressed as an OCTET STRING in the same manner as y) where z = g^xr MOD p, where g, p and l are as above, and where xr is a new random integer selected by the manager in the interval 2^(l-1) <= xr < 2^l < p-1. A SET to an object of this type will fail with the error wrongValue if the current 'y' does not match the 'y' portion of the value of the varbind for the object. (E.g. GET yout, SET concat(yin, z), yout <> yin).

Note that the private values xa and xr are never transmitted from manager to device or vice versa, only the values
y and z.
Obviously, these values must be retained until a successful SET on the associated object.

The shared secret 'sk' is calculated at the agent as sk = z^xa MOD p, and at the manager as sk = y^xr MOD p.

Each object definition of this type MUST describe how to map from the shared secret 'sk' to the operational key value used by the protocols and operations related to the object. In general, if n bits of key are required, the author suggests using the n right-most bits of the shared secret as the operational key value."

```
  REFERENCE
     "-- Diffie-Hellman Key-Agreement Standard, PKCS #3;
        RSA Laboratories, November 1993"
  SYNTAX            OCTET STRING

-- Diffie Hellman public values

usmDHPublicObjects      OBJECT IDENTIFIER ::= { usmDHKeyObjects 1 }

usmDHParameters OBJECT-TYPE
  SYNTAX  OCTET STRING
  MAX-ACCESS read-write
  STATUS  current
  DESCRIPTION
     "The public Diffie-Hellman parameters for doing
 a Diffie-Hellman
  key agreement for this device.  This is encoded as an ASN.1
  DHParameter per PKCS #3, section 9.  E.g.

     DHParameter ::= SEQUENCE {
        prime   INTEGER,   -- p
        base    INTEGER,   -- g
        privateValueLength  INTEGER OPTIONAL }


  Implementors are encouraged to use either the values from
  Oakley Group 1  or the values of from Oakley Group 2 as specified
  in RFC-2409, The Internet Key Exchange, Section 6.1, 6.2 as the
  default for this object.  Other values may be used, but the
  security properties of those values MUST be well understood and
  MUST meet the requirements of PKCS #3 for the selection of
  Diffie-Hellman primes.

     In addition, any time usmDHParameters changes, all values of
  type DHKeyChange will change and new random numbers MUST be
  generated by the agent for each DHKeyChange object."
  REFERENCE
     "-- Diffie-Hellman Key-Agreement Standard, PKCS #3,
        RSA Laboratories,
 November 1993
      -- The Internet Key Exchange, RFC 2409, November 1998,
        Sec 6.1, 6.2"
  ::= { usmDHPublicObjects 1 }

usmDHUserKeyTable OBJECT-TYPE
  SYNTAX  SEQUENCE OF UsmDHUserKeyEntry
  MAX-ACCESS not-accessible
  STATUS  current
```

```
  DESCRIPTION
     "This table augments and extends the usmUserTable and provides
  4 objects which exactly mirror the objects in that table with the
  textual convention of 'KeyChange'.  This extension allows key
  changes to be done in a manner where the knowledge of the current
  secret plus knowledge of the key change data exchanges (e.g. via
  wiretapping)  will not reveal the new key."
  ::= { usmDHPublicObjects 2 }

usmDHUserKeyEntry OBJECT-TYPE
  SYNTAX  UsmDHUserKeyEntry
  MAX-ACCESS not-accessible
  STATUS  current
  DESCRIPTION
     "A row of DHKeyChange objects which augment or replace the
  functionality of the KeyChange objects in the base table row."
  AUGMENTS { usmUserEntry }
   ::= {usmDHUserKeyTable 1 }

UsmDHUserKeyEntry ::= SEQUENCE {
     usmDHUserAuthKeyChange          DHKeyChange,
  usmDHUserOwnAuthKeyChange   DHKeyChange,
     usmDHUserPrivKeyChange          DHKeyChange,
     usmDHUserOwnPrivKeyChange       DHKeyChange
     }

usmDHUserAuthKeyChange OBJECT-TYPE
  SYNTAX  DHKeyChange
  MAX-ACCESS read-create
  STATUS  current
  DESCRIPTION
     "The object used to change any given user's Authentication Key
  using a Diffie-Hellman key exchange.

  The right-most n bits of the shared secret 'sk', where 'n' is the
  number of bits required for the protocol defined by
  usmUserAuthProtocol, are installed as the operational
  authentication key for this row after a successful SET."
  ::= { usmDHUserKeyEntry 1 }

usmDHUserOwnAuthKeyChange OBJECT-TYPE
  SYNTAX  DHKeyChange
  MAX-ACCESS read-create
  STATUS  current
  DESCRIPTION
     "The object used to change the agents own Authentication Key
  using a Diffie-Hellman
```

key exchange.

The right-most n bits of the shared secret 'sk', where 'n' is the number of bits required for the protocol defined by usmUserAuthProtocol, are installed as the operational authentication key for this row after a successful SET."
::= { usmDHUserKeyEntry 2 }

usmDHUserPrivKeyChange OBJECT-TYPE
SYNTAX DHKeyChange
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The object used to change any given user's Privacy Key using a Diffie-Hellman key exchange.

The right-most n bits of the shared secret 'sk', where 'n' is the number of bits required for the protocol defined by usmUserPrivProtocol, are installed as the operational privacy key for this row after a successful SET."
::= { usmDHUserKeyEntry 3 }

usmDHUserOwnPrivKeyChange OBJECT-TYPE
SYNTAX DHKeyChange
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The object used to change the agent's own Privacy Key using a Diffie-Hellman key exchange.

The right-most n bits of the shared secret 'sk', where 'n' is the number of bits required for the protocol defined by usmUserPrivProtocol, are installed as the operational privacy key for this row after a successful SET."
::= { usmDHUserKeyEntry 4 }

usmDHKickstartGroup OBJECT IDENTIFIER ::= { usmDHKeyObjects 2 }

usmDHKickstartTable OBJECT-TYPE
SYNTAX SEQUENCE OF UsmDHKickstartEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"A table of mappings between zero or more Diffie-Helman key agreement values and entries in the usmUserTable. Entries in this table are created by providing the associated device with a Diffie-Helman public value and a usmUserName/usmUserSecurityName pair during initialization. How these values are provided is

```
   outside the scope of this MIB, but could be provided manually, or
   through a configuration file.  Valid public value/name pairs
   result
  in the creation of a row in this table as well as the
   creation of an associated row (with keys derived as indicated) in
   the usmUserTable.  The actual access the related usmSecurityName
   has is dependent on the entries in the VACM tables.  In general,
   an implementor will specify one or more standard security names
   and will provide entries in the VACM tables granting various
   levels of access to those names.  The actual content of the VACM
   table is beyond the scope of this MIB.

   Note: This table is expected to be readable without authentication
   using the usmUserSecurityName 'dhKickstart'.  See the conformance
   statements for details."
   ::= { usmDHKickstartGroup 1 }

usmDHKickstartEntry OBJECT-TYPE
   SYNTAX      UsmDHKickstartEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION

      "An entry in the usmDHKickstartTable.  The agent SHOULD either
   delete this entry or mark it as inactive upon a successful SET of
    any of the KeyChange-typed objects in the usmUserEntry or upon a
   successful SET of any of the DHKeyChange-typed objects in the
   usmDhKeyChangeEntry where the related usmSecurityName (e.g. row of
   usmUserTable or row of ushDhKeyChangeTable) equals this entry's
   usmDhKickstartSecurityName.  In otherwords, once you've changed
   one or more of the keys for a row in usmUserTable with a
   particular security name, the row in this table with that same
   security name is no longer useful or meaningful."

   INDEX   { usmDHKickstartIndex }
   ::= {usmDHKickstartTable 1 }

UsmDHKickstartEntry ::= SEQUENCE  {
      usmDHKickstartIndex     Integer32,
      usmDHKickstartMyPublic  OCTET STRING,
      usmDHKickstartMgrPublic OCTET STRING,
      usmDHKickstartSecurityName      SnmpAdminString
      }

usmDHKickstartIndex OBJECT-TYPE
   SYNTAX      Integer32  (1..2147483647)
   MAX-ACCESS  not-accessible
   STATUS      current
```

```
  DESCRIPTION
      "Index value for
 this row."
  ::= { usmDHKickstartEntry 1 }

usmDHKickstartMyPublic OBJECT-TYPE
  SYNTAX      OCTET STRING
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The agent's Diffie-Hellman public value for this row.  At
  initialization, the agent generates a random number and derives
  its public value from that number.  This public value is published
  here.  This public value 'y' equals g^r MOD p where g is the from
  the set of Diffie-Hellman parameters, p is the prime from those
  parameters, and r is a random integer selected by the agent in the
  interval 2^(l-1) <= r < p-1 < 2^l.  If l is unspecified, then r is
  a random integer selected in the interval 0 <= r < p-1

  The public value is expressed as an OCTET STRING 'PV' of length
  'k' which satisfies

          k
      y =  SUM   2^(8(k-i)) PV'i
          i = 1

      where PV1,...,PVk are the octets of PV from first to last, and
      where PV1 != 0.


  The following
 DH parameters (Oakley group #2, RFC 2409, sec 6.1,
  6.2) are used for this object:

  g = 2
  p = FFFFFFFF FFFFFFFF C90FDAA2 2168C234 C4C6628B 80DC1CD1
     29024E08 8A67CC74 020BBEA6 3B139B22 514A0879 8E3404DD
     EF9519B3 CD3A431B 302B0A6D F25F1437 4FE1356D 6D51C245
     E485B576 625E7EC6 F44C42E9 A637ED6B 0BFF5CB6 F406B7ED
     EE386BFB 5A899FA5 AE9F2411 7C4B1FE6 49286651 ECE65381
     FFFFFFFF FFFFFFFF
  l=1024
  "
  REFERENCE
     "-- Diffie-Hellman Key-Agreement Standard, PKCS#3v1.4;
        RSA Laboratories, November 1993
      -- The Internet Key Exchange, RFC2409;
        Harkins, D., Carrel, D.; November 1998"
```

::= { usmDHKickstartEntry 2 }

usmDHKickstartMgrPublic OBJECT-TYPE
SYNTAX OCTET STRING
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"The manager's Diffie-Hellman public value for this row. Note that this value is not set via the SNMP agent, but may be set via some out of band
method, such as the device's configuration file.
The manager calculates this value in the same manner and using the same parameter set as the agent does. E.g. it selects a random number 'r', calculates y = g^r mod p and provides 'y' as the public number expressed as an OCTET STRING. See usmDHKickstartMyPublic for details.

When this object is set with a valid value during initialization, a row is created in the usmUserTable with the following values:

usmUserEngineID localEngineID
usmUserName [value of usmDHKickstartSecurityName]
usmUserSecurityName [value of usmDHKickstartSecurityName]
usmUserCloneFrom ZeroDotZero
usmUserAuthProtocol usmHMACMD5AuthProtocol
usmUserAuthKeyChange -- derived from set value
usmUserOwnAuthKeyChange -- derived from set value
usmUserPrivProtocol usmDESPrivProtocol
usmUserPrivKeyChange -- derived from set value
usmUserOwnPrivKeyChange -- derived from set value
usmUserPublic "
usmUserStorageType permanent
usmUserStatus active

A shared secret 'sk' is calculated at the agent as sk = mgrPublic^r mod p where r is the agents random number and p is the DH prime from the common parameters. The underlying privacy key for this row is derived from sk by applying the key derivation function PBKDF2 defined in PKCS#5v2.0 with a salt of 0xd1310ba6, and iterationCount of 500, a keyLength of 16 (for usmDESPrivProtocol), and a prf (pseudo random function) of 'id-hmacWithSHA1'. The underlying authentication key for this row is derived from sk by applying the key derivation function PBKDF2 with a salt of 0x98dfb5ac , an interation count of 500, a keyLength of 16 (for usmHMAC5AuthProtocol), and a prf of 'id-hmacWithSHA1'. Note: The salts are the first two words in the ks0 [key schedule 0] of the BLOWFISH

```
 cipher from 'Applied
  Cryptography' by Bruce Schnier - they could be any relatively
  random string of bits.

  The manager can use its knowledge of its own random number and the
  agent's public value to kickstart its access to the agent in a
  secure manner.  Note that the security of this approach is
  directly related to the strength of the authorization security of
  the out of band provisioning of the managers public value
  (e.g. the configuration file), but is not dependent at all on the
  strength of the confidentiality of the out of band provisioning
  data."
  REFERENCE
     "-- Password-Based Cryptography Standard, PKCS#5v2.0;
        RSA Laboratories, March 1999
      -- Applied Cryptography, 2nd Ed.; B. Schneier,
        Counterpane Systems; John Wiley & Sons, 1996"
  ::= { usmDHKickstartEntry 3 }

usmDHKickstartSecurityName OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The usmUserName and usmUserSecurityName in the usmUserTable
  associated with this row.  This is provided in the same manner and
  at the same time as the usmDHKickstartMgrPublic value -
  e.g. possibly manually, or via the device's configuration file."
  ::= { usmDHKickstartEntry 4 }

-- Conformance Information

usmDHKeyMIBCompliances  OBJECT IDENTIFIER ::= { usmDHKeyConformance 1 }
usmDHKeyMIBGroups       OBJECT IDENTIFIER ::= { usmDHKeyConformance 2 }

-- Compliance statements

usmDHKeyMIBCompliance   MODULE-COMPLIANCE
  STATUS      current
  DESCRIPTION
     "The compliance statement for this module."
  MODULE
     GROUP usmDHKeyMIBBasicGroup
     DESCRIPTION
     "This group MAY be implemented by any agent which
     implements the usmUserTable and which wishes to provide the
     ability to change user and agent authentication and privacy
     keys via Diffie-Hellman key exchanges."
```

GROUP usmDHKeyParamGroup
DESCRIPTION
"This group MUST be implemented by any agent which implements a MIB containing the DHKeyChange Textual Convention defined in this module."

GROUP usmDHKeyKickstartGroup
DESCRIPTION
"This group MAY be implemented by any agent which implements the usmUserTable and which wishes the ability to populate the USM table based on out-of-band provided DH ignition values.
Any agent implementing this group is expected to provide preinstalled entries in the vacm tables as follows:

In the usmUserTable: This entry allows access to the system and dhKickstart groups

usmUserEngineID localEngineID
usmUserName 'dhKickstart'
usmUserSecurityName 'dhKickstart'
usmUserCloneFrom ZeroDotZero
usmUserAuthProtocol none
usmUserAuthKeyChange "
usmUserOwnAuthKeyChange "
usmUserPrivProtocol
none
usmUserPrivKeyChange "
usmUserOwnPrivKeyChange "
usmUserPublic "
usmUserStorageType permanent
usmUserStatus active

In the vacmSecurityToGroupTable: This maps the initial user into the accessible objects.

vacmSecurityModel 3 (USM)
vacmSecurityName 'dhKickstart'
vacmGroupName 'dhKickstart'
vacmSecurityToGroupStorageType permanent
vacmSecurityToGroupStatus active

In the vacmAccessTable: Group name to view name translation.

vacmGroupName 'dhKickstart'
vacmAccessContextPrefix "
vacmAccessSecurityModel 3 (USM)

vacmAccessSecurityLevel noAuthNoPriv
vacmAccessContextMatch exact
vacmAccessReadViewName 'dhKickRestricted'
vacmAccessWriteViewName ''
vacmAccessNotifyViewName
'dhKickRestricted'
vacmAccessStorageType permanent
vacmAccessStatus active

In the vacmViewTreeFamilyTable: Two entries to allow the initial entry to access the system and kickstart groups.

vacmViewTreeFamilyViewName 'dhKickRestricted'
vacmViewTreeFamilySubtree 1.3.6.1.2.1.1 (system)
vacmViewTreeFamilyMask ''
vacmViewTreeFamilyType 1
vacmViewTreeFamilyStorageType permanent
vacmViewTreeFamilyStatus active

vacmViewTreeFamilyViewName 'dhKickRestricted'
vacmViewTreeFamilySubtree (usmDHKickstartTable OID)
vacmViewTreeFamilyMask ''
vacmViewTreeFamilyType 1
vacmViewTreeFamilyStorageType permanent
vacmViewTreeFamilyStatus active
"

OBJECT usmDHParameters
MIN-ACCESS read-only
DESCRIPTION
"It
is compliant to implement this object as read-only for
any device."

::= { usmDHKeyMIBCompliances 1 }

-- Units of Compliance

usmDHKeyMIBBasicGroup OBJECT-GROUP
OBJECTS {
usmDHUserAuthKeyChange,
usmDHUserOwnAuthKeyChange,
usmDHUserPrivKeyChange,
usmDHUserOwnPrivKeyChange
}
STATUS current
DESCRIPTION
""

```
  ::= { usmDHKeyMIBGroups 1 }

usmDHKeyParamGroup OBJECT-GROUP
  OBJECTS     {
                usmDHParameters
              }
  STATUS      current
  DESCRIPTION
      "The mandatory object for all MIBs which use the DHKeyChange
  textual convention."
  ::= { usmDHKeyMIBGroups 2 }

usmDHKeyKickstartGroup OBJECT-GROUP
  OBJECTS     {
                usmDHKickstartMyPublic,
                usmDHKickstartMgrPublic,
                usmDHKickstartSecurityName
              }
  STATUS      current
  DESCRIPTION
      "The objects used
 for kickstarting one or more SNMPv3 USM
  associations via a configuration file or other out of band,
  non-confidential access."
  ::= { usmDHKeyMIBGroups 3 }


END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/SNMP-USM-DH-OBJECTS-MIB
No license file was found, but licenses were detected in source scan.

DOT3-OAM-MIB DEFINITIONS ::= BEGIN

IMPORTS
  MODULE-IDENTITY, mib-2, OBJECT-TYPE, Counter32, Unsigned32,
    Integer32, NOTIFICATION-TYPE
    FROM SNMPv2-SMI
    -- from [RFC2578]
  TEXTUAL-CONVENTION, MacAddress, TimeStamp, TruthValue

    FROM SNMPv2-TC
    -- from [RFC2579]
  CounterBasedGauge64
    FROM HCNUM-TC
    -- from [RFC2856]
  ifIndex
```

```
  FROM IF-MIB
  -- from [RFC2863]
 MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
  FROM SNMPv2-CONF;



  -- from [RFC2580]

 dot3OamMIB MODULE-IDENTITY
  LAST-UPDATED "200706140000Z"  -- June 14,2007"
  ORGANIZATION
    "IETF Ethernet Interfaces and Hub MIB Working Group"
  CONTACT-INFO
    "WG Charter:
      http://www.ietf.org/html.charters/hubmib-charter.html
    Mailing lists:
      General Discussion: hubmib@ietf.org
      To Subscribe: hubmib-requests@ietf.org
      In Body: subscribe your_email_address
     Chair: Bert Wijnen
      Alcatel-Lucent
      Email: bwijnen at alcatel-lucent dot com
    Editor: Matt Squire
      Hatteras Networks
      E-mail: msquire at hatterasnetworks dot com
    "
  DESCRIPTION
    "The MIB module for managing the new Ethernet OAM features
    introduced by the Ethernet in the First Mile taskforce (IEEE
    802.3ah).  The functionality presented here is based on IEEE
    802.3ah [802.3ah], released in October, 2004.  [802.3ah] was
    prepared as an addendum to the standing version of IEEE 802.3
    [802.3-2002].  Since then, [802.3ah] has been
    merged into the base IEEE 802.3 specification in [802.3-2005].

    In particular, this MIB focuses on the new OAM functions
    introduced in Clause 57 of [802.3ah].  The OAM functionality
    of Clause 57 is controlled by new management attributes
    introduced in Clause 30 of [802.3ah].  The OAM functions are
    not specific to any particular Ethernet
physical layer, and
    can be generically applied to any Ethernet interface of
    [802.3-2002].

    An Ethernet OAM protocol data unit is a valid Ethernet frame
    with a destination MAC address equal to the reserved MAC
    address for Slow Protocols (See 43B of [802.3ah]), a
```

lengthOrType field equal to the reserved type for Slow Protocols, and a Slow Protocols subtype equal to that of the subtype reserved for Ethernet OAM. OAMPDU is used throughout this document as an abbreviation for Ethernet OAM protocol data unit.

The following reference is used throughout this MIB module:

[802.3ah] refers to:
IEEE Std 802.3ah-2004: 'Draft amendment to - Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications - Media Access Control Parameters, Physical Layers and Management Parameters for subscriber access networks', October 2004.

[802.3-2002] refers to:
IEEE Std 802.3-2002:
'Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications - Media Access Control Parameters, Physical Layers and Management Parameters for subscriber access networks', March 2002.

[802.3-2005] refers to:
IEEE Std 802.3-2005:
'Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks
- Specific requirements - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications - Media Access Control Parameters, Physical Layers and Management Parameters for subscriber access networks', December 2005.

[802-2001] refers to:
'IEEE Standard for LAN/MAN (Local Area Network/Metropolitan Area Network): Overview and

```
      Architecture', IEEE 802, June 2001.

   Copyright (c) The IETF Trust (2007).  This version of
   this MIB module is part of RFC 4878; See the RFC itself for
   full legal notices. "

  REVISION    "200706140000Z"  -- June 14, 2007"
  DESCRIPTION "Initial version, published as RFC 4878."
   ::= { mib-2 158 }

--
-- Sections of the Ethernet OAM MIB



--
   dot3OamNotifications OBJECT IDENTIFIER ::= { dot3OamMIB 0 }
   dot3OamObjects       OBJECT IDENTIFIER ::= { dot3OamMIB 1 }

  dot3OamConformance   OBJECT IDENTIFIER ::= { dot3OamMIB 2 }

--
-- Textual conventions for the OAM MIB
--
EightOTwoOui ::= TEXTUAL-CONVENTION
  STATUS       current
  DESCRIPTION
    "24-bit Organizationally Unique Identifier.  Information on
    OUIs can be found in IEEE 802-2001 [802-2001], Clause 9."
  SYNTAX       OCTET STRING(SIZE(3))

-- ****************************************************************
--
-- Ethernet OAM Control group
--

dot3OamTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF Dot3OamEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains the primary controls and status for the
    OAM capabilities of an Ethernet-like interface.  There will be
    one row in this table for each Ethernet-like interface in the
    system that supports the OAM functions defined in [802.3ah].
    "
  ::= { dot3OamObjects 1 }
```

```
dot3OamEntry OBJECT-TYPE
  SYNTAX     Dot3OamEntry
   MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "An entry in the table that contains information on the
    Ethernet OAM function for a single Ethernet like interface.
    Entries in the table are created automatically for each
    interface supporting Ethernet OAM.  The status of the row
    entry can be determined from dot3OamOperStatus.

    A dot3OamEntry is indexed in the dot3OamTable by the ifIndex
    object of the Interfaces MIB.
    "
  INDEX       { ifIndex }
  ::= { dot3OamTable 1 }



Dot3OamEntry ::=
  SEQUENCE {
    dot3OamAdminState               INTEGER,
    dot3OamOperStatus               INTEGER,
    dot3OamMode                     INTEGER,
    dot3OamMaxOamPduSize            Unsigned32,
    dot3OamConfigRevision           Unsigned32,
    dot3OamFunctionsSupported       BITS
  }

dot3OamAdminState OBJECT-TYPE
  SYNTAX      INTEGER {
                enabled(1),
                 disabled(2)
               }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "This object is used to provision the default administrative
    OAM mode for this interface.  This object represents the
    desired state of OAM for this interface.

    The dot3OamAdminState always starts in the disabled(2) state
    until an explicit management action or configuration
    information retained by the system causes a transition to the
    enabled(1) state.  When enabled(1), Ethernet OAM will attempt
    to operate over this interface.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.2"
```

```
  ::= { dot3OamEntry 1 }

 dot3OamOperStatus OBJECT-TYPE
  SYNTAX      INTEGER {
                disabled(1),
                linkFault(2),
                passiveWait(3),
                activeSendLocal(4),
                sendLocalAndRemote(5),
                sendLocalAndRemoteOk(6),
                oamPeeringLocallyRejected(7),
                 oamPeeringRemotelyRejected(8),
                operational(9),
                nonOperHalfDuplex(10)
              }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "At initialization and failure conditions, two OAM entities on



    the same full-duplex Ethernet link begin a discovery phase to
    determine what OAM capabilities may be used on that link.  The
    progress of this initialization is controlled by the OA
    sublayer.

    This value is always disabled(1) if OAM is disabled on this
    interface via the dot3OamAdminState.

    If the link has detected a fault and is transmitting OAMPDUs
    with a link fault indication, the value is linkFault(2).
    Also, if the interface is not operational (ifOperStatus is
    not up(1)), linkFault(2) is returned.  Note that the object
    ifOperStatus may not be up(1) as a result of link failure or
    administrative
action (ifAdminState being down(2) or
    testing(3)).

    The passiveWait(3) state is returned only by OAM entities in
    passive mode (dot3OamMode) and reflects the state in which the
    OAM entity is waiting to see if the peer device is OA
    capable.  The activeSendLocal(4) value is used by active mode
    devices (dot3OamMode) and reflects the OAM entity actively
    trying to discover whether the peer has OAM capability but has
    not yet made that determination.

    The state sendLocalAndRemote(5) reflects that the local OA
```

entity has discovered the peer but has not yet accepted or
rejected the configuration of the peer. The local device can,
for whatever reason, decide that the peer device is
unacceptable and decline OAM peering. If the local OAM entity
rejects the peer OAM entity, the state becomes
oamPeeringLocallyRejected(7). If the OAM peering is allowed
by the local device, the state moves
to
sendLocalAndRemoteOk(6). Note that both the
sendLocalAndRemote(5) and oamPeeringLocallyRejected(7) states
fall within the state SEND_LOCAL_REMOTE of the Discovery state
diagram [802.3ah, Figure 57-5], with the difference being
whether the local OAM client has actively rejected the peering
or has just not indicated any decision yet. Whether a peering
decision has been made is indicated via the local flags field
in the OAMPDU (reflected in the aOAMLocalFlagsField of
30.3.6.1.10).

If the remote OAM entity rejects the peering, the state
becomes oamPeeringRemotelyRejected(8). Note that both the
sendLocalAndRemoteOk(6) and oamPeeringRemotelyRejected(8)
states fall within the state SEND_LOCAL_REMOTE_OK of the
Discovery state diagram [802.3ah, Figure 57-5], with the
difference being whether the remote OAM client has rejected

the peering or has just not yet decided. This
is indicated
via the remote flags field in the OAMPDU (reflected in the
aOAMRemoteFlagsField of 30.3.6.1.11).

When the local OAM entity learns that both it and the remote
OAM entity have accepted the peering, the state moves to
operational(9) corresponding to the SEND_ANY state of the
Discovery state diagram [802.3ah, Figure 57-5].

Since Ethernet OAM functions are not designed to work
completely over half-duplex interfaces, the value
nonOperHalfDuplex(10) is returned whenever Ethernet OAM is
enabled (dot3OamAdminState is enabled(1)), but the interface
is in half-duplex operation.
"
REFERENCE "[802.3ah], 30.3.6.1.4, 30.3.6.1.10, 30.3.6.1.11"
::= { dot3OamEntry 2 }

dot3OamMode OBJECT-TYPE
SYNTAX INTEGER {

```
            passive(1),
            active(2)
           }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "This object configures
the mode of OAM operation for this
    Ethernet-like interface.  OAM on Ethernet interfaces may be in
    'active' mode or 'passive' mode.  These two modes differ in
    that active mode provides additional capabilities to initiate
    monitoring activities with the remote OAM peer entity, while
    passive mode generally waits for the peer to initiate OA
    actions with it.  As an example, an active OAM entity can put
    the remote OAM entity in a loopback state, where a passive OA
    entity cannot.

    The default value of dot3OamMode is dependent on the type of
    system on which this Ethernet-like interface resides.  The
    default value should be 'active(2)' unless it is known that
    this system should take on a subservient role to the other
    device connected over this interface.

    Changing this value results in incrementing the configuration
    revision field of locally generated OAMPDUs (30.3.6.1.12) and
    potentially
re-doing the OAM discovery process if the
    dot3OamOperStatus was already operational(9).
    "
  REFERENCE   "[802.3ah], 30.3.6.1.3"



  ::= { dot3OamEntry 3 }

 dot3OamMaxOamPduSize OBJECT-TYPE
  SYNTAX      Unsigned32 (64..1518)
  UNITS       "octets"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The largest OAMPDU that the OAM entity supports.  OA
    entities exchange maximum OAMPDU sizes and negotiate to use
    the smaller of the two maximum OAMPDU sizes between the peers.
    This value is determined by the local implementation.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.8"
  ::= { dot3OamEntry 4 }
```

```
 dot3OamConfigRevision OBJECT-TYPE
  SYNTAX      Unsigned32(0..65535)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The configuration revision of the OAM entity as reflected in
    the latest OAMPDU sent by the OAM entity.  The config revision
    is used by OAM entities
to indicate that configuration changes
    have occurred, which might require the peer OAM entity to
    re-evaluate whether OAM peering is allowed.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.12"
  ::= { dot3OamEntry 5 }

 dot3OamFunctionsSupported OBJECT-TYPE
  SYNTAX      BITS {
                unidirectionalSupport (0),
                loopbackSupport(1),
                eventSupport(2),
                variableSupport(3)
              }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The OAM functions supported on this Ethernet-like interface.
    OAM consists of separate functional sets beyond the basic
    discovery process that is always required.  These functional
    groups can be supported independently by any implementation.
    These values are communicated to the peer via the local
    configuration field of Information OAMPDUs.

    Setting 'unidirectionalSupport(0)' indicates that the
OA
```

```
    entity supports the transmission of OAMPDUs on links that are
    operating in unidirectional mode (traffic flowing in one
    direction only).  Setting 'loopbackSupport(1)' indicates that
    the OAM entity can initiate and respond to loopback commands.
    Setting 'eventSupport(2)' indicates that the OAM entity can
    send and receive Event Notification OAMPDUs.  Setting
    'variableSupport(3)' indicates that the OAM entity can send
    and receive Variable Request and Response OAMPDUs.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.6"
```

```
  ::= { dot3OamEntry 6 }

-- ****************************************************************
--
-- Ethernet OAM Peer group
--

dot3OamPeerTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF Dot3OamPeerEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains information about the OAM peer for a
    particular Ethernet-like interface.  OAM entities communicate
     with a single OAM peer entity on Ethernet links on which OA
    is enabled and operating properly.  There is one entry in this
    table for each entry in the dot3OamTable for which information
    on the peer OAM entity is available.
    "
  ::= { dot3OamObjects 2 }

dot3OamPeerEntry OBJECT-TYPE
  SYNTAX      Dot3OamPeerEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An entry in the table containing information on the peer OA
    entity for a single Ethernet-like interface.

    Note that there is at most one OAM peer for each Ethernet-like
    interface.  Entries are automatically created when information
    about the OAM peer entity becomes available, and automatically
    deleted when the OAM peer entity is no longer in
    communication.  Peer information is not available when
    dot3OamOperStatus is disabled(1), linkFault(2),
    passiveWait(3), activeSendLocal(4), or nonOperHalfDuplex(10).
     "
  INDEX       { ifIndex }



  ::= { dot3OamPeerTable 1 }

Dot3OamPeerEntry ::=
  SEQUENCE {
    dot3OamPeerMacAddress          MacAddress,
    dot3OamPeerVendorOui           EightOTwoOui,
    dot3OamPeerVendorInfo          Unsigned32,
```

```
    dot3OamPeerMode                 INTEGER,
    dot3OamPeerMaxOamPduSize        Unsigned32,
    dot3OamPeerConfigRevision       Unsigned32,
    dot3OamPeerFunctionsSupported   BITS
   }

 dot3OamPeerMacAddress OBJECT-TYPE
   SYNTAX      MacAddress
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
     "The MAC address of the peer OAM entity.  The MAC address is
     derived from the most recently received OAMPDU.
     "
   REFERENCE   "[802.3ah], 30.3.6.1.5."
   ::= { dot3OamPeerEntry 1 }

 dot3OamPeerVendorOui OBJECT-TYPE
   SYNTAX      EightOTwoOui
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
     "The
 OUI of the OAM peer as reflected in the latest
     Information OAMPDU received with a Local Information TLV.  The
     OUI can be used to identify the vendor of the remote OA
     entity.  This value is initialized to three octets of zero
     before any Local Information TLV is received.
     "
   REFERENCE   "[802.3ah], 30.3.6.1.16."
   ::= { dot3OamPeerEntry 2 }

 dot3OamPeerVendorInfo OBJECT-TYPE
   SYNTAX      Unsigned32
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
     "The Vendor Info of the OAM peer as reflected in the latest
     Information OAMPDU received with a Local Information TLV.
     The semantics of the Vendor Information field is proprietary
     and specific to the vendor (identified by the
     dot3OamPeerVendorOui).  This information could, for example,



     be used to identify a specific product or product family.
     This value is initialized to zero before any Local
     Information TLV is received.
```

```
    "
  REFERENCE   "[802.3ah], 30.3.6.1.17."
  ::= { dot3OamPeerEntry 3 }

 dot3OamPeerMode OBJECT-TYPE
  SYNTAX      INTEGER {
                passive(1),
                active(2),
                unknown(3)
              }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The mode of the OAM peer as reflected in the latest
    Information OAMPDU received with a Local Information TLV.  The
    mode of the peer can be determined from the Configuration
    field in the Local Information TLV of the last Information
    OAMPDU received from the peer.  The value is unknown(3)
    whenever no Local Information TLV has been received.  The
    values of active(2) and passive(1) are returned when a Local
    Information TLV has been received indicating that the peer is
    in active or passive mode, respectively.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.7."
  ::= { dot3OamPeerEntry 4 }

 dot3OamPeerMaxOamPduSize
OBJECT-TYPE
  SYNTAX      Unsigned32 (0 | 64..1518)
  UNITS       "octets"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The maximum size of OAMPDU supported by the peer as reflected
    in the latest Information OAMPDU received with a Local
    Information TLV.  Ethernet OAM on this interface must not use
    OAMPDUs that exceed this size.  The maximum OAMPDU size can be
    determined from the PDU Configuration field of the Local
    Information TLV of the last Information OAMPDU received from
    the peer.  A value of zero is returned if no Local Information
    TLV has been received.  Otherwise, the value of the OAM peer's
    maximum OAMPDU size is returned in this value.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.9."
  ::= { dot3OamPeerEntry 5 }
```

```
 dot3OamPeerConfigRevision OBJECT-TYPE
   SYNTAX      Unsigned32(0..65535)
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
     "The
configuration revision of the OAM peer as reflected in
     the latest OAMPDU.  This attribute is changed by the peer
     whenever it has a local configuration change for Ethernet OA
     on this interface.  The configuration revision can be
     determined from the Revision field of the Local Information
     TLV of the most recently received Information OAMPDU with
     a Local Information TLV.  A value of zero is returned if
     no Local Information TLV has been received.
   "
   REFERENCE   "[802.3ah], 30.3.6.1.13."
   ::= { dot3OamPeerEntry 6 }

 dot3OamPeerFunctionsSupported OBJECT-TYPE
   SYNTAX      BITS {
                 unidirectionalSupport (0),
                 loopbackSupport(1),
                 eventSupport(2),
                 variableSupport(3)
               }
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
     "The OAM functions supported on this Ethernet-like interface.
     OAM consists of separate functionality
sets above the basic
     discovery process.  This value indicates the capabilities of
     the peer OAM entity with respect to these functions.  This
     value is initialized so all bits are clear.

     If unidirectionalSupport(0) is set, then the peer OAM entity
     supports sending OAM frames on Ethernet interfaces when the
     receive path is known to be inoperable.  If
     loopbackSupport(1) is set, then the peer OAM entity can send
     and receive OAM loopback commands.  If eventSupport(2) is set,
     then the peer OAM entity can send and receive event OAMPDUs to
     signal various error conditions.  If variableSupport(3) is
     set, then the peer OAM entity can send and receive variable
     requests to monitor the attribute value as described in Clause
     57 of [802.3ah].

     The capabilities of the OAM peer can be determined from the
```

configuration field of the Local Information TLV of the most
recently received
Information OAMPDU with a Local Information
TLV. All zeros are returned if no Local Information TLV has

yet been received.
"
REFERENCE "[802.3ah], REFERENCE 30.3.6.1.7."
::= { dot3OamPeerEntry 7 }

-- **
--
-- Ethernet OAM Loopback group
--

dot3OamLoopbackTable OBJECT-TYPE
SYNTAX SEQUENCE OF Dot3OamLoopbackEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"This table contains controls for the loopback state of the
local link as well as indicates the status of the loopback
function. There is one entry in this table for each entry in
dot3OamTable that supports loopback functionality (where
dot3OamFunctionsSupported includes the loopbackSupport bit
set).

Loopback can be used to place the remote OAM entity in a state
where every received frame (except OAMPDUs) is echoed back

over the same interface on which they were received. In this
state, at the remote entity, 'normal' traffic is disabled as
only the looped back frames are transmitted on the interface.
Loopback is thus an intrusive operation that prohibits normal
data flow and should be used accordingly.
"
::= { dot3OamObjects 3 }

dot3OamLoopbackEntry OBJECT-TYPE
SYNTAX Dot3OamLoopbackEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"An entry in the table, containing information on the loopback
status for a single Ethernet-like interface. Entries in the
table are automatically created whenever the local OAM entity

```
    supports loopback capabilities.  The loopback status on the
    interface can be determined from the dot3OamLoopbackStatus
    object.
    "
  INDEX      { ifIndex }
  ::= { dot3OamLoopbackTable 1 }

 Dot3OamLoopbackEntry ::=



  SEQUENCE {
    dot3OamLoopbackStatus
         INTEGER,
    dot3OamLoopbackIgnoreRx          INTEGER
  }

 dot3OamLoopbackStatus OBJECT-TYPE
  SYNTAX     INTEGER {
              -- all values, except where noted, can be read
              -- but cannot be written
              noLoopback (1),

              -- initiatingLoopback can be read or written
              initiatingLoopback (2),
              remoteLoopback (3),

              -- terminatingLoopback can be read or written
              terminatingLoopback (4),
              localLoopback (5),
              unknown (6)
             }
  MAX-ACCESS  read-write
  STATUS     current
  DESCRIPTION
    "The loopback status of the OAM entity.  This status is
    determined by a combination of the local parser and
    multiplexer states, the remote parser and multiplexer states,
    as well as by the actions of the local OAM client.  When
    operating in normal mode
with no loopback in progress, the
    status reads noLoopback(1).

    The values initiatingLoopback(2) and terminatingLoopback(4)
    can be read or written.  The other values can only be read -
    they can never be written.  Writing initiatingLoopback causes
    the local OAM entity to start the loopback process with its
    peer.  This value can only be written when the status is
```

noLoopback(1). Writing the value initiatingLoopback(2) in any other state has no effect. When in remoteLoopback(3), writing terminatingLoopback(4) causes the local OAM entity to initiate the termination of the loopback state. Writing terminatingLoopack(4) in any other state has no effect.

If the OAM client initiates a loopback and has sent a Loopback OAMPDU and is waiting for a response, where the local parser and multiplexer states are DISCARD (see [802.3ah, 57.2.11.1]), the status is 'initiatingLoopback'. In this

case, the local OAM entity has yet to receive any acknowledgment that the remote OAM entity has received its loopback command request.

If the local OAM client knows that the remote OAM entity is in loopback mode (via the remote state information as described in [802.3ah, 57.2.11.1, 30.3.6.1.15]), the status is remoteLoopback(3). If the local OAM client is in the process of terminating the remote loopback [802.3ah, 57.2.11.3, 30.3.6.1.14] with its local multiplexer and parser states in DISCARD, the status is terminatingLoopback(4). If the remote OAM client has put the local OAM entity in loopback mode as indicated by its local parser state, the status is localLoopback(5).

The unknown(6) status indicates that the parser and multiplexer combination is unexpected. This status may be returned if the OAM loopback is in a transition state but should not persist.

The values of this attribute correspond to the following values of the local and remote parser and multiplexer states.

value	LclPrsr	LclMux	RmtPrsr	RmtMux
noLoopback	FWD	FWD	FWD	FWD
initLoopback	DISCARD	DISCARD	FWD	FWD
rmtLoopback	DISCARD	FWD	LPBK	DISCARD
tmtngLoopback	DISCARD	DISCARD	LPBK	DISCARD
lclLoopback	LPBK	DISCARD	DISCARD	FWD
unknown	***	any other combination	***	

"

REFERENCE "[802.3ah], REFERENCE 57.2.11, 30.3.61.14, 30.3.6.1.15"

```
  ::= { dot3OamLoopbackEntry 1 }

 dot3OamLoopbackIgnoreRx OBJECT-TYPE
  SYNTAX      INTEGER { ignore(1), process(2) }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "Since OAM loopback is a disruptive operation (user traffic
    does not pass), this attribute provides a mechanism to provide
    controls
over whether received OAM loopback commands are
    processed or ignored.  When the value is ignore(1), received
    loopback commands are ignored.  When the value is process(2),
    OAM loopback commands are processed.  The default value is to
    ignore loopback commands (ignore(1)).
    "
  REFERENCE   "[802.3ah], REFERENCE 57.2.11, 30.3.61.14,
    30.3.6.1.15"
  ::= { dot3OamLoopbackEntry 2 }



 -- ****************************************************************
 --
 -- Ethernet OAM Statistics group
 --

 dot3OamStatsTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF Dot3OamStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains statistics for the OAM function on a
    particular Ethernet-like interface.  There is an entry in the
    table for every entry in the dot3OamTable.

    The counters in this table are defined as 32-bit entries to
    match the counter size as defined in [802.3ah].
Given that
    the OA protocol is a slow protocol, the counters increment at
    a slow rate.
    "
  ::= { dot3OamObjects 4 }

 dot3OamStatsEntry OBJECT-TYPE
  SYNTAX      Dot3OamStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
```

```
  DESCRIPTION
    "An entry in the table containing statistics information on
    the Ethernet OAM function for a single Ethernet-like
    interface.  Entries are automatically created for every entry
    in the dot3OamTable.  Counters are maintained across
    transitions in dot3OamOperStatus.
    "
  INDEX       { ifIndex }
  ::= { dot3OamStatsTable 1 }

 Dot3OamStatsEntry ::=
  SEQUENCE {
          dot3OamInformationTx              Counter32,
          dot3OamInformationRx              Counter32,
          dot3OamUniqueEventNotificationTx    Counter32,
          dot3OamUniqueEventNotificationRx    Counter32,
          dot3OamDuplicateEventNotificationTx
Counter32,
          dot3OamDuplicateEventNotificationRx Counter32,
          dot3OamLoopbackControlTx          Counter32,
          dot3OamLoopbackControlRx          Counter32,
          dot3OamVariableRequestTx          Counter32,
          dot3OamVariableRequestRx          Counter32,
          dot3OamVariableResponseTx         Counter32,



          dot3OamVariableResponseRx         Counter32,
          dot3OamOrgSpecificTx              Counter32,
          dot3OamOrgSpecificRx              Counter32,
          dot3OamUnsupportedCodesTx         Counter32,
          dot3OamUnsupportedCodesRx         Counter32,
          dot3OamFramesLostDueToOam          Counter32
         }

 dot3OamInformationTx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Information OAMPDUs transmitted on
     this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.  "
  REFERENCE   "[802.3ah], 30.3.6.1.20."
```

::= { dot3OamStatsEntry 1 }

dot3OamInformationRx OBJECT-TYPE
SYNTAX Counter32
UNITS "frames"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"A count of the number of Information OAMPDUs received on this
interface.

Discontinuities of this counter can occur at re-initialization
of the management system, and at other times as indicated by
the value of the ifCounterDiscontinuityTime.
"
REFERENCE "[802.3ah], 30.3.6.1.21."
::= { dot3OamStatsEntry 2 }

dot3OamUniqueEventNotificationTx OBJECT-TYPE
SYNTAX Counter32
UNITS "frames"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"A count
of the number of unique Event OAMPDUs transmitted on
this interface. Event Notifications may be sent in duplicate
to increase the probability of successfully being received,

given the possibility that a frame may be lost in transit.
Duplicate Event Notification transmissions are counted by
dot3OamDuplicateEventNotificationTx.

A unique Event Notification OAMPDU is indicated as an Event
Notification OAMPDU with a Sequence Number field that is
distinct from the previously transmitted Event Notification
OAMPDU Sequence Number.

Discontinuities of this counter can occur at re-initialization
of the management system, and at other times as indicated by
the value of the ifCounterDiscontinuityTime.
"
REFERENCE "[802.3ah], 30.3.6.1.22."
::= { dot3OamStatsEntry 3 }

dot3OamUniqueEventNotificationRx OBJECT-TYPE

SYNTAX Counter32
UNITS "frames"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"A count of the number of unique Event OAMPDUs received on this interface. Event Notification OAMPDUs may be sent in duplicate to increase the probability of successfully being received, given the possibility that a frame may be lost in transit. Duplicate Event Notification receptions are counted by dot3OamDuplicateEventNotificationRx.

A unique Event Notification OAMPDU is indicated as an Event Notification OAMPDU with a Sequence Number field that is distinct from the previously received Event Notification OAMPDU Sequence Number.

Discontinuities of this counter can occur at re-initialization of the management system, and at other times as indicated by the value of the ifCounterDiscontinuityTime.
"
REFERENCE "[802.3ah], 30.3.6.1.24."
::= { dot3OamStatsEntry 4 }

dot3OamDuplicateEventNotificationTx OBJECT-TYPE
SYNTAX
Counter32
UNITS "frames"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"A count of the number of duplicate Event OAMPDUs transmitted

on this interface. Event Notification OAMPDUs may be sent in duplicate to increase the probability of successfully being received, given the possibility that a frame may be lost in transit.

A duplicate Event Notification OAMPDU is indicated as an Event Notification OAMPDU with a Sequence Number field that is identical to the previously transmitted Event Notification OAMPDU Sequence Number.

Discontinuities of this counter can occur at re-initialization of the management system, and at other times as indicated by the value of the ifCounterDiscontinuityTime.

```
    "
  REFERENCE   "[802.3ah], 30.3.6.1.23."
  ::= { dot3OamStatsEntry 5 }

dot3OamDuplicateEventNotificationRx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS
  "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of duplicate Event OAMPDUs received on
    this interface.  Event Notification OAMPDUs may be sent in
    duplicate to increase the probability of successfully being
    received, given the possibility that a frame may be lost in
    transit.

    A duplicate Event Notification OAMPDU is indicated as an Event
    Notification OAMPDU with a Sequence Number field that is
    identical to the previously received Event Notification OAMPDU
    Sequence Number.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.25."
  ::= { dot3OamStatsEntry 6 }

dot3OamLoopbackControlTx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS
    current
  DESCRIPTION
    "A count of the number of Loopback Control OAMPDUs transmitted




    on this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.26."
  ::= { dot3OamStatsEntry 7 }
```

```
dot3OamLoopbackControlRx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Loopback Control OAMPDUs received
    on this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.27."
  ::= { dot3OamStatsEntry 8 }

dot3OamVariableRequestTx OBJECT-TYPE
  SYNTAX      Counter32
   UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Variable Request OAMPDUs transmitted
    on this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.28."
  ::= { dot3OamStatsEntry 9 }

dot3OamVariableRequestRx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Variable Request OAMPDUs received on



    this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
```

```
    "
  REFERENCE   "[802.3ah], 30.3.6.1.29."
  ::= { dot3OamStatsEntry
10 }

 dot3OamVariableResponseTx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Variable Response OAMPDUs
    transmitted on this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.30."
  ::= { dot3OamStatsEntry 11 }

 dot3OamVariableResponseRx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Variable Response OAMPDUs received
    on this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
     "
  REFERENCE   "[802.3ah], 30.3.6.1.31."
  ::= { dot3OamStatsEntry 12 }

 dot3OamOrgSpecificTx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Organization Specific OAMPDUs



    transmitted on this interface.
```

Discontinuities of this counter can occur at re-initialization
of the management system, and at other times as indicated by
the value of the ifCounterDiscontinuityTime.
"
REFERENCE "[802.3ah], 30.3.6.1.32."
::= { dot3OamStatsEntry 13 }

dot3OamOrgSpecificRx OBJECT-TYPE
SYNTAX Counter32
UNITS "frames"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"A count of the number of Organization Specific OAMPDUs
received on this interface.

Discontinuities of this counter can occur at re-initialization
of the management system, and at other
times as indicated by
the value of the ifCounterDiscontinuityTime.
"
REFERENCE "[802.3ah], 30.3.6.1.33."
::= { dot3OamStatsEntry 14 }

dot3OamUnsupportedCodesTx OBJECT-TYPE
SYNTAX Counter32
UNITS "frames"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"A count of the number of OAMPDUs transmitted on this
interface with an unsupported op-code.

Discontinuities of this counter can occur at re-initialization
of the management system, and at other times as indicated by
the value of the ifCounterDiscontinuityTime.
"
REFERENCE "[802.3ah], 30.3.6.1.18."
::= { dot3OamStatsEntry 15 }

dot3OamUnsupportedCodesRx OBJECT-TYPE
SYNTAX Counter32
UNITS "frames"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"A count of the number of OAMPDUs received on this interface

```
    with an unsupported op-code.

    Discontinuities
of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.19."
  ::= { dot3OamStatsEntry 16 }

 dot3OamFramesLostDueToOam OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of frames that were dropped by the OA
    multiplexer.  Since the OAM multiplexer has multiple inputs
    and a single output, there may be cases where frames are
    dropped due to transmit resource contention.  This counter is
    incremented whenever a frame is dropped by the OAM layer.
    Note that any Ethernet frame, not just OAMPDUs, may be dropped
    by the OAM layer.  This can occur when an OAMPDU takes
    precedence over a 'normal' frame resulting in the 'normal'
    frame being dropped.

    When this counter
is incremented, no other counters in this
    MIB are incremented.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.46."
  ::= { dot3OamStatsEntry 17 }

 -- ****************************************************************
 --
 -- Ethernet OAM Event Configuration group
 --

 dot3OamEventConfigTable OBJECT-TYPE
  SYNTAX     SEQUENCE OF Dot3OamEventConfigEntry
  MAX-ACCESS not-accessible
```

STATUS current
DESCRIPTION
"Ethernet OAM includes the ability to generate and receive
Event Notification OAMPDUs to indicate various link problems.
This table contains the mechanisms to enable Event

Notifications and configure the thresholds to generate the
standard Ethernet OAM events. There is one entry in the table
for every entry in
dot3OamTable that supports OAM events
(where dot3OamFunctionsSupported includes the eventSupport
bit set). The values in the table are maintained across
changes to dot3OamOperStatus.

The standard threshold crossing events are:
- Errored Symbol Period Event. Generated when the number of
symbol errors exceeds a threshold within a given window
defined by a number of symbols (for example, 1,000 symbols
out of 1,000,000 had errors).
- Errored Frame Period Event. Generated when the number of
frame errors exceeds a threshold within a given window
defined by a number of frames (for example, 10 frames out
of 1000 had errors).
- Errored Frame Event. Generated when the number of frame
errors exceeds a threshold within a given window defined
by a period of time (for example, 10 frames in 1 second
had errors).
- Errored Frame Seconds
Summary Event. Generated when the
number of errored frame seconds exceeds a threshold within
a given time period (for example, 10 errored frame seconds
within the last 100 seconds). An errored frame second is
defined as a 1 second interval which had >0 frame errors.
There are other events (dying gasp, critical events) that are
not threshold crossing events but which can be
enabled/disabled via this table.
"
::= { dot3OamObjects 5 }

dot3OamEventConfigEntry OBJECT-TYPE
SYNTAX Dot3OamEventConfigEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Entries are automatically created and deleted from this
table, and exist whenever the OAM entity supports Ethernet OA

```
    events (as indicated by the eventSupport bit in
    dot3OamFunctionsSuppported).  Values in the table are
    maintained across changes to the value of dot3OamOperStatus.

    Event
configuration controls when the local management entity
    sends Event Notification OAMPDUs to its OAM peer, and when
    certain event flags are set or cleared in OAMPDUs.
    "
  INDEX       { ifIndex }
  ::= { dot3OamEventConfigTable 1 }



 Dot3OamEventConfigEntry ::=
  SEQUENCE {
          dot3OamErrSymPeriodWindowHi        Unsigned32,
          dot3OamErrSymPeriodWindowLo        Unsigned32,
          dot3OamErrSymPeriodThresholdHi     Unsigned32,
          dot3OamErrSymPeriodThresholdLo     Unsigned32,
          dot3OamErrSymPeriodEvNotifEnable   TruthValue,
          dot3OamErrFramePeriodWindow        Unsigned32,
          dot3OamErrFramePeriodThreshold     Unsigned32,
          dot3OamErrFramePeriodEvNotifEnable TruthValue,
          dot3OamErrFrameWindow              Unsigned32,
          dot3OamErrFrameThreshold           Unsigned32,
          dot3OamErrFrameEvNotifEnable       TruthValue,

       dot3OamErrFrameSecsSummaryWindow   Integer32,
          dot3OamErrFrameSecsSummaryThreshold Integer32,
          dot3OamErrFrameSecsEvNotifEnable   TruthValue,
          dot3OamDyingGaspEnable             TruthValue,
          dot3OamCriticalEventEnable         TruthValue
        }

 dot3OamErrSymPeriodWindowHi OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "2^32 symbols"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "The two objects dot3OamErrSymPeriodWindowHi and
    dot3OamErrSymPeriodLo together form an unsigned 64-bit
    integer representing the number of symbols over which this
    threshold event is defined.  This is defined as
  dot3OamErrSymPeriodWindow = ((2^32)*dot3OamErrSymPeriodWindowHi)
                              + dot3OamErrSymPeriodWindowLo
```

```
    If dot3OamErrSymPeriodThreshold symbol errors occur within a
    window of dot3OamErrSymPeriodWindow symbols, an Event

    Notification OAMPDU should be generated with an Errored Symbol
    Period Event TLV indicating that the threshold has been
    crossed in this window.

    The default value for dot3OamErrSymPeriodWindow is the number
    of symbols in one second for the underlying physical layer.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.34"
  ::= { dot3OamEventConfigEntry 1 }

 dot3OamErrSymPeriodWindowLo OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "symbols"



  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "The two objects dot3OamErrSymPeriodWindowHi and
    dot3OamErrSymPeriodWindowLo together form an unsigned 64-bit
    integer representing the number of symbols over which this
    threshold event is defined.  This is defined as

  dot3OamErrSymPeriodWindow = ((2^32)*dot3OamErrSymPeriodWindowHi)
                            + dot3OamErrSymPeriodWindowLo

    If dot3OamErrSymPeriodThreshold symbol errors
occur within a
    window of dot3OamErrSymPeriodWindow symbols, an Event
    Notification OAMPDU should be generated with an Errored Symbol
    Period Event TLV indicating that the threshold has been
    crossed in this window.

    The default value for dot3OamErrSymPeriodWindow is the number
    of symbols in one second for the underlying physical layer.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.34"
  ::= { dot3OamEventConfigEntry 2 }

 dot3OamErrSymPeriodThresholdHi OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "2^32 symbols"
  MAX-ACCESS  read-write
  STATUS      current
```

```
  DESCRIPTION
    "The two objects dot3OamErrSymPeriodThresholdHi and
    dot3OamErrSymPeriodThresholdLo together form an unsigned
    64-bit integer representing the number of symbol errors that
    must occur within a given window to cause this event.

    This is defined as

      dot3OamErrSymPeriodThreshold =
                  ((2^32) *
dot3OamErrSymPeriodThresholdHi)
                        + dot3OamErrSymPeriodThresholdLo

    If dot3OamErrSymPeriodThreshold symbol errors occur within a
    window of dot3OamErrSymPeriodWindow symbols, an Event
    Notification OAMPDU should be generated with an Errored Symbol
    Period Event TLV indicating that the threshold has been
    crossed in this window.

    The default value for dot3OamErrSymPeriodThreshold is one
    symbol errors.  If the threshold value is zero, then an Event



    Notification OAMPDU is sent periodically (at the end of every
    window).  This can be used as an asynchronous notification to
    the peer OAM entity of the statistics related to this
    threshold crossing alarm.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.34"
  ::= { dot3OamEventConfigEntry 3 }

 dot3OamErrSymPeriodThresholdLo OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "symbols"
  MAX-ACCESS  read-write
  STATUS
 current
  DESCRIPTION
    "The two objects dot3OamErrSymPeriodThresholdHi and
    dot3OamErrSymPeriodThresholdLo together form an unsigned
    64-bit integer representing the number of symbol errors that
    must occur within a given window to cause this event.

    This is defined as

      dot3OamErrSymPeriodThreshold =
                  ((2^32) * dot3OamErrSymPeriodThresholdHi)
```

+ dot3OamErrSymPeriodThresholdLo

If dot3OamErrSymPeriodThreshold symbol errors occur within a window of dot3OamErrSymPeriodWindow symbols, an Event Notification OAMPDU should be generated with an Errored Symbol Period Event TLV indicating that the threshold has been crossed in this window.

The default value for dot3OamErrSymPeriodThreshold is one symbol error. If the threshold value is zero, then an Event Notification OAMPDU is sent periodically (at the end of every window). This
can be used as an asynchronous notification to
the peer OAM entity of the statistics related to this threshold crossing alarm.
"
REFERENCE "[802.3ah], 30.3.6.1.34"
::= { dot3OamEventConfigEntry 4 }

dot3OamErrSymPeriodEvNotifEnable OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"If true, the OAM entity should send an Event Notification OAMPDU when an Errored Symbol Period Event occurs.

By default, this object should have the value true for Ethernet-like interfaces that support OAM. If the OAM layer does not support Event Notifications (as indicated via the dot3OamFunctionsSupported attribute), this value is ignored.
"
::= { dot3OamEventConfigEntry 5 }

dot3OamErrFramePeriodWindow OBJECT-TYPE
SYNTAX Unsigned32
UNITS "frames"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"The
number of frames over which the threshold is defined.
The default value of the window is the number of minimum size Ethernet frames that can be received over the physical layer in one second.

```
    If dot3OamErrFramePeriodThreshold frame errors occur within a
    window of dot3OamErrFramePeriodWindow frames, an Event
    Notification OAMPDU should be generated with an Errored Frame
    Period Event TLV indicating that the threshold has been
    crossed in this window.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.38"
  ::= { dot3OamEventConfigEntry 6 }

 dot3OamErrFramePeriodThreshold OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "frames"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "The number of frame errors that must occur for this event to
    be triggered.  The default value is one frame error.  If the
    threshold value is zero, then an Event Notification OAMPDU is
    sent periodically
(at the end of every window).  This can be
    used as an asynchronous notification to the peer OAM entity of
    the statistics related to this threshold crossing alarm.

    If dot3OamErrFramePeriodThreshold frame errors occur within a
    window of dot3OamErrFramePeriodWindow frames, an Event
    Notification OAMPDU should be generated with an Errored Frame
    Period Event TLV indicating that the threshold has been
    crossed in this window.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.38"



  ::= { dot3OamEventConfigEntry 7 }

 dot3OamErrFramePeriodEvNotifEnable OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "If true, the OAM entity should send an Event Notification
    OAMPDU when an Errored Frame Period Event occurs.

    By default, this object should have the value true for
    Ethernet-like interfaces that support OAM.  If the OAM layer
    does not support Event Notifications
```

(as indicated via the
dot3OamFunctionsSupported attribute), this value is ignored.
"
::= { dot3OamEventConfigEntry 8 }

dot3OamErrFrameWindow OBJECT-TYPE
SYNTAX Unsigned32
UNITS "tenths of a second"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"The amount of time (in 100ms increments) over which the
threshold is defined. The default value is 10 (1 second).

If dot3OamErrFrameThreshold frame errors occur within a window
of dot3OamErrFrameWindow seconds (measured in tenths of
seconds), an Event Notification OAMPDU should be generated
with an Errored Frame Event TLV indicating that the threshold
has been crossed in this window.
"
REFERENCE "[802.3ah], 30.3.6.1.36"
DEFVAL { 10 }
::= { dot3OamEventConfigEntry 9 }

dot3OamErrFrameThreshold OBJECT-TYPE
SYNTAX Unsigned32
UNITS "frames"
MAX-ACCESS read-write

STATUS current
DESCRIPTION
"The number of frame errors that must occur for this event to
be triggered. The default value is one frame error. If the
threshold value is zero, then an Event Notification OAMPDU is
sent periodically (at the end of every window). This can be
used as an asynchronous notification to the peer OAM entity of
the statistics related to this threshold crossing alarm.

If dot3OamErrFrameThreshold frame errors occur within a window
of dot3OamErrFrameWindow (in tenths of seconds), an Event
Notification OAMPDU should be generated with an Errored Frame
Event TLV indicating the threshold has been crossed in this
window.
"
REFERENCE "[802.3ah], 30.3.6.1.36"

```
  DEFVAL { 1 }
  ::= { dot3OamEventConfigEntry 10 }

 dot3OamErrFrameEvNotifEnable OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "If true,
the OAM entity should send an Event Notification
    OAMPDU when an Errored Frame Event occurs.

    By default, this object should have the value true for
    Ethernet-like interfaces that support OAM.  If the OAM layer
    does not support Event Notifications (as indicated via the
    dot3OamFunctionsSupported attribute), this value is ignored.
    "
  DEFVAL { true }
  ::= { dot3OamEventConfigEntry 11 }

 dot3OamErrFrameSecsSummaryWindow OBJECT-TYPE
  SYNTAX      Integer32 (100..9000)
  UNITS       "tenths of a second"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "The amount of time (in 100 ms intervals) over which the
    threshold is defined.  The default value is 100 (10 seconds).

    If dot3OamErrFrameSecsSummaryThreshold frame errors occur
    within a window of dot3OamErrFrameSecsSummaryWindow (in tenths
    of seconds), an Event Notification OAMPDU should be generated
    with an Errored Frame
Seconds Summary Event TLV indicating
    that the threshold has been crossed in this window.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.40"
  DEFVAL { 100 }
  ::= { dot3OamEventConfigEntry 12 }

 dot3OamErrFrameSecsSummaryThreshold OBJECT-TYPE
  SYNTAX      Integer32 (1..900)



  UNITS       "errored frame seconds"
  MAX-ACCESS  read-write
  STATUS      current
```

```
  DESCRIPTION
    "The number of errored frame seconds that must occur for this
    event to be triggered.  The default value is one errored frame
    second.  If the threshold value is zero, then an Event
    Notification OAMPDU is sent periodically (at the end of every
    window).  This can be used as an asynchronous notification to
    the peer OAM entity of the statistics related to this
    threshold crossing alarm.

    If dot3OamErrFrameSecsSummaryThreshold frame errors occur
    within a window of dot3OamErrFrameSecsSummaryWindow (in tenths
    of seconds),
an Event Notification OAMPDU should be generated
    with an Errored Frame Seconds Summary Event TLV indicating
    that the threshold has been crossed in this window.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.40"
  DEFVAL { 1 }
  ::= { dot3OamEventConfigEntry 13 }

 dot3OamErrFrameSecsEvNotifEnable OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "If true, the local OAM entity should send an Event
    Notification OAMPDU when an Errored Frame Seconds Event
    occurs.

    By default, this object should have the value true for
    Ethernet-like interfaces that support OAM.  If the OAM layer
    does not support Event Notifications (as indicated via the
    dot3OamFunctionsSupported attribute), this value is ignored.
    "
  DEFVAL { true }
  ::= { dot3OamEventConfigEntry 14 }

 dot3OamDyingGaspEnable OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-write

 STATUS      current
  DESCRIPTION
    "If true, the local OAM entity should attempt to indicate a
    dying gasp via the OAMPDU flags field to its peer OAM entity
    when a dying gasp event occurs.  The exact definition of a
    dying gasp event is implementation dependent.  If the system
```

```
    does not support dying gasp capability, setting this object
    has no effect, and reading the object should always result in
    'false'.

    By default, this object should have the value true for
    Ethernet-like interfaces that support OAM.  If the OAM layer
    does not support Event Notifications (as indicated via the
    dot3OamFunctionsSupported attribute), this value is ignored.
    "
  DEFVAL { true }
  ::= { dot3OamEventConfigEntry 15 }

 dot3OamCriticalEventEnable OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "If true, the local OAM entity should attempt to indicate
a
    critical event via the OAMPDU flags to its peer OAM entity
    when a critical event occurs.  The exact definition of a
    critical event is implementation dependent.  If the system
    does not support critical event capability, setting this
    object has no effect, and reading the object should always
    result in 'false'.

    By default, this object should have the value true for
    Ethernet-like interfaces that support OAM.  If the OAM layer
    does not support Event Notifications (as indicated via the
    dot3OamFunctionsSupported attribute), this value is ignored.
    "
  DEFVAL { true }
  ::= { dot3OamEventConfigEntry 16 }

 -- ****************************************************************
 --
 -- Ethernet OAM Event Log group
 --

 dot3OamEventLogTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF Dot3OamEventLogEntry
  MAX-ACCESS   not-accessible
  STATUS      current
  DESCRIPTION
    "This table records
```

a history of the events that have occurred
at the Ethernet OAM level. These events can include locally detected events, which may result in locally generated OAMPDUs, and remotely detected events, which are detected by the OAM peer entity and signaled to the local entity via

Ethernet OAM. Ethernet OAM events can be signaled by Event Notification OAMPDUs or by the flags field in any OAMPDU.

This table contains both threshold crossing events and non-threshold crossing events. The parameters for the threshold window, threshold value, and actual value (dot3OamEventLogWindowXX, dot3OamEventLogThresholdXX, dot3OamEventLogValue) are only applicable to threshold crossing events, and are returned as all F's (2^32 - 1) for non-threshold crossing events.

Entries in the table are automatically created when such events are detected. The size of the table is implementation dependent.
When the table reaches its maximum size, older entries are automatically deleted to make room for newer entries.
"
::= { dot3OamObjects 6 }

dot3OamEventLogEntry OBJECT-TYPE
SYNTAX Dot3OamEventLogEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"An entry in the dot3OamEventLogTable. Entries are automatically created whenever Ethernet OAM events occur at the local OAM entity, and when Event Notification OAMPDUs are received at the local OAM entity (indicating that events have occurred at the peer OAM entity). The size of the table is implementation dependent, but when the table becomes full, older events are automatically deleted to make room for newer events. The table index dot3OamEventLogIndex increments for each new entry, and when the maximum value is reached, the value restarts at zero.
"
INDEX { ifIndex, dot3OamEventLogIndex
}
::= { dot3OamEventLogTable 1 }

```
Dot3OamEventLogEntry ::=
  SEQUENCE {
    dot3OamEventLogIndex              Unsigned32,
    dot3OamEventLogTimestamp          TimeStamp,
    dot3OamEventLogOui                EightOTwoOui,
    dot3OamEventLogType               Unsigned32,
    dot3OamEventLogLocation           INTEGER,
    dot3OamEventLogWindowHi           Unsigned32,
    dot3OamEventLogWindowLo           Unsigned32,
    dot3OamEventLogThresholdHi        Unsigned32,



    dot3OamEventLogThresholdLo        Unsigned32,
    dot3OamEventLogValue              CounterBasedGauge64,
    dot3OamEventLogRunningTotal       CounterBasedGauge64,
    dot3OamEventLogEventTotal         Unsigned32
  }

dot3OamEventLogIndex      OBJECT-TYPE
  SYNTAX      Unsigned32(1..4294967295)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An arbitrary integer for identifying individual events
     within the event log.  "
  ::= { dot3OamEventLogEntry 1 }

dot3OamEventLogTimestamp  OBJECT-TYPE
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The value of sysUpTime at the time of the logged event.  For
    locally generated events, the time of the event can be
    accurately retrieved from sysUpTime.  For remotely generated
    events, the time of the event is indicated by the reception of
    the Event Notification OAMPDU indicating that the event
    occurred on the peer.  A system may attempt to adjust the
    timestamp value to more accurately reflect the time of the
    event at the peer OAM entity by using other information, such
    as that found in the timestamp found of the Event Notification
    TLVs, which provides an indication of the relative time
    between events at the peer entity.  "
  ::= { dot3OamEventLogEntry 2 }

dot3OamEventLogOui  OBJECT-TYPE
  SYNTAX
```

```
    EightOTwoOui
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The OUI of the entity defining the object type.  All IEEE
    802.3 defined events (as appearing in [802.3ah] except for the
    Organizationally Unique Event TLVs) use the IEEE 802.3 OUI of
    0x0180C2.  Organizations defining their own Event Notification
    TLVs include their OUI in the Event Notification TLV that
    gets reflected here.  "
  ::= { dot3OamEventLogEntry 3 }

dot3OamEventLogType      OBJECT-TYPE
  SYNTAX      Unsigned32



  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The type of event that generated this entry in the event log.
    When the OUI is the IEEE 802.3 OUI of 0x0180C2, the following
    event types are defined:
       erroredSymbolEvent(1),
       erroredFramePeriodEvent(2),
       erroredFrameEvent(3),
       erroredFrameSecondsEvent(4),
       linkFault(256),
       dyingGaspEvent(257),
        criticalLinkEvent(258)
    The first four are considered threshold crossing events, as
    they are generated when a metric exceeds a given value within
    a specified window.  The other three are not threshold
    crossing events.

    When the OUI is not 71874 (0x0180C2 in hex), then some other
    organization has defined the event space.  If event subtyping
    is known to the implementation, it may be reflected here.
    Otherwise, this value should return all F's (2^32 - 1).
    "
  REFERENCE   "[802.3ah], 30.3.6.1.10 and 57.5.3."
  ::= { dot3OamEventLogEntry 4 }

dot3OamEventLogLocation OBJECT-TYPE
  SYNTAX      INTEGER { local(1), remote(2) }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
```

"Whether this event occurred locally (local(1)), or was
received from the OAM peer via Ethernet OAM (remote(2)).
"
::= { dot3OamEventLogEntry 5 }

dot3OamEventLogWindowHi OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"If the event represents a threshold crossing event, the two
objects dot3OamEventWindowHi and dot3OamEventWindowLo, form
an unsigned 64-bit integer yielding the window over which the
value was measured for the threshold crossing event (for
example, 5, when 11 occurrences happened in 5 seconds while
the threshold was 10). The two objects are combined as:

dot3OamEventLogWindow = ((2^32) * dot3OamEventLogWindowHi)
+ dot3OamEventLogWindowLo

Otherwise, this value is returned as all F's (2^32 - 1) and
adds no useful information.
"
REFERENCE "[802.3ah], 30.3.6.1.37 and 57.5.3.2."
::= { dot3OamEventLogEntry 6 }

dot3OamEventLogWindowLo OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"If the
event represents a threshold crossing event, the two
objects dot3OamEventWindowHi and dot3OamEventWindowLo form an
unsigned 64-bit integer yielding the window over which the
value was measured for the threshold crossing event (for
example, 5, when 11 occurrences happened in 5 seconds while
the threshold was 10). The two objects are combined as:

dot3OamEventLogWindow = ((2^32) * dot3OamEventLogWindowHi)
+ dot3OamEventLogWindowLo

Otherwise, this value is returned as all F's (2^32 - 1) and
adds no useful information.
"

```
  REFERENCE   "[802.3ah], 30.3.6.1.37 and 57.5.3.2."
  ::= { dot3OamEventLogEntry 7 }

 dot3OamEventLogThresholdHi      OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "If the event represents a threshold crossing event, the two
    objects dot3OamEventThresholdHi and dot3OamEventThresholdLo
     form an unsigned 64-bit integer yielding the value that was
    crossed for the threshold crossing event (for example, 10,
    when 11 occurrences happened in 5 seconds while the threshold
    was 10).  The two objects are combined as:

  dot3OamEventLogThreshold = ((2^32) * dot3OamEventLogThresholdHi)
                             + dot3OamEventLogThresholdLo

    Otherwise, this value is returned as all F's (2^32 -1) and
    adds no useful information.
    "



  REFERENCE   "[802.3ah], 30.3.6.1.37 and 57.5.3.2."
  ::= { dot3OamEventLogEntry 8 }

 dot3OamEventLogThresholdLo      OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "If the event represents a threshold crossing event, the two
    objects dot3OamEventThresholdHi and dot3OamEventThresholdLo
    form an unsigned 64-bit integer yielding the value that was
    crossed for the threshold crossing event (for example,
10,
    when 11 occurrences happened in 5 seconds while the threshold
    was 10).  The two objects are combined as:

  dot3OamEventLogThreshold = ((2^32) * dot3OamEventLogThresholdHi)
                             + dot3OamEventLogThresholdLo

    Otherwise, this value is returned as all F's (2^32 - 1) and
    adds no useful information.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.37 and 57.5.3.2."
  ::= { dot3OamEventLogEntry 9 }
```

```
dot3OamEventLogValue      OBJECT-TYPE
  SYNTAX      CounterBasedGauge64
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "If the event represents a threshold crossing event, this
    value indicates the value of the parameter within the given
    window that generated this event (for example, 11, when 11
    occurrences happened in 5 seconds while the threshold was 10).

    Otherwise, this value is returned as all F's
    (2^64 - 1) and adds no useful information.

"
  REFERENCE   "[802.3ah], 30.3.6.1.37 and 57.5.3.2."
  ::= { dot3OamEventLogEntry 10 }

dot3OamEventLogRunningTotal      OBJECT-TYPE
  SYNTAX      CounterBasedGauge64
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "Each Event Notification TLV contains a running total of the
    number of times an event has occurred, as well as the number
    of times an Event Notification for the event has been



    transmitted.  For non-threshold crossing events, the number of
    events (dot3OamLogRunningTotal) and the number of resultant
    Event Notifications (dot3OamLogEventTotal) should be
    identical.

    For threshold crossing events, since multiple occurrences may
    be required to cross the threshold, these values are likely
    different.  This value represents the total number of times
    this event has happened since the last reset (for example,
    3253, when 3253 symbol errors have occurred since the last
     reset, which has resulted in 51 symbol error threshold
    crossing events since the last reset).
    "
  REFERENCE   "[802.3ah], 30.3.6.1.37 and 57.5.3.2."
  ::= { dot3OamEventLogEntry 11 }

dot3OamEventLogEventTotal      OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
```

```
  STATUS      current
  DESCRIPTION
    "Each Event Notification TLV contains a running total of the
    number of times an event has occurred, as well as the number
    of times an Event Notification for the event has been
    transmitted.  For non-threshold crossing events, the number of
    events (dot3OamLogRunningTotal) and the number of resultant
    Event Notifications (dot3OamLogEventTotal) should be
    identical.

    For threshold crossing events, since multiple occurrences may
    be required to cross the threshold, these values are likely
    different.  This value represents the total number of times
    one or more of these
occurrences have resulted in an Event
    Notification (for example, 51 when 3253 symbol errors have
    occurred since the last reset, which has resulted in 51 symbol
    error threshold crossing events since the last reset).
    "
  REFERENCE   "[802.3ah], 30.3.6.1.37 and 57.5.3.2."
  ::= { dot3OamEventLogEntry 12 }

 -- ****************************************************************
 --
 -- Ethernet OAM Notifications
 --

 dot3OamThresholdEvent NOTIFICATION-TYPE
  OBJECTS { dot3OamEventLogTimestamp,
          dot3OamEventLogOui,



          dot3OamEventLogType,
          dot3OamEventLogLocation,
          dot3OamEventLogWindowHi,
          dot3OamEventLogWindowLo,
          dot3OamEventLogThresholdHi,
          dot3OamEventLogThresholdLo,
          dot3OamEventLogValue,
          dot3OamEventLogRunningTotal,
          dot3OamEventLogEventTotal
        }
  STATUS  current
  DESCRIPTION

 "A dot3OamThresholdEvent notification is sent when a local or
    remote threshold crossing event is detected.  A local
```

threshold crossing event is detected by the local entity,
while a remote threshold crossing event is detected by the
reception of an Ethernet OAM Event Notification OAMPDU
that indicates a threshold event.

This notification should not be sent more than once per
second.

The OAM entity can be derived from extracting the ifIndex from
the variable bindings. The objects in the notification
correspond to the values in a row instance in the
dot3OamEventLogTable.

The management entity should periodically check
dot3OamEventLogTable to detect any missed events."
::= { dot3OamNotifications 1 }

dot3OamNonThresholdEvent NOTIFICATION-TYPE
OBJECTS { dot3OamEventLogTimestamp,
dot3OamEventLogOui,
dot3OamEventLogType,
dot3OamEventLogLocation,
dot3OamEventLogEventTotal
}
STATUS current
DESCRIPTION
"A dot3OamNonThresholdEvent notification is sent when a local
or remote non-threshold crossing event is detected. A local
event is detected by the local entity, while a remote event is
detected by the reception of an Ethernet OAM Event
Notification OAMPDU that indicates a non-threshold crossing
event.

This notification should not be sent more than once per

second.

The OAM entity can be derived from extracting the ifIndex from
the variable bindings. The objects in the notification
correspond to the values in a row instance of the
dot3OamEventLogTable.

The management entity should periodically check
dot3OamEventLogTable to detect any missed events."
::= { dot3OamNotifications 2 }

```
-- ****************************************************************
--
-- Ethernet OAM Compliance
group
--

dot3OamGroups OBJECT IDENTIFIER ::= { dot3OamConformance 1 }
dot3OamCompliances OBJECT IDENTIFIER ::= { dot3OamConformance 2 }

-- Compliance statements

dot3OamCompliance MODULE-COMPLIANCE
  STATUS         current
  DESCRIPTION "The compliance statement for managed entities
               supporting OAM on Ethernet-like interfaces.
               "
 MODULE   -- this module
  MANDATORY-GROUPS { dot3OamControlGroup,
                     dot3OamPeerGroup,
                     dot3OamStatsBaseGroup
                   }

  GROUP       dot3OamLoopbackGroup
  DESCRIPTION
    "This group is mandatory for all IEEE 802.3 OA
    implementations that support loopback functionality. "

  GROUP       dot3OamErrSymbolPeriodEventGroup
  DESCRIPTION
    "This group is mandatory for all IEEE 802.3 OA
    implementations that support event functionality. "

  GROUP       dot3OamErrFramePeriodEventGroup
  DESCRIPTION

   "This group is mandatory for all IEEE 802.3 OA
    implementations that support event functionality. "

  GROUP       dot3OamErrFrameEventGroup



  DESCRIPTION
    "This group is mandatory for all IEEE 802.3 OA
    implementations that support event functionality. "

  GROUP       dot3OamErrFrameSecsSummaryEventGroup
  DESCRIPTION
```

```
    "This group is mandatory for all IEEE 802.3 OA
    implementations that support event functionality. "

  GROUP       dot3OamFlagEventGroup
  DESCRIPTION
    "This group is optional for all IEEE 802.3 OA
    implementations.  The ability to send critical events or dying
    gasp events is not required in any system."

  GROUP       dot3OamEventLogGroup
  DESCRIPTION
    "This group is optional for all IEEE 802.3 OA
    implementations.  Entries in this table are dependent on what
    event functionality is supported in the local OA
    implementation.  At least one type of event must be supported
     for entries to appear in this table.  "

  GROUP       dot3OamNotificationGroup
  DESCRIPTION
    "This group is optional for all IEEE 802.3 OA
    implementations.  Since the information in the notifications
    is dependent on the dot3OamEventLogTable, that table must be
    implemented for notifications.  "

  ::= { dot3OamCompliances 1}

dot3OamControlGroup OBJECT-GROUP
  OBJECTS     {   dot3OamAdminState,
                  dot3OamOperStatus,
                  dot3OamMode,
                  dot3OamMaxOamPduSize,
                  dot3OamConfigRevision,
                  dot3OamFunctionsSupported
              }
  STATUS      current
  DESCRIPTION
    "A collection of objects providing the abilities,
    configuration, and status of an Ethernet OAM entity.  "
  ::= { dot3OamGroups 1 }

dot3OamPeerGroup OBJECT-GROUP
  OBJECTS     {   dot3OamPeerMacAddress,



                  dot3OamPeerVendorOui,
```

```
            dot3OamPeerVendorInfo,
              dot3OamPeerMode,
              dot3OamPeerFunctionsSupported,
              dot3OamPeerMaxOamPduSize,
              dot3OamPeerConfigRevision
            }
  STATUS      current
  DESCRIPTION
    "A collection of objects providing the abilities,
    configuration, and status of a peer Ethernet OAM entity.  "
  ::= { dot3OamGroups 2 }

dot3OamStatsBaseGroup OBJECT-GROUP
  OBJECTS     {   dot3OamInformationTx,
              dot3OamInformationRx,
              dot3OamUniqueEventNotificationTx,
              dot3OamUniqueEventNotificationRx,
              dot3OamDuplicateEventNotificationTx,
              dot3OamDuplicateEventNotificationRx,
              dot3OamLoopbackControlTx,
              dot3OamLoopbackControlRx,
              dot3OamVariableRequestTx,
              dot3OamVariableRequestRx,
              dot3OamVariableResponseTx,
               dot3OamVariableResponseRx,
              dot3OamOrgSpecificTx,
              dot3OamOrgSpecificRx,
              dot3OamUnsupportedCodesTx,
              dot3OamUnsupportedCodesRx,
              dot3OamFramesLostDueToOam
            }
  STATUS      current
  DESCRIPTION
    "A collection of objects providing the statistics for the
    number of various transmit and receive events for OAM on an
    Ethernet-like interface.  Note that all of these counters must
    be supported even if the related function (as described in
    dot3OamFunctionsSupported) is not supported.  "
  ::= { dot3OamGroups 3 }

dot3OamLoopbackGroup OBJECT-GROUP
  OBJECTS     {   dot3OamLoopbackStatus,
              dot3OamLoopbackIgnoreRx
            }
  STATUS      current
  DESCRIPTION
    "A collection of objects for controlling the OAM remote
```

```
    loopback function.  "

::= { dot3OamGroups 4 }

dot3OamErrSymbolPeriodEventGroup OBJECT-GROUP
  OBJECTS     {   dot3OamErrSymPeriodWindowHi,
                  dot3OamErrSymPeriodWindowLo,
                  dot3OamErrSymPeriodThresholdHi,
                  dot3OamErrSymPeriodThresholdLo,
                  dot3OamErrSymPeriodEvNotifEnable
              }
  STATUS      current
  DESCRIPTION
    "A collection of objects for configuring the thresholds for an
    Errored Symbol Period Event.

    Each [802.3ah] defined Event Notification TLV has its own
    conformance group because each event can be implemented
    independently of any other.  "
  ::= { dot3OamGroups 5 }

dot3OamErrFramePeriodEventGroup OBJECT-GROUP
  OBJECTS     {   dot3OamErrFramePeriodWindow,
                  dot3OamErrFramePeriodThreshold,
                  dot3OamErrFramePeriodEvNotifEnable
              }
  STATUS      current
  DESCRIPTION
    "A collection of objects for
configuring the thresholds for an
    Errored Frame Period Event.

    Each [802.3ah] defined Event Notification TLV has its own
    conformance group because each event can be implemented
    independently of any other.  "
  ::= { dot3OamGroups 6 }

dot3OamErrFrameEventGroup OBJECT-GROUP
  OBJECTS     {   dot3OamErrFrameWindow,
                  dot3OamErrFrameThreshold,
                  dot3OamErrFrameEvNotifEnable
              }
  STATUS      current
  DESCRIPTION
    "A collection of objects for configuring the thresholds for an
    Errored Frame Event.
```

```
    Each [802.3ah] defined Event Notification TLV has its own
    conformance group because each event can be implemented
    independently of any other.  "



  ::= { dot3OamGroups 7 }

dot3OamErrFrameSecsSummaryEventGroup OBJECT-GROUP
  OBJECTS     {   dot3OamErrFrameSecsSummaryWindow,
                  dot3OamErrFrameSecsSummaryThreshold,
                  dot3OamErrFrameSecsEvNotifEnable
              }
  STATUS      current
  DESCRIPTION
    "A collection of objects for configuring the thresholds for an
    Errored Frame Seconds Summary Event.

    Each [802.3ah] defined Event Notification TLV has its own
    conformance group because each event can be implemented
    independently of any other.  "
  ::= { dot3OamGroups 8 }

dot3OamFlagEventGroup OBJECT-GROUP
  OBJECTS     {   dot3OamDyingGaspEnable,
                  dot3OamCriticalEventEnable
              }
  STATUS      current
  DESCRIPTION
    "A collection of objects for configuring the sending OAMPDUs
    with the critical event flag or dying gasp flag enabled.  "
  ::= { dot3OamGroups 9 }

dot3OamEventLogGroup OBJECT-GROUP
  OBJECTS {  dot3OamEventLogTimestamp,
             dot3OamEventLogOui,
             dot3OamEventLogType,
             dot3OamEventLogLocation,
             dot3OamEventLogWindowHi,
             dot3OamEventLogWindowLo,
              dot3OamEventLogThresholdHi,
             dot3OamEventLogThresholdLo,
             dot3OamEventLogValue,
             dot3OamEventLogRunningTotal,
             dot3OamEventLogEventTotal
           }
  STATUS      current
```

```
  DESCRIPTION
    "A collection of objects for configuring the thresholds for an
    Errored Frame Seconds Summary Event and maintaining the event
    information.  "
   ::= { dot3OamGroups 10 }

dot3OamNotificationGroup NOTIFICATION-GROUP



  NOTIFICATIONS {
            dot3OamThresholdEvent,
            dot3OamNonThresholdEvent
             }
  STATUS      current
  DESCRIPTION
    "A collection of notifications used by Ethernet OAM to signal
    to a management entity that local or remote events have
    occurred on a specified Ethernet link. "
  ::= { dot3OamGroups 11 }

 END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/DOT3-OAM-MIB
No license file was found, but licenses were detected in source scan.

```
SYSAPPL-MIB DEFINITIONS ::= BEGIN

 IMPORTS
    MODULE-IDENTITY, OBJECT-TYPE,
    Unsigned32, TimeTicks, Counter32, Gauge32
       FROM SNMPv2-SMI
    DateAndTime, TEXTUAL-CONVENTION
       FROM SNMPv2-TC
    MODULE-COMPLIANCE, OBJECT-GROUP
       FROM SNMPv2-CONF
    mib-2 FROM SNMPv2-SMI;

 -- System Application MIB

 sysApplMIB MODULE-IDENTITY
    LAST-UPDATED "9710200000Z"
    ORGANIZATION "IETF Applications MIB Working Group"
    CONTACT-INFO
         "Cheryl Krupczak (Editor, WG Advisor)
          Postal: Empire Technologies, Inc.
          541 Tenth Street NW
```

```
          Suite 169
          Atlanta, GA 30318
          USA
          Phone: (770) 384-0184
          Email: cheryl@empiretech.com

          Jon Saperia (WG Chair)
          Postal:  BGS Systems, Inc.
          One First Avenue
          Waltham, MA 02254-9111
          USA

 Phone: (617) 891-0000
          Email: saperia@networks.bgs.com"
    DESCRIPTION
        "The MIB module defines management objects that model
        applications as collections of executables and files
        installed and executing on a host system.  The MIB
        presents a system-level view of applications; i.e.,
        objects in this MIB are limited to those attributes
        that can typically be obtained from the system itself
        without adding special instrumentation to the applications."
    ::= { mib-2 54  }


sysApplOBJ              OBJECT IDENTIFIER ::= { sysApplMIB 1 }
sysApplInstalled        OBJECT IDENTIFIER ::= { sysApplOBJ 1 }
sysApplRun              OBJECT IDENTIFIER ::= { sysApplOBJ 2 }
sysApplMap              OBJECT IDENTIFIER ::= { sysApplOBJ 3 }
sysApplNotifications    OBJECT IDENTIFIER ::= { sysApplMIB 2 }
sysApplConformance      OBJECT IDENTIFIER ::= { sysApplMIB 3 }

-- Textual Conventions

RunState ::= TEXTUAL-CONVENTION
     STATUS      current
    DESCRIPTION
        "This TC describes the current execution state of
        a running application or process.  The possible
        values are:
          running(1),
          runnable(2),  - waiting for a resource (CPU, etc.)
          waiting(3),   - waiting for an event
          exiting(4),
          other(5)      - other invalid state"
    SYNTAX      INTEGER {
                running (1),
                runnable (2), -- waiting for resource (CPU, etc.)
```

```
            waiting (3),  -- waiting for event
            exiting (4),
            other (5)     -- other invalid state
            }

LongUtf8String ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "1024a"
    STATUS  current
    DESCRIPTION
          "To facilitate internationalization, this TC
           represents information taken from the ISO/IEC IS
           10646-1 character set, encoded as an octet string
            using the UTF-8 character encoding scheme described
           in RFC 2044 [10].  For strings in 7-bit US-ASCII,
           there is no impact since the UTF-8 representation
           is identical to the US-ASCII encoding."
    SYNTAX  OCTET STRING (SIZE (0..1024))

Utf8String ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "255a"
    STATUS  current
    DESCRIPTION
          "To facilitate internationalization, this TC
           represents information taken from the ISO/IEC IS
           10646-1 character set, encoded as an octet string
           using the UTF-8 character encoding scheme described
           in RFC 2044 [10].  For strings in 7-bit US-ASCII,
           there is no impact since the UTF-8 representation
           is identical to the US-ASCII encoding."
    SYNTAX  OCTET STRING (SIZE (0..255))



-- sysApplInstalled Group
-- This group provides information about application
packages
-- that have been installed on the host computer.  The group
-- contains two tables.  The first, the sysApplInstallPkgTable,
-- describes the application packages, the second, the
-- sysApplInstallElmtTable, describes the constituent elements
-- (files and executables) which compose an application package.

--
-- In order to appear in this group, an application and its
-- component files must be discoverable by the system itself,
-- possibly through some type of software installation mechanism
-- or registry.
```

```
-- sysApplInstallPkgTable
-- The system installed application packages table provides
-- information on the software packages installed on a system.
-- These packages may consist of many different files including
-- executable and non-executable files.

sysApplInstallPkgTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF SysApplInstallPkgEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "The table listing
the software application packages
      installed on a host computer. In order to appear in
      this table, it may be necessary for the application
      to be installed using some type of software
      installation mechanism or global registry so that its
      existence can be detected by the agent implementation."

   ::= { sysApplInstalled 1 }

sysApplInstallPkgEntry OBJECT-TYPE
   SYNTAX      SysApplInstallPkgEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "The logical row describing an installed application
      package."
   INDEX    { sysApplInstallPkgIndex }
   ::= { sysApplInstallPkgTable 1 }

SysApplInstallPkgEntry ::= SEQUENCE {
   sysApplInstallPkgIndex              Unsigned32,
   sysApplInstallPkgManufacturer       Utf8String,
   sysApplInstallPkgProductName        Utf8String,
   sysApplInstallPkgVersion            Utf8String,
   sysApplInstallPkgSerialNumber
    Utf8String,
   sysApplInstallPkgDate               DateAndTime,
   sysApplInstallPkgLocation           LongUtf8String
}

sysApplInstallPkgIndex OBJECT-TYPE
   SYNTAX      Unsigned32 (1..'ffffffff'h)
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "An integer used only for indexing purposes.
```

Generally monotonically increasing from 1 as new
applications are installed.

The value for each installed application must
remain constant at least from one re-initialization of
the network management entity which implements this
MIB module to the next re-initialization.

The specific value is meaningful only within a given SNMP
entity. A sysApplInstallPkgIndex value must not be re-used
until the next agent entity restart in the event the
installed application entry is deleted."
::= { sysApplInstallPkgEntry 1 }

sysApplInstallPkgManufacturer
OBJECT-TYPE
SYNTAX Utf8String
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The Manufacturer of the software application package."
::= { sysApplInstallPkgEntry 2 }

sysApplInstallPkgProductName OBJECT-TYPE
SYNTAX Utf8String
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The name assigned to the software application package
by the Manufacturer."
::= { sysApplInstallPkgEntry 3 }

sysApplInstallPkgVersion OBJECT-TYPE
SYNTAX Utf8String
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The version number assigned to the application package
by the manufacturer of the software."
::= { sysApplInstallPkgEntry 4 }

sysApplInstallPkgSerialNumber OBJECT-TYPE
SYNTAX Utf8String
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The serial number of the software assigned

```
by the
        manufacturer."
    ::= { sysApplInstallPkgEntry 5 }

sysApplInstallPkgDate OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The date and time this software application was installed
        on the host."
    ::= { sysApplInstallPkgEntry 6 }

sysApplInstallPkgLocation OBJECT-TYPE
    SYNTAX      LongUtf8String
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The complete path name where the application package
        is installed.  For example, the value would be
        '/opt/MyapplDir' if the application package was installed
        in the /opt/MyapplDir directory."
    ::= { sysApplInstallPkgEntry 7 }


-- sysApplInstallElmtTable
-- The table describing the individual application package
-- elements (files and executables) installed on the host computer.

sysApplInstallElmtTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF SysApplInstallElmtEntry
     MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table details the individual application package
        elements (files and executables) which comprise the
        applications defined in the sysApplInstallPkg Table.
        Each entry in this table has an index to the
        sysApplInstallPkg table to identify the application
        package of which it is a part. As a result, there may
        be many entries in this table for each instance in the
        sysApplInstallPkg Table.

        Table entries are indexed by sysApplInstallPkgIndex,
        sysApplInstallElmtIndex to facilitate retrieval of
        all elements associated with a particular installed
        application package."
    ::= { sysApplInstalled 2 }
```

```
sysApplInstallElmtEntry OBJECT-TYPE
   SYNTAX      SysApplInstallElmtEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "The logical row
describing an element of an installed
      application.  The element may be an executable or
      non-executable file."
   INDEX    {sysApplInstallPkgIndex, sysApplInstallElmtIndex}
   ::= { sysApplInstallElmtTable 1 }

SysApplInstallElmtEntry ::= SEQUENCE {
   sysApplInstallElmtIndex              Unsigned32,
   sysApplInstallElmtName               Utf8String,
   sysApplInstallElmtType               INTEGER,
   sysApplInstallElmtDate               DateAndTime,
   sysApplInstallElmtPath               LongUtf8String,
   sysApplInstallElmtSizeHigh           Unsigned32,
   sysApplInstallElmtSizeLow            Unsigned32,
   sysApplInstallElmtRole               BITS,
   sysApplInstallElmtModifyDate         DateAndTime,
   sysApplInstallElmtCurSizeHigh        Unsigned32,
   sysApplInstallElmtCurSizeLow         Unsigned32

}

sysApplInstallElmtIndex OBJECT-TYPE
   SYNTAX      Unsigned32 (1..'ffffffff'h)
    MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "An arbitrary integer used for indexing.  The value
      of this index is unique among all rows in this table
      that exist or have existed since the last agent restart."
   ::= { sysApplInstallElmtEntry 1 }


sysApplInstallElmtName OBJECT-TYPE
   SYNTAX      Utf8String
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The name of this element which is contained in the
      application."
   ::= { sysApplInstallElmtEntry 2 }
```

```
sysApplInstallElmtType OBJECT-TYPE
   SYNTAX      INTEGER {
                  unknown(1),
                  nonexecutable(2),
                  operatingSystem(3),  -- executable
                  deviceDriver(4),     -- executable
                  application(5)       -- executable
                  }
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The type of element that is
part of the installed
      application."
   ::= { sysApplInstallElmtEntry 3 }

sysApplInstallElmtDate OBJECT-TYPE
   SYNTAX      DateAndTime
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The date and time that this component was installed on
      the system."
   ::= { sysApplInstallElmtEntry 4 }

sysApplInstallElmtPath OBJECT-TYPE
   SYNTAX      LongUtf8String
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The full directory path where this element is installed.
      For example, the value would be '/opt/EMPuma/bin' for an
      element installed in the directory '/opt/EMPuma/bin'.
      Most application packages include information about the
      elements contained in the package. In addition, elements
      are typically installed in sub-directories under the
      package installation directory.  In cases where the
      element path names are not included
in the package
      information itself, the path can usually be determined
      by a simple search of the sub-directories.  If the
      element is not installed in that location and there is
      no other information available to the agent implementation,
      then the path is unknown and null is returned."
   ::= { sysApplInstallElmtEntry 5}

sysApplInstallElmtSizeHigh OBJECT-TYPE
   SYNTAX      Unsigned32
```

```
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The installed file size in 2^32 byte blocks. This is
        the size of the file on disk immediately after installation.

        For example, for a file with a total size of 4,294,967,296
        bytes, this variable would have a value of 1; for a file
        with a total size of 4,294,967,295 bytes this variable
        would be 0."
    ::= { sysApplInstallElmtEntry 6 }

sysApplInstallElmtSizeLow OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS
 read-only
    STATUS      current
    DESCRIPTION
        "The installed file size modulo 2^32 bytes.  This is
        the size of the file on disk immediately after installation.

        For example, for a file with a total size of 4,294,967,296
        bytes this variable would have a value of 0; for a file with
        a total size of 4,294,967,295 bytes this variable would be
        4,294,967,295."
    ::= { sysApplInstallElmtEntry 7 }

sysApplInstallElmtRole  OBJECT-TYPE
    SYNTAX      BITS {
                executable(0),
                  -- An application may have one or
                  -- more executable elements.  The rest of the
                  -- bits have no meaning if the element is not
                  -- executable.
                exclusive(1),
                  -- Only one copy of an exclusive element may be
                  -- running per invocation of the running
                  -- application.

            primary(2),
                  -- The primary executable.  An application can
                  -- have one, and only one element that is designated
                  -- as the primary executable.  The execution of
                  -- this element constitutes an invocation of
                  -- the application.  This is used by the agent
                  -- implementation to determine the initiation of
                  -- an application.  The primary executable must
                  -- remain running long enough for the agent
```

```
                -- implementation to detect its presence.
              required(3),
                -- An application may have zero or more required
                -- elements. All required elements must be running

                -- in order for the application to be judged to be
                -- running and healthy.
              dependent(4),
                -- An application may have
zero or more
                -- dependent elements. Dependent elements may
                -- not be running unless required elements are.
              unknown(5)
                -- Default value for the case when an operator
                -- has not yet assigned one of the other values.
                -- When set, bits 1, 2, 3, and 4 have no meaning.
              }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
      "An operator assigned value used in the determination of
      application status. This value is used by the agent to
      determine both the mapping of started processes to the
      initiation of an application, as well as to allow for a
      determination of application health. The default value,
      unknown(5), is used when an operator has not yet assigned
      one of the other values.  If unknown(5) is set, bits
      1 - 4 have no meaning.  The possible values are:

              executable(0),
                An application may have one or
                more executable elements.  The rest of the
                bits have no meaning if the element is not
                executable.
              exclusive(1),
                Only one copy of an exclusive element may be
                running per invocation of the running
                application.
              primary(2),
                The primary executable.  An application can
                have one, and only one element that is designated
                as the primary executable.  The execution of
                this element constitutes an invocation of
                the application.  This is used by the agent
                implementation to determine the initiation of
                an application.  The primary executable must
                remain running long enough for
```

the agent
implementation to detect its presence.
required(3),
An application may have zero or more required
elements. All required elements must be running
in order for the application to be judged to be
running and healthy.
dependent(4),
An application may have zero or more
dependent elements. Dependent elements may
not be running unless required elements are.
unknown(5)
Default value for the case when an operator
has not yet assigned one of the other values.
When set, bits 1, 2, 3, and 4 have no meaning.

sysApplInstallElmtRole is used by the agent implementation
in determining the initiation of an application, the
current state of a running application (see
sysApplRunCurrentState), when an application invocation is
no longer running, and the exit status of a terminated
application invocation (see sysApplPastRunExitState)."

DEFVAL { { unknown } }
::= { sysApplInstallElmtEntry 8 }

sysApplInstallElmtModifyDate OBJECT-TYPE
SYNTAX DateAndTime
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The date and time that this element was last modified.
Modification of the sysApplInstallElmtRole columnar
object does NOT constitute a modification of the element
itself and should not affect the value of this object."
::= { sysApplInstallElmtEntry 9 }

sysApplInstallElmtCurSizeHigh OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The current file size in 2^32 byte blocks.
For example, for a file with a total size of 4,294,967,296
bytes,
this variable would have a value of 1; for a file
with a total size of 4,294,967,295 bytes this variable
would be 0."

::= { sysApplInstallElmtEntry 10 }

sysApplInstallElmtCurSizeLow OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The current file size modulo 2^32 bytes.
For example, for a file with a total size of 4,294,967,296
bytes this variable would have a value of 0; for a file with
a total size of 4,294,967,295 bytes this variable would be
4,294,967,295."
::= { sysApplInstallElmtEntry 11 }

-- sysApplRun Group
-- This group models activity information for applications
-- that have been invoked and are either currently running,
-- or have previously run on the host system. Likewise,
-- the individual elements of an invoked application are
-- also modeled to show currently running processes, and
-- processes that
have run in the past.

-- sysApplRunTable
-- The sysApplRunTable contains the application instances
-- which are currently running on the host. Since a single
-- application might be invoked multiple times, an entry is
-- added to this table for each INVOCATION of an application.
-- The table is indexed by sysApplInstallPkgIndex, sysApplRunIndex
-- to enable managers to easily locate all invocations of
-- a particular application package.

sysApplRunTable OBJECT-TYPE
SYNTAX SEQUENCE OF SysApplRunEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The table describes the applications which are executing
on the host. Each time an application is invoked,
an entry is created in this table. When an application ends,
the entry is removed from this table and a corresponding
entry is created in the SysApplPastRunTable.

A new entry is created in this table whenever
the agent
implementation detects a new running process that is an

```
        installed application element whose sysApplInstallElmtRole
        designates it as being the application's primary executable
        (sysApplInstallElmtRole = primary(2) ).

        The table is indexed by sysApplInstallPkgIndex,
        sysApplRunIndex to enable managers to easily locate all
        invocations of a particular application package."
    ::= { sysApplRun 1 }

sysApplRunEntry OBJECT-TYPE
    SYNTAX      SysApplRunEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The logical row describing an application which is
        currently running on this host."
    INDEX    { sysApplInstallPkgIndex, sysApplRunIndex }
    ::= { sysApplRunTable   1 }

SysApplRunEntry ::= SEQUENCE {
    sysApplRunIndex                 Unsigned32,
    sysApplRunStarted               DateAndTime,
    sysApplRunCurrentState
            RunState
}

sysApplRunIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..'ffffffff'h)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Part of the index for this table. An arbitrary
        integer used only for indexing purposes. Generally
        monotonically increasing from 1 as new applications are
        started on the host, it uniquely identifies application
        invocations.

        The numbering for this index increases by 1 for each
        INVOCATION of an application, regardless of which
        installed application package this entry represents a
        running instance of.

        An example of the indexing for a couple of entries is
        shown below.

                :
            sysApplRunStarted.17.14
            sysApplRunStarted.17.63
```

```
            sysApplRunStarted.18.13
                :

        In this example, the agent has observed 12
application
        invocations when the application represented by entry 18
        in the sysApplInstallPkgTable is invoked.  The next
        invocation detected by the agent is an invocation of
        installed application package 17.  Some time later,
        installed application 17 is invoked a second time.

        NOTE: this index is not intended to reflect a real-time
        (wall clock time) ordering of application invocations;
        it is merely intended to uniquely identify running
        instances of applications.  Although the
        sysApplInstallPkgIndex is included in the INDEX clause
        for this table, it serves only to ease searching of
        this table by installed application and does not
        contribute to uniquely identifying table entries."
    ::= { sysApplRunEntry 1 }

sysApplRunStarted OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The
date and time that the application was started."
    ::= { sysApplRunEntry 2 }

sysApplRunCurrentState OBJECT-TYPE
    SYNTAX      RunState
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The current state of the running application instance.
        The possible values are running(1), runnable(2) but waiting
        for a resource such as CPU, waiting(3) for an event,
        exiting(4), or other(5). This value is based on an evaluation
        of the running elements of this application instance (see
        sysApplElmRunState) and their Roles as defined by
        sysApplInstallElmtRole.  An agent implementation may
        detect that an application instance is in the process of
        exiting if one or more of its REQUIRED elements are no
        longer running.  Most agent implementations will wait until
        a second internal poll has been completed to give the
        system time to start REQUIRED elements before
```

```
marking the
        application instance as exiting."
    ::= { sysApplRunEntry 3 }


-- sysApplPastRunTable
-- The sysApplPastRunTable provides a history of applications
-- previously run on the host computer. Entries are removed from
-- the sysApplRunTable and corresponding entries are added to this
-- table when an application becomes inactive. Entries remain in
-- this table until they are aged out when either the table size
-- reaches a maximum as determined by the sysApplPastRunMaxRows,
-- or when an entry has aged to exceed a time limit as set be
-- sysApplPastRunTblTimeLimit.
--
-- When aging out entries, the oldest entry, as determined by

-- the value of sysApplPastRunTimeEnded, will be removed first.

sysApplPastRunTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF SysApplPastRunEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A history of the applications that have previously run
        on the host
computer.  An entry's information is moved to
        this table from the sysApplRunTable when the invoked
        application represented by the entry ceases to be running.

        An agent implementation can determine that an application
        invocation is no longer running by evaluating the running
        elements of the application instance and their Roles as
        defined by sysApplInstallElmtRole.  Obviously, if there
        are no running elements for the application instance,
        then the application invocation is no longer running.
        If any one of the REQUIRED elements is not running,
        the application instance may be in the process of exiting.
        Most agent implementations will wait until a second internal
        poll has been completed to give the system time to either
        restart partial failures or to give all elements time to
        exit.  If, after the second poll, there are REQUIRED
        elements that
are not running, then the application
        instance may be considered by the agent implementation
        to no longer be running.

        Entries remain in the sysApplPastRunTable until they
```

```
        are aged out when either the table size reaches a maximum
        as determined by the sysApplPastRunMaxRows, or when an entry
        has aged to exceed a time limit as set by
        sysApplPastRunTblTimeLimit.

        Entries in this table are indexed by sysApplInstallPkgIndex,
        sysApplPastRunIndex to facilitate retrieval of all past
        run invocations of a particular installed application."
    ::= { sysApplRun 2 }

sysApplPastRunEntry OBJECT-TYPE
    SYNTAX      SysApplPastRunEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The logical row describing an invocation of an application
        which was previously run and has terminated.  The entry
        is basically copied from the sysApplRunTable
when the
        application instance terminates.  Hence, the entry's
        value for sysApplPastRunIndex is the same as its value was
        for sysApplRunIndex."
    INDEX    { sysApplInstallPkgIndex, sysApplPastRunIndex }
    ::= { sysApplPastRunTable   1 }

SysApplPastRunEntry ::= SEQUENCE {
    sysApplPastRunIndex                 Unsigned32,
    sysApplPastRunStarted               DateAndTime,
    sysApplPastRunExitState              INTEGER,
    sysApplPastRunTimeEnded              DateAndTime
}

sysApplPastRunIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..'ffffffff'h)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Part of the index for this table. An integer
        matching the value of the removed sysApplRunIndex
        corresponding to this row."
    ::= { sysApplPastRunEntry 1 }

sysApplPastRunStarted OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS
     current
    DESCRIPTION
```

```
        "The date and time that the application was started."
    ::= { sysApplPastRunEntry 2 }

sysApplPastRunExitState OBJECT-TYPE
    SYNTAX      INTEGER {
                complete (1), -- normal exit at sysApplRunTimeEnded
                failed (2),   -- abnormal exit
                other (3)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "The state of the application instance when it terminated.
       This value is based on an evaluation of the running elements
       of an application and their Roles as defined by
       sysApplInstallElmtRole.  An application instance is said to
       have exited in a COMPLETE state and its entry is removed
       from the sysApplRunTable and added to the sysApplPastRunTable
       when the agent detects that ALL elements of an application
       invocation are no longer running.  Most agent implementations
       will wait
until a second internal poll has been completed to
       give the system time to either restart partial failures or
       to give all elements time to exit.  A failed state occurs if,
       after the second poll, any elements continue to run but
       one or more of the REQUIRED elements are no longer running.
       All other combinations MUST be defined as OTHER."
    ::= { sysApplPastRunEntry 3 }

sysApplPastRunTimeEnded OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The DateAndTime the application instance was determined
        to be no longer running."
    ::= { sysApplPastRunEntry 4 }

-- sysApplElmtRunTable
-- The sysApplElmtRunTable contains an entry for each process that
-- is currently running on the host.  An entry is created in
-- this table for each process at the time it is started, and will
-- remain in the table until the process terminates.
--
-- The table
is indexed by sysApplElmtRunInstallPkg,
-- sysApplElmtRunInvocID, and sysApplElmtRunIndex to make it easy
-- to locate all running elements of a particular invoked application
```

```
-- which has been installed on the system.


sysApplElmtRunTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF SysApplElmtRunEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "The table describes the processes which are
      currently executing on the host system. Each entry
      represents a running process and is associated with
      the invoked application of which that process is a part, if
      possible.  This table contains an entry for every process
      currently running on the system, regardless of whether its
      'parent' application can be determined.  So, for example,
      processes like 'ps' and 'grep' will have entries though they
      are not associated with an installed application package.

      Because
a running application may involve
      more than one executable, it is possible to have
      multiple entries in this table for each application.
      Entries are removed from this table when the process
      terminates.
      The table is indexed by sysApplElmtRunInstallPkg,
      sysApplElmtRunInvocID, and sysApplElmtRunIndex to
      facilitate the retrieval of all running elements of a
      particular invoked application which has been installed on
      the system."
   ::= { sysApplRun 3 }

sysApplElmtRunEntry OBJECT-TYPE
   SYNTAX      SysApplElmtRunEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "The logical row describing a process currently
      running on this host.  When possible, the entry is
      associated with the invoked application of which it
      is a part."
   INDEX    { sysApplElmtRunInstallPkg, sysApplElmtRunInvocID,
            sysApplElmtRunIndex
}
   ::= { sysApplElmtRunTable   1 }

SysApplElmtRunEntry ::= SEQUENCE {
   sysApplElmtRunInstallPkg       Unsigned32,
   sysApplElmtRunInvocID          Unsigned32,
```

```
    sysApplElmtRunIndex             Unsigned32,
    sysApplElmtRunInstallID         Unsigned32,
    sysApplElmtRunTimeStarted       DateAndTime,
    sysApplElmtRunState             RunState,
    sysApplElmtRunName              LongUtf8String,
    sysApplElmtRunParameters        Utf8String,
    sysApplElmtRunCPU               TimeTicks,
    sysApplElmtRunMemory            Gauge32,
    sysApplElmtRunNumFiles          Gauge32,
    sysApplElmtRunUser              Utf8String
}

sysApplElmtRunInstallPkg OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Part of the index for this table, this value
        identifies the installed software package for
        the application of which this process
is a part.
        Provided that the process's 'parent' application can be
        determined, the value of this object is the same
        value as the sysApplInstallPkgIndex for the
        entry in the sysApplInstallPkgTable that corresponds
        to the installed application of which this process
        is a part.

        If, however, the 'parent' application cannot be
        determined, (for example the process is not part
        of a particular installed application), the value
        for this object is then '0', signifying that this
        process cannot be related back to an application,
        and in turn, an installed software package."
    ::= { sysApplElmtRunEntry 1 }

sysApplElmtRunInvocID OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Part of the index for this table, this value
        identifies the invocation of an application of which
         this process is a part.  Provided that the 'parent'
        application can be determined, the value of this object
        is the same value as the sysApplRunIndex for the
        corresponding application invocation in the
        sysApplRunTable.
```

```
        If, however, the 'parent' application cannot be
        determined, the value for this object is then '0',
        signifying that this process cannot be related back
        to an invocation of an application in the
        sysApplRunTable."
    ::= { sysApplElmtRunEntry 2 }

sysApplElmtRunIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Part of the index for this table.  A unique value
        for each process running on the host.  Wherever
        possible, this should be the system's native, unique
        identification number."
    ::= { sysApplElmtRunEntry 3 }


sysApplElmtRunInstallID
OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The index into the sysApplInstallElmtTable. The
        value of this object is the same value as the
        sysApplInstallElmtIndex for the application element
        of which this entry represents a running instance.
        If this process cannot be associated with an installed
        executable, the value should be '0'."
    ::= { sysApplElmtRunEntry 4 }

sysApplElmtRunTimeStarted OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The time the process was started."
    ::= { sysApplElmtRunEntry 5 }

sysApplElmtRunState OBJECT-TYPE
    SYNTAX      RunState
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The current state of the running process. The
```

```
        possible values are running(1), runnable(2) but waiting
         for a resource such as CPU, waiting(3) for an event,
        exiting(4), or other(5)."
    ::= { sysApplElmtRunEntry 6 }

sysApplElmtRunName OBJECT-TYPE
    SYNTAX      LongUtf8String
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The full path and filename of the process.
        For example, '/opt/MYYpkg/bin/myyproc' would
        be returned for process 'myyproc' whose execution
        path is '/opt/MYYpkg/bin/myyproc'."
    ::= { sysApplElmtRunEntry 7 }

sysApplElmtRunParameters OBJECT-TYPE
    SYNTAX      Utf8String
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The starting parameters for the process."
::= { sysApplElmtRunEntry 8 }

sysApplElmtRunCPU OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
         "The number of centi-seconds of the total system's
         CPU resources consumed by this process.
 Note that
         on a multi-processor system, this value may
         have been incremented by more than one centi-second
         in one centi-second of real (wall clock) time."
    ::= { sysApplElmtRunEntry 9 }

sysApplElmtRunMemory OBJECT-TYPE
    SYNTAX      Gauge32
    UNITS       "Kbytes"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The total amount of real system memory measured in
        Kbytes currently allocated to this process."

    ::= { sysApplElmtRunEntry 10 }
```

```
sysApplElmtRunNumFiles OBJECT-TYPE
   SYNTAX      Gauge32
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The number of regular files currently open by the
      process.  Transport connections (sockets)
      should NOT be included in the calculation of
      this value, nor should operating system specific
      special file types."
   ::= { sysApplElmtRunEntry 11 }

sysApplElmtRunUser OBJECT-TYPE
    SYNTAX      Utf8String
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The process owner's login name (e.g. root)."
   ::= { sysApplElmtRunEntry 12 }

-- sysApplElmtPastRunTable
-- The sysApplElmtPastRunTable maintains a history of
-- processes which have previously executed on
-- the host as part of an application. Upon termination
-- of a process, the entry representing the process is removed from
-- the sysApplElmtRunTable and a corresponding entry is created in
-- this table provided that the process was part of an
-- identifiable application.  If the process could not be associated

-- with an invoked application, no corresponding entry is created.
-- Hence, whereas the sysApplElmtRunTable contains an entry for
-- every process currently executing on the system, the
-- sysApplElmtPastRunTable only contains entries for processes
-- that previously executed as part of an invoked application.
--
-- Entries
remain in this table until they are aged out when
-- either the number of entries in the table reaches a
-- maximum as determined by sysApplElmtPastRunMaxRows, or
-- when an entry has aged to exceed a time limit as set by
-- sysApplElmtPastRunTblTimeLimit.  When aging out entries,
-- the oldest entry, as determined by the value of
-- sysApplElmtPastRunTimeEnded, will be removed first.
--
-- The table is indexed by sysApplInstallPkgIndex (from the
-- sysApplInstallPkgTable), sysApplElmtPastRunInvocID, and
-- sysApplElmtPastRunIndex to make it easy to locate all
-- previously executed processes of a particular invoked application
```

-- that has been installed on the system.

```
sysApplElmtPastRunTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF SysApplElmtPastRunEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "The table describes the processes which have previously
      executed on the host system as part of an application.
       Each entry represents a process which has previously
      executed and is associated with the invoked application
      of which it was a part.  Because an invoked application
      may involve more than one executable, it is possible
      to have multiple entries in this table for
      each application invocation. Entries are added
      to this table when the corresponding process in the
      sysApplElmtRun Table terminates.

      Entries remain in this table until they are aged out when
      either the number of entries in the table reaches a
      maximum as determined by sysApplElmtPastRunMaxRows, or
      when an entry has aged to exceed a time limit as set by
      sysApplElmtPastRunTblTimeLimit.  When aging out entries,
      the oldest entry, as determined by the value of
      sysApplElmtPastRunTimeEnded, will be removed first.

      The table is indexed by sysApplInstallPkgIndex (from the
       sysApplInstallPkgTable), sysApplElmtPastRunInvocID,
      and sysApplElmtPastRunIndex to make it easy to locate all
      previously executed processes of a particular invoked
      application that has been installed on the system."
   ::= { sysApplRun 4 }

sysApplElmtPastRunEntry OBJECT-TYPE
   SYNTAX      SysApplElmtPastRunEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "The logical row describing a process which was
      previously executed on this host as part of an
      installed application.  The entry is basically copied
      from the sysApplElmtRunTable when the process
      terminates.  Hence, the entry's value for
      sysApplElmtPastRunIndex is the same as its value
      was for sysApplElmtRunIndex.  Note carefully: only those
      processes which could be associated with an
      identified application are included in this table."
```

```
   INDEX    { sysApplInstallPkgIndex,
sysApplElmtPastRunInvocID,
            sysApplElmtPastRunIndex }
   ::= { sysApplElmtPastRunTable   1 }

SysApplElmtPastRunEntry ::= SEQUENCE {
   sysApplElmtPastRunInvocID          Unsigned32,
   sysApplElmtPastRunIndex            Unsigned32,
   sysApplElmtPastRunInstallID        Unsigned32,
   sysApplElmtPastRunTimeStarted      DateAndTime,
   sysApplElmtPastRunTimeEnded        DateAndTime,
   sysApplElmtPastRunName             LongUtf8String,
   sysApplElmtPastRunParameters       Utf8String,
   sysApplElmtPastRunCPU              TimeTicks,
   sysApplElmtPastRunMemory           Unsigned32,
   sysApplElmtPastRunNumFiles         Unsigned32,
   sysApplElmtPastRunUser             Utf8String
}

sysApplElmtPastRunInvocID OBJECT-TYPE
   SYNTAX      Unsigned32 (1..'ffffffff'h)
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "Part of the index for this table, this value
      identifies
the invocation of an application of which
      the process represented by this entry was a part.
      The value of this object is the same value as the
      sysApplRunIndex for the corresponding application
      invocation in the sysApplRunTable.  If the invoked
      application as a whole has terminated, it will be the
      same as the sysApplPastRunIndex."
   ::= { sysApplElmtPastRunEntry 1 }

sysApplElmtPastRunIndex OBJECT-TYPE
   SYNTAX      Unsigned32 (0..'ffffffff'h)
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "Part of the index for this table. An integer
      assigned by the agent equal to the corresponding
      sysApplElmtRunIndex which was removed from the
      sysApplElmtRunTable and moved to this table
      when the element terminated.

      Note: entries in this table are indexed by
      sysApplElmtPastRunInvocID, sysApplElmtPastRunIndex.
```

```
        The possibility
exists, though unlikely, of a
        collision occurring by a new entry which was run
        by the same invoked application (InvocID), and
        was assigned the same process identification number
        (ElmtRunIndex) as an element which was previously
        run by the same invoked application.

        Should this situation occur, the new entry replaces
        the old entry.

        See Section: 'Implementation Issues -
        sysApplElmtPastRunTable Entry Collisions' for the
        conditions that would have to occur in order for a
        collision to occur."
    ::= { sysApplElmtPastRunEntry 2 }


sysApplElmtPastRunInstallID OBJECT-TYPE
    SYNTAX      Unsigned32 (1..'ffffffff'h)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The index into the installed element table. The
        value of this object is the same value as the
        sysApplInstallElmtIndex for the application element

of which this entry represents a previously executed
        process."
    ::= { sysApplElmtPastRunEntry 3 }

sysApplElmtPastRunTimeStarted OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The time the process was started."
    ::= { sysApplElmtPastRunEntry 4 }

sysApplElmtPastRunTimeEnded OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The time the process ended."
    ::= { sysApplElmtPastRunEntry 5 }

sysApplElmtPastRunName OBJECT-TYPE
```

```
    SYNTAX      LongUtf8String
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The full path and filename of the process.
        For example, '/opt/MYYpkg/bin/myyproc' would
        be returned for process 'myyproc' whose execution
        path was '/opt/MYYpkg/bin/myyproc'."
    ::= { sysApplElmtPastRunEntry 6 }

sysApplElmtPastRunParameters
OBJECT-TYPE
    SYNTAX      Utf8String
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The starting parameters for the process."
    ::= { sysApplElmtPastRunEntry 7 }

sysApplElmtPastRunCPU OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The last known number of centi-seconds of the total
        system's CPU resources consumed by this process.
        Note that on a multi-processor system, this value may
        increment by more than one centi-second in one
        centi-second of real (wall clock) time."
    ::= { sysApplElmtPastRunEntry 8 }

sysApplElmtPastRunMemory OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    UNITS       "Kbytes"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The last known total amount of real system memory
        measured in Kbytes allocated to this process before it

     terminated."
    ::= { sysApplElmtPastRunEntry 9 }

sysApplElmtPastRunNumFiles OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
```

```
        "The last known number of files open by the
        process before it terminated.  Transport
        connections (sockets) should NOT be included in
        the calculation of this value."
    ::= { sysApplElmtPastRunEntry 10 }

sysApplElmtPastRunUser OBJECT-TYPE
    SYNTAX      Utf8String
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The process owner's login name (e.g. root)."
    ::= { sysApplElmtPastRunEntry 11 }


-- Additional Scalar objects to control table sizes

sysApplPastRunMaxRows OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The maximum number of entries allowed in the
        sysApplPastRunTable.
Once the number of rows in
        the sysApplPastRunTable reaches this value, the
        management subsystem will remove the oldest entry
        in the table to make room for the new entry to be added.
        Entries will be removed on the basis of oldest
        sysApplPastRunTimeEnded value first.

        This object may be used to control the amount of
        system resources that can used for sysApplPastRunTable
        entries. A conforming implementation should attempt
        to support the default value, however, a lesser value
        may be necessary due to implementation-dependent issues
        and resource availability."
    DEFVAL      { 500 }
    ::= { sysApplRun 5 }

sysApplPastRunTableRemItems OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter of the number of entries removed from
        the sysApplPastRunTable because of table size limitations
```

```
    as set in sysApplPastRunMaxRows.  This counter is the
       number of entries the management subsystem has had to
       remove in order to make room for new entries (so as not
       to exceed the limit set by sysApplPastRunMaxRows) since
       the last initialization of the management subsystem."
    ::= { sysApplRun 6 }

sysApplPastRunTblTimeLimit OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    UNITS       "seconds"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
       "The maximum time in seconds which an entry in the
        sysApplPastRunTable may exist before it is removed.
        Any entry that is older than this value will be
        removed (aged out) from the table.

        Note that an entry may be aged out prior to reaching
        this time limit if it is the oldest entry in the
        table and must be removed to make space for a new
        entry so as to not exceed sysApplPastRunMaxRows."
     DEFVAL      { 7200 }
    ::= { sysApplRun 7 }

sysApplElemPastRunMaxRows OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
       "The maximum number of entries allowed in the
       sysApplElmtPastRunTable.  Once the number of rows in
       the sysApplElmtPastRunTable reaches this value,
       the management subsystem will remove the oldest entry
       to make room for the new entry to be added.  Entries
       will be removed on the basis of oldest
       sysApplElmtPastRunTimeEnded value first.
       This object may be used to control the amount of
       system resources that can used for sysApplElemPastRunTable
       entries. A conforming implementation should attempt
       to support the default value, however, a lesser value
       may be necessary due to implementation-dependent issues
       and resource availability."
    DEFVAL
    { 500 }
    ::= { sysApplRun 8 }

sysApplElemPastRunTableRemItems OBJECT-TYPE
```

```
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter of the number of entries removed from the
        sysApplElemPastRunTable because of table size limitations
        as set in sysApplElemPastRunMaxRows.  This counter is the
        number of entries the management subsystem has had to
        remove in order to make room for new entries (so as not
        to exceed the limit set by sysApplElemPastRunMaxRows) since
        the last initialization of the management subsystem."
    ::= { sysApplRun 9 }

sysApplElemPastRunTblTimeLimit OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    UNITS       "seconds"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The maximum time in seconds which an entry in the
         sysApplElemPastRunTable may exist before it is removed.

        Any entry that is older than this value will be
         removed (aged out) from the table.

         Note that an entry may be aged out prior to reaching
         this time limit if it is the oldest entry in the
         table and must be removed to make space for a new
         entry so as to not exceed sysApplElemPastRunMaxRows."
    DEFVAL      { 7200 }
    ::= { sysApplRun 10 }

sysApplAgentPollInterval  OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    UNITS       "seconds"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The minimum interval in seconds that the management
        subsystem implementing this MIB will poll the status
        of the managed resources. Because of the non-trivial
        effort involved in polling the managed resources,
        and because the method for obtaining the status of
        the managed resources is implementation-dependent,
        a conformant implementation
may chose a lower bound
        greater than 0.
```

A value of 0 indicates that there is no delay
in the passing of information from the managed
resources to the agent."
DEFVAL { 60 }
::= { sysApplRun 11 }

-- sysApplMap Group
-- This group contains a table, the sysApplMapTable,
-- whose sole purpose is to provide a 'backwards'
-- mapping so that, given a known sysApplElmtRunIndex
-- (process identification number), the corresponding invoked
-- application (sysApplRunIndex), installed element
-- (sysApplInstallElmtIndex), and installed application
-- package (sysApplInstallPkgIndex) can be quickly determined.
--
-- The table will contain one entry for each process
-- currently running on the system.
--
-- A backwards mapping is extremely useful since the tables
-- in this MIB module are typically indexed with the
-- installed application package (sysApplInstallPkgIndex)
-- as the primary key, and on down
as required by the
-- specific table, with the process ID number (sysApplElmtRunIndex)
-- being the least significant key.
--
-- It is expected that management applications will use
-- this mapping table by doing a 'GetNext' operation with
-- the known process ID number (sysApplElmtRunIndex) as the partial
-- instance identifier. Assuming that there is an entry for
-- the process, the result should return a single columnar value,
-- the sysApplMapInstallPkgIndex, with the sysApplElmtRunIndex,
-- sysApplRunIndex, and sysApplInstallElmtIndex contained in the
-- instance identifier for the returned MIB object value.
--
-- NOTE: if the process can not be associated back to an
-- invoked application installed on the system, then the
-- value returned for the columnar value sysApplMapInstallPkgIndex
-- will be '0' and the instance portion of the object-identifier
-- will be the process ID number (sysApplElmtRunIndex) followed

-- by 0.0.

sysApplMapTable
OBJECT-TYPE
SYNTAX SEQUENCE OF SysApplMapEntry
MAX-ACCESS not-accessible

```
    STATUS      current
    DESCRIPTION
        "The sole purpose of this table is to provide a
        'backwards' mapping so that, given a known
        sysApplElmtRunIndex (process identification number),
        the corresponding invoked application (sysApplRunIndex),
        installed element (sysApplInstallElmtIndex), and
        installed application package (sysApplInstallPkgIndex)
        can be quickly determined.

        This table will contain one entry for each process
        that is currently executing on the system.

        It is expected that management applications will use
        this mapping table by doing a 'GetNext' operation with
        the known process ID number (sysApplElmtRunIndex) as the
        partial instance identifier.  Assuming that there is an
        entry for the process, the result should return a single
        columnar
value, the sysApplMapInstallPkgIndex, with the
        sysApplElmtRunIndex, sysApplRunIndex, and
        sysApplInstallElmtIndex contained in the instance identifier
        for the returned MIB object value.

        NOTE: if the process can not be associated back to an
        invoked application installed on the system, then the
        value returned for the columnar value
        sysApplMapInstallPkgIndex will be '0' and the instance
        portion of the object-identifier will be the process ID
        number (sysApplElmtRunIndex) followed by 0.0."
    ::= { sysApplMap 1 }

sysApplMapEntry OBJECT-TYPE
    SYNTAX      SysApplMapEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A logical row representing a process currently running
         on the system.  This entry provides the index mapping from
         process identifier, back to the invoked application,
         installed element, and finally, the
installed application
         package.  The entry includes only one accessible columnar
         object, the sysApplMapInstallPkgIndex, but the
         invoked application and installed element can be
         determined from the instance identifier since they form
         part of the index clause."
    INDEX  { sysApplElmtRunIndex, sysApplElmtRunInvocID,
```

```
            sysApplMapInstallElmtIndex }
    ::= { sysApplMapTable 1 }

SysApplMapEntry ::= SEQUENCE {
    sysApplMapInstallElmtIndex    Unsigned32,
    sysApplMapInstallPkgIndex     Unsigned32
}

sysApplMapInstallElmtIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The index into the sysApplInstallElmtTable. The
        value of this object is the same value as the
        sysApplInstallElmtIndex for the application element
        of which this entry represents a running instance.
        If this
process cannot be associated to an installed
        executable, the value should be '0'."
    ::= { sysApplMapEntry 1 }

sysApplMapInstallPkgIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of this object identifies the installed
        software package for the application of which this
        process is a part.  Provided that the process's 'parent'
        application can be determined, the value of this object
        is the same value as the sysApplInstallPkgIndex for the
        entry in the sysApplInstallPkgTable that corresponds
        to the installed application of which this process
        is a part.

        If, however, the 'parent' application cannot be
        determined, (for example the process is not part
        of a particular installed application), the value
        for this object is then '0', signifying that this

 process cannot be related back to an application,
        and in turn, an installed software package."
    ::= { sysApplMapEntry 2 }


-- Conformance Macros
sysApplMIBCompliances  OBJECT IDENTIFIER ::= { sysApplConformance 1 }
```

```
sysApplMIBGroups      OBJECT IDENTIFIER ::= { sysApplConformance 2 }

sysApplMIBCompliance MODULE-COMPLIANCE
   STATUS  current
   DESCRIPTION
      "Describes the requirements for conformance to
      the System Application MIB"
   MODULE  -- this module
      MANDATORY-GROUPS { sysApplInstalledGroup,
                         sysApplRunGroup, sysApplMapGroup }
   ::= { sysApplMIBCompliances 1 }

sysApplInstalledGroup OBJECT-GROUP
   OBJECTS { sysApplInstallPkgManufacturer,
             sysApplInstallPkgProductName,
             sysApplInstallPkgVersion,
             sysApplInstallPkgSerialNumber,
             sysApplInstallPkgDate,
             sysApplInstallPkgLocation,
             sysApplInstallElmtName,
              sysApplInstallElmtType,
             sysApplInstallElmtDate,
             sysApplInstallElmtPath,
             sysApplInstallElmtSizeHigh,
             sysApplInstallElmtSizeLow,
             sysApplInstallElmtRole,
             sysApplInstallElmtModifyDate,
             sysApplInstallElmtCurSizeHigh,
             sysApplInstallElmtCurSizeLow }
   STATUS  current
   DESCRIPTION
      "The system application installed group contains
      information about applications and their constituent
      components which have been installed on the host system."
   ::= { sysApplMIBGroups 1 }

sysApplRunGroup OBJECT-GROUP
   OBJECTS { sysApplRunStarted,
             sysApplRunCurrentState,
             sysApplPastRunStarted,
             sysApplPastRunExitState,
             sysApplPastRunTimeEnded,
             sysApplElmtRunInstallID,
             sysApplElmtRunTimeStarted,
             sysApplElmtRunState,
              sysApplElmtRunName,
             sysApplElmtRunParameters,
             sysApplElmtRunCPU,
```

```
            sysApplElmtRunMemory,
            sysApplElmtRunNumFiles,
            sysApplElmtRunUser,
            sysApplElmtPastRunInstallID,
            sysApplElmtPastRunTimeStarted,
            sysApplElmtPastRunTimeEnded,
            sysApplElmtPastRunName,
            sysApplElmtPastRunParameters,
            sysApplElmtPastRunCPU,
            sysApplElmtPastRunMemory,
            sysApplElmtPastRunNumFiles,
            sysApplElmtPastRunUser,
            sysApplPastRunMaxRows,
            sysApplPastRunTableRemItems,
            sysApplPastRunTblTimeLimit,
            sysApplElemPastRunMaxRows,
            sysApplElemPastRunTableRemItems,
            sysApplElemPastRunTblTimeLimit,
            sysApplAgentPollInterval }
    STATUS  current
    DESCRIPTION
        "The system application
 run group contains information
        about applications and associated elements which have
        run or are currently running on the host system."
    ::= { sysApplMIBGroups 2 }

 sysApplMapGroup OBJECT-GROUP
    OBJECTS { sysApplMapInstallPkgIndex }
    STATUS  current
    DESCRIPTION
        "The Map Group contains a single table, sysApplMapTable,
        that provides a backwards mapping for determining the
        invoked application, installed element, and installed
        application package given a known process identification
        number."
 ::= { sysApplMIBGroups 3 }

 END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/SYSAPPL-MIB
No license file was found, but licenses were detected in source scan.

IANA-ITU-ALARM-TC-MIB DEFINITIONS ::= BEGIN

IMPORTS
  MODULE-IDENTITY, mib-2
```

```
    FROM SNMPv2-SMI         -- [RFC2578]
  TEXTUAL-CONVENTION
    FROM SNMPv2-TC;         -- [RFC2579]



ianaItuAlarmNumbers MODULE-IDENTITY
   LAST-UPDATED "200409090000Z"  -- September 09, 2004
   ORGANIZATION "IANA"
   CONTACT-INFO
      "Postal:    Internet Assigned Numbers Authority
                  Internet Corporation for Assigned Names
                  and Numbers
                  4676 Admiralty Way, Suite 330
                  Marina del Rey, CA 90292-6601
                  USA

      Tel:    +1  310-823-9358
      E-Mail: iana@iana.org"
   DESCRIPTION
      "The MIB module defines the ITU Alarm
      textual convention for objects expected to require
      regular extension.

      Copyright (C) The Internet Society (2004).  The
      initial version of this MIB module
 was published
      in RFC 3877.  For full legal notices see the RFC
      itself.  Supplementary information may be available on:
      http://www.ietf.org/copyrights/ianamib.html"
    REVISION    "200409090000Z"  -- September 09, 2004
    DESCRIPTION
       "Initial version, published as RFC 3877."
   ::= { mib-2 119 }

IANAItuProbableCause ::= TEXTUAL-CONVENTION
  STATUS current
  DESCRIPTION
     "ITU-T probable cause values.  Duplicate values defined in
      X.733 are appended with X733 to ensure syntactic uniqueness.
      Probable cause value 0 is reserved for special purposes.

      The Internet Assigned Number Authority (IANA) is responsible
      for the assignment of the enumerations in this TC.
      IANAItuProbableCause value of 0 is reserved for special
      purposes and MUST NOT be assigned.

      Values of IANAItuProbableCause in the range 1 to 1023 are
```

reserved for causes that correspond to ITU-T probable cause.

All other requests for new causes will be handled on a first-come, first served basis and will be assigned enumeration values starting with 1025.

Request should come in the form of well-formed

SMI [RFC2578] for enumeration names that are unique and sufficiently descriptive.

While some effort will be taken to ensure that new probable causes do not conceptually duplicate existing probable causes it is acknowledged that the existence of conceptual duplicates in the starting probable cause list is an known industry reality.

To aid IANA in the administration of probable cause names and values, the OPS Area Director will appoint one or more experts to help review requests.

See http://www.iana.org"

```
  REFERENCE
     "ITU Recommendation M.3100, 'Generic Network Information
        Model', 1995
     ITU Recommendation X.733, 'Information Technology
- Open
        Systems Interconnection - System Management: Alarm
        Reporting Function', 1992
     ITU Recommendation X.736, 'Information Technology - Open
        Systems Interconnection - System Management: Security
        Alarm Reporting Function', 1992"

  SYNTAX        INTEGER
        {
        -- The following probable causes were defined in M.3100
         aIS  (1),
         callSetUpFailure  (2),
         degradedSignal  (3),
         farEndReceiverFailure  (4),
         framingError  (5),
         lossOfFrame (6),
         lossOfPointer  (7),
         lossOfSignal  (8),
         payloadTypeMismatch (9),
         transmissionError (10),
         remoteAlarmInterface (11),
```

```
            excessiveBER  (12),
            pathTraceMismatch  (13),
            unavailable  (14),
            signalLabelMismatch (15),
            lossOfMultiFrame (16),
            receiveFailure (17),

        transmitFailure (18),
            modulationFailure (19),
            demodulationFailure (20),
            broadcastChannelFailure (21),


            connectionEstablishmentError (22),
            invalidMessageReceived (23),
            localNodeTransmissionError (24),
            remoteNodeTransmissionError (25),
            routingFailure (26),

--Values 27-50 are reserved for communications alarm related
--probable causes
-- The following are used with equipment alarm.

            backplaneFailure (51),
            dataSetProblem  (52),
            equipmentIdentifierDuplication  (53),
            externalIFDeviceProblem  (54),
            lineCardProblem (55),
            multiplexerProblem  (56),
            nEIdentifierDuplication  (57),
            powerProblem  (58),
            processorProblem  (59),
            protectionPathFailure  (60),
            receiverFailure  (61),
            replaceableUnitMissing  (62),
            replaceableUnitTypeMismatch
 (63),
            synchronizationSourceMismatch  (64),
            terminalProblem   (65),
            timingProblem   (66),
            transmitterFailure  (67),
            trunkCardProblem  (68),
            replaceableUnitProblem  (69),
            realTimeClockFailure (70),
--An equipment alarm to be issued if the system detects that the
--real time clock has failed
            antennaFailure (71),
            batteryChargingFailure (72),
```

diskFailure (73),
frequencyHoppingFailure (74),
iODeviceError (75),
lossOfSynchronisation (76),
lossOfRedundancy (77),
powerSupplyFailure (78),
signalQualityEvaluationFailure (79),
tranceiverFailure (80),
protectionMechanismFailure (81),
protectingResourceFailure (82),
-- Values 83-100 are reserved for equipment alarm related probable
-- causes
-- The following are used with environmental alarm.
airCompressorFailure (101),

airConditioningFailure (102),
airDryerFailure (103),
batteryDischarging (104),
batteryFailure (105),
commercialPowerFailure (106),
coolingFanFailure (107),
engineFailure (108),
fireDetectorFailure (109),
fuseFailure (110),
generatorFailure (111),
lowBatteryThreshold (112),
pumpFailure (113),
rectifierFailure (114),
rectifierHighVoltage (115),
rectifierLowFVoltage (116),
ventilationsSystemFailure (117),
enclosureDoorOpen (118),
explosiveGas (119),
fire (120),
flood (121),
highHumidity (122),
highTemperature (123),
highWind (124),
iceBuildUp (125),
intrusionDetection (126),
lowFuel
(127),
lowHumidity (128),
lowCablePressure (129),
lowTemperatue (130),
lowWater (131),
smoke (132),

```
        toxicGas  (133),
        coolingSystemFailure (134),
        externalEquipmentFailure (135),
        externalPointFailure (136),
-- Values 137-150 are reserved for environmental alarm related
-- probable causes
-- The following are used with Processing error alarm.
        storageCapacityProblem (151),
        memoryMismatch  (152),
        corruptData  (153),
        outOfCPUCycles   (154),
        sfwrEnvironmentProblem  (155),
        sfwrDownloadFailure  (156),
        lossOfRealTimel (157),
--A processing error alarm to be issued after the system has
--reinitialised.  This will indicate
--to the management systems that the view they have of the managed


--system may no longer
--be valid.  Usage example: The managed
--system issues this alarm
 after a reinitialization with severity
--warning to inform the
--management system about the event.  No clearing notification will
--be sent.
        applicationSubsystemFailure (158),
        configurationOrCustomisationError (159),
        databaseInconsistency (160),
        fileError (161),
        outOfMemory (162),
        softwareError (163),
        timeoutExpired (164),
        underlayingResourceUnavailable (165),
        versionMismatch (166),
--Values 168-200 are reserved for processing error alarm related
-- probable causes.
        bandwidthReduced (201),
        congestion (202),
        excessiveErrorRate (203),
        excessiveResponseTime (204),
        excessiveRetransmissionRate (205),
        reducedLoggingCapability (206),
        systemResourcesOverload (207 ),
        -- The following were defined X.733
        adapterError (500),
        applicationSubsystemFailture
```

(501),
bandwidthReducedX733 (502),
callEstablishmentError (503),
communicationsProtocolError (504),
communicationsSubsystemFailure (505),
configurationOrCustomizationError (506),
congestionX733 (507),
coruptData (508),
cpuCyclesLimitExceeded (509),
dataSetOrModemError (510),
degradedSignalX733 (511),
dteDceInterfaceError (512),
enclosureDoorOpenX733 (513),
equipmentMalfunction (514),
excessiveVibration (515),
fileErrorX733 (516),
fireDetected (517),
framingErrorX733 (518),
heatingVentCoolingSystemProblem (519),
humidityUnacceptable (520),
inputOutputDeviceError (521),
inputDeviceError (522),

lanError (523),
leakDetected (524),
localNodeTransmissionErrorX733 (525),

lossOfFrameX733 (526),
lossOfSignalX733 (527),
materialSupplyExhausted (528),
multiplexerProblemX733 (529),
outOfMemoryX733 (530),
ouputDeviceError (531),
performanceDegraded (532),
powerProblems (533),
pressureUnacceptable (534),
processorProblems (535),
pumpFailureX733 (536),
queueSizeExceeded (537),
receiveFailureX733 (538),
receiverFailureX733 (539),
remoteNodeTransmissionErrorX733 (540),
resourceAtOrNearingCapacity (541),
responseTimeExecessive (542),
retransmissionRateExcessive (543),
softwareErrorX733 (544),
softwareProgramAbnormallyTerminated (545),

```
            softwareProgramError (546),
            storageCapacityProblemX733 (547),
            temperatureUnacceptable (548),
            thresholdCrossed (549),
            timingProblemX733
(550),
            toxicLeakDetected (551),
            transmitFailureX733 (552),
            transmiterFailure (553),
            underlyingResourceUnavailable (554),
            versionMismatchX733 (555),
            -- The following are defined in X.736
            authenticationFailure (600),
            breachOfConfidentiality (601),
            cableTamper (602),
            delayedInformation (603),
            denialOfService (604),
            duplicateInformation (605),
            informationMissing (606),
            informationModificationDetected (607),
            informationOutOfSequence (608),
            keyExpired (609),
            nonRepudiationFailure (610),
            outOfHoursActivity (611),
            outOfService (612),
            proceduralError (613),


            unauthorizedAccessAttempt (614),
            unexpectedInformation (615),

            other (1024)
            }

IANAItuEventType ::= TEXTUAL-CONVENTION
   STATUS current
  DESCRIPTION
          "The ITU event Type values.

          The Internet Assigned Number Authority (IANA) is
          responsible for the assignment of the enumerations
          in this TC.

          Request should  come in the form of well-formed
          SMI [RFC2578] for enumeration names that are unique
          and sufficiently descriptive.

          See http://www.iana.org "
```

```
  REFERENCE
        "ITU Recommendation X.736, 'Information Technology - Open
         Systems Interconnection - System Management: Security
         Alarm Reporting Function', 1992"
  SYNTAX        INTEGER
        {
        other (1),
        communicationsAlarm (2),
        qualityOfServiceAlarm (3),
        processingErrorAlarm (4),
        equipmentAlarm (5),
        environmentalAlarm (6),
        integrityViolation (7),
        operationalViolation (8),
        physicalViolation (9),
        securityServiceOrMechanismViolation
(10),
        timeDomainViolation (11)
        }

END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/IANA-ITU-ALARM-TC-MIB
No license file was found, but licenses were detected in source scan.

```
PKTC-IETF-MTA-MIB DEFINITIONS ::= BEGIN

IMPORTS
  MODULE-IDENTITY,
  OBJECT-TYPE,
  OBJECT-IDENTITY,
  Unsigned32,
  Counter32,
  NOTIFICATION-TYPE,
  mib-2
      FROM SNMPv2-SMI                 -- [RFC2578]
  TEXTUAL-CONVENTION,
  RowStatus,
  TruthValue
      FROM SNMPv2-TC                  -- [RFC2579]
  OBJECT-GROUP,
  MODULE-COMPLIANCE,
  NOTIFICATION-GROUP
      FROM SNMPv2-CONF                -- [RFC2580]
  InetAddressType,
  InetAddress
      FROM INET-ADDRESS-MIB           -- [RFC4001]
```

```
sysDescr
    FROM SNMPv2-MIB                 -- [RFC3418]
SnmpAdminString
    FROM SNMP-FRAMEWORK-MIB         -- [RFC3411]
docsDevSoftwareGroupV2
    FROM DOCS-CABLE-DEVICE-MIB      -- [RFC4639]
DocsX509ASN1DEREncodedCertificate,
docsBpi2CodeDownloadGroup
    FROM DOCS-IETF-BPI2-MIB         -- [RFC4131]
LongUtf8String
     FROM SYSAPPL-MIB               -- [RFC2287]
ifPhysAddress
    FROM IF-MIB;                    -- [RFC2863]

pktcIetfMtaMib MODULE-IDENTITY
LAST-UPDATED "200609180000Z" -- September 18, 2006
ORGANIZATION "IETF IP over Cable Data Network Working Group"
CONTACT-INFO
   "Eugene Nechamkin
    Broadcom Corporation,
    200-13711 International Place,



    Richmond, BC, V6V 2Z8
    CANADA
    Phone: +1 604 233 8500
    Email: enechamkin@broadcom.com

    Jean-Francois Mule
    Cable Television Laboratories, Inc.
    858 Coal Creek Circle
    Louisville, CO 80027-9750
    U.S.A.
    Phone: +1 303 661 9100
    Email: jf.mule@cablelabs.com

IETF IPCDN Working Group
    General Discussion: ipcdn@ietf.org
    Subscribe: http://www.ietf.org/mailman/listinfo/ipcdn
    Archive: ftp://ftp.ietf.org/ietf-mail-archive/ipcdn
    Co-Chair: Jean-Francois Mule, jf.mule@cablelabs.com
     Co-Chair: Richard Woundy, Richard_Woundy@cable.comcast.com"

DESCRIPTION
  "This MIB module defines the basic management object
   for the Multimedia Terminal Adapter devices compliant
   with PacketCable and IPCablecom requirements.
```

```
      Copyright (C) The IETF Trust (2006).  This version of
      this MIB module is part of RFC 4682; see the RFC itself for
      full legal notices."

    REVISION    "200609180000Z"   -- September 18, 2006

    DESCRIPTION
      "Initial version, published as RFC 4682."

::=  { mib-2 140 }

  -- Textual Conventions

PktcMtaDevProvEncryptAlg  ::= TEXTUAL-CONVENTION
    STATUS      current
    DESCRIPTION
        " This textual convention defines various types of the
          encryption algorithms used for the encryption of the MTA
          configuration file.  The description of the encryption
          algorithm for each enumerated value is as follows:

          'none(0)'            no encryption
 is used,
          'des64CbcMode(1)'    DES 64-bit key in CBC mode,




          't3Des192CbcMode(2)' 3DES 192-bit key in CBC mode,
          'aes128CbcMode(3)'   AES 128-bit key in CBC mode,
          'aes256CbcMode(4)'   AES 256-bit key in CBC mode."
    SYNTAX      INTEGER  {
                none            (0),
                des64CbcMode    (1),
                t3Des192CbcMode  (2),
                aes128CbcMode    (3),
                aes256CbcMode    (4)
    }

--====================================================================
-- The MTA MIB module only supports a single Provisioning Server.
--====================================================================

pktcMtaNotification OBJECT IDENTIFIER ::= { pktcIetfMtaMib 0 }
pktcMtaMibObjects  OBJECT IDENTIFIER ::= { pktcIetfMtaMib 1 }
pktcMtaDevBase     OBJECT IDENTIFIER ::= { pktcMtaMibObjects 1 }
pktcMtaDevServer   OBJECT IDENTIFIER ::= { pktcMtaMibObjects 2 }
pktcMtaDevSecurity OBJECT IDENTIFIER ::= { pktcMtaMibObjects 3
```

```
 }
pktcMtaDevErrors   OBJECT IDENTIFIER ::= { pktcMtaMibObjects 4 }
pktcMtaConformance  OBJECT IDENTIFIER ::= { pktcIetfMtaMib 2 }

--
-- The following pktcMtaDevBase group describes the base MTA objects
--

pktcMtaDevResetNow  OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     " This object controls the MTA software reset.
       Reading this object always returns 'false'.  Setting this
       object to 'true' causes the device to reset immediately
       and the following actions to occur:
          1.  All connections (if present) are flushed locally.
          2.  All current actions such as ringing immediately
              terminate.
          3.  Requests for signaling notifications, such as
              notification based on digit map recognition, are
              flushed.
          4.  All endpoints are disabled.
          5.  The provisioning flow is started at step MTA-1.

    If a value is written into an instance of
       pktcMtaDevResetNow, the agent MUST NOT retain the supplied
       value across MTA re-initializations or reboots."
  REFERENCE



     " PacketCable MTA Device Provisioning Specification."
  ::= { pktcMtaDevBase 1 }

pktcMtaDevSerialNumber OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object specifies the manufacturer's serial
       number of this MTA.  The value of this object MUST be
       identical to the value specified in DHCP option 43,
       sub-option 4.  The list of sub-options for DHCP option
       43 are defined in the PacketCable MTA Device
       Provisioning Specification."
  REFERENCE
```

```
      " PacketCable MTA Device Provisioning Specification."
  ::= { pktcMtaDevBase 2 }

pktcMtaDevSwCurrentVers OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      " This object identifies the software version currently
       operating in the MTA.
       The MTA MUST return a string descriptive of the current
       software load.  This object should use the syntax
       defined by the individual vendor to identify the software
       version.  The data presented in this object MUST be
       identical to the software version information contained
       in the 'sysDescr' MIB object of the MTA.  The value of
       this object MUST be identical to the value specified in
       DHCP option 43, sub-option 6.  The list of sub-options for
       DHCP option 43 are defined in the PacketCable MTA Device
       Provisioning Specification."
  REFERENCE
      " PacketCable MTA Device Provisioning Specification."

::= { pktcMtaDevBase 3 }

pktcMtaDevFQDN      OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object contains the Fully Qualified
 Domain Name for
       this MTA.  The MTA FQDN is used to uniquely identify the
       device to the PacketCable back office elements."



  ::= { pktcMtaDevBase 4 }

pktcMtaDevEndPntCount     OBJECT-TYPE
  SYNTAX      Unsigned32 (1..255)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object contains the number of physical endpoints for
       this MTA."
  ::= { pktcMtaDevBase 5 }
```

```
pktcMtaDevEnabled     OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
      " This object contains the MTA Admin Status of this device.
        If this object is set to 'true', the MTA is
        administratively enabled, and the MTA MUST be able to
        interact with the PacketCable entities, such as CMS,
        Provisioning Server, KDC, and other MTAs and MGs on all
        PacketCable interfaces.
        If this object is set to 'false', the MTA is
        administratively
 disabled, and the MTA MUST perform the
        following actions for all endpoints:
           - Shut down all media sessions, if present.
           - Shut down Network Control Signaling (NCS)
           signaling by following the Restart in
           Progress procedures in the PacketCable NCS
           specification.
        The MTA must execute all actions required to
        enable or disable the telephony services for all
        endpoints immediately upon receipt of an SNMP SET
        operation.

        Additionally, the MTA MUST maintain the SNMP Interface
        for management and also the SNMP Key management interface.
        Also, the MTA MUST NOT continue Kerberized key management
        with CMSes until this object is set to 'true'.
        Note: MTAs MUST renew the CMS Kerberos tickets according
        to the PacketCable Security or IPCablecom Specification.
        If a value is written into an instance
 of
        pktcMtaDevEnabled, the agent MUST NOT retain the supplied
        value across MTA re-initializations or reboots."
  REFERENCE
     " PacketCable MTA Device Provisioning Specification;
       PacketCable Security Specification;
       PacketCable Network-Based Call Signaling Protocol




       Specification."
  ::= { pktcMtaDevBase 6 }

pktcMtaDevTypeIdentifier     OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-only
```

```
  STATUS      current
  DESCRIPTION
     " This object provides the MTA device type identifier.  The
       value of this object must be a copy of the DHCP option 60
       value exchanged between the MTA and the DHCP server.  The
       DHCP option 60 value contains an ASCII-encoded string
       identifying capabilities of the MTA as defined in the
       PacketCable MTA Device Provisioning Specification."
  REFERENCE
     " RFC 2132, DHCP Options and BOOTP Vendor Extensions;
       PacketCable
 MTA Device Provisioning Specification."
  ::= { pktcMtaDevBase 7 }

pktcMtaDevProvisioningState     OBJECT-TYPE
  SYNTAX      INTEGER {
              pass                    (1),
              inProgress              (2),
              failConfigFileError     (3),
              passWithWarnings        (4),
              passWithIncompleteParsing (5),
              failureInternalError    (6),
              failureOtherReason      (7)
  }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object indicates the completion state of the MTA
       device provisioning process.

       pass:
       If the configuration file could be parsed successfully
       and the MTA is able to reflect the same in its
       MIB, the MTA MUST return the value 'pass'.

       inProgress:
       If the MTA is in the process of being provisioned,
       the MTA MUST return the value 'inProgress'.

       failConfigFileError:
        If the configuration file was in error due to incorrect
       values in the mandatory parameters, the MTA MUST reject
       the configuration file, and the MTA MUST return the value



       'failConfigFileError'.
```

```
        passWithWarnings:
        If the configuration file had proper values for all the
        mandatory parameters but has errors in any of the optional
        parameters (this includes any vendor-specific Object
        Identifiers (OIDs) that are incorrect or not known
        to the MTA), the MTA MUST return the value
        'passWithWarnings'.

        passWithIncompleteParsing:
        If the configuration file is valid but the MTA cannot
        reflect the same in its configuration (for example, too
        many entries caused memory exhaustion), it must accept
        the CMS configuration entries related, and the MTA MUST
        return the value 'passWithIncompleteParsing'.

        failureInternalError:
         If the configuration file cannot be parsed due to an
        Internal error, the MTA MUST return the value
        'failureInternalError'.

        failureOtherReason:
        If the MTA cannot accept the configuration file for any
        other reason than the ones stated above, the MTA MUST
        return the value 'failureOtherReason'.

        When a final SNMP INFORM is sent as part of Step 25 of the
        MTA Provisioning process, this parameter is also included
        in the final INFORM message."
      REFERENCE
       " PacketCable MTA Device Provisioning Specification."
   ::= { pktcMtaDevBase 8 }

pktcMtaDevHttpAccess  OBJECT-TYPE
   SYNTAX      TruthValue
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      " This object indicates whether the HTTP protocol is
        supported for the MTA configuration file transfer."
   ::= { pktcMtaDevBase 9 }

pktcMtaDevProvisioningTimer  OBJECT-TYPE
   SYNTAX      Unsigned32
 (0..30)
   UNITS       "minutes"
   MAX-ACCESS  read-write
   STATUS      current
```

```
  DESCRIPTION
     " This object defines the time interval for the provisioning
       flow to complete.  The MTA MUST finish all provisioning
       operations starting from the moment when an MTA receives
       its DHCP ACK and ending at the moment when the MTA
       downloads its configuration file (e.g., MTA5 to MTA23)
       within the period of time set by this object.
       Failure to comply with this condition constitutes
       a provisioning flow failure.  If the object is set to 0,
       the MTA MUST ignore the provisioning timer condition.
       If a value is written into an instance of
       pktcMtaDevProvisioningTimer, the agent MUST NOT retain the
       supplied value across MTA re-initializations or reboots."
  REFERENCE
     " PacketCable MTA Device Provisioning Specification."
  DEFVAL {10}
  ::=  {pktcMtaDevBase 10}

pktcMtaDevProvisioningCounter
  OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object counts the number of times the
        provisioning cycle has looped through step MTA-1."
    ::= {pktcMtaDevBase 11}

pktcMtaDevErrorOidsTable  OBJECT-TYPE
  SYNTAX SEQUENCE OF PktcMtaDevErrorOidsEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
     " This table contains the list of configuration errors or
       warnings the MTA encountered when parsing the
       configuration file it received from the Provisioning
       Server.
       For each error, an entry is created in this table,
       containing the configuration parameters the MTA rejected
       and the associated reason (e.g., wrong or unknown OID,
       inappropriate object values).  If the MTA
       did not report a provisioning state of 'pass(1)' in
       the pktcMtaDevProvisioningState object, this
 table MUST be
       populated for each error or warning instance.  Even if
       different parameters share the same error type (e.g., all
```

realm name configuration parameters are invalid), all
observed errors or warnings must be reported as
different instances. Errors are placed into the table in
no particular order. The table MUST be cleared each time

the MTA reboots."
REFERENCE
" PacketCable MTA Device Provisioning Specification."
::= {pktcMtaDevBase 12 }

pktcMtaDevErrorOidsEntry OBJECT-TYPE
SYNTAX PktcMtaDevErrorOidsEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
" This entry contains the necessary information the MTA MUST
attempt to provide in case of configuration file errors or
warnings."
INDEX { pktcMtaDevErrorOidIndex }
::= {pktcMtaDevErrorOidsTable 1}

PktcMtaDevErrorOidsEntry ::= SEQUENCE {
pktcMtaDevErrorOidIndex Unsigned32,
pktcMtaDevErrorOid SnmpAdminString,
pktcMtaDevErrorValue SnmpAdminString,
pktcMtaDevErrorReason SnmpAdminString
}

pktcMtaDevErrorOidIndex OBJECT-TYPE
SYNTAX Unsigned32 (1..1024)
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
" This object is the index of the MTA configuration error
table. It is an integer value that starts at value '1'
and is incremented for each encountered configuration
file error or warning.

The maximum number of errors or warnings that can be
recorded in the pktcMtaDevErrorOidsTable is set to 1024 as
a configuration file is usually validated by operators
before deployment. Given the possible number of
configuration parameter assignments in the MTA
configuration file, 1024 is perceived as a sufficient
limit even with future extensions.

```
        If the number of the errors in the configuration
 file
        exceeds 1024, all errors beyond the 1024th one MUST
        be ignored and not be reflected in the
        pktcMtaDevErrorOidsTable."

    ::= {pktcMtaDevErrorOidsEntry 1}



pktcMtaDevErrorOid  OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        " This object contains a human readable representation
        (character string) of the OID corresponding to the
        configuration file parameter that caused the particular
        error.
        For example, if the value of the pktcMtaDevEnabled object
        in the configuration file caused an error, then this
        object instance will contain the human-readable string of
        '1.3.6.1.2.1.140.1.1.6.0'.
        If the MTA generated an error because it was not able
        to recognize a particular OID, then this object
        instance would contain an empty value (zero-length
        string).
        For example,
 if the value of an OID in the configuration
        file was interpreted by the MTA as being 1.2.3.4.5, and if
        the MTA was not able to recognize this OID as a valid one,
        this object instance will contain a zero-length string.

        If the number of errors in the configuration file exceeds
        1024, then for all subsequent errors, the
        pktcMtaDevErrorOid of the table's 1024th entry MUST
        contain a human-readable representation of the
        pktcMtaDevErrorsTooManyErrors object; i.e., the string
        '1.3.6.1.2.1.140.1.1.4.1.0'.
        Note that the syntax of this object is SnmpAdminString
        instead of OBJECT IDENTIFIER because the object value may
        not be a valid OID due to human or configuration tool
        encoding errors."

    ::= {pktcMtaDevErrorOidsEntry 2}

pktcMtaDevErrorValue  OBJECT-TYPE
```

SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
" This
object contains the value of the OID corresponding to
the configuration file parameter that caused the error.
If the MTA cannot recognize the OID of the
configuration parameter causing the error, then this
object instance contains the OID itself as interpreted
by the MTA in human-readable representation.
If the MTA can recognize the OID but generate an error due
to a wrong value of the parameter, then the object

instance contains the erroneous value of the parameter as
read from the configuration file.
In both cases, the value of this object must be
represented in human-readable form as a character string.
For example, if the value of the pktcMtaDevEnabled object
in the configuration file was 3 (invalid value), then the
pktcMtaDevErrorValue object instance will contain the
human-readable (string) representation of value '3'.

Similarly, if the OID in the configuration file has been
interpreted by the MTA as being 1.2.3.4.5 and the MTA
cannot recognize this OID as a valid one, then this
pktcMtaDevErrorValue object instance will contain human
readable (string) representation of value '1.2.3.4.5'.

If the number of errors in the configuration file exceeds
1024, then for all subsequent errors, the
pktcMtaDevErrorValue of the table's 1024th entry MUST
contain a human-readable representation of the
pktcMtaDevErrorsTooManyErrors object; i.e., the string
'1.3.6.1.2.1.140.1.1.4.1.0'."

::= {pktcMtaDevErrorOidsEntry 3}

pktcMtaDevErrorReason OBJECT-TYPE
SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
" This object indicates the reason for the error or warning,
as per the MTA's interpretation, in human-readable form.
For example:

```
      'VALUE NOT IN RANGE', 'VALUE DOES NOT MATCH TYPE',
        'UNSUPPORTED VALUE', 'LAST 4 BITS MUST BE SET TO ZERO',
        'OUT OF MEMORY - CANNOT STORE'.
        This object may also contain vendor specific errors for
        private vendor OIDs and any proprietary error codes or
        messages that can help diagnose configuration errors.

        If the number of errors in the configuration file exceeds
        1024, then for all subsequent errors, the
        pktcMtaDevErrorReason of the table's 1024th entry MUST
        contain a human-readable string indicating the reason
        for an error; for example,
        'Too many errors in the configuration file'."
    ::= {pktcMtaDevErrorOidsEntry 4}

--
-- The following group describes server access and parameters used




-- for the initial MTA provisioning and bootstrapping phases.
--

pktcMtaDevDhcpServerAddressType  OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-only
    STATUS      current
     DESCRIPTION
        " This object contains the Internet address type for the
          PacketCable DHCP servers specified in MTA MIB."
    DEFVAL { ipv4 }
    ::= { pktcMtaDevServer 1}

pktcMtaDevServerDhcp1   OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        " This object contains the Internet Address of the primary
          DHCP server the MTA uses during provisioning.
          The type of this address is determined by the value of
          the pktcMtaDevDhcpServerAddressType object.
          When the latter has the value 'ipv4(1)', this object
          contains the IP address of the primary DHCP
          server.  It is provided by the CM to the MTA via the DHCP
          option code 122, sub-option 1, as defined in RFC 3495.
```

```
        The behavior of this object when the value of
        pktcMtaDevDhcpServerAddressType is other than 'ipv4(1)'
        is not presently specified, but it may be specified
         in future versions of this MIB module.
        If this object is of value
        0.0.0.0, the MTA MUST stop all provisioning
        attempts, as well as all other activities.
        If this object is of value 255.255.255.255, it means
        that there was no preference given for the primary
        DHCP server, and, the MTA must follow the logic of
        RFC2131, and the value of DHCP option 122,
        sub-option 2, must be ignored."
    REFERENCE
       " PacketCable MTA Device Provisioning Specification;
        RFC 2131, Dynamic Host Configuration Protocol;
        RFC 3495, DHCP Option for CableLabs Client Configuration."
    ::= { pktcMtaDevServer 2 }

pktcMtaDevServerDhcp2  OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-only



    STATUS      current
    DESCRIPTION
       " This object contains the Internet Address of the secondary
        DHCP server the MTA uses during provisioning.
        The type of this address
  is determined by the value of
        the pktcMtaDevDhcpServerAddressType object.
        When the latter has the value 'ipv4(1)', this object
        contains the IP address of the secondary DHCP
        server.  It is provided by the CM to the MTA via the DHCP
        option code 122, sub-option 2, as defined in RFC 3495.

        The behavior of this object when the value of
        pktcMtaDevDhcpServerAddressType is other than 'ipv4(1)'
        is not presently specified, but it may be specified
        in future versions of this MIB module.
        If there was no secondary DHCP server provided in DHCP
        Option 122, sub-option 2, this object must return the value
        0.0.0.0."
    REFERENCE
       " PacketCable MTA Device Provisioning Specification;
        RFC 3495, DHCP Option for CableLabs Client Configuration."
        ::= { pktcMtaDevServer 3 }
```

```
pktcMtaDevDnsServerAddressType  OBJECT-TYPE
  SYNTAX      InetAddressType
  MAX-ACCESS
 read-only
  STATUS      current
  DESCRIPTION
     " This object contains the Internet address type for the
       PacketCable DNS servers specified in MTA MIB."
  DEFVAL { ipv4 }
  ::= { pktcMtaDevServer 4}

pktcMtaDevServerDns1  OBJECT-TYPE
  SYNTAX      InetAddress
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     " This object contains the IP Address of the primary
       DNS server to be used by the MTA.  The type of this address
       is determined by the value of the
       pktcMtaDevDnsServerAddressType object.
       When the latter has the value 'ipv4(1)', this object
       contains the IP address of the primary DNS server.
       As defined in RFC 2132, PacketCable-compliant MTAs receive
       the IP addresses of the DNS Servers in DHCP option 6.
       The behavior of this object when the value of
       pktcMtaDevDnsServerAddressType is other than 'ipv4(1)'



       is not presently specified, but it
 may be specified
       in future versions of this MIB module.
       If a value is written into an instance of
       pktcMtaDevServerDns1, the agent MUST NOT retain the
       supplied value across MTA re-initializations or reboots."
  REFERENCE
     " PacketCable MTA Device Provisioning Specification;
       RFC 2132, DHCP Options and BOOTP Vendor Extensions."
  ::= { pktcMtaDevServer 5 }

pktcMtaDevServerDns2  OBJECT-TYPE
  SYNTAX      InetAddress
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     " This object contains the IP Address of the secondary
       DNS server to be used by the MTA.  The type of this address
       is determined by the value of the
```

pktcMtaDevDnsServerAddressType object.
When the latter has the value 'ipv4(1)', this object
contains the IP address of the secondary DNS
server. As defined in RFC 2132, PacketCable-compliant MTAs
receive the IP addresses of
the DNS Servers in DHCP
option 6.
The behavior of this object when the value of
pktcMtaDevDnsServerAddressType is other than 'ipv4(1)'
is not presently specified, but it may be specified
in future versions of this MIB module.
If a value is written into an instance of
pktcMtaDevServerDns2, the agent MUST NOT retain the
supplied value across MTA re-initializations or reboots."
REFERENCE
" PacketCable MTA Device Provisioning Specification;
RFC 2132, DHCP Options and BOOTP Vendor Extensions."
::= { pktcMtaDevServer 6 }

pktcMtaDevTimeServerAddressType OBJECT-TYPE
SYNTAX InetAddressType
MAX-ACCESS read-only
STATUS current
DESCRIPTION
" This object contains the Internet address type for the
PacketCable Time servers specified in MTA MIB."
DEFVAL { ipv4 }
::= { pktcMtaDevServer 7}

pktcMtaDevTimeServer OBJECT-TYPE
SYNTAX InetAddress

MAX-ACCESS read-write
STATUS current
DESCRIPTION
" This object contains the Internet Address of the Time
Server used by an S-MTA for Time Synchronization. The type
of this address is determined by the value of the
pktcMtaDevTimeServerAddressType object.
When the latter has the value 'ipv4(1)', this object
contains the IP address of the Time Server used for Time
Synchronization.
In the case of an S-MTA, this object must be
populated with a value other than 0.0.0.0 as obtained
from DHCP option 4. The protocol by which the time of day
MUST be retrieved is defined in RFC 868.

In the case of an E-MTA, this object must contain a
value of 0.0.0.0 if the address type is 'ipv4(1)' since
an E-MTA does not use the Time Protocol for time
synchronization (an E-MTA uses the time retrieved by the
DOCSIS cable modem).
The behavior of this object when the value of
pktcMtaDevTimeServerAddressType is other than 'ipv4(1)'
is not presently specified, but it may be specified in
future versions of this MIB module.
If a value is written into an instance of
pktcMtaDevTimeServer, the agent MUST NOT retain the
supplied value across MTA re-initializations or reboots."
REFERENCE
" RFC 868, Time Protocol;
RFC 2131, Dynamic Host Configuration Protocol;
RFC 2132, DHCP Options and BOOTP Vendor Extensions."
::= { pktcMtaDevServer 8}

pktcMtaDevConfigFile OBJECT-TYPE
SYNTAX SnmpAdminString
MAX-ACCESS read-write
STATUS current
DESCRIPTION
" This object specifies the MTA device configuration file
information, including the access method, the server name,
and the configuration file name. The value of this object
is the Uniform Resource Locator (URL)
of the configuration
file for TFTP or HTTP download.
If this object value is a TFTP URL, it must be formatted
as defined in RFC 3617.
If this object value is an HTTP URL, it must be formatted
as defined in RFC 2616.
If the MTA SNMP Enrollment mechanism is used, then the MTA
must download the file provided by the Provisioning Server

during provisioning via an SNMP SET on this object.
If the MTA SNMP Enrollment mechanism is not used, this
object MUST contain the URL value corresponding to the
'siaddr' and 'file' fields received in the DHCP ACK to
locate the configuration file: the 'siaddr' and 'file'
fields represent the host and file of the TFTP URL,
respectively. In this case, the MTA MUST return an
'inconsistentValue' error in response to SNMP SET
operations.
The MTA MUST return a zero-length string if the server

address (host part of the URL) is unknown.
If a value is written into an instance of
pktcMtaDevConfigFile, the agent MUST NOT retain the
supplied value across MTA re-initializations or reboots."
REFERENCE
" PacketCable MTA Device Provisioning Specification;
RFC 3617, URI Scheme for TFTP; RFC 2616, HTTP 1.1"
::= { pktcMtaDevServer 9 }

pktcMtaDevSnmpEntity OBJECT-TYPE
SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
" This object contains the FQDN of the SNMP entity of the
Provisioning Server. When the MTA SNMP Enrollment
Mechanism is used, this object represents the server that
the MTA communicates with, that it receives the
configuration file URL from, and that it sends the
enrollment notification to. The SNMP entity is also the
destination entity for all the provisioning
notifications. It
may be used for post-provisioning
SNMP operations. During the provisioning phase, this
SNMP entity FQDN is supplied to the MTA via DHCP option
122, sub-option 3, as defined in RFC 3495. The MTA must
resolve the FQDN value before its very first network
interaction with the SNMP entity during the provisioning
phase."

REFERENCE
" PacketCable MTA Device Provisioning Specification;
RFC 3495, DHCP Option for CableLabs Client Configuration."
::= { pktcMtaDevServer 10 }

pktcMtaDevProvConfigHash OBJECT-TYPE
SYNTAX OCTET STRING (SIZE(20))
MAX-ACCESS read-write
STATUS current

DESCRIPTION
" This object contains the hash value of the contents of the
configuration file.
The authentication algorithm is Secure Hashing Algorithm
1 (SHA-1), and the length is 160 bits. The hash
calculation MUST follow the requirements defined in the

PacketCable Security Specification. When the MTA SNMP
Enrollment mechanism is used, this hash value is
calculated and sent to the MTA prior to sending the
config file. This object value is then provided by the
Provisioning server via an SNMP SET operation.
When the MTA SNMP Enrollment mechanism is not in use, the
hash value is provided in the configuration file itself,
and it is also calculated by the MTA. This object value
MUST represent the hash value calculated by the MTA.
When the MTA SNMP Enrollment mechanism is not in use, the
MTA must reject all SNMP SET operations on this object and
return an 'inconsistentValue' error.
If a value is written into an instance of
pktcMtaDevProvConfigHash, the agent MUST NOT retain the
supplied value across MTA re-initializations or reboots."
REFERENCE
" PacketCable MTA Device Provisioning
Specification;
PacketCable Security Specification."
::= { pktcMtaDevServer 11 }

pktcMtaDevProvConfigKey OBJECT-TYPE
SYNTAX OCTET STRING (SIZE(32))
MAX-ACCESS read-write
STATUS current
DESCRIPTION
" This object contains the key used to encrypt/decrypt
the configuration file when secure SNMPv3 provisioning
is used.
The value of this object is provided along with the
configuration file information (pktcMtaDevConfigFile)
and hash (pktcMtaDevProvConfigHash) by the Provisioning
Server via SNMP SET once the configuration file has been
created, as defined by the PacketCable Security
specification.

The privacy algorithm is defined by the
pktcMtaDevProvConfigEncryptAlg MIB object. The
MTA requirements related to the privacy algorithm are
defined in the PacketCable Security Specification.

If this object is set at
any other provisioning step than
that allowed by the PacketCable MTA Device

Provisioning Specification, the MTA SHOULD return
an 'inconsistentValue' error.
This object must not be used in non secure provisioning
mode. In non-secure provisioning modes, the MTA SHOULD
return an 'inconsistentValue' in response to SNMP SET
operations, and the MTA SHOULD return a zero-length
string in response to SNMP GET operations.
If a value is written into an instance of
pktcMtaDevProvConfigKey, the agent MUST NOT retain the
supplied value across MTA re-initializations or reboots."
REFERENCE
" PacketCable MTA Device Provisioning Specification;
PacketCable Security Specification."
::= { pktcMtaDevServer 12 }

pktcMtaDevProvConfigEncryptAlg OBJECT-TYPE
SYNTAX PktcMtaDevProvEncryptAlg
MAX-ACCESS read-write
STATUS current
DESCRIPTION

" This object defines the encryption algorithm used for
privacy protection of the MTA Configuration File content."
DEFVAL { des64CbcMode }
::= { pktcMtaDevServer 13 }

pktcMtaDevProvSolicitedKeyTimeout OBJECT-TYPE
SYNTAX Unsigned32 (0..180)
UNITS "seconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
" This object defines a Kerberos Key Management timer on the
MTA. It is the time period during which the MTA saves the
nonce and Server Kerberos Principal Identifier to match an
AP Request and its associated AP Reply response from the
Provisioning Server.
After the timeout has been exceeded, the client discards
this (nonce, Server Kerberos Principal Identifier) pair,
after which it will no longer accept a matching AP Reply.
This timer only applies when the Provisioning Server
initiated key management for SNMPv3 (with a
Wake
Up message).
If this object is set to a zero value, the MTA MUST return
an 'inconsistentValue' in response to SNMP SET operations.
This object should not be used in non-secure provisioning
modes. In non-secure provisioning modes, the MTA MUST

```
        return an 'inconsistentValue' in response to SNMP SET
        operations, and the MTA MUST return a zero value in




        response to SNMP GET operations.
        If a value is written into an instance of
        pktcMtaDevProvSolicitedKeyTimeout, the agent MUST NOT
        retain the supplied value across MTA re-initializations
        or reboots."
    DEFVAL { 3 }
    ::= { pktcMtaDevServer 14 }

--=================================================================
--
--  Unsolicited key updates are retransmitted according to an
--  exponential back-off mechanism using two timers and a maximum
--  retry counter for AS replies.
--  The initial retransmission timer value is the nominal
 timer
--  value (pktcMtaDevProvUnsolicitedKeyNomTimeout).  The
--  retransmissions occur with an exponentially increasing interval
--  that caps at the maximum timeout value
--  (pktcMtaDevProvUnsolicitedKeyMaxTimeout).
--  Retransmissions stop when the maximum retry counter is reached
--  (pktcMtaDevProvUnsolicitedKeyMaxRetries).
--  For example, with values of 3 seconds for the nominal
--  timer, 100 seconds for the maximum timeout, and 8 retries max,
--  and with an exponential value of 2, this results in
--  retransmission intervals will be 3 s, 6 s, 12 s, 24 s, 48 s,
--  96 s, 100 s, and 100 s;
--  retransmissions then stop because the maximum number of
--  retries (8) has been reached.
--
--=================================================================
--
--  Timeouts for unsolicited key management updates are only
--  pertinent before the first SNMPv3 message is sent between the
--  MTA and the Provisioning Server and before the configuration
--  file is loaded.
--
--=================================================================

pktcMtaDevProvUnsolicitedKeyMaxTimeout
  OBJECT-TYPE
    SYNTAX      Unsigned32 (0..600)
    UNITS       "seconds"
    MAX-ACCESS  read-only
```

```
  STATUS      current
  DESCRIPTION
     " This object defines the timeout value that applies to
       an MTA-initiated AP-REQ/REP key management exchange with
       the Provisioning Server in SNMPv3 provisioning.
       It is the maximum timeout value, and it may not be exceeded
       in the exponential back-off algorithm.  If the DHCP option




       code 122, sub-option 5, is provided to the MTA, it
       overwrites this value.
       In non-secure provisioning modes, the MTA MUST
       return a zero value in response to SNMP GET
       operations."
  REFERENCE
     " PacketCable Security Specification."
  DEFVAL {600}
  ::= { pktcMtaDevServer 15 }

pktcMtaDevProvUnsolicitedKeyNomTimeout  OBJECT-TYPE
  SYNTAX      Unsigned32 (0..600)
   UNITS       "seconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object defines the starting value of the timeout
       for the AP-REQ/REP Backoff and Retry mechanism
       with exponential timeout in SNMPv3 provisioning.
       If the DHCP option code 122, sub-option 5, is provided
       the MTA, it overwrites this value.
       In non-secure provisioning modes, the MTA MUST
       return a zero value in response to SNMP GET
       operations."
  REFERENCE
     " PacketCable Security Specification."
  DEFVAL {3}
  ::= { pktcMtaDevServer 16}

pktcMtaDevProvUnsolicitedKeyMaxRetries  OBJECT-TYPE
  SYNTAX      Unsigned32 (0..32)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object contains a retry counter that applies to
       an MTA-initiated AP-REQ/REP key management exchange with
       the Provisioning Server in secure SNMPv3 provisioning.
       It is the maximum
```

```
 number of retries before the MTA stops
        attempting to establish a Security Association with
        Provisioning Server.
        If the DHCP option code 122, sub-option 5, is provided to
        the MTA, it overwrites this value.
        If this object is set to a zero value, the MTA MUST return
        an 'inconsistentValue' in response to SNMP SET operations.
        In non-secure provisioning modes, the MTA MUST
        return a zero value in response to SNMP GET
        operations."
    REFERENCE



       " PacketCable Security Specification."
    DEFVAL {8}
    ::= { pktcMtaDevServer 17 }

pktcMtaDevProvKerbRealmName  OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(1..255))
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       " This object contains the name of the associated
        provisioning Kerberos realm acquired during the MTA4
        provisioning step (DHCP Ack) for SNMPv3 provisioning.
        The uppercase ASCII representation
 of the associated
        Kerberos realm name MUST be used by both the Manager (SNMP
        entity) and the MTA.
        The Kerberos realm name for the Provisioning Server is
        supplied to the MTA via DHCP option code 122, sub-option 6,
        as defined in RFC 3495.  In secure SNMP provisioning mode,
        the value of the Kerberos realm name for the Provisioning
        Server supplied in the MTA configuration file must match
        the value supplied in the DHCP option code 122,
        sub-option 6.  Otherwise, the value of this object must
        contain the value supplied in DHCP Option 122,
        sub-option 6."
    REFERENCE
       " PacketCable MTA Device Provisioning Specification;
        RFC 3495, DHCP Option for CableLabs Client Configuration."
    ::= { pktcMtaDevServer 18 }

pktcMtaDevProvState  OBJECT-TYPE
    SYNTAX      INTEGER  {
                operational             (1),
                waitingForSnmpSetInfo
```

```
    (2),
            waitingForTftpAddrResponse (3),
            waitingForConfigFile       (4)
    }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       " This object defines the MTA provisioning state.
         If the state is:

          'operational(1)', the device has completed the loading
           and processing of the initialization parameters.

          'waitingForSnmpSetInfo(2)', the device is waiting on
           its configuration file download access information.
           Note that this state is only reported when the MTA



           SNMP enrollment mechanism is used.

          'waitingForTftpAddrResponse(3)', the device has sent a
           DNS request to resolve the server providing the
           configuration file, and it is awaiting for a response.
           Note that this state is only reported when the MTA
           SNMP enrollment mechanism is used.

          'waitingForConfigFile(4)', the device has
  sent a
           request via TFTP or HTTP for the download of its
           configuration file, and it is awaiting for a response or
           the file download is in progress."
    REFERENCE
       " PacketCable MTA Device Provisioning Specification,
         PacketCable Security Specification."
    ::= { pktcMtaDevServer 19 }

    --
    -- The following object group describes the security objects.
    --

  pktcMtaDevManufacturerCertificate  OBJECT-TYPE
    SYNTAX      DocsX509ASN1DEREncodedCertificate
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       " This object contains the MTA Manufacturer Certificate.
         The object value must be the ASN.1 DER encoding of the MTA
```

```
        manufacturer's X.509 public key certificate.  The MTA
        Manufacturer Certificate is issued to each MTA
        manufacturer and is installed into each MTA at the time of
        manufacture or with a secure code download.  The specific
        requirements
 related to this certificate are defined in
        the PacketCable or IPCablecom Security specifications."
    REFERENCE
       " PacketCable Security Specification."

    ::= {pktcMtaDevSecurity 1}

pktcMtaDevCertificate  OBJECT-TYPE
    SYNTAX      DocsX509ASN1DEREncodedCertificate
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       " This object contains the MTA Device Certificate.
        The object value must be the ASN.1 DER encoding of the
        MTA's X.509 public-key certificate issued by the
        manufacturer and installed into the MTA at the time of




        manufacture or with a secure code download.
        This certificate contains the MTA MAC address.  The
        specific requirements related to this certificate are
        defined in the PacketCable or IPCablecom Security
        specifications."
    REFERENCE
       " PacketCable Security Specification."
    ::= { pktcMtaDevSecurity 2 }

pktcMtaDevCorrelationId  OBJECT-TYPE
     SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       " This object contains a correlation ID, an arbitrary value
        generated by the MTA that will be exchanged as part of the
        device capability data to the Provisioning Application.
        This random value is used as an identifier to correlate
        related events in the MTA provisioning sequence.
        This value is intended for use only during the MTA
        initialization and configuration file download."
    REFERENCE
       " PacketCable MTA Device Provisioning Specification."
    ::= { pktcMtaDevSecurity 3 }
```

```
pktcMtaDevTelephonyRootCertificate  OBJECT-TYPE
  SYNTAX      DocsX509ASN1DEREncodedCertificate
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object contains the telephony Service Provider Root
       certificate.  The object value is the ASN.1 DER encoding of
       the IP Telephony Service Provider
 Root X.509 public key
       certificate.  This certification is stored in the MTA
       non-volatile memory and can be updated with a secure code
       download.  This certificate is used to validate the initial
       AS Reply received by the MTA from the Key Distribution
       Center (KDC) during the MTA initialization.  The specific
       requirements related to this certificate are defined in
       the PacketCable or IPCablecom Security specifications."
  REFERENCE
     " PacketCable Security Specification."
  ::= { pktcMtaDevSecurity 4 }

--============================================================
--
--   Informative Procedures for Setting up Security Associations
--




--   A Security Association may be set up either via configuration or
--   via NCS signaling.
--
--   I.   Security association setup via configuration.
--
--   The realm must be configured first.  Associated with the realm
--   is a KDC.  The realm table (pktcMtaDevRealmTable)
 indicates
--   information about the realm (e.g., name, organization name) and
--   parameters associated with KDC communications (e.g., grace
--   periods, AS Request/AS Reply adaptive back-off parameters).
--
--   Once the realm is established, one or more CMS(es) may be
--   defined in the realm.  Associated with each CMS
--   entry in the pktcMtaDevCmsTable is an explicit reference
--   to a Realm via the realm name (pktcMtaDevCmsKerbRealmName),
--   the FQDN of the CMS, and parameters associated with IPSec
--   key management with the CMS (e.g., clock skew, AP Request/
--   AP Reply adaptive back-off parameters).
--
```

```
-- II.  Security association setup via NCS signaling.
--
-- The procedure of establishing the Security Associations
-- for NCS signaling is described in the PacketCable Security
-- specification.
-- It involves the analysis of the pktcNcsEndPntConfigTable row
-- for the corresponding endpoint number and the correlation of
-- the CMS FQDN from this row
 with the CMS Table and
-- consequently, with the Realm Table.  Both of these tables
-- are defined below.  The pktcNcsEndPntConfigTable is defined in
-- the IP over Cable Data Network (IPCDN)
-- NCS Signaling MIB [NCSSIGMIB].
--
-- III.  When the MTA receives wake-up or re-key messages from a
-- CMS, it performs key management based on the corresponding
-- entry in the CMS table.  If the matching CMS entry does not
-- exist, it must ignore the wake-up or re-key messages.
--
--================================================================
--================================================================
--
-- pktcMtaDevRealmTable
--
-- The pktcMtaDevRealmTable shows the KDC realms.  The table is
-- indexed with pktcMtaDevRealmIndex.  The Realm Table contains the
-- pktcMtaDevRealmName in conjunction with any server that needs
-- a Security Association with the MTA.  Uppercase must be used
-- to compare the pktcMtaDevRealmName content.
--



--================================================================

pktcMtaDevRealmAvailSlot
  OBJECT-TYPE
  SYNTAX      Unsigned32 (0..64)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object contains the index number of the first
       available entry in the realm table (pktcMtaDevRealmTable).
       If all the entries in the realm table have been assigned,
       this object contains the value of zero.
       A management station should create new entries in the
       realm table, using the following procedure:
```

```
        First, issue a management protocol retrieval operation
        to determine the value of the first available index in the
        realm table (pktcMtaDevRealmAvailSlot).

        Second, issue a management protocol SET operation
        to create an instance of the pktcMtaDevRealmStatus
        object by setting its value to 'createAndWait(5)'.

        Third, if the SET operation succeeded, continue

    modifying the object instances corresponding to the newly
        created conceptual row, without fear of collision with
        other management stations.  When all necessary conceptual
        columns of the row are properly populated (via SET
        operations or default values), the management station may
        SET the pktcMtaDevRealmStatus object to 'active(1)'."
    ::= {  pktcMtaDevSecurity 5 }

pktcMtaDevRealmTable  OBJECT-TYPE
    SYNTAX      SEQUENCE OF PktcMtaDevRealmEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        " This object contains the realm table.
        The CMS table (pktcMtaDevCmsTable) and the realm table
        (pktcMtaDevRealmTable) are used for managing the MTA-CMS
        Security Associations.  The realm table defines the
        Kerberos realms for the Application Servers (CMSes and the
        Provisioning Server)."
    ::= {  pktcMtaDevSecurity 6 }

pktcMtaDevRealmEntry  OBJECT-TYPE
    SYNTAX
     PktcMtaDevRealmEntry
    MAX-ACCESS  not-accessible
    STATUS      current



    DESCRIPTION
        " This table entry object lists the MTA security parameters
        for a single Kerberos realm.  The conceptual rows MUST NOT
        persist across MTA reboots."
    INDEX { pktcMtaDevRealmIndex }
::= { pktcMtaDevRealmTable 1 }

PktcMtaDevRealmEntry ::= SEQUENCE {
    pktcMtaDevRealmIndex                Unsigned32,
```

```
  pktcMtaDevRealmName                    SnmpAdminString,
  pktcMtaDevRealmPkinitGracePeriod       Unsigned32,
  pktcMtaDevRealmTgsGracePeriod          Unsigned32,
  pktcMtaDevRealmOrgName                 LongUtf8String,
  pktcMtaDevRealmUnsolicitedKeyMaxTimeout Unsigned32,
  pktcMtaDevRealmUnsolicitedKeyNomTimeout Unsigned32,
  pktcMtaDevRealmUnsolicitedKeyMaxRetries Unsigned32,
  pktcMtaDevRealmStatus                  RowStatus
  }

pktcMtaDevRealmIndex  OBJECT-TYPE
  SYNTAX      Unsigned32 (1..64)
  MAX-ACCESS  not-accessible
  STATUS
    current
  DESCRIPTION
     " This object defines the realm table index."
  ::= { pktcMtaDevRealmEntry 1}

pktcMtaDevRealmName  OBJECT-TYPE
  SYNTAX      SnmpAdminString (SIZE(1..255))
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object identifies the Kerberos realm name in all
       capitals.  The MTA MUST prohibit the instantiation of any
       two rows with identical Kerberos realm names.  The MTA MUST
       also verify that any search operation involving Kerberos
       realm names is done using the uppercase ASCII
       representation of the characters."
  ::= { pktcMtaDevRealmEntry 2 }

pktcMtaDevRealmPkinitGracePeriod  OBJECT-TYPE
  SYNTAX      Unsigned32 (15..600)
  UNITS       "minutes"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object contains the PKINIT Grace Period.  For the
       purpose of key management with Application Servers (CMSes



       or
 the Provisioning Server), the MTA must utilize the
       PKINIT exchange to obtain Application Server tickets.  The
       MTA may utilize the PKINIT exchange to obtain Ticket
       Granting Tickets (TGTs), which are then used to obtain
```

```
        Application Server tickets in a TGS exchange.
        The PKINIT exchange occurs according to the current Ticket
        Expiration Time (TicketEXP) and on the PKINIT Grace Period
        (PKINITGP).  The MTA MUST initiate the PKINIT exchange at
        the time: TicketEXP - PKINITGP."
    REFERENCE
       " PacketCable Security Specification."
    DEFVAL { 15 }
    ::= { pktcMtaDevRealmEntry 3 }

pktcMtaDevRealmTgsGracePeriod  OBJECT-TYPE
    SYNTAX      Unsigned32 (1..600)
    UNITS       "minutes"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
       " This object contains the Ticket Granting Server Grace
        Period (TGSGP).  The Ticket Granting Server (TGS)
        Request/Reply exchange may be performed
 by the MTA
        on demand whenever an Application Server ticket is
        needed to establish security parameters.  If the MTA
        possesses a ticket that corresponds to the Provisioning
        Server or a CMS that currently exists in the CMS table,
        the MTA MUST initiate the TGS Request/Reply exchange
        at the time: TicketEXP - TGSGP."
    REFERENCE
       " PacketCable Security Specification."
    DEFVAL { 10 }
    ::= { pktcMtaDevRealmEntry 4 }

pktcMtaDevRealmOrgName  OBJECT-TYPE
    SYNTAX      LongUtf8String
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
       " This object contains the X.500 organization name attribute
        as defined in the subject name of the service provider
        certificate."
    REFERENCE
       " PacketCable Security Specification;
        RFCs 3280 and 4630, Internet X.509 Public Key
        Infrastructure Certificate and Certificate Revocation List
        (CRL) Profile"
     ::= { pktcMtaDevRealmEntry 5 }
```

```
pktcMtaDevRealmUnsolicitedKeyMaxTimeout  OBJECT-TYPE
  SYNTAX      Unsigned32 (1..600)
  UNITS       "seconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object specifies the maximum time the MTA will
       attempt to perform the exponential back-off algorithm.
       This timer only applies when the MTA initiated key
       management.  If the DHCP option code 122, sub-option 4, is
       provided to the MTA, it overwrites this value.

       Unsolicited key updates are retransmitted according to an
       exponential back-off mechanism using two timers and a
       maximum retry counter for AS replies.
       The initial retransmission timer value is the nominal
       timer value (pktcMtaDevRealmUnsolicitedKeyNomTimeout).  The
       retransmissions occur with an exponentially increasing
       interval that caps at the maximum timeout value
       (pktcMtaDevRealmUnsolicitedKeyMaxTimeout).
        Retransmissions stop when the maximum retry counter is
       reached (pktcMatDevRealmUnsolicitedMaxRetries).

       For example, with values of 3 seconds for the nominal
       timer, 20 seconds for the maximum timeout, and 5 retries
       max, retransmission intervals will be 3 s, 6 s,
       12 s, 20 s, and 20 s, and retransmissions then stop because
       the maximum number of retries has been reached."
  REFERENCE
     " PacketCable Security Specification."
  DEFVAL { 100 }
  ::= { pktcMtaDevRealmEntry 6 }

pktcMtaDevRealmUnsolicitedKeyNomTimeout  OBJECT-TYPE
  SYNTAX      Unsigned32 (100..600000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object specifies the initial timeout value
       for the AS-REQ/AS-REP exponential back-off and retry
       mechanism.  If the DHCP option code 122, sub-option 4, is
       provided to the MTA, it
 overwrites this value.
       This value should account for the average roundtrip
       time between the MTA and the KDC, as well as the
       processing delay on the KDC.
```

Unsolicited key updates are retransmitted according to an
exponential back-off mechanism using two timers and a
maximum retry counter for AS replies.
The initial retransmission timer value is the nominal
timer value (pktcMtaDevRealmUnsolicitedKeyNomTimeout). The
retransmissions occur with an exponentially increasing
interval that caps at the maximum timeout value
(pktcMtaDevRealmUnsolicitedKeyMaxTimeout).
Retransmissions stop when the maximum retry counter is
reached (pktcMatDevRealmUnsolicitedMaxRetries).

For example, with values of 3 seconds for the nominal
timer, 20 seconds for the maximum timeout, and 5 retries
max, in retransmission intervals will be 3 s, 6 s,

12 s, 20 s, and 20 s; retransmissions then stop because
the maximum number of retries has been reached."
REFERENCE
" PacketCable Security Specification."
DEFVAL { 3000 }
::= { pktcMtaDevRealmEntry 7 }

pktcMtaDevRealmUnsolicitedKeyMaxRetries OBJECT-TYPE
SYNTAX Unsigned32 (0..1024)
MAX-ACCESS read-create
STATUS current
DESCRIPTION
" This object specifies the maximum number of retries the
MTA attempts to obtain a ticket from the KDC.

Unsolicited key updates are retransmitted according to an
exponential back-off mechanism using two timers and a
maximum retry counter for AS replies.
The initial retransmission timer value is the nominal
timer value (pktcMtaDevRealmUnsolicitedKeyNomTimeout). The
retransmissions occur with an exponentially increasing
interval that caps at the maximum timeout value
(pktcMtaDevRealmUnsolicitedKeyMaxTimeout).
Retransmissions stop when the maximum retry counter is
reached (pktcMatDevRealmUnsolicitedMaxRetries).

For example, with values of 3 seconds for the nominal
timer, 20 seconds for the maximum timeout, and 5 retries
max, retransmission intervals will be 3 s, 6 s,

```
        12 s, 20 s, and 20 s; retransmissions then stop because
        the maximum number of retries has been reached."
    REFERENCE
       " PacketCable Security Specification."
    DEFVAL { 5 }



    ::= { pktcMtaDevRealmEntry 8 }

pktcMtaDevRealmStatus     OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
       " This object defines the row status of this realm in the
        realm table (pktcMtaDevRealmTable).

        An entry in this table is not qualified for activation
        until the object instances of all corresponding columns
        have been initialized, either by default values, or
 via
        explicit SET operations.  Until all object instances in
        this row are initialized, the status value for this realm
        must be 'notReady(3)'.
        In particular, two columnar objects must be explicitly
        SET: the realm name (pktcMtaDevRealmName) and the
        organization name (pktcMtaDevRealmOrgName).  Once these 2
        objects have been set and the row status is SET to
        'active(1)', the MTA MUST NOT allow any modification of
        these 2 object values.
        The value of this object has no effect on whether other
        columnar objects in this row can be modified."
    ::= { pktcMtaDevRealmEntry 9 }

--================================================================
--
--  The CMS table, pktcMtaDevCmsTable
--
-- The CMS table and the realm table (pktcMtaDevRealmTable) are used
-- for managing the MTA signaling security.  The CMS table defines
-- the CMSes the MTA is allowed to communicate with and contains
-- the
 parameters describing the SA establishment between the MTA
-- and a CMS.
-- The CMS table is indexed by pktcMtaDevCmsIndex.  The table
-- contains the CMS FQDN (pktcMtaDevCmsFQDN) and the associated
-- Kerberos realm name (pktcMtaDevCmsKerbRealmName) so that the MTA
```

```
-- can find the corresponding Kerberos realm name in the
-- pktcMtaDevRealmTable.
--
--================================================================

pktcMtaDevCmsAvailSlot   OBJECT-TYPE
  SYNTAX      Unsigned32 (0..128)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION



      " This object contains the index number of the first
        available entry in the CMS table (pktcMtaDevCmsTable).
        If all the entries in the CMS table have been assigned,
        this object contains the value of zero.
        A management station should create new entries in the
        CMS table, using the following procedure:

        First, issue a management protocol retrieval operation

 to determine the value of the first available index in the
        CMS table (pktcMtaDevCmsAvailSlot).

        Second, issue a management protocol SET operation
        to create an instance of the pktcMtaDevCmsStatus
        object by setting its value to 'createAndWait(5)'.

        Third, if the SET operation succeeded, continue
        modifying the object instances corresponding to the newly
        created conceptual row, without fear of collision with
        other management stations.  When all necessary conceptual
        columns of the row are properly populated (via SET
        operations or default values), the management station may
        SET the pktcMtaDevCmsStatus object to 'active(1)'."
  ::= {  pktcMtaDevSecurity 7 }

pktcMtaDevCmsTable  OBJECT-TYPE
  SYNTAX      SEQUENCE OF PktcMtaDevCmsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      " This object defines the CMS table.
        The CMS table (pktcMtaDevCmsTable)
 and the realm table
        (pktcMtaDevRealmTable) are used for managing security
        between the MTA and CMSes.  Each CMS table entry defines
```

```
        a CMS the managed MTA is allowed to communicate with
        and contains security parameters for key management with
        that CMS."
    ::= {  pktcMtaDevSecurity 8 }

pktcMtaDevCmsEntry  OBJECT-TYPE
    SYNTAX      PktcMtaDevCmsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        " This table entry object lists the MTA key management
        parameters used when establishing Security Associations
        with a CMS.  The conceptual rows MUST NOT persist across
        MTA reboots."
    INDEX { pktcMtaDevCmsIndex }



    ::= { pktcMtaDevCmsTable 1 }

PktcMtaDevCmsEntry ::= SEQUENCE {
    pktcMtaDevCmsIndex                  Unsigned32,
    pktcMtaDevCmsFqdn                   SnmpAdminString,
    pktcMtaDevCmsKerbRealmName              SnmpAdminString,
    pktcMtaDevCmsMaxClockSkew
                Unsigned32,
    pktcMtaDevCmsSolicitedKeyTimeout        Unsigned32,
    pktcMtaDevCmsUnsolicitedKeyMaxTimeout   Unsigned32,
    pktcMtaDevCmsUnsolicitedKeyNomTimeout   Unsigned32,
    pktcMtaDevCmsUnsolicitedKeyMaxRetries   Unsigned32,
    pktcMtaDevCmsIpsecCtrl                  TruthValue,
    pktcMtaDevCmsStatus                 RowStatus
    }

pktcMtaDevCmsIndex  OBJECT-TYPE
    SYNTAX      Unsigned32 (1..128)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        " This object defines the CMS table index."
    ::= { pktcMtaDevCmsEntry 1 }

pktcMtaDevCmsFqdn  OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(1..255))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        " This object specifies the CMS FQDN.  The MTA must
```

```
        prohibit the instantiation of any two rows with identical
        FQDNs.  The MTA must also verify that any search and/or
        comparison operation
 involving a CMS FQDN is case
        insensitive.  The MTA must resolve the CMS FQDN as required
         by the corresponding PacketCable Specifications."
   REFERENCE
      " PacketCable MTA Device Provisioning Specification;
        PacketCable Security Specification;
        PacketCable Network-Based Call Signaling Protocol
        Specification."
   ::= { pktcMtaDevCmsEntry 2 }

pktcMtaDevCmsKerbRealmName  OBJECT-TYPE
   SYNTAX      SnmpAdminString (SIZE(1..255))
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      " This object identifies the Kerberos realm name in uppercase
        characters associated with the CMS defined in this




        conceptual row.  The object value is a reference
        point to the corresponding Kerberos realm name in the
        realm table (pktcMtaDevRealmTable)."
   ::= { pktcMtaDevCmsEntry 3 }

pktcMtaDevCmsMaxClockSkew    OBJECT-TYPE
   SYNTAX      Unsigned32 (1..1800)
   UNITS       "seconds"
    MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      " This object specifies the maximum allowable clock skew
        between the MTA and the CMS defined in this row."
   DEFVAL { 300 }
   ::= { pktcMtaDevCmsEntry 4 }

pktcMtaDevCmsSolicitedKeyTimeout  OBJECT-TYPE
   SYNTAX      Unsigned32 (100..30000)
   UNITS       "milliseconds"
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      " This object defines a Kerberos Key Management timer on the
        MTA.  It is the time period during which the MTA saves the
        nonce and Server Kerberos Principal Identifier to match an
```

```
        AP Request and its associated AP Reply response from the
        CMS.  This timer only applies when the CMS initiated key
        management (with a Wake Up message or a Rekey message)."
    REFERENCE
       " PacketCable Security Specification."
    DEFVAL { 1000 }
    ::= { pktcMtaDevCmsEntry 5 }

--================================================================
--
--
   Unsolicited key updates are retransmitted according to an
--  exponential back-off mechanism using two timers and a maximum
--  retry counter for AS replies.
--  The initial retransmission timer value is the nominal timer
--  value (pktcMtaDevCmsUnsolicitedKeyNomTimeout).  The
--  retransmissions occur with an exponentially increasing interval
--  that caps at the maximum timeout value
--  (pktcMtaDevCmsUnsolicitedKeyMaxTimeout).
--  Retransmissions stop when the maximum retry counter is reached
--  (pktcMatDevCmsUnsolicitedMaxRetries).
--  For example, with values of 3 seconds for the nominal
--  timer, 20 seconds for the maximum timeout, and 5 retries max,
--  retransmission intervals will be 3 s, 6 s, 12 s,



--  20 s, and 20 s; retransmissions then stop due to the
--  maximum number of retries reached.
--
--================================================================

pktcMtaDevCmsUnsolicitedKeyMaxTimeout  OBJECT-TYPE
    SYNTAX      Unsigned32 (1..600)
     UNITS       "seconds"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
       " This object defines the timeout value that only applies
        to an MTA-initiated key management exchange.  It is the
        maximum timeout, and it may not be exceeded in the
        exponential back-off algorithm."
    REFERENCE
       " PacketCable Security Specification."
    DEFVAL { 600 }
    ::= { pktcMtaDevCmsEntry 6 }

pktcMtaDevCmsUnsolicitedKeyNomTimeout  OBJECT-TYPE
```

```
  SYNTAX      Unsigned32 (100..30000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object defines the starting value of the timeout
       for an MTA-initiated key management.  It should account for
       the average roundtrip time between the MTA and the CMS and
       the processing time on the CMS."
  REFERENCE
     " PacketCable Security Specification."
  DEFVAL { 500 }
  ::= { pktcMtaDevCmsEntry 7 }

pktcMtaDevCmsUnsolicitedKeyMaxRetries
  OBJECT-TYPE
  SYNTAX      Unsigned32 (0..1024)
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object contains the maximum number of retries before
       the MTA stops attempting to establish a Security
       Association with the CMS."
  REFERENCE
     " PacketCable Security Specification."
  DEFVAL { 5 }
  ::= { pktcMtaDevCmsEntry 8 }



pktcMtaDevCmsIpsecCtrl     OBJECT-TYPE
  SYNTAX        TruthValue
  MAX-ACCESS    read-only
  STATUS        current
  DESCRIPTION
     " This object specifies the MTA IPSec control flag.
       If the object value is 'true', the MTA must use Kerberos
       Key Management and IPsec to communicate with this CMS.  If
       it is 'false', IPSec Signaling Security and Kerberos key
       management are disabled for this specific CMS."
  DEFVAL { true }
  ::= { pktcMtaDevCmsEntry 9 }

pktcMtaDevCmsStatus     OBJECT-TYPE
  SYNTAX
  RowStatus
  MAX-ACCESS  read-create
```

```
  STATUS      current
  DESCRIPTION
     " This object defines the row status associated with this
       particular CMS in the CMS table (pktcMtaDevCmsTable).

       An entry in this table is not qualified for activation
       until the object instances of all corresponding columns
       have been initialized, either by default values or via
       explicit SET operations.  Until all object instances in
       this row are initialized, the status value for this realm
       must be 'notReady(3)'.
       In particular, two columnar objects must be SET: the
       CMS FQDN (pktcMtaDevCmsFqdn) and the Kerberos realm name
       (pktcMtaDevCmsKerbRealmName).  Once these 2 objects have
       been set and the row status is SET to 'active(1)', the MTA
       MUST NOT allow any modification of these 2 object values.

       The value of this object has no effect on
       whether other columnar objects
 in this row can be
       modified."
  ::= { pktcMtaDevCmsEntry 10 }

pktcMtaDevResetKrbTickets   OBJECT-TYPE
  SYNTAX      BITS {
                 invalidateProvOnReboot   (0),
                 invalidateAllCmsOnReboot (1)
           }
  MAX-ACCESS   read-write
  STATUS    current
  DESCRIPTION
     " This object defines a Kerberos Ticket Control Mask that
       instructs the MTA to invalidate the specific Application




       Server Kerberos ticket(s) that are stored locally in the
       MTA NVRAM (non-volatile or persistent memory).
       If the MTA does not store Kerberos tickets in NVRAM, it
       MUST ignore setting of this object and MUST report a BITS
       value of zero when the object is read.
       If the MTA supports Kerberos tickets storage in NVRAM, the
       object value is encoded as follows:
       - Setting the invalidateProvOnReboot bit (bit 0) to 1
         means that the MTA MUST invalidate
 the Kerberos
         Application Ticket(s) for the Provisioning Application
         at the next MTA reboot if secure SNMP provisioning mode
```

```
          is used.  In non-secure provisioning modes, the MTA MUST
          return an 'inconsistentValue' in response to SNMP SET
          operations with a bit 0 set to 1.
        - Setting the invalidateAllCmsOnReboot bit (bit 1) to 1
          means that the MTA MUST invalidate the Kerberos
          Application Ticket(s) for all CMSes currently assigned
          to the MTA endpoints.
        If a value is written into an instance of
        pktcMtaDevResetKrbTickets, the agent MUST retain the
        supplied value across an MTA re-initialization or
        reboot."
  REFERENCE
     "PacketCable Security Specification."
  DEFVAL { {   } }
  ::= {  pktcMtaDevSecurity 9 }

--
-- The following group, pktcMtaDevErrors, defines an OID
-- corresponding to error conditions encountered during the MTA
-- provisioning.
--

pktcMtaDevErrorsTooManyErrors
 OBJECT-IDENTITY
  STATUS     current
  DESCRIPTION
     "This object defines the OID corresponding to the error
      condition when too many errors are encountered in the
      MTA configuration file during provisioning."
    ::= { pktcMtaDevErrors  1 }

pktcMtaDevProvisioningEnrollment  NOTIFICATION-TYPE
  OBJECTS {
         sysDescr,
         pktcMtaDevSwCurrentVers,
         pktcMtaDevTypeIdentifier,
         ifPhysAddress,
         pktcMtaDevCorrelationId




  }
  STATUS   current
  DESCRIPTION
     " This INFORM notification is issued by the MTA to initiate
       the PacketCable provisioning process when the MTA SNMP
       enrollment mechanism is used.
       It contains the system description, the current software
```

```
        version, the MTA device type identifier, the MTA MAC
        address (obtained in the MTA ifTable in the ifPhysAddress
        object that corresponds to the ifIndex
 1), and a
        correlation ID."
   ::= { pktcMtaNotification 1 }

pktcMtaDevProvisioningStatus  NOTIFICATION-TYPE
   OBJECTS {
          ifPhysAddress,
          pktcMtaDevCorrelationId,
          pktcMtaDevProvisioningState
   }
   STATUS      current
   DESCRIPTION
      " This INFORM notification may be issued by the MTA to
        confirm the completion of the PacketCable provisioning
        process, and to report its provisioning completion
        status.
        It contains the MTA MAC address (obtained in the MTA
        ifTable in the ifPhysAddress object that corresponds
        to the ifIndex 1), a correlation ID and the MTA
        provisioning state as defined in
        pktcMtaDevProvisioningState."
   ::= { pktcMtaNotification 2 }

--
-- Compliance Statements
--

pktcMtaCompliances  OBJECT IDENTIFIER ::= { pktcMtaConformance 1 }
pktcMtaGroups       OBJECT IDENTIFIER ::= { pktcMtaConformance 2 }

pktcMtaBasicCompliance MODULE-COMPLIANCE
    STATUS      current
   DESCRIPTION
      " The compliance statement for MTA devices that implement
        PacketCable or IPCablecom requirements.

        This compliance statement applies to MTA implementations
        that support PacketCable 1.0 or IPCablecom requirements,
        which are not IPv6-capable at the time of this




        RFC publication."

   MODULE  -- Unconditionally mandatory groups for MTAs
```

```
    MANDATORY-GROUPS {
      pktcMtaGroup,
      pktcMtaNotificationGroup
    }

    OBJECT  pktcMtaDevDhcpServerAddressType
      SYNTAX      InetAddressType { ipv4(1) }
      DESCRIPTION
        " Support for address types other than 'ipv4(1)'
      is not presently specified and therefore is not
      required.  It may be defined in future versions of
      this MIB module."

    OBJECT  pktcMtaDevDnsServerAddressType
      SYNTAX      InetAddressType { ipv4(1) }

DESCRIPTION
        " Support for address types other than 'ipv4(1)'
      is not presently specified and therefore is not
      required.  It may be defined in future versions of
      this MIB module."

    OBJECT  pktcMtaDevTimeServerAddressType
      SYNTAX      InetAddressType { ipv4(1) }
      DESCRIPTION
        " Support for address types other than 'ipv4(1)'
      is not presently specified and therefore is not
      required.  It may be defined in future versions of
      this MIB module."

    OBJECT    pktcMtaDevServerDhcp1
      SYNTAX  InetAddress (SIZE(4))
      DESCRIPTION
        "An implementation is only required to support IPv4
      addresses.  Other address types support may be defined in
      future versions of this MIB module."

    OBJECT    pktcMtaDevServerDhcp2
      SYNTAX  InetAddress (SIZE(4))
      DESCRIPTION
        "An implementation
is only required to support IPv4
      addresses.  Other address types support may be defined in
      future versions of this MIB module."

    OBJECT    pktcMtaDevServerDns1
```

SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4 addresses. Other address types support may be defined in future versions of this MIB module."

OBJECT pktcMtaDevServerDns2
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4 addresses. Other address types support may be defined in future versions of this MIB module."

OBJECT pktcMtaDevTimeServer
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4 addresses. Other address types support may be defined in future versions of this MIB module."

OBJECT pktcMtaDevProvConfigEncryptAlg
SYNTAX PktcMtaDevProvEncryptAlg
DESCRIPTION
"An implementation is only required to support values of none(0) and des64Cbcmode(1).
An IV of zero is used to encrypt in des64Cbcmode, and the length of pktcMtaDevProvConfigKey is 64 bits, as defined in the PacketCable Security specification.
Other encryption types may be defined in future versions of this MIB module."

OBJECT pktcMtaDevRealmOrgName
SYNTAX LongUtf8String (SIZE (1..384))
DESCRIPTION
"The Organization Name field in X.509 certificates can contain up to 64 UTF-8 encoded characters, as defined in RFCs 3280 and 4630. Therefore, compliant devices are only required to support Organization Name values of up to 64 UTF-8 encoded characters.
Given that RFCs 3280 and 4630 define the UTF-8 encoding, compliant devices must support a maximum size of 384 octets for pktcMtaDevRealmOrgName. The calculation of 384 octets comes from the RFC 3629 UTF-8 encoding definition whereby the UTF-8 encoded characters are encoded as sequences of 1 to 6 octets, assuming that code points as high as 0x7fffffff

might be used. Subsequent versions of Unicode and ISO 10646 have limited the upper bound to 0x10ffff.

Consequently, the current version of UTF-8, defined in RFC 3629, does not require more than four octets to encode a valid code point."

::= { pktcMtaCompliances 1 }

pktcMtaGroup OBJECT-GROUP
OBJECTS {
pktcMtaDevResetNow,
pktcMtaDevSerialNumber,
pktcMtaDevSwCurrentVers,
pktcMtaDevFQDN,
pktcMtaDevEndPntCount,

pktcMtaDevEnabled,
pktcMtaDevProvisioningCounter,
pktcMtaDevErrorOid,
pktcMtaDevErrorValue,
pktcMtaDevErrorReason,
pktcMtaDevTypeIdentifier,
pktcMtaDevProvisioningState,
pktcMtaDevHttpAccess,
pktcMtaDevCertificate,
pktcMtaDevCorrelationId,
pktcMtaDevManufacturerCertificate,
pktcMtaDevDhcpServerAddressType,
pktcMtaDevDnsServerAddressType,
pktcMtaDevTimeServerAddressType,
pktcMtaDevProvConfigEncryptAlg,
pktcMtaDevServerDhcp1,
pktcMtaDevServerDhcp2,
pktcMtaDevServerDns1,
pktcMtaDevServerDns2,
pktcMtaDevTimeServer,
pktcMtaDevConfigFile,
pktcMtaDevSnmpEntity,
pktcMtaDevRealmPkinitGracePeriod,
pktcMtaDevRealmTgsGracePeriod,
pktcMtaDevRealmAvailSlot,
pktcMtaDevRealmName,
pktcMtaDevRealmOrgName,
pktcMtaDevRealmUnsolicitedKeyMaxTimeout,
pktcMtaDevRealmUnsolicitedKeyNomTimeout,

```
        pktcMtaDevRealmUnsolicitedKeyMaxRetries,
        pktcMtaDevRealmStatus,
        pktcMtaDevCmsAvailSlot,
        pktcMtaDevCmsFqdn,
        pktcMtaDevCmsKerbRealmName,
        pktcMtaDevCmsUnsolicitedKeyMaxTimeout,



        pktcMtaDevCmsUnsolicitedKeyNomTimeout,
        pktcMtaDevCmsUnsolicitedKeyMaxRetries,
        pktcMtaDevCmsSolicitedKeyTimeout,
        pktcMtaDevCmsMaxClockSkew,
        pktcMtaDevCmsIpsecCtrl,
        pktcMtaDevCmsStatus,
        pktcMtaDevResetKrbTickets,
        pktcMtaDevProvUnsolicitedKeyMaxTimeout,
        pktcMtaDevProvUnsolicitedKeyNomTimeout,
        pktcMtaDevProvUnsolicitedKeyMaxRetries,
        pktcMtaDevProvKerbRealmName,
        pktcMtaDevProvSolicitedKeyTimeout,
        pktcMtaDevProvConfigHash,
        pktcMtaDevProvConfigKey,
        pktcMtaDevProvState,
         pktcMtaDevProvisioningTimer,
        pktcMtaDevTelephonyRootCertificate
  }
  STATUS      current
  DESCRIPTION
     " A collection of objects for managing PacketCable or
      IPCablecom MTA implementations."
  ::= { pktcMtaGroups 1 }

pktcMtaNotificationGroup          NOTIFICATION-GROUP
  NOTIFICATIONS {
             pktcMtaDevProvisioningStatus,
             pktcMtaDevProvisioningEnrollment
  }
  STATUS      current
  DESCRIPTION
     " A collection of notifications dealing with the change of
       MTA provisioning status."
  ::= { pktcMtaGroups 2 }

pktcMtaBasicSmtaCompliance MODULE-COMPLIANCE
  STATUS      current
  DESCRIPTION
     " The compliance statement for S-MTA devices
```

```
        that implement PacketCable or IPCablecom requirements.

        This compliance statement applies to S-MTA implementations
        that support PacketCable or IPCablecom requirements,
        which are not IPv6-capable
at the time of this
        RFC publication."

 MODULE -- Unconditionally Mandatory Groups for S-MTA devices
     MANDATORY-GROUPS {



         pktcMtaGroup,
         pktcMtaNotificationGroup
     }

     OBJECT  pktcMtaDevDhcpServerAddressType
         SYNTAX      InetAddressType { ipv4(1) }
         DESCRIPTION
             " Support for address types other than 'ipv4(1)'
         is not presently specified and therefore is not
         required.  It may be defined in future versions of
         this MIB module."

     OBJECT  pktcMtaDevDnsServerAddressType
         SYNTAX      InetAddressType { ipv4(1) }
         DESCRIPTION
             " Support for address types other than 'ipv4(1)'
         is not presently specified and therefore is not
         required.  It may be defined in future versions of
         this MIB module."

     OBJECT  pktcMtaDevTimeServerAddressType
         SYNTAX      InetAddressType { ipv4(1)
}
         DESCRIPTION
             " Support for address types other than 'ipv4(1)'
         is not presently specified and therefore is not
         required.  It may be defined in future versions of
         this MIB module."

     OBJECT    pktcMtaDevServerDhcp1
         SYNTAX  InetAddress (SIZE(4))
         DESCRIPTION
             "An implementation is only required to support IPv4
         addresses.  Other address types support may be defined in
         future versions of this MIB module."
```

OBJECT pktcMtaDevServerDhcp2
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4
addresses. Other address types support may be defined in
future versions of this MIB module."

OBJECT pktcMtaDevServerDns1
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required
to support IPv4
addresses. Other address types support may be defined in
future versions of this MIB module."

OBJECT pktcMtaDevServerDns2
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4
addresses. Other address types support may be defined in
future versions of this MIB module."

OBJECT pktcMtaDevTimeServer
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4
addresses. Other address types support may be defined in
future versions of this MIB module."

OBJECT pktcMtaDevProvConfigEncryptAlg
SYNTAX PktcMtaDevProvEncryptAlg
DESCRIPTION
"An implementation is only required to support
values of none(0) and des64Cbcmode(1).
An IV of zero is used to encrypt
in des64Cbcmode, and
the length of pktcMtaDevProvConfigKey is 64 bits, as
defined in the PacketCable Security specification.
Other encryption types may be defined in future
versions of this MIB module."

OBJECT pktcMtaDevRealmOrgName
SYNTAX LongUtf8String (SIZE (1..384))
DESCRIPTION

```
            "The Organization Name field in X.509 certificates
          can contain up to 64 UTF-8 encoded characters, as
          defined in RFCs 3280 and 4630.  Therefore, compliant
          devices are only required to support Organization
          Name values of up to 64 UTF-8 encoded characters.
          Given that RFCs 3280 and 4630 define the UTF-8 encoding,
          compliant devices must support a maximum size of 384
          octets for pktcMtaDevRealmOrgName.  The calculation of
          384 octets comes from the RFC 3629 UTF-8 encoding
          definition whereby the UTF-8 encoded
 characters
          are encoded as sequences of 1 to 6 octets,
          assuming that code points as high as 0x7fffffff
          might be used.  Subsequent versions of Unicode and ISO
          10646 have limited the upper bound to 0x10ffff.
          Consequently, the current version of UTF-8, defined in
          RFC 3629 does not require more than four octets to
          encode a valid code point."
    MODULE DOCS-CABLE-DEVICE-MIB
      MANDATORY-GROUPS {



          docsDevSoftwareGroupV2
      }

    MODULE DOCS-IETF-BPI2-MIB
      MANDATORY-GROUPS {
          docsBpi2CodeDownloadGroup
      }

    ::= { pktcMtaCompliances 2 }

END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/PKTC-IETF-MTA-MIB
No license file was found, but licenses were detected in source scan.

PKTC-IETF-SIG-MIB DEFINITIONS ::= BEGIN

IMPORTS
    MODULE-IDENTITY,
    OBJECT-TYPE,
    Integer32,
    Unsigned32,
    mib-2
        FROM SNMPv2-SMI                 -- [RFC2578]
```

```
  InetAddressType,
  InetAddress,
  InetPortNumber
      FROM INET-ADDRESS-MIB            -- [RFC4001]
  TEXTUAL-CONVENTION,
  RowStatus,
  TruthValue
      FROM SNMPv2-TC                   -- [RFC2579]



  OBJECT-GROUP,
  MODULE-COMPLIANCE
      FROM SNMPv2-CONF                 -- [RFC2580]
  SnmpAdminString
      FROM SNMP-FRAMEWORK-MIB          -- [RFC3411]
  ifIndex
      FROM IF-MIB                      -- [RFC2863]
  Dscp
      FROM DIFFSERV-DSCP-TC;           -- [RFC3289]

pktcIetfSigMib MODULE-IDENTITY
  LAST-UPDATED    "200712180000Z" -- December 18, 2007
  ORGANIZATION    "IETF IPCDN Working Group"
  CONTACT-INFO
     "Sumanth Channabasappa
      Cable Television
 Laboratories, Inc.
      858 Coal Creek Circle,
      Louisville, CO 80027, USA
      Phone: +1 303-661-3307
      Email: Sumanth@cablelabs.com

      Gordon Beacham
      Motorola, Inc.
      6450 Sequence Drive, Bldg. 1
      San Diego, CA 92121, USA
      Phone: +1 858-404-2334
      Email: gordon.beacham@motorola.com

      Satish Kumar Mudugere Eswaraiah
      Texas Instruments India (P) Ltd.,
      Golf view, Wind Tunnel Road
      Murugesh Palya
      Bangalore 560 017, INDIA
      Phone:   +91 80 5269451
      Email:  satish.kumar@ti.com
```

```
  IETF IPCDN Working Group
      General Discussion: ipcdn@ietf.org
      Subscribe: http://www.ietf.org/mailman/listinfo/ipcdn
      Archive: ftp://ftp.ietf.org/ietf-mail-archive/ipcdn
      Co-Chair: Jean-Francois Mule, jf.mule@cablelabs.com
      Co-Chair: Richard Woundy, Richard_Woundy@cable.comcast.com"

  DESCRIPTION
    "This MIB module supplies the basic management
     objects for the PacketCable and IPCablecom Signaling
     protocols.  This version of the MIB includes
     common signaling and Network Call Signaling




     (NCS)-related signaling objects.

     Copyright (C) The IETF Trust (2008).  This version of
     this MIB module is part of RFC 5098; see the RFC itself for
     full legal notices."
  REVISION              "200712180000Z"
  DESCRIPTION
    "Initial version, published as RFC 5098."

::=  { mib-2 169 }

-- Textual Conventions

TenthdBm ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "d-1"
  STATUS       current
  DESCRIPTION
     "This TEXTUAL-CONVENTION represents power levels that are
      normally expressed in dBm.  Units are in tenths of a dBm;
      for example, -13.5 dBm will be represented as -135."
  SYNTAX       Integer32

PktcCodecType ::= TEXTUAL-CONVENTION
  STATUS       current
  DESCRIPTION
     " This TEXTUAL-CONVENTION defines various types of codecs

  that MAY be supported.  The description for each
       enumeration is listed below:

       Enumeration     Description
       other           a defined codec not in the enumeration
       unknown         a codec not defined by the PacketCable
```

Codec Specification
g729 ITU-T Recommendation G.729
reserved for future use
g729E ITU-T Recommendation G.729E
pcmu Pulse Code Modulation u-law (PCMU)
g726at32 ITU-T Recommendation G.726-32 (32 kbit/s)
g728 ITU-T Recommendation G.728
pcma Pulse Code Modulation a-law (PCMA)
g726at16 ITU-T Recommendation G.726-16 (16 kbit/s)
g726at24 ITU-T Recommendation G.726-24 (24 kbit/s)
g726at40 ITU-T Recommendation G.726-40 (40 kbit/s)
ilbc IETF Internet low-bit rate codec
bv16 Broadcom BroadVoice16

The list of codecs is consistent with the IETF
Real-Time Transport Protocol (RTP) Profile registry and

the RTP Map Parameters Table in PacketCable Audio/Video
Codecs Specification [PKT-SP-CODEC]. The literal codec
name for each codec is listed below:

Codec Literal Codec Name
g729 G729
g729E G729E
pcmu PCMU
g726at32 G726-32
g728 G728
pcma PCMA
g726at16 G726-16
g726at24 G726-24
g726at40 G726-40
ilbc iLBC
bv16 BV16

The literal codec name is the second column of the table
with codec RTP Map Parameters. The Literal Codec Name Column
contains the codec name used in the local connection
options (LCO) of the NCS messages create connection

(CRCX)/modify connection (MDCX) and is also used to
identify the codec in the Call Management System (CMS)
Provisioning Specification. The RTP Map Parameter column of
the Table contains the string used in the media attribute
line (a=) of the session description protocol (SDP)
parameters in NCS messages."
SYNTAX INTEGER {

```
            other     (1),
            unknown   (2),
            g729      (3),
            reserved  (4),
            g729E     (5),
            pcmu      (6),
            g726at32  (7),
            g728      (8),
            pcma      (9),
            g726at16  (10),
            g726at24  (11),
            g726at40  (12),
            ilbc      (13),
            bv16      (14)
    }

PktcRingCadence   ::= TEXTUAL-CONVENTION
    STATUS       current
    DESCRIPTION
        "This object provides an encoding scheme for ring




        cadences, including repeatability
characteristics.  All
        fields in this object MUST be encoded in network-byte
        order.

        The first three higher-order octets are reserved.  The
        octets that follow are used to encode a 'bit-string', with
        each bit corresponding to 50 milliseconds.  A bit value of
        '1' indicates the presence of a ring-tone, and a bit value
        of '0' indicates the absence of a ring-tone, for that
        duration (50 ms) (Note: A minimum number of octets
        required to encode the bit-string MUST be used).

        The first two of the reserved octets MUST indicate the
        length of the encoded cadence (in bits) and MUST range
        between 1 and 264.  (Note: The length in bits MUST also be
        consistent with the number of octets that encode the
        cadence).  The MTA MUST ignore any unused bits in the last
        octet, but MUST reflect the value as provided on
        subsequent SNMP GETs.

        The
third of the reserved octets indicates 'repeatability'
        and MUST be either 0x80 or 0x00 -- the former value
        indicating 'non-repeatability', and the latter indicating
```

```
        'repeatability'.

        The MTA MUST reject attempts to set a value that violates
        any of the above requirements."


    SYNTAX  OCTET STRING (SIZE(4..36))


PktcSigType     ::= TEXTUAL-CONVENTION
    STATUS      current
    DESCRIPTION
       " This object lists the various types of signaling that may
        be supported:

        other(1) - set when signaling other than NCS is used
        ncs(2)   - Network Call Signaling is a derivation of MGCP
                   (Media Gateway Control Protocol) defined for
                    IPCablecom/PacketCable MTAs."
    SYNTAX INTEGER {
                other(1),
                ncs(2)
    }




DtmfCode::=TEXTUAL-CONVENTION
    STATUS      current
    DESCRIPTION
       "This TEXTUAL-CONVENTION represents the Dual-Tone
        Multi-Frequency (DTMF) Character used
       to indicate the start or end of the digit transition
       sequence used for caller id or Visual Message Waiting
       Indicator (VMWI).

       Note: The DTMF code '*' is indicated using 'dtmfcodeStar',
       and the DTMF code '#' is indicated using ' dtmfcodeHash'."
    SYNTAX      INTEGER {
                dtmfcode0(0),
                dtmfcode1(1),
                dtmfcode2(2),
                dtmfcode3(3),
                dtmfcode4(4),
                dtmfcode5(5),
                dtmfcode6(6),
                dtmfcode7(7),
```

```
            dtmfcode8(8),
            dtmfcode9(9),
            dtmfcodeStar(10),
            dtmfcodeHash(11),
            dtmfcodeA(12),
            dtmfcodeB(13),
            dtmfcodeC(14),
            dtmfcodeD(15)
}

PktcSubscriberSideSigProtocol::=TEXTUAL-CONVENTION
  STATUS  current
  DESCRIPTION
     "This TEXTUAL-CONVENTION
 represents the Signaling
      protocol being used for purposes such as caller id
      or VMWI.

      A value of fsk(1) indicates Frequency Shift Keying
      (FSK).
      A value of dtmf(2) indicates Dual-Tone Multi-Frequency
      (DTMF)."
      SYNTAX INTEGER {
           fsk(1),
           dtmf(2)
      }

pktcSigMibObjects OBJECT IDENTIFIER ::= { pktcIetfSigMib 1 }
pktcSigDevObjects OBJECT IDENTIFIER ::=




                          { pktcSigMibObjects 1 }
pktcSigEndPntConfigObjects OBJECT IDENTIFIER ::=
                          { pktcSigMibObjects 2 }
--
-- The codec table (pktcSigDevCodecTable) defines all combinations
-- of codecs supported by the Multimedia Terminal Adapter (MTA).
--
pktcSigDevCodecTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF PktcSigDevCodecEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      " This table describes the MTA-supported codec types.  An MTA
        MUST populate this table with all possible combinations of
       codecs it supports for simultaneous operation.  For example,
       an MTA with two endpoints may be designed with a particular
```

Digital Signal Processing (DSP) and memory architecture that allows it to support the following fixed combinations of codecs for simultaneous operation:

Codec Type	Maximum Number of Simultaneous Codecs
PCMA	3
PCMA PCMU	2 1
PCMA	1
PCMU	2
PCMU	3
PCMA G729	1 1
G729	2
PCMU G729	1 1

Based on this example, the entries in the codec table would be:

pktcSigDev CodecComboIndex	pktcSigDev CodecType	pktcSigDev CodecMax
1	pcma	3
2	pcma	2
2	pcmu	1
3	pcma	1
3	pcmu	2
4	pcmu	3
5	pcma	1
5	g729	1
6	g729	2
7	pcmu	1
7	g729	1

An operator querying this table is able to determine all possible codec combinations the MTA is capable of simultaneously supporting.

```
        This table MUST NOT include non-voice codecs."
    ::=
  { pktcSigDevObjects 1 }

pktcSigDevCodecEntry  OBJECT-TYPE
    SYNTAX      PktcSigDevCodecEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Each entry represents the maximum number of active
        connections with a particular codec the MTA is capable of
        supporting.  Each row is indexed by a composite key
        consisting of a number enumerating the particular codec
        combination and the codec type."
    INDEX { pktcSigDevCodecComboIndex, pktcSigDevCodecType }
    ::= { pktcSigDevCodecTable 1 }

PktcSigDevCodecEntry  ::= SEQUENCE {
    pktcSigDevCodecComboIndex    Unsigned32,
    pktcSigDevCodecType     PktcCodecType,
    pktcSigDevCodecMax      Unsigned32
    }

pktcSigDevCodecComboIndex  OBJECT-TYPE
    SYNTAX      Unsigned32 (1..255)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        " The index value that enumerates a particular codec
         combination in the pktcSigDevCodecTable."
    ::=
  { pktcSigDevCodecEntry 1 }

pktcSigDevCodecType  OBJECT-TYPE
    SYNTAX       PktcCodecType
    MAX-ACCESS   not-accessible
    STATUS       current




    DESCRIPTION
        " A codec type supported by this MTA."
    ::= { pktcSigDevCodecEntry 2 }

pktcSigDevCodecMax  OBJECT-TYPE
    SYNTAX      Unsigned32(1..255)
    MAX-ACCESS  read-only
```

```
  STATUS      current
  DESCRIPTION
      " The maximum number of simultaneous sessions of a
        particular codec that the MTA can support."
  ::= { pktcSigDevCodecEntry 3 }

--
-- These are the common signaling-related definitions that affect
-- the entire MTA device.
--

pktcSigDevEchoCancellation  OBJECT-TYPE
  SYNTAX       TruthValue
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
      " This object specifies if the device is capable of echo
        cancellation.  The MTA MUST set this MIB object to a
        value of true(1) if it is capable of echo
        cancellation, and a value of false(2) if not."
   ::= { pktcSigDevObjects 2 }

pktcSigDevSilenceSuppression  OBJECT-TYPE
  SYNTAX       TruthValue
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
      " This object specifies if the device is capable of
        silence suppression (as a result of Voice Activity
        Detection).  The MTA MUST set this MIB object to a
        value of true(1) if it is capable of silence
        suppression, and a value of false(2) if not."
::= { pktcSigDevObjects 3 }

pktcSigDevCidSigProtocol  OBJECT-TYPE
  SYNTAX       PktcSubscriberSideSigProtocol
  MAX-ACCESS   read-write
  STATUS       current
  DESCRIPTION
      "This object is used to configure the subscriber-line
       protocol used for signaling on-hook caller id information.



       Different countries define different caller id signaling
       protocols to support caller identification.

       Setting this object at a value fsk(1) sets the subscriber
```

line protocol to be
Frequency Shift Keying (FSK).

Setting this object at a value dtmf(2) sets the subscriber
line protocol to be Dual-Tone Multi-Frequency (DTMF).

The value of this MIB object MUST NOT persist across MTA
reboots."
REFERENCE
"ETSI-EN-300-659-1 Specification"
DEFVAL { fsk }
::= { pktcSigDevObjects 4 }

pktcSigDevR0Cadence OBJECT-TYPE
SYNTAX PktcRingCadence
MAX-ACCESS read-write
STATUS current
DESCRIPTION
" This object specifies ring cadence 0 (a user-defined
field).

The value of this MIB object MUST NOT persist across MTA
reboots."
::= { pktcSigDevObjects 5 }

pktcSigDevR1Cadence OBJECT-TYPE
SYNTAX PktcRingCadence
MAX-ACCESS read-write
STATUS current
DESCRIPTION
" This object specifies ring cadence 1 (a user-defined
field).

The value of this MIB object MUST NOT persist across MTA
reboots."

::= { pktcSigDevObjects 6 }

pktcSigDevR2Cadence OBJECT-TYPE
SYNTAX PktcRingCadence
MAX-ACCESS read-write
STATUS current
DESCRIPTION
" This object specifies ring cadence 2 (a user-defined
field).

```
        The value of this MIB object MUST NOT persist across MTA
        reboots."
    ::= { pktcSigDevObjects 7 }

pktcSigDevR3Cadence     OBJECT-TYPE
    SYNTAX      PktcRingCadence
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        " This object specifies ring cadence 3 (a user-defined
        field).

        The value of this MIB object MUST NOT persist across MTA
        reboots."
    ::= { pktcSigDevObjects 8 }

pktcSigDevR4Cadence     OBJECT-TYPE
    SYNTAX      PktcRingCadence
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        " This object specifies ring cadence 4 (a user-defined
        field).

        The value of this MIB object MUST NOT persist across MTA
         reboots."
    ::= { pktcSigDevObjects 9 }

pktcSigDevR5Cadence     OBJECT-TYPE
    SYNTAX      PktcRingCadence
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        " This object specifies ring cadence 5 (a user-defined
        field).

        The value of this MIB object MUST NOT persist across MTA
        reboots."
    ::= { pktcSigDevObjects 10 }

pktcSigDevR6Cadence     OBJECT-TYPE
    SYNTAX      PktcRingCadence
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        " This object specifies ring cadence 6 (a user-defined
        field).
```

```
        The value of this MIB object MUST NOT persist across MTA
        reboots."
    ::= { pktcSigDevObjects 11 }

pktcSigDevR7Cadence     OBJECT-TYPE
    SYNTAX      PktcRingCadence
    MAX-ACCESS   read-write
    STATUS      current
    DESCRIPTION
       " This object specifies ring cadence 7 (a user-defined
        field).

        The value of this MIB object MUST
 NOT persist across MTA
        reboots."
    ::= { pktcSigDevObjects 12 }

pktcSigDevRgCadence     OBJECT-TYPE
    SYNTAX      PktcRingCadence
    MAX-ACCESS   read-write
    STATUS      current
    DESCRIPTION
       " This object specifies ring cadence rg (a user-defined
        field).

        The value of this MIB object MUST NOT persist across MTA
        reboots."
    ::= { pktcSigDevObjects 13 }

pktcSigDevRsCadence     OBJECT-TYPE
    SYNTAX      PktcRingCadence
    MAX-ACCESS   read-write
    STATUS      current
    DESCRIPTION
       " This object specifies ring cadence rs (a user-defined
        field).  The MTA MUST reject any attempt to make this object
        repeatable.

        The value of this MIB object MUST NOT persist across MTA
        reboots."
    ::= { pktcSigDevObjects 14 }

pktcSigDefCallSigDscp  OBJECT-TYPE
    SYNTAX      Dscp  -- RFC 3289: DIFFSERV-DSCP-TC
```

```
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
      "
 The default value used in the IP header for setting the
       Differentiated Services Code Point (DSCP) value for call




       signaling.

       The value of this MIB object MUST NOT persist across MTA
       reboots."
  DEFVAL { 0 }
  ::= { pktcSigDevObjects 15 }

pktcSigDefMediaStreamDscp  OBJECT-TYPE
  SYNTAX      Dscp  -- RFC 3289: DIFFSERV-DSCP-TC
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
      " This object contains the default value used in the IP
       header for setting the Differentiated Services Code Point
       (DSCP) value for media stream packets.  The MTA MUST NOT
       update this object with the value supplied by the CMS in
       the NCS messages (if present).  Any currently active
       connections are not affected by updates to this object.
       When the value of this object is updated by SNMP, the MTA
       MUST use the new value as a default starting only from
       new connections.

        The value of this MIB object MUST NOT persist across MTA
       reboots."
  DEFVAL { 0 }
  ::= { pktcSigDevObjects 16 }

--
-- pktcSigCapabilityTable - This table defines the valid signaling
-- types supported by this MTA.
--

pktcSigCapabilityTable    OBJECT-TYPE
  SYNTAX       SEQUENCE OF PktcSigCapabilityEntry
  MAX-ACCESS    not-accessible
  STATUS       current
  DESCRIPTION
      " This table describes the signaling types supported by this
       MTA."
```

```
  ::= { pktcSigDevObjects 17 }

pktcSigCapabilityEntry    OBJECT-TYPE
  SYNTAX        PktcSigCapabilityEntry
  MAX-ACCESS    not-accessible
  STATUS        current
  DESCRIPTION
     " Entries in pktcMtaDevSigCapabilityTable - list of
       supported signaling types, versions, and vendor extensions




       for this MTA.  Each entry in the list provides for one
       signaling type and version combination.  If the device
       supports multiple versions of the same signaling
 type, it
       will require multiple entries."
  INDEX { pktcSigCapabilityIndex }
  ::= { pktcSigCapabilityTable 1 }

PktcSigCapabilityEntry  ::= SEQUENCE {
  pktcSigCapabilityIndex           Unsigned32,
  pktcSigCapabilityType            PktcSigType,
  pktcSigCapabilityVersion          SnmpAdminString,
  pktcSigCapabilityVendorExt        SnmpAdminString
  }

pktcSigCapabilityIndex      OBJECT-TYPE
  SYNTAX        Unsigned32 (1..255)
  MAX-ACCESS    not-accessible
  STATUS        current
  DESCRIPTION
     " The index value that uniquely identifies an entry in the
       pktcSigCapabilityTable."
  ::= { pktcSigCapabilityEntry 1 }

pktcSigCapabilityType     OBJECT-TYPE
  SYNTAX        PktcSigType
  MAX-ACCESS    read-only
  STATUS        current
  DESCRIPTION
     " This object identifies the type of signaling used.  This
       value has to be associated with a single signaling
       version."
  ::= { pktcSigCapabilityEntry
 2 }

pktcSigCapabilityVersion     OBJECT-TYPE
```

```
  SYNTAX       SnmpAdminString
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
     " Provides the version of the signaling type - reference
       pktcSigCapabilityType.  Examples would be 1.0 or 2.33 etc."
  ::= { pktcSigCapabilityEntry 3 }

pktcSigCapabilityVendorExt     OBJECT-TYPE
  SYNTAX       SnmpAdminString
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
     " The vendor extension allows vendors to provide a list of




       additional capabilities.

       The syntax for this MIB object in ABNF ([RFC5234]) is
       specified to be zero or more occurrences of vendor
       extensions, as follows:

        pktcSigCapabilityVendorExt  = *(vendor-extension)
        vendor-extension = (ext symbol alphanum) DQUOTE ; DQUOTE
        ext      = DQUOTE %x58 DQUOTE
        symbol   = (DQUOTE %x2D DQUOTE)/(DQUOTE %x2D DQUOTE)
        alphanum = 1*6(ALPHA/DIGIT)

      "
  ::= { pktcSigCapabilityEntry 4 }

pktcSigDefNcsReceiveUdpPort  OBJECT-TYPE
  SYNTAX      InetPortNumber (1025..65535)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object contains the MTA User Datagram Protocol (UDP)
       receive port that is being used for NCS call signaling.
       This object should only be changed by the configuration
       file.

       Unless changed via configuration, this MIB object MUST
       reflect a value of '2427'."
  REFERENCE
     "PacketCable NCS Specification"
  ::= { pktcSigDevObjects 18 }
```

```
pktcSigPowerRingFrequency    OBJECT-TYPE
  SYNTAX       INTEGER {
                 f20Hz(1),
                 f25Hz(2),
                 f33Point33Hz(3),
                 f50Hz(4),
                 f15Hz(5),
                 f16Hz(6),
                 f22Hz(7),
                 f23Hz(8),
                 f45Hz(9)
  }
  MAX-ACCESS   read-only
  STATUS       current
   DESCRIPTION
     " This object must only be provided via the configuration
       file during the provisioning process.  The power ring



       frequency is the frequency at which the sinusoidal voltage
       must travel down the twisted pair to make terminal
       equipment ring.  Different countries define different
       electrical characteristics to make terminal equipment
       ring.

       The f20Hz setting corresponds to a power ring frequency
       of 20 Hertz.  The f25Hz setting corresponds to a power ring
       frequency of 25 Hertz.  The f33Point33Hz setting
       corresponds to a power ring frequency of 33.33 Hertz.  The
       f50Hz setting corresponds to a power ring frequency of 50
       Hertz.  The f15Hz setting corresponds to a power ring
       frequency of 15 Hertz.  The f16Hz setting corresponds to a
       power ring frequency of 16 Hertz.  The f22Hz setting
       corresponds to a power ring frequency of
 22 Hertz.  The
       f23Hz setting corresponds to a power ring frequency of 23
       Hertz.  The f45Hz setting corresponds to a power ring
       frequency of 45 Hertz."
  REFERENCE
       "ETSI-EN-300-001"
  ::= { pktcSigDevObjects 19 }

pktcSigPulseSignalTable    OBJECT-TYPE
  SYNTAX       SEQUENCE OF PktcSigPulseSignalEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
```

```
      " The Pulse signal table defines the pulse signal operation.
        There are nine types of international pulse signals,
        with each signal having a set of provisionable parameters.
        The values of the MIB objects in this table take effect
        only if these parameters are not defined via signaling, in
        which case, the latter determines the values of the
        parameters.  The MIB objects in this table do not persist
        across MTA reboots."
  REFERENCE
     "ETSI-TS-101-909-4 Specification"
  ::= { pktcSigDevObjects
 20 }

pktcSigPulseSignalEntry    OBJECT-TYPE
  SYNTAX       PktcSigPulseSignalEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
     " This object defines the set of parameters associated with
       each particular value of pktcSigPulseSignalType.  Each
       entry in the pktcSigPulseSignalTable is indexed by the
       pktcSigPulseSignalType object.



       The conceptual rows MUST NOT persist across MTA reboots."
  INDEX { pktcSigPulseSignalType }
  ::= { pktcSigPulseSignalTable 1 }

PktcSigPulseSignalEntry ::= SEQUENCE {
     pktcSigPulseSignalType             INTEGER,
     pktcSigPulseSignalFrequency        INTEGER,
     pktcSigPulseSignalDbLevel          TenthdBm,
     pktcSigPulseSignalDuration         Unsigned32,
     pktcSigPulseSignalPulseInterval    Unsigned32,
     pktcSigPulseSignalRepeatCount      Unsigned32
}

pktcSigPulseSignalType    OBJECT-TYPE
  SYNTAX       INTEGER
               {
                  initialRing(1),
                pulseLoopClose(2),
                pulseLoopOpen(3),
                enableMeterPulse(4),
                meterPulseBurst(5),
                pulseNoBattery(6),
                pulseNormalPolarity(7),
```

```
                pulseReducedBattery(8),
                pulseReversePolarity(9)
              }
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
     "There are nine types of international pulse signals.  These
      signals are defined as follows:
      initial ring
      pulse loop close
      pulse loop open
      enable meter pulse
      meter pulse burst
      pulse no battery
      pulse normal polarity
      pulse reduced battery
      pulse reverse polarity"
  REFERENCE
     "ETSI-EN-300-324-1 Specification"

  ::= { pktcSigPulseSignalEntry 1 }

pktcSigPulseSignalFrequency    OBJECT-TYPE
  SYNTAX       INTEGER {

         twentyfive(1),



              twelvethousand(2),
              sixteenthousand(3)
  }
  MAX-ACCESS   read-write
  STATUS       current
  DESCRIPTION
     " This object is only applicable to the initialRing,
       enableMeterPulse, and meterPulseBurst signal types.  This
       object identifies the frequency of the generated signal.
       The following table defines the default values for this
       object depending on signal type:

       pktcSigPulseSignalType     Default
       initialRing              25
       enableMeterPulse          16000
       meterPulseBurst           16000

       The value of twentyfive MUST only be used for the
       initialRing signal type.  The values of twelvethousand and
```

```
        sixteenthousand MUST only be used for enableMeterPulse and
        meterPulseBurst signal types.  An attempt to set this
        object while the value of pktcSigPulseSignalType is not
        initialRing,
 enableMeterPulse, or meterPulseBurst will
        result in an 'inconsistentValue' error."
   REFERENCE
      "ETSI-EN-300-001 Specification"
       ::= { pktcSigPulseSignalEntry 2}

pktcSigPulseSignalDbLevel    OBJECT-TYPE
   SYNTAX       TenthdBm (-350..0)
   UNITS        "1/10 of a dBm"
   MAX-ACCESS   read-write
   STATUS       current
   DESCRIPTION
      " This object is only applicable to the enableMeterPulse and
        meterPulseBurst signal types.  This is the decibel level
        for each frequency at which tones could be generated at
        the a and b terminals (TE connection point).  An attempt to
        set this object while the value of pktcSigPulseSignalType
        is not enableMeterPulse or meterPulseBurst will result in
        an 'inconsistentValue' error."
   REFERENCE
      "ETSI-EN-300-001 Specification"

   DEFVAL { -135 }
   ::={pktcSigPulseSignalEntry 3 }

pktcSigPulseSignalDuration    OBJECT-TYPE



   SYNTAX       Unsigned32
(0..5000)
   UNITS        "Milliseconds"
   MAX-ACCESS   read-write
   STATUS       current
   DESCRIPTION
      " This object specifies the pulse duration for each
        signal type.  In addition, the MTA must accept the values
        in the incremental steps specific for each signal type.
        The following table defines the default values and the
        incremental steps for this object depending on the signal
        type:

        pktcSigPulseSignaltype  Default (ms)   Increment (ms)
        initialRing                200             50
```

pulseLoopClose 200 10
pulseLoopOpen 200 10
enableMeterPulse 150 10
meterPulseBurst 150 10
pulseNoBattery 200 10
pulseNormalPolarity 200 10
pulseReducedBattery 200 10
pulseReversePolarity
200 10

An attempt to set this object to a value that does not fall on one of the increment boundaries, or on the wrong increment boundary for the specific signal type, will result in an 'inconsistentValue' error."

REFERENCE
"ETSI-EN-300-324-1 Specification"
::= {pktcSigPulseSignalEntry 4 }

pktcSigPulseSignalPulseInterval OBJECT-TYPE
SYNTAX Unsigned32 (0..5000)
UNITS "Milliseconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
" This object specifies the repeat interval, or the period, for each signal type. In addition, the MTA must accept the values in the incremental steps specific for each signal type. The following table defines the default values and the incremental steps for this object, depending on the signal type:

pktcSigPulseSignaltype Default (ms) Increment (ms)
initialRing 200 50
pulseLoopClose 1000 10
pulseLoopOpen 1000 10

enableMeterPulse 1000 10
meterPulseBurst 1000 10
pulseNoBattery 1000 10
pulseNormalPolarity 1000 10
pulseReducedBattery 1000 10
pulseReversePolarity 1000 10

An attempt to set this object to a value that does not fall on one of the increment boundaries, or on the wrong increment boundary for the specific signal type, will

```
        result in an 'inconsistentValue' error."
    REFERENCE
       "ETSI-EN-300-324-1 Specification"
       ::= { pktcSigPulseSignalEntry 5}

pktcSigPulseSignalRepeatCount    OBJECT-TYPE
    SYNTAX       Unsigned32 (1..50)
    MAX-ACCESS   read-write
    STATUS       current

 DESCRIPTION
       " This object specifies how many times to repeat a pulse.
         This object is not used by the enableMeterPulse signal
         type, and in that case, the value is irrelevant.  The
         following table defines the default values and the valid
         ranges for this object, depending on the signal type:

         pktcSigPulseSignaltype  Default   Range

         initialRing               1       1-5
         pulseLoopClose            1       1-50
         pulseLoopOpen             1       1-50
         enableMeterPulse      (any value)(but not used)
         meterPulseBurst           1       1-50
         pulseNoBattery            1       1-50
         pulseNormalPolarity       1       1-50
         pulseReducedBattery       1       1-50
         pulseReversePolarity      1       1-50

         An attempt to set this object to a value that does not
         fall within the range for the specific
         signal type will result in an
 'inconsistentValue' error."
    ::={ pktcSigPulseSignalEntry 6 }

pktcSigDevCidMode    OBJECT-TYPE
    SYNTAX       INTEGER {
                 duringRingingETS(1),
                 dtAsETS(2),
                 rpAsETS(3),



                 lrAsETS(4),
                 lrETS(5)
                 }
    MAX-ACCESS read-write
    STATUS current
```

```
  DESCRIPTION
     " For on-hook caller id, pktcSigDevCidMode selects the method
       for representing and signaling caller identification.  For
       the duringRingingETS method, the Frequency Shift Keying
       (FSK) or the Dual-Tone Multi-Frequency (DTMF) containing
       the caller identification information is sent between the
       first and second ring pattern.

       For the dtAsETS,rpAsETS, lrAsETS and lrETS
       methods, the FSK or DTMF containing the caller id
       information is sent before the first ring pattern.

       For the dtAsETS method, the FSK or DTMF is sent after the
       Dual
 Tone Alert Signal.  For the rpAsETS method, the FSK or
       DTMF is sent after a Ring Pulse.

       For the lrAsETS method, the Line Reversal occurs first,
       then the Dual Tone Alert Signal, and, finally, the FSK or
       DTMF is sent.

       For the lrETS method, the Line Reversal occurs first,
       then the FSK or DTMF is sent.

       The value of this MIB object MUST NOT persist across MTA
       reboots."

  DEFVAL { rpAsETS}
  ::= {pktcSigDevObjects 21 }

pktcSigDevCidAfterRing     OBJECT-TYPE
  SYNTAX       Unsigned32 (0|50..2000)
  UNITS        "Milliseconds"
  MAX-ACCESS   read-write
  STATUS       current
  DESCRIPTION
     " This object specifies the delay between the end of first
       ringing pattern and the start of the transmission of the
       FSK or DTMF containing the caller id information.  It is
       only used when pktcSigDevCidMode is set to a value of
       'duringRingingETS'.

       The following
 table defines the default values
       for this MIB object, depending on the signal type
```

(pktcSigDevCidMode), and MUST be followed:

Value of pktcSigDevCidMode Default value

duringringingETS 550 ms
dtAsETS any value (not used)
rpAsETS any value (not used)
lrAsETS any value (not used)
lrETS any value (not used)

An attempt to set this object while the value of pktcSigDevCidMode is not duringringingETS will result in an 'inconsistentValue' error.

The value of this MIB object MUST NOT persist across MTA reboots."

REFERENCE
"ETSI-EN-300-659-1 Specification"
DEFVAL { 550 }
::= {pktcSigDevObjects 22 }

pktcSigDevCidAfterDTAS OBJECT-TYPE
SYNTAX Unsigned32 (0|45..500)
UNITS "Milliseconds"
MAX-ACCESS
read-write
STATUS current
DESCRIPTION
" This object specifies the delay between the end of the Dual Tone Alert Signal (DT-AS) and the start of the transmission of the FSK or DTMF containing the caller id information. This object is only used when pktcSigDevCidMode is set to a value of 'dtAsETS' or 'lrAsETS'.

The following table defines the default values for this MIB object, depending on the signal type (pktcSigDevCidMode), and MUST be followed:

Value of pktcSigDevCidMode Default value

duringringingETS any value (not used)
dtAsETS 50 ms
rpAsETS any value (not used)
lrAsETS 50 ms
lrETS any value (not used)

An attempt to set this object while the value of

pktcSigDevCidMode
is not 'dtAsETS' or 'lrAsETS' will
result in an 'inconsistentValue' error.

The value of this MIB object MUST NOT persist across MTA
reboots."
REFERENCE
"ETSI-EN-300-659-1 Specification"
DEFVAL { 50 }
::= {pktcSigDevObjects 23 }

pktcSigDevCidAfterRPAS OBJECT-TYPE
SYNTAX Unsigned32 (0|500..800)
UNITS "Milliseconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
" This object specifies the delay between the end of the
Ring Pulse Alert Signal (RP-AS) and the start of the
transmission of the FSK or DTMF containing the caller id
information. This MIB object is only used when
pktcSigDevCidMode is set to a value of 'rpAsETS'.
The following table defines the default values
for this MIB object, depending on the signal type
(pktcSigDevCidMode), and MUST be followed:

Value of pktcSigDevCidMode Default
value

duringringingETS any value (not used)
dtAsETS any value (not used)
rpAsETS 650 ms
lrAsETS any value (not used)
lrETS any value (not used)

An attempt to set this object while the value of
pktcSigDevCidMode is not 'rpAsETS' will result in an
'inconsistentValue' error.

The value of this MIB object MUST NOT persist across MTA
reboots."
REFERENCE
"ETSI-EN-300-659-1 Specification"
DEFVAL { 650 }

```
  ::= {pktcSigDevObjects 24 }

pktcSigDevRingAfterCID    OBJECT-TYPE
  SYNTAX       Unsigned32 (0|50..500)
  UNITS        "Milliseconds"
  MAX-ACCESS   read-write



  STATUS       current
  DESCRIPTION
     " This object specifies the delay between the end of the
       complete transmission of the FSK or DTMF containing the
       caller
 id information and the start of the first ring
       pattern.  It is only used when pktcSigDevCidMode is
       set to a value of 'dtAsETS', 'rpAsETS', 'lrAsETS' or
       'lrETS'.

       The following table defines the default values
       for this MIB object, depending on the signal type
      (pktcSigDevCidMode), and MUST be followed:

       Value of pktcSigDevCidMode       Default value

       duringringingETS              any value  (not used)
       dtAsETS                      250 ms
       rpAsETS                      250 ms
       lrAsETS                      250 ms
       lrETS                       250 ms

       An attempt to set this object while the value of
       pktcSigDevCidMode is not 'dtAsETS', 'rpAsETS',
       'lrAsETS', or 'lrETS' will result in an 'inconsistent
       value' error.

       The value of this MIB object MUST NOT persist across MTA
       reboots."
  REFERENCE

   "ETSI-EN-300-659-1 Specification"
  DEFVAL { 250 }
  ::= {pktcSigDevObjects 25 }

pktcSigDevCidDTASAfterLR    OBJECT-TYPE
  SYNTAX       Unsigned32 (50..655)
  UNITS        "Milliseconds"
  MAX-ACCESS   read-write
```

```
  STATUS       current
  DESCRIPTION
     " This object specifies the delay between the end of the
       Line Reversal and the start of the Dual Tone Alert Signal
       (DT-AS).  This object is only used when pktcSigDevCidMode
       is set to a value of 'lrAsETS'.

       The following table defines the default values
       for this MIB object, depending on the signal type
      (pktcSigDevCidMode), and MUST be followed:




       Value of pktcSigDevCidMode       Default value

       duringringingETS                 any value  (not used)
       dtAsETS                         any value  (not used)
       rpAsETS                         any value  (not used)
       lrAsETS                         250 ms
       lrETS
                     any value  (not used)

       An attempt to set this object while the value of
       pktcSigDevCidMode is not lrAsETS will result in an
       'inconsistentValue' error.

       The value of this MIB object MUST NOT persist across MTA
       reboots."
  REFERENCE
     "ETSI-EN-300-659-1 Specification"
  DEFVAL { 250 }

  ::= {pktcSigDevObjects 26 }

pktcSigDevVmwiMode    OBJECT-TYPE
  SYNTAX       INTEGER {
               dtAsETS(1),
               rpAsETS(2),
               lrAsETS(3),
               osi(4),
               lrETS(5)
               }
  MAX-ACCESS read-write
  STATUS current
  DESCRIPTION
     " For visual message waiting indicator (VMWI),
       pktcSigDevVmwiMode selects the alerting signal method.  For
```

```
        the dtAsETS, rpAsETS, lrAsETS, osi, and lrETS methods,
        the FSK containing the VMWI information is sent after an
        alerting signal.

        For the dtAsETS method,
 the FSK, or DTMF
        is sent after the Dual Tone Alert Signal.  For the rpAsETS
        method, the FSK or DTMF is sent after a Ring Pulse.

        For the lrAsETS method, the Line Reversal occurs first,
        then the Dual Tone Alert Signal, and, finally, the FSK or
        DTMF is sent.

        For the OSI method, the FSK or DTMF is sent after the Open
        Switching Interval.




        For the lrETS method, the Line Reversal occurs first,
        then the FSK or DTMF is sent.

        The value of this MIB object MUST NOT persist across MTA
        reboots."

   DEFVAL { rpAsETS }
   ::= {pktcSigDevObjects 27 }

pktcSigDevVmwiAfterDTAS    OBJECT-TYPE
   SYNTAX       Unsigned32 (0|45..500)
   UNITS        "Milliseconds"
   MAX-ACCESS   read-write
   STATUS       current
   DESCRIPTION
      " This object specifies the delay between the end of the
        Dual Tone Alert Signal (DT-AS) and the start of the
        transmission of the
 FSK or DTMF containing the VMWI
        information.

        This object is only used when pktcSigDevVmwiMode is
        set to a value of 'dtAsETS' or 'lrAsETS'.

        The following table defines the default values
        for this MIB object, depending on the signal type
       (pktcSigDevVmwiMode), and MUST be followed:

        Value of pktcSigDevVmwiMode       Default value
```

```
        dtAsETS                    50 ms
        rpAsETS                    any value  (not used)
        lrAsETS                    50 ms
        lrETS                      any value  (not used)

        An attempt to set this object while the value of
        pktcSigDevVmwiMode is not 'dtAsETS' or 'lrAsETS' will
        result in an 'inconsistentValue' error.

        The value of this MIB object MUST NOT persist across MTA
        reboots."
    REFERENCE
       "ETSI-EN-300-659-1 Specification"
    DEFVAL { 50 }
    ::= {pktcSigDevObjects 28
  }


pktcSigDevVmwiAfterRPAS    OBJECT-TYPE
    SYNTAX       Unsigned32 (0|500..800)



    UNITS        "Milliseconds"
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
       " This object specifies the delay between the end of the
        Ring Pulse Alert Signal (RP-AS) and the start of the
        transmission of the FSK or DTMF containing the VMWI
        information.

        This object is only used when pktcSigDevVmwiMode is
        set to a value of 'rpAsETS'.

        The following table defines the default values
        for this MIB object, depending on the signal type
       (pktcSigDevVmwiMode), and MUST be followed:

        Value of pktcSigDevVmwiMode       Default value

        dtAsETS                    any value  (not used)
        rpAsETS                    650 ms
        lrAsETS                    any value  (not used)
        lrETS                      any value  (not used)

        An attempt
```

```
 to set this object while the value of
       pktcSigDevVmwiMode is not 'rpAsETS' will result in an
       'inconsistentValue' error.

       The value of this MIB object MUST NOT persist across MTA
       reboots."
  REFERENCE
     "ETSI-EN-300-659-1 Specification"
  DEFVAL { 650 }
  ::= {pktcSigDevObjects 29 }

pktcSigDevVmwiDTASAfterLR    OBJECT-TYPE
  SYNTAX       Unsigned32 (0|50..655)
  UNITS        "Milliseconds"
  MAX-ACCESS   read-write
  STATUS       current
  DESCRIPTION
     " This object specifies the delay between the end of the
       Line Reversal and the start of the Dual Tone Alert Signal
       (DT-AS) for VMWI information.  This object is only used
       when pktcSigDevVmwiMode is set to a value of 'lrAsETS'.

       The following table defines the default values
       for this MIB object, depending on the signal type
      (pktcSigDevVmwiMode), and MUST be followed:




       Value of pktcSigDevVmwiMode
      Default value

       dtAsETS                    any value  (not used)
       rpAsETS                    any value  (not used)
       lrAsETS                   250 ms
       lrETS                    any value  (not used)

       An attempt to set this object while the value of
       pktcSigDevVmwiMode is not 'lrAsETS' will result in an
       'inconsistentValue' error.

       The value of this MIB object MUST NOT persist across MTA
       reboots."
  REFERENCE
     "ETSI-EN-300-659-1 Specification"
  DEFVAL { 250 }
  ::= {pktcSigDevObjects 30 }
```

```
pktcSigDevRingCadenceTable    OBJECT-TYPE
  SYNTAX       SEQUENCE OF PktcSigDevRingCadenceEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
     "Cadence rings are defined by the telco governing
      body for each country.  The MTA must be able to support
      various ranges of cadence patterns and cadence periods.
      The
 MTA will be able to support country-specific
      provisioning of the cadence and idle period.  Each
      cadence pattern will be assigned a unique value ranging
      from 0-127 (inclusive) corresponding to the value of x,
      where x is the value sent in the cadence ringing (cr)
      signal cr(x), requested per the appropriate NCS
      message, and defined in the E package.  The MTA will derive
      the cadence periods from the ring cadence table entry, as
      provisioned by the customer.  The MTA is allowed to provide
      appropriate default values for each of the ring cadences.
      This table only needs to be supported when the MTA
      implements the E package."
  REFERENCE
     "ETSI-TS-101-909-4 Specification"
  ::= { pktcSigDevObjects 31 }

pktcSigDevRingCadenceEntry    OBJECT-TYPE
  SYNTAX       PktcSigDevRingCadenceEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION




     " Each entry in
 this row corresponds to a ring cadence
       that is being supported by the device.  The conceptual
       rows MUST NOT persist across MTA reboots."
  INDEX { pktcSigDevRingCadenceIndex }
  ::= { pktcSigDevRingCadenceTable 1 }

PktcSigDevRingCadenceEntry ::= SEQUENCE {
     pktcSigDevRingCadenceIndex       Unsigned32,
     pktcSigDevRingCadence            PktcRingCadence
  }

pktcSigDevRingCadenceIndex    OBJECT-TYPE
  SYNTAX       Unsigned32 (0..127)
  MAX-ACCESS   not-accessible
```

```
  STATUS       current
  DESCRIPTION
      " A unique value ranging from 0 to 127 that corresponds to the
        value sent by the LE based on country-specific cadences,
        one row per cadence cycle.  In any given system
        implementation for a particular country, it is anticipated
        that a small number of ring cadences will be in use.  Thus,
        this table most likely will not be populated to its full
        size."
  ::= { pktcSigDevRingCadenceEntry
 1 }

pktcSigDevRingCadence    OBJECT-TYPE
  SYNTAX       PktcRingCadence
  MAX-ACCESS   read-write
  STATUS       current
  DESCRIPTION
     "This is the Ring Cadence."
  ::= { pktcSigDevRingCadenceEntry 2 }


pktcSigDevToneTable    OBJECT-TYPE
  SYNTAX       SEQUENCE OF PktcSigDevToneEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
      " The Tone Table defines the composition of tones and
        various tone operations.

        The definition of the tones callWaiting1 through
        callWaiting4 in this table MUST only contain the
        audible tone itself; the delay between tones or the value
        of the tone repeat count are not applicable for the call
        waiting tones.




        The delay between tones or the repeat count is controlled
        by the objects pktcSigEndPntConfigCallWaitingDelay and
        pktcSigEndPntConfigCallWaitingMaxRep.  If the
        pktcSigDevToneType is set to either
 of the values
        callWaiting1, callWaiting2, callWaiting3, or callWaiting4,
        then the value of the pktcSigDevToneWholeToneRepeatCount
        object indicates that the particular frequency group is
        applicable, as a repeatable part of the tone, based on the
        value of the MIB object
```

pktcSigDevToneWholeToneRepeatCount.

The MTA MUST make sure that, after the provisioning cycle, the table is fully populated (i.e., for each possible index, an entry MUST be defined) using reasonable defaults for each row that was not defined by the provisioning information delivered via MTA Configuration.

The frequency composition of each tone is defined by the pktcSigDevMultiFreqToneTable. For each tone type defined in pktcSigDevToneTable, the MTA MUST populate at least one entry in the pktcSigDevMultiFreqToneTable.

For each particular value of pktcSigDevToneType, the pktcSigDevToneTable table can define non-repeating and repeating groups of the frequencies defined by the pktcSigDevMultiFreqToneTable, such that each group is represented by the set of the consecutive rows (frequency group) in the pktcSigDevMultiFreqToneTable.

Objects in this table do not persist across MTA reboots. For tones with multiple frequencies refer to the MIB table pktcSigDevMultiFreqToneTable."

```
  REFERENCE
     "PacketCable NCS Specification, ETSI-TS-101-909-4
     Specification."
  ::= { pktcSigDevObjects 32 }

pktcSigDevToneEntry    OBJECT-TYPE
  SYNTAX       PktcSigDevToneEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
     " The different tone types that can be provisioned based on
     country-specific needs.

     Each entry contains the tone generation parameters for
     a specific frequency group of the specific
 Tone Type.
```

The different parameters can be provisioned via MTA configuration based on country specific needs. An MTA MUST populate all entries of this table for each tone type."

```
  INDEX { pktcSigDevToneType, pktcSigDevToneFreqGroup }
  ::= { pktcSigDevToneTable 1 }

PktcSigDevToneEntry ::= SEQUENCE {
  pktcSigDevToneType                  INTEGER,
  pktcSigDevToneFreqGroup             Unsigned32,
  pktcSigDevToneFreqCounter           Unsigned32,
  pktcSigDevToneWholeToneRepeatCount  Unsigned32,
  pktcSigDevToneSteady                TruthValue
  }

pktcSigDevToneType      OBJECT-TYPE
  SYNTAX      INTEGER {
              busy(1),
              confirmation(2),
              dial(3),
              messageWaiting(4),
              offHookWarning(5),
              ringBack(6),
              reOrder(7),
              stutterdial(8),
              callWaiting1(9),

      callWaiting2(10),
              callWaiting3(11),
              callWaiting4(12),
              alertingSignal(13),
              specialDial(14),
              specialInfo(15),
              release(16),
              congestion(17),
              userDefined1(18),
              userDefined2(19),
              userDefined3(20),
              userDefined4(21)
              }
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A unique value that will correspond to the different
      tone types.  These tones can be provisioned based on
      country-specific needs.  This object defines the type
      of tone being accessed.

      The alertingSignal, specialDial, specialInfo, release,
```

```
        congestion, userDefined1, userDefined2, userDefined3,
        and userDefined4 tone types are used in
        the E line package."
    ::= { pktcSigDevToneEntry 1 }

pktcSigDevToneFreqGroup  OBJECT-TYPE

    SYNTAX      Unsigned32(1..4)
      MAX-ACCESS   not-accessible
      STATUS      current
      DESCRIPTION
        "This MIB object represents the Tone Sequence reference
        of a multi-sequence tone."
      ::={ pktcSigDevToneEntry 2}

pktcSigDevToneFreqCounter OBJECT-TYPE
      SYNTAX      Unsigned32(1..8)
      MAX-ACCESS   read-only
      STATUS      current
      DESCRIPTION
        "This MIB object represents the number of consecutive
        multi-frequency tones for the particular tone type in
        the multi-frequency table (pktcSigDevMultiFreqToneTable).

        Such a sequence of the consecutive multi-frequency tones
        forms the tone group for the particular tone type in the
        pktcSigDevToneTable."
      ::={ pktcSigDevToneEntry 3}

pktcSigDevToneWholeToneRepeatCount      OBJECT-TYPE
    SYNTAX      Unsigned32 (0..5000)
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
       "This is the repeat count,
 which signifies how many times
        to repeat the entire on-off cadence sequence.  Setting this
        object may result in a cadence duration longer or shorter
        than the overall signal duration specified by the time out
        (TO) object for a particular signal.  If the repeat count
        results in a longer tone duration than the signal duration
        specified by the TO, the tone duration defined by the
        TO object for a particular signal always represents
        the overall signal duration for a tone.  In this case, the
        tone duration repeat count will not be fully exercised, and
        the desired tone duration will be truncated per the TO
        setting.  If the repeat count results in a shorter tone
        duration than the signal duration specified by the TO, the
```

tone duration defined by the repeat count takes precedence
over the TO and will end the signal event. In this case,

the TO represents a
time not to be exceeded for the signal.
It is recommended to ensure proper telephony signaling so that
the TO duration setting should always be longer than the
desired repeat count-time duration."
::={ pktcSigDevToneEntry 4 }

pktcSigDevToneSteady OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This MIB object represents the steady tone status. A value
of 'true(1)' indicates that the steady tone is applied, and
a value of 'false(2)' indicates otherwise.
Devices must play out the on-off cadence sequence for
the number of times indicated by the MIB object
'pktcSigDevToneWholeToneRepeatCount' prior to applying the
last tone steadily, indefinitely. If the MIB table
'pktcSigDevToneTable' contains multiple rows with this
Object set to a value of 'true(1)', the steady tone is
applied to the last repeating frequency
group of the tone.

Setting this MIB object may result in a tone duration that is
longer or shorter than the overall signal duration
specified by the time out (TO) MIB object for a particular
signal. If the repeat count results in a longer tone
duration than the signal duration specified by the TO, the
tone duration defined by the TO object for a particular
signal always represents the overall signal duration for a
tone. In this case, the tone duration repeat count will
not be fully exercised, and the desired tone duration will
be truncated per the TO setting. If the repeat count
results in a shorter tone duration than the signal duration
specified by the TO, the tone duration defined by the
repeat count takes precedence over the TO and will end the
signal event. In this case, the TO represents a time not to
be exceeded for the signal.

It is recommended to ensure proper telephony signaling that
The TO duration setting should always be longer than the

```
      desired repeat count-time duration, plus the desired maximum
      steady tone period."
  ::={ pktcSigDevToneEntry 5 }

pktcSigDevMultiFreqToneTable    OBJECT-TYPE
    SYNTAX       SEQUENCE OF PktcSigDevMultiFreqToneEntry
    MAX-ACCESS   not-accessible
    STATUS       current



    DESCRIPTION
        " This MIB table defines the characteristics of tones
          with multiple frequencies.  The constraints imposed
          on the tones by the MIB table pktcSigDevToneTable
          need to be considered for MIB objects in this table
          as well.

          The MTA MUST populate the corresponding row(s)
          of the pktcSigDevMultiFreqToneTable for each tone
          defined in the pktcSigDevToneTable.

          The contents of the table may be provisioned via
          MTA configuration."
     REFERENCE
        "PacketCable NCS Specification, ETSI-TS-101-909-4
         Specification."
    ::= { pktcSigDevObjects 33 }

pktcSigDevMultiFreqToneEntry    OBJECT-TYPE
    SYNTAX       PktcSigDevMultiFreqToneEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        " The different tone types with multiple frequencies
          that can be provisioned based on country-specific
          needs."
    INDEX {pktcSigDevToneType, pktcSigDevToneNumber}
    ::= { pktcSigDevMultiFreqToneTable 1 }

PktcSigDevMultiFreqToneEntry ::= SEQUENCE {
      pktcSigDevToneNumber                Unsigned32,
      pktcSigDevToneFirstFreqValue          Unsigned32,
      pktcSigDevToneSecondFreqValue         Unsigned32,
      pktcSigDevToneThirdFreqValue          Unsigned32,
      pktcSigDevToneFourthFreqValue         Unsigned32,
      pktcSigDevToneFreqMode               INTEGER,
      pktcSigDevToneFreqAmpModePrtg
```

```
        Unsigned32,
      pktcSigDevToneDbLevel                TenthdBm,
      pktcSigDevToneFreqOnDuration          Unsigned32,
      pktcSigDevToneFreqOffDuration         Unsigned32,
      pktcSigDevToneFreqRepeatCount         Unsigned32
}

pktcSigDevToneNumber OBJECT-TYPE
   SYNTAX       Unsigned32(1..8)
   MAX-ACCESS   not-accessible
   STATUS       current
   DESCRIPTION



      "This MIB object represents the frequency reference
       of a multi-frequency tone."
   ::={ pktcSigDevMultiFreqToneEntry 1}

pktcSigDevToneFirstFreqValue    OBJECT-TYPE
   SYNTAX       Unsigned32(0..4000)
   MAX-ACCESS   read-only
   STATUS       current
   DESCRIPTION
     "This MIB object represents the value of the first
      frequency of a tone type.  A value of zero implies
      absence of the referenced frequency."
   ::={ pktcSigDevMultiFreqToneEntry 2}

pktcSigDevToneSecondFreqValue
  OBJECT-TYPE
   SYNTAX       Unsigned32(0..4000)
   MAX-ACCESS   read-only
   STATUS       current
   DESCRIPTION
     "This MIB object represents the value of the second
      frequency of a tone type.  A value of zero implies
      absence of the referenced frequency."
   ::={ pktcSigDevMultiFreqToneEntry 3}

pktcSigDevToneThirdFreqValue    OBJECT-TYPE
   SYNTAX       Unsigned32(0..4000)
   MAX-ACCESS   read-only
   STATUS       current
   DESCRIPTION
     "This MIB object represents the value of the third
      frequency of a tone type.  A value of zero implies
      absence of the referenced frequency."
```

```
    ::={ pktcSigDevMultiFreqToneEntry 4}

 pktcSigDevToneFourthFreqValue    OBJECT-TYPE
    SYNTAX       Unsigned32(0..4000)
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
      "This MIB object represents the value of the fourth
       frequency of a tone type.  A
value of zero implies
       absence of the referenced frequency."
    ::={ pktcSigDevMultiFreqToneEntry 5}

 pktcSigDevToneFreqMode OBJECT-TYPE
    SYNTAX       INTEGER {
                 firstModulatedBySecond(1),
                 summation(2)



                }
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
    "This MIB object provides directive on the
     modulation or summation of the frequencies
     involved in the tone.

     It is to be noted that while summation can
     be done without any constraint on the number
     of frequencies, the modulation (amplitude)
     holds good only when there are two frequencies
     (first and second).

     Thus:
       - If the mode is set to a value of
         'firstModulatedBySecond(1)', the first frequency
         MUST be modulated by the second, and the remaining
         frequencies (third and fourth) ignored.  The
         percentage
of amplitude modulation to be applied
         is defined by the MIB object
         pktcSigDevToneFreqAmpModePrtg.

       - If the mode is set to a value of
         'summation(2)', all the frequencies MUST be
         summed without any modulation.
    "
```

```
    ::={ pktcSigDevMultiFreqToneEntry 6}

pktcSigDevToneFreqAmpModePrtg OBJECT-TYPE
    SYNTAX      Unsigned32(0..100)
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
      "This MIB object represents the percentage of amplitude
       modulation applied to the second frequency
       when the MIB object pktcSigDevToneFreqMode is
       set to a value of 'firstModulatedBySecond (1)'.

       If the MIB object pktcSigDevToneFreqMode is set to
       value of 'summation (2)', then this MIB object MUST be
       ignored."
    ::={ pktcSigDevMultiFreqToneEntry 7}

pktcSigDevToneDbLevel    OBJECT-TYPE
   SYNTAX      TenthdBm (-250..-110)
   UNITS
     "1/10 of a dBm"
   MAX-ACCESS   read-only



   STATUS      current
   DESCRIPTION
      "This MIB object contains the decibel level for each
       analog signal (tone) that is locally generated
       (versus in-band supervisory tones) and sourced to
       the a-b terminals (TE connection point).  Each tone
       in itself may consist of multiple frequencies, as
       defined by the MIB table pktcSigDevMultiFreqToneTable.

       This MIB object reflects the desired level at
       the Telco (POTS) a-b (T/R) terminals, including the
       effect of any MTA receiver gain (loss).  This is required
       so that locally generated tones are consistent with
       remotely generated in-band tones at the a-b terminals,
       consistent with user expectations.

       This MIB object must be set for each tone.
       When tones are formed by combining multi-frequencies,
       the level of each frequency
shall be set so as to result
       in the tone level specified in this object at the a-b
       (T/R) terminals.
```

```
        The wide range of levels for this Object is required
        to provide signal-generator levels across the wide
        range of gains (losses) -- but does not imply the entire
        range is to be achievable given the range of gains (losses)
        in the MTA."
 DEFVAL { -120 }
 ::={ pktcSigDevMultiFreqToneEntry 8}

pktcSigDevToneFreqOnDuration OBJECT-TYPE
    SYNTAX       Unsigned32(0..5000)
    UNITS        "milliseconds"
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
      "This MIB object represents the duration for which the
       frequency reference corresponding to the tone type
       is turned on."
    ::={ pktcSigDevMultiFreqToneEntry 9}

pktcSigDevToneFreqOffDuration OBJECT-TYPE
    SYNTAX       Unsigned32(0..5000)
    UNITS        "milliseconds"
    MAX-ACCESS
 read-only
    STATUS       current
    DESCRIPTION
      "This MIB object represents the duration for which the




       frequency reference corresponding to the tone type
       is turned off."
    ::={ pktcSigDevMultiFreqToneEntry 10}

pktcSigDevToneFreqRepeatCount OBJECT-TYPE
    SYNTAX       Unsigned32(0..5000)
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
    "This MIB object indicates the number of times
    to repeat the cadence cycle represented by the
    on/off durations (refer to the MIB objects
    pktcSigDevToneFreqOnDuration and
    pktcSigDevToneFreqOffDuration).

    Setting this object may result in a tone duration that is
    longer or shorter than the overall signal duration
    specified by the time out (TO) object for the
```

corresponding tone type. If the value of this MIB
Object indicates a longer duration than that
specified by the TO, the latter overrules
the former,
and the desired tone duration will be truncated according
to the TO.

However, if the repeat count results in a shorter
tone duration than the signal duration specified by
the TO, the tone duration defined by the repeat count
takes precedence over the TO and will end the signal
event. In this case, the TO represents a time not to
be exceeded for the signal. It is recommended, to
ensure proper telephony signaling, that the TO
duration setting should always be longer than the
desired repeat count-time duration. A value of zero
means the tone sequence is to be played once but not
repeated."
::={ pktcSigDevMultiFreqToneEntry 11}

pktcSigDevCidDelayAfterLR OBJECT-TYPE
SYNTAX Unsigned32 (300..800)
UNITS "Milliseconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"This object specifies the delay between
the end of the
Line Reversal and the start of the FSK or DTMF signal.
This MIB object is used only when pktcSigDevCidMode is
set to a value of 'lrETS'. This timing has a range of
300 to 800 ms.

The following table defines the default values
for this MIB object, depending on the signal type
(pktcSigDevCidMode), and MUST be followed:

Value of pktcSigDevCidMode	Default value
duringringingETS	any value (not used)
dtAsETS	any value (not used)
rpAsETS	any value (not used)
lrAsETS	any value (not used)
lrETS	400

An attempt to set this object while the value of

pktcSigDevCidMode is not set to a value of 'lrETS' will
result in an 'inconsistentValue' error.

The value of this
MIB object MUST NOT persist across MTA
reboots."
DEFVAL { 400 }
::= {pktcSigDevObjects 34 }

pktcSigDevCidDtmfStartCode OBJECT-TYPE
SYNTAX DtmfCode
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"This object identifies optional start codes used when
the MIB object pktcSigDevCidSigProtocol is set
to a value of 'dtmf(2)'.

Different countries define different caller id signaling
codes to support caller identification. When Dual-Tone
Multi-Frequency (DTMF) is used, the caller id digits are
preceded by a 'start code' digit, followed by the digit
transmission sequence <S1>...<Sn> (where Sx represents
the digits 0-9), and terminated by the 'end code' digit.

For example,
<A><S1>...<Sn> <D><S1>...<Sn> <B><S1>...<Sn> <C>.
The start code for calling number delivery may be DTMF

'A' or 'D'. The start code for redirecting a number may be
DTMF 'D'. The DTMF code 'B' may be sent by the network
as a start code for the transfer of information values,
through which special events can be indicated to the
user. In some countries, the '*' or '#' may be used
instead of 'A', 'B', 'C', or 'D'.

The value of this MIB object MUST NOT persist across MTA

reboots."
REFERENCE
"ETSI-EN-300-659-1 specification"
DEFVAL {dtmfcodeA}
::= { pktcSigDevObjects 35 }

pktcSigDevCidDtmfEndCode OBJECT-TYPE
SYNTAX DtmfCode

```
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
       "This object identifies optional end codes used when the
        pktcSigDevCidSigProtocol is set to a value of
        'dtmf(2)'.

        Different countries define different caller id signaling
        protocols to support caller
identification.  When
        Dual-Tone Multi-Frequency (DTMF) is used, the caller id
        digits are preceded by a 'start code' digit, followed by
        the digit transmission sequence <S1>...<Sn> (where Sx
        represents the digits 0-9), and terminated by the 'end
        code' digit.

        For example,
          <A><S1>...<Sn> <D><S1>...<Sn> <B><S1>...<Sn> <C>.

        The DTMF code 'C' may be sent by the network as an
        end code for the transfer of information values, through
        which special events can be indicated to the user.  In
        some countries, the '*' or '#' may be used instead of
        'A', 'B', 'C', or 'D'.

        The value of this MIB object MUST NOT persist across MTA
        reboots."
    REFERENCE
       "ETSI-EN-300-659-1 specification"
    DEFVAL {dtmfcodeC}
::= { pktcSigDevObjects 36 }

pktcSigDevVmwiSigProtocol  OBJECT-TYPE
    SYNTAX       PktcSubscriberSideSigProtocol
     MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
       "This object identifies the subscriber line protocol used
        for signaling the information on Visual Message Waiting
        Indicator (VMWI).  Different countries define different
        VMWI signaling protocols to support VMWI service.



        Frequency shift keying (FSK) is most commonly used.
        DTMF is an alternative.

        The value of this MIB object MUST NOT persist across MTA
```

```
        reboots."
    DEFVAL { fsk }
::= { pktcSigDevObjects 37 }

pktcSigDevVmwiDelayAfterLR    OBJECT-TYPE
    SYNTAX      Unsigned32 (0|300..800)
    UNITS       "Milliseconds"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "This object specifies the delay between the end of the
        Line Reversal and the start of the FSK or DTMF signal.
        This object is only used when pktcSigDevVmwiMode
is
        set to a value of 'lrETS'.
        This timing has a range of 300 to 800 ms.

        The following table defines the default values
        for this MIB object, depending on the signal type
        (pktcSigDevVmwiMode), and MUST be followed:

        Value of pktcSigDevVmwiMode      Default value

        duringringingETS                 any value  (not used)
        dtAsETS                          any value  (not used)
        rpAsETS                          any value  (not used)
        lrAsETS                          any value  (not used)
        lrETS                            400

        An attempt to set this object while the value of
        pktcSigDevVmwiMode is not 'lrETS' will result in an
        'inconsistentValue' error.

        The value of this MIB object MUST NOT persist across MTA
        reboots."

    DEFVAL {400}
        ::= {pktcSigDevObjects 38 }

pktcSigDevVmwiDtmfStartCode
OBJECT-TYPE
    SYNTAX      DtmfCode
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "This object identifies optional start codes used when
```

```
        the pktcSigDevVmwiSigProtocol is set to a value of
        'dtmf(2)'.  Different countries define different On Hook
        Data Transmission Protocol signaling codes to support
        VMWI.

        When Dual-Tone Multi-Frequency (DTMF) is used, the VMWI
        digits are preceded by a 'start code' digit, followed
        by the digit transmission sequence <S1>...<Sn> (where
        Sx represents the digits 0-9), and terminated by the 'end
        code' digit.

        For example,
          <A><S1>...<Sn> <D><S1>...<Sn> <B><S1>...<Sn> <C>.

        The start code for redirecting VMWI may be DTMF 'D'
        The DTMF code 'B' may be sent by the network as a start
        code for the transfer of information values, through
         which special events can be indicated to the user.  In
        some countries, the '*' or '#' may be used instead of
        'A', 'B', 'C', or 'D'.

        The value of this MIB object MUST NOT persist across MTA
        reboots."
    REFERENCE
        "ETSI-EN-300-659-1 specification"
    DEFVAL {dtmfcodeA}
::= { pktcSigDevObjects 39 }

pktcSigDevVmwiDtmfEndCode OBJECT-TYPE
    SYNTAX       DtmfCode
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
       "This object identifies an optional end code used when the
        pktcSigDevVmwiSigProtocol is set to a value of
        'dtmf(2)'.  Different countries define different on-hook
        Data Transmission Protocol signaling codes to support
        VMWI.

        When Dual-Tone Multi-Frequency (DTMF) is used, the VMWI
        digits are preceded by a 'start code' digit, followed
        by the digit transmission sequence
<S1>...<Sn> (where
        Sx represents the digits 0-9), and terminated by the 'end
        code' digit.

        For example,
```

<A><S1>...<Sn> <D><S1>...<Sn> <B><S1>...<Sn> <C>.

The DTMF code 'C' may be sent by the network as an end code
for the transfer of information values, through which
special events can be indicated to the user. In some
countries, the '*' or '#' may be used instead of 'A',
'B', 'C', or 'D'.

The value of this MIB object MUST NOT persist across MTA
reboots."
REFERENCE
"ETSI-EN-300-659-1 specification"
DEFVAL {dtmfcodeC}
::= { pktcSigDevObjects 40 }

pktcSigDevrpAsDtsDuration OBJECT-TYPE
SYNTAX Unsigned32 (0|200..500)
UNITS "Milliseconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
" This object specifies the duration of the rpASDTS ring

pulse prior to the start of the transmission of the
FSK or DTMF containing the caller id information. It is
only used when pktcSigDevCidMode is set to a value of
'rpAsETS'.

The following table defines the default values
for this MIB object, depending on the signal type
(pktcSigDevCidMode), and MUST be followed:

Value of pktcSigDevCidMode Default value

duringringingETS any value (not used)
dtAsETS any value (not used)
rpAsETS 250
lrAsETS any value (not used)
lrETS any value (not used)

An attempt to set this object while the value of
pktcSigDevCidMode is not 'rpAsETS' will result in
an 'inconsistentValue' error.

The value of this MIB object MUST NOT persist

```
 across MTA
         reboots."
     REFERENCE
        "ETSI-EN-300-659-1 Specification and Belgacom
         BGC_D_48_9811_30_09_EDOC version 3.3"
     DEFVAL { 250 }
     ::= {pktcSigDevObjects 41 }




--
-- The Endpoint Config Table is used to define attributes that
-- are specific to connection EndPoints.
--

pktcSigEndPntConfigTable  OBJECT-TYPE
   SYNTAX        SEQUENCE OF PktcSigEndPntConfigEntry
   MAX-ACCESS    not-accessible
   STATUS        current
   DESCRIPTION
      " This table describes the information pertaining to each
        endpoint of the MTA.  All entries in this table represent
        the provisioned endpoints provisioned with the information
        required by the MTA to maintain the NCS protocol
        communication with the CMS.  Each endpoint can be assigned
        to its own CMS.  If the specific endpoint does not have
        the corresponding CMS information in this table, the
        endpoint is considered as not
 provisioned with voice
        services.  Objects in this table do not persist across
        MTA reboots."
  ::=  { pktcSigEndPntConfigObjects 1 }

pktcSigEndPntConfigEntry  OBJECT-TYPE
   SYNTAX        PktcSigEndPntConfigEntry
   MAX-ACCESS    not-accessible
   STATUS        current
   DESCRIPTION
      "Each entry in the pktcSigEndPntConfigTable represents
       required signaling parameters for the specific endpoint
       provisioned with voice services.  The conceptual rows MUST
       NOT persist across MTA reboots."
   INDEX { ifIndex }
   ::= { pktcSigEndPntConfigTable 1 }

PktcSigEndPntConfigEntry  ::= SEQUENCE {
   pktcSigEndPntConfigCallAgentId            SnmpAdminString,
```

```
  pktcSigEndPntConfigCallAgentUdpPort       InetPortNumber,
  pktcSigEndPntConfigPartialDialTO          Unsigned32,
  pktcSigEndPntConfigCriticalDialTO         Unsigned32,
  pktcSigEndPntConfigBusyToneTO             Unsigned32,
  pktcSigEndPntConfigDialToneTO
    Unsigned32,
  pktcSigEndPntConfigMessageWaitingTO       Unsigned32,
  pktcSigEndPntConfigOffHookWarnToneTO      Unsigned32,
  pktcSigEndPntConfigRingingTO              Unsigned32,
  pktcSigEndPntConfigRingBackTO             Unsigned32,
  pktcSigEndPntConfigReorderToneTO          Unsigned32,
  pktcSigEndPntConfigStutterDialToneTO      Unsigned32,



  pktcSigEndPntConfigTSMax                  Unsigned32,
  pktcSigEndPntConfigMax1                   Unsigned32,
  pktcSigEndPntConfigMax2                   Unsigned32,
  pktcSigEndPntConfigMax1QEnable            TruthValue,
  pktcSigEndPntConfigMax2QEnable            TruthValue,
  pktcSigEndPntConfigMWD                    Unsigned32,
  pktcSigEndPntConfigTdinit                 Unsigned32,
  pktcSigEndPntConfigTdmin                  Unsigned32,
  pktcSigEndPntConfigTdmax                  Unsigned32,
  pktcSigEndPntConfigRtoMax                 Unsigned32,
  pktcSigEndPntConfigRtoInit
        Unsigned32,
  pktcSigEndPntConfigLongDurationKeepAlive  Unsigned32,
  pktcSigEndPntConfigThist                  Unsigned32,
  pktcSigEndPntConfigStatus                 RowStatus,
  pktcSigEndPntConfigCallWaitingMaxRep      Unsigned32,
  pktcSigEndPntConfigCallWaitingDelay       Unsigned32,
  pktcSigEndPntStatusCallIpAddressType      InetAddressType,
  pktcSigEndPntStatusCallIpAddress          InetAddress,
  pktcSigEndPntStatusError                  INTEGER,
  pktcSigEndPntConfigMinHookFlash           Unsigned32,
  pktcSigEndPntConfigMaxHookFlash           Unsigned32,
  pktcSigEndPntConfigPulseDialInterdigitTime Unsigned32,
  pktcSigEndPntConfigPulseDialMinMakeTime   Unsigned32,
  pktcSigEndPntConfigPulseDialMaxMakeTime   Unsigned32,
  pktcSigEndPntConfigPulseDialMinBreakTime  Unsigned32,
  pktcSigEndPntConfigPulseDialMaxBreakTime  Unsigned32
  }

pktcSigEndPntConfigCallAgentId    OBJECT-TYPE
  SYNTAX     SnmpAdminString(SIZE
(3..255))
  MAX-ACCESS  read-create
```

```
  STATUS      current
  DESCRIPTION
      " This object contains a string indicating the call agent
        name (e.g., ca@example.com).  The call agent name, after
        the character '@', MUST be a fully qualified domain name
        (FQDN) and MUST have a corresponding pktcMtaDevCmsFqdn
        entry in the pktcMtaDevCmsTable.  The object
        pktcMtaDevCmsFqdn is defined in the PacketCable MIBMTA
        Specification.  For each particular endpoint, the MTA MUST
        use the current value of this object to communicate with
        the corresponding CMS.  The MTA MUST update this object
        with the value of the 'Notified Entity' parameter of the
        NCS message.  Because of the high importance of this object
        to the ability of the MTA to maintain reliable NCS
        communication with the CMS, it is highly recommended not
        to change this object's value using SNMP during normal

      operation."



  ::= {  pktcSigEndPntConfigEntry 1 }

pktcSigEndPntConfigCallAgentUdpPort    OBJECT-TYPE
  SYNTAX      InetPortNumber (1025..65535)
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      " This object contains the current value of the User
        Datagram Protocol (UDP) receive port on which the
        call agent will receive NCS from the endpoint.
        For each particular endpoint, the MTA MUST use the current
        value of this object to communicate with the corresponding
        CMS.  The MTA MUST update this object with the value of the
        'Notified Entity' parameter of the NCS message.  If the
        Notified Entity parameter does not contain a CallAgent
        port, the MTA MUST update this object with the default
        value of 2727.  Because of the high importance of this
        object to the ability of the MTA to maintain reliable NCS
        communication with the CMS, it is highly recommended
 not
        to change this object's value using SNMP during normal
        operation."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL    { 2727 }
  ::= { pktcSigEndPntConfigEntry 2 }
```

```
pktcSigEndPntConfigPartialDialTO     OBJECT-TYPE
  SYNTAX       Unsigned32
  UNITS        "seconds"
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
     "This object contains the value of the partial dial
      time out.
      The time out (TO) elements are intended to limit the time a
      tone or frequency is generated.  When this MIB object is set
      to a value of '0', the MTA MUST NOT generate the
      corresponding frequency or tone, regardless of the
      definitions pertaining to frequency, tone duration, or
      cadence."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 16 }
  ::= { pktcSigEndPntConfigEntry 3 }

pktcSigEndPntConfigCriticalDialTO     OBJECT-TYPE
  SYNTAX       Unsigned32
  UNITS
       "seconds"



  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
     "This object contains the value of the critical
      dial time out.
      The time out (TO) elements are intended to limit the time a
      tone or frequency is generated.  When this MIB object is set
      to a value of '0', the MTA MUST NOT generate the
      corresponding frequency or tone, regardless of the
      definitions pertaining to frequency, tone duration, or
      cadence."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 4 }
  ::= { pktcSigEndPntConfigEntry 4 }

pktcSigEndPntConfigBusyToneTO     OBJECT-TYPE
  SYNTAX       Unsigned32
  UNITS        "seconds"
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
```

```
      " This object contains the default time out value for busy
        tone.  The MTA MUST NOT update this object with the
        value provided in the NCS message (if present).  If
        the
 value of the object is modified by the SNMP Management
        Station, the MTA MUST use the new value as a default only
        for a new signal requested by the NCS message.
        The time out (TO) elements are intended to limit the time
        a tone or frequency is generated.  When this MIB object is
        set to a value of '0', the MTA MUST NOT generate the
        corresponding frequency or tone, regardless of the
        definitions pertaining to frequency, tone duration, or
        cadence."
    REFERENCE
       "PacketCable NCS Specification"
    DEFVAL    { 30 }
    ::= { pktcSigEndPntConfigEntry 5 }

pktcSigEndPntConfigDialToneTO     OBJECT-TYPE
    SYNTAX       Unsigned32
    UNITS        "seconds"
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
       " This object contains the default time out value for dial
        tone.  The MTA MUST NOT update this object with the
        value provided in the NCS message (if present).
 If



        the value of the object is modified by the SNMP Management
        Station, the MTA MUST use the new value as a default only
        for a new signal requested by the NCS message.
        The time out (TO) elements are intended to limit the time
        a tone or frequency is generated.  When this MIB object is
        set to a value of '0', the MTA MUST NOT generate the
        corresponding frequency or tone, regardless of the
        definitions pertaining to frequency, tone duration, or
        cadence."
    REFERENCE
       "PacketCable NCS Specification"
    DEFVAL    { 16 }
    ::= { pktcSigEndPntConfigEntry 6 }

pktcSigEndPntConfigMessageWaitingTO     OBJECT-TYPE
    SYNTAX       Unsigned32
    UNITS        "seconds"
```

```
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
     " This object contains the default time out value for message
       waiting indicator.  The MTA MUST NOT update this object
       with the value
 provided in the NCS message (if
       present).  If the value of the object is modified by the
       SNMP Manager application, the MTA MUST use the new value
       as a default only for a new signal requested by the NCS
       message.
       The time out (TO) elements are intended to limit the time
       a tone or frequency is generated.  When this MIB object is
       set to a value of '0', the MTA MUST NOT generate the
       corresponding frequency or tone, regardless of the
       definitions pertaining to frequency, tone duration, or
       cadence."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL    { 16 }
  ::= { pktcSigEndPntConfigEntry 7 }

pktcSigEndPntConfigOffHookWarnToneTO     OBJECT-TYPE
  SYNTAX       Unsigned32
  UNITS        "seconds"
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
     " This object contains the default time out value for the
       off-hook warning tone.  The MTA MUST
 NOT update this object
       with the value provided in the NCS message (if present).  If
       the value of the object is modified by the SNMP Manager



       application, the MTA MUST use the new value as a default
       only for a new signal requested by the NCS message.  The
       time out (TO) elements are intended to limit the time a tone
       or frequency is generated.  When this MIB object is set to a
       value of '0', the MTA MUST NOT generate the corresponding
       frequency or tone, regardless of the definitions pertaining
       to frequency, tone duration, or cadence."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 0 }
  ::= { pktcSigEndPntConfigEntry 8 }
```

```
pktcSigEndPntConfigRingingTO     OBJECT-TYPE
  SYNTAX       Unsigned32
  UNITS        "seconds"
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
     " This object contains the default time out value for
       ringing.  The MTA
 MUST NOT update this object with the
       value provided in the NCS message (if present).  If
       the value of the object is modified by the SNMP Management
       Station, the MTA MUST use the new value as a default only
       for a new signal requested by the NCS message.
       The time out (TO) elements are intended to limit the time
       a tone or frequency is generated.  When this MIB object is
       set to a value of '0', the MTA MUST NOT generate the
       corresponding frequency or tone, regardless of the
       definitions pertaining to frequency, tone duration, or
       cadence."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL    { 180 }
  ::= { pktcSigEndPntConfigEntry 9 }

pktcSigEndPntConfigRingBackTO     OBJECT-TYPE
  SYNTAX       Unsigned32
  UNITS        "seconds"
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
     " This object contains the default time out value for ring

     back.  The MTA MUST NOT update this object with the
       value provided in the NCS message (if present).  If
       the value of the object is modified by the SNMP Management
       Station, the MTA MUST use the new value as a default only
       for a new signal requested by the NCS message.
       The time out (TO) elements are intended to limit the time




       a tone or frequency is generated.  When this MIB object is
       set to a value of '0', the MTA MUST NOT generate the
       corresponding frequency or tone, regardless of the
       definitions pertaining to frequency, tone duration, or
       cadence."
  REFERENCE
     "PacketCable NCS Specification"
```

```
  DEFVAL    { 180 }
  ::= { pktcSigEndPntConfigEntry 10 }

pktcSigEndPntConfigReorderToneTO     OBJECT-TYPE
  SYNTAX       Unsigned32
  UNITS        "seconds"
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
     " This object contains the default time
 out value for reorder
       tone.  The MTA MUST NOT update this object with the
       value provided in the NCS message (if present).  If
       the value of the object is modified by the SNMP Management
       Station, the MTA MUST use the new value as a default only
       for a new signal requested by the NCS message.
       The time out (TO) elements are intended to limit the time
       a tone or frequency is generated.  When this MIB object is
       set to a value of '0', the MTA MUST NOT generate the
       corresponding frequency or tone, regardless of the
       definitions pertaining to frequency, tone duration, or
       cadence."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL    { 30 }
  ::= { pktcSigEndPntConfigEntry 11 }

pktcSigEndPntConfigStutterDialToneTO     OBJECT-TYPE
  SYNTAX       Unsigned32
  UNITS        "seconds"
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
     " This object
 contains the default time out value for stutter
       dial tone.  The MTA MUST NOT update this object with the
       value provided in the NCS message (if present).  If
       the value of the object is modified by the SNMP Management
       Station, the MTA MUST use the new value as a default only
       for a new signal requested by the NCS message.
       The time out (TO) elements are intended to limit the time
       a tone or frequency is generated.  When this MIB object is
       set to a value of '0', the MTA MUST NOT generate the



       corresponding frequency or tone, regardless of the
       definitions pertaining to frequency, tone duration, or
```

```
        cadence."
    REFERENCE
        "PacketCable NCS Specification"
    DEFVAL    { 16 }
    ::= { pktcSigEndPntConfigEntry 12 }

pktcSigEndPntConfigTSMax     OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This MIB object
 is used as part of an NCS
        retransmission algorithm.  Prior to any retransmission,
        the MTA must check to make sure that the time elapsed
        since the sending of the initial datagram does not
        exceed the value specified by this MIB object.  If more
        than Tsmax time has elapsed, then the retransmissions
        MUST cease.

        Refer to the MIB object pktcSigEndPntConfigThist for
        information on when the endpoint becomes disconnected."
    REFERENCE
      "PacketCable NCS Specification"
    DEFVAL { 20 }
    ::= { pktcSigEndPntConfigEntry 13 }

pktcSigEndPntConfigMax1     OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "This object contains the suspicious error threshold for
       signaling messages.  The pktcSigEndPntConfigMax1 object
       indicates the retransmission threshold at which the MTA MAY
       actively query the domain
 name server (DNS) in order to
       detect the possible change of call agent interfaces."
    REFERENCE
      "PacketCable NCS Specification"
    DEFVAL { 5 }
    ::= { pktcSigEndPntConfigEntry 14 }

pktcSigEndPntConfigMax2     OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
```

```
        "This object contains the disconnect error threshold for
        signaling messages.  The pktcSigEndPntConfigMax2 object
        indicates the retransmission threshold at which the MTA
        SHOULD contact the DNS one more time to see if any other
        interfaces to the call agent have become available."
    REFERENCE
        "PacketCable NCS Specification"
    DEFVAL { 7 }
    ::= { pktcSigEndPntConfigEntry 15 }

pktcSigEndPntConfigMax1QEnable     OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This object enables/disables the Max1 domain name server
        (DNS)
 query operation when the pktcSigEndPntConfigMax1
        threshold has been reached.
        A value of true(1) indicates enabling, and a value of
        false(2) indicates disabling."
    DEFVAL { true }
    ::= { pktcSigEndPntConfigEntry 16 }

pktcSigEndPntConfigMax2QEnable     OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This object enables/disables the Max2 domain name server
        (DNS) query operation when the pktcSigEndPntConfigMax2
        threshold has been reached.
        A value of true(1) indicates enabling, and a value of
        false(2) indicates disabling."
    DEFVAL { true }
    ::= { pktcSigEndPntConfigEntry 17 }

pktcSigEndPntConfigMWD     OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "seconds"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Maximum Waiting Delay (MWD) contains the maximum number of
        seconds an MTA waits, after powering
```

```
 on, before initiating
       the restart procedure with the call agent."
   REFERENCE
      "PacketCable NCS Specification"
   DEFVAL { 600 }



   ::= { pktcSigEndPntConfigEntry 18 }

pktcSigEndPntConfigTdinit     OBJECT-TYPE
   SYNTAX      Unsigned32
   UNITS       "seconds"
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "This MIB object represents the 'disconnected' initial
       waiting delay within the context of an MTA's 'disconnected
       procedure'.  The 'disconnected procedure' is initiated when
       an endpoint becomes 'disconnected' while attempting to
       communicate with a call agent.

       The 'disconnected timer' associated with the 'disconnected
       Procedure' is initialized to a random value, uniformly
       distributed between zero and the value contained in this
       MIB object.

       For more information on the usage of this timer, please
       refer to the PacketCable NCS Specification."
    REFERENCE
      "PacketCable NCS Specification"
   DEFVAL { 15 }
   ::= { pktcSigEndPntConfigEntry 19 }

pktcSigEndPntConfigTdmin     OBJECT-TYPE
   SYNTAX      Unsigned32
   UNITS       "seconds"
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
         "This MIB object represents the 'disconnected' minimum
          waiting delay within the context of an MTA's
          'disconnected procedure', specifically when local user
          activity is detected.
          The 'disconnected procedure' is initiated when
          an endpoint becomes 'disconnected' while attempting to
          communicate with a call agent.
          For more information on the usage of this timer, please
```

refer to the PacketCable NCS Specification."
REFERENCE
"PacketCable NCS Specification"
DEFVAL { 15 }
::= { pktcSigEndPntConfigEntry 20 }

pktcSigEndPntConfigTdmax OBJECT-TYPE
SYNTAX Unsigned32

UNITS
"seconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION
" This object contains the maximum number of seconds the MTA
waits, after a disconnect, before initiating the
disconnected procedure with the call agent.
"
REFERENCE
"PacketCable NCS Specification"
DEFVAL { 600 }
::= { pktcSigEndPntConfigEntry 21 }

pktcSigEndPntConfigRtoMax OBJECT-TYPE
SYNTAX Unsigned32
UNITS "seconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This object specifies the maximum number of seconds the MTA
waits for a response to an NCS message before initiating
a retransmission."
REFERENCE
"PacketCable NCS Specification"
DEFVAL { 4 }
::= { pktcSigEndPntConfigEntry 22 }

pktcSigEndPntConfigRtoInit OBJECT-TYPE
SYNTAX Unsigned32
UNITS "milliseconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION

" This object contains the initial number of seconds for the
retransmission timer."

```
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 200 }
  ::= { pktcSigEndPntConfigEntry 23 }

pktcSigEndPntConfigLongDurationKeepAlive     OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "minutes"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " Specifies a time out value, in minutes, for sending long
       duration call notification messages."



  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 60 }
  ::= { pktcSigEndPntConfigEntry 24 }

pktcSigEndPntConfigThist  OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "seconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " Time out period, in seconds, before no response is declared."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 30 }
  ::= { pktcSigEndPntConfigEntry 25 }

pktcSigEndPntConfigStatus     OBJECT-TYPE
   SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object contains the Row Status associated with the
       pktcSigEndPntConfigTable.  There are no restrictions or
       dependencies amidst the columnar objects before this
       row can be activated or for modifications of the
       columnar objects when this object is set to a
       value of 'active(1)."
  ::= { pktcSigEndPntConfigEntry 26 }

pktcSigEndPntConfigCallWaitingMaxRep     OBJECT-TYPE
  SYNTAX      Unsigned32 (0..10)
```

```
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object contains the default value of the maximum
       number of repetitions of the Call Waiting tone that the
       MTA will play from a single CMS request.  The MTA MUST NOT
       update this object with the information provided in the
       NCS message (if present).  If the value of the object is
       modified by the SNMP
 Manager application, the MTA MUST use
       the new value as a default only for a new signal
       requested by the NCS message."
  DEFVAL    { 1 }
  ::= { pktcSigEndPntConfigEntry 27 }

pktcSigEndPntConfigCallWaitingDelay     OBJECT-TYPE
  SYNTAX       Unsigned32 (1..100)



  UNITS        "seconds"
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
     " This object contains the delay between repetitions of the
       Call Waiting tone that the MTA will play from a single CMS
       request."
  DEFVAL    { 10 }
  ::= { pktcSigEndPntConfigEntry 28 }

pktcSigEndPntStatusCallIpAddressType  OBJECT-TYPE
  SYNTAX      InetAddressType
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object contains the type of Internet address contained
       in the MIB object 'pktcSigEndPntStatusCallIpAddress'.

       Since pktcSigEndPntStatusCallIpAddress is expected to
       contain an IP address, a value of dns(16)
 is disallowed."

  ::= { pktcSigEndPntConfigEntry 29 }

pktcSigEndPntStatusCallIpAddress  OBJECT-TYPE
  SYNTAX      InetAddress
  MAX-ACCESS  read-only
  STATUS      current
```

```
  DESCRIPTION
    " This MIB object contains the chosen IP address of the CMS
      currently being used for the corresponding endpoint.

      The device determines the IP address by using DNS to
      resolve the IP address of the CMS from the FQDN stored in
      the MIB object 'pktcSigEndPntConfigCallAgentId'.  The
      processes are outlined in the PacketCable NCS and Security
      specifications, and MUST be followed by the MTA.

      The IP address type contained in this MIB object is
      indicated by pktcSigEndPntStatusCallIpAddressType."
  REFERENCE
     "PacketCable NCS Specification;
      PacketCable Security specification, [PKT-SP-SEC]."
::= { pktcSigEndPntConfigEntry 30 }

pktcSigEndPntStatusError  OBJECT-TYPE
  SYNTAX INTEGER {
          operational
 (1),
          noSecurityAssociation (2),



          disconnected (3)
         }
  MAX-ACCESS   read-only
  STATUS  current
  DESCRIPTION
    " This object contains the error status for this interface.
      The operational status indicates that all operations
      necessary to put the line in service have occurred, and the
      CMS has acknowledged the Restart In Progress (RSIP)
      message successfully.  If pktcMtaDevCmsIpsecCtrl is enabled
      for the associated call agent, the noSecurityAssociation
      status indicates that no Security Association (SA) yet
      exists for this endpoint.  If pktcMtaDevCmsIpsecCtrl is
      disabled for the associated call agent, the
      noSecurityAssociation status is not applicable and should
      not be used by the MTA.  The disconnected status indicates
      one of the following two:
      If pktcMtaDevCmsIpsecCtrl is disabled, then no security
      association
 is involved with this endpoint.  The NCS
      signaling software is in process of establishing the NCS
      signaling link via an RSIP exchange.
      Otherwise, when pktcMtaDevCmsIpsecCtrl is enabled,
```

```
        security Association has been established, and the NCS
        signaling software is in process of establishing the NCS
        signaling link via an RSIP exchange."
    ::= { pktcSigEndPntConfigEntry 31 }

pktcSigEndPntConfigMinHookFlash    OBJECT-TYPE
    SYNTAX      Unsigned32 (20..1550)
    UNITS       "Milliseconds"
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
       " This is the minimum time a line needs to be on-hook for a
        valid hook flash.  The value of this object MUST be
        greater than the value of
        pktcSigEndPntConfigPulseDialMaxBreakTime.  The value of
        pktcSigEndPntConfigMinHookFlash MUST be less than
        pktcSigEndPntConfigMaxHookFlash.  This object MUST only be
        set via the
   MTA configuration during the provisioning
        process.
          Furthermore, given the possibility for the 'pulse dial'
          and 'hook flash' to overlap, the value of this object
          MUST be greater than the value contained by the MIB
          Object 'pktcSigEndPntConfigPulseDialMaxMakeTime'."
    DEFVAL { 300 }
    ::= { pktcSigEndPntConfigEntry 32 }



pktcSigEndPntConfigMaxHookFlash    OBJECT-TYPE
    SYNTAX      Unsigned32 (20..1550)
    UNITS       "Milliseconds"
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
       " This is the maximum time a line needs to be on-hook for a
        valid hook flash.  The value of
        pktcSigEndPntConfigMaxHookFlash MUST be greater than
        pktcSigEndPntConfigMinHookFlash.  This object MUST only be
        set via the MTA configuration during the provisioning
        process."
    DEFVAL { 800 }
    ::= { pktcSigEndPntConfigEntry 33 }

pktcSigEndPntConfigPulseDialInterdigitTime
     OBJECT-TYPE
    SYNTAX      Unsigned32 (100..1500)
```

```
  UNITS       "Milliseconds"
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
     " This is the pulse dial inter-digit time out.  This object
       MUST only be set via the MTA configuration during the
       provisioning process."
  DEFVAL { 100 }
  ::= { pktcSigEndPntConfigEntry 34 }

pktcSigEndPntConfigPulseDialMinMakeTime    OBJECT-TYPE
  SYNTAX       Unsigned32 (20..200)
  UNITS       "Milliseconds"
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
     " This is the minimum make pulse width for the dial pulse.
       The value of pktcSigEndPntConfigPulseDialMinMakeTime MUST
       be less than pktcSigEndPntConfigPulseDialMaxMakeTime.  This
       object MUST only be set via the MTA configuration during
       the provisioning process."
  DEFVAL { 25 }
  ::= { pktcSigEndPntConfigEntry 35 }

pktcSigEndPntConfigPulseDialMaxMakeTime    OBJECT-TYPE
   SYNTAX       Unsigned32 (20..200)
  UNITS       "Milliseconds"
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
     " This is the maximum make pulse width for the dial pulse.



       The value of pktcSigEndPntConfigPulseDialMaxMakeTime MUST
       be greater than pktcSigEndPntConfigPulseDialMinMakeTime.
       This object MUST only be provided via the configuration
       file during the provisioning process.
       Furthermore, given the possibility for the 'pulse dial'
       and 'hook flash' to overlap, the value of this object MUST
       be less than the value contained by the MIB object
       pktcSigEndPntConfigMinHookFlash."
  DEFVAL { 55 }
  ::= { pktcSigEndPntConfigEntry 36 }

pktcSigEndPntConfigPulseDialMinBreakTime    OBJECT-TYPE
  SYNTAX       Unsigned32 (20..200)
  UNITS       "Milliseconds"
```

```
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
      " This is the minimum break pulse width
 for the dial pulse.
        The value of pktcSigEndPntConfigPulseDialMinBreakTime MUST
        be less than pktcSigEndPntConfigPulseDialMaxBreakTime.
        This object must only be provided via the configuration
        file during the provisioning process."
  DEFVAL { 45 }
  ::= { pktcSigEndPntConfigEntry 37 }

pktcSigEndPntConfigPulseDialMaxBreakTime    OBJECT-TYPE
  SYNTAX       Unsigned32 (20..200)
  UNITS        "Milliseconds"
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
      " This is the maximum break pulse width for the dial pulse.
        The value of pktcSigEndPntConfigPulseDialMaxBreakTime MUST
        be greater than pktcSigEndPntConfigPulseDialMinBreakTime.
        This object MUST only be provided via the configuration
        file during the provisioning process."
  DEFVAL { 75 }
  ::= { pktcSigEndPntConfigEntry 38 }

--
-- notification group is for future extension.
--
pktcSigNotification  OBJECT IDENTIFIER ::= {
 pktcIetfSigMib 0 }
pktcSigConformance   OBJECT IDENTIFIER ::= { pktcIetfSigMib 2 }
pktcSigCompliances   OBJECT IDENTIFIER ::= { pktcSigConformance 1 }
pktcSigGroups        OBJECT IDENTIFIER ::= { pktcSigConformance 2 }

--




-- compliance statements
--

pktcSigBasicCompliance  MODULE-COMPLIANCE
  STATUS     current
  DESCRIPTION
      " The compliance statement for MTAs that implement
        NCS signaling."
```

```
MODULE  -- pktcIetfSigMib

---
-- Unconditionally mandatory groups for all MTAs
---

MANDATORY-GROUPS {
  pktcSigDeviceGroup,
  pktcSigEndpointGroup
}
---
-- Conditionally mandatory groups for MTAs
---

GROUP pktcInternationalGroup
  DESCRIPTION
     " This group is mandatory only for MTAs implementing
       international telephony features."

GROUP pktcLLinePackageGroup
  DESCRIPTION
     " This group is mandatory only for MTAs implementing the L
       line package."

GROUP pktcELinePackageGroup
  DESCRIPTION
     " This group is mandatory only
 for MTAs implementing the E
       Line Package."
  ::={ pktcSigCompliances 1 }

pktcSigDeviceGroup  OBJECT-GROUP
  OBJECTS {
  pktcSigDevCodecMax,
  pktcSigDevEchoCancellation,
  pktcSigDevSilenceSuppression,
  pktcSigDevR0Cadence,
  pktcSigDevR1Cadence,
  pktcSigDevR2Cadence,
  pktcSigDevR3Cadence,



  pktcSigDevR4Cadence,
  pktcSigDevR5Cadence,
  pktcSigDevR6Cadence,
  pktcSigDevR7Cadence,
  pktcSigDevRgCadence,
```

```
    pktcSigDevRsCadence,
    pktcSigDefCallSigDscp,
    pktcSigDefMediaStreamDscp,
    pktcSigDevVmwiMode,
    pktcSigCapabilityType,
    pktcSigCapabilityVersion,
    pktcSigCapabilityVendorExt,
    pktcSigDefNcsReceiveUdpPort
    }
    STATUS current
    DESCRIPTION
        "Group of MIB objects containing signaling configuration
         information that is applicable per-device."
    ::= { pktcSigGroups 1 }

pktcSigEndpointGroup  OBJECT-GROUP
    OBJECTS {
    pktcSigEndPntConfigCallAgentId,
    pktcSigEndPntConfigCallAgentUdpPort,

    pktcSigEndPntConfigPartialDialTO,
    pktcSigEndPntConfigCriticalDialTO,
    pktcSigEndPntConfigBusyToneTO,
    pktcSigEndPntConfigDialToneTO,
    pktcSigEndPntConfigMessageWaitingTO,
    pktcSigEndPntConfigOffHookWarnToneTO,
    pktcSigEndPntConfigRingingTO,
    pktcSigEndPntConfigRingBackTO,
    pktcSigEndPntConfigReorderToneTO,
    pktcSigEndPntConfigStutterDialToneTO,
    pktcSigEndPntConfigTSMax,
    pktcSigEndPntConfigMax1,
    pktcSigEndPntConfigMax2,
    pktcSigEndPntConfigMax1QEnable,
    pktcSigEndPntConfigMax2QEnable,
    pktcSigEndPntConfigMWD,
    pktcSigEndPntConfigTdinit,
    pktcSigEndPntConfigTdmin,
    pktcSigEndPntConfigTdmax,
    pktcSigEndPntConfigRtoMax,
    pktcSigEndPntConfigRtoInit,
    pktcSigEndPntConfigLongDurationKeepAlive,
    pktcSigEndPntConfigThist,
    pktcSigEndPntConfigStatus,



    pktcSigEndPntConfigCallWaitingMaxRep,
```

```
    pktcSigEndPntConfigCallWaitingDelay,
    pktcSigEndPntStatusCallIpAddressType,
    pktcSigEndPntStatusCallIpAddress,
    pktcSigEndPntStatusError
     }
    STATUS current
    DESCRIPTION
        "Group of MIB objects containing signaling configuration
         information that is applicable per-endpoint."
    ::= { pktcSigGroups 2 }

  pktcInternationalGroup    OBJECT-GROUP
    OBJECTS {
    pktcSigEndPntConfigMinHookFlash,
    pktcSigEndPntConfigMaxHookFlash,
    pktcSigEndPntConfigPulseDialInterdigitTime,
    pktcSigEndPntConfigPulseDialMinMakeTime,
    pktcSigEndPntConfigPulseDialMaxMakeTime,
    pktcSigEndPntConfigPulseDialMinBreakTime,
    pktcSigEndPntConfigPulseDialMaxBreakTime,
    pktcSigDevRingCadence,
    pktcSigDevCidSigProtocol,
    pktcSigDevCidDelayAfterLR,
    pktcSigDevCidDtmfStartCode,
    pktcSigDevCidDtmfEndCode,
    pktcSigDevVmwiSigProtocol,
    pktcSigDevVmwiDelayAfterLR,
    pktcSigDevVmwiDtmfStartCode,
    pktcSigDevVmwiDtmfEndCode,
    pktcSigDevrpAsDtsDuration,
    pktcSigDevCidMode,
    pktcSigDevCidAfterRing,
    pktcSigDevCidAfterDTAS,
    pktcSigDevCidAfterRPAS,
    pktcSigDevRingAfterCID,
     pktcSigDevCidDTASAfterLR,
    pktcSigDevVmwiMode,
    pktcSigDevVmwiAfterDTAS,
    pktcSigDevVmwiAfterRPAS,
    pktcSigDevVmwiDTASAfterLR,
    pktcSigPowerRingFrequency,
    pktcSigPulseSignalFrequency,
    pktcSigPulseSignalDbLevel,
    pktcSigPulseSignalDuration,
    pktcSigPulseSignalPulseInterval,
    pktcSigPulseSignalRepeatCount,
    pktcSigDevToneDbLevel,
```

```
    pktcSigDevToneFreqCounter,
    pktcSigDevToneWholeToneRepeatCount,
    pktcSigDevToneSteady,
    pktcSigDevToneFirstFreqValue,
    pktcSigDevToneSecondFreqValue,
    pktcSigDevToneThirdFreqValue,
    pktcSigDevToneFourthFreqValue,
    pktcSigDevToneFreqMode,
    pktcSigDevToneFreqAmpModePrtg,
    pktcSigDevToneFreqOnDuration,
    pktcSigDevToneFreqOffDuration,
    pktcSigDevToneFreqRepeatCount
    }
    STATUS current
    DESCRIPTION
        " Group of objects that extend the behavior of existing
        objects to support operations in the widest possible set
        of international marketplaces.
    Note that many of these
        objects represent a superset of behaviors described in
        other objects within this MIB module."
    ::= { pktcSigGroups 3 }

pktcLLinePackageGroup  OBJECT-GROUP
    OBJECTS {
    pktcSigDevR0Cadence,
    pktcSigDevR1Cadence,
    pktcSigDevR2Cadence,
    pktcSigDevR3Cadence,
    pktcSigDevR4Cadence,
    pktcSigDevR5Cadence,
    pktcSigDevR6Cadence,
    pktcSigDevR7Cadence,
    pktcSigDevRgCadence,
    pktcSigDevRsCadence
    }
    STATUS current
    DESCRIPTION
    "Group of Objects to support the L line package."
    ::= { pktcSigGroups 4 }

pktcELinePackageGroup  OBJECT-GROUP
    OBJECTS {
    pktcSigDevR0Cadence,
    pktcSigDevR1Cadence,
    pktcSigDevR2Cadence,
```

pktcSigDevR3Cadence,
pktcSigDevR4Cadence,
pktcSigDevR5Cadence,

pktcSigDevR6Cadence,
pktcSigDevR7Cadence,
pktcSigDevRgCadence,
pktcSigDevRsCadence,
pktcSigPulseSignalFrequency,
pktcSigPulseSignalDbLevel,
pktcSigPulseSignalDuration,
pktcSigPulseSignalPulseInterval,
pktcSigPulseSignalRepeatCount,
pktcSigDevRingCadence
}
STATUS current
DESCRIPTION
"Group of Objects to support the E line package."
::= { pktcSigGroups 5 }

END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/PKTC-IETF-SIG-MIB

1.447 json 20090211

1.447.1 Available under license :

Apache Geronimo Bundles: json-20090211
Copyright 2003-2010 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work,

excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions

of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

==========
== JSON License ==
==========

http://www.json.org/license.html

Copyright (c) 2002 JSON.org

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons
to whom the Software is furnished
to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

The Software shall be used for Good, not Evil.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.448 yang-parser-api 0.8.4-Beryllium-SR4

1.448.1 Available under license :

Found license 'Eclipse Public License 1.0' in 'Copyright (c) 2013 Cisco Systems, Inc. and others. All rights reserved. This program and the accompanying materials are made available under the terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2013 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'

1.449 javassist 3.17.1-GA

1.449.1 Available under license :

Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean
the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name)
to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written

communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual
or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by
combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and
You must cause any modified files to carry prominent notices stating that You changed the files; and
You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that
such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any
Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims
asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.450 commons-http-client 3.0.1

1.450.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/auth/MalformedChallengeException.java,v 1.6 2004/05/13 04:02:00 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*

* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/MalformedChallengeException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/util/HttpURLConnection.java,v 1.15 2004/04/18 23:51:38 jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing

permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/util/HttpURLConnection.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/auth/HttpAuthenticator.java,v 1.19 2004/10/06 17:32:04 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):

* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/HttpAuthenticator.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/MethodRetryHandler.java,v 1.5 2004/07/05 22:46:58 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/MethodRetryHandler.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/auth/InvalidCredentialsException.java,v 1.4 2004/05/13 04:02:00 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*

* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/InvalidCredentialsException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/methods/HeadMethod.java,v 1.29 2004/06/13 20:22:19 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing

permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/HeadMethod.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/protocol/SecureProtocolSocketFactory.java,v 1.6 2004/04/18 23:51:38 jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific
 language governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):

* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/protocol/SecureProtocolSocketFactory.java
No license file was found, but licenses were detected in source scan.

/*
* $HeadURL: https://svn.apache.org/repos/asf/jakarta/commons/proper/httpclient/branches/HTTPCLIENT_3_0_BRANCH/src/java/org/apache/commons/httpclient/util/LangUtils.java $
* $Revision: 354155 $
* $Date: 2005-12-05 15:18:10 -0500 (Mon, 05 Dec 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations
 under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/util/LangUtils.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/methods/multipart/ByteArrayPartSource.java,v 1.7 2004/04/18 23:51:37 jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==

```
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific
 language governing permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/multipart/ByteArrayPartSource.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/HttpConnection.java,v 1.107 2005/01/14 21:30:59 olegk Exp $
* $Revision: 327792 $
* $Date: 2005-10-23 09:34:28 -0400 (Sun, 23 Oct 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
```

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpConnection.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/methods/multipart/StringPart.java,v 1.11 2004/04/18 23:51:37 jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/multipart/StringPart.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/cookie/CookieSpecBase.java,v 1.28 2004/11/06 19:15:42 mbecke Exp $
* $Revision: 190485 $
* $Date: 2005-06-13 15:04:56 -0400 (Mon, 13 Jun 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/cookie/CookieSpecBase.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/methods/multipart/Part.java,v 1.16 2005/01/14 21:16:40 olegk Exp $
* $Revision: 332125 $
* $Date: 2005-11-09 14:41:40 -0500 (Wed, 09 Nov 2005) $
*

```
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/multipart/Part.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/HttpRecoverableException.java,v 1.15 2004/07/05
22:46:58 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
```

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpRecoverableException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/ConnectionPoolTimeoutException.java,v 1.1 2004/07/05 22:46:58 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/ConnectionPoolTimeoutException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/auth/AuthState.java,v 1.3 2004/11/02 19:39:16 olegk Exp $
* $Revision: 290260 $
* $Date: 2005-09-19 16:37:48 -0400 (Mon, 19 Sep 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions
 and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/AuthState.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/HeaderElement.java,v 1.23 2004/05/13 04:03:25 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*

```
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions
 and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HeaderElement.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/util/DateParseException.java,v 1.5 2004/11/06
19:15:42 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
```

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/util/DateParseException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/NTCredentials.java,v 1.10 2004/04/18 23:51:35 jsdever Exp $
* $Revision: 326707 $
* $Date: 2005-10-19 16:51:46 -0400 (Wed, 19 Oct 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/NTCredentials.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made
 by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/TraceMethod.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/auth/AuthChallengeParser.java,v 1.10 2004/05/13
04:02:00 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
```

```
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language
 governing permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/AuthChallengeParser.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/methods/multipart/PartSource.java,v 1.6 2004/04/18
23:51:37 jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language
```

governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/multipart/PartSource.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/CircularRedirectException.java,v 1.1 2005/01/14 19:40:39 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):

* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/CircularRedirectException.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/HeaderGroup.java,v 1.8 2004/05/13 04:03:25 mbecke
Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 2003-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions
 and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HeaderGroup.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/HttpConnectionManager.java,v 1.24 2004/07/05
22:46:58 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
```

* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpConnectionManager.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/auth/DigestScheme.java,v 1.22 2004/12/30 11:01:27 oglueck Exp $
* $Revision: 368699 $
* $Date: 2006-01-13 07:24:45 -0500 (Fri, 13 Jan 2006) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing

permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/DigestScheme.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/UsernamePasswordCredentials.java,v 1.14 2004/04/18 23:51:35 jsdever Exp $
* $Revision: 326707 $
* $Date: 2005-10-19 16:51:46 -0400 (Wed, 19 Oct 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):

* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/UsernamePasswordCredentials.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/auth/BasicScheme.java,v 1.17 2004/05/13 04:02:00 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/BasicScheme.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/ConnectMethod.java,v 1.29 2004/06/24 21:39:52 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*

* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions
 and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/ConnectMethod.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/NoHttpResponseException.java,v 1.1 2004/07/05 22:46:58 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing

permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/NoHttpResponseException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/util/ExceptionUtil.java,v 1.5 2004/10/19 18:09:46 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):

* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/util/ExceptionUtil.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/protocol/ControllerThreadSocketFactory.java,v 1.2 2004/04/18 23:51:38 jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific
 language governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/protocol/ControllerThreadSocketFactory.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/Credentials.java,v 1.9 2004/04/18 23:51:34 jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==

```
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions
 and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/Credentials.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/auth/AuthChallengeProcessor.java,v 1.2 2004/04/18
23:51:36 jsdever Exp $
* $Revision: 290260 $
* $Date: 2005-09-19 16:37:48 -0400 (Mon, 19 Sep 2005) $
*
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
```

* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/AuthChallengeProcessor.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/HttpURL.java,v 1.18 2004/09/30 17:26:41 oglueck Exp $
* $Revision: 358634 $
* $Date: 2005-12-22 16:23:15 -0500 (Thu, 22 Dec 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions
 and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpURL.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/methods/EntityEnclosingMethod.java,v 1.39
2004/07/03 14:27:03 olegk Exp $
* $Revision: 161963 $
* $Date: 2005-04-19 16:25:06 -0400 (Tue, 19 Apr 2005) $
*
* ====================================================================
*
*  Copyright 2003-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language
 governing permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/EntityEnclosingMethod.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/methods/RequestEntity.java,v 1.4 2004/05/17
21:46:03 olegk Exp $
* $Revision: 161963 $
* $Date: 2005-04-19 16:25:06 -0400 (Tue, 19 Apr 2005) $
*
* ====================================================================
```

```
*
*  Copyright 2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/RequestEntity.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/WireLogOutputStream.java,v 1.7 2004/06/24 21:39:52
mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
```

* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/WireLogOutputStream.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/NameValuePair.java,v 1.17 2004/04/18 23:51:35
jsdever Exp $
* $Revision: 157457 $
* $Date: 2005-03-14 15:23:16 -0500 (Mon, 14 Mar 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/NameValuePair.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/cookie/CookieSpec.java,v 1.11 2004/09/14 20:11:31 olegk Exp $
* $Revision: 356822 $
* $Date: 2005-12-14 13:08:35 -0500 (Wed, 14 Dec 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/cookie/CookieSpec.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/ContentLengthInputStream.java,v 1.12 2004/10/04 22:05:44 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==

```
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/ContentLengthInputStream.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/HttpClient.java,v 1.98 2004/10/07 16:14:15 olegk Exp
$
* $Revision: 354155 $
* $Date: 2005-12-05 15:18:10 -0500 (Mon, 05 Dec 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
```

* See the License for the specific language governing permissions
 and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpClient.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/cookie/MalformedCookieException.java,v 1.8 2004/05/13 04:02:00 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/cookie/MalformedCookieException.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/Cookie.java,v 1.44 2004/06/05 16:49:20 olegk Exp $
* $Revision: 157457 $
* $Date: 2005-03-14 15:23:16 -0500 (Mon, 14 Mar 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions
 and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/Cookie.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/RedirectException.java,v 1.2 2004/04/18 23:51:35
jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
```

```
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/RedirectException.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/ConnectTimeoutException.java,v 1.5 2004/07/05
22:46:58 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
```

permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/ConnectTimeoutException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/ChunkedInputStream.java,v 1.24 2004/10/10 15:18:55 olegk Exp $
* $Revision: 291181 $
* $Date: 2005-09-23 14:13:25 -0400 (Fri, 23 Sep 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):

* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/ChunkedInputStream.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/Header.java,v 1.17 2004/09/15 20:42:17 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions
 and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/Header.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/methods/StringRequestEntity.java,v 1.3 2004/07/03
14:27:03 olegk Exp $
* $Revision: 356822 $
* $Date: 2005-12-14 13:08:35 -0500 (Wed, 14 Dec 2005) $
*
* ====================================================================
*
*  Copyright 2004 The Apache Software Foundation
```

*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
* [Additional notices, if required by prior licensing conditions]
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/StringRequestEntity.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/MultiThreadedHttpConnectionManager.java,v 1.47 2004/12/21 11:27:55 olegk Exp $
* $Revision: 366716 $
* $Date: 2006-01-07 08:04:58 -0500 (Sat, 07 Jan 2006) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific
 language governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-
jar/org/apache/commons/httpclient/MultiThreadedHttpConnectionManager.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/params/HttpConnectionManagerParams.java,v 1.9
2004/09/13 16:25:20 olegk Exp $
* $Revision: 354155 $
* $Date: 2005-12-05 15:18:10 -0500 (Mon, 05 Dec 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/params/HttpConnectionManagerParams.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/URI.java,v 1.47 2004/05/13 04:03:25 mbecke Exp $
* $Revision: 372560 $
* $Date: 2006-01-26 11:07:06 -0500 (Thu, 26 Jan 2006) $
*
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions
 and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/URI.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/HttpMethod.java,v 1.43 2004/10/07 16:14:15 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
```

```
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions
 and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpMethod.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/methods/multipart/MultipartRequestEntity.java,v 1.1
2004/10/06 03:39:59 mbecke Exp $
* $Revision: 327791 $
* $Date: 2005-10-23 09:27:39 -0400 (Sun, 23 Oct 2005) $
*
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
```

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific
 language governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-
jar/org/apache/commons/httpclient/methods/multipart/MultipartRequestEntity.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/auth/AuthenticationException.java,v 1.6 2004/05/13
04:02:00 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*

*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/AuthenticationException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/methods/multipart/PartBase.java,v 1.5 2004/04/18 23:51:37 jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/multipart/PartBase.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/HttpClientError.java,v 1.4 2004/05/13 04:03:25 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $

```
*
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpClientError.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/HttpParser.java,v 1.13 2005/01/11 13:57:06 oglueck
Exp $
* $Revision: 179411 $
* $Date: 2005-06-01 16:04:58 -0400 (Wed, 01 Jun 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
```

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions
 and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpParser.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/URIException.java,v 1.12 2004/09/30 18:53:20 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions
 and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*

*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/URIException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/methods/multipart/FilePartSource.java,v 1.10 2004/04/18 23:51:37 jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific
 language governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/multipart/FilePartSource.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/ChunkedOutputStream.java,v 1.16 2004/05/13 04:03:25 mbecke Exp $
* $Revision: 220180 $
* $Date: 2005-07-21 16:29:45 -0400 (Thu, 21 Jul 2005) $

```
*
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/ChunkedOutputStream.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/util/EncodingUtil.java,v 1.8 2004/05/13 04:01:22
mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
```

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/util/EncodingUtil.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/methods/ExpectContinueMethod.java,v 1.13
2004/05/08 10:12:08 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2003-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*

*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/ExpectContinueMethod.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/protocol/DefaultProtocolSocketFactory.java,v 1.10 2004/05/13 04:01:22 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific
 language governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/protocol/DefaultProtocolSocketFactory.java
No license file was found, but licenses were detected in source scan.

/*
* $HeadURL: https://svn.apache.org/repos/asf/jakarta/commons/proper/httpclient/branches/HTTPCLIENT_3_0_BRANCH/src/java/org/apache/commons/httpclient/util/ParameterFormatter.java $
* $Revision: 178662 $

* $Date: 2005-05-26 14:21:14 -0400 (Thu, 26 May 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
 * limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/util/ParameterFormatter.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/ProxyHost.java,v 1.2 2005/01/14 21:16:40 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions
and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/ProxyHost.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/auth/NTLM.java,v 1.11 2004/05/13 04:02:00 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions
and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*

```
*/
/**
* Provides an implementation of the NTLM authentication protocol.
* <p>
* This class provides methods for generating authentication
* challenge responses for the NTLM authentication protocol.  The NTLM
* protocol is a proprietary Microsoft protocol and as such no RFC
* exists for it.  This class is based upon the reverse engineering
* efforts of a wide range of people.</p>
*
* <p>Please note that an implementation of JCE must be correctly installed and configured when
* using NTLM support.</p>
*
* <p>This class should not be used externally to HttpClient as it's API is specifically
* designed to work with HttpClient's use
 case, in particular it's connection management.</p>
*
* @author <a href="mailto:adrian@ephox.com">Adrian Sutton</a>
* @author <a href="mailto:jsdever@apache.org">Jeff Dever</a>
* @author <a href="mailto:mbowler@GargoyleSoftware.com">Mike Bowler</a>
*
* @version $Revision: 155418 $ $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
* @since 3.0
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/NTLM.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/util/IdleConnectionTimeoutThread.java,v 1.2
2004/05/13 02:40:36 mbecke Exp $
* $Revision: 354829 $
* $Date: 2005-12-07 14:05:13 -0500 (Wed, 07 Dec 2005) $
*
* ====================================================================
*
*  Copyright 2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
```

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/util/IdleConnectionTimeoutThread.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/util/TimeoutController.java,v 1.6 2004/04/18 23:51:38 jsdever Exp $
* $Revision: 291181 $
* $Date: 2005-09-23 14:13:25 -0400 (Fri, 23 Sep 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/util/TimeoutController.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/AutoCloseInputStream.java,v 1.9 2004/04/18 23:51:34
jsdever Exp $
* $Revision: 291181 $
* $Date: 2005-09-23 14:13:25 -0400 (Fri, 23 Sep 2005) $
*
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/AutoCloseInputStream.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/HttpState.java,v 1.38 2004/12/20 11:50:54 olegk Exp
$
* $Revision: 377704 $
* $Date: 2006-02-14 06:48:29 -0500 (Tue, 14 Feb 2006) $
*
```

```
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions
 and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpState.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/util/ParameterParser.java,v 1.5 2004/05/13 04:01:22
mbecke Exp $
* $Revision: 345737 $
* $Date: 2005-11-20 07:30:47 -0500 (Sun, 20 Nov 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
```

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/util/ParameterParser.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/auth/CredentialsProvider.java,v 1.6 2004/07/05 22:46:59 olegk Exp $
* $Revision: 357669 $
* $Date: 2005-12-19 04:19:10 -0500 (Mon, 19 Dec 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/CredentialsProvider.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/HttpMethodBase.java,v 1.222 2005/01/14 21:16:40 olegk Exp $
* $Revision: 345322 $
* $Date: 2005-11-17 15:20:08 -0500 (Thu, 17 Nov 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpMethodBase.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/util/IdleConnectionHandler.java,v 1.2 2004/05/13 02:40:36 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*

```
* ====================================================================
*
*  Copyright 2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/util/IdleConnectionHandler.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/HttpHost.java,v 1.3 2005/01/14 21:16:40 olegk Exp $
* $Revision: 157457 $
* $Date: 2005-03-14 15:23:16 -0500 (Mon, 14 Mar 2005) $
*
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
```

* See the License for the specific language governing permissions
and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpHost.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/protocol/ProtocolSocketFactory.java,v 1.10
2004/05/13 04:01:22 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/protocol/ProtocolSocketFactory.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/cookie/CookiePolicy.java,v 1.15 2004/09/14 20:11:31 olegk Exp $
* $Revision: 356822 $
* $Date: 2005-12-14 13:08:35 -0500 (Wed, 14 Dec 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/cookie/CookiePolicy.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/ResponseConsumedWatcher.java,v 1.5 2004/04/18 23:51:35 jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==

*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/ResponseConsumedWatcher.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/params/HttpParamsFactory.java,v 1.5 2004/05/13 04:01:22 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/params/HttpParamsFactory.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/HttpStatus.java,v 1.18 2004/05/02 11:21:13 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions
 and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpStatus.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/params/HostParams.java,v 1.5 2004/10/06 17:32:04 olegk Exp $
* $Revision: 224451 $
* $Date: 2005-07-23 06:23:59 -0400 (Sat, 23 Jul 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/params/HostParams.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/util/DateUtil.java,v 1.2 2004/12/24 20:36:13 olegk Exp $
* $Revision: 224451 $
* $Date: 2005-07-23 06:23:59 -0400 (Sat, 23 Jul 2005) $
*
* ==

```
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions
 and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/util/DateUtil.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/HttpMethodRetryHandler.java,v 1.2 2004/09/14
20:11:31 olegk Exp $
* $Revision: 224452 $
* $Date: 2005-07-23 06:33:39 -0400 (Sat, 23 Jul 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
```

* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpMethodRetryHandler.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/params/HttpConnectionParams.java,v 1.6 2004/09/15 20:32:21 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/params/HttpConnectionParams.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/protocol/ReflectionSocketFactory.java,v 1.4
2004/12/21 23:15:21 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language
 governing permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/protocol/ReflectionSocketFactory.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/methods/OptionsMethod.java,v 1.15 2004/04/18
23:51:37 jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
```

```
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/OptionsMethod.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/ProtocolException.java,v 1.4 2004/05/13 04:03:25
mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
```

* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/ProtocolException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/methods/InputStreamRequestEntity.java,v 1.4 2004/05/17 21:46:03 olegk Exp $
* $Revision: 224452 $
* $Date: 2005-07-23 06:33:39 -0400 (Sat, 23 Jul 2005) $
*
* ==
*
* Copyright 2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
* [Additional notices, if required by prior licensing conditions]
*

*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/InputStreamRequestEntity.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/auth/AuthScheme.java,v 1.12 2004/05/13 04:02:00 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/AuthScheme.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/HostConfiguration.java,v 1.23 2005/01/14 21:16:40 olegk Exp $
* $Revision: 354155 $
* $Date: 2005-12-05 15:18:10 -0500 (Mon, 05 Dec 2005) $

```
*
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HostConfiguration.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/cookie/NetscapeDraftSpec.java,v 1.11 2004/05/13
04:02:00 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
```

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/cookie/NetscapeDraftSpec.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/methods/multipart/FilePart.java,v 1.19 2004/04/18 23:51:37 jsdever Exp $
* $Revision: 354155 $
* $Date: 2005-12-05 15:18:10 -0500 (Mon, 05 Dec 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*

*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/multipart/FilePart.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/cookie/IgnoreCookiesSpec.java,v 1.6 2004/09/14 20:11:31 olegk Exp $
* $Revision: 179050 $
* $Date: 2005-05-30 08:22:06 -0400 (Mon, 30 May 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/cookie/IgnoreCookiesSpec.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/HttpConstants.java,v 1.15 2004/04/18 23:51:35 jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $

```
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpConstants.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/DefaultMethodRetryHandler.java,v 1.4 2004/07/05
22:46:58 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
```

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/DefaultMethodRetryHandler.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/cookie/RFC2109Spec.java,v 1.21 2004/06/05 16:49:20 olegk Exp $
* $Revision: 290666 $
* $Date: 2005-09-21 05:30:56 -0400 (Wed, 21 Sep 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*

```
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/cookie/RFC2109Spec.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/HttpException.java,v 1.19 2004/09/30 18:53:20 olegk
Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions
 and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpException.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/Wire.java,v 1.9 2004/06/24 21:39:52 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
```

```
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions
 and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/Wire.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/util/DateParser.java,v 1.11 2004/11/06 19:15:42
mbecke Exp $
* $Revision: 224451 $
* $Date: 2005-07-23 06:23:59 -0400 (Sat, 23 Jul 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
```

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/util/DateParser.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/methods/GetMethod.java,v 1.29 2004/06/13 20:22:19 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/GetMethod.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/auth/RFC2617Scheme.java,v 1.10 2004/05/13
04:02:00 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/RFC2617Scheme.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/params/HttpMethodParams.java,v 1.17 2004/10/06
17:32:04 olegk Exp $
* $Revision: 354155 $
* $Date: 2005-12-05 15:18:10 -0500 (Mon, 05 Dec 2005) $
*
```

```
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/params/HttpMethodParams.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/methods/PutMethod.java,v 1.26 2004/04/18 23:51:37
jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
```

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/PutMethod.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/DefaultHttpMethodRetryHandler.java,v 1.3 2004/12/20 11:47:46 olegk Exp $
* $Revision: 280621 $
* $Date: 2005-09-13 14:41:21 -0400 (Tue, 13 Sep 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/DefaultHttpMethodRetryHandler.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/HttpVersion.java,v 1.6 2004/12/20 19:52:50 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions
 and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpVersion.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/methods/DeleteMethod.java,v 1.14 2004/04/18 23:51:37 jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*

```
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/DeleteMethod.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/params/HttpClientParams.java,v 1.7 2004/05/13
04:01:22 mbecke Exp $
* $Revision: 354155 $
* $Date: 2005-12-05 15:18:10 -0500 (Mon, 05 Dec 2005) $
*
* ====================================================================
*
*  Copyright 1999-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
```

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/params/HttpClientParams.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/params/HttpParams.java,v 1.6 2004/05/13 04:01:22 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/params/HttpParams.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/auth/AuthChallengeException.java,v 1.2 2004/04/18 23:51:36 jsdever Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/AuthChallengeException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/protocol/SSLProtocolSocketFactory.java,v 1.10 2004/05/13 04:01:22 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*

```
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific
 language governing permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/protocol/SSLProtocolSocketFactory.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/auth/CredentialsNotAvailableException.java,v 1.4
2004/05/13 04:02:00 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
```

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific
 language governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-
jar/org/apache/commons/httpclient/auth/CredentialsNotAvailableException.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/protocol/Protocol.java,v 1.10 2004/04/18 23:51:38
jsdever Exp $
* $Revision: 157457 $
* $Date: 2005-03-14 15:23:16 -0500 (Mon, 14 Mar 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*

```
*/
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/protocol/Protocol.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/auth/NTLMScheme.java,v 1.21 2004/05/13 04:02:00
mbecke Exp $
* $Revision: 156690 $
* $Date: 2005-03-09 16:40:30 -0500 (Wed, 09 Mar 2005) $
*
* ====================================================================
*
*  Copyright 2002-2004 The Apache Software Foundation
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
/** An implementation of the Microsoft proprietary NTLM authentication scheme.  For a detailed
* explanation of the NTLM scheme please see <a href="http://davenport.sourceforge.net/ntlm.html">
* http://davenport.sourceforge.net/ntlm.html</a>.
*
* @author <a href="mailto:remm@apache.org">Remy Maucherat</a>
* @author Rodney Waldhoff
* @author <a href="mailto:jsdever@apache.org">Jeff Dever</a>
* @author Ortwin Gl???ck
* @author Sean C. Sullivan
* @author <a href="mailto:adrian@ephox.com">Adrian Sutton</a>
* @author <a href="mailto:mbowler@GargoyleSoftware.com">Mike Bowler</a>
```

* @author Oleg Kalnichevski
 */

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/NTLMScheme.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/params/DefaultHttpParamsFactory.java,v 1.16 2004/11/20 21:48:47 mbecke Exp $
* $Revision: 404762 $
* $Date: 2006-05-07 10:07:41 -0400 (Sun, 07 May 2006) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/params/DefaultHttpParamsFactory.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/util/URIUtil.java,v 1.27 2004/05/05 20:34:01 olegk Exp $
* $Revision: 155418 $

* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions
 and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/util/URIUtil.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/auth/AuthPolicy.java,v 1.6 2004/05/13 04:02:00 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*

```
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing
 permissions and
*  limitations under the License.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/
/**
* Authentication policy class. The Authentication policy provides corresponding
* authentication scheme interfrace for a given type of authorization challenge.
* <p>The following specifications are provided:
*  <ul>
*   <li><tt>Basic</tt>: Basic authentication scheme as defined in RFC2617
*          (considered inherently insecure, but most widely supported)
*   <li><tt>Digest</tt>: Digest authentication scheme as defined in RFC2617
*   <li><tt>NTLM</tt>: The NTLM scheme is a proprietary Microsoft Windows
*          Authentication protocol (considered to be the most secure among
*          currently supported authentication
 schemes)
*  </ul>
*
* @author <a href="mailto:oleg@ural.ru">Oleg Kalnichevski</a>
*
* @version $Revision: 155418 $
* @since 3.0
*/
/**
    * The NTLM scheme is a proprietary Microsoft Windows Authentication
    * protocol (considered to be the most secure among currently supported
    * authentication schemes).
    */
```

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/AuthPolicy.java
No license file was found, but licenses were detected in source scan.

```
/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-
commons//httpclient/src/java/org/apache/commons/httpclient/auth/AuthSchemeBase.java,v 1.7 2004/04/18 23:51:36
jsdever Exp $
* $Revision: 155418 $
```

* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/AuthSchemeBase.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/ProxyClient.java,v 1.5 2004/12/20 11:39:04 olegk Exp $
* $Revision: 354155 $
* $Date: 2005-12-05 15:18:10 -0500 (Mon, 05 Dec 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions
and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/ProxyClient.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/auth/AuthScope.java,v 1.2 2004/06/23 06:50:25 olegk Exp $
* $Revision: 354155 $
* $Date: 2005-12-05 15:18:10 -0500 (Mon, 05 Dec 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions
and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.

*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/AuthScope.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/HttpMethodDirector.java,v 1.34 2005/01/14 19:40:39 olegk Exp $
* $Revision: 366870 $
* $Date: 2006-01-07 13:12:55 -0500 (Sat, 07 Jan 2006) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpMethodDirector.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/WireLogInputStream.java,v 1.15 2004/06/24 21:39:52 mbecke Exp $
* $Revision: 155418 $

* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/WireLogInputStream.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/params/DefaultHttpParams.java,v 1.9 2004/12/21 23:15:21 olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/params/DefaultHttpParams.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/HttpsURL.java,v 1.11 2004/09/30 17:26:41 oglueck Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions
 and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.

*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/HttpsURL.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/StatusLine.java,v 1.14 2004/07/19 20:24:21 olegk Exp $
* $Revision: 354155 $
* $Date: 2005-12-05 15:18:10 -0500 (Mon, 05 Dec 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions
 and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/StatusLine.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/methods/PostMethod.java,v 1.58 2004/08/08 12:50:09 olegk Exp $
* $Revision: 155418 $

* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/PostMethod.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/methods/ByteArrayRequestEntity.java,v 1.3 2004/05/13 02:26:08 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
* [Additional notices, if required by prior licensing conditions]
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/ByteArrayRequestEntity.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/SimpleHttpConnectionManager.java,v 1.23 2004/10/16 22:40:08 mbecke Exp $
* $Revision: 329914 $
* $Date: 2005-10-31 16:24:47 -0500 (Mon, 31 Oct 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more

* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/SimpleHttpConnectionManager.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/methods/MultipartPostMethod.java,v 1.27 2004/10/06 03:39:59 mbecke Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 2002-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language
 governing permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/methods/MultipartPostMethod.java
No license file was found, but licenses were detected in source scan.

/*
* $Header: /home/jerenkrantz/tmp/commons/commons-convert/cvs/home/cvs/jakarta-commons//httpclient/src/java/org/apache/commons/httpclient/auth/HttpAuthRealm.java,v 1.9 2004/06/12 22:47:23

olegk Exp $
* $Revision: 155418 $
* $Date: 2005-02-26 08:01:52 -0500 (Sat, 26 Feb 2005) $
*
* ==
*
* Copyright 1999-2004 The Apache Software Foundation
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing
 permissions and
* limitations under the License.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*
*/

Found in path(s):
* /commons-httpclient-3-0-1-sources-3-jar/org/apache/commons/httpclient/auth/HttpAuthRealm.java

1.451 spring-security-taglibs 3.2.4.RELEASE

1.451.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-taglibs-3-2-4-release-sources-1-jar/org/springframework/security/taglibs/csrf/CsrfMetaTagsTag.java
* /spring-security-taglibs-3-2-4-release-sources-1-jar/org/springframework/security/taglibs/TagLibConfig.java
* /spring-security-taglibs-3-2-4-release-sources-1-jar/org/springframework/security/taglibs/csrf/CsrfInputTag.java
* /spring-security-taglibs-3-2-4-release-sources-1-jar/org/springframework/security/taglibs/csrf/AbstractCsrfTag.java
No license file was found, but licenses were detected in source scan.

/* Copyright 2004, 2005, 2006 Acegi Technology Pty Limited
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-taglibs-3-2-4-release-sources-1-jar/org/springframework/security/taglibs/velocity/Authz.java
* /spring-security-taglibs-3-2-4-release-sources-1-jar/org/springframework/security/taglibs/authz/AccessControlListTag.java
* /spring-security-taglibs-3-2-4-release-sources-1-jar/org/springframework/security/taglibs/velocity/AuthzImpl.java
* /spring-security-taglibs-3-2-4-release-sources-1-jar/org/springframework/security/taglibs/authz/AuthenticationTag.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2004-2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0

```
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-security-taglibs-3-2-4-release-sources-1-jar/org/springframework/security/taglibs/authz/AbstractAuthorizeTag.java

1.452 scala-library 2.10.4

1.452.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/**
*
* A `ClassTag[T]` stores the erased class of a given type `T`, accessible via the `runtimeClass`
* field. This is particularly useful for instantiating `Array`s whose element types are unknown
* at compile time.
*
* `ClassTag`s are a weaker special case of [[scala.reflect.api.TypeTags#TypeTag]]s, in that they
* wrap only the runtime class of a given type, whereas a `TypeTag` contains all static type
* information. That is, `ClassTag`s are constructed from knowing only the top-level class of a
* type, without necessarily knowing all of its argument types. This runtime information is enough
* for runtime `Array` creation.
*
* For example:
* {{{
*   scala> def mkArray[T : ClassTag](elems: T*) = Array[T](elems: _*)
*   mkArray: [T](elems: T*)(implicit evidence$1: scala.reflect.ClassTag[T])Array[T]
*
*   scala> mkArray(42, 13)
*   res0: Array[Int] = Array(42, 13)
*
*   scala> mkArray("Japan","Brazil","Germany")
 *   res1: Array[String] = Array(Japan, Brazil, Germany)
* }}}
*
* See [[scala.reflect.api.TypeTags]] for more examples, or the
* [[http://docs.scala-lang.org/overviews/reflection/typetags-manifests.html Reflection Guide: TypeTags]]
* for more details.
*
*/
```

Found in path(s):
* /scala-library-2-10-4-sources-3-jar/scala/reflect/ClassTag.scala
No license file was found, but licenses were detected in source scan.

```
/**
  * Latch used to implement waiting on a DefaultPromise's result.
  *
  * Inspired by: http://gee.cs.oswego.edu/cgi-
bin/viewcvs.cgi/jsr166/src/main/java/util/concurrent/locks/AbstractQueuedSynchronizer.java
  * Written by Dog Lea with assistance from members of JCP JSR-166
  * Expert Group and released to the public domain, as explained at
  * http://creativecommons.org/publicdomain/zero/1.0/
  */
```

Found in path(s):
* /scala-library-2-10-4-sources-3-jar/scala/concurrent/impl/Promise.scala
No license file was found, but licenses were detected in source scan.

```
/** This singleton object contains the `apply` and `unapplySeq` methods for
*  convenient construction and deconstruction. It is possible to deconstruct
*  any `Node` instance (that is not a `SpecialNode` or a `Group`) using the
*  syntax `case Elem(prefix, label, attribs, scope, child @ _*) => ...`
*
*  Copyright 2008 Google Inc. All Rights Reserved.
*  @author Burak Emir <bqe@google.com>
*/
```

Found in path(s):
* /scala-library-2-10-4-sources-3-jar/scala/xml/Elem.scala
No license file was found, but licenses were detected in source scan.

```
/**
* Copyright 2008 Google Inc. All Rights Reserved.
* @author Burak Emir <bqe@google.com>
*/
/** This class represents an attribute and at the same time a linked list of
*  attributes. Every instance of this class is either
*  - an instance of `UnprefixedAttribute key,value` or
*  - an instance of `PrefixedAttribute namespace_prefix,key,value` or
*  - `Null, the empty attribute list.
*
*  Namespace URIs are obtained by using the namespace scope of the element
*  owning this attribute (see `getNamespace`).
*
*  Copyright 2008 Google Inc. All Rights Reserved.
*  @author Burak Emir <bqe@google.com>
*/
```

Found in path(s):
* /scala-library-2-10-4-sources-3-jar/scala/xml/MetaData.scala

1.453 concepts 0.8.4-Beryllium-SR4

1.453.1 Available under license :

Found license 'Eclipse Public License 1.0' in 'Copyright (c) 2013 Cisco Systems, Inc. and others. All rights reserved. This program and the accompanying materials are made available under the terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2014 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2013 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'

1.454 spring-security-web 3.2.4.RELEASE

1.454.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/csrf/DefaultCsrfToken.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/bind/support/AuthenticationPrincipalArgumentResolver.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/csrf/CsrfException.java
*
 /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/access/DelegatingAccessDeniedHandler.java
* /spring-security-web-3-2-4-release-sources-3-

jar/org/springframework/security/web/csrf/HttpSessionCsrfTokenRepository.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/session/InvalidSessionAccessDeniedHandler.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/authentication/session/AbstractSessionFixationProtectionStrategy.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/csrf/MissingCsrfTokenException.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/authentication/session/SessionFixationProtectionEvent.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/context/AbstractSecurityWebApplicationInitializer.java
*
/spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/csrf/CsrfTokenRepository.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/header/HeaderWriter.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/csrf/InvalidCsrfTokenException.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/util/matcher/AnyRequestMatcher.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/header/writers/CacheControlHeadersWriter.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/header/writers/DelegatingRequestMatcherHeaderWriter.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/csrf/CsrfLogoutHandler.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/header/writers/frameoptions/XFrameOptionsHeaderWriter.java
*
/spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/servlet/support/csrf/CsrfRequestDataValueProcessor.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/csrf/CsrfAuthenticationStrategy.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/bind/annotation/AuthenticationPrincipal.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/authentication/session/ChangeSessionIdAuthenticationStrategy.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/header/writers/HstsHeaderWriter.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/authentication/session/SessionFixationProtectionStrategy.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/util/matcher/MediaTypeRequestMatcher.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/csrf/CsrfFilter.java
*
/spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/csrf/CsrfToken.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/header/writers/XXssProtectionHeaderWriter.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/header/writers/XContentTypeOptionsHeaderWriter.java

No license file was found, but licenses were detected in source scan.

/* Copyright 2004, 2005, 2006 Acegi Technology Pty Limited
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/authentication/rememberme/TokenBasedRememberMeServices.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/access/channel/ChannelProcessingFilter.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/PortResolverImpl.java
*
 /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/authentication/www/NonceExpiredException.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/authentication/WebAuthenticationDetailsSource.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/authentication/AbstractAuthenticationProcessingFilter.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/savedrequest/Enumerator.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/PortMapperImpl.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/authentication/WebAuthenticationDetails.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/access/ExceptionTranslationFilter.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/FilterChainProxy.java
*
 /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/util/UrlUtils.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/access/channel/ChannelDecisionManagerImpl.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/savedrequest/FastHttpDateFormat.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/savedrequest/SavedRequestAwareWrapper.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/access/intercept/FilterInvocationSecurityMetadataSource.java
* /spring-security-web-3-2-4-release-sources-3-

jar/org/springframework/security/web/authentication/switchuser/AuthenticationSwitchUserEvent.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/savedrequest/DefaultSavedRequest.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/access/DefaultWebInvocationPrivilegeEvaluator.java
*
/spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/access/intercept/FilterSecurityInterceptor.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/PortMapper.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/access/channel/ChannelEntryPoint.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/session/HttpSessionCreatedEvent.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/authentication/NullRememberMeServices.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/access/AccessDeniedHandler.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/authentication/www/BasicAuthenticationEntryPoint.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/authentication/switchuser/SwitchUserGrantedAuthority.java
*
/spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/session/ConcurrentSessionFilter.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/PortResolver.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/authentication/www/BasicAuthenticationFilter.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/access/intercept/DefaultFilterInvocationSecurityMetadataSource.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/access/AccessDeniedHandlerImpl.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/access/channel/SecureChannelProcessor.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/authentication/RememberMeServices.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/session/HttpSessionDestroyedEvent.java
*
/spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/access/channel/InsecureChannelProcessor.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/session/HttpSessionEventPublisher.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/AuthenticationEntryPoint.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/access/channel/RetryWithHttpsEntryPoint.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/authentication/AnonymousAuthenticationFilter.java

* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/access/channel/RetryWithHttpEntryPoint.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/servletapi/SecurityContextHolderAwareRequestWrapper.java
*
/spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/authentication/LoginUrlAuthenticationEntryPoint.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/authentication/www/DigestAuthenticationEntryPoint.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/access/WebInvocationPrivilegeEvaluator.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/authentication/UsernamePasswordAuthenticationFilter.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/authentication/switchuser/SwitchUserFilter.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/authentication/rememberme/RememberMeAuthenticationFilter.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/authentication/logout/LogoutHandler.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/access/channel/ChannelProcessor.java
*
/spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/access/channel/ChannelDecisionManager.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/authentication/logout/SecurityContextLogoutHandler.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/authentication/logout/LogoutFilter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not
* use this file except in compliance with the License. You may obtain a copy of
* the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /spring-security-web-3-2-4-release-sources-3-

jar/org/springframework/security/web/util/matcher/AndRequestMatcher.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/util/matcher/NegatedRequestMatcher.java
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/util/matcher/OrRequestMatcher.java
No license file was found, but licenses were detected in source scan.

/* Copyright 2004, 2005, 2006 2009 Acegi Technology Pty Limited
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/authentication/www/DigestAuthenticationFilter.java
No license file was found, but licenses were detected in source scan.

/*
R * Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-web-3-2-4-release-sources-3-
jar/org/springframework/security/web/authentication/session/CompositeSessionAuthenticationStrategy.java
No license file was found, but licenses were detected in source scan.

/* Copyright 2002-2012 the original author or authors.
* Copyright 2004, 2005, 2006 Acegi Technology Pty Limited
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/FilterInvocation.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/servletapi/SecurityContextHolderAwareRequestFilter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/header/HeaderWriterFilter.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/authentication/rememberme/JdbcTokenRepositoryImpl.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*

* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on
* an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the
* specific language governing permissions and limitations under the License.
*/

Found in path(s):
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/servletapi/HttpServletRequestFactory.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/util/AntPathRequestMatcher.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/context/request/async/SecurityContextCallableProcessingInterceptor.java
*
 /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/context/SaveContextOnUpdateOrErrorResponseWrapper.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/util/matcher/AntPathRequestMatcher.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/util/matcher/RegexRequestMatcher.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/servletapi/HttpServlet25RequestFactory.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/servletapi/HttpServlet3RequestFactory.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/context/request/async/WebAsyncManagerIntegrationFilter.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/util/RegexRequestMatcher.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/util/ELRequestMatcherContext.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/util/matcher/ELRequestMatcherContext.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/util/matcher/RequestHeaderRequestMatcher.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/util/RequestMatcherEditor.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/jaasapi/JaasApiIntegrationFilter.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/util/ELRequestMatcher.java
*
/spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/util/matcher/RequestMatcherEditor.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/util/matcher/ELRequestMatcher.java
* /spring-security-web-3-2-4-release-sources-3-jar/org/springframework/security/web/authentication/DelegatingAuthenticationEntryPoint.java

1.455 object-cache-api 0.8.4-Beryllium-SR4

1.455.1 Available under license :

Found license 'Eclipse Public License 1.0' in 'Copyright (c) 2014 Cisco Systems, Inc. and others. All rights reserved. This program and the accompanying materials are made available under the terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2014 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'

1.456 spring-security-core 3.2.4.RELEASE

1.456.1 Available under license :

No license file was found, but licenses were detected in source scan.

// Permission to use, copy, modify, and distribute this software for any
// purpose with or without fee is hereby granted, provided that the above
// copyright notice and this permission notice appear in all copies.

Found in path(s):
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/crypto/bcrypt/BCrypt.java
No license file was found, but licenses were detected in source scan.

```
/**
   *
   * @param authentication represents the user in question. Should not be null.
   * @param targetDomainObject the domain object for which permissions should be checked. May be null
   *         in which case implementations should return false, as the null condition can be checked explicitly
   *         in the expression.
   * @param permission a representation of the permission object as supplied by the expression system. Not null.
   * @return true if the permission is granted, false otherwise
   */
```

Found in path(s):
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/PermissionEvaluator.java
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/hierarchicalroles/UserDetailsWrapper.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/hierarchicalroles/CycleInRoleHierarchyException.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/hierarchicalroles/UserDetailsServiceWrapper.java
*
 /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/hierarchicalroles/RoleHierarchyImpl.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/hierarchicalroles/RoleHierarchy.java
No license file was found, but licenses were detected in source scan.

```
/* Copyright 2004, 2005, 2006 Acegi Technology Pty Limited
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/util/MethodInvocationUtils.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/util/SimpleMethodInvocation.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/AccessDeniedException.java
*
/spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/encoding/PasswordEncoder.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/intercept/RunAsUserToken.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/event/AbstractAuthenticationEvent.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/session/SessionRegistry.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/userdetails/UsernameNotFoundException.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/userdetails/User.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/userdetails/UserDetails.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/SecurityMetadataSource.java
*
/spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/dao/AbstractUserDetailsAuthenticationProvider.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/event/AbstractAuthenticationFailureEvent.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/jaas/LoginExceptionResolver.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/vote/AuthenticatedVoter.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/event/AuthenticationSuccessEvent.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/intercept/aopalliance/MethodSecurityMetadataSourceAdvisor.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/annotation/Secured.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/event/InteractiveAuthenticationSuccessEvent.java
*
/spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/userdetails/memory/UserMapEditor.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/rcp/RemoteAuthenticationManagerImpl.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/event/AuthenticationFailureProxyUntrustedEvent.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/ProviderNotFoundException.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/event/AuthenticationFailureDisabledEvent.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/jaas/JaasAuthenticationProvider.java

* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/AccessDecisionManager.java
*
/spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/AnonymousAuthenticationProvider.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/encoding/BaseDigestPasswordEncoder.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/context/ThreadLocalSecurityContextHolderStrategy.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/ProviderManager.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/dao/DaoAuthenticationProvider.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/annotation/SecuredAnnotationSecurityMetadataSource.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/userdetails/UserDetailsService.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/encoding/PlaintextPasswordEncoder.java
*
/spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/LockedException.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/event/AuthorizedEvent.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/ConfigAttribute.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/event/AuthenticationFailureBadCredentialsEvent.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/TestingAuthenticationToken.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/dao/ReflectionSaltSource.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/vote/RoleVoter.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/dao/SaltSource.java
*
/spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/method/MapBasedMethodSecurityMetadataSource.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/intercept/MethodInvocationPrivilegeEvaluator.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/session/SessionInformation.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/annotation/Jsr250MethodSecurityMetadataSource.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/rcp/RemoteAuthenticationManager.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/userdetails/UserCache.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/jaas/event/JaasAuthenticationFailedEvent.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/UsernamePasswordAuthenticationToken.java

*
/spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/TestingAuthenticationProvider.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/AuthenticationProvider.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/jaas/AuthorityGranter.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/AuthenticationServiceException.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/encoding/BasePasswordEncoder.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/context/SecurityContextHolder.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/intercept/RunAsManagerImpl.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/AnonymousAuthenticationToken.java
*
/spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/method/AbstractMethodSecurityMetadataSource.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/event/LoggerListener.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/Authentication.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/event/AuthenticationFailureProviderNotFoundEvent.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/encoding/LdapShaPasswordEncoder.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/vote/AffirmativeBased.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/context/SecurityContext.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/jaas/JaasAuthenticationToken.java
*
/spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/event/AbstractAuthorizationEvent.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/jaas/JaasPasswordCallbackHandler.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/intercept/RunAsImplAuthenticationProvider.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/intercept/aopalliance/MethodSecurityInterceptor.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/GrantedAuthority.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/intercept/RunAsManager.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/vote/UnanimousBased.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/RememberMeAuthenticationProvider.java
*
/spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/util/InMemoryResource.java
* /spring-security-core-3-2-4-release-sources-3-

jar/org/springframework/security/access/event/AuthorizationFailureEvent.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/AuthenticationTrustResolver.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/core/userdetails/cache/NullUserCache.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/access/event/AuthenticationCredentialsNotFoundEvent.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/access/intercept/InterceptorStatusToken.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/access/AuthorizationServiceException.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/util/FieldUtils.java
*
/spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/access/intercept/aspectj/AspectJCallback.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/SecurityConfig.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/jaas/JaasAuthenticationCallbackHandler.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/core/context/GlobalSecurityContextHolderStrategy.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/jaas/event/JaasAuthenticationSuccessEvent.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/event/AuthenticationFailureLockedEvent.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/vote/ConsensusBased.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/rcp/RemoteAuthenticationProvider.java
*
/spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/RememberMeAuthenticationToken.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/core/session/SessionRegistryImpl.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/rcp/RemoteAuthenticationException.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/access/vote/AbstractAccessDecisionManager.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/jaas/JaasNameCallbackHandler.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/core/userdetails/memory/InMemoryDaoImpl.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/vote/AbstractAclVoter.java
*
/spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/access/intercept/AbstractSecurityInterceptor.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/AuthenticationCredentialsNotFoundException.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/core/userdetails/memory/UserAttributeEditor.java

* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/jaas/event/JaasAuthenticationEvent.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/event/AuthenticationFailureServiceExceptionEvent.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/encoding/ShaPasswordEncoder.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/event/AuthenticationFailureCredentialsExpiredEvent.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/DisabledException.java
*
/spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/encoding/Md5PasswordEncoder.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/userdetails/memory/UserMap.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/session/SessionIdentifierAware.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/dao/SystemWideSaltSource.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/AccessDecisionVoter.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/AuthenticationTrustResolverImpl.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/intercept/NullRunAsManager.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/context/InheritableThreadLocalSecurityContextHolderStrategy.java
*
/spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/method/MethodSecurityMetadataSource.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/userdetails/jdbc/JdbcDaoImpl.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/AuthenticationManager.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/event/PublicInvocationEvent.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/jaas/SecurityContextLoginModule.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/ConfigAttributeEditor.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/userdetails/memory/UserAttribute.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/context/SecurityContextImpl.java
*
/spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/AccountExpiredException.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/intercept/AfterInvocationProviderManager.java
* /spring-security-core-3-2-4-release-sources-3-

jar/org/springframework/security/authentication/AbstractAuthenticationToken.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/jaas/DefaultLoginExceptionResolver.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/CredentialsExpiredException.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/InsufficientAuthenticationException.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/event/LoggerListener.java
*
/spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/jaas/JaasGrantedAuthority.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/BadCredentialsException.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/AuthenticationDetailsSource.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/AuthenticationException.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/core/authority/GrantedAuthorityImpl.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/core/SpringSecurityMessageSource.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/core/userdetails/cache/EhCacheBasedUserCache.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/core/context/SecurityContextHolderStrategy.java
*
/spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/access/AfterInvocationProvider.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/authentication/event/AuthenticationFailureExpiredEvent.java
No license file was found, but licenses were detected in source scan.

```
/**
* A token issued by {@link TokenService}.
*
* <p>
* It is important that the keys assigned to tokens are sufficiently randomised and secured that
* they can serve as identifying a unique user session. Implementations of {@link TokenService}
* are free to use encryption or encoding strategies of their choice. It is strongly recommended that
* keys are of sufficient length to balance safety against persistence cost. In relation to persistence
* cost, it is strongly recommended that returned keys are small enough for encoding in a cookie.
* </p>
*
* @author Ben Alex
* @since 2.0.1
*/
```

Found in path(s):

* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/token/Token.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/crypto/bcrypt/BCryptPasswordEncoder.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/crypto/password/PasswordEncoder.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/crypto/keygen/HexEncodingStringKeyGenerator.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/crypto/encrypt/Encryptors.java
*

/spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/crypto/password/Digester.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/crypto/keygen/KeyGenerators.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/crypto/encrypt/AesBytesEncryptor.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/crypto/keygen/SecureRandomBytesKeyGenerator.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/crypto/keygen/SharedKeyGenerator.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/crypto/encrypt/BytesEncryptor.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/crypto/password/StandardPasswordEncoder.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/crypto/util/EncodingUtils.java
*
/spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/crypto/keygen/StringKeyGenerator.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/crypto/password/NoOpPasswordEncoder.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/crypto/encrypt/CipherUtils.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/crypto/keygen/BytesKeyGenerator.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/crypto/encrypt/TextEncryptor.java
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/crypto/encrypt/HexEncodingTextEncryptor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2006-2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on
* an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the
* specific language governing permissions and limitations under the License.
*/

Found in path(s):
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/access/expression/method/MethodSecurityExpressionOperations.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.

```
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not
* use this file except in compliance with the License. You may obtain a copy of
* the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/
```

Found in path(s):
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/parameters/DefaultSecurityParameterNameDiscoverer.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/method/P.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/expression/method/ExpressionBasedAnnotationAttributeFactory.java
No license file was found, but licenses were detected in source scan.

```
/**
   * Determines if the {@link #getAuthentication()} has permission to access the target given the permission
   * @param target the target domain object to check permission on
   * @param permission the permission to check on the domain object (i.e. "read", "write", etc).
   * @return true if permission is granted to the {@link #getAuthentication()}, else false
   */
```

Found in path(s):
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/access/expression/SecurityExpressionOperations.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
```

*/

Found in path(s):
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/core/parameters/AnnotationParameterNameDiscoverer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on
* an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the
* specific language governing permissions and limitations under the License.
*/

Found in path(s):
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/concurrent/DelegatingSecurityContextExecutor.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/concurrent/DelegatingSecurityContextRunnable.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/concurrent/AbstractDelegatingSecurityContextSupport.java
*
 /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/concurrent/DelegatingSecurityContextExecutorService.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/task/DelegatingSecurityContextAsyncTaskExecutor.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/InternalAuthenticationServiceException.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/scheduling/DelegatingSecurityContextSchedulingTaskExecutor.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/task/DelegatingSecurityContextTaskExecutor.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/concurrent/DelegatingSecurityContextCallable.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/concurrent/DelegatingSecurityContextScheduledExecutorService.java
No license file was found, but licenses were detected in source scan.

/* Copyright 2004, 2005, 2006 Acegi Technology Pty Limited
*

```
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* Reviews the <code>Object</code> returned from a secure object invocation,
* being able to modify the <code>Object</code> or throw an {@link
* AccessDeniedException}.
* <p>
* Typically used to ensure the principal is permitted to access the domain
* object instance returned by a service layer bean.
 Can also be used to
* mutate the domain object instance so the principal is only able to access
* authorised bean properties or <code>Collection</code> elements.
* <p>
* Special consideration should be given to using an
* <code>AfterInvocationManager</code> on bean methods that modify a database.
* Typically an <code>AfterInvocationManager</code> is used with read-only
* methods, such as <code>public DomainObject getById(id)</code>. If used with
* methods that modify a database, a transaction manager should be used to
* ensure any <code>AccessDeniedException</code> will cause a rollback of the
* changes made by the transaction.
* </p>
*
* @author Ben Alex
*/

Found in path(s):
* /spring-security-core-3-2-4-release-sources-3-
jar/org/springframework/security/access/intercept/AfterInvocationManager.java
No license file was found, but licenses were detected in source scan.

/* Copyright 2004, 2005, 2006, 2007 Acegi Technology Pty Limited
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
```

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* Implementation of the MD4 message digest derived from the RSA Data Security, Inc, MD4 Message-Digest Algorithm.
*
* @author Alan Stewart
*/

Found in path(s):
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/encoding/Md4.java
No license file was found, but licenses were detected in source scan.

/* Copyright 2004, 2005, 2006, 2007 Acegi Technology Pty Limited
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/encoding/Md4PasswordEncoder.java
No license file was found, but licenses were detected in source scan.

/**
* Base64 encoder which is a reduced version of Robert Harder's public domain implementation (version 2.3.7).
* See http://iharder.net/base64 for more information.
* <p>
* For internal use only.
*
* @author Luke Taylor
* @since 3.0
*/

Found in path(s):

* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/crypto/codec/Base64.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/jaas/memory/InMemoryConfiguration.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/jaas/AbstractJaasAuthenticationProvider.java
* /spring-security-core-3-2-4-release-sources-3-jar/org/springframework/security/authentication/jaas/DefaultJaasAuthenticationProvider.java

1.457 yang-parser-impl 0.8.4-Beryllium-SR4

1.457.1 Available under license :

Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2016 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2014, 2015 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2015 Pantheon Technologies s.r.o. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in 'Copyright (c) 2013 Cisco Systems, Inc. and others. All rights reserved. This program and the accompanying materials are made available under the terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2014 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2013 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public

License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2015 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2013, 2015 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'

1.458 spring-security-config 3.2.4.RELEASE

1.458.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/method/GlobalMethodSecurityBeanDefinitionParser.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/configuration/ObjectPostProcessorConfiguration.java
*
 /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/authentication/configurers/GlobalAuthenticationConfigurerAdapter.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/web/configurers/JeeConfigurer.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/method/configuration/EnableGlobalMethodSecurity.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/configuration/AutowireBeanFactoryObjectPostProcessor.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/web/configurers/ChannelSecurityConfigurer.java
* /spring-security-config-3-2-4-release-sources-

jar/org/springframework/security/config/annotation/web/AbstractRequestMatcherRegistry.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/web/configuration/EnableWebSecurity.java
*
/spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/authentication/configurers/ldap/LdapAuthenticationProviderConfigurer.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/web/configurers/AbstractConfigAttributeRequestMatcherRegistry.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/web/configurers/LogoutConfigurer.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/method/configuration/GlobalMethodSecurityAspectJAutoProxyRegistrar.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/method/configuration/GlobalMethodSecuritySelector.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/http/RememberMeBeanDefinitionParser.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/web/configuration/AutowiredWebSecurityConfigurersIgnoreParents.java
*
/spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/authentication/ProviderManagerBuilder.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/SecurityConfigurerAdapter.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/web/builders/WebSecurity.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/web/configuration/WebSecurityConfiguration.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/AbstractSecurityBuilder.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/authentication/configurers/userdetails/DaoAuthenticationConfigurer.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/authentication/builders/AuthenticationManagerBuilder.java
*
/spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/authentication/configuration/AuthenticationConfiguration.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/web/configurers/AnonymousConfigurer.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/web/configurers/UrlAuthorizationConfigurer.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/annotation/web/configuration/WebSecurityConfigurerAdapter.java
* /spring-security-config-3-2-4-release-sources-

jar/org/springframework/security/config/annotation/web/servlet/configuration/EnableWebMvcSecurity.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/servlet/configuration/WebMvcSecurityConfiguration.java
*
/spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/RequestCacheConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/HttpSecurityBuilder.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/SecurityBuilder.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/HeadersConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/authentication/configurers/userdetails/AbstractDaoAuthenticationConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/authentication/configuration/EnableGlobalAuthentication.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/AbstractHttpConfigurer.java
*
/spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/AbstractInterceptUrlConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/SessionManagementConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/authentication/configurers/provisioning/InMemoryUserDetailsManagerConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/builders/HttpSecurity.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/openid/OpenIDLoginConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/http/HttpConfigurationBuilder.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/PermitAllSupport.java
*
/spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/SecurityContextConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/authentication/configurers/userdetails/UserDetailsAwareConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/SecurityConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/FormLoginConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/builders/FilterComparator.java
* /spring-security-config-3-2-4-release-sources-

jar/org/springframework/security/config/annotation/AlreadyBuiltException.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/PortMapperConfigurer.java
*
/spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/AbstractConfiguredSecurityBuilder.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/RememberMeConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/ExpressionUrlAuthorizationConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/authentication/configurers/userdetails/UserDetailsServiceConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/AbstractAuthenticationFilterConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/authentication/configurers/provisioning/JdbcUserDetailsManagerConfigurer.java
*
/spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/CsrfConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/WebSecurityConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/ServletApiConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/HttpBasicConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/ObjectPostProcessor.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/DefaultLoginPageConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/authentication/configurers/provisioning/UserDetailsManagerConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/X509Configurer.java
*
/spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/web/configurers/ExceptionHandlingConfigurer.java
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/annotation/method/configuration/GlobalMethodSecurityConfiguration.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with

* the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on
* an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the
* specific language governing permissions and limitations under the License.
*/

Found in path(s):
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/http/SecurityFilters.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2009-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-config-3-2-4-release-sources-
jar/org/springframework/security/config/SecurityNamespaceHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
*/

Found in path(s):
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/debug/SecurityDebugBeanFactoryPostProcessor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/http/CsrfBeanDefinitionParser.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/method/MethodConfigUtils.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/http/FormLoginBeanDefinitionParser.java
*
 /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/http/AuthenticationConfigBuilder.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/http/LogoutBeanDefinitionParser.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/http/HttpSecurityBeanDefinitionParser.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/http/WebConfigUtils.java
* /spring-security-config-3-2-4-release-sources-jar/org/springframework/security/config/http/HeadersBeanDefinitionParser.java

1.459 util 0.8.4-Beryllium-SR4

1.459.1 Available under license :

Found license 'Eclipse Public License 1.0' in 'Copyright (c) 2014 Cisco Systems, Inc. and others. All rights reserved. This program and the accompanying materials are made available under the terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2014 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2014 Robert Varga. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2013 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2015 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2014 Brocade Communications Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'

1.460 mibble-commercial-parser 2.9.3

1.460.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
RFC1213-MIB DEFINITIONS ::= BEGIN

IMPORTS
      mgmt, NetworkAddress, IpAddress, Counter, Gauge,
           TimeTicks
         FROM RFC1155-SMI
      OBJECT-TYPE
           FROM RFC-1212;

--  This MIB module uses the extended OBJECT-TYPE macro as
--  defined in [14];



--  MIB-II (same prefix as MIB-I)

mib-2      OBJECT IDENTIFIER ::= { mgmt 1 }

-- textual conventions

DisplayString ::=
  OCTET STRING
-- This data type is used to model textual information taken
```

```
-- from the NVT ASCII character set.  By convention, objects
-- with this syntax are declared as having

--
--      SIZE (0..255)

PhysAddress ::=
  OCTET STRING
-- This data type is used to model media addresses.  For many
-- types of media, this will be in a binary representation.
-- For example, an ethernet address would be represented as
-- a string of 6 octets.


-- groups in MIB-II

system       OBJECT IDENTIFIER ::= { mib-2 1 }

interfaces
  OBJECT IDENTIFIER ::= { mib-2 2 }

at           OBJECT IDENTIFIER ::= { mib-2 3 }

ip           OBJECT IDENTIFIER ::= { mib-2 4 }

icmp         OBJECT IDENTIFIER ::= { mib-2 5 }

tcp          OBJECT IDENTIFIER ::= { mib-2 6 }

udp          OBJECT IDENTIFIER ::= { mib-2 7 }

egp          OBJECT IDENTIFIER ::= { mib-2 8 }

-- historical (some say hysterical)
-- cmot      OBJECT IDENTIFIER ::= { mib-2 9 }

transmission OBJECT IDENTIFIER ::= { mib-2 10 }

snmp         OBJECT IDENTIFIER ::= { mib-2 11 }


-- the System group

-- Implementation of the System group is mandatory for all
-- systems.  If an agent is not configured to have a value
-- for any of these variables, a string of length 0 is
-- returned.
```

```
sysDescr OBJECT-TYPE
  SYNTAX  DisplayString (SIZE (0..255))
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "A textual description of the entity.  This value
        should include the full name and version
        identification of the
 system's hardware type,
        software operating-system, and networking
        software.  It is mandatory that this only contain
        printable ASCII characters."
  ::= { system 1 }

sysObjectID OBJECT-TYPE
  SYNTAX  OBJECT IDENTIFIER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The vendor's authoritative identification of the
        network management subsystem contained in the
        entity.  This value is allocated within the SMI
        enterprises subtree (1.3.6.1.4.1) and provides an
        easy and unambiguous means for determining `what
        kind of box' is being managed.  For example, if
        vendor `Flintstones, Inc.' was assigned the
        subtree 1.3.6.1.4.1.4242, it could assign the
        identifier 1.3.6.1.4.1.4242.1.1 to its `Fred
        Router'."
  ::= { system 2 }

sysUpTime OBJECT-TYPE
  SYNTAX  TimeTicks
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
         "The time (in hundredths of a second) since the
        network management portion of the system was last
        re-initialized."
  ::= { system 3 }

sysContact OBJECT-TYPE
  SYNTAX  DisplayString (SIZE (0..255))
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "The textual identification of the contact person
        for this managed node, together with information
```

```
        on how to contact this person."
    ::= { system 4 }

sysName OBJECT-TYPE
    SYNTAX  DisplayString (SIZE (0..255))
    ACCESS  read-write
    STATUS  mandatory
    DESCRIPTION
        "An administratively-assigned name for this
        managed node.  By convention, this is the node's
        fully-qualified domain name."
    ::= { system 5 }

sysLocation OBJECT-TYPE
    SYNTAX  DisplayString (SIZE (0..255))
    ACCESS  read-write
    STATUS  mandatory
    DESCRIPTION
        "The physical location of this node (e.g.,
        `telephone closet,
 3rd floor')."
    ::= { system 6 }

sysServices OBJECT-TYPE
    SYNTAX  INTEGER (0..127)
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "A value which indicates the set of services that
        this entity primarily offers.

        The value is a sum.  This sum initially takes the
        value zero, Then, for each layer, L, in the range
        1 through 7, that this node performs transactions
        for, 2 raised to (L - 1) is added to the sum.  For
        example, a node which performs primarily routing
        functions would have a value of 4 (2^(3-1)).  In
        contrast, a node which is a host offering
        application services would have a value of 72
        (2^(4-1) + 2^(7-1)).  Note that in the context of
        the Internet suite of protocols, values should be
        calculated accordingly:

            layer  functionality
                1  physical (e.g., repeaters)

            2  datalink/subnetwork (e.g., bridges)
                3  internet (e.g., IP gateways)
```

```
                4  end-to-end  (e.g., IP hosts)
                7  applications (e.g., mail relays)

        For systems including OSI protocols, layers 5 and
        6 may also be counted."
  ::= { system 7 }

-- the Interfaces group

-- Implementation of the Interfaces group is mandatory for
-- all systems.

ifNumber OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of network interfaces (regardless of
        their current state) present on this system."
  ::= { interfaces 1 }


-- the Interfaces table

-- The Interfaces table contains information on the entity's
-- interfaces.  Each interface is thought of as being
-- attached to a `subnetwork'.  Note that this term should
-- not be confused with `subnet' which refers to an
-- addressing partitioning scheme used in the Internet suite
-- of
 protocols.

ifTable OBJECT-TYPE
  SYNTAX  SEQUENCE OF IfEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "A list of interface entries.  The number of
        entries is given by the value of ifNumber."
  ::= { interfaces 2 }

ifEntry OBJECT-TYPE
  SYNTAX  IfEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "An interface entry containing objects at the
        subnetwork layer and below for a particular
```

```
        interface."
    INDEX   { ifIndex }
    ::= { ifTable 1 }

IfEntry ::=
    SEQUENCE {
        ifIndex
            INTEGER,
        ifDescr
            DisplayString,
        ifType
            INTEGER,
        ifMtu
            INTEGER,
        ifSpeed
            Gauge,
        ifPhysAddress
            PhysAddress,
        ifAdminStatus
            INTEGER,
        ifOperStatus
            INTEGER,
        ifLastChange
            TimeTicks,
        ifInOctets
            Counter,
        ifInUcastPkts
             Counter,
        ifInNUcastPkts
            Counter,
        ifInDiscards
            Counter,
        ifInErrors
            Counter,
        ifInUnknownProtos
            Counter,
        ifOutOctets
            Counter,
        ifOutUcastPkts
            Counter,
        ifOutNUcastPkts
            Counter,
        ifOutDiscards
            Counter,
        ifOutErrors
            Counter,
        ifOutQLen
            Gauge,
```

```
      ifSpecific
          OBJECT IDENTIFIER
    }

ifIndex OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
            "A unique value for each interface.  Its value
            ranges between 1 and the value of ifNumber.  The
            value for each interface must remain constant at
            least from one re-initialization of the entity's
            network management system to the next re-
            initialization."
    ::= { ifEntry 1 }

ifDescr OBJECT-TYPE
    SYNTAX  DisplayString
  (SIZE (0..255))
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
            "A textual string containing information about the
            interface.  This string should include the name of
            the manufacturer, the product name and the version
            of the hardware interface."
    ::= { ifEntry 2 }

ifType OBJECT-TYPE
    SYNTAX  INTEGER {
                other(1),         -- none of the following
                regular1822(2),
                hdh1822(3),
                ddn-x25(4),
                rfc877-x25(5),
                ethernet-csmacd(6),
                iso88023-csmacd(7),
                iso88024-tokenBus(8),
                iso88025-tokenRing(9),
                iso88026-man(10),
                starLan(11),
                proteon-10Mbit(12),
                proteon-80Mbit(13),
                hyperchannel(14),
                fddi(15),
                lapb(16),
                sdlc(17),
```

```
            ds1(18),          -- T-1

        e1(19),           -- european equiv. of T-1
            basicISDN(20),
            primaryISDN(21),   -- proprietary serial
            propPointToPointSerial(22),
            ppp(23),
            softwareLoopback(24),
            eon(25),           -- CLNP over IP [11]
            ethernet-3Mbit(26),
            nsip(27),          -- XNS over IP
            slip(28),          -- generic SLIP
            ultra(29),         -- ULTRA technologies
            ds3(30),           -- T-3
            sip(31),           -- SMDS
            frame-relay(32)
          }
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The type of interface, distinguished according to
        the physical/link protocol(s) immediately `below'
        the network layer in the protocol stack."
  ::= { ifEntry 3 }

ifMtu OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION

      "The size of the largest datagram which can be
        sent/received on the interface, specified in
        octets.  For interfaces that are used for
        transmitting network datagrams, this is the size
        of the largest network datagram that can be sent
        on the interface."
  ::= { ifEntry 4 }

ifSpeed OBJECT-TYPE
  SYNTAX  Gauge
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "An estimate of the interface's current bandwidth
        in bits per second.  For interfaces which do not
        vary in bandwidth or for those where no accurate
        estimation can be made, this object should contain
```

```
        the nominal bandwidth."
  ::= { ifEntry 5 }

ifPhysAddress OBJECT-TYPE
  SYNTAX  PhysAddress
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The interface's address at the protocol layer
        immediately `below' the network layer in the
        protocol stack.  For
 interfaces which do not have
        such an address (e.g., a serial line), this object
        should contain an octet string of zero length."
  ::= { ifEntry 6 }

ifAdminStatus OBJECT-TYPE
  SYNTAX  INTEGER {
            up(1),       -- ready to pass packets
            down(2),
            testing(3)   -- in some test mode
          }
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "The desired state of the interface.  The
        testing(3) state indicates that no operational
        packets can be passed."
  ::= { ifEntry 7 }

ifOperStatus OBJECT-TYPE
  SYNTAX  INTEGER {
            up(1),       -- ready to pass packets
            down(2),
            testing(3)   -- in some test mode
          }
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The current operational state of the interface.
        The testing(3) state indicates that no operational
        packets can
 be passed."
  ::= { ifEntry 8 }

ifLastChange OBJECT-TYPE
  SYNTAX  TimeTicks
  ACCESS  read-only
```

```
  STATUS  mandatory
  DESCRIPTION
        "The value of sysUpTime at the time the interface
        entered its current operational state.  If the
        current state was entered prior to the last re-
        initialization of the local network management
        subsystem, then this object contains a zero
        value."
  ::= { ifEntry 9 }

ifInOctets OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of octets received on the
        interface, including framing characters."
  ::= { ifEntry 10 }

ifInUcastPkts OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of subnetwork-unicast packets
        delivered to a higher-layer protocol."
  ::= { ifEntry 11 }

ifInNUcastPkts OBJECT-TYPE
  SYNTAX  Counter
   ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of non-unicast (i.e., subnetwork-
        broadcast or subnetwork-multicast) packets
        delivered to a higher-layer protocol."
  ::= { ifEntry 12 }

ifInDiscards OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of inbound packets which were chosen
        to be discarded even though no errors had been
        detected to prevent their being deliverable to a
        higher-layer protocol.  One possible reason for
        discarding such a packet could be to free up
```

```
        buffer space."
    ::= { ifEntry 13 }

ifInErrors OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The number of inbound packets that contained
        errors preventing them from being deliverable to a
        higher-layer protocol."
    ::= { ifEntry 14 }

ifInUnknownProtos
 OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The number of packets received via the interface
        which were discarded because of an unknown or
        unsupported protocol."
    ::= { ifEntry 15 }

ifOutOctets OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The total number of octets transmitted out of the
        interface, including framing characters."
    ::= { ifEntry 16 }

ifOutUcastPkts OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The total number of packets that higher-level
        protocols requested be transmitted to a
        subnetwork-unicast address, including those that
        were discarded or not sent."
    ::= { ifEntry 17 }

ifOutNUcastPkts OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
```

```
  DESCRIPTION
        "The total number
 of packets that higher-level
        protocols requested be transmitted to a non-
        unicast (i.e., a subnetwork-broadcast or
        subnetwork-multicast) address, including those
        that were discarded or not sent."
  ::= { ifEntry 18 }

ifOutDiscards OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of outbound packets which were chosen
        to be discarded even though no errors had been
        detected to prevent their being transmitted.  One
        possible reason for discarding such a packet could
        be to free up buffer space."
  ::= { ifEntry 19 }

ifOutErrors OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of outbound packets that could not be
        transmitted because of errors."
  ::= { ifEntry 20 }

ifOutQLen OBJECT-TYPE
  SYNTAX  Gauge
  ACCESS  read-only
  STATUS  mandatory
   DESCRIPTION
        "The length of the output packet queue (in
        packets)."
  ::= { ifEntry 21 }

ifSpecific OBJECT-TYPE
  SYNTAX  OBJECT IDENTIFIER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "A reference to MIB definitions specific to the
        particular media being used to realize the
        interface.  For example, if the interface is
        realized by an ethernet, then the value of this
```

```
            object refers to a document defining objects
            specific to ethernet.  If this information is not
            present, its value should be set to the OBJECT
            IDENTIFIER { 0 0 }, which is a syntatically valid
            object identifier, and any conformant
            implementation of ASN.1 and BER must be able to
            generate and recognize this value."
    ::= { ifEntry 22 }


-- the Address Translation group

-- Implementation of the Address Translation group is
-- mandatory for all
 systems.  Note however that this group
-- is deprecated by MIB-II. That is, it is being included

-- solely for compatibility with MIB-I nodes, and will most
-- likely be excluded from MIB-III nodes.  From MIB-II and
-- onwards, each network protocol group contains its own
-- address translation tables.

-- The Address Translation group contains one table which is
-- the union across all interfaces of the translation tables
-- for converting a NetworkAddress (e.g., an IP address) into
-- a subnetwork-specific address.  For lack of a better term,
-- this document refers to such a subnetwork-specific address
-- as a `physical' address.

-- Examples of such translation tables are: for broadcast
-- media where ARP is in use, the translation table is
-- equivalent to the ARP cache; or, on an X.25 network where
-- non-algorithmic translation to X.121 addresses is
-- required, the translation table contains the
-- NetworkAddress to X.121 address equivalences.

atTable OBJECT-TYPE
    SYNTAX
  SEQUENCE OF AtEntry
    ACCESS  not-accessible
    STATUS  deprecated
    DESCRIPTION
            "The Address Translation tables contain the
            NetworkAddress to `physical' address equivalences.
            Some interfaces do not use translation tables for
            determining address equivalences (e.g., DDN-X.25
            has an algorithmic method); if all interfaces are
            of this type, then the Address Translation table
```

```
        is empty, i.e., has zero entries."
    ::= { at 1 }

atEntry OBJECT-TYPE
    SYNTAX  AtEntry
    ACCESS  not-accessible
    STATUS  deprecated
    DESCRIPTION
        "Each entry contains one NetworkAddress to
        `physical' address equivalence."
    INDEX   { atIfIndex,
              atNetAddress }
    ::= { atTable 1 }

AtEntry ::=
    SEQUENCE {
        atIfIndex
            INTEGER,
        atPhysAddress
            PhysAddress,
        atNetAddress
            NetworkAddress
    }

atIfIndex OBJECT-TYPE
    SYNTAX
   INTEGER
    ACCESS  read-write
    STATUS  deprecated
    DESCRIPTION
        "The interface on which this entry's equivalence
        is effective.  The interface identified by a
        particular value of this index is the same
        interface as identified by the same value of
        ifIndex."
    ::= { atEntry 1 }

atPhysAddress OBJECT-TYPE
    SYNTAX  PhysAddress
    ACCESS  read-write
    STATUS  deprecated
    DESCRIPTION
        "The media-dependent `physical' address.

        Setting this object to a null string (one of zero
        length) has the effect of invaliding the
        corresponding entry in the atTable object.  That
        is, it effectively dissasociates the interface
```

```
        identified with said entry from the mapping
        identified with said entry.  It is an
        implementation-specific matter as to whether the
        agent removes an invalidated entry from the table.
        Accordingly,
 management stations must be prepared
        to receive tabular information from agents that
        corresponds to entries not currently in use.
        Proper interpretation of such entries requires
        examination of the relevant atPhysAddress object."
  ::= { atEntry 2 }

atNetAddress OBJECT-TYPE
  SYNTAX  NetworkAddress
  ACCESS  read-write
  STATUS  deprecated
  DESCRIPTION
        "The NetworkAddress (e.g., the IP address)
        corresponding to the media-dependent `physical'
        address."
  ::= { atEntry 3 }


-- the IP group

-- Implementation of the IP group is mandatory for all
-- systems.

ipForwarding OBJECT-TYPE
  SYNTAX  INTEGER {
            forwarding(1),    -- acting as a gateway
            not-forwarding(2) -- NOT acting as a gateway
          }
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "The indication of whether this entity is acting
        as an IP gateway in respect
 to the forwarding of
        datagrams received by, but not addressed to, this
        entity.  IP gateways forward datagrams.  IP hosts
        do not (except those source-routed via the host).

        Note that for some managed nodes, this object may
        take on only a subset of the values possible.
        Accordingly, it is appropriate for an agent to
        return a `badValue' response if a management
        station attempts to change this object to an
```

```
        inappropriate value."
    ::= { ip 1 }

ipDefaultTTL OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-write
    STATUS  mandatory
    DESCRIPTION
        "The default value inserted into the Time-To-Live
        field of the IP header of datagrams originated at
        this entity, whenever a TTL value is not supplied
        by the transport layer protocol."
    ::= { ip 2 }

ipInReceives OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
     DESCRIPTION
        "The total number of input datagrams received from
        interfaces, including those received in error."
    ::= { ip 3 }

ipInHdrErrors OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The number of input datagrams discarded due to
        errors in their IP headers, including bad
        checksums, version number mismatch, other format
        errors, time-to-live exceeded, errors discovered
        in processing their IP options, etc."
    ::= { ip 4 }

ipInAddrErrors OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The number of input datagrams discarded because
        the IP address in their IP header's destination
        field was not a valid address to be received at
        this entity.  This count includes invalid
        addresses (e.g., 0.0.0.0) and addresses of
        unsupported Classes (e.g.,
   Class E).  For entities
        which are not IP Gateways and therefore do not
```

forward datagrams, this counter includes datagrams
discarded because the destination address was not
a local address."
::= { ip 5 }

ipForwDatagrams OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of input datagrams for which this
entity was not their final IP destination, as a
result of which an attempt was made to find a
route to forward them to that final destination.
In entities which do not act as IP Gateways, this
counter will include only those packets which were
Source-Routed via this entity, and the Source-
Route option processing was successful."
::= { ip 6 }

ipInUnknownProtos OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of locally-addressed
datagrams
received successfully but discarded because of an
unknown or unsupported protocol."
::= { ip 7 }

ipInDiscards OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of input IP datagrams for which no
problems were encountered to prevent their
continued processing, but which were discarded
(e.g., for lack of buffer space). Note that this
counter does not include any datagrams discarded
while awaiting re-assembly."
::= { ip 8 }

ipInDelivers OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory

```
  DESCRIPTION
        "The total number of input datagrams successfully
        delivered to IP user-protocols (including ICMP)."
  ::= { ip 9 }

ipOutRequests OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of IP datagrams
 which local IP
        user-protocols (including ICMP) supplied to IP in
        requests for transmission.  Note that this counter
        does not include any datagrams counted in
        ipForwDatagrams."
  ::= { ip 10 }

ipOutDiscards OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of output IP datagrams for which no
        problem was encountered to prevent their
        transmission to their destination, but which were
        discarded (e.g., for lack of buffer space).  Note
        that this counter would include datagrams counted
        in ipForwDatagrams if any such packets met this
        (discretionary) discard criterion."
  ::= { ip 11 }

ipOutNoRoutes OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of IP datagrams discarded because no
        route could be found to transmit them
 to their
        destination.  Note that this counter includes any
        packets counted in ipForwDatagrams which meet this
        `no-route' criterion.  Note that this includes any
        datagarms which a host cannot route because all of
        its default gateways are down."
  ::= { ip 12 }

ipReasmTimeout OBJECT-TYPE
```

```
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The maximum number of seconds which received
        fragments are held while they are awaiting
        reassembly at this entity."
  ::= { ip 13 }

ipReasmReqds OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of IP fragments received which needed
        to be reassembled at this entity."
  ::= { ip 14 }

ipReasmOKs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of IP datagrams successfully re-

       assembled."
  ::= { ip 15 }

ipReasmFails OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of failures detected by the IP re-
        assembly algorithm (for whatever reason: timed
        out, errors, etc).  Note that this is not
        necessarily a count of discarded IP fragments
        since some algorithms (notably the algorithm in
        RFC 815) can lose track of the number of fragments
        by combining them as they are received."
  ::= { ip 16 }

ipFragOKs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of IP datagrams that have been
```

```
        successfully fragmented at this entity."
  ::= { ip 17 }

ipFragFails OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of IP datagrams that have been
        discarded because they needed to
 be fragmented at
        this entity but could not be, e.g., because their
        Don't Fragment flag was set."
  ::= { ip 18 }

ipFragCreates OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of IP datagram fragments that have
        been generated as a result of fragmentation at
        this entity."
  ::= { ip 19 }

-- the IP address table

-- The IP address table contains this entity's IP addressing
-- information.

ipAddrTable OBJECT-TYPE
  SYNTAX  SEQUENCE OF IpAddrEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "The table of addressing information relevant to
        this entity's IP addresses."
  ::= { ip 20 }

ipAddrEntry OBJECT-TYPE
  SYNTAX  IpAddrEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "The addressing information for one of this
        entity's IP addresses."
  INDEX   { ipAdEntAddr }
  ::=
```

```
 { ipAddrTable 1 }

IpAddrEntry ::=
  SEQUENCE {
     ipAdEntAddr
        IpAddress,
     ipAdEntIfIndex
        INTEGER,
     ipAdEntNetMask
        IpAddress,
     ipAdEntBcastAddr
        INTEGER,
     ipAdEntReasmMaxSize
        INTEGER (0..65535)
  }

ipAdEntAddr OBJECT-TYPE
  SYNTAX  IpAddress
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The IP address to which this entry's addressing
        information pertains."
  ::= { ipAddrEntry 1 }

ipAdEntIfIndex OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The index value which uniquely identifies the
        interface to which this entry is applicable.  The
        interface identified by a particular value of this
        index is the same interface as identified by the
        same value of ifIndex."
  ::= { ipAddrEntry 2 }

ipAdEntNetMask OBJECT-TYPE
  SYNTAX  IpAddress
  ACCESS
 read-only
  STATUS  mandatory
  DESCRIPTION
        "The subnet mask associated with the IP address of
        this entry.  The value of the mask is an IP
        address with all the network bits set to 1 and all
        the hosts bits set to 0."
  ::= { ipAddrEntry 3 }
```

```
ipAdEntBcastAddr OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The value of the least-significant bit in the IP
        broadcast address used for sending datagrams on
        the (logical) interface associated with the IP
        address of this entry.  For example, when the
        Internet standard all-ones broadcast address is
        used, the value will be 1.  This value applies to
        both the subnet and network broadcasts addresses
        used by the entity on this (logical) interface."
  ::= { ipAddrEntry 4 }

ipAdEntReasmMaxSize OBJECT-TYPE
  SYNTAX  INTEGER (0..65535)
  ACCESS  read-only
   STATUS  mandatory
  DESCRIPTION
        "The size of the largest IP datagram which this
        entity can re-assemble from incoming IP fragmented
        datagrams received on this interface."
  ::= { ipAddrEntry 5 }

-- the IP routing table

-- The IP routing table contains an entry for each route
-- presently known to this entity.

ipRouteTable OBJECT-TYPE
  SYNTAX  SEQUENCE OF IpRouteEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "This entity's IP Routing table."
  ::= { ip 21 }

ipRouteEntry OBJECT-TYPE
  SYNTAX  IpRouteEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "A route to a particular destination."
  INDEX   { ipRouteDest }
  ::= { ipRouteTable 1 }
```

```
IpRouteEntry ::=
  SEQUENCE {
    ipRouteDest
      IpAddress,
    ipRouteIfIndex
      INTEGER,
    ipRouteMetric1
      INTEGER,
    ipRouteMetric2
      INTEGER,
    ipRouteMetric3
       INTEGER,
    ipRouteMetric4
      INTEGER,
    ipRouteNextHop
      IpAddress,
    ipRouteType
      INTEGER,
    ipRouteProto
      INTEGER,
    ipRouteAge
      INTEGER,
    ipRouteMask
      IpAddress,
    ipRouteMetric5
      INTEGER,
    ipRouteInfo
      OBJECT IDENTIFIER
  }

ipRouteDest OBJECT-TYPE
  SYNTAX  IpAddress
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
      "The destination IP address of this route.  An
      entry with a value of 0.0.0.0 is considered a
      default route.  Multiple routes to a single
      destination can appear in the table, but access to
      such multiple entries is dependent on the table-
      access mechanisms defined by the network
      management protocol in use."
  ::= { ipRouteEntry 1 }

ipRouteIfIndex OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-write
  STATUS  mandatory
```

```
 DESCRIPTION
        "The index value which uniquely identifies the
        local interface through which the next hop of this
        route should be reached.  The interface identified
        by a particular value of this index is the same
        interface as identified by the same value of
        ifIndex."
  ::= { ipRouteEntry 2 }

ipRouteMetric1 OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "The primary routing metric for this route.  The
        semantics of this metric are determined by the
        routing-protocol specified in the route's
        ipRouteProto value.  If this metric is not used,
        its value should be set to -1."
  ::= { ipRouteEntry 3 }

ipRouteMetric2 OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "An alternate routing metric for this route.  The
        semantics of this metric are determined
 by the
        routing-protocol specified in the route's
        ipRouteProto value.  If this metric is not used,
        its value should be set to -1."
  ::= { ipRouteEntry 4 }

ipRouteMetric3 OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "An alternate routing metric for this route.  The
        semantics of this metric are determined by the
        routing-protocol specified in the route's
        ipRouteProto value.  If this metric is not used,
        its value should be set to -1."
  ::= { ipRouteEntry 5 }

ipRouteMetric4 OBJECT-TYPE
```

```
  SYNTAX  INTEGER
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
          "An alternate routing metric for this route.  The
          semantics of this metric are determined by the
          routing-protocol specified in the route's
          ipRouteProto value.  If this metric is not used,
          its value should be set to -1."
   ::= { ipRouteEntry 6 }

ipRouteNextHop OBJECT-TYPE
  SYNTAX  IpAddress
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
          "The IP address of the next hop of this route.
          (In the case of a route bound to an interface
          which is realized via a broadcast media, the value
          of this field is the agent's IP address on that
          interface.)"
  ::= { ipRouteEntry 7 }

ipRouteType OBJECT-TYPE
  SYNTAX  INTEGER {
              other(1),       -- none of the following

              invalid(2),     -- an invalidated route

                              -- route to directly
              direct(3),      -- connected (sub-)network

                              -- route to a non-local
              indirect(4)     -- host/network/sub-network
          }
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
          "The type of route.  Note that the values
          direct(3) and indirect(4) refer
 to the notion of
          direct and indirect routing in the IP
          architecture.

          Setting this object to the value invalid(2) has
          the effect of invalidating the corresponding entry
          in the ipRouteTable object.  That is, it
          effectively dissasociates the destination
```

```
        identified with said entry from the route
        identified with said entry.  It is an
        implementation-specific matter as to whether the
        agent removes an invalidated entry from the table.
        Accordingly, management stations must be prepared
        to receive tabular information from agents that
        corresponds to entries not currently in use.
        Proper interpretation of such entries requires
        examination of the relevant ipRouteType object."
  ::= { ipRouteEntry 8 }

ipRouteProto OBJECT-TYPE
  SYNTAX  INTEGER {
            other(1),       -- none of the following


             -- non-protocol information,
                        -- e.g., manually configured
            local(2),       -- entries

                        -- set via a network
            netmgmt(3),     -- management protocol

                        -- obtained via ICMP,
            icmp(4),        -- e.g., Redirect

                        -- the remaining values are
                        -- all gateway routing
                        -- protocols
            egp(5),
            ggp(6),
            hello(7),
            rip(8),
            is-is(9),
            es-is(10),
            ciscoIgrp(11),
            bbnSpfIgp(12),
            ospf(13),
            bgp(14)
          }
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The routing mechanism via which this route was
        learned.  Inclusion of values for gateway routing
        protocols
 is not intended to imply that hosts
        should support those protocols."
```

::= { ipRouteEntry 9 }

ipRouteAge OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-write
STATUS mandatory
DESCRIPTION
"The number of seconds since this route was last updated or otherwise determined to be correct. Note that no semantics of `too old' can be implied except through knowledge of the routing protocol by which the route was learned."
::= { ipRouteEntry 10 }

ipRouteMask OBJECT-TYPE
SYNTAX IpAddress
ACCESS read-write
STATUS mandatory
DESCRIPTION
"Indicate the mask to be logical-ANDed with the destination address before being compared to the value in the ipRouteDest field. For those systems that do not support arbitrary subnet masks, an agent constructs the value of the ipRouteMask by determining whether the value of the correspondent ipRouteDest field belong to a class-A, B, or C network, and then using one of:

mask	network
255.0.0.0	class-A
255.255.0.0	class-B
255.255.255.0	class-C

If the value of the ipRouteDest is 0.0.0.0 (a default route), then the mask value is also 0.0.0.0. It should be noted that all IP routing subsystems implicitly use this mechanism."
::= { ipRouteEntry 11 }

ipRouteMetric5 OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-write
STATUS mandatory
DESCRIPTION
"An alternate routing metric for this route. The semantics of this metric are determined by the routing-protocol specified in the route's ipRouteProto value. If this metric is not used, its value should be set to -1."

```
  ::= { ipRouteEntry 12 }

ipRouteInfo OBJECT-TYPE
  SYNTAX  OBJECT IDENTIFIER
   ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "A reference to MIB definitions specific to the
        particular routing protocol which is responsible
        for this route, as determined by the value
        specified in the route's ipRouteProto value.  If
        this information is not present, its value should
        be set to the OBJECT IDENTIFIER { 0 0 }, which is
        a syntatically valid object identifier, and any
        conformant implementation of ASN.1 and BER must be
        able to generate and recognize this value."
  ::= { ipRouteEntry 13 }



-- the IP Address Translation table

-- The IP address translation table contain the IpAddress to
-- `physical' address equivalences.  Some interfaces do not
-- use translation tables for determining address
-- equivalences (e.g., DDN-X.25 has an algorithmic method);
-- if all interfaces are of this type, then the Address
-- Translation table is empty, i.e., has zero
 entries.

ipNetToMediaTable OBJECT-TYPE
  SYNTAX  SEQUENCE OF IpNetToMediaEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "The IP Address Translation table used for mapping
        from IP addresses to physical addresses."
  ::= { ip 22 }

ipNetToMediaEntry OBJECT-TYPE
  SYNTAX  IpNetToMediaEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "Each entry contains one IpAddress to `physical'
        address equivalence."
  INDEX   { ipNetToMediaIfIndex,
            ipNetToMediaNetAddress }
  ::= { ipNetToMediaTable 1 }
```

```
IpNetToMediaEntry ::=
  SEQUENCE {
    ipNetToMediaIfIndex
      INTEGER,
    ipNetToMediaPhysAddress
      PhysAddress,
    ipNetToMediaNetAddress
      IpAddress,
    ipNetToMediaType
      INTEGER
  }

ipNetToMediaIfIndex OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
      "The interface
 on which this entry's equivalence
      is effective.  The interface identified by a
      particular value of this index is the same
      interface as identified by the same value of
      ifIndex."
  ::= { ipNetToMediaEntry 1 }

ipNetToMediaPhysAddress OBJECT-TYPE
  SYNTAX  PhysAddress
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
      "The media-dependent `physical' address."
  ::= { ipNetToMediaEntry 2 }

ipNetToMediaNetAddress OBJECT-TYPE
  SYNTAX  IpAddress
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
      "The IpAddress corresponding to the media-
      dependent `physical' address."
  ::= { ipNetToMediaEntry 3 }

ipNetToMediaType OBJECT-TYPE
  SYNTAX  INTEGER {
          other(1),       -- none of the following
          invalid(2),     -- an invalidated mapping
          dynamic(3),
```

```
            static(4)
        }
  ACCESS  read-write
  STATUS  mandatory
   DESCRIPTION
        "The type of mapping.

        Setting this object to the value invalid(2) has
        the effect of invalidating the corresponding entry
        in the ipNetToMediaTable.  That is, it effectively
        dissasociates the interface identified with said
        entry from the mapping identified with said entry.
        It is an implementation-specific matter as to
        whether the agent removes an invalidated entry
        from the table.  Accordingly, management stations
        must be prepared to receive tabular information
        from agents that corresponds to entries not
        currently in use.  Proper interpretation of such
        entries requires examination of the relevant
        ipNetToMediaType object."
  ::= { ipNetToMediaEntry 4 }


-- additional IP objects

ipRoutingDiscards OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number
 of routing entries which were chosen
        to be discarded even though they are valid.  One
        possible reason for discarding such an entry could
        be to free-up buffer space for other routing
        entries."
  ::= { ip 23 }


-- the ICMP group

-- Implementation of the ICMP group is mandatory for all
-- systems.

icmpInMsgs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
```

```
  DESCRIPTION
        "The total number of ICMP messages which the
        entity received.  Note that this counter includes
        all those counted by icmpInErrors."
  ::= { icmp 1 }

icmpInErrors OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP messages which the entity
        received but determined as having ICMP-specific
        errors (bad ICMP checksums, bad length, etc.)."
  ::= { icmp 2 }

icmpInDestUnreachs OBJECT-TYPE
  SYNTAX  Counter

  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Destination Unreachable
        messages received."
  ::= { icmp 3 }

icmpInTimeExcds OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Time Exceeded messages
        received."
  ::= { icmp 4 }

icmpInParmProbs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Parameter Problem messages
        received."
  ::= { icmp 5 }

icmpInSrcQuenchs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
```

```
  DESCRIPTION
        "The number of ICMP Source Quench messages
        received."
  ::= { icmp 6 }

icmpInRedirects OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Redirect messages received."
  ::= { icmp 7 }

icmpInEchos OBJECT-TYPE
   SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Echo (request) messages
        received."
  ::= { icmp 8 }

icmpInEchoReps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Echo Reply messages received."
  ::= { icmp 9 }

icmpInTimestamps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Timestamp (request) messages
        received."
  ::= { icmp 10 }

icmpInTimestampReps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Timestamp Reply messages
        received."
  ::= { icmp 11 }
```

```
icmpInAddrMasks OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Address Mask Request messages
        received."
  ::= {
 icmp 12 }

icmpInAddrMaskReps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Address Mask Reply messages
        received."
  ::= { icmp 13 }

icmpOutMsgs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of ICMP messages which this
        entity attempted to send.  Note that this counter
        includes all those counted by icmpOutErrors."
  ::= { icmp 14 }

icmpOutErrors OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP messages which this entity did
        not send due to problems discovered within ICMP
        such as a lack of buffers.  This value should not
        include errors discovered outside the ICMP layer
        such as the inability of IP to route the resultant
        datagram.  In some implementations there may
 be no
        types of error which contribute to this counter's
        value."
  ::= { icmp 15 }

icmpOutDestUnreachs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
```

```
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Destination Unreachable
        messages sent."
  ::= { icmp 16 }

icmpOutTimeExcds OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Time Exceeded messages sent."
  ::= { icmp 17 }

icmpOutParmProbs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Parameter Problem messages
        sent."
  ::= { icmp 18 }

icmpOutSrcQuenchs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Source Quench messages sent."
  ::= { icmp 19 }

icmpOutRedirects OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS
 mandatory
  DESCRIPTION
        "The number of ICMP Redirect messages sent.  For a
        host, this object will always be zero, since hosts
        do not send redirects."
  ::= { icmp 20 }

icmpOutEchos OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of ICMP Echo (request) messages sent."
```

::= { icmp 21 }

icmpOutEchoReps OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of ICMP Echo Reply messages sent."
::= { icmp 22 }

icmpOutTimestamps OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of ICMP Timestamp (request) messages
sent."
::= { icmp 23 }

icmpOutTimestampReps OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of ICMP Timestamp Reply messages
sent."
::= {
icmp 24 }

icmpOutAddrMasks OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of ICMP Address Mask Request messages
sent."
::= { icmp 25 }

icmpOutAddrMaskReps OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of ICMP Address Mask Reply messages
sent."
::= { icmp 26 }

```
-- the TCP group

-- Implementation of the TCP group is mandatory for all
-- systems that implement the TCP.

-- Note that instances of object types that represent
-- information about a particular TCP connection are
-- transient; they persist only as long as the connection
-- in question.

tcpRtoAlgorithm OBJECT-TYPE
  SYNTAX  INTEGER {
              other(1),    -- none of the following

              constant(2), -- a constant rto
              rsre(3),     -- MIL-STD-1778, Appendix B
              vanj(4)      -- Van Jacobson's algorithm [10]

          }
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
          "The algorithm used to determine the timeout value
          used for retransmitting unacknowledged octets."
  ::= { tcp 1 }

tcpRtoMin OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
          "The minimum value permitted by a TCP
          implementation for the retransmission timeout,
          measured in milliseconds.  More refined semantics
          for objects of this type depend upon the algorithm
          used to determine the retransmission timeout.  In
          particular, when the timeout algorithm is rsre(3),
          an object of this type has the semantics of the
          LBOUND quantity described in RFC 793."
  ::= { tcp 2 }


tcpRtoMax OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
          "The maximum value permitted by a TCP
```

implementation for the retransmission
timeout,
measured in milliseconds. More refined semantics
for objects of this type depend upon the algorithm
used to determine the retransmission timeout. In
particular, when the timeout algorithm is rsre(3),
an object of this type has the semantics of the
UBOUND quantity described in RFC 793."
::= { tcp 3 }

tcpMaxConn OBJECT-TYPE
SYNTAX INTEGER
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The limit on the total number of TCP connections
the entity can support. In entities where the
maximum number of connections is dynamic, this
object should contain the value -1."
::= { tcp 4 }

tcpActiveOpens OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of times TCP connections have made a
direct transition to the SYN-SENT state from the
CLOSED state."
::= { tcp 5 }

tcpPassiveOpens OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of times TCP connections have made a
direct transition to the SYN-RCVD state from the
LISTEN state."
::= { tcp 6 }

tcpAttemptFails OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of times TCP connections have made a
direct transition to the CLOSED state from either

```
        the SYN-SENT state or the SYN-RCVD state, plus the
        number of times TCP connections have made a direct
        transition to the LISTEN state from the SYN-RCVD
        state."
    ::= { tcp 7 }

tcpEstabResets OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The number of times TCP connections have made a
        direct transition to the CLOSED state from either
        the
 ESTABLISHED state or the CLOSE-WAIT state."
    ::= { tcp 8 }

tcpCurrEstab OBJECT-TYPE
    SYNTAX  Gauge
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The number of TCP connections for which the
        current state is either ESTABLISHED or CLOSE-
        WAIT."
    ::= { tcp 9 }

tcpInSegs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The total number of segments received, including
        those received in error.  This count includes
        segments received on currently established
        connections."
    ::= { tcp 10 }

tcpOutSegs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The total number of segments sent, including
        those on current connections but excluding those
        containing only retransmitted octets."
    ::= { tcp 11 }
```

```
tcpRetransSegs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
   STATUS  mandatory
  DESCRIPTION
        "The total number of segments retransmitted - that
        is, the number of TCP segments transmitted
        containing one or more previously transmitted
        octets."
  ::= { tcp 12 }


-- the TCP Connection table

-- The TCP connection table contains information about this
-- entity's existing TCP connections.

tcpConnTable OBJECT-TYPE
  SYNTAX  SEQUENCE OF TcpConnEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "A table containing TCP connection-specific
        information."
  ::= { tcp 13 }

tcpConnEntry OBJECT-TYPE
  SYNTAX  TcpConnEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "Information about a particular current TCP
        connection.  An object of this type is transient,
        in that it ceases to exist when (or soon after)
        the connection makes the transition to the CLOSED
        state."
  INDEX
  { tcpConnLocalAddress,
          tcpConnLocalPort,
          tcpConnRemAddress,
          tcpConnRemPort }
  ::= { tcpConnTable 1 }

TcpConnEntry ::=
  SEQUENCE {
     tcpConnState
        INTEGER,
     tcpConnLocalAddress
```

```
        IpAddress,
    tcpConnLocalPort
        INTEGER (0..65535),
    tcpConnRemAddress
        IpAddress,
    tcpConnRemPort
        INTEGER (0..65535)
  }

tcpConnState OBJECT-TYPE
  SYNTAX  INTEGER {
              closed(1),
              listen(2),
              synSent(3),
              synReceived(4),
              established(5),
              finWait1(6),
              finWait2(7),
              closeWait(8),
              lastAck(9),
              closing(10),
              timeWait(11),
              deleteTCB(12)
          }
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
          "The state of this TCP connection.

          The only value which may
 be set by a management
          station is deleteTCB(12).  Accordingly, it is
          appropriate for an agent to return a `badValue'
          response if a management station attempts to set
          this object to any other value.

          If a management station sets this object to the
          value deleteTCB(12), then this has the effect of
          deleting the TCB (as defined in RFC 793) of the
          corresponding connection on the managed node,
          resulting in immediate termination of the
          connection.

          As an implementation-specific option, a RST
          segment may be sent from the managed node to the
          other TCP endpoint (note however that RST segments
          are not sent reliably)."
  ::= { tcpConnEntry 1 }
```

```
tcpConnLocalAddress OBJECT-TYPE
  SYNTAX  IpAddress
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The local IP address for this TCP connection.  In

  the case of a connection in the listen state which
        is willing to accept connections for any IP
        interface associated with the node, the value
        0.0.0.0 is used."
  ::= { tcpConnEntry 2 }

tcpConnLocalPort OBJECT-TYPE
  SYNTAX  INTEGER (0..65535)
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The local port number for this TCP connection."
  ::= { tcpConnEntry 3 }

tcpConnRemAddress OBJECT-TYPE
  SYNTAX  IpAddress
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The remote IP address for this TCP connection."
  ::= { tcpConnEntry 4 }

tcpConnRemPort OBJECT-TYPE
  SYNTAX  INTEGER (0..65535)
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The remote port number for this TCP connection."
  ::= { tcpConnEntry 5 }


-- additional TCP objects

tcpInErrs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number
```

of segments received in error
(e.g., bad TCP checksums)."
::= { tcp 14 }

tcpOutRsts OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The number of TCP segments sent containing the
RST flag."
::= { tcp 15 }

-- the UDP group

-- Implementation of the UDP group is mandatory for all
-- systems which implement the UDP.

udpInDatagrams OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The total number of UDP datagrams delivered to
UDP users."
::= { udp 1 }

udpNoPorts OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION
"The total number of received UDP datagrams for
which there was no application at the destination
port."
::= { udp 2 }

udpInErrors OBJECT-TYPE
SYNTAX Counter
ACCESS read-only
STATUS mandatory
DESCRIPTION

"The number of received UDP datagrams that could
not be delivered for reasons other than the lack
of an application at the destination port."
::= { udp 3 }

```
udpOutDatagrams OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of UDP datagrams sent from this
        entity."
  ::= { udp 4 }


-- the UDP Listener table

-- The UDP listener table contains information about this
-- entity's UDP end-points on which a local application is
-- currently accepting datagrams.

udpTable OBJECT-TYPE
  SYNTAX  SEQUENCE OF UdpEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "A table containing UDP listener information."
  ::= { udp 5 }

udpEntry OBJECT-TYPE
  SYNTAX  UdpEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "Information about a particular current UDP
        listener."
  INDEX   { udpLocalAddress, udpLocalPort
 }
  ::= { udpTable 1 }

UdpEntry ::=
  SEQUENCE {
     udpLocalAddress
        IpAddress,
     udpLocalPort
        INTEGER (0..65535)
  }

udpLocalAddress OBJECT-TYPE
  SYNTAX  IpAddress
  ACCESS  read-only
  STATUS  mandatory
```

```
  DESCRIPTION
        "The local IP address for this UDP listener.  In
        the case of a UDP listener which is willing to
        accept datagrams for any IP interface associated
        with the node, the value 0.0.0.0 is used."
  ::= { udpEntry 1 }

udpLocalPort OBJECT-TYPE
  SYNTAX  INTEGER (0..65535)
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The local port number for this UDP listener."
  ::= { udpEntry 2 }


-- the EGP group

-- Implementation of the EGP group is mandatory for all
-- systems which implement the EGP.

egpInMsgs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of EGP messages received without
         error."
  ::= { egp 1 }

egpInErrors OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of EGP messages received that proved
        to be in error."
  ::= { egp 2 }

egpOutMsgs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of locally generated EGP
        messages."
  ::= { egp 3 }
```

```
egpOutErrors OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of locally generated EGP messages not
        sent due to resource limitations within an EGP
        entity."
  ::= { egp 4 }


-- the EGP Neighbor table

-- The EGP neighbor table contains information about this
-- entity's EGP neighbors.

egpNeighTable OBJECT-TYPE
  SYNTAX  SEQUENCE OF EgpNeighEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "The EGP neighbor table."
   ::= { egp 5 }

egpNeighEntry OBJECT-TYPE
  SYNTAX  EgpNeighEntry
  ACCESS  not-accessible
  STATUS  mandatory
  DESCRIPTION
        "Information about this entity's relationship with
        a particular EGP neighbor."
  INDEX   { egpNeighAddr }
  ::= { egpNeighTable 1 }

EgpNeighEntry ::=
  SEQUENCE {
     egpNeighState
        INTEGER,
     egpNeighAddr
        IpAddress,
     egpNeighAs
        INTEGER,
     egpNeighInMsgs
        Counter,
     egpNeighInErrs
        Counter,
     egpNeighOutMsgs
        Counter,
```

```
      egpNeighOutErrs
         Counter,
      egpNeighInErrMsgs
         Counter,
      egpNeighOutErrMsgs
         Counter,
      egpNeighStateUps
         Counter,
      egpNeighStateDowns
         Counter,
      egpNeighIntervalHello
         INTEGER,
      egpNeighIntervalPoll
         INTEGER,
      egpNeighMode
         INTEGER,
      egpNeighEventTrigger

        INTEGER
   }

egpNeighState OBJECT-TYPE
   SYNTAX  INTEGER {
              idle(1),
              acquisition(2),
              down(3),
              up(4),
              cease(5)
           }
   ACCESS  read-only
   STATUS  mandatory
   DESCRIPTION
           "The EGP state of the local system with respect to
           this entry's EGP neighbor.  Each EGP state is
           represented by a value that is one greater than
           the numerical value associated with said state in
           RFC 904."
   ::= { egpNeighEntry 1 }

egpNeighAddr OBJECT-TYPE
   SYNTAX  IpAddress
   ACCESS  read-only
   STATUS  mandatory
   DESCRIPTION
           "The IP address of this entry's EGP neighbor."
   ::= { egpNeighEntry 2 }

egpNeighAs OBJECT-TYPE
```

```
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The autonomous system of this EGP peer.  Zero
        should be specified if the autonomous system
        number
 of the neighbor is not yet known."
  ::= { egpNeighEntry 3 }

egpNeighInMsgs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of EGP messages received without error
        from this EGP peer."
  ::= { egpNeighEntry 4 }

egpNeighInErrs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of EGP messages received from this EGP
        peer that proved to be in error (e.g., bad EGP
        checksum)."
  ::= { egpNeighEntry 5 }

egpNeighOutMsgs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of locally generated EGP messages to
        this EGP peer."
  ::= { egpNeighEntry 6 }

egpNeighOutErrs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of locally generated EGP messages not
        sent to this
 EGP peer due to resource limitations
        within an EGP entity."
  ::= { egpNeighEntry 7 }
```

```
egpNeighInErrMsgs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of EGP-defined error messages received
        from this EGP peer."
  ::= { egpNeighEntry 8 }

egpNeighOutErrMsgs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of EGP-defined error messages sent to
        this EGP peer."
  ::= { egpNeighEntry 9 }

egpNeighStateUps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of EGP state transitions to the UP
        state with this EGP peer."
  ::= { egpNeighEntry 10 }

egpNeighStateDowns OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The number of EGP state transitions from the UP
        state to any
 other state with this EGP peer."
  ::= { egpNeighEntry 11 }

egpNeighIntervalHello OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The interval between EGP Hello command
        retransmissions (in hundredths of a second).  This
        represents the t1 timer as defined in RFC 904."
  ::= { egpNeighEntry 12 }
```

```
egpNeighIntervalPoll OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The interval between EGP poll command
        retransmissions (in hundredths of a second).  This
        represents the t3 timer as defined in RFC 904."
  ::= { egpNeighEntry 13 }

egpNeighMode OBJECT-TYPE
  SYNTAX  INTEGER { active(1), passive(2) }
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The polling mode of this EGP entity, either
        passive or active."
  ::= { egpNeighEntry 14 }

egpNeighEventTrigger OBJECT-TYPE
  SYNTAX  INTEGER
 { start(1), stop(2) }
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "A control variable used to trigger operator-
        initiated Start and Stop events.  When read, this
        variable always returns the most recent value that
        egpNeighEventTrigger was set to.  If it has not
        been set since the last initialization of the
        network management subsystem on the node, it
        returns a value of `stop'.

        When set, this variable causes a Start or Stop
        event on the specified neighbor, as specified on
        pages 8-10 of RFC 904.  Briefly, a Start event
        causes an Idle peer to begin neighbor acquisition
        and a non-Idle peer to reinitiate neighbor
        acquisition.  A stop event causes a non-Idle peer
        to return to the Idle state until a Start event
        occurs, either via egpNeighEventTrigger or
        otherwise."
  ::= { egpNeighEntry
 15 }


-- additional EGP objects
```

```
egpAs OBJECT-TYPE
  SYNTAX  INTEGER
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The autonomous system number of this EGP entity."
  ::= { egp 6 }

-- the Transmission group

-- Based on the transmission media underlying each interface
-- on a system, the corresponding portion of the Transmission
-- group is mandatory for that system.

-- When Internet-standard definitions for managing
-- transmission media are defined, the transmission group is
-- used to provide a prefix for the names of those objects.

-- Typically, such definitions reside in the experimental
-- portion of the MIB until they are "proven", then as a
-- part of the Internet standardization process, the
-- definitions are accordingly elevated and a new object
-- identifier, under the transmission group is defined. By
-- convention, the name assigned is:
--
--     type OBJECT IDENTIFIER    ::= { transmission number }
--
-- where "type" is the symbolic
 value used for the media in
-- the ifType column of the ifTable object, and "number" is
-- the actual integer value corresponding to the symbol.


-- the SNMP group

-- Implementation of the SNMP group is mandatory for all
-- systems which support an SNMP protocol entity.  Some of
-- the objects defined below will be zero-valued in those
-- SNMP implementations that are optimized to support only
-- those functions specific to either a management agent or
-- a management station.  In particular, it should be
-- observed that the objects below refer to an SNMP entity,
-- and there may be several SNMP entities residing on a
-- managed node (e.g., if the node is hosting acting as
-- a management station).

snmpInPkts OBJECT-TYPE
  SYNTAX  Counter
```

```
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of Messages delivered to the
        SNMP entity from the transport service."
  ::= { snmp 1 }

snmpOutPkts OBJECT-TYPE
  SYNTAX  Counter
  ACCESS
 read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Messages which were
        passed from the SNMP protocol entity to the
        transport service."
  ::= { snmp 2 }

snmpInBadVersions OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Messages which were
        delivered to the SNMP protocol entity and were for
        an unsupported SNMP version."
  ::= { snmp 3 }

snmpInBadCommunityNames OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Messages delivered to
        the SNMP protocol entity which used a SNMP
        community name not known to said entity."
  ::= { snmp 4 }

snmpInBadCommunityUses OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Messages delivered to

    the SNMP protocol entity which represented an SNMP
        operation which was not allowed by the SNMP
        community named in the Message."
```

```
  ::= { snmp 5 }

snmpInASNParseErrs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of ASN.1 or BER errors
        encountered by the SNMP protocol entity when
        decoding received SNMP Messages."
  ::= { snmp 6 }

-- { snmp 7 } is not used

snmpInTooBigs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP PDUs which were
        delivered to the SNMP protocol entity and for
        which the value of the error-status field is
        `tooBig'."
  ::= { snmp 8 }

snmpInNoSuchNames OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP PDUs which were
        delivered to the
 SNMP protocol entity and for
        which the value of the error-status field is
        `noSuchName'."
  ::= { snmp 9 }

snmpInBadValues OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP PDUs which were
        delivered to the SNMP protocol entity and for
        which the value of the error-status field is
        `badValue'."
  ::= { snmp 10 }
```

```
snmpInReadOnlys OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number valid SNMP PDUs which were
        delivered to the SNMP protocol entity and for
        which the value of the error-status field is
        `readOnly'.  It should be noted that it is a
        protocol error to generate an SNMP PDU which
        contains the value `readOnly' in the error-status
        field, as such this object is provided as a means
        of detecting
 incorrect implementations of the
        SNMP."
  ::= { snmp 11 }

snmpInGenErrs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP PDUs which were
        delivered to the SNMP protocol entity and for
        which the value of the error-status field is
        `genErr'."
  ::= { snmp 12 }

snmpInTotalReqVars OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of MIB objects which have been
        retrieved successfully by the SNMP protocol entity
        as the result of receiving valid SNMP Get-Request
        and Get-Next PDUs."
  ::= { snmp 13 }

snmpInTotalSetVars OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of MIB objects which have been
        altered successfully by the SNMP protocol entity
        as the result
```

```
 of receiving valid SNMP Set-Request
        PDUs."
  ::= { snmp 14 }

snmpInGetRequests OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Get-Request PDUs which
        have been accepted and processed by the SNMP
        protocol entity."
  ::= { snmp 15 }

snmpInGetNexts OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Get-Next PDUs which have
        been accepted and processed by the SNMP protocol
        entity."
  ::= { snmp 16 }

snmpInSetRequests OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP Set-Request PDUs which
        have been accepted and processed by the SNMP
        protocol entity."
  ::= { snmp 17 }

snmpInGetResponses OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
   DESCRIPTION
        "The total number of SNMP Get-Response PDUs which
        have been accepted and processed by the SNMP
        protocol entity."
  ::= { snmp 18 }

snmpInTraps OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
```

```
  DESCRIPTION
        "The total number of SNMP Trap PDUs which have
        been accepted and processed by the SNMP protocol
        entity."
  ::= { snmp 19 }

snmpOutTooBigs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP PDUs which were
        generated by the SNMP protocol entity and for
        which the value of the error-status field is
        `tooBig.'"
  ::= { snmp 20 }

snmpOutNoSuchNames OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP PDUs which were
        generated by the SNMP protocol entity and for
         which the value of the error-status is
        `noSuchName'."
  ::= { snmp 21 }

snmpOutBadValues OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP PDUs which were
        generated by the SNMP protocol entity and for
        which the value of the error-status field is
        `badValue'."
  ::= { snmp 22 }

-- { snmp 23 } is not used

snmpOutGenErrs OBJECT-TYPE
  SYNTAX  Counter
  ACCESS  read-only
  STATUS  mandatory
  DESCRIPTION
        "The total number of SNMP PDUs which were
        generated by the SNMP protocol entity and for
```

```
        which the value of the error-status field is
        `genErr'."
    ::= { snmp 24 }

snmpOutGetRequests OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The total number of SNMP Get-Request PDUs which
        have been generated by the SNMP protocol entity."
    ::= { snmp 25 }

snmpOutGetNexts OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The total number of SNMP Get-Next PDUs which have
        been generated by the SNMP protocol entity."
    ::= { snmp 26 }

snmpOutSetRequests OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The total number of SNMP Set-Request PDUs which
        have been generated by the SNMP protocol entity."
    ::= { snmp 27 }

snmpOutGetResponses OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The total number of SNMP Get-Response PDUs which
        have been generated by the SNMP protocol entity."
    ::= { snmp 28 }

snmpOutTraps OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The total number of SNMP Trap PDUs which have
        been generated by the SNMP protocol entity."
```

```
   ::= { snmp 29 }

snmpEnableAuthenTraps OBJECT-TYPE
  SYNTAX  INTEGER { enabled(1), disabled(2) }
  ACCESS  read-write
  STATUS  mandatory
  DESCRIPTION
        "Indicates whether the SNMP agent process is
        permitted to generate authentication-failure
        traps.  The value of this object overrides any
        configuration information; as such, it provides a
        means whereby all authentication-failure traps may
        be disabled.

        Note that it is strongly recommended that this
        object be stored in non-volatile memory so that it
        remains constant between re-initializations of the
        network management system."
  ::= { snmp 30 }

END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/RFC1213-MIB
No license file was found, but licenses were detected in source scan.

```
IANAifType-MIB DEFINITIONS ::= BEGIN

 IMPORTS
    MODULE-IDENTITY, mib-2      FROM SNMPv2-SMI
    TEXTUAL-CONVENTION          FROM SNMPv2-TC;

 ianaifType MODULE-IDENTITY
    LAST-UPDATED "200709130000Z"  -- September 13, 2007
    ORGANIZATION "IANA"
    CONTACT-INFO "        Internet Assigned Numbers Authority

                  Postal: ICANN
                       4676 Admiralty Way, Suite 330
                       Marina del Rey, CA 90292

                  Tel:    +1 310 823 9358
                  E-Mail: iana&iana.org"

    DESCRIPTION  "This MIB module defines the IANAifType Textual
                  Convention, and thus the enumerated values of
                  the ifType object defined in MIB-II's ifTable."
```

```
    REVISION     "200709130000Z"  -- September 13, 2007
    DESCRIPTION  "Registration of new IANAifTypes 243 and 244."

    REVISION     "200705290000Z"
 -- May 29, 2007
    DESCRIPTION  "Changed the description for IANAifType 228."

    REVISION     "200703080000Z"  -- March 08, 2007
    DESCRIPTION  "Registration of new IANAifType 242."

    REVISION     "200701230000Z"  -- January 23, 2007
    DESCRIPTION  "Registration of new IANAifTypes 239, 240, and 241."

    REVISION     "200610170000Z"  -- October 17, 2006
    DESCRIPTION  "Deprecated/Obsoleted IANAifType 230.  Registration of
                  IANAifType 238."

    REVISION     "200609250000Z"  -- September 25, 2006
    DESCRIPTION  "Changed the description for IANA ifType
                  184 and added new IANA ifType 237."

    REVISION     "200608170000Z"  -- August 17, 2006
    DESCRIPTION  "Changed the descriptions for IANAifTypes
                  20 and 21."

    REVISION     "200608110000Z"  -- August 11, 2006
    DESCRIPTION  "Changed the descriptions for IANAifTypes
                  7, 11, 62,
69, and 117."

    REVISION     "200607250000Z"  -- July 25, 2006
    DESCRIPTION  "Registration of new IANA ifType 236."

    REVISION     "200606140000Z"  -- June 14, 2006
    DESCRIPTION  "Registration of new IANA ifType 235."

    REVISION     "200603310000Z"  -- March 31, 2006
    DESCRIPTION  "Registration of new IANA ifType 234."

    REVISION     "200603300000Z"  -- March 30, 2006
    DESCRIPTION  "Registration of new IANA ifType 233."

    REVISION     "200512220000Z"  -- December 22, 2005
    DESCRIPTION  "Registration of new IANA ifTypes 231 and 232."

    REVISION     "200510100000Z"  -- October 10, 2005
    DESCRIPTION  "Registration of new IANA ifType 230."
```

```
    REVISION     "200509090000Z"  -- September 09, 2005
    DESCRIPTION  "Registration of new IANA ifType 229."

    REVISION     "200505270000Z"  -- May 27, 2005
    DESCRIPTION  "Registration of new IANA ifType 228."

    REVISION     "200503030000Z"
-- March 3, 2005
    DESCRIPTION  "Added the IANAtunnelType TC and deprecated
            IANAifType sixToFour (215) per RFC4087."

    REVISION     "200411220000Z"  -- November 22, 2004
    DESCRIPTION  "Registration of new IANA ifType 227 per RFC4631."

    REVISION     "200406170000Z"  -- June 17, 2004
    DESCRIPTION  "Registration of new IANA ifType 226."

    REVISION     "200405120000Z"  -- May 12, 2004
    DESCRIPTION  "Added description for IANAifType 6, and
            changed the descriptions for IANAifTypes
             180, 181, and 182."

    REVISION     "200405070000Z"  -- May 7, 2004
    DESCRIPTION  "Registration of new IANAifType 225."

    REVISION     "200308250000Z"  -- Aug 25, 2003
    DESCRIPTION  "Deprecated IANAifTypes 7 and 11. Obsoleted
            IANAifTypes 62, 69, and 117.  ethernetCsmacd (6)
            should be used instead of these values"

    REVISION     "200308180000Z"
-- Aug 18, 2003
    DESCRIPTION  "Registration of new IANAifType
            224."

    REVISION     "200308070000Z"  -- Aug 7, 2003
    DESCRIPTION  "Registration of new IANAifTypes
            222 and 223."

    REVISION     "200303180000Z"  -- Mar 18, 2003
    DESCRIPTION  "Registration of new IANAifType
            221."

    REVISION     "200301130000Z"  -- Jan 13, 2003
    DESCRIPTION  "Registration of new IANAifType
            220."

    REVISION     "200210170000Z"  -- Oct 17, 2002
```

DESCRIPTION "Registration of new IANAifType
219."

REVISION "200207160000Z" -- Jul 16, 2002
DESCRIPTION "Registration of new IANAifTypes
217 and 218."

REVISION "200207100000Z" -- Jul 10, 2002
DESCRIPTION "Registration of new IANAifTypes
215 and 216."

REVISION "200206190000Z" -- Jun 19, 2002
DESCRIPTION "Registration
of new IANAifType
214."

REVISION "200201040000Z" -- Jan 4, 2002
DESCRIPTION "Registration of new IANAifTypes
211, 212 and 213."

REVISION "200112200000Z" -- Dec 20, 2001
DESCRIPTION "Registration of new IANAifTypes
209 and 210."

REVISION "200111150000Z" -- Nov 15, 2001
DESCRIPTION "Registration of new IANAifTypes
207 and 208."

REVISION "200111060000Z" -- Nov 6, 2001
DESCRIPTION "Registration of new IANAifType
206."

REVISION "200111020000Z" -- Nov 2, 2001
DESCRIPTION "Registration of new IANAifType
205."

REVISION "200110160000Z" -- Oct 16, 2001
DESCRIPTION "Registration of new IANAifTypes
199, 200, 201, 202, 203, and 204."

REVISION "200109190000Z" -- Sept 19, 2001
DESCRIPTION "Registration
of new IANAifType
198."

REVISION "200105110000Z" -- May 11, 2001
DESCRIPTION "Registration of new IANAifType
197."

REVISION "200101120000Z" -- Jan 12, 2001
DESCRIPTION "Registration of new IANAifTypes
195 and 196."

REVISION "200012190000Z" -- Dec 19, 2000
DESCRIPTION "Registration of new IANAifTypes
193 and 194."

REVISION "200012070000Z" -- Dec 07, 2000
DESCRIPTION "Registration of new IANAifTypes
191 and 192."

REVISION "200012040000Z" -- Dec 04, 2000
DESCRIPTION "Registration of new IANAifType
190."

REVISION "200010170000Z" -- Oct 17, 2000
DESCRIPTION "Registration of new IANAifTypes
188 and 189."

REVISION "200010020000Z" -- Oct 02, 2000
DESCRIPTION "Registration of new IANAifType
187."

REVISION "200009010000Z" -- Sept 01, 2000
DESCRIPTION "Registration of new IANAifTypes
184, 185, and 186."

REVISION "200008240000Z" -- Aug 24, 2000
DESCRIPTION "Registration of new IANAifType 183."

REVISION "200008230000Z" -- Aug 23, 2000
DESCRIPTION "Registration of new IANAifTypes
174-182."

REVISION "200008220000Z" -- Aug 22, 2000
DESCRIPTION "Registration of new IANAifTypes 170,
171, 172 and 173."

REVISION "200004250000Z" -- Apr 25, 2000
DESCRIPTION "Registration of new IANAifTypes 168 and 169."

```
    REVISION     "200003060000Z"  -- Mar 6, 2000
    DESCRIPTION  "Fixed a missing semi-colon in the IMPORT.
                  Also cleaned up the REVISION log a bit.
                  It is not complete, but from now on it will
                  be maintained and kept up to date with
each
                  change to this MIB module."

    REVISION     "199910081430Z"  -- Oct 08, 1999
    DESCRIPTION  "Include new name assignments up to cnr(85).
                  This is the first version available via the WWW
                  at: ftp://ftp.isi.edu/mib/ianaiftype.mib"

    REVISION     "199401310000Z"  -- Jan 31, 1994
    DESCRIPTION  "Initial version of this MIB as published in
                  RFC 1573."

    ::= { mib-2 30 }


 IANAifType ::= TEXTUAL-CONVENTION
    STATUS       current
    DESCRIPTION
          "This data type is used as the syntax of the ifType
          object in the (updated) definition of MIB-II's
          ifTable.

          The definition of this textual convention with the
          addition of newly assigned values is published
          periodically by the IANA, in either the Assigned
          Numbers RFC, or some derivative of it specific to
          Internet
Network Management number assignments.  (The
          latest arrangements can be obtained by contacting the
          IANA.)

          Requests for new values should be made to IANA via
          email (iana&iana.org).

          The relationship between the assignment of ifType
          values and of OIDs to particular media-specific MIBs
          is solely the purview of IANA and is subject to change
          without notice.  Quite often, a media-specific MIB's
          OID-subtree assignment within MIB-II's 'transmission'
          subtree will be the same as its ifType value.
          However, in some circumstances this will not be the
          case, and implementors must not pre-assume any
          specific relationship between ifType values and
```

```
        transmission subtree OIDs."
    SYNTAX  INTEGER {
            other(1),          -- none of the following
            regular1822(2),
             hdh1822(3),
            ddnX25(4),
            rfc877x25(5),
            ethernetCsmacd(6), -- for all ethernet-like interfaces,
                        -- regardless of speed, as per RFC3635
            iso88023Csmacd(7), -- Deprecated via RFC3635
                        -- ethernetCsmacd (6) should be used instead
            iso88024TokenBus(8),
            iso88025TokenRing(9),
            iso88026Man(10),
            starLan(11), -- Deprecated via RFC3635
                    -- ethernetCsmacd (6) should be used instead
            proteon10Mbit(12),
            proteon80Mbit(13),
            hyperchannel(14),
            fddi(15),
            lapb(16),
            sdlc(17),
            ds1(18),            -- DS1-MIB
            e1(19),             -- Obsolete see DS1-MIB
            basicISDN(20),
      -- no longer used
                                -- see also RFC2127
            primaryISDN(21),            -- no longer used
                                -- see also RFC2127
            propPointToPointSerial(22), -- proprietary serial
            ppp(23),
            softwareLoopback(24),
            eon(25),            -- CLNP over IP
            ethernet3Mbit(26),
            nsip(27),           -- XNS over IP
            slip(28),           -- generic SLIP
            ultra(29),          -- ULTRA technologies
            ds3(30),            -- DS3-MIB
            sip(31),            -- SMDS, coffee
            frameRelay(32),     -- DTE only.
            rs232(33),
            para(34),           -- parallel-port
            arcnet(35),         -- arcnet
            arcnetPlus(36),     -- arcnet plus
            atm(37),
       -- ATM cells
            miox25(38),
            sonet(39),          -- SONET or SDH
```

```
            x25ple(40),
            iso88022llc(41),
            localTalk(42),
            smdsDxi(43),
            frameRelayService(44),  -- FRNETSERV-MIB
            v35(45),
            hssi(46),
            hippi(47),
            modem(48),          -- Generic modem
            aal5(49),           -- AAL5 over ATM
            sonetPath(50),
            sonetVT(51),
            smdsIcip(52),       -- SMDS InterCarrier Interface
            propVirtual(53),    -- proprietary virtual/internal
            propMultiplexor(54),-- proprietary multiplexing
            ieee80212(55),      -- 100BaseVG
            fibreChannel(56),   -- Fibre Channel
            hippiInterface(57), -- HIPPI interfaces
            frameRelayInterconnect(58), --
Obsolete use either
                        -- frameRelay(32) or
                        -- frameRelayService(44).
            aflane8023(59),     -- ATM Emulated LAN for 802.3
            aflane8025(60),     -- ATM Emulated LAN for 802.5
            cctEmul(61),        -- ATM Emulated circuit
            fastEther(62),      -- Obsoleted via RFC3635
                        -- ethernetCsmacd (6) should be used instead
            isdn(63),           -- ISDN and X.25
            v11(64),            -- CCITT V.11/X.21
            v36(65),            -- CCITT V.36
            g703at64k(66),      -- CCITT G703 at 64Kbps
            g703at2mb(67),      -- Obsolete see DS1-MIB
            qllc(68),           -- SNA QLLC
            fastEtherFX(69),    -- Obsoleted via RFC3635

           -- ethernetCsmacd (6) should be used instead
            channel(70),        -- channel
            ieee80211(71),      -- radio spread spectrum
            ibm370parChan(72),  -- IBM System 360/370 OEMI Channel
            escon(73),          -- IBM Enterprise Systems Connection
            dlsw(74),           -- Data Link Switching
            isdns(75),          -- ISDN S/T interface
            isdnu(76),          -- ISDN U interface
            lapd(77),           -- Link Access Protocol D
            ipSwitch(78),       -- IP Switching Objects
            rsrb(79),           -- Remote Source Route Bridging
            atmLogical(80),     -- ATM Logical Port
            ds0(81),            -- Digital Signal Level 0
```

```
            ds0Bundle(82),      -- group of ds0s on the same ds1
            bsc(83),            -- Bisynchronous Protocol

           async(84),          -- Asynchronous Protocol
            cnr(85),            -- Combat Net Radio
            iso88025Dtr(86),    -- ISO 802.5r DTR
            eplrs(87),          -- Ext Pos Loc Report Sys
            arap(88),           -- Appletalk Remote Access Protocol
            propCnls(89),       -- Proprietary Connectionless Protocol
            hostPad(90),        -- CCITT-ITU X.29 PAD Protocol
            termPad(91),        -- CCITT-ITU X.3 PAD Facility
            frameRelayMPI(92),  -- Multiproto Interconnect over FR
            x213(93),           -- CCITT-ITU X213
            adsl(94),           -- Asymmetric Digital Subscriber Loop
            radsl(95),          -- Rate-Adapt. Digital Subscriber Loop
            sdsl(96),           -- Symmetric Digital Subscriber Loop
            vdsl(97),           -- Very H-Speed Digital Subscrib. Loop
            iso88025CRFPInt(98),
-- ISO 802.5 CRFP
            myrinet(99),        -- Myricom Myrinet
            voiceEM(100),       -- voice recEive and transMit
            voiceFXO(101),      -- voice Foreign Exchange Office
            voiceFXS(102),      -- voice Foreign Exchange Station
            voiceEncap(103),    -- voice encapsulation
            voiceOverIp(104),   -- voice over IP encapsulation
            atmDxi(105),        -- ATM DXI
            atmFuni(106),       -- ATM FUNI
            atmIma (107),       -- ATM IMA
            pppMultilinkBundle(108), -- PPP Multilink Bundle
            ipOverCdlc (109),   -- IBM ipOverCdlc
            ipOverClaw (110),   -- IBM Common Link Access to Workstn
            stackToStack (111), -- IBM stackToStack
            virtualIpAddress (112), -- IBM VIPA
            mpc (113),          -- IBM multi-protocol channel support

ipOverAtm (114),    -- IBM ipOverAtm
            iso88025Fiber (115), -- ISO 802.5j Fiber Token Ring
            tdlc (116),         -- IBM twinaxial data link control
            gigabitEthernet (117), -- Obsoleted via RFC3635
                                -- ethernetCsmacd (6) should be used instead
            hdlc (118),         -- HDLC
            lapf (119),         -- LAP F
            v37 (120),          -- V.37
            x25mlp (121),       -- Multi-Link Protocol
            x25huntGroup (122), -- X25 Hunt Group
            trasnpHdlc (123),   -- Transp HDLC
            interleave (124),   -- Interleave channel
            fast (125),         -- Fast channel
```

ip (126), -- IP (for APPN HPR in IP networks)
docsCableMaclayer (127), -- CATV Mac Layer
docsCableDownstream (128), -- CATV Downstream interface
docsCableUpstream
(129), -- CATV Upstream interface
a12MppSwitch (130), -- Avalon Parallel Processor
tunnel (131), -- Encapsulation interface
coffee (132), -- coffee pot
ces (133), -- Circuit Emulation Service
atmSubInterface (134), -- ATM Sub Interface
l2vlan (135), -- Layer 2 Virtual LAN using 802.1Q
l3ipvlan (136), -- Layer 3 Virtual LAN using IP
l3ipxvlan (137), -- Layer 3 Virtual LAN using IPX
digitalPowerline (138), -- IP over Power Lines
mediaMailOverIp (139), -- Multimedia Mail over IP
dtm (140), -- Dynamic syncronous Transfer Mode
dcn (141), -- Data Communications Network
ipForward (142), -- IP Forwarding Interface
msdsl (143), -- Multi-rate Symmetric DSL

ieee1394 (144), -- IEEE1394 High Performance Serial Bus
if-gsn (145), -- HIPPI-6400
dvbRccMacLayer (146), -- DVB-RCC MAC Layer
dvbRccDownstream (147), -- DVB-RCC Downstream Channel
dvbRccUpstream (148), -- DVB-RCC Upstream Channel
atmVirtual (149), -- ATM Virtual Interface
mplsTunnel (150), -- MPLS Tunnel Virtual Interface
srp (151), -- Spatial Reuse Protocol
voiceOverAtm (152), -- Voice Over ATM
voiceOverFrameRelay (153), -- Voice Over Frame Relay
idsl (154), -- Digital Subscriber Loop over ISDN
compositeLink (155), -- Avici Composite Link Interface
ss7SigLink (156), -- SS7 Signaling Link
propWirelessP2P (157), -- Prop. P2P wireless interface
frForward (158), -- Frame Forward Interface
rfc1483 (159), -- Multiprotocol over ATM AAL5
usb (160), -- USB Interface
ieee8023adLag (161), -- IEEE 802.3ad Link Aggregate
bgppolicyaccounting (162), -- BGP Policy Accounting
frf16MfrBundle (163), -- FRF .16 Multilink Frame Relay
h323Gatekeeper (164), -- H323 Gatekeeper
h323Proxy (165), -- H323 Voice and Video Proxy
mpls (166), -- MPLS
mfSigLink (167), -- Multi-frequency signaling link
hdsl2 (168), -- High Bit-Rate DSL - 2nd generation
shdsl (169), -- Multirate HDSL2
ds1FDL (170), -- Facility Data Link 4Kbps on a DS1
pos (171), -- Packet over SONET/SDH Interface

dvbAsiIn (172), -- DVB-ASI Input
dvbAsiOut (173), -- DVB-ASI Output
plc (174), -- Power Line Communtications
nfas (175), -- Non Facility Associated Signaling
tr008 (176), -- TR008
gr303RDT (177), -- Remote Digital Terminal
gr303IDT (178), -- Integrated Digital Terminal
isup (179), -- ISUP
propDocsWirelessMaclayer (180), -- Cisco proprietary Maclayer
propDocsWirelessDownstream (181), -- Cisco proprietary Downstream
propDocsWirelessUpstream (182), -- Cisco proprietary Upstream
hiperlan2 (183), -- HIPERLAN Type 2 Radio Interface
propBWAp2Mp (184), -- PropBroadbandWirelessAccesspt2multipt
-- use of this iftype for IEEE 802.16 WMAN
-- interfaces as per IEEE Std 802.16f is
-- deprecated and ifType 237 should be used instead.
sonetOverheadChannel (185), -- SONET Overhead Channel
digitalWrapperOverheadChannel
(186), -- Digital Wrapper
aal2 (187), -- ATM adaptation layer 2
radioMAC (188), -- MAC layer over radio links
atmRadio (189), -- ATM over radio links
imt (190), -- Inter Machine Trunks
mvl (191), -- Multiple Virtual Lines DSL
reachDSL (192), -- Long Reach DSL
frDlciEndPt (193), -- Frame Relay DLCI End Point
atmVciEndPt (194), -- ATM VCI End Point
opticalChannel (195), -- Optical Channel
opticalTransport (196), -- Optical Transport
propAtm (197), -- Proprietary ATM
voiceOverCable (198), -- Voice Over Cable Interface
infiniband (199), -- Infiniband
teLink (200), -- TE Link
q2931 (201), -- Q.2931
virtualTg (202), -- Virtual Trunk Group

sipTg (203), -- SIP Trunk Group
sipSig (204), -- SIP Signaling
docsCableUpstreamChannel (205), -- CATV Upstream Channel
econet (206), -- Acorn Econet
pon155 (207), -- FSAN 155Mb Symetrical PON interface
pon622 (208), -- FSAN622Mb Symetrical PON interface
bridge (209), -- Transparent bridge interface
linegroup (210), -- Interface common to multiple lines
voiceEMFGD (211), -- voice E&M Feature Group D
voiceFGDEANA (212), -- voice FGD Exchange Access North American
voiceDID (213), -- voice Direct Inward Dialing
mpegTransport (214), -- MPEG transport interface

```
            sixToFour (215), -- 6to4 interface (DEPRECATED)
            gtp (216), -- GTP (GPRS Tunneling Protocol)
            pdnEtherLoop1 (217), -- Paradyne EtherLoop 1
            pdnEtherLoop2
(218), -- Paradyne EtherLoop 2
            opticalChannelGroup (219), -- Optical Channel Group
            homepna (220), -- HomePNA ITU-T G.989
            gfp (221), -- Generic Framing Procedure (GFP)
            ciscoISLvlan (222), -- Layer 2 Virtual LAN using Cisco ISL
            actelisMetaLOOP (223), -- Acteleis proprietary MetaLOOP High Speed Link
            fcipLink (224), -- FCIP Link
            rpr (225), -- Resilient Packet Ring Interface Type
            qam (226), -- RF Qam Interface
            lmp (227), -- Link Management Protocol
            cblVectaStar (228), -- Cambridge Broadband Networks Limited VectaStar
            docsCableMCmtsDownstream (229), -- CATV Modular CMTS Downstream Interface
            adsl2 (230), -- Asymmetric Digital Subscriber Loop Version 2
                    -- (DEPRECATED/OBSOLETED - please use adsl2plus 238 instead)

        macSecControlledIF (231), -- MACSecControlled
            macSecUncontrolledIF (232), -- MACSecUncontrolled
            aviciOpticalEther (233), -- Avici Optical Ethernet Aggregate
            atmbond (234), -- atmbond
            voiceFGDOS (235), -- voice FGD Operator Services
            mocaVersion1 (236), -- MultiMedia over Coax Alliance (MoCA) Interface
                    -- as documented in information provided privately to IANA
            ieee80216WMAN (237), -- IEEE 802.16 WMAN interface
            adsl2plus (238), -- Asymmetric Digital Subscriber Loop Version 2,
                        -- Version 2 Plus and all variants
            dvbRcsMacLayer (239), -- DVB-RCS MAC Layer
            dvbTdm (240), -- DVB Satellite TDM
            dvbRcsTdma (241), -- DVB-RCS TDMA
            x86Laps (242), -- LAPS based on ITU-T X.86/Y.1323
            wwanPP (243), -- 3GPP
WWAN
            wwanPP2 (244) -- 3GPP2 WWAN
            }

IANAtunnelType ::= TEXTUAL-CONVENTION
  STATUS     current
  DESCRIPTION
        "The encapsulation method used by a tunnel. The value
        direct indicates that a packet is encapsulated
        directly within a normal IP header, with no
        intermediate header, and unicast to the remote tunnel
        endpoint (e.g., an RFC 2003 IP-in-IP tunnel, or an RFC
        1933 IPv6-in-IPv4 tunnel). The value minimal indicates
        that a Minimal Forwarding Header (RFC 2004) is
```

```
        inserted between the outer header and the payload
        packet. The value UDP indicates that the payload
        packet is encapsulated within a normal UDP packet
        (e.g., RFC 1234).

        The values sixToFour, sixOverFour, and isatap
        indicates that an IPv6 packet is encapsulated directly
        within an IPv4 header, with no intermediate header,

        and unicast to the destination determined by the 6to4,
        6over4, or ISATAP protocol.

        The remaining protocol-specific values indicate that a
        header of the protocol of that name is inserted
        between the outer header and the payload header.

        The assignment policy for IANAtunnelType values is
        identical to the policy for assigning IANAifType
        values."
    SYNTAX     INTEGER {
                other(1),       -- none of the following
                direct(2),      -- no intermediate header
                gre(3),         -- GRE encapsulation
                minimal(4),     -- Minimal encapsulation
                l2tp(5),        -- L2TP encapsulation
                pptp(6),        -- PPTP encapsulation
                l2f(7),         -- L2F encapsulation
                udp(8),         -- UDP encapsulation
                atmp(9),        -- ATMP encapsulation

              msdp(10),       -- MSDP encapsulation
                sixToFour(11),  -- 6to4 encapsulation
                sixOverFour(12), -- 6over4 encapsulation
                isatap(13),     -- ISATAP encapsulation
                teredo(14)      -- Teredo encapsulation
              }

    END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/iana/IANAifType-MIB
No license file was found, but licenses were detected in source scan.

```
APM-MIB DEFINITIONS ::= BEGIN
IMPORTS
  MODULE-IDENTITY, OBJECT-TYPE,
  NOTIFICATION-TYPE,
  Counter32, Unsigned32                    FROM SNMPv2-SMI
```

```
  TEXTUAL-CONVENTION, RowStatus, TimeStamp,
  TimeInterval, TruthValue, DateAndTime,
  StorageType                         FROM SNMPv2-TC
  MODULE-COMPLIANCE, OBJECT-GROUP,
  NOTIFICATION-GROUP                  FROM SNMPv2-CONF
  SnmpAdminString                     FROM SNMP-FRAMEWORK-MIB
  rmon, OwnerString                   FROM RMON-MIB
  protocolDirLocalIndex               FROM RMON2-MIB;

--  Application Performance Measurement MIB

apm MODULE-IDENTITY
  LAST-UPDATED "200402190000Z"  -- February 19, 2004
  ORGANIZATION "IETF RMON MIB Working Group"
  CONTACT-INFO
    "Author:
            Steve Waldbusser



        Phone:  +1-650-948-6500
        Fax :   +1-650-745-0671
        Email:  waldbusser@nextbeacon.com

      Working Group Chair:
            Andy Bierman
            Cisco Systems, Inc.
        Postal: 170 West Tasman Drive
            San Jose, CA USA 95134
          Tel: +1 408 527-3711
        E-mail: abierman@cisco.com

      Working Group Mailing List: <rmonmib@ietf.org>
      To subscribe send email to: <rmonmib-request@ietf.org>
    "
  DESCRIPTION
    "The MIB module for measuring application performance
    as experienced by end-users.

    Copyright (C) The Internet Society (2004). This version of
    this MIB module is part of RFC 3729; see the RFC itself for
    full legal notices."

  REVISION "200402190000Z"    -- February 19, 2004
  DESCRIPTION
    "The original version of this MIB Module, published as
    RFC3729."
```

::= { rmon 23 }

apmMibObjects OBJECT IDENTIFIER ::= { apm 1 }
apmConformance OBJECT IDENTIFIER ::= { apm 2 }
apmCompliances
OBJECT IDENTIFIER ::= { apmConformance 1 }
apmGroups OBJECT IDENTIFIER ::= { apmConformance 2 }

AppLocalIndex ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
"A locally arbitrary unique identifier associated with an
application or application verb.

All objects of type AppLocalIndex are assigned by the agent
out of a common number space. In other words, AppLocalIndex
values assigned to entries in one table must not overlap with
AppLocalIndex values assigned to entries in another
table. Further, every protocolDirLocalIndex value registered
by the agent automatically assigns the same value out of the

AppLocalIndex number space.

For example, if the protocolDirLocalIndex values { 1, 3, 5, 7 }
have been assigned, and the apmHttpFilterAppLocalIndex values
{ 6, 8, 9 } have been assigned:

- Assignment of new AppLocalIndex values must not use
the
values { 1, 3, 5, 6, 7, 8, 9 }.
- AppLocalIndex values { 1, 3, 5, 7 } are automatically
assigned and are associated with the identical value of
protocolDirLocalIndex. In particular, an entry in the
apmAppDirTable indexed by a value provides further
information about a protocol indexed by the same value
in the protocolDirTable of RMON2.

The value for each supported application must remain constant
at least from one re-initialization of the entity's network
management system to the next re-initialization, except that
if an application is deleted and re-created, it must be
re-created with a new value that has not been used since the
last re-initialization.

The specific value is meaningful only within a given SNMP

entity. An AppLocalIndex value must not be re-used until the
next agent restart."
SYNTAX Unsigned32
(1..2147483647)

ProtocolDirNetworkAddress ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
"A network level address whose semantics and encoding are
specified by an associated protocolDirLocalIndex
value. Objects of this type must specify which
protocolDirLocalIndex value is used. This value is encoded
according to the encoding rules for the identified
protocolDirectory entry.

For example, if the associated protocolDirLocalIndex indicates
an encapsulation of ip, this object is encoded as a length
octet of 4, followed by the 4 octets of the ip address,
in network byte order.

Objects of this type may allow this value to be the zero
length string. If so, they must identify they meaning of this
value."
SYNTAX OCTET STRING (SIZE(0..255))

DataSourceOrZero ::= TEXTUAL-CONVENTION

STATUS current
DESCRIPTION
"Identifies the source of
the data that the associated
function is configured to analyze. This source can be any
interface on this device.

In order to identify a particular interface, this
object shall identify the instance of the ifIndex
object, defined in [4], for the desired interface.

For example, if an entry were to receive data from
interface #1, this object would be set to ifIndex.1.

If the source of the data isn't an interface or cannot be
localized to an interface, this object would be set to 0.0"

REFERENCE "The DataSource textual convention is defined in
RFC 2021 [5]."

SYNTAX OBJECT IDENTIFIER

RmonClientID ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
"A long-lived unique ID assigned to an end-system. This ID is assigned by the agent using an implementation-specific algorithm.

Because a client machine may be assigned multiple addresses

over any time period it can be difficult to attribute behavior to a particular client based solely on its address. A ClientID may be assigned to provide a more stable handle for referencing that client. The entity that assigns the ClientID may use various implementation techniques to keep track of a client but if the assigning entity is unable to track client address mappings, it may map client identifiers to client addresses rather than to distinct client machines.

This is named ClientID because it helps to solve a problem seen in network clients (servers usually have well-known, long-lived addresses). However, ClientID's may be assigned to any end-system regardless of its role on the network."
SYNTAX Unsigned32 (0..4294967295)

TransactionAggregationType ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION

"Specifies one of 4 different techniques
for aggregating
transactions.

The metrics for a single transaction are the responsiveness of the transaction and whether the transaction succeeded (a boolean). When such metrics are aggregated in this MIB Module, these metrics are replaced by averages and distributions of responsiveness and availability. The metrics describing aggregates are constant no matter which type of aggregation is being performed. These metrics may be found in the apmReportTable.

The flows(1) aggregation is the simplest. All transactions

that share common application/server/client 3-tuples are
aggregated together, resulting in a set of metrics for all
such unique 3-tuples.

The clients(2) aggregation results in somewhat more
aggregation (i.e., fewer resulting records). All transactions
that share common application/client tuples are aggregated
together, resulting in a
set of metrics for all such unique
tuples.

The servers(3) aggregation usually results in still more
aggregation (i.e., fewer resulting records). All transactions
that share common application/server tuples are aggregated
together, resulting in a set of metrics for all such unique
tuples.

The applications(4) aggregation results in the most
aggregation (i.e., the fewest resulting records). All
transactions that share a common application are aggregated
together, resulting in a set of metrics for all such unique
applications.

Note that it is not meaningful to aggregate applications, as
different applications have widely varying characteristics. As a
result, this set of aggregations is complete."
SYNTAX INTEGER {
flows(1), -- Least Aggregation
clients(2),
servers(3),
applications(4) -- Most Aggregation
}

-- The APM Application Directory Group

-- The Application Directory Table contains a record for every

-- application monitored by this agent. This table is also used to
-- configure whether or not an application will be measured and which
-- bucket boundaries will be used for the application.
--
-- The bucket boundaries define the break-points between bins of a
-- histogram analysis for that application. As an example of how this
-- works, consider an entry representing response-time for http.
-- If the boundaries are set as follows:
-- Boundary1: 500 milliseconds

```
-- Boundary2: 1 second
-- Boundary3: 2 seconds
-- Boundary4: 5
-- Boundary5: 15
-- Boundary6: 60
--
-- If the following measurements are made (all in milliseconds):
-- 377, 8645, 1300, 487, 1405, 775, 1115, 850, 945, 1054, 7745, 9380
--
-- A report run during this interval would report the following
-- counts:
-- Bucket1: 2
-- Bucket2: 3
-- Bucket3: 4
-- Bucket4: 0
-- Bucket5: 3
-- Bucket6: 0
--
 Bucket7: 0

apmAppDirTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ApmAppDirEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The APM MIB directory of applications and application
     verbs. The agent will populate this table with all
     applications/verbs of any responsivenessType it has the
     capability to monitor. Since the agent populates this table
     with every entry it has the capability to monitor, the
     entries in this table are read-write, allowing the management
     station to modify parameters in this table but not to add new
     entries or delete entries (however, entries may be
     disabled). If new entries are added to the apmHttpFilterTable
     or the apmUserDefinedAppTable, the agent will add the
     corresponding entries to this table.

     It is an implementation-dependent matter as to how the agent
     sets these default parameters. For example, it may leave
     certain entries
 in this table 'off(0)' if the agent developer



     believes that combination will be infrequently used, allowing
     a manager that needs that capability to set it to 'on(1)'.

     Some applications are registered in the RMON2 protocol
```

```
      directory and some are registered in other tables in this
      MIB Module. Regardless of where an application is originally
      registered, it is assigned an AppLocalIndex value that is the
      primary index for this table.

      The contents of this table affect all reports and exceptions
      generated by this agent. Accordingly, modification of this
      table should be performed by a manager acting in the role of
      administrator. In particular, management software should not
      require or enforce particular configuration of this table - it
      should reflect the preferences of the site administrator, not
      the software author. As a practical matter, this requires
      management
 software to allow the administrator to configure
      the values it will use so that it can be adapted to the site
      policy."
  ::= { apmMibObjects 1 }

apmAppDirEntry OBJECT-TYPE
  SYNTAX      ApmAppDirEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "The APM MIB directory of applications and application
      verbs. An entry will exist in this table for all applications
      for which application performance measurement is supported."
  INDEX { apmAppDirAppLocalIndex,
          apmAppDirResponsivenessType }
  ::= { apmAppDirTable 1 }

ApmAppDirEntry ::= SEQUENCE {
  apmAppDirAppLocalIndex           AppLocalIndex,
  apmAppDirResponsivenessType      INTEGER,
  apmAppDirConfig                  INTEGER,
  apmAppDirResponsivenessBoundary1  Unsigned32,
  apmAppDirResponsivenessBoundary2  Unsigned32,
  apmAppDirResponsivenessBoundary3  Unsigned32,
  apmAppDirResponsivenessBoundary4  Unsigned32,
  apmAppDirResponsivenessBoundary5
 Unsigned32,
  apmAppDirResponsivenessBoundary6  Unsigned32
}

apmAppDirAppLocalIndex OBJECT-TYPE
  SYNTAX      AppLocalIndex
  MAX-ACCESS  not-accessible
```

```
  STATUS      current
  DESCRIPTION
     "The AppLocalIndex assigned for this application Directory
     entry."
  ::= { apmAppDirEntry 1 }

apmAppDirResponsivenessType OBJECT-TYPE
  SYNTAX      INTEGER {
                transactionOriented(1),
                throughputOriented(2),
                streamingOriented(3)
              }
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "This object describes and configures the agent's support for
     application performance measurement for this application.
     There are 3 types of measurements for different types of
     applications:

     Transaction-Oriented applications have a fairly constant
     workload to perform for all transactions. The responsiveness
     metric for transaction-oriented
 applications is application
     response time (from first request to final delivery of
     service) and is measured in milliseconds. This is
     commonly referred to as end-user response time.

     Throughput-Oriented applications have widely varying workloads
     based on the nature of the client request. In particular,
     throughput-oriented applications vary widely in the amount of
     data that must be transported to satisfy the request. The
     responsiveness metric for throughput-oriented applications is
     kilobits per second.

     Streaming-Oriented applications deliver data at a constant
     metered rate of speed regardless of the responsiveness of the
     networking and computing infrastructure. This constant rate of
     speed is generally specified to be below (sometimes well
     below) the nominal capability of the infrastructure. However,
     when the infrastructures cannot deliver data at this speed,
      interruption of service or degradation of service can
     result. The responsiveness metric for streaming-oriented
     applications is the ratio of time that the service is degraded
     or interrupted to the total service time. This metric is
     measured in parts per million.
```

Note that for some applications, measuring more than one
responsiveness type may be interesting. For agents that wish

to support more than one measurement for a application, they
will populate this table with multiple entries for that
application, one for each type."
::= { apmAppDirEntry 2 }

apmAppDirConfig OBJECT-TYPE
SYNTAX INTEGER {
off(1),
on(2)
}
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"This object describes and configures support for application
performance measurement for this application.

If the value of this object is on(2),
the agent supports
measurement of application performance metrics for this
application and is configured to measure such metrics for all
APM MIB functions and all interfaces. If the value of this
object is off(1), the agent supports measurement of
application performance for this application but is configured
to not measure these metrics for any APM MIB functions or
interfaces. Whenever this value changes from on(2) to off(1),
the agent shall delete all related entries in all tables in
this MIB Module.

The value of this object must persist across reboots."
::= { apmAppDirEntry 3 }

apmAppDirResponsivenessBoundary1 OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"The boundary value between bucket1 and bucket 2. If this
value is modified, all entries in the apmReportTable must be
deleted by the agent.

The value
of this object must persist across reboots."
::= { apmAppDirEntry 4 }

```
apmAppDirResponsivenessBoundary2 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     "The boundary value between bucket2 and bucket 3. If this



     value is modified, all entries in the apmReportTable must be
     deleted by the agent.

     The value of this object must persist across reboots."
  ::= { apmAppDirEntry 5 }

apmAppDirResponsivenessBoundary3 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     "The boundary value between bucket3 and bucket 4. If this
     value is modified, all entries in the apmReportTable must be
     deleted by the agent.

     The value of this object must persist across reboots."
  ::= { apmAppDirEntry 6 }

apmAppDirResponsivenessBoundary4 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-write
  STATUS      current
   DESCRIPTION
     "The boundary value between bucket4 and bucket 5. If this
     value is modified, all entries in the apmReportTable must be
     deleted by the agent.

     The value of this object must persist across reboots."
  ::= { apmAppDirEntry 7 }

apmAppDirResponsivenessBoundary5 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     "The boundary value between bucket5 and bucket 6. If this
     value is modified, all entries in the apmReportTable must be
     deleted by the agent.
```

```
      The value of this object must persist across reboots."
   ::= { apmAppDirEntry 8 }

apmAppDirResponsivenessBoundary6 OBJECT-TYPE
   SYNTAX      Unsigned32
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION
      "The boundary value between bucket6 and bucket 7. If this




      value is modified, all entries in the apmReportTable must be
      deleted by the agent.

      The value of
 this object must persist across reboots."
   ::= { apmAppDirEntry 9 }

-- Scalars related to the Application Directory table

apmBucketBoundaryLastChange OBJECT-TYPE
   SYNTAX     TimeStamp
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The value of sysUpTime the last time that any bucket boundary
      in any appDirEntry was changed. This object can help to
      determine if two managers are both trying to enforce different
      configurations of this table."
   ::= { apmMibObjects 2 }

apmAppDirID OBJECT-TYPE
   SYNTAX     OBJECT IDENTIFIER
   MAX-ACCESS read-write
   STATUS     current
   DESCRIPTION
      "This object allows managers to avoid downloading application
      directory information when the directory is set to a known
      (usually fixed) configuration.

      If the value of this object isn't 0.0, it signifies
      that the entire contents of the apmAppDirTable,
      apmHttpFilterTable, apmUserDefinedAppTable and
       protocolDirTable are equal to a known state identified
      by the value of this object. If a manager recognizes this
      value as identifying a directory configuration it has a local
```

copy of, it may use this local copy rather than downloading these tables. Note that it may have downloaded this local copy (and the ID) from another agent and used this copy for all other agents that advertised the same ID.

If an agent recognizes that the entire contents of the apmAppDirTable, apmHttpFilterTable, apmUserDefinedAppTable and protocolDirTable are equal to a known state to which an ID has been assigned, it should set this object to that ID.

In many cases when this feature is used, the application directory information will be in read-only memory and thus the tables may not be modified via SNMP requests. In the event

that the tables are writable and a modification is made, the
agent is responsible for setting this object to 0.0 if it cannot determine that the state is equal to a known state.

An agent is not obligated to recognize and advertise all such registered states as it may not have knowledge of all states. Thus, a manager may encounter agents whose DirectoryID value is 0.0 even though the contents of the directory were equal to a registered state.

Note that the contents of those tables includes the protocolDirLocalIndex and appLocalIndex values. In other words, these values can't be assigned randomly on each agent, but must be equal to values that are part of the known state. While it is possible for a manager to download application directory details using SNMP and to set the appropriate directoryID, the manager would need to have some scheme to ensure consistent values of LocalIndex variables from agent to agent.
Such schemes are outside the scope of this specification.

Application directory registrations are unique within an administrative domain.

Typically these registrations will be made by an agent software developer who will set the application directory tables to a read-only state and assign a DirectoryID to that state. Thus, all agents running this software would share the same DirectoryID. As the application directory might change

```
      from one software release to the next, the developer may
      register different DirectoryID's for each software release.

      A customer could also create a site-wide application directory
      configuration and assign a DirectoryID to that configuration
      as long as consistent values of LocalIndex variables can be
      ensured.

      The value of this object must persist across reboots."
   ::= { apmMibObjects 3 }

-- APM HTTP Filter Table

-- The HTTP Filter Table
 creates virtual applications which measure the
-- performance of certain web pages  or sets of web pages. Some
-- circumstances where this is particularly useful are:
--
--      - An Intranet or ASP scenario where a business application is
--        running on one or more web pages or scripts.



--        (i.e., /expense/submit.cgi?employeeID=3426&...)
--      - A web-hosting scenario where one wants to measure the
--        service level for a particular customer
--      - An e-commerce scenario where the performance of certain
--        pages needs to be monitored more closely.
--        (i.e., shopping cart, shipping, credit card authorization)

apmHttpFilterTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ApmHttpFilterEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A table that creates virtual applications which measure the
      performance of certain web pages or sets of web pages.

      When an entry is added to this table, the agent
 will
      automatically create one or more entries in the
      apmAppDirTable (one for each responsivenessType it is
      capable of measuring).

      Note that when entries exist in this table some HTTP
      transactions will be summarized twice: in applications
      represented here as well as the HTTP application. If entries
      in this table overlap, these transactions may be summarized
```

```
      additional times.

      The contents of this table affect all reports and exceptions
      generated by this agent. Accordingly, modification of this
      table should be performed by a manager acting in the role of
      administrator. In particular, management software should not
      require or enforce particular configuration of this table - it
      should reflect the preferences of the site administrator, not
      the software author."
  ::= { apmMibObjects 4 }

apmHttpFilterEntry OBJECT-TYPE
  SYNTAX      ApmHttpFilterEntry
  MAX-ACCESS  not-accessible
   STATUS      current
  DESCRIPTION
     "A virtual application which measure the performance of certain
     web pages or sets of web pages."
  INDEX { apmHttpFilterIndex }
  ::= { apmHttpFilterTable 1 }

ApmHttpFilterEntry ::= SEQUENCE {
  apmHttpFilterIndex             Unsigned32,
  apmHttpFilterAppLocalIndex      AppLocalIndex,



  apmHttpFilterServerProtocol     Unsigned32,
  apmHttpFilterServerAddress      ProtocolDirNetworkAddress,
  apmHttpFilterURLPath           OCTET STRING,
  apmHttpFilterMatchType          INTEGER,
  apmHttpFilterOwner             OwnerString,
  apmHttpFilterStorageType        StorageType,
  apmHttpFilterRowStatus          RowStatus
}

apmHttpFilterIndex OBJECT-TYPE
  SYNTAX      Unsigned32 (0..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "An index that uniquely identifies an entry in the
     apmHttpFilterTable."
  ::= { apmHttpFilterEntry 1 }

apmHttpFilterAppLocalIndex
 OBJECT-TYPE
  SYNTAX      AppLocalIndex
```

```
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The AppLocalIndex that represents HTTP transactions
     that match this entry.

     This object is read-only. A value is created by the agent from
     an unused AppLocalIndex value when this apmHttpFilterEntry is
     created."
  ::= { apmHttpFilterEntry 2 }

apmHttpFilterServerProtocol OBJECT-TYPE
  SYNTAX      Unsigned32 (1..2147483647)
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The protocolDirLocalIndex value of the network level protocol
     of the apmHttpFilterServerAddress."
  ::= { apmHttpFilterEntry 3 }

apmHttpFilterServerAddress OBJECT-TYPE
  SYNTAX      ProtocolDirNetworkAddress
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This entry will only represent transactions coming from the
     network address specified in this object.




     This is represented
 as an octet string with
     specific semantics and length as identified
     by the associated apmHttpFilterServerProtocol object.

     If this object is the zero-length string, then this entry will
     match one of the addresses represented by the 'host' component
     of the associated apmHttpFilterURLPath object, where the
     format if a URL [9] is
     http://<host>:<port>/<path>?<searchpart>."
  ::= { apmHttpFilterEntry 4 }

apmHttpFilterURLPath OBJECT-TYPE
  SYNTAX      OCTET STRING (SIZE(0..65535))
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
```

"This entry will only represent HTTP transactions
where the URL path component in the request matches this
value. This value represents the requested path regardless of
any substitution that the server might perform.

Prior to the matching, the URL is stripped of any server
address or DNS name and consists solely of the path name on

that server.

If the length of this object is zero, then this entry will
match if the associated apmHttpFilterServerAddress match. If
the length of that object is also zero, then this entry will
match nothing.

The value of the associated apmHttpFilterMatchType dictates
the type of matching that will be attempted."
::= { apmHttpFilterEntry 5 }

apmHttpFilterMatchType OBJECT-TYPE
SYNTAX INTEGER {
exact(1),
stripTrailingSlash(2),
prefix(3)
}
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The matching algorithm used to compare the URL pathname.

If the value is exact(1), then the pathname component will be
compared with the associated apmHttpFilterURLPath and
will only be associated with this entry if it matches exactly.

If the value is stripTrailingSlash(2), then the pathname

component will be compared with the associated
apmHttpFilterURLPath and will only be associated with this
entry if it matches exactly or if the pathname ends with a '/'
symbol and matches apmHttpFilterURLPath if the '/' symbol is
removed from the pathname. This option exists for those paths
where an optional trailing slash is possible but for which a
prefix match would be too broad.

If the value is prefix(3), then the pathname component will be
compared with the associated apmHttpFilterURLPath and will

only be associated with this entry if the beginning of the
pathname matches every octet of this value. Octets that extend
beyond the length of this value are ignored."
::= { apmHttpFilterEntry 6 }

apmHttpFilterOwner OBJECT-TYPE
SYNTAX OwnerString
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The entity that configured this entry and is
therefore using
the resources assigned to it."
::= { apmHttpFilterEntry 7 }

apmHttpFilterStorageType OBJECT-TYPE
SYNTAX StorageType
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The storage type of this apmHttpFilterEntry. If the value of
this object is 'permanent', no objects in this row need to be
writable."
::= { apmHttpFilterEntry 8 }

apmHttpFilterRowStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The status of this apmHttpFilterEntry. No objects in this row
may be modified while the row's status is 'active'."
::= { apmHttpFilterEntry 9 }

apmHttpIgnoreUnregisteredURLs OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-write
STATUS current

DESCRIPTION
"When true, APM measurements of HTTP transactions will only
measure transactions relating to URLs that match a filter in
the apmHttpFilterTable. Thus,
measurements for the HTTP
application will present aggregated statistics for
URL-matching HTTP transactions and measurements for the HTTP

GET application verb will present aggregated statistics for
URL-matching HTTP GET transactions.

This will be used in environments that wish to monitor only
targeted URLs and to ignore large volumes of internet web
browsing traffic.

This object affects all APM reports and exceptions generated
by this agent. Accordingly, modification of this object should
be performed by a manager acting in the role of
administrator. In particular, management software should not
require or enforce particular configuration of this object -
it should reflect the preferences of the site administrator,
not the software author.

The value of this object must persist across reboots."
::= { apmMibObjects 5 }

apmHttp4xxIsFailure OBJECT-TYPE
SYNTAX
TruthValue
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"When true, this agent will recognize HTTP errors in the range
of 400 through 499 and will treat them as unavailable
transactions. When false or when this object isn't supported,
they will be treated as successful transactions.

This object allows such error pages to be tracked at the
possible expense of having user typos treated as poor service
on the part of the web server.

This object affects all reports and exceptions generated by
this agent. Accordingly, modification of this object should be
performed by a manager acting in the role of administrator. In
particular, management software should not require or enforce
particular configuration of this object - it should reflect
the preferences of the site administrator, not the software
author.

The value of this object must persist
across reboots."
::= { apmMibObjects 6 }

-- The APM User-Defined Application Table

```
-- Many application protocols will never be registered with a
-- standards body (and thus included in a protocol directory standard)
-- because they are custom, in-house or proprietary
-- applications. Nevertheless, implementation strategies exist for
-- monitoring the end-user experience of these applications.
--
-- This read-only table provides a means for the agent to advertise
-- which user-defined applications it is monitoring and to associate
-- each with an AppLocalIndex value. It is an implementation-dependent
-- matter as to how the agent learns how to monitor these
-- applications.

apmUserDefinedAppTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ApmUserDefinedAppEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A table that advertises user-defined applications that the
     agent is measuring.

     The agent will automatically create one or more
 entries in the
     apmAppDirTable (one for each responsivenessType it is
     capable of measuring) for each entry in this table.

     Note that when entries exist in this table some
     transactions can be summarized more than once if there is
     overlap between applications defined here and applications
     defined in the protocol directory or in the httpFilter table."
  ::= { apmMibObjects 7 }

apmUserDefinedAppEntry OBJECT-TYPE
  SYNTAX      ApmUserDefinedAppEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A user-defined application that the agent is measuring, along
     with its AppLocalIndex assignment.

     The apmAppDirAppLocalIndex value in the index identifies
     the agent-assigned AppLocalIndex value for this user-defined
     application."
  INDEX { apmAppDirAppLocalIndex }
  ::= { apmUserDefinedAppTable 1 }

ApmUserDefinedAppEntry ::= SEQUENCE {
  apmUserDefinedAppParentIndex    Unsigned32,
```

```
    apmUserDefinedAppApplication    SnmpAdminString
}

apmUserDefinedAppParentIndex OBJECT-TYPE
  SYNTAX      Unsigned32 (1..2147483647)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The protocolDirLocalIndex value of the highest-layer
     protocol defined in the protocolDirTable that this
     application is a child of."
  ::= { apmUserDefinedAppEntry 1 }

apmUserDefinedAppApplication OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "A human readable descriptive tag for this application."
  ::= { apmUserDefinedAppEntry 2 }

-- The APM Name Table

apmNameTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ApmNameEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A client machine may have multiple addresses during a period
     of monitoring. The apmNameTable assigns a long-lived
     identifier to a client and records what addresses
 were
     assigned to that client for periods of time. Various
     implementation techniques exist for tracking this mapping but
     if an agent is unable to track client address mappings, it may
     map client identifiers to client addresses rather than to
     distinct client machines.

     A particular apmNameClientID should be a constant attribute of
     a particular client. When available, the agent may also record
     the machine name and/or user name which may be valuable for
     displaying to humans. The apmNameMachineName and
     apmNameUserName are relatively constant, changing only if
     these attributes actually change on the client.
```

The agent will store a historical log of these entries, aging
out old entries as the log becomes too large. Since this table
contains information vital to the interpretation of other
tables (e.g., the apmReportTable), the agent should ensure that

the log doesn't
age out entries that would be referenced by
data in those tables.

Note that an entry for a clientID is active from its
StartTime until the StartTime of another entry (for the same
clientID) that supersedes it, or 'now' if none supersede
it. Therefore, if a clientID only has a single entry, it is by
definition very new and should never be aged out. No entry for
a clientID should be aged out unless it has been updated by a
new entry for the client (i.e., with an updated address) and
only if the new entry is 'old' enough.

To determine how old is old enough, compute the maximum value
of Interval * (NumReports + 1) of all entries in the
apmReportControlTable (the '+ 1' is to allow a reasonable
period of time for the report to be downloaded). Then take the
larger of this value and the age in seconds of the oldest
entry in the current transaction table. If an entry for
a
clientID is superseded by another entry whose StartTime is
more than this many seconds ago, then the older entry may be
deleted."
::= { apmMibObjects 8 }

apmNameEntry OBJECT-TYPE
SYNTAX ApmNameEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"An entry in the APM name table. An entry exists for each
period of time that a client has been associated with a
particular address.

The protocolDirLocalIndex value in the index identifies
the network layer protocol for the ClientAddress for this
entry.

Note that some combinations of index values may result in an
index that exceeds 128 sub-identifiers in length which exceeds
the maximum for the SNMP protocol. Implementations should take

```
      care to avoid such combinations."
  INDEX { apmNameClientID,
          protocolDirLocalIndex, apmNameClientAddress,
          apmNameMappingStartTime }
  ::=
 { apmNameTable 1 }

ApmNameEntry ::= SEQUENCE {
  apmNameClientID               RmonClientID,
  apmNameClientAddress          ProtocolDirNetworkAddress,



  apmNameMappingStartTime       DateAndTime,
  apmNameMachineName            SnmpAdminString,
  apmNameUserName               SnmpAdminString
}

apmNameClientID OBJECT-TYPE
  SYNTAX      RmonClientID
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A unique ID assigned to the machine represented by this
      mapping. This ID is assigned by the agent using an
      implementation-specific algorithm."
  ::= { apmNameEntry 1 }

apmNameClientAddress OBJECT-TYPE
  SYNTAX      ProtocolDirNetworkAddress (SIZE(1..255))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The network client address for this client when this mapping
     was active.

     This is represented as an octet string with specific semantics
     and length as
 identified by the protocolDirLocalIndex
     component of the index. This object may not be the zero length
     string.

     Since this object is an index variable, it is encoded in the
     index according to the index encoding rules.  For example, if
     the protocolDirLocalIndex component of the index indicates an
     encapsulation of ip, this object is encoded as a length octet
     of 4, followed by the 4 octets of the ip address, in network
     byte order. Care should be taken to avoid values of this
```

```
      object that, in conjunction with the other index variables,
      would result in an index longer than SNMP's maximum of 128
      subidentifiers."
   ::= { apmNameEntry 2 }

apmNameMappingStartTime OBJECT-TYPE
   SYNTAX      DateAndTime
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "The time that the agent first discovered this mapping
      as active."
   ::= { apmNameEntry 3 }




apmNameMachineName OBJECT-TYPE
    SYNTAX      SnmpAdminString
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The human readable name of the client machine.

      If the client has no machine name or the agent is
      unable to learn the machine name, this object will be
      a zero-length string."
   ::= { apmNameEntry 4 }

apmNameUserName OBJECT-TYPE
   SYNTAX      SnmpAdminString
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The human readable name of a human user using the client
      machine. If more than one user name are available
      simultaneously, it is an implementation-dependent matter as to
      which is used here. However, if the user name changes, this
      object should change to reflect that change.

      Non-human user names like 'root' or 'administrator' aren't
      intended as values for this object. If the client has no
      recorded user name or the agent is unable to learn a user
      name, this
 object will be a zero-length string."
   ::= { apmNameEntry 5 }

-- The APM Report Group
```

```
apmReportControlTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ApmReportControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "Parameters that control the creation of a set of reports that
     aggregate application performance."
  ::= { apmMibObjects 9 }

apmReportControlEntry OBJECT-TYPE
  SYNTAX      ApmReportControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A conceptual row in the apmReportControlTable.

     An example of the indexing of this table is




     apmReportControlInterval.3"
  INDEX { apmReportControlIndex }
  ::= { apmReportControlTable 1 }

ApmReportControlEntry ::= SEQUENCE {
  apmReportControlIndex           Unsigned32,
  apmReportControlDataSource      DataSourceOrZero,
  apmReportControlAggregationType  TransactionAggregationType,
  apmReportControlInterval
 Unsigned32,
  apmReportControlRequestedSize    Unsigned32,
  apmReportControlGrantedSize      Unsigned32,
  apmReportControlRequestedReports Unsigned32,
  apmReportControlGrantedReports   Unsigned32,
  apmReportControlStartTime        TimeStamp,
  apmReportControlReportNumber     Unsigned32,
  apmReportControlDeniedInserts    Counter32,
  apmReportControlDroppedFrames    Counter32,
  apmReportControlOwner           OwnerString,
  apmReportControlStorageType      StorageType,
  apmReportControlStatus          RowStatus
}


apmReportControlIndex OBJECT-TYPE
  SYNTAX      Unsigned32 (1..65535)
  MAX-ACCESS  not-accessible
```

```
  STATUS      current
  DESCRIPTION
     "An index that uniquely identifies an entry in the
     apmReportControlTable.  Each such entry defines a unique
     report whose results are placed in the apmReportTable on
     behalf of this apmReportControlEntry."
  ::= { apmReportControlEntry 1 }

apmReportControlDataSource OBJECT-TYPE
   SYNTAX      DataSourceOrZero
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The source of the data for APM Reports generated on
     behalf of this apmReportControlEntry.

     If the measurement is being performed by a probe, this should
     be set to interface or port where data was received for
     analysis. If the measurement isn't being performed by a probe,
     this should be set to the primary interface over which the
     measurement is being performed. If the measurement isn't being
     performed by a probe and there is no primary interface or this



     information isn't known, this object should be set to 0.0.

     This object may not be modified if the associated
     apmReportControlStatus object is equal to active(1)."
  ::= { apmReportControlEntry 2 }

apmReportControlAggregationType OBJECT-TYPE
  SYNTAX      TransactionAggregationType
        --    INTEGER {
        --      flows(1),
         --      clients(2),
        --      servers(3),
        --      applications(4)
        --    }
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The type of aggregation being performed for this set of
     reports.

     The metrics for a single transaction are the responsiveness of
     the transaction and whether the transaction succeeded (a
     boolean). When such metrics are aggregated in this MIB Module,
```

these metrics are replaced by averages and distributions of responsiveness and availability. The metrics describing aggregates are constant no matter which type of aggregation is being performed. These metrics may be found in the apmReportTable.

The flows(1) aggregation is the simplest. All transactions that share common application/server/client 3-tuples are aggregated together, resulting in a set of metrics for all such unique 3-tuples.

The clients(2) aggregation results in somewhat more aggregation (i.e., fewer resulting records). All transactions that share common application/client tuples are aggregated together, resulting in a set of metrics for all such unique tuples.

The servers(3) aggregation usually results in still more aggregation (i.e., fewer resulting records). All transactions that share common application/server tuples are aggregated together, resulting in a set of metrics for all such unique tuples.

The applications(4) aggregation results in the most aggregation (i.e., the fewest resulting records). All

transactions that share a common application are aggregated together, resulting in a set of metrics for all such unique applications.

Note that it is not meaningful to aggregate applications, as different applications have widely varying characteristics. As
a result, this set of aggregations is complete.

This object may not be modified if the associated apmReportControlStatus object is equal to active(1)."
::= { apmReportControlEntry 3 }

apmReportControlInterval OBJECT-TYPE
SYNTAX Unsigned32
UNITS "Seconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The interval in seconds over which data is accumulated before

being aggregated into a report in the apmReportTable. All
reports with the same apmReportControlIndex will be based on
the same interval. This object must be greater than zero.

Many users desire that these reports be synchronized to within
seconds of the beginning of the hour because the results may
be correlated more meaningfully to business behavior and so
that data from multiple agents is aggregated over the same
time periods. Thus management software may take extra effort
to synchronize
reports to the beginning of the hour and to one
another. However, the agent must not allow reports to 'drift'
over time as they will quickly become unsynchronized. In
particular, if there is any fixed processing delay between
reports, the reports should deduct this time from the interval
so that reports don't drift.

This object may not be modified if the associated
apmReportControlStatus object is equal to active(1)."
::= { apmReportControlEntry 4 }

apmReportControlRequestedSize OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The number of entries requested to be allocated for each
report generated on behalf of this entry."
::= { apmReportControlEntry 5 }

apmReportControlGrantedSize OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of entries per
report the agent has allocated
based on the requested amount in apmReportControlRequestedSize.
Since multiple reports are saved, the total number of entries
allocated will be this number multiplied by the value of
apmReportControlGrantedReports, or 1 if that object doesn't
exist.

When the associated apmReportControlRequestedSize object is
created or modified, the agent should set this object as

```
      closely to the requested value as is possible for the
      particular implementation and available resources. When
      considering resources available, the agent must consider its
      ability to allocate this many entries for all reports.

      Note that while the actual number of entries stored in the
      reports may fluctuate due to changing conditions, the agent
      must continue to have storage available to satisfy the full
      report size for all reports when necessary. Further, the agent
      must
 not lower this value except as a result of a set to the
      associated apmReportControlRequestedSize object."
  ::= { apmReportControlEntry 6 }

apmReportControlRequestedReports OBJECT-TYPE
  SYNTAX      Unsigned32 (0..65535)
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "The number of saved reports requested to be allocated on
      behalf of this entry."
  ::= { apmReportControlEntry 7 }

apmReportControlGrantedReports OBJECT-TYPE
  SYNTAX      Unsigned32 (0..65535)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The number of saved reports the agent has allocated
      based on the requested amount in
      apmReportControlRequestedReports. Since each report can have
      many entries, the total number of entries allocated will be
      this number multiplied by the value of
      apmReportControlGrantedSize, or 1 if that object doesn't
      exist.



      When the associated apmReportControlRequestedReports
 object is
      created or modified, the agent should set this object as
      closely to the requested value as is possible for the
      particular implementation and available resources. When
      considering resources available, the agent must consider its
      ability to allocate this many reports each with the number of
      entries represented by apmReportControlGrantedSize, or 1 if
      that object doesn't exist.
```

```
      Note that while the storage required for each report may
      fluctuate due to changing conditions, the agent must continue
      to have storage available to satisfy the full report size for
      all reports when necessary. Further, the agent must not lower
      this value except as a result of a set to the associated
      apmReportControlRequestedSize object."
   ::= { apmReportControlEntry 8 }

apmReportControlStartTime OBJECT-TYPE
   SYNTAX      TimeStamp
   MAX-ACCESS  read-only
   STATUS      current

   DESCRIPTION
      "The value of sysUpTime when the system began processing the
      report in progress. Note that the report in progress is not
      available.

      This object may be used by the management station to figure
      out the start time for all previous reports saved for this
      apmReportControlEntry, as reports are started at fixed
      intervals."
   ::= { apmReportControlEntry 9 }

apmReportControlReportNumber OBJECT-TYPE
   SYNTAX      Unsigned32 (1..4294967295)
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The number of the report in progress. When an
      apmReportControlEntry is activated, the first report will be
      numbered one."
   ::= { apmReportControlEntry 10 }

apmReportControlDeniedInserts OBJECT-TYPE
   SYNTAX      Counter32
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The number of failed attempts to add an entry to reports for




      this apmReportControlEntry
 because the number of entries
      would have exceeded apmReportControlGrantedSize.

      This number is valuable in determining if enough entries have
```

been allocated for reports in light of fluctuating network
usage. Note that since an entry that is denied will often be
attempted again, this number will not predict the exact number
of additional entries needed, but can be used to understand
the relative magnitude of the problem.

Also note that there is no ordering specified for the entries
in the report, thus there are no rules for which entries will
be omitted when not enough entries are available. As a
consequence, the agent is not required to delete 'least
valuable' entries first."
::= { apmReportControlEntry 11 }

apmReportControlDroppedFrames OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The total number of frames which were
received by the agent
and therefore not accounted for in the *StatsDropEvents, but
for which the agent chose not to count for this entry for
whatever reason. Most often, this event occurs when the agent
is out of some resources and decides to shed load from this
collection.

This count does not include packets that were not counted
because they had MAC-layer errors.

This counter is only relevant if this apm report is based on
a data source whose collection methodology is based on
analyzing network traffic.

Note that if the apmReportTables are inactive because no
applications are enabled in the application directory, this
value should be 0.

Note that, unlike the dropEvents counter, this number is the
exact number of frames dropped."
::= { apmReportControlEntry 12 }

apmReportControlOwner OBJECT-TYPE
SYNTAX OwnerString
MAX-ACCESS read-create

STATUS current

```
  DESCRIPTION
     "The entity that configured this entry and is
     therefore using the resources assigned to it."
  ::= { apmReportControlEntry 13 }

apmReportControlStorageType OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The storage type of this apmReportControlEntry. If the value
     of this object is 'permanent', no objects in this row need to
     be writable."
  ::= { apmReportControlEntry 14 }

apmReportControlStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The status of this apmReportControlEntry.

     An entry may not exist in the active state unless all
     objects in the entry have an appropriate value. The only
     objects in the entry that may be modified while the entry is
     in the active state are apmReportControlRequestedSize and
     apmReportControlRequestedReports.

      If this object is not equal to active(1), all
     associated entries in the apmReportTable shall be deleted
     by the agent."
  ::= { apmReportControlEntry 15 }

-- The APM Report Table

apmReportTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ApmReportEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The data resulting from aggregated APM reports. Consult the
     definition of apmReportControlAggregationType for the
     definition of the various types of aggregations."
  ::= { apmMibObjects 10 }

apmReportEntry OBJECT-TYPE
  SYNTAX      ApmReportEntry
```

MAX-ACCESS not-accessible

STATUS current
DESCRIPTION
"A conceptual row in the apmReportTable.
The apmReportControlIndex value in the index identifies the
apmReportControlEntry on whose behalf this entry was created.
The apmReportIndex value in the index identifies which report
(in the series of reports) this
entry is a part of.
The apmAppDirAppLocalIndex value in the index identifies
the common application of the transactions aggregated in this
entry.
The apmAppDirResponsivenessType value in the index
identifies the type of responsiveness metric reported by
this entry and uniquely identifies this entry when more
than one responsiveness metric is measured for a flow.
Entries will only exist in this table for those
combinations of AppLocalIndex and ResponsivenessType
that are configured 'on(1)'.
The protocolDirLocalIndex value in the index identifies
the network layer protocol of the apmReportServerAddress.
When the associated apmReportControlAggregationType value is
equal to applications(4) or clients(2), this
protocolDirLocalIndex value will equal 0.
The apmReportServerAddress value in the index identifies the
network layer address of the server in transactions
aggregated
in this entry.
The apmNameClientID value in the index identifies the
client in transactions aggregated in this entry. If the
associated apmReportControlAggregationType is equal to
applications(4) or servers(3), then this protocolDirLocalIndex
value will equal 0.

An example of the indexing of this entry is
apmReportTransactionCount.3.15.3.1.8.4.192.168.1.2.3232235788

Note that some combinations of index values may result in an
index that exceeds 128 sub-identifiers in length which exceeds
the maximum for the SNMP protocol. Implementations should take
care to avoid such combinations."
INDEX { apmReportControlIndex, apmReportIndex,
apmAppDirAppLocalIndex,
apmAppDirResponsivenessType,
protocolDirLocalIndex, apmReportServerAddress,

```
        apmNameClientID }
  ::= { apmReportTable 1 }

ApmReportEntry ::= SEQUENCE {
  apmReportIndex
              Unsigned32,
  apmReportServerAddress         ProtocolDirNetworkAddress,



  apmReportTransactionCount      Unsigned32,
  apmReportSuccessfulTransactions Unsigned32,
  apmReportResponsivenessMean    Unsigned32,
  apmReportResponsivenessMin     Unsigned32,
  apmReportResponsivenessMax     Unsigned32,
  apmReportResponsivenessB1      Unsigned32,
  apmReportResponsivenessB2      Unsigned32,
  apmReportResponsivenessB3      Unsigned32,
  apmReportResponsivenessB4      Unsigned32,
  apmReportResponsivenessB5      Unsigned32,
  apmReportResponsivenessB6      Unsigned32,
  apmReportResponsivenessB7      Unsigned32
}

apmReportIndex OBJECT-TYPE
  SYNTAX      Unsigned32 (1..4294967295)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The value of apmReportControlReportNumber for the report to
     which this entry belongs."
  ::= { apmReportEntry 1 }

apmReportServerAddress OBJECT-TYPE
  SYNTAX
    ProtocolDirNetworkAddress
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The network server address for this apmReportEntry.

     This is represented as an octet string with
     specific semantics and length as identified
     by the protocolDirLocalIndex component of the index.

     Since this object is an index variable, it is encoded in the
     index according to the index encoding rules.  For example, if
     the protocolDirLocalIndex indicates an encapsulation of ip,
```

```
      this object is encoded as a length octet of 4, followed by the
      4 octets of the ip address, in network byte order. Care
      should be taken to avoid values of this object that, in
      conjunction with the other index variables, would result in an
      index longer than SNMP's maximum of 128 subidentifiers.

      If the associated apmReportControlAggregationType is equal to
      applications(4) or clients(2), then this object will
 be a null
      string and will be encoded simply as a length octet of 0."
  ::= { apmReportEntry 2 }



apmReportTransactionCount OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The total number of transactions aggregated into this record."
  ::= { apmReportEntry 3 }

apmReportSuccessfulTransactions OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The total number of successful transactions aggregated into
     this record."
  ::= { apmReportEntry 4 }

apmReportResponsivenessMean OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The arithmetic mean of the responsiveness metrics for all
     successful transactions aggregated into this record."
  ::= { apmReportEntry 5 }

apmReportResponsivenessMin OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS
   current
  DESCRIPTION
     "The minimum of the responsiveness metrics for all
```

```
      successful transactions aggregated into this record."
   ::= { apmReportEntry 6 }

apmReportResponsivenessMax OBJECT-TYPE
   SYNTAX      Unsigned32
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The maximum of the responsiveness metrics for all
      successful transactions aggregated into this record."
   ::= { apmReportEntry 7 }

-- Note that when updating a report entry, a transaction will not be
-- counted in more than 1 bucket in an entry. It will be counted in
-- the first bucket that matches, starting with Bucket 1 (B1). Note
-- that if a transaction matches 2 application types, it will update



-- one bucket in each of 2 entries in this table.

apmReportResponsivenessB1 OBJECT-TYPE
   SYNTAX      Unsigned32
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The number of successful transactions aggregated into this
      record
  whose responsiveness was less than boundary1 value for
      this application."
   ::= { apmReportEntry 8 }

apmReportResponsivenessB2 OBJECT-TYPE
   SYNTAX      Unsigned32
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The number of successful transactions aggregated into this
      record whose responsiveness did not fall into Bucket 1 and was
      greater than or equal to the boundary1 value for this
      application and less than the boundary2 value for this
      application."
   ::= { apmReportEntry 9 }

apmReportResponsivenessB3 OBJECT-TYPE
   SYNTAX      Unsigned32
   MAX-ACCESS  read-only
   STATUS      current
```

```
  DESCRIPTION
     "The number of successful transactions aggregated into this
     record whose responsiveness did not fall into Bucket 1 or 2
     and as greater than or equal to the boundary2 value for this
     application and less than the boundary3 value for this
     application."
  ::= { apmReportEntry
 10 }

apmReportResponsivenessB4 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of successful transactions aggregated into this
     record whose responsiveness did not fall into Buckets 1
     through 3 and was greater than or equal to the boundary3 value
     for this application and less than the boundary4 value for
     this application."
  ::= { apmReportEntry 11 }




apmReportResponsivenessB5 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of successful transactions aggregated into this
     record whose responsiveness did not fall into Buckets 1
     through 4 and was greater than or equal to the boundary4 value
     for this application and less than the boundary5 value for
     this application."
  ::= { apmReportEntry 12 }

apmReportResponsivenessB6 OBJECT-TYPE
  SYNTAX      Unsigned32
   MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of successful transactions aggregated into this
     record whose responsiveness did not fall into Buckets 1
     through 5 and was greater than or equal to the
     boundary5 value for this application and less than the
     boundary6 value for this application."
  ::= { apmReportEntry 13 }
```

```
apmReportResponsivenessB7 OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of successful transactions aggregated into this
     record whose responsiveness did not fall into Buckets 1
     through 6 and was greater than or equal to the boundary6 value
     for this application."
  ::= { apmReportEntry 14 }

-- APM Transaction Table

apmTransactionTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ApmTransactionEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "This table contains transactions
 that are currently running
     or have recently finished."
  ::= { apmMibObjects 11 }

apmTransactionEntry OBJECT-TYPE
  SYNTAX      ApmTransactionEntry



  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A conceptual row in the apmTransactionTable.

     The apmAppDirAppLocalIndex value in the index identifies
     the application of the transaction represented by this entry.
     The apmAppDirResponsivenessType value in the index
     identifies the type of responsiveness metric reported by
     this entry and uniquely identifies this entry when more
     than one responsiveness metric is measured for a flow.
     Entries will only exist in this table for those
     combinations of AppLocalIndex and ResponsivenessType
     that are configured 'on(1)'.
     The protocolDirLocalIndex value in the index identifies
     the network layer protocol of the apmTransactionServerAddress.
     The apmTransactionServerAddress
 value in the index identifies
     the network layer address of the server in the transaction
     represented by this entry.
```

```
      The apmNameClientID value in the index identifies the
      client in the transaction represented by this entry.

      An example of the indexing of this entry is
      apmTransactionCount.3.1.8.4.192.168.1.2.3232235788.2987

      Note that some combinations of index values may result in an
      index that exceeds 128 sub-identifiers in length which exceeds
      the maximum for the SNMP protocol. Implementations should take
      care to avoid such combinations."
    INDEX { apmAppDirAppLocalIndex,
            apmAppDirResponsivenessType,
            protocolDirLocalIndex, apmTransactionServerAddress,
            apmNameClientID, apmTransactionID }
    ::= { apmTransactionTable 1 }

ApmTransactionEntry ::= SEQUENCE {
    apmTransactionServerAddress      ProtocolDirNetworkAddress,
    apmTransactionID
   Unsigned32,
    apmTransactionResponsiveness     Unsigned32,
    apmTransactionAge                TimeInterval,
    apmTransactionSuccess            TruthValue
}

apmTransactionServerAddress OBJECT-TYPE
    SYNTAX      ProtocolDirNetworkAddress (SIZE (1..255))
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION



      "The network server address for this apmTransactionEntry.

      This is represented as an octet string with specific semantics
      and length as identified by the protocolDirLocalIndex
      component of the index. This object may not be the zero length
      string.

      For example, if the protocolDirLocalIndex indicates an
      encapsulation of ip, this object is encoded as a length octet
      of 4, followed by the 4 octets of the ip address, in network
      byte order. Care should be taken to avoid values of this
      object that, in conjunction with the other index variables,
      would result in an index longer than
   SNMP's maximum of 128
      subidentifiers."
```

```
  ::= { apmTransactionEntry 1 }

apmTransactionID OBJECT-TYPE
  SYNTAX      Unsigned32 (0..4294967295)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A unique value for this transaction amongst other
     transactions sharing the same application layer protocol and
     server and client addresses. Implementations may choose to use
     the value of the client's source port, when possible."
  ::= { apmTransactionEntry 2 }

apmTransactionResponsiveness OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The current value of the responsiveness metric for this
     transaction. If this transaction has completed, the final
     value of the metric will be available.

     Note that this value may change over the lifetime of the
     transaction and it is the final value of this metric that is
     recorded as the responsiveness
 of the transaction for use in
     other APM MIB functions."
  ::= { apmTransactionEntry 3 }

apmTransactionAge OBJECT-TYPE
  SYNTAX      TimeInterval
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "If this transaction is still executing, this value shall be




     the length of time since it was started. If it has completed,
     this value shall be the length of time it was executing."
  ::= { apmTransactionEntry 4 }

apmTransactionSuccess OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The success of this transaction up to this time. Once a
```

```
      transaction has been marked as failed, it cannot move back
      into the successful state."
  ::= { apmTransactionEntry 5 }

apmTransactionsRequestedHistorySize OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
      "The maximum number of completed transactions
 desired to be
      retained in the apmTransactionTable. If the agent doesn't have
      enough resources to retain this many, it will retain as many as
      possible. Regardless of this value, the agent must attempt to
      keep records for all current transactions it is monitoring.

      The value of this object must persist across reboots."
  ::= { apmMibObjects 12 }

-- The APM Exception table
-- The APM Exception Table creates filters so that a management
-- station can get immediate notification of a transaction that has
-- had poor availability or responsiveness.
--
-- This function is particularly helpful in unaggregated situations
-- where the numbers of agents is relatively high and the transaction
-- rate per agent is relatively low (such as agents for desktops or
-- dedicated to small workgroups). Polling agents in such an
-- environment would either cause scalability problems (high rate) or
-- lead to long notification delays (low rate).


apmExceptionTable
 OBJECT-TYPE
  SYNTAX      SEQUENCE OF ApmExceptionEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "This table creates filters so that a management station can
      get immediate notification of a transaction that has had poor



      availability or responsiveness.

      Each apmExceptionEntry is associated with a particular type of
      transaction and is applied to all transactions of that
      type. Multiple apmExceptionEntries may be associated with a
```

```
      particular type of transaction. A transaction type is
      identified by the value of the apmAppDirAppLocalIndex
      component of the index.

      Because the quality of a transaction is not known until it is
      completed, these thresholds are only applied after the
      transaction has completed."
  ::= { apmMibObjects 13 }

apmExceptionEntry OBJECT-TYPE
  SYNTAX      ApmExceptionEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A conceptual row in the apmExceptionTable.

      The apmAppDirAppLocalIndex value in the index identifies
      the application this entry will monitor.
      The apmAppDirResponsivenessType value in the index
      identifies the type of responsiveness metric this entry will
      monitor."

  INDEX { apmAppDirAppLocalIndex,
          apmAppDirResponsivenessType, apmExceptionIndex }
  ::= { apmExceptionTable 1 }

ApmExceptionEntry ::= SEQUENCE {
  apmExceptionIndex                    Unsigned32,
  apmExceptionResponsivenessComparison    INTEGER,
  apmExceptionResponsivenessThreshold     Unsigned32,
  apmExceptionUnsuccessfulException       INTEGER,
  apmExceptionResponsivenessEvents        Counter32,
  apmExceptionUnsuccessfulEvents          Counter32,
  apmExceptionOwner                    OwnerString,
  apmExceptionStorageType                 StorageType,
  apmExceptionStatus                   RowStatus
}

apmExceptionIndex
 OBJECT-TYPE
  SYNTAX      Unsigned32 (1..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION



      "An index that uniquely identifies an entry in the
```

```
      apmExceptionTable amongst other entries with equivalent index
      values for apmAppDirAppLocalIndex and
      apmAppDirResponsivenessType. Each such entry sets up
      thresholds for a particular measurement of a particular
      application."
    ::= { apmExceptionEntry 1 }

apmExceptionResponsivenessComparison OBJECT-TYPE
    SYNTAX      INTEGER {
                  none(1),
                  greater(2),
                  less(3)
                }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "If this value is greater(2) or less(3), the associated
      apmExceptionResponsivenessThreshold will be compared to this
      value and an exception will be created if the responsiveness
      is greater than the threshold (greater(2)) or less than the
       threshold (less(3))."
    ::= { apmExceptionEntry 2 }

apmExceptionResponsivenessThreshold OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "The threshold that responsiveness metrics are compared to."
    ::= { apmExceptionEntry 3 }

apmExceptionUnsuccessfulException OBJECT-TYPE
    SYNTAX      INTEGER {
                  off(1),
                  on(2)
                }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "If this value is on(2), an exception will be created if a
      transaction of the associated type is unsuccessful."
    ::= { apmExceptionEntry 4 }

apmExceptionResponsivenessEvents OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
```

```
  DESCRIPTION
     "The total number of responsiveness exceptions generated. This
     counter will be incremented even if no notification was sent
     due to notifications not being
 configured or due to exceeding
     the apmNotificationMaxRate value."
  ::= { apmExceptionEntry 5 }

apmExceptionUnsuccessfulEvents OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The total number of unsuccessful exceptions generated. This
     counter will be incremented even if no notification was sent
     due to notifications not being configured or due to exceeding
     the apmNotificationMaxRate value."
  ::= { apmExceptionEntry 6 }

apmExceptionOwner OBJECT-TYPE
  SYNTAX      OwnerString
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The entity that configured this entry and is
     therefore using the resources assigned to it."
  ::= { apmExceptionEntry 7 }

apmExceptionStorageType OBJECT-TYPE
  SYNTAX     StorageType
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "The storage type of this apmReportControlEntry. If the value

    of this object is 'permanent', no objects in this row need to
     be writable."
  ::= { apmExceptionEntry 8 }

apmExceptionStatus OBJECT-TYPE
  SYNTAX     RowStatus
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "The status of this apmExceptionEntry. The only objects in the
     entry that may be modified while the entry is in the active
```

state are apmExceptionResponsivenessComparison,
apmExceptionResponsivenessThreshold and
apmExceptionUnsuccessfulException."
::= { apmExceptionEntry 9 }

apmThroughputExceptionMinTime OBJECT-TYPE
SYNTAX Unsigned32
UNITS "seconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"Because the responsiveness for throughput-oriented
transactions is divided by the elapsed time, it can be very
sensitive to short-term performance variations for
transactions that take a short period of time. For example,
when downloading
a very short file, a single dropped packet
could double or triple the total response time.

Further, throughput is usually examined for applications that
transfer a lot of data, and when doing so it is helpful to
conceptualize transaction costs that are proportional to the
amount of data separately from those costs that are relatively
fixed (i.e., independent of the amount of data). For very
short transactions, these fixed transaction costs (handshake,
setup time, authentication, round-trip time) may dominate the
total response time for the transaction, resulting in
throughput measurements that aren't really proportional to the
network's, server's and client's combined data throughput
capability.

This object controls the minimum number of seconds that an
throughput-based transaction must exceed before an exception
can be generated for it. If this object is set
to zero, then
all throughput-based transactions are candidates for
exceptions.

The value of this object must persist across reboots."
DEFVAL { 10 }
::= { apmMibObjects 14 }

apmNotificationMaxRate OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-write
STATUS current

```
  DESCRIPTION
      "The maximum number of notifications that can be generated
      from this agent by the apmExceptionTable in any 60 second
      period.

      The value of this object must persist across reboots."
  DEFVAL { 1 }
  ::= { apmMibObjects 15 }




-- APM Notifications

apmNotifications OBJECT IDENTIFIER ::= { apm 0 }

apmTransactionResponsivenessAlarm NOTIFICATION-TYPE
  OBJECTS     { apmExceptionResponsivenessThreshold,
                apmTransactionResponsiveness }
  STATUS      current
  DESCRIPTION
      "Notification sent when a transaction exceeds a threshold
      defined in the apmException table. The index of the

      included apmExceptionResponsivenessThreshold object identifies
      the apmExceptionEntry that specified the threshold. The
      apmTransactionResponsiveness variable identifies the actual
      transaction and its responsiveness.

      Agent implementors are urged to include additional data
      objects in the alarm that may explain the reason for the
      alarm. It is helpful to include such data in the alarm because
      it describes the situation at the time the alarm was
      generated, where polls after the fact may not provide
      meaningful information. Examples of such information are CPU
      load, memory utilization, network utilization, and transaction
      statistics."
  ::= { apmNotifications 1 }

apmTransactionUnsuccessfulAlarm NOTIFICATION-TYPE
  OBJECTS     { apmExceptionResponsivenessThreshold }
  STATUS      current
  DESCRIPTION
      "Notification sent when a transaction is unsuccessful.
      The index of the included
 apmExceptionResponsivenessThreshold
      object identifies both the type of the transaction that caused
      this notification as well as the apmExceptionEntry that
```

```
      specified the threshold.

      Agent implementors are urged to include additional data
      objects in the alarm that may explain the reason for the
      alarm. It is helpful to include such data in the alarm because
      it describes the situation at the time the alarm was
      generated, where polls after the fact may not provide
      meaningful information. Examples of such information are CPU
      load, memory utilization, network utilization, and transaction
      statistics."
    ::= { apmNotifications 2 }

apmCompliance MODULE-COMPLIANCE
    STATUS  current



    DESCRIPTION
      "Describes the requirements for conformance to
      the APM MIB"
    MODULE  -- this module
      MANDATORY-GROUPS { apmAppDirGroup, apmReportGroup }

      GROUP apmUserDefinedApplicationsGroup
        DESCRIPTION
          "Implementation of the apmUserDefinedApplicationsGroup
          is optional."

      GROUP apmTransactionGroup
        DESCRIPTION
          "Implementation of the apmTransactionGroup is optional."

      GROUP apmExceptionGroup
        DESCRIPTION
          "Implementation of the apmExceptionGroup is optional."

      GROUP apmNotificationGroup
        DESCRIPTION
          "Implementation of the apmNotificationGroup is optional."

    ::= { apmCompliances 1 }

apmAppDirGroup OBJECT-GROUP
    OBJECTS { apmAppDirConfig,
              apmAppDirResponsivenessBoundary1,
              apmAppDirResponsivenessBoundary2,
              apmAppDirResponsivenessBoundary3,
              apmAppDirResponsivenessBoundary4,
```

```
            apmAppDirResponsivenessBoundary5,
            apmAppDirResponsivenessBoundary6,
            apmBucketBoundaryLastChange, apmAppDirID,
            apmNameMachineName, apmNameUserName }
    STATUS
    current
    DESCRIPTION
       "The APM MIB directory of applications and application verbs."
    ::=  { apmGroups 1 }

apmUserDefinedApplicationsGroup OBJECT-GROUP
    OBJECTS {     apmHttpFilterAppLocalIndex,
                  apmHttpFilterServerProtocol,
                  apmHttpFilterServerAddress, apmHttpFilterURLPath,
                  apmHttpFilterMatchType, apmHttpFilterOwner,
                  apmHttpFilterStorageType, apmHttpFilterRowStatus,
                  apmHttpIgnoreUnregisteredURLs, apmHttp4xxIsFailure,
                  apmUserDefinedAppParentIndex,




                  apmUserDefinedAppApplication }
    STATUS  current
    DESCRIPTION
       "Objects used for creating and managing user-defined
       applications."
    ::= { apmGroups 2 }

apmReportGroup OBJECT-GROUP
    OBJECTS { apmReportControlDataSource,
              apmReportControlAggregationType,
              apmReportControlInterval,
              apmReportControlRequestedSize,
              apmReportControlGrantedSize,
               apmReportControlRequestedReports,
              apmReportControlGrantedReports,
              apmReportControlStartTime,
              apmReportControlReportNumber,
              apmReportControlDeniedInserts,
              apmReportControlDroppedFrames,
              apmReportControlOwner,
              apmReportControlStorageType,
              apmReportControlStatus,
              apmReportTransactionCount,
              apmReportSuccessfulTransactions,
              apmReportResponsivenessMean,
              apmReportResponsivenessMin,
              apmReportResponsivenessMax,
```

```
            apmReportResponsivenessB1,
            apmReportResponsivenessB2,
            apmReportResponsivenessB3,
            apmReportResponsivenessB4,
            apmReportResponsivenessB5,
            apmReportResponsivenessB6,
            apmReportResponsivenessB7 }
    STATUS  current
    DESCRIPTION
        "The apm report group controls the creation
   and retrieval of
        reports that aggregate application performance."
    ::=  { apmGroups 3 }

apmTransactionGroup OBJECT-GROUP
    OBJECTS { apmTransactionResponsiveness,
              apmTransactionAge, apmTransactionSuccess,
              apmTransactionsRequestedHistorySize }
    STATUS  current
    DESCRIPTION
        "The apm transaction group contains statistics for
        individual transactions."



    ::=  { apmGroups 4 }

apmExceptionGroup OBJECT-GROUP
    OBJECTS { apmExceptionResponsivenessComparison,
              apmExceptionResponsivenessThreshold,
              apmExceptionUnsuccessfulException,
              apmExceptionResponsivenessEvents,
              apmExceptionUnsuccessfulEvents,
              apmExceptionOwner, apmExceptionStorageType,
              apmExceptionStatus, apmThroughputExceptionMinTime,
              apmNotificationMaxRate }
    STATUS  current
    DESCRIPTION
        "The apm exception group causes notifications to be sent
        whenever
   transactions are detected that had poor availability
        or responsiveness."
    ::=  { apmGroups 5 }

apmNotificationGroup NOTIFICATION-GROUP
    NOTIFICATIONS { apmTransactionResponsivenessAlarm,
                    apmTransactionUnsuccessfulAlarm }
    STATUS        current
```

```
  DESCRIPTION
     "Notifications sent by an APM MIB agent."
  ::= { apmGroups 6 }

END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/APM-MIB
No license file was found, but licenses were detected in source scan.

```
DOCS-IF-MIB DEFINITIONS ::= BEGIN

 IMPORTS
   MODULE-IDENTITY,
   OBJECT-TYPE,
   Unsigned32,
   Integer32,
   Counter32,
   Counter64,
   TimeTicks,
   IpAddress,
   transmission
         FROM SNMPv2-SMI        -- [RFC2578]
   TEXTUAL-CONVENTION,
   MacAddress,
   RowStatus,
   TruthValue,
   TimeInterval,
   TimeStamp,
   StorageType
         FROM SNMPv2-TC         -- [RFC2579]
   OBJECT-GROUP,

   MODULE-COMPLIANCE
         FROM SNMPv2-CONF       -- [RFC2580]
   ifIndex, InterfaceIndexOrZero
         FROM IF-MIB            -- [RFC2863]
   InetAddressType,
   InetAddress
         FROM INET-ADDRESS-MIB  -- [RFC4001]
   IANAifType
         FROM IANAifType-MIB;   -- [IANA]

docsIfMib MODULE-IDENTITY
   LAST-UPDATED    "200605240000Z" -- May 24, 2006
   ORGANIZATION    "IETF IPCDN Working Group"
   CONTACT-INFO
```

" David Raftus
Postal: ATI Technologies Inc.
340 Terry Fox Drive, Suite 202
Ottawa Ontario
Canada
Phone: +1 613 592 1052 ext.222
E-mail: david.raftus@ati.com

Eduardo Cardona
Postal: Cable Television Laboratories, Inc.
858 Coal Creek Circle
Louisville, CO 80027-9750
U.S.A.
Phone: Tel: +1 303 661 9100
Fax: +1 303 661 9199
E-mail: e.cardona@cablelabs.com;mibs@cablelabs.com

IETF IPCDN Working Group
General Discussion: ipcdn@ietf.org
Subscribe: http://www.ietf.org/mailman/listinfo/ipcdn
Archive: ftp://ftp.ietf.org/ietf-mail-archive/ipcdn
Co-chairs: Richard Woundy, Richard_Woundy@cable.comcast.com
Jean-Francois Mule, jf.mule@cablelabs.com"

DESCRIPTION
"This is the MIB Module for DOCSIS 2.0-compliant Radio

Frequency (RF) interfaces in Cable Modems and
Cable Modem Termination Systems.

Copyright (C) The Internet Society (2006). This
version of this MIB module is part of RFC 4546; see
the RFC itself for full legal notices."

REVISION "200605240000Z"
DESCRIPTION
"Revision of the IETF RF MIB module for DOCSIS 2.0.
This version published as RFC 4546.
This MIB module revision includes the following
among others:
Usage of ifType (205) for upstream logical channels.
Addition of downstream and upstream utilization
counters.
Additional statistics per upstream interface.
Upstream channel offline configuration mechanism.
Added MIB support for new DOCSIS 2.0 modulation
attributes.

```
        Euro-DOCSIS downstream interleave values.
        Adjustments to RFC 2670 definitions based on
        the MIB review guidelines from the IETF



        Operations and Management Area (OPS)."

    REVISION "199908190000Z"
    DESCRIPTION
       "Initial version, published as RFC 2670.
        Modified by Mike St. Johns to fix problems identified by
        the first pass of the MIB doctor.  Of special note,
        docsIfRangingResp and docsIfCmtsInsertionInterval were
        obsoleted and replaced by other objects with the same
        functionality, but with more appropriate syntax."
    ::= { transmission 127 }


-- Textual Conventions

TenthdBmV ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d-1"
    STATUS       current
    DESCRIPTION
       "This data type represents power levels that are normally
        expressed in dBmV.  Units are in tenths of a dBmV;
        for example, 5.1 dBmV will be represented as 51."
    SYNTAX       Integer32

TenthdB ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d-1"
    STATUS       current
    DESCRIPTION
       "This data type represents power levels that are
 normally
        expressed in dB.  Units are in tenths of a dB;
        for example, 5.1 dB will be represented as 51."
    SYNTAX       Integer32

DocsisVersion ::= TEXTUAL-CONVENTION
   STATUS         current
   DESCRIPTION
      "Indicates the DOCSIS Radio Frequency specification being
       referenced.
       'docsis10' indicates DOCSIS 1.0.
       'docsis11' indicates DOCSIS 1.1.
       'docsis20' indicates DOCSIS 2.0."
```

```
  SYNTAX       INTEGER {
      docsis10 (1),
      docsis11 (2),
      docsis20 (3)
  }

DocsisQosVersion ::= TEXTUAL-CONVENTION




  STATUS         current
  DESCRIPTION
     "Indicates the referenced quality-of-service
      level.
      'docsis10 refers to DOCSIS 1.0 Class of
      Service queuing services, and 'docsis11' refers
      to DOCSIS 1.1 Quality of Service."
  SYNTAX       INTEGER {
     docsis10 (1),
     docsis11 (2)
  }

DocsisUpstreamType ::= TEXTUAL-CONVENTION
  STATUS         current
   DESCRIPTION
       "Indicates the DOCSIS Upstream Channel Type.
        'unknown' means information not available.
        'tdma' is related to TDMA, Time Division
        Multiple Access; 'atdma' is related to A-TDMA,
        Advanced Time Division Multiple Access,
        'scdma' is related to S-CDMA, Synchronous
        Code Division Multiple Access.
        'tdmaAndAtdma is related to simultaneous support of
        TDMA and A-TDMA modes."
  SYNTAX         INTEGER {
     unknown(0),
     tdma(1),
     atdma(2),
     scdma(3),
     tdmaAndAtdma(4)
  }

DocsEqualizerData ::= TEXTUAL-CONVENTION
    STATUS       current
    DESCRIPTION
        "This data type represents the equalizer data
         as measured at the receiver interface.
         The format of the equalizer follows the structure of the
```

```
        Transmit Equalization Adjust RNG-RSP TLV of DOCSIS RFI
        v2.0 :
        1 byte Main tap location 1..(n + m)
         1 byte Number of forward taps per symbol
        1 byte Number of forward taps: n
        1 byte Number of reverse taps: m

        Following are the equalizer coefficients:
        First, forward taps coefficients:
        2 bytes F1 (real),  2 bytes  F1 (imag)




        ...
        2 bytes Fn (real),  2 bytes  Fn (imag)

        Then, reverse taps coefficients:
        2 bytes D1 (real),  2 bytes  D1 (imag)
        ...

        2 bytes Dm (real),  2 bytes  Dm (imag)

        The equalizer coefficients are considered signed 16-bit
        integers in the range from -32768 (0x8000) to 32767
        (0x7FFF).

        DOCSIS specifications require up to a maximum of
        64 equalizer taps (n + m); therefore, this object size
         can get up 260 bytes (4 + 4x64).
        The minimum object size (other than zero) for a t-spaced
        tap with a minimum of 8 symbols will be 36 (4 + 4x8)."
    REFERENCE

  "Data-Over-Cable Service Interface Specifications: Radio
      Frequency Interface Specification SP-RFIv2.0-I10-051209,
      Figure 8-23."
    SYNTAX       OCTET STRING(SIZE (0 | 36..260))


docsIfMibObjects  OBJECT IDENTIFIER ::= { docsIfMib 1 }
docsIfBaseObjects OBJECT IDENTIFIER ::= { docsIfMibObjects 1 }
docsIfCmObjects   OBJECT IDENTIFIER ::= { docsIfMibObjects 2 }
docsIfCmtsObjects OBJECT IDENTIFIER ::= { docsIfMibObjects 3 }

--
-- BASE GROUP
--
```

```
--
-- The following table is implemented on both the Cable Modem
-- and the Cable Modem Termination System.  This table is
-- read only for the CM.
--

docsIfDownstreamChannelTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF DocsIfDownstreamChannelEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "This table describes the attributes of downstream
       channels (frequency bands)."
   REFERENCE




       "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface
 Specification SP-RFIv2.0-I10-051209,
        Tables 6-16, and 6-17."
   ::= { docsIfBaseObjects 1 }

docsIfDownstreamChannelEntry OBJECT-TYPE
   SYNTAX      DocsIfDownstreamChannelEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "An entry provides a list of attributes for a single
       downstream channel.
       An entry in this table exists for each ifEntry with an
       ifType of docsCableDownstream(128)."
   INDEX { ifIndex }
   ::= { docsIfDownstreamChannelTable 1 }

DocsIfDownstreamChannelEntry ::= SEQUENCE {
       docsIfDownChannelId              Integer32,
       docsIfDownChannelFrequency       Integer32,
       docsIfDownChannelWidth           Integer32,
       docsIfDownChannelModulation      INTEGER,
       docsIfDownChannelInterleave      INTEGER,
       docsIfDownChannelPower           TenthdBmV,
       docsIfDownChannelAnnex           INTEGER,
       docsIfDownChannelStorageType
     StorageType
   }

docsIfDownChannelId OBJECT-TYPE
```

```
    SYNTAX      Integer32 (0..255)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The Cable Modem Termination System identification of the
        downstream channel within this particular MAC interface.
        if the interface is down, the object returns the most
        current value.  If the downstream channel ID is unknown,
        this object returns a value of 0."
    ::= { docsIfDownstreamChannelEntry 1 }

docsIfDownChannelFrequency OBJECT-TYPE
    SYNTAX      Integer32 (0..1000000000)
    UNITS       "hertz"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The center of the downstream frequency associated with
        this channel.  This object will return the current tuner




        frequency.  If a CMTS provides IF output, this object
        will return 0, unless this CMTS is in control of the
        final downstream frequency.  See
 the associated
        compliance object for a description of valid frequencies
        that may be written to this object."

    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.3.3."
    ::= { docsIfDownstreamChannelEntry 2 }

docsIfDownChannelWidth OBJECT-TYPE
    SYNTAX      Integer32 (0..16000000)
    UNITS       "hertz"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The bandwidth of this downstream channel.  Most
        implementations are expected to support a channel width
        of 6 MHz (North America) and/or 8 MHz (Europe).  See the
        associated compliance object for a description of the
        valid channel widths for this object."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
```

```
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Table 6-17."

 ::= { docsIfDownstreamChannelEntry 3 }

docsIfDownChannelModulation OBJECT-TYPE
   SYNTAX      INTEGER {
      unknown(1),
      other(2),
      qam64(3),
      qam256(4)
   }
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION
      "The modulation type associated with this downstream
       channel.  If the interface is down, this object either
       returns the configured value (CMTS), the most current
       value (CM), or the value of unknown(1).  See the
       associated conformance object for write conditions and
       limitations.  See the reference for specifics on the
       modulation profiles implied by qam64 and qam256."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio



        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Table 6-17."
   ::= { docsIfDownstreamChannelEntry 4 }

docsIfDownChannelInterleave OBJECT-TYPE
   SYNTAX      INTEGER {
      unknown(1),
       other(2),
      taps8Increment16(3),
      taps16Increment8(4),
      taps32Increment4(5),
      taps64Increment2(6),
      taps128Increment1(7),
      taps12increment17(8)
   }
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION
      "The Forward Error Correction (FEC) interleaving used
       for this downstream channel.
       Values are defined as follows:
```

taps8Increment16(3): protection 5.9/4.1 usec,
latency .22/.15 msec
taps16Increment8(4): protection 12/8.2 usec,
latency .48/.33 msec
taps32Increment4(5): protection 24/16 usec,
latency .98/.68 msec
taps64Increment2(6): protection 47/33 usec,
latency 2/1.4 msec
taps128Increment1(7): protection 95/66 usec,
latency 4/2.8 msec
taps12increment17(8):
protection 18/14 usec,
latency 0.43/0.32 msec

The value 'taps12increment17' is supported by EuroDOCSIS cable systems only, and the others by DOCSIS cable systems.

If the interface is down, this object either returns the configured value (CMTS), the most current value (CM), or the value of unknown(1).
The value of other(2) is returned if the interleave is known but not defined in the above list.
See the associated conformance object for write conditions and limitations. See the reference for the FEC configuration described by the setting of this object."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio Frequency Interface Specification SP-RFIv2.0-I10-051209,

Table 6-15."
::= { docsIfDownstreamChannelEntry 5 }

docsIfDownChannelPower OBJECT-TYPE
SYNTAX TenthdBmV
UNITS
"dBmV"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"At the CMTS, the operational transmit power. At the CM, the received power level.
If the interface is down, this object either returns the configured value (CMTS), the most current value (CM) or the value of 0. See the associated conformance object for write conditions and limitations. See the reference for recommended and required power levels."

```
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-16, 6-17."
    ::= { docsIfDownstreamChannelEntry 6 }

docsIfDownChannelAnnex OBJECT-TYPE
    SYNTAX      INTEGER {
        unknown(1),
        other(2),
        annexA(3),
        annexB(4),
        annexC(5)
    }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of this object indicates
 the conformance of
         the implementation to important regional cable standards.
         annexA : Annex A from ITU-T J.83 is used.
                  (equivalent to EN 300 429)
         annexB : Annex B from ITU-T J.83 is used.
         annexC : Annex C from ITU-T J.83 is used."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Sections 6.3.1, and H.3.1."
    ::= { docsIfDownstreamChannelEntry 7 }

docsIfDownChannelStorageType OBJECT-TYPE
    SYNTAX       StorageType
    MAX-ACCESS   read-only




    STATUS       current
    DESCRIPTION
        "The storage type for this conceptual row.
         Entries with this object set to permanent(4)
         do not require write operations for read-write
         objects."
    ::= { docsIfDownstreamChannelEntry 8 }

--
-- The following table is implemented on both the CM and the CMTS.
-- For the CM, only attached channels
```

```
 appear in the table.  For the
-- CM, this table is read-only as well.
--

docsIfUpstreamChannelTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF DocsIfUpstreamChannelEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "This table describes the attributes of attached upstream
       channels."
   ::= { docsIfBaseObjects 2 }

docsIfUpstreamChannelEntry OBJECT-TYPE
   SYNTAX      DocsIfUpstreamChannelEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "List of attributes for a single upstream channel.  For
       DOCSIS 2.0 CMTSs, an entry in this table exists for
       each ifEntry with an ifType of docsCableUpstreamChannel
       (205).
       For DOCSIS 1.x CM/CMTSs and DOCSIS 2.0 CMs, an entry in
       this table exists for each ifEntry with an ifType of
       docsCableUpstream (129).

       For DOCSIS 2.0 CMTSs, two classes of interfaces can be
       defined for this table:
        o Upstream Physical Interfaces: The traditional DOCSIS
          1.x CMTS upstream interface ifType 129 and the DOCSIS
          2.0 ifType 205 that are functional.  In other words,
          interfaces that represent upstream receivers within
          an RF MAC interface.
          Entries of physical interfaces are exposed to the
          management interface with their corresponding
          ifStack hierarchy and are not administratively
          created by this table.




        o Upstream Temporary Interfaces: A fictitious
          interface created for the purpose of manipulating
          physical interface parameters offline, then
          validating prior to updating the target physical
          interface.

       In case of a reinitialization of the managed system,
```

```
        physical interfaces values persist while the temporary
        interfaces are not recreated.

        This mechanism helps to minimize
 service disruptions
        originating in situations where a group of interface
        parameter values need to be consistent with each other
        in SET operations.  A temporary buffer
        (temporary interface) is provided to allow the CMTS
        to validate the parameters offline."
    INDEX { ifIndex }
    ::= { docsIfUpstreamChannelTable 1 }

DocsIfUpstreamChannelEntry ::= SEQUENCE {
        docsIfUpChannelId                   Integer32,
        docsIfUpChannelFrequency            Integer32,
        docsIfUpChannelWidth                Integer32,
        docsIfUpChannelModulationProfile    Unsigned32,
        docsIfUpChannelSlotSize             Unsigned32,
        docsIfUpChannelTxTimingOffset       Unsigned32,
        docsIfUpChannelRangingBackoffStart  Integer32,
        docsIfUpChannelRangingBackoffEnd    Integer32,
        docsIfUpChannelTxBackoffStart       Integer32,
        docsIfUpChannelTxBackoffEnd         Integer32,

       docsIfUpChannelScdmaActiveCodes      Unsigned32,
        docsIfUpChannelScdmaCodesPerSlot    Integer32,
        docsIfUpChannelScdmaFrameSize       Unsigned32,
        docsIfUpChannelScdmaHoppingSeed     Unsigned32,
        docsIfUpChannelType                 DocsisUpstreamType,
        docsIfUpChannelCloneFrom            InterfaceIndexOrZero,
        docsIfUpChannelUpdate               TruthValue,
        docsIfUpChannelStatus               RowStatus,
        docsIfUpChannelPreEqEnable          TruthValue
    }

docsIfUpChannelId OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The CMTS identification of the upstream channel."
    ::= { docsIfUpstreamChannelEntry 1 }



docsIfUpChannelFrequency OBJECT-TYPE
    SYNTAX      Integer32 (0..1000000000)
```

```
    UNITS       "hertz"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The center of the frequency
 band associated with this
        upstream interface.  This object returns 0 if the frequency
        is undefined or unknown.  Minimum permitted upstream
        frequency is 5,000,000 Hz for current technology.  See
        the associated conformance object for write conditions
        and limitations."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Table 4-2."
    ::= { docsIfUpstreamChannelEntry 2 }

docsIfUpChannelWidth OBJECT-TYPE
    SYNTAX      Integer32 (0..64000000)
    UNITS       "hertz"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The bandwidth of this upstream interface.  This object
        returns 0 if the interface width is undefined or unknown.
        Minimum permitted interface width is currently 200,000 Hz.
        See the associated conformance object for write conditions
        and limitations."
     REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Table 6-5."
    ::= { docsIfUpstreamChannelEntry 3 }

docsIfUpChannelModulationProfile OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "An entry identical to the docsIfModIndex in the
        docsIfCmtsModulationTable that describes this channel.
        This channel is further instantiated there by a grouping
        of interval usage codes (IUCs) that, together, fully
        describe the channel modulation.  This object returns 0 if
        the docsIfCmtsModulationTable entry does not exist or is
        empty.  See the associated conformance object for write
        conditions and limitations.
```

Setting this object returns an 'inconsistentValue'
error if the following conditions are not satisfied:
1. All the
IUC entries in the selected modulation profile
MUST have the same value of docsIfCmtsModChannelType.
2. All of the Modulation parameters in the selected
modulation profile MUST be consistent with the other
parameters in this docsIfUpstreamChannelEntry."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Table 8-19."
::= { docsIfUpstreamChannelEntry 4 }

docsIfUpChannelSlotSize OBJECT-TYPE
SYNTAX Unsigned32
UNITS "ticks"
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"Applicable to TDMA and ATDMA channel types only.
The number of 6.25 microsecond ticks in each upstream
mini-slot. Returns zero if the value is undefined or
unknown or in case of an SCDMA channel.
See the associated conformance object for write
conditions and limitations."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 8.1.2.4."
::= { docsIfUpstreamChannelEntry 5 }

docsIfUpChannelTxTimingOffset OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"At the CM, a measure of the current round trip time
obtained from the ranging offset (initial ranging offset +
ranging offset adjustments).
At the CMTS, the maximum of timing offset, among all the
CMs that are/were present on the channel, taking into
account all (initial + periodic) timing offset
corrections that were sent for each of the CMs. Generally,
these measurements are positive, but if the measurements
are negative, the value of this object is zero. Used for

timing of CM upstream transmissions to ensure synchronized

arrivals at the CMTS.
Units are one 64th fraction of 6.25 microseconds."

REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio Frequency Interface Specification SP-RFIv2.0-I10-051209, Section 6.2.19."
::= { docsIfUpstreamChannelEntry 6 }

docsIfUpChannelRangingBackoffStart OBJECT-TYPE
SYNTAX Integer32 (0..16)
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The initial random backoff window to use when retrying Ranging Requests. Expressed as a power of 2. A value of 16 at the CMTS indicates that a proprietary adaptive retry mechanism is to be used. See the associated conformance object for write conditions and limitations."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio Frequency Interface Specification SP-RFIv2.0-I10-051209, Sections 8.3.4, and 9.4."
::= { docsIfUpstreamChannelEntry
7 }

docsIfUpChannelRangingBackoffEnd OBJECT-TYPE
SYNTAX Integer32 (0..16)
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The final random backoff window to use when retrying Ranging Requests. Expressed as a power of 2. A value of 16 at the CMTS indicates that a proprietary adaptive retry mechanism is to be used. See the associated conformance object for write conditions and limitations."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio Frequency Interface Specification SP-RFIv2.0-I10-051209, Section 8.3.4, and 9.4."
::= { docsIfUpstreamChannelEntry 8 }

docsIfUpChannelTxBackoffStart OBJECT-TYPE
SYNTAX Integer32 (0..16)

```
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The initial random backoff window to use when retrying
         transmissions.  Expressed as a power of 2.  A value of 16

        at the CMTS indicates that a proprietary adaptive retry
         mechanism is to be used.  See the associated conformance
         object for write conditions and limitations."



    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Section 8.3.4, and 9.4."
    ::= { docsIfUpstreamChannelEntry 9 }

docsIfUpChannelTxBackoffEnd OBJECT-TYPE
    SYNTAX      Integer32 (0..16)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The final random backoff window to use when retrying
         transmissions.  Expressed as a power of 2.  A value of 16
         at the CMTS indicates that a proprietary adaptive retry
         mechanism is to be used.  See the associated conformance
         object for write conditions and limitations."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification
 SP-RFIv2.0-I10-051209,
         Section 8.3.4, and 9.4."
    ::= { docsIfUpstreamChannelEntry 10 }

docsIfUpChannelScdmaActiveCodes OBJECT-TYPE
    SYNTAX     Unsigned32 (0|64..66|68..70|72|74..78|80..82|84..88
                          |90..96|98..100|102|104..106|108
                          |110..112|114..126|128)
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
        "Applicable for SCDMA channel types only.
         Number of active codes.  Returns zero for
         Non-SCDMA channel types.  Note that legal
         values from 64..128 MUST be non-prime."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
```

```
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.11.2.1."
    ::= { docsIfUpstreamChannelEntry 11 }

docsIfUpChannelScdmaCodesPerSlot OBJECT-TYPE
    SYNTAX      Integer32(0 | 2..32)
    UNITS       "codesperMinislots"
    MAX-ACCESS  read-create
    STATUS      current
     DESCRIPTION
        "Applicable for SCDMA channel types only.
        The number of SCDMA codes per mini-slot.
        Returns zero if the value is undefined or unknown or in




        case of a TDMA or ATDMA channel."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.11.2.1."
    ::= { docsIfUpstreamChannelEntry 12 }

docsIfUpChannelScdmaFrameSize OBJECT-TYPE
    SYNTAX      Unsigned32 (0..32)
    UNITS       "spreadIntervals"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Applicable for SCDMA channel types only.
        SCDMA Frame size in units of spreading intervals.
        This value returns zero for non-SCDMA Profiles."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.12."
    ::= {
 docsIfUpstreamChannelEntry 13 }

docsIfUpChannelScdmaHoppingSeed OBJECT-TYPE
    SYNTAX     Unsigned32 (0..32767)
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
        "Applicable for SCDMA channel types only.
        15-bit seed used for code hopping sequence initialization.
        Returns zero for non-SCDMA channel types.
        Setting this value to a value different than zero for
```

```
        non-SCDMA channel types returns the error 'wrongValue'."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.14.1."
    ::= { docsIfUpstreamChannelEntry 14 }

docsIfUpChannelType OBJECT-TYPE
    SYNTAX      DocsisUpstreamType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Reflects the Upstream channel type.
        This object returns the value of docsIfCmtsModChannelType
        for the modulation profile selected
 in
        docsIfUpChannelModulationProfile for this row."
    REFERENCE



        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.1."
    ::= { docsIfUpstreamChannelEntry 15 }

docsIfUpChannelCloneFrom OBJECT-TYPE
    SYNTAX      InterfaceIndexOrZero
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This object contains the ifIndex value of the physical
        interface row entry whose parameters are to be adjusted.

        Upon setting this object to the ifIndex value of a
        physical interface, the following interface objects values
        are copied to this entry:
        docsIfUpChannelFrequency,
        docsIfUpChannelWidth,
        docsIfUpChannelModulationProfile,
        docsIfUpChannelSlotSize,
        docsIfUpChannelRangingBackoffStart,
        docsIfUpChannelRangingBackoffEnd,
        docsIfUpChannelTxBackoffStart,
         docsIfUpChannelTxBackoffEnd,
        docsIfUpChannelScdmaActiveCodes,
        docsIfUpChannelScdmaCodesPerSlot,
        docsIfUpChannelScdmaFrameSize,
```

docsIfUpChannelScdmaHoppingSeed,
docsIfUpChannelType, and
docsIfUpChannelPreEqEnable
Setting this object to the value of a non-existent or
a temporary upstream interface returns the error
'wrongValue'.
This object MUST contain a value of zero for physical
interfaces entries.
Setting this object in row entries that correspond to
physical interfaces returns the error 'wrongValue'."
::= { docsIfUpstreamChannelEntry 16 }

docsIfUpChannelUpdate OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"Used to perform the copy of adjusted parameters from the
temporary interface entry to the physical interface
indicated by the docsIfUpChannelCloneFrom
object. The
transfer is initiated through an SNMP SET to 'true' of

this object.
A SET to 'true' fails and returns error 'commitFailed'
if docsIfUpChannelStatus value is 'notInService', which
means that the interface parameters values are not
compatible with each other or have not been validated yet.
Reading this object always returns 'false'."
::= { docsIfUpstreamChannelEntry 17 }

docsIfUpChannelStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This object is only used for the creation of a temporary
upstream row with the purpose of updating the parameters
of a physical upstream channel entry.

The following restrictions apply to this object:
1. This object is not writable for physical interfaces.
2. Temporary interface entries are only created by a SET

of this object to createandWait(5).
3. ifAdminStatus from the Interface MIB RFC 2863 is used

to take a physical upstream channel offline, to be
consistent with DOCSIS 1.x operation, as indicated in
RFC 2670.
In addition,
o ifAdminStatus 'down' is reflected in this object
as 'notInService'.
o ifOperStatus 'down' while ifAdminStatus 'up' is
reflected in this object as 'notInservice'.
4. Temporary created rows MUST be set to 'active' with
the purpose of validating upstream parameter
consistency prior to transferring the parameters to the
physical interface.

Below is a mandatory procedure for adjusting the values
of a physical interface:
1. Create a temporary interface entry through an SNMP SET
using 'createAndWait'. At this point, the RowStatus
reports 'notReady'.
The Manager entity uses an ifIndex value outside the
operational range of the physical interfaces for the
creation of a temporary interface.
2. Set the docsIfUpChannelCloneFrom object to the ifIndex
value of the physical row to update. Now
docsIfUpChannelStatus reports 'notInService'.
3. Change the upstream parameters to the desired values
in the temporary row.

4. Validate that all parameters are consistent by setting
docsIfUpChannelStatus to 'active'. A failure to set the
RowStatus to 'active' returns the error 'commitFailed',
which means the parameters are not compatible with the
target physical interface.
5. With docsIfUpChannelStatus 'active', transfer the
parameters to the target physical interface by setting
the object docsIfUpChannelUpdate to 'true'.
6. Delete the temporary
row by setting
docsIfUpChannelStatus to 'destroy'."
::= { docsIfUpstreamChannelEntry 18 }

docsIfUpChannelPreEqEnable OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"At the CMTS, this object is used to enable or disable

pre-equalization on the upstream channel represented by
this table instance. At the CM, this object is read-only
and reflects the status of pre-equalization as represented
in the RNG-RSP. Pre-equalization is considered enabled at
the CM if a RNG-RSP with pre-equalization data has been
received at least once since the last mac
reinitialization."
DEFVAL {false}
::= { docsIfUpstreamChannelEntry 19 }

-- The following table describes the attributes of each class of
-- service. The entries in this table are referenced from the
-- docsIfServiceEntries. They exist as a separate table in order to
--
reduce redundant information in docsIfServiceTable.
--
-- This table is implemented at both the CM and the CMTS.
-- The CM need only maintain entries for the classes of service
-- referenced by its docsIfCmServiceTable.
--

docsIfQosProfileTable OBJECT-TYPE
SYNTAX SEQUENCE OF DocsIfQosProfileEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Describes the attributes for each class of service."
::= { docsIfBaseObjects 3 }

docsIfQosProfileEntry OBJECT-TYPE
SYNTAX DocsIfQosProfileEntry

MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Describes the attributes for a single class of service.
If implemented as read-create in the Cable Modem
Termination System, creation of entries in this table is
controlled by the value of
docsIfCmtsQosProfilePermissions.

If implemented as read-only, entries are created based
on information in REG-REQ
MAC messages received from
cable modems (for Cable Modem Termination System), or
based on information extracted from the TFTP option file

```
        (for Cable Modem).
        In the Cable Modem Termination System, read-only entries
        are removed if no longer referenced by
        docsIfCmtsServiceTable.

        An entry in this table MUST not be removed while it is
        referenced by an entry in docsIfCmServiceTable (Cable
        Modem) or docsIfCmtsServiceTable (Cable Modem Termination
        System).

        An entry in this table SHOULD NOT be changeable while
        it is referenced by an entry in docsIfCmtsServiceTable.

        If this table is created automatically, there SHOULD only
        be a single entry for each Class of Service.  Multiple
        entries with the same Class of Service parameters are NOT
        RECOMMENDED."
    INDEX { docsIfQosProfIndex }
    ::= { docsIfQosProfileTable 1 }

DocsIfQosProfileEntry
 ::= SEQUENCE {
        docsIfQosProfIndex              Integer32,
        docsIfQosProfPriority           Integer32,
        docsIfQosProfMaxUpBandwidth     Integer32,
        docsIfQosProfGuarUpBandwidth    Integer32,
        docsIfQosProfMaxDownBandwidth   Integer32,
        docsIfQosProfMaxTxBurst         Integer32,  -- deprecated
        docsIfQosProfBaselinePrivacy    TruthValue,
        docsIfQosProfStatus             RowStatus,
        docsIfQosProfMaxTransmitBurst   Integer32,
        docsIfQosProfStorageType        StorageType
    }

docsIfQosProfIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..16383)



    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The index value that uniquely identifies an entry
         in the docsIfQosProfileTable."
    ::= { docsIfQosProfileEntry 1 }

docsIfQosProfPriority OBJECT-TYPE
    SYNTAX      Integer32 (0..7)
```

```
    MAX-ACCESS  read-create
    STATUS      current

   DESCRIPTION
        "A relative priority assigned to this service when
        allocating bandwidth.  Zero indicates lowest priority
        and seven indicates highest priority.
        Interpretation of priority is device-specific.
        MUST NOT be changed while this row is active."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Annex C.1.1.4."
    DEFVAL { 0 }
    ::= { docsIfQosProfileEntry 2 }

docsIfQosProfMaxUpBandwidth OBJECT-TYPE
    SYNTAX      Integer32 (0..100000000)
    UNITS "bits per second"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The maximum upstream bandwidth, in bits per second,
        allowed for a service with this service class.
        Zero if there is no restriction of upstream bandwidth.
        MUST NOT be changed while this row is active."
    REFERENCE
        "Data-Over-Cable Service
  Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Annex C.1.1.4."
    DEFVAL { 0 }
    ::= { docsIfQosProfileEntry 3 }

docsIfQosProfGuarUpBandwidth OBJECT-TYPE
    SYNTAX      Integer32 (0..100000000)
    UNITS "bits per second"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Minimum guaranteed upstream bandwidth, in bits per second,



        allowed for a service with this service class.
        MUST NOT be changed while this row is active."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
```

```
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Annex C.1.1.4."
    DEFVAL { 0 }
    ::= { docsIfQosProfileEntry 4 }

docsIfQosProfMaxDownBandwidth OBJECT-TYPE
    SYNTAX      Integer32 (0..100000000)
    UNITS "bits per second"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The maximum downstream bandwidth,
 in bits per second,
        allowed for a service with this service class.
        Zero if there is no restriction of downstream bandwidth.
        MUST NOT be changed while this row is active."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Annex C.1.1.4."

    DEFVAL { 0 }
    ::= { docsIfQosProfileEntry 5 }

docsIfQosProfMaxTxBurst OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    UNITS "mini-slots"
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
        "The maximum number of mini-slots that may be requested
        for a single upstream transmission.
        A value of zero means there is no limit.
        MUST NOT be changed while this row is active.
        This object has been deprecated and replaced by
        docsIfQosProfMaxTransmitBurst, to fix a mismatch
        of the units and value range with respect to
 the DOCSIS
        Maximum Upstream Channel Transmit Burst Configuration
        Setting."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        C.1.1.4."
    DEFVAL { 0 }
    ::= { docsIfQosProfileEntry 6 }
```

```
docsIfQosProfBaselinePrivacy OBJECT-TYPE
   SYNTAX      TruthValue
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "Indicates whether Baseline Privacy is enabled for this
       service class.
       MUST NOT be changed while this row is active."
   DEFVAL { false }
   ::= { docsIfQosProfileEntry 7 }

docsIfQosProfStatus OBJECT-TYPE
   SYNTAX      RowStatus
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "This is object is used to create or delete rows in
       this table.  This object MUST NOT be changed from active
       while the row is referenced by any entry in either
       docsIfCmServiceTable
 (on the CM) or
       docsIfCmtsServiceTable (on the CMTS)."
   ::= { docsIfQosProfileEntry 8 }

docsIfQosProfMaxTransmitBurst OBJECT-TYPE
   SYNTAX      Integer32 (0..65535)
   UNITS       "bytes"
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "The maximum number of bytes that may be requested for a
       single upstream transmission.  A value of zero means there
       is no limit.  Note: This value does not include any
       physical layer overhead.
       MUST NOT be changed while this row is active."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Annex C.1.1.4."
   DEFVAL { 0 }
   ::= { docsIfQosProfileEntry 9 }

docsIfQosProfStorageType OBJECT-TYPE
   SYNTAX       StorageType
   MAX-ACCESS   read-only
   STATUS       current
   DESCRIPTION
```

```
        "The storage type for this conceptual
 row.
        Entries with this object set to permanent(4)



        do not require write operations for writable
        objects."
    ::= { docsIfQosProfileEntry 10 }

docsIfSignalQualityTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfSignalQualityEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "At the CM, describes the PHY signal quality of downstream
        channels.  At the CMTS, this object describes the PHY
        signal quality of upstream channels.  At the CMTS, this
        table MAY exclude contention intervals."
    ::= { docsIfBaseObjects 4 }

docsIfSignalQualityEntry OBJECT-TYPE
    SYNTAX      DocsIfSignalQualityEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "At the CM, this object describes the PHY characteristics of
        a downstream channel.  At the CMTS, it describes the PHY
        signal quality of an upstream channel.
        An entry in this table exists
 for each ifEntry with an
        ifType of docsCableDownstream(128) for Cable Modems.
        For DOCSIS 1.1 Cable Modem Termination Systems, an entry
        exists for each ifEntry with an ifType of
        docsCableUpstream (129).
        For DOCSIS 2.0 Cable Modem Termination Systems, an entry
        exists for each ifEntry with an ifType of
        docsCableUpstreamChannel (205)."
    INDEX { ifIndex }
    ::= { docsIfSignalQualityTable 1 }

DocsIfSignalQualityEntry ::= SEQUENCE {
        docsIfSigQIncludesContention  TruthValue,
        docsIfSigQUnerroreds          Counter32,
        docsIfSigQCorrecteds          Counter32,
        docsIfSigQUncorrectables      Counter32,
        docsIfSigQSignalNoise         TenthdB,
        docsIfSigQMicroreflections    Integer32,
```

```
        docsIfSigQEqualizationData    DocsEqualizerData,
        docsIfSigQExtUnerroreds       Counter64,
        docsIfSigQExtCorrecteds       Counter64,
        docsIfSigQExtUncorrectables
    Counter64
    }

docsIfSigQIncludesContention OBJECT-TYPE



    SYNTAX      TruthValue
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "true(1) if this CMTS includes contention intervals in
         the counters in this table.  Always false(2) for CMs."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Section 9.4.1"
    ::= { docsIfSignalQualityEntry 1 }

docsIfSigQUnerroreds OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "codewords"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Codewords received on this channel without error.
         This includes all codewords, whether or not they
         were part of frames destined for this device.
         Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other
         times as indicated
 by the value of
         ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Sections 6.2.4, and 6.3.6."
    ::= { docsIfSignalQualityEntry 2 }

docsIfSigQCorrecteds OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "codewords"
    MAX-ACCESS  read-only
    STATUS      current
```

```
    DESCRIPTION
        "Codewords received on this channel with correctable
        errors.  This includes all codewords, whether or not
        they were part of frames destined for this device.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency
 Interface Specification SP-RFIv2.0-I10-051209,
        Sections 6.2.4, and 6.3.6."



    ::= { docsIfSignalQualityEntry 3 }

docsIfSigQUncorrectables OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "codewords"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Codewords received on this channel with uncorrectable
        errors.  This includes all codewords, whether or not
        they were part of frames destined for this device.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Sections 6.2.4, and 6.3.6."
    ::= { docsIfSignalQualityEntry 4 }

docsIfSigQSignalNoise OBJECT-TYPE
    SYNTAX      TenthdB
     UNITS       "TenthdB"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Signal/Noise ratio as perceived for this channel.
        At the CM, this object  describes the Signal/Noise of the
        downstream channel.  At the CMTS, it describes the
        average Signal/Noise of the upstream channel."
    REFERENCE
```

```
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 4-1 and 4-2"
    ::= { docsIfSignalQualityEntry 5 }

docsIfSigQMicroreflections OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    UNITS       "-dBc"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Microreflections, including in-channel response
         as perceived on this interface, measured in dBc below
         the signal level.
         This object is not assumed to return an absolutely
         accurate value, but it gives a rough indication




          of microreflections received on this interface.
         It is up to the implementer to provide information
         as accurately as possible."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 4-1 and 4-2"
    ::= { docsIfSignalQualityEntry 6 }

docsIfSigQEqualizationData OBJECT-TYPE
      SYNTAX      DocsEqualizerData
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
          "At the CM, this object returns the equalization data for
           the downstream channel.

           At the CMTS, this object is not applicable and is not
           instantiated.  Note that previous CMTS implementations
           may instantiate this object in two ways:
           - An equalization value indicating an equalization
             average for the upstream channel.  Those values have
             vendor-dependent
 interpretations.
           - Return a zero-length OCTET STRING to indicate that
             the value is unknown or if there is no equalization
             data available or defined."
      REFERENCE
          "DOCSIS Radio Frequency Interface Specification,
```

```
            Figure 6-23."
        ::= { docsIfSignalQualityEntry 7 }


docsIfSigQExtUnerroreds OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "codewords"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Codewords received on this channel without error.
        This includes all codewords, whether or not they
        were part of frames destined for this device.
        This is the 64-bit version of docsIfSigQUnerroreds.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio




        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Sections 6.2.4, and 6.3.6."
    ::= { docsIfSignalQualityEntry 8 }

docsIfSigQExtCorrecteds OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "codewords"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Codewords received on this channel with correctable
        errors.  This includes all codewords, whether or not
        they were part of frames destined for this device.
        This is the 64-bit version of docsIfSigQCorrecteds.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Sections 6.2.4, and 6.3.6."
    ::= { docsIfSignalQualityEntry 9 }

docsIfSigQExtUncorrectables OBJECT-TYPE
```

```
    SYNTAX      Counter64
    UNITS       "codewords"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Codewords received on this channel with uncorrectable
        errors.  This includes all codewords, whether or not
        they were part of frames destined for this device.
        This is the 64-bit version of docsIfSigQUncorrectables.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Sections 6.2.4, 6.3.6."
    ::= { docsIfSignalQualityEntry 10 }

--
-- DOCSIS Version of
 the device
--




docsIfDocsisBaseCapability OBJECT-TYPE
      SYNTAX      DocsisVersion
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
          "Indication of the DOCSIS capability of the device."
      REFERENCE
          "Data-Over-Cable Service Interface Specifications: Radio
           Frequency Interface Specification SP-RFIv2.0-I10-051209,
           Annex G."
      ::= { docsIfBaseObjects 5 }

--
-- CABLE MODEM GROUP
--

--
-- The CM MAC Table
--

docsIfCmMacTable OBJECT-TYPE
```

```
    SYNTAX      SEQUENCE OF DocsIfCmMacEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Describes the attributes of each CM MAC interface,
         extending the information available from ifEntry."
    ::= { docsIfCmObjects 1 }

docsIfCmMacEntry OBJECT-TYPE
    SYNTAX      DocsIfCmMacEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry containing objects describing attributes
 of
         each MAC entry, extending the information in ifEntry.
         An entry in this table exists for each ifEntry with an
         ifType of docsCableMaclayer(127)."
    INDEX { ifIndex }
    ::= { docsIfCmMacTable 1 }

DocsIfCmMacEntry ::= SEQUENCE {
        docsIfCmCmtsAddress          MacAddress,
        docsIfCmCapabilities         BITS,
        docsIfCmRangingRespTimeout   TimeTicks,
        docsIfCmRangingTimeout       TimeInterval
     }




docsIfCmCmtsAddress OBJECT-TYPE
    SYNTAX      MacAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Identifies the CMTS that is believed to control this MAC
         domain.  At the CM, this will be the source address from
         SYNC, MAP, and other MAC-layer messages.  If the CMTS is
         unknown, returns 00-00-00-00-00-00."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
          Section 8.2.2."
    ::= { docsIfCmMacEntry 1 }

docsIfCmCapabilities OBJECT-TYPE
    SYNTAX      BITS {
```

```
        atmCells(0),
        concatenation(1)
    }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Identifies the capabilities of the MAC implementation
         at this interface.  Note that packet transmission is
         always supported.  Therefore, there is no specific bit
         required to explicitly indicate this capability.
         Note that BITS objects are encoded most significant bit
         first.  For example, if bit 1 is set, the value of this
         object is the octet string '40'H."
    ::= { docsIfCmMacEntry 2 }

docsIfCmRangingRespTimeout OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-write
    STATUS      obsolete
    DESCRIPTION
        "Waiting time for a Ranging Response packet.
         This object has been obsoleted and replaced by
         docsIfCmRangingTimeout to correct
 the typing to
         TimeInterval."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Section 9.1.6."
    DEFVAL { 20 }
    ::= { docsIfCmMacEntry 3 }




docsIfCmRangingTimeout OBJECT-TYPE
    SYNTAX      TimeInterval
    UNITS       "HundredOfSeconds"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "Waiting time for a Ranging Response packet.
         This object MUST NOT persist at reinitialization
         of the managed system."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Section 9.1.6, timer T3."
```

```
    DEFVAL { 20 }
    ::= { docsIfCmMacEntry 4 }

--
-- CM status table.
-- This table is implemented only at the CM.
--

docsIfCmStatusTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfCmStatusEntry
    MAX-ACCESS  not-accessible
     STATUS      current
    DESCRIPTION
        "This table maintains a number of status objects
         and counters for Cable Modems."
    ::= { docsIfCmObjects 2 }

docsIfCmStatusEntry OBJECT-TYPE
    SYNTAX      DocsIfCmStatusEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A set of status objects and counters for a single MAC
         layer instance in Cable Modem.
         An entry in this table exists for each ifEntry with an
         ifType of docsCableMaclayer(127)."
    INDEX { ifIndex }
    ::= { docsIfCmStatusTable 1 }

DocsIfCmStatusEntry ::= SEQUENCE {
        docsIfCmStatusValue             INTEGER,
        docsIfCmStatusCode              OCTET STRING,
        docsIfCmStatusTxPower             TenthdBmV,
        docsIfCmStatusResets            Counter32,
        docsIfCmStatusLostSyncs           Counter32,



        docsIfCmStatusInvalidMaps         Counter32,
        docsIfCmStatusInvalidUcds
     Counter32,
        docsIfCmStatusInvalidRangingResponses   Counter32,
        docsIfCmStatusInvalidRegistrationResponses Counter32,
        docsIfCmStatusT1Timeouts          Counter32,
        docsIfCmStatusT2Timeouts          Counter32,
        docsIfCmStatusT3Timeouts          Counter32,
        docsIfCmStatusT4Timeouts          Counter32,
        docsIfCmStatusRangingAborteds     Counter32,
```

```
        docsIfCmStatusDocsisOperMode      DocsisQosVersion,
        docsIfCmStatusModulationType      DocsisUpstreamType,
        docsIfCmStatusEqualizationData    DocsEqualizerData,
        docsIfCmStatusUCCs                Counter32,
        docsIfCmStatusUCCFails            Counter32
    }

docsIfCmStatusValue OBJECT-TYPE
    SYNTAX      INTEGER {
        other(1),
        notReady(2),
        notSynchronized(3),
        phySynchronized(4),
        usParametersAcquired(5),
        rangingComplete(6),
        ipComplete(7),
        todEstablished(8),
        securityEstablished(9),
         paramTransferComplete(10),
        registrationComplete(11),
        operational(12),
        accessDenied(13)
    }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Current Cable Modem connectivity state, as specified
         in the RF Interface Specification.  Interpretations for
         state values 1-12 are clearly outlined in the SP-RFI
         reference given below.
         The state value accessDenied(13) indicates the CMTS has
         sent a Registration Aborted message to the CM.  The same
         state is reported as accessDenied(7) by the CMTS object
         docsIfCmtsCmStatusValue."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Section 11.2.
         Data-Over-Cable Service Interface Specifications:



         Operations Support System Interface Specification
         SP-OSSIv2.0-I09-050812,
 Section 6.3.4.2."
    ::= { docsIfCmStatusEntry 1 }

docsIfCmStatusCode OBJECT-TYPE
```

```
    SYNTAX      OCTET STRING (SIZE( 0 | 5 | 6 ))
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Status code for a Cable Modem as defined in the
        OSSI Specification.  The status code consists
        of a single character indicating error groups, followed
        by a two- or three-digit number indicating the status
        condition, followed by a decimal.
        An example of a returned value could be 'T101.0'.
        The zero-length OCTET STRING indicates no status code yet
        registered."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications:
        Operations Support System Interface Specification
        SP-OSSIv2.0-I09-050812, Annex D."
    ::= { docsIfCmStatusEntry 2 }


docsIfCmStatusTxPower OBJECT-TYPE
    SYNTAX      TenthdBmV
    UNITS       "TenthdBmV"
    MAX-ACCESS  read-only
    STATUS      current
     DESCRIPTION
        "The operational transmit power for the attached upstream
        channel."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.18."
    ::= { docsIfCmStatusEntry 3 }

docsIfCmStatusResets OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "resets"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of times the CM reset or initialized this
        interface.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other



        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
```

```
    ::= { docsIfCmStatusEntry 4 }

docsIfCmStatusLostSyncs OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of times the CM
 lost synchronization with
         the downstream channel.
         Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Section 8.3.2."
    ::= { docsIfCmStatusEntry 5 }

docsIfCmStatusInvalidMaps OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "maps"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of times the CM received invalid MAP messages.
         Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE

 "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Section 8.3.4."
    ::= { docsIfCmStatusEntry 6 }

docsIfCmStatusInvalidUcds OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "messages"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of times the CM received invalid UCD messages.
         Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other
         times as indicated by the value of
```

ifCounterDiscontinuityTime for the associated ifIndex."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 8.3.3."
::= { docsIfCmStatusEntry 7 }

docsIfCmStatusInvalidRangingResponses OBJECT-TYPE
SYNTAX Counter32
UNITS "messages"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Number of times the CM received invalid ranging response
messages.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 8.3.6."
::= { docsIfCmStatusEntry 8 }

docsIfCmStatusInvalidRegistrationResponses OBJECT-TYPE
SYNTAX Counter32
UNITS "messages"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Number of times the CM received invalid registration
response messages.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as
indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 8.3.8."
::= { docsIfCmStatusEntry 9 }

docsIfCmStatusT1Timeouts OBJECT-TYPE

```
    SYNTAX      Counter32
    UNITS       "timeouts"
    MAX-ACCESS  read-only
    STATUS      current



    DESCRIPTION
        "Number of times counter T1 expired in the CM.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Figure 9-2."
    ::= { docsIfCmStatusEntry 10 }

docsIfCmStatusT2Timeouts OBJECT-TYPE
     SYNTAX      Counter32
    UNITS       "timeouts"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of times counter T2 expired in the CM.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Figure 9-2."
    ::= { docsIfCmStatusEntry 11 }

docsIfCmStatusT3Timeouts OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "timeouts"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of times counter T3 expired in the CM.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times
  as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
```

```
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Figure 9-2."
    ::= { docsIfCmStatusEntry 12 }

docsIfCmStatusT4Timeouts OBJECT-TYPE
    SYNTAX      Counter32



    UNITS       "timeouts"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of times counter T4 expired in the CM.
         Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Figure 9-2."
    ::= { docsIfCmStatusEntry 13 }

docsIfCmStatusRangingAborteds
 OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "attempts"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Number of times the ranging process was aborted
         by the CMTS.
         Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Section 9.3.3."
    ::= { docsIfCmStatusEntry 14 }

docsIfCmStatusDocsisOperMode OBJECT-TYPE
    SYNTAX      DocsisQosVersion
    MAX-ACCESS  read-only
```

```
    STATUS      current
    DESCRIPTION
        "Indication of whether the device has registered using 1.0
         Class of Service or 1.1 Quality of Service.
         An unregistered CM SHOULD indicate 'docsis11'
 for a
         docsIfDocsisBaseCapability value of DOCSIS 1.1/2.0.  An
         unregistered CM SHOULD indicate 'docsis10'  for a
         docsIfDocsisBaseCapability value of DOCSIS 1.0."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Annex G."



    ::= { docsIfCmStatusEntry 15 }

docsIfCmStatusModulationType OBJECT-TYPE
    SYNTAX      DocsisUpstreamType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Indicates modulation type status currently used by the
         CM.  Since this object specifically identifies PHY mode,
         the shared upstream channel type is not permitted."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Section 6.2.1."

    ::= { docsIfCmStatusEntry 16 }

docsIfCmStatusEqualizationData OBJECT-TYPE
    SYNTAX      DocsEqualizerData
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Pre-equalization data for this CM after convolution with
         data indicated in the RNG-RSP.  This data is valid when
         docsIfUpChannelPreEqEnable is set to true."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Figure 8-23."
    ::= { docsIfCmStatusEntry 17 }

docsIfCmStatusUCCs OBJECT-TYPE
```

```
    SYNTAX          Counter32
    UNITS           "attempts"
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The number of successful Upstream Channel Change
        transactions.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmStatusEntry 18 }

docsIfCmStatusUCCFails OBJECT-TYPE
    SYNTAX          Counter32
    UNITS           "attempts"



    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The number of failed Upstream Channel Change
        transactions.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmStatusEntry 19 }

--
-- The Cable Modem Service Table
--

docsIfCmServiceTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfCmServiceEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Describes the attributes of each upstream service queue
        on a CM."
    ::= { docsIfCmObjects 3 }

docsIfCmServiceEntry OBJECT-TYPE
    SYNTAX      DocsIfCmServiceEntry
    MAX-ACCESS  not-accessible
    STATUS
```

```
      current
    DESCRIPTION
        "Describes the attributes of an upstream bandwidth service
         queue.
         An entry in this table exists for each Service ID.
         The primary index is an ifIndex with an ifType of
         docsCableMaclayer(127)."
    INDEX { ifIndex, docsIfCmServiceId }
    ::= { docsIfCmServiceTable 1 }

DocsIfCmServiceEntry ::= SEQUENCE {
        docsIfCmServiceId              Integer32,
        docsIfCmServiceQosProfile      Integer32,
        docsIfCmServiceTxSlotsImmed    Counter32,
        docsIfCmServiceTxSlotsDed      Counter32,
        docsIfCmServiceTxRetries       Counter32,
        docsIfCmServiceTxExceededs     Counter32,
        docsIfCmServiceRqRetries       Counter32,
        docsIfCmServiceRqExceededs     Counter32,
        docsIfCmServiceExtTxSlotsImmed Counter64,
        docsIfCmServiceExtTxSlotsDed   Counter64




     }

docsIfCmServiceId OBJECT-TYPE
    SYNTAX      Integer32 (1..16383)
    MAX-ACCESS
  not-accessible
    STATUS      current
    DESCRIPTION
        "Identifies a service queue for upstream bandwidth.  The
         attributes of this service queue are shared between the
         CM and the CMTS.  The CMTS allocates upstream bandwidth
         to this service queue based on requests from the CM and
         on the class of service associated with this queue."
    ::= { docsIfCmServiceEntry 1 }

docsIfCmServiceQosProfile OBJECT-TYPE
    SYNTAX      Integer32 (0..16383)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The index in docsIfQosProfileTable describing the quality
         of service attributes associated with this particular
         service.  If no associated entry in docsIfQosProfileTable
         exists, this object returns a value of zero."
```

```
    ::= { docsIfCmServiceEntry 2 }

docsIfCmServiceTxSlotsImmed OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS
      current
    DESCRIPTION
        "The number of upstream mini-slots that have been used to
        transmit data PDUs in immediate (contention) mode.  This
        includes only those PDUs that are presumed to have
        arrived at the head-end (i.e., those that were explicitly
        acknowledged).  It does not include retransmission attempts
        or mini-slots used by requests.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.4."
    ::= { docsIfCmServiceEntry 3 }

docsIfCmServiceTxSlotsDed OBJECT-TYPE




    SYNTAX      Counter32
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS
   current
    DESCRIPTION
        "The number of upstream mini-slots that have been used to
        transmit data PDUs in dedicated mode (i.e., as a result
        of a unicast Data Grant).
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.4."
    ::= { docsIfCmServiceEntry 4 }
```

```
docsIfCmServiceTxRetries OBJECT-TYPE
   SYNTAX      Counter32
   UNITS       "attempts"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
       "The number of attempts to transmit data PDUs containing
        requests for acknowledgment that did not result in
        acknowledgment.
        Discontinuities in the value of
 this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
   REFERENCE
       "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.4."
   ::= { docsIfCmServiceEntry 5 }

docsIfCmServiceTxExceededs OBJECT-TYPE
   SYNTAX      Counter32
   UNITS       "attempts"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
       "The number of data PDU transmission failures due to
        excessive retries without acknowledgment.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of




        ifCounterDiscontinuityTime for the associated ifIndex."
   REFERENCE
       "Data-Over-Cable Service Interface Specifications:
 Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.4."
   ::= { docsIfCmServiceEntry 6 }

docsIfCmServiceRqRetries OBJECT-TYPE
   SYNTAX      Counter32
   UNITS       "attempts"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
```

"The number of attempts to transmit bandwidth requests
that did not result in acknowledgment.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 9.4."
::= { docsIfCmServiceEntry 7 }

docsIfCmServiceRqExceededs OBJECT-TYPE
SYNTAX Counter32
UNITS "attempts"
MAX-ACCESS read-only
STATUS
current
DESCRIPTION
"The number of requests for bandwidth that failed due to
excessive retries without acknowledgment.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 9.4."
::= { docsIfCmServiceEntry 8 }

docsIfCmServiceExtTxSlotsImmed OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current

DESCRIPTION
"The number of upstream mini-slots that have been used to
transmit data PDUs in immediate (contention) mode. This
includes only those PDUs that are presumed to have
arrived at the head-end
(i.e., those that were explicitly
acknowledged). It does not include retransmission attempts
or mini-slots used by requests.
Discontinuities in the value of this counter can occur

```
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.4."
    ::= { docsIfCmServiceEntry 9 }

docsIfCmServiceExtTxSlotsDed OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of upstream mini-slots that have been used to
        transmit data PDUs in dedicated mode (i.e., as a result
        of a unicast Data Grant).
        Discontinuities in the value of this counter can occur

        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.4."
    ::= { docsIfCmServiceEntry 10 }

--
-- CMTS GROUP
--

--
-- The CMTS MAC Table
--

docsIfCmtsMacTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfCmtsMacEntry
    MAX-ACCESS  not-accessible
    STATUS      current



    DESCRIPTION
        "Describes the attributes of each CMTS MAC interface,
        extending the information available from ifEntry.
        Mandatory for all CMTS devices."
```

```
    ::= { docsIfCmtsObjects 1 }

docsIfCmtsMacEntry OBJECT-TYPE
    SYNTAX      DocsIfCmtsMacEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry containing objects describing attributes of each
         MAC entry, extending the information in ifEntry.
        An entry in this table exists for each ifEntry with an
        ifType of docsCableMaclayer(127)."
    INDEX { ifIndex }
    ::= { docsIfCmtsMacTable 1 }

DocsIfCmtsMacEntry ::= SEQUENCE {
        docsIfCmtsCapabilities            BITS,
        docsIfCmtsSyncInterval            Integer32,
        docsIfCmtsUcdInterval             Integer32,
        docsIfCmtsMaxServiceIds           Integer32,
        docsIfCmtsInsertionInterval       TimeTicks,   -- Obsolete
        docsIfCmtsInvitedRangingAttempts  Integer32,
        docsIfCmtsInsertInterval          TimeInterval,
        docsIfCmtsMacStorageType          StorageType
    }

docsIfCmtsCapabilities OBJECT-TYPE
    SYNTAX      BITS {
        atmCells(0),
        concatenation(1)
    }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Identifies the capabilities of the CMTS MAC
         implementation at this interface.  Note
 that packet
         transmission is always supported.  Therefore, there
         is no specific bit required to explicitly indicate
         this capability.
         Note that BITS objects are encoded most significant bit
         first.  For example, if bit 1 is set, the value of this
         object is the octet string '40'H."
    ::= { docsIfCmtsMacEntry 1 }

docsIfCmtsSyncInterval OBJECT-TYPE
```

```
    SYNTAX      Integer32 (1..200)
    UNITS       "Milliseconds"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The interval between CMTS transmission of successive SYNC
        messages at this interface."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.3."
    ::= { docsIfCmtsMacEntry 2 }

docsIfCmtsUcdInterval OBJECT-TYPE
    SYNTAX      Integer32 (1..2000)
    UNITS       "Milliseconds"
    MAX-ACCESS  read-write

   STATUS      current
    DESCRIPTION
        "The interval between CMTS transmission of successive
        Upstream Channel Descriptor messages for each upstream
        channel at this interface."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.3"
    ::= { docsIfCmtsMacEntry 3 }

docsIfCmtsMaxServiceIds OBJECT-TYPE
    SYNTAX     Integer32 (1..16383)
    UNITS      "SIDs"
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
        "The maximum number of service IDs that may be
        simultaneously active."
    ::= { docsIfCmtsMacEntry 4 }

docsIfCmtsInsertionInterval OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-write
    STATUS      obsolete
    DESCRIPTION
        "The amount of time to elapse between each broadcast
        initial maintenance grant.  Broadcast initial maintenance
        grants are used to allow
```

```
 new cable modems to join the
        network.  Zero indicates that a vendor-specific algorithm
        is used instead of a fixed time.  The maximum amount of




        time permitted by the specification is 2 seconds.
        This object has been obsoleted and replaced by
        docsIfCmtsInsertInterval to fix a SYNTAX typing problem."
    REFERENCE
       "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Annex B."
    ::= { docsIfCmtsMacEntry 5 }

docsIfCmtsInvitedRangingAttempts OBJECT-TYPE
    SYNTAX      Integer32 (0..1024)
    UNITS      "attempts"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
       "The maximum number of attempts to make on invitations
        for ranging requests.  A value of zero means the system
        SHOULD attempt to range forever."
    REFERENCE
       "Data-Over-Cable Service Interface Specifications: Radio
        Frequency
 Interface Specification SP-RFIv2.0-I10-051209,
        Section 9.3.3 and Annex B."
    ::= { docsIfCmtsMacEntry 6 }

docsIfCmtsInsertInterval OBJECT-TYPE
    SYNTAX      TimeInterval
    UNITS       "HundredOfSeconds"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
       "The amount of time to elapse between each broadcast
        initial maintenance grant.  Broadcast initial maintenance
        grants are used to allow new cable modems to join the
        network.  Zero indicates that a vendor-specific algorithm
        is used instead of a fixed time.  The maximum amount of
        time permitted by the specification is 2 seconds."
    REFERENCE
       "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Annex B."
    ::= { docsIfCmtsMacEntry 7 }
```

```
docsIfCmtsMacStorageType OBJECT-TYPE
   SYNTAX       StorageType
   MAX-ACCESS   read-only
   STATUS
     current
   DESCRIPTION
      "The storage type for this conceptual row.



       Entries with this object set to permanent(4)
       do not require write operations for read-write
       objects."
   ::= { docsIfCmtsMacEntry 8 }

--
--
-- CMTS status table.
--

docsIfCmtsStatusTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF DocsIfCmtsStatusEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "For the MAC layer, this group maintains a number of
       status objects and counters."
   ::= { docsIfCmtsObjects 2 }

docsIfCmtsStatusEntry OBJECT-TYPE
   SYNTAX      DocsIfCmtsStatusEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
     "Status entry for a single MAC layer.
       An entry in this table exists for each ifEntry with an
       ifType of docsCableMaclayer(127)."
   INDEX { ifIndex }
   ::= { docsIfCmtsStatusTable 1 }

DocsIfCmtsStatusEntry ::= SEQUENCE {
       docsIfCmtsStatusInvalidRangeReqs
       Counter32,
       docsIfCmtsStatusRangingAborteds         Counter32,
       docsIfCmtsStatusInvalidRegReqs          Counter32,
       docsIfCmtsStatusFailedRegReqs           Counter32,
       docsIfCmtsStatusInvalidDataReqs         Counter32,
```

```
      docsIfCmtsStatusT5Timeouts              Counter32
   }

docsIfCmtsStatusInvalidRangeReqs OBJECT-TYPE
   SYNTAX      Counter32
   UNITS       "messages"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "This object counts invalid RNG-REQ messages received on
       this interface.
       Discontinuities in the value of this counter can occur




       at reinitialization of the managed system, and at other
       times as indicated by the value of
       ifCounterDiscontinuityTime for the associated ifIndex."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 8.3.5."
   ::= { docsIfCmtsStatusEntry 1 }

docsIfCmtsStatusRangingAborteds OBJECT-TYPE
   SYNTAX      Counter32
   UNITS       "attempts"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "This object counts ranging attempts that were explicitly
       aborted by the CMTS.
       Discontinuities in the value of this counter can occur
       at reinitialization of the managed system, and at other
       times as indicated by the value of
       ifCounterDiscontinuityTime for the associated ifIndex."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Section 8.3.6."
   ::= { docsIfCmtsStatusEntry 2 }

docsIfCmtsStatusInvalidRegReqs OBJECT-TYPE
   SYNTAX      Counter32
   UNITS       "messages"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
```

"This object counts invalid REG-REQ messages
received on
this interface; that is, syntax, out of range parameters,
or erroneous requests.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 8.3.7."
::= { docsIfCmtsStatusEntry 3 }

docsIfCmtsStatusFailedRegReqs OBJECT-TYPE
SYNTAX Counter32

UNITS "attempts"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This object counts failed registration attempts. Included
are docsIfCmtsStatusInvalidRegReqs, authentication, and
class of service failures.
Discontinuities in the value of this counter can occur
at reinitialization
of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 8.3.7."
::= { docsIfCmtsStatusEntry 4 }

docsIfCmtsStatusInvalidDataReqs OBJECT-TYPE
SYNTAX Counter32
UNITS "messages"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This object counts invalid data request messages
received on this interface.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of

```
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsStatusEntry 5 }

docsIfCmtsStatusT5Timeouts OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "timeouts"
     MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object counts the number of times counter T5
         expired on this interface.
         Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Figure 9-2."
    ::= { docsIfCmtsStatusEntry 6 }



--
-- CM status table (within CMTS).
-- This table is implemented only at the CMTS.
-- It contains per-CM status information available in the CMTS.
--

docsIfCmtsCmStatusTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfCmtsCmStatusEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A set of objects in the CMTS, maintained for each
         cable modem connected to this CMTS."
    ::= { docsIfCmtsObjects 3 }

docsIfCmtsCmStatusEntry OBJECT-TYPE
    SYNTAX      DocsIfCmtsCmStatusEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Status information for a single cable modem.
         An entry in this table exists for each cable modem
         that is connected to the CMTS implementing this table."
    INDEX { docsIfCmtsCmStatusIndex }
    ::= { docsIfCmtsCmStatusTable 1 }
```

```
DocsIfCmtsCmStatusEntry ::= SEQUENCE {
      docsIfCmtsCmStatusIndex             Integer32,
      docsIfCmtsCmStatusMacAddress        MacAddress,
      docsIfCmtsCmStatusIpAddress         IpAddress, -- deprecated
      docsIfCmtsCmStatusDownChannelIfIndex  InterfaceIndexOrZero,
      docsIfCmtsCmStatusUpChannelIfIndex    InterfaceIndexOrZero,
      docsIfCmtsCmStatusRxPower           TenthdBmV,
      docsIfCmtsCmStatusTimingOffset      Unsigned32,
      docsIfCmtsCmStatusEqualizationData
   DocsEqualizerData,
      docsIfCmtsCmStatusValue             INTEGER,
      docsIfCmtsCmStatusUnerroreds        Counter32,
      docsIfCmtsCmStatusCorrecteds        Counter32,
      docsIfCmtsCmStatusUncorrectables    Counter32,
      docsIfCmtsCmStatusSignalNoise       TenthdB,
      docsIfCmtsCmStatusMicroreflections  Integer32,
      docsIfCmtsCmStatusExtUnerroreds     Counter64,
      docsIfCmtsCmStatusExtCorrecteds     Counter64,
      docsIfCmtsCmStatusExtUncorrectables Counter64,
      docsIfCmtsCmStatusDocsisRegMode     DocsisQosVersion,
      docsIfCmtsCmStatusModulationType    DocsisUpstreamType,
      docsIfCmtsCmStatusInetAddressType   InetAddressType,
      docsIfCmtsCmStatusInetAddress       InetAddress,



      docsIfCmtsCmStatusValueLastUpdate   TimeStamp,
      docsIfCmtsCmStatusHighResolutionTimingOffset Unsigned32
   }

docsIfCmtsCmStatusIndex OBJECT-TYPE
   SYNTAX
   Integer32 (1..2147483647)
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "Index value to uniquely identify an entry in this table.
       For an individual cable modem, this index value SHOULD
       NOT change during CMTS uptime."
   ::= { docsIfCmtsCmStatusEntry 1 }

docsIfCmtsCmStatusMacAddress OBJECT-TYPE
   SYNTAX      MacAddress
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "MAC address of the cable modem.  If the cable modem has
```

multiple MAC addresses, this is the MAC address associated
with the Cable interface."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 8.2.2."
::= { docsIfCmtsCmStatusEntry 2 }

docsIfCmtsCmStatusIpAddress OBJECT-TYPE
SYNTAX IpAddress
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
"IP address
of this cable modem. If the cable modem has no
IP address assigned, or the IP address is unknown, this
object returns a value of 0.0.0.0. If the cable modem has
multiple IP addresses, this object returns the IP address
associated with the Cable interface.
This object has been deprecated and replaced by
docsIfCmtsCmStatusInetAddressType and
docsIfCmtsCmStatusInetAddress, to enable IPv6 addressing
in the future."
::= { docsIfCmtsCmStatusEntry 3 }

docsIfCmtsCmStatusDownChannelIfIndex OBJECT-TYPE
SYNTAX InterfaceIndexOrZero
MAX-ACCESS read-only
STATUS current

DESCRIPTION
"IfIndex of the downstream channel that this CM is
connected to. If the downstream channel is unknown, this
object returns a value of zero."
::= { docsIfCmtsCmStatusEntry 4 }

docsIfCmtsCmStatusUpChannelIfIndex OBJECT-TYPE
SYNTAX InterfaceIndexOrZero
MAX-ACCESS
read-only
STATUS current
DESCRIPTION
"For DOCSIS 2.0, indicates the ifIndex of the logical
upstream channel (ifType 205) this CM is connected to.
For DOCSIS 1.x, indicates the ifIndex of the upstream
channel (ifType 129) this CM is connected to.

```
        If the upstream channel is unknown, this object
        returns a value of zero."
    ::= { docsIfCmtsCmStatusEntry 5 }

docsIfCmtsCmStatusRxPower OBJECT-TYPE
    SYNTAX      TenthdBmV
    UNITS       "ThenthdBmV"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The receive power as perceived for upstream data from
        this cable modem.
        If the receive power is unknown, this object returns
        a value of zero."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.18."
    ::= { docsIfCmtsCmStatusEntry 6
 }

docsIfCmtsCmStatusTimingOffset OBJECT-TYPE
    SYNTAX      Unsigned32 (0..4294967295)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A measure of the current round trip time for this CM.
        Used for timing of CM upstream transmissions to ensure
        synchronized arrivals at the CMTS.  Units are in terms
        of (6.25 microseconds/64).  Returns zero if the value
        is unknown.
        For channels requiring finer resolution, please refer to
        object docsIfCmtsCmStatusHighResolutionTimingOffset."
    REFERENCE




        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.17."
    ::= { docsIfCmtsCmStatusEntry 7 }

docsIfCmtsCmStatusEqualizationData OBJECT-TYPE
    SYNTAX      DocsEqualizerData
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Equalization data for this CM, as measured by the CMTS.
```

```
        Returns the zero-length OCTET STRING if the value is
        unknown or if there is no equalization data available
        or defined."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Figure 8-23."
    ::= { docsIfCmtsCmStatusEntry 8 }

docsIfCmtsCmStatusValue OBJECT-TYPE
    SYNTAX      INTEGER {
        other(1),
        ranging(2),
        rangingAborted(3),
        rangingComplete(4),
        ipComplete(5),
        registrationComplete(6),
        accessDenied(7),
        operational(8),
        -- value 8 should not be used
        registeredBPIInitializing(9)
    }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Current cable modem connectivity state, as specified
        in the RF Interface Specification.  Returned status
        information is the CM status, as assumed by the CMTS,
        and indicates
 the following events:
        other(1)
          Any state other than below.
        ranging(2)
          The CMTS has received an Initial Ranging Request
          message from the CM, and the ranging process is not
          yet complete.
        rangingAborted(3)
          The CMTS has sent a Ranging Abort message to the CM.



        rangingComplete(4)
          The CMTS has sent a Ranging Complete message to the CM.
        ipComplete(5)
          The CMTS has received a DHCP reply message and
          forwarded it to the CM.
        registrationComplete(6)
          The CMTS has sent a Registration Response message to
```

the CM.
accessDenied(7)
The CMTS has sent a Registration Aborted message
to the CM.
operational(8)
Value 8 is considered reserved and should not be defined
in future revisions of this MIB module to avoid conflict
with documented
implementations that support value 8 to
indicate operational state after completing the BPI
initialization process.
registeredBPIInitializing(9)
Baseline Privacy (BPI) is enabled and the CMTS is in the
process of completing BPI initialization. This state
MAY last for a significant length of time if failures
occur during the initialization process. After
completion of BPI initialization, the CMTS will report
registrationComplete(6).
The CMTS only needs to report states it is able to
detect."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 11.2."
::= { docsIfCmtsCmStatusEntry 9 }

docsIfCmtsCmStatusUnerroreds OBJECT-TYPE
SYNTAX Counter32
UNITS "codewords"
MAX-ACCESS read-only
STATUS current

DESCRIPTION
"Codewords received without error from this cable modem.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
REFERENCE
"Data-Over-Cable Service Interface Specifications: Radio
Frequency Interface Specification SP-RFIv2.0-I10-051209,
Section 6.2.4."
::= { docsIfCmtsCmStatusEntry 10 }

docsIfCmtsCmStatusCorrecteds OBJECT-TYPE
SYNTAX Counter32

```
    UNITS       "codewords"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Codewords received with correctable errors from this
         cable modem.
         Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime
  for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Section 6.2.4."
    ::= { docsIfCmtsCmStatusEntry 11 }

docsIfCmtsCmStatusUncorrectables OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "codewords"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Codewords received with uncorrectable errors from this
         cable modem.
         Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Section 6.2.4."
    ::= { docsIfCmtsCmStatusEntry 12 }

docsIfCmtsCmStatusSignalNoise OBJECT-TYPE
     SYNTAX      TenthdB
    UNITS       "TenthdB"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Signal/Noise ratio as perceived for upstream data from
         this cable modem.
         If the Signal/Noise is unknown, this object returns
         a value of zero."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
```

```
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Tables 4-1 and 4-2."
    ::= { docsIfCmtsCmStatusEntry 13 }

docsIfCmtsCmStatusMicroreflections OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    UNITS       "-dBc"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Total microreflections, including in-channel response
        as perceived on this interface, measured in dBc below
        the signal level.
        This object is not assumed to return an absolutely
        accurate value, but it gives a rough indication
        of microreflections
 received on this interface.
        It is up to the implementer to provide information
        as accurately as possible.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Tables 4-1 and 4-2"
    ::= { docsIfCmtsCmStatusEntry 14 }

docsIfCmtsCmStatusExtUnerroreds OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "codewords"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Codewords received without error from this cable modem.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the
 value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Section 6.2.5."
    ::= { docsIfCmtsCmStatusEntry 15 }
```

```
docsIfCmtsCmStatusExtCorrecteds OBJECT-TYPE
   SYNTAX      Counter64
   UNITS       "codewords"



   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "Codewords received with correctable errors from this
       cable modem.
       Discontinuities in the value of this counter can occur
       at reinitialization of the managed system, and at other
       times as indicated by the value of
       ifCounterDiscontinuityTime for the associated ifIndex."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Section 6.2.5."
   ::= { docsIfCmtsCmStatusEntry
 16 }

docsIfCmtsCmStatusExtUncorrectables OBJECT-TYPE
   SYNTAX      Counter64
   UNITS       "codewords"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "Codewords received with uncorrectable errors from this
       cable modem.
       Discontinuities in the value of this counter can occur
       at reinitialization of the managed system, and at other
       times as indicated by the value of
       ifCounterDiscontinuityTime for the associated ifIndex."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Section 6.2.5."
   ::= { docsIfCmtsCmStatusEntry 17 }

docsIfCmtsCmStatusDocsisRegMode OBJECT-TYPE
      SYNTAX      DocsisQosVersion
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "Indication of whether the CM has registered using 1.0
          Class of Service or 1.1 Quality of Service."
```

```
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Annex G."
    ::= { docsIfCmtsCmStatusEntry 18 }

docsIfCmtsCmStatusModulationType OBJECT-TYPE
    SYNTAX      DocsisUpstreamType



    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Indicates modulation type currently used by the CM.  Since
         this object specifically identifies PHY mode, the shared
         type is not permitted.  If the upstream channel is
         unknown, this object returns a value of zero."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Table 8-19."
    ::= { docsIfCmtsCmStatusEntry 19 }

docsIfCmtsCmStatusInetAddressType OBJECT-TYPE
      SYNTAX      InetAddressType
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
          "The type of internet address of
          docsIfCmtsCmStatusInetAddress.  If the cable modem
          internet address is unassigned or unknown, then the
          value of this object is unknown(0)."
      ::= { docsIfCmtsCmStatusEntry 20 }

docsIfCmtsCmStatusInetAddress OBJECT-TYPE
      SYNTAX      InetAddress
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
          "Internet address of this cable modem.  If the Cable
          Modem has no Internet address assigned, or the Internet
          address is unknown, the value of this object is the
          zero-length OCTET STRING.  If the cable modem has
          multiple Internet addresses, this object returns the
          Internet address associated with the Cable
          (i.e., RF MAC) interface."
      ::= { docsIfCmtsCmStatusEntry 21 }
```

```
docsIfCmtsCmStatusValueLastUpdate OBJECT-TYPE
      SYNTAX      TimeStamp
      MAX-ACCESS  read-only
       STATUS      current
      DESCRIPTION
         "The value of sysUpTime when docsIfCmtsCmStatusValue
          was last updated."
      ::= { docsIfCmtsCmStatusEntry 22 }

docsIfCmtsCmStatusHighResolutionTimingOffset OBJECT-TYPE



   SYNTAX      Unsigned32 (0..4294967295)
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "A measure of the current round trip time for this CM.
       Used for timing of CM upstream transmissions to ensure
       synchronized arrivals at the CMTS.  Units are in terms
       of (6.25 microseconds/(64*256)).  Returns zero if the value
       is unknown.
       This is the high resolution version of object
       docsIfCmtsCmStatusTimingOffset, for channels requiring
       finer resolution."
   REFERENCE
      "Data-Over-Cable Service Interface Specifications: Radio
       Frequency Interface Specification SP-RFIv2.0-I10-051209,
       Section 6.2.17."
   ::= { docsIfCmtsCmStatusEntry
 23 }

--
-- The CMTS Service Table.
--

docsIfCmtsServiceTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF DocsIfCmtsServiceEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "Describes the attributes of upstream service queues
       in a Cable Modem Termination System."
   ::= { docsIfCmtsObjects 4 }

docsIfCmtsServiceEntry OBJECT-TYPE
   SYNTAX      DocsIfCmtsServiceEntry
```

```
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Describes the attributes of a single upstream bandwidth
         service queue.
         Entries in this table exist for each ifEntry with an
         ifType of docsCableMaclayer(127), and for each service
         queue (Service ID) within this MAC layer.
         Entries in this table are created with the creation of
         individual Service IDs by the MAC layer and removed
         when a Service ID is removed."
    INDEX { ifIndex, docsIfCmtsServiceId }
    ::= { docsIfCmtsServiceTable
 1 }

DocsIfCmtsServiceEntry ::= SEQUENCE {



        docsIfCmtsServiceId             Integer32,
        docsIfCmtsServiceCmStatusIndex    Integer32,  -- deprecated
        docsIfCmtsServiceAdminStatus      INTEGER,
        docsIfCmtsServiceQosProfile       Integer32,
        docsIfCmtsServiceCreateTime       TimeStamp,
        docsIfCmtsServiceInOctets         Counter32,
        docsIfCmtsServiceInPackets        Counter32,
        docsIfCmtsServiceNewCmStatusIndex Integer32
    }

docsIfCmtsServiceId OBJECT-TYPE
    SYNTAX      Integer32 (1..16383)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Identifies a service queue for upstream bandwidth.  The
         attributes of this service queue are shared between the
         Cable Modem and the Cable Modem Termination System.
         The CMTS allocates upstream bandwidth to this service
         queue based on requests from the CM and on the class of
         service
 associated with this queue."
    ::= { docsIfCmtsServiceEntry 1 }

docsIfCmtsServiceCmStatusIndex OBJECT-TYPE
    SYNTAX      Integer32 (0..65535)
    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
```

"Pointer to an entry in docsIfCmtsCmStatusTable identifying
the cable modem using this Service Queue. If multiple
cable modems are using this Service Queue, the value of
this object is zero.
This object has been deprecated and replaced by
docsIfCmtsServiceNewCmStatusIndex, to fix a mismatch
of the value range with respect to docsIfCmtsCmStatusIndex
(1..2147483647)."
::= { docsIfCmtsServiceEntry 2 }

docsIfCmtsServiceAdminStatus OBJECT-TYPE
SYNTAX INTEGER {
enabled(1),
disabled(2),
destroyed(3) }
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"Allows a service class for a particular modem to be
suppressed,
(re-)enabled, or deleted altogether."

::= { docsIfCmtsServiceEntry 3 }

docsIfCmtsServiceQosProfile OBJECT-TYPE
SYNTAX Integer32 (0..16383)
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The index in docsIfQosProfileTable describing the quality
of service attributes associated with this particular
service. If no associated docsIfQosProfileTable entry
exists, this object returns a value of zero."
::= { docsIfCmtsServiceEntry 4 }

docsIfCmtsServiceCreateTime OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime when this entry was created."
::= { docsIfCmtsServiceEntry 5 }

docsIfCmtsServiceInOctets OBJECT-TYPE
SYNTAX Counter32
UNITS "Bytes"

MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The cumulative number of Packet Data octets received
on this Service
ID. The count does not include the
size of the Cable MAC header.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsServiceEntry 6 }

docsIfCmtsServiceInPackets OBJECT-TYPE
SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The cumulative number of Packet Data packets received
on this Service ID.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."

::= { docsIfCmtsServiceEntry 7 }

docsIfCmtsServiceNewCmStatusIndex OBJECT-TYPE
SYNTAX Integer32 (0..2147483647)
MAX-ACCESS
read-only
STATUS current
DESCRIPTION
"Pointer (via docsIfCmtsCmStatusIndex) to an entry in
docsIfCmtsCmStatusTable identifying the cable modem
using this Service Queue. If multiple cable modems are
using this Service Queue, the value of this object is
zero."
::= { docsIfCmtsServiceEntry 8 }

--
-- The following table provides upstream channel modulation profiles.
-- Entries in this table can be
-- re-used by one or more upstream channels. An upstream channel
-- will have a modulation profile for each value of

```
-- docsIfModIntervalUsageCode.
--

docsIfCmtsModulationTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF DocsIfCmtsModulationEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "Describes a modulation profile associated with one or more
       upstream channels."
   ::= { docsIfCmtsObjects 5 }

docsIfCmtsModulationEntry OBJECT-TYPE
   SYNTAX      DocsIfCmtsModulationEntry
    MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "Describes a modulation profile for an Interval Usage Code
       for one or more upstream channels.
       Entries in this table are created by the operator.

       Initial default entries MAY be created at system
       initialization time, which could report a value of
       'permanent' or 'readOnly' for docsIfCmtsModStorageType.
       A CMTS MAY reject the creation of additional Interval
       Usage Codes for a modulation profile being defined at
       Initialization time.
       No individual objects have to be specified in order
       to create an entry in this table.



       Note that some objects do not have DEFVAL clauses
       but do have calculated defaults and need not be specified
       during row creation."
    INDEX { docsIfCmtsModIndex, docsIfCmtsModIntervalUsageCode}
   ::= { docsIfCmtsModulationTable 1 }

DocsIfCmtsModulationEntry
 ::= SEQUENCE {
       docsIfCmtsModIndex                Integer32,
       docsIfCmtsModIntervalUsageCode       INTEGER,
       docsIfCmtsModControl               RowStatus,
       docsIfCmtsModType                 INTEGER,
       docsIfCmtsModPreambleLen            Integer32,
       docsIfCmtsModDifferentialEncoding    TruthValue,
       docsIfCmtsModFECErrorCorrection      Integer32,
       docsIfCmtsModFECCodewordLength       Integer32,
```

```
        docsIfCmtsModScramblerSeed          Integer32,
        docsIfCmtsModMaxBurstSize           Integer32,
        docsIfCmtsModGuardTimeSize          Unsigned32,
        docsIfCmtsModLastCodewordShortened  TruthValue,
        docsIfCmtsModScrambler              TruthValue,
        docsIfCmtsModByteInterleaverDepth   Unsigned32,
        docsIfCmtsModByteInterleaverBlockSize Unsigned32,
        docsIfCmtsModPreambleType           INTEGER,
        docsIfCmtsModTcmErrorCorrectionOn   TruthValue,
        docsIfCmtsModScdmaInterleaverStepSize Unsigned32,
        docsIfCmtsModScdmaSpreaderEnable    TruthValue,
        docsIfCmtsModScdmaSubframeCodes     Unsigned32,
        docsIfCmtsModChannelType            DocsisUpstreamType,
        docsIfCmtsModStorageType            StorageType
    }

docsIfCmtsModIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An index into the Channel Modulation table representing
        a group of Interval Usage Codes, all associated with the
        same channel."
    ::= { docsIfCmtsModulationEntry 1 }

docsIfCmtsModIntervalUsageCode OBJECT-TYPE
    SYNTAX      INTEGER {
        request(1),
        requestData(2),
        initialRanging(3),
        periodicRanging(4),
        shortData(5),




        longData(6),
        advPhyShortData(9),
        advPhyLongData(10),
        ugs(11)
    }
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An index into the Channel Modulation table that, when
        grouped with other Interval Usage Codes, fully
        instantiates all modulation sets for a given upstream
        channel."
```

```
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Table 8-20."
    ::= { docsIfCmtsModulationEntry 2 }

docsIfCmtsModControl OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Controls and reflects the status of rows in this table.
         There is no restriction on the changing of values in this
         table while their associated rows are active, with the
         exception of:

         1. If a modulation profile is being referenced by one
            or more upstream channels, an attempt to set the value
            of docsIfCmtsModChannelType returns
 an
            'inconsistentValue' error.

         2. If a modulation profile is being referenced by one
            or more upstream channels, an attempt to set
            docsIfCmtsModControl to destroy(6) or notInService(2)
            returns an 'inconsistentValue' error."
    ::= { docsIfCmtsModulationEntry 3 }

docsIfCmtsModType OBJECT-TYPE
    SYNTAX      INTEGER {
        other(1),
        qpsk(2),
        qam16(3),
        qam8(4),
        qam32(5),
        qam64(6),
        qam128(7)




    }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The modulation type used on this channel.  Returns
         other(1) if the modulation type is not
         qpsk, qam16, qam8, qam32, qam64, or qam128.
         Type qam128 is used for SCDMA channels only.
```

```
        See the reference for the modulation profiles
        implied by different modulation types."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications:
 Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Tables 6-7, and 8-19."
    DEFVAL { qpsk }
    ::= { docsIfCmtsModulationEntry 4 }

docsIfCmtsModPreambleLen OBJECT-TYPE
    SYNTAX      Integer32 (0..1536)
    UNITS       "bits"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The preamble length for this modulation profile in bits.
        Default value is the minimum needed by the implementation
        at the CMTS for the given modulation profile."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Tables 6-7, and 8-19."
    ::= { docsIfCmtsModulationEntry 5 }

docsIfCmtsModDifferentialEncoding OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Specifies whether or not differential encoding is used
        on this channel."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Tables 6-7, and 8-19."
    DEFVAL { false }
    ::= { docsIfCmtsModulationEntry 6 }

docsIfCmtsModFECErrorCorrection OBJECT-TYPE
    SYNTAX      Integer32 (0..16)



    UNITS       "Bytes"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
```

```
        "The number of correctable errored bytes (t) used in
         forward error correction code.  The value of 0 indicates
         that no correction is employed.  The number of check bytes
         appended will be twice this value."
      REFERENCE
         "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
      DEFVAL { 0 }
      ::= { docsIfCmtsModulationEntry 7 }

docsIfCmtsModFECCodewordLength OBJECT-TYPE
      SYNTAX      Integer32 (1..255)
      UNITS       "Bytes"
       MAX-ACCESS  read-create
      STATUS      current
      DESCRIPTION
         "The number of data bytes (k) in the forward error
         correction codeword.
         This object is not used if docsIfCmtsModFECErrorCorrection
         is zero."
      REFERENCE
         "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
      DEFVAL { 32 }
      ::= { docsIfCmtsModulationEntry 8 }

docsIfCmtsModScramblerSeed OBJECT-TYPE
      SYNTAX      Integer32 (0..32767)
      MAX-ACCESS  read-create
      STATUS      current
      DESCRIPTION
         "The 15-bit seed value for the scrambler polynomial."
      REFERENCE
         "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Table 8-19."
      DEFVAL { 0 }
      ::= { docsIfCmtsModulationEntry 9 }

docsIfCmtsModMaxBurstSize OBJECT-TYPE
      SYNTAX      Integer32
    (0..255)
      UNITS       "mini-slots"
```

```
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The maximum number of mini-slots that can be transmitted
         during this channel's burst time.  Returns zero if the
         burst length is bounded by the allocation MAP rather than
         by this profile.
         Default value is 0, except for shortData, where it is 8."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Table 8-19."
    ::= { docsIfCmtsModulationEntry 10 }

docsIfCmtsModGuardTimeSize OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "Symbol-times"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of symbol-times that MUST follow the end of
         this channel's burst.  Default value is the minimum time
         needed by the implementation for this modulation profile."

 REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
    ::= { docsIfCmtsModulationEntry 11 }

docsIfCmtsModLastCodewordShortened OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Indicates whether the last FEC codeword is truncated."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
    DEFVAL { true }
    ::= { docsIfCmtsModulationEntry 12 }

docsIfCmtsModScrambler OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
```

```
        "Indicates whether the scrambler is employed."



    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
          Tables 6-7, and 8-19."
    DEFVAL { false }
    ::= { docsIfCmtsModulationEntry 13 }

docsIfCmtsModByteInterleaverDepth OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "ATDMA Byte Interleaver Depth (Ir).  This object returns 1
         for non-ATDMA profiles."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
    DEFVAL { 1 }
    ::= { docsIfCmtsModulationEntry 14 }

docsIfCmtsModByteInterleaverBlockSize OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "ATDMA Byte Interleaver Block size (Br).  This object
         returns zero for non-ATDMA profiles "
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
          Tables 6-7, and 8-19."
    DEFVAL { 18 }
    ::= { docsIfCmtsModulationEntry 15 }

docsIfCmtsModPreambleType OBJECT-TYPE
    SYNTAX      INTEGER {
        unknown(0),
        qpsk0(1),
        qpsk1(2)
    }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
```

```
        "Preamble type for DOCSIS 2.0 bursts.  The value
         'unknown(0)' represents a row entry consisting only of
         DOCSIS 1.x bursts"
    REFERENCE



        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
    DEFVAL { qpsk0 }
    ::= { docsIfCmtsModulationEntry 16 }

docsIfCmtsModTcmErrorCorrectionOn OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Trellis Code Modulation (TCM) On/Off.  This value returns
         false for non-S-CDMA profiles."
    REFERENCE
        "Data-Over-Cable
  Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
    DEFVAL { false }
    ::= { docsIfCmtsModulationEntry 17 }

docsIfCmtsModScdmaInterleaverStepSize OBJECT-TYPE
    SYNTAX      Unsigned32 (0 | 1..32)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        " S-CDMA Interleaver step size.  This value returns zero
          for non-S-CDMA profiles."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
         Frequency Interface Specification SP-RFIv2.0-I10-051209,
         Tables 6-7, and 8-19."
    DEFVAL { 1 }
    ::= { docsIfCmtsModulationEntry 18 }

docsIfCmtsModScdmaSpreaderEnable OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        " S-CDMA spreader.  This value returns false for non-S-CDMA
```

```
        profiles.  Default value for IUC 3 and 4 is OFF; for

      all other IUCs it is ON."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Tables 6-7, and 8-19."
    ::= { docsIfCmtsModulationEntry 19 }




docsIfCmtsModScdmaSubframeCodes OBJECT-TYPE
    SYNTAX      Unsigned32 (0 | 1..128)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        " S-CDMA sub-frame size.  This value returns zero
         for non-S-CDMA profiles."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Table 6-7, and 8-19."
    DEFVAL { 1 }
    ::= { docsIfCmtsModulationEntry 20 }

docsIfCmtsModChannelType OBJECT-TYPE
    SYNTAX      DocsisUpstreamType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Describes the modulation channel type for this modulation
        entry.
        All the active
 entries in a modulation profile (that is all
        active entries that share a common docsIfCmtsModIndex)
        MUST have the same value of docsIfCmtsModChannelType."
    REFERENCE
        "Data-Over-Cable Service Interface Specifications: Radio
        Frequency Interface Specification SP-RFIv2.0-I10-051209,
        Table 8-19."
    DEFVAL { tdma }
    ::= { docsIfCmtsModulationEntry 21 }

docsIfCmtsModStorageType OBJECT-TYPE
    SYNTAX       StorageType
    MAX-ACCESS   read-only
    STATUS       current
```

```
    DESCRIPTION
        "The storage type for this conceptual row.
         Entries with this object set to permanent(4)
         do not require write operations for read-write
         objects."
    DEFVAL      { nonVolatile }
::= { docsIfCmtsModulationEntry 22 }

docsIfCmtsQosProfilePermissions OBJECT-TYPE
    SYNTAX      BITS {
        createByManagement(0),
        updateByManagement(1),
        createByModems(2)




    }
    MAX-ACCESS  read-write
     STATUS      current
    DESCRIPTION
        "This object specifies permitted methods of creating
         entries in docsIfQosProfileTable.
         createByManagement(0) is set if entries can be created
         using SNMP.  updateByManagement(1) is set if updating
         entries using SNMP is permitted.  createByModems(2)
         is set if entries can be created based on information
         in REG-REQ MAC messages received from cable modems.
         Information in this object is only applicable if
         docsIfQosProfileTable is implemented as read-create.
         Otherwise, this object is implemented as read-only
         and returns createByModems(2).
         Either createByManagement(0) or updateByManagement(1)
         MUST be set when writing to this object.
         Note that BITS objects are encoded most significant bit
         first.  For example, if bit 2 is set, the value of this
         object is the octet string '20'H."
    ::= { docsIfCmtsObjects
 6 }

docsIfCmtsMacToCmTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfCmtsMacToCmEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This is a table to provide a quick access index into the
         docsIfCmtsCmStatusTable.  There is exactly one row in this
         table for each row in the docsIfCmtsCmStatusTable.  In
         general, the management station SHOULD use this table only
```

```
        to get a pointer into the docsIfCmtsCmStatusTable (which
        corresponds to the CM's RF interface MAC address) and
        SHOULD not iterate (e.g., GetNext through) this table."
    ::= { docsIfCmtsObjects 7 }

docsIfCmtsMacToCmEntry OBJECT-TYPE
    SYNTAX      DocsIfCmtsMacToCmEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A row in the docsIfCmtsMacToCmTable.
        An entry in this table exists for each cable modem
        that is connected to the CMTS implementing this table."
     INDEX   { docsIfCmtsCmMac }
    ::= {docsIfCmtsMacToCmTable 1 }

DocsIfCmtsMacToCmEntry ::= SEQUENCE {




        docsIfCmtsCmMac     MacAddress,
        docsIfCmtsCmPtr     Integer32
    }

docsIfCmtsCmMac OBJECT-TYPE
    SYNTAX      MacAddress
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The RF side MAC address for the referenced CM (e.g., the
        interface on the CM that has docsCableMacLayer(127) as
        its ifType)."
    ::= { docsIfCmtsMacToCmEntry 1 }

docsIfCmtsCmPtr OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "An row index into docsIfCmtsCmStatusTable.  When queried
        with the correct instance value (e.g., a CM's MAC address),
        returns the index in docsIfCmtsCmStatusTable that
        represents that CM."
    ::= { docsIfCmtsMacToCmEntry 2 }

-- The following independent object and associated table
 provide
-- operators with a mechanism to evaluate the load/utilization of
```

```
-- both upstream and downstream physical channels.  This information
-- may be used for capacity planning and incident analysis and may
-- be particularly helpful in provisioning of high value QOS.
--
-- Utilization is expressed as an index representing the calculated
-- percentage utilization of the upstream or downstream channel in
-- the most recent sampling interval (i.e., utilization interval).
-- Refer to the DESCRIPTION field of the
-- docsIfCmtsChannelUtUtilization object for definitions and
-- calculation details.

docsIfCmtsChannelUtilizationInterval OBJECT-TYPE
   SYNTAX      Integer32 (0..86400)
   UNITS       "seconds"
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION
      "The time interval in seconds over which the channel
       utilization index is calculated.  All upstream/downstream
       channels use the same
       docsIfCmtsChannelUtilizationInterval.



        Setting a value of zero disables utilization reporting.
       A channel utilization index is calculated over a fixed
       window applying to the most recent
       docsIfCmtsChannelUtilizationInterval.  It would therefore
       be prudent to use a relatively short
       docsIfCmtsChannelUtilizationInterval.
       It is a vendor decision whether to reset the timer when
       docsIfCmtsChannelUtilizationInterval is changed during a
       utilization sampling period."
   ::= { docsIfCmtsObjects 8 }

docsIfCmtsChannelUtilizationTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF DocsIfCmtsChannelUtilizationEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "Reports utilization statistics for attached upstream and
       downstream physical channels."
   ::= { docsIfCmtsObjects 9 }

docsIfCmtsChannelUtilizationEntry OBJECT-TYPE
   SYNTAX      DocsIfCmtsChannelUtilizationEntry
   MAX-ACCESS  not-accessible
```

```
    STATUS      current
    DESCRIPTION
        "Utilization statistics for a single upstream or downstream
         physical channel.  An entry exists in this table for each
         ifEntry with an ifType equal to
         docsCableDownstream (128)
         or docsCableUpstream (129)."
    INDEX  { ifIndex, docsIfCmtsChannelUtIfType,
         docsIfCmtsChannelUtId }
    ::= { docsIfCmtsChannelUtilizationTable 1 }

DocsIfCmtsChannelUtilizationEntry ::= SEQUENCE {
        docsIfCmtsChannelUtIfType        IANAifType,
        docsIfCmtsChannelUtId            Integer32,
        docsIfCmtsChannelUtUtilization   Integer32
    }

docsIfCmtsChannelUtIfType OBJECT-TYPE
    SYNTAX      IANAifType
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The secondary index into this table.  Indicates the IANA
         interface type associated with this physical channel.
         Only docsCableDownstream (128) and




         docsCableUpstream
 (129) are valid."
    ::= { docsIfCmtsChannelUtilizationEntry 1 }

docsIfCmtsChannelUtId OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The tertiary index into this table.  Indicates the CMTS
         identifier for this physical channel."
    ::= { docsIfCmtsChannelUtilizationEntry 2 }

docsIfCmtsChannelUtUtilization OBJECT-TYPE
    SYNTAX      Integer32 (0..100)
    UNITS       "percent"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The calculated and truncated utilization index for this
```

physical upstream or downstream channel, accurate as of the most recent docsIfCmtsChannelUtilizationInterval.

Upstream Channel Utilization Index:

The upstream channel utilization index is expressed as a percentage of mini-slots utilized on the physical channel, regardless of burst type. For an Initial Maintenance region, the mini-slots for the complete region are considered utilized if the CMTS received an upstream burst within the region from any CM on the physical channel. For contention REQ and REQ/DATA regions, the mini-slots for a transmission opportunity within the region are considered utilized if the CMTS received an upstream burst within the opportunity from any CM on the physical channel. For all other regions, utilized mini-slots are those in which the CMTS granted bandwidth to any unicast SID on the physical channel.

For an upstream interface that has multiple logical upstream channels enabled, the utilization index is a weighted sum of utilization indices for the logical channels. The weight for each utilization index is the percentage of upstream mini-slots allocated for the corresponding logical channel.

Example:

If 75% of bandwidth is allocated to the first logical channel and 25% to the second, and the utilization indices for each are 60 and 40, respectively, the utilization index for the upstream physical channel is (60 * 0.75) + (40 * 0.25) = 55. This figure applies to the most recent utilization interval.

Downstream Channel Utilization Index:

The downstream channel utilization index is a percentage expressing the ratio between bytes used to transmit data versus the total number of bytes transmitted in the raw bandwidth of the MPEG channel. As with the upstream utilization index, the calculated value represents the most recent utilization interval.

Formula:

Downstream utilization index =
(100 * (data bytes / raw bytes))

```
        Definitions:
        Data bytes:    Number of bytes transmitted as data in the

                       docsIfCmtsChannelUtilizationInterval.
                       Identical to docsIfCmtsDownChannelCtrUsed
                       Bytes measured over the utilization
                       interval.
        Raw bandwidth: Total number of bytes available for
                       transmitting data, not including bytes
                       used for headers and other overhead.
        Raw bytes:     (raw bandwidth *
                       docsIfCmtsChannelUtilizationInterval).
                       Identical to docsIfCmtsDownChannelCtrTotal
                       Bytes measured over the utilization
                       interval."
    ::= { docsIfCmtsChannelUtilizationEntry 3 }

-- The following table provides operators with input data
-- appropriate for calculating downstream channel utilization.
-- Operators may use the docsIfCmtsChannelUtilizationTable or
-- perform their own polling of the
-- docsIfCmtsDownChannelCounterTable objects to characterize
--
 their downstream channel usage.  The 32-bit counter objects are
-- included to provide backward compatibility with SNMPv1 managers,
-- which cannot access 64-bit counter objects.

docsIfCmtsDownChannelCounterTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfCmtsDownChannelCounterEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table is implemented at the CMTS to collect
        downstream channel statistics for utilization




        calculations."
    ::= { docsIfCmtsObjects 10 }

docsIfCmtsDownChannelCounterEntry OBJECT-TYPE
    SYNTAX      DocsIfCmtsDownChannelCounterEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry provides a list of traffic counters for a single
        downstream channel.
```

```
        An entry in this table exists for each ifEntry with an
        ifType of docsCableDownstream(128)."
    INDEX { ifIndex }
    ::= { docsIfCmtsDownChannelCounterTable
 1 }

DocsIfCmtsDownChannelCounterEntry ::= SEQUENCE {
        docsIfCmtsDownChnlCtrId             Integer32,
        docsIfCmtsDownChnlCtrTotalBytes     Counter32,
        docsIfCmtsDownChnlCtrUsedBytes      Counter32,
        docsIfCmtsDownChnlCtrExtTotalBytes  Counter64,
        docsIfCmtsDownChnlCtrExtUsedBytes   Counter64
    }

docsIfCmtsDownChnlCtrId OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The Cable Modem Termination System identification
        of the downstream channel within this particular MAC
        interface.  If the interface is down, the object returns
        the most current value.  If the downstream channel ID is
        unknown, this object returns a value of 0."
    ::= { docsIfCmtsDownChannelCounterEntry 1 }

docsIfCmtsDownChnlCtrTotalBytes OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "Bytes"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "At the CMTS, the total number of bytes in the Payload
        portion of MPEG Packets (i.e., not including MPEG header
        or pointer_field) transported by this downstream channel.
        This is the 32-bit version of
        docsIfCmtsDownChnlCtrExtTotalBytes, included to provide
        back compatibility with SNMPv1 managers.
        Discontinuities in the value of this counter can occur



        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsDownChannelCounterEntry 2 }

docsIfCmtsDownChnlCtrUsedBytes OBJECT-TYPE
```

```
    SYNTAX      Counter32
    UNITS       "Bytes"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "At the CMTS, the total number of DOCSIS data bytes
        transported by this downstream channel.
        The number of data bytes is defined as the total
 number
        of bytes transported in DOCSIS payloads minus the number
        of stuff bytes transported in DOCSIS payloads.
        This is the 32-bit version of
        docsIfCmtsDownChnlCtrExtUsedBytes, included to provide
        back compatibility with SNMPv1 managers.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsDownChannelCounterEntry 3 }

docsIfCmtsDownChnlCtrExtTotalBytes OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "Bytes"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "At the CMTS, the total number of bytes in the Payload
        portion of MPEG Packets (i.e., not including MPEG header
        or pointer_field) transported by this downstream
        channel.
        This is the 64-bit version of

        docsIfCmtsDownChnlCtrTotalBytes and will not be
        accessible to SNMPv1 managers.
        Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsDownChannelCounterEntry 4 }

docsIfCmtsDownChnlCtrExtUsedBytes OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "Bytes"
    MAX-ACCESS  read-only



    STATUS      current
```

```
    DESCRIPTION
        "At the CMTS, the total number of DOCSIS data bytes
        transported by this downstream channel.  The number
        of data bytes is defined as the total number of bytes
        transported in DOCSIS payloads minus the number of
        stuff bytes transported in DOCSIS payloads.
        This is the 64-bit version of
        docsIfCmtsDownChnlCtrUsedBytes and will not be accessible
        to SNMPv1 managers.
         Discontinuities in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsDownChannelCounterEntry 5 }

-- The following table provides operators with input data appropriate
-- for calculating upstream channel utilization, and for determining
-- the traffic characteristics of upstream channels.  Operators may
-- use the docsIfCmtsChannelUtilizationTable or perform their own
-- polling of the docsIfCmtsUpChannelCounterTable objects for
-- utilization determination.
-- The first four 32 and 64 objects in this table are mandatory.
-- Vendors may choose to implement the remaining optional objects to
-- provide operators with finer characterization of upstream channel
-- traffic patterns.  The 32-bit counter objects are included to
-- provide backward compatibility with SNMPv1 managers, which cannot
-- access
 64-bit counter objects.

docsIfCmtsUpChannelCounterTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsIfCmtsUpChannelCounterEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table is implemented at the CMTS to provide upstream
        channel statistics appropriate for channel utilization
        calculations."
    ::= { docsIfCmtsObjects 11 }

docsIfCmtsUpChannelCounterEntry OBJECT-TYPE
    SYNTAX      DocsIfCmtsUpChannelCounterEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "List of traffic statistics for a single upstream channel.
        For DOCSIS 2.0 CMTSs, an entry in this table
        exists for each ifEntry with an ifType of
        docsCableUpstreamChannel (205).
```

```
        For DOCSIS 1.x CMTSs, an entry in this table
        exists for each ifEntry with an ifType of
        docsCableUpstream (129)."
    INDEX { ifIndex }
    ::= { docsIfCmtsUpChannelCounterTable 1 }

DocsIfCmtsUpChannelCounterEntry
 ::= SEQUENCE {
        docsIfCmtsUpChnlCtrId                    Integer32,
        docsIfCmtsUpChnlCtrTotalMslots           Counter32,
        docsIfCmtsUpChnlCtrUcastGrantedMslots    Counter32,
        docsIfCmtsUpChnlCtrTotalCntnMslots       Counter32,
        docsIfCmtsUpChnlCtrUsedCntnMslots        Counter32,
        docsIfCmtsUpChnlCtrExtTotalMslots        Counter64,
        docsIfCmtsUpChnlCtrExtUcastGrantedMslots Counter64,
        docsIfCmtsUpChnlCtrExtTotalCntnMslots    Counter64,
        docsIfCmtsUpChnlCtrExtUsedCntnMslots     Counter64,
        docsIfCmtsUpChnlCtrCollCntnMslots        Counter32,
        docsIfCmtsUpChnlCtrTotalCntnReqMslots    Counter32,
        docsIfCmtsUpChnlCtrUsedCntnReqMslots     Counter32,
        docsIfCmtsUpChnlCtrCollCntnReqMslots     Counter32,
        docsIfCmtsUpChnlCtrTotalCntnReqDataMslots Counter32,
        docsIfCmtsUpChnlCtrUsedCntnReqDataMslots
       Counter32,
        docsIfCmtsUpChnlCtrCollCntnReqDataMslots  Counter32,
        docsIfCmtsUpChnlCtrTotalCntnInitMaintMslots Counter32,
        docsIfCmtsUpChnlCtrUsedCntnInitMaintMslots Counter32,
        docsIfCmtsUpChnlCtrCollCntnInitMaintMslots Counter32,
        docsIfCmtsUpChnlCtrExtCollCntnMslots     Counter64,
        docsIfCmtsUpChnlCtrExtTotalCntnReqMslots  Counter64,
        docsIfCmtsUpChnlCtrExtUsedCntnReqMslots   Counter64,
        docsIfCmtsUpChnlCtrExtCollCntnReqMslots   Counter64,
        docsIfCmtsUpChnlCtrExtTotalCntnReqDataMslots Counter64,
        docsIfCmtsUpChnlCtrExtUsedCntnReqDataMslots Counter64,
        docsIfCmtsUpChnlCtrExtCollCntnReqDataMslots Counter64,
        docsIfCmtsUpChnlCtrExtTotalCntnInitMaintMslots Counter64,
        docsIfCmtsUpChnlCtrExtUsedCntnInitMaintMslots Counter64,
        docsIfCmtsUpChnlCtrExtCollCntnInitMaintMslots Counter64
    }

docsIfCmtsUpChnlCtrId
 OBJECT-TYPE
    SYNTAX      Integer32 (0..255)
    MAX-ACCESS  read-only
    STATUS      current
```

```
    DESCRIPTION
        "The CMTS identification of the upstream channel."
    ::= { docsIfCmtsUpChannelCounterEntry 1 }

docsIfCmtsUpChnlCtrTotalMslots OBJECT-TYPE
    SYNTAX      Counter32



    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Current count, from CMTS initialization, of all mini-slots
         defined for this upstream logical channel.  This count
         includes all IUCs and SIDs, even those allocated to the
         NULL SID for a 2.0 logical channel that is inactive.  This
         is the 32-bit version of docsIfCmtsUpChnlCtrExtTotalMslots
         and is included for back compatibility with SNMPv1
         managers.  Support for this object is mandatory.
         Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at
 other
         times as indicated by the value of
         ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry 2 }

docsIfCmtsUpChnlCtrUcastGrantedMslots OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Current count, from CMTS initialization, of unicast
         granted mini-slots on the upstream logical channel,
         regardless of burst type.  Unicast granted mini-slots are
         those in which the CMTS assigned bandwidth to any unicast
         SID on the logical channel.  However, this object does not
         include minis-lots for reserved IUCs, or grants to SIDs
         designated as meaning 'no CM'.  This is the 32-bit version
         of docsIfCmtsUpChnlCtrExtUcastGrantedMslots, and is
         included for back compatibility with SNMPv1 managers.
         Support for this object is mandatory.
         Discontinuities
 in the value of this counter can occur
         at reinitialization of the managed system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime for the associated ifIndex."
```

::= { docsIfCmtsUpChannelCounterEntry 3 }

docsIfCmtsUpChnlCtrTotalCntnMslots OBJECT-TYPE
SYNTAX Counter32
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention
mini-slots defined for this upstream logical channel. This
count includes all mini-slots assigned to a broadcast or

multicast SID on the logical channel. This is the 32-bit
version of docsIfCmtsUpChnlCtrExtTotalCntnMslots, and is
included for back compatibility with SNMPv1 managers.
Support for this object is mandatory.
Discontinuities in the value of this counter can occur
at reinitialization of the managed
system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 4 }

docsIfCmtsUpChnlCtrUsedCntnMslots OBJECT-TYPE
SYNTAX Counter32
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention
mini-slots utilized on the upstream logical channel. For
contention regions, utilized mini-slots are those in which
the CMTS correctly received an upstream burst from any CM
on the upstream logical channel. This is the 32-bit
version of docsIfCmtsUpChnlCtrExtUsedCntnMslots and is
included for back compatibility with SNMPv1 managers.
Support for this object is mandatory.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other

times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 5 }

docsIfCmtsUpChnlCtrExtTotalMslots OBJECT-TYPE
SYNTAX Counter64

```
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Current count, from CMTS initialization, of all mini-slots
         defined for this upstream logical channel.  This count
         includes all IUCs and SIDs, even those allocated to the
         NULL SID for a 2.0 logical channel that is inactive.  This
         is the 64-bit version of docsIfCmtsUpChnlCtrTotalMslots
         and will not be accessible to SNMPv1 managers.
         Support for this object is mandatory.
         Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime for the associated
 ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry 6 }



docsIfCmtsUpChnlCtrExtUcastGrantedMslots OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Current count, from CMTS initialization, of unicast
         granted mini-slots on the upstream logical channel,
         regardless of burst type.  Unicast granted mini-slots are
         those in which the CMTS assigned bandwidth to any unicast
         SID on the logical channel.  However, this object does not
         include mini-slots for reserved IUCs, or grants to SIDs
         designated as meaning 'no CM'.  This is the 64-bit version
         of docsIfCmtsUpChnlCtrUcastGrantedMslots and will not be
         accessible to SNMPv1 managers.
         Support for this object is mandatory.
         Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other

 times as indicated by the value of
         ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry 7 }

docsIfCmtsUpChnlCtrExtTotalCntnMslots OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
```

```
    DESCRIPTION
        "Current count, from CMTS initialization, of contention
         mini-slots defined for this upstream logical channel.  This
         count includes all mini-slots assigned to a broadcast or
         multicast SID on the logical channel.  This is the 64-bit
         version of docsIfCmtsUpChnlCtrTotalCntnMslots and will
         not be accessible to SNMPv1 managers.
         Support for this object is mandatory.
         Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime for the associated ifIndex."

    ::= { docsIfCmtsUpChannelCounterEntry 8 }

docsIfCmtsUpChnlCtrExtUsedCntnMslots OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Current count, from CMTS initialization, of contention



         mini-slots utilized on the upstream logical channel.  For
         contention regions, utilized mini-slots are those in which
         the CMTS correctly received an upstream burst from any CM
         on the upstream logical channel.  This is the 64-bit
         version of docsIfCmtsUpChnlCtrUsedCntnMslots and will not
         be accessible to SNMPv1 managers.
         Support for this object is mandatory.
         Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry
 9 }

docsIfCmtsUpChnlCtrCollCntnMslots OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Current count, from CMTS initialization, of contention
         mini-slots subjected to collisions on the upstream logical
         channel.  For contention regions, these are the mini-slots
```

applicable to bursts that the CMTS detected but could not
correctly receive. This is the 32-bit version of
docsIfCmtsUpChnlCtrExtCollCntnMslots and is included for
back compatibility with SNMPv1 managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 10 }

docsIfCmtsUpChnlCtrTotalCntnReqMslots OBJECT-TYPE
SYNTAX Counter32

UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention
request mini-slots defined for this upstream logical
channel. This count includes all mini-slots for IUC1
assigned to a broadcast or multicast SID on the logical
channel. This is the 32-bit version of
docsIfCmtsUpChnlCtrExtTotalCntnReqMslots and is included
for back compatibility with SNMPv1 managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of

ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 11 }

docsIfCmtsUpChnlCtrUsedCntnReqMslots OBJECT-TYPE
SYNTAX Counter32
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"Current count, from CMTS initialization, of contention
request mini-slots utilized on this upstream logical
channel. This count includes all contention mini-slots for
IUC1 applicable to bursts that the CMTS correctly
received. This is the 32-bit version of
docsIfCmtsUpChnlCtrExtUsedCntnReqMslots and is included
for back compatibility with SNMPv1 managers.
Discontinuities in the value of this counter can occur

at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 12 }

docsIfCmtsUpChnlCtrCollCntnReqMslots OBJECT-TYPE
SYNTAX Counter32
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention
request mini-slots subjected to collisions
on this upstream
logical channel. This includes all contention mini-slots
for IUC1 applicable to bursts that the CMTS detected but
could not correctly receive. This is the 32-bit version of
docsIfCmtsUpChnlCtrExtCollCntnReqMslots and is included
for back compatibility with SNMPv1 managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 13 }

docsIfCmtsUpChnlCtrTotalCntnReqDataMslots OBJECT-TYPE
SYNTAX Counter32
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention

request data mini-slots defined for this upstream logical
channel. This count includes all
mini-slots for IUC2
assigned to a broadcast or multicast SID on the logical
channel. This is the 32-bit version of
docsIfCmtsUpChnlCtrExtTotalCntnReqDataMslots and is
included for back compatibility with SNMPv1 managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 14 }

```
docsIfCmtsUpChnlCtrUsedCntnReqDataMslots OBJECT-TYPE
   SYNTAX      Counter32
   UNITS       "mini-slots"
MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "Current count, from CMTS initialization, of contention
       request data mini-slots utilized on this upstream logical
       channel.  This includes all contention mini-slots for IUC2
       applicable to bursts that the CMTS correctly received.

      This is the 32-bit version of
       docsIfCmtsUpChnlCtrExtUsedCntnReqDataMslots and is
       included for back compatibility with SNMPv1 managers.
       Discontinuities in the value of this counter can occur
       at reinitialization of the managed system, and at other
       times as indicated by the value of
       ifCounterDiscontinuityTime for the associated ifIndex."
   ::= { docsIfCmtsUpChannelCounterEntry 15 }

docsIfCmtsUpChnlCtrCollCntnReqDataMslots OBJECT-TYPE
   SYNTAX      Counter32
   UNITS       "mini-slots"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "Current count, from CMTS initialization, of contention
       request data mini-slots subjected to collisions on this
       upstream logical channel.  This includes all contention
       mini-slots for IUC2 applicable to bursts that the CMTS
       detected, but could not correctly receive.  This is the
       32-bit version of
       docsIfCmtsUpChnlCtrExtCollCntnReqDataMslots
 and is
       included for back compatibility with SNMPv1 managers.
       Discontinuities in the value of this counter can occur
       at reinitialization of the managed system, and at other
       times as indicated by the value of




       ifCounterDiscontinuityTime for the associated ifIndex."
   ::= { docsIfCmtsUpChannelCounterEntry 16 }

docsIfCmtsUpChnlCtrTotalCntnInitMaintMslots OBJECT-TYPE
   SYNTAX      Counter32
   UNITS       "mini-slots"
   MAX-ACCESS  read-only
```

```
    STATUS      current
    DESCRIPTION
        "Current count, from CMTS initialization, of contention
         initial maintenance mini-slots defined for this upstream
         logical channel.  This includes all mini-slots for IUC3
         assigned to a broadcast or multicast SID on the logical
         channel.  This is the 32-bit version of
         docsIfCmtsUpChnlCtrExtTotalCntnInitMaintMslots
         and is included for back compatibility
 with SNMPv1
         managers.
         Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry 17 }

docsIfCmtsUpChnlCtrUsedCntnInitMaintMslots OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Current count, from CMTS initialization, of contention
         initial maintenance mini-slots utilized on this upstream
         logical channel.  This includes all contention mini-slots
         for IUC3 applicable to bursts that the CMTS correctly
         received.  This is the 32-bit version of
         docsIfCmtsUpChnlCtrExtUsedCntnInitMaintMslots
         and is included for back compatibility with SNMPv1
         managers.
         Discontinuities in the value of this counter can occur
          at reinitialization of the managed system, and at other
         times as indicated by the value of
         ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry 18 }

docsIfCmtsUpChnlCtrCollCntnInitMaintMslots OBJECT-TYPE
    SYNTAX      Counter32
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "Current count, from CMTS initialization, of contention
         initial maintenance mini-slots subjected to collisions on
         this upstream logical channel.  This includes all
```

contention mini-slots for IUC3 applicable to bursts that
the CMTS detected, but could not correctly receive.
This is the 32-bit version of
docsIfCmtsUpChnlCtrExtCollCntnInitMaintMslots
and is included for back compatibility with SNMPv1
managers.
Discontinuities in the value of this counter can occur
at reinitialization
of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 19 }

docsIfCmtsUpChnlCtrExtCollCntnMslots OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of collision
contention mini-slots on the upstream logical channel.
For contention regions, these are the mini-slots applicable
to bursts that the CMTS detected, but could not correctly
receive. This is the 64-bit version of
docsIfCmtsUpChnlCtrCollCntnMslots and will not be
accessible to SNMPv1 managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime
for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 20 }

docsIfCmtsUpChnlCtrExtTotalCntnReqMslots OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention
request mini-slots defined for this upstream logical
channel. This count includes all mini-slots for IUC1
assigned to a broadcast or multicast SID on the logical
channel. This is the 64-bit version of
docsIfCmtsUpChnlCtrTotalCntnReqMslots and will not be
accessible to SNMPv1 managers.
Discontinuities in the value of this counter can occur

at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 21 }

docsIfCmtsUpChnlCtrExtUsedCntnReqMslots
OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention
request mini-slots utilized on this upstream logical
channel. This count includes all contention mini-slots for
IUC1 applicable to bursts that the CMTS correctly
received. This is the 64-bit version of
docsIfCmtsUpChnlCtrUsedCntnReqMslots and will not be
accessible to SNMPv1 managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 22 }

docsIfCmtsUpChnlCtrExtCollCntnReqMslots OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS
current
DESCRIPTION
"Current count, from CMTS initialization, of contention
request mini-slots subjected to collisions on this upstream
logical channel. This includes all contention mini-slots
for IUC1 applicable to bursts that the CMTS detected,
but could not correctly receive. This is the 64-bit
version of docsIfCmtsUpChnlCtrCollCntnReqMslots and will
not be accessible to SNMPv1 managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 23 }

docsIfCmtsUpChnlCtrExtTotalCntnReqDataMslots OBJECT-TYPE

SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current

DESCRIPTION
"Current count, from CMTS initialization,
of contention
request data mini-slots defined for this upstream logical
channel. This count includes all mini-slots for IUC2
assigned to a broadcast or multicast SID on the logical
channel. This is the 64-bit version of
docsIfCmtsUpChnlCtrTotalCntnReqDataMslots and will not be
accessible to SNMPv1 managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 24 }

docsIfCmtsUpChnlCtrExtUsedCntnReqDataMslots OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of contention
request data mini-slots utilized on this upstream logical
channel. This
includes all contention mini-slots for IUC2
applicable to bursts that the CMTS correctly received.
This is the 64-bit version of
docsIfCmtsUpChnlCtrUsedCntnReqDataMslots and will not be
accessible to SNMPv1 managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 25 }

docsIfCmtsUpChnlCtrExtCollCntnReqDataMslots OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"Current count, from CMTS initialization, of contention
request data mini-slots subjected to collisions on this
upstream logical channel. This includes all contention
mini-slots for IUC2 applicable to bursts that the CMTS

detected, but could not correctly receive. This is the
64-bit version of
docsIfCmtsUpChnlCtrCollCntnReqDataMslots
and will not be accessible to SNMPv1 managers.
Discontinuities in the value of this counter can occur

at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 26 }

docsIfCmtsUpChnlCtrExtTotalCntnInitMaintMslots OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of initial
maintenance mini-slots defined for this upstream logical
channel. This count includes all mini-slots for IUC3
assigned to a broadcast or multicast SID on the logical
channel. This is the 64-bit version of
docsIfCmtsUpChnlCtrTotalCntnInitMaintMslots
and will not be accessible to SNMPv1 managers.
Discontinuities in the value of this counter can occur
at reinitialization of the managed system, and at other
times as indicated by the value of
ifCounterDiscontinuityTime for the associated ifIndex."
::= { docsIfCmtsUpChannelCounterEntry 27 }

docsIfCmtsUpChnlCtrExtUsedCntnInitMaintMslots OBJECT-TYPE
SYNTAX Counter64
UNITS "mini-slots"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Current count, from CMTS initialization, of initial
maintenance mini-slots utilized on this upstream logical
channel. This includes all contention mini-slots for IUC3
applicable to bursts that the CMTS correctly received.
This is the 64-bit version of

```
        docsIfCmtsUpChnlCtrUsedCntnInitMaintMslots
        and will not be accessible to SNMPv1 managers.
        Discontinuities
 in the value of this counter can occur
        at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry 28 }

docsIfCmtsUpChnlCtrExtCollCntnInitMaintMslots OBJECT-TYPE
    SYNTAX      Counter64
    UNITS       "mini-slots"
    MAX-ACCESS  read-only
    STATUS      current



    DESCRIPTION
        "Current count, from CMTS initialization, of contention
        initial maintenance mini-slots subjected to collisions on
        this upstream logical channel.  This includes all
        contention mini-slots for IUC3 applicable to bursts that
        the CMTS detected, but could not correctly receive.
        This is the 64-bit version of
        docsIfCmtsUpChnlCtrCollCntnInitMaintMslots and will not
        be accessible to SNMPv1 managers.
        Discontinuities in the value of this counter can occur
         at reinitialization of the managed system, and at other
        times as indicated by the value of
        ifCounterDiscontinuityTime for the associated ifIndex."
    ::= { docsIfCmtsUpChannelCounterEntry 29 }

--
-- notification group is for future extension.
--

docsIfNotification OBJECT IDENTIFIER     ::= { docsIfMib 2 }

--
-- MIB Compliance statements.
--


--
-- Conformance definitions
--

docsIfConformance  OBJECT IDENTIFIER     ::= { docsIfMib 3 }
docsIfCompliances  OBJECT IDENTIFIER     ::= { docsIfConformance 1 }
```

```
docsIfGroups       OBJECT IDENTIFIER     ::= { docsIfConformance 2 }

docsIfBasicCompliance MODULE-COMPLIANCE
   STATUS      deprecated
   DESCRIPTION
      "The compliance statement for devices that implement
       DOCSIS 1.x compliant Radio Frequency Interfaces."

MODULE  -- docsIfMib

-- unconditionally mandatory groups
MANDATORY-GROUPS {
   docsIfBasicGroup
   }

-- conditionally mandatory group
GROUP docsIfCmGroup



   DESCRIPTION
       "This group is implemented only in cable modems, not in
       cable modem termination systems."

-- conditionally mandatory group
GROUP docsIfCmtsGroup
   DESCRIPTION
      "This group is implemented only in cable modem termination
       systems, not in cable modems."

OBJECT  docsIfDownChannelFrequency
   WRITE-SYNTAX Integer32 (54000000..860000000)
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-write in cable modem termination systems;
       read-only in cable modems.  The values above are
       appropriate for a cable plant using a Sub-Split channel
       plan.  If DOCSIS is extended to cover other types of
       channel plans (and frequency allocations), this object
       will be modified accordingly."

OBJECT  docsIfDownChannelWidth
   WRITE-SYNTAX Integer32 (6000000)
   MIN-ACCESS  read-only
   DESCRIPTION
      "It is important to implement this object as read-only.
       In cable modems, this object is always
```

```
 implemented as
        read-only.  The above value is appropriate for cable
        plants running under NTSC (National Television
        Standards Committee) standards.  If DOCSIS is extended to
        work with other standards (e.g., European standards), this
        object will be modified accordingly."

OBJECT  docsIfDownChannelModulation
   WRITE-SYNTAX INTEGER {
                    qam64 (3),
                    qam256 (4)
                   }
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-write in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfDownChannelInterleave
   WRITE-SYNTAX INTEGER {
            taps8Increment16(3),
            taps16Increment8(4),
            taps32Increment4(5),



            taps64Increment2(6),
            taps128Increment1(7)
             }
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-write in cable modem termination
 systems;
       read-only in cable modems."

OBJECT  docsIfDownChannelPower
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-write in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelFrequency
   WRITE-SYNTAX Integer32 (5000000..42000000)
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-write in cable modem termination systems;
       read-only in cable modems.  The values above are
       appropriate for a cable plant using a Sub-Split channel
       plan.  If DOCSIS is extended to cover other types of
```

channel plans (and frequency allocations), this object
will be modified accordingly."

OBJECT docsIfUpChannelWidth
WRITE-SYNTAX Integer32 (200000..3200000)
MIN-ACCESS read-only
DESCRIPTION
"Read-write in cable modem termination systems;
read-only in cable modems. The above value is appropriate
for cable plants running under NTSC (National Television
Standards Committee) standards. If DOCSIS is extended to
work with other standards (e.g., European standards), this
object will be modified accordingly."

OBJECT docsIfUpChannelModulationProfile
MIN-ACCESS read-only
DESCRIPTION
"Read-write in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfUpChannelSlotSize
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfUpChannelRangingBackoffStart
MIN-ACCESS read-only
DESCRIPTION
"Read-write in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfUpChannelRangingBackoffEnd
MIN-ACCESS read-only
DESCRIPTION
"Read-write in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfUpChannelTxBackoffStart
MIN-ACCESS read-only
DESCRIPTION
"Read-write in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfUpChannelTxBackoffEnd

MIN-ACCESS read-only
DESCRIPTION
"Read-write in cable modem termination systems;
read-only in cable modems."

OBJECT docsIfQosProfPriority
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfQosProfMaxUpBandwidth
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfQosProfGuarUpBandwidth
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant
to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfQosProfMaxDownBandwidth
MIN-ACCESS read-only
DESCRIPTION

"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfQosProfMaxTxBurst
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfQosProfBaselinePrivacy
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.

```
        It is compliant to implement this object as read-only
        in cable modem termination systems."

OBJECT  docsIfQosProfStatus
   MIN-ACCESS  read-only
   DESCRIPTION
      "This object is always read-only in cable modems.
       It is compliant
 to implement this object as read-only
       in cable modem termination systems."

OBJECT  docsIfCmtsServiceAdminStatus
   MIN-ACCESS  read-only
   DESCRIPTION
      "It is compliant to implement this object as read-only."

OBJECT  docsIfCmtsSyncInterval
   MIN-ACCESS  read-only
   DESCRIPTION
      "It is compliant to implement this object as read-only."

OBJECT  docsIfCmtsUcdInterval
   MIN-ACCESS  read-only
   DESCRIPTION
      "It is compliant to implement this object as read-only."

OBJECT  docsIfCmtsInsertInterval
   MIN-ACCESS  read-only
   DESCRIPTION
      "It is compliant to implement this object as read-only."

OBJECT  docsIfCmtsInvitedRangingAttempts
   MIN-ACCESS  read-only
   DESCRIPTION




      "It is compliant to implement this object as read-only."

OBJECT  docsIfCmtsQosProfilePermissions
   WRITE-SYNTAX     BITS {
      createByManagement(0),
      updateByManagement(1)
     }
   MIN-ACCESS  read-only
   DESCRIPTION
       "It is compliant to implement this object as read-only."
```

```
OBJECT docsIfCmtsModType
   WRITE-SYNTAX INTEGER {
                qpsk (2),
                qam16 (3)
                 }
   DESCRIPTION
      "A management station MAY only set 16QAM or QPSK modulation,
       but others might be possible, based on device
       configuration."

OBJECT  docsIfCmtsModPreambleLen
   SYNTAX Integer32 (0..1024)
   DESCRIPTION
      "The range of the values for this MODULE-COMPLIANCE
       is 0..1024."

OBJECT  docsIfCmtsModFECErrorCorrection
      SYNTAX Integer32 (0..10)
      DESCRIPTION
         "The range of the values for this MODULE-COMPLIANCE
          is 0..10."

   ::= { docsIfCompliances 1 }

docsIfBasicComplianceV2 MODULE-COMPLIANCE
   STATUS      current
   DESCRIPTION
      "The compliance statement for devices that implement
       DOCSIS 2.0 Radio Frequency Interfaces."

MODULE  -- docsIfMib

-- unconditionally
 mandatory groups
MANDATORY-GROUPS {
   docsIfBasicGroupV2
   }




-- conditionally mandatory group
GROUP docsIfCmGroupV2
   DESCRIPTION
      "This group is implemented only in cable modems, not in
       cable modem termination systems."

-- conditionally mandatory group
```

```
GROUP docsIfCmtsGroupV2
   DESCRIPTION
      "This group is implemented only in cable modem termination
       systems, not in cable modems."


OBJECT  docsIfDownChannelFrequency
   WRITE-SYNTAX Integer32 (47000000..862000000)
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-write in cable modem termination systems;
       read-only in cable modems.
       A range of 54MHz to 860MHz is appropriate for a cable
       plant using a North American Sub-Split channel plan.
       The spectrum range has been expanded to accommodate
       a lower edge of 47MHz and an upper edge of 862MHz
       for some European channel plans.
       If DOCSIS is extended to cover other
 types of channel
       plans (and frequency allocations), this object will be
       modified accordingly."

OBJECT  docsIfDownChannelWidth
   WRITE-SYNTAX Integer32 (6000000 | 8000000)
   MIN-ACCESS  read-only
   DESCRIPTION
      "It is important to implement this object as read-only.
       In cable modems, this object is always implemented as
       read-only.  The value of 6 MHz is appropriate for cable
       plants running under NTSC (National Television
       Standards Committee) standards.  The value of 8 MHz is
       appropriate for cable plants running under ETSI
       standards.  For other regional standards, this
       object will be modified accordingly."

OBJECT  docsIfDownChannelModulation
   WRITE-SYNTAX INTEGER {
                  qam64 (3),
                  qam256 (4)
                 }
   MIN-ACCESS  read-only
   DESCRIPTION



      "Read-write in cable modem termination systems;
```

```
      read-only in cable modems."

OBJECT  docsIfDownChannelInterleave
   WRITE-SYNTAX INTEGER {
            taps8Increment16(3),
            taps16Increment8(4),
            taps32Increment4(5),
            taps64Increment2(6),
            taps128Increment1(7),
            taps12increment17(8)
             }
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-write in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfDownChannelPower
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-write in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelFrequency
   WRITE-SYNTAX Integer32 (5000000..65000000)
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems.
       A range of 5MHz to 42MHz is appropriate for a cable
       plant using a North American Sub-Split channel plan.
        The spectrum range has been expanded to accommodate
       an upper edge of 65MHz for some European channel plans.
       If DOCSIS is extended to cover other types of channel
       plans (and frequency allocations), this object will
       be modified accordingly."

OBJECT  docsIfUpChannelWidth
   WRITE-SYNTAX Integer32 (200000..6400000)
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems,
       read-only in cable modems.  The above value is appropriate
       for cable plants running under NTSC (National Television
       Standards Committee) standards.  If DOCSIS is extended to
       work with other standards (e.g., European standards), this
       object will be modified accordingly."
```

```
OBJECT  docsIfUpChannelModulationProfile
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelSlotSize
    MIN-ACCESS  read-only
   DESCRIPTION
      "This object is always read-only in cable modems.
       It is compliant to implement this object as read-only
       in cable modem termination systems."

OBJECT  docsIfUpChannelRangingBackoffStart
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelRangingBackoffEnd
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelTxBackoffStart
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelTxBackoffEnd
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelScdmaActiveCodes
   MIN-ACCESS
 read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems.
       The number of active codes when SCDMA is in use MUST range
       from 64 to 128 and MUST be a non-Prime value.
       Providing this range allows for the following features
```

and capabilities:
1) Power management in S-CDMA spreader-on frames
(with a 3 dB spread).

2) Avoidance of code 0.
3) Flexible mini-slot sizes with and without the use of
code 0."

```
OBJECT  docsIfUpChannelScdmaCodesPerSlot
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelScdmaFrameSize
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelScdmaHoppingSeed
   MIN-ACCESS  read-only
    DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelCloneFrom
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelUpdate
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems."

OBJECT  docsIfUpChannelStatus
     MIN-ACCESS  read-only
     DESCRIPTION
        "Read-create in Cable Modem Termination Systems;
         read-only in Cable Modems.
         Entries associated to physical interfaces only support
         the read-only value 'active'."
```

```
OBJECT  docsIfUpChannelPreEqEnable
   MIN-ACCESS  read-only
   DESCRIPTION
      "Read-create in cable modem termination systems;
       read-only in cable modems."



OBJECT  docsIfQosProfPriority
   MIN-ACCESS  read-only

  DESCRIPTION
      "This object is always read-only in cable modems.
       It is compliant to implement this object as read-only
       in cable modem termination systems."

OBJECT  docsIfQosProfMaxUpBandwidth
   MIN-ACCESS  read-only
   DESCRIPTION
      "This object is always read-only in cable modems.
       It is compliant to implement this object as read-only
       in cable modem termination systems."

OBJECT  docsIfQosProfGuarUpBandwidth
   MIN-ACCESS  read-only
   DESCRIPTION
      "This object is always read-only in cable modems.
       It is compliant to implement this object as read-only
       in cable modem termination systems."

OBJECT  docsIfQosProfMaxDownBandwidth
   MIN-ACCESS  read-only
   DESCRIPTION
      "This object is always read-only in cable modems.
       It is compliant to implement this object as read-only
       in cable modem termination systems."

OBJECT  docsIfQosProfBaselinePrivacy
   MIN-ACCESS  read-only
    DESCRIPTION
      "This object is always read-only in cable modems.
       It is compliant to implement this object as read-only
       in cable modem termination systems."

OBJECT  docsIfQosProfStatus
   MIN-ACCESS  read-only
   DESCRIPTION
```

"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfQosProfMaxTransmitBurst
MIN-ACCESS read-only
DESCRIPTION
"This object is always read-only in cable modems.
It is compliant to implement this object as read-only
in cable modem termination systems."

OBJECT docsIfCmRangingTimeout
MIN-ACCESS read-only
DESCRIPTION
"It is compliant to implement this object as read-only."

OBJECT docsIfCmStatusModulationType
SYNTAX INTEGER {
unknown(0),
tdma(1),
atdma(2),
scdma(3)
}
DESCRIPTION

"CM does not use both modulation burst profiles of a
'tdmAndAtdma' ChannelType; therefore, 'tdmAndAtdma'is
not supported."

OBJECT docsIfCmtsServiceAdminStatus
MIN-ACCESS read-only
DESCRIPTION
"It is compliant to implement this object as read-only."

OBJECT docsIfCmtsSyncInterval
MIN-ACCESS read-only
DESCRIPTION
"It is compliant to implement this object as read-only."

OBJECT docsIfCmtsUcdInterval
MIN-ACCESS read-only
DESCRIPTION
"It is compliant to implement this object as read-only."

OBJECT docsIfCmtsInsertInterval
MIN-ACCESS read-only

```
    DESCRIPTION
        "It is compliant to implement this object as read-only."

OBJECT  docsIfCmtsInvitedRangingAttempts
    MIN-ACCESS  read-only
    DESCRIPTION
        "It is compliant to implement this object as read-only."

OBJECT  docsIfCmtsQosProfilePermissions
    WRITE-SYNTAX     BITS {
        createByManagement(0),
        updateByManagement(1)
        }
    MIN-ACCESS  read-only



    DESCRIPTION
        "It is compliant to implement this object as read-only."

OBJECT docsIfCmtsModType
    WRITE-SYNTAX      INTEGER {
        qpsk(2),
        qam16(3),
        qam64(6)
    }
    DESCRIPTION
        "A management station MAY only set 64QAM, 16QAM, or QPSK
         modulation for Time or Code division Multiple Access,
         but others might be possible based on device
         configuration."

OBJECT docsIfCmtsCmStatusModulationType
   SYNTAX         INTEGER {
       unknown(0),
       tdma(1),
       atdma(2),
       scdma(3)
   }
    DESCRIPTION
        "CM does not use both modulation burst profiles of a
         'tdmAndAtdma' ChannelType; therefore, 'tdmAndAtdma'is
         not supported."

    ::= { docsIfCompliances 2 }

docsIfBasicGroup OBJECT-GROUP
    OBJECTS {
```

```
        docsIfDownChannelId,
        docsIfDownChannelFrequency,
        docsIfDownChannelWidth,
        docsIfDownChannelModulation,
         docsIfDownChannelInterleave,
        docsIfDownChannelPower,
        docsIfUpChannelId,
        docsIfUpChannelFrequency,
        docsIfUpChannelWidth,
        docsIfUpChannelModulationProfile,
        docsIfUpChannelSlotSize,
        docsIfUpChannelTxTimingOffset,
        docsIfUpChannelRangingBackoffStart,
        docsIfUpChannelRangingBackoffEnd,
        docsIfUpChannelTxBackoffStart,
        docsIfUpChannelTxBackoffEnd,
        docsIfQosProfPriority,



        docsIfQosProfMaxUpBandwidth,
        docsIfQosProfGuarUpBandwidth,
        docsIfQosProfMaxDownBandwidth,
        docsIfQosProfMaxTxBurst,
        docsIfQosProfBaselinePrivacy,
        docsIfQosProfStatus,
        docsIfSigQIncludesContention,
        docsIfSigQUnerroreds,
        docsIfSigQCorrecteds,
        docsIfSigQUncorrectables,
        docsIfSigQSignalNoise,
        docsIfSigQMicroreflections,
        docsIfSigQEqualizationData
    }
    STATUS      deprecated
    DESCRIPTION
        "Group of objects implemented in both cable modems and
        cable modem termination systems."
    ::= { docsIfGroups 1 }

docsIfCmGroup OBJECT-GROUP
    OBJECTS {
        docsIfCmCmtsAddress,
        docsIfCmCapabilities,
        docsIfCmRangingTimeout,
        docsIfCmStatusValue,
        docsIfCmStatusCode,
        docsIfCmStatusTxPower,
```

```
        docsIfCmStatusResets,
        docsIfCmStatusLostSyncs,
        docsIfCmStatusInvalidMaps,
        docsIfCmStatusInvalidUcds,
        docsIfCmStatusInvalidRangingResponses,
        docsIfCmStatusInvalidRegistrationResponses,
        docsIfCmStatusT1Timeouts,
        docsIfCmStatusT2Timeouts,
        docsIfCmStatusT3Timeouts,
        docsIfCmStatusT4Timeouts,
        docsIfCmStatusRangingAborteds,
        docsIfCmServiceQosProfile,
        docsIfCmServiceTxSlotsImmed,
        docsIfCmServiceTxSlotsDed,
        docsIfCmServiceTxRetries,
        docsIfCmServiceTxExceededs,
        docsIfCmServiceRqRetries,
         docsIfCmServiceRqExceededs
    }
    STATUS      deprecated



    DESCRIPTION
        "Group of objects implemented in cable modems."
    ::= { docsIfGroups 2 }

docsIfCmtsGroup OBJECT-GROUP
    OBJECTS {
        docsIfCmtsCapabilities,
        docsIfCmtsSyncInterval,
        docsIfCmtsUcdInterval,
        docsIfCmtsMaxServiceIds,
        docsIfCmtsInvitedRangingAttempts,
        docsIfCmtsInsertInterval,
        docsIfCmtsStatusInvalidRangeReqs,
        docsIfCmtsStatusRangingAborteds,
        docsIfCmtsStatusInvalidRegReqs,
        docsIfCmtsStatusFailedRegReqs,
        docsIfCmtsStatusInvalidDataReqs,
        docsIfCmtsStatusT5Timeouts,
        docsIfCmtsCmStatusMacAddress,
        docsIfCmtsCmStatusIpAddress,
        docsIfCmtsCmStatusDownChannelIfIndex,
        docsIfCmtsCmStatusUpChannelIfIndex,
        docsIfCmtsCmStatusRxPower,
        docsIfCmtsCmStatusTimingOffset,
        docsIfCmtsCmStatusEqualizationData,
```

```
        docsIfCmtsCmStatusValue,
         docsIfCmtsCmStatusUnerroreds,
        docsIfCmtsCmStatusCorrecteds,
        docsIfCmtsCmStatusUncorrectables,
        docsIfCmtsCmStatusSignalNoise,
        docsIfCmtsCmStatusMicroreflections,
        docsIfCmtsServiceCmStatusIndex,
        docsIfCmtsServiceAdminStatus,
        docsIfCmtsServiceQosProfile,
        docsIfCmtsServiceCreateTime,
        docsIfCmtsServiceInOctets,
        docsIfCmtsServiceInPackets,
        docsIfCmtsModType,
        docsIfCmtsModControl,
        docsIfCmtsModPreambleLen,
        docsIfCmtsModDifferentialEncoding,
        docsIfCmtsModFECErrorCorrection,
        docsIfCmtsModFECCodewordLength,
        docsIfCmtsModScramblerSeed,
        docsIfCmtsModMaxBurstSize,
        docsIfCmtsModGuardTimeSize,
        docsIfCmtsModLastCodewordShortened,
        docsIfCmtsModScrambler,



        docsIfCmtsQosProfilePermissions,
        docsIfCmtsCmPtr
    }
    STATUS      deprecated
    DESCRIPTION
        "Group of objects
 implemented in Cable Modem Termination
         Systems."
    ::= { docsIfGroups 3 }

-- obsolete group
-- RFC 2670 already had a obsolete group, even though RFC2670
-- was the first version of this MIB Module.

docsIfObsoleteGroup OBJECT-GROUP
    OBJECTS {
        docsIfCmRangingRespTimeout,
        docsIfCmtsInsertionInterval
    }
    STATUS      obsolete
    DESCRIPTION
        "Group of objects obsoleted."
```

```
    ::= { docsIfGroups 4 }

docsIfBasicGroupV2 OBJECT-GROUP
    OBJECTS {
        docsIfDownChannelId,
        docsIfDownChannelFrequency,
        docsIfDownChannelWidth,
        docsIfDownChannelModulation,
        docsIfDownChannelInterleave,
        docsIfDownChannelPower,
        docsIfDownChannelAnnex,
        docsIfUpChannelId,
        docsIfUpChannelFrequency,
        docsIfUpChannelWidth,
        docsIfUpChannelModulationProfile,
        docsIfUpChannelSlotSize,
        docsIfUpChannelTxTimingOffset,
        docsIfUpChannelRangingBackoffStart,
         docsIfUpChannelRangingBackoffEnd,
        docsIfUpChannelTxBackoffStart,
        docsIfUpChannelTxBackoffEnd,
        docsIfUpChannelScdmaActiveCodes,
        docsIfUpChannelScdmaCodesPerSlot,
        docsIfUpChannelScdmaFrameSize,
        docsIfUpChannelScdmaHoppingSeed,
        docsIfUpChannelType,
        docsIfUpChannelCloneFrom,



        docsIfUpChannelUpdate,
        docsIfUpChannelStatus,
        docsIfUpChannelPreEqEnable,
        docsIfQosProfPriority,
        docsIfQosProfMaxUpBandwidth,
        docsIfQosProfGuarUpBandwidth,
        docsIfQosProfMaxDownBandwidth,
        docsIfQosProfBaselinePrivacy,
        docsIfQosProfStatus,
        docsIfQosProfMaxTransmitBurst,
        docsIfSigQIncludesContention,
        docsIfSigQUnerroreds,
        docsIfSigQCorrecteds,
        docsIfSigQUncorrectables,
        docsIfSigQSignalNoise,
        docsIfSigQMicroreflections,
        docsIfSigQExtUnerroreds,
        docsIfSigQExtCorrecteds,
```

```
        docsIfSigQExtUncorrectables,
        docsIfDocsisBaseCapability
    }
    STATUS      current
    DESCRIPTION
        "Group of objects implemented in both cable modems and
        cable modem termination systems."
    ::= { docsIfGroups 5 }

docsIfCmGroupV2 OBJECT-GROUP
    OBJECTS {
        docsIfCmCmtsAddress,
        docsIfCmCapabilities,
        docsIfCmRangingTimeout,
        docsIfCmStatusValue,
        docsIfCmStatusCode,
        docsIfCmStatusTxPower,
        docsIfCmStatusResets,
        docsIfCmStatusLostSyncs,
        docsIfCmStatusInvalidMaps,
        docsIfCmStatusInvalidUcds,
        docsIfCmStatusInvalidRangingResponses,
        docsIfCmStatusInvalidRegistrationResponses,
        docsIfCmStatusT1Timeouts,
        docsIfCmStatusT2Timeouts,
        docsIfCmStatusT3Timeouts,
        docsIfCmStatusT4Timeouts,
        docsIfCmStatusRangingAborteds,
        docsIfCmStatusDocsisOperMode,
        docsIfCmStatusModulationType,



        docsIfCmStatusEqualizationData,
        docsIfCmStatusUCCs,
        docsIfCmStatusUCCFails,
        docsIfCmServiceQosProfile,
        docsIfCmServiceTxSlotsImmed,
        docsIfCmServiceTxSlotsDed,
        docsIfCmServiceTxRetries,
        docsIfCmServiceTxExceededs,
        docsIfCmServiceRqRetries,
        docsIfCmServiceRqExceededs,
        docsIfCmServiceExtTxSlotsImmed,
        docsIfCmServiceExtTxSlotsDed,
        docsIfSigQEqualizationData
    }
    STATUS      current
```

```
    DESCRIPTION
        "Group of objects implemented in cable modems."
    ::= { docsIfGroups 6 }

docsIfCmtsGroupV2 OBJECT-GROUP
    OBJECTS {
        docsIfCmtsCapabilities,
        docsIfCmtsSyncInterval,
        docsIfCmtsUcdInterval,
        docsIfCmtsMaxServiceIds,
        docsIfCmtsInvitedRangingAttempts,
        docsIfCmtsInsertInterval,
        docsIfCmtsMacStorageType,
        docsIfCmtsStatusInvalidRangeReqs,
        docsIfCmtsStatusRangingAborteds,
        docsIfCmtsStatusInvalidRegReqs,
         docsIfCmtsStatusFailedRegReqs,
        docsIfCmtsStatusInvalidDataReqs,
        docsIfCmtsStatusT5Timeouts,
        docsIfCmtsCmStatusMacAddress,
        docsIfCmtsCmStatusDownChannelIfIndex,
        docsIfCmtsCmStatusUpChannelIfIndex,
        docsIfCmtsCmStatusRxPower,
        docsIfCmtsCmStatusTimingOffset,
        docsIfCmtsCmStatusEqualizationData,
        docsIfCmtsCmStatusValue,
        docsIfCmtsCmStatusUnerroreds,
        docsIfCmtsCmStatusCorrecteds,
        docsIfCmtsCmStatusUncorrectables,
        docsIfCmtsCmStatusSignalNoise,
        docsIfCmtsCmStatusMicroreflections,
        docsIfCmtsCmStatusExtUnerroreds,
        docsIfCmtsCmStatusExtCorrecteds,



        docsIfCmtsCmStatusExtUncorrectables,
        docsIfCmtsCmStatusDocsisRegMode,
        docsIfCmtsCmStatusModulationType,
        docsIfCmtsCmStatusInetAddressType,
        docsIfCmtsCmStatusInetAddress,
        docsIfCmtsCmStatusValueLastUpdate,
        docsIfCmtsCmStatusHighResolutionTimingOffset,
         docsIfCmtsServiceAdminStatus,
        docsIfCmtsServiceQosProfile,
        docsIfCmtsServiceCreateTime,
        docsIfCmtsServiceInOctets,
        docsIfCmtsServiceInPackets,
```

docsIfCmtsServiceNewCmStatusIndex,
docsIfCmtsModType,
docsIfCmtsModControl,
docsIfCmtsModPreambleLen,
docsIfCmtsModDifferentialEncoding,
docsIfCmtsModFECErrorCorrection,
docsIfCmtsModFECCodewordLength,
docsIfCmtsModScramblerSeed,
docsIfCmtsModMaxBurstSize,
docsIfCmtsModGuardTimeSize,
docsIfCmtsModLastCodewordShortened,
docsIfCmtsModScrambler,
docsIfCmtsModByteInterleaverDepth,
docsIfCmtsModByteInterleaverBlockSize,
docsIfCmtsModPreambleType,
docsIfCmtsModTcmErrorCorrectionOn,
docsIfCmtsModScdmaInterleaverStepSize,
docsIfCmtsModScdmaSpreaderEnable,
docsIfCmtsModScdmaSubframeCodes,
docsIfCmtsModChannelType,

docsIfCmtsModStorageType,
docsIfCmtsQosProfilePermissions,
docsIfCmtsCmPtr,
docsIfCmtsChannelUtilizationInterval,
docsIfCmtsChannelUtUtilization,
docsIfCmtsDownChnlCtrId,
docsIfCmtsDownChnlCtrTotalBytes,
docsIfCmtsDownChnlCtrUsedBytes,
docsIfCmtsDownChnlCtrExtTotalBytes,
docsIfCmtsDownChnlCtrExtUsedBytes,
docsIfCmtsUpChnlCtrId,
docsIfCmtsUpChnlCtrTotalMslots,
docsIfCmtsUpChnlCtrUcastGrantedMslots,
docsIfCmtsUpChnlCtrTotalCntnMslots,
docsIfCmtsUpChnlCtrUsedCntnMslots,
docsIfCmtsUpChnlCtrExtTotalMslots,

docsIfCmtsUpChnlCtrExtUcastGrantedMslots,
docsIfCmtsUpChnlCtrExtTotalCntnMslots,
docsIfCmtsUpChnlCtrExtUsedCntnMslots,
docsIfCmtsUpChnlCtrCollCntnMslots,
docsIfCmtsUpChnlCtrTotalCntnReqMslots,
docsIfCmtsUpChnlCtrUsedCntnReqMslots,
docsIfCmtsUpChnlCtrCollCntnReqMslots,
docsIfCmtsUpChnlCtrTotalCntnReqDataMslots,

```
        docsIfCmtsUpChnlCtrUsedCntnReqDataMslots,
        docsIfCmtsUpChnlCtrCollCntnReqDataMslots,
        docsIfCmtsUpChnlCtrTotalCntnInitMaintMslots,
        docsIfCmtsUpChnlCtrUsedCntnInitMaintMslots,
        docsIfCmtsUpChnlCtrCollCntnInitMaintMslots,
        docsIfCmtsUpChnlCtrExtCollCntnMslots,
        docsIfCmtsUpChnlCtrExtTotalCntnReqMslots,
        docsIfCmtsUpChnlCtrExtUsedCntnReqMslots,
        docsIfCmtsUpChnlCtrExtCollCntnReqMslots,
        docsIfCmtsUpChnlCtrExtTotalCntnReqDataMslots,
        docsIfCmtsUpChnlCtrExtUsedCntnReqDataMslots,
        docsIfCmtsUpChnlCtrExtCollCntnReqDataMslots,
        docsIfCmtsUpChnlCtrExtTotalCntnInitMaintMslots,
        docsIfCmtsUpChnlCtrExtUsedCntnInitMaintMslots,
        docsIfCmtsUpChnlCtrExtCollCntnInitMaintMslots,
        docsIfDownChannelStorageType,
        docsIfQosProfStorageType

    }
    STATUS      current
    DESCRIPTION
        "Group of objects implemented in Cable Modem
 Termination
         Systems."
    ::= { docsIfGroups 7 }

END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/DOCS-IF-MIB
No license file was found, but licenses were detected in source scan.

SNMP-FRAMEWORK-MIB DEFINITIONS ::= BEGIN

IMPORTS
    MODULE-IDENTITY, OBJECT-TYPE,
    OBJECT-IDENTITY,
    snmpModules                 FROM SNMPv2-SMI
    TEXTUAL-CONVENTION              FROM SNMPv2-TC
    MODULE-COMPLIANCE, OBJECT-GROUP     FROM SNMPv2-CONF;

snmpFrameworkMIB MODULE-IDENTITY
    LAST-UPDATED "200210140000Z"
    ORGANIZATION "SNMPv3 Working Group"
    CONTACT-INFO "WG-EMail:   snmpv3@lists.tislabs.com
                  Subscribe:  snmpv3-request@lists.tislabs.com

                  Co-Chair:   Russ Mundy
```

Network Associates Laboratories
postal: 15204 Omega Drive, Suite 300
Rockville, MD 20850-4601
USA
EMail: mundy@tislabs.com
phone: +1 301-947-7107

Co-Chair &
Co-editor: David Harrington

Enterasys Networks
postal: 35 Industrial Way
P. O. Box 5005
Rochester, New Hampshire 03866-5005
USA
EMail: dbh@enterasys.com
phone: +1 603-337-2614

Co-editor: Randy Presuhn
BMC Software, Inc.
postal: 2141 North First Street
San Jose, California 95131
USA
EMail: randy_presuhn@bmc.com
phone: +1 408-546-1006

Co-editor: Bert Wijnen
Lucent Technologies
postal: Schagen 33
3461 GL Linschoten
Netherlands

EMail: bwijnen@lucent.com
phone: +31 348-680-485

"
DESCRIPTION "The SNMP Management Architecture MIB

Copyright (C) The Internet Society (2002). This
version of this MIB module is part of RFC 3411;
see the RFC itself for full legal notices.
"

REVISION "200210140000Z" -- 14 October 2002
DESCRIPTION "Changes in this revision:
- Updated various administrative information.

```
                - Corrected some typos.
                - Corrected typo in description of SnmpEngineID
                  that led to range overlap for 127.
                - Changed '255a' to '255t' in definition of
                  SnmpAdminString to align with current SMI.
                - Reworded 'reserved' for value zero in
                  DESCRIPTION of SnmpSecurityModel.
                - The algorithm for allocating security models
                  should give
 256 per enterprise block, rather
                  than 255.
                - The example engine ID of 'abcd' is not
                  legal. Replaced with '800002b804616263'H based
                  on example enterprise 696, string 'abc'.
                - Added clarification that engineID should
                  persist across re-initializations.
                 This revision published as RFC 3411.
                "
    REVISION     "199901190000Z"        -- 19 January 1999
    DESCRIPTION  "Updated editors' addresses, fixed typos.
                  Published as RFC 2571.
                "
    REVISION     "199711200000Z"        -- 20 November 1997
    DESCRIPTION  "The initial version, published in RFC 2271.
                "
    ::= { snmpModules 10 }

 -- Textual Conventions used in the SNMP Management Architecture ***

SnmpEngineID ::= TEXTUAL-CONVENTION
  STATUS       current
  DESCRIPTION "An SNMP engine's
 administratively-unique identifier.
              Objects of this type are for identification, not for
              addressing, even though it is possible that an
              address may have been used in the generation of
              a specific value.



              The value for this object may not be all zeros or
              all 'ff'H or the empty (zero length) string.

              The initial value for this object may be configured
              via an operator console entry or via an algorithmic
              function.  In the latter case, the following
              example algorithm is recommended.
```

In cases where there are multiple engines on the
same system, the use of this algorithm is NOT
appropriate, as it would result in all of those
engines ending up with the same ID value.

1) The very first bit is used to indicate how the

rest of the data is composed.

0 - as defined by enterprise using former methods
that existed before SNMPv3. See item 2 below.

1 - as defined by this architecture, see item 3
below.

Note that this allows existing uses of the
engineID (also known as AgentID [RFC1910]) to
co-exist with any new uses.

2) The snmpEngineID has a length of 12 octets.

The first four octets are set to the binary
equivalent of the agent's SNMP management
private enterprise number as assigned by the
Internet Assigned Numbers Authority (IANA).
For example, if Acme Networks has been assigned
{ enterprises 696 }, the first four octets would
be assigned '000002b8'H.

The remaining eight octets
are determined via
one or more enterprise-specific methods. Such
methods must be designed so as to maximize the
possibility that the value of this object will
be unique in the agent's administrative domain.
For example, it may be the IP address of the SNMP
entity, or the MAC address of one of the
interfaces, with each address suitably padded
with random octets. If multiple methods are
defined, then it is recommended that the first
octet indicate the method being used and the
remaining octets be a function of the method.

3) The length of the octet string varies.

The first four octets are set to the binary

equivalent of the agent's SNMP management
private enterprise number as assigned by the
Internet Assigned Numbers Authority (IANA).
For example, if Acme Networks has been assigned
{ enterprises 696 }, the first four octets would
be assigned '000002b8'H.

The very first bit is set to 1. For example, the
above value for Acme Networks now changes to be
'800002b8'H.

The fifth octet indicates how the rest (6th and
following octets) are formatted. The values for
the fifth octet are:

0 - reserved, unused.

1 - IPv4 address (4 octets)
lowest non-special IP address

2 - IPv6 address (16 octets)
lowest non-special IP address

3 - MAC address (6 octets)
lowest IEEE MAC address, canonical order

4 - Text, administratively assigned
Maximum remaining length 27

5 - Octets, administratively assigned
Maximum remaining length 27

6-127 - reserved, unused

128-255 - as defined by the enterprise
Maximum remaining length 27

"

SYNTAX OCTET STRING (SIZE(5..32))

```
SnmpSecurityModel ::= TEXTUAL-CONVENTION
  STATUS       current
  DESCRIPTION "An identifier that uniquely identifies a
               Security Model of the Security Subsystem within
               this SNMP Management Architecture.

               The values for securityModel are allocated as
               follows:

               - The zero value does not identify any particular
                 security model.

               - Values between 1 and 255, inclusive,
are reserved
                 for standards-track Security Models and are
                 managed by the Internet Assigned Numbers Authority
                 (IANA).
               - Values greater than 255 are allocated to
                 enterprise-specific Security Models.  An
                 enterprise-specific securityModel value is defined
                 to be:

                 enterpriseID * 256 + security model within
                 enterprise

                 For example, the fourth Security Model defined by
                 the enterprise whose enterpriseID is 1 would be
                 259.

               This scheme for allocation of securityModel
               values allows for a maximum of 255 standards-
               based Security Models, and for a maximum of
               256 Security Models per enterprise.

               It is believed that the assignment of new
               securityModel values will be rare in
practice
               because the larger the number of simultaneously
               utilized Security Models, the larger the
               chance that interoperability will suffer.
               Consequently, it is believed that such a range
               will be sufficient.  In the unlikely event that
               the standards committee finds this number to be
               insufficient over time, an enterprise number
               can be allocated to obtain an additional 256
               possible values.
```

Note that the most significant bit must be zero;
hence, there are 23 bits allocated for various
organizations to design and define non-standard

securityModels. This limits the ability to
define new proprietary implementations of Security
Models to the first 8,388,608 enterprises.

It is worthwhile to note that, in its encoded

form, the securityModel value will normally
require only a single byte since, in practice,
the leftmost bits will be zero for most messages
and sign extension is suppressed by the encoding
rules.

As of this writing, there are several values
of securityModel defined for use with SNMP or
reserved for use with supporting MIB objects.
They are as follows:

0 reserved for 'any'
1 reserved for SNMPv1
2 reserved for SNMPv2c
3 User-Based Security Model (USM)
"
SYNTAX INTEGER(0 .. 2147483647)

SnmpMessageProcessingModel ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION "An identifier that uniquely identifies a Message
Processing Model of the Message Processing
Subsystem within this SNMP Management
Architecture.

The values for messageProcessingModel are
allocated as follows:

- Values between 0 and 255, inclusive, are
reserved for standards-track Message Processing
Models and are managed by the Internet Assigned
Numbers Authority (IANA).

- Values greater than 255 are allocated to
enterprise-specific Message Processing Models.

An enterprise messageProcessingModel value is defined to be:

enterpriseID * 256 +
    messageProcessingModel within enterprise

For example, the fourth Message Processing Model defined by the enterprise whose enterpriseID

is 1 would be 259.

This scheme for allocating messageProcessingModel values allows for a maximum of 255 standards-based Message Processing Models, and for a maximum of 256 Message Processing Models per enterprise.

It is believed that the assignment of new messageProcessingModel values will be rare in practice because the larger the number of simultaneously utilized Message Processing Models, the larger the chance that interoperability will suffer. It is believed that such a range will be sufficient. In the unlikely event that the standards committee finds this number to be insufficient over time, an enterprise number can be allocated to obtain an additional 256 possible values.

Note that the most significant bit must be zero; hence, there are 23 bits allocated for various organizations to design and define non-standard messageProcessingModels. This limits the ability to define new proprietary implementations of Message Processing Models to the first 8,388,608 enterprises.

It is worthwhile to note that, in its encoded form, the messageProcessingModel value will normally require only a single byte since, in practice, the leftmost bits will be zero for most messages and sign extension is suppressed by the encoding rules.

As of this writing, there are several values of messageProcessingModel defined for use with SNMP.

```
            They are as follows:

               0  reserved for SNMPv1
               1  reserved for SNMPv2c
               2  reserved for SNMPv2u and SNMPv2*
               3  reserved for SNMPv3
            "
  SYNTAX       INTEGER(0 .. 2147483647)




SnmpSecurityLevel
 ::= TEXTUAL-CONVENTION
  STATUS       current
  DESCRIPTION "A Level of Security at which SNMP messages can be
            sent or with which operations are being processed;
            in particular, one of:

              noAuthNoPriv - without authentication and
                           without privacy,
              authNoPriv   - with authentication but
                           without privacy,
              authPriv     - with authentication and
                           with privacy.

            These three values are ordered such that
            noAuthNoPriv is less than authNoPriv and
            authNoPriv is less than authPriv.
           "
  SYNTAX       INTEGER { noAuthNoPriv(1),
                  authNoPriv(2),
                  authPriv(3)
                }

SnmpAdminString ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "255t"
  STATUS
    current
  DESCRIPTION "An octet string containing administrative
            information, preferably in human-readable form.

            To facilitate internationalization, this
            information is represented using the ISO/IEC
            IS 10646-1 character set, encoded as an octet
            string using the UTF-8 transformation format
```

described in [RFC2279].

Since additional code points are added by amendments to the 10646 standard from time to time, implementations must be prepared to encounter any code point from 0x00000000 to 0x7fffffff. Byte sequences that do not correspond to the valid UTF-8 encoding of a code point or are outside this range are prohibited.

The use of control codes should be avoided.

When it is necessary to represent a newline,

the control code sequence CR LF should be used.

The use of leading or trailing white space should be avoided.

For code points not directly supported by user interface hardware or software, an alternative means of entry and display, such as hexadecimal, may be provided.

For information encoded in 7-bit US-ASCII, the UTF-8 encoding is identical to the US-ASCII encoding.

UTF-8 may require multiple bytes to represent a single character / code point; thus the length of this object in octets may be different from the number of characters encoded. Similarly, size constraints refer to the number of encoded octets, not the number of characters represented by an encoding.

Note that when this
TC is used for an object that
is used or envisioned to be used as an index, then a SIZE restriction MUST be specified so that the number of sub-identifiers for any object instance does not exceed the limit of 128, as defined by [RFC3416].

```
            Note that the size of an SnmpAdminString object is
            measured in octets, not characters.
           "
  SYNTAX      OCTET STRING (SIZE (0..255))


-- Administrative assignments ************************************

snmpFrameworkAdmin
  OBJECT IDENTIFIER ::= { snmpFrameworkMIB 1 }
snmpFrameworkMIBObjects
  OBJECT IDENTIFIER ::= { snmpFrameworkMIB 2 }
snmpFrameworkMIBConformance
  OBJECT IDENTIFIER ::= { snmpFrameworkMIB 3 }

-- the snmpEngine Group ******************************************

snmpEngine OBJECT IDENTIFIER ::= { snmpFrameworkMIBObjects 1 }




snmpEngineID    OBJECT-TYPE
  SYNTAX      SnmpEngineID
   MAX-ACCESS   read-only
  STATUS      current
  DESCRIPTION "An SNMP engine's administratively-unique identifier.

            This information SHOULD be stored in non-volatile
            storage so that it remains constant across
            re-initializations of the SNMP engine.
           "
  ::= { snmpEngine 1 }

snmpEngineBoots  OBJECT-TYPE
  SYNTAX      INTEGER (1..2147483647)
  MAX-ACCESS   read-only
  STATUS      current
  DESCRIPTION "The number of times that the SNMP engine has
            (re-)initialized itself since snmpEngineID
            was last configured.
           "
  ::= { snmpEngine 2 }

snmpEngineTime   OBJECT-TYPE
  SYNTAX      INTEGER (0..2147483647)
```

```
  UNITS       "seconds"
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION "The number of seconds since the value of
              the snmpEngineBoots object last changed.
              When incrementing this object's value would
               cause it to exceed its maximum,
              snmpEngineBoots is incremented as if a
              re-initialization had occurred, and this
              object's value consequently reverts to zero.
             "
  ::= { snmpEngine 3 }

snmpEngineMaxMessageSize OBJECT-TYPE
  SYNTAX       INTEGER (484..2147483647)
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION "The maximum length in octets of an SNMP message
              which this SNMP engine can send or receive and
              process, determined as the minimum of the maximum
              message size values supported among all of the
              transports available to and supported by the engine.
             "
  ::= { snmpEngine 4 }



-- Registration Points for Authentication and Privacy Protocols **

snmpAuthProtocols OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION  "Registration point for standards-track
               authentication protocols
 used in SNMP Management
               Frameworks.
              "
  ::= { snmpFrameworkAdmin 1 }

snmpPrivProtocols OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION  "Registration point for standards-track privacy
               protocols used in SNMP Management Frameworks.
              "
  ::= { snmpFrameworkAdmin 2 }

-- Conformance information ********************************************

snmpFrameworkMIBCompliances
```

```
            OBJECT IDENTIFIER ::= {snmpFrameworkMIBConformance 1}
snmpFrameworkMIBGroups
            OBJECT IDENTIFIER ::= {snmpFrameworkMIBConformance 2}

-- compliance statements

snmpFrameworkMIBCompliance MODULE-COMPLIANCE
  STATUS       current
  DESCRIPTION "The compliance statement for SNMP engines which
               implement the SNMP Management Framework MIB.
              "
  MODULE    -- this module
     MANDATORY-GROUPS { snmpEngineGroup }

  ::= { snmpFrameworkMIBCompliances 1 }

-- units of conformance

snmpEngineGroup
 OBJECT-GROUP
  OBJECTS {
           snmpEngineID,
           snmpEngineBoots,
           snmpEngineTime,
           snmpEngineMaxMessageSize
          }
  STATUS       current
  DESCRIPTION "A collection of objects for identifying and
               determining the configuration and current timeliness




               values of an SNMP engine.
              "
  ::= { snmpFrameworkMIBGroups 1 }

END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/SNMP-FRAMEWORK-MIB
No license file was found, but licenses were detected in source scan.

DOCS-CABLE-DEVICE-MIB DEFINITIONS ::= BEGIN

IMPORTS
      MODULE-IDENTITY,
      OBJECT-TYPE,
      IpAddress,
```

```
    Unsigned32,
    Counter32,
    Integer32,
    zeroDotZero,
    mib-2
        FROM SNMPv2-SMI          -- RFC 2578
    RowStatus,
    RowPointer,
    DateAndTime,
    TruthValue,
    StorageType
        FROM SNMPv2-TC           -- RFC 2579
    InetAddressType,
    InetAddress
        FROM INET-ADDRESS-MIB    -- RFC 4001
    OBJECT-GROUP,
    MODULE-COMPLIANCE
        FROM SNMPv2-CONF         -- RFC 2580
    SnmpAdminString
        FROM SNMP-FRAMEWORK-MIB  -- RFC 3411
    InterfaceIndexOrZero
        FROM IF-MIB              -- RFC 2863
    ZeroBasedCounter32
        FROM RMON2-MIB           -- RFC 4502
    diffServMIBDataPathGroup,
    diffServMIBClfrGroup,

   diffServMIBClfrElementGroup,
    diffServMIBMultiFieldClfrGroup,
    diffServMIBActionGroup,
    diffServMIBDscpMarkActGroup,
    diffServMIBCounterGroup,
    diffServMIBAlgDropGroup,



    diffServDataPathStatus,
    diffServClfrStatus,
    diffServClfrElementStatus,
    diffServMultiFieldClfrAddrType,
    diffServMultiFieldClfrSrcAddr,
    diffServMultiFieldClfrDstAddr,
    diffServAlgDropStatus,
    diffServDataPathStorage,
    diffServClfrStorage,
    diffServClfrElementStorage,
    diffServMultiFieldClfrStorage,
    diffServActionStorage,
```

```
        diffServCountActStorage,
        diffServAlgDropStorage,
        diffServAlgDropType
            FROM DIFFSERV-MIB;        -- RFC 3289


docsDev MODULE-IDENTITY
        LAST-UPDATED    "200612200000Z" -- December 20, 2006
        ORGANIZATION    "IETF IP over Cable Data Network
                         Working Group"
        CONTACT-INFO
          "       Rich
 Woundy
            Postal: Comcast Cable
                    27 Industrial Avenue
                    Chelmsford, MA 01824 U.S.A.
            Phone:  +1 978 244 4010
            E-mail: richard_woundy@cable.comcast.com

                    Kevin Marez
            Postal: Motorola Corporation
                    6450 Sequence Drive
                    San Diego, CA 92121 U.S.A.
            Phone:  +1 858 404 3785
            E-mail: kevin.marez@motorola.com

            IETF IPCDN Working Group
            General Discussion: ipcdn@ietf.org
            Subscribe: http://www.ietf.org/mailman/listinfo/ipcdn
            Archive: ftp://ftp.ietf.org/ietf-mail-archive/ipcdn
            Co-chairs: Richard Woundy,
                       richard_woundy@cable.comcast.com
                       Jean-Francois Mule,
                       jf.mule@cablelabs.com"

        DESCRIPTION
          "This is the MIB Module for DOCSIS-compliant cable modems




            and cable-modem
 termination systems.

            Copyright (C) The IETF Trust (2006).  This version
            of this MIB module was published in RFC 4639; for full
            legal notices see the RFC itself."

        REVISION "200612200000Z" -- December 20, 2006
```

DESCRIPTION
"Second version, published as RFC 4639.

Modifications to this MIB module since RFC 2669 include:
- Deprecation of the docsDevFilter group in favor of the
DiffServ MIB groups, to enable support for IPv6
filtering and DiffServ Code Point (DSCP) marking.
- Deprecation of the docsDevCpeGroup in favor of the
docsDevCpeInetGroup, to enable support of IPv6.
- Addition of various InetAddress objects to enable
support of IPv6.
- Deprecation of docsDevNmAccessTable in favor of SNMP
Coexistence and SNMPv3 -- yet adding
docsDevNmAccessTrapVersion and clarifying
docsDevNmAccessIp for current use of this table,
- Addition of docsDevIgmpModeControl for management and
control of the IGMP mode of operation,
- Addition of docsDevMaxCpe for management of the
maxmium number of CPEs permitted access through a
cable modem,
- Addition of docsDevSwServerTransportProtocol, and
modifications to docsDevSoftware object DESCRIPTIONS,
to enable software downloads via either TFTP or HTTP,
- Replacement of docsDevEvThrottleInhibited with
docsDevEvThrottleThresholdExceeded to simplify
event threshold management,
- Modification of docsDevEvReporting to enable local
logging to the internal volatile log, and not to the
internal non-volatile log,
- Modification of the compliance statement to make the
docsDevCpe objects optional
- Created placeholders for two OIDs in the
docsDevFilterPolicyTable that were never used
- Modified the DESCRIPTION of
docsDevSwServerTransportProtocol and
docsDevSwServerAddressType to address the
dependence between each object
- Added a reference to docsDevServerConfigTftpAddress
- Clarified the scope of notifications that are covered
by docsDevEvThrottleThreshold
- Clarified an error condition that could occur when

doing a SET to docsDevEvReporting
- Defined each of the enumerated types for both
docsDevEvLevel and docsDevEvPriority
- Added UNITS clause to docsDevFilterLLCMatches,

docsDevFilterIpMatches, docsDevMaxCpe,
docsDevEvThrottleThreshold and docsDevEvCounts.
- Added REFERENCE clause to docsDevFilterIpProtocol
- Modified DESCRIPTION
of docsDevCpeInetAddr to be
more protocol-neutral
- Removed the enumerated value (1) from both
docsDevCpeInetSource and docsDevCpeSource
- Covered additional read-write and read-create objects
in the Security Considerations section
- Modified the default value of docsDevNmAccessIpMask
to be consistent with OSSI specification
- Modified the SYNTAX of docsDevNmAccessCommunity and
docsDevNmAccessInterfaces in the Conformance
Statement section
- Added SYNTAX clause to docsDevEvReporting in the
Conformance Statement section
- Modified SYNTAX clause of docsDevEvReporting to
move new enumerated type to byte boundary
- Added references to DOCSIS 2.0 specifications to
multiple objects
- Clarified non-persistency across reboots for
all
tables
- Clarified functionality of docsDevSw objects as
they relate to docsDevSwOperStatus
- Clarified enumerated types (9) and (10) for
docsDevServerBootState
- Defined the state of unknown(0) for the following
objects: docsDevServerDhcpAddressType,
docsDevServerTimeAddressType,
docsDevServerConfigTftpAddressType and
docsDevServerConfigTftpAddressType
- Modified the value in docsDevFilterIpDaddr to be
consistent with the SYNTAX
- Specified which rows could be modified in an
active row for docsDevFilterPolicyStatus
- Defined the term 'manually' in docsDevCpeEnroll
- Clarified the description for
docsDevFilterTosOrMask
- Covered the case of a non-existent row for
docsDevFilterPolicyPtr
- Added DEFVAL clauses for multiple
objects
- Replaced docsDevNotification OBJECT IDENTIFIER
with docsDevNotifications to address possible
compatibility issues

```
            - Added support for the usage of RFC 3413 and RFC 3014
              as event notification mechanisms
            - Removed docsDevFilterPolicyObsoleteGroup
            - Added stdInterface(9) type to docsDevEvReporting to
              support the usage of RFC3413 and RFC3014
            - Modified DESCRIPTION for docsDevMaxCpe"

        REVISION "199908190000Z"
        DESCRIPTION
           "Initial version, published as RFC 2669."

        ::= { mib-2 69 }

docsDevMIBObjects  OBJECT IDENTIFIER ::= { docsDev 1 }

docsDevBase OBJECT IDENTIFIER ::= { docsDevMIBObjects 1 }

--
-- For the following object, there is no concept in the
-- RFI specification corresponding to a backup CMTS.  The
-- enumeration is provided here in case someone is able
-- to define such a role or device.
--

docsDevRole OBJECT-TYPE
       SYNTAX INTEGER {
          cm(1),
          cmtsActive(2),
          cmtsBackup(3)
        }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
           "Defines the current role of this device.  cm(1) is a
            Cable Modem, cmtsActive(2) is a Cable Modem Termination
            System that is controlling the system of cable modems,
            and cmtsBackup(3) is a CMTS that is currently connected
            but is not controlling the system (not currently used).

            In general, if this device is a 'cm', its role will not
            change during operation or between reboots.  If the
            device is a 'cmts' it may change between cmtsActive and
            cmtsBackup and back again during normal operation.  NB:
            At this time, the DOCSIS standards do not support the
            concept of a backup CMTS, but cmtsBackup is included for
            completeness."
```

```
    ::= { docsDevBase 1 }



docsDevDateTime
 OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
       "The current date and time, with time zone information
        (if known).

        If the real data and time cannot be determined, this
        shall represent elapsed time from boot relative to
        the standard epoch '1970-1-1,0:0:0.0'.  In other
        words, if this agent has been up for 3 minutes and
        not been able to determine what the actual date and
        time are, this object will return the value
        '1970-1-1,0:03:0.0'."
    ::= { docsDevBase 2 }

docsDevResetNow OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
       "Setting this object to true(1) causes the device to
        reset.  Reading this object always returns false(2)."
    ::= { docsDevBase 3 }

docsDevSerialNumber
 OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       "The manufacturer's serial number for this device."
    ::= { docsDevBase 4 }

docsDevSTPControl OBJECT-TYPE
    SYNTAX INTEGER {
       stEnabled(1),
       noStFilterBpdu(2),
       noStPassBpdu(3)
    }
    MAX-ACCESS  read-write
```

```
        STATUS      current
        DESCRIPTION
            "This object controls operation of the spanning tree
             protocol (as distinguished from transparent bridging).

             If set to stEnabled(1), then the spanning tree protocol
             is enabled, subject to bridging constraints.



             If noStFilterBpdu(2), then spanning tree is not active,
             and Bridge PDUs received are discarded.

             If noStPassBpdu(3), then spanning tree is not active,
             and Bridge PDUs are transparently forwarded.

             Note that a device need
 not implement all of these
             options, but that noStFilterBpdu(2) is required."
        DEFVAL { noStFilterBpdu }
        ::= { docsDevBase 5 }

docsDevIgmpModeControl OBJECT-TYPE
        SYNTAX INTEGER {
            passive(1),
            active(2)
        }
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
            "This object controls the IGMP mode of operation for
             the CM or CMTS.  In passive mode, the device forwards
             IGMP between interfaces as based on knowledge of
             Multicast Session activity on the subscriber side
             interface and the rules defined in the DOCSIS RFI
             specification.  In active mode, the device terminates
             at and initiates IGMP through its interfaces as based
             on the knowledge of Multicast Session activity on the
             subscriber side interface."
        REFERENCE
            "DOCSIS RFI 1.1 Specification, Section 3.3.1. and

             DOCSIS RFI 2.0 Specification, Section 5.3.1."
        DEFVAL { passive }
        ::= { docsDevBase 6 }

docsDevMaxCpe OBJECT-TYPE
        SYNTAX      Unsigned32 (0..255)
```

```
        UNITS       "CPEs"
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
           "The maximum number of CPEs that can be granted access
            through a CM during a CM epoch.  This value can be
            obtained from the CM configuration file; however,
            it may be adjusted by the CM according to hardware or
            software limitations that have been imposed on the
            implementation."
        REFERENCE
           "DOCSIS RFI 1.0 Specification, Appendix C.7.20., and




            DOCSIS RFI 1.1 Specification, Appendix C.1.1.7. and
            DOCSIS RFI 2.0 Specification, Appendix C.1.1.7."
        ::= { docsDevBase 7 }



--
-- The following table provides one level of security for access
-- to the device by network management stations.
--
 Note that access is also constrained by the
-- community strings and any vendor-specific security.
--

docsDevNmAccessTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF DocsDevNmAccessEntry
        MAX-ACCESS  not-accessible
        STATUS      deprecated
        DESCRIPTION
           "This table controls access to SNMP objects by network
            management stations.  If the table is empty, access to
            SNMP objects is unrestricted.  The objects in this table
            MUST NOT persist across reboots.  The objects in this
            table are only accessible from cable devices that are
            not capable of operating in SNMP Coexistence mode
            (RFC 3584) or in SNMPv3 mode (RFC 3410).
            See the conformance section for
            details.  Note that some devices are required by other
            specifications (e.g., the DOCSIS OSSIv1.1 specification)
            to support the legacy SNMPv1/v2c docsDevNmAccess mode
            for
 backward compatibility.

            This table is deprecated.  Instead, use the SNMP
```

```
            coexistence MIBs from RFC 3584, the TARGET and
            NOTIFICATION MIBs from RFC 3413, and
            the View-Based Access Control Model (VACM) MIBs for
            all SNMP protocol versions from RFC 3415."
        ::= { docsDevMIBObjects 2 }

docsDevNmAccessEntry OBJECT-TYPE
        SYNTAX      DocsDevNmAccessEntry
        MAX-ACCESS  not-accessible
        STATUS      deprecated
        DESCRIPTION
            "An entry describing access to SNMP objects by a
            particular network management station.  An entry in
            this table is not readable unless the management station
            has read-write permission (either implicit if the table
            is empty, or explicit through an entry in this table).
            Entries are ordered by docsDevNmAccessIndex.  The first




            matching entry (e.g., matching IP address and community

    string) is used to derive access."
        INDEX { docsDevNmAccessIndex }
        ::= {  docsDevNmAccessTable 1 }

DocsDevNmAccessEntry ::= SEQUENCE {
            docsDevNmAccessIndex         Integer32,
            docsDevNmAccessIp            IpAddress,
            docsDevNmAccessIpMask        IpAddress,
            docsDevNmAccessCommunity     OCTET STRING,
            docsDevNmAccessControl       INTEGER,
            docsDevNmAccessInterfaces    OCTET STRING,
            docsDevNmAccessStatus        RowStatus,
            docsDevNmAccessTrapVersion   INTEGER
        }

docsDevNmAccessIndex OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      deprecated
        DESCRIPTION
            "Index used to order the application of access
            entries."
        ::= { docsDevNmAccessEntry 1 }

docsDevNmAccessIp OBJECT-TYPE
        SYNTAX      IpAddress
```

```
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "The IP address (or subnet) of the network management
            station.  The address 0.0.0.0 is defined to mean
            any Network Management Station (NMS).  If traps are
            enabled for this entry, then the value must be the
            address of a specific device.  Implementations MAY
            recognize 255.255.255.255 as equivalent to 0.0.0.0."
        DEFVAL { '00000000'h }
        ::= { docsDevNmAccessEntry 2 }

    docsDevNmAccessIpMask OBJECT-TYPE
        SYNTAX      IpAddress
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "The IP subnet mask of the network management stations.
            If traps are enabled for this entry, then the value must
            be 0.0.0.0.  Implementations MAY recognize
            255.255.255.255 as equivalent to 0.0.0.0."



        DEFVAL { '00000000'h }
        ::= { docsDevNmAccessEntry 3 }

    docsDevNmAccessCommunity OBJECT-TYPE
        SYNTAX      OCTET
     STRING
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "The community string to be matched for access by this
            entry.  If set to a zero-length string, then any
            community string will match.  When read, this object
            SHOULD return a zero-length string."
        DEFVAL { "public" }
        ::= { docsDevNmAccessEntry 4 }

    docsDevNmAccessControl OBJECT-TYPE
        SYNTAX        INTEGER {
           none(1),
           read(2),
           readWrite(3),
           roWithTraps(4),
           rwWithTraps(5),
           trapsOnly(6)
```

```
    }
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
       "Specifies the type of access allowed to this NMS.
        Setting this object to none(1) causes the table entry
        to be destroyed.  Read(2) allows access by 'get' and
        'get-next' PDUs.  ReadWrite(3) allows access by 'set' as
        well.
 RoWithtraps(4), rwWithTraps(5), and trapsOnly(6)
        control distribution of Trap PDUs transmitted by this
        device."
    DEFVAL { read }
    ::= { docsDevNmAccessEntry 5 }

-- The syntax of the following object was copied from RFC 1493,
-- dot1dStaticAllowedToGoTo.

docsDevNmAccessInterfaces OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE (1..32))
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
       "Specifies the set of interfaces from which requests from
        this NMS will be accepted.  Each octet within
        the value of this object specifies a set of eight




        interfaces, the first octet specifying ports 1
        through 8, the second octet specifying interfaces 9
        through 16, etc.  Within each octet, the most
        significant bit represents the lowest numbered
        interface, and the least significant bit represents the
        highest numbered
 interface.  Thus, each interface is
        represented by a single bit within the value of this
        object.  If that bit has a value of '1' then that
        interface is included in the set.

        Note that entries in this table apply only to link-layer
        interfaces (e.g., Ethernet and CATV MAC).  Bits
        representing upstream and downstream channel interfaces
        MUST NOT be set to '1'.

        Note that if bits corresponding to non-existing
        interfaces are set, the result is implementation
        specific.
```

```
            Note that according to the DOCSIS OSSIv1.1
            specification, when ifIndex '1' is included in the
            set, then this row applies to all CPE
            (customer-facing) interfaces.

            The size of this object is the minimum required to
            represent all configured interfaces for this device."
        ::= { docsDevNmAccessEntry 6 }

docsDevNmAccessStatus
 OBJECT-TYPE
        SYNTAX      RowStatus
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "Controls and reflects the status of rows in this
            table.  Rows in this table may be created by either the
            create-and-go or create-and-wait paradigm.  There is no
            restriction on changing values in a row of this table
            while the row is active.

            The following objects MUST have valid values before this
            object can be set to active: docsDevNmAccessIp,
            docsDevNmAccessStatus, docsDevNmAccessIpMask,
            docsDevNmAccessCommunity, docsDevNmAccessControl, and
            docsDevNmAccessInterfaces."
        ::= { docsDevNmAccessEntry 7 }

docsDevNmAccessTrapVersion OBJECT-TYPE
        SYNTAX      INTEGER {



           disableSNMPv2trap(1),
           enableSNMPv2trap(2)
        }
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "Specifies the TRAP version that is sent to this NMS.
            Setting this object to disableSNMPv2trap (1) causes the
            trap in SNMPv1 format to be sent to a particular NMS.
            Setting this object to enableSNMPv2trap (2) causes the
            trap in SNMPv2 format be sent to a particular NMS."
        DEFVAL { disableSNMPv2trap }
        ::= { docsDevNmAccessEntry 8 }
```

```
--
-- The following group describes control objects used for downloading
-- firmware to a cable device.  Procedures for software download are
-- described in Section 3.2.1 of the RFC containing this MIB module.
--

docsDevSoftware OBJECT IDENTIFIER ::= { docsDevMIBObjects 3 }

docsDevSwServer OBJECT-TYPE
      SYNTAX      IpAddress
      MAX-ACCESS  read-write
      STATUS      deprecated
      DESCRIPTION
         "The address of the TFTP server used for software
          upgrades.  If the TFTP server is unknown or is a
          non-IPv4 address, return
 0.0.0.0.

          This object is deprecated.  See docsDevSwServerAddress
          for its replacement.  This object will have its value
          modified, given a valid SET to docsDevSwServerAddress."
      ::= { docsDevSoftware 1 }

docsDevSwFilename OBJECT-TYPE
      SYNTAX      SnmpAdminString (SIZE (0..64))
      MAX-ACCESS  read-write
      STATUS      current
      DESCRIPTION
         "The filename of the software image to be downloaded via
          TFTP, or the abs_path (as defined in RFC 2616) of the
          software image to be downloaded via HTTP.

          Unless set via SNMP, this is the filename or abs_path
          specified by the provisioning server during the boot
          process that corresponds to the software version that




          is desired for this device.

          If unknown, the value of this object is the zero-length
          string."
      ::= { docsDevSoftware 2 }

docsDevSwAdminStatus OBJECT-TYPE
       SYNTAX INTEGER {
          upgradeFromMgt(1),
          allowProvisioningUpgrade(2),
```

```
        ignoreProvisioningUpgrade(3)
    }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "If set to upgradeFromMgt(1), the device will initiate a
         TFTP or HTTP software image download.  After
         successfully receiving an image, the device will set
         its state to ignoreProvisioningUpgrade(3) and reboot.
         If the download process is interrupted (e.g., by a reset
         or power failure), the device will load the previous
         image and, after re-initialization, continue to attempt
         loading the image specified in docsDevSwFilename.

         If set to allowProvisioningUpgrade(2), the device will
         use the software version information supplied by the
         provisioning server when next rebooting (this does not
         cause a reboot).


        When set to ignoreProvisioningUpgrade(3), the device
         will disregard software image upgrade information
         from the provisioning server.

         Note that reading this object can return
         upgradeFromMgt(1).  This indicates that a software
         download is currently in progress, and that the device
         will reboot after successfully receiving an image."
    DEFVAL { allowProvisioningUpgrade }
    ::= { docsDevSoftware 3 }

docsDevSwOperStatus OBJECT-TYPE
    SYNTAX INTEGER {
        inProgress(1),
        completeFromProvisioning(2),
        completeFromMgt(3),
        failed(4),
        other(5)
    }



    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "InProgress(1) indicates that a TFTP or HTTP download is
         underway, either as a result of a version mismatch at
         provisioning or as a result of a upgradeFromMgt request.
```

No other docsDevSw* objects can be modified in
this state.

CompleteFromProvisioning(2) indicates that the last
software upgrade was a result of version mismatch at
provisioning.

CompleteFromMgt(3) indicates that the last software
upgrade was a result of setting docsDevSwAdminStatus to
upgradeFromMgt.

Failed(4) indicates that the last attempted download
failed, ordinarily due to TFTP or HTTP timeout."
REFERENCE
"DOCSIS RFI 1.0 Specification, Section 8.2., and
DOCSIS RFI 1.1 Specification, Section 10.1. and
DOCSIS RFI 2.0 Specification, Section 12.1."
::= { docsDevSoftware 4 }

docsDevSwCurrentVers OBJECT-TYPE
SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The software version currently operating in this device.
This
string's syntax is that used by the
individual vendor to identify software versions.
For a CM, this string will describe the current
software load. For a CMTS, this object SHOULD contain
a human-readable representation either of the vendor
specific designation of the software for the chassis,
or of the software for the control processor. If
neither of these is applicable, the value MUST be a
zero-length string."
::= { docsDevSoftware 5 }

docsDevSwServerAddressType OBJECT-TYPE
SYNTAX InetAddressType
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"The type of address of the TFTP or HTTP server used for

software upgrades.

```
            If docsDevSwServerTransportProtocol is currently set to
            tftp(1), attempting to set this object to dns(16) MUST
            result in an error."
        ::=
    { docsDevSoftware 6 }

docsDevSwServerAddress OBJECT-TYPE
        SYNTAX      InetAddress
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
            "The address of the TFTP or HTTP server used for software
            upgrades.

            If the TFTP/HTTP server is unknown, return the zero-
            length address string (see the TextualConvention).

            If docsDevSwServer is also implemented in this agent,
            this object is tied to it.  A set of this object to an
            IPv4 address will result in also setting the value of
            docsDevSwServer to that address.  If this object is set
            to an IPv6 address, docsDevSwServer is set to 0.0.0.0.
            If docsDevSwServer is set, this object is also set to
            that value.  Note that if both are set in the same
            action, the order of which one sets the other is
            undefined."
        ::= { docsDevSoftware 7 }

docsDevSwServerTransportProtocol
    OBJECT-TYPE
        SYNTAX INTEGER {
            tftp(1),
            http(2)
        }
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
            "This object specifies the transport protocol (TFTP or
            HTTP) to be used for software upgrades.

            If the value of this object is tftp(1), then the cable
            device uses TFTP (RFC 1350) read request packets to
            download the docsDevSwFilename from the
            docsDevSwServerAddress in octet mode.

            If the value of this object is http(2), then the cable
            device uses HTTP 1.0 (RFC 1945) or HTTP 1.1 (RFC 2616)
```

```
            GET requests sent to host docsDevSwServerAddress to



            download the software image from path docsDevSwFilename.

            If docsDevSwServerAddressType is currently set to
            dns(16), attempting to set this object to tftp(1) MUST
            result in an error."
        DEFVAL
{ tftp }
        ::= { docsDevSoftware 8 }

--
-- The following group describes server access and parameters used
-- for initial provisioning and bootstrapping.
--

docsDevServer OBJECT IDENTIFIER ::= { docsDevMIBObjects 4 }

docsDevServerBootState OBJECT-TYPE
        SYNTAX INTEGER {
            operational(1),
            disabled(2),
            waitingForDhcpOffer(3),
            waitingForDhcpResponse(4),
            waitingForTimeServer(5),
            waitingForTftp(6),
            refusedByCmts(7),
            forwardingDenied(8),
            other(9),
            unknown(10)
        }
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
            "If operational(1), the device has completed loading and
            processing of configuration parameters, and the CMTS has
            completed the Registration exchange.

            If disabled(2), then the device was administratively
            disabled, possibly by being refused network access
in
            the configuration file.

            If waitingForDhcpOffer(3), then a Dynamic Host
            Configuration Protocol (DHCP) Discover has been
            transmitted, and no offer has yet been received.
```

If waitingForDhcpResponse(4), then a DHCP Request has
been transmitted, and no response has yet been received.

If waitingForTimeServer(5), then a Time Request has been
transmitted, and no response has yet been received.

If waitingForTftp(6), then a request to the TFTP
parameter server has been made, and no response
received.

If refusedByCmts(7), then the Registration
Request/Response exchange with the CMTS failed.

If forwardingDenied(8), then the registration process
was completed, but the network access option in the
received configuration file prohibits forwarding.

If other(9), then the registration
process reached a
point that does not fall into one of the above
categories.

If unknown(10), then the device has not yet begun the
registration process or is in some other indeterminate
state."
REFERENCE
"DOCSIS RFI 1.0 Specification, Figure 7-1, and
DOCSIS RFI 1.1 Specification, Figure 9-1 and
DOCSIS RFI 2.0 Specification, Figure 11-1."
::= { docsDevServer 1 }

docsDevServerDhcp OBJECT-TYPE
SYNTAX IpAddress
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
"The IP address of the DHCP server that assigned an IP
address to this device. Returns 0.0.0.0 if DHCP is not
used for IP address assignment, or if this agent is
not assigned an IPv4 address.

This object is deprecated and is replaced by
docsDevServerDhcpAddress."
::= { docsDevServer

```
 2 }

docsDevServerTime OBJECT-TYPE
      SYNTAX      IpAddress
      MAX-ACCESS  read-only
      STATUS      deprecated
      DESCRIPTION
         "The IP address of the Time server (RFC 0868).  Returns
          0.0.0.0 if the time server IP address is unknown, or if
          the time server is not an IPv4 server.

          This object is deprecated and is replaced by




          docsDevServerTimeAddress."
      ::= { docsDevServer 3 }

docsDevServerTftp OBJECT-TYPE
      SYNTAX      IpAddress
      MAX-ACCESS  read-only
      STATUS      deprecated
      DESCRIPTION
         "The IP address of the TFTP server responsible for
          downloading provisioning and configuration parameters
          to this device.  Returns 0.0.0.0 if the TFTP server
          address is unknown or is not an IPv4 address.

          This object is deprecated and is replaced by
          docsDevServerConfigTftpAddress."
      ::= { docsDevServer
 4 }

docsDevServerConfigFile OBJECT-TYPE
      SYNTAX      SnmpAdminString
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "The name of the device configuration file read from
          the TFTP server.  Returns a zero-length string if
          the configuration file name is unknown."
      ::= { docsDevServer 5 }

docsDevServerDhcpAddressType OBJECT-TYPE
      SYNTAX      InetAddressType
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
```

"The type of address of docsDevServerDhcpAddress. If
DHCP was not used, this value should return
unknown(0)."
::= { docsDevServer 6 }

docsDevServerDhcpAddress OBJECT-TYPE
SYNTAX InetAddress
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The internet address of the DHCP server that assigned
an IP address to this device. Returns the zero length

octet string if DHCP was not used for IP address
assignment."
::= { docsDevServer 7 }

docsDevServerTimeAddressType OBJECT-TYPE
SYNTAX InetAddressType
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The type of address of docsDevServerTimeAddress. If
no time server exists, this value should return
unknown(0)."
::= { docsDevServer 8 }

docsDevServerTimeAddress OBJECT-TYPE
SYNTAX InetAddress
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The Internet address of the RFC 868 Time server,
as provided by DHCP option 4.

Note that if multiple values are provided to the
CM in DHCP option 4, the value of this MIB object
MUST be the Time server address from which the Time
of Day reference was acquired as based on the DOCSIS
RFI specification.
During the period of time where
the Time of Day have not been acquired, the Time
server address reported by the CM may report the
first address value in the DHCP option value or the
last server address the CM attempted to get the Time

```
            of day value.

            Returns the zero-length octet string if the time server
            IP address is not provisioned."
        REFERENCE
           "DOCSIS RFI 1.1 Specification, Section 9.2.7. and
            DOCSIS RFI 2.0 Specification, Section 11.2.7."
        ::= { docsDevServer 9 }

docsDevServerConfigTftpAddressType OBJECT-TYPE
        SYNTAX      InetAddressType
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
           "The type of address of docsDevServerConfigTftpAddress.
            If no TFTP server exists, this value should return
            unknown(0)."
        ::= { docsDevServer 10 }

docsDevServerConfigTftpAddress OBJECT-TYPE
         SYNTAX      InetAddress



        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
           "The internet address of the TFTP server responsible for
            downloading provisioning and configuration parameters
            to this device.  Returns the zero-length octet string if
            the config server address is unknown.  There are certain
            security risks that are involved with using TFTP."
        REFERENCE
           "RFC 3617, Section 5"
        ::= { docsDevServer 11 }


--
-- Event Reporting
--

docsDevEvent OBJECT IDENTIFIER ::= { docsDevMIBObjects 5 }

docsDevEvControl OBJECT-TYPE
        SYNTAX INTEGER {
           resetLog(1),
           useDefaultReporting(2)
        }
```

```
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
            "Setting this object to resetLog(1) empties the event
             log.  All data is deleted.  Setting it to
             useDefaultReporting(2) returns all event
 priorities to
             their factory-default reporting.  Reading this object
             always returns useDefaultReporting(2)."
        ::= { docsDevEvent 1 }

docsDevEvSyslog OBJECT-TYPE
        SYNTAX      IpAddress
        MAX-ACCESS  read-write
        STATUS      deprecated
        DESCRIPTION
            "The IP address of the Syslog server.  If 0.0.0.0, either
             syslog transmission is inhibited, or the Syslog server
             address is not an IPv4 address.

             This object is deprecated and is replaced by
             docsDevEvSyslogAddress."
        ::= { docsDevEvent 2 }

docsDevEvThrottleAdminStatus OBJECT-TYPE



        SYNTAX INTEGER {
            unconstrained(1),
            maintainBelowThreshold(2),
            stopAtThreshold(3),
            inhibited(4)
        }
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
            "Controls the transmission of traps and syslog messages
             with respect
 to the trap pacing threshold.

             unconstrained(1) causes traps and syslog messages to be
             transmitted without regard to the threshold settings.

             maintainBelowThreshold(2) causes trap transmission and
             syslog messages to be suppressed if the number of traps
             would otherwise exceed the threshold.
```

stopAtThreshold(3) causes trap transmission to cease at
the threshold and not to resume until directed to do so.

inhibited(4) causes all trap transmission and syslog
messages to be suppressed.

A single event is always treated as a single event for
threshold counting. That is, an event causing both a
trap and a syslog message is still treated as a single
event.

Writing to this object resets the thresholding state."
DEFVAL { unconstrained }
::= { docsDevEvent 3 }

docsDevEvThrottleInhibited OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
"If true(1), trap and syslog transmission is currently
inhibited due to thresholds and/or the current setting
of docsDevEvThrottleAdminStatus. In addition, this is
true(1) when transmission is inhibited because no
syslog (docsDevEvSyslog) or trap (docsDevNmAccessEntry)
destinations have been set.

This object is deprecated and is replaced by
docsDevEvThrottleThresholdExceeded."

::= { docsDevEvent 4 }

docsDevEvThrottleThreshold OBJECT-TYPE
SYNTAX Unsigned32
UNITS "events"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"Number of events per docsDevEvThrottleInterval permitted
before throttling is to occur.

A single event, whether the notification could result in

messages transmitted using syslog, SNMP, or both
protocols, and regardless of the number of destinations,
(including zero) is always treated as a single event for

```
            threshold counting.  For example, an event causing both
            a trap and a syslog message is still treated as a single
            event.

            All system notifications that occur within the device
            should be taken into consideration when calculating
            and monitoring the threshold."
        DEFVAL { 0 }
        ::= { docsDevEvent 5 }

docsDevEvThrottleInterval OBJECT-TYPE
        SYNTAX      Integer32 (1..2147483647)
        UNITS       "seconds"
        MAX-ACCESS  read-write
        STATUS      current
        DESCRIPTION
            "The interval over which docsDevEvThrottleThreshold
            applies."
        DEFVAL { 1 }
        ::= { docsDevEvent 6 }

--
-- The following table controls the reporting of the various classes
-- of events.
--

docsDevEvControlTable
 OBJECT-TYPE
        SYNTAX      SEQUENCE OF DocsDevEvControlEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
            "This table allows control of the reporting of event
            classes.  For each event priority, a combination of




            logging and reporting mechanisms may be chosen.  The
            mapping of event types to priorities is
            vendor dependent.  Vendors may also choose to allow
            the user to control that mapping through proprietary
            means.  Table entries MUST persist across reboots for
            CMTS devices and MUST NOT persist across reboots for CM
            devices."
        ::= {  docsDevEvent 7 }

docsDevEvControlEntry OBJECT-TYPE
        SYNTAX      DocsDevEvControlEntry
```

```
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
            "Allows configuration of the reporting mechanisms for a
             particular
    event priority."
        INDEX { docsDevEvPriority }
        ::= { docsDevEvControlTable 1 }

    DocsDevEvControlEntry ::= SEQUENCE {
            docsDevEvPriority       INTEGER,
            docsDevEvReporting      BITS
        }

    docsDevEvPriority OBJECT-TYPE
        SYNTAX INTEGER {
            emergency(1),
            alert(2),
            critical(3),
            error(4),
            warning(5),
            notice(6),
            information(7),
            debug(8)
        }
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
            "The priority level that is controlled by this
             entry.  These are ordered from most (emergency) to least
             (debug) critical.  Each event with a CM or CMTS has a
             particular priority level associated with it (as defined
             by the vendor).

             emergency(1) events indicate vendor-specific fatal
             hardware or software errors that prevent normal system
              operation.




             alert(2) events indicate a serious failure that causes
             the reporting system to reboot but is not caused by
             hardware or software malfunctioning.

             critical(3) events indicate a serious failure that
             requires attention and prevents the device from
             transmitting data but that could be recovered without
```

rebooting the system.

error(4) and warning(5) events indicate that a failure occurred that could interrupt the normal data flow but that does not cause the device to re-register.

notice(6) and information(7) events indicate a milestone or checkpoint in normal operation that could be of particular importance for troubleshooting.

debug(8) events are reserved for vendor-specific events.

During normal operation, no event more critical than notice(6) should be generated. Events between warning and emergency should be generated at appropriate levels of problems (e.g., emergency when the box is about to crash)."

::= { docsDevEvControlEntry 1 }

docsDevEvReporting OBJECT-TYPE
SYNTAX BITS {
local(0),
traps(1),
syslog(2),
-- The following are extensions to the original set of
-- labels. The extensions start at an octet boundary.
-- So for bits 3 - 7, one MUST set them to zero on send
-- and one MUST ignore them on receipt.
localVolatile(8),
stdInterface(9)
}
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"Defines the action to be taken on occurrence of this event class. Implementations may not necessarily support all options for all event classes but at minimum must allow traps and syslogging to be disabled.

If the local(0) bit is set, then log to the internal log and update non-volatile store, for backward

```
            compatibility with the original RFC 2669 definition.
            If the traps(1) bit is set, then generate
            an SNMP trap; if the syslog(2) bit is set, then
            send a syslog message (assuming that the syslog address
            is set).  If the localVolatile(8) bit is set, then
            log to the internal log without updating non-volatile
            store.  If the stdInterface(9) bit is set, then the
            agent ignores all other bits except the local(0),
            syslog(2), and localVolatile(8) bits.  Setting the
            stdInterface(9) bit indicates that RFC3413 and
            RFC3014 are being used to control event reporting
            mechanisms."
        ::= { docsDevEvControlEntry 2 }

docsDevEventTable OBJECT-TYPE
        SYNTAX      SEQUENCE OF DocsDevEventEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
            "Contains a log of network and device events that may be
            of interest in fault isolation and troubleshooting.
            If the local(0) bit is set in docsDevEvReporting,
            entries in this table MUST persist across reboots."
        ::= {  docsDevEvent 8 }

docsDevEventEntry OBJECT-TYPE
        SYNTAX      DocsDevEventEntry
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
            "Describes a network or device event that may be of
            interest in fault isolation and troubleshooting.
            Multiple sequential identical events are represented by
            incrementing docsDevEvCounts and setting
            docsDevEvLastTime to the current time rather than
            creating multiple rows.

            Entries are created with the first occurrence of an
            event.  docsDevEvControl can
    be used to clear the
            table.  Individual events cannot be deleted."
        INDEX { docsDevEvIndex }
        ::= { docsDevEventTable 1 }

DocsDevEventEntry ::= SEQUENCE {
            docsDevEvIndex          Integer32,
            docsDevEvFirstTime      DateAndTime,
```

```
        docsDevEvLastTime       DateAndTime,
        docsDevEvCounts         Counter32,
        docsDevEvLevel          INTEGER,
        docsDevEvId             Unsigned32,
        docsDevEvText           SnmpAdminString
    }

docsDevEvIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Provides relative ordering of the objects in the event
        log.  This object will always increase except when
        (a) the log is reset via docsDevEvControl,
        (b) the device reboots and does not implement
        non-volatile storage for this log, or (c)
 it reaches
        the value 2^31.  The next entry for all the above
        cases is 1."
    ::= { docsDevEventEntry 1 }

docsDevEvFirstTime OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of docsDevDateTime at the time this entry was
        created."
    ::= { docsDevEventEntry 2 }

docsDevEvLastTime OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "When an entry reports only one event, this object will
        have the same value as the corresponding instance of
        docsDevEvFirstTime.  When an entry reports multiple
        events, this object will record the value that
        docsDevDateTime had when the most recent event for this
        entry occurred."
    ::= { docsDevEventEntry 3 }

-- This object was renamed from docsDevEvCount to meet naming
--
```

```
 requirements for Counter32
docsDevEvCounts OBJECT-TYPE
      SYNTAX      Counter32
      UNITS       "events"



      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "The number of consecutive event instances reported by
          this entry.  This starts at 1 with the creation of this
          row and increments by 1 for each subsequent duplicate
          event."
      ::= { docsDevEventEntry 4 }
docsDevEvLevel OBJECT-TYPE
      SYNTAX INTEGER {
         emergency(1),
         alert(2),
         critical(3),
         error(4),
         warning(5),
         notice(6),
         information(7),
         debug(8)
      }
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
         "The priority level of this event, as defined by the
          vendor.  These are ordered from most serious (emergency)
          to least serious (debug).

          emergency(1) events
 indicate vendor-specific fatal
          hardware or software errors that prevent normal system
          operation.

          alert(2) events indicate a serious failure that causes
          the reporting system to reboot but that is not caused by
          hardware or software malfunctioning.

          critical(3) events indicate a serious failure that
          requires attention and prevents the device from
          transmitting data but that could be recovered without
          rebooting the system.

          error(4) and warning(5) events indicate that a failure
```

```
            occurred that could interrupt the normal data flow but
            that does not cause the device to re-register.

            notice(6) and information(7) events indicate a
            milestone or checkpoint in normal operation that could
            be of particular importance for troubleshooting.

            debug(8) events are reserved for vendor-specific




           events.

            During normal operation, no event more
            critical than notice(6) should be generated.  Events
            between warning and emergency should be generated at
            appropriate levels of problems (e.g., emergency when the
            box is about to crash)."
        ::= { docsDevEventEntry 5 }

--
-- It is strongly recommended that implementors follow the CableLabs
-- enumerations for docsDevEvId, per the DOCSIS OSSIv1.1 spec
-- and follow-on specifications.
--

docsDevEvId OBJECT-TYPE
        SYNTAX      Unsigned32
        MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
            "For this product, uniquely identifies the type of event
            that is reported by this entry."
        REFERENCE
            "DOCSIS OSSI 1.1 Specification, Appendix H and
            DOCSIS OSSI 2.0 Specification, Annex D."
        ::= { docsDevEventEntry 6 }

docsDevEvText OBJECT-TYPE
        SYNTAX      SnmpAdminString

       MAX-ACCESS  read-only
        STATUS      current
        DESCRIPTION
            "Provides a human-readable description of the event,
            including all relevant context (interface numbers,
            etc.)."
```

```
    ::= { docsDevEventEntry 7 }

docsDevEvSyslogAddressType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
       "The type of address of docsDevEvSyslogAddress.  If
        no syslog server exists, this value should return
        unknown(0)."
    DEFVAL { unknown }
    ::= { docsDevEvent 9 }




docsDevEvSyslogAddress OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
       "The Internet address of the Syslog server, as provided
        by DHCP option 7 or set via SNMP management.  If the
        address of the server is set to the zero-length
        string, the 0.0.0.0
 IPv4 address, or the 0: IPv6
        address, Syslog transmission is inhibited.

        Note that if multiple values are provided to the CM in
        DHCP option 7, the value of this MIB object MUST be the
        first Syslog server address received.

        By default at agent boot, this object returns the zero
        length string."
    ::= { docsDevEvent 10 }

docsDevEvThrottleThresholdExceeded OBJECT-TYPE
    SYNTAX TruthValue
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
       "If true(1), trap and syslog transmission is currently
        inhibited due to exceeding the trap/syslog event
        threshold in the current interval."
    ::= { docsDevEvent 11 }

--
-- Link Level Control Filtering
```

```
--

docsDevFilter OBJECT IDENTIFIER ::= { docsDevMIBObjects 6 }

docsDevFilterLLCUnmatchedAction OBJECT-TYPE
    SYNTAX INTEGER {
       discard(1),
       accept(2)
    }
    MAX-ACCESS
 read-write
    STATUS      current
    DESCRIPTION
       "LLC (Link Level Control) filters can be defined on an
        inclusive or exclusive basis: CMs can be configured to
        forward only packets matching a set of layer three
        protocols, or to drop packets matching a set of layer
        three protocols.  Typical use of these filters is to



        filter out possibly harmful (given the context of a
        large metropolitan LAN) protocols.

        If set to discard(1), any L2 packet that does not match
        at least one filter in the docsDevFilterLLCTable will be
        discarded.  If set to accept(2), any L2 packet that
        does not match at least one filter in the
        docsDevFilterLLCTable will be accepted for further
        processing (e.g., bridging).  In other words, if the
        packet does not match an entry in the table, it takes
        this action;
 if it does match an entry in the table, it
        takes the opposite of this action."
    DEFVAL { accept }
    ::= { docsDevFilter 1 }

docsDevFilterLLCTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsDevFilterLLCEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
       "A list of filters to apply to (bridged) LLC
        traffic.  The filters in this table are applied to
        incoming traffic on the appropriate interface(s)  prior
        to any further processing (e.g., before the packet
        is handed off for level 3 processing, or for bridging).
        The specific action taken when no filter is matched is
```

```
        controlled by docsDevFilterLLCUnmatchedAction.  Table
        entries MUST NOT persist across reboots for any device."
    ::= { docsDevFilter 2 }

docsDevFilterLLCEntry OBJECT-TYPE
    SYNTAX      DocsDevFilterLLCEntry
    MAX-ACCESS  not-accessible

  STATUS      current
    DESCRIPTION
      "Describes a single filter to apply to (bridged) LLC
       traffic received on a specified interface. "
    INDEX { docsDevFilterLLCIndex }
    ::= { docsDevFilterLLCTable 1 }

DocsDevFilterLLCEntry ::= SEQUENCE {
        docsDevFilterLLCIndex             Integer32,
        docsDevFilterLLCStatus            RowStatus,
        docsDevFilterLLCIfIndex           InterfaceIndexOrZero,
        docsDevFilterLLCProtocolType      INTEGER,
        docsDevFilterLLCProtocol          Integer32,
        docsDevFilterLLCMatches           Counter32
    }



docsDevFilterLLCIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
      "Index used for the identification of filters (note that
       LLC filter order is irrelevant)."
    ::= { docsDevFilterLLCEntry 1 }
docsDevFilterLLCStatus
 OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "Controls and reflects the status of rows in this
       table.  There is no restriction on changing any of the
       associated columns for this row while this object is set
       to active.

       Specifying only this object (with the
       appropriate index) on a CM is sufficient to create a
       filter row that matches all inbound packets on the
```

```
            ethernet interface and results in the packets being
            discarded.  docsDevFilterLLCIfIndex (at least) must be
            specified on a CMTS to create a row."
        ::= { docsDevFilterLLCEntry 2}

    docsDevFilterLLCIfIndex OBJECT-TYPE
        SYNTAX      InterfaceIndexOrZero
        MAX-ACCESS  read-create
        STATUS      current
        DESCRIPTION
            "The entry interface to which this filter applies.  The
            value corresponds
     to ifIndex for either a CATV MAC or
            another network interface.  If the value is zero, the
            filter applies to all interfaces.  In Cable Modems, the
            default value is the customer side interface(s).  In
            CMTSs, this object has to be specified to
            create a row in this table.

            Note that according to the DOCSIS OSSIv1.1
            specification, ifIndex '1' in the CM means that this
            row applies to all Cable Modem-to-CPE Interfaces
            (CMCI)."
        REFERENCE
            "DOCSIS OSSI 1.1 Specification, Section 3.3.4.1. and
            DOCSIS OSSI 2.0 Specification, Section 6.3.4.1."
        ::= { docsDevFilterLLCEntry 3 }



    docsDevFilterLLCProtocolType OBJECT-TYPE
        SYNTAX INTEGER {
            ethertype(1),
            dsap(2)
        }
        MAX-ACCESS  read-create
        STATUS      current
        DESCRIPTION
            "The format of the value in docsDevFilterLLCProtocol:
             either a two-byte Ethernet Ethertype, or a one-byte
            802.2 Service Access Point (SAP) value.  ethertype(1)
            also applies to Standard Network Access Protocol
            (SNAP) encapsulated frames."
        DEFVAL { ethertype }
        ::= { docsDevFilterLLCEntry 4 }

    docsDevFilterLLCProtocol OBJECT-TYPE
```

```
        SYNTAX      Integer32 (0..65535)
        MAX-ACCESS  read-create
        STATUS      current
        DESCRIPTION
           "The layer-three protocol for which this filter applies.
            The protocol value format depends on
            docsDevFilterLLCProtocolType.  Note that for SNAP
            frames, ethertype filtering is performed rather than
            Destination Service Access Point (DSAP) =0xAA."
        DEFVAL { 0 }
        ::= { docsDevFilterLLCEntry 5 }

    docsDevFilterLLCMatches OBJECT-TYPE
        SYNTAX      Counter32
        UNITS       "matches"
        MAX-ACCESS  read-only
        STATUS      current

       DESCRIPTION
           "Counts the number of times this filter was matched."
        ::= { docsDevFilterLLCEntry 6 }

    --
    -- IPv4 Filtering
    --

    docsDevFilterIpDefault OBJECT-TYPE
        SYNTAX INTEGER {
           discard(1),
           accept(2)
        }
        MAX-ACCESS  read-write




        STATUS      deprecated
        DESCRIPTION
           "The default behavior for (bridged) packets that do not
            match IP filters (or Internet filters, if implemented)
            is defined by docsDevFilterIpDefault.

            If set to discard(1), all packets not matching an IP
            filter in docsDevFilterIpTable will be discarded.  If
            set to accept(2), all packets not matching an IP filter
            or an Internet filter will be accepted for further
            processing (e.g., bridging)."
        DEFVAL { accept }
        ::= { docsDevFilter 3 }
```

```
docsDevFilterIpTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsDevFilterIpEntry
    MAX-ACCESS
 not-accessible
    STATUS      deprecated
    DESCRIPTION
       "An ordered list of filters or classifiers to apply to
        IP traffic.  Filter application is ordered by the filter
        index, rather than by a best match algorithm (note that
        this implies that the filter table may have gaps in the
        index values).  Packets that match no filters will have
        policy 0 in the docsDevFilterPolicyTable applied to
        them, if it exists.  Otherwise, Packets that match no
        filters are discarded or forwarded according to the
        setting of docsDevFilterIpDefault.

        Any IP packet can theoretically match multiple rows of
        this table.  When considering a packet, the table is
        scanned in row index order (e.g., filter 10 is checked
        before filter 20).  If the packet matches that filter
        (which means that it matches ALL criteria for that
row),
        actions appropriate to docsDevFilterIpControl and
        docsDevFilterPolicyId are taken.  If the packet was
        discarded processing is complete.  If
        docsDevFilterIpContinue is set to true, the filter
        comparison continues with the next row in the table,
        looking for additional matches.

        If the packet matches no filter in the table, the packet
        is accepted or dropped for further processing
        according to the setting of docsDevFilterIpDefault.
        If the packet is accepted, the actions specified by
        policy group 0 (e.g., the rows in
        docsDevFilterPolicyTable that have a value of 0 for
        docsDevFilterPolicyId) are taken, if that policy



        group exists.

        Logically, this table is consulted twice during the
        processing of any IP packet: once upon its acceptance
        from the L2 entity, and once upon
its transmission to
        the L2 entity.  In actuality, for cable modems, IP
        filtering is generally the only IP processing done for
```

transit traffic. This means that inbound and outbound
filtering can generally be done at the same time with
one pass through the filter table.

The objects in this table are only accessible from cable
devices that are not operating in DiffServ MIB mode
(RFC 3289). See the conformance section for details.

Note that some devices are required by other
specifications (e.g., the DOCSIS OSSIv1.1 specification)
to support the legacy SNMPv1/v2c docsDevFilter mode
for backward compatibility.

Table entries MUST NOT persist across reboots for any
device.

This table is deprecated. Instead, use the DiffServ MIB
from RFC 3289."
::= { docsDevFilter 4 }

docsDevFilterIpEntry
OBJECT-TYPE
SYNTAX DocsDevFilterIpEntry
MAX-ACCESS not-accessible
STATUS deprecated
DESCRIPTION
"Describes a filter to apply to IP traffic received on a
specified interface. All identity objects in this table
(e.g., source and destination address/mask, protocol,
source/dest port, TOS/mask, interface and direction)
must match their respective fields in the packet for
any given filter to match.

To create an entry in this table, docsDevFilterIpIfIndex
must be specified."
INDEX { docsDevFilterIpIndex }
::= { docsDevFilterIpTable 1 }

DocsDevFilterIpEntry ::= SEQUENCE {
docsDevFilterIpIndex Integer32,
docsDevFilterIpStatus RowStatus,
docsDevFilterIpControl INTEGER,

docsDevFilterIpIfIndex InterfaceIndexOrZero,

```
    docsDevFilterIpDirection        INTEGER,
        docsDevFilterIpBroadcast        TruthValue,
        docsDevFilterIpSaddr            IpAddress,
        docsDevFilterIpSmask            IpAddress,
        docsDevFilterIpDaddr            IpAddress,
        docsDevFilterIpDmask            IpAddress,
        docsDevFilterIpProtocol         Integer32,
        docsDevFilterIpSourcePortLow    Integer32,
        docsDevFilterIpSourcePortHigh   Integer32,
        docsDevFilterIpDestPortLow      Integer32,
        docsDevFilterIpDestPortHigh     Integer32,
        docsDevFilterIpMatches          ZeroBasedCounter32,
        docsDevFilterIpTos              OCTET STRING,
        docsDevFilterIpTosMask          OCTET STRING,
        docsDevFilterIpContinue         TruthValue,
        docsDevFilterIpPolicyId         Integer32
    }

docsDevFilterIpIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)

 MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
        "Index used to order the application of filters.
         The filter with the lowest index is always applied
         first."
    ::= { docsDevFilterIpEntry 1 }

docsDevFilterIpStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
        "Controls and reflects the status of rows in this
         table.  Specifying only this object (with the
         appropriate index) on a CM is sufficient to create a
         filter row that matches all inbound packets on the
         ethernet interface and results in the packets being
         discarded.  docsDevFilterIpIfIndex (at least) must be
         specified on a CMTS to create a row.  Creation of the
         rows may be done via either create-and-wait or
         create-and-go, but the filter is not applied until this

   object is set to (or changes to) active.  There is no
         restriction in changing any object in a row while this
         object is set to active."
    ::= { docsDevFilterIpEntry 2 }
```

```
docsDevFilterIpControl OBJECT-TYPE
    SYNTAX INTEGER {
       discard(1),
       accept(2),
       policy(3)
    }
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
       "If set to discard(1), all packets matching this filter
        will be discarded, and scanning of the remainder of the
        filter list will be aborted.  If set to accept(2), all
        packets matching this filter will be accepted for
        further processing (e.g., bridging).  If
        docsDevFilterIpContinue is set to true, see if there
        are other matches; otherwise, done.  If set to
        policy (3), execute the policy entries
        matched by docsDevFilterIpPolicyId in
        docsDevFilterPolicyTable.

         If docsDevFilterIpContinue is set to true, continue
        scanning the table for other matches; otherwise, done."
    DEFVAL { discard }
    ::= { docsDevFilterIpEntry 3 }

docsDevFilterIpIfIndex OBJECT-TYPE
    SYNTAX      InterfaceIndexOrZero
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
       "The entry interface to which this filter applies.  The
        value corresponds to ifIndex for either a CATV MAC or
        another interface.  If the value is zero, the
        filter applies to all interfaces.  Default value in CMs
        is the index of the customer-side (e.g., ethernet)
        interface(s).  In CMTSes, this object MUST be
        specified to create a row in this table.

        Note that according to the DOCSIS OSSIv1.1
        specification, ifIndex '1' in the Cable Modem means
        that this row applies to all CMCI (customer-facing)
         interfaces."
    REFERENCE
       "DOCSIS OSSI 1.1 Specification, Section 3.3.4.1. and
```

```
            DOCSIS OSSI 2.0 Specification, Section 6.3.4.1."
        ::= { docsDevFilterIpEntry 4 }

docsDevFilterIpDirection OBJECT-TYPE



        SYNTAX INTEGER {
           inbound(1),
           outbound(2),
           both(3)
        }
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "Determines whether the filter is applied to inbound(1)
            traffic, outbound(2) traffic, or traffic in both(3)
            directions."
        DEFVAL { inbound }
        ::= { docsDevFilterIpEntry 5 }

docsDevFilterIpBroadcast OBJECT-TYPE
        SYNTAX      TruthValue
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "If set to true(1), the filter only applies to multicast
            and broadcast traffic.  If set to false(2), the filter
            applies to all traffic."

       DEFVAL { false }
        ::= { docsDevFilterIpEntry 6 }

docsDevFilterIpSaddr OBJECT-TYPE
        SYNTAX      IpAddress
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "The source IP address, or portion thereof, that is to be
            matched for this filter.  The source address is first
            masked (ANDed) against docsDevFilterIpSmask before
            being compared to this value.  A value of 0 for this
            object and 0 for the mask matches all IP addresses."
        DEFVAL { '00000000'h }
        ::= { docsDevFilterIpEntry 7 }

docsDevFilterIpSmask OBJECT-TYPE
        SYNTAX      IpAddress
```

```
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "A bit mask that is to be applied to the source address
            prior to matching.  This mask is not necessarily the
            same as a subnet mask, but 1s bits must be leftmost and
            contiguous."
        DEFVAL
 { '00000000'h }



        ::= { docsDevFilterIpEntry 8 }

docsDevFilterIpDaddr OBJECT-TYPE
        SYNTAX      IpAddress
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "The destination IP address, or portion thereof, that is
            to be matched for this filter.  The destination address
            is first masked (ANDed) against docsDevFilterIpDmask
            before being compared to this value.  A value of
            00000000 for this object and 00000000 for the mask
            matches all IP addresses."
        DEFVAL { '00000000'h }
        ::= { docsDevFilterIpEntry 9 }

docsDevFilterIpDmask OBJECT-TYPE
        SYNTAX      IpAddress
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "A bit mask that is to be applied to the destination
            address prior to matching.  This mask is not necessarily
            the same as a subnet mask, but 1s bits MUST be leftmost

            and contiguous."
        DEFVAL { '00000000'h }
        ::= { docsDevFilterIpEntry 10 }

docsDevFilterIpProtocol OBJECT-TYPE
        SYNTAX Integer32 (0..256)
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
           "The IP protocol value that is to be matched.  For
            example, icmp is 1, tcp is 6, and udp is 17.  A value of
```

```
        256 matches ANY protocol."
    REFERENCE "www.iana.org/assignments/protocol-numbers"
    DEFVAL { 256 }
    ::= { docsDevFilterIpEntry 11 }

docsDevFilterIpSourcePortLow OBJECT-TYPE
    SYNTAX      Integer32 (0..65535)
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
       "This is the inclusive lower bound of the transport-layer
        source port range that is to be matched.  If the IP
        protocol of the packet is neither UDP nor TCP, this




        object is ignored during matching."
    REFERENCE "www.iana.org/assignments/port-numbers"
     DEFVAL { 0 }
    ::= { docsDevFilterIpEntry 12 }

docsDevFilterIpSourcePortHigh OBJECT-TYPE
    SYNTAX      Integer32 (0..65535)
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
       "This is the inclusive upper bound of the transport-layer
        source port range that is to be matched.  If the IP
        protocol of the packet is neither UDP nor TCP, this
        object is ignored during matching."
    REFERENCE "www.iana.org/assignments/port-numbers"
    DEFVAL { 65535 }
    ::= { docsDevFilterIpEntry 13 }

docsDevFilterIpDestPortLow OBJECT-TYPE
    SYNTAX      Integer32 (0..65535)
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
       "This is the inclusive lower bound of the transport-layer
        destination port range that is to be matched.  If the IP
        protocol of the packet is neither UDP nor TCP, this

       object is ignored during matching."
    REFERENCE "www.iana.org/assignments/port-numbers"
    DEFVAL { 0 }
    ::= { docsDevFilterIpEntry 14 }
```

```
docsDevFilterIpDestPortHigh OBJECT-TYPE
    SYNTAX      Integer32 (0..65535)
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
       "This is the inclusive upper bound of the transport-layer
        destination port range that is to be matched.  If the IP
        protocol of the packet is neither UDP nor TCP, this
        object is ignored during matching."
    REFERENCE "www.iana.org/assignments/port-numbers"
    DEFVAL { 65535 }
    ::= { docsDevFilterIpEntry 15 }

docsDevFilterIpMatches OBJECT-TYPE
    SYNTAX      ZeroBasedCounter32
    UNITS       "matches"
    MAX-ACCESS  read-only




    STATUS      deprecated
    DESCRIPTION
       "Counts the number of times this filter was matched.
        This object is initialized
 to 0 at boot, or at row
        creation, and is reset only upon reboot."
    ::= { docsDevFilterIpEntry 16 }

docsDevFilterIpTos  OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE (1))
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
       "This is the value to be matched to the packet's
        TOS (Type of Service) value (after the TOS value
        is ANDed with docsDevFilterIpTosMask).  A value for this
        object of 0 and a mask of 0 matches all TOS values."
    DEFVAL { '00'h }
    ::= { docsDevFilterIpEntry 17 }

docsDevFilterIpTosMask OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE (1))
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
       "The mask to be applied to the packet's TOS value before
        matching."
    DEFVAL { '00'h }
```

```
    ::= { docsDevFilterIpEntry 18 }

docsDevFilterIpContinue OBJECT-TYPE
    SYNTAX      TruthValue

 MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
       "If this value is set to true and docsDevFilterIpControl
        is anything but discard (1), continue scanning and
        applying policies.  See Section 3.3.3 for more
        details."
    DEFVAL { false }
    ::= { docsDevFilterIpEntry 19 }

docsDevFilterIpPolicyId OBJECT-TYPE
    SYNTAX      Integer32 (0..2147483647)
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
       "This object points to an entry in
        docsDevFilterPolicyTable.  If docsDevFilterIpControl



        is set to policy (3), execute all matching policies
        in docsDevFilterPolicyTable.  If no matching policy
        exists, treat as if docsDevFilterIpControl were set
        to accept (1).  If this object is set to the value of
        0, there is no matching policy, and
        docsDevFilterPolicyTable MUST NOT be consulted."
     DEFVAL { 0 }
    ::= { docsDevFilterIpEntry 20 }

--
-- Policy Mapping Table
--

docsDevFilterPolicyTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsDevFilterPolicyEntry
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
       "A Table that maps between a policy group ID and a set
        of pointers to policies to be applied.  All rows with
        the same docsDevFilterPolicyId are part of the same
        group of policy pointers and are applied in the order
        in this table.  docsDevFilterPolicyTable exists to
```

allow multiple policy actions (referenced by policy
pointers) to be applied to any given classified packet.
The policy actions are applied in index order.
For example:

Index ID Type Action
1 1 TOS 1
9 5 TOS 1
12 1 IPSEC 3

This says that a packet that matches a filter with
policy id 1 first has TOS policy 1 applied (which might
set the TOS bits to enable a higher priority) and next
has the IPSEC policy 3 applied (which may result in the
packets being dumped into a secure VPN to a remote
encryptor).

Policy ID 0 is reserved for default actions and is
applied only to packets that match no filters in
docsDevFilterIpTable.

Table entries MUST NOT persist across reboots for any
device.

This table is deprecated. Instead, use the DiffServ MIB

from RFC 3289."
::= { docsDevFilter 5 }

docsDevFilterPolicyEntry OBJECT-TYPE
SYNTAX DocsDevFilterPolicyEntry
MAX-ACCESS not-accessible
STATUS deprecated
DESCRIPTION
"An entry in the docsDevFilterPolicyTable. Entries are
created by Network
Management. To create an entry,
docsDevFilterPolicyId MUST be specified."
INDEX { docsDevFilterPolicyIndex }
::= { docsDevFilterPolicyTable 1 }

DocsDevFilterPolicyEntry ::= SEQUENCE {
docsDevFilterPolicyIndex Integer32,
docsDevFilterPolicyId Integer32,
-- docsDevFilterPolicyType INTEGER,

```
--         docsDevFilterPolicyAction  Integer32,
           docsDevFilterPolicyStatus  RowStatus,
           docsDevFilterPolicyPtr     RowPointer
       }

docsDevFilterPolicyIndex OBJECT-TYPE
       SYNTAX      Integer32 (1..2147483647)
       MAX-ACCESS  not-accessible
       STATUS      deprecated
       DESCRIPTION "Index value for the table."
       ::= { docsDevFilterPolicyEntry 1 }

docsDevFilterPolicyId OBJECT-TYPE
       SYNTAX      Integer32 (0..2147483647)
       MAX-ACCESS  read-create
       STATUS      deprecated
       DESCRIPTION
          "Policy ID for this entry.  If a policy ID can apply
 to
           multiple rows of this table, all relevant policies are
           executed.  Policy 0 (if populated) is applied to all
           packets that do not match any of the filters.  N.B. If
           docsDevFilterIpPolicyId is set to 0, it DOES NOT match
           policy 0 of this table."
       ::= { docsDevFilterPolicyEntry 2 }

-- The following two objects were removed and never used; however,
-- to preserve OID numbering, they are simply commented out to
-- to ensure that they are not used again.
-- docsDevFilterPolicyType ::= { docsDevFilterPolicyEntry 3 }
-- docsDevFilterPolicyAction ::= { docsDevFilterPolicyEntry 4 }



docsDevFilterPolicyStatus OBJECT-TYPE
       SYNTAX      RowStatus
       MAX-ACCESS  read-create
       STATUS      deprecated
       DESCRIPTION
          "Object used to create an entry in this table.  There is
           no restriction in changing any object in a row while
           this object is set to active.
           The
 following object MUST have a valid value before this
           object can be set to active:  docsDevFilterPolicyPtr."
       ::= { docsDevFilterPolicyEntry 5 }

docsDevFilterPolicyPtr OBJECT-TYPE
```

```
    SYNTAX      RowPointer
    MAX-ACCESS  read-create
    STATUS      deprecated
    DESCRIPTION
       "This object points to a row in an applicable filter
        policy table.  Currently, the only standard policy
        table is docsDevFilterTosTable.

        Per the textual convention, this object points to the
        first accessible object in the row; e.g., to point to a
        row in docsDevFilterTosTable with an index of 21, the
        value of this object would be the object identifier
        docsDevTosStatus.21.

        Vendors are recommended to adhere to the same convention
        when adding vendor-specific policy table extensions.

        If this pointer references an empty or non-existent

       row, then no policy action is taken.

        The default upon row creation is a null pointer that
        results in no policy action being taken."
    DEFVAL { zeroDotZero }
    ::= { docsDevFilterPolicyEntry 6 }

--
-- TOS Policy action table
--

docsDevFilterTosTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF DocsDevFilterTosEntry
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
       "Table used to describe Type of Service (TOS) bits




        processing.

        This table is an adjunct to the docsDevFilterIpTable
        and the docsDevFilterPolicy table.  Entries in the
        latter table can point to specific rows in this (and
        other) tables and cause specific actions to be taken.
        This table permits the manipulation of the value of the
        Type of Service bits in the IP header of the matched
        packet as follows:
```

```
            Set the tosBits
 of the packet to
               (tosBits & docsDevFilterTosAndMask) |
               docsDevFilterTosOrMask

            This construct allows you to do a clear and set of all
            the TOS bits in a flexible manner.

            Table entries MUST NOT persist across reboots for any
            device.

            This table is deprecated.  Instead, use the DiffServ MIB
            from RFC 3289."
        ::= { docsDevFilter 6 }

docsDevFilterTosEntry OBJECT-TYPE
        SYNTAX      DocsDevFilterTosEntry
        MAX-ACCESS  not-accessible
        STATUS      deprecated
        DESCRIPTION
           "A TOS policy entry."
        INDEX { docsDevFilterTosIndex }
        ::= { docsDevFilterTosTable 1 }

DocsDevFilterTosEntry ::= SEQUENCE {
            docsDevFilterTosIndex   Integer32,
            docsDevFilterTosStatus  RowStatus,
            docsDevFilterTosAndMask OCTET STRING,
            docsDevFilterTosOrMask  OCTET STRING
        }

docsDevFilterTosIndex OBJECT-TYPE
         SYNTAX      Integer32 (1..2147483647)
        MAX-ACCESS  not-accessible
        STATUS      deprecated
        DESCRIPTION
           "The unique index for this row.  There are no ordering
            requirements for this table, and any valid index may be
            specified."



        ::= { docsDevFilterTosEntry 1 }

docsDevFilterTosStatus OBJECT-TYPE
        SYNTAX      RowStatus
        MAX-ACCESS  read-create
```

```
        STATUS      deprecated
        DESCRIPTION
            "The object used to create and delete entries in this
             table.  A row created by specifying just this object
             results in a row that specifies no change to the TOS
             bits.  A row may be created using either the
             create-and-go or create-and-wait paradigms.  There is
             no restriction on the ability to change values in this
             row while the row is active."
        ::= { docsDevFilterTosEntry 2 }

docsDevFilterTosAndMask OBJECT-TYPE
         SYNTAX      OCTET STRING (SIZE (1))
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "This value is bitwise ANDed with the matched packet's
             TOS bits."
        DEFVAL { 'ff'h }
        ::= { docsDevFilterTosEntry 3 }

docsDevFilterTosOrMask OBJECT-TYPE
        SYNTAX      OCTET STRING (SIZE (1))
        MAX-ACCESS  read-create
        STATUS      deprecated
        DESCRIPTION
            "This value is bitwise ORed with the result from the
             AND procedure (tosBits & docsDevFilterTosAndMask).
             The result then replaces the packet's TOS bits."
        DEFVAL { '00'h }
        ::= { docsDevFilterTosEntry 4 }

--
-- CPE IP Management and anti-spoofing group.  Only implemented on
-- Cable Modems.
--

docsDevCpe OBJECT IDENTIFIER ::= { docsDevMIBObjects 7 }

docsDevCpeEnroll OBJECT-TYPE
        SYNTAX      INTEGER {
            none(1),
            any(2)




        }
        MAX-ACCESS  read-write
```

```
    STATUS      current
     DESCRIPTION
        "This object controls the population of
         docsDevFilterCpeTable.
         If set to none, the filters must be set manually
         by a network management action (either configuration
         or SNMP set).
         If set to any, the CM wiretaps the packets originating
         from the ethernet and enrolls up to docsDevCpeIpMax
         addresses as based on the source IPv4 or v6 addresses of
         those packets."
     DEFVAL { any }
     ::= { docsDevCpe 1 }

docsDevCpeIpMax OBJECT-TYPE
     SYNTAX      Integer32 (-1..2147483647)
     MAX-ACCESS  read-write
     STATUS      current
     DESCRIPTION
        "This object controls the maximum number of CPEs allowed
         to be learned behind this device.  If set to zero, any
         number of CPEs may connect up to the maximum permitted
         for the device.
         If set to -1, no filtering
 is done on CPE source
         addresses, and no entries are made in the
         docsDevFilterCpeTable via learning.  If an attempt is
         made to set this to a number greater than that
         permitted for the device, it is set to that maximum."
     DEFVAL { -1 }
     ::= { docsDevCpe 2 }

docsDevCpeTable OBJECT-TYPE
     SYNTAX      SEQUENCE OF DocsDevCpeEntry
     MAX-ACCESS  not-accessible
     STATUS      deprecated
     DESCRIPTION
        "This table lists the IPv4 addresses seen (or permitted)
         as source addresses in packets originating from the
         customer interface on this device.  In addition, this
         table can be provisioned with the specific addresses
         permitted for the CPEs via the normal row creation
         mechanisms.  Table entries MUST NOT persist across
         reboots for any device.

         N.B.  Management action can add entries in this table
         and
```

in docsDevCpeIpTable past the value of

docsDevCpeIpMax. docsDevCpeIpMax ONLY restricts the ability of the CM to add learned addresses automatically.

This table is deprecated and is replaced by docsDevCpeInetTable."

::= { docsDevCpe 3 }

```
docsDevCpeEntry OBJECT-TYPE
    SYNTAX      DocsDevCpeEntry
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
       "An entry in the docsDevFilterCpeTable.  There is one
        entry for each IPv4 CPE seen or provisioned.  If
        docsDevCpeIpMax is set to -1, this table is ignored;
        otherwise, upon receipt of an IP packet from the
        customer interface of the CM, the source IP address is
        checked against this table.  If the address is in the
        table, packet processing continues.  If the address is
        not in the table but docsDevCpeEnroll is set to any
```

and the sum of the table sizes of docsDevCpeTable and docsDevCpeInetTable is less than docsDevCpeIpMax, the address is added to the table, and packet processing continues. Otherwise, the packet is dropped.

The filtering actions specified by this table occur after any LLC filtering (docsDevFilterLLCTable), but prior to any IP filtering (docsDevFilterIpTable, docsDevNmAccessTable)."

```
    INDEX   { docsDevCpeIp }
    ::= {docsDevCpeTable 1 }

DocsDevCpeEntry ::= SEQUENCE {
        docsDevCpeIp      IpAddress,
        docsDevCpeSource  INTEGER,
        docsDevCpeStatus  RowStatus
    }

docsDevCpeIp OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  not-accessible
    STATUS      deprecated
```

```
        DESCRIPTION
            "The IPv4 address to which this entry applies.

             N.B.  Attempts to set all zeros or all ones address
             values MUST
    be rejected."



        ::= { docsDevCpeEntry 1 }

    docsDevCpeSource OBJECT-TYPE
        SYNTAX      INTEGER {
            other(1),
            manual(2),
            learned(3)
        }

        MAX-ACCESS  read-only
        STATUS      deprecated
        DESCRIPTION
            "This object describes how this entry was created.  If
             the value is manual(2), this row was created by a
             network management action (either configuration or
             SNMP set).  If set to learned(3), then it was found via
             looking at the source IPv4 address of a received packet.
             The value other(1) is used for any entries that do not
             meet manual(2) or learned(3) criteria."
        ::= { docsDevCpeEntry 2 }

    docsDevCpeStatus OBJECT-TYPE
        SYNTAX  RowStatus
        MAX-ACCESS  read-create
        STATUS  deprecated
        DESCRIPTION
            "Standard object to manipulate rows.  To create a row in
             this table, one only needs
    to specify this object.
             Management stations SHOULD use the create-and-go
             mechanism for creating rows in this table."
        ::= { docsDevCpeEntry 3 }

    --
    -- Internet CPE Management and anti spoofing group, for support of
    -- non-IPv4 CPEs.
    --

    docsDevCpeInetTable OBJECT-TYPE
```

```
    SYNTAX      SEQUENCE OF DocsDevCpeInetEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
       "This table lists the IP addresses seen (or permitted) as
        source addresses in packets originating from the
        customer interface on this device.  In addition, this
        table can be provisioned with the specific addresses
        permitted for the CPEs via the normal row creation
        mechanisms.



        N.B.  Management action can add entries in this table
        and in docsDevCpeIpTable past the value of
        docsDevCpeIpMax.  docsDevCpeIpMax ONLY restricts the

 ability of the CM to add learned addresses
        automatically.

        Table entries MUST NOT persist across reboots for any
        device.

        This table exactly mirrors docsDevCpeTable and applies
        to IPv4 and IPv6 addresses."
    ::= { docsDevCpe 4 }

docsDevCpeInetEntry OBJECT-TYPE
    SYNTAX      DocsDevCpeInetEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
       "An entry in the docsDevFilterCpeInetTable.  There is one
        entry for each IP CPE seen or provisioned.  If
        docsDevCpeIpMax is set to -1, this table is ignored;
        otherwise, upon receipt of an IP packet from the
        customer interface of the CM, the source IP address is
        checked against this table.  If the address is in the
        table, packet processing continues.  If the address is
        not in the table but docsDevCpeEnroll is set to any and
        the
 sum of the table sizes for docsDevCpeTable and
        docsDevCpeInetTable is less than docsDevCpeIpMax, the
        address is added to the table, and packet processing
        continues.  Otherwise, the packet is dropped.

        The filtering actions specified by this table occur
        after any LLC filtering (docsDevFilterLLCTable), but
```

```
            prior to any IP filtering (docsDevFilterIpTable,
            docsDevNmAccessTable).

            When an agent (cable modem) restarts, then all
            dynamically created rows are lost."
        INDEX   { docsDevCpeInetType, docsDevCpeInetAddr }
        ::= { docsDevCpeInetTable 1 }

DocsDevCpeInetEntry ::= SEQUENCE {
            docsDevCpeInetType      InetAddressType,
            docsDevCpeInetAddr      InetAddress,
            docsDevCpeInetSource    INTEGER,
            docsDevCpeInetRowStatus RowStatus
        }




docsDevCpeInetType OBJECT-TYPE
        SYNTAX      InetAddressType
        MAX-ACCESS
  not-accessible
        STATUS      current
        DESCRIPTION
            "The type of internet address of docsDevCpeInetAddr."
        ::= { docsDevCpeInetEntry 1 }

docsDevCpeInetAddr OBJECT-TYPE
        SYNTAX      InetAddress
        MAX-ACCESS  not-accessible
        STATUS      current
        DESCRIPTION
            "The Internet address to which this entry applies.

            Implementors need to be aware that if the size of
            docsDevCpeInetAddr exceeds 114 octets OIDs of
            instances of columns in this row will have more
            than 128 sub-identifiers and cannot be accessed
            using SNMPv1, SNMPv2c, or SNMPv3.  Only unicast
            address are allowed for this object."
        ::= { docsDevCpeInetEntry 2 }

docsDevCpeInetSource OBJECT-TYPE
        SYNTAX      INTEGER {
            manual(2),
            learned(3)
        }
        MAX-ACCESS  read-only
```

```
        STATUS      current
        DESCRIPTION
            "This object
    describes how this entry was created.  If
            the value is manual(2), this row was created by a
            network management action (either configuration or
            SNMP set).  If set to learned(3), then it was found
            via looking at the source IP address of a received
            packet."
        ::= { docsDevCpeInetEntry 3 }

    docsDevCpeInetRowStatus OBJECT-TYPE
        SYNTAX  RowStatus
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "Standard object to manipulate rows.  To create a row in
            this table, one only needs to specify this object.
            Management stations SHOULD use the create-and-go
            mechanism for creating rows in this table."



        ::= { docsDevCpeInetEntry 4 }


    --
    -- Placeholder for notifications/traps.
    --

    -- erroneous, DO NOT USE docsDevNotification
    docsDevNotification OBJECT IDENTIFIER   ::= { docsDev 2 }
    -- erroneous, DO NOT USE docsDevNotification

    docsDevNotifications
     OBJECT IDENTIFIER   ::= { docsDev 0 }



    --
    -- RFC 2669 Conformance definitions
    --

    docsDevConformance  OBJECT IDENTIFIER   ::= { docsDev 3 }
    docsDevGroups       OBJECT IDENTIFIER   ::= { docsDevConformance 1 }
    docsDevCompliances  OBJECT IDENTIFIER   ::= { docsDevConformance 2 }

    docsDevBasicCompliance MODULE-COMPLIANCE
        STATUS  deprecated
```

```
        DESCRIPTION
            "The RFC 2669 compliance statement for MCNS/DOCSIS
             Cable Modems and Cable Modem Termination Systems."

MODULE  -- docsDev

-- conditionally mandatory groups

GROUP docsDevBaseGroup
        DESCRIPTION
            "Mandatory in Cable Modems, optional in Cable Modem
             Termination Systems."

GROUP docsDevEventGroup
        DESCRIPTION
            "Mandatory in Cable Modems, optional in Cable Modem
             Termination Systems."

GROUP docsDevFilterGroup
        DESCRIPTION
            "Mandatory in Cable Modems, optional in Cable Modem
             Termination Systems."

GROUP
 docsDevNmAccessGroup



        DESCRIPTION
            "This group is only implemented in devices that do not
             implement the SNMPv3 User Security Model.  It SHOULD NOT
             be implemented by devices that conform to SNMPv3.

             For devices that do not implement SNMPv3 or later, this
             group is Mandatory in Cable Modems and is optional
             in Cable Modem Termination Systems."

GROUP docsDevServerGroup
        DESCRIPTION
            "This group is implemented only in Cable Modems, and is
             not implemented in Cable Modem Termination Systems."

GROUP docsDevSoftwareGroup
        DESCRIPTION
            "This group is Mandatory in Cable Modems and optional in
             Cable Modem Termination Systems."

GROUP docsDevCpeGroup
```

```
        DESCRIPTION
            "This group is Mandatory in Cable Modems, and is
             not implemented in Cable Modem Termination Systems."

    OBJECT docsDevSTPControl
        MIN-ACCESS read-only
         DESCRIPTION
            "It is compliant to implement this object as read-only.
             Devices need only support noStFilterBpdu(2)."

    OBJECT docsDevNmAccessIp
        DESCRIPTION
            "It is compliant to recognize the IP address
             255.255.255.255 as referring to any NMS."

    OBJECT docsDevEvReporting
         MIN-ACCESS read-only
         DESCRIPTION
            "It is compliant to implement this object as read-only.
             Devices need only support local(0).  An agent need not
             enforce that trap or syslog logging be accompanied
             by local(0) or localVolatile(3) logging."
        ::= { docsDevCompliances 1 }

    docsDevBaseGroup OBJECT-GROUP
        OBJECTS {
            docsDevRole,
            docsDevDateTime,




            docsDevResetNow,
            docsDevSerialNumber,
            docsDevSTPControl
        }
        STATUS      current
        DESCRIPTION
            "A collection of objects providing device status
     and
            control."
        ::= { docsDevGroups 1 }

    docsDevNmAccessGroup OBJECT-GROUP
        OBJECTS {
            docsDevNmAccessIp,
            docsDevNmAccessIpMask,
            docsDevNmAccessCommunity,
            docsDevNmAccessControl,
```

```
        docsDevNmAccessInterfaces,
        docsDevNmAccessStatus
    }
    STATUS      deprecated
    DESCRIPTION
        "A collection of objects for controlling access to SNMP
        objects on cable devices.

        This group has been deprecated because all the
        objects have been deprecated in favor of SNMPv3 and
        Coexistence MIBs."
    ::= { docsDevGroups 2 }

docsDevSoftwareGroup OBJECT-GROUP
    OBJECTS {
        docsDevSwServer,
        docsDevSwFilename,
        docsDevSwAdminStatus,
        docsDevSwOperStatus,
        docsDevSwCurrentVers
    }
    STATUS      deprecated
    DESCRIPTION
        "A collection of objects
 for controlling software
        downloads.

        This group has been deprecated and replaced by
        docsDevSoftwareGroupV2.  Object docsDevSwServer
        has been replaced by docsDevSwServerAddressType
        and docsDevSwServerAddress, and
        docsDevSwServerTransportProtocol has been added to
        support TFTP and HTTP firmware downloads."



    ::= { docsDevGroups 3 }

docsDevServerGroup OBJECT-GROUP
    OBJECTS {
        docsDevServerBootState,
        docsDevServerDhcp,
        docsDevServerTime,
        docsDevServerTftp,
        docsDevServerConfigFile
    }
    STATUS      deprecated
    DESCRIPTION
```

"A collection of objects providing status about server
provisioning.

This group has been deprecated and replaced by
docsDevServerGroupV2. The objects docsDevServerDhcp,
docsDevServerTime, and docsDevServerTftp have

been replaced by docsDevServerDhcpAddressType,
docsDevServerDhcpAddress, docsDevServerTimeAddressType,
docsDevServerTimeAddress,
docsDevServerConfigTftpAddressType, and
docsDevServerConfigTftpAddress."
::= { docsDevGroups 4 }

docsDevEventGroup OBJECT-GROUP
OBJECTS {
docsDevEvControl,
docsDevEvSyslog,
docsDevEvThrottleAdminStatus,
docsDevEvThrottleInhibited,
docsDevEvThrottleThreshold,
docsDevEvThrottleInterval,
docsDevEvReporting,
docsDevEvFirstTime,
docsDevEvLastTime,
docsDevEvCounts,
docsDevEvLevel,
docsDevEvId,
docsDevEvText
}
STATUS deprecated
DESCRIPTION
"A collection of objects used to control and monitor
events.

This group has been deprecated and replaced by
docsDevEventGroupV2.
The object docsDevEvSyslog has

been replaced by docsDevEvSyslogAddressType and
docsDevEvSyslogAddress, and docsDevEvThrottleInhibited
has been replaced by
docsDevEvThrottleThresholdExceeded."
::= { docsDevGroups 5 }

docsDevFilterGroup OBJECT-GROUP

```
    OBJECTS {
       docsDevFilterLLCUnmatchedAction,
       docsDevFilterIpDefault,
       docsDevFilterLLCStatus,
       docsDevFilterLLCIfIndex,
       docsDevFilterLLCProtocolType,
       docsDevFilterLLCProtocol,
       docsDevFilterLLCMatches,
       docsDevFilterIpControl,
       docsDevFilterIpIfIndex,
       docsDevFilterIpStatus,
       docsDevFilterIpDirection,
       docsDevFilterIpBroadcast,
       docsDevFilterIpSaddr,
       docsDevFilterIpSmask,
       docsDevFilterIpDaddr,
       docsDevFilterIpDmask,
       docsDevFilterIpProtocol,
       docsDevFilterIpSourcePortLow,
        docsDevFilterIpSourcePortHigh,
       docsDevFilterIpDestPortLow,
       docsDevFilterIpDestPortHigh,
       docsDevFilterIpMatches,
       docsDevFilterIpTos,
       docsDevFilterIpTosMask,
       docsDevFilterIpContinue,
       docsDevFilterIpPolicyId,
       docsDevFilterPolicyId,
       docsDevFilterPolicyStatus,
       docsDevFilterPolicyPtr,
       docsDevFilterTosStatus,
       docsDevFilterTosAndMask,
       docsDevFilterTosOrMask
    }
    STATUS      deprecated
    DESCRIPTION
       "A collection of objects to specify filters at the link
        layer and IPv4 layer.

        This group has been deprecated and replaced by various
        groups from the DiffServ MIB."



    ::= { docsDevGroups 6 }

docsDevCpeGroup OBJECT-GROUP
    OBJECTS {
```

```
        docsDevCpeEnroll,
        docsDevCpeIpMax,
        docsDevCpeSource,
        docsDevCpeStatus
       }
      STATUS      deprecated
      DESCRIPTION
         "A collection of objects used to control the number
          and specific values of IPv4 addresses allowed for
          associated Customer Premises Equipment (CPE).

          This group has been deprecated and replaced by
          docsDevInetCpeGroup.  The object docsDevCpeSource has
          been replaced by docsDevCpeInetSource, and
          docsDevCpeStatus has been replaced by
          docsDevCpeInetRowStatus."
      ::= { docsDevGroups 7 }

--
-- RFC 4639 Conformance definitions
--

docsDevGroupsV2       OBJECT IDENTIFIER  ::= { docsDevConformance 3 }
docsDevCompliancesV2  OBJECT IDENTIFIER  ::= { docsDevConformance 4 }

docsDevCmCompliance MODULE-COMPLIANCE
       STATUS  current
       DESCRIPTION
          "The compliance statement for DOCSIS Cable Modems.

           This compliance statement applies to implementations
           of DOCSIS versions that are not
 IPv6 capable."

MODULE DIFFSERV-MIB -- RFC 3289

MANDATORY-GROUPS {
        diffServMIBDataPathGroup,
        diffServMIBClfrGroup,
        diffServMIBClfrElementGroup,
        diffServMIBMultiFieldClfrGroup,
        diffServMIBActionGroup,
        diffServMIBDscpMarkActGroup,
        diffServMIBCounterGroup,
        diffServMIBAlgDropGroup
```

```
        }

OBJECT diffServDataPathStatus  -- same as RFC 3289
      SYNTAX RowStatus { active(1) }
      WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
      DESCRIPTION
         "Support for createAndWait and notInService is not
          required."

OBJECT diffServClfrStatus  -- same as RFC 3289
      SYNTAX RowStatus { active(1) }
      WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
      DESCRIPTION
         "Support for createAndWait and notInService is not
          required."

OBJECT diffServClfrElementStatus  -- same as RFC 3289
      SYNTAX RowStatus { active(1)
 }
      WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
      DESCRIPTION
         "Support for createAndWait and notInService is not
          required."

OBJECT diffServMultiFieldClfrAddrType
      SYNTAX  InetAddressType { ipv4(1) }
      DESCRIPTION
         "An implementation is only required to support IPv4
          addresses."

OBJECT diffServMultiFieldClfrSrcAddr
      SYNTAX  InetAddress (SIZE(4))
      DESCRIPTION
         "An implementation is only required to support IPv4
          addresses."

OBJECT diffServMultiFieldClfrDstAddr
      SYNTAX  InetAddress (SIZE(4))
      DESCRIPTION
         "An implementation is only required to support IPv4
          addresses."

OBJECT diffServAlgDropStatus  -- same as RFC 3289
      SYNTAX RowStatus { active(1) }
      WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
      DESCRIPTION
         "Support for createAndWait and notInService is not
```

required."

OBJECT diffServDataPathStorage
SYNTAX StorageType { volatile(2) }
DESCRIPTION
"An implementation is only required to support volatile storage."

OBJECT diffServClfrStorage
SYNTAX StorageType { volatile(2) }
DESCRIPTION
"An implementation is only required to support volatile storage."

OBJECT diffServClfrElementStorage
SYNTAX StorageType { volatile(2) }
DESCRIPTION
"An implementation is only required to support volatile storage."

OBJECT diffServMultiFieldClfrStorage
SYNTAX StorageType { volatile(2) }
DESCRIPTION
"An implementation is only required to support volatile storage."

OBJECT diffServActionStorage
SYNTAX StorageType { volatile(2) }
DESCRIPTION
"An implementation is only required to support volatile storage."

OBJECT diffServCountActStorage
SYNTAX StorageType { volatile(2) }
DESCRIPTION
"An implementation is only required to support volatile storage."

OBJECT diffServAlgDropStorage
SYNTAX StorageType { volatile(2) }
DESCRIPTION
"An implementation is only required to support volatile storage."

OBJECT diffServAlgDropType

```
        SYNTAX  INTEGER { alwaysDrop(5) }
        DESCRIPTION
            "This object is only used to provide packet
             filtering.  Implementations need not support other
             values of this enumeration."



MODULE  -- docsDev

MANDATORY-GROUPS {
          docsDevBaseGroup,
          docsDevBaseIgmpGroup,
          docsDevBaseMaxCpeGroup,
          docsDevSoftwareGroupV2,
          docsDevServerGroupV2,
          docsDevEventGroupV2,
          docsDevFilterLLCGroup
          }

-- conditionally mandatory groups

GROUP docsDevInetCpeGroup
       DESCRIPTION
          "This group is
 optional in Cable Modems."

OBJECT docsDevDateTime
        MIN-ACCESS read-only
        DESCRIPTION
           "It is compliant to implement this object as read-only."

OBJECT docsDevSTPControl
        SYNTAX INTEGER { noStFilterBpdu(2) }
        MIN-ACCESS read-only
        DESCRIPTION
           "It is compliant to implement this object as read-only.
            Devices need only support noStFilterBpdu(2)."

OBJECT docsDevIgmpModeControl
        SYNTAX INTEGER { passive(1) }
        MIN-ACCESS read-only
        DESCRIPTION
           "It is compliant to implement this object as read-only.
            Devices need only support passive(1)."

OBJECT docsDevSwServerAddressType
        SYNTAX InetAddressType { ipv4(1) }
```

DESCRIPTION
"An implementation is only required to support IPv4
addresses."

OBJECT docsDevSwServerAddress
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to
support IPv4
addresses."

OBJECT docsDevServerDhcpAddressType
SYNTAX InetAddressType { ipv4(1) }
DESCRIPTION
"An implementation is only required to support IPv4
addresses."

OBJECT docsDevServerDhcpAddress
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4
addresses."

OBJECT docsDevServerTimeAddressType
SYNTAX InetAddressType { ipv4(1) }
DESCRIPTION
"An implementation is only required to support IPv4
addresses."

OBJECT docsDevServerTimeAddress
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4
addresses."

OBJECT docsDevServerConfigTftpAddressType
SYNTAX InetAddressType { ipv4(1) }
DESCRIPTION
"An implementation is only required to support IPv4
addresses."

OBJECT
docsDevServerConfigTftpAddress
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4

```
            addresses."

OBJECT docsDevEvReporting
        MIN-ACCESS read-only
        DESCRIPTION
            "It is compliant to implement this object as read-only.
             Devices need only support local(0)."

OBJECT docsDevEvSyslogAddressType
        SYNTAX InetAddressType { ipv4(1) }
        DESCRIPTION
            "An implementation is only required to support IPv4
             addresses."




OBJECT docsDevEvSyslogAddress
        SYNTAX  InetAddress (SIZE(4))
        DESCRIPTION
            "An implementation is only required to support IPv4
             addresses."

OBJECT docsDevSwServerTransportProtocol
        SYNTAX INTEGER { tftp(1) }
        DESCRIPTION
            "An implementation is only required to support TFTP
             software image downloads."

        ::= { docsDevCompliancesV2
 1 }

docsDevCmtsCompliance MODULE-COMPLIANCE
        STATUS  current
        DESCRIPTION
            "The compliance statement for DOCSIS Cable Modem
             Termination Systems.

             This compliance statement applies to implementations
             of DOCSIS versions that are not IPv6 capable."

MODULE  -- docsDev

-- conditionally mandatory groups

GROUP docsDevBaseGroup
       DESCRIPTION
          "Optional in Cable Modem Termination Systems."
```

```
GROUP docsDevBaseIgmpGroup
      DESCRIPTION
         "Optional in Cable Modem Termination Systems."

GROUP docsDevBaseMaxCpeGroup
      DESCRIPTION
         "This group MUST NOT be implemented in Cable Modem
          Termination Systems."

GROUP docsDevSoftwareGroupV2
      DESCRIPTION
         "Optional in Cable Modem Termination Systems."

GROUP docsDevServerGroupV2
      DESCRIPTION
         "This group MUST NOT be implemented in Cable Modem
          Termination Systems."



GROUP docsDevEventGroupV2
       DESCRIPTION
         "Optional in Cable Modem Termination Systems."

GROUP docsDevFilterLLCGroup
      DESCRIPTION
         "This group MUST NOT be implemented in Cable Modem
          Termination Systems.  See the Subscriber Management
          MIB for similar CMTS capability."

GROUP docsDevInetCpeGroup
      DESCRIPTION
         "This group MUST NOT be implemented in Cable Modem
          Termination Systems.  See the Subscriber Management
          MIB for similar CMTS capability."

OBJECT docsDevDateTime
       MIN-ACCESS read-only
       DESCRIPTION
         "It is compliant to implement this object as read-only."

OBJECT docsDevSTPControl
       SYNTAX INTEGER { noStFilterBpdu(2) }
       MIN-ACCESS read-only
       DESCRIPTION
         "It is compliant to implement this object as read-only.
          Devices need only support noStFilterBpdu(2)."
```

```
OBJECT docsDevIgmpModeControl
      SYNTAX INTEGER { passive(1)
 }
      MIN-ACCESS read-only
      DESCRIPTION
         "It is compliant to implement this object as read-only.
          Devices need only support passive(1)."

OBJECT docsDevSwServerAddressType
      SYNTAX InetAddressType { ipv4(1) }
      DESCRIPTION
         "An implementation is only required to support IPv4
          addresses."

OBJECT docsDevSwServerAddress
      SYNTAX  InetAddress (SIZE(4))
      DESCRIPTION
         "An implementation is only required to support IPv4
          addresses."

OBJECT docsDevEvReporting



      MIN-ACCESS read-only
      DESCRIPTION
         "It is compliant to implement this object as read-only.
          Devices need only support local(0)."

OBJECT docsDevEvSyslogAddressType
      SYNTAX InetAddressType { ipv4(1) }
      DESCRIPTION
         "An implementation is only required to support IPv4
          addresses."

OBJECT docsDevEvSyslogAddress
      SYNTAX  InetAddress
 (SIZE(4))
      DESCRIPTION
         "An implementation is only required to support IPv4
          addresses."

OBJECT docsDevSwServerTransportProtocol
      SYNTAX INTEGER { tftp(1) }
      DESCRIPTION
         "An implementation is only required to support TFTP
          software image downloads."
```

```
        ::= { docsDevCompliancesV2 2 }

docsDevBaseIgmpGroup OBJECT-GROUP
      OBJECTS {
          docsDevIgmpModeControl
      }
      STATUS      current
      DESCRIPTION
         "An object providing cable device IGMP status and
          control."
      ::= { docsDevGroupsV2 1 }

docsDevBaseMaxCpeGroup OBJECT-GROUP
      OBJECTS {
          docsDevMaxCpe
      }
      STATUS      current
      DESCRIPTION
         "An object providing management of the maximum number of
          CPEs permitted access through a cable modem."
      ::= { docsDevGroupsV2 2 }

docsDevNmAccessExtGroup OBJECT-GROUP
      OBJECTS {

        docsDevNmAccessTrapVersion




      }
      STATUS      deprecated
      DESCRIPTION
         "An object, in addition to the objects in
          docsDevNmAccessGroup, for controlling access to
          SNMP objects on cable devices.

          This group is included in this MIB due to existing
          implementations of docsDevNmAccessTrapVersion in
          DOCSIS cable modems.

          This group has been deprecated because the object has
          been deprecated in favor of SNMPv3 and Coexistence
          MIBs."
      ::= { docsDevGroupsV2 3 }

docsDevSoftwareGroupV2 OBJECT-GROUP
      OBJECTS {
```

```
            docsDevSwFilename,
            docsDevSwAdminStatus,
            docsDevSwOperStatus,
            docsDevSwCurrentVers,
            docsDevSwServerAddressType,
            docsDevSwServerAddress,
            docsDevSwServerTransportProtocol
        }
        STATUS      current
        DESCRIPTION
            "A collection of
    objects for controlling software
             downloads.  This group replaces docsDevSoftwareGroup."
        ::= { docsDevGroupsV2 4 }

    docsDevServerGroupV2 OBJECT-GROUP
        OBJECTS {
            docsDevServerBootState,
            docsDevServerDhcpAddressType,
            docsDevServerDhcpAddress,
            docsDevServerTimeAddressType,
            docsDevServerTimeAddress,
            docsDevServerConfigTftpAddressType,
            docsDevServerConfigTftpAddress,
            docsDevServerConfigFile
        }
        STATUS      current
        DESCRIPTION
            "A collection of objects providing status about server
             provisioning.  This group replaces docsDevServerGroup."
        ::= { docsDevGroupsV2 5 }



    docsDevEventGroupV2 OBJECT-GROUP
        OBJECTS {
            docsDevEvControl,
            docsDevEvThrottleAdminStatus,
            docsDevEvThrottleThreshold,
            docsDevEvThrottleInterval,
            docsDevEvReporting,
            docsDevEvFirstTime,
             docsDevEvLastTime,
            docsDevEvCounts,
            docsDevEvLevel,
            docsDevEvId,
            docsDevEvText,
            docsDevEvSyslogAddressType,
```

```
        docsDevEvSyslogAddress,
        docsDevEvThrottleThresholdExceeded
    }
    STATUS      current
    DESCRIPTION
        "A collection of objects used to control and monitor
         events.  This group replaces docsDevEventGroup.
         The event reporting mechanism, and more specifically
         docsDevEvReporting, can be used to take advantage of
         the event reporting features of RFC3413 and RFC3014."
    ::= { docsDevGroupsV2 6 }

docsDevFilterLLCGroup OBJECT-GROUP
    OBJECTS {
        docsDevFilterLLCUnmatchedAction,
        docsDevFilterLLCStatus,
        docsDevFilterLLCIfIndex,
        docsDevFilterLLCProtocolType,
        docsDevFilterLLCProtocol,
        docsDevFilterLLCMatches
    }
    STATUS
    current
    DESCRIPTION
        "A collection of objects to specify link layer filters."
    ::= { docsDevGroupsV2 7 }

docsDevInetCpeGroup OBJECT-GROUP
    OBJECTS {
      docsDevCpeEnroll,
      docsDevCpeIpMax,
      docsDevCpeInetSource,
      docsDevCpeInetRowStatus
    }
    STATUS     current



    DESCRIPTION
        "A collection of objects used to control the number
         and specific values of Internet (e.g., IPv4 and IPv6)
         addresses allowed for associated Customer Premises
         Equipment (CPE)."
    ::= { docsDevGroupsV2 8 }

END
```

Found in path(s):

* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/DOCS-CABLE-DEVICE-MIB
No license file was found, but licenses were detected in source scan.

```
IPSEC-SPD-MIB DEFINITIONS ::= BEGIN

IMPORTS
  MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE, Integer32,
  Unsigned32, mib-2           FROM SNMPv2-SMI
                              -- [RFC2578]

  TEXTUAL-CONVENTION, RowStatus, TruthValue,
  TimeStamp, StorageType, VariablePointer
                              FROM SNMPv2-TC
                              -- [RFC2579]




  MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
                              FROM SNMPv2-CONF
                              -- [RFC2580]

  InterfaceIndex
                              FROM IF-MIB
                              -- [RFC2863]

  diffServMIBMultiFieldClfrGroup, IfDirection,
  diffServMultiFieldClfrNextFree
                              FROM DIFFSERV-MIB
                              -- [RFC3289]

  InetAddressType, InetAddress
                               FROM INET-ADDRESS-MIB
                              -- [RFC4001]

  SnmpAdminString                   FROM SNMP-FRAMEWORK-MIB
                              -- [RFC3411]

  ;

--
-- module identity
--

spdMIB MODULE-IDENTITY
  LAST-UPDATED "200702070000Z"    -- 7 February 2007
  ORGANIZATION "IETF IP Security Policy Working Group"
  CONTACT-INFO "Michael Baer
```

P.O. Box 72682
Davis, CA 95617
Phone: +1 530 902 3131
Email: baerm@tislabs.com

Ricky Charlet
Email: rcharlet@alumni.calpoly.edu

Wes Hardaker
Sparta, Inc.
P.O. Box 382
Davis, CA 95617
Phone: +1 530 792 1913
Email: hardaker@tislabs.com

Robert Story
Revelstone Software
PO Box 1812

Tucker, GA 30085
Phone: +1 770 617 3722
Email: rstory@ipsp.revelstone.com

Cliff Wang
ARO
4300 S. Miami Blvd.
Durham, NC 27703
E-Mail: cliffwangmail@yahoo.com"

```
  DESCRIPTION
   "This MIB module defines configuration objects for managing
   IPsec Security Policies.  In general, this MIB can be
   implemented anywhere IPsec security services exist (e.g.,
   bump-in-the-wire, host, gateway, firewall, router, etc.).

   Copyright (C) The IETF Trust (2007).  This version of
   this MIB module is part of RFC 4807; see the RFC itself for
   full legal notices."

-- Revision History

  REVISION     "200702070000Z"    -- 7 February 2007
  DESCRIPTION  "Initial version, published as RFC 4807."

  ::= { mib-2 153 }
```

```
--
-- groups of related objects
--

spdConfigObjects        OBJECT IDENTIFIER
   ::= { spdMIB 1 }
spdNotificationObjects
  OBJECT IDENTIFIER
   ::= { spdMIB 2 }
spdConformanceObjects    OBJECT IDENTIFIER
   ::= { spdMIB 3 }
spdActions              OBJECT IDENTIFIER
   ::= { spdMIB 4 }

--
-- Textual Conventions
--

SpdBooleanOperator ::= TEXTUAL-CONVENTION
  STATUS   current
  DESCRIPTION
     "The SpdBooleanOperator operator is used to specify
      whether sub-components in a decision-making process are




      ANDed or ORed together to decide if the resulting
      expression is true or false."
  SYNTAX      INTEGER { or(1), and(2) }

SpdAdminStatus ::= TEXTUAL-CONVENTION
  STATUS   current
  DESCRIPTION
     "The SpdAdminStatus is used to specify the administrative
      status of an object.  Objects that are disabled MUST NOT
      be used by the packet processing engine."
  SYNTAX      INTEGER { enabled(1), disabled(2) }

SpdIPPacketLogging ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "d"
  STATUS   current
  DESCRIPTION
     "SpdIPPacketLogging specifies
 whether an audit message
      SHOULD be logged if a packet is passed through a Security
      Association (SA) and if some of that packet is included in
      the log event.  A value of '-1' indicates no logging.  A
      value of '0' or greater indicates that logging SHOULD be
```

done and indicates the number of bytes starting at the
beginning of the packet to place in the log. Values greater
than the size of the packet being processed indicate that
the entire packet SHOULD be sent.

Examples:
'-1' no logging
'0' log but do not include any of the packet in the log
'20' log and include the first 20 bytes of the packet
in the log."

SYNTAX Integer32 (-1..65535)

SpdTimePeriod ::= TEXTUAL-CONVENTION
DISPLAY-HINT "31t"
STATUS current
DESCRIPTION
"This property identifies an overall range of calendar dates
and time. In a boolean context, a value
within this time
range, inclusive, is considered true.

This information is encoded as an octet string using
the UTF-8 transformation format described in STD 63,
RFC 3629.

It uses the format suggested in RFC 3060. An octet string

represents a start date and time and an end date and time.
For example:

yyyymmddThhmmss/yyyymmddThhmmss

Where: yyyy = year mm = month dd = day
hh = hour mm = minute ss = second

The first 'yyyymmddThhmmss' sub-string indicates the start
date and time. The second 'yyyymmddThhmmss' sub-string
indicates the end date and time. The character 'T' within
these sub-strings indicates the beginning of the time
portion of each sub-string. The solidus character '/'
separates the start from the end date and time. The end
date and time MUST be subsequent to the start date and

```
time.

        There are also two allowed substitutes for a
        'yyyymmddThhmmss' sub-string: one for the start date and
        time, and one for the end date and time.

        If the start date and time are replaced with the string
        'THISANDPRIOR', this sub-string would indicate the current
        date and time and the previous dates and time.

        If the end date and time are replaced with the string
        'THISANDFUTURE', this sub-string would indicate the current
        date and time and the subsequent dates and time.

        Any of the following SHOULD be considered a
        'wrongValue' error:
        - Setting a value with the end date and time earlier than
          or equal to the start date and time.
        - Setting the start date and time to 'THISANDFUTURE'.
        - Setting the end date and time to 'THISANDPRIOR'."
    REFERENCE "RFC 3060, 3269"
    SYNTAX      OCTET STRING (SIZE (0..31))
--
-- Policy group definitions
--

spdLocalConfigObjects
 OBJECT IDENTIFIER
    ::= { spdConfigObjects 1 }

spdIngressPolicyGroupName OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(0..32))
    MAX-ACCESS  read-write
    STATUS      current



    DESCRIPTION
        "This object indicates the global system policy group that
        is to be applied on ingress packets (i.e., arriving at an
        interface from a network) when a given endpoint does not
        contain a policy definition in the spdEndpointToGroupTable.
        Its value can be used as an index into the
        spdGroupContentsTable to retrieve a list of policies.  A
        zero length string indicates that no system-wide policy exists
        and the default policy of 'drop' SHOULD be executed for
        ingress packets until one is imposed by either this object
        or by the endpoint processing a given packet.
```

```
      This object MUST be persistent"
  DEFVAL { "" }
  ::= { spdLocalConfigObjects 1 }

spdEgressPolicyGroupName OBJECT-TYPE
  SYNTAX
   SnmpAdminString (SIZE(0..32))
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     "This object indicates the policy group containing the
      global system policy that is to be applied on egress
      packets (i.e., packets leaving an interface and entering a
      network) when a given endpoint does not contain a policy
      definition in the spdEndpointToGroupTable.  Its value can
      be used as an index into the spdGroupContentsTable to
      retrieve a list of policies.  A zero length string
      indicates that no system-wide policy exists and the default
      policy of 'drop' SHOULD be executed for egress packets
      until one is imposed by either this object or by the
      endpoint processing a given packet.

      This object MUST be persistent"
  DEFVAL { "" }
  ::= { spdLocalConfigObjects 2 }


spdEndpointToGroupTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SpdEndpointToGroupEntry
  MAX-ACCESS  not-accessible
   STATUS      current
  DESCRIPTION
     "This table maps policies (groupings) onto an endpoint
      (interface).  A policy group assigned to an endpoint is then
      used to control access to the network traffic passing
      through that endpoint.




      If an endpoint has been configured with a policy group and
      no rule within that policy group matches that packet, the
      default action in this case SHALL be to drop the packet.

      If no policy group has been assigned to an endpoint, then
      the policy group specified by spdIngressPolicyGroupName MUST
      be used on traffic inbound from the network through that
```

```
        endpoint, and the policy group specified by
        spdEgressPolicyGroupName MUST be used for traffic outbound
        to the network through that endpoint."
    ::= { spdConfigObjects 2 }

spdEndpointToGroupEntry OBJECT-TYPE
    SYNTAX      SpdEndpointToGroupEntry
    MAX-ACCESS  not-accessible
    STATUS
      current
    DESCRIPTION
       "A mapping assigning a policy group to an endpoint."

    INDEX { spdEndGroupDirection, spdEndGroupInterface }
    ::= { spdEndpointToGroupTable 1 }

SpdEndpointToGroupEntry ::= SEQUENCE {
    spdEndGroupDirection                IfDirection,
    spdEndGroupInterface                InterfaceIndex,
    spdEndGroupName                     SnmpAdminString,
    spdEndGroupLastChanged               TimeStamp,
    spdEndGroupStorageType               StorageType,
    spdEndGroupRowStatus                 RowStatus
}

spdEndGroupDirection OBJECT-TYPE
    SYNTAX      IfDirection
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
       "This object indicates which direction of packets crossing
        the interface are associated with which spdEndGroupName
        object.  Ingress packets, or packets into the device match
        when this value is inbound(1).  Egress packets or packets
        out
 of the device match when this value is outbound(2)."
    ::= { spdEndpointToGroupEntry 1 }

spdEndGroupInterface OBJECT-TYPE
    SYNTAX      InterfaceIndex
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION



       "This value matches the IF-MIB's ifTable's ifIndex column
        and indicates the interface associated with a given
```

```
        endpoint.  This object can be used to uniquely identify an
        endpoint that a set of policy groups are applied to."
    ::= { spdEndpointToGroupEntry 2 }

spdEndGroupName OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(1..32))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The policy group name to apply at this endpoint.  The
        value of the spdEndGroupName object is then used as an
        index into the spdGroupContentsTable to come up with a list
        of rules that MUST be applied at this endpoint."
    ::= { spdEndpointToGroupEntry 3 }

spdEndGroupLastChanged OBJECT-TYPE

    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime when this row was last modified
        or created either through SNMP SETs or by some other
        external means.

        If this row has not been modified since the last
        re-initialization of the network management subsystem, this
        object SHOULD have a zero value."
    ::= { spdEndpointToGroupEntry 4 }

spdEndGroupStorageType OBJECT-TYPE
    SYNTAX      StorageType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The storage type for this row.  Rows in this table that
        were created through an external process MAY have a storage
        type of readOnly or permanent.

        For a storage type of permanent, none of the columns have
        to be writable."
    DEFVAL { nonVolatile }
    ::= { spdEndpointToGroupEntry 5 }

spdEndGroupRowStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
```

```
    STATUS      current
    DESCRIPTION
        "This object indicates the conceptual status of this row.

        The value of this object has no effect on whether other
        objects in this conceptual row can be modified.

        This object is considered 'notReady' and MUST NOT be set to
        active until one or more active rows exist within the
        spdGroupContentsTable for the group referenced by the
        spdEndGroupName object."
    ::= { spdEndpointToGroupEntry 6 }

--
-- policy group definition table
--

spdGroupContentsTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF SpdGroupContentsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains a list of rules and/or subgroups
        contained within a given policy group.  For a given value
        of spdGroupContName, the set of rows sharing that value
        forms a 'group'.  The rows in a group MUST be processed
        according to the value of the spdGroupContPriority
 object
        in each row.  The processing MUST be executed starting with
        the lowest value of spdGroupContPriority and in ascending
        order thereafter.

        If an action is executed as the result of the processing of
        a row in a group, the processing of further rows in that
        group MUST stop.  Iterating to the next policy group row by
        finding the next largest spdGroupContPriority object SHALL
        only be done if no actions were run while processing the
        current row for a given packet."
    ::= { spdConfigObjects 3 }

spdGroupContentsEntry OBJECT-TYPE
    SYNTAX      SpdGroupContentsEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Defines a given sub-component within a policy group.  A
```

```
      sub-component is either a rule or another group as
      indicated by spdGroupContComponentType and referenced by
      spdGroupContComponentName."



  INDEX   { spdGroupContName,
 spdGroupContPriority }
  ::= { spdGroupContentsTable 1 }

SpdGroupContentsEntry ::= SEQUENCE {
  spdGroupContName                SnmpAdminString,
  spdGroupContPriority            Integer32,
  spdGroupContFilter              VariablePointer,
  spdGroupContComponentType           INTEGER,
  spdGroupContComponentName           SnmpAdminString,
  spdGroupContLastChanged         TimeStamp,
  spdGroupContStorageType         StorageType,
  spdGroupContRowStatus           RowStatus
}

spdGroupContName OBJECT-TYPE
  SYNTAX      SnmpAdminString (SIZE(1..32))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The administrative name of the group associated with this
     row.  A 'group' is formed by all the rows in this table that
     have the same value of this object."
  ::= { spdGroupContentsEntry 1 }

spdGroupContPriority OBJECT-TYPE
  SYNTAX      Integer32 (0..65535)

  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The priority (sequence number) of the sub-component in
      a group that this row represents.  This value indicates
      the order that each row of this table MUST be processed
      from low to high.  For example, a row with a priority of 0
      is processed before a row with a priority of 1, a 1 before
      a 2, etc."
  ::= { spdGroupContentsEntry 2 }

spdGroupContFilter OBJECT-TYPE
  SYNTAX      VariablePointer
  MAX-ACCESS  read-create
```

STATUS current
DESCRIPTION
"spdGroupContFilter points to a filter that is evaluated
to determine whether the spdGroupContComponentName within
this row is exercised. Managers can use this object to
classify groups of rules, or subgroups, together in order to
achieve a greater degree of control and optimization over
the execution order of the items within the group. If the

filter evaluates to false, the rule or subgroup will be
skipped and the next rule or subgroup will be evaluated
instead. This value can be used to indicate a scalar or
row in a table. When indicating a row in a table, this
value MUST point to the first column instance in that row.

An example usage of this object would be to limit a
group of rules to executing only when the IP packet
being processed is designated to be processed by IKE.
This effectively creates a group of IKE-specific rules.

The following tables and scalars can be pointed to by this
column. All but diffServMultiFieldClfrTable are defined in
this MIB:

diffServMultiFieldClfrTable
spdIpOffsetFilterTable
spdTimeFilterTable
spdCompoundFilterTable
spdTrueFilter
spdIpsoHeaderFilterTable

Implementations MAY choose to provide
support for other
filter tables or scalars.

If this column is set to a VariablePointer value, which
references a non-existent row in an otherwise supported
table, the inconsistentName exception MUST be returned. If
the table or scalar pointed to by the VariablePointer is
not supported at all, then an inconsistentValue exception
MUST be returned.

If, during packet processing, a row in this table is applied
to a packet and the value of this column in that row
references a non-existent or non-supported object, the

```
        packet MUST be dropped."
    REFERENCE "RFC 3289"
    DEFVAL { spdTrueFilterInstance }
    ::= { spdGroupContentsEntry 3 }

spdGroupContComponentType OBJECT-TYPE
    SYNTAX      INTEGER { group(1), rule(2) }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Indicates whether the spdGroupContComponentName object
        is the name of another group
 defined within the
        spdGroupContentsTable or is the name of a rule defined




        within the spdRuleDefinitionTable."
    DEFVAL { rule }
    ::= { spdGroupContentsEntry 4 }

spdGroupContComponentName OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(1..32))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The name of the policy rule or subgroup contained within
        this row, as indicated by the spdGroupContComponentType
        object."
    ::= { spdGroupContentsEntry 5 }

spdGroupContLastChanged OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of sysUpTime when this row was last modified
        or created either through SNMP SETs or by some other
        external means.

        If this row has not been modified since the last
        re-initialization of the network management subsystem,
        this object SHOULD have a zero value."
    ::= { spdGroupContentsEntry
 6 }

spdGroupContStorageType OBJECT-TYPE
    SYNTAX      StorageType
```

```
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The storage type for this row.  Rows in this table that
      were created through an external process MAY have a storage
      type of readOnly or permanent.

      For a storage type of permanent, none of the columns have
      to be writable."
  DEFVAL { nonVolatile }
  ::= { spdGroupContentsEntry 7 }

spdGroupContRowStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object indicates the conceptual status of this row.



      The value of this object has no effect on whether other
      objects in this conceptual row can be modified.

      This object MUST NOT be set to active until the row to
      which the spdGroupContComponentName points to exists and is
      active.

      If active, this object MUST remain active
 unless one of the
      following two conditions are met:

      I.  No active row in spdEndpointToGroupTable exists that
          references this row's group (i.e., indicate this row's
          spdGroupContName).

      II. Or at least one other active row in this table has a
          matching spdGroupContName.

      If neither condition is met, an attempt to set this row to
      something other than active MUST result in an
      inconsistentValue error."
  ::= { spdGroupContentsEntry 8 }



--
-- policy definition table
--
```

```
spdRuleDefinitionTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SpdRuleDefinitionEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "This table defines a rule by associating a filter
      or a set of filters to an action to be executed."
  ::= { spdConfigObjects 4 }

spdRuleDefinitionEntry OBJECT-TYPE
  SYNTAX      SpdRuleDefinitionEntry
  MAX-ACCESS  not-accessible
  STATUS      current
   DESCRIPTION
     "A row defining a particular rule definition.  A rule
      definition binds a filter pointer to an action pointer."
  INDEX   { spdRuleDefName }
  ::= { spdRuleDefinitionTable 1 }

SpdRuleDefinitionEntry ::= SEQUENCE {
  spdRuleDefName                SnmpAdminString,



  spdRuleDefDescription          SnmpAdminString,
  spdRuleDefFilter              VariablePointer,
  spdRuleDefFilterNegated        TruthValue,
  spdRuleDefAction              VariablePointer,
  spdRuleDefAdminStatus          SpdAdminStatus,
  spdRuleDefLastChanged          TimeStamp,
  spdRuleDefStorageType          StorageType,
  spdRuleDefRowStatus            RowStatus
}

spdRuleDefName OBJECT-TYPE
  SYNTAX      SnmpAdminString (SIZE(1..32))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "spdRuleDefName is the administratively assigned name of

    the rule referred to by the spdGroupContComponentName
      object."
  ::= { spdRuleDefinitionEntry 1 }

spdRuleDefDescription OBJECT-TYPE
  SYNTAX      SnmpAdminString
```

```
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "A user defined string.  This field MAY be used for
      administrative tracking purposes."
  DEFVAL { "" }
  ::= { spdRuleDefinitionEntry 2 }

spdRuleDefFilter OBJECT-TYPE
  SYNTAX      VariablePointer
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "spdRuleDefFilter points to a filter that is used to
      evaluate whether the action associated with this row is
      executed or not.  The action will only execute if the
      filter referenced by this object evaluates to TRUE after
      first applying any negation required by the
      spdRuleDefFilterNegated object.

      The following tables and scalars can be pointed to by this
      column.  All but diffServMultiFieldClfrTable
 are defined in
      this MIB.  Implementations MAY choose to provide support
      for other filter tables or scalars as well:

           diffServMultiFieldClfrTable



           spdIpOffsetFilterTable
           spdTimeFilterTable
           spdCompoundFilterTable
           spdTrueFilter

      If this column is set to a VariablePointer value, which
      references a non-existent row in an otherwise supported
      table, the inconsistentName exception MUST be returned.  If
      the table or scalar pointed to by the VariablePointer is
      not supported at all, then an inconsistentValue exception
      MUST be returned.

      If, during packet processing, this column has a value that
      references a non-existent or non-supported object, the
      packet MUST be dropped."
  REFERENCE "RFC 3289"
  ::= { spdRuleDefinitionEntry 3 }
```

```
spdRuleDefFilterNegated OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS
 read-create
  STATUS      current
  DESCRIPTION
     "spdRuleDefFilterNegated specifies whether or not the results of
      the filter referenced by the spdRuleDefFilter object is
      negated."
  DEFVAL { false }
  ::= { spdRuleDefinitionEntry 4 }

spdRuleDefAction OBJECT-TYPE
  SYNTAX      VariablePointer
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This column points to the action to be taken.  It MAY,
      but is not limited to, point to a row in one of the
      following tables:

        spdCompoundActionTable
        ipsaSaPreconfiguredActionTable
        ipiaIkeActionTable
        ipiaIpsecActionTable

      It MAY also point to one of the scalar objects beneath
      spdStaticActions.

      If this object is set to a pointer to a row in an
      unsupported (or unknown) table, an inconsistentValue



      error MUST be returned.

      If this object is set to point to a non-existent
 row in an
      otherwise supported table, an inconsistentName error MUST
      be returned.

      If, during packet processing, this column has a value that
      references a non-existent or non-supported object, the
      packet MUST be dropped."
  ::= { spdRuleDefinitionEntry 5 }

spdRuleDefAdminStatus OBJECT-TYPE
  SYNTAX      SpdAdminStatus
```

```
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "Indicates whether the current rule definition is considered
      active.  If the value is enabled, the rule MUST be evaluated
      when processing packets.  If the value is disabled, the
      packet processing MUST continue as if this rule's filter
      had effectively failed."
  DEFVAL { enabled }
  ::= { spdRuleDefinitionEntry 6 }

spdRuleDefLastChanged OBJECT-TYPE
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The value of sysUpTime when this row was last modified

     or created either through SNMP SETs or by some other
      external means.

      If this row has not been modified since the last
      re-initialization of the network management subsystem, this
      object SHOULD have a zero value."
  ::= { spdRuleDefinitionEntry 7 }

spdRuleDefStorageType OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The storage type for this row.  Rows in this table that
      were created through an external process MAY have a
      storage type of readOnly or permanent.

      For a storage type of permanent, none of the columns have




      to be writable."
  DEFVAL { nonVolatile }
  ::= { spdRuleDefinitionEntry 8 }

spdRuleDefRowStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
```

```
        "This object indicates the conceptual status of this row.

        The value of this object has no effect on
 whether other
        objects in this conceptual row can be modified.

        This object MUST NOT be set to active until the containing
        conditions, filters, and actions have been defined.  Once
        active, it MUST remain active until no active
        policyGroupContents entries are referencing it.  A failed
        attempt to do so MUST return an inconsistentValue error."
   ::= { spdRuleDefinitionEntry 9 }

--
-- Policy compound filter definition table
--

spdCompoundFilterTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF SpdCompoundFilterEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "A table defining compound filters and their associated
       parameters.  A row in this table can be pointed to by a
       spdRuleDefFilter object."
   ::= { spdConfigObjects 5 }

spdCompoundFilterEntry OBJECT-TYPE
   SYNTAX      SpdCompoundFilterEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "An entry
 in the spdCompoundFilterTable.  Each entry in this
       table represents a compound filter.  A filter defined by
       this table is considered to have a TRUE return value if and
       only if:

       spdCompFiltLogicType is AND and all of the sub-filters
       associated with it, as defined in the spdSubfiltersTable,
       are all true themselves (after applying any required



       negation, as defined by the ficFilterIsNegated object).

       spdCompFiltLogicType is OR and at least one of the
       sub-filters associated with it, as defined in the
```

```
        spdSubfiltersTable, is true itself (after applying any
        required negation, as defined by the ficFilterIsNegated
        object."
    INDEX       { spdCompFiltName }
    ::= { spdCompoundFilterTable 1 }

SpdCompoundFilterEntry ::= SEQUENCE {
    spdCompFiltName                     SnmpAdminString,
    spdCompFiltDescription              SnmpAdminString,
    spdCompFiltLogicType
                SpdBooleanOperator,
    spdCompFiltLastChanged              TimeStamp,
    spdCompFiltStorageType              StorageType,
    spdCompFiltRowStatus                RowStatus
}

spdCompFiltName OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(1..32))
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A user definable string.  This value is used as an index
        into this table."
    ::= { spdCompoundFilterEntry 1 }

spdCompFiltDescription OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "A user definable string.  This field MAY be used for
        your administrative tracking purposes."
    DEFVAL { "" }
    ::= { spdCompoundFilterEntry 2 }

spdCompFiltLogicType OBJECT-TYPE
    SYNTAX      SpdBooleanOperator
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "Indicates whether the sub-component filters of this
        compound
 filter are functionally ANDed or ORed together."
    DEFVAL { and }
    ::= { spdCompoundFilterEntry 3 }
```

```
spdCompFiltLastChanged OBJECT-TYPE
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The value of sysUpTime when this row was last modified
      or created either through SNMP SETs or by some other
      external means.

      If this row has not been modified since the last
      re-initialization of the network management subsystem, this
      object SHOULD have a zero value."
  ::= { spdCompoundFilterEntry 4 }

spdCompFiltStorageType OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The storage type for this row.  Rows in this table that
      were created through an external process MAY have a
      storage type of readOnly or permanent.

      For a storage type of permanent, none of the columns have
      to be writable."

 DEFVAL { nonVolatile }
  ::= { spdCompoundFilterEntry 5 }

spdCompFiltRowStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object indicates the conceptual status of this row.

      The value of this object has no effect on whether other
      objects in this conceptual row can be modified.

      Once active, it MUST NOT have its value changed if any
      active rows in the spdRuleDefinitionTable are currently
      pointing at this row."
  ::= { spdCompoundFilterEntry 6 }

--
-- Policy filters in a cf table
--
```

```
spdSubfiltersTable OBJECT-TYPE


  SYNTAX      SEQUENCE OF SpdSubfiltersEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "This table defines a list of filters contained within a
      given compound filter defined in the
      spdCompoundFilterTable."
  ::= { spdConfigObjects 6 }

spdSubfiltersEntry OBJECT-TYPE
  SYNTAX      SpdSubfiltersEntry
   MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "An entry in the spdSubfiltersTable.  There is an entry in
      this table for each sub-filter of all compound filters
      present in the spdCompoundFilterTable."
  INDEX       {  spdCompFiltName, spdSubFiltPriority }
  ::= { spdSubfiltersTable 1 }

SpdSubfiltersEntry ::= SEQUENCE {
  spdSubFiltPriority                Integer32,
  spdSubFiltSubfilter               VariablePointer,
  spdSubFiltSubfilterIsNegated      TruthValue,
  spdSubFiltLastChanged             TimeStamp,
  spdSubFiltStorageType             StorageType,
  spdSubFiltRowStatus               RowStatus
}

spdSubFiltPriority OBJECT-TYPE
  SYNTAX      Integer32 (0..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The priority of a given filter within a compound filter.
      The order of execution is from lowest to highest priority
       value (i.e., priority 0 before priority 1, 1 before 2,
      etc.).  Implementations MAY choose to follow this ordering,
      as set by the manager that created the rows.  This can allow
      a manager to intelligently construct filter lists such that
      faster filters are evaluated first."
  ::= { spdSubfiltersEntry 1 }
```

```
spdSubFiltSubfilter OBJECT-TYPE
  SYNTAX      VariablePointer
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION


      "The OID of the contained filter.  The value of this
       object is a VariablePointer that references the filter to
       be included in this compound filter.

       The following tables and scalars can be pointed to by this
       column.  All but diffServMultiFieldClfrTable are defined in
       this MIB.  Implementations MAY choose to provide support
       for other filter tables or scalars as well:

            diffServMultiFieldClfrTable
            spdIpsoHeaderFilterTable
             spdIpOffsetFilterTable
            spdTimeFilterTable
            spdCompoundFilterTable
            spdTrueFilter

       If this column is set to a VariablePointer value that
       references a non-existent row in an otherwise supported
       table, the inconsistentName exception MUST be returned.  If
       the table or scalar pointed to by the VariablePointer is
       not supported at all, then an inconsistentValue exception
       MUST be returned.

       If, during packet processing, this column has a value that
       references a non-existent or non-supported object, the
       packet MUST be dropped."
  REFERENCE "RFC 3289"
  ::= { spdSubfiltersEntry 2 }

spdSubFiltSubfilterIsNegated OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "Indicates whether or not the result of applying this sub-filter
      is negated."
  DEFVAL { false }
  ::= { spdSubfiltersEntry
 3 }
```

```
spdSubFiltLastChanged OBJECT-TYPE
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The value of sysUpTime when this row was last modified
      or created either through SNMP SETs or by some other
      external means.




      If this row has not been modified since the last
      re-initialization of the network management subsystem, this
      object SHOULD have a zero value."
  ::= { spdSubfiltersEntry 4 }

spdSubFiltStorageType OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The storage type for this row.  Rows in this table that
      were created through an external process MAY have a
      storage type of readOnly or permanent.

      For a storage type of permanent, none of the columns have
      to be writable."
  DEFVAL { nonVolatile }
  ::= { spdSubfiltersEntry 5 }

spdSubFiltRowStatus OBJECT-TYPE
  SYNTAX
    RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object indicates the conceptual status of this row.

      The value of this object has no effect on whether other
      objects in this conceptual row can be modified.

      This object cannot be made active until a filter
      referenced by the spdSubFiltSubfilter object is both
      defined and active.  An attempt to do so MUST result in
      an inconsistentValue error.

      If active, this object MUST remain active unless one of the
```

```
        following two conditions are met:

        I.  No active row in the SpdCompoundFilterTable exists
            that has a matching spdCompFiltName.

        II. Or, at least one other active row in this table has a
            matching spdCompFiltName.

        If neither condition is met, an attempt to set this row to
        something other than active MUST result in an
        inconsistentValue error."
    ::=
  { spdSubfiltersEntry 6 }




--
-- Static Filters
--

spdStaticFilters OBJECT IDENTIFIER ::= { spdConfigObjects 7 }

spdTrueFilter OBJECT-TYPE
      SYNTAX      Integer32 (1)
      MAX-ACCESS  read-only
      STATUS      current
      DESCRIPTION
          "This scalar indicates a (automatic) true result for
           a filter.  That is, this is a filter that is always
           true; it is useful for adding as a default filter for a
           default action or a set of actions."
      ::= { spdStaticFilters 1 }


spdTrueFilterInstance OBJECT IDENTIFIER ::= { spdTrueFilter 0 }



--
-- Policy IP Offset filter definition table
--

spdIpOffsetFilterTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF SpdIpOffsetFilterEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains a list of filter definitions to be
```

```
        used within the spdRuleDefinitionTable or the
        spdSubfiltersTable.

        This type of filter is used
 to compare an administrator
        specified octet string to the octets at a particular
        location in a packet."
   ::= { spdConfigObjects 8 }

spdIpOffsetFilterEntry OBJECT-TYPE
   SYNTAX      SpdIpOffsetFilterEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "A definition of a particular filter."
   INDEX       {  spdIpOffFiltName }
   ::= { spdIpOffsetFilterTable 1 }




SpdIpOffsetFilterEntry ::= SEQUENCE {
   spdIpOffFiltName                 SnmpAdminString,
   spdIpOffFiltOffset               Unsigned32,
   spdIpOffFiltType                 INTEGER,
   spdIpOffFiltValue                OCTET STRING,
   spdIpOffFiltLastChanged          TimeStamp,
   spdIpOffFiltStorageType          StorageType,
   spdIpOffFiltRowStatus            RowStatus
}

spdIpOffFiltName OBJECT-TYPE
   SYNTAX      SnmpAdminString (SIZE(1..32))
   MAX-ACCESS  not-accessible
   STATUS      current
    DESCRIPTION
      "The administrative name for this filter."
   ::= { spdIpOffsetFilterEntry 1 }

spdIpOffFiltOffset OBJECT-TYPE
   SYNTAX      Unsigned32 (0..65535)
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "This is the byte offset from the front of the entire IP
       packet where the value or arithmetic comparison is done.  A
       value of '0' indicates the first byte of the packet header.
       If this value is greater than the length of the packet, the
```

```
        filter represented by this row should be considered to
        fail."
    ::= { spdIpOffsetFilterEntry 2 }

spdIpOffFiltType OBJECT-TYPE
    SYNTAX INTEGER { equal(1),
                     notEqual(2),
                     arithmeticLess(3),
                     arithmeticGreaterOrEqual(4),
                     arithmeticGreater(5),
                     arithmeticLessOrEqual(6) }
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This defines the
   various tests that are used when
        evaluating a given filter.

        The various tests definable in this table are as follows:

        equal:
          - Tests if the OCTET STRING, 'spdIpOffFiltValue', matches



            a value in the packet starting at the given offset in
            the packet and comparing the entire OCTET STRING of
            'spdIpOffFiltValue'.  Any values compared this way are
            assumed to be unsigned integer values in network byte
            order of the same length as 'spdIpOffFiltValue'.

        notEqual:
          - Tests if the OCTET STRING, 'spdIpOffFiltValue', does
            not match a value in the packet starting at the given
            offset in the packet and comparing to the entire OCTET
            STRING of 'spdIpOffFiltValue'.  Any values compared
            this way are assumed to be unsigned integer values in
            network byte order of the same length as
            'spdIpOffFiltValue'.


        arithmeticLess:
          - Tests if the OCTET STRING, 'spdIpOffFiltValue', is
            arithmetically less than ('<') the value starting at
            the given offset within the packet.  The value in the
            packet is assumed to be an unsigned integer in network
            byte order of the same length as 'spdIpOffFiltValue'.
```

arithmeticGreaterOrEqual:
- Tests if the OCTET STRING, 'spdIpOffFiltValue', is arithmetically greater than or equal to ('>=') the value starting at the given offset within the packet. The value in the packet is assumed to be an unsigned integer in network byte order of the same length as 'spdIpOffFiltValue'.

arithmeticGreater:
- Tests if the OCTET STRING, 'spdIpOffFiltValue', is arithmetically greater than ('>') the value starting at the given offset within the packet. The value in the packet is
assumed to be an unsigned integer in network
byte order of the same length as 'spdIpOffFiltValue'.

arithmeticLessOrEqual:
- Tests if the OCTET STRING, 'spdIpOffFiltValue', is arithmetically less than or equal to ('<=') the value starting at the given offset within the packet. The value in the packet is assumed to be an unsigned integer in network byte order of the same length as 'spdIpOffFiltValue'."

::= { spdIpOffsetFilterEntry 3 }

spdIpOffFiltValue OBJECT-TYPE

SYNTAX OCTET STRING (SIZE(1..1024))
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"spdIpOffFiltValue is used for match comparisons of a packet at spdIpOffFiltOffset."
::= { spdIpOffsetFilterEntry 4 }

spdIpOffFiltLastChanged OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime when this
row was last modified
or created either through SNMP SETs or by some other external means.

```
        If this row has not been modified since the last
        re-initialization of the network management subsystem, this
        object SHOULD have a zero value."
    ::= { spdIpOffsetFilterEntry 5 }


spdIpOffFiltStorageType OBJECT-TYPE
    SYNTAX      StorageType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The storage type for this row.  Rows in this table that
        were created through an external process MAY have a
        storage type of readOnly or permanent.

        For a storage type of permanent, none of the columns have
        to be writable."
    DEFVAL { nonVolatile }
    ::= { spdIpOffsetFilterEntry 6 }

spdIpOffFiltRowStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "This object indicates the conceptual status of this row.

        The value of
 this object has no effect on whether other
        objects in this conceptual row can be modified.

        If active, this object MUST remain active if it is




        referenced by an active row in another table.  An attempt
        to set it to anything other than active while it is
        referenced by an active row in another table MUST result in
        an inconsistentValue error."
    ::= { spdIpOffsetFilterEntry 7 }


--
-- Time/scheduling filter table
--

spdTimeFilterTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF SpdTimeFilterEntry
```

```
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "Defines a table of filters that can be used to
      effectively enable or disable policies based on a valid
      time range."
  ::= { spdConfigObjects 9 }

spdTimeFilterEntry OBJECT-TYPE
  SYNTAX      SpdTimeFilterEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A row describing a given time frame for which a policy
      is filtered on to activate or deactivate the rule.

      If all the column objects in a row are true for the current
      time, the row evaluates as 'true'.  More explicitly, the
      time matching column objects in a row MUST be logically
      ANDed together to form the boolean true/false for the row."
  INDEX   { spdTimeFiltName }
  ::= { spdTimeFilterTable 1 }

SpdTimeFilterEntry ::= SEQUENCE {
  spdTimeFiltName               SnmpAdminString,
  spdTimeFiltPeriod             SpdTimePeriod,
  spdTimeFiltMonthOfYearMask    BITS,
  spdTimeFiltDayOfMonthMask     OCTET STRING,
  spdTimeFiltDayOfWeekMask      BITS,
  spdTimeFiltTimeOfDayMask      SpdTimePeriod,
  spdTimeFiltLastChanged        TimeStamp,
  spdTimeFiltStorageType        StorageType,
  spdTimeFiltRowStatus          RowStatus
}




spdTimeFiltName OBJECT-TYPE
  SYNTAX      SnmpAdminString (SIZE(1..32))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "An administratively assigned name for this filter."
  ::= { spdTimeFilterEntry 1 }


spdTimeFiltPeriod OBJECT-TYPE
```

```
  SYNTAX      SpdTimePeriod
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The valid time period for this filter.  This column is
      considered 'true' if the current time is within the range of
      this object."
  DEFVAL { "THISANDPRIOR/THISANDFUTURE" }
  ::= { spdTimeFilterEntry 2 }


spdTimeFiltMonthOfYearMask OBJECT-TYPE
  SYNTAX      BITS { january(0), february(1), march(2),
                     april(3), may(4), june(5), july(6),
                     august(7), september(8), october(9),
                     november(10), december(11) }
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "A bit mask that indicates acceptable months of the year.
      This column evaluates to 'true' if the current month's bit
      is set."
  DEFVAL { { january, february, march,
 april, may, june, july,
           august, september, october, november, december } }
  ::= { spdTimeFilterEntry 3 }

spdTimeFiltDayOfMonthMask OBJECT-TYPE
  SYNTAX      OCTET STRING (SIZE(8))
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "Defines which days of the month the current time is
      valid for.  It is a sequence of 64 BITS, where each BIT
      represents a corresponding day of the month in forward or
      reverse order.  Starting from the left-most bit, the first
      31 bits identify the day of the month, counting from the
      beginning of the month.  The following 31 bits (bits 32-62)
      indicate the day of the month, counting from the end of the



      month.  For months with fewer than 31 days, the bits that
      correspond to the non-existent days of that month are
      ignored (e.g., for non-leap year Februarys, bits 29-31 and
      60-62 are ignored).

      This column evaluates
```

```
 to 'true' if the current day of the
       month's bit is set.

       For example, a value of 0X'80 00 00 01 00 00 00 00'
       indicates that this column evaluates to true on the first
       and last days of the month.

       The last two bits in the string MUST be zero."
  DEFVAL { 'fffffffffffffffe'H }
  ::= { spdTimeFilterEntry 4 }

spdTimeFiltDayOfWeekMask OBJECT-TYPE
  SYNTAX      BITS { sunday(0), monday(1), tuesday(2),
                     wednesday(3), thursday(4), friday(5),
                     saturday(6) }
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "A bit mask that defines which days of the week that the current
      time is valid for.  This column evaluates to 'true' if the
      current day of the week's bit is set."
  DEFVAL { { monday, tuesday, wednesday, thursday, friday,
             saturday, sunday } }
  ::= { spdTimeFilterEntry 5 }

spdTimeFiltTimeOfDayMask OBJECT-TYPE
  SYNTAX      SpdTimePeriod
   MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "Indicates the start and end time of the day for which this
      filter evaluates to true.  The date portions of the
      spdTimePeriod TC are ignored for purposes of evaluating this
      mask, and only the time-specific portions are used.

      This column evaluates to 'true' if the current time of day
      is within the range of the start and end times of the day
      indicated by this object."
  DEFVAL { "00000000T000000/00000000T240000" }
  ::= { spdTimeFilterEntry 6 }

spdTimeFiltLastChanged OBJECT-TYPE
  SYNTAX      TimeStamp



  MAX-ACCESS  read-only
  STATUS      current
```

```
  DESCRIPTION
      "The value of sysUpTime when this row was last modified
       or created either through SNMP SETs or by some other
       external means.

       If this row has not been modified since the last
       re-initialization of the network management subsystem, this

      object SHOULD have a zero value."
  ::= { spdTimeFilterEntry 7 }

spdTimeFiltStorageType OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "The storage type for this row.  Rows in this table that
       were created through an external process MAY have a storage
       type of readOnly or permanent.

       For a storage type of permanent, none of the columns have
       to be writable."
  DEFVAL { nonVolatile }
  ::= { spdTimeFilterEntry 8 }

spdTimeFiltRowStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "This object indicates the conceptual status of this
       row.

       The value of this object has no effect on whether other
       objects in this conceptual row can be modified.

       If active, this object MUST remain active if it is
       referenced by an active row in another table.  An attempt
       to set
 it to anything other than active while it is
       referenced by an active row in another table MUST result in
       an inconsistentValue error."
  ::= { spdTimeFilterEntry 9 }

--
-- IPSO protection authority filtering
--
```

```
spdIpsoHeaderFilterTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SpdIpsoHeaderFilterEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "This table contains a list of IPSO header filter
      definitions to be used within the spdRuleDefinitionTable or
      the spdSubfiltersTable.  IPSO headers and their values are
      described in RFC 1108."
  REFERENCE "RFC 1108"
  ::= { spdConfigObjects 10 }

spdIpsoHeaderFilterEntry OBJECT-TYPE
  SYNTAX      SpdIpsoHeaderFilterEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A definition of a particular filter."
  INDEX       {  spdIpsoHeadFiltName }
  ::= { spdIpsoHeaderFilterTable 1 }

SpdIpsoHeaderFilterEntry ::= SEQUENCE
 {
  spdIpsoHeadFiltName                 SnmpAdminString,
  spdIpsoHeadFiltType                 BITS,
  spdIpsoHeadFiltClassification       INTEGER,
  spdIpsoHeadFiltProtectionAuth       INTEGER,
  spdIpsoHeadFiltLastChanged          TimeStamp,
  spdIpsoHeadFiltStorageType          StorageType,
  spdIpsoHeadFiltRowStatus            RowStatus
}

spdIpsoHeadFiltName OBJECT-TYPE
  SYNTAX      SnmpAdminString (SIZE(1..32))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The administrative name for this filter."
  ::= { spdIpsoHeaderFilterEntry 1 }

spdIpsoHeadFiltType OBJECT-TYPE
  SYNTAX      BITS { classificationLevel(0),
                     protectionAuthority(1) }
  MAX-ACCESS  read-create
  STATUS      current
```

```
  DESCRIPTION
     "This object indicates which of the IPSO header field a
      packet is filtered on for this row.  If this object is set
      to classification(0), the spdIpsoHeadFiltClassification




       object indicates how the packet is filtered.  If this object
      is set to protectionAuthority(1), the
      spdIpsoHeadFiltProtectionAuth object indicates how the
      packet is filtered."
  ::= { spdIpsoHeaderFilterEntry 2 }

spdIpsoHeadFiltClassification OBJECT-TYPE
  SYNTAX      INTEGER { topSecret(61), secret(90),
                        confidential(150), unclassified(171) }
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object indicates the IPSO classification header field
      value that the packet MUST have for this row to evaluate to
      'true'.

      The values of these enumerations are defined by RFC 1108."
  REFERENCE "RFC 1108"
  ::= { spdIpsoHeaderFilterEntry 3 }

spdIpsoHeadFiltProtectionAuth OBJECT-TYPE
  SYNTAX      INTEGER { genser(0), siopesi(1), sci(2),
                        nsa(3), doe(4) }
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "This object indicates the IPSO protection authority header
      field value that the packet MUST have for this row to
      evaluate to 'true'.

      The values of these enumerations are defined by RFC 1108.
      Hence the reason the SMIv2 convention of not using 0 in
      enumerated lists is violated here."
  REFERENCE "RFC 1108"
  ::= { spdIpsoHeaderFilterEntry 4 }

spdIpsoHeadFiltLastChanged OBJECT-TYPE
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
```

"The value of sysUpTime when this row was last modified
or created either through SNMP SETs or by some other
external means.

If this row has not been modified since the last
re-initialization of the network management subsystem, this
object SHOULD have a zero value."

::= { spdIpsoHeaderFilterEntry 5 }

spdIpsoHeadFiltStorageType OBJECT-TYPE
SYNTAX StorageType
MAX-ACCESS read-create
STATUS
current
DESCRIPTION
"The storage type for this row. Rows in this table that
were created through an external process MAY have a storage
type of readOnly or permanent.

For a storage type of permanent, none of the columns have
to be writable."
DEFVAL { nonVolatile }
::= { spdIpsoHeaderFilterEntry 6 }

spdIpsoHeadFiltRowStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This object indicates the conceptual status of this row.

The value of this object has no effect on whether other
objects in this conceptual row can be modified.

However, this object MUST NOT be set to active if the
requirements of the spdIpsoHeadFiltType object are not met.
Specifically, if the spdIpsoHeadFiltType bit for
classification(0) is set, the spdIpsoHeadFiltClassification
column MUST have a valid value for the row
status to be set
to active. If the spdIpsoHeadFiltType bit for
protectionAuthority(1) is set, the
spdIpsoHeadFiltProtectionAuth column MUST have a valid
value for the row status to be set to active.

```
        If active, this object MUST remain active if it is
        referenced by an active row in another table.  An attempt
        to set it to anything other than active while it is
        referenced by an active row in another table MUST result in
        an inconsistentValue error."
    ::= { spdIpsoHeaderFilterEntry 7 }

--
-- compound actions table
--

spdCompoundActionTable OBJECT-TYPE



    SYNTAX      SEQUENCE OF SpdCompoundActionEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Table used to allow multiple actions to be associated
        with a rule.  It uses the spdSubactionsTable to do this.
        The rows from spdSubactionsTable that are partially indexed
        by spdCompActName form the
 set of compound actions to be
        performed.  The spdCompActExecutionStrategy column in this
        table indicates how those actions are processed."
    ::= { spdConfigObjects 11 }

spdCompoundActionEntry OBJECT-TYPE
    SYNTAX      SpdCompoundActionEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A row in the spdCompoundActionTable."
    INDEX   { spdCompActName }
    ::= { spdCompoundActionTable 1 }

SpdCompoundActionEntry ::= SEQUENCE {
    spdCompActName                  SnmpAdminString,
    spdCompActExecutionStrategy        INTEGER,
    spdCompActLastChanged              TimeStamp,
    spdCompActStorageType              StorageType,
    spdCompActRowStatus                RowStatus
}

spdCompActName OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(1..32))
    MAX-ACCESS  not-accessible
```

```
  STATUS      current
  DESCRIPTION
     "This is an administratively assigned name of this
      compound action."
  ::= { spdCompoundActionEntry
 1 }

spdCompActExecutionStrategy OBJECT-TYPE
  SYNTAX      INTEGER { doAll(1),
                        doUntilSuccess(2),
                        doUntilFailure(3) }
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object indicates how the sub-actions are executed
      based on the success of the actions as they finish
      executing.



      doAll          - run each sub-action regardless of the
                       exit status of the previous action.
                       This parent action is always
                       considered to have acted successfully.

      doUntilSuccess  - run each sub-action until one succeeds,
                       at which point stop processing the
                       sub-actions within this parent
                       compound action.  If one of the
                       sub-actions did execute successfully,
                       this parent
 action is also considered
                       to have executed successfully.

      doUntilFailure  - run each sub-action until one fails,
                       at which point stop processing the
                       sub-actions within this compound
                       action.  If any sub-action fails, the
                       result of this parent action is
                       considered to have failed."
  DEFVAL { doUntilSuccess }
  ::= { spdCompoundActionEntry 2 }

spdCompActLastChanged OBJECT-TYPE
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
```

```
      "The value of sysUpTime when this row was last modified
       or created either through SNMP SETs or by some other
       external means.

       If this row has not been modified since the last
       re-initialization of the network management subsystem, this
       object SHOULD have a zero value."
  ::= { spdCompoundActionEntry
 3 }

spdCompActStorageType OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The storage type for this row.  Rows in this table that
      were created through an external process MAY have a storage
      type of readOnly or permanent.

      For a storage type of permanent, none of the columns have
      to be writable."
  DEFVAL { nonVolatile }



  ::= { spdCompoundActionEntry 4 }

spdCompActRowStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object indicates the conceptual status of this row.

      The value of this object has no effect on whether other
      objects in this conceptual row can be modified.

      Once a row in the spdCompoundActionTable has been made
      active, this object MUST NOT be set to destroy without
      first destroying all the contained rows listed in the
      spdSubactionsTable."
   ::= { spdCompoundActionEntry 5 }



--
-- actions contained within a compound action
--
```

```
spdSubactionsTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SpdSubactionsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "This table contains a list of the sub-actions within a
      given compound action.  Compound actions executing these
      actions MUST execute them in series based on the
      spdSubActPriority value, with the lowest value executing
      first."
  ::= { spdConfigObjects 12 }

spdSubactionsEntry OBJECT-TYPE
  SYNTAX      SpdSubactionsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A row containing a reference to a given compound-action
      sub-action."
  INDEX   { spdCompActName, spdSubActPriority }
  ::= { spdSubactionsTable 1 }

SpdSubactionsEntry ::= SEQUENCE {
  spdSubActPriority                 Integer32,
  spdSubActSubActionName
  VariablePointer,



  spdSubActLastChanged               TimeStamp,
  spdSubActStorageType               StorageType,
  spdSubActRowStatus                 RowStatus
}

spdSubActPriority OBJECT-TYPE
  SYNTAX      Integer32 (0..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The priority of a given sub-action within a compound
      action.  The order in which sub-actions MUST be executed
      are based on the value from this column, with the lowest
      numeric value executing first (i.e., priority 0 before
      priority 1, 1 before 2, etc.)."
  ::= { spdSubactionsEntry 1 }

spdSubActSubActionName OBJECT-TYPE
  SYNTAX      VariablePointer
```

MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This column points to the action to be taken. It MAY,
but is not limited to, point to a row in one of the
following tables:

spdCompoundActionTable
- Allowing recursion
ipsaSaPreconfiguredActionTable
ipiaIkeActionTable
ipiaIpsecActionTable

It MAY also point to one of the scalar objects beneath
spdStaticActions.

If this object is set to a pointer to a row in an
unsupported (or unknown) table, an inconsistentValue
error MUST be returned.

If this object is set to point to a non-existent row in
an otherwise supported table, an inconsistentName error
MUST be returned.

If, during packet processing, this column has a value that
references a non-existent or non-supported object, the
packet MUST be dropped."
::= { spdSubactionsEntry 2 }

spdSubActLastChanged OBJECT-TYPE

SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime when this row was last modified
or created either through SNMP SETs or by some other
external
means.

If this row has not been modified since the last
re-initialization of the network management subsystem, this
object SHOULD have a zero value."
::= { spdSubactionsEntry 3 }

spdSubActStorageType OBJECT-TYPE

```
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The storage type for this row.  Rows in this table that
      were created through an external process MAY have a storage
      type of readOnly or permanent.

      For a storage type of permanent, none of the columns have
      to be writable."
  DEFVAL { nonVolatile }
  ::= { spdSubactionsEntry 4 }

spdSubActRowStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object indicates the conceptual status of this row.

      The value of this object has no effect on whether other
      objects in this conceptual row can be modified.


  If active, this object MUST remain active unless one of the
      following two conditions are met.  An attempt to set it to
      anything other than active while the following conditions
      are not met MUST result in an inconsistentValue error.  The
      two conditions are:

      I.  No active row in the spdCompoundActionTable exists
          which has a matching spdCompActName.

      II. Or, at least one other active row in this table has a
          matching spdCompActName."



  ::= { spdSubactionsEntry 5 }

--
-- Static Actions
--

-- these are static actions that can be pointed to by the
-- spdRuleDefAction or the spdSubActSubActionName objects to
-- drop, accept, or reject packets.
```

```
spdStaticActions OBJECT IDENTIFIER ::= { spdConfigObjects 13 }

spdDropAction    OBJECT-TYPE
  SYNTAX      Integer32 (1)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "This scalar indicates that a packet MUST be dropped
       and SHOULD
 NOT have action/packet logging."
  ::= { spdStaticActions 1 }

spdDropActionLog OBJECT-TYPE
  SYNTAX      Integer32 (1)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "This scalar indicates that a packet MUST be dropped
       and SHOULD have action/packet logging."
  ::= { spdStaticActions 2 }

spdAcceptAction OBJECT-TYPE
  SYNTAX      Integer32 (1)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "This Scalar indicates that a packet MUST be accepted
       (pass-through) and SHOULD NOT have action/packet logging."
  ::= { spdStaticActions 3 }

spdAcceptActionLog OBJECT-TYPE
  SYNTAX      Integer32 (1)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "This scalar indicates that a packet MUST be accepted
       (pass-through) and SHOULD have action/packet logging."
  ::= { spdStaticActions 4 }




--
--
-- Notification objects information
--
--
```

```
spdNotificationVariables OBJECT IDENTIFIER
 ::=
  { spdNotificationObjects 1 }

spdNotifications OBJECT IDENTIFIER ::=
  { spdNotificationObjects 0 }

spdActionExecuted OBJECT-TYPE
   SYNTAX      VariablePointer
   MAX-ACCESS  accessible-for-notify
   STATUS      current
   DESCRIPTION
       "Points to the action instance that was executed that
        resulted in the notification being sent."
   ::= { spdNotificationVariables 1 }

spdIPEndpointAddType OBJECT-TYPE
   SYNTAX      InetAddressType
   MAX-ACCESS  accessible-for-notify
   STATUS      current
   DESCRIPTION
       "Contains the address type for the interface that the
        notification triggering packet is passing through."
   ::= { spdNotificationVariables 2 }

spdIPEndpointAddress OBJECT-TYPE
   SYNTAX      InetAddress
   MAX-ACCESS  accessible-for-notify
   STATUS      current
   DESCRIPTION
       "Contains the interface address for the interface that the
        notification triggering packet is passing through.

        The format of
  this object is specified by the
        spdIPEndpointAddType object."
   ::= { spdNotificationVariables 3 }

spdIPSourceType OBJECT-TYPE
   SYNTAX      InetAddressType
   MAX-ACCESS  accessible-for-notify
   STATUS      current
   DESCRIPTION
       "Contains the source address type of the packet that



        triggered the notification."
```

```
  ::= { spdNotificationVariables 4 }

spdIPSourceAddress OBJECT-TYPE
  SYNTAX      InetAddress
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
     "Contains the source address of the packet that
      triggered the notification.

      The format of this object is specified by the
      spdIPSourceType object."
  ::= { spdNotificationVariables 5 }

spdIPDestinationType OBJECT-TYPE
  SYNTAX      InetAddressType
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
     "Contains the destination address type of the packet
      that triggered the notification."
   ::= { spdNotificationVariables 6 }

spdIPDestinationAddress OBJECT-TYPE
  SYNTAX      InetAddress
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
     "Contains the destination address of the packet that
      triggered the notification.

      The format of this object is specified by the
      spdIPDestinationType object."
  ::= { spdNotificationVariables 7 }

spdPacketDirection OBJECT-TYPE
  SYNTAX      IfDirection
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
     "Indicates if the packet that triggered the action in
      questions was ingress (inbound) or egress (outbound)."
  ::= { spdNotificationVariables 8 }

spdPacketPart OBJECT-TYPE
  SYNTAX      OCTET STRING (SIZE (0..65535))
  MAX-ACCESS  accessible-for-notify
```

```
  STATUS      current
  DESCRIPTION
     "spdPacketPart is the front part of the full IP packet that
      triggered this notification.  The initial size limit
is
      determined by the smaller of the size, indicated by:

      I.  The value of the object with the TC syntax
         'SpdIPPacketLogging' that indicated the packet SHOULD be
         logged and

      II. The size of the triggering packet.

      The final limit is determined by the SNMP packet size when
      sending the notification.  The maximum size that can be
      included will be the smaller of the initial size, given the
      above, and the length that will fit in a single SNMP
      notification packet after the rest of the notification's
      objects and any other necessary packet data (headers encoding,
      etc.) have been included in the packet."
  ::= { spdNotificationVariables 9 }

spdActionNotification NOTIFICATION-TYPE
  OBJECTS { spdActionExecuted, spdIPEndpointAddType,
            spdIPEndpointAddress,
            spdIPSourceType, spdIPSourceAddress,
            spdIPDestinationType,
            spdIPDestinationAddress,
             spdPacketDirection }
  STATUS  current
  DESCRIPTION
     "Notification that an action was executed by a rule.
      Only actions with logging enabled will result in this
      notification getting sent.  The object includes the
      spdActionExecuted object, which will indicate which action
      was executed within the scope of the rule.  Additionally,
      the spdIPSourceType, spdIPSourceAddress,
      spdIPDestinationType, and spdIPDestinationAddress objects
      are included to indicate the packet source and destination
      of the packet that triggered the action.  Finally, the
      spdIPEndpointAddType, spdIPEndpointAddress, and
      spdPacketDirection objects indicate which interface the
      executed action was associated with, and if the packet was
      ingress or egress through the endpoint.

      A spdActionNotification SHOULD be limited to a maximum of
```

```
        one notification sent per minute
    for any action
        notifications that do not have any other configuration
        controlling their send rate.



        Note that compound actions with multiple executed
        sub-actions may result in multiple notifications being sent
        from a single rule execution."
    ::= { spdNotifications 1 }

spdPacketNotification NOTIFICATION-TYPE
    OBJECTS { spdActionExecuted, spdIPEndpointAddType,
              spdIPEndpointAddress,
              spdIPSourceType, spdIPSourceAddress,
              spdIPDestinationType,
              spdIPDestinationAddress,
              spdPacketDirection,
              spdPacketPart }
    STATUS  current
    DESCRIPTION
       "Notification that a packet passed through a Security
        Association (SA).  Only SAs created by actions with packet
        logging enabled will result in this notification getting
        sent.  The objects sent MUST include the spdActionExecuted,
        which will indicate which action was executed
    within the
        scope of the rule.  Additionally, the spdIPSourceType,
        spdIPSourceAddress, spdIPDestinationType, and
        spdIPDestinationAddress objects MUST be included to
        indicate the packet source and destination of the packet
        that triggered the action.  The spdIPEndpointAddType,
        spdIPEndpointAddress, and spdPacketDirection objects are
        included to indicate which endpoint the packet was
        associated with.  Finally, spdPacketPart is included to
        enable sending a variable sized part of the front of the
        packet with the size dependent on the value of the object of
        TC syntax 'SpdIPPacketLogging', which indicated that logging
        should be done.

        A spdPacketNotification SHOULD be limited to a maximum of
        one notification sent per minute for any action
        notifications that do not have any other configuration
        controlling their send rate.

        An action notification
```

```
 SHOULD be limited to a maximum of
       one notification sent per minute for any action
       notifications that do not have any other configuration
       controlling their send rate."
  ::= { spdNotifications 2 }


--
--
-- Conformance information



--
--

spdCompliances OBJECT IDENTIFIER
  ::= { spdConformanceObjects 1 }
spdGroups OBJECT IDENTIFIER
  ::= { spdConformanceObjects 2 }

--
-- Compliance statements
--
--
spdRuleFilterFullCompliance MODULE-COMPLIANCE
  STATUS      current
  DESCRIPTION
      "The compliance statement for SNMP entities that include
       an IPsec MIB implementation with Endpoint, Rules, and
       filters support.

       When this MIB is implemented with support for read-create,
       then such an implementation can claim full compliance.  Such
       devices can then be both monitored and configured with this
       MIB."

  MODULE -- This Module
     MANDATORY-GROUPS { spdEndpointGroup,

    spdGroupContentsGroup,
                    spdRuleDefinitionGroup,
                    spdStaticFilterGroup,
                    spdStaticActionGroup ,
                    diffServMIBMultiFieldClfrGroup }

     GROUP spdIpsecSystemPolicyNameGroup
     DESCRIPTION
```

"This group is mandatory for IPsec Policy
implementations that support a system policy group
name."

GROUP spdCompoundFilterGroup
DESCRIPTION
"This group is mandatory for IPsec Policy
implementations that support compound filters."

GROUP spdIPOffsetFilterGroup
DESCRIPTION
"This group is mandatory for IPsec Policy
implementations that support IP Offset filters. In
general, this SHOULD be supported by a compliant IPsec

Policy implementation."

GROUP spdTimeFilterGroup
DESCRIPTION
"This group is mandatory for IPsec Policy
implementations that support time filters."

GROUP spdIpsoHeaderFilterGroup
DESCRIPTION
"This group is mandatory for IPsec Policy
implementations that support IPSO Header filters."

GROUP spdCompoundActionGroup
DESCRIPTION
"This group is mandatory for IPsec Policy
implementations that support compound actions."

OBJECT spdEndGroupLastChanged
MIN-ACCESS not-accessible
DESCRIPTION
"This object not required for compliance."

OBJECT spdGroupContComponentType
SYNTAX INTEGER {
rule(2)
}
DESCRIPTION
"Support of the value group(1) is only required for
implementations that support Policy Groups within
Policy Groups."

OBJECT spdGroupContLastChanged
MIN-ACCESS not-accessible
DESCRIPTION
"This object not required for compliance."

OBJECT spdRuleDefLastChanged
MIN-ACCESS not-accessible
DESCRIPTION
"This object not required for compliance."

OBJECT spdCompFiltLastChanged
MIN-ACCESS not-accessible
DESCRIPTION
"This object not required for compliance."

OBJECT spdSubFiltLastChanged
MIN-ACCESS not-accessible

DESCRIPTION
"This object not required for compliance."

OBJECT spdIpOffFiltLastChanged
MIN-ACCESS not-accessible
DESCRIPTION
"This object not required for compliance."

OBJECT spdTimeFiltLastChanged
MIN-ACCESS not-accessible
DESCRIPTION
"This object not required for compliance."

OBJECT spdIpsoHeadFiltLastChanged
MIN-ACCESS not-accessible
DESCRIPTION
"This object not required for compliance."

OBJECT spdCompActLastChanged
MIN-ACCESS
not-accessible
DESCRIPTION
"This object not required for compliance."

OBJECT spdSubActLastChanged
MIN-ACCESS not-accessible
DESCRIPTION
"This object not required for compliance."

```
      OBJECT      diffServMultiFieldClfrNextFree
      MIN-ACCESS  not-accessible
      DESCRIPTION
         "This object is not required for compliance."

   ::= { spdCompliances 1 }


spdLoggingCompliance MODULE-COMPLIANCE
   STATUS      current
   DESCRIPTION
      "The compliance statement for SNMP entities that support
       sending notifications when actions are invoked."
   MODULE -- This Module
      MANDATORY-GROUPS { spdActionLoggingObjectGroup,
                         spdActionNotificationGroup }

   ::= { spdCompliances 2 }

--



-- ReadOnly Compliances
--
spdRuleFilterReadOnlyCompliance MODULE-COMPLIANCE
   STATUS      current
   DESCRIPTION
      "The compliance statement for SNMP entities that include
       an IPsec MIB implementation with Endpoint, Rules, and
       filters support.

       If this MIB is implemented without support for read-create
       (i.e., in read-only), it is not in full compliance, but it
       can claim read-only compliance.  Such a device can then be
       monitored, but cannot be configured with this MIB."

   MODULE -- This Module
      MANDATORY-GROUPS { spdEndpointGroup,
                         spdGroupContentsGroup,
                         spdRuleDefinitionGroup,
                         spdStaticFilterGroup,
                         spdStaticActionGroup ,
                         diffServMIBMultiFieldClfrGroup }

      GROUP spdIpsecSystemPolicyNameGroup
      DESCRIPTION
```

"This group is mandatory for IPsec Policy
implementations that support a system policy group
name."

GROUP spdCompoundFilterGroup
DESCRIPTION
"This group is mandatory for IPsec Policy
implementations that support compound filters."

GROUP spdIPOffsetFilterGroup
DESCRIPTION
"This group is mandatory for IPsec Policy
implementations that support IP Offset filters. In
general, this SHOULD be supported by a compliant IPsec
Policy implementation."

GROUP spdTimeFilterGroup
DESCRIPTION
"This group is mandatory for IPsec Policy
implementations that support time filters."

GROUP spdIpsoHeaderFilterGroup
DESCRIPTION
"This group is mandatory for IPsec Policy

implementations that support IPSO Header filters."

GROUP spdCompoundActionGroup
DESCRIPTION
"This group is mandatory for IPsec Policy
implementations that support compound actions."

OBJECT spdCompActExecutionStrategy
MIN-ACCESS read-only
DESCRIPTION
"Write access is not
required."

OBJECT spdCompActLastChanged
DESCRIPTION
"This object is not required for compliance."

OBJECT spdCompActRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdCompActStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdCompFiltDescription
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdCompFiltLastChanged
DESCRIPTION
"This object is not required for compliance."

OBJECT spdCompFiltLogicType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdCompFiltRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdCompFiltStorageType

MIN-ACCESS read-only
DESCRIPTION

"Write access is not required."

OBJECT spdEgressPolicyGroupName
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdEndGroupLastChanged
DESCRIPTION
"This object is not required for compliance."

OBJECT spdEndGroupName
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdEndGroupRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdEndGroupStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdGroupContComponentName
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdGroupContComponentType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdGroupContFilter
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdGroupContLastChanged
DESCRIPTION
"This object is not required for compliance."

OBJECT spdGroupContRowStatus
MIN-ACCESS read-only
DESCRIPTION

"Write access is not required."

OBJECT spdGroupContStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIngressPolicyGroupName
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpOffFiltLastChanged

DESCRIPTION
"This object is not required for compliance."

OBJECT spdIpOffFiltOffset
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpOffFiltRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpOffFiltStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpOffFiltType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpOffFiltValue
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpsoHeadFiltClassification
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpsoHeadFiltLastChanged
DESCRIPTION

"This object is not required for compliance."

OBJECT spdIpsoHeadFiltProtectionAuth
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpsoHeadFiltRowStatus
MIN-ACCESS read-only
DESCRIPTION

"Write access is not required."

OBJECT spdIpsoHeadFiltStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdIpsoHeadFiltType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdRuleDefAction
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdRuleDefAdminStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdRuleDefDescription
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdRuleDefFilter
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdRuleDefFilterNegated
MIN-ACCESS
read-only
DESCRIPTION
"Write access is not required."

OBJECT spdRuleDefLastChanged

DESCRIPTION
"This object is not required for compliance."

OBJECT spdRuleDefRowStatus
MIN-ACCESS read-only
DESCRIPTION

"Write access is not required."

OBJECT spdRuleDefStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdSubActLastChanged
DESCRIPTION
"This object is not required for compliance."

OBJECT spdSubActRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdSubActStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdSubActSubActionName
MIN-ACCESS read-only
DESCRIPTION
"Write access
is not required."

OBJECT spdSubFiltLastChanged
DESCRIPTION
"This object is not required for compliance."

OBJECT spdSubFiltRowStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdSubFiltStorageType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT spdSubFiltSubfilter
MIN-ACCESS read-only

DESCRIPTION
"Write access is not required."

```
    OBJECT      spdSubFiltSubfilterIsNegated
    MIN-ACCESS  read-only
    DESCRIPTION
        "Write access is not required."

    OBJECT      spdTimeFiltDayOfMonthMask
    MIN-ACCESS  read-only
    DESCRIPTION
        "Write access is not required."

    OBJECT      spdTimeFiltDayOfWeekMask
    MIN-ACCESS  read-only
    DESCRIPTION
        "Write access is not required."

    OBJECT
    spdTimeFiltLastChanged
    DESCRIPTION
        "This object is not required for compliance."

    OBJECT      spdTimeFiltMonthOfYearMask
    MIN-ACCESS  read-only
    DESCRIPTION
        "Write access is not required."

    OBJECT      spdTimeFiltPeriod
    MIN-ACCESS  read-only
    DESCRIPTION
        "Write access is not required."

    OBJECT      spdTimeFiltRowStatus
    MIN-ACCESS  read-only
    DESCRIPTION
        "Write access is not required."

    OBJECT      spdTimeFiltTimeOfDayMask
    MIN-ACCESS  read-only
    DESCRIPTION
        "Write access is not required."

    OBJECT      spdTimeFiltStorageType
    MIN-ACCESS  read-only
    DESCRIPTION
        "Write access is not required."

::= { spdCompliances 3 }
```

```
--
--
-- Compliance Groups Definitions
--

--
-- Endpoint, Rule, Filter Compliance Groups
--

spdEndpointGroup OBJECT-GROUP
  OBJECTS {
     spdEndGroupName,
 spdEndGroupLastChanged,
     spdEndGroupStorageType, spdEndGroupRowStatus
  }
  STATUS current
  DESCRIPTION
     "This group is made up of objects from the IPsec Policy
      Endpoint Table."
  ::= { spdGroups 1 }

spdGroupContentsGroup OBJECT-GROUP
  OBJECTS {
     spdGroupContComponentType, spdGroupContFilter,
     spdGroupContComponentName, spdGroupContLastChanged,
     spdGroupContStorageType, spdGroupContRowStatus
  }
  STATUS current
  DESCRIPTION
     "This group is made up of objects from the IPsec Policy
      Group Contents Table."
  ::= { spdGroups 2 }

spdIpsecSystemPolicyNameGroup OBJECT-GROUP
  OBJECTS {
     spdIngressPolicyGroupName,
     spdEgressPolicyGroupName
  }
  STATUS current
  DESCRIPTION
     "This group is made up of objects represent the System
      Policy Group Names."
  ::= { spdGroups 3}

spdRuleDefinitionGroup OBJECT-GROUP
  OBJECTS {
```

```
        spdRuleDefDescription, spdRuleDefFilter,
        spdRuleDefFilterNegated, spdRuleDefAction,
        spdRuleDefAdminStatus, spdRuleDefLastChanged,



        spdRuleDefStorageType, spdRuleDefRowStatus
    }
    STATUS current
    DESCRIPTION
        "This group is made up of objects from the IPsec Policy Rule
        Definition Table."
    ::= { spdGroups 4 }

spdCompoundFilterGroup OBJECT-GROUP
    OBJECTS {
        spdCompFiltDescription, spdCompFiltLogicType,
        spdCompFiltLastChanged, spdCompFiltStorageType,
        spdCompFiltRowStatus, spdSubFiltSubfilter,
        spdSubFiltSubfilterIsNegated, spdSubFiltLastChanged,
        spdSubFiltStorageType, spdSubFiltRowStatus
    }
    STATUS current
    DESCRIPTION
        "This group is made up of objects from the IPsec Policy
        Compound Filter Table and Sub-Filter Table Group."
    ::= { spdGroups 5 }

spdStaticFilterGroup OBJECT-GROUP
        OBJECTS { spdTrueFilter }
    STATUS current
    DESCRIPTION
        "The static filter group.  Currently this is just
 a true
        filter."
    ::= { spdGroups 6 }

spdIPOffsetFilterGroup OBJECT-GROUP
    OBJECTS {
        spdIpOffFiltOffset, spdIpOffFiltType,
        spdIpOffFiltValue, spdIpOffFiltLastChanged,
        spdIpOffFiltStorageType, spdIpOffFiltRowStatus
    }

    STATUS current
    DESCRIPTION
        "This group is made up of objects from the IPsec Policy IP
        Offset Filter Table."
```

```
  ::= { spdGroups 7 }

spdTimeFilterGroup OBJECT-GROUP
  OBJECTS {
     spdTimeFiltPeriod,
     spdTimeFiltMonthOfYearMask, spdTimeFiltDayOfMonthMask,
     spdTimeFiltDayOfWeekMask, spdTimeFiltTimeOfDayMask,




     spdTimeFiltLastChanged,
     spdTimeFiltStorageType, spdTimeFiltRowStatus
  }
  STATUS current
  DESCRIPTION
     "This group is made up of objects from the IPsec Policy Time
      Filter Table."
  ::= { spdGroups 8 }

spdIpsoHeaderFilterGroup OBJECT-GROUP
  OBJECTS {
     spdIpsoHeadFiltType, spdIpsoHeadFiltClassification,
     spdIpsoHeadFiltProtectionAuth,
 spdIpsoHeadFiltLastChanged,
     spdIpsoHeadFiltStorageType, spdIpsoHeadFiltRowStatus
  }
  STATUS current
  DESCRIPTION
     "This group is made up of objects from the IPsec Policy IPSO
      Header Filter Table."
  ::= { spdGroups 9 }

--
-- action compliance groups
--

spdStaticActionGroup OBJECT-GROUP
  OBJECTS {
     spdDropAction, spdAcceptAction,
     spdDropActionLog, spdAcceptActionLog
  }
  STATUS current
  DESCRIPTION
     "This group is made up of objects from the IPsec Policy
      Static Actions."
  ::= { spdGroups 10 }

spdCompoundActionGroup OBJECT-GROUP
```

```
  OBJECTS {
     spdCompActExecutionStrategy, spdCompActLastChanged,
     spdCompActStorageType,

     spdCompActRowStatus, spdSubActSubActionName,
     spdSubActLastChanged, spdSubActStorageType,
     spdSubActRowStatus
  }
  STATUS current
  DESCRIPTION
     "The IPsec Policy Compound Action Table and Actions In




      Compound Action Table
 Group."
  ::= { spdGroups 11 }

spdActionLoggingObjectGroup OBJECT-GROUP
  OBJECTS {
     spdActionExecuted,
     spdIPEndpointAddType,   spdIPEndpointAddress,
     spdIPSourceType,        spdIPSourceAddress,
     spdIPDestinationType,   spdIPDestinationAddress,
     spdPacketDirection,     spdPacketPart
  }
  STATUS current
  DESCRIPTION
     "This group is made up of all the Notification objects for
     this MIB."
  ::= { spdGroups 12 }

spdActionNotificationGroup NOTIFICATION-GROUP
  NOTIFICATIONS {
     spdActionNotification,
     spdPacketNotification
  }
  STATUS current
  DESCRIPTION
     "This group is made up of all the Notifications for this MIB."
  ::= { spdGroups 13 }


END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/IPSEC-SPD-MIB
```

No license file was found, but licenses were detected in source scan.

```
DIFFSERV-MIB DEFINITIONS ::= BEGIN

  IMPORTS
  Unsigned32, Counter64, MODULE-IDENTITY, OBJECT-TYPE,
  OBJECT-IDENTITY, zeroDotZero, mib-2
      FROM SNMPv2-SMI
  TEXTUAL-CONVENTION, RowStatus, RowPointer,
  StorageType, AutonomousType
      FROM SNMPv2-TC
  MODULE-COMPLIANCE, OBJECT-GROUP
      FROM SNMPv2-CONF
  ifIndex, InterfaceIndexOrZero
     FROM IF-MIB
  InetAddressType, InetAddress, InetAddressPrefixLength,
  InetPortNumber
     FROM INET-ADDRESS-MIB
  BurstSize
     FROM INTEGRATED-SERVICES-MIB
  Dscp, DscpOrAny
     FROM DIFFSERV-DSCP-TC;

diffServMib MODULE-IDENTITY
  LAST-UPDATED "200202070000Z"
  ORGANIZATION "IETF Differentiated Services WG"
  CONTACT-INFO
    "       Fred Baker
            Cisco Systems
            1121 Via Del Rey
            Santa Barbara, CA 93117, USA
            E-mail: fred@cisco.com

            Kwok Ho Chan

           Nortel Networks
            600 Technology Park Drive
            Billerica, MA 01821, USA
            E-mail: khchan@nortelnetworks.com

            Andrew Smith
            Harbour Networks
            Jiuling Building



            21 North Xisanhuan Ave.
            Beijing, 100089, PRC
            E-mail: ah_smith@acm.org
```

```
            Differentiated Services Working Group:
            diffserv@ietf.org"
    DESCRIPTION
      "This MIB defines the objects necessary to manage a device that
      uses the Differentiated Services Architecture described in RFC
      2475. The Conceptual Model of a Differentiated Services Router
      provides supporting information on how such a router is modeled."
    REVISION "200202070000Z"
    DESCRIPTION
      "Initial version, published as RFC 3289."
    ::= { mib-2 97 }

diffServMIBObjects     OBJECT IDENTIFIER ::= { diffServMib 1 }
diffServMIBConformance OBJECT IDENTIFIER ::= { diffServMib 2 }
diffServMIBAdmin
       OBJECT IDENTIFIER ::= { diffServMib 3 }

IndexInteger ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d"
    STATUS    current
    DESCRIPTION
      "An integer which may be used as a table index."
    SYNTAX    Unsigned32 (1..4294967295)

IndexIntegerNextFree ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d"
    STATUS    current
    DESCRIPTION
      "An integer which may be used as a new Index in a table.

      The special value of 0 indicates that no more new entries can be
      created in the relevant table.

      When a MIB is used for configuration, an object with this SYNTAX
      always contains a legal value (if non-zero) for an index that is
      not currently used in the relevant table. The Command Generator
      (Network Management Application) reads this variable and uses the
      (non-zero) value read when creating a new row with an SNMP SET.
      When the SET is performed, the Command Responder (agent) must
      determine whether the value is indeed
   still unused; Two Network
      Management Applications may attempt to create a row
      (configuration entry) simultaneously and use the same value. If
      it is currently unused, the SET succeeds and the Command
      Responder (agent) changes the value of this object, according to
      an implementation-specific algorithm.  If the value is in use,
```

```
      however, the SET fails.  The Network Management Application must
      then re-read this variable to obtain a new usable value.

      An OBJECT-TYPE definition using this SYNTAX MUST specify the
      relevant table for which the object is providing this
      functionality."
    SYNTAX   Unsigned32 (0..4294967295)

IfDirection ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
      "IfDirection specifies a direction of data travel on an
      interface. 'inbound' traffic is operated on during reception from
      the interface, while 'outbound' traffic is operated on prior to
      transmission on
 the interface."
    SYNTAX  INTEGER {
              inbound(1),     -- ingress interface
              outbound(2)     -- egress interface
}

--
-- Data Path
--

diffServDataPath       OBJECT IDENTIFIER ::= { diffServMIBObjects 1 }

--
-- Data Path Table
--
-- The Data Path Table enumerates the Differentiated Services
-- Functional Data Paths within this device.  Each entry in this table
-- is indexed by ifIndex and ifDirection.  Each entry provides the
-- first Differentiated Services Functional Data Path Element to
-- process data flowing along specific data path.  This table should
-- have at most two entries for each interface capable of
-- Differentiated Services processing on this device: ingress and
-- egress.

-- Note that Differentiated Services Functional Data Path Elements
-- linked together using their individual next pointers and anchored by
-- an entry of the diffServDataPathTable constitute a functional data
-- path.
--

diffServDataPathTable OBJECT-TYPE
```

```
  SYNTAX
    SEQUENCE OF DiffServDataPathEntry
  MAX-ACCESS   not-accessible
  STATUS       current



  DESCRIPTION
    "The data path table contains RowPointers indicating the start of
    the functional data path for each interface and traffic direction
    in this device. These may merge, or be separated into parallel
    data paths."
  ::= { diffServDataPath 1 }

diffServDataPathEntry OBJECT-TYPE
  SYNTAX       DiffServDataPathEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An entry in the data path table indicates the start of a single
    Differentiated Services Functional Data Path in this device.

    These are associated with individual interfaces, logical or
    physical, and therefore are instantiated by ifIndex. Therefore,
    the interface index must have been assigned, according to the
    procedures applicable to that, before it can be meaningfully
    used. Generally, this means that the interface must
 exist.

    When diffServDataPathStorage is of type nonVolatile, however,
    this may reflect the configuration for an interface whose ifIndex
    has been assigned but for which the supporting implementation is
    not currently present."
  INDEX { ifIndex, diffServDataPathIfDirection }
  ::= { diffServDataPathTable 1 }

DiffServDataPathEntry ::= SEQUENCE  {
  diffServDataPathIfDirection    IfDirection,
  diffServDataPathStart          RowPointer,
  diffServDataPathStorage        StorageType,
  diffServDataPathStatus         RowStatus
}

diffServDataPathIfDirection OBJECT-TYPE
  SYNTAX       IfDirection
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
```

"IfDirection specifies whether the reception or transmission path
for this interface is in view."
::= { diffServDataPathEntry 1 }

diffServDataPathStart OBJECT-TYPE
SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current

DESCRIPTION
"This selects the first Differentiated Services Functional Data
Path Element to handle traffic for this data path. This
RowPointer should point to an instance of one of:
diffServClfrEntry
diffServMeterEntry
diffServActionEntry
diffServAlgDropEntry
diffServQEntry

A value of zeroDotZero in this attribute indicates that no
Differentiated Services treatment is performed on traffic of this
data path. A pointer with the value zeroDotZero normally
terminates a functional data path.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or
becomes inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."
::= { diffServDataPathEntry 2 }

diffServDataPathStorage OBJECT-TYPE
SYNTAX StorageType
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The storage type for this conceptual row. Conceptual rows
having the value 'permanent' need not allow write-access to any
columnar objects in the row."
DEFVAL { nonVolatile }
::= { diffServDataPathEntry 3 }

diffServDataPathStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION

```
      "The status of this conceptual row. All writable objects in this
      row may be modified at any time."
    ::= { diffServDataPathEntry 4 }

--
-- Classifiers
--

diffServClassifier     OBJECT IDENTIFIER ::= { diffServMIBObjects 2 }

--



-- Classifier Table
--
-- The Classifier Table allows multiple classifier elements, of same or
-- different types, to be used together. A classifier must completely
-- classify all packets presented to it. This means that all traffic
-- presented to a classifier must match at least one classifier element
-- within the classifier, with the classifier element parameters
--
 specified by a filter.

-- If there is ambiguity between classifier elements of different
-- classifier, classifier linkage order indicates their precedence; the
-- first classifier in the link is applied to the traffic first.

-- Entries in the classifier element table serves as the anchor for
-- each classification pattern, defined in filter table entries.  Each
-- classifier element table entry also specifies the subsequent
-- downstream Differentiated Services Functional Data Path Element when
-- the classification pattern is satisfied. Each entry in the
-- classifier element table describes one branch of the fan-out
-- characteristic of a classifier indicated in the Informal
-- Differentiated Services Model section 4.1.  A classifier is composed
-- of one or more classifier elements.

diffServClfrNextFree OBJECT-TYPE
    SYNTAX       IndexIntegerNextFree
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
      "This object contains an unused value for diffServClfrId,
 or a
      zero to indicate that none exist."
    ::= { diffServClassifier 1 }
```

```
diffServClfrTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF DiffServClfrEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table enumerates all the diffserv classifier functional
    data path elements of this device.  The actual classification
    definitions are defined in diffServClfrElementTable entries
    belonging to each classifier.

    An entry in this table, pointed to by a RowPointer specifying an
    instance of diffServClfrStatus, is frequently used as the name
    for a set of classifier elements, which all use the index
    diffServClfrId. Per the semantics of the classifier element
    table, these entries constitute one or more unordered sets of
    tests which may be simultaneously applied to a message to



    classify it.

    The primary function of this table is to ensure that the value of
    diffServClfrId
 is unique before attempting to use it in creating
    a diffServClfrElementEntry. Therefore, the diffServClfrEntry must
    be created on the same SET as the diffServClfrElementEntry, or
    before the diffServClfrElementEntry is created."
  ::= { diffServClassifier 2 }

diffServClfrEntry OBJECT-TYPE
  SYNTAX      DiffServClfrEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An entry in the classifier table describes a single classifier.
    All classifier elements belonging to the same classifier use the
    classifier's diffServClfrId as part of their index."
  INDEX { diffServClfrId }
  ::= { diffServClfrTable 1 }

DiffServClfrEntry ::= SEQUENCE  {
  diffServClfrId             IndexInteger,
  diffServClfrStorage        StorageType,
  diffServClfrStatus         RowStatus
}

diffServClfrId OBJECT-TYPE
  SYNTAX      IndexInteger
```

```
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION

    "An index that enumerates the classifier entries.  Managers
    should obtain new values for row creation in this table by
    reading diffServClfrNextFree."
  ::= { diffServClfrEntry 1 }

diffServClfrStorage OBJECT-TYPE
  SYNTAX       StorageType
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The storage type for this conceptual row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServClfrEntry 2 }

diffServClfrStatus OBJECT-TYPE



  SYNTAX       RowStatus
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The status of this conceptual row. All writable objects in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
   ::= { diffServClfrEntry 3 }

--
-- Classifier Element Table
--
diffServClfrElementNextFree OBJECT-TYPE
  SYNTAX       IndexIntegerNextFree
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
    "This object contains an unused value for diffServClfrElementId,
    or a zero to indicate that none exist."
  ::= { diffServClassifier 3 }

diffServClfrElementTable OBJECT-TYPE
```

```
  SYNTAX      SEQUENCE OF DiffServClfrElementEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "The classifier element table enumerates the relationship between
    classification patterns and subsequent downstream Differentiated
    Services Functional Data Path elements.
    diffServClfrElementSpecific points to a filter that specifies the
    classification parameters. A classifier may use filter tables of
    different types together.

    One example of a filter table defined in this MIB is
    diffServMultiFieldClfrTable, for
IP Multi-Field Classifiers
    (MFCs). Such an entry might identify anything from a single
    micro-flow (an identifiable sub-session packet stream directed
    from one sending transport to the receiving transport or
    transports), or aggregates of those such as the traffic from a
    host, traffic for an application, or traffic between two hosts
    using an application and a given DSCP. The standard Behavior
    Aggregate used in the Differentiated Services Architecture is
    encoded as a degenerate case of such an aggregate - the traffic
    using a particular DSCP value.

    Filter tables for other filter types may be defined elsewhere."



  ::= { diffServClassifier 4 }

diffServClfrElementEntry OBJECT-TYPE
  SYNTAX      DiffServClfrElementEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An entry in the classifier element table describes a single
    element of the classifier."
  INDEX { diffServClfrId,
 diffServClfrElementId }
  ::= { diffServClfrElementTable 1 }

DiffServClfrElementEntry ::= SEQUENCE  {
  diffServClfrElementId         IndexInteger,
  diffServClfrElementPrecedence  Unsigned32,
  diffServClfrElementNext       RowPointer,
  diffServClfrElementSpecific    RowPointer,
  diffServClfrElementStorage     StorageType,
  diffServClfrElementStatus      RowStatus
```

}

diffServClfrElementId OBJECT-TYPE
  SYNTAX   IndexInteger
  MAX-ACCESS   not-accessible
  STATUS   current
  DESCRIPTION
    "An index that enumerates the Classifier Element entries.
    Managers obtain new values for row creation in this table by
    reading diffServClfrElementNextFree."
  ::= { diffServClfrElementEntry 1 }

diffServClfrElementPrecedence OBJECT-TYPE
  SYNTAX   Unsigned32 (1..4294967295)
  MAX-ACCESS   read-create
  STATUS   current
  DESCRIPTION
    "The relative order in which classifier elements are applied:
    higher numbers
 represent classifier element with higher
    precedence. Classifier elements with the same order must be
    unambiguous i.e. they must define non-overlapping patterns, and
    are considered to be applied simultaneously to the traffic
    stream. Classifier elements with different order may overlap in
    their filters: the classifier element with the highest order
    that matches is taken.

    On a given interface, there must be a complete classifier in
    place at all times in the ingress direction. This means one or
    more filters must match any possible pattern. There is no such

    requirement in the egress direction."
  ::= { diffServClfrElementEntry 2 }

diffServClfrElementNext OBJECT-TYPE
  SYNTAX   RowPointer
  MAX-ACCESS   read-create
  STATUS   current
  DESCRIPTION
    "This attribute provides one branch of the fan-out functionality
    of a classifier described in the Informal Differentiated Services

 Model section 4.1.

    This selects the next Differentiated Services Functional Data
    Path Element to handle traffic for this data path. This

RowPointer should point to an instance of one of:
diffServClfrEntry
diffServMeterEntry
diffServActionEntry
diffServAlgDropEntry
diffServQEntry

A value of zeroDotZero in this attribute indicates no further Differentiated Services treatment is performed on traffic of this data path. The use of zeroDotZero is the normal usage for the last functional data path element of the current data path.

Setting this to point to a target that does not exist results in an inconsistentValue error. If the row pointed to is removed or becomes inactive by other means, the treatment is as if this attribute contains a value of zeroDotZero."

::= { diffServClfrElementEntry 3 }

diffServClfrElementSpecific OBJECT-TYPE
SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"A pointer to a valid entry in another table, filter table, that describes the applicable classification parameters, e.g. an entry in diffServMultiFieldClfrTable.

The value zeroDotZero is interpreted to match anything not matched by another classifier element - only one such entry may exist for each classifier.

Setting this to point to a target that does not exist results in an inconsistentValue error. If the row pointed to is removed or

becomes inactive by other means, the element is ignored."
::= { diffServClfrElementEntry 4 }

diffServClfrElementStorage OBJECT-TYPE
SYNTAX StorageType
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The storage type for this conceptual row. Conceptual rows having the value 'permanent' need not allow write-access to any columnar objects in the row."

```
  DEFVAL
 { nonVolatile }
  ::= { diffServClfrElementEntry 5 }

diffServClfrElementStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The status of this conceptual row. All writable objects in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
  ::= { diffServClfrElementEntry 6 }

--
-- IP Multi-field Classification Table
--
-- Classification based on six different fields in the IP header.
-- Functional Data Paths may share definitions by using the same entry.
--

diffServMultiFieldClfrNextFree OBJECT-TYPE
  SYNTAX      IndexIntegerNextFree
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object contains an unused value for
    diffServMultiFieldClfrId, or a zero to indicate that none exist."
  ::= {
 diffServClassifier 5 }

diffServMultiFieldClfrTable OBJECT-TYPE
  SYNTAX  SEQUENCE OF DiffServMultiFieldClfrEntry
  MAX-ACCESS  not-accessible
  STATUS  current
  DESCRIPTION
    "A table of IP Multi-field Classifier filter entries that a




    system may use to identify IP traffic."
  ::= { diffServClassifier 6 }

diffServMultiFieldClfrEntry OBJECT-TYPE
  SYNTAX      DiffServMultiFieldClfrEntry
  MAX-ACCESS  not-accessible
```

```
  STATUS   current
  DESCRIPTION
    "An IP Multi-field Classifier entry describes a single filter."
  INDEX { diffServMultiFieldClfrId }
  ::= { diffServMultiFieldClfrTable 1 }

DiffServMultiFieldClfrEntry ::= SEQUENCE {
  diffServMultiFieldClfrId          IndexInteger,
  diffServMultiFieldClfrAddrType    InetAddressType,
  diffServMultiFieldClfrDstAddr     InetAddress,
  diffServMultiFieldClfrDstPrefixLength InetAddressPrefixLength,
  diffServMultiFieldClfrSrcAddr     InetAddress,
  diffServMultiFieldClfrSrcPrefixLength
 InetAddressPrefixLength,
  diffServMultiFieldClfrDscp        DscpOrAny,
  diffServMultiFieldClfrFlowId      Unsigned32,
  diffServMultiFieldClfrProtocol    Unsigned32,
  diffServMultiFieldClfrDstL4PortMin InetPortNumber,
  diffServMultiFieldClfrDstL4PortMax InetPortNumber,
  diffServMultiFieldClfrSrcL4PortMin InetPortNumber,
  diffServMultiFieldClfrSrcL4PortMax InetPortNumber,
  diffServMultiFieldClfrStorage     StorageType,
  diffServMultiFieldClfrStatus      RowStatus
}

diffServMultiFieldClfrId OBJECT-TYPE
  SYNTAX        IndexInteger
  MAX-ACCESS    not-accessible
  STATUS    current
  DESCRIPTION
    "An index that enumerates the MultiField Classifier filter
    entries.  Managers obtain new values for row creation in this
    table by reading diffServMultiFieldClfrNextFree."

  ::= { diffServMultiFieldClfrEntry 1 }

diffServMultiFieldClfrAddrType OBJECT-TYPE
  SYNTAX        InetAddressType
  MAX-ACCESS    read-create

  STATUS        current
  DESCRIPTION
    "The type of IP address used by this classifier entry.  While
    other types of addresses are defined in the InetAddressType



    textual convention, and DNS names, a classifier can only look at
```

```
    packets on the wire. Therefore, this object is limited to IPv4
    and IPv6 addresses."
  ::= { diffServMultiFieldClfrEntry 2 }

diffServMultiFieldClfrDstAddr OBJECT-TYPE
  SYNTAX        InetAddress
  MAX-ACCESS    read-create
  STATUS        current
  DESCRIPTION
    "The IP address to match against the packet's destination IP
    address. This may not be a DNS name, but may be an IPv4 or IPv6
    prefix.  diffServMultiFieldClfrDstPrefixLength indicates the
    number of bits that are relevant."
  ::= { diffServMultiFieldClfrEntry 3 }

diffServMultiFieldClfrDstPrefixLength OBJECT-TYPE
  SYNTAX        InetAddressPrefixLength
  UNITS         "bits"
  MAX-ACCESS    read-create
  STATUS
 current
  DESCRIPTION
    "The length of the CIDR Prefix carried in
    diffServMultiFieldClfrDstAddr. In IPv4 addresses, a length of 0
    indicates a match of any address; a length of 32 indicates a
    match of a single host address, and a length between 0 and 32
    indicates the use of a CIDR Prefix. IPv6 is similar, except that
    prefix lengths range from 0..128."
  DEFVAL        { 0 }
  ::= { diffServMultiFieldClfrEntry 4 }

diffServMultiFieldClfrSrcAddr OBJECT-TYPE
  SYNTAX        InetAddress
  MAX-ACCESS    read-create
  STATUS        current
  DESCRIPTION
    "The IP address to match against the packet's source IP address.
    This may not be a DNS name, but may be an IPv4 or IPv6 prefix.
    diffServMultiFieldClfrSrcPrefixLength indicates the number of
    bits that are relevant."
  ::= { diffServMultiFieldClfrEntry 5 }

diffServMultiFieldClfrSrcPrefixLength OBJECT-TYPE
  SYNTAX        InetAddressPrefixLength
  UNITS
       "bits"
  MAX-ACCESS    read-create
  STATUS        current
```

```
    DESCRIPTION


        "The length of the CIDR Prefix carried in
        diffServMultiFieldClfrSrcAddr. In IPv4 addresses, a length of 0
        indicates a match of any address; a length of 32 indicates a
        match of a single host address, and a length between 0 and 32
        indicates the use of a CIDR Prefix. IPv6 is similar, except that
        prefix lengths range from 0..128."
    DEFVAL      { 0 }
    ::= { diffServMultiFieldClfrEntry 6 }

diffServMultiFieldClfrDscp OBJECT-TYPE
    SYNTAX      DscpOrAny
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The value that the DSCP in the packet must have to match this
        entry. A value of -1 indicates that a specific DSCP value has not
        been defined and thus all DSCP values are considered a match."
    DEFVAL      { -1 }
    ::= { diffServMultiFieldClfrEntry 7 }

diffServMultiFieldClfrFlowId OBJECT-TYPE

   SYNTAX      Unsigned32 (0..1048575)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The flow identifier in an IPv6 header."
    ::= { diffServMultiFieldClfrEntry 8 }

diffServMultiFieldClfrProtocol OBJECT-TYPE
    SYNTAX      Unsigned32 (0..255)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        "The IP protocol to match against the IPv4 protocol number or the
        IPv6 Next- Header number in the packet. A value of 255 means
        match all.  Note the protocol number of 255 is reserved by IANA,
        and Next-Header number of 0 is used in IPv6."
    DEFVAL      { 255 }
    ::= { diffServMultiFieldClfrEntry 9 }

diffServMultiFieldClfrDstL4PortMin OBJECT-TYPE
    SYNTAX      InetPortNumber
    MAX-ACCESS  read-create
```

```
  STATUS        current
  DESCRIPTION
    "The minimum value that the layer-4 destination port number in
    the packet must have in order to match this classifier entry."
  DEFVAL
      { 0 }



  ::= { diffServMultiFieldClfrEntry 10 }

diffServMultiFieldClfrDstL4PortMax OBJECT-TYPE
  SYNTAX        InetPortNumber
  MAX-ACCESS    read-create
  STATUS        current
  DESCRIPTION
    "The maximum value that the layer-4 destination port number in
    the packet must have in order to match this classifier entry.
    This value must be equal to or greater than the value specified
    for this entry in diffServMultiFieldClfrDstL4PortMin."
  DEFVAL        { 65535 }
  ::= { diffServMultiFieldClfrEntry 11 }

diffServMultiFieldClfrSrcL4PortMin OBJECT-TYPE
  SYNTAX        InetPortNumber
  MAX-ACCESS    read-create
  STATUS        current
  DESCRIPTION
    "The minimum value that the layer-4 source port number in the
    packet must have in order to match this classifier entry."
  DEFVAL        { 0 }
  ::= { diffServMultiFieldClfrEntry 12 }

diffServMultiFieldClfrSrcL4PortMax OBJECT-TYPE
  SYNTAX        InetPortNumber
   MAX-ACCESS    read-create
  STATUS        current
  DESCRIPTION
    "The maximum value that the layer-4 source port number in the
    packet must have in order to match this classifier entry. This
    value must be equal to or greater than the value specified for
    this entry in diffServMultiFieldClfrSrcL4PortMin."
  DEFVAL        { 65535 }
  ::= { diffServMultiFieldClfrEntry 13 }

diffServMultiFieldClfrStorage OBJECT-TYPE
  SYNTAX       StorageType
  MAX-ACCESS   read-create
```

```
  STATUS       current
  DESCRIPTION
    "The storage type for this conceptual row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServMultiFieldClfrEntry 14 }

diffServMultiFieldClfrStatus OBJECT-TYPE



  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The status of this conceptual row. All writable objects
 in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
  ::= { diffServMultiFieldClfrEntry 15 }

--
-- Meters
--

diffServMeter         OBJECT IDENTIFIER ::= { diffServMIBObjects 3 }

--
-- This MIB supports a variety of Meters.  It includes a specific
-- definition for Token Bucket Meter, which are but one type of
-- specification. Other metering parameter sets can be defined in other
-- MIBs.

-- Multiple meter elements may be logically cascaded using their
-- diffServMeterSucceedNext and diffServMeterFailNext pointers if
-- required. One example of this might be for an AF PHB implementation
-- that uses multiple level conformance meters.

-- Cascading of individual meter elements in the MIB is intended to be
-- functionally equivalent to multiple level conformance determination
-- of a packet.
 The sequential nature of the representation is merely
-- a notational convenience for this MIB.

-- srTCM meters (RFC 2697) can be specified using two sets of
```

```
-- diffServMeterEntry and diffServTBParamEntry. The first set specifies
-- the Committed Information Rate and Committed Burst Size
-- token-bucket.  The second set specifies the Excess Burst Size
-- token-bucket.

-- trTCM meters (RFC 2698) can be specified using two sets of
-- diffServMeterEntry and diffServTBParamEntry. The first set specifies
-- the Committed Information Rate and Committed Burst Size
-- token-bucket.  The second set specifies the Peak Information Rate
-- and Peak Burst Size token-bucket.

-- tswTCM meters (RFC 2859) can be specified using two sets of
-- diffServMeterEntry and diffServTBParamEntry. The first set specifies
-- the Committed Target Rate token-bucket.  The second set specifies




-- the Peak Target Rate token-bucket. diffServTBParamInterval in each
-- token bucket reflects the Average Interval.
--

diffServMeterNextFree
 OBJECT-TYPE
   SYNTAX       IndexIntegerNextFree
   MAX-ACCESS   read-only
   STATUS       current
   DESCRIPTION
     "This object contains an unused value for diffServMeterId, or a
     zero to indicate that none exist."
   ::= { diffServMeter 1 }

diffServMeterTable OBJECT-TYPE
   SYNTAX       SEQUENCE OF DiffServMeterEntry
   MAX-ACCESS   not-accessible
   STATUS       current
   DESCRIPTION
     "This table enumerates specific meters that a system may use to
     police a stream of traffic. The traffic stream to be metered is
     determined by the Differentiated Services Functional Data Path
     Element(s) upstream of the meter i.e. by the object(s) that point
     to each entry in this table.  This may include all traffic on an
     interface.

     Specific meter details are to be found in table entry referenced
     by diffServMeterSpecific."
   ::= { diffServMeter 2 }

diffServMeterEntry OBJECT-TYPE
```

```
  SYNTAX       DiffServMeterEntry
   MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An entry in the meter table describes a single conformance level
    of a meter."
  INDEX { diffServMeterId }
  ::= { diffServMeterTable 1 }

DiffServMeterEntry ::= SEQUENCE  {
  diffServMeterId              IndexInteger,
  diffServMeterSucceedNext      RowPointer,
  diffServMeterFailNext         RowPointer,
  diffServMeterSpecific         RowPointer,
  diffServMeterStorage          StorageType,
  diffServMeterStatus           RowStatus
}




diffServMeterId OBJECT-TYPE
  SYNTAX       IndexInteger
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An index that enumerates the Meter entries.  Managers obtain new
    values for row creation in this table by reading
    diffServMeterNextFree."
  ::= { diffServMeterEntry 1 }

diffServMeterSucceedNext OBJECT-TYPE
  SYNTAX       RowPointer
  MAX-ACCESS   read-create
  STATUS
   current
  DESCRIPTION
    "If the traffic does conform, this selects the next
    Differentiated Services Functional Data Path element to handle
    traffic for this data path. This RowPointer should point to an
    instance of one of:
      diffServClfrEntry
      diffServMeterEntry
      diffServActionEntry
      diffServAlgDropEntry
      diffServQEntry

    A value of zeroDotZero in this attribute indicates that no
```

further Differentiated Services treatment is performed on traffic of this data path. The use of zeroDotZero is the normal usage for the last functional data path element of the current data path.

Setting this to point to a target that does not exist results in an inconsistentValue error. If the row pointed to is removed or becomes inactive by other means, the treatment is as if this attribute contains a value of zeroDotZero."

DEFVAL { zeroDotZero }

::= { diffServMeterEntry 2 }

diffServMeterFailNext OBJECT-TYPE

SYNTAX RowPointer

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"If the traffic does not conform, this selects the next Differentiated Services Functional Data Path element to handle traffic for this data path. This RowPointer should point to an instance of one of:

diffServClfrEntry

diffServMeterEntry

diffServActionEntry

diffServAlgDropEntry

diffServQEntry

A value of zeroDotZero in this attribute indicates no further Differentiated Services treatment is performed on traffic of this data path. The use of zeroDotZero is the normal usage for the last functional data path element of the current data path.

Setting this to point to a target that does not exist results in an inconsistentValue error. If the row pointed to is removed or becomes inactive by other means, the treatment is as if this attribute contains a value of zeroDotZero."

DEFVAL { zeroDotZero }

::= { diffServMeterEntry 3 }

diffServMeterSpecific OBJECT-TYPE

SYNTAX RowPointer

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This indicates the behavior of the meter by pointing to an entry

```
      containing detailed parameters. Note that entries in that
      specific table must be managed explicitly.

      For example, diffServMeterSpecific may point to an entry in
      diffServTBParamTable, which contains an instance of a single set
      of Token Bucket parameters.

      Setting this to point to a target that does not exist results in
      an inconsistentValue error.  If the row pointed to is removed or
      becomes inactive by other means, the meter always succeeds."
    ::= { diffServMeterEntry 4 }

diffServMeterStorage OBJECT-TYPE
    SYNTAX       StorageType
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
      "The
   storage type for this conceptual row.  Conceptual rows
      having the value 'permanent' need not allow write-access to any
      columnar objects in the row."
    DEFVAL { nonVolatile }
    ::= { diffServMeterEntry 5 }

diffServMeterStatus OBJECT-TYPE
    SYNTAX       RowStatus
    MAX-ACCESS   read-create




    STATUS       current
    DESCRIPTION
      "The status of this conceptual row. All writable objects in this
      row may be modified at any time. Setting this variable to
      'destroy' when the MIB contains one or more RowPointers pointing
      to it results in destruction being delayed until the row is no
      longer used."
    ::= { diffServMeterEntry 6 }

--
-- Token Bucket Parameter Table
--

diffServTBParam        OBJECT IDENTIFIER ::= { diffServMIBObjects 4 }

-- Each entry in the Token Bucket Parameter Table parameterize a single
-- token bucket.  Multiple token buckets can be used together to
-- parameterize multiple levels of conformance.
```

```
-- Note that
 an entry in the Token Bucket Parameter Table can be shared
-- by multiple diffServMeterTable entries.
--

diffServTBParamNextFree OBJECT-TYPE
  SYNTAX       IndexIntegerNextFree
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
    "This object contains an unused value for diffServTBParamId, or a
    zero to indicate that none exist."
  ::= { diffServTBParam 1 }

diffServTBParamTable OBJECT-TYPE
  SYNTAX       SEQUENCE OF DiffServTBParamEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "This table enumerates a single set of token bucket meter
    parameters that a system may use to police a stream of traffic.
    Such meters are modeled here as having a single rate and a single
    burst size. Multiple entries are used when multiple rates/burst
    sizes are needed."
  ::= { diffServTBParam 2 }

diffServTBParamEntry OBJECT-TYPE
  SYNTAX       DiffServTBParamEntry
  MAX-ACCESS   not-accessible
  STATUS
     current



  DESCRIPTION
    "An entry that describes a single set of token bucket
    parameters."
  INDEX { diffServTBParamId }
  ::= { diffServTBParamTable 1 }

DiffServTBParamEntry ::= SEQUENCE  {
  diffServTBParamId             IndexInteger,
  diffServTBParamType           AutonomousType,
  diffServTBParamRate           Unsigned32,
  diffServTBParamBurstSize      BurstSize,
  diffServTBParamInterval       Unsigned32,
  diffServTBParamStorage        StorageType,
```

```
  diffServTBParamStatus         RowStatus
}

diffServTBParamId OBJECT-TYPE
  SYNTAX       IndexInteger
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An index that enumerates the Token Bucket Parameter entries.
    Managers obtain new values for row creation in this table by
    reading diffServTBParamNextFree."
  ::= { diffServTBParamEntry 1 }

diffServTBParamType OBJECT-TYPE
  SYNTAX       AutonomousType
  MAX-ACCESS   read-create

  STATUS       current
  DESCRIPTION
    "The Metering algorithm associated with the Token Bucket
    parameters.  zeroDotZero indicates this is unknown.

    Standard values for generic algorithms:
    diffServTBParamSimpleTokenBucket, diffServTBParamAvgRate,
    diffServTBParamSrTCMBlind, diffServTBParamSrTCMAware,
    diffServTBParamTrTCMBlind, diffServTBParamTrTCMAware, and
    diffServTBParamTswTCM are specified in this MIB as OBJECT-
    IDENTITYs; additional values may be further specified in other
    MIBs."
  ::= { diffServTBParamEntry 2 }

diffServTBParamRate OBJECT-TYPE
  SYNTAX       Unsigned32  (1..4294967295)
  UNITS        "kilobits per second"
  MAX-ACCESS   read-create
  STATUS       current



  DESCRIPTION
    "The token-bucket rate, in kilobits per second (kbps). This
    attribute is used for:
    1. CIR in RFC 2697 for srTCM
    2. CIR and PIR in RFC 2698 for trTCM
    3. CTR and PTR in RFC 2859 for TSWTCM

    4. AverageRate in RFC 3290."
  ::= { diffServTBParamEntry 3 }
```

```
diffServTBParamBurstSize OBJECT-TYPE
  SYNTAX      BurstSize
  UNITS       "Bytes"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The maximum number of bytes in a single transmission burst. This
    attribute is used for:
    1. CBS and EBS in RFC 2697 for srTCM
    2. CBS and PBS in RFC 2698 for trTCM
    3. Burst Size in RFC 3290."
  ::= { diffServTBParamEntry 4 }

diffServTBParamInterval OBJECT-TYPE
  SYNTAX      Unsigned32 (1..4294967295)
  UNITS       "microseconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The time interval used with the token bucket.  For:
    1. Average Rate Meter, the Informal Differentiated Services Model
      section 5.2.1, - Delta.
    2. Simple Token Bucket Meter, the Informal Differentiated
      Services Model section 5.1, - time interval t.
    3. RFC 2859 TSWTCM, - AVG_INTERVAL.
     4. RFC 2697 srTCM, RFC 2698 trTCM, - token bucket update time
      interval."
  ::= { diffServTBParamEntry 5 }

diffServTBParamStorage OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The storage type for this conceptual row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServTBParamEntry 6 }



diffServTBParamStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
```

```
      "The status of this conceptual row. All writable objects in this
      row may be modified at any time. Setting this variable to
      'destroy' when the MIB contains one or more RowPointers pointing
      to it results in destruction being delayed until the row is no
      longer used."
    ::= { diffServTBParamEntry 7 }

--
-- OIDs for diffServTBParamType
 definitions.
--

diffServTBMeters  OBJECT IDENTIFIER ::= { diffServMIBAdmin 1 }

diffServTBParamSimpleTokenBucket OBJECT-IDENTITY
    STATUS       current
    DESCRIPTION
      "Two Parameter Token Bucket Meter as described in the Informal
      Differentiated Services Model section 5.2.3."
    ::= { diffServTBMeters 1 }

diffServTBParamAvgRate OBJECT-IDENTITY
    STATUS       current
    DESCRIPTION
      "Average Rate Meter as described in the Informal Differentiated
      Services Model section 5.2.1."
    ::= { diffServTBMeters 2 }

diffServTBParamSrTCMBlind OBJECT-IDENTITY
    STATUS       current
    DESCRIPTION
      "Single Rate Three Color Marker Metering as defined by RFC 2697,
      in the `Color Blind' mode as described by the RFC."
    REFERENCE
       "RFC 2697"
    ::= { diffServTBMeters 3 }

diffServTBParamSrTCMAware OBJECT-IDENTITY
    STATUS       current
    DESCRIPTION
      "Single Rate Three Color Marker Metering as defined by RFC 2697,
      in the
 `Color Aware' mode as described by the RFC."
    REFERENCE
       "RFC 2697"
```

```
  ::= { diffServTBMeters 4 }

diffServTBParamTrTCMBlind OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "Two Rate Three Color Marker Metering as defined by RFC 2698, in
    the `Color Blind' mode as described by the RFC."
  REFERENCE
     "RFC 2698"
  ::= { diffServTBMeters 5 }

diffServTBParamTrTCMAware OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "Two Rate Three Color Marker Metering as defined by RFC 2698, in
    the `Color Aware' mode as described by the RFC."
  REFERENCE
     "RFC 2698"
  ::= { diffServTBMeters 6 }

diffServTBParamTswTCM OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "Time Sliding Window Three Color Marker Metering as defined by
    RFC 2859."
  REFERENCE
     "RFC 2859"
  ::= { diffServTBMeters 7 }

--
-- Actions
--

diffServAction        OBJECT IDENTIFIER ::= { diffServMIBObjects 5 }

--
-- The Action
 Table allows enumeration of the different types of
-- actions to be applied to a traffic flow.
--

diffServActionNextFree OBJECT-TYPE
  SYNTAX       IndexIntegerNextFree
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
    "This object contains an unused value for diffServActionId, or a
    zero to indicate that none exist."
```

```
  ::= { diffServAction 1 }


diffServActionTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF DiffServActionEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "The Action Table enumerates actions that can be performed to a
    stream of traffic. Multiple actions can be concatenated. For
    example, traffic exiting from a meter may be counted, marked, and
    potentially dropped before entering a queue.

    Specific actions are indicated by diffServActionSpecific which
    points to an entry of a specific action type parameterizing the
    action in detail."
  ::= { diffServAction
 2 }

diffServActionEntry OBJECT-TYPE
  SYNTAX      DiffServActionEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "Each entry in the action table allows description of one
    specific action to be applied to traffic."
  INDEX { diffServActionId }
  ::= { diffServActionTable 1 }

DiffServActionEntry ::= SEQUENCE  {
  diffServActionId             IndexInteger,
  diffServActionInterface      InterfaceIndexOrZero,
  diffServActionNext           RowPointer,
  diffServActionSpecific       RowPointer,
  diffServActionStorage        StorageType,
  diffServActionStatus         RowStatus
}

diffServActionId OBJECT-TYPE
  SYNTAX      IndexInteger
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An index that enumerates the Action entries.  Managers obtain
    new values for row creation in this table by reading
    diffServActionNextFree."
  ::= { diffServActionEntry 1 }
```

```
diffServActionInterface
  OBJECT-TYPE
    SYNTAX        InterfaceIndexOrZero
    MAX-ACCESS    read-create
    STATUS        current



    DESCRIPTION
      "The interface index (value of ifIndex) that this action occurs
      on. This may be derived from the diffServDataPathStartEntry's
      index by extension through the various RowPointers. However, as
      this may be difficult for a network management station, it is
      placed here as well.  If this is indeterminate, the value is
      zero.

      This is of especial relevance when reporting the counters which
      may apply to traffic crossing an interface:
        diffServCountActOctets,
        diffServCountActPkts,
        diffServAlgDropOctets,
        diffServAlgDropPkts,
        diffServAlgRandomDropOctets, and
        diffServAlgRandomDropPkts.

      It is also especially relevant to the queue and scheduler which
      may be subsequently applied."
    ::= { diffServActionEntry 2 }

diffServActionNext
 OBJECT-TYPE
   SYNTAX       RowPointer
   MAX-ACCESS   read-create
   STATUS       current
   DESCRIPTION
     "This selects the next Differentiated Services Functional Data
     Path Element to handle traffic for this data path. This
     RowPointer should point to an instance of one of:
       diffServClfrEntry
       diffServMeterEntry
       diffServActionEntry
       diffServAlgDropEntry
       diffServQEntry

     A value of zeroDotZero in this attribute indicates no further
     Differentiated Services treatment is performed on traffic of this
     data path. The use of zeroDotZero is the normal usage for the
```

last functional data path element of the current data path.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or
becomes inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."
DEFVAL
{ zeroDotZero }
::= { diffServActionEntry 3 }

diffServActionSpecific OBJECT-TYPE

SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"A pointer to an object instance providing additional information
for the type of action indicated by this action table entry.

For the standard actions defined by this MIB module, this should
point to either a diffServDscpMarkActEntry or a
diffServCountActEntry. For other actions, it may point to an
object instance defined in some other MIB.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or
becomes inactive by other means, the Meter should be treated as
if it were not present. This may lead to incorrect policy
behavior."
::= { diffServActionEntry 4 }

diffServActionStorage OBJECT-TYPE
SYNTAX StorageType
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The storage type for this conceptual row. Conceptual rows
having the value 'permanent' need not allow write-access to any
columnar objects in the row."
DEFVAL { nonVolatile }
::= { diffServActionEntry 5 }

diffServActionStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current

```
  DESCRIPTION
    "The status of this conceptual row. All writable objects in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
  ::= { diffServActionEntry 6 }

-- DSCP Mark Action Table
--
-- Rows of this table are pointed to by diffServActionSpecific to
-- provide detailed parameters specific to the DSCP Mark action.
--
-- A single entry in this table can be shared by multiple




-- diffServActionTable entries.
--

diffServDscpMarkActTable
 OBJECT-TYPE
  SYNTAX      SEQUENCE OF DiffServDscpMarkActEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table enumerates specific DSCPs used for marking or
    remarking the DSCP field of IP packets. The entries of this table
    may be referenced by a diffServActionSpecific attribute."
  ::= { diffServAction 3 }

diffServDscpMarkActEntry OBJECT-TYPE
  SYNTAX      DiffServDscpMarkActEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An entry in the DSCP mark action table that describes a single
    DSCP used for marking."
  INDEX { diffServDscpMarkActDscp }
  ::= { diffServDscpMarkActTable 1 }

DiffServDscpMarkActEntry ::= SEQUENCE  {
  diffServDscpMarkActDscp         Dscp
}

diffServDscpMarkActDscp OBJECT-TYPE
  SYNTAX      Dscp
  MAX-ACCESS  read-only
```

```
  STATUS       current
  DESCRIPTION
     "The DSCP that this Action will store into
 the DSCP field of the
     subject. It is quite possible that the only packets subject to
     this Action are already marked with this DSCP. Note also that
     Differentiated Services processing may result in packet being
     marked on both ingress to a network and on egress from it, and
     that ingress and egress can occur in the same router."
  ::= { diffServDscpMarkActEntry 1 }

--
-- Count Action Table
--
-- Because the MIB structure allows multiple cascading
-- diffServActionEntry be used to describe multiple actions for a data
-- path, the counter became an optional action type.  In normal
-- implementation, either a data path has counters or it does not, as
-- opposed to being configurable. The management entity may choose to




-- read the counter or not.  Hence it is recommended for implementation
-- that have counters to always configure the count action as the first
-- of multiple actions.
--

diffServCountActNextFree OBJECT-TYPE
  SYNTAX       IndexIntegerNextFree
   MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
     "This object contains an unused value for
     diffServCountActId, or a zero to indicate that none exist."
  ::= { diffServAction 4 }

diffServCountActTable OBJECT-TYPE
  SYNTAX       SEQUENCE OF DiffServCountActEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
     "This table contains counters for all the traffic passing through
     an action element."
  ::= { diffServAction 5 }

diffServCountActEntry OBJECT-TYPE
  SYNTAX       DiffServCountActEntry
  MAX-ACCESS   not-accessible
```

```
  STATUS       current
  DESCRIPTION
    "An entry in the count action table describes a single set of
    traffic counters."
  INDEX { diffServCountActId }
  ::= { diffServCountActTable 1 }

DiffServCountActEntry ::= SEQUENCE  {
  diffServCountActId          IndexInteger,
  diffServCountActOctets      Counter64,
  diffServCountActPkts        Counter64,

  diffServCountActStorage     StorageType,
  diffServCountActStatus      RowStatus
}

diffServCountActId OBJECT-TYPE
  SYNTAX       IndexInteger
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An index that enumerates the Count Action entries.  Managers
    obtain new values for row creation in this table by reading




    diffServCountActNextFree."
  ::= { diffServCountActEntry 1 }

diffServCountActOctets OBJECT-TYPE
  SYNTAX       Counter64
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
    "The number of octets at the Action data path element.

    Discontinuities in the value of this counter can occur at re-
    initialization of the management system and at other times as
    indicated by the value of ifCounterDiscontinuityTime on the
    relevant interface."
  ::= { diffServCountActEntry 2 }

diffServCountActPkts OBJECT-TYPE
  SYNTAX       Counter64
  MAX-ACCESS   read-only
  STATUS
 current
  DESCRIPTION
```

```
      "The number of packets at the Action data path element.

      Discontinuities in the value of this counter can occur at re-
      initialization of the management system and at other times as
      indicated by the value of ifCounterDiscontinuityTime on the
      relevant interface."
    ::= { diffServCountActEntry 3 }

diffServCountActStorage OBJECT-TYPE
    SYNTAX      StorageType
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "The storage type for this conceptual row.  Conceptual rows
      having the value 'permanent' need not allow write-access to any
      columnar objects in the row."
    DEFVAL { nonVolatile }
    ::= { diffServCountActEntry 4 }

diffServCountActStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "The status of this conceptual row. All writable objects in this
      row may be modified at any time. Setting this variable to
       'destroy' when the MIB contains one or more RowPointers pointing




      to it results in destruction being delayed until the row is no
      longer used."
    ::= { diffServCountActEntry 5 }

--
-- Algorithmic Drop Table
--

diffServAlgDrop       OBJECT IDENTIFIER ::= { diffServMIBObjects 6 }

diffServAlgDropNextFree OBJECT-TYPE
    SYNTAX      IndexIntegerNextFree
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "This object contains an unused value for diffServAlgDropId, or a
      zero to indicate that none exist."
    ::= { diffServAlgDrop 1 }
```

```
diffServAlgDropTable OBJECT-TYPE
  SYNTAX       SEQUENCE OF DiffServAlgDropEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "The algorithmic drop table contains entries describing an
    element that drops packets according to some algorithm."
  ::= { diffServAlgDrop 2 }

diffServAlgDropEntry OBJECT-TYPE
  SYNTAX       DiffServAlgDropEntry
  MAX-ACCESS
  not-accessible
  STATUS       current
  DESCRIPTION
    "An entry describes a process that drops packets according to
    some algorithm. Further details of the algorithm type are to be
    found in diffServAlgDropType and with more detail parameter entry
    pointed to by diffServAlgDropSpecific when necessary."
  INDEX { diffServAlgDropId }
  ::= { diffServAlgDropTable 1 }

DiffServAlgDropEntry ::= SEQUENCE  {
  diffServAlgDropId              IndexInteger,
  diffServAlgDropType            INTEGER,
  diffServAlgDropNext            RowPointer,
  diffServAlgDropQMeasure        RowPointer,
  diffServAlgDropQThreshold      Unsigned32,
  diffServAlgDropSpecific        RowPointer,
  diffServAlgDropOctets          Counter64,



  diffServAlgDropPkts            Counter64,
  diffServAlgRandomDropOctets    Counter64,
  diffServAlgRandomDropPkts      Counter64,
  diffServAlgDropStorage         StorageType,
  diffServAlgDropStatus
 RowStatus
}

diffServAlgDropId OBJECT-TYPE
  SYNTAX       IndexInteger
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An index that enumerates the Algorithmic Dropper entries.
```

Managers obtain new values for row creation in this table by
reading diffServAlgDropNextFree."
::= { diffServAlgDropEntry 1 }

diffServAlgDropType OBJECT-TYPE
SYNTAX INTEGER {
other(1),
tailDrop(2),
headDrop(3),
randomDrop(4),
alwaysDrop(5)
}
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The type of algorithm used by this dropper. The value other(1)
requires further specification in some other MIB module.

In the tailDrop(2) algorithm, diffServAlgDropQThreshold
represents the maximum depth of the queue, pointed to by
diffServAlgDropQMeasure, beyond which all newly arriving packets

will be dropped.

In the headDrop(3) algorithm, if a packet arrives when the
current depth of the queue, pointed to by
diffServAlgDropQMeasure, is at diffServAlgDropQThreshold, packets
currently at the head of the queue are dropped to make room for
the new packet to be enqueued at the tail of the queue.

In the randomDrop(4) algorithm, on packet arrival, an Active
Queue Management algorithm is executed which may randomly drop a
packet. This algorithm may be proprietary, and it may drop either
the arriving packet or another packet in the queue.
diffServAlgDropSpecific points to a diffServRandomDropEntry that
describes the algorithm. For this algorithm,

diffServAlgDropQThreshold is understood to be the absolute
maximum size of the queue and additional parameters are described
in diffServRandomDropTable.

The alwaysDrop(5) algorithm is as its name specifies; always
drop. In
this case, the other configuration values in this Entry
are not meaningful; There is no useful 'next' processing step,
there is no queue, and parameters describing the queue are not

useful. Therefore, diffServAlgDropNext, diffServAlgDropMeasure,
and diffServAlgDropSpecific are all zeroDotZero."
::= { diffServAlgDropEntry 2 }

diffServAlgDropNext OBJECT-TYPE
SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This selects the next Differentiated Services Functional Data
Path Element to handle traffic for this data path. This
RowPointer should point to an instance of one of:
diffServClfrEntry
diffServMeterEntry
diffServActionEntry
diffServQEntry

A value of zeroDotZero in this attribute indicates no further
Differentiated Services treatment is performed on traffic of this
data path. The use of zeroDotZero is the normal usage for the
last functional data path element of the current data path.

When diffServAlgDropType is alwaysDrop(5), this object is
ignored.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or
becomes inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."
::= { diffServAlgDropEntry 3 }

diffServAlgDropQMeasure OBJECT-TYPE
SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"Points to an entry in the diffServQTable to indicate the queue
that a drop algorithm is to monitor when deciding whether to drop
a packet. If the row pointed to does not exist, the algorithmic
dropper element is considered inactive.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or
becomes
inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."

::= { diffServAlgDropEntry 4 }

diffServAlgDropQThreshold OBJECT-TYPE
SYNTAX Unsigned32 (1..4294967295)
UNITS "Bytes"
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"A threshold on the depth in bytes of the queue being measured at
which a trigger is generated to the dropping algorithm, unless
diffServAlgDropType is alwaysDrop(5) where this object is
ignored.

For the tailDrop(2) or headDrop(3) algorithms, this represents
the depth of the queue, pointed to by diffServAlgDropQMeasure, at
which the drop action will take place. Other algorithms will need
to define their own semantics for this threshold."
::= { diffServAlgDropEntry 5 }

diffServAlgDropSpecific OBJECT-TYPE
SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION

"Points to a table entry that provides further detail regarding a
drop algorithm.

Entries with diffServAlgDropType equal to other(1) may have this
point to a table defined in another MIB module.

Entries with diffServAlgDropType equal to randomDrop(4) must have
this point to an entry in diffServRandomDropTable.

For all other algorithms specified in this MIB, this should take
the value zeroDotZero.

The diffServAlgDropType is authoritative for the type of the drop
algorithm and the specific parameters for the drop algorithm
needs to be evaluated based on the diffServAlgDropType.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or
becomes inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."

::= { diffServAlgDropEntry 6 }

diffServAlgDropOctets OBJECT-TYPE
SYNTAX
Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of octets that have been deterministically dropped by this drop process.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the value of ifCounterDiscontinuityTime on the relevant interface."
::= { diffServAlgDropEntry 7 }

diffServAlgDropPkts OBJECT-TYPE
SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of packets that have been deterministically dropped by this drop process.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the value of ifCounterDiscontinuityTime on the relevant interface."
::= { diffServAlgDropEntry 8 }

diffServAlgRandomDropOctets OBJECT-TYPE

SYNTAX Counter64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of octets that have been randomly dropped by this drop process. This counter applies, therefore, only to random droppers.

Discontinuities in the value of this counter can occur at re-initialization of the management system and at other times as indicated by the value of ifCounterDiscontinuityTime on the relevant interface."
::= { diffServAlgDropEntry 9 }

diffServAlgRandomDropPkts OBJECT-TYPE

```
  SYNTAX      Counter64
  MAX-ACCESS  read-only



  STATUS      current
  DESCRIPTION
    "The number of packets that have been randomly dropped by this
    drop process. This counter applies, therefore, only to random
    droppers.

    Discontinuities in the value of this counter can occur at re-
    initialization of the management system and at other times as
    indicated by the value of ifCounterDiscontinuityTime
 on the
    relevant interface."
  ::= { diffServAlgDropEntry 10 }

diffServAlgDropStorage OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The storage type for this conceptual row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServAlgDropEntry 11 }

diffServAlgDropStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The status of this conceptual row. All writable objects in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
  ::= { diffServAlgDropEntry 12 }

--
-- Random Drop Table
--

diffServRandomDropNextFree OBJECT-TYPE
  SYNTAX
```

```
    IndexIntegerNextFree
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
    "This object contains an unused value for diffServRandomDropId,
    or a zero to indicate that none exist."
  ::= { diffServAlgDrop 3 }



diffServRandomDropTable OBJECT-TYPE
  SYNTAX       SEQUENCE OF DiffServRandomDropEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "The random drop table contains entries describing a process that
    drops packets randomly. Entries in this table are pointed to by
    diffServAlgDropSpecific."
  ::= { diffServAlgDrop 4 }

diffServRandomDropEntry OBJECT-TYPE
  SYNTAX       DiffServRandomDropEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "An entry describes a process that drops packets according to a
    random algorithm."
  INDEX { diffServRandomDropId }
  ::= { diffServRandomDropTable 1 }

DiffServRandomDropEntry ::= SEQUENCE  {
  diffServRandomDropId
            IndexInteger,
  diffServRandomDropMinThreshBytes   Unsigned32,
  diffServRandomDropMinThreshPkts    Unsigned32,
  diffServRandomDropMaxThreshBytes   Unsigned32,
  diffServRandomDropMaxThreshPkts    Unsigned32,
  diffServRandomDropProbMax          Unsigned32,
  diffServRandomDropWeight           Unsigned32,
  diffServRandomDropSamplingRate     Unsigned32,
  diffServRandomDropStorage          StorageType,
  diffServRandomDropStatus           RowStatus
}

diffServRandomDropId OBJECT-TYPE
  SYNTAX       IndexInteger
  MAX-ACCESS   not-accessible
```

```
  STATUS       current
  DESCRIPTION
    "An index that enumerates the Random Drop entries.  Managers
    obtain new values for row creation in this table by reading
    diffServRandomDropNextFree."
  ::= { diffServRandomDropEntry 1 }

diffServRandomDropMinThreshBytes OBJECT-TYPE
  SYNTAX       Unsigned32  (1..4294967295)
  UNITS        "bytes"
  MAX-ACCESS   read-create
  STATUS       current



   DESCRIPTION
    "The average queue depth in bytes, beyond which traffic has a
    non-zero probability of being dropped. Changes in this variable
    may or may not be reflected in the reported value of
    diffServRandomDropMinThreshPkts."
  ::= { diffServRandomDropEntry 2 }

diffServRandomDropMinThreshPkts OBJECT-TYPE
  SYNTAX       Unsigned32  (1..4294967295)
  UNITS        "packets"
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The average queue depth in packets, beyond which traffic has a
    non-zero probability of being dropped. Changes in this variable
    may or may not be reflected in the reported value of
    diffServRandomDropMinThreshBytes."
  ::= { diffServRandomDropEntry 3 }

diffServRandomDropMaxThreshBytes OBJECT-TYPE
  SYNTAX       Unsigned32  (1..4294967295)
  UNITS        "bytes"
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The average queue depth beyond which
 traffic has a probability
    indicated by diffServRandomDropProbMax of being dropped or
    marked. Note that this differs from the physical queue limit,
    which is stored in diffServAlgDropQThreshold. Changes in this
    variable may or may not be reflected in the reported value of
    diffServRandomDropMaxThreshPkts."
  ::= { diffServRandomDropEntry 4 }
```

```
diffServRandomDropMaxThreshPkts OBJECT-TYPE
  SYNTAX      Unsigned32  (1..4294967295)
  UNITS       "packets"
  MAX-ACCESS   read-create
  STATUS      current
  DESCRIPTION
    "The average queue depth beyond which traffic has a probability
    indicated by diffServRandomDropProbMax of being dropped or
    marked. Note that this differs from the physical queue limit,
    which is stored in diffServAlgDropQThreshold. Changes in this
    variable may or may not be reflected in the reported value of
    diffServRandomDropMaxThreshBytes."
  ::= { diffServRandomDropEntry 5 }

diffServRandomDropProbMax
 OBJECT-TYPE



  SYNTAX      Unsigned32 (0..1000)
  MAX-ACCESS   read-create
  STATUS      current
  DESCRIPTION
    "The worst case random drop probability, expressed in drops per
    thousand packets.

    For example, if in the worst case every arriving packet may be
    dropped (100%) for a period, this has the value 1000.
    Alternatively, if in the worst case only one percent (1%) of
    traffic may be dropped, it has the value 10."
 ::= { diffServRandomDropEntry 6 }

diffServRandomDropWeight OBJECT-TYPE
  SYNTAX      Unsigned32 (0..65536)
  MAX-ACCESS   read-create
  STATUS      current
  DESCRIPTION
    "The weighting of past history in affecting the Exponentially
    Weighted Moving Average function that calculates the current
    average queue depth.  The equation uses
    diffServRandomDropWeight/65536 as the coefficient for the new
    sample in the equation, and (65536 -
    diffServRandomDropWeight)/65536
 as the coefficient of the old
    value.

    Implementations may limit the values of diffServRandomDropWeight
```

```
      to a subset of the possible range of values, such as powers of
      two. Doing this would facilitate implementation of the
      Exponentially Weighted Moving Average using shift instructions or
      registers."
    ::= { diffServRandomDropEntry 7 }

diffServRandomDropSamplingRate OBJECT-TYPE
    SYNTAX      Unsigned32 (0..1000000)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "The number of times per second the queue is sampled for queue
      average calculation.  A value of zero is used to mean that the
      queue is sampled approximately each time a packet is enqueued (or
      dequeued)."
    ::= { diffServRandomDropEntry 8 }

diffServRandomDropStorage OBJECT-TYPE
    SYNTAX      StorageType
    MAX-ACCESS  read-create
    STATUS      current



    DESCRIPTION
      "The storage type for this conceptual
   row.  Conceptual rows
      having the value 'permanent' need not allow write-access to any
      columnar objects in the row."
    DEFVAL { nonVolatile }
    ::= { diffServRandomDropEntry 9 }

diffServRandomDropStatus OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "The status of this conceptual row. All writable objects in this
      row may be modified at any time. Setting this variable to
      'destroy' when the MIB contains one or more RowPointers pointing
      to it results in destruction being delayed until the row is no
      longer used."
    ::= { diffServRandomDropEntry 10 }

--
-- Queue Table
--
```

```
diffServQueue         OBJECT IDENTIFIER ::= { diffServMIBObjects 7 }

--
-- An entry of diffServQTable represents a FIFO queue Differentiated
-- Services Functional Data Path element as described in the Informal
-- Differentiated Services Model section 7.1.1. Note that the
-- specification of scheduling
 parameters for a queue as part of the
-- input to a scheduler functional data path element as described in
-- the Informal Differentiated Services Model section 7.1.2. This
-- allows building of hierarchical queuing/scheduling. A queue
-- therefore has these attributes:
--
-- 1. Which scheduler will service this queue, diffServQNext.
-- 2. How the scheduler will service this queue, with respect
--    to all the other queues the same scheduler needs to service,
--    diffServQMinRate.
--
-- Note that upstream Differentiated Services Functional Data Path
-- elements may point to a shared diffServQTable entry as described
-- in the Informal Differentiated Services Model section 7.1.1.
--

diffServQNextFree OBJECT-TYPE
  SYNTAX       IndexIntegerNextFree
  MAX-ACCESS   read-only




  STATUS       current
  DESCRIPTION
    "This object contains an unused value for diffServQId, or a zero
    to indicate that none exist."
  ::= { diffServQueue 1 }

diffServQTable OBJECT-TYPE
   SYNTAX       SEQUENCE OF DiffServQEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "The Queue Table enumerates the individual queues.  Note that the
    MIB models queuing systems as composed of individual queues, one
    per class of traffic, even though they may in fact be structured
    as classes of traffic scheduled using a common calendar queue, or
    in other ways."
  ::= { diffServQueue 2 }

diffServQEntry OBJECT-TYPE
```

```
  SYNTAX      DiffServQEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An entry in the Queue Table describes a single queue or class of
    traffic."
  INDEX { diffServQId }
  ::= { diffServQTable 1 }

DiffServQEntry ::= SEQUENCE  {
  diffServQId                IndexInteger,
  diffServQNext              RowPointer,
  diffServQMinRate           RowPointer,
  diffServQMaxRate           RowPointer,
  diffServQStorage
  StorageType,
  diffServQStatus            RowStatus
}

diffServQId OBJECT-TYPE
  SYNTAX      IndexInteger
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An index that enumerates the Queue entries.  Managers obtain new
    values for row creation in this table by reading
    diffServQNextFree."
  ::= { diffServQEntry 1 }

diffServQNext OBJECT-TYPE



  SYNTAX      RowPointer
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "This selects the next Differentiated Services Scheduler.  The
    RowPointer must point to a diffServSchedulerEntry.

    A value of zeroDotZero in this attribute indicates an incomplete
    diffServQEntry instance. In such a case, the entry has no
    operational effect, since it has no parameters to give it
    meaning.

    Setting this to point to a target that does not exist results in
    an inconsistentValue error.  If the row pointed to is removed or
```

becomes inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."
::= { diffServQEntry 2 }

diffServQMinRate OBJECT-TYPE
SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This RowPointer indicates the diffServMinRateEntry that the
scheduler, pointed to by diffServQNext, should use to service
this queue.

If the row pointed to is zeroDotZero, the minimum rate and
priority is unspecified.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or
becomes inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."
::= { diffServQEntry 3 }

diffServQMaxRate OBJECT-TYPE
SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This RowPointer indicates the diffServMaxRateEntry
that the
scheduler, pointed to by diffServQNext, should use to service
this queue.

If the row pointed to is zeroDotZero, the maximum rate is the
line speed of the interface.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or
becomes inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."
::= { diffServQEntry 4 }

diffServQStorage OBJECT-TYPE
SYNTAX StorageType
MAX-ACCESS read-create
STATUS current

```
    DESCRIPTION
      "The storage type for this conceptual row.  Conceptual rows
      having the value 'permanent' need not allow write-access to any
      columnar objects in the row."
    DEFVAL { nonVolatile }
    ::= { diffServQEntry 5 }

diffServQStatus OBJECT-TYPE
    SYNTAX       RowStatus
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION

  "The status of this conceptual row. All writable objects in this
      row may be modified at any time. Setting this variable to
      'destroy' when the MIB contains one or more RowPointers pointing
      to it results in destruction being delayed until the row is no
      longer used."
    ::= { diffServQEntry 6 }

--
-- Scheduler Table
--

diffServScheduler      OBJECT IDENTIFIER ::= { diffServMIBObjects 8 }

--
-- A Scheduler Entry represents a packet scheduler, such as a priority
-- scheduler or a WFQ scheduler. It provides flexibility for multiple
-- scheduling algorithms, each servicing multiple queues, to be used on
-- the same logical/physical interface.
--
-- Note that upstream queues or schedulers specify several of the
-- scheduler's parameters. These must be properly specified if the
-- scheduler is to behave as expected.
--
-- The diffServSchedulerMaxRate attribute specifies the parameters when
-- a scheduler's output is sent to another scheduler. This is used in
-- building
 hierarchical queues or schedulers.



--
-- More discussion of the scheduler functional data path element is in
-- the Informal Differentiated Services Model section 7.1.2.
--
```

```
diffServSchedulerNextFree OBJECT-TYPE
  SYNTAX      IndexIntegerNextFree
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object contains an unused value for diffServSchedulerId, or
    a zero to indicate that none exist."
  ::= { diffServScheduler 1 }

diffServSchedulerTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF DiffServSchedulerEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "The Scheduler Table enumerates packet schedulers. Multiple
    scheduling algorithms can be used on a given data path, with each
    algorithm described by one diffServSchedulerEntry."
  ::= { diffServScheduler 2 }

diffServSchedulerEntry OBJECT-TYPE
  SYNTAX      DiffServSchedulerEntry
  MAX-ACCESS  not-accessible
  STATUS      current
   DESCRIPTION
    "An entry in the Scheduler Table describing a single instance of
    a scheduling algorithm."
  INDEX { diffServSchedulerId }
  ::= { diffServSchedulerTable 1 }

DiffServSchedulerEntry ::= SEQUENCE  {
  diffServSchedulerId              IndexInteger,
  diffServSchedulerNext            RowPointer,
  diffServSchedulerMethod          AutonomousType,
  diffServSchedulerMinRate         RowPointer,
  diffServSchedulerMaxRate         RowPointer,
  diffServSchedulerStorage         StorageType,
  diffServSchedulerStatus          RowStatus
}

diffServSchedulerId OBJECT-TYPE
  SYNTAX      IndexInteger
  MAX-ACCESS  not-accessible
  STATUS      current



  DESCRIPTION
    "An index that enumerates the Scheduler entries.  Managers obtain
```

new values for row creation in this table by reading
diffServSchedulerNextFree."
::= { diffServSchedulerEntry 1 }

diffServSchedulerNext OBJECT-TYPE

SYNTAX RowPointer
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This selects the next Differentiated Services Functional Data
Path Element to handle traffic for this data path. This normally
is null (zeroDotZero), or points to a diffServSchedulerEntry or a
diffServQEntry.

However, this RowPointer may also point to an instance of:
diffServClfrEntry,
diffServMeterEntry,
diffServActionEntry,
diffServAlgDropEntry.

It would point another diffServSchedulerEntry when implementing
multiple scheduler methods for the same data path, such as having
one set of queues scheduled by WRR and that group participating
in a priority scheduling system in which other queues compete
with it in that way. It might also point to a second scheduler
in a hierarchical scheduling system.

If the row pointed to is zeroDotZero, no further Differentiated
Services
treatment is performed on traffic of this data path.

Setting this to point to a target that does not exist results in
an inconsistentValue error. If the row pointed to is removed or
becomes inactive by other means, the treatment is as if this
attribute contains a value of zeroDotZero."
DEFVAL { zeroDotZero }
::= { diffServSchedulerEntry 2 }

diffServSchedulerMethod OBJECT-TYPE
SYNTAX AutonomousType
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The scheduling algorithm used by this Scheduler. zeroDotZero
indicates that this is unknown. Standard values for generic
algorithms: diffServSchedulerPriority, diffServSchedulerWRR, and
diffServSchedulerWFQ are specified in this MIB; additional values

```
    may be further specified in other MIBs."
  ::= { diffServSchedulerEntry 3 }

diffServSchedulerMinRate OBJECT-TYPE
  SYNTAX      RowPointer
  MAX-ACCESS  read-create

  STATUS      current
  DESCRIPTION
    "This RowPointer indicates the entry in diffServMinRateTable
    which indicates the priority or minimum output rate from this
    scheduler. This attribute is used only when there is more than
    one level of scheduler.

    When it has the value zeroDotZero, it indicates that no minimum
    rate or priority is imposed.

    Setting this to point to a target that does not exist results in
    an inconsistentValue error.  If the row pointed to is removed or
    becomes inactive by other means, the treatment is as if this
    attribute contains a value of zeroDotZero."
  DEFVAL      { zeroDotZero }
  ::= { diffServSchedulerEntry 4 }

diffServSchedulerMaxRate OBJECT-TYPE
  SYNTAX      RowPointer
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "This RowPointer indicates the entry in diffServMaxRateTable
    which indicates the maximum output rate from this scheduler.
    When
 more than one maximum rate applies (eg, when a multi-rate
    shaper is in view), it points to the first of those rate entries.
    This attribute is used only when there is more than one level of
    scheduler.

    When it has the value zeroDotZero, it indicates that no maximum
    rate is imposed.

    Setting this to point to a target that does not exist results in
    an inconsistentValue error.  If the row pointed to is removed or
    becomes inactive by other means, the treatment is as if this
    attribute contains a value of zeroDotZero."
  DEFVAL      { zeroDotZero }
```

```
  ::= { diffServSchedulerEntry 5 }

diffServSchedulerStorage OBJECT-TYPE
  SYNTAX       StorageType
  MAX-ACCESS   read-create



  STATUS       current
  DESCRIPTION
    "The storage type for this conceptual row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::=
 { diffServSchedulerEntry 6 }

diffServSchedulerStatus OBJECT-TYPE
  SYNTAX       RowStatus
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The status of this conceptual row. All writable objects in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
  ::= { diffServSchedulerEntry 7 }

--
-- OIDs for diffServTBParamType definitions.
--

diffServSchedulers  OBJECT IDENTIFIER ::= { diffServMIBAdmin 2 }

diffServSchedulerPriority OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "For use with diffServSchedulerMethod to indicate the Priority
    scheduling method.  This is defined as an algorithm in which the
    presence of data in a queue or set of queues absolutely precludes
    dequeue from another queue or set of queues of lower priority.
    Note
 that attributes from diffServMinRateEntry of the
    queues/schedulers feeding this scheduler are used when
    determining the next packet to schedule."
  ::= { diffServSchedulers 1 }
```

```
diffServSchedulerWRR OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "For use with diffServSchedulerMethod to indicate the Weighted
    Round Robin scheduling method, defined as any algorithm in which
    a set of queues are visited in a fixed order, and varying amounts
    of traffic are removed from each queue in turn to implement an
    average output rate by class. Notice attributes from
    diffServMinRateEntry of the queues/schedulers feeding this
    scheduler are used when determining the next packet to schedule."



  ::= { diffServSchedulers 2 }

diffServSchedulerWFQ OBJECT-IDENTITY
  STATUS       current
  DESCRIPTION
    "For use with diffServSchedulerMethod to indicate the Weighted
    Fair Queuing scheduling method, defined as any algorithm
 in which
    a set of queues are conceptually visited in some order, to
    implement an average output rate by class. Notice attributes from
    diffServMinRateEntry of the queues/schedulers feeding this
    scheduler are used when determining the next packet to schedule."
  ::= { diffServSchedulers 3 }

--
-- Minimum Rate Parameters Table
--
-- The parameters used by a scheduler for its inputs or outputs are
-- maintained separately from the Queue or Scheduler table entries for
-- reusability reasons and so that they may be used by both queues and
-- schedulers.  This follows the approach for separation of data path
-- elements from parameterization that is used throughout this MIB.
-- Use of these Minimum Rate Parameter Table entries by Queues and
-- Schedulers allows the modeling of hierarchical scheduling systems.
--
-- Specifically, a Scheduler has one or more inputs and one output.
-- Any queue feeding a scheduler, or any scheduler which feeds a second
-- scheduler,
 might specify a minimum transfer rate by pointing to an
-- Minimum Rate Parameter Table entry.
--
-- The diffServMinRatePriority/Abs/Rel attributes are used as
-- parameters to the work-conserving portion of a scheduler:
-- "work-conserving" implies that the scheduler can continue to emit
-- data as long as there is data available at its input(s).  This has
```

```
-- the effect of guaranteeing a certain priority relative to other
-- scheduler inputs and/or a certain minimum proportion of the
-- available output bandwidth. Properly configured, this means a
-- certain minimum rate, which may be exceeded should traffic be
-- available should there be spare bandwidth after all other classes
-- have had opportunities to consume their own minimum rates.
--

diffServMinRateNextFree OBJECT-TYPE
  SYNTAX      IndexIntegerNextFree
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object contains an unused value for diffServMinRateId, or a
    zero to indicate
 that none exist."



  ::= { diffServScheduler 3 }

diffServMinRateTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF DiffServMinRateEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "The Minimum Rate Parameters Table enumerates individual sets of
    scheduling parameter that can be used/reused by Queues and
    Schedulers."
  ::= { diffServScheduler 4 }

diffServMinRateEntry OBJECT-TYPE
  SYNTAX      DiffServMinRateEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An entry in the Minimum Rate Parameters Table describes a single
    set of scheduling parameters for use by one or more queues or
    schedulers."
  INDEX { diffServMinRateId }
  ::= { diffServMinRateTable 1 }

DiffServMinRateEntry ::= SEQUENCE  {
  diffServMinRateId            IndexInteger,
  diffServMinRatePriority      Unsigned32,
  diffServMinRateAbsolute      Unsigned32,
  diffServMinRateRelative      Unsigned32,
```

```
    diffServMinRateStorage         StorageType,
    diffServMinRateStatus          RowStatus
}

diffServMinRateId OBJECT-TYPE
    SYNTAX       IndexInteger
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
      "An index that enumerates the Scheduler Parameter entries.
      Managers obtain new values for row creation in this table by
      reading diffServMinRateNextFree."
    ::= { diffServMinRateEntry 1 }

diffServMinRatePriority OBJECT-TYPE
    SYNTAX       Unsigned32  (1..4294967295)
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
      "The priority of this input to the associated scheduler, relative




      to the scheduler's other inputs. A queue or scheduler with a
      larger numeric value will be served before another with a smaller
      numeric value."
    ::= { diffServMinRateEntry 2 }

diffServMinRateAbsolute OBJECT-TYPE
    SYNTAX       Unsigned32  (1..4294967295)
    UNITS        "kilobits per second"
    MAX-ACCESS
    read-create
    STATUS       current
    DESCRIPTION
      "The minimum absolute rate, in kilobits/sec, that a downstream
      scheduler element should allocate to this queue. If the value is
      zero, then there is effectively no minimum rate guarantee. If the
      value is non-zero, the scheduler will assure the servicing of
      this queue to at least this rate.

      Note that this attribute value and that of
      diffServMinRateRelative are coupled: changes to one will affect
      the value of the other. They are linked by the following
      equation, in that setting one will change the other:

        diffServMinRateRelative =
              (diffServMinRateAbsolute*1000000)/ifSpeed
```

```
    or, if appropriate:

     diffServMinRateRelative = diffServMinRateAbsolute/ifHighSpeed"
  REFERENCE
    "ifSpeed, ifHighSpeed, Interface MIB, RFC 2863"
  ::= { diffServMinRateEntry 3 }

diffServMinRateRelative OBJECT-TYPE
  SYNTAX      Unsigned32  (1..4294967295)
   MAX-ACCESS   read-create
  STATUS      current
  DESCRIPTION
    "The minimum rate that a downstream scheduler element should
    allocate to this queue, relative to the maximum rate of the
    interface as reported by ifSpeed or ifHighSpeed, in units of
    1/1000 of 1. If the value is zero, then there is effectively no
    minimum rate guarantee. If the value is non-zero, the scheduler
    will assure the servicing of this queue to at least this rate.

    Note that this attribute value and that of
    diffServMinRateAbsolute are coupled: changes to one will affect
    the value of the other. They are linked by the following
    equation, in that setting one will change the other:



     diffServMinRateRelative =
          (diffServMinRateAbsolute*1000000)/ifSpeed

    or, if appropriate:

     diffServMinRateRelative = diffServMinRateAbsolute/ifHighSpeed"
  REFERENCE
    "ifSpeed, ifHighSpeed, Interface MIB,
 RFC 2863"
  ::= { diffServMinRateEntry 4 }

diffServMinRateStorage OBJECT-TYPE
  SYNTAX      StorageType
  MAX-ACCESS   read-create
  STATUS      current
  DESCRIPTION
    "The storage type for this conceptual row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServMinRateEntry 5 }
```

```
diffServMinRateStatus OBJECT-TYPE
  SYNTAX       RowStatus
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The status of this conceptual row. All writable objects in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
  ::= { diffServMinRateEntry 6 }

--
-- Maximum Rate Parameter Table
--
-- The parameters used by a scheduler for its inputs or outputs are
-- maintained
 separately from the Queue or Scheduler table entries for
-- reusability reasons and so that they may be used by both queues and
-- schedulers.  This follows the approach for separation of data path
-- elements from parameterization that is used throughout this MIB.
-- Use of these Maximum Rate Parameter Table entries by Queues and
-- Schedulers allows the modeling of hierarchical scheduling systems.
--
-- Specifically, a Scheduler has one or more inputs and one output.
-- Any queue feeding a scheduler, or any scheduler which feeds a second
-- scheduler, might specify a maximum transfer rate by pointing to a
-- Maximum Rate Parameter Table entry. Multi-rate shapers, such as a




-- Dual Leaky Bucket algorithm, specify their rates using multiple
-- Maximum Rate Parameter Entries with the same diffServMaxRateId but
-- different diffServMaxRateLevels.
--
-- The diffServMaxRateLevel/Abs/Rel attributes are used as
-- parameters to the non-work-conserving portion of a scheduler:
-- non-work-conserving
 implies that the scheduler may sometimes not
-- emit a packet, even if there is data available at its input(s).
-- This has the effect of limiting the servicing of the queue/scheduler
-- input or output, in effect performing shaping of the packet stream
-- passing through the queue/scheduler, as described in the Informal
-- Differentiated Services Model section 7.2.
--

diffServMaxRateNextFree OBJECT-TYPE
```

```
  SYNTAX      IndexIntegerNextFree
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object contains an unused value for diffServMaxRateId, or a
    zero to indicate that none exist."
  ::= { diffServScheduler 5 }

diffServMaxRateTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF DiffServMaxRateEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "The Maximum Rate Parameter Table enumerates individual sets of
    scheduling parameter that can be used/reused by Queues and
    Schedulers."
  ::=
 { diffServScheduler 6 }

diffServMaxRateEntry OBJECT-TYPE
  SYNTAX      DiffServMaxRateEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An entry in the Maximum Rate Parameter Table describes a single
    set of scheduling parameters for use by one or more queues or
    schedulers."
  INDEX { diffServMaxRateId, diffServMaxRateLevel }
  ::= { diffServMaxRateTable 1 }

DiffServMaxRateEntry ::= SEQUENCE  {
  diffServMaxRateId            IndexInteger,
  diffServMaxRateLevel         Unsigned32,
  diffServMaxRateAbsolute      Unsigned32,



  diffServMaxRateRelative      Unsigned32,
  diffServMaxRateThreshold     BurstSize,
  diffServMaxRateStorage       StorageType,
  diffServMaxRateStatus        RowStatus
}

diffServMaxRateId OBJECT-TYPE
  SYNTAX      IndexInteger
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
```

```
      "An index that enumerates the Maximum Rate Parameter entries.

      Managers obtain new values for row creation in this table by
      reading diffServMaxRateNextFree."
    ::= { diffServMaxRateEntry 1 }

diffServMaxRateLevel OBJECT-TYPE
    SYNTAX      Unsigned32 (1..32)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
      "An index that indicates which level of a multi-rate shaper is
      being given its parameters. A multi-rate shaper has some number
      of rate levels. Frame Relay's dual rate specification refers to a
      'committed' and an 'excess' rate; ATM's dual rate specification
      refers to a 'mean' and a 'peak' rate. This table is generalized
      to support an arbitrary number of rates. The committed or mean
      rate is level 1, the peak rate (if any) is the highest level rate
      configured, and if there are other rates they are distributed in
      monotonically increasing order between them."
    ::= { diffServMaxRateEntry 2 }

diffServMaxRateAbsolute OBJECT-TYPE
    SYNTAX      Unsigned32
   (1..4294967295)
    UNITS       "kilobits per second"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      "The maximum rate in kilobits/sec that a downstream scheduler
      element should allocate to this queue. If the value is zero, then
      there is effectively no maximum rate limit and that the scheduler
      should attempt to be work conserving for this queue. If the value
      is non-zero, the scheduler will limit the servicing of this queue
      to, at most, this rate in a non-work-conserving manner.

      Note that this attribute value and that of
      diffServMaxRateRelative are coupled: changes to one will affect
      the value of the other. They are linked by the following



      equation, in that setting one will change the other:

        diffServMaxRateRelative =
            (diffServMaxRateAbsolute*1000000)/ifSpeed

      or, if appropriate:
```

```
      diffServMaxRateRelative = diffServMaxRateAbsolute/ifHighSpeed"
    REFERENCE
      "ifSpeed, ifHighSpeed, Interface MIB, RFC 2863"
  ::= { diffServMaxRateEntry 3 }

diffServMaxRateRelative OBJECT-TYPE
  SYNTAX       Unsigned32  (1..4294967295)
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The maximum rate that a downstream scheduler element should
    allocate to this queue, relative to the maximum rate of the
    interface as reported by ifSpeed or ifHighSpeed, in units of
    1/1000 of 1. If the value is zero, then there is effectively no
    maximum rate limit and the scheduler should attempt to be work
    conserving for this queue. If the value is non-zero, the
    scheduler will limit the servicing of this queue to, at most,
    this rate in a non-work-conserving manner.

    Note that this attribute value and that of
    diffServMaxRateAbsolute are coupled: changes to one will affect
    the value of the other. They are linked by the following
    equation, in that setting
 one will change the other:

      diffServMaxRateRelative =
           (diffServMaxRateAbsolute*1000000)/ifSpeed

    or, if appropriate:

      diffServMaxRateRelative = diffServMaxRateAbsolute/ifHighSpeed"
  REFERENCE
    "ifSpeed, ifHighSpeed, Interface MIB, RFC 2863"
  ::= { diffServMaxRateEntry 4 }

diffServMaxRateThreshold OBJECT-TYPE
  SYNTAX       BurstSize
  UNITS        "Bytes"
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The number of bytes of queue depth at which the rate of a




    multi-rate scheduler will increase to the next output rate. In
    the last conceptual row for such a shaper, this threshold is
```

```
    ignored and by convention is zero."
  REFERENCE
     "Adaptive rate Shaper, RFC 2963"
  ::= { diffServMaxRateEntry 5 }

diffServMaxRateStorage OBJECT-TYPE
  SYNTAX       StorageType
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The storage type for this
 conceptual row.  Conceptual rows
    having the value 'permanent' need not allow write-access to any
    columnar objects in the row."
  DEFVAL { nonVolatile }
  ::= { diffServMaxRateEntry 6 }

diffServMaxRateStatus OBJECT-TYPE
  SYNTAX       RowStatus
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
    "The status of this conceptual row. All writable objects in this
    row may be modified at any time. Setting this variable to
    'destroy' when the MIB contains one or more RowPointers pointing
    to it results in destruction being delayed until the row is no
    longer used."
  ::= { diffServMaxRateEntry 7 }

--
-- MIB Compliance statements.
--

diffServMIBCompliances OBJECT IDENTIFIER ::=
                          { diffServMIBConformance 1 }
diffServMIBGroups     OBJECT IDENTIFIER ::=
                          { diffServMIBConformance 2 }

diffServMIBFullCompliance MODULE-COMPLIANCE
  STATUS current

 DESCRIPTION
    "When this MIB is implemented with support for read-create, then
    such an implementation can claim full compliance. Such devices
    can then be both monitored and configured with this MIB."

  MODULE IF-MIB -- The interfaces MIB, RFC2863
  MANDATORY-GROUPS {
```

```
  ifCounterDiscontinuityGroup
}

MODULE -- This Module
MANDATORY-GROUPS {
   diffServMIBDataPathGroup, diffServMIBClfrGroup,
   diffServMIBClfrElementGroup, diffServMIBMultiFieldClfrGroup,
   diffServMIBActionGroup, diffServMIBAlgDropGroup,
   diffServMIBQGroup, diffServMIBSchedulerGroup,
   diffServMIBMaxRateGroup, diffServMIBMinRateGroup,
   diffServMIBCounterGroup
}

GROUP diffServMIBMeterGroup
DESCRIPTION
  "This group is mandatory for devices that implement metering
  functions."

GROUP diffServMIBTBParamGroup
DESCRIPTION
  "This group is mandatory for devices that implement token-bucket
  metering functions."

 GROUP diffServMIBDscpMarkActGroup
DESCRIPTION
  "This group is mandatory for devices that implement DSCP-Marking
  functions."

GROUP diffServMIBRandomDropGroup
DESCRIPTION
  "This group is mandatory for devices that implement Random Drop
  functions."

OBJECT diffServDataPathStatus
SYNTAX RowStatus { active(1) }
WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
DESCRIPTION
  "Support for createAndWait and notInService is not required."

OBJECT diffServClfrStatus
SYNTAX RowStatus { active(1) }
WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
DESCRIPTION
  "Support for createAndWait and notInService is not required."
```

```
  OBJECT diffServClfrElementStatus
  SYNTAX RowStatus { active(1) }
  WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }



  DESCRIPTION
    "Support for createAndWait and notInService is not required."

  OBJECT diffServMultiFieldClfrAddrType
  SYNTAX  InetAddressType
{ unknown(0), ipv4(1), ipv6(2) }
  DESCRIPTION
    "An implementation is only required to support IPv4 and IPv6
    addresses."

  OBJECT diffServMultiFieldClfrDstAddr
  SYNTAX  InetAddress (SIZE(0|4|16))
  DESCRIPTION
    "An implementation is only required to support IPv4 and globally
    unique IPv6 addresses."

  OBJECT diffServAlgDropStatus
  SYNTAX RowStatus { active(1) }
  WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
  DESCRIPTION
    "Support for createAndWait and notInService is not required."

  OBJECT diffServRandomDropStatus
  SYNTAX RowStatus { active(1) }
  WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
  DESCRIPTION
    "Support for createAndWait and notInService is not required."

  OBJECT diffServQStatus
  SYNTAX RowStatus { active(1) }
  WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
  DESCRIPTION
    "Support for createAndWait and notInService is not required."

  OBJECT diffServSchedulerStatus
   SYNTAX RowStatus { active(1) }
  WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
  DESCRIPTION
    "Support for createAndWait and notInService is not required."

  OBJECT diffServMinRateStatus
  SYNTAX RowStatus { active(1) }
```

```
  WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
  DESCRIPTION
    "Support for createAndWait and notInService is not required."

  OBJECT diffServMaxRateStatus
  SYNTAX RowStatus { active(1) }
  WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }



  DESCRIPTION
    "Support for createAndWait and notInService is not required."

  ::= { diffServMIBCompliances 1 }

--
-- Read-Only Compliance
--

diffServMIBReadOnlyCompliance MODULE-COMPLIANCE
  STATUS current
  DESCRIPTION
    "When this MIB is implemented without support for read-create
    (i.e. in read-only mode), then such an implementation can claim
    read-only compliance. Such a device can then be monitored but can
    not be configured
 with this MIB."

  MODULE IF-MIB -- The interfaces MIB, RFC2863
  MANDATORY-GROUPS {
    ifCounterDiscontinuityGroup
  }

  MODULE -- This Module
  MANDATORY-GROUPS {
     diffServMIBDataPathGroup, diffServMIBClfrGroup,
     diffServMIBClfrElementGroup, diffServMIBMultiFieldClfrGroup,
     diffServMIBActionGroup, diffServMIBAlgDropGroup,
     diffServMIBQGroup, diffServMIBSchedulerGroup,
     diffServMIBMaxRateGroup, diffServMIBMinRateGroup,
     diffServMIBCounterGroup
  }

  GROUP diffServMIBMeterGroup
  DESCRIPTION
    "This group is mandatory for devices that implement metering
    functions."
```

```
GROUP diffServMIBTBParamGroup
DESCRIPTION
  "This group is mandatory for devices that implement token-bucket
  metering functions."

GROUP       diffServMIBDscpMarkActGroup
DESCRIPTION
  "This group is mandatory for devices that implement DSCP-Marking
  functions."

GROUP       diffServMIBRandomDropGroup



 DESCRIPTION
  "This group is mandatory for devices that implement Random Drop
  functions."

OBJECT      diffServDataPathStart
MIN-ACCESS  read-only
DESCRIPTION
  "Write access is not required."

OBJECT      diffServDataPathStorage
MIN-ACCESS  read-only
DESCRIPTION
  "Write access is not required."

OBJECT      diffServDataPathStatus
SYNTAX       RowStatus { active(1) }
MIN-ACCESS  read-only
DESCRIPTION
  "Write access is not required, and active is the only status that
  needs to be supported."

OBJECT      diffServClfrNextFree
MIN-ACCESS  not-accessible
DESCRIPTION
  "Object not needed when diffServClfrTable is implemented read-
  only"

OBJECT      diffServClfrStorage
MIN-ACCESS  read-only
DESCRIPTION
  "Write access is not required."

OBJECT      diffServClfrStatus
SYNTAX       RowStatus { active(1) }
```

MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that
needs to be supported."

OBJECT diffServClfrElementNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object not needed when diffServClfrelementTable is implemented
read-only"

OBJECT diffServClfrElementPrecedence
MIN-ACCESS read-only
DESCRIPTION

"Write access is not required."

OBJECT diffServClfrElementNext
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServClfrElementSpecific
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServClfrElementStorage
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServClfrElementStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that
needs to be supported."

OBJECT diffServMultiFieldClfrNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServMultiFieldClfrTable is
implemented in read-only mode."

OBJECT diffServMultiFieldClfrAddrType

SYNTAX InetAddressType { unknown(0), ipv4(1), ipv6(2) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required. An implementation is only required to support IPv4 and IPv6 addresses."

OBJECT diffServMultiFieldClfrDstAddr
SYNTAX InetAddress (SIZE(0|4|16))
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required. An implementation is only required to support IPv4 and globally unique IPv6 addresses."

OBJECT diffServMultiFieldClfrDstPrefixLength
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrSrcAddr
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required. An implementation is only required to support IPv4 and globally unique IPv6 addresses."

OBJECT diffServMultiFieldClfrSrcPrefixLength
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrDscp
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrFlowId
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrProtocol
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrDstL4PortMin
MIN-ACCESS read-only

DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrDstL4PortMax
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrSrcL4PortMin
MIN-ACCESS
read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrSrcL4PortMax
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrStorage
MIN-ACCESS read-only

DESCRIPTION
"Write access is not required."

OBJECT diffServMultiFieldClfrStatus
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, createAndWait and notInService
support is not required."

OBJECT diffServMeterNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServMultiFieldClfrTable is
implemented in read-only mode."

OBJECT diffServMeterSucceedNext
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMeterFailNext
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMeterSpecific
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMeterStorage
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMeterStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that
needs to be supported."

OBJECT diffServTBParamNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServTBParamTable is implemented in
read-only mode."

OBJECT diffServTBParamType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServTBParamRate
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServTBParamBurstSize
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT
diffServTBParamInterval
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

```
  OBJECT      diffServTBParamStorage
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access is not required."

  OBJECT      diffServTBParamStatus
  SYNTAX      RowStatus { active(1) }
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access is not required, and active is the only status that
    needs to be supported."

  OBJECT      diffServActionNextFree
  MIN-ACCESS  not-accessible
  DESCRIPTION
    "Object is not needed when diffServActionTable is implemented in
    read-only mode."

  OBJECT      diffServActionInterface
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access is not required."

  OBJECT      diffServActionNext
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access is not required."




  OBJECT      diffServActionSpecific
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access
is not required."

  OBJECT      diffServActionStorage
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access is not required."

  OBJECT      diffServActionStatus
  SYNTAX      RowStatus { active(1) }
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access is not required, and active is the only status that
    needs to be supported."
```

```
OBJECT      diffServCountActNextFree
MIN-ACCESS  not-accessible
DESCRIPTION
  "Object is not needed when diffServCountActTable is implemented
  in read-only mode."

OBJECT      diffServCountActStorage
MIN-ACCESS  read-only
DESCRIPTION
  "Write access is not required."

OBJECT      diffServCountActStatus
SYNTAX      RowStatus { active(1) }
MIN-ACCESS  read-only
DESCRIPTION
  "Write access is not required, and active is the only status that
  needs to be supported."

OBJECT      diffServAlgDropNextFree
MIN-ACCESS  not-accessible
DESCRIPTION
   "Object is not needed when diffServAlgDropTable is implemented in
  read-only mode."

OBJECT      diffServAlgDropType
MIN-ACCESS  read-only
DESCRIPTION
  "Write access is not required."

OBJECT      diffServAlgDropNext
MIN-ACCESS  read-only



DESCRIPTION
  "Write access is not required."

OBJECT      diffServAlgDropQMeasure
MIN-ACCESS  read-only
DESCRIPTION
  "Write access is not required."

OBJECT      diffServAlgDropQThreshold
MIN-ACCESS  read-only
DESCRIPTION
  "Write access is not required."
```

OBJECT diffServAlgDropSpecific
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServAlgDropStorage
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServAlgDropStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required,
and active is the only status that
needs to be supported."

OBJECT diffServRandomDropNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServRandomDropTable is implemented
in read-only mode."

OBJECT diffServRandomDropMinThreshBytes
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServRandomDropMinThreshPkts
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServRandomDropMaxThreshBytes
MIN-ACCESS read-only

DESCRIPTION
"Write access is not required."

OBJECT diffServRandomDropMaxThreshPkts
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServRandomDropProbMax

MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServRandomDropWeight
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServRandomDropSamplingRate
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServRandomDropStorage
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServRandomDropStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that
needs to be supported."

OBJECT diffServQNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServQTable is implemented in
read-only mode."

OBJECT diffServQNext
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServQMinRate
MIN-ACCESS read-only

DESCRIPTION
"Write access is not required."

OBJECT diffServQMaxRate
MIN-ACCESS read-only

DESCRIPTION
"Write access is not required."

OBJECT diffServQStorage
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServQStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that
needs to be supported."

OBJECT diffServSchedulerNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServSchedulerTable is implemented
in read-only mode."

OBJECT diffServSchedulerNext
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServSchedulerMethod
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServSchedulerMinRate
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServSchedulerMaxRate
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServSchedulerStorage
MIN-ACCESS read-only

DESCRIPTION
"Write access is not required."

OBJECT diffServSchedulerStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that needs to be supported."

OBJECT diffServMinRateNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServMinRateTable is implemented in read-only mode."

OBJECT diffServMinRatePriority
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMinRateAbsolute
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMinRateRelative
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMinRateStorage
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT diffServMinRateStatus
SYNTAX RowStatus { active(1) }
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required, and active is the only status that needs to be supported."

OBJECT diffServMaxRateNextFree
MIN-ACCESS not-accessible
DESCRIPTION
"Object is not needed when diffServMaxrateTable is implemented in read-only mode."

```
  OBJECT      diffServMaxRateAbsolute
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access is not required."

  OBJECT      diffServMaxRateRelative
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access is not required."

  OBJECT      diffServMaxRateThreshold
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access is not required."

  OBJECT      diffServMaxRateStorage
  MIN-ACCESS  read-only
  DESCRIPTION
     "Write access is not required."

  OBJECT      diffServMaxRateStatus
  SYNTAX      RowStatus { active(1) }
  MIN-ACCESS  read-only
  DESCRIPTION
    "Write access is not required, and active is the only status that
    needs to be supported."

  ::= { diffServMIBCompliances 2 }

diffServMIBDataPathGroup OBJECT-GROUP
  OBJECTS {
          diffServDataPathStart, diffServDataPathStorage,
          diffServDataPathStatus
  }
  STATUS      current
  DESCRIPTION
    "The Data Path Group defines the MIB Objects that describe a
    functional data path."
  ::= { diffServMIBGroups 1 }

diffServMIBClfrGroup OBJECT-GROUP
  OBJECTS {
          diffServClfrNextFree, diffServClfrStorage,
          diffServClfrStatus
  }
  STATUS      current
  DESCRIPTION
```

```
      "The Classifier Group defines the MIB Objects that describe the

      list the starts of individual classifiers."
    ::= { diffServMIBGroups 2 }

diffServMIBClfrElementGroup
 OBJECT-GROUP
    OBJECTS {
            diffServClfrElementNextFree,
            diffServClfrElementPrecedence, diffServClfrElementNext,
            diffServClfrElementSpecific, diffServClfrElementStorage,
            diffServClfrElementStatus
    }
    STATUS       current
    DESCRIPTION
      "The Classifier Element Group defines the MIB Objects that
      describe the classifier elements that make up a generic
      classifier."
    ::= { diffServMIBGroups 3 }

diffServMIBMultiFieldClfrGroup OBJECT-GROUP
    OBJECTS {
            diffServMultiFieldClfrNextFree,
            diffServMultiFieldClfrAddrType,
            diffServMultiFieldClfrDstAddr,
            diffServMultiFieldClfrDstPrefixLength,
            diffServMultiFieldClfrFlowId,
            diffServMultiFieldClfrSrcAddr,
            diffServMultiFieldClfrSrcPrefixLength,
            diffServMultiFieldClfrDscp,
            diffServMultiFieldClfrProtocol,
            diffServMultiFieldClfrDstL4PortMin,
             diffServMultiFieldClfrDstL4PortMax,
            diffServMultiFieldClfrSrcL4PortMin,
            diffServMultiFieldClfrSrcL4PortMax,
            diffServMultiFieldClfrStorage,
            diffServMultiFieldClfrStatus
    }
    STATUS       current
    DESCRIPTION
      "The Multi-field Classifier Group defines the MIB Objects that
      describe a classifier element for matching on various fields of
      an IP and upper-layer protocol header."
    ::= { diffServMIBGroups 4 }

diffServMIBMeterGroup OBJECT-GROUP
```

```
  OBJECTS {
          diffServMeterNextFree, diffServMeterSucceedNext,
          diffServMeterFailNext, diffServMeterSpecific,
          diffServMeterStorage, diffServMeterStatus
  }



  STATUS      current
  DESCRIPTION
    "The Meter Group defines the objects used in describing a generic
    meter element."
  ::= { diffServMIBGroups 5 }

diffServMIBTBParamGroup OBJECT-GROUP
  OBJECTS {
          diffServTBParamNextFree,
 diffServTBParamType,
          diffServTBParamRate, diffServTBParamBurstSize,
          diffServTBParamInterval, diffServTBParamStorage,
          diffServTBParamStatus
  }
  STATUS      current
  DESCRIPTION
    "The Token-Bucket Meter Group defines the objects used in
    describing a token bucket meter element."
  ::= { diffServMIBGroups 6 }

diffServMIBActionGroup OBJECT-GROUP
  OBJECTS {
          diffServActionNextFree, diffServActionNext,
          diffServActionSpecific, diffServActionStorage,
          diffServActionInterface, diffServActionStatus
  }
  STATUS      current
  DESCRIPTION
    "The Action Group defines the objects used in describing a
    generic action element."
  ::= { diffServMIBGroups 7 }

diffServMIBDscpMarkActGroup OBJECT-GROUP
  OBJECTS {
          diffServDscpMarkActDscp
  }
  STATUS      current
  DESCRIPTION
    "The DSCP Mark Action Group defines the objects used in
```

```
      describing a DSCP Marking Action element."
  ::= { diffServMIBGroups 8 }

diffServMIBCounterGroup OBJECT-GROUP
  OBJECTS {
          diffServCountActOctets, diffServCountActPkts,
          diffServAlgDropOctets, diffServAlgDropPkts,
          diffServAlgRandomDropOctets, diffServAlgRandomDropPkts,
          diffServCountActStorage, diffServCountActStatus,
          diffServCountActNextFree




  }
  STATUS      current
  DESCRIPTION
    "A collection of objects providing information specific to
    packet-oriented network interfaces."
  ::= { diffServMIBGroups 9 }

diffServMIBAlgDropGroup OBJECT-GROUP
  OBJECTS {
          diffServAlgDropNextFree, diffServAlgDropType,
          diffServAlgDropNext, diffServAlgDropQMeasure,
          diffServAlgDropQThreshold, diffServAlgDropSpecific,
          diffServAlgDropStorage, diffServAlgDropStatus
  }
  STATUS      current
  DESCRIPTION
    "The Algorithmic Drop Group contains
 the objects that describe
    algorithmic dropper operation and configuration."
  ::= { diffServMIBGroups 10 }

diffServMIBRandomDropGroup OBJECT-GROUP
  OBJECTS {
          diffServRandomDropNextFree,
          diffServRandomDropMinThreshBytes,
          diffServRandomDropMinThreshPkts,
          diffServRandomDropMaxThreshBytes,
          diffServRandomDropMaxThreshPkts,
          diffServRandomDropProbMax,
          diffServRandomDropWeight,
          diffServRandomDropSamplingRate,
          diffServRandomDropStorage,
          diffServRandomDropStatus
  }
  STATUS      current
```

```
  DESCRIPTION
    "The Random Drop Group augments the Algorithmic Drop Group for
    random dropper operation and configuration."
  ::= { diffServMIBGroups 11 }

diffServMIBQGroup OBJECT-GROUP

  OBJECTS {
          diffServQNextFree, diffServQNext, diffServQMinRate,
          diffServQMaxRate, diffServQStorage, diffServQStatus

  }
  STATUS      current
  DESCRIPTION
    "The Queue Group contains the objects that describe an




    interface's queues."
  ::= { diffServMIBGroups 12 }

diffServMIBSchedulerGroup OBJECT-GROUP
  OBJECTS {
          diffServSchedulerNextFree, diffServSchedulerNext,
          diffServSchedulerMethod, diffServSchedulerMinRate,
          diffServSchedulerMaxRate, diffServSchedulerStorage,
          diffServSchedulerStatus
  }
  STATUS      current
  DESCRIPTION
    "The Scheduler Group contains the objects that describe packet
    schedulers on interfaces."
  ::= { diffServMIBGroups 13 }

diffServMIBMinRateGroup OBJECT-GROUP
  OBJECTS {
          diffServMinRateNextFree, diffServMinRatePriority,
          diffServMinRateAbsolute, diffServMinRateRelative,
          diffServMinRateStorage, diffServMinRateStatus
  }
  STATUS      current
  DESCRIPTION
    "The Minimum Rate Parameter Group contains the objects that

  describe packet schedulers' minimum rate or priority guarantees."
  ::= { diffServMIBGroups 14 }

diffServMIBMaxRateGroup OBJECT-GROUP
```

```
  OBJECTS {
          diffServMaxRateNextFree, diffServMaxRateAbsolute,
          diffServMaxRateRelative, diffServMaxRateThreshold,
          diffServMaxRateStorage, diffServMaxRateStatus
  }
  STATUS       current
  DESCRIPTION
    "The Maximum Rate Parameter Group contains the objects that
    describe packet schedulers' maximum rate guarantees."
  ::= { diffServMIBGroups 15 }

END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/DIFFSERV-MIB
No license file was found, but licenses were detected in source scan.

```
RADIUS-ACC-CLIENT-MIB DEFINITIONS ::= BEGIN

IMPORTS
     MODULE-IDENTITY, OBJECT-TYPE, OBJECT-IDENTITY,
     Counter32, Integer32, Gauge32,
     IpAddress, TimeTicks, mib-2      FROM SNMPv2-SMI
     SnmpAdminString                  FROM SNMP-FRAMEWORK-MIB
     InetAddressType, InetAddress,
     InetPortNumber                   FROM INET-ADDRESS-MIB
     MODULE-COMPLIANCE, OBJECT-GROUP  FROM SNMPv2-CONF;


radiusAccClientMIB MODULE-IDENTITY
    LAST-UPDATED "200608210000Z" -- 21 August 2006
    ORGANIZATION "IETF RADIUS Extensions Working Group."
    CONTACT-INFO
          " Bernard Aboba
            Microsoft
            One Microsoft Way




            Redmond, WA  98052
            US
            Phone: +1 425 936 6605
            EMail: bernarda@microsoft.com"
    DESCRIPTION
         "The MIB module for entities implementing the client
          side of the Remote
 Authentication Dial-In User Service
          (RADIUS) accounting protocol.  Copyright (C) The
```

```
            Internet Society (2006).  This version of this MIB
            module is part of RFC 4670; see the RFC itself for
            full legal notices."
        REVISION "200608210000Z"  -- 21 August 2006
        DESCRIPTION
            "Revised version as published in RFC 4670.
            This version obsoletes that of RFC 2620 by
            deprecating the MIB table containing IPv4-only
            address formats and defining a new table to add support
            for version-neutral IP address formats.  The remaining
            MIB objects from RFC 2620 are carried forward into this
            version."
        REVISION "199906110000Z"  -- 11 Jun 1999
        DESCRIPTION "Initial version as published in RFC 2620."
        ::= { radiusAccounting 2 }

    radiusMIB OBJECT-IDENTITY
        STATUS  current
        DESCRIPTION
            "The OID assigned to RADIUS MIB work by the IANA."
         ::= { mib-2 67 }

    radiusAccounting  OBJECT IDENTIFIER ::= {radiusMIB 2}

    radiusAccClientMIBObjects     OBJECT IDENTIFIER
        ::= { radiusAccClientMIB 1 }

    radiusAccClient  OBJECT IDENTIFIER
        ::= { radiusAccClientMIBObjects 1 }

    radiusAccClientInvalidServerAddresses OBJECT-TYPE
        SYNTAX Counter32
        UNITS "packets"
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The number of RADIUS Accounting-Response packets
            received from unknown addresses."
        ::= { radiusAccClient 1 }




    radiusAccClientIdentifier OBJECT-TYPE
        SYNTAX SnmpAdminString
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
```

```
            "The NAS-Identifier of the RADIUS accounting client.
             This is not necessarily the same as sysName in MIB
             II."
        REFERENCE "RFC 2865 section 5.32"
        ::= { radiusAccClient 2 }

    radiusAccServerTable OBJECT-TYPE
        SYNTAX SEQUENCE OF RadiusAccServerEntry
        MAX-ACCESS not-accessible
         STATUS     deprecated
        DESCRIPTION
            "The (conceptual) table listing the RADIUS accounting
             servers with which the client shares a secret."
        ::= { radiusAccClient 3 }

    radiusAccServerEntry OBJECT-TYPE
        SYNTAX     RadiusAccServerEntry
        MAX-ACCESS not-accessible
        STATUS     deprecated
        DESCRIPTION
            "An entry (conceptual row) representing a RADIUS
             accounting server with which the client shares a
             secret."
        INDEX      { radiusAccServerIndex }
        ::= { radiusAccServerTable 1 }

    RadiusAccServerEntry ::= SEQUENCE {
        radiusAccServerIndex                    Integer32,
        radiusAccServerAddress                  IpAddress,
        radiusAccClientServerPortNumber         Integer32,
        radiusAccClientRoundTripTime            TimeTicks,
        radiusAccClientRequests                 Counter32,
        radiusAccClientRetransmissions
      Counter32,
        radiusAccClientResponses                Counter32,
        radiusAccClientMalformedResponses       Counter32,
        radiusAccClientBadAuthenticators        Counter32,
        radiusAccClientPendingRequests          Gauge32,
        radiusAccClientTimeouts                 Counter32,
        radiusAccClientUnknownTypes             Counter32,
        radiusAccClientPacketsDropped           Counter32
    }




    radiusAccServerIndex OBJECT-TYPE
```

```
    SYNTAX     Integer32 (1..2147483647)
    MAX-ACCESS not-accessible
    STATUS     deprecated
    DESCRIPTION
        "A number uniquely identifying each RADIUS
         Accounting server with which this client
         communicates."
    ::= { radiusAccServerEntry 1 }

radiusAccServerAddress OBJECT-TYPE
    SYNTAX     IpAddress
    MAX-ACCESS read-only
    STATUS     deprecated
    DESCRIPTION
        "The IP address of the RADIUS accounting server

    referred to in this table entry."
    ::= { radiusAccServerEntry 2 }

radiusAccClientServerPortNumber  OBJECT-TYPE
    SYNTAX Integer32 (0..65535)
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The UDP port the client is using to send requests to
         this server."
    REFERENCE "RFC 2866 section 3"
    ::= { radiusAccServerEntry 3 }

radiusAccClientRoundTripTime  OBJECT-TYPE
    SYNTAX TimeTicks
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
         "The time interval between the most recent
         Accounting-Response and the Accounting-Request that
         matched it from this RADIUS accounting server."
    REFERENCE "RFC 2866 section 2"
    ::= { radiusAccServerEntry 4 }

-- Request/Response statistics
--
-- Requests = Responses + PendingRequests + ClientTimeouts
--
-- Responses - MalformedResponses - BadAuthenticators -
-- UnknownTypes - PacketsDropped = Successfully received
```

```
radiusAccClientRequests
 OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of RADIUS Accounting-Request packets
         sent.  This does not include retransmissions."
    REFERENCE "RFC 2866 section 4.1"
    ::= { radiusAccServerEntry 5 }

radiusAccClientRetransmissions OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of RADIUS Accounting-Request packets
         retransmitted to this RADIUS accounting server.
         Retransmissions include retries where the
         Identifier and Acct-Delay have been updated, as
         well as those in which they remain the same."
    REFERENCE "RFC 2866 section 2"
    ::= { radiusAccServerEntry 6 }

radiusAccClientResponses OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS deprecated
     DESCRIPTION
        "The number of RADIUS packets received on the
         accounting port from this server."
    REFERENCE "RFC 2866 section 4.2"
    ::= { radiusAccServerEntry 7 }

radiusAccClientMalformedResponses OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of malformed RADIUS Accounting-Response
         packets received from this server.  Malformed packets
```

include packets with an invalid length. Bad
authenticators and unknown types are not included as
malformed accounting responses."
REFERENCE "RFC 2866 section 3"

::= { radiusAccServerEntry 8 }

radiusAccClientBadAuthenticators OBJECT-TYPE
SYNTAX Counter32
UNITS "packets"
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
"The number of RADIUS Accounting-Response
packets that contained invalid
authenticators
received from this server."
REFERENCE "RFC 2866 section 3"
::= { radiusAccServerEntry 9 }

radiusAccClientPendingRequests OBJECT-TYPE
SYNTAX Gauge32
UNITS "packets"
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
"The number of RADIUS Accounting-Request packets
sent to this server that have not yet timed out or
received a response. This variable is incremented
when an Accounting-Request is sent and decremented
due to receipt of an Accounting-Response, a timeout,
or a retransmission."
REFERENCE "RFC 2866 section 2"
::= { radiusAccServerEntry 10 }

radiusAccClientTimeouts OBJECT-TYPE
SYNTAX Counter32
UNITS "timeouts"
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
"The number of accounting timeouts to this server.
After a timeout, the client may retry to the same

server, send to a different server, or give up.
A retry to the same server is counted as a

```
        retransmit as well as a timeout.  A send to a different
        server is counted as an Accounting-Request as well as
        a timeout."
    REFERENCE "RFC 2866 section 2"
    ::= { radiusAccServerEntry  11 }

radiusAccClientUnknownTypes OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"



    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of RADIUS packets of unknown type that
         were received from this server on the accounting port."
    REFERENCE "RFC 2866 section 4"
    ::= { radiusAccServerEntry  12 }

radiusAccClientPacketsDropped OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of RADIUS packets that were received from
         this server on the accounting port and dropped for some

     other reason."
    ::= { radiusAccServerEntry  13 }


-- New MIB objects added in this revision

radiusAccServerExtTable OBJECT-TYPE
    SYNTAX SEQUENCE OF RadiusAccServerExtEntry
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
        "The (conceptual) table listing the RADIUS accounting
         servers with which the client shares a secret."
    ::= { radiusAccClient 4 }

radiusAccServerExtEntry OBJECT-TYPE
    SYNTAX     RadiusAccServerExtEntry
    MAX-ACCESS not-accessible
    STATUS     current
```

```
    DESCRIPTION
        "An entry (conceptual row) representing a RADIUS
         accounting server with which the client shares a
         secret."
    INDEX      { radiusAccServerExtIndex }
    ::= { radiusAccServerExtTable 1 }

RadiusAccServerExtEntry ::= SEQUENCE {
    radiusAccServerExtIndex                 Integer32,
    radiusAccServerInetAddressType          InetAddressType,
    radiusAccServerInetAddress
            InetAddress,
    radiusAccClientServerInetPortNumber     InetPortNumber,
    radiusAccClientExtRoundTripTime         TimeTicks,



    radiusAccClientExtRequests              Counter32,
    radiusAccClientExtRetransmissions       Counter32,
    radiusAccClientExtResponses             Counter32,
    radiusAccClientExtMalformedResponses    Counter32,
    radiusAccClientExtBadAuthenticators     Counter32,
    radiusAccClientExtPendingRequests       Gauge32,
    radiusAccClientExtTimeouts              Counter32,
    radiusAccClientExtUnknownTypes          Counter32,
    radiusAccClientExtPacketsDropped        Counter32,
    radiusAccClientCounterDiscontinuity     TimeTicks
}

radiusAccServerExtIndex OBJECT-TYPE
    SYNTAX     Integer32 (1..2147483647)
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
        "A number uniquely identifying each RADIUS
         Accounting server
 with which this client
         communicates."
    ::= { radiusAccServerExtEntry 1 }


radiusAccServerInetAddressType OBJECT-TYPE
      SYNTAX     InetAddressType
      MAX-ACCESS read-only
      STATUS     current
      DESCRIPTION
          "The type of address format used for the
           radiusAccServerInetAddress object."
```

```
        ::= { radiusAccServerExtEntry 2 }


 radiusAccServerInetAddress OBJECT-TYPE
        SYNTAX     InetAddress
        MAX-ACCESS read-only
        STATUS     current
        DESCRIPTION
            "The IP address of the RADIUS accounting
             server referred to in this table entry, using
             the version-neutral IP address format."
        ::= { radiusAccServerExtEntry 3 }

 radiusAccClientServerInetPortNumber  OBJECT-TYPE
        SYNTAX InetPortNumber ( 1..65535 )
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION



            "The UDP port the client is using
to send requests
             to this accounting server.  The value zero (0) is
             invalid."
        REFERENCE "RFC 2866 section 3"
        ::= { radiusAccServerExtEntry 4 }


radiusAccClientExtRoundTripTime  OBJECT-TYPE
    SYNTAX TimeTicks
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The time interval between the most recent
        Accounting-Response and the Accounting-Request that
        matched it from this RADIUS accounting server."
    REFERENCE "RFC 2866 section 2"
    ::= { radiusAccServerExtEntry 5 }

-- Request/Response statistics
--
-- Requests = Responses + PendingRequests + ClientTimeouts
--
-- Responses - MalformedResponses - BadAuthenticators -
-- UnknownTypes - PacketsDropped = Successfully received

radiusAccClientExtRequests OBJECT-TYPE
```

```
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Accounting-Request
 packets
         sent.  This does not include retransmissions.
         This counter may experience a discontinuity when the
         RADIUS Accounting Client module within the managed
         entity is reinitialized, as indicated by the current
         value of radiusAccClientCounterDiscontinuity."
    REFERENCE "RFC 2866 section 4.1"
    ::= { radiusAccServerExtEntry 6 }

radiusAccClientExtRetransmissions OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Accounting-Request packets
         retransmitted to this RADIUS accounting server.



         Retransmissions include retries where the
         Identifier and Acct-Delay have been updated, as
         well as those in which they remain the same.
         This counter may experience a discontinuity when the
         RADIUS Accounting Client module within the managed

   entity is reinitialized, as indicated by the current
         value of radiusAccClientCounterDiscontinuity."
    REFERENCE "RFC 2866 section 2"
    ::= { radiusAccServerExtEntry 7 }

radiusAccClientExtResponses OBJECT-TYPE
    SYNTAX Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS packets received on the
         accounting port from this server.  This counter
         may experience a discontinuity when the RADIUS
         Accounting Client module within the managed entity is
         reinitialized, as indicated by the current value of
```

```
            radiusAccClientCounterDiscontinuity."
        REFERENCE "RFC 2866 section 4.2"
        ::= { radiusAccServerExtEntry 8 }

    radiusAccClientExtMalformedResponses OBJECT-TYPE
        SYNTAX Counter32
        UNITS "packets"
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The number of malformed RADIUS Accounting-Response
             packets received from this server.  Malformed packets
             include packets with an invalid length.  Bad
             authenticators and unknown types are not included as
             malformed accounting responses.  This counter may
             experience a discontinuity when the RADIUS Accounting
             Client module within the managed entity is
             reinitialized, as indicated by the current
             value of radiusAccClientCounterDiscontinuity."
        REFERENCE "RFC 2866 section 3"
        ::= { radiusAccServerExtEntry 9 }

    radiusAccClientExtBadAuthenticators OBJECT-TYPE
        SYNTAX Counter32
        UNITS "packets"
        MAX-ACCESS read-only
        STATUS current



        DESCRIPTION
            "The number of RADIUS Accounting-Response
             packets that contained invalid authenticators
             received from this server.  This counter may
             experience a discontinuity when the RADIUS
             Accounting Client
     module within the managed
             entity is reinitialized, as indicated by the
             current value of
             radiusAccClientCounterDiscontinuity."
        REFERENCE "RFC 2866 section 3"
        ::= { radiusAccServerExtEntry 10 }

    radiusAccClientExtPendingRequests OBJECT-TYPE
        SYNTAX Gauge32
        UNITS "packets"
        MAX-ACCESS read-only
        STATUS current
```

```
    DESCRIPTION
        "The number of RADIUS Accounting-Request packets
         sent to this server that have not yet timed out or
         received a response.  This variable is incremented
         when an Accounting-Request is sent and decremented
         due to receipt of an Accounting-Response, a timeout,
         or a retransmission.  This counter may experience a
         discontinuity when the RADIUS Accounting Client module
         within the managed entity is reinitialized, as
         indicated by the current value of
         radiusAccClientCounterDiscontinuity."
     REFERENCE "RFC 2866 section 2"
    ::= { radiusAccServerExtEntry 11 }

radiusAccClientExtTimeouts OBJECT-TYPE
   SYNTAX Counter32
   UNITS "timeouts"
   MAX-ACCESS read-only
   STATUS current
   DESCRIPTION
       "The number of accounting timeouts to this server.
        After a timeout, the client may retry to the same
        server, send to a different server, or give up.
        A retry to the same server is counted as a
        retransmit as well as a timeout.  A send to a different
        server is counted as an Accounting-Request as well as
        a timeout.  This counter may experience a discontinuity
        when the RADIUS Accounting Client module within the
        managed entity is reinitialized, as indicated by the
        current value of radiusAccClientCounterDiscontinuity."
    REFERENCE "RFC 2866 section 2"



    ::= { radiusAccServerExtEntry  12 }

radiusAccClientExtUnknownTypes OBJECT-TYPE
    SYNTAX
 Counter32
    UNITS "packets"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS packets of unknown type that
         were received from this server on the accounting port.
         This counter may experience a discontinuity when the
         RADIUS Accounting Client module within the managed
         entity is reinitialized, as indicated by the current
```

```
            value of radiusAccClientCounterDiscontinuity."
        REFERENCE "RFC 2866 section 4"
        ::= { radiusAccServerExtEntry  13 }

    radiusAccClientExtPacketsDropped OBJECT-TYPE
        SYNTAX Counter32
        UNITS "packets"
        MAX-ACCESS read-only
        STATUS current
        DESCRIPTION
            "The number of RADIUS packets that were received from
            this server on the accounting port and dropped for some
            other reason.  This counter may experience a
            discontinuity when the RADIUS Accounting Client module
            within
     the managed entity is reinitialized, as indicated
            by the current value of
            radiusAccClientCounterDiscontinuity."
        ::= { radiusAccServerExtEntry  14 }

    radiusAccClientCounterDiscontinuity OBJECT-TYPE
            SYNTAX TimeTicks
            UNITS "centiseconds"
            MAX-ACCESS read-only
            STATUS current
            DESCRIPTION
                "The number of centiseconds since the last
                discontinuity in the RADIUS Accounting Client
                counters.  A discontinuity may be the result of a
                reinitialization of the RADIUS Accounting Client
                module within the managed entity."
            ::= { radiusAccServerExtEntry 15 }




    -- conformance information

    radiusAccClientMIBConformance  OBJECT IDENTIFIER
        ::= { radiusAccClientMIB 2 }

    radiusAccClientMIBCompliances  OBJECT IDENTIFIER
        ::= { radiusAccClientMIBConformance 1 }

    radiusAccClientMIBGroups  OBJECT IDENTIFIER
```

```
    ::= { radiusAccClientMIBConformance
 2 }


-- units of conformance

radiusAccClientMIBCompliance MODULE-COMPLIANCE
   STATUS  deprecated
   DESCRIPTION
        "The compliance statement for accounting clients
         implementing the RADIUS Accounting Client MIB.
         Implementation of this module is for IPv4-only
         entities, or for backwards compatibility use with
         entities that support both IPv4 and IPv6."
   MODULE  -- this module
      MANDATORY-GROUPS { radiusAccClientMIBGroup }

   ::= { radiusAccClientMIBCompliances 1 }


radiusAccClientExtMIBCompliance MODULE-COMPLIANCE
   STATUS  current
   DESCRIPTION
        "The compliance statement for accounting
         clients implementing the RADIUS Accounting
         Client IPv6 Extensions MIB.  Implementation of
         this module is for entities that support IPv6,
         or support IPv4 and IPv6."
   MODULE  -- this module
      MANDATORY-GROUPS { radiusAccClientExtMIBGroup }

   OBJECT
 radiusAccServerInetAddressType
   SYNTAX InetAddressType { ipv4(1), ipv6(2) }
   DESCRIPTION
        "An implementation is only required to support
         IPv4 and globally unique IPv6 addresses."

   OBJECT radiusAccServerInetAddress
   SYNTAX InetAddress ( SIZE (4|16) )
   DESCRIPTION



        "An implementation is only required to support
         IPv4 and globally unique IPv6 addresses."

   ::= { radiusAccClientMIBCompliances 2 }
```

```
-- units of conformance

radiusAccClientMIBGroup OBJECT-GROUP
   OBJECTS { radiusAccClientIdentifier,
             radiusAccClientInvalidServerAddresses,
             radiusAccServerAddress,
             radiusAccClientServerPortNumber,
             radiusAccClientRoundTripTime,
             radiusAccClientRequests,
             radiusAccClientRetransmissions,
             radiusAccClientResponses,
             radiusAccClientMalformedResponses,
             radiusAccClientBadAuthenticators,

          radiusAccClientPendingRequests,
             radiusAccClientTimeouts,
             radiusAccClientUnknownTypes,
             radiusAccClientPacketsDropped
          }
   STATUS  deprecated
   DESCRIPTION
        "The basic collection of objects providing management of
         RADIUS Accounting Clients."
   ::= { radiusAccClientMIBGroups 1 }


radiusAccClientExtMIBGroup OBJECT-GROUP
   OBJECTS { radiusAccClientIdentifier,
             radiusAccClientInvalidServerAddresses,
             radiusAccServerInetAddressType,
             radiusAccServerInetAddress,
             radiusAccClientServerInetPortNumber,
             radiusAccClientExtRoundTripTime,
             radiusAccClientExtRequests,
             radiusAccClientExtRetransmissions,
             radiusAccClientExtResponses,
             radiusAccClientExtMalformedResponses,
             radiusAccClientExtBadAuthenticators,
             radiusAccClientExtPendingRequests,

   radiusAccClientExtTimeouts,
             radiusAccClientExtUnknownTypes,
             radiusAccClientExtPacketsDropped,
             radiusAccClientCounterDiscontinuity
```

```
    }
  STATUS  current
  DESCRIPTION
      "The basic collection of objects providing management of
       RADIUS Accounting Clients."
  ::= { radiusAccClientMIBGroups 2 }


END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/RADIUS-ACC-CLIENT-MIB
No license file was found, but licenses were detected in source scan.

```
MIOX25-MIB DEFINITIONS  ::= BEGIN

IMPORTS
      Counter,
      TimeTicks
            FROM RFC1155-SMI
      OBJECT-TYPE
            FROM RFC-1212
      DisplayString, transmission,
      ifIndex
            FROM RFC1213-MIB
      InstancePointer
            FROM RFC1316-MIB
      X121Address
            FROM RFC1382-MIB
      PositiveInteger
            FROM RFC1381-MIB;

            -- IP over X.25 MIB

miox    OBJECT IDENTIFIER ::= { transmission 38 }

mioxPle        OBJECT IDENTIFIER ::= { miox 1 }
mioxPeer       OBJECT IDENTIFIER ::= { miox 2 }

-- ###############################################################
--             Ple Table
-- ###############################################################

-- Systems that implement RFC 1356 must also implement
-- all objects in this group.

mioxPleTable    OBJECT-TYPE
```

```
        SYNTAX  SEQUENCE OF MioxPleEntry
        ACCESS  not-accessible
         STATUS  mandatory
        DESCRIPTION
            "This table contains information relative to
            an interface to an X.25 Packet Level Entity
            (PLE)."
        ::= { mioxPle 1   }

    mioxPleEntry    OBJECT-TYPE
        SYNTAX  MioxPleEntry
        ACCESS  not-accessible
        STATUS  mandatory
        DESCRIPTION
            "These objects manage the encapsulation of
            other protocols within X.25."
        INDEX { ifIndex }
        ::= { mioxPleTable 1 }

    MioxPleEntry ::= SEQUENCE {
        mioxPleMaxCircuits
            INTEGER,
        mioxPleRefusedConnections
            Counter,
        mioxPleEnAddrToX121LkupFlrs
            Counter,
        mioxPleLastFailedEnAddr
            OCTET STRING,
        mioxPleEnAddrToX121LkupFlrTime
            TimeTicks,
        mioxPleX121ToEnAddrLkupFlrs
            Counter,
        mioxPleLastFailedX121Address
            X121Address,
        mioxPleX121ToEnAddrLkupFlrTime
             TimeTicks,
        mioxPleQbitFailures
            Counter,
        mioxPleQbitFailureRemoteAddress
            X121Address,
        mioxPleQbitFailureTime
            TimeTicks,
        mioxPleMinimumOpenTimer
            PositiveInteger,
        mioxPleInactivityTimer
            PositiveInteger,
        mioxPleHoldDownTimer
            PositiveInteger,
```

```
    mioxPleCollisionRetryTimer
        PositiveInteger,
    mioxPleDefaultPeerId
        InstancePointer
    }

mioxPleMaxCircuits OBJECT-TYPE
    SYNTAX  INTEGER (0..2147483647)
    ACCESS  read-write
    STATUS  mandatory
    DESCRIPTION
        "The maximum number of X.25 circuits that
        can be open at one time for this interface.
        A value of zero indicates the interface will
        not allow any additional circuits (as it may
        soon be shutdown).  A value of 2147483647
         allows an unlimited number of circuits."
    ::= { mioxPleEntry 1 }

mioxPleRefusedConnections OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The number of X.25 calls from a remote
        systems to this system that were cleared by
        this system.  The interface instance should
        identify the X.25 interface the call came in
        on."
    ::= { mioxPleEntry 2 }

mioxPleEnAddrToX121LkupFlrs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The number of times a translation from an
        Encapsulated Address to an X.121 address
        failed to find a corresponding X.121
        address.  Encapsulated addresses can be
        looked up in the mioxPeerTable or translated
        via an algorithm as for the DDN.  Addresses

        that are successfully recognized do not
        increment this counter.  Addresses that are
        not recognized (reflecting an abnormal
        packet delivery condition) increment this
        counter.
```

```
            If an address translation fails, it may be
            difficult to determine which PLE entry
            should count the failure.  In such cases the
            first likely entry in this table should be
            selected.  Agents should record the failure
            even if they are unsure which PLE should be
            associated with the failure."
        ::= { mioxPleEntry 3 }

    mioxPleLastFailedEnAddr OBJECT-TYPE
        SYNTAX  OCTET STRING (SIZE(2..128))
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
            "The last Encapsulated address that failed
            to find a corresponding X.121 address and
            caused mioxPleEnAddrToX121LkupFlrs
     to be
            incremented.  The first octet of this object
            contains the encapsulation type, the
            remaining octets contain the address of that
            type that failed.  Thus for an IP address,
            the length will be five octets, the first
            octet will contain 204 (hex CC), and the
            last four octets will contain the IP
            address.  For a snap encapsulation, the
            first byte would be 128 (hex 80) and the
            rest of the octet string would have the snap
            header."
        ::= { mioxPleEntry 4 }

    mioxPleEnAddrToX121LkupFlrTime OBJECT-TYPE
        SYNTAX  TimeTicks
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
            "The most recent value of sysUpTime when the
            translation from an Encapsulated Address to
            X.121 address failed to find a corresponding
            X.121 address."
         ::= { mioxPleEntry 5 }


    mioxPleX121ToEnAddrLkupFlrs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
```

```
        DESCRIPTION
            "The number of times the translation from an
            X.121 address to an Encapsulated Address
            failed to find a corresponding Encapsulated
            Address.  Addresses successfully recognized
            by an algorithm do not increment this
            counter.  This counter reflects the number
            of times call acceptance encountered the
            abnormal condition of not recognizing the
            peer."
        ::= { mioxPleEntry 6 }

    mioxPleLastFailedX121Address OBJECT-TYPE
        SYNTAX  X121Address
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
            "The last X.121 address that caused
            mioxPleX121ToEnAddrLkupFlrs to increase."
        ::= { mioxPleEntry 7 }

    mioxPleX121ToEnAddrLkupFlrTime
     OBJECT-TYPE
        SYNTAX  TimeTicks
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
            "The most recent value of sysUpTime when the
            translation from an X.121 address to an
            Encapsulated Address failed to find a
            corresponding Encapsulated Address."
        ::= { mioxPleEntry 8 }

    mioxPleQbitFailures OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
            "The number of times a connection was closed
            because of a Q-bit failure."
        ::= { mioxPleEntry 9 }

    mioxPleQbitFailureRemoteAddress OBJECT-TYPE
        SYNTAX  X121Address
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
            "The remote address of the most recent
```

```
            (last) connection that was closed because of
            a Q-bit failure."
        ::= { mioxPleEntry 10 }

mioxPleQbitFailureTime OBJECT-TYPE

       SYNTAX  TimeTicks
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
            "The most recent value of sysUpTime when a
            connection was closed because of a Q-bit
            failure.  This will also be the last time
            that mioxPleQbitFailures was incremented."
        ::= { mioxPleEntry 11 }

mioxPleMinimumOpenTimer OBJECT-TYPE
        SYNTAX  PositiveInteger
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
            "The minimum time in milliseconds this
            interface will keep a connection open before
            allowing it to be closed.  A value of zero
            indicates no timer."
        DEFVAL { 0 }
        ::= { mioxPleEntry 12 }

mioxPleInactivityTimer OBJECT-TYPE
        SYNTAX  PositiveInteger
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
            "The amount of time time in milliseconds
            this interface will
 keep an idle connection
            open before closing it.  A value of
            2147483647 indicates no timer."
        DEFVAL { 10000 }
        ::= { mioxPleEntry 13 }

mioxPleHoldDownTimer    OBJECT-TYPE
        SYNTAX  PositiveInteger
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
            "The hold down timer in milliseconds.  This
            is the minimum amount of time to wait before
```

trying another call to a host that was
previously unsuccessful. A value of
2147483647 indicates the host will not be
retried."
DEFVAL { 0 }
::= { mioxPleEntry 14 }

mioxPleCollisionRetryTimer OBJECT-TYPE
SYNTAX PositiveInteger
ACCESS read-write
STATUS mandatory
DESCRIPTION
"The Collision Retry Timer in milliseconds.
The time to delay between call attempts when
the maximum number of circuits
is exceeded
in a call attempt."
DEFVAL { 0 }
::= { mioxPleEntry 15 }

mioxPleDefaultPeerId OBJECT-TYPE
SYNTAX InstancePointer
ACCESS read-write
STATUS mandatory
DESCRIPTION
"This identifies the instance of the index
in the mioxPeerTable for the default
parameters to use with this interface.

The entry identified by this object may have
a zero length Encapsulation address and a
zero length X.121 address.

These default parameters are used with
connections to hosts that do not have
entries in the mioxPeerTable. Such
connections occur when using ddn-x25 IP-X.25
address mapping or when accepting
connections from other hosts not in the
mioxPeerTable.

The mioxPeerEncTable entry with the same

index as the mioxPeerTable entry specifies
the call encapsulation types this PLE will
accept for peers not in the mioxPeerTable.
If the mioxPeerEncTable doesn't contain any

```
            entries, this PLE will not accept calls from
            entries not in the mioxPeerTable."
        ::= { mioxPleEntry 16 }



-- ###########################################################
--              Peer Table
-- ###########################################################

-- Systems that implement RFC 1356 must also implement
-- all objects in this group.

mioxPeerTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF MioxPeerEntry
        ACCESS  not-accessible
        STATUS  mandatory
        DESCRIPTION
            "This table contains information about the
            possible peers this machine may exchange
            packets with."
        ::= { mioxPeer 1 }

mioxPeerEntry OBJECT-TYPE
        SYNTAX  MioxPeerEntry

 ACCESS  not-accessible
        STATUS  mandatory
        DESCRIPTION
            "Per peer information."
        INDEX { mioxPeerIndex   }
        ::= { mioxPeerTable 1 }


MioxPeerEntry ::= SEQUENCE {
        mioxPeerIndex
            PositiveInteger,
        mioxPeerStatus
            INTEGER,
        mioxPeerMaxCircuits
            PositiveInteger,
        mioxPeerIfIndex
            PositiveInteger,
        mioxPeerConnectSeconds
            Counter,
        mioxPeerX25CallParamId
            InstancePointer,
        mioxPeerEnAddr
```

```
            OCTET STRING,
        mioxPeerX121Address
            X121Address,
        mioxPeerX25CircuitId
            InstancePointer,
        mioxPeerDescr
            DisplayString
        }

mioxPeerIndex   OBJECT-TYPE
        SYNTAX  PositiveInteger
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
            "An index value that distinguished one entry
            from another.
  This index is independent of
            any other index."
        ::= { mioxPeerEntry 1 }

-- Systems can claim conformance with this MIB without
-- implementing sets to mioxPeerStatus with a value of
-- clearCall or makeCall.
-- All other defined values must be accepted.
-- Implementors should realize that allowing these values
-- provides richer management, and implementations
-- are encouraged to accept these values.
mioxPeerStatus OBJECT-TYPE
        SYNTAX  INTEGER {
                    valid (1),
                    createRequest (2),
                    underCreation (3),
                    invalid (4),
                    clearCall (5),
                    makeCall (6)
                    }
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
            "This reports the status of a peer entry.
            A value of valid indicates a normal entry
            that is in use by the agent.  A value of

          underCreation indicates a newly created
            entry which isn't yet in use because the
            creating management station is still setting
            values.
```

The value of invalid indicates the entry is no longer in use and the agent is free to delete the entry at any time. A management station is also free to use an entry in the invalid state.

Entries are created by setting a value of createRequest. Only non-existent or invalid entries can be set to createRequest. Upon receiving a valid createRequest, the agent will create an entry in the underCreation state. This object can not be set to a value of underCreation directly, entries can only be created by setting a value of createRequest. Entries that exist in other

than the invalid state can not be set to createRequest.

Entries with a value of underCreation are not used by the system and the management station can change the values of other objects in the table entry. Management stations should also remember to configure values in the mioxPeerEncTable with the same peer index value as this peer entry.

An entry in the underCreation state can be set to valid or invalid. Entries in the underCreation state will stay in that state until 1) the agent times them out, 2) they are set to valid, 3) they are set to invalid. If an agent notices an entry has been in the underCreation state for an abnormally long time, it may decide the management station has failed and invalidate

the entry. A prudent agent will understand that the management station may need to wait for human input and will allow for that possibility in its determination of this abnormally long period.

Once a management station has completed all fields of an entry, it will set a value of valid. This causes the entry to be activated.

Entries in the valid state may also be set
to makeCall or clearCall to make or clear
X.25 calls to the peer. After such a set
request the entry will still be in the valid
state. Setting a value of makeCall causes
the agent to initiate an X.25 call request
to the peer specified by the entry. Setting
a value of clearCall causes the agent to
initiate clearing one X.25 call present
to
the peer. Each set request will initiate
another call or clear request (up to the
maximum allowed); this means that management
stations that fail to get a response to a
set request should query to see if a call
was in fact placed or cleared before
retrying the request. Entries not in the
valid state can not be set to makeCall or
clearCall.

The values of makeCall and clearCall provide
for circuit control on devices which perform
Ethernet Bridging using static circuit
assignment without address recognition;
other devices which dynamically place calls
based on destination addresses may reject
such requests.

An agent that (re)creates a new entry
because of a set with createRequest, should

also (re)create a mioxPeerEncTable entry
with a mioxPeerEncIndex of 1, and a
mioxPeerEncType of 204 (hex CC)."
::= { mioxPeerEntry 2 }

mioxPeerMaxCircuits OBJECT-TYPE
SYNTAX PositiveInteger
ACCESS read-write
STATUS mandatory
DESCRIPTION
"The maximum number of X.25 circuits allowed
to this peer."
DEFVAL { 1 }
::= { mioxPeerEntry 3 }

mioxPeerIfIndex OBJECT-TYPE
SYNTAX PositiveInteger

```
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
                "The value of the ifIndex object for the
                interface to X.25 to use to call the peer."
        DEFVAL { 1 }
        ::= { mioxPeerEntry 4 }

mioxPeerConnectSeconds OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        DESCRIPTION
                "The number of seconds a call to this peer
                was active.  This counter
 will be
                incremented by one for every second a
                connection to a peer was open.  If two calls
                are open at the same time, one second of
                elapsed real time will results in two
                seconds of connect time."
        ::= { mioxPeerEntry 5 }

mioxPeerX25CallParamId OBJECT-TYPE
        SYNTAX  InstancePointer
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
                "The instance of the index object in the
                x25CallParmTable from RFC 1382 for the X.25
                call parameters used to communicate with the
                remote host.  The well known value {0 0}
                indicates no call parameters specified."
        DEFVAL { {0 0} }
        ::= { mioxPeerEntry 6 }

mioxPeerEnAddr  OBJECT-TYPE
        SYNTAX    OCTET STRING (SIZE (0..128))
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
                "The Encapsulation address of the remote
                 host mapped by this table entry.  A length
                of zero indicates the remote IP address is
                unknown or unspecified for use as a PLE
                default.

                The first octet of this object contains the
```

```
            encapsulation type, the remaining octets
            contain an address of that type.  Thus for
            an IP address, the length will be five
            octets, the first octet will contain 204
            (hex CC), and the last four octets will
            contain the IP address.  For a snap
            encapsulation, the first byte would be 128
            (hex 80) and the rest of the octet string
            would have the snap header."
        DEFVAL { "h }
        ::= { mioxPeerEntry 7 }

mioxPeerX121Address OBJECT-TYPE
        SYNTAX  X121Address
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
            "The X.25 address of the remote
 host mapped
            by this table entry.  A zero length string
            indicates the X.25 address is unspecified
            for use as the PLE default."
        DEFVAL { "h }
        ::= { mioxPeerEntry 8 }

-- Systems can claim conformance to this MIB without
-- implementing sets to mioxPeerX25CircuitId.
-- However systems that use PVCs with RFC1356
-- are encouraged to implement sets.
mioxPeerX25CircuitId OBJECT-TYPE
        SYNTAX  InstancePointer
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
            "This object identifies the instance of the
            index for the X.25 circuit open to the peer
            mapped by this table entry.  The well known
            value {0 0} indicates no connection
            currently active.  For multiple connections,
            this identifies the index of a multiplexing
            table entry for the connections.  This can
            only be written to configure
 use of PVCs
            which means the identified circuit table
            entry for a write must be a PVC."
        DEFVAL { {0 0} }
        ::= { mioxPeerEntry 9 }
```

```
mioxPeerDescr   OBJECT-TYPE
      SYNTAX  DisplayString (SIZE (0..255))
      ACCESS  read-write
      STATUS  mandatory
      DESCRIPTION
            "This object returns any identification
            information about the peer.  An agent may
            supply the comment information found in the
            configuration file entry for this peer.  A
            zero length string indicates no information
            available."
      DEFVAL { "h }
      ::= { mioxPeerEntry 10 }



-- ###########################################################
--            Peer Encapsulation Table
-- ###########################################################

mioxPeerEncTable OBJECT-TYPE
      SYNTAX  SEQUENCE OF MioxPeerEncEntry
      ACCESS  not-accessible
      STATUS
  mandatory
      DESCRIPTION
            "This table contains the list of
            encapsulations used to communicate with a
            peer.  This table has two indexes, the first
            identifies the peer, the second
            distinguishes encapsulation types.

            The first index identifies the corresponding
            entry in the mioxPeerTable.  The second
            index gives the priority of the different
            encapsulations.

            The encapsulation types are ordered in
            priority order.  For calling a peer, the
            first entry (mioxPeerEncIndex of 1) is tried
            first.  If the call doesn't succeed because
            the remote host clears the call due to
            incompatible call user data, the next entry
            in the list is tried.  Each entry is tried
            until the list is exhausted.

            For answering a call, the
```

```
 encapsulation type
            requested by the peer must be found the list
            or the call will be refused.  If there are
            no entries in this table for a peer, all
            call requests from the peer will be refused.

            Objects in this table can only be set when
            the mioxPeerStatus object with the same
            index has a value of underCreation.  When
            that status object is set to invalid and
            deleted, the entry in this table with that
            peer index must also be deleted."
        ::= { mioxPeer 2 }

mioxPeerEncEntry OBJECT-TYPE
        SYNTAX  MioxPeerEncEntry
        ACCESS  not-accessible
        STATUS  mandatory
        DESCRIPTION
            "Per connection information."
        INDEX { mioxPeerIndex, mioxPeerEncIndex}
        ::= { mioxPeerEncTable 1 }

MioxPeerEncEntry ::= SEQUENCE {
        mioxPeerEncIndex
            PositiveInteger,
        mioxPeerEncType
             INTEGER
        }

mioxPeerEncIndex        OBJECT-TYPE
        SYNTAX  PositiveInteger
        ACCESS  read-only
        STATUS    mandatory
        DESCRIPTION
            "The second index in the table which
            distinguishes different encapsulation
            types."
        ::= { mioxPeerEncEntry 1 }

mioxPeerEncType OBJECT-TYPE
        SYNTAX  INTEGER (0..256)
        ACCESS  read-write
        STATUS  mandatory
        DESCRIPTION
            "The value of the encapsulation type.  For
            IP encapsulation this will have a value of
            204 (hex CC).  For SNAP encapsulated
```

```
            packets, this will have a value of 128 (hex
            80).  For CLNP, ISO 8473, this will have a
            value of 129 (hex 81).  For ES-ES, ISO 9542,
            this will have a value of 130 (hex 82).  A
            value of 197 (hex C5) identifies the Blacker
            X.25 encapsulation.  A value
 of 0,
            identifies the Null encapsulation.

            This value can only be written when the
            mioxPeerStatus object with the same
            mioxPeerIndex has a value of underCreation.
            Setting this object to a value of 256
            deletes the entry.  When deleting an entry,
            all other entries in the mioxPeerEncTable
            with the same mioxPeerIndex and with an
            mioxPeerEncIndex higher then the deleted
            entry, will all have their mioxPeerEncIndex
            values decremented by one."
      ::= { mioxPeerEncEntry 2 }

-- ##############################################################

END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/MIOX25-MIB
No license file was found, but licenses were detected in source scan.

RFC1158-MIB DEFINITIONS ::= BEGIN

IMPORTS
      mgmt, OBJECT-TYPE, NetworkAddress, IpAddress,
      Counter, Gauge, TimeTicks
         FROM RFC1155-SMI;

DisplayString ::=
         OCTET STRING

mib-2      OBJECT IDENTIFIER ::= { mgmt 1 }     -- MIB-II
         -- (same prefix as MIB-I)

system     OBJECT IDENTIFIER ::= { mib-2 1 }
interfaces OBJECT IDENTIFIER ::= { mib-2 2 }
at         OBJECT IDENTIFIER ::= { mib-2 3 }
ip         OBJECT IDENTIFIER ::= { mib-2 4 }
icmp       OBJECT IDENTIFIER ::= { mib-2 5 }
tcp        OBJECT IDENTIFIER ::= { mib-2 6 }
```

```
udp        OBJECT IDENTIFIER ::= { mib-2 7 }
egp        OBJECT IDENTIFIER ::= { mib-2 8 }
-- cmot    OBJECT IDENTIFIER ::= { mib-2 9 }
transmission OBJECT IDENTIFIER ::= { mib-2 10 }
snmp       OBJECT IDENTIFIER ::= { mib-2 11 }


-- object types

-- the System group

sysDescr OBJECT-TYPE
      SYNTAX  DisplayString (SIZE (0..255))
      ACCESS  read-only
       STATUS  mandatory
      ::= { system 1 }

sysObjectID OBJECT-TYPE
      SYNTAX  OBJECT IDENTIFIER
      ACCESS  read-only
      STATUS  mandatory
      ::= { system 2 }

sysUpTime OBJECT-TYPE
      SYNTAX  TimeTicks
      ACCESS  read-only
      STATUS  mandatory
      ::= { system 3 }

sysContact OBJECT-TYPE
      SYNTAX  DisplayString (SIZE (0..255))
      ACCESS  read-write
      STATUS  mandatory
      ::= { system 4 }

sysName OBJECT-TYPE
      SYNTAX  DisplayString (SIZE (0..255))
      ACCESS  read-write
      STATUS  mandatory
      ::= { system 5 }

sysLocation OBJECT-TYPE
      SYNTAX  DisplayString (SIZE (0..255))
      ACCESS  read-only
      STATUS  mandatory
      ::= { system 6 }

sysServices OBJECT-TYPE
```

```
        SYNTAX  INTEGER (0..127)
        ACCESS  read-only
        STATUS  mandatory
        ::= { system 7 }


-- the Interfaces group

ifNumber OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-only
        STATUS
    mandatory
        ::= { interfaces 1 }

-- the Interfaces table

ifTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF IfEntry
        ACCESS  read-only
        STATUS  mandatory
        ::= { interfaces 2 }

ifEntry OBJECT-TYPE
        SYNTAX  IfEntry
        ACCESS  read-only
        STATUS  mandatory
        ::= { ifTable 1 }

IfEntry ::= SEQUENCE {
    ifIndex
        INTEGER,
    ifDescr
        DisplayString,
    ifType
        INTEGER,
    ifMtu
        INTEGER,
    ifSpeed
        Gauge,
    ifPhysAddress
        OCTET STRING,
    ifAdminStatus
        INTEGER,
    ifOperStatus
        INTEGER,
    ifLastChange
        TimeTicks,
```

```
  ifInOctets
     Counter,
  ifInUcastPkts
     Counter,
  ifInNUcastPkts
     Counter,
  ifInDiscards
     Counter,
  ifInErrors
     Counter,
  ifInUnknownProtos
     Counter,
  ifOutOctets
     Counter,
  ifOutUcastPkts
     Counter,
  ifOutNUcastPkts
     Counter,
  ifOutDiscards
     Counter,
  ifOutErrors
      Counter,
  ifOutQLen
     Gauge,
  ifSpecific
     OBJECT IDENTIFIER
}

ifIndex OBJECT-TYPE
     SYNTAX  INTEGER
     ACCESS  read-only
     STATUS  mandatory
     ::= { ifEntry 1 }

ifDescr OBJECT-TYPE
     SYNTAX  DisplayString (SIZE (0..255))
     ACCESS  read-only
     STATUS  mandatory
     ::= { ifEntry 2 }

ifType OBJECT-TYPE
     SYNTAX  INTEGER {
               other(1),           -- none of the
                                   -- following
               regular1822(2),
               hdh1822(3),
               ddn-x25(4),
               rfc877-x25(5),
```

```
                ethernet-csmacd(6),
                iso88023-csmacd(7),
                iso88024-tokenBus(8),
                iso88025-tokenRing(9),
                iso88026-man(10),
                starLan(11),
                proteon-10Mbit(12),
                proteon-80Mbit(13),
                hyperchannel(14),
                 fddi(15),
                lapb(16),
                sdlc(17),
                t1-carrier(18),
                cept(19),       -- european
                              --equivalent of T-1
                basicISDN(20),
                primaryISDN(21),
                                -- proprietary
                                -- serial
                propPointToPointSerial(22),
                terminalServer-asyncPort(23),
                softwareLoopback(24),
                eon(25),             -- CLNP over IP
                ethernet-3Mbit(26),
                nsip(27),            -- XNS over IP
                slip(28)             -- generic SLIP
            }
        ACCESS  read-only
        STATUS  mandatory
        ::= { ifEntry 3 }

    ifMtu OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-only
        STATUS  mandatory
        ::= { ifEntry 4 }

    ifSpeed
     OBJECT-TYPE
        SYNTAX  Gauge
        ACCESS  read-only
        STATUS  mandatory
        ::= { ifEntry 5 }

    ifPhysAddress OBJECT-TYPE
        SYNTAX  OCTET STRING
        ACCESS  read-only
        STATUS  mandatory
```

```
    ::= { ifEntry 6 }

ifAdminStatus OBJECT-TYPE
    SYNTAX  INTEGER {
            up(1),     -- ready to pass packets
            down(2),
            testing(3) -- in some test mode
          }
    ACCESS  read-write
    STATUS  mandatory
    ::= { ifEntry 7 }

ifOperStatus OBJECT-TYPE
    SYNTAX  INTEGER {
            up(1),     -- ready to pass packets
            down(2),
            testing(3) -- in some test mode
          }
    ACCESS  read-only
    STATUS  mandatory
    ::= { ifEntry 8 }

ifLastChange OBJECT-TYPE
    SYNTAX  TimeTicks
    ACCESS  read-only
    STATUS  mandatory
    ::= { ifEntry 9 }

ifInOctets OBJECT-TYPE
    SYNTAX  Counter
     ACCESS  read-only
    STATUS  mandatory
    ::= { ifEntry 10 }

ifInUcastPkts OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { ifEntry 11 }

ifInNUcastPkts OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { ifEntry 12 }

ifInDiscards OBJECT-TYPE
    SYNTAX  Counter
```

```
        ACCESS  read-only
        STATUS  mandatory
        ::= { ifEntry 13 }

    ifInErrors OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ifEntry 14 }

    ifInUnknownProtos OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ifEntry 15 }

    ifOutOctets OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ifEntry 16 }

    ifOutUcastPkts OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ifEntry 17 }

    ifOutNUcastPkts
     OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ifEntry 18 }

    ifOutDiscards OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ifEntry 19 }

    ifOutErrors OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ifEntry 20 }

    ifOutQLen OBJECT-TYPE
```

```
        SYNTAX  Gauge
        ACCESS  read-only
        STATUS  mandatory
        ::= { ifEntry 21 }

ifSpecific OBJECT-TYPE
        SYNTAX  OBJECT IDENTIFIER
        ACCESS  read-only
        STATUS  mandatory
        ::= { ifEntry 22 }

nullSpecific OBJECT IDENTIFIER ::= { 0 0 }

-- the Address Translation group (deprecated)

atTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF AtEntry
        ACCESS  read-write
        STATUS  deprecated
        ::= { at 1 }

atEntry OBJECT-TYPE
        SYNTAX  AtEntry
        ACCESS  read-write
        STATUS  deprecated
        ::= { atTable 1 }

AtEntry ::=
 SEQUENCE {
   atIfIndex
        INTEGER,
   atPhysAddress
        OCTET STRING,
   atNetAddress
        NetworkAddress
}

atIfIndex OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-write
        STATUS  deprecated
        ::= { atEntry 1 }

atPhysAddress OBJECT-TYPE
        SYNTAX  OCTET STRING
        ACCESS  read-write
        STATUS  deprecated
        ::= { atEntry 2 }
```

```
atNetAddress OBJECT-TYPE
      SYNTAX  NetworkAddress
      ACCESS  read-write
      STATUS  deprecated
      ::= { atEntry 3 }


-- the IP group

ipForwarding OBJECT-TYPE
      SYNTAX  INTEGER {
                gateway(1), -- entity forwards
                        -- datagrams
                host(2)     -- entity does NOT
                        -- forward datagrams
              }
      ACCESS  read-write
      STATUS  mandatory
      ::= { ip 1 }

ipDefaultTTL OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-write
      STATUS  mandatory
      ::=
 { ip 2 }

ipInReceives OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { ip 3 }

ipInHdrErrors OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { ip 4 }

ipInAddrErrors OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { ip 5 }

ipForwDatagrams OBJECT-TYPE
      SYNTAX  Counter
```

```
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 6 }

ipInUnknownProtos OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 7 }

ipInDiscards OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 8 }

ipInDelivers OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 9 }

ipOutRequests OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= {
 ip 10 }

ipOutDiscards OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 11 }

ipOutNoRoutes OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 12 }

ipReasmTimeout OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 13 }

ipReasmReqds OBJECT-TYPE
```

```
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 14 }

ipReasmOKs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 15 }

ipReasmFails OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 16 }

ipFragOKs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 17 }

ipFragFails OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 18 }

ipFragCreates
 OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 19 }

-- the IP Interface table

ipAddrTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF IpAddrEntry
        ACCESS  read-only
        STATUS  mandatory
        ::= { ip 20 }

ipAddrEntry OBJECT-TYPE
        SYNTAX  IpAddrEntry
        ACCESS  read-only
        STATUS  mandatory
```

```
      ::= { ipAddrTable 1 }

IpAddrEntry ::= SEQUENCE {
  ipAdEntAddr
     IpAddress,
  ipAdEntIfIndex
     INTEGER,
  ipAdEntNetMask
     IpAddress,
  ipAdEntBcastAddr
     INTEGER,
  ipAdEntReasmMaxSize
     INTEGER (0..65535)
}

ipAdEntAddr OBJECT-TYPE
      SYNTAX  IpAddress
      ACCESS  read-only
      STATUS  mandatory
      ::=  { ipAddrEntry 1 }

ipAdEntIfIndex OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-only
      STATUS  mandatory
      ::=  { ipAddrEntry 2 }

ipAdEntNetMask OBJECT-TYPE
      SYNTAX  IpAddress
      ACCESS  read-only
       STATUS  mandatory
      ::=  { ipAddrEntry 3 }

ipAdEntBcastAddr OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-only
      STATUS  mandatory
      ::= { ipAddrEntry 4 }

ipAdEntReasmMaxSize OBJECT-TYPE
      SYNTAX  INTEGER (0..65535)
      ACCESS  read-only
      STATUS  mandatory
      ::= { ipAddrEntry 5 }

-- the IP Routing table

ipRoutingTable OBJECT-TYPE
```

```
        SYNTAX  SEQUENCE OF IpRouteEntry
        ACCESS  read-write
        STATUS  mandatory
        ::= { ip 21 }

ipRouteEntry OBJECT-TYPE
        SYNTAX  IpRouteEntry
        ACCESS  read-write
        STATUS  mandatory
        ::= { ipRoutingTable 1 }

IpRouteEntry ::= SEQUENCE {
  ipRouteDest
      IpAddress,
  ipRouteIfIndex
      INTEGER,
  ipRouteMetric1
      INTEGER,
  ipRouteMetric2
      INTEGER,
  ipRouteMetric3
      INTEGER,
  ipRouteMetric4
      INTEGER,
  ipRouteNextHop
      IpAddress,
  ipRouteType
      INTEGER,
  ipRouteProto
      INTEGER,
   ipRouteAge
      INTEGER,
  ipRouteMask
      IpAddress
}

ipRouteDest OBJECT-TYPE
        SYNTAX  IpAddress
        ACCESS  read-write
        STATUS  mandatory
        ::= { ipRouteEntry 1 }

ipRouteIfIndex  OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-write
        STATUS  mandatory
        ::= { ipRouteEntry 2 }
```

```
ipRouteMetric1 OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipRouteEntry 3 }

ipRouteMetric2 OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipRouteEntry 4 }

ipRouteMetric3 OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipRouteEntry 5 }

ipRouteMetric4 OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipRouteEntry 6 }

ipRouteNextHop OBJECT-TYPE
      SYNTAX  IpAddress
      ACCESS  read-write
      STATUS  mandatory

    ::= { ipRouteEntry 7 }

ipRouteType OBJECT-TYPE
      SYNTAX  INTEGER {
                other(1),    -- none of the following

                invalid(2),  -- an invalidated route

                        -- route to directly
                direct(3),   -- connected
                        -- (sub-)network

                        -- route to a non-local
                remote(4)    -- host/network/
                        -- sub-network
           }
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipRouteEntry 8 }
```

```
ipRouteProto OBJECT-TYPE
    SYNTAX  INTEGER {
            other(1),    -- none of the following

                    -- non-protocol
                    -- information

                    --   e.g., manually
            local(2),    --   configured entries

                    -- set via a network
            netmgmt(3),
 --   management protocol

                    -- obtained via ICMP,
            icmp(4),     --   e.g., Redirect

                    -- the following are
                    -- gateway routing
                    -- protocols
            egp(5),
            ggp(6),
            hello(7),
            rip(8),
            is-is(9),
            es-is(10),
            ciscoIgrp(11),
            bbnSpfIgp(12),
            ospf(13),
            bgp(14)
        }
    ACCESS  read-only
    STATUS  mandatory
    ::= { ipRouteEntry 9 }

ipRouteAge OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-write
    STATUS  mandatory
    ::= { ipRouteEntry 10 }

ipRouteMask OBJECT-TYPE
    SYNTAX  IpAddress
    ACCESS  read-write
    STATUS  mandatory
    ::= { ipRouteEntry 11 }
```

```
-- the IP Address Translation tables

ipNetToMediaTable
 OBJECT-TYPE
      SYNTAX  SEQUENCE OF IpNetToMediaEntry
      ACCESS  read-write
      STATUS  mandatory
      ::= { ip 22 }

ipNetToMediaEntry OBJECT-TYPE
      SYNTAX  IpNetToMediaEntry
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipNetToMediaTable 1 }

IpNetToMediaEntry ::= SEQUENCE {
  ipNetToMediaIfIndex
      INTEGER,
  ipNetToMediaPhysAddress
      OCTET STRING,
  ipNetToMediaNetAddress
      IpAddress,
  ipNetToMediaType
      INTEGER
}

ipNetToMediaIfIndex OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipNetToMediaEntry 1 }

ipNetToMediaPhysAddress OBJECT-TYPE
      SYNTAX  OCTET STRING
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipNetToMediaEntry 2 }

ipNetToMediaNetAddress OBJECT-TYPE
      SYNTAX  IpAddress
      ACCESS  read-write
      STATUS  mandatory
      ::= { ipNetToMediaEntry 3 }

ipNetToMediaType OBJECT-TYPE

    SYNTAX  INTEGER {
              other(1),   -- none of the following
```

```
                invalid(2), -- an invalidated mapping
                dynamic(3), -- connected (sub-)network

                static(4)
            }
        ACCESS  read-write
        STATUS  mandatory
        ::= { ipNetToMediaEntry 4 }

-- the ICMP group

icmpInMsgs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 1 }

icmpInErrors OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 2 }

icmpInDestUnreachs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 3 }

icmpInTimeExcds OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 4 }

icmpInParmProbs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 5 }

icmpInSrcQuenchs
 OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 6 }
```

```
icmpInRedirects OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 7 }

icmpInEchos OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 8 }

icmpInEchoReps OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 9 }

icmpInTimestamps OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 10 }

icmpInTimestampReps OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 11 }

icmpInAddrMasks OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 12 }

icmpInAddrMaskReps OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory

  ::= { icmp 13 }

icmpOutMsgs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
```

```
    ::= { icmp 14 }

icmpOutErrors OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 15 }

icmpOutDestUnreachs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 16 }

icmpOutTimeExcds OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 17 }

icmpOutParmProbs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 18 }

icmpOutSrcQuenchs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 19 }

icmpOutRedirects OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { icmp 20 }

icmpOutEchos OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
     STATUS  mandatory
    ::= { icmp 21 }

icmpOutEchoReps OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
```

```
        ::= { icmp 22 }

icmpOutTimestamps OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 23 }

icmpOutTimestampReps OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 24 }

icmpOutAddrMasks OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 25 }

icmpOutAddrMaskReps OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { icmp 26 }


-- the TCP group

tcpRtoAlgorithm OBJECT-TYPE
        SYNTAX  INTEGER {
                    other(1),    -- none of the following
                    constant(2), -- a constant rto
                    rsre(3),     -- MIL-STD-1778,
                                 -- Appendix B

        vanj(4)      -- Van Jacobson's
                     -- algorithm
              }
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcp 1 }

tcpRtoMin OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcp 2 }
```

```
tcpRtoMax OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-only
    STATUS  mandatory
    ::= { tcp 3 }

tcpMaxConn OBJECT-TYPE
    SYNTAX  INTEGER
    ACCESS  read-only
    STATUS  mandatory
    ::= { tcp 4 }

tcpActiveOpens OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { tcp 5 }

tcpPassiveOpens OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { tcp 6 }

tcpAttemptFails OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::= { tcp 7 }

tcpEstabResets OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only

   STATUS  mandatory
    ::= { tcp 8 }

tcpCurrEstab OBJECT-TYPE
    SYNTAX  Gauge
    ACCESS  read-only
    STATUS  mandatory
    ::= { tcp 9 }

tcpInSegs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
```

```
        ::= { tcp 10 }

tcpOutSegs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcp 11 }

tcpRetransSegs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcp 12 }

-- the TCP connections table

tcpConnTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF TcpConnEntry
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcp 13 }

tcpConnEntry OBJECT-TYPE
        SYNTAX  TcpConnEntry
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcpConnTable 1 }

TcpConnEntry ::= SEQUENCE {
    tcpConnState
        INTEGER,
    tcpConnLocalAddress
        IpAddress,
    tcpConnLocalPort
        INTEGER (0..65535),
     tcpConnRemAddress
        IpAddress,
    tcpConnRemPort
        INTEGER (0..65535)
}

tcpConnState OBJECT-TYPE
        SYNTAX  INTEGER {
                    closed(1),
                    listen(2),
                    synSent(3),
                    synReceived(4),
                    established(5),
```

```
                finWait1(6),
                finWait2(7),
                closeWait(8),
                lastAck(9),
                closing(10),
                timeWait(11)
            }
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcpConnEntry 1 }

tcpConnLocalAddress OBJECT-TYPE
        SYNTAX  IpAddress
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcpConnEntry 2 }

tcpConnLocalPort OBJECT-TYPE
        SYNTAX  INTEGER (0..65535)
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcpConnEntry 3 }

tcpConnRemAddress OBJECT-TYPE
        SYNTAX  IpAddress
        ACCESS  read-only
        STATUS  mandatory
         ::= { tcpConnEntry 4 }

tcpConnRemPort OBJECT-TYPE
        SYNTAX  INTEGER (0..65535)
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcpConnEntry 5 }

-- additional TCP variables

tcpInErrs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcp 14 }

tcpOutRsts OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { tcp 15 }
```

```
-- the UDP group

udpInDatagrams OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { udp 1 }

udpNoPorts OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { udp 2 }

udpInErrors OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { udp 3 }

udpOutDatagrams OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { udp 4 }

-- the UDP listener table

udpTable
 OBJECT-TYPE
      SYNTAX  SEQUENCE OF UdpEntry
      ACCESS  read-only
      STATUS  mandatory
      ::= { udp 5 }

udpEntry OBJECT-TYPE
      SYNTAX  UdpEntry
      ACCESS  read-only
      STATUS  mandatory
      ::= { udpTable 1 }

UdpEntry ::= SEQUENCE {
  udpLocalAddress
      IpAddress,
  udpLocalPort
      INTEGER (0..65535)
```

```
}

udpLocalAddress OBJECT-TYPE
      SYNTAX  IpAddress
      ACCESS  read-only
      STATUS  mandatory
      ::= { udpEntry 1 }

udpLocalPort OBJECT-TYPE
      SYNTAX  INTEGER (0..65535)
      ACCESS  read-only
      STATUS  mandatory
      ::= { udpEntry 2 }

-- the EGP group

egpInMsgs OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { egp 1 }

egpInErrors OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { egp 2 }

egpOutMsgs OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
       ::= { egp 3 }

egpOutErrors OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::= { egp 4 }

-- the EGP Neighbor table

egpNeighTable OBJECT-TYPE
      SYNTAX  SEQUENCE OF EgpNeighEntry
      ACCESS  read-only
      STATUS  mandatory
      ::= { egp 5 }
```

```
egpNeighEntry OBJECT-TYPE
      SYNTAX  EgpNeighEntry
      ACCESS  read-only
      STATUS  mandatory
      ::= { egpNeighTable 1 }

EgpNeighEntry ::= SEQUENCE {
  egpNeighState
     INTEGER,
  egpNeighAddr
     IpAddress,
  egpNeighAs
     INTEGER,
  egpNeighInMsgs
     Counter,
  egpNeighInErrs
     Counter,
  egpNeighOutMsgs
     Counter,
  egpNeighOutErrs
     Counter,
  egpNeighInErrMsgs
     Counter,
  egpNeighOutErrMsgs
     Counter,
  egpNeighStateUps
     Counter,
  egpNeighStateDowns
     Counter,
  egpNeighIntervalHello
     INTEGER,
  egpNeighIntervalPoll
     INTEGER,
  egpNeighMode
      INTEGER,
  egpNeighEventTrigger
     INTEGER
}

egpNeighState OBJECT-TYPE
      SYNTAX  INTEGER {
                idle(1),
                acquisition(2),
                down(3),
                up(4),
                cease(5)
              }
      ACCESS  read-only
```

```
        STATUS  mandatory
        ::= { egpNeighEntry 1 }

egpNeighAddr OBJECT-TYPE
        SYNTAX  IpAddress
        ACCESS  read-only
        STATUS  mandatory
        ::= { egpNeighEntry 2 }

egpNeighAs OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-only
        STATUS  mandatory
        ::= { egpNeighEntry 3 }

egpNeighInMsgs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { egpNeighEntry 4 }

egpNeighInErrs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { egpNeighEntry 5 }

egpNeighOutMsgs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS
      mandatory
        ::= { egpNeighEntry 6 }

egpNeighOutErrs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { egpNeighEntry 7 }

egpNeighInErrMsgs OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { egpNeighEntry 8 }

egpNeighOutErrMsgs OBJECT-TYPE
        SYNTAX  Counter
```

```
        ACCESS  read-only
        STATUS  mandatory
        ::= { egpNeighEntry 9 }

egpNeighStateUps OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { egpNeighEntry 10 }

egpNeighStateDowns OBJECT-TYPE
        SYNTAX  Counter
        ACCESS  read-only
        STATUS  mandatory
        ::= { egpNeighEntry 11 }

egpNeighIntervalHello OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-only
        STATUS  mandatory
        ::= { egpNeighEntry 12 }

egpNeighIntervalPoll OBJECT-TYPE
        SYNTAX  INTEGER
        ACCESS  read-only
        STATUS  mandatory

      ::= { egpNeighEntry 13 }

egpNeighMode OBJECT-TYPE
        SYNTAX  INTEGER {
                    active(1),
                    passive(2)
                }
        ACCESS  read-only
        STATUS  mandatory
        ::= { egpNeighEntry 14 }

egpNeighEventTrigger OBJECT-TYPE
        SYNTAX  INTEGER {
                    start(1),
                    stop(2)
                }
        ACCESS  read-write
        STATUS  mandatory
        ::= { egpNeighEntry 15 }

-- additional EGP variables
```

```
egpAs OBJECT-TYPE
      SYNTAX  INTEGER
      ACCESS  read-only
      STATUS  mandatory
      ::= { egp 6 }


-- the Transmission group (empty at present)

-- the SNMP group

snmpInPkts OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::=  { snmp 1 }

snmpOutPkts OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::=  { snmp 2 }

snmpInBadVersions OBJECT-TYPE
      SYNTAX  Counter
      ACCESS
 read-only
      STATUS  mandatory
      ::=  { snmp 3 }

snmpInBadCommunityNames OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::=  { snmp 4 }

snmpInBadCommunityUses OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::=  { snmp 5 }

snmpInASNParseErrs OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::=  { snmp 6 }
```

```
snmpInBadTypes OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { snmp 7 }

snmpInTooBigs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { snmp 8 }

snmpInNoSuchNames OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { snmp 9 }

snmpInBadValues OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { snmp 10 }

snmpInReadOnlys OBJECT-TYPE
     SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { snmp 11 }

snmpInGenErrs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { snmp 12 }

snmpInTotalReqVars OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { snmp 13 }

snmpInTotalSetVars OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { snmp 14 }
```

```
snmpInGetRequests OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { snmp 15 }

snmpInGetNexts OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { snmp 16 }

snmpInSetRequests OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { snmp 17 }

snmpInGetResponses OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
     ::=  { snmp 18 }

snmpInTraps OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { snmp 19 }

snmpOutTooBigs OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { snmp 20 }

snmpOutNoSuchNames OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { snmp 21 }

snmpOutBadValues OBJECT-TYPE
    SYNTAX  Counter
    ACCESS  read-only
    STATUS  mandatory
    ::=  { snmp 22 }
```

```
snmpOutReadOnlys OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::=  { snmp 23 }

snmpOutGenErrs OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::=  { snmp 24 }

snmpOutGetRequests OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::=  { snmp 25 }

snmpOutGetNexts OBJECT-TYPE
      SYNTAX  Counter

     ACCESS  read-only
      STATUS  mandatory
      ::=  { snmp 26 }

snmpOutSetRequests OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::=  { snmp 27 }

snmpOutGetResponses OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::=  { snmp 28 }

snmpOutTraps OBJECT-TYPE
      SYNTAX  Counter
      ACCESS  read-only
      STATUS  mandatory
      ::=  { snmp 29 }

snmpEnableAuthTraps OBJECT-TYPE
      SYNTAX  INTEGER {
                enabled(1),
                disabled(2)
```

```
            }
        ACCESS  read-write
        STATUS  mandatory
        ::=  { snmp 30 }

END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/RFC1158-MIB
No license file was found, but licenses were detected in source scan.

```
DLSW-MIB DEFINITIONS ::= BEGIN

IMPORTS
        DisplayString, RowStatus,
        RowPointer, TruthValue,
        TEXTUAL-CONVENTION              FROM SNMPv2-TC
        Counter32, Gauge32, TimeTicks,
        OBJECT-TYPE, MODULE-IDENTITY,
        NOTIFICATION-TYPE, mib-2        FROM SNMPv2-SMI
        MODULE-COMPLIANCE, OBJECT-GROUP,
        NOTIFICATION-GROUP              FROM SNMPv2-CONF
        ifIndex                     FROM IF-MIB
        sdlcLSAddress                   FROM SNA-SDLC-MIB;

dlsw MODULE-IDENTITY
  LAST-UPDATED  "9606040900Z"
  ORGANIZATION  "AIW DLSw MIB RIGLET and IETF DLSw MIB Working Group"
  CONTACT-INFO
              "David D. Chen
               IBM Corporation
               800 Park, Highway 54
               Research Triangle Park, NC 27709-9990
               Tel:    1 919 254 6182
               E-mail: dchen@vnet.ibm.com"
 DESCRIPTION

    "This MIB module contains objects to manage Data Link
       Switches."
::= { mib-2 46 }

dlswMIB         OBJECT IDENTIFIER ::= { dlsw 1 }
dlswDomains     OBJECT IDENTIFIER ::= { dlsw 2 }

-- ****************************************************************
-- Textual convention definitions
-- ****************************************************************
```

```
NBName ::= TEXTUAL-CONVENTION
  STATUS       current
  DESCRIPTION
    "Represents a single qualified NetBIOS name, which can include
     `don't care' and `wildcard' characters to represent a number
     of real NetBIOS names.  If an individual character position in
     the qualified name contains a `?', the corresponding character
     position in a real NetBIOS name is a `don't care'.  If the
     qualified name ends in `*', the remainder of a real NetBIOS
     name is a `don't care'. `*' is only considered a wildcard if it
     appears at the end of a name."
  SYNTAX  OCTET STRING (SIZE
(0..16))

MacAddressNC ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "1x:"
  STATUS       current
  DESCRIPTION
    "Represents an 802 MAC address represented in
     non-canonical format.  That is, the most significant
     bit will be transmitted first.  If this information
     is not available, the value is a zero length string."
  SYNTAX       OCTET STRING (SIZE (0 | 6))

TAddress ::= TEXTUAL-CONVENTION
  STATUS  current
  DESCRIPTION
    "Denotes a transport service address.
     For dlswTCPDomain, a TAddress is 4 octets long,
     containing the IP-address in network-byte order."
  SYNTAX  OCTET STRING (SIZE (0..255))

EndStationLocation ::= TEXTUAL-CONVENTION
  STATUS  current
  DESCRIPTION
    "Representing the location of an end station related
     to the managed DLSw node."
  SYNTAX  INTEGER  {
            other         (1),
            internal      (2),  -- local virtual MAC address
            remote        (3),  -- via
 DLSw partner
            local         (4)   -- locally attached
          }

DlcType ::= TEXTUAL-CONVENTION
  STATUS  current
  DESCRIPTION
```

```
      "Representing the type of DLC of an end station, if
       applicable."
    SYNTAX  INTEGER  {
              other         (1),  -- not assigned yet
              na            (2),  -- not applicable
              llc           (3),  -- 802.2 Logical Link Control
              sdlc          (4),  -- SDLC
              qllc          (5)   -- QLLC
            }

LFSize  ::= TEXTUAL-CONVENTION
    STATUS  current
    DESCRIPTION
      "The largest size of the INFO field (including DLC header,
       not including any MAC-level or framing octets).
       64 valid values as defined by the IEEE 802.1D
       Addendum are acceptable."
    SYNTAX  INTEGER  {
              lfs516(516), lfs635(635), lfs754(754), lfs873(873),
              lfs993(993), lfs1112(1112), lfs1231(1231),
              lfs1350(1350), lfs1470(1470),
 lfs1542(1542),
              lfs1615(1615), lfs1688(1688), lfs1761(1761),
              lfs1833(1833), lfs1906(1906), lfs1979(1979),
              lfs2052(2052), lfs2345(2345), lfs2638(2638),
              lfs2932(2932), lfs3225(3225), lfs3518(3518),
              lfs3812(3812), lfs4105(4105), lfs4399(4399),
              lfs4865(4865), lfs5331(5331), lfs5798(5798),
              lfs6264(6264), lfs6730(6730), lfs7197(7197),
              lfs7663(7663), lfs8130(8130), lfs8539(8539),
              lfs8949(8949), lfs9358(9358), lfs9768(9768),
              lfs10178(10178), lfs10587(10587), lfs10997(10997),
              lfs11407(11407), lfs12199(12199), lfs12992(12992),
              lfs13785(13785), lfs14578(14578), lfs15370(15370),
              lfs16163(16163), lfs16956(16956), lfs17749(17749),
              lfs20730(20730), lfs23711(23711), lfs26693(26693),
              lfs29674(29674), lfs32655(32655), lfs38618(38618),
              lfs41600(41600), lfs44591(44591),
 lfs47583(47583),
              lfs50575(50575), lfs53567(53567), lfs56559(56559),
              lfs59551(59551), lfs65535(65535)
            }

null OBJECT IDENTIFIER ::= { 0 0 }


-- ************************************************************
-- DLSw Transport Domain definitions
```

```
-- ****************************************************************

-- DLSw over TCP
dlswTCPDomain  OBJECT IDENTIFIER ::= { dlswDomains 1 }
-- for an IP address of length 4:
--
-- octets   contents       encoding
--  1-4     IP-address      network-byte order
--
DlswTCPAddress ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "1d.1d.1d.1d"
  STATUS       current
  DESCRIPTION
        "Represents the IP address of a DLSw which uses
         TCP as a transport protocol."
  SYNTAX       OCTET STRING (SIZE (4))


-- ****************************************************************
-- DLSw MIB Definition
-- ****************************************************************

-- The
 DLSw MIB module contains an object part and a conformance part.
-- Object part is organized in the following groups:
-- (1) dlswNode      -  information about this DLSw
-- (2) dlswTConn     -  about adjacent DLSw partners
-- (3) dlswInterface -  about which interfaces DLSw is active on
-- (4) dlswDirectory -  about any directory of local/remote resources
-- (5) dlswCircuit   -  about established circuits.
-- (6) dlswSdlc      -  about SDLC data link switched devices

dlswNode        OBJECT IDENTIFIER ::= { dlswMIB 1 }
dlswTConn       OBJECT IDENTIFIER ::= { dlswMIB 2 }
dlswInterface   OBJECT IDENTIFIER ::= { dlswMIB 3 }
dlswDirectory   OBJECT IDENTIFIER ::= { dlswMIB 4 }
dlswCircuit     OBJECT IDENTIFIER ::= { dlswMIB 5 }
dlswSdlc        OBJECT IDENTIFIER ::= { dlswMIB 6 }  -- SDLC

-- ****************************************************************
-- THE NODE GROUP
-- ****************************************************************

-- ----------------------------------------------------------------
--
 DLSw Node Identity
-- ----------------------------------------------------------------
dlswNodeVersion  OBJECT-TYPE
```

```
  SYNTAX     OCTET STRING (SIZE (2))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "This value identifies the particular version of the DLSw
     standard supported by this DLSw.  The first octet is a
     hexadecimal value representing the DLSw standard Version
     number of this DLSw, and the second is a hexadecimal value
     representing the DLSw standard Release number. This
     information is reported in DLSw Capabilities Exchange."
  REFERENCE
    "DLSW: Switch-to-Switch Protocol RFC 1795"
  ::= { dlswNode 1 }

dlswNodeVendorID  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (3))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The value identifies the manufacturer's IEEE-assigned
     organizationally Unique Identifier (OUI) of this DLSw.
     This information
 is reported in DLSw Capabilities
     Exchange."
  REFERENCE
    "DLSW: Switch-to-Switch Protocol RFC 1795"
  ::= { dlswNode 2 }

dlswNodeVersionString  OBJECT-TYPE
  SYNTAX     DisplayString
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "This string gives product-specific information about
     this DLSw (e.g., product name, code release and fix level).
     This flows in Capabilities Exchange messages."
  REFERENCE
    "DLSW: Switch-to-Switch Protocol RFC 1795"
  ::= { dlswNode 3 }

-- ----------------------------------------------------------------
-- DLSw Code Capability
-- ----------------------------------------------------------------
dlswNodeStdPacingSupport  OBJECT-TYPE
  SYNTAX     INTEGER  {
    none             (1),  -- does not support DLSw
                           -- Standard pacing scheme
    adaptiveRcvWindow (2),  -- the receive window size
```

```
                    -- varies
    fixedRcvWindow
   (3)   -- the receive window size
                    -- remains constant
  }
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "Circuit pacing, as defined in the DLSw Standard, allows each
     of the two DLSw nodes on a circuit to control the amount
     of data the other is permitted to send to them.  This object
     reflects the level of support the DLSw node has for this
     protocol.  (1) means the node has no support for the standard
     circuit pacing flows;  it may use RFC 1434+ methods only, or
     a proprietary flow control scheme.  (2) means the node supports
     the standard scheme and can vary the window sizes it grants as
     a data receiver.  (3) means the node supports the standard
     scheme but never varies its receive window size."
  ::= { dlswNode 4 }

-- ------------------------------------------------------------
-- DLSw Node Operational Objects
-- ------------------------------------------------------------
dlswNodeStatus
 OBJECT-TYPE
  SYNTAX     INTEGER  {
     active       (1),
     inactive     (2)
  }
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
    "The status of the DLSw part of the system.  Changing the
     value from active to inactive causes DLSw to take
     the following actions - (1) it disconnects all circuits
     through all DLSw partners, (2) it disconnects all
     transport connections to all DLSw partners, (3) it
     disconnects all local DLC connections, and (4) it stops
     processing all DLC connection set-up traffic.
     Since these are destructive actions, the user should
     query the circuit and transport connection tables in
     advance to understand the effect this action will have.
     Changing the value from inactive to active causes DLSw
     to come up in its initial state, i.e., transport
     connections established and ready to bring up circuits."
   ::= { dlswNode 5 }

dlswNodeUpTime  OBJECT-TYPE
```

```
  SYNTAX     TimeTicks
  UNITS      "hundredths of a second"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The amount of time (in hundredths of a second) since
      the DLSw portion of the system was last re-initialized.
      That is, if dlswState is in the active state,
      the time the dlswState entered the active state.
      It will remain zero if dlswState is in the
      inactive state."
  ::= { dlswNode 6 }

dlswNodeVirtualSegmentLFSize  OBJECT-TYPE
  SYNTAX     LFSize
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
     "The largest frame size (including DLC header and info field
      but not any MAC-level or framing octets) this DLSw can forward
      on any path through itself.  This object can represent any box-
      level frame size forwarding restriction (e.g., from the use
      of fixed-size buffers).  Some DLSw implementations will have
       no such restriction.

      This value will affect the LF size of circuits during circuit
      creation.  The LF size of an existing circuit can be found in
      the RIF (Routing Information Field)."
  DEFVAL  { lfs65535 }
  ::= { dlswNode 7 }

-- ..........................................................................
-- NETBIOS Resources
-- ..........................................................................

dlswNodeResourceNBExclusivity  OBJECT-TYPE
  SYNTAX     TruthValue
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
     "The value of true indicates that the NetBIOS Names
      configured in dlswDirNBTable are the only ones accessible
      via this DLSw.

      If a node supports sending run-time capabilities exchange
      messages, changes to this object should cause that action.
      It is up to the implementation exactly when to start the
      run-time capabilities exchange."
```

```
  ::= { dlswNode 8 }

-- ....................................................................
--
 MAC Address List
-- ....................................................................

dlswNodeResourceMacExclusivity  OBJECT-TYPE
  SYNTAX     TruthValue
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
    "The value of true indicates that the MAC addresses
     configured in the dlswDirMacTable are the only ones
     accessible via this DLSw.

     If a node supports sending run-time capabilities exchange
     messages, changes to this object should cause that action.
     It is up to the implementation exactly when to start the
     run-time capabilities exchange."
  ::= { dlswNode 9 }


-- ********************************************************************
-- TRANSPORT CONNECTION (aka: PARTNER DLSW)
-- ********************************************************************

-- --------------------------------------------------------------

-- Transport Connection Statistics Objects
-- --------------------------------------------------------------
dlswTConnStat
   OBJECT IDENTIFIER ::= { dlswTConn 1 }

dlswTConnStatActiveConnections  OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of transport connections that are not in
     `disconnected' state."
  ::= { dlswTConnStat 1 }

dlswTConnStatCloseIdles  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
```

```
      "The number of times transport connections in this node
       exited the connected state with zero active circuits on
       the transport connection."
    ::= { dlswTConnStat 2 }

dlswTConnStatCloseBusys  OBJECT-TYPE
    SYNTAX     Counter32
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
      "The number of times transport connections in this node
       exited the connected state with some non-zero number
       of active circuits on the transport connection.  Normally
        this means the transport connection failed unexpectedly."
    ::= { dlswTConnStat 3 }

-- ----------------------------------------------------------------
-- Transport Connection Configuration Table
-- ----------------------------------------------------------------
dlswTConnConfigTable  OBJECT-TYPE
    SYNTAX     SEQUENCE OF DlswTConnConfigEntry
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
      "This table defines the transport connections
       that will be initiated or accepted by this
       DLSw.  Structure of masks allows wildcard
       definition for a collection of transport
       connections by a conceptual row.  For a
       specific transport connection, there may
       be multiple of conceptual rows match the
       transport address.  The `best' match will
       the one to determine the characteristics
       of the transport connection."
    ::= { dlswTConn 2 }

dlswTConnConfigEntry  OBJECT-TYPE
    SYNTAX     DlswTConnConfigEntry
     MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
      "Each conceptual row defines a collection of
       transport connections."
    INDEX   { dlswTConnConfigIndex }
    ::= { dlswTConnConfigTable 1 }

DlswTConnConfigEntry ::= SEQUENCE {
    dlswTConnConfigIndex              INTEGER,
```

```
  dlswTConnConfigTDomain          OBJECT IDENTIFIER,
  dlswTConnConfigLocalTAddr       TAddress,
  dlswTConnConfigRemoteTAddr      TAddress,
  dlswTConnConfigLastModifyTime   TimeTicks,
  dlswTConnConfigEntryType        INTEGER,
  dlswTConnConfigGroupDefinition  RowPointer,
  dlswTConnConfigSetupType        INTEGER,
  dlswTConnConfigSapList          OCTET STRING,
  dlswTConnConfigAdvertiseMacNB   TruthValue,
  dlswTConnConfigInitCirRecvWndw  INTEGER,
  dlswTConnConfigOpens            Counter32,
  dlswTConnConfigRowStatus        RowStatus
  }

dlswTConnConfigIndex  OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS
 not-accessible
  STATUS     current
  DESCRIPTION
    "The index to the conceptual row of the table.
     Negative numbers are not allowed.  There
     are objects defined that point to conceptual
     rows of this table with this index value.
     Zero is used to denote that no corresponding
     row exists.

     Index values are assigned by the agent, and
     should not be reused but should continue to
     increase in value."
  ::= { dlswTConnConfigEntry 1 }

dlswTConnConfigTDomain  OBJECT-TYPE
  SYNTAX     OBJECT IDENTIFIER
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The object identifier which indicates the transport
     domain of this conceptual row."
  ::= { dlswTConnConfigEntry 2 }

dlswTConnConfigLocalTAddr  OBJECT-TYPE
  SYNTAX     TAddress
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The local transport address for this conceptual row
     of the transport connection
```

definition."
::= { dlswTConnConfigEntry 3 }

dlswTConnConfigRemoteTAddr OBJECT-TYPE
SYNTAX TAddress
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The remote transport address. Together with
dlswTConnConfigEntryType and dlswTConnConfigGroupDefinition,
the object instance of this conceptual row identifies a
collection of the transport connections that will be
either initiated by this DLSw or initiated by a partner
DLSw and accepted by this DLSw."
::= { dlswTConnConfigEntry 4 }

dlswTConnConfigLastModifyTime OBJECT-TYPE
SYNTAX TimeTicks
UNITS "hundredths of a second"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The time (in hundredths of a second) since the value of
any object in this conceptual row except for
dlswTConnConfigOpens was last changed. This value
may be compared to dlswTConnOperConnectTime to
determine whether
values in this row are completely
valid for a transport connection created using
this row definition."
::= { dlswTConnConfigEntry 5 }

dlswTConnConfigEntryType OBJECT-TYPE
SYNTAX INTEGER {
individual (1),
global (2),
group (3)
}
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The object instance signifies the type of entry in the
associated conceptual row. The value of `individual'
means that the entry applies to a specific partner DLSw
node as identified by dlswTConnConfigRemoteTAddr and
dlswTConnConfigTDomain. The value of `global'
means that the entry applies to all partner DLSw nodes
of the TDomain. The value of 'group' means that the entry

```
      applies to a specific set of DLSw nodes in the TDomain.
      Any group definitions are enterprise-specific and are pointed
      to by dlswTConnConfigGroupDefinition.  In the
 cases of
      `global' and `group', the value in dlswTConnConfigRemoteTAddr
      may not have any significance."
  ::= { dlswTConnConfigEntry 6 }

dlswTConnConfigGroupDefinition OBJECT-TYPE
  SYNTAX     RowPointer
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "For conceptual rows of `individual' and `global' as
     specified in dlswTConnConfigEntryType, the instance
     of this object is  `0.0'.  For conceptual rows of
     `group', the instance points to the specific
     group definition."
  ::= { dlswTConnConfigEntry 7 }

dlswTConnConfigSetupType  OBJECT-TYPE

  SYNTAX     INTEGER  {
     other             (1),
     activePersistent   (2),
     activeOnDemand     (3),
     passive           (4),
     excluded           (5)
  }
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "This value of the instance of a conceptual row
     identifies the behavior of the collection of
     transport
 connections that this conceptual row
     defines.  The value of activePersistent, activeOnDemand
     and passive means this DLSw will accept any transport
     connections, initiated by partner DLSw nodes, which
     are defined by this conceptual row.  The value of
     activePersistent means this DLSw will also initiate
     the transport connections of this conceptual row and
     retry periodically if necessary.  The value of
     activeOnDemand means this DLSw will initiate a
     transport connection of this conceptual row, if
     there is a directory cache hits.  The value of
     other is implementation specific.  The value of exclude
     means that the specified node is not allowed to be
```

```
      a partner to this DLSw node.  To take a certain
      conceptual row definition out of service, a value of
      notInService for dlswTConnConfigRowStatus should be
      used."
  DEFVAL  { passive }
  ::= { dlswTConnConfigEntry 8
 }

dlswTConnConfigSapList  OBJECT-TYPE
  SYNTAX     OCTET STRING  (SIZE(16))
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "The SAP list indicates which SAPs are advertised to
      the transport connection defined by this conceptual
      row.  Only SAPs with even numbers are represented,
      in the form of the most significant bit of the first
      octet representing the SAP 0, the next most significant
      bit representing the SAP 2, to the least significant
      bit of the last octet representing the SAP 254.  Data
      link switching is allowed for those SAPs which have
      one in its corresponding bit, not allowed otherwise.
      The whole SAP list has to be changed together.  Changing
      the SAP list affects only new circuit establishments
      and has no effect on established circuits.

      This list can be used to restrict specific partners
      from knowing about all the SAPs used by DLSw on all its

    interfaces (these are represented in dlswIfSapList for
      each interface).  For instance, one may want to run NetBIOS
      with some partners but not others.

      If a node supports sending run-time capabilities exchange
      messages, changes to this object should cause that action.
      When to start the run-time capabilities exchange is
      implementation-specific.
      The DEFVAL below indicates support for SAPs 0, 4, 8, and C."
  DEFVAL  { 'AA000000000000000000000000000000'H }
  ::= { dlswTConnConfigEntry 9 }

dlswTConnConfigAdvertiseMacNB  OBJECT-TYPE
  SYNTAX     TruthValue
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "The value of true indicates that any defined local MAC
       addresses and NetBIOS names will be advertised to a
```

partner node via initial and (if supported) run-time
capabilities exchange messages. The DLSw node should send
the appropriate exclusivity control vector to accompany
each list it sends, or to represent that the node is
explicitly configured to have a null list.

The value of false indicates that the DLSw node should not
send a MAC address list or NetBIOS name list, and should
also not send their corresponding exclusivity control
vectors."
DEFVAL { true }
::= { dlswTConnConfigEntry 10 }

dlswTConnConfigInitCirRecvWndw OBJECT-TYPE
SYNTAX INTEGER (0..65535)
UNITS "SSP messages"
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The initial circuit receive pacing window size, in the unit
of SSP messages, to be used for future transport connections
activated using this table row. The managed node sends this
value as its initial receive pacing window in its initial
capabilities exchange message. Changing this value does not
affect the initial circuit receive pacing window size of
currently active
transport connections. If the standard window
pacing scheme is not supported, the value is zero.

A larger receive window value may be appropriate for partners
that are reachable only via physical paths that have longer
network delays."
DEFVAL { 1 }
::= { dlswTConnConfigEntry 11 }

dlswTConnConfigOpens OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Number of times transport connections entered
connected state according to the definition of
this conceptual row."
::= { dlswTConnConfigEntry 12 }

dlswTConnConfigRowStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create

```
  STATUS     current
  DESCRIPTION
     "This object is used by the manager to create
      or delete the row entry in the dlswTConnConfigTable
      following the RowStatus textual convention.  The value
      of notInService will be used to take a conceptual
      row
 definition out of use."
  ::= { dlswTConnConfigEntry 13 }

-- ---------------------------------------------------------------
-- Transport Connection Operation Table
-- ---------------------------------------------------------------
-- (1) At most one transport connection can be connected between
--     this DLSw and one of its DLSw partners at a given time.
-- (2) Multiple transport types are supported.
-- (3) Since the entries may be reused, dlswTConnOperEntryTime
--     needs to be consulted for the possibility of counter reset.
-- ---------------------------------------------------------------

dlswTConnOperTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswTConnOperEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "A list of transport connections.   It is optional but
      desirable for the agent to keep an entry for some
      period of time after the transport connection is
      disconnected.  This allows the manager to capture
       additional useful information about the connection, in
      particular, statistical information and the cause of the
      disconnection."
  ::= { dlswTConn 3 }

dlswTConnOperEntry  OBJECT-TYPE
  SYNTAX     DlswTConnOperEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     ""
  INDEX   { dlswTConnOperTDomain, dlswTConnOperRemoteTAddr }
  ::= { dlswTConnOperTable 1 }

DlswTConnOperEntry ::= SEQUENCE {
  dlswTConnOperTDomain               OBJECT IDENTIFIER,
  dlswTConnOperLocalTAddr             TAddress,
  dlswTConnOperRemoteTAddr            TAddress,
```

```
  dlswTConnOperEntryTime              TimeTicks,
  dlswTConnOperConnectTime            TimeTicks,
  dlswTConnOperState                  INTEGER,
  dlswTConnOperConfigIndex            INTEGER,
  dlswTConnOperFlowCntlMode           INTEGER,

  dlswTConnOperPartnerVersion         OCTET STRING,
  dlswTConnOperPartnerVendorID        OCTET STRING,
  dlswTConnOperPartnerVersionStr
      DisplayString,
  dlswTConnOperPartnerInitPacingWndw  INTEGER,

  dlswTConnOperPartnerSapList         OCTET STRING,
  dlswTConnOperPartnerNBExcl          TruthValue,
  dlswTConnOperPartnerMacExcl         TruthValue,
  dlswTConnOperPartnerNBInfo          INTEGER,
  dlswTConnOperPartnerMacInfo         INTEGER,

  dlswTConnOperDiscTime               TimeTicks,
  dlswTConnOperDiscReason             INTEGER,
  dlswTConnOperDiscActiveCir          INTEGER,

  dlswTConnOperInDataPkts             Counter32,
  dlswTConnOperOutDataPkts            Counter32,
  dlswTConnOperInDataOctets           Counter32,
  dlswTConnOperOutDataOctets          Counter32,

  dlswTConnOperInCntlPkts             Counter32,
  dlswTConnOperOutCntlPkts            Counter32,

  dlswTConnOperCURexSents             Counter32,
  dlswTConnOperICRexRcvds             Counter32,
  dlswTConnOperCURexRcvds             Counter32,
   dlswTConnOperICRexSents            Counter32,

  dlswTConnOperNQexSents              Counter32,
  dlswTConnOperNRexRcvds              Counter32,
  dlswTConnOperNQexRcvds              Counter32,
  dlswTConnOperNRexSents              Counter32,
  dlswTConnOperCirCreates             Counter32,
  dlswTConnOperCircuits               Gauge32
  }

dlswTConnOperTDomain  OBJECT-TYPE
  SYNTAX     OBJECT IDENTIFIER
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
```

```
      "The object identifier indicates the transport domain
       of this transport connection."
   ::= { dlswTConnOperEntry 1 }

dlswTConnOperLocalTAddr  OBJECT-TYPE
   SYNTAX     TAddress
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The local transport address for this transport connection.
       This value could be different from dlswTConnConfigLocalAddr,
       if the value of the latter were changed after this transport
       connection was
 established."
   ::= { dlswTConnOperEntry 2 }

dlswTConnOperRemoteTAddr  OBJECT-TYPE
   SYNTAX     TAddress
   MAX-ACCESS not-accessible
   STATUS     current
   DESCRIPTION
      "The remote transport address of this transport connection."
   ::= { dlswTConnOperEntry 3 }

dlswTConnOperEntryTime  OBJECT-TYPE
   SYNTAX     TimeTicks
   UNITS      "hundredths of a second"
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The amount of time (in hundredths of a second) since this
       transport connection conceptual row was created."
   ::= { dlswTConnOperEntry 4 }

-- ..........................................................
-- DLSw Transport Connection Operational Objects
-- ..........................................................

dlswTConnOperConnectTime  OBJECT-TYPE
   SYNTAX     TimeTicks
   UNITS      "hundredths of a second"
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The amount of time (in hundredths
 of a second) since this
       transport connection last entered the 'connected' state.
       A value of zero means this transport connection has never
```

```
      been established."
  ::= { dlswTConnOperEntry 5 }

dlswTConnOperState  OBJECT-TYPE
  SYNTAX     INTEGER  {
      connecting        (1),
      initCapExchange    (2),
      connected         (3),
      quiescing         (4),
      disconnecting      (5),
      disconnected       (6)
  }
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
     "The state of this transport connection.  The transport
      connection enters `connecting' state when DLSw makes
      a connection request to the transport layer.  Once initial
      Capabilities Exchange is sent, the transport connection
      enters enters `initCapExchange' state.  When partner
      capabilities have been determined and the transport
      connection is ready for sending CanUReach (CUR) messages,
      it moves
 to the `connected' state.  When DLSw is in the
      process of bringing down the connection, it is in the
      `disconnecting' state.  When the transport layer
      indicates one of its connections is disconnected, the
      transport connection moves to the `disconnected' state.

      Whereas all of the values will be returned in response
      to a management protocol retrieval operation, only two
      values may be specified in a management protocol set
      operation: `quiescing' and `disconnecting'.  Changing
      the value to `quiescing' prevents new circuits from being
      established, and will cause a transport disconnect when
      the last circuit on the connection goes away.  Changing
      the value to `disconnecting' will force off all circuits
      immediately and bring the connection to `disconnected'
      state."
  ::= { dlswTConnOperEntry 6 }

dlswTConnOperConfigIndex  OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS
 read-only
  STATUS     current
  DESCRIPTION
     "The value of dlswTConnConfigIndex of the dlswTConnConfigEntry
```

```
      that governs the configuration information used by this
      dlswTConnOperEntry.  The manager can therefore normally
      examine both configured and operational information
      for this transport connection.

      This value is zero if the corresponding dlswTConnConfigEntry
      was deleted after the creation of this dlswTConnOperEntry.
      If some fields in the former were changed but the conceptual
      row was not deleted, some configuration information may not
      be valid for this operational transport connection.  The
      manager can compare dlswTConnOperConnectTime and
      dlswTConnConfigLastModifyTime to determine if this condition
      exists."
  ::= { dlswTConnOperEntry 7 }

-- ...........................................................
-- Transport Connection Characteristics
-- ...........................................................

dlswTConnOperFlowCntlMode
  OBJECT-TYPE
  SYNTAX     INTEGER  {
    undetermined   (1),
    pacing         (2),   -- DLSw standard flow control
    other          (3)    -- non-DLSw standard flow control
  }
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The flow control mechanism in use on this transport connection.
     This value is undetermined (1) before the mode of flow control
     can be established on a new transport connection (i.e., after
     CapEx is sent but before Capex or other SSP control messages
     have been received).  Pacing (2) indicates that the standard
     RFC 1795 pacing mechanism is in use.  Other (3) may be either
     the RFC 1434+ xBusy mechanism operating to a back-level DLSw,
     or a vendor-specific flow control method.  Whether it is xBusy
     or not can be inferred from dlswTConnOperPartnerVersion."
  ::= { dlswTConnOperEntry 8 }

--
 ...........................................................

dlswTConnOperPartnerVersion  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (0 | 2))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
```

```
      "This value identifies which version (first octet) and release
      (second octet) of the DLSw standard is supported by this
      partner DLSw. This information is obtained from a DLSw
      capabilities exchange message received from the partner DLSw.
      A string of zero length is returned before a Capabilities
      Exchange message is received, or if one is never received.
      A conceptual row with a dlswTConnOperState of `connected' but
      a zero length partner version indicates that the partner is
      a non-standard DLSw partner.

      If an implementation chooses to keep dlswTConnOperEntrys in
      the `disconnected' state, this value should remain unchanged."
    REFERENCE
      "DLSW: Switch-to-Switch Protocol RFC 1795"

    ::= { dlswTConnOperEntry 9 }

dlswTConnOperPartnerVendorID  OBJECT-TYPE
    SYNTAX     OCTET STRING (SIZE (0 | 3))
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
      "This value identifies the IEEE-assigned organizationally
      Unique Identifier (OUI) of the maker of this partner
      DLSw.  This information is obtained from a DLSw
      capabilities exchange message received from the partner DLSw.
      A string of zero length is returned before a Capabilities
      Exchange message is received, or if one is never received.

      If an implementation chooses to keep dlswTConnOperEntrys in
      the `disconnected' state, this value should remain unchanged."
    ::= { dlswTConnOperEntry 10 }

dlswTConnOperPartnerVersionStr  OBJECT-TYPE
    SYNTAX     DisplayString (SIZE (0..253))
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
      "This value identifies the particular product version (e.g.,
      product name, code level, fix
   level) of this partner DLSw.
      The format of the actual version string is vendor-specific.
      This information is obtained from a DLSw capabilities exchange
      message received from the partner DLSw.
      A string of zero length is returned before a Capabilities
      Exchange message is received, if one is never received, or
      if one is received but it does not contain a version string.
      If an implementation chooses to keep dlswTConnOperEntrys in
```

```
      the `disconnected' state, this value should remain unchanged."
    REFERENCE
      "DLSW: Switch-to-Switch Protocol RFC 1795"
    ::= { dlswTConnOperEntry 11 }

dlswTConnOperPartnerInitPacingWndw  OBJECT-TYPE
    SYNTAX     INTEGER (0..65535)
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
      "The value of the partner initial receive pacing window.  This
      is our initial send pacing window for all new circuits on this
      transport connection, as modified and granted by
 the first flow
      control indication the partner sends on each circuit.
      This information is obtained from a DLSw capabilities exchange
      message received from the partner DLSw.
      A value of zero is returned before a Capabilities
      Exchange message is received, or if one is never received.

      If an implementation chooses to keep dlswTConnOperEntrys in
      the `disconnected' state, this value should remain unchanged."
    REFERENCE
      "DLSW: Switch-to-Switch Protocol RFC 1795"
    ::= { dlswTConnOperEntry 12 }

-- ..........................................................................

dlswTConnOperPartnerSapList  OBJECT-TYPE
    SYNTAX     OCTET STRING (SIZE (0 | 16))
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
      "The Supported SAP List received in the capabilities
      exchange message from the partner DLSw.  This list has
      the same format described for dlswTConnConfigSapList.
      A string of zero length is
 returned before a Capabilities
      Exchange message is received, or if one is never received.

      If an implementation chooses to keep dlswTConnOperEntrys in
      the `disconnected' state, this value should remain unchanged."
    ::= { dlswTConnOperEntry 13 }

dlswTConnOperPartnerNBExcl  OBJECT-TYPE
    SYNTAX     TruthValue
    MAX-ACCESS read-only
    STATUS     current
```

```
  DESCRIPTION
    "The value of true signifies that the NetBIOS names received
     from this partner in the NetBIOS name list in its capabilities
     exchange message are the only NetBIOS names reachable by
     that partner.  `False' indicates that other NetBIOS names may
     be reachable.  `False' should be returned before a Capabilities
     Exchange message is received, if one is never received, or if
     one is received without a NB Name Exclusivity CV.

     If an implementation chooses to keep dlswTConnOperEntrys in
     the `disconnected' state, this value should remain
 unchanged."
  ::= { dlswTConnOperEntry 14 }

dlswTConnOperPartnerMacExcl  OBJECT-TYPE
  SYNTAX     TruthValue
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The value of true signifies that the MAC addresses received
     from this partner in the MAC address list in its capabilities
     exchange message are the only MAC addresses reachable by
     that partner.  `False' indicates that other MAC addresses may
     be reachable.  `False' should be returned before a Capabilities
     Exchange message is received, if one is never received, or if
     one is received without a MAC Address Exclusivity CV.

     If an implementation chooses to keep dlswTConnOperEntrys in
     the `disconnected' state, this value should remain unchanged."
  ::= { dlswTConnOperEntry 15 }

dlswTConnOperPartnerNBInfo  OBJECT-TYPE
  SYNTAX     INTEGER  {
    none          (1),  -- none is kept
    partial       (2),  -- partial list is kept

    complete      (3),  -- complete list is kept
    notApplicable  (4)
  }
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "It is up to this DSLw whether to keep either none, some,
     or all of the NetBIOS name list that was received in
     the capabilities exchange message sent by this partner DLSw.
     This object identifies how much information was kept by
     this DLSw.  These names are stored as userConfigured
     remote entries in dlswDirNBTable.
```

```
      A value of (4), notApplicable, should be returned before
      a Capabilities Exchange message is received, or if one is
      never received.
      If an implementation chooses to keep dlswTConnOperEntrys in
      the `disconnected' state, this value should remain unchanged."
   ::= { dlswTConnOperEntry 16 }

dlswTConnOperPartnerMacInfo  OBJECT-TYPE
   SYNTAX     INTEGER  {
     none          (1),  -- none is kept
     partial       (2),  -- partial list is kept
      complete       (3),  -- complete list is kept
     notApplicable  (4)
   }
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
     "It is up to this DLSw whether to keep either none, some,
      or all of the MAC address list that was received in the
      capabilities exchange message sent by this partner DLSw.
      This object identifies how much information was kept by
      this DLSw.  These names are stored as userConfigured
      remote entries in dlswDirMACTable.
      A value of (4), notApplicable, should be returned before
      a Capabilities Exchange message is received, or if one is
      never received.

      If an implementation chooses to keep dlswTConnOperEntrys in
      the `disconnected' state, this value should remain unchanged."
   ::= { dlswTConnOperEntry 17 }

-- ..........................................................................
-- Information about the last disconnect of this transport connection.
--   These objects
 make sense only for implementations that keep
--   transport connection information around after disconnection.
-- ..........................................................................
dlswTConnOperDiscTime  OBJECT-TYPE
   SYNTAX     TimeTicks
   UNITS      "hundredths of a second"
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
     "The amount of time (in hundredths of a second) since the
      dlswTConnOperState last entered `disconnected' state."
   ::= { dlswTConnOperEntry 18 }

dlswTConnOperDiscReason  OBJECT-TYPE
```

```
  SYNTAX     INTEGER  {
      other             (1),
      capExFailed       (2),
      transportLayerDisc (3),
      operatorCommand    (4),
      lastCircuitDiscd   (5),
      protocolError      (6)
  }
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "This object signifies the reason that either prevented the
      transport connection from entering the connected state, or
      caused the transport
 connection to enter the disconnected
      state."
  ::= { dlswTConnOperEntry 19 }

dlswTConnOperDiscActiveCir  OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of circuits active (not in DISCONNECTED state)
      at the time the transport connection was last disconnected.
      This value is zero if the transport connection has never
      been connected."
  ::= { dlswTConnOperEntry 20 }

-- ..........................................................
-- Transport Connection Statistics
-- (1) Traffic counts
-- ..........................................................
dlswTConnOperInDataPkts  OBJECT-TYPE
  SYNTAX     Counter32
  UNITS      "SSP messages"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of Switch-to-Switch Protocol (SSP) messages of
      type DGRMFRAME, DATAFRAME, or INFOFRAME received on this
      transport connection."
   ::= { dlswTConnOperEntry 21 }

dlswTConnOperOutDataPkts  OBJECT-TYPE
  SYNTAX     Counter32
  UNITS      "SSP messages"
  MAX-ACCESS read-only
```

```
  STATUS     current
  DESCRIPTION
    "The number of Switch-to-Switch Protocol (SSP) messages of
     type DGRMFRAME, DATAFRAME, or INFOFRAME transmitted on this
     transport connection."
  ::= { dlswTConnOperEntry 22 }

dlswTConnOperInDataOctets  OBJECT-TYPE
  SYNTAX     Counter32
  UNITS      "octets"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number octets in Switch-to-Switch Protocol (SSP) messages
     of type DGRMFRAME, DATAFRAME, or INFOFRAME received on this
     transport connection.  Each message is counted starting with
     the first octet following the SSP message header."
  ::= { dlswTConnOperEntry 23 }

dlswTConnOperOutDataOctets  OBJECT-TYPE
  SYNTAX     Counter32
  UNITS      "octets"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number octets in Switch-to-Switch Protocol (SSP) messages
     of type DGRMFRAME, DATAFRAME, or INFOFRAME transmitted on this
     transport connection.  Each message is counted starting with
     the first octet following the SSP message header."
  ::= { dlswTConnOperEntry 24 }

dlswTConnOperInCntlPkts  OBJECT-TYPE
  SYNTAX     Counter32
  UNITS      "SSP messages"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of Switch-to-Switch Protocol (SSP) messages
     received on this transport connection which were not of
     type DGRMFRAME, DATAFRAME, or INFOFRAME."
  ::= { dlswTConnOperEntry 25 }

dlswTConnOperOutCntlPkts  OBJECT-TYPE
  SYNTAX     Counter32
  UNITS      "SSP messages"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
```

```
      "The number of Switch-to-Switch Protocol (SSP) messages of
       transmitted on this transport connection which were not of
       type DGRMFRAME, DATAFRAME,
 or INFOFRAME."
  ::= { dlswTConnOperEntry 26 }

-- ..........................................................
-- (2) Directory activities (Explorer messages)
-- ..........................................................

dlswTConnOperCURexSents  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of CanUReach_ex messages sent on this transport
      connection."
  ::= { dlswTConnOperEntry 27 }

dlswTConnOperICRexRcvds  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of ICanReach_ex messages received on this transport
      connection."
  ::= { dlswTConnOperEntry 28 }

dlswTConnOperCURexRcvds  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of CanUReach_ex messages received on this transport
      connection."
  ::= { dlswTConnOperEntry 29 }

dlswTConnOperICRexSents
 OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of ICanReach_ex messages sent on this transport
      connection."
  ::= { dlswTConnOperEntry 30 }

-- ..........................................................
```

```
dlswTConnOperNQexSents  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of NetBIOS_NQ_ex (NetBIOS Name Query-explorer)
     messages sent on this transport connection."
  ::= { dlswTConnOperEntry 31 }

dlswTConnOperNRexRcvds  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of NETBIOS_NR_ex (NetBIOS Name Recognized-explorer)
     messages received on this transport connection."
  ::= { dlswTConnOperEntry 32 }

dlswTConnOperNQexRcvds  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of NETBIOS_NQ_ex messages received on this
     transport connection."
  ::= { dlswTConnOperEntry 33 }

dlswTConnOperNRexSents  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of NETBIOS_NR_ex messages sent on this transport
     connection."
  ::= { dlswTConnOperEntry 34 }

-- .....................................................................
-- (3) Circuit activities on each transport connection
-- .....................................................................
dlswTConnOperCirCreates  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of times that circuits entered `circuit_established'
     state (not counting transitions from `circuit_restart')."
  ::= { dlswTConnOperEntry 35 }
```

```
dlswTConnOperCircuits  OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of currently active circuits on this transport
     connection, where `active' means not in `disconnected' state."
  ::= { dlswTConnOperEntry 36 }


-- ---------------------------------------------------------------
-- Transport Connection Specific
-- ---------------------------------------------------------------
dlswTConnSpecific OBJECT IDENTIFIER ::= { dlswTConn 4 }
dlswTConnTcp      OBJECT IDENTIFIER ::= { dlswTConnSpecific 1 }

-- .....................................................................
-- TCP Transport Connection Specific -  Configuration
-- .....................................................................
dlswTConnTcpConfigTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswTConnTcpConfigEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "This table defines the TCP transport connections that
     will be either initiated by or accepted by this DSLw.
     It augments the entries in dlswTConnConfigTable
 whose domain
     is dlswTCPDomain."
  ::= { dlswTConnTcp 1 }

dlswTConnTcpConfigEntry  OBJECT-TYPE
  SYNTAX     DlswTConnTcpConfigEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "Each conceptual row defines parameters that are
     specific to dlswTCPDomain transport connections."
  INDEX   { dlswTConnConfigIndex }
  ::= { dlswTConnTcpConfigTable 1 }

DlswTConnTcpConfigEntry ::= SEQUENCE {
  dlswTConnTcpConfigKeepAliveInt       INTEGER,
  dlswTConnTcpConfigTcpConnections     INTEGER,
  dlswTConnTcpConfigMaxSegmentSize     INTEGER
  }
```

```
dlswTConnTcpConfigKeepAliveInt  OBJECT-TYPE
  SYNTAX     INTEGER (0..1800)
  UNITS      "seconds"
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The time in seconds between TCP keepAlive messages when
     no traffic is flowing.  Zero signifies no keepAlive protocol.
     Changes take effect only for new TCP connections."
  DEFVAL  { 0 }
  ::= { dlswTConnTcpConfigEntry
 1 }

dlswTConnTcpConfigTcpConnections  OBJECT-TYPE
  SYNTAX     INTEGER (1..16)
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "This is our preferred number of TCP connections within a
     TCP transport connection.  The actual number used is negotiated
     at capabilities exchange time. Changes take effect only
     for new transport connections."
  DEFVAL  { 2 }
  ::= { dlswTConnTcpConfigEntry 2 }

dlswTConnTcpConfigMaxSegmentSize  OBJECT-TYPE
  SYNTAX     INTEGER (0..65535)
  UNITS      "packets"
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "This is the number of bytes that this node is
     willing to receive over the read TCP connection(s).
     Changes take effect for new transport connections."
  DEFVAL  { 4096 }
  ::= { dlswTConnTcpConfigEntry 3 }



-- ..........................................................................
-- TCP Transport Connection Specific -  Operation
-- ..........................................................................
dlswTConnTcpOperTable
 OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswTConnTcpOperEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "A list of TCP transport connections.   It is optional
```

```
      but desirable for the agent to keep an entry for some
      period of time after the transport connection is
      disconnected.  This allows the manager to capture
      additional useful information about the connection, in
      particular, statistical information and the cause of the
      disconnection."
  ::= { dlswTConnTcp 2 }

dlswTConnTcpOperEntry  OBJECT-TYPE
  SYNTAX     DlswTConnTcpOperEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    ""
  INDEX   { dlswTConnOperTDomain, dlswTConnOperRemoteTAddr }
  ::= { dlswTConnTcpOperTable 1 }

DlswTConnTcpOperEntry ::= SEQUENCE {
  dlswTConnTcpOperKeepAliveInt            INTEGER,
  dlswTConnTcpOperPrefTcpConnections
     INTEGER,
  dlswTConnTcpOperTcpConnections          INTEGER
  }

dlswTConnTcpOperKeepAliveInt  OBJECT-TYPE
  SYNTAX     INTEGER (0..1800)
  UNITS      "seconds"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The time in seconds between TCP keepAlive messages when
     no traffic is flowing.  Zero signifies no keepAlive protocol is
     operating."
  ::= { dlswTConnTcpOperEntry 1 }

dlswTConnTcpOperPrefTcpConnections  OBJECT-TYPE
  SYNTAX     INTEGER (1..16)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "This is the number of TCP connections preferred by this DLSw
     partner, as received in its capabilities exchange message."
  ::= { dlswTConnTcpOperEntry 2 }


dlswTConnTcpOperTcpConnections  OBJECT-TYPE
  SYNTAX     INTEGER (1..16)
  MAX-ACCESS read-only
```

```
  STATUS     current
  DESCRIPTION
    "This is the actual current number of TCP connections within
     this transport connection."
   ::= { dlswTConnTcpOperEntry 3 }

-- ****************************************************************
-- DLSW INTERFACE GROUP
-- ****************************************************************

dlswIfTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswIfEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The list of interfaces on which DLSw is active."
  ::= { dlswInterface 1 }

dlswIfEntry  OBJECT-TYPE
  SYNTAX     DlswIfEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    ""
  INDEX   { ifIndex }
  ::= { dlswIfTable 1 }

DlswIfEntry ::= SEQUENCE {
  dlswIfRowStatus      RowStatus,
  dlswIfVirtualSegment INTEGER,
  dlswIfSapList        OCTET STRING
  }

dlswIfRowStatus  OBJECT-TYPE
  SYNTAX     RowStatus
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "This object is used by the manager to create
     or delete the row entry in the dlswIfTable
     following the
 RowStatus textual convention."
  ::= { dlswIfEntry 1 }

dlswIfVirtualSegment  OBJECT-TYPE
  SYNTAX     INTEGER (0..4095 | 65535)
  MAX-ACCESS read-create
  STATUS     current
```

```
  DESCRIPTION
     "The segment number that uniquely identifies the virtual
      segment to which this DLSw interface is connected.
      Current source routing protocols limit this value to
      the range 0 - 4095. (The value 0 is used by some
      management applications for special test cases.)
      A value of 65535 signifies that no virtual segment
      is assigned to this interface.  For instance,
      in a non-source routing environment, segment number
      assignment is not required."
  DEFVAL { 65535 }
  ::= { dlswIfEntry 2 }

dlswIfSapList  OBJECT-TYPE
  SYNTAX     OCTET STRING  (SIZE(16))
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "The SAP list indicates which SAPs are allowed to be
      data link switched through this interface.
 This list
      has the same format described for dlswTConnConfigSapList.

      When changes to this object take effect is implementation-
      specific.  Turning off a particular SAP can destroy
      active circuits that are using that SAP.  An agent
      implementation may reject such changes until there are no
      active circuits if it so chooses.  In this case, it is up
      to the manager to close the circuits first, using
      dlswCircuitState.

      The DEFVAL below indicates support for SAPs 0, 4, 8, and C."
  DEFVAL  { 'AA000000000000000000000000000000'H }
  ::= { dlswIfEntry 3 }


-- ****************************************************************************
-- DIRECTORY
-- Directory services caches the locations of MAC addresses
-- and NetBIOS names.  For resources which are attached via
-- local interfaces, the ifIndex may be cached, and for
-- resources which are reachable via a DLSw partner, the
-- transport address of the DLSw partner is cached.
--
 ****************************************************************************

-- ----------------------------------------------------------------
-- Directory Related Statistical Objects
```

```
-- ---------------------------------------------------------------------
dlswDirStat     OBJECT IDENTIFIER ::= { dlswDirectory 1 }

dlswDirMacEntries  OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The current total number of entries in the dlswDirMacTable."
  ::= { dlswDirStat 1 }

dlswDirMacCacheHits  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of times a cache search for a particular MAC address
     resulted in success."
  ::= { dlswDirStat 2 }

dlswDirMacCacheMisses  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of times a cache search for a particular MAC address
     resulted in failure."
   ::= { dlswDirStat 3 }

dlswDirMacCacheNextIndex  OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The next value of dlswDirMacIndex to be assigned by
     the agent.  A retrieval of this object atomically reserves
     the returned value for use by the manager to create a row
     in dlswDirMacTable.  This makes it possible for the agent
     to control the index space of the MAC address cache, yet
     allows the manager to administratively create new rows."
  ::= { dlswDirStat 4 }

dlswDirNBEntries  OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The current total number of entries in the dlswDirNBTable."
```

```
  ::= { dlswDirStat 5 }

dlswDirNBCacheHits  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of times a cache search for a particular NetBIOS
     name resulted
 in success."
  ::= { dlswDirStat 6 }

dlswDirNBCacheMisses  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of times a cache search for a particular NetBIOS
     name resulted in failure."
  ::= { dlswDirStat 7 }

dlswDirNBCacheNextIndex  OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The next value of dlswDirNBIndex to be assigned by the
     agent.  A retrieval of this object atomically reserves
     the returned value for use by the manager to create
     a row in dlswDirNBTable.  This makes it possible for the
     agent to control the index space for the NetBIOS name
     cache, yet allows the manager to administratively
     create new rows."
  ::= { dlswDirStat 8 }

-- ---------------------------------------------------------------------
-- Directory Cache
-- ---------------------------------------------------------------------
dlswDirCache
    OBJECT IDENTIFIER ::= { dlswDirectory 2 }

-- .....................................................................
-- Directory for MAC Addresses.
-- All Possible combinations of values of these objects.
--
--    EntryType   LocationType       Location        Status
--  --------------- ------------ ------------------ --------------
--  userConfigured    local     ifEntry or 0.0     reachable, or
```

```
--                                      notReachable, or
--                                      unknown
-- userConfigured    remote    TConnConfigEntry   reachable, or
--                                      notReachable, or
--                                      unknown
-- partnerCapExMsg   remote    TConnOperEntry     unknown
-- dynamic           local     ifEntry or 0.0     reachable
-- dynamic           remote    TConnOperEntry     reachable
--
-- ..............................................................
dlswDirMacTable
 OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswDirMacEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "This table contains locations of MAC addresses.
     They could be either verified or not verified,
     local or remote, and configured locally or learned
     from either Capabilities Exchange messages or
     directory searches."
  ::= { dlswDirCache 1 }

dlswDirMacEntry  OBJECT-TYPE
  SYNTAX     DlswDirMacEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "Indexed by dlswDirMacIndex."
  INDEX   { dlswDirMacIndex }
  ::= { dlswDirMacTable 1 }

DlswDirMacEntry ::= SEQUENCE {
  dlswDirMacIndex         INTEGER,
  dlswDirMacMac           MacAddressNC,
  dlswDirMacMask          MacAddressNC,
  dlswDirMacEntryType     INTEGER,
  dlswDirMacLocationType  INTEGER,
  dlswDirMacLocation      RowPointer,
  dlswDirMacStatus        INTEGER,
  dlswDirMacLFSize
   LFSize,
  dlswDirMacRowStatus     RowStatus
  }

dlswDirMacIndex  OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS not-accessible
```

```
  STATUS     current
  DESCRIPTION
    "Uniquely identifies a conceptual row of this table."
  ::= { dlswDirMacEntry 1 }

dlswDirMacMac  OBJECT-TYPE
  SYNTAX     MacAddressNC
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The MAC address, together with the dlswDirMacMask,
     specifies a set of MAC addresses that are defined or
     discovered through an interface or partner DLSw nodes."
  ::= { dlswDirMacEntry 2 }

dlswDirMacMask  OBJECT-TYPE
  SYNTAX     MacAddressNC
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The MAC address mask, together with the dlswDirMacMac,
     specifies a set of MAC addresses that are defined or
     discovered through an interface or partner DLSw nodes."
  DEFVAL { 'FFFFFFFFFFFF'H }
  ::= { dlswDirMacEntry 3 }

dlswDirMacEntryType
  OBJECT-TYPE
  SYNTAX     INTEGER  {
     other                (1),
     userConfiguredPublic     (2),
     userConfiguredPrivate    (3),
     partnerCapExMsg          (4),
     dynamic              (5)
  }
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The cause of the creation of this conceptual row.
     It could be one of the three methods: (1) user
     configured, including via management protocol
     set operations, configuration file, command line
     or equivalent methods; (2) learned from the
     partner DLSw Capabilities Exchange messages;
     and (3) dynamic, e.g., learned from ICanReach
     messages, or LAN explorer frames.  Since only
     individual MAC addresses can be dynamically learned,
     dynamic entries will all have a mask of all FFs.
```

```
      The public versus private distinction for user-
      configured resources applies only to local resources
      (UC remote
 resources are private), and indicates
      whether that resource should be advertised in
      capabilities exchange messages sent by this node."
  DEFVAL { userConfiguredPublic }
  ::= { dlswDirMacEntry 4 }

dlswDirMacLocationType  OBJECT-TYPE
  SYNTAX     INTEGER  {
      other              (1),
      local              (2),
      remote               (3)
  }
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "The location of the resource (or a collection of
      resources using a mask) of this conceptual row
      is either (1) local - the resource is reachable
      via an interface, or (2) remote - the resource
      is reachable via a partner DLSw node (or a set
      of partner DLSw nodes)."
  DEFVAL { local }
  ::= { dlswDirMacEntry 5 }

dlswDirMacLocation  OBJECT-TYPE
  SYNTAX     RowPointer
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "Points to either the ifEntry, dlswTConnConfigEntry,
       dlswTConnOperEntry, 0.0, or something that is implementation
      specific.  It identifies the location of the MAC address
      (or the collection of MAC addresses.)"
  DEFVAL { null }
  ::= { dlswDirMacEntry 6 }

dlswDirMacStatus  OBJECT-TYPE
  SYNTAX     INTEGER  {
      unknown              (1),
      reachable            (2),
      notReachable         (3)
  }
  MAX-ACCESS read-create
  STATUS     current
```

```
  DESCRIPTION
     "This object specifies whether DLSw currently believes
      the MAC address to be accessible at the specified location.
      The value `notReachable' allows a configured resource
      definition to be taken out of service when a search to
      that resource fails (avoiding a repeat of the search)."
  DEFVAL { unknown }
  ::= { dlswDirMacEntry 7 }

dlswDirMacLFSize  OBJECT-TYPE
  SYNTAX     LFSize
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "The largest size of the MAC
 INFO field (LLC header and data)
      that a circuit to the MAC address can carry through this path."
  DEFVAL { lfs65535 }
  ::= { dlswDirMacEntry 8 }

dlswDirMacRowStatus  OBJECT-TYPE
  SYNTAX     RowStatus
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "This object is used by the manager to create
      or delete the row entry in the dlswDirMacTable
      following the RowStatus textual convention."
  ::= { dlswDirMacEntry 9 }

-- ..........................................................................
-- Directory for NetBIOS Names
-- All Possible combinations of values of these objects.
--
--    EntryType   LocationType       Location        Status
--  --------------- ------------ ------------------- --------------
-- userConfigured    local     ifEntry or 0.0     reachable, or
--                                    notReachable, or
--                                    unknown
-- userConfigured    remote    TConnConfigEntry
  reachable, or
--                                    notReachable, or
--                                    unknown
-- partnerCapExMsg   remote    TConnOperEntry     unknown
-- dynamic           local     ifEntry or 0.0     reachable
-- dynamic           remote    TConnOperEntry     reachable
--
-- ..........................................................................
```

```
dlswDirNBTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswDirNBEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "This table contains locations of NetBIOS names.
     They could be either verified or not verified,
     local or remote, and configured locally or learned
     from either Capabilities Exchange messages or
     directory searches."
  ::= { dlswDirCache 2 }

dlswDirNBEntry  OBJECT-TYPE
  SYNTAX     DlswDirNBEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "Indexed by dlswDirNBIndex."
  INDEX   {
 dlswDirNBIndex }
  ::= { dlswDirNBTable 1 }

DlswDirNBEntry ::= SEQUENCE {
  dlswDirNBIndex          INTEGER,
  dlswDirNBName           NBName,
  dlswDirNBNameType       INTEGER,
  dlswDirNBEntryType      INTEGER,
  dlswDirNBLocationType   INTEGER,
  dlswDirNBLocation       RowPointer,
  dlswDirNBStatus         INTEGER,
  dlswDirNBLFSize         LFSize,
  dlswDirNBRowStatus      RowStatus
  }

dlswDirNBIndex  OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "Uniquely identifies a conceptual row of this table."
  ::= { dlswDirNBEntry 1 }

dlswDirNBName  OBJECT-TYPE
  SYNTAX     NBName
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The NetBIOS name (including `any char' and `wildcard'
```

```
      characters) specifies a set of NetBIOS names that are
      defined or discovered through an interface or partner
      DLSw nodes."
  ::= { dlswDirNBEntry
 2 }

dlswDirNBNameType  OBJECT-TYPE
  SYNTAX     INTEGER  {
      unknown       (1),
      individual    (2),
      group         (3)
  }
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "Whether dlswDirNBName represents an (or a set of) individual
     or group NetBIOS name(s)."
  DEFVAL { unknown }
  ::= { dlswDirNBEntry 3 }

dlswDirNBEntryType  OBJECT-TYPE
  SYNTAX     INTEGER  {
      other                 (1),
      userConfiguredPublic     (2),
      userConfiguredPrivate    (3),
      partnerCapExMsg          (4),
      dynamic                  (5)
  }
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The cause of the creation of this conceptual row.
     It could be one of the three methods: (1) user
     configured, including via management protocol
     set operations, configuration file, command line,
     or equivalent methods; (2) learned from the
     partner DLSw Capabilities
 Exchange messages;
     and (3) dynamic, e.g., learned from ICanReach
     messages, or test frames.  Since only actual
     NetBIOS names can be dynamically learned, dynamic
     entries will not contain any char or wildcard
     characters.

     The public versus private distinction for user-
     configured resources applies only to local resources
     (UC remote resources are private), and indicates
     whether that resource should be advertised in
```

```
      capabilities exchange messages sent by this node."
    DEFVAL { userConfiguredPublic }
    ::= { dlswDirNBEntry 4 }

dlswDirNBLocationType  OBJECT-TYPE
    SYNTAX     INTEGER  {
       other              (1),
       local              (2),
       remote              (3)
    }
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
      "The location of the resource (or a collection of resources
       using any char/wildcard characters) of this conceptual row
       is either
 (1) local - the resource is reachable via an
       interface, or (2) remote - the resource is reachable via a
       a partner DLSw node (or a set of partner DLSw nodes)."
    DEFVAL { local }
    ::= { dlswDirNBEntry 5 }

dlswDirNBLocation  OBJECT-TYPE
    SYNTAX     RowPointer
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
      "Points to either the ifEntry, dlswTConnConfigEntry,
       dlswTConnOperEntry, 0.0, or something that is implementation
       specific.  It identifies the location of the NetBIOS name
       or the set of NetBIOS names."
    DEFVAL { null }
    ::= { dlswDirNBEntry 6 }

dlswDirNBStatus  OBJECT-TYPE
    SYNTAX     INTEGER  {
       unknown             (1),
       reachable           (2),
       notReachable         (3)
    }
    MAX-ACCESS read-create
    STATUS     current
    DESCRIPTION
      "This object specifies whether DLSw currently believes
       the NetBIOS name to be accessible at the specified location.
        The value `notReachable' allows a configured resource
       definition to be taken out of service when a search to
       that resource fails (avoiding a repeat of the search)."
```

```
  DEFVAL { unknown }
  ::= { dlswDirNBEntry 7 }

dlswDirNBLFSize  OBJECT-TYPE
  SYNTAX     LFSize
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The largest size of the MAC INFO field (LLC header and data)
     that a circuit to the NB name can carry through this path."
  DEFVAL { lfs65535 }
  ::= { dlswDirNBEntry 8 }

dlswDirNBRowStatus  OBJECT-TYPE
  SYNTAX     RowStatus
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "This object is used by manager to create
     or delete the row entry in the dlswDirNBTable
     following the RowStatus textual convention."
  ::= { dlswDirNBEntry 9 }



-- ---------------------------------------------------------------
-- Resource Locations
-- ---------------------------------------------------------------
dlswDirLocate
      OBJECT IDENTIFIER ::= { dlswDirectory 3 }

-- .....................................................................
-- Locate Entries in the dlswDirMacTable for a given MAC address
-- .....................................................................
dlswDirLocateMacTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswDirLocateMacEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "This table is used to retrieve all entries in the
     dlswDirMacTable that match a given MAC address,
     in the order of the best matched first, the
     second best matched second, and so on, till
     no more entries match the given MAC address."
  ::= { dlswDirLocate 1 }

dlswDirLocateMacEntry  OBJECT-TYPE
  SYNTAX     DlswDirLocateMacEntry
  MAX-ACCESS not-accessible
```

```
  STATUS     current
  DESCRIPTION
     "Indexed by dlswDirLocateMacMac and dlswDirLocateMacMatch.
      The first object is the MAC address of interest,
 and
      the second object is the order in the list of all
      entries that match the MAC address."
  INDEX   { dlswDirLocateMacMac, dlswDirLocateMacMatch }
  ::= { dlswDirLocateMacTable 1 }

DlswDirLocateMacEntry ::= SEQUENCE {
  dlswDirLocateMacMac           MacAddressNC,
  dlswDirLocateMacMatch         INTEGER,
  dlswDirLocateMacLocation      RowPointer
  }

dlswDirLocateMacMac  OBJECT-TYPE
  SYNTAX     MacAddressNC
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "The MAC address to be located."
  ::= { dlswDirLocateMacEntry 1 }

dlswDirLocateMacMatch  OBJECT-TYPE
  SYNTAX     INTEGER (1..255)
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "The order of the entries of dlswDirMacTable
      that match dlswDirLocateMacMac.  A value of
      one represents the entry that best matches the
      MAC address.  A value of two represents the second
      best matched entry, and so on."

 ::= { dlswDirLocateMacEntry 2 }

dlswDirLocateMacLocation  OBJECT-TYPE
  SYNTAX     RowPointer
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "Points to the dlswDirMacEntry."
  ::= { dlswDirLocateMacEntry 3 }

-- ..........................................................................
-- Locate Entries in the dlswDirNBTable for a given NetBIOS name
-- ..........................................................................
```

```
dlswDirLocateNBTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswDirLocateNBEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "This table is used to retrieve all entries in the
     dlswDirNBTable that match a given NetBIOS name,
     in the order of the best matched first, the
     second best matched second, and so on, till
     no more entries match the given NetBIOS name."
  ::= { dlswDirLocate 2 }

dlswDirLocateNBEntry  OBJECT-TYPE
  SYNTAX     DlswDirLocateNBEntry
  MAX-ACCESS not-accessible

  STATUS     current
  DESCRIPTION
    "Indexed by dlswDirLocateNBName and dlswDirLocateNBMatch.
     The first object is the NetBIOS name of interest, and
     the second object is the order in the list of all
     entries that match the NetBIOS name."
  INDEX   { dlswDirLocateNBName, dlswDirLocateNBMatch }
  ::= { dlswDirLocateNBTable 1 }

DlswDirLocateNBEntry ::= SEQUENCE {
  dlswDirLocateNBName          NBName,
  dlswDirLocateNBMatch         INTEGER,
  dlswDirLocateNBLocation       RowPointer
  }

dlswDirLocateNBName  OBJECT-TYPE
  SYNTAX     NBName
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The NetBIOS name to be located (no any char or wildcards)."
  ::= { dlswDirLocateNBEntry 1 }

dlswDirLocateNBMatch  OBJECT-TYPE
  SYNTAX     INTEGER (1..255)
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The order of the entries of dlswDirNBTable
     that match dlswDirLocateNBName.  A value of
      one represents the entry that best matches the
     NetBIOS name.  A value of two represents the second
```

```
      best matched entry, and so on."
  ::= { dlswDirLocateNBEntry 2 }

dlswDirLocateNBLocation  OBJECT-TYPE
  SYNTAX     RowPointer
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "Points to the dlswDirNBEntry."
  ::= { dlswDirLocateNBEntry 3 }


-- ****************************************************************
-- CIRCUIT
-- A circuit is the end-to-end association of two DLSw entities
-- through one or two DLSw nodes.  It is the concatenation of
-- two "data links", optionally with an intervening transport
-- connection. The origin of the circuit is the end station that
-- initiates the circuit.  The target of the circuit is the end
-- station that receives the initiation.
-- ****************************************************************

-- ----------------------------------------------------------------
-- Statistics Related to
 Circuits
-- ----------------------------------------------------------------
dlswCircuitStat      OBJECT IDENTIFIER ::= { dlswCircuit 1 }

dlswCircuitStatActives  OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The current number of circuits in dlswCircuitTable that are
     not in the disconnected state."
  ::= { dlswCircuitStat 1 }

dlswCircuitStatCreates  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The total number of entries ever added to dlswCircuitTable,
     or reactivated upon exiting `disconnected' state."
  ::= { dlswCircuitStat 2 }


-- ----------------------------------------------------------------
```

```
-- Circuit Table
--
-- This table is the DLSw entity's view of circuits.  There will be
-- a conceptual row in the table associated with each data link.
--
-- The chart below lists the various possible combinations of
-- origin and target MAC
 locations and the number of entries in
-- this Circuit Table:
--
--          number of       |    Origin End Station Location
--         entries in the    |--------------------------------------
--         Circuit Table     | internal     local       remote
--     ---------------------- |--------------------------------------
--     Target    | internal |     NA          2           1
--     End       | local    |     2           2           1
--     Station   | remote   |     1           1           NA
--     Location  |          |
--
--     NA: Not applicable
--
--  Note:
--  (a) IfIndex and RouteInfo are applied only if location is local.
--  (b) TDomain and TAddr are applied only if location is remote.
--
-- Most of statistics related to circuits can be collected
-- from LLC-2 Link Station Table.
-- --------------------------------------------------------------------
dlswCircuitTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswCircuitEntry
  MAX-ACCESS not-accessible
  STATUS
    current
  DESCRIPTION
     "This table is the circuit representation in the DLSw
      entity. Virtual data links are used to represent any internal
      end stations.  There is a conceptual row associated with
      each data link.  Thus, for circuits without an intervening
      transport connection, there are two conceptual rows
      for each circuit.

      The table consists of the circuits being established,
      established, and as an implementation option, circuits that
      have been disconnected.  For circuits carried over
      transport connections, an entry is created after
      the CUR_cs was sent or received.  For circuits between
      two locally attached devices, or internal virtual MAC
      addresses, an entry is created when the equivalent of
```

```
      CUR_cs sent/received status is reached.

      End station 1 (S1) and End station 2 (S2) are used to
      represent the two end stations of the circuit.
      S1 is always
 an end station which is locally attached.
      S2 may be locally attached or remote.  If it is locally
      attached, the circuit will be represented by two rows indexed
      by (A, B) and (B, A) where A & B are the relevant MACs/SAPs.

      The table may be used to store the causes of disconnection of
      circuits.  It is recommended that the oldest disconnected
      circuit entry be removed from this table when the memory
      space of disconnected circuits is needed."
  ::= { dlswCircuit 2 }

dlswCircuitEntry  OBJECT-TYPE
  SYNTAX     DlswCircuitEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    ""
  INDEX   { dlswCircuitS1Mac,
            dlswCircuitS1Sap,
            dlswCircuitS2Mac,
            dlswCircuitS2Sap }
  ::= { dlswCircuitTable 1 }

DlswCircuitEntry ::= SEQUENCE {
  dlswCircuitS1Mac             MacAddressNC,
  dlswCircuitS1Sap             OCTET STRING,
  dlswCircuitS1IfIndex          INTEGER,
   dlswCircuitS1DlcType          DlcType,
  dlswCircuitS1RouteInfo        OCTET STRING,
  dlswCircuitS1CircuitId        OCTET STRING,
  dlswCircuitS1Dlc             RowPointer,

  dlswCircuitS2Mac             MacAddressNC,
  dlswCircuitS2Sap             OCTET STRING,
  dlswCircuitS2Location         EndStationLocation,
  dlswCircuitS2TDomain          OBJECT IDENTIFIER,
  dlswCircuitS2TAddress         TAddress,
  dlswCircuitS2CircuitId        OCTET STRING,

  dlswCircuitOrigin            INTEGER,

  dlswCircuitEntryTime          TimeTicks,
  dlswCircuitStateTime          TimeTicks,
```

```
  dlswCircuitState               INTEGER,

  dlswCircuitPriority            INTEGER,

  dlswCircuitFCSendGrantedUnits   INTEGER,
  dlswCircuitFCSendCurrentWndw    INTEGER,
  dlswCircuitFCRecvGrantedUnits   INTEGER,
  dlswCircuitFCRecvCurrentWndw    INTEGER,
  dlswCircuitFCLargestRecvGranted Gauge32,
  dlswCircuitFCLargestSendGranted
 Gauge32,
  dlswCircuitFCHalveWndwSents     Counter32,
  dlswCircuitFCResetOpSents       Counter32,
  dlswCircuitFCHalveWndwRcvds     Counter32,
  dlswCircuitFCResetOpRcvds       Counter32,
  dlswCircuitDiscReasonLocal      INTEGER,
  dlswCircuitDiscReasonRemote     INTEGER,
  dlswCircuitDiscReasonRemoteData OCTET STRING
  }

-- ..........................................................................
-- Information related to the End Station 1 (S1).
-- ..........................................................................
dlswCircuitS1Mac  OBJECT-TYPE
  SYNTAX     MacAddressNC
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The MAC Address of End Station 1 (S1) used for this circuit."
  ::= { dlswCircuitEntry 1 }

dlswCircuitS1Sap  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE(1))
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The SAP at End Station 1 (S1) used for this circuit."
  ::= { dlswCircuitEntry 2 }

dlswCircuitS1IfIndex
 OBJECT-TYPE
  SYNTAX     INTEGER (0..2147483647)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The ifEntry index of the local interface through which S1
     can be reached."
  ::= { dlswCircuitEntry 3 }
```

```
dlswCircuitS1DlcType  OBJECT-TYPE
  SYNTAX     DlcType
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The DLC protocol in use between the DLSw node and S1."
  ::= { dlswCircuitEntry 4 }

dlswCircuitS1RouteInfo  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (0..30))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "If source-route bridging is in use between the DLSw
     node and S1, this is the routing information field
     describing the path between the two devices.
     Otherwise the value will be an OCTET STRING of
     zero length."
  ::= { dlswCircuitEntry 5 }

dlswCircuitS1CircuitId  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (0 | 8))
  MAX-ACCESS read-only
   STATUS     current
  DESCRIPTION
    "The Circuit ID assigned by this DLSw node to this circuit.
     The first four octets are the DLC port Id, and
     the second four octets are the Data Link Correlator.
     If the DLSw SSP was not used to establish this circuit,
     the value will be a string of zero length."
  ::= { dlswCircuitEntry 6 }

dlswCircuitS1Dlc  OBJECT-TYPE
  SYNTAX     RowPointer
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "Points to a conceptual row of the underlying DLC MIB,
     which could either be the standard MIBs (e.g., the SDLC),
     or an enterprise-specific DLC MIB."
  ::= { dlswCircuitEntry 7 }

-- ..........................................................
-- Information related to the End Station 2 (S2).
-- ..........................................................
dlswCircuitS2Mac  OBJECT-TYPE
  SYNTAX     MacAddressNC
```

```
  MAX-ACCESS not-accessible
  STATUS     current

 DESCRIPTION
    "The MAC Address of End Station 2 (S2) used for this circuit."
  ::= { dlswCircuitEntry 8 }

dlswCircuitS2Sap  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE(1))
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The SAP at End Station 2 (S2) used for this circuit."
  ::= { dlswCircuitEntry 9 }

dlswCircuitS2Location  OBJECT-TYPE
  SYNTAX     EndStationLocation
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The location of End Station 2 (S2).
     If the location of End Station 2 is local, the
     interface information will be available in the
     conceptual row whose S1 and S2 are the S2 and
     the S1 of this conceptual row, respectively."
  ::= { dlswCircuitEntry 10 }

dlswCircuitS2TDomain  OBJECT-TYPE
  SYNTAX     OBJECT IDENTIFIER
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "If the location of End Station 2 is remote,
     this value is the transport domain
 of the
     transport protocol the circuit is running
     over.  Otherwise, the value is 0.0."
  ::= { dlswCircuitEntry 11 }

dlswCircuitS2TAddress  OBJECT-TYPE
  SYNTAX     TAddress
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "If the location of End Station 2 is remote,
     this object contains the address of the partner
     DLSw, else it will be an OCTET STRING of zero length."
  ::= { dlswCircuitEntry 12 }
```

```
dlswCircuitS2CircuitId  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (0 | 8))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The Circuit ID assigned to this circuit by the partner
     DLSw node.  The first four octets are the DLC port Id, and
     the second four octets are the Data Link Correlator.
     If the DLSw SSP was not used to establish this circuit,
     the value will be a string of zero length."
  ::= { dlswCircuitEntry 13 }

-- ..........................................................
dlswCircuitOrigin
 OBJECT-TYPE
  SYNTAX     INTEGER  {
     s1           (1),
     s2           (2)
  }
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "This object specifies which of the two end stations
     initiated the establishment of this circuit."
  ::= { dlswCircuitEntry 14 }

-- ..........................................................
-- Operational information related to this circuit.
-- ..........................................................
dlswCircuitEntryTime  OBJECT-TYPE
  SYNTAX     TimeTicks
  UNITS      "hundredths of a second"
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The amount of time (in hundredths of a second) since this
     circuit table conceptual row was created."
  ::= { dlswCircuitEntry 15 }

dlswCircuitStateTime  OBJECT-TYPE
  SYNTAX     TimeTicks
  UNITS      "hundredths of a second"
  MAX-ACCESS read-only
  STATUS     current
   DESCRIPTION
    "The amount of time (in hundredths of a second) since this
     circuit entered the current state."
```

```
  ::= { dlswCircuitEntry 16 }

dlswCircuitState  OBJECT-TYPE
  SYNTAX     INTEGER  {
     disconnected          (1),
     circuitStart          (2),
     resolvePending        (3),
     circuitPending        (4),
     circuitEstablished    (5),
     connectPending        (6),
     contactPending        (7),
     connected             (8),
     disconnectPending     (9),
     haltPending           (10),
     haltPendingNoack      (11),
     circuitRestart        (12),
     restartPending        (13)
  }
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
     "The current state of this circuit.  The agent, implementation
     specific, may choose to keep entries for some period of time
     after circuit disconnect, so the manager can gather the time
     and cause of disconnection.

      While all of the specified values may be returned from a GET
     operation, the only SETable value is `disconnectPending'.
     When this value is set, DLSw should perform the appropriate
     action given its previous state (e.g., send HALT_DL if the
     state was `connected') to bring the circuit down to the
     `disconnected' state.  Both the partner DLSw and local end
     station(s) should be notified as appropriate.

     This MIB provides no facility to re-establish a disconnected
     circuit, because in DLSw this should be an end station-driven
     function."
  ::= { dlswCircuitEntry 17 }

dlswCircuitPriority  OBJECT-TYPE
  SYNTAX     INTEGER  {
     unsupported     (1),
     low             (2),
     medium          (3),
     high            (4),
     highest         (5)
  }
  MAX-ACCESS read-only
```

```
    STATUS      current
    DESCRIPTION
        "The transmission priority of this circuit as understood by
        this
   DLSw node.  This value is determined by the two DLSw
        nodes at circuit startup time.  If this DLSw node does not
        support DLSw circuit priority, the value `unsupported' should
        be returned."
    ::= { dlswCircuitEntry 18 }

-- ..........................................................................
-- Pacing Objects:
-- These objects are applicable if DLSw is using the SSP circuit
-- pacing protocol to control the flow between the two data links
-- in this circuit.
-- ..........................................................................
dlswCircuitFCSendGrantedUnits  OBJECT-TYPE
    SYNTAX      INTEGER (0..65535)
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
        "The number of paced SSP messages that this DLSw is currently
        authorized to send on this circuit before it must stop and
        wait for an additional flow control indication from the
        partner DLSw.

        The value zero should be returned if this circuit is not
        running
   the DLSw pacing protocol."
    ::= { dlswCircuitEntry 19 }

dlswCircuitFCSendCurrentWndw  OBJECT-TYPE
    SYNTAX      INTEGER (0..65535)
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
        "The current window size that this DLSw is using in its role
        as a data sender.  This is the value by which this DLSw would
        increase the number of messages it is authorized to send, if
        it were to receive a flow control indication with the bits
        specifying `repeat window'.
        The value zero should be returned if this circuit is not
        running the DLSw pacing protocol."
    ::= { dlswCircuitEntry 20 }

dlswCircuitFCRecvGrantedUnits  OBJECT-TYPE
    SYNTAX      INTEGER (0..65535)
    MAX-ACCESS read-only
```

```
    STATUS      current
    DESCRIPTION
        "The current number of paced SSP messages that this DLSw has
         authorized the partner DLSw to send on this circuit before
         the partner DLSw must stop and wait for an additional flow

        control indication from this DLSw.

         The value zero should be returned if this circuit is not
         running the DLSw pacing protocol."
    ::= { dlswCircuitEntry 21 }

dlswCircuitFCRecvCurrentWndw  OBJECT-TYPE
    SYNTAX      INTEGER (0..65535)
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
        "The current window size that this DLSw is using in its role
         as a data receiver.  This is the number of additional paced
         SSP messages that this DLSw would be authorizing its DLSw
         partner to send, if this DLSw were to send a flow control
         indication with the bits specifying `repeat window'.

         The value zero should be returned if this circuit is not
         running the DLSw pacing protocol."
    ::= { dlswCircuitEntry 22 }

dlswCircuitFCLargestRecvGranted  OBJECT-TYPE
    SYNTAX      Gauge32
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
        "The largest receive window size granted by this DLSw during

    the current activation of this circuit.  This is not the
         largest number of messages granted at any time, but the
         largest window size as represented by FCIND operator bits.

         The value zero should be returned if this circuit is not
         running the DLSw pacing protocol."
    ::= { dlswCircuitEntry 23 }

dlswCircuitFCLargestSendGranted  OBJECT-TYPE
    SYNTAX      Gauge32
    MAX-ACCESS read-only
    STATUS      current
    DESCRIPTION
        "The largest send (with respect to this DLSw) window size
```

```
      granted by the partner DLSw during the current activation of
      this circuit.

      The value zero should be returned if this circuit is not
      running the DLSw pacing protocol."
  ::= { dlswCircuitEntry 24 }

dlswCircuitFCHalveWndwSents  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of Halve Window operations this DLSw has sent on
      this circuit, in its role as a data
 receiver.

      The value zero should be returned if this circuit is not
      running the DLSw pacing protocol."
  ::= { dlswCircuitEntry 25 }

dlswCircuitFCResetOpSents  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of Reset Window operations this DLSw has sent on
      this circuit, in its role as a data receiver.

      The value zero should be returned if this circuit is not
      running the DLSw pacing protocol."
  ::= { dlswCircuitEntry 26 }

dlswCircuitFCHalveWndwRcvds  OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of Halve Window operations this DLSw has received on
      this circuit, in its role as a data sender.

      The value zero should be returned if this circuit is not
      running the DLSw pacing protocol."
  ::= { dlswCircuitEntry 27 }

dlswCircuitFCResetOpRcvds  OBJECT-TYPE
  SYNTAX     Counter32
   MAX-ACCESS read-only
  STATUS     current
```

```
  DESCRIPTION
     "The number of Reset Window operations this DLSw has received on
      this circuit, in its role as a data sender.
      The value zero should be returned if this circuit is not
      running the DLSw pacing protocol."
  ::= { dlswCircuitEntry 28 }


-- ...........................................................
-- Information about the circuit disconnection
-- ...........................................................
dlswCircuitDiscReasonLocal  OBJECT-TYPE
  SYNTAX     INTEGER  {
      endStationDiscRcvd          (1),
      endStationDlcError          (2),
      protocolError               (3),
      operatorCommand             (4),
      haltDlRcvd                  (5),
      haltDlNoAckRcvd             (6),
      transportConnClosed         (7)
  }
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The reason why this circuit was last
 disconnected, as seen
      by this DLSw node.

      This object is present only if the agent keeps circuit
      table entries around for some period after circuit disconnect."
  ::= { dlswCircuitEntry 29 }

dlswCircuitDiscReasonRemote  OBJECT-TYPE
  SYNTAX     INTEGER  {
      unknown                     (1),
      endStationDiscRcvd          (2),
      endStationDlcError          (3),
      protocolError               (4),
      operatorCommand             (5)
  }
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The generic reason code why this circuit was last
      disconnected, as reported by the DLSw partner in a HALT_DL
      or HALT_DL_NOACK.  If the partner does not send a reason
      code in these messages, or the DLSw implementation does
      not report receiving one, the value `unknown' is returned.
```

```
      This object is present only if the agent keeps circuit table
      entries around for some period after
 circuit disconnect."
  ::= { dlswCircuitEntry 30 }

dlswCircuitDiscReasonRemoteData  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (0 | 4))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "Implementation-specific data reported by the DLSw partner in
     a HALT_DL or HALT_DL_NOACK, to help specify how and why this
     circuit was last disconnected.  If the partner does not send
     this data in these messages, or the DLSw implementation does
     not report receiving it, a string of zero length is returned.

     This object is present only if the agent keeps circuit table
     entries around for some period after circuit disconnect."
  ::= { dlswCircuitEntry 31 }


-- ....................................................................
-- Statistics related to this circuit.
-- All statistics are in LLC-2 Link Station Statistical Table.
-- All SDLC statistics are in SDLC MIB
-- ....................................................................


--
 ************************************************************************
-- DLSW SDLC EXTENSION
-- ************************************************************************
dlswSdlcLsEntries  OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The number of entries in dlswSdlcLsTable."
  ::= { dlswSdlc 1 }

-- ....................................................................
dlswSdlcLsTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF DlswSdlcLsEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "The table defines the virtual MAC addresses for those
```

```
      SDLC link stations that participate in data link switching."
   ::= { dlswSdlc 2 }

dlswSdlcLsEntry  OBJECT-TYPE
   SYNTAX     DlswSdlcLsEntry
   MAX-ACCESS not-accessible
   STATUS     current
   DESCRIPTION
      "The index of this table is the ifIndex value for the
       SDLC port which owns this link station and the poll
       address of
 the particular SDLC link station."
   INDEX  { ifIndex, sdlcLSAddress }
   ::= { dlswSdlcLsTable 1 }

DlswSdlcLsEntry ::= SEQUENCE {
   dlswSdlcLsLocalMac          MacAddressNC,
   dlswSdlcLsLocalSap          OCTET STRING,
   dlswSdlcLsLocalIdBlock      DisplayString,
   dlswSdlcLsLocalIdNum        DisplayString,
   dlswSdlcLsRemoteMac         MacAddressNC,
   dlswSdlcLsRemoteSap         OCTET STRING,
   dlswSdlcLsRowStatus         RowStatus
   }

dlswSdlcLsLocalMac    OBJECT-TYPE
   SYNTAX     MacAddressNC
   MAX-ACCESS read-create
   STATUS     current
   DESCRIPTION
      "The virtual MAC address used to represent the SDLC-attached
       link station to the rest of the DLSw network."
   ::= { dlswSdlcLsEntry 1 }

dlswSdlcLsLocalSap    OBJECT-TYPE
   SYNTAX     OCTET STRING (SIZE(1))
   MAX-ACCESS read-create
   STATUS     current
   DESCRIPTION
      "The SAP used to represent this link station."
   ::= { dlswSdlcLsEntry 2 }

dlswSdlcLsLocalIdBlock OBJECT-TYPE
    SYNTAX     DisplayString  (SIZE (0 | 3))
   MAX-ACCESS read-create
   STATUS     current
   DESCRIPTION
      "The block number is the first three digits of the node_id,
```

```
      if available.  These 3 hexadecimal digits identify the
      product."
  DEFVAL { "H" }
  ::= { dlswSdlcLsEntry 3 }

dlswSdlcLsLocalIdNum OBJECT-TYPE
  SYNTAX     DisplayString  (SIZE (0 | 5))
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The ID number is the last 5 digits of the node_id, if
     available.  These 5 hexadecimal digits are
     administratively defined and combined with the 3 digit
     block number form the node_id.  This node_id is used to
     identify the local node and is included in SNA XIDs."
  DEFVAL { "H" }
  ::= { dlswSdlcLsEntry 4 }

dlswSdlcLsRemoteMac    OBJECT-TYPE
  SYNTAX     MacAddressNC
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The MAC address to which DLSw should attempt to
 connect
     this link station. If this information is not available,
     a length of zero for this object should be returned."
  DEFVAL { "H" }
  ::= { dlswSdlcLsEntry 5 }

dlswSdlcLsRemoteSap    OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE (0 | 1))
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "The SAP of the remote station to which this link
     station should be connected.  If this information
     is not available, a length of zero for this object
     should be returned."
  DEFVAL { "H" }
  ::= { dlswSdlcLsEntry 6 }

dlswSdlcLsRowStatus    OBJECT-TYPE
  SYNTAX     RowStatus
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
    "This object is used by the manager to create
```

```
      or delete the row entry in the dlswSdlcLsTable
      following the RowStatus textual convention."
   ::= { dlswSdlcLsEntry 7 }


-- ********************************************************************
-- TRAP GENERATION CONTROL
--
 ********************************************************************
dlswTrapControl OBJECT IDENTIFIER  ::= { dlswNode 10}

dlswTrapCntlTConnPartnerReject  OBJECT-TYPE
   SYNTAX     INTEGER  {
      enabled     (1),
      disabled    (2),
      partial     (3)
   }
   MAX-ACCESS read-write
   STATUS     current
   DESCRIPTION
     "Indicates whether the DLSw is permitted to emit partner
      reject related traps.  With the value of `enabled'
      the DLSw will emit all partner reject related traps.
      With the value of `disabled' the DLSw will not emit
      any partner reject related traps.  With the value
      of `partial' the DLSw will only emits partner reject
      traps for CapEx reject.  The changes take effect
      immediately."
   ::= { dlswTrapControl 1 }

dlswTrapCntlTConnProtViolation  OBJECT-TYPE
   SYNTAX     TruthValue
   MAX-ACCESS read-write
   STATUS     current
   DESCRIPTION
     "Indicates whether the DLSw is permitted to generate
       protocol-violation traps on the events such as
      window size violation.  The changes take effect
      immediately."
   ::= { dlswTrapControl 2 }

dlswTrapCntlTConn  OBJECT-TYPE
   SYNTAX     INTEGER {
      enabled     (1),
      disabled    (2),
      partial     (3)
   }
   MAX-ACCESS read-write
```

```
  STATUS     current
  DESCRIPTION
    "Indicates whether the DLSw is permitted to emit transport
     connection up and down traps.  With the value of `enabled'
     the DLSw will emit traps when connections enter `connected'
     and `disconnected' states.  With the value of `disabled'
     the DLSw will not emit traps when connections enter of
     `connected' and `disconnected' states.  With the value
     of `partial' the DLSw will only emits transport connection
     down traps when the connection is closed with busy.
     The changes take effect immediately."
  ::= { dlswTrapControl 3 }

dlswTrapCntlCircuit  OBJECT-TYPE
   SYNTAX     INTEGER {
      enabled     (1),
      disabled    (2),
      partial     (3)
   }
  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
    "Indicates whether the DLSw is permitted to generate
     circuit up and down traps.  With the value of `enabled'
     the DLSw will emit traps when circuits enter `connected'
     and `disconnected' states.  With the value of `disabled'
     the DLSw will not emit traps when circuits enter of
     `connected' and `disconnected' states.  With the value
     of `partial' the DLSw will emit traps only for those
     circuits that are initiated by this DLSw, e.g.,
     originating the CUR_CS message.  The changes take effect
     immediately."
  ::= { dlswTrapControl 4 }

-- ****************************************************************************
-- NOTIFICATIONS, i.e., TRAP DEFINITIONS
-- ****************************************************************************
dlswTraps             OBJECT IDENTIFIER
 ::= { dlswMIB 0 }

-- ----------------------------------------------------------------
-- This section defines the well-known notifications sent by
-- DLSW agents.
-- Care must be taken to insure that no particular notification
-- is sent to a single receiving entity more often than once
-- every five seconds.
--
-- Traps includes:
```

```
-- (1) Partner rejected (capEx rejection, not in partner list, etc.)
-- (2) DLSw protocol violation (e.g., window size violation, etc.)
-- (3) Transport connection up/down

-- (4) Circuit up/down
-- --------------------------------------------------------------------
--

dlswTrapTConnPartnerReject NOTIFICATION-TYPE
  OBJECTS { dlswTConnOperTDomain, dlswTConnOperRemoteTAddr
  }
  STATUS     current
  DESCRIPTION
    "This trap is sent each time a transport connection
     is rejected by a partner DLSw during Capabilities
     Exchanges.  The emission of this trap is controlled
     by dlswTrapCntlTConnPartnerReject."
  ::= { dlswTraps
 1 }

dlswTrapTConnProtViolation NOTIFICATION-TYPE
  OBJECTS { dlswTConnOperTDomain, dlswTConnOperRemoteTAddr
  }
  STATUS     current
  DESCRIPTION
    "This trap is sent each time a protocol violation is
     detected for a transport connection.  The emission of this
     trap is controlled by dlswTrapCntlTConnProtViolation."
  ::= { dlswTraps 2 }

dlswTrapTConnUp NOTIFICATION-TYPE
  OBJECTS { dlswTConnOperTDomain, dlswTConnOperRemoteTAddr
  }
  STATUS     current
  DESCRIPTION
    "This trap is sent each time a transport connection
     enters `connected' state.  The emission of this trap
     is controlled by dlswTrapCntlTConn."
  ::= { dlswTraps 3 }

dlswTrapTConnDown NOTIFICATION-TYPE
  OBJECTS { dlswTConnOperTDomain, dlswTConnOperRemoteTAddr
  }
  STATUS     current
  DESCRIPTION
    "This trap is sent each time a transport connection
     enters `disconnected' state.  The emission of this trap
     is controlled by dlswTrapCntlTConn."
```

```
   ::= { dlswTraps 4 }

dlswTrapCircuitUp NOTIFICATION-TYPE
  OBJECTS { dlswCircuitS1Mac, dlswCircuitS1Sap,
          dlswCircuitS2Mac, dlswCircuitS2Sap
  }
  STATUS     current
  DESCRIPTION
    "This trap is sent each time a circuit enters `connected'
     state.  The emission of this trap is controlled by
     dlswTrapCntlCircuit."
  ::= { dlswTraps 5 }

dlswTrapCircuitDown NOTIFICATION-TYPE
  OBJECTS { dlswCircuitS1Mac, dlswCircuitS1Sap,
          dlswCircuitS2Mac, dlswCircuitS2Sap
  }
  STATUS     current
  DESCRIPTION
    "This trap is sent each time a circuit enters `disconnected'
     state.  The emission of this trap is controlled by
     dlswTrapCntlCircuit."
  ::= { dlswTraps 6 }


-- ************************************************************************
-- CONFORMANCE INFORMATION
-- ************************************************************************
dlswConformance       OBJECT IDENTIFIER ::= { dlsw 3 }

dlswCompliances
       OBJECT IDENTIFIER ::= { dlswConformance 1 }
dlswGroups            OBJECT IDENTIFIER ::= { dlswConformance 2 }

-- ------------------------------------------------------------------
-- COMPLIANCE STATEMENTS
-- ------------------------------------------------------------------

-- ..................................................................
-- Core compliance for all DLSw entities
-- ..................................................................
dlswCoreCompliance MODULE-COMPLIANCE
  STATUS current
  DESCRIPTION
    "The core compliance statement for all DLSw nodes."
  MODULE
     MANDATORY-GROUPS  {
          dlswNodeGroup,
```

```
            dlswTConnStatGroup,
            dlswTConnConfigGroup,
            dlswTConnOperGroup,
            dlswInterfaceGroup,
            dlswCircuitGroup,
            dlswCircuitStatGroup,
            dlswNotificationGroup }

        GROUP dlswNodeNBGroup
          DESCRIPTION

       "The DLSw NetBIOS Node group is mandatory only for
            those DLSw entities that implement NetBIOS."

        GROUP dlswTConnNBGroup
          DESCRIPTION
            "The DLSw NetBIOS Transport Connection group is
            mandatory only for those DLSw entities that
            implement NetBIOS."

        OBJECT  dlswNodeStatus
          MIN-ACCESS  read-only
          DESCRIPTION
            "Write access is not required."

        OBJECT  dlswNodeVirtualSegmentLFSize
          MIN-ACCESS  read-only
          DESCRIPTION
            "Write access is not required."

        OBJECT  dlswNodeResourceNBExclusivity
          MIN-ACCESS  read-only
          DESCRIPTION
            "Write access is not required."

        OBJECT  dlswNodeResourceMacExclusivity
          MIN-ACCESS  read-only
          DESCRIPTION
            "Write access is not required."

        OBJECT  dlswTrapCntlTConnPartnerReject
          MIN-ACCESS
    read-only
          DESCRIPTION
            "Write access is not required."

        OBJECT  dlswTrapCntlTConnProtViolation
          MIN-ACCESS  read-only
```

DESCRIPTION
"Write access is not required."

OBJECT dlswTrapCntlTConn
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."
OBJECT dlswTrapCntlCircuit
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigTDomain
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigLocalTAddr
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigRemoteTAddr
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigEntryType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigGroupDefinition
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigSetupType
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigSapList
MIN-ACCESS read-only
DESCRIPTION
"Write access is not required."

OBJECT dlswTConnConfigAdvertiseMacNB

```
        MIN-ACCESS  read-only
        DESCRIPTION
            "Write access is not required."

    OBJECT  dlswTConnConfigInitCirRecvWndw
        MIN-ACCESS  read-only
        DESCRIPTION
            "Write access is not required."

    OBJECT  dlswTConnConfigRowStatus
        MIN-ACCESS  read-only
        DESCRIPTION
            "Write access is
not required."

    OBJECT  dlswTConnOperState
        MIN-ACCESS  read-only
        DESCRIPTION
            "Write access is not required."

    OBJECT  dlswIfRowStatus
        MIN-ACCESS  read-only
        DESCRIPTION
            "Write access is not required."

    OBJECT  dlswIfVirtualSegment
        MIN-ACCESS  read-only
        DESCRIPTION
            "Write access is not required."

    OBJECT  dlswIfSapList
        MIN-ACCESS  read-only
        DESCRIPTION
            "Write access is not required."

    OBJECT  dlswCircuitState
        MIN-ACCESS  read-only
        DESCRIPTION
            "Write access is not required."

  ::= { dlswCompliances 1 }

-- ..........................................................................
-- Compliance for all DLSw entities that provide TCP transport.
-- ..........................................................................
dlswTConnTcpCompliance MODULE-COMPLIANCE
```

```
    STATUS current
    DESCRIPTION
        "Compliance for DLSw nodes that use TCP as a
        transport connection protocol."
    MODULE
        MANDATORY-GROUPS  {
            dlswTConnTcpConfigGroup,
            dlswTConnTcpOperGroup }

        OBJECT  dlswTConnTcpConfigKeepAliveInt
            MIN-ACCESS  read-only
            DESCRIPTION
                "Write access is not required."

        OBJECT  dlswTConnTcpConfigTcpConnections
            MIN-ACCESS  read-only
            DESCRIPTION
                "Write access is not required."

        OBJECT  dlswTConnTcpConfigMaxSegmentSize
            MIN-ACCESS  read-only
            DESCRIPTION
                "Write access is not required."

    ::= { dlswCompliances 2 }

-- ..........................................................................
-- Compliance for all DLSw Entities that implement a directory
-- ..........................................................................
dlswDirCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "Compliance for DLSw nodes that provide a directory
        function."
    MODULE
        MANDATORY-GROUPS  {
            dlswDirGroup }

        GROUP dlswDirNBGroup
            DESCRIPTION
                "The DLSw NetBIOS group is mandatory only for
                those DLSw entities that implement NetBIOS."

        OBJECT  dlswDirMacMac
            MIN-ACCESS  read-only
            DESCRIPTION
                "Write access is not required."
```

```
OBJECT  dlswDirMacMask
   MIN-ACCESS  read-only
   DESCRIPTION
      "Write access is not required."

OBJECT  dlswDirMacEntryType
   MIN-ACCESS  read-only
   DESCRIPTION
      "Write access is not required."
OBJECT  dlswDirMacLocationType
   MIN-ACCESS  read-only
   DESCRIPTION
      "Write access is not required."

OBJECT  dlswDirMacLocation
   MIN-ACCESS  read-only
   DESCRIPTION
       "Write access is not required."

OBJECT  dlswDirMacStatus
   MIN-ACCESS  read-only
   DESCRIPTION
      "Write access is not required."

OBJECT  dlswDirMacLFSize
   MIN-ACCESS  read-only
   DESCRIPTION
      "Write access is not required."

OBJECT  dlswDirMacRowStatus
   MIN-ACCESS  read-only
   DESCRIPTION
      "Write access is not required."

OBJECT  dlswDirNBName
   MIN-ACCESS  read-only
   DESCRIPTION
      "Write access is not required."

OBJECT  dlswDirNBNameType
   MIN-ACCESS  read-only
   DESCRIPTION
      "Write access is not required."

OBJECT  dlswDirNBEntryType
   MIN-ACCESS  read-only
   DESCRIPTION
      "Write access is not required."
```

```
        OBJECT  dlswDirNBLocationType
            MIN-ACCESS  read-only
            DESCRIPTION

    "Write access is not required."

        OBJECT  dlswDirNBLocation
            MIN-ACCESS  read-only
            DESCRIPTION
                "Write access is not required."

        OBJECT  dlswDirNBStatus
            MIN-ACCESS  read-only
            DESCRIPTION
                "Write access is not required."

        OBJECT  dlswDirNBLFSize
            MIN-ACCESS  read-only
            DESCRIPTION
                "Write access is not required."

        OBJECT  dlswDirNBRowStatus
            MIN-ACCESS  read-only
            DESCRIPTION
                "Write access is not required."

    ::= { dlswCompliances 3 }

-- ..........................................................
-- Compliance for all DLSw entities that provide an ordered
-- list of directory entries that match a resource
-- ..........................................................
dlswDirLocateCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "Compliance for DLSw nodes that provide
 an ordered
        list of directory entries for a given resource."
    MODULE
        MANDATORY-GROUPS  {
            dlswDirLocateGroup }

        GROUP dlswDirLocateNBGroup
            DESCRIPTION
              "The DLSw NetBIOS group is mandatory only for
               those DLSw entities that implement NetBIOS."
```

```
  ::= { dlswCompliances 4 }

-- ...........................................................
-- Compliance for all DLSw entities that support SDLC end stations
-- ...........................................................
dlswSdlcCompliance MODULE-COMPLIANCE
  STATUS current
  DESCRIPTION
    "Compliance for DLSw nodes that support SDLC."
  MODULE
    MANDATORY-GROUPS  {
          dlswSdlcGroup }

    OBJECT  dlswSdlcLsLocalMac
      MIN-ACCESS  read-only
      DESCRIPTION
        "Write access is not required."

    OBJECT  dlswSdlcLsLocalSap
      MIN-ACCESS  read-only
      DESCRIPTION
         "Write access is not required."

    OBJECT  dlswSdlcLsLocalIdBlock
      MIN-ACCESS  read-only
      DESCRIPTION
        "Write access is not required."

    OBJECT  dlswSdlcLsLocalIdNum
      MIN-ACCESS  read-only
      DESCRIPTION
        "Write access is not required."

    OBJECT  dlswSdlcLsRemoteMac
      MIN-ACCESS  read-only
      DESCRIPTION
        "Write access is not required."

    OBJECT  dlswSdlcLsRemoteSap
      MIN-ACCESS  read-only
      DESCRIPTION
        "Write access is not required."

    OBJECT  dlswSdlcLsRowStatus
      MIN-ACCESS  read-only
      DESCRIPTION
        "Write access is not required."
```

```
  ::= { dlswCompliances 5 }

-- ----------------------------------------------------------------
-- CONFORMANCE GROUPS
-- ----------------------------------------------------------------

-- ..............................................................
--
 Node Conformance Group
-- ..............................................................
dlswNodeGroup  OBJECT-GROUP
  OBJECTS  {
     dlswNodeVersion,
     dlswNodeVendorID,
     dlswNodeVersionString,
     dlswNodeStdPacingSupport,
     dlswNodeStatus,
     dlswNodeUpTime,
     dlswNodeVirtualSegmentLFSize,
     dlswNodeResourceMacExclusivity,
     dlswTrapCntlTConnPartnerReject,
     dlswTrapCntlTConnProtViolation,
     dlswTrapCntlTConn,
     dlswTrapCntlCircuit
     }
  STATUS current
  DESCRIPTION
    "Conformance group for DLSw node general information."
  ::= { dlswGroups 1 }

-- ..............................................................
dlswNodeNBGroup  OBJECT-GROUP
  OBJECTS  {
     dlswNodeResourceNBExclusivity
     }
  STATUS current
  DESCRIPTION
    "Conformance group for DLSw node general information
     specifically for nodes that support NetBIOS."
  ::=
 { dlswGroups 2 }

-- ..............................................................
dlswTConnStatGroup  OBJECT-GROUP
  OBJECTS  {
     dlswTConnStatActiveConnections,
     dlswTConnStatCloseIdles,
     dlswTConnStatCloseBusys
```

```
      }
  STATUS current
  DESCRIPTION
    "Conformance group for statistics for transport
     connections."
  ::= { dlswGroups 3 }

-- ..........................................................
dlswTConnConfigGroup  OBJECT-GROUP
  OBJECTS  {
     dlswTConnConfigTDomain,
     dlswTConnConfigLocalTAddr,
     dlswTConnConfigRemoteTAddr,
     dlswTConnConfigLastModifyTime,
     dlswTConnConfigEntryType,
     dlswTConnConfigGroupDefinition,
     dlswTConnConfigSetupType,
     dlswTConnConfigSapList,
     dlswTConnConfigAdvertiseMacNB,
     dlswTConnConfigInitCirRecvWndw,
     dlswTConnConfigOpens,
     dlswTConnConfigRowStatus
     }
  STATUS current
  DESCRIPTION
    "Conformance
 group for the configuration of
     transport connections."
  ::= { dlswGroups 4 }

-- ..........................................................
dlswTConnOperGroup  OBJECT-GROUP
  OBJECTS  {
     dlswTConnOperLocalTAddr,
     dlswTConnOperEntryTime,
     dlswTConnOperConnectTime,
     dlswTConnOperState,
     dlswTConnOperConfigIndex,
     dlswTConnOperFlowCntlMode,
     dlswTConnOperPartnerVersion,
     dlswTConnOperPartnerVendorID,
     dlswTConnOperPartnerVersionStr,
     dlswTConnOperPartnerInitPacingWndw,
     dlswTConnOperPartnerSapList,
     dlswTConnOperPartnerMacExcl,
     dlswTConnOperPartnerMacInfo,
     dlswTConnOperDiscTime,
     dlswTConnOperDiscReason,
```

```
        dlswTConnOperDiscActiveCir,
        dlswTConnOperInDataPkts,
        dlswTConnOperOutDataPkts,
        dlswTConnOperInDataOctets,
        dlswTConnOperOutDataOctets,
        dlswTConnOperInCntlPkts,
        dlswTConnOperOutCntlPkts,
        dlswTConnOperCURexSents,
         dlswTConnOperICRexRcvds,
        dlswTConnOperCURexRcvds,
        dlswTConnOperICRexSents,
        dlswTConnOperCirCreates,
        dlswTConnOperCircuits
        }
    STATUS current
    DESCRIPTION
      "Conformance group for operation information for
      transport connections."
    ::= { dlswGroups 5 }
-- ..........................................................................
dlswTConnNBGroup  OBJECT-GROUP
    OBJECTS  {
        dlswTConnOperPartnerNBExcl,
        dlswTConnOperPartnerNBInfo,
        dlswTConnOperNQexSents,
        dlswTConnOperNRexRcvds,
        dlswTConnOperNQexRcvds,
        dlswTConnOperNRexSents
        }
    STATUS current
    DESCRIPTION
      "Conformance group for operation information for
      transport connections, specifically for nodes
      that support NetBIOS."
    ::= { dlswGroups 6 }

-- ..........................................................................
dlswTConnTcpConfigGroup  OBJECT-GROUP
    OBJECTS  {
        dlswTConnTcpConfigKeepAliveInt,
         dlswTConnTcpConfigTcpConnections,
        dlswTConnTcpConfigMaxSegmentSize
        }
    STATUS current
    DESCRIPTION
      "Conformance group for configuration information for
      transport connections using TCP."
    ::= { dlswGroups 7 }
```

```
-- ..................................................................
dlswTConnTcpOperGroup  OBJECT-GROUP
  OBJECTS  {
     dlswTConnTcpOperKeepAliveInt,
     dlswTConnTcpOperPrefTcpConnections,
     dlswTConnTcpOperTcpConnections
     }
  STATUS current
  DESCRIPTION
    "Conformance group for operation information for
     transport connections using TCP."
  ::= { dlswGroups 8 }

-- ..................................................................
dlswInterfaceGroup  OBJECT-GROUP
  OBJECTS  {
     dlswIfRowStatus,
     dlswIfVirtualSegment,
     dlswIfSapList
     }
  STATUS current
  DESCRIPTION
    "Conformance group for DLSw interfaces."
  ::= { dlswGroups
 9 }

-- ..................................................................
dlswDirGroup  OBJECT-GROUP
  OBJECTS  {
     dlswDirMacEntries,
     dlswDirMacCacheHits,
     dlswDirMacCacheMisses,
     dlswDirMacCacheNextIndex,
     dlswDirMacMac,
     dlswDirMacMask,
     dlswDirMacEntryType,
     dlswDirMacLocationType,
     dlswDirMacLocation,
     dlswDirMacStatus,
     dlswDirMacLFSize,
     dlswDirMacRowStatus
     }
  STATUS current
  DESCRIPTION
    "Conformance group for DLSw directory using MAC
     addresses."
  ::= { dlswGroups 10 }
```

```
-- ..................................................................
dlswDirNBGroup  OBJECT-GROUP
  OBJECTS  {
     dlswDirNBEntries,
     dlswDirNBCacheHits,
     dlswDirNBCacheMisses,
     dlswDirNBCacheNextIndex,
     dlswDirNBName,
     dlswDirNBNameType,
     dlswDirNBEntryType,
     dlswDirNBLocationType,
     dlswDirNBLocation,
     dlswDirNBStatus,
      dlswDirNBLFSize,
     dlswDirNBRowStatus
     }
  STATUS current
  DESCRIPTION
    "Conformance group for DLSw directory using NetBIOS
    names."
  ::= { dlswGroups 11 }

-- ..................................................................
dlswDirLocateGroup  OBJECT-GROUP
  OBJECTS  {
     dlswDirLocateMacLocation
     }
  STATUS current
  DESCRIPTION
    "Conformance group for a node that can return directory
    entry order for a given MAC address."
  ::= { dlswGroups 12 }

-- ..................................................................
dlswDirLocateNBGroup  OBJECT-GROUP
  OBJECTS  {
     dlswDirLocateNBLocation
     }
  STATUS current
  DESCRIPTION
    "Conformance group for a node that can return directory
    entry order for a given NetBIOS name."
  ::= { dlswGroups 13 }

-- ..................................................................
dlswCircuitStatGroup  OBJECT-GROUP
  OBJECTS  {
```

```
      dlswCircuitStatActives,
       dlswCircuitStatCreates
      }
  STATUS current
  DESCRIPTION
    "Conformance group for statistics about circuits."
  ::= { dlswGroups 14 }

-- ..........................................................
dlswCircuitGroup  OBJECT-GROUP
  OBJECTS  {
      dlswCircuitS1IfIndex,
      dlswCircuitS1DlcType,
      dlswCircuitS1RouteInfo,
      dlswCircuitS1CircuitId,
      dlswCircuitS1Dlc,
      dlswCircuitS2Location,
      dlswCircuitS2TDomain,
      dlswCircuitS2TAddress,
      dlswCircuitS2CircuitId,
      dlswCircuitOrigin,
      dlswCircuitEntryTime,
      dlswCircuitStateTime,
      dlswCircuitState,
      dlswCircuitPriority,
      dlswCircuitFCSendGrantedUnits,
      dlswCircuitFCSendCurrentWndw,
      dlswCircuitFCRecvGrantedUnits,
      dlswCircuitFCRecvCurrentWndw,
      dlswCircuitFCLargestRecvGranted,
      dlswCircuitFCLargestSendGranted,
      dlswCircuitFCHalveWndwSents,
      dlswCircuitFCResetOpSents,
       dlswCircuitFCHalveWndwRcvds,
      dlswCircuitFCResetOpRcvds,
      dlswCircuitDiscReasonLocal,
      dlswCircuitDiscReasonRemote,
      dlswCircuitDiscReasonRemoteData
      }
  STATUS current
  DESCRIPTION
    "Conformance group for DLSw circuits."
  ::= { dlswGroups 15 }

-- ..........................................................
dlswSdlcGroup  OBJECT-GROUP
  OBJECTS  {
      dlswSdlcLsEntries,
```

```
      dlswSdlcLsLocalMac,
      dlswSdlcLsLocalSap,
      dlswSdlcLsLocalIdBlock,
      dlswSdlcLsLocalIdNum,
      dlswSdlcLsRemoteMac,
      dlswSdlcLsRemoteSap,
      dlswSdlcLsRowStatus
      }
  STATUS current
  DESCRIPTION
    "Conformance group for DLSw SDLC support."
  ::= { dlswGroups 16 }

-- ..........................................................
dlswNotificationGroup  NOTIFICATION-GROUP
  NOTIFICATIONS  {
      dlswTrapTConnPartnerReject,
      dlswTrapTConnProtViolation,

     dlswTrapTConnUp,
      dlswTrapTConnDown,
      dlswTrapCircuitUp,
      dlswTrapCircuitDown
      }
  STATUS current
  DESCRIPTION
    "Conformance group for DLSw notifications."
  ::= { dlswGroups 17 }

END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/DLSW-MIB
No license file was found, but licenses were detected in source scan.

SIP-COMMON-MIB DEFINITIONS ::= BEGIN

IMPORTS
  MODULE-IDENTITY,
  OBJECT-TYPE,
  NOTIFICATION-TYPE,
  Counter32,
  Gauge32,
  TimeTicks,
  Unsigned32,


  mib-2
```

```
        FROM SNMPv2-SMI            -- RFC 2578

    RowStatus,
    TimeStamp,
    TruthValue
        FROM SNMPv2-TC             -- RFC 2579

    MODULE-COMPLIANCE,
    OBJECT-GROUP,
    NOTIFICATION-GROUP
        FROM SNMPv2-CONF           -- RFC 2580

    SnmpAdminString
        FROM SNMP-FRAMEWORK-MIB    -- RFC 3411

    SipTCTransportProtocol,
    SipTCMethodName,
    SipTCEntityRole,
    SipTCOptionTagHeaders
        FROM SIP-TC-MIB            -- RFC 4780

    applIndex
        FROM NETWORK-SERVICES-MIB  -- RFC 2788

    InetPortNumber
        FROM INET-ADDRESS-MIB;     -- RFC 4001

sipCommonMIB MODULE-IDENTITY
    LAST-UPDATED "200704200000Z"
    ORGANIZATION "IETF Session Initiation Protocol Working Group"
    CONTACT-INFO
          "SIP WG email: sip@ietf.org

          Co-editor  Kevin Lingle
                Cisco Systems, Inc.
          postal:    7025 Kit Creek Road
                P.O. Box 14987
                Research Triangle Park, NC 27709
                USA
          email:     klingle@cisco.com
          phone:     +1 919 476 2029

          Co-editor  Joon Maeng
          email:     jmaeng@austin.rr.com

          Co-editor  Jean-Francois Mule
                CableLabs
```

```
            postal:    858 Coal Creek Circle
                       Louisville, CO 80027
                       USA
            email:     jf.mule@cablelabs.com
            phone:     +1 303 661 9100

            Co-editor  Dave Walker
            email:     drwalker@rogers.com"
    DESCRIPTION
      "Session Initiation Protocol (SIP) Common MIB module.  This
       module defines objects that may be common to all SIP entities.

        SIP is an application-layer signaling protocol for creating,
       modifying and terminating multimedia sessions with one or more
       participants.  These sessions include Internet multimedia
       conferences and Internet telephone calls.  SIP is defined in
       RFC 3261 (June 2002).

       This MIB is defined for managing objects that are common to
       SIP User Agents (UAs), Proxy, Redirect, and Registrar servers.
       Objects specific to each of these entities MAY be managed using
       entity specific MIBs defined in other modules.

       Copyright (C) The IETF Trust (2007).  This version of
       this MIB module is part of RFC 4780; see the RFC itself for
       full legal notices."
    REVISION     "200704200000Z"
    DESCRIPTION
       "Initial version of the IETF SIP-COMMON-MIB module.  This
        version published as part of RFC 4780."
     ::= { mib-2 149 }

-- Top-Level Components of this MIB.
sipCommonMIBNotifications OBJECT IDENTIFIER
 ::= { sipCommonMIB 0 }
sipCommonMIBObjects       OBJECT IDENTIFIER ::= { sipCommonMIB 1 }
sipCommonMIBConformance   OBJECT IDENTIFIER ::= { sipCommonMIB 2 }

--
-- This MIB contains objects that are common to all SIP entities.
--

-- Common basic configuration
sipCommonCfgBase       OBJECT IDENTIFIER ::= { sipCommonMIBObjects 1 }

-- Protocol timer configuration
sipCommonCfgTimer      OBJECT IDENTIFIER ::= { sipCommonMIBObjects 2 }
```

```
-- SIP message summary statistics


sipCommonSummaryStats  OBJECT IDENTIFIER ::= { sipCommonMIBObjects 3 }

-- Per method statistics
sipCommonMethodStats   OBJECT IDENTIFIER ::= { sipCommonMIBObjects 4 }

-- Per Status code or status code class statistics
sipCommonStatusCode    OBJECT IDENTIFIER ::= { sipCommonMIBObjects 5 }

-- Transaction statistics
sipCommonStatsTrans    OBJECT IDENTIFIER ::= { sipCommonMIBObjects 6 }

-- Method retry statistics
sipCommonStatsRetry    OBJECT IDENTIFIER ::= { sipCommonMIBObjects 7 }

-- Other statistics
sipCommonOtherStats
   OBJECT IDENTIFIER ::= { sipCommonMIBObjects 8 }

-- Accessible-for-notify objects
sipCommonNotifObjects  OBJECT IDENTIFIER ::= { sipCommonMIBObjects 9 }

--
-- Common Configuration Objects
--
sipCommonCfgTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SipCommonCfgEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains the common configuration objects applicable
     to all SIP entities."
  ::= { sipCommonCfgBase 1 }

sipCommonCfgEntry OBJECT-TYPE
  SYNTAX      SipCommonCfgEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "A row of common configuration.

     Each row represents objects for a particular SIP entity
     instance present in this system.  applIndex is used to uniquely
     identify these instances of SIP entities and correlate them
     through the common framework of the NETWORK-SERVICES-MIB (RFC
```

```
      2788)."
    INDEX { applIndex }
    ::= { sipCommonCfgTable 1
   }

SipCommonCfgEntry ::= SEQUENCE {


      sipCommonCfgProtocolVersion      SnmpAdminString,
      sipCommonCfgServiceOperStatus    INTEGER,
      sipCommonCfgServiceStartTime     TimeTicks,
      sipCommonCfgServiceLastChange    TimeTicks,
      sipCommonCfgOrganization         SnmpAdminString,
      sipCommonCfgMaxTransactions      Unsigned32,
      sipCommonCfgServiceNotifEnable   BITS,
      sipCommonCfgEntityType           SipTCEntityRole
    }

sipCommonCfgProtocolVersion OBJECT-TYPE
    SYNTAX      SnmpAdminString
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "This object will reflect the version of SIP supported by this
       SIP entity.  It will follow the same format as SIP version
       information contained in the SIP messages generated by this SIP
       entity.  For example, entities supporting SIP version 2 will
       return 'SIP/2.0' as dictated by the standard."
    REFERENCE
      "RFC 3261, Section 7.1"
    ::= { sipCommonCfgEntry
   1 }

sipCommonCfgServiceOperStatus OBJECT-TYPE
    SYNTAX      INTEGER {
                  unknown(1),
                  up(2),
                  down(3),
                  congested(4),
                  restarting(5),
                  quiescing(6),
                  testing(7)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "This object contains the current operational state of
       the SIP application.
```

unknown : The operational status cannot be determined
for some reason.
up : The application is operating normally and is
processing (receiving and possibly issuing) SIP
requests and responses.
down : The application is currently unable to process
SIP messages.
congested : The application is operational but no additional

inbound transactions can be accommodated at the
moment.
restarting : The application is currently unavailable, but it
is in the process of restarting and will
presumably, soon be able to process SIP messages.
quiescing : The application is currently operational
but has been administratively put into
quiescence mode. Additional inbound
transactions MAY be rejected.
testing : The application is currently in test mode
and MAY not be able to process SIP messages.

The operational status values defined for this object are not
based on any specific information contained in the SIP
standard."
::= { sipCommonCfgEntry 2 }

sipCommonCfgServiceStartTime OBJECT-TYPE
SYNTAX TimeTicks
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime at the time the SIP entity was last
started. If
started prior to the last re-initialization of the
local network management subsystem, then this object contains a
zero value."
::= { sipCommonCfgEntry 3 }

sipCommonCfgServiceLastChange OBJECT-TYPE
SYNTAX TimeTicks
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime at the time the SIP entity entered its
current operational state. If the current state was entered

```
      prior to the last re-initialization of the local network
      management subsystem, then this object contains a zero value."
   ::= { sipCommonCfgEntry 4 }

sipCommonCfgOrganization OBJECT-TYPE
   SYNTAX      SnmpAdminString
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
     "This object contains the organization name that the SIP entity
      inserts into Organization headers of SIP messages processed by
      this system.  If the string is empty, no Organization header is
      to be generated."




   REFERENCE
     "RFC 3261, Section 20.25"
   ::= { sipCommonCfgEntry 5 }

sipCommonCfgMaxTransactions OBJECT-TYPE
   SYNTAX      Unsigned32 (1..4294967295)
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
     "This object indicates the maximum number of simultaneous
      transactions per second that the SIP entity can manage.  In
      general, the value of this object SHOULD reflect a level of
      transaction processing per second that is considered high
      enough to impact the system's CPU and/or memory resources to
      the point of deteriorating SIP call processing but not high
      enough to cause catastrophic system failure."
   ::= { sipCommonCfgEntry 6 }

sipCommonCfgServiceNotifEnable OBJECT-TYPE
   SYNTAX      BITS {
                 sipCommonServiceColdStart(0),
                 sipCommonServiceWarmStart(1),
                 sipCommonServiceStatusChanged(2)
               }
   MAX-ACCESS  read-write
   STATUS      current
    DESCRIPTION
     "This object specifies which SIP service related notifications
      are enabled.  Each bit represents a specific notification.  If
      a bit has a value 1, the associated notification is enabled and
      will be generated by the SIP entity at the appropriate time.
```

```
      Support for these notifications is OPTIONAL: either none or all
      notification values are supported.  If an implementation does
      not support this object, it should return a 'noSuchObject'
      exception to an SNMP GET operation.  If notifications are
      supported, this object's default value SHOULD reflect
      sipCommonServiceColdStart and sipCommonServiceWarmStart enabled
      and sipCommonServiceStatusChanged disabled.

      This object value SHOULD persist across reboots."
   DEFVAL { { sipCommonServiceColdStart,
              sipCommonServiceWarmStart } }
   ::= { sipCommonCfgEntry 7 }

sipCommonCfgEntityType OBJECT-TYPE
   SYNTAX      SipTCEntityRole
    MAX-ACCESS  read-only



   STATUS      current
   DESCRIPTION
     "This object identifies the list of SIP entities to which this
      row is related.  It is defined as a bit map.  Each bit
      represents a type of SIP entity.  If a bit has value 1, the
      SIP entity represented by this row plays the role of this
      entity type.  If a bit has value 0, the SIP entity represented
      by this row does not act as this entity type.  Combinations
      of bits can be set when the SIP entity plays multiple SIP
      roles."
   ::= { sipCommonCfgEntry 8 }

--
-- Support for multiple ports
--
sipCommonPortTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF SipCommonPortEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
     "This table contains the list of ports that each SIP entity in
      this system is allowed to use.  These ports can be advertised
      using the Contact header in a REGISTER request or response."
   ::= {
 sipCommonCfgBase 2 }

sipCommonPortEntry OBJECT-TYPE
   SYNTAX      SipCommonPortEntry
```

```
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "Specification of a particular port.

     Each row represents those objects for a particular SIP entity
     present in this system.  applIndex is used to uniquely identify
     these instances of SIP entities and correlate them through
     the common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
  INDEX { applIndex, sipCommonPort }
  ::= { sipCommonPortTable 1 }

SipCommonPortEntry ::= SEQUENCE {
     sipCommonPort               InetPortNumber,
     sipCommonPortTransportRcv   SipTCTransportProtocol
  }

sipCommonPort OBJECT-TYPE
  SYNTAX      InetPortNumber (1..65535)
  MAX-ACCESS  not-accessible
  STATUS      current



  DESCRIPTION
    "This object reflects a particular port that can be used by the
     SIP application."
  ::= { sipCommonPortEntry 1 }

sipCommonPortTransportRcv
 OBJECT-TYPE
  SYNTAX      SipTCTransportProtocol
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object will specify the transport protocol the SIP entity
     will use to receive SIP messages.

     This object is a bit map.  Each bit represents a transport
     protocol.  If a bit has value 1, then that transport protocol
     is currently being used.  If a bit has value 0, then that
     transport protocol is currently not being used."
  ::= { sipCommonPortEntry 2 }

--
-- Support for SIP option tags (SIP extensions).
-- SIP extensions MAY be supported or required by SIP entities.
--
```

```
sipCommonOptionTagTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SipCommonOptionTagEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains a list of the SIP option tags (SIP
     extensions) that are either required, supported, or
     unsupported by the SIP entity.  These option tags are
      used in the Require, Proxy-Require, Supported, and
     Unsupported header fields.

     Example: If a user agent client supports, and requires the
     server to support, reliability of provisional responses
     (RFC 3262), this table contains a row with the option tag string
     '100rel' in sipCommonOptionTag and the OCTET STRING value of
     '1010 0000' or '0xA0' in sipCommonOptionTagHeaderField.

     If a server does not support the required feature (indicated in
     a Require header to a UAS, or in a Proxy-Require to a Proxy
     Server), the server returns a 420 Bad Extension listing the
     feature in an Unsupported header.

     Normally, the list of such features supported by an entity is
     static (i.e., will not change over time)."



  REFERENCE
    "RFC 3261, Sections 19.2, 20.32, 20.29, 20.37, and 20.40"
  ::= { sipCommonCfgBase 3 }

sipCommonOptionTagEntry OBJECT-TYPE
  SYNTAX      SipCommonOptionTagEntry
  MAX-ACCESS
 not-accessible
  STATUS      current
  DESCRIPTION
    "A particular SIP option tag (extension) supported or
     unsupported by the SIP entity, and which may be supported or
     required by a peer.

     Each row represents those objects for a particular SIP entity
     present in this system.  applIndex is used to uniquely identify
     these instances of SIP entities and correlate them through the
     common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
  INDEX { applIndex, sipCommonOptionTagIndex }
  ::= { sipCommonOptionTagTable 1 }
```

```
SipCommonOptionTagEntry ::= SEQUENCE {
      sipCommonOptionTagIndex       Unsigned32,
      sipCommonOptionTag            SnmpAdminString,
      sipCommonOptionTagHeaderField  SipTCOptionTagHeaders
   }

sipCommonOptionTagIndex OBJECT-TYPE
   SYNTAX      Unsigned32 (1..4294967295)
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "This object uniquely identifies a conceptual
 row in the table."
   ::= { sipCommonOptionTagEntry 1 }

sipCommonOptionTag OBJECT-TYPE
   SYNTAX      SnmpAdminString
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "This object indicates the SIP option tag.  The option tag names
      are registered with IANA and available at http://www.iana.org."
   REFERENCE "RFC 3261, Section 27.1"
   ::= { sipCommonOptionTagEntry 2 }

sipCommonOptionTagHeaderField OBJECT-TYPE
   SYNTAX      SipTCOptionTagHeaders
   MAX-ACCESS  read-only
   STATUS      current



   DESCRIPTION
      "This object indicates whether the SIP option tag is supported
       (Supported header), unsupported (Unsupported header), or
       required (Require or Proxy-Require header) by the SIP entity.
       A SIP option tag may be both supported and required."
   ::= { sipCommonOptionTagEntry 3 }

--
-- Supported SIP Methods
--
sipCommonMethodSupportedTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF SipCommonMethodSupportedEntry
    MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
```

```
      "This table contains a list of methods supported by each SIP
       entity in this system (see the standard set of SIP methods in
       Section 7.1 of RFC 3261).  Any additional methods that may be
       incorporated into the SIP protocol can be represented by this
       table without any requirement to update this MIB module.

       The table is informational in nature and conveys capabilities
       of the managed system to the SNMP Manager.

       From a protocol point of view, the list of methods advertised
       by the SIP entity in the Allow header (Section 20.5 of RFC
       3261) MUST be consistent with the methods reflected in this
       table."
::= { sipCommonCfgBase 4 }

sipCommonMethodSupportedEntry OBJECT-TYPE
  SYNTAX      SipCommonMethodSupportedEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "A particular method supported by the SIP entity.

     Each row represents those objects for a particular SIP entity
     present in this system.  applIndex is used to uniquely identify
     these instances of SIP entities and correlate them through
     the common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
  INDEX { applIndex, sipCommonMethodSupportedIndex }
  ::= { sipCommonMethodSupportedTable 1 }

SipCommonMethodSupportedEntry ::= SEQUENCE {
     sipCommonMethodSupportedIndex     Unsigned32,
     sipCommonMethodSupportedName      SipTCMethodName
  }



sipCommonMethodSupportedIndex OBJECT-TYPE
  SYNTAX      Unsigned32 (1..4294967295)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This object uniquely identifies a conceptual row in the table
     and reflects an assigned number used to identify a specific
     SIP method.

     This identifier is suitable for referencing the associated
     method throughout this and other MIBs supported by this managed
```

```
        system."
    ::= { sipCommonMethodSupportedEntry 1 }

sipCommonMethodSupportedName OBJECT-TYPE
    SYNTAX      SipTCMethodName
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "This object reflects the supported method's name.  The method
        name MUST be all upper case (e.g., 'INVITE')."
::= { sipCommonMethodSupportedEntry 2 }

--
-- SIP Timer Configuration
--
sipCommonCfgTimerTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF SipCommonCfgTimerEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "This table contains timer configuration objects applicable to
        SIP user agent and SIP stateful Proxy Server entities."
    ::= { sipCommonCfgTimer 1 }

sipCommonCfgTimerEntry OBJECT-TYPE
    SYNTAX      SipCommonCfgTimerEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A row of timer configuration.

        Each row represents those objects for a particular SIP entity
        present
 in this system.  applIndex is used to uniquely identify
        these instances of SIP entities and correlate them through
        the common framework of the NETWORK-SERVICES-MIB (RFC 2788).
        The objects in this table entry SHOULD be non-volatile and
        their value SHOULD be kept at reboot."



    INDEX { applIndex }
    ::= { sipCommonCfgTimerTable 1 }

SipCommonCfgTimerEntry ::= SEQUENCE {
        sipCommonCfgTimerA              Unsigned32,
        sipCommonCfgTimerB              Unsigned32,
        sipCommonCfgTimerC              Unsigned32,
```

```
      sipCommonCfgTimerD            Unsigned32,
      sipCommonCfgTimerE            Unsigned32,
      sipCommonCfgTimerF            Unsigned32,
      sipCommonCfgTimerG            Unsigned32,
      sipCommonCfgTimerH            Unsigned32,
      sipCommonCfgTimerI            Unsigned32,
      sipCommonCfgTimerJ            Unsigned32,
      sipCommonCfgTimerK            Unsigned32,

   sipCommonCfgTimerT1           Unsigned32,
      sipCommonCfgTimerT2           Unsigned32,
      sipCommonCfgTimerT4           Unsigned32
   }

sipCommonCfgTimerA OBJECT-TYPE
   SYNTAX      Unsigned32 (100..1000)
   UNITS       "milliseconds"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
     "This object reflects the initial value for the retransmit timer
      for the INVITE method.  The retransmit timer doubles after each
      retransmission, ensuring an exponential backoff in network
      traffic.  This object represents the initial time a SIP entity
      will wait to receive a provisional response to an INVITE before
      resending the INVITE request."
   REFERENCE
     "RFC 3261, Section 17.1.1.2"
   DEFVAL { 500 }
   ::= { sipCommonCfgTimerEntry 1 }

sipCommonCfgTimerB OBJECT-TYPE
   SYNTAX      Unsigned32 (32000..300000)
   UNITS       "milliseconds"
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION

   "This object reflects the maximum time a SIP entity will wait to
      receive a final response to an INVITE.  The timer is started
      upon transmission of the initial INVITE request."
   REFERENCE
     "RFC 3261, Section 17.1.1.2"



   DEFVAL { 32000 }
::= { sipCommonCfgTimerEntry 2 }
```

```
sipCommonCfgTimerC OBJECT-TYPE
  SYNTAX      Unsigned32 (180000..300000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the maximum time a SIP Proxy Server will
     wait to receive a provisional response to an INVITE.  The Timer
     C MUST be set for each client transaction when an INVITE
     request is proxied."
  REFERENCE
    "RFC 3261, Section 16.6"
  DEFVAL { 180000 }
  ::= { sipCommonCfgTimerEntry 3 }

sipCommonCfgTimerD OBJECT-TYPE
  SYNTAX      Unsigned32 (0..300000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object
 reflects the amount of time that the server
     transaction can remain in the 'Completed' state when unreliable
     transports are used.  The default value MUST be equal to or
     greater than 32000 for UDP transport, and its value MUST be 0
     for TCP/SCTP transport."
  REFERENCE
    "RFC 3261, Section 17.1.1.2"
  DEFVAL { 32000 }
  ::= { sipCommonCfgTimerEntry 4 }

sipCommonCfgTimerE OBJECT-TYPE
  SYNTAX      Unsigned32 (100..1000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the initial value for the retransmit timer
     for a non-INVITE method while in 'Trying' state.  The
     retransmit timer doubles after each retransmission until it
     reaches T2 to ensure an exponential backoff in network traffic.
     This object represents the initial time a SIP entity will wait
     to receive a provisional response to the request before
     resending the non-INVITE
 request."
  REFERENCE
```

```
    "RFC 3261, Section 17.1.2.2"
  DEFVAL { 500 }
  ::= { sipCommonCfgTimerEntry 5 }

sipCommonCfgTimerF  OBJECT-TYPE
  SYNTAX      Unsigned32 (32000..300000)
  UNITS      "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the maximum time a SIP entity will wait to
     receive a final response to a non-INVITE request.  The timer is
     started upon transmission of the initial request."
  REFERENCE
    "RFC 3261, Section 17.1.2.2"
  DEFVAL { 32000 }

  ::= { sipCommonCfgTimerEntry 6 }

sipCommonCfgTimerG  OBJECT-TYPE
  SYNTAX      Unsigned32 (0..1000)
  UNITS      "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the initial value for the retransmit timer
     for final responses to INVITE requests.  If timer G fires, the
     response is passed to the transport layer again for
     retransmission,
 and timer G is set to fire in MIN(2*T1, T2)
     seconds.  From then on, when timer G fires, the response is
     passed to the transport again for transmission, and timer G is
     reset with a value that doubles, unless that value exceeds T2,
     in which case, it is reset with the value of T2.  The default
     value MUST be T1 for UDP transport, and its value MUST be 0 for
     reliable transport like TCP/SCTP."
  REFERENCE
    "RFC 3261, Section 17.2.1"
  DEFVAL { 500 }
  ::= { sipCommonCfgTimerEntry 7 }

sipCommonCfgTimerH  OBJECT-TYPE
  SYNTAX      Unsigned32 (32000..300000)
  UNITS      "milliseconds"
  MAX-ACCESS  read-only
```

```
    STATUS      current
    DESCRIPTION
      "This object reflects the maximum time a server will wait to
       receive an ACK before it abandons retransmitting the response.



       The timer is started upon entering the 'Completed' state."
    REFERENCE
      "RFC 3261, Section 17.2.1"
    DEFVAL { 32000 }
    ::=
  { sipCommonCfgTimerEntry 8 }

sipCommonCfgTimerI  OBJECT-TYPE
    SYNTAX      Unsigned32 (0..10000)
    UNITS       "milliseconds"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "This object reflects the maximum time a SIP entity will wait to
       receive additional ACK message retransmissions.

       The timer is started upon entering the 'Confirmed' state.  The
       default value MUST be T4 for UDP transport and its value MUST
       be 0 for reliable transport like TCP/SCTP."
    REFERENCE
      "RFC 3261, Section 17.2.1"
    DEFVAL { 5000 }
    ::= { sipCommonCfgTimerEntry 9 }

sipCommonCfgTimerJ  OBJECT-TYPE
    SYNTAX      Unsigned32 (32000..300000)
    UNITS       "milliseconds"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "This object reflects the maximum time a SIP server will wait to
       receive retransmissions of non-INVITE requests.  The timer is
       started upon entering the 'Completed' state for non-INVITE
        transactions.  When timer J fires, the server MUST transition to
       the 'Terminated' state."
    REFERENCE
      "RFC 3261, Section 17.2.2"
    DEFVAL { 32000 }
    ::= { sipCommonCfgTimerEntry 10 }

sipCommonCfgTimerK  OBJECT-TYPE
```

```
  SYNTAX      Unsigned32 (0..10000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the maximum time a SIP client will wait to
     receive retransmissions of responses to non-INVITE requests.
     The timer is started upon entering the 'Completed' state for



     non-INVITE transactions.  When timer K fires, the server MUST
     transition to the 'Terminated' state.  The default value MUST
     be T4 for UDP transport, and its value MUST be 0 for reliable
     transport like TCP/SCTP."
  REFERENCE
    "RFC 3261, Section 17.1.2.2"
  DEFVAL { 5000 }
  ::= { sipCommonCfgTimerEntry 11 }

sipCommonCfgTimerT1  OBJECT-TYPE
  SYNTAX
 Unsigned32 (200..10000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the T1 timer for a SIP entity.  T1 is an
     estimate of the round-trip time (RTT) between the client and
     server transactions."
  REFERENCE
    "RFC 3261, Section 17"
  DEFVAL { 500 }
  ::= { sipCommonCfgTimerEntry 12 }

sipCommonCfgTimerT2  OBJECT-TYPE
  SYNTAX      Unsigned32 (200..10000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the T2 timer for a SIP entity.  T2 is the
     maximum retransmit interval for non-INVITE requests and INVITE
     responses.  It's used in various parts of the protocol to reset
     other Timer* objects to this value."
  REFERENCE
    "RFC 3261, Section 17"
  DEFVAL { 4000 }
```

```
  ::= { sipCommonCfgTimerEntry 13 }

sipCommonCfgTimerT4  OBJECT-TYPE
  SYNTAX      Unsigned32 (200..10000)
  UNITS
    "milliseconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the T4 timer for a SIP entity.  T4 is the
     maximum duration a message will remain in the network.  It
     represents the amount of time the network will take to clear
     messages between client and server transactions.  It's used in



     various parts of the protocol to reset other Timer* objects to
     this value."
  REFERENCE
    "RFC 3261, Section 17"
  DEFVAL { 5000 }
  ::= { sipCommonCfgTimerEntry 14 }

--
-- Common Statistics Objects
--

--
-- Summary Statistics
--
sipCommonSummaryStatsTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SipCommonSummaryStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains the summary statistics objects applicable
     to all SIP entities.  Each row represents those objects for a
     particular SIP entity present in this system."
  ::= {
 sipCommonSummaryStats 1 }

sipCommonSummaryStatsEntry OBJECT-TYPE
  SYNTAX      SipCommonSummaryStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "A row of summary statistics.
```

```
      Each row represents those objects for a particular SIP entity
      present in this system.  applIndex is used to uniquely identify
      these instances of SIP entities and correlate them through
      the common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
    INDEX { applIndex }
    ::= { sipCommonSummaryStatsTable 1 }

SipCommonSummaryStatsEntry ::= SEQUENCE {
      sipCommonSummaryInRequests         Counter32,
      sipCommonSummaryOutRequests        Counter32,
      sipCommonSummaryInResponses        Counter32,
      sipCommonSummaryOutResponses       Counter32,
      sipCommonSummaryTotalTransactions  Counter32,
      sipCommonSummaryDisconTime         TimeStamp
    }

sipCommonSummaryInRequests OBJECT-TYPE



    SYNTAX      Counter32
     MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "This object indicates the total number of SIP request messages
      received by the SIP entity, including retransmissions.

      Discontinuities in the value of this counter can occur at
      re-initialization of the SIP entity or service.  A Management
      Station can detect discontinuities in this counter by
      monitoring the sipCommonSummaryDisconTime object in the same
      row."
    ::= { sipCommonSummaryStatsEntry 1 }

sipCommonSummaryOutRequests OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "This object contains the total number of SIP request messages
      sent out (originated and relayed) by the SIP entity.  Where a
      particular message is sent more than once, for example as a
      retransmission or as a result of forking, each transmission is
      counted separately.

      Discontinuities in the value
 of this counter can occur at
      re-initialization of the SIP entity or service.  A Management
```

Station can detect discontinuities in this counter by
monitoring the sipCommonSummaryDisconTime object in the same
row."
::= { sipCommonSummaryStatsEntry 2 }

sipCommonSummaryInResponses OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This object contains the total number of SIP response messages
received by the SIP entity, including retransmissions.

Discontinuities in the value of this counter can occur at
re-initialization of the SIP entity or service. A Management
Station can detect discontinuities in this counter by
monitoring the sipCommonSummaryDisconTime object in the same
row."
::= { sipCommonSummaryStatsEntry 3 }

sipCommonSummaryOutResponses OBJECT-TYPE

SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This object contains the total number of SIP response messages
sent (originated and relayed) by the SIP entity including
retransmissions.

Discontinuities in the value of this counter can occur at
re-initialization of the SIP entity or service. A Management
Station can detect discontinuities in this counter by
monitoring the sipCommonSummaryDisconTime object in the same
row."
::= { sipCommonSummaryStatsEntry 4 }

sipCommonSummaryTotalTransactions OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This object contains a count of the number of transactions that
are in progress and transactions that have reached the
'Terminated' state. It is not applicable to stateless SIP Proxy
Servers.

A SIP transaction occurs between a client and a server, and
comprises all messages from the first request sent from the
client to the server, up to a final (non-1xx) response sent
from the server to the client.

If the request is INVITE and the final response is a non-2xx,
the transaction also include an ACK to the response. The ACK
for a 2xx response to an INVITE request is a separate
transaction.

The branch ID parameter in the Via header field values serves
as a transaction identifier.

A transaction is identified by the CSeq sequence number within
a single call leg. The ACK request has the same CSeq number as
the corresponding INVITE request, but comprises a transaction
of its own.

In the case of a forked request, each branch counts as a single
transaction.

For a transaction stateless Proxy Server, this counter is
always 0.

Discontinuities in the value of this counter can occur at
re-initialization of the SIP entity or service. A Management

Station can detect discontinuities in this counter by
monitoring the sipCommonSummaryDisconTime object in the same
row."
::= { sipCommonSummaryStatsEntry 5 }

sipCommonSummaryDisconTime OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of the sysUpTime object when the counters for the
summary statistics objects in this row last experienced a
discontinuity."
::= { sipCommonSummaryStatsEntry 6 }

--
-- SIP Method Statistics
-- Total counts for each SIP method.

```
--
sipCommonMethodStatsTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SipCommonMethodStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains the method statistics objects for SIP
     entities.  Each row represents those objects for a particular
     SIP entity present in this system."
  ::= { sipCommonMethodStats 1 }

sipCommonMethodStatsEntry OBJECT-TYPE

  SYNTAX      SipCommonMethodStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "A row of per entity method statistics.

     Each row represents those objects for a particular SIP entity
     present in this system.  applIndex is used to uniquely identify
     these instances of SIP entities and correlate them through
     the common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
  INDEX { applIndex, sipCommonMethodStatsName }
  ::= { sipCommonMethodStatsTable 1 }

SipCommonMethodStatsEntry ::= SEQUENCE {
      sipCommonMethodStatsName   SipTCMethodName,
      sipCommonMethodStatsOutbounds    Counter32,




      sipCommonMethodStatsInbounds     Counter32,
      sipCommonMethodStatsDisconTime   TimeStamp

  }

sipCommonMethodStatsName OBJECT-TYPE
  SYNTAX      SipTCMethodName
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This object uniquely identifies the SIP method related to the

     objects in a particular row."
  ::= { sipCommonMethodStatsEntry 1 }

sipCommonMethodStatsOutbounds OBJECT-TYPE
```

```
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the total number of requests sent by the
     SIP entity, excluding retransmissions.  Retransmissions are
     counted separately and are not reflected in this counter.  A
     Management Station can detect discontinuities in this counter
     by monitoring the sipCommonMethodStatsDisconTime object in the
     same row."
  REFERENCE
    "RFC 3261, Section 7.1"
  ::= { sipCommonMethodStatsEntry 2 }

sipCommonMethodStatsInbounds OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the total number of requests received by
     the SIP entity.  Retransmissions are counted separately and are
     not reflected in this counter.  A Management Station
 can detect
     discontinuities in this counter by monitoring the
     sipCommonMethodStatsDisconTime object in the same row."
  REFERENCE
    "RFC 3261, Section 7.1"
  ::= { sipCommonMethodStatsEntry 3 }

sipCommonMethodStatsDisconTime  OBJECT-TYPE
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION




    "The value of the sysUpTime object when the counters for the
     method statistics objects in this row last experienced a
     discontinuity."
  ::= { sipCommonMethodStatsEntry 4 }

--
-- Support for specific status codes
--
sipCommonStatusCodeTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SipCommonStatusCodeEntry
  MAX-ACCESS  not-accessible
```

```
  STATUS      current
  DESCRIPTION
     "This table contains the list of SIP status codes that each SIP
      entity in this system has been requested to monitor.  It is the
      mechanism by which specific status codes are monitored.
      Entries created in this table
 must not persist across reboots."
  ::= { sipCommonStatusCode 1 }

sipCommonStatusCodeEntry OBJECT-TYPE
  SYNTAX      SipCommonStatusCodeEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "This row contains information on a particular SIP status code
      that the SIP entity has been requested to monitor.  Entries
      created in this table must not persist across reboots.

      Each row represents those objects for a particular SIP entity
      present in this system.  applIndex is used to uniquely identify
      these instances of SIP entities and correlate them through
      the common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
  INDEX { applIndex, sipCommonStatusCodeMethod,
          sipCommonStatusCodeValue }
  ::= { sipCommonStatusCodeTable 1 }

SipCommonStatusCodeEntry ::= SEQUENCE {
      sipCommonStatusCodeMethod     SipTCMethodName,
      sipCommonStatusCodeValue      Unsigned32,
      sipCommonStatusCodeIns
       Counter32,
      sipCommonStatusCodeOuts       Counter32,
      sipCommonStatusCodeRowStatus  RowStatus,
      sipCommonStatusCodeDisconTime TimeStamp
  }

sipCommonStatusCodeMethod OBJECT-TYPE
  SYNTAX      SipTCMethodName
  MAX-ACCESS  not-accessible



  STATUS      current
  DESCRIPTION
     "This object uniquely identifies a conceptual row in the
      table."
  ::= { sipCommonStatusCodeEntry 1 }
```

```
sipCommonStatusCodeValue OBJECT-TYPE
  SYNTAX      Unsigned32 (100..999)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This object contains a SIP status code value that the SIP
     entity has been requested to monitor.  All of the other
     information in the row is related to this value."
  ::= { sipCommonStatusCodeEntry 2 }

sipCommonStatusCodeIns OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the total number of response
 messages
     received by the SIP entity with the status code value contained
     in the sipCommonStatusCodeValue column.

     Discontinuities in the value of this counter can occur at
     re-initialization of the SIP entity or service, or when the
     monitoring of the status code is temporarily disabled.  A
     Management Station can detect discontinuities in this counter
     by monitoring the sipCommonStatusCodeDisconTime object in the
     same row."
  ::= { sipCommonStatusCodeEntry 3 }

sipCommonStatusCodeOuts OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the total number of response messages sent
     by the SIP entity with the status code value contained in the
     sipCommonStatusCodeValue column.

     Discontinuities in the value of this counter can occur at
     re-initialization of the SIP entity or service, or when the
     monitoring of
 the Status code is temporarily disabled.  A
     Management Station can detect discontinuities in this counter
     by monitoring the sipCommonStatusCodeDisconTime object in the
     same row."



  ::= { sipCommonStatusCodeEntry 4 }
```

```
sipCommonStatusCodeRowStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
    "The row augmentation in sipCommonStatusCodeNotifTable will be
     governed by the value of this RowStatus.

     The values 'createAndGo' and 'destroy' are the only valid
     values allowed for this object.  If a row exists, it will
     reflect a status of 'active' when queried."
  ::= { sipCommonStatusCodeEntry 5 }

sipCommonStatusCodeDisconTime  OBJECT-TYPE
  SYNTAX TimeStamp
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The value of the sysUpTime object when the counters for the
     status code statistics objects in this row last experienced
     a discontinuity."
   ::= { sipCommonStatusCodeEntry 6 }

--
-- Support for specific status code notifications
--

sipCommonStatusCodeNotifTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SipCommonStatusCodeNotifEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains objects to control notifications related to
     particular status codes that each SIP entity in this system has
     been requested to monitor.

     There is an entry in this table corresponding to each entry in
     sipCommonStatusCodeTable.  Therefore, this table augments
     sipCommonStatusCodeTable and utilizes the same index
     methodology.

     The objects in this table are not included directly in the
     sipCommonStatusCodeTable simply to keep the status code
     notification control objects separate from the actual status
     code statistics."
  ::= { sipCommonStatusCode 2 }
```

```
sipCommonStatusCodeNotifEntry OBJECT-TYPE
  SYNTAX
 SipCommonStatusCodeNotifEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This row contains information controlling notifications for a
     particular SIP status code that the SIP entity has been
     requested to monitor."
  AUGMENTS { sipCommonStatusCodeEntry }
  ::= { sipCommonStatusCodeNotifTable 1 }

SipCommonStatusCodeNotifEntry ::= SEQUENCE {
      sipCommonStatusCodeNotifSend         TruthValue,
      sipCommonStatusCodeNotifEmitMode     INTEGER,
      sipCommonStatusCodeNotifThresh       Unsigned32,
      sipCommonStatusCodeNotifInterval     Unsigned32
  }

sipCommonStatusCodeNotifSend OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "This object controls whether a sipCommonStatusCodeNotif is
     emitted when the status code value specified by
     sipCommonStatusCodeValue is sent or received.  If the value of
     this object is 'true', then a notification
 is sent.  If it is
     'false', no notification is sent.
     Note well that a notification MAY be emitted for every message
     sent or received that contains the particular status code.
     Depending on the status code involved, this can cause a
     significant number of notification emissions that could be
     detrimental to network performance.  Managers are forewarned to
     be prudent in the use of this object to enable notifications.
     Look to sipCommonStatusCodeNotifEmitMode for alternative
     controls for sipCommonStatusCodeNotif emissions."
  DEFVAL { false }
  ::= { sipCommonStatusCodeNotifEntry 1 }

sipCommonStatusCodeNotifEmitMode OBJECT-TYPE
  SYNTAX      INTEGER {
                normal(1),
                oneShot(2),
                triggered(3)  -- read-only
```

```
            }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION


       "The object sipCommonStatusCodeNotifSend MUST be set to 'true'
        for the values of this object to have any effect.  It is
        RECOMMENDED that the desired emit mode be established by this
        object prior to setting sipCommonStatusCodeNotifSend to 'true'.
        This object and the sipCommonStatusCodeNotifSend object can
        obviously be set independently, but their respective values
        will have a dependency on each other and the resulting
        notifications.

        This object specifies the mode for emissions of
        sipCommonStatusCodeNotif notifications.

        normal    : sipCommonStatusCodeNotif notifications will be
                    emitted by the system for each SIP response
                    message sent or received that contains the
                    desired status code.

        oneShot   : Only one sipCommonStatusCodeNotif notification
                    will be emitted.  It will be the next SIP response
                    message sent or received that contains the
                    desired
    status code.

                    No more notifications are emitted until this
                    object is set to 'oneShot' again or set to
                    'normal'.  This option is provided as a means of
                    quelling the potential promiscuous behavior that
                    can be associated with the
                    sipCommonStatusCodeNotif.

        triggered : This value is only readable and cannot be set.  It
                    reflects that the 'oneShot' case has occurred,
                    and indicates that the mode needs to be reset to
                    get further notifications.  The mode is reset by
                    setting this object to 'oneShot' or 'normal'."
    DEFVAL { oneShot }
    ::= { sipCommonStatusCodeNotifEntry 2 }

    sipCommonStatusCodeNotifThresh OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-write
```

```
    STATUS      current
    DESCRIPTION
      "This object specifies the number of response messages sent or

     received by this system that are considered excessive.  Based
      on crossing that threshold, a
      sipCommonStatusCodeThreshExceededInNotif notification or a
      sipCommonStatusCodeThreshExceededOutNotif will be sent.  The
      sipCommonStatusCodeThreshExceededInNotif and




      sipCommonStatusCodeThreshExceededOutNotif notifications can be
      used as an early warning mechanism in lieu of using
      sipCommonStatusCodeNotif.

      Note that the configuration applied by this object will be
      applied equally to inbound and outbound response messages."
    DEFVAL { 500 }
    ::= { sipCommonStatusCodeNotifEntry 3 }

  sipCommonStatusCodeNotifInterval OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "seconds"
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
      "This object specifies the time interval over which, if
      sipCommonStatusCodeThresh is exceeded with respect to sent or
      received messages, a sipCommonStatusCodeThreshExceededInNotif
       or sipCommonStatusCodeThreshExceededOutNotif notification will
      be sent.

      Note that the configuration applied by this object will be
      applied equally to inbound and outbound response messages."
    DEFVAL { 60 }
    ::= { sipCommonStatusCodeNotifEntry 4 }

  --
  -- Transaction Statistics
  --
  sipCommonTransCurrentTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF SipCommonTransCurrentEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
      "This table contains information on the transactions currently
      awaiting definitive responses by each SIP entity in this
```

```
      system.

      This table does not apply to transaction stateless Proxy
      Servers."
  ::= { sipCommonStatsTrans 1 }

sipCommonTransCurrentEntry OBJECT-TYPE
  SYNTAX      SipCommonTransCurrentEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "Information on a particular SIP entity's current transactions.



      Each row represents those objects for a particular SIP entity
      present in this system.  applIndex is used to uniquely identify
      these instances of SIP entities and correlate them through
      the common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
  INDEX { applIndex }
  ::= { sipCommonTransCurrentTable 1 }

SipCommonTransCurrentEntry ::= SEQUENCE {
      sipCommonTransCurrentactions  Gauge32
  }

sipCommonTransCurrentactions OBJECT-TYPE
  SYNTAX      Gauge32 (0..4294967295)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object contains the number of transactions awaiting
      definitive (non-1xx) response.  In the case of a forked
      request, each branch counts as a single transaction
      corresponding to the entity identified by applIndex."
::= { sipCommonTransCurrentEntry 1 }

--
-- SIP Retry Statistics
--
-- This group contains various statistics objects about
-- retransmission counts.
--
sipCommonStatsRetryTable
 OBJECT-TYPE
  SYNTAX      SEQUENCE OF SipCommonStatsRetryEntry
  MAX-ACCESS  not-accessible
  STATUS      current
```

```
  DESCRIPTION
    "This table contains retry statistics objects applicable to each
     SIP entity in this system."
  ::= { sipCommonStatsRetry 1 }

sipCommonStatsRetryEntry OBJECT-TYPE
  SYNTAX      SipCommonStatsRetryEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "A row of retry statistics.

     Each row represents those objects for a particular SIP entity
     present in this system.  applIndex is used to uniquely identify
     these instances of SIP entities and correlate them through the
     common framework of the NETWORK-SERVICES-MIB (RFC 2788)."



  INDEX { applIndex, sipCommonStatsRetryMethod }
  ::= { sipCommonStatsRetryTable 1 }

SipCommonStatsRetryEntry ::= SEQUENCE {
     sipCommonStatsRetryMethod           SipTCMethodName,
     sipCommonStatsRetries
       Counter32,
     sipCommonStatsRetryFinalResponses    Counter32,
     sipCommonStatsRetryNonFinalResponses Counter32,
     sipCommonStatsRetryDisconTime        TimeStamp
  }

sipCommonStatsRetryMethod OBJECT-TYPE
  SYNTAX      SipTCMethodName
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This object uniquely identifies the SIP method related to the
     objects in a row."
  ::= { sipCommonStatsRetryEntry 1 }

sipCommonStatsRetries OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the total number of request
     retransmissions that have been sent by the SIP entity.  Note
     that there could be multiple retransmissions per request.
```

```
      Discontinuities in the value of this counter can occur at
      re-initialization of the SIP entity or service.  A Management
      Station can detect discontinuities in this counter by
      monitoring
 the sipCommonStatsRetryDisconTime object in the same
      row."
  ::= { sipCommonStatsRetryEntry 2 }

sipCommonStatsRetryFinalResponses OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the total number of Final Response retries
     that have been sent by the SIP entity.  Note that there could
     be multiple retransmissions per request.

     Discontinuities in the value of this counter can occur at
     re-initialization of the SIP entity or service.  A Management
     Station can detect discontinuities in this counter by




     monitoring the sipCommonStatsRetryDisconTime object in the same
     row."
  ::= { sipCommonStatsRetryEntry 3 }

sipCommonStatsRetryNonFinalResponses OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "This object reflects the total number of non-Final Response
     retries that
 have been sent by the SIP entity.

     Discontinuities in the value of this counter can occur at
     re-initialization of the SIP entity or service.  A Management
     Station can detect discontinuities in this counter by
     monitoring the sipCommonStatsRetryDisconTime object in the same
     row."
  ::= { sipCommonStatsRetryEntry 4 }

sipCommonStatsRetryDisconTime  OBJECT-TYPE
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
```

```
  DESCRIPTION
     "The value of the sysUpTime object when the counters for the
      retry statistics objects in this row last experienced a
      discontinuity."
  ::= { sipCommonStatsRetryEntry 5 }

--
-- Other Common Statistics
--
sipCommonOtherStatsTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF SipCommonOtherStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "This table contains other common statistics supported by each
      SIP entity in this system."
  ::= {
 sipCommonOtherStats 1 }

sipCommonOtherStatsEntry OBJECT-TYPE
  SYNTAX      SipCommonOtherStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "Information on a particular SIP entity's other common
      statistics.



      Each row represents those objects for a particular SIP entity
      present in this system.  applIndex is used to uniquely identify
      these instances of SIP entities and correlate them through
      the common framework of the NETWORK-SERVICES-MIB (RFC 2788)."
  INDEX { applIndex }
  ::= { sipCommonOtherStatsTable 1 }

SipCommonOtherStatsEntry ::= SEQUENCE {
      sipCommonOtherStatsNumUnsupportedUris     Counter32,
      sipCommonOtherStatsNumUnsupportedMethods  Counter32,
      sipCommonOtherStatsOtherwiseDiscardedMsgs Counter32,
      sipCommonOtherStatsDisconTime   TimeStamp
  }

sipCommonOtherStatsNumUnsupportedUris OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS
```

```
    current
    DESCRIPTION
      "Number of RequestURIs received with an unsupported scheme.
       A server normally responds to such requests with a 400 Bad
       Request status code.

       Discontinuities in the value of this counter can occur at
       re-initialization of the SIP entity or service.  A Management
       Station can detect discontinuities in this counter by
       monitoring the sipCommonOtherStatsDisconTime object in the same
       row."
    ::= { sipCommonOtherStatsEntry 1 }

sipCommonOtherStatsNumUnsupportedMethods OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "Number of SIP requests received with unsupported methods.  A
       server normally responds to such requests with a 501 (Not
       Implemented) or 405 (Method Not Allowed).

       Discontinuities in the value of this counter can occur at
       re-initialization of the SIP entity or service.  A Management
       Station can
   detect discontinuities in this counter by
       monitoring the sipCommonOtherStatsDisconTime object in the same
       row."
    ::= { sipCommonOtherStatsEntry 2 }

sipCommonOtherStatsOtherwiseDiscardedMsgs OBJECT-TYPE
    SYNTAX      Counter32



    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "Number of SIP messages received that, for any number of
       reasons, was discarded without a response.

       Discontinuities in the value of this counter can occur at
       re-initialization of the SIP entity or service.  A Management
       Station can detect discontinuities in this counter by
       monitoring the sipCommonOtherStatsDisconTime object in the same
       row."
    ::= { sipCommonOtherStatsEntry 3 }
```

```
sipCommonOtherStatsDisconTime OBJECT-TYPE
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The value of the sysUpTime object when the counters for the
      statistics objects in this row last
 experienced a
      discontinuity."
  ::= { sipCommonOtherStatsEntry 4 }

--
-- Notification related objects
--

--
-- Status code related notification objects.
--
sipCommonStatusCodeNotifTo OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
     "This object contains the value of the To header in the message
      containing the status code that caused the notification.  The
      header name will be part of this object value.  For example,
      'To: Watson '."
  ::= { sipCommonNotifObjects 1 }

sipCommonStatusCodeNotifFrom OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
     "This object contains the value of the From header in the
      message containing the status code that caused the



      notification.  The header name will be part of this object
      value.  For example, 'From: Watson '."
  ::= { sipCommonNotifObjects
 2 }

sipCommonStatusCodeNotifCallId OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  accessible-for-notify
  STATUS      current
```

```
  DESCRIPTION
    "This object contains the value of the Call-ID in the message
     containing the status code that caused the notification.  The
     header name will be part of this object value.  For example,
     'Call-ID: 5551212@example.com'."
  ::= { sipCommonNotifObjects 3 }

sipCommonStatusCodeNotifCSeq OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
    "This object contains the CSeq value in the message containing
     the status code that caused the notification.  The header name
     will be part of this object value.  For example, 'CSeq: 1722
     INVITE'."
  ::= { sipCommonNotifObjects 4 }

--
-- General notification related objects.
--
sipCommonNotifApplIndex OBJECT-TYPE
  SYNTAX      Unsigned32 (1..2147483647)

 MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
    "This object contains the applIndex as described in RFC 2788.
     This object is created in order to allow a variable binding
     containing a value of applIndex in a notification."
  ::= { sipCommonNotifObjects 5 }

sipCommonNotifSequenceNumber OBJECT-TYPE
  SYNTAX      Unsigned32 (1..2147483647)
  MAX-ACCESS  accessible-for-notify
  STATUS      current
  DESCRIPTION
    "This object contains a sequence number for each notification
     generated by this SIP entity.  Each notification SHOULD have a
     unique sequence number.  A network manager can use this
     information to determine whether notifications from a



     particular SIP entity have been missed.  The value of this
     object MUST start at 1 and increase by 1 with each generated
     notification.  If a system restarts, the sequence number MAY
     start again from 1."
```

```
  ::= { sipCommonNotifObjects
 6 }

--
-- Notifications
--
sipCommonStatusCodeNotif NOTIFICATION-TYPE
  OBJECTS {
    sipCommonNotifSequenceNumber,
    sipCommonNotifApplIndex,
    sipCommonStatusCodeNotifTo,
    sipCommonStatusCodeNotifFrom,
    sipCommonStatusCodeNotifCallId,
    sipCommonStatusCodeNotifCSeq,
    sipCommonStatusCodeIns,
    sipCommonStatusCodeOuts
  }
  STATUS      current
  DESCRIPTION
    "Signifies that a specific status code has been sent or received
     by the system."
  ::= { sipCommonMIBNotifications 1 }

sipCommonStatusCodeThreshExceededInNotif NOTIFICATION-TYPE
  OBJECTS {
    sipCommonNotifSequenceNumber,
    sipCommonNotifApplIndex,
    sipCommonStatusCodeIns
  }
  STATUS      current
  DESCRIPTION
    "Signifies that a specific status code was found to have been
     received by the system frequently enough to exceed the
     configured threshold.  This notification can be used as
     an early warning mechanism
 in lieu of using
     sipCommonStatusCodeNotif."
  ::= { sipCommonMIBNotifications 2 }

sipCommonStatusCodeThreshExceededOutNotif NOTIFICATION-TYPE
  OBJECTS {
    sipCommonNotifSequenceNumber,
    sipCommonNotifApplIndex,
    sipCommonStatusCodeOuts
  }
  STATUS      current
```

```
  DESCRIPTION
    "Signifies that a specific status code was found to have been
     sent by the system enough to exceed the configured threshold.
     This notification can be used as an early warning mechanism in
     lieu of using sipCommonStatusCodeNotif."
  ::= { sipCommonMIBNotifications 3 }

sipCommonServiceColdStart NOTIFICATION-TYPE
  OBJECTS {
    sipCommonNotifSequenceNumber,
    sipCommonNotifApplIndex,
    sipCommonCfgServiceStartTime
  }
  STATUS      current
  DESCRIPTION
    "Signifies that the SIP service has reinitialized itself or
     started for the first time.  This SHOULD result from a hard
     'down' to 'up' administrative status
 change.  The configuration
     or behavior of the service MAY be altered."
  ::= { sipCommonMIBNotifications 4 }

sipCommonServiceWarmStart NOTIFICATION-TYPE
  OBJECTS {
    sipCommonNotifSequenceNumber,
    sipCommonNotifApplIndex,
    sipCommonCfgServiceLastChange
  }
  STATUS      current
  DESCRIPTION
    "Signifies that the SIP service has reinitialized itself and is
     restarting after an administrative 'reset'.  The configuration
     or behavior of the service MAY be altered."
  ::= { sipCommonMIBNotifications 5 }

sipCommonServiceStatusChanged NOTIFICATION-TYPE
  OBJECTS {
    sipCommonNotifSequenceNumber,
    sipCommonNotifApplIndex,
    sipCommonCfgServiceLastChange,
    sipCommonCfgServiceOperStatus
  }
  STATUS      current
  DESCRIPTION
    "Signifies that the SIP service operational status has changed."
  ::= { sipCommonMIBNotifications 6 }
```

```
--
-- Conformance



--
sipCommonMIBCompliances
  OBJECT IDENTIFIER
 ::= { sipCommonMIBConformance 1 }
sipCommonMIBGroups
  OBJECT IDENTIFIER ::= { sipCommonMIBConformance 2 }

--
-- Compliance Statements
--
sipCommonCompliance MODULE-COMPLIANCE
  STATUS      current
  DESCRIPTION
    "The compliance statement for SIP entities."

  MODULE -- this module
     MANDATORY-GROUPS { sipCommonConfigGroup,
                        sipCommonStatsGroup
                      }

  OBJECT       sipCommonStatusCodeRowStatus
  SYNTAX       RowStatus { active(1) }
  WRITE-SYNTAX RowStatus { createAndGo(4), destroy(6) }
  DESCRIPTION
    "Support for createAndWait and notInService is not required."

  OBJECT       sipCommonCfgServiceNotifEnable
  MIN-ACCESS   not-accessible
  DESCRIPTION
    "This object is optional and does not need to be supported."

  GROUP        sipCommonInformationalGroup
  DESCRIPTION
    "This group is OPTIONAL.  A SIP entity can elect to not provide
     any support for these objects, as they
 provide optional
     information."

  GROUP        sipCommonConfigTimerGroup
  DESCRIPTION
    "This group is OPTIONAL.  A SIP entity can elect to not provide
     any timer configuration."
```

```
    GROUP       sipCommonStatsRetryGroup
    DESCRIPTION
      "This group is OPTIONAL.  A SIP entity can elect to not provide
       any retry statistics."

    GROUP       sipCommonNotifGroup
    DESCRIPTION



      "This group is OPTIONAL.  A SIP entity can elect to not provide
       any notifications.  If implemented, the
       sipCommonStatusCodeNotifGroup and sipCommonNotifObjectsGroup
       MUST also be implemented."

    GROUP       sipCommonStatusCodeNotifGroup
    DESCRIPTION
      "This group is OPTIONAL.  A SIP entity can elect to not provide
       any notifications.  If implemented, the sipCommonNotifGroup and
       sipCommonNotifObjectsGroup MUST also be implemented."

    GROUP       sipCommonNotifObjectsGroup
    DESCRIPTION
      "This group is
   OPTIONAL.  A SIP entity can elect to not provide
       any notifications.  If implemented, the
       sipCommonStatusCodeNotifGroup and sipCommonNotifGroup MUST also
       be implemented."

    ::= { sipCommonMIBCompliances 1 }

--
-- Units of Conformance
--
sipCommonConfigGroup OBJECT-GROUP
    OBJECTS {
            sipCommonCfgProtocolVersion,
            sipCommonCfgServiceOperStatus,
            sipCommonCfgServiceStartTime,
            sipCommonCfgServiceLastChange,
            sipCommonPortTransportRcv,
            sipCommonOptionTag,
            sipCommonOptionTagHeaderField,
            sipCommonCfgMaxTransactions,
            sipCommonCfgServiceNotifEnable,
            sipCommonCfgEntityType,
            sipCommonMethodSupportedName
    }
```

```
  STATUS  current
  DESCRIPTION
    "A collection of objects providing configuration common to all
     SIP entities."
  ::= { sipCommonMIBGroups 1 }

sipCommonInformationalGroup OBJECT-GROUP
  OBJECTS {
        sipCommonCfgOrganization
   }
  STATUS  current



  DESCRIPTION
    "A collection of objects providing configuration common to all
     SIP entities."
  ::= { sipCommonMIBGroups 2 }

sipCommonConfigTimerGroup OBJECT-GROUP
  OBJECTS {
        sipCommonCfgTimerA,
        sipCommonCfgTimerB,
        sipCommonCfgTimerC,
        sipCommonCfgTimerD,
        sipCommonCfgTimerE,
        sipCommonCfgTimerF,
        sipCommonCfgTimerG,
        sipCommonCfgTimerH,
        sipCommonCfgTimerI,
        sipCommonCfgTimerJ,
        sipCommonCfgTimerK,
        sipCommonCfgTimerT1,
        sipCommonCfgTimerT2,
        sipCommonCfgTimerT4
  }
  STATUS  current
  DESCRIPTION
    "A collection of objects providing timer configuration common to
     all SIP entities."
  ::= { sipCommonMIBGroups 3 }

sipCommonStatsGroup OBJECT-GROUP
  OBJECTS {
        sipCommonSummaryInRequests,
        sipCommonSummaryOutRequests,
```

```
        sipCommonSummaryInResponses,
        sipCommonSummaryOutResponses,
        sipCommonSummaryTotalTransactions,
        sipCommonSummaryDisconTime,
        sipCommonMethodStatsOutbounds,
        sipCommonMethodStatsInbounds,
        sipCommonMethodStatsDisconTime,
        sipCommonStatusCodeIns,
        sipCommonStatusCodeOuts,
        sipCommonStatusCodeRowStatus,
        sipCommonStatusCodeDisconTime,
        sipCommonTransCurrentactions,
        sipCommonOtherStatsNumUnsupportedUris,
        sipCommonOtherStatsNumUnsupportedMethods,
        sipCommonOtherStatsOtherwiseDiscardedMsgs,
        sipCommonOtherStatsDisconTime



  }
  STATUS  current
  DESCRIPTION
    "A collection of objects providing statistics common to all SIP
     entities."
  ::= { sipCommonMIBGroups 4 }

sipCommonStatsRetryGroup OBJECT-GROUP
  OBJECTS {
         sipCommonStatsRetries,
         sipCommonStatsRetryFinalResponses,
          sipCommonStatsRetryNonFinalResponses,
         sipCommonStatsRetryDisconTime
  }
  STATUS  current
  DESCRIPTION
    "A collection of objects providing retry statistics."
  ::= { sipCommonMIBGroups 5 }

sipCommonNotifGroup NOTIFICATION-GROUP
  NOTIFICATIONS {
         sipCommonStatusCodeNotif,
         sipCommonStatusCodeThreshExceededInNotif,
         sipCommonStatusCodeThreshExceededOutNotif,
         sipCommonServiceColdStart,
         sipCommonServiceWarmStart,
         sipCommonServiceStatusChanged
  }
```

```
  STATUS  current
  DESCRIPTION
    "A collection of notifications common to all SIP entities."
  ::= { sipCommonMIBGroups 6 }

sipCommonStatusCodeNotifGroup OBJECT-GROUP
  OBJECTS {
        sipCommonStatusCodeNotifSend,
        sipCommonStatusCodeNotifEmitMode,
        sipCommonStatusCodeNotifThresh,
        sipCommonStatusCodeNotifInterval
  }
  STATUS  current
  DESCRIPTION
    "A collection of
 objects related to the control and attribution
     of notifications common to all SIP entities."
  ::= { sipCommonMIBGroups 7 }

sipCommonNotifObjectsGroup OBJECT-GROUP



  OBJECTS {
        sipCommonStatusCodeNotifTo,
        sipCommonStatusCodeNotifFrom,
        sipCommonStatusCodeNotifCallId,
        sipCommonStatusCodeNotifCSeq,
        sipCommonNotifApplIndex,
        sipCommonNotifSequenceNumber
  }
  STATUS  current
  DESCRIPTION
    "A collection of accessible-for-notify objects related to the
     notification defined in this MIB module."
  ::= { sipCommonMIBGroups 8 }

END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/SIP-COMMON-MIB
No license file was found, but licenses were detected in source scan.

RMON2-MIB DEFINITIONS ::= BEGIN
IMPORTS
  MODULE-IDENTITY, OBJECT-TYPE, Counter32, Integer32,
  Gauge32, IpAddress, TimeTicks, mib-2        FROM SNMPv2-SMI
  TEXTUAL-CONVENTION, RowStatus, DisplayString, TimeStamp
```

```
                                FROM SNMPv2-TC
  MODULE-COMPLIANCE, OBJECT-GROUP            FROM SNMPv2-CONF
  ifIndex                                FROM IF-MIB
  OwnerString, statistics, history, hosts,
  matrix, filter, etherStatsEntry, historyControlEntry,
  hostControlEntry, matrixControlEntry, filterEntry,
  channelEntry                FROM RMON-MIB
  tokenRing, tokenRingMLStatsEntry, tokenRingPStatsEntry,




  ringStationControlEntry, sourceRoutingStatsEntry
                          FROM TOKEN-RING-RMON-MIB;
--  Remote Network Monitoring MIB

rmon MODULE-IDENTITY
  LAST-UPDATED "200605020000Z"    -- May 2, 2006
  ORGANIZATION "IETF RMON
 MIB Working Group"
  CONTACT-INFO
     "Author:
             Steve Waldbusser
        Phone:  +1-650-948-6500
        Fax :   +1-650-745-0671
        Email:  waldbusser@nextbeacon.com

      Working Group Chair:
             Andy Bierman
        E-mail: ietf@andybierman.com

      Working Group Mailing List: <rmonmib@ietf.org>
      To subscribe send email to: <rmonmib-request@ietf.org>    "
  DESCRIPTION
     "The MIB module for managing remote monitoring
      device implementations.  This MIB module
      extends the architecture introduced in the original
      RMON MIB as specified in RFC 2819.

      Copyright (C) The Internet Society (2006).  This version of
      this MIB module is part of RFC 4502;  see the RFC itself for
      full legal notices."

  REVISION "200605020000Z"    -- May 2, 2006
  DESCRIPTION
     "This version updates the proposed-standard version of the
     RMON2 MIB (published
 as RFC 2021) by adding 2 new
     enumerations to the nlMatrixTopNControlRateBase object and
```

4 new enumerations to the alMatrixTopNControlRateBase object. These new enumerations support the creation of high-capacity topN reports in the High Capacity RMON MIB [RFC3273].

Additionally, the following objects have been deprecated, as they have not had enough independent implementations to demonstrate interoperability to meet the requirements of a Draft Standard:

probeDownloadFile
probeDownloadTFTPServer
probeDownloadAction
probeDownloadStatus

serialMode
serialProtocol
serialTimeout
serialModemInitString
serialModemHangUpString
serialModemConnectResp
serialModemNoConnectResp
serialDialoutTimeout
serialStatus
serialConnectDestIpAddress
serialConnectType
serialConnectDialString
serialConnectSwitchConnectSeq
serialConnectSwitchDisconnectSeq
serialConnectSwitchResetSeq
serialConnectOwner
serialConnectStatus
netConfigIPAddress
netConfigSubnetMask
netConfigStatus
netDefaultGateway
tokenRingMLStats2DroppedFrames
tokenRingMLStats2CreateTime
tokenRingPStats2DroppedFrames
tokenRingPStats2CreateTime
ringStationControl2DroppedFrames
ringStationControl2CreateTime
sourceRoutingStats2DroppedFrames
sourceRoutingStats2CreateTime
trapDestIndex
trapDestCommunity
trapDestProtocol

trapDestAddress
trapDestOwner
trapDestStatus

In addition, two corrections were made. The LastCreateTime Textual Convention had been defined with a base type of another textual convention, which isn't allowed in SMIv2. The definition has been modified to use TimeTicks as the base type.

Further,
the SerialConfigEntry SEQUENCE definition included sub-typing information that is not allowed in SMIv2. This information has been deleted. Ranges were added to a number of objects and textual-conventions to constrain their maximum (and sometimes minimum) sizes. The addition of these ranges documents existing practice for these objects. These objects

are:
ControlString
protocolDirID
protocolDirParameters
addressMapNetworkAddress
nlHostAddress
nlMatrixSDSourceAddress
nlMatrixSDDestAddress
nlMatrixDSSourceAddress
nlMatrixDSDestAddress
nlMatrixTopNSourceAddress
nlMatrixTopNDestAddress
alHostEntry
alMatrixSDEntry
alMatrixDSEntry
alMatrixTopNSourceAddress
alMatrixTopNDestAddress

Finally, the TimeFilter TC has been updated to encourage agent implementations that allow a MIB walk to behave well even when performed by an application that is not aware of the special TimeFilter semantics."

REVISION "200207080000Z" -- 08 July, 2002
DESCRIPTION
"Added new enumerations to support the High-Capacity RMON MIB as defined in RFC 3273. Also fixed some typos and added clarifications."

```
  REVISION "199605270000Z"    -- 27 May, 1996
  DESCRIPTION
     "Original version.  Published as RFC 2021."
  ::= { mib-2 16 }

-- { rmon 1 } through { rmon 10 } are defined in RMON and
-- the Token Ring RMON MIB [RFC1513]

  protocolDir     OBJECT IDENTIFIER ::= { rmon 11 }
  protocolDist    OBJECT IDENTIFIER ::= { rmon 12 }
  addressMap      OBJECT IDENTIFIER ::= { rmon 13 }
  nlHost          OBJECT IDENTIFIER ::= { rmon 14 }
  nlMatrix        OBJECT IDENTIFIER ::= { rmon 15 }
  alHost          OBJECT IDENTIFIER ::= { rmon 16 }
  alMatrix        OBJECT IDENTIFIER
::= { rmon 17 }
  usrHistory      OBJECT IDENTIFIER ::= { rmon 18 }
  probeConfig     OBJECT IDENTIFIER ::= { rmon 19 }
  rmonConformance OBJECT IDENTIFIER ::= { rmon 20 }




-- Textual Conventions

ZeroBasedCounter32 ::= TEXTUAL-CONVENTION
  STATUS current
  DESCRIPTION
     "This TC describes an object that counts events with the
     following semantics: objects of this type will be set to
     zero(0) on creation and will thereafter count appropriate
     events, wrapping back to zero(0) when the value 2^32 is
     reached.

     Provided that an application discovers the new object within
     the minimum time to wrap, it can use the initial value as a
     delta since it last polled the table of which this object is
     part.  It is important for a management station to be aware of
     this minimum time and the actual time between polls, and to
     discard data if the actual time is too long or there is no
     defined minimum time.

      Typically, this TC is used in tables where the INDEX space is
     constantly changing and/or the TimeFilter mechanism is in use."
  SYNTAX Gauge32

LastCreateTime ::= TEXTUAL-CONVENTION
```

STATUS current
DESCRIPTION
"This TC describes an object that stores the value of the
sysUpTime object at the last time its entry was created.

This can be used for polling applications to determine that an
entry has been deleted and re-created between polls, causing
an otherwise undetectable discontinuity in the data.

If sysUpTime is reset to zero as a result of a re-
initialization of the network management (sub)system, then
the values of all LastCreateTime objects are also reset.
However, after approximately 497 days without a re-
initialization, the sysUpTime object will reach 2^^32-1 and
then increment to zero; in this case, existing values
of TimeStamp objects do not change.
This can lead to
ambiguities in the value of TimeStamp objects."
SYNTAX TimeTicks

TimeFilter ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
"To be used for the index to a table. Allows an application
to download only those rows changed since a particular time.

Note that this is not a history mechanism. Only current values
of underlying objects are returned; saved instance values
associated with particular values of sysUpTime are not.

An entry is considered changed if the value of any object in the
entry changes, if the row is created, or if any object in the
entry is created or deleted. Note that deleted entries cannot
be detected or downloaded.

A time-filtered conceptual table is created by inserting a
single object of SYNTAX TimeFilter as the first INDEX component
in a copy of an existing basic conceptual table (i.e., any
SEQUENCE without a TimeFilter INDEX component). Thus,
for
each conceptual entry 'I' in the basic table, there exists N
conceptual entries in the time-filtered version, indexed N.I,
where 'N' is equal to the value of sysUpTime.

When an application retrieves conceptual instances from a
time-filtered table, and an INDEX value is provided for the

TimeFilter INDEX component 'N', the agent will only consider returning basic conceptual entries (e.g., 'fooColumn.N.I') if any column within the basic conceptual entry has changed since sysUpTime 'N'. If not, the basic conceptual entry will be ignored for the particular retrieval operation.

When sysUpTime is equal to zero, this table shall be empty.

One conceptual entry exists for each past value of sysUpTime, except that the whole table is purged should sysUpTime wrap.

As an entry in a time-filtered table is updated (i.e., one of the columns in the basic conceptual table is changed), new conceptual
entries are also created in the time-filtered version (which still shares the now updated object values with all other instances). The number of unique time-filtered instances that are created is determined by the value of sysUpTime at which the basic entry was last updated. One unique instance will exist for each value of sysUpTime at the last update time for the row. However, a new TimeFilter index instance is created for each new sysUpTime value. The TimeFilter index values not associated with entry updates are called duplicate time-filtered instances.

After some deployment experience, it has been determined that a time-filtered table is more efficient if the agent stops a MIB walk operation by skipping over rows with a TimeFilter index value higher than the value in the received GetNext/GetBulk request. That is, instead of incrementing a TimeFilter index value, the agent will continue to the
next

object or table. As a consequence, GetNext or GetBulk operations will provide only one pass through a time-filtered table.

It is suggested that an agent implement a time-filtered table in this manner to improve performance and avoid a MIB walk getting stuck in time-filtered tables. It is, however, still acceptable for an agent to implement a time-filtered table in the traditional manner (i.e., every conceptual time-filtered instance is returned in GetNext and GetBulk PDU responses), and management applications must be able to deal with such traditional implementations.

See the appendix for further discussion of this textual

convention.

The following example is provided to demonstrate TimeFilter behavior:

Consider the following basic conceptual table, basicFooTable. (Note that the basic version of a time-filtered table may not actually be defined.)

```
basicFooTable:

 basicFooTable ...
INDEX { fooIndex }

BasicFooEntry {
  fooIndex     Integer32,
  fooCounts    Counter32
}
```

For this example, the basicFooTable contains two static conceptual entries (fooIndex equals '1' and '2'), created at time zero. It also contains one dynamic conceptual entry (fooIndex equals '3'), which is created at time '3' and deleted at time '7'.

The time-filtered version of the basicFooTable could be defined as follows:

```
FooTable:

fooTable ...
INDEX { fooTimeMark, fooIndex }

FooEntry {



  fooTimeMark  TimeFilter,
  fooIndex     Integer32,
  fooCounts    Counter32
}
```

Note that entries exist in the time-filtered conceptual table only if they actually exist in the underlying (basic) table.

For this example, the fooTable will have three underlying basic

entries (fooIndex == 1, 2, and 3), with the following
activity (for sysUpTime equal 0 to 9):

- fooEntry.N.1 is created at time '0' and most recently updated at time '6' to the value '5'.
- fooEntry.N.2 is created at time '0' and most recently updated at time '8' to the value '9'.
- fooEntry.N.3 is created at time '3', updated at time '5' to the value '17', and deleted at time '7'.

The following tables show the values that would be returned for MIB walk operations with various TimeFilter values, done at different times. An application issues a retrieval request at time 'T', with a TimeFilter value, 'N' (typically set to a lower value, such as the value of sysUpTime at the last polling cycle).

The following values would be returned in a MIB walk of fooCounts.N if T equals '0' and N equals '0':

fooCounts.N.I	Value
fooCounts.0.1	0
fooCounts.0.2	0

Note that nothing is returned for fooCounts.0.3, since that entry does not exist at sysUpTime equals '0'.

The following values would be returned in a full (traditional) MIB walk of fooCounts.N if T equals '3' and N equals '0':

fooCounts.N.I	Value
fooCounts.0.1	0
fooCounts.0.2	0
fooCounts.0.3	0
fooCounts.1.3	0
fooCounts.2.3	0
fooCounts.3.3	0

Note that there are no instances for T equals 1 or 2 for the first two values of N, as these entries did not change since they were created at time '0'.

Note that the current value for 'fooCounts.N.3' is returned here, even for values of N less than '3' (when the entry was

created). The agent only considers the current existence of an entry in the TimeFilter algorithm, not the time when the entry

was created.

Note that the instances 'fooCounts.0.3', 'fooCounts.1.3', and 'fooCounts.2.3' are duplicates and can be suppressed by the agent in a MIB walk.

The following values would be returned in a full (traditional) MIB walk of fooCounts.N if T equals '6' and N equals '3':

fooCounts.N.I	Value
fooCounts.3.1	5
fooCounts.3.3	17
fooCounts.4.1	5
fooCounts.4.3	17
fooCounts.5.1	5
fooCounts.5.3	17
fooCounts.6.1	5

Note that no instances for entry 'fooCounts.N.2' are returned, since it has not changed since time '3'.

Note that all instances except 'fooCounts.5.3' and 'fooCounts.6.1' are duplicates and can be suppressed by the agent in a MIB walk.

The following values would be returned in a full (traditional) MIB walk of fooCounts.N if T equals '9' and N equals '6':

fooCounts.N.I	Value
fooCounts.6.1	5
fooCounts.6.2	9
fooCounts.7.2	9
fooCounts.8.2	9

Note that no instances for entry 'fooCounts.N.3' are returned, since it was deleted at time '7'.

Note that instances 'fooCounts.6.2' and 'fooCounts.7.2'

are duplicates and can be suppressed by the agent in a MIB

walk."

SYNTAX TimeTicks

DataSource ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
"Identifies the source of the data that the associated
function is configured to analyze. This source can be any
interface on this device.

In order to identify a particular interface, this
object shall identify the instance of the ifIndex
object, defined in [RFC2863], for the desired interface.

For example, if an entry were to receive data from
interface #1, this object
would be set to ifIndex.1."
SYNTAX OBJECT IDENTIFIER

--
-- Protocol Directory Group
--
-- Lists the inventory of protocols the probe has the capability of
-- monitoring and allows the addition, deletion, and configuration of
-- entries in this list.

protocolDirLastChange OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime at the time the protocol directory
was last modified, either through insertions or deletions,
or through modifications of the
protocolDirAddressMapConfig, protocolDirHostConfig, or
protocolDirMatrixConfig."
::= { protocolDir 1 }

protocolDirTable OBJECT-TYPE
SYNTAX SEQUENCE OF ProtocolDirEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"This table lists the protocols that this agent has the
capability to decode and count. There is one entry in this
table for each such protocol.

```
  These protocols represent
      different network-layer, transport-layer, and higher-layer



      protocols.  The agent should boot up with this table
      preconfigured with those protocols that it knows about and
      wishes to monitor.  Implementations are strongly encouraged to
      support protocols higher than the network layer (at least for
      the protocol distribution group), even for implementations
      that don't support the application-layer groups."
   ::= { protocolDir 2 }

protocolDirEntry OBJECT-TYPE
   SYNTAX      ProtocolDirEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "A conceptual row in the protocolDirTable.

       An example of the indexing of this entry is
       protocolDirLocalIndex.8.0.0.0.1.0.0.8.0.2.0.0, which is the
       encoding of a length of 8, followed by 8 subids encoding the
       protocolDirID of 1.2048, followed by a length of 2 and the
       2 subids encoding zero-valued
 parameters.

       Note that some combinations of index values may result in an
       index that exceeds 128 sub-identifiers in length, which exceeds
       the maximum for the SNMP protocol.  Implementations should take
       care to avoid such combinations."
   INDEX { protocolDirID, protocolDirParameters }
   ::= { protocolDirTable  1 }

ProtocolDirEntry ::= SEQUENCE {
   protocolDirID                OCTET STRING,
   protocolDirParameters        OCTET STRING,
   protocolDirLocalIndex        Integer32,
   protocolDirDescr             DisplayString,
   protocolDirType              BITS,
   protocolDirAddressMapConfig  INTEGER,
   protocolDirHostConfig        INTEGER,
   protocolDirMatrixConfig      INTEGER,
   protocolDirOwner             OwnerString,
   protocolDirStatus            RowStatus
}

protocolDirID OBJECT-TYPE
```

```
  SYNTAX      OCTET STRING  (SIZE (4..128))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A unique identifier for a particular protocol.  Standard
      identifiers will be defined in such a manner that they




      can often be used as specifications for new protocols - i.e.,
      a tree-structured assignment mechanism that matches the
      protocol encapsulation 'tree' and that has algorithmic
      assignment mechanisms for certain subtrees.  See RFC 2074 for
      more details.

      Despite the algorithmic mechanism, the probe will only place
      entries in here for those protocols it chooses to collect.  In
      other words, it need not populate this table with all
      possible ethernet protocol types, nor need it create them on
      the fly when it sees them.  Whether it does these
      things is a matter of product definition (cost/benefit,
      usability) and is up to the designer of the product.

      If an entry is written to this table with a protocolDirID that
      the agent doesn't understand, either
 directly or
      algorithmically, the SET request will be rejected with an
      inconsistentName or badValue (for SNMPv1) error."
  ::= { protocolDirEntry 1 }

protocolDirParameters OBJECT-TYPE
  SYNTAX      OCTET STRING (SIZE (1..32))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A set of parameters for the associated protocolDirID.
      See the associated RMON2 Protocol Identifiers document
      for a description of the possible parameters.  There
      will be one octet in this string for each sub-identifier in
      the protocolDirID, and the parameters will appear here in the
      same order as the associated sub-identifiers appear in the
      protocolDirID.

      Every node in the protocolDirID tree has a different, optional
      set of parameters defined (that is, the definition of
      parameters for a node is optional).  The proper parameter
      value for each node is included in this string.  Note that
```

the
inclusion of a parameter value in this string for each node is
not optional. What is optional is that a node may have no
parameters defined, in which case the parameter field for that
node will be zero."
::= { protocolDirEntry 2 }

protocolDirLocalIndex OBJECT-TYPE
SYNTAX Integer32 (1..2147483647)
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"The locally arbitrary but unique identifier associated
with this protocolDir entry.

The value for each supported protocol must remain constant at
least from one re-initialization of the entity's network
management system to the next re-initialization, except that
if a protocol is deleted and re-created, it must be re-created
with a new value that has not been used since the last
re-initialization.

The specific value is meaningful only within a given SNMP
entity. A protocolDirLocalIndex must not
be re-used until the
next agent restart in the event that the protocol directory
entry is deleted."
::= { protocolDirEntry 3 }

protocolDirDescr OBJECT-TYPE
SYNTAX DisplayString (SIZE (1..64))
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"A textual description of the protocol encapsulation.
A probe may choose to describe only a subset of the
entire encapsulation (e.g., only the highest layer).

This object is intended for human consumption only.

This object may not be modified if the associated
protocolDirStatus object is equal to active(1)."
::= { protocolDirEntry 4 }

protocolDirType OBJECT-TYPE

```
  SYNTAX      BITS {
                extensible(0),
                addressRecognitionCapable(1)
              }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "This object describes 2 attributes of this protocol
      directory entry.


The presence or absence of the 'extensible' bit describes
      whether this protocol directory entry can be extended
      by the user by creating protocol directory entries that are
      children of this protocol.

      An example of an entry that will often allow extensibility is



      'ip.udp'.  The probe may automatically populate some children
      of this node, such as 'ip.udp.snmp' and 'ip.udp.dns'.
      A probe administrator or user may also populate additional
      children via remote SNMP requests that create entries in this
      table.  When a child node is added for a protocol for which the
      probe has no built-in support extending a parent node (for
      which the probe does have built-in support),
      that child node is not extendable.  This is termed 'limited
      extensibility'.

      When a child node is added through this extensibility
      mechanism, the values of protocolDirLocalIndex and
      protocolDirType
shall be assigned by the agent.

      The other objects in the entry will be assigned by the
      manager who is creating the new entry.

      This object also describes whether this agent can
      recognize addresses for this protocol, should it be a
      network-level protocol.  That is, while a probe may be able
      to recognize packets of a particular network-layer protocol
      and count them, it takes additional logic to be able to
      recognize the addresses in this protocol and to populate
      network-layer or application-layer tables with the addresses
      in this protocol.  If this bit is set, the agent will
      recognize network-layer addresses for this protocol and
      populate the network- and application-layer host and matrix
```

tables with these protocols.

Note that when an entry is created, the agent will supply values for the bits that match the capabilities of the agent

with respect to this protocol. Note that since row creations usually exercise the limited extensibility feature, these bits will usually be set to zero."

::= { protocolDirEntry 5 }

protocolDirAddressMapConfig OBJECT-TYPE
SYNTAX INTEGER {
notSupported(1),
supportedOff(2),
supportedOn(3)
}
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This object describes and configures the probe's support for address mapping for this protocol. When the probe creates entries in this table for all protocols that it understands,

it will set the entry to notSupported(1) if it doesn't have the capability to perform address mapping for the protocol or if this protocol is not a network-layer protocol. When an entry is created in this table by a management operation as part of the limited extensibility feature,

the probe must set this value to notSupported(1), because limited extensibility of the protocolDirTable does not extend to interpreting addresses of the extended protocols.

If the value of this object is notSupported(1), the probe will not perform address mapping for this protocol and shall not allow this object to be changed to any other value.
If the value of this object is supportedOn(3), the probe supports address mapping for this protocol and is configured to perform address mapping for this protocol for all addressMappingControlEntries and all interfaces.
If the value of this object is supportedOff(2), the probe supports address mapping for this protocol but is configured to not perform address mapping for this protocol for any addressMappingControlEntries and all interfaces.
Whenever this value changes from supportedOn(3) to supportedOff(2), the probe

```
 shall delete all related entries in
      the addressMappingTable."
   ::= { protocolDirEntry 6 }

protocolDirHostConfig OBJECT-TYPE
   SYNTAX      INTEGER {
                  notSupported(1),
                  supportedOff(2),
                  supportedOn(3)
               }
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "This object describes and configures the probe's support for
      the network-layer and application-layer host tables for this
      protocol.  When the probe creates entries in this table for
      all protocols that it understands, it will set the entry to
      notSupported(1) if it doesn't have the capability to track the
      nlHostTable for this protocol or if the alHostTable is
      implemented but doesn't have the capability to track this
      protocol.  Note that if the alHostTable is implemented, the
      probe may only support a protocol if it is supported in both
      the nlHostTable and the
 alHostTable.

      If the associated protocolDirType object has the
      addressRecognitionCapable bit set, then this is a network-
      layer protocol for which the probe recognizes addresses, and



      thus the probe will populate the nlHostTable and alHostTable
      with addresses it discovers for this protocol.

      If the value of this object is notSupported(1), the probe
      will not track the nlHostTable or alHostTable for this
      protocol and shall not allow this object to be changed to any
      other value.  If the value of this object is supportedOn(3),
      the probe supports tracking of the nlHostTable and alHostTable
      for this protocol and is configured to track both tables
      for this protocol for all control entries and all interfaces.
      If the value of this object is supportedOff(2), the probe
      supports tracking of the nlHostTable and alHostTable for this
      protocol but is configured to not track these
 tables
      for any control entries or interfaces.
      Whenever this value changes from supportedOn(3) to
      supportedOff(2), the probe shall delete all related entries in
```

the nlHostTable and alHostTable.

Note that since each alHostEntry references 2 protocol directory entries, one for the network address and one for the type of the highest protocol recognized, an entry will only be created in that table if this value is supportedOn(3) for both protocols."
::= { protocolDirEntry 7 }

protocolDirMatrixConfig OBJECT-TYPE
SYNTAX INTEGER {
notSupported(1),
supportedOff(2),
supportedOn(3)
}
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This object describes and configures the probe's support for the network-layer and application-layer matrix tables for this protocol. When the probe creates entries
in this table for
all protocols that it understands, it will set the entry to notSupported(1) if it doesn't have the capability to track the nlMatrixTables for this protocol or if the alMatrixTables are implemented but don't have the capability to track this protocol. Note that if the alMatrix tables are implemented, the probe may only support a protocol if it is supported in both of the nlMatrixTables and both of the alMatrixTables.

If the associated protocolDirType object has the addressRecognitionCapable bit set, then this is a network-

layer protocol for which the probe recognizes addresses, and thus the probe will populate both of the nlMatrixTables and both of the alMatrixTables with addresses it discovers for this protocol.

If the value of this object is notSupported(1), the probe will not track either of the nlMatrixTables or the alMatrixTables
for this protocol and shall not allow this
object to be changed to any other value. If the value of this object is supportedOn(3), the probe supports tracking of both of the nlMatrixTables and (if implemented) both of the

```
      alMatrixTables for this protocol and is configured to track
      these tables for this protocol for all control entries and all
      interfaces.  If the value of this object is supportedOff(2),
      the probe supports tracking of both of the nlMatrixTables and
      (if implemented) both of the alMatrixTables for this protocol
      but is configured to not track these tables for this
      protocol for any control entries or interfaces.
      Whenever this value changes from supportedOn(3) to
      supportedOff(2), the probe shall delete all related entries in
      the nlMatrixTables and the alMatrixTables.

      Note that since each alMatrixEntry references 2 protocol
      directory entries, one for
 the network address and one for the
      type of the highest protocol recognized, an entry will
      only be created in that table if this value is supportedOn(3)
      for both protocols."
  ::= { protocolDirEntry 8 }

protocolDirOwner OBJECT-TYPE
  SYNTAX      OwnerString
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The entity that configured this entry and is
     therefore using the resources assigned to it."
  ::= { protocolDirEntry 9 }

protocolDirStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The status of this protocol directory entry.

     An entry may not exist in the active state unless all
     objects in the entry have an appropriate value.




     If this object is not equal to active(1), all associated
     entries in the nlHostTable, nlMatrixSDTable, nlMatrixDSTable,
     alHostTable, alMatrixSDTable, and alMatrixDSTable shall be
      deleted."
  ::= { protocolDirEntry 10 }

--
```

```
-- Protocol Distribution Group  (protocolDist)
--
-- Collects the relative amounts of octets and packets for the
-- different protocols detected on a network segment.
--    protocolDistControlTable,
--    protocolDistStatsTable

protocolDistControlTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF ProtocolDistControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "Controls the setup of protocol type distribution statistics
     tables.

     Implementations are encouraged to add an entry per monitored
     interface upon initialization so that a default collection
     of protocol statistics is available.

     Rationale:
     This table controls collection of very basic statistics
     for any or all of the protocols detected on a given interface.
     An NMS can use this table to quickly determine bandwidth
     allocation utilized by different protocols.

     A media-specific
 statistics collection could also
     be configured (e.g., etherStats, trPStats) to easily obtain
     total frame, octet, and droppedEvents for the same
     interface."
  ::= { protocolDist 1 }

protocolDistControlEntry OBJECT-TYPE
  SYNTAX      ProtocolDistControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A conceptual row in the protocolDistControlTable.

      An example of the indexing of this entry is
      protocolDistControlDroppedFrames.7"
  INDEX { protocolDistControlIndex }



  ::= { protocolDistControlTable 1 }

ProtocolDistControlEntry ::= SEQUENCE {
```

```
  protocolDistControlIndex              Integer32,
  protocolDistControlDataSource         DataSource,
  protocolDistControlDroppedFrames      Counter32,
  protocolDistControlCreateTime         LastCreateTime,
  protocolDistControlOwner              OwnerString,
  protocolDistControlStatus             RowStatus
}

protocolDistControlIndex
 OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS  not-accessible
  STATUS     current
  DESCRIPTION
     "A unique index for this protocolDistControlEntry."
  ::= { protocolDistControlEntry 1 }

protocolDistControlDataSource OBJECT-TYPE
  SYNTAX     DataSource
  MAX-ACCESS  read-create
  STATUS     current
  DESCRIPTION
     "The source of data for the this protocol distribution.

     The statistics in this group reflect all packets
     on the local network segment attached to the
     identified interface.

     This object may not be modified if the associated
     protocolDistControlStatus object is equal to active(1)."
  ::= { protocolDistControlEntry 2 }

protocolDistControlDroppedFrames OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The total number of frames that were received by the probe
     and therefore not accounted for in the *StatsDropEvents,
 but
     that the probe chose not to count for this entry for
     whatever reason.  Most often, this event occurs when the probe
     is out of some resources and decides to shed load from this
     collection.

     This count does not include packets that were not counted
     because they had MAC-layer errors.
```

```
      Note that, unlike the dropEvents counter, this number is the
      exact number of frames dropped."
   ::= { protocolDistControlEntry 3 }

protocolDistControlCreateTime OBJECT-TYPE
   SYNTAX     LastCreateTime
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The value of sysUpTime when this control entry was last
      activated.  This can be used by the management station to
      ensure that the table has not been deleted and recreated
      between polls."
   ::= { protocolDistControlEntry 4 }

protocolDistControlOwner OBJECT-TYPE
   SYNTAX      OwnerString
   MAX-ACCESS  read-create
   STATUS      current
    DESCRIPTION
      "The entity that configured this entry and is
      therefore using the resources assigned to it."
   ::= { protocolDistControlEntry 5 }

protocolDistControlStatus OBJECT-TYPE
   SYNTAX      RowStatus
   MAX-ACCESS  read-create
   STATUS      current
   DESCRIPTION
      "The status of this row.

      An entry may not exist in the active state unless all
      objects in the entry have an appropriate value.

      If this object is not equal to active(1), all associated
      entries in the protocolDistStatsTable shall be deleted."
   ::= { protocolDistControlEntry 6 }

-- per interface protocol distribution statistics table
protocolDistStatsTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF ProtocolDistStatsEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "An entry is made in this table for every protocol in the
      protocolDirTable that has been seen in at least one packet.
```

```
      Counters are updated
 in this table for every protocol type
      that is encountered when parsing a packet, but no counters are




      updated for packets with MAC-layer errors.

      Note that if a protocolDirEntry is deleted, all associated
      entries in this table are removed."
   ::= { protocolDist 2 }

protocolDistStatsEntry OBJECT-TYPE
   SYNTAX      ProtocolDistStatsEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "A conceptual row in the protocolDistStatsTable.

      The index is composed of the protocolDistControlIndex of the
      associated protocolDistControlEntry, followed by the
      protocolDirLocalIndex of the associated protocol that this
      entry represents.  In other words, the index identifies the
      protocol distribution an entry is a part of and the
      particular protocol that it represents.

      An example of the indexing of this entry is
      protocolDistStatsPkts.1.18"
   INDEX { protocolDistControlIndex,
  protocolDirLocalIndex }
   ::= { protocolDistStatsTable 1 }

ProtocolDistStatsEntry ::= SEQUENCE {
   protocolDistStatsPkts                ZeroBasedCounter32,
   protocolDistStatsOctets               ZeroBasedCounter32
}

protocolDistStatsPkts OBJECT-TYPE
   SYNTAX      ZeroBasedCounter32
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The number of packets of this protocol type received
      without errors.  Note that this is the number of
      link-layer packets, so if a single network-layer packet
      is fragmented into several link-layer frames, this counter
      is incremented several times."
   ::= { protocolDistStatsEntry 1 }
```

```
protocolDistStatsOctets OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The number of octets in packets of this protocol type



      received since it was added to the protocolDistStatsTable
      (excluding framing bits,
 but including FCS octets), except for
      those octets in packets that contained errors.

      Note that this doesn't count just those octets in the
      particular protocol frames but includes the entire packet
      that contained the protocol."
  ::= { protocolDistStatsEntry 2 }

--
-- Address Map Group   (addressMap)
--
-- Lists MAC address to network address bindings discovered by the
-- probe and what interface they were last seen on.
--    addressMapControlTable
--    addressMapTable

addressMapInserts OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
      "The number of times an address mapping entry has been
      inserted into the addressMapTable.  If an entry is inserted,
      then deleted, and then inserted, this counter will be
      incremented by 2.

      Note that the table size can be determined by subtracting
      addressMapDeletes from addressMapInserts."
  ::= { addressMap 1 }

addressMapDeletes
 OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
```

"The number of times an address mapping entry has been
deleted from the addressMapTable (for any reason). If
an entry is deleted, then inserted, and then deleted, this
counter will be incremented by 2.

Note that the table size can be determined by subtracting
addressMapDeletes from addressMapInserts."
::= { addressMap 2 }

addressMapMaxDesiredEntries OBJECT-TYPE
SYNTAX Integer32 (-1..2147483647)
MAX-ACCESS read-write

STATUS current
DESCRIPTION
"The maximum number of entries that are desired in the
addressMapTable. The probe will not create more than
this number of entries in the table but may choose to create
fewer entries in this table for any reason, including the lack
of resources.

If this object is set to a value less than the current number
of entries, enough entries are chosen in an
implementation-dependent manner and deleted so that the number
of entries in the table equals the value of this object.

If this value is set to -1, the probe may create any number
of entries in this table.

This object may be used to control how resources are allocated
on the probe for the various RMON functions."
::= { addressMap 3 }

addressMapControlTable OBJECT-TYPE
SYNTAX SEQUENCE OF AddressMapControlEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"A table to control the collection of mappings from network
layer address to physical address to interface.

Note that this is not like the typical RMON
controlTable and dataTable in which each entry creates
its own data table. Each entry in this table enables the
discovery of addresses on a new interface and the placement
of address

```
 mappings into the central addressMapTable.

      Implementations are encouraged to add an entry per monitored
      interface upon initialization so that a default collection
      of address mappings is available."
  ::= { addressMap 4 }

addressMapControlEntry OBJECT-TYPE
  SYNTAX      AddressMapControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A conceptual row in the addressMapControlTable.

      An example of the indexing of this entry is
      addressMapControlDroppedFrames.1"



  INDEX { addressMapControlIndex }
  ::= { addressMapControlTable 1 }

AddressMapControlEntry ::= SEQUENCE {
  addressMapControlIndex              Integer32,
  addressMapControlDataSource         DataSource,
  addressMapControlDroppedFrames      Counter32,
  addressMapControlOwner              OwnerString,
  addressMapControlStatus             RowStatus
}

addressMapControlIndex OBJECT-TYPE
  SYNTAX      Integer32 (1..65535)
  MAX-ACCESS
 not-accessible
  STATUS      current
  DESCRIPTION
      "A unique index for this entry in the addressMapControlTable."
  ::= { addressMapControlEntry 1 }

addressMapControlDataSource OBJECT-TYPE
  SYNTAX      DataSource
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      "The source of data for this addressMapControlEntry."
  ::= { addressMapControlEntry 2 }

addressMapControlDroppedFrames OBJECT-TYPE
```

```
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The total number of frames that were received by the probe
     and therefore not accounted for in the *StatsDropEvents, but
     that the probe chose not to count for this entry for
     whatever reason.  Most often, this event occurs when the probe
     is out of some resources and decides to shed load from this
     collection.

     This count does not include packets that were not counted
     because they had MAC-layer errors.

      Note that, unlike the dropEvents counter, this number is the
     exact number of frames dropped."
  ::= { addressMapControlEntry 3 }

addressMapControlOwner OBJECT-TYPE
  SYNTAX      OwnerString



  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The entity that configured this entry and is
     therefore using the resources assigned to it."
  ::= { addressMapControlEntry 4 }

addressMapControlStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The status of this addressMap control entry.

     An entry may not exist in the active state unless all
     objects in the entry have an appropriate value.

     If this object is not equal to active(1), all associated
     entries in the addressMapTable shall be deleted."
  ::= { addressMapControlEntry 5 }

addressMapTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF AddressMapEntry
  MAX-ACCESS  not-accessible
```

```
    STATUS      current
    DESCRIPTION
        "A table of mappings from network layer address to physical
        address to interface.

        The probe will add entries to this table based on the source
        MAC and network addresses seen in packets without MAC-level
        errors.  The probe will populate this table for all protocols
        in the protocol directory table whose value of
        protocolDirAddressMapConfig is equal to supportedOn(3), and
        will delete any entries whose protocolDirEntry is deleted or
        has a protocolDirAddressMapConfig value of supportedOff(2)."
    ::= { addressMap 5 }

addressMapEntry OBJECT-TYPE
    SYNTAX      AddressMapEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A conceptual row in the addressMapTable.

        The protocolDirLocalIndex in the index identifies the network
        layer protocol of the addressMapNetworkAddress.




        An example of the indexing of this entry is
         addressMapSource.783495.18.4.128.2.6.6.11.1.3.6.1.2.1.2.2.1.1.1.

        Note that some combinations of index values may result in an
        index that exceeds 128 sub-identifiers in length, which exceeds
        the maximum for the SNMP protocol.  Implementations should take
        care to avoid such combinations."
    INDEX { addressMapTimeMark, protocolDirLocalIndex,
            addressMapNetworkAddress, addressMapSource }
    ::= { addressMapTable 1 }

AddressMapEntry ::= SEQUENCE {
    addressMapTimeMark              TimeFilter,
    addressMapNetworkAddress        OCTET STRING,
    addressMapSource                OBJECT IDENTIFIER,
    addressMapPhysicalAddress       OCTET STRING,
    addressMapLastChange            TimeStamp
}

addressMapTimeMark OBJECT-TYPE
    SYNTAX      TimeFilter
```

```
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A TimeFilter for this entry.  See the TimeFilter textual
     convention to see how this
 works."
  ::= { addressMapEntry 1 }

addressMapNetworkAddress OBJECT-TYPE
  SYNTAX      OCTET STRING (SIZE (1..255))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The network address for this relation.

     This is represented as an octet string with
     specific semantics and length as identified
     by the protocolDirLocalIndex component of the
     index.

     For example, if the protocolDirLocalIndex indicates an
     encapsulation of ip, this object is encoded as a length
     octet of 4, followed by the 4 octets of the IP address,
     in network byte order."
  ::= { addressMapEntry 2 }

addressMapSource OBJECT-TYPE
  SYNTAX      OBJECT IDENTIFIER



  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The interface or port on which the associated network
      address was most recently seen.

     If this address mapping was discovered on an interface, this
     object shall
 identify the instance of the ifIndex
     object, defined in [RFC2863], for the desired interface.
     For example, if an entry were to receive data from
     interface #1, this object would be set to ifIndex.1.

     If this address mapping was discovered on a port, this
     object shall identify the instance of the rptrGroupPortIndex
     object, defined in [RFC2108], for the desired port.
     For example, if an entry were to receive data from
```

group #1, port #1, this object would be set to
rptrGroupPortIndex.1.1.

Note that while the dataSource associated with this entry
may only point to index objects, this object may at times
point to repeater port objects. This situation occurs when
the dataSource points to an interface that is a locally
attached repeater and the agent has additional information
about the source port of traffic seen on that repeater."
::= { addressMapEntry 3 }

addressMapPhysicalAddress
OBJECT-TYPE
SYNTAX OCTET STRING
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The last source physical address on which the associated
network address was seen. If the protocol of the associated
network address was encapsulated inside of a network-level or
higher protocol, this will be the address of the next-lower
protocol with the addressRecognitionCapable bit enabled and
will be formatted as specified for that protocol."
::= { addressMapEntry 4 }

addressMapLastChange OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime at the time this entry was last
created or the values of the physical address changed.

This can be used to help detect duplicate address problems, in
which case this object will be updated frequently."
::= { addressMapEntry 5 }

--
-- Network Layer Host Group
--
--
Counts the amount of traffic sent from and to each network address
-- discovered by the probe.
-- Note that while the hlHostControlTable also has objects that
-- control an optional alHostTable, implementation of the alHostTable is

```
-- not required to fully implement this group.

hlHostControlTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF HlHostControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A list of higher-layer (i.e., non-MAC) host table control
     entries.

     These entries will enable the collection of the network- and
     application-level host tables indexed by network addresses.
     Both the network- and application-level host tables are
     controlled by this table so that they will both be created
     and deleted at the same time, further increasing the ease with
     which they can be implemented as a single datastore.  (Note that
     if an implementation stores application-layer host records
in
     memory, it can derive network-layer host records from them.)

     Entries in the nlHostTable will be created on behalf of each
     entry in this table.  Additionally, if this probe implements
     the alHostTable, entries in the alHostTable will be created on
     behalf of each entry in this table.

     Implementations are encouraged to add an entry per monitored
     interface upon initialization so that a default collection
     of host statistics is available."
  ::= { nlHost 1 }

hlHostControlEntry OBJECT-TYPE
  SYNTAX      HlHostControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A conceptual row in the hlHostControlTable.

     An example of the indexing of this entry is




     hlHostControlNlDroppedFrames.1"
  INDEX { hlHostControlIndex }
  ::= { hlHostControlTable 1 }

HlHostControlEntry ::= SEQUENCE {
  hlHostControlIndex             Integer32,
  hlHostControlDataSource
```

```
   DataSource,
  hlHostControlNlDroppedFrames     Counter32,
  hlHostControlNlInserts           Counter32,
  hlHostControlNlDeletes           Counter32,
  hlHostControlNlMaxDesiredEntries Integer32,
  hlHostControlAlDroppedFrames     Counter32,
  hlHostControlAlInserts           Counter32,
  hlHostControlAlDeletes           Counter32,
  hlHostControlAlMaxDesiredEntries Integer32,
  hlHostControlOwner               OwnerString,
  hlHostControlStatus              RowStatus
}

hlHostControlIndex OBJECT-TYPE
  SYNTAX      Integer32 (1..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "An index that uniquely identifies an entry in the
     hlHostControlTable.  Each such entry defines
     a function that discovers hosts on a particular
     interface and places statistics about them in the
     nlHostTable, and optionally in the alHostTable, on
     behalf of this hlHostControlEntry."
  ::= { hlHostControlEntry 1 }

hlHostControlDataSource
 OBJECT-TYPE
  SYNTAX      DataSource
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The source of data for the associated host tables.

     The statistics in this group reflect all packets
     on the local network segment attached to the
     identified interface.

     This object may not be modified if the associated
     hlHostControlStatus object is equal to active(1)."
  ::= { hlHostControlEntry 2 }

hlHostControlNlDroppedFrames OBJECT-TYPE



  SYNTAX     Counter32
  MAX-ACCESS read-only
```

```
  STATUS     current
  DESCRIPTION
     "The total number of frames that were received by the probe
      and therefore not accounted for in the *StatsDropEvents, but
      that the probe chose not to count for the associated
      nlHost entries for whatever reason.  Most often, this event
      occurs when the probe is out of some resources and decides to
      shed load from this collection.


    This count does not include packets that were not counted
      because they had MAC-layer errors.

      Note that if the nlHostTable is inactive because no protocols
      are enabled in the protocol directory, this value should be 0.

      Note that, unlike the dropEvents counter, this number is the
      exact number of frames dropped."
  ::= { hlHostControlEntry 3 }

hlHostControlNlInserts OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of times an nlHost entry has been
      inserted into the nlHost table.  If an entry is inserted, then
      deleted, and then inserted, this counter will be incremented
      by 2.

      To allow for efficient implementation strategies, agents may
      delay updating this object for short periods of time.  For
      example, an implementation strategy may allow internal
      data structures to differ from those visible via SNMP for
      short
 periods of time.  This counter may reflect the internal
      data structures for those short periods of time.

      Note that the table size can be determined by subtracting
      hlHostControlNlDeletes from hlHostControlNlInserts."
  ::= { hlHostControlEntry 4 }

hlHostControlNlDeletes OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of times an nlHost entry has been
```

deleted from the nlHost table (for any reason). If an entry
is deleted, then inserted, and then deleted, this counter will
be incremented by 2.

To allow for efficient implementation strategies, agents may
delay updating this object for short periods of time. For
example, an implementation strategy may allow internal
data structures to differ from those visible via SNMP for
short periods of time. This counter may reflect the internal
data structures for those short
periods of time.

Note that the table size can be determined by subtracting
hlHostControlNlDeletes from hlHostControlNlInserts."
::= { hlHostControlEntry 5 }

hlHostControlNlMaxDesiredEntries OBJECT-TYPE
SYNTAX Integer32 (-1..2147483647)
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The maximum number of entries that are desired in the
nlHostTable on behalf of this control entry. The probe will
not create more than this number of associated entries in the
table but may choose to create fewer entries in this table
for any reason, including the lack of resources.

If this object is set to a value less than the current number
of entries, enough entries are chosen in an
implementation-dependent manner and deleted so that the number
of entries in the table equals the value of this object.

If this value is set to -1, the probe may create any number

of entries in this table. If the associated
hlHostControlStatus object is equal to 'active', this
object may not be modified.

This object may be used to control how resources are allocated
on the probe for the various RMON functions."
::= { hlHostControlEntry 6 }

hlHostControlAlDroppedFrames OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only

STATUS current
DESCRIPTION
"The total number of frames that were received by the probe
and therefore not accounted for in the *StatsDropEvents, but
that the probe chose not to count for the associated

alHost entries for whatever reason. Most often, this event
occurs when the probe is out of some resources and decides to
shed load from this collection.

This count does not include packets that were not counted
because they had MAC-layer errors.

Note that if the alHostTable is not implemented or is inactive

because no protocols are enabled in the protocol directory,
this value should be 0.

Note that, unlike the dropEvents counter, this number is the
exact number of frames dropped."
::= { hlHostControlEntry 7 }

hlHostControlAlInserts OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of times an alHost entry has been
inserted into the alHost table. If an entry is inserted, then
deleted, and then inserted, this counter will be incremented
by 2.

To allow for efficient implementation strategies, agents may
delay updating this object for short periods of time. For
example, an implementation strategy may allow internal
data structures to differ from those visible via SNMP for
short periods of time. This counter may reflect the internal
data structures for those short periods of time.

Note that the table size can
be determined by subtracting
hlHostControlAlDeletes from hlHostControlAlInserts."
::= { hlHostControlEntry 8 }

hlHostControlAlDeletes OBJECT-TYPE
SYNTAX Counter32

MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of times an alHost entry has been
deleted from the alHost table (for any reason). If an entry
is deleted, then inserted, and then deleted, this counter will
be incremented by 2.

To allow for efficient implementation strategies, agents may
delay updating this object for short periods of time. For

example, an implementation strategy may allow internal
data structures to differ from those visible via SNMP for
short periods of time. This counter may reflect the internal
data structures for those short periods of time.

Note that the table size can be determined by subtracting
hlHostControlAlDeletes from hlHostControlAlInserts."

::= { hlHostControlEntry 9 }

hlHostControlAlMaxDesiredEntries OBJECT-TYPE
SYNTAX Integer32 (-1..2147483647)
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The maximum number of entries that are desired in the alHost
table on behalf of this control entry. The probe will not
create more than this number of associated entries in the
table but may choose to create fewer entries in this table
for any reason, including the lack of resources.

If this object is set to a value less than the current number
of entries, enough entries are chosen in an
implementation-dependent manner and deleted so that the number
of entries in the table equals the value of this object.

If this value is set to -1, the probe may create any number
of entries in this table. If the associated
hlHostControlStatus object is equal to 'active', this
object may not be modified.

This object may be used to control how resources are allocated
on the probe for the various RMON functions."
::= { hlHostControlEntry 10 }

```
hlHostControlOwner OBJECT-TYPE
  SYNTAX      OwnerString
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "The entity that configured this entry and is
     therefore using the resources assigned to it."
  ::= { hlHostControlEntry 11 }

hlHostControlStatus OBJECT-TYPE
  SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION



     "The status of this hlHostControlEntry.

     An entry may not exist in the active state unless all
     objects in the entry have an appropriate value.

     If this object is not equal to active(1), all associated
     entries in the nlHostTable and alHostTable shall be deleted."
  ::= { hlHostControlEntry 12 }

nlHostTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF NlHostEntry
  MAX-ACCESS  not-accessible
  STATUS
  current
  DESCRIPTION
     "A collection of statistics for a particular network layer
     address that has been discovered on an interface of this
     device.

     The probe will populate this table for all network layer
     protocols in the protocol directory table whose value of
     protocolDirHostConfig is equal to supportedOn(3), and
     will delete any entries whose protocolDirEntry is deleted or
     has a protocolDirHostConfig value of supportedOff(2).

     The probe will add to this table all addresses seen
     as the source or destination address in all packets with no
     MAC errors, and will increment octet and packet counts in the
     table for all packets with no MAC errors."
::= { nlHost 2 }
```

```
nlHostEntry OBJECT-TYPE
  SYNTAX      NlHostEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A conceptual row in the nlHostTable.

     The hlHostControlIndex value in the index identifies the
      hlHostControlEntry on whose behalf this entry was created.
     The protocolDirLocalIndex value in the index identifies the
     network layer protocol of the nlHostAddress.

     An example of the indexing of this entry is
     nlHostOutPkts.1.783495.18.4.128.2.6.6.

     Note that some combinations of index values may result in an
     index that exceeds 128 sub-identifiers in length, which exceeds
     the maximum for the SNMP protocol.  Implementations should take



     care to avoid such combinations."
  INDEX { hlHostControlIndex, nlHostTimeMark,
          protocolDirLocalIndex, nlHostAddress }
  ::= { nlHostTable 1 }

NlHostEntry ::= SEQUENCE {
  nlHostTimeMark             TimeFilter,
  nlHostAddress              OCTET STRING,
  nlHostInPkts               ZeroBasedCounter32,
  nlHostOutPkts              ZeroBasedCounter32,
  nlHostInOctets             ZeroBasedCounter32,
  nlHostOutOctets            ZeroBasedCounter32,
   nlHostOutMacNonUnicastPkts  ZeroBasedCounter32,
  nlHostCreateTime           LastCreateTime
}

nlHostTimeMark OBJECT-TYPE
  SYNTAX      TimeFilter
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A TimeFilter for this entry.  See the TimeFilter textual
     convention to see how this works."
  ::= { nlHostEntry 1 }

nlHostAddress OBJECT-TYPE
```

```
  SYNTAX      OCTET STRING  (SIZE (1..255))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The network address for this nlHostEntry.

     This is represented as an octet string with
     specific semantics and length as identified
     by the protocolDirLocalIndex component of the index.

     For example, if the protocolDirLocalIndex indicates an
     encapsulation of IP, this object is encoded as a length
     octet of 4, followed by the 4 octets of the IP address,
     in network byte order."
  ::= { nlHostEntry 2 }

nlHostInPkts OBJECT-TYPE

  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of packets without errors transmitted to



     this address since it was added to the nlHostTable.  Note that
     this is the number of link-layer packets, so if a single
     network-layer packet is fragmented into several link-layer
     frames, this counter is incremented several times."
  ::= { nlHostEntry 3 }

nlHostOutPkts OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of packets without errors transmitted by
     this address since it was added to the nlHostTable.  Note that
     this is the number of link-layer packets, so if a single
     network-layer packet is fragmented into several link-layer
     frames, this counter is incremented several times."
  ::= { nlHostEntry 4 }

nlHostInOctets OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS
```

read-only
STATUS current
DESCRIPTION
"The number of octets transmitted to this address
since it was added to the nlHostTable (excluding
framing bits, but including FCS octets), excluding
octets in packets that contained errors.

Note that this doesn't count just those octets in the particular
protocol frames but includes the entire packet that contained
the protocol."
::= { nlHostEntry 5 }

nlHostOutOctets OBJECT-TYPE
SYNTAX ZeroBasedCounter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of octets transmitted by this address
since it was added to the nlHostTable (excluding
framing bits, but including FCS octets), excluding
octets in packets that contained errors.

Note that this doesn't count just those octets in the particular
protocol frames but includes the entire packet that contained
the protocol."
::=
{ nlHostEntry 6 }

nlHostOutMacNonUnicastPkts OBJECT-TYPE
SYNTAX ZeroBasedCounter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of packets without errors transmitted by this
address that were directed to any MAC broadcast addresses
or to any MAC multicast addresses since this host was
added to the nlHostTable. Note that this is the number of
link-layer packets, so if a single network-layer packet is
fragmented into several link-layer frames, this counter is
incremented several times."
::= { nlHostEntry 7 }

nlHostCreateTime OBJECT-TYPE
SYNTAX LastCreateTime

```
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The value of sysUpTime when this entry was last activated.
     This can be used by the management station to ensure that the
     entry has not been deleted and recreated between polls."
  ::= { nlHostEntry 8 }

--
-- Network Layer Matrix
 Group
--
-- Counts the amount of traffic sent between each pair of network
-- addresses discovered by the probe.
-- Note that while the hlMatrixControlTable also has objects that
-- control optional alMatrixTables, implementation of the
-- alMatrixTables is not required to fully implement this group.

hlMatrixControlTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF HlMatrixControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A list of higher-layer (i.e., non-MAC) matrix control entries.

     These entries will enable the collection of the network- and
     application-level matrix tables containing conversation
     statistics indexed by pairs of network addresses.
     Both the network- and application-level matrix tables are
     controlled by this table so that they will both be created
     and deleted at the same time, further increasing the ease with
     which they can be implemented as a single datastore.  (Note that
      if an implementation stores application-layer matrix records




     in memory, it can derive network-layer matrix records from
     them.)

     Entries in the nlMatrixSDTable and nlMatrixDSTable will be
     created on behalf of each entry in this table.  Additionally,
     if this probe implements the alMatrix tables, entries in the
     alMatrix tables will be created on behalf of each entry in
     this table."
  ::= { nlMatrix 1 }

hlMatrixControlEntry OBJECT-TYPE
  SYNTAX      HlMatrixControlEntry
```

```
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A conceptual row in the hlMatrixControlTable.

     An example of indexing of this entry is
     hlMatrixControlNlDroppedFrames.1"
  INDEX { hlMatrixControlIndex }
  ::= { hlMatrixControlTable 1 }

HlMatrixControlEntry ::= SEQUENCE {
  hlMatrixControlIndex              Integer32,
  hlMatrixControlDataSource         DataSource,
  hlMatrixControlNlDroppedFrames
      Counter32,
  hlMatrixControlNlInserts          Counter32,
  hlMatrixControlNlDeletes          Counter32,
  hlMatrixControlNlMaxDesiredEntries  Integer32,
  hlMatrixControlAlDroppedFrames    Counter32,
  hlMatrixControlAlInserts          Counter32,
  hlMatrixControlAlDeletes          Counter32,
  hlMatrixControlAlMaxDesiredEntries  Integer32,
  hlMatrixControlOwner              OwnerString,
  hlMatrixControlStatus             RowStatus
}

hlMatrixControlIndex OBJECT-TYPE
  SYNTAX      Integer32 (1..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "An index that uniquely identifies an entry in the
     hlMatrixControlTable.  Each such entry defines
     a function that discovers conversations on a particular
     interface and places statistics about them in the
     nlMatrixSDTable and the nlMatrixDSTable, and optionally the
     alMatrixSDTable and alMatrixDSTable, on
 behalf of this




     hlMatrixControlEntry."
  ::= { hlMatrixControlEntry 1 }

hlMatrixControlDataSource OBJECT-TYPE
  SYNTAX      DataSource
  MAX-ACCESS  read-create
  STATUS      current
```

DESCRIPTION
"The source of the data for the associated matrix tables.

The statistics in this group reflect all packets
on the local network segment attached to the
identified interface.

This object may not be modified if the associated
hlMatrixControlStatus object is equal to active(1)."
::= { hlMatrixControlEntry 2 }

hlMatrixControlNlDroppedFrames OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The total number of frames that were received by the probe
and therefore not accounted for in the *StatsDropEvents, but
that the probe chose not to count for this entry for
whatever reason. Most often, this event occurs when the probe
is out of
some resources and decides to shed load from this
collection.

This count does not include packets that were not counted
because they had MAC-layer errors.

Note that if the nlMatrixTables are inactive because no
protocols are enabled in the protocol directory, this value
should be 0.

Note that, unlike the dropEvents counter, this number is the
exact number of frames dropped."
::= { hlMatrixControlEntry 3 }

hlMatrixControlNlInserts OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of times an nlMatrix entry has been
inserted into the nlMatrix tables. If an entry is inserted,

then deleted, and then inserted, this counter will be
incremented by 2. The addition of a conversation into both
the nlMatrixSDTable and nlMatrixDSTable shall be counted as

two insertions (even though every addition into one table must
be accompanied by an insertion into the other).

To allow for efficient implementation strategies, agents may
delay updating this object for short periods of time. For
example, an implementation strategy may allow internal
data structures to differ from those visible via SNMP for
short periods of time. This counter may reflect the internal
data structures for those short periods of time.

Note that the sum of then nlMatrixSDTable and nlMatrixDSTable
sizes can be determined by subtracting
hlMatrixControlNlDeletes from hlMatrixControlNlInserts."
::= { hlMatrixControlEntry 4 }

hlMatrixControlNlDeletes OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of times an nlMatrix entry has been
deleted from the nlMatrix tables (for any reason). If an
entry is deleted, then inserted, and then deleted, this
counter
will be incremented by 2. The deletion of a
conversation from both the nlMatrixSDTable and nlMatrixDSTable
shall be counted as two deletions (even though every deletion
from one table must be accompanied by a deletion from the
other).

To allow for efficient implementation strategies, agents may
delay updating this object for short periods of time. For
example, an implementation strategy may allow internal
data structures to differ from those visible via SNMP for
short periods of time. This counter may reflect the internal
data structures for those short periods of time.

Note that the table size can be determined by subtracting
hlMatrixControlNlDeletes from hlMatrixControlNlInserts."
::= { hlMatrixControlEntry 5 }

hlMatrixControlNlMaxDesiredEntries OBJECT-TYPE
SYNTAX Integer32 (-1..2147483647)
MAX-ACCESS read-create
STATUS current
DESCRIPTION

"The
maximum number of entries that are desired in the
nlMatrix tables on behalf of this control entry. The probe
will not create more than this number of associated entries in
the table but may choose to create fewer entries in this
table for any reason, including the lack of resources.

If this object is set to a value less than the current number
of entries, enough entries are chosen in an
implementation-dependent manner and deleted so that the number
of entries in the table equals the value of this object.

If this value is set to -1, the probe may create any number
of entries in this table. If the associated
hlMatrixControlStatus object is equal to 'active', this
object may not be modified.

This object may be used to control how resources are allocated
on the probe for the various RMON functions."
::= { hlMatrixControlEntry 6 }

hlMatrixControlAlDroppedFrames OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The total number of frames that were received by the probe
and therefore not accounted for in the *StatsDropEvents, but
that the probe chose not to count for this entry for
whatever reason. Most often, this event occurs when the probe
is out of some resources and decides to shed load from this
collection.

This count does not include packets that were not counted
because they had MAC-layer errors.

Note that if the alMatrixTables are not implemented or are
inactive because no protocols are enabled in the protocol
directory, this value should be 0.

Note that, unlike the dropEvents counter, this number is the
exact number of frames dropped."
::= { hlMatrixControlEntry 7 }

hlMatrixControlAlInserts OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only

STATUS current
DESCRIPTION

"The number of times an alMatrix entry has been
inserted into the alMatrix tables. If an entry is inserted,
then deleted, and then inserted, this counter will be
incremented by 2. The addition of a conversation into both
the alMatrixSDTable and alMatrixDSTable shall be counted as
two insertions (even though every addition into one table must
be accompanied by an insertion into the other).

To allow for efficient implementation strategies, agents may
delay updating this object for short periods of time. For
example, an implementation strategy may allow internal
data structures to differ from those visible via SNMP for
short periods of time. This counter may reflect the internal
data structures for those short periods of time.

Note that the table size can be determined by subtracting
hlMatrixControlAlDeletes from hlMatrixControlAlInserts."
::= { hlMatrixControlEntry
8 }

hlMatrixControlAlDeletes OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of times an alMatrix entry has been
deleted from the alMatrix tables. If an entry is deleted,
then inserted, and then deleted, this counter will be
incremented by 2. The deletion of a conversation from both
the alMatrixSDTable and alMatrixDSTable shall be counted as
two deletions (even though every deletion from one table must
be accompanied by a deletion from the other).

To allow for efficient implementation strategies, agents may
delay updating this object for short periods of time. For
example, an implementation strategy may allow internal
data structures to differ from those visible via SNMP for
short periods of time. This counter may reflect the internal
data structures for those short periods of time.

Note
that the table size can be determined by subtracting
hlMatrixControlAlDeletes from hlMatrixControlAlInserts."

::= { hlMatrixControlEntry 9 }

hlMatrixControlAlMaxDesiredEntries OBJECT-TYPE
SYNTAX Integer32 (-1..2147483647)
MAX-ACCESS read-create
STATUS current
DESCRIPTION

"The maximum number of entries that are desired in the alMatrix tables on behalf of this control entry. The probe will not create more than this number of associated entries in the table but may choose to create fewer entries in this table for any reason, including the lack of resources.

If this object is set to a value less than the current number of entries, enough entries are chosen in an implementation-dependent manner and deleted so that the number of entries in the table equals the value of this object.

If this value is set to -1, the probe may create any number of entries in this
table. If the associated
hlMatrixControlStatus object is equal to 'active', this object may not be modified.

This object may be used to control how resources are allocated on the probe for the various RMON functions."
::= { hlMatrixControlEntry 10 }

hlMatrixControlOwner OBJECT-TYPE
SYNTAX OwnerString
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The entity that configured this entry and is therefore using the resources assigned to it."
::= { hlMatrixControlEntry 11 }

hlMatrixControlStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The status of this hlMatrixControlEntry.

An entry may not exist in the active state unless all

```
      objects in the entry have an appropriate value.

      If this object is not equal to active(1), all
      associated entries in the nlMatrixSDTable,
      nlMatrixDSTable, alMatrixSDTable,
 and alMatrixDSTable
      shall be deleted by the agent."
  ::= { hlMatrixControlEntry 12 }

nlMatrixSDTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF NlMatrixSDEntry
  MAX-ACCESS  not-accessible



  STATUS      current
  DESCRIPTION
      "A list of traffic matrix entries that collect statistics for
      conversations between two network-level addresses.  This table
      is indexed first by the source address and then by the
      destination address to make it convenient to collect all
      conversations from a particular address.

      The probe will populate this table for all network layer
      protocols in the protocol directory table whose value of
      protocolDirMatrixConfig is equal to supportedOn(3), and
      will delete any entries whose protocolDirEntry is deleted or
      has a protocolDirMatrixConfig value of supportedOff(2).

      The probe will add to this table all pairs of addresses
      seen in all packets with no
 MAC errors and will increment
      octet and packet counts in the table for all packets with no
      MAC errors.

      Further, this table will only contain entries that have a
      corresponding entry in the nlMatrixDSTable with the same
      source address and destination address."
  ::= { nlMatrix 2 }

nlMatrixSDEntry OBJECT-TYPE
  SYNTAX      NlMatrixSDEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A conceptual row in the nlMatrixSDTable.

      The hlMatrixControlIndex value in the index identifies the
```

hlMatrixControlEntry on whose behalf this entry was created.
The protocolDirLocalIndex value in the index identifies the
network-layer protocol of the nlMatrixSDSourceAddress and
nlMatrixSDDestAddress.

An example of the indexing of this table is
nlMatrixSDPkts.1.783495.18.4.128.2.6.6.4.128.2.6.7.

Note that some combinations of index values may result in an

index that exceeds 128 sub-identifiers in length, which exceeds
the maximum for the SNMP protocol. Implementations should take
care to avoid such combinations."
INDEX { hlMatrixControlIndex, nlMatrixSDTimeMark,
protocolDirLocalIndex,
nlMatrixSDSourceAddress, nlMatrixSDDestAddress }
::= { nlMatrixSDTable 1 }

```
NlMatrixSDEntry ::= SEQUENCE {
  nlMatrixSDTimeMark            TimeFilter,
  nlMatrixSDSourceAddress       OCTET STRING,
  nlMatrixSDDestAddress         OCTET STRING,
  nlMatrixSDPkts              ZeroBasedCounter32,
  nlMatrixSDOctets            ZeroBasedCounter32,
  nlMatrixSDCreateTime          LastCreateTime
}

nlMatrixSDTimeMark OBJECT-TYPE
  SYNTAX      TimeFilter
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A TimeFilter for this entry.  See the TimeFilter textual
     convention to see how this works."
  ::= { nlMatrixSDEntry 1 }

nlMatrixSDSourceAddress OBJECT-TYPE
   SYNTAX      OCTET STRING  (SIZE (1..255))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The network source address for this nlMatrixSDEntry.

     This is represented as an octet string with
     specific semantics and length as identified
     by the protocolDirLocalIndex component of the index.
```

For example, if the protocolDirLocalIndex indicates an
encapsulation of IP, this object is encoded as a length
octet of 4, followed by the 4 octets of the IP address,
in network byte order."
::= { nlMatrixSDEntry 2 }

nlMatrixSDDestAddress OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (1..255))
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The network destination address for this
nlMatrixSDEntry.

This is represented as an octet string with
specific semantics and length as identified
by the protocolDirLocalIndex component of the index.

For example, if the protocolDirLocalIndex indicates an

encapsulation of IP, this object is encoded as a length
octet of 4, followed by the 4 octets of the IP address,
in network byte order."
::= { nlMatrixSDEntry 3 }

nlMatrixSDPkts OBJECT-TYPE
SYNTAX ZeroBasedCounter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of packets without errors transmitted from the
source address to the destination address since this entry was
added to the nlMatrixSDTable. Note that this is the number of
link-layer packets, so if a single network-layer packet is
fragmented into several link-layer frames, this counter is
incremented several times."
::= { nlMatrixSDEntry 4 }

nlMatrixSDOctets OBJECT-TYPE
SYNTAX ZeroBasedCounter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of octets transmitted from the source address to

the destination address since this entry was added to the
nlMatrixSDTable (excluding framing bits, but
including FCS octets), excluding octets in packets that
contained errors.

Note that this doesn't count just those octets in the particular
protocol frames but includes the entire packet that contained
the protocol."
::= { nlMatrixSDEntry 5 }

nlMatrixSDCreateTime OBJECT-TYPE
SYNTAX LastCreateTime
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime when this entry was last activated.
This can be used by the management station to ensure that the
entry has not been deleted and recreated between polls."
::= { nlMatrixSDEntry 6 }

-- Traffic matrix tables from destination to source

nlMatrixDSTable OBJECT-TYPE

SYNTAX SEQUENCE OF NlMatrixDSEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"A list of traffic matrix
entries that collect statistics for
conversations between two network-level addresses. This table
is indexed first by the destination address and then by the
source address to make it convenient to collect all
conversations to a particular address.

The probe will populate this table for all network layer
protocols in the protocol directory table whose value of
protocolDirMatrixConfig is equal to supportedOn(3), and
will delete any entries whose protocolDirEntry is deleted or
has a protocolDirMatrixConfig value of supportedOff(2).

The probe will add to this table all pairs of addresses
seen in all packets with no MAC errors and will increment
octet and packet counts in the table for all packets with no
MAC errors.

```
      Further, this table will only contain entries that have a
      corresponding entry in the nlMatrixSDTable with the same
      source address and destination
 address."
  ::= { nlMatrix 3 }

nlMatrixDSEntry OBJECT-TYPE
  SYNTAX      NlMatrixDSEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A conceptual row in the nlMatrixDSTable.

      The hlMatrixControlIndex value in the index identifies the
      hlMatrixControlEntry on whose behalf this entry was created.
      The protocolDirLocalIndex value in the index identifies the
      network-layer protocol of the nlMatrixDSSourceAddress and
      nlMatrixDSDestAddress.

      An example of the indexing of this table is
      nlMatrixDSPkts.1.783495.18.4.128.2.6.7.4.128.2.6.6.

      Note that some combinations of index values may result in an
      index that exceeds 128 sub-identifiers in length, which exceeds
      the maximum for the SNMP protocol.  Implementations should take
      care to avoid such combinations."
  INDEX { hlMatrixControlIndex, nlMatrixDSTimeMark,
          protocolDirLocalIndex,



          nlMatrixDSDestAddress,
 nlMatrixDSSourceAddress }
  ::= { nlMatrixDSTable 1 }

NlMatrixDSEntry ::= SEQUENCE {
  nlMatrixDSTimeMark              TimeFilter,
  nlMatrixDSSourceAddress          OCTET STRING,
  nlMatrixDSDestAddress            OCTET STRING,
  nlMatrixDSPkts                 ZeroBasedCounter32,
  nlMatrixDSOctets                ZeroBasedCounter32,
  nlMatrixDSCreateTime            LastCreateTime
}

nlMatrixDSTimeMark OBJECT-TYPE
  SYNTAX      TimeFilter
  MAX-ACCESS  not-accessible
```

```
  STATUS      current
  DESCRIPTION
     "A TimeFilter for this entry.  See the TimeFilter textual
     convention to see how this works."
  ::= { nlMatrixDSEntry 1 }

nlMatrixDSSourceAddress OBJECT-TYPE
  SYNTAX      OCTET STRING  (SIZE (1..255))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The network source address for this nlMatrixDSEntry.

     This is represented as an octet string with
     specific semantics and
 length as identified
     by the protocolDirLocalIndex component of the index.

     For example, if the protocolDirLocalIndex indicates an
     encapsulation of IP, this object is encoded as a length
     octet of 4, followed by the 4 octets of the IP address,
     in network byte order."
  ::= { nlMatrixDSEntry 2 }

nlMatrixDSDestAddress OBJECT-TYPE
  SYNTAX      OCTET STRING  (SIZE (1..255))
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "The network destination address for this
     nlMatrixDSEntry.

     This is represented as an octet string with
     specific semantics and length as identified




     by the protocolDirLocalIndex component of the index.

     For example, if the protocolDirLocalIndex indicates an
     encapsulation of IP, this object is encoded as a length
     octet of 4, followed by the 4 octets of the IP address,
     in network byte order."
  ::= { nlMatrixDSEntry 3 }

nlMatrixDSPkts
 OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
```

```
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of packets without errors transmitted from the
     source address to the destination address since this entry was
     added to the nlMatrixDSTable.  Note that this is the number of
     link-layer packets, so if a single network-layer packet is
     fragmented into several link-layer frames, this counter is
     incremented several times."
  ::= { nlMatrixDSEntry 4 }

nlMatrixDSOctets OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of octets transmitted from the source address
     to the destination address since this entry was added to the
     nlMatrixDSTable (excluding framing bits, but
     including FCS octets), excluding octets in packets that
     contained errors.

     Note that this doesn't count just those octets in the particular
      protocol frames but includes the entire packet that contained
     the protocol."
  ::= { nlMatrixDSEntry 5 }

nlMatrixDSCreateTime OBJECT-TYPE
  SYNTAX     LastCreateTime
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The value of sysUpTime when this entry was last activated.
     This can be used by the management station to ensure that the
     entry has not been deleted and recreated between polls."
  ::= { nlMatrixDSEntry 6 }

nlMatrixTopNControlTable OBJECT-TYPE



  SYNTAX      SEQUENCE OF NlMatrixTopNControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A set of parameters that control the creation of a
     report of the top N matrix entries according to
     a selected metric."
```

```
  ::= { nlMatrix 4 }

nlMatrixTopNControlEntry OBJECT-TYPE
  SYNTAX      NlMatrixTopNControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A conceptual row
 in the nlMatrixTopNControlTable.

      An example of the indexing of this table is
      nlMatrixTopNControlDuration.3"
  INDEX { nlMatrixTopNControlIndex }
  ::= { nlMatrixTopNControlTable 1 }

NlMatrixTopNControlEntry ::= SEQUENCE {
  nlMatrixTopNControlIndex            Integer32,
  nlMatrixTopNControlMatrixIndex      Integer32,
  nlMatrixTopNControlRateBase         INTEGER,
  nlMatrixTopNControlTimeRemaining    Integer32,
  nlMatrixTopNControlGeneratedReports Counter32,
  nlMatrixTopNControlDuration         Integer32,
  nlMatrixTopNControlRequestedSize    Integer32,
  nlMatrixTopNControlGrantedSize      Integer32,
  nlMatrixTopNControlStartTime        TimeStamp,
  nlMatrixTopNControlOwner            OwnerString,
  nlMatrixTopNControlStatus           RowStatus
}

nlMatrixTopNControlIndex OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
      "An index that uniquely identifies an entry
       in the nlMatrixTopNControlTable.  Each such
      entry defines one topN report prepared for
      one interface."
  ::= { nlMatrixTopNControlEntry 1 }

nlMatrixTopNControlMatrixIndex OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)



  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
```

```
      "The nlMatrix[SD/DS] table for which a topN report will be
      prepared on behalf of this entry.  The nlMatrix[SD/DS] table
      is identified by the value of the hlMatrixControlIndex
      for that table - that value is used here to identify the
      particular table.

      This object may not be modified if the associated
      nlMatrixTopNControlStatus object is equal to active(1)."
   ::= { nlMatrixTopNControlEntry 2 }

nlMatrixTopNControlRateBase OBJECT-TYPE
   SYNTAX      INTEGER {
                 nlMatrixTopNPkts(1),
                 nlMatrixTopNOctets(2),
                 nlMatrixTopNHighCapacityPkts(3),
                 nlMatrixTopNHighCapacityOctets(4)
               }
   MAX-ACCESS read-create
   STATUS     current
   DESCRIPTION
      "The variable for each nlMatrix[SD/DS] entry that the
      nlMatrixTopNEntries are sorted by, as well as a control
      for the table that the results will be reported in.

      This object may not be modified if the associated
      nlMatrixTopNControlStatus object is equal to active(1).

      If this value is less than or equal to 2, when the report
      is prepared, entries are created in the nlMatrixTopNTable
      associated with this object.
      If this value is greater than or equal to 3, when the report
      is prepared, entries are created in the
      nlMatrixTopNHighCapacityTable associated with this object."
   ::= { nlMatrixTopNControlEntry 3 }

nlMatrixTopNControlTimeRemaining OBJECT-TYPE
   SYNTAX     Integer32 (0..2147483647)
   MAX-ACCESS read-create
   STATUS     current
   DESCRIPTION
      "The number of seconds left
 in the report currently
      being collected.  When this object is modified by
      the management station, a new collection is started,
      possibly aborting a currently running report.  The
      new value is used as the requested duration of this
```

report and is immediately loaded into the associated
nlMatrixTopNControlDuration object.

When the report finishes, the probe will automatically
start another collection with the same initial value
of nlMatrixTopNControlTimeRemaining. Thus, the management
station may simply read the resulting reports repeatedly,
checking the startTime and duration each time to ensure that a
report was not missed or that the report parameters were not
changed.

While the value of this object is non-zero, it decrements
by one per second until it reaches zero. At the time
that this object decrements to zero, the report is made
accessible
in the nlMatrixTopNTable, overwriting any report
that may be there.

When this object is modified by the management station, any
associated entries in the nlMatrixTopNTable shall be deleted.

(Note that this is a different algorithm than the one used
in the hostTopNTable)."
::= { nlMatrixTopNControlEntry 4 }

nlMatrixTopNControlGeneratedReports OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of reports that have been generated by this entry."
::= { nlMatrixTopNControlEntry 5 }

nlMatrixTopNControlDuration OBJECT-TYPE
SYNTAX Integer32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of seconds that this report has collected
during the last sampling interval.

When the associated nlMatrixTopNControlTimeRemaining object is
set, this object shall be set by the probe to the
same
value and shall not be modified until the next
time the nlMatrixTopNControlTimeRemaining is set.

```
      This value shall be zero if no reports have been
      requested for this nlMatrixTopNControlEntry."



  ::= { nlMatrixTopNControlEntry 6 }

nlMatrixTopNControlRequestedSize OBJECT-TYPE
  SYNTAX     Integer32 (0..2147483647)
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
      "The maximum number of matrix entries requested for this report.

      When this object is created or modified, the probe
      should set nlMatrixTopNControlGrantedSize as closely to this
      object as possible for the particular probe
      implementation and available resources."
  DEFVAL { 150 }
  ::= { nlMatrixTopNControlEntry 7 }

nlMatrixTopNControlGrantedSize OBJECT-TYPE
  SYNTAX     Integer32 (0..2147483647)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
      "The maximum number of matrix entries in this report.

      When
 the associated nlMatrixTopNControlRequestedSize object is
      created or modified, the probe should set this
      object as closely to the requested value as
      possible for the particular implementation and
      available resources.  The probe must not lower this
      value except as a side-effect of a set to the associated
      nlMatrixTopNControlRequestedSize object.

      If the value of nlMatrixTopNControlRateBase is equal to
      nlMatrixTopNPkts, when the next topN report is generated,
      matrix entries with the highest value of nlMatrixTopNPktRate
      shall be placed in this table in decreasing order of this rate
      until there is no more room or until there are no more
      matrix entries.

      If the value of nlMatrixTopNControlRateBase is equal to
      nlMatrixTopNOctets, when the next topN report is generated,
      matrix entries with the highest value of nlMatrixTopNOctetRate
```

shall be placed in this table in decreasing
order of this rate
until there is no more room or until there are no more
matrix entries.

It is an implementation-specific matter how entries with the
same value of nlMatrixTopNPktRate or nlMatrixTopNOctetRate are
sorted. It is also an implementation-specific matter as to

whether zero-valued entries are available."
::= { nlMatrixTopNControlEntry 8 }

nlMatrixTopNControlStartTime OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime when this topN report was
last started. In other words, this is the time that
the associated nlMatrixTopNControlTimeRemaining object was
modified to start the requested report or the time
the report was last automatically (re)started.

This object may be used by the management station to
determine whether a report was missed."
::= { nlMatrixTopNControlEntry 9 }

nlMatrixTopNControlOwner
OBJECT-TYPE
SYNTAX OwnerString
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The entity that configured this entry and is
therefore using the resources assigned to it."
::= { nlMatrixTopNControlEntry 10 }

nlMatrixTopNControlStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The status of this nlMatrixTopNControlEntry.

An entry may not exist in the active state unless all
objects in the entry have an appropriate value.

```
      If this object is not equal to active(1), all
      associated entries in the nlMatrixTopNTable shall be deleted
      by the agent."
  ::= { nlMatrixTopNControlEntry 11 }

nlMatrixTopNTable OBJECT-TYPE
  SYNTAX     SEQUENCE OF NlMatrixTopNEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
      "A set of statistics for those network-layer matrix entries




      that have
 counted the highest number of octets or packets."
  ::= { nlMatrix 5 }

nlMatrixTopNEntry OBJECT-TYPE
  SYNTAX     NlMatrixTopNEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
      "A conceptual row in the nlMatrixTopNTable.

      The nlMatrixTopNControlIndex value in the index identifies the
      nlMatrixTopNControlEntry on whose behalf this entry was
      created.

      An example of the indexing of this table is
      nlMatrixTopNPktRate.3.10"
  INDEX { nlMatrixTopNControlIndex, nlMatrixTopNIndex }
  ::= { nlMatrixTopNTable 1 }

NlMatrixTopNEntry ::= SEQUENCE {
  nlMatrixTopNIndex               Integer32,
  nlMatrixTopNProtocolDirLocalIndex Integer32,
  nlMatrixTopNSourceAddress        OCTET STRING,
  nlMatrixTopNDestAddress          OCTET STRING,
  nlMatrixTopNPktRate              Gauge32,
  nlMatrixTopNReversePktRate       Gauge32,
  nlMatrixTopNOctetRate            Gauge32,
  nlMatrixTopNReverseOctetRate
    Gauge32
}

nlMatrixTopNIndex OBJECT-TYPE
```

```
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "An index that uniquely identifies an entry in
     the nlMatrixTopNTable among those in the same report.
     This index is between 1 and N, where N is the
     number of entries in this report.

     If the value of nlMatrixTopNControlRateBase is equal to
     nlMatrixTopNPkts, increasing values of nlMatrixTopNIndex shall
     be assigned to entries with decreasing values of
     nlMatrixTopNPktRate until index N is assigned or there are no
     more nlMatrixTopNEntries.

     If the value of nlMatrixTopNControlRateBase is equal to
     nlMatrixTopNOctets, increasing values of nlMatrixTopNIndex




     shall be assigned to entries with decreasing values of
     nlMatrixTopNOctetRate until index N is assigned or there are
     no more nlMatrixTopNEntries."
  ::= { nlMatrixTopNEntry 1 }

nlMatrixTopNProtocolDirLocalIndex
 OBJECT-TYPE
  SYNTAX     Integer32 (1..2147483647)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The protocolDirLocalIndex of the network-layer protocol of
     this entry's network address."
  ::= { nlMatrixTopNEntry 2 }

nlMatrixTopNSourceAddress OBJECT-TYPE
  SYNTAX     OCTET STRING  (SIZE (1..255))
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The network-layer address of the source host in this
     conversation.

     This is represented as an octet string with
     specific semantics and length as identified
     by the associated nlMatrixTopNProtocolDirLocalIndex.

     For example, if the protocolDirLocalIndex indicates an
```

encapsulation of IP, this object is encoded as a length
octet of 4, followed by the 4 octets of the IP address,
in network byte order."
::= { nlMatrixTopNEntry 3 }

nlMatrixTopNDestAddress OBJECT-TYPE
SYNTAX OCTET
STRING (SIZE (1..255))
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The network-layer address of the destination host in this
conversation.

This is represented as an octet string with
specific semantics and length as identified
by the associated nlMatrixTopNProtocolDirLocalIndex.

For example, if the nlMatrixTopNProtocolDirLocalIndex
indicates an encapsulation of IP, this object is encoded as a
length octet of 4, followed by the 4 octets of the IP address,
in network byte order."

::= { nlMatrixTopNEntry 4 }

nlMatrixTopNPktRate OBJECT-TYPE
SYNTAX Gauge32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of packets seen from the source host
to the destination host during this sampling interval, counted
using the rules for counting the nlMatrixSDPkts object.
If the value of nlMatrixTopNControlRateBase is
nlMatrixTopNPkts,
this variable will be used to sort this
report."
::= { nlMatrixTopNEntry 5 }

nlMatrixTopNReversePktRate OBJECT-TYPE
SYNTAX Gauge32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of packets seen from the destination host to the
source host during this sampling interval, counted

using the rules for counting the nlMatrixSDPkts object. (Note that the corresponding nlMatrixSDPkts object selected is the one whose source address is equal to nlMatrixTopNDestAddress and whose destination address is equal to nlMatrixTopNSourceAddress.)

Note that if the value of nlMatrixTopNControlRateBase is equal to nlMatrixTopNPkts, the sort of topN entries is based entirely on nlMatrixTopNPktRate, and not on the value of this object."

::= { nlMatrixTopNEntry 6 }

nlMatrixTopNOctetRate OBJECT-TYPE
SYNTAX Gauge32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of octets seen from the source host to the destination host during this sampling interval, counted using the rules for counting the nlMatrixSDOctets object. If the value of nlMatrixTopNControlRateBase is nlMatrixTopNOctets, this variable will be used to sort this report."

::= { nlMatrixTopNEntry 7 }

nlMatrixTopNReverseOctetRate OBJECT-TYPE

SYNTAX Gauge32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The number of octets seen from the destination host to the source host during this sampling interval, counted using the rules for counting the nlMatrixDSOctets object. (Note that the corresponding nlMatrixSDOctets object selected is the one whose source address is equal to nlMatrixTopNDestAddress and whose destination address is equal to nlMatrixTopNSourceAddress.)

Note that if the value of nlMatrixTopNControlRateBase is equal to nlMatrixTopNOctets, the sort of topN entries is based entirely on nlMatrixTopNOctetRate, and not on the value of this object."

::= { nlMatrixTopNEntry 8 }

```
-- Application Layer Functions
--
-- The application layer host, matrix, and matrixTopN functions report
-- on protocol usage at the network layer or higher.  Note that the
-- use of the term application layer does not imply that only
-- application-layer protocols are counted, rather it means that
-- protocols up to and including the application layer are supported.

--
-- Application Layer Host Group
--
-- Counts the amount of traffic, by protocol, sent from and to each
-- network address discovered by the probe.
-- Implementation of this group requires implementation of the Network
-- Layer Host Group.

alHostTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF AlHostEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A collection of statistics for a particular
 protocol from a
     particular network address that has been discovered on an
     interface of this device.

     The probe will populate this table for all protocols in the
     protocol directory table whose value of
     protocolDirHostConfig is equal to supportedOn(3), and
     will delete any entries whose protocolDirEntry is deleted or
     has a protocolDirHostConfig value of supportedOff(2).



     The probe will add to this table all addresses
     seen as the source or destination address in all packets with
     no MAC errors and will increment octet and packet counts in
     the table for all packets with no MAC errors.  Further,
     entries will only be added to this table if their address
     exists in the nlHostTable and will be deleted from this table
     if their address is deleted from the nlHostTable."
  ::= { alHost 1 }

alHostEntry OBJECT-TYPE
  SYNTAX      AlHostEntry
  MAX-ACCESS  not-accessible
  STATUS
```

```
    current
  DESCRIPTION
    "A conceptual row in the alHostTable.

    The hlHostControlIndex value in the index identifies the
    hlHostControlEntry on whose behalf this entry was created.
    The first protocolDirLocalIndex value in the index identifies
    the network-layer protocol of the address.
    The nlHostAddress value in the index identifies the network-
    layer address of this entry.
    The second protocolDirLocalIndex value in the index identifies
    the protocol that is counted by this entry.

    An example of the indexing in this entry is
    alHostOutPkts.1.783495.18.4.128.2.6.6.34.

    Note that some combinations of index values may result in an
    index that exceeds 128 sub-identifiers in length, which exceeds
    the maximum for the SNMP protocol.  Implementations should take
    care to avoid such combinations."
  INDEX { hlHostControlIndex, alHostTimeMark,
          protocolDirLocalIndex,
 nlHostAddress,
          protocolDirLocalIndex }
  ::= { alHostTable 1 }

AlHostEntry ::= SEQUENCE {
  alHostTimeMark              TimeFilter,
  alHostInPkts               ZeroBasedCounter32,
  alHostOutPkts               ZeroBasedCounter32,
  alHostInOctets              ZeroBasedCounter32,
  alHostOutOctets             ZeroBasedCounter32,
  alHostCreateTime            LastCreateTime
}

alHostTimeMark OBJECT-TYPE
  SYNTAX      TimeFilter




  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "A TimeFilter for this entry.  See the TimeFilter textual
    convention to see how this works."
  ::= { alHostEntry 1 }

alHostInPkts OBJECT-TYPE
```

```
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The number of packets of this protocol type without errors
      transmitted to this address since it was added to the
      alHostTable.  Note that this is the number
 of link-layer
      packets, so if a single network-layer packet is fragmented
      into several link-layer frames, this counter is incremented
      several times."
  ::= { alHostEntry 2 }

alHostOutPkts OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The number of packets of this protocol type without errors
      transmitted by this address since it was added to the
      alHostTable.  Note that this is the number of link-layer
      packets, so if a single network-layer packet is fragmented
      into several link-layer frames, this counter is incremented
      several times."
   ::= { alHostEntry 3 }

alHostInOctets OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The number of octets transmitted to this address
      of this protocol type since it was added to the
      alHostTable (excluding framing bits, but
 including
      FCS octets), excluding octets in packets that
      contained errors.

      Note that this doesn't count just those octets in the particular
      protocol frames but includes the entire packet that contained
      the protocol."
  ::= { alHostEntry 4 }



alHostOutOctets OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
```

```
  STATUS      current
  DESCRIPTION
      "The number of octets transmitted by this address
      of this protocol type since it was added to the
      alHostTable (excluding framing bits, but including
      FCS octets), excluding octets in packets that
      contained errors.

      Note that this doesn't count just those octets in the particular
      protocol frames but includes the entire packet that contained
      the protocol."
  ::= { alHostEntry 5 }

alHostCreateTime OBJECT-TYPE
  SYNTAX     LastCreateTime
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
      "The value
 of sysUpTime when this entry was last activated.
      This can be used by the management station to ensure that the
      entry has not been deleted and recreated between polls."
  ::= { alHostEntry 6 }

--
-- Application Layer Matrix Group
--
-- Counts the amount of traffic, by protocol, sent between each pair
-- of network addresses discovered by the probe.
-- Implementation of this group requires implementation of the Network
-- Layer Matrix Group.

alMatrixSDTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF AlMatrixSDEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A list of application traffic matrix entries that collect
      statistics for conversations of a particular protocol between
      two network-level addresses.  This table is indexed first by
      the source address and then by the destination address to make
      it convenient to collect all statistics from a particular
      address.

      The probe will populate
 this table for all protocols in the
      protocol directory table whose value of
```

protocolDirMatrixConfig is equal to supportedOn(3), and
will delete any entries whose protocolDirEntry is deleted or
has a protocolDirMatrixConfig value of supportedOff(2).

The probe will add to this table all pairs of addresses for
all protocols seen in all packets with no MAC errors and will
increment octet and packet counts in the table for all packets
with no MAC errors. Further, entries will only be added to
this table if their address pair exists in the nlMatrixSDTable
and will be deleted from this table if the address pair is
deleted from the nlMatrixSDTable."
::= { alMatrix 1 }

alMatrixSDEntry OBJECT-TYPE
SYNTAX AlMatrixSDEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"A conceptual row in the alMatrixSDTable.

The hlMatrixControlIndex value in the index
identifies the
hlMatrixControlEntry on whose behalf this entry was created.
The first protocolDirLocalIndex value in the index identifies
the network-layer protocol of the nlMatrixSDSourceAddress and
nlMatrixSDDestAddress.
The nlMatrixSDSourceAddress value in the index identifies the
network-layer address of the source host in this conversation.
The nlMatrixSDDestAddress value in the index identifies the
network-layer address of the destination host in this
conversation.
The second protocolDirLocalIndex value in the index identifies
the protocol that is counted by this entry.

An example of the indexing of this entry is
alMatrixSDPkts.1.783495.18.4.128.2.6.6.4.128.2.6.7.34.

Note that some combinations of index values may result in an
index that exceeds 128 sub-identifiers in length, which exceeds
the maximum for the SNMP protocol. Implementations should
take
care to avoid such combinations."
INDEX { hlMatrixControlIndex, alMatrixSDTimeMark,
protocolDirLocalIndex,
nlMatrixSDSourceAddress, nlMatrixSDDestAddress,
protocolDirLocalIndex }

```
  ::= { alMatrixSDTable 1 }

AlMatrixSDEntry ::= SEQUENCE {
  alMatrixSDTimeMark              TimeFilter,



  alMatrixSDPkts                 ZeroBasedCounter32,
  alMatrixSDOctets               ZeroBasedCounter32,
  alMatrixSDCreateTime           LastCreateTime
}

alMatrixSDTimeMark OBJECT-TYPE
  SYNTAX     TimeFilter
  MAX-ACCESS  not-accessible
  STATUS     current
  DESCRIPTION
     "A TimeFilter for this entry.  See the TimeFilter textual
     convention to see how this works."
  ::= { alMatrixSDEntry 1 }

alMatrixSDPkts OBJECT-TYPE
  SYNTAX     ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS     current
  DESCRIPTION
     "The number of packets of this protocol type without errors
     transmitted
 from the source address to the destination address
     since this entry was added to the alMatrixSDTable.  Note that
     this is the number of link-layer packets, so if a single
     network-layer packet is fragmented into several link-layer
     frames, this counter is incremented several times."
  ::= { alMatrixSDEntry 2 }

alMatrixSDOctets OBJECT-TYPE
  SYNTAX     ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS     current
  DESCRIPTION
     "The number of octets in packets of this protocol type
     transmitted from the source address to the destination address
     since this entry was added to the alMatrixSDTable (excluding
     framing bits, but including FCS octets), excluding octets
     in packets that contained errors.

     Note that this doesn't count just those octets in the particular
     protocol frames but includes the entire packet that contained
```

```
      the protocol."
  ::= { alMatrixSDEntry 3 }

alMatrixSDCreateTime
 OBJECT-TYPE
  SYNTAX     LastCreateTime
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION



      "The value of sysUpTime when this entry was last activated.
      This can be used by the management station to ensure that the
      entry has not been deleted and recreated between polls."
  ::= { alMatrixSDEntry 4 }

-- Traffic matrix tables from destination to source

alMatrixDSTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF AlMatrixDSEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A list of application traffic matrix entries that collect
      statistics for conversations of a particular protocol between
      two network-level addresses.  This table is indexed first by
      the destination address and then by the source address to make
      it convenient to collect all statistics to a particular
      address.

      The probe will populate this table for all protocols in the
      protocol directory
 table whose value of
      protocolDirMatrixConfig is equal to supportedOn(3), and
      will delete any entries whose protocolDirEntry is deleted or
      has a protocolDirMatrixConfig value of supportedOff(2).

      The probe will add to this table all pairs of addresses for
      all protocols seen in all packets with no MAC errors and will
      increment octet and packet counts in the table for all packets
      with no MAC errors.  Further, entries will only be added to
      this table if their address pair exists in the nlMatrixDSTable
      and will be deleted from this table if the address pair is
      deleted from the nlMatrixDSTable."
  ::= { alMatrix 2 }

alMatrixDSEntry OBJECT-TYPE
```

```
  SYNTAX      AlMatrixDSEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      "A conceptual row in the alMatrixDSTable.

      The hlMatrixControlIndex value in the index identifies the
      hlMatrixControlEntry on whose behalf
 this entry was created.
      The first protocolDirLocalIndex value in the index identifies
      the network-layer protocol of the alMatrixDSSourceAddress and
      alMatrixDSDestAddress.
      The nlMatrixDSDestAddress value in the index identifies the
      network-layer address of the destination host in this



      conversation.
      The nlMatrixDSSourceAddress value in the index identifies the
      network-layer address of the source host in this conversation.
      The second protocolDirLocalIndex value in the index identifies
      the protocol that is counted by this entry.

      An example of the indexing of this entry is
      alMatrixDSPkts.1.783495.18.4.128.2.6.7.4.128.2.6.6.34.

      Note that some combinations of index values may result in an
      index that exceeds 128 sub-identifiers in length, which exceeds
      the maximum for the SNMP protocol.  Implementations should take
      care to avoid such combinations."
  INDEX { hlMatrixControlIndex,
 alMatrixDSTimeMark,
          protocolDirLocalIndex,
          nlMatrixDSDestAddress, nlMatrixDSSourceAddress,
          protocolDirLocalIndex }
  ::= { alMatrixDSTable 1 }

AlMatrixDSEntry ::= SEQUENCE {
  alMatrixDSTimeMark              TimeFilter,
  alMatrixDSPkts                 ZeroBasedCounter32,
  alMatrixDSOctets                ZeroBasedCounter32,
  alMatrixDSCreateTime            LastCreateTime
}

alMatrixDSTimeMark OBJECT-TYPE
  SYNTAX      TimeFilter
  MAX-ACCESS  not-accessible
  STATUS      current
```

```
  DESCRIPTION
     "A TimeFilter for this entry.  See the TimeFilter textual
     convention to see how this works."
  ::= { alMatrixDSEntry 1 }

alMatrixDSPkts OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of packets of this protocol type without errors
     transmitted from the source address to the destination address

    since this entry was added to the alMatrixDSTable.  Note that
     this is the number of link-layer packets, so if a single
     network-layer packet is fragmented into several link-layer
     frames, this counter is incremented several times."
  ::= { alMatrixDSEntry 2 }




alMatrixDSOctets OBJECT-TYPE
  SYNTAX      ZeroBasedCounter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "The number of octets in packets of this protocol type
     transmitted from the source address to the destination address
     since this entry was added to the alMatrixDSTable (excluding
     framing bits, but including FCS octets), excluding octets
     in packets that contained errors.

     Note that this doesn't count just those octets in the particular
     protocol frames but includes the entire packet that contained
     the protocol."
  ::= { alMatrixDSEntry 3 }

alMatrixDSCreateTime OBJECT-TYPE
  SYNTAX     LastCreateTime
  MAX-ACCESS
 read-only
  STATUS     current
  DESCRIPTION
     "The value of sysUpTime when this entry was last activated.
     This can be used by the management station to ensure that the
     entry has not been deleted and recreated between polls."
  ::= { alMatrixDSEntry 4 }
```

```
alMatrixTopNControlTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF AlMatrixTopNControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A set of parameters that control the creation of a
     report of the top N matrix entries according to
     a selected metric."
  ::= { alMatrix 3 }

alMatrixTopNControlEntry OBJECT-TYPE
  SYNTAX      AlMatrixTopNControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "A conceptual row in the alMatrixTopNControlTable.

     An example of the indexing of this table is
     alMatrixTopNControlDuration.3"
  INDEX { alMatrixTopNControlIndex }
  ::= { alMatrixTopNControlTable 1 }




AlMatrixTopNControlEntry
 ::= SEQUENCE {
  alMatrixTopNControlIndex           Integer32,
  alMatrixTopNControlMatrixIndex     Integer32,
  alMatrixTopNControlRateBase        INTEGER,
  alMatrixTopNControlTimeRemaining   Integer32,
  alMatrixTopNControlGeneratedReports Counter32,
  alMatrixTopNControlDuration        Integer32,
  alMatrixTopNControlRequestedSize   Integer32,
  alMatrixTopNControlGrantedSize     Integer32,
  alMatrixTopNControlStartTime       TimeStamp,
  alMatrixTopNControlOwner           OwnerString,
  alMatrixTopNControlStatus          RowStatus
}

alMatrixTopNControlIndex OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "An index that uniquely identifies an entry
     in the alMatrixTopNControlTable.  Each such
```

```
      entry defines one topN report prepared for
      one interface."
   ::= { alMatrixTopNControlEntry 1 }

alMatrixTopNControlMatrixIndex OBJECT-TYPE
    SYNTAX     Integer32 (1..65535)
   MAX-ACCESS read-create
   STATUS     current
   DESCRIPTION
      "The alMatrix[SD/DS] table for which a topN report will be
      prepared on behalf of this entry.  The alMatrix[SD/DS] table
      is identified by the value of the hlMatrixControlIndex
      for that table - that value is used here to identify the
      particular table.

      This object may not be modified if the associated
      alMatrixTopNControlStatus object is equal to active(1)."
   ::= { alMatrixTopNControlEntry 2 }

alMatrixTopNControlRateBase OBJECT-TYPE
   SYNTAX     INTEGER {
                alMatrixTopNTerminalsPkts(1),
                alMatrixTopNTerminalsOctets(2),
                alMatrixTopNAllPkts(3),
                alMatrixTopNAllOctets(4),
                alMatrixTopNTerminalsHighCapacityPkts(5),
                alMatrixTopNTerminalsHighCapacityOctets(6),



                alMatrixTopNAllHighCapacityPkts(7),

              alMatrixTopNAllHighCapacityOctets(8)
               }
   MAX-ACCESS read-create
   STATUS     current
   DESCRIPTION
      "This object controls which alMatrix[SD/DS] entry that the
      alMatrixTopNEntries are sorted by, which view of the matrix
      table that will be used, as well as which table the results
      will be reported in.

      The values alMatrixTopNTerminalsPkts,
      alMatrixTopNTerminalsOctets,
      alMatrixTopNTerminalsHighCapacityPkts, and
      alMatrixTopNTerminalsHighCapacityOctets cause collection
      only from protocols that have no child protocols that are
      counted.  The values alMatrixTopNAllPkts,
```

alMatrixTopNAllOctets, alMatrixTopNAllHighCapacityPkts, and
alMatrixTopNAllHighCapacityOctets cause collection from all
alMatrix entries.

This object may not be modified if the associated
alMatrixTopNControlStatus object is equal to active(1)."
::= { alMatrixTopNControlEntry
3 }

alMatrixTopNControlTimeRemaining OBJECT-TYPE
SYNTAX Integer32 (0..2147483647)
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The number of seconds left in the report currently
being collected. When this object is modified by
the management station, a new collection is started,
possibly aborting a currently running report. The
new value is used as the requested duration of this
report and is immediately loaded into the associated
alMatrixTopNControlDuration object.

When the report finishes, the probe will automatically
start another collection with the same initial value
of alMatrixTopNControlTimeRemaining. Thus, the management
station may simply read the resulting reports repeatedly,
checking the startTime and duration each time to ensure that a
report was not missed or that the report parameters were not
changed.

While the value
of this object is non-zero, it decrements
by one per second until it reaches zero. At the time

that this object decrements to zero, the report is made
accessible in the alMatrixTopNTable, overwriting any report
that may be there.

When this object is modified by the management station, any
associated entries in the alMatrixTopNTable shall be deleted.

(Note that this is a different algorithm than the one used
in the hostTopNTable)."
DEFVAL { 1800 }
::= { alMatrixTopNControlEntry 4 }

```
alMatrixTopNControlGeneratedReports OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of reports that have been generated by this entry."
  ::= { alMatrixTopNControlEntry 5 }

alMatrixTopNControlDuration OBJECT-TYPE
  SYNTAX     Integer32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The number of seconds that this report has collected
      during the last sampling interval.

     When the associated alMatrixTopNControlTimeRemaining object
     is set, this object shall be set by the probe to the
     same value and shall not be modified until the next
     time the alMatrixTopNControlTimeRemaining is set.

     This value shall be zero if no reports have been
     requested for this alMatrixTopNControlEntry."
  ::= { alMatrixTopNControlEntry 6 }

alMatrixTopNControlRequestedSize OBJECT-TYPE
  SYNTAX     Integer32 (0..2147483647)
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "The maximum number of matrix entries requested for this report.

     When this object is created or modified, the probe
     should set alMatrixTopNControlGrantedSize as closely to this
     object as possible for the particular probe
     implementation and available resources."



  DEFVAL { 150 }
  ::= { alMatrixTopNControlEntry 7 }

alMatrixTopNControlGrantedSize OBJECT-TYPE
   SYNTAX     Integer32 (0..2147483647)
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The maximum number of matrix entries in this report.
```

When the associated alMatrixTopNControlRequestedSize object
is created or modified, the probe should set this
object as closely to the requested value as
possible for the particular implementation and
available resources. The probe must not lower this
value except as a side-effect of a set to the associated
alMatrixTopNControlRequestedSize object.

If the value of alMatrixTopNControlRateBase is equal to
alMatrixTopNTerminalsPkts or alMatrixTopNAllPkts, when the
next topN report is generated, matrix entries with the highest
value of alMatrixTopNPktRate shall be placed in this table in
decreasing order of this rate until there is no more room or
until there are no more matrix entries.

If the value of alMatrixTopNControlRateBase
is equal to
alMatrixTopNTerminalsOctets or alMatrixTopNAllOctets, when the
next topN report is generated, matrix entries with the highest
value of alMatrixTopNOctetRate shall be placed in this table
in decreasing order of this rate until there is no more room
or until there are no more matrix entries.

It is an implementation-specific matter how entries with the
same value of alMatrixTopNPktRate or alMatrixTopNOctetRate are
sorted. It is also an implementation-specific matter as to
whether zero-valued entries are available."
::= { alMatrixTopNControlEntry 8 }

alMatrixTopNControlStartTime OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime when this topN report was
last started. In other words, this is the time that
the associated alMatrixTopNControlTimeRemaining object
was modified
to start the requested report or the time
the report was last automatically (re)started.

This object may be used by the management station to
determine whether a report was missed."
::= { alMatrixTopNControlEntry 9 }

```
alMatrixTopNControlOwner OBJECT-TYPE
  SYNTAX     OwnerString
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "The entity that configured this entry and is
     therefore using the resources assigned to it."
  ::= { alMatrixTopNControlEntry 10 }

alMatrixTopNControlStatus OBJECT-TYPE
  SYNTAX     RowStatus
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "The status of this alMatrixTopNControlEntry.

     An entry may not exist in the active state unless all
     objects in the entry have an appropriate value.

     If this object is not equal to active(1), all
     associated entries in the alMatrixTopNTable shall be
     deleted by the agent."
  ::= { alMatrixTopNControlEntry
 11 }

alMatrixTopNTable OBJECT-TYPE
  SYNTAX     SEQUENCE OF AlMatrixTopNEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "A set of statistics for those application-layer matrix
     entries that have counted the highest number of octets or
     packets."
  ::= { alMatrix 4 }

alMatrixTopNEntry OBJECT-TYPE
  SYNTAX     AlMatrixTopNEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "A conceptual row in the alMatrixTopNTable.

     The alMatrixTopNControlIndex value in the index identifies
     the alMatrixTopNControlEntry on whose behalf this entry was
     created.
```

```
      An example of the indexing of this table is
      alMatrixTopNPktRate.3.10"
    INDEX { alMatrixTopNControlIndex, alMatrixTopNIndex }
    ::= { alMatrixTopNTable 1 }

AlMatrixTopNEntry ::= SEQUENCE {
    alMatrixTopNIndex                   Integer32,
    alMatrixTopNProtocolDirLocalIndex   Integer32,

  alMatrixTopNSourceAddress             OCTET STRING,
    alMatrixTopNDestAddress             OCTET STRING,
    alMatrixTopNAppProtocolDirLocalIndex  Integer32,
    alMatrixTopNPktRate                 Gauge32,
    alMatrixTopNReversePktRate          Gauge32,
    alMatrixTopNOctetRate               Gauge32,
    alMatrixTopNReverseOctetRate        Gauge32
  }

alMatrixTopNIndex OBJECT-TYPE
    SYNTAX     Integer32 (1..65535)
    MAX-ACCESS not-accessible
    STATUS     current
    DESCRIPTION
      "An index that uniquely identifies an entry in
      the alMatrixTopNTable among those in the same report.

      This index is between 1 and N, where N is the
      number of entries in this report.

      If the value of alMatrixTopNControlRateBase is equal to
      alMatrixTopNTerminalsPkts or alMatrixTopNAllPkts, increasing
      values of alMatrixTopNIndex shall be assigned to entries with
      decreasing values of alMatrixTopNPktRate until index N is

     assigned or there are no more alMatrixTopNEntries.

      If the value of alMatrixTopNControlRateBase is equal to
      alMatrixTopNTerminalsOctets or alMatrixTopNAllOctets,
      increasing values of alMatrixTopNIndex shall be assigned to
      entries with decreasing values of alMatrixTopNOctetRate until
      index N is assigned or there are no more alMatrixTopNEntries."
    ::= { alMatrixTopNEntry 1 }

alMatrixTopNProtocolDirLocalIndex OBJECT-TYPE
    SYNTAX     Integer32 (1..2147483647)
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
```

"The protocolDirLocalIndex of the network-layer protocol of
this entry's network address."

::= { alMatrixTopNEntry 2 }

alMatrixTopNSourceAddress OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (1..255))
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The network-layer address of the source host in this
conversation.

This is represented as an octet string with
specific semantics and length as identified
by the associated alMatrixTopNProtocolDirLocalIndex.

For example, if the alMatrixTopNProtocolDirLocalIndex
indicates an encapsulation of IP, this object is encoded as a
length octet of 4, followed by the 4 octets of the IP address,
in network byte order."
::= { alMatrixTopNEntry 3 }

alMatrixTopNDestAddress OBJECT-TYPE
SYNTAX OCTET STRING (SIZE (1..255))
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The network-layer address of the destination host in this
conversation.

This is represented as an octet string with
specific semantics and length as identified
by the associated alMatrixTopNProtocolDirLocalIndex.

For example, if the alMatrixTopNProtocolDirLocalIndex
indicates an encapsulation of IP, this object is encoded as a
length octet of 4, followed by the 4 octets of the IP address,
in network
byte order."
::= { alMatrixTopNEntry 4 }

alMatrixTopNAppProtocolDirLocalIndex OBJECT-TYPE
SYNTAX Integer32 (1..2147483647)
MAX-ACCESS read-only
STATUS current

```
  DESCRIPTION
      "The type of the protocol counted by this matrix entry."
  ::= { alMatrixTopNEntry 5 }

alMatrixTopNPktRate OBJECT-TYPE
  SYNTAX     Gauge32



  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
      "The number of packets seen of this protocol from the source
      host to the destination host during this sampling interval,
      counted using the rules for counting the alMatrixSDPkts
      object.

      If the value of alMatrixTopNControlRateBase is
      alMatrixTopNTerminalsPkts or alMatrixTopNAllPkts, this
      variable will be used to sort this report."
  ::= { alMatrixTopNEntry 6 }

alMatrixTopNReversePktRate OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
      "The number of packets
 seen of this protocol from the
      destination host to the source host during this sampling
      interval, counted using the rules for counting the
      alMatrixDSPkts object.  (Note that the corresponding
      alMatrixSDPkts object selected is the one whose source address
      is equal to alMatrixTopNDestAddress and whose destination
      address is equal to alMatrixTopNSourceAddress.)

      Note that if the value of alMatrixTopNControlRateBase is equal
      to alMatrixTopNTerminalsPkts or alMatrixTopNAllPkts, the sort
      of topN entries is based entirely on alMatrixTopNPktRate, and
      not on the value of this object."
  ::= { alMatrixTopNEntry 7 }

alMatrixTopNOctetRate OBJECT-TYPE
  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
      "The number of octets seen of this protocol from the source
```

```
      host to the destination host during this sampling interval,
      counted using the rules for counting
 the alMatrixSDOctets
      object.

      If the value of alMatrixTopNControlRateBase is
      alMatrixTopNTerminalsOctets or alMatrixTopNAllOctets, this
      variable will be used to sort this report."
  ::= { alMatrixTopNEntry 8 }

alMatrixTopNReverseOctetRate OBJECT-TYPE



  SYNTAX     Gauge32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
      "The number of octets seen of this protocol from the
      destination host to the source host during this sampling
      interval, counted using the rules for counting the
      alMatrixDSOctets object.  (Note that the corresponding
      alMatrixSDOctets object selected is the one whose source
      address is equal to alMatrixTopNDestAddress and whose
      destination address is equal to alMatrixTopNSourceAddress.)

      Note that if the value of alMatrixTopNControlRateBase is equal
      to alMatrixTopNTerminalsOctets or alMatrixTopNAllOctets, the
      sort of topN entries is based
 entirely on
      alMatrixTopNOctetRate, and not on the value of this object."
  ::= { alMatrixTopNEntry 9 }

--
-- User History Collection Group (usrHistory)
--
-- The usrHistory group combines mechanisms seen in the alarm and
-- history groups to provide user-specified history collection,
-- utilizing two additional control tables and one additional data
-- table.  This function has traditionally been done by NMS
-- applications, via periodic polling.  The usrHistory group allows
-- this task to be offloaded to an RMON probe.
--
-- Data (an ASN.1 INTEGER based object) is collected in the same
-- manner as any history data table (e.g., etherHistoryTable) except
-- that the user specifies the MIB instances to be collected.  Objects
-- are collected in bucket-groups, with the intent that all MIB
-- instances in the same bucket-group are collected as atomically as
```

-- possible by the RMON probe.
--
-- The usrHistoryControlTable is a one-dimensional read-create table.
-- Each row configures
 a collection of user history buckets, much
-- the same as a historyControlEntry, except that the creation of a
-- row in this table will cause one or more associated instances in
-- the usrHistoryObjectTable to be created. The user specifies the
-- number of bucket elements (rows in the usrHistoryObjectTable)
-- requested, as well as the number of buckets requested.
--
-- The usrHistoryObjectTable is a 2-d read-write table.
-- Each row configures a single MIB instance to be collected.
-- All rows with the same major index constitute a bucket-group.
--
-- The usrHistoryTable is a 3-d read-only table containing

-- the data of associated usrHistoryControlEntries. Each
-- entry represents the value of a single MIB instance
-- during a specific sampling interval (or the rate of
-- change during the interval).
--
-- A sample value is stored in two objects - an absolute value and
-- a status object. This allows numbers from -(2G-1) to +4G to be
-- stored. The status object also indicates
 whether a sample is
-- valid. This allows data collection to continue if periodic
-- retrieval of a particular instance fails for any reason.
--
-- Row Creation Order Relationships
--
-- The static nature of the usrHistoryObjectTable creates
-- some row creation/modification issues. The rows in this
-- table need to be set before the associated
-- usrHistoryControlEntry can be activated.
--
-- Note that the usrHistoryObject entries associated with a
-- particular usrHistoryControlEntry are not required to
-- be active before the control entry is activated. However,
-- the usrHistory data entries associated with an inactive
-- usrHistoryObject entry will be inactive (i.e.,
-- usrHistoryValStatus == valueNotAvailable).
--

usrHistoryControlTable OBJECT-TYPE
  SYNTAX SEQUENCE OF UsrHistoryControlEntry

```
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
     "A list of data-collection configuration entries."
  ::= { usrHistory 1 }

usrHistoryControlEntry OBJECT-TYPE
   SYNTAX UsrHistoryControlEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
     "A list of parameters that set up a group of user-defined
     MIB objects to be sampled periodically (called a
     bucket-group).

     For example, an instance of usrHistoryControlInterval
     might be named usrHistoryControlInterval.1"
  INDEX { usrHistoryControlIndex }
  ::= { usrHistoryControlTable 1 }




UsrHistoryControlEntry ::= SEQUENCE {
  usrHistoryControlIndex            Integer32,
  usrHistoryControlObjects          Integer32,
  usrHistoryControlBucketsRequested  Integer32,
  usrHistoryControlBucketsGranted    Integer32,
  usrHistoryControlInterval         Integer32,
  usrHistoryControlOwner            OwnerString,
  usrHistoryControlStatus           RowStatus
}

usrHistoryControlIndex OBJECT-TYPE
  SYNTAX Integer32 (1..65535)
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
     "An index that uniquely
 identifies an entry in the
     usrHistoryControlTable.  Each such entry defines a
     set of samples at a particular interval for a specified
     set of MIB instances available from the managed system."
  ::= { usrHistoryControlEntry 1 }

usrHistoryControlObjects OBJECT-TYPE
  SYNTAX Integer32 (1..65535)
  MAX-ACCESS read-create
```

```
    STATUS current
    DESCRIPTION
        "The number of MIB objects to be collected
        in the portion of usrHistoryTable associated with this
        usrHistoryControlEntry.

        This object may not be modified if the associated instance
        of usrHistoryControlStatus is equal to active(1)."
    ::= { usrHistoryControlEntry 2 }

usrHistoryControlBucketsRequested OBJECT-TYPE
    SYNTAX Integer32 (1..65535)
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The requested number of discrete time intervals
        over which data is to be saved in the part of the
        usrHistoryTable associated with this usrHistoryControlEntry.

         When this object is created or modified, the probe
        should set usrHistoryControlBucketsGranted as closely to
        this object as possible for the particular probe
        implementation and available resources."
    DEFVAL { 50 }



    ::= { usrHistoryControlEntry 3 }

usrHistoryControlBucketsGranted OBJECT-TYPE
    SYNTAX Integer32 (1..65535)
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of discrete sampling intervals
        over which data shall be saved in the part of
        the usrHistoryTable associated with this
        usrHistoryControlEntry.

        When the associated usrHistoryControlBucketsRequested
        object is created or modified, the probe should set
        this object as closely to the requested value as
        possible for the particular probe implementation and
        available resources.  The probe must not lower this
        value except as a result of a modification to the associated
         usrHistoryControlBucketsRequested object.

        The associated usrHistoryControlBucketsRequested object
```

should be set before or at the same time as this object
to allow the probe to accurately estimate the resources
required for this usrHistoryControlEntry.

There will be times when the actual number of buckets
associated with this entry is less than the value of
this object. In this case, at the end of each sampling
interval, a new bucket will be added to the usrHistoryTable.

When the number of buckets reaches the value of this object
and a new bucket is to be added to the usrHistoryTable,
the oldest bucket associated with this usrHistoryControlEntry
shall be deleted by the agent so that the new bucket can be
added.

When the value of this object changes to a value less than
the current value, entries are deleted from the
usrHistoryTable associated with
this usrHistoryControlEntry.
Enough of the oldest of these entries shall be deleted by the
agent so that their number remains less than or equal to the
new value of this object.

When the value of this object changes to a value greater
than the current value, the number of associated usrHistory
entries may be allowed to grow."
::= { usrHistoryControlEntry 4 }

usrHistoryControlInterval OBJECT-TYPE
SYNTAX Integer32 (1..2147483647)
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The interval in seconds over which the data is
sampled for each bucket in the part of the usrHistory
table associated with this usrHistoryControlEntry.

Because the counters in a bucket may overflow at their
maximum value with no indication, a prudent manager will
take into account the possibility of overflow in any of
the associated counters. It is important to consider the

minimum time in which any counter could overflow on a
particular media type and to set the usrHistoryControlInterval
object to a value less than this interval.

```
      This object may not be modified if the associated
      usrHistoryControlStatus object is equal to active(1)."
   DEFVAL { 1800 }
   ::= { usrHistoryControlEntry 5 }

usrHistoryControlOwner OBJECT-TYPE
   SYNTAX OwnerString
   MAX-ACCESS read-create
   STATUS current
   DESCRIPTION
      "The entity that configured this entry and is
      therefore using the resources assigned to it."
   ::= { usrHistoryControlEntry 6 }

usrHistoryControlStatus OBJECT-TYPE
   SYNTAX RowStatus
   MAX-ACCESS read-create
   STATUS current
   DESCRIPTION
      "The status of this variable history control entry.

      An entry may not exist in the active state unless all
      objects in the entry have an appropriate value.

      If this object is not equal to active(1), all associated
      entries
 in the usrHistoryTable shall be deleted."
   ::= { usrHistoryControlEntry 7 }

-- Object table

usrHistoryObjectTable OBJECT-TYPE



   SYNTAX SEQUENCE OF UsrHistoryObjectEntry
   MAX-ACCESS not-accessible
   STATUS current
   DESCRIPTION
      "A list of data-collection configuration entries."
   ::= { usrHistory 2 }

usrHistoryObjectEntry OBJECT-TYPE
   SYNTAX UsrHistoryObjectEntry
   MAX-ACCESS not-accessible
   STATUS current
   DESCRIPTION
```

"A list of MIB instances to be sampled periodically.

Entries in this table are created when an associated
usrHistoryControlObjects object is created.

The usrHistoryControlIndex value in the index is
that of the associated usrHistoryControlEntry.

For example, an instance of usrHistoryObjectVariable might be
usrHistoryObjectVariable.1.3"
INDEX { usrHistoryControlIndex, usrHistoryObjectIndex }
::= { usrHistoryObjectTable 1 }

```
UsrHistoryObjectEntry ::= SEQUENCE {

  usrHistoryObjectIndex            Integer32,
  usrHistoryObjectVariable         OBJECT IDENTIFIER,
  usrHistoryObjectSampleType       INTEGER
}

usrHistoryObjectIndex OBJECT-TYPE
  SYNTAX Integer32 (1..65535)
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
    "An index used to uniquely identify an entry in the
    usrHistoryObject table.  Each such entry defines a
    MIB instance to be collected periodically."
  ::= { usrHistoryObjectEntry 1 }


usrHistoryObjectVariable OBJECT-TYPE
  SYNTAX OBJECT IDENTIFIER
  MAX-ACCESS read-create
  STATUS current
  DESCRIPTION
    "The object identifier of the particular variable to be
```

sampled.

Only variables that resolve to an ASN.1 primitive type of
Integer32 (Integer32, Counter, Gauge, or TimeTicks) may be
sampled.

Because SNMP access control is articulated entirely in terms
of the contents of MIB views, no access control mechanism

```
 exists that can restrict the value of this object to identify
      only those objects that exist in a particular MIB view.
      Because there is thus no acceptable means of restricting the
      read access that could be obtained through the user history
      mechanism, the probe must only grant write access to this
      object in those views that have read access to all objects on
      the probe.  See USM [RFC3414] and VACM [RFC3415] for more
      information.

      During a set operation, if the supplied variable name is not
      available in the selected MIB view, a badValue error must be
      returned.

      This object may not be modified if the associated
      usrHistoryControlStatus object is equal to active(1)."
  ::= { usrHistoryObjectEntry 2 }

usrHistoryObjectSampleType OBJECT-TYPE
  SYNTAX INTEGER {
           absoluteValue(1),
           deltaValue(2)
         }
  MAX-ACCESS read-create
  STATUS current
  DESCRIPTION
      "The method of sampling the selected variable for storage in
      the usrHistoryTable.

      If the value of this object is absoluteValue(1), the value of
      the selected variable will be copied directly into the history
      bucket.

      If the value of this object is deltaValue(2), the value of the
      selected variable at the last sample will be subtracted from
      the current value, and the difference will be stored in the
      history bucket.  If the associated usrHistoryObjectVariable
      instance could not be obtained at the previous sample
      interval, then a delta sample is not possible, and the value
      of the associated usrHistoryValStatus object for this interval
      will be valueNotAvailable(1).



      This object may not be modified if the associated
      usrHistoryControlStatus object is equal to active(1)."
  ::= { usrHistoryObjectEntry 3 }
```

```
-- data table

usrHistoryTable OBJECT-TYPE
  SYNTAX SEQUENCE OF UsrHistoryEntry
   MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
     "A list of user-defined history entries."
  ::= { usrHistory 3 }

usrHistoryEntry OBJECT-TYPE
  SYNTAX UsrHistoryEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
     "A historical sample of user-defined variables.  This sample
     is associated with the usrHistoryControlEntry that set up the
     parameters for a regular collection of these samples.

     The usrHistoryControlIndex value in the index identifies the
     usrHistoryControlEntry on whose behalf this entry was created.
     The usrHistoryObjectIndex value in the index identifies the
     usrHistoryObjectEntry on whose behalf this entry was created.

     For example, an instance of usrHistoryAbsValue, which represents
     the 14th sample of a variable collected as specified by
     usrHistoryControlEntry.1 and usrHistoryObjectEntry.1.5,
     would be named usrHistoryAbsValue.1.14.5"
   INDEX { usrHistoryControlIndex, usrHistorySampleIndex,
         usrHistoryObjectIndex }
  ::= { usrHistoryTable 1 }

UsrHistoryEntry ::= SEQUENCE {
  usrHistorySampleIndex   Integer32,
  usrHistoryIntervalStart TimeStamp,
  usrHistoryIntervalEnd   TimeStamp,
  usrHistoryAbsValue      Gauge32,
  usrHistoryValStatus     INTEGER
}

usrHistorySampleIndex OBJECT-TYPE
  SYNTAX     Integer32 (1..2147483647)
  MAX-ACCESS not-accessible
  STATUS     current



  DESCRIPTION
```

"An index that uniquely identifies the particular sample this
entry represents among all samples associated with the same
usrHistoryControlEntry. This index starts at 1 and increases
by one as each new sample is taken."
::= { usrHistoryEntry 1 }

usrHistoryIntervalStart OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime at the start of the interval over
which this sample was
measured. If the probe keeps track of
the time of day, it should start the first sample of the
history at a time such that when the next hour of the day
begins, a sample is started at that instant.

Note that following this rule may require that the probe delay
collecting the first sample of the history, as each sample
must be of the same interval. Also note that the sample that
is currently being collected is not accessible in this table
until the end of its interval."
::= { usrHistoryEntry 2 }

usrHistoryIntervalEnd OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime at the end of the interval over which
this sample was measured."
::= { usrHistoryEntry 3 }

usrHistoryAbsValue OBJECT-TYPE
SYNTAX Gauge32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The absolute value (i.e., unsigned value) of the

user-specified statistic during the last sampling period. The
value during the current sampling period is not made available
until the period is completed.

To obtain the true value for this sampling interval, the
associated instance of usrHistoryValStatus must be checked,
and usrHistoryAbsValue adjusted as necessary.

```
      If the MIB instance could not be accessed during the sampling
      interval, then this object will have a value of zero, and the
      associated instance of usrHistoryValStatus will be set to
      'valueNotAvailable(1)'.

      The access control check prescribed in the definition of
      usrHistoryObjectVariable SHOULD be checked for each sampling
      interval.  If this check determines that access should not be
      allowed, then this object will have a value of zero, and the
      associated instance of usrHistoryValStatus will be set to
      'valueNotAvailable(1)'."
  ::= { usrHistoryEntry
 4 }


usrHistoryValStatus OBJECT-TYPE
  SYNTAX INTEGER {
      valueNotAvailable(1),
      valuePositive(2),
      valueNegative(3)
  }
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
      "This object indicates the validity and sign of the data in
      the associated instance of usrHistoryAbsValue.

      If the MIB instance could not be accessed during the sampling
      interval, then 'valueNotAvailable(1)' will be returned.

      If the sample is valid and the actual value of the sample is
      greater than or equal to zero, then 'valuePositive(2)' is
      returned.

      If the sample is valid and the actual value of the sample is
      less than zero, 'valueNegative(3)' will be returned.  The
      associated instance of usrHistoryAbsValue should be multiplied
      by -1 to obtain the true sample value."
  ::= { usrHistoryEntry 5 }

-- The Probe Configuration Group
--
-- This group controls the configuration of various operating
--
```

parameters of the probe.

```
ControlString ::= TEXTUAL-CONVENTION
  STATUS current
  DESCRIPTION
    "This data type is used to communicate with a modem or a

    serial data switch.  A ControlString contains embedded
    commands to control how the device will interact with the
    remote device through the serial interface.  Commands are
    represented as two-character sequences beginning with
    the '^' character.

    The following commands are recognized by the device (note
    that command characters are case sensitive):

      ^s  Send string that follows, which is terminated by the
          next command or the end of string.
      ^c  Delay for the number of seconds that follows.  Toss
          out any data received rather than store it in a
          buffer for parsing.
      ^t  Set timeout to the value represented by the decimal
          digits that follow.  The default timeout is 20

    seconds.  Note that this timeout may be overridden
          by a smaller serialTimeout configured for the
          associated serial interface (see serialConfigTable).
      ^w  Wait for the reply string that follows, which is
          terminated by the next command or the end of string.
          Partial and case-insensitive matching is applied, i.e.,
          if the reply string (any case combination) is found
          anywhere in the received string, then the a match is
          found.  If the current timeout elapses without a match,
          then the remaining control string is ignored.
      ^!  The ^ character.
      ^d  Delay the number of seconds specified by the decimal
          digits that follow.
      ^b  Send break for the number of milliseconds specified by
          the decimal digits that follow.  If no digits follow,
          break will be enforced for 250 milliseconds by default.

     The following ASCII control characters may be inserted into
    the '^s' send string or the '^w' reply string:

      ^@    0x00
      ^A    0x01
```

..
^M 0x0D
..
^Z 0x1A
^[0x1B
^ 0x1C
^] 0x1D
^^ 0x1E
^_ 0x1F

Binary data may also be inserted into the data stream. The control sequence for each byte of binary data is ^0x##, where ## is the hexadecimal representation of the data byte. Two ASCII characters (0-9, a-f, A-F) must follow the '^0x' control prefix. For example, '^0x0D^0x0A' is interpreted as a carriage return followed by a line feed."
SYNTAX OCTET STRING (SIZE (0..255))

probeCapabilities OBJECT-TYPE
SYNTAX BITS {
etherStats(0),
historyControl(1),
etherHistory(2),
alarm(3),
hosts(4),
hostTopN(5),
matrix(6),
filter(7),
capture(8),
event(9),
tokenRingMLStats(10),
tokenRingPStats(11),
tokenRingMLHistory(12),
tokenRingPHistory(13),
ringStation(14),
ringStationOrder(15),
ringStationConfig(16),
sourceRouting(17),
protocolDirectory(18),
protocolDistribution(19),
addressMapping(20),
nlHost(21),
nlMatrix(22),
alHost(23),
alMatrix(24),

```
      usrHistory(25),
      probeConfig(26)
    }
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
      "An indication of the RMON MIB groups supported
      on at least one interface by this probe."
    ::= { probeConfig 1 }

  probeSoftwareRev  OBJECT-TYPE
    SYNTAX     DisplayString (SIZE(0..15))
    MAX-ACCESS read-only




    STATUS     current
    DESCRIPTION
      "The software revision of this device.  This string will have
      a zero length if the revision is unknown."
    ::= { probeConfig 2 }

  probeHardwareRev
   OBJECT-TYPE
    SYNTAX     DisplayString (SIZE(0..31))
    MAX-ACCESS read-only
    STATUS     current
    DESCRIPTION
      "The hardware revision of this device.  This string will have
      a zero length if the revision is unknown."
    ::= { probeConfig 3 }

  probeDateTime  OBJECT-TYPE
    SYNTAX     OCTET STRING (SIZE (0 | 8 | 11))
    MAX-ACCESS read-write
    STATUS     current
    DESCRIPTION
      "Probe's current date and time.

       field  octets  contents               range
       -----  ------  --------              -----
         1      1-2   year                  0..65536
         2       3    month                  1..12
         3       4    day                   1..31
         4       5    hour                  0..23
         5       6    minutes                 0..59
         6       7    seconds                 0..60
                      (use 60 for leap-second)
```

```
         7      8    deci-seconds
        0..9
         8      9    direction from UTC       '+' / '-'
         9     10    hours from UTC           0..11
        10     11    minutes from UTC         0..59

       For example, Tuesday May 26, 1992 at 1:30:15 PM
       EDT would be displayed as:

                1992-5-26,13:30:15.0,-4:0

       Note that if only local time is known, then
       time zone information (fields 8-10) is not
       present, and that if no time information is known, the
       null string is returned."
  ::= { probeConfig 4 }

probeResetControl  OBJECT-TYPE



  SYNTAX     INTEGER {
                running(1),
                warmBoot(2),
                coldBoot(3)
             }

  MAX-ACCESS read-write
  STATUS     current
  DESCRIPTION
      "Setting this object to warmBoot(2) causes the device to
      restart the application software with current configuration
      parameters saved in non-volatile memory.  Setting this

 object to coldBoot(3) causes the device to reinitialize
      configuration parameters in non-volatile memory to default
      values and to restart the application software.  When the device
      is running normally, this variable has a value of
      running(1)."
  ::= { probeConfig 5 }

-- The following download objects do not restrict an implementation
-- from implementing additional download mechanisms (controlled in an
-- implementation-specific manner).  Further, in the case where the RMON
-- agent shares a processor with other types of systems, the
-- implementation is not required to download those non-RMON functions
-- with this mechanism.
```

```
probeDownloadFile  OBJECT-TYPE
  SYNTAX     DisplayString (SIZE(0..127))
  MAX-ACCESS read-write
  STATUS     deprecated
  DESCRIPTION
     "The file name to be downloaded from the TFTP server when a
     download is next requested via this MIB.  This value is set to
     the zero-length string when no file name
has been specified.

     This object has been deprecated, as it has not had enough
     independent implementations to demonstrate interoperability to
     meet the requirements of a Draft Standard."
  ::= { probeConfig 6 }

probeDownloadTFTPServer  OBJECT-TYPE
  SYNTAX     IpAddress
  MAX-ACCESS read-write
  STATUS     deprecated
  DESCRIPTION
     "The IP address of the TFTP server that contains the boot
     image to load when a download is next requested via this MIB.
     This value is set to '0.0.0.0' when no IP address has been




     specified.

     This object has been deprecated, as it has not had enough
     independent implementations to demonstrate interoperability to
     meet the requirements of a Draft Standard."
  ::= { probeConfig 7 }

probeDownloadAction  OBJECT-TYPE
  SYNTAX     INTEGER {
               notDownloading(1),
               downloadToPROM(2),
               downloadToRAM(3)
             }
  MAX-ACCESS
 read-write
  STATUS     deprecated
  DESCRIPTION
     "When this object is set to downloadToRAM(3) or
     downloadToPROM(2), the device will discontinue its
     normal operation and begin download of the image specified
     by probeDownloadFile from the server specified by
     probeDownloadTFTPServer using the TFTP protocol.  If
```

```
      downloadToRAM(3) is specified, the new image is copied
      to RAM only (the old image remains unaltered in the flash
      EPROM).  If downloadToPROM(2) is specified,
      the new image is written to the flash EPROM
      memory after its checksum has been verified to be correct.
      When the download process is completed, the device will
      warm boot to restart the newly loaded application.
      When the device is not downloading, this object will have
      a value of notDownloading(1).

      This object has been deprecated, as it has not had enough
      independent implementations to demonstrate
 interoperability to
      meet the requirements of a Draft Standard."
   ::= { probeConfig 8 }

probeDownloadStatus  OBJECT-TYPE
   SYNTAX     INTEGER {
                 downloadSuccess(1),
                 downloadStatusUnknown(2),
                 downloadGeneralError(3),
                 downloadNoResponseFromServer(4),
                 downloadChecksumError(5),
                 downloadIncompatibleImage(6),
                 downloadTftpFileNotFound(7),
                 downloadTftpAccessViolation(8)
              }
   MAX-ACCESS read-only




   STATUS     deprecated
   DESCRIPTION
      "The status of the last download procedure, if any.  This
      object will have a value of downloadStatusUnknown(2) if no
      download process has been performed.

      This object has been deprecated, as it has not had enough
      independent implementations to demonstrate interoperability to
      meet the requirements of a Draft Standard."
    ::= { probeConfig 9 }

serialConfigTable  OBJECT-TYPE
   SYNTAX     SEQUENCE OF SerialConfigEntry
   MAX-ACCESS not-accessible
   STATUS     deprecated
   DESCRIPTION
      "A table of serial interface configuration entries.  This data
```

```
      will be stored in non-volatile memory and preserved across
      probe resets or power loss.

      This table has been deprecated, as it has not had enough
      independent implementations to demonstrate interoperability to
      meet the requirements of a Draft Standard."
   ::= { probeConfig 10 }

serialConfigEntry  OBJECT-TYPE
   SYNTAX     SerialConfigEntry
   MAX-ACCESS not-accessible
   STATUS     deprecated
   DESCRIPTION
      "A set of configuration parameters for a particular
      serial interface on this device.  If the device has no serial
      interfaces, this table is empty.

      The index is composed of the ifIndex assigned to this serial
      line interface."
   INDEX  { ifIndex }
   ::=
 { serialConfigTable 1 }

SerialConfigEntry ::= SEQUENCE {
   serialMode                INTEGER,
   serialProtocol            INTEGER,
   serialTimeout              Integer32,
   serialModemInitString       ControlString,
   serialModemHangUpString     ControlString,
   serialModemConnectResp      DisplayString,
   serialModemNoConnectResp    DisplayString,
   serialDialoutTimeout        Integer32,



   serialStatus              RowStatus
}

serialMode  OBJECT-TYPE
   SYNTAX     INTEGER {
                 direct(1),
                 modem(2)
              }
   MAX-ACCESS read-create
   STATUS     deprecated
   DESCRIPTION
      "The type of incoming connection to be expected on this
       serial interface."
```

```
  DEFVAL { direct }
  ::= { serialConfigEntry 1 }

serialProtocol  OBJECT-TYPE
  SYNTAX     INTEGER {
               other(1),
               slip(2),
               ppp(3)
             }
  MAX-ACCESS read-create
  STATUS
   deprecated
  DESCRIPTION
     "The type of data link encapsulation to be used on this
     serial interface."
  DEFVAL { slip }
  ::= { serialConfigEntry 2 }

serialTimeout  OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "This timeout value is used when the Management Station has
     initiated the conversation over the serial link.  This variable
     represents the number of seconds of inactivity allowed before
     terminating the connection on this serial interface.  Use the
     serialDialoutTimeout in the case where the probe has initiated
     the connection for the purpose of sending a trap."
  DEFVAL { 300 }
  ::= { serialConfigEntry 3 }

serialModemInitString  OBJECT-TYPE
  SYNTAX     ControlString (SIZE (0..255))
  MAX-ACCESS read-create
  STATUS     deprecated



  DESCRIPTION
     "A control string that controls how a modem attached to this

 serial interface should be initialized.  The initialization
     is performed once during startup and again after each
     connection is terminated if the associated serialMode has the
     value of modem(2).

     A control string that is appropriate for a wide variety of
```

```
      modems is: '^s^MATE0Q0V1X4 S0=1 S2=43^M'."
   ::= { serialConfigEntry 4 }

serialModemHangUpString  OBJECT-TYPE
   SYNTAX     ControlString (SIZE (0..255))
   MAX-ACCESS read-create
   STATUS     deprecated
   DESCRIPTION
      "A control string that specifies how to disconnect a modem
       connection on this serial interface.  This object is only
       meaningful if the associated serialMode has the value
       of modem(2).

       A control string that is appropriate for a wide variety of
       modems is: '^d2^s+++^d2^sATH0^M^d2'."
   ::= { serialConfigEntry 5 }

serialModemConnectResp  OBJECT-TYPE
   SYNTAX     DisplayString (SIZE (0..255))
   MAX-ACCESS read-create

   STATUS     deprecated
   DESCRIPTION
      "An ASCII string containing substrings that describe the
      expected modem connection response code and associated bps
      rate.  The substrings are delimited by the first character
      in the string, for example:
        /CONNECT/300/CONNECT 1200/1200/CONNECT 2400/2400/
        CONNECT 4800/4800/CONNECT 9600/9600
      will be interpreted as:
         response code    bps rate
         CONNECT           300
         CONNECT 1200      1200
         CONNECT 2400      2400
         CONNECT 4800      4800
         CONNECT 9600      9600
      The agent will use the information in this string to adjust
      the bps rate of this serial interface once a modem connection
      is established.

      A value that is appropriate for a wide variety of modems is:



      '/CONNECT/300/CONNECT 1200/1200/CONNECT 2400/2400/
       CONNECT 4800/4800/CONNECT 9600/9600/CONNECT 14400/14400/
      CONNECT
```

```
 19200/19200/CONNECT 38400/38400/."
  ::= { serialConfigEntry 6 }

serialModemNoConnectResp  OBJECT-TYPE
  SYNTAX     DisplayString (SIZE (0..255))
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "An ASCII string containing response codes that may be
     generated by a modem to report the reason why a connection
     attempt has failed.  The response codes are delimited by
     the first character in the string, for example:
       /NO CARRIER/BUSY/NO DIALTONE/NO ANSWER/ERROR/

     If one of these response codes is received via this serial
     interface while attempting to make a modem connection,
     the agent will issue the hang up command as specified by
     serialModemHangUpString.

     A value that is appropriate for a wide variety of modems is:
     '/NO CARRIER/BUSY/NO DIALTONE/NO ANSWER/ERROR/'."
  ::= { serialConfigEntry 7 }

serialDialoutTimeout  OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS
 read-create
  STATUS     deprecated
  DESCRIPTION
     "This timeout value is used when the probe initiates the
     serial connection with the intention of contacting a
     management station.  This variable represents the number
     of seconds of inactivity allowed before terminating the
     connection on this serial interface."
  DEFVAL { 20 }
  ::= { serialConfigEntry 8 }

serialStatus  OBJECT-TYPE
  SYNTAX     RowStatus
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "The status of this serialConfigEntry.

     An entry may not exist in the active state unless all
     objects in the entry have an appropriate value."
  ::= { serialConfigEntry 9 }
```

```
netConfigTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF NetConfigEntry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
     "A table of netConfigEntries.

     This table has been deprecated, as it has not had enough
     independent
 implementations to demonstrate interoperability to
     meet the requirements of a Draft Standard."
  ::= { probeConfig 11 }

netConfigEntry  OBJECT-TYPE
  SYNTAX     NetConfigEntry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
     "A set of configuration parameters for a particular
     network interface on this device.  If the device has no network
     interface, this table is empty.

     The index is composed of the ifIndex assigned to the
     corresponding interface."
  INDEX  { ifIndex }
  ::= { netConfigTable 1 }

NetConfigEntry ::= SEQUENCE {
  netConfigIPAddress         IpAddress,
  netConfigSubnetMask        IpAddress,
  netConfigStatus            RowStatus
}

netConfigIPAddress  OBJECT-TYPE
  SYNTAX     IpAddress
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "The IP address of this Net interface.  The default value
     for this object is 0.0.0.0.  If either the netConfigIPAddress
      or netConfigSubnetMask is 0.0.0.0, then when the device
     boots, it may use BOOTP to try to figure out what these
     values should be.  If BOOTP fails before the device
     can talk on the network, this value must be configured
     (e.g., through a terminal attached to the device).  If BOOTP is
     used, care should be taken to not send BOOTP broadcasts too
```

frequently and to eventually send them very infrequently if no
replies are received."
::= { netConfigEntry 1 }

netConfigSubnetMask OBJECT-TYPE
SYNTAX IpAddress
MAX-ACCESS read-create
STATUS deprecated
DESCRIPTION
"The subnet mask of this Net interface. The default value
for this object is 0.0.0.0. If either the netConfigIPAddress
or netConfigSubnetMask is 0.0.0.0, then when the device
boots, it may use BOOTP to try to figure out what these
values should be. If BOOTP fails before the device
can talk on
the network, this value must be configured
(e.g., through a terminal attached to the device). If BOOTP is
used, care should be taken to not send BOOTP broadcasts too
frequently and to eventually send them very infrequently if no
replies are received."
::= { netConfigEntry 2 }

netConfigStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS deprecated
DESCRIPTION
"The status of this netConfigEntry.

An entry may not exist in the active state unless all
objects in the entry have an appropriate value."
::= { netConfigEntry 3 }

netDefaultGateway OBJECT-TYPE
SYNTAX IpAddress
MAX-ACCESS read-write
STATUS deprecated
DESCRIPTION
"The IP Address of the default gateway. If this value is
undefined or unknown, it shall have the value 0.0.0.0."
::= { probeConfig 12 }

-- Trap Destination Table
--
-- This table defines the destination addresses for traps

```
 generated
-- from the device.  This table maps a community to one or more trap
-- destination entries.
--
-- The same trap will be sent to all destinations specified in the
-- entries that have the same trapDestCommunity as the eventCommunity
-- (as defined by RMON MIB), as long as no access control mechanism
-- (e.g., VACM) prohibits sending to one or more of the destinations.
-- Information in this table will be stored in non-volatile memory.



-- If the device has gone through a hard restart, this information
-- will be reset to its default state.

trapDestTable  OBJECT-TYPE
  SYNTAX     SEQUENCE OF TrapDestEntry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
     "A list of trap destination entries."
  ::= { probeConfig 13 }

trapDestEntry  OBJECT-TYPE
  SYNTAX     TrapDestEntry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
     "This entry includes a destination IP address to which
     traps are sent for this community."
   INDEX { trapDestIndex }
  ::= { trapDestTable 1 }

TrapDestEntry ::= SEQUENCE {
  trapDestIndex             Integer32,
  trapDestCommunity          OCTET STRING,
  trapDestProtocol           INTEGER,
  trapDestAddress            OCTET STRING,
  trapDestOwner              OwnerString,
  trapDestStatus             RowStatus
}

trapDestIndex  OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
     "A value that uniquely identifies this trapDestEntry."
```

```
  ::= { trapDestEntry 1 }

trapDestCommunity  OBJECT-TYPE
  SYNTAX     OCTET STRING (SIZE(0..127))
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "A community to which this destination address belongs.
     This entry is associated with any eventEntries in the RMON
     MIB whose value of eventCommunity is equal to the value of
     this object.  Every time an associated event entry sends a

    trap due to an event, that trap will be sent to each




     address in the trapDestTable with a trapDestCommunity equal
     to eventCommunity, as long as no access control mechanism
     precludes it (e.g., VACM).

     This object may not be modified if the associated
     trapDestStatus object is equal to active(1)."
  ::= { trapDestEntry 2 }

trapDestProtocol OBJECT-TYPE
  SYNTAX     INTEGER {
                ip(1),
                ipx(2)
             }
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "The protocol with which this trap is to be sent."
  ::= { trapDestEntry 3 }

trapDestAddress  OBJECT-TYPE
  SYNTAX     OCTET STRING
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "The destination address for traps on behalf of this entry.

     If the associated trapDestProtocol object is equal to ip(1),
     the encoding of this object is the same as the snmpUDPAddress
     textual
 convention in RFC 3417, 'Transport Mappings for the
      Simple Network Management Protocol (SNMP)' [RFC3417]:
       -- for a SnmpUDPAddress of length 6:
```

```
        --
        -- octets   contents        encoding
        --  1-4     IP-address      network-byte order
        --  5-6     UDP-port        network-byte order

       If the associated trapDestProtocol object is equal to ipx(2),
       the encoding of this object is the same as the snmpIPXAddress
       textual convention in RFC 3417, 'Transport Mappings for the
        Simple Network Management Protocol (SNMP)' [RFC3417]:
        -- for a SnmpIPXAddress of length 12:
        --
        -- octets   contents           encoding
        --  1-4     network-number      network-byte order
        --  5-10    physical-address    network-byte order
        -- 11-12    socket-number       network-byte order

       This object may not be modified if the associated



       trapDestStatus object
 is equal to active(1)."
  ::= { trapDestEntry 4 }

trapDestOwner  OBJECT-TYPE
  SYNTAX     OwnerString
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "The entity that configured this entry and is
     therefore using the resources assigned to it."
  ::= { trapDestEntry 5 }

trapDestStatus  OBJECT-TYPE
  SYNTAX     RowStatus
  MAX-ACCESS read-create
  STATUS     deprecated
  DESCRIPTION
     "The status of this trap destination entry.

     An entry may not exist in the active state unless all
     objects in the entry have an appropriate value."
  ::= { trapDestEntry 6 }

-- Serial Connection Table
--
-- The device may communicate with a management station using
-- SLIP.  In order for the device to send traps via SLIP, it must
```

```
-- be able to initiate a connection over the serial interface.  The
-- serialConnectionTable stores the parameters for such connection
-- initiation.

serialConnectionTable  OBJECT-TYPE
  SYNTAX     SEQUENCE
 OF SerialConnectionEntry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
     "A list of serialConnectionEntries.

     This table has been deprecated, as it has not had enough
     independent implementations to demonstrate interoperability
     to meet the requirements of a Draft Standard."
  ::= { probeConfig 14 }

serialConnectionEntry  OBJECT-TYPE
  SYNTAX     SerialConnectionEntry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION




     "Configuration for a SLIP link over a serial line."
  INDEX { serialConnectIndex }
  ::= { serialConnectionTable 1 }

SerialConnectionEntry ::= SEQUENCE {
  serialConnectIndex                Integer32,
  serialConnectDestIpAddress        IpAddress,
  serialConnectType                 INTEGER,
  serialConnectDialString           ControlString,
  serialConnectSwitchConnectSeq     ControlString,
  serialConnectSwitchDisconnectSeq  ControlString,
   serialConnectSwitchResetSeq      ControlString,
  serialConnectOwner                OwnerString,
  serialConnectStatus               RowStatus
}

serialConnectIndex  OBJECT-TYPE
  SYNTAX     Integer32 (1..65535)
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
     "A value that uniquely identifies this serialConnection
     entry."
```

::= { serialConnectionEntry 1 }

serialConnectDestIpAddress OBJECT-TYPE
SYNTAX IpAddress
MAX-ACCESS read-create
STATUS deprecated
DESCRIPTION
"The IP Address that can be reached at the other end of this
serial connection.

This object may not be modified if the associated
serialConnectStatus object is equal to active(1)."
::= { serialConnectionEntry 2 }

serialConnectType OBJECT-TYPE
SYNTAX INTEGER {
direct(1),
modem(2),
switch(3),
modemSwitch(4)

}
MAX-ACCESS read-create
STATUS deprecated
DESCRIPTION

"The type of outgoing connection to be made. If this object
has the value direct(1), then a direct serial connection
is assumed. If this object has the value modem(2),
then serialConnectDialString will be used to make a modem
connection. If this object has the value switch(3),
then serialConnectSwitchConnectSeq will be used to establish
the connection over a serial data switch, and
serialConnectSwitchDisconnectSeq will be used to terminate
the connection. If this object has the value
modem-switch(4), then a modem connection will be made first,
followed by the switch connection.

This object may not be modified if the associated
serialConnectStatus object is equal to active(1)."
DEFVAL { direct }
::= { serialConnectionEntry 3 }

serialConnectDialString OBJECT-TYPE
SYNTAX ControlString (SIZE(0..255))

```
    MAX-ACCESS read-create
    STATUS     deprecated
    DESCRIPTION
       "A control string that specifies how to dial the phone
       number in order to establish a modem connection.  The
       string should include the dialing prefix and suffix.  For
       example: '^s^MATD9,888-1234^M' will instruct the Probe
       to send a carriage return, followed by the dialing prefix
       'ATD', the phone number '9,888-1234', and a carriage
       return as the dialing suffix.

       This object may not be modified if the associated
       serialConnectStatus object is equal to active(1)."
    ::= { serialConnectionEntry 4 }

serialConnectSwitchConnectSeq  OBJECT-TYPE
    SYNTAX     ControlString (SIZE(0..255))
    MAX-ACCESS read-create
    STATUS     deprecated
    DESCRIPTION
       "A control string that specifies how to establish a
       data switch connection.

       This object may not be modified if the associated
       serialConnectStatus object is
  equal to active(1)."
    ::= { serialConnectionEntry 5 }

serialConnectSwitchDisconnectSeq  OBJECT-TYPE
    SYNTAX     ControlString (SIZE(0..255))



    MAX-ACCESS read-create
    STATUS     deprecated
    DESCRIPTION
       "A control string that specifies how to terminate a
       data switch connection.

       This object may not be modified if the associated
       serialConnectStatus object is equal to active(1)."
    ::= { serialConnectionEntry 6 }

serialConnectSwitchResetSeq  OBJECT-TYPE
    SYNTAX     ControlString (SIZE(0..255))
    MAX-ACCESS read-create
    STATUS     deprecated
    DESCRIPTION
```

"A control string that specifies how to reset a data
switch in the event of a timeout.

This object may not be modified if the associated
serialConnectStatus object is equal to active(1)."
::= { serialConnectionEntry 7 }

serialConnectOwner OBJECT-TYPE
SYNTAX OwnerString
MAX-ACCESS read-create
STATUS deprecated
DESCRIPTION
"The entity that configured this entry and is
therefore using the resources assigned to it."
::= { serialConnectionEntry 8 }

serialConnectStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS deprecated
DESCRIPTION
"The status of this serialConnectionEntry.

If the manager attempts to set this object to active(1) when
the serialConnectType is set to modem(2) or modem-switch(4)
and the serialConnectDialString is a zero-length string or
cannot be correctly parsed as a ConnectString, the set
request will be rejected with badValue(3).

If the manager attempts to set this object to active(1) when
the serialConnectType is set to switch(3) or modem-switch(4)
and the serialConnectSwitchConnectSeq,
the serialConnectSwitchDisconnectSeq, or

the serialConnectSwitchResetSeq is a zero-length string
or cannot be correctly parsed as a ConnectString,
the set
request will be rejected with badValue(3).

An entry may not exist in the active state unless all
objects in the entry have an appropriate value."
::= { serialConnectionEntry 9 }

--
-- Extensions to the RMON 1 MIB for RMON 2 devices
--

```
-- These extensions include the standard LastCreateTime Textual
-- Convention for all control tables, as well as an augmentation of
-- the filter entry that provides variable-length offsets into
-- packets.


-- Each of the following, except for filterDroppedFrames, is a
-- read-only object which, if implemented, automatically appears when
-- the RMON1 row it is associated with is created.

etherStats2Table  OBJECT-TYPE
  SYNTAX     SEQUENCE OF EtherStats2Entry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1."
  ::= { statistics 4 }

etherStats2Entry  OBJECT-TYPE
  SYNTAX     EtherStats2Entry
  MAX-ACCESS not-accessible
  STATUS
    current
  DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1."
  AUGMENTS { etherStatsEntry }
  ::= { etherStats2Table 1 }

EtherStats2Entry ::= SEQUENCE {
  etherStatsDroppedFrames     Counter32,
  etherStatsCreateTime        LastCreateTime
}

etherStatsDroppedFrames OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION



     "The total number of frames that were received by the probe
      and therefore not accounted for in the *StatsDropEvents, but
      that the probe chose not to count for this entry for
      whatever reason.  Most often, this event occurs when the
      probe is out of some resources and decides to shed load from
      this collection.
```

```
      This count does not include packets that were not counted
      because they had MAC-layer errors.

      Note that, unlike the dropEvents counter, this number is the
      exact number of frames dropped."
   ::= { etherStats2Entry
 1 }

etherStatsCreateTime OBJECT-TYPE
   SYNTAX     LastCreateTime
   MAX-ACCESS read-only
   STATUS     current
   DESCRIPTION
      "The value of sysUpTime when this control entry was last
      activated.  This can be used by the management station to
      ensure that the table has not been deleted and recreated
      between polls."
   ::= { etherStats2Entry 2 }

historyControl2Table  OBJECT-TYPE
   SYNTAX     SEQUENCE OF HistoryControl2Entry
   MAX-ACCESS not-accessible
   STATUS     current
   DESCRIPTION
      "Contains the RMON-2 augmentations to RMON-1."
   ::= { history 5 }

historyControl2Entry  OBJECT-TYPE
   SYNTAX     HistoryControl2Entry
   MAX-ACCESS not-accessible
   STATUS     current
   DESCRIPTION
      "Contains the RMON-2 augmentations to RMON-1."
   AUGMENTS { historyControlEntry }
   ::= { historyControl2Table 1 }

HistoryControl2Entry ::= SEQUENCE {
   historyControlDroppedFrames Counter32
}

historyControlDroppedFrames
 OBJECT-TYPE
   SYNTAX     Counter32



   MAX-ACCESS read-only
   STATUS     current
```

```
  DESCRIPTION
    "The total number of frames that were received by the probe
     and therefore not accounted for in the *StatsDropEvents, but
     that the probe chose not to count for this entry for
     whatever reason.  Most often, this event occurs when the
     probe is out of some resources and decides to shed load from
     this collection.

     This count does not include packets that were not counted
     because they had MAC-layer errors.

     Note that, unlike the dropEvents counter, this number is the
     exact number of frames dropped."
  ::= { historyControl2Entry 1 }

hostControl2Table  OBJECT-TYPE
  SYNTAX     SEQUENCE OF HostControl2Entry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1."
  ::= { hosts 4 }

hostControl2Entry  OBJECT-TYPE
  SYNTAX     HostControl2Entry
   MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1."
  AUGMENTS { hostControlEntry }
  ::= { hostControl2Table 1 }

HostControl2Entry ::= SEQUENCE {
  hostControlDroppedFrames    Counter32,
  hostControlCreateTime       LastCreateTime
}

hostControlDroppedFrames OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The total number of frames that were received by the probe
     and therefore not accounted for in the *StatsDropEvents, but
     that the probe chose not to count for this entry for
     whatever reason.  Most often, this event occurs when the
```

```
      probe is out of some resources and decides to shed load from
      this collection.

      This count does not include packets that were not counted
      because they had MAC-layer errors.

      Note that, unlike the dropEvents counter, this number is the
      exact number
 of frames dropped."
  ::= { hostControl2Entry 1 }

hostControlCreateTime OBJECT-TYPE
  SYNTAX     LastCreateTime
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The value of sysUpTime when this control entry was last
     activated.  This can be used by the management station to
     ensure that the table has not been deleted and recreated
     between polls."
  ::= { hostControl2Entry 2 }

matrixControl2Table  OBJECT-TYPE
  SYNTAX     SEQUENCE OF MatrixControl2Entry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1."
  ::= { matrix 4 }

matrixControl2Entry  OBJECT-TYPE
  SYNTAX     MatrixControl2Entry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1."
  AUGMENTS { matrixControlEntry }
  ::= { matrixControl2Table 1 }

MatrixControl2Entry ::= SEQUENCE {
  matrixControlDroppedFrames  Counter32,
   matrixControlCreateTime     LastCreateTime
}

matrixControlDroppedFrames OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
```

```
  STATUS     current
  DESCRIPTION


      "The total number of frames that were received by the probe
      and therefore not accounted for in the *StatsDropEvents, but
      that the probe chose not to count for this entry for
      whatever reason.  Most often, this event occurs when the
      probe is out of some resources and decides to shed load from
      this collection.

      This count does not include packets that were not counted
      because they had MAC-layer errors.

      Note that, unlike the dropEvents counter, this number is the
      exact number of frames dropped."
  ::= { matrixControl2Entry 1 }

matrixControlCreateTime OBJECT-TYPE
  SYNTAX     LastCreateTime
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The value of sysUpTime when this control entry was last

  activated.  This can be used by the management station to
     ensure that the table has not been deleted and recreated
     between polls."
  ::= { matrixControl2Entry 2 }

channel2Table  OBJECT-TYPE
  SYNTAX     SEQUENCE OF Channel2Entry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1."
  ::= { filter 3 }

channel2Entry  OBJECT-TYPE
  SYNTAX     Channel2Entry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1."
  AUGMENTS { channelEntry }
  ::= { channel2Table 1 }
```

```
Channel2Entry ::= SEQUENCE {
  channelDroppedFrames    Counter32,
  channelCreateTime       LastCreateTime
}

channelDroppedFrames OBJECT-TYPE



  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
    "The total number of frames that were received by the probe
     and therefore not accounted for in the *StatsDropEvents,
but
     that the probe chose not to count for this entry for
     whatever reason.  Most often, this event occurs when the
     probe is out of some resources and decides to shed load from
     this collection.

     This count does not include packets that were not counted
     because they had MAC-layer errors.

     Note that, unlike the dropEvents counter, this number is the
     exact number of frames dropped."
  ::= { channel2Entry 1 }

channelCreateTime OBJECT-TYPE
  SYNTAX     LastCreateTime
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
     "The value of sysUpTime when this control entry was last
     activated.  This can be used by the management station to
     ensure that the table has not been deleted and recreated
     between polls."
  ::= { channel2Entry 2 }

tokenRingMLStats2Table  OBJECT-TYPE
  SYNTAX     SEQUENCE OF TokenRingMLStats2Entry
  MAX-ACCESS not-accessible
  STATUS     deprecated

 DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1.

     This table has been deprecated, as it has not had enough
```

```
      independent implementations to demonstrate interoperability
      to meet the requirements of a Draft Standard."
   ::= { statistics 5 }

tokenRingMLStats2Entry  OBJECT-TYPE
   SYNTAX     TokenRingMLStats2Entry
   MAX-ACCESS not-accessible
   STATUS     deprecated
   DESCRIPTION
      "Contains the RMON-2 augmentations to RMON-1."
   AUGMENTS { tokenRingMLStatsEntry }



   ::= { tokenRingMLStats2Table 1 }

TokenRingMLStats2Entry ::= SEQUENCE {
   tokenRingMLStatsDroppedFrames       Counter32,
   tokenRingMLStatsCreateTime          LastCreateTime
}

tokenRingMLStatsDroppedFrames OBJECT-TYPE
   SYNTAX     Counter32
   MAX-ACCESS read-only
   STATUS     deprecated
   DESCRIPTION
      "The total number of frames that were received by the probe
      and therefore not accounted for in the *StatsDropEvents, but
      that the probe
 chose not to count for this entry for
      whatever reason.  Most often, this event occurs when the
      probe is out of some resources and decides to shed load from
      this collection.

      This count does not include packets that were not counted
      because they had MAC-layer errors.

      Note that, unlike the dropEvents counter, this number is the
      exact number of frames dropped."
   ::= { tokenRingMLStats2Entry 1 }

tokenRingMLStatsCreateTime OBJECT-TYPE
   SYNTAX     LastCreateTime
   MAX-ACCESS read-only
   STATUS     deprecated
   DESCRIPTION
      "The value of sysUpTime when this control entry was last
      activated.  This can be used by the management station to
```

```
      ensure that the table has not been deleted and recreated
      between polls."
  ::= { tokenRingMLStats2Entry 2 }

tokenRingPStats2Table  OBJECT-TYPE
  SYNTAX     SEQUENCE OF TokenRingPStats2Entry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
      "Contains the RMON-2 augmentations to RMON-1.

      This table has been deprecated, as it has not had enough
      independent implementations to demonstrate interoperability
      to meet the requirements of a Draft Standard."
  ::= { statistics 6 }



tokenRingPStats2Entry  OBJECT-TYPE
  SYNTAX     TokenRingPStats2Entry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
     "Contains the RMON-2 augmentations to RMON-1."
  AUGMENTS {  tokenRingPStatsEntry }
  ::= { tokenRingPStats2Table 1 }

TokenRingPStats2Entry ::= SEQUENCE {
  tokenRingPStatsDroppedFrames    Counter32,
  tokenRingPStatsCreateTime       LastCreateTime
}

tokenRingPStatsDroppedFrames OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     deprecated
  DESCRIPTION
     "The total number of frames that were received by the probe
      and therefore not accounted for in the *StatsDropEvents, but
      that the probe chose not to count
 for this entry for
      whatever reason.  Most often, this event occurs when the
      probe is out of some resources and decides to shed load from
      this collection.

      This count does not include packets that were not counted
      because they had MAC-layer errors.
```

```
      Note that, unlike the dropEvents counter, this number is the
      exact number of frames dropped."
   ::= { tokenRingPStats2Entry 1 }

tokenRingPStatsCreateTime OBJECT-TYPE
   SYNTAX     LastCreateTime
   MAX-ACCESS read-only
   STATUS     deprecated
   DESCRIPTION
      "The value of sysUpTime when this control entry was last
      activated.  This can be used by the management station to
      ensure that the table has not been deleted and recreated
      between polls."
   ::= { tokenRingPStats2Entry 2 }

ringStationControl2Table  OBJECT-TYPE
   SYNTAX     SEQUENCE OF RingStationControl2Entry
   MAX-ACCESS not-accessible
   STATUS     deprecated



   DESCRIPTION

      "Contains the RMON-2 augmentations to RMON-1.

      This table has been deprecated, as it has not had enough
      independent implementations to demonstrate interoperability
      to meet the requirements of a Draft Standard."
   ::= { tokenRing 7 }

ringStationControl2Entry  OBJECT-TYPE
   SYNTAX     RingStationControl2Entry
   MAX-ACCESS not-accessible
   STATUS     deprecated
   DESCRIPTION
      "Contains the RMON-2 augmentations to RMON-1."
   AUGMENTS { ringStationControlEntry }
   ::= { ringStationControl2Table 1 }

RingStationControl2Entry ::= SEQUENCE {
   ringStationControlDroppedFrames Counter32,
   ringStationControlCreateTime    LastCreateTime
}

ringStationControlDroppedFrames OBJECT-TYPE
   SYNTAX     Counter32
   MAX-ACCESS read-only
```

```
  STATUS     deprecated
  DESCRIPTION
     "The total number of frames that were received by the probe
      and therefore not accounted for in the *StatsDropEvents, but
      that the probe chose not to
 count for this entry for
      whatever reason.  Most often, this event occurs when the
      probe is out of some resources and decides to shed load from
      this collection.

      This count does not include packets that were not counted
      because they had MAC-layer errors.

      Note that, unlike the dropEvents counter, this number is the
      exact number of frames dropped."
  ::= { ringStationControl2Entry 1 }

ringStationControlCreateTime OBJECT-TYPE
  SYNTAX     LastCreateTime
  MAX-ACCESS read-only
  STATUS     deprecated
  DESCRIPTION
     "The value of sysUpTime when this control entry was last
      activated.  This can be used by the management station to




      ensure that the table has not been deleted and recreated
      between polls."
  ::= { ringStationControl2Entry 2 }

sourceRoutingStats2Table  OBJECT-TYPE
  SYNTAX     SEQUENCE OF SourceRoutingStats2Entry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
      "Contains the RMON-2 augmentations to RMON-1.

      This table has been deprecated, as it has not had enough
      independent implementations to demonstrate interoperability
      to meet the requirements of a Draft Standard."
  ::= { tokenRing 8 }

sourceRoutingStats2Entry  OBJECT-TYPE
  SYNTAX     SourceRoutingStats2Entry
  MAX-ACCESS not-accessible
  STATUS     deprecated
  DESCRIPTION
```

```
      "Contains the RMON-2 augmentations to RMON-1."
   AUGMENTS { sourceRoutingStatsEntry }
   ::= { sourceRoutingStats2Table 1 }

SourceRoutingStats2Entry ::= SEQUENCE {
   sourceRoutingStatsDroppedFrames Counter32,
   sourceRoutingStatsCreateTime    LastCreateTime
}

sourceRoutingStatsDroppedFrames OBJECT-TYPE
   SYNTAX     Counter32
   MAX-ACCESS read-only
   STATUS     deprecated
   DESCRIPTION
      "The total number of frames that were received by the probe
      and therefore not accounted for in the *StatsDropEvents, but
      that the probe chose
 not to count for this entry for
      whatever reason.  Most often, this event occurs when the
      probe is out of some resources and decides to shed load from
      this collection.

      This count does not include packets that were not counted
      because they had MAC-layer errors.

      Note that, unlike the dropEvents counter, this number is the
      exact number of frames dropped."
   ::= { sourceRoutingStats2Entry 1 }



sourceRoutingStatsCreateTime OBJECT-TYPE
   SYNTAX     LastCreateTime
   MAX-ACCESS read-only
   STATUS     deprecated
   DESCRIPTION
      "The value of sysUpTime when this control entry was last
      activated.  This can be used by the management station to
      ensure that the table has not been deleted and recreated
      between polls."
   ::= { sourceRoutingStats2Entry 2 }

filter2Table OBJECT-TYPE
   SYNTAX     SEQUENCE OF Filter2Entry
   MAX-ACCESS not-accessible
   STATUS     current
   DESCRIPTION
      "Provides
```

```
 a variable-length packet filter feature to the
      RMON-1 filter table."
  ::= { filter 4 }

filter2Entry OBJECT-TYPE
  SYNTAX     Filter2Entry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
      "Provides a variable-length packet filter feature to the
      RMON-1 filter table."
  AUGMENTS { filterEntry }
  ::= { filter2Table 1 }

Filter2Entry ::= SEQUENCE {
  filterProtocolDirDataLocalIndex     Integer32,
  filterProtocolDirLocalIndex         Integer32
}

filterProtocolDirDataLocalIndex OBJECT-TYPE
  SYNTAX     Integer32 (0..2147483647)
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
      "When this object is set to a non-zero value, the filter that
      it is associated with performs the following operations on
      every packet:

      1) If the packet doesn't match the protocol directory entry
         identified by this object, discard the packet and exit
         (i.e., discard the packet if it
 is not of the identified
         protocol).



      2) If the associated filterProtocolDirLocalIndex is non-zero
         and the packet doesn't match the protocol directory
         entry identified by that object, discard the packet and
         exit.
      3) If the packet matches, perform the regular filter
         algorithm as if the beginning of this named protocol is
         the beginning of the packet, potentially applying the
         filterOffset value to move further into the packet."
  DEFVAL { 0 }
  ::= { filter2Entry 1 }

filterProtocolDirLocalIndex OBJECT-TYPE
```

```
  SYNTAX     Integer32 (0..2147483647)
  MAX-ACCESS read-create
  STATUS     current
  DESCRIPTION
     "When this object is set to a non-zero value, the filter that
     it is associated with will discard the packet if the packet
     doesn't match this protocol directory entry."
  DEFVAL { 0 }
  ::= { filter2Entry 2 }

-- Conformance Macros

rmon2MIBCompliances OBJECT
 IDENTIFIER ::= { rmonConformance 1 }
rmon2MIBGroups      OBJECT IDENTIFIER ::= { rmonConformance 2 }


rmon2MIBCompliance MODULE-COMPLIANCE
  STATUS  current
  DESCRIPTION
     "Describes the requirements for conformance to
     the RMON2 MIB"
  MODULE  -- this module
     MANDATORY-GROUPS { protocolDirectoryGroup,
                        protocolDistributionGroup,
                        addressMapGroup,
                        nlHostGroup,
                        nlMatrixGroup,
                        usrHistoryGroup,
                        probeInformationGroup }

     OBJECT nlMatrixTopNControlRateBase
        SYNTAX      INTEGER {
                      nlMatrixTopNPkts(1),
                      nlMatrixTopNOctets(2)
                    }
        DESCRIPTION



           "Conformance to RMON2 requires only support for these
           values of nlMatrixTopNControlRateBase."

     GROUP   rmon1EnhancementGroup
         DESCRIPTION
           "The rmon1EnhancementGroup is mandatory for systems
           that implement RMON [RFC2819]."
     GROUP  rmon1EthernetEnhancementGroup
```

```
        DESCRIPTION
            "The rmon1EthernetEnhancementGroup is optional and is
            appropriate for systems that implement the Ethernet
            group of RMON [RFC2819]."
    ::= { rmon2MIBCompliances 1 }

rmon2MIBApplicationLayerCompliance MODULE-COMPLIANCE
    STATUS  current
    DESCRIPTION
        "Describes the requirements for conformance to
        the RMON2 MIB with Application-Layer Enhancements."
    MODULE  -- this module
        MANDATORY-GROUPS { protocolDirectoryGroup,
                           protocolDistributionGroup,
                           addressMapGroup,
                           nlHostGroup,
                           nlMatrixGroup,
                           alHostGroup,
                           alMatrixGroup,
                           usrHistoryGroup,
                           probeInformationGroup }

        OBJECT nlMatrixTopNControlRateBase
            SYNTAX      INTEGER {
                          nlMatrixTopNPkts(1),
                          nlMatrixTopNOctets(2)
                        }
            DESCRIPTION
                "Conformance to RMON2 requires only support for these
                values of nlMatrixTopNControlRateBase."

        OBJECT alMatrixTopNControlRateBase
            SYNTAX     INTEGER {
                           alMatrixTopNTerminalsPkts(1),
                           alMatrixTopNTerminalsOctets(2),
                           alMatrixTopNAllPkts(3),
                           alMatrixTopNAllOctets(4)
                         }
            DESCRIPTION
                "Conformance to RMON2 requires only support for these




                values of alMatrixTopNControlRateBase."

        GROUP   rmon1EnhancementGroup
            DESCRIPTION
                "The rmon1EnhancementGroup is mandatory
```

```
 for systems
            that implement RMON [RFC2819]."
        GROUP  rmon1EthernetEnhancementGroup
          DESCRIPTION
            "The rmon1EthernetEnhancementGroup is optional and is
            appropriate for systems that implement the Ethernet
            group of RMON [RFC2819]."
  ::= { rmon2MIBCompliances 2 }


protocolDirectoryGroup OBJECT-GROUP
  OBJECTS { protocolDirLastChange,
            protocolDirLocalIndex, protocolDirDescr,
            protocolDirType, protocolDirAddressMapConfig,
            protocolDirHostConfig, protocolDirMatrixConfig,
            protocolDirOwner, protocolDirStatus }
  STATUS  current
  DESCRIPTION
     "Lists the inventory of protocols the probe has the
     capability of monitoring and allows the addition, deletion,
     and configuration of entries in this list."
  ::= { rmon2MIBGroups 1 }

protocolDistributionGroup OBJECT-GROUP
  OBJECTS { protocolDistControlDataSource,
            protocolDistControlDroppedFrames,
             protocolDistControlCreateTime,
            protocolDistControlOwner, protocolDistControlStatus,
            protocolDistStatsPkts, protocolDistStatsOctets }
  STATUS  current
  DESCRIPTION
     "Collects the relative amounts of octets and packets for the
     different protocols detected on a network segment."
  ::= { rmon2MIBGroups 2 }

addressMapGroup OBJECT-GROUP
  OBJECTS { addressMapInserts, addressMapDeletes,
            addressMapMaxDesiredEntries,
            addressMapControlDataSource,
            addressMapControlDroppedFrames,
            addressMapControlOwner, addressMapControlStatus,
            addressMapPhysicalAddress,
            addressMapLastChange }
  STATUS  current



  DESCRIPTION
```

```
      "Lists MAC address to network address bindings discovered by
      the probe and what interface they were last seen on."
    ::= { rmon2MIBGroups 3 }

nlHostGroup OBJECT-GROUP
    OBJECTS { hlHostControlDataSource,
              hlHostControlNlDroppedFrames, hlHostControlNlInserts,
              hlHostControlNlDeletes,
              hlHostControlNlMaxDesiredEntries,
              hlHostControlAlDroppedFrames, hlHostControlAlInserts,
              hlHostControlAlDeletes,
              hlHostControlAlMaxDesiredEntries, hlHostControlOwner,
              hlHostControlStatus, nlHostInPkts, nlHostOutPkts,
              nlHostInOctets, nlHostOutOctets,
              nlHostOutMacNonUnicastPkts, nlHostCreateTime }
    STATUS  current
    DESCRIPTION
      "Counts the amount of traffic sent from and to each network
      address discovered by the probe.  Note that while the
      hlHostControlTable also has objects that control an optional
      alHostTable, implementation of the alHostTable is not
      required to fully implement this group."
    ::= { rmon2MIBGroups 4 }

nlMatrixGroup OBJECT-GROUP
    OBJECTS { hlMatrixControlDataSource,
              hlMatrixControlNlDroppedFrames,
              hlMatrixControlNlInserts, hlMatrixControlNlDeletes,
              hlMatrixControlNlMaxDesiredEntries,
              hlMatrixControlAlDroppedFrames,
              hlMatrixControlAlInserts, hlMatrixControlAlDeletes,
              hlMatrixControlAlMaxDesiredEntries,
              hlMatrixControlOwner, hlMatrixControlStatus,
              nlMatrixSDPkts, nlMatrixSDOctets, nlMatrixSDCreateTime,
              nlMatrixDSPkts, nlMatrixDSOctets, nlMatrixDSCreateTime,
              nlMatrixTopNControlMatrixIndex,
              nlMatrixTopNControlRateBase,
              nlMatrixTopNControlTimeRemaining,
              nlMatrixTopNControlGeneratedReports,
              nlMatrixTopNControlDuration,
              nlMatrixTopNControlRequestedSize,
              nlMatrixTopNControlGrantedSize,
              nlMatrixTopNControlStartTime,
              nlMatrixTopNControlOwner, nlMatrixTopNControlStatus,
              nlMatrixTopNProtocolDirLocalIndex,
              nlMatrixTopNSourceAddress,
   nlMatrixTopNDestAddress,
              nlMatrixTopNPktRate, nlMatrixTopNReversePktRate,
```

```
            nlMatrixTopNOctetRate, nlMatrixTopNReverseOctetRate }
    STATUS  current
    DESCRIPTION
        "Counts the amount of traffic sent between each pair of
        network addresses discovered by the probe.  Note that while
        the hlMatrixControlTable also has objects that control
        optional alMatrixTables, implementation of the
        alMatrixTables is not required to fully implement this
        group."
     ::= { rmon2MIBGroups 5 }

alHostGroup OBJECT-GROUP
    OBJECTS { alHostInPkts, alHostOutPkts,
            alHostInOctets, alHostOutOctets, alHostCreateTime }
    STATUS  current
    DESCRIPTION
        "Counts the amount of traffic, by protocol, sent from and to
        each network address discovered by the probe.  Implementation
        of this group requires implementation of the Network-Layer
        Host Group."
    ::= { rmon2MIBGroups 6 }

alMatrixGroup
   OBJECT-GROUP
    OBJECTS { alMatrixSDPkts, alMatrixSDOctets, alMatrixSDCreateTime,
            alMatrixDSPkts, alMatrixDSOctets, alMatrixDSCreateTime,
            alMatrixTopNControlMatrixIndex,
            alMatrixTopNControlRateBase,
            alMatrixTopNControlTimeRemaining,
            alMatrixTopNControlGeneratedReports,
            alMatrixTopNControlDuration,
            alMatrixTopNControlRequestedSize,
            alMatrixTopNControlGrantedSize,
            alMatrixTopNControlStartTime,
            alMatrixTopNControlOwner, alMatrixTopNControlStatus,
            alMatrixTopNProtocolDirLocalIndex,
            alMatrixTopNSourceAddress, alMatrixTopNDestAddress,
            alMatrixTopNAppProtocolDirLocalIndex,
            alMatrixTopNPktRate, alMatrixTopNReversePktRate,
            alMatrixTopNOctetRate, alMatrixTopNReverseOctetRate }
    STATUS  current
    DESCRIPTION
        "Counts the amount of traffic, by protocol, sent between each
         pair of network addresses discovered by the
        probe.  Implementation of this group requires implementation
```

```
      of the Network-Layer Matrix Group."
  ::= { rmon2MIBGroups 7 }

usrHistoryGroup OBJECT-GROUP



  OBJECTS { usrHistoryControlObjects,
            usrHistoryControlBucketsRequested,
            usrHistoryControlBucketsGranted,
            usrHistoryControlInterval,
            usrHistoryControlOwner, usrHistoryControlStatus,
            usrHistoryObjectVariable, usrHistoryObjectSampleType,
            usrHistoryIntervalStart, usrHistoryIntervalEnd,
            usrHistoryAbsValue, usrHistoryValStatus }
  STATUS  current
  DESCRIPTION
     "The usrHistoryGroup provides user-defined collection of
     historical information from MIB objects on the probe."
  ::= { rmon2MIBGroups 8 }

probeInformationGroup OBJECT-GROUP
  OBJECTS { probeCapabilities,
            probeSoftwareRev, probeHardwareRev, probeDateTime }
  STATUS  current
   DESCRIPTION
     "This group describes various operating parameters of the
     probe and controls the local time of the probe."
  ::= { rmon2MIBGroups 9 }

probeConfigurationGroup OBJECT-GROUP
  OBJECTS { probeResetControl, probeDownloadFile,
            probeDownloadTFTPServer, probeDownloadAction,
            probeDownloadStatus,
            serialMode, serialProtocol, serialTimeout,
            serialModemInitString, serialModemHangUpString,
            serialModemConnectResp, serialModemNoConnectResp,
            serialDialoutTimeout, serialStatus,
            netConfigIPAddress, netConfigSubnetMask,
            netConfigStatus, netDefaultGateway,
            trapDestCommunity, trapDestProtocol, trapDestAddress,
            trapDestOwner, trapDestStatus,
            serialConnectDestIpAddress, serialConnectType,
            serialConnectDialString, serialConnectSwitchConnectSeq,
            serialConnectSwitchDisconnectSeq,
            serialConnectSwitchResetSeq,
             serialConnectOwner, serialConnectStatus }
  STATUS  deprecated
```

```
  DESCRIPTION
     "This group controls the configuration of various operating
     parameters of the probe.  This group is not referenced by any
     MODULE-COMPLIANCE macro because it is 'grandfathered' from
     more recent MIB review rules that would require it."
  ::= { rmon2MIBGroups 10 }



rmon1EnhancementGroup OBJECT-GROUP
  OBJECTS { historyControlDroppedFrames, hostControlDroppedFrames,
            hostControlCreateTime, matrixControlDroppedFrames,
            matrixControlCreateTime, channelDroppedFrames,
            channelCreateTime, filterProtocolDirDataLocalIndex,
            filterProtocolDirLocalIndex }
  STATUS  current
  DESCRIPTION
     "This group adds some enhancements to RMON-1 that help
     management stations."
  ::= { rmon2MIBGroups 11 }

rmon1EthernetEnhancementGroup OBJECT-GROUP
  OBJECTS { etherStatsDroppedFrames,
 etherStatsCreateTime }
  STATUS  current
  DESCRIPTION
     "This group adds some enhancements to RMON-1 that help
     management stations."
  ::= { rmon2MIBGroups 12 }

rmon1TokenRingEnhancementGroup OBJECT-GROUP
  OBJECTS { tokenRingMLStatsDroppedFrames,
            tokenRingMLStatsCreateTime,
            tokenRingPStatsDroppedFrames, tokenRingPStatsCreateTime,
            ringStationControlDroppedFrames,
            ringStationControlCreateTime,
            sourceRoutingStatsDroppedFrames,
            sourceRoutingStatsCreateTime }
  STATUS  deprecated
  DESCRIPTION
     "This group adds some enhancements to RMON-1 that help
     management stations.  This group is not referenced by any
     MODULE-COMPLIANCE macro because it is 'grandfathered' from
     more recent MIB review rules that would require it."
  ::= { rmon2MIBGroups 13 }
END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/RMON2-MIB
No license file was found, but licenses were detected in source scan.

```
SNA-NAU-MIB DEFINITIONS ::= BEGIN

-- This MIB module contains objects necessary
-- for management of the following SNA devices: PU types 1.0, 2.0, 2.1
-- and LU types 0, 1, 2, 3, 4, 7.  It also contains generic objects
-- which can be used to manage LU 6.2.

-- Naming conventions in this document:
-- The following names are used in object descriptors according to
-- SNA conventions.
-- The name 'PU' or 'Node' is used to describe Node type 1.0, 2.0 or
-- 2.1.
-- The name 'LU' is used to describe Logical Unit of type 0,1,2,3,
-- 4,7 or 6.2.



IMPORTS
    DisplayString, RowStatus, TimeStamp, InstancePointer
        FROM SNMPv2-TC

    Counter32, Gauge32, Integer32, mib-2,
    OBJECT-TYPE, MODULE-IDENTITY, NOTIFICATION-TYPE
        FROM SNMPv2-SMI

    MODULE-COMPLIANCE, OBJECT-GROUP
        FROM SNMPv2-CONF;


snanauMIB MODULE-IDENTITY
    LAST-UPDATED  "9405120900Z"

 ORGANIZATION  "IETF SNA NAU MIB Working Group"
    CONTACT-INFO
        "       Zbigniew Kielczewski
                Eicon Technology Inc.
                2196 32nd Avenue
                Lachine, Que  H8T 3H7
                Canada
                Tel:    1 514 631 2592
                E-mail: zbig@eicon.qc.ca

                Deirdre Kostick
                Bellcore
```

```
                331 Newman Springs Road
                Red Bank, NJ 07701
                Tel:    1 908 758 2642
                E-mail: dck2@mail.bellcore.com

                Kitty Shih (editor)
                Novell
                890 Ross Drive
                Sunnyvale, CA 94089
                Tel:   1 408 747 4305
                E-mail: kmshih@novell.com"
    DESCRIPTION
          "This is the MIB module for objects used to
           manage
 SNA devices."
::= { mib-2 34 }

-- The SNANAU MIB module contains an objects part and a conformance part.
-- Objects are organized into the following groups:
-- (1)snaNode group,
-- (2)snaLU group,
-- (3)snaMgtTools group.

snanauObjects   OBJECT IDENTIFIER ::= { snanauMIB 1 }

 snaNode      OBJECT IDENTIFIER ::= { snanauObjects 1 }
 snaLu        OBJECT IDENTIFIER ::= { snanauObjects 2 }
 snaMgtTools   OBJECT IDENTIFIER ::= { snanauObjects 3}


-- ****************************************************************
-- snaNode group
--
-- It contains Managed Objects related to any type of Node and
-- some specific objects for Node Type 2.0.
-- ****************************************************************


-- ****************************************************************
-- The following table contains generic Node configuration
-- parameters.
-- ****************************************************************

snaNodeAdminTable OBJECT-TYPE
    SYNTAX  SEQUENCE OF SnaNodeAdminEntry
     MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
```

"This table contains objects which describe the
configuration parameters for an SNA Node. Link
specific configuration objects are contained in
a separate MIB module (e.g., SNA DLC MIB)
corresponding to the link type.
The table snaNodeAdminLinkTable contains objects
which identify the relationship between node instances
and link instances.

The entries (i.e., rows) in this table can be created
by either an Agent or a Management Station.
The Management Station can do this through setting
the appropriate value in the snaNodeAdminRowStatus.

The snaNodeAdminRowStatus object describes the
status of an entry and is used to change the status
of an entry. The entry is deleted
by an Agent based
on the value of the snaNodeAdminRowStatus.

The snaNodeAdminState object describes the desired
operational state of a Node and is used to change the
operational state of a Node. For example, such
information may be obtained from a configuration file.

How an Agent or a Management Station obtains the
initial value of each object at creation time is an
implementation specific issue.

For each entry in this table, there is a corresponding
entry in the snaNodeOperTable.
While the objects in this table describe the desired
or configured operational values of the SNA Node, the
actual runtime values are contained in
snaNodeOperTable."
::= { snaNode 1 }

snaNodeAdminEntry OBJECT-TYPE
SYNTAX SnaNodeAdminEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"An entry contains the configuration parameters for
one SNA Node instance. The objects in the entry
have read-create access.
An entry can be created, modified or deleted. The
object snaNodeAdminRowStatus is used (i.e., set) to
create or delete a row entry."

```
    INDEX  { snaNodeAdminIndex }
    ::= { snaNodeAdminTable 1 }

SnaNodeAdminEntry ::= SEQUENCE {
    snaNodeAdminIndex
        Integer32,
    snaNodeAdminName
        DisplayString,
    snaNodeAdminType
        INTEGER,
    snaNodeAdminXidFormat
        INTEGER,
    snaNodeAdminBlockNum
        DisplayString,
    snaNodeAdminIdNum
        DisplayString,
    snaNodeAdminEnablingMethod
        INTEGER,
    snaNodeAdminLuTermDefault
        INTEGER,
    snaNodeAdminMaxLu

   Integer32,
    snaNodeAdminHostDescription
        DisplayString,
    snaNodeAdminStopMethod
        INTEGER,
    snaNodeAdminState
        INTEGER,
    snaNodeAdminRowStatus
        RowStatus
    }

snaNodeAdminIndex OBJECT-TYPE
    SYNTAX  Integer32
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
        "Index used to uniquely identify each Node instance.
        If an Agent creates the entry, then it will assign
        this number otherwise a Management Station
        generates a random number when it reserves the
        entry for creation."
    ::= { snaNodeAdminEntry 1 }

snaNodeAdminName OBJECT-TYPE
    SYNTAX  DisplayString (SIZE(0..17))
    MAX-ACCESS  read-create
```

```
        STATUS  current
        DESCRIPTION
                "The value indicates the desired name of the
                Node for use during Node activation.

      In Type 2.1 networks, this is a fully-qualified name,
                meaning that the Node name is preceded by the NetId (if
                present) with a period as the delimiter.

                A write operation to this object will
                not change the operational value reflected
                in snaNodeOperName until the Node has
                been re-activated (e.g., after the next initialization
                of the SNA services)."
        ::= { snaNodeAdminEntry 2 }

    snaNodeAdminType OBJECT-TYPE
        SYNTAX  INTEGER {
                other(1),
                pu10(2),
                pu20(3),
                t21len(4),
                endNode(5),
                networkNode(6)
                }
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
                "The value indicates the type of SNA Node.

                A write operation to this object will
                not change the operational value reflected

     in snaNodeOperType until the Node has
                been re-activated (e.g., after the next initialization
                of the SNA services)."
        ::= { snaNodeAdminEntry 3 }

    snaNodeAdminXidFormat OBJECT-TYPE
        SYNTAX  INTEGER  {
                format0(1),
                format1(2),
                format3(3)
                }
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
                "The value indicates the type of XID format used for
```

```
            this Node.  Note that there is no format type 2.

            A write operation to this object will
            not change the operational value reflected
            in snaNodeOperAdminXidFormat until the Node has
            been re-activated (e.g., after the next initialization
            of the SNA services)."
        ::= { snaNodeAdminEntry 4 }

snaNodeAdminBlockNum OBJECT-TYPE
        SYNTAX  DisplayString (SIZE(3))
        MAX-ACCESS  read-create
        STATUS
    current
        DESCRIPTION
            "The value indicates the block number for this Node
            instance.  It is the first 3 hexadecimal digits of the
            SNA Node id.

            A write operation to this object will
            not change the operational value reflected
            in snaNodeOperBlockNum until the Node has
            been re-activated (e.g., after the next initialization
            of the SNA services)."
        ::= { snaNodeAdminEntry 5 }

snaNodeAdminIdNum OBJECT-TYPE
        SYNTAX  DisplayString (SIZE(5))
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "The value indicates the ID number for this Node
            instance.  This is the last 5 hexadecimal digits of
            the SNA Node id.

            A write operation to this object will
            not change the operational value reflected
            in snaNodeOperIdNum until the Node has
             been re-activated (e.g., after the next initialization
            of the SNA services)."
        ::= { snaNodeAdminEntry 6 }

snaNodeAdminEnablingMethod OBJECT-TYPE
        SYNTAX  INTEGER {
            other (1),
            startup (2),
            demand (3),
            onlyMS (4)
```

```
            }
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "The value indicates how the Node should be
            activated for the first time.
            The values have the following meanings:

            other (1)  - may be used for proprietary methods
              not listed in this enumeration,
            startup (2) - at SNA services' initialization time
              (this is the default),
            demand (3) - only when LU is requested by application,
                    or
            onlyMS (4) - by a Management Station only.

            A  write operation
    to this object may immediately
            change the operational value reflected
            in snaNodeOperEnablingMethod depending
            on the Agent implementation.  If the Agent
            implementation accepts immediate changes, then the
            behavior of the Node changes immediately and not only
            after the next system startup of the SNA services.
            An immediate change may only apply when the
            current value 'demand (3)' is changed to 'onlyMS (4)'
            and vice versa."
        ::= { snaNodeAdminEntry 7 }

    snaNodeAdminLuTermDefault OBJECT-TYPE
        SYNTAX  INTEGER {
            unbind (1),
            termself (2),
            rshutd (3),
            poweroff(4)
            }
         MAX-ACCESS  read-create
         STATUS  current
         DESCRIPTION
            "The value indicates the desired default method
            used to deactivate LUs for this Node
             For LU6.2s, 'unbind(1)' is the only valid value.

            unbind(1) -   terminate the LU-LU session by sending
                  an SNA UNBIND request.
            termself(2) - terminate the LU-LU session by sending
                  an SNA TERM-SELF (Terminate Self) request on
                  the SSCP-LU session. The SSCP will inform the
```

remote session LU partner to send an UNBIND
request to terminate the session.

rshutd(3) - terminate the LU-LU session by sending
an SNA RSHUTD (Request ShutDown) request to
the remote session LU partner. The remote LU
will then send an UNBIND request to terminate
the session.

poweroff(4) - terminate the LU-LU session by sending
either an SNA LUSTAT (LU Status) request on
the LU-LU
session or an SNA NOTIFY request on
the SSCP-LU session indicating that the LU has
been powered off. Sending both is also
acceptable. The result should be that the
remote session LU partner will send an UNBIND
to terminate the session.

The default behavior indicated by the value of this
object may be overridden for an LU instance. The
override is performed by setting the snaLuAdminTerm
object instance in the snaLuAdminTable to the desired
value.

A write operation to this object may immediately
change the operational value reflected
in snaNodeOperLuTermDefault depending
on the Agent implementation."
::= { snaNodeAdminEntry 8 }

snaNodeAdminMaxLu OBJECT-TYPE
SYNTAX Integer32
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"The maximum number of LUs that may be
activated for this Node. For PU2.1, this object
refers to the number of dependent LUs.

A write operation to this object will
not change the operational value reflected
in snaNodeOperMaxLu until the Node has
been re-activated (e.g., after the next initialization
of the SNA services)."
::= { snaNodeAdminEntry 9 }

snaNodeAdminHostDescription OBJECT-TYPE
SYNTAX DisplayString (SIZE(0..128))
MAX-ACCESS read-create

```
        STATUS  current
        DESCRIPTION
                "The value identifies the remote host associated
                with this Node.
                Since SSCP Id's may not be unique
                across hosts, the host description
                is required to uniquely identify the SSCP.
                This object
 is only applicable to PU2.0 type
                Nodes. If the remote host is unknown, then the
                value is the null string.

                A write operation to this object may immediately
                change the operational value reflected
                in snaNodeOperHostDescription depending
                on the Agent implementation."
        ::= { snaNodeAdminEntry 10 }

snaNodeAdminStopMethod OBJECT-TYPE
        SYNTAX  INTEGER {
                other (1),
                normal (2),
                immed (3),
                force (4)
                }
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
                "The value indicates the desired method to be used
                by the Agent to stop a Node (i.e., change the Node's
                operational state to inactive(1) ).

                The values have the following meaning:

                other (1) - used for proprietary
                     methods not listed in this enumeration.
                normal(2) - deactivate only when there is no more
                    activity on this Node (i.e., all data flows
                    have been completed and all sessions
                    have been terminated).
                immed(3)  - deactivate immediately regardless of
                    current activities on this Node. Wait for
                    deactivation responses (from remote Node)
                    before changing the Node state to inactive.
                force(4)  - deactivate immediately regardless of
                    current activities on this Node. Do not wait
                    for deactivation responses (from remote Node)
                    before changing the Node state to inactive.
```

```
            A write operation to this object may immediately
            change the operational value reflected
            in snaNodeOperStopMethod
 depending
            on the Agent implementation."
        ::= { snaNodeAdminEntry 11 }

snaNodeAdminState OBJECT-TYPE
        SYNTAX  INTEGER {
            inactive (1),
            active (2)
            }
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "The value indicates the desired operational
             state of the SNA Node. This object is used
             by the Management Station to
             activate or deactivate the Node.

            If the current value in snaNodeOperState is
            'active (2)', then setting this object to
            'inactive (1)' will initiate the Node shutdown
            process using the method indicated
            by snaNodeOperStopMethod.

            If the current value in snaNodeOperState is
            'inactive (1)', then setting this object to
            'active (2)'
 will initiate the
            Node's activation.

            A Management Station can always set this object to
            'active (2)' irrespective of the value in the
            snaOperEnablingMethod."
        ::= { snaNodeAdminEntry 12 }

snaNodeAdminRowStatus OBJECT-TYPE
        SYNTAX  RowStatus
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "This object is used by a Management Station to
            create or delete the row entry in the
            snaNodeAdminTable following
            the RowStatus textual convention.
```

```
            Upon successful creation of
            the row, an Agent automatically creates a
            corresponding entry in the snaNodeOperTable with
            snaNodeOperState equal to 'inactive (1)'.

            Row deletion can be Management Station or Agent
            initiated:
            (a) The Management
 Station can set the value to
            'destroy (6)' only when the value of
            snaNodeOperState of this Node instance is
            'inactive (1)'. The Agent will then delete the rows
            corresponding to this Node instance from the
            snaNodeAdminTable and the snaNodeOperTable.
            (b) The Agent detects that a row is in the
            'notReady (3)' state for greater than a
            default period of 5 minutes.
            (c) All rows with the snaNodeAdminRowStatus object's
            value of 'notReady (3)' will be removed upon the
            next initialization of the SNA services."
        ::= { snaNodeAdminEntry 13 }


-- ****************************************************************
-- The following object is updated when there is a change to
-- the value of any object in the snaNodeAdminTable.
-- ****************************************************************

snaNodeAdminTableLastChange
 OBJECT-TYPE
        SYNTAX  TimeStamp
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value indicates the timestamp
            (e.g., the Agent's sysUpTime value) of the last
            change made to any object in the snaNodeAdminTable,
            including row deletions/additions (e.g., changes to
            snaNodeAdminRowStatus values).

            This object can be used to reduce frequent
            retrievals of the snaNodeAdminTable by a Management
            Station. It is expected that a Management Station
            will periodically poll this object and compare its
            current value with the previous one. A difference
            indicates that some Node configuration information
            has been changed. Only then will the Management
            Station retrieve the entire table."
```

```
        ::= { snaNode
 2 }


-- ****************************************************************
-- The following table contains Node operational parameters.
-- ****************************************************************

snaNodeOperTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF SnaNodeOperEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
                "This table contains the dynamic parameters which
                have read-only access. These objects reflect the
                actual status of the Node. The entries in this
                table cannot be created or modified by a
                Management Station.
                This table augments the snaNodeAdminTable."
        ::= { snaNode 3 }

snaNodeOperEntry OBJECT-TYPE
        SYNTAX  SnaNodeOperEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
                "The entry contains parameters which describe the
                state of
 one Node. The entries are created by the
                Agent. They have read-only access."
        AUGMENTS   { snaNodeAdminEntry }
        ::= { snaNodeOperTable 1 }

SnaNodeOperEntry ::= SEQUENCE {
        snaNodeOperName
                DisplayString,
        snaNodeOperType
                INTEGER,
        snaNodeOperXidFormat
                INTEGER,
        snaNodeOperBlockNum
                DisplayString,
        snaNodeOperIdNum
                DisplayString,
        snaNodeOperEnablingMethod
                INTEGER,
        snaNodeOperLuTermDefault
                INTEGER,
```

```
        snaNodeOperMaxLu
                Integer32,
        snaNodeOperHostDescription
                DisplayString,
        snaNodeOperStopMethod
                INTEGER,
        snaNodeOperState
                INTEGER,
        snaNodeOperHostSscpId
                OCTET STRING,
        snaNodeOperStartTime
                TimeStamp,
        snaNodeOperLastStateChange
                 TimeStamp,
        snaNodeOperActFailures
                Counter32,
        snaNodeOperActFailureReason
                INTEGER
        }

snaNodeOperName OBJECT-TYPE
        SYNTAX  DisplayString (SIZE(0..17))
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value identifies the current name of the Node.
            In Type 2.1 networks, this
            is a fully-qualified name, meaning that the Node name
            is preceded by the NetId (if present) with a period
            as the delimiter."
        ::= { snaNodeOperEntry 1 }

snaNodeOperType OBJECT-TYPE
        SYNTAX  INTEGER {
                other(1),
                pu10(2),
                pu20(3),
                t21LEN(4),
                endNode(5),
                networkNode(6)
                }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                 "The value identifies the current type of the Node."
        ::= { snaNodeOperEntry 2 }

snaNodeOperXidFormat OBJECT-TYPE
```

```
        SYNTAX  INTEGER  {
                format0 (1),
                format1 (2),
                format3 (3)
                }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The value identifies the type of XID format currently
                 used for this Node.
                 Note that there is no format type 2."
        ::= { snaNodeOperEntry 3 }

snaNodeOperBlockNum OBJECT-TYPE
        SYNTAX DisplayString (SIZE(3))
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The value identifies the block number for this Node
                instance. It is the first 3 hexadecimal digits
                of the SNA Node id."
        ::= { snaNodeOperEntry 4 }

snaNodeOperIdNum OBJECT-TYPE
        SYNTAX  DisplayString (SIZE(5))
         MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The value identifies the ID number for this Node
                instance.  This is the last 5 hexadecimal digits of
                the SNA Node id."
        ::= { snaNodeOperEntry 5 }

snaNodeOperEnablingMethod OBJECT-TYPE
        SYNTAX  INTEGER {
                other (1),
                startup (2),
                demand (3),
                onlyMS (4)
                }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The value indicates how the Node is activated for
                the first time.
                The values have the following meanings:
                  other (1)   - not at boot time, LU activation
                     or by a Management Station;
```

```
                startup (2) - at SNA services' initialization
                  time (this is the default),

    demand (3)  - only when LU is requested by
                  application,
                onlyMS (4) - by a network Management Station
                  only."
      ::= { snaNodeOperEntry 6 }

snaNodeOperLuTermDefault OBJECT-TYPE
      SYNTAX  INTEGER {
            unbind (1),
            termself (2),
            rshutd (3),
            poweroff (4)
            }
      MAX-ACCESS  read-only
      STATUS  current
      DESCRIPTION
          "The value identifies the default method used to
          deactivate LUs for this Node.
          For LU6.2s, 'unbind(1)' is the only valid value.

          unbind(1) -   terminate the LU-LU session by sending
                an SNA UNBIND request.
          termself(2) - terminate the LU-LU session by sending
                an SNA TERM-SELF (Terminate Self) request on
                the SSCP-LU session. The SSCP will inform
the
                remote session LU partner to send an UNBIND
                request to terminate the session.
          rshutd(3) -   terminate the LU-LU session by sending
                an SNA RSHUTD (Request ShutDown) request to
                the remote session LU partner. The remote LU
                will then send an UNBIND request to terminate
                the session.
          poweroff(4) - terminate the LU-LU session by sending
                either an SNA LUSTAT (LU Status) request on
                the LU-LU session or an SNA NOTIFY request on
                the SSCP-LU session indicating that the LU has
                been powered off. Sending both is also
                acceptable. The result should be that the
                remote session LU partner will send an UNBIND
                to terminate the session.

          This object
describes the default behavior for this
          Node; however, it is possible that for a specific LU
```

```
            the behavior indicated by the snaLuOperTerm object is
            different."
        ::= { snaNodeOperEntry 7 }

snaNodeOperMaxLu OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This value identifies the current, maximum number
            of LUs that are activated for this Node. For PU2.1,
            this object refers to the number of dependent LUs."
        ::= { snaNodeOperEntry 8 }

snaNodeOperHostDescription OBJECT-TYPE
        SYNTAX  DisplayString (SIZE(0..128))
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This value identifies the remote host currently
             associated with this Node.
             Since SSCP Id's may not be unique
             across hosts, the
 host description
             is required to uniquely identify the SSCP."
        ::= { snaNodeOperEntry 9 }

snaNodeOperStopMethod OBJECT-TYPE
        SYNTAX  INTEGER {
            other (1),
            normal (2),
            immed (3),
            force (4)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This value identifies the current Node shutdown
            method to be used by the Agent to stop the Node.
            When the Agent changes the Node's state to 'inactive
            (1)', the Agent must use the shutdown method
            indicated by this object.

            The values have the following meaning:

            other (1) - proprietary method not listed in this
                    enumeration
            normal(2) - deactivate only when there is no more
```

```
                activity on this Node (i.e., all
data flows
                have been completed and all sessions have
                been terminated).
            immed(3)  - deactivate immediately regardless of
                current activities on this Node. Wait for
                deactivation responses (from remote Node)
                before changing the Node state to inactive.
            force(4)  - deactivate immediately regardless of
                current activities on this Node. Do not wait
                for deactivation responses (from remote Node)
                before changing the Node state to inactive.

            Note that a write operation to
            snaNodeAdminOperStopMethod may immediately change
            the value of snaNodeOperStopMethod depending on
            the Agent implementation."
        ::= { snaNodeOperEntry 10 }

snaNodeOperState OBJECT-TYPE
        SYNTAX  INTEGER {

       inactive (1),
            active (2),
            waiting (3),
            stopping (4)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The current state of the Node.
            The values have the following meanings:
              inactive (1), a row representing the Node has
                been created in the AdminTable
                and, the Node is ready for activation -or-
                an active Node has been stopped -or-
                a waiting Node has returned to the inactive
                state.
              waiting (3), a request to have the Node activated
                has been issued, and the Node is pending
                activation.
              active (2), the Node is ready and operating.
              stopping (4), the request to stop the Node has
                been
 issued while the StopMethod normal
                or immediate is used."
        ::= { snaNodeOperEntry 11 }
```

```
snaNodeOperHostSscpId OBJECT-TYPE
        SYNTAX  OCTET STRING (SIZE(0..6))
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "This value identifies the current SSCP Id
                 associated with the Node. This object is only
                 applicable to PU 2.0s. If the Node
                 is not a PU 2.0 type, then this object contains a
                 zero length string."
        ::= { snaNodeOperEntry 12 }

snaNodeOperStartTime OBJECT-TYPE
        SYNTAX  TimeStamp
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The timestamp (e.g, the Agent's sysUpTime value)
                 at the Node activation."
        ::= { snaNodeOperEntry 13 }

snaNodeOperLastStateChange OBJECT-TYPE
        SYNTAX  TimeStamp
        MAX-ACCESS  read-only

        STATUS  current
        DESCRIPTION
                "The timestamp (e.g., the Agent's sysUpTime value)
                at the last state change of the Node."
        ::= { snaNodeOperEntry 14 }

snaNodeOperActFailures OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "This value identifies the number of failed Node
                activation attempts."
        ::= { snaNodeOperEntry 15 }

snaNodeOperActFailureReason OBJECT-TYPE
        SYNTAX  INTEGER {
                other (1),
                linkFailure (2),
                noResources (3),
                badConfiguration (4),
                internalError (5)
                }
```

```
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The value indicates the reason for the activation
                failure.  The value 'other (1)' indicates a reason
                not
 listed in the enumeration. This object
                will be sent in the trap snaNodeActFailTrap."
        ::= { snaNodeOperEntry 16 }


-- ****************************************************************
-- The following object is updated when there is a change to
-- the value of snaNodeOperState in any row or a row is
-- added/deleted from the snaNodeOperTable via the snaNodeAdminTable.
-- ****************************************************************

snaNodeOperTableLastChange OBJECT-TYPE
        SYNTAX  TimeStamp
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The timestamp (e.g., the Agent's sysUpTime value)
                at the last change made to any object in the
                snaNodeOperTable, including row deletions/additions
                made as a result of changes to the
                snaNodeAdminRowStatus object.

                This object can be used to reduce frequent
                retrievals
 of the snaNodeOperTable by a Management
                Station. It is expected that a Management Station
                will periodically poll this object and compare its
                current value with the previous one. A difference
                indicates that some Node operational information
                has been changed. Only then will the Management
                Station retrieve the entire table."
        ::= { snaNode 4 }


-- ****************************************************************
-- The following table contains PU 2.0 statistics dynamic parameters.
-- ****************************************************************

snaPu20StatsTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF SnaPu20StatsEntry
        MAX-ACCESS  not-accessible
        STATUS  current
```

```
        DESCRIPTION
            "This table contains the dynamic parameters which
            have read-only access. The entries in this table
            correspond
 to PU 2.0 entries in the snaNodeOperTable
            and cannot be created by a Management Station."
        ::= { snaNode 5 }

snaPu20StatsEntry OBJECT-TYPE
        SYNTAX  SnaPu20StatsEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
            "The entry contains parameters which describe the
            statistics for one PU 2.0. They have read-only
            access.
            The counters represent traffic for all kinds
            of sessions: LU-LU, SSCP-PU, SSCP-LU.

            Each Node of PU Type 2.0 from the snaNodeAdminTable
            has one entry in this table and the index used
            here has the same value as snaNodeAdminIndex of
            that PU.  The entry is created by the Agent."
        INDEX   { snaNodeAdminIndex }
        ::= { snaPu20StatsTable 1 }

SnaPu20StatsEntry ::= SEQUENCE {
        snaPu20StatsSentBytes
            Counter32,
         snaPu20StatsReceivedBytes
            Counter32,
        snaPu20StatsSentPius
            Counter32,
        snaPu20StatsReceivedPius
            Counter32,
        snaPu20StatsSentNegativeResps
            Counter32,
        snaPu20StatsReceivedNegativeResps
            Counter32,
        snaPu20StatsActLus
            Gauge32,
        snaPu20StatsInActLus
            Gauge32,
        snaPu20StatsBindLus
            Gauge32
        }

snaPu20StatsSentBytes OBJECT-TYPE
```

```
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of bytes sent by this Node."
        ::= { snaPu20StatsEntry 1 }

snaPu20StatsReceivedBytes OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of bytes received by this Node."
        ::= { snaPu20StatsEntry
 2 }

snaPu20StatsSentPius OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of PIUs sent by this Node."
        ::= { snaPu20StatsEntry 3 }

snaPu20StatsReceivedPius OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of PIUs received by this Node."
        ::= { snaPu20StatsEntry 4 }

snaPu20StatsSentNegativeResps OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of negative responses sent
            by this Node."
        ::= { snaPu20StatsEntry 5 }

snaPu20StatsReceivedNegativeResps OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The number of negative responses received
```

```
        by this Node."
        ::= { snaPu20StatsEntry 6 }

snaPu20StatsActLus OBJECT-TYPE
        SYNTAX  Gauge32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The number of LUs on this PU which have
                received and responded to ACTLU from the host."
        ::= { snaPu20StatsEntry 7 }

snaPu20StatsInActLus OBJECT-TYPE
        SYNTAX  Gauge32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The number of LUs on this PU which have
                not received an ACTLU from the host.  This is
                possible if the number of configured LUs exceeds
                that on the host."
        ::= { snaPu20StatsEntry 8 }

snaPu20StatsBindLus OBJECT-TYPE
        SYNTAX  Gauge32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The number of LUs on this PU which have
                received and acknowledged
 a BIND request from the
                host."
        ::= { snaPu20StatsEntry 9 }

-- ****************************************************************
-- The following table contains the association between Nodes and
-- link identifiers.
-- It is used for configuration purposes.
-- ****************************************************************

snaNodeLinkAdminTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF SnaNodeLinkAdminEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
                "This table contains the references to link
                specific tables. If a Node is configured for
                multiple links, then the Node will have
```

```
            multiple entries in this table.
            The entries in this table can be generated
            initially, after initialization of SNA service,
            by the Agent which uses information from
            Node configuration file.

          Subsequent modifications of parameters,
            creation of new Nodes link entries and deletion
            of entries is possible.
            The modification to this table can be
            saved in the Node configuration file for the
            next initialization of SNA service, but the mechanism
            for this function is not defined here."
        ::= { snaNode 6 }

snaNodeLinkAdminEntry OBJECT-TYPE
        SYNTAX  SnaNodeLinkAdminEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
            "Entry contains the configuration information that
            associates a Node instance to one link instance.
            The objects in the entry have read-create access.
            Entry can be created, modified or deleted.
            The object snaNodeLinkAdminRowStatus is used (set)
            to create or delete an entry.
            The object
 snaNodeLinkAdminSpecific can be set
            later, after the entry has been created."
        INDEX   { snaNodeAdminIndex,
                  snaNodeLinkAdminIndex }
        ::= { snaNodeLinkAdminTable 1 }

SnaNodeLinkAdminEntry ::= SEQUENCE {
        snaNodeLinkAdminIndex
            Integer32,
        snaNodeLinkAdminSpecific
            InstancePointer,
        snaNodeLinkAdminMaxPiu
            Integer32,
        snaNodeLinkAdminRowStatus
            RowStatus
        }

snaNodeLinkAdminIndex OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  not-accessible
        STATUS  current
```

```
        DESCRIPTION
            "This value is used to index the instances of objects.
            If an Agent creates the entry, then it will assign
            this number otherwise a Management Station
            generates a random number when it reserves the
            entry for creation."
        ::=
 { snaNodeLinkAdminEntry 1 }

snaNodeLinkAdminSpecific OBJECT-TYPE
        SYNTAX  InstancePointer
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "This value points to the row in the table
            containing information on the link instance.
            (e.g., the sdlcLSAdminTable of
            the SNA DLC MIB module)."
        ::= { snaNodeLinkAdminEntry 2 }

snaNodeLinkAdminMaxPiu OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "This value identifies the maximum number of octets
            that can be exchanged by this Node in one
            Path Information Unit (PIU)."
        ::= { snaNodeLinkAdminEntry 3 }

snaNodeLinkAdminRowStatus OBJECT-TYPE
        SYNTAX  RowStatus
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "This object is used by a
 Management Station to
            create or delete the row entry in the
            snaNodeLinkAdminTable.
            To activate a row, a Management Station sets the value
            to 'active (1)' or 'notReady (3)'.  Upon successful
            creation of the row, the Agent automatically creates
            a corresponding entry in the snaNodeLinkOperTable.

            Row deletion can be Management Station or Agent
            initiated:
            (a) The Management Station can set the value to
            'destroy (6)' only when the value of
```

```
            snaNodeLinkOperState of this Link
            instance is 'inactive (1)'. The Agent will then
            delete the row corresponding to this Link
            instance from snaNodeLinkOperTable and
            from snaNodeLinkAdminTable.
            (b) The Agent detects that a row is in the
            'notReady (3)' state for greater than a

  default period of 5 minutes.
            (c) The Agent will not include a row with RowStatus=
            'notReady (3)', after SNA system re-initialization
             (e.g., reboot)."
        ::= { snaNodeLinkAdminEntry 4 }


-- ****************************************************************
-- The following object is updated when there is a change to
-- the value of any object in the snaNodeLinkAdminTable.
-- ****************************************************************

snaNodeLinkAdminTableLastChange OBJECT-TYPE
        SYNTAX  TimeStamp
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "The timestamp (e.g., the Agent's sysUpTime value)
                at the last
                change made to any object in the snaNodeLinkAdminTable,
                including row deletions/additions (i.e., changes
                to the snaNodeLinkAdminRowStatus object).

                This object can be used to reduce
 frequent
                retrievals of the snaNodeLinkAdminTable by a
                Management Station. It is expected that a
                Management Station will periodically poll this
                object and compare its current value with the
                previous one.
                A difference indicates that some Node operational
                information has been changed. Only then will the
                Management Station retrieve the entire table."
        ::= { snaNode 7 }


-- ****************************************************************
-- The following table contains the association between
-- Nodes and link identifiers.
-- It provides the current status.
```

```
-- ********************************************************************

snaNodeLinkOperTable OBJECT-TYPE
        SYNTAX  SEQUENCE OF SnaNodeLinkOperEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
                "This table contains all references
 to link
                specific tables for operational parameters.
                If a Node is configured for multiple links,
                then the Node will have multiple entries in
                this table. This table augments the
                snaNodeLinkAdminTable."
        ::= { snaNode 8 }

snaNodeLinkOperEntry OBJECT-TYPE
        SYNTAX  SnaNodeLinkOperEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
                "Entry contains all current parameters for one
                Node link. The objects in the entry have
                read-only access."
        AUGMENTS   { snaNodeLinkAdminEntry }
        ::= { snaNodeLinkOperTable 1 }

SnaNodeLinkOperEntry ::= SEQUENCE {
        snaNodeLinkOperSpecific
                InstancePointer,
        snaNodeLinkOperMaxPiu
                Integer32
        }

snaNodeLinkOperSpecific OBJECT-TYPE
        SYNTAX  InstancePointer
        MAX-ACCESS
  read-only
        STATUS  current
        DESCRIPTION
                "This value points to the row in the table
                containing information on the link instance.
                (e.g., the sdlcLSOperTable of
                the SNA DLC MIB module)."
        ::= { snaNodeLinkOperEntry 1 }

snaNodeLinkOperMaxPiu OBJECT-TYPE
        SYNTAX  Integer32
```

```
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "Maximum number of octets that can
            be exchanged by this Node in one Path
            Information Unit (PIU)."
        ::= { snaNodeLinkOperEntry 2 }


-- ****************************************************************
-- The following object is updated when a row is added/deleted
-- from the snaNodeLinkOperTable.
-- ****************************************************************

snaNodeLinkOperTableLastChange OBJECT-TYPE
        SYNTAX  TimeStamp
        MAX-ACCESS  read-only

 STATUS  current
        DESCRIPTION
            "The timestamp of the last
            change made to any object in the snaNodeLinkOperTable,
            including row deletions/additions.

            This object can be used to reduce frequent
            retrievals of the snaNodeLinkOperTable by a
            Management Station. It is expected that a
            Management Station will periodically poll this
            object and compare its current value with the
            previous one.
            A difference indicates that some Node operational
            information has been changed. Only then will the
            Management Station retrieve the entire table."
        ::= { snaNode 9 }

-- ****************************************************************
-- Traps
-- ****************************************************************

snaNodeTraps OBJECT IDENTIFIER ::= { snaNode 10 }

snaNodeStateChangeTrap
 NOTIFICATION-TYPE
        OBJECTS  { snaNodeOperName,
            snaNodeOperState }
        STATUS  current
        DESCRIPTION
            "This trap indicates that the operational state
```

```
            (i.e., value of the snaNodeOperState object) of a Node
             has changed. The following variables are returned:
              snaNodeOperName - current name of the Node,
                with the instance identifying the Node; and,
              snaNodeOperState - current state after
                the change."
        ::= { snaNodeTraps 1 }

snaNodeActFailTrap NOTIFICATION-TYPE
        OBJECTS  { snaNodeOperName,
                   snaNodeOperState,
                   snaNodeOperActFailureReason }
        STATUS  current
        DESCRIPTION
                "This trap indicates a Node activation failure.
                The value of snaNodeOperState indicates the current
                state after the activation attempt.
                 The value of snaNodeOperActFailureReason indicates
                the failure reason."
        ::=  { snaNodeTraps 2 }


-- ********************************************************************
-- snaLu group
--
-- It contains Managed Objects related to LUs in general and some
-- specific for LUs of type 0, 1, 2, 3.
-- ********************************************************************


-- ********************************************************************
-- The following table contains LU configuration parameters.
-- ********************************************************************

snaLuAdminTable OBJECT-TYPE
      SYNTAX  SEQUENCE OF SnaLuAdminEntry
      MAX-ACCESS  not-accessible
      STATUS  current
      DESCRIPTION
            "This table contains LU configuration information.
            The rows in this table can be created and deleted
            by a Management Station.
            Only objects which are common to all types of LUs

            are included in this table."
      ::= { snaLu 1 }

snaLuAdminEntry OBJECT-TYPE
```

```
        SYNTAX  SnaLuAdminEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
            "Contains configuration variables for an LU."
        INDEX   { snaNodeAdminIndex, snaLuAdminLuIndex }
        ::= { snaLuAdminTable 1 }

    SnaLuAdminEntry ::= SEQUENCE {
        snaLuAdminLuIndex
            Integer32,
        snaLuAdminName
            DisplayString,
        snaLuAdminSnaName
            DisplayString,
        snaLuAdminType
            INTEGER,
        snaLuAdminDepType
            INTEGER,
        snaLuAdminLocalAddress
            OCTET STRING,
        snaLuAdminDisplayModel
            INTEGER,
        snaLuAdminTerm
            INTEGER,
        snaLuAdminRowStatus
            RowStatus
        }

    snaLuAdminLuIndex OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  not-accessible
        STATUS  current
         DESCRIPTION
            "This value identifies the unique index for an
             LU instance within a Node."
        ::= { snaLuAdminEntry 1 }

    snaLuAdminName OBJECT-TYPE
        SYNTAX  DisplayString (SIZE(0..48))
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "This value identifies the user configurable
            name for this LU. If a name is not assigned to the LU,
            then this object contains a zero length string.

            A write operation to this object will
```

```
            not change the operational value reflected
            in snaLuOperName until the Node has
            been re-activated (e.g., after the next
            initialization of the SNA services)."
        ::= { snaLuAdminEntry 2 }

snaLuAdminSnaName OBJECT-TYPE
        SYNTAX  DisplayString (SIZE(1..17))
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "This value identifies
 the SNA LU name
            used in exchange of SNA data.

            A write operation to this object will
            not change the operational value reflected
            in snaLuOperSnaName until the Node has
            been re-activated (e.g., after the next
            initialization of the SNA services)."
        ::= { snaLuAdminEntry 3 }

snaLuAdminType OBJECT-TYPE
        SYNTAX  INTEGER {
            other(1),
            lu0(2),
            lu1(3),
            lu2(4),
            lu3(5),
            lu4(6),
            lu62(7),
            lu7(8)
            }
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "This value identifies the LU type.

            A write operation to this object will
            not change the operational value reflected
            in snaLuOperAdminType until the Node has
            been re-activated (e.g., after the next
             initialization of the SNA services)."
        ::= { snaLuAdminEntry 4 }

snaLuAdminDepType OBJECT-TYPE
        SYNTAX  INTEGER {
            dependent(1),
```

```
            independent(2)
            }
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "This value identifies whether the LU is
            dependent or independent.

            A write operation to this object will
            not change the operational value reflected
            in snaLuOperDepType until the Node has
            been re-activated (e.g., after the next
            initialization of the SNA services)."
        ::= { snaLuAdminEntry 5 }

    snaLuAdminLocalAddress OBJECT-TYPE
        SYNTAX  OCTET STRING (SIZE(1))
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "The local address for this LU is a byte with a value
            ranging from 0 to 254.For dependent LUs, this value
             ranges from 1 to 254 and for independent LUs this
            value is always 0.

            A write operation to this object will not change the
            operational value reflected in snaLuOperLocalAddress
            until the Node has been re-activated (e.g., after the
            next initialization of the SNA services)."
        ::= { snaLuAdminEntry 6 }

    snaLuAdminDisplayModel OBJECT-TYPE
        SYNTAX  INTEGER {
            invalid(1),
            model2A(2),
            model2B(3),
            model3A(4),
            model3B(5),
            model4A(6),
            model4B(7),
            model5A(8),
            model5B(9),
            dynamic(10)
            }
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "The value of this object identifies the  model type
```

```
            and screen size of the terminal connected to the host.
            This
 is only valid for LU Type 2.  The values have
            the following meaning:

            model2A(2) - Model 2 (24 rows x 80 cols) with base
                attributes
            model2B(3) - Model 2 (24 rows x 80 cols) with
                extended attributes
            model3A(4) - Model 3 (32 rows x 80 cols) with base
                attributes
            model3B(5) - Model 3 (32 rows x 80 cols) with extended
                attributes
            model4A(6) - Model 4 (43 rows x 80 cols) with base
                attributes
            model4B(7) - Model 4 (43 rows x 80 cols) with extended
                                attributes
            model5A(8) - Model 5 (27 rows x 132 cols) with base
                attributes
            model5B(9) - Model 5 (27 rows x 132 cols) with
                extended attributes
            dynamic(10) - Screen size determine with
 BIND and Read
                                Partition Query.

            In case this LU is not Type 2, then this object
            should contain the invalid(1) value."
        ::= { snaLuAdminEntry 7 }

snaLuAdminTerm OBJECT-TYPE
        SYNTAX  INTEGER {
            unbind (1),
            termself (2),
            rshutd (3),
            poweroff (4)
            }
        MAX-ACCESS  read-create
        STATUS  current
        DESCRIPTION
            "This value identifies the desired method for
            deactivation of this LU. This value overrides the
            default method (snaNodeOperLuTermDefault) for this
            Node.  For LU 6.2, only the value 'unbind (1)'
            applies.

            unbind(1) -   terminate the LU-LU session by sending
                an SNA UNBIND request.
            termself(2) - terminate the LU-LU session by sending
```

an SNA TERM-SELF
(Terminate Self) request on
the SSCP-LU session. The SSCP will inform the
remote session LU partner to send an UNBIND
request to terminate the session.
rshutd(3) - terminate the LU-LU session by sending
an SNA RSHUTD (Request ShutDown) request to
the remote session LU partner. The remote LU
will then send an UNBIND request to terminate
the session.
poweroff(4) - terminate the LU-LU session by sending
either an SNA LUSTAT (LU Status) request on
the LU-LU session or an SNA NOTIFY request on
the SSCP-LU session indicating that the LU has
been powered off. Sending both is also
acceptable. The result should be that the
remote session LU partner
will send an UNBIND
to terminate the session.

A write operation to this object may immediately
change the operational value reflected
in snaLuOperTerm depending
on the Agent implementation."
::= { snaLuAdminEntry 8 }

snaLuAdminRowStatus OBJECT-TYPE
SYNTAX RowStatus
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This object is used by a Management Station to
create or delete the row entry in the
snaLuAdminTable.
To activate a row, the Management Station sets the
value to 'active (1)' or 'notReady (3)'.
Upon successful creation of the row, the Agent
automatically creates a corresponding entry in the
snaLuOperTable with snaLuOperState equal to
'inactive (1)'.
Row deletion can be Management Station
or Agent
initiated:
(a) The Management Station can set the value to
'destroy (6)' only when the value of snaLuOperState
of this LU instance is 'inactive (1)'. The Agent will
then delete the row corresponding to this LU
instance from snaLuAdminTable and

```
            from snaLuOperTable.
            (b) The Agent detects that a row is in the
            'notReady (3)' state for greater than a
            default period of 5 minutes.
            (c) The Agent will not create a row with RowStatus
            equal to 'notReady (3)', after SNA system
            re-initialization (e.g., reboot)."
        ::= { snaLuAdminEntry 9 }


-- ****************************************************************
-- The following table contains LU state dynamic parameters.
-- ****************************************************************

snaLuOperTable OBJECT-TYPE
        SYNTAX
    SEQUENCE OF SnaLuOperEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
            "This table contains dynamic runtime information and
            control variables relating to LUs.
            Only objects which are common to all types of LUs are
            included in this table. This table augments the
            snaLuAdminTable."
        ::= { snaLu 2 }

snaLuOperEntry OBJECT-TYPE
        SYNTAX  SnaLuOperEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
            "Contains objects reflecting current information
            for an LU.
            Each entry is created by the Agent.  All entries
            have read-only access."
        AUGMENTS        { snaLuAdminEntry }
        ::= { snaLuOperTable 1 }

SnaLuOperEntry ::= SEQUENCE {
        snaLuOperName
            DisplayString,
        snaLuOperSnaName
            DisplayString,
        snaLuOperType

          INTEGER,
        snaLuOperDepType
```

```
            INTEGER,
        snaLuOperLocalAddress
            OCTET STRING,
        snaLuOperDisplayModel
            INTEGER,
        snaLuOperTerm
            INTEGER,
        snaLuOperState
            INTEGER,
        snaLuOperSessnCount
            Gauge32
        }

    snaLuOperName OBJECT-TYPE
        SYNTAX  DisplayString (SIZE(0..48))
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "User configurable name for this LU. If a name
            is not assigned, then this object contains a
            zero length string."
        ::= { snaLuOperEntry 1 }

    snaLuOperSnaName OBJECT-TYPE
        SYNTAX  DisplayString (SIZE(1..17))
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value identifies the current SNA LU name."
        ::= { snaLuOperEntry 2 }

    snaLuOperType OBJECT-TYPE
        SYNTAX  INTEGER {
            other(1),
             lu0(2),
            lu1(3),
            lu2(4),
            lu3(5),
            lu4(6),
            lu62(7),
            lu7(8)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value identifies the current LU type."
        ::= { snaLuOperEntry 3 }
```

```
snaLuOperDepType OBJECT-TYPE
    SYNTAX  INTEGER {
            dependent(1),
            independent(2)
            }
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "The value identifies whether the LU is currently
             dependent or independent.

            A write operation to this object will
            not change the operational value reflected
            in snaLuOperDepType until the Node has
            been re-activated (e.g., after the next
            initialization of the SNA services)."
    ::= { snaLuOperEntry 4 }

snaLuOperLocalAddress
 OBJECT-TYPE
    SYNTAX  OCTET STRING (SIZE(1))
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
            "The local address for this LU is a byte with a value
            ranging from 0 to 254. For dependent LUs, this value
            ranges from 1 to 254; for independent LUs this value
            is always 0.

            A write operation to this object will
            not change the operational value reflected
            in snaLuOperLocalAddress until the Node has
            been re-activated (e.g., after the next
            initialization of the SNA services)."
    ::= { snaLuOperEntry 5 }

snaLuOperDisplayModel OBJECT-TYPE
    SYNTAX  INTEGER {
            invalid(1),
            model2A(2),
            model2B(3),
            model3A(4),
            model3B(5),
            model4A(6),
            model4B(7),
            model5A(8),
            model5B(9),
```

```
            dynamic(10)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The screen model type of the terminal connected to
            the host. If this LU is not Type 2, then this
            object should contain the 'invalid(1)' value."
        ::= { snaLuOperEntry 6 }

    snaLuOperTerm OBJECT-TYPE
        SYNTAX  INTEGER {
            unbind (1),
            termself (2),
            rshutd (3),
            poweroff (4)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value identifies the current method for
            deactivation of this LU. This value overrides the
            default method (snaNodeOperLuTermDefault) for this
            Node.  For LU 6.2, only the value 'unbind (1)'
            applies.

            unbind(1) -   terminate the LU-LU session by sending
                an SNA UNBIND request.
             termself(2) - terminate the LU-LU session by sending
                an SNA TERM-SELF (Terminate Self) request on
                the SSCP-LU session. The SSCP will inform the
                remote session LU partner to send an UNBIND
                request to terminate the session.
            rshutd(3) -   terminate the LU-LU session by sending
                an SNA RSHUTD (Request ShutDown) request to
                the remote session LU partner. The remote LU
                will then send an UNBIND request to terminate
                the session.
            poweroff(4) - terminate the LU-LU session by sending
                either an SNA LUSTAT (LU Status) request on
                the LU-LU session or an SNA NOTIFY request on
                the SSCP-LU session indicating that the LU has
                been powered off. Sending both is also

               acceptable. The result should be that the
                remote session LU partner will send an UNBIND
                to terminate the session."
        ::= { snaLuOperEntry 7 }
```

```
snaLuOperState OBJECT-TYPE
    SYNTAX  INTEGER {
        inactive (1),
        active (2)
        }
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The value identifies the current operational state of
        this LU.
        It has different meanings for dependent and independent
        LUs.
        For dependent LUs the values indicate the following:
          inactive (1) - LU didn't receive ACTLU, or
              it received DACTLU, or received ACTLU and sent
              negative response.
          active (2) - LU received ACTLU and acknowledged
              positively.

        For independent LUs the values
 indicate the following:
          active (2) - the LU is defined and is able to send
              and receive BIND.
          inactive (1) - the LU has a session count equal
              to 0."
    ::= { snaLuOperEntry 8 }

snaLuOperSessnCount OBJECT-TYPE
    SYNTAX  Gauge32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The number of currently active LU-LU sessions of
        this LU.
        For the independent LU, if this object has value 0,
        it indicates that LU is inactive."
    ::= { snaLuOperEntry 9 }


-- ****************************************************************
-- The following table contains LU session status parameters.
-- ****************************************************************

snaLuSessnTable OBJECT-TYPE
    SYNTAX  SEQUENCE OF SnaLuSessnEntry
    MAX-ACCESS  not-accessible
    STATUS  current
```

```
        DESCRIPTION

       "This is a table containing objects which describe the
            operational state of LU sessions.  Only objects which
            are common to all types of LU sessions are included
            in this table.

            When a session's snaLuSessnOperState value changes to
            'pendingBind (2)', then the corresponding entry
            in the session table is created by the Agent.

            When the session's snaLuSessnOperState value changes to
             'unbound (1)',  then the session will be removed from
            the session table by the Agent."
        ::= { snaLu 3 }

snaLuSessnEntry OBJECT-TYPE
        SYNTAX  SnaLuSessnEntry
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
            "An entry contains dynamic parameters for an LU-LU
            session.
            The indices identify the Node, local LU, and remote LU
            for this session."
        INDEX   { snaNodeAdminIndex,
                  snaLuAdminLuIndex,
                  snaLuSessnRluIndex,
                  snaLuSessnIndex }
        ::= { snaLuSessnTable 1 }

SnaLuSessnEntry ::= SEQUENCE {
        snaLuSessnRluIndex
            Integer32,
        snaLuSessnIndex
            Integer32,
        snaLuSessnLocalApplName
            DisplayString,
        snaLuSessnRemoteLuName
            DisplayString,
        snaLuSessnMaxSndRuSize
            INTEGER,
        snaLuSessnMaxRcvRuSize
            INTEGER,
        snaLuSessnSndPacingSize
            INTEGER,
        snaLuSessnRcvPacingSize
            INTEGER,
```

```
    snaLuSessnActiveTime
        TimeStamp,
    snaLuSessnAdminState
        INTEGER,
    snaLuSessnOperState
        INTEGER,
    snaLuSessnSenseData
        OCTET STRING,
    snaLuSessnTerminationRu
        INTEGER,
    snaLuSessnUnbindType
        OCTET STRING,
    snaLuSessnLinkIndex
         Integer32
    }

snaLuSessnRluIndex OBJECT-TYPE
    SYNTAX  Integer32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "This value may be used to identify information about
        the session partner LU in a table of information about
        remote LUs.  Such a table is not defined in this
        document.  If a table of remote LU information is not
        implemented, or if the table is implemented but it does
        not contain information about the partner LU for a
        particular session (as for dependent LU-LU sessions)
        then this object will have a value of zero."
    ::= { snaLuSessnEntry 1 }

snaLuSessnIndex OBJECT-TYPE
    SYNTAX  Integer32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "This value identifies the unique index of the session.
        It is recommended
 that an Agent should not reuse the
        index of a deactivated session for a significant
        period of time (e.g., one week)."
    ::= { snaLuSessnEntry 2 }

snaLuSessnLocalApplName OBJECT-TYPE
    SYNTAX  DisplayString (SIZE(0..48))
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
```

```
            "The name of the local application using this LU.
            If the local application is unknown, then this object
            contains a zero length string."
        ::= { snaLuSessnEntry 3 }

    snaLuSessnRemoteLuName OBJECT-TYPE
        SYNTAX  DisplayString (SIZE(0..17))
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "For dependent LUs which are indicated by the
            snaLuOperDepType object containing the value
            'dependent (1)', this object contains the Primary
            LU (PLU) name.  For independent LUs,
            this object contains the fully-qualified
     remote LU
            name of this 6.2 session.
            A fully qualified name is an SNA NAU entity name
            preceded by the NetId and a period as the delimiter."
        ::= { snaLuSessnEntry 4 }

    snaLuSessnMaxSndRuSize OBJECT-TYPE
        SYNTAX  INTEGER (1..8192)
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The maximum RU size used on this session for sending
            RUs."
        ::= { snaLuSessnEntry 5 }

    snaLuSessnMaxRcvRuSize OBJECT-TYPE
        SYNTAX  INTEGER (1..8192)
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The maximum RU size used on this session for
            receiving RUs."
        ::= { snaLuSessnEntry 6 }

    snaLuSessnSndPacingSize OBJECT-TYPE
        SYNTAX  INTEGER (1..63)
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The size of the send pacing window on this session."
        ::= {
     snaLuSessnEntry 7 }
```

```
snaLuSessnRcvPacingSize OBJECT-TYPE
    SYNTAX  INTEGER (1..63)
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The size of the receive pacing window on this
        session."
    ::= { snaLuSessnEntry 8 }

snaLuSessnActiveTime OBJECT-TYPE
    SYNTAX  TimeStamp
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The timestamp (e.g., the Agent's sysUpTime value)
        when this session becomes active."
    ::= { snaLuSessnEntry 9 }

snaLuSessnAdminState OBJECT-TYPE
    SYNTAX  INTEGER {
        unbound (1),
        bound (3)
        }
    MAX-ACCESS  read-write
    STATUS  current
    DESCRIPTION
        "The value indicates the desired operational state of
        the session. This object is used to
        change the operational state of the session.
        A Management Station
 can only change the operational
        state of the session to 'unbound (1)'.

        Session deactivation:
          If a session is in the operational state
          'bound (3)' then setting the value of this
          object to 'unbound (1)' will initiate the
          session shutdown.

          If a session is in the operational state
          'pendingBind (2)' then setting the value of this
          object to 'unbound (1)' will initiate the session
          shutdown.
          If a session is in the operational state
          'pendingUnbind (4)' for an abnormally long period
          of time (e.g., three minutes) then setting the value
          of this object to 'unbound (1)' will change the
          session operational state to 'unbound (1)'.
```

```
            Note: for dependent LUs, deactivating the session is
            the same as deactivating
 the LU."
        ::= { snaLuSessnEntry 10 }

snaLuSessnOperState OBJECT-TYPE
        SYNTAX  INTEGER {
            unbound (1),
            pendingBind (2),
            bound (3),
            pendingUnbind (4)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value indicates the current operational state of
            the session.

             'unbound (1)' - session has been  unbound;
                 in this state it will be removed from the
                 session table by the Agent.

             'pendingBind (2)' - this state has different
                 meanings for dependent and independent LUs;
                 for dependent LU - waiting for BIND from
                 the host, for independent LU - waiting for
                 BIND response.  When a session enters this
                 state, the corresponding entry in the

              session table is created by the Agent.

             'bound (3)' - session has been successfully bound.

             'pendingUnbind (4)' - session enters this state
                 when an UNBIND is sent and before the
                 rsp(UNBIND) is received."
        ::= { snaLuSessnEntry 11 }

snaLuSessnSenseData OBJECT-TYPE
        SYNTAX  OCTET STRING (SIZE(0..8))
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value identifies the sense code when there is
            a BIND failure. It is taken from the negative BIND
            response or UNBIND request.
            This is displayed as 8 hexadecimal digits."
```

```
    ::= { snaLuSessnEntry 12 }

snaLuSessnTerminationRu OBJECT-TYPE
    SYNTAX INTEGER {
        other (1),
        bindFailure (2),
        unbind (3)
        }
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The value identifies the SNA RU that terminated the
        session.
        If the session is not in the unbound state, this object
        has a value of  'other (1)'."
    ::= { snaLuSessnEntry 13 }


snaLuSessnUnbindType OBJECT-TYPE
    SYNTAX  OCTET STRING (SIZE(0..1))
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "If the session is in the unbound state, and it was
        terminated by an UNBIND, then this object contains
        the UNBIND type value (byte 1 of the UNBIND RU);
        otherwise the string is null."
    ::= { snaLuSessnEntry 14 }

snaLuSessnLinkIndex OBJECT-TYPE
    SYNTAX  Integer32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "This value identifies the link over which the session
        passes.  It is an index into snaNodeLinkAdminTable.
        If the index value is not known,
 the value of this
        object shall be zero."
    ::= { snaLuSessnEntry 15 }


-- ****************************************************************
-- The following table contains LU sessions statistics dynamic
-- parameters.
-- ****************************************************************

snaLuSessnStatsTable OBJECT-TYPE
```

```
    SYNTAX  SEQUENCE OF SnaLuSessnStatsEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
        "This table contains dynamic statistics information
        relating to LU sessions.
        The entries in this table augment the entries in
        the snaLuSessnTable and cannot be created by
        a Management Station."
    ::= { snaLu 4 }

snaLuSessnStatsEntry OBJECT-TYPE
    SYNTAX  SnaLuSessnStatsEntry
    MAX-ACCESS  not-accessible
    STATUS  current
    DESCRIPTION
        "Contains statistics information for an LU session.

   Each entry is created by the Agent.
        Objects in this table have read-only access.
        Each session from snaLuSessnTable
        has one entry in this table."
    AUGMENTS   { snaLuSessnEntry }
    ::= { snaLuSessnStatsTable 1 }

SnaLuSessnStatsEntry ::= SEQUENCE {
    snaLuSessnStatsSentBytes
        Counter32,
    snaLuSessnStatsReceivedBytes
        Counter32,
    snaLuSessnStatsSentRus
        Counter32,
    snaLuSessnStatsReceivedRus
        Counter32,
    snaLuSessnStatsSentNegativeResps
        Counter32,
    snaLuSessnStatsReceivedNegativeResps
        Counter32
    }

snaLuSessnStatsSentBytes OBJECT-TYPE
    SYNTAX  Counter32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The number of bytes sent by the local LU."
    ::= { snaLuSessnStatsEntry 1 }
```

```
snaLuSessnStatsReceivedBytes OBJECT-TYPE
    SYNTAX
 Counter32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The number of bytes received by the local LU."
    ::= { snaLuSessnStatsEntry 2 }

snaLuSessnStatsSentRus OBJECT-TYPE
    SYNTAX  Counter32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The number of RUs sent by the local LU."
    ::= { snaLuSessnStatsEntry 3 }

snaLuSessnStatsReceivedRus OBJECT-TYPE
    SYNTAX  Counter32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The number of RUs received by the local LU."
    ::= { snaLuSessnStatsEntry 4 }

snaLuSessnStatsSentNegativeResps OBJECT-TYPE
    SYNTAX  Counter32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The number of negative responses sent by the
        local LU."
    ::= { snaLuSessnStatsEntry 5 }

snaLuSessnStatsReceivedNegativeResps OBJECT-TYPE
    SYNTAX
  Counter32
    MAX-ACCESS  read-only
    STATUS  current
    DESCRIPTION
        "The number of negative responses received by the
        local LU."
    ::= { snaLuSessnStatsEntry 6 }


-- ****************************************************************
-- Traps
-- ****************************************************************
```

```
snaLuTraps OBJECT IDENTIFIER ::= { snaLu 5 }

snaLuStateChangeTrap NOTIFICATION-TYPE
     OBJECTS  {  snaLuOperName,
           snaLuOperSnaName,
          snaLuOperState }
     STATUS  current
     DESCRIPTION
          "This trap indicates that the operational state
          (i.e., snaLuOperState value) of the LU has changed.
          The value of snaLuOperName indicates the name of the
          LU.
          The value of snaLuOperSnaName indicates the SNA name
          of LU.
          The value of snaLuOperState indicates the current
          state after
 change."
     ::= { snaLuTraps 1 }

snaLuSessnBindFailTrap NOTIFICATION-TYPE
     OBJECTS  { snaLuSessnLocalApplName,
          snaLuSessnRemoteLuName,
          snaLuSessnOperState,
          snaLuSessnSenseData }
     STATUS  current
     DESCRIPTION
          "This trap indicates the failure of a BIND.
          The value of snaLuSessnLocalApplName indicates the local
          application name.
          The value of snaLuSessnPartnerName indicates the partner
          name.
          The value of snaLuSessnOperState indicates the current
          state after change.
          The value of snaLuSessnBindFailureReason
          indicates the failure reason.
          The Agent should not generate more than 1 trap of this
          type per minute to minimize the level of management
          traffic on the network."
     ::= { snaLuTraps 2 }

-- ****************************************************************
--
 snaMgtTools group
--
-- Currently this group contains only one table.
-- ****************************************************************
```

```
-- ****************************************************************
-- The following table contains Response Time Monitoring (RTM)
-- configuration information and statistics for LU Type 2s.
-- RTM supports the capability to measure and report end-user
-- response times for dependent LUs. When the RTM state of an LU
-- is 'on', response times for each LU transaction are monitored.
-- A set of ranges is defined (e.g., Range 1 includes the number of
-- transactions with response times less than 1 second) using the
-- "boundary" definitions (e.g., boundary #2 is defined as 3 seconds).
-- A set of counters (one per range) identifies
-- the number of transactions within each response time range.
-- ****************************************************************

snaLuRtmTable OBJECT-TYPE
      SYNTAX  SEQUENCE OF SnaLuRtmEntry
       MAX-ACCESS  not-accessible
      STATUS  current
      DESCRIPTION
            "This table contains Response Time Monitoring (RTM)
            information relating to an LU (Type 2). Each entry
            corresponds to an LU 2 entry in
            snaLuAdminTable."
      ::= { snaMgtTools 1 }

snaLuRtmEntry OBJECT-TYPE
      SYNTAX  SnaLuRtmEntry
      MAX-ACCESS  not-accessible
      STATUS  current
      DESCRIPTION
            "Contains RTM information for an LU (Type 2).
            Each entry is created by the Agent."
      INDEX   { snaLuRtmPuIndex, snaLuRtmLuIndex }
      ::= { snaLuRtmTable 1 }

SnaLuRtmEntry ::= SEQUENCE {
      snaLuRtmPuIndex
            Integer32,
      snaLuRtmLuIndex
            Integer32,
      snaLuRtmState
            INTEGER,
      snaLuRtmStateTime
            TimeStamp,
      snaLuRtmDef
            INTEGER,
      snaLuRtmBoundary1
            Integer32,
```

```
        snaLuRtmBoundary2
            Integer32,
        snaLuRtmBoundary3
            Integer32,
        snaLuRtmBoundary4
            Integer32,
        snaLuRtmCounter1
            Counter32,
        snaLuRtmCounter2
            Counter32,
        snaLuRtmCounter3
            Counter32,
        snaLuRtmCounter4
            Counter32,
        snaLuRtmOverFlows
            Counter32,
        snaLuRtmObjPercent
            Integer32,
        snaLuRtmObjRange
            INTEGER,
        snaLuRtmNumTrans
            Integer32,
        snaLuRtmLastRspTime
            Integer32,
        snaLuRtmAvgRspTime
            Integer32
        }

snaLuRtmPuIndex OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS not-accessible
        STATUS  current
        DESCRIPTION
            "The value identifies the PU 2.0 with which this LU is
            associated."
        ::= { snaLuRtmEntry 1 }

snaLuRtmLuIndex OBJECT-TYPE
        SYNTAX
      Integer32
        MAX-ACCESS  not-accessible
        STATUS  current
        DESCRIPTION
            "The value uniquely identifies an LU in a PU 2.0."
        ::= { snaLuRtmEntry 2 }

snaLuRtmState OBJECT-TYPE
        SYNTAX  INTEGER {
```

```
            off(1),
            on(2)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The value indicates the current RTM state of an LU."
        ::= { snaLuRtmEntry 3 }

    snaLuRtmStateTime  OBJECT-TYPE
        SYNTAX  TimeStamp
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "The timestamp (e.g., the Agent's sysUpTime value)
            when this session's RTM state (e.g., snaLuRtmState)
            changes value."
        ::= { snaLuRtmEntry 4 }

    snaLuRtmDef OBJECT-TYPE
        SYNTAX  INTEGER {
            firstChar(1),
            kb(2),
            cdeb(3)
            }
        MAX-ACCESS  read-only

       STATUS  current
        DESCRIPTION
            "The value indicates the mode of measurement for this
            RTM request.  The values have following meaning:
              firstChar(1) - time to first character on screen
              kb(2) - time to keyboard usable by operator
              cdeb(3) - time to Change Direction/End Bracket."
        ::= { snaLuRtmEntry 5 }

    snaLuRtmBoundary1 OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This object contains the value of the first boundary
            in units of 1/10th of a second."
        ::= { snaLuRtmEntry 6 }

    snaLuRtmBoundary2 OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  read-only
```

```
        STATUS  current
        DESCRIPTION
                "This object contains the value of the second boundary
                 in units of 1/10th of a second."
        ::= { snaLuRtmEntry 7 }

snaLuRtmBoundary3 OBJECT-TYPE
         SYNTAX  Integer32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "This object contains the value of the third boundary
                 in units of 1/10th of a second."
        ::= { snaLuRtmEntry 8 }

snaLuRtmBoundary4 OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "This object contains the value of the fourth boundary
                in units of 1/10th of a second."
        ::= { snaLuRtmEntry 9 }

snaLuRtmCounter1 OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "This value indicates the number of transactions which
                fall in the range specified by the first boundary."
        ::= { snaLuRtmEntry 10 }

snaLuRtmCounter2 OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
                "This value indicates
 the number of transactions which
                fall in the range specified by the second boundary."
        ::= { snaLuRtmEntry 11 }

snaLuRtmCounter3 OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
```

```
            "This value indicates the number of transactions which
            fall in the range specified by the third boundary."
        ::= { snaLuRtmEntry 12 }

snaLuRtmCounter4 OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This value indicates the number of transactions which
            fall in the range specified by the fourth boundary."
        ::= { snaLuRtmEntry 13 }

snaLuRtmOverFlows OBJECT-TYPE
        SYNTAX  Counter32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This value indicates the number of transactions which
            exceed the highest range specified by
 the
            boundaries."
        ::= { snaLuRtmEntry 14 }

snaLuRtmObjPercent OBJECT-TYPE
        SYNTAX  Integer32
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This value indicates the desired percentage of
            transactions which should be under a designated
            boundary range indicated by snaLuRtmObjRange."
        ::= { snaLuRtmEntry 15 }

snaLuRtmObjRange OBJECT-TYPE
         SYNTAX  INTEGER {
            other(1),
            range1(2),
            range2(3),
            range3(4),
            range4(5),
            range5(6)
            }
        MAX-ACCESS  read-only
        STATUS  current
        DESCRIPTION
            "This value indicates the designated boundary range to
            which the snaLuRtmObject refers.
```

```
            The values have the following meanings:
              other(1)   - not specified
              range1(2)  - less than boundary
 1
              range2(3)  - between boundary 1 and 2
              range3(4)  - between boundary 2 and 3
              range4(5)  - between boundary 3 and 4
              range5(6)  - greater than boundary 4."
      ::= { snaLuRtmEntry 16 }

snaLuRtmNumTrans OBJECT-TYPE
      SYNTAX  Integer32
      MAX-ACCESS  read-only
      STATUS  current
      DESCRIPTION
            "This value indicates the total number of transactions
            executed since the RTM monitoring began (i.e.,
            snaLuRtmState changed to 'on(2)') for this LU."
      ::= { snaLuRtmEntry 17 }

snaLuRtmLastRspTime OBJECT-TYPE
      SYNTAX  Integer32
      MAX-ACCESS  read-only
      STATUS  current
      DESCRIPTION
            "This value indicates the response time for the last
            transaction in units of 1/10th of a second."
      ::= { snaLuRtmEntry 18 }

snaLuRtmAvgRspTime OBJECT-TYPE
      SYNTAX  Integer32
      MAX-ACCESS  read-only
       STATUS  current
      DESCRIPTION
            "This value indicates the average response time for all
            transactions in units of 1/10th of a second."
      ::= { snaLuRtmEntry 19 }


-- ****************************************************************
-- Conformance information
-- ****************************************************************

snanauConformance       OBJECT IDENTIFIER ::= { snanauMIB 2 }

snanauCompliances       OBJECT IDENTIFIER ::= {snanauConformance 1 }
snanauGroups            OBJECT IDENTIFIER ::= {snanauConformance 2 }
```

```
-- Compliance statements
snanauCompliance  MODULE-COMPLIANCE
      STATUS  current
      DESCRIPTION
            "The compliance statement for the SNMPv2 entities
            which implement the snanau MIB."
      MODULE  -- this module

--      Unconditionally mandatory groups
            MANDATORY-GROUPS  { snaNodeGroup,
                  snaLuGroup,
                  snaSessionGroup
 }

--      Conditionally mandatory groups
            GROUP  snaPu20Group
            DESCRIPTION
                  "The snaPu20Group is mandatory only for those
                  entities which implement PU type 2.0"
            GROUP  snaMgtToolsRtmGroup
            DESCRIPTION
                  "The snaMgtToolsGroup is mandatory only for
                  those entities which implement LU type 2
                  and RTM."

--      Refinement of requirements for objects access.
--      The Agent which does not implement row creation for
--      snaNodeAdminTable, snaNodeLinkAdminTable and
--      snaLuAdminTable must at least accept
--      objects modification (read-write access instead of
--      read-create).

            OBJECT  snaNodeAdminName
            MIN-ACCESS  read-write
            DESCRIPTION
                  "An Agent is required to implement read-write
                  access to this object."

             OBJECT  snaNodeAdminType
            MIN-ACCESS  read-write
            DESCRIPTION
                  "An Agent is required to implement read-write
                  access to this object."

            OBJECT  snaNodeAdminXidFormat
            MIN-ACCESS  read-write
            DESCRIPTION
                  "An Agent is required to implement read-write
```

access to this object."

OBJECT snaNodeAdminBlockNum
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeAdminIdNum
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeAdminEnablingMethod
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeAdminLuTermDefault
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeAdminMaxLu
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeAdminHostDescription
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeAdminStopMethod
MIN-ACCESS read-write
DESCRIPTION
"An
Agent is required to implement read-write
access to this object."

OBJECT snaNodeAdminState
MIN-ACCESS read-write
DESCRIPTION

"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeLinkAdminSpecific
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaNodeLinkAdminMaxPiu
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."
OBJECT snaLuAdminName
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this
object."

OBJECT snaLuAdminSnaName
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaLuAdminType
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaLuAdminDepType
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaLuAdminLocalAddress
MIN-ACCESS read-write
DESCRIPTION
"An Agent is required to implement read-write
access to this object."

OBJECT snaLuAdminDisplayModel
MIN-ACCESS

```
 read-write
          DESCRIPTION
               "An Agent is required to implement read-write
               access to this object."

          OBJECT  snaLuAdminTerm
          MIN-ACCESS  read-write
          DESCRIPTION
               "An Agent is required to implement read-write
               access to this object."

     ::= {snanauCompliances 1 }


-- Units of conformance

snaNodeGroup  OBJECT-GROUP
     OBJECTS  { snaNodeAdminName,
          snaNodeAdminType,
          snaNodeAdminXidFormat,
          snaNodeAdminBlockNum,
          snaNodeAdminIdNum,
          snaNodeAdminEnablingMethod,
          snaNodeAdminLuTermDefault,
          snaNodeAdminMaxLu,
          snaNodeAdminHostDescription,
          snaNodeAdminStopMethod,
          snaNodeAdminState,
          snaNodeAdminRowStatus,
          snaNodeAdminTableLastChange,
          snaNodeOperName,
           snaNodeOperType,
          snaNodeOperXidFormat,
          snaNodeOperBlockNum,
          snaNodeOperIdNum,
          snaNodeOperEnablingMethod,
          snaNodeOperLuTermDefault,
          snaNodeOperMaxLu,
          snaNodeOperHostDescription,
          snaNodeOperStopMethod,
          snaNodeOperState,
          snaNodeOperHostSscpId,
          snaNodeOperStartTime,
          snaNodeOperLastStateChange,
          snaNodeOperActFailures,
          snaNodeOperActFailureReason,
          snaNodeOperTableLastChange,
          snaNodeLinkAdminSpecific,
```

```
            snaNodeLinkAdminMaxPiu,
            snaNodeLinkAdminRowStatus,
            snaNodeLinkAdminTableLastChange,
            snaNodeLinkOperSpecific,
            snaNodeLinkOperMaxPiu,
            snaNodeLinkOperTableLastChange }
        STATUS  current
        DESCRIPTION

        "A collection of objects providing the
            instrumentation of SNA nodes."
        ::= { snanauGroups 1 }

snaLuGroup  OBJECT-GROUP
        OBJECTS  { snaLuAdminName,
            snaLuAdminSnaName,
            snaLuAdminType,
            snaLuAdminDepType,
            snaLuAdminLocalAddress,
            snaLuAdminDisplayModel,
            snaLuAdminTerm,
            snaLuAdminRowStatus,
            snaLuOperName,
            snaLuOperSnaName,
            snaLuOperType,
            snaLuOperDepType,
            snaLuOperLocalAddress,
            snaLuOperDisplayModel,
            snaLuOperTerm,
            snaLuOperState,
            snaLuOperSessnCount }
        STATUS  current
        DESCRIPTION
            "A collection of objects providing the
            instrumentation of SNA LUs."
        ::= { snanauGroups 2 }

snaSessionGroup  OBJECT-GROUP
        OBJECTS  { snaLuSessnRluIndex,

       snaLuSessnIndex,
            snaLuSessnLocalApplName,
            snaLuSessnRemoteLuName,
            snaLuSessnMaxSndRuSize,
            snaLuSessnMaxRcvRuSize,
            snaLuSessnSndPacingSize,
            snaLuSessnRcvPacingSize,
            snaLuSessnActiveTime,
```

```
            snaLuSessnAdminState,
            snaLuSessnOperState,
            snaLuSessnSenseData,
            snaLuSessnTerminationRu,
            snaLuSessnUnbindType,
            snaLuSessnLinkIndex,
            snaLuSessnStatsSentBytes,
            snaLuSessnStatsReceivedBytes,
            snaLuSessnStatsSentRus,
            snaLuSessnStatsReceivedRus,
            snaLuSessnStatsSentNegativeResps,
            snaLuSessnStatsReceivedNegativeResps }
        STATUS  current
        DESCRIPTION
            "A collection of objects providing the
            instrumentation of SNA sessions."
        ::= { snanauGroups 3 }

snaPu20Group
  OBJECT-GROUP
        OBJECTS  { snaPu20StatsSentBytes,
            snaPu20StatsReceivedBytes,
            snaPu20StatsSentPius,
            snaPu20StatsReceivedPius,
            snaPu20StatsSentNegativeResps,
            snaPu20StatsReceivedNegativeResps,
            snaPu20StatsActLus,
            snaPu20StatsInActLus,
            snaPu20StatsBindLus }
        STATUS  current
        DESCRIPTION
            "A collection of objects providing the
            instrumentation of PU 2.0."
        ::= { snanauGroups 4 }

snaMgtToolsRtmGroup  OBJECT-GROUP
        OBJECTS  { snaLuRtmState,
            snaLuRtmStateTime,
            snaLuRtmDef,
            snaLuRtmBoundary1,
            snaLuRtmBoundary2,
            snaLuRtmBoundary3,
            snaLuRtmBoundary4,
            snaLuRtmCounter1,
            snaLuRtmCounter2,
            snaLuRtmCounter3,
            snaLuRtmCounter4,
            snaLuRtmOverFlows,
```

```
            snaLuRtmObjPercent,
            snaLuRtmObjRange,
            snaLuRtmNumTrans,
            snaLuRtmLastRspTime,
            snaLuRtmAvgRspTime }
    STATUS  current
    DESCRIPTION
            "A collection of objects providing the
            instrumentation of RTM for SNA LU 2.0."
    ::= { snanauGroups 5 }

-- end of conformance statement


END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/SNA-NAU-MIB
No license file was found, but licenses were detected in source scan.

```
Modem-MIB DEFINITIONS ::= BEGIN


IMPORTS
  MODULE-IDENTITY, OBJECT-TYPE, OBJECT-IDENTITY,
  Counter32, Integer32 FROM SNMPv2-SMI
  DisplayString FROM SNMPv2-TC
  MODULE-COMPLIANCE, OBJECT-GROUP FROM SNMPv2-CONF
  mib-2 FROM RFC1213-MIB;


mdmMIB MODULE-IDENTITY
  LAST-UPDATED "9406120000Z"
  ORGANIZATION "IETF Modem Management Working Group"
  CONTACT-INFO
        "       Steven Waldbusser
         Postal: Carnegie Mellon University
                 5000 Forbes Ave
                 Pittsburgh, PA, 15213
                 US

           Tel: +1 412 268 6628
           Fax: +1 412 268 4987
        E-mail: waldbusser@cmu.edu"
  DESCRIPTION
       "The MIB module for management of dial-up modems."
  ::= { mdmMib 1 }
```

```
mdmMib OBJECT IDENTIFIER ::= { mib-2 38 }

mdmMIBObjects OBJECT IDENTIFIER ::= { mdmMIB 1 }


-- conformance information

mdmConformance OBJECT IDENTIFIER
 ::= { mdmMIB 2 }

mdmCompliances OBJECT IDENTIFIER ::= { mdmConformance 1 }
mdmGroups      OBJECT IDENTIFIER ::= { mdmConformance 2 }

-- units of conformance

mdmIDGroup    OBJECT-GROUP
  OBJECTS   { mdmIDManufacturerOID, mdmIDProductDetails }
  STATUS    current
  DESCRIPTION
        "A collection of objects that identify the manufacturer and
        model information for a modem."
  ::= { mdmGroups 1 }

mdmLineInterfaceGroup    OBJECT-GROUP
  OBJECTS { mdmLineCarrierLossTime,
     mdmLineState, mdmLineCapabilitiesID,
     mdmLineCapabilitiesEnableRequested,
     mdmLineCapabilitiesEnableGranted }
  STATUS  current
  DESCRIPTION
        "A collection of objects that describe the configuration and
        state of the modem's line interface."
  ::= { mdmGroups 2 }

mdmDTEInterfaceGroup    OBJECT-GROUP
  OBJECTS { mdmDTEActionDTROnToOff, mdmDTEActionDTROffToOn,
            mdmDTESyncTimingSource, mdmDTESyncAsyncMode,

   mdmDTEInactivityTimeout }
  STATUS      current
  DESCRIPTION
        "A collection of objects that describe the configuration and
        state of the modem's DTE interface."
  ::= { mdmGroups 3 }

mdmCallControlGroup    OBJECT-GROUP
  OBJECTS { mdmCCRingsBeforeAnswer,
     mdmCCCallSetUpFailTimer, mdmCCResultCodeEnable,
```

```
      mdmCCEscapeAction, mdmCCCallDuration,
      mdmCCConnectionFailReason, mdmCCStoredDialString }
  STATUS  current
  DESCRIPTION
        "A collection of objects that describe the configuration of
        call control capabilities on the modem and the status of
        calls placed with this modem."
  ::= { mdmGroups 4 }

mdmErrorControlGroup   OBJECT-GROUP
  OBJECTS { mdmECErrorControlUsed }
  STATUS  current
  DESCRIPTION
        "A collection of objects that describe the configuration and
        state of error control on a modem."
  ::= { mdmGroups 5 }

mdmDataCompressionGroup   OBJECT-GROUP
  OBJECTS
 { mdmDCCompressionTypeUsed }
  STATUS  current
  DESCRIPTION
        "A collection of objects that describe the configuration and
        state of data compression on a modem."
  ::= { mdmGroups 6 }

mdmSignalConvertorGroup   OBJECT-GROUP
OBJECTS { mdmSCCurrentLineReceiveRate, mdmSCCurrentLineTransmitRate,
       mdmSCInitialLineReceiveRate, mdmSCInitialLineTransmitRate,
       mdmSCModulationSchemeUsed }
  STATUS  current
  DESCRIPTION
        "A collection of objects that describe the configuration and
        state of error control on a modem."
  ::= { mdmGroups 7 }

mdmStatisticsGroup  OBJECT-GROUP
  OBJECTS { mdmStatsRingNoAnswers,
      mdmStatsIncomingConnectionFailures,
      mdmStatsIncomingConnectionCompletions,
      mdmStatsFailedDialAttempts,
      mdmStatsOutgoingConnectionFailures,
      mdmStatsOutgoingConnectionCompletions,
      mdmStatsRetrains,
      mdmStats2400OrLessConnections, mdmStats2400To14400Connections,
       mdmStatsGreaterThan14400Connections,
      mdmStatsErrorControlledConnections,
      mdmStatsCompressedConnections,
```

```
      mdmStatsCompressionEfficiency,
      mdmStatsSentOctets, mdmStatsReceivedOctets,
      mdmStatsSentDataFrames, mdmStatsReceivedDataFrames,
      mdmStatsResentFrames, mdmStatsErrorFrames }
  STATUS  current
  DESCRIPTION
        "A collection of objects that describe the state of calls on
        this modem."
  ::= { mdmGroups 8 }

mdmNumber OBJECT-TYPE
  SYNTAX  Integer32
  MAX-ACCESS  read-only
  STATUS  current
  DESCRIPTION
        "The number of modem rows in the modem table.  This value
        defines the maximum value of the mdmIndex object."
  ::= { mdmMIBObjects 1 }

-- The modem ID table.

mdmIDTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmIDEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The base table for the modems managed by this MIB.  The
        mdmLineTable,
 mdmDTEInterfaceTable, mdmCallControlTable, and
        mdmStatsTable all augment the rows defined in this table."
  ::= { mdmMIBObjects 2 }

mdmIDEntry OBJECT-TYPE
  SYNTAX      MdmIDEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "Entries in this table are created only by the agent. One
        entry exists for each modem managed by the agent."
  INDEX       { mdmIndex }
  ::= { mdmIDTable 1 }

MdmIDEntry ::= SEQUENCE {
  mdmIndex              Integer32,
  mdmIDManufacturerOID    OBJECT IDENTIFIER,
  mdmIDProductDetails     DisplayString
}
```

```
mdmIndex OBJECT-TYPE
  SYNTAX      Integer32 (1..65535)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "A unique number for each modem that ranges from 1 to
        mdmNumber.  The value must remain constant at least from one
        re-initialization of the network management agent to the
        next."
  ::= { mdmIDEntry 1
 }

mdmIDManufacturerOID OBJECT-TYPE
  SYNTAX      OBJECT IDENTIFIER
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "This value is intended to identify the manufacturer, model,
        and version of this modem.  This may be used to identify the
        existance of enterprise-specific functions and behaviours."
  REFERENCE
        "V.58 attribute manufacturerID subfield ManufacturerOI"
  ::= { mdmIDEntry 2 }

mdmIDProductDetails OBJECT-TYPE
  SYNTAX      DisplayString (SIZE (0..79))
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "A textual description of this device, including the
        manufacturer's name, modem model name, hardware revision,
        firmware revision, and optionally, its serial number.  The
        exact format of this description is defined by the vendor.
        This description may only contain characters from the NVT
        ASCII character set."
  REFERENCE
         "V.58 attribute manufacturerID subfield productDetails"
  ::= { mdmIDEntry 3 }

-- The modem Line Interface Table

mdmLineTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmLineEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The modem Line Table augments the modem ID table."
  ::= { mdmMIBObjects 3 }
```

```
mdmLineEntry OBJECT-TYPE
  SYNTAX      MdmLineEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "Entries in this table are created only by the agent. One
        entry exists for each modem managed by the agent."
  AUGMENTS    { mdmIDEntry }
  ::= { mdmLineTable 1 }

MdmLineEntry ::= SEQUENCE {
  mdmLineCarrierLossTime         Integer32,
  mdmLineState                   INTEGER
}

mdmLineCarrierLossTime OBJECT-TYPE
  SYNTAX      Integer32 (1..255)
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "Duration in 10ths of a second the modem waits after
 loss of
        carrier before hanging up.  If this value is set to `255',
        the modem will not hang up upon loss of carrier.  This
        allows the modem to distinguish between a momentary lapse in
        line quality and a true disconnect and can be useful to tune
        the tolerance of the modem to lines of poor quality."
  REFERENCE "V.58 lineSignalFailDisconnectTimer"
  ::= { mdmLineEntry 1 }

mdmLineState OBJECT-TYPE
  SYNTAX      INTEGER {
                unknown(1),
                onHook(2),
                offHook(3),  -- and not connected
                connected(4),
                busiedOut(5),
                reset(6)
              }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "Allows the inspection and alteration of the state of the
        modem.  Management commands may change the state to `on-
        hook', `busied-out', or `reset' from any state.  No other
```

```
        alterations are permitted from the management protocol.
        When this object is set to reset, the modem shall be reset
        and the value will change to the modem's new, implementation
        dependent state."
  ::= { mdmLineEntry 2 }

mdmLineCapabilitiesTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmLineCapabilitiesEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "A list of protocol capabilities for this modem."
  ::= { mdmMIBObjects 4 }

mdmLineCapabilitiesEntry OBJECT-TYPE
  SYNTAX      MdmLineCapabilitiesEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "A listing of the protocol(s) that this modem is capable of.
        Entries in this table are created only by the agent.  One
        entry exists for each protocol that the modem is capable of,
        regardless of whether that protocol is enabled or not.

        This table is useful for providing an
 inventory of the
        capabilities on a modem, and allowing the manager to enable
        or disable capabilities from the menu of available
        possibilities.  Row creation is not required to enable or
        disable capabilities."
  INDEX       { mdmIndex, mdmLineCapabilitiesIndex }
  ::= { mdmLineCapabilitiesTable 1 }

MdmLineCapabilitiesEntry ::= SEQUENCE {
  mdmLineCapabilitiesIndex           Integer32,
  mdmLineCapabilitiesID              OBJECT IDENTIFIER,
  mdmLineCapabilitiesEnableRequested  INTEGER,
  mdmLineCapabilitiesEnableGranted    INTEGER
}

mdmLineCapabilitiesIndex OBJECT-TYPE
  SYNTAX      Integer32
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "A unique index for this capabilities entry."
  ::= { mdmLineCapabilitiesEntry 1 }
```

```
mdmLineCapabilitiesID OBJECT-TYPE
  SYNTAX      OBJECT IDENTIFIER
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "An identifier for
 this capability.  Standard protocol
        capabilities will have identifiers registered in this
        document or other companion standards documents.
        Proprietary protocol capabilities will be registered by
        their respective organization.  All capabilities, standard
        or vendor-specific, shall be registered in this table."
  ::= { mdmLineCapabilitiesEntry 2 }

mdmLineCapabilitiesEnableRequested OBJECT-TYPE
  SYNTAX      INTEGER {
                disabled(1),
                optional(2),
                preferred(3)
              }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "The requested configuration of this capability.  If this
        value is 'disabled(1)', this is a request to disable this
        protocol.  If this value is 'preferred(3)', this is a
        request to enable this protocol, and to prefer it in any
        negotiation over other appropriate protocols
 that have a
        value of 'optional(2)'."
  DEFVAL      { preferred }
  ::= { mdmLineCapabilitiesEntry 3 }

mdmLineCapabilitiesEnableGranted OBJECT-TYPE
  SYNTAX      INTEGER {
                disabled(1),
                optional(2),
                preferred(3)
              }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The actual configuration of this capability.  The agent
        shall attempt to set this as close as possible to the
        associated mdmLineCapabilitiesEnableRequested value.  The
        agent shall make this determination in an implementation-
        specific manner that may take into account the configuration
        of other capabilities or other considerations.  The modem
```

```
        will choose in an implementation-specific manner between
        multiple mutually-exclusive capabilities that each have the
        same (non-disabled) value.  However, the modem must prefer
         all capabilities with a value of 'preferred(3)' over all
        capabilities with a value of 'optional(2)'.

        In other words, if there are one or more mutually-exclusive
        capabilities (e.g. V.32 and V.32bis) that are set to
        `preferred', the agent must choose one in an
        implementation-specific manner.  Otherwise, if there are one
        or more mutually-exclusive capabilities that are set to
        `optional', the agent must choose one in an implementation-
        specific manner."
  ::= { mdmLineCapabilitiesEntry 4 }

mdmLineCapabilities   OBJECT IDENTIFIER ::= { mdmMIBObjects 5 }

mdmLineCapabilitiesV21 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.21"
  ::= { mdmLineCapabilities 1 }

mdmLineCapabilitiesV22 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.22"
  ::= { mdmLineCapabilities 2 }

mdmLineCapabilitiesV22bis OBJECT-IDENTITY
  STATUS  current
   DESCRIPTION
        "ITU V.22bis"
  ::= { mdmLineCapabilities 3 }

mdmLineCapabilitiesV23CC OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.23CC"
  ::= { mdmLineCapabilities 4 }

mdmLineCapabilitiesV23SC OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.23SC"
  ::= { mdmLineCapabilities 5 }

mdmLineCapabilitiesV25bis OBJECT-IDENTITY
```

```
  STATUS  current
  DESCRIPTION
        "ITU V.25bis"
  ::= { mdmLineCapabilities 6 }

mdmLineCapabilitiesV26bis OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.26bis"
  ::= { mdmLineCapabilities 7 }

mdmLineCapabilitiesV26ter OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.26ter"
  ::= { mdmLineCapabilities 8 }

mdmLineCapabilitiesV27ter OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.27ter"
  ::= { mdmLineCapabilities 9 }

mdmLineCapabilitiesV32 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.32"
   ::= { mdmLineCapabilities 10 }

mdmLineCapabilitiesV32bis OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.32bis"
  ::= { mdmLineCapabilities 11 }

mdmLineCapabilitiesV32terbo OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.32terbo"
  ::= { mdmLineCapabilities 12 }

mdmLineCapabilitiesVFC OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.FC"
  ::= { mdmLineCapabilities 13 }

mdmLineCapabilitiesV34 OBJECT-IDENTITY
```

```
  STATUS  current
  DESCRIPTION
        "ITU V.34"
  ::= { mdmLineCapabilities 14 }

mdmLineCapabilitiesV42 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.42"
  ::= { mdmLineCapabilities 15 }

mdmLineCapabilitiesV42bis OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.42bis"
  ::= { mdmLineCapabilities 16 }

mdmLineCapabilitiesMNP1 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP1"
  ::= { mdmLineCapabilities 17 }

mdmLineCapabilitiesMNP2
 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP2"
  ::= { mdmLineCapabilities 18 }

mdmLineCapabilitiesMNP3 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP3"
  ::= { mdmLineCapabilities 19 }

mdmLineCapabilitiesMNP4 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP4"
  ::= { mdmLineCapabilities 20 }

mdmLineCapabilitiesMNP5 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP5"
  ::= { mdmLineCapabilities 21 }
```

```
mdmLineCapabilitiesMNP6 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP6"
  ::= { mdmLineCapabilities 22 }

mdmLineCapabilitiesMNP7 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP7"
  ::= { mdmLineCapabilities 23 }

mdmLineCapabilitiesMNP8 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP8"
  ::= { mdmLineCapabilities 24 }

mdmLineCapabilitiesMNP9 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION

  "MNP9"
  ::= { mdmLineCapabilities 25 }

mdmLineCapabilitiesMNP10 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "MNP10"
  ::= { mdmLineCapabilities 26 }

mdmLineCapabilitiesV29 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.29"
  ::= { mdmLineCapabilities 27 }

mdmLineCapabilitiesV33 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "ITU V.33"
  ::= { mdmLineCapabilities 28 }

mdmLineCapabilitiesBell208 OBJECT-IDENTITY
  STATUS  current
  DESCRIPTION
        "Bell 208"
  ::= { mdmLineCapabilities 29 }
```

```
-- DTE Interface Table

mdmDTEInterfaceTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmDTEInterfaceEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The modem DTE Interface Table augments the modem ID table."
  ::= { mdmMIBObjects 6 }

mdmDTEInterfaceEntry OBJECT-TYPE
  SYNTAX      MdmDTEInterfaceEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
         "Entries in this table are created only by the agent. One
        entry exists for each modem managed by the agent."
  AUGMENTS    { mdmIDEntry }
  ::= { mdmDTEInterfaceTable 1 }

MdmDTEInterfaceEntry ::= SEQUENCE {
  mdmDTEActionDTROnToOff      INTEGER,
  mdmDTEActionDTROffToOn      INTEGER,
  mdmDTESyncTimingSource      INTEGER,
  mdmDTESyncAsyncMode         INTEGER,
  mdmDTEInactivityTimeout     Integer32
}

mdmDTEActionDTROnToOff OBJECT-TYPE
  SYNTAX      INTEGER {
                ignore(1),
                escapeToCommandMode(2),
                disconnectCall(3),
                resetModem(4)
              }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "Defines the action the modem will take when DTR drops.

        If the value is set to ignore(1), the modem takes no action
        when DTR drops.  Typically, mdmDTEActionDTROffToOn would
        also be set to ignore(1) if this object
 is set to ignore(1).

        If the value is escapeToCommandMode(2), the modem remains
```

```
        connected and enters command mode.  If the value is
        disconnectCall(3), the current call (if any) is terminated
        and the modem will not auto-answer while DTR is off.  If the
        value is resetModem(4), the current call (if any) is
        terminated and the modem is reset."
    DEFVAL      { disconnectCall }
    ::= { mdmDTEInterfaceEntry 1 }

mdmDTEActionDTROffToOn OBJECT-TYPE
    SYNTAX      INTEGER {
                    ignore(1),
                    enableDial(2),
                    autoAnswerEnable(3),
                    establishConnection(4)
                }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "Defines the action the modem will take when DTR is raised.

        If the value is set to ignore(1), the modem takes no action
        when DTR is raised.  Typically, mdmDTEActionDTROnToOff would
         also be set to ignore(1) if this object is set to ignore(1).

        If the value is set to enableDial(2), the modem prepares to
        dial an outgoing call.  If the value is set to
        autoAnswerEnable(3), the modem will be configured to answer
        any incoming call.  If the value is set to
        establishConnection(4), the modem dials an implementation
        specific number.

        Immediately after any reset or power-on of the modem, if the
        DTR is high, the action specified here will be executed."
    DEFVAL      { autoAnswerEnable }
    ::= { mdmDTEInterfaceEntry 2 }

mdmDTESyncTimingSource OBJECT-TYPE
    SYNTAX      INTEGER {
                    internal(1),
                    external(2),
                    loopback(3),
                    network(4)
                }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The clock source for synchronous transmissions.  If set to
```

```
          internal(1), the modem is the clock source and sends the
          clock signals to the DTE.  If set to external(2), the
          transmit clock signals are provided by the DTE.  If
          loopback(3), the modem receiver clock is used for the
          transmit clock.  If network(4), the clock signals are
          supplied by the DCE interface.

          If the modem is not in synchronous mode, setting this object
          will have no effect on the current operations of the modem."
    REFERENCE   "V.58 transmitClockSource"
    DEFVAL      { internal }
    ::= { mdmDTEInterfaceEntry 3 }

mdmDTESyncAsyncMode OBJECT-TYPE
    SYNTAX      INTEGER {
                  async(1),
                  sync(2),
                  syncAfterDial(3)
                }
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
          "The operational mode of the modem.  If the value is
          syncAfterDial(3), the modem will accept commands in

         asynchronous mode and change to synchronous mode to pass
          data after a dial sequence has been executed."
    DEFVAL      { async }
    ::= { mdmDTEInterfaceEntry 4 }

mdmDTEInactivityTimeout OBJECT-TYPE
    SYNTAX      Integer32 (0..65535)
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
          "The amount of idle time in minutes that the modem will wait
          before disconnecting a connection.  When a call is connected
          and no data is transferred (continuous marking condition) on
          both circuits 103 and 104 for the specified time, the DCE
          disconnects the call. If the value is 0, no idle disconnect
          will occur.  This function applies to asynchronous dial
          operations only and is intended for administrative control
          over idle connections."
    REFERENCE   "V.58 inactivityTimerSelect"
    DEFVAL { 0 }
    ::= { mdmDTEInterfaceEntry 5 }
```

```
-- The Call Control Table

mdmCallControlTable
 OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmCallControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The modem Call Control Table augments the modem ID table."
  ::= { mdmMIBObjects 7 }

mdmCallControlEntry OBJECT-TYPE
  SYNTAX      MdmCallControlEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "Entries in this table are created only by the agent. One
        entry exists for each modem managed by the agent."
  AUGMENTS    { mdmIDEntry }
  ::= { mdmCallControlTable 1 }

MdmCallControlEntry ::= SEQUENCE {
  mdmCCRingsBeforeAnswer      Integer32,
  mdmCCCallSetUpFailTimer     Integer32,
  mdmCCResultCodeEnable       INTEGER,
  mdmCCEscapeAction           INTEGER,
  mdmCCCallDuration           Integer32,
  mdmCCConnectionFailReason   INTEGER
}

mdmCCRingsBeforeAnswer OBJECT-TYPE
  SYNTAX      Integer32
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION

       "Determines which ring the modem will wait to answer the
        phone on.  If this value is `0', the modem will not go
        offhook and answer a call when a ring signal is detected."
  REFERENCE   "V.58 ringsBeforeAnswer"
  DEFVAL      { 1 }
  ::= { mdmCallControlEntry 1 }

mdmCCCallSetUpFailTimer OBJECT-TYPE
  SYNTAX      Integer32 (0..255)
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
```

```
        "This parameter specifies the amount of time, in seconds,
        that the modem shall allow between either answering a call
        (automatically or manually) or completion of dialing, and
        establishment of a connection with the remote modem. If no
        connection is established during this time, the modem
        disconnects from the line and returns a result code
        indicating the cause of the disconnection. In TIA-602, this
        is controlled by the value in the S7 register."
  REFERENCE   "V.58
 callSetUpFailTimer"
  DEFVAL      { 30 }
  ::= { mdmCallControlEntry 2 }

mdmCCResultCodeEnable OBJECT-TYPE
  SYNTAX      INTEGER {
                disabled(1),
                numericEnabled(2),
                verboseEnabled(3)
              }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "When disabled, the DCE shall issue no 'result codes' of any
        kind to the DTE either in response to unsolicited events
        (eg. ring signal), or commands. In TIA-602, this is
        controlled by the ATQ command.  When numericEnabled, the DCE
        shall issue result codes in numeric form.  When
        verboseEnabled, the DCE shall issue result codes in a
        verbose, textual form."
  REFERENCE   "V.58 responseModeSelect"
  DEFVAL      { verboseEnabled }
  ::= { mdmCallControlEntry 3 }

mdmCCEscapeAction OBJECT-TYPE
  SYNTAX      INTEGER {
                ignoreEscape(1),

    hangUp(2),
                enterCommandMode(3)
              }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "The modem's action upon successfully recognizing the
        'escape to command mode' character sequence."
  DEFVAL { ignoreEscape }
  ::= { mdmCallControlEntry 4 }
```

```
-- Call status portion of the call control table

mdmCCCallDuration OBJECT-TYPE
  SYNTAX      Integer32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "Present or last completed connection time in seconds. If
        there have been no previous connections, this value should
        be -1."
  ::= { mdmCallControlEntry 5 }


mdmCCConnectionFailReason OBJECT-TYPE
  SYNTAX      INTEGER {
            -- General
                  unknown(1),
                  other(2),
                  managementCommand(3),
                  inactivityTimeout(4),
                  mnpIncompatibility(5),

                 protocolError(6),
            -- DCE
                  powerLoss(10),
                  equipmentFailure(11),
            -- DTE Interface
                  dtrDrop(20),
            -- Line Interface
                  noDialTone(30),
                  lineBusy(31),
                  noAnswer(32),
                  voiceDetected(33),
            -- Signal Converter
                  carrierLost(40),
                  trainingFailed(41),
                  faxDetected(42)
     }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION

        "Indicates the reason that the last connection or attempt
        failed. The meaning of each reason code is explained below.

          unknown:
        This code means the failure reason is unknown or
        there has been no previous call.
```

other:
This code used when no other code is applicable.
Additional vendor information may be available
elsewhere.

managementCommand:
A management command terminated the call. These
commands include escaping to command mode, initiating
dialing, restoring lines, and disconnecting.

inactivityTimeout:
The call was terminated because it was inactive for
at the minimum duration specified.

mnpIncompatibility:
The modems are unable to resolve MNP protocol
differences.

protocolError:
An error occured in one of protocol in use. Further
information is required to determine in which
protocol the error occurred, and the exact nature of
the error.

powerLoss:
The modem lost power and disconnected the call.

equipmentFailure:
The modem equipment failed.

dtrDrop:

DTR has been turned off while the modem is to
disconnect on DTR drop. (Ref: V.58 cct108TurnedOff)

noDialTone:
If the modem is to monitor for call progress tones,
but the modem has failed to detect dial tone while
attempting to dial a number.

lineBusy:
Busy signal is detected while busy signal detection
is enabled, or while the 'W' or '@' dial modifier is
used. (Ref: V.58 engagedTone)

noAnswer:
The call was not answered.

```
            voiceDetected:
          A voice was detected on the call.

            carrierLost:
          Indicates that the modem has disconnected due to
          detection of loss of carrier.  In TIA-602, the S10
          register determines the time that loss of carrier
          must be detected before the modem disconnects.

            trainingFailed:
          Indicates that the modems did
 not successfully train
          and reach data mode on the previous connection.

            faxDetected:
          A fax was detected on the call."
  REFERENCE   "V.58 callCleared"
  ::= { mdmCallControlEntry 6 }

-- The Stored Dial String table

mdmCCStoredDialStringTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmCCStoredDialStringEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The table of stored dial strings."
  REFERENCE   "V.58 telephoneNumbers"
  ::= { mdmMIBObjects 8 }

mdmCCStoredDialStringEntry OBJECT-TYPE
  SYNTAX      MdmCCStoredDialStringEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "A stored dial string."
  INDEX  { mdmIndex, mdmCCStoredDialStringIndex }
  ::= { mdmCCStoredDialStringTable 1 }

MdmCCStoredDialStringEntry ::= SEQUENCE {
  mdmCCStoredDialStringIndex     Integer32,
  mdmCCStoredDialString          DisplayString
}

mdmCCStoredDialStringIndex OBJECT-TYPE
   SYNTAX      Integer32 (0..65535)
  MAX-ACCESS  not-accessible
```

```
  STATUS      current
  DESCRIPTION
        "The unique index of a particular dial string."
  ::= { mdmCCStoredDialStringEntry 1 }

mdmCCStoredDialString OBJECT-TYPE
  SYNTAX      DisplayString (SIZE(0..64))
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
        "A dial string stored in the modem."
  ::= { mdmCCStoredDialStringEntry 2 }

-- The modem Error Correcting Group

mdmECTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmECEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The modem error correcting table augments the modem ID
        table."
  ::= { mdmMIBObjects 9 }

mdmECEntry OBJECT-TYPE
  SYNTAX      MdmECEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "Entries in this table are created only by the agent. One
        entry exists for each modem managed by the agent."
  AUGMENTS
   { mdmIDEntry }
  ::= { mdmECTable 1 }

MdmECEntry ::= SEQUENCE {
  mdmECErrorControlUsed          OBJECT IDENTIFIER
}

mdmECErrorControlUsed OBJECT-TYPE
  SYNTAX      OBJECT IDENTIFIER
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "Indicates the error control method used during the current
        or previous call.  This shall be one of the values for error
        control protocols registered in the capabilities table for
        this modem.  If no error control protocol is in use, this
```

```
        object shall have the value '{0 0}'."
  REFERENCE   "V.58 errorControlActive"
  ::= { mdmECEntry 1 }

-- The modem Data Compression Group

mdmDCTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmDCEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The modem data compression table augments the modem ID
        table."
  ::= { mdmMIBObjects 10 }

mdmDCEntry OBJECT-TYPE
  SYNTAX      MdmDCEntry
   MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "Entries in this table are created only by the agent. One
        entry exists for each modem managed by the agent."
  AUGMENTS    { mdmIDEntry }
  ::= { mdmDCTable 1 }

MdmDCEntry ::= SEQUENCE {
  mdmDCCompressionTypeUsed        OBJECT IDENTIFIER
}

mdmDCCompressionTypeUsed OBJECT-TYPE
  SYNTAX      OBJECT IDENTIFIER
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "Indicates the data compression method used during the
        current or previous call.  This shall be one of the values
        for compression protocols registered in the capabilities
        table for this modem.  If no compression protocol is in use,
        this object shall have the value '{0 0}'."
  ::= { mdmDCEntry 1 }

-- The modem Signal Convertor Group

mdmSCTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmSCEntry
  MAX-ACCESS  not-accessible
  STATUS      current
```

```
   DESCRIPTION
        "The modem signal convertor table augments the modem ID
        table."
  ::= { mdmMIBObjects 11 }

mdmSCEntry OBJECT-TYPE
  SYNTAX      MdmSCEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "Entries in this table are created only by the agent. One
        entry exists for each modem managed by the agent."
  AUGMENTS    { mdmIDEntry }
  ::= { mdmSCTable 1 }

MdmSCEntry ::= SEQUENCE {
  mdmSCCurrentLineTransmitRate        Integer32,
  mdmSCCurrentLineReceiveRate         Integer32,
  mdmSCInitialLineTransmitRate        Integer32,
  mdmSCInitialLineReceiveRate         Integer32,
  mdmSCModulationSchemeUsed           OBJECT IDENTIFIER
}

mdmSCCurrentLineTransmitRate OBJECT-TYPE
  SYNTAX      Integer32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The current link transmit rate of a connection, or the last
        link transmit rate of the last connection
 in bits per
        second."
  REFERENCE   "V.58 transmissionSignallingRateActive"
  ::= { mdmSCEntry 1 }

mdmSCCurrentLineReceiveRate OBJECT-TYPE
  SYNTAX      Integer32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The current link receive rate of a connection, or the last
        link receive rate of the last connection in bits per
        second."
  REFERENCE   "V.58 transmissionSignallingRateActive"
  ::= { mdmSCEntry 2 }

mdmSCInitialLineTransmitRate OBJECT-TYPE
  SYNTAX      Integer32
```

```
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The initial link transmit rate of the current connection,
        or the initial link transmit rate of the last connection in
        bits per second."
  ::= { mdmSCEntry 3 }

mdmSCInitialLineReceiveRate OBJECT-TYPE
  SYNTAX      Integer32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The initial link receive rate of the
 current connection, or
        the initial link receive rate of the last connection in bits
        per second."
  ::= { mdmSCEntry 4 }

mdmSCModulationSchemeUsed OBJECT-TYPE
  SYNTAX      OBJECT IDENTIFIER
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The modulation scheme of the current or previous call.
        This shall be one of the values for modulation protocols
        registered in the capabilities table for this modem."
  REFERENCE   "V.58 gstnModulationSchemeActive"
  ::= { mdmSCEntry 5 }

-- The Modem Statistics Table

mdmStatsTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF MdmStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "The modem statistics Table augments the modem ID table."
  ::= { mdmMIBObjects 12 }

mdmStatsEntry OBJECT-TYPE
  SYNTAX      MdmStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
        "Entries in this table are
 created only by the agent. One
        entry exists for each modem managed by the agent."
```

```
  AUGMENTS    { mdmIDEntry }
  ::= { mdmStatsTable 1 }

MdmStatsEntry ::= SEQUENCE {
  mdmStatsRingNoAnswers                 Counter32,
  mdmStatsIncomingConnectionFailures    Counter32,
  mdmStatsIncomingConnectionCompletions Counter32,
  mdmStatsFailedDialAttempts            Counter32,
  mdmStatsOutgoingConnectionFailures    Counter32,
  mdmStatsOutgoingConnectionCompletions Counter32,
  mdmStatsRetrains                      Counter32,
  mdmStats2400OrLessConnections         Counter32,
  mdmStats2400To14400Connections        Counter32,
  mdmStatsGreaterThan14400Connections   Counter32,
  mdmStatsErrorControlledConnections    Counter32,
  mdmStatsCompressedConnections         Counter32,
  mdmStatsCompressionEfficiency         Integer32,
  mdmStatsSentOctets                    Counter32,
  mdmStatsReceivedOctets
 Counter32,
  mdmStatsSentDataFrames                Counter32,
  mdmStatsReceivedDataFrames            Counter32,
  mdmStatsResentFrames                  Counter32,
  mdmStatsErrorFrames                   Counter32
}

mdmStatsRingNoAnswers OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of events in which ringing was detected but the
        call was not answered."
  ::= { mdmStatsEntry 1 }

mdmStatsIncomingConnectionFailures OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of incoming connection requests that this modem
        answered in which it could not train with the other DCE."
  ::= { mdmStatsEntry 2 }

mdmStatsIncomingConnectionCompletions OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
```

```
  DESCRIPTION
        "The number of incoming connection requests
 that this modem
        answered and successfully trained with the other DCE."
  ::= { mdmStatsEntry 3 }

mdmStatsFailedDialAttempts OBJECT-TYPE
      SYNTAX         Counter32
      MAX-ACCESS  read-only
      STATUS         current
      DESCRIPTION
            "The number of call attempts that failed because the modem
      didn't go off hook, or there was no dialtone."
      ::= { mdmStatsEntry 4 }

mdmStatsOutgoingConnectionFailures OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of outgoing calls from this modem which
        sucessfully went off hook and dialed, in which it could not
        train with the other DCE."
  ::= { mdmStatsEntry 5 }

mdmStatsOutgoingConnectionCompletions OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of outgoing calls from this modem which resulted

    in successfully training with the other DCE."
  ::= { mdmStatsEntry 6 }

mdmStatsRetrains OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of retrains experienced on connections on this
        line."
  ::= { mdmStatsEntry 7 }


-- Utilization counters

mdmStats2400OrLessConnections OBJECT-TYPE
```

```
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of connections initially established at a
        modulation speed of 2400 bits per second or less."
  ::= { mdmStatsEntry 8 }


mdmStats2400To14400Connections OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of connections initially established at a
        modulation speed of greater than 2400 bits per second and
        less than 14400 bits per second."
  ::= { mdmStatsEntry 9 }

mdmStatsGreaterThan14400Connections
 OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of connections initially established at a
        modulation speed of greater than 14400 bits per second."
  ::= { mdmStatsEntry 10 }

mdmStatsErrorControlledConnections OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of established connections using an error
        control protocol."
  ::= { mdmStatsEntry 11 }

mdmStatsCompressedConnections OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of established connections using a compression
        protocol."
  ::= { mdmStatsEntry 12 }

mdmStatsCompressionEfficiency OBJECT-TYPE
```

```
  SYNTAX      Integer32 (0..65535)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of bytes transferred
 into the compression
        encoder divided by the number of bytes transferred out of
        the encoder, multiplied by 100 for either the current or
        last call.  If a data compression protocol is not in use,
        this value shall be `100'."
  REFERENCE   "V.58 compressionEfficiency"
  ::= { mdmStatsEntry 13 }

mdmStatsSentOctets OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of octets presented to the modem by the DTE."
  ::= { mdmStatsEntry 14 }

mdmStatsReceivedOctets OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of octets presented to the DTE by the modem."
  ::= { mdmStatsEntry 15 }

mdmStatsSentDataFrames OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of data frames sent on the line interface.  If

       there is no frame-oriented protocol in use on the line
        interface, this counter shall not increment."
  ::= { mdmStatsEntry 16 }

mdmStatsReceivedDataFrames OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of data frames received on the line interface.
        If there is no frame-oriented protocol in use on the line
        interface, this counter shall not increment."
```

```
  ::= { mdmStatsEntry 17 }

mdmStatsResentFrames OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The number of times this modem retransmits frames on the
        line interface.  If there is no frame-oriented protocol in
        use on the line interface, this counter shall not
        increment."
  ::= { mdmStatsEntry 18 }

mdmStatsErrorFrames OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      current
   DESCRIPTION
        "The number of block errors received on the link.  If there
        is no frame-oriented protocol in use on the line interface,
        this counter shall not increment."
  ::= { mdmStatsEntry 19 }


-- compliance statements

mdmCompliance MODULE-COMPLIANCE
  STATUS  current
  DESCRIPTION
        "The compliance statement for SNMPv2 entities which
        implement the modem MIB."

  MODULE  -- this module
    MANDATORY-GROUPS { mdmIDGroup, mdmLineInterfaceGroup,
          mdmDTEInterfaceGroup, mdmCallControlGroup,
          mdmSignalConvertorGroup, mdmStatisticsGroup }

    GROUP   mdmErrorControlGroup
    DESCRIPTION
      "This group is mandatory only for those modems that
      implement an error correction protocol."

    GROUP mdmDataCompressionGroup
    DESCRIPTION
      "This group is mandatory only for those modems that
      implement a data compression protocol."
```

```
 ::= { mdmCompliances 1 }


END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/Modem-MIB
No license file was found, but licenses were detected in source scan.

```
IANA-ITU-ALARM-TC-MIB DEFINITIONS ::= BEGIN

 IMPORTS
   MODULE-IDENTITY, mib-2       FROM SNMPv2-SMI
   TEXTUAL-CONVENTION           FROM SNMPv2-TC;

 ianaItuAlarmNumbers MODULE-IDENTITY
    LAST-UPDATED "200409090000Z"  -- September 09, 2004
    ORGANIZATION "IANA"
    CONTACT-INFO
       "Postal:    Internet Assigned Numbers Authority
                   Internet Corporation for Assigned Names
                   and Numbers
                   4676 Admiralty Way, Suite 330
                   Marina del Rey, CA 90292-6601
                   USA

        Tel:    +1  310-823-9358
        E-Mail: iana&iana.org"
    DESCRIPTION
       "The MIB module defines the ITU Alarm
       textual convention for objects expected to require
       regular extension.

       Copyright (C) The Internet Society (2004).  The
       initial version
of this MIB module was published
       in RFC 3877. For full legal notices see the RFC
       itself. Supplementary information may be available on:
           http://www.ietf.org/copyrights/ianamib.html"
     REVISION    "200409090000Z"
     DESCRIPTION
        "Initial version, published as RFC 3877."
    ::= { mib-2 119 }


 IANAItuProbableCause ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
```

"ITU-T probable cause values. Duplicate values defined in
X.733 are appended with X733 to ensure syntactic uniqueness.
Probable cause value 0 is reserved for special purposes.

The Internet Assigned Number Authority (IANA) is responsible
for the assignment of the enumerations in this TC.
IANAItuProbableCause value of 0 is reserved for special
purposes and MUST NOT be assigned.

Values of IANAItuProbableCause in the range 1 to 1023 are
reserved
for causes that correspond to ITU-T probable cause.

All other requests for new causes will be handled on a
first-come, first served basis and will be assigned
enumeration values starting with 1025.

Request should come in the form of well-formed
SMI [RFC2578] for enumeration names that are unique and
sufficiently descriptive.

While some effort will be taken to ensure that new probable
causes do not conceptually duplicate existing probable
causes it is acknowledged that the existence of conceptual
duplicates in the starting probable cause list is an known
industry reality.

To aid IANA in the administration of probable cause names
and values, the OPS Area Director will appoint one or more
experts to help review requests.

See http://www.iana.org"
REFERENCE
"ITU Recommendation M.3100,
'Generic Network Information
Model', 1995
ITU Recommendation X.733, 'Information Technology - Open
Systems Interconnection - System Management: Alarm
Reporting Function', 1992
ITU Recommendation X.736, 'Information Technology - Open
Systems Interconnection - System Management: Security
Alarm Reporting Function', 1992"

SYNTAX INTEGER
{
-- The following probable causes were defined in M.3100
aIS (1),
callSetUpFailure (2),

degradedSignal (3),
farEndReceiverFailure (4),
framingError (5),
lossOfFrame (6),
lossOfPointer (7),
lossOfSignal (8),
payloadTypeMismatch (9),
transmissionError (10),
remoteAlarmInterface (11),
excessiveBER (12),

pathTraceMismatch (13),
unavailable (14),
signalLabelMismatch (15),
lossOfMultiFrame (16),
receiveFailure (17),
transmitFailure (18),
modulationFailure (19),
demodulationFailure (20),
broadcastChannelFailure (21),
connectionEstablishmentError (22),
invalidMessageReceived (23),
localNodeTransmissionError (24),
remoteNodeTransmissionError (25),
routingFailure (26),
--Values 27-50 are reserved for communications alarm related
--probable causes
-- The following are used with equipment alarm.
backplaneFailure (51),
dataSetProblem (52),
equipmentIdentifierDuplication (53),
externalIFDeviceProblem (54),
lineCardProblem (55),
multiplexerProblem (56),
nEIdentifierDuplication
(57),
powerProblem (58),
processorProblem (59),
protectionPathFailure (60),
receiverFailure (61),
replaceableUnitMissing (62),
replaceableUnitTypeMismatch (63),
synchronizationSourceMismatch (64),
terminalProblem (65),
timingProblem (66),
transmitterFailure (67),
trunkCardProblem (68),
replaceableUnitProblem (69),

realTimeClockFailure (70),
--An equipment alarm to be issued if the system detects that the
--real time clock has failed
antennaFailure (71),
batteryChargingFailure (72),
diskFailure (73),
frequencyHoppingFailure (74),
iODeviceError (75),
lossOfSynchronisation (76),
lossOfRedundancy (77),
powerSupplyFailure (78),
signalQualityEvaluationFailure (79),
tranceiverFailure (80),
protectionMechanismFailure (81),
protectingResourceFailure (82),
-- Values 83-100 are reserved for equipment alarm related probable
-- causes
-- The following are used with environmental alarm.
airCompressorFailure (101),
airConditioningFailure (102),
airDryerFailure (103),
batteryDischarging (104),
batteryFailure (105),
commercialPowerFailure (106),
coolingFanFailure (107),
engineFailure (108),
fireDetectorFailure (109),
fuseFailure (110),
generatorFailure (111),
lowBatteryThreshold (112),
pumpFailure (113),
rectifierFailure (114),
rectifierHighVoltage (115),
rectifierLowFVoltage
(116),
ventilationsSystemFailure (117),
enclosureDoorOpen (118),
explosiveGas (119),
fire (120),
flood (121),
highHumidity (122),
highTemperature (123),
highWind (124),
iceBuildUp (125),
intrusionDetection (126),
lowFuel (127),
lowHumidity (128),
lowCablePressure (129),

```
            lowTemperatue  (130),
            lowWater  (131),
            smoke  (132),
            toxicGas  (133),
            coolingSystemFailure (134),
            externalEquipmentFailure (135),
            externalPointFailure (136),
  -- Values 137-150 are reserved for environmental alarm related
  -- probable causes
  -- The following are used with Processing error alarm.
            storageCapacityProblem (151),
            memoryMismatch  (152),

           corruptData  (153),
            outOfCPUCycles   (154),
            sfwrEnvironmentProblem  (155),
            sfwrDownloadFailure  (156),
            lossOfRealTimel (157),
  --A processing error alarm to be issued after the system has
  --reinitialised. This will indicate
  --to the management systems that the view they have of the managed
  --system may no longer
  --be valid. Usage example: The managed
  --system issues this alarm after a reinitialization with severity
  --warning to inform the
  --management system about the event. No clearing notification will
  --be sent.
            applicationSubsystemFailure (158),
            configurationOrCustomisationError (159),
            databaseInconsistency (160),
            fileError (161),
            outOfMemory (162),
            softwareError (163),
            timeoutExpired (164),
            underlayingResourceUnavailable (165),
            versionMismatch
(166),
  --Values 168-200 are reserved for processing error alarm related
  -- probable causes.
            bandwidthReduced (201),
            congestion (202),
            excessiveErrorRate (203),
            excessiveResponseTime (204),
            excessiveRetransmissionRate (205),
            reducedLoggingCapability (206),
            systemResourcesOverload (207 ),
            -- The following were defined X.733
            adapterError (500),
```

applicationSubsystemFailture (501),
bandwidthReducedX733 (502),
callEstablishmentError (503),
communicationsProtocolError (504),
communicationsSubsystemFailure (505),
configurationOrCustomizationError (506),
congestionX733 (507),
coruptData (508),
cpuCyclesLimitExceeded (509),
dataSetOrModemError (510),
degradedSignalX733
(511),
dteDceInterfaceError (512),
enclosureDoorOpenX733 (513),
equipmentMalfunction (514),
excessiveVibration (515),
fileErrorX733 (516),
fireDetected (517),
framingErrorX733 (518),
heatingVentCoolingSystemProblem (519),
humidityUnacceptable (520),
inputOutputDeviceError (521),
inputDeviceError (522),
lanError (523),
leakDetected (524),
localNodeTransmissionErrorX733 (525),
lossOfFrameX733 (526),
lossOfSignalX733 (527),
materialSupplyExhausted (528),
multiplexerProblemX733 (529),
outOfMemoryX733 (530),
ouputDeviceError (531),
performanceDegraded (532),
powerProblems (533),
pressureUnacceptable (534),

processorProblems (535),
pumpFailureX733 (536),
queueSizeExceeded (537),
receiveFailureX733 (538),
receiverFailureX733 (539),
remoteNodeTransmissionErrorX733 (540),
resourceAtOrNearingCapacity (541),
responseTimeExecessive (542),
retransmissionRateExcessive (543),
softwareErrorX733 (544),
softwareProgramAbnormallyTerminated (545),
softwareProgramError (546),

storageCapacityProblemX733 (547),
temperatureUnacceptable (548),
thresholdCrossed (549),
timingProblemX733 (550),
toxicLeakDetected (551),
transmitFailureX733 (552),
transmiterFailure (553),
underlyingResourceUnavailable (554),
versionMismatchX733 (555),
-- The following are defined in X.736

authenticationFailure (600),
breachOfConfidentiality (601),
cableTamper (602),
delayedInformation (603),
denialOfService (604),
duplicateInformation (605),
informationMissing (606),
informationModificationDetected (607),
informationOutOfSequence (608),
keyExpired (609),
nonRepudiationFailure (610),
outOfHoursActivity (611),
outOfService (612),
proceduralError (613),
unauthorizedAccessAttempt (614),
unexpectedInformation (615),

other (1024)
}

IANAItuEventType ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
"The ITU event Type values.

The Internet Assigned Number Authority (IANA) is
responsible for the assignment of the enumerations

in this TC.

Request should come in the form of well-formed
SMI [RFC2578] for enumeration names that are unique
and sufficiently descriptive.

See http://www.iana.org "
REFERENCE
"ITU Recommendation X.736, 'Information Technology - Open

```
          Systems Interconnection - System Management: Security
          Alarm Reporting Function', 1992"
    SYNTAX        INTEGER
          {
          other (1),
          communicationsAlarm (2),
          qualityOfServiceAlarm (3),
          processingErrorAlarm (4),
          equipmentAlarm (5),
          environmentalAlarm (6),
          integrityViolation (7),
          operationalViolation (8),
          physicalViolation (9),
          securityServiceOrMechanismViolation (10),
          timeDomainViolation (11)
          }

 END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/iana/IANA-ITU-ALARM-TC-MIB
No license file was found, but licenses were detected in source scan.

```
SNMPv2-MIB DEFINITIONS ::= BEGIN

IMPORTS
  MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,
  TimeTicks, Counter32, snmpModules, mib-2
     FROM SNMPv2-SMI
  DisplayString, TestAndIncr, TimeStamp




     FROM SNMPv2-TC
  MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
     FROM SNMPv2-CONF;

snmpMIB MODULE-IDENTITY
  LAST-UPDATED "200210160000Z"
  ORGANIZATION "IETF SNMPv3 Working Group"
  CONTACT-INFO
        "WG-EMail:   snmpv3@lists.tislabs.com
         Subscribe:  snmpv3-request@lists.tislabs.com

         Co-Chair:   Russ Mundy
                     Network Associates Laboratories
         postal:     15204 Omega Drive, Suite 300
                     Rockville, MD 20850-4601
```

USA
EMail: mundy@tislabs.com
phone: +1 301 947-7107

Co-Chair: David Harrington
Enterasys
Networks
postal: 35 Industrial Way
P. O. Box 5005
Rochester, NH 03866-5005
USA
EMail: dbh@enterasys.com
phone: +1 603 337-2614

Editor: Randy Presuhn
BMC Software, Inc.
postal: 2141 North First Street
San Jose, CA 95131
USA
EMail: randy_presuhn@bmc.com
phone: +1 408 546-1006"
DESCRIPTION
"The MIB module for SNMP entities.

Copyright (C) The Internet Society (2002). This
version of this MIB module is part of RFC 3418;
see the RFC itself for full legal notices.
"
REVISION "200210160000Z"
DESCRIPTION
"This revision of this MIB module was published as
RFC 3418."
REVISION "199511090000Z"
DESCRIPTION

"This revision of this MIB module was published as
RFC 1907."
REVISION "199304010000Z"
DESCRIPTION
"The initial revision of this MIB module was published
as RFC 1450."
::= { snmpModules 1 }

snmpMIBObjects OBJECT IDENTIFIER ::= { snmpMIB 1 }

```
--  ::= { snmpMIBObjects 1 }       this OID is obsolete
--  ::= { snmpMIBObjects 2 }       this OID is obsolete
--  ::= { snmpMIBObjects 3 }       this OID is obsolete

-- the System group
--
-- a collection of objects common to all managed systems.

system   OBJECT IDENTIFIER ::= { mib-2 1 }

sysDescr OBJECT-TYPE
  SYNTAX      DisplayString (SIZE (0..255))
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "A textual description of the entity.  This value should
        include the full name and version identification of
        the system's hardware type, software operating-system,
        and networking software."
  ::= { system 1 }

sysObjectID
 OBJECT-TYPE
  SYNTAX      OBJECT IDENTIFIER
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The vendor's authoritative identification of the
        network management subsystem contained in the entity.
        This value is allocated within the SMI enterprises
        subtree (1.3.6.1.4.1) and provides an easy and
        unambiguous means for determining `what kind of box' is
        being managed.  For example, if vendor `Flintstones,
        Inc.' was assigned the subtree 1.3.6.1.4.1.424242,
        it could assign the identifier 1.3.6.1.4.1.424242.1.1
        to its `Fred Router'."
  ::= { system 2 }

sysUpTime OBJECT-TYPE



  SYNTAX      TimeTicks
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
        "The time (in hundredths of a second) since the
        network management portion of the system was last
```

```
        re-initialized."
    ::= { system 3 }

sysContact OBJECT-TYPE
     SYNTAX      DisplayString (SIZE (0..255))
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The textual identification of the contact person for
        this managed node, together with information on how
        to contact this person.  If no contact information is
        known, the value is the zero-length string."
    ::= { system 4 }

sysName OBJECT-TYPE
    SYNTAX      DisplayString (SIZE (0..255))
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "An administratively-assigned name for this managed
        node.  By convention, this is the node's fully-qualified
        domain name.  If the name is unknown, the value is
        the zero-length string."
    ::= { system 5 }

sysLocation OBJECT-TYPE
    SYNTAX      DisplayString (SIZE (0..255))
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The physical location of this node (e.g., 'telephone
        closet,
 3rd floor').  If the location is unknown, the
        value is the zero-length string."
    ::= { system 6 }

sysServices OBJECT-TYPE
    SYNTAX      INTEGER (0..127)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A value which indicates the set of services that this
        entity may potentially offer.  The value is a sum.



        This sum initially takes the value zero. Then, for
        each layer, L, in the range 1 through 7, that this node
```

performs transactions for, 2 raised to (L - 1) is added
to the sum. For example, a node which performs only
routing functions would have a value of 4 (2^(3-1)).
In contrast, a node which is a host offering application
services would have a value of 72 (2^(4-1) + 2^(7-1)).
Note that in the context of the Internet suite of
protocols, values should be calculated accordingly:

layer	functionality
1	physical (e.g., repeaters)
2	datalink/subnetwork (e.g., bridges)
3	internet (e.g., supports the IP)
4	end-to-end (e.g., supports the TCP)
7	applications (e.g., supports the SMTP)

For systems including OSI protocols, layers 5 and 6
may also be counted."
::= { system 7 }

-- object resource information
--
-- a collection of objects which describe the SNMP entity's
-- (statically and dynamically configurable) support of
-- various MIB modules.

sysORLastChange OBJECT-TYPE
SYNTAX TimeStamp
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The value of sysUpTime at the time of the most recent
change in state or value of any instance of sysORID."
::= { system 8 }

sysORTable OBJECT-TYPE
SYNTAX SEQUENCE OF SysOREntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The (conceptual) table listing the capabilities of
the local SNMP application acting as a command
responder with respect to various MIB modules.
SNMP entities having dynamically-configurable support
of MIB modules will have a dynamically-varying number
of conceptual rows."
::= { system 9 }

```
sysOREntry OBJECT-TYPE
  SYNTAX     SysOREntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
        "An entry (conceptual row) in the sysORTable."
  INDEX      { sysORIndex }
  ::= { sysORTable 1 }

SysOREntry ::= SEQUENCE {
  sysORIndex     INTEGER,
  sysORID        OBJECT IDENTIFIER,
  sysORDescr     DisplayString,
  sysORUpTime    TimeStamp
}

sysORIndex OBJECT-TYPE
  SYNTAX     INTEGER (1..2147483647)
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
        "The auxiliary variable used for identifying instances
        of the columnar
 objects in the sysORTable."
  ::= { sysOREntry 1 }

sysORID OBJECT-TYPE
  SYNTAX     OBJECT IDENTIFIER
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
        "An authoritative identification of a capabilities
        statement with respect to various MIB modules supported
        by the local SNMP application acting as a command
        responder."
  ::= { sysOREntry 2 }

sysORDescr OBJECT-TYPE
  SYNTAX     DisplayString
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
        "A textual description of the capabilities identified
        by the corresponding instance of sysORID."
  ::= { sysOREntry 3 }

sysORUpTime OBJECT-TYPE
```

```
  SYNTAX     TimeStamp
  MAX-ACCESS read-only



  STATUS     current
  DESCRIPTION
          "The value of sysUpTime at the time this conceptual
          row was last instantiated."
  ::= { sysOREntry 4 }


-- the SNMP group
--
-- a collection of objects providing basic instrumentation
 and
-- control of an SNMP entity.

snmp     OBJECT IDENTIFIER ::= { mib-2 11 }

snmpInPkts OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
          "The total number of messages delivered to the SNMP
          entity from the transport service."
  ::= { snmp 1 }

snmpInBadVersions OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
          "The total number of SNMP messages which were delivered
          to the SNMP entity and were for an unsupported SNMP
          version."
  ::= { snmp 3 }

snmpInBadCommunityNames OBJECT-TYPE
  SYNTAX     Counter32
  MAX-ACCESS read-only
  STATUS     current
  DESCRIPTION
         "The total number of community-based SNMP messages (for
         example,  SNMPv1) delivered to the SNMP entity which
         used an SNMP community name not known to said entity.
         Also, implementations which authenticate community-based
```

SNMP messages using check(s) in addition to matching
the community name (for example, by also checking
whether the message originated from a transport address
allowed to use a specified community name) MAY include
in this value the number of messages which failed the
additional check(s). It is strongly RECOMMENDED that

the documentation for any security model which is used
to authenticate community-based SNMP messages specify
the precise conditions that contribute to this value."
::= { snmp 4 }

snmpInBadCommunityUses OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The total number of community-based SNMP messages (for
example, SNMPv1) delivered to the SNMP entity which
represented an SNMP operation that was not allowed for
the SNMP community named in the message. The precise
conditions under which this counter is incremented
(if at all) depend on how the SNMP entity implements
its access control mechanism and how its applications
interact with that access control mechanism. It is
strongly RECOMMENDED that the documentation for any
access control mechanism which is used to control access
to and visibility of MIB instrumentation specify the
precise conditions that contribute to this value."
::= { snmp 5 }

snmpInASNParseErrs OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The total number of ASN.1 or BER errors encountered by
the SNMP entity when decoding received SNMP messages."
::= { snmp 6 }

snmpEnableAuthenTraps OBJECT-TYPE
SYNTAX INTEGER { enabled(1), disabled(2) }
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"Indicates whether the

SNMP entity is permitted to
generate authenticationFailure traps. The value of this object overrides any configuration information; as such, it provides a means whereby all authenticationFailure traps may be disabled.

Note that it is strongly recommended that this object be stored in non-volatile memory so that it remains constant across re-initializations of the network management system."

::= { snmp 30 }

snmpSilentDrops OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The total number of Confirmed Class PDUs (such as GetRequest-PDUs, GetNextRequest-PDUs, GetBulkRequest-PDUs, SetRequest-PDUs, and InformRequest-PDUs) delivered to the SNMP entity which were silently dropped because the size of a reply containing an alternate Response Class PDU (such as a

Response-PDU) with an empty variable-bindings field was greater than either a local constraint or the maximum message size associated with the originator of the request."
::= { snmp 31 }

snmpProxyDrops OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The total number of Confirmed Class PDUs (such as GetRequest-PDUs, GetNextRequest-PDUs, GetBulkRequest-PDUs, SetRequest-PDUs, and InformRequest-PDUs) delivered to the SNMP entity which were silently dropped because the transmission of the (possibly translated) message to a proxy target failed in a manner (other than a time-out) such that no Response Class PDU (such as a Response-PDU) could be returned."
::= { snmp 32 }

```
-- information for notifications
--
-- a collection of objects which allow the SNMP entity, when
-- supporting a notification
 originator application,
-- to be configured to generate SNMPv2-Trap-PDUs.

snmpTrap      OBJECT IDENTIFIER ::= { snmpMIBObjects 4 }

snmpTrapOID OBJECT-TYPE
  SYNTAX     OBJECT IDENTIFIER
  MAX-ACCESS accessible-for-notify
  STATUS     current
  DESCRIPTION



        "The authoritative identification of the notification
        currently being sent.  This variable occurs as
        the second varbind in every SNMPv2-Trap-PDU and
        InformRequest-PDU."
  ::= { snmpTrap 1 }

--  ::= { snmpTrap 2 }   this OID is obsolete

snmpTrapEnterprise OBJECT-TYPE
  SYNTAX     OBJECT IDENTIFIER
  MAX-ACCESS accessible-for-notify
  STATUS     current
  DESCRIPTION
        "The authoritative identification of the enterprise
        associated with the trap currently being sent.  When an
        SNMP proxy agent is mapping an RFC1157 Trap-PDU
        into a SNMPv2-Trap-PDU, this variable occurs as the
        last varbind."
  ::= { snmpTrap
 3 }

--  ::= { snmpTrap 4 }   this OID is obsolete


-- well-known traps

snmpTraps      OBJECT IDENTIFIER ::= { snmpMIBObjects 5 }

coldStart NOTIFICATION-TYPE
  STATUS  current
```

```
  DESCRIPTION
        "A coldStart trap signifies that the SNMP entity,
        supporting a notification originator application, is
        reinitializing itself and that its configuration may
        have been altered."
  ::= { snmpTraps 1 }

warmStart NOTIFICATION-TYPE
  STATUS  current
  DESCRIPTION
        "A warmStart trap signifies that the SNMP entity,
        supporting a notification originator application,
        is reinitializing itself such that its configuration
        is unaltered."
  ::= { snmpTraps 2 }

-- Note the linkDown NOTIFICATION-TYPE ::= { snmpTraps 3 }
-- and the linkUp NOTIFICATION-TYPE ::= { snmpTraps 4 }
-- are defined in RFC 2863 [RFC2863]



authenticationFailure NOTIFICATION-TYPE
  STATUS  current
  DESCRIPTION
        "An
 authenticationFailure trap signifies that the SNMP
        entity has received a protocol message that is not
        properly authenticated.  While all implementations
        of SNMP entities MAY be capable of generating this
        trap, the snmpEnableAuthenTraps object indicates
        whether this trap will be generated."
  ::= { snmpTraps 5 }

-- Note the egpNeighborLoss notification is defined
-- as { snmpTraps 6 } in RFC 1213

-- the set group
--
-- a collection of objects which allow several cooperating
-- command generator applications to coordinate their use of the
-- set operation.

snmpSet       OBJECT IDENTIFIER ::= { snmpMIBObjects 6 }

snmpSetSerialNo OBJECT-TYPE
  SYNTAX     TestAndIncr
  MAX-ACCESS read-write
```

```
  STATUS     current
  DESCRIPTION
          "An advisory lock used to allow several cooperating
          command generator applications to coordinate their
          use of the SNMP set operation.

          This
 object is used for coarse-grain coordination.
          To achieve fine-grain coordination, one or more similar
          objects might be defined within each MIB group, as
          appropriate."
  ::= { snmpSet 1 }

-- conformance information

snmpMIBConformance
           OBJECT IDENTIFIER ::= { snmpMIB 2 }

snmpMIBCompliances
           OBJECT IDENTIFIER ::= { snmpMIBConformance 1 }
snmpMIBGroups  OBJECT IDENTIFIER ::= { snmpMIBConformance 2 }

-- compliance statements




--    ::= { snmpMIBCompliances 1 }      this OID is obsolete
snmpBasicCompliance MODULE-COMPLIANCE
  STATUS  deprecated
  DESCRIPTION
          "The compliance statement for SNMPv2 entities which
          implement the SNMPv2 MIB.

          This compliance statement is replaced by
          snmpBasicComplianceRev2."
  MODULE  -- this module
     MANDATORY-GROUPS { snmpGroup, snmpSetGroup, systemGroup,
                        snmpBasicNotificationsGroup }

     GROUP   snmpCommunityGroup
      DESCRIPTION
          "This group is mandatory for SNMPv2 entities which
          support community-based authentication."

  ::= { snmpMIBCompliances 2 }

snmpBasicComplianceRev2 MODULE-COMPLIANCE
```

```
  STATUS  current
  DESCRIPTION
          "The compliance statement for SNMP entities which
          implement this MIB module."
  MODULE  -- this module
    MANDATORY-GROUPS { snmpGroup, snmpSetGroup, systemGroup,
                       snmpBasicNotificationsGroup }

    GROUP   snmpCommunityGroup
    DESCRIPTION
      "This group is mandatory for SNMP entities which
      support community-based authentication."

    GROUP   snmpWarmStartNotificationGroup
    DESCRIPTION
      "This group is mandatory for an SNMP entity which
      supports command responder applications, and is
      able to reinitialize itself such that its
      configuration is unaltered."

  ::= { snmpMIBCompliances
 3 }

-- units of conformance

--  ::= { snmpMIBGroups 1 }          this OID is obsolete
--  ::= { snmpMIBGroups 2 }          this OID is obsolete
--  ::= { snmpMIBGroups 3 }          this OID is obsolete



--  ::= { snmpMIBGroups 4 }          this OID is obsolete

snmpGroup OBJECT-GROUP
  OBJECTS { snmpInPkts,
            snmpInBadVersions,
            snmpInASNParseErrs,
            snmpSilentDrops,
            snmpProxyDrops,
            snmpEnableAuthenTraps }
  STATUS  current
  DESCRIPTION
          "A collection of objects providing basic instrumentation
          and control of an SNMP entity."
  ::= { snmpMIBGroups 8 }

snmpCommunityGroup OBJECT-GROUP
  OBJECTS { snmpInBadCommunityNames,
```

```
            snmpInBadCommunityUses }
    STATUS  current
    DESCRIPTION
            "A collection of objects providing basic instrumentation
            of a SNMP entity which supports community-based
            authentication."
    ::= { snmpMIBGroups 9 }

snmpSetGroup
 OBJECT-GROUP
    OBJECTS { snmpSetSerialNo }
    STATUS  current
    DESCRIPTION
            "A collection of objects which allow several cooperating
            command generator applications to coordinate their
            use of the set operation."
    ::= { snmpMIBGroups 5 }

systemGroup OBJECT-GROUP
    OBJECTS { sysDescr, sysObjectID, sysUpTime,
              sysContact, sysName, sysLocation,
              sysServices,
              sysORLastChange, sysORID,
              sysORUpTime, sysORDescr }
    STATUS  current
    DESCRIPTION
            "The system group defines objects which are common to all
            managed systems."
    ::= { snmpMIBGroups 6 }

snmpBasicNotificationsGroup NOTIFICATION-GROUP
    NOTIFICATIONS { coldStart, authenticationFailure }



    STATUS        current
    DESCRIPTION
      "The basic notifications implemented by an SNMP entity
       supporting command responder applications."
    ::= { snmpMIBGroups 7 }

snmpWarmStartNotificationGroup
 NOTIFICATION-GROUP
  NOTIFICATIONS { warmStart }
  STATUS        current
  DESCRIPTION
    "An additional notification for an SNMP entity supporting
    command responder applications, if it is able to reinitialize
```

```
    itself such that its configuration is unaltered."
 ::= { snmpMIBGroups 11 }

snmpNotificationGroup OBJECT-GROUP
  OBJECTS { snmpTrapOID, snmpTrapEnterprise }
  STATUS  current
  DESCRIPTION
        "These objects are required for entities
        which support notification originator applications."
  ::= { snmpMIBGroups 12 }

-- definitions in RFC 1213 made obsolete by the inclusion of a
-- subset of the snmp group in this MIB

snmpOutPkts OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP Messages which were
        passed from the SNMP protocol entity to the
        transport service."
  ::= { snmp 2 }

-- { snmp 7 } is not used

snmpInTooBigs
 OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP PDUs which were
        delivered to the SNMP protocol entity and for
        which the value of the error-status field was
        `tooBig'."
  ::= { snmp 8 }



snmpInNoSuchNames OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP PDUs which were
        delivered to the SNMP protocol entity and for
        which the value of the error-status field was
```

```
        `noSuchName'."
  ::= { snmp 9 }

snmpInBadValues OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP PDUs which were
        delivered to the SNMP protocol entity and for
        which the value of the error-status field was
        `badValue'."
  ::= { snmp 10 }

snmpInReadOnlys
 OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number valid SNMP PDUs which were delivered
        to the SNMP protocol entity and for which the value
        of the error-status field was `readOnly'.  It should
        be noted that it is a protocol error to generate an
        SNMP PDU which contains the value `readOnly' in the
        error-status field, as such this object is provided
        as a means of detecting incorrect implementations of
        the SNMP."
  ::= { snmp 11 }

snmpInGenErrs OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP PDUs which were delivered
        to the SNMP protocol entity and for which the value
        of the error-status field was `genErr'."
  ::= { snmp 12 }

snmpInTotalReqVars OBJECT-TYPE



  SYNTAX      Counter32
   MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
```

"The total number of MIB objects which have been
retrieved successfully by the SNMP protocol entity
as the result of receiving valid SNMP Get-Request
and Get-Next PDUs."
::= { snmp 13 }

snmpInTotalSetVars OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS obsolete
DESCRIPTION
"The total number of MIB objects which have been
altered successfully by the SNMP protocol entity as
the result of receiving valid SNMP Set-Request PDUs."
::= { snmp 14 }

snmpInGetRequests OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS obsolete
DESCRIPTION
"The total number of SNMP Get-Request PDUs which
have been accepted and processed by the SNMP
protocol entity."
::= { snmp 15 }

snmpInGetNexts OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS
read-only
STATUS obsolete
DESCRIPTION
"The total number of SNMP Get-Next PDUs which have been
accepted and processed by the SNMP protocol entity."
::= { snmp 16 }

snmpInSetRequests OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS obsolete
DESCRIPTION
"The total number of SNMP Set-Request PDUs which
have been accepted and processed by the SNMP protocol
entity."
::= { snmp 17 }

```
snmpInGetResponses OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP Get-Response PDUs which
        have been accepted and processed by the SNMP protocol
        entity."
  ::= { snmp 18 }

snmpInTraps OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP Trap PDUs which have been
        accepted and
 processed by the SNMP protocol entity."
  ::= { snmp 19 }

snmpOutTooBigs OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP PDUs which were generated
        by the SNMP protocol entity and for which the value
        of the error-status field was `tooBig.'"
  ::= { snmp 20 }

snmpOutNoSuchNames OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP PDUs which were generated
        by the SNMP protocol entity and for which the value
        of the error-status was `noSuchName'."
  ::= { snmp 21 }

snmpOutBadValues OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP PDUs which were generated
        by the SNMP protocol entity and for which the value
        of the error-status field was
```

```
 `badValue'."
  ::= { snmp 22 }



-- { snmp 23 } is not used

snmpOutGenErrs OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP PDUs which were generated
        by the SNMP protocol entity and for which the value
        of the error-status field was `genErr'."
  ::= { snmp 24 }

snmpOutGetRequests OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP Get-Request PDUs which
        have been generated by the SNMP protocol entity."
  ::= { snmp 25 }

snmpOutGetNexts OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP Get-Next PDUs which have
        been generated by the SNMP protocol entity."
  ::= { snmp 26 }

snmpOutSetRequests OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
   STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP Set-Request PDUs which
        have been generated by the SNMP protocol entity."
  ::= { snmp 27 }

snmpOutGetResponses OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
```

```
  DESCRIPTION
        "The total number of SNMP Get-Response PDUs which
        have been generated by the SNMP protocol entity."
  ::= { snmp 28 }



snmpOutTraps OBJECT-TYPE
  SYNTAX      Counter32
  MAX-ACCESS  read-only
  STATUS      obsolete
  DESCRIPTION
        "The total number of SNMP Trap PDUs which have
        been generated by the SNMP protocol entity."
  ::= { snmp 29 }

snmpObsoleteGroup OBJECT-GROUP
  OBJECTS { snmpOutPkts, snmpInTooBigs, snmpInNoSuchNames,
            snmpInBadValues, snmpInReadOnlys, snmpInGenErrs,
            snmpInTotalReqVars, snmpInTotalSetVars,
            snmpInGetRequests, snmpInGetNexts, snmpInSetRequests,

    snmpInGetResponses, snmpInTraps, snmpOutTooBigs,
            snmpOutNoSuchNames, snmpOutBadValues,
            snmpOutGenErrs, snmpOutGetRequests, snmpOutGetNexts,
            snmpOutSetRequests, snmpOutGetResponses, snmpOutTraps
            }
  STATUS  obsolete
  DESCRIPTION
        "A collection of objects from RFC 1213 made obsolete
        by this MIB module."
  ::= { snmpMIBGroups 10 }

END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/SNMPv2-MIB
No license file was found, but licenses were detected in source scan.

SNMP-USM-DH-OBJECTS-MIB DEFINITIONS ::= BEGIN

IMPORTS
  MODULE-IDENTITY, OBJECT-TYPE,
  -- OBJECT-IDENTITY,
  experimental, Integer32
     FROM SNMPv2-SMI
  TEXTUAL-CONVENTION
```

```
    FROM SNMPv2-TC
  MODULE-COMPLIANCE, OBJECT-GROUP
    FROM SNMPv2-CONF
  usmUserEntry
    FROM SNMP-USER-BASED-SM-MIB
  SnmpAdminString
    FROM SNMP-FRAMEWORK-MIB;

snmpUsmDHObjectsMIB MODULE-IDENTITY
  LAST-UPDATED "200003060000Z"  -- 6 March 2000, Midnight
  ORGANIZATION "Excite@Home"
  CONTACT-INFO "Author: Mike StJohns
            Postal: Excite@Home
                 450 Broadway
                 Redwood City, CA 94063
            Email:  stjohns@corp.home.net
            Phone:  +1-650-556-5368"

  DESCRIPTION
     "The management information definitions for providing forward
  secrecy for key changes for the usmUserTable, and for providing a
  method
 for 'kickstarting' access to the agent via a Diffie-Helman
  key agreement."

  REVISION     "200003060000Z"
  DESCRIPTION
    "Initial version published as RFC 2786."


  ::= { experimental 101 }  -- IANA DHKEY-CHANGE 101

-- Administrative assignments

usmDHKeyObjects OBJECT IDENTIFIER ::= { snmpUsmDHObjectsMIB 1 }
usmDHKeyConformance OBJECT IDENTIFIER ::= { snmpUsmDHObjectsMIB 2 }

-- Textual conventions

DHKeyChange ::=         TEXTUAL-CONVENTION
  STATUS            current
  DESCRIPTION
     "Upon initialization, or upon creation of a row containing an
  object of this type, and after any successful SET of this value, a
  GET of this value returns 'y' where y = g^xa MOD p, and where g is
  the base from usmDHParameters, p is the prime from
  usmDHParameters, and xa is a new random integer selected by the
  agent in the interval 2^(l-1) <= xa < 2^l < p-1.  'l' is the
```

optional privateValueLength from usmDHParameters in bits. If 'l' is omitted,
then xa (and xr below) is selected in the interval 0 <= xa < p-1. y is expressed as an OCTET STRING 'PV' of length 'k' which satisfies

$$y = \sum_{i=1}^{k} 2^{(8(k-i))} PV'i$$

where PV1,...,PVk are the octets of PV from first to last, and where PV1 <> 0.

A successful SET consists of the value 'y' expressed as an OCTET STRING as above concatenated with the value 'z'(expressed as an OCTET STRING in the same manner as y) where z = g^xr MOD p, where g, p and l are as above, and where xr is a new random integer selected by the manager in the interval 2^(l-1) <= xr < 2^l < p-1. A SET to an object of this type will fail with the error wrongValue if the current 'y' does not match the 'y' portion of the value of the varbind for the object. (E.g. GET yout, SET concat(yin, z), yout <> yin).

Note that the private values xa and xr are never transmitted from manager to device or vice versa, only the values y and z.
Obviously, these values must be retained until a successful SET on the associated object.

The shared secret 'sk' is calculated at the agent as sk = z^xa MOD p, and at the manager as sk = y^xr MOD p.

Each object definition of this type MUST describe how to map from the shared secret 'sk' to the operational key value used by the protocols and operations related to the object. In general, if n bits of key are required, the author suggests using the n right-most bits of the shared secret as the operational key value."
REFERENCE
"-- Diffie-Hellman Key-Agreement Standard, PKCS #3;
RSA Laboratories, November 1993"
SYNTAX OCTET STRING

-- Diffie Hellman public values

usmDHPublicObjects OBJECT IDENTIFIER ::= { usmDHKeyObjects 1 }

usmDHParameters OBJECT-TYPE
SYNTAX OCTET STRING

```
  MAX-ACCESS read-write
  STATUS  current
  DESCRIPTION
     "The public Diffie-Hellman parameters for doing
 a Diffie-Hellman
  key agreement for this device.  This is encoded as an ASN.1
  DHParameter per PKCS #3, section 9.  E.g.

     DHParameter ::= SEQUENCE {
       prime   INTEGER,   -- p
       base    INTEGER,   -- g
       privateValueLength  INTEGER OPTIONAL }


  Implementors are encouraged to use either the values from
  Oakley Group 1  or the values of from Oakley Group 2 as specified
  in RFC-2409, The Internet Key Exchange, Section 6.1, 6.2 as the
  default for this object.  Other values may be used, but the
  security properties of those values MUST be well understood and
  MUST meet the requirements of PKCS #3 for the selection of
  Diffie-Hellman primes.

     In addition, any time usmDHParameters changes, all values of
  type DHKeyChange will change and new random numbers MUST be
  generated by the agent for each DHKeyChange object."
  REFERENCE
     "-- Diffie-Hellman Key-Agreement Standard, PKCS #3,
        RSA Laboratories,
 November 1993
      -- The Internet Key Exchange, RFC 2409, November 1998,
        Sec 6.1, 6.2"
  ::= { usmDHPublicObjects 1 }

usmDHUserKeyTable OBJECT-TYPE
  SYNTAX  SEQUENCE OF UsmDHUserKeyEntry
  MAX-ACCESS not-accessible
  STATUS  current
  DESCRIPTION
     "This table augments and extends the usmUserTable and provides
  4 objects which exactly mirror the objects in that table with the
  textual convention of 'KeyChange'.  This extension allows key
  changes to be done in a manner where the knowledge of the current
  secret plus knowledge of the key change data exchanges (e.g. via
  wiretapping)  will not reveal the new key."
  ::= { usmDHPublicObjects 2 }

usmDHUserKeyEntry OBJECT-TYPE
  SYNTAX  UsmDHUserKeyEntry
```

```
  MAX-ACCESS not-accessible
  STATUS  current
  DESCRIPTION
     "A row of DHKeyChange objects which augment or replace the
  functionality of the KeyChange objects in the base table row."
  AUGMENTS { usmUserEntry }
   ::= {usmDHUserKeyTable 1 }

UsmDHUserKeyEntry ::= SEQUENCE {
     usmDHUserAuthKeyChange          DHKeyChange,
  usmDHUserOwnAuthKeyChange   DHKeyChange,
     usmDHUserPrivKeyChange          DHKeyChange,
     usmDHUserOwnPrivKeyChange       DHKeyChange
     }

usmDHUserAuthKeyChange OBJECT-TYPE
  SYNTAX  DHKeyChange
  MAX-ACCESS read-create
  STATUS  current
  DESCRIPTION
     "The object used to change any given user's Authentication Key
  using a Diffie-Hellman key exchange.

  The right-most n bits of the shared secret 'sk', where 'n' is the
  number of bits required for the protocol defined by
  usmUserAuthProtocol, are installed as the operational
  authentication key for this row after a successful SET."
  ::= { usmDHUserKeyEntry 1 }

usmDHUserOwnAuthKeyChange OBJECT-TYPE
  SYNTAX  DHKeyChange
  MAX-ACCESS read-create
  STATUS  current
  DESCRIPTION
     "The object used to change the agents own Authentication Key
  using a Diffie-Hellman
 key exchange.

  The right-most n bits of the shared secret 'sk', where 'n' is the
  number of bits required for the protocol defined by
  usmUserAuthProtocol, are installed as the operational
  authentication key for this row after a successful SET."
  ::= { usmDHUserKeyEntry 2 }

usmDHUserPrivKeyChange OBJECT-TYPE
  SYNTAX  DHKeyChange
  MAX-ACCESS read-create
  STATUS  current
```

```
    DESCRIPTION
        "The object used to change any given user's Privacy Key using
    a Diffie-Hellman key exchange.

    The right-most n bits of the shared secret 'sk', where 'n' is the
    number of bits required for the protocol defined by
    usmUserPrivProtocol, are installed as the operational privacy key
    for this row after a successful SET."
    ::= { usmDHUserKeyEntry 3 }

usmDHUserOwnPrivKeyChange OBJECT-TYPE
    SYNTAX  DHKeyChange
    MAX-ACCESS read-create
    STATUS  current
    DESCRIPTION
        "The object used to change the agent's own Privacy Key using a
     Diffie-Hellman key exchange.

    The right-most n bits of the shared secret 'sk', where 'n' is the
    number of bits required for the protocol defined by
    usmUserPrivProtocol, are installed as the operational privacy key
    for this row after a successful SET."
    ::= { usmDHUserKeyEntry 4 }

usmDHKickstartGroup OBJECT IDENTIFIER ::= { usmDHKeyObjects 2 }

usmDHKickstartTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF UsmDHKickstartEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A table of mappings between zero or more Diffie-Helman key
    agreement values and entries in the usmUserTable.  Entries in this
    table are created by providing the associated device with a
    Diffie-Helman public value and a usmUserName/usmUserSecurityName
    pair during initialization. How these values are provided is
    outside the scope of this MIB, but could be provided manually, or
    through a configuration file.  Valid public value/name pairs
    result
   in the creation of a row in this table as well as the
    creation of an associated row (with keys derived as indicated) in
    the usmUserTable.  The actual access the related usmSecurityName
    has is dependent on the entries in the VACM tables.  In general,
    an implementor will specify one or more standard security names
    and will provide entries in the VACM tables granting various
    levels of access to those names.  The actual content of the VACM
    table is beyond the scope of this MIB.
```

```
   Note: This table is expected to be readable without authentication
   using the usmUserSecurityName 'dhKickstart'.  See the conformance
   statements for details."
   ::= { usmDHKickstartGroup 1 }

usmDHKickstartEntry OBJECT-TYPE
   SYNTAX      UsmDHKickstartEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION

      "An entry in the usmDHKickstartTable.  The agent SHOULD either
   delete this entry or mark it as inactive upon a successful SET of
    any of the KeyChange-typed objects in the usmUserEntry or upon a
   successful SET of any of the DHKeyChange-typed objects in the
   usmDhKeyChangeEntry where the related usmSecurityName (e.g. row of
   usmUserTable or row of ushDhKeyChangeTable) equals this entry's
   usmDhKickstartSecurityName.  In otherwords, once you've changed
   one or more of the keys for a row in usmUserTable with a
   particular security name, the row in this table with that same
   security name is no longer useful or meaningful."

   INDEX   { usmDHKickstartIndex }
   ::= {usmDHKickstartTable 1 }

UsmDHKickstartEntry ::= SEQUENCE  {
      usmDHKickstartIndex     Integer32,
      usmDHKickstartMyPublic  OCTET STRING,
      usmDHKickstartMgrPublic OCTET STRING,
      usmDHKickstartSecurityName      SnmpAdminString
      }

usmDHKickstartIndex OBJECT-TYPE
   SYNTAX      Integer32  (1..2147483647)
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "Index value for
 this row."
   ::= { usmDHKickstartEntry 1 }

usmDHKickstartMyPublic OBJECT-TYPE
   SYNTAX      OCTET STRING
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The agent's Diffie-Hellman public value for this row.  At
   initialization, the agent generates a random number and derives
```

its public value from that number. This public value is published here. This public value 'y' equals g^r MOD p where g is the from the set of Diffie-Hellman parameters, p is the prime from those parameters, and r is a random integer selected by the agent in the interval 2^(l-1) <= r < p-1 < 2^l. If l is unspecified, then r is a random integer selected in the interval 0 <= r < p-1

The public value is expressed as an OCTET STRING 'PV' of length 'k' which satisfies

$$y = \sum_{i=1}^{k} 2^{(8(k-i))} PV'i$$

where PV1,...,PVk are the octets of PV from first to last, and where PV1 != 0.

The following DH parameters (Oakley group #2, RFC 2409, sec 6.1, 6.2) are used for this object:

g = 2
p = FFFFFFFF FFFFFFFF C90FDAA2 2168C234 C4C6628B 80DC1CD1
29024E08 8A67CC74 020BBEA6 3B139B22 514A0879 8E3404DD
EF9519B3 CD3A431B 302B0A6D F25F1437 4FE1356D 6D51C245
E485B576 625E7EC6 F44C42E9 A637ED6B 0BFF5CB6 F406B7ED
EE386BFB 5A899FA5 AE9F2411 7C4B1FE6 49286651 ECE65381
FFFFFFFF FFFFFFFF
l=1024
"

REFERENCE
"-- Diffie-Hellman Key-Agreement Standard, PKCS#3v1.4;
RSA Laboratories, November 1993
-- The Internet Key Exchange, RFC2409;
Harkins, D., Carrel, D.; November 1998"
::= { usmDHKickstartEntry 2 }

usmDHKickstartMgrPublic OBJECT-TYPE
SYNTAX OCTET STRING
MAX-ACCESS read-only
STATUS current
DESCRIPTION

"The manager's Diffie-Hellman public value for this row. Note that this value is not set via the SNMP agent, but may be set via some out of band

method, such as the device's configuration file.
The manager calculates this value in the same manner and using the same parameter set as the agent does. E.g. it selects a random number 'r', calculates y = g^r mod p and provides 'y' as the public number expressed as an OCTET STRING. See usmDHKickstartMyPublic for details.

When this object is set with a valid value during initialization, a row is created in the usmUserTable with the following values:

usmUserEngineID localEngineID
usmUserName [value of usmDHKickstartSecurityName]
usmUserSecurityName [value of usmDHKickstartSecurityName]
usmUserCloneFrom ZeroDotZero
usmUserAuthProtocol usmHMACMD5AuthProtocol
usmUserAuthKeyChange -- derived from set value
usmUserOwnAuthKeyChange -- derived from set value
usmUserPrivProtocol usmDESPrivProtocol
usmUserPrivKeyChange -- derived from set value
usmUserOwnPrivKeyChange -- derived from set value
usmUserPublic "
usmUserStorageType permanent
usmUserStatus active

A shared secret 'sk' is calculated at the agent as sk = mgrPublic^r mod p where r is the agents random number and p is the DH prime from the common parameters. The underlying privacy key for this row is derived from sk by applying the key derivation function PBKDF2 defined in PKCS#5v2.0 with a salt of 0xd1310ba6, and iterationCount of 500, a keyLength of 16 (for usmDESPrivProtocol), and a prf (pseudo random function) of 'id-hmacWithSHA1'. The underlying authentication key for this row is derived from sk by applying the key derivation function PBKDF2 with a salt of 0x98dfb5ac , an interation count of 500, a keyLength of 16 (for usmHMAC5AuthProtocol), and a prf of 'id-hmacWithSHA1'. Note: The salts are the first two words in the ks0 [key schedule 0] of the BLOWFISH
cipher from 'Applied
Cryptography' by Bruce Schnier - they could be any relatively random string of bits.

The manager can use its knowledge of its own random number and the agent's public value to kickstart its access to the agent in a secure manner. Note that the security of this approach is directly related to the strength of the authorization security of the out of band provisioning of the managers public value (e.g. the configuration file), but is not dependent at all on the strength of the confidentiality of the out of band provisioning

```
  data."
  REFERENCE
     "-- Password-Based Cryptography Standard, PKCS#5v2.0;
        RSA Laboratories, March 1999
      -- Applied Cryptography, 2nd Ed.; B. Schneier,
        Counterpane Systems; John Wiley & Sons, 1996"
  ::= { usmDHKickstartEntry 3 }

usmDHKickstartSecurityName OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      "The usmUserName and usmUserSecurityName in the usmUserTable
  associated with this row.  This is provided in the same manner and
  at the same time as the usmDHKickstartMgrPublic value -
  e.g. possibly manually, or via the device's configuration file."
  ::= { usmDHKickstartEntry 4 }

-- Conformance Information

usmDHKeyMIBCompliances  OBJECT IDENTIFIER ::= { usmDHKeyConformance 1 }
usmDHKeyMIBGroups       OBJECT IDENTIFIER ::= { usmDHKeyConformance 2 }

-- Compliance statements

usmDHKeyMIBCompliance   MODULE-COMPLIANCE
  STATUS      current
  DESCRIPTION
     "The compliance statement for this module."
  MODULE
     GROUP usmDHKeyMIBBasicGroup
     DESCRIPTION
     "This group MAY be implemented by any agent which
     implements the usmUserTable and which wishes to provide the
     ability to change user and agent authentication and privacy
     keys via Diffie-Hellman key exchanges."

     GROUP usmDHKeyParamGroup
     DESCRIPTION
         "This group MUST be implemented by any agent which
     implements a MIB containing the DHKeyChange Textual
     Convention defined in this module."

     GROUP usmDHKeyKickstartGroup
     DESCRIPTION
        "This group MAY be implemented by any agent which
     implements the usmUserTable and which wishes the ability to
```

populate the USM table based on out-of-band provided DH ignition values.

Any agent implementing this group is expected to provide preinstalled entries in the vacm tables as follows:

In the usmUserTable: This entry allows access to the system and dhKickstart groups

```
usmUserEngineID         localEngineID
usmUserName             'dhKickstart'
usmUserSecurityName     'dhKickstart'
usmUserCloneFrom        ZeroDotZero
usmUserAuthProtocol     none
usmUserAuthKeyChange    ''
usmUserOwnAuthKeyChange ''
usmUserPrivProtocol
none
usmUserPrivKeyChange    ''
usmUserOwnPrivKeyChange ''
usmUserPublic           ''
usmUserStorageType      permanent
usmUserStatus           active
```

In the vacmSecurityToGroupTable: This maps the initial user into the accessible objects.

```
vacmSecurityModel               3 (USM)
vacmSecurityName                'dhKickstart'
vacmGroupName                   'dhKickstart'
vacmSecurityToGroupStorageType  permanent
vacmSecurityToGroupStatus       active
```

In the vacmAccessTable: Group name to view name translation.

```
vacmGroupName                   'dhKickstart'
vacmAccessContextPrefix         ''
vacmAccessSecurityModel         3 (USM)
vacmAccessSecurityLevel         noAuthNoPriv
vacmAccessContextMatch          exact
vacmAccessReadViewName          'dhKickRestricted'
vacmAccessWriteViewName         ''
vacmAccessNotifyViewName
'dhKickRestricted'
vacmAccessStorageType           permanent
vacmAccessStatus                active
```

In the vacmViewTreeFamilyTable: Two entries to allow the initial entry to access the system and kickstart groups.

```
      vacmViewTreeFamilyViewName      'dhKickRestricted'
      vacmViewTreeFamilySubtree       1.3.6.1.2.1.1  (system)
      vacmViewTreeFamilyMask          ''
      vacmViewTreeFamilyType          1
      vacmViewTreeFamilyStorageType   permanent
      vacmViewTreeFamilyStatus        active

      vacmViewTreeFamilyViewName      'dhKickRestricted'
      vacmViewTreeFamilySubtree       (usmDHKickstartTable OID)
      vacmViewTreeFamilyMask          ''
      vacmViewTreeFamilyType          1
      vacmViewTreeFamilyStorageType   permanent
      vacmViewTreeFamilyStatus        active
      ''

      OBJECT usmDHParameters
      MIN-ACCESS      read-only
      DESCRIPTION
         "It
 is compliant to implement this object as read-only for
      any device."

   ::= { usmDHKeyMIBCompliances 1 }

-- Units of Compliance

usmDHKeyMIBBasicGroup OBJECT-GROUP
   OBJECTS     {
                usmDHUserAuthKeyChange,
                usmDHUserOwnAuthKeyChange,
                usmDHUserPrivKeyChange,
                usmDHUserOwnPrivKeyChange
               }
   STATUS      current
   DESCRIPTION
      ""
   ::= { usmDHKeyMIBGroups 1 }

usmDHKeyParamGroup OBJECT-GROUP
   OBJECTS     {
                usmDHParameters
               }
   STATUS      current
   DESCRIPTION
      "The mandatory object for all MIBs which use the DHKeyChange
   textual convention."
   ::= { usmDHKeyMIBGroups 2 }
```

```
usmDHKeyKickstartGroup OBJECT-GROUP
  OBJECTS     {
                usmDHKickstartMyPublic,
                usmDHKickstartMgrPublic,
                usmDHKickstartSecurityName
              }
  STATUS      current
  DESCRIPTION
      "The objects used
 for kickstarting one or more SNMPv3 USM
  associations via a configuration file or other out of band,
  non-confidential access."
  ::= { usmDHKeyMIBGroups 3 }


END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/SNMP-USM-DH-OBJECTS-MIB
No license file was found, but licenses were detected in source scan.

```
DOT3-OAM-MIB DEFINITIONS ::= BEGIN

IMPORTS
  MODULE-IDENTITY, mib-2, OBJECT-TYPE, Counter32, Unsigned32,
    Integer32, NOTIFICATION-TYPE
    FROM SNMPv2-SMI
    -- from [RFC2578]
  TEXTUAL-CONVENTION, MacAddress, TimeStamp, TruthValue

    FROM SNMPv2-TC
    -- from [RFC2579]
  CounterBasedGauge64
    FROM HCNUM-TC
    -- from [RFC2856]
  ifIndex
    FROM IF-MIB
    -- from [RFC2863]
  MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
    FROM SNMPv2-CONF;



    -- from [RFC2580]

  dot3OamMIB MODULE-IDENTITY
    LAST-UPDATED "200706140000Z"  -- June 14,2007"
```

ORGANIZATION
"IETF Ethernet Interfaces and Hub MIB Working Group"
CONTACT-INFO
"WG Charter:
http://www.ietf.org/html.charters/hubmib-charter.html
Mailing lists:
General Discussion: hubmib@ietf.org
To Subscribe: hubmib-requests@ietf.org
In Body: subscribe your_email_address
Chair: Bert Wijnen
Alcatel-Lucent
Email: bwijnen at alcatel-lucent dot com
Editor: Matt Squire
Hatteras Networks
E-mail: msquire at hatterasnetworks dot com
"
DESCRIPTION
"The MIB module for managing the new Ethernet OAM features
introduced by the Ethernet in the First Mile taskforce (IEEE
802.3ah). The functionality presented here is based on IEEE
802.3ah [802.3ah], released in October, 2004. [802.3ah] was
prepared as an addendum to the standing version of IEEE 802.3
[802.3-2002]. Since then, [802.3ah] has been
merged into the base IEEE 802.3 specification in [802.3-2005].

In particular, this MIB focuses on the new OAM functions
introduced in Clause 57 of [802.3ah]. The OAM functionality
of Clause 57 is controlled by new management attributes
introduced in Clause 30 of [802.3ah]. The OAM functions are
not specific to any particular Ethernet
physical layer, and
can be generically applied to any Ethernet interface of
[802.3-2002].

An Ethernet OAM protocol data unit is a valid Ethernet frame
with a destination MAC address equal to the reserved MAC
address for Slow Protocols (See 43B of [802.3ah]), a
lengthOrType field equal to the reserved type for Slow
Protocols, and a Slow Protocols subtype equal to that of the
subtype reserved for Ethernet OAM. OAMPDU is used throughout
this document as an abbreviation for Ethernet OAM protocol
data unit.

The following reference is used throughout this MIB module:

[802.3ah] refers to:
IEEE Std 802.3ah-2004: 'Draft amendment to -
Information technology - Telecommunications and
information exchange between systems - Local and
metropolitan area networks - Specific requirements - Part
3: Carrier sense multiple access with collision detection
(CSMA/CD) access method and physical layer specifications
- Media Access Control Parameters, Physical Layers and
Management Parameters for subscriber access networks',
October 2004.

[802.3-2002] refers to:
IEEE Std 802.3-2002:
'Information technology - Telecommunications and
information exchange between systems - Local and
metropolitan area networks - Specific requirements - Part
3: Carrier sense multiple access with collision detection
(CSMA/CD) access method and physical layer specifications
- Media Access Control Parameters, Physical Layers and
Management Parameters for subscriber access networks',
March 2002.

[802.3-2005] refers to:
IEEE Std 802.3-2005:
'Information technology - Telecommunications and
information exchange between systems - Local and
metropolitan area networks
- Specific requirements - Part
3: Carrier sense multiple access with collision detection
(CSMA/CD) access method and physical layer specifications
- Media Access Control Parameters, Physical Layers and
Management Parameters for subscriber access networks',
December 2005.

[802-2001] refers to:
'IEEE Standard for LAN/MAN (Local Area
Network/Metropolitan Area Network): Overview and
Architecture', IEEE 802, June 2001.

Copyright (c) The IETF Trust (2007). This version of
this MIB module is part of RFC 4878; See the RFC itself for
full legal notices. "

REVISION "200706140000Z" -- June 14, 2007"
DESCRIPTION "Initial version, published as RFC 4878."
::= { mib-2 158 }

--

```
-- Sections of the Ethernet OAM MIB



--
   dot3OamNotifications OBJECT IDENTIFIER ::= { dot3OamMIB 0 }
   dot3OamObjects       OBJECT IDENTIFIER ::= { dot3OamMIB 1 }

  dot3OamConformance   OBJECT IDENTIFIER ::= { dot3OamMIB 2 }

--
-- Textual conventions for the OAM MIB
--
EightOTwoOui ::= TEXTUAL-CONVENTION
  STATUS       current
  DESCRIPTION
    "24-bit Organizationally Unique Identifier.  Information on
    OUIs can be found in IEEE 802-2001 [802-2001], Clause 9."
  SYNTAX       OCTET STRING(SIZE(3))

-- ****************************************************************
--
-- Ethernet OAM Control group
--

dot3OamTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF Dot3OamEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains the primary controls and status for the
    OAM capabilities of an Ethernet-like interface.  There will be
    one row in this table for each Ethernet-like interface in the
    system that supports the OAM functions defined in [802.3ah].
    "
  ::= { dot3OamObjects 1 }

dot3OamEntry OBJECT-TYPE
  SYNTAX     Dot3OamEntry
   MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "An entry in the table that contains information on the
    Ethernet OAM function for a single Ethernet like interface.
    Entries in the table are created automatically for each
    interface supporting Ethernet OAM.  The status of the row
    entry can be determined from dot3OamOperStatus.
```

```
    A dot3OamEntry is indexed in the dot3OamTable by the ifIndex
    object of the Interfaces MIB.
    "
  INDEX       { ifIndex }
  ::= { dot3OamTable 1 }



Dot3OamEntry ::=
  SEQUENCE {
    dot3OamAdminState               INTEGER,
    dot3OamOperStatus               INTEGER,
    dot3OamMode                     INTEGER,
    dot3OamMaxOamPduSize            Unsigned32,
    dot3OamConfigRevision           Unsigned32,
    dot3OamFunctionsSupported       BITS
  }

dot3OamAdminState OBJECT-TYPE
  SYNTAX      INTEGER {
                enabled(1),
                 disabled(2)
               }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "This object is used to provision the default administrative
    OAM mode for this interface.  This object represents the
    desired state of OAM for this interface.

    The dot3OamAdminState always starts in the disabled(2) state
    until an explicit management action or configuration
    information retained by the system causes a transition to the
    enabled(1) state.  When enabled(1), Ethernet OAM will attempt
    to operate over this interface.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.2"
  ::= { dot3OamEntry 1 }

dot3OamOperStatus OBJECT-TYPE
  SYNTAX      INTEGER {
                disabled(1),
                linkFault(2),
                passiveWait(3),
                activeSendLocal(4),
                sendLocalAndRemote(5),
                sendLocalAndRemoteOk(6),
                oamPeeringLocallyRejected(7),
```

```
                oamPeeringRemotelyRejected(8),
                operational(9),
                nonOperHalfDuplex(10)
              }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "At initialization and failure conditions, two OAM entities on
      the same full-duplex Ethernet link begin a discovery phase to
      determine what OAM capabilities may be used on that link.  The
      progress of this initialization is controlled by the OA
      sublayer.

      This value is always disabled(1) if OAM is disabled on this
      interface via the dot3OamAdminState.

      If the link has detected a fault and is transmitting OAMPDUs
      with a link fault indication, the value is linkFault(2).
      Also, if the interface is not operational (ifOperStatus is
      not up(1)), linkFault(2) is returned.  Note that the object
      ifOperStatus may not be up(1) as a result of link failure or
      administrative
  action (ifAdminState being down(2) or
      testing(3)).

      The passiveWait(3) state is returned only by OAM entities in
      passive mode (dot3OamMode) and reflects the state in which the
      OAM entity is waiting to see if the peer device is OA
      capable.  The activeSendLocal(4) value is used by active mode
      devices (dot3OamMode) and reflects the OAM entity actively
      trying to discover whether the peer has OAM capability but has
      not yet made that determination.

      The state sendLocalAndRemote(5) reflects that the local OA
      entity has discovered the peer but has not yet accepted or
      rejected the configuration of the peer.  The local device can,
      for whatever reason, decide that the peer device is
      unacceptable and decline OAM peering.  If the local OAM entity
      rejects the peer OAM entity, the state becomes
      oamPeeringLocallyRejected(7).  If the OAM peering is allowed
      by the local device, the state moves
  to
      sendLocalAndRemoteOk(6).  Note that both the
      sendLocalAndRemote(5) and oamPeeringLocallyRejected(7) states
      fall within the state SEND_LOCAL_REMOTE of the Discovery state
```

diagram [802.3ah, Figure 57-5], with the difference being
whether the local OAM client has actively rejected the peering
or has just not indicated any decision yet. Whether a peering
decision has been made is indicated via the local flags field
in the OAMPDU (reflected in the aOAMLocalFlagsField of
30.3.6.1.10).

If the remote OAM entity rejects the peering, the state
becomes oamPeeringRemotelyRejected(8). Note that both the
sendLocalAndRemoteOk(6) and oamPeeringRemotelyRejected(8)
states fall within the state SEND_LOCAL_REMOTE_OK of the
Discovery state diagram [802.3ah, Figure 57-5], with the
difference being whether the remote OAM client has rejected

the peering or has just not yet decided. This
is indicated
via the remote flags field in the OAMPDU (reflected in the
aOAMRemoteFlagsField of 30.3.6.1.11).

When the local OAM entity learns that both it and the remote
OAM entity have accepted the peering, the state moves to
operational(9) corresponding to the SEND_ANY state of the
Discovery state diagram [802.3ah, Figure 57-5].

Since Ethernet OAM functions are not designed to work
completely over half-duplex interfaces, the value
nonOperHalfDuplex(10) is returned whenever Ethernet OAM is
enabled (dot3OamAdminState is enabled(1)), but the interface
is in half-duplex operation.
"
REFERENCE "[802.3ah], 30.3.6.1.4, 30.3.6.1.10, 30.3.6.1.11"
::= { dot3OamEntry 2 }

dot3OamMode OBJECT-TYPE
SYNTAX INTEGER {
passive(1),
active(2)
}
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"This object configures
the mode of OAM operation for this
Ethernet-like interface. OAM on Ethernet interfaces may be in
'active' mode or 'passive' mode. These two modes differ in
that active mode provides additional capabilities to initiate

monitoring activities with the remote OAM peer entity, while
passive mode generally waits for the peer to initiate OA
actions with it. As an example, an active OAM entity can put
the remote OAM entity in a loopback state, where a passive OA
entity cannot.

The default value of dot3OamMode is dependent on the type of
system on which this Ethernet-like interface resides. The
default value should be 'active(2)' unless it is known that
this system should take on a subservient role to the other
device connected over this interface.

Changing this value results in incrementing the configuration
revision field of locally generated OAMPDUs (30.3.6.1.12) and
potentially
re-doing the OAM discovery process if the
dot3OamOperStatus was already operational(9).
"
REFERENCE "[802.3ah], 30.3.6.1.3"

::= { dot3OamEntry 3 }

dot3OamMaxOamPduSize OBJECT-TYPE
SYNTAX Unsigned32 (64..1518)
UNITS "octets"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The largest OAMPDU that the OAM entity supports. OA
entities exchange maximum OAMPDU sizes and negotiate to use
the smaller of the two maximum OAMPDU sizes between the peers.
This value is determined by the local implementation.
"
REFERENCE "[802.3ah], 30.3.6.1.8"
::= { dot3OamEntry 4 }

dot3OamConfigRevision OBJECT-TYPE
SYNTAX Unsigned32(0..65535)
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The configuration revision of the OAM entity as reflected in
the latest OAMPDU sent by the OAM entity. The config revision
is used by OAM entities
to indicate that configuration changes
have occurred, which might require the peer OAM entity to

```
    re-evaluate whether OAM peering is allowed.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.12"
  ::= { dot3OamEntry 5 }

 dot3OamFunctionsSupported OBJECT-TYPE
  SYNTAX      BITS {
                unidirectionalSupport (0),
                loopbackSupport(1),
                eventSupport(2),
                variableSupport(3)
              }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The OAM functions supported on this Ethernet-like interface.
    OAM consists of separate functional sets beyond the basic
    discovery process that is always required.  These functional
    groups can be supported independently by any implementation.
    These values are communicated to the peer via the local
    configuration field of Information OAMPDUs.

    Setting 'unidirectionalSupport(0)' indicates that the
OA



    entity supports the transmission of OAMPDUs on links that are
    operating in unidirectional mode (traffic flowing in one
    direction only).  Setting 'loopbackSupport(1)' indicates that
    the OAM entity can initiate and respond to loopback commands.
    Setting 'eventSupport(2)' indicates that the OAM entity can
    send and receive Event Notification OAMPDUs.  Setting
    'variableSupport(3)' indicates that the OAM entity can send
    and receive Variable Request and Response OAMPDUs.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.6"
  ::= { dot3OamEntry 6 }

 -- ****************************************************************
 --
 -- Ethernet OAM Peer group
 --

 dot3OamPeerTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF Dot3OamPeerEntry
  MAX-ACCESS  not-accessible
  STATUS      current
```

```
  DESCRIPTION
    "This table contains information about the OAM peer for a
    particular Ethernet-like interface.  OAM entities communicate
     with a single OAM peer entity on Ethernet links on which OA
    is enabled and operating properly.  There is one entry in this
    table for each entry in the dot3OamTable for which information
    on the peer OAM entity is available.
    "
  ::= { dot3OamObjects 2 }

dot3OamPeerEntry OBJECT-TYPE
  SYNTAX      Dot3OamPeerEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An entry in the table containing information on the peer OA
    entity for a single Ethernet-like interface.

    Note that there is at most one OAM peer for each Ethernet-like
    interface.  Entries are automatically created when information
    about the OAM peer entity becomes available, and automatically
    deleted when the OAM peer entity is no longer in
    communication.  Peer information is not available when
    dot3OamOperStatus is disabled(1), linkFault(2),
    passiveWait(3), activeSendLocal(4), or nonOperHalfDuplex(10).
     "
  INDEX       { ifIndex }



  ::= { dot3OamPeerTable 1 }

Dot3OamPeerEntry ::=
  SEQUENCE {
    dot3OamPeerMacAddress             MacAddress,
    dot3OamPeerVendorOui              EightOTwoOui,
    dot3OamPeerVendorInfo             Unsigned32,
    dot3OamPeerMode                   INTEGER,
    dot3OamPeerMaxOamPduSize          Unsigned32,
    dot3OamPeerConfigRevision         Unsigned32,
    dot3OamPeerFunctionsSupported     BITS
  }

dot3OamPeerMacAddress OBJECT-TYPE
  SYNTAX      MacAddress
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
```

```
    "The MAC address of the peer OAM entity.  The MAC address is
    derived from the most recently received OAMPDU.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.5."
  ::= { dot3OamPeerEntry 1 }

 dot3OamPeerVendorOui OBJECT-TYPE
  SYNTAX      EightOTwoOui
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The
OUI of the OAM peer as reflected in the latest
    Information OAMPDU received with a Local Information TLV.  The
    OUI can be used to identify the vendor of the remote OA
    entity.  This value is initialized to three octets of zero
    before any Local Information TLV is received.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.16."
  ::= { dot3OamPeerEntry 2 }

 dot3OamPeerVendorInfo OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The Vendor Info of the OAM peer as reflected in the latest
    Information OAMPDU received with a Local Information TLV.
    The semantics of the Vendor Information field is proprietary
    and specific to the vendor (identified by the
    dot3OamPeerVendorOui).  This information could, for example,



    be used to identify a specific product or product family.
    This value is initialized to zero before any Local
    Information TLV is received.
     "
  REFERENCE   "[802.3ah], 30.3.6.1.17."
  ::= { dot3OamPeerEntry 3 }

 dot3OamPeerMode OBJECT-TYPE
  SYNTAX      INTEGER {
                passive(1),
                active(2),
                unknown(3)
              }
  MAX-ACCESS  read-only
```

```
  STATUS      current
  DESCRIPTION
    "The mode of the OAM peer as reflected in the latest
    Information OAMPDU received with a Local Information TLV.  The
    mode of the peer can be determined from the Configuration
    field in the Local Information TLV of the last Information
    OAMPDU received from the peer.  The value is unknown(3)
    whenever no Local Information TLV has been received.  The
    values of active(2) and passive(1) are returned when a Local
    Information TLV has been received indicating that the peer is
    in active or passive mode, respectively.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.7."
  ::= { dot3OamPeerEntry 4 }

 dot3OamPeerMaxOamPduSize
OBJECT-TYPE
  SYNTAX      Unsigned32 (0 | 64..1518)
  UNITS       "octets"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The maximum size of OAMPDU supported by the peer as reflected
    in the latest Information OAMPDU received with a Local
    Information TLV.  Ethernet OAM on this interface must not use
    OAMPDUs that exceed this size.  The maximum OAMPDU size can be
    determined from the PDU Configuration field of the Local
    Information TLV of the last Information OAMPDU received from
    the peer.  A value of zero is returned if no Local Information
    TLV has been received.  Otherwise, the value of the OAM peer's
    maximum OAMPDU size is returned in this value.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.9."
  ::= { dot3OamPeerEntry 5 }




 dot3OamPeerConfigRevision OBJECT-TYPE
  SYNTAX      Unsigned32(0..65535)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The
configuration revision of the OAM peer as reflected in
    the latest OAMPDU.  This attribute is changed by the peer
    whenever it has a local configuration change for Ethernet OA
    on this interface.  The configuration revision can be
```

```
    determined from the Revision field of the Local Information
    TLV of the most recently received Information OAMPDU with
    a Local Information TLV.  A value of zero is returned if
    no Local Information TLV has been received.
   "
  REFERENCE   "[802.3ah], 30.3.6.1.13."
  ::= { dot3OamPeerEntry 6 }

 dot3OamPeerFunctionsSupported OBJECT-TYPE
  SYNTAX      BITS {
                unidirectionalSupport (0),
                loopbackSupport(1),
                eventSupport(2),
                variableSupport(3)
              }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The OAM functions supported on this Ethernet-like interface.
    OAM consists of separate functionality
sets above the basic
    discovery process.  This value indicates the capabilities of
    the peer OAM entity with respect to these functions.  This
    value is initialized so all bits are clear.

    If unidirectionalSupport(0) is set, then the peer OAM entity
    supports sending OAM frames on Ethernet interfaces when the
    receive path is known to be inoperable.  If
    loopbackSupport(1) is set, then the peer OAM entity can send
    and receive OAM loopback commands.  If eventSupport(2) is set,
    then the peer OAM entity can send and receive event OAMPDUs to
    signal various error conditions.  If variableSupport(3) is
    set, then the peer OAM entity can send and receive variable
    requests to monitor the attribute value as described in Clause
    57 of [802.3ah].

    The capabilities of the OAM peer can be determined from the
    configuration field of the Local Information TLV of the most
    recently received
Information OAMPDU with a Local Information
    TLV.  All zeros are returned if no Local Information TLV has



    yet been received.
    "
  REFERENCE   "[802.3ah], REFERENCE 30.3.6.1.7."
  ::= { dot3OamPeerEntry 7 }
```

```
-- ****************************************************************
--
-- Ethernet OAM Loopback group
--

dot3OamLoopbackTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF Dot3OamLoopbackEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains controls for the loopback state of the
    local link as well as indicates the status of the loopback
    function.  There is one entry in this table for each entry in
    dot3OamTable that supports loopback functionality (where
    dot3OamFunctionsSupported includes the loopbackSupport bit
    set).

    Loopback can be used to place the remote OAM entity in a state
    where every received frame (except OAMPDUs) is echoed back

  over the same interface on which they were received.  In this
    state, at the remote entity, 'normal' traffic is disabled as
    only the looped back frames are transmitted on the interface.
    Loopback is thus an intrusive operation that prohibits normal
    data flow and should be used accordingly.
    "
  ::= { dot3OamObjects 3 }

dot3OamLoopbackEntry OBJECT-TYPE
  SYNTAX      Dot3OamLoopbackEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An entry in the table, containing information on the loopback
    status for a single Ethernet-like interface.  Entries in the
    table are automatically created whenever the local OAM entity
    supports loopback capabilities.  The loopback status on the
    interface can be determined from the dot3OamLoopbackStatus
    object.
    "
  INDEX       { ifIndex }
  ::= { dot3OamLoopbackTable 1 }

Dot3OamLoopbackEntry ::=
```

```
  SEQUENCE {
    dot3OamLoopbackStatus
          INTEGER,
    dot3OamLoopbackIgnoreRx          INTEGER
  }

 dot3OamLoopbackStatus OBJECT-TYPE
  SYNTAX      INTEGER {
                -- all values, except where noted, can be read
                -- but cannot be written
                noLoopback (1),

                -- initiatingLoopback can be read or written
                initiatingLoopback (2),
                remoteLoopback (3),

                -- terminatingLoopback can be read or written
                terminatingLoopback (4),
                localLoopback (5),
                unknown (6)
              }
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "The loopback status of the OAM entity.  This status is
    determined by a combination of the local parser and
    multiplexer states, the remote parser and multiplexer states,
    as well as by the actions of the local OAM client.  When
    operating in normal mode
with no loopback in progress, the
    status reads noLoopback(1).

    The values initiatingLoopback(2) and terminatingLoopback(4)
    can be read or written.  The other values can only be read -
    they can never be written.  Writing initiatingLoopback causes
    the local OAM entity to start the loopback process with its
    peer.  This value can only be written when the status is
    noLoopback(1).  Writing the value initiatingLoopback(2) in any
    other state has no effect.  When in remoteLoopback(3), writing
    terminatingLoopback(4) causes the local OAM entity to initiate
    the termination of the loopback state.  Writing
    terminatingLoopack(4) in any other state has no effect.

    If the OAM client initiates a loopback and has sent a
    Loopback OAMPDU and is waiting for a response, where the local
    parser and multiplexer states are DISCARD (see [802.3ah,
    57.2.11.1]), the status is 'initiatingLoopback'.  In this
```

case, the local OAM entity has yet to receive any
acknowledgment that the remote OAM entity has received its
loopback command request.

If the local OAM client knows that the remote OAM entity is in
loopback mode (via the remote state information as described
in [802.3ah, 57.2.11.1, 30.3.6.1.15]), the status is
remoteLoopback(3). If the local OAM client is in the process
of terminating the remote loopback [802.3ah, 57.2.11.3,
30.3.6.1.14] with its local multiplexer and parser states in
DISCARD, the status is terminatingLoopback(4). If the remote
OAM client has put the local OAM entity in loopback mode as
indicated by its local parser state, the status is
localLoopback(5).

The unknown(6) status indicates that the parser and
multiplexer combination is unexpected. This status may be
returned if the OAM loopback is in a transition state but
should not persist.

The values of this attribute correspond to the following
values of the local and remote parser and multiplexer states.

value LclPrsr LclMux RmtPrsr RmtMux
noLoopback FWD FWD FWD FWD
initLoopback DISCARD DISCARD FWD FWD
rmtLoopback DISCARD FWD LPBK DISCARD
tmtngLoopback DISCARD DISCARD LPBK DISCARD
lclLoopback LPBK DISCARD DISCARD FWD
unknown *** any other combination ***
"
REFERENCE "[802.3ah], REFERENCE 57.2.11, 30.3.61.14,
30.3.6.1.15"
::= { dot3OamLoopbackEntry 1 }

dot3OamLoopbackIgnoreRx OBJECT-TYPE
SYNTAX INTEGER { ignore(1), process(2) }
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"Since OAM loopback is a disruptive operation (user traffic
does not pass), this attribute provides a mechanism to provide
controls

```
over whether received OAM loopback commands are
    processed or ignored.  When the value is ignore(1), received
    loopback commands are ignored.  When the value is process(2),
    OAM loopback commands are processed.  The default value is to
    ignore loopback commands (ignore(1)).
    "
  REFERENCE   "[802.3ah], REFERENCE 57.2.11, 30.3.61.14,
    30.3.6.1.15"
  ::= { dot3OamLoopbackEntry 2 }



-- ****************************************************************
--
-- Ethernet OAM Statistics group
--

 dot3OamStatsTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF Dot3OamStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "This table contains statistics for the OAM function on a
    particular Ethernet-like interface.  There is an entry in the
    table for every entry in the dot3OamTable.

    The counters in this table are defined as 32-bit entries to
    match the counter size as defined in [802.3ah].
 Given that
    the OA protocol is a slow protocol, the counters increment at
    a slow rate.
    "
  ::= { dot3OamObjects 4 }

 dot3OamStatsEntry OBJECT-TYPE
  SYNTAX      Dot3OamStatsEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An entry in the table containing statistics information on
    the Ethernet OAM function for a single Ethernet-like
    interface.  Entries are automatically created for every entry
    in the dot3OamTable.  Counters are maintained across
    transitions in dot3OamOperStatus.
    "
  INDEX       { ifIndex }
  ::= { dot3OamStatsTable 1 }
```

```
Dot3OamStatsEntry ::=
  SEQUENCE {
        dot3OamInformationTx              Counter32,
        dot3OamInformationRx              Counter32,
        dot3OamUniqueEventNotificationTx    Counter32,
        dot3OamUniqueEventNotificationRx    Counter32,
        dot3OamDuplicateEventNotificationTx
Counter32,
        dot3OamDuplicateEventNotificationRx Counter32,
        dot3OamLoopbackControlTx          Counter32,
        dot3OamLoopbackControlRx          Counter32,
        dot3OamVariableRequestTx          Counter32,
        dot3OamVariableRequestRx          Counter32,
        dot3OamVariableResponseTx         Counter32,



        dot3OamVariableResponseRx         Counter32,
        dot3OamOrgSpecificTx              Counter32,
        dot3OamOrgSpecificRx              Counter32,
        dot3OamUnsupportedCodesTx         Counter32,
        dot3OamUnsupportedCodesRx         Counter32,
        dot3OamFramesLostDueToOam          Counter32
       }

dot3OamInformationTx OBJECT-TYPE
  SYNTAX     Counter32
  UNITS      "frames"
  MAX-ACCESS  read-only
  STATUS     current
  DESCRIPTION
    "A count of the number of Information OAMPDUs transmitted on
     this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.  "
  REFERENCE   "[802.3ah], 30.3.6.1.20."
  ::= { dot3OamStatsEntry 1 }

dot3OamInformationRx OBJECT-TYPE
  SYNTAX     Counter32
  UNITS      "frames"
  MAX-ACCESS  read-only
  STATUS     current
  DESCRIPTION
    "A count of the number of Information OAMPDUs received on this
    interface.
```

Discontinuities of this counter can occur at re-initialization
of the management system, and at other times as indicated by
the value of the ifCounterDiscontinuityTime.
"
REFERENCE "[802.3ah], 30.3.6.1.21."
::= { dot3OamStatsEntry 2 }

dot3OamUniqueEventNotificationTx OBJECT-TYPE
SYNTAX Counter32
UNITS "frames"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"A count
of the number of unique Event OAMPDUs transmitted on
this interface. Event Notifications may be sent in duplicate
to increase the probability of successfully being received,

given the possibility that a frame may be lost in transit.
Duplicate Event Notification transmissions are counted by
dot3OamDuplicateEventNotificationTx.

A unique Event Notification OAMPDU is indicated as an Event
Notification OAMPDU with a Sequence Number field that is
distinct from the previously transmitted Event Notification
OAMPDU Sequence Number.

Discontinuities of this counter can occur at re-initialization
of the management system, and at other times as indicated by
the value of the ifCounterDiscontinuityTime.
"
REFERENCE "[802.3ah], 30.3.6.1.22."
::= { dot3OamStatsEntry 3 }

dot3OamUniqueEventNotificationRx OBJECT-TYPE
SYNTAX Counter32
UNITS "frames"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"A count of the number of unique Event OAMPDUs received on
this interface. Event Notification OAMPDUs may be sent in
duplicate to increase the probability of successfully being
received, given the possibility that a frame may be lost in
transit. Duplicate Event Notification receptions are counted

by dot3OamDuplicateEventNotificationRx.

A unique Event Notification OAMPDU is indicated as an Event Notification OAMPDU with a Sequence Number field that is distinct from the previously received Event Notification OAMPDU Sequence Number.

Discontinuities of this counter can occur at re-initialization of the management system, and at other times as indicated by the value of the ifCounterDiscontinuityTime.
"
REFERENCE "[802.3ah], 30.3.6.1.24."
::= { dot3OamStatsEntry 4 }

dot3OamDuplicateEventNotificationTx OBJECT-TYPE
SYNTAX
Counter32
UNITS "frames"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"A count of the number of duplicate Event OAMPDUs transmitted

on this interface. Event Notification OAMPDUs may be sent in duplicate to increase the probability of successfully being received, given the possibility that a frame may be lost in transit.

A duplicate Event Notification OAMPDU is indicated as an Event Notification OAMPDU with a Sequence Number field that is identical to the previously transmitted Event Notification OAMPDU Sequence Number.

Discontinuities of this counter can occur at re-initialization of the management system, and at other times as indicated by the value of the ifCounterDiscontinuityTime.
"
REFERENCE "[802.3ah], 30.3.6.1.23."
::= { dot3OamStatsEntry 5 }

dot3OamDuplicateEventNotificationRx OBJECT-TYPE
SYNTAX Counter32
UNITS
"frames"
MAX-ACCESS read-only
STATUS current

```
  DESCRIPTION
    "A count of the number of duplicate Event OAMPDUs received on
    this interface.  Event Notification OAMPDUs may be sent in
    duplicate to increase the probability of successfully being
    received, given the possibility that a frame may be lost in
    transit.

    A duplicate Event Notification OAMPDU is indicated as an Event
    Notification OAMPDU with a Sequence Number field that is
    identical to the previously received Event Notification OAMPDU
    Sequence Number.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.25."
  ::= { dot3OamStatsEntry 6 }

dot3OamLoopbackControlTx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS
    current
  DESCRIPTION
    "A count of the number of Loopback Control OAMPDUs transmitted




    on this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.26."
  ::= { dot3OamStatsEntry 7 }

dot3OamLoopbackControlRx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Loopback Control OAMPDUs received
    on this interface.
```

```
    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.27."
  ::= { dot3OamStatsEntry 8 }

 dot3OamVariableRequestTx OBJECT-TYPE
  SYNTAX      Counter32
   UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Variable Request OAMPDUs transmitted
    on this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.28."
  ::= { dot3OamStatsEntry 9 }

 dot3OamVariableRequestRx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Variable Request OAMPDUs received on




    this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.29."
  ::= { dot3OamStatsEntry
 10 }

 dot3OamVariableResponseTx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
```

```
  DESCRIPTION
    "A count of the number of Variable Response OAMPDUs
    transmitted on this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.30."
  ::= { dot3OamStatsEntry 11 }

dot3OamVariableResponseRx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Variable Response OAMPDUs received
    on this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
     "
  REFERENCE   "[802.3ah], 30.3.6.1.31."
  ::= { dot3OamStatsEntry 12 }

 dot3OamOrgSpecificTx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Organization Specific OAMPDUs



    transmitted on this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.32."
  ::= { dot3OamStatsEntry 13 }

dot3OamOrgSpecificRx OBJECT-TYPE
  SYNTAX      Counter32
```

```
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of Organization Specific OAMPDUs
    received on this interface.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other
times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.33."
  ::= { dot3OamStatsEntry 14 }

 dot3OamUnsupportedCodesTx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of OAMPDUs transmitted on this
    interface with an unsupported op-code.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.18."
  ::= { dot3OamStatsEntry 15 }

 dot3OamUnsupportedCodesRx OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of OAMPDUs received on this interface




    with an unsupported op-code.

    Discontinuities
of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
```

```
  REFERENCE   "[802.3ah], 30.3.6.1.19."
  ::= { dot3OamStatsEntry 16 }

 dot3OamFramesLostDueToOam OBJECT-TYPE
  SYNTAX      Counter32
  UNITS       "frames"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "A count of the number of frames that were dropped by the OA
    multiplexer.  Since the OAM multiplexer has multiple inputs
    and a single output, there may be cases where frames are
    dropped due to transmit resource contention.  This counter is
    incremented whenever a frame is dropped by the OAM layer.
    Note that any Ethernet frame, not just OAMPDUs, may be dropped
    by the OAM layer.  This can occur when an OAMPDU takes
    precedence over a 'normal' frame resulting in the 'normal'
    frame being dropped.

    When this counter
 is incremented, no other counters in this
    MIB are incremented.

    Discontinuities of this counter can occur at re-initialization
    of the management system, and at other times as indicated by
    the value of the ifCounterDiscontinuityTime.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.46."
  ::= { dot3OamStatsEntry 17 }

 -- ****************************************************************
 --
 -- Ethernet OAM Event Configuration group
 --

 dot3OamEventConfigTable OBJECT-TYPE
  SYNTAX     SEQUENCE OF Dot3OamEventConfigEntry
  MAX-ACCESS not-accessible
  STATUS     current
  DESCRIPTION
    "Ethernet OAM includes the ability to generate and receive
    Event Notification OAMPDUs to indicate various link problems.
    This table contains the mechanisms to enable Event




    Notifications and configure the thresholds to generate the
    standard Ethernet OAM events.  There is one entry in the table
```

for every entry in
dot3OamTable that supports OAM events
(where dot3OamFunctionsSupported includes the eventSupport
bit set). The values in the table are maintained across
changes to dot3OamOperStatus.

The standard threshold crossing events are:
- Errored Symbol Period Event. Generated when the number of
symbol errors exceeds a threshold within a given window
defined by a number of symbols (for example, 1,000 symbols
out of 1,000,000 had errors).
- Errored Frame Period Event. Generated when the number of
frame errors exceeds a threshold within a given window
defined by a number of frames (for example, 10 frames out
of 1000 had errors).
- Errored Frame Event. Generated when the number of frame
errors exceeds a threshold within a given window defined
by a period of time (for example, 10 frames in 1 second
had errors).
- Errored Frame Seconds
Summary Event. Generated when the
number of errored frame seconds exceeds a threshold within
a given time period (for example, 10 errored frame seconds
within the last 100 seconds). An errored frame second is
defined as a 1 second interval which had >0 frame errors.
There are other events (dying gasp, critical events) that are
not threshold crossing events but which can be
enabled/disabled via this table.
"
::= { dot3OamObjects 5 }

dot3OamEventConfigEntry OBJECT-TYPE
SYNTAX Dot3OamEventConfigEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"Entries are automatically created and deleted from this
table, and exist whenever the OAM entity supports Ethernet OA
events (as indicated by the eventSupport bit in
dot3OamFunctionsSuppported). Values in the table are
maintained across changes to the value of dot3OamOperStatus.

Event
configuration controls when the local management entity
sends Event Notification OAMPDUs to its OAM peer, and when
certain event flags are set or cleared in OAMPDUs.
"
INDEX { ifIndex }

::= { dot3OamEventConfigTable 1 }

```
Dot3OamEventConfigEntry ::=
  SEQUENCE {
        dot3OamErrSymPeriodWindowHi       Unsigned32,
        dot3OamErrSymPeriodWindowLo       Unsigned32,
        dot3OamErrSymPeriodThresholdHi    Unsigned32,
        dot3OamErrSymPeriodThresholdLo    Unsigned32,
        dot3OamErrSymPeriodEvNotifEnable  TruthValue,
        dot3OamErrFramePeriodWindow       Unsigned32,
        dot3OamErrFramePeriodThreshold    Unsigned32,
        dot3OamErrFramePeriodEvNotifEnable TruthValue,
        dot3OamErrFrameWindow             Unsigned32,
        dot3OamErrFrameThreshold          Unsigned32,
        dot3OamErrFrameEvNotifEnable      TruthValue,

     dot3OamErrFrameSecsSummaryWindow   Integer32,
        dot3OamErrFrameSecsSummaryThreshold Integer32,
        dot3OamErrFrameSecsEvNotifEnable  TruthValue,
        dot3OamDyingGaspEnable            TruthValue,
        dot3OamCriticalEventEnable        TruthValue
       }

dot3OamErrSymPeriodWindowHi OBJECT-TYPE
  SYNTAX     Unsigned32
  UNITS      "2^32 symbols"
  MAX-ACCESS  read-write
  STATUS     current
  DESCRIPTION
    "The two objects dot3OamErrSymPeriodWindowHi and
    dot3OamErrSymPeriodLo together form an unsigned 64-bit
    integer representing the number of symbols over which this
    threshold event is defined.  This is defined as
  dot3OamErrSymPeriodWindow = ((2^32)*dot3OamErrSymPeriodWindowHi)
                          + dot3OamErrSymPeriodWindowLo

    If dot3OamErrSymPeriodThreshold symbol errors occur within a
    window of dot3OamErrSymPeriodWindow symbols, an Event

    Notification OAMPDU should be generated with an Errored Symbol
    Period Event TLV indicating that the threshold has been
    crossed in this window.

    The default value for dot3OamErrSymPeriodWindow is the number
    of symbols in one second for the underlying physical layer.
    "
```

```
  REFERENCE   "[802.3ah], 30.3.6.1.34"
  ::= { dot3OamEventConfigEntry 1 }

 dot3OamErrSymPeriodWindowLo OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "symbols"



  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "The two objects dot3OamErrSymPeriodWindowHi and
    dot3OamErrSymPeriodWindowLo together form an unsigned 64-bit
    integer representing the number of symbols over which this
    threshold event is defined.  This is defined as

  dot3OamErrSymPeriodWindow = ((2^32)*dot3OamErrSymPeriodWindowHi)
                            + dot3OamErrSymPeriodWindowLo

    If dot3OamErrSymPeriodThreshold symbol errors
occur within a
    window of dot3OamErrSymPeriodWindow symbols, an Event
    Notification OAMPDU should be generated with an Errored Symbol
    Period Event TLV indicating that the threshold has been
    crossed in this window.

    The default value for dot3OamErrSymPeriodWindow is the number
    of symbols in one second for the underlying physical layer.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.34"
  ::= { dot3OamEventConfigEntry 2 }

 dot3OamErrSymPeriodThresholdHi OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "2^32 symbols"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "The two objects dot3OamErrSymPeriodThresholdHi and
    dot3OamErrSymPeriodThresholdLo together form an unsigned
    64-bit integer representing the number of symbol errors that
    must occur within a given window to cause this event.

    This is defined as

      dot3OamErrSymPeriodThreshold =
                ((2^32) *
```

dot3OamErrSymPeriodThresholdHi)
+ dot3OamErrSymPeriodThresholdLo

If dot3OamErrSymPeriodThreshold symbol errors occur within a window of dot3OamErrSymPeriodWindow symbols, an Event Notification OAMPDU should be generated with an Errored Symbol Period Event TLV indicating that the threshold has been crossed in this window.

The default value for dot3OamErrSymPeriodThreshold is one symbol errors. If the threshold value is zero, then an Event

Notification OAMPDU is sent periodically (at the end of every window). This can be used as an asynchronous notification to the peer OAM entity of the statistics related to this threshold crossing alarm.
"
REFERENCE "[802.3ah], 30.3.6.1.34"
::= { dot3OamEventConfigEntry 3 }

dot3OamErrSymPeriodThresholdLo OBJECT-TYPE
SYNTAX Unsigned32
UNITS "symbols"
MAX-ACCESS read-write
STATUS
current
DESCRIPTION
"The two objects dot3OamErrSymPeriodThresholdHi and dot3OamErrSymPeriodThresholdLo together form an unsigned 64-bit integer representing the number of symbol errors that must occur within a given window to cause this event.

This is defined as

dot3OamErrSymPeriodThreshold =
((2^32) * dot3OamErrSymPeriodThresholdHi)
+ dot3OamErrSymPeriodThresholdLo

If dot3OamErrSymPeriodThreshold symbol errors occur within a window of dot3OamErrSymPeriodWindow symbols, an Event Notification OAMPDU should be generated with an Errored Symbol Period Event TLV indicating that the threshold has been crossed in this window.

The default value for dot3OamErrSymPeriodThreshold is one symbol error. If the threshold value is zero, then an Event

```
    Notification OAMPDU is sent periodically (at the end of every
    window).  This
can be used as an asynchronous notification to
    the peer OAM entity of the statistics related to this
    threshold crossing alarm.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.34"
  ::= { dot3OamEventConfigEntry 4 }

 dot3OamErrSymPeriodEvNotifEnable OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "If true, the OAM entity should send an Event Notification
    OAMPDU when an Errored Symbol Period Event occurs.




    By default, this object should have the value true for
    Ethernet-like interfaces that support OAM.  If the OAM layer
    does not support Event Notifications (as indicated via the
    dot3OamFunctionsSupported attribute), this value is ignored.
    "
  ::= { dot3OamEventConfigEntry 5 }

 dot3OamErrFramePeriodWindow OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "frames"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "The
number of frames over which the threshold is defined.
    The default value of the window is the number of minimum size
    Ethernet frames that can be received over the physical layer
    in one second.

    If dot3OamErrFramePeriodThreshold frame errors occur within a
    window of dot3OamErrFramePeriodWindow frames, an Event
    Notification OAMPDU should be generated with an Errored Frame
    Period Event TLV indicating that the threshold has been
    crossed in this window.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.38"
  ::= { dot3OamEventConfigEntry 6 }
```

```
 dot3OamErrFramePeriodThreshold OBJECT-TYPE
   SYNTAX      Unsigned32
   UNITS       "frames"
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION
     "The number of frame errors that must occur for this event to
     be triggered.  The default value is one frame error.  If the
     threshold value is zero, then an Event Notification OAMPDU is
     sent periodically
(at the end of every window).  This can be
     used as an asynchronous notification to the peer OAM entity of
     the statistics related to this threshold crossing alarm.

     If dot3OamErrFramePeriodThreshold frame errors occur within a
     window of dot3OamErrFramePeriodWindow frames, an Event
     Notification OAMPDU should be generated with an Errored Frame
     Period Event TLV indicating that the threshold has been
     crossed in this window.
     "
   REFERENCE   "[802.3ah], 30.3.6.1.38"



   ::= { dot3OamEventConfigEntry 7 }

 dot3OamErrFramePeriodEvNotifEnable OBJECT-TYPE
   SYNTAX      TruthValue
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION
     "If true, the OAM entity should send an Event Notification
     OAMPDU when an Errored Frame Period Event occurs.

     By default, this object should have the value true for
     Ethernet-like interfaces that support OAM.  If the OAM layer
     does not support Event Notifications
(as indicated via the
     dot3OamFunctionsSupported attribute), this value is ignored.
     "
   ::= { dot3OamEventConfigEntry 8 }

 dot3OamErrFrameWindow OBJECT-TYPE
   SYNTAX      Unsigned32
   UNITS       "tenths of a second"
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION
```

"The amount of time (in 100ms increments) over which the
threshold is defined. The default value is 10 (1 second).

If dot3OamErrFrameThreshold frame errors occur within a window
of dot3OamErrFrameWindow seconds (measured in tenths of
seconds), an Event Notification OAMPDU should be generated
with an Errored Frame Event TLV indicating that the threshold
has been crossed in this window.
"
REFERENCE "[802.3ah], 30.3.6.1.36"
DEFVAL { 10 }
::= { dot3OamEventConfigEntry 9 }

dot3OamErrFrameThreshold OBJECT-TYPE
SYNTAX Unsigned32
UNITS "frames"
MAX-ACCESS read-write

STATUS current
DESCRIPTION
"The number of frame errors that must occur for this event to
be triggered. The default value is one frame error. If the
threshold value is zero, then an Event Notification OAMPDU is
sent periodically (at the end of every window). This can be
used as an asynchronous notification to the peer OAM entity of
the statistics related to this threshold crossing alarm.

If dot3OamErrFrameThreshold frame errors occur within a window
of dot3OamErrFrameWindow (in tenths of seconds), an Event
Notification OAMPDU should be generated with an Errored Frame
Event TLV indicating the threshold has been crossed in this
window.
"
REFERENCE "[802.3ah], 30.3.6.1.36"
DEFVAL { 1 }
::= { dot3OamEventConfigEntry 10 }

dot3OamErrFrameEvNotifEnable OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"If true,
the OAM entity should send an Event Notification
OAMPDU when an Errored Frame Event occurs.

```
    By default, this object should have the value true for
    Ethernet-like interfaces that support OAM.  If the OAM layer
    does not support Event Notifications (as indicated via the
    dot3OamFunctionsSupported attribute), this value is ignored.
    "
  DEFVAL { true }
  ::= { dot3OamEventConfigEntry 11 }

 dot3OamErrFrameSecsSummaryWindow OBJECT-TYPE
  SYNTAX      Integer32 (100..9000)
  UNITS       "tenths of a second"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "The amount of time (in 100 ms intervals) over which the
    threshold is defined.  The default value is 100 (10 seconds).

    If dot3OamErrFrameSecsSummaryThreshold frame errors occur
    within a window of dot3OamErrFrameSecsSummaryWindow (in tenths
    of seconds), an Event Notification OAMPDU should be generated
    with an Errored Frame
Seconds Summary Event TLV indicating
    that the threshold has been crossed in this window.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.40"
  DEFVAL { 100 }
  ::= { dot3OamEventConfigEntry 12 }

 dot3OamErrFrameSecsSummaryThreshold OBJECT-TYPE
  SYNTAX      Integer32 (1..900)



  UNITS       "errored frame seconds"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "The number of errored frame seconds that must occur for this
    event to be triggered.  The default value is one errored frame
    second.  If the threshold value is zero, then an Event
    Notification OAMPDU is sent periodically (at the end of every
    window).  This can be used as an asynchronous notification to
    the peer OAM entity of the statistics related to this
    threshold crossing alarm.

    If dot3OamErrFrameSecsSummaryThreshold frame errors occur
    within a window of dot3OamErrFrameSecsSummaryWindow (in tenths
```

```
    of seconds),
an Event Notification OAMPDU should be generated
    with an Errored Frame Seconds Summary Event TLV indicating
    that the threshold has been crossed in this window.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.40"
  DEFVAL { 1 }
  ::= { dot3OamEventConfigEntry 13 }

 dot3OamErrFrameSecsEvNotifEnable OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "If true, the local OAM entity should send an Event
    Notification OAMPDU when an Errored Frame Seconds Event
    occurs.

    By default, this object should have the value true for
    Ethernet-like interfaces that support OAM.  If the OAM layer
    does not support Event Notifications (as indicated via the
    dot3OamFunctionsSupported attribute), this value is ignored.
    "
  DEFVAL { true }
  ::= { dot3OamEventConfigEntry 14 }

 dot3OamDyingGaspEnable OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-write

  STATUS      current
  DESCRIPTION
    "If true, the local OAM entity should attempt to indicate a
    dying gasp via the OAMPDU flags field to its peer OAM entity
    when a dying gasp event occurs.  The exact definition of a
    dying gasp event is implementation dependent.  If the system




    does not support dying gasp capability, setting this object
    has no effect, and reading the object should always result in
    'false'.

    By default, this object should have the value true for
    Ethernet-like interfaces that support OAM.  If the OAM layer
    does not support Event Notifications (as indicated via the
    dot3OamFunctionsSupported attribute), this value is ignored.
    "
```

```
  DEFVAL { true }
  ::= { dot3OamEventConfigEntry 15 }

 dot3OamCriticalEventEnable OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
    "If true, the local OAM entity should attempt to indicate
a
    critical event via the OAMPDU flags to its peer OAM entity
    when a critical event occurs.  The exact definition of a
    critical event is implementation dependent.  If the system
    does not support critical event capability, setting this
    object has no effect, and reading the object should always
    result in 'false'.

    By default, this object should have the value true for
    Ethernet-like interfaces that support OAM.  If the OAM layer
    does not support Event Notifications (as indicated via the
    dot3OamFunctionsSupported attribute), this value is ignored.
    "
  DEFVAL { true }
  ::= { dot3OamEventConfigEntry 16 }

 -- ****************************************************************
 --
 -- Ethernet OAM Event Log group
 --

 dot3OamEventLogTable OBJECT-TYPE
  SYNTAX       SEQUENCE OF Dot3OamEventLogEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
    "This table records
a history of the events that have occurred
    at the Ethernet OAM level.  These events can include locally
    detected events, which may result in locally generated
    OAMPDUs, and remotely detected events, which are detected by
    the OAM peer entity and signaled to the local entity via




    Ethernet OAM.  Ethernet OAM events can be signaled by Event
    Notification OAMPDUs or by the flags field in any OAMPDU.

    This table contains both threshold crossing events and
```

```
    non-threshold crossing events.  The parameters for the
    threshold window, threshold value, and actual value
    (dot3OamEventLogWindowXX, dot3OamEventLogThresholdXX,
    dot3OamEventLogValue) are only applicable to threshold
    crossing events, and are returned as all F's (2^32 - 1) for
    non-threshold crossing events.

    Entries in the table are automatically created when such
    events are detected.  The size of the table is implementation
    dependent.
  When the table reaches its maximum size, older
    entries are automatically deleted to make room for newer
    entries.
    "
    ::= { dot3OamObjects 6 }

  dot3OamEventLogEntry OBJECT-TYPE
   SYNTAX      Dot3OamEventLogEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
    "An entry in the dot3OamEventLogTable.  Entries are
    automatically created whenever Ethernet OAM events occur at
    the local OAM entity, and when Event Notification OAMPDUs are
    received at the local OAM entity (indicating that events have
    occurred at the peer OAM entity).  The size of the table is
    implementation dependent, but when the table becomes full,
    older events are automatically deleted to make room for newer
    events.  The table index dot3OamEventLogIndex increments for
    each new entry, and when the maximum value is reached, the
    value restarts at zero.
    "
   INDEX       { ifIndex, dot3OamEventLogIndex
  }
   ::= { dot3OamEventLogTable 1 }

  Dot3OamEventLogEntry ::=
   SEQUENCE {
    dot3OamEventLogIndex              Unsigned32,
    dot3OamEventLogTimestamp          TimeStamp,
    dot3OamEventLogOui                EightOTwoOui,
    dot3OamEventLogType               Unsigned32,
    dot3OamEventLogLocation           INTEGER,
    dot3OamEventLogWindowHi           Unsigned32,
    dot3OamEventLogWindowLo           Unsigned32,
    dot3OamEventLogThresholdHi        Unsigned32,
```

```
    dot3OamEventLogThresholdLo          Unsigned32,
    dot3OamEventLogValue                CounterBasedGauge64,
    dot3OamEventLogRunningTotal         CounterBasedGauge64,
    dot3OamEventLogEventTotal           Unsigned32
  }

dot3OamEventLogIndex       OBJECT-TYPE
  SYNTAX      Unsigned32(1..4294967295)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
    "An arbitrary integer for identifying individual events
     within the event log.  "
  ::= { dot3OamEventLogEntry 1 }

dot3OamEventLogTimestamp  OBJECT-TYPE
  SYNTAX      TimeStamp
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The value of sysUpTime at the time of the logged event.  For
    locally generated events, the time of the event can be
    accurately retrieved from sysUpTime.  For remotely generated
    events, the time of the event is indicated by the reception of
    the Event Notification OAMPDU indicating that the event
    occurred on the peer.  A system may attempt to adjust the
    timestamp value to more accurately reflect the time of the
    event at the peer OAM entity by using other information, such
    as that found in the timestamp found of the Event Notification
    TLVs, which provides an indication of the relative time
    between events at the peer entity.  "
  ::= { dot3OamEventLogEntry 2 }

dot3OamEventLogOui  OBJECT-TYPE
  SYNTAX
    EightOTwoOui
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The OUI of the entity defining the object type.  All IEEE
    802.3 defined events (as appearing in [802.3ah] except for the
    Organizationally Unique Event TLVs) use the IEEE 802.3 OUI of
    0x0180C2.  Organizations defining their own Event Notification
    TLVs include their OUI in the Event Notification TLV that
    gets reflected here.  "
  ::= { dot3OamEventLogEntry 3 }
```

```
dot3OamEventLogType      OBJECT-TYPE
  SYNTAX      Unsigned32



  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "The type of event that generated this entry in the event log.
    When the OUI is the IEEE 802.3 OUI of 0x0180C2, the following
    event types are defined:
       erroredSymbolEvent(1),
       erroredFramePeriodEvent(2),
       erroredFrameEvent(3),
       erroredFrameSecondsEvent(4),
       linkFault(256),
       dyingGaspEvent(257),
        criticalLinkEvent(258)
    The first four are considered threshold crossing events, as
    they are generated when a metric exceeds a given value within
    a specified window.  The other three are not threshold
    crossing events.

    When the OUI is not 71874 (0x0180C2 in hex), then some other
    organization has defined the event space.  If event subtyping
    is known to the implementation, it may be reflected here.
    Otherwise, this value should return all F's (2^32 - 1).
    "
  REFERENCE   "[802.3ah], 30.3.6.1.10 and 57.5.3."
  ::= { dot3OamEventLogEntry 4 }

dot3OamEventLogLocation OBJECT-TYPE
  SYNTAX      INTEGER { local(1), remote(2) }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "Whether this event occurred locally (local(1)), or was
    received from the OAM peer via Ethernet OAM (remote(2)).
    "
  ::= { dot3OamEventLogEntry 5 }

dot3OamEventLogWindowHi      OBJECT-TYPE
   SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "If the event represents a threshold crossing event, the two
    objects dot3OamEventWindowHi and dot3OamEventWindowLo, form
```

```
    an unsigned 64-bit integer yielding the window over which the
    value was measured for the threshold crossing event (for
    example, 5, when 11 occurrences happened in 5 seconds while
    the threshold was 10).  The two objects are combined as:




    dot3OamEventLogWindow = ((2^32) * dot3OamEventLogWindowHi)
                            + dot3OamEventLogWindowLo

    Otherwise, this value is returned as all F's (2^32 - 1) and
    adds no useful information.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.37 and 57.5.3.2."
  ::= { dot3OamEventLogEntry 6 }

 dot3OamEventLogWindowLo      OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "If the
event represents a threshold crossing event, the two
    objects dot3OamEventWindowHi and dot3OamEventWindowLo form an
    unsigned 64-bit integer yielding the window over which the
    value was measured for the threshold crossing event (for
    example, 5, when 11 occurrences happened in 5 seconds while
    the threshold was 10).  The two objects are combined as:

    dot3OamEventLogWindow = ((2^32) * dot3OamEventLogWindowHi)
                            + dot3OamEventLogWindowLo

    Otherwise, this value is returned as all F's (2^32 - 1) and
    adds no useful information.
    "
  REFERENCE   "[802.3ah], 30.3.6.1.37 and 57.5.3.2."
  ::= { dot3OamEventLogEntry 7 }

 dot3OamEventLogThresholdHi      OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
    "If the event represents a threshold crossing event, the two
    objects dot3OamEventThresholdHi and dot3OamEventThresholdLo
     form an unsigned 64-bit integer yielding the value that was
    crossed for the threshold crossing event (for example, 10,
```

when 11 occurrences happened in 5 seconds while the threshold
was 10). The two objects are combined as:

dot3OamEventLogThreshold = ((2^32) * dot3OamEventLogThresholdHi)
+ dot3OamEventLogThresholdLo

Otherwise, this value is returned as all F's (2^32 -1) and
adds no useful information.
"

REFERENCE "[802.3ah], 30.3.6.1.37 and 57.5.3.2."
::= { dot3OamEventLogEntry 8 }

dot3OamEventLogThresholdLo OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"If the event represents a threshold crossing event, the two
objects dot3OamEventThresholdHi and dot3OamEventThresholdLo
form an unsigned 64-bit integer yielding the value that was
crossed for the threshold crossing event (for example,
10,
when 11 occurrences happened in 5 seconds while the threshold
was 10). The two objects are combined as:

dot3OamEventLogThreshold = ((2^32) * dot3OamEventLogThresholdHi)
+ dot3OamEventLogThresholdLo

Otherwise, this value is returned as all F's (2^32 - 1) and
adds no useful information.
"
REFERENCE "[802.3ah], 30.3.6.1.37 and 57.5.3.2."
::= { dot3OamEventLogEntry 9 }

dot3OamEventLogValue OBJECT-TYPE
SYNTAX CounterBasedGauge64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"If the event represents a threshold crossing event, this
value indicates the value of the parameter within the given
window that generated this event (for example, 11, when 11
occurrences happened in 5 seconds while the threshold was 10).

Otherwise, this value is returned as all F's

(2^64 - 1) and adds no useful information.

"
REFERENCE "[802.3ah], 30.3.6.1.37 and 57.5.3.2."
::= { dot3OamEventLogEntry 10 }

dot3OamEventLogRunningTotal OBJECT-TYPE
SYNTAX CounterBasedGauge64
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Each Event Notification TLV contains a running total of the
number of times an event has occurred, as well as the number
of times an Event Notification for the event has been

transmitted. For non-threshold crossing events, the number of
events (dot3OamLogRunningTotal) and the number of resultant
Event Notifications (dot3OamLogEventTotal) should be
identical.

For threshold crossing events, since multiple occurrences may
be required to cross the threshold, these values are likely
different. This value represents the total number of times
this event has happened since the last reset (for example,
3253, when 3253 symbol errors have occurred since the last
reset, which has resulted in 51 symbol error threshold
crossing events since the last reset).
"
REFERENCE "[802.3ah], 30.3.6.1.37 and 57.5.3.2."
::= { dot3OamEventLogEntry 11 }

dot3OamEventLogEventTotal OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"Each Event Notification TLV contains a running total of the
number of times an event has occurred, as well as the number
of times an Event Notification for the event has been
transmitted. For non-threshold crossing events, the number of
events (dot3OamLogRunningTotal) and the number of resultant
Event Notifications (dot3OamLogEventTotal) should be
identical.

For threshold crossing events, since multiple occurrences may
be required to cross the threshold, these values are likely

```
    different.  This value represents the total number of times
    one or more of these
occurrences have resulted in an Event
    Notification (for example, 51 when 3253 symbol errors have
    occurred since the last reset, which has resulted in 51 symbol
    error threshold crossing events since the last reset).
    "
  REFERENCE   "[802.3ah], 30.3.6.1.37 and 57.5.3.2."
  ::= { dot3OamEventLogEntry 12 }

 -- ****************************************************************
 --
 -- Ethernet OAM Notifications
 --

 dot3OamThresholdEvent NOTIFICATION-TYPE
  OBJECTS { dot3OamEventLogTimestamp,
            dot3OamEventLogOui,



            dot3OamEventLogType,
            dot3OamEventLogLocation,
            dot3OamEventLogWindowHi,
            dot3OamEventLogWindowLo,
            dot3OamEventLogThresholdHi,
            dot3OamEventLogThresholdLo,
            dot3OamEventLogValue,
            dot3OamEventLogRunningTotal,
            dot3OamEventLogEventTotal
          }
  STATUS  current
  DESCRIPTION

 "A dot3OamThresholdEvent notification is sent when a local or
    remote threshold crossing event is detected.  A local
    threshold crossing event is detected by the local entity,
    while a remote threshold crossing event is detected by the
    reception of an Ethernet OAM Event Notification OAMPDU
    that indicates a threshold event.

    This notification should not be sent more than once per
    second.

    The OAM entity can be derived from extracting the ifIndex from
    the variable bindings.  The objects in the notification
    correspond to the values in a row instance in the
    dot3OamEventLogTable.
```

```
    The management entity should periodically check
    dot3OamEventLogTable to detect any missed events."
  ::= { dot3OamNotifications 1 }

 dot3OamNonThresholdEvent NOTIFICATION-TYPE
   OBJECTS { dot3OamEventLogTimestamp,
             dot3OamEventLogOui,
             dot3OamEventLogType,
             dot3OamEventLogLocation,
              dot3OamEventLogEventTotal
            }
   STATUS  current
   DESCRIPTION
    "A dot3OamNonThresholdEvent notification is sent when a local
    or remote non-threshold crossing event is detected.  A local
    event is detected by the local entity, while a remote event is
    detected by the reception of an Ethernet OAM Event
    Notification OAMPDU that indicates a non-threshold crossing
    event.

    This notification should not be sent more than once per




    second.

    The OAM entity can be derived from extracting the ifIndex from
    the variable bindings.  The objects in the notification
    correspond to the values in a row instance of the
    dot3OamEventLogTable.

    The management entity should periodically check
    dot3OamEventLogTable to detect any missed events."
  ::= { dot3OamNotifications 2 }

 -- ****************************************************************
 --
 -- Ethernet OAM Compliance
group
 --

 dot3OamGroups OBJECT IDENTIFIER ::= { dot3OamConformance 1 }
 dot3OamCompliances OBJECT IDENTIFIER ::= { dot3OamConformance 2 }

 -- Compliance statements

 dot3OamCompliance MODULE-COMPLIANCE
```

```
 STATUS         current
 DESCRIPTION "The compliance statement for managed entities
             supporting OAM on Ethernet-like interfaces.
             "
MODULE   -- this module
 MANDATORY-GROUPS { dot3OamControlGroup,
                    dot3OamPeerGroup,
                    dot3OamStatsBaseGroup
                  }

 GROUP       dot3OamLoopbackGroup
 DESCRIPTION
   "This group is mandatory for all IEEE 802.3 OA
   implementations that support loopback functionality. "

 GROUP       dot3OamErrSymbolPeriodEventGroup
 DESCRIPTION
   "This group is mandatory for all IEEE 802.3 OA
   implementations that support event functionality. "

 GROUP       dot3OamErrFramePeriodEventGroup
 DESCRIPTION

  "This group is mandatory for all IEEE 802.3 OA
   implementations that support event functionality. "

 GROUP       dot3OamErrFrameEventGroup



 DESCRIPTION
   "This group is mandatory for all IEEE 802.3 OA
   implementations that support event functionality. "

 GROUP       dot3OamErrFrameSecsSummaryEventGroup
 DESCRIPTION
   "This group is mandatory for all IEEE 802.3 OA
   implementations that support event functionality. "

 GROUP        dot3OamFlagEventGroup
 DESCRIPTION
   "This group is optional for all IEEE 802.3 OA
   implementations.  The ability to send critical events or dying
   gasp events is not required in any system."

 GROUP       dot3OamEventLogGroup
 DESCRIPTION
   "This group is optional for all IEEE 802.3 OA
```

```
    implementations.  Entries in this table are dependent on what
    event functionality is supported in the local OA
    implementation.  At least one type of event must be supported
     for entries to appear in this table.  "

  GROUP       dot3OamNotificationGroup
  DESCRIPTION
    "This group is optional for all IEEE 802.3 OA
    implementations.  Since the information in the notifications
    is dependent on the dot3OamEventLogTable, that table must be
    implemented for notifications.  "

  ::= { dot3OamCompliances 1}

dot3OamControlGroup OBJECT-GROUP
  OBJECTS     {   dot3OamAdminState,
                  dot3OamOperStatus,
                  dot3OamMode,
                  dot3OamMaxOamPduSize,
                  dot3OamConfigRevision,
                  dot3OamFunctionsSupported
                }
  STATUS      current
  DESCRIPTION
    "A collection of objects providing the abilities,
    configuration, and status of an Ethernet OAM entity.  "
  ::= { dot3OamGroups 1 }

dot3OamPeerGroup OBJECT-GROUP
  OBJECTS     {   dot3OamPeerMacAddress,




                  dot3OamPeerVendorOui,

                 dot3OamPeerVendorInfo,
                  dot3OamPeerMode,
                  dot3OamPeerFunctionsSupported,
                  dot3OamPeerMaxOamPduSize,
                  dot3OamPeerConfigRevision
                }
  STATUS      current
  DESCRIPTION
    "A collection of objects providing the abilities,
    configuration, and status of a peer Ethernet OAM entity.  "
  ::= { dot3OamGroups 2 }

dot3OamStatsBaseGroup OBJECT-GROUP
```

```
  OBJECTS     {   dot3OamInformationTx,
                  dot3OamInformationRx,
                  dot3OamUniqueEventNotificationTx,
                  dot3OamUniqueEventNotificationRx,
                  dot3OamDuplicateEventNotificationTx,
                  dot3OamDuplicateEventNotificationRx,
                  dot3OamLoopbackControlTx,
                  dot3OamLoopbackControlRx,
                  dot3OamVariableRequestTx,
                  dot3OamVariableRequestRx,
                  dot3OamVariableResponseTx,
                   dot3OamVariableResponseRx,
                  dot3OamOrgSpecificTx,
                  dot3OamOrgSpecificRx,
                  dot3OamUnsupportedCodesTx,
                  dot3OamUnsupportedCodesRx,
                  dot3OamFramesLostDueToOam
              }
  STATUS      current
  DESCRIPTION
    "A collection of objects providing the statistics for the
    number of various transmit and receive events for OAM on an
    Ethernet-like interface.  Note that all of these counters must
    be supported even if the related function (as described in
    dot3OamFunctionsSupported) is not supported.  "
  ::= { dot3OamGroups 3 }

dot3OamLoopbackGroup OBJECT-GROUP
  OBJECTS     {   dot3OamLoopbackStatus,
                  dot3OamLoopbackIgnoreRx
              }
  STATUS      current
  DESCRIPTION
    "A collection of objects for controlling the OAM remote




    loopback function.  "

::= { dot3OamGroups 4 }

dot3OamErrSymbolPeriodEventGroup OBJECT-GROUP
  OBJECTS     {   dot3OamErrSymPeriodWindowHi,
                  dot3OamErrSymPeriodWindowLo,
                  dot3OamErrSymPeriodThresholdHi,
                  dot3OamErrSymPeriodThresholdLo,
                  dot3OamErrSymPeriodEvNotifEnable
              }
```

```
  STATUS      current
  DESCRIPTION
    "A collection of objects for configuring the thresholds for an
    Errored Symbol Period Event.

    Each [802.3ah] defined Event Notification TLV has its own
    conformance group because each event can be implemented
    independently of any other.  "
  ::= { dot3OamGroups 5 }

dot3OamErrFramePeriodEventGroup OBJECT-GROUP
  OBJECTS     {   dot3OamErrFramePeriodWindow,
                  dot3OamErrFramePeriodThreshold,
                  dot3OamErrFramePeriodEvNotifEnable
              }
  STATUS      current
  DESCRIPTION
    "A collection of objects for
configuring the thresholds for an
    Errored Frame Period Event.

    Each [802.3ah] defined Event Notification TLV has its own
    conformance group because each event can be implemented
    independently of any other.  "
  ::= { dot3OamGroups 6 }

dot3OamErrFrameEventGroup OBJECT-GROUP
  OBJECTS     {   dot3OamErrFrameWindow,
                  dot3OamErrFrameThreshold,
                  dot3OamErrFrameEvNotifEnable
              }
  STATUS      current
  DESCRIPTION
    "A collection of objects for configuring the thresholds for an
    Errored Frame Event.

    Each [802.3ah] defined Event Notification TLV has its own
    conformance group because each event can be implemented
    independently of any other.  "



  ::= { dot3OamGroups 7 }

dot3OamErrFrameSecsSummaryEventGroup OBJECT-GROUP
  OBJECTS     {   dot3OamErrFrameSecsSummaryWindow,
                  dot3OamErrFrameSecsSummaryThreshold,
                  dot3OamErrFrameSecsEvNotifEnable
```

```
            }
  STATUS      current
  DESCRIPTION
    "A collection of objects for configuring the thresholds for an
    Errored Frame Seconds Summary Event.

    Each [802.3ah] defined Event Notification TLV has its own
    conformance group because each event can be implemented
    independently of any other.  "
  ::= { dot3OamGroups 8 }

dot3OamFlagEventGroup OBJECT-GROUP
  OBJECTS     {   dot3OamDyingGaspEnable,
                  dot3OamCriticalEventEnable
              }
  STATUS      current
  DESCRIPTION
    "A collection of objects for configuring the sending OAMPDUs
    with the critical event flag or dying gasp flag enabled.  "
  ::= { dot3OamGroups 9 }

dot3OamEventLogGroup OBJECT-GROUP
  OBJECTS {  dot3OamEventLogTimestamp,
             dot3OamEventLogOui,
             dot3OamEventLogType,
             dot3OamEventLogLocation,
             dot3OamEventLogWindowHi,
             dot3OamEventLogWindowLo,
              dot3OamEventLogThresholdHi,
             dot3OamEventLogThresholdLo,
             dot3OamEventLogValue,
             dot3OamEventLogRunningTotal,
             dot3OamEventLogEventTotal
           }
  STATUS      current
  DESCRIPTION
    "A collection of objects for configuring the thresholds for an
    Errored Frame Seconds Summary Event and maintaining the event
    information.  "
  ::= { dot3OamGroups 10 }

dot3OamNotificationGroup NOTIFICATION-GROUP



  NOTIFICATIONS {
             dot3OamThresholdEvent,
             dot3OamNonThresholdEvent
```

```
            }
  STATUS      current
  DESCRIPTION
    "A collection of notifications used by Ethernet OAM to signal
    to a management entity that local or remote events have
    occurred on a specified Ethernet link. "
  ::= { dot3OamGroups 11 }

 END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/DOT3-OAM-MIB
No license file was found, but licenses were detected in source scan.

```
SYSAPPL-MIB DEFINITIONS ::= BEGIN

 IMPORTS
    MODULE-IDENTITY, OBJECT-TYPE,
    Unsigned32, TimeTicks, Counter32, Gauge32
       FROM SNMPv2-SMI
    DateAndTime, TEXTUAL-CONVENTION
       FROM SNMPv2-TC
    MODULE-COMPLIANCE, OBJECT-GROUP
       FROM SNMPv2-CONF
    mib-2 FROM SNMPv2-SMI;

 -- System Application MIB

 sysApplMIB MODULE-IDENTITY
    LAST-UPDATED "9710200000Z"
    ORGANIZATION "IETF Applications MIB Working Group"
    CONTACT-INFO
         "Cheryl Krupczak (Editor, WG Advisor)
          Postal: Empire Technologies, Inc.
          541 Tenth Street NW
          Suite 169
          Atlanta, GA 30318
          USA
          Phone: (770) 384-0184
          Email: cheryl@empiretech.com

          Jon Saperia (WG Chair)
          Postal:  BGS Systems, Inc.
          One First Avenue
          Waltham, MA 02254-9111
          USA
```

```
 Phone: (617) 891-0000
         Email: saperia@networks.bgs.com"
    DESCRIPTION
        "The MIB module defines management objects that model
        applications as collections of executables and files
        installed and executing on a host system.  The MIB
        presents a system-level view of applications; i.e.,
        objects in this MIB are limited to those attributes
        that can typically be obtained from the system itself
        without adding special instrumentation to the applications."
    ::= { mib-2 54  }


sysApplOBJ              OBJECT IDENTIFIER ::= { sysApplMIB 1 }
sysApplInstalled        OBJECT IDENTIFIER ::= { sysApplOBJ 1 }
sysApplRun              OBJECT IDENTIFIER ::= { sysApplOBJ 2 }
sysApplMap              OBJECT IDENTIFIER ::= { sysApplOBJ 3 }
sysApplNotifications    OBJECT IDENTIFIER ::= { sysApplMIB 2 }
sysApplConformance      OBJECT IDENTIFIER ::= { sysApplMIB 3 }

-- Textual Conventions

RunState ::= TEXTUAL-CONVENTION
     STATUS      current
    DESCRIPTION
        "This TC describes the current execution state of
        a running application or process.  The possible
        values are:
          running(1),
          runnable(2),  - waiting for a resource (CPU, etc.)
          waiting(3),   - waiting for an event
          exiting(4),
          other(5)      - other invalid state"
    SYNTAX      INTEGER {
                running (1),
                runnable (2), -- waiting for resource (CPU, etc.)
                waiting (3),  -- waiting for event
                exiting (4),
                other (5)     -- other invalid state
                }

LongUtf8String ::= TEXTUAL-CONVENTION
      DISPLAY-HINT "1024a"
      STATUS  current
      DESCRIPTION
            "To facilitate internationalization, this TC
            represents information taken from the ISO/IEC IS
            10646-1 character set, encoded as an octet string
```

```
            using the UTF-8 character encoding scheme described
            in RFC 2044 [10].  For strings in 7-bit US-ASCII,
            there is no impact since the UTF-8 representation
            is identical to the US-ASCII encoding."
        SYNTAX  OCTET STRING (SIZE (0..1024))

Utf8String ::= TEXTUAL-CONVENTION
        DISPLAY-HINT "255a"
        STATUS  current
        DESCRIPTION
            "To facilitate internationalization, this TC
            represents information taken from the ISO/IEC IS
            10646-1 character set, encoded as an octet string
            using the UTF-8 character encoding scheme described
            in RFC 2044 [10].  For strings in 7-bit US-ASCII,
            there is no impact since the UTF-8 representation
            is identical to the US-ASCII encoding."
        SYNTAX  OCTET STRING (SIZE (0..255))



-- sysApplInstalled Group
-- This group provides information about application
packages
-- that have been installed on the host computer.  The group
-- contains two tables.  The first, the sysApplInstallPkgTable,
-- describes the application packages, the second, the
-- sysApplInstallElmtTable, describes the constituent elements
-- (files and executables) which compose an application package.

--
-- In order to appear in this group, an application and its
-- component files must be discoverable by the system itself,
-- possibly through some type of software installation mechanism
-- or registry.

-- sysApplInstallPkgTable
-- The system installed application packages table provides
-- information on the software packages installed on a system.
-- These packages may consist of many different files including
-- executable and non-executable files.

sysApplInstallPkgTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF SysApplInstallPkgEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The table listing
```

```
the software application packages
        installed on a host computer. In order to appear in
        this table, it may be necessary for the application
        to be installed using some type of software
        installation mechanism or global registry so that its
        existence can be detected by the agent implementation."

    ::= { sysApplInstalled 1 }

sysApplInstallPkgEntry OBJECT-TYPE
    SYNTAX      SysApplInstallPkgEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The logical row describing an installed application
        package."
    INDEX    { sysApplInstallPkgIndex }
    ::= { sysApplInstallPkgTable 1 }

SysApplInstallPkgEntry ::= SEQUENCE {
    sysApplInstallPkgIndex              Unsigned32,
    sysApplInstallPkgManufacturer       Utf8String,
    sysApplInstallPkgProductName        Utf8String,
    sysApplInstallPkgVersion            Utf8String,
    sysApplInstallPkgSerialNumber
     Utf8String,
    sysApplInstallPkgDate               DateAndTime,
    sysApplInstallPkgLocation           LongUtf8String
}

sysApplInstallPkgIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..'ffffffff'h)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An integer used only for indexing purposes.
        Generally monotonically increasing from 1 as new
        applications are installed.

        The value for each installed application must
        remain constant at least from one re-initialization of
        the network management entity which implements this
        MIB module to the next re-initialization.

        The specific value is meaningful only within a given SNMP
        entity. A sysApplInstallPkgIndex value must not be re-used
        until the next agent entity restart in the event the
        installed application entry is deleted."
```

```
    ::= { sysApplInstallPkgEntry 1 }

sysApplInstallPkgManufacturer
OBJECT-TYPE
    SYNTAX      Utf8String
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The Manufacturer of the software application package."
    ::= { sysApplInstallPkgEntry 2 }

sysApplInstallPkgProductName OBJECT-TYPE
    SYNTAX      Utf8String
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The name assigned to the software application package
        by the Manufacturer."
    ::= { sysApplInstallPkgEntry 3 }

sysApplInstallPkgVersion OBJECT-TYPE
    SYNTAX      Utf8String
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The version number assigned to the application package
        by the manufacturer of the software."
    ::= { sysApplInstallPkgEntry 4 }

sysApplInstallPkgSerialNumber OBJECT-TYPE
    SYNTAX      Utf8String
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The serial number of the software assigned
by the
        manufacturer."
    ::= { sysApplInstallPkgEntry 5 }

sysApplInstallPkgDate OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The date and time this software application was installed
        on the host."
    ::= { sysApplInstallPkgEntry 6 }
```

```
sysApplInstallPkgLocation OBJECT-TYPE
   SYNTAX      LongUtf8String
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The complete path name where the application package
      is installed.  For example, the value would be
      '/opt/MyapplDir' if the application package was installed
      in the /opt/MyapplDir directory."
   ::= { sysApplInstallPkgEntry 7 }


-- sysApplInstallElmtTable
-- The table describing the individual application package
-- elements (files and executables) installed on the host computer.

sysApplInstallElmtTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF SysApplInstallElmtEntry
    MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "This table details the individual application package
      elements (files and executables) which comprise the
      applications defined in the sysApplInstallPkg Table.
      Each entry in this table has an index to the
      sysApplInstallPkg table to identify the application
      package of which it is a part. As a result, there may
      be many entries in this table for each instance in the
      sysApplInstallPkg Table.

      Table entries are indexed by sysApplInstallPkgIndex,
      sysApplInstallElmtIndex to facilitate retrieval of
      all elements associated with a particular installed
      application package."
   ::= { sysApplInstalled 2 }

sysApplInstallElmtEntry OBJECT-TYPE
   SYNTAX      SysApplInstallElmtEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "The logical row
describing an element of an installed
      application.  The element may be an executable or
      non-executable file."
   INDEX    {sysApplInstallPkgIndex, sysApplInstallElmtIndex}
   ::= { sysApplInstallElmtTable 1 }
```

```
SysApplInstallElmtEntry ::= SEQUENCE {
   sysApplInstallElmtIndex              Unsigned32,
   sysApplInstallElmtName               Utf8String,
   sysApplInstallElmtType               INTEGER,
   sysApplInstallElmtDate               DateAndTime,
   sysApplInstallElmtPath               LongUtf8String,
   sysApplInstallElmtSizeHigh           Unsigned32,
   sysApplInstallElmtSizeLow            Unsigned32,
   sysApplInstallElmtRole               BITS,
   sysApplInstallElmtModifyDate         DateAndTime,
   sysApplInstallElmtCurSizeHigh        Unsigned32,
   sysApplInstallElmtCurSizeLow         Unsigned32

}

sysApplInstallElmtIndex OBJECT-TYPE
   SYNTAX      Unsigned32 (1..'ffffffff'h)
    MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "An arbitrary integer used for indexing.  The value
      of this index is unique among all rows in this table
      that exist or have existed since the last agent restart."
   ::= { sysApplInstallElmtEntry 1 }


sysApplInstallElmtName OBJECT-TYPE
   SYNTAX      Utf8String
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The name of this element which is contained in the
      application."
   ::= { sysApplInstallElmtEntry 2 }

sysApplInstallElmtType OBJECT-TYPE
   SYNTAX      INTEGER {
               unknown(1),
               nonexecutable(2),
               operatingSystem(3),  -- executable
               deviceDriver(4),     -- executable
               application(5)       -- executable
               }
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "The type of element that is
```

```
part of the installed
        application."
    ::= { sysApplInstallElmtEntry 3 }

sysApplInstallElmtDate OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The date and time that this component was installed on
        the system."
    ::= { sysApplInstallElmtEntry 4 }

sysApplInstallElmtPath OBJECT-TYPE
    SYNTAX      LongUtf8String
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The full directory path where this element is installed.
        For example, the value would be '/opt/EMPuma/bin' for an
        element installed in the directory '/opt/EMPuma/bin'.
        Most application packages include information about the
        elements contained in the package. In addition, elements
        are typically installed in sub-directories under the
        package installation directory.  In cases where the
        element path names are not included
in the package
        information itself, the path can usually be determined
        by a simple search of the sub-directories.  If the
        element is not installed in that location and there is
        no other information available to the agent implementation,
        then the path is unknown and null is returned."
    ::= { sysApplInstallElmtEntry 5}

sysApplInstallElmtSizeHigh OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The installed file size in 2^32 byte blocks. This is
        the size of the file on disk immediately after installation.

        For example, for a file with a total size of 4,294,967,296
        bytes, this variable would have a value of 1; for a file
        with a total size of 4,294,967,295 bytes this variable
        would be 0."
    ::= { sysApplInstallElmtEntry 6 }
```

```
sysApplInstallElmtSizeLow OBJECT-TYPE
   SYNTAX      Unsigned32
   MAX-ACCESS
 read-only
   STATUS      current
   DESCRIPTION
      "The installed file size modulo 2^32 bytes.  This is
      the size of the file on disk immediately after installation.

      For example, for a file with a total size of 4,294,967,296
      bytes this variable would have a value of 0; for a file with
      a total size of 4,294,967,295 bytes this variable would be
      4,294,967,295."
   ::= { sysApplInstallElmtEntry 7 }

sysApplInstallElmtRole  OBJECT-TYPE
   SYNTAX      BITS {
            executable(0),
              -- An application may have one or
              -- more executable elements.  The rest of the
              -- bits have no meaning if the element is not
              -- executable.
            exclusive(1),
              -- Only one copy of an exclusive element may be
              -- running per invocation of the running
              -- application.

        primary(2),
              -- The primary executable.  An application can
              -- have one, and only one element that is designated
              -- as the primary executable.  The execution of
              -- this element constitutes an invocation of
              -- the application.  This is used by the agent
              -- implementation to determine the initiation of
              -- an application.  The primary executable must
              -- remain running long enough for the agent
              -- implementation to detect its presence.
            required(3),
              -- An application may have zero or more required
              -- elements. All required elements must be running

              -- in order for the application to be judged to be
              -- running and healthy.
            dependent(4),
              -- An application may have
zero or more
              -- dependent elements. Dependent elements may
              -- not be running unless required elements are.
```

unknown(5)
-- Default value for the case when an operator
-- has not yet assigned one of the other values.
-- When set, bits 1, 2, 3, and 4 have no meaning.
}
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"An operator assigned value used in the determination of application status. This value is used by the agent to determine both the mapping of started processes to the initiation of an application, as well as to allow for a determination of application health. The default value, unknown(5), is used when an operator has not yet assigned one of the other values. If unknown(5) is set, bits 1 - 4 have no meaning. The possible values are:

executable(0),
An application may have one or more executable elements. The rest of the bits have no meaning if the element is not executable.
exclusive(1),
Only one copy of an exclusive element may be running per invocation of the running application.
primary(2),
The primary executable. An application can have one, and only one element that is designated as the primary executable. The execution of this element constitutes an invocation of the application. This is used by the agent implementation to determine the initiation of an application. The primary executable must remain running long enough for
the agent
implementation to detect its presence.
required(3),
An application may have zero or more required elements. All required elements must be running in order for the application to be judged to be running and healthy.
dependent(4),
An application may have zero or more dependent elements. Dependent elements may not be running unless required elements are.
unknown(5)
Default value for the case when an operator

has not yet assigned one of the other values.
When set, bits 1, 2, 3, and 4 have no meaning.

sysApplInstallElmtRole is used by the agent implementation
in determining the initiation of an application, the
current state of a running application (see
sysApplRunCurrentState), when an application invocation is
no longer running, and the exit status of a terminated
application invocation (see sysApplPastRunExitState)."

DEFVAL { { unknown } }
::= { sysApplInstallElmtEntry 8 }

sysApplInstallElmtModifyDate OBJECT-TYPE
SYNTAX DateAndTime
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The date and time that this element was last modified.
Modification of the sysApplInstallElmtRole columnar
object does NOT constitute a modification of the element
itself and should not affect the value of this object."
::= { sysApplInstallElmtEntry 9 }

sysApplInstallElmtCurSizeHigh OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The current file size in 2^32 byte blocks.
For example, for a file with a total size of 4,294,967,296
bytes,
this variable would have a value of 1; for a file
with a total size of 4,294,967,295 bytes this variable
would be 0."
::= { sysApplInstallElmtEntry 10 }

sysApplInstallElmtCurSizeLow OBJECT-TYPE
SYNTAX Unsigned32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The current file size modulo 2^32 bytes.
For example, for a file with a total size of 4,294,967,296
bytes this variable would have a value of 0; for a file with
a total size of 4,294,967,295 bytes this variable would be
4,294,967,295."
::= { sysApplInstallElmtEntry 11 }

```
-- sysApplRun Group
-- This group models activity information for applications
-- that have been invoked and are either currently running,
-- or have previously run on the host system.  Likewise,
-- the individual elements of an invoked application are
-- also modeled to show currently running processes, and
-- processes that
have run in the past.

-- sysApplRunTable
-- The sysApplRunTable contains the application instances
-- which are currently running on the host.  Since a single
-- application might be invoked multiple times, an entry is
-- added to this table for each INVOCATION of an application.
-- The table is indexed by sysApplInstallPkgIndex, sysApplRunIndex
-- to enable managers to easily locate all invocations of
-- a particular application package.

sysApplRunTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF SysApplRunEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "The table describes the applications which are executing
      on the host.  Each time an application is invoked,
      an entry is created in this table. When an application ends,
      the entry is removed from this table and a corresponding
            entry is created in the SysApplPastRunTable.

      A new entry is created in this table whenever
the agent
      implementation detects a new running process that is an
      installed application element whose sysApplInstallElmtRole
      designates it as being the application's primary executable
      (sysApplInstallElmtRole = primary(2) ).

      The table is indexed by sysApplInstallPkgIndex,
      sysApplRunIndex to enable managers to easily locate all
      invocations of a particular application package."
   ::= { sysApplRun 1 }

sysApplRunEntry OBJECT-TYPE
   SYNTAX      SysApplRunEntry
   MAX-ACCESS  not-accessible
   STATUS      current
```

```
    DESCRIPTION
        "The logical row describing an application which is
        currently running on this host."
    INDEX    { sysApplInstallPkgIndex, sysApplRunIndex }
    ::= { sysApplRunTable   1 }

SysApplRunEntry ::= SEQUENCE {
    sysApplRunIndex                 Unsigned32,
    sysApplRunStarted               DateAndTime,
    sysApplRunCurrentState
            RunState
}

sysApplRunIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..'ffffffff'h)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Part of the index for this table. An arbitrary
        integer used only for indexing purposes. Generally
        monotonically increasing from 1 as new applications are
        started on the host, it uniquely identifies application
        invocations.

        The numbering for this index increases by 1 for each
        INVOCATION of an application, regardless of which
        installed application package this entry represents a
        running instance of.

        An example of the indexing for a couple of entries is
        shown below.

                :
            sysApplRunStarted.17.14
            sysApplRunStarted.17.63
            sysApplRunStarted.18.13
                :

        In this example, the agent has observed 12
application
        invocations when the application represented by entry 18
        in the sysApplInstallPkgTable is invoked.  The next
        invocation detected by the agent is an invocation of
        installed application package 17.  Some time later,
        installed application 17 is invoked a second time.

        NOTE: this index is not intended to reflect a real-time
        (wall clock time) ordering of application invocations;
```

```
        it is merely intended to uniquely identify running
        instances of applications.  Although the
        sysApplInstallPkgIndex is included in the INDEX clause
        for this table, it serves only to ease searching of
        this table by installed application and does not
        contribute to uniquely identifying table entries."
    ::= { sysApplRunEntry 1 }

sysApplRunStarted OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The
date and time that the application was started."
    ::= { sysApplRunEntry 2 }

sysApplRunCurrentState OBJECT-TYPE
    SYNTAX      RunState
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The current state of the running application instance.
        The possible values are running(1), runnable(2) but waiting
        for a resource such as CPU, waiting(3) for an event,
        exiting(4), or other(5). This value is based on an evaluation
        of the running elements of this application instance (see
        sysApplElmRunState) and their Roles as defined by
        sysApplInstallElmtRole.  An agent implementation may
        detect that an application instance is in the process of
        exiting if one or more of its REQUIRED elements are no
        longer running.  Most agent implementations will wait until
        a second internal poll has been completed to give the
        system time to start REQUIRED elements before
marking the
        application instance as exiting."
    ::= { sysApplRunEntry 3 }


-- sysApplPastRunTable
-- The sysApplPastRunTable provides a history of applications
-- previously run on the host computer. Entries are removed from
-- the sysApplRunTable and corresponding entries are added to this
-- table when an application becomes inactive. Entries remain in
-- this table until they are aged out when either the table size
-- reaches a maximum as determined by the sysApplPastRunMaxRows,
-- or when an entry has aged to exceed a time limit as set be
-- sysApplPastRunTblTimeLimit.
```

```
--
-- When aging out entries, the oldest entry, as determined by

-- the value of sysApplPastRunTimeEnded, will be removed first.

sysApplPastRunTable OBJECT-TYPE
   SYNTAX      SEQUENCE OF SysApplPastRunEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
       "A history of the applications that have previously run
       on the host
computer.  An entry's information is moved to
       this table from the sysApplRunTable when the invoked
       application represented by the entry ceases to be running.

       An agent implementation can determine that an application
       invocation is no longer running by evaluating the running
       elements of the application instance and their Roles as
       defined by sysApplInstallElmtRole.  Obviously, if there
       are no running elements for the application instance,
       then the application invocation is no longer running.
       If any one of the REQUIRED elements is not running,
       the application instance may be in the process of exiting.
       Most agent implementations will wait until a second internal
       poll has been completed to give the system time to either
       restart partial failures or to give all elements time to
       exit.  If, after the second poll, there are REQUIRED
       elements that
are not running, then the application
       instance may be considered by the agent implementation
       to no longer be running.

       Entries remain in the sysApplPastRunTable until they
       are aged out when either the table size reaches a maximum
       as determined by the sysApplPastRunMaxRows, or when an entry
       has aged to exceed a time limit as set by
       sysApplPastRunTblTimeLimit.

       Entries in this table are indexed by sysApplInstallPkgIndex,
       sysApplPastRunIndex to facilitate retrieval of all past
       run invocations of a particular installed application."
   ::= { sysApplRun 2 }

sysApplPastRunEntry OBJECT-TYPE
   SYNTAX      SysApplPastRunEntry
   MAX-ACCESS  not-accessible
   STATUS      current
```

```
    DESCRIPTION
        "The logical row describing an invocation of an application
        which was previously run and has terminated.  The entry
        is basically copied from the sysApplRunTable
when the
        application instance terminates.  Hence, the entry's
        value for sysApplPastRunIndex is the same as its value was
        for sysApplRunIndex."
    INDEX    { sysApplInstallPkgIndex, sysApplPastRunIndex }
    ::= { sysApplPastRunTable   1 }

SysApplPastRunEntry ::= SEQUENCE {
    sysApplPastRunIndex                 Unsigned32,
    sysApplPastRunStarted               DateAndTime,
    sysApplPastRunExitState              INTEGER,
    sysApplPastRunTimeEnded               DateAndTime
}

sysApplPastRunIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (1..'ffffffff'h)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Part of the index for this table. An integer
        matching the value of the removed sysApplRunIndex
        corresponding to this row."
    ::= { sysApplPastRunEntry 1 }

sysApplPastRunStarted OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS
     current
    DESCRIPTION
        "The date and time that the application was started."
    ::= { sysApplPastRunEntry 2 }

sysApplPastRunExitState OBJECT-TYPE
    SYNTAX      INTEGER {
                complete (1), -- normal exit at sysApplRunTimeEnded
                failed (2),   -- abnormal exit
                other (3)
                }
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "The state of the application instance when it terminated.
       This value is based on an evaluation of the running elements
```

```
        of an application and their Roles as defined by
        sysApplInstallElmtRole.  An application instance is said to
        have exited in a COMPLETE state and its entry is removed
        from the sysApplRunTable and added to the sysApplPastRunTable
        when the agent detects that ALL elements of an application
        invocation are no longer running.  Most agent implementations
        will wait
until a second internal poll has been completed to
        give the system time to either restart partial failures or
        to give all elements time to exit.  A failed state occurs if,
        after the second poll, any elements continue to run but
        one or more of the REQUIRED elements are no longer running.
        All other combinations MUST be defined as OTHER."
    ::= { sysApplPastRunEntry 3 }

sysApplPastRunTimeEnded OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The DateAndTime the application instance was determined
        to be no longer running."
    ::= { sysApplPastRunEntry 4 }

-- sysApplElmtRunTable
-- The sysApplElmtRunTable contains an entry for each process that
-- is currently running on the host.  An entry is created in
-- this table for each process at the time it is started, and will
-- remain in the table until the process terminates.
--
-- The table
is indexed by sysApplElmtRunInstallPkg,
-- sysApplElmtRunInvocID, and sysApplElmtRunIndex to make it easy
-- to locate all running elements of a particular invoked application
-- which has been installed on the system.


sysApplElmtRunTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF SysApplElmtRunEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The table describes the processes which are
        currently executing on the host system. Each entry
        represents a running process and is associated with
        the invoked application of which that process is a part, if
        possible.  This table contains an entry for every process
        currently running on the system, regardless of whether its
```

'parent' application can be determined. So, for example,
processes like 'ps' and 'grep' will have entries though they
are not associated with an installed application package.

Because
a running application may involve
more than one executable, it is possible to have
multiple entries in this table for each application.
Entries are removed from this table when the process
terminates.
The table is indexed by sysApplElmtRunInstallPkg,
sysApplElmtRunInvocID, and sysApplElmtRunIndex to
facilitate the retrieval of all running elements of a
particular invoked application which has been installed on
the system."
::= { sysApplRun 3 }

sysApplElmtRunEntry OBJECT-TYPE
SYNTAX SysApplElmtRunEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
"The logical row describing a process currently
running on this host. When possible, the entry is
associated with the invoked application of which it
is a part."
INDEX { sysApplElmtRunInstallPkg, sysApplElmtRunInvocID,
sysApplElmtRunIndex
}
::= { sysApplElmtRunTable 1 }

SysApplElmtRunEntry ::= SEQUENCE {
sysApplElmtRunInstallPkg Unsigned32,
sysApplElmtRunInvocID Unsigned32,
sysApplElmtRunIndex Unsigned32,
sysApplElmtRunInstallID Unsigned32,
sysApplElmtRunTimeStarted DateAndTime,
sysApplElmtRunState RunState,
sysApplElmtRunName LongUtf8String,
sysApplElmtRunParameters Utf8String,
sysApplElmtRunCPU TimeTicks,
sysApplElmtRunMemory Gauge32,
sysApplElmtRunNumFiles Gauge32,
sysApplElmtRunUser Utf8String
}

sysApplElmtRunInstallPkg OBJECT-TYPE
SYNTAX Unsigned32 (0..'ffffffff'h)

```
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Part of the index for this table, this value
        identifies the installed software package for
        the application of which this process
is a part.
        Provided that the process's 'parent' application can be
        determined, the value of this object is the same
        value as the sysApplInstallPkgIndex for the
        entry in the sysApplInstallPkgTable that corresponds
        to the installed application of which this process
        is a part.

        If, however, the 'parent' application cannot be
        determined, (for example the process is not part
        of a particular installed application), the value
        for this object is then '0', signifying that this
        process cannot be related back to an application,
        and in turn, an installed software package."
    ::= { sysApplElmtRunEntry 1 }

sysApplElmtRunInvocID OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Part of the index for this table, this value
        identifies the invocation of an application of which
         this process is a part.  Provided that the 'parent'
        application can be determined, the value of this object
        is the same value as the sysApplRunIndex for the
        corresponding application invocation in the
        sysApplRunTable.

        If, however, the 'parent' application cannot be
        determined, the value for this object is then '0',
        signifying that this process cannot be related back
        to an invocation of an application in the
        sysApplRunTable."
    ::= { sysApplElmtRunEntry 2 }

sysApplElmtRunIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Part of the index for this table.  A unique value
```

```
        for each process running on the host.  Wherever
        possible, this should be the system's native, unique
        identification number."
    ::= { sysApplElmtRunEntry 3 }


sysApplElmtRunInstallID
OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The index into the sysApplInstallElmtTable. The
        value of this object is the same value as the
        sysApplInstallElmtIndex for the application element
        of which this entry represents a running instance.
        If this process cannot be associated with an installed
        executable, the value should be '0'."
    ::= { sysApplElmtRunEntry 4 }

sysApplElmtRunTimeStarted OBJECT-TYPE
    SYNTAX      DateAndTime
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The time the process was started."
    ::= { sysApplElmtRunEntry 5 }

sysApplElmtRunState OBJECT-TYPE
    SYNTAX      RunState
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The current state of the running process. The
        possible values are running(1), runnable(2) but waiting
         for a resource such as CPU, waiting(3) for an event,
        exiting(4), or other(5)."
    ::= { sysApplElmtRunEntry 6 }

sysApplElmtRunName OBJECT-TYPE
    SYNTAX      LongUtf8String
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The full path and filename of the process.
        For example, '/opt/MYYpkg/bin/myyproc' would
        be returned for process 'myyproc' whose execution
        path is '/opt/MYYpkg/bin/myyproc'."
```

```
    ::= { sysApplElmtRunEntry 7 }

sysApplElmtRunParameters OBJECT-TYPE
    SYNTAX      Utf8String
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The starting parameters for the process."
::= { sysApplElmtRunEntry 8 }

sysApplElmtRunCPU OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of centi-seconds of the total system's
        CPU resources consumed by this process.
 Note that
        on a multi-processor system, this value may
        have been incremented by more than one centi-second
        in one centi-second of real (wall clock) time."
    ::= { sysApplElmtRunEntry 9 }

sysApplElmtRunMemory OBJECT-TYPE
    SYNTAX      Gauge32
    UNITS       "Kbytes"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The total amount of real system memory measured in
        Kbytes currently allocated to this process."

    ::= { sysApplElmtRunEntry 10 }

sysApplElmtRunNumFiles OBJECT-TYPE
    SYNTAX      Gauge32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of regular files currently open by the
        process.  Transport connections (sockets)
        should NOT be included in the calculation of
        this value, nor should operating system specific
        special file types."
    ::= { sysApplElmtRunEntry 11 }

sysApplElmtRunUser OBJECT-TYPE
```

```
    SYNTAX      Utf8String
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The process owner's login name (e.g. root)."
    ::= { sysApplElmtRunEntry 12 }

-- sysApplElmtPastRunTable
-- The sysApplElmtPastRunTable maintains a history of
-- processes which have previously executed on
-- the host as part of an application. Upon termination
-- of a process, the entry representing the process is removed from
-- the sysApplElmtRunTable and a corresponding entry is created in
-- this table provided that the process was part of an
-- identifiable application.  If the process could not be associated

-- with an invoked application, no corresponding entry is created.
-- Hence, whereas the sysApplElmtRunTable contains an entry for
-- every process currently executing on the system, the
-- sysApplElmtPastRunTable only contains entries for processes
-- that previously executed as part of an invoked application.
--
-- Entries
remain in this table until they are aged out when
-- either the number of entries in the table reaches a
-- maximum as determined by sysApplElmtPastRunMaxRows, or
-- when an entry has aged to exceed a time limit as set by
-- sysApplElmtPastRunTblTimeLimit.  When aging out entries,
-- the oldest entry, as determined by the value of
-- sysApplElmtPastRunTimeEnded, will be removed first.
--
-- The table is indexed by sysApplInstallPkgIndex (from the
-- sysApplInstallPkgTable), sysApplElmtPastRunInvocID, and
-- sysApplElmtPastRunIndex to make it easy to locate all
-- previously executed processes of a particular invoked application
-- that has been installed on the system.


sysApplElmtPastRunTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF SysApplElmtPastRunEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The table describes the processes which have previously
        executed on the host system as part of an application.
         Each entry represents a process which has previously
        executed and is associated with the invoked application
        of which it was a part.  Because an invoked application
```

```
        may involve more than one executable, it is possible
        to have multiple entries in this table for
        each application invocation. Entries are added
        to this table when the corresponding process in the
        sysApplElmtRun Table terminates.

        Entries remain in this table until they are aged out when
        either the number of entries in the table reaches a
        maximum as determined by sysApplElmtPastRunMaxRows, or
        when an entry has aged to exceed a time limit as set by
        sysApplElmtPastRunTblTimeLimit.  When aging out entries,
        the oldest entry, as determined by the value of
        sysApplElmtPastRunTimeEnded, will be removed first.

        The table is indexed by sysApplInstallPkgIndex (from the
         sysApplInstallPkgTable), sysApplElmtPastRunInvocID,
        and sysApplElmtPastRunIndex to make it easy to locate all
        previously executed processes of a particular invoked
        application that has been installed on the system."
    ::= { sysApplRun 4 }

sysApplElmtPastRunEntry OBJECT-TYPE
    SYNTAX      SysApplElmtPastRunEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The logical row describing a process which was
        previously executed on this host as part of an
        installed application.  The entry is basically copied
        from the sysApplElmtRunTable when the process
        terminates.  Hence, the entry's value for
        sysApplElmtPastRunIndex is the same as its value
        was for sysApplElmtRunIndex.  Note carefully: only those
        processes which could be associated with an
        identified application are included in this table."
    INDEX    { sysApplInstallPkgIndex,
sysApplElmtPastRunInvocID,
               sysApplElmtPastRunIndex }
    ::= { sysApplElmtPastRunTable   1 }

SysApplElmtPastRunEntry ::= SEQUENCE {
    sysApplElmtPastRunInvocID          Unsigned32,
    sysApplElmtPastRunIndex            Unsigned32,
    sysApplElmtPastRunInstallID        Unsigned32,
    sysApplElmtPastRunTimeStarted      DateAndTime,
    sysApplElmtPastRunTimeEnded        DateAndTime,
    sysApplElmtPastRunName             LongUtf8String,
    sysApplElmtPastRunParameters       Utf8String,
```

```
    sysApplElmtPastRunCPU             TimeTicks,
    sysApplElmtPastRunMemory          Unsigned32,
    sysApplElmtPastRunNumFiles        Unsigned32,
    sysApplElmtPastRunUser            Utf8String
}

sysApplElmtPastRunInvocID OBJECT-TYPE
    SYNTAX      Unsigned32 (1..'ffffffff'h)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Part of the index for this table, this value
        identifies
the invocation of an application of which
        the process represented by this entry was a part.
        The value of this object is the same value as the
        sysApplRunIndex for the corresponding application
        invocation in the sysApplRunTable.  If the invoked
        application as a whole has terminated, it will be the
        same as the sysApplPastRunIndex."
    ::= { sysApplElmtPastRunEntry 1 }

sysApplElmtPastRunIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "Part of the index for this table. An integer
        assigned by the agent equal to the corresponding
        sysApplElmtRunIndex which was removed from the
        sysApplElmtRunTable and moved to this table
        when the element terminated.

        Note: entries in this table are indexed by
        sysApplElmtPastRunInvocID, sysApplElmtPastRunIndex.
        The possibility
exists, though unlikely, of a
        collision occurring by a new entry which was run
        by the same invoked application (InvocID), and
        was assigned the same process identification number
        (ElmtRunIndex) as an element which was previously
        run by the same invoked application.

        Should this situation occur, the new entry replaces
        the old entry.

        See Section: 'Implementation Issues -
        sysApplElmtPastRunTable Entry Collisions' for the
```

conditions that would have to occur in order for a
collision to occur."
::= { sysApplElmtPastRunEntry 2 }

sysApplElmtPastRunInstallID OBJECT-TYPE
SYNTAX Unsigned32 (1..'ffffffff'h)
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The index into the installed element table. The
value of this object is the same value as the
sysApplInstallElmtIndex for the application element

of which this entry represents a previously executed
process."
::= { sysApplElmtPastRunEntry 3 }

sysApplElmtPastRunTimeStarted OBJECT-TYPE
SYNTAX DateAndTime
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The time the process was started."
::= { sysApplElmtPastRunEntry 4 }

sysApplElmtPastRunTimeEnded OBJECT-TYPE
SYNTAX DateAndTime
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The time the process ended."
::= { sysApplElmtPastRunEntry 5 }

sysApplElmtPastRunName OBJECT-TYPE
SYNTAX LongUtf8String
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"The full path and filename of the process.
For example, '/opt/MYYpkg/bin/myyproc' would
be returned for process 'myyproc' whose execution
path was '/opt/MYYpkg/bin/myyproc'."
::= { sysApplElmtPastRunEntry 6 }

sysApplElmtPastRunParameters
OBJECT-TYPE
SYNTAX Utf8String

```
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The starting parameters for the process."
    ::= { sysApplElmtPastRunEntry 7 }

sysApplElmtPastRunCPU OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The last known number of centi-seconds of the total
        system's CPU resources consumed by this process.
        Note that on a multi-processor system, this value may
        increment by more than one centi-second in one
        centi-second of real (wall clock) time."
    ::= { sysApplElmtPastRunEntry 8 }

sysApplElmtPastRunMemory OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    UNITS       "Kbytes"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The last known total amount of real system memory
        measured in Kbytes allocated to this process before it

     terminated."
    ::= { sysApplElmtPastRunEntry 9 }

sysApplElmtPastRunNumFiles OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The last known number of files open by the
        process before it terminated.  Transport
        connections (sockets) should NOT be included in
        the calculation of this value."
    ::= { sysApplElmtPastRunEntry 10 }

sysApplElmtPastRunUser OBJECT-TYPE
    SYNTAX      Utf8String
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The process owner's login name (e.g. root)."
    ::= { sysApplElmtPastRunEntry 11 }
```

```
-- Additional Scalar objects to control table sizes

sysApplPastRunMaxRows OBJECT-TYPE
   SYNTAX      Unsigned32 (0..'ffffffff'h)
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION
      "The maximum number of entries allowed in the
      sysApplPastRunTable.
Once the number of rows in
      the sysApplPastRunTable reaches this value, the
      management subsystem will remove the oldest entry
      in the table to make room for the new entry to be added.
      Entries will be removed on the basis of oldest
      sysApplPastRunTimeEnded value first.

      This object may be used to control the amount of
      system resources that can used for sysApplPastRunTable
      entries. A conforming implementation should attempt
      to support the default value, however, a lesser value
      may be necessary due to implementation-dependent issues
      and resource availability."
   DEFVAL      { 500 }
   ::= { sysApplRun 5 }

sysApplPastRunTableRemItems OBJECT-TYPE
   SYNTAX      Counter32
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      "A counter of the number of entries removed from
      the sysApplPastRunTable because of table size limitations

   as set in sysApplPastRunMaxRows.  This counter is the
      number of entries the management subsystem has had to
      remove in order to make room for new entries (so as not
      to exceed the limit set by sysApplPastRunMaxRows) since
      the last initialization of the management subsystem."
   ::= { sysApplRun 6 }

sysApplPastRunTblTimeLimit OBJECT-TYPE
   SYNTAX      Unsigned32 (0..'ffffffff'h)
   UNITS       "seconds"
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION
```

```
        "The maximum time in seconds which an entry in the
         sysApplPastRunTable may exist before it is removed.
         Any entry that is older than this value will be
         removed (aged out) from the table.

         Note that an entry may be aged out prior to reaching
         this time limit if it is the oldest entry in the
         table and must be removed to make space for a new
         entry so as to not exceed sysApplPastRunMaxRows."
      DEFVAL      { 7200 }
    ::= { sysApplRun 7 }

sysApplElemPastRunMaxRows OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        "The maximum number of entries allowed in the
        sysApplElmtPastRunTable.  Once the number of rows in
        the sysApplElmtPastRunTable reaches this value,
        the management subsystem will remove the oldest entry
        to make room for the new entry to be added.  Entries
        will be removed on the basis of oldest
        sysApplElmtPastRunTimeEnded value first.
        This object may be used to control the amount of
        system resources that can used for sysApplElemPastRunTable
        entries. A conforming implementation should attempt
        to support the default value, however, a lesser value
        may be necessary due to implementation-dependent issues
        and resource availability."
    DEFVAL
    { 500 }
    ::= { sysApplRun 8 }

sysApplElemPastRunTableRemItems OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "A counter of the number of entries removed from the
        sysApplElemPastRunTable because of table size limitations
        as set in sysApplElemPastRunMaxRows.  This counter is the
        number of entries the management subsystem has had to
        remove in order to make room for new entries (so as not
        to exceed the limit set by sysApplElemPastRunMaxRows) since
        the last initialization of the management subsystem."
    ::= { sysApplRun 9 }
```

```
sysApplElemPastRunTblTimeLimit OBJECT-TYPE
   SYNTAX      Unsigned32 (0..'ffffffff'h)
   UNITS       "seconds"
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION
      "The maximum time in seconds which an entry in the
       sysApplElemPastRunTable may exist before it is removed.

      Any entry that is older than this value will be
       removed (aged out) from the table.

       Note that an entry may be aged out prior to reaching
       this time limit if it is the oldest entry in the
       table and must be removed to make space for a new
       entry so as to not exceed sysApplElemPastRunMaxRows."
   DEFVAL      { 7200 }
   ::= { sysApplRun 10 }

sysApplAgentPollInterval  OBJECT-TYPE
   SYNTAX      Unsigned32 (0..'ffffffff'h)
   UNITS       "seconds"
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION
      "The minimum interval in seconds that the management
       subsystem implementing this MIB will poll the status
       of the managed resources. Because of the non-trivial
       effort involved in polling the managed resources,
       and because the method for obtaining the status of
       the managed resources is implementation-dependent,
       a conformant implementation
may chose a lower bound
       greater than 0.

       A value of 0 indicates that there is no delay
       in the passing of information from the managed
       resources to the agent."
   DEFVAL      { 60 }
   ::= { sysApplRun 11 }



-- sysApplMap Group
-- This group contains a table, the sysApplMapTable,
-- whose sole purpose is to provide a 'backwards'
-- mapping so that, given a known sysApplElmtRunIndex
-- (process identification number), the corresponding invoked
-- application (sysApplRunIndex), installed element
```

```
-- (sysApplInstallElmtIndex), and installed application
-- package (sysApplInstallPkgIndex) can be quickly determined.
--
-- The table will contain one entry for each process
-- currently running on the system.
--
-- A backwards mapping is extremely useful since the tables
-- in this MIB module are typically indexed with the
-- installed application package (sysApplInstallPkgIndex)
-- as the primary key, and on down
as required by the
-- specific table, with the process ID number (sysApplElmtRunIndex)
-- being the least significant key.
--
-- It is expected that management applications will use
-- this mapping table by doing a 'GetNext' operation with
-- the known process ID number (sysApplElmtRunIndex) as the partial
-- instance identifier.  Assuming that there is an entry for
-- the process, the result should return a single columnar value,
-- the sysApplMapInstallPkgIndex, with the sysApplElmtRunIndex,
-- sysApplRunIndex, and sysApplInstallElmtIndex contained in the
-- instance identifier for the returned MIB object value.
--
-- NOTE: if the process can not be associated back to an
-- invoked application installed on the system, then the
-- value returned for the columnar value sysApplMapInstallPkgIndex
-- will be '0' and the instance portion of the object-identifier
-- will be the process ID number (sysApplElmtRunIndex) followed

-- by 0.0.

sysApplMapTable
OBJECT-TYPE
   SYNTAX      SEQUENCE OF SysApplMapEntry
   MAX-ACCESS  not-accessible
   STATUS      current
   DESCRIPTION
      "The sole purpose of this table is to provide a
      'backwards' mapping so that, given a known
      sysApplElmtRunIndex (process identification number),
      the corresponding invoked application (sysApplRunIndex),
      installed element (sysApplInstallElmtIndex), and
      installed application package (sysApplInstallPkgIndex)
      can be quickly determined.

      This table will contain one entry for each process
      that is currently executing on the system.
```

```
        It is expected that management applications will use
        this mapping table by doing a 'GetNext' operation with
        the known process ID number (sysApplElmtRunIndex) as the
        partial instance identifier.  Assuming that there is an
        entry for the process, the result should return a single
        columnar
value, the sysApplMapInstallPkgIndex, with the
        sysApplElmtRunIndex, sysApplRunIndex, and
        sysApplInstallElmtIndex contained in the instance identifier
        for the returned MIB object value.

        NOTE: if the process can not be associated back to an
        invoked application installed on the system, then the
        value returned for the columnar value
        sysApplMapInstallPkgIndex will be '0' and the instance
        portion of the object-identifier will be the process ID
        number (sysApplElmtRunIndex) followed by 0.0."
    ::= { sysApplMap 1 }

sysApplMapEntry OBJECT-TYPE
    SYNTAX      SysApplMapEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A logical row representing a process currently running
        on the system.  This entry provides the index mapping from
        process identifier, back to the invoked application,
        installed element, and finally, the
installed application
        package.  The entry includes only one accessible columnar
        object, the sysApplMapInstallPkgIndex, but the
        invoked application and installed element can be
        determined from the instance identifier since they form
        part of the index clause."
    INDEX  { sysApplElmtRunIndex, sysApplElmtRunInvocID,
             sysApplMapInstallElmtIndex }
    ::= { sysApplMapTable 1 }

SysApplMapEntry ::= SEQUENCE {
    sysApplMapInstallElmtIndex    Unsigned32,
    sysApplMapInstallPkgIndex     Unsigned32
}

sysApplMapInstallElmtIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
```

```
        "The index into the sysApplInstallElmtTable. The
        value of this object is the same value as the
        sysApplInstallElmtIndex for the application element
        of which this entry represents a running instance.
        If this
process cannot be associated to an installed
        executable, the value should be '0'."
    ::= { sysApplMapEntry 1 }

sysApplMapInstallPkgIndex OBJECT-TYPE
    SYNTAX      Unsigned32 (0..'ffffffff'h)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The value of this object identifies the installed
        software package for the application of which this
        process is a part.  Provided that the process's 'parent'
        application can be determined, the value of this object
        is the same value as the sysApplInstallPkgIndex for the
        entry in the sysApplInstallPkgTable that corresponds
        to the installed application of which this process
        is a part.

        If, however, the 'parent' application cannot be
        determined, (for example the process is not part
        of a particular installed application), the value
        for this object is then '0', signifying that this

 process cannot be related back to an application,
        and in turn, an installed software package."
    ::= { sysApplMapEntry 2 }


-- Conformance Macros
sysApplMIBCompliances  OBJECT IDENTIFIER ::= { sysApplConformance 1 }
sysApplMIBGroups       OBJECT IDENTIFIER ::= { sysApplConformance 2 }

sysApplMIBCompliance MODULE-COMPLIANCE
    STATUS  current
    DESCRIPTION
        "Describes the requirements for conformance to
        the System Application MIB"
    MODULE  -- this module
        MANDATORY-GROUPS { sysApplInstalledGroup,
                           sysApplRunGroup, sysApplMapGroup }
    ::= { sysApplMIBCompliances 1 }

sysApplInstalledGroup OBJECT-GROUP
```

```
    OBJECTS { sysApplInstallPkgManufacturer,
              sysApplInstallPkgProductName,
              sysApplInstallPkgVersion,
              sysApplInstallPkgSerialNumber,
              sysApplInstallPkgDate,
              sysApplInstallPkgLocation,
              sysApplInstallElmtName,
               sysApplInstallElmtType,
              sysApplInstallElmtDate,
              sysApplInstallElmtPath,
              sysApplInstallElmtSizeHigh,
              sysApplInstallElmtSizeLow,
              sysApplInstallElmtRole,
              sysApplInstallElmtModifyDate,
              sysApplInstallElmtCurSizeHigh,
              sysApplInstallElmtCurSizeLow }
    STATUS  current
    DESCRIPTION
       "The system application installed group contains
       information about applications and their constituent
       components which have been installed on the host system."
    ::= { sysApplMIBGroups 1 }

sysApplRunGroup OBJECT-GROUP
    OBJECTS { sysApplRunStarted,
              sysApplRunCurrentState,
              sysApplPastRunStarted,
              sysApplPastRunExitState,
              sysApplPastRunTimeEnded,
              sysApplElmtRunInstallID,
              sysApplElmtRunTimeStarted,
              sysApplElmtRunState,
               sysApplElmtRunName,
              sysApplElmtRunParameters,
              sysApplElmtRunCPU,
              sysApplElmtRunMemory,
              sysApplElmtRunNumFiles,
              sysApplElmtRunUser,
              sysApplElmtPastRunInstallID,
              sysApplElmtPastRunTimeStarted,
              sysApplElmtPastRunTimeEnded,
              sysApplElmtPastRunName,
              sysApplElmtPastRunParameters,
              sysApplElmtPastRunCPU,
              sysApplElmtPastRunMemory,
              sysApplElmtPastRunNumFiles,
              sysApplElmtPastRunUser,
              sysApplPastRunMaxRows,
```

```
            sysApplPastRunTableRemItems,
            sysApplPastRunTblTimeLimit,
            sysApplElemPastRunMaxRows,
            sysApplElemPastRunTableRemItems,
            sysApplElemPastRunTblTimeLimit,
            sysApplAgentPollInterval }
    STATUS  current
    DESCRIPTION
        "The system application
 run group contains information
        about applications and associated elements which have
        run or are currently running on the host system."
    ::= { sysApplMIBGroups 2 }

 sysApplMapGroup OBJECT-GROUP
    OBJECTS { sysApplMapInstallPkgIndex }
    STATUS  current
    DESCRIPTION
        "The Map Group contains a single table, sysApplMapTable,
        that provides a backwards mapping for determining the
        invoked application, installed element, and installed
        application package given a known process identification
        number."
 ::= { sysApplMIBGroups 3 }

 END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/SYSAPPL-MIB
No license file was found, but licenses were detected in source scan.

```
IANA-ITU-ALARM-TC-MIB DEFINITIONS ::= BEGIN

IMPORTS
  MODULE-IDENTITY, mib-2
      FROM SNMPv2-SMI         -- [RFC2578]
  TEXTUAL-CONVENTION
      FROM SNMPv2-TC;         -- [RFC2579]



ianaItuAlarmNumbers MODULE-IDENTITY
    LAST-UPDATED "200409090000Z"  -- September 09, 2004
    ORGANIZATION "IANA"
    CONTACT-INFO
        "Postal:    Internet Assigned Numbers Authority
                    Internet Corporation for Assigned Names
                    and Numbers
```

4676 Admiralty Way, Suite 330
Marina del Rey, CA 90292-6601
USA

Tel: +1 310-823-9358
E-Mail: iana@iana.org"
DESCRIPTION
"The MIB module defines the ITU Alarm
textual convention for objects expected to require
regular extension.

Copyright (C) The Internet Society (2004). The
initial version of this MIB module
was published
in RFC 3877. For full legal notices see the RFC
itself. Supplementary information may be available on:
http://www.ietf.org/copyrights/ianamib.html"
REVISION "200409090000Z" -- September 09, 2004
DESCRIPTION
"Initial version, published as RFC 3877."
::= { mib-2 119 }

IANAItuProbableCause ::= TEXTUAL-CONVENTION
STATUS current
DESCRIPTION
"ITU-T probable cause values. Duplicate values defined in
X.733 are appended with X733 to ensure syntactic uniqueness.
Probable cause value 0 is reserved for special purposes.

The Internet Assigned Number Authority (IANA) is responsible
for the assignment of the enumerations in this TC.
IANAItuProbableCause value of 0 is reserved for special
purposes and MUST NOT be assigned.

Values of IANAItuProbableCause in the range 1 to 1023 are
reserved for causes that correspond to ITU-T probable cause.

All other requests for new causes will be handled on a
first-come, first served basis and will be assigned
enumeration values starting with 1025.

Request should come in the form of well-formed

SMI [RFC2578] for enumeration names that are unique and
sufficiently descriptive.

While some effort will be taken to ensure that new probable

```
        causes do not conceptually duplicate existing probable
        causes it is acknowledged that the existence of conceptual
        duplicates in the starting probable cause list is an known
        industry reality.

        To aid IANA in the administration of probable cause names
        and values, the OPS Area Director will appoint one or more
        experts to help review requests.

        See http://www.iana.org"
    REFERENCE
       "ITU Recommendation M.3100, 'Generic Network Information
          Model', 1995
        ITU Recommendation X.733, 'Information Technology
- Open
          Systems Interconnection - System Management: Alarm
          Reporting Function', 1992
        ITU Recommendation X.736, 'Information Technology - Open
          Systems Interconnection - System Management: Security
          Alarm Reporting Function', 1992"

    SYNTAX        INTEGER
          {
          -- The following probable causes were defined in M.3100
           aIS  (1),
           callSetUpFailure  (2),
           degradedSignal  (3),
           farEndReceiverFailure  (4),
           framingError  (5),
           lossOfFrame (6),
           lossOfPointer  (7),
           lossOfSignal  (8),
           payloadTypeMismatch (9),
           transmissionError (10),
           remoteAlarmInterface (11),
           excessiveBER  (12),
           pathTraceMismatch  (13),
           unavailable  (14),
           signalLabelMismatch (15),
           lossOfMultiFrame (16),
           receiveFailure (17),

       transmitFailure (18),
           modulationFailure (19),
           demodulationFailure (20),
           broadcastChannelFailure (21),
```

```
        connectionEstablishmentError (22),
        invalidMessageReceived (23),
        localNodeTransmissionError (24),
        remoteNodeTransmissionError (25),
        routingFailure (26),

--Values 27-50 are reserved for communications alarm related
--probable causes
-- The following are used with equipment alarm.

        backplaneFailure (51),
        dataSetProblem  (52),
        equipmentIdentifierDuplication  (53),
        externalIFDeviceProblem  (54),
        lineCardProblem (55),
        multiplexerProblem  (56),
        nEIdentifierDuplication  (57),
        powerProblem  (58),
        processorProblem  (59),
        protectionPathFailure  (60),
        receiverFailure  (61),
        replaceableUnitMissing  (62),
        replaceableUnitTypeMismatch
 (63),
        synchronizationSourceMismatch  (64),
        terminalProblem   (65),
        timingProblem   (66),
        transmitterFailure  (67),
        trunkCardProblem  (68),
        replaceableUnitProblem  (69),
        realTimeClockFailure (70),
--An equipment alarm to be issued if the system detects that the
--real time clock has failed
        antennaFailure (71),
        batteryChargingFailure (72),
        diskFailure (73),
        frequencyHoppingFailure (74),
        iODeviceError (75),
        lossOfSynchronisation (76),
        lossOfRedundancy (77),
        powerSupplyFailure (78),
        signalQualityEvaluationFailure (79),
        tranceiverFailure (80),
        protectionMechanismFailure (81),
        protectingResourceFailure (82),
-- Values 83-100 are reserved for equipment alarm related probable
-- causes
-- The following are used with environmental alarm.
```

```
        airCompressorFailure  (101),


        airConditioningFailure  (102),
        airDryerFailure   (103),
        batteryDischarging  (104),
        batteryFailure   (105),
        commercialPowerFailure  (106),
        coolingFanFailure  (107),
        engineFailure  (108),
        fireDetectorFailure  (109),
        fuseFailure  (110),
        generatorFailure  (111),
        lowBatteryThreshold (112),
        pumpFailure  (113),
        rectifierFailure  (114),
        rectifierHighVoltage  (115),
        rectifierLowFVoltage  (116),
        ventilationsSystemFailure  (117),
        enclosureDoorOpen  (118),
        explosiveGas  (119),
        fire (120),
        flood   (121),
        highHumidity  (122),
        highTemperature  (123),
        highWind  (124),
        iceBuildUp  (125),
        intrusionDetection  (126),
        lowFuel
 (127),
        lowHumidity  (128),
        lowCablePressure  (129),
        lowTemperatue  (130),
        lowWater  (131),
        smoke  (132),
        toxicGas  (133),
        coolingSystemFailure (134),
        externalEquipmentFailure (135),
        externalPointFailure (136),
-- Values 137-150 are reserved for environmental alarm related
-- probable causes
-- The following are used with Processing error alarm.
        storageCapacityProblem (151),
        memoryMismatch  (152),
        corruptData  (153),
        outOfCPUCycles   (154),
        sfwrEnvironmentProblem  (155),
        sfwrDownloadFailure  (156),
```

```
        lossOfRealTimel (157),
--A processing error alarm to be issued after the system has
--reinitialised.  This will indicate
--to the management systems that the view they have of the managed


--system may no longer
--be valid.  Usage example: The managed
--system issues this alarm
 after a reinitialization with severity
--warning to inform the
--management system about the event.  No clearing notification will
--be sent.
        applicationSubsystemFailure (158),
        configurationOrCustomisationError (159),
        databaseInconsistency (160),
        fileError (161),
        outOfMemory (162),
        softwareError (163),
        timeoutExpired (164),
        underlayingResourceUnavailable (165),
        versionMismatch (166),
--Values 168-200 are reserved for processing error alarm related
-- probable causes.
        bandwidthReduced (201),
        congestion (202),
        excessiveErrorRate (203),
        excessiveResponseTime (204),
        excessiveRetransmissionRate (205),
        reducedLoggingCapability (206),
        systemResourcesOverload (207 ),
        -- The following were defined X.733
        adapterError (500),
        applicationSubsystemFailture
 (501),
        bandwidthReducedX733 (502),
        callEstablishmentError (503),
        communicationsProtocolError (504),
        communicationsSubsystemFailure (505),
        configurationOrCustomizationError (506),
        congestionX733 (507),
        coruptData (508),
        cpuCyclesLimitExceeded (509),
        dataSetOrModemError (510),
        degradedSignalX733 (511),
        dteDceInterfaceError (512),
        enclosureDoorOpenX733 (513),
        equipmentMalfunction (514),
```

excessiveVibration (515),
fileErrorX733 (516),
fireDetected (517),
framingErrorX733 (518),
heatingVentCoolingSystemProblem (519),
humidityUnacceptable (520),
inputOutputDeviceError (521),
inputDeviceError (522),

lanError (523),
leakDetected (524),
localNodeTransmissionErrorX733 (525),

lossOfFrameX733 (526),
lossOfSignalX733 (527),
materialSupplyExhausted (528),
multiplexerProblemX733 (529),
outOfMemoryX733 (530),
ouputDeviceError (531),
performanceDegraded (532),
powerProblems (533),
pressureUnacceptable (534),
processorProblems (535),
pumpFailureX733 (536),
queueSizeExceeded (537),
receiveFailureX733 (538),
receiverFailureX733 (539),
remoteNodeTransmissionErrorX733 (540),
resourceAtOrNearingCapacity (541),
responseTimeExecessive (542),
retransmissionRateExcessive (543),
softwareErrorX733 (544),
softwareProgramAbnormallyTerminated (545),
softwareProgramError (546),
storageCapacityProblemX733 (547),
temperatureUnacceptable (548),
thresholdCrossed (549),
timingProblemX733
(550),
toxicLeakDetected (551),
transmitFailureX733 (552),
transmiterFailure (553),
underlyingResourceUnavailable (554),
versionMismatchX733 (555),
-- The following are defined in X.736
authenticationFailure (600),
breachOfConfidentiality (601),

```
        cableTamper (602),
        delayedInformation (603),
        denialOfService (604),
        duplicateInformation (605),
        informationMissing (606),
        informationModificationDetected (607),
        informationOutOfSequence (608),
        keyExpired (609),
        nonRepudiationFailure (610),
        outOfHoursActivity (611),
        outOfService (612),
        proceduralError (613),


        unauthorizedAccessAttempt (614),
        unexpectedInformation (615),

        other (1024)
        }

IANAItuEventType ::= TEXTUAL-CONVENTION
   STATUS current
  DESCRIPTION
        "The ITU event Type values.

        The Internet Assigned Number Authority (IANA) is
        responsible for the assignment of the enumerations
        in this TC.

        Request should  come in the form of well-formed
        SMI [RFC2578] for enumeration names that are unique
        and sufficiently descriptive.

        See http://www.iana.org "
  REFERENCE
       "ITU Recommendation X.736, 'Information Technology - Open
        Systems Interconnection - System Management: Security
        Alarm Reporting Function', 1992"
  SYNTAX        INTEGER
       {
       other (1),
       communicationsAlarm (2),
       qualityOfServiceAlarm (3),
       processingErrorAlarm (4),
       equipmentAlarm (5),
       environmentalAlarm (6),
       integrityViolation (7),
       operationalViolation (8),
```

```
        physicalViolation (9),
        securityServiceOrMechanismViolation
 (10),
        timeDomainViolation (11)
        }

END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/IANA-ITU-ALARM-TC-MIB
No license file was found, but licenses were detected in source scan.

```
PKTC-IETF-MTA-MIB DEFINITIONS ::= BEGIN

IMPORTS
  MODULE-IDENTITY,
  OBJECT-TYPE,
  OBJECT-IDENTITY,
  Unsigned32,
  Counter32,
  NOTIFICATION-TYPE,
  mib-2
      FROM SNMPv2-SMI                 -- [RFC2578]
  TEXTUAL-CONVENTION,
  RowStatus,
  TruthValue
      FROM SNMPv2-TC                  -- [RFC2579]
  OBJECT-GROUP,
  MODULE-COMPLIANCE,
  NOTIFICATION-GROUP
      FROM SNMPv2-CONF                -- [RFC2580]
  InetAddressType,
  InetAddress
      FROM INET-ADDRESS-MIB           -- [RFC4001]
  sysDescr
      FROM SNMPv2-MIB                 -- [RFC3418]
  SnmpAdminString
      FROM SNMP-FRAMEWORK-MIB         -- [RFC3411]
  docsDevSoftwareGroupV2
      FROM DOCS-CABLE-DEVICE-MIB      -- [RFC4639]
  DocsX509ASN1DEREncodedCertificate,
  docsBpi2CodeDownloadGroup
      FROM DOCS-IETF-BPI2-MIB         -- [RFC4131]
  LongUtf8String
       FROM SYSAPPL-MIB               -- [RFC2287]
  ifPhysAddress
      FROM IF-MIB;                    -- [RFC2863]
```

```
pktcIetfMtaMib MODULE-IDENTITY
LAST-UPDATED "200609180000Z" -- September 18, 2006
ORGANIZATION "IETF IP over Cable Data Network Working Group"
CONTACT-INFO
    "Eugene Nechamkin
     Broadcom Corporation,
     200-13711 International Place,



     Richmond, BC, V6V 2Z8
     CANADA
     Phone: +1 604 233 8500
     Email: enechamkin@broadcom.com

     Jean-Francois Mule
     Cable Television Laboratories, Inc.
     858 Coal Creek Circle
     Louisville, CO 80027-9750
     U.S.A.
     Phone: +1 303 661 9100
     Email: jf.mule@cablelabs.com

  IETF IPCDN Working Group
     General Discussion: ipcdn@ietf.org
     Subscribe: http://www.ietf.org/mailman/listinfo/ipcdn
     Archive: ftp://ftp.ietf.org/ietf-mail-archive/ipcdn
     Co-Chair: Jean-Francois Mule, jf.mule@cablelabs.com
      Co-Chair: Richard Woundy, Richard_Woundy@cable.comcast.com"

  DESCRIPTION
    "This MIB module defines the basic management object
     for the Multimedia Terminal Adapter devices compliant
     with PacketCable and IPCablecom requirements.

     Copyright (C) The IETF Trust (2006).  This version of
     this MIB module is part of RFC 4682; see the RFC itself for
     full legal notices."

  REVISION    "200609180000Z"   -- September 18, 2006

  DESCRIPTION
    "Initial version, published as RFC 4682."

::=  { mib-2 140 }

 -- Textual Conventions
```

```
PktcMtaDevProvEncryptAlg  ::= TEXTUAL-CONVENTION
  STATUS      current
  DESCRIPTION
     " This textual convention defines various types of the
       encryption algorithms used for the encryption of the MTA
       configuration file.  The description of the encryption
       algorithm for each enumerated value is as follows:

       'none(0)'           no encryption
 is used,
       'des64CbcMode(1)'    DES 64-bit key in CBC mode,



       't3Des192CbcMode(2)' 3DES 192-bit key in CBC mode,
       'aes128CbcMode(3)'   AES 128-bit key in CBC mode,
       'aes256CbcMode(4)'   AES 256-bit key in CBC mode."
  SYNTAX      INTEGER  {
            none            (0),
            des64CbcMode    (1),
            t3Des192CbcMode  (2),
            aes128CbcMode    (3),
            aes256CbcMode    (4)
  }

--========================================================================
-- The MTA MIB module only supports a single Provisioning Server.
--========================================================================

pktcMtaNotification OBJECT IDENTIFIER ::= { pktcIetfMtaMib 0 }
pktcMtaMibObjects  OBJECT IDENTIFIER ::= { pktcIetfMtaMib 1 }
pktcMtaDevBase     OBJECT IDENTIFIER ::= { pktcMtaMibObjects 1 }
pktcMtaDevServer   OBJECT IDENTIFIER ::= { pktcMtaMibObjects 2 }
pktcMtaDevSecurity OBJECT IDENTIFIER ::= { pktcMtaMibObjects 3
 }
pktcMtaDevErrors   OBJECT IDENTIFIER ::= { pktcMtaMibObjects 4 }
pktcMtaConformance  OBJECT IDENTIFIER ::= { pktcIetfMtaMib 2 }

--
-- The following pktcMtaDevBase group describes the base MTA objects
--

pktcMtaDevResetNow  OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     " This object controls the MTA software reset.
```

Reading this object always returns 'false'. Setting this
object to 'true' causes the device to reset immediately
and the following actions to occur:

1. All connections (if present) are flushed locally.
2. All current actions such as ringing immediately terminate.
3. Requests for signaling notifications, such as notification based on digit map recognition, are flushed.
4. All endpoints are disabled.
5. The provisioning flow is started at step MTA-1.

If a value is written into an instance of
pktcMtaDevResetNow, the agent MUST NOT retain the supplied
value across MTA re-initializations or reboots."
REFERENCE

" PacketCable MTA Device Provisioning Specification."
::= { pktcMtaDevBase 1 }

pktcMtaDevSerialNumber OBJECT-TYPE
SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
" This object specifies the manufacturer's serial
number of this MTA. The value of this object MUST be
identical to the value specified in DHCP option 43,
sub-option 4. The list of sub-options for DHCP option
43 are defined in the PacketCable MTA Device
Provisioning Specification."
REFERENCE
" PacketCable MTA Device Provisioning Specification."
::= { pktcMtaDevBase 2 }

pktcMtaDevSwCurrentVers OBJECT-TYPE
SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
" This object identifies the software version currently
operating in the MTA.
The MTA MUST return a string descriptive of the current
software load. This object should use the syntax
defined by the individual vendor to identify the software
version. The data presented in this object MUST be

identical to the software version information contained
in the 'sysDescr' MIB object of the MTA. The value of
this object MUST be identical to the value specified in
DHCP option 43, sub-option 6. The list of sub-options for
DHCP option 43 are defined in the PacketCable MTA Device
Provisioning Specification."
REFERENCE
" PacketCable MTA Device Provisioning Specification."

::= { pktcMtaDevBase 3 }

pktcMtaDevFQDN OBJECT-TYPE
SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
" This object contains the Fully Qualified
Domain Name for
this MTA. The MTA FQDN is used to uniquely identify the
device to the PacketCable back office elements."

::= { pktcMtaDevBase 4 }

pktcMtaDevEndPntCount OBJECT-TYPE
SYNTAX Unsigned32 (1..255)
MAX-ACCESS read-only
STATUS current
DESCRIPTION
" This object contains the number of physical endpoints for
this MTA."
::= { pktcMtaDevBase 5 }

pktcMtaDevEnabled OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-write
STATUS current
DESCRIPTION
" This object contains the MTA Admin Status of this device.
If this object is set to 'true', the MTA is
administratively enabled, and the MTA MUST be able to
interact with the PacketCable entities, such as CMS,
Provisioning Server, KDC, and other MTAs and MGs on all
PacketCable interfaces.
If this object is set to 'false', the MTA is
administratively

```
 disabled, and the MTA MUST perform the
        following actions for all endpoints:
           - Shut down all media sessions, if present.
           - Shut down Network Control Signaling (NCS)
           signaling by following the Restart in
           Progress procedures in the PacketCable NCS
           specification.
        The MTA must execute all actions required to
        enable or disable the telephony services for all
        endpoints immediately upon receipt of an SNMP SET
        operation.

        Additionally, the MTA MUST maintain the SNMP Interface
        for management and also the SNMP Key management interface.
        Also, the MTA MUST NOT continue Kerberized key management
        with CMSes until this object is set to 'true'.
        Note: MTAs MUST renew the CMS Kerberos tickets according
        to the PacketCable Security or IPCablecom Specification.
        If a value is written into an instance
of
        pktcMtaDevEnabled, the agent MUST NOT retain the supplied
        value across MTA re-initializations or reboots."
  REFERENCE
     " PacketCable MTA Device Provisioning Specification;
       PacketCable Security Specification;
       PacketCable Network-Based Call Signaling Protocol




       Specification."
  ::= { pktcMtaDevBase 6 }

pktcMtaDevTypeIdentifier     OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object provides the MTA device type identifier.  The
       value of this object must be a copy of the DHCP option 60
       value exchanged between the MTA and the DHCP server.  The
       DHCP option 60 value contains an ASCII-encoded string
       identifying capabilities of the MTA as defined in the
       PacketCable MTA Device Provisioning Specification."
  REFERENCE
     " RFC 2132, DHCP Options and BOOTP Vendor Extensions;
       PacketCable
 MTA Device Provisioning Specification."
  ::= { pktcMtaDevBase 7 }
```

```
pktcMtaDevProvisioningState     OBJECT-TYPE
  SYNTAX      INTEGER {
              pass                    (1),
              inProgress              (2),
              failConfigFileError     (3),
              passWithWarnings        (4),
              passWithIncompleteParsing (5),
              failureInternalError    (6),
              failureOtherReason      (7)
  }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object indicates the completion state of the MTA
       device provisioning process.

       pass:
       If the configuration file could be parsed successfully
       and the MTA is able to reflect the same in its
       MIB, the MTA MUST return the value 'pass'.

       inProgress:
       If the MTA is in the process of being provisioned,
       the MTA MUST return the value 'inProgress'.

       failConfigFileError:
        If the configuration file was in error due to incorrect
       values in the mandatory parameters, the MTA MUST reject
       the configuration file, and the MTA MUST return the value



       'failConfigFileError'.

       passWithWarnings:
       If the configuration file had proper values for all the
       mandatory parameters but has errors in any of the optional
       parameters (this includes any vendor-specific Object
       Identifiers (OIDs) that are incorrect or not known
       to the MTA), the MTA MUST return the value
       'passWithWarnings'.

       passWithIncompleteParsing:
       If the configuration file is valid but the MTA cannot
       reflect the same in its configuration (for example, too
       many entries caused memory exhaustion), it must accept
       the CMS configuration entries related, and the MTA MUST
```

```
        return the value 'passWithIncompleteParsing'.

        failureInternalError:
         If the configuration file cannot be parsed due to an
        Internal error, the MTA MUST return the value
        'failureInternalError'.

        failureOtherReason:
        If the MTA cannot accept the configuration file for any
        other reason than the ones stated above, the MTA MUST
        return the value 'failureOtherReason'.

        When a final SNMP INFORM is sent as part of Step 25 of the
        MTA Provisioning process, this parameter is also included
        in the final INFORM message."
      REFERENCE
       " PacketCable MTA Device Provisioning Specification."
   ::= { pktcMtaDevBase 8 }

pktcMtaDevHttpAccess  OBJECT-TYPE
   SYNTAX      TruthValue
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
      " This object indicates whether the HTTP protocol is
        supported for the MTA configuration file transfer."
   ::= { pktcMtaDevBase 9 }

pktcMtaDevProvisioningTimer  OBJECT-TYPE
   SYNTAX      Unsigned32
 (0..30)
   UNITS       "minutes"
   MAX-ACCESS  read-write
   STATUS      current



   DESCRIPTION
      " This object defines the time interval for the provisioning
        flow to complete.  The MTA MUST finish all provisioning
        operations starting from the moment when an MTA receives
        its DHCP ACK and ending at the moment when the MTA
        downloads its configuration file (e.g., MTA5 to MTA23)
        within the period of time set by this object.
        Failure to comply with this condition constitutes
        a provisioning flow failure.  If the object is set to 0,
        the MTA MUST ignore the provisioning timer condition.
        If a value is written into an instance of
```

```
        pktcMtaDevProvisioningTimer, the agent MUST NOT retain the
        supplied value across MTA re-initializations or reboots."
    REFERENCE
       " PacketCable MTA Device Provisioning Specification."
    DEFVAL {10}
    ::=  {pktcMtaDevBase 10}

pktcMtaDevProvisioningCounter
   OBJECT-TYPE
     SYNTAX      Counter32
     MAX-ACCESS  read-only
     STATUS      current
     DESCRIPTION
          "This object counts the number of times the
          provisioning cycle has looped through step MTA-1."
     ::= {pktcMtaDevBase 11}

pktcMtaDevErrorOidsTable  OBJECT-TYPE
    SYNTAX SEQUENCE OF PktcMtaDevErrorOidsEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
       " This table contains the list of configuration errors or
         warnings the MTA encountered when parsing the
         configuration file it received from the Provisioning
         Server.
         For each error, an entry is created in this table,
         containing the configuration parameters the MTA rejected
         and the associated reason (e.g., wrong or unknown OID,
         inappropriate object values).  If the MTA
         did not report a provisioning state of 'pass(1)' in
         the pktcMtaDevProvisioningState object, this
  table MUST be
         populated for each error or warning instance.  Even if
         different parameters share the same error type (e.g., all
         realm name configuration parameters are invalid), all
         observed errors or warnings must be reported as
         different instances.  Errors are placed into the table in
         no particular order.  The table MUST be cleared each time




         the MTA reboots."
    REFERENCE
       " PacketCable MTA Device Provisioning Specification."
    ::= {pktcMtaDevBase 12 }

pktcMtaDevErrorOidsEntry  OBJECT-TYPE
```

```
  SYNTAX PktcMtaDevErrorOidsEntry
  MAX-ACCESS not-accessible
  STATUS current
  DESCRIPTION
     " This entry contains the necessary information the MTA MUST
       attempt to provide in case of configuration file errors or
       warnings."
  INDEX { pktcMtaDevErrorOidIndex }
         ::= {pktcMtaDevErrorOidsTable 1}

PktcMtaDevErrorOidsEntry ::= SEQUENCE {
  pktcMtaDevErrorOidIndex Unsigned32,
   pktcMtaDevErrorOid      SnmpAdminString,
  pktcMtaDevErrorValue    SnmpAdminString,
  pktcMtaDevErrorReason   SnmpAdminString
  }

pktcMtaDevErrorOidIndex  OBJECT-TYPE
  SYNTAX      Unsigned32 (1..1024)
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     " This object is the index of the MTA configuration error
       table.  It is an integer value that starts at value '1'
       and is incremented for each encountered configuration
       file error or warning.

       The maximum number of errors or warnings that can be
       recorded in the pktcMtaDevErrorOidsTable is set to 1024 as
       a configuration file is usually validated by operators
       before deployment.  Given the possible number of
       configuration parameter assignments in the MTA
       configuration file, 1024 is perceived as a sufficient
       limit even with future extensions.

       If the number of the errors in the configuration
 file
       exceeds 1024, all errors beyond the 1024th one MUST
       be ignored and not be reflected in the
       pktcMtaDevErrorOidsTable."

  ::= {pktcMtaDevErrorOidsEntry 1}



pktcMtaDevErrorOid  OBJECT-TYPE
  SYNTAX      SnmpAdminString
```

```
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object contains a human readable representation
       (character string) of the OID corresponding to the
       configuration file parameter that caused the particular
       error.
       For example, if the value of the pktcMtaDevEnabled object
       in the configuration file caused an error, then this
       object instance will contain the human-readable string of
       '1.3.6.1.2.1.140.1.1.6.0'.
       If the MTA generated an error because it was not able
       to recognize a particular OID, then this object
       instance would contain an empty value (zero-length
       string).
       For example,
 if the value of an OID in the configuration
       file was interpreted by the MTA as being 1.2.3.4.5, and if
       the MTA was not able to recognize this OID as a valid one,
       this object instance will contain a zero-length string.

       If the number of errors in the configuration file exceeds
       1024, then for all subsequent errors, the
       pktcMtaDevErrorOid of the table's 1024th entry MUST
       contain a human-readable representation of the
       pktcMtaDevErrorsTooManyErrors object; i.e., the string
       '1.3.6.1.2.1.140.1.1.4.1.0'.
       Note that the syntax of this object is SnmpAdminString
       instead of OBJECT IDENTIFIER because the object value may
       not be a valid OID due to human or configuration tool
       encoding errors."

  ::= {pktcMtaDevErrorOidsEntry 2}

pktcMtaDevErrorValue  OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This
 object contains the value of the OID corresponding to
       the configuration file parameter that caused the error.
       If the MTA cannot recognize the OID of the
       configuration parameter causing the error, then this
       object instance contains the OID itself as interpreted
       by the MTA in human-readable representation.
       If the MTA can recognize the OID but generate an error due
       to a wrong value of the parameter, then the object
```

instance contains the erroneous value of the parameter as
read from the configuration file.
In both cases, the value of this object must be
represented in human-readable form as a character string.
For example, if the value of the pktcMtaDevEnabled object
in the configuration file was 3 (invalid value), then the
pktcMtaDevErrorValue object instance will contain the
human-readable (string) representation of value '3'.

Similarly, if the OID in the configuration file has been
interpreted by the MTA as being 1.2.3.4.5 and the MTA
cannot recognize this OID as a valid one, then this
pktcMtaDevErrorValue object instance will contain human
readable (string) representation of value '1.2.3.4.5'.

If the number of errors in the configuration file exceeds
1024, then for all subsequent errors, the
pktcMtaDevErrorValue of the table's 1024th entry MUST
contain a human-readable representation of the
pktcMtaDevErrorsTooManyErrors object; i.e., the string
'1.3.6.1.2.1.140.1.1.4.1.0'."

::= {pktcMtaDevErrorOidsEntry 3}

pktcMtaDevErrorReason OBJECT-TYPE
SYNTAX SnmpAdminString
MAX-ACCESS read-only
STATUS current
DESCRIPTION
" This object indicates the reason for the error or warning,
as per the MTA's interpretation, in human-readable form.
For example:

'VALUE NOT IN RANGE', 'VALUE DOES NOT MATCH TYPE',
'UNSUPPORTED VALUE', 'LAST 4 BITS MUST BE SET TO ZERO',
'OUT OF MEMORY - CANNOT STORE'.
This object may also contain vendor specific errors for
private vendor OIDs and any proprietary error codes or
messages that can help diagnose configuration errors.

If the number of errors in the configuration file exceeds
1024, then for all subsequent errors, the
pktcMtaDevErrorReason of the table's 1024th entry MUST
contain a human-readable string indicating the reason
for an error; for example,

```
        'Too many errors in the configuration file'."
    ::= {pktcMtaDevErrorOidsEntry 4}

--
-- The following group describes server access and parameters used



-- for the initial MTA provisioning and bootstrapping phases.
--

pktcMtaDevDhcpServerAddressType  OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-only
    STATUS      current
     DESCRIPTION
        " This object contains the Internet address type for the
          PacketCable DHCP servers specified in MTA MIB."
    DEFVAL { ipv4 }
    ::= { pktcMtaDevServer 1}

pktcMtaDevServerDhcp1   OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        " This object contains the Internet Address of the primary
          DHCP server the MTA uses during provisioning.
          The type of this address is determined by the value of
          the pktcMtaDevDhcpServerAddressType object.
          When the latter has the value 'ipv4(1)', this object
          contains the IP address of the primary DHCP
          server.  It is provided by the CM to the MTA via the DHCP
          option code 122, sub-option 1, as defined in RFC 3495.

          The behavior of this object when the value of
          pktcMtaDevDhcpServerAddressType is other than 'ipv4(1)'
          is not presently specified, but it may be specified
           in future versions of this MIB module.
          If this object is of value
          0.0.0.0, the MTA MUST stop all provisioning
          attempts, as well as all other activities.
          If this object is of value 255.255.255.255, it means
          that there was no preference given for the primary
          DHCP server, and, the MTA must follow the logic of
          RFC2131, and the value of DHCP option 122,
          sub-option 2, must be ignored."
    REFERENCE
```

```
      " PacketCable MTA Device Provisioning Specification;
       RFC 2131, Dynamic Host Configuration Protocol;
       RFC 3495, DHCP Option for CableLabs Client Configuration."
  ::= { pktcMtaDevServer 2 }

pktcMtaDevServerDhcp2  OBJECT-TYPE
  SYNTAX      InetAddress
  MAX-ACCESS  read-only



  STATUS      current
  DESCRIPTION
      " This object contains the Internet Address of the secondary
       DHCP server the MTA uses during provisioning.
       The type of this address
 is determined by the value of
       the pktcMtaDevDhcpServerAddressType object.
       When the latter has the value 'ipv4(1)', this object
       contains the IP address of the secondary DHCP
       server.  It is provided by the CM to the MTA via the DHCP
       option code 122, sub-option 2, as defined in RFC 3495.

       The behavior of this object when the value of
       pktcMtaDevDhcpServerAddressType is other than 'ipv4(1)'
       is not presently specified, but it may be specified
       in future versions of this MIB module.
       If there was no secondary DHCP server provided in DHCP
       Option 122, sub-option 2, this object must return the value
       0.0.0.0."
  REFERENCE
      " PacketCable MTA Device Provisioning Specification;
       RFC 3495, DHCP Option for CableLabs Client Configuration."
       ::= { pktcMtaDevServer 3 }

pktcMtaDevDnsServerAddressType  OBJECT-TYPE
  SYNTAX      InetAddressType
  MAX-ACCESS
 read-only
  STATUS      current
  DESCRIPTION
      " This object contains the Internet address type for the
       PacketCable DNS servers specified in MTA MIB."
  DEFVAL { ipv4 }
  ::= { pktcMtaDevServer 4}

pktcMtaDevServerDns1  OBJECT-TYPE
  SYNTAX      InetAddress
```

```
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     " This object contains the IP Address of the primary
       DNS server to be used by the MTA.  The type of this address
       is determined by the value of the
       pktcMtaDevDnsServerAddressType object.
       When the latter has the value 'ipv4(1)', this object
       contains the IP address of the primary DNS server.
       As defined in RFC 2132, PacketCable-compliant MTAs receive
       the IP addresses of the DNS Servers in DHCP option 6.
       The behavior of this object when the value of
       pktcMtaDevDnsServerAddressType is other than 'ipv4(1)'




       is not presently specified, but it
 may be specified
       in future versions of this MIB module.
       If a value is written into an instance of
       pktcMtaDevServerDns1, the agent MUST NOT retain the
       supplied value across MTA re-initializations or reboots."
  REFERENCE
     " PacketCable MTA Device Provisioning Specification;
       RFC 2132, DHCP Options and BOOTP Vendor Extensions."
  ::= { pktcMtaDevServer 5 }

pktcMtaDevServerDns2  OBJECT-TYPE
  SYNTAX      InetAddress
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     " This object contains the IP Address of the secondary
       DNS server to be used by the MTA.  The type of this address
       is determined by the value of the
       pktcMtaDevDnsServerAddressType object.
       When the latter has the value 'ipv4(1)', this object
       contains the IP address of the secondary DNS
       server.  As defined in RFC 2132, PacketCable-compliant MTAs
       receive the IP addresses of
 the DNS Servers in DHCP
       option 6.
       The behavior of this object when the value of
       pktcMtaDevDnsServerAddressType is other than 'ipv4(1)'
       is not presently specified, but it may be specified
       in future versions of this MIB module.
       If a value is written into an instance of
       pktcMtaDevServerDns2, the agent MUST NOT retain the
```

```
        supplied value across MTA re-initializations or reboots."
    REFERENCE
       " PacketCable MTA Device Provisioning Specification;
        RFC 2132, DHCP Options and BOOTP Vendor Extensions."
    ::= { pktcMtaDevServer 6 }

pktcMtaDevTimeServerAddressType  OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       " This object contains the Internet address type for the
        PacketCable Time servers specified in MTA MIB."
    DEFVAL { ipv4 }
    ::= { pktcMtaDevServer 7}

pktcMtaDevTimeServer   OBJECT-TYPE
    SYNTAX      InetAddress



     MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
       " This object contains the Internet Address of the Time
        Server used by an S-MTA for Time Synchronization.  The type
        of this address is determined by the value of the
        pktcMtaDevTimeServerAddressType object.
        When the latter has the value 'ipv4(1)', this object
        contains the IP address of the Time Server used for Time
        Synchronization.
        In the case of an S-MTA, this object must be
        populated with a value other than 0.0.0.0 as obtained
        from DHCP option 4.  The protocol by which the time of day
        MUST be retrieved is defined in RFC 868.
        In the case of an E-MTA, this object must contain a
        value of 0.0.0.0 if the address type is 'ipv4(1)' since
        an E-MTA does not use the Time Protocol for time
        synchronization (an E-MTA uses the time retrieved by the
        DOCSIS cable modem).
         The behavior of this object when the value of
        pktcMtaDevTimeServerAddressType is other than 'ipv4(1)'
        is not presently specified, but it may be specified in
        future versions of this MIB module.
        If a value is written into an instance of
        pktcMtaDevTimeServer, the agent MUST NOT retain the
        supplied value across MTA re-initializations or reboots."
    REFERENCE
```

```
      " RFC 868, Time Protocol;
       RFC 2131, Dynamic Host Configuration Protocol;
       RFC 2132, DHCP Options and BOOTP Vendor Extensions."
  ::= { pktcMtaDevServer 8}

pktcMtaDevConfigFile  OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     " This object specifies the MTA device configuration file
       information, including the access method, the server name,
       and the configuration file name.  The value of this object
       is the Uniform Resource Locator (URL)
 of the configuration
       file for TFTP or HTTP download.
       If this object value is a TFTP URL, it must be formatted
       as defined in RFC 3617.
       If this object value is an HTTP URL, it must be formatted
       as defined in RFC 2616.
       If the MTA SNMP Enrollment mechanism is used, then the MTA
       must download the file provided by the Provisioning Server



       during provisioning via an SNMP SET on this object.
       If the MTA SNMP Enrollment mechanism is not used, this
       object MUST contain the URL value corresponding to the
       'siaddr' and 'file' fields received in the DHCP ACK to
       locate the configuration file: the 'siaddr' and 'file'
       fields represent the host and file of the TFTP URL,
       respectively.  In this case, the MTA MUST return an
       'inconsistentValue' error in response to SNMP SET
       operations.
       The MTA MUST return a zero-length string if the server
        address (host part of the URL) is unknown.
       If a value is written into an instance of
       pktcMtaDevConfigFile, the agent MUST NOT retain the
       supplied value across MTA re-initializations or reboots."
  REFERENCE
     " PacketCable MTA Device Provisioning Specification;
       RFC 3617, URI Scheme for TFTP; RFC 2616, HTTP 1.1"
  ::= { pktcMtaDevServer 9 }

pktcMtaDevSnmpEntity  OBJECT-TYPE
  SYNTAX      SnmpAdminString
  MAX-ACCESS  read-only
  STATUS      current
```

```
  DESCRIPTION
     " This object contains the FQDN of the SNMP entity of the
       Provisioning Server.  When the MTA SNMP Enrollment
       Mechanism is used, this object represents the server that
       the MTA communicates with, that it receives the
       configuration file URL from, and that it sends the
       enrollment notification to.  The SNMP entity is also the
       destination entity for all the provisioning
       notifications.  It
 may be used for post-provisioning
       SNMP operations.  During the provisioning phase, this
       SNMP entity FQDN is supplied to the MTA via DHCP option
       122, sub-option 3, as defined in RFC 3495.  The MTA must
       resolve the FQDN value before its very first network
       interaction with the SNMP entity during the provisioning
       phase."

  REFERENCE
     " PacketCable MTA Device Provisioning Specification;
       RFC 3495, DHCP Option for CableLabs Client Configuration."
  ::= { pktcMtaDevServer 10 }

pktcMtaDevProvConfigHash  OBJECT-TYPE
  SYNTAX      OCTET STRING (SIZE(20))
  MAX-ACCESS  read-write
  STATUS      current



  DESCRIPTION
     " This object contains the hash value of the contents of the
       configuration file.
       The authentication algorithm is Secure Hashing Algorithm
       1 (SHA-1), and the length is 160 bits.  The hash
       calculation MUST follow the requirements defined in the

       PacketCable Security Specification.  When the MTA SNMP
       Enrollment mechanism is used, this hash value is
       calculated and sent to the MTA prior to sending the
       config file.  This object value is then provided by the
       Provisioning server via an SNMP SET operation.
       When the MTA SNMP Enrollment mechanism is not in use, the
       hash value is provided in the configuration file itself,
       and it is also calculated by the MTA.  This object value
       MUST represent the hash value calculated by the MTA.
       When the MTA SNMP Enrollment mechanism is not in use, the
       MTA must reject all SNMP SET operations on this object and
       return an 'inconsistentValue' error.
```

```
        If a value is written into an instance of
        pktcMtaDevProvConfigHash, the agent MUST NOT retain the
        supplied value across MTA re-initializations or reboots."
    REFERENCE
       " PacketCable MTA Device Provisioning
 Specification;
        PacketCable Security Specification."
    ::= { pktcMtaDevServer 11 }

pktcMtaDevProvConfigKey  OBJECT-TYPE
    SYNTAX      OCTET STRING (SIZE(32))
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
       " This object contains the key used to encrypt/decrypt
        the configuration file when secure SNMPv3 provisioning
        is used.
        The value of this object is provided along with the
        configuration file information (pktcMtaDevConfigFile)
        and hash (pktcMtaDevProvConfigHash) by the Provisioning
        Server via SNMP SET once the configuration file has been
        created, as defined by the PacketCable Security
        specification.

        The privacy algorithm is defined by the
        pktcMtaDevProvConfigEncryptAlg MIB object.  The
        MTA requirements related to the privacy algorithm are
        defined in the PacketCable Security Specification.

        If this object is set at
 any other provisioning step than
        that allowed by the PacketCable MTA Device



        Provisioning Specification, the MTA SHOULD return
        an 'inconsistentValue' error.
        This object must not be used in non secure provisioning
        mode.  In non-secure provisioning modes, the MTA SHOULD
        return an 'inconsistentValue' in response to SNMP SET
        operations, and the MTA SHOULD return a zero-length
        string in response to SNMP GET operations.
        If a value is written into an instance of
        pktcMtaDevProvConfigKey, the agent MUST NOT retain the
        supplied value across MTA re-initializations or reboots."
    REFERENCE
       " PacketCable MTA Device Provisioning Specification;
        PacketCable Security Specification."
```

::= { pktcMtaDevServer 12 }

pktcMtaDevProvConfigEncryptAlg OBJECT-TYPE
SYNTAX PktcMtaDevProvEncryptAlg
MAX-ACCESS read-write
STATUS current
DESCRIPTION

" This object defines the encryption algorithm used for
privacy protection of the MTA Configuration File content."
DEFVAL { des64CbcMode }
::= { pktcMtaDevServer 13 }

pktcMtaDevProvSolicitedKeyTimeout OBJECT-TYPE
SYNTAX Unsigned32 (0..180)
UNITS "seconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
" This object defines a Kerberos Key Management timer on the
MTA. It is the time period during which the MTA saves the
nonce and Server Kerberos Principal Identifier to match an
AP Request and its associated AP Reply response from the
Provisioning Server.
After the timeout has been exceeded, the client discards
this (nonce, Server Kerberos Principal Identifier) pair,
after which it will no longer accept a matching AP Reply.
This timer only applies when the Provisioning Server
initiated key management for SNMPv3 (with a
Wake
Up message).
If this object is set to a zero value, the MTA MUST return
an 'inconsistentValue' in response to SNMP SET operations.
This object should not be used in non-secure provisioning
modes. In non-secure provisioning modes, the MTA MUST
return an 'inconsistentValue' in response to SNMP SET
operations, and the MTA MUST return a zero value in

response to SNMP GET operations.
If a value is written into an instance of
pktcMtaDevProvSolicitedKeyTimeout, the agent MUST NOT
retain the supplied value across MTA re-initializations
or reboots."
DEFVAL { 3 }
::= { pktcMtaDevServer 14 }

```
--================================================================
--
--  Unsolicited key updates are retransmitted according to an
--  exponential back-off mechanism using two timers and a maximum
--  retry counter for AS replies.
--  The initial retransmission timer value is the nominal
 timer
--  value (pktcMtaDevProvUnsolicitedKeyNomTimeout).  The
--  retransmissions occur with an exponentially increasing interval
--  that caps at the maximum timeout value
--  (pktcMtaDevProvUnsolicitedKeyMaxTimeout).
--  Retransmissions stop when the maximum retry counter is reached
--  (pktcMtaDevProvUnsolicitedKeyMaxRetries).
--  For example, with values of 3 seconds for the nominal
--  timer, 100 seconds for the maximum timeout, and 8 retries max,
--  and with an exponential value of 2, this results in
--  retransmission intervals will be 3 s, 6 s, 12 s, 24 s, 48 s,
--  96 s, 100 s, and 100 s;
--  retransmissions then stop because the maximum number of
--  retries (8) has been reached.
--
--================================================================
--
--  Timeouts for unsolicited key management updates are only
--  pertinent before the first SNMPv3 message is sent between the
--  MTA and the Provisioning Server and before the configuration
--  file is loaded.
--
--================================================================

pktcMtaDevProvUnsolicitedKeyMaxTimeout
 OBJECT-TYPE
  SYNTAX      Unsigned32 (0..600)
  UNITS       "seconds"
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object defines the timeout value that applies to
       an MTA-initiated AP-REQ/REP key management exchange with
       the Provisioning Server in SNMPv3 provisioning.
       It is the maximum timeout value, and it may not be exceeded
       in the exponential back-off algorithm.  If the DHCP option




       code 122, sub-option 5, is provided to the MTA, it
       overwrites this value.
       In non-secure provisioning modes, the MTA MUST
```

```
        return a zero value in response to SNMP GET
        operations."
    REFERENCE
       " PacketCable Security Specification."
    DEFVAL {600}
    ::= { pktcMtaDevServer 15 }

pktcMtaDevProvUnsolicitedKeyNomTimeout  OBJECT-TYPE
    SYNTAX      Unsigned32 (0..600)
     UNITS       "seconds"
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       " This object defines the starting value of the timeout
        for the AP-REQ/REP Backoff and Retry mechanism
        with exponential timeout in SNMPv3 provisioning.
        If the DHCP option code 122, sub-option 5, is provided
        the MTA, it overwrites this value.
        In non-secure provisioning modes, the MTA MUST
        return a zero value in response to SNMP GET
        operations."
    REFERENCE
       " PacketCable Security Specification."
    DEFVAL {3}
    ::= { pktcMtaDevServer 16}

pktcMtaDevProvUnsolicitedKeyMaxRetries  OBJECT-TYPE
    SYNTAX      Unsigned32 (0..32)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
       " This object contains a retry counter that applies to
        an MTA-initiated AP-REQ/REP key management exchange with
        the Provisioning Server in secure SNMPv3 provisioning.
        It is the maximum
 number of retries before the MTA stops
        attempting to establish a Security Association with
        Provisioning Server.
        If the DHCP option code 122, sub-option 5, is provided to
        the MTA, it overwrites this value.
        If this object is set to a zero value, the MTA MUST return
        an 'inconsistentValue' in response to SNMP SET operations.
        In non-secure provisioning modes, the MTA MUST
        return a zero value in response to SNMP GET
        operations."
    REFERENCE
```

```
      " PacketCable Security Specification."
  DEFVAL {8}
  ::= { pktcMtaDevServer 17 }

pktcMtaDevProvKerbRealmName  OBJECT-TYPE
  SYNTAX      SnmpAdminString (SIZE(1..255))
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      " This object contains the name of the associated
        provisioning Kerberos realm acquired during the MTA4
        provisioning step (DHCP Ack) for SNMPv3 provisioning.
        The uppercase ASCII representation
 of the associated
        Kerberos realm name MUST be used by both the Manager (SNMP
        entity) and the MTA.
        The Kerberos realm name for the Provisioning Server is
        supplied to the MTA via DHCP option code 122, sub-option 6,
        as defined in RFC 3495.  In secure SNMP provisioning mode,
        the value of the Kerberos realm name for the Provisioning
        Server supplied in the MTA configuration file must match
        the value supplied in the DHCP option code 122,
        sub-option 6.  Otherwise, the value of this object must
        contain the value supplied in DHCP Option 122,
        sub-option 6."
  REFERENCE
      " PacketCable MTA Device Provisioning Specification;
        RFC 3495, DHCP Option for CableLabs Client Configuration."
  ::= { pktcMtaDevServer 18 }

pktcMtaDevProvState  OBJECT-TYPE
  SYNTAX      INTEGER  {
              operational              (1),
              waitingForSnmpSetInfo
     (2),
              waitingForTftpAddrResponse (3),
              waitingForConfigFile       (4)
  }
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
      " This object defines the MTA provisioning state.
        If the state is:

          'operational(1)', the device has completed the loading
           and processing of the initialization parameters.
```

'waitingForSnmpSetInfo(2)', the device is waiting on
its configuration file download access information.
Note that this state is only reported when the MTA

SNMP enrollment mechanism is used.

'waitingForTftpAddrResponse(3)', the device has sent a
DNS request to resolve the server providing the
configuration file, and it is awaiting for a response.
Note that this state is only reported when the MTA
SNMP enrollment mechanism is used.

'waitingForConfigFile(4)', the device has
sent a
request via TFTP or HTTP for the download of its
configuration file, and it is awaiting for a response or
the file download is in progress."
REFERENCE
" PacketCable MTA Device Provisioning Specification,
PacketCable Security Specification."
::= { pktcMtaDevServer 19 }

--
-- The following object group describes the security objects.
--

pktcMtaDevManufacturerCertificate OBJECT-TYPE
SYNTAX DocsX509ASN1DEREncodedCertificate
MAX-ACCESS read-only
STATUS current
DESCRIPTION
" This object contains the MTA Manufacturer Certificate.
The object value must be the ASN.1 DER encoding of the MTA
manufacturer's X.509 public key certificate. The MTA
Manufacturer Certificate is issued to each MTA
manufacturer and is installed into each MTA at the time of
manufacture or with a secure code download. The specific
requirements
related to this certificate are defined in
the PacketCable or IPCablecom Security specifications."
REFERENCE
" PacketCable Security Specification."

::= {pktcMtaDevSecurity 1}

pktcMtaDevCertificate OBJECT-TYPE

```
  SYNTAX      DocsX509ASN1DEREncodedCertificate
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object contains the MTA Device Certificate.
       The object value must be the ASN.1 DER encoding of the
       MTA's X.509 public-key certificate issued by the
       manufacturer and installed into the MTA at the time of




       manufacture or with a secure code download.
       This certificate contains the MTA MAC address.  The
       specific requirements related to this certificate are
       defined in the PacketCable or IPCablecom Security
       specifications."
  REFERENCE
     " PacketCable Security Specification."
  ::= { pktcMtaDevSecurity 2 }

pktcMtaDevCorrelationId  OBJECT-TYPE
   SYNTAX      Unsigned32
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object contains a correlation ID, an arbitrary value
       generated by the MTA that will be exchanged as part of the
       device capability data to the Provisioning Application.
       This random value is used as an identifier to correlate
       related events in the MTA provisioning sequence.
       This value is intended for use only during the MTA
       initialization and configuration file download."
  REFERENCE
     " PacketCable MTA Device Provisioning Specification."
  ::= { pktcMtaDevSecurity 3 }

pktcMtaDevTelephonyRootCertificate  OBJECT-TYPE
  SYNTAX      DocsX509ASN1DEREncodedCertificate
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object contains the telephony Service Provider Root
       certificate.  The object value is the ASN.1 DER encoding of
       the IP Telephony Service Provider
 Root X.509 public key
       certificate.  This certification is stored in the MTA
       non-volatile memory and can be updated with a secure code
       download.  This certificate is used to validate the initial
```

```
        AS Reply received by the MTA from the Key Distribution
        Center (KDC) during the MTA initialization.  The specific
        requirements related to this certificate are defined in
        the PacketCable or IPCablecom Security specifications."
    REFERENCE
       " PacketCable Security Specification."
    ::= { pktcMtaDevSecurity 4 }

--================================================================
--
--   Informative Procedures for Setting up Security Associations
--




--   A Security Association may be set up either via configuration or
--   via NCS signaling.
--
--   I.   Security association setup via configuration.
--
--   The realm must be configured first.  Associated with the realm
--   is a KDC.  The realm table (pktcMtaDevRealmTable)
 indicates
--   information about the realm (e.g., name, organization name) and
--   parameters associated with KDC communications (e.g., grace
--   periods, AS Request/AS Reply adaptive back-off parameters).
--
--   Once the realm is established, one or more CMS(es) may be
--   defined in the realm.  Associated with each CMS
--   entry in the pktcMtaDevCmsTable is an explicit reference
--   to a Realm via the realm name (pktcMtaDevCmsKerbRealmName),
--   the FQDN of the CMS, and parameters associated with IPSec
--   key management with the CMS (e.g., clock skew, AP Request/
--   AP Reply adaptive back-off parameters).
--
--   II.  Security association setup via NCS signaling.
--
--   The procedure of establishing the Security Associations
--   for NCS signaling is described in the PacketCable Security
--   specification.
--   It involves the analysis of the pktcNcsEndPntConfigTable row
--   for the corresponding endpoint number and the correlation of
--   the CMS FQDN from this row
 with the CMS Table and
--   consequently, with the Realm Table.  Both of these tables
--   are defined below.  The pktcNcsEndPntConfigTable is defined in
--   the IP over Cable Data Network (IPCDN)
--   NCS Signaling MIB [NCSSIGMIB].
```

```
--
--  III.  When the MTA receives wake-up or re-key messages from a
--  CMS, it performs key management based on the corresponding
--  entry in the CMS table.  If the matching CMS entry does not
--  exist, it must ignore the wake-up or re-key messages.
--
--================================================================
--================================================================
--
--  pktcMtaDevRealmTable
--
--  The pktcMtaDevRealmTable shows the KDC realms.  The table is
--  indexed with pktcMtaDevRealmIndex.  The Realm Table contains the
--  pktcMtaDevRealmName in conjunction with any server that needs
--  a Security Association with the MTA.  Uppercase must be used
--  to compare the pktcMtaDevRealmName content.
--



--================================================================

pktcMtaDevRealmAvailSlot
  OBJECT-TYPE
  SYNTAX      Unsigned32 (0..64)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object contains the index number of the first
       available entry in the realm table (pktcMtaDevRealmTable).
       If all the entries in the realm table have been assigned,
       this object contains the value of zero.
       A management station should create new entries in the
       realm table, using the following procedure:

       First, issue a management protocol retrieval operation
       to determine the value of the first available index in the
       realm table (pktcMtaDevRealmAvailSlot).

       Second, issue a management protocol SET operation
       to create an instance of the pktcMtaDevRealmStatus
       object by setting its value to 'createAndWait(5)'.

       Third, if the SET operation succeeded, continue

  modifying the object instances corresponding to the newly
       created conceptual row, without fear of collision with
       other management stations.  When all necessary conceptual
```

```
        columns of the row are properly populated (via SET
        operations or default values), the management station may
        SET the pktcMtaDevRealmStatus object to 'active(1)'."
    ::= {  pktcMtaDevSecurity 5 }

pktcMtaDevRealmTable  OBJECT-TYPE
    SYNTAX      SEQUENCE OF PktcMtaDevRealmEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
       " This object contains the realm table.
        The CMS table (pktcMtaDevCmsTable) and the realm table
        (pktcMtaDevRealmTable) are used for managing the MTA-CMS
        Security Associations.  The realm table defines the
        Kerberos realms for the Application Servers (CMSes and the
        Provisioning Server)."
    ::= {  pktcMtaDevSecurity 6 }

pktcMtaDevRealmEntry  OBJECT-TYPE
    SYNTAX
     PktcMtaDevRealmEntry
    MAX-ACCESS  not-accessible
    STATUS      current



    DESCRIPTION
       " This table entry object lists the MTA security parameters
        for a single Kerberos realm.  The conceptual rows MUST NOT
        persist across MTA reboots."
    INDEX { pktcMtaDevRealmIndex }
::= { pktcMtaDevRealmTable 1 }

PktcMtaDevRealmEntry ::= SEQUENCE {
    pktcMtaDevRealmIndex                  Unsigned32,
    pktcMtaDevRealmName                   SnmpAdminString,
    pktcMtaDevRealmPkinitGracePeriod      Unsigned32,
    pktcMtaDevRealmTgsGracePeriod         Unsigned32,
    pktcMtaDevRealmOrgName                LongUtf8String,
    pktcMtaDevRealmUnsolicitedKeyMaxTimeout Unsigned32,
    pktcMtaDevRealmUnsolicitedKeyNomTimeout Unsigned32,
    pktcMtaDevRealmUnsolicitedKeyMaxRetries Unsigned32,
    pktcMtaDevRealmStatus                 RowStatus
    }

pktcMtaDevRealmIndex  OBJECT-TYPE
    SYNTAX      Unsigned32 (1..64)
    MAX-ACCESS  not-accessible
```

```
  STATUS
    current
  DESCRIPTION
      " This object defines the realm table index."
  ::= { pktcMtaDevRealmEntry 1}

pktcMtaDevRealmName  OBJECT-TYPE
  SYNTAX      SnmpAdminString (SIZE(1..255))
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      " This object identifies the Kerberos realm name in all
        capitals.  The MTA MUST prohibit the instantiation of any
        two rows with identical Kerberos realm names.  The MTA MUST
        also verify that any search operation involving Kerberos
        realm names is done using the uppercase ASCII
        representation of the characters."
  ::= { pktcMtaDevRealmEntry 2 }

pktcMtaDevRealmPkinitGracePeriod  OBJECT-TYPE
  SYNTAX      Unsigned32 (15..600)
  UNITS       "minutes"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
      " This object contains the PKINIT Grace Period.  For the
        purpose of key management with Application Servers (CMSes




        or
 the Provisioning Server), the MTA must utilize the
        PKINIT exchange to obtain Application Server tickets.  The
        MTA may utilize the PKINIT exchange to obtain Ticket
        Granting Tickets (TGTs), which are then used to obtain
        Application Server tickets in a TGS exchange.
        The PKINIT exchange occurs according to the current Ticket
        Expiration Time (TicketEXP) and on the PKINIT Grace Period
        (PKINITGP).  The MTA MUST initiate the PKINIT exchange at
        the time: TicketEXP - PKINITGP."
  REFERENCE
      " PacketCable Security Specification."
  DEFVAL { 15 }
  ::= { pktcMtaDevRealmEntry 3 }

pktcMtaDevRealmTgsGracePeriod  OBJECT-TYPE
  SYNTAX      Unsigned32 (1..600)
  UNITS       "minutes"
```

```
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object contains the Ticket Granting Server Grace
       Period (TGSGP).  The Ticket Granting Server (TGS)
       Request/Reply exchange may be performed
 by the MTA
       on demand whenever an Application Server ticket is
       needed to establish security parameters.  If the MTA
       possesses a ticket that corresponds to the Provisioning
       Server or a CMS that currently exists in the CMS table,
       the MTA MUST initiate the TGS Request/Reply exchange
       at the time: TicketEXP - TGSGP."
  REFERENCE
     " PacketCable Security Specification."
  DEFVAL { 10 }
  ::= { pktcMtaDevRealmEntry 4 }

pktcMtaDevRealmOrgName  OBJECT-TYPE
  SYNTAX      LongUtf8String
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object contains the X.500 organization name attribute
       as defined in the subject name of the service provider
       certificate."
  REFERENCE
     " PacketCable Security Specification;
       RFCs 3280 and 4630, Internet X.509 Public Key
       Infrastructure Certificate and Certificate Revocation List
       (CRL) Profile"
   ::= { pktcMtaDevRealmEntry 5 }



pktcMtaDevRealmUnsolicitedKeyMaxTimeout  OBJECT-TYPE
  SYNTAX      Unsigned32 (1..600)
  UNITS       "seconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object specifies the maximum time the MTA will
       attempt to perform the exponential back-off algorithm.
       This timer only applies when the MTA initiated key
       management.  If the DHCP option code 122, sub-option 4, is
       provided to the MTA, it overwrites this value.
```

```
        Unsolicited key updates are retransmitted according to an
        exponential back-off mechanism using two timers and a
        maximum retry counter for AS replies.
        The initial retransmission timer value is the nominal
        timer value (pktcMtaDevRealmUnsolicitedKeyNomTimeout).  The
        retransmissions occur with an exponentially increasing
        interval that caps at the maximum timeout value
        (pktcMtaDevRealmUnsolicitedKeyMaxTimeout).
         Retransmissions stop when the maximum retry counter is
        reached (pktcMatDevRealmUnsolicitedMaxRetries).

        For example, with values of 3 seconds for the nominal
        timer, 20 seconds for the maximum timeout, and 5 retries
        max, retransmission intervals will be 3 s, 6 s,
        12 s, 20 s, and 20 s, and retransmissions then stop because
        the maximum number of retries has been reached."
    REFERENCE
       " PacketCable Security Specification."
    DEFVAL { 100 }
    ::= { pktcMtaDevRealmEntry 6 }

pktcMtaDevRealmUnsolicitedKeyNomTimeout  OBJECT-TYPE
    SYNTAX      Unsigned32 (100..600000)
    UNITS       "milliseconds"
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
       " This object specifies the initial timeout value
        for the AS-REQ/AS-REP exponential back-off and retry
        mechanism.  If the DHCP option code 122, sub-option 4, is
        provided to the MTA, it
 overwrites this value.
        This value should account for the average roundtrip
        time between the MTA and the KDC, as well as the
        processing delay on the KDC.




        Unsolicited key updates are retransmitted according to an
        exponential back-off mechanism using two timers and a
        maximum retry counter for AS replies.
        The initial retransmission timer value is the nominal
        timer value (pktcMtaDevRealmUnsolicitedKeyNomTimeout).  The
        retransmissions occur with an exponentially increasing
        interval that caps at the maximum timeout value
        (pktcMtaDevRealmUnsolicitedKeyMaxTimeout).
        Retransmissions stop when the maximum retry counter is
```

```
        reached (pktcMatDevRealmUnsolicitedMaxRetries).

        For example, with values of 3 seconds for the nominal
        timer, 20 seconds for the maximum timeout, and 5 retries
        max, in retransmission intervals will be 3 s, 6 s,

      12 s, 20 s, and 20 s; retransmissions then stop because
        the maximum number of retries has been reached."
    REFERENCE
      " PacketCable Security Specification."
    DEFVAL { 3000 }
    ::= { pktcMtaDevRealmEntry 7 }

pktcMtaDevRealmUnsolicitedKeyMaxRetries  OBJECT-TYPE
    SYNTAX      Unsigned32 (0..1024)
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
      " This object specifies the maximum number of retries the
        MTA attempts to obtain a ticket from the KDC.

        Unsolicited key updates are retransmitted according to an
        exponential back-off mechanism using two timers and a
        maximum retry counter for AS replies.
        The initial retransmission timer value is the nominal
        timer value (pktcMtaDevRealmUnsolicitedKeyNomTimeout).  The
        retransmissions occur with an exponentially increasing
        interval that caps at the maximum timeout value
        (pktcMtaDevRealmUnsolicitedKeyMaxTimeout).
         Retransmissions stop when the maximum retry counter is
        reached (pktcMatDevRealmUnsolicitedMaxRetries).

        For example, with values of 3 seconds for the nominal
        timer, 20 seconds for the maximum timeout, and 5 retries
        max, retransmission intervals will be 3 s, 6 s,
        12 s, 20 s, and 20 s; retransmissions then stop because
        the maximum number of retries has been reached."
    REFERENCE
      " PacketCable Security Specification."
    DEFVAL { 5 }



    ::= { pktcMtaDevRealmEntry 8 }

pktcMtaDevRealmStatus     OBJECT-TYPE
    SYNTAX      RowStatus
    MAX-ACCESS  read-create
```

```
  STATUS      current
  DESCRIPTION
      " This object defines the row status of this realm in the
        realm table (pktcMtaDevRealmTable).

        An entry in this table is not qualified for activation
        until the object instances of all corresponding columns
        have been initialized, either by default values, or
via
        explicit SET operations.  Until all object instances in
        this row are initialized, the status value for this realm
        must be 'notReady(3)'.
        In particular, two columnar objects must be explicitly
        SET: the realm name (pktcMtaDevRealmName) and the
        organization name (pktcMtaDevRealmOrgName).  Once these 2
        objects have been set and the row status is SET to
        'active(1)', the MTA MUST NOT allow any modification of
        these 2 object values.
        The value of this object has no effect on whether other
        columnar objects in this row can be modified."
  ::= { pktcMtaDevRealmEntry 9 }

--================================================================
--
--  The CMS table, pktcMtaDevCmsTable
--
-- The CMS table and the realm table (pktcMtaDevRealmTable) are used
-- for managing the MTA signaling security.  The CMS table defines
-- the CMSes the MTA is allowed to communicate with and contains
-- the
 parameters describing the SA establishment between the MTA
-- and a CMS.
-- The CMS table is indexed by pktcMtaDevCmsIndex.  The table
-- contains the CMS FQDN (pktcMtaDevCmsFQDN) and the associated
-- Kerberos realm name (pktcMtaDevCmsKerbRealmName) so that the MTA
-- can find the corresponding Kerberos realm name in the
-- pktcMtaDevRealmTable.
--
--================================================================

pktcMtaDevCmsAvailSlot   OBJECT-TYPE
  SYNTAX      Unsigned32 (0..128)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
```

" This object contains the index number of the first
available entry in the CMS table (pktcMtaDevCmsTable).
If all the entries in the CMS table have been assigned,
this object contains the value of zero.
A management station should create new entries in the
CMS table, using the following procedure:

First, issue a management protocol retrieval operation

to determine the value of the first available index in the
CMS table (pktcMtaDevCmsAvailSlot).

Second, issue a management protocol SET operation
to create an instance of the pktcMtaDevCmsStatus
object by setting its value to 'createAndWait(5)'.

Third, if the SET operation succeeded, continue
modifying the object instances corresponding to the newly
created conceptual row, without fear of collision with
other management stations. When all necessary conceptual
columns of the row are properly populated (via SET
operations or default values), the management station may
SET the pktcMtaDevCmsStatus object to 'active(1)'."
::= { pktcMtaDevSecurity 7 }

pktcMtaDevCmsTable OBJECT-TYPE
SYNTAX SEQUENCE OF PktcMtaDevCmsEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
" This object defines the CMS table.
The CMS table (pktcMtaDevCmsTable)
and the realm table
(pktcMtaDevRealmTable) are used for managing security
between the MTA and CMSes. Each CMS table entry defines
a CMS the managed MTA is allowed to communicate with
and contains security parameters for key management with
that CMS."
::= { pktcMtaDevSecurity 8 }

pktcMtaDevCmsEntry OBJECT-TYPE
SYNTAX PktcMtaDevCmsEntry
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
" This table entry object lists the MTA key management
parameters used when establishing Security Associations
with a CMS. The conceptual rows MUST NOT persist across

```
        MTA reboots."
    INDEX { pktcMtaDevCmsIndex }



    ::= { pktcMtaDevCmsTable 1 }

PktcMtaDevCmsEntry ::= SEQUENCE {
    pktcMtaDevCmsIndex                  Unsigned32,
    pktcMtaDevCmsFqdn                   SnmpAdminString,
    pktcMtaDevCmsKerbRealmName          SnmpAdminString,
    pktcMtaDevCmsMaxClockSkew
                Unsigned32,
    pktcMtaDevCmsSolicitedKeyTimeout    Unsigned32,
    pktcMtaDevCmsUnsolicitedKeyMaxTimeout   Unsigned32,
    pktcMtaDevCmsUnsolicitedKeyNomTimeout   Unsigned32,
    pktcMtaDevCmsUnsolicitedKeyMaxRetries   Unsigned32,
    pktcMtaDevCmsIpsecCtrl              TruthValue,
    pktcMtaDevCmsStatus                 RowStatus
    }

pktcMtaDevCmsIndex  OBJECT-TYPE
    SYNTAX      Unsigned32 (1..128)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        " This object defines the CMS table index."
    ::= { pktcMtaDevCmsEntry 1 }

pktcMtaDevCmsFqdn  OBJECT-TYPE
    SYNTAX      SnmpAdminString (SIZE(1..255))
    MAX-ACCESS  read-create
    STATUS      current
    DESCRIPTION
        " This object specifies the CMS FQDN.  The MTA must
          prohibit the instantiation of any two rows with identical
          FQDNs.  The MTA must also verify that any search and/or
          comparison operation
   involving a CMS FQDN is case
          insensitive.  The MTA must resolve the CMS FQDN as required
           by the corresponding PacketCable Specifications."
    REFERENCE
        " PacketCable MTA Device Provisioning Specification;
          PacketCable Security Specification;
          PacketCable Network-Based Call Signaling Protocol
          Specification."
    ::= { pktcMtaDevCmsEntry 2 }
```

```
pktcMtaDevCmsKerbRealmName  OBJECT-TYPE
  SYNTAX      SnmpAdminString (SIZE(1..255))
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object identifies the Kerberos realm name in uppercase
       characters associated with the CMS defined in this




       conceptual row.  The object value is a reference
       point to the corresponding Kerberos realm name in the
       realm table (pktcMtaDevRealmTable)."
  ::= { pktcMtaDevCmsEntry 3 }

pktcMtaDevCmsMaxClockSkew    OBJECT-TYPE
  SYNTAX      Unsigned32 (1..1800)
  UNITS       "seconds"
   MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object specifies the maximum allowable clock skew
       between the MTA and the CMS defined in this row."
  DEFVAL { 300 }
  ::= { pktcMtaDevCmsEntry 4 }

pktcMtaDevCmsSolicitedKeyTimeout  OBJECT-TYPE
  SYNTAX      Unsigned32 (100..30000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object defines a Kerberos Key Management timer on the
       MTA.  It is the time period during which the MTA saves the
       nonce and Server Kerberos Principal Identifier to match an
       AP Request and its associated AP Reply response from the
       CMS.  This timer only applies when the CMS initiated key
       management (with a Wake Up message or a Rekey message)."
  REFERENCE
     " PacketCable Security Specification."
  DEFVAL { 1000 }
  ::= { pktcMtaDevCmsEntry 5 }

--================================================================
--
--
 Unsolicited key updates are retransmitted according to an
--  exponential back-off mechanism using two timers and a maximum
```

```
-- retry counter for AS replies.
-- The initial retransmission timer value is the nominal timer
-- value (pktcMtaDevCmsUnsolicitedKeyNomTimeout).  The
-- retransmissions occur with an exponentially increasing interval
-- that caps at the maximum timeout value
-- (pktcMtaDevCmsUnsolicitedKeyMaxTimeout).
-- Retransmissions stop when the maximum retry counter is reached
-- (pktcMatDevCmsUnsolicitedMaxRetries).
-- For example, with values of 3 seconds for the nominal
-- timer, 20 seconds for the maximum timeout, and 5 retries max,
-- retransmission intervals will be 3 s, 6 s, 12 s,



-- 20 s, and 20 s; retransmissions then stop due to the
-- maximum number of retries reached.
--
--================================================================

pktcMtaDevCmsUnsolicitedKeyMaxTimeout  OBJECT-TYPE
  SYNTAX      Unsigned32 (1..600)
   UNITS       "seconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object defines the timeout value that only applies
       to an MTA-initiated key management exchange.  It is the
       maximum timeout, and it may not be exceeded in the
       exponential back-off algorithm."
  REFERENCE
     " PacketCable Security Specification."
  DEFVAL { 600 }
  ::= { pktcMtaDevCmsEntry 6 }

pktcMtaDevCmsUnsolicitedKeyNomTimeout  OBJECT-TYPE
  SYNTAX      Unsigned32 (100..30000)
  UNITS       "milliseconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object defines the starting value of the timeout
       for an MTA-initiated key management.  It should account for
       the average roundtrip time between the MTA and the CMS and
       the processing time on the CMS."
  REFERENCE
     " PacketCable Security Specification."
  DEFVAL { 500 }
  ::= { pktcMtaDevCmsEntry 7 }
```

```
pktcMtaDevCmsUnsolicitedKeyMaxRetries
 OBJECT-TYPE
  SYNTAX      Unsigned32 (0..1024)
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object contains the maximum number of retries before
       the MTA stops attempting to establish a Security
       Association with the CMS."
  REFERENCE
     " PacketCable Security Specification."
  DEFVAL { 5 }
  ::= { pktcMtaDevCmsEntry 8 }



pktcMtaDevCmsIpsecCtrl     OBJECT-TYPE
  SYNTAX        TruthValue
  MAX-ACCESS    read-only
  STATUS        current
  DESCRIPTION
     " This object specifies the MTA IPSec control flag.
       If the object value is 'true', the MTA must use Kerberos
       Key Management and IPsec to communicate with this CMS.  If
       it is 'false', IPSec Signaling Security and Kerberos key
       management are disabled for this specific CMS."
  DEFVAL { true }
  ::= { pktcMtaDevCmsEntry 9 }

pktcMtaDevCmsStatus     OBJECT-TYPE
  SYNTAX
 RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object defines the row status associated with this
       particular CMS in the CMS table (pktcMtaDevCmsTable).

       An entry in this table is not qualified for activation
       until the object instances of all corresponding columns
       have been initialized, either by default values or via
       explicit SET operations.  Until all object instances in
       this row are initialized, the status value for this realm
       must be 'notReady(3)'.
       In particular, two columnar objects must be SET: the
       CMS FQDN (pktcMtaDevCmsFqdn) and the Kerberos realm name
```

(pktcMtaDevCmsKerbRealmName). Once these 2 objects have
been set and the row status is SET to 'active(1)', the MTA
MUST NOT allow any modification of these 2 object values.

The value of this object has no effect on
whether other columnar objects
in this row can be
modified."
::= { pktcMtaDevCmsEntry 10 }

pktcMtaDevResetKrbTickets OBJECT-TYPE
SYNTAX BITS {
invalidateProvOnReboot (0),
invalidateAllCmsOnReboot (1)
}
MAX-ACCESS read-write
STATUS current
DESCRIPTION
" This object defines a Kerberos Ticket Control Mask that
instructs the MTA to invalidate the specific Application

Server Kerberos ticket(s) that are stored locally in the
MTA NVRAM (non-volatile or persistent memory).
If the MTA does not store Kerberos tickets in NVRAM, it
MUST ignore setting of this object and MUST report a BITS
value of zero when the object is read.
If the MTA supports Kerberos tickets storage in NVRAM, the
object value is encoded as follows:
- Setting the invalidateProvOnReboot bit (bit 0) to 1
means that the MTA MUST invalidate
the Kerberos
Application Ticket(s) for the Provisioning Application
at the next MTA reboot if secure SNMP provisioning mode
is used. In non-secure provisioning modes, the MTA MUST
return an 'inconsistentValue' in response to SNMP SET
operations with a bit 0 set to 1.
- Setting the invalidateAllCmsOnReboot bit (bit 1) to 1
means that the MTA MUST invalidate the Kerberos
Application Ticket(s) for all CMSes currently assigned
to the MTA endpoints.
If a value is written into an instance of
pktcMtaDevResetKrbTickets, the agent MUST retain the
supplied value across an MTA re-initialization or
reboot."
REFERENCE
"PacketCable Security Specification."

```
  DEFVAL { {   } }
  ::= {  pktcMtaDevSecurity 9 }

--
-- The following group, pktcMtaDevErrors, defines an OID
-- corresponding to error conditions encountered during the MTA
-- provisioning.
--

pktcMtaDevErrorsTooManyErrors
 OBJECT-IDENTITY
  STATUS     current
  DESCRIPTION
     "This object defines the OID corresponding to the error
      condition when too many errors are encountered in the
      MTA configuration file during provisioning."
    ::= { pktcMtaDevErrors  1 }

pktcMtaDevProvisioningEnrollment  NOTIFICATION-TYPE
  OBJECTS {
         sysDescr,
         pktcMtaDevSwCurrentVers,
         pktcMtaDevTypeIdentifier,
         ifPhysAddress,
         pktcMtaDevCorrelationId




  }
  STATUS   current
  DESCRIPTION
     " This INFORM notification is issued by the MTA to initiate
       the PacketCable provisioning process when the MTA SNMP
       enrollment mechanism is used.
       It contains the system description, the current software
       version, the MTA device type identifier, the MTA MAC
       address (obtained in the MTA ifTable in the ifPhysAddress
       object that corresponds to the ifIndex
 1), and a
       correlation ID."
  ::= { pktcMtaNotification 1 }

pktcMtaDevProvisioningStatus  NOTIFICATION-TYPE
  OBJECTS {
         ifPhysAddress,
         pktcMtaDevCorrelationId,
         pktcMtaDevProvisioningState
  }
```

```
  STATUS      current
  DESCRIPTION
      " This INFORM notification may be issued by the MTA to
        confirm the completion of the PacketCable provisioning
        process, and to report its provisioning completion
        status.
        It contains the MTA MAC address (obtained in the MTA
        ifTable in the ifPhysAddress object that corresponds
        to the ifIndex 1), a correlation ID and the MTA
        provisioning state as defined in
        pktcMtaDevProvisioningState."
  ::= { pktcMtaNotification 2 }

--
-- Compliance Statements
--

pktcMtaCompliances  OBJECT IDENTIFIER ::= { pktcMtaConformance 1 }
pktcMtaGroups       OBJECT IDENTIFIER ::= { pktcMtaConformance 2 }

pktcMtaBasicCompliance MODULE-COMPLIANCE
   STATUS      current
  DESCRIPTION
      " The compliance statement for MTA devices that implement
        PacketCable or IPCablecom requirements.

        This compliance statement applies to MTA implementations
        that support PacketCable 1.0 or IPCablecom requirements,
        which are not IPv6-capable at the time of this




        RFC publication."

  MODULE  -- Unconditionally mandatory groups for MTAs

      MANDATORY-GROUPS {
         pktcMtaGroup,
         pktcMtaNotificationGroup
      }

      OBJECT  pktcMtaDevDhcpServerAddressType
         SYNTAX      InetAddressType { ipv4(1) }
         DESCRIPTION
            " Support for address types other than 'ipv4(1)'
         is not presently specified and therefore is not
         required.  It may be defined in future versions of
         this MIB module."
```

OBJECT pktcMtaDevDnsServerAddressType
SYNTAX InetAddressType { ipv4(1) }

DESCRIPTION
" Support for address types other than 'ipv4(1)'
is not presently specified and therefore is not
required. It may be defined in future versions of
this MIB module."

OBJECT pktcMtaDevTimeServerAddressType
SYNTAX InetAddressType { ipv4(1) }
DESCRIPTION
" Support for address types other than 'ipv4(1)'
is not presently specified and therefore is not
required. It may be defined in future versions of
this MIB module."

OBJECT pktcMtaDevServerDhcp1
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4
addresses. Other address types support may be defined in
future versions of this MIB module."

OBJECT pktcMtaDevServerDhcp2
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation
is only required to support IPv4
addresses. Other address types support may be defined in
future versions of this MIB module."

OBJECT pktcMtaDevServerDns1

SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4
addresses. Other address types support may be defined in
future versions of this MIB module."

OBJECT pktcMtaDevServerDns2
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4
addresses. Other address types support may be defined in

future versions of this MIB module."

OBJECT pktcMtaDevTimeServer
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4
addresses. Other address types support may be defined in
future versions of this MIB module."

OBJECT pktcMtaDevProvConfigEncryptAlg
SYNTAX PktcMtaDevProvEncryptAlg
DESCRIPTION
"An implementation is only required to support
values of none(0) and des64Cbcmode(1).
An IV of zero is used to encrypt in des64Cbcmode, and
the length of pktcMtaDevProvConfigKey is 64 bits, as
defined in the PacketCable Security specification.
Other encryption types may be defined in future
versions of this MIB module."

OBJECT pktcMtaDevRealmOrgName
SYNTAX LongUtf8String (SIZE (1..384))
DESCRIPTION
"The Organization Name field in X.509 certificates
can contain up to 64 UTF-8 encoded characters,
as defined in RFCs 3280 and 4630. Therefore, compliant
devices are only required to support Organization
Name values of up to 64 UTF-8 encoded characters.
Given that RFCs 3280 and 4630 define the UTF-8 encoding,
compliant devices must support a maximum size of 384
octets for pktcMtaDevRealmOrgName. The calculation of
384 octets comes from the RFC 3629 UTF-8 encoding
definition whereby the UTF-8 encoded characters
are encoded as sequences of 1 to 6 octets,
assuming that code points as high as 0x7fffffff
might be used. Subsequent versions of Unicode and ISO
10646 have limited the upper bound to 0x10ffff.

Consequently, the current version of UTF-8, defined in
RFC 3629, does not require more than four octets to
encode a valid code point."

::= { pktcMtaCompliances 1 }

pktcMtaGroup OBJECT-GROUP
OBJECTS {

pktcMtaDevResetNow,
pktcMtaDevSerialNumber,
pktcMtaDevSwCurrentVers,
pktcMtaDevFQDN,
pktcMtaDevEndPntCount,

pktcMtaDevEnabled,
pktcMtaDevProvisioningCounter,
pktcMtaDevErrorOid,
pktcMtaDevErrorValue,
pktcMtaDevErrorReason,
pktcMtaDevTypeIdentifier,
pktcMtaDevProvisioningState,
pktcMtaDevHttpAccess,
pktcMtaDevCertificate,
pktcMtaDevCorrelationId,
pktcMtaDevManufacturerCertificate,
pktcMtaDevDhcpServerAddressType,
pktcMtaDevDnsServerAddressType,
pktcMtaDevTimeServerAddressType,
pktcMtaDevProvConfigEncryptAlg,
pktcMtaDevServerDhcp1,
pktcMtaDevServerDhcp2,
pktcMtaDevServerDns1,
pktcMtaDevServerDns2,
pktcMtaDevTimeServer,
pktcMtaDevConfigFile,
pktcMtaDevSnmpEntity,
pktcMtaDevRealmPkinitGracePeriod,
pktcMtaDevRealmTgsGracePeriod,
pktcMtaDevRealmAvailSlot,
pktcMtaDevRealmName,
pktcMtaDevRealmOrgName,
pktcMtaDevRealmUnsolicitedKeyMaxTimeout,
pktcMtaDevRealmUnsolicitedKeyNomTimeout,
pktcMtaDevRealmUnsolicitedKeyMaxRetries,
pktcMtaDevRealmStatus,
pktcMtaDevCmsAvailSlot,
pktcMtaDevCmsFqdn,
pktcMtaDevCmsKerbRealmName,
pktcMtaDevCmsUnsolicitedKeyMaxTimeout,

pktcMtaDevCmsUnsolicitedKeyNomTimeout,
pktcMtaDevCmsUnsolicitedKeyMaxRetries,
pktcMtaDevCmsSolicitedKeyTimeout,
pktcMtaDevCmsMaxClockSkew,

```
        pktcMtaDevCmsIpsecCtrl,
        pktcMtaDevCmsStatus,
        pktcMtaDevResetKrbTickets,
        pktcMtaDevProvUnsolicitedKeyMaxTimeout,
        pktcMtaDevProvUnsolicitedKeyNomTimeout,
        pktcMtaDevProvUnsolicitedKeyMaxRetries,
        pktcMtaDevProvKerbRealmName,
        pktcMtaDevProvSolicitedKeyTimeout,
        pktcMtaDevProvConfigHash,
        pktcMtaDevProvConfigKey,
        pktcMtaDevProvState,
         pktcMtaDevProvisioningTimer,
        pktcMtaDevTelephonyRootCertificate
  }
  STATUS      current
  DESCRIPTION
     " A collection of objects for managing PacketCable or
      IPCablecom MTA implementations."
  ::= { pktcMtaGroups 1 }

pktcMtaNotificationGroup          NOTIFICATION-GROUP
  NOTIFICATIONS {
             pktcMtaDevProvisioningStatus,
             pktcMtaDevProvisioningEnrollment
  }
  STATUS      current
  DESCRIPTION
     " A collection of notifications dealing with the change of
       MTA provisioning status."
  ::= { pktcMtaGroups 2 }

pktcMtaBasicSmtaCompliance MODULE-COMPLIANCE
  STATUS      current
  DESCRIPTION
     " The compliance statement for S-MTA devices
       that implement PacketCable or IPCablecom requirements.

       This compliance statement applies to S-MTA implementations
       that support PacketCable or IPCablecom requirements,
       which are not IPv6-capable
 at the time of this
       RFC publication."

  MODULE -- Unconditionally Mandatory Groups for S-MTA devices
     MANDATORY-GROUPS {
```

```
        pktcMtaGroup,
        pktcMtaNotificationGroup
    }

    OBJECT  pktcMtaDevDhcpServerAddressType
        SYNTAX      InetAddressType { ipv4(1) }
        DESCRIPTION
            " Support for address types other than 'ipv4(1)'
        is not presently specified and therefore is not
        required.  It may be defined in future versions of
        this MIB module."

    OBJECT  pktcMtaDevDnsServerAddressType
        SYNTAX      InetAddressType { ipv4(1) }
        DESCRIPTION
            " Support for address types other than 'ipv4(1)'
        is not presently specified and therefore is not
        required.  It may be defined in future versions of
        this MIB module."

    OBJECT  pktcMtaDevTimeServerAddressType
        SYNTAX      InetAddressType { ipv4(1)
}
        DESCRIPTION
            " Support for address types other than 'ipv4(1)'
        is not presently specified and therefore is not
        required.  It may be defined in future versions of
        this MIB module."

    OBJECT    pktcMtaDevServerDhcp1
        SYNTAX  InetAddress (SIZE(4))
        DESCRIPTION
            "An implementation is only required to support IPv4
        addresses.  Other address types support may be defined in
        future versions of this MIB module."

    OBJECT    pktcMtaDevServerDhcp2
        SYNTAX  InetAddress (SIZE(4))
        DESCRIPTION
            "An implementation is only required to support IPv4
        addresses.  Other address types support may be defined in
        future versions of this MIB module."

    OBJECT    pktcMtaDevServerDns1
        SYNTAX  InetAddress (SIZE(4))
        DESCRIPTION
            "An implementation is only required
```

to support IPv4
addresses. Other address types support may be defined in
future versions of this MIB module."

OBJECT pktcMtaDevServerDns2
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4
addresses. Other address types support may be defined in
future versions of this MIB module."

OBJECT pktcMtaDevTimeServer
SYNTAX InetAddress (SIZE(4))
DESCRIPTION
"An implementation is only required to support IPv4
addresses. Other address types support may be defined in
future versions of this MIB module."

OBJECT pktcMtaDevProvConfigEncryptAlg
SYNTAX PktcMtaDevProvEncryptAlg
DESCRIPTION
"An implementation is only required to support
values of none(0) and des64Cbcmode(1).
An IV of zero is used to encrypt
in des64Cbcmode, and
the length of pktcMtaDevProvConfigKey is 64 bits, as
defined in the PacketCable Security specification.
Other encryption types may be defined in future
versions of this MIB module."

OBJECT pktcMtaDevRealmOrgName
SYNTAX LongUtf8String (SIZE (1..384))
DESCRIPTION
"The Organization Name field in X.509 certificates
can contain up to 64 UTF-8 encoded characters, as
defined in RFCs 3280 and 4630. Therefore, compliant
devices are only required to support Organization
Name values of up to 64 UTF-8 encoded characters.
Given that RFCs 3280 and 4630 define the UTF-8 encoding,
compliant devices must support a maximum size of 384
octets for pktcMtaDevRealmOrgName. The calculation of
384 octets comes from the RFC 3629 UTF-8 encoding
definition whereby the UTF-8 encoded
characters
are encoded as sequences of 1 to 6 octets,

```
        assuming that code points as high as 0x7fffffff
        might be used.  Subsequent versions of Unicode and ISO
        10646 have limited the upper bound to 0x10ffff.
        Consequently, the current version of UTF-8, defined in
        RFC 3629 does not require more than four octets to
        encode a valid code point."
  MODULE DOCS-CABLE-DEVICE-MIB
    MANDATORY-GROUPS {



        docsDevSoftwareGroupV2
    }

  MODULE DOCS-IETF-BPI2-MIB
    MANDATORY-GROUPS {
        docsBpi2CodeDownloadGroup
    }

   ::= { pktcMtaCompliances 2 }

END
```

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/PKTC-IETF-MTA-MIB
No license file was found, but licenses were detected in source scan.

```
PKTC-IETF-SIG-MIB DEFINITIONS ::= BEGIN

IMPORTS
  MODULE-IDENTITY,
  OBJECT-TYPE,
  Integer32,
  Unsigned32,
  mib-2
      FROM SNMPv2-SMI                -- [RFC2578]
  InetAddressType,
  InetAddress,
  InetPortNumber
      FROM INET-ADDRESS-MIB          -- [RFC4001]
  TEXTUAL-CONVENTION,
  RowStatus,
  TruthValue
      FROM SNMPv2-TC                 -- [RFC2579]



  OBJECT-GROUP,
```

```
  MODULE-COMPLIANCE
      FROM SNMPv2-CONF                -- [RFC2580]
  SnmpAdminString
      FROM SNMP-FRAMEWORK-MIB         -- [RFC3411]
  ifIndex
      FROM IF-MIB                     -- [RFC2863]
  Dscp
      FROM DIFFSERV-DSCP-TC;          -- [RFC3289]

pktcIetfSigMib MODULE-IDENTITY
  LAST-UPDATED    "200712180000Z" -- December 18, 2007
  ORGANIZATION    "IETF IPCDN Working Group"
  CONTACT-INFO
     "Sumanth Channabasappa
      Cable Television
 Laboratories, Inc.
      858 Coal Creek Circle,
      Louisville, CO 80027, USA
      Phone: +1 303-661-3307
      Email: Sumanth@cablelabs.com

      Gordon Beacham
      Motorola, Inc.
      6450 Sequence Drive, Bldg. 1
      San Diego, CA 92121, USA
      Phone: +1 858-404-2334
      Email: gordon.beacham@motorola.com

      Satish Kumar Mudugere Eswaraiah
      Texas Instruments India (P) Ltd.,
      Golf view, Wind Tunnel Road
      Murugesh Palya
      Bangalore 560 017, INDIA
      Phone:   +91 80 5269451
      Email:  satish.kumar@ti.com

  IETF IPCDN Working Group
      General Discussion: ipcdn@ietf.org
      Subscribe: http://www.ietf.org/mailman/listinfo/ipcdn
      Archive: ftp://ftp.ietf.org/ietf-mail-archive/ipcdn
      Co-Chair: Jean-Francois Mule, jf.mule@cablelabs.com
      Co-Chair: Richard Woundy, Richard_Woundy@cable.comcast.com"

  DESCRIPTION
     "This MIB module supplies the basic management
      objects for the PacketCable and IPCablecom Signaling
     protocols.  This version of the MIB includes
     common signaling and Network Call Signaling
```

```
      (NCS)-related signaling objects.

      Copyright (C) The IETF Trust (2008).  This version of
      this MIB module is part of RFC 5098; see the RFC itself for
      full legal notices."
  REVISION             "200712180000Z"
  DESCRIPTION
    "Initial version, published as RFC 5098."

::=  { mib-2 169 }

-- Textual Conventions

TenthdBm ::= TEXTUAL-CONVENTION
  DISPLAY-HINT "d-1"
  STATUS       current
  DESCRIPTION
     "This TEXTUAL-CONVENTION represents power levels that are
      normally expressed in dBm.  Units are in tenths of a dBm;
      for example, -13.5 dBm will be represented as -135."
  SYNTAX       Integer32

PktcCodecType ::= TEXTUAL-CONVENTION
  STATUS       current
  DESCRIPTION
     " This TEXTUAL-CONVENTION defines various types of codecs

  that MAY be supported.  The description for each
       enumeration is listed below:

       Enumeration     Description
       other          a defined codec not in the enumeration
       unknown         a codec not defined by the PacketCable
                    Codec Specification
       g729           ITU-T Recommendation G.729
       reserved        for future use
       g729E          ITU-T Recommendation G.729E
       pcmu           Pulse Code Modulation u-law (PCMU)
       g726at32        ITU-T Recommendation G.726-32 (32 kbit/s)
       g728           ITU-T Recommendation G.728
       pcma           Pulse Code Modulation a-law (PCMA)
       g726at16        ITU-T Recommendation G.726-16 (16 kbit/s)
       g726at24        ITU-T Recommendation G.726-24 (24 kbit/s)
       g726at40        ITU-T Recommendation G.726-40 (40 kbit/s)
       ilbc           IETF Internet low-bit rate codec
```

bv16 Broadcom BroadVoice16

The list of codecs is consistent with the IETF
Real-Time Transport Protocol (RTP) Profile registry and

the RTP Map Parameters Table in PacketCable Audio/Video
Codecs Specification [PKT-SP-CODEC]. The literal codec
name for each codec is listed below:

Codec	Literal Codec Name
g729	G729
g729E	G729E
pcmu	PCMU
g726at32	G726-32
g728	G728
pcma	PCMA
g726at16	G726-16
g726at24	G726-24
g726at40	G726-40
ilbc	iLBC
bv16	BV16

The literal codec name is the second column of the table
with codec RTP Map Parameters. The Literal Codec Name Column
contains the codec name used in the local connection
options (LCO) of the NCS messages create connection

(CRCX)/modify connection (MDCX) and is also used to
identify the codec in the Call Management System (CMS)
Provisioning Specification. The RTP Map Parameter column of
the Table contains the string used in the media attribute
line (a=) of the session description protocol (SDP)
parameters in NCS messages."

```
SYNTAX INTEGER {
    other     (1),
    unknown   (2),
    g729      (3),
    reserved  (4),
    g729E     (5),
    pcmu      (6),
    g726at32  (7),
    g728      (8),
    pcma      (9),
    g726at16  (10),
    g726at24  (11),
    g726at40  (12),
```

```
            ilbc      (13),
            bv16      (14)
    }

PktcRingCadence   ::= TEXTUAL-CONVENTION
    STATUS        current
    DESCRIPTION
        "This object provides an encoding scheme for ring




        cadences, including repeatability
 characteristics.  All
        fields in this object MUST be encoded in network-byte
        order.

        The first three higher-order octets are reserved.  The
        octets that follow are used to encode a 'bit-string', with
        each bit corresponding to 50 milliseconds.  A bit value of
        '1' indicates the presence of a ring-tone, and a bit value
        of '0' indicates the absence of a ring-tone, for that
        duration (50 ms) (Note: A minimum number of octets
        required to encode the bit-string MUST be used).

        The first two of the reserved octets MUST indicate the
        length of the encoded cadence (in bits) and MUST range
        between 1 and 264.  (Note: The length in bits MUST also be
        consistent with the number of octets that encode the
        cadence).  The MTA MUST ignore any unused bits in the last
        octet, but MUST reflect the value as provided on
        subsequent SNMP GETs.

        The
 third of the reserved octets indicates 'repeatability'
        and MUST be either 0x80 or 0x00 -- the former value
        indicating 'non-repeatability', and the latter indicating
        'repeatability'.

        The MTA MUST reject attempts to set a value that violates
        any of the above requirements."


    SYNTAX  OCTET STRING (SIZE(4..36))


PktcSigType     ::= TEXTUAL-CONVENTION
    STATUS       current
    DESCRIPTION
```

```
      " This object lists the various types of signaling that may
        be supported:

        other(1) - set when signaling other than NCS is used
        ncs(2)   - Network Call Signaling is a derivation of MGCP
                   (Media Gateway Control Protocol) defined for
                    IPCablecom/PacketCable MTAs."
    SYNTAX INTEGER {
                other(1),
                ncs(2)
    }




DtmfCode::=TEXTUAL-CONVENTION
    STATUS       current
    DESCRIPTION
       "This TEXTUAL-CONVENTION represents the Dual-Tone
        Multi-Frequency (DTMF) Character used
       to indicate the start or end of the digit transition
       sequence used for caller id or Visual Message Waiting
       Indicator (VMWI).

       Note: The DTMF code '*' is indicated using 'dtmfcodeStar',
       and the DTMF code '#' is indicated using ' dtmfcodeHash'."
    SYNTAX       INTEGER {
                dtmfcode0(0),
                dtmfcode1(1),
                dtmfcode2(2),
                dtmfcode3(3),
                dtmfcode4(4),
                dtmfcode5(5),
                dtmfcode6(6),
                dtmfcode7(7),
                dtmfcode8(8),
                dtmfcode9(9),
                dtmfcodeStar(10),
                dtmfcodeHash(11),
                dtmfcodeA(12),
                dtmfcodeB(13),
                dtmfcodeC(14),
                dtmfcodeD(15)
}

PktcSubscriberSideSigProtocol::=TEXTUAL-CONVENTION
    STATUS  current
```

```
  DESCRIPTION
     "This TEXTUAL-CONVENTION
 represents the Signaling
      protocol being used for purposes such as caller id
      or VMWI.

      A value of fsk(1) indicates Frequency Shift Keying
      (FSK).
      A value of dtmf(2) indicates Dual-Tone Multi-Frequency
      (DTMF)."
      SYNTAX INTEGER {
           fsk(1),
           dtmf(2)
      }

pktcSigMibObjects OBJECT IDENTIFIER ::= { pktcIetfSigMib 1 }
pktcSigDevObjects OBJECT IDENTIFIER ::=




                          { pktcSigMibObjects 1 }
pktcSigEndPntConfigObjects OBJECT IDENTIFIER ::=
                          { pktcSigMibObjects 2 }
--
-- The codec table (pktcSigDevCodecTable) defines all combinations
-- of codecs supported by the Multimedia Terminal Adapter (MTA).
--
pktcSigDevCodecTable OBJECT-TYPE
  SYNTAX      SEQUENCE OF PktcSigDevCodecEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
      " This table describes the MTA-supported codec types.  An MTA
       MUST populate this table with all possible combinations of
       codecs it supports for simultaneous operation.  For example,
       an MTA with two endpoints may be designed with a particular
       Digital Signal Processing (DSP) and memory architecture that
       allows it to support the following fixed combinations of
       codecs for simultaneous operation:

       Codec Type     Maximum Number of Simultaneous Codecs
       PCMA                    3

       PCMA                    2
       PCMU                    1

       PCMA                    1
```

PCMU 2

PCMU 3

PCMA 1
G729 1

G729 2

PCMU 1
G729 1

Based on this example, the entries
in the codec table
would be:

pktcSigDev CodecComboIndex	pktcSigDev CodecType	pktcSigDev CodecMax
1	pcma	3
2	pcma	2
2	pcmu	1
3	pcma	1
3	pcmu	2
4	pcmu	3
5	pcma	1
5	g729	1
6	g729	2
7	pcmu	1
7	g729	1

An operator querying this table is able to determine all
possible codec combinations the MTA is capable of
simultaneously supporting.

This table MUST NOT include non-voice codecs."
::=
{ pktcSigDevObjects 1 }

```
pktcSigDevCodecEntry  OBJECT-TYPE
  SYNTAX      PktcSigDevCodecEntry
  MAX-ACCESS  not-accessible
  STATUS      current
  DESCRIPTION
     "Each entry represents the maximum number of active
      connections with a particular codec the MTA is capable of
```

```
        supporting.  Each row is indexed by a composite key
        consisting of a number enumerating the particular codec
        combination and the codec type."
    INDEX { pktcSigDevCodecComboIndex, pktcSigDevCodecType }
    ::= { pktcSigDevCodecTable 1 }

PktcSigDevCodecEntry  ::= SEQUENCE {
    pktcSigDevCodecComboIndex    Unsigned32,
    pktcSigDevCodecType     PktcCodecType,
    pktcSigDevCodecMax      Unsigned32
    }

pktcSigDevCodecComboIndex  OBJECT-TYPE
    SYNTAX      Unsigned32 (1..255)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        " The index value that enumerates a particular codec
          combination in the pktcSigDevCodecTable."
    ::=
 { pktcSigDevCodecEntry 1 }

pktcSigDevCodecType  OBJECT-TYPE
    SYNTAX       PktcCodecType
    MAX-ACCESS   not-accessible
    STATUS       current



    DESCRIPTION
        " A codec type supported by this MTA."
    ::= { pktcSigDevCodecEntry 2 }

pktcSigDevCodecMax  OBJECT-TYPE
    SYNTAX      Unsigned32(1..255)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        " The maximum number of simultaneous sessions of a
          particular codec that the MTA can support."
    ::= { pktcSigDevCodecEntry 3 }

--
-- These are the common signaling-related definitions that affect
-- the entire MTA device.
--

pktcSigDevEchoCancellation  OBJECT-TYPE
```

```
  SYNTAX      TruthValue
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object specifies if the device is capable of echo
       cancellation.  The MTA MUST set this MIB object to a
       value of true(1) if it is capable of echo
       cancellation, and a value of false(2) if not."
   ::= { pktcSigDevObjects 2 }

pktcSigDevSilenceSuppression  OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object specifies if the device is capable of
       silence suppression (as a result of Voice Activity
       Detection).  The MTA MUST set this MIB object to a
       value of true(1) if it is capable of silence
       suppression, and a value of false(2) if not."
::= { pktcSigDevObjects 3 }

pktcSigDevCidSigProtocol  OBJECT-TYPE
  SYNTAX      PktcSubscriberSideSigProtocol
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     "This object is used to configure the subscriber-line
      protocol used for signaling on-hook caller id information.



      Different countries define different caller id signaling
      protocols to support caller identification.

      Setting this object at a value fsk(1) sets the subscriber
      line protocol to be
 Frequency Shift Keying (FSK).

      Setting this object at a value dtmf(2) sets the subscriber
      line protocol to be Dual-Tone Multi-Frequency (DTMF).

      The value of this MIB object MUST NOT persist across MTA
      reboots."
   REFERENCE
     "ETSI-EN-300-659-1 Specification"
   DEFVAL { fsk }
::= { pktcSigDevObjects 4 }
```

```
pktcSigDevR0Cadence     OBJECT-TYPE
  SYNTAX      PktcRingCadence
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     " This object specifies ring cadence 0 (a user-defined
       field).

       The value of this MIB object MUST NOT persist across MTA
       reboots."
  ::= { pktcSigDevObjects 5 }

pktcSigDevR1Cadence     OBJECT-TYPE
  SYNTAX      PktcRingCadence
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     " This object specifies ring cadence 1 (a user-defined
       field).

       The value of this MIB object MUST NOT persist across MTA
       reboots."

 ::= { pktcSigDevObjects 6 }

pktcSigDevR2Cadence     OBJECT-TYPE
  SYNTAX       PktcRingCadence
  MAX-ACCESS    read-write
  STATUS       current
  DESCRIPTION
     " This object specifies ring cadence 2 (a user-defined
       field).




       The value of this MIB object MUST NOT persist across MTA
       reboots."
  ::= { pktcSigDevObjects 7 }

pktcSigDevR3Cadence     OBJECT-TYPE
  SYNTAX       PktcRingCadence
  MAX-ACCESS   read-write
  STATUS       current
  DESCRIPTION
     " This object specifies ring cadence 3 (a user-defined
       field).
```

```
        The value of this MIB object MUST NOT persist across MTA
        reboots."
    ::= { pktcSigDevObjects 8 }

pktcSigDevR4Cadence     OBJECT-TYPE
    SYNTAX       PktcRingCadence
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
       " This object specifies ring cadence 4 (a user-defined
        field).

        The value of this MIB object MUST NOT persist across MTA
         reboots."
    ::= { pktcSigDevObjects 9 }

pktcSigDevR5Cadence     OBJECT-TYPE
    SYNTAX       PktcRingCadence
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
       " This object specifies ring cadence 5 (a user-defined
        field).

        The value of this MIB object MUST NOT persist across MTA
        reboots."
    ::= { pktcSigDevObjects 10 }

pktcSigDevR6Cadence     OBJECT-TYPE
    SYNTAX      PktcRingCadence
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
       " This object specifies ring cadence 6 (a user-defined
        field).




        The value of this MIB object MUST NOT persist across MTA
        reboots."
    ::= { pktcSigDevObjects 11 }

pktcSigDevR7Cadence     OBJECT-TYPE
    SYNTAX       PktcRingCadence
    MAX-ACCESS   read-write
    STATUS       current
```

```
  DESCRIPTION
     " This object specifies ring cadence 7 (a user-defined
       field).

       The value of this MIB object MUST
 NOT persist across MTA
       reboots."
  ::= { pktcSigDevObjects 12 }

pktcSigDevRgCadence     OBJECT-TYPE
  SYNTAX       PktcRingCadence
  MAX-ACCESS   read-write
  STATUS       current
  DESCRIPTION
     " This object specifies ring cadence rg (a user-defined
       field).

       The value of this MIB object MUST NOT persist across MTA
       reboots."
  ::= { pktcSigDevObjects 13 }

pktcSigDevRsCadence     OBJECT-TYPE
  SYNTAX       PktcRingCadence
  MAX-ACCESS   read-write
  STATUS       current
  DESCRIPTION
     " This object specifies ring cadence rs (a user-defined
       field).  The MTA MUST reject any attempt to make this object
       repeatable.

       The value of this MIB object MUST NOT persist across MTA
       reboots."
  ::= { pktcSigDevObjects 14 }

pktcSigDefCallSigDscp  OBJECT-TYPE
  SYNTAX      Dscp  -- RFC 3289: DIFFSERV-DSCP-TC
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     "
 The default value used in the IP header for setting the
       Differentiated Services Code Point (DSCP) value for call



       signaling.

       The value of this MIB object MUST NOT persist across MTA
```

```
        reboots."
    DEFVAL { 0 }
    ::= { pktcSigDevObjects 15 }

pktcSigDefMediaStreamDscp  OBJECT-TYPE
    SYNTAX      Dscp  -- RFC 3289: DIFFSERV-DSCP-TC
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
        " This object contains the default value used in the IP
          header for setting the Differentiated Services Code Point
          (DSCP) value for media stream packets.  The MTA MUST NOT
          update this object with the value supplied by the CMS in
          the NCS messages (if present).  Any currently active
          connections are not affected by updates to this object.
          When the value of this object is updated by SNMP, the MTA
          MUST use the new value as a default starting only from
          new connections.

           The value of this MIB object MUST NOT persist across MTA
          reboots."
    DEFVAL { 0 }
    ::= { pktcSigDevObjects 16 }

--
-- pktcSigCapabilityTable - This table defines the valid signaling
-- types supported by this MTA.
--

pktcSigCapabilityTable    OBJECT-TYPE
    SYNTAX        SEQUENCE OF PktcSigCapabilityEntry
    MAX-ACCESS    not-accessible
    STATUS        current
    DESCRIPTION
        " This table describes the signaling types supported by this
          MTA."
    ::= { pktcSigDevObjects 17 }

pktcSigCapabilityEntry    OBJECT-TYPE
    SYNTAX        PktcSigCapabilityEntry
    MAX-ACCESS    not-accessible
    STATUS        current
    DESCRIPTION
        " Entries in pktcMtaDevSigCapabilityTable - list of
          supported signaling types, versions, and vendor extensions
```

```
        for this MTA.  Each entry in the list provides for one
        signaling type and version combination.  If the device
        supports multiple versions of the same signaling
 type, it
        will require multiple entries."
   INDEX { pktcSigCapabilityIndex }
   ::= { pktcSigCapabilityTable 1 }

PktcSigCapabilityEntry  ::= SEQUENCE {
   pktcSigCapabilityIndex           Unsigned32,
   pktcSigCapabilityType            PktcSigType,
   pktcSigCapabilityVersion          SnmpAdminString,
   pktcSigCapabilityVendorExt        SnmpAdminString
   }

pktcSigCapabilityIndex       OBJECT-TYPE
   SYNTAX        Unsigned32 (1..255)
   MAX-ACCESS    not-accessible
   STATUS        current
   DESCRIPTION
      " The index value that uniquely identifies an entry in the
        pktcSigCapabilityTable."
   ::= { pktcSigCapabilityEntry 1 }

pktcSigCapabilityType      OBJECT-TYPE
   SYNTAX        PktcSigType
   MAX-ACCESS    read-only
   STATUS        current
   DESCRIPTION
      " This object identifies the type of signaling used.  This
        value has to be associated with a single signaling
        version."
   ::= { pktcSigCapabilityEntry
 2 }

pktcSigCapabilityVersion      OBJECT-TYPE
   SYNTAX        SnmpAdminString
   MAX-ACCESS    read-only
   STATUS        current
   DESCRIPTION
      " Provides the version of the signaling type - reference
        pktcSigCapabilityType.  Examples would be 1.0 or 2.33 etc."
   ::= { pktcSigCapabilityEntry 3 }

pktcSigCapabilityVendorExt      OBJECT-TYPE
   SYNTAX        SnmpAdminString
   MAX-ACCESS    read-only
   STATUS        current
```

```
  DESCRIPTION
     " The vendor extension allows vendors to provide a list of



       additional capabilities.

       The syntax for this MIB object in ABNF ([RFC5234]) is
       specified to be zero or more occurrences of vendor
       extensions, as follows:

        pktcSigCapabilityVendorExt  = *(vendor-extension)
        vendor-extension = (ext symbol alphanum) DQUOTE ; DQUOTE
        ext      = DQUOTE %x58 DQUOTE
        symbol   = (DQUOTE %x2D DQUOTE)/(DQUOTE %x2D DQUOTE)
        alphanum = 1*6(ALPHA/DIGIT)

      "
  ::= { pktcSigCapabilityEntry 4 }

pktcSigDefNcsReceiveUdpPort  OBJECT-TYPE
  SYNTAX      InetPortNumber (1025..65535)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     " This object contains the MTA User Datagram Protocol (UDP)
       receive port that is being used for NCS call signaling.
       This object should only be changed by the configuration
       file.

       Unless changed via configuration, this MIB object MUST
       reflect a value of '2427'."
  REFERENCE
     "PacketCable NCS Specification"
  ::= { pktcSigDevObjects 18 }

pktcSigPowerRingFrequency    OBJECT-TYPE
  SYNTAX      INTEGER {
              f20Hz(1),
              f25Hz(2),
              f33Point33Hz(3),
              f50Hz(4),
              f15Hz(5),
              f16Hz(6),
              f22Hz(7),
              f23Hz(8),
              f45Hz(9)
  }
```

```
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
     " This object must only be provided via the configuration
       file during the provisioning process.  The power ring



       frequency is the frequency at which the sinusoidal voltage
       must travel down the twisted pair to make terminal
       equipment ring.  Different countries define different
       electrical characteristics to make terminal equipment
       ring.

       The f20Hz setting corresponds to a power ring frequency
       of 20 Hertz.  The f25Hz setting corresponds to a power ring
       frequency of 25 Hertz.  The f33Point33Hz setting
       corresponds to a power ring frequency of 33.33 Hertz.  The
       f50Hz setting corresponds to a power ring frequency of 50
       Hertz.  The f15Hz setting corresponds to a power ring
       frequency of 15 Hertz.  The f16Hz setting corresponds to a
       power ring frequency of 16 Hertz.  The f22Hz setting
       corresponds to a power ring frequency of
 22 Hertz.  The
       f23Hz setting corresponds to a power ring frequency of 23
       Hertz.  The f45Hz setting corresponds to a power ring
       frequency of 45 Hertz."
  REFERENCE
       "ETSI-EN-300-001"
  ::= { pktcSigDevObjects 19 }

pktcSigPulseSignalTable    OBJECT-TYPE
  SYNTAX       SEQUENCE OF PktcSigPulseSignalEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
     " The Pulse signal table defines the pulse signal operation.
       There are nine types of international pulse signals,
       with each signal having a set of provisionable parameters.
       The values of the MIB objects in this table take effect
       only if these parameters are not defined via signaling, in
       which case, the latter determines the values of the
       parameters.  The MIB objects in this table do not persist
       across MTA reboots."
  REFERENCE
     "ETSI-TS-101-909-4 Specification"
  ::= { pktcSigDevObjects
```

```
 20 }

pktcSigPulseSignalEntry    OBJECT-TYPE
  SYNTAX       PktcSigPulseSignalEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
     " This object defines the set of parameters associated with
       each particular value of pktcSigPulseSignalType.  Each
       entry in the pktcSigPulseSignalTable is indexed by the
       pktcSigPulseSignalType object.



       The conceptual rows MUST NOT persist across MTA reboots."
  INDEX { pktcSigPulseSignalType }
  ::= { pktcSigPulseSignalTable 1 }

PktcSigPulseSignalEntry ::= SEQUENCE {
     pktcSigPulseSignalType             INTEGER,
     pktcSigPulseSignalFrequency        INTEGER,
     pktcSigPulseSignalDbLevel          TenthdBm,
     pktcSigPulseSignalDuration         Unsigned32,
     pktcSigPulseSignalPulseInterval    Unsigned32,
     pktcSigPulseSignalRepeatCount      Unsigned32
}

pktcSigPulseSignalType    OBJECT-TYPE
  SYNTAX       INTEGER
               {
                  initialRing(1),
                  pulseLoopClose(2),
                  pulseLoopOpen(3),
                  enableMeterPulse(4),
                  meterPulseBurst(5),
                  pulseNoBattery(6),
                  pulseNormalPolarity(7),
                  pulseReducedBattery(8),
                  pulseReversePolarity(9)
               }
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
     "There are nine types of international pulse signals.  These
      signals are defined as follows:
      initial ring
      pulse loop close
      pulse loop open
```

```
      enable meter pulse
      meter pulse burst
      pulse no battery
      pulse normal polarity
      pulse reduced battery
      pulse reverse polarity"
  REFERENCE
     "ETSI-EN-300-324-1 Specification"

  ::= { pktcSigPulseSignalEntry 1 }

pktcSigPulseSignalFrequency    OBJECT-TYPE
  SYNTAX       INTEGER {

        twentyfive(1),



            twelvethousand(2),
            sixteenthousand(3)
  }
  MAX-ACCESS   read-write
  STATUS       current
  DESCRIPTION
     " This object is only applicable to the initialRing,
       enableMeterPulse, and meterPulseBurst signal types.  This
       object identifies the frequency of the generated signal.
       The following table defines the default values for this
       object depending on signal type:

       pktcSigPulseSignalType     Default
       initialRing              25
       enableMeterPulse          16000
       meterPulseBurst           16000

       The value of twentyfive MUST only be used for the
       initialRing signal type.  The values of twelvethousand and
       sixteenthousand MUST only be used for enableMeterPulse and
       meterPulseBurst signal types.  An attempt to set this
       object while the value of pktcSigPulseSignalType is not
       initialRing,
 enableMeterPulse, or meterPulseBurst will
       result in an 'inconsistentValue' error."
  REFERENCE
     "ETSI-EN-300-001 Specification"
      ::= { pktcSigPulseSignalEntry 2}

pktcSigPulseSignalDbLevel    OBJECT-TYPE
```

```
  SYNTAX      TenthdBm (-350..0)
  UNITS       "1/10 of a dBm"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     " This object is only applicable to the enableMeterPulse and
       meterPulseBurst signal types.  This is the decibel level
       for each frequency at which tones could be generated at
       the a and b terminals (TE connection point).  An attempt to
       set this object while the value of pktcSigPulseSignalType
       is not enableMeterPulse or meterPulseBurst will result in
       an 'inconsistentValue' error."
  REFERENCE
     "ETSI-EN-300-001 Specification"

  DEFVAL { -135 }
  ::={pktcSigPulseSignalEntry 3 }

pktcSigPulseSignalDuration    OBJECT-TYPE



  SYNTAX      Unsigned32
(0..5000)
  UNITS       "Milliseconds"
  MAX-ACCESS  read-write
  STATUS      current
  DESCRIPTION
     " This object specifies the pulse duration for each
       signal type.  In addition, the MTA must accept the values
       in the incremental steps specific for each signal type.
       The following table defines the default values and the
       incremental steps for this object depending on the signal
       type:

       pktcSigPulseSignaltype  Default (ms)   Increment (ms)
       initialRing               200           50
       pulseLoopClose            200           10
       pulseLoopOpen             200           10
       enableMeterPulse          150           10
       meterPulseBurst           150           10
       pulseNoBattery            200           10
       pulseNormalPolarity       200           10
       pulseReducedBattery       200           10
       pulseReversePolarity
      200           10

       An attempt to set this object to a value that does not
```

```
        fall on one of the increment boundaries, or on the wrong
        increment boundary for the specific signal type, will
        result in an 'inconsistentValue' error."
    REFERENCE
       "ETSI-EN-300-324-1 Specification"
       ::= {pktcSigPulseSignalEntry 4 }

pktcSigPulseSignalPulseInterval     OBJECT-TYPE
    SYNTAX       Unsigned32 (0..5000)
    UNITS        "Milliseconds"
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
       " This object specifies the repeat interval, or the period,
        for each signal type.  In addition, the MTA must accept
        the values in the incremental steps specific for each
        signal type.  The following table defines the default
        values and the incremental steps for this object, depending
        on the signal type:

        pktcSigPulseSignaltype  Default (ms)   Increment (ms)
         initialRing               200            50
        pulseLoopClose             1000           10
        pulseLoopOpen              1000           10



        enableMeterPulse           1000           10
        meterPulseBurst            1000           10
        pulseNoBattery             1000           10
        pulseNormalPolarity        1000           10
        pulseReducedBattery        1000           10
        pulseReversePolarity       1000           10

        An attempt to set this object to a value that does not
        fall on one of the increment boundaries, or on the wrong
        increment boundary for the specific signal type, will
        result in an 'inconsistentValue' error."
    REFERENCE
       "ETSI-EN-300-324-1 Specification"
       ::= { pktcSigPulseSignalEntry 5}

pktcSigPulseSignalRepeatCount    OBJECT-TYPE
    SYNTAX       Unsigned32 (1..50)
    MAX-ACCESS   read-write
    STATUS       current
```

```
DESCRIPTION
    " This object specifies how many times to repeat a pulse.
      This object is not used by the enableMeterPulse signal
      type, and in that case, the value is irrelevant.  The
      following table defines the default values and the valid
      ranges for this object, depending on the signal type:

      pktcSigPulseSignaltype  Default   Range

      initialRing             1       1-5
      pulseLoopClose          1       1-50
      pulseLoopOpen           1       1-50
      enableMeterPulse      (any value)(but not used)
      meterPulseBurst         1       1-50
      pulseNoBattery          1       1-50
      pulseNormalPolarity     1       1-50
      pulseReducedBattery     1       1-50
      pulseReversePolarity    1       1-50

      An attempt to set this object to a value that does not
      fall within the range for the specific
      signal type will result in an
'inconsistentValue' error."
  ::={ pktcSigPulseSignalEntry 6 }

pktcSigDevCidMode    OBJECT-TYPE
  SYNTAX       INTEGER {
            duringRingingETS(1),
            dtAsETS(2),
            rpAsETS(3),



            lrAsETS(4),
            lrETS(5)
            }
  MAX-ACCESS read-write
  STATUS current
  DESCRIPTION
    " For on-hook caller id, pktcSigDevCidMode selects the method
      for representing and signaling caller identification.  For
      the duringRingingETS method, the Frequency Shift Keying
      (FSK) or the Dual-Tone Multi-Frequency (DTMF) containing
      the caller identification information is sent between the
      first and second ring pattern.

      For the dtAsETS,rpAsETS, lrAsETS and lrETS
      methods, the FSK or DTMF containing the caller id
```

information is sent before the first ring pattern.

For the dtAsETS method, the FSK or DTMF is sent after the Dual
Tone Alert Signal. For the rpAsETS method, the FSK or DTMF is sent after a Ring Pulse.

For the lrAsETS method, the Line Reversal occurs first, then the Dual Tone Alert Signal, and, finally, the FSK or DTMF is sent.

For the lrETS method, the Line Reversal occurs first, then the FSK or DTMF is sent.

The value of this MIB object MUST NOT persist across MTA reboots."

DEFVAL { rpAsETS}
::= {pktcSigDevObjects 21 }

pktcSigDevCidAfterRing OBJECT-TYPE
SYNTAX Unsigned32 (0|50..2000)
UNITS "Milliseconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
" This object specifies the delay between the end of first ringing pattern and the start of the transmission of the FSK or DTMF containing the caller id information. It is only used when pktcSigDevCidMode is set to a value of 'duringRingingETS'.

The following
table defines the default values
for this MIB object, depending on the signal type

(pktcSigDevCidMode), and MUST be followed:

Value of pktcSigDevCidMode Default value

duringringingETS 550 ms
dtAsETS any value (not used)
rpAsETS any value (not used)
lrAsETS any value (not used)
lrETS any value (not used)

```
        An attempt to set this object while the value of
        pktcSigDevCidMode is not duringringingETS will result in
        an 'inconsistentValue' error.

        The value of this MIB object MUST NOT persist across MTA
        reboots."
    REFERENCE
       "ETSI-EN-300-659-1 Specification"
    DEFVAL { 550 }
    ::= {pktcSigDevObjects 22 }

pktcSigDevCidAfterDTAS    OBJECT-TYPE
    SYNTAX       Unsigned32 (0|45..500)
    UNITS        "Milliseconds"
    MAX-ACCESS
    read-write
    STATUS       current
    DESCRIPTION
       " This object specifies the delay between the end of the
        Dual Tone Alert Signal (DT-AS) and the start of the
        transmission of the FSK or DTMF containing the caller id
        information.  This object is only used when
        pktcSigDevCidMode is set to a value of 'dtAsETS' or
        'lrAsETS'.

        The following table defines the default values
        for this MIB object, depending on the signal type
       (pktcSigDevCidMode), and MUST be followed:

        Value of pktcSigDevCidMode       Default value


        duringringingETS              any value (not used)
        dtAsETS                       50 ms
        rpAsETS                       any value (not used)
        lrAsETS                       50 ms
        lrETS                        any value (not used)

        An attempt to set this object while the value of



        pktcSigDevCidMode
 is not 'dtAsETS' or 'lrAsETS' will
        result in an 'inconsistentValue' error.

        The value of this MIB object MUST NOT persist across MTA
        reboots."
```

```
  REFERENCE
     "ETSI-EN-300-659-1 Specification"
  DEFVAL { 50 }
  ::= {pktcSigDevObjects 23 }

pktcSigDevCidAfterRPAS    OBJECT-TYPE
  SYNTAX       Unsigned32 (0|500..800)
  UNITS        "Milliseconds"
  MAX-ACCESS   read-write
  STATUS       current
  DESCRIPTION
     " This object specifies the delay between the end of the
       Ring Pulse Alert Signal (RP-AS) and the start of the
       transmission of the FSK or DTMF containing the caller id
       information.  This MIB object is only used when
       pktcSigDevCidMode is set to a value of 'rpAsETS'.
       The following table defines the default values
       for this MIB object, depending on the signal type
      (pktcSigDevCidMode), and MUST be followed:

       Value of pktcSigDevCidMode       Default
 value

       duringringingETS               any value  (not used)
       dtAsETS                        any value  (not used)
       rpAsETS                        650 ms
       lrAsETS                        any value  (not used)
       lrETS                         any value  (not used)

       An attempt to set this object while the value of
       pktcSigDevCidMode is not 'rpAsETS' will result in an
       'inconsistentValue' error.

       The value of this MIB object MUST NOT persist across MTA
       reboots."
  REFERENCE
     "ETSI-EN-300-659-1 Specification"
  DEFVAL { 650 }
  ::= {pktcSigDevObjects 24 }

pktcSigDevRingAfterCID    OBJECT-TYPE
  SYNTAX       Unsigned32 (0|50..500)
  UNITS        "Milliseconds"
  MAX-ACCESS   read-write



  STATUS       current
```

```
  DESCRIPTION
      " This object specifies the delay between the end of the
        complete transmission of the FSK or DTMF containing the
        caller
 id information and the start of the first ring
        pattern.  It is only used when pktcSigDevCidMode is
        set to a value of 'dtAsETS', 'rpAsETS', 'lrAsETS' or
        'lrETS'.

        The following table defines the default values
        for this MIB object, depending on the signal type
       (pktcSigDevCidMode), and MUST be followed:

        Value of pktcSigDevCidMode       Default value

        duringringingETS              any value  (not used)
        dtAsETS                       250 ms
        rpAsETS                       250 ms
        lrAsETS                       250 ms
        lrETS                         250 ms

        An attempt to set this object while the value of
        pktcSigDevCidMode is not 'dtAsETS', 'rpAsETS',
        'lrAsETS', or 'lrETS' will result in an 'inconsistent
        value' error.

        The value of this MIB object MUST NOT persist across MTA
        reboots."
  REFERENCE

   "ETSI-EN-300-659-1 Specification"
  DEFVAL { 250 }
  ::= {pktcSigDevObjects 25 }

pktcSigDevCidDTASAfterLR    OBJECT-TYPE
  SYNTAX       Unsigned32 (50..655)
  UNITS        "Milliseconds"
  MAX-ACCESS   read-write
  STATUS       current
  DESCRIPTION
      " This object specifies the delay between the end of the
        Line Reversal and the start of the Dual Tone Alert Signal
        (DT-AS).  This object is only used when pktcSigDevCidMode
        is set to a value of 'lrAsETS'.

        The following table defines the default values
        for this MIB object, depending on the signal type
       (pktcSigDevCidMode), and MUST be followed:
```

```
        Value of pktcSigDevCidMode       Default value

        duringringingETS                 any value  (not used)
        dtAsETS                          any value  (not used)
        rpAsETS                          any value  (not used)
        lrAsETS                          250 ms
        lrETS
                        any value  (not used)

        An attempt to set this object while the value of
        pktcSigDevCidMode is not lrAsETS will result in an
        'inconsistentValue' error.

        The value of this MIB object MUST NOT persist across MTA
        reboots."
    REFERENCE
       "ETSI-EN-300-659-1 Specification"
    DEFVAL { 250 }

    ::= {pktcSigDevObjects 26 }

pktcSigDevVmwiMode    OBJECT-TYPE
    SYNTAX      INTEGER {
                dtAsETS(1),
                rpAsETS(2),
                lrAsETS(3),
                osi(4),
                lrETS(5)
                }
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
       " For visual message waiting indicator (VMWI),
        pktcSigDevVmwiMode selects the alerting signal method.  For
        the dtAsETS, rpAsETS, lrAsETS, osi, and lrETS methods,
        the FSK containing the VMWI information is sent after an
        alerting signal.

        For the dtAsETS method,
   the FSK, or DTMF
        is sent after the Dual Tone Alert Signal.  For the rpAsETS
        method, the FSK or DTMF is sent after a Ring Pulse.

        For the lrAsETS method, the Line Reversal occurs first,
```

then the Dual Tone Alert Signal, and, finally, the FSK or
DTMF is sent.

For the OSI method, the FSK or DTMF is sent after the Open
Switching Interval.

For the lrETS method, the Line Reversal occurs first,
then the FSK or DTMF is sent.

The value of this MIB object MUST NOT persist across MTA
reboots."

```
  DEFVAL { rpAsETS }
  ::= {pktcSigDevObjects 27 }

pktcSigDevVmwiAfterDTAS    OBJECT-TYPE
  SYNTAX       Unsigned32 (0|45..500)
  UNITS        "Milliseconds"
  MAX-ACCESS   read-write
  STATUS       current
  DESCRIPTION
     " This object specifies the delay between the end of the
       Dual Tone Alert Signal (DT-AS) and the start of the
       transmission of the
 FSK or DTMF containing the VMWI
       information.
```

This object is only used when pktcSigDevVmwiMode is
set to a value of 'dtAsETS' or 'lrAsETS'.

The following table defines the default values
for this MIB object, depending on the signal type
(pktcSigDevVmwiMode), and MUST be followed:

Value of pktcSigDevVmwiMode	Default value
dtAsETS	50 ms
rpAsETS	any value (not used)
lrAsETS	50 ms
lrETS	any value (not used)

An attempt to set this object while the value of
pktcSigDevVmwiMode is not 'dtAsETS' or 'lrAsETS' will
result in an 'inconsistentValue' error.

```
        The value of this MIB object MUST NOT persist across MTA
        reboots."
    REFERENCE
       "ETSI-EN-300-659-1 Specification"
    DEFVAL { 50 }
    ::= {pktcSigDevObjects 28
  }


pktcSigDevVmwiAfterRPAS    OBJECT-TYPE
    SYNTAX       Unsigned32 (0|500..800)



    UNITS        "Milliseconds"
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
       " This object specifies the delay between the end of the
        Ring Pulse Alert Signal (RP-AS) and the start of the
        transmission of the FSK or DTMF containing the VMWI
        information.

        This object is only used when pktcSigDevVmwiMode is
        set to a value of 'rpAsETS'.

        The following table defines the default values
        for this MIB object, depending on the signal type
       (pktcSigDevVmwiMode), and MUST be followed:

        Value of pktcSigDevVmwiMode       Default value

        dtAsETS                     any value  (not used)
        rpAsETS                     650 ms
        lrAsETS                    any value  (not used)
        lrETS                      any value  (not used)

        An attempt
   to set this object while the value of
        pktcSigDevVmwiMode is not 'rpAsETS' will result in an
        'inconsistentValue' error.

        The value of this MIB object MUST NOT persist across MTA
        reboots."
    REFERENCE
       "ETSI-EN-300-659-1 Specification"
    DEFVAL { 650 }
    ::= {pktcSigDevObjects 29 }
```

```
pktcSigDevVmwiDTASAfterLR    OBJECT-TYPE
  SYNTAX       Unsigned32 (0|50..655)
  UNITS        "Milliseconds"
  MAX-ACCESS   read-write
  STATUS       current
  DESCRIPTION
     " This object specifies the delay between the end of the
       Line Reversal and the start of the Dual Tone Alert Signal
       (DT-AS) for VMWI information.  This object is only used
       when pktcSigDevVmwiMode is set to a value of 'lrAsETS'.

       The following table defines the default values
       for this MIB object, depending on the signal type
      (pktcSigDevVmwiMode), and MUST be followed:




       Value of pktcSigDevVmwiMode
      Default value

       dtAsETS                    any value  (not used)
       rpAsETS                    any value  (not used)
       lrAsETS                   250 ms
       lrETS                    any value  (not used)

       An attempt to set this object while the value of
       pktcSigDevVmwiMode is not 'lrAsETS' will result in an
       'inconsistentValue' error.

       The value of this MIB object MUST NOT persist across MTA
       reboots."
  REFERENCE
     "ETSI-EN-300-659-1 Specification"
  DEFVAL { 250 }
  ::= {pktcSigDevObjects 30 }

pktcSigDevRingCadenceTable    OBJECT-TYPE
  SYNTAX       SEQUENCE OF PktcSigDevRingCadenceEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
     "Cadence rings are defined by the telco governing
      body for each country.  The MTA must be able to support
      various ranges of cadence patterns and cadence periods.
      The
```

```
 MTA will be able to support country-specific
       provisioning of the cadence and idle period.  Each
       cadence pattern will be assigned a unique value ranging
       from 0-127 (inclusive) corresponding to the value of x,
       where x is the value sent in the cadence ringing (cr)
       signal cr(x), requested per the appropriate NCS
       message, and defined in the E package.  The MTA will derive
       the cadence periods from the ring cadence table entry, as
       provisioned by the customer.  The MTA is allowed to provide
       appropriate default values for each of the ring cadences.
       This table only needs to be supported when the MTA
       implements the E package."
  REFERENCE
     "ETSI-TS-101-909-4 Specification"
  ::= { pktcSigDevObjects 31 }

pktcSigDevRingCadenceEntry    OBJECT-TYPE
  SYNTAX       PktcSigDevRingCadenceEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION



      " Each entry in
 this row corresponds to a ring cadence
       that is being supported by the device.  The conceptual
       rows MUST NOT persist across MTA reboots."
  INDEX { pktcSigDevRingCadenceIndex }
  ::= { pktcSigDevRingCadenceTable 1 }

PktcSigDevRingCadenceEntry ::= SEQUENCE {
     pktcSigDevRingCadenceIndex       Unsigned32,
     pktcSigDevRingCadence            PktcRingCadence
  }

pktcSigDevRingCadenceIndex    OBJECT-TYPE
  SYNTAX       Unsigned32 (0..127)
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
     " A unique value ranging from 0 to 127 that corresponds to the
       value sent by the LE based on country-specific cadences,
       one row per cadence cycle.  In any given system
       implementation for a particular country, it is anticipated
       that a small number of ring cadences will be in use.  Thus,
       this table most likely will not be populated to its full
       size."
```

```
  ::= { pktcSigDevRingCadenceEntry
 1 }

pktcSigDevRingCadence    OBJECT-TYPE
  SYNTAX       PktcRingCadence
  MAX-ACCESS   read-write
  STATUS       current
  DESCRIPTION
     "This is the Ring Cadence."
  ::= { pktcSigDevRingCadenceEntry 2 }


pktcSigDevToneTable    OBJECT-TYPE
  SYNTAX       SEQUENCE OF PktcSigDevToneEntry
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
     " The Tone Table defines the composition of tones and
       various tone operations.

       The definition of the tones callWaiting1 through
       callWaiting4 in this table MUST only contain the
       audible tone itself; the delay between tones or the value
       of the tone repeat count are not applicable for the call
       waiting tones.




       The delay between tones or the repeat count is controlled
       by the objects pktcSigEndPntConfigCallWaitingDelay and
       pktcSigEndPntConfigCallWaitingMaxRep.  If the
       pktcSigDevToneType is set to either
 of the values
       callWaiting1, callWaiting2, callWaiting3, or callWaiting4,
       then the value of the pktcSigDevToneWholeToneRepeatCount
       object indicates that the particular frequency group is
       applicable, as a repeatable part of the tone, based on the
       value of the MIB object
       pktcSigDevToneWholeToneRepeatCount.

       The MTA MUST make sure that, after the provisioning
       cycle, the table is fully populated (i.e., for each
       possible index, an entry MUST be defined) using
       reasonable defaults for each row that was not defined
       by the provisioning information delivered via MTA
       Configuration.
```

```
        The frequency composition of each tone is defined by the
        pktcSigDevMultiFreqToneTable.  For each tone type defined
        in pktcSigDevToneTable, the MTA MUST populate at least
        one entry in the pktcSigDevMultiFreqToneTable.

        For each particular value of pktcSigDevToneType,
 the
        pktcSigDevToneTable table can define non-repeating and
        repeating groups of the frequencies defined by the
        pktcSigDevMultiFreqToneTable, such that each group is
        represented by the set of the consecutive rows
        (frequency group) in the pktcSigDevMultiFreqToneTable.

        Objects in this table do not persist across MTA reboots.
        For tones with multiple frequencies refer to the MIB table
        pktcSigDevMultiFreqToneTable."
    REFERENCE
       "PacketCable NCS Specification, ETSI-TS-101-909-4
       Specification."
    ::= { pktcSigDevObjects 32 }

pktcSigDevToneEntry    OBJECT-TYPE
    SYNTAX       PktcSigDevToneEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
       " The different tone types that can be provisioned based on
        country-specific needs.

        Each entry contains the tone generation parameters for
        a specific frequency group of the specific
 Tone Type.



        The different parameters can be provisioned via MTA
        configuration based on country specific needs.
        An MTA MUST populate all entries of this table for each
        tone type."
    INDEX { pktcSigDevToneType, pktcSigDevToneFreqGroup }
    ::= { pktcSigDevToneTable 1 }

PktcSigDevToneEntry ::= SEQUENCE {
    pktcSigDevToneType                  INTEGER,
    pktcSigDevToneFreqGroup             Unsigned32,
    pktcSigDevToneFreqCounter           Unsigned32,
    pktcSigDevToneWholeToneRepeatCount  Unsigned32,
    pktcSigDevToneSteady                TruthValue
```

```
  }

pktcSigDevToneType       OBJECT-TYPE
  SYNTAX      INTEGER {
              busy(1),
              confirmation(2),
              dial(3),
              messageWaiting(4),
              offHookWarning(5),
              ringBack(6),
              reOrder(7),
              stutterdial(8),
              callWaiting1(9),

      callWaiting2(10),
              callWaiting3(11),
              callWaiting4(12),
              alertingSignal(13),
              specialDial(14),
              specialInfo(15),
              release(16),
              congestion(17),
              userDefined1(18),
              userDefined2(19),
              userDefined3(20),
              userDefined4(21)
              }
  MAX-ACCESS   not-accessible
  STATUS       current
  DESCRIPTION
     "A unique value that will correspond to the different
      tone types.  These tones can be provisioned based on
      country-specific needs.  This object defines the type
      of tone being accessed.

      The alertingSignal, specialDial, specialInfo, release,



      congestion, userDefined1, userDefined2, userDefined3,
      and userDefined4 tone types are used in
      the E line package."
  ::= { pktcSigDevToneEntry 1 }

pktcSigDevToneFreqGroup  OBJECT-TYPE

  SYNTAX      Unsigned32(1..4)
    MAX-ACCESS   not-accessible
```

```
    STATUS      current
    DESCRIPTION
      "This MIB object represents the Tone Sequence reference
      of a multi-sequence tone."
    ::={ pktcSigDevToneEntry 2}

pktcSigDevToneFreqCounter OBJECT-TYPE
    SYNTAX      Unsigned32(1..8)
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
      "This MIB object represents the number of consecutive
      multi-frequency tones for the particular tone type in
      the multi-frequency table (pktcSigDevMultiFreqToneTable).

      Such a sequence of the consecutive multi-frequency tones
      forms the tone group for the particular tone type in the
      pktcSigDevToneTable."
    ::={ pktcSigDevToneEntry 3}

pktcSigDevToneWholeToneRepeatCount      OBJECT-TYPE
  SYNTAX      Unsigned32 (0..5000)
  MAX-ACCESS  read-only
  STATUS      current
  DESCRIPTION
     "This is the repeat count,
 which signifies how many times
      to repeat the entire on-off cadence sequence.  Setting this
      object may result in a cadence duration longer or shorter
      than the overall signal duration specified by the time out
      (TO) object for a particular signal.  If the repeat count
      results in a longer tone duration than the signal duration
      specified by the TO, the tone duration defined by the
      TO object for a particular signal always represents
      the overall signal duration for a tone.  In this case, the
      tone duration repeat count will not be fully exercised, and
      the desired tone duration will be truncated per the TO
      setting.  If the repeat count results in a shorter tone
      duration than the signal duration specified by the TO, the
      tone duration defined by the repeat count takes precedence
      over the TO and will end the signal event.  In this case,



      the TO represents a
 time not to be exceeded for the signal.
      It is recommended to ensure proper telephony signaling so that
      the TO duration setting should always be longer than the
```

desired repeat count-time duration."
::={ pktcSigDevToneEntry 4 }

pktcSigDevToneSteady OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This MIB object represents the steady tone status. A value
of 'true(1)' indicates that the steady tone is applied, and
a value of 'false(2)' indicates otherwise.
Devices must play out the on-off cadence sequence for
the number of times indicated by the MIB object
'pktcSigDevToneWholeToneRepeatCount' prior to applying the
last tone steadily, indefinitely. If the MIB table
'pktcSigDevToneTable' contains multiple rows with this
Object set to a value of 'true(1)', the steady tone is
applied to the last repeating frequency
group of the tone.

Setting this MIB object may result in a tone duration that is
longer or shorter than the overall signal duration
specified by the time out (TO) MIB object for a particular
signal. If the repeat count results in a longer tone
duration than the signal duration specified by the TO, the
tone duration defined by the TO object for a particular
signal always represents the overall signal duration for a
tone. In this case, the tone duration repeat count will
not be fully exercised, and the desired tone duration will
be truncated per the TO setting. If the repeat count
results in a shorter tone duration than the signal duration
specified by the TO, the tone duration defined by the
repeat count takes precedence over the TO and will end the
signal event. In this case, the TO represents a time not to
be exceeded for the signal.

It is recommended to ensure proper telephony signaling that
The TO duration setting should always be longer than the
desired repeat count-time duration, plus the desired maximum
steady tone period."
::={ pktcSigDevToneEntry 5 }

pktcSigDevMultiFreqToneTable OBJECT-TYPE
SYNTAX SEQUENCE OF PktcSigDevMultiFreqToneEntry
MAX-ACCESS not-accessible
STATUS current

```
    DESCRIPTION
      " This MIB table defines the characteristics of tones
        with multiple frequencies.  The constraints imposed
        on the tones by the MIB table pktcSigDevToneTable
        need to be considered for MIB objects in this table
        as well.

        The MTA MUST populate the corresponding row(s)
        of the pktcSigDevMultiFreqToneTable for each tone
        defined in the pktcSigDevToneTable.

        The contents of the table may be provisioned via
        MTA configuration."
    REFERENCE
      "PacketCable NCS Specification, ETSI-TS-101-909-4
       Specification."
    ::= { pktcSigDevObjects 33 }

pktcSigDevMultiFreqToneEntry    OBJECT-TYPE
    SYNTAX      PktcSigDevMultiFreqToneEntry
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
      " The different tone types with multiple frequencies
        that can be provisioned based on country-specific
        needs."
    INDEX {pktcSigDevToneType, pktcSigDevToneNumber}
    ::= { pktcSigDevMultiFreqToneTable 1 }

PktcSigDevMultiFreqToneEntry ::= SEQUENCE {
     pktcSigDevToneNumber                Unsigned32,
     pktcSigDevToneFirstFreqValue         Unsigned32,
     pktcSigDevToneSecondFreqValue         Unsigned32,
     pktcSigDevToneThirdFreqValue         Unsigned32,
     pktcSigDevToneFourthFreqValue         Unsigned32,
     pktcSigDevToneFreqMode               INTEGER,
     pktcSigDevToneFreqAmpModePrtg
       Unsigned32,
     pktcSigDevToneDbLevel               TenthdBm,
     pktcSigDevToneFreqOnDuration         Unsigned32,
     pktcSigDevToneFreqOffDuration        Unsigned32,
     pktcSigDevToneFreqRepeatCount         Unsigned32
}

pktcSigDevToneNumber OBJECT-TYPE
    SYNTAX      Unsigned32(1..8)
```

```
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION


        "This MIB object represents the frequency reference
         of a multi-frequency tone."
    ::={ pktcSigDevMultiFreqToneEntry 1}

pktcSigDevToneFirstFreqValue    OBJECT-TYPE
    SYNTAX       Unsigned32(0..4000)
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
      "This MIB object represents the value of the first
       frequency of a tone type.  A value of zero implies
       absence of the referenced frequency."
    ::={ pktcSigDevMultiFreqToneEntry 2}

pktcSigDevToneSecondFreqValue
  OBJECT-TYPE
    SYNTAX       Unsigned32(0..4000)
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
      "This MIB object represents the value of the second
       frequency of a tone type.  A value of zero implies
       absence of the referenced frequency."
    ::={ pktcSigDevMultiFreqToneEntry 3}

pktcSigDevToneThirdFreqValue    OBJECT-TYPE
    SYNTAX       Unsigned32(0..4000)
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
      "This MIB object represents the value of the third
       frequency of a tone type.  A value of zero implies
       absence of the referenced frequency."
    ::={ pktcSigDevMultiFreqToneEntry 4}

pktcSigDevToneFourthFreqValue    OBJECT-TYPE
    SYNTAX       Unsigned32(0..4000)
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
      "This MIB object represents the value of the fourth
       frequency of a tone type.  A
```

value of zero implies
absence of the referenced frequency."
::={ pktcSigDevMultiFreqToneEntry 5}

pktcSigDevToneFreqMode OBJECT-TYPE
SYNTAX INTEGER {
firstModulatedBySecond(1),
summation(2)

}
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This MIB object provides directive on the
modulation or summation of the frequencies
involved in the tone.

It is to be noted that while summation can
be done without any constraint on the number
of frequencies, the modulation (amplitude)
holds good only when there are two frequencies
(first and second).

Thus:
- If the mode is set to a value of
'firstModulatedBySecond(1)', the first frequency
MUST be modulated by the second, and the remaining
frequencies (third and fourth) ignored. The
percentage
of amplitude modulation to be applied
is defined by the MIB object
pktcSigDevToneFreqAmpModePrtg.

- If the mode is set to a value of
'summation(2)', all the frequencies MUST be
summed without any modulation.
"
::={ pktcSigDevMultiFreqToneEntry 6}

pktcSigDevToneFreqAmpModePrtg OBJECT-TYPE
SYNTAX Unsigned32(0..100)
MAX-ACCESS read-only
STATUS current
DESCRIPTION
"This MIB object represents the percentage of amplitude
modulation applied to the second frequency

```
        when the MIB object pktcSigDevToneFreqMode is
        set to a value of 'firstModulatedBySecond (1)'.

        If the MIB object pktcSigDevToneFreqMode is set to
        value of 'summation (2)', then this MIB object MUST be
        ignored."
    ::={ pktcSigDevMultiFreqToneEntry 7}

pktcSigDevToneDbLevel    OBJECT-TYPE
    SYNTAX       TenthdBm (-250..-110)
    UNITS
      "1/10 of a dBm"
    MAX-ACCESS   read-only



    STATUS       current
    DESCRIPTION
       "This MIB object contains the decibel level for each
        analog signal (tone) that is locally generated
        (versus in-band supervisory tones) and sourced to
        the a-b terminals (TE connection point).  Each tone
        in itself may consist of multiple frequencies, as
        defined by the MIB table pktcSigDevMultiFreqToneTable.

        This MIB object reflects the desired level at
        the Telco (POTS) a-b (T/R) terminals, including the
        effect of any MTA receiver gain (loss).  This is required
        so that locally generated tones are consistent with
        remotely generated in-band tones at the a-b terminals,
        consistent with user expectations.

        This MIB object must be set for each tone.
        When tones are formed by combining multi-frequencies,
        the level of each frequency
shall be set so as to result
        in the tone level specified in this object at the a-b
        (T/R) terminals.

        The wide range of levels for this Object is required
        to provide signal-generator levels across the wide
        range of gains (losses) -- but does not imply the entire
        range is to be achievable given the range of gains (losses)
        in the MTA."
  DEFVAL { -120 }
  ::={ pktcSigDevMultiFreqToneEntry 8}

 pktcSigDevToneFreqOnDuration OBJECT-TYPE
```

```
    SYNTAX      Unsigned32(0..5000)
    UNITS       "milliseconds"
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
      "This MIB object represents the duration for which the
       frequency reference corresponding to the tone type
       is turned on."
    ::={ pktcSigDevMultiFreqToneEntry 9}

 pktcSigDevToneFreqOffDuration OBJECT-TYPE
    SYNTAX      Unsigned32(0..5000)
    UNITS       "milliseconds"
    MAX-ACCESS
 read-only
    STATUS      current
    DESCRIPTION
      "This MIB object represents the duration for which the




       frequency reference corresponding to the tone type
       is turned off."
    ::={ pktcSigDevMultiFreqToneEntry 10}

 pktcSigDevToneFreqRepeatCount OBJECT-TYPE
    SYNTAX      Unsigned32(0..5000)
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
    "This MIB object indicates the number of times
    to repeat the cadence cycle represented by the
    on/off durations (refer to the MIB objects
    pktcSigDevToneFreqOnDuration and
    pktcSigDevToneFreqOffDuration).

    Setting this object may result in a tone duration that is
    longer or shorter than the overall signal duration
    specified by the time out (TO) object for the
    corresponding tone type.  If the value of this MIB
    Object indicates a longer duration than that
    specified by the TO, the latter overrules
the former,
    and the desired tone duration will be truncated according
    to the TO.

    However, if the repeat count results in a shorter
    tone duration than the signal duration specified by
```

```
    the TO, the tone duration defined by the repeat count
    takes precedence over the TO and will end the signal
    event.  In this case, the TO represents a time not to
    be exceeded for the signal.  It is recommended, to
    ensure proper telephony signaling, that the TO
    duration setting should always be longer than the
    desired repeat count-time duration.  A value of zero
    means the tone sequence is to be played once but not
    repeated."
    ::={ pktcSigDevMultiFreqToneEntry 11}

 pktcSigDevCidDelayAfterLR  OBJECT-TYPE
    SYNTAX       Unsigned32 (300..800)
    UNITS        "Milliseconds"
    MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
       "This object specifies the delay between
the end of the
        Line Reversal and the start of the FSK or DTMF signal.
        This MIB object is used only when pktcSigDevCidMode is
        set to a value of 'lrETS'.  This timing has a range of
        300 to 800 ms.



        The following table defines the default values
        for this MIB object, depending on the signal type
       (pktcSigDevCidMode), and MUST be followed:

       Value of pktcSigDevCidMode       Default value

        duringringingETS              any value  (not used)
        dtAsETS                      any value  (not used)
        rpAsETS                      any value  (not used)
        lrAsETS                     any value  (not used)
        lrETS                      400

        An attempt to set this object while the value of
        pktcSigDevCidMode is not set to a value of 'lrETS' will
        result in an 'inconsistentValue' error.

        The value of this
MIB object MUST NOT persist across MTA
        reboots."
    DEFVAL { 400 }
    ::= {pktcSigDevObjects 34 }
```

```
pktcSigDevCidDtmfStartCode OBJECT-TYPE
   SYNTAX      DtmfCode
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION
      "This object identifies optional start codes used when
       the MIB object pktcSigDevCidSigProtocol is set
       to a value of 'dtmf(2)'.

       Different countries define different caller id signaling
       codes to support caller identification.  When Dual-Tone
       Multi-Frequency (DTMF) is used, the caller id digits are
       preceded by a 'start code' digit, followed by the digit
       transmission sequence <S1>...<Sn> (where Sx represents
       the digits 0-9), and terminated by the 'end code' digit.

       For example,
         <A><S1>...<Sn> <D><S1>...<Sn> <B><S1>...<Sn> <C>.
       The start code for calling number delivery may be DTMF

       'A' or 'D'.  The start code for redirecting a number may be
       DTMF 'D'.  The DTMF code 'B' may be sent by the network
       as a start code for the transfer of information values,
       through which special events can be indicated to the
       user.  In some countries, the '*' or '#' may be used
       instead of 'A', 'B', 'C', or 'D'.

       The value of this MIB object MUST NOT persist across MTA




       reboots."
   REFERENCE
      "ETSI-EN-300-659-1 specification"
   DEFVAL {dtmfcodeA}
::= { pktcSigDevObjects 35 }

pktcSigDevCidDtmfEndCode OBJECT-TYPE
   SYNTAX      DtmfCode
   MAX-ACCESS  read-write
   STATUS      current
   DESCRIPTION
      "This object identifies optional end codes used when the
       pktcSigDevCidSigProtocol is set to a value of
       'dtmf(2)'.

       Different countries define different caller id signaling
       protocols to support caller
```

```
identification.  When
        Dual-Tone Multi-Frequency (DTMF) is used, the caller id
        digits are preceded by a 'start code' digit, followed by
        the digit transmission sequence <S1>...<Sn> (where Sx
        represents the digits 0-9), and terminated by the 'end
        code' digit.

        For example,
          <A><S1>...<Sn> <D><S1>...<Sn> <B><S1>...<Sn> <C>.

        The DTMF code 'C' may be sent by the network as an
        end code for the transfer of information values, through
        which special events can be indicated to the user.  In
        some countries, the '*' or '#' may be used instead of
        'A', 'B', 'C', or 'D'.

        The value of this MIB object MUST NOT persist across MTA
        reboots."
    REFERENCE
        "ETSI-EN-300-659-1 specification"
    DEFVAL {dtmfcodeC}
::= { pktcSigDevObjects 36 }

pktcSigDevVmwiSigProtocol  OBJECT-TYPE
    SYNTAX       PktcSubscriberSideSigProtocol
     MAX-ACCESS   read-write
    STATUS       current
    DESCRIPTION
       "This object identifies the subscriber line protocol used
        for signaling the information on Visual Message Waiting
        Indicator (VMWI).  Different countries define different
        VMWI signaling protocols to support VMWI service.



        Frequency shift keying (FSK) is most commonly used.
        DTMF is an alternative.

        The value of this MIB object MUST NOT persist across MTA
        reboots."
     DEFVAL { fsk }
::= { pktcSigDevObjects 37 }

pktcSigDevVmwiDelayAfterLR    OBJECT-TYPE
    SYNTAX       Unsigned32 (0|300..800)
    UNITS        "Milliseconds"
    MAX-ACCESS   read-write
    STATUS       current
```

```
    DESCRIPTION
      "This object specifies the delay between the end of the
       Line Reversal and the start of the FSK or DTMF signal.
       This object is only used when pktcSigDevVmwiMode
is
       set to a value of 'lrETS'.
       This timing has a range of 300 to 800 ms.

       The following table defines the default values
       for this MIB object, depending on the signal type
      (pktcSigDevVmwiMode), and MUST be followed:

       Value of pktcSigDevVmwiMode       Default value

       duringringingETS                  any value  (not used)
       dtAsETS                           any value  (not used)
       rpAsETS                           any value  (not used)
       lrAsETS                           any value  (not used)
       lrETS                             400

       An attempt to set this object while the value of
       pktcSigDevVmwiMode is not 'lrETS' will result in an
       'inconsistentValue' error.

       The value of this MIB object MUST NOT persist across MTA
       reboots."

    DEFVAL {400}
      ::= {pktcSigDevObjects 38 }

 pktcSigDevVmwiDtmfStartCode
OBJECT-TYPE
    SYNTAX      DtmfCode
    MAX-ACCESS  read-write
    STATUS      current
    DESCRIPTION
      "This object identifies optional start codes used when




       the pktcSigDevVmwiSigProtocol is set to a value of
       'dtmf(2)'.  Different countries define different On Hook
       Data Transmission Protocol signaling codes to support
       VMWI.

       When Dual-Tone Multi-Frequency (DTMF) is used, the VMWI
       digits are preceded by a 'start code' digit, followed
       by the digit transmission sequence <S1>...<Sn> (where
```

Sx represents the digits 0-9), and terminated by the 'end
code' digit.

For example,
<A><S1>...<Sn> <D><S1>...<Sn> <B><S1>...<Sn> <C>.

The start code for redirecting VMWI may be DTMF 'D'
The DTMF code 'B' may be sent by the network as a start
code for the transfer of information values, through
which special events can be indicated to the user. In
some countries, the '*' or '#' may be used instead of
'A', 'B', 'C', or 'D'.

The value of this MIB object MUST NOT persist across MTA
reboots."
REFERENCE
"ETSI-EN-300-659-1 specification"
DEFVAL {dtmfcodeA}
::= { pktcSigDevObjects 39 }

pktcSigDevVmwiDtmfEndCode OBJECT-TYPE
SYNTAX DtmfCode
MAX-ACCESS read-write
STATUS current
DESCRIPTION
"This object identifies an optional end code used when the
pktcSigDevVmwiSigProtocol is set to a value of
'dtmf(2)'. Different countries define different on-hook
Data Transmission Protocol signaling codes to support
VMWI.

When Dual-Tone Multi-Frequency (DTMF) is used, the VMWI
digits are preceded by a 'start code' digit, followed
by the digit transmission sequence
<S1>...<Sn> (where
Sx represents the digits 0-9), and terminated by the 'end
code' digit.

For example,
<A><S1>...<Sn> <D><S1>...<Sn> <B><S1>...<Sn> <C>.

The DTMF code 'C' may be sent by the network as an end code
for the transfer of information values, through which
special events can be indicated to the user. In some
countries, the '*' or '#' may be used instead of 'A',

'B', 'C', or 'D'.

The value of this MIB object MUST NOT persist across MTA reboots."

REFERENCE

"ETSI-EN-300-659-1 specification"

DEFVAL {dtmfcodeC}

::= { pktcSigDevObjects 40 }

pktcSigDevrpAsDtsDuration OBJECT-TYPE

SYNTAX Unsigned32 (0|200..500)

UNITS "Milliseconds"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

" This object specifies the duration of the rpASDTS ring

pulse prior to the start of the transmission of the FSK or DTMF containing the caller id information. It is only used when pktcSigDevCidMode is set to a value of 'rpAsETS'.

The following table defines the default values for this MIB object, depending on the signal type (pktcSigDevCidMode), and MUST be followed:

Value of pktcSigDevCidMode	Default value
duringringingETS	any value (not used)
dtAsETS	any value (not used)
rpAsETS	250
lrAsETS	any value (not used)
lrETS	any value (not used)

An attempt to set this object while the value of pktcSigDevCidMode is not 'rpAsETS' will result in an 'inconsistentValue' error.

The value of this MIB object MUST NOT persist across MTA reboots."

REFERENCE

"ETSI-EN-300-659-1 Specification and Belgacom BGC_D_48_9811_30_09_EDOC version 3.3"

DEFVAL { 250 }

::= {pktcSigDevObjects 41 }

```
--
-- The Endpoint Config Table is used to define attributes that
-- are specific to connection EndPoints.
--

pktcSigEndPntConfigTable  OBJECT-TYPE
  SYNTAX        SEQUENCE OF PktcSigEndPntConfigEntry
  MAX-ACCESS    not-accessible
  STATUS        current
  DESCRIPTION
     " This table describes the information pertaining to each
       endpoint of the MTA.  All entries in this table represent
       the provisioned endpoints provisioned with the information
       required by the MTA to maintain the NCS protocol
       communication with the CMS.  Each endpoint can be assigned
       to its own CMS.  If the specific endpoint does not have
       the corresponding CMS information in this table, the
       endpoint is considered as not
 provisioned with voice
       services.  Objects in this table do not persist across
       MTA reboots."
 ::=  { pktcSigEndPntConfigObjects 1 }

pktcSigEndPntConfigEntry  OBJECT-TYPE
  SYNTAX        PktcSigEndPntConfigEntry
  MAX-ACCESS    not-accessible
  STATUS        current
  DESCRIPTION
     "Each entry in the pktcSigEndPntConfigTable represents
      required signaling parameters for the specific endpoint
      provisioned with voice services.  The conceptual rows MUST
      NOT persist across MTA reboots."
  INDEX { ifIndex }
  ::= { pktcSigEndPntConfigTable 1 }

PktcSigEndPntConfigEntry  ::= SEQUENCE {
  pktcSigEndPntConfigCallAgentId             SnmpAdminString,
  pktcSigEndPntConfigCallAgentUdpPort        InetPortNumber,
  pktcSigEndPntConfigPartialDialTO           Unsigned32,
  pktcSigEndPntConfigCriticalDialTO          Unsigned32,
  pktcSigEndPntConfigBusyToneTO              Unsigned32,
  pktcSigEndPntConfigDialToneTO
    Unsigned32,
  pktcSigEndPntConfigMessageWaitingTO        Unsigned32,
  pktcSigEndPntConfigOffHookWarnToneTO       Unsigned32,
  pktcSigEndPntConfigRingingTO               Unsigned32,
```

```
  pktcSigEndPntConfigRingBackTO            Unsigned32,
  pktcSigEndPntConfigReorderToneTO         Unsigned32,
  pktcSigEndPntConfigStutterDialToneTO     Unsigned32,



  pktcSigEndPntConfigTSMax                 Unsigned32,
  pktcSigEndPntConfigMax1                  Unsigned32,
  pktcSigEndPntConfigMax2                  Unsigned32,
  pktcSigEndPntConfigMax1QEnable           TruthValue,
  pktcSigEndPntConfigMax2QEnable           TruthValue,
  pktcSigEndPntConfigMWD                   Unsigned32,
  pktcSigEndPntConfigTdinit                Unsigned32,
  pktcSigEndPntConfigTdmin                 Unsigned32,
  pktcSigEndPntConfigTdmax                 Unsigned32,
  pktcSigEndPntConfigRtoMax                Unsigned32,
  pktcSigEndPntConfigRtoInit
        Unsigned32,
  pktcSigEndPntConfigLongDurationKeepAlive  Unsigned32,
  pktcSigEndPntConfigThist                 Unsigned32,
  pktcSigEndPntConfigStatus                RowStatus,
  pktcSigEndPntConfigCallWaitingMaxRep     Unsigned32,
  pktcSigEndPntConfigCallWaitingDelay      Unsigned32,
  pktcSigEndPntStatusCallIpAddressType     InetAddressType,
  pktcSigEndPntStatusCallIpAddress         InetAddress,
  pktcSigEndPntStatusError                 INTEGER,
  pktcSigEndPntConfigMinHookFlash          Unsigned32,
  pktcSigEndPntConfigMaxHookFlash          Unsigned32,
  pktcSigEndPntConfigPulseDialInterdigitTime Unsigned32,
  pktcSigEndPntConfigPulseDialMinMakeTime   Unsigned32,
  pktcSigEndPntConfigPulseDialMaxMakeTime   Unsigned32,
  pktcSigEndPntConfigPulseDialMinBreakTime  Unsigned32,
  pktcSigEndPntConfigPulseDialMaxBreakTime  Unsigned32
  }

pktcSigEndPntConfigCallAgentId    OBJECT-TYPE
  SYNTAX     SnmpAdminString(SIZE
(3..255))
  MAX-ACCESS  read-create
  STATUS     current
  DESCRIPTION
     " This object contains a string indicating the call agent
       name (e.g., ca@example.com).  The call agent name, after
       the character '@', MUST be a fully qualified domain name
       (FQDN) and MUST have a corresponding pktcMtaDevCmsFqdn
       entry in the pktcMtaDevCmsTable.  The object
       pktcMtaDevCmsFqdn is defined in the PacketCable MIBMTA
       Specification.  For each particular endpoint, the MTA MUST
```

use the current value of this object to communicate with
the corresponding CMS. The MTA MUST update this object
with the value of the 'Notified Entity' parameter of the
NCS message. Because of the high importance of this object
to the ability of the MTA to maintain reliable NCS
communication with the CMS, it is highly recommended not
to change this object's value using SNMP during normal

operation."

::= { pktcSigEndPntConfigEntry 1 }

pktcSigEndPntConfigCallAgentUdpPort OBJECT-TYPE
SYNTAX InetPortNumber (1025..65535)
MAX-ACCESS read-create
STATUS current
DESCRIPTION
" This object contains the current value of the User
Datagram Protocol (UDP) receive port on which the
call agent will receive NCS from the endpoint.
For each particular endpoint, the MTA MUST use the current
value of this object to communicate with the corresponding
CMS. The MTA MUST update this object with the value of the
'Notified Entity' parameter of the NCS message. If the
Notified Entity parameter does not contain a CallAgent
port, the MTA MUST update this object with the default
value of 2727. Because of the high importance of this
object to the ability of the MTA to maintain reliable NCS
communication with the CMS, it is highly recommended
not
to change this object's value using SNMP during normal
operation."
REFERENCE
"PacketCable NCS Specification"
DEFVAL { 2727 }
::= { pktcSigEndPntConfigEntry 2 }

pktcSigEndPntConfigPartialDialTO OBJECT-TYPE
SYNTAX Unsigned32
UNITS "seconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION
"This object contains the value of the partial dial
time out.
The time out (TO) elements are intended to limit the time a

tone or frequency is generated. When this MIB object is set to a value of '0', the MTA MUST NOT generate the corresponding frequency or tone, regardless of the definitions pertaining to frequency, tone duration, or cadence."

REFERENCE
"PacketCable NCS Specification"

DEFVAL { 16 }

::= { pktcSigEndPntConfigEntry 3 }

pktcSigEndPntConfigCriticalDialTO OBJECT-TYPE

SYNTAX Unsigned32

UNITS
"seconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION
"This object contains the value of the critical dial time out.
The time out (TO) elements are intended to limit the time a tone or frequency is generated. When this MIB object is set to a value of '0', the MTA MUST NOT generate the corresponding frequency or tone, regardless of the definitions pertaining to frequency, tone duration, or cadence."

REFERENCE
"PacketCable NCS Specification"

DEFVAL { 4 }

::= { pktcSigEndPntConfigEntry 4 }

pktcSigEndPntConfigBusyToneTO OBJECT-TYPE

SYNTAX Unsigned32

UNITS "seconds"

MAX-ACCESS read-create

STATUS current

DESCRIPTION
" This object contains the default time out value for busy tone. The MTA MUST NOT update this object with the value provided in the NCS message (if present). If the
value of the object is modified by the SNMP Management Station, the MTA MUST use the new value as a default only for a new signal requested by the NCS message.
The time out (TO) elements are intended to limit the time a tone or frequency is generated. When this MIB object is

set to a value of '0', the MTA MUST NOT generate the
corresponding frequency or tone, regardless of the
definitions pertaining to frequency, tone duration, or
cadence."
REFERENCE
"PacketCable NCS Specification"
DEFVAL { 30 }
::= { pktcSigEndPntConfigEntry 5 }

pktcSigEndPntConfigDialToneTO OBJECT-TYPE
SYNTAX Unsigned32
UNITS "seconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION
" This object contains the default time out value for dial
tone. The MTA MUST NOT update this object with the
value provided in the NCS message (if present).
If

the value of the object is modified by the SNMP Management
Station, the MTA MUST use the new value as a default only
for a new signal requested by the NCS message.
The time out (TO) elements are intended to limit the time
a tone or frequency is generated. When this MIB object is
set to a value of '0', the MTA MUST NOT generate the
corresponding frequency or tone, regardless of the
definitions pertaining to frequency, tone duration, or
cadence."
REFERENCE
"PacketCable NCS Specification"
DEFVAL { 16 }
::= { pktcSigEndPntConfigEntry 6 }

pktcSigEndPntConfigMessageWaitingTO OBJECT-TYPE
SYNTAX Unsigned32
UNITS "seconds"
MAX-ACCESS read-create
STATUS current
DESCRIPTION
" This object contains the default time out value for message
waiting indicator. The MTA MUST NOT update this object
with the value
provided in the NCS message (if
present). If the value of the object is modified by the
SNMP Manager application, the MTA MUST use the new value

```
        as a default only for a new signal requested by the NCS
        message.
        The time out (TO) elements are intended to limit the time
        a tone or frequency is generated.  When this MIB object is
        set to a value of '0', the MTA MUST NOT generate the
        corresponding frequency or tone, regardless of the
        definitions pertaining to frequency, tone duration, or
        cadence."
    REFERENCE
       "PacketCable NCS Specification"
    DEFVAL    { 16 }
    ::= { pktcSigEndPntConfigEntry 7 }

pktcSigEndPntConfigOffHookWarnToneTO     OBJECT-TYPE
    SYNTAX       Unsigned32
    UNITS        "seconds"
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
       " This object contains the default time out value for the
        off-hook warning tone.  The MTA MUST
 NOT update this object
        with the value provided in the NCS message (if present).  If
        the value of the object is modified by the SNMP Manager



        application, the MTA MUST use the new value as a default
        only for a new signal requested by the NCS message.  The
        time out (TO) elements are intended to limit the time a tone
        or frequency is generated.  When this MIB object is set to a
        value of '0', the MTA MUST NOT generate the corresponding
        frequency or tone, regardless of the definitions pertaining
        to frequency, tone duration, or cadence."
    REFERENCE
       "PacketCable NCS Specification"
    DEFVAL { 0 }
    ::= { pktcSigEndPntConfigEntry 8 }

pktcSigEndPntConfigRingingTO     OBJECT-TYPE
    SYNTAX       Unsigned32
    UNITS        "seconds"
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
       " This object contains the default time out value for
        ringing.  The MTA
```

```
 MUST NOT update this object with the
        value provided in the NCS message (if present).  If
        the value of the object is modified by the SNMP Management
        Station, the MTA MUST use the new value as a default only
        for a new signal requested by the NCS message.
        The time out (TO) elements are intended to limit the time
        a tone or frequency is generated.  When this MIB object is
        set to a value of '0', the MTA MUST NOT generate the
        corresponding frequency or tone, regardless of the
        definitions pertaining to frequency, tone duration, or
        cadence."
    REFERENCE
       "PacketCable NCS Specification"
    DEFVAL    { 180 }
    ::= { pktcSigEndPntConfigEntry 9 }

pktcSigEndPntConfigRingBackTO     OBJECT-TYPE
    SYNTAX       Unsigned32
    UNITS        "seconds"
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
       " This object contains the default time out value for ring

       back.  The MTA MUST NOT update this object with the
        value provided in the NCS message (if present).  If
        the value of the object is modified by the SNMP Management
        Station, the MTA MUST use the new value as a default only
        for a new signal requested by the NCS message.
        The time out (TO) elements are intended to limit the time



        a tone or frequency is generated.  When this MIB object is
        set to a value of '0', the MTA MUST NOT generate the
        corresponding frequency or tone, regardless of the
        definitions pertaining to frequency, tone duration, or
        cadence."
    REFERENCE
       "PacketCable NCS Specification"
    DEFVAL    { 180 }
    ::= { pktcSigEndPntConfigEntry 10 }

pktcSigEndPntConfigReorderToneTO     OBJECT-TYPE
    SYNTAX       Unsigned32
    UNITS        "seconds"
    MAX-ACCESS   read-create
    STATUS       current
```

```
  DESCRIPTION
      " This object contains the default time
 out value for reorder
        tone.  The MTA MUST NOT update this object with the
        value provided in the NCS message (if present).  If
        the value of the object is modified by the SNMP Management
        Station, the MTA MUST use the new value as a default only
        for a new signal requested by the NCS message.
        The time out (TO) elements are intended to limit the time
        a tone or frequency is generated.  When this MIB object is
        set to a value of '0', the MTA MUST NOT generate the
        corresponding frequency or tone, regardless of the
        definitions pertaining to frequency, tone duration, or
        cadence."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL    { 30 }
  ::= { pktcSigEndPntConfigEntry 11 }

pktcSigEndPntConfigStutterDialToneTO     OBJECT-TYPE
  SYNTAX       Unsigned32
  UNITS        "seconds"
  MAX-ACCESS   read-create
  STATUS       current
  DESCRIPTION
     " This object
 contains the default time out value for stutter
        dial tone.  The MTA MUST NOT update this object with the
        value provided in the NCS message (if present).  If
        the value of the object is modified by the SNMP Management
        Station, the MTA MUST use the new value as a default only
        for a new signal requested by the NCS message.
        The time out (TO) elements are intended to limit the time
        a tone or frequency is generated.  When this MIB object is
        set to a value of '0', the MTA MUST NOT generate the
        corresponding frequency or tone, regardless of the
        definitions pertaining to frequency, tone duration, or
        cadence."
  REFERENCE
        "PacketCable NCS Specification"
  DEFVAL    { 16 }
  ::= { pktcSigEndPntConfigEntry 12 }

pktcSigEndPntConfigTSMax     OBJECT-TYPE
  SYNTAX      Unsigned32
```

```
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
        "This MIB object
 is used as part of an NCS
        retransmission algorithm.  Prior to any retransmission,
        the MTA must check to make sure that the time elapsed
        since the sending of the initial datagram does not
        exceed the value specified by this MIB object.  If more
        than Tsmax time has elapsed, then the retransmissions
        MUST cease.

        Refer to the MIB object pktcSigEndPntConfigThist for
        information on when the endpoint becomes disconnected."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 20 }
  ::= { pktcSigEndPntConfigEntry 13 }

pktcSigEndPntConfigMax1     OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object contains the suspicious error threshold for
      signaling messages.  The pktcSigEndPntConfigMax1 object
      indicates the retransmission threshold at which the MTA MAY
      actively query the domain
 name server (DNS) in order to
      detect the possible change of call agent interfaces."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 5 }
  ::= { pktcSigEndPntConfigEntry 14 }

pktcSigEndPntConfigMax2     OBJECT-TYPE
  SYNTAX      Unsigned32
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION



     "This object contains the disconnect error threshold for
      signaling messages.  The pktcSigEndPntConfigMax2 object
      indicates the retransmission threshold at which the MTA
      SHOULD contact the DNS one more time to see if any other
      interfaces to the call agent have become available."
```

```
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 7 }
  ::= { pktcSigEndPntConfigEntry 15 }

pktcSigEndPntConfigMax1QEnable     OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object enables/disables the Max1 domain name server
      (DNS)
 query operation when the pktcSigEndPntConfigMax1
      threshold has been reached.
      A value of true(1) indicates enabling, and a value of
      false(2) indicates disabling."
  DEFVAL { true }
  ::= { pktcSigEndPntConfigEntry 16 }

pktcSigEndPntConfigMax2QEnable     OBJECT-TYPE
  SYNTAX      TruthValue
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object enables/disables the Max2 domain name server
      (DNS) query operation when the pktcSigEndPntConfigMax2
      threshold has been reached.
      A value of true(1) indicates enabling, and a value of
      false(2) indicates disabling."
  DEFVAL { true }
  ::= { pktcSigEndPntConfigEntry 17 }

pktcSigEndPntConfigMWD     OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "seconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "Maximum Waiting Delay (MWD) contains the maximum number of
      seconds an MTA waits, after powering
 on, before initiating
      the restart procedure with the call agent."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 600 }
```

```
  ::= { pktcSigEndPntConfigEntry 18 }

pktcSigEndPntConfigTdinit     OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "seconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This MIB object represents the 'disconnected' initial
      waiting delay within the context of an MTA's 'disconnected
      procedure'.  The 'disconnected procedure' is initiated when
      an endpoint becomes 'disconnected' while attempting to
      communicate with a call agent.

      The 'disconnected timer' associated with the 'disconnected
      Procedure' is initialized to a random value, uniformly
      distributed between zero and the value contained in this
      MIB object.

      For more information on the usage of this timer, please
      refer to the PacketCable NCS Specification."
   REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 15 }
  ::= { pktcSigEndPntConfigEntry 19 }

pktcSigEndPntConfigTdmin     OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "seconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
        "This MIB object represents the 'disconnected' minimum
         waiting delay within the context of an MTA's
         'disconnected procedure', specifically when local user
         activity is detected.
         The 'disconnected procedure' is initiated when
         an endpoint becomes 'disconnected' while attempting to
         communicate with a call agent.
         For more information on the usage of this timer, please
         refer to the PacketCable NCS Specification."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 15 }
  ::= { pktcSigEndPntConfigEntry 20 }

pktcSigEndPntConfigTdmax     OBJECT-TYPE
  SYNTAX      Unsigned32
```

```
  UNITS
  "seconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object contains the maximum number of seconds the MTA
       waits, after a disconnect, before initiating the
       disconnected procedure with the call agent.
        "
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 600 }
  ::= { pktcSigEndPntConfigEntry 21 }

pktcSigEndPntConfigRtoMax     OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "seconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     "This object specifies the maximum number of seconds the MTA
      waits for a response to an NCS message before initiating
      a retransmission."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 4 }
  ::= { pktcSigEndPntConfigEntry 22 }

pktcSigEndPntConfigRtoInit     OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "milliseconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION

    " This object contains the initial number of seconds for the
       retransmission timer."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 200 }
  ::= { pktcSigEndPntConfigEntry 23 }

pktcSigEndPntConfigLongDurationKeepAlive     OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "minutes"
```

```
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " Specifies a time out value, in minutes, for sending long
       duration call notification messages."



  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 60 }
  ::= { pktcSigEndPntConfigEntry 24 }

pktcSigEndPntConfigThist  OBJECT-TYPE
  SYNTAX      Unsigned32
  UNITS       "seconds"
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " Time out period, in seconds, before no response is declared."
  REFERENCE
     "PacketCable NCS Specification"
  DEFVAL { 30 }
  ::= { pktcSigEndPntConfigEntry 25 }

pktcSigEndPntConfigStatus     OBJECT-TYPE
   SYNTAX      RowStatus
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object contains the Row Status associated with the
       pktcSigEndPntConfigTable.  There are no restrictions or
       dependencies amidst the columnar objects before this
       row can be activated or for modifications of the
       columnar objects when this object is set to a
       value of 'active(1)."
  ::= { pktcSigEndPntConfigEntry 26 }

pktcSigEndPntConfigCallWaitingMaxRep     OBJECT-TYPE
  SYNTAX      Unsigned32 (0..10)
  MAX-ACCESS  read-create
  STATUS      current
  DESCRIPTION
     " This object contains the default value of the maximum
       number of repetitions of the Call Waiting tone that the
       MTA will play from a single CMS request.  The MTA MUST NOT
       update this object with the information provided in the
       NCS message (if present).  If the value of the object is
```

```
        modified by the SNMP
 Manager application, the MTA MUST use
        the new value as a default only for a new signal
        requested by the NCS message."
   DEFVAL    { 1 }
   ::= { pktcSigEndPntConfigEntry 27 }

pktcSigEndPntConfigCallWaitingDelay     OBJECT-TYPE
   SYNTAX       Unsigned32 (1..100)



   UNITS        "seconds"
   MAX-ACCESS   read-create
   STATUS       current
   DESCRIPTION
      " This object contains the delay between repetitions of the
        Call Waiting tone that the MTA will play from a single CMS
        request."
   DEFVAL    { 10 }
   ::= { pktcSigEndPntConfigEntry 28 }

pktcSigEndPntStatusCallIpAddressType  OBJECT-TYPE
   SYNTAX      InetAddressType
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
     " This object contains the type of Internet address contained
       in the MIB object 'pktcSigEndPntStatusCallIpAddress'.

       Since pktcSigEndPntStatusCallIpAddress is expected to
       contain an IP address, a value of dns(16)
 is disallowed."

   ::= { pktcSigEndPntConfigEntry 29 }

pktcSigEndPntStatusCallIpAddress  OBJECT-TYPE
   SYNTAX      InetAddress
   MAX-ACCESS  read-only
   STATUS      current
   DESCRIPTION
     " This MIB object contains the chosen IP address of the CMS
       currently being used for the corresponding endpoint.

       The device determines the IP address by using DNS to
       resolve the IP address of the CMS from the FQDN stored in
       the MIB object 'pktcSigEndPntConfigCallAgentId'.  The
       processes are outlined in the PacketCable NCS and Security
```

```
        specifications, and MUST be followed by the MTA.

        The IP address type contained in this MIB object is
        indicated by pktcSigEndPntStatusCallIpAddressType."
    REFERENCE
       "PacketCable NCS Specification;
        PacketCable Security specification, [PKT-SP-SEC]."
::= { pktcSigEndPntConfigEntry 30 }

pktcSigEndPntStatusError  OBJECT-TYPE
    SYNTAX INTEGER {
            operational
 (1),
            noSecurityAssociation (2),



            disconnected (3)
           }
    MAX-ACCESS   read-only
    STATUS  current
    DESCRIPTION
      " This object contains the error status for this interface.
        The operational status indicates that all operations
        necessary to put the line in service have occurred, and the
        CMS has acknowledged the Restart In Progress (RSIP)
        message successfully.  If pktcMtaDevCmsIpsecCtrl is enabled
        for the associated call agent, the noSecurityAssociation
        status indicates that no Security Association (SA) yet
        exists for this endpoint.  If pktcMtaDevCmsIpsecCtrl is
        disabled for the associated call agent, the
        noSecurityAssociation status is not applicable and should
        not be used by the MTA.  The disconnected status indicates
        one of the following two:
        If pktcMtaDevCmsIpsecCtrl is disabled, then no security
        association
 is involved with this endpoint.  The NCS
        signaling software is in process of establishing the NCS
        signaling link via an RSIP exchange.
        Otherwise, when pktcMtaDevCmsIpsecCtrl is enabled,
        security Association has been established, and the NCS
        signaling software is in process of establishing the NCS
        signaling link via an RSIP exchange."
    ::= { pktcSigEndPntConfigEntry 31 }

pktcSigEndPntConfigMinHookFlash    OBJECT-TYPE
    SYNTAX       Unsigned32 (20..1550)
    UNITS        "Milliseconds"
```

```
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
     " This is the minimum time a line needs to be on-hook for a
       valid hook flash.  The value of this object MUST be
       greater than the value of
       pktcSigEndPntConfigPulseDialMaxBreakTime.  The value of
       pktcSigEndPntConfigMinHookFlash MUST be less than
       pktcSigEndPntConfigMaxHookFlash.  This object MUST only be
       set via the
 MTA configuration during the provisioning
       process.
         Furthermore, given the possibility for the 'pulse dial'
         and 'hook flash' to overlap, the value of this object
         MUST be greater than the value contained by the MIB
         Object 'pktcSigEndPntConfigPulseDialMaxMakeTime'."
  DEFVAL { 300 }
  ::= { pktcSigEndPntConfigEntry 32 }




pktcSigEndPntConfigMaxHookFlash    OBJECT-TYPE
  SYNTAX       Unsigned32 (20..1550)
  UNITS        "Milliseconds"
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
     " This is the maximum time a line needs to be on-hook for a
       valid hook flash.  The value of
       pktcSigEndPntConfigMaxHookFlash MUST be greater than
       pktcSigEndPntConfigMinHookFlash.  This object MUST only be
       set via the MTA configuration during the provisioning
       process."
  DEFVAL { 800 }
  ::= { pktcSigEndPntConfigEntry 33 }

pktcSigEndPntConfigPulseDialInterdigitTime
   OBJECT-TYPE
  SYNTAX       Unsigned32 (100..1500)
  UNITS        "Milliseconds"
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
     " This is the pulse dial inter-digit time out.  This object
       MUST only be set via the MTA configuration during the
       provisioning process."
  DEFVAL { 100 }
```

::= { pktcSigEndPntConfigEntry 34 }

pktcSigEndPntConfigPulseDialMinMakeTime OBJECT-TYPE
SYNTAX Unsigned32 (20..200)
UNITS "Milliseconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
" This is the minimum make pulse width for the dial pulse.
The value of pktcSigEndPntConfigPulseDialMinMakeTime MUST
be less than pktcSigEndPntConfigPulseDialMaxMakeTime. This
object MUST only be set via the MTA configuration during
the provisioning process."
DEFVAL { 25 }
::= { pktcSigEndPntConfigEntry 35 }

pktcSigEndPntConfigPulseDialMaxMakeTime OBJECT-TYPE
SYNTAX Unsigned32 (20..200)
UNITS "Milliseconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
" This is the maximum make pulse width for the dial pulse.

The value of pktcSigEndPntConfigPulseDialMaxMakeTime MUST
be greater than pktcSigEndPntConfigPulseDialMinMakeTime.
This object MUST only be provided via the configuration
file during the provisioning process.
Furthermore, given the possibility for the 'pulse dial'
and 'hook flash' to overlap, the value of this object MUST
be less than the value contained by the MIB object
pktcSigEndPntConfigMinHookFlash."
DEFVAL { 55 }
::= { pktcSigEndPntConfigEntry 36 }

pktcSigEndPntConfigPulseDialMinBreakTime OBJECT-TYPE
SYNTAX Unsigned32 (20..200)
UNITS "Milliseconds"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
" This is the minimum break pulse width
for the dial pulse.
The value of pktcSigEndPntConfigPulseDialMinBreakTime MUST
be less than pktcSigEndPntConfigPulseDialMaxBreakTime.
This object must only be provided via the configuration

```
        file during the provisioning process."
  DEFVAL { 45 }
  ::= { pktcSigEndPntConfigEntry 37 }

pktcSigEndPntConfigPulseDialMaxBreakTime    OBJECT-TYPE
  SYNTAX       Unsigned32 (20..200)
  UNITS        "Milliseconds"
  MAX-ACCESS   read-only
  STATUS       current
  DESCRIPTION
      " This is the maximum break pulse width for the dial pulse.
        The value of pktcSigEndPntConfigPulseDialMaxBreakTime MUST
        be greater than pktcSigEndPntConfigPulseDialMinBreakTime.
        This object MUST only be provided via the configuration
        file during the provisioning process."
  DEFVAL { 75 }
  ::= { pktcSigEndPntConfigEntry 38 }

--
-- notification group is for future extension.
--
pktcSigNotification  OBJECT IDENTIFIER ::= {
 pktcIetfSigMib 0 }
pktcSigConformance   OBJECT IDENTIFIER ::= { pktcIetfSigMib 2 }
pktcSigCompliances   OBJECT IDENTIFIER ::= { pktcSigConformance 1 }
pktcSigGroups        OBJECT IDENTIFIER ::= { pktcSigConformance 2 }

--



-- compliance statements
--

pktcSigBasicCompliance  MODULE-COMPLIANCE
  STATUS     current
  DESCRIPTION
      " The compliance statement for MTAs that implement
        NCS signaling."

MODULE  -- pktcIetfSigMib

---
-- Unconditionally mandatory groups for all MTAs
---

MANDATORY-GROUPS {
  pktcSigDeviceGroup,
```

```
  pktcSigEndpointGroup
}
---
-- Conditionally mandatory groups for MTAs
---

GROUP pktcInternationalGroup
  DESCRIPTION
     " This group is mandatory only for MTAs implementing
       international telephony features."

GROUP pktcLLinePackageGroup
  DESCRIPTION
     " This group is mandatory only for MTAs implementing the L
       line package."

GROUP pktcELinePackageGroup
  DESCRIPTION
     " This group is mandatory only
 for MTAs implementing the E
       Line Package."
  ::={ pktcSigCompliances 1 }

pktcSigDeviceGroup  OBJECT-GROUP
  OBJECTS {
  pktcSigDevCodecMax,
  pktcSigDevEchoCancellation,
  pktcSigDevSilenceSuppression,
  pktcSigDevR0Cadence,
  pktcSigDevR1Cadence,
  pktcSigDevR2Cadence,
  pktcSigDevR3Cadence,



  pktcSigDevR4Cadence,
  pktcSigDevR5Cadence,
  pktcSigDevR6Cadence,
  pktcSigDevR7Cadence,
  pktcSigDevRgCadence,
  pktcSigDevRsCadence,
  pktcSigDefCallSigDscp,
  pktcSigDefMediaStreamDscp,
  pktcSigDevVmwiMode,
  pktcSigCapabilityType,
  pktcSigCapabilityVersion,
  pktcSigCapabilityVendorExt,
  pktcSigDefNcsReceiveUdpPort
```

```
    }
    STATUS current
    DESCRIPTION
        "Group of MIB objects containing signaling configuration
         information that is applicable per-device."
    ::= { pktcSigGroups 1 }

  pktcSigEndpointGroup  OBJECT-GROUP
    OBJECTS {
    pktcSigEndPntConfigCallAgentId,
    pktcSigEndPntConfigCallAgentUdpPort,

    pktcSigEndPntConfigPartialDialTO,
    pktcSigEndPntConfigCriticalDialTO,
    pktcSigEndPntConfigBusyToneTO,
    pktcSigEndPntConfigDialToneTO,
    pktcSigEndPntConfigMessageWaitingTO,
    pktcSigEndPntConfigOffHookWarnToneTO,
    pktcSigEndPntConfigRingingTO,
    pktcSigEndPntConfigRingBackTO,
    pktcSigEndPntConfigReorderToneTO,
    pktcSigEndPntConfigStutterDialToneTO,
    pktcSigEndPntConfigTSMax,
    pktcSigEndPntConfigMax1,
    pktcSigEndPntConfigMax2,
    pktcSigEndPntConfigMax1QEnable,
    pktcSigEndPntConfigMax2QEnable,
    pktcSigEndPntConfigMWD,
    pktcSigEndPntConfigTdinit,
    pktcSigEndPntConfigTdmin,
    pktcSigEndPntConfigTdmax,
    pktcSigEndPntConfigRtoMax,
    pktcSigEndPntConfigRtoInit,
    pktcSigEndPntConfigLongDurationKeepAlive,
    pktcSigEndPntConfigThist,
    pktcSigEndPntConfigStatus,



    pktcSigEndPntConfigCallWaitingMaxRep,
    pktcSigEndPntConfigCallWaitingDelay,
    pktcSigEndPntStatusCallIpAddressType,
    pktcSigEndPntStatusCallIpAddress,
    pktcSigEndPntStatusError
     }
    STATUS current
    DESCRIPTION
        "Group of MIB objects containing signaling configuration
```

```
        information that is applicable per-endpoint."
    ::= { pktcSigGroups 2 }

pktcInternationalGroup    OBJECT-GROUP
    OBJECTS {
    pktcSigEndPntConfigMinHookFlash,
    pktcSigEndPntConfigMaxHookFlash,
    pktcSigEndPntConfigPulseDialInterdigitTime,
    pktcSigEndPntConfigPulseDialMinMakeTime,
    pktcSigEndPntConfigPulseDialMaxMakeTime,
    pktcSigEndPntConfigPulseDialMinBreakTime,
    pktcSigEndPntConfigPulseDialMaxBreakTime,
    pktcSigDevRingCadence,
    pktcSigDevCidSigProtocol,
    pktcSigDevCidDelayAfterLR,
    pktcSigDevCidDtmfStartCode,
    pktcSigDevCidDtmfEndCode,
    pktcSigDevVmwiSigProtocol,
    pktcSigDevVmwiDelayAfterLR,
    pktcSigDevVmwiDtmfStartCode,
    pktcSigDevVmwiDtmfEndCode,
    pktcSigDevrpAsDtsDuration,
    pktcSigDevCidMode,
    pktcSigDevCidAfterRing,
    pktcSigDevCidAfterDTAS,
    pktcSigDevCidAfterRPAS,
    pktcSigDevRingAfterCID,
     pktcSigDevCidDTASAfterLR,
    pktcSigDevVmwiMode,
    pktcSigDevVmwiAfterDTAS,
    pktcSigDevVmwiAfterRPAS,
    pktcSigDevVmwiDTASAfterLR,
    pktcSigPowerRingFrequency,
    pktcSigPulseSignalFrequency,
    pktcSigPulseSignalDbLevel,
    pktcSigPulseSignalDuration,
    pktcSigPulseSignalPulseInterval,
    pktcSigPulseSignalRepeatCount,
    pktcSigDevToneDbLevel,



    pktcSigDevToneFreqCounter,
    pktcSigDevToneWholeToneRepeatCount,
    pktcSigDevToneSteady,
    pktcSigDevToneFirstFreqValue,
    pktcSigDevToneSecondFreqValue,
    pktcSigDevToneThirdFreqValue,
```

```
  pktcSigDevToneFourthFreqValue,
  pktcSigDevToneFreqMode,
  pktcSigDevToneFreqAmpModePrtg,
  pktcSigDevToneFreqOnDuration,
  pktcSigDevToneFreqOffDuration,
  pktcSigDevToneFreqRepeatCount
  }
  STATUS current
  DESCRIPTION
     " Group of objects that extend the behavior of existing
       objects to support operations in the widest possible set
       of international marketplaces.
   Note that many of these
       objects represent a superset of behaviors described in
       other objects within this MIB module."
  ::= { pktcSigGroups 3 }

pktcLLinePackageGroup  OBJECT-GROUP
  OBJECTS {
  pktcSigDevR0Cadence,
  pktcSigDevR1Cadence,
  pktcSigDevR2Cadence,
  pktcSigDevR3Cadence,
  pktcSigDevR4Cadence,
  pktcSigDevR5Cadence,
  pktcSigDevR6Cadence,
  pktcSigDevR7Cadence,
  pktcSigDevRgCadence,
  pktcSigDevRsCadence
  }
  STATUS current
  DESCRIPTION
  "Group of Objects to support the L line package."
  ::= { pktcSigGroups 4 }

pktcELinePackageGroup  OBJECT-GROUP
  OBJECTS {
  pktcSigDevR0Cadence,
  pktcSigDevR1Cadence,
  pktcSigDevR2Cadence,
  pktcSigDevR3Cadence,
  pktcSigDevR4Cadence,
  pktcSigDevR5Cadence,



  pktcSigDevR6Cadence,
  pktcSigDevR7Cadence,
```

pktcSigDevRgCadence,
pktcSigDevRsCadence,
pktcSigPulseSignalFrequency,
pktcSigPulseSignalDbLevel,
pktcSigPulseSignalDuration,
pktcSigPulseSignalPulseInterval,
pktcSigPulseSignalRepeatCount,
pktcSigDevRingCadence
}
STATUS current
DESCRIPTION
"Group of Objects to support the E line package."
::= { pktcSigGroups 5 }

END

Found in path(s):
* /mibble-commercial-mibs-2-9-3-jar/mibs/ietf/PKTC-IETF-SIG-MIB

1.461 springsource-javax-jms 1.1.0

1.461.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* @(#)ObjectMessage.java 1.19 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/ObjectMessage.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)ResourceAllocationException.java 1.4 01/02/16
*
* Copyright 1997-1999 Sun Microsystems, Inc. All Rights Reserved.
*
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/ServerSession.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)ServerSessionPool.java 1.12 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/ServerSessionPool.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)StreamMessage.java 1.40 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/StreamMessage.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)MessageProducer.java 1.25 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/MessageProducer.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)Destination.java 1.16 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/Destination.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)InvalidClientIDException.java 1.8 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/InvalidClientIDException.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)Topic.java 1.17 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/Topic.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)TopicPublisher.java 1.30 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/TopicPublisher.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)QueueConnection.java 1.22 02/04/10
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/QueueConnection.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)ConnectionFactory.java 1.11 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/ConnectionFactory.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)InvalidDestinationException.java 1.8 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/InvalidDestinationException.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)DeliveryMode.java 1.9 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/DeliveryMode.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)QueueReceiver.java 1.21 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/QueueReceiver.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)TemporaryQueue.java 1.13 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/TemporaryQueue.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)Connection.java 1.22 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/Connection.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)Queue.java 1.16 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/Queue.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)MapMessage.java 1.35 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/MapMessage.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)ExceptionListener.java 1.8 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/ExceptionListener.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)XAQueueSession.java 1.11 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/XAQueueSession.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)InvalidSelectorException.java 1.6 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/InvalidSelectorException.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)TemporaryTopic.java 1.11 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/TemporaryTopic.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)XATopicSession.java 1.12 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/XATopicSession.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)JMSSecurityException.java 1.8 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/JMSSecurityException.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)Session.java 1.44 02/04/10
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/Session.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)JMSException.java 1.15 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/JMSException.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)TopicSubscriber.java 1.28 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/TopicSubscriber.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)MessageNotReadableException.java 1.7 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/MessageNotReadableException.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)TopicRequestor.java 1.20 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/TopicRequestor.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)QueueBrowser.java 1.20 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/QueueBrowser.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)QueueSession.java 1.26 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/QueueSession.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)TopicSession.java 1.40 02/04/10
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/TopicSession.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)QueueSender.java 1.29 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/QueueSender.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)XASession.java 1.18 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/XASession.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)TransactionInProgressException.java 1.8 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/TransactionInProgressException.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)XAConnection.java 1.8 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/XAConnection.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)XATopicConnectionFactory.java 1.14 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/XATopicConnectionFactory.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)QueueRequestor.java 1.21 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/QueueRequestor.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)MessageNotWriteableException.java 1.7 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/MessageNotWriteableException.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)XAQueueConnectionFactory.java 1.14 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/XAQueueConnectionFactory.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)BytesMessage.java 1.31 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/BytesMessage.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)MessageFormatException.java 1.7 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/MessageFormatException.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)ConnectionConsumer.java 1.16 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/ConnectionConsumer.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)TopicConnection.java 1.19 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/TopicConnection.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)TransactionRolledBackException.java 1.7 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/TransactionRolledBackException.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)ResourceAllocationException.java 1.6 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/ResourceAllocationException.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)XATopicConnection.java 1.17 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/XATopicConnection.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)XAQueueConnection.java 1.17 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/XAQueueConnection.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)ConnectionMetaData.java 1.11 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/ConnectionMetaData.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)MessageEOFException.java 1.8 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/MessageEOFException.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)MessageListener.java 1.14 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/MessageListener.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)TopicConnectionFactory.java 1.15 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/TopicConnectionFactory.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)Message.java 1.60 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/Message.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)XAConnectionFactory.java 1.10 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/XAConnectionFactory.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)QueueConnectionFactory.java 1.14 02/04/23
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/QueueConnectionFactory.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)MessageConsumer.java 1.19 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.

*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/MessageConsumer.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)IllegalStateException.java 1.7 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/IllegalStateException.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)TextMessage.java 1.17 02/04/09
*
* Copyright 1997-2002 Sun Microsystems, Inc. All Rights Reserved.
*
* SUN PROPRIETARY/CONFIDENTIAL.
* This software is the proprietary information of Sun Microsystems, Inc.
* Use is subject to license terms.
*
*/

Found in path(s):
* /com-springsource-javax-jms-sources-1-1-0-jar-zip/com-springsource-javax-jms-sources-1-1-0-jar/javax/jms/TextMessage.java

1.462 yang-model-api 0.8.4-Beryllium-SR4

1.462.1 Available under license :

Found license 'Eclipse Public License 1.0' in 'Copyright (c) 2013 Cisco Systems, Inc. and others. All rights reserved. This program and the accompanying materials are made available under the terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2014 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public

License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2013 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2015 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'

1.463 spring-security-acl 3.2.4.RELEASE

1.463.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/domain/SpringCacheBasedAclCache.java
No license file was found, but licenses were detected in source scan.

```
/* Copyright 2004, 2005, 2006 Acegi Technology Pty Limited
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
```

*/

Found in path(s):
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/model/Acl.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/domain/PrincipalSid.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/domain/BasePermission.java
*
/spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/afterinvocation/AclEntryAfterInvocationProvider.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/model/AclCache.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/model/AuditableAcl.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/model/MutableAcl.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/domain/ObjectIdentityRetrievalStrategyImpl.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/model/AuditableAccessControlEntry.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/afterinvocation/AbstractAclProvider.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/domain/CumulativePermission.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/domain/EhCacheBasedAclCache.java
*
/spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/model/OwnershipAcl.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/domain/IdentityUnavailableException.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/model/Permission.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/model/AclService.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/domain/ObjectIdentityImpl.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/model/AlreadyExistsException.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/domain/GrantedAuthoritySid.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/model/MutableAclService.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/afterinvocation/Filterer.java
*
/spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/jdbc/LookupStrategy.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/model/AccessControlEntry.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/domain/AclAuthorizationStrategyImpl.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/model/Sid.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/domain/SidRetrievalStrategyImpl.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/domain/ConsoleAuditLogger.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/afterinvocation/AclEntryAfterInvocationCollectionFilteringProvider.java
* /spring-security-acl-3-2-4-release-sources-

jar/org/springframework/security/acls/domain/AclAuthorizationStrategy.java
*
/spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/domain/AclImpl.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/afterinvocation/CollectionFilterer.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/model/ObjectIdentity.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/jdbc/BasicLookupStrategy.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/jdbc/JdbcMutableAclService.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/AclEntryVoter.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/afterinvocation/ArrayFilterer.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/model/NotFoundException.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/model/UnloadedSidException.java
*
/spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/domain/AclFormattingUtils.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/model/ObjectIdentityRetrievalStrategy.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/model/SidRetrievalStrategy.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/model/ChildrenExistException.java
* /spring-security-acl-3-2-4-release-sources-
jar/org/springframework/security/acls/domain/AccessControlEntryImpl.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/jdbc/JdbcAclService.java
* /spring-security-acl-3-2-4-release-sources-jar/org/springframework/security/acls/domain/AuditLogger.java

1.464 springsourcehibernatevalidator 4.1.0.GA

1.464.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2010, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.

*/

Found in path(s):
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/NotEmptyDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/AssertFalseDef.java
*
 /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/LengthDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/MinDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/FutureDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/MaxDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/ConstraintDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/SizeDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/privilegedactions/ConstructorInstance.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/DigitsDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/CreditCardNumberDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/NullDef.java
*
 /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/NotNullDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/PatternDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/ScriptAssertDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/RangeDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/DecimalMinDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/PastDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/CascadeDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/ConstraintMapping.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/DecimalMaxDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/NotBlankDef.java
*
 /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/ConstraintsForType.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/AssertTrueDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/ConstraintDefWrapper.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/GenericConstraintDef.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/EmailDef.java
No license file was found, but licenses were detected in source scan.

/*
* $Id: NotBlankValidator.java 19090 2010-03-23 15:22:59Z hardy.ferentschik $
*
* JBoss, Home of Professional Open Source
* Copyright 2010, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/NotBlankValidator.java
No license file was found, but licenses were detected in source scan.

/*
* $Id: ConstraintTree.java 19781 2010-06-22 16:30:24Z hardy.ferentschik $
*
* JBoss, Home of Professional Open Source
* Copyright 2010, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/ConstraintTree.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2010, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.

*/

Found in path(s):
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/MaxValidatorForNumber.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/ConfigurationImpl.java
*
 /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/ScriptAssert.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/annotationfactory/AnnotationProxy.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/annotationfactory/AnnotationDescriptor.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/ScriptAssertValidator.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2010, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/scriptassert/ScriptEvaluator.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/resourceloading/AggregateResourceBundleLocator.java
*
 /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/resourceloading/CachingResourceBundleLocator.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/scriptassert/ScriptEvaluatorFactory.java
No license file was found, but licenses were detected in source scan.

/*
* $Id: IteratorEnumeration.java 19090 2010-03-23 15:22:59Z hardy.ferentschik $
*
* JBoss, Home of Professional Open Source
* Copyright 2010, Red Hat, Inc. and/or its affiliates, and individual contributors

* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/IteratorEnumeration.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2009, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /hibernate-validator-4-1-0-final-sources-
zip/org/hibernate/validator/constraints/impl/SizeValidatorForCollection.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/privilegedactions/GetDeclaredField.java
*
/hibernate-validator-4-1-0-final-sources-
zip/org/hibernate/validator/constraints/impl/DecimalMaxValidatorForNumber.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/NotEmpty.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/groups/GroupChain.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/LuhnValidator.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/SizeValidatorForString.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/xml/ValidationBootstrapParameters.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/PathImpl.java

* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/metadata/PropertyDescriptorImpl.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/IdentitySet.java
*
/hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/privilegedactions/GetClassLoader.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/metadata/AnnotationIgnores.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/MessageAndPath.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/MaxValidatorForString.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/xml/ValidationXmlParser.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/Length.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/groups/GroupChainGenerator.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/privilegedactions/GetMethods.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/LazyValidatorFactory.java
*
/hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/metadata/BeanMetaDataCache.java
* /hibernate-validator-4-1-0-final-sources-
zip/org/hibernate/validator/engine/resolver/SingleThreadCachedTraversableResolver.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/metadata/ElementDescriptorImpl.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/privilegedactions/GetDeclaredFields.java
* /hibernate-validator-4-1-0-final-sources-
zip/org/hibernate/validator/constraints/impl/DecimalMaxValidatorForString.java
* /hibernate-validator-4-1-0-final-sources-
zip/org/hibernate/validator/constraints/impl/SizeValidatorForArraysOfInt.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/MessageInterpolatorContext.java
* /hibernate-validator-4-1-0-final-sources-
zip/org/hibernate/validator/constraints/impl/SizeValidatorForArraysOfBoolean.java
* /hibernate-validator-4-1-0-final-sources-
zip/org/hibernate/validator/constraints/impl/DecimalMinValidatorForNumber.java
*
/hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/privilegedactions/LoadClass.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/FutureValidatorForDate.java
* /hibernate-validator-4-1-0-final-sources-
zip/org/hibernate/validator/constraints/impl/PastValidatorForCalendar.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/HibernateValidator.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/ConstraintViolationImpl.java
* /hibernate-validator-4-1-0-final-sources-
zip/org/hibernate/validator/constraints/impl/SizeValidatorForArraysOfByte.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/ValidatorTypeHelper.java
* /hibernate-validator-4-1-0-final-sources-
zip/org/hibernate/validator/constraints/impl/SizeValidatorForArraysOfLong.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/xml/XmlMappingParser.java
*
/hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/ValueContext.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/privilegedactions/GetConstructor.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/NodeImpl.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/metadata/BeanDescriptorImpl.java
* /hibernate-validator-4-1-0-final-sources-
zip/org/hibernate/validator/constraints/impl/SizeValidatorForArraysOfFloat.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/ConstraintValidatorFactoryImpl.java

* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/privilegedactions/GetAnnotationParameter.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/MinValidatorForString.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/DigitsValidatorForString.java
*
/hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/DecimalMinValidatorForString.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/AssertTrueValidator.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/SizeValidatorForMap.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/DigitsValidatorForNumber.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/SizeValidatorForArraysOfChar.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/metadata/BeanMetaData.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/privilegedactions/GetDeclaredMethods.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/resolver/DefaultTraversableResolver.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/privilegedactions/GetMethodFromPropertyName.java
*
/hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/ConstraintValidatorContextImpl.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/ValidatorContextImpl.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/annotationfactory/AnnotationFactory.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/SizeValidatorForArraysOfDouble.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/metadata/ConstraintDescriptorImpl.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/privilegedactions/NewInstance.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/Range.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/metadata/ConstraintOrigin.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/privilegedactions/SetAccessibility.java
*
/hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/messageinterpolation/ResourceBundleMessageInterpolator.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/SizeValidatorForArraysOfShort.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/MinValidatorForNumber.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/FutureValidatorForCalendar.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/AssertFalseValidator.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/SizeValidatorForArraysOfPrimitives.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/Email.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/metadata/ConstraintHelper.java
*
/hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/privilegedactions/GetMethod.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/resolver/JPATraversableResolver.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/SizeValidatorForArray.java

* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/groups/Group.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/HibernateValidatorConfiguration.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/LengthValidator.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/NullValidator.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/PastValidatorForDate.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/ValidatorFactoryImpl.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/CreditCardNumber.java
*
/hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/NotNullValidator.java
No license file was found, but licenses were detected in source scan.

/*
* $Id: NotBlank.java 19327 2010-04-30 08:11:15Z hardy.ferentschik $
*
* JBoss, Home of Professional Open Source
* Copyright 2010, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/NotBlank.java
No license file was found, but licenses were detected in source scan.

24 10:31:09Z hardy.ferentschik $
~
~ JBoss, Home of Professional Open Source
~ Copyright 2010, Red Hat, Inc. and/or its affiliates, and individual contributors
~ by the @authors tag. See the copyright.txt in the distribution for a
~ full listing of individual contributors.
~
~ Licensed under the Apache License, Version 2.0 (the "License");
~ you may not use this file except in compliance with the License.
~ You may obtain a copy of the License at
~ http://www.apache.org/licenses/LICENSE
2.0
~ Unless required by applicable law or agreed to in writing, software
~ distributed under the License is distributed on an "AS IS" BASIS,

~ WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
~ See the License for the specific language governing permissions and
~ limitations under the License.

Found in path(s):
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/xml/package.html
*
/hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/resolver/package.html
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/package.html
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/groups/package.html
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/annotationfactory/package.html
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/privilegedactions/package.html
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/package.html
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/scriptassert/package.html
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/package.html
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/package.html
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/messageinterpolation/package.html
*
/hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/package.html
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/metadata/package.html
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/resourceloading/package.html
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2008, Red Hat Middleware LLC, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/URLValidator.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/URL.java
No license file was found, but licenses were detected in source scan.

25 18:21:27Z hardy.ferentschik $
~
~ JBoss, Home of Professional Open Source

~ Copyright 2010, Red Hat, Inc. and/or its affiliates, and individual contributors
~ by the @authors tag. See the copyright.txt in the distribution for a
~ full listing of individual contributors.
~
~ Licensed under the Apache License, Version 2.0 (the "License");
~ you may not use this file except in compliance with the License.
~ You may obtain a copy of the License at
~ http://www.apache.org/licenses/LICENSE
2.0
~ Unless required by applicable law or agreed to in writing, software
~ distributed under the License is distributed on an "AS IS" BASIS,
~ WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
~ See the License for the specific language governing permissions and
~ limitations under the License.

Found in path(s):
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/package.html
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2009, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/metadata/MetaConstraint.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/constraints/impl/PatternValidator.java
*
/hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/ValidationContext.java
* /hibernate-validator-4-1-0-final-sources-
zip/org/hibernate/validator/resourceloading/PlatformResourceBundleLocator.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/Version.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/metadata/BeanMetaDataImpl.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/LoggerFactory.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/util/ReflectionHelper.java
* /hibernate-validator-4-1-0-final-sources-

zip/org/hibernate/validator/resourceloading/DelegatingResourceBundleLocator.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/resourceloading/ResourceBundleLocator.java
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/engine/ValidatorImpl.java
No license file was found, but licenses were detected in source scan.

~ JBoss, Home of Professional Open Source
~ Copyright 2010, Red Hat, Inc. and/or its affiliates, and individual contributors
~ by the @authors tag. See the copyright.txt in the distribution for a
~ full listing of individual contributors.
~
~ Licensed under the Apache License, Version 2.0 (the "License");
~ you may not use this file except in compliance with the License.
~ You may obtain a copy of the License at
~ http://www.apache.org/licenses/LICENSE
2.0
~ Unless required by applicable law or agreed to in writing, software
~ distributed under the License is distributed on an "AS IS" BASIS,
~ WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
~ See the License for the specific language governing permissions and
~ limitations under the License.

Found in path(s):
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/package.html
No license file was found, but licenses were detected in source scan.

/* JBoss, Home of Professional Open Source
* Copyright 2010, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /hibernate-validator-4-1-0-final-sources-zip/org/hibernate/validator/cfg/defs/URLDef.java

1.465 yang-model-util 0.8.4-Beryllium-SR4

1.465.1 Available under license :

Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2015 Pantheon Technologies s.r.o. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in 'Copyright (c) 2013 Cisco Systems, Inc. and others. All rights reserved. This program and the accompanying materials are made available under the terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2014 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2013 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2015 Cisco Systems, Inc. and others. All rights reserved. * This program and the accompanying materials are made available under the * terms of the Eclipse Public License v1.0 which accompanies this distribution,'

1.466 jakarta-json-api 1.1.5

1.466.1 Available under license :

Eclipse Public License - v 2.0

THE ACCOMPANYING PROGRAM IS PROVIDED UNDER THE TERMS OF THIS ECLIPSE PUBLIC LICENSE ("AGREEMENT"). ANY USE, REPRODUCTION OR DISTRIBUTION OF THE PROGRAM CONSTITUTES RECIPIENT'S ACCEPTANCE OF THIS AGREEMENT.

1. DEFINITIONS

"Contribution" means:

a) in the case of the initial Contributor, the initial content
Distributed under this Agreement, and

b) in the case of each subsequent Contributor:
i) changes to the Program, and
ii) additions to the Program;
where such changes and/or additions to the Program originate from and are Distributed by that particular Contributor. A Contribution "originates" from a Contributor if it was added to the Program by such Contributor itself or anyone acting on such Contributor's behalf. Contributions do not include changes or additions to the Program that are not Modified Works.

"Contributor" means any person or entity that Distributes the Program.

"Licensed Patents" mean patent claims licensable by a Contributor which

are necessarily infringed by the use or sale of its Contribution alone or when combined with the Program.

"Program" means the Contributions Distributed in accordance with this Agreement.

"Recipient" means anyone who receives the Program under this Agreement or any Secondary License (as applicable), including Contributors.

"Derivative Works" shall mean any work, whether in Source Code or other form, that is based on (or derived from) the Program and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship.

"Modified Works" shall mean any work in Source Code or other form that results from an addition to, deletion from, or modification of the contents of the Program, including, for purposes of clarity any new file in Source Code form that
contains any contents of the Program. Modified
Works shall not include works that contain only declarations, interfaces, types, classes, structures, or files of the Program solely in each case in order to link to, bind by name, or subclass the Program or Modified Works thereof.

"Distribute" means the acts of a) distributing or b) making available in any manner that enables the transfer of a copy.

"Source Code" means the form of a Program preferred for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Secondary License" means either the GNU General Public License, Version 2.0, or any later versions of that license, including any exceptions or additional permissions as identified by the initial Contributor.

2. GRANT OF RIGHTS

a) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free
copyright
license to reproduce, prepare Derivative Works of, publicly display, publicly perform, Distribute and sublicense the Contribution of such Contributor, if any, and such Derivative Works.

b) Subject to the terms of this Agreement, each Contributor hereby grants Recipient a non-exclusive, worldwide, royalty-free patent license under Licensed Patents to make, use, sell, offer to sell,

import and otherwise transfer the Contribution of such Contributor, if any, in Source Code or other form. This patent license shall apply to the combination of the Contribution and the Program if, at the time the Contribution is added by the Contributor, such addition of the Contribution causes such combination to be covered by the Licensed Patents. The patent license shall not apply to any other combinations which include the Contribution. No hardware per se is licensed hereunder.

c) Recipient understands
that although each Contributor grants the
licenses to its Contributions set forth herein, no assurances are provided by any Contributor that the Program does not infringe the patent or other intellectual property rights of any other entity. Each Contributor disclaims any liability to Recipient for claims brought by any other entity based on infringement of intellectual property rights or otherwise. As a condition to exercising the rights and licenses granted hereunder, each Recipient hereby assumes sole responsibility to secure any other intellectual property rights needed, if any. For example, if a third party patent license is required to allow Recipient to Distribute the Program, it is Recipient's responsibility to acquire that license before distributing the Program.

d) Each Contributor represents that to its knowledge it has sufficient copyright rights in its Contribution, if any, to grant

the copyright license set forth in this Agreement.

e) Notwithstanding the terms of any Secondary License, no Contributor makes additional grants to any Recipient (other than those set forth in this Agreement) as a result of such Recipient's receipt of the Program under the terms of a Secondary License (if permitted under the terms of Section 3).

3. REQUIREMENTS

3.1 If a Contributor Distributes the Program in any form, then:

a) the Program must also be made available as Source Code, in accordance with section 3.2, and the Contributor must accompany the Program with a statement that the Source Code for the Program is available under this Agreement, and informs Recipients how to obtain it in a reasonable manner on or through a medium customarily used for software exchange; and

b) the Contributor may Distribute the Program under a license different than this Agreement, provided that such license:

i) effectively disclaims on behalf of all other Contributors all warranties and conditions, express and implied, including warranties or conditions of title and non-infringement, and implied warranties or conditions of merchantability and fitness for a particular purpose;

ii) effectively excludes on behalf of all other Contributors all liability for damages, including direct, indirect, special, incidental and consequential damages, such as lost profits;

iii) does not attempt to limit or alter the recipients' rights in the Source Code under section 3.2; and

iv) requires any subsequent distribution of the Program by any party to be under a license that satisfies the requirements of this section 3.

3.2 When the Program is Distributed as Source Code:

a) it must be made available under this Agreement, or if the Program (i) is combined with other material in a separate file or files made available under a Secondary License, and (ii) the initial Contributor attached to the Source Code the notice described in Exhibit A of this Agreement, then the Program may be made available under the terms of such Secondary Licenses, and

b) a copy of this Agreement must be included with each copy of the Program.

3.3 Contributors may not remove or alter any copyright, patent, trademark, attribution notices, disclaimers of warranty, or limitations of liability ("notices") contained within the Program from any copy of the Program which they Distribute, provided that Contributors may add their own appropriate notices.

4. COMMERCIAL DISTRIBUTION

Commercial distributors of software may accept certain responsibilities with respect to end users, business partners and the like. While this license is intended to facilitate the commercial use of the Program, the Contributor who includes the Program in a commercial product offering should do so in a manner which does not create potential liability for other Contributors. Therefore, if a Contributor includes the Program in a commercial product offering, such Contributor ("Commercial Contributor") hereby agrees to defend and indemnify every other Contributor ("Indemnified Contributor") against any losses,

damages and costs (collectively "Losses") arising from claims, lawsuits and other legal actions brought by a third party against the Indemnified Contributor to the extent caused by the acts or omissions of such Commercial Contributor in connection with its distribution of the Program in a commercial product offering. The obligations in this section do not apply to any claims or Losses relating to any actual or alleged intellectual property infringement. In order to qualify, an Indemnified Contributor must: a) promptly notify the Commercial Contributor in writing
of such claim, and b) allow the Commercial Contributor to control, and cooperate with the Commercial Contributor in, the defense and any related settlement negotiations. The Indemnified Contributor may participate in any such claim at its own expense.

For example, a Contributor might include the Program in a commercial product offering, Product X. That Contributor is then a Commercial Contributor. If that Commercial Contributor then makes performance claims, or offers warranties related to Product X, those performance claims and warranties are such Commercial Contributor's responsibility alone. Under this section, the Commercial Contributor would have to defend claims against the other Contributors related to those performance claims and warranties, and if a court requires any other Contributor to pay any damages as a result, the Commercial Contributor must pay those damages.

5. NO WARRANTY

EXCEPT AS EXPRESSLY SET FORTH IN
THIS AGREEMENT, AND TO THE EXTENT
PERMITTED BY APPLICABLE LAW, THE PROGRAM IS PROVIDED ON AN "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, EITHER EXPRESS OR IMPLIED INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OR CONDITIONS OF TITLE, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Each Recipient is solely responsible for determining the appropriateness of using and distributing the Program and assumes all risks associated with its exercise of rights under this Agreement, including but not limited to the risks and costs of program errors, compliance with applicable laws, damage to or loss of data, programs or equipment, and unavailability or interruption of operations.

6. DISCLAIMER OF LIABILITY

EXCEPT AS EXPRESSLY SET FORTH IN THIS AGREEMENT, AND TO THE EXTENT PERMITTED BY APPLICABLE LAW, NEITHER RECIPIENT NOR ANY CONTRIBUTORS SHALL HAVE ANY LIABILITY FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION LOST PROFITS), HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN

CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OR DISTRIBUTION OF THE PROGRAM OR THE EXERCISE OF ANY RIGHTS GRANTED HEREUNDER, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. GENERAL

If any provision of this Agreement is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this Agreement, and without further action by the parties hereto, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

If Recipient institutes patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Program itself (excluding combinations of the Program with other software or hardware) infringes such Recipient's patent(s), then such Recipient's rights granted under Section 2(b) shall terminate as of the date such litigation is filed.

All Recipient's rights under this Agreement shall terminate if it fails to comply with any of the material terms or conditions of this Agreement and does not cure such failure in a reasonable period of time after becoming aware of such noncompliance. If all Recipient's rights under this Agreement terminate, Recipient agrees to cease use and distribution of the Program as soon as reasonably practicable. However, Recipient's obligations under this Agreement and any licenses granted by Recipient relating to the Program shall continue and survive.

Everyone is permitted to copy and distribute copies of this Agreement, but in order to avoid inconsistency the Agreement is copyrighted and may only be modified in the following manner. The Agreement Steward reserves the right to publish new versions (including revisions) of this Agreement from time to time. No one other than the Agreement Steward has the right to modify this Agreement. The Eclipse Foundation is the initial Agreement Steward. The Eclipse Foundation may assign the responsibility to serve as the Agreement Steward to a suitable separate entity. Each new version of the Agreement will be given a distinguishing version number. The Program (including Contributions) may always be Distributed subject to the version of the Agreement under which it was received. In addition, after a new version of the Agreement is published, Contributor may elect to Distribute the Program (including its Contributions) under the new version.

Except as expressly stated in Sections 2(a) and 2(b) above, Recipient receives no rights or licenses to the intellectual property of any

Contributor under this Agreement, whether expressly, by implication, estoppel
or otherwise. All rights in the Program not expressly granted under this Agreement are reserved. Nothing in this Agreement is intended to be enforceable by any entity that is not a Contributor or Recipient. No third-party beneficiary rights are created under this Agreement.

Exhibit A - Form of Secondary Licenses Notice

"This Source Code may also be made available under the following Secondary Licenses when the conditions for such availability set forth in the Eclipse Public License, v. 2.0 are satisfied: {name license(s), version(s), and exceptions or additional permissions here}."

Simply including a copy of this Agreement, including this Exhibit A is not sufficient to license the Source Code under Secondary Licenses.

If it is not possible or desirable to put the notice in a particular file, then You may include the notice in a location (such as a LICENSE file in a relevant directory) where a recipient would be likely to
look for such a notice.

You may add additional accurate notices of copyright ownership.

The GNU General Public License (GPL) Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor
Boston, MA 02110-1335
USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.)

You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you
must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed
at all.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is

to say, a work containing the Program or a portion of it, either
verbatim or with modifications and/or translated into another language.
(Hereinafter, translation is included without limitation in the term
"modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this License; they are outside its scope. The act of running
the Program is not restricted,
and the output from the Program is
covered only if its contents constitute a work based on the Program
(independent of having been made by running the Program). Whether that
is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source
code as you receive it, in any medium, provided that you conspicuously
and appropriately publish on each copy an appropriate copyright notice
and disclaimer of warranty; keep intact all the notices that refer to
this License and to the absence of any warranty; and give any other
recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of
it, thus forming a work based on the Program, and copy and distribute
such modifications
or work under the terms of Section 1 above, provided
that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices
stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in
whole or in part contains or is derived from the Program or any part
thereof, to be licensed as a whole at no charge to all third parties
under the terms of this License.

c) If the modified program normally reads commands interactively
when run, you must cause it, when started running for such
interactive use in the most ordinary way, to print or display an
announcement including an appropriate copyright notice and a notice
that there is no warranty (or else, saying that you provide a
warranty) and that users may redistribute the program under these
conditions, and telling the user how
to view a copy of this License.
(Exception: if the Program itself is interactive but does not
normally print such an announcement, your work based on the Program
is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you;
rather, the intent is to
exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost

of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control

compilation and installation of the executable. However, as a special exception, the source code distributed
need not include anything that is
normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have
their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible
for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would

not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular
circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted
in
certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free

programs whose distribution conditions are different, write to the
author to ask for permission. For software which is copyrighted by the
Free Software Foundation, write to the Free Software Foundation; we
sometimes make exceptions for this. Our decision will be guided by the
two goals of preserving the free status of all derivatives of our free
software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO
WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW.
EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR
OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND,
EITHER
EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE
ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH
YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL
NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN
WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY
AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR
DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL
DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM
(INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED
INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF
THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR
OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF
TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest
possible use to the public, the best way to achieve this is to make it
free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to
attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the
"copyright" line and a pointer to where the full notice is found.

One line to give the program's name and a brief idea of what it does.
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify

it under the terms of the GNU General Public License as published by
the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful, but
WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1335 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this
when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type
`show w'. This is free software, and you are welcome to redistribute
it under certain conditions; type `show c' for details.

The hypothetical commands `show
w' and `show c' should show the
appropriate parts of the General Public License. Of course, the commands
you use may be called something other than `show w' and `show c'; they
could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the program, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
program `Gnomovision' (which makes passes at compilers) written by
James Hacker.

signature of Ty Coon, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you
may consider it more useful to permit linking proprietary applications
with the library. If this is what you want to do, use the GNU
Library
General Public License instead of this License.

CLASSPATH EXCEPTION

Linking this library statically or dynamically with other modules is
making a combined work based on this library. Thus, the terms and
conditions of the GNU General Public License version 2 cover the whole
combination.

As a special exception, the copyright holders of this library give you
permission to link this library with independent modules to produce an
executable, regardless of the license terms of these independent
modules, and to copy and distribute the resulting executable under
terms of your choice, provided that you also meet, for each linked
independent module, the terms and conditions of the license of that
module. An independent module is a module which is not derived from or
based on this library. If you modify this library, you may extend this
exception to your version of the library, but you are not obligated to
do so. If
you do not wish to do so, delete this exception statement
from your version.

Notices for Eclipse Project for JSON Processing

This content is produced and maintained by the Eclipse Project for JSON Processing project.

* Project home: https://projects.eclipse.org/projects/ee4j.jsonp

Trademarks

Eclipse Project for JSON Processing is a trademark of the Eclipse Foundation.

Copyright

All content is the property of the respective authors or their employers. For more information regarding authorship of content, please consult the listed source code repository logs.

Declared Project Licenses

This program and the accompanying materials are made available under the terms of the Eclipse Public License v. 2.0 which is available at http://www.eclipse.org/legal/epl-2.0. This Source Code may also be made available under the following Secondary Licenses when the conditions for such availability set forth in the Eclipse Public License v. 2.0 are satisfied: GNU General Public License, version 2 with the GNU Classpath Exception which is available at https://www.gnu.org/software/classpath/license.html.

SPDX-License-Identifier:
EPL-2.0 OR GPL-2.0 WITH Classpath-exception-2.0

Source Code

The project maintains the following source code repositories:

* https://github.com/eclipse-ee4j/jsonp

Third-party Content

JUnit (4.12)

* License: Eclipse Public License

Cryptography

Content may contain encryption software. The country in which you are currently may have restrictions on the import, possession, and use, and/or re-export to another country, of encryption software. BEFORE using any encryption software, please check the country's laws, regulations and policies concerning the import, possession, or use, and re-export of encryption software, to see if this is permitted.

1.467 bean-validation-api 1.1.0.Final

1.467.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2009, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):

* /validation-api-1-1-0-final-sources-5-jar/javax/validation/GroupSequence.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2011-2013, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/metadata/ParameterDescriptor.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2012-2013, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/metadata/ExecutableDescriptor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012-2013, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a

* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/BootstrapConfiguration.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2012, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/groups/ConvertGroup.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2011, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/metadata/MethodDescriptor.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2012, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/ParameterNameProvider.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/metadata/ConstructorDescriptor.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2009-2012, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.

*/

Found in path(s):
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/ConstraintViolationException.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/spi/ConfigurationState.java
*
/validation-api-1-1-0-final-sources-5-jar/javax/validation/ConstraintValidatorFactory.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/ValidatorContext.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/ValidatorFactory.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2013, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/metadata/CrossParameterDescriptor.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/metadata/package-info.java
*
/validation-api-1-1-0-final-sources-5-jar/javax/validation/constraintvalidation/SupportedValidationTarget.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraintvalidation/ValidationTarget.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/executable/package-info.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraintvalidation/package-info.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/bootstrap/package-info.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraints/package-info.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/metadata/CascadableDescriptor.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/metadata/GroupConversionDescriptor.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/package-info.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/ConstraintTarget.java
*
/validation-api-1-1-0-final-sources-5-jar/javax/validation/spi/package-info.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2009-2012, Red Hat, Inc. and/or its affiliates, and individual contributors

* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/Configuration.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2009, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/Valid.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraints/Past.java
*
 /validation-api-1-1-0-final-sources-5-jar/javax/validation/bootstrap/GenericBootstrap.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/bootstrap/ProviderSpecificBootstrap.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/Payload.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/ConstraintValidator.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/metadata/ConstraintDescriptor.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraints/Null.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraints/Min.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraints/Pattern.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/spi/ValidationProvider.java

* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraints/AssertFalse.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/metadata/ElementDescriptor.java
*
 /validation-api-1-1-0-final-sources-5-jar/javax/validation/Constraint.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/ConstraintDefinitionException.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraints/Future.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraints/Digits.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/metadata/Scope.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/UnexpectedTypeException.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraints/NotNull.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraints/AssertTrue.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/ValidationProviderResolver.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/GroupDefinitionException.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/ConstraintDeclarationException.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraints/Max.java
*
 /validation-api-1-1-0-final-sources-5-jar/javax/validation/OverridesAttribute.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/ValidationException.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/groups/Default.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/spi/BootstrapState.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/Validation.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/metadata/PropertyDescriptor.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/TraversableResolver.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraints/Size.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2009-2013, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/ConstraintViolation.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraints/DecimalMax.java
*

/validation-api-1-1-0-final-sources-5-jar/javax/validation/groups/package-info.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/ConstraintValidatorContext.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/Path.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/Validator.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/ReportAsSingleViolation.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/MessageInterpolator.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/metadata/BeanDescriptor.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/constraints/DecimalMin.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2013, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/metadata/MethodType.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2012-2013, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/ElementKind.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/executable/ExecutableType.java
*
/validation-api-1-1-0-final-sources-5-jar/javax/validation/executable/ExecutableValidator.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/metadata/ReturnValueDescriptor.java
* /validation-api-1-1-0-final-sources-5-jar/javax/validation/executable/ValidateOnExecution.java

1.468 jta 1.1

1.468.1 Available under license :

Found license 'Common Development and Distribution License (CDDL) 1.1' in '* The contents of this file are subject to the terms * of the Common Development and Distribution License * (the License). You may not use this file except in * Copyright 2006 Sun Microsystems, Inc. All rights reserved.'

1.469 jms 1.1

1.469.1 Available under license :

// --
// NOTICE file corresponding to the section 4d of The Apache License,

// Version 2.0, in this case for JMS 1.1
// --

JMS 1.1
Copyright 2003-2006 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).
Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,

"control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the

editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity

on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the

attribution notices contained
within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as
required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,

whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License,
Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and

limitations under the License.

1.470 aspectj-tools 1.9.6

1.470.1 Available under license :

Found license 'Eclipse Public License 1.0' in '* This program and the accompanying materials * are made available under the terms of the Eclipse Public License 2.0 " * All Rights Reserved.\n" + //$NON-NLS-1$'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2005 Contributors. All rights reserved. * This program and the accompanying materials are made available * under the terms of the Eclipse Public License v1.0'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2006 Contributors.All rights reserved. * This program and the accompanying materials are made available * under the terms of the Eclipse Public License v1.0'
Found license 'Eclipse Public License 1.0' in '* This program and the accompanying materials * are made available under the terms of the Eclipse Public License 2.0'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2006 Contributors. All rights reserved. * This program and the accompanying materials are made available * under the terms of the Eclipse Public License v1.0'
Found license 'Common Public License 1.0 (CPLv1.0)' in '* and others. All rights reserved. * This program and the accompanying materials are made available under * the terms of the Common Public License v1.0 which accompanies this'
Found license 'Eclipse Public License 1.0' in '# This program and the accompanying materials # are made available under the terms of the Eclipse Public License 2.0'
Found license 'Common Public License 1.0 (CPLv1.0)' in '* All rights reserved. * This program and the accompanying materials are made available * under the terms of the Common Public License v1.0'
Found license 'Common Public License 1.0 (CPLv1.0)' in '* All rights reserved. This program and the accompanying materials * are made available under the terms of the Common Public License v1.0'
Found license 'Eclipse Public License 1.0' in '* All rights reserved. * This program and the accompanying materials are made available * under the terms of the Eclipse Public License v1.0 "This software is distributed under the Eclipse Public License\n" +'
Found license 'Eclipse Public License 1.0' in '# This program and the accompanying materials # are made available under the terms of the Eclipse Public License 2.0 compiler.copyright = Copyright IBM Corp 2000, 2020. All rights reserved.'
Found license 'Eclipse Public License 1.0' in '// * All rights reserved. // * This program and the accompanying materials are made available // * under the terms of the Eclipse Public License v1.0'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2006, 2010 Contributors. All rights reserved. * This program and the accompanying materials are made available * under the terms of the Eclipse Public License v1.0'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2010 Contributors. All rights reserved. * This program and the accompanying materials are made available * under the terms of the Eclipse Public License v1.0'
Found license 'Eclipse Public License 1.0' in '* This program and the accompanying materials * are made available under the terms of the Eclipse Public License 2.0'
Found license 'Eclipse Public License 1.0' in '* This program and the accompanying materials * are made available under the terms of the Eclipse Public License 2.0 in all these cases the incoming type binding is for Z, but annotations are for different levels. We need to align their layout for proper attribution.'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2008 Contributors. All rights reserved. * This program and the accompanying materials are made available * under the terms of the Eclipse Public License v1.0'
Found license 'Eclipse Public License 1.0' in '* This program and the accompanying materials * are made available under the terms of the Eclipse Public License 2.0 Binary vs source, substitutions, annotation re-attribution from SE7 locations etc trigger these'

Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2007 Contributors. All rights reserved. * This program and the accompanying materials are made available * under the terms of the Eclipse Public License v1.0'
Found license 'Eclipse Public License 1.0' in '* This program and the accompanying materials * are made available under the terms of the Eclipse Public License 2.0 * more details.'
Found license 'Eclipse Public License 1.0' in '* All rights reserved. * This program and the accompanying materials are made available * under the terms of the Eclipse Public License v1.0'
Found license 'Eclipse Public License 1.0' in '* All rights reserved. This program and the accompanying materials * are made available under the terms of the Eclipse Public License v1.0'
Found license 'Eclipse Public License 1.0' in '* This program and the accompanying materials * are made available under the terms of the Eclipse Public License 2.0 * lookup3.c, by Bob Jenkins, May 2006, Public Domain. * the public domain. It has no warranty.'
Found license 'Eclipse Public License 1.0' in '* All rights reserved. This program and the accompanying materials * are made available under the terms of the Eclipse Public License v2.0'

1.471 aop-alliance 1.0

1.471.1 Available under license :

Public Domain

1.472 spring-messaging 4.3.30.RELEASE

1.472.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/converter/MessageConversionException.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/converter/SimpleMessageConverter.java
* /spring-messaging-4-3-30-release-sources-

jar/org/springframework/messaging/support/AbstractSubscribableChannel.java
*
/spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/core/CachingDestinationResolverProxy.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/support/ChannelInterceptor.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/support/ErrorMessage.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/MessageHandlingException.java
* /spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/support/ExecutorChannelInterceptor.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/Message.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/SimpAttributes.java
* /spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/simp/SimpMessageMappingInfo.java
* /spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/handler/annotation/support/MessageHandlerMethodFactory.java
*
/spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/support/MessageHeaderInitializer.java
* /spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/handler/invocation/HandlerMethodReturnValueHandlerComposite.java
* /spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/core/AbstractMessagingTemplate.java
* /spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/converter/DefaultContentTypeResolver.java
* /spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/support/ImmutableMessageChannelInterceptor.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/support/HeaderMapper.java
* /spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/core/AbstractDestinationResolvingMessagingTemplate.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/core/DestinationResolver.java
*
/spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/support/MessageBuilder.java
* /spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/core/AbstractMessageReceivingTemplate.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/support/GenericMessage.java
* /spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/handler/annotation/support/HeaderMethodArgumentResolver.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/support/InterceptableChannel.java
* /spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/support/MessageHandlingRunnable.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at

*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/ValueConstants.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/Headers.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/user/UserDestinationResolver.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/user/SimpSession.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/user/DefaultUserSessionRegistry.java
*
 /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/converter/ByteArrayMessageConverter.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/StompFrameHandler.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/HandlerMethodSelector.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/tcp/TcpOperations.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/user/SimpSubscriptionMatcher.java

* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/user/UserSessionRegistry.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/core/MessageReceivingOperations.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/Payload.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/core/MessageRequestReplyOperations.java
*
/spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/MessageHeaders.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/invocation/AbstractAsyncReturnValueHandler.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/SimpMessageSendingOperations.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/converter/StringMessageConverter.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/tcp/TcpConnection.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/tcp/reactor/PassThroughPromiseToListenableFutureAdapter.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/MessagingAdviceBean.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/invocation/ListenableFutureReturnValueHandler.java
*
/spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/Header.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/user/DestinationUserNameProvider.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/AbstractMessageCondition.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/tcp/TcpConnectionHandler.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/support/AnnotationExceptionHandlerMethodResolver.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/annotation/SubscribeMapping.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/StompSessionHandler.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/user/SimpUser.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/converter/MessageConverter.java
*
/spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/StompSessionHandlerAdapter.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/converter/SmartMessageConverter.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/invocation/HandlerMethodArgumentResolver.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/MessageCondition.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/ConnectionHandlingStompSession.java
* /spring-messaging-4-3-30-release-sources-

jar/org/springframework/messaging/simp/SimpMessageTypeMessageCondition.java
* /spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/core/MessageSendingOperations.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/user/SimpSubscription.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*

* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/handler/annotation/MessageExceptionHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.7
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-messaging-4-3-30-release-sources-
jar/org/springframework/messaging/simp/config/ChannelRegistration.java

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/support/MethodArgumentTypeMismatchException.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/support/IdTimestampMessageHeaderInitializer.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/user/UserRegistryMessageHandler.java
*
 /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/core/AbstractMessageSendingTemplate.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/SimpSessionScope.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/support/AbstractMethodArgumentResolutionException.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/HandlerMethod.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/invocation/MethodArgumentResolutionException.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/broker/AbstractSubscriptionRegistry.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/StompBrokerRelayMessageHandler.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/converter/ContentTypeResolver.java
*
 /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/StompHeaderAccessor.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/SimpMessageHeaderAccessor.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/invocation/CompletableFutureReturnValueHandler.java
* /spring-messaging-4-3-30-release-sources-

jar/org/springframework/messaging/simp/config/MessageBrokerRegistry.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/support/MethodArgumentNotValidException.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/invocation/HandlerMethodReturnValueHandler.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/annotation/support/SendToMethodReturnValueHandler.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/StompClientSupport.java
*
/spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/MessageMapping.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/support/ExecutorSubscribableChannel.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/support/MessageHeaderAccessor.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/user/UserDestinationResult.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/MessagingException.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/SimpAttributesContextHolder.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/Reactor2TcpStompClient.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/DestinationPatternsMessageCondition.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/annotation/support/SubscriptionMethodReturnValueHandler.java
*
/spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/invocation/AbstractExceptionHandlerMethodResolver.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/SimpMessagingTemplate.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/tcp/ReconnectStrategy.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
*/

Found in path(s):
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/converter/CompositeMessageConverter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2020 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/converter/AbstractMessageConverter.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/converter/MarshallingMessageConverter.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/support/AbstractNamedValueMethodArgumentResolver.java
*
 /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/config/StompBrokerRelayRegistration.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/StompDecoder.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/converter/MappingJackson2MessageConverter.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/support/AbstractMessageChannel.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/StompEncoder.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/support/NativeMessageHeaderAccessor.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/DefaultStompSession.java
No license file was found, but licenses were detected in source scan.

/*

* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/StompHeaders.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/support/DefaultMessageHandlerMethodFactory.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/support/PayloadArgumentResolver.java
*
 /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/tcp/reactor/Reactor2TcpConnection.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/MessageChannel.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/BufferingStompDecoder.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/Reactor2StompCodec.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/user/SimpUserRegistry.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/user/UserSessionRegistryAdapter.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/core/GenericMessagingTemplate.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/converter/GenericMessageConverter.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/StompCommand.java
*
 /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/ConnectionLostException.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/support/DestinationVariableMethodArgumentResolver.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/support/MessageMethodArgumentResolver.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/tcp/reactor/AbstractPromiseToListenableFutureAdapter.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/SendTo.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/annotation/SendToUser.java

* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/config/AbstractBrokerRegistration.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/core/MessagePostProcessor.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/PollableChannel.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/core/DestinationResolvingMessageRequestReplyOperations.java
*
 /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/StompConversionException.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/SimpMessageType.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/core/DestinationResolutionException.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/broker/BrokerAvailabilityEvent.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/SubscribableChannel.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/core/BeanFactoryMessageChannelDestinationResolver.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/core/DestinationResolvingMessageSendingOperations.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/MessageDeliveryException.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/annotation/support/PrincipalMethodArgumentResolver.java
*
 /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/core/DestinationResolvingMessageReceivingOperations.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/tcp/FixedIntervalReconnectStrategy.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/annotation/support/MissingSessionUserException.java

* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/support/ChannelInterceptorAdapter.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/DestinationVariable.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2019 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/invocation/HandlerMethodArgumentResolverComposite.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/user/MultiServerUserRegistry.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/invocation/AsyncHandlerMethodReturnValueHandler.java
*
 /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/stomp/StompSession.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/config/AbstractMessageBrokerConfiguration.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
```

* limitations under the License.
*/

Found in path(s):
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/broker/SubscriptionRegistry.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/config/SimpleBrokerRegistration.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/support/AbstractHeaderMapper.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/tcp/reactor/Reactor2TcpClient.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/annotation/support/HeadersMethodArgumentResolver.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/broker/AbstractBrokerMessageHandler.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/broker/SimpleBrokerMessageHandler.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/invocation/AbstractMethodMessageHandler.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/broker/DefaultSubscriptionRegistry.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/user/UserDestinationMessageHandler.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/annotation/support/SimpAnnotationMethodMessageHandler.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/MessageHandler.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/user/DefaultUserDestinationResolver.java
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/handler/invocation/InvocableHandlerMethod.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.

```
*/
/**
  * Set the max pool size of the ThreadPoolExecutor.
  * <p><strong>NOTE:</strong> When an unbounded
  * {@link #queueCapacity(int) queueCapacity} is configured (the default), the
  * max pool size is effectively ignored. See the "Unbounded queues" strategy
  * in {@link java.util.concurrent.ThreadPoolExecutor
 ThreadPoolExecutor} for
  * more details.
  * <p>By default this is set to {@code Integer.MAX_VALUE}.
  */
```

Found in path(s):
* /spring-messaging-4-3-30-release-sources-jar/org/springframework/messaging/simp/config/TaskExecutorRegistration.java

1.473 from2 2.3.0

1.473.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Hugh Kennedy

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
 OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.474 universalify 0.1.2

1.474.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2017, Ryan Zimmerman <opensrc@ryanzim.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the 'Software'), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS
FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR
COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER
IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.475 tough-cookie 2.5.0

1.475.1 Available under license :

Copyright (c) 2015, Salesforce.com, Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of Salesforce.com nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT

HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.


```
[
 {
  "test": "Sat, 15-Apr-17 21:01:22 GMT",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
 }, {
  "test": "Thu, 19-Apr-2007 16:00:00 GMT",
  "expected": "Thu, 19 Apr 2007 16:00:00 GMT"
 }, {
  "test": "Wed, 25 Apr 2007 21:02:13 GMT",
  "expected": "Wed, 25 Apr 2007 21:02:13 GMT"
 }, {
  "test": "Thu, 19/Apr\\2007 16:00:00 GMT",
  "expected": "Thu, 19 Apr 2007 16:00:00 GMT"
 }, {
  "test": "Fri, 1 Jan 2010 01:01:50 GMT",
  "expected": "Fri, 01 Jan 2010 01:01:50 GMT"
 }, {
  "test": "Wednesday, 1-Jan-2003 00:00:00 GMT",
  "expected": "Wed, 01 Jan 2003 00:00:00 GMT"
 }, {
  "test": ", 1-Jan-2003 00:00:00 GMT",
  "expected": "Wed, 01 Jan 2003 00:00:00 GMT"
 }, {
  "test": " 1-Jan-2003 00:00:00 GMT",
  "expected": "Wed, 01 Jan 2003 00:00:00 GMT"
 }, {
  "test": "1-Jan-2003 00:00:00 GMT",
  "expected": "Wed, 01 Jan 2003 00:00:00 GMT"
 }, {
  "test": "Wed,18-Apr-07 22:50:12 GMT",
  "expected": "Wed, 18 Apr 2007 22:50:12 GMT"
 }, {
  "test":
 "WillyWonka  , 18-Apr-07 22:50:12 GMT",
  "expected": "Wed, 18 Apr 2007 22:50:12 GMT"
 }, {
  "test": "WillyWonka  , 18-Apr-07 22:50:12",
  "expected": "Wed, 18 Apr 2007 22:50:12 GMT"
 }, {
  "test": "WillyWonka  ,  18-apr-07   22:50:12",
  "expected": "Wed, 18 Apr 2007 22:50:12 GMT"
```

```
}, {
  "test": "Mon, 18-Apr-1977 22:50:13 GMT",
  "expected": "Mon, 18 Apr 1977 22:50:13 GMT"
}, {
  "test": "Mon, 18-Apr-77 22:50:13 GMT",
  "expected": "Mon, 18 Apr 1977 22:50:13 GMT"
}, {
  "test": "\"Sat, 15-Apr-17\\\"21:01:22\\\"GMT\"",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "Partyday, 18- April-07 22:50:12",
  "expected": "Wed, 18 Apr 2007 22:50:12 GMT"
}, {
  "test": "Partyday, 18 - Apri-07 22:50:12",
  "expected": "Wed, 18 Apr 2007 22:50:12 GMT"
}, {
  "test": "Wednes, 1-Januar-2003 00:00:00 GMT",
  "expected": "Wed, 01 Jan 2003 00:00:00 GMT"
}, {
  "test": "Sat, 15-Apr-17 21:01:22",
  "expected": "Sat, 15 Apr 2017 21:01:22
GMT"
}, {
  "test": "Sat, 15-Apr-17 21:01:22 GMT-2",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "Sat, 15-Apr-17 21:01:22 GMT BLAH",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "Sat, 15-Apr-17 21:01:22 GMT-0400",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "Sat, 15-Apr-17 21:01:22 GMT-0400 (EDT)",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "Sat, 15-Apr-17 21:01:22 DST",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "Sat, 15-Apr-17 21:01:22 -0400",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "Sat, 15-Apr-17 21:01:22 (hello there)",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "Sat, 15-Apr-17 21:01:22 11:22:33",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "Sat, 15-Apr-17 ::00 21:01:22",
```

```
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "Sat, 15-Apr-17 boink:z 21:01:22",
  "expected":
"Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "Sat, 15-Apr-17 91:22:33 21:01:22",
  "expected": null
}, {
  "test": "Thu Apr 18 22:50:12 2007 GMT",
  "expected": "Wed, 18 Apr 2007 22:50:12 GMT"
}, {
  "test": "22:50:12 Thu Apr 18 2007 GMT",
  "expected": "Wed, 18 Apr 2007 22:50:12 GMT"
}, {
  "test": "Thu 22:50:12 Apr 18 2007 GMT",
  "expected": "Wed, 18 Apr 2007 22:50:12 GMT"
}, {
  "test": "Thu Apr 22:50:12 18 2007 GMT",
  "expected": "Wed, 18 Apr 2007 22:50:12 GMT"
}, {
  "test": "Thu Apr 18 22:50:12 2007 GMT",
  "expected": "Wed, 18 Apr 2007 22:50:12 GMT"
}, {
  "test": "Thu Apr 18 2007 22:50:12 GMT",
  "expected": "Wed, 18 Apr 2007 22:50:12 GMT"
}, {
  "test": "Thu Apr 18 2007 GMT 22:50:12",
  "expected": "Wed, 18 Apr 2007 22:50:12 GMT"
}, {
  "test": "Sat, 15-Apr-17 21:01:22 GMT",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "15-Sat, Apr-17 21:01:22 GMT",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"

}, {
  "test": "15-Sat, Apr 21:01:22 GMT 17",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "15-Sat, Apr 21:01:22 GMT 2017",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "15 Apr 21:01:22 2017",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "15 17 Apr 21:01:22",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
```

```
}, {
  "test": "Apr 15 17 21:01:22",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "Apr 15 21:01:22 17",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "2017 April 15 21:01:22",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "15 April 2017 21:01:22",
  "expected": "Sat, 15 Apr 2017 21:01:22 GMT"
}, {
  "test": "98 April 17 21:01:22",
  "expected": null
}, {
  "test": "Thu, 012-Aug-2008 20:49:07 GMT",
  "expected": null
}, {
  "test": "Thu, 12-Aug-31841 20:49:07 GMT",
  "expected": null
}, {
  "test": "Thu, 12-Aug-9999999999 20:49:07
GMT",
  "expected": null
}, {
  "test": "Thu, 999999999999-Aug-2007 20:49:07 GMT",
  "expected": null
}, {
  "test": "Thu, 12-Aug-2007 20:61:99999999999 GMT",
  "expected": null
}, {
  "test": "IAintNoDateFool",
  "expected": null
}
]
```


BSD-3-Clause

1.476 springsource-javax-validation 1.0.0.GA

1.476.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* JBoss, Home of Professional Open Source
* Copyright 2009, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
```

* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-0-0-ga-sources-jar/javax/validation/GroupSequence.java
No license file was found, but licenses were detected in source scan.

/*
* JBoss, Home of Professional Open Source
* Copyright 2009, Red Hat, Inc. and/or its affiliates, and individual contributors
* by the @authors tag. See the copyright.txt in the distribution for a
* full listing of individual contributors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* http://www.apache.org/licenses/LICENSE-2.0
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /validation-api-1-0-0-ga-sources-jar/javax/validation/ConstraintDeclarationException.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/constraints/Min.java
*
 /validation-api-1-0-0-ga-sources-jar/javax/validation/constraints/Max.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/spi/BootstrapState.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/ValidatorFactory.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/spi/ConfigurationState.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/constraints/Future.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/metadata/Scope.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/groups/package-info.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/ReportAsSingleViolation.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/metadata/ElementDescriptor.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/ConstraintValidatorFactory.java

* /validation-api-1-0-0-ga-sources-jar/javax/validation/constraints/Size.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/spi/ValidationProvider.java
*
 /validation-api-1-0-0-ga-sources-jar/javax/validation/constraints/Past.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/constraints/AssertFalse.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/Validator.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/Valid.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/ConstraintDefinitionException.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/GroupDefinitionException.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/constraints/DecimalMax.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/Validation.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/groups/Default.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/MessageInterpolator.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/ConstraintViolation.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/UnexpectedTypeException.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/constraints/NotNull.java
*
 /validation-api-1-0-0-ga-sources-jar/javax/validation/Configuration.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/ConstraintValidator.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/metadata/ConstraintDescriptor.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/ValidationProviderResolver.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/ConstraintValidatorContext.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/metadata/PropertyDescriptor.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/ConstraintViolationException.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/ValidatorContext.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/TraversableResolver.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/bootstrap/ProviderSpecificBootstrap.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/Payload.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/metadata/BeanDescriptor.java
*
 /validation-api-1-0-0-ga-sources-jar/javax/validation/bootstrap/GenericBootstrap.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/OverridesAttribute.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/Path.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/constraints/DecimalMin.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/constraints/AssertTrue.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/constraints/Pattern.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/Constraint.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/constraints/Digits.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/constraints/Null.java
* /validation-api-1-0-0-ga-sources-jar/javax/validation/ValidationException.java

1.477 js-base64 2.6.4

1.477.1 Available under license :

Copyright (c) 2014, Dan Kogai
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of {{{project}}} nor the names of its
 contributors may be used to endorse or promote products derived from
 this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER
 OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.478 errno 0.1.8

1.478.1 Available under license :

MIT

1.479 fs-extra 7.0.1

1.479.1 Available under license :

(The MIT License)

Copyright (c) 2011-2017 JP Richardson

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files
(the 'Software'), to deal in the Software without restriction, including without limitation the rights to use, copy, modify,
merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE
WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS
OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.480 exit-on-epipe 1.0.1

1.480.1 Available under license :

Copyright (C) 2015-present SheetJS

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache License 2.0

1.481 preserve 0.2.0

1.481.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2015, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following

conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

1.482 acorn 6.4.2

1.482.1 Available under license :

Copyright (C) 2012-2018 by various contributors (see AUTHORS)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.483 braces 3.0.2

1.483.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2018, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.484 tryer 1.0.1

1.484.1 Available under license :

MIT
Copyright 2013, 2017 Phil Booth

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.485 braces 1.8.5

1.485.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2016, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.486 bfj 6.1.2

1.486.1 Available under license :

Copyright 2015, 2016 Phil Booth

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.487 minimatch 2.0.10

1.487.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.488 har-validator 5.1.5

1.488.1 Available under license :

MIT License

Copyright (c) 2018 Ahmad Nassri <ahmad@ahmadnassri.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.489 uri-js 4.4.1

1.489.1 Available under license :

Copyright 2011 Gary Court. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY GARY COURT "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL GARY COURT OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The views and conclusions contained in the software and documentation are those of the authors and should not be interpreted as representing official policies, either expressed or implied, of Gary Court.
BSD-2-Clause

1.490 xpp3-min 1.1.4c

1.490.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2003 Extreme! Lab, Indiana University. All rights reserved.
*
* This software is open source. See the bottom of this file for the license.
*
* $Id: MXParser.java,v 1.52 2006/11/09 18:29:37 aslom Exp $
*/
/*

* Indiana University Extreme! Lab Software License, Version 1.2
*
* Copyright (C) 2003 The Trustees of Indiana University.
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
* 1) All redistributions of source code must retain the above
*   copyright notice, the list of authors in the original source
*   code, this list of conditions and the disclaimer listed in this
*   license;
*
* 2) All redistributions in binary form must reproduce the above
*   copyright notice, this list of conditions and the disclaimer
*   listed in this license in the documentation
 and/or other
*   materials provided with the distribution;
*
* 3) Any documentation included with all redistributions must include
*   the following acknowledgement:
*
*   "This product includes software developed by the Indiana
*   University Extreme! Lab. For further information please visit
*   http://www.extreme.indiana.edu/"
*
*   Alternatively, this acknowledgment may appear in the software
*   itself, and wherever such third-party acknowledgments normally
*   appear.
*
* 4) The name "Indiana University" or "Indiana University
*   Extreme! Lab" shall not be used to endorse or promote
*   products derived from this software without prior written
*   permission from Indiana University. For written permission,
*   please contact http://www.extreme.indiana.edu/.
*
* 5) Products derived from this software may not use "Indiana
*   University" name nor may "Indiana University" appear in their name,
*   without prior written permission
 of the Indiana University.
*
* Indiana University provides no reassurances that the source code
* provided does not infringe the patent or any other intellectual
* property rights of any other entity. Indiana University disclaims any
* liability to any recipient for claims brought by any other entity
* based on infringement of intellectual property rights or otherwise.
*

* LICENSEE UNDERSTANDS THAT SOFTWARE IS PROVIDED "AS IS" FOR WHICH
* NO WARRANTIES AS TO CAPABILITIES OR ACCURACY ARE MADE. INDIANA
* UNIVERSITY GIVES NO WARRANTIES AND MAKES NO REPRESENTATION THAT
* SOFTWARE IS FREE OF INFRINGEMENT OF THIRD PARTY PATENT, COPYRIGHT, OR
* OTHER PROPRIETARY RIGHTS. INDIANA UNIVERSITY MAKES NO WARRANTIES THAT
* SOFTWARE IS FREE FROM "BUGS", "VIRUSES", "TROJAN HORSES", "TRAP
* DOORS", "WORMS", OR OTHER HARMFUL CODE. LICENSEE ASSUMES THE ENTIRE
* RISK AS TO THE PERFORMANCE OF SOFTWARE AND/OR ASSOCIATED MATERIALS,
* AND TO THE PERFORMANCE AND VALIDITY OF INFORMATION GENERATED
 USING
* SOFTWARE.
*/

Found in path(s):
* /xpp3-min-1-1-4c-sources-1-jar/org/xmlpull/mxp1/MXParser.java

1.491 commons-lang3 2.4

1.491.1 Available under license :

Apache Commons Lang
Copyright 2001-2008 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership

of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,

worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or

documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,

indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.492 array-differ 1.0.0

1.492.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.493 ansi-escapes 1.4.0

1.493.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.494 beeper 1.1.1

1.494.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.495 cli-cursor 1.0.2

1.495.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell

copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.496 coffee-loader 0.7.3

1.496.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.497 date-format 2.2.0

1.497.1 Available under license :

Copyright (c) 2018-present, Ryan Haskell-Glatz

All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.

* Neither the name of Ryan Haskell-Glatz nor the names of other
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.498 duplexify 3.7.1

1.498.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Mathias Buus

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.499 duplexer2 0.0.2

1.499.1 Available under license :

BSD-style without advertising clause
Copyright (c) 2013, Deoxxa Development
==========
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:
1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
3. Neither the name of Deoxxa Development nor the names of its contributors
may be used to endorse or promote products derived from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY DEOXXA DEVELOPMENT "AS IS" AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL DEOXXA DEVELOPMENT BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.500 figures 1.7.0

1.500.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.501 expand-range 1.8.2

1.501.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2016, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.502 exit-hook 1.1.1

1.502.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.503 flush-write-stream 1.1.1

1.503.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 Mathias Buus

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.504 growly 1.3.0

1.504.1 Available under license :

MIT

1.505 gulp-util 3.0.8

1.505.1 Available under license :

Copyright (c) 2014 Fractal <contact@wearefractal.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN

CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.506 gulplog 1.0.0

1.506.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Blaine Bublitz, Eric Schoffstall and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.507 glogg 1.0.2

1.507.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014, 2015, 2018 Blaine Bublitz <blaine.bublitz@gmail.com> and Eric Schoffstall <yo@contra.io>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.508 has-gulplog 0.1.0

1.508.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 gulp

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.509 in-publish 2.0.1

1.509.1 Available under license :

ISC
Copyright (c) 2015, Rebecca Turner <me@re-becca.org>

Permission to use, copy, modify, and/or distribute this software for any

purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.510 is-finite 1.1.0

1.510.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.511 is-utf8 0.2.1

1.511.1 Available under license :

MIT
The MIT License (MIT)

Copyright (C) 2014 Wei Fanzhe

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit

persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.512 log-update 1.0.2

1.512.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.513 math-random 1.0.4

1.513.1 Available under license :

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell

copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.514 mute-stream 0.0.4

1.514.1 Available under license :

Copyright (c) Isaac Z. Schlueter ("Author")
All rights reserved.

The BSD License

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE AUTHOR AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
 GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

BSD-style without advertising clause

1.515 multipipe 0.1.2

1.515.1 Available under license :

MIT

1.516 parallel-transform 1.2.0

1.516.1 Available under license :

Copyright 2013 Mathias Buus

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE
 OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.517 p-limit 2.3.0

1.517.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.518 pretty-hrtime 1.0.3

1.518.1 Available under license :

MIT
Copyright (c) 2013 [Richardson & Sons, LLC](http://richardsonandsons.com/)

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.519 randomatic 3.1.1

1.519.1 Available under license :

The MIT License (MIT)

Copyright (c) 2013-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.520 redux-mock-store 1.5.4

1.520.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017 Arnaud Benard

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.521 sass-graph 2.2.5

1.521.1 Available under license :

Copyright 2014 Michael Mifsud

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.522 restore-cursor 1.0.1

1.522.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN

THE SOFTWARE.
MIT

1.523 run-async 0.1.0

1.523.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Simon Boudrias

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.524 rx-lite 3.1.2

1.524.1 Available under license :

Apache License 2.0

1.525 shellwords 0.1.1

1.525.1 Available under license :

Copyright (C) 2011 by Jimmy Cuadra

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is

furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.526 sparkles 1.0.1

1.526.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Blaine Bublitz <blaine.bublitz@gmail.com> and Eric Schoffstall <yo@contra.io>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN
ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.527 spdx-expression-parse 3.0.1

1.527.1 Available under license :

The MIT License

Copyright (c) 2015 Kyle E. Mitchell & other authors listed in AUTHORS

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.528 string-template 1.0.0

1.528.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 MacFJA

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.529 through2 2.0.5

1.529.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) Rod Vagg (the "Original Author") and additional contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.530 stream-shift 1.0.1

1.530.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2016 Mathias Buus

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.531 unique-slug 2.0.2

1.531.1 Available under license :

The ISC License

Copyright npm, Inc

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.532 worker-loader 2.0.0

1.532.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.533 commons-dbcp 2.0.1

1.533.1 Available under license :

Apache Commons DBCP
Copyright 2001-2014 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation

source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this

License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided

that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
   the Work or Derivative Works thereof, You may choose to offer,
   and charge a fee for, acceptance of support, warranty, indemnity,
   or other liability obligations and/or rights consistent with this
   License. However, in accepting such obligations, You may act only
   on Your own behalf and on Your sole responsibility, not on behalf
   of any other Contributor, and only if You agree to indemnify,
   defend, and hold each Contributor harmless for any liability
    incurred by, or claims asserted against, such Contributor by reason
   of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

   To apply the Apache License to your work, attach the following
   boilerplate notice, with the fields enclosed by brackets "[]"
   replaced with your own identifying information. (Don't include
   the brackets!) The text should be enclosed in the appropriate
   comment syntax for the file format. We also recommend that a
   file or class name and description of purpose be included on the
   same "printed page" as the copyright notice for easier
   identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

    http://www.apache.org/licenses/LICENSE-2.0

 Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.534 kryo 2.17

1.534.1 Available under license :

No license file was found, but licenses were detected in source scan.

/***
* Copyright 2011 See AUTHORS file.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
**/

Found in path(s):
* /kryo-2-17-sources-1-jar/com/esotericsoftware/kryo/util/IntMap.java
* /kryo-2-17-sources-1-jar/com/esotericsoftware/kryo/util/IdentityMap.java

1.535 annotations 13.0

1.535.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2000-2009 JetBrains s.r.o.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /annotations-13-0-sources-3-jar/org/jetbrains/annotations/NonNls.java
* /annotations-13-0-sources-3-jar/org/jetbrains/annotations/Nullable.java
* /annotations-13-0-sources-3-jar/org/jetbrains/annotations/Nls.java
* /annotations-13-0-sources-3-jar/org/jetbrains/annotations/PropertyKey.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2006 Sascha Weinreuter
*

* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /annotations-13-0-sources-3-jar/org/intellij/lang/annotations/Subst.java
* /annotations-13-0-sources-3-jar/org/intellij/lang/annotations/Pattern.java
* /annotations-13-0-sources-3-jar/org/intellij/lang/annotations/Language.java
* /annotations-13-0-sources-3-jar/org/intellij/lang/annotations/PrintFormat.java
*
 /annotations-13-0-sources-3-jar/org/intellij/lang/annotations/RegExp.java
* /annotations-13-0-sources-3-jar/org/intellij/lang/annotations/Identifier.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2000-2013 JetBrains s.r.o.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /annotations-13-0-sources-3-jar/org/intellij/lang/annotations/Flow.java
* /annotations-13-0-sources-3-jar/org/jetbrains/annotations/Contract.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2000-2012 JetBrains s.r.o.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /annotations-13-0-sources-3-jar/org/jetbrains/annotations/TestOnly.java
* /annotations-13-0-sources-3-jar/org/intellij/lang/annotations/MagicConstant.java
* /annotations-13-0-sources-3-jar/org/intellij/lang/annotations/JdkConstants.java
* /annotations-13-0-sources-3-jar/org/jetbrains/annotations/NotNull.java

1.536 woodstox-core 6.2.4

1.536.1 Available under license :

This copy of Jackson JSON processor databind module is licensed under the
Apache (Software) License, version 2.0 ("the License").
See the License for details about distribution rights, and the
specific rights regarding derivate works.

You may obtain a copy of the License at:

http://www.apache.org/licenses/LICENSE-2.0

1.537 lodash 4.17.21

1.537.1 Available under license :

Software License Agreement (BSD License)

Copyright (c) 2007, Parakey Inc.
All rights reserved.

Redistribution and use of this software in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above
 copyright notice, this list of conditions and the
 following disclaimer.

* Redistributions in binary form must reproduce the above

copyright notice, this list of conditions and the
following disclaimer in the documentation and/or other
materials provided with the distribution.

* Neither the name of Parakey Inc. nor the names of its
contributors may be used to endorse or promote products
derived from this software without specific prior
written permission of Parakey Inc.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND
FITNESS
FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER
IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT
OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Copyright OpenJS Foundation and other contributors <https://openjsf.org/>

Based on Underscore.js, copyright Jeremy Ashkenas,
DocumentCloud and Investigative Reporters & Editors <http://underscorejs.org/>

This software consists of voluntary contributions made by many
individuals. For exact contribution history, see the revision history
available at https://github.com/lodash/lodash

The following license applies to all parts of this software except as
documented below:

====

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be

included in all copies
or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

====

Copyright and related rights for sample code are waived via CC0. Sample code is defined as all source code displayed within the prose of the documentation.

CC0: http://creativecommons.org/publicdomain/zero/1.0/

====

Files located in the node_modules and vendor directories are externally maintained libraries used by this software which have their own licenses; we recommend you read them, as their terms may differ from the terms above.
Copyright (c) 2010-2016 Jeremy Ashkenas, DocumentCloud

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

MIT
Copyright (c) 2009-2016 Jeremy Ashkenas, DocumentCloud and Investigative Reporters & Editors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.538 error_prone_annotations 2.1.3

1.538.1 Available under license :

Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of

fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean
the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name)
to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual
or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by
combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and
You must cause any modified files to carry prominent notices stating that You changed the files; and
You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that
such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.
5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or
product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any
Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims
asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.539 j2objc-annotations 1.1

1.539.1 Available under license :

Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean
the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the

Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name)
to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual
or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by
combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

You must give any other recipients of the Work or Derivative Works a copy of this License; and
You must cause any modified files to carry prominent notices stating that You changed the files; and
You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices

normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that
such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.
5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or
product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any
Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims
asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.540 jsr305 1.3.9

1.540.1 Available under license :

Apache License
Version 2.0, January 2004
https://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain

separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without

modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include

the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

https://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.541 log4j-over-slf4j 1.7.21

1.541.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2001-2004 The Apache Software Foundation.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/Log4jLoggerFactory.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/spi/ErrorHandler.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/spi/OptionHandler.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/LogManager.java
*

/log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/PatternLayout.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/MDC.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/spi/LoggerFactory.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/Priority.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/spi/LoggerRepository.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/Logger.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/AppenderSkeleton.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/spi/Configurator.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/spi/Filter.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/SimpleLayout.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/PropertyConfigurator.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/WriterAppender.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/Level.java
*
/log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/Category.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/helpers/LogLog.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/FileAppender.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/Appender.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/NDC.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/ConsoleAppender.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/Layout.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/BasicConfigurator.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/RollingFileAppender.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/spi/LoggingEvent.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/xml/DOMConfigurator.java
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/spi/HierarchyEventListener.java
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /log4j-over-slf4j-1-7-21-sources-2-jar/org/apache/log4j/helpers/NullEnumeration.java

1.542 spring-binding 2.5.1.RELEASE

1.542.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2004-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/message/MessageResolver.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/expression/PropertyNotFoundException.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/expression/support/AbstractGetValueExpression.java
*
 /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/el/DefaultELResolver.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/convert/converters/FormattedStringToNumber.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/format/package-info.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/convert/converters/SpringConvertingConverterAdapter.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/beanwrapper/package-
info.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/package-info.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/expression/support/CollectionAddingExpression.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/el/package-info.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/package-info.java
*
 /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/mapping/impl/DefaultMappingContext.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/validation/package-info.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/message/MessageContextErrors.java

* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/service/package-info.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/expression/beanwrapper/BeanWrapperExpression.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/results/package-info.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/expression/support/NullParserContext.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/ParserContext.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/support/package-info.java
*
 /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/collection/MapAccessor.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/message/DefaultMessageContext.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/convert/service/TwoWayCapableConversionExecutor.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/message/MessageBuilder.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/collection/package-info.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/convert/service/RuntimeBindingConversionExecutor.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/el/ELExpressionParser.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/expression/ValueCoercionException.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/mapping/results/AbstractMappingResult.java
*
 /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/convert/service/SpringBindingConverterAdapter.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/el/ELExpression.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/expression/el/MapAdaptableELResolver.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/package-info.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/package-info.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/collection/StringKeyedMapAdapter.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/collection/SharedMap.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/StringToDate.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/message/package-info.java
*
 /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/method/package-info.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/method/MethodInvoker.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/impl/package-info.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/expression/support/FluentParserContext.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/expression/support/LiteralExpression.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2004-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/expression/support/AbstractExpressionParser.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2004-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not
* use this file except in compliance with the License. You may obtain a copy of
* the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/collection/SharedMapDecorator.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2004-2008 the original author oimport java.io.Serializable;

import org.springframework.core.style.ToStringCreator;
ou may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/message/Message.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2004-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/convert/converters/StringToBigDecimal.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/StringToInteger.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/method/MethodKey.java
*
 /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/convert/converters/ReverseConverter.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/expression/support/CompositeStringExpression.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/StringToByte.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/collection/MapAdaptable.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/ConversionService.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/convert/converters/PropertyEditorConverter.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/convert/service/StaticConversionExecutor.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/convert/ConversionExecutorNotFoundException.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/method/Parameter.java
*
 /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/StringToEnum.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/method/Parameters.java

* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/ConversionExecutionException.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/support/StaticExpression.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/StringToClass.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/ConversionExecutor.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/EvaluationException.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/StringToLocale.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/Converter.java
*
 /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/ArrayToCollection.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/StringToFloat.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/StringToBigInteger.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/ObjectToCollection.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/StringToObject.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/StringToShort.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/StringToLong.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/TwoWayConverter.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/StringToCharacter.java
*
 /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/impl/DefaultMapper.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/method/InvalidMethodKeyException.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/ObjectToArray.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/method/MethodSignature.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/StringToDouble.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/service/GenericConversionService.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/Expression.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/StringToBoolean.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/ArrayToArray.java
*
 /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/service/NoOpConverter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2004-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*

* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/format/IntegerNumberFormatFactory.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/MappingResultsCriteria.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/results/RequiredError.java
*
 /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/beanwrapper/BeanWrapperExpressionParser.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/message/MessageCriteria.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/message/StateManageableMessageContext.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/ExpressionVariable.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/format/DefaultNumberFormatFactory.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/format/AbstractNumberFormatFactory.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/format/CurrencyNumberFormatFactory.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/message/DefaultMessageResolver.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/el/DefaultELContext.java
*
 /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/results/SourceAccessError.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/results/TypeConversionError.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/message/MessageContext.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/results/TargetAccessError.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/message/Severity.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/results/Success.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/el/DefaultElContextFactory.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/format/PercentNumberFormatFactory.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/el/ELContextFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2004-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/support/SimpleParserContext.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/spel/SpringELExpression.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/impl/DefaultMappingResults.java
*
 /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/spel/SpringELExpressionParser.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/validation/ValidationContext.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2004-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/MappingResults.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/MappingResult.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/expression/spel/EvaluationContextFactory.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/expression/spel/SimpleEvaluationContextFactory.java
* /spring-binding-2-5-1-release-sources-2-
jar/org/springframework/binding/expression/spel/StandardEvaluationContextFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2004-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at

*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/ConversionException.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/converters/InvalidFormatException.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/method/MethodInvocationException.java
*
 /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/impl/DefaultMapping.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/ParserException.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/Mapping.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/mapping/Mapper.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/expression/ExpressionParser.java
* /spring-binding-2-5-1-release-sources-2-jar/org/springframework/binding/convert/service/DefaultConversionService.java

1.543 spring-webmvc-portlet 4.3.19.RELEASE

1.543.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):

* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/mvc/annotation/AnnotationMethodHandlerAdapter.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/mvc/annotation/DefaultAnnotationHandlerMapping.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/mvc/annotation/PortletAnnotationMappingUtils.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/HandlerExecutionChain.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/context/PortletWebRequest.java

* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/multipart/PortletMultipartResolver.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/bind/annotation/ActionMapping.java
*
 /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/mvc/annotation/AnnotationMethodHandlerExceptionResolver.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/FrameworkPortlet.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/bind/annotation/RenderMapping.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/handler/SimpleMappingExceptionResolver.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/handler/AbstractHandlerExceptionResolver.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/mvc/PortletWrappingController.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/DispatcherPortlet.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/context/PortletRequestAttributes.java
*
 /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/context/PortletApplicationContextUtils.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/multipart/CommonsPortletMultipartResolver.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/handler/SimplePortletPostProcessor.java
No license file was found, but licenses were detected in source scan.

/*

* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/HandlerExceptionResolver.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/HandlerAdapter.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/context/PortletContextResource.java
*
 /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/context/PortletRequestHandledEvent.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/ModelAndViewDefiningException.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/bind/MissingPortletRequestParameterException.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/handler/HandlerInterceptorAdapter.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/handler/ParameterHandlerMapping.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/handler/PortletModeHandlerMapping.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/context/AbstractRefreshablePortletApplicationContext.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/handler/PortletRequestMethodNotSupportedException.java
*
 /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/mvc/PortletModeNameViewController.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/GenericPortletBean.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/bind/PortletRequestUtils.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/multipart/DefaultMultipartActionRequest.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/util/PortletUtils.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-

jar/org/springframework/web/portlet/bind/PortletRequestDataBinder.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/ModelAndView.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/handler/ParameterMappingInterceptor.java
*
/spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/mvc/SimpleControllerHandlerAdapter.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/handler/AbstractMapBasedHandlerMapping.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/handler/SimplePortletHandlerAdapter.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/handler/PortletContentGenerator.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/context/PortletContextAware.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/NoHandlerFoundException.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/handler/WebRequestHandlerInterceptorAdapter.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/handler/PortletModeParameterHandlerMapping.java
*
/spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/context/PortletApplicationObjectSupport.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/mvc/ResourceAwareController.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/context/PortletContextResourcePatternResolver.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/HandlerMapping.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/context/PortletContextAwareProcessor.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/mvc/Controller.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/bind/PortletRequestBindingException.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/context/PortletContextScope.java
*
/spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/context/PortletConfigAware.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/handler/PortletSessionRequiredException.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/bind/PortletRequestParameterPropertyValues.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2008 the original author or authors.
*

* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/handler/PortletModeParameterLookupKey.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/multipart/MultipartActionRequest.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2006 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-portlet-4-3-19-release-sources-2-
jar/org/springframework/web/portlet/context/PortletContextResourceLoader.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*

* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/mvc/EventAwareController.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/context/XmlPortletApplicationContext.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/bind/annotation/ResourceMapping.java
*
 /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/bind/annotation/EventMapping.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/context/PortletConfigPropertySource.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/context/PortletContextPropertySource.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/handler/AbstractHandlerMapping.java
*
 /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/context/ConfigurablePortletApplicationContext.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-

jar/org/springframework/web/portlet/mvc/AbstractController.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/context/StaticPortletApplicationContext.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/mvc/ParameterizableViewController.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/context/StandardPortletEnvironment.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/handler/UserRoleAuthorizationInterceptor.java
* /spring-webmvc-portlet-4-3-19-release-sources-2-jar/org/springframework/web/portlet/HandlerInterceptor.java

1.544 spring-oxm 4.3.19.RELEASE

1.544.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2013 the original author or authors.
 *
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/config/Jaxb2MarshallerBeanDefinitionParser.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
```

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/ValidationFailureException.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/support/SaxResourceUtils.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/MarshallingException.java
*
/spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/UncategorizedMappingException.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/support/MarshallingSource.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/mime/MimeContainer.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/MarshallingFailureException.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/UnmarshallingFailureException.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/GenericMarshaller.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/XmlMappingException.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/GenericUnmarshaller.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/xstream/XStreamMarshaller.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/config/OxmNamespaceHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at

*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/mime/MimeMarshaller.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/mime/MimeUnmarshaller.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/jibx/JibxMarshaller.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/jaxb/ClassPathJaxb2TypeScanner.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/jaxb/Jaxb2Marshaller.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/config/JibxMarshallerBeanDefinitionParser.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/config/XmlBeansMarshallerBeanDefinitionParser.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/castor/CastorMappingException.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/castor/CastorMarshaller.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/config/CastorMarshallerBeanDefinitionParser.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
*/

Found in path(s):
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/xmlbeans/XmlBeansMarshaller.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/xmlbeans/XmlOptionsFactoryBean.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/xstream/CatchAllConverter.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/support/AbstractMarshaller.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/Marshaller.java
* /spring-oxm-4-3-19-release-sources-3-jar/org/springframework/oxm/Unmarshaller.java

1.545 spring-context-support 4.3.19.RELEASE

1.545.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/KeyGeneratorAdapter.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/config/ProxyJCacheConfiguration.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/CacheResolverAdapter.java
*
/spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/quartz/SchedulerFactoryBean.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/mail/SimpleMailMessage.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/ehcache/EhCacheCache.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/quartz/SchedulerAccessor.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/JCacheCache.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/AbstractFallbackJCacheOperationSource.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/commonj/TimerManagerTaskScheduler.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/ehcache/EhCacheManagerFactoryBean.java
*

/spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/quartz/ResourceLoaderClassLoadHelper.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/quartz/CronTriggerFactoryBean.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/quartz/SpringBeanJobFactory.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/caffeine/CaffeineCacheManager.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/quartz/SimpleTriggerFactoryBean.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/caffeine/CaffeineCache.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/commonj/WorkManagerTaskExecutor.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/quartz/SchedulerContextAware.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
```

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/transaction/TransactionAwareCacheDecorator.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/commonj/ScheduledTimerListener.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/CacheResultInterceptor.java
*
 /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/ui/freemarker/FreeMarkerConfigurationFactory.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/JCacheCacheManager.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/DefaultCacheInvocationContext.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/mail/MailMessage.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/JCacheAspectSupport.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/CachePutInterceptor.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/quartz/MethodInvokingJobDetailFactoryBean.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/ehcache/EhCacheManagerUtils.java
*

/spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/transaction/TransactionAwareCacheManagerProxy.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/ui/freemarker/SpringTemplateLoader.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/ehcache/EhCacheFactoryBean.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/AbstractCacheInterceptor.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/JCacheInterceptor.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/AbstractJCacheOperation.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/JCacheOperationSource.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/mail/MailSender.java
*
/spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/CacheResultOperation.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/ui/jasperreports/JasperReportsUtils.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/DefaultCacheMethodDetails.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/config/JCacheConfigurerSupport.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/AbstractJCacheKeyOperation.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/mail/javamail/JavaMailSender.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/BeanFactoryJCacheOperationSourceAdvisor.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/CacheRemoveAllInterceptor.java
*
/spring-context-support-4-3-19-release-sources-2-jar/org/springframework/mail/javamail/MimeMailMessage.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/SimpleExceptionCacheResolver.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/quartz/AdaptableJobFactory.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/DefaultCacheKeyInvocationContext.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/ui/freemarker/FreeMarkerTemplateUtils.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/jcache/interceptor/CacheRemoveAllOperation.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/quartz/LocalTaskExecutorThreadPool.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/quartz/LocalDataSourceJobStore.java
*

/spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/quartz/QuartzJobBean.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/scheduling/quartz/SchedulerAccessorBean.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/cache/jcache/interceptor/CacheRemoveOperation.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/cache/jcache/interceptor/CachePutOperation.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/cache/jcache/interceptor/AbstractKeyCacheInterceptor.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/cache/jcache/config/JCacheConfigurer.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/guava/GuavaCacheManager.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/cache/jcache/JCacheManagerFactoryBean.java
*
/spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/scheduling/quartz/JobDetailFactoryBean.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/mail/javamail/InternetAddressEditor.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/cache/jcache/interceptor/JCacheOperationSourcePointcut.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/cache/jcache/interceptor/CacheRemoveEntryInterceptor.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/mail/javamail/ConfigurableMimeFileTypeMap.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/scheduling/commonj/DelegatingWork.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/mail/MailParseException.java
* /spring-context-support-4-3-19-release-sources-2-

jar/org/springframework/scheduling/commonj/TimerManagerFactoryBean.java
*
/spring-context-support-4-3-19-release-sources-2-jar/org/springframework/mail/MailSendException.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/mail/MailPreparationException.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/scheduling/quartz/JobMethodInvocationFailedException.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/cache/transaction/AbstractTransactionSupportingCacheManager.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/mail/MailAuthenticationException.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/ui/velocity/VelocityEngineFactoryBean.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/mail/javamail/MimeMessagePreparator.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/mail/javamail/SmartMimeMessage.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/scheduling/quartz/DelegatingJob.java
*
/spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/scheduling/commonj/DelegatingTimerListener.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/ui/freemarker/FreeMarkerConfigurationFactoryBean.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/scheduling/commonj/TimerManagerAccessor.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/ui/velocity/SpringResourceLoader.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/mail/MailException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/cache/guava/GuavaCache.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/cache/jcache/interceptor/DefaultJCacheOperationSource.java
* /spring-context-support-4-3-19-release-sources-2-

jar/org/springframework/cache/jcache/config/AbstractJCacheConfiguration.java
*
/spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/cache/jcache/interceptor/AnnotationJCacheOperationSource.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/cache/jcache/interceptor/JCacheOperation.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/mail/javamail/JavaMailSenderImpl.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/cache/ehcache/EhCacheCacheManager.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/scheduling/quartz/SimpleThreadPoolTaskExecutor.java
* /spring-context-support-4-3-19-release-sources-2-
jar/org/springframework/mail/javamail/MimeMessageHelper.java
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/ui/velocity/VelocityEngineFactory.java
*
/spring-context-support-4-3-19-release-sources-2-jar/org/springframework/ui/velocity/VelocityEngineUtils.java
No license file was found, but licenses were detected in source scan.

##
Copyright 2002-2018 the original author or authors.
#
Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at
#
http://www.apache.org/licenses/LICENSE-2.0
#
Unless required by applicable law or agreed to in writing, software

```
# distributed under the License is distributed on an "AS IS" BASIS,
# WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
# See the License for the specific language governing permissions and
# limitations under the License.
##############################################################################

##############################################################################
#
# Defaults for the Java Activation Framework (revised).
# Modified extensions registered
 in this file:
# text/plain   java c c++ cpp pl cc h
# image/png    png
#
##############################################################################

text/html    html htm HTML HTM
text/plain    txt text TXT TEXT java c c++ cpp pl cc h
image/gif    gif GIF
image/ief    ief
image/jpeg    jpeg jpg jpe JPG
image/tiff    tiff tif
image/x-xwindowdump   xwd
application/postscript   ai eps ps
application/rtf    rtf
application/x-tex   tex
application/x-texinfo   texinfo texi
application/x-troff   t tr roff
audio/basic    au
audio/midi    midi mid
audio/x-aifc    aifc
audio/x-aiff    aif aiff
audio/x-mpeg    mpeg mpg
audio/x-wav    wav
video/mpeg    mpeg mpg mpe
video/quicktime    qt mov
video/x-msvideo    avi

##############################################################################
#
# Additional file types adapted from
# http://www.utoronto.ca/webdocs/HTMLdocs/Book/Book-3ed/appb/mimetype.html
# kindly re-licensed to Apache Software License 2.0 by Ian Graham.
#
##############################################################################

#
```

TEXT TYPES

text/x-speech talk
text/css css
text/csv csv

IMAGE TYPES

X-Windows bitmap (b/w)
image/x-xbitmap xbm
X-Windows pixelmap (8-bit color)
image/x-xpixmap xpm
Portable Network Graphics
image/png png
Image Exchange Format (RFC 1314)
image/ief ief
RGB
image/rgb rgb
Group III Fax (RFC 1494)
image/g3fax g3f
X Windowdump format
image/x-xwindowdump xwd
Macintosh PICT format
image/x-pict pict
PPM (UNIX PPM package)
image/x-portable-pixmap ppm
PGM (UNIX PPM package)
image/x-portable-graymap pgm
PBM (UNIX PPM package)
image/x-portable-bitmap pbm
PNM (UNIX PPM package)
image/x-portable-anymap pnm
Microsoft Windows bitmap
image/x-ms-bmp bmp
CMU raster
image/x-cmu-raster ras
Kodak Photo-CD
image/x-photo-cd pcd
Computer Graphics Metafile
image/cgm cgm
CALS Type 1 or 2
image/x-cals mil cal
Fractal Image Format (Iterated Systems)
image/fif fif
#
QuickSilver active image (Micrografx)
image/x-mgx-dsf dsf
CMX vector image (Corel)

image/x-cmx cmx
Wavelet-compressed (Summus)
image/wavelet wi
AutoCad Drawing (SoftSource)
image/vnd.dwg dwg
AutoCad DXF file (SoftSource)
image/vnd.dxf dxf
Simple Vector Format (SoftSource)
image/vnd.svf svf

AUDIO/VOICE/MUSIC RELATED TYPES

"""basic""audio - 8-bit u-law PCM"
audio/basic au snd
Macintosh audio format (AIpple)
audio/x-aiff aif aiff aifc
Microsoft audio
audio/x-wav wav
MPEG audio
audio/x-mpeg mpa abs mpega
MPEG-2 audio
audio/x-mpeg-2 mp2a mpa2
compressed speech (Echo Speech Corp.)
audio/echospeech es
Toolvox speech audio (Voxware)
audio/voxware vox
RapidTransit compressed audio (Fast Man)
application/fastman lcc
Realaudio (Progressive Networks)
application/x-pn-realaudio ra ram
MIDI music data
x-music/x-midi mmid
Koan music data (SSeyo)
application/vnd.koan skp
Speech synthesis data (MVP Solutions)
text/x-speech talk

#
VIDEO TYPES

MPEG video
video/mpeg mpeg mpg mpe
MPEG-2 video
video/mpeg-2 mpv2 mp2v
Macintosh Quicktime
video/quicktime qt mov
Microsoft video
video/x-msvideo avi

```
# SGI Movie format
video/x-sgi-movie   movie
# VDOlive streaming video (VDOnet)
video/vdo    vdo
# Vivo streaming video (Vivo software)
video/vnd.vivo    viv

# SPECIAL HTTP/WEB APPLICATION TYPES

# Proxy autoconfiguration (Netscape browsers)
application/x-ns-proxy-autoconfig pac
# Netscape Cooltalk chat data (Netscape)
x-conference/x-cooltalk   ice

# TEXT-RELATED

# PostScript
application/postscript   ai eps ps
# Microsoft Rich Text Format
application/rtf    rtf
# Adobe Acrobat PDF
application/pdf    pdf
# Maker Interchange Format (FrameMaker)
application/vnd.mif   mif
# Troff document
application/x-troff   t tr roff
# Troff document with MAN macros
application/x-troff-man   man
# Troff document with ME macros
application/x-troff-me   me
# Troff document with MS macros
application/x-troff-ms   ms
#
 LaTeX document
application/x-latex   latex
# Tex/LateX document
application/x-tex   tex
# GNU TexInfo document
application/x-texinfo   texinfo texi
# TeX dvi format
application/x-dvi   dvi
# MS word document
application/msword   doc DOC
# Office Document Architecture
application/oda    oda
# Envoy Document
application/envoy   evy
```

```
# ARCHIVE/COMPRESSED ARCHIVES

# Gnu tar format
application/x-gtar   gtar
# 4.3BSD tar format
application/x-tar   tar
# POSIX tar format
application/x-ustar   ustar
# Old CPIO format
application/x-bcpio   bcpio
# POSIX CPIO format
application/x-cpio   cpio
# UNIX sh shell archive
application/x-shar   shar
# DOS/PC - Pkzipped archive
application/zip    zip
# Macintosh Binhexed archive
application/mac-binhex40  hqx
# Macintosh Stuffit Archive
application/x-stuffit   sit sea
# Fractal Image Format
application/fractals   fif
# "Binary UUencoded"
application/octet-stream  bin uu
# PC executable
application/octet-stream  exe
# "WAIS ""sources"""
application/x-wais-source  src
 wsrc
# NCSA HDF data format
application/hdf    hdf

# DOWNLOADABLE PROGRAM/SCRIPTS

# Javascript program
text/javascript    js ls mocha
# UNIX bourne shell program
application/x-sh   sh
# UNIX c-shell program
application/x-csh   csh
# Perl program
application/x-perl   pl
# Tcl (Tool Control Language) program
application/x-tcl   tcl

# ANIMATION/MULTIMEDIA

# FutureSplash vector animation (FutureWave)
```

application/futuresplash spl
mBED multimedia data (mBED)
application/mbedlet   mbd
PowerMedia multimedia (RadMedia)
application/x-rad-powermedia rad

PRESENTATION

PowerPoint presentation (Microsoft)
application/mspowerpoint ppz
ASAP WordPower (Software Publishing Corp.)
application/x-asap   asp
Astound Web Player multimedia data (GoldDisk)
application/astound   asn

SPECIAL EMBEDDED OBJECT

OLE script e.g. Visual Basic (Ncompass)
application/x-olescript   axs
OLE Object (Microsoft/NCompass)
application/x-oleobject   ods
OpenScape
 OLE/OCX objects (Business@Web)
x-form/x-openscape   opp
Visual Basic objects (Amara)
application/x-webbasic   wba
Specialized data entry forms (Alpha Software)
application/x-alpha-form frm
client-server objects (Wayfarer Communications)
x-script/x-wfxclient   wfx

GENERAL APPLICATIONS

Undefined binary data (often executable progs)
application/octet-stream exe com
Pointcast news data (Pointcast)
application/x-pcn   pcn
Excel spreadsheet (Microsoft)
application/vnd.ms-excel xls
PowerPoint (Microsoft)
application/vnd.ms-powerpoint ppt
Microsoft Project (Microsoft)
application/vnd.ms-project mpp
SourceView document (Dataware Electronics)
application/vnd.svd   svd
Net Install - software install (20/20 Software)
application/x-net-install ins
Carbon Copy - remote control/access (Microcom)

application/ccv ccv
Spreadsheets (Visual Components)
workbook/formulaone vts

2D/3D DATA/VIRTUAL REALITY TYPES

VRML data file
x-world/x-vrml wrl vrml
WIRL -
VRML data (VREAM)
x-world/x-vream vrw
Play3D 3d scene data (Play3D)
application/x-p3d p3d
Viscape Interactive 3d world data (Superscape)
x-world/x-svr svr
WebActive 3d data (Plastic Thought)
x-world/x-wvr wvr
QuickDraw3D scene data (Apple)
x-world/x-3dmf 3dmf

SCIENTIFIC/MATH/CAD TYPES

Mathematica notebook
application/mathematica ma
Computational meshes for numerical simulations
x-model/x-mesh msh
Vis5D 5-dimensional data
application/vis5d v5d
IGES models -- CAD/CAM (CGM) data
application/iges igs
Autocad WHIP vector drawings
drawing/x-dwf dwf

Found in path(s):
* /spring-context-support-4-3-19-release-sources-2-jar/org/springframework/mail/javamail/mime.types

1.546 commons-dbcp 1.2.2.osgi

1.546.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with

* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/PoolableConnectionFactory.java
*
 /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/datasources/InstanceKeyObjectFactory.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/datasources/CPDSConnectionFactory.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/datasources/KeyedCPDSConnectionFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/DelegatingPreparedStatement.java
*
 /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/datasources/SharedPoolDataSourceFactory.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/PoolingConnection.java

* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/jocl/JOCLContentHandler.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/datasources/SequencedHashMap.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/DriverManagerConnectionFactory.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/datasources/PerUserPoolDataSourceFactory.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/DataSourceConnectionFactory.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/ConnectionFactory.java
*
/com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/DelegatingCallableStatement.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/datasources/InstanceKeyDataSource.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/datasources/PooledConnectionAndInfo.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/cpdsadapter/PooledConnectionImpl.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/cpdsadapter/DriverAdapterCPDS.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/cpdsadapter/PoolablePreparedStatementStub.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/BasicDataSourceFactory.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/PoolablePreparedStatement.java
*
/com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/PoolingDataSource.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/datasources/UserPassKey.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/DbcpException.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/AbandonedConfig.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/DelegatingConnection.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/SQLNestedException.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/AbandonedTrace.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/PoolableConnection.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/PoolingDriver.java

*
/com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/cpdsadapter/ConnectionImpl.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/datasources/PerUserPoolDataSource.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/jocl/ConstructorUtil.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/AbandonedObjectPool.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/DelegatingResultSet.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/datasources/PoolKey.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/datasources/LRUMap.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/DriverConnectionFactory.java
*
/com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/BasicDataSource.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/DelegatingStatement.java
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/datasources/SharedPoolDataSource.java
No license file was found, but licenses were detected in source scan.

Licensed to the Apache Software Foundation (ASF) under one or more
contributor license agreements. See the NOTICE file distributed with
this work for additional information regarding copyright ownership.
The ASF licenses this file to You under the Apache License, Version 2.0
(the "License"); you may not use this file except in compliance with
the License. You may obtain a copy of the License at

    http://www.apache.org/licenses/LICENSE
2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Found in path(s):
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/overview.html
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/package.html
*
/com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/cpdsadapter/package.html

* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/jocl/package.html
* /com-springsource-org-apache-commons-dbcp-1-2-2-osgi-sources-jar/org/apache/commons/dbcp/datasources/package.html

1.547 commons-logging 1.1.1

1.547.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct

or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

// --
// NOTICE file corresponding to the section 4d of The Apache License,
// Version 2.0, in this case for Commons Logging
// --

Commons Logging
Copyright 2001-2007 The Apache Software Foundation

This product includes/uses software(s) developed by 'an unknown organization'
- Unnamed - avalon-framework:avalon-framework:jar:4.1.3
- Unnamed - log4j:log4j:jar:1.2.12
- Unnamed - logkit:logkit:jar:1.0.1

1.548 dom4j 1.6.1

1.548.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
File: ConcurrentReaderHashMap

Written by Doug Lea. Adapted and released, under explicit
permission, from JDK1.2 HashMap.java and Hashtable.java which
carries the following copyright:

* Copyright 1997 by Sun Microsystems, Inc.,
* 901 San Antonio Road, Palo Alto, California, 94303, U.S.A.
* All rights reserved.
*
* This software is the confidential and proprietary information
* of Sun Microsystems, Inc. ("Confidential Information"). You
* shall not disclose such Confidential Information and shall use
* it only in accordance with the terms of the license agreement
* you entered into with Sun.

History:
Date   Who   What
28oct1999 dl   Created
14dec1999 dl   jmm snapshot
19apr2000 dl   use barrierLock
12jan2001 dl   public release
17nov2001 dl   Minor tunings
20may2002 dl   BarrierLock can now be serialized.
09dec2002 dl   Fix interference checks.
*/

Found in path(s):
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/ConcurrentReaderHashMap.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2001-2005 (C) MetaStuff, Ltd. All Rights Reserved.
*
* This software is open source.
* See the bottom of this file for the licence.
*/
/*
* Redistribution and use of this software and associated documentation
* ("Software"), with or without modification, are permitted provided that the
* following conditions are met:
*
* 1. Redistributions of source code must retain copyright statements and
* notices. Redistributions must also contain a copy of this document.
*
* 2. Redistributions in binary form must reproduce the above copyright notice,
* this list of conditions and the following disclaimer in the documentation
* and/or other materials provided with the distribution.
*
* 3. The name "DOM4J" must not be used to endorse or promote products derived

* from this Software without prior written permission of MetaStuff, Ltd. For
* written permission, please contact dom4j-info@metastuff.com.
 *
* 4. Products derived from this Software may not be called "DOM4J" nor may
* "DOM4J" appear in their names without prior written permission of MetaStuff,
* Ltd. DOM4J is a registered trademark of MetaStuff, Ltd.
*
* 5. Due credit should be given to the DOM4J Project - http://www.dom4j.org
*
* THIS SOFTWARE IS PROVIDED BY METASTUFF, LTD. AND CONTRIBUTORS ``AS IS'' AND
* ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
* IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL METASTUFF, LTD. OR ITS CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
* CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
* ARISING IN
 ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
* POSSIBILITY OF SUCH DAMAGE.
*
* Copyright 2001-2005 (C) MetaStuff, Ltd. All Rights Reserved.
*/

Found in path(s):
* /dom4j-1-6-1-sources-4-jar/org/dom4j/InvalidXPathException.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/ProcessingInstruction.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/swing/LeafTreeNode.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/XPath.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/util/IndexedElement.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/DefaultAttribute.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/Branch.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/swing/XMLTableColumnDefinition.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/util/AttributeHelper.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/util/NodeComparator.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/SingleIterator.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/XPPReader.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/Node.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/rule/NullAction.java
*
 /dom4j-1-6-1-sources-4-jar/org/dom4j/DocumentHelper.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/DocumentSource.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/AbstractNode.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/dom/DOMDocument.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/STAXEventWriter.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/AbstractText.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/AbstractBranch.java

* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/SAXEventRecorder.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/dom/DOMNamespace.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/FlyweightEntity.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/util/NonLazyElement.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/NamespaceStack.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/BaseElement.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/dom/DOMElement.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/rule/pattern/NodeTypePattern.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/jaxb/JAXBRuntimeException.java
*
/dom4j-1-6-1-sources-4-jar/org/dom4j/xpp/ProxyXmlStartTag.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/bean/BeanAttribute.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/rule/Stylesheet.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/dom/DOMEntityReference.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/FlyweightAttribute.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/DefaultText.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/XMLResult.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/dom/DOMNodeHelper.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/XPathException.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/AbstractElement.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/Namespace.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/rule/Pattern.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/DOMWriter.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/IllegalAddException.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/dom/DOMCDATA.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/datatype/DatatypeDocumentFactory.java
*
/dom4j-1-6-1-sources-4-jar/org/dom4j/dtd/AttributeDecl.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/util/UserDataDocumentFactory.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/jaxb/JAXBWriter.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/Attribute.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/bean/BeanDocumentFactory.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/ElementHandler.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/FlyweightText.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/JAXPHelper.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/util/PerThreadSingleton.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/QNameCache.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/VisitorSupport.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/DocumentResult.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/Entity.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/NodeFilter.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/DefaultElement.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/rule/Rule.java
*
/dom4j-1-6-1-sources-4-jar/org/dom4j/CharacterData.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/PruningDispatchHandler.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/dom/DOMDocumentType.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/jaxb/JAXBSupport.java

* /dom4j-1-6-1-sources-4-jar/org/dom4j/DocumentFactory.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/ElementStack.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/xpath/DefaultXPath.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/XMLWriter.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/STAXEventReader.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/swing/XMLTableDefinition.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/SAXModifyContentHandler.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/SAXValidator.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/jaxb/JAXBReader.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/SAXModifyReader.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/FilterIterator.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/BackedList.java
*
 /dom4j-1-6-1-sources-4-jar/org/dom4j/DocumentException.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/Comment.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/dtd/ExternalEntityDecl.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/DOMReader.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/util/XMLErrorHandler.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/Text.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/datatype/InvalidSchemaException.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/swing/BranchTreeNode.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/dtd/ElementDecl.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/AbstractEntity.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/HTMLWriter.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/datatype/DatatypeAttribute.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/util/UserDataElement.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/DocumentType.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/SAXModifyElementHandler.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/DefaultNamespace.java
*
 /dom4j-1-6-1-sources-4-jar/org/dom4j/rule/RuleManager.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/rule/Action.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/ElementModifier.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/ElementNameIterator.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/QName.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/util/NonLazyDocumentFactory.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/dom/DOMText.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/DefaultDocument.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/dom/DOMAttributeNodeMap.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/util/IndexedDocumentFactory.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/datatype/DatatypeElementFactory.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/dom/DOMProcessingInstruction.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/DefaultDocumentType.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/dtd/InternalEntityDecl.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/DefaultProcessingInstruction.java
*
 /dom4j-1-6-1-sources-4-jar/org/dom4j/dom/DOMComment.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/util/UserDataAttribute.java

* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/FlyweightComment.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/FlyweightProcessingInstruction.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/PruningElementStack.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/NamespaceCache.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/datatype/SchemaParser.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/AbstractComment.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/AbstractDocumentType.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/SAXContentHandler.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/jaxb/JAXBModifier.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/SAXWriter.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/swing/DocumentTreeModel.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/util/SingletonStrategy.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/XPP3Reader.java
*
/dom4j-1-6-1-sources-4-jar/org/dom4j/io/OutputFormat.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/AbstractDocument.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/Visitor.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/DefaultComment.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/ElementQNameIterator.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/datatype/DatatypeElement.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/util/SimpleSingleton.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/swing/XMLTableModel.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/rule/RuleSet.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/Element.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/jaxb/JAXBObjectModifier.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/AbstractAttribute.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/DefaultCDATA.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/bean/BeanMetaData.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/DispatchHandler.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/ContentListFacade.java
*
/dom4j-1-6-1-sources-4-jar/org/dom4j/Document.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/rule/pattern/DefaultPattern.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/ElementPath.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/ElementIterator.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/jaxb/JAXBObjectHandler.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/datatype/NamedTypeResolver.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/xpath/DefaultNamespaceContext.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/dom/DOMDocumentFactory.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/SAXModifyException.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/AbstractProcessingInstruction.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/xpath/XPathPattern.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/CDATA.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/AbstractCharacterData.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/SAXReader.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/rule/Mode.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/FlyweightCDATA.java
*

/dom4j-1-6-1-sources-4-jar/org/dom4j/tree/DefaultEntity.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/dom/DOMAttribute.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/SAXHelper.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/util/ProxyDocumentFactory.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/bean/BeanAttributeList.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/bean/BeanElement.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/tree/AbstractCDATA.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/DocumentInputSource.java
* /dom4j-1-6-1-sources-4-jar/org/dom4j/io/SAXModifier.java

1.549 txw2 2.2.11

1.549.1 Available under license :

Found license 'General Public License 2.0' in 'Copyright (c) 2005-2010 Oracle and/or its affiliates. All rights reserved. The contents of this file are subject to the terms of either the GNU General Public License Version 2 only ("GPL") or the Common Development and Distribution License("CDDL") (collectively, the "License"). You may not use this file except in compliance with the License. You can Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2005-2010 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License // This class is in the Public Domain. NO WARRANTY! * Public Domain, and comes with NO WARRANTY.'
Found license 'General Public License 2.0' in '* Copyright (c) 2005-2010 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License // NO WARRANTY! This class is in the public domain.'
Found license 'Common Development and Distribution License (CDDL) 1.1' in 'Copyright (c) 2005-2010 Oracle and/or its affiliates. All rights reserved. The contents of this file are subject to the terms of either the GNU General Public License Version 2 only ("GPL") or the Common Development and Distribution License("CDDL") (collectively, the "License"). You may not use this file except in compliance with the License. You can Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the GPL Version 2 section of the License'
Found license 'General Public License 2.0' in '* Copyright (c) 2005-2010 Oracle and/or its affiliates. All rights reserved. * The contents of this file are subject to the terms of either the GNU * General Public License Version 2 only ("GPL") or the Common Development * and Distribution License("CDDL") (collectively, the "License"). You * may not use this file except in compliance with the License. You can * Oracle designates this particular file as subject to the "Classpath" * exception as provided by Oracle in the GPL Version 2 section of the License'

1.550 react 17.0.2

1.550.1 Available under license :

MIT License

Copyright (c) Microsoft Corporation.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF
CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE

1.551 y18n 3.2.2

1.551.1 Available under license :

Copyright (c) 2015, Contributors

Permission to use, copy, modify, and/or distribute this software for any purpose
with or without fee is hereby granted, provided that the above copyright notice
and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND
FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS
OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER
TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF
THIS SOFTWARE.
ISC

1.552 event-emitter 0.3.5

1.552.1 Available under license :

Copyright (C) 2012-2015 Mariusz Nowak (www.medikoo.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.553 acorn-walk 7.2.0

1.553.1 Available under license :

Copyright (C) 2012-2018 by various contributors (see AUTHORS)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT

OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.554 type-fest 0.8.1

1.554.1 Available under license :

UNRECOGNIZED LICENSE; MD5 sum: 6d4049152bc0ad3ee4db0c73a0a659e4
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Creative Commons Legal Code

CC0 1.0 Universal

CREATIVE COMMONS CORPORATION IS NOT A LAW FIRM AND DOES NOT PROVIDE LEGAL SERVICES. DISTRIBUTION OF THIS DOCUMENT DOES NOT CREATE AN ATTORNEY-CLIENT RELATIONSHIP. CREATIVE COMMONS PROVIDES THIS INFORMATION ON AN "AS-IS" BASIS. CREATIVE COMMONS MAKES NO WARRANTIES REGARDING THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER, AND DISCLAIMS LIABILITY FOR DAMAGES RESULTING FROM THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER.

Statement of Purpose

The laws of most jurisdictions throughout the world automatically confer exclusive Copyright and Related Rights (defined below) upon the creator and subsequent owner(s) (each and all, an "owner") of an original work of authorship and/or a database (each, a "Work").

Certain owners wish to permanently relinquish those rights to a Work for the purpose of contributing to a commons of creative, cultural and scientific works ("Commons")
that the public can reliably and without fear
of later claims of infringement build upon, modify, incorporate in other works, reuse and redistribute as freely as possible in any form whatsoever and for any purposes, including without limitation commercial purposes. These owners may contribute to the Commons to promote the ideal of a free culture and the further production of creative, cultural and scientific works, or to gain reputation or greater distribution for their Work in part through the use and efforts of others.

For these and/or other purposes and motivations, and without any expectation of additional consideration or compensation, the person associating CC0 with a Work (the "Affirmer"), to the extent that he or she is an owner of Copyright and Related Rights in the Work, voluntarily elects to apply CC0 to the Work and publicly distribute the Work under its terms, with knowledge of his or her Copyright and Related Rights in the Work and the meaning and intended legal
effect of CC0 on those rights.

1. Copyright and Related Rights. A Work made available under CC0 may be protected by copyright and related or neighboring rights ("Copyright and Related Rights"). Copyright and Related Rights include, but are not limited to, the following:

i. the right to reproduce, adapt, distribute, perform, display, communicate, and translate a Work;
ii. moral rights retained by the original author(s) and/or performer(s);
iii. publicity and privacy rights pertaining to a person's image or likeness depicted in a Work;
iv. rights protecting against unfair competition in regards to a Work, subject to the limitations in paragraph 4(a), below;
v. rights protecting the extraction, dissemination, use and reuse of data in a Work;
vi. database rights (such as those arising under Directive 96/9/EC of the European Parliament and of the Council of 11 March 1996 on the legal protection of databases, and under any national implementation

thereof, including any amended or successor version of such directive); and
vii. other similar, equivalent or corresponding rights throughout the world based on applicable law or treaty, and any national implementations thereof.

2. Waiver. To the greatest extent permitted by, but not in contravention of, applicable law, Affirmer hereby overtly, fully, permanently, irrevocably and unconditionally waives, abandons, and surrenders all of

Affirmer's Copyright and Related Rights and associated claims and causes of action, whether now known or unknown (including existing as well as future claims and causes of action), in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "Waiver"). Affirmer makes the Waiver for the benefit of each member of the public at large and to the detriment of Affirmer's heirs and successors, fully intending that such Waiver shall not be subject to revocation, rescission, cancellation, termination, or any other legal or equitable action to disrupt the quiet enjoyment of the Work by the public as contemplated by Affirmer's express Statement of Purpose.

3. Public License Fallback. Should any part of the Waiver for any reason be judged legally invalid or ineffective under applicable law, then the Waiver shall be preserved to the maximum extent permitted taking into account Affirmer's express Statement of Purpose. In addition, to the extent the Waiver is so judged Affirmer hereby grants to each affected person a royalty-free, non transferable, non sublicensable, non exclusive, irrevocable and unconditional license to exercise Affirmer's Copyright and Related Rights in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "License"). The License shall be deemed effective as of the date CC0 was applied by Affirmer to the Work. Should any part of the License for any reason be judged legally invalid or ineffective under applicable law, such partial invalidity or ineffectiveness shall not invalidate the remainder of the License, and in such case Affirmer hereby affirms that he or she will not (i) exercise any of his or her remaining Copyright and Related Rights in the Work or (ii) assert any associated claims and causes of action with respect to the Work, in either case contrary to Affirmer's express Statement of Purpose.

4. Limitations and Disclaimers.

a. No trademark or patent rights held by Affirmer are waived, abandoned, surrendered, licensed or otherwise affected by this document.
b. Affirmer offers the Work as-is and makes no representations or warranties of any kind concerning the Work, express, implied, statutory or otherwise, including without limitation warranties of title, merchantability, fitness for a particular purpose, non infringement, or the absence of latent or other defects, accuracy, or

the present or absence of errors, whether or not discoverable, all to the greatest extent permissible under applicable law.

c. Affirmer disclaims responsibility for clearing rights of other persons that may apply to the Work or any use thereof, including without limitation any person's Copyright and Related Rights in the Work. Further, Affirmer disclaims responsibility for obtaining any necessary consents, permissions or other rights required for any use of the Work.

d. Affirmer understands and acknowledges that Creative Commons is not a party to this document and has no duty or obligation with respect to this CC0 or use of the Work.

1.555 make-dir 3.1.0

1.555.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.556 fill-range 7.0.1

1.556.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-present, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal

in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.557 es6-iterator 2.0.3

1.557.1 Available under license :

The MIT License (MIT)

Copyright (C) 2013-2017 Mariusz Nowak (www.medikoo.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.558 camelcase 5.3.1

1.558.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.559 is-number 7.0.0

1.559.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-present, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.560 is-ci 2.0.0

1.560.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016-2018 Thomas Watson Steen

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.561 slash 2.0.0

1.561.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the

Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.562 dot-prop 4.2.1

1.562.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.563 aspectj-weaver 1.9.6

1.563.1 Available under license :

Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2005 Contributors. All rights reserved. * This program and the accompanying materials are made available * under the terms of the Eclipse Public License v1.0'
Found license 'Eclipse Public License 1.0' in '* Copyright (c) 2006 Contributors. All rights reserved. * This program and the accompanying materials are made available * under the terms of the Eclipse Public License v1.0'
Found license 'Eclipse Public License 1.0' in '* All rights reserved. * This program and the accompanying materials are made available * under the terms of the Eclipse Public License v1.0'

Found license 'Eclipse Public License 1.0' in '* All rights reserved. This program and the accompanying materials * are made available under the terms of the Eclipse Public License v1.0'

1.564 eventemitter3 4.0.7

1.564.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Arnout Kazemier

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.565 escalade 3.1.1

1.565.1 Available under license :

MIT License

Copyright (c) Luke Edwards <luke.edwards05@gmail.com> (lukeed.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED,

INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.566 enhanced-resolve 4.5.0

1.566.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.567 eslint-visitor-keys 1.3.0

1.567.1 Available under license :

Apache License 2.0

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent

to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works

that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS,

WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "{}" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright contributors

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.

You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.568 es6-weak-map 2.0.3

1.568.1 Available under license :

ISC
ISC License

Copyright (c) 2013-2018, Mariusz Nowak, @medikoo, medikoo.com

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

1.569 clone-deep 4.0.1

1.569.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2018, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in

all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.570 d 1.0.1

1.570.1 Available under license :

ISC
ISC License

Copyright (c) 2013-2019, Mariusz Nowak, @medikoo, medikoo.com

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.571 figgy-pudding 3.5.2

1.571.1 Available under license :

ISC License

Copyright (c) npm, Inc.

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE COPYRIGHT HOLDER DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE COPYRIGHT HOLDER BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR

CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS
OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE
USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.572 sass-loader 8.0.2

1.572.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.573 shallow-clone 3.0.1

1.573.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015-present, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.574 es6-symbol 3.1.3

1.574.1 Available under license :

ISC
ISC License

Copyright (c) 2013-2019, Mariusz Nowak, @medikoo, medikoo.com

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.575 filter-obj 1.1.0

1.575.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.576 jta 1.1.0

1.576.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this

License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided

that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Meecrowave :: JTA
Copyright 2017 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.577 commander 4.1.1

1.577.1 Available under license :

No license file was found, but licenses were detected in source scan.

= Commander

The complete solution for Ruby command-line executables.
Commander bridges the gap between other terminal related libraries
you know and love (OptionParser, HighLine), while providing many new
features, and an elegant API.

== Features

* Easier than baking cookies
* Parses options using OptionParser
* Auto-populates struct with options (no more { |v| options[:recursive] = v })
* Auto-generates help documentation via pluggable help formatters
* Optional default command when none is present
* Global / Command level options
* Packaged with two help formatters (Terminal, TerminalCompact)
* Imports the highline gem for interacting with the terminal
* Adds additional user interaction functionality
* Highly customizable progress bar with intuitive, simple usage
* Multi-word command name support such as 'drupal module install MOD', rather than 'drupal module_install MOD'
* Sexy paging for long bodies of text
*
Support for MacOS text-to-speech
* Command aliasing (very powerful, as both switches and arguments can be used)
* Growl notification support for MacOS
* Use the 'commander' executable to initialize a commander driven program

== Installation

```
$ gem install commander
```

== Quick Start

To generate a quick template for a commander app, run:

```
$ commander init yourfile.rb
```

== Example

For more option examples view the Commander::Command#option method. Also
an important feature to note is that action may be a class to instantiate,
as well as an object, specifying a method to call, so view the RDoc for more information.

```
require 'rubygems'
```

```
require 'commander/import'

# :name is optional, otherwise uses the basename of this executable
program :name, 'Foo Bar'
program :version, '1.0.0'
program :description, 'Stupid command that prints foo or bar.'

command :foo do |c|
  c.syntax = 'foobar foo'
  c.description = 'Displays foo'
  c.action do |args, options|

   say 'foo'
  end
end

command :bar do |c|
  c.syntax = 'foobar bar [options]'
  c.description = 'Display bar with optional prefix and suffix'
  c.option '--prefix STRING', String, 'Adds a prefix to bar'
  c.option '--suffix STRING', String, 'Adds a suffix to bar'
  c.action do |args, options|
    options.default :prefix => '(', :suffix => ')'
    say "#{options.prefix}bar#{options.suffix}"
  end
end

$ foobar bar
# => (bar)

$ foobar bar --suffix '{' --prefix '}'
# => {bar}
```

== HighLine

As mentioned above the highline gem is imported into 'global scope', below
are some quick examples for how to utilize highline in your command(s):

```
# Ask for password masked with '*' character
ask("Password:  ") { |q| q.echo = "*" }

# Ask for password
ask("Password:  ") { |q| q.echo = false }

# Ask if the user agrees (yes or no)
agree("Do something?")

# Asks on a single line (note the space after ':')
```

```
 ask("Name: ")


# Asks with new line after "Description:"
 ask("Description:")

 # Calls Date#parse to parse the date string passed
 ask("Birthday? ", Date)

 # Ensures Integer is within the range specified
 ask("Age? ", Integer) { |q| q.in = 0..105 }

 # Asks for a list of strings, converts to array
 ask("Fav colors?", Array)
```

== HighLine & Interaction Additions

In addition to highline's fantastic choice of methods, commander adds the
following methods to simplify common tasks:

```
 # Ask for password
 password

 # Ask for password with specific message and mask character
 password "Enter your password please:", '-'

 # Ask for CLASS, which may be any valid class responding to #parse. Date, Time, Array, etc
 names = ask_for_array 'Names: '
 bday = ask_for_date 'Birthday?: '

 # Simple progress bar (Commander::UI::ProgressBar)
 uris = %w[
   http://vision-media.ca
   http://google.com
   http://yahoo.com
   ]
 progress uris do |uri|
   res = open uri
    # Do something with response
 end

# 'Log' action to stdout
log "create", "path/to/file.rb"

# Enable paging of output after this point
enable_paging

# Ask editor for input (EDITOR environment variable or whichever is available: TextMate, vim, vi, emacs, nano,
```

```
pico)
 ask_editor

 # Ask editor, supplying initial text
 ask_editor 'previous data to update'

 # Ask editor, preferring a specific editor
 ask_editor 'previous data', 'vim'

 # Choose from an array of elements
 choice = choose("Favorite language?", :ruby, :perl, :js)

 # Alter IO for the duration of the block
 io new_input, new_output do
   new_input_contents = $stdin.read
   puts new_input_contents # outputs to new_output stream
 end
 # $stdin / $stdout reset back to original streams

 # Speech synthesis
 speak 'What is your favorite food? '
 food = ask 'favorite food?: '
 speak "Wow, I like #{food} too. We have so much in common."

 # Execute arbitrary applescript
 applescript 'foo'


 # Converse with speech recognition server
 case converse 'What is the best food?', :cookies => 'Cookies', :unknown => 'Nothing'
 when :cookies
   speak 'o.m.g. you are awesome!'
 else
   case converse 'That is lame, shall I convince you cookies are the best?', :yes => 'Ok', :no => 'No', :maybe =>
'Maybe another time'
   when :yes
     speak 'Well you see, cookies are just fantastic, they melt in your mouth.'
   else
     speak 'Ok then, bye.'
   end
 end
```

== Growl Notifications

Commander provides methods for displaying Growl notifications. To use these
methods you need to install http://github.com/visionmedia/growl which utilizes
the growlnotify[http://growl.info/extras.php#growlnotify] executable. Note that
growl is auto-imported by Commander when available, no need to require.

```
# Display a generic Growl notification
notify 'Something happened'

# Display an 'info' status notification
notify_info 'You have #{emails.length} new email(s)'

# Display an 'ok' status
notification
notify_ok 'Gems updated'

# Display a 'warning' status notification
notify_warning '1 gem failed installation'

# Display an 'error' status notification
notify_error "Gem #{name} failed"
```

growlnotify can also be installed via homebrew[http://mxcl.github.com/homebrew/]:

```
$ brew install growlnotify
```

== Commander Goodies

=== Option Defaults

The options struct passed to #action provides a #default method, allowing you
to set defaults in a clean manner for options which have not been set.

```
command :foo do |c|
  c.option '--interval SECONDS', Integer, 'Interval in seconds'
  c.option '--timeout SECONDS', Integer, 'Timeout in seconds'
  c.action do |args, options|
    options.default \
      :interval => 2,
      :timeout  => 60
  end
end
```

=== Command Aliasing

Aliases can be created using the #alias_command method like below:

```
command :'install gem' do |c|
  c.action { puts 'foo' }
end
alias_command :'gem install', :'install gem'
```

Or more

complicated aliases can be made, passing any arguments
as if it was invoked via the command line:

```
command :'install gem' do |c|
  c.syntax = 'install gem <name> [options]'
  c.option '--dest DIR', String, 'Destination directory'
  c.action { |args, options| puts "installing #{args.first} to #{options.dest}" }
end
alias_command :update, :'install gem', 'rubygems', '--dest', 'some_path'

$ foo update
# => installing rubygems to some_path
```

=== Command Defaults

Although working with a command executable framework provides many
benefits over a single command implementation, sometimes you still
want the ability to create a terse syntax for your command. With that
in mind we may use #default_command to help with this. Considering
our previous :'install gem' example:

```
default_command :update

$ foo
# => installing rubygems to some_path
```

Keeping in mind that commander searches for the longest possible match
when considering a command, so if you were to pass arguments
to foo
like below, expecting them to be passed to :update, this would be incorrect,
and would end up calling :'install gem', so be careful that the users do
not need to use command names within the arguments.

```
$ foo install gem
# => installing  to
```

=== Additional Global Help

Arbitrary help can be added using the following #program symbol:

```
program :help, 'Author', 'TJ Holowaychuk <tj@vision-media.ca>'
```

Which will output the rest of the help doc, along with:

```
AUTHOR:

  TJ Holowaychuk <tj@vision-media.ca>
```

=== Global Options

Although most switches will be at the command level, several are available
by default at the global level, such as --version, and --help. Using #global_option
you can add additional global options:

```
global_option('-c', '--config FILE', 'Load config data for your commands to use') { |file| ... }
```

This method accepts the same syntax as Commander::Command#option so check it out for documentation.

All global options regardless of providing a block are accessable
at the command level. This
means that instead of the following:

```
global_option('--verbose') { $verbose = true }
...
c.action do |args, options|
  say 'foo' if $verbose
...
```

You may:

```
global_option '--verbose'
...
c.action do |args, options|
  say 'foo' if options.verbose
...
```

=== Formatters

Two core formatters are currently available, the default Terminal formatter as well
as TerminalCompact. To utilize a different formatter simply use :help_formatter like below:

```
program :help_formatter, Commander::HelpFormatter::TerminalCompact
```

Or utilize the help formatter aliases:

```
program :help_formatter, :compact
```

This abstraction could be utilized to generate HTML documentation for your executable.

== Tips

When adding a global or command option, OptionParser implicitly adds a small
switch even when not explicitly created, for example -c will be the same as --config
in both examples, however '-c' will only appear in the documentation when explicitly
assigning

it.

```
global_option '-c', '--config FILE'
global_option '--config FILE'
```

== ASCII Tables

For feature rich ASCII tables for your terminal app check out visionmedia's terminal-table gem at http://github.com/visionmedia/terminal-table

```
+----------+-------+----+--------+----------------------+
| Terminal | Table | Is | Wicked | Awesome              |
+----------+-------+----+--------+----------------------+
|          |       |    |        | get it while its hot! |
+----------+-------+----+--------+----------------------+
```

== Running Specifications

```
$ rake spec
```

OR

```
$ spec --color spec
```

== Contrib

Feel free to fork and request a pull, or submit a ticket
http://github.com/visionmedia/commander/issues

== License

(The MIT License)

Copyright (c) 2008-2009 TJ Holowaychuk <tj@vision-media.ca>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software
without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Found in path(s):
* /commander-4-1-1-gem/data-tar-gz/README.rdoc
No license file was found, but licenses were detected in source scan.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

Found in path(s):
* /commander-4-1-1-gem/data-tar-gz/lib/commander.rb

1.578 semver-diff 3.1.1

1.578.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.579 is-installed-globally 0.3.2

1.579.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.580 is-npm 4.0.0

1.580.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,

ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.581 is-path-inside 3.0.3

1.581.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.582 pbkdf2 3.1.2

1.582.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Daniel Cousens

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.583 pupa 2.1.1

1.583.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.584 is-yarn-global 0.3.0

1.584.1 Available under license :

MIT License

Copyright (c) 2018 LitoMore

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.585 update-notifier 4.1.3

1.585.1 Available under license :

BSD-2-Clause
Copyright Google

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.586 latest-version 5.1.0

1.586.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.587 write-file-atomic 3.0.3

1.587.1 Available under license :

ISC
Copyright (c) 2015, Rebecca Turner

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.588 has-yarn 2.1.0

1.588.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit

persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.589 escape-goat 2.1.1

1.589.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.590 glob-parent 5.1.2

1.590.1 Available under license :

ISC
The ISC License

Copyright (c) 2015, 2019 Elan Shanker

Permission to use, copy, modify, and/or distribute this software for any

purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.591 global-dirs 2.1.0

1.591.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (https://sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.592 hoopy 0.1.4

1.592.1 Available under license :

Copyright 2017 Phil Booth

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.593 duplexer 0.1.2

1.593.1 Available under license :

MIT
Copyright (c) 2012 Raynos.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.594 readdirp 3.2.0

1.594.1 Available under license :

MIT License

Copyright (c) 2012-2019 Thorsten Lorenz, Paul Miller (https://paulmillr.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.595 chokidar 3.3.0

1.595.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2012-2019 Paul Miller (https://paulmillr.com), Elan Shanker

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the Software), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED AS IS, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.596 lz4 1.2.0

1.596.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4UnsafeUtils.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/xxhash/XXHashJNI.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4BlockOutputStream.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4Factory.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4Constants.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4HCJNICompressor.java
*
 /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4Exception.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4FastDecompressor.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/xxhash/XXHashConstants.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/xxhash/StreamingXXHash32JNI.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/util/Native.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/xxhash/AbstractStreamingXXHash32Java.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4JNICompressor.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/util/UnsafeUtils.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/xxhash/XXHashFactory.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/util/Utils.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4BlockInputStream.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/xxhash/XXHash32.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/xxhash/XXHash32JNI.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4Decompressor.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/xxhash/StreamingXXHash32.java
*
 /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4SafeDecompressor.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4JNI.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4Utils.java

* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4JNISafeDecompressor.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4Compressor.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4UnknownSizeDecompressor.java
* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/LZ4JNIFastDecompressor.java
No license file was found, but licenses were detected in source scan.

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE
2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Found in path(s):
* /lz4-1-2-0-sources-1-jar/overview.html
* /lz4-1-2-0-sources-1-jar/net/jpountz/lz4/package.html
* /lz4-1-2-0-sources-1-jar/net/jpountz/xxhash/package.html
* /lz4-1-2-0-sources-1-jar/net/jpountz/util/package.html

1.597 normalize-url 4.5.1

1.597.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,

ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.598 log4j-rolling-appender 20131024-2017

1.598.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object

form, that is based on (or derived from) the
Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication
on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant
of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses

granted to You under this License for that Work shall terminate as
of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,

any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names
of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole
responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright 1999-2005 The Apache Software Foundation

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

1.599 forwarded 0.2.0

1.599.1 Available under license :

(The MIT License)

Copyright (c) 2014-2017 Douglas Christopher Wilson

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the 'Software'), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF

MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.600 glob-stream 6.1.0

1.600.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015-2017 Blaine Bublitz <blaine.bublitz@gmail.com>, Eric Schoffstall <yo@contra.io> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.601 unique-stream 2.3.1

1.601.1 Available under license :

Copyright 2014 Eugene Ware

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to

permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.602 is-negated-glob 1.0.0

1.602.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.603 to-absolute-glob 2.0.2

1.603.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-2016, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.604 through2-filter 3.0.0

1.604.1 Available under license :

MIT
(The MIT License)

Copyright (c) Bryce B. Baril <bryce@ravenwall.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.605 ordered-read-streams 1.0.1

1.605.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Artem Medeusheyev

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.606 hosted-git-info 2.8.9

1.606.1 Available under license :

ISC
Copyright (c) 2015, Rebecca Turner

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.607 ws 6.2.2

1.607.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2017-2019 Kamil Myliwiec <http://kamilmysliwiec.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.608 postcss-load-config 2.1.2

1.608.1 Available under license :

MIT
License (MIT)

Copyright (c) Michael Ciniawsky <michael.ciniawsky@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.609 internmap 1.0.1

1.609.1 Available under license :

ISC
Copyright 2021 Mike Bostock

Permission to use, copy, modify, and/or distribute this software for any purpose
with or without fee is hereby granted, provided that the above copyright notice
and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS
OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.610 accessors-smart 1.2

1.610.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2011 JSON-SMART authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /accessors-smart-1-2-sources-5-jar/net/minidev/asm/BeansAccess.java
* /accessors-smart-1-2-sources-5-jar/net/minidev/asm/DynamicClassLoader.java
* /accessors-smart-1-2-sources-5-jar/net/minidev/asm/Accessor.java
* /accessors-smart-1-2-sources-5-jar/net/minidev/asm/ASMUtil.java

1.611 xsdlib 2013.6.1

1.611.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* The Apache Software License, Version 1.1
*
*
* Copyright (c) 1999-2013 The Apache Software Foundation. All rights
* reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in
*   the documentation and/or other materials provided with the
*   distribution.
*
* 3. The end-user documentation included with the redistribution,
*   if any, must include the following acknowledgment:
*   "This product includes software developed by the
*   Apache Software Foundation (http://www.apache.org/)."
*   Alternately,
 this acknowledgment may appear in the software itself,
*   if and wherever such third-party acknowledgments normally appear.
*
* 4. The names "Xerces" and "Apache Software Foundation" must
*   not be used to endorse or promote products derived from this
*   software without prior written permission. For written
*   permission, please contact apache@apache.org.
*

* 5. Products derived from this software may not be called "Apache",
*   nor may "Apache" appear in their name, without prior written
*   permission of the Apache Software Foundation.
*
* THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESSED OR IMPLIED
* WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
* OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
* DISCLAIMED. IN NO EVENT SHALL THE APACHE SOFTWARE FOUNDATION OR
* ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
* SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
* LIMITED TO, PROCUREMENT
 OF SUBSTITUTE GOODS OR SERVICES; LOSS OF
* USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
* ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
* OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT
* OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation and was
* originally based on software copyright (c) 1999, International
* Business Machines, Inc., http://www.apache.org. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*/

Found in path(s):
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/regexp/RangeToken.java
No license file was found, but licenses were detected in source scan.

/*
* The Apache Software License, Version 1.1
*
*
* Copyright (c) 1999-2003 The Apache Software Foundation. All rights
* reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in
*   the documentation and/or other materials provided with the

```
*    distribution.
*
* 3. The end-user documentation included with the redistribution,
*    if any, must include the following acknowledgment:
*       "This product includes software developed by the
*        Apache Software Foundation (http://www.apache.org/)."
*    Alternately,
 this acknowledgment may appear in the software itself,
*    if and wherever such third-party acknowledgments normally appear.
*
* 4. The names "Xerces" and "Apache Software Foundation" must
*    not be used to endorse or promote products derived from this
*    software without prior written permission. For written
*    permission, please contact apache@apache.org.
*
* 5. Products derived from this software may not be called "Apache",
*    nor may "Apache" appear in their name, without prior written
*    permission of the Apache Software Foundation.
*
* THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESSED OR IMPLIED
* WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
* OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
* DISCLAIMED.  IN NO EVENT SHALL THE APACHE SOFTWARE FOUNDATION OR
* ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
* SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
* LIMITED TO, PROCUREMENT
 OF SUBSTITUTE GOODS OR SERVICES; LOSS OF
* USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
* ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
* OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT
* OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation and was
* originally based on software copyright (c) 1999, International
* Business Machines, Inc., http://www.apache.org.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*/

Found in path(s):
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/regexp/ParserForXMLSchema.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/regexp/RegexParser.java
No license file was found, but licenses were detected in source scan.

/*
```

* The Apache Software License, Version 1.1
*
*
* Copyright (c) 1999-2002 The Apache Software Foundation. All rights
* reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in
*   the documentation and/or other materials provided with the
*   distribution.
*
* 3. The end-user documentation included with the redistribution,
*   if any, must include the following acknowledgment:
*   "This product includes software developed by the
*   Apache Software Foundation (http://www.apache.org/)."
*   Alternately,
 this acknowledgment may appear in the software itself,
*   if and wherever such third-party acknowledgments normally appear.
*
* 4. The names "Xerces" and "Apache Software Foundation" must
*   not be used to endorse or promote products derived from this
*   software without prior written permission. For written
*   permission, please contact apache@apache.org.
*
* 5. Products derived from this software may not be called "Apache",
*   nor may "Apache" appear in their name, without prior written
*   permission of the Apache Software Foundation.
*
* THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESSED OR IMPLIED
* WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
* OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
* DISCLAIMED. IN NO EVENT SHALL THE APACHE SOFTWARE FOUNDATION OR
* ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
* SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
* LIMITED TO, PROCUREMENT
 OF SUBSTITUTE GOODS OR SERVICES; LOSS OF
* USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
* ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
* OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT
* OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.

* ==
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation and was
* originally based on software copyright (c) 1999, International
* Business Machines, Inc., http://www.apache.org. For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*/

Found in path(s):
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/regexp/Token.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/regexp/ParseException.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/regexp/RegularExpression.java
*
 /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/regexp/Match.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/regexp/Op.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/regexp/REUtil.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/regexp/BMPattern.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2001-2013 Oracle and/or its affiliates. All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions are
* met:
*
* - Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
* - Redistribution in binary form must reproduct the above copyright
*   notice, this list of conditions and the following disclaimer in the
*   documentation and/or other materials provided with the distribution.
*
* Neither the name of Sun Microsystems, Inc. or the names of
* contributors may be used to endorse or promote products derived from
* this software without specific prior written permission.
*
* This software is provided "AS IS," without
 a warranty of any kind. ALL
* EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES,
* INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A
* PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE HEREBY EXCLUDED. SUN AND
* ITS LICENSORS SHALL NOT BE LIABLE FOR ANY DAMAGES OR LIABILITIES
* SUFFERED BY LICENSEE AS A RESULT OF OR RELATING TO USE, MODIFICATION

* OR DISTRIBUTION OF THE SOFTWARE OR ITS DERIVATIVES. IN NO EVENT WILL
* SUN OR ITS LICENSORS BE LIABLE FOR ANY LOST REVENUE, PROFIT OR DATA,
* OR FOR DIRECT, INDIRECT, SPECIAL, CONSEQUENTIAL, INCIDENTAL OR
* PUNITIVE DAMAGES, HOWEVER CAUSED AND REGARDLESS OF THE THEORY OF
* LIABILITY, ARISING OUT OF THE USE OF OR INABILITY TO USE SOFTWARE,
* EVEN IF SUN HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.
*/

Found in path(s):
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/regexp/InternalImpl.java
No license file was found, but licenses were detected in source scan.

Copyright (c) 2001-2013 Oracle and/or its affiliates. All rights reserved.
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
- Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
- Neither the name of Oracle nor the names of its
from this software without specific prior written permission.

Found in path(s):
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/Messages.properties
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/Messages_ja.properties
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2001-2013 Oracle and/or its affiliates. All rights reserved.
*
* Redistribution and use in source and binary forms, with or without
* modification, are permitted provided that the following conditions
* are met:
*
* - Redistributions of source code must retain the above copyright
* notice, this list of conditions and the following disclaimer.
*
* - Redistributions in binary form must reproduce the above copyright
* notice, this list of conditions and the following disclaimer in the
* documentation and/or other materials provided with the distribution.
*
* - Neither the name of Oracle nor the names of its
* contributors may be used to endorse or promote products derived
* from this software without specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS

* IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING,
BUT NOT LIMITED TO,
* THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
* PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
* CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
* EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
* PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
* PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
* LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
* NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
* SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/ShortType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/datetime/DateTimeFactory.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/datetime/BigTimeDurationValueType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/NonPositiveIntegerType.java
*
/xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/MinInclusiveFacet.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/SimpleURType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/XSDatatype.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/WhiteSpaceFacet.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/SerializationContext.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/XSDatatypeImpl.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/DataTypeWithLexicalConstraintFacet.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/UnsignedLongType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/Base64BinaryType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/IDType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/GYearMonthType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/IntegerType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/GDayType.java
*
/xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/ListValueType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/DurationType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/ConcreteType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/TokenType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/DataTypeWithFacet.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/datetime/AbstractCalendarParser.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/NmtokenType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/datetime/CalendarFormatter.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/Proxy.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/datetime/CalendarParser.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/datetime/TimeZone.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/TotalDigitsFacet.java
*
/xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/regex/RegExp.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/FinalComponent.java

* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/GMonthType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/GMonthDayType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/PositiveIntegerType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/DateTimeBaseType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/UnsignedByteType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/BooleanType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/LengthFacet.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/IntType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/GYearType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/LongType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/datetime/IDateTimeValueType.java
*
/xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/EnumerationFacet.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/datetime/AbstractCalendarFormatter.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/DatabindableDatatype.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/DateTimeType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/UnicodeUtil.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/regex/XercesImpl.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/BinaryBaseType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/BuiltinAtomicType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/AnyURIType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/datetime/PreciseCalendarFormatter.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/NcnameType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/UnsignedShortType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/NegativeIntegerType.java
*
/xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/MaxExclusiveFacet.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/Discrete.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/IntegerDerivedType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/regex/JDKImpl.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/UnionType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/Comparator.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/datetime/PreciseCalendarParser.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/NormalizedStringType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/QnameValueType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/xml/util/XmlChars.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/datetime/BigDateTimeValueType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/XmlNames.java
*
/xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/HexBinaryType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/PatternFacet.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/DataTypeWithValueConstraintFacet.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/ngimpl/DatatypeBuilderImpl.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/UnsignedIntType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/TypeIncubator.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/FloatingNumberType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/IntegerValueType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/datetime/ITimeDurationValueType.java

* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/RangeFacet.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/NameType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/ListType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/TimeType.java
*
 /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/MinExclusiveFacet.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/StringType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/ErrorType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/NonNegativeIntegerType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/ErrorDatatypeLibrary.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/FloatType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/WhiteSpaceProcessor.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/DatatypeFactory.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/MinLengthFacet.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/FractionDigitsFacet.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/IDREFType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/regex/RegExpFactory.java
*
 /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/QnameType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/MaxLengthFacet.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/BinaryValueType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/ngimpl/DataTypeLibraryImpl.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/datetime/Util.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/NumberType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/DateType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/DoubleType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/LanguageType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/MaxInclusiveFacet.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/ByteType.java
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/EntityType.java
No license file was found, but licenses were detected in source scan.

2013 Oracle and/or its affiliates. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
Neither the name of Oracle nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO,

THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Found in path(s):
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/xsd/package.html
No license file was found, but licenses were detected in source scan.

Copyright (c) 2001-2013 Oracle and/or its affiliates. All rights reserved.
modification, are permitted provided that the following conditions are
- Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
this software without specific prior written permission.

Found in path(s):
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/regexp/message_fr.properties
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/regexp/message_ja.properties
* /xsdlib-2013-6-1-sources-2-jar/com/sun/msv/datatype/regexp/message.properties

1.612 cglib 3.0

1.612.1 Available under license :

```
 ========================================================================
 ==  NOTICE file corresponding to the section 4 d of                   ==
 ==  the Apache License, Version 2.0,                                  ==
 ==  in this case for the Apache Ant distribution.                     ==
 ========================================================================
```

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

This product includes also software developed by :
- the W3C consortium (http://www.w3c.org) ,
- the SAX project (http://www.saxproject.org)

Please read the different LICENSE files present in the root directory of
this distribution.

ASM: a very small and fast Java bytecode manipulation framework
Copyright (c) 2000,2002,2003 INRIA, France Telecom
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
3. Neither the name of the copyright holders nor the names of its
  contributors may be used to endorse or promote products derived from
  this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY
 AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
THE POSSIBILITY OF SUCH DAMAGE.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the

outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of

this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed

as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,

indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

```
/*
*                              Apache License
*                        Version 2.0, January 2004
```

```
*                 http://www.apache.org/licenses/
*
*  TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION
*
*  1. Definitions.
*
*     "License" shall mean the terms and conditions for use, reproduction,
*     and distribution as defined by Sections 1 through 9 of this document.
*
*     "Licensor" shall mean the copyright owner or entity authorized by
*     the copyright owner that is granting the License.
*
*     "Legal Entity" shall mean the union of the acting entity and all
*     other entities that control, are controlled by, or are under common
*     control with that entity. For the purposes of this definition,
*     "control" means (i) the power, direct or indirect, to cause the
*     direction or management of such entity, whether by contract or
*     otherwise, or (ii) ownership of fifty percent (50%) or more of the
*
 outstanding shares, or (iii) beneficial ownership of such entity.
*
*     "You" (or "Your") shall mean an individual or Legal Entity
*     exercising permissions granted by this License.
*
*     "Source" form shall mean the preferred form for making modifications,
*     including but not limited to software source code, documentation
*     source, and configuration files.
*
*     "Object" form shall mean any form resulting from mechanical
*     transformation or translation of a Source form, including but
*     not limited to compiled object code, generated documentation,
*     and conversions to other media types.
*
*     "Work" shall mean the work of authorship, whether in Source or
*     Object form, made available under the License, as indicated by a
*     copyright notice that is included in or attached to the work
*     (an example is provided in the Appendix below).
*
*     "Derivative Works" shall mean any work, whether in Source or Object
*
    form, that is based on (or derived from) the Work and for which the
*     editorial revisions, annotations, elaborations, or other modifications
*     represent, as a whole, an original work of authorship. For the purposes
*     of this License, Derivative Works shall not include works that remain
*     separable from, or merely link (or bind by name) to the interfaces of,
*     the Work and Derivative Works thereof.
*
*     "Contribution" shall mean any work of authorship, including
```

* the original version of the Work and any modifications or additions
* to that Work or Derivative Works thereof, that is intentionally
* submitted to Licensor for inclusion in the Work by the copyright owner
* or by an individual or Legal Entity authorized to submit on behalf of
* the copyright owner. For the purposes of this definition, "submitted"
* means any form of electronic, verbal, or written communication sent
* to the Licensor or its representatives,
including but not limited to
* communication on electronic mailing lists, source code control systems,
* and issue tracking systems that are managed by, or on behalf of, the
* Licensor for the purpose of discussing and improving the Work, but
* excluding communication that is conspicuously marked or otherwise
* designated in writing by the copyright owner as "Not a Contribution."
*
* "Contributor" shall mean Licensor and any individual or Legal Entity
* on behalf of whom a Contribution has been received by Licensor and
* subsequently incorporated within the Work.
*
* 2. Grant of Copyright License. Subject to the terms and conditions of
* this License, each Contributor hereby grants to You a perpetual,
* worldwide, non-exclusive, no-charge, royalty-free, irrevocable
* copyright license to reproduce, prepare Derivative Works of,
* publicly display, publicly perform, sublicense, and distribute the
*
Work and such Derivative Works in Source or Object form.
*
* 3. Grant of Patent License. Subject to the terms and conditions of
* this License, each Contributor hereby grants to You a perpetual,
* worldwide, non-exclusive, no-charge, royalty-free, irrevocable
* (except as stated in this section) patent license to make, have made,
* use, offer to sell, sell, import, and otherwise transfer the Work,
* where such license applies only to those patent claims licensable
* by such Contributor that are necessarily infringed by their
* Contribution(s) alone or by combination of their Contribution(s)
* with the Work to which such Contribution(s) was submitted. If You
* institute patent litigation against any entity (including a
* cross-claim or counterclaim in a lawsuit) alleging that the Work
* or a Contribution incorporated within the Work constitutes direct
* or contributory patent infringement, then any patent licenses
* granted to You under this License for that Work shall terminate
* as of the date such litigation is filed.
*
* 4. Redistribution. You may reproduce and distribute copies of the
* Work or Derivative Works thereof in any medium, with or without
* modifications, and in Source or Object form, provided that You
* meet the following conditions:
*
* (a) You must give any other recipients of the Work or

```
*         Derivative Works a copy of this License; and
*
*      (b) You must cause any modified files to carry prominent notices
*         stating that You changed the files; and
*
*      (c) You must retain, in the Source form of any Derivative Works
*         that You distribute, all copyright, patent, trademark, and
*         attribution notices from the Source form of the Work,
*         excluding those notices that do not pertain to any part of
*         the Derivative Works; and
*
*      (d) If the Work includes a "NOTICE"
 text file as part of its
*         distribution, then any Derivative Works that You distribute must
*         include a readable copy of the attribution notices contained
*         within such NOTICE file, excluding those notices that do not
*         pertain to any part of the Derivative Works, in at least one
*         of the following places: within a NOTICE text file distributed
*         as part of the Derivative Works; within the Source form or
*         documentation, if provided along with the Derivative Works; or,
*         within a display generated by the Derivative Works, if and
*         wherever such third-party notices normally appear. The contents
*         of the NOTICE file are for informational purposes only and
*         do not modify the License. You may add Your own attribution
*         notices within Derivative Works that You distribute, alongside
*         or as an addendum to the NOTICE text from the Work, provided
*         that
 such additional attribution notices cannot be construed
*         as modifying the License.
*
*      You may add Your own copyright statement to Your modifications and
*      may provide additional or different license terms and conditions
*      for use, reproduction, or distribution of Your modifications, or
*      for any such Derivative Works as a whole, provided Your use,
*      reproduction, and distribution of the Work otherwise complies with
*      the conditions stated in this License.
*
*   5. Submission of Contributions. Unless You explicitly state otherwise,
*      any Contribution intentionally submitted for inclusion in the Work
*      by You to the Licensor shall be under the terms and conditions of
*      this License, without any additional terms or conditions.
*      Notwithstanding the above, nothing herein shall supersede or modify
*      the terms of any separate license agreement you may have executed
*      with Licensor regarding such Contributions.
 *
*   6. Trademarks. This License does not grant permission to use the trade
*      names, trademarks, service marks, or product names of the Licensor,
*      except as required for reasonable and customary use in describing the
```

```
*      origin of the Work and reproducing the content of the NOTICE file.
*
*   7. Disclaimer of Warranty. Unless required by applicable law or
*      agreed to in writing, Licensor provides the Work (and each
*      Contributor provides its Contributions) on an "AS IS" BASIS,
*      WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
*      implied, including, without limitation, any warranties or conditions
*      of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
*      PARTICULAR PURPOSE. You are solely responsible for determining the
*      appropriateness of using or redistributing the Work and assume any
*      risks associated with Your exercise of permissions under this License.
*
*   8. Limitation of Liability.
 In no event and under no legal theory,
*      whether in tort (including negligence), contract, or otherwise,
*      unless required by applicable law (such as deliberate and grossly
*      negligent acts) or agreed to in writing, shall any Contributor be
*      liable to You for damages, including any direct, indirect, special,
*      incidental, or consequential damages of any character arising as a
*      result of this License or out of the use or inability to use the
*      Work (including but not limited to damages for loss of goodwill,
*      work stoppage, computer failure or malfunction, or any and all
*      other commercial damages or losses), even if such Contributor
*      has been advised of the possibility of such damages.
*
*   9. Accepting Warranty or Additional Liability. While redistributing
*      the Work or Derivative Works thereof, You may choose to offer,
*      and charge a fee for, acceptance of support, warranty, indemnity,
*      or other
 liability obligations and/or rights consistent with this
*      License. However, in accepting such obligations, You may act only
*      on Your own behalf and on Your sole responsibility, not on behalf
*      of any other Contributor, and only if You agree to indemnify,
*      defend, and hold each Contributor harmless for any liability
*      incurred by, or claims asserted against, such Contributor by reason
*      of your accepting any such warranty or additional liability.
*
*   END OF TERMS AND CONDITIONS
*
*   APPENDIX: How to apply the Apache License to your work.
*
*      To apply the Apache License to your work, attach the following
*      boilerplate notice, with the fields enclosed by brackets "[]"
*      replaced with your own identifying information. (Don't include
*      the brackets!)  The text should be enclosed in the appropriate
*      comment syntax for the file format. We also recommend that a
*      file or class name and description of purpose
```

be included on the
*   same "printed page" as the copyright notice for easier
*   identification within third-party archives.
*
*   Copyright [yyyy] [name of copyright owner]
*
*   Licensed under the Apache License, Version 2.0 (the "License");
*   you may not use this file except in compliance with the License.
*   You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
*   Unless required by applicable law or agreed to in writing, software
*   distributed under the License is distributed on an "AS IS" BASIS,
*   WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*   See the License for the specific language governing permissions and
*   limitations under the License.
*/
This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

1.613 json-smart 2.3

1.613.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
*   Copyright 2011-2014 JSON-SMART authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /json-smart-2-3-sources-4-jar/net/minidev/json/writer/DefaultMapper.java
No license file was found, but licenses were detected in source scan.

/*

* Copyright 2011 JSON-SMART authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /json-smart-2-3-sources-4-jar/net/minidev/json/JSONObject.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/JSONNavi.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/JSONArray.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/JSONStreamAwareEx.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/writer/FakeMapper.java
*
/json-smart-2-3-sources-4-jar/net/minidev/json/JSONAwareEx.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/JSONValue.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/parser/ParseException.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/JStylerObj.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/JSONUtil.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/parser/JSONParserString.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/writer/JsonReader.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/parser/JSONParserReader.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/writer/BeansMapper.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/JSONStreamAware.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/parser/JSONParserBase.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/writer/DefaultMapperOrdered.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/parser/JSONParserMemory.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/writer/ArraysMapper.java
*
/json-smart-2-3-sources-4-jar/net/minidev/json/writer/CollectionMapper.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/parser/JSONParser.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/writer/CompressorMapper.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/writer/DefaultMapperCollection.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/writer/JsonReaderI.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/parser/JSONParserStream.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/JSONStyle.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/parser/JSONParserInputStream.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/JSONAware.java
* /json-smart-2-3-sources-4-jar/net/minidev/json/parser/JSONParserByteArray.java

1.614 jctools-core 3.0.0

1.614.1 Available under license :

No license file was found, but licenses were detected in source scan.

<project xmlns="http://maven.apache.org/POM/4.0.0" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 http://maven.apache.org/maven-v4_0_0.xsd">
 <modelVersion>4.0.0</modelVersion>

 <artifactId>jctools-core</artifactId>
 <groupId>org.jctools</groupId>
 <version>3.0.0</version>
 <name>Java Concurrency Tools Core Library</name>
 <description>Java Concurrency Tools Core Library</description>
 <packaging>bundle</packaging>

 <dependencies>
  <dependency>
   <groupId>org.hamcrest</groupId>
   <artifactId>hamcrest-all</artifactId>
   <version>${hamcrest.version}</version>
   <scope>test</scope>
  </dependency>

  <dependency>
   <groupId>junit</groupId>
   <artifactId>junit</artifactId>
   <version>${junit.version}</version>
   <scope>test</scope>
  </dependency>

  <dependency>
   <groupId>com.google.guava</groupId>
   <artifactId>guava-testlib</artifactId>
   <version>${guava-testlib.version}</version>
   <scope>test</scope>
  </dependency>
 </dependencies>
 <build>
  <plugins>
   <plugin>
    <groupId>org.apache.maven.plugins</groupId>
    <artifactId>maven-surefire-plugin</artifactId>
    <version>3.0.0-M3</version>
    <configuration>
     <includes>

```
  <include>*</include>
 </includes>
</configuration>
</plugin>
<plugin>
 <groupId>org.apache.felix</groupId>
 <artifactId>maven-bundle-plugin</artifactId>
 <version>4.2.1</version>
 <extensions>true</extensions>
 <configuration>
  <instructions>
   <Import-Package>sun.misc;resolution:=optional</Import-Package>
  </instructions>
 </configuration>
</plugin>
<plugin>
 <groupId>org.apache.maven.plugins</groupId>
 <artifactId>maven-source-plugin</artifactId>
 <version>3.2.0</version>
 <executions>
  <execution>
   <id>attach-sources</id>
   <phase>verify</phase>
   <goals>
    <goal>jar-no-fork</goal>
   </goals>
  </execution>
 </executions>
</plugin>
<plugin>
 <groupId>org.apache.maven.plugins</groupId>
 <artifactId>maven-javadoc-plugin</artifactId>
 <version>3.1.1</version>
 <configuration>
  <additionalOptions>
   <additionalOption>-Xdoclint:none</additionalOption>
  </additionalOptions>
  <source>8</source>
 </configuration>
 <executions>
  <execution>
   <id>attach-javadocs</id>
   <goals>
    <goal>jar</goal>
   </goals>
  </execution>
 </executions>
</plugin>
```

```
 </plugins>
</build>

<distributionManagement>
 <repository>
  <id>bintray-jctools-jctools</id>
  <name>jctools-jctools</name>
  <url>https://api.bintray.com/maven/jctools/jctools/jctools-core/;publish=1</url>
 </repository>
</distributionManagement>

<url>https://github.com/JCTools</url>
<inceptionYear>2013</inceptionYear>

<licenses>
 <license>
  <name>Apache
License, Version 2.0</name>
  <url>http://www.apache.org/licenses/LICENSE-2.0.txt</url>
  <distribution>repo</distribution>
 </license>
</licenses>

<scm>
 <url>https://github.com/JCTools/JCTools</url>
 <connection>scm:git:https://github.com/JCTools/JCTools</connection>
 <tag>HEAD</tag>
</scm>

<developers>
 <developer>
  <url>https://github.com/nitsanw</url>
 </developer>
 <developer>
  <url>https://github.com/mjpt777</url>
 </developer>
 <developer>
  <url>https://github.com/RichardWarburton</url>
 </developer>
 <developer>
  <url>https://github.com/kay</url>
 </developer>
 <developer>
  <url>https://github.com/franz1981</url>
 </developer>
</developers>

<prerequisites>
```

```
 <maven>3.5.0</maven>
</prerequisites>

<properties>
 <project.build.sourceEncoding>UTF-8</project.build.sourceEncoding>
 <java.version>1.6</java.version>
 <java.test.version>1.8</java.test.version>

 <maven.compiler.source>${java.version}</maven.compiler.source>
 <maven.compiler.target>${java.version}</maven.compiler.target>
 <maven.compiler.testSource>${java.test.version}</maven.compiler.testSource>
 <maven.compiler.testTarget>${java.test.version}</maven.compiler.testTarget>

 <hamcrest.version>1.3</hamcrest.version>
 <junit.version>4.12</junit.version>
 <guava-testlib.version>21.0</guava-testlib.version>
</properties>
</project>

Found
 in path(s):
* /jctools-core-3-0-0-5-jar/META-INF/maven/org.jctools/jctools-core/pom.xml
No license file was found, but licenses were detected in source scan.

Manifest-Version: 1.0
Bnd-LastModified: 1578049665284
Build-Jdk: 1.8.0_232
Built-By: yak
Bundle-Description: Java Concurrency Tools Core Library
Bundle-License: http://www.apache.org/licenses/LICENSE-2.0.txt
Bundle-ManifestVersion: 2
Bundle-Name: Java Concurrency Tools Core Library
Bundle-SymbolicName: org.jctools.core
Bundle-Version: 3.0.0
Created-By: Apache Maven Bundle Plugin
Export-Package: org.jctools.maps;version="3.0.0",org.jctools.util;vers
ion="3.0.0";uses:="sun.misc",org.jctools.queues;version="3.0.0";uses:
="org.jctools.queues.spec",org.jctools.queues.spec;version="3.0.0",or
g.jctools.queues.atomic;version="3.0.0";uses:="org.jctools.queues,org
.jctools.queues.spec"
Import-Package: sun.misc;resolution:=optional
Require-Capability: osgi.ee;filter:="(&(osgi.ee=JavaSE)(version=1.6))"
Tool: Bnd-4.2.0.201903051501

Found in path(s):
* /jctools-core-3-0-0-5-jar/META-INF/MANIFEST.MF
```

1.615 babel-plugin-syntax-top-level-await 7.14.5

1.615.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.616 memoize-one 5.2.1

1.616.1 Available under license :

MIT License

Copyright (c) 2019 Alexander Reardon

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.617 fs-readdir-recursive 1.1.0

1.617.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Jonathan Ong me@jongleberry.com

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.618 node-notifier 5.4.5

1.618.1 Available under license :

MIT

1.619 sinon 11.1.2

1.619.1 Available under license :

(The BSD License)

Copyright (c) 2010-2017, Christian Johansen, christian@cjohansen.no
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,
  this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,
  this list of conditions and the following disclaimer in the documentation
  and/or other materials provided with the distribution.
* Neither the name of Christian Johansen nor the names of his contributors
  may be used to endorse or promote products derived from this software
  without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
 AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.620 httpclient 3.10.0

1.620.1 Available under license :

The MIT License (MIT)

Copyright (c) 2012-2019 Twilio SendGrid, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.621 groovy 3.0.8

1.621.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* This file is adapted from the Antlr4 Java grammar which has the following license
*
* Copyright (c) 2013 Terence Parr, Sam Harwell
* All rights reserved.
* [The "BSD licence"]
*
*   http://www.opensource.org/licenses/bsd-license.php
*
* Subsequent modifications by the Groovy community have been done under the Apache License v2:
*
* Licensed to the Apache Software Foundation (ASF) under one
* or more contributor license agreements. See the NOTICE file
* distributed with this work for additional information
* regarding copyright ownership. The ASF licenses this file
* to you under the Apache License, Version 2.0 (the
* "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing,
* software distributed under the
 License is distributed on an
* "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY
* KIND, either express or implied. See the License for the
* specific language governing permissions and limitations
* under the License.
*/

```
/**
* The Groovy grammar is based on the official grammar for Java:
* https://github.com/antlr/grammars-v4/blob/master/java/Java.g4
*/
parser grammar GroovyParser;

options {
  tokenVocab = GroovyLexer;
  contextSuperClass = GroovyParserRuleContext;
  superClass = AbstractParser;
}

@header {
  import java.util.Map;
  import org.codehaus.groovy.ast.NodeMetaDataHandler;
}

@members {

  public static class GroovyParserRuleContext extends ParserRuleContext implements NodeMetaDataHandler {
     private Map metaDataMap = null;

     public GroovyParserRuleContext() {}

     public GroovyParserRuleContext(ParserRuleContext parent, int invokingStateNumber) {
        super(parent, invokingStateNumber);
     }

     @Override
      public Map<?, ?> getMetaDataMap() {
        return this.metaDataMap;
     }

     @Override
     public void setMetaDataMap(Map<?, ?> metaDataMap) {
        this.metaDataMap = metaDataMap;
     }
  }

  @Override
  public int getSyntaxErrorSource() {
     return GroovySyntaxError.PARSER;
  }

  @Override
  public int getErrorLine() {
     Token token = _input.LT(-1);
```

```
        if (null == token) {
            return -1;
        }

        return token.getLine();
    }

    @Override
    public int getErrorColumn() {
        Token token = _input.LT(-1);

        if (null == token) {
            return -1;
        }

        return token.getCharPositionInLine() + 1 + token.getText().length();
    }
}

// starting point for parsing a groovy file
compilationUnit
    :   nls (packageDeclaration sep?)? scriptStatements? EOF
    ;

scriptStatements
    :   scriptStatement (sep scriptStatement)* sep?
    ;

scriptStatement
    :   importDeclaration
   // Import statement.  Can be used in any scope.  Has "import x as y" also.
    |   typeDeclaration
    // validate the method in the AstBuilder#visitMethodDeclaration, e.g. method without method body is not allowed
    |   { !SemanticPredicates.isInvalidMethodDeclaration(_input) }?
        methodDeclaration[3, 9]
    |   statement
    ;

packageDeclaration
    :   annotationsOpt PACKAGE qualifiedName
    ;

importDeclaration
    :   annotationsOpt IMPORT STATIC? qualifiedName (DOT MUL | AS alias=identifier)?
    ;
```

```
typeDeclaration
  :  classOrInterfaceModifiersOpt classDeclaration
  ;

modifier
  :  classOrInterfaceModifier
  |  m=(   NATIVE
       |  SYNCHRONIZED
       |  TRANSIENT
       |  VOLATILE
       |  DEF
       |  VAR
       )
  ;

modifiersOpt
  :  (modifiers nls)?
  ;

modifiers
  :  modifier (nls modifier)*
  ;

classOrInterfaceModifiersOpt
  :  (classOrInterfaceModifiers
        NL* /* Use `NL*` here for better performance,
 so DON'T replace it with `nls` */
     )?
  ;

classOrInterfaceModifiers
  :  classOrInterfaceModifier (nls classOrInterfaceModifier)*
  ;

classOrInterfaceModifier
  :  annotation       // class or interface
  |  m=(   PUBLIC     // class or interface
       |  PROTECTED  // class or interface
       |  PRIVATE    // class or interface
       |  STATIC     // class or interface
       |  ABSTRACT   // class or interface
       |  FINAL      // class only -- does not apply to interfaces
       |  STRICTFP   // class or interface
       |  DEFAULT    // interface only -- does not apply to classes
       )
  ;

variableModifier
```

```
  :  annotation
  |  m=( FINAL
       | DEF
       | VAR
       // Groovy supports declaring local variables as instance/class fields,
       // e.g. import groovy.transform.*; @Field static List awe = [1, 2, 3]
       // e.g. import groovy.transform.*; def a = { @Field public List awe
 = [1, 2, 3] }
       // Notice: Groovy 2.4.7 just allows to declare local variables with the following modifiers when using
annotations(e.g. @Field)
       // TODO check whether the following modifiers accompany annotations or not. Because the legacy codes(e.g.
benchmark/bench/heapsort.groovy) allow to declare the special instance/class fields without annotations, we leave it
as it is for the time being
       | PUBLIC
       | PROTECTED
       | PRIVATE
       | STATIC
       | ABSTRACT
       | STRICTFP
       )
  ;

variableModifiersOpt
  :  (variableModifiers nls)?
  ;

variableModifiers
  :  variableModifier (nls variableModifier)*
  ;

typeParameters
  :  LT nls typeParameter (COMMA nls typeParameter)* nls GT
  ;

typeParameter
  :  className (EXTENDS nls typeBound)?
  ;

typeBound
  :  type (BITAND nls type)*
  ;

typeList
  :  type (COMMA nls type)*
  ;


/**
```

```
*  t   0: class; 1: interface; 2: enum; 3: annotation; 4:
 trait
*/
classDeclaration
locals[ int t ]
  :  (   CLASS { $t = 0; }
     |   INTERFACE { $t = 1; }
     |   ENUM { $t = 2; }
     |   AT INTERFACE { $t = 3; }
     |   TRAIT { $t = 4; }
     )
     identifier
     (nls typeParameters)?
     (nls EXTENDS nls scs=typeList)?
     (nls IMPLEMENTS nls is=typeList)?
     nls classBody[$t]
  ;

// t    see the comment of classDeclaration
classBody[int t]
  :  LBRACE nls
     (
        /* Only enum can have enum constants */
        { 2 == $t }?
        enumConstants (nls COMMA)? sep?
     |
     )
     (classBodyDeclaration[$t] (sep classBodyDeclaration[$t])*)? sep? RBRACE
  ;

enumConstants
  :  enumConstant (nls COMMA nls enumConstant)*
  ;

enumConstant
  :  annotationsOpt identifier arguments? anonymousInnerClassDeclaration[1]?
  ;

classBodyDeclaration[int t]
  :  (STATIC nls)? block
  |  memberDeclaration[$t]
  ;

memberDeclaration[int t]
  :  methodDeclaration[0,
 $t]
  |  fieldDeclaration
  |  modifiersOpt classDeclaration
```

```
  ;

/**
*  t   0: *class member* all kinds of method declaration AND constructor declaration,
*      1: normal method declaration, 2: abstract method declaration
*      3: normal method declaration OR abstract method declaration
*  ct  9: script, other see the comment of classDeclaration
*/
methodDeclaration[int t, int ct]
  :  modifiersOpt typeParameters? (returnType[$ct] nls)?
     methodName formalParameters
     (
        DEFAULT nls elementValue
     |
        (nls THROWS nls qualifiedClassNameList)?
        (nls methodBody)?
     )?
  ;

methodName
  :  identifier
  |  stringLiteral
  ;

returnType[int ct]
  :
     standardType
  |  VOID
  ;

fieldDeclaration
  :  variableDeclaration[1]
  ;

variableDeclarators
  :  variableDeclarator (COMMA nls variableDeclarator)*
  ;

variableDeclarator
  :  variableDeclaratorId (nls ASSIGN nls variableInitializer)?
   ;

variableDeclaratorId
  :  identifier
  ;

variableInitializer
  :  enhancedStatementExpression
```

```
  ;

variableInitializers
  :  variableInitializer (nls COMMA nls variableInitializer)* nls COMMA?
  ;

emptyDims
  :  (annotationsOpt LBRACK RBRACK)+
  ;

emptyDimsOpt
  :  emptyDims?
  ;

standardType
options { baseContext = type; }
  :  annotationsOpt
     (
        primitiveType
     |
        standardClassOrInterfaceType
     )
     emptyDimsOpt
  ;

type
  :  annotationsOpt
     (
        (
           primitiveType
        |
           // !!! Error Alternative !!!
            VOID
        )
     |
           generalClassOrInterfaceType
     )
     emptyDimsOpt
  ;

classOrInterfaceType
  :  (   qualifiedClassName
     |   qualifiedStandardClassName
     ) typeArguments?
  ;

generalClassOrInterfaceType
options { baseContext = classOrInterfaceType; }
```

```
  :  qualifiedClassName typeArguments?
  ;

standardClassOrInterfaceType
options { baseContext = classOrInterfaceType; }
  :  qualifiedStandardClassName typeArguments?
  ;

primitiveType
  :  BuiltInPrimitiveType
  ;

typeArguments
  :  LT nls typeArgument (COMMA nls typeArgument)* nls GT
  ;

typeArgument
  :  type
  |  annotationsOpt QUESTION ((EXTENDS | SUPER) nls type)?
  ;

annotatedQualifiedClassName
  :  annotationsOpt qualifiedClassName
  ;

qualifiedClassNameList
  :  annotatedQualifiedClassName (COMMA nls annotatedQualifiedClassName)*
  ;

formalParameters
  :  LPAREN formalParameterList? rparen
  ;

formalParameterList
  :  (formalParameter | thisFormalParameter) (COMMA nls formalParameter)*
  ;

thisFormalParameter
  :  type THIS
  ;

formalParameter
  :  variableModifiersOpt type? ELLIPSIS? variableDeclaratorId (nls ASSIGN nls expression)?
  ;

methodBody
  :  block
```

```
  ;

qualifiedName
  :  qualifiedNameElement
 (DOT qualifiedNameElement)*
  ;

/**
*  Java doesn't have the keywords 'as', 'in', 'def', 'trait' so we make some allowances
*  for them in package names for better integration with existing Java packages
*/
qualifiedNameElement
  :  identifier
  |  DEF
  |  IN
  |  AS
  |  TRAIT
  ;

qualifiedNameElements
  :  (qualifiedNameElement DOT)*
  ;

qualifiedClassName
  :  qualifiedNameElements identifier
  ;

qualifiedStandardClassName
  :  qualifiedNameElements className (DOT className)*
  ;

literal
  :  IntegerLiteral                                    #integerLiteralAlt
  |  FloatingPointLiteral                                 #floatingPointLiteralAlt
  |  stringLiteral                                    #stringLiteralAlt
  |  BooleanLiteral                                     #booleanLiteralAlt
  |  NullLiteral
                                          #nullLiteralAlt
  ;

// GSTRING

gstring
  :  GStringBegin gstringValue (GStringPart  gstringValue)* GStringEnd
  ;

gstringValue
  :  gstringPath
```

```
  |  closure
  ;

gstringPath
  :  identifier GStringPathPart*
  ;


// LAMBDA EXPRESSION
lambdaExpression
options { baseContext = standardLambdaExpression; }
  :  lambdaParameters nls ARROW nls lambdaBody
  ;

// JAVA STANDARD LAMBDA EXPRESSION
standardLambdaExpression
  :  standardLambdaParameters nls ARROW nls lambdaBody
  ;

lambdaParameters
options { baseContext = standardLambdaParameters; }
  :  formalParameters

  // { a -> a * 2 } can be parsed as a lambda expression in a block, but we expect a closure.
  // So it is better to put parameters in the parentheses and the following single parameter without parentheses is
limited
//   |  variableDeclaratorId
  ;

standardLambdaParameters
  :  formalParameters
  |
  variableDeclaratorId
  ;

lambdaBody
  :  block
  |  statementExpression
  ;

// CLOSURE
closure
  :  LBRACE (nls (formalParameterList nls)? ARROW)? sep? blockStatementsOpt RBRACE
  ;

// GROOVY-8991: Difference in behaviour with closure and lambda
closureOrLambdaExpression
  :  closure
```

```
  | lambdaExpression
  ;

blockStatementsOpt
  : blockStatements?
  ;

blockStatements
  : blockStatement (sep blockStatement)* sep?
  ;

// ANNOTATIONS

annotationsOpt
  : (annotation (nls annotation)* nls)?
  ;

annotation
  : AT annotationName (nls LPAREN elementValues? rparen)?
  ;

elementValues
  : elementValuePairs
  | elementValue
  ;

annotationName : qualifiedClassName ;

elementValuePairs
  : elementValuePair (COMMA elementValuePair)*
  ;

elementValuePair
  : elementValuePairName nls ASSIGN nls elementValue
  ;

elementValuePairName
  : identifier
  | keywords
  ;

// TODO verify the potential performance issue
 because rule expression contains sub-rule assignments(https://github.com/antlr/grammars-v4/issues/215)
elementValue
  : elementValueArrayInitializer
  | annotation
  | expression
  ;
```

```
elementValueArrayInitializer
  :  LBRACK (elementValue (COMMA elementValue)* COMMA?)? RBRACK
  ;

// STATEMENTS / BLOCKS

block
  :  LBRACE sep? blockStatementsOpt RBRACE
  ;

blockStatement
  :  localVariableDeclaration
  |  statement
  ;

localVariableDeclaration
  :  { !SemanticPredicates.isInvalidLocalVariableDeclaration(_input) }?
     variableDeclaration[0]
  ;

/**
*  t   0: local variable declaration; 1: field declaration
*/
variableDeclaration[int t]
  :  modifiers nls
     (   type? variableDeclarators
     |   typeNamePairs nls ASSIGN nls variableInitializer
     )
  |
     type variableDeclarators
  ;

typeNamePairs
  :  LPAREN typeNamePair (COMMA typeNamePair)* rparen
  ;

typeNamePair
  :  type? variableDeclaratorId
  ;

variableNames
   :  LPAREN variableDeclaratorId (COMMA variableDeclaratorId)+ rparen
  ;

conditionalStatement
  :  ifElseStatement
  |  switchStatement
```

```
  ;

ifElseStatement
  : IF expressionInPar nls tb=statement ((nls | sep) ELSE nls fb=statement)?
  ;

switchStatement
  : SWITCH expressionInPar nls LBRACE nls (switchBlockStatementGroup+ nls)? RBRACE
  ;

loopStatement
  : FOR LPAREN forControl rparen nls statement                    #forStmtAlt
  | WHILE expressionInPar nls statement                           #whileStmtAlt
  | DO nls statement nls WHILE expressionInPar                    #doWhileStmtAlt
  ;

continueStatement
  : CONTINUE
    identifier?
  ;

breakStatement
  : BREAK
    identifier?
  ;

tryCatchStatement
  : TRY resources? nls block
    (nls catchClause)*
    (nls finallyBlock)?
   ;

assertStatement
  : ASSERT ce=expression (nls (COLON | COMMA) nls me=expression)?
  ;

statement
  : block                                                         #blockStmtAlt
  | conditionalStatement                                          #conditionalStmtAlt
  | loopStatement                                                 #loopStmtAlt
  | tryCatchStatement                                             #tryCatchStmtAlt
  | SYNCHRONIZED expressionInPar nls block                        #synchronizedStmtAlt
  | RETURN expression?                                            #returnStmtAlt
  | THROW expression                                              #throwStmtAlt
  | breakStatement
                                                                  #breakStmtAlt
  | continueStatement                                             #continueStmtAlt
  | identifier COLON nls statement                                #labeledStmtAlt
```

```
  | assertStatement                                                    #assertStmtAlt
  | localVariableDeclaration                                          #localVariableDeclarationStmtAlt
  | statementExpression                                               #expressionStmtAlt
  | SEMI                                                             #emptyStmtAlt
  ;

catchClause
  : CATCH LPAREN variableModifiersOpt catchType? identifier rparen nls block
  ;

catchType
  : qualifiedClassName
 (BITOR qualifiedClassName)*
  ;

finallyBlock
  : FINALLY nls block
  ;

resources
  : LPAREN nls resourceList sep? rparen
  ;

resourceList
  : resource (sep resource)*
  ;

resource
  : localVariableDeclaration
  | expression
  ;


/** Matches cases then statements, both of which are mandatory.
*  To handle empty cases at the end, we add switchLabel* to statement.
*/
switchBlockStatementGroup
  : switchLabel (nls switchLabel)* nls blockStatements
  ;

switchLabel
  : CASE expression COLON
  | DEFAULT COLON
  ;

forControl
  : enhancedForControl
  | classicalForControl
```

```
  ;

enhancedForControl
  :  variableModifiersOpt type? variableDeclaratorId (COLON | IN) expression
  ;

classicalForControl
  :  forInit? SEMI expression? SEMI forUpdate?
  ;

forInit
  :  localVariableDeclaration
  |  expressionList[false]
  ;

forUpdate
  :  expressionList[false]
  ;


// EXPRESSIONS

castParExpression
  :
 LPAREN type rparen
  ;

parExpression
  :  expressionInPar
  ;

expressionInPar
  :  LPAREN enhancedStatementExpression rparen
  ;

expressionList[boolean canSpread]
  :  expressionListElement[$canSpread] (COMMA expressionListElement[$canSpread])*
  ;

expressionListElement[boolean canSpread]
  :  MUL? expression
  ;

enhancedStatementExpression
  :  statementExpression
  |  standardLambdaExpression
  ;
```

```
statementExpression
  :  commandExpression                #commandExprAlt
  ;

postfixExpression
  :  pathExpression op=(INC | DEC)?
  ;

expression
  // must come before postfixExpression to resovle the ambiguities between casting and call on parentheses
expression, e.g. (int)(1 / 2)
  :  castParExpression castOperandExpression                                  #castExprAlt

  // qualified names, array expressions, method invocation, post inc/dec
  |  postfixExpression
         #postfixExprAlt

  // ~(BNOT)/!(LNOT) (level 1)
  |  (BITNOT | NOT) nls expression                                            #unaryNotExprAlt

  // math power operator (**) (level 2)
  |  left=expression op=POWER nls right=expression                            #powerExprAlt

  // ++(prefix)/--(prefix)/+(unary)/-(unary) (level 3)
  |  op=(INC | DEC | ADD | SUB) expression                                    #unaryAddExprAlt

  // multiplication/division/modulo (level 4)
  |  left=expression nls op=(MUL | DIV | MOD) nls right=expression            #multiplicativeExprAlt

  // binary addition/subtraction (level 5)
  |  left=expression op=(ADD | SUB) nls right=expression                      #additiveExprAlt

  // bit shift expressions (level 6)
  |  left=expression nls
      (          (  dlOp=LT LT
                 |  tgOp=GT GT GT
                 |  dgOp=GT GT


              )
      |  rangeOp=(   RANGE_INCLUSIVE
                 |   RANGE_EXCLUSIVE
                 )
      ) nls
    right=expression                                                         #shiftExprAlt

  // boolean relational expressions (level 7)
  |  left=expression nls op=(AS | INSTANCEOF | NOT_INSTANCEOF) nls type      #relationalExprAlt
  |  left=expression nls op=(LE | GE | GT | LT | IN | NOT_IN)  nls right=expression     #relationalExprAlt
```

```
  // equality/inequality (==/!=) (level 8)
  |  left=expression nls
        op=(    IDENTICAL
          |    NOT_IDENTICAL
          |    EQUAL
          |    NOTEQUAL
          |    SPACESHIP
          ) nls
     right=expression                                          #equalityExprAlt

  // regex find and match (=~ and ==~) (level 8.5)
  // jez: moved =~ closer to precedence of == etc, as...

  // 'if (foo =~ "a.c")' is very close in intent to 'if (foo == "abc")'
  |  left=expression nls op=(REGEX_FIND | REGEX_MATCH) nls right=expression          #regexExprAlt

  // bitwise or non-short-circuiting and (&)  (level 9)
  |  left=expression nls op=BITAND nls right=expression                  #andExprAlt

  // exclusive or (^)  (level 10)
  |  left=expression nls op=XOR nls right=expression                     #exclusiveOrExprAlt

  // bitwise or non-short-circuiting or (|)  (level 11)
  |  left=expression nls op=BITOR nls right=expression                   #inclusiveOrExprAlt

  // logical and (&&)  (level 12)
  |  left=expression nls op=AND nls right=expression                     #logicalAndExprAlt

  // logical or (||)  (level 13)
  |  left=expression nls op=OR nls right=expression                      #logicalOrExprAlt

  // conditional test (level 14)
  |  <assoc=right>
 con=expression nls
     (   QUESTION nls tb=expression nls COLON nls
     |   ELVIS nls
     )
     fb=expression                                             #conditionalExprAlt

  // assignment expression (level 15)
  // "(a) = [1]" is a special case of multipleAssignmentExprAlt, it will be handle by assignmentExprAlt
  |  <assoc=right> left=variableNames nls op=ASSIGN nls right=statementExpression
#multipleAssignmentExprAlt
  |  <assoc=right> left=expression nls
                op=(   ASSIGN
                  |   ADD_ASSIGN
                  |   SUB_ASSIGN
```

```
                | MUL_ASSIGN
                | DIV_ASSIGN
                | AND_ASSIGN
                | OR_ASSIGN
                | XOR_ASSIGN
                | RSHIFT_ASSIGN
                | URSHIFT_ASSIGN
                | LSHIFT_ASSIGN
                | MOD_ASSIGN
                | POWER_ASSIGN
                | ELVIS_ASSIGN
                ) nls
            enhancedStatementExpression                         #assignmentExprAlt
  ;

castOperandExpression
options { baseContext = expression; }
  : castParExpression castOperandExpression                         #castExprAlt

  | postfixExpression                                           #postfixExprAlt

  // ~(BNOT)/!(LNOT)
  | (BITNOT | NOT) nls castOperandExpression                         #unaryNotExprAlt

  // ++(prefix)/--(prefix)/+(unary)/-(unary)
  | op=(INC | DEC | ADD | SUB) castOperandExpression                    #unaryAddExprAlt
  ;

commandExpression
  : expression
    (
      { !SemanticPredicates.isFollowingArgumentsOrClosure($expression.ctx) }?
      argumentList
    |
      /* if pathExpression is a method call, no need to have any more arguments */
    )

    commandArgument*
  ;

commandArgument
  : commandPrimary
    // what follows is either a normal argument, parens,
    // an appended block, an index operation, or nothing
    // parens (a b already processed):
    //      a b c() d e -> a(b).c().d(e)
    //      a b c()() d e -> a(b).c().call().d(e)
    // index (a b already processed):
```

```
    //      a b c[x] d e -> a(b).c[x].d(e)
    //      a b c[x][y] d e -> a(b).c[x][y].d(e)
    // block (a b already processed):
    //      a b c {x} d e -> a(b).c({x}).d(e)
    //
    // parens/block completes method call
    // index makes method call to property get with index
    //
    (   pathElement+
    |   argumentList
    )?
  ;

/**
*  A "path expression" is a name or other primary, possibly qualified by various
*  forms of dot, and/or
 followed by various kinds of brackets.
*  It can be used for value or assigned to, or else further qualified, indexed, or called.
*  It is called a "path" because it looks like a linear path through a data structure.
*  Examples:  x.y, x?.y, x*.y, x.@y; x[], x[y], x[y,z]; x(), x(y), x(y,z); x{s}; a.b[n].c(x).d{s}
*  (Compare to a C lvalue, or LeftHandSide in the JLS section 15.26.)
*  General expressions are built up from path expressions, using operators like '+' and '='.
*
*  t   0: primary, 1: namePart, 2: arguments, 3: closureOrLambdaExpression, 4: indexPropertyArgs, 5:
namedPropertyArgs,
*      6: non-static inner class creator
*/
pathExpression returns [int t]
  :  (
        primary
     |
        // if 'static' followed by DOT, we can treat them as identifiers, e.g. static.unused = { -> }
        { _input.LT(2).getType() == DOT }?
        STATIC
     ) (pathElement { $t = $pathElement.t; })*
  ;

pathElement returns [int t]
  :  nls

 (
        // AT: foo.@bar selects the field (or attribute), not property
        (
           (   DOT                // The all-powerful dot.
           |   SPREAD_DOT         // Spread operator:  x*.y  ===  x?.collect{it.y}
           |   SAFE_DOT           // Optional-null operator:  x?.y  === (x==null)?null:x.y
           |   SAFE_CHAIN_DOT     // Optional-null chain operator:  x??.y.z  === x?.y?.z
           ) nls (AT | nonWildcardTypeArguments)?
```

```
        |
          METHOD_POINTER nls      // Method pointer operator: foo.&y == foo.metaClass.getMethodPointer(foo,
"y")
        |
          METHOD_REFERENCE nls    // Method reference: System.out::println
        )
        namePart
        { $t = 1; }
    |
        DOT nls NEW creator[1]
        { $t = 6; }

        // Can always append a block, as foo{bar}
    |   closureOrLambdaExpression
        { $t = 3; }
    )

  |   arguments

   { $t = 2; }

  // Element selection is always an option, too.
  // In Groovy, the stuff between brackets is a general argument list,
  // since the bracket operator is transformed into a method call.
  |   indexPropertyArgs
      { $t = 4; }

  |   namedPropertyArgs
      { $t = 5; }
  ;

/**
*  This is the grammar for what can follow a dot:  x.a, x.@a, x.&a, x.'a', etc.
*/
namePart
  :
     (   identifier

     // foo.'bar' is in all ways same as foo.bar, except that bar can have an arbitrary spelling
     |   stringLiteral

     |   dynamicMemberName

     /* just a PROPOSAL, which has not been implemented yet!
     // PROPOSAL, DECIDE:  Is this inline form of the 'with' statement useful?
     // Definition:  a.{foo} === {with(a) {foo}}
     // May cover some path expression use-cases previously handled by dynamic scoping (closure delegates).
     |   block
```

```
      */

      // let's allow common keywords as property names
      |
    keywords
      )
    ;

/**
*  If a dot is followed by a parenthesized or quoted expression, the member is computed dynamically,
*  and the member selection is done only at runtime.  This forces a statically unchecked member access.
*/
dynamicMemberName
    :   parExpression
    |   gstring
    ;

/** An expression may be followed by [...].
*  Unlike Java, these brackets may contain a general argument list,
*  which is passed to the array element operator, which can make of it what it wants.
*  The brackets may also be empty, as in T[].  This is how Groovy names array types.
*/
indexPropertyArgs
    :   QUESTION? LBRACK expressionList[true]? RBRACK
    ;

namedPropertyArgs
    :   QUESTION? LBRACK (namedPropertyArgList | COLON) RBRACK
    ;

primary
    :
      // Append `typeArguments?` to `identifier` to support constructor reference with generics, e.g.
HashMap<String, Integer>::new
      // Though this is not a graceful solution, it is much faster than replacing `builtInType`
 with `type`
      identifier typeArguments?                                 #identifierPrmrAlt
    |   literal                                                 #literalPrmrAlt
    |   gstring                                                 #gstringPrmrAlt
    |   NEW nls creator[0]                                      #newPrmrAlt
    |   THIS                                                    #thisPrmrAlt
    |   SUPER                                                   #superPrmrAlt
    |   parExpression                                           #parenPrmrAlt
    |   closureOrLambdaExpression                               #closureOrLambdaExpressionPrmrAlt
    |   list                                                    #listPrmrAlt
     |   map                                                    #mapPrmrAlt
    |   builtInType                                             #builtInTypePrmrAlt
    ;
```

```
namedPropertyArgPrimary
options { baseContext = primary; }
  :  identifier                                    #identifierPrmrAlt
  |  literal                                       #literalPrmrAlt
  |  gstring                                       #gstringPrmrAlt
  |  parExpression                                 #parenPrmrAlt
  ;

namedArgPrimary
options { baseContext = primary; }
  :  identifier                                    #identifierPrmrAlt
  |  literal                                       #literalPrmrAlt
  |
 gstring                                           #gstringPrmrAlt
  ;

commandPrimary
options { baseContext = primary; }
  :  identifier                                    #identifierPrmrAlt
  |  literal                                       #literalPrmrAlt
  |  gstring                                       #gstringPrmrAlt
  ;

list
  :  LBRACK expressionList[true]? COMMA? RBRACK
  ;

map
  :  LBRACK
     (  mapEntryList COMMA?
     |  COLON
     )
     RBRACK
  ;

mapEntryList
  :  mapEntry (COMMA mapEntry)*
  ;

namedPropertyArgList
options { baseContext = mapEntryList; }
  :  namedPropertyArg (COMMA namedPropertyArg)*
  ;

mapEntry
  :  mapEntryLabel COLON nls expression
  |  MUL COLON nls expression
```

```
  ;

namedPropertyArg
options { baseContext = mapEntry; }
  :  namedPropertyArgLabel
 COLON nls expression
  |  MUL COLON nls expression
  ;

namedArg
options { baseContext = mapEntry; }
  :  namedArgLabel COLON nls expression
  |  MUL COLON nls expression
  ;

mapEntryLabel
  :  keywords
  |  primary
  ;

namedPropertyArgLabel
options { baseContext = mapEntryLabel; }
  :  keywords
  |  namedPropertyArgPrimary
  ;

namedArgLabel
options { baseContext = mapEntryLabel; }
  :  keywords
  |  namedArgPrimary
  ;

/**
*  t 0: general creation; 1: non-static inner class creation
*/
creator[int t]
  :  createdName
     (  nls arguments anonymousInnerClassDeclaration[0]?
     |  dim+ (nls arrayInitializer)?
     )
  ;

dim
  :  annotationsOpt LBRACK expression? RBRACK
  ;

arrayInitializer
  :  LBRACE nls (variableInitializers nls)? RBRACE
```

```
  ;

/**
*  t   0: anonymous inner class; 1: anonymous enum
*/
anonymousInnerClassDeclaration[int t]
  :  classBody[0]
  ;

createdName
  :  annotationsOpt

 (  primitiveType
    |  qualifiedClassName typeArgumentsOrDiamond?
    )
  ;

nonWildcardTypeArguments
  :  LT nls typeList nls GT
  ;

typeArgumentsOrDiamond
  :  LT GT
  |  typeArguments
  ;

arguments
  :  LPAREN enhancedArgumentListInPar? COMMA? rparen
  ;

argumentList
options { baseContext = enhancedArgumentListInPar; }
  :  firstArgumentListElement
     (  COMMA nls
        argumentListElement
     )*
  ;

enhancedArgumentList
options { baseContext = enhancedArgumentListInPar; }
  :  firstEnhancedArgumentListElement
     (  COMMA nls
        enhancedArgumentListElement
     )*
  ;

enhancedArgumentListInPar
  :  enhancedArgumentListElement
```

```
      (  COMMA nls
         enhancedArgumentListElement
      )*
  ;

firstArgumentListElement
options { baseContext = enhancedArgumentListElement; }
  :  expressionListElement[true]
  |  namedArg
  ;

argumentListElement
options { baseContext = enhancedArgumentListElement;
 }
  :  expressionListElement[true]
  |  namedPropertyArg
  ;

firstEnhancedArgumentListElement
options { baseContext = enhancedArgumentListElement; }
  :  expressionListElement[true]
  |  standardLambdaExpression
  |  namedArg
  ;

enhancedArgumentListElement
  :  expressionListElement[true]
  |  standardLambdaExpression
  |  namedPropertyArg
  ;

stringLiteral
  :  StringLiteral
  ;

className
  :  CapitalizedIdentifier
  ;

identifier
  :  Identifier
  |  CapitalizedIdentifier
  |  VAR
  |  IN
// |  DEF
  |  TRAIT
  |  AS
  ;
```

```
builtInType
  : BuiltInPrimitiveType
  | VOID
  ;

keywords
  : ABSTRACT
  | AS
  | ASSERT
  | BREAK
  | CASE
  | CATCH
  | CLASS
  | CONST
  | CONTINUE
  | DEF
  | DEFAULT
  | DO
  | ELSE
  | ENUM
  | EXTENDS
  | FINAL
  | FINALLY
  | FOR
  | GOTO
  | IF
  | IMPLEMENTS
  | IMPORT
  | IN
  | INSTANCEOF
  | INTERFACE
  | NATIVE
  | NEW
  | PACKAGE
  | RETURN
  | STATIC
  | STRICTFP
  | SUPER
  | SWITCH
  | SYNCHRONIZED
  | THIS
  | THROW
  | THROWS
  | TRANSIENT
  | TRAIT
  | THREADSAFE
  | TRY
```

```
  |  VAR
  |  VOLATILE
  |  WHILE

  |  NullLiteral
  |  BooleanLiteral

  |  BuiltInPrimitiveType
  |  VOID

  |  PUBLIC
  |  PROTECTED
  |  PRIVATE
  ;

rparen
  :  RPAREN
  ;

nls
  :  NL*
  ;

sep :   (NL | SEMI)+
  ;
```

Found in path(s):
* /groovy-3-0-8-sources-1-jar/GroovyParser.g4
No license file was found, but licenses were detected in source scan.

```
/** JSR-241 Groovy Recognizer.
*
* Run 'java Main [-showtree] directory-full-of-groovy-files'
*
* [The -showtree option pops up a Swing frame that shows
*  the AST constructed from the parser.]
*
* Contributing authors:
*            John Mitchell          johnm@non.net
*            Terence Parr           parrt@magelang.com
*            John Lilley            jlilley@empathy.com
*            Scott Stanchfield      thetick@magelang.com
*            Markus Mohnen          mohnen@informatik.rwth-aachen.de
*            Peter Williams         pete.williams@sun.com
*            Allan Jacobs           Allan.Jacobs@eng.sun.com
*            Steve Messick          messick@redhills.com
*            James Strachan         jstrachan@protique.com
*            John Pybus             john@pybus.org
```

```
*              John Rose              rose00@mac.com
*              Jeremy Rayner
     groovy@ross-rayner.com
*              Alex Popescu           the.mindstorm@gmail.com
*              Martin Kempf           mkempf@hsr.ch
*              Reto Kleeb             rkleeb@hsr.ch
*
* Version 1.00 December 9, 1997 -- initial release
* Version 1.01 December 10, 1997
*              fixed bug in octal def (0..7 not 0..8)
* Version 1.10 August 1998 (parrt)
*              added tree construction
*              fixed definition of WS,comments for mac,pc,unix newlines
*              added unary plus
* Version 1.11 (Nov 20, 1998)
*              Added "shutup" option to turn off last ambig warning.
*              Fixed inner class def to allow named class defs as statements
*              synchronized requires compound not simple statement
*              add [] after builtInType DOT class in primaryExpression
*              "const" is reserved but not valid..removed from modifiers
* Version 1.12 (Feb 2, 1999)
*              Changed LITERAL_xxx to xxx in tree
 grammar.
*              Updated java.g to use tokens {...} now for 2.6.0 (new feature).
*
* Version 1.13 (Apr 23, 1999)
*              Didn't have (stat)? for else clause in tree parser.
*              Didn't gen ASTs for interface extends.  Updated tree parser too.
*              Updated to 2.6.0.
* Version 1.14 (Jun 20, 1999)
*              Allowed final/abstract on local classes.
*              Removed local interfaces from methods
*              Put instanceof precedence where it belongs...in relationalExpr
*                   It also had expr not type as arg; fixed it.
*              Missing ! on SEMI in classBlock
*              fixed: (expr) + "string" was parsed incorrectly (+ as unary plus).
*              fixed: didn't like Object[].class in parser or tree parser
* Version 1.15 (Jun 26, 1999)
*              Screwed up rule with instanceof in it. :(  Fixed.
*              Tree parser didn't like (expr).something; fixed.
*              Allowed multiple inheritance
 in tree grammar. oops.
* Version 1.16 (August 22, 1999)
*              Extending an interface built a wacky tree: had extra EXTENDS.
*              Tree grammar didn't allow multiple superinterfaces.
*              Tree grammar didn't allow empty var initializer: {}
* Version 1.17 (October 12, 1999)
*              ESC lexer rule allowed 399 max not 377 max.
```

```
*            java.tree.g didn't handle the expression of synchronized
*            statements.
* Version 1.18 (August 12, 2001)
*            Terence updated to Java 2 Version 1.3 by
*            observing/combining work of Allan Jacobs and Steve
*            Messick.  Handles 1.3 src.  Summary:
*            o  primary didn't include boolean.class kind of thing
*            o  constructor calls parsed explicitly now:
*              see explicitConstructorInvocation
*            o  add strictfp modifier
*            o  missing objBlock after new expression in tree grammar
*            o
  merged local class definition alternatives, moved after declaration
*            o  fixed problem with ClassName.super.field
*            o  reordered some alternatives to make things more efficient
*            o  long and double constants were not differentiated from int/float
*            o  whitespace rule was inefficient: matched only one char
*            o  add an examples directory with some nasty 1.3 cases
*            o  made Main.java use buffered IO and a Reader for Unicode support
*            o  supports UNICODE?
*              Using Unicode charVocabulary makes code file big, but only
*              in the bitsets at the end. I need to make ANTLR generate
*              unicode bitsets more efficiently.
* Version 1.19 (April 25, 2002)
*            Terence added in nice fixes by John Pybus concerning floating
*            constants and problems with super() calls.  John did a nice
*            reorg of the primary/postfix expression
 stuff to read better
*            and makes f.g.super() parse properly (it was METHOD_CALL not
*            a SUPER_CTOR_CALL).  Also:
*
*            o  "finally" clause was a root...made it a child of "try"
*            o  Added stuff for asserts too for Java 1.4, but *commented out*
*              as it is not backward compatible.
*
* Version 1.20 (October 27, 2002)
*
*       Terence ended up reorging John Pybus' stuff to
*       remove some nondeterminisms and some syntactic predicates.
*       Note that the grammar is stricter now; e.g., this(...) must
*      be the first statement.
*
*       Trinary ?: operator wasn't working as array name:
*             (isBig ? bigDigits : digits)[i];
*
*       Checked parser/tree parser on source for
*             Resin-2.0.5, jive-2.1.1, jdk 1.3.1, Lucene, antlr 2.7.2a4,
*            and the 110k-line jGuru server source.
```

```
*
* Version 1.21 (October 17, 2003)
*  Fixed lots of problems including:
 *  Ray Waldin: add typeDefinition to interfaceBlock in java.tree.g
*  He found a problem/fix with floating point that start with 0
*  Ray also fixed problem that (int.class) was not recognized.
*  Thorsten van Ellen noticed that \n are allowed incorrectly in strings.
*  TJP fixed CHAR_LITERAL analogously.
*
* Version 1.21.2 (March, 2003)
*       Changes by Matt Quail to support generics (as per JDK1.5/JSR14)
*       Notes:
*       o We only allow the "extends" keyword and not the "implements"
*           keyword, since that's what JSR14 seems to imply.
*       o Thanks to Monty Zukowski for his help on the antlr-interest
*           mail list.
*       o Thanks to Alan Eliasen for testing the grammar over his
*           Fink source base
*
* Version 1.22 (July, 2004)
*       Changes by Michael Studman to support Java 1.5 language extensions
*       Notes:
*       o Added support for annotations types
*       o Finished off Matt Quail's generics
 enhancements to support bound type arguments
*       o Added support for new for statement syntax
*       o Added support for static import syntax
*       o Added support for enum types
*       o Tested against JDK 1.5 source base and source base of jdigraph project
*       o Thanks to Matt Quail for doing the hard part by doing most of the generics work
*
* Version 1.22.1 (July 28, 2004)
*       Bug/omission fixes for Java 1.5 language support
*       o Fixed tree structure bug with classOrInterface - thanks to Pieter Vangorpto for
*           spotting this
*       o Fixed bug where incorrect handling of SR and BSR tokens would cause type
*           parameters to be recognised as type arguments.
*       o Enabled type parameters on constructors, annotations on enum constants
*           and package definitions
*       o Fixed problems when parsing if ((char.class.equals(c))) {} - solution by Matt Quail at Cenqua
*
* Version 1.22.2 (July 28, 2004)
 *       Slight refactoring of Java 1.5 language support
*       o Refactored for/"foreach" productions so that original literal "for" literal
*         is still used but the for sub-clauses vary by token type
*       o Fixed bug where type parameter was not included in generic constructor's branch of AST
*
* Version 1.22.3 (August 26, 2004)
```

```
*       Bug fixes as identified by Michael Stahl; clean up of tabs/spaces
*       and other refactorings
*       o Fixed typeParameters omission in identPrimary and newStatement
*       o Replaced GT reconcilliation code with simple semantic predicate
*       o Adapted enum/assert keyword checking support from Michael Stahl's java15 grammar
*       o Refactored typeDefinition production and field productions to reduce duplication
*
* Version 1.22.4 (October 21, 2004)
*    Small bux fixes
*    o Added typeArguments to explicitConstructorInvocation, e.g. new <String>MyParameterised()
*    o Added typeArguments to postfixExpression
 productions for anonymous inner class super
*      constructor invocation, e.g. new Outer().<String>super()
*    o Fixed bug in array declarations identified by Geoff Roy
*
* Version 1.22.4.g.1
*    o I have taken java.g for Java1.5 from Michael Studman (1.22.4)
*      and have applied the groovy.diff from java.g (1.22) by John Rose
*      back onto the new root (1.22.4) - Jeremy Rayner (Jan 2005)
*
* Version 1.22.4.g.2
*    o mkempf, rkleeb, Dec 2007
*    o fixed various rules so that they call the correct Create Method
*      to make sure that the line information are correct
*
* Based on an original grammar released in the PUBLIC DOMAIN
*/

Found in path(s):
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/parser/GroovyRecognizer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2011 Google Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/util/concurrent/concurrentlinkedhashmap/package-info.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/util/concurrent/concurrentlinkedhashmap/LinkedDeque.java
No license file was found, but licenses were detected in source scan.

/** Java 1.5 Recognizer
*
* Run 'java Main [-showtree] directory-full-of-java-files'
*
* [The -showtree option pops up a Swing frame that shows
* the AST constructed from the parser.]
*
* Run 'java Main <directory full of java files>'
*
* Contributing authors:
*   Jeremy Rayner   groovy@ross-rayner.com
* John Mitchell johnm@non.net
* Terence Parr parrt@magelang.com
* John Lilley jlilley@empathy.com
* Scott Stanchfield thetick@magelang.com
* Markus Mohnen mohnen@informatik.rwth-aachen.de
* Peter Williams pete.williams@sun.com
* Allan Jacobs Allan.Jacobs@eng.sun.com
* Steve Messick messick@redhills.com
* John Pybus john@pybus.org
*
* Version 1.00 December 9, 1997 -- initial release
* Version 1.01 December 10, 1997
* fixed bug in octal def (0..7 not 0..8)
* Version 1.10 August 1998 (parrt)
* added tree construction
* fixed definition of WS,comments for mac,pc,unix newlines
 * added unary plus
* Version 1.11 (Nov 20, 1998)
* Added "shutup" option to turn off last ambig warning.
* Fixed inner class def to allow named class defs as statements
* synchronized requires compound not simple statement
* add [] after builtInType DOT class in primaryExpression
* "const" is reserved but not valid..removed from modifiers
* Version 1.12 (Feb 2, 1999)
* Changed LITERAL_xxx to xxx in tree grammar.
* Updated java.g to use tokens {...} now for 2.6.0 (new feature).
*
* Version 1.13 (Apr 23, 1999)
* Didn't have (stat)? for else clause in tree parser.
* Didn't gen ASTs for interface extends. Updated tree parser too.
* Updated to 2.6.0.
* Version 1.14 (Jun 20, 1999)

* Allowed final/abstract on local classes.
* Removed local interfaces from methods
* Put instanceof precedence where it belongs...in relationalExpr
*   It also had expr not type as arg; fixed it.
* Missing ! on SEMI in classBlock
* fixed: (expr) + "string" was parsed incorrectly
 (+ as unary plus).
* fixed: didn't like Object[].class in parser or tree parser
* Version 1.15 (Jun 26, 1999)
* Screwed up rule with instanceof in it. :(Fixed.
* Tree parser didn't like (expr).something; fixed.
* Allowed multiple inheritance in tree grammar. oops.
* Version 1.16 (August 22, 1999)
* Extending an interface built a wacky tree: had extra EXTENDS.
* Tree grammar didn't allow multiple superinterfaces.
* Tree grammar didn't allow empty var initializer: {}
* Version 1.17 (October 12, 1999)
* ESC lexer rule allowed 399 max not 377 max.
* java.tree.g didn't handle the expression of synchronized
* statements.
* Version 1.18 (August 12, 2001)
*   Terence updated to Java 2 Version 1.3 by
* observing/combining work of Allan Jacobs and Steve
* Messick. Handles 1.3 src. Summary:
* o primary didn't include boolean.class kind of thing
*   o constructor calls parsed explicitly now:
*   see explicitConstructorInvocation
* o add strictfp
 modifier
*   o missing objBlock after new expression in tree grammar
* o merged local class definition alternatives, moved after declaration
* o fixed problem with ClassName.super.field
*   o reordered some alternatives to make things more efficient
* o long and double constants were not differentiated from int/float
* o whitespace rule was inefficient: matched only one char
* o add an examples directory with some nasty 1.3 cases
* o made Main.java use buffered IO and a Reader for Unicode support
* o supports UNICODE?
*   Using Unicode charVocabulay makes code file big, but only
*   in the bitsets at the end. I need to make ANTLR generate
*   unicode bitsets more efficiently.
* Version 1.19 (April 25, 2002)
* Terence added in nice fixes by John Pybus concerning floating
* constants and problems with super() calls. John did a nice
* reorg of the primary/postfix expression stuff to read better
* and makes f.g.super() parse properly (it was
 METHOD_CALL not
* a SUPER_CTOR_CALL). Also:

```
*
*  o  "finally" clause was a root...made it a child of "try"
*  o  Added stuff for asserts too for Java 1.4, but *commented out*
*     as it is not backward compatible.
*
* Version 1.20 (October 27, 2002)
*
*   Terence ended up reorging John Pybus' stuff to
*   remove some nondeterminisms and some syntactic predicates.
*   Note that the grammar is stricter now; e.g., this(...) must
* be the first statement.
*
*   Ternary ?: operator wasn't working as array name:
*    (isBig ? bigDigits : digits)[i];
*
*   Checked parser/tree parser on source for
*    Resin-2.0.5, jive-2.1.1, jdk 1.3.1, Lucene, antlr 2.7.2a4,
*  and the 110k-line jGuru server source.
*
* Version 1.21 (October 17, 2003)
*  Fixed lots of problems including:
*  Ray Waldin: add typeDefinition to interfaceBlock in java.tree.g
*  He found a problem/fix with floating point that start with 0
*  Ray also fixed problem that (int.class) was not recognized.
 *  Thorsten van Ellen noticed that \n are allowed incorrectly in strings.
*  TJP fixed CHAR_LITERAL analogously.
*
* Version 1.21.2 (March, 2003)
*   Changes by Matt Quail to support generics (as per JDK1.5/JSR14)
*   Notes:
*   o We only allow the "extends" keyword and not the "implements"
*  keyword, since that's what JSR14 seems to imply.
*   o Thanks to Monty Zukowski for his help on the antlr-interest
*  mail list.
*   o Thanks to Alan Eliasen for testing the grammar over his
*  Fink source base
*
* Version 1.22 (July, 2004)
*   Changes by Michael Studman to support Java 1.5 language extensions
*   Notes:
*   o Added support for annotations types
*   o Finished off Matt Quail's generics enhancements to support bound type arguments
*   o Added support for new for statement syntax
*   o Added support for static import syntax
*   o Added support for enum types
*   o Tested against JDK 1.5 source base and source base of jdigraph project
*   o Thanks to Matt Quail
```

for doing the hard part by doing most of the generics work
*
* Version 1.22.1 (July 28, 2004)
* Bug/omission fixes for Java 1.5 language support
* o Fixed tree structure bug with classOrInterface - thanks to Pieter Vangorpto for
* spotting this
* o Fixed bug where incorrect handling of SR and BSR tokens would cause type
* parameters to be recognised as type arguments.
* o Enabled type parameters on constructors, annotations on enum constants
* and package definitions
* o Fixed problems when parsing if ((char.class.equals(c))) {} - solution by Matt Quail at Cenqua
*
* Version 1.22.2 (July 28, 2004)
* Slight refactoring of Java 1.5 language support
* o Refactored for/"foreach" productions so that original literal "for" literal
* is still used but the for sub-clauses vary by token type
* o Fixed bug where type parameter was not included in generic constructor's branch of AST
*
* Version 1.22.3 (August 26, 2004)
* Bug fixes as identified by Michael
Stahl; clean up of tabs/spaces
* and other refactorings
* o Fixed typeParameters omission in identPrimary and newStatement
* o Replaced GT reconciliation code with simple semantic predicate
* o Adapted enum/assert keyword checking support from Michael Stahl's java15 grammar
* o Refactored typeDefinition production and field productions to reduce duplication
*
* Version 1.22.4 (October 21, 2004)
* Small bux fixes
* o Added typeArguments to explicitConstructorInvocation, e.g. new <String>MyParameterised()
* o Added typeArguments to postfixExpression productions for anonymous inner class super
* constructor invocation, e.g. new Outer().<String>super()
* o Fixed bug in array declarations identified by Geoff Roy
*
* Version 1.22.4.j.1
* Changes by Jeremy Rayner to support java2groovy tool
* o I have taken java.g for Java1.5 from Michael Studman (1.22.4)
* and have made some changes to enable use by java2groovy tool (Jan 2007)
*
* Based on an original grammar released in the PUBLIC DOMAIN
*/

Found in path(s):
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/java/JavaRecognizer.java
No license file was found, but licenses were detected in source scan.

Licensed to the Apache Software Foundation (ASF) under one
or more contributor license agreements. See the NOTICE file

distributed with this work for additional information
regarding copyright ownership. The ASF licenses this file
to you under the Apache License, Version 2.0 (the
"License"); you may not use this file except in compliance
with the License. You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE
2.0

Unless required by applicable law or agreed to in writing,
software distributed under the License is distributed on an
"AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY
KIND, either express or implied. See the License for the
specific language governing permissions and limitations
under the License.

Found in path(s):
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/io/package.html
* /groovy-3-0-8-sources-1-jar/groovy/io/package.html
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/xml/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/wrappers/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/package.html
* /groovy-3-0-8-sources-1-jar/groovy/inspect/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/javac/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/package.html
* /groovy-3-0-8-sources-1-jar/groovy/time/package.html
* /groovy-3-0-8-sources-1-jar/groovy/security/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/messages/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/package.html
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/package.html
* /groovy-3-0-8-sources-1-jar/groovy/lang/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/typehandling/package.html
* /groovy-3-0-8-sources-1-jar/groovy/grape/defaultGrapeConfig.xml
* /groovy-3-0-8-sources-1-jar/overview.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/syntax/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/package.html
* /groovy-3-0-8-sources-1-jar/overviewj.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v5/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/package.html

* /groovy-3-0-8-sources-1-jar/groovy/util/package.html
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/treewalker/package.html
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one
* or more contributor license agreements. See the NOTICE file
* distributed with this work for additional information
* regarding copyright ownership. The ASF licenses this file
* to you under the Apache License, Version 2.0 (the
* "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing,
* software distributed under the License is distributed on an
* "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY
* KIND, either express or implied. See the License for the
* specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/IntArrayIterator.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/MetaClassRegistryChangeEventListener.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/customizers/SourceAwareCustomizer.java
* /groovy-3-0-8-sources-1-jar/groovy/util/MapEntry.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/m12n/SimpleExtensionModule.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/ListExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/DelegateASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/ExtendedVerifier.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/GroovyObjectSupport.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/ByteArrayPutAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/messages/Message.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/MissingPropertyExceptionNoStack.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/PropertyAccessInterceptor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/shell/util/Logger.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/BooleanArrayPutAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/MethodCall.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/EnumHelper.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/AdaptingMetaClass.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/ReadOnlyPropertyException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/AssertStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/sc/StaticTypesClosureWriter.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/metaclass/Realm.java

* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/javac/JavacJavaCompiler.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/NullCheckASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/IntegerCachedClass.java
* /groovy-3-0-8-sources-1-jar/groovy/util/BuilderSupport.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/ASTRuntimeException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/transformers/CastExpressionOptimizer.java
* /groovy-3-0-8-sources-1-jar/groovy/ui/GroovySocketServer.java
* /groovy-3-0-8-sources-1-jar/groovy/util/IFileNameFinder.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/trait/TraitASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/DynamicVariable.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/stc/SecondParam.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/AbstractConcurrentMap.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/ASTTest.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/SpreadMapEvaluatingException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/ASTTransformationCollectorCodeVisitor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/javac/RawJavaFileObject.java
*
/groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/AbstractLexer.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/BooleanCachedClass.java
* /groovy-3-0-8-sources-1-
jar/org/codehaus/groovy/control/customizers/builder/SourceAwareCustomizerFactory.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/EmptyExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v5/Java5.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/MethodPointerExpressionWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/SortableASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/internal/metaclass/MetaClassConstant.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/SocketGroovyMethods.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/builder/ExternalStrategy.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/CallSiteGenerator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v5/JUnit4Utils.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/GroovySourceAST.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/GetEffectivePogoPropertySite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/LoopingStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/transformers/ListExpressionTransformer.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/syntax/TokenException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/java/Java2GroovyConverter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/NewMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/BinaryExpressionHelper.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/IncorrectClosureArgumentsException.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/ExternalizeMethods.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/ModifierManager.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/IntegerArrayPutAtMetaMethod.java
*
/groovy-3-0-8-sources-1-jar/groovy/security/GroovyCodeSourcePermission.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/MethodSelectionException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/ImmutableASTTransformation.java

* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/trait/TraitReceiverTransformer.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/MetaClassRegistry.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/ThreadInterruptibleASTTransformation.groovy
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/plugin/DefaultRunners.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/BytecodeDumper.java
* /groovy-3-0-8-sources-1-jar/groovy/util/FactoryBuilderSupport.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/v7/GroovyClassValueJava7.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/IteratorBufferedIterator.java
*
/groovy-3-0-8-sources-1-jar/org/apache/groovy/util/concurrent/LazyInitializable.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/wrappers/ByteWrapper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/m12n/PropertiesModuleFactory.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/ResourceGroovyMethods.java
* /groovy-3-0-8-sources-1-jar/groovy/cli/TypedOption.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/SignatureCodecVersion1.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/PropertyOptions.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/NewifyASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/tailrec/ReturnStatementToIterationConverter.groovy
* /groovy-3-0-8-sources-1-jar/groovy/transform/builder/InitializerStrategy.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/builder/AstSpecificationCompiler.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/CharacterArrayPutAtMetaMethod.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/EncodingGroovyMethods.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/EmptyRange.java
* /groovy-3-0-8-sources-1-jar/groovy/cli/OptionField.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/sc/StaticInvocationWriter.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/groovydoc/Groovydoc.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/ClosureExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/LongArrayGetAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/CompileDynamicProcessor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v7/TypeTransformers.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/EnumConstantClassNode.java
* /groovy-3-0-8-sources-1-jar/groovy/util/logging/Log4j.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/decompiled/LazyFieldNode.java
*
/groovy-3-0-8-sources-1-
jar/org/codehaus/groovy/control/customizers/builder/ASTTransformationCustomizerFactory.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/BlockStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v7/MethodHandleWrapper.java
* /groovy-3-0-8-sources-1-jar/groovy/io/PlatformLineWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/VerifierCodeVisitor.java
* /groovy-3-0-8-sources-1-jar/groovy/util/PermutationGenerator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/ComposedClosure.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/lang/annotation/Incubating.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/ArrayGetAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/groovy/time/BaseDuration.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/java/Groovifier.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/StaticCompileTransformation.java

*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/TypeChooser.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/MethodCallExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/syntax/SyntaxException.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/ast/tools/ImmutablePropertyUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/util/TypeUtil.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/customizers/ImportCustomizer.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/MethodKey.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/powerassert/ValueRecorder.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/UnaryPlusExpression.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple8.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/builder/Builder.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/wrappers/IntWrapper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/GeneratedClosure.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/indy/sc/IndyStaticTypesMultiTypeDispatcher.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/StaticCompilationMetadataKeys.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple3.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/BinaryDoubleExpressionHelper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/LambdaExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/FastArray.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/SpreadListEvaluatingException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/SharedVariableCollector.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/decompiled/ClassStub.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/tools/ParameterUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/DefaultCachedMethodKey.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Script.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/CachedClosureClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/MultipleSetterProperty.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/AnnotationNode.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/ExpressionStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/UnicodeEscapingReader.java
* /groovy-3-0-8-sources-1-jar/groovy/util/ConfigSlurper.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/AnnotatedNode.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/ParameterArray.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/InterfaceHelperClassNode.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/CategoryASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/ScriptReference.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/GetEffectivePojoFieldSite.java
*
 /groovy-3-0-8-sources-1-jar/groovy/util/ResourceConnector.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/sc/StaticTypesWriterController.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/StatementMetaTypeChooser.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/treewalker/TraversalHelper.java
* /groovy-3-0-8-sources-1-jar/groovy/util/NodePrinter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/ReadWriteLockASTTransformation.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/GrabConfig.java

* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ReferenceManager.java
* /groovy-3-0-8-sources-1-jar/groovy/cli/Unparsed.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/ClassExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/InheritConstructorsASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/CastExpression.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/KnownImmutable.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/ScriptBytecodeAdapter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/BinaryLongExpressionHelper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/tailrec/VariableAccessReplacer.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v8/Selector.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/SecondPassExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/CachedClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/memoize/LRUCache.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/TemporaryMethodKey.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/CompilationUnitAware.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/syntax/ASTHelper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/transformers/StaticCompilationTransformer.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/MethodNode.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/trait/NAryOperationRewriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/InnerClassVisitor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/GeneratedMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/EmptyStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/decompiled/LazyConstructorNode.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/PrefixExpression.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/internal/util/UncheckedThrow.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/decompiled/DecompiledClassNode.java
* /groovy-3-0-8-sources-1-jar/groovy/beans/ListenerList.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/DefaultGroovyStaticMethods.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/NamedParams.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/ArrayExpression.java
*
 /groovy-3-0-8-sources-1-jar/org/apache/groovy/util/Maps.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/MetaClassRegistryChangeEvent.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/tools/ClosureUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/io/NullWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/NotExpression.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/options/Visibility.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/customizers/builder/PostCompletionFactory.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/VisibilityOptions.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/Field.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/memoize/NullProtectionStorage.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/messages/SyntaxErrorMessage.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/StaticMetaClassSite.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/util/ObjectHolder.java
*

/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/DelegatingController.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/HandleMetaClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/MethodCallTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/MethodInvocationTrap.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/util/StringUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/ParserPlugin.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/ArrayUtil.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/BytecodeProcessor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/WhileStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/typehandling/IntegerMath.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/Finalizable.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/messages/SimpleMessage.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/InnerClassNode.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/ParserPluginFactory.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/EncodingGroovyMethodsSupport.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/TraitTypeCheckingExtension.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/treewalker/PreOrderTraversal.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/BooleanArrayIterator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/javac/JavaAwareResolveVisitor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/NumberNumberPlus.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/LazyASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/BaseScriptASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/PogoMetaClassSite.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/GroovySourceToken.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/ProxyMetaClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/AbstractASTTransformUtil.java
* /groovy-3-0-8-sources-1-jar/groovy/util/DelegatingScript.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/ConvertedMap.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/AutoCloneASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/NumberNumberMinus.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/NumberNumberDiv.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/AbstractConcurrentMapBase.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ByteArrayIterator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/AntlrParserPlugin.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/DoWhileStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/typehandling/NumberMath.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/AbstractComparator.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/plugin/GroovyRunner.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ReferenceBundle.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/MultipleCompilationErrorsException.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/MutableMetaClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/TupleConstructorASTTransformation.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/groovydoc/GroovydocTag.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/SynchronizedASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/CompilePhase.java

* /groovy-3-0-8-sources-1-jar/groovy/util/ClosureComparator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/treewalker/CompositeVisitor.java
* /groovy-3-0-8-sources-1-jar/groovy/cli/UnparsedField.groovy
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/CompilationUnit.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/DoubleArrayPutAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v6/Java6.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/Reference.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/shell/util/Preferences.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/customizers/builder/InlinedASTCustomizerFactory.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/sc/StaticTypesStatementWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/ConstructorSite.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/GroovySystem.java
* /groovy-3-0-8-sources-1-
jar/org/codehaus/groovy/transform/sc/transformers/StaticMethodCallExpressionTransformer.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/EnumVisitor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/GroovyException.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/messages/LocatedMessage.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/WritableFile.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/CompileUnit.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/StringBufferWriter.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/PropertyValue.java
* /groovy-3-0-8-sources-1-jar/groovy/util/IndentPrinter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/io/ReaderSource.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/trait/Traits.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/antlr/LexerFrame.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/MopWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/customizers/builder/CustomizersFactory.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple1.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/CurriedClosure.java
*
 /groovy-3-0-8-sources-1-jar/groovy/lang/ExpandoMetaClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ManagedConcurrentMap.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/InnerClassVisitorHelper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/memoize/StampedCommonCache.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/TryCatchStatement.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/groovydoc/GroovydocHolder.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/ErrorCollector.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ReferenceType.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/m12n/ExtensionModule.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/SingletonASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/MethodCaller.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/StringUtil.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/decompiled/ClassSignatureParser.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/sc/StaticTypesTypeChooser.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/BenchmarkInterceptor.java

* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/indy/IndyCallSiteWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/ErrorReporter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/ClassInfo.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/stc/IncorrectTypeHintException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/Reflector.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/internal/atnmanager/ParserAtnManager.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/IfStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/DoubleCachedClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/ListOfExpressionsExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/AstToTextHelper.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/AbstractInterruptibleASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/BooleanReturningMethodInvoker.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/PackageNode.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/FieldNode.java
* /groovy-3-0-8-sources-1-jar/groovy/beans/PropertyWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/VariableScopeVisitor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/treewalker/VisitorAdapter.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/PackageScope.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/AutoImplementASTTransformation.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple7.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Closure.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/UnaryExpressionHelper.java
*
/groovy-3-0-8-sources-1-jar/groovy/lang/GroovyObject.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/options/DefaultPropertyHandler.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/TripleKeyHashMap.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/DelegatesTo.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/genDgmMath.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/LexerFrame.java
* /groovy-3-0-8-sources-1-jar/groovy/io/EncodingAwareBufferedWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/LineColumn.java
* /groovy-3-0-8-sources-1-jar/groovy/beans/PropertyReader.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/javac/JavaStubCompilationUnit.java
* /groovy-3-0-8-sources-1-jar/groovy/grape/GrabAnnotationTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/ExtensionMethodCache.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/NamedVariant.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/GenericsVisitor.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/StatementWriter.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Interceptor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/sc/StaticTypesLambdaWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/ReflectionMethodInvoker.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/SynchronizedStatement.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/GroovyLangParser.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/PrimitiveHelper.java
* /groovy-3-0-8-sources-1-jar/groovy/cli/internal/CliBuilderInternal.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/sc/StaticTypesWriterControllerFactoryImpl.java

* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/gse/StringSetMap.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/CallSiteAwareMetaMethod.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple15.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/memoize/EvictableCache.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/m12n/MetaInfExtensionModule.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/builder/SimpleStrategy.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/syntax/Types.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Binding.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/indy/InvokeDynamicWriter.java
* /groovy-3-0-8-sources-1-jar/groovy/io/FileVisitResult.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/OwnedMetaClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/sc/AbstractFunctionalInterfaceWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/sc/StaticTypesUnaryExpressionHelper.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/ast/tools/ExpressionUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/MixinInstanceMetaProperty.java
*
 /groovy-3-0-8-sources-1-jar/groovy/util/ProxyGenerator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/StaticCompilationVisitor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/CompileStack.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/MethodReferenceExpressionWriter.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/stc/PickAnyArgumentHint.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/MissingMethodExceptionNoStack.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v9/ClassFindFailedException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v7/TypeHelper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/GStringImpl.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple6.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/builder/AstStringCompiler.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple12.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/SourceURI.java
*
 /groovy-3-0-8-sources-1-jar/groovy/transform/ToString.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/FileSystemCompiler.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/javac/JavaAwareCompilationUnit.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/ExpandoMetaClassCreationHandle.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/ClassCompletionVerifier.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/StaticImportVisitor.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple10.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/treewalker/NodeAsHTMLPrinter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/MetaClassConstructorSite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/TypeCheckingExtension.java
* /groovy-3-0-8-sources-1-jar/groovy/beans/ListenerListASTTransformation.groovy
* /groovy-3-0-8-sources-1-jar/groovy/namespace/QName.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v7/IndyGuardsFiltersAndSignatures.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v7/IndyMath.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Singleton.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/ArrayMetaMethod.java

* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/typehandling/FloatingPointMath.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/IntRange.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/transformers/CompareToNullExpression.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/MissingPropertyException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/GroovyASTTransformationClass.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/MissingFieldException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/InstanceOfVerifier.java
* /groovy-3-0-8-sources-1-jar/groovy/cli/internal/OptionAccessor.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/MemoizedASTTransformation.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/Parameter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/LongArrayIterable.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/AbstractASTTransformation.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/ConditionalInterrupt.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/GrapeUtil.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/customizers/SecureASTCustomizer.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/TailRecursive.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/tailrec/AstHelper.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/GeneratedLambda.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/memoize/LRUProtectionStorage.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/PerInstancePojoMetaClassSite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/syntax/Numbers.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/LongArrayIterator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/Main.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/IndexedPropertyASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/ClosureListExpression.java
* /groovy-3-0-8-sources-1-jar/groovy/beans/Vetoable.java
* /groovy-3-0-8-sources-1-jar/groovy/beans/BindableASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/ast/TransformTestHelper.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/MetaClassHelper.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/ClosureInvokingMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/ContinueStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/ClassNodeResolver.java
* /groovy-3-0-8-sources-1-jar/groovy/io/FileType.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/AstBuilder.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/BreakStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/AnnotationConstantsVisitor.java
* /groovy-3-0-8-sources-1-jar/groovy/util/logging/Log.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/SourceExtensionHandler.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/ConstructorCallExpression.java
* /groovy-3-0-8-sources-1-jar/groovy/util/BufferedIterator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/BytecodeInterface8.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/stc/PickFirstResolver.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/powerassert/AssertionRenderer.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/GroovyClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/CompilerConfiguration.java

* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/DoubleArrayIterator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/wrappers/CharWrapper.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/MetaMethodSite.java
* /groovy-3-0-8-sources-1-jar/groovy/util/Proxy.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/GroovySunClassLoader.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/ObjectArrayPutAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/PropertyNode.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/ExternalizeVerifier.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/shell/IO.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/PogoMetaClassGetPropertySite.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/AutoFinal.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/CompilationFailedException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/GeneratorContext.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/memoize/ProtectionStorage.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/FloatArrayPutAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/ByteArrayGetAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/tailrec/StatementReplacer.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/VMPluginFactory.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/FloatCachedClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/SourceUnit.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/ExpressionAsVariableSlot.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/PackageScopeTarget.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Lazy.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/Memoized.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/javac/MemJavaFileObject.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/treewalker/SourceCodeTraversal.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/ByteCachedClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/ASTTransformation.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/BaseScript.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ManagedLinkedList.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/PropertyLookupVisitor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/treewalker/MindMapPrinter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/ModuleNode.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/ASTTestTransformation.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/UnionTypeClassNode.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/StringCachedClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/NamedVariantASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/ExpressionTransformer.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/BooleanExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/ASTTransformationVisitor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/IntArrayIterable.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/CallSite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/typehandling/GroovyCastException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/DefaultMethodKey.java

* /groovy-3-0-8-sources-1-jar/groovy/lang/Range.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/TransformMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/ArgumentListExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/MixinInMetaClass.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/MetaBeanProperty.java
* /groovy-3-0-8-sources-1-jar/groovy/util/AbstractFactory.java
*
/groovy-3-0-8-sources-1-jar/groovy/lang/TrampolineClosure.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/DelegationMetadata.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/GString.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Mixin.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/RegexSupport.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/CallSiteWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/ObjectArrayGetAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/InvokerInvocationException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/DefaultGroovyMethodsSupport.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/SourceBuffer.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/sc/StaticPropertyAccessHelper.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/io/StringBuilderWriter.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/CompileStatic.java
*
/groovy-3-0-8-sources-1-jar/groovy/transform/AutoImplement.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/GroovyResourceLoader.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/ClosureMetaClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/trait/SuperCallTraitTransformer.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/InheritConstructors.java
* /groovy-3-0-8-sources-1-jar/groovy/beans/Bindable.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/stc/SingleSignatureClosureHint.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/MethodMetaProperty.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/util/ScriptRunner.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/transformers/ConstructorCallTransformer.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/syntax/ParserException.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/builder/DefaultStrategy.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/stc/ClosureParams.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/Phases.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/genMathModification.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ManagedReference.java
* /groovy-3-0-8-sources-1-jar/groovy/util/logging/Commons.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/GroovyInterceptable.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/AutoFinalASTTransformation.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/NullCheck.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v7/Selector.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/customizers/builder/SecureASTCustomizerFactory.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/BytecodeExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/MethodHelper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/powerassert/Value.java
*

/groovy-3-0-8-sources-1-jar/groovy/lang/ObjectRange.java
* /groovy-3-0-8-sources-1-jar/groovy/util/NodeList.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/powerassert/SourceTextNotAvailableException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/java/Java2GroovyProcessor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/TimedInterruptibleASTTransformation.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/ExternalizeVerifierASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/tools/PropertyNodeUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/typehandling/ShortTypeHandling.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/StackTraceUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/wrappers/GroovyObjectWrapper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/PackageScopeASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/BinaryFloatExpressionHelper.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/RangeInfo.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/PositionInfo.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/transformers/CompareIdentityExpression.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/GroovyCodeSource.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/ReflectionUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/javac/JavaStubGenerator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/CallSiteClassLoader.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/ast/tools/ClassNodeUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/sc/StaticCompilationMopWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/ClassCodeVisitorSupport.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/MixinASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/syntax/CSTNode.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/NamedArgumentListExpression.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple14.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/BinaryExpressionMultiTypeDispatcher.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/IntegerArrayGetAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/ImmutableBase.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/CaseStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/decompiled/MemberSignatureParser.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/java/PreJava2GroovyConverter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/ProcessingUnit.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/util/LoggableTextifier.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/transformers/VariableExpressionTransformer.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/syntax/Reduction.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/MetaMethodIndex.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/io/AbstractReaderSource.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ListHashMap.java
* /groovy-3-0-8-sources-1-jar/groovy/util/GroovyScriptEngine.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/decompiled/Annotations.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/decompiled/FormalParameterParser.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/decompiled/LazyMethodNode.java
* /groovy-3-0-8-sources-1-jar/groovy/beans/DefaultPropertyWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/memoize/ValueConvertable.java

* /groovy-3-0-8-sources-1-jar/groovy/transform/AnnotationCollector.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/AntlrParserPluginFactory.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/tools/BeanUtils.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/tailrec/VariableExpressionTransformer.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/BooleanArrayGetAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/groovy/beans/DefaultPropertyReader.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/memoize/UnlimitedConcurrentCache.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/StaticMethodCallExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/DgmConverter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/SwitchStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/BinaryExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/NumberCachedClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v7/Java7.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/ClosureMetaMethod.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/UnicodeLexerSharedInputState.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/NonEmptySequence.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/ForStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/WriterControllerFactory.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/GroovyBugError.java
* /groovy-3-0-8-sources-1-jar/groovy/beans/VetoableASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/BinaryObjectExpressionHelper.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple9.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/DeprecationException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/ExternalizeMethodsASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/android/AndroidSupport.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/StaticMetaMethodSite.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/util/BeanUtils.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/ConstructorMetaClassSite.java
* /groovy-3-0-8-sources-1-jar/groovy/time/TimeCategory.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/DeclarationExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/wrappers/ShortWrapper.java
* /groovy-3-0-8-sources-1-jar/groovy/util/logging/Slf4j.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/WriterController.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v9/Java9.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/DefaultGroovyMethods.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/Verifier.java
* /groovy-3-0-8-sources-1-
jar/org/codehaus/groovy/control/customizers/builder/CompilerCustomizationBuilder.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/ClassNode.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/io/StringReaderSource.java
*
 /groovy-3-0-8-sources-1-jar/org/apache/groovy/util/Arrays.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/m12n/ExtensionModuleRegistry.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/tailrec/CollectRecursiveCalls.groovy
* /groovy-3-0-8-sources-1-jar/groovy/transform/WithWriteLock.java

* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/tools/ClassNodeUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/builder/AstBuilderTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/powerassert/PowerAssertionError.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ManagedConcurrentValueMap.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/LongArrayPutAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/Immutable.groovy
* /groovy-3-0-8-sources-1-jar/groovy/lang/SpreadMap.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/VariableSlotLoader.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/shell/util/MessageSource.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/io/InputStreamReaderSource.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/Generated.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/TryWithResourcesASTTransformation.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/Trait.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/LambdaWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/GroovyClassValueFactory.java
* /groovy-3-0-8-sources-1-jar/groovy/xml/QName.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/StaticVerifier.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/util/SystemUtil.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/ArrayCachedClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/TypeCheckingContext.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/PojoMetaMethodSite.java
*
 /groovy-3-0-8-sources-1-jar/groovy/io/GroovyPrintWriter.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple2.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/SemanticPredicates.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/CacheAccessControlException.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/internal/util/Function.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/CharSequenceReader.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/BigIntegerCachedClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/ArrayPutAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/ReflectionMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/GroovyCategorySupport.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/m12n/ExtensionModuleScanner.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Newify.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/BinaryExpressionWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/FieldExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/TemporaryVariableExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/DefaultMetaClassInfo.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/SpreadExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ComplexKeyHashMap.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/StaticTypesTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/BinaryBooleanExpressionHelper.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple11.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple4.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/metaclass/MetaClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/syntax/TokenUtil.java

* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/ImportNode.java
*
 /groovy-3-0-8-sources-1-jar/groovy/lang/GroovyRuntimeException.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Grab.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/stc/ClosureSignatureHint.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v8/Java8.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/ConstructorMetaMethodSite.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/internal/util/Supplier.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/LazyReference.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/Undefined.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/treewalker/NodePrinter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/ThrowStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/wrappers/PojoWrapper.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/GroovyShell.java
* /groovy-3-0-8-sources-1-jar/groovy/util/NodeBuilder.java
*
 /groovy-3-0-8-sources-1-jar/groovy/util/OrderBy.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/PogoInterceptableSite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/AsmClassGenerator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/LoaderConfiguration.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/customizers/ASTTransformationCustomizer.groovy
* /groovy-3-0-8-sources-1-jar/groovy/lang/DelegatingMetaClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/CachedConstructor.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/options/LegacyHashMapPropertyHandler.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/treewalker/SourcePrinter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/util/LoggableClassVisitor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/syntax/ReadException.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/MetaProperty.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/MapEntryExpression.java
*
 /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple16.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/wrappers/FloatWrapper.java
* /groovy-3-0-8-sources-1-jar/groovy/grape/GrapeEngine.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/SignatureCodec.java
* /groovy-3-0-8-sources-1-jar/groovy/util/GroovyCollections.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/IllegalPropertyAccessException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/ConstantExpression.java
* /groovy-3-0-8-sources-1-jar/groovy/util/ObjectGraphBuilder.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/javac/JavaCompilerFactory.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/ElvisOperatorExpression.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/GroovySyntaxError.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/GroovyLangLexer.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/ResolveVisitor.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/syntax/TokenMismatchException.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Buildable.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/memoize/Memoize.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/BinaryIntExpressionHelper.java

* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/tailrec/TernaryToIfStatementConverter.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/NumberNumberMetaMethod.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/CompileDynamic.groovy
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/ast/tools/AnnotatedNodeUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/CachedMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/ClassGenerator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/customizers/builder/ImportCustomizerFactory.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/AssertionWriter.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/GroovyClassValue.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/genArrayAccess.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/StaticTypesMarker.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/ReverseListIterator.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/MetaExpandoProperty.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/AnnotationCollectorMode.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/NamedDelegate.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/RootLoader.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/CallSiteArray.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/StaticTypeCheckingVisitor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/Compiler.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/ConstructorNode.java
*
 /groovy-3-0-8-sources-1-jar/groovy/lang/Sequence.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/SunClassLoader.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/typehandling/NumberMathModificationInfo.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/SingleKeyHashMap.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/gse/DependencyTracker.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/ShortArrayPutAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v7/IndyArrayAccess.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/BytecodeSequence.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/ListWithDefault.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/GStringExpression.java
* /groovy-3-0-8-sources-1-jar/groovy/beans/PropertyAccessor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v8/IndyMath.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v8/TypeTransformers.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/ShortArrayGetAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/memoize/ConcurrentCommonCache.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/Synchronized.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/Internal.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/wrappers/DoubleWrapper.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/internal/util/UnicodeConst.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/MetaClassSite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/AttributeExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/ReturnStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/tailrec/InWhileLoopWrapper.groovy
* /groovy-3-0-8-sources-1-jar/groovy/lang/MapWithDefault.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/EqualsAndHashCode.java

*
 /groovy-3-0-8-sources-1-jar/groovy/util/Factory.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/PlainObjectMetaMethodSite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/VMPlugin.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/InvocationWriter.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Groovydoc.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/IndexedProperty.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/FinalVariableAnalyzer.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/VariableScope.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/MethodPointerExpression.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/ast/tools/MethodNodeUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/GenericsType.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v8/IndyInterface.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ListBufferedIterator.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/GroovyExceptionInterface.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v7/IndyInterface.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/memoize/MemoizeCache.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/HashCodeHelper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/memoize/ConcurrentSoftCache.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/GetEffectivePogoFieldSite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/tailrec/RecursivenessTester.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/HasCleanup.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/ArrayTypeUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/StaticTypeCheckingSupport.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/ast/tools/VisibilityUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/FloatArrayGetAtMetaMethod.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/CachedSAMClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ReleaseInfo.java
* /groovy-3-0-8-sources-1-jar/groovy/io/LineColumnReader.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/WithReadLock.java
* /groovy-3-0-8-sources-1-jar/groovy/util/Eval.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/DoubleArrayGetAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/ObjectCachedClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/wrappers/LongWrapper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/ConvertedClosure.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/BytecodeHelper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/MethodRankHelper.java
* /groovy-3-0-8-sources-1-jar/groovy/time/TimeDuration.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/util/PositionConfigureUtils.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/ClosureWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v8/CacheableCallSite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/ClosureStaticMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/GroovyCodeVisitor.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/stc/FromAbstractTypeMethods.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/Janitor.java

* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/customizers/CompilationCustomizer.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/MetaClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/FlushingStreamWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/MapConstructorASTTransformation.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple0.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/tailrec/VariableExpressionReplacer.groovy
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/BigDecimalCachedClass.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/GrabResolver.java
* /groovy-3-0-8-sources-1-jar/groovy/time/DatumDependentDuration.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/ReturnAdder.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/Expression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/Statement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/StringGroovyMethods.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/decompiled/AsmDecompiler.java
* /groovy-3-0-8-sources-1-jar/groovy/util/ScriptException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/ExtensionMethodNode.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/DummyCallSite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/messages/WarningMessage.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/ASTTransformationsContext.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/AbstractCallSite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/DefaultTypeCheckingExtension.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/MapExpression.java
* /groovy-3-0-8-sources-1-jar/groovy/util/ObservableMap.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/plugin/GroovyRunnerRegistry.java
* /groovy-3-0-8-sources-1-jar/groovy/beans/DefaultPropertyAccessor.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/stc/FirstParam.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/BuilderASTTransformation.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/SelfType.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/typehandling/BigDecimalMath.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/AbstractParser.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/DummyClassGenerator.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/NumberNumberMultiply.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/transformers/BinaryExpressionTransformer.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/stc/FromString.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/BooleanClosureWrapper.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/TimedInterrupt.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/FloatArrayIterator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/io/URLReaderSource.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/transformers/ClosureExpressionTransformer.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/LockableObject.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/stc/ClosureSignatureConflictResolver.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/CodeVisitorSupport.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/options/PropertyHandler.java
*

/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/SourceURIASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/OptimizingStatementWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/LogASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/DoubleArrayIterable.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/NewStaticMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/LongCachedClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/TupleExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/PogoGetPropertySite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/IOGroovyMethods.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Writable.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/ConditionalInterruptibleASTTransformation.groovy
*
/groovy-3-0-8-sources-1-jar/groovy/transform/Canonical.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/stmt/CatchStatement.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/EnumCompletionVisitor.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/ClosureException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/ProcessGroovyMethods.java
* /groovy-3-0-8-sources-1-jar/groovy/util/ConfigObject.java
* /groovy-3-0-8-sources-1-
jar/org/codehaus/groovy/classgen/asm/sc/StaticTypesMethodReferenceExpressionWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/Receiver.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/dgmimpl/arrays/CharacterArrayGetAtMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/GetEffectivePojoPropertySite.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/ImmutableOptions.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/MixinInstanceMetaMethod.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/MetaClassRegistryImpl.java
* /groovy-3-0-8-sources-1-jar/groovy/util/Node.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v9/ClassFinder.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/Utilities.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/Sortable.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/TypeCheckingMode.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/messages/ExceptionMessage.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/AntlrASTProcessSnippets.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/treewalker/FlatNodeListTraversal.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/AbstractExtensionMethodCache.java
* /groovy-3-0-8-sources-1-jar/groovy/util/FileNameByRegexFinder.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/ReflectionCache.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/ModifierNode.java
*
/groovy-3-0-8-sources-1-jar/groovy/cli/CliBuilderException.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/ToStringASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/internal/atnmanager/AtnManager.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/NamedParam.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/Antlr4PluginFactory.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple5.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/MetaObjectProtocol.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/MissingMethodExecutionFailed.java

* /groovy-3-0-8-sources-1-jar/groovy/lang/MissingClassException.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/TupleConstructor.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/stc/MapEntryOrKeyValue.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/NullObject.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/ClassMetaClassGetPropertySite.java
*
 /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/SyntaxErrorReportable.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/ParameterTypes.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/CachedField.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/BitwiseNegationExpression.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Grapes.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ShortArrayIterator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/MixinNode.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/MetaClassImpl.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/ConversionHandler.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/MixedInMetaClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/transformers/RangeExpressionTransformer.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/TransformingCodeVisitor.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/typehandling/BigIntegerMath.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v5/PluginDefaultGroovyMethods.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/javac/JavacCompilerFactory.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v8/IndyGuardsFiltersAndSignatures.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/XStreamUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/java/Java2GroovyMain.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/GroovyTypeCheckingExtensionSupport.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/ClassHelper.java
* /groovy-3-0-8-sources-1-jar/groovy/util/logging/Log4j2.java
* /groovy-3-0-8-sources-1-jar/groovy/time/Duration.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/internal/atnmanager/LexerAtnManager.java
*
 /groovy-3-0-8-sources-1-jar/groovy/io/GroovyPrintStream.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/syntax/Token.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/AbstractTypeCheckingExtension.java
* /groovy-3-0-8-sources-1-
jar/org/codehaus/groovy/transform/sc/transformers/MethodCallExpressionTransformer.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/options/ImmutablePropertyHandler.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v8/IndyArrayAccess.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/GroovyStarter.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/TracingInterceptor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/tools/WideningCategories.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/TernaryExpression.java
* /groovy-3-0-8-sources-1-jar/groovy/grape/Grape.java
* /groovy-3-0-8-sources-1-jar/groovy/time/TimeDatumDependentDuration.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/CharArrayIterator.java
*

/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/GrapeMain.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/OptimizerVisitor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/javac/JavaCompiler.java
* /groovy-3-0-8-sources-1-jar/groovy/util/CharsetToolkit.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/tools/GeneralUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/trait/TraitComposer.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/BytecodeInstruction.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/GroovyClassVisitor.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/AutoCloneStyle.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/sc/StaticTypesCallSiteWriter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/typehandling/DefaultTypeTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/PogoMetaMethodSite.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/RangeExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/io/FileReaderSource.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/GroovyASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v8/TypeHelper.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/StringWriterIOException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/AnnotationCollectorTransform.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/ThreadManagedMetaBeanProperty.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/m12n/StandardPropertiesModuleFactory.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/SourceInfo.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/powerassert/SourceText.java
* /groovy-3-0-8-sources-1-
jar/org/codehaus/groovy/classgen/asm/sc/StaticTypesBinaryExpressionMultiTypeDispatcher.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/MethodClosure.java
*
/groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/InvokerHelper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/ShortCachedClass.java
* /groovy-3-0-8-sources-1-jar/groovy/util/ObservableList.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/SpreadMapExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/stc/EnumTypeCheckingExtension.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v8/PluginDefaultGroovyMethods.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/memoize/CommonCache.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/decompiled/AsmReferenceResolver.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/MissingMethodException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/PojoMetaClassGetPropertySite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/AccessPermissionChecker.java
* /groovy-3-0-8-sources-1-jar/groovy/cli/Option.java
*
/groovy-3-0-8-sources-1-jar/org/apache/groovy/internal/util/ReevaluatingReference.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/ConfigurationException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v8/MethodHandleWrapper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/VariableExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ManagedConcurrentLinkedQueue.java
* /groovy-3-0-8-sources-1-jar/groovy/inspect/Inspector.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/typehandling/LongMath.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/Antlr4ParserPlugin.java

* /groovy-3-0-8-sources-1-jar/groovy/lang/MetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/tailrec/TailRecursiveASTTransformation.groovy
* /groovy-3-0-8-sources-1-jar/groovy/lang/GroovyClassLoader.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/treewalker/NodeCollector.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/NullCallSite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/wrappers/Wrapper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/PropertyExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ArrayIterable.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/plugin/GroovyRunner.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/ASTParserException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/URLStreams.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/LabelVerifier.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/ThreadInterrupt.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/ReflectorLoader.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/InnerClassCompletionVisitor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/control/customizers/DelegatingCustomizer.java
*
 /groovy-3-0-8-sources-1-jar/groovy/util/FileTreeBuilder.groovy
* /groovy-3-0-8-sources-1-jar/groovy/lang/Delegate.java
* /groovy-3-0-8-sources-1-jar/groovy/ui/GroovyMain.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/NodeMetaDataHandler.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/tools/StringHelper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/AnnotationVisitor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/ConcurrentReaderHashMap.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/AutoClone.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/decompiled/TypeSignatureParser.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/NumberRange.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/GroovydocManager.java
* /groovy-3-0-8-sources-1-jar/groovy/grape/GrapeIvy.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/AntlrASTProcessor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/PostfixExpression.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/sc/transformers/BooleanExpressionTransformer.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/UnaryMinusExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/EqualsAndHashCodeASTTransformation.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/ast/tools/ConstructorNodeUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/genArrayUtil.groovy
* /groovy-3-0-8-sources-1-jar/groovy/lang/GrabExclude.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/ClassGeneratorException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/ClassLoaderForClassArtifacts.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/indy/IndyBinHelper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/wrappers/BooleanWrapper.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/util/ArrayIterator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/tailrec/ReturnAdderForClosures.groovy
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/ClassCodeExpressionTransformer.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Reference.java

* /groovy-3-0-8-sources-1-jar/groovy/lang/GeneratedGroovyProxy.java
* /groovy-3-0-8-sources-1-jar/groovy/util/Expando.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/tools/GenericsUtils.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/OperandStack.java
* /groovy-3-0-8-sources-1-jar/groovy/util/ResourceException.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/Category.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/ErrorCollecting.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/BytecodeVariable.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/tailrec/HasRecursiveCalls.groovy
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/syntax/RuntimeParserException.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/classgen/asm/MethodCallerMultiAdapter.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/callsite/PojoMetaClassSite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/metaclass/NewInstanceMetaMethod.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/parser/antlr4/internal/DescriptiveErrorStrategy.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/DateGroovyMethods.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/stc/ThirdParam.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/GroovyCallable.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/NumberAwareComparator.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/AnnotationConstantExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/vmplugin/v7/CacheableCallSite.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/builder/AstBuilder.groovy
* /groovy-3-0-8-sources-1-jar/groovy/transform/stc/SimpleType.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/IteratorClosureAdapter.java
*
 /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/runtime/ProxyGeneratorAdapter.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/treewalker/Visitor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/GroovyClassValuePreJava7.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/AutoExternalize.groovy
* /groovy-3-0-8-sources-1-jar/groovy/lang/Tuple13.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/reflection/stdclasses/CharacterCachedClass.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/ASTNode.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/expr/MethodReferenceExpression.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/FieldASTTransformation.java
* /groovy-3-0-8-sources-1-jar/groovy/transform/TypeChecked.java
* /groovy-3-0-8-sources-1-jar/groovy/lang/MetaArrayLengthProperty.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/ast/Variable.java
* /groovy-3-0-8-sources-1-jar/groovy/util/ObservableSet.java
*
 /groovy-3-0-8-sources-1-jar/groovy/transform/MapConstructor.java
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/transform/trait/TraitHelpersTuple.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 Google Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.

* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/util/concurrent/concurrentlinkedhashmap/EntryWeigher.java
No license file was found, but licenses were detected in source scan.

Licensed to the Apache Software Foundation (ASF) under one or more
contributor license agreements. See the NOTICE file distributed with
this work for additional information regarding copyright ownership.
The ASF licenses this file to You under the Apache License, Version 2.0
(the "License"); you may not use this file except in compliance with
the License. You may obtain a copy of the License at
#
http://www.apache.org/licenses/LICENSE-2.0
#
Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

global transformation to handle @Grab annotation
groovy.grape.GrabAnnotationTransformation

Found in path(s):
* /groovy-3-0-8-sources-1-jar/META-INF/services/org.codehaus.groovy.transform.ASTTransformation
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2010 Google Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/util/concurrent/concurrentlinkedhashmap/Weigher.java
* /groovy-3-0-8-sources-1-
jar/org/apache/groovy/util/concurrent/concurrentlinkedhashmap/ConcurrentLinkedHashMap.java
* /groovy-3-0-8-sources-1-jar/org/apache/groovy/util/concurrent/concurrentlinkedhashmap/EvictionListener.java
*
/groovy-3-0-8-sources-1-jar/org/apache/groovy/util/concurrent/concurrentlinkedhashmap/Weighers.java
No license file was found, but licenses were detected in source scan.

* to you under the Apache License, Version 2.0 (the
* "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at
*   http://www.apache.org/licenses/LICENSE-2.0
* software distributed under the License is distributed on an
* Based on an original grammar released in the PUBLIC DOMAIN

Found in path(s):
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/groovy.g
* /groovy-3-0-8-sources-1-jar/org/codehaus/groovy/antlr/java/java.g
No license file was found, but licenses were detected in source scan.

Licensed to the Apache Software Foundation (ASF) under one or more
contributor license agreements. See the NOTICE file distributed with
this work for additional information regarding copyright ownership.
The ASF licenses this file to You under the Apache License, Version 2.0
(the "License"); you may not use this file except in compliance with
the License. You may obtain a copy of the License at
#
http://www.apache.org/licenses/LICENSE-2.0
#
Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Format: one extension on each line without the leading "*."
Listed below are default groovy source file extensions.

NOTE: This implementation
 of supporting multiple file extensions is experimental and
the exact implementation details may vary when modularization gets introduced in
groovy 2.0. However, in terms of the behavior, this support will remain intact.

groovy

Found in path(s):
* /groovy-3-0-8-sources-1-jar/META-INF/groovy/org.codehaus.groovy.source.Extensions
No license file was found, but licenses were detected in source scan.

```
/*
* This file is adapted from the Antlr4 Java grammar which has the following license
*
*  Copyright (c) 2013 Terence Parr, Sam Harwell
*  All rights reserved.
*  [The "BSD licence"]
*
*    http://www.opensource.org/licenses/bsd-license.php
*
* Subsequent modifications by the Groovy community have been done under the Apache License v2:
*
*  Licensed to the Apache Software Foundation (ASF) under one
*  or more contributor license agreements.  See the NOTICE file
*  distributed with this work for additional information
*  regarding copyright ownership.  The ASF licenses this file
*  to you under the Apache License, Version 2.0 (the
*  "License"); you may not use this file except in compliance
*  with the License.  You may obtain a copy of the License at
*
*    http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing,
*  software distributed under the
 License is distributed on an
*  "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY
*  KIND, either express or implied.  See the License for the
*  specific language governing permissions and limitations
*  under the License.
*/

/**
* The Groovy grammar is based on the official grammar for Java:
* https://github.com/antlr/grammars-v4/blob/master/java/Java.g4
*/
lexer grammar GroovyLexer;

options {
  superClass = AbstractLexer;
}

@header {
  import java.util.Deque;
```

```
  import java.util.ArrayDeque;
  import java.util.Map;
  import java.util.HashMap;
  import java.util.Set;
  import java.util.HashSet;
  import java.util.Collections;
  import java.util.Arrays;
  import java.util.stream.IntStream;
  import java.util.logging.Logger;
  import java.util.logging.Level;
  import java.util.EmptyStackException;
  import org.apache.groovy.util.Maps;
  import static org.apache.groovy.parser.antlr4.SemanticPredicates.*;
}

@members {
  private static final
 Logger LOGGER = Logger.getLogger(GroovyLexer.class.getName());
  private long tokenIndex     = 0;
  private int  lastTokenType  = 0;
  private int  invalidDigitCount = 0;

  /**
   * Record the index and token type of the current token while emitting tokens.
   */
  @Override
  public void emit(Token token) {
     this.tokenIndex++;

     int tokenType = token.getType();
     if (Token.DEFAULT_CHANNEL == token.getChannel()) {
        this.lastTokenType = tokenType;
     }

     if (RollBackOne == tokenType) {
        this.rollbackOneChar();
     }

     super.emit(token);
  }

  private static final int[] REGEX_CHECK_ARRAY =
                          IntStream.of(
                             Identifier, CapitalizedIdentifier, NullLiteral, BooleanLiteral, THIS, RPAREN, RBRACK,
RBRACE,
                             IntegerLiteral, FloatingPointLiteral, StringLiteral, GStringEnd, INC, DEC
```

```
            ).sorted().toArray();

private boolean isRegexAllowed() {
    if (Arrays.binarySearch(REGEX_CHECK_ARRAY, this.lastTokenType) >= 0) {
        return false;
    }

    return true;
}

/**
 * just a hook, which will be overrided by GroovyLangLexer
 */
protected void rollbackOneChar() {}

private static class Paren {
    private String text;
    private int lastTokenType;
    private int line;
    private int column;

    public Paren(String text, int lastTokenType, int line, int column) {
        this.text = text;
        this.lastTokenType = lastTokenType;
        this.line = line;
        this.column = column;
    }

    public String getText() {
        return this.text;
    }

    public int getLastTokenType() {
        return this.lastTokenType;
    }

    public int getLine() {
        return line;
    }

    public int getColumn() {

  return column;
    }

    @Override
    public int hashCode() {
        return (int) (text.hashCode() * line + column);
```

```
        }

        @Override
        public boolean equals(Object obj) {
            if (!(obj instanceof Paren)) {
                return false;
            }

            Paren other = (Paren) obj;

            return this.text.equals(other.text) && (this.line == other.line && this.column == other.column);
        }
    }

    protected void enterParenCallback(String text) {}

    protected void exitParenCallback(String text) {}

    private final Deque<Paren> parenStack = new ArrayDeque<>(32);

    private void enterParen() {
        String text = getText();
        enterParenCallback(text);

        parenStack.push(new Paren(text, this.lastTokenType, getLine(), getCharPositionInLine()));
    }

    private void exitParen() {
        String text = getText();
        exitParenCallback(text);

        Paren paren = parenStack.peek();
        if (null
    == paren) return;
        parenStack.pop();
    }
    private boolean isInsideParens() {
        Paren paren = parenStack.peek();

        // We just care about "(" and "[", inside which the new lines will be ignored.
        // Notice: the new lines between "{" and "}" can not be ignored.
        if (null == paren) {
            return false;
        }

        return ("(".equals(paren.getText()) && TRY != paren.getLastTokenType()) // we don't treat try-paren(i.e. try
    (....)) as parenthesis
                || "[".equals(paren.getText());
```

```
}
private void ignoreTokenInsideParens() {
    if (!this.isInsideParens()) {
        return;
    }

    this.setChannel(Token.HIDDEN_CHANNEL);
}
private void ignoreMultiLineCommentConditionally() {
    if (!this.isInsideParens() && isFollowedByWhiteSpaces(_input)) {
        return;
    }

    this.setChannel(Token.HIDDEN_CHANNEL);
}

@Override
public int getSyntaxErrorSource() {

 return GroovySyntaxError.LEXER;
}

@Override
public int getErrorLine() {
    return getLine();
}

@Override
public int getErrorColumn() {
    return getCharPositionInLine() + 1;
}

@Override
public int popMode() {
    try {
        return super.popMode();
    } catch (EmptyStackException ignored) { // raised when parens are unmatched: too many ), ], or }
        if (LOGGER.isLoggable(Level.FINEST)) {
            LOGGER.finest(org.codehaus.groovy.runtime.DefaultGroovyMethods.asString(ignored));
        }
    }

    return Integer.MIN_VALUE;
}

private static boolean isJavaIdentifierStartAndNotIdentifierIgnorable(int codePoint) {
    return Character.isJavaIdentifierStart(codePoint) && !Character.isIdentifierIgnorable(codePoint);
}
```

```
  private static boolean isJavaIdentifierPartAndNotIdentifierIgnorable(int codePoint) {
     return Character.isJavaIdentifierPart(codePoint) && !Character.isIdentifierIgnorable(codePoint);
   }
}


// 3.10.5 String Literals
StringLiteral
  :  GStringQuotationMark    DqStringCharacter* GStringQuotationMark
  |  SqStringQuotationMark   SqStringCharacter* SqStringQuotationMark

  |  Slash      { this.isRegexAllowed() && _input.LA(1) != '*' }?
           SlashyStringCharacter+       Slash

  |  TdqStringQuotationMark  TdqStringCharacter*    TdqStringQuotationMark
  |  TsqStringQuotationMark  TsqStringCharacter*    TsqStringQuotationMark
  |  DollarSlashyGStringQuotationMarkBegin   DollarSlashyStringCharacter+
DollarSlashyGStringQuotationMarkEnd
  ;

// Groovy gstring
GStringBegin
  :  GStringQuotationMark DqStringCharacter* Dollar -> pushMode(DQ_GSTRING_MODE),
pushMode(GSTRING_TYPE_SELECTOR_MODE)
  ;
TdqGStringBegin
  :  TdqStringQuotationMark   TdqStringCharacter* Dollar -> type(GStringBegin),
pushMode(TDQ_GSTRING_MODE), pushMode(GSTRING_TYPE_SELECTOR_MODE)
  ;
SlashyGStringBegin
  :  Slash { this.isRegexAllowed()
 && _input.LA(1) != '*' }? SlashyStringCharacter* Dollar { isFollowedByJavaLetterInGString(_input) }? ->
type(GStringBegin), pushMode(SLASHY_GSTRING_MODE),
pushMode(GSTRING_TYPE_SELECTOR_MODE)
  ;
DollarSlashyGStringBegin
  :  DollarSlashyGStringQuotationMarkBegin DollarSlashyStringCharacter* Dollar {
isFollowedByJavaLetterInGString(_input) }? -> type(GStringBegin),
pushMode(DOLLAR_SLASHY_GSTRING_MODE), pushMode(GSTRING_TYPE_SELECTOR_MODE)
  ;

mode DQ_GSTRING_MODE;
GStringEnd
  :  GStringQuotationMark     -> popMode
  ;
GStringPart
  :  Dollar  -> pushMode(GSTRING_TYPE_SELECTOR_MODE)
```

```
  ;
GStringCharacter
  :  DqStringCharacter -> more
  ;

mode TDQ_GSTRING_MODE;
TdqGStringEnd
  :  TdqStringQuotationMark    -> type(GStringEnd), popMode
  ;
TdqGStringPart
  :  Dollar   -> type(GStringPart), pushMode(GSTRING_TYPE_SELECTOR_MODE)
  ;
TdqGStringCharacter
  :  TdqStringCharacter -> more
  ;

mode SLASHY_GSTRING_MODE;
SlashyGStringEnd
  :
 Dollar? Slash  -> type(GStringEnd), popMode
  ;
SlashyGStringPart
  :  Dollar { isFollowedByJavaLetterInGString(_input) }?   -> type(GStringPart),
pushMode(GSTRING_TYPE_SELECTOR_MODE)
  ;
SlashyGStringCharacter
  :  SlashyStringCharacter -> more
  ;

mode DOLLAR_SLASHY_GSTRING_MODE;
DollarSlashyGStringEnd
  :  DollarSlashyGStringQuotationMarkEnd      -> type(GStringEnd), popMode
  ;
DollarSlashyGStringPart
  :  Dollar { isFollowedByJavaLetterInGString(_input) }?   -> type(GStringPart),
pushMode(GSTRING_TYPE_SELECTOR_MODE)
  ;
DollarSlashyGStringCharacter
  :  DollarSlashyStringCharacter -> more
  ;

mode GSTRING_TYPE_SELECTOR_MODE;
GStringLBrace
  :  '{' { this.enterParen();  } -> type(LBRACE), popMode, pushMode(DEFAULT_MODE)
  ;
GStringIdentifier
  :  IdentifierInGString -> type(Identifier), popMode, pushMode(GSTRING_PATH_MODE)
  ;
```

```
mode GSTRING_PATH_MODE;
GStringPathPart
  :  Dot IdentifierInGString
  ;
RollBackOne
  :  . {
        //
 a trick to handle GStrings followed by EOF properly
        int readChar = _input.LA(-1);
        if (EOF == _input.LA(1) && ('"' == readChar || '/' == readChar)) {
           setType(GStringEnd);
        } else {
           setChannel(HIDDEN);
        }
       } -> popMode
  ;


mode DEFAULT_MODE;
// character in the double quotation string. e.g. "a"
fragment
DqStringCharacter
  :  ~["\r\n\\$]
  |  EscapeSequence
  ;

// character in the single quotation string. e.g. 'a'
fragment
SqStringCharacter
  :  ~['\r\n\\]
  |  EscapeSequence
  ;

// character in the triple double quotation string. e.g. """a"""
fragment TdqStringCharacter
  :  ~["\\$]
  |  GStringQuotationMark { _input.LA(1) != '"' || _input.LA(2) != '"' || _input.LA(3) == '"' && (_input.LA(4) != '"'
|| _input.LA(5) != '"') }?
  |  EscapeSequence
  ;

// character in the triple single quotation string. e.g. '''a'''
fragment TsqStringCharacter
  :  ~['\\]
  |  SqStringQuotationMark
```

```
 { _input.LA(1) != '\' || _input.LA(2) != '\' || _input.LA(3) == '\' && (_input.LA(4) != '\' || _input.LA(5) != '\') }?
  |  EscapeSequence
  ;

// character in the slashy string. e.g. /a/
fragment SlashyStringCharacter
  :  SlashEscape
  |  Dollar { !isFollowedByJavaLetterInGString(_input) }?
  |  ~[/$\u0000]
  ;

// character in the dollar slashy string. e.g. $/a/$
fragment DollarSlashyStringCharacter
  :  DollarSlashEscape | DollarDollarEscape
  |  Slash { _input.LA(1) != '$' }?
  |  Dollar { !isFollowedByJavaLetterInGString(_input) }?
  |  ~[/$\u0000]
  ;

// Groovy keywords
AS             : 'as';
DEF            : 'def';
IN             : 'in';
TRAIT          : 'trait';
THREADSAFE     : 'threadsafe'; // reserved keyword

// the reserved type name of Java10
VAR            : 'var';

// 3.9 Keywords
BuiltInPrimitiveType
  :  BOOLEAN
  |  CHAR
  |  BYTE
  |  SHORT
  |  INT
  |  LONG
  |  FLOAT
  |  DOUBLE
   ;

ABSTRACT     : 'abstract';
ASSERT       : 'assert';

fragment
BOOLEAN      : 'boolean';

BREAK        : 'break';
```

```
fragment
BYTE         : 'byte';

CASE         : 'case';
CATCH        : 'catch';

fragment
CHAR         : 'char';

CLASS        : 'class';
CONST        : 'const';
CONTINUE     : 'continue';
DEFAULT      : 'default';
DO           : 'do';

fragment
DOUBLE       : 'double';

ELSE         : 'else';
ENUM         : 'enum';
EXTENDS      : 'extends';
FINAL        : 'final';
FINALLY      : 'finally';

fragment
FLOAT        : 'float';


FOR          : 'for';
IF           : 'if';
GOTO         : 'goto';
IMPLEMENTS   : 'implements';
IMPORT       : 'import';
INSTANCEOF   : 'instanceof';

fragment
INT          : 'int';

INTERFACE    : 'interface';

fragment
LONG         : 'long';

NATIVE       : 'native';
NEW          : 'new';
PACKAGE      : 'package';
PRIVATE      : 'private';
```

```
PROTECTED     : 'protected';
PUBLIC        : 'public';
RETURN        :
 'return';

fragment
SHORT         : 'short';


STATIC        : 'static';
STRICTFP      : 'strictfp';
SUPER         : 'super';
SWITCH        : 'switch';
SYNCHRONIZED  : 'synchronized';
THIS          : 'this';
THROW         : 'throw';
THROWS        : 'throws';
TRANSIENT     : 'transient';
TRY           : 'try';
VOID          : 'void';
VOLATILE      : 'volatile';
WHILE         : 'while';


// 3.10.1 Integer Literals

IntegerLiteral
  :  (   DecimalIntegerLiteral
     |   HexIntegerLiteral
     |   OctalIntegerLiteral
     |   BinaryIntegerLiteral
     ) (Underscore { require(false, "Number ending with underscores is invalid", -1, true); })?

  // !!! Error Alternative !!!
  |   Zero ([0-9] { invalidDigitCount++; })+ { require(false, "Invalid octal number", -(invalidDigitCount + 1), true);
} IntegerTypeSuffix?
  ;

fragment
Zero
  :  '0'
  ;

fragment
DecimalIntegerLiteral
  :  DecimalNumeral IntegerTypeSuffix?
  ;
```

```
fragment
HexIntegerLiteral
  :  HexNumeral
 IntegerTypeSuffix?
  ;

fragment
OctalIntegerLiteral
  :  OctalNumeral IntegerTypeSuffix?
  ;

fragment
BinaryIntegerLiteral
  :  BinaryNumeral IntegerTypeSuffix?
  ;

fragment
IntegerTypeSuffix
  :  [lLiIgG]
  ;

fragment
DecimalNumeral
  :  Zero
  |  NonZeroDigit (Digits? | Underscores Digits)
  ;

fragment
Digits
  :  Digit (DigitOrUnderscore* Digit)?
  ;

fragment
Digit
  :  Zero
  |  NonZeroDigit
  ;

fragment
NonZeroDigit
  :  [1-9]
  ;

fragment
DigitOrUnderscore
  :  Digit
  |  Underscore
  ;
```

```
fragment
Underscores
  :  Underscore+
  ;

fragment
Underscore
  :  '_'
  ;

fragment
HexNumeral
  :  Zero [xX] HexDigits
  ;

fragment
HexDigits
  :  HexDigit (HexDigitOrUnderscore* HexDigit)?
  ;

fragment
HexDigit
  :  [0-9a-fA-F]
  ;

fragment
HexDigitOrUnderscore
  :  HexDigit
  |  Underscore
  ;

fragment
OctalNumeral
  :  Zero Underscores? OctalDigits
  ;

fragment
OctalDigits
  :  OctalDigit
 (OctalDigitOrUnderscore* OctalDigit)?
  ;

fragment
OctalDigit
  :  [0-7]
  ;
```

```
fragment
OctalDigitOrUnderscore
  :  OctalDigit
  |  Underscore
  ;

fragment
BinaryNumeral
  :  Zero [bB] BinaryDigits
  ;

fragment
BinaryDigits
  :  BinaryDigit (BinaryDigitOrUnderscore* BinaryDigit)?
  ;

fragment
BinaryDigit
  :  [01]
  ;

fragment
BinaryDigitOrUnderscore
  :  BinaryDigit
  |  Underscore
  ;

// 3.10.2 Floating-Point Literals

FloatingPointLiteral
  :  (   DecimalFloatingPointLiteral
     |   HexadecimalFloatingPointLiteral
     ) (Underscore { require(false, "Number ending with underscores is invalid", -1, true); })?
  ;

fragment
DecimalFloatingPointLiteral
  :  Digits Dot Digits ExponentPart? FloatTypeSuffix?
  |  Digits ExponentPart FloatTypeSuffix?
  |  Digits FloatTypeSuffix
  ;

fragment
ExponentPart
  :  ExponentIndicator SignedInteger
  ;

fragment
```

```
ExponentIndicator
  :  [eE]
  ;

fragment
SignedInteger
   :  Sign? Digits
  ;

fragment
Sign
  :  [+\-]
  ;

fragment
FloatTypeSuffix
  :  [fFdDgG]
  ;

fragment
HexadecimalFloatingPointLiteral
  :  HexSignificand BinaryExponent FloatTypeSuffix?
  ;

fragment
HexSignificand
  :  HexNumeral Dot?
  |  Zero [xX] HexDigits? Dot HexDigits
  ;

fragment
BinaryExponent
  :  BinaryExponentIndicator SignedInteger
  ;

fragment
BinaryExponentIndicator
  :  [pP]
  ;

fragment
Dot :  '.'
  ;

// 3.10.3 Boolean Literals

BooleanLiteral
  :  'true'
```

```
  | 'false'
  ;


// 3.10.6 Escape Sequences for Character and String Literals

fragment
EscapeSequence
  : Backslash [btnfrs'"\\]
  | OctalEscape
  | UnicodeEscape
  | DollarEscape
  | LineEscape
  ;


fragment
OctalEscape
  : Backslash OctalDigit
  | Backslash OctalDigit OctalDigit
  | Backslash ZeroToThree OctalDigit OctalDigit
  ;

// Groovy allows 1 or more u's after the backslash
fragment
UnicodeEscape
  :
 Backslash 'u' HexDigit HexDigit HexDigit HexDigit
  ;

fragment
ZeroToThree
  : [0-3]
  ;

// Groovy Escape Sequences

fragment
DollarEscape
  : Backslash Dollar
  ;

fragment
LineEscape
  : Backslash LineTerminator
  ;

fragment
```

```
LineTerminator
  :  '\r'? '\n' | '\r'
  ;

fragment
SlashEscape
  :  Backslash Slash
  ;

fragment
Backslash
  :  '\\'
  ;

fragment
Slash
  :  '/'
  ;

fragment
Dollar
  :  '$'
  ;

fragment
GStringQuotationMark
  :  ''
  ;

fragment
SqStringQuotationMark
  :  '\''
  ;

fragment
TdqStringQuotationMark
  :  ''''''
  ;

fragment
TsqStringQuotationMark
  :  '\'\'\''
  ;

fragment
DollarSlashyGStringQuotationMarkBegin
  :  '$/'
  ;
```

```
fragment
DollarSlashyGStringQuotationMarkEnd
  :   '/$'
  ;

fragment
DollarSlashEscape
  :   '$/'
  ;

fragment
DollarDollarEscape
  :   '$$'
  ;

// 3.10.7 The Null Literal
NullLiteral
  :   'null'
  ;

// Groovy Operators

RANGE_INCLUSIVE    :
 '..';
RANGE_EXCLUSIVE    : '..<';
SPREAD_DOT         : '*.';
SAFE_DOT           : '?.';
SAFE_CHAIN_DOT     : '??.';
ELVIS              : '?:';
METHOD_POINTER     : '.&';
METHOD_REFERENCE   : '::';
REGEX_FIND         : '=~';
REGEX_MATCH        : '==~';
POWER              : '**';
POWER_ASSIGN       : '**=';
SPACESHIP          : '<=>';
IDENTICAL          : '===';
NOT_IDENTICAL      : '!==';
ARROW              : '->';

// !internalPromise will be parsed as !in ternalPromise, so semantic predicates are necessary
NOT_INSTANCEOF     : '!instanceof' { isFollowedBy(_input, ' ', '\t', '\r', '\n') }?;
NOT_IN             : '!in'         { isFollowedBy(_input, ' ', '\t', '\r', '\n', '[', '(', '{') }?;


// 3.11 Separators
```

```
LPAREN          : '('  { this.enterParen();     } -> pushMode(DEFAULT_MODE);
RPAREN          : ')'  { this.exitParen();      } -> popMode;

LBRACE          : '{'  { this.enterParen();     } -> pushMode(DEFAULT_MODE);
RBRACE          : '}'  { this.exitParen();
    } -> popMode;

LBRACK          : '['  { this.enterParen();     } -> pushMode(DEFAULT_MODE);
RBRACK          : ']'  { this.exitParen();      } -> popMode;

SEMI            : ';';
COMMA           : ',';
DOT             : Dot;

// 3.12 Operators

ASSIGN          : '=';
GT              : '>';
LT              : '<';
NOT             : '!';
BITNOT          : '~';
QUESTION        : '?';
COLON           : ':';
EQUAL           : '==';
LE              : '<=';
GE              : '>=';
NOTEQUAL        : '!=';
AND             : '&&';
OR              : '||';
INC             : '++';
DEC             : '--';
ADD             : '+';
SUB             : '-';
MUL             : '*';
DIV             : Slash;
BITAND          : '&';
BITOR           : '|';
XOR             : '^';
MOD             : '%';


ADD_ASSIGN      : '+=';
SUB_ASSIGN      : '-=';
MUL_ASSIGN      : '*=';
DIV_ASSIGN      : '/=';
AND_ASSIGN      : '&=';
OR_ASSIGN       : '|=';
XOR_ASSIGN      : '^=';
```

```
MOD_ASSIGN     : '%=';
LSHIFT_ASSIGN  :
 '<<=';
RSHIFT_ASSIGN  : '>>=';
URSHIFT_ASSIGN : '>>>=';
ELVIS_ASSIGN   : '?=';


// 3.8 Identifiers (must appear after all keywords in the grammar)
CapitalizedIdentifier
  :  JavaLetter {Character.isUpperCase(_input.LA(-1))}? JavaLetterOrDigit*
  ;

Identifier
  :  JavaLetter JavaLetterOrDigit*
  ;

fragment
IdentifierInGString
  :  JavaLetterInGString JavaLetterOrDigitInGString*
  ;

fragment
JavaLetter
  :  [a-zA-Z$_] // these are the "java letters" below 0x7F
  |  // covers all characters above 0x7F which are not a surrogate
     ~[\u0000-\u007F\uD800-\uDBFF]
     { isJavaIdentifierStartAndNotIdentifierIgnorable(_input.LA(-1)) }?
  |  // covers UTF-16 surrogate pairs encodings for U+10000 to U+10FFFF
     [\uD800-\uDBFF] [\uDC00-\uDFFF]
     { Character.isJavaIdentifierStart(Character.toCodePoint((char) _input.LA(-2), (char) _input.LA(-1))) }?
  ;

fragment
JavaLetterInGString
  :  JavaLetter { _input.LA(-1) != '$' }?
  ;

fragment
JavaLetterOrDigit
   :  [a-zA-Z0-9$_] // these are the "java letters or digits" below 0x7F
  |  // covers all characters above 0x7F which are not a surrogate
     ~[\u0000-\u007F\uD800-\uDBFF]
     { isJavaIdentifierPartAndNotIdentifierIgnorable(_input.LA(-1)) }?
  |  // covers UTF-16 surrogate pairs encodings for U+10000 to U+10FFFF
     [\uD800-\uDBFF] [\uDC00-\uDFFF]
     { Character.isJavaIdentifierPart(Character.toCodePoint((char) _input.LA(-2), (char) _input.LA(-1))) }?
  ;
```

```
fragment
JavaLetterOrDigitInGString
  :   JavaLetterOrDigit  { _input.LA(-1) != '$' }?
  ;

fragment
ShCommand
  :   ~[\r\n\uFFFF]*
  ;

//
// Additional symbols not defined in the lexical specification
//

AT : '@';
ELLIPSIS : '...';

//
// Whitespace, line escape and comments
//
WS  : ([ \t]+ | LineEscape+) -> skip
  ;

// Inside (...) and [...] but not {...}, ignore newlines.
NL  : LineTerminator   { this.ignoreTokenInsideParens(); }
  ;

// Multiple-line comments (including
 groovydoc comments)
ML_COMMENT
  :   '/*' .*? '*/'       { this.ignoreMultiLineCommentConditionally(); } -> type(NL)
  ;

// Single-line comments
SL_COMMENT
  :   '//' ~[\r\n\uFFFF]* { this.ignoreTokenInsideParens(); }            -> type(NL)
  ;

// Script-header comments.
// The very first characters of the file may be "#!".  If so, ignore the first line.
SH_COMMENT
  :   '#!' { require(0 == this.tokenIndex, "Shebang comment should appear at the first line", -2, true); } ShCommand
(LineTerminator '#!' ShCommand)* -> skip
  ;

// Unexpected characters will be handled by groovy parser later.
UNEXPECTED_CHAR
```

: .
;

Found in path(s):
* /groovy-3-0-8-sources-1-jar/GroovyLexer.g4

1.622 groovy-json 3.0.8

1.622.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one
* or more contributor license agreements. See the NOTICE file
* distributed with this work for additional information
* regarding copyright ownership. The ASF licenses this file
* to you under the Apache License, Version 2.0 (the
* "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing,
* software distributed under the License is distributed on an
* "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY
* KIND, either express or implied. See the License for the
* specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/BaseJsonParser.java
* /groovy-json-3-0-8-sources-jar/groovy/json/JsonException.java
*
/groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/ValueMap.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/CacheType.java
* /groovy-json-3-0-8-sources-jar/groovy/json/JsonParser.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/Value.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/ValueContainer.java
* /groovy-json-3-0-8-sources-jar/groovy/json/StreamingJsonBuilder.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/CharacterSource.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/CharScanner.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/Cache.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/NumberValue.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/FastStringService.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/CharBuf.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/IO.java

*
/groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/Exceptions.java
* /groovy-json-3-0-8-sources-jar/groovy/json/DefaultJsonGenerator.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/JsonParserCharArray.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/SimpleCache.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/FastStringServiceFactory.java
* /groovy-json-3-0-8-sources-jar/groovy/json/JsonToken.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/FastStringUtils.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/DefaultFastStringService.java
* /groovy-json-3-0-8-sources-jar/groovy/json/JsonOutput.java
* /groovy-json-3-0-8-sources-jar/groovy/json/JsonBuilder.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/LazyValueMap.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/JsonStringDecoder.java
*
/groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/ByteScanner.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/Type.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/JsonParserLax.java
* /groovy-json-3-0-8-sources-jar/groovy/json/JsonSlurperClassic.java
* /groovy-json-3-0-8-sources-jar/groovy/json/JsonSlurper.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/CharSequenceValue.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/ValueMapImpl.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/JsonFastParser.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/ValueList.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/DefaultFastStringServiceFactory.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/ReaderCharacterSource.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/LazyMap.java
* /groovy-json-3-0-8-sources-jar/groovy/json/JsonLexer.java
*
/groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/ArrayUtils.java
* /groovy-json-3-0-8-sources-jar/groovy/json/JsonTokenType.java
* /groovy-json-3-0-8-sources-jar/groovy/json/JsonParserType.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/MapItemValue.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/Sys.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/Dates.java
* /groovy-json-3-0-8-sources-jar/groovy/json/JsonDelegate.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/JsonParserUsingCharacterSource.java
* /groovy-json-3-0-8-sources-jar/groovy/json/JsonGenerator.java
* /groovy-json-3-0-8-sources-jar/groovy/json/StringEscapeUtils.java
* /groovy-json-3-0-8-sources-jar/org/apache/groovy/json/internal/Chr.java
No license file was found, but licenses were detected in source scan.

#
Licensed to the Apache Software Foundation (ASF) under one
or more contributor license agreements. See the NOTICE file
distributed with this work for additional information
regarding copyright ownership. The ASF licenses this file
to you under the Apache License, Version 2.0 (the
"License"); you may not use this file except in compliance

with the License. You may obtain a copy of the License at
#
http://www.apache.org/licenses/LICENSE-2.0
#
Unless required by applicable law or agreed to in writing,
software distributed under the License is distributed on an
"AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY
KIND, either express or implied. See the License for the
specific language governing permissions and limitations
under the License.
#
org.apache.groovy.json.DefaultFastStringServiceFactory

Found in path(s):
* /groovy-json-3-0-8-sources-jar/META-INF/services/org.apache.groovy.json.FastStringServiceFactory

1.623 are-we-there-yet 1.1.7

1.623.1 Available under license :

ISC
Copyright (c) 2015, Rebecca Turner

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.624 delaunator 4.0.1

1.624.1 Available under license :

ISC
ISC License

Copyright (c) 2017, Mapbox

Permission to use, copy, modify, and/or distribute this software for any purpose
with or without fee is hereby granted, provided that the above copyright notice
and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH

REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS
OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.625 available-typed-arrays 1.0.5

1.625.1 Available under license :

MIT License

Copyright (c) 2020 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.626 ansi-html-community 0.0.8

1.626.1 Available under license :

Apache License 2.0
Apache License

Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership of such entity.

"You"
(or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial revisions, annotations, elaborations,
or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"

means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems
that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants
to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work
or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding those notices that do not

pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution
of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental,
or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted
against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "{}"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright {yyyy} {name of copyright owner}

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.627 ansi-colors 1.1.0

1.627.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-2017, Brian Woodward.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.628 ansi-cyan 0.1.1

1.628.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) <%= year() %>, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.629 arr-map 2.0.2

1.629.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, 2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.630 append-buffer 1.0.2

1.630.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2017, Brian Woodward.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.631 arr-filter 1.1.2

1.631.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2015, 2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.632 ansi-red 0.1.1

1.632.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) <%= year() %>, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.633 array-initial 1.1.0

1.633.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Jon Schlinkert, contributors.

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.
MIT

1.634 array-last 1.3.0

1.634.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2015, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.635 array-sort 1.0.0

1.635.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.636 async-done 1.3.2

1.636.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Blaine Bublitz, Eric Schoffstall and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.637 async-settle 1.0.0

1.637.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Blaine Bublitz, Eric Schoffstall and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.638 bach 1.2.0

1.638.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Blaine Bublitz, Eric Schoffstall and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.639 clone-buffer 1.0.0

1.639.1 Available under license :

MIT

1.640 cloneable-readable 1.1.3

1.640.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2016 Matteo Collina

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.641 clone-stats 1.0.0

1.641.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Hugh Kennedy

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.642 collection-map 1.0.0

1.642.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, 2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.643 default-compare 1.0.0

1.643.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2017, Brian Woodward.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.644 default-resolution 2.0.0

1.644.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Blaine Bublitz, Eric Schoffstall and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.645 each-props 1.3.2

1.645.1 Available under license :

MIT
MIT License

Copyright (c) 2016 Takayuki Sato

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.646 fast-levenshtein 1.1.4

1.646.1 Available under license :

(MIT License)

Copyright (c) 2013 [Ramesh Nair](http://www.hiddentao.com/)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.647 find-cache-dir 3.3.2

1.647.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (https://sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit

persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.648 fs-mkdirp-stream 1.0.0

1.648.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017 Blaine Bublitz <blaine.bublitz@gmail.com>, Eric Schoffstall <yo@contra.io> and other contributors (Originally based on code from node-mkdirp - MIT/X11 license - Copyright 2010 James Halliday)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN
NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.649 glob-watcher 5.0.5

1.649.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017 Blaine Bublitz <blaine.bublitz@gmail.com>, Eric Schoffstall <yo@contra.io> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.650 is-valid-glob 1.0.0

1.650.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.651 is-what 3.14.1

1.651.1 Available under license :

MIT
MIT License

Copyright (c) 2018 Luca Ban - Mesqueeb

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.652 last-run 1.1.1

1.652.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Blaine Bublitz, Eric Schoffstall and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is

furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.653 lead 1.0.0

1.653.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017 Blaine Bublitz <blaine.bublitz@gmail.com>, Eric Schoffstall <yo@contra.io> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.654 matchdep 2.0.0

1.654.1 Available under license :

MIT
Copyright (c) 2013 Tyler Kellen

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

1.655 mute-stdout 1.0.1

1.655.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, 2018 Blaine Bublitz <blaine.bublitz@gmail.com> and Eric Schoffstall <yo@contra.io>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER
IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.656 now-and-later 2.0.1

1.656.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Blaine Bublitz, Eric Schoffstall and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.657 object-reduce 1.0.1

1.657.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2015, 2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is

furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.658 plugin-error 0.1.2

1.658.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.659 remove-bom-buffer 3.0.0

1.659.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.660 replace-ext 1.0.1

1.660.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Blaine Bublitz <blaine.bublitz@gmail.com>, Eric Schoffstall <yo@contra.io> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.661 remove-bom-stream 1.2.0

1.661.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017 Blaine Bublitz <blaine.bublitz@gmail.com>, Eric Schoffstall <yo@contra.io> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.662 replace-homedir 1.0.0

1.662.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017 Blaine Bublitz <blaine.bublitz@gmail.com>, Eric Schoffstall <yo@contra.io> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell

copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.663 resolve-options 1.1.0

1.663.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017 Blaine Bublitz <blaine.bublitz@gmail.com>, Eric Schoffstall <yo@contra.io> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.664 semver-greatest-satisfied-range 1.1.0

1.664.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, 2017 Blaine Bublitz <blaine.bublitz@gmail.com>, Eric Schoffstall <yo@contra.io> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.665 stream-exhaust 1.0.2

1.665.1 Available under license :

Copyright <YEAR> <COPYRIGHT HOLDER>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION

WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.666 sver-compat 1.5.0

1.666.1 Available under license :

MIT
MIT License

Copyright (C) 2017 Guy Bedford

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.667 to-through 2.0.0

1.667.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017 Blaine Bublitz <blaine.bublitz@gmail.com>, Eric Schoffstall <yo@contra.io> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.668 unicode-canonical-property-names-ecmascript 2.0.0

1.668.1 Available under license :

Copyright Mathias Bynens <https://mathiasbynens.be/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.669 unicode-match-property-ecmascript 2.0.0

1.669.1 Available under license :

Copyright Mathias Bynens <https://mathiasbynens.be/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the

"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.670 undertaker-registry 1.0.1

1.670.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, 2017 Blaine Bublitz <blaine.bublitz@gmail.com>, Eric Schoffstall <yo@contra.io> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.671 undertaker 1.3.0

1.671.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Blaine Bublitz, Eric Schoffstall and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.672 vinyl-fs 3.0.3

1.672.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2013-2017 Blaine Bublitz <blaine.bublitz@gmail.com>, Eric Schoffstall <yo@contra.io> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.673 value-or-function 3.0.0

1.673.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Blaine Bublitz, Eric Schoffstall and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.674 vinyl 2.2.1

1.674.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2013 Blaine Bublitz <blaine.bublitz@gmail.com>, Eric Schoffstall <yo@contra.io> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.675 vinyl-sourcemap 1.1.0

1.675.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017 Blaine Bublitz <blaine.bublitz@gmail.com>, Eric Schoffstall <yo@contra.io> and other contributors (Based on code from gulp-sourcemaps - ISC License - Copyright (c) 2014, Florian Reiterer)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO
EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.676 ansi-align 3.0.1

1.676.1 Available under license :

Copyright (c) 2016, Contributors

Permission to use, copy, modify, and/or distribute this software for any purpose
with or without fee is hereby granted, provided that the above copyright notice
and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND
FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS
OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER
TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF
THIS SOFTWARE.
ISC

1.677 ip-address 5.3.3

1.677.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2020 Sean C Foley
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*   or at
*   https://github.com/seancfoley/IPAddress/blob/master/LICENSE
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv4/IPv4AddressTrie.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/AddressTrieOps.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv6/IPv6AddressTrie.java

* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/BinaryTreeNode.java
*
 /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/AddressTrieMap.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv6/IPv6AddressAssociativeTrie.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/mac/MACAddressTrie.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/TreeOps.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/AddressTrieSet.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/Partition.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/mac/MACAddressAssociativeTrie.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv4/IPv4AddressAssociativeTrie.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/AbstractTree.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/AddressTrie.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/AssociativeAddressTrie.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016-2018 Sean C Foley
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*   or at
*   https://github.com/seancfoley/IPAddress/blob/master/LICENSE
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv4/IPv4AddressStringParameters.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/large/package-info.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/IPAddressNetwork.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/AddressItem.java
*
 /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/standard/IPAddressJoinedSegments.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/standard/AddressCreator.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/AddressSegmentParams.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/IPAddressStringParameters.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/sql/MySQLTranslator.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/IPAddressString.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/sql/SQLStringMatcher.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/validate/Validator.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/AddressSegment.java

* /ipaddress-5-3-3-sources-jar/inet/ipaddr/AddressStringParameters.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv6/IPv6AddressSegment.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/AddressSection.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/string/IPAddressStringDivisionSeries.java
*
 /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/string/IPAddressStringDivision.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/IPAddress.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/IPAddressRange.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/large/IPAddressLargeDivisionGrouping.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/NetworkMismatchException.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv4/IPv4Address.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/AddressComponent.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/string/package-info.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv6/IPv6AddressSection.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/validate/ParsedHostIdentifierStringQualifier.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/package-info.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/string/AddressStringDivisionSeries.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/AddressComponentRange.java
*
 /ipaddress-5-3-3-sources-jar/inet/ipaddr/AddressConversionException.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv6/IPv6AddressNetwork.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/standard/IPAddressBitsDivision.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/standard/package-info.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/AddressStringException.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/MACAddressString.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv4/IPv4AddressSegment.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/validate/ParsedAddressCreator.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv6/IPv6Address.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/mac/MACAddressNetwork.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/validate/IPAddressProvider.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/HostIdentifierException.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/IPAddressSegment.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/IPAddressDivisionSeries.java
*
 /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv6/IPv6AddressStringParameters.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/HostNameParameters.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/Address.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/SizeMismatchException.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/validate/AddressParseData.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/AddressComparator.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/AddressValueException.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/string/AddressStringDivision.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/standard/IPAddressDivision.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/IPAddressPartStringCollection.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/IPAddressConverter.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/IPAddressStringWriter.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/mac/MACAddressSection.java
*

/ipaddress-5-3-3-sources-jar/inet/ipaddr/MACAddressStringParameters.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/standard/AddressDivisionGrouping.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/mac/MACAddress.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv4/IPv4AddressNetwork.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/AddressDivisionSeries.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv4/IPv4AddressSection.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/PrefixLenException.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/HostName.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/standard/AddressDivision.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/IPAddressPartStringSubCollection.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv4/IPv4JoinedSegments.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/AddressItemRange.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/IPAddressPartConfiguredString.java
*
/ipaddress-5-3-3-sources-jar/inet/ipaddr/format/AddressDivisionBase.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/validate/HostIdentifierStringValidator.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/InconsistentPrefixException.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/large/IPAddressLargeDivision.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/AddressPositionException.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/HostNameException.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/standard/AddressBitsDivision.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/mac/MACAddressSegment.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/AddressDivisionGroupingBase.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/sql/IPAddressSQLTranslator.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/standard/IPAddressDivisionGrouping.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/IPAddressSegmentSeries.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/validate/ParsedHost.java
*
/ipaddress-5-3-3-sources-jar/inet/ipaddr/AddressSegmentSeries.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/IPAddressPartStringCollectionBase.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/IncompatibleAddressException.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/HostIdentifierString.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/AddressNetwork.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/validate/MACAddressProvider.java
* /ipaddress-5-3-3-sources-jar/module-info.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/AddressDivisionWriter.java
No license file was found, but licenses were detected in source scan.

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at
http://www.apache.org/licenses/LICENSE-2.0
distributed under the License is distributed on an "AS IS" BASIS,

Found in path(s):
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/IPAddressResources.properties
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2018 Sean C Foley
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*     or at
*     https://github.com/seancfoley/IPAddress/blob/master/LICENSE
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):

```
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/mac/package-info.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/package-info.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/validate/ParsedAddressGrouping.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/AddressGenericDivision.java
*
 /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/validate/package-info.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/package-info.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv4/package-info.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/validate/ParsedMACAddress.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv4/IPv4AddressSeqRange.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/util/sql/package-info.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/validate/ParsedIPAddress.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/format/IPAddressGenericDivision.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv6/IPv6AddressSeqRange.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/IPAddressSeqRange.java
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/ipv6/package-info.java
No license file was found, but licenses were detected in source scan.
```

```
/*
* Copyright 2016-2020 Sean C Foley
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*     or at
*     https://github.com/seancfoley/IPAddress/blob/master/LICENSE
*
```

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /ipaddress-5-3-3-sources-jar/inet/ipaddr/IPAddressSection.java

1.678 slf4j 1.5.8-PATCHED

1.678.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2004-2007 QOS.ch
* All rights reserved.
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be
* included in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
* NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
* LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
* OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
* WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/

Found in path(s):
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/ILoggerFactory.java
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/spi/LocationAwareLogger.java
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/helpers/MarkerIgnoringBase.java
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/IMarkerFactory.java
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/impl/StaticMarkerBinder.java
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/helpers/Util.java

* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/impl/StaticLoggerBinder.java
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/helpers/MessageFormatter.java
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/spi/MDCAdapter.java
*
/slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/MDC.java
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/helpers/BasicMarkerFactory.java
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/MarkerFactory.java
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java5/org/slf4j/Logger.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2004-2005 SLF4J.ORG
* Copyright (c) 2004-2005 QOS.ch
*
* All rights reserved.
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, and/or sell copies of the Software, and to permit persons
* to whom the Software is furnished to do so, provided that the above
* copyright notice(s) and this permission notice appear in all copies of
* the Software and that both the above copyright notice(s) and this
* permission notice appear in supporting documentation.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A
PARTICULAR PURPOSE AND NONINFRINGEMENT
* OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR
* HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY
* SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER
* RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF
* CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN
* CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
*
* Except as contained in this notice, the name of a copyright holder
* shall not be used in advertising or otherwise to promote the sale, use
* or other dealings in this Software without prior written authorization
* of the copyright holder.
*
*/

Found in path(s):
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/spi/LoggerFactoryBinder.java
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/spi/MarkerFactoryBinder.java
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/helpers/NOPLogger.java

No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2004-2008 QOS.ch
* All rights reserved.
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be
* included in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
* NONINFRINGEMENT. IN
NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
* LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
* OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
* WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/

Found in path(s):
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/LoggerFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2004-2005 SLF4J.ORG
* Copyright (c) 2004-2005 QOS.ch
*
* All rights reserved.
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, and/or sell copies of the Software, and to permit persons
* to whom the Software is furnished to do so, provided that the above
* copyright notice(s) and this permission notice appear in all copies of
* the Software and that both the above copyright notice(s) and this
* permission notice appear in supporting documentation.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR
A PARTICULAR PURPOSE AND NONINFRINGEMENT
* OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR
* HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY
* SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER
* RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF
* CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN
* CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
*
* Except as contained in this notice, the name of a copyright holder
* shall not be used in advertising or otherwise to promote the sale, use
* or other dealings in this Software without prior written authorization
* of the copyright holder.
*
*/

Found in path(s):
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/helpers/SubstituteLoggerFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2004-2008 QOS.ch
* All rights reserved.
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be
* included in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
* NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
* LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
* OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
* WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/

Found in path(s):
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/helpers/BasicMarker.java

* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/Logger.java
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/Marker.java
* /slf4j-api-jdk15-1-5-8-patched-sources-jar/java/org/slf4j/helpers/BasicMDCAdapter.java

1.679 xz 1.4

1.679.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* RangeCoder
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*          Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/rangecoder/RangeCoder.java
No license file was found, but licenses were detected in source scan.

```
/*
* ARMThumbOptions
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/ARMThumbOptions.java
No license file was found, but licenses were detected in source scan.

```
/*
* SPARCOptions
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/SPARCOptions.java

No license file was found, but licenses were detected in source scan.

```
/*
* XZ
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/XZ.java
No license file was found, but licenses were detected in source scan.

```
/*
* LZMAInputStream
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*          Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/LZMAInputStream.java
No license file was found, but licenses were detected in source scan.

```
/*
* DeltaOptions
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/DeltaOptions.java
No license file was found, but licenses were detected in source scan.

```
/*
* 2-, 3-, and 4-byte hashing
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*          Igor Pavlov <http://7-zip.org/>
*
```

* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/lz/Hash234.java
No license file was found, but licenses were detected in source scan.

/*
* SeekableXZInputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/SeekableXZInputStream.java
No license file was found, but licenses were detected in source scan.

/*
* State
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*   Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/lzma/State.java
No license file was found, but licenses were detected in source scan.

/*
* EncoderUtil
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/common/EncoderUtil.java
No license file was found, but licenses were detected in source scan.

```
/*
* FilterCoder
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/FilterCoder.java
No license file was found, but licenses were detected in source scan.

```
/*
* LZMAEncoderNormal
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*          Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/lzma/LZMAEncoderNormal.java
No license file was found, but licenses were detected in source scan.

```
/*
* RangeDecoderFromBuffer
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*          Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/rangecoder/RangeDecoderFromBuffer.java
No license file was found, but licenses were detected in source scan.

```
/*
* RangeDecoderFromStream
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*          Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
```

* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/rangecoder/RangeDecoderFromStream.java
No license file was found, but licenses were detected in source scan.

/*
* DeltaInputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/DeltaInputStream.java
No license file was found, but licenses were detected in source scan.

/*
* BCJEncoder
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/BCJEncoder.java
No license file was found, but licenses were detected in source scan.

/*
* ARMOptions
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/ARMOptions.java
No license file was found, but licenses were detected in source scan.

/*
* BCJ filter for Itanium (IA-64) instructions

*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*   Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/simple/IA64.java
No license file was found, but licenses were detected in source scan.

/*
* FinishableOutputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/FinishableOutputStream.java
No license file was found, but licenses were detected in source scan.

/*
* BlockOutputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/BlockOutputStream.java
No license file was found, but licenses were detected in source scan.

/*
* SHA256
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):

* /xz-1-4-sources-1-jar/org/tukaani/xz/check/SHA256.java
No license file was found, but licenses were detected in source scan.

```
/*
* Hash Chain match finder with 2-, 3-, and 4-byte hashing
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*          Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/lz/HC4.java
No license file was found, but licenses were detected in source scan.

```
/*
* DeltaOutputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/DeltaOutputStream.java
No license file was found, but licenses were detected in source scan.

```
/*
* BlockInputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/BlockInputStream.java
No license file was found, but licenses were detected in source scan.

```
/*
* DeltaDecoder
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
```

* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/delta/DeltaDecoder.java
* /xz-1-4-sources-1-jar/org/tukaani/xz/DeltaDecoder.java
No license file was found, but licenses were detected in source scan.

/*
* UnsupportedOptionsException
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/UnsupportedOptionsException.java
No license file was found, but licenses were detected in source scan.

/*
* None
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/check/None.java
No license file was found, but licenses were detected in source scan.

/*
* IndexRecord
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/index/IndexRecord.java
No license file was found, but licenses were detected in source scan.

```
/*
* FinishableWrapperOutputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/FinishableWrapperOutputStream.java
No license file was found, but licenses were detected in source scan.

```
/*
* LZMA2Encoder
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/LZMA2Encoder.java
No license file was found, but licenses were detected in source scan.

```
/*
* XZIOException
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/XZIOException.java
No license file was found, but licenses were detected in source scan.

```
/*
* RangeDecoder
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*          Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/rangecoder/RangeDecoder.java
No license file was found, but licenses were detected in source scan.

/*
* BCJCoder
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/BCJCoder.java
No license file was found, but licenses were detected in source scan.

/*
* StreamFlags
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/common/StreamFlags.java
No license file was found, but licenses were detected in source scan.

/*
* BCJDecoder
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/BCJDecoder.java
No license file was found, but licenses were detected in source scan.

/*
* LZMA2Options
*
* Author: Lasse Collin <lasse.collin@tukaani.org>

*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/LZMA2Options.java
No license file was found, but licenses were detected in source scan.

/*
* XZFormatException
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/XZFormatException.java
No license file was found, but licenses were detected in source scan.

/*
* XZInputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/XZInputStream.java
No license file was found, but licenses were detected in source scan.

/*
* LZEncoder
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*   Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/lz/LZEncoder.java

No license file was found, but licenses were detected in source scan.

```
/*
* CRC64
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/check/CRC64.java
No license file was found, but licenses were detected in source scan.

```
/*
* DeltaEncoder
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/DeltaEncoder.java
* /xz-1-4-sources-1-jar/org/tukaani/xz/delta/DeltaEncoder.java
No license file was found, but licenses were detected in source scan.

```
/*
* CorruptedInputException
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/CorruptedInputException.java
No license file was found, but licenses were detected in source scan.

```
/*
* LZMAEncoder
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*          Igor Pavlov <http://7-zip.org/>
*
```

* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/lzma/LZMAEncoder.java
No license file was found, but licenses were detected in source scan.

/*
* CountingInputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/CountingInputStream.java
No license file was found, but licenses were detected in source scan.

/*
* DecoderUtil
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/common/DecoderUtil.java
No license file was found, but licenses were detected in source scan.

/*
* SingleXZInputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/SingleXZInputStream.java
No license file was found, but licenses were detected in source scan.

/*

* BCJ filter for little endian ARM instructions
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/simple/SimpleFilter.java
No license file was found, but licenses were detected in source scan.

/*
* LZMA2OutputStream
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*   Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/LZMA2OutputStream.java
No license file was found, but licenses were detected in source scan.

/*
* XZOutputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/XZOutputStream.java
No license file was found, but licenses were detected in source scan.

/*
* IndexEncoder
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/index/IndexEncoder.java
No license file was found, but licenses were detected in source scan.

/*
* CRC32
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/check/CRC32.java
No license file was found, but licenses were detected in source scan.

/*
* SeekableInputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/SeekableInputStream.java
No license file was found, but licenses were detected in source scan.

/*
* SimpleInputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/SimpleInputStream.java
No license file was found, but licenses were detected in source scan.

/*
* BCJOptions
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*

* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/BCJOptions.java
No license file was found, but licenses were detected in source scan.

/*
* LZMAEncoderFast
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*   Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/lzma/LZMAEncoderFast.java
No license file was found, but licenses were detected in source scan.

/*
* SeekableFileInputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/SeekableFileInputStream.java
No license file was found, but licenses were detected in source scan.

/*
* SimpleOutputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/SimpleOutputStream.java
No license file was found, but licenses were detected in source scan.

```
/*
* PowerPCOptions
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/PowerPCOptions.java
No license file was found, but licenses were detected in source scan.

```
/*
* Util
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/common/Util.java
No license file was found, but licenses were detected in source scan.

```
/*
* CountingOutputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/CountingOutputStream.java
No license file was found, but licenses were detected in source scan.

```
/*
* BCJ filter for big endian PowerPC instructions
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*          Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/simple/PowerPC.java
No license file was found, but licenses were detected in source scan.

/*
* IndexHash
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/index/IndexHash.java
No license file was found, but licenses were detected in source scan.

/*
* BCJ filter for x86 instructions
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*   Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/simple/X86.java
No license file was found, but licenses were detected in source scan.

/*
* LZMA2Coder
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/LZMA2Coder.java
No license file was found, but licenses were detected in source scan.

/*
* IndexDecoder
*

* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/index/IndexDecoder.java
No license file was found, but licenses were detected in source scan.

/*
* LZMA2InputStream
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*   Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/LZMA2InputStream.java
No license file was found, but licenses were detected in source scan.

/*
* LZMA2Decoder
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/LZMA2Decoder.java
No license file was found, but licenses were detected in source scan.

/*
* Matches
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*   Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):

* /xz-1-4-sources-1-jar/org/tukaani/xz/lz/Matches.java
No license file was found, but licenses were detected in source scan.

```
/*
* IndexIndicatorException
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/IndexIndicatorException.java
No license file was found, but licenses were detected in source scan.

```
/*
* FilterEncoder
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/FilterEncoder.java
No license file was found, but licenses were detected in source scan.

```
/*
* MemoryLimitException
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/MemoryLimitException.java
No license file was found, but licenses were detected in source scan.

```
/*
* BCJ filter for little endian ARM instructions
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*          Igor Pavlov <http://7-zip.org/>
*
```

* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/simple/ARM.java
No license file was found, but licenses were detected in source scan.

/*
* LZDecoder
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*   Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/lz/LZDecoder.java
No license file was found, but licenses were detected in source scan.

/*
* CRC32Hash
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*   Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/lz/CRC32Hash.java
No license file was found, but licenses were detected in source scan.

/*
* LZMADecoder
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*   Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/lzma/LZMADecoder.java

No license file was found, but licenses were detected in source scan.

/*
* RawCoder
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/RawCoder.java
No license file was found, but licenses were detected in source scan.

/*
* X86Options
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/X86Options.java
No license file was found, but licenses were detected in source scan.

/*
* IndexBase
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/index/IndexBase.java
No license file was found, but licenses were detected in source scan.

/*
* DeltaCoder
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.

*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/DeltaCoder.java
* /xz-1-4-sources-1-jar/org/tukaani/xz/delta/DeltaCoder.java
No license file was found, but licenses were detected in source scan.

/*
* Binary Tree match finder with 2-, 3-, and 4-byte hashing
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*   Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/lz/BT4.java
No license file was found, but licenses were detected in source scan.

/*
* FilterOptions
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*   Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/FilterOptions.java
No license file was found, but licenses were detected in source scan.

/**
* XZ data compression support.
*
* <h4>Introduction</h4>
* <p>
* This aims to be a complete implementation of XZ data compression
* in pure Java. Features:
*
* Full support for the .xz file format specification version 1.0.4
* Single-threaded streamed compression and decompression
* Single-threaded decompression with limited random access support
* Raw streams (no .xz headers) for advanced users, including LZMA2
*   with preset dictionary

```
* </ul>
* <p>
* Threading is planned but it is unknown when it will be implemented.
* <p>
* For the latest source code, see the
* <a href="http://tukaani.org/xz/java.html">home page of XZ for Java</a>.
*
* <h4>Getting started</h4>
* <p>
* Start by reading the documentation of {@link org.tukaani.xz.XZOutputStream}
* and {@link org.tukaani.xz.XZInputStream}.
* If you use XZ inside another file format or protocol,
 * see also {@link org.tukaani.xz.SingleXZInputStream}.
*
* <h4>Licensing</h4>
* <p>
* XZ for Java has been put into the public domain, thus you can do
* whatever you want with it. All the files in the package have been
* written by Lasse Collin and/or Igor Pavlov.
* <p>
* This software is provided "as is", without any warranty.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/package-info.java
No license file was found, but licenses were detected in source scan.

```
/*
* BCJ filter for SPARC instructions
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*          Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/simple/SPARC.java
No license file was found, but licenses were detected in source scan.

```
/*
* Optimum
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*          Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
```

* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/lzma/Optimum.java
No license file was found, but licenses were detected in source scan.

/*
* RangeEncoder
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*   Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/rangecoder/RangeEncoder.java
No license file was found, but licenses were detected in source scan.

/*
* BCJ filter for little endian ARM-Thumb instructions
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*   Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/simple/ARMThumb.java
No license file was found, but licenses were detected in source scan.

/*
* FilterDecoder
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/FilterDecoder.java
No license file was found, but licenses were detected in source scan.

/*
* IA64Options
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/IA64Options.java
No license file was found, but licenses were detected in source scan.

/*
* BlockInfo
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/index/BlockInfo.java
No license file was found, but licenses were detected in source scan.

/*
* Check
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/check/Check.java
No license file was found, but licenses were detected in source scan.

/*
* UncompressedLZMA2OutputStream
*
* Author: Lasse Collin <lasse.collin@tukaani.org>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/UncompressedLZMA2OutputStream.java
No license file was found, but licenses were detected in source scan.

```
/*
* LZMACoder
*
* Authors: Lasse Collin <lasse.collin@tukaani.org>
*          Igor Pavlov <http://7-zip.org/>
*
* This file has been put into the public domain.
* You can do whatever you want with this file.
*/
```

Found in path(s):
* /xz-1-4-sources-1-jar/org/tukaani/xz/lzma/LZMACoder.java

1.680 ehcache-core 2.6.10

1.680.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/**
*  Copyright Terracotta, Inc.
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*/
/**
    * Returns a list of all element keys in the cache, whether or not they are expired.
    * <p/>
    * The returned keys are unique and can almost be considered a set. See {@link net.sf.ehcache.store.CacheKeySet
CacheKeySet} for
    * more details.
    * <p/>
    * The List returned is not live. It is a copy.
     * <p/>
    * The time taken is O(n). On a single CPU 1.8Ghz P4, approximately 8ms is required
```

```
   * for each 1000 entries.
   *
   * @return a list of {@link Object} keys
   * @throws IllegalStateException if the cache is not {@link Status#STATUS_ALIVE}
   * @see net.sf.ehcache.store.CacheKeySet
   */
```

Found in path(s):
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/Cache.java
No license file was found, but licenses were detected in source scan.

```
/**
* Copyright 2006 Thomas Hawtin
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/lang/VicariousThreadLocal.java
No license file was found, but licenses were detected in source scan.

```
/**
*  Copyright Terracotta, Inc.
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*/
```

Found in path(s):

* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/PoolableStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/statistics/LiveCacheStatisticsWrapper.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/ManagementRESTServiceConfiguration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/AtomicLongSequence.java
*
 /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/ClusterOperation.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/SingletonEhCacheRegionFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/CacheManagerPeerProviderFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/terracotta/TerracottaClientRejoinListener.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/compound/SerializationCopyStrategy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/WeakIdentityConcurrentMap.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/TransactionTimeoutException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/compound/ReadWriteSerializationCopyStrategy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/XidTransactionIDSerializedForm.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/OperationsFilter.java
*
 /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/ElementValueComparatorConfigurationElement.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/AgentSizeOf.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/MemoryOnlyStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/cluster/NoopCacheCluster.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/event/CacheManagerEventListenerRegistry.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/disk/ods/AATreeSet.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/management/api/HibernateStats.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/manager/selector/AtomikosSelector.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/ObjectGraphWalker.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/management/api/EhcacheStats.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/impl/AtomicPoolAccessor.java
*
 /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/attribute/ReflectionAttributeExtractor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/TransactionIDImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/ManagedCacheManagerPeerProvider.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/EhcacheJtaTransactionManagerLookup.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/statistics/CacheUsageListener.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/impl/FromLargestCacheOnDiskPoolEvictor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/AbstractEhcacheProvider.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/CacheConfigurationListener.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/exceptionhandler/CacheExceptionHandlerFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/LfuPolicy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/terracotta/ClusteredInstanceFactoryWrapper.java
*
 /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/DelegatingTransactionIDFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/NamedThreadFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/NotifyingMemoryStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/TerracottaClientConfiguration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/impl/AbstractPool.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/ratestatistics/AtomicRateStatistic.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/impl/OrderComparator.java

* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/blocking/BlockingCache.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/generator/ConfigurationGenerator.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/MaxDepthExceededException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/GreaterThan.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/MemoryUnit.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/TerracottaStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/CacheEntry.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/PoolAccessor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/WriteBehind.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/Element.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/RMICacheReplicatorFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/SerializableXid.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/manager/selector/WeblogicSelector.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/DefaultElementEvictionData.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/PreferTCCLObjectInputStream.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/EhCacheRegionFactory.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/provider/MBeanRegistrationProviderImpl.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/constructs/nonstop/store/TransactionalExecutorServiceStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/DiskStoreBootstrapCacheLoader.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/PoolEvictor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/aggregator/Aggregator.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/management/impl/BeanUtils.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/DeleteAllOperation.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/AbstractEhcacheRegionFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/terracotta/TerracottaBootstrapCacheLoader.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/statistics/sampled/CacheStatisticsSampler.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/impl/ResultImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/disk/ods/FileAllocationTree.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/CacheConfiguration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/Configuration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/aggregator/Min.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/management/impl/EhcacheStatsImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/SlewClock.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonStopCacheException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/impl/FromLargestCacheOnHeapPoolEvictor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/CacheTransactionHelper.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/NonstopStore.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/AbstractSoftLockManager.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/concurrent/CacheLockProvider.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/impl/BoundedPool.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/strategy/TransactionalEhcacheEntityRegionAccessStrategy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/WriteBehindQueueManager.java

* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/RejoinAwareNonstopStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/management/impl/EhcacheHibernate.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/manager/selector/GlassfishSelector.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/FrontEndCacheTier.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/impl/DynamicSearchChecker.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/strategy/ReadOnlyEhcacheEntityRegionAccessStrategy.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/CachePeer.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/SearchAttribute.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/FactoryConfigurationElement.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/CopyStrategyConfiguration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/aggregator/AggregatorException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/TransactionAwareAttributeExtractor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/statistics/LiveCacheStatistics.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/event/CacheEventListenerFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/CacheStoreHelper.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/constructs/nonstop/concurrency/ExplicitLockingContextThreadLocal.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/management/impl/CollectionStats.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/processor/XARequest.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/Not.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/CacheManager.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/sampled/ComprehensiveCacheSampler.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/CacheManagerPeerListenerFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/PinningConfiguration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/manager/selector/JndiSelector.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/SizeOfPolicyConfigurationElement.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/attribute/AttributeType.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/Decision.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/ConfigurationHelper.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/terracotta/ClusteredInstanceFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/filter/PassThroughFilter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/SingleOperationType.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/LessThan.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/impl/AbstractFromLargestCachePoolEvictor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/RmiEventMessage.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/PinningConfigurationElement.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/util/CountingThreadFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/TimeUtil.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/StripedReadWriteLockProvider.java
*

/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/commands/AbstractStoreCommand.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/RMISynchronousCacheReplicator.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/RMIBootstrapCacheLoader.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/EhcacheXAResourceImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/Searchable.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/ReflectionSizeOf.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/EhcacheDecoratorAdapter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/management/impl/EntityStats.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/CacheManagerMBean.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/ratestatistics/package-info.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/TransactionIDSerializedForm.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/cluster/ClusterSchemeNotAvailableException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/impl/BalancedAccessOnHeapPoolEvictor.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/CacheWriterConfigurationElement.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/SingletonEhCacheProvider.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/SoftLockManagerImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/filter/SizeOfFilter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/LargeSet.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/chm/SelectableConcurrentHashMap.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/impl/ResultsImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/Direction.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/counter/sampled/SampledRateCounterConfig.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/management/impl/NullHibernateStats.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/TransactionalRMICachePeer.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/FifoPolicy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/RMICachePeer.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/generator/model/SimpleNodeAttribute.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/ReadCommittedSoftLockImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/exceptionhandler/CacheExceptionHandler.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/CoalesceKeysFilter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/SizeOf.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/JvmInformation.java
*
/ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/strategy/ReadWriteEhcacheEntityRegionAccessStrategy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/RMIBootstrapCacheLoaderFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/ElementValueComparator.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/TransactionIDNotFoundException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/MemoryEfficientByteArrayOutputStream.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/regions/EhcacheTransactionalDataRegion.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/AbstractTransactionIDFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/RemoteCacheException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/impl/DefaultSizeOfEngine.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/counter/sampled/SampledRateCounterImpl.java
*

/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/TerracottaConfiguration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/management/impl/AggregateCacheRegionStats.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/management/impl/ProviderMBeanRegistrationHelper.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/concurrency/NonStopCacheKeySet.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/UnsafeSizeOf.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/SoftLockFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/EhCache.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/ratestatistics/AbstractRateStatistic.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/NotEqualTo.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/sampled/CacheSamplerImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/TimeProviderLoader.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/commands/StoreRemoveCommand.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/EhcacheInit.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/MimeTypeByteArray.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/counter/CounterImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/CacheWriter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/counter/Counter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/BaseCriteria.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/counter/sampled/SampledCounter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/exceptionhandler/ExceptionHandlingDynamicCacheProxy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/RMICacheManagerPeerListenerFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/management/impl/HibernateStatsImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/management/impl/BaseEmitterBean.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/event/NotificationScope.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/concurrent/Sync.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/event/TerracottaCacheEventReplication.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/manager/selector/NullSelector.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/LruPolicy.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/management/provider/MBeanRegistrationProviderException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/ManagementServer.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/AbstractCacheConfigurationListener.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/EhcacheCoreInit.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/VmUtils.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/attribute/JavaBeanAttributeExtractor.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/manager/TransactionManagerLookup.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/Timestamper.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/filter/AnnotationProxyFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/ElementIdAssigningStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/ReadCommittedSoftLockFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/ThrowTimeoutException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/blocking/CacheEntryFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/EhcacheXAResource.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/impl/GroupedResultImpl.java

* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/EventMessage.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/counter/sampled/SampledCounterImpl.java
*
 /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/Store.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/event/RegisteredEventListeners.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/ElementValueComparatorConfiguration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/TaskNotSubmittedTimeoutException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/disk/HashEntry.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/Statistics.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/RMICacheManagerPeerListener.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/SizeOfPolicyConfiguration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/WriteBehindManager.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/LegacyStoreWrapper.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/extension/CacheExtensionFactory.java
*
 /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/management/impl/EhcacheHibernateMBeanRegistration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/PropertyUtil.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/AbstractStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/Query.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/provider/NullMBeanRegistrationProvider.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/local/LocalTransactionContext.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/Size.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/LocalReadsOnTimeoutStore.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/strategy/TransactionalEhcacheCollectionRegionAccessStrategy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/SoftLockID.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/compound/CopyStrategy.java
*
 /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/impl/AbstractBalancedAccessEvictor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/NoOpOnTimeoutStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/TransactionID.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/generator/ConfigurationUtil.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/StoreQuery.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/LongSequence.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/DefaultCacheConfigurationElement.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/generator/model/NodeAttribute.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/aggregator/Count.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/SingleOperation.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/AbstractPolicy.java
*
 /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/blocking/SelfPopulatingCache.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/generator/model/SimpleNodeElement.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/compound/LegacyCopyStrategyAdapter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/generator/model/NodeElement.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/counter/CounterConfig.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/concurrent/ReadWriteLockSync.java

* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonstopExecutorService.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/concurrency/NonstopSync.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/generator/model/elements/ConfigurationElement.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/ResourceClassLoader.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/AgentLoader.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/CircularLossyQueue.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/impl/BalancedAccessOnDiskPoolEvictor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/ClusterOperationCallable.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/EhcacheXAException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/BatchOperation.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/blocking/LockTimeoutException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/UpdateChecker.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writethrough/WriteThroughManager.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/aggregator/Max.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/WriteOperation.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/event/TerracottaCacheEventReplicationFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/annotations/IgnoreSizeOf.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/ConfigurationFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/ILike.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/filter/AnnotationSizeOfFilter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/CacheManagerPeerProvider.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/FeaturesManager.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/constructs/nonstop/concurrency/CacheOperationUnderExplicitLockCallable.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/constructs/nonstop/store/NonstopTimeoutBehaviorStoreResolver.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/disk/DiskStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/concurrent/ConcurrencyUtil.java
*
/ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/constructs/nonstop/concurrency/LockOperationTimedOutNonstopException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/AbstractCacheWriter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/disk/StoreUpdateException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/ConfigError.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/sampled/SampledCacheManager.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/ccs/EhcacheReadWriteCache.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/impl/StrictlyBoundedPool.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/sampled/CacheManagerSampler.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/ManagementServerLoader.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/concurrent/StripedReadWriteLock.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/NotILike.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/SoftLockHelper.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/ExceptionOnTimeoutStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/InCollection.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/event/CacheEventListener.java

* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/processor/XARequestProcessor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/processor/XAThreadPool.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/ratestatistics/UnlockedRateStatistic.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/MulticastKeepaliveHeartbeatReceiver.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/sampled/SampledCache.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/CacheConfigurationMBean.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/RejoinAwareBlockingOperation.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/management/impl/CacheRegionUtils.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/NonstopConfiguration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/CacheWriterManagerException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/terracotta/InternalEhcache.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/manager/selector/Selector.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/CacheReplicator.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/constructs/nonstop/concurrency/ExplicitLockingClusterOperation.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/strategy/ReadWriteEhcacheCollectionRegionAccessStrategy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/LibraryInit.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/terracotta/TerracottaClusteredInstanceHelper.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/ExpiredTransactionIDImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/impl/AbstractPoolAccessor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/CacheConfiguration.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/management/provider/MBeanRegistrationProviderFactoryImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/commands/StorePutCommand.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/counter/CounterManagerImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/ElementIdHelper.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/terracotta/KeySnapshotter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/disk/DiskSizeOfEngine.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/ratestatistics/RateStatistic.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/WriteBehindQueue.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/cluster/ClusterScheme.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/blocking/UpdatingSelfPopulatingCache.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/NullStore.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/strategy/NonStrictReadWriteEhcacheEntityRegionAccessStrategy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/MulticastKeepaliveHeartbeatSender.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/constructs/nonstop/concurrency/NonstopCacheLockProvider.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/PersistenceConfiguration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/extension/CacheExtension.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/MemoryStoreEvictionPolicy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/generator/model/NodeElementVisitor.java
*

/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/local/JtaLocalTransactionStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonstopThreadPool.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/ccs/EhcacheReadOnlyCache.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/Between.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/CacheStatistics.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/constructs/nonstop/concurrency/NonstopThreadUniqueIdProvider.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/TierableStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/CacheStatisticsMBean.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/sampled/SampledEhcacheMBeans.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/DynamicSearchListener.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/cluster/ClusterTopologyListener.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/provider/MBeanRegistrationProviderFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/Policy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/CacheManager.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/impl/UnboundedPool.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/KeyBasedOperation.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/statistics/sampled/SampledCacheStatistics.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/attribute/AttributeExtractor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/Or.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/statistics/NullLiveCacheStatisticsData.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/sampled/SampledCacheMBean.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/DiskStoreConfigurationElement.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/management/impl/CacheRegionStats.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/counter/CounterManager.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/nonstop/NonstopAwareCollectionRegionAccessStrategy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/counter/sampled/SampledRateCounter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/CacheKeySet.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonstopThread.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/management/impl/EhcacheHibernateMbeanNames.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/CacheException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/concurrency/ExplicitLockingContext.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/blocking/UpdatingCacheEntryFactory.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/LessThanOrEqual.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/management/api/EhcacheHibernateMBean.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/CacheManagerPeerListener.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/SoftLock.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/nonstop/HibernateNonstopCacheExceptionHandler.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/classloader/ClassLoaderAwareCache.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/TimeoutBehaviorConfigurationElement.java

* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/generator/model/AbstractDepthFirstVisitor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/Criteria.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/aggregator/Sum.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/attribute/DynamicAttributesExtractor.java
*
 /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/generator/model/XMLGeneratorVisitor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/event/CacheManagerEventListenerFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/FailSafeTimer.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/management/sampled/SampledMBeanRegistrationProvider.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/SearchException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/ObjectExistsException.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/TerracottaConfigurationElement.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/ManagementRESTServiceConfigurationElement.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/aggregator/Average.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/DeadLockException.java
*
 /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/compound/NullReadWriteCopyStrategy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/regions/EhcacheQueryResultsRegion.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/strategy/ReadOnlyEhcacheCollectionRegionAccessStrategy.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/constructs/nonstop/concurrency/InvalidLockStateAfterRejoinException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/impl/SearchManager.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/PersistenceConfigurationElement.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/TerracottaConfigConfigurationElement.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/provider/MBeanRegistrationProvider.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/statistics/sampled/NullSampledCacheStatistics.java
*
 /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/DefaultElementValueComparator.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/statistics/sampled/SampledCacheStatisticsImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/Ehcache.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/disk/ElementSubstituteFilter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/generator/model/AbstractNodeElement.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/regions/EhcacheEntityRegion.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/CacheInitializationHelper.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/TransactionException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/ExecutorServiceStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/MergedEnumeration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/disk/Segment.java
*
 /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/strategy/EhcacheAccessStrategyFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/WriteAllOperation.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/TransactionInterruptedException.java

* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/regions/EhcacheDataRegion.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/commands/Command.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/TimeoutBehaviorConfiguration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/filter/CombinationSizeOfFilter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonstopExecutorServiceFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/attribute/AttributeExtractorException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/attribute/KeyObjectAttributeExtractor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/util/OverrideCheck.java
*
 /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/SoftLockManager.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/TransactionController.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/CastingOperationConverter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/XATransactionContext.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/ElementEvictionData.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/DiskStoreConfiguration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/compound/ImmutableValueElementCopyStrategy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/BeanHandler.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/AbstractTransactionStore.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/NonstopConfigurationElement.java
*
 /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/Pool.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/FindBugsSuppressWarnings.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/operations/DeleteOperation.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/XAExecutionListener.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/event/CacheEventListenerAdapter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/disk/ods/Region.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/CacheManagerExecutorServiceFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/manager/DefaultTransactionManagerLookup.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/Result.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/sampled/CacheManagerSamplerImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/AlwaysMatch.java
*
 /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/loader/CacheLoaderFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/NullResults.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/XidTransactionID.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/management/impl/QueryStats.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/FactoryConfiguration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/ccs/EhcacheNonstrictReadWriteCache.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/NonstopStoreImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/nonstop/NonstopAccessStrategyFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/ExpiredXidTransactionIDImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/DiskBackedMemoryStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/CacheWriterManager.java
*
 /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/management/impl/EhcacheHibernateMBeanRegistrationImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/RMIAsynchronousCacheReplicator.java

* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/event/NonstopCacheEventListener.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/StoreListener.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/counter/sampled/TimeStampedCounterValue.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/attribute/ValueObjectAttributeExtractor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/Cache.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/cluster/CacheCluster.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/Disposable.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/SizeOfEngine.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/disk/DiskStorageFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/sampled/Utils.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/terracotta/DisconnectedClusterNode.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/aggregator/Aggregators.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/ConfigurableRMIClientSocketFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/strategy/EhcacheAccessStrategyFactoryImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/EqualTo.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/manager/selector/FactorySelector.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/MemoryLimitedCacheLoader.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/terracotta/RotatingSnapshotFile.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/CacheQuery.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/terracotta/TerracottaClient.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonstopExecutorServiceImpl.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/CacheMBean.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/XidTransactionIDImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/bootstrap/BootstrapCacheLoader.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/manager/selector/BitronixSelector.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/TransactionIDFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/DiskStorePathManager.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/CacheWriterConfiguration.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/ManagementService.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/GreaterThanOrEqual.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/CacheConfigurationElement.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/DiskStoreBootstrapCacheLoaderFactory.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/Status.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/sampled/CacheSampler.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/local/TransactionListener.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/terracotta/TerracottaNotRunningException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/classloader/InternalClassLoaderAwareCache.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/concurrent/StripedReadWriteLockSync.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/impl/BaseQueryInterpreter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/Results.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/strategy/AbstractEhcacheAccessStrategy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/ProductInfo.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/nonstop/NonstopAwareEntityRegionAccessStrategy.java

*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/statistics/LiveCacheStatisticsImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/ManualRMICacheManagerPeerProvider.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/SetAsList.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/HibernateUtil.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/RMICacheManagerPeerProviderFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/OptimisticLockFailureException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/event/CacheManagerEventListener.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/terracotta/TerracottaCacheCluster.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/AggregateIterator.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/And.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/statistics/LiveCacheStatisticsData.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/impl/BaseResult.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/local/LocalTransactionStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/impl/AggregateOnlyResult.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/ClassLoaderUtil.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/sampled/SampledCacheManagerMBean.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/impl/LockedPoolAccessor.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/compound/ReadWriteCopyStrategy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/Store.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/strategy/NonStrictReadWriteEhcacheCollectionRegionAccessStrategy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/MemoryStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/regions/EhcacheTimestampsRegion.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/RMICacheManagerPeerProvider.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/MemorySizeParser.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/store/ClusterOperationCallableImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/CacheWriterFactory.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/CopyStrategyConfigurationElement.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/AbstractWriteBehindQueue.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/disk/ods/RegionSet.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/web/ShutdownListener.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/generator/ConfigurationSource.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/CacheConfigError.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/loader/CacheLoader.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/concurrent/LockType.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/EhCacheProvider.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonstopTimeoutBehaviorFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/LoaderTimeoutException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/aggregator/AggregatorInstance.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/terracotta/SerializationHelper.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/Attribute.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/ccs/AbstractEhcacheConcurrencyStrategy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/FlyweightType.java

* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/LegacyEventMessage.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/manager/selector/GenericJndiSelector.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/xa/XATransactionStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/counter/sampled/SampledCounterConfig.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/MulticastRMICacheManagerPeerProvider.java
* /ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/config/generator/model/elements/SearchableConfigurationElement.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/manager/selector/ClassSelector.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/statistics/sampled/SampledCacheStatisticsWrapper.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/regions/EhcacheGeneralDataRegion.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/config/InvalidConfigurationException.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/local/LocalRecoveryManager.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/writer/writebehind/OperationConverter.java
*
/ehcache-core-2-6-10-sources-1-
jar/net/sf/ehcache/hibernate/strategy/AbstractReadWriteEhcacheAccessStrategy.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/cluster/ClusterNode.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/store/LruMemoryStore.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/bootstrap/BootstrapCacheLoaderFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/search/expression/ComparableValue.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/terracotta/TerracottaBootstrapCacheLoaderFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/distribution/PayloadUtil.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/CacheDecoratorFactory.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/management/sampled/ComprehensiveCacheSamplerImpl.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/util/LargeCollection.java
*
/ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/hibernate/regions/EhcacheCollectionRegion.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/filter/ResourceSizeOfFilter.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/constructs/nonstop/NonstopActiveDelegateHolder.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/pool/sizeof/PrimitiveType.java
* /ehcache-core-2-6-10-sources-1-jar/net/sf/ehcache/transaction/TransactionIDFactoryImpl.java

1.681 autoprefixer 9.8.8

1.681.1 Available under license :

MIT
The MIT License (MIT)

Copyright 2013 Andrey Sitnik <andrey@sitnik.ru>

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.682 fbjs 0.8.18

1.682.1 Available under license :

MIT License

Copyright (c) 2013-present, Facebook, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.683 asn1 0.2.6

1.683.1 Available under license :

Copyright (c) 2011 Mark Cavage, All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights

to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE
MIT

1.684 postcss 7.0.39

1.684.1 Available under license :

MIT
The MIT License (MIT)

Copyright 2013 Andrey Sitnik <andrey@sitnik.ru>

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.685 clean-css 4.2.4

1.685.1 Available under license :

MIT
Copyright (C) 2017 JakubPawlowicz.com

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is furnished
to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER
DEALINGS IN THE SOFTWARE.

1.686 swagger-models 2.1.11

1.686.1 Available under license :

No license file was found, but licenses were detected in source scan.

/**
* Copyright 2017 SmartBear Software
* <p>
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
* <p>
* http://www.apache.org/licenses/LICENSE-2.0
* <p>
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/BooleanSchema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/headers/Header.java

* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/servers/ServerVariables.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/parameters/Parameter.java
*
 /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/security/Scopes.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/Components.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/ByteArraySchema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/links/LinkParameter.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/ComposedSchema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/ExternalDocumentation.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/parameters/QueryParameter.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/FileSchema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/ArraySchema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/security/OAuthFlows.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/DateSchema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/parameters/PathParameter.java
*
 /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/XML.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/tags/Tag.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/BinarySchema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/NumberSchema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/responses/ApiResponses.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/ObjectSchema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/links/Link.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/MapSchema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/DateTimeSchema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/Operation.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/UUIDSchema.java
*
 /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/Schema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/examples/Example.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/security/OAuthFlow.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/EncodingProperty.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/PathItem.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/MediaType.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/StringSchema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/servers/Server.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/OpenAPI.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/responses/ApiResponse.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/info/Info.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/PasswordSchema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/Encoding.java
*
 /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/Content.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/servers/ServerVariable.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/IntegerSchema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/security/SecurityScheme.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/security/SecurityRequirement.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/Paths.java

* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/parameters/CookieParameter.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/media/EmailSchema.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/parameters/RequestBody.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/info/Contact.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/callbacks/Callback.java
*
/swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/parameters/HeaderParameter.java
* /swagger-models-2-1-11-sources-jar/io/swagger/v3/oas/models/info/License.java

1.687 snapdragon 0.8.2

1.687.1 Available under license :

MIT

1.688 rc 1.2.8

1.688.1 Available under license :

UNRECOGNIZED LICENSE; MD5 sum: dcf8f74e9fad2b9d45a0c5d70eba335d
The MIT License

Copyright (c) 2011 Dominic Tarr

Permission is hereby granted, free of charge,
to any person obtaining a copy of this software and
associated documentation files (the "Software"), to
deal in the Software without restriction, including
without limitation the rights to use, copy, modify,
merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom
the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice
shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR
ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Apache License, Version 2.0

Copyright (c) 2011 Dominic Tarr

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Copyright (c) 2013, Dominic Tarr
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
 SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The views and conclusions contained in the software and documentation are those
of the authors and should not be interpreted as representing official policies,
either expressed or implied, of the FreeBSD Project.

1.689 strip-json-comments 2.0.1

1.689.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.690 to-object-path 0.3.0

1.690.1 Available under license :

MIT

1.691 snapdragon-node 2.1.1

1.691.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.692 has-value 1.0.0

1.692.1 Available under license :

Creative Commons Legal Code

CC0 1.0 Universal

> CREATIVE COMMONS CORPORATION IS NOT A LAW FIRM AND DOES NOT PROVIDE LEGAL SERVICES. DISTRIBUTION OF THIS DOCUMENT DOES NOT CREATE AN ATTORNEY-CLIENT RELATIONSHIP. CREATIVE COMMONS PROVIDES THIS INFORMATION ON AN "AS-IS" BASIS. CREATIVE COMMONS MAKES NO WARRANTIES REGARDING THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER, AND DISCLAIMS LIABILITY FOR DAMAGES RESULTING FROM THE USE OF THIS DOCUMENT OR THE INFORMATION OR WORKS PROVIDED HEREUNDER.

Statement of Purpose

The laws of most jurisdictions throughout the world automatically confer exclusive Copyright and Related Rights (defined below) upon the creator and subsequent owner(s) (each and all, an "owner") of an original work of authorship and/or a database (each, a "Work").

Certain owners wish to permanently relinquish those rights to a Work for the purpose of contributing to a commons of creative, cultural and scientific works ("Commons")
that the public can reliably and without fear
of later claims of infringement build upon, modify, incorporate in other works, reuse and redistribute as freely as possible in any form whatsoever and for any purposes, including without limitation commercial purposes. These owners may contribute to the Commons to promote the ideal of a free culture and the further production of creative, cultural and scientific works, or to gain reputation or greater distribution for their Work in part through the use and efforts of others.

For these and/or other purposes and motivations, and without any expectation of additional consideration or compensation, the person associating CC0 with a Work (the "Affirmer"), to the extent that he or she is an owner of Copyright and Related Rights in the Work, voluntarily elects to apply CC0 to the Work and publicly distribute the Work under its terms, with knowledge of his or her Copyright and Related Rights in the

Work and the meaning and intended legal
effect of CC0 on those rights.

1. Copyright and Related Rights. A Work made available under CC0 may be protected by copyright and related or neighboring rights ("Copyright and Related Rights"). Copyright and Related Rights include, but are not limited to, the following:

i. the right to reproduce, adapt, distribute, perform, display, communicate, and translate a Work;
ii. moral rights retained by the original author(s) and/or performer(s);
iii. publicity and privacy rights pertaining to a person's image or likeness depicted in a Work;
iv. rights protecting against unfair competition in regards to a Work, subject to the limitations in paragraph 4(a), below;
v. rights protecting the extraction, dissemination, use and reuse of data in a Work;
vi. database rights (such as those arising under Directive 96/9/EC of the European Parliament and of the Council of 11 March 1996 on the legal protection of databases, and under any national implementation

thereof, including any amended or successor version of such directive); and
vii. other similar, equivalent or corresponding rights throughout the world based on applicable law or treaty, and any national implementations thereof.

2. Waiver. To the greatest extent permitted by, but not in contravention of, applicable law, Affirmer hereby overtly, fully, permanently, irrevocably and unconditionally waives, abandons, and surrenders all of Affirmer's Copyright and Related Rights and associated claims and causes of action, whether now known or unknown (including existing as well as future claims and causes of action), in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "Waiver"). Affirmer makes the
Waiver for the benefit of each
member of the public at large and to the detriment of Affirmer's heirs and successors, fully intending that such Waiver shall not be subject to revocation, rescission, cancellation, termination, or any other legal or equitable action to disrupt the quiet enjoyment of the Work by the public as contemplated by Affirmer's express Statement of Purpose.

3. Public License Fallback. Should any part of the Waiver for any reason be judged legally invalid or ineffective under applicable law, then the Waiver shall be preserved to the maximum extent permitted taking into

account Affirmer's express Statement of Purpose. In addition, to the extent the Waiver is so judged Affirmer hereby grants to each affected person a royalty-free, non transferable, non sublicensable, non exclusive, irrevocable and unconditional license to exercise Affirmer's Copyright and Related Rights in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable
law or treaty (including future
time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "License"). The License shall be deemed effective as of the date CC0 was applied by Affirmer to the Work. Should any part of the License for any reason be judged legally invalid or ineffective under applicable law, such partial invalidity or ineffectiveness shall not invalidate the remainder of the License, and in such case Affirmer hereby affirms that he or she will not (i) exercise any of his or her remaining Copyright and Related Rights in the Work or (ii) assert any associated claims and causes of action with respect to the Work, in either case contrary to Affirmer's express Statement of Purpose.

4. Limitations and Disclaimers.

a. No trademark or patent rights held by Affirmer are waived, abandoned, surrendered, licensed or otherwise affected
by this document.
b. Affirmer offers the Work as-is and makes no representations or warranties of any kind concerning the Work, express, implied, statutory or otherwise, including without limitation warranties of title, merchantability, fitness for a particular purpose, non infringement, or the absence of latent or other defects, accuracy, or the present or absence of errors, whether or not discoverable, all to the greatest extent permissible under applicable law.
c. Affirmer disclaims responsibility for clearing rights of other persons that may apply to the Work or any use thereof, including without limitation any person's Copyright and Related Rights in the Work. Further, Affirmer disclaims responsibility for obtaining any necessary consents, permissions or other rights required for any use of the Work.
d. Affirmer understands and acknowledges that Creative Commons is not a party to this document and has no duty or obligation with
respect to
this CC0 or use of the Work.

1.693 repeat-element 1.1.4

1.693.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015-present, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.694 union-value 1.0.1

1.694.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.695 source-map-resolve 0.5.3

1.695.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014, 2015, 2016, 2017, 2018, 2019 Simon Lydell
Copyright (c) 2019 ZHAO Jinxiang

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN
ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.696 split-string 3.1.0

1.696.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is

furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.697 json-stable-stringify-without-jsonify 1.0.1

1.697.1 Available under license :

This software is released under the MIT license:

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.698 http-proxy 1.18.1

1.698.1 Available under license :

MIT

node-http-proxy

Copyright (c) 2010-2016 Charlie Robbins, Jarrett Cruger & the Contributors.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER
IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.699 pascalcase 0.1.1

1.699.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF

OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.700 has-values 1.0.0

1.700.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.701 object-copy 0.1.0

1.701.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in

all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.702 is-extendable 0.1.1

1.702.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.703 requires-port 1.0.0

1.703.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 Unshift.io, Arnout Kazemier, the Contributors.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.704 map-cache 0.2.2

1.704.1 Available under license :

MIT

1.705 is-descriptor 0.1.6

1.705.1 Available under license :

MIT

1.706 mixin-deep 1.3.2

1.706.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2015, 2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in

all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.707 require-directory 2.1.1

1.707.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2011 Troy Goode <troygoode@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.708 posix-character-classes 0.1.1

1.708.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016-2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.709 static-extend 0.1.2

1.709.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

MIT

1.710 kind-of 6.0.3

1.710.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.711 object.pick 1.3.0

1.711.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2016, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.712 is-buffer 1.1.6

1.712.1 Available under license :

The MIT License (MIT)

Copyright (c) Feross Aboukhadijeh

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.713 js-yaml 3.14.1

1.713.1 Available under license :

MIT
(The MIT License)

Copyright (C) 2011-2015 by Vitaly Puzrin

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.714 is-windows 1.0.2

1.714.1 Available under license :

MIT

1.715 nanomatch 1.2.13

1.715.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2016-2018, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.716 use 3.1.1

1.716.1 Available under license :

MIT

1.717 is-stream 1.1.0

1.717.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.718 unset-value 1.0.0

1.718.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, 2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal

in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.719 is-data-descriptor 0.1.4

1.719.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.720 ret 0.1.15

1.720.1 Available under license :

MIT

1.721 repeat-string 1.6.1

1.721.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2015, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.
MIT

1.722 to-regex 3.0.2

1.722.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2016-2018, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal

in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.723 micromatch 3.1.10

1.723.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2018, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.724 type-detect 4.0.8

1.724.1 Available under license :

Copyright (c) 2013 Jake Luer <jake@alogicalparadox.com> (http://alogicalparadox.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.725 mime 1.6.0

1.725.1 Available under license :

The MIT License (MIT)

Copyright (c) 2010 Benjamin Thomas, Robert Kieffer

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.726 is-accessor-descriptor 0.1.6

1.726.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.727 object-visit 1.0.1

1.727.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, 2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.728 regex-not 1.0.2

1.728.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2016, 2018, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.729 map-visit 1.0.0

1.729.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015-2016, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.730 set-value 2.0.1

1.730.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.731 resolve-url 0.2.1

1.731.1 Available under license :

The MIT License (MIT)

Copyright (c) 2013 Simon Lydell

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.732 safe-regex 1.1.0

1.732.1 Available under license :

This software is released under the MIT license:

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.733 ini 1.3.8

1.733.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.734 source-map-url 0.4.1

1.734.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Simon Lydell

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.735 snapdragon-util 3.0.1

1.735.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.736 urix 0.1.0

1.736.1 Available under license :

The MIT License (MIT)

Copyright (c) 2013 Simon Lydell

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal

in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.737 tapable 1.1.3

1.737.1 Available under license :

The MIT License

Copyright (c) Tobias Koppers @sokra

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.738 prr 1.0.1

1.738.1 Available under license :

MIT
The MIT License (MIT)
==========

Copyright (c) 2014 Rod Vagg

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.739 pify 2.3.0

1.739.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.740 setimmediate 1.0.5

1.740.1 Available under license :

Copyright (c) 2012 Barnesandnoble.com, llc, Donavon West, and Domenic Denicola

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.741 next-tick 1.1.0

1.741.1 Available under license :

ISC
ISC License

Copyright (c) 2012-2020, Mariusz Nowak, @medikoo, medikoo.com

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH

REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.742 lowercase-keys 1.0.1

1.742.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.743 pify 4.0.1

1.743.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.744 type 1.2.0

1.744.1 Available under license :

MIT

1.745 make-dir 2.1.0

1.745.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.746 worker-farm 1.7.0

1.746.1 Available under license :

MIT

1.747 buffer-xor 1.0.3

1.747.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Daniel Cousens

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.748 tty-browserify 0.0.0

1.748.1 Available under license :

This software is released under the MIT license:

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.749 nth-check 1.0.2

1.749.1 Available under license :

BSD-2-Clause
Copyright (c) Felix Bhm
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS;
OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS,
EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.750 homedir-polyfill 1.0.3

1.750.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2016 Brian Woodward

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal

in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.751 is-relative 1.0.0

1.751.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.752 parse-filepath 1.0.2

1.752.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2015, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.753 hash.js 1.1.7

1.753.1 Available under license :

MIT

1.754 array-uniq 1.0.3

1.754.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.755 https-browserify 1.0.0

1.755.1 Available under license :

MIT
This software is released under the MIT license:

Copyright (c) James Halliday

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.756 console-browserify 1.2.0

1.756.1 Available under license :

MIT
Copyright (c) 2012 Raynos.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.757 create-hmac 1.1.7

1.757.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017 crypto-browserify contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.758 path-root-regex 0.1.2

1.758.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.759 util 0.11.1

1.759.1 Available under license :

MIT
Copyright Joyent, Inc. and other Node contributors. All rights reserved.
Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.760 ripemd160 2.0.2

1.760.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 crypto-browserify

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.761 detect-file 1.0.0

1.761.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016-2017, Brian Woodward.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.762 cssesc 3.0.0

1.762.1 Available under license :

Copyright Mathias Bynens <https://mathiasbynens.be/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.763 react-lifecycles-compat 3.0.4

1.763.1 Available under license :

MIT

1.764 object-map 1.0.1

1.764.1 Available under license :

Copyright (c) 2014-2017, Jon Schlinkert, contributors.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.765 crypto-browserify 3.12.0

1.765.1 Available under license :

The MIT License

Copyright (c) 2013 Dominic Tarr

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice
shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR
ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.766 parse-json 2.2.0

1.766.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.767 hmac-drbg 1.0.1

1.767.1 Available under license :

MIT

1.768 pseudomap 1.0.2

1.768.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.769 html-loader 0.5.5

1.769.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the 'Software'), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION

WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.770 sha.js 2.4.11

1.770.1 Available under license :

UNRECOGNIZED LICENSE; MD5 sum: ed8374e1e452c82c294b3c00b67ea6d4
Copyright (c) 2013-2018 sha.js contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

Copyright (c) 1998 - 2009, Paul Johnston & Contributors
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

Redistributions in binary form must reproduce the above copyright notice, this
list of conditions and the following disclaimer in the documentation and/or
other materials provided with the distribution.

Neither the name of the author nor the names of its contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND

ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.771 stream-browserify 2.0.2

1.771.1 Available under license :

MIT
This software is released under the MIT license:

Copyright (c) James Halliday

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.772 upath 1.2.0

1.772.1 Available under license :

MIT
Copyright(c) 2014-2019 Angelos Pikoulas (agelos.pikoulas@gmail.com)

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without

restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

1.773 glob-parent 3.1.0

1.773.1 Available under license :

The ISC License

Copyright (c) 2015 Elan Shanker

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR
IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.774 vm-browserify 1.1.2

1.774.1 Available under license :

MIT
MIT License

Permission is hereby granted, free of charge, to any person obtaining a copy of

this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS
FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR
COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER
IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE
OR OTHER DEALINGS IN THE SOFTWARE.

1.775 browserify-zlib 0.2.0

1.775.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2015 Devon Govett <devongovett@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

This project contains parts of Node.js.
Node.js is licensed for use as follows:

"""

Copyright Node.js contributors. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
IN THE SOFTWARE.
"""

This license applies to parts of Node.js originating from the
https://github.com/joyent/node repository:

"""
Copyright Joyent, Inc. and other Node contributors. All rights reserved.
Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions
of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
IN THE SOFTWARE.
"""
MIT

1.776 block-stream 0.0.9

1.776.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR
IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
Copyright (c) Isaac Z. Schlueter
All rights reserved.

The BSD License

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:
1. Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE NETBSD FOUNDATION, INC. AND CONTRIBUTORS
``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE FOUNDATION OR CONTRIBUTORS
BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE
 GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

1.777 promise 7.3.1

1.777.1 Available under license :

Copyright (c) 2014 Forbes Lindesay

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.778 pinkie-promise 2.0.1

1.778.1 Available under license :

The MIT License (MIT)

Copyright (c) Vsevolod Strukchinsky <floatdrop@gmail.com> (github.com/floatdrop)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.779 num2fraction 1.2.2

1.779.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 PostCSS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.780 os-browserify 0.3.0

1.780.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2017 CoderPuppy

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is

furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.781 md5.js 1.3.5

1.781.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2016 Kirill Fomichev

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.782 rechoir 0.6.2

1.782.1 Available under license :

Copyright (c) 2015 Tyler Kellen

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.
MIT

1.783 global-prefix 1.0.2

1.783.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.784 relateurl 0.2.7

1.784.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) Steven Vachon <contact@svachon.com> (svachon.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.785 pinkie 2.0.4

1.785.1 Available under license :

The MIT License (MIT)

Copyright (c) Vsevolod Strukchinsky <floatdrop@gmail.com> (github.com/floatdrop)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.786 miller-rabin 4.0.1

1.786.1 Available under license :

MIT

1.787 randomfill 1.0.4

1.787.1 Available under license :

MIT License

Copyright (c) 2017 crypto-browserify

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.788 normalize-range 0.1.2

1.788.1 Available under license :

The MIT License (MIT)

Copyright (c) James Talmage <james@talmage.io> (github.com/jamestalmage)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.789 buffer 4.9.2

1.789.1 Available under license :

The MIT License (MIT)

Copyright (c) Feross Aboukhadijeh, and other contributors.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.790 builtin-status-codes 3.0.0

1.790.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) Ben Drucker <bvdrucker@gmail.com> (bendrucker.me)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.791 cipher-base 1.0.4

1.791.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017 crypto-browserify contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights

to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.792 array-slice 1.1.0

1.792.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.793 constants-browserify 1.0.0

1.793.1 Available under license :

MIT

1.794 loader-runner 2.4.0

1.794.1 Available under license :

The MIT License

Copyright (c) Tobias Koppers @sokra

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.795 browserify-aes 1.2.0

1.795.1 Available under license :

ISC
MIT
The MIT License (MIT)

Copyright (c) 2014-2017 browserify-aes contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell

copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.796 fastparse 1.1.2

1.796.1 Available under license :

Copyright 2018 Tobias Koppers

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.797 is-unc-path 1.0.0

1.797.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.798 path-browserify 0.0.1

1.798.1 Available under license :

This software is released under the MIT license:

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.799 evp_bytestokey 1.0.3

1.799.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017 crypto-browserify contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.800 path-dirname 1.0.2

1.800.1 Available under license :

MIT

The MIT License (MIT)

Copyright (c) Elan Shanker and Node.js contributors. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.801 node-gyp 3.8.0

1.801.1 Available under license :

(The MIT License)

Copyright (c) 2012 Nathan Rajlich <nathan@tootallnate.net>

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.
MIT
Copyright (c) 2009 Google Inc. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following disclaimer
in the documentation and/or other materials provided with the
distribution.

* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.802 fined 1.2.0

1.802.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2016, 2017, 2018 Blaine Bublitz <blaine.bublitz@gmail.com> and Eric Schoffstall <yo@contra.io>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.803 shallowequal 1.1.0

1.803.1 Available under license :

MIT
MIT License

Copyright (c) 2017 Alberto Leal <mailforalberto@gmail.com> (github.com/dashed)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.804 lower-case 1.1.4

1.804.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Blake Embrey (hello@blakeembrey.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.805 array-each 1.0.1

1.805.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015, 2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.806 querystring-es3 0.2.1

1.806.1 Available under license :

Copyright 2012 Irakli Gozalishvili. All rights reserved.
Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
IN THE SOFTWARE.
MIT

1.807 minimalistic-assert 1.0.1

1.807.1 Available under license :

Copyright 2015 Calvin Metcalf

Permission to use, copy, modify, and/or distribute this software for any purpose
with or without fee is hereby granted, provided that the above copyright notice
and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.808 global-modules 1.0.0

1.808.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.809 resolve-dir 1.0.1

1.809.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015-2016, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.810 object-defaults 1.1.0

1.810.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2015, 2017, Jon Schlinkert

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.811 to-arraybuffer 1.0.1

1.811.1 Available under license :

The MIT License

Copyright (c) 2016 John Hiesey

Permission is hereby granted, free of charge,
to any person obtaining a copy of this software and
associated documentation files (the "Software"), to
deal in the Software without restriction, including
without limitation the rights to use, copy, modify,
merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom
the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice
shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR
ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT

OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.812 ajv-errors 1.0.1

1.812.1 Available under license :

MIT License

Copyright (c) 2017 Evgeny Poberezkin

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.813 domain-browser 1.2.0

1.813.1 Available under license :

MIT
<!-- LICENSEFILE/ -->

<h1>License</h1>

Unless stated otherwise all works are:

Copyright © 2013+ Bevry Pty Ltd

and licensed under:

MIT License

<h2>MIT License</h2>

<pre>
Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
</pre>

<!-- /LICENSEFILE -->

1.814 create-hash 1.2.0

1.814.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017 crypto-browserify contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

MIT

1.815 stream-http 2.8.3

1.815.1 Available under license :

MIT
The MIT License

Copyright (c) 2015 John Hiesey

Permission is hereby granted, free of charge,
to any person obtaining a copy of this software and
associated documentation files (the "Software"), to
deal in the Software without restriction, including
without limitation the rights to use, copy, modify,
merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom
the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice
shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR
ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.816 node-libs-browser 2.2.1

1.816.1 Available under license :

(The MIT License)

Copyright (c) 2012 Tobias Koppers

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.817 is-absolute 1.0.0

1.817.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2017, Jon Schlinkert.
Copyright (c) 2009-2014, TJ Holowaychuk

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.818 flagged-respawn 1.0.1

1.818.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2018 Tyler Kellen <tyler@sleekcode.net>, Blaine Bublitz <blaine.bublitz@gmail.com>, and Eric Schoffstall <yo@contra.io>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.819 ast-types 0.9.6

1.819.1 Available under license :

Copyright (c) 2013 Ben Newman <bn@cs.stanford.edu>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,

TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.820 make-iterator 1.0.1

1.820.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2018, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.821 param-case 2.1.1

1.821.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Blake Embrey (hello@blakeembrey.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.822 expand-tilde 2.0.2

1.822.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015-2016, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.823 public-encrypt 4.0.3

1.823.1 Available under license :

MIT

1.824 import-lazy 2.1.0

1.824.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.825 upper-case 1.1.3

1.825.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Blake Embrey (hello@blakeembrey.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.826 unc-path-regex 0.1.2

1.826.1 Available under license :

MIT

1.827 es6-templates 0.2.3

1.827.1 Available under license :

Copyright 2014 Square Inc.

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
UNRECOGNIZED LICENSE; MD5 sum: ee7c37de2b9224d059f26dbd00d5bae6

1.828 brorand 1.1.0

1.828.1 Available under license :

MIT

1.829 boolbase 1.0.0

1.829.1 Available under license :

ISC

1.830 recast 0.11.23

1.830.1 Available under license :

Copyright (c) 2012 Ben Newman <bn@cs.stanford.edu>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
 WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.831 browserify-des 1.0.2

1.831.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2017 Calvin Metcalf, Fedor Indutny & contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.832 private 0.1.8

1.832.1 Available under license :

Copyright (c) 2014 Ben Newman <bn@cs.stanford.edu>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.833 async-limiter 1.0.1

1.833.1 Available under license :

MIT
The MIT License (MIT)
Copyright (c) 2017 Samuel Reed <samuel.trace.reed@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the

Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.834 minimalistic-crypto-utils 1.0.1

1.834.1 Available under license :

MIT

1.835 nopt 3.0.6

1.835.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.836 browserify-cipher 1.0.1

1.836.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2017 Calvin Metcalf & contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights

to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.837 path-root 0.1.1

1.837.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.838 no-case 2.3.2

1.838.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Blake Embrey (hello@blakeembrey.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.839 diffie-hellman 5.0.3

1.839.1 Available under license :

Copyright (c) 2017 Calvin Metcalf

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE

SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.840 yargs-parser 13.1.2

1.840.1 Available under license :

Copyright (c) 2016, Contributors

Permission to use, copy, modify, and/or distribute this software
for any purpose with or without fee is hereby granted, provided
that the above copyright notice and this permission notice
appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES
OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS,
WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION,
ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.841 camel-case 3.0.0

1.841.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Blake Embrey (hello@blakeembrey.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,

ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.842 memory-fs 0.4.1

1.842.1 Available under license :

MIT

1.843 parse-passwd 1.0.0

1.843.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2016 Brian Woodward

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.844 registry-url 5.1.0

1.844.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated

documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.845 xdg-basedir 4.0.0

1.845.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.846 widest-line 3.1.0

1.846.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.847 got 9.6.0

1.847.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.848 core-js 2.6.12

1.848.1 Available under license :

Copyright (c) 2014-2020 Denis Pushkarev

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.849 strict-uri-encode 2.0.0

1.849.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) Kevin Martensson <kevinmartensson@gmail.com> (github.com/kevva)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,

TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.850 sindresorhus-is 0.14.0

1.850.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.851 cli-boxes 2.2.1

1.851.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (https://sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A

PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.852 cacheable-request 6.1.0

1.852.1 Available under license :

MIT License

Copyright (c) 2017 Luke Childs

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.853 decompress-response 3.3.0

1.853.1 Available under license :

`The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.854 split-on-first 1.1.0

1.854.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.855 dot-prop 5.3.0

1.855.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.856 responselike 1.0.2

1.856.1 Available under license :

Copyright (c) 2017 Luke Childs

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.857 pako 1.0.11

1.857.1 Available under license :

UNRECOGNIZED LICENSE; MD5 sum: 313da501a381d9a74ba74a95100a44a4
(The MIT License)

Copyright (C) 2014-2017 by Vitaly Puzrin and Andrei Tuputcyn

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.858 szmarczak-http-timer 1.1.2

1.858.1 Available under license :

MIT
MIT License

Copyright (c) 2018 Szymon Marczak

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.859 defer-to-connect 1.1.3

1.859.1 Available under license :

MIT
MIT License

Copyright (c) 2018 Szymon Marczak

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.860 is-obj 2.0.0

1.860.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the

Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.861 unique-string 2.0.0

1.861.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.862 json-buffer 3.0.0

1.862.1 Available under license :

Copyright (c) 2013 Dominic Tarr

Permission is hereby granted, free of charge,
to any person obtaining a copy of this software and
associated documentation files (the "Software"), to
deal in the Software without restriction, including
without limitation the rights to use, copy, modify,
merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom

the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice
shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR
ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.863 p-cancelable 1.1.0

1.863.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.864 to-readable-stream 1.0.0

1.864.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.865 package-json 6.5.0

1.865.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.866 crypto-random-string 2.0.0

1.866.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.867 keyv 3.1.0

1.867.1 Available under license :

MIT License

Copyright (c) 2017 Luke Childs

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

MIT

1.868 prepend-http 2.0.0

1.868.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.869 configstore 5.0.1

1.869.1 Available under license :

BSD-2-Clause
BSD 2-Clause License

Copyright (c) Google
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"

AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.870 url-parse-lax 3.0.0

1.870.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.871 cacache 12.0.4

1.871.1 Available under license :

ISC License

Copyright (c) npm, Inc.

Permission to use, copy, modify, and/or distribute this software for
any purpose with or without fee is hereby granted, provided that the
above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE COPYRIGHT HOLDER DISCLAIMS
ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE
COPYRIGHT HOLDER BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR
CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS
OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE
USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.872 interpret 1.4.0

1.872.1 Available under license :

Copyright (c) 2014-2018 Tyler Kellen <tyler@sleekcode.net>, Blaine Bublitz <blaine.bublitz@gmail.com>, and Eric Schoffstall <yo@contra.io>

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER
IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.
MIT

1.873 chalk 3.0.0

1.873.1 Available under license :

MIT

1.874 timers-browserify 2.0.12

1.874.1 Available under license :

timers-browserify

This project uses the [MIT](http://jryans.mit-license.org/) license:

Copyright 2012 J. Ryan Stinnett <jryans@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the Software),
to deal in the Software without restriction, including without limitation
the rights to use, copy, modify, merge, publish, distribute, sublicense,
and/or sell copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED AS IS, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS
BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER
DEALINGS IN THE SOFTWARE.

lib/node

The `lib/node` directory borrows files from joyent/node which uses the following license:

Copyright Joyent, Inc. and other Node contributors. All rights reserved.
Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

MIT

1.875 webpack-log 2.0.0

1.875.1 Available under license :

MIT License

Copyright (c) 2017 webpack-contrib

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

MIT

1.876 asn1.js 5.4.1

1.876.1 Available under license :

MIT

MIT License

Copyright (c) 2017 Fedor Indutny

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.877 parse-asn1 5.1.6

1.877.1 Available under license :

Copyright (c) 2017, crypto-browserify contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.878 browserify-rsa 4.1.0

1.878.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2016 Calvin Metcalf & contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all

copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.879 hash-base 3.1.0

1.879.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2016 Kirill Fomichev

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.880 @emotion/unitless 0.7.5

1.880.1 Available under license :

MIT License

Copyright (c) Emotion team and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.881 watchpack 1.7.5

1.881.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.882 findup-sync 3.0.0

1.882.1 Available under license :

The MIT License (MIT)

Copyright (c) 2013-2018 Ben Alman <cowboy@rj3.net>, Blaine Bublitz <blaine.bublitz@gmail.com>, and Eric Schoffstall <yo@contra.io>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES
OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.883 serialize-javascript 4.0.0

1.883.1 Available under license :

Copyright 2014 Yahoo! Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

* Neither the name of the Yahoo! Inc. nor the
  names of its contributors may be used to endorse or promote products

derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO
EVENT SHALL YAHOO! INC. BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.884 value-equal 1.0.1

1.884.1 Available under license :

MIT
MIT License

Copyright (c) Michael Jackson 2016-2018

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.885 create-ecdh 4.0.4

1.885.1 Available under license :

MIT

1.886 babel-eslint 10.1.0

1.886.1 Available under license :

Copyright (c) 2014-2016 Sebastian McKenzie <sebmck@gmail.com>

MIT License

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.887 history 4.10.1

1.887.1 Available under license :

MIT License

Copyright (c) React Training 2016-2018

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all

copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.888 resolve-pathname 3.0.0

1.888.1 Available under license :

MIT
MIT License

Copyright (c) Michael Jackson 2016-2018

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.889 tiny-warning 1.0.3

1.889.1 Available under license :

MIT License

Copyright (c) 2019 Alexander Reardon

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.890 resolve-from 3.0.0

1.890.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.891 schema-utils 2.7.1

1.891.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
 WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.892 css-color-keywords 1.0.0

1.892.1 Available under license :

ISC
ISC License

Copyright (c) 2017, Jakob Krigovsky

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.893 @emotion/is-prop-valid 0.8.8

1.893.1 Available under license :

MIT License

Copyright (c) Emotion team and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.894 @emotion/stylis 0.8.5

1.894.1 Available under license :

MIT License

Copyright (c) Emotion team and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.895 @emotion/memoize 0.7.4

1.895.1 Available under license :

MIT License

Copyright (c) Emotion team and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.896 just-extend 4.2.1

1.896.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 angus croll

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights

to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.897 path-parse 1.0.7

1.897.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 Javier Blanco

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.898 balanced-match 1.0.2

1.898.1 Available under license :

(MIT)

Copyright (c) 2013 Julian Gruber <julian@juliangruber.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.899 is-fullwidth-code-point 3.0.0

1.899.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR

COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.900 sprintf-js 1.0.3

1.900.1 Available under license :

MIT License

Copyright (c) 2019 Johannes Tegnr / Jitesoft

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.901 ansi-regex 5.0.1

1.901.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the

Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.902 find-up 4.1.0

1.902.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.903 min-document 2.19.0

1.903.1 Available under license :

Copyright (c) 2013 Colingo.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.904 normalize-path 3.0.0

1.904.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2018, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.905 p-locate 4.1.0

1.905.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.906 es-to-primitive 1.2.1

1.906.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.907 xtend 4.0.2

1.907.1 Available under license :

MIT

1.908 ssri 6.0.2

1.908.1 Available under license :

ISC License

Copyright (c) npm, Inc.

Permission to use, copy, modify, and/or distribute this software for
any purpose with or without fee is hereby granted, provided that the
above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE COPYRIGHT HOLDER DISCLAIMS
ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE
COPYRIGHT HOLDER BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR
CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS
OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE
USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.909 path-exists 4.0.0

1.909.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR

COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.910 locate-path 5.0.0

1.910.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.911 mimic-response 1.0.1

1.911.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED,

INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.912 has-ansi 2.0.0

1.912.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (https://sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.913 object-keys 1.1.1

1.913.1 Available under license :

The MIT License (MIT)

Copyright (C) 2013 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in

all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.914 end-of-stream 1.4.4

1.914.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Mathias Buus

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.915 global 4.4.0

1.915.1 Available under license :

Copyright (c) 2012 Colingo.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal

in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.916 argparse 1.0.10

1.916.1 Available under license :

(The MIT License)

Copyright (C) 2012 by Vitaly Puzrin

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.917 string-width 4.2.3

1.917.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.918 which-boxed-primitive 1.0.2

1.918.1 Available under license :

MIT License

Copyright (c) 2019 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.919 get-symbol-description 1.0.0

1.919.1 Available under license :

MIT

1.920 is-date-object 1.0.5

1.920.1 Available under license :

MIT

1.921 is-string 1.0.7

1.921.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.922 wrap-ansi 2.1.0

1.922.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.923 has-tostringtag 1.0.0

1.923.1 Available under license :

MIT

1.924 is-regex 1.1.4

1.924.1 Available under license :

MIT

1.925 core-util-is 1.0.3

1.925.1 Available under license :

MIT
Copyright Node.js contributors. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
IN THE SOFTWARE.

1.926 is-symbol 1.0.4

1.926.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.927 for-each 0.3.3

1.927.1 Available under license :

The MIT License (MIT)

Copyright (c) 2012 Raynos.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.928 get-caller-file 1.0.3

1.928.1 Available under license :

ISC
ISC License (ISC)
Copyright 2018 Stefan Penner

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.929 is-boolean-object 1.1.2

1.929.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.930 is-bigint 1.0.4

1.930.1 Available under license :

MIT

1.931 tslib 1.14.1

1.931.1 Available under license :

Copyright (c) Microsoft Corporation.

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR

OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
/*! ***
Copyright (c) Microsoft Corporation.

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
*** */

1.932 require-main-filename 1.0.1

1.932.1 Available under license :

Copyright (c) 2016, Contributors

Permission to use, copy, modify, and/or distribute this software
for any purpose with or without fee is hereby granted, provided
that the above copyright notice and this permission notice
appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES
OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS,
WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION,
ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.933 term-size 2.2.1

1.933.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (https://sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the

rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.934 boxen 4.2.0

1.934.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.935 v8flags 3.2.0

1.935.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2018 Tyler Kellen <tyler@sleekcode.net>, Blaine Bublitz <blaine.bublitz@gmail.com>, and Eric Schoffstall <yo@contra.io>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.936 liftoff 3.1.0

1.936.1 Available under license :

MIT
Copyright (c) 2014 Tyler Kellen

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

1.937 lazystream 1.0.1

1.937.1 Available under license :

MIT
Copyright (c) 2013 J. Pommerening, contributors.

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

1.938 is-negative-zero 2.0.2

1.938.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.939 is-weakref 1.0.2

1.939.1 Available under license :

MIT License

Copyright (c) 2020 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.940 snake-yaml 1.21

1.940.1 Available under license :

Found license 'Eclipse Public License 1.0' in '// This module is multi-licensed and may be used under the terms // EPL, Eclipse Public License, V1.0 or later, http://www.eclipse.org/legal // LGPL, GNU Lesser General Public License, V2.1 or later, http://www.gnu.org/licenses/lgpl.html // GPL, GNU General Public License, V2 or later, http://www.gnu.org/licenses/gpl.html // AL, Apache License, V2.0 or later, http://www.apache.org/licenses // BSD, BSD License, http://www.opensource.org/licenses/bsd-license.php * Multi-licensed: EPL / LGPL / GPL / AL / BSD.'

Found license 'GNU Lesser General Public License' in '// This module is multi-licensed and may be used under the terms // EPL, Eclipse Public License, V1.0 or later, http://www.eclipse.org/legal // LGPL, GNU Lesser General Public License, V2.1 or later, http://www.gnu.org/licenses/lgpl.html // GPL, GNU General Public License, V2 or later, http://www.gnu.org/licenses/gpl.html // AL, Apache License, V2.0 or later, http://www.apache.org/licenses // BSD, BSD License, http://www.opensource.org/licenses/bsd-license.php * Multi-licensed: EPL / LGPL / GPL / AL / BSD.'

1.941 log4j-api 2.17.1

1.941.1 Available under license :

Apache Log4j 1.x Compatibility API
Copyright 1999-1969 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable

(except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,

and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.942 apache-log4j 2.17.1

1.942.1 Available under license :

Apache Log4j Core
Copyright 1999-2012 Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

ResolverUtil.java
Copyright 2005-2006 Tim Fennell

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache license, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the license for the specific language governing permissions and
* limitations under the license.
*/

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical

transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made,

use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,

or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright 1999-2005 The Apache Software Foundation

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.943 log4j-slf4j-impl 2.17.1

1.943.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted"

means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each

Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");

you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache Log4j SLF4J Binding
Copyright 1999-1969 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

1.944 chokidar 3.5.3

1.944.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2012-2019 Paul Miller (https://paulmillr.com), Elan Shanker

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the Software), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED AS IS, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.945 transform-runtime 0.0.0

1.945.1 Available under license :

ISC

1.946 redux-logger 4.0.0

1.946.1 Available under license :

MIT
Copyright (c) 2016 Eugene Rodionov

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH
 THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.947 babel-plugin-transform-remove-strict-mode 0.0.2

1.947.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2016 genify

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is

furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.948 ramda 0.27.2

1.948.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2013-2018 Scott Sauyet and Michael Hurley

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.949 reflectasm:shaded shaded:1.07

1.949.1 Available under license :

No license file was found, but licenses were detected in source scan.

<name>New BSD License</name>

Found in path(s):
* /reflectasm-1-07-shaded-jar-zip/reflectasm-1-07-shaded-jar/META-INF/maven/com.esotericsoftware.reflectasm/reflectasm/pom.xml

1.950 springsource-org-quartz 1.6.0

1.950.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2004-2006 OpenSymphony
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not
* use this file except in compliance with the License. You may obtain a copy
* of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*
*/
```

Found in path(s):
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/DBSemaphore.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/JTANonClusteredSemaphore.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/RemoteMBeanScheduler.java

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2004-2006 OpenSymphony
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not
* use this file except in compliance with the License. You may obtain a copy
* of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
```

* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/listeners/FilterAndBroadcastTriggerListener.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/listeners/FilterAndBroadcastJobListener.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/listeners/JobChainingJobListener.java
*
/com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/UpdateLockRowSemaphore.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2004-2005 OpenSymphony
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not
* use this file except in compliance with the License. You may obtain a copy
* of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*
*/

Found in path(s):
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/ee/servlet/QuartzInitializerListener.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/ee/servlet/QuartzInitializerServlet.java
No license file was found, but licenses were detected in source scan.

All rights reserved.

Found in path(s):
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/xml/job_scheduling_data_1_5.xsd
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2004-2006 OpenSymphony
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not
* use this file except in compliance with the License. You may obtain a copy
* of the License at

*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/listeners/TriggerListenerSupport.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/listeners/SchedulerListenerSupport.java
* /com-springsource-org-quartz-1-6-0-sources-
jar/org/quartz/plugins/SchedulerPluginWithUserTransactionSupport.java
*
 /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/TablePrefixAware.java
* /com-springsource-org-quartz-1-6-0-sources-
jar/org/quartz/impl/jdbcjobstore/AttributeRestoringConnectionInvocationHandler.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/listeners/JobListenerSupport.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/utils/StringKeyDirtyFlagMap.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/utils/ExceptionHelper.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2004-2005 OpenSymphony
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not
* use this file except in compliance with the License. You may obtain a copy
* of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*
*/

Found in path(s):
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/SchedulerFactory.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/simpl/SimpleInstanceIdGenerator.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/SchedulerConfigException.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/LockException.java
*

/com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/SchedulerMetaData.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/utils/DirtyFlagMap.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/jobs/ee/jms/SendTopicMessageJob.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/ee/jta/UserTransactionHelper.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/helpers/VersionPrinter.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/JobPersistenceException.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/utils/Pair.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/spi/SchedulerPlugin.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/TriggerUtils.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/core/SchedulerSignalerImpl.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/SimpleTrigger.java
*
/com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/spi/JobFactory.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/calendar/WeeklyCalendar.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/StatefulJob.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/simpl/ThreadContextClassLoadHelper.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/simpl/LoadingLoaderClassLoadHelper.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/simpl/InitThreadContextClassLoadHelper.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/InvalidConfigurationException.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/CloudscapeDelegate.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/helpers/TriggerUtils.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/core/QuartzSchedulerResources.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/PointbaseDelegate.java
*
/com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/Calendar.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/CriticalSchedulerException.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/SchedulerRepository.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/calendar/BaseCalendar.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/JobExecutionException.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/utils/PropertiesParser.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/TriggerListener.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/DriverDelegate.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/SchedulerException.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/MSSQLDelegate.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/jobs/ee/jms/JmsHelper.java
*
/com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/jobs/NoOpJob.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/SchedulerContext.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/utils/ConnectionProvider.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/utils/TriggerStatus.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/jobs/ee/jms/SendDesitnationMessageJob.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/jobs/ee/jms/JmsMessageFactory.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/DB2v7Delegate.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/jobs/ee/jms/SendQueueMessageJob.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/StdJobRunShellFactory.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/plugins/history/LoggingJobHistoryPlugin.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/NthIncludedDayTrigger.java
*

/com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/NoSuchDelegateException.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/jobs/ee/ejb/EJBInvokerJob.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/DB2v6Delegate.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/spi/ClassLoadHelper.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/calendar/HolidayCalendar.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/InterruptableJob.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/spi/TriggerFiredBundle.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/utils/DBConnectionManager.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/simpl/HostnameInstanceIdGenerator.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/core/RemotableQuartzScheduler.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/StdJDBCDelegate.java
*
/com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/plugins/xml/JobInitializationPluginMultiple.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/simpl/PropertySettingJobFactory.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/spi/JobStore.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/core/SchedulingContext.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/utils/Key.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/QuartzServer.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/jobs/FileScanJob.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/core/JobRunShellFactory.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/plugins/history/LoggingTriggerHistoryPlugin.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/StdSchedulerFactory.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/StdJDBCConstants.java
*
/com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/SimpleSemaphore.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/JobDataMap.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/Constants.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/spi/TimeBroker.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/utils/JNDIConnectionProvider.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/StdScheduler.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/JobDetail.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/xml/JobSchedulingBundle.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/plugins/xml/JobInitializationPlugin.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/SchedulerListener.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/core/QuartzScheduler.java
*
/com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/JobExecutionContext.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/xml/ValidationException.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/ee/jta/JTAJobRunShell.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/core/JobRunShell.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/JobStoreSupport.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/spi/SchedulerSignaler.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/Scheduler.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/simpl/SimpleTimeBroker.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/Trigger.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/calendar/AnnualCalendar.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/RemoteScheduler.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/HSQLDBDelegate.java

*
/com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/UnableToInterruptJobException.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/simpl/CascadingClassLoadHelper.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/jobs/ee/mail/SendMailJob.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/plugins/management/ShutdownHookPlugin.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/jobs/NativeJob.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/SchedulerStateRecord.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/calendar/MonthlyCalendar.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/simpl/SimpleJobFactory.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/simpl/SimpleClassLoadHelper.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/JobStoreCMT.java
*
/com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/ee/jta/JTAJobRunShellFactory.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/spi/ThreadPool.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/FiredTriggerRecord.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/Util.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/utils/PoolingConnectionProvider.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/DB2v8Delegate.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/simpl/RAMJobStore.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/Semaphore.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/xml/JobSchedulingDataProcessor.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/PostgreSQLDelegate.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/core/QuartzSchedulerThread.java
*
/com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/DirectSchedulerFactory.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/StdRowLockSemaphore.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/jobs/FileScanListener.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/ObjectAlreadyExistsException.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/Job.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/impl/jdbcjobstore/JobStoreTX.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/simpl/SimpleThreadPool.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/CronTrigger.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/jobs/ee/jms/JmsJobException.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/jobs/ee/jmx/JMXInvokerJob.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/spi/InstanceIdGenerator.java
*
/com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/JobListener.java
* /com-springsource-org-quartz-1-6-0-sources-jar/org/quartz/xml/CalendarBundle.java

1.951 springframework-core 3.1.3.RELEASE

1.951.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2007 the original author or authors.
*

* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/ContextResource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/XmlValidationModeDetector.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/StringValueResolver.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/PatternMatchUtils.java
*
 /spring-core-3-1-3-release-sources-jar/org/springframework/core/type/filter/AbstractClassTestingTypeFilter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/style/ValueStyler.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/style/StylerUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/FileSystemResourceLoader.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/support/EncodedResource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/ResourceLoader.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/type/filter/AspectJTypeFilter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/type/filter/TypeFilter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/support/ResourcePatternResolver.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/task/TaskTimeoutException.java
*
 /spring-core-3-1-3-release-sources-jar/org/springframework/core/type/filter/RegexPatternTypeFilter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/SmartClassLoader.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/type/classreading/MetadataReaderFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
*/

Found in path(s):
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/type/filter/AssignableTypeFilter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2005 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/PropertiesPersister.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/ControlFlow.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/ErrorCoded.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not
* use this file except in compliance with the License. You may obtain a copy of
* the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/Assert.java

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):

```
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/ConcurrencyThrottleSupport.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/NamedInheritableThreadLocal.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/InfrastructureProxy.java
*
 /spring-core-3-1-3-release-sources-jar/org/springframework/core/AliasRegistry.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/FileCopyUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/SimpleTransformErrorListener.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/ControlFlowFactory.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/AutoPopulatingList.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/style/DefaultToStringStyler.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/DecoratingClassLoader.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/task/TaskExecutor.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/Log4jConfigurer.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/CommonsLogWriter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/DefaultPropertiesPersister.java
*
 /spring-core-3-1-3-release-sources-jar/org/springframework/core/PrioritizedParameterNameDiscoverer.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/comparator/ComparableComparator.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/DescriptiveResource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/task/TaskRejectedException.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/NestedExceptionUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/DomUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/style/ToStringCreator.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/comparator/BooleanComparator.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/style/ToStringStyler.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/comparator/CompoundComparator.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/TransformerUtils.java
*
```

/spring-core-3-1-3-release-sources-jar/org/springframework/core/style/DefaultValueStyler.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/NamedThreadLocal.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/converter/GenericConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/AbstractPropertyResolver.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/CollectionToCollectionConverter.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/AbstractDescriptor.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/ConversionUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/ConfigurableObjectInputStream.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/support/ResourceArrayPropertyEditor.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/ResourceEditor.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/PropertySources.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/CollectionToArrayConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/SimpleCommandLinePropertySource.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/ConfigurableConversionService.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/GenericConversionService.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/core/AttributeAccessorSupport.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/CollectionUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/StringUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/MapPropertySource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/support/ResourcePropertySource.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/ArrayToCollectionConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/EnumerablePropertySource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/AbstractFileResolvingResource.java

* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/ByteArrayResource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/ArrayToArrayConverter.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/ObjectToArrayConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/ParameterDescriptor.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/ArrayToObjectConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/GenericCollectionTypeResolver.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/FieldDescriptor.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/CommandLineArgs.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/ConversionService.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/MethodParameter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/GenericTypeResolver.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/ObjectToCollectionConverter.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/BeanPropertyDescriptor.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/SystemEnvironmentPropertySource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/PropertySource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/ConfigurablePropertyResolver.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/ClassDescriptor.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/PropertyResolver.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/ExceptionDepthComparator.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/WritableResource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/SimpleCommandLineArgsParser.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/BridgeMethodResolver.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/util/ReflectionUtils.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/ConvertingPropertyEditorAdapter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/StandardEnvironment.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/type/filter/AbstractTypeHierarchyTraversingFilter.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/CollectionToStringConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/ObjectUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/PropertiesPropertySource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/JOptCommandLinePropertySource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/ErrorHandler.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/DefaultConversionService.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/core/env/Environment.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/CommandLinePropertySource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/ReadOnlySystemAttributesMap.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/StringToBooleanConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/XMLEventStreamReader.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/MissingRequiredPropertiesException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2006 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/SpringVersion.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/support/LocalizedResourceHelper.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/annotation/AnnotationAwareOrderComparator.java
*
 /spring-core-3-1-3-release-sources-jar/org/springframework/core/ConstantException.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/InputStreamResource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/ParameterNameDiscoverer.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/SimpleSaxErrorHandler.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/AttributeAccessor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/serializer/DefaultSerializer.java
* /spring-core-3-1-3-release-sources-

jar/org/springframework/core/convert/support/StringToCollectionConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/serializer/support/SerializingConverter.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/core/SimpleAliasRegistry.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/StaxStreamXMLReader.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/type/classreading/CachingMetadataReaderFactory.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/serializer/DefaultDeserializer.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/serializer/Deserializer.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/StaxUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/ConversionException.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/ConversionServiceFactory.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/AbstractStaxContentHandler.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/serializer/Serializer.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/util/SerializationUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/TypeUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/serializer/support/DeserializingConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/StaxStreamContentHandler.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/StringToArrayConverter.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/LocalVariableTableParameterNameDiscoverer.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/EnvironmentCapable.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/PathMatcher.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/ObjectToObjectConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/StopWatch.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/util/LinkedMultiValueMap.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/SystemPropertyUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/FileSystemUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/ConversionFailedException.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/support/VfsPatternUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/AbstractStaxXMLReader.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/StaxEventXMLReader.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/WeakReferenceMonitor.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/SimpleNamespaceContext.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/XMLEventStreamWriter.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/serializer/support/SerializationFailedException.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/ConverterNotFoundException.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/support/ResourcePatternUtils.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2005 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/comparator/InvertibleComparator.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/comparator/NullSafeComparator.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/task/SyncTaskExecutor.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/enums/LabeledEnumResolver.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/Conventions.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/StringToLocaleConverter.java
*
 /spring-core-3-1-3-release-sources-jar/org/springframework/util/NumberUtils.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/NumberToCharacterConverter.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/StringToEnumConverterFactory.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/PriorityOrdered.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/type/filter/AnnotationTypeFilter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/enums/AbstractGenericLabeledEnum.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/ObjectToStringConverter.java

* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/StringToCharacterConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/task/support/TaskExecutorAdapter.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/StaxSource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/enums/ShortCodedLabeledEnum.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/type/classreading/SimpleMetadataReaderFactory.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/enums/LabeledEnum.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/StringToNumberConverterFactory.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/ArrayToStringConverter.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/type/classreading/ClassMetadataReadingVisitor.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/type/ClassMetadata.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/CharacterToNumberFactory.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/enums/AbstractCachingLabeledEnumResolver.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/converter/ConverterRegistry.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/Ordered.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/NestedIOException.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/task/AsyncTaskExecutor.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/AbstractXMLStreamReader.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/StringToPropertiesConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/converter/ConverterFactory.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/type/StandardClassMetadata.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/enums/LetterCodedLabeledEnum.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/enums/StaticLabeledEnumResolver.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/core/annotation/Order.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/PropertiesToStringConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/StaxResult.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/ClassRelativeResourceLoader.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/type/MethodMetadata.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/MultiValueMap.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/enums/StaticLabeledEnum.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/task/SimpleAsyncTaskExecutor.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/NestedCheckedException.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/CustomizableThreadCreator.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/core/io/DefaultResourceLoader.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/ConcurrentMap.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/IdToEntityConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/task/support/ConcurrentExecutorAdapter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/type/classreading/MetadataReader.java

* /spring-core-3-1-3-release-sources-jar/org/springframework/core/JdkVersion.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/type/AnnotationMetadata.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/converter/ConditionalGenericConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/DigestUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/OverridingClassLoader.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/AbstractXMLReader.java
*
/spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/NumberToNumberConverterFactory.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/enums/AbstractLabeledEnum.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/MethodInvoker.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/CollectionToObjectConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/CachingMapDecorator.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/DomContentHandler.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/converter/Converter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/task/support/ExecutorServiceAdapter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/EnumToStringConverter.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/core/enums/StringCodedLabeledEnum.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/NestedRuntimeException.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/convert/support/FallbackObjectToStringConverter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2004-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/CompositeIterator.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.

*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/ClassUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/MutablePropertySources.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/AntPathMatcher.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/LinkedCaseInsensitiveMap.java
*
 /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/UrlResource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/ConfigurableEnvironment.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/type/classreading/AnnotationAttributesReadingVisitor.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/support/PropertiesLoaderSupport.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/VfsUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/OrderComparator.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/type/classreading/MethodMetadataReadingVisitor.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/type/classreading/SimpleMetadataReader.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/annotation/AnnotationAttributes.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/annotation/AnnotationUtils.java
*
 /spring-core-3-1-3-release-sources-jar/org/springframework/util/ResourceUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/support/MapToMapConverter.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/Resource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/type/StandardMethodMetadata.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/AntPathStringMatcher.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/Property.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/type/StandardAnnotationMetadata.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/CollectionFactory.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/support/PropertiesLoaderUtils.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/xml/StaxEventContentHandler.java
*
 /spring-core-3-1-3-release-sources-jar/org/springframework/core/Constants.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/convert/TypeDescriptor.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/type/classreading/AnnotationMetadataReadingVisitor.java

* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/PropertySourcesPropertyResolver.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/ClassPathResource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/AbstractResource.java
* /spring-core-3-1-3-release-sources-
jar/org/springframework/core/io/support/PathMatchingResourcePatternResolver.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/CompositePropertySource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/FileSystemResource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/util/PropertyPlaceholderHelper.java
*
/spring-core-3-1-3-release-sources-jar/org/springframework/core/io/VfsResource.java
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/env/AbstractEnvironment.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-core-3-1-3-release-sources-jar/org/springframework/core/io/InputStreamSource.java

1.952 springframework-asm 3.1.3.RELEASE

1.952.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by

the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but

excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the

appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Ivy
Copyright 2007-2009 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Portions of Ivy were originally developed by
Jayasoft SARL (http://www.jayasoft.fr/)
and are licensed to the Apache Software Foundation under the
"Software Grant License Agreement"

SSH and SFTP support is provided by the JCraft JSch package,
which is open source software, available under
the terms of a BSD style license.
The original software and related information is available
at http://www.jcraft.com/jsch/.
Apache Jakarta HttpClient
Copyright 1999-2007 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).
// --
// NOTICE file corresponding to the section 4d of The Apache License,
// Version 2.0, in this case for Commons Logging
// --

Commons Logging
Copyright 2001-2007 The Apache Software Foundation

This product includes/uses software(s) developed by 'an unknown organization'
- Unnamed - avalon-framework:avalon-framework:jar:4.1.3
- Unnamed - log4j:log4j:jar:1.2.12
- Unnamed - logkit:logkit:jar:1.0.1
This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).
Spring Framework 3.1
Copyright (c) 2002-2011 SpringSource, a division of VMware, Inc.

This product is licensed to you under the Apache License, Version 2.0 (the "License").
You may not use this product except in compliance with the License.

This product may include a number of subcomponents with separate copyright notices and
license terms. Your use of the source code for the these subcomponents is subject to

the terms and conditions of the subcomponent's license, as noted in the LICENSE file.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or
(iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from)
the Work and for which the
editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain

separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication
on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant
of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as
of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the

Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed

with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names
of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law
(such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your
sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following

boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution

notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor

has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

==========

SPRING FRAMEWORK 3.2.0.BUILD-SNAPSHOT SUBCOMPONENTS:

Spring Framework 3.2.0.BUILD-SNAPSHOT includes a number of subcomponents
with separate copyright notices and license terms. The product that
includes this file does not necessarily use all the open source
subcomponents referred to below. Your use of the source

code for these subcomponents is subject to the terms and
conditions of the following licenses.

>>> ASM 4.0 (org.ow2.asm:asm:4.0, org.ow2.asm:asm-commons:4.0):

Copyright (c) 2000-2011 INRIA, France Telecom
All rights reserved.

Redistribution and use in
source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

3. Neither the name of the copyright holders nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
THE POSSIBILITY OF SUCH DAMAGE.

Copyright (c) 1999-2009, OW2 Consortium <http://www.ow2.org/>

>>> CGLIB 3.0 (cglib:cglib:3.0):

Per the LICENSE file in the CGLIB JAR distribution downloaded from
http://sourceforge.net/projects/cglib/files/cglib3/3.0/cglib-3.0.jar/download,
CGLIB 3.0 is licensed under the Apache License, version 2.0, the text of which
is included above.

==========

To the extent any open source subcomponents are licensed under the EPL and/or other similar licenses that require the source code and/or modifications to source code
to be made available (as would be noted above), you may obtain a copy of the source code corresponding to the binaries for such open source components and modifications thereto, if any, (the "Source Files"), by downloading the Source Files from http://www.springsource.org/download, or by sending a request, with your name and address to:

VMware, Inc., 3401 Hillview Avenue
Palo Alto, CA 94304
United States of America

or email info@vmware.com. All such requests should clearly specify:

OPEN SOURCE FILES REQUEST
Attention General Counsel

VMware shall mail a copy of the Source Files to you on a CD or equivalent physical medium. This offer to obtain a copy of the Source Files is valid for three years from the date you acquired this Software product.
Spring Framework 3.2.0.BUILD-SNAPSHOT
Copyright (c) 2002-2012 SpringSource, a division of VMware, Inc.

This product is licensed to you under the Apache License, Version 2.0 (the "License"). You may not use this product except in compliance with the License.

This product may include a number of subcomponents with separate copyright notices and license terms. Your use of the source code for these subcomponents is subject to the terms and conditions of the subcomponent's license, as noted in the license.txt file.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by

the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but

excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the

appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial

revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.

Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

==========

SPRING FRAMEWORK 3.1 SUBCOMPONENTS:

Spring Framework 3.1 includes a number of subcomponents with
separate copyright notices and license terms. The product that
includes this file does not necessarily use all the open source
subcomponents referred to below. Your use of the source
code for these subcomponents is subject to the terms and
conditions of the following licenses.

>>> asm-2.2.3:

Copyright (c) 2000-2005 INRIA, France Telecom
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided
that the following conditions
are met:

1. Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright

notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

3. Neither the name of the copyright holders nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED
TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
THE POSSIBILITY OF SUCH DAMAGE.

Copyright (c) 1999-2009, OW2 Consortium <http://www.ow2.org/>

==========

To the extent any open source subcomponents are licensed under the EPL and/or other similar licenses that require the source code and/or modifications to source code to be made available (as would be noted above), you may obtain a copy of the source code corresponding to the binaries for such open source components and modifications thereto, if any, (the "Source Files"), by downloading the Source Files from http://www.springsource.org/download, or by sending a request, with your name and address to: VMware,
Inc., 3401 Hillview
Avenue, Palo Alto, CA 94304, United States of America or email info@vmware.com. All such requests should clearly specify: OPEN SOURCE FILES REQUEST, Attention General Counsel. VMware shall mail a copy of the Source Files to you on a CD or equivalent physical medium. This offer to obtain a copy of the Source Files is valid for three years from the date you acquired this Software product.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii)
beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the
Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication

on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant
of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as
of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and

attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained
within such NOTICE file, excluding those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own
copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names
of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or

implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed

under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

License for JCraft JSch package

Copyright (c) 2002,2003,2004,2005,2006,2007 Atsuhiko Yamanaka, JCraft,Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in
the documentation and/or other materials provided with the distribution.

3. The names of the authors may not be used to endorse or promote products
derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED ``AS IS'' AND ANY EXPRESSED OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND
FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL JCRAFT,
INC. OR ANY CONTRIBUTORS TO THIS SOFTWARE BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA,
OR PROFITS;
OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE,
EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

License for jQuery

Copyright (c) 2007 John Resig, http://jquery.com/

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall
be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution

notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor

has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

1.953 springframework-jdbc 3.1.3.RELEASE

1.953.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/object/GenericStoredProcedure.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/object/GenericSqlQuery.java

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2006 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
```

*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/support/SqlLobValue.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/lookup/DataSourceLookup.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/SqlReturnResultSet.java
*
 /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/support/JdbcBeanDefinitionReader.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/JdbcUpdateAffectedIncorrectNumberOfRowsException.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/MetaDataAccessException.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/lob/JtaLobCreatorSynchronization.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/core/namedparam/NamedParameterJdbcDaoSupport.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/SQLWarningException.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/datasource/lookup/SingleDataSourceLookup.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/lob/SpringLobCreatorSynchronization.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/lob/LobCreatorUtils.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/datasource/lookup/DataSourceLookupFailureException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/embedded/EmbeddedDatabaseType.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/embedded/HsqlEmbeddedDatabaseConfigurer.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/simple/SimpleJdbcOperations.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/JdbcTransactionObjectSupport.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/xml/Jdbc4SqlXmlHandler.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/embedded/EmbeddedDatabaseConfigurerFactory.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/embedded/EmbeddedDatabaseBuilder.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/ColumnMapRowMapper.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/simple/ParameterizedBeanPropertyRowMapper.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/embedded/OutputStreamFactory.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/BeanPropertyRowMapper.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/namedparam/NamedParameterJdbcOperations.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/lookup/JndiDataSourceLookup.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/namedparam/SqlParameterSource.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/SimpleDriverDataSource.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/embedded/DataSourceFactory.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/embedded/EmbeddedDatabase.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/embedded/EmbeddedDatabaseConfigurer.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/embedded/AbstractEmbeddedDatabaseConfigurer.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/SingleColumnRowMapper.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/embedded/SimpleDriverDataSourceFactory.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/config/JdbcNamespaceHandler.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/embedded/ConnectionProperties.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/init/DatabasePopulator.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/simple/SimpleJdbcTemplate.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/embedded/H2EmbeddedDatabaseConfigurer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not
* use this file except in compliance with the License. You may obtain a copy of
* the License at

*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/object/BatchSqlUpdate.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2005 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/lob/AbstractLobHandler.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/ConnectionHandle.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/ParameterDisposer.java
*
 /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/LobRetrievalFailureException.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/rowset/ResultSetWrappingSqlRowSetMetaData.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/rowset/SqlRowSetMetaData.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/core/support/AbstractLobStreamingResultSetExtractor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.

* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/simple/AbstractJdbcCall.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/core/metadata/GenericCallMetaDataProvider.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/config/EmbeddedDatabaseBeanDefinitionParser.java
*
 /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/core/metadata/PostgresTableMetaDataProvider.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/core/namedparam/NamedParameterBatchUpdateUtils.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/datasource/init/CompositeDatabasePopulator.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/core/metadata/OracleTableMetaDataProvider.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/config/DatabasePopulatorConfigUtils.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/datasource/embedded/EmbeddedDatabaseFactoryBean.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/core/namedparam/NamedParameterJdbcTemplate.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/metadata/CallMetaDataContext.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/incrementer/SybaseAnywhereMaxValueIncrementer.java
*
 /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/ParameterizedPreparedStatementSetter.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/core/metadata/PostgresCallMetaDataProvider.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/init/DataSourceInitializer.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/WebSphereDataSourceAdapter.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/SqlRowSetResultSetExtractor.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/incrementer/SybaseMaxValueIncrementer.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/config/InitializeDatabaseBeanDefinitionParser.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/datasource/embedded/EmbeddedDatabaseFactory.java

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* {@link LobHandler} implementation for Oracle databases. Uses proprietary API
* to create <code>oracle.sql.BLOB</code> and <code>oracle.sql.CLOB</code>
* instances, as necessary when working with Oracle's JDBC driver.
* Note that this LobHandler requires Oracle JDBC driver 9i or higher!
*
* <p>While
 most databases are able to work with {@link DefaultLobHandler},
* Oracle just accepts Blob/Clob instances created via its own proprietary
* BLOB/CLOB API, and additionally doesn't accept large streams for
* PreparedStatement's corresponding setter methods. Therefore, you need
* to use a strategy like this LobHandler implementation.
*
* <p>Needs to work on a native JDBC Connection, to be able to cast it to
* <code>oracle.jdbc.OracleConnection</code>. If you pass in Connections from a
* connection pool (the usual case in a J2EE environment), you need to set an
* appropriate {@link org.springframework.jdbc.support.nativejdbc.NativeJdbcExtractor}
* to allow for automatical retrieval of the underlying native JDBC Connection.
* LobHandler and NativeJdbcExtractor are separate concerns, therefore they
* are represented by separate strategy interfaces.
*
* <p>Coded via reflection to avoid dependencies on Oracle classes.
* Even reads in Oracle constants via reflection because of
 different Oracle
* drivers (classes12, ojdbc14, ojdbc5, ojdbc6) having different constant values!
* As this LobHandler initializes Oracle classes on instantiation, do not define
* this as eager-initializing singleton if you do not want to depend on the Oracle
* JAR being in the class path: use "lazy-init=true" to avoid this issue.
*
* @author Juergen Hoeller
* @author Thomas Risberg
```

* @since 04.12.2003
* @see #setNativeJdbcExtractor
* @see oracle.sql.BLOB
* @see oracle.sql.CLOB
*/

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/lob/OracleLobHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* Strategy interface for translating between {@link SQLException SQLExceptions}
* and Spring's data access strategy-agnostic {@link DataAccessException}
* hierarchy.
*
* <p>Implementations can be generic (for example, using
* {@link java.sql.SQLException#getSQLState() SQLState} codes for JDBC) or wholly
 * proprietary (for example, using Oracle error codes) for greater precision.
*
* @author Rod Johnson
* @author Juergen Hoeller
* @see org.springframework.dao.DataAccessException
*/

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/SQLExceptionTranslator.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2005 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.

```
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/PreparedStatementCreator.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/SqlProvider.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/CallableStatementCreator.java
*
/spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/DatabaseMetaDataCallback.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
  * Close this LobCreator session and free its temporarily created BLOBs and CLOBs.
  * Will not need to do anything if using PreparedStatement's standard methods,
  * but might be necessary to free database resources if using proprietary means.
  * <p><b>NOTE</b>: Needs to be invoked after the involved
 PreparedStatements have
  * been executed or the affected O/R mapping sessions have been flushed.
  * Otherwise, the database resources for the temporary BLOBs might stay allocated.
  */
```

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/lob/LobCreator.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):

* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/lob/PassThroughBlob.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/embedded/DerbyEmbeddedDatabaseConfigurer.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/DataSourceTransactionManager.java
*
/spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/rowset/SqlRowSet.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/lookup/IsolationLevelDataSourceRouter.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/rowset/ResultSetWrappingSqlRowSet.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/nativejdbc/OracleJdbc4NativeJdbcExtractor.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/JdbcOperations.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/simple/AbstractJdbcInsert.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/lob/PassThroughClob.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/JdbcTemplate.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/metadata/TableMetaDataContext.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/UserCredentialsDataSourceAdapter.java
*
/spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/lob/DefaultLobHandler.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/metadata/DerbyCallMetaDataProvider.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/SingleConnectionDataSource.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/TransactionAwareDataSourceProxy.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/simple/SimpleJdbcCallOperations.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/ConnectionHolder.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/metadata/TableMetaDataProviderFactory.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/LazyConnectionDataSourceProxy.java

* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/simple/SimpleJdbcCall.java
*
/spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/config/SortedResourcesFactoryBean.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/metadata/CallMetaDataProvider.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/nativejdbc/Jdbc4NativeJdbcExtractor.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/metadata/Db2CallMetaDataProvider.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/DataSourceUtils.java
No license file was found, but licenses were detected in source scan.

/**
*
* The classes in this package make JDBC easier to use and
* reduce the likelihood of common errors. In particular, they:
*
* Simplify error handling, avoiding the need for try/catch/final
* blocks in application code.
* Present exceptions to application code in a generic hierarchy of
* unchecked exceptions, enabling applications to catch data access
* exceptions without being dependent on JDBC, and to ignore fatal
* exceptions there is no value in catching.
* Allow the implementation of error handling to be modified
* to target different RDBMSes without introducing proprietary
* dependencies into application code.
*
*
* <p>This package and related packages are discussed in Chapter 9 of
* Expert One-On-One J2EE Design and
Development
* by Rod Johnson (Wrox, 2002).
*
*/

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/package-info.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* Implement this interface when parameters need to be customized based
* on the connection. We might need to do this to make use of proprietary
* features, available only with a specific Connection type.
*
* @author Rod Johnson
* @author Thomas Risberg
* @see CallableStatementCreatorFactory#newCallableStatementCreator(ParameterMapper)
 * @see org.springframework.jdbc.object.StoredProcedure#execute(ParameterMapper)
*/
/**
  * Create a Map of input parameters, keyed by name.
  * @param con JDBC connection. This is useful (and the purpose of this interface)
  * if we need to do something RDBMS-specific with a proprietary Connection
  * implementation class. This class conceals such proprietary details. However,
  * it is best to avoid using such proprietary RDBMS features if possible.
  * @throws SQLException if a SQLException is encountered setting
  * parameter values (that is, there's no need to catch SQLException)
  * @return Map of input parameters, keyed by name (never <code>null</code>)
  */

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/ParameterMapper.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/init/DatabasePopulatorUtils.java
* /spring-jdbc-3-1-3-release-sources-

zip/org/springframework/jdbc/support/CustomSQLExceptionTranslatorRegistry.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/core/metadata/GenericTableMetaDataProvider.java
*
/spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/SQLErrorCodesFactory.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/SQLErrorCodes.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/nativejdbc/JBossNativeJdbcExtractor.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/PreparedStatementCreatorFactory.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/datasource/init/ScriptStatementFailedException.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/StatementCreatorUtils.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/datasource/lookup/AbstractRoutingDataSource.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/DelegatingDataSource.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/namedparam/NamedParameterUtils.java
*
/spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/AbstractDataSource.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/CustomSQLExceptionTranslatorRegistrar.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/init/CannotReadScriptException.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/init/ResourceDatabasePopulator.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2006 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/RowCountCallbackHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/AbstractDriverBasedDataSource.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/SQLExceptionSubclassTranslator.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/AbstractFallbackSQLExceptionTranslator.java
*
 /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/RowMapperResultSetExtractor.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/incrementer/HsqlSequenceMaxValueIncrementer.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/SqlValue.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/CannotGetJdbcConnectionException.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/core/support/AbstractLobCreatingPreparedStatementCallback.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/DatabaseStartupValidator.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/support/AbstractSqlTypeValue.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/nativejdbc/WebSphereNativeJdbcExtractor.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/core/namedparam/BeanPropertySqlParameterSource.java
*
 /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/SqlTypeValue.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/support/JdbcDaoSupport.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/ConnectionCallback.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/object/UpdatableSqlQuery.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/datasource/IsolationLevelDataSourceAdapter.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/simple/ParameterizedRowMapper.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/ConnectionProxy.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/xml/XmlBinaryStreamProvider.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/PreparedStatementCallback.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/simple/SimpleJdbcInsert.java
*
 /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/CallableStatementCallback.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/xml/SqlXmlFeatureNotImplementedException.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/xml/SqlXmlObjectMappingHandler.java

* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/xml/XmlResultProvider.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/StatementCallback.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/lookup/MapDataSourceLookup.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/object/SqlCall.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/object/StoredProcedure.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/incrementer/PostgreSQLSequenceMaxValueIncrementer.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/KeyHolder.java
*
/spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/namedparam/ParsedSql.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/incrementer/DB2SequenceMaxValueIncrementer.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/incrementer/MySQLMaxValueIncrementer.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/nativejdbc/WebLogicNativeJdbcExtractor.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/ResultSetExtractor.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/BadSqlGrammarException.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/IncorrectResultSetColumnCountException.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/incrementer/HsqlMaxValueIncrementer.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/incrementer/H2SequenceMaxValueIncrementer.java
*
/spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/incrementer/AbstractDataFieldMaxValueIncrementer.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/incrementer/DerbyMaxValueIncrementer.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/CustomSQLErrorCodesTranslation.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/nativejdbc/CommonsDbcpNativeJdbcExtractor.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/InvalidResultSetAccessException.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/object/SqlQuery.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/object/MappingSqlQueryWithParameters.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/CallableStatementCreatorFactory.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/object/MappingSqlQuery.java
*
/spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/object/RdbmsOperation.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/incrementer/AbstractSequenceMaxValueIncrementer.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/DriverManagerDataSource.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/core/simple/ParameterizedSingleColumnRowMapper.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/incrementer/AbstractColumnMaxValueIncrementer.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/DisposableSqlTypeValue.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/object/SqlUpdate.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/JdbcUtils.java

* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/xml/SqlXmlValue.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/xml/XmlCharacterStreamProvider.java
*
 /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/namedparam/MapSqlParameterSource.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/SQLErrorCodeSQLExceptionTranslator.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/SQLStateSQLExceptionTranslator.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/incrementer/DB2MainframeSequenceMaxValueIncrementer.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/BatchUpdateUtils.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/SqlParameter.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/object/SqlFunction.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/GeneratedKeyHolder.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/xml/SqlXmlHandler.java
*
 /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/nativejdbc/NativeJdbcExtractorAdapter.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/core/namedparam/AbstractSqlParameterSource.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/incrementer/OracleSequenceMaxValueIncrementer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* Abstraction for handling large binary fields and large text fields in
* specific databases, no matter if represented as simple types or Large OBjects.
* Its main purpose is to isolate Oracle's peculiar handling of LOBs in
* {@link OracleLobHandler}; most other databases should be able to work
* with
 the provided {@link DefaultLobHandler}.
*
* <p>Provides accessor methods for BLOBs and CLOBs, and acts as factory for
* LobCreator instances, to be used as sessions for creating BLOBs or CLOBs.

```
* LobCreators are typically instantiated for each statement execution or for
* each transaction; they are not thread-safe because they might track
* allocated database resources in order to free them after execution.
*
* <p>Most databases/drivers should be able to work with {@link DefaultLobHandler},
* which by default delegates to JDBC's direct accessor methods, avoiding the
* <code>java.sql.Blob</code> and <code>java.sql.Clob</code> API completely.
* {@link DefaultLobHandler} can also be configured to access LOBs using
* <code>PreparedStatement.setBlob/setClob</code> (e.g. for PostgreSQL), through
* setting the {@link DefaultLobHandler#setWrapAsLob "wrapAsLob"} property.
*
* <p>Unfortunately, Oracle 9i just accepts Blob/Clob instances created via its own
* proprietary BLOB/CLOB
 API, and additionally doesn't accept large streams for
* PreparedStatement's corresponding setter methods. Therefore, you need to use
* {@link OracleLobHandler} there, which uses Oracle's BLOB/CLOB API for both types
* of access. The Oracle 10g JDBC driver should basically work with
* {@link DefaultLobHandler} as well, with some limitations in terms of LOB sizes.
*
* <p>Of course, you need to declare different field types for each database.
* In Oracle, any binary content needs to go into a BLOB, and all character content
* beyond 4000 bytes needs to go into a CLOB. In MySQL, there is no notion of a
* CLOB type but rather a LONGTEXT type that behaves like a VARCHAR. For complete
* portability, use a LobHandler for fields that might typically require LOBs on
* some database because of the field size (take Oracle's numbers as a guideline).
*
* <p><b>Summarizing the recommended options (for actual LOB fields):</b>
* <ul>
* <li><b>JDBC 4.0 driver:</b> {@link DefaultLobHandler}
 with <code>streamAsLob=true</code>.
* <li><b>PostgreSQL:</b> {@link DefaultLobHandler} with <code>wrapAsLob=true</code>.
* <li><b>Oracle 9i/10g:</b> {@link OracleLobHandler} with a connection-pool-specific
* {@link OracleLobHandler#setNativeJdbcExtractor NativeJdbcExtractor}.
* <li>For all other database drivers (and for non-LOB fields that might potentially
* turn into LOBs on some databases): a plain {@link DefaultLobHandler}.
* </ul>
*
* @author Juergen Hoeller
* @since 23.12.2003
* @see DefaultLobHandler
* @see OracleLobHandler
* @see java.sql.ResultSet#getBlob
* @see java.sql.ResultSet#getClob
* @see java.sql.ResultSet#getBytes
* @see java.sql.ResultSet#getBinaryStream
* @see java.sql.ResultSet#getString
* @see java.sql.ResultSet#getAsciiStream
* @see java.sql.ResultSet#getCharacterStream
```

*/

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/lob/LobHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/SqlInOutParameter.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/SqlOutParameter.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/UncategorizedSQLException.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/metadata/CallParameterMetaData.java
*
 /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/SmartDataSource.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/RowCallbackHandler.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/ResultSetSupportingSqlParameter.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/metadata/HsqlTableMetaDataProvider.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/nativejdbc/C3P0NativeJdbcExtractor.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/object/SqlOperation.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/SqlParameterValue.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/core/support/AbstractInterruptibleBatchPreparedStatementSetter.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/nativejdbc/NativeJdbcExtractor.java
*
 /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/metadata/DerbyTableMetaDataProvider.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/simple/SimpleJdbcInsertOperations.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/support/nativejdbc/SimpleNativeJdbcExtractor.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/PreparedStatementSetter.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/ArgPreparedStatementSetter.java
* /spring-jdbc-3-1-3-release-sources-
zip/org/springframework/jdbc/core/metadata/SybaseCallMetaDataProvider.java

* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/metadata/TableMetaDataProvider.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/lookup/BeanFactoryDataSourceLookup.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/metadata/SqlServerCallMetaDataProvider.java
*
 /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/incrementer/DataFieldMaxValueIncrementer.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/simple/SimpleJdbcDaoSupport.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/SqlReturnType.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/metadata/OracleCallMetaDataProvider.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/support/JdbcAccessor.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/ArgTypePreparedStatementSetter.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/BatchPreparedStatementSetter.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/metadata/TableParameterMetaData.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/namedparam/SqlParameterSourceUtils.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/RowMapper.java
*
 /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/metadata/CallMetaDataProviderFactory.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/datasource/SimpleConnectionHandle.java
* /spring-jdbc-3-1-3-release-sources-zip/org/springframework/jdbc/core/InterruptibleBatchPreparedStatementSetter.java

1.954 spring-framework-beans 3.1.3.RELEASE

1.954.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):

* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/PluggableSchemaResolver.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/PropertiesEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/TimeZoneEditor.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/ListableBeanFactory.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/PropertyAccessException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/PropertyAccessor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/SingletonBeanRegistry.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/xml/AbstractBeanDefinitionParser.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/NoSuchBeanDefinitionException.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/support/AutowireCandidateResolver.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/annotation/QualifierAnnotationAutowireCandidateResolver.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/CustomEditorConfigurer.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/PropertyBatchUpdateException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/AbstractPropertyAccessor.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/config/AutowireCapableBeanFactory.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/ConfigurableBeanFactory.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/ParserContext.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/FileEditor.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/config/MethodInvokingFactoryBean.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/support/StaticListableBeanFactory.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/wiring/BeanConfigurerSupport.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/TypeMismatchException.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/NamespaceHandlerSupport.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/config/InstantiationAwareBeanPostProcessorAdapter.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/DelegatingEntityResolver.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/TypeConverter.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/xml/DefaultNamespaceHandlerResolver.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/support/BeanDefinitionReaderUtils.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/config/ServiceLocatorFactoryBean.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/ManagedMap.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/CustomScopeConfigurer.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/DocumentDefaultsDefinition.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/PropertyValues.java
* /spring-beans-3-1-3-release-sources-

jar/org/springframework/beans/factory/parsing/EmptyReaderEventListener.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/ConversionNotSupportedException.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/config/PropertyOverrideConfigurer.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/CustomCollectionEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/BeanDefinitionHolder.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/BeansDtdResolver.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/DocumentLoader.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/ManagedSet.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/annotation/Autowire.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/GenericTypeAwarePropertyDescriptor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/PropertyValue.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/ManagedList.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/ManagedArray.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/xml/SimplePropertyNamespaceHandler.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/AbstractBeanDefinition.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/BeanExpressionContext.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/config/FieldRetrievingFactoryBean.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/ConfigurablePropertyAccessor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/MutablePropertyValues.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/InstantiationStrategy.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/DeprecatedBeanWarner.java
*
/spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/config/PropertyResourceConfigurer.java

* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/BeanFactoryAware.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/BeanDefinitionRegistryPostProcessor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/AbstractBeanDefinitionReader.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/MethodOverrides.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/ConstructorArgumentValues.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/BeanDefinitionReader.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/support/PagedListHolder.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/ProviderCreatingFactoryBean.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/BeanIsAbstractException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/PropertiesFactoryBean.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/PropertyAccessorUtils.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/URIEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/InputSourceEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/FactoryBean.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/InputStreamEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/ClassEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/AbstractFactoryBean.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/SimpleAutowireCandidateResolver.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/AutowireUtils.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/ClassArrayEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/RootBeanDefinition.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/DisposableBeanAdapter.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/PropertyPathFactoryBean.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/CachedIntrospectionResults.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/ObjectFactoryCreatingFactoryBean.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/XmlBeanDefinitionReader.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/CharsetEditor.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/AbstractSingleBeanDefinitionParser.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/UUIDEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/SimpleTypeConverter.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/ConstructorResolver.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/BeanPostProcessor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/TypedStringValue.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/FactoryBeanRegistrySupport.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/BeanUtils.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/access/el/SimpleSpringBeanELResolver.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/PropertyMatches.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/annotation/CustomAutowireConfigurer.java
*
 /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/DestructionAwareBeanPostProcessor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/ConfigurableListableBeanFactory.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/access/SingletonBeanFactoryLocator.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/NotWritablePropertyException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/BeanCreationException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/ChildBeanDefinition.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/BeansException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/Problem.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/serviceloader/ServiceListFactoryBean.java
*
 /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/PropertiesBeanDefinitionReader.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/BeanDefinitionResource.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/BeanComponentDefinition.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/ParseState.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/CharacterEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/BeanExpressionResolver.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/BeanDefinitionRegistry.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/access/el/SpringBeanELResolver.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/ObjectFactory.java

* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/ListFactoryBean.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/ReplaceOverride.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/BeanExpressionException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/support/PropertyComparator.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/config/SmartInstantiationAwareBeanPostProcessor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/PropertyAccessorFactory.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/parsing/CompositeComponentDefinition.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/CustomMapEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/UnsatisfiedDependencyException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/SmartFactoryBean.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/MapFactoryBean.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/SetFactoryBean.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/support/SimpleBeanDefinitionRegistry.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/annotation/AnnotationBeanUtils.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/Scope.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/support/ArgumentConvertingMethodInvoker.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/support/MergedBeanDefinitionPostProcessor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/GenericBeanDefinition.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/annotation/Configurable.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/BeanWrapperImpl.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/Aware.java
* /spring-beans-3-1-3-release-sources-

jar/org/springframework/beans/factory/config/InstantiationAwareBeanPostProcessor.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/CustomDateEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/BeanDefinition.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/BeanDefinitionParser.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/CurrencyEditor.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/annotation/InitDestroyAnnotationBeanPostProcessor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/BeanFactory.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/PropertyEditorRegistrySupport.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/config/PropertyPlaceholderConfigurer.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/annotation/Autowired.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/CustomNumberEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/BeanWrapper.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/support/ResourceEditorRegistrar.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/DirectFieldAccessor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/XmlBeanFactory.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/config/DestructionAwareAttributeHolder.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/config/PlaceholderConfigurerSupport.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/annotation/Qualifier.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/BeanDefinitionVisitor.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/BeanClassLoaderAware.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/propertyeditors/StringArrayPropertyEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/StringTrimmerEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/annotation/Value.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/BeanNameAware.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/xml/DefaultBeanDefinitionDocumentReader.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/BeanDefinitionBuilder.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/annotation/RequiredAnnotationBeanPostProcessor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/PropertyValuesEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/DefaultsDefinition.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/BeanMetadataAttributeAccessor.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/UtilNamespaceHandler.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/support/MutableSortDefinition.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/FactoryBeanNotInitializedException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/ManagedProperties.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/annotation/AnnotationBeanWiringInfoResolver.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/PropertyEditorRegistrar.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/CannotLoadBeanClassException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/access/BeanFactoryReference.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/support/BeanDefinitionValidationException.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/RuntimeBeanReference.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/QualifierEntry.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/FailFastProblemReporter.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/config/BeanReferenceFactoryBean.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/wiring/ClassNameBeanWiringInfoResolver.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/XmlReaderContext.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/AliasDefinition.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/ResourceEntityResolver.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/wiring/BeanWiringInfo.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/serviceloader/ServiceLoaderFactoryBean.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/wiring/BeanWiringInfoResolver.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/CustomBooleanEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/LookupOverride.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/BeanMetadataAttribute.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/DefaultDocumentLoader.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/BeanNotOfRequiredTypeException.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/config/PreferencesPlaceholderConfigurer.java

* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/PatternEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/ReaderContext.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/MethodOverride.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/BeanDefinitionStoreException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/NamespaceHandler.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/annotation/Required.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/annotation/AnnotatedBeanDefinition.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/serviceloader/AbstractServiceLoaderBasedFactoryBean.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/xml/AbstractSimpleBeanDefinitionParser.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/support/AutowireCandidateQualifier.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/support/CglibSubclassingInstantiationStrategy.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/BeanDefinitionDefaults.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/support/DefaultBeanNameGenerator.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/serviceloader/ServiceFactoryBean.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/ReaderEventListener.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/ImportDefinition.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/PropertyEditorRegistry.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/ProblemReporter.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/BeanNameGenerator.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/config/RuntimeBeanNameReference.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/access/BeanFactoryLocator.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/parsing/ConstructorArgumentEntry.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/SecurityContextProvider.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/SimpleSecurityContextProvider.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2005 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/MethodReplacer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/DependencyDescriptor.java

* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/BeanDefinitionValueResolver.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/SimpleInstantiationStrategy.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/DefaultListableBeanFactory.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/annotation/InjectionMetadata.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/annotation/BeanFactoryAnnotationUtils.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/AbstractBeanFactory.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/DefaultSingletonBeanRegistry.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/annotation/AutowiredAnnotationBeanPostProcessor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/BeanFactoryUtils.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/ExtendedBeanInfo.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/support/AbstractAutowireCapableBeanFactory.java
*
/spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/BeanDefinitionParserDelegate.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/annotation/AnnotatedGenericBeanDefinition.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/TypeConverterDelegate.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/CommonsLogFactoryBean.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2005 the original author or authors.

*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/InitializingBean.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/BeanIsNotAFactoryException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/support/SortDefinition.java
*
 /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/DisposableBean.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/BeanFactoryPostProcessor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/LocaleEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/access/BootstrapException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/xml/SimpleConstructorNamespaceHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2006 the original author or authors.

*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/URLEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/ResourceBundleEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/PropertyEntry.java
*
 /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/parsing/BeanDefinitionParsingException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/NotReadablePropertyException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/InvalidPropertyException.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/parsing/AbstractComponentDefinition.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/xml/BeanDefinitionDocumentReader.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/SourceExtractor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/NullValueInNestedPathException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/BeanEntry.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/NamedBean.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/BeanDefinitionDecorator.java
*
 /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/xml/XmlBeanDefinitionStoreException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/BeanInstantiationException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/BeanMetadataElement.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/ComponentDefinition.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/parsing/PassThroughSourceExtractor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/BeanInitializationException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/MethodInvocationException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/ByteArrayPropertyEditor.java
* /spring-beans-3-1-3-release-sources-
jar/org/springframework/beans/factory/BeanCreationNotAllowedException.java
*
 /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/propertyeditors/CharArrayPropertyEditor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/Location.java

* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/FatalBeanException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/Mergeable.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/parsing/NullSourceExtractor.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/xml/NamespaceHandlerResolver.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/BeanCurrentlyInCreationException.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/config/BeanReference.java
* /spring-beans-3-1-3-release-sources-jar/org/springframework/beans/factory/HierarchicalBeanFactory.java

1.955 springframework-transaction 3.1.3.RELEASE

1.955.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/work/jboss/JBossWorkManagerUtils.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/annotation/Transactional.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/connection/ConnectionSpecConnectionFactoryAdapter.java
*
 /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/support/PersistenceExceptionTranslationInterceptor.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/DefaultTransactionAttribute.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/jta/WebSphereUowTransactionManager.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/work/jboss/JBossWorkManagerTaskExecutor.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/TransactionDefinition.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/jta/JtaTransactionManager.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/jta/UserTransactionAdapter.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/jta/ManagedTransactionAdapter.java

* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/annotation/AnnotationTransactionAttributeSource.java
*
 /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/NameMatchTransactionAttributeSource.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/MatchAlwaysTransactionAttributeSource.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/AbstractFallbackTransactionAttributeSource.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/TransactionInterceptor.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/MethodMapTransactionAttributeSource.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/jta/SimpleTransactionFactory.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/work/glassfish/GlassFishWorkManagerTaskExecutor.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/endpoint/AbstractMessageEndpointFactory.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/jta/WebLogicJtaTransactionManager.java
*
 /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/RuleBasedTransactionAttribute.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/jta/OC4JJtaTransactionManager.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/CompositeTransactionAttributeSource.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2008 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/TransactionAttributeSourceAdvisor.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/core/ConnectionCallback.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/core/CciTemplate.java
*

/spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/interceptor/TransactionAttributeSourcePointcut.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/TransientDataAccessException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/PlatformTransactionManager.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/support/DefaultTransactionDefinition.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/core/RecordExtractor.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/support/ResourceHolderSupport.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/NonTransientDataAccessResourceException.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/interceptor/BeanFactoryTransactionAttributeSourceAdvisor.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/jca/cci/connection/TransactionAwareConnectionFactoryProxy.java
*
/spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/core/CciOperations.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/context/SpringContextResourceAdapter.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/dao/support/ChainedPersistenceExceptionTranslator.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/core/support/CciDaoSupport.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/connection/SingleConnectionFactory.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/support/ResourceHolder.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/NonTransientDataAccessException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/core/InteractionCallback.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/interceptor/TransactionAttributeSourceEditor.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/TransientDataAccessResourceException.java
*
/spring-tx-3-1-3-release-sources-jar/org/springframework/dao/RecoverableDataAccessException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2006 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/DataIntegrityViolationException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/DataAccessResourceFailureException.java

* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/NoTransactionException.java
*
/spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/InvalidTimeoutException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/support/PersistenceExceptionTranslator.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/PessimisticLockingFailureException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/CleanupFailureDataAccessException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/OptimisticLockingFailureException.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/NestedTransactionNotSupportedException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/support/DaoSupport.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/TypeMismatchDataAccessException.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/dao/IncorrectUpdateSemanticsDataAccessException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/CannotAcquireLockException.java
*
/spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/HeuristicCompletionException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/InvalidDataAccessApiUsageException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/TransactionException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/PermissionDeniedDataAccessException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/CannotSerializeTransactionException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/UnexpectedRollbackException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/InvalidIsolationLevelException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/CannotCreateTransactionException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/ConcurrencyFailureException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/UncategorizedDataAccessException.java
*
/spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/TransactionUsageException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/InvalidDataAccessResourceUsageException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/TransactionAttributeEditor.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/IllegalTransactionStateException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/TransactionTimedOutException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/DataRetrievalFailureException.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/TransactionSuspensionNotSupportedException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/DataAccessException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/DeadlockLoserDataAccessException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2009 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/support/TransactionSynchronizationUtils.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/context/ResourceAdapterApplicationContext.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/support/TransactionSynchronization.java
*
/spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/support/SimpleTransactionStatus.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/DuplicateKeyException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/support/AbstractTransactionStatus.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/config/JtaTransactionManagerBeanDefinitionParser.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/endpoint/GenericMessageEndpointManager.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/support/DataAccessUtils.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/jta/JtaAfterCompletionSynchronization.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/connection/ConnectionFactoryUtils.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/support/DelegatingTransactionDefinition.java
*
/spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/support/SmartTransactionObject.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/annotation/Ejb3TransactionAnnotationParser.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/config/TxNamespaceHandler.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/support/TransactionCallbackWithoutResult.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/work/WorkManagerTaskExecutor.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/jta/TransactionFactory.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/annotation/Isolation.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/support/ResourceAdapterFactoryBean.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/jta/JtaTransactionObject.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/annotation/Propagation.java
*
/spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/support/TransactionSynchronizationAdapter.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/work/SimpleTaskWorkManager.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/TransactionAttribute.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/support/TransactionTemplate.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/support/LocalConnectionFactoryBean.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/support/CallbackPreferringPlatformTransactionManager.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/interceptor/DelegatingTransactionAttribute.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/TransactionStatus.java

* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/config/TxAdviceBeanDefinitionParser.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2012 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/TransactionAspectSupport.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/annotation/AbstractTransactionManagementConfiguration.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/EmptyResultDataAccessException.java
*
 /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/QueryTimeoutException.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/annotation/ProxyTransactionManagementConfiguration.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/dao/IncorrectResultSizeDataAccessException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/TransactionAttributeSource.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/TransactionAspectUtils.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/dao/annotation/PersistenceExceptionTranslationAdvisor.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/context/BootstrapContextAwareProcessor.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/jta/SpringJtaSynchronizationAdapter.java
*
/spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/connection/CciLocalTransactionManager.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/TransactionSystemException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/work/DelegatingWork.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/endpoint/GenericMessageEndpointFactory.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/annotation/TransactionAnnotationParser.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/RollbackRuleAttribute.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/support/ResourceTransactionManager.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/connection/DelegatingConnectionFactory.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/support/SimpleBootstrapContext.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2007 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/NoRollbackRuleAttribute.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2005 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/connection/ConnectionHolder.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/InvalidResultSetAccessException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/core/RecordCreator.java
*
/spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/object/MappingCommAreaOperation.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/CannotGetCciConnectionException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/object/MappingRecordOperation.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/core/support/CommAreaRecord.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2011 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/annotation/TransactionManagementConfigurer.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/annotation/EnableTransactionManagement.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/support/TransactionOperations.java
*
/spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/support/TransactionCallback.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/dao/annotation/PersistenceExceptionTranslationPostProcessor.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/config/TransactionManagementConfigUtils.java
* /spring-tx-3-1-3-release-sources-
jar/org/springframework/transaction/config/AnnotationDrivenBeanDefinitionParser.java

* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/support/TransactionSynchronizationManager.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/support/ResourceHolderSynchronization.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/annotation/SpringTransactionAnnotationParser.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/context/BootstrapContextAware.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/annotation/TransactionManagementConfigurationSelector.java
*
 /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/interceptor/TransactionProxyFactoryBean.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/support/AbstractPlatformTransactionManager.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/support/DefaultTransactionStatus.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2005 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/RecordTypeNotSupportedException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/CannotCreateRecordException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/transaction/SavepointManager.java
*
 /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/object/EisOperation.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/CciOperationNotSupportedException.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/object/SimpleRecordOperation.java
* /spring-tx-3-1-3-release-sources-jar/org/springframework/jca/cci/connection/NotSupportedRecordFactory.java

1.956 netty-buffer 4.1.48.Final

1.956.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/AbstractDerivedByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/AdvancedLeakAwareByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/UnreleasableByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/AbstractReferenceCountedByteBuf.java
*
 /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/SimpleLeakAwareByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/ByteBufHolder.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/ReadOnlyByteBufferBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/FixedCompositeByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PooledUnsafeDirectByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/DefaultByteBufHolder.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/ReadOnlyUnsafeDirectByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/WrappedByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/EmptyByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/ByteBufProcessor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT

* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/UnsafeHeapSwappedByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/UnsafeDirectSwappedByteBuf.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/HeapByteBufUtil.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/AbstractUnsafeSwappedByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PoolChunkListMetric.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PoolArenaMetric.java
*
 /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/UnpooledDuplicatedByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/UnpooledSlicedByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/UnpooledUnsafeHeapByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PoolChunkMetric.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PooledUnsafeHeapByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/UnsafeByteBufUtil.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PoolSubpageMetric.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*

*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/ByteBufAllocatorMetric.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PooledByteBufAllocatorMetric.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/ByteBufAllocatorMetricProvider.java
No license file was found, but licenses were detected in source scan.

~ Copyright 2012 The Netty Project
 ~
 ~ The Netty Project licenses this file to you under the Apache License,
 ~ version 2.0 (the "License"); you may not use this file except in compliance
 ~ with the License. You may obtain a copy of the License at:
 ~
 ~   http://www.apache.org/licenses/LICENSE
2.0
 ~
 ~ Unless required by applicable law or agreed to in writing, software
 ~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
 ~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
 ~ License for the specific language governing permissions and limitations
 ~ under the License.

Found in path(s):
* /netty-buffer-4-1-48-final-sources-jar/META-INF/maven/io.netty/netty-buffer/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PooledHeapByteBuf.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/ByteBufUtil.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/SlicedByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/ByteBufInputStream.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PoolArena.java
*
 /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/CompositeByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PoolSubpage.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/ByteBufAllocator.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/ByteBufOutputStream.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PooledDirectByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/DuplicatedByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/Unpooled.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/UnpooledDirectByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PoolThreadCache.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/ReadOnlyByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/package-info.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/UnpooledByteBufAllocator.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PooledByteBufAllocator.java
*
 /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/AbstractByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/AbstractByteBufAllocator.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PooledByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/UnpooledUnsafeDirectByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PoolChunkList.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/UnpooledHeapByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PoolChunk.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/ByteBuf.java

* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/SwappedByteBuf.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PooledDuplicatedByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/AbstractUnpooledSlicedByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/WrappedUnpooledUnsafeDirectByteBuf.java
*
 /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/PooledSlicedByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/SimpleLeakAwareCompositeByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/AbstractPooledDerivedByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/UnpooledUnsafeNoCleanerDirectByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/WrappedCompositeByteBuf.java
* /netty-buffer-4-1-48-final-sources-jar/io/netty/buffer/AdvancedLeakAwareCompositeByteBuf.java
No license file was found, but licenses were detected in source scan.

The Netty Project licenses this file to you under the Apache License,
version 2.0 (the "License"); you may not use this file except in compliance
with the License. You may obtain a copy of the License at:
http://www.apache.org/licenses/LICENSE-2.0
distributed under the License is distributed on an "AS IS" BASIS, WITHOUT

Found in path(s):
* /netty-buffer-4-1-48-final-sources-jar/META-INF/native-image/io.netty/buffer/native-image.properties

1.957 source-map-js 1.0.2

1.957.1 Available under license :

BSD-3-Clause

Copyright (c) 2009-2011, Mozilla Foundation and contributors

All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the names of the Mozilla Foundation nor the names of project
 contributors may be used to endorse or promote products derived from this
 software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
 IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.958 netty-codec-socks 4.1.49.Final

1.958.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.

*/

Found in path(s):
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5AddressEncoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5AddressDecoder.java
* /netty-codec-socks-4-1-49-final-sources-
jar/io/netty/handler/codec/socksx/SocksPortUnificationServerHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksRequestType.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksResponseType.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksSubnegotiationVersion.java
*
 /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/SocksVersion.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksProtocolVersion.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksCmdStatus.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksCmdType.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksMessageType.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksAuthStatus.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5AuthMethod.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5CommandType.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksAddressType.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthStatus.java
*
 /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5CommandStatus.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksAuthScheme.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5AddressType.java
No license file was found, but licenses were detected in source scan.

~ Copyright 2012 The Netty Project
 ~

~ The Netty Project licenses this file to you under the Apache License,
~ version 2.0 (the "License"); you may not use this file except in compliance
~ with the License. You may obtain a copy of the License at:
~
~ http://www.apache.org/licenses/LICENSE
2.0
~
~ Unless required by applicable law or agreed to in writing, software
~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
~ License for the specific language governing permissions and limitations
~ under the License.

Found in path(s):
* /netty-codec-socks-4-1-49-final-sources-jar/META-INF/maven/io.netty/netty-codec-socks/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5ServerEncoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4ServerEncoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5Message.java
*
/netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/package-info.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4ClientEncoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/package-info.java
* /netty-codec-socks-4-1-49-final-sources-
jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthResponseDecoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/AbstractSocks5Message.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/AbstractSocksMessage.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5InitialRequestDecoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4Message.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/AbstractSocks4Message.java

* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5CommandRequestDecoder.java
*
 /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5CommandResponseDecoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5InitialResponseDecoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5ClientEncoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthRequestDecoder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksInitResponseDecoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5PasswordAuthRequest.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5CommandResponse.java
*
 /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksCommonUtils.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksAuthRequest.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/DefaultSocks4CommandResponse.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4ServerDecoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5InitialRequest.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksAuthResponse.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5CommandRequest.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksMessageEncoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksInitRequest.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthRequest.java
*
 /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksMessage.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/SocksMessage.java

* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksInitResponse.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5PasswordAuthResponse.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4CommandType.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/DefaultSocks4CommandRequest.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksInitRequestDecoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksCmdResponse.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5InitialRequest.java
*
/netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/package-info.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksCmdResponseDecoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksAuthRequestDecoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksRequest.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4CommandResponse.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthResponse.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/UnknownSocksResponse.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4CommandStatus.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5InitialResponse.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksCmdRequestDecoder.java
*
/netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5CommandResponse.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5InitialResponse.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksCmdRequest.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4ClientDecoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/package-info.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksAuthResponseDecoder.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v4/Socks4CommandRequest.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/SocksResponse.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socksx/v5/Socks5CommandRequest.java
* /netty-codec-socks-4-1-49-final-sources-jar/io/netty/handler/codec/socks/UnknownSocksRequest.java

1.959 netty-codec 4.1.49.Final

1.959.1 Available under license :

No license file was found, but licenses were detected in source scan.

~ Copyright 2012 The Netty Project
~
~ The Netty Project licenses this file to you under the Apache License,
~ version 2.0 (the "License"); you may not use this file except in compliance
~ with the License. You may obtain a copy of the License at:
~
~ http://www.apache.org/licenses/LICENSE
2.0
~

~ Unless required by applicable law or agreed to in writing, software
~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
~ License for the specific language governing permissions and limitations
~ under the License.

Found in path(s):
* /netty-codec-4-1-49-final-sources-jar/META-INF/maven/io.netty/netty-codec/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/HeadersUtils.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/ProtocolDetectionState.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/protobuf/ProtobufVarint32FrameDecoder.java
*
 /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/protobuf/ProtobufEncoderNano.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/UnsupportedValueConverter.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/ProtocolDetectionResult.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/protobuf/ProtobufDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/protobuf/ProtobufEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/protobuf/ProtobufDecoderNano.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/protobuf/ProtobufVarint32LengthFieldPrepender.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0

```
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/*
* Written by Robert Harder and released to the public domain, as explained at
* http://creativecommons.org/licenses/publicdomain
*/
/**
* Enumeration of supported Base64 dialects.
* <p>
* The internal lookup tables in this class has been derived from
* <a href="http://iharder.sourceforge.net/current/java/base64/">Robert
 Harder's Public Domain
* Base64 Encoder/Decoder</a>.
*/
```

Found in path(s):
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/base64/Base64Dialect.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/*
* Written by Robert Harder and released to the public domain, as explained at
* http://creativecommons.org/licenses/publicdomain
*/
/**
* Utility class for {@link ByteBuf} that encodes and decodes to and from
* <a href="http://en.wikipedia.org/wiki/Base64">Base64</a> notation.
* <p>
*
```

The encoding and decoding algorithm in this class has been derived from
* Robert Harder's Public Domain
* Base64 Encoder/Decoder.
*/

Found in path(s):
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/base64/Base64.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/JdkZlibDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/xml/XmlFrameDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Crc32c.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
* A decoder that splits the received {@link ByteBuf}s dynamically by the

```
* value of the length field in the message.  It is particularly useful when you
* decode a binary message which has an integer header field that represents the
* length of the message body or the whole message.
*
 <p>
* {@link LengthFieldBasedFrameDecoder} has many configuration parameters so
* that it can decode any message with a length field, which is often seen in
* proprietary client-server protocols. Here are some example that will give
* you the basic idea on which option does what.
*
* <h3>2 bytes length field at offset 0, do not strip header</h3>
*
* The value of the length field in this example is <tt>12 (0x0C)</tt> which
* represents the length of "HELLO, WORLD".  By default, the decoder assumes
* that the length field represents the number of the bytes that follows the
* length field.  Therefore, it can be decoded with the simplistic parameter
* combination.
* <pre>
* <b>lengthFieldOffset</b>   = <b>0</b>
* <b>lengthFieldLength</b>   = <b>2</b>
* lengthAdjustment    = 0
* initialBytesToStrip = 0 (= do not strip header)
*
* BEFORE DECODE (14 bytes)         AFTER DECODE (14 bytes)
* +--------+----------------+      +--------+----------------+
* | Length | Actual Content
 |----->| Length | Actual Content |
* | 0x000C | "HELLO, WORLD" |      | 0x000C | "HELLO, WORLD" |
* +--------+----------------+      +--------+----------------+
* </pre>
*
* <h3>2 bytes length field at offset 0, strip header</h3>
*
* Because we can get the length of the content by calling
* {@link ByteBuf#readableBytes()}, you might want to strip the length
* field by specifying <tt>initialBytesToStrip</tt>.  In this example, we
* specified <tt>2</tt>, that is same with the length of the length field, to
* strip the first two bytes.
* <pre>
* lengthFieldOffset   = 0
* lengthFieldLength   = 2
* lengthAdjustment    = 0
* <b>initialBytesToStrip</b> = <b>2</b> (= the length of the Length field)
*
* BEFORE DECODE (14 bytes)         AFTER DECODE (12 bytes)
* +--------+----------------+      +----------------+
* | Length | Actual Content |----->| Actual Content |
* | 0x000C | "HELLO, WORLD" |      | "HELLO, WORLD" |
```

```
* +--------+----------------+      +----------------+
 * </pre>
*
* <h3>2 bytes length field at offset 0, do not strip header, the length field
*     represents the length of the whole message</h3>
*
* In most cases, the length field represents the length of the message body
* only, as shown in the previous examples.  However, in some protocols, the
* length field represents the length of the whole message, including the
* message header.  In such a case, we specify a non-zero
* <tt>lengthAdjustment</tt>.  Because the length value in this example message
* is always greater than the body length by <tt>2</tt>, we specify <tt>-2</tt>
* as <tt>lengthAdjustment</tt> for compensation.
* <pre>
* lengthFieldOffset   =  0
* lengthFieldLength   =  2
* <b>lengthAdjustment</b>    = <b>-2</b> (= the length of the Length field)
* initialBytesToStrip =  0
*
* BEFORE DECODE (14 bytes)         AFTER DECODE (14 bytes)
* +--------+----------------+      +--------+----------------+
* | Length | Actual Content |----->| Length | Actual
 Content |
* | 0x000E | "HELLO, WORLD" |      | 0x000E | "HELLO, WORLD" |
* +--------+----------------+      +--------+----------------+
* </pre>
*
* <h3>3 bytes length field at the end of 5 bytes header, do not strip header</h3>
*
* The following message is a simple variation of the first example.  An extra
* header value is prepended to the message.  <tt>lengthAdjustment</tt> is zero
* again because the decoder always takes the length of the prepended data into
* account during frame length calculation.
* <pre>
* <b>lengthFieldOffset</b>   = <b>2</b> (= the length of Header 1)
* <b>lengthFieldLength</b>   = <b>3</b>
* lengthAdjustment    = 0
* initialBytesToStrip = 0
*
* BEFORE DECODE (17 bytes)                      AFTER DECODE (17 bytes)
* +----------+----------+----------------+      +----------+----------+----------------+
* | Header 1 |  Length  | Actual Content |----->| Header 1 |  Length  | Actual Content |
* |  0xCAFE  | 0x00000C | "HELLO, WORLD" |      |
  0xCAFE  | 0x00000C | "HELLO, WORLD" |
* +----------+----------+----------------+      +----------+----------+----------------+
* </pre>
*
* <h3>3 bytes length field at the beginning of 5 bytes header, do not strip header</h3>
```

```
*
* This is an advanced example that shows the case where there is an extra
* header between the length field and the message body.  You have to specify a
* positive <tt>lengthAdjustment</tt> so that the decoder counts the extra
* header into the frame length calculation.
* <pre>
* lengthFieldOffset   = 0
* lengthFieldLength   = 3
* <b>lengthAdjustment</b>    = <b>2</b> (= the length of Header 1)
* initialBytesToStrip = 0
*
* BEFORE DECODE (17 bytes)                 AFTER DECODE (17 bytes)
* +----------+----------+----------------+      +----------+----------+----------------+
* |  Length  | Header 1 | Actual Content |----->|  Length  | Header 1 | Actual Content |
* | 0x00000C |  0xCAFE  | "HELLO, WORLD" |      | 0x00000C |  0xCAFE  | "HELLO,
 WORLD" |
* +----------+----------+----------------+      +----------+----------+----------------+
* </pre>
*
* <h3>2 bytes length field at offset 1 in the middle of 4 bytes header,
*     strip the first header field and the length field</h3>
*
* This is a combination of all the examples above.  There are the prepended
* header before the length field and the extra header after the length field.
* The prepended header affects the <tt>lengthFieldOffset</tt> and the extra
* header affects the <tt>lengthAdjustment</tt>.  We also specified a non-zero
* <tt>initialBytesToStrip</tt> to strip the length field and the prepended
* header from the frame.  If you don't want to strip the prepended header, you
* could specify <tt>0</tt> for <tt>initialBytesToSkip</tt>.
* <pre>
* lengthFieldOffset   = 1 (= the length of HDR1)
* lengthFieldLength   = 2
* <b>lengthAdjustment</b>    = <b>1</b> (= the length of HDR2)
* <b>initialBytesToStrip</b> = <b>3</b> (= the length of HDR1 + LEN)
 *
* BEFORE DECODE (16 bytes)                 AFTER DECODE (13 bytes)
* +------+--------+------+----------------+      +------+----------------+
* | HDR1 | Length | HDR2 | Actual Content |----->| HDR2 | Actual Content |
* | 0xCA | 0x000C | 0xFE | "HELLO, WORLD" |      | 0xFE | "HELLO, WORLD" |
* +------+--------+------+----------------+      +------+----------------+
* </pre>
*
* <h3>2 bytes length field at offset 1 in the middle of 4 bytes header,
*     strip the first header field and the length field, the length field
*     represents the length of the whole message</h3>
*
* Let's give another twist to the previous example.  The only difference from
* the previous example is that the length field represents the length of the
```

```
* whole message instead of the message body, just like the third example.
* We have to count the length of HDR1 and Length into <tt>lengthAdjustment</tt>.
* Please note that we don't need to take the length of HDR2 into account
* because
 the length field already includes the whole header length.
* <pre>
* lengthFieldOffset   =  1
* lengthFieldLength   =  2
* <b>lengthAdjustment</b>    = <b>-3</b> (= the length of HDR1 + LEN, negative)
* <b>initialBytesToStrip</b> = <b> 3</b>
*
* BEFORE DECODE (16 bytes)                       AFTER DECODE (13 bytes)
* +------+--------+------+----------------+      +------+----------------+
* | HDR1 | Length | HDR2 | Actual Content |----->| HDR2 | Actual Content |
* | 0xCA | 0x0010 | 0xFE | "HELLO, WORLD" |      | 0xFE | "HELLO, WORLD" |
* +------+--------+------+----------------+      +------+----------------+
* </pre>
* @see LengthFieldPrepender
*/
```

Found in path(s):
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/LengthFieldBasedFrameDecoder.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
```

Found in path(s):
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/CompressionUtil.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/DatagramPacketDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/string/LineSeparator.java
*
 /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/string/LineEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/DatagramPacketEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/DateFormatter.java

* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/ByteBufChecksum.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/CodecOutputList.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2DivSufSort.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2BlockDecompressor.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2HuffmanAllocator.java
*
 /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/LzfDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/FastLzFrameEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2Rand.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2Constants.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/MessageAggregationException.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2Decoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2Encoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2MoveToFrontTable.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2MTFAndRLE2StageEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/FastLzFrameDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/FastLz.java
*
 /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/json/JsonObjectDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Lz4FrameEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/LzmaFrameEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/DecoderResultProvider.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/AsciiHeadersEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/LzfEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Lz4FrameDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/SnappyFramedDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2BlockCompressor.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/json/package-info.java
*

/netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/SnappyFramedEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Lz4Constants.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2HuffmanStageDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2BitReader.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2BitWriter.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Bzip2HuffmanStageEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Crc32.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/ZlibCodecFactory.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/DelimiterBasedFrameDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/protobuf/package-info.java
*
/netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/ZlibDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/ByteToMessageCodec.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/MarshallingDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Snappy.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/Delimiters.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/ContextBoundUnmarshallerProvider.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ObjectEncoderOutputStream.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/bytes/ByteArrayDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/string/StringEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/MessageAggregator.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/MessageToByteEncoder.java
*
/netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/ReplayingDecoderByteBuf.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/JZlibEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/package-info.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/LimitingByteInput.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/MessageToMessageEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/SnappyFrameDecoder.java

* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/ChannelBufferByteInput.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/bytes/ByteArrayEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/MessageToMessageCodec.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/base64/Base64Encoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/string/StringDecoder.java
*
 /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ReferenceMap.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/LineBasedFrameDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/DecompressionException.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ClassLoaderClassResolver.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/package-info.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/MessageToMessageDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/LengthFieldPrepender.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/WeakReferenceMap.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/ZlibWrapper.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/MarshallingEncoder.java
*
 /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/bytes/package-info.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/CompressionException.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/ZlibEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/MarshallerProvider.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/base64/package-info.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/CompatibleMarshallingEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/ZlibUtil.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/base64/Base64Decoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/CorruptedFrameException.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/SoftReferenceMap.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ObjectEncoder.java
*
 /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/DecoderException.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/ThreadLocalUnmarshallerProvider.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/ByteToMessageDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/ThreadLocalMarshallerProvider.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/package-info.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/DefaultMarshallerProvider.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/EncoderException.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/UnsupportedMessageTypeException.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/CachingClassResolver.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/JZlibDecoder.java
*
 /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/DecoderResult.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/FixedLengthFrameDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/JdkZlibEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ClassResolvers.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/PrematureChannelClosureException.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/DefaultUnmarshallerProvider.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/ReplayingDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/CompactObjectInputStream.java

* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/xml/package-info.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/CompactObjectOutputStream.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/SnappyFrameEncoder.java
*
 /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ClassResolver.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/package-info.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/string/package-info.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ObjectDecoderInputStream.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/CompatibleObjectEncoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/ChannelBufferByteOutput.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/TooLongFrameException.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/CompatibleMarshallingDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/serialization/ObjectDecoder.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/CodecException.java
*
 /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/marshalling/UnmarshallerProvider.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/DefaultHeaders.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/EmptyHeaders.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/Headers.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/compression/Lz4XXHash32.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/ValueConverter.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/CharSequenceValueConverter.java
* /netty-codec-4-1-49-final-sources-jar/io/netty/handler/codec/DefaultHeadersImpl.java

1.960 netty-transport-native-epoll 4.1.49.Final

1.960.1 Available under license :

No license file was found, but licenses were detected in source scan.

~ Copyright 2014 The Netty Project
~
~ The Netty Project licenses this file to you under the Apache License,
~ version 2.0 (the "License"); you may not use this file except in compliance
~ with the License. You may obtain a copy of the License at:
~
~ http://www.apache.org/licenses/LICENSE
2.0
~

~ Unless required by applicable law or agreed to in writing, software
~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
~ License for the specific language governing permissions and limitations
~ under the License.

Found in path(s):
* /netty-transport-native-epoll-4-1-49-final-sources-jar/META-INF/maven/io.netty/netty-transport-native-epoll/pom.xml
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
   * Set the {@code TCP_MD5SIG} option on the socket. See {@code linux/tcp.h} for more details.
   * Keys can only be set on, not read to prevent a potential leak, as they are confidential.
   * Allowing them being read would mean anyone with access to the channel could get them.

  */
/**
   * Set the {@code TCP_QUICKACK} option on the socket. See <a
href="http://linux.die.net/man/7/tcp">TCP_QUICKACK</a>
   * for more details.
   */
```

Found in path(s):
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollSocketChannelConfig.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
```

```
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
    * Set the {@code TCP_MD5SIG} option on the socket. See {@code linux/tcp.h} for more details.
    * Keys can only be set on, not read to prevent a potential leak, as they are confidential.
    * Allowing them being read would mean anyone with access to the channel could get them.

  */
```

Found in path(s):
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollServerSocketChannelConfig.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
```

Found in path(s):
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/AbstractEpollChannel.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollSocketChannel.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/NativeDatagramPacketArray.java
*
 /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollEventLoopGroup.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollChannelOption.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/package-info.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollTcpInfo.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollDatagramChannel.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollEventLoop.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/Epoll.java

* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollServerSocketChannel.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollDatagramChannelConfig.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollEventArray.java
* /netty-transport-native-epoll-4-1-49-final-sources-
jar/io/netty/channel/epoll/EpollServerDomainSocketChannel.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/TcpMd5Util.java
*
 /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollDomainSocketChannel.java
* /netty-transport-native-epoll-4-1-49-final-sources-
jar/io/netty/channel/epoll/EpollRecvByteAllocatorStreamingHandle.java

* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/AbstractEpollStreamChannel.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollServerChannelConfig.java
* /netty-transport-native-epoll-4-1-49-final-sources-
jar/io/netty/channel/epoll/EpollDomainSocketChannelConfig.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/AbstractEpollServerChannel.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollMode.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollChannelConfig.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/EpollRecvByteAllocatorHandle.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/Native.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/netty_epoll_native.c
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):

* /netty-transport-native-epoll-4-1-49-final-sources-jar/netty_epoll_linuxsocket.c
* /netty-transport-native-epoll-4-1-49-final-sources-jar/netty_epoll_linuxsocket.h
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/LinuxSocket.java
* /netty-transport-native-epoll-4-1-49-final-sources-jar/io/netty/channel/epoll/NativeStaticallyReferencedJniMethods.java

1.961 netty-handler 4.1.49.Final

1.961.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/traffic/package-info.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/traffic/TrafficCounter.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/traffic/ChannelTrafficShapingHandler.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/traffic/GlobalTrafficShapingHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2018 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations

* under the License.
*/

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/SignatureAlgorithmConverter.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslCachingKeyMaterialProvider.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslPrivateKey.java
*
 /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslX509TrustManagerWrapper.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslKeyMaterialProvider.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslKeyMaterial.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslTlsv13X509ExtendedTrustManager.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/ExtendedOpenSslSession.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslSession.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/DefaultOpenSslKeyMaterial.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslX509KeyManagerFactory.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslCachingX509KeyManagerFactory.java
No license file was found, but licenses were detected in source scan.

The Netty Project licenses this file to you under the Apache License,
version 2.0 (the "License"); you may not use this file except in compliance
with the License. You may obtain a copy of the License at:
http://www.apache.org/licenses/LICENSE-2.0
distributed under the License is distributed on an "AS IS" BASIS, WITHOUT

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/META-INF/native-image/io.netty/handler/native-image.properties
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/TrustManagerFactoryWrapper.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/SslMasterKeyHandler.java

* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/KeyManagerFactoryWrapper.java
*
 /netty-handler-4-1-49-final-sources-jar/io/netty/handler/address/DynamicAddressConnectHandler.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/address/package-info.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/PseudoRandomFunction.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/util/X509KeyManagerWrapper.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/util/SimpleKeyManagerFactory.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslPrivateKeyMethod.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ipfilter/IpSubnetFilterRule.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ipfilter/IpFilterRule.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkSslEngine.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/SslContext.java
*
 /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslServerSessionContext.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/SslProvider.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/util/SimpleTrustManagerFactory.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslX509Certificate.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkBaseApplicationProtocolNegotiator.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ipfilter/RuleBasedIpFilter.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkSslContext.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/util/FingerprintTrustManagerFactory.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/JettyNpnSslEngine.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/SniHandler.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/JettyAlpnSslEngine.java
*
 /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkDefaultApplicationProtocolNegotiator.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslClientContext.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/ApplicationProtocolUtil.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkSslServerContext.java

* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/ApplicationProtocolNegotiator.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslSessionStats.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ipfilter/IpFilterRuleType.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkNpnApplicationProtocolNegotiator.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslNpnApplicationProtocolNegotiator.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslEngine.java
*
 /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ipfilter/package-info.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ipfilter/AbstractRemoteAddressFilter.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/PemReader.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/CipherSuiteConverter.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/SslUtils.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/traffic/GlobalChannelTrafficCounter.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/util/OpenJdkSelfSignedCertGenerator.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/util/ThreadLocalInsecureRandom.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkSslClientContext.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslEngineMap.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslSessionContext.java
*
 /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSsl.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslContext.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslDefaultApplicationProtocolNegotiator.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/ApplicationProtocolConfig.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/util/BouncyCastleSelfSignedCertGenerator.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/CipherSuiteFilter.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/Java7SslParametersUtils.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ipfilter/UniqueIpFilter.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/IdentityCipherSuiteFilter.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkApplicationProtocolNegotiator.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/util/InsecureTrustManagerFactory.java
*
 /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkAlpnApplicationProtocolNegotiator.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/SupportedCipherSuiteFilter.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslApplicationProtocolNegotiator.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslServerContext.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2011 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT

* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/traffic/AbstractTrafficShapingHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
// Try the OpenJDK's proprietary implementation.

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/util/SelfSignedCertificate.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/SslCompletionEvent.java

* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkAlpnSslEngine.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/SslClientHelloHandler.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/AbstractSniHandler.java
*
 /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/ocsp/package-info.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/SslCloseCompletionEvent.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OptionalSslHandler.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/JdkAlpnSslUtils.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/SniCompletionEvent.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/ocsp/OcspClientHandler.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/Conscrypt.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/ConscryptAlpnSslEngine.java
No license file was found, but licenses were detected in source scan.

~ Copyright 2012 The Netty Project
 ~
 ~ The Netty Project licenses this file to you under the Apache License,
 ~ version 2.0 (the "License"); you may not use this file except in compliance
 ~ with the License. You may obtain a copy of the License at:
 ~
 ~   http://www.apache.org/licenses/LICENSE
2.0
 ~
 ~ Unless required by applicable law or agreed to in writing, software
 ~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
 ~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
 ~ License for the specific language governing permissions and limitations
 ~ under the License.

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/META-INF/maven/io.netty/netty-handler/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/logging/LoggingHandler.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/timeout/WriteTimeoutException.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/SslHandler.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/util/package-info.java
*
 /netty-handler-4-1-49-final-sources-jar/io/netty/handler/stream/ChunkedStream.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/package-info.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/timeout/IdleStateEvent.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/logging/package-info.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/timeout/package-info.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/stream/ChunkedNioFile.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/stream/ChunkedInput.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/timeout/IdleState.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/timeout/ReadTimeoutException.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/stream/ChunkedFile.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/timeout/TimeoutException.java
*
 /netty-handler-4-1-49-final-sources-jar/io/netty/handler/timeout/ReadTimeoutHandler.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/timeout/WriteTimeoutHandler.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/stream/package-info.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/stream/ChunkedWriteHandler.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/NotSslRecordException.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/stream/ChunkedNioStream.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/logging/LogLevel.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/timeout/IdleStateHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/traffic/GlobalChannelTrafficShapingHandler.java

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/SslHandshakeCompletionEvent.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/ClientAuth.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/ApplicationProtocolNegotiationHandler.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslSessionTicketKey.java
*
 /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/ApplicationProtocolAccessor.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/ApplicationProtocolNames.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslJavaxX509Certificate.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/SslContextBuilder.java

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2020 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/address/ResolveAddressHandler.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/SslHandshakeTimeoutException.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/logging/ByteBufFormat.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslCertificateException.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/ReferenceCountedOpenSslServerContext.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/PemX509Certificate.java
*
 /netty-handler-4-1-49-final-sources-jar/io/netty/handler/flow/package-info.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/flush/package-info.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/flush/FlushConsolidationHandler.java

* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/PemValue.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/Java8SslUtils.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/util/X509TrustManagerWrapper.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/PemEncoded.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/DelegatingSslContext.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/OpenSslKeyMaterialManager.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/ReferenceCountedOpenSslEngine.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/PemPrivateKey.java
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/ReferenceCountedOpenSslContext.java
*
/netty-handler-4-1-49-final-sources-jar/io/netty/handler/ssl/ReferenceCountedOpenSslClientContext.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version
* 2.0 (the "License"); you may not use this file except in compliance with the
* License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-handler-4-1-49-final-sources-jar/io/netty/handler/flow/FlowControlHandler.java

1.962 netty-transport-native-unix-common 4.1.49.Final

1.962.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/netty_unix_socket.h
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/DomainSocketChannel.java
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/netty_unix_filedescriptor.c
*
 /netty-transport-native-unix-common-4-1-49-final-sources-
jar/io/netty/channel/unix/DomainSocketChannelConfig.java
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/netty_unix_socket.c
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/netty_unix_errors.h
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/netty_unix_filedescriptor.h
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/DatagramSocketAddress.java
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/DomainSocketAddress.java
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/NativeInetAddress.java
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/Socket.java
* /netty-transport-native-unix-common-4-1-49-final-sources-
jar/io/netty/channel/unix/ServerDomainSocketChannel.java
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/Errors.java
*
 /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/UnixChannel.java
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/netty_unix_errors.c
* /netty-transport-native-unix-common-4-1-49-final-sources-
jar/io/netty/channel/unix/DomainSocketReadMode.java
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/FileDescriptor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/UnixChannelOption.java
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/IovArray.java
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/package-info.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/netty_unix_jni.h
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/UnixChannelUtil.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-native-unix-common-4-1-49-final-sources-
jar/io/netty/channel/unix/LimitsStaticallyReferencedJniMethods.java
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/Limits.java

* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/SocketWritableByteChannel.java
*
 /netty-transport-native-unix-common-4-1-49-final-sources-jar/netty_unix_util.c
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/netty_unix_limits.c
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/PeerCredentials.java
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/ErrorsStaticallyReferencedJniMethods.java
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/netty_unix_util.h
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/netty_unix_limits.h
No license file was found, but licenses were detected in source scan.

~ Copyright 2016 The Netty Project
 ~
 ~ The Netty Project licenses this file to you under the Apache License,
 ~ version 2.0 (the "License"); you may not use this file except in compliance
 ~ with the License. You may obtain a copy of the License at:
 ~
 ~   http://www.apache.org/licenses/LICENSE
2.0
 ~
 ~ Unless required by applicable law or agreed to in writing, software
 ~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
 ~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
 ~ License for the specific language governing permissions and limitations
 ~ under the License.

Found in path(s):
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/META-INF/maven/io.netty/netty-transport-native-unix-common/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2018 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/netty_unix_buffer.h
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/netty_unix_buffer.c
* /netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/PreferredDirectByteBufAllocator.java
*
/netty-transport-native-unix-common-4-1-49-final-sources-jar/io/netty/channel/unix/Buffer.java

1.963 netty-codec-http 4.1.49.Final

1.963.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DecoratingHttp2FrameWriter.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/WeightedFairQueueByteDistributor.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/UniformStreamByteDistributor.java
*
/netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DecoratingHttp2ConnectionDecoder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/StreamBufferingEncoder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DecoratingHttp2ConnectionEncoder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/StreamByteDistributor.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/InboundHttp2ToHttpAdapterBuilder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2StreamVisitor.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2PromisedRequestVerifier.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/AbstractInboundHttp2ToHttpAdapterBuilder.java
No license file was found, but licenses were detected in source scan.

The Netty Project licenses this file to you under the Apache License,
version 2.0 (the "License"); you may not use this file except in compliance

with the License. You may obtain a copy of the License at:
http://www.apache.org/licenses/LICENSE-2.0
distributed under the License is distributed on an "AS IS" BASIS, WITHOUT

Found in path(s):
* /netty-codec-http2-4-1-49-final-sources-jar/META-INF/native-image/io.netty/codec-http2/native-image.properties
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2UnknownFrame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2StreamChannelId.java
* /netty-codec-http2-4-1-49-final-sources-
jar/io/netty/handler/codec/http2/CleartextHttp2ServerUpgradeHandler.java
*
 /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2MultiplexCodecBuilder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2StreamChannelBootstrap.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2UnknownFrame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameCodecBuilder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2StreamChannel.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameStreamEvent.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HttpToHttp2ConnectionHandlerBuilder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/CharSequenceMap.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ConnectionHandlerBuilder.java
*
/netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/AbstractHttp2ConnectionHandlerBuilder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ConnectionPrefaceAndSettingsFrameWrittenEvent.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either

express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/
// https://tools.ietf.org/html/rfc7540#section-8.1.2.2 makes a special exception for TE

Found in path(s):
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HttpConversionUtil.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2SecurityUtil.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameLogger.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2OutboundFrameLogger.java
*
 /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2InboundFrameLogger.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.

*/

Found in path(s):
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ResetFrame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2WindowUpdateFrame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/AbstractHttp2StreamFrame.java
*
 /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2SettingsFrame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameCodec.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ChannelDuplexHandler.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2GoAwayFrame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/ReadOnlyHttp2Headers.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2MultiplexCodec.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2GoAwayFrame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2HeadersFrame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/InboundHttpToHttp2Adapter.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2StreamFrame.java
*
 /netty-codec-http2-4-1-49-final-sources-
jar/io/netty/handler/codec/http2/Http2StreamFrameToHttpObjectCodec.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2DataFrame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameStream.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2PingFrame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameStreamVisitor.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2DataFrame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Frame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameStreamException.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2WindowUpdateFrame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2PingFrame.java
*
 /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2SettingsFrame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2HeadersFrame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2ResetFrame.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations

* under the License.
*/

Found in path(s):
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/AbstractHttp2StreamChannel.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2SettingsAckFrame.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/MaxCapacityQueue.java
*
/netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2MultiplexHandler.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2SettingsAckFrame.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2EventAdapter.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2ConnectionDecoder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2FrameReader.java
*
/netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/InboundHttp2ToHttpAdapter.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/package-info.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ServerUpgradeCodec.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2LocalFlowController.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameSizePolicy.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameListenerDecorator.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ConnectionDecoder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2FrameWriter.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2HeadersDecoder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameListener.java
*
/netty-codec-http2-4-1-49-final-sources-
jar/io/netty/handler/codec/http2/DelegatingDecompressorFrameListener.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ConnectionEncoder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HttpToHttp2ConnectionHandler.java

* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/EmptyHttp2Headers.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2HeadersEncoder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ConnectionHandler.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2NoMoreStreamIdsException.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Connection.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/CompressorHttp2ConnectionEncoder.java
*
 /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2DataWriter.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ConnectionAdapter.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2LifecycleManager.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Settings.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2RemoteFlowController.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2Headers.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Flags.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameAdapter.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameReader.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2Connection.java
*
 /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2HeadersDecoder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Error.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2LocalFlowController.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2ConnectionEncoder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Stream.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Headers.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2RemoteFlowController.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ClientUpgradeCodec.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameTypes.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/DefaultHttp2HeadersEncoder.java
*
 /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FrameWriter.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2FlowController.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2Exception.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2CodecUtil.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations

* under the License.
*/
/*
* Copyright 2014 Twitter, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable
 law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackHuffmanEncoder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackUtil.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackHeaderField.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackEncoder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackDecoder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackDynamicTable.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackHuffmanDecoder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/HpackStaticTable.java
No license file was found, but licenses were detected in source scan.

~ Copyright 2014 The Netty Project
 ~
 ~ The Netty Project licenses this file to you under the Apache License,
 ~ version 2.0 (the "License"); you may not use this file except in compliance
 ~ with the License. You may obtain a copy of the License at:
 ~
 ~   http://www.apache.org/licenses/LICENSE
2.0
 ~
 ~ Unless required by applicable law or agreed to in writing, software
 ~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
 ~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
 ~ License for the specific language governing permissions and limitations
 ~ under the License.

Found in path(s):
* /netty-codec-http2-4-1-49-final-sources-jar/META-INF/maven/io.netty/netty-codec-http2/pom.xml

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2SettingsReceivedConsumer.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2ControlFrameLimitEncoder.java
* /netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2EmptyDataFrameListener.java
*
/netty-codec-http2-4-1-49-final-sources-jar/io/netty/handler/codec/http2/Http2EmptyDataFrameConnectionDecoder.java

1.964 netty-transport 4.1.49.Final

1.964.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/AbstractCoalescingBufferQueue.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/MaxBytesRecvByteBufAllocator.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DefaultMaxMessagesRecvByteBufAllocator.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/pool/ChannelPoolMap.java
*
 /netty-transport-4-1-49-final-sources-jar/io/netty/channel/pool/AbstractChannelPoolHandler.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/pool/SimpleChannelPool.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/pool/FixedChannelPool.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/pool/AbstractChannelPoolMap.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/pool/ChannelHealthChecker.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DefaultMaxBytesRecvByteBufAllocator.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/MaxMessagesRecvByteBufAllocator.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/pool/ChannelPool.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/pool/package-info.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/pool/ChannelPoolHandler.java
No license file was found, but licenses were detected in source scan.

The Netty Project licenses this file to you under the Apache License,
version 2.0 (the "License"); you may not use this file except in compliance
with the License. You may obtain a copy of the License at:
http://www.apache.org/licenses/LICENSE-2.0
distributed under the License is distributed on an "AS IS" BASIS, WITHOUT

Found in path(s):
* /netty-transport-4-1-49-final-sources-jar/META-INF/native-image/io.netty/transport/native-image.properties
No license file was found, but licenses were detected in source scan.

/*

* Copyright 2018 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/nio/NioChannelOption.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/SimpleUserEventChannelHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/EventLoopTaskQueueFactory.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ExtendedClosedChannelException.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelHandlerMask.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:

*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/oio/OioByteStreamChannel.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/ChannelInputShutdownReadComplete.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DelegatingChannelPromiseNotifier.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/internal/ChannelUtils.java
*
 /netty-transport-4-1-49-final-sources-jar/io/netty/bootstrap/FailedChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/ChannelOutputShutdownEvent.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/oio/OioDatagramChannelConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/internal/package-info.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/ChannelOutputShutdownException.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/PendingBytesTracker.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/oio/DefaultOioDatagramChannelConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/nio/SelectedSelectionKeySetSelector.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*

* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/PendingWriteQueue.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelFactory.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/embedded/EmbeddedChannelId.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/AbstractEventLoop.java
*
 /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ReflectiveChannelFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-49-final-sources-jar/io/netty/bootstrap/AbstractBootstrapConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DefaultSelectStrategy.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/group/VoidChannelGroupFuture.java
*
 /netty-transport-4-1-49-final-sources-jar/io/netty/channel/SelectStrategyFactory.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DefaultSelectStrategyFactory.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelInboundInvoker.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/bootstrap/ServerBootstrapConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelOutboundInvoker.java

* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/WriteBufferWaterMark.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/SelectStrategy.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/PreferHeapByteBufAllocator.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/bootstrap/BootstrapConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/DuplexChannel.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelPromiseNotifier.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/local/LocalChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/local/LocalEventLoopGroup.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/group/package-info.java
*
 /netty-transport-4-1-49-final-sources-jar/io/netty/channel/FixedRecvByteBufAllocator.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/FailedChannelFuture.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelPromiseAggregator.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/bootstrap/AbstractBootstrap.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DefaultFileRegion.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DefaultEventLoop.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/DefaultDatagramChannelConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/local/package-info.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelOutboundHandler.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/oio/OioDatagramChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/bootstrap/package-info.java
*
 /netty-transport-4-1-49-final-sources-jar/io/netty/channel/group/CombinedIterator.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/oio/package-info.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DefaultChannelConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/SocketChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelInboundHandlerAdapter.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/oio/package-info.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DefaultChannelPromise.java

* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/ChannelInputShutdownEvent.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/group/ChannelGroupFuture.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/VoidChannelPromise.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/group/DefaultChannelGroupFuture.java
*
 /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/nio/NioDatagramChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/ServerSocketChannelConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelException.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/MultithreadEventLoopGroup.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/DatagramChannelConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/oio/OioEventLoopGroup.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/CombinedChannelDuplexHandler.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/embedded/package-info.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelPipelineException.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelOption.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/AbstractChannel.java
*
 /netty-transport-4-1-49-final-sources-jar/io/netty/bootstrap/ServerBootstrap.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/nio/package-info.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/SucceededChannelFuture.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/AbstractChannelHandlerContext.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/oio/OioServerSocketChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelFlushPromiseNotifier.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/EventLoop.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelFutureListener.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/nio/NioTask.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/AdaptiveRecvByteBufAllocator.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/RecvByteBufAllocator.java
*
 /netty-transport-4-1-49-final-sources-jar/io/netty/channel/nio/AbstractNioChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/embedded/EmbeddedChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/package-info.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelHandlerContext.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ThreadPerChannelEventLoopGroup.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/SocketChannelConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ServerChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/nio/AbstractNioMessageChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/CompleteChannelFuture.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/EventLoopGroup.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/DatagramPacket.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/EventLoopException.java
*
 /netty-transport-4-1-49-final-sources-jar/io/netty/channel/embedded/EmbeddedEventLoop.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/AbstractServerChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DefaultEventLoopGroup.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/FileRegion.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ThreadPerChannelEventLoop.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/bootstrap/Bootstrap.java

* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelPipeline.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/oio/AbstractOioByteChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/DefaultSocketChannelConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/nio/NioEventLoopGroup.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/nio/ProtocolFamilyConverter.java
*
 /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/nio/NioServerSocketChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/DatagramChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelPromise.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/local/LocalAddress.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/SingleThreadEventLoop.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelInboundHandler.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/oio/AbstractOioMessageChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelOutboundHandlerAdapter.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/Channel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/local/LocalServerChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/nio/NioSocketChannel.java
*
 /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/InternetProtocolFamily.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/nio/package-info.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/ServerSocketChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/group/ChannelGroupFutureListener.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelInitializer.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelFuture.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelMetadata.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/nio/AbstractNioByteChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/nio/NioEventLoop.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DefaultChannelPipeline.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/embedded/EmbeddedSocketAddress.java
*
 /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/oio/OioSocketChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/package-info.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/nio/NioDatagramChannelConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelDuplexHandler.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/DefaultServerSocketChannelConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/oio/AbstractOioChannel.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/local/LocalChannelRegistry.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0

```
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
* Handles an I/O event or intercepts an I/O operation, and forwards it to its next handler in
* its {@link ChannelPipeline}.
*
* <h3>Sub-types</h3>
* <p>
* {@link ChannelHandler} itself does not provide many methods, but you usually have to implement one of its
subtypes:
* <ul>
* <li>{@link
 ChannelInboundHandler} to handle inbound I/O events, and</li>
* <li>{@link ChannelOutboundHandler} to handle outbound I/O operations.</li>
* </ul>
* </p>
* <p>
* Alternatively, the following adapter classes are provided for your convenience:
* <ul>
* <li>{@link ChannelInboundHandlerAdapter} to handle inbound I/O events,</li>
* <li>{@link ChannelOutboundHandlerAdapter} to handle outbound I/O operations, and</li>
* <li>{@link ChannelDuplexHandler} to handle both inbound and outbound events</li>
* </ul>
* </p>
* <p>
* For more information, please refer to the documentation of each subtype.
* </p>
*
* <h3>The context object</h3>
* <p>
* A {@link ChannelHandler} is provided with a {@link ChannelHandlerContext}
* object.  A {@link ChannelHandler} is supposed to interact with the
* {@link ChannelPipeline} it belongs to via a context object.  Using the
* context object, the {@link ChannelHandler} can pass events upstream or
* downstream, modify the pipeline dynamically,
 or store the information
* (using {@link AttributeKey}s) which is specific to the handler.
*
* <h3>State management</h3>
*
* A {@link ChannelHandler} often needs to store some stateful information.
* The simplest and recommended approach is to use member variables:
* <pre>
```

```
* public interface Message {
*     // your methods here
* }
*
* public class DataServerHandler extends {@link SimpleChannelInboundHandler}&lt;Message&gt; {
*
*     <b>private boolean loggedIn;</b>
*
*     {@code @Override}
*     public void channelRead0({@link ChannelHandlerContext} ctx, Message message) {
*         if (message instanceof LoginMessage) {
*             authenticate((LoginMessage) message);
*             <b>loggedIn = true;</b>
*         } else (message instanceof GetDataMessage) {
*             if (<b>loggedIn</b>) {
*                 ctx.writeAndFlush(fetchSecret((GetDataMessage) message));
*             } else {
*                 fail();
*             }
*         }
 *     }
*     ...
* }
* </pre>
* Because the handler instance has a state variable which is dedicated to
* one connection, you have to create a new handler instance for each new
* channel to avoid a race condition where a unauthenticated client can get
* the confidential information:
* <pre>
* // Create a new handler instance per channel.
* // See {@link ChannelInitializer#initChannel(Channel)}.
* public class DataServerInitializer extends {@link ChannelInitializer}&lt;{@link Channel}&gt; {
*     {@code @Override}
*     public void initChannel({@link Channel} channel) {
*         channel.pipeline().addLast("handler", <b>new DataServerHandler()</b>);
*     }
* }
*
* </pre>
*
* <h4>Using {@link AttributeKey}s</h4>
*
* Although it's recommended to use member variables to store the state of a
* handler, for some reason you might not want to create many handler instances.
* In such a case, you can use {@link AttributeKey}s which is provided by
* {@link ChannelHandlerContext}:
 * <pre>
* public interface Message {
```

```
*     // your methods here
* }
*
* {@code @Sharable}
* public class DataServerHandler extends {@link SimpleChannelInboundHandler}&lt;Message&gt; {
*     private final {@link AttributeKey}&lt;{@link Boolean}&gt; auth =
*         {@link AttributeKey#valueOf(String) AttributeKey.valueOf("auth")};
*
*     {@code @Override}
*     public void channelRead({@link ChannelHandlerContext} ctx, Message message) {
*         {@link Attribute}&lt;{@link Boolean}&gt; attr = ctx.attr(auth);
*         if (message instanceof LoginMessage) {
*             authenticate((LoginMessage) o);
*             <b>attr.set(true)</b>;
*         } else (message instanceof GetDataMessage) {
*             if (<b>Boolean.TRUE.equals(attr.get())</b>) {
*                 ctx.writeAndFlush(fetchSecret((GetDataMessage) o));
*             } else {
*                 fail();
*             }
*         }
*     }
*     ...
* }
* </pre>
* Now that the state
 of the handler is attached to the {@link ChannelHandlerContext}, you can add the
* same handler instance to different pipelines:
* <pre>
* public class DataServerInitializer extends {@link ChannelInitializer}&lt;{@link Channel}&gt; {
*
*     private static final DataServerHandler <b>SHARED</b> = new DataServerHandler();
*
*     {@code @Override}
*     public void initChannel({@link Channel} channel) {
*         channel.pipeline().addLast("handler", <b>SHARED</b>);
*     }
* }
* </pre>
*
*
* <h4>The {@code @Sharable} annotation</h4>
* <p>
* In the example above which used an {@link AttributeKey},
* you might have noticed the {@code @Sharable} annotation.
* <p>
* If a {@link ChannelHandler} is annotated with the {@code @Sharable}
* annotation, it means you can create an instance of the handler just once and
```

* add it to one or more {@link ChannelPipeline}s multiple times without
* a race condition.
* <p>
* If this annotation is not specified, you have to create
 a new handler
* instance every time you add it to a pipeline because it has unshared state
* such as member variables.
* <p>
* This annotation is provided for documentation purpose, just like
* the JCIP annotations.
*
* <h3>Additional resources worth reading</h3>
* <p>
* Please refer to the {@link ChannelHandler}, and
* {@link ChannelPipeline} to find out more about inbound and outbound operations,
* what fundamental differences they have, how they flow in a pipeline, and how to handle
* the operation in your application.
*/

Found in path(s):
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DefaultChannelId.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/oio/OioSocketChannelConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ConnectTimeoutException.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/oio/DefaultOioServerSocketChannelConfig.java
*
 /netty-transport-4-1-49-final-sources-jar/io/netty/channel/group/ChannelMatchers.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/group/ChannelGroupException.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DefaultMessageSizeEstimator.java

* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DefaultAddressedEnvelope.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelHandlerAdapter.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/MessageSizeEstimator.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/bootstrap/ChannelFactory.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/group/ChannelGroup.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelProgressivePromise.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelProgressiveFuture.java
*
/netty-transport-4-1-49-final-sources-jar/io/netty/channel/SimpleChannelInboundHandler.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/group/ChannelMatcher.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/oio/DefaultOioSocketChannelConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelProgressiveFutureListener.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/socket/oio/OioServerSocketChannelConfig.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelOutboundBuffer.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/nio/SelectedSelectionKeySet.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/ChannelId.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/AddressedEnvelope.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/group/DefaultChannelGroup.java
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DefaultChannelProgressivePromise.java
*
/netty-transport-4-1-49-final-sources-jar/io/netty/channel/AbstractEventLoopGroup.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/CoalescingBufferQueue.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance

* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-transport-4-1-49-final-sources-jar/io/netty/channel/DefaultChannelHandlerContext.java
No license file was found, but licenses were detected in source scan.

~ Copyright 2012 The Netty Project
 ~
 ~ The Netty Project licenses this file to you under the Apache License,
 ~ version 2.0 (the "License"); you may not use this file except in compliance
 ~ with the License. You may obtain a copy of the License at:
 ~
 ~   http://www.apache.org/licenses/LICENSE
2.0
 ~
 ~ Unless required by applicable law or agreed to in writing, software
 ~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
 ~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
 ~ License for the specific language governing permissions and limitations
 ~ under the License.

Found in path(s):
* /netty-transport-4-1-49-final-sources-jar/META-INF/maven/io.netty/netty-transport/pom.xml

1.965 netty-resolver 4.1.49.Final

1.965.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/AbstractAddressResolver.java
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/CompositeNameResolver.java
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/InetNameResolver.java
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/HostsFileEntriesResolver.java
*
 /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/DefaultAddressResolverGroup.java
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/DefaultNameResolver.java
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/InetSocketAddressResolver.java
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/AddressResolver.java
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/HostsFileParser.java
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/DefaultHostsFileEntriesResolver.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/NoopAddressResolver.java
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/package-info.java
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/SimpleNameResolver.java
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/NoopAddressResolverGroup.java
*
 /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/NameResolver.java
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/AddressResolverGroup.java
No license file was found, but licenses were detected in source scan.

~ Copyright 2014 The Netty Project

~
~ The Netty Project licenses this file to you under the Apache License,
~ version 2.0 (the "License"); you may not use this file except in compliance
~ with the License. You may obtain a copy of the License at:
~
~   http://www.apache.org/licenses/LICENSE
2.0
~
~ Unless required by applicable law or agreed to in writing, software
~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
~ License for the specific language governing permissions and limitations
~ under the License.

Found in path(s):
* /netty-resolver-4-1-49-final-sources-jar/META-INF/maven/io.netty/netty-resolver/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/RoundRobinInetAddressResolver.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/HostsFileEntries.java
* /netty-resolver-4-1-49-final-sources-jar/io/netty/resolver/ResolvedAddressTypes.java

1.966 netty-handler-proxy 4.1.49.Final

1.966.1 Available under license :

No license file was found, but licenses were detected in source scan.

~ Copyright 2014 The Netty Project
~
~ The Netty Project licenses this file to you under the Apache License,
~ version 2.0 (the "License"); you may not use this file except in compliance
~ with the License. You may obtain a copy of the License at:
~
~ http://www.apache.org/licenses/LICENSE
2.0
~
~ Unless required by applicable law or agreed to in writing, software
~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
~ License for the specific language governing permissions and limitations
~ under the License.

Found in path(s):
* /netty-handler-proxy-4-1-49-final-sources-jar/META-INF/maven/io.netty/netty-handler-proxy/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations

* under the License.
*/

Found in path(s):
* /netty-handler-proxy-4-1-49-final-sources-jar/io/netty/handler/proxy/ProxyConnectException.java
* /netty-handler-proxy-4-1-49-final-sources-jar/io/netty/handler/proxy/ProxyConnectionEvent.java
* /netty-handler-proxy-4-1-49-final-sources-jar/io/netty/handler/proxy/package-info.java
*
/netty-handler-proxy-4-1-49-final-sources-jar/io/netty/handler/proxy/Socks4ProxyHandler.java
* /netty-handler-proxy-4-1-49-final-sources-jar/io/netty/handler/proxy/Socks5ProxyHandler.java
* /netty-handler-proxy-4-1-49-final-sources-jar/io/netty/handler/proxy/ProxyHandler.java
* /netty-handler-proxy-4-1-49-final-sources-jar/io/netty/handler/proxy/HttpProxyHandler.java

1.967 negotiator 0.6.3

1.967.1 Available under license :

(The MIT License)

Copyright (c) 2012-2014 Federico Romero
Copyright (c) 2012-2014 Isaac Z. Schlueter
Copyright (c) 2014-2015 Douglas Christopher Wilson

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES
OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.968 json-path 2.7.0

1.968.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2011 the original author or authors.
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/InvalidPathException.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/JsonPath.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/JsonPathException.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/path/PropertyPathToken.java
*
 /json-path-2-7-0-sources-jar/com/jayway/jsonpath/WriteContext.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/spi/json/GsonJsonProvider.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/function/latebinding/PathLateBindingValue.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/InvalidJsonException.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/spi/mapper/JsonSmartMappingProvider.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/spi/json/JettisonProvider.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/InvalidCriteriaException.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/Option.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/Path.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/Configuration.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/path/CompiledPath.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/Criteria.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/spi/json/JsonProvider.java
*
 /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/path/ScanPathToken.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/spi/json/JsonSmartJsonProvider.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/DocumentContext.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/MapFunction.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/path/EvaluationContextImpl.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/path/WildcardPathToken.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/Filter.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/path/PredicatePathToken.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/EvaluationListener.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/InvalidModificationException.java

* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/Predicate.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/TypeRef.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/ReadContext.java
*
/json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/path/ArrayIndexToken.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/spi/mapper/JacksonMappingProvider.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/path/ArraySliceToken.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/spi/mapper/MappingProvider.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/path/PathToken.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/EvaluationContext.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/spi/cache/LRUCache.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/path/PredicateContextImpl.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/Utils.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/spi/json/AbstractJsonProvider.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/spi/mapper/GsonMappingProvider.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/path/ArrayPathToken.java
*
/json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/function/latebinding/JsonLateBindingValue.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/spi/json/JacksonJsonProvider.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/ValueCompareException.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/spi/mapper/TapestryMappingProvider.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/spi/mapper/MappingException.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/path/RootPathToken.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/spi/mapper/JakartaMappingProvider.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/JsonFormatter.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/JsonContext.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/internal/function/latebinding/ILateBindingValue.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/PathNotFoundException.java
* /json-path-2-7-0-sources-jar/com/jayway/jsonpath/ParseContext.java

1.969 minimatch 3.1.2

1.969.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR

IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.970 cookie 0.4.2

1.970.1 Available under license :

(The MIT License)

Copyright (c) 2012-2014 Roman Shtylman <shtylman@gmail.com>
Copyright (c) 2015 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR
OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.971 loadash 1.0.0

1.971.1 Available under license :

ISC

1.972 react-merge-refs 1.1.0

1.972.1 Available under license :

MIT
MIT License

Copyright (c) 2020 Greg Berg

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.973 ansi-regex 4.1.1

1.973.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.974 debug 4.3.4

1.974.1 Available under license :

(The MIT License)

Copyright (c) 2014-2017 TJ Holowaychuk <tj@vision-media.ca>
Copyright (c) 2018-2021 Josh Junon

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the 'Software'), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT
LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.975 sshpk 1.17.0

1.975.1 Available under license :

Copyright Joyent, Inc. All rights reserved.
Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION

WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
IN THE SOFTWARE.
MIT

1.976 metrics-servlets 4.1.0

1.976.1 Available under license :

Apache-2.0

1.977 metrics-jetty 4.1.0

1.977.1 Available under license :

Apache-2.0

1.978 metrics-health-checks 4.1.0

1.978.1 Available under license :

Apache-2.0

1.979 is-shared-array-buffer 1.0.2

1.979.1 Available under license :

MIT License

Copyright (c) 2021 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

MIT

1.980 is-number-object 1.0.7

1.980.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.981 copy-anything 2.0.6

1.981.1 Available under license :

MIT
MIT License

Copyright (c) 2018 Luca Ban - Mesqueeb

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.982 crc-32 1.2.2

1.982.1 Available under license :

Apache License 2.0

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation,

and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable

by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only

on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "{}" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright (C) 2014-present SheetJS LLC

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.983 has-property-descriptors 1.0.0

1.983.1 Available under license :

MIT License

Copyright (c) 2022 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.984 has-bigints 1.0.2

1.984.1 Available under license :

MIT License

Copyright (c) 2019 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.985 functions-have-names 1.2.3

1.985.1 Available under license :

MIT License

Copyright (c) 2019 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.986 unbox-primitive 1.0.2

1.986.1 Available under license :

MIT License

Copyright (c) 2019 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

MIT

1.987 send 0.18.0

1.987.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2012 TJ Holowaychuk
Copyright (c) 2014-2022 Douglas Christopher Wilson

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT
OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.988 globalthis 1.0.3

1.988.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all

copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.989 bn.js 5.2.1

1.989.1 Available under license :

Copyright Fedor Indutny, 2015.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.990 async 3.2.4

1.990.1 Available under license :

MIT
Copyright (c) 2010-2018 Caolan McMahon

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights

to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.991 resilience4j-circuitbreaker 1.7.1

1.991.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
*
*  Copyright 2016 Robert Winkler
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*        http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*
*
*/
```

Found in path(s):
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/internal/InMemoryCircuitBreakerRegistry.java
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/event/CircuitBreakerOnStateTransitionEvent.java
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/event/CircuitBreakerOnErrorEvent.java

*
/resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/event/CircuitBreakerOnResetEvent.java
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/event/AbstractCircuitBreakerEvent.java
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/CircuitBreakerRegistry.java
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/CircuitBreakerConfig.java
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/CallNotPermittedException.java
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/event/CircuitBreakerOnIgnoredErrorEvent.java
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/event/CircuitBreakerOnCallNotPermittedEvent.java
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/event/CircuitBreakerOnSuccessEvent.java
*
/resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/event/CircuitBreakerEvent.java
No license file was found, but licenses were detected in source scan.

```
/*
*
*  Copyright 2017: Robert Winkler
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*        http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*
*
*/
```

Found in path(s):
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/utils/package-info.java
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/CircuitBreaker.java
No license file was found, but licenses were detected in source scan.

```
/*
*
*  Copyright 2016 Robert Winkler and Bohdan Storozhuk
*
*  Licensed under the Apache License, Version 2.0 (the "License");
```

* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
*
*/

Found in path(s):
* /resilience4j-circuitbreaker-1-7-1-sources-2-
jar/io/github/resilience4j/circuitbreaker/internal/CircuitBreakerMetrics.java
No license file was found, but licenses were detected in source scan.

/*
*
* Copyright 2018: Clint Checketts
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
*
*/

Found in path(s):
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/internal/package-info.java
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/event/package-info.java
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/package-info.java
No license file was found, but licenses were detected in source scan.

/*
*
* Copyright 2019 Robert Winkler
*

```
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*        http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*
*
*/
```

Found in path(s):
* /resilience4j-circuitbreaker-1-7-1-sources-2-jar/io/github/resilience4j/circuitbreaker/internal/CircuitBreakerStateMachine.java

1.992 resilience4j-core 1.7.1

1.992.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2019 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/lang/NonNullFields.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/lang/NonNull.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/lang/Nullable.java
No license file was found, but licenses were detected in source scan.

```
/*
```

```
*
*  Copyright 2019 Mahmoud Romeh
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*        http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*
*
*/
```

Found in path(s):
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/ConfigurationNotFoundException.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2019 Ingyu Hwang
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*       http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/metrics/MetricsPublisher.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/registry/RegistryEventConsumer.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/registry/CompositeRegistryEventConsumer.java
No license file was found, but licenses were detected in source scan.

```
/*
*
*  Copyright 2018: Clint Checketts
*
```

```
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*        http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*
*
*/
```

Found in path(s):
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/package-info.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/registry/package-info.java
No license file was found, but licenses were detected in source scan.

```
/*
*
*  Copyright 2017: Robert Winkler
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*        http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*
*
*/
```

Found in path(s):
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/EventConsumer.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/EventPublisher.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/EventProcessor.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/StopWatch.java
No license file was found, but licenses were detected in source scan.

```
/*
*
```

```
*  Copyright 2020: Robert Winkler
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*        http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*
*
*/
```

Found in path(s):
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/exception/AcquirePermissionCancelledException.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/CallableUtils.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/SupplierUtils.java
*
 /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/StringUtils.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/CheckFunctionUtils.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/ClassUtils.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/CompletionStageUtils.java
No license file was found, but licenses were detected in source scan.

```
/*
*
*  Copyright 2019: Robert Winkler
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*        http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*
*
*/
```

Found in path(s):
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/registry/EntryReplacedEvent.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/registry/RegistryEvent.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/registry/AbstractRegistryEvent.java
*
/resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/registry/EntryAddedEvent.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/registry/EntryRemovedEvent.java
No license file was found, but licenses were detected in source scan.

```
/*
*
*  Copyright 2020 krnsaurabh
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*        http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*
*
*/
```

Found in path(s):
* /resilience4j-core-1-7-1-sources-2-
jar/io/github/resilience4j/core/ContextAwareScheduledThreadPoolExecutor.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/NamingThreadFactory.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/ContextPropagator.java
No license file was found, but licenses were detected in source scan.

```
/*
*
*  Copyright 2016 Robert Winkler and Bohdan Storozhuk
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*        http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
```

* See the License for the specific language governing permissions and
* limitations under the License.
*
*
*/

Found in path(s):
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/ResultUtils.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/lang/NonNullApi.java
No license file was found, but licenses were detected in source scan.

/*
*
* Copyright 2019 Robert Winkler and Bohdan Storozhuk
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
*
*/

Found in path(s):
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/metrics/SnapshotImpl.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/metrics/Snapshot.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/metrics/Measurement.java
*
/resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/metrics/PartialAggregation.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/metrics/SlidingTimeWindowMetrics.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/metrics/AbstractAggregation.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/metrics/Metrics.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/metrics/FixedSizeSlidingWindowMetrics.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/metrics/TotalAggregation.java
No license file was found, but licenses were detected in source scan.

/*
*
* Copyright 2019 Mahmoud Romeh, Robert Winkler
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
*
*/

Found in path(s):
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/registry/AbstractRegistry.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/Registry.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2020 KrnSaurabh
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/registry/InMemoryRegistryStore.java
* /resilience4j-core-1-7-1-sources-2-jar/io/github/resilience4j/core/RegistryStore.java

1.993 jaeger-thrift 0.28.0

1.993.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2016-2018, The Jaeger Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /jaeger-thrift-0-28-0-sources-jar/io/jaegertracing/thrift/senders/ThriftSenderBase.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2016, Uber Technologies, Inc
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.

*/

Found in path(s):
* /jaeger-thrift-0-28-0-sources-jar/io/jaegertracing/thrift/reporters/protocols/ThriftUdpTransport.java

1.994 jaeger-core 0.28.0

1.994.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2018, The Jaeger Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/PropagationRegistry.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2016, Uber Technologies, Inc
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/Constants.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/samplers/GuaranteedThroughputSampler.java

* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/utils/Http.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/exceptions/UnsupportedFormatException.java
*
 /jaeger-core-0-28-0-sources-jar/io/jaegertracing/senders/Sender.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/reporters/CompositeReporter.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/utils/RateLimiter.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/exceptions/EmptyTracerStateStringException.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/reporters/InMemoryReporter.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/exceptions/EmptyIpException.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/exceptions/SenderException.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/senders/UdpSender.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/senders/HttpSender.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/metrics/Timer.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/samplers/http/ProbabilisticSamplingStrategy.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/propagation/PrefixedKeys.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/reporters/LoggingReporter.java
*
 /jaeger-core-0-28-0-sources-jar/io/jaegertracing/samplers/http/OperationSamplingParameters.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/propagation/Injector.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/Tracer.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/samplers/RateLimitingSampler.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/samplers/PerOperationSampler.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/propagation/TextMapCodec.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/senders/ThriftSender.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/reporters/protocols/JaegerThriftSpanConverter.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/samplers/http/RateLimitingSamplingStrategy.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/Configuration.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/SpanContext.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/exceptions/NotFourOctetsException.java
*
 /jaeger-core-0-28-0-sources-jar/io/jaegertracing/utils/Utils.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/samplers/http/PerOperationSamplingParameters.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/metrics/Metric.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/samplers/ProbabilisticSampler.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/metrics/Tag.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/utils/SystemClock.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/utils/Clock.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/samplers/ConstSampler.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/exceptions/MalformedTracerStateStringException.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/samplers/Sampler.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/metrics/Metrics.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/samplers/HttpSamplingManager.java
*
 /jaeger-core-0-28-0-sources-jar/io/jaegertracing/samplers/RemoteControlledSampler.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/reporters/Reporter.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/samplers/SamplingStatus.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/metrics/Counter.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/metrics/Gauge.java

* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/samplers/http/SamplingStrategyResponse.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/exceptions/SamplingStrategyErrorException.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/Span.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/LogData.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/reporters/NoopReporter.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/samplers/SamplingManager.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/propagation/Extractor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2017, Uber Technologies, Inc
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/baggage/Restriction.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/baggage/http/BaggageRestrictionResponse.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/baggage/BaggageRestrictionManager.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/propagation/B3TextMapCodec.java
*
 /jaeger-core-0-28-0-sources-jar/io/jaegertracing/baggage/BaggageSetter.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/utils/Java6CompatibleThreadLocalRandom.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/Reference.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/exceptions/BaggageRestrictionManagerException.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/baggage/HttpBaggageRestrictionManagerProxy.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/baggage/BaggageRestrictionManagerProxy.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/propagation/HexCodec.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/baggage/RemoteBaggageRestrictionManager.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/baggage/DefaultBaggageRestrictionManager.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2016-2017, Uber Technologies, Inc
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0

*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/reporters/RemoteReporter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2017, The Jaeger Authors
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/metrics/NoopMetricsFactory.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/propagation/Codec.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/metrics/InMemoryMetricsFactory.java
* /jaeger-core-0-28-0-sources-jar/io/jaegertracing/metrics/MetricsFactory.java
*
 /jaeger-core-0-28-0-sources-jar/io/jaegertracing/propagation/CompositeCodec.java

1.995 jackson-datatype-hibernate 2.12.7

1.995.1 Available under license :

This copy of Jackson JSON processor streaming parser/generator is licensed under the
Apache (Software) License, version 2.0 ("the License").
See the License for details about distribution rights, and the
specific rights regarding derivate works.

You may obtain a copy of the License at:

http://www.apache.org/licenses/LICENSE-2.0

1.996 registry-auth-token 4.2.2

1.996.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 Espen Hovlandsdal

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.997 qs 6.11.0

1.997.1 Available under license :

BSD-3-Clause
BSD 3-Clause License

Copyright (c) 2014, Nathan LaFreniere and other [contributors](https://github.com/ljharb/qs/graphs/contributors)
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this
  list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice,
  this list of conditions and the following disclaimer in the documentation
  and/or other materials provided with the distribution.

3. Neither the name of the copyright holder nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.998 babel-plugin-proposal-nullish-coalescing-operator 7.18.6

1.998.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.999 @babel/plugin-proposal-json-strings 7.18.6

1.999.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1000 clone-response 1.0.3

1.1000.1 Available under license :

MIT License

Copyright (c) 2017 Luke Childs

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all

copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1001 @sinonjs/text-encoding 0.7.2

1.1001.1 Available under license :

UNRECOGNIZED LICENSE; MD5 sum: 8252786db873eea2568eaae90ed7b3f6
The encoding indexes, algorithms, and many comments in the code
derive from the Encoding Standard https://encoding.spec.whatwg.org/

Otherwise, the code of this repository is released under the Unlicense
license and is also dual-licensed under an Apache 2.0 license. Both
are included below.

Unlicense

This is free and unencumbered software released into the public domain.

Anyone is free to copy, modify, publish, use, compile, sell, or
distribute this software, either in source code form or as a compiled
binary, for any purpose, commercial or non-commercial, and by any
means.

In jurisdictions that recognize copyright laws, the author or authors
of this software dedicate any and all copyright interest in the
software to the public domain. We make this dedication for the benefit
of the public at large and to the detriment of our heirs and
successors. We intend this dedication to be an overt act of
relinquishment in perpetuity of all present and future rights to this
software under copyright
law.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS BE LIABLE FOR ANY CLAIM, DAMAGES OR
OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR

OTHER DEALINGS IN THE SOFTWARE.

For more information, please refer to <http://unlicense.org/>

Apache 2.0 License

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the

editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate

as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain,
in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions

of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE.
You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty
or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!)
The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1002 es5-ext 0.10.62

1.1002.1 Available under license :

MIT
MIT License

Copyright (c) Microsoft Corporation.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF
CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE

1.1003 type 2.7.2

1.1003.1 Available under license :

ISC License

Copyright (c) 2019-2022, Mariusz Nowak, @medikoo, medikoo.com

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1004 object.assign 4.1.4

1.1004.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1005 jackson-annotations 2.12.7

1.1005.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or

Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You

institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use,

reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1006 jackson-dataformat-yaml 2.12.7

1.1006.1 Available under license :

This copy of Jackson JSON processor YAML module is licensed under the
Apache (Software) License, version 2.0 ("the License").
See the License for details about distribution rights, and the
specific rights regarding derivate works.

You may obtain a copy of the License at:

http://www.apache.org/licenses/LICENSE-2.0
Jackson JSON processor

Jackson is a high-performance, Free/Open Source JSON processing library.
It was originally written by Tatu Saloranta (tatu.saloranta@iki.fi), and has
been in development since 2007.
It is currently developed by a community of developers, as well as supported

commercially by FasterXML.com.

Licensing

Jackson core and extension components may be licensed under different licenses.
To find the details that apply to this artifact see the accompanying LICENSE file.
For more information, including possible other licensing options, contact
FasterXML.com (http://fasterxml.com).

Credits

A list of contributors may be found from CREDITS file, which is included
in some artifacts (usually source distributions); but is always available
from the source code management (SCM) system project uses.

1.1007 jackson-dataformat-smile 2.12.7

1.1007.1 Available under license :

No license file was found, but licenses were detected in source scan.

Copyright 2012 FasterXML.com
#
Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at
#
http://www.apache.org/licenses/LICENSE-2.0
#
Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

com.fasterxml.jackson.dataformat.smile.SmileFactory

Found in path(s):
* /jackson-dataformat-smile-2-12-7-sources-jar/META-INF/services/com.fasterxml.jackson.core.JsonFactory

1.1008 jackson-jaxrs 2.12.7

1.1008.1 Available under license :

This copy of Jackson JSON processor databind module is licensed under the
Apache (Software) License, version 2.0 ("the License").
See the License for details about distribution rights, and the
specific rights regarding derivate works.

You may obtain a copy of the License at:

http://www.apache.org/licenses/LICENSE-2.0
Jackson JSON processor

Jackson is a high-performance, Free/Open Source JSON processing library.
It was originally written by Tatu Saloranta (tatu.saloranta@iki.fi), and has
been in development since 2007.
It is currently developed by a community of developers, as well as supported
commercially by FasterXML.com.

Licensing

Jackson core and extension components may be licensed under different licenses.
To find the details that apply to this artifact see the accompanying LICENSE file.
For more information, including possible other licensing options, contact
FasterXML.com (http://fasterxml.com).

Credits

A list of contributors may be found from CREDITS file, which is included
in some artifacts (usually source distributions); but is always available
from the source code management (SCM) system project uses.

1.1009 jackson-dataformat-xml 2.12.7

1.1009.1 Available under license :

This copy of Jackson JSON processor databind module is licensed under the
Apache (Software) License, version 2.0 ("the License").
See the License for details about distribution rights, and the
specific rights regarding derivate works.

You may obtain a copy of the License at:

http://www.apache.org/licenses/LICENSE-2.0
Jackson JSON processor

Jackson is a high-performance, Free/Open Source JSON processing library.
It was originally written by Tatu Saloranta (tatu.saloranta@iki.fi), and has
been in development since 2007.
It is currently developed by a community of developers, as well as supported
commercially by FasterXML.com.

Licensing

Jackson core and extension components may be licensed under different licenses.

To find the details that apply to this artifact see the accompanying LICENSE file.
For more information, including possible other licensing options, contact
FasterXML.com (http://fasterxml.com).

Credits

A list of contributors may be found from CREDITS file, which is included
in some artifacts (usually source distributions); but is always available
from the source code management (SCM) system project uses.

1.1010 jackson-module-jsonschema 2.12.7

1.1010.1 Available under license :

This copy of Jackson JSON processor databind module is licensed under the
Apache (Software) License, version 2.0 ("the License").
See the License for details about distribution rights, and the
specific rights regarding derivate works.

You may obtain a copy of the License at:

http://www.apache.org/licenses/LICENSE-2.0

1.1011 jackson-xc 2.12.7

1.1011.1 Available under license :

Jackson JSON processor

Jackson is a high-performance, Free/Open Source JSON processing library.
It was originally written by Tatu Saloranta (tatu.saloranta@iki.fi), and has
been in development since 2007.
It is currently developed by a community of developers, as well as supported
commercially by FasterXML.com.

Licensing

Jackson core and extension components may licensed under different licenses.
To find the details that apply to this artifact see the accompanying LICENSE file.
For more information, including possible other licensing options, contact
FasterXML.com (http://fasterxml.com).

Credits

A list of contributors may be found from CREDITS file, which is included
in some artifacts (usually source distributions); but is always available
from the source code management (SCM) system project uses.

This copy of Jackson JSON processor `jackson-module-jaxb-annotations` module is licensed under the
Apache (Software) License, version 2.0 ("the License").
See the License for details about distribution rights, and the
specific rights regarding derivate works.

You may obtain a copy of the License at:

http://www.apache.org/licenses/LICENSE-2.0

1.1012 jackson-jaxrs-base 2.12.7

1.1012.1 Available under license :

This copy of Jackson JSON processor databind module is licensed under the
Apache (Software) License, version 2.0 ("the License").
See the License for details about distribution rights, and the
specific rights regarding derivate works.

You may obtain a copy of the License at:

http://www.apache.org/licenses/LICENSE-2.0

1.1013 ext 1.7.0

1.1013.1 Available under license :

ISC
ISC License

Copyright (c) 2011-2022, Mariusz Nowak, @medikoo, medikoo.com

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.

1.1014 follow-redirects 1.15.2

1.1014.1 Available under license :

Copyright 2014present Olivier Lalonde <olalonde@gmail.com>, James Talmage <james@talmage.io>, Ruben Verborgh

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF
CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1015 regjsparser 0.9.1

1.1015.1 Available under license :

BSD-2-Clause
Copyright (c) Julian Viereck and Contributors, All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL <COPYRIGHT HOLDER> BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS
OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT

(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1016 unicode-property-aliases-ecmascript 2.1.0

1.1016.1 Available under license :

Copyright Mathias Bynens <https://mathiasbynens.be/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1017 spring-instrument 4.3.20.RELEASE

1.1017.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-instrument-4-3-20-release-sources-1-jar/org/springframework/instrument/InstrumentationSavingAgent.java

1.1018 logback-core 1.2.9

1.1018.1 Available under license :

No license file was found, but licenses were detected in source scan.

/**
* Logback: the reliable, generic, fast and flexible logging framework.
* Copyright (C) 1999-2015, QOS.ch. All rights reserved.
*
* This program and the accompanying materials are dual-licensed under
* either the terms of the Eclipse Public License v1.0 as published by
* the Eclipse Foundation
*
*   or (per the licensee's choosing)
*
* under the terms of the GNU Lesser General Public License version 2.1
* as published by the Free Software Foundation.
*/

Found in path(s):
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/FilterAttachableImpl.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/ConsoleAppender.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/ParamAction.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/status/OnConsoleStatusListener.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/CoreConstants.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ssl/SSLConfigurable.java
*
 /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/Duration.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/html/NOPThrowableRenderer.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/SimpleRuleStore.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/conditional/Condition.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/LayoutBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ssl/SSLContextFactoryBean.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/OutputStreamAppender.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/ForegroundCompositeConverterBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/AppenderAttachableImpl.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/status/StatusUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/TriggeringPolicyBase.java

*
 /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/LifeCycleManager.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/SizeBasedTriggeringPolicy.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/parser/Compiler.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/filter/EvaluatorFilter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/SystemInfo.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/ReplacingCompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/PostCompileProcessor.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/TimeBasedFileNamingAndTriggeringPolicy.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/TimeBasedRollingPolicy.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/ConfigurationWatchList.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/LogbackLock.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/ContextAware.java
*
 /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/IncompatibleClassException.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/parser/SimpleKeywordNode.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/boolex/EventEvaluatorBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/ActionUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/ANSIConstants.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/StatusListenerConfigHelper.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ssl/SSLConfiguration.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/sift/DefaultDiscriminator.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/ExecutorServiceUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/AbstractComponentTracker.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/filter/AbstractMatcherFilter.java
*
 /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/encoder/Encoder.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/LoginAuthenticator.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/ActionConst.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/QueueFactory.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/sift/AbstractAppenderFactoryUsingJoran.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/status/StatusBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/EnvUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/OptionHelper.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/PatternLayoutBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/layout/EchoLayout.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/CharSequenceState.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ssl/KeyStoreFactoryBean.java
*
 /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/status/OnPrintStreamStatusListenerBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/RedCompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/helper/PeriodicityType.java
* /logback-core-1-2-9-sources-1-
jar/ch/qos/logback/core/rolling/DefaultTimeBasedFileNamingAndTriggeringPolicy.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/subst/Tokenizer.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/LogbackException.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/BoldRedCompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/WhiteCompositeConverter.java

* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/FormattingConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/sift/Discriminator.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ssl/SSLConfigurableSocket.java
*
 /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/LifeCycle.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/util/AlmostAsIsEscapeUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/util/AsIsEscapeUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/BoldWhiteCompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/DefaultClass.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/encoder/NonClosableInputStream.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ObjectWriterFactory.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/CompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/IdentityCompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/helper/MonoTypedConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/DeferredProcessingAware.java
*
 /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/recovery/RecoveryCoordinator.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/hook/ShutdownHook.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/BasicStatusManager.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/SpacePadder.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/FileUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/recovery/ResilientSyslogOutputStream.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/DefaultNestedComponentRegistry.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/JoranConfiguratorBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/conditional/ThenAction.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/helper/FileStoreUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/FileSize.java
*
 /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/CachingDateFormatter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/CyclicBufferTracker.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/status/NopStatusListener.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/RollingPolicy.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/YellowCompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/html/CssBuilder.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/html/IThrowableRenderer.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/NestedBasicPropertyIA.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/event/StartEvent.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/filter/Filter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/NOPAction.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/DefaultInvocationGate.java
*
 /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/event/stax/StartEvent.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/ElementSelector.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/server/ServerListener.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/AbstractEventEvaluatorAction.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/conditional/ElseAction.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/AbstractSSLSocketAppender.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/AppenderRefAction.java

* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/helper/IntegerTokenConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/helper/TimeBasedArchiveRemover.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/subst/NodeToStringTransformer.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/EventPlayer.java
*
/logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/InterpretationContext.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ssl/SSLComponent.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/FormatInfo.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/GenericConfigurator.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/encoder/ByteArrayUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/StatusListenerAction.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/ConsoleTarget.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/MagentaCompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/property/FileExistsPropertyDefiner.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/DelayStrategy.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/helper/ArchiveRemover.java
*
/logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/parser/OptionTokenizer.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/node/ComponentNode.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/boolex/EvaluationException.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/BoldGreenCompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/BoldMagentaCompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/TimeUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/SMTPAppenderBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ssl/SSLConfigurableServerSocket.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/boolex/JaninoEventEvaluatorBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/util/StringToObjectConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/SyslogAppenderBase.java
*
/logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/server/RemoteReceiverServerRunner.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/NestedComplexPropertyIA.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/sift/AppenderTracker.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/SizeAndTimeBasedFNATP.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/FilterAttachable.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/AutoFlushingObjectWriter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/encoder/LayoutWrappingEncoder.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/server/Client.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/ContextAwareImpl.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/event/stax/StaxEvent.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/parser/CompositeNode.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/ScanException.java
*
/logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/status/StatusManager.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/parser/Node.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/ShutdownHookAction.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/parser/TokenStream.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/status/Status.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/helper/Compressor.java

* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/CyanCompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/event/stax/EndEvent.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/server/ServerSocketListener.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/helpers/NOPAppender.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/BlueCompositeConverter.java
*
/logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/status/OnErrorConsoleStatusListener.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/sift/AbstractDiscriminator.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/SyslogConstants.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/SyslogOutputStream.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/JNDIUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/parser/FormattingNode.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/subst/Token.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/boolex/Matcher.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/NoAutoStart.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/FixedDelay.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/subst/Parser.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/GreenCompositeConverter.java
*
/logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ssl/SSLParametersConfiguration.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/encoder/EchoEncoder.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/RolloverFailure.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/LocationUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/Context.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/helper/FileNamePattern.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/PropertyAction.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/AbstractSocketAppender.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/DatePatternToRegexUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/encoder/EncoderBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/conditional/PropertyEvalScriptBuilder.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/IADataForComplexProperty.java
*
/logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/RollingFileAppender.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/helper/FileFilterUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/event/EndEvent.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/event/SaxEventRecorder.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/helper/CompressionMode.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/AppenderAttachable.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/helper/RollingCalendar.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/HostClassAndPropertyDouble.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/server/AbstractServerSocketAppender.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/helper/DateTokenConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/ImplicitAction.java
*
/logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/event/stax/StaxEventRecorder.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/parser/Token.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/helper/SizeAndTimeBasedArchiveRemover.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/AppenderAction.java

* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/StatusPrinter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/BlackCompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/server/ConcurrentServerRunner.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/status/StatusListener.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/Interpreter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ssl/SSL.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/util/RegularEscapeUtil.java
*
/logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/FixedWindowRollingPolicy.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/helpers/CyclicBuffer.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/server/ServerRunner.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/Loader.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/TriggeringPolicy.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/FileAppender.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/server/SSLServerSocketAppenderBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/AsyncAppenderBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/hook/DelayingShutdownHook.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/PropertySetterException.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/server/RemoteReceiverStreamClient.java
*
/logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ssl/TrustManagerFactoryFactoryBean.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/AppenderBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/IADataForBasicProperty.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/PreSerializationTransformer.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/ActionException.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/LiteralConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/DynamicConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/helpers/Transform.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/IncludeAction.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/JoranException.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ssl/KeyManagerFactoryFactoryBean.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/ContextAwareBase.java
*
/logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/ContentTypeUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/CloseUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/status/WarnStatus.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/Action.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/Appender.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/property/ResourceExistsPropertyDefiner.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/status/InfoStatus.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/Converter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/ConverterUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/recovery/ResilientOutputStreamBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ssl/SSLNestedComponentRegistryRules.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/recovery/ResilientFileOutputStream.java
*
/logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/PropertyDefiner.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/status/StatusListenerAsList.java

* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/status/ViewStatusMessagesServletBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/StringCollectionUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/parser/Parser.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/RollingPolicyBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ObjectWriter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/conditional/PropertyWrapperForScripts.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/helper/TokenConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/ContextUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/conditional/ThenOrElseActionBase.java
*
 /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/event/BodyEvent.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/read/ListAppender.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/ConversionRuleAction.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/RuleStore.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/DefaultSocketConnector.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ssl/ConfigurableSSLServerSocketFactory.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ssl/ConfigurableSSLSocketFactory.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/ssl/SecureRandomFactoryBean.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/NewRuleAction.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/util/IEscapeUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/FilterReply.java
*
 /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/ContextPropertyAction.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/PropertyContainer.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/SocketConnector.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/BoldBlueCompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/subst/Node.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/TimestampAction.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/boolex/EventEvaluator.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/event/SaxEvent.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/server/RemoteReceiverServerListener.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/DynamicClassLoadingException.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/util/ConfigurationWatchListUtil.java
*
 /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/PropertyDefinerBase.java
* /logback-core-1-2-9-sources-1-
jar/ch/qos/logback/core/rolling/TimeBasedFileNamingAndTriggeringPolicyBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/html/HTMLLayoutBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/util/RestrictedEscapeUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/helpers/ThrowableToStringArray.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/BoldCyanCompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/NoAutoStartUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/ElementPath.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/GrayCompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/conditional/IfAction.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/CharSequenceToRegexMapper.java
*

/logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/util/PropertySetter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/read/CyclicBufferAppender.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/UnsynchronizedAppenderBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/event/stax/BodyEvent.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/color/BoldYellowCompositeConverter.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/rolling/helper/RenameUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/ContextBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/Layout.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/util/AggregationType.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/spi/XMLUtil.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/sift/SiftingJoranConfiguratorBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/status/ErrorStatus.java
*
/logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/server/RemoteReceiverClient.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/pattern/PatternLayoutEncoderBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/action/DefinePropertyAction.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/joran/event/InPlayListener.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/net/server/ClientVisitor.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/sift/AppenderFactory.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/spi/ComponentTracker.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/hook/ShutdownHookBase.java
* /logback-core-1-2-9-sources-1-jar/ch/qos/logback/core/sift/SiftingAppenderBase.java

1.1019 logback-classic 1.2.9

1.1019.1 Available under license :

No license file was found, but licenses were detected in source scan.

Logback: the reliable, generic, fast and flexible logging framework.
Copyright (C) 1999-2010, QOS.ch. All rights reserved.
#
See http://logback.qos.ch/license.html for the applicable licensing
conditions.

This SQL script creates the required tables by ch.qos.logback.classic.db.DBAppender.
#
It is intended for HSQL databases. It has been tested on HSQL 1.8.07.

DROP TABLE logging_event_exception IF EXISTS;
DROP TABLE logging_event_property IF EXISTS;
DROP TABLE logging_event IF EXISTS;

CREATE TABLE logging_event (
 timestmp BIGINT NOT NULL,
 formatted_message LONGVARCHAR NOT NULL,
 logger_name VARCHAR(256) NOT NULL,

```
 level_string VARCHAR(256) NOT NULL,
 thread_name VARCHAR(256),
 reference_flag SMALLINT,
 arg0 VARCHAR(256),
 arg1 VARCHAR(256),
 arg2 VARCHAR(256),
 arg3 VARCHAR(256),
 caller_filename VARCHAR(256),
 caller_class VARCHAR(256),
 caller_method VARCHAR(256),
 caller_line CHAR(4),
  event_id BIGINT NOT NULL IDENTITY);


CREATE TABLE logging_event_property (
 event_id BIGINT NOT NULL,
 mapped_key  VARCHAR(254) NOT NULL,
 mapped_value LONGVARCHAR,
 PRIMARY KEY(event_id, mapped_key),
 FOREIGN KEY (event_id) REFERENCES logging_event(event_id));

CREATE TABLE logging_event_exception (
 event_id BIGINT NOT NULL,
 i SMALLINT NOT NULL,
 trace_line VARCHAR(256) NOT NULL,
 PRIMARY KEY(event_id, i),
 FOREIGN KEY (event_id) REFERENCES logging_event(event_id));

Found in path(s):
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/db/script/hsqldb.sql
No license file was found, but licenses were detected in source scan.

# Logback: the reliable, generic, fast and flexible logging framework.
# Copyright (C) 1999-2010, QOS.ch. All rights reserved.
#
# See http://logback.qos.ch/license.html for the applicable licensing
# conditions.

# This SQL script creates the required tables by ch.qos.logback.classic.db.DBAppender
#
# It is intended for IBM DB2 databases.
#
# WARNING  WARNING WARNING  WARNING
# ================================
# This SQL script has not been tested on an actual DB2
# instance. It may contain errors or even invalid SQL
# statements.
```

```
DROP TABLE  logging_event_property;
DROP TABLE  logging_event_exception;
DROP TABLE  logging_event;

CREATE TABLE logging_event
 (
  timestmp         BIGINT NOT NULL,
  formatted_message VARCHAR(4000) NOT NULL,
  logger_name       VARCHAR(254) NOT NULL,
  level_string      VARCHAR(254) NOT NULL,
  thread_name       VARCHAR(254),
  reference_flag    SMALLINT,
  arg0
        VARCHAR(254),
  arg1              VARCHAR(254),
  arg2              VARCHAR(254),
  arg3              VARCHAR(254),
  caller_filename   VARCHAR(254) NOT NULL,
  caller_class      VARCHAR(254) NOT NULL,
  caller_method     VARCHAR(254) NOT NULL,
  caller_line       CHAR(4) NOT NULL,
  event_id          INTEGER GENERATED ALWAYS AS IDENTITY (START WITH 1)
 );

CREATE TABLE logging_event_property
 (
  event_id      INTEGER NOT NULL,
  mapped_key        VARCHAR(254) NOT NULL,
  mapped_value      VARCHAR(1024),
  PRIMARY KEY(event_id, mapped_key),
  FOREIGN KEY (event_id) REFERENCES logging_event(event_id)
 );

CREATE TABLE logging_event_exception
 (
  event_id        INTEGER NOT NULL,
  i               SMALLINT NOT NULL,
  trace_line      VARCHAR(254) NOT NULL,
  PRIMARY KEY(event_id, i),
  FOREIGN KEY (event_id) REFERENCES logging_event(event_id)
 );

Found in path(s):
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/db/script/db2.sql
No license file was found, but licenses were detected in source scan.

--# Logback: the reliable, generic, fast and flexible logging framework.
--# Copyright (C) 1999-2012, QOS.ch. All rights reserved.
```

```
--#
--# See http://logback.qos.ch/license.html for the applicable licensing
--# conditions.
--#
--# This SQL script creates the required tables by ch.qos.logback.classic.db.DBAppender.
--#
--# It is intended for SQLite3 databases. It has been tested on SQLite 3.7.4
--# on Android ICS (4.0.3).


BEGIN;
DROP TABLE IF EXISTS logging_event_property;
DROP TABLE IF EXISTS logging_event_exception;
DROP TABLE IF EXISTS logging_event;
COMMIT;


BEGIN;
CREATE TABLE logging_event
(
  timestmp         BIGINT NOT NULL,
  formatted_message  TEXT NOT NULL,
  logger_name       VARCHAR(254) NOT NULL,
  level_string      VARCHAR(254) NOT NULL,
  thread_name       VARCHAR(254),
  reference_flag    SMALLINT,
  arg0              VARCHAR(254),
  arg1              VARCHAR(254),
  arg2
      VARCHAR(254),
  arg3              VARCHAR(254),
  caller_filename   VARCHAR(254) NOT NULL,
  caller_class      VARCHAR(254) NOT NULL,
  caller_method     VARCHAR(254) NOT NULL,
  caller_line       CHAR(4) NOT NULL,
  event_id          INTEGER NOT NULL PRIMARY KEY AUTOINCREMENT
);
COMMIT;

BEGIN;
CREATE TABLE logging_event_property
(
  event_id       BIGINT NOT NULL,
  mapped_key        VARCHAR(254) NOT NULL,
  mapped_value      TEXT,
  PRIMARY KEY(event_id, mapped_key),
  FOREIGN KEY (event_id) REFERENCES logging_event(event_id)
);
```

```
COMMIT;

BEGIN;
CREATE TABLE logging_event_exception
(
  event_id        BIGINT NOT NULL,
  i               SMALLINT NOT NULL,
  trace_line      VARCHAR(254) NOT NULL,
  PRIMARY KEY(event_id, i),
  FOREIGN KEY (event_id) REFERENCES logging_event(event_id)
);
COMMIT;
```

Found in path(s):
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/db/script/sqllite.sql
No license file was found, but licenses were detected in source scan.

```
# Logback: the reliable, generic, fast and flexible logging framework.
# Copyright (C) 1999-2010, QOS.ch. All rights reserved.
#
# See http://logback.qos.ch/license.html for the applicable licensing
# conditions.

# This SQL script creates the required tables by ch.qos.logback.classic.db.DBAppender.
#
# It is intended for MySQL databases. It has been tested on MySQL 5.1.37
# on Linux


BEGIN;
DROP TABLE IF EXISTS logging_event_property;
DROP TABLE IF EXISTS logging_event_exception;
DROP TABLE IF EXISTS logging_event;
COMMIT;


BEGIN;
CREATE TABLE logging_event
(
  timestmp        BIGINT NOT NULL,
  formatted_message  TEXT NOT NULL,
  logger_name       VARCHAR(254) NOT NULL,
  level_string      VARCHAR(254) NOT NULL,
  thread_name       VARCHAR(254),
  reference_flag    SMALLINT,
  arg0              VARCHAR(254),
  arg1              VARCHAR(254),
  arg2              VARCHAR(254),
```

```
  arg3
      VARCHAR(254),
  caller_filename   VARCHAR(254) NOT NULL,
  caller_class      VARCHAR(254) NOT NULL,
  caller_method     VARCHAR(254) NOT NULL,
  caller_line       CHAR(4) NOT NULL,
  event_id          BIGINT NOT NULL AUTO_INCREMENT PRIMARY KEY
 );
COMMIT;

BEGIN;
CREATE TABLE logging_event_property
 (
  event_id       BIGINT NOT NULL,
  mapped_key        VARCHAR(254) NOT NULL,
  mapped_value      TEXT,
  PRIMARY KEY(event_id, mapped_key),
  FOREIGN KEY (event_id) REFERENCES logging_event(event_id)
 );
COMMIT;

BEGIN;
CREATE TABLE logging_event_exception
 (
  event_id        BIGINT NOT NULL,
  i               SMALLINT NOT NULL,
  trace_line      VARCHAR(254) NOT NULL,
  PRIMARY KEY(event_id, i),
  FOREIGN KEY (event_id) REFERENCES logging_event(event_id)
 );
COMMIT;

Found in path(s):
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/db/script/mysql.sql
No license file was found, but licenses were detected in source scan.

-- Logback: the reliable, generic, fast and flexible logging framework.
-- Copyright (C) 1999-2010, QOS.ch. All rights reserved.
--
-- See http://logback.qos.ch/license.html for the applicable licensing
-- conditions.

-- This SQL script creates the required tables by ch.qos.logback.classic.db.DBAppender
--
-- The event_id column type was recently changed from INT to DECIMAL(40)
-- without testing.

DROP TABLE logging_event_property
```

```
DROP TABLE logging_event_exception
DROP TABLE logging_event

CREATE TABLE logging_event
(
  timestmp         DECIMAL(20) NOT NULL,
  formatted_message  VARCHAR(4000) NOT NULL,
  logger_name       VARCHAR(254) NOT NULL,
  level_string      VARCHAR(254) NOT NULL,
  thread_name       VARCHAR(254),
  reference_flag    SMALLINT,
  arg0              VARCHAR(254),
  arg1              VARCHAR(254),
  arg2              VARCHAR(254),
  arg3              VARCHAR(254),

  caller_filename   VARCHAR(254) NOT NULL,
  caller_class      VARCHAR(254) NOT NULL,
  caller_method     VARCHAR(254) NOT NULL,
  caller_line       CHAR(4) NOT NULL,
  event_id          DECIMAL(40) NOT NULL identity,
  PRIMARY KEY(event_id)
)

CREATE TABLE logging_event_property
(
  event_id          DECIMAL(40) NOT NULL,
  mapped_key        VARCHAR(254) NOT NULL,
  mapped_value      VARCHAR(1024),
  PRIMARY KEY(event_id, mapped_key),
  FOREIGN KEY (event_id) REFERENCES logging_event(event_id)
)

CREATE TABLE logging_event_exception
(
  event_id         DECIMAL(40) NOT NULL,
  i                SMALLINT NOT NULL,
  trace_line       VARCHAR(254) NOT NULL,
  PRIMARY KEY(event_id, i),
  FOREIGN KEY (event_id) REFERENCES logging_event(event_id)
)
```

Found in path(s):
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/db/script/mssql.sql
No license file was found, but licenses were detected in source scan.

```
/**
* Logback: the reliable, generic, fast and flexible logging framework.
```

* Copyright (C) 1999-2016, QOS.ch. All rights reserved.
*
* This program and the accompanying materials are dual-licensed under
* either the terms of the Eclipse Public License v1.0 as published by
* the Eclipse Foundation
*
*   or (per the licensee's choosing)
*
* under the terms of the GNU Lesser General Public License version 2.1
* as published by the Free Software Foundation.
*/

Found in path(s):
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/jmx/JMXConfigurator.java
No license file was found, but licenses were detected in source scan.

/**
* Logback: the reliable, generic, fast and flexible logging framework.
* Copyright (C) 1999-2021, QOS.ch. All rights reserved.
*
* This program and the accompanying materials are dual-licensed under
* either the terms of the Eclipse Public License v1.0 as published by
* the Eclipse Foundation
*
*   or (per the licensee's choosing)
*
* under the terms of the GNU Lesser General Public License version 2.1
* as published by the Free Software Foundation.
*/

Found in path(s):
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/PrefixCompositeConverter.java
No license file was found, but licenses were detected in source scan.

-- Logback: the reliable, generic, fast and flexible logging framework.
-- Copyright (C) 1999-2010, QOS.ch. All rights reserved.
--
-- See http://logback.qos.ch/license.html for the applicable licensing
-- conditions.

-- This SQL script creates the required tables by ch.qos.logback.classic.db.DBAppender
--
-- It is intended for Oracle 9i, 10g and 11g databases. Tested on version 9.2,
-- 10g and 11g.

-- The following lines are useful in cleaning any previously existing tables

```
--drop TRIGGER logging_event_id_seq_trig;
--drop SEQUENCE logging_event_id_seq;
--drop table logging_event_property;
--drop table logging_event_exception;
--drop table logging_event;


CREATE SEQUENCE logging_event_id_seq MINVALUE 1 START WITH 1;

CREATE TABLE logging_event
 (
   timestmp         NUMBER(20) NOT NULL,
   formatted_message  VARCHAR2(4000) NOT NULL,
   logger_name       VARCHAR(254) NOT NULL,
   level_string      VARCHAR(254)
 NOT NULL,
   thread_name       VARCHAR(254),
   reference_flag    SMALLINT,
   arg0              VARCHAR(254),
   arg1              VARCHAR(254),
   arg2              VARCHAR(254),
   arg3              VARCHAR(254),
   caller_filename   VARCHAR(254) NOT NULL,
   caller_class      VARCHAR(254) NOT NULL,
   caller_method     VARCHAR(254) NOT NULL,
   caller_line       CHAR(4) NOT NULL,
   event_id          NUMBER(10) PRIMARY KEY
 );


-- the / suffix may or may not be needed depending on your SQL Client
-- Some SQL Clients, e.g. SQuirrel SQL has trouble with the following
-- trigger creation command, while SQLPlus (the basic SQL Client which
-- ships with Oracle) has no trouble at all.

CREATE TRIGGER logging_event_id_seq_trig
 BEFORE INSERT ON logging_event
 FOR EACH ROW
 BEGIN
   SELECT logging_event_id_seq.NEXTVAL
   INTO   :NEW.event_id
   FROM   DUAL;
 END;
/


CREATE TABLE logging_event_property
 (
```

```
  event_id       NUMBER(10) NOT NULL,

 mapped_key        VARCHAR2(254) NOT NULL,
  mapped_value      VARCHAR2(1024),
  PRIMARY KEY(event_id, mapped_key),
  FOREIGN KEY (event_id) REFERENCES logging_event(event_id)
);

CREATE TABLE logging_event_exception
(
  event_id        NUMBER(10) NOT NULL,
  i               SMALLINT NOT NULL,
  trace_line      VARCHAR2(254) NOT NULL,
  PRIMARY KEY(event_id, i),
  FOREIGN KEY (event_id) REFERENCES logging_event(event_id)
);
```

Found in path(s):
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/db/script/oracle.sql
No license file was found, but licenses were detected in source scan.

```
-- Logback: the reliable, generic, fast and flexible logging framework.
-- Copyright (C) 1999-2010, QOS.ch. All rights reserved.
--
-- See http://logback.qos.ch/license.html for the applicable licensing
-- conditions.

-- This SQL script creates the required tables by ch.qos.logback.classic.db.DBAppender
-- for Sybase SQLAnywhere.  Tested on SQLAnywhere 10.0.1.

DROP TABLE logging_event_property
DROP TABLE logging_event_exception
DROP TABLE logging_event

CREATE TABLE logging_event
(
 timestmp         bigint NOT NULL,
 formatted_message  LONG VARCHAR NOT NULL,
 logger_name       VARCHAR(254) NOT NULL,
 level_string      VARCHAR(254) NOT NULL,
 thread_name       VARCHAR(254),
 reference_flag    SMALLINT,
 arg0              VARCHAR(254),
 arg1              VARCHAR(254),
 arg2              VARCHAR(254),
 arg3              VARCHAR(254),
 caller_filename   VARCHAR(254) NOT NULL,
 caller_class      VARCHAR(254)
```

```
 NOT NULL,
 caller_method     VARCHAR(254) NOT NULL,
 caller_line       varCHAR(4) NOT NULL,
 event_id          int NOT NULL DEFAULT AUTOINCREMENT,
 PRIMARY KEY(event_id)
)

CREATE TABLE logging_event_property
 (
 event_id          int NOT NULL REFERENCES logging_event(event_id),
 mapped_key        VARCHAR(254) NOT NULL,
 mapped_value      LONG VARCHAR,
 PRIMARY KEY(event_id, mapped_key)
 )

CREATE TABLE logging_event_exception
 (
 event_id         int NOT NULL REFERENCES logging_event(event_id) ,
 i                SMALLINT NOT NULL,
 trace_line       VARCHAR(254) NOT NULL,
 PRIMARY KEY(event_id, i)
 )
```

Found in path(s):
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/db/script/sybaseSqlAnywhere.sql
No license file was found, but licenses were detected in source scan.

```
-- Logback: the reliable, generic, fast and flexible logging framework.
-- Copyright (C) 1999-2010, QOS.ch. All rights reserved.
--
-- See http://logback.qos.ch/license.html for the applicable licensing
-- conditions.

-- This SQL script creates the required tables by ch.qos.logback.classic.db.DBAppender
--
-- It is intended for PostgreSQL databases.

DROP TABLE    logging_event_property;
DROP TABLE    logging_event_exception;
DROP TABLE    logging_event;
DROP SEQUENCE logging_event_id_seq;


CREATE SEQUENCE logging_event_id_seq MINVALUE 1 START 1;


CREATE TABLE logging_event
 (
```

```
  timestmp         BIGINT NOT NULL,
  formatted_message  TEXT NOT NULL,
  logger_name       VARCHAR(254) NOT NULL,
  level_string      VARCHAR(254) NOT NULL,
  thread_name       VARCHAR(254),
  reference_flag    SMALLINT,
  arg0              VARCHAR(254),
  arg1              VARCHAR(254),
  arg2              VARCHAR(254),
   arg3              VARCHAR(254),
  caller_filename   VARCHAR(254) NOT NULL,
  caller_class      VARCHAR(254) NOT NULL,
  caller_method     VARCHAR(254) NOT NULL,
  caller_line       CHAR(4) NOT NULL,
  event_id          BIGINT DEFAULT nextval('logging_event_id_seq') PRIMARY KEY
 );

CREATE TABLE logging_event_property
 (
  event_id       BIGINT NOT NULL,
  mapped_key        VARCHAR(254) NOT NULL,
  mapped_value      VARCHAR(1024),
  PRIMARY KEY(event_id, mapped_key),
  FOREIGN KEY (event_id) REFERENCES logging_event(event_id)
 );

CREATE TABLE logging_event_exception
 (
  event_id         BIGINT NOT NULL,
  i                SMALLINT NOT NULL,
  trace_line       VARCHAR(254) NOT NULL,
  PRIMARY KEY(event_id, i),
  FOREIGN KEY (event_id) REFERENCES logging_event(event_id)
 );
```

Found in path(s):
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/db/script/postgresql.sql
No license file was found, but licenses were detected in source scan.

```
/**
* Logback: the reliable, generic, fast and flexible logging framework.
* Copyright (C) 1999-2015, QOS.ch. All rights reserved.
*
* This program and the accompanying materials are dual-licensed under
* either the terms of the Eclipse Public License v1.0 as published by
* the Eclipse Foundation
*
*   or (per the licensee's choosing)
```

*
* under the terms of the GNU Lesser General Public License version 2.1
* as published by the Free Software Foundation.
*/

Found in path(s):
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/ThrowableProxyConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/html/UrlCssBuilder.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/LoggingEventPreSerializationTransformer.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/sift/SiftAction.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/ThreadConverter.java
*
 /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/joran/action/LoggerContextListenerAction.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/helpers/MDCInsertingServletFilter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/Level.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/sift/AppenderFactoryUsingJoran.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/EnsureExceptionHandling.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/LineOfCallerConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/ContextNameConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/jul/LevelChangePropagator.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/ThrowableProxyVO.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/sift/SiftingJoranConfigurator.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/joran/action/ConfigurationAction.java
*
 /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/sift/MDCBasedDiscriminator.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/turbo/TurboFilter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/LoggerRemoteView.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/SimpleSocketServer.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/server/RemoteAppenderServerRunner.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/SocketNode.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/selector/servlet/ContextDetachingSCL.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/joran/action/LoggerAction.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/server/RemoteAppenderServerListener.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/turbo/ReconfigureOnChangeFilter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/boolex/OnErrorEvaluator.java
*
 /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/LoggingEvent.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/selector/DefaultContextSelector.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/filter/ThresholdFilter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/sift/SiftingAppender.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/PackagingDataCalculator.java
* /logback-classic-1-2-9-sources-jar/org/slf4j/impl/StaticLoggerBinder.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/filter/LevelFilter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/SSLSocketAppender.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/selector/servlet/LoggerContextFilter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/server/ServerSocketAppender.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/FileOfCallerConverter.java
*

/logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/StackTraceElementProxy.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/LoggerContextAware.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/TargetLengthBasedClassNameAbbreviator.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/CallerData.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/turbo/DynamicThresholdFilter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/joran/action/ConsolePluginAction.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/db/names/ColumnName.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/AsyncAppender.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/IThrowableProxy.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/db/names/DBNameResolver.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/MarkerConverter.java
*
/logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/ViewStatusMessagesServlet.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/STEUtil.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/ExtendedThrowableProxyConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/ILoggingEvent.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/html/DefaultCssBuilder.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/db/names/DefaultDBNameResolver.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/joran/action/RootLoggerAction.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/sift/JNDIBasedContextDiscriminator.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/LoggerComparator.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/SMTPAppender.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/RelativeTimeConverter.java
*
/logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/MDCConverter.java
* /logback-classic-1-2-9-sources-jar/org/slf4j/impl/StaticMarkerBinder.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/RootCauseFirstThrowableProxyConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/turbo/DuplicateMessageFilter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/server/ServerSocketReceiver.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/jmx/MBeanUtil.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/db/names/TableName.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/sift/ContextBasedDiscriminator.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/LoggerContextAwareBase.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/util/CopyOnInheritThreadLocal.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/SocketAppender.java
*
/logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/html/DefaultThrowableRenderer.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/turbo/LRUMessageCache.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/LineSeparatorConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/Util.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/selector/ContextJNDISelector.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/SimpleSSLSocketServer.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/Configurator.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/util/LevelToSyslogSeverity.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/html/HTMLLayout.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/LoggerContext.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/NamedConverter.java
*

/logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/LoggerContextListener.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/util/DefaultNestedComponentRules.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/util/ContextSelectorStaticBinder.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/Abbreviator.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/turbo/MarkerFilter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/CallerDataConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/selector/ContextSelector.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/SocketAcceptor.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/server/RemoteAppenderClient.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/turbo/MDCValueLevelPair.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/ThrowableProxy.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/joran/action/LevelAction.java
*
/logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/EventArgUtil.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/ClassNameOnlyAbbreviator.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/turbo/MatchingFilter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/DateConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/Logger.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/joran/JoranConfigurator.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/ClassOfCallerConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/joran/action/ReceiverAction.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/turbo/MDCFilter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/ReceiverBase.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/joran/action/JMXConfiguratorAction.java
*
/logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/util/LoggerNameUtil.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/color/HighlightingCompositeConverter.java
* /logback-classic-1-2-9-sources-jar/org/slf4j/impl/StaticMDCBinder.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/LevelConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/boolex/IEvaluator.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/SyslogStartConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/SSLSocketReceiver.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/LocalSequenceNumberConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/jul/JULHelper.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/MethodOfCallerConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/util/EnvUtil.java
*
/logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/LoggingEventVO.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/ClassPackagingData.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/LoggerConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/joran/action/ContextNameAction.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/ClassicConstants.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/BasicConfigurator.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/util/LogbackMDCAdapter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/db/names/SimpleDBNameResolver.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/ClassicConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/joran/action/EvaluatorAction.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/server/SSLServerSocketReceiver.java

*
 /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/PropertyConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/util/ContextInitializer.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/boolex/JaninoEventEvaluator.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/ThrowableProxyUtil.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/log4j/XMLLayout.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/server/RemoteAppenderStreamClient.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/jmx/JMXConfiguratorMBean.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/server/SSLServerSocketAppender.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/joran/action/InsertFromJNDIAction.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/MessageConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/ThrowableHandlingConverter.java
*
 /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/PlatformInfo.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/PatternLayout.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/SocketReceiver.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/net/SyslogAppender.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/boolex/OnMarkerEvaluator.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/pattern/NopThrowableInformationConverter.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/TurboFilterList.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/encoder/PatternLayoutEncoder.java
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/spi/LoggerContextVO.java
No license file was found, but licenses were detected in source scan.

Logback: the reliable, generic, fast and flexible logging framework.
Copyright (C) 1999-2010, QOS.ch. All rights reserved.
#
See http://logback.qos.ch/license.html for the applicable licensing
conditions.

This SQL script creates the required tables by ch.qos.logback.classic.db.DBAppender.
#
It is intended for H2 databases.

DROP TABLE logging_event_exception IF EXISTS;
DROP TABLE logging_event_property IF EXISTS;
DROP TABLE logging_event IF EXISTS;

CREATE TABLE logging_event (
 timestmp BIGINT NOT NULL,
 formatted_message LONGVARCHAR NOT NULL,
 logger_name VARCHAR(256) NOT NULL,
 level_string VARCHAR(256) NOT NULL,
 thread_name VARCHAR(256),
 reference_flag SMALLINT,
 arg0 VARCHAR(256),
 arg1 VARCHAR(256),

```
 arg2 VARCHAR(256),
 arg3 VARCHAR(256),
 caller_filename VARCHAR(256),
 caller_class VARCHAR(256),
 caller_method VARCHAR(256),
 caller_line CHAR(4),
 event_id IDENTITY NOT NULL);


CREATE
 TABLE logging_event_property (
 event_id BIGINT NOT NULL,
 mapped_key  VARCHAR(254) NOT NULL,
 mapped_value LONGVARCHAR,
 PRIMARY KEY(event_id, mapped_key),
 FOREIGN KEY (event_id) REFERENCES logging_event(event_id));

CREATE TABLE logging_event_exception (
 event_id BIGINT NOT NULL,
 i SMALLINT NOT NULL,
 trace_line VARCHAR(256) NOT NULL,
 PRIMARY KEY(event_id, i),
 FOREIGN KEY (event_id) REFERENCES logging_event(event_id));
```

Found in path(s):
* /logback-classic-1-2-9-sources-jar/ch/qos/logback/classic/db/script/h2.sql

1.1020 underscore 1.13.6

1.1020.1 Available under license :

MIT
Copyright (c) 2009-2022 Jeremy Ashkenas, Julian Gonggrijp, and DocumentCloud and Investigative Reporters & Editors

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1021 he 1.2.0

1.1021.1 Available under license :

Copyright Mathias Bynens <https://mathiasbynens.be/>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1022 emoji-regex 8.0.0

1.1022.1 Available under license :

Copyright Mathias Bynens <https://mathiasbynens.be/>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1023 d3-interpolate 2.0.1

1.1023.1 Available under license :

Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1024 d3-color 2.0.0

1.1024.1 Available under license :

Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
 endorse or promote products derived from this software without specific prior
 written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
 CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1025 d3-array 2.12.1

1.1025.1 Available under license :

BSD-3-Clause
Copyright 2010-2020 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1026 react-dom 17.0.2

1.1026.1 Available under license :

MIT
MIT License

Copyright (c) Facebook, Inc. and its affiliates.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1027 d3-shape 2.1.0

1.1027.1 Available under license :

BSD-3-Clause
Copyright 2010-2015 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
 endorse or promote products derived from this software without specific prior
 written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
 CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1028 d3-scale-chromatic 2.0.0

1.1028.1 Available under license :

Copyright 2010-2018 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Apache-Style Software License for ColorBrewer software and ColorBrewer Color
Schemes

Copyright (c) 2002 Cynthia Brewer, Mark Harrower, and The Pennsylvania State
University.

Licensed under the Apache License, Version 2.0 (the "License"); you may not use
this file except in compliance with the License. You may obtain a copy of the
License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software distributed
under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR
CONDITIONS OF ANY KIND, either express or implied. See the License for the
specific language governing permissions and limitations under the License.
BSD-3-Clause

1.1029 d3-time 2.1.1

1.1029.1 Available under license :

Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1030 coffee-script 1.12.7

1.1030.1 Available under license :

Copyright (c) 2009-2017 Jeremy Ashkenas

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,

WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1031 filesize 3.6.1

1.1031.1 Available under license :

Copyright (c) 2018, Jason Mulligan
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of filesize nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER
OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1032 d3-scale 3.3.0

1.1032.1 Available under license :

BSD-3-Clause
Copyright 2010-2015 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
 endorse or promote products derived from this software without specific prior
 written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
 CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1033 d3-time-format 3.0.0

1.1033.1 Available under license :

BSD-3-Clause
Copyright 2010-2017 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
 endorse or promote products derived from this software without specific prior
 written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1034 d3-path 2.0.0

1.1034.1 Available under license :

BSD-3-Clause
Copyright 2015-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
 endorse or promote products derived from this software without specific prior
 written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1035 lodash-es 4.17.21

1.1035.1 Available under license :

Copyright OpenJS Foundation and other contributors <https://openjsf.org/>

Based on Underscore.js, copyright Jeremy Ashkenas,
DocumentCloud and Investigative Reporters & Editors <http://underscorejs.org/>

This software consists of voluntary contributions made by many
individuals. For exact contribution history, see the revision history
available at https://github.com/lodash/lodash

The following license applies to all parts of this software except as
documented below:

====

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies
 or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

====

Copyright and related rights for sample code are waived via CC0. Sample
code is defined as all source code displayed within the prose of the
documentation.

CC0: http://creativecommons.org/publicdomain/zero/1.0/

====

Files located in the node_modules and vendor directories are externally
maintained libraries used by this software which have their own
licenses; we recommend you read them, as their terms may differ from the
terms above.
MIT

1.1036 redux 3.7.2

1.1036.1 Available under license :

The [Redux logo](./logo/) is dedicated to the public domain and licensed under
[CC0]([CC0](http://creativecommons.org/publicdomain/zero/1.0/)).
You can copy, modify, and distribute it, even for commercial purposes, all without asking permission.

[Read more about CC0.](http://creativecommons.org/publicdomain/zero/1.0/)
You can find its legal text below.

Creative Commons Zero v1.0 Universal

CC0 1.0 Universal

Statement of Purpose

The laws of most jurisdictions throughout the world automatically confer
exclusive Copyright and Related Rights (defined below) upon the creator and
subsequent owner(s) (each and all, an "owner") of an original work of
authorship and/or a database (each, a "Work").

Certain owners wish to permanently relinquish those rights to a Work for the
purpose of contributing to a commons of creative, cultural and scientific
works ("Commons") that the public can reliably and without fear of later
claims of infringement build upon, modify, incorporate in other
works, reuse
and redistribute as freely as possible in any form whatsoever and for any
purposes, including without limitation commercial purposes. These owners may
contribute to the Commons to promote the ideal of a free culture and the
further production of creative, cultural and scientific works, or to gain
reputation or greater distribution for their Work in part through the use and
efforts of others.

For these and/or other purposes and motivations, and without any expectation
of additional consideration or compensation, the person associating CC0 with a
Work (the "Affirmer"), to the extent that he or she is an owner of Copyright
and Related Rights in the Work, voluntarily elects to apply CC0 to the Work
and publicly distribute the Work under its terms, with knowledge of his or her
Copyright and Related Rights in the Work and the meaning and intended legal
effect of CC0 on those rights.

1. Copyright and Related Rights. A Work made available under CC0 may be protected by copyright
and related or neighboring rights ("Copyright and
Related Rights"). Copyright and Related Rights include, but are not limited to, the following:

i. the right to reproduce, adapt, distribute, perform, display, communicate, and translate a Work;

ii. moral rights retained by the original author(s) and/or performer(s);

iii. publicity and privacy rights pertaining to a person's image or likeness depicted in a Work;

iv. rights protecting against unfair competition in regards to a Work, subject to the limitations in paragraph 4(a), below;

v. rights protecting the extraction, dissemination, use and reuse of data in a Work;

vi. database rights (such as those arising under Directive 96/9/EC of the European Parliament and of the Council of 11 March 1996 on the legal protection of databases, and under any national implementation thereof, including any amended or successor version of such directive); and

vii. other similar, equivalent or corresponding rights throughout
the world
based on applicable law or treaty, and any national implementations thereof.

2. Waiver. To the greatest extent permitted by, but not in contravention of, applicable law, Affirmer hereby overtly, fully, permanently, irrevocably and unconditionally waives, abandons, and surrenders all of Affirmer's Copyright and Related Rights and associated claims and causes of action, whether now known or unknown (including existing as well as future claims and causes of action), in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever, including without limitation commercial, advertising or promotional purposes (the "Waiver"). Affirmer makes the Waiver for the benefit of each member of the public at large and to the detriment of Affirmer's heirs and successors, fully intending that such Waiver shall
not be subject to revocation, rescission, cancellation, termination, or
any other legal or equitable action to disrupt the quiet enjoyment of the Work by the public as contemplated by Affirmer's express Statement of Purpose.

3. Public License Fallback. Should any part of the Waiver for any reason be judged legally invalid or ineffective under applicable law, then the Waiver

shall be preserved to the maximum extent permitted taking into account Affirmer's express Statement of Purpose. In addition, to the extent the Waiver is so judged Affirmer hereby grants to each affected person a royalty-free, non transferable, non sublicensable, non exclusive, irrevocable and unconditional license to exercise Affirmer's Copyright and Related Rights in the Work (i) in all territories worldwide, (ii) for the maximum duration provided by applicable law or treaty (including future time extensions), (iii) in any current or future medium and for any number of copies, and (iv) for any purpose whatsoever,
including without limitation commercial, advertising or promotional purposes (the "License"). The License shall be deemed effective as of the date CC0 was applied by Affirmer to the Work. Should any part of the License for any reason be judged legally invalid or ineffective under applicable law, such partial invalidity or ineffectiveness shall not invalidate the remainder of the License, and in such case Affirmer hereby affirms that he or she will not (i) exercise any of his or her remaining Copyright and Related Rights in the Work or (ii) assert any associated claims and causes of action with respect to the Work, in either case contrary to Affirmer's express Statement of Purpose.

4. Limitations and Disclaimers.

a. No trademark or patent rights held by Affirmer are waived, abandoned, surrendered, licensed or otherwise affected by this document.

b. Affirmer offers the Work as-is and makes no representations or warranties of any kind concerning the Work, express, implied, statutory or otherwise,
including without limitation warranties of title, merchantability, fitness for a particular purpose, non infringement, or the absence of latent or other defects, accuracy, or the present or absence of errors, whether or not discoverable, all to the greatest extent permissible under applicable law.

c. Affirmer disclaims responsibility for clearing rights of other persons that may apply to the Work or any use thereof, including without limitation any person's Copyright and Related Rights in the Work. Further, Affirmer disclaims responsibility for obtaining any necessary consents, permissions or other rights required for any use of the Work.

d. Affirmer understands and acknowledges that Creative Commons is not a party to this document and has no duty or obligation with respect to this CC0 or use of the Work.

For more information, please see
<http://creativecommons.org/publicdomain/zero/1.0/>
MIT
The MIT License (MIT)

Copyright (c) 2015-present Dan Abramov

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1037 convert-source-map 1.9.0

1.1037.1 Available under license :

Copyright 2013 Thorsten Lorenz.
All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN

CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

1.1038 base 0.11.2

1.1038.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1039 codepage 1.15.0

1.1039.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise

designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any

risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "{}"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright (C) 2013-present SheetJS LLC

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache License 2.0

1.1040 adler-32 1.2.0

1.1040.1 Available under license :

Apache License 2.0
Copyright (C) 2014-present SheetJS

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1041 cfb 1.2.2

1.1041.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the

direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding

those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise,

unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "{}"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright (C) 2013-present SheetJS LLC

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache License 2.0

1.1042 frac 1.1.2

1.1042.1 Available under license :

Copyright (C) 2012-present SheetJS

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache License 2.0

1.1043 react-router-dom 5.3.4

1.1043.1 Available under license :

MIT License

Copyright (c) React Training 2015-2019
Copyright (c) Remix Software 2020-2022

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

MIT

1.1044 tiny-invariant 1.3.1

1.1044.1 Available under license :

MIT License

Copyright (c) 2019 Alexander Reardon

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1045 react-router 5.3.4

1.1045.1 Available under license :

MIT License

Copyright (c) React Training 2015-2019
Copyright (c) Remix Software 2020-2022

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1046 d3-force 2.1.1

1.1046.1 Available under license :

Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1047 d3-timer 2.0.0

1.1047.1 Available under license :

Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
 endorse or promote products derived from this software without specific prior
 written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
 CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1048 d3-dispatch 2.0.0

1.1048.1 Available under license :

Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1049 d3-quadtree 2.0.0

1.1049.1 Available under license :

Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS

SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1050 amdi18n-loader 0.9.4

1.1050.1 Available under license :

Copyright <YEAR> <COPYRIGHT HOLDER>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1051 babel-loader 8.3.0

1.1051.1 Available under license :

Copyright (c) 2014-2019 Lus Couto <hello@luiscouto.pt>

MIT License

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE

LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1052 regenerator-runtime 0.13.11

1.1052.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present, Facebook, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1053 apache-commons-text 1.10.0

1.1053.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,

and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to

communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and

attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or

implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Commons Text
Copyright 2014-2022 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (https://www.apache.org/).

1.1054 xlsx 0.17.5

1.1054.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable

(except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,

and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "{}"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright (C) 2012-present SheetJS LLC

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1055 d3-fetch 2.0.0

1.1055.1 Available under license :

BSD-3-Clause
Copyright 2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this

list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS
BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1056 d3-zoom 2.0.0

1.1056.1 Available under license :

Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR

CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1057 d3-brush 2.1.0

1.1057.1 Available under license :

Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
 endorse or promote products derived from this software without specific prior
 written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
 CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1058 d3-hierarchy 2.0.0

1.1058.1 Available under license :

Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
 endorse or promote products derived from this software without specific prior
 written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
 CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1059 d3-random 2.2.2

1.1059.1 Available under license :

Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1060 d3-selection 2.0.0

1.1060.1 Available under license :

BSD-3-Clause
Copyright (c) 2010-2018, Michael Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* The name Michael Bostock may not be used to endorse or promote products
derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL MICHAEL BOSTOCK BE LIABLE FOR ANY DIRECT,
INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY
OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE,

EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1061 d3-transition 2.0.0

1.1061.1 Available under license :

BSD-3-Clause
Copyright (c) 2010-2015, Michael Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* The name Michael Bostock may not be used to endorse or promote products
 derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL MICHAEL BOSTOCK BE LIABLE FOR ANY DIRECT,
INDIRECT,
 INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY
OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE,
EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

TERMS OF USE - EASING EQUATIONS

Open source under the BSD License.

Copyright 2001 Robert Penner
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

- Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials
provided with the distribution.

- Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1062 d3-polygon 2.0.0

1.1062.1 Available under license :

Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;

LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1063 d3-axis 2.1.0

1.1063.1 Available under license :

Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
 endorse or promote products derived from this software without specific prior
 written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
 CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1064 d3-geo 2.0.2

1.1064.1 Available under license :

BSD-3-Clause
Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
 endorse or promote products derived from this software without specific prior
 written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
 CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This license applies to GeographicLib, versions 1.12 and later.

Copyright (c) 2008-2012, Charles Karney

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following
 conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1065 d3-dsv 2.0.0

1.1065.1 Available under license :

BSD-3-Clause
Copyright 2013-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
 endorse or promote products derived from this software without specific prior
 written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
 CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1066 d3 6.7.0

1.1066.1 Available under license :

BSD-3-Clause
Copyright 2010-2020 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1067 d3-chord 2.0.0

1.1067.1 Available under license :

Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES

(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1068 d3-ease 2.0.0

1.1068.1 Available under license :

BSD-3-Clause
Copyright 2010-2016 Mike Bostock
Copyright 2001 Robert Penner
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
 endorse or promote products derived from this software without specific prior
 written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT
 SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1069 d3-drag 2.0.0

1.1069.1 Available under license :

Copyright 2010-2016 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
 endorse or promote products derived from this software without specific prior
 written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
 CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1070 d3-contour 2.0.0

1.1070.1 Available under license :

Copyright 2012-2017 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1071 d3-format 2.0.0

1.1071.1 Available under license :

BSD-3-Clause
Copyright 2010-2015 Mike Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of the author nor the names of contributors may be used to
endorse or promote products derived from this software without specific prior
written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR
ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT

(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1072 loader-utils 1.4.2

1.1072.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1073 camelize 1.0.1

1.1073.1 Available under license :

This software is released under the MIT license:

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS

FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1074 safe-regex-test 1.0.0

1.1074.1 Available under license :

MIT License

Copyright (c) 2022 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1075 is-callable 1.2.7

1.1075.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell

copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1076 react-redux 7.2.9

1.1076.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015-present Dan Abramov

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1077 unicode-match-property-value-ecmascript 2.1.0

1.1077.1 Available under license :

Copyright Mathias Bynens <https://mathiasbynens.be/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1078 @sinonjs/commons 1.8.6

1.1078.1 Available under license :

BSD-3-Clause
BSD 3-Clause License

Copyright (c) 2018, Sinon.JS
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

* Neither the name of the copyright holder nor the names of its
contributors may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"

AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT
SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE
FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1079 redux-thunk 2.4.2

1.1079.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-present Dan Abramov

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1080 decode-uri-component 0.2.2

1.1080.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2017, Sam Verschueren <sam.verschueren@gmail.com> (github.com/SamVerschueren)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1081 styled-components 4.4.1

1.1081.1 Available under license :

MIT

1.1082 dna-ui-utils 1.0.29

1.1082.1 Available under license :

ISC
MIT

1.1083 react-list 0.8.17

1.1083.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017 Casey Foster

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1084 yargs 7.1.2

1.1084.1 Available under license :

Copyright 2010 James Halliday (mail@substack.net)
Modified work Copyright 2014 Contributors (ben@npmjs.com)

This project is free software released under the MIT/X11 license:

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE
FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1085 less 3.13.1

1.1085.1 Available under license :

Apache License 2.0

1.1086 jackson-databind 2.12.7.1

1.1086.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain

separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without

modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include

the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Jackson JSON processor

Jackson is a high-performance, Free/Open Source JSON processing library.
It was originally written by Tatu Saloranta (tatu.saloranta@iki.fi), and has
been in development since 2007.
It is currently developed by a community of developers.

Licensing

Jackson 2.x core and extension components are licensed under Apache License 2.0
To find the details that apply to this artifact see the accompanying LICENSE file.

Credits

A list of contributors may be found from CREDITS(-2.x) file, which is included
in some artifacts (usually source distributions); but is always available
from the source code management (SCM) system project uses.

1.1087 query-string 7.1.3

1.1087.1 Available under license :

MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (http://sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit

persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1088 json5 2.2.3

1.1088.1 Available under license :

MIT
MIT License

Copyright (c) 2012-2018 Aseem Kishore, and [others].

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

[others]: https://github.com/json5/json5/contributors

1.1089 regenerate 1.4.2

1.1089.1 Available under license :

Copyright Mathias Bynens <https://mathiasbynens.be/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1090 typedarray-to-buffer 3.1.5

1.1090.1 Available under license :

The MIT License (MIT)

Copyright (c) Feross Aboukhadijeh

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR

IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1091 react-is 16.13.1

1.1091.1 Available under license :

MIT
MIT License

Copyright (c) Facebook, Inc. and its affiliates.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1092 scheduler 0.20.2

1.1092.1 Available under license :

MIT
MIT License

Copyright (c) Facebook, Inc. and its affiliates.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1093 typed-array-length 1.0.4

1.1093.1 Available under license :

MIT License

Copyright (c) 2020 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1094 es-set-tostringtag 2.0.1

1.1094.1 Available under license :

MIT License

Copyright (c) 2022 ECMAScript Shims

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1095 camel-api 3.8.0

1.1095.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
    * Get the {@link Component} as the specified type.
    *
    * @param  type                  the proprietary class
 or interface of the underlying concrete Component.
    * @return                       an instance of the underlying concrete Component as the required type.
```

```
    * @throws IllegalArgumentException if the component class can't be cast to required type,
    */
```

Found in path(s):
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ComponentAware.java
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
    * Returns the list of configurers to apply to an {@link SSLSocketFactory} in order to fully configure it in
    * compliance
 with the provided configuration options. The configurers are to be applied in the order in which they
    * appear in the list.
    * <p/>
    * It is preferred to use {@link #getSSLSocketFactorySSLSocketConfigurers(SSLContext)} instead of this
method as
    * {@code SSLSocketFactory} does not contain any configuration options that are non-proprietary.
    *
    * @param  context the context that serves as the factory for {@code SSLSocketFactory} instances
    *
    * @return         the needed configurers
    *
    * @see            #getSSLSocketFactorySSLSocketConfigurers(SSLContext)
    */
/**
    * Returns the list of configurers to apply to an {@link SSLServerSocketFactory} in order to fully configure it in
    * compliance with the provided configuration options. The configurers are to be applied in the order in which they
    * appear in the list.
    * <p/>
    * It is preferred to use {@link #getSSLServerSocketFactorySSLServerSocketConfigurers(SSLContext)}
 instead of this
    * method as {@code SSLServerSocketFactory} does not contain any configuration options that are non-
proprietary.
```

```
   *
   * @param  context the context that serves as the factory for {@code SSLServerSocketFactory} instances
   *
   * @return         the needed configurers
   *
   * @see            #getSSLServerSocketFactorySSLServerSocketConfigurers(SSLContext)
   */
```

Found in path(s):
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/BaseSSLContextParameters.java
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
   * Access the underlying concrete CamelClusterView implementation to provide access to further features.
   *
   *
 @param  clazz the proprietary class or interface of the underlying concrete CamelClusterView.
   * @return       an instance of the underlying concrete CamelClusterView as the required type.
   */
```

Found in path(s):
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cluster/CamelClusterView.java
No license file was found, but licenses were detected in source scan.

```
<!--

  Licensed to the Apache Software Foundation (ASF) under one or more
  contributor license agreements.  See the NOTICE file distributed with
  this work for additional information regarding copyright ownership.
  The ASF licenses this file to You under the Apache License, Version 2.0
  (the "License"); you may not use this file except in compliance with
  the License.  You may obtain a copy of the License at
```

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

-->

Found in path(s):
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/package.html
* /camel-api-3-8-0-sources-1-jar/META-INF/maven/org.apache.camel/camel-api/pom.xml
*
/camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/package.html
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/catalog/package.html
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cluster/package.html
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/component/extension/package.html
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/health/package.html
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/package.html
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
    * Access the underlying concrete ComponentExtension implementation to provide access to further features.
    *

 * @param  clazz the proprietary class or interface of the underlying concrete ComponentExtension.
    * @return       an instance of the underlying concrete ComponentExtension as the required type.
    */
```

Found in path(s):

* /camel-api-3-8-0-sources-1-jar/org/apache/camel/component/extension/ComponentExtension.java
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
    * Access the underlying concrete CamelClusterService implementation to provide access to further features.
    *

  * @param  clazz the proprietary class or interface of the underlying concrete CamelClusterService.
    * @return       an instance of the underlying concrete CamelClusterService as the required type.
    */
```

Found in path(s):
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cluster/CamelClusterService.java
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/AsyncCallback.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RecoverableAggregationRepository.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ComponentNameResolver.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/EndpointInject.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/InternalProcessor.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/UriFactoryResolver.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/DataType.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Processor.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/annotations/Language.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/GroupAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/service/ServiceHelper.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ExchangeException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ValidatorRegistry.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceLoadBalancerFunction.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/CamelAuthorizationException.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/Navigate.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/DataFormatCustomizer.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/RuntimeExpressionException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/Transformer.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/component/extension/ComponentVerifierExtension.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/OnCamelContextInitializing.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/PackageScanResourceResolver.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ValueHolder.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RuntimeEndpointRegistry.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ShutdownPrepared.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/StaticService.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceLoadBalancerFactory.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/CamelContextCustomizer.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/CamelContextAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceDiscoveryAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/AliasedX509ExtendedKeyManager.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ExpressionFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RestBindingJaxbDataFormatFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/FactoryFinder.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/OnCamelContextStarting.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceChooserFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/StateRepository.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/StreamCachingStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/StartupStep.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ApiEndpoint.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceDefinition.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/BeanInject.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ExecutorServiceManager.java

* /camel-api-3-8-0-sources-1-jar/org/apache/camel/NamedNode.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/SynchronizationVetoable.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/annotations/ServiceFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ExchangeTimedOutException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/LifecycleStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RouteStartupOrder.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Converter.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/NodeIdFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cluster/CamelClusterMember.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceCallConstants.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/FactoryFinderResolver.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Suspendable.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/GlobalSSLContextParametersSupplier.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ExpressionFactoryAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceFilter.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/TrustManagersParameters.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ExchangeFormatter.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ExpressionEvaluationException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/health/HealthCheckFilter.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/InvokeOnHeader.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ScheduledPollConsumerScheduler.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ComponentResolver.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/Endpoint.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/UnitOfWork.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/BatchConsumer.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/NoTypeConversionAvailableException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ProcessorFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RestConfiguration.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/NoSuchPropertyException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ErrorHandlerFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/health/HealthCheckRepository.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ShutdownAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/JsseParameters.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/CamelEvent.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/LanguageCustomizer.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/Predicate.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/IdAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RoutePolicyFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Service.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/CircuitBreakerConstants.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/HeadersMapFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/SSLContextServerParameters.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ResolveEndpointFailedException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/FallbackConverter.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Body.java

* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/BrowsableEndpoint.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/HeaderFilterStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/SSLContextParameters.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ConfigurerResolver.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/catalog/LanguageValidationResult.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RoutesBuilderLoader.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/PollingConsumer.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/PropertyConfigurer.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/AfterPropertiesConfigured.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/StreamCache.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/RuntimeExchangeException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/InterceptStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ShutdownRoute.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Producer.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/component/extension/MetaDataExtension.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/annotations/Component.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/BeanRepository.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/PropertiesSource.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/AggregationRepository.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/StreamCacheException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/DeferServiceFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/MessageHistoryFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/OnCamelContextEvent.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/NoSuchBeanException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/SuspendableService.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Handler.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ExtendedExchange.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cluster/CamelPreemptiveClusterService.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/NamespaceAware.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/annotations/CloudServiceFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/FailedToCreateProducerException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/CamelExchangeException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/PackageScanFilter.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/MessageHistory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Channel.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RouteIdAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ManagementObjectNameStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ExpectedBodyTypeException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RoutePolicy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ConfigurerStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ExpressionIllegalSyntaxException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/PropertiesFunction.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/MockSendToEndpointStrategyFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/BeanProxyFactory.java

* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Message.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceFilterAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceLoadBalancer.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/InflightRepository.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/UriParams.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/Policy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/EndpointAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/PollingConsumerPollStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/service/ServiceSupport.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/FluentProducerTemplate.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/InOnly.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/annotations/Dataformat.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Expression.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/WrappedFile.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/DataFormat.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/catalog/RuntimeCamelCatalog.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/FailedToCreateConsumerException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ThreadPoolFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/DataFormatFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ExceptionHandler.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/BeanConfigInject.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/TypeConverter.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ConsumerCache.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/package-info.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/FailedToCreateRouteException.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ClaimCheckRepository.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/DiscoverableService.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RoutesLoader.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ExecutorServiceAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/XMLRoutesDefinitionLoader.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/NoFactoryAvailableException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/PropertyBindingException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/DelegateEndpoint.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/Breakpoint.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/CamelBeanPostProcessor.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/CamelLogger.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/InvalidPayloadRuntimeException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/SendDynamicAware.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ExpressionResultTypeAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ManagementMBeanAssembler.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/SynchronizationRouteAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/SimpleExecutorService.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/TypeConversionException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/BeanScope.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ExtendedStartupListener.java

* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cluster/CamelPreemptiveClusterView.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ManagementStrategyFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/InOut.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ExchangeProperties.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/AsPredicate.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/UriParam.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RestRegistry.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/CamelException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/Synchronization.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ManagementNameStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ExchangePattern.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ExtendedCamelContext.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/service/BaseService.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RestProducerFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/Debugger.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/NotifyBuilderMatcher.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/KeyStoreParameters.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ShutdownableService.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/RouteAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ShutdownStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ManagementInterceptStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceDiscoveryFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/catalog/EndpointValidationResult.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/NamedRoute.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/OnCamelContextInitialized.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/TypeConverterRegistry.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/EndpointStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ApiMethod.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/KeyManagersParameters.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/WaitForTaskToComplete.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/TypeConverters.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ErrorHandler.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/TypeConverterLoader.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Consume.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ComponentCustomizer.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/TimeoutMap.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/CamelInternalProcessorAdvice.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/PredicateFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/Tracer.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/annotations/SendDynamic.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/Language.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/GlobalEndpointConfiguration.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/CamelContextNameStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceDiscovery.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/Injector.java

*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ErrorHandlerAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/OnCamelContextStop.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/LogListener.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Consumer.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/AsyncProcessor.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/TransactedPolicy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/RuntimeTransformException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/EndpointProducerResolver.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/EventNotifier.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/NoSuchEndpointException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/UuidGenerator.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/CamelExecutionException.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/SSLContextParametersAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ProducerCache.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/Configurer.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/LanguageResolver.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/CatalogCamelContext.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/DeferredContextBinding.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ValidationException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/AsEndpointUri.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/Registry.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/PropertyInject.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RouteController.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/EndpointUriFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RouteError.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/OptimisticLockingAggregationRepository.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/CamelContextLifecycle.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/NoSuchHeaderException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/RollbackExchangeException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/RoutingSlip.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ThreadPoolProfile.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ShutdownRunningTask.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/DataTypeAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RestConsumerFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/VetoCamelContextStartException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Traceable.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/AlreadyStoppedException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/UnitOfWorkFactory.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/Header.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/TransformerRegistry.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ProxyInstantiationException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/FilterParameters.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Produce.java

* /camel-api-3-8-0-sources-1-jar/org/apache/camel/LoadPropertiesException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/StartupSummaryLevel.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/health/HealthCheck.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/health/HealthCheckResultBuilder.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/SecureRandomParameters.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/SupervisingRouteController.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ReifierStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/RuntimeCamelException.java
*
/camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ApiParam.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/WrapAwareProcessor.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Builder.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/InterceptSendToEndpoint.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/health/HealthCheckConfiguration.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/BootstrapCloseable.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/DataFormatName.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ConsumerTemplate.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/DataFormatContentTypeHeader.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/UriEndpoint.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/RuntimeConfiguration.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceRegistry.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/OnCamelContextStopping.java
*
/camel-api-3-8-0-sources-1-jar/org/apache/camel/FailedToStartRouteException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/StatefulService.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ErrorHandlerRedeliveryCustomizer.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/BeanProcessorFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Pattern.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/ClientAuthentication.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cluster/CamelClusterEventListener.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/AsyncProcessorAwaitManager.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/PollingConsumerPollingStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/AnnotationScanTypeConverters.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/OnCamelContextStarted.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceChooser.java
*
/camel-api-3-8-0-sources-1-jar/org/apache/camel/DelegateProcessor.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceHealth.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/MaskingFormatter.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/TypeConverterExistsException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ModelReifierFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/EndpointConsumerResolver.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/UriPath.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RestApiProcessorFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/LoggingLevel.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/TimerListener.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/Contract.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/health/HealthCheckHelper.java

* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/PropertiesComponent.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Category.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceChooserAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ModelToXMLDumper.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/BinaryPredicate.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/HeaderFilterStrategyAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/StartupListener.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/InvalidPayloadException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/EndpointRegistry.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ApiParams.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RestApiConsumerFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ExtendedPropertyConfigurerGetter.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/SecureSocketProtocolsParameters.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RestRegistryFactory.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/catalog/ConfigurationPropertiesValidationResult.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/BulkTypeConverters.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/AuthorizationPolicy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/annotations/ConstantProvider.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/AsyncProducer.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/PackageScanClassResolver.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ClassResolver.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ManagementAgent.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/SharedInternalProcessor.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/SSLContextClientParameters.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/AnnotationBasedProcessorFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/OnCamelContextStart.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/RecipientList.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/CamelContext.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/TypeConverterLoaderException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/PredicateFactoryAware.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/DynamicRouter.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/CamelContextTracker.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/NonManagedService.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/Condition.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/component/extension/ComponentVerifierExtensionHelper.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/MultipleConsumersSupport.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Exchange.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/health/HealthCheckRegistry.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/LoadablePropertiesSource.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/Experimental.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/BeanIntrospection.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/InterceptEndpointFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/annotations/JdkService.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/catalog/SuggestionStrategy.java

* /camel-api-3-8-0-sources-1-jar/org/apache/camel/NoSuchLanguageException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/IdempotentRepository.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ServiceStatus.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/EndpointUtilizationStatistics.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/IsSingleton.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceFilterFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/catalog/JSonSchemaResolver.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ManagementStrategy.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/StartupStepRecorder.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/Resource.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/TypeConverterExists.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/InvalidPropertyException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/Metadata.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/OnCamelContextStopped.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/InternalProcessorFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/AggregationStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Ordered.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/InvokeOnHeaderStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/DataFormatResolver.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ProducerTemplate.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/support/jsse/CipherSuitesParameters.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/AsyncEndpoint.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/RoutesBuilder.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/GeneratedPropertyConfigurer.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/catalog/PropertiesValidationResult.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/Validator.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/HasGroup.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RouteTemplateParameterSource.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/BindToRegistry.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ExchangeProperty.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/EventFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/HasCamelContext.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Headers.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/PropertyConfigurerAware.java
*
 /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/RouteFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/CamelUnitOfWorkException.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Component.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ModelJAXBContextFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ManagementObjectStrategy.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/Route.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/StaticExpression.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/cloud/ServiceExpressionFactory.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/PropertyConfigurerGetter.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/HasId.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/NormalizedEndpointUri.java

* /camel-api-3-8-0-sources-1-jar/org/apache/camel/spi/ReactiveExecutor.java
* /camel-api-3-8-0-sources-1-jar/org/apache/camel/ManagementStatisticsLevel.java

1.1096 camel-base 3.8.0

1.1096.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/TypeConvertersLoader.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/converter/ObjectConverter.java
*
 /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/DefaultPropertiesParser.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextStartingEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/BaseTypeConverterRegistry.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/StepFailedEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/converter/CamelConverter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/converter/SQLConverter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/ExchangeSendingEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/PropertiesLookup.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/TypeConvertersPackageScanClassResolver.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/RouteStartedEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/EnvPropertiesFunction.java
*
 /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/ServicePropertiesFunction.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/EnumTypeConverter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/RouteRemovedEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/FilePropertiesSource.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextInitializedEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextStartedEvent.java

* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextSuspendedEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/StepCompletedEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/converter/IOConverter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextRoutesStoppingEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/PropertiesLocation.java
*
 /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/ExchangeCreatedEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextRoutesStartedEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/InstanceMethodTypeConverter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/PropertiesComponent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextStartupFailureEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/CoreTypeConverterRegistry.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextResumedEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/AbstractStepEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/ServiceStopFailureEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/ExchangeFailedEvent.java
*
 /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/StepStartedEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/RouteAddedEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/RouteStartingEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/AsyncProcessorTypeConverter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextResumingEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/ServiceStartupFailureEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextSuspendingEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextStoppedEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/FastAnnotationTypeConverterLoader.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/ServiceHostPropertiesFunction.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/converter/NIOConverter.java
*
 /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/ArrayTypeConverter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextRoutesStoppedEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextResumeFailureEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/scan/CompositePackageScanFilter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/InstanceMethodFallbackTypeConverter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/ToStringTypeConverter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/DefaultTypeConverter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextStoppingEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/ExchangeCompletedEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/scan/AnnotatedWithAnyPackageScanFilter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/converter/UriTypeConverter.java
*
 /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/LocationPropertiesSource.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/StaticMethodTypeConverter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/FutureTypeConverter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/ServicePortPropertiesFunction.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/DefaultEventFactory.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/ExchangeSentEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/AbstractContextEvent.java

* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/scan/InvertingPackageScanFilter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextRoutesStartingEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/converter/DurationConverter.java
*
 /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/scan/AnnotatedWithPackageScanFilter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/SysPropertiesFunction.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/scan/AssignableToPackageScanFilter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/converter/DateTimeConverter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/PropertiesParser.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/AbstractRouteEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/AbstractLocationPropertiesSource.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/ExchangeFailureHandlingEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/DefaultPropertiesLookup.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/AbstractExchangeEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextInitializingEvent.java
*
 /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/ClasspathPropertiesSource.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/StaticMethodFallbackTypeConverter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/AnnotationTypeConverterLoader.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/CachingInjector.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/RouteStoppingEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/ExchangeRedeliveryEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/CamelContextStopFailureEvent.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/converter/CollectionConverter.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/RefPropertiesSource.java
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/ExchangeFailureHandledEvent.java
*
 /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/RouteStoppedEvent.java
No license file was found, but licenses were detected in source scan.

<!--

  Licensed to the Apache Software Foundation (ASF) under one or more
  contributor license agreements. See the NOTICE file distributed with
  this work for additional information regarding copyright ownership.
  The ASF licenses this file to You under the Apache License, Version 2.0
  (the "License"); you may not use this file except in compliance with
  the License. You may obtain a copy of the License at

      http://www.apache.org/licenses/LICENSE-2.0

  Unless required by applicable law or agreed to in writing, software
  distributed under the License is distributed on an "AS IS" BASIS,
  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
  See the License for the specific language governing permissions and
  limitations under the License.

-->

Found in path(s):
* /camel-base-3-8-0-sources-1-jar/META-INF/maven/org.apache.camel/camel-base/pom.xml
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/converter/package.html
*
 /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/scan/package.html
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/converter/package.html
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/component/properties/package.html
* /camel-base-3-8-0-sources-1-jar/org/apache/camel/impl/event/package.html

1.1097 camel-base-engine 3.8.0

1.1097.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultAsyncProcessorAwaitManager.java
*
 /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/LimitedPollingConsumerPollStrategy.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultCamelBeanPostProcessor.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultManagementNameStrategy.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultManagementStrategy.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/SimpleCamelContext.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultValidatorRegistry.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultBeanIntrospection.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultMessageHistoryFactory.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultUriFactoryResolver.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/FileStateRepository.java
*

/camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/debugger/BacklogTracer.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/debugger/DefaultBacklogTracerEventMessage.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultInflightRepository.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultFactoryFinderResolver.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultComponentNameResolver.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultRoutesLoader.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/CamelInternalProcessor.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/AutowiredLifecycleStrategy.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultExecutorServiceManager.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/WebSpherePackageScanClassResolver.java
*
/camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/MemoryStateRepository.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/ExplicitCamelContextNameStrategy.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultConfigurerResolver.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultFluentProducerTemplate.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultNodeIdFactory.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultSupervisingRouteController.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/CustomizersLifecycleStrategy.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultHeadersMapFactory.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultPackageScanClassResolver.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultPackageScanResourceResolver.java
*
/camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultCamelContextNameStrategy.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/SharedCamelInternalProcessor.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultChannel.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultClassResolver.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/MDCUnitOfWork.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultConsumerTemplate.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/BasePackageScanResolver.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/TransformerKey.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/InternalRouteController.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultInjector.java
*
/camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/ProvisionalEndpointRegistry.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultFactoryFinder.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/InternalRouteStartupManager.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultReactiveExecutor.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/HashMapHeadersMapFactory.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultComponentResolver.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/CompoundIterator.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultRouteController.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/OnCamelContextLifecycleStrategy.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultGlobalEndpointConfiguration.java
*
/camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultRouteFactory.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultProducerTemplate.java

* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultRouteError.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultManagementStrategyFactory.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultEndpointRegistry.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultRuntimeEndpointRegistry.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultDataFormatResolver.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultLanguageResolver.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/BootstrapFactoryFinder.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultRoute.java
*
 /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/RouteService.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultTransformerRegistry.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/BaseExecutorServiceManager.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/AbstractCamelContext.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/debugger/DefaultDebugger.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultShutdownStrategy.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultTracer.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultResource.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultUnitOfWork.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultUnitOfWorkFactory.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/ValidatorKey.java
*
 /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/EndpointKey.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DurationRoutePolicyFactory.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/debugger/BacklogDebugger.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/CamelPostProcessorHelper.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DurationRoutePolicy.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/AbstractDynamicRegistry.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultStreamCachingStrategy.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultServiceBootstrapCloseable.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/SubscribeMethodProcessor.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/BootstrapConfigurerResolver.java
*
 /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultInterceptEndpointFactory.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DeferServiceStartupListener.java
* /camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/engine/DefaultRouteStartupOrder.java
No license file was found, but licenses were detected in source scan.

<!--

  Licensed to the Apache Software Foundation (ASF) under one or more
  contributor license agreements. See the NOTICE file distributed with
  this work for additional information regarding copyright ownership.
  The ASF licenses this file to You under the Apache License, Version 2.0
  (the "License"); you may not use this file except in compliance with
  the License. You may obtain a copy of the License at

      http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

-->

Found in path(s):
* /camel-base-engine-3-8-0-sources-1-jar/META-INF/maven/org.apache.camel/camel-base-engine/pom.xml
*
/camel-base-engine-3-8-0-sources-1-jar/org/apache/camel/impl/debugger/package.html

1.1098 camel-core-engine 3.8.0

1.1098.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /camel-core-engine-3-8-0-sources-1-jar/org/apache/camel/impl/RouteIdFactory.java
* /camel-core-engine-3-8-0-sources-1-jar/org/apache/camel/impl/DefaultModelReifierFactory.java
*
/camel-core-engine-3-8-0-sources-1-jar/org/apache/camel/impl/lw/LightweightCamelContext.java
* /camel-core-engine-3-8-0-sources-1-jar/org/apache/camel/impl/lw/LightweightRuntimeCamelContext.java
* /camel-core-engine-3-8-0-sources-1-jar/org/apache/camel/impl/DefaultCamelContext.java
* /camel-core-engine-3-8-0-sources-1-jar/org/apache/camel/impl/DefaultModel.java
No license file was found, but licenses were detected in source scan.

<!--

Licensed to the Apache Software Foundation (ASF) under one or more
contributor license agreements. See the NOTICE file distributed with
this work for additional information regarding copyright ownership.
The ASF licenses this file to You under the Apache License, Version 2.0
(the "License"); you may not use this file except in compliance with
the License. You may obtain a copy of the License at

    http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

-->

Found in path(s):
* /camel-core-engine-3-8-0-sources-1-jar/META-INF/maven/org.apache.camel/camel-core-engine/pom.xml
*
 /camel-core-engine-3-8-0-sources-1-jar/org/apache/camel/impl/package.html

1.1099 camel-core-model 3.8.0

1.1099.1 Available under license :

```
 ============================================================================
==  NOTICE file corresponding to the section 4 d of                 ==
==  the Apache License, Version 2.0,                          ==
==  in this case for the Apache Camel distribution.                 ==
============================================================================
```

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Please read the different LICENSE files present in the licenses directory of
this distribution.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,

and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work,

excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions

of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1100 camel-core-processor 3.8.0

1.1100.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/LoopProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/resequencer/ElementComparator.java
*
/camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/loadbalancer/ExceptionFailureStatistics.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/DefaultProcessorFactory.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/PipelineHelper.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/saga/SagaCompletionMode.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/aggregate/AggregationStrategyMethodInfo.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/DynamicRouter.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/errorhandler/DefaultErrorHandler.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/ThrottlerRejectedExecutionException.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/errorhandler/RedeliveryPolicy.java
*
/camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/ScriptProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/saga/NeverSagaProcessor.java

* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/Throttler.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/FinallyProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/loadbalancer/LoadBalancer.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/saga/NotSupportedSagaProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/SendDynamicAwareResolver.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/StepProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/InterceptEndpointProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/idempotent/IdempotentOnCompletion.java
*
 /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/ClaimCheckAggregationStrategy.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/loadbalancer/DistributionRatio.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/aggregate/AggregateProcessorStatistics.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/aggregate/ClosedCorrelationKeyException.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/loadbalancer/WeightedRandomLoadBalancer.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/Splitter.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/RoutePipeline.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/ContractAdvice.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/DelayProcessorSupport.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/RemoveHeadersProcessor.java
*
 /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/StreamResequencer.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/SendProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/RemovePropertyProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/loadbalancer/TopicLoadBalancer.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/transformer/ProcessorTransformer.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/aggregate/GroupedMessageAggregationStrategy.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/RemovePropertiesProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/SortProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/loadbalancer/LoadBalancerSupport.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/loadbalancer/StickyLoadBalancer.java
*
 /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/RemoveHeaderProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/ThreadsProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/errorhandler/ErrorHandlerSupport.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/saga/SagaPropagation.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/errorhandler/ExceptionPolicyStrategy.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/InterceptSendToEndpointProcessor.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/resequencer/MessageRejectedException.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/DefaultDeferServiceFactory.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/ExchangePatternProcessor.java
*
 /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/errorhandler/NoErrorHandler.java
* /camel-core-processor-3-8-0-sources-1-

jar/org/apache/camel/processor/aggregate/MemoryAggregationRepository.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/errorhandler/ExceptionPolicyKey.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/DefaultAnnotationBasedProcessorFactory.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/saga/SagaProcessorBuilder.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/idempotent/IdempotentConsumer.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/UnitOfWorkProducer.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/saga/SagaProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/Enricher.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/aggregate/StringAggregationStrategy.java
*
/camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/aggregate/DefaultAggregateController.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/SetPropertyProcessor.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/aggregate/AbstractListAggregationStrategy.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/aggregate/GroupedExchangeAggregationStrategy.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/StopProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/resequencer/ResequencerEngine.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/SetHeaderProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/RestBindingAdvice.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/saga/MandatorySagaProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/SendDynamicProcessor.java
*
/camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/errorhandler/RedeliveryErrorHandler.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/LogProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/resequencer/Sequence.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/errorhandler/DefaultExceptionPolicyStrategy.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/loadbalancer/LoadBalancerConsumer.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/WrapProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/RoutingSlip.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/ProcessorExchangePair.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/Pipeline.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/saga/RequiresNewSagaProcessor.java
*
/camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/aggregate/AggregationStrategyBeanAdapter.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/ChoiceProcessor.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/aggregate/UseLatestAggregationStrategy.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/CatchProcessor.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/aggregate/AggregationStrategyParameterInfo.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/DefaultClaimCheckRepository.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/TransformProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/MulticastProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/loadbalancer/QueueLoadBalancer.java

*
/camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/OnCompletionProcessor.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/resequencer/DefaultExchangeComparator.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/resequencer/SequenceElementComparator.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/validator/ProcessorValidator.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/SamplingThrottler.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/resequencer/TimeoutHandler.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/aggregate/GroupedBodyAggregationStrategy.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/loadbalancer/RoundRobinLoadBalancer.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/FilterProcessor.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/loadbalancer/WeightedRoundRobinLoadBalancer.java
*
/camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/resequencer/Timeout.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/aggregate/ShareUnitOfWorkAggregationStrategy.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/PollEnricher.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/RecipientListProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/loadbalancer/WeightedLoadBalancer.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/FatalFallbackErrorHandler.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/errorhandler/ExceptionPolicy.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/aggregate/AggregateController.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/EvaluateExpressionProcessor.java
*
/camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/TryProcessor.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/aggregate/AggregationStrategyBeanInfo.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/loadbalancer/RandomLoadBalancer.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/SetBodyProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/loadbalancer/FailOverLoadBalancer.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/resequencer/SequenceSender.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/errorhandler/DeadLetterChannel.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/idempotent/NoMessageIdException.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/EventNotifierProducer.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/Resequencer.java
*
/camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/Delayer.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/resequencer/ExpressionResultComparator.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/ClaimCheckProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/resequencer/Element.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/transformer/DataFormatTransformer.java
* /camel-core-processor-3-8-0-sources-1-
jar/org/apache/camel/processor/aggregate/UseOriginalAggregationStrategy.java

* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/aggregate/OptimisticLockRetryPolicy.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/aggregate/AggregateProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/DefaultInternalProcessorFactory.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/RecipientList.java
*
 /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/RollbackProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/saga/RequiredSagaProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/saga/SupportsSagaProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/WireTapProcessor.java
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/ThrowExceptionProcessor.java
No license file was found, but licenses were detected in source scan.

<!--

  Licensed to the Apache Software Foundation (ASF) under one or more
  contributor license agreements. See the NOTICE file distributed with
  this work for additional information regarding copyright ownership.
  The ASF licenses this file to You under the Apache License, Version 2.0
  (the "License"); you may not use this file except in compliance with
  the License. You may obtain a copy of the License at

      http://www.apache.org/licenses/LICENSE-2.0

  Unless required by applicable law or agreed to in writing, software
  distributed under the License is distributed on an "AS IS" BASIS,
  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
  See the License for the specific language governing permissions and
  limitations under the License.

-->

Found in path(s):
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/loadbalancer/package.html
*
 /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/aggregate/package.html
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/saga/package.html
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/transformer/package.html
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/package.html
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/validator/package.html
* /camel-core-processor-3-8-0-sources-1-jar/META-INF/maven/org.apache.camel/camel-core-processor/pom.xml
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/errorhandler/package.html
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/resequencer/package.html
* /camel-core-processor-3-8-0-sources-1-jar/org/apache/camel/processor/idempotent/package.html

1.1101 camel-core-reifier 3.8.0

1.1101.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/transformer/TransformerReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/TarFileDataFormatReifier.java
*
 /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/ThriftDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-
jar/org/apache/camel/reifier/dataformat/UniVocityAbstractDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/language/JsonPathExpressionReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/ThrottleReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/language/ExpressionReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/SoapJaxbDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/BarcodeDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/MulticastReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/UniVocityTsvDataFormatReifier.java
*
 /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/ExpressionReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/SetBodyReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/TryReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/errorhandler/DefaultErrorHandlerReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/RemovePropertyReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/loadbalancer/CustomLoadBalancerReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/ProcessorReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/RouteReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/GrokDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/RecipientListReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/JacksonXMLDataFormatReifier.java
*

/camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/CatchReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/SamplingReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/language/XQueryExpressionReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/SetPropertyReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/validator/EndpointValidatorReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/FhirDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/FlatpackDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/OnCompletionReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/SagaReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/RemoveHeadersReifier.java
*
/camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/WhenSkipSendToEndpointReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/UnmarshalReifier.java
* /camel-core-reifier-3-8-0-sources-1-
jar/org/apache/camel/reifier/loadbalancer/RoundRobinLoadBalancerReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/CircuitBreakerReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/StopReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/DataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/ZipFileDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/CsvDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/loadbalancer/LoadBalancerReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/XMLSecurityDataFormatReifier.java
*
/camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/CryptoDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/InterceptSendToEndpointReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/validator/ValidatorReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/RssDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/language/JoorExpressionReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/YAMLDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/WireTapReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/LoadBalanceReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/JaxbDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/LogReifier.java
*
/camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/EnrichReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/MarshalReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/WhenReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/Any23DataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/TransformReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/SetHeaderReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/UniVocityCsvDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/ProtobufDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/language/XPathExpressionReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/validator/PredicateValidatorReifier.java
*
/camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/transformer/EndpointTransformeReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/validator/CustomValidatorReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/errorhandler/DeadLetterChannelReifier.java

* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/OnFallbackReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/ThrowExceptionReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/BindyDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/IcalDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/ASN1DataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/RollbackReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/OtherwiseReifier.java
*
/camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/XmlRpcDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/SortReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/BeanReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/rest/RestBindingReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/DynamicRouterReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/IdempotentConsumerReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/AggregateReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/JsonApiDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/PolicyReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/SetExchangePatternReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/FhirXmlDataFormatReifier.java
*
/camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/RemoveHeaderReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/AbstractReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/ServiceCallReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/loadbalancer/StickyLoadBalancerReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/SendReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/AvroDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/TransactedReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/language/XMLTokenizerExpressionReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/language/MethodCallExpressionReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/transformer/DataFormatTransformerReifier.java
*
/camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/SplitReifier.java
* /camel-core-reifier-3-8-0-sources-1-
jar/org/apache/camel/reifier/dataformat/UniVocityFixedWidthDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/loadbalancer/FailoverLoadBalancerReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/PipelineReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/ChoiceReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/ToDynamicReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/FinallyReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/SyslogDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/Base64DataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/loadbalancer/TopicLoadBalancerReifier.java
*
/camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/loadbalancer/WeightedLoadBalancerReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/LZFDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/errorhandler/NoErrorHandlerReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/language/SimpleExpressionReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/InterceptReifier.java

* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/JsonDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/loadbalancer/RandomLoadBalancerReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/language/CSimpleExpressionReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/RemovePropertiesReifier.java
*
 /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/ScriptReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/CBORDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/InterceptFromReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/HL7DataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/StepReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/AbstractPolicyReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/FilterReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/DelayReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/ConvertBodyReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/errorhandler/ErrorHandlerRefReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/errorhandler/ErrorHandlerReifier.java
*
 /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/ProcessReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/language/DatasonnetExpressionReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/FhirJsonDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/PollEnrichReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/RoutingSlipReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/language/TokenizerExpressionReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/ValidateReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/ThreadsReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/XStreamDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-
jar/org/apache/camel/reifier/dataformat/MimeMultipartDataFormatReifier.java
*
 /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/OnExceptionReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/PGPDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/LoopReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/GzipDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/transformer/CustomTransformeReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/BeanioDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/ResequenceReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/CustomDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/ZipDataFormatReifier.java
* /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/dataformat/TidyMarkupDataFormatReifier.java
*
 /camel-core-reifier-3-8-0-sources-1-jar/org/apache/camel/reifier/ClaimCheckReifier.java
No license file was found, but licenses were detected in source scan.

<!--

  Licensed to the Apache Software Foundation (ASF) under one or more
  contributor license agreements. See the NOTICE file distributed with
  this work for additional information regarding copyright ownership.

The ASF licenses this file to You under the Apache License, Version 2.0
(the "License"); you may not use this file except in compliance with
the License. You may obtain a copy of the License at

    http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

-->

Found in path(s):
* /camel-core-reifier-3-8-0-sources-1-jar/META-INF/maven/org.apache.camel/camel-core-reifier/pom.xml

1.1102 camel-endpointdsl 3.8.0

1.1102.1 Available under license :

No license file was found, but licenses were detected in source scan.

<!--

Licensed to the Apache Software Foundation (ASF) under one or more
contributor license agreements. See the NOTICE file distributed with
this work for additional information regarding copyright ownership.
The ASF licenses this file to You under the Apache License, Version 2.0
(the "License"); you may not use this file except in compliance with
the License. You may obtain a copy of the License at

    http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

-->

Found in path(s):
* /camel-endpointdsl-3-8-0-sources-jar/META-INF/maven/org.apache.camel/camel-endpointdsl/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more

```
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
     * To use a shared Netty HTTP server. See Netty HTTP Server Example for
     * more details.
     *

   * The option is a:
     * &lt;code&gt;org.apache.camel.component.netty.http.NettySharedHttpServer&lt;/code&gt; type.
     *
     * Group: consumer (advanced)
     *
     * @param nettySharedHttpServer the value to set
     * @return the dsl builder
     */
```

Found in path(s):
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/NettyHttpEndpointBuilderFactory.java
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
```

```
*/
/**
      * The exec protection level PROT command. C - Clear S - Safe(SSL
      * protocol only) E - Confidential(SSL protocol
 only) P - Private.
      *
      * The option is a: &lt;code&gt;java.lang.String&lt;/code&gt; type.
      *
      * Group: security
      *
      * @param execProt the value to set
      * @return the dsl builder
      */
```

Found in path(s):
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/FtpsEndpointBuilderFactory.java
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/AtomixQueueEndpointBuilderFactory.java
*
 /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/InfluxDbEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/PubNubEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MailEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ClassEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/KubernetesReplicationControllersEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/DdbEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/FopEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-

jar/org/apache/camel/builder/endpoint/dsl/SpringLdapEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/LuceneEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/ServiceNowEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/DigitalSignatureEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/Athena2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/AvroEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/Translate2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/EhcacheEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/GraphqlEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JooqEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/Web3jEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/LambdaEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SparkEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/CMEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/Sqs2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JBPMEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/DebeziumMongodbEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/GoogleDriveEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/HazelcastAtomicnumberEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/OptaPlannerEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ElsqlEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SagaEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JCacheEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/GooglePubsubEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SWFEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/KubernetesResourcesQuotaEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/JSR356WebSocketEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/SchematronEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SnmpEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/EC2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SmppEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-

jar/org/apache/camel/builder/endpoint/dsl/QuickfixjEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SdbEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/GoogleSheetsStreamEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/RssEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/EtcdWatchEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/XsltEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/DebeziumMySqlEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/RestSwaggerEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/IAM2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MockEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/CMISEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/StompEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/EKSEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/HazelcastSetEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MllpEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/StaticEndpointBuilders.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/SqlStoredEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/UndertowEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/GangliaEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/BeanstalkEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/StubEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/AhcEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/IAMEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JcloudsEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ClientEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/AtomixMapEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/CouchbaseEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/CinderEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/ReactiveStreamsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/InfinispanEmbeddedEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/AtomEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/KinesisFirehose2EndpointBuilderFactory.java

*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/CaffeineCacheEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/HazelcastMultimapEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ServiceEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/GeoCoderEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MinioEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/HazelcastRingbufferEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/RestApiEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/NeutronEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/FhirEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/IronMQEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SlackEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JingEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/EndpointRouteBuilder.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MSK2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/QuartzEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/BonitaEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/OpenshiftBuildsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/IgniteSetEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/DataLakeEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/NatsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/QueueServiceEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MyBatisEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/EndpointBuilders.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/AtomixMessagingEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/KubernetesCustomResourcesEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/BrowseEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/TwitterSearchEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/WebsocketEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MicroProfileMetricsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SpringBatchEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/PulsarEndpointBuilderFactory.java

* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/DebeziumPostgresEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/Sns2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SolrEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/GoogleSheetsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MinaEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SqlEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/StAXEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/LanguageEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/AtlasMapEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/KubernetesConfigMapsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ServerEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/KubernetesNodesEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/KeystoneEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/GoogleCalendarStreamEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/KinesisFirehoseEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/KafkaEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ChatScriptEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/XJEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/DozerEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/IgniteMessagingEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MsvEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ECSEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MyBatisBeanEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/StitchEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JsonataEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/KubernetesSecretsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/VmEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ConsulEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ServletEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/XQueryEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/EKS2EndpointBuilderFactory.java
*

/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JettyHttpEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/HazelcastListEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/CxfRsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/TikaEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MetricsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/RefEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/BoxEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/DataSetEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/GoogleBigQuerySQLEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/AbstractEndpointBuilder.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/DigitalOceanEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/TwilioEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/VertxWebsocketEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/PgEventEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/RestEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/IgniteQueueEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/XmppEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ThriftEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SoroushBotEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/FlatpackEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/CordaEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/XChangeEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/PahoMqtt5EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/TelegramEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/VertxEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/WekaEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/EtcdStatsEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/RedisEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/Olingo2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/EtcdKeysEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MSKEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/NsqEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MustacheEndpointBuilderFactory.java

* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SedaEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SesEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/JsonValidatorEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SchedulerEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/LumberjackEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/KameletEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/KubernetesJobEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JpaEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/LdapEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SnsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/CassandraEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/KubernetesPodsEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/FlinkEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/EventHubsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/PdfEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/RabbitMQEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/FacebookEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/DJLEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SipEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/CwEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/VelocityEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/GuavaEventBusEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/LdifEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/OpenshiftBuildConfigsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/IOTAEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/SimpleNotificationEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ScpEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/InfinispanRemoteEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JiraEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/XsltSaxonEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-

jar/org/apache/camel/builder/endpoint/dsl/SpringIntegrationEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ChunkEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/CoAPEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/Ddb2StreamEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/ArangoDbEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/FreemarkerEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/WebhookEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/KinesisEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/DrillEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/BeanValidatorEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/AtmosEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SwiftEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/GrapeEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/WordpressEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/PgReplicationSlotEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/TranslateEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/NettyEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/DirectEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/KubernetesDeploymentsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/HazelcastQueueEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/KubernetesPersistentVolumesEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/KMS2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/ZooKeeperEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/BraintreeEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/FileWatchEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/DirectVmEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/AWS2EC2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/KMSEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-

jar/org/apache/camel/builder/endpoint/dsl/SpringRabbitMQEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/MongoDbEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/CaffeineLoadCacheEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/Ddb2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/GoraEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/HazelcastSedaEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/GitHubEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/Jt400EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/JGroupsRaftEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/STS2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/IPFSEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/HdfsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/CronEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/CouchDbEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/MiloServerEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/GoogleMailEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MQ2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ExecEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/AtomixValueEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/KubernetesServiceAccountsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JGroupsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/KubernetesNamespacesEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/Ses2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/WsEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/SalesforceEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MasterEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/HazelcastInstanceEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/YammerEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/NitriteEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/GridFsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/DockerEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/PrinterEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/S3EndpointBuilderFactory.java

*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ResteasyEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/HazelcastReplicatedmapEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/AsteriskEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SftpEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/DisruptorEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/SplunkHECEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/DebeziumSqlserverEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ZendeskEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/CometdEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/GlanceEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/DisruptorVmEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/VertxHttpEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/LogEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/FileEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/IrcEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/XmlVerifierEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/GoogleMailStreamEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/XmlSignerEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/ControlBusEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/IgniteComputeEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/WeatherEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/DnsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/TwitterTimelineEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/MicrometerEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/AtomixSetEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/HttpEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/DataFormatEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/DdbStreamEndpointBuilderFactory.java

* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/BeanEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/StringTemplateEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JcrEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SshEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/AtomixMultiMapEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JsltEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/KuduEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/AWS2S3EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/EventEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/Lambda2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/IgniteIdGenEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/Cw2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/TwitterDirectMessageEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/WorkdayEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/PlatformHttpEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SpringWebserviceEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/DropboxEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MvelEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/QueueEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/BlobServiceEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/KubernetesHPAEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JoltEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ZooKeeperMasterEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/KubernetesPersistentVolumesClaimsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/GrpcEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/Olingo4EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/FtpEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/TimerEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ElasticsearchEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/NetWeaverEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JdbcEndpointBuilderFactory.java

* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/PahoEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/GoogleBigQueryEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/KubernetesServicesEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/VertxKafkaEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SplunkEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/HBaseEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/AtmosphereWebsocketEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/HazelcastMapEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/GoogleCalendarEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ECS2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/IgniteEventsEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/DataSetTestEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/CxfEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/NagiosEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/BlobEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MQEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ApnsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/CryptoCmsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/RestOpenApiEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/GitEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/EventbridgeEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SqsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/ValidatorEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/RobotFrameworkEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-
jar/org/apache/camel/builder/endpoint/dsl/HazelcastTopicEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/StreamEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/Kinesis2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JMXEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/NovaEndpointBuilderFactory.java
*

/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/MiloClientEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/OAIPMHEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/AS2EndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/IgniteCacheEndpointBuilderFactory.java
No license file was found, but licenses were detected in source scan.

```
/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements.  See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
     * Use this option to force disabling time to live. For example when you
     * do request/reply over JMS, then
 Camel will by default use the
     * requestTimeout value as time to live on the message being sent. The
     * problem is that the sender and receiver systems have to have their
     * clocks synchronized, so they are in sync. This is not always so easy
     * to archive. So you can use disableTimeToLive=true to not set a time
     * to live value on the sent message. Then the message will not expire
     * on the receiver system. See below in section About time to live for
     * more details.
     *
     * The option is a: &lt;code&gt;boolean&lt;/code&gt; type.
     *
     * Default: false
     * Group: producer (advanced)
     *
     * @param disableTimeToLive the value to set
     * @return the dsl builder
     */
```

Found in path(s):
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/Sjms2EndpointBuilderFactory.java

* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/ActiveMQEndpointBuilderFactory.java
*
/camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/SjmsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/JmsEndpointBuilderFactory.java
* /camel-endpointdsl-3-8-0-sources-jar/org/apache/camel/builder/endpoint/dsl/AMQPEndpointBuilderFactory.java

1.1103 camel-management-api 3.8.0

1.1103.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/mbean/ManagedSamplingThrottlerMBean.java
*
/camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/mbean/ManagedAggregateProcessorMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/mbean/ManagedLogMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/mbean/ManagedSuspendableRouteMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/NotificationSender.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/mbean/ManagedThrottlingInflightRoutePolicyMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/mbean/ManagedRouteMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/mbean/ManagedPollEnricherMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/ManagedOperation.java
* /camel-management-api-3-8-0-sources-1-

jar/org/apache/camel/api/management/mbean/ManagedRemoveHeadersMBean.java
*
/camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedProducerCacheMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedRollbackMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedChoiceMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedRecipientListMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedConsumerCacheMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/ManagedInstance.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/ManagedNotifications.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedMarshalMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/mbean/ManagedStepMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/mbean/ManagedStopMBean.java
*
/camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedDynamicRouterMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedIdempotentConsumerMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/mbean/ManagedFilterMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedRuntimeEndpointRegistryMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedTransformMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedSetHeaderMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedValidateMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedMulticastMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedClusterServiceMBean.java
*
/camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedPerformanceCounterMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedUnmarshalMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedServiceMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedStickyLoadBalancerMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedBacklogTracerMBean.java
* /camel-management-api-3-8-0-sources-1-

jar/org/apache/camel/api/management/mbean/ManagedBeanIntrospectionMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedResourceEndpointMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/BacklogTracerEventMessage.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedProcessorMBean.java
*
/camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedThroughputLoggerMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/NotificationSenderAware.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedRemovePropertiesMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedDelayerMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedThrowExceptionMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedAsyncProcessorAwaitManagerMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedTopicLoadBalancerMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedSendProcessorMBean.java
*
/camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedRemovePropertyMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedThrottlerMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedResequencerMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedInflightRepositoryMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedRandomLoadBalancerMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/mbean/RouteError.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedRoundRobinLoadBalancerMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedThrottlingExceptionRoutePolicyMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedTracerMBean.java
*
/camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedRestRegistryMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedFailoverLoadBalancerMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedWireTapMBean.java

* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedTransformerRegistryMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedSendDynamicProcessorMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedRemoveHeaderMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedSetBodyMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/ManagedAttribute.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedThreadsMBean.java
*
/camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedSetExchangePatternMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedExtendedInformation.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/ManagedResource.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedValidatorRegistryMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedEndpointRegistryMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/ManagedCamelContext.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedStreamCachingStrategyMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedSplitterMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedClaimCheckMBean.java
*
/camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/mbean/ManagedBeanMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedCamelContextMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedConvertBodyMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/mbean/ManagedLoopMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedProcessMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedBacklogDebuggerMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedCounterMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/ManagedNotification.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedScriptMBean.java
*
/camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedCamelHealthMBean.java
* /camel-management-api-3-8-0-sources-1-

jar/org/apache/camel/api/management/mbean/ManagedEndpointMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedThreadPoolMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedTypeConverterRegistryMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedSupervisingRouteControllerMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedConsumerMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ComponentVerifierExtension.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedWeightedBalancerMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedSchedulePollConsumerMBean.java
*
/camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedRoutingSlipMBean.java
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/JmxSystemPropertyKeys.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedBrowsableEndpointMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedRouteControllerMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedComponentMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedDataFormatMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedProducerMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedEnricherMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/JmxNotificationBroadcasterAware.java
*
/camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedSetPropertyMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/ManagedCustomLoadBalancerMBean.java
* /camel-management-api-3-8-0-sources-1-
jar/org/apache/camel/api/management/mbean/CamelOpenMBeanTypes.java
No license file was found, but licenses were detected in source scan.

<!--

Licensed to the Apache Software Foundation (ASF) under one or more
contributor license agreements. See the NOTICE file distributed with
this work for additional information regarding copyright ownership.
The ASF licenses this file to You under the Apache License, Version 2.0

(the "License"); you may not use this file except in compliance with
the License. You may obtain a copy of the License at

    http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

-->

Found in path(s):
* /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/package.html
* /camel-management-api-3-8-0-sources-1-jar/META-INF/maven/org.apache.camel/camel-management-api/pom.xml
*
 /camel-management-api-3-8-0-sources-1-jar/org/apache/camel/api/management/mbean/package.html

1.1104 camel-rabbitmq 3.8.0

1.1104.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/RabbitMQProducer.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/reply/ReplyHolder.java
*

/camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/RabbitMQComponent.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/pool/PoolableChannelFactory.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/RabbitMQEndpoint.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/reply/ReplyManager.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/ReplyToType.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/RabbitMQConstants.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/RabbitMQMessageConverter.java
* /camel-rabbitmq-3-8-0-sources-
jar/org/apache/camel/component/rabbitmq/reply/TemporaryQueueReplyHandler.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/RabbitMQConsumer.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/reply/ReplyHandler.java
*
/camel-rabbitmq-3-8-0-sources-
jar/org/apache/camel/component/rabbitmq/reply/UseMessageIdAsCorrelationIdMessageSentCallback.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/reply/CorrelationTimeoutMap.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/reply/MessageSentCallback.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/RabbitMQSendDynamicAware.java
* /camel-rabbitmq-3-8-0-sources-
jar/org/apache/camel/component/rabbitmq/RabbitMQConnectionFactorySupport.java
* /camel-rabbitmq-3-8-0-sources-
jar/org/apache/camel/component/rabbitmq/reply/TemporaryQueueReplyManager.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/RabbitConsumer.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/RabbitMQMessagePublisher.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/reply/QueueReplyHandler.java
*
/camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/RabbitMQHeaderFilterStrategy.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/reply/ReplyManagerSupport.java
* /camel-rabbitmq-3-8-0-sources-jar/org/apache/camel/component/rabbitmq/RabbitMQDeclareSupport.java
No license file was found, but licenses were detected in source scan.

<!--

Licensed to the Apache Software Foundation (ASF) under one or more
contributor license agreements. See the NOTICE file distributed with
this work for additional information regarding copyright ownership.
The ASF licenses this file to You under the Apache License, Version 2.0
(the "License"); you may not use this file except in compliance with
the License. You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

-->

Found in path(s):
* /camel-rabbitmq-3-8-0-sources-jar/META-INF/maven/org.apache.camel/camel-rabbitmq/pom.xml

1.1105 camel-support 3.8.0

1.1105.1 Available under license :

No license file was found, but licenses were detected in source scan.

<!--

  Licensed to the Apache Software Foundation (ASF) under one or more
  contributor license agreements. See the NOTICE file distributed with
  this work for additional information regarding copyright ownership.
  The ASF licenses this file to You under the Apache License, Version 2.0
  (the "License"); you may not use this file except in compliance with
  the License. You may obtain a copy of the License at

      http://www.apache.org/licenses/LICENSE-2.0

  Unless required by applicable law or agreed to in writing, software
  distributed under the License is distributed on an "AS IS" BASIS,
  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
  See the License for the specific language governing permissions and
  limitations under the License.

-->

Found in path(s):
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/saga/package.html
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/package.html
*
 /camel-support-3-8-0-sources-1-jar/org/apache/camel/converter/stream/package.html
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/component/extension/metadata/package.html
* /camel-support-3-8-0-sources-1-jar/META-INF/maven/org.apache.camel/camel-support/pom.xml
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/component/extension/verifier/package.html
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/jndi/package.html
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/package.html
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at

*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/CamelContextHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/EventDrivenPollingConsumer.java
*
 /camel-support-3-8-0-sources-1-jar/org/apache/camel/component/ResourceEndpoint.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/AsyncProcessorSupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/builder/Namespaces.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/MessageHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ReactiveHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ScriptHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/saga/CamelSagaStep.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/builder/BinaryPredicateSupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/converter/stream/StreamCacheConverter.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/PropertyBindingSupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/cache/EventNotifierCallback.java
*
 /camel-support-3-8-0-sources-1-jar/org/apache/camel/component/extension/verifier/NoSuchOptionException.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ExpressionListComparator.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/converter/stream/InputStreamCache.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/MessageSupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/cache/PollingConsumerServicePool.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ChildServiceSupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/management/NotificationSenderAdapter.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/component/extension/verifier/IllegalOptionException.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/converter/stream/ByteArrayInputStreamCache.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/builder/ExpressionBuilder.java
*
 /camel-support-3-8-0-sources-1-
jar/org/apache/camel/component/extension/verifier/DefaultComponentVerifierExtension.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/InputStreamIterator.java
* /camel-support-3-8-0-sources-1-
jar/org/apache/camel/support/processor/idempotent/FileIdempotentRepository.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/EndpointUriFactorySupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultComponent.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/PropertyNamesInterceptor.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/jndi/JndiContext.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/processor/DelegateSyncProcessor.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/AbstractApiProducer.java

* /camel-support-3-8-0-sources-1-jar/org/apache/camel/converter/stream/CachedByteArrayOutputStream.java
*
 /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/IntrospectionSupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/TimeoutMapEntry.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultScheduledPollConsumer.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/ApiConsumerHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/startup/DefaultStartupStepRecorder.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/AbstractApiComponent.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/ApiMethodPropertiesHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/NoLock.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/builder/TokenXMLExpressionIterator.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ExchangeHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/jndi/JndiBeanRepository.java
*
 /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/GroupIterator.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultRegistry.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/language/AnnotationExpressionFactory.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/builder/PredicateBuilder.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/AsyncCallbackToCompletableFutureAdapter.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/PredicateToExpressionAdapter.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ExpressionAdapter.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultPollingConsumerPollStrategy.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/RestComponentHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/ApiCollection.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/ApiMethodArg.java
*
 /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/AbstractApiConfiguration.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultEndpointUtilizationStatistics.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultLRUCacheFactory.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/processor/CamelLogProcessor.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/GZIPHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/AsyncProcessorHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/SimpleTypeConverter.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/SimpleEventNotifierSupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/language/DefaultAnnotationExpressionFactory.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/LRUCache.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/AbstractApiEndpoint.java
*
 /camel-support-3-8-0-sources-1-jar/org/apache/camel/saga/InMemorySagaService.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/LifecycleStrategySupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/saga/CamelSagaCoordinator.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/jndi/CamelSingletonInitialContextFactory.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/BridgeExceptionHandlerToErrorHandler.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/CustomizersSupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/component/extension/verifier/OptionsGroup.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/GroupTokenIterator.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ResourceHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/startup/LoggingStartupStepRecorder.java

* /camel-support-3-8-0-sources-1-jar/org/apache/camel/throttling/ThrottlingExceptionHalfOpenHandler.java
*
 /camel-support-3-8-0-sources-1-
jar/org/apache/camel/support/processor/idempotent/MemoryIdempotentRepository.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/saga/CamelSagaService.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/ApiMethodHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultInterceptSendToEndpoint.java
* /camel-support-3-8-0-sources-1-
jar/org/apache/camel/component/extension/verifier/ComponentVerifierException.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/HeaderFilterStrategyComponent.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ExpressionComparator.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/processor/UnmarshalProcessor.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/component/extension/metadata/MetaDataBuilder.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ScheduledBatchPollingConsumer.java
*
 /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/cluster/ClusterServiceHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ObjectHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/PredicateAssertHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/processor/DefaultExchangeFormatter.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/SynchronizationAdapter.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/UnitOfWorkHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/LanguageSupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/component/extension/verifier/DefaultResult.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/PlatformHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/EventNotifierSupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/NormalizedUri.java
*
 /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/cache/ProducerServicePool.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/PropertyConfigurerSupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/component/extension/verifier/ResultBuilder.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/converter/stream/FileInputStreamCache.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/ApiMethod.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultTimeoutMap.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultPollingEndpoint.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/saga/InMemorySagaCoordinator.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/component/extension/verifier/ResultErrorHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/ApiMethodParser.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ExpressionSupport.java
*
 /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ProcessorPollingConsumer.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/VanillaUuidGenerator.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/BreakpointSupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/language/LanguageAnnotation.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/LazyStartProducer.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/PatternHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/AbstractApiConsumer.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultDataFormat.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/startup/DefaultStartupStep.java

* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/AsyncProcessorConverterHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/OrderedComparator.java
*
/camel-support-3-8-0-sources-1-jar/org/apache/camel/component/extension/verifier/ResultErrorBuilder.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/converter/stream/ReaderCache.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/converter/stream/CachedOutputStream.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/language/NamespacePrefix.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultScheduledPollConsumerScheduler.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/builder/TokenPairExpressionIterator.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/processor/DefaultMaskingFormatter.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ClassicUuidGenerator.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/EmptyAsyncCallback.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ExpressionToPredicateAdapter.java
*
/camel-support-3-8-0-sources-1-
jar/org/apache/camel/component/extension/verifier/DefaultResultVerificationError.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/SimpleUuidGenerator.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/LoggingExceptionHandler.java
* /camel-support-3-8-0-sources-1-
jar/org/apache/camel/support/management/DefaultManagementMBeanAssembler.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/processor/PredicateValidatingProcessor.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/cache/ServicePool.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultHeaderFilterStrategy.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultProducer.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultMessageHistory.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ConstantExpressionAdapter.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/TypedProcessorFactory.java
*
/camel-support-3-8-0-sources-1-jar/org/apache/camel/support/EventHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultThreadPoolFactory.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DeferProducer.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/SimpleRegistry.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/cluster/RebalancingCamelClusterService.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/processor/DelegateAsyncProcessor.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/converter/stream/CipherPair.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/EndpointHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ResolverHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/RestProducerFactoryHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/SynchronousDelegateProducer.java
*
/camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/ApiMethodImpl.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/SendDynamicAwareSupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/PropertyConfigurerHelper.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/cache/DefaultConsumerCache.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/cache/DefaultProducerCache.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/processor/MarshalProcessor.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/throttling/ThrottlingExceptionRoutePolicy.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/throttling/ThrottlingInflightRoutePolicy.java

* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultUuidGenerator.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultExchangeHolder.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ScheduledPollConsumer.java
*
 /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/TimerListenerManager.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultConsumer.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/cluster/AbstractCamelClusterService.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/processor/PredicateValidationException.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/builder/ValueBuilder.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/management/MBeanInfoAssembler.java
* /camel-support-3-8-0-sources-1-
jar/org/apache/camel/component/extension/metadata/AbstractMetaDataExtension.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/builder/RecordableInputStream.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultMessage.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/PollingConsumerSupport.java
*
 /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/RoutePolicySupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultExchange.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/cluster/ClusterServiceSelectors.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/CamelObjectInputStream.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/PropertiesInterceptor.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/TypeConverterSupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ScheduledPollEndpoint.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/builder/OutputStreamBuilder.java
* /camel-support-3-8-0-sources-1-
jar/org/apache/camel/component/extension/verifier/CatalogVerifierCustomizer.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/component/extension/metadata/DefaultMetaData.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultAsyncProducer.java
*
 /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/cluster/AbstractCamelClusterView.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/ResultInterceptor.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/processor/DelegateProcessor.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/jndi/CamelInitialContextFactory.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/processor/ConvertBodyProcessor.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/management/MixinRequiredModelMBean.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/HeaderSelectorProducer.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/DefaultEndpoint.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/cache/EmptyProducerCache.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/LRUCacheFactory.java
*
 /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/RoutesBuilderLoaderSupport.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/ProcessorEndpoint.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/RestConsumerContextPathMatcher.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/processor/ThroughputLogger.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/ApiName.java
* /camel-support-3-8-0-sources-1-jar/org/apache/camel/support/component/ArgumentSubstitutionParser.java

1.1106 camel-util 3.8.0

1.1106.1 Available under license :

No license file was found, but licenses were detected in source scan.

<!--

  Licensed to the Apache Software Foundation (ASF) under one or more
  contributor license agreements. See the NOTICE file distributed with
  this work for additional information regarding copyright ownership.
  The ASF licenses this file to You under the Apache License, Version 2.0
  (the "License"); you may not use this file except in compliance with
  the License. You may obtain a copy of the License at

      http://www.apache.org/licenses/LICENSE-2.0

  Unless required by applicable law or agreed to in writing, software
  distributed under the License is distributed on an "AS IS" BASIS,
  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
  See the License for the specific language governing permissions and
  limitations under the License.

-->

Found in path(s):
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/concurrent/package.html
* /camel-util-3-8-0-sources-1-jar/META-INF/maven/org.apache.camel/camel-util/pom.xml
*
 /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/package.html
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/backoff/package.html
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/function/package.html
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
*/

Found in path(s):
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/PropertiesHelper.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/SkipIterator.java
*
 /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/concurrent/RejectableFutureTask.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/Scanner.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/CollectionHelper.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/DoubleMap.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/backoff/BackOff.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/function/ThrowingBiFunction.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/function/ThrowingBiConsumer.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/ObjectHelper.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/ReferenceCount.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/URIScanner.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/KeyValueHolder.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/concurrent/SubmitOrderedCompletionService.java
*
 /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/function/ThrowingRunnable.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/FilterIterator.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/function/Predicates.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/concurrent/SynchronousExecutorService.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/concurrent/LockHelper.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/InetAddressUtil.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/IOHelper.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/CastUtils.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/StreamUtils.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/function/Suppliers.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/backoff/BackOffTimerTask.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/CaseInsensitiveMap.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/AntPathMatcher.java
*
 /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/HostUtils.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/UnsafeUriCharactersEncoder.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/concurrent/RejectableScheduledThreadPoolExecutor.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/function/Bindings.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/function/ThrowingTriConsumer.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/TimeUtils.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/concurrent/SizedScheduledExecutorService.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/function/TriConsumer.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/Pair.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/OgnlHelper.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/concurrent/RejectableThreadPoolExecutor.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/CamelURIParser.java
*

/camel-util-3-8-0-sources-1-jar/org/apache/camel/util/OrderedProperties.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/URISupport.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/backoff/BackOffTimer.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/FilePathResolver.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/FileUtil.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/IntrospectionSupport.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/UnitUtils.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/StringHelper.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/ReflectionHelper.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/StringQuoteHelper.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/SensitiveUtils.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/concurrent/ThreadHelper.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/concurrent/Rejectable.java
*
/camel-util-3-8-0-sources-1-jar/org/apache/camel/util/concurrent/AsyncCompletionService.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/BufferCaster.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/function/ThrowingConsumer.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/function/ThrowingToLongFunction.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/function/ThrowingFunction.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/StopWatch.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/concurrent/CamelThreadFactory.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/function/ThrowingHelper.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/concurrent/ThreadPoolRejectedPolicy.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/function/ThrowingSupplier.java
* /camel-util-3-8-0-sources-1-jar/org/apache/camel/util/CollectionStringBuffer.java
*
/camel-util-3-8-0-sources-1-jar/org/apache/camel/util/PackageHelper.java

1.1107 printj 1.1.2

1.1107.1 Available under license :

Apache License 2.0
Copyright (C) 2016-present SheetJS

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1108 punycode 2.3.0

1.1108.1 Available under license :

Copyright Mathias Bynens <https://mathiasbynens.be/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1109 http-cache-semantics 4.1.1

1.1109.1 Available under license :

BSD-2-Clause
Copyright 2016-2018 Kornel Lesiski

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS

OF USE, DATA,
OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1110 jackson-datatype-jsr310 2.12.7

1.1110.1 Available under license :

This copy of Jackson JSON processor streaming parser/generator is licensed under the
Apache (Software) License, version 2.0 ("the License").
See the License for details about distribution rights, and the
specific rights regarding derivate works.

You may obtain a copy of the License at:

http://www.apache.org/licenses/LICENSE-2.0

1.1111 ssf 0.11.2

1.1111.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and

do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all

other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "{}"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright (C) 2013-present SheetJS LLC

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache License 2.0

1.1112 wmf 1.0.2

1.1112.1 Available under license :

Apache License 2.0

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain

separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without

modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "{}"
replaced with your own identifying information. (Don't include

the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright (C) 2020-present SheetJS LLC

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1113 internal-slot 1.0.5

1.1113.1 Available under license :

MIT License

Copyright (c) 2019 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1114 minimist 1.2.8

1.1114.1 Available under license :

This software is released under the MIT license:

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS
FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR
COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER
IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1115 babel-plugin-proposal-optional-chaining 7.21.0

1.1115.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1116 is-array-buffer 3.0.2

1.1116.1 Available under license :

MIT License

Copyright (c) 2015 Chen Gengyuan, Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1117 css-to-react-native 3.2.0

1.1117.1 Available under license :

MIT License

Copyright (c) 2016 Jacob Parker and Maximilian Stoiber

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights

to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1118 classmate 1.0.0

1.1118.1 Available under license :

This copy of Java ClassMate library is licensed under Apache (Software) License,
version 2.0 ("the License").
See the License for details about distribution rights, and the specific rights regarding derivate works.

You may obtain a copy of the License at:

http://www.apache.org/licenses/LICENSE-2.0
Java ClassMate library was originally written by Tatu Saloranta (tatu.saloranta@iki.fi)

Other developers who have contributed code are:

* Brian Langel

1.1119 spdx-correct 3.2.0

1.1119.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,

and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to

communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and

attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or

implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1120 checker-qual 3.31.0

1.1120.1 Available under license :

Checker Framework qualifiers
Copyright 2004-present by the Checker Framework developers

MIT License:

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1121 spdx-license-ids 3.0.13

1.1121.1 Available under license :

[
"AGPL-1.0",
"AGPL-3.0",
"BSD-2-Clause-FreeBSD",
"BSD-2-Clause-NetBSD",
"GFDL-1.1",
"GFDL-1.2",

"GFDL-1.3",
"GPL-1.0",
"GPL-2.0",
"GPL-2.0-with-GCC-exception",
"GPL-2.0-with-autoconf-exception",
"GPL-2.0-with-bison-exception",
"GPL-2.0-with-classpath-exception",
"GPL-2.0-with-font-exception",
"GPL-3.0",
"GPL-3.0-with-GCC-exception",
"GPL-3.0-with-autoconf-exception",
"LGPL-2.0",
"LGPL-2.1",
"LGPL-3.0",
"Nunit",
"StandardML-NJ",
"bzip2-1.0.5",
"eCos-2.0",
"wxWindows"
]
Creative Commons CC0
[
"0BSD",
"AAL",
"ADSL",
"AFL-1.1",
"AFL-1.2",
"AFL-2.0",
"AFL-2.1",
"AFL-3.0",
"AGPL-1.0-only",
"AGPL-1.0-or-later",
"AGPL-3.0-only",
"AGPL-3.0-or-later",
"AMDPLPA",
"AML",
"AMPAS",
"ANTLR-PD",
"ANTLR-PD-fallback",
"APAFML",
"APL-1.0",
"APSL-1.0",
"APSL-1.1",
"APSL-1.2",
"APSL-2.0",
"Abstyles",
"AdaCore-doc",
"Adobe-2006",

"Adobe-Glyph",
"Afmparse",
"Aladdin",
"Apache-1.0",
"Apache-1.1",
"Apache-2.0",
"App-s2p",
"Arphic-1999",
"Artistic-1.0",
"Artistic-1.0-Perl",
"Artistic-1.0-cl8",
"Artistic-2.0",
"BSD-1-Clause",
"BSD-2-Clause",
"BSD-2-Clause-Patent",
"BSD-2-Clause-Views",
"BSD-3-Clause",
"BSD-3-Clause-Attribution",
"BSD-3-Clause-Clear",
"BSD-3-Clause-LBNL",
"BSD-3-Clause-Modification",
"BSD-3-Clause-No-Military-License",
"BSD-3-Clause-No-Nuclear-License",
"BSD-3-Clause-No-Nuclear-License-2014",
"BSD-3-Clause-No-Nuclear-Warranty",
"BSD-3-Clause-Open-MPI",
"BSD-4-Clause",
"BSD-4-Clause-Shortened",
"BSD-4-Clause-UC",
"BSD-4.3RENO",
"BSD-4.3TAHOE",
"BSD-Advertising-Acknowledgement",
"BSD-Attribution-HPND-disclaimer",
"BSD-Protection",
"BSD-Source-Code",
"BSL-1.0",
"BUSL-1.1",
"Baekmuk",
"Bahyph",
"Barr",
"Beerware",
"BitTorrent-1.0",
"BitTorrent-1.1",
"Bitstream-Charter",
"Bitstream-Vera",
"BlueOak-1.0.0",
"Borceux",
"Brian-Gladman-3-Clause",

"C-UDA-1.0",
"CAL-1.0",
"CAL-1.0-Combined-Work-Exception",
"CATOSL-1.1",
"CC-BY-1.0",
"CC-BY-2.0",
"CC-BY-2.5",
"CC-BY-2.5-AU",
"CC-BY-3.0",
"CC-BY-3.0-AT",
"CC-BY-3.0-DE",
"CC-BY-3.0-IGO",
"CC-BY-3.0-NL",
"CC-BY-3.0-US",
"CC-BY-4.0",
"CC-BY-NC-1.0",
"CC-BY-NC-2.0",
"CC-BY-NC-2.5",
"CC-BY-NC-3.0",
"CC-BY-NC-3.0-DE",
"CC-BY-NC-4.0",
"CC-BY-NC-ND-1.0",
"CC-BY-NC-ND-2.0",
"CC-BY-NC-ND-2.5",
"CC-BY-NC-ND-3.0",
"CC-BY-NC-ND-3.0-DE",
"CC-BY-NC-ND-3.0-IGO",
"CC-BY-NC-ND-4.0",
"CC-BY-NC-SA-1.0",
"CC-BY-NC-SA-2.0",
"CC-BY-NC-SA-2.0-DE",
"CC-BY-NC-SA-2.0-FR",
"CC-BY-NC-SA-2.0-UK",
"CC-BY-NC-SA-2.5",
"CC-BY-NC-SA-3.0",
"CC-BY-NC-SA-3.0-DE",
"CC-BY-NC-SA-3.0-IGO",
"CC-BY-NC-SA-4.0",
"CC-BY-ND-1.0",
"CC-BY-ND-2.0",
"CC-BY-ND-2.5",
"CC-BY-ND-3.0",
"CC-BY-ND-3.0-DE",
"CC-BY-ND-4.0",
"CC-BY-SA-1.0",
"CC-BY-SA-2.0",
"CC-BY-SA-2.0-UK",
"CC-BY-SA-2.1-JP",

"CC-BY-SA-2.5",
"CC-BY-SA-3.0",
"CC-BY-SA-3.0-AT",
"CC-BY-SA-3.0-DE",
"CC-BY-SA-4.0",
"CC-PDDC",
"CC0-1.0",
"CDDL-1.0",
"CDDL-1.1",
"CDL-1.0",
"CDLA-Permissive-1.0",
"CDLA-Permissive-2.0",
"CDLA-Sharing-1.0",
"CECILL-1.0",
"CECILL-1.1",
"CECILL-2.0",
"CECILL-2.1",
"CECILL-B",
"CECILL-C",
"CERN-OHL-1.1",
"CERN-OHL-1.2",
"CERN-OHL-P-2.0",
"CERN-OHL-S-2.0",
"CERN-OHL-W-2.0",
"CFITSIO",
"CMU-Mach",
"CNRI-Jython",
"CNRI-Python",
"CNRI-Python-GPL-Compatible",
"COIL-1.0",
"CPAL-1.0",
"CPL-1.0",
"CPOL-1.02",
"CUA-OPL-1.0",
"Caldera",
"ClArtistic",
"Clips",
"Community-Spec-1.0",
"Condor-1.1",
"Cornell-Lossless-JPEG",
"Crossword",
"CrystalStacker",
"Cube",
"D-FSL-1.0",
"DL-DE-BY-2.0",
"DOC",
"DRL-1.0",
"DSDP",

"Dotseqn",
"ECL-1.0",
"ECL-2.0",
"EFL-1.0",
"EFL-2.0",
"EPICS",
"EPL-1.0",
"EPL-2.0",
"EUDatagrid",
"EUPL-1.0",
"EUPL-1.1",
"EUPL-1.2",
"Elastic-2.0",
"Entessa",
"ErlPL-1.1",
"Eurosym",
"FDK-AAC",
"FSFAP",
"FSFUL",
"FSFULLR",
"FSFULLRWD",
"FTL",
"Fair",
"Frameworx-1.0",
"FreeBSD-DOC",
"FreeImage",
"GD",
"GFDL-1.1-invariants-only",
"GFDL-1.1-invariants-or-later",
"GFDL-1.1-no-invariants-only",
"GFDL-1.1-no-invariants-or-later",
"GFDL-1.1-only",
"GFDL-1.1-or-later",
"GFDL-1.2-invariants-only",
"GFDL-1.2-invariants-or-later",
"GFDL-1.2-no-invariants-only",
"GFDL-1.2-no-invariants-or-later",
"GFDL-1.2-only",
"GFDL-1.2-or-later",
"GFDL-1.3-invariants-only",
"GFDL-1.3-invariants-or-later",
"GFDL-1.3-no-invariants-only",
"GFDL-1.3-no-invariants-or-later",
"GFDL-1.3-only",
"GFDL-1.3-or-later",
"GL2PS",
"GLWTPL",
"GPL-1.0-only",

"GPL-1.0-or-later",
"GPL-2.0-only",
"GPL-2.0-or-later",
"GPL-3.0-only",
"GPL-3.0-or-later",
"Giftware",
"Glide",
"Glulxe",
"Graphics-Gems",
"HP-1986",
"HPND",
"HPND-Markus-Kuhn",
"HPND-export-US",
"HPND-sell-variant",
"HPND-sell-variant-MIT-disclaimer",
"HTMLTIDY",
"HaskellReport",
"Hippocratic-2.1",
"IBM-pibs",
"ICU",
"IEC-Code-Components-EULA",
"IJG",
"IJG-short",
"IPA",
"IPL-1.0",
"ISC",
"ImageMagick",
"Imlib2",
"Info-ZIP",
"Intel",
"Intel-ACPI",
"Interbase-1.0",
"JPL-image",
"JPNIC",
"JSON",
"Jam",
"JasPer-2.0",
"Kazlib",
"Knuth-CTAN",
"LAL-1.2",
"LAL-1.3",
"LGPL-2.0-only",
"LGPL-2.0-or-later",
"LGPL-2.1-only",
"LGPL-2.1-or-later",
"LGPL-3.0-only",
"LGPL-3.0-or-later",
"LGPLLR",

"LOOP",
"LPL-1.0",
"LPL-1.02",
"LPPL-1.0",
"LPPL-1.1",
"LPPL-1.2",
"LPPL-1.3a",
"LPPL-1.3c",
"LZMA-SDK-9.11-to-9.20",
"LZMA-SDK-9.22",
"Latex2e",
"Leptonica",
"LiLiQ-P-1.1",
"LiLiQ-R-1.1",
"LiLiQ-Rplus-1.1",
"Libpng",
"Linux-OpenIB",
"Linux-man-pages-copyleft",
"MIT",
"MIT-0",
"MIT-CMU",
"MIT-Modern-Variant",
"MIT-Wu",
"MIT-advertising",
"MIT-enna",
"MIT-feh",
"MIT-open-group",
"MITNFA",
"MPL-1.0",
"MPL-1.1",
"MPL-2.0",
"MPL-2.0-no-copyleft-exception",
"MS-LPL",
"MS-PL",
"MS-RL",
"MTLL",
"MakeIndex",
"Martin-Birgmeier",
"Minpack",
"MirOS",
"Motosoto",
"MulanPSL-1.0",
"MulanPSL-2.0",
"Multics",
"Mup",
"NAIST-2003",
"NASA-1.3",
"NBPL-1.0",

"NCGL-UK-2.0",
"NCSA",
"NGPL",
"NICTA-1.0",
"NIST-PD",
"NIST-PD-fallback",
"NLOD-1.0",
"NLOD-2.0",
"NLPL",
"NOSL",
"NPL-1.0",
"NPL-1.1",
"NPOSL-3.0",
"NRL",
"NTP",
"NTP-0",
"Naumen",
"Net-SNMP",
"NetCDF",
"Newsletr",
"Nokia",
"Noweb",
"O-UDA-1.0",
"OCCT-PL",
"OCLC-2.0",
"ODC-By-1.0",
"ODbL-1.0",
"OFFIS",
"OFL-1.0",
"OFL-1.0-RFN",
"OFL-1.0-no-RFN",
"OFL-1.1",
"OFL-1.1-RFN",
"OFL-1.1-no-RFN",
"OGC-1.0",
"OGDL-Taiwan-1.0",
"OGL-Canada-2.0",
"OGL-UK-1.0",
"OGL-UK-2.0",
"OGL-UK-3.0",
"OGTSL",
"OLDAP-1.1",
"OLDAP-1.2",
"OLDAP-1.3",
"OLDAP-1.4",
"OLDAP-2.0",
"OLDAP-2.0.1",
"OLDAP-2.1",

"OLDAP-2.2",
"OLDAP-2.2.1",
"OLDAP-2.2.2",
"OLDAP-2.3",
"OLDAP-2.4",
"OLDAP-2.5",
"OLDAP-2.6",
"OLDAP-2.7",
"OLDAP-2.8",
"OML",
"OPL-1.0",
"OPUBL-1.0",
"OSET-PL-2.1",
"OSL-1.0",
"OSL-1.1",
"OSL-2.0",
"OSL-2.1",
"OSL-3.0",
"OpenPBS-2.3",
"OpenSSL",
"PDDL-1.0",
"PHP-3.0",
"PHP-3.01",
"PSF-2.0",
"Parity-6.0.0",
"Parity-7.0.0",
"Plexus",
"PolyForm-Noncommercial-1.0.0",
"PolyForm-Small-Business-1.0.0",
"PostgreSQL",
"Python-2.0",
"Python-2.0.1",
"QPL-1.0",
"QPL-1.0-INRIA-2004",
"Qhull",
"RHeCos-1.1",
"RPL-1.1",
"RPL-1.5",
"RPSL-1.0",
"RSA-MD",
"RSCPL",
"Rdisc",
"Ruby",
"SAX-PD",
"SCEA",
"SGI-B-1.0",
"SGI-B-1.1",
"SGI-B-2.0",

"SHL-0.5",
"SHL-0.51",
"SISSL",
"SISSL-1.2",
"SMLNJ",
"SMPPL",
"SNIA",
"SPL-1.0",
"SSH-OpenSSH",
"SSH-short",
"SSPL-1.0",
"SWL",
"Saxpath",
"SchemeReport",
"Sendmail",
"Sendmail-8.23",
"SimPL-2.0",
"Sleepycat",
"Spencer-86",
"Spencer-94",
"Spencer-99",
"SugarCRM-1.1.3",
"SunPro",
"Symlinks",
"TAPR-OHL-1.0",
"TCL",
"TCP-wrappers",
"TMate",
"TORQUE-1.1",
"TOSL",
"TPDL",
"TPL-1.0",
"TTWL",
"TU-Berlin-1.0",
"TU-Berlin-2.0",
"UCAR",
"UCL-1.0",
"UPL-1.0",
"Unicode-DFS-2015",
"Unicode-DFS-2016",
"Unicode-TOU",
"Unlicense",
"VOSTROM",
"VSL-1.0",
"Vim",
"W3C",
"W3C-19980720",
"W3C-20150513",

"WTFPL",
"Watcom-1.0",
"Wsuipa",
"X11",
"X11-distribute-modifications-variant",
"XFree86-1.1",
"XSkat",
"Xerox",
"Xnet",
"YPL-1.0",
"YPL-1.1",
"ZPL-1.1",
"ZPL-2.0",
"ZPL-2.1",
"Zed",
"Zend-2.0",
"Zimbra-1.3",
"Zimbra-1.4",
"Zlib",
"blessing",
"bzip2-1.0.6",
"checkmk",
"copyleft-next-0.3.0",
"copyleft-next-0.3.1",
"curl",
"diffmark",
"dvipdfm",
"eGenix",
"etalab-2.0",
"gSOAP-1.3b",
"gnuplot",
"iMatix",
"libpng-2.0",
"libselinux-1.0",
"libtiff",
"libutil-David-Nugent",
"mpi-permissive",
"mpich2",
"mplus",
"psfrag",
"psutils",
"snprintf",
"w3m",
"xinetd",
"xlock",
"xpp",
"zlib-acknowledgement"
]

spdx-license-ids

[![npm version](https://img.shields.io/npm/v/spdx-license-ids.svg)](https://www.npmjs.com/package/spdx-license-ids)
[![Github Actions](https://action-badges.now.sh/jslicense/spdx-license-ids)](https://wdp9fww0r9.execute-api.us-west-2.amazonaws.com/production/results/jslicense/spdx-license-ids)

A list of [SPDX license](https://spdx.org/licenses/) identifiers

Installation

[Download JSON directly](https://raw.githubusercontent.com/jslicense/spdx-license-ids/main/index.json), or [use](https://docs.npmjs.com/cli/install) [npm](https://docs.npmjs.com/about-npm/):

```
npm install spdx-license-ids
```

[Node.js](https://nodejs.org/) API

require('spdx-license-ids')

Type: `string[]`

All license IDs except for the currently deprecated ones.

```javascript
const ids = require('spdx-license-ids');
//=> ['0BSD', 'AAL', 'ADSL', 'AFL-1.1', 'AFL-1.2', 'AFL-2.0', 'AFL-2.1', 'AFL-3.0', 'AGPL-1.0-only', ...]

ids.includes('BSD-3-Clause'); //=> true
ids.includes('CC-BY-1.0');
 //=> true

ids.includes('GPL-3.0'); //=> false
```

require('spdx-license-ids/deprecated')

Type: `string[]`

Deprecated license IDs.

```javascript
const deprecatedIds = require('spdx-license-ids/deprecated');
//=> ['AGPL-1.0', 'AGPL-3.0', 'GFDL-1.1', 'GFDL-1.2', 'GFDL-1.3', 'GPL-1.0', 'GPL-2.0', ...]

deprecatedIds.includes('BSD-3-Clause'); //=> false
```

deprecatedIds.includes('CC-BY-1.0'); //=> false

deprecatedIds.includes('GPL-3.0'); //=> true
```

## License

[Creative Commons Zero v1.0 Universal](https://creativecommons.org/publicdomain/zero/1.0/deed)

# 1.1122 handlebars-loader 1.7.3

## 1.1122.1 Available under license :

MIT

# 1.1123 regexpu-core 5.3.2

## 1.1123.1 Available under license :

Copyright Mathias Bynens <https://mathiasbynens.be/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
 CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

# 1.1124 array-buffer-byte-length 1.0.0

## 1.1124.1 Available under license :

MIT License

Copyright (c) 2023 Inspect JS
```

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1125 grpc-protobuf 1.9.0

1.1125.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014, gRPC Authors All rights reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /grpc-protobuf-1-9-0-sources-1-jar/io/grpc/protobuf/ProtoUtils.java
No license file was found, but licenses were detected in source scan.

/*

* Copyright 2017, gRPC Authors All rights reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /grpc-protobuf-1-9-0-sources-1-jar/io/grpc/protobuf/StatusProto.java
* /grpc-protobuf-1-9-0-sources-1-jar/io/grpc/protobuf/ProtoServiceDescriptorSupplier.java
* /grpc-protobuf-1-9-0-sources-1-jar/io/grpc/protobuf/package-info.java
* /grpc-protobuf-1-9-0-sources-1-jar/io/grpc/protobuf/ProtoMethodDescriptorSupplier.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016, gRPC Authors All rights reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /grpc-protobuf-1-9-0-sources-1-jar/io/grpc/protobuf/ProtoFileDescriptorSupplier.java

1.1126 grpc-netty 1.9.0

1.1126.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*

```
* Copyright 2016, gRPC Authors All rights reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless
 required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/GrpcHttp2HeadersUtils.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016, gRPC Authors All rights reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
```

* limitations under the License.
*/

Found in path(s):
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/GrpcHttp2ConnectionHandler.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/GracefulCloseCommand.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/ClientTransportLifecycleManager.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/StreamIdHolder.java
*
 /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/InternalHandlerSettings.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/InternalNettyServerBuilder.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/HandlerSettings.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/InternalNettyChannelBuilder.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/ForcefulCloseCommand.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/GrpcHttp2OutboundHeaders.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/AbstractHttp2Headers.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NettyHandlerSettings.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015, gRPC Authors All rights reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NettyWritableBuffer.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NettyWritableBufferAllocator.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/package-info.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NettyChannelProvider.java
*
 /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/CancelServerStreamCommand.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/AbstractNettyHandler.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/JettyTlsUtil.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NettyServerProvider.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/WriteQueue.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NettyClientStream.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/GrpcSslContexts.java

* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/ProtocolNegotiators.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/SendPingCommand.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/ProtocolNegotiator.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017, gRPC Authors All rights reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/MaxConnectionIdleManager.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/KeepAliveEnforcer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014, gRPC Authors All rights reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NettyClientTransport.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NettyClientHandler.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/SendResponseHeadersCommand.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NegotiationType.java
*

/grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/CreateStreamCommand.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/CancelClientStreamCommand.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NettyServerHandler.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/Utils.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NettyReadableBuffer.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NettyServerBuilder.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NettyServerStream.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NettyChannelBuilder.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/SendGrpcFrameCommand.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NettyServerTransport.java
* /grpc-netty-1-9-0-sources-1-jar/io/grpc/netty/NettyServer.java

1.1127 uuid-creator 5.2.0

1.1127.1 Available under license :

No license file was found, but licenses were detected in source scan.

<name>MIT License</name>

Found in path(s):
* /uuid-creator-5-2-0-sources-jar/META-INF/maven/com.github.f4b6a3/uuid-creator/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* MIT License
*
* Copyright (c) 2018-2022 Fabio Lima
*
* Permission is hereby granted, free of charge, to any person obtaining a copy
* of this software and associated documentation files (the "Software"), to deal
* in the Software without restriction, including without limitation the rights
* to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
* copies of the Software, and to permit persons to whom the Software is
* furnished to do so, subject to the following conditions:
*
* The above copyright notice and this permission notice shall be included in all
* copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
* IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
* FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
* AUTHORS OR COPYRIGHT HOLDERS BE LIABLE
FOR ANY CLAIM, DAMAGES OR OTHER
* LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
* OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
* SOFTWARE.
*/

Found in path(s):
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/rfc4122/NameBasedSha1Factory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/util/UuidComparator.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/Base62Codec.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/function/ClockSeqFunction.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/util/internal/RandomUtil.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/Base64Codec.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/other/NcnameCodec.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/enums/UuidVersion.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/function/impl/DefaultTimeFunction.java
*
 /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/Base32Codec.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/util/UuidTime.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/function/impl/DefaultClockSeqFunction.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/rfc4122/TimeOrderedFactory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/exception/InvalidUuidException.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/enums/UuidLocalDomain.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/AbstRandomBasedFactory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/NoArgsFactory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/rfc4122/DceSecurityFactory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/rfc4122/TimeOrderedEpochFactory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/BaseNCodec.java
*
 /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/nonstandard/PrefixCombFactory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/util/MachineId.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/function/Base32Encoder.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/UuidFactory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/function/RandomFunction.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/util/UuidValidator.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/BaseN.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/function/impl/HashNodeIdFunction.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/other/DotNetGuid4Codec.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/other/TimeOrderedCodec.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/Base64UrlCodec.java
*
 /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/function/NodeIdFunction.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/util/immutable/CharArray.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/function/BaseNRemainderDecoder.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/function/Base16Encoder.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/nonstandard/ShortSuffixCombFactory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/function/Base16Decoder.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/BinaryCodec.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/Base16Codec.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/AbstTimeBasedFactory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/UuidCreator.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/nonstandard/ShortPrefixCombFactory.java
*

/uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/util/internal/SettingsUtil.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/function/impl/DefaultNodeIdFunction.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/rfc4122/NameBasedMd5Factory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/enums/UuidVariant.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/StringCodec.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/util/immutable/LongArray.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/UrnCodec.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/other/DotNetGuid1Codec.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/function/impl/MacNodeIdFunction.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/Base58BtcCodec.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/function/impl/DefaultRandomFunction.java
*
/uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/util/CombUtil.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/UriCodec.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/function/BaseNEncoder.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/rfc4122/RandomBasedFactory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/util/internal/NetworkUtil.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/enums/UuidNamespace.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/function/impl/RandomNodeIdFunction.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/util/UuidUtil.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/function/Base64Decoder.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/util/internal/ByteUtil.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/other/SlugCodec.java
*
/uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/function/impl/WindowsTimeFunction.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/UuidCodec.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/function/Base64Encoder.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/function/TimeFunction.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/nonstandard/SuffixCombFactory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/AbstCombFactory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/function/Base32Decoder.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/rfc4122/TimeBasedFactory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/factory/AbstNameBasedFactory.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/function/BaseNRemainderEncoder.java
* /uuid-creator-5-2-0-sources-jar/com/github/f4b6a3/uuid/codec/base/function/BaseNDecoder.java

1.1128 update-browserslist-db 1.0.11

1.1128.1 Available under license :

The MIT License (MIT)

Copyright 2022 Andrey Sitnik <andrey@sitnik.ru> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of

the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1129 immutability-helper 3.1.1

1.1129.1 Available under license :

MIT License

Copyright (c) 2017 Moshe Kolodny

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1130 date-fns 2.30.0

1.1130.1 Available under license :

MIT License

Copyright (c) 2021 Sasha Koss and Lesha Koss https://kossnocorp.mit-license.org

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1131 postcss-selector-parser 6.0.13

1.1131.1 Available under license :

Copyright (c) Ben Briggs <beneb.info@gmail.com> (http://beneb.info)

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,

WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1132 postgre-sql 42.6.0

1.1132.1 Available under license :

Copyright (c) 1997, PostgreSQL Global Development Group
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice,
this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice,
this list of conditions and the following disclaimer in the documentation
and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE
GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1133 resilience4j-ratelimiter 1.7.1

1.1133.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
*
* Copyright 2016 Robert Winkler and Bohdan Storozhuk
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at

*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
*
*/

Found in path(s):
* /resilience4j-ratelimiter-1-7-1-sources-3-
jar/io/github/resilience4j/ratelimiter/internal/SemaphoreBasedRateLimiter.java
* /resilience4j-ratelimiter-1-7-1-sources-3-jar/io/github/resilience4j/ratelimiter/internal/AtomicRateLimiter.java
* /resilience4j-ratelimiter-1-7-1-sources-3-
jar/io/github/resilience4j/ratelimiter/event/RateLimiterOnSuccessEvent.java
*
 /resilience4j-ratelimiter-1-7-1-sources-3-
jar/io/github/resilience4j/ratelimiter/internal/InMemoryRateLimiterRegistry.java
* /resilience4j-ratelimiter-1-7-1-sources-3-jar/io/github/resilience4j/ratelimiter/event/AbstractRateLimiterEvent.java
* /resilience4j-ratelimiter-1-7-1-sources-3-jar/io/github/resilience4j/ratelimiter/RateLimiter.java
* /resilience4j-ratelimiter-1-7-1-sources-3-jar/io/github/resilience4j/ratelimiter/event/RateLimiterEvent.java
* /resilience4j-ratelimiter-1-7-1-sources-3-
jar/io/github/resilience4j/ratelimiter/event/RateLimiterOnFailureEvent.java
* /resilience4j-ratelimiter-1-7-1-sources-3-jar/io/github/resilience4j/ratelimiter/RateLimiterConfig.java
* /resilience4j-ratelimiter-1-7-1-sources-3-jar/io/github/resilience4j/ratelimiter/RequestNotPermitted.java
* /resilience4j-ratelimiter-1-7-1-sources-3-
jar/io/github/resilience4j/ratelimiter/event/RateLimiterOnDrainedEvent.java
* /resilience4j-ratelimiter-1-7-1-sources-3-
jar/io/github/resilience4j/ratelimiter/internal/RateLimiterEventProcessor.java
*
 /resilience4j-ratelimiter-1-7-1-sources-3-jar/io/github/resilience4j/ratelimiter/RateLimiterRegistry.java
No license file was found, but licenses were detected in source scan.

/*
*
* Copyright 2018: Clint Checketts
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
*
*/

Found in path(s):
* /resilience4j-ratelimiter-1-7-1-sources-3-jar/io/github/resilience4j/ratelimiter/event/package-info.java
* /resilience4j-ratelimiter-1-7-1-sources-3-jar/io/github/resilience4j/ratelimiter/utils/package-info.java
* /resilience4j-ratelimiter-1-7-1-sources-3-jar/io/github/resilience4j/ratelimiter/internal/package-info.java
*
/resilience4j-ratelimiter-1-7-1-sources-3-jar/io/github/resilience4j/ratelimiter/package-info.java

1.1134 babel-plugin-syntax-flow 7.22.5

1.1134.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1135 babel-plugin-transform-property-literals 7.22.5

1.1135.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1136 babel-plugin-transform-reserved-words 7.22.5

1.1136.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1137 babel-plugin-syntax-typescript 7.22.5

1.1137.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1138 babel-plugin-transform-member-expression-literals 7.22.5

1.1138.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1139 babel-plugin-transform-flow-strip-types 7.22.5

1.1139.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE

LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1140 html-entities 2.4.0

1.1140.1 Available under license :

MIT
Copyright (c) 2021 Dulin Marat

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1141 semver 5.7.2

1.1141.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN

ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.1142 typed-array-byte-offset 1.0.0

1.1142.1 Available under license :

MIT License

Copyright (c) 2020 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1143 babel-plugin-styled-components 2.1.4

1.1143.1 Available under license :

MIT
MIT License

Copyright (c) 2016-present Vladimir Danchenkov and Maximilian Stoiber

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all

copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1144 styled-components 5.3.11

1.1144.1 Available under license :

No license file was found, but licenses were detected in source scan.

{"version":3,"file":"styled-components.browser.cjs.js","sources":["../src/utils/interleave.js","../src/utils/isPlainObject.js","../src/utils/empties.js","../src/utils/isFunction.js","../src/utils/getComponentName.js","../src/utils/isStyledComponent.js","../src/constants.js","../src/utils/error.js","../src/utils/errors.js","../src/sheet/GroupedTag.js","../src/sheet/GroupIDAllocator.js","../src/sheet/Rehydration.js","../src/utils/nonce.js","../src/sheet/dom.js","../src/sheet/Tag.js","../src/sheet/Sheet.js","../src/utils/generateAlphabeticName.js","../src/utils/hash.js","../src/utils/isStaticRules.js","../src/models/ComponentStyle.js","../src/utils/stylis.js","../src/utils/stylisPluginInsertRule.js","../src/models/StyleSheetManager.js","../src/models/Keyframes.js","../src/utils/hyphenateStyleName.js","../src/utils/flatten.js","../src/utils/isStatelessFunction.js","../src/utils/addUnitIfNeeded.js","../src/constructors/css.js","../src/utils/checkDynamicCreation.js","../src/utils/determineTheme.js","../src/utils/escape.js","../src/utils/generateComponentId.js","../src/utils/isTag.js","../src/utils/mixinDeep.js","../src/models/ThemeProvider.js","../src/models/StyledComponent.js","../src/utils/generateDisplayName.js","../src/utils/joinStrings.js","../src/utils/createWarnTooManyClasses.js","../src/utils/domElements.js","../src/constructors/styled.js","../src/constructors/constructWithOptions.js","../src/models/GlobalStyle.js","../src/models/ServerStyleSheet.js","../src/secretInternals.js","../src/base.js","../src/constructors/createGlobalStyle.js","../src/constructors/keyframes.js","../src/hooks/useTheme.js","../src/hoc/withTheme.js"],"sourcesContent":["// @flow\nimport type { Interpolation } from '../types';\n\nexport default (\n strings: Array<string>,\n interpolations: Array<Interpolation>\n): Array<Interpolation> => {\n const result = [strings[0]];\n\n for (let i = 0, len = interpolations.length; i < len; i += 1) {\n result.push(interpolations[i], strings[i + 1]);\n }\n\n return result;\n};\n","// @flow\nimport { typeOf } from 'react-is';\n\nexport default (x: any): boolean =>\n x !== null &&\n typeof x === 'object' &&\n (x.toString ? x.toString() : Object.prototype.toString.call(x)) === '[object Object]' &&\n !typeOf(x);\n","// @flow\nexport const EMPTY_ARRAY = Object.freeze([]);\nexport const EMPTY_OBJECT = Object.freeze({});\n","// @flow\nexport default function isFunction(test: any): boolean %checks {\n return typeof test === 'function';\n}\n","// @flow\nimport type { IStyledComponent } from '../types';\n\nexport default function getComponentName(\n target: $PropertyType<IStyledComponent, 'target'>\n): string {\n return (\n (process.env.NODE_ENV !== 'production' ? typeof target === 'string' && target : false) ||\n // $FlowFixMe\n target.displayName ||\n // $FlowFixMe\n target.name ||\n 'Component'\n);\n}\n","// @flow\nexport default function isStyledComponent(target: any): boolean %checks {\n return target && typeof target.styledComponentId === 'string';\n}\n","// @flow\n\ndeclare var SC_DISABLE_SPEEDY: ?boolean;\ndeclare var __VERSION__: string;\n\nexport const SC_ATTR: string =\n (typeof process !== 'undefined' &&\n typeof process.env !== 'undefined' &&

(process.env.REACT_APP_SC_ATTR || process.env.SC_ATTR)) ||\n 'data-styled';\n\nexport const SC_ATTR_ACTIVE = 'active';\nexport const SC_ATTR_VERSION = 'data-styled-version';\nexport const SC_VERSION = __VERSION__;\nexport const SPLITTER = '/*!sc*/\\n';\n\nexport const IS_BROWSER = typeof window !== 'undefined' && 'HTMLElement' in window;\n\nexport const DISABLE_SPEEDY = Boolean(\n typeof SC_DISABLE_SPEEDY === 'boolean'\n   ? SC_DISABLE_SPEEDY\n   : typeof process !== 'undefined' && typeof process.env !== 'undefined'\n   ? typeof process.env.REACT_APP_SC_DISABLE_SPEEDY !== 'undefined' &&\n   process.env.REACT_APP_SC_DISABLE_SPEEDY !== ''\n   ? process.env.REACT_APP_SC_DISABLE_SPEEDY
 === 'false'\n   ? false\n   : process.env.REACT_APP_SC_DISABLE_SPEEDY\n   : typeof process.env.SC_DISABLE_SPEEDY !== 'undefined' && process.env.SC_DISABLE_SPEEDY !== ''\n   ? process.env.SC_DISABLE_SPEEDY === 'false'\n   ? false\n   : process.env.SC_DISABLE_SPEEDY\n   : process.env.NODE_ENV !== 'production'\n   : false\n);\n\n// Shared empty execution context when generating static styles\nexport const STATIC_EXECUTION_CONTEXT = {};\n","// @flow\nimport errorMap from './errors';\n\nconst ERRORS = process.env.NODE_ENV !== 'production' ? errorMap : {};\n\n/**\n * super basic version of sprintf\n */\nfunction format(...args) {\n let a = args[0];\n const b = [];\n\n for (let c = 1, len = args.length; c < len; c += 1) {\n   b.push(args[c]);\n }\n\n b.forEach(d => {\n   a = a.replace(/%[a-z]/, d);\n });\n\n return a;\n}\n\n/**\n * Create an error file out of errors.md for development and a simple web link to the full errors\n
 * in production mode.\n */\nexport default function throwStyledComponentsError(\n code: string | number,\n ...interpolations: Array<any>\n) {\n if (process.env.NODE_ENV === 'production') {\n   throw new Error(\n   `An error occurred. See https://git.io/JUIaE#${code} for more information.${\n        interpolations.length > 0 ? ` Args: ${interpolations.join(', ')}` : ''\n      }\n      `\n   );\n } else {\n   throw new Error(format(ERRORS[code], ...interpolations).trim());\n }\n}\n","export default {\"1\":\"Cannot create styled-component for component: %s.\\n\\n\",\"2\":\"Can't collect styles once you've consumed a `ServerStyleSheet`'s styles! `ServerStyleSheet` is a one off instance for each server-side render cycle.\\n\\n- Are you trying to reuse it across renders?\\n- Are you accidentally calling collectStyles twice?\\n\\n\",\"3\":\"Streaming SSR is only supported in a Node.js environment; Please do not try to call this method in the browser.\\n\\n\",\"4\":\"The `StyleSheetManager`
 expects a valid target or sheet prop!\\n\\n- Does this error occur on the client and is your target falsy?\\n- Does this error occur on the server and is the sheet falsy?\\n\\n\",\"5\":\"The clone method cannot be used on the client!\\n\\n- Are you running in a client-like environment on the server?\\n- Are you trying to run SSR on the client?\\n\\n\",\"6\":\"Trying to insert a new style tag, but the given Node is unmounted!\\n\\n- Are you using a custom target that isn't mounted?\\n- Does your document not have a valid head element?\\n- Have you accidentally removed a style tag manually?\\n\\n\",\"7\":\"ThemeProvider: Please return an object from your \\\"theme\\\" prop function, e.g.\\n\\n```js\\ntheme={() => ({})}\\n```\\n\\n\",\"8\":\"ThemeProvider: Please make your \\\"theme\\\" prop an object.\\n\\n\",\"9\":\"Missing document `<head>`\\n\\n\",\"10\":\"Cannot find a StyleSheet instance. Usually this happens if there are multiple copies of styled-components loaded at once. Check
 out this issue for how to troubleshoot and fix the common cases where this situation can happen: https://github.com/styled-components/styled-components/issues/1941#issuecomment-417862021\\n\\n\",\"11\":\"_This error was replaced with a dev-time warning, it will be deleted for v4 final._ [createGlobalStyle] received children which will not be rendered. Please use the component without passing children elements.\\n\\n\",\"12\":\"It seems you are interpolating a keyframe declaration (%s) into an untagged string. This was supported in styled-components v3, but is not longer supported in v4 as keyframes are now injected on-demand. Please wrap your string in the css\\`\\`\\` helper which ensures the styles are injected correctly. See https://www.styled-components.com/docs/api#css\\n\\n\",\"13\":\"%s is not a styled component and cannot be referred to via component selector. See https://www.styled-components.com/docs/advanced#referring-to-other-components for more details.\\n\\n\",\"14\":\"ThemeProvider:
 \\\"theme\\\" prop is required.\\n\\n\",\"15\":\"A stylis plugin has been supplied that is not named. We need a name for each plugin to be able to prevent styling collisions between different stylis configurations within the same app.

Before you pass your plugin to `<StyleSheetManager stylisPlugins={[]}>`, please make sure each plugin is uniquely-named, e.g.\\n\\n```js\\nObject.defineProperty(importedPlugin, 'name', { value: 'some-unique-name' });\\n```\\n\\n\",\"16\":\"Reached the limit of how many styled components may be created at group %s.\\nYou may only create up to 1,073,741,824 components. If you're creating components dynamically,\\nas for instance in your render method then you may be running into this limitation.\\n\\n\",\"17\":\"CSSStyleSheet could not be found on HTMLStyleElement.\\nHas styled-components' style tag been unmounted or altered by another script?\\n\"};","// @flow\n/* eslint-disable no-use-before-define */\n\nimport type { GroupedTag, Tag } from './types';\nimport { SPLITTER } from '../constants';\nimport throwStyledError from '../utils/error';\n\n/** Create a GroupedTag with an underlying Tag implementation */\nexport const makeGroupedTag = (tag: Tag): GroupedTag => {\n return new DefaultGroupedTag(tag);\n};\n\nconst BASE_SIZE = 1 << 9;\n\nclass DefaultGroupedTag implements GroupedTag {\n groupSizes: Uint32Array;\n\n length: number;\n\n tag: Tag;\n\n constructor(tag: Tag) {\n   this.groupSizes = new Uint32Array(BASE_SIZE);\n   this.length = BASE_SIZE;\n   this.tag = tag;\n }\n\n indexOfGroup(group: number): number {\n   let index = 0;\n   for (let i = 0; i < group; i++) {\n   index += this.groupSizes[i];\n   }\n\n   return index;\n }\n\n insertRules(group: number, rules: string[]): void {\n   if (group >= this.groupSizes.length) {\n   const oldBuffer = this.groupSizes;\n   const oldSize = oldBuffer.length;\n\n   let newSize = oldSize;\n   while (group >= newSize) {\n   newSize <<= 1;\n   if (newSize < 0) {\n   throwStyledError(16, `${group}`);\n   }\n   }\n\n   this.groupSizes = new Uint32Array(newSize);\n   this.groupSizes.set(oldBuffer);\n   this.length = newSize;\n\n   for (let i = oldSize; i < newSize; i++) {\n   this.groupSizes[i] = 0;\n   }\n   }\n\n   let ruleIndex = this.indexOfGroup(group + 1);\n\n   for (let i = 0, l = rules.length; i < l; i++) {\n   if (this.tag.insertRule(ruleIndex, rules[i])) {\n   this.groupSizes[group]++;\n   ruleIndex++;\n   }\n   }\n }\n\n clearGroup(group: number): void {\n   if (group < this.length) {\n   const length = this.groupSizes[group];\n   const startIndex = this.indexOfGroup(group);\n   const endIndex = startIndex + length;\n\n   this.groupSizes[group] = 0;\n\n   for (let i = startIndex; i < endIndex; i++) {\n   this.tag.deleteRule(startIndex);\n   }\n   }\n }\n\n getGroup(group: number): string {\n   let css = '';\n   if (group >= this.length || this.groupSizes[group] === 0) {\n   return css;\n   }\n\n   const length = this.groupSizes[group];\n   const startIndex = this.indexOfGroup(group);\n   const endIndex = startIndex + length;\n\n   for (let i = startIndex; i < endIndex; i++) {\n   css += `${this.tag.getRule(i)}${SPLITTER}`;\n   }\n\n   return css;\n }\n}\n","// @flow\n\nimport throwStyledError from '../utils/error';\n\nconst MAX_SMI = 1 << 31 - 1;\n\nlet groupIDRegister: Map<string, number> = new Map();\nlet reverseRegister: Map<number, string> = new Map();\nlet nextFreeGroup = 1;\n\nexport const resetGroupIds = () => {\n groupIDRegister = new Map();\n reverseRegister = new Map();\n nextFreeGroup = 1;\n};\n\nexport const getGroupForId = (id: string): number => {\n if (groupIDRegister.has(id)) {\n   return (groupIDRegister.get(id): any);\n }\n\n while (reverseRegister.has(nextFreeGroup)) {\n   nextFreeGroup++;\n }\n\n const group = nextFreeGroup++;\n\n if (\n   process.env.NODE_ENV !== 'production' &&\n   ((group | 0) < 0 || group > MAX_SMI)\n) {\n   throwStyledError(16, `${group}`);\n }\n\n groupIDRegister.set(id, group);\n reverseRegister.set(group, id);\n return group;\n};\n\nexport const getIdForGroup = (group: number): void | string => {\n return reverseRegister.get(group);\n};\n\nexport const setGroupForId = (id: string, group: number) => {\n if (group >= nextFreeGroup) {\n   nextFreeGroup = group + 1;\n }\n\n groupIDRegister.set(id, group);\n reverseRegister.set(group, id);\n};\n","// @flow\n\nimport { SPLITTER, SC_ATTR, SC_ATTR_ACTIVE, SC_ATTR_VERSION, SC_VERSION } from '../constants';\nimport { getIdForGroup, setGroupForId } from './GroupIDAllocator';\nimport type { Sheet } from './types';\n\nconst SELECTOR = `style[${SC_ATTR}][${SC_ATTR_VERSION}=\"${SC_VERSION}\"]`;\nconst MARKER_RE = new RegExp(`^${SC_ATTR}\\\\.g(\\\\d+)\\\\[id=\"([\\\\w\\\\d-]+)\"\\\\].*?\"([^\"]*)`);\n\nexport const outputSheet = (sheet: Sheet) => {\n const tag = sheet.getTag();\n const { length } = tag;\n\n let css = '';\n for (let group = 0; group < length; group++) {\n   const id = getIdForGroup(group);\n   if (id === undefined) continue;\n\n   const names = sheet.names.get(id);\n   const rules = tag.getGroup(group);\n   if (!names || !rules || !names.size) continue;\n\n   const selector = `${SC_ATTR}.g${group}[id=\"${id}\"]`;\n\n   let content = '';\n   if (names !== undefined) {\n

names.forEach(name => {\n if (name.length > 0) {\n content += `${name},`;\n }\n });\n }\n\n // NOTE: It's easier to collect rules and have the marker\n // after the actual rules to simplify the rehydration\n css += `${rules}${selector}{content:\"${content}\"}${SPLITTER}`;\n }\n\n return css;\n};\n\nconst rehydrateNamesFromContent = (sheet: Sheet, id: string, content: string) => {\n const names = content.split(',');\n let name;\n\n for (let i = 0, l = names.length; i < l; i++) {\n // eslint-disable-next-line\n if ((name = names[i])) {\n sheet.registerName(id, name);\n }\n }\n};\n\nconst rehydrateSheetFromTag = (sheet: Sheet, style: HTMLStyleElement) => {\n const parts = (style.textContent || '').split(SPLITTER);\n const rules: string[] = [];\n\n for (let i = 0, l = parts.length; i < l; i++) {\n const part = parts[i].trim();\n if (!part) continue;\n\n const marker = part.match(MARKER_RE);\n\n if (marker) {\n const group = parseInt(marker[1], 10) | 0;\n const id = marker[2];\n\n if (group !== 0) {\n // Rehydrate componentId to group index mapping\n setGroupForId(id, group);\n // Rehydrate names and rules\n // looks like: data-styled.g11[id=\"idA\"]{content:\"nameA,\"}\n rehydrateNamesFromContent(sheet, id, marker[3]);\n sheet.getTag().insertRules(group, rules);\n }\n\n rules.length = 0;\n } else {\n rules.push(part);\n }\n }\n};\n\nexport const rehydrateSheet = (sheet: Sheet) => {\n const nodes = document.querySelectorAll(SELECTOR);\n\n for (let i = 0, l = nodes.length; i < l; i++) {\n const node = ((nodes[i]: any): HTMLStyleElement);\n if (node && node.getAttribute(SC_ATTR) !== SC_ATTR_ACTIVE) {\n rehydrateSheetFromTag(sheet, node);\n\n if (node.parentNode) {\n node.parentNode.removeChild(node);\n }\n }\n }\n};\n","// @flow\n/* eslint-disable camelcase, no-undef */\n\ndeclare var __webpack_nonce__: string;\n\nconst getNonce = () => {\n return typeof __webpack_nonce__ !== 'undefined' ? __webpack_nonce__ : null;\n};\n\nexport default getNonce;\n","// @flow\n\nimport { SC_ATTR, SC_ATTR_ACTIVE, SC_ATTR_VERSION, SC_VERSION } from '../constants';\nimport getNonce from '../utils/nonce';\nimport throwStyledError from '../utils/error';\n\nconst ELEMENT_TYPE = 1; /* Node.ELEMENT_TYPE */\n\n/** Find last style element if any inside target */\nconst findLastStyleTag = (target: HTMLElement): void | HTMLStyleElement => {\n const { childNodes } = target;\n\n for (let i = childNodes.length; i >= 0; i--) {\n const child = ((childNodes[i]: any): ?HTMLElement);\n if (child && child.nodeType === ELEMENT_TYPE && child.hasAttribute(SC_ATTR)) {\n return ((child: any): HTMLStyleElement);\n }\n }\n\n return undefined;\n};\n\n/** Create a style element inside `target` or <head> after the last */\nexport const makeStyleTag = (target?: HTMLElement): HTMLStyleElement => {\n const head = ((document.head: any): HTMLElement);\n const parent = target || head;\n const style = document.createElement('style');\n const prevStyle = findLastStyleTag(parent);\n const nextSibling = prevStyle !== undefined ? prevStyle.nextSibling : null;\n\n style.setAttribute(SC_ATTR, SC_ATTR_ACTIVE);\n style.setAttribute(SC_ATTR_VERSION, SC_VERSION);\n\n const nonce = getNonce();\n\n if (nonce) style.setAttribute('nonce', nonce);\n\n parent.insertBefore(style, nextSibling);\n\n return style;\n};\n\n/** Get the CSSStyleSheet instance for a given style element */\nexport const getSheet = (tag: HTMLStyleElement): CSSStyleSheet => {\n if (tag.sheet) {\n return ((tag.sheet: any): CSSStyleSheet);\n }\n\n // Avoid Firefox quirk where the style element might not have a sheet property\n const { styleSheets } = document;\n for (let i = 0, l = styleSheets.length; i < l; i++) {\n const sheet = styleSheets[i];\n if (sheet.ownerNode === tag) {\n return ((sheet: any): CSSStyleSheet);\n }\n }\n\n throwStyledError(17);\n return (undefined: any);\n};\n","// @flow\n/* eslint-disable no-use-before-define */\n\nimport { makeStyleTag, getSheet } from './dom';\nimport type { SheetOptions, Tag } from './types';\n\n/** Create a CSSStyleSheet-like tag depending on the environment */\nexport const makeTag = ({ isServer, useCSSOMInjection, target }: SheetOptions): Tag => {\n if (isServer) {\n return new VirtualTag(target);\n } else if (useCSSOMInjection) {\n return new CSSOMTag(target);\n } else {\n return new TextTag(target);\n }\n};\n\nexport class CSSOMTag implements Tag {\n element: HTMLStyleElement;\n\n sheet: CSSStyleSheet;\n\n length: number;\n\n constructor(target?: HTMLElement) {\n const element = (this.element = makeStyleTag(target));\n\n // Avoid Edge bug where empty style elements don't create sheets\n element.appendChild(document.createTextNode(''));\n\n this.sheet = getSheet(element);\n this.length = 0;\n }\n\n insertRule(index: number, rule: string): boolean {\n try {\n this.sheet.insertRule(rule, index);

this.length++;\n return true;\n } catch (_error) {\n return false;\n }\n }\n\n deleteRule(index: number): void {\n this.sheet.deleteRule(index);\n this.length--;\n }\n\n getRule(index: number): string {\n const rule = this.sheet.cssRules[index];\n // Avoid IE11 quirk where cssText is inaccessible on some invalid rules\n if (rule !== undefined && typeof rule.cssText === 'string') {\n return rule.cssText;\n } else {\n return '';\n }\n }\n}\n\n/** A Tag that emulates the CSSStyleSheet API but uses text nodes */\nexport class TextTag implements Tag {\n element: HTMLStyleElement;\n\n nodes: NodeList<Node>;\n\n length: number;\n\n constructor(target?: HTMLElement) {\n const element = (this.element = makeStyleTag(target));\n this.nodes = element.childNodes;\n this.length = 0;\n }\n\n insertRule(index: number, rule: string): boolean {\n if (index <= this.length && index >= 0) {\n const node = document.createTextNode(rule);\n const refNode = this.nodes[index];\n this.element.insertBefore(node, refNode || null);\n this.length++;\n return true;\n } else {\n return false;\n }\n }\n\n deleteRule(index: number): void {\n this.element.removeChild(this.nodes[index]);\n this.length--;\n }\n\n getRule(index: number): string {\n if (index < this.length) {\n return this.nodes[index].textContent;\n } else {\n return '';\n }\n }\n}\n\n/** A completely virtual (server-side) Tag that doesn't manipulate the DOM */\nexport class VirtualTag implements Tag {\n rules: string[];\n\n length: number;\n\n constructor(_target?: HTMLElement) {\n this.rules = [];\n this.length = 0;\n }\n\n insertRule(index: number, rule: string): boolean {\n if (index <= this.length) {\n this.rules.splice(index, 0, rule);\n this.length++;\n return true;\n } else {\n return false;\n }\n }\n\n deleteRule(index: number): void {\n this.rules.splice(index, 1);\n this.length--;\n }\n\n getRule(index: number): string {\n if (index < this.length) {\n return this.rules[index];\n } else {\n return '';\n }\n }\n}\n","// @flow\nimport { DISABLE_SPEEDY, IS_BROWSER } from '../constants';\nimport { EMPTY_OBJECT } from '../utils/empties';\nimport { makeGroupedTag } from './GroupedTag';\nimport { getGroupForId } from './GroupIDAllocator';\nimport { outputSheet, rehydrateSheet } from './Rehydration';\nimport { makeTag } from './Tag';\nimport type { GroupedTag, Sheet, SheetOptions } from './types';\n\nlet SHOULD_REHYDRATE = IS_BROWSER;\n\ntype SheetConstructorArgs = {\n isServer?: boolean,\n useCSSOMInjection?: boolean,\n target?: HTMLElement,\n};\n\ntype GlobalStylesAllocationMap = { [key: string]: number };\ntype NamesAllocationMap = Map<string, Set<string>>;\n\nconst defaultOptions: SheetOptions = {\n isServer: !IS_BROWSER,\n useCSSOMInjection: !DISABLE_SPEEDY,\n};\n\n/** Contains the main stylesheet logic for stringification and caching */\nexport default class StyleSheet implements Sheet {\n gs: GlobalStylesAllocationMap;\n\n names: NamesAllocationMap;\n\n options: SheetOptions;\n\n server: boolean;\n\n tag: void | GroupedTag;\n\n /** Register a group ID to give it an index */\n static registerId(id: string): number {\n return getGroupForId(id);\n }\n\n constructor(\n options: SheetConstructorArgs = EMPTY_OBJECT,\n globalStyles?: GlobalStylesAllocationMap = {},\n names?: NamesAllocationMap\n) {\n this.options = {\n ...defaultOptions,\n ...options,\n };\n\n this.gs = globalStyles;\n this.names = new Map(names);\n this.server = !!options.isServer;\n\n // We rehydrate only once and use the sheet that is created first\n if (!this.server && IS_BROWSER && SHOULD_REHYDRATE) {\n SHOULD_REHYDRATE = false;\n rehydrateSheet(this);\n }\n }\n\n reconstructWithOptions(options: SheetConstructorArgs, withNames?: boolean = true) {\n return new StyleSheet(\n { ...this.options, ...options },\n this.gs,\n (withNames && this.names) || undefined\n);\n }\n\n allocateGSInstance(id: string) {\n return (this.gs[id] = (this.gs[id] || 0) + 1);\n }\n\n /** Lazily initialises a GroupedTag for when it's actually needed */\n getTag(): GroupedTag {\n return this.tag || (this.tag = makeGroupedTag(makeTag(this.options)));\n }\n\n /** Check whether a name is known for caching */\n hasNameForId(id: string, name: string): boolean {\n return this.names.has(id) && (this.names.get(id): any).has(name);\n }\n\n /** Mark a group's name as known for caching */\n registerName(id: string, name: string) {\n getGroupForId(id);\n\n if (!this.names.has(id)) {\n const groupNames = new Set();\n groupNames.add(name);\n this.names.set(id, groupNames);\n } else {\n (this.names.get(id): any).add(name);\n }\n }\n\n /** Insert new rules which also marks the name as known */\n insertRules(id: string, name: string, rules: string[]) {\n this.registerName(id, name);\n this.getTag().insertRules(getGroupForId(id), rules);\n }\n\n /** Clears all cached names for a given group ID */\n clearNames(id: string) {\n if

(this.names.has(id)) {\n (this.names.get(id): any).clear();\n }\n }\n\n /** Clears all rules for a given group ID */\n clearRules(id: string) {\n this.getTag().clearGroup(getGroupForId(id));\n this.clearNames(id);\n }\n\n /** Clears the entire tag which deletes all rules but not its names */\n clearTag() {\n // NOTE: This does not clear the names, since it's only used during SSR\n // so that we can continuously output only new rules\n this.tag = undefined;\n }\n\n /** Outputs the current sheet as a CSS string with markers for SSR */\n toString(): string {\n return outputSheet(this);\n }\n}\n","// @flow\n/* eslint-disable no-bitwise */\n\nconst AD_REPLACER_R = /(a)(d)/gi;\n\n/* This is the \"capacity\" of our alphabet i.e. 2x26 for all letters plus their capitalised\n * counterparts */\nconst charsLength = 52;\n\n/* start at 75 for 'a' until 'z' (25) and then start at 65 for capitalised letters */\nconst getAlphabeticChar = (code: number): string =>\n String.fromCharCode(code + (code > 25 ? 39 : 97));\n\n/* input a number, usually a hash and convert it to base-52 */\nexport default function generateAlphabeticName(code: number): string {\n let name = '';\n let x;\n\n /* get a char and divide by alphabet-length */\n for (x = Math.abs(code); x > charsLength; x = (x / charsLength) | 0) {\n name = getAlphabeticChar(x % charsLength) + name;\n }\n\n return (getAlphabeticChar(x % charsLength) + name).replace(AD_REPLACER_R, '$1-$2');\n}\n","// @flow\n/* eslint-disable */\n\nexport const SEED = 5381;\n\n// When we have separate strings it's useful to run a progressive\n// version of djb2 where we pretend that we're still looping over\n// the same string\nexport const phash = (h: number, x: string): number => {\n let i = x.length;\n\n while (i) {\n h = (h * 33) ^ x.charCodeAt(--i);\n }\n\n return h;\n};\n\n// This is a djb2 hashing function\nexport const hash = (x: string): number => {\n return phash(SEED, x);\n};\n","// @flow\nimport isFunction from './isFunction';\nimport isStyledComponent from './isStyledComponent';\nimport type { RuleSet } from '../types';\n\nexport default function isStaticRules(rules: RuleSet): boolean {\n for (let i = 0; i < rules.length; i += 1) {\n const rule = rules[i];\n\n if (isFunction(rule) && !isStyledComponent(rule)) {\n // functions are allowed to be static if they're just being\n // used to get the classname of a nested styled component\n return false;\n }\n }\n\n return true;\n}\n","// @flow\nimport { SC_VERSION } from '../constants';\nimport StyleSheet from '../sheet';\nimport type { RuleSet, Stringifier } from '../types';\nimport flatten from '../utils/flatten';\nimport generateName from '../utils/generateAlphabeticName';\nimport { hash, phash } from '../utils/hash';\nimport isStaticRules from '../utils/isStaticRules';\n\nconst SEED = hash(SC_VERSION);\n\n/**\n * ComponentStyle is all the CSS-specific stuff, not the React-specific stuff.\n */\nexport default class ComponentStyle {\n baseHash: number;\n\n baseStyle: ?ComponentStyle;\n\n componentId: string;\n\n isStatic: boolean;\n\n rules: RuleSet;\n\n staticRulesId: string;\n\n constructor(rules: RuleSet, componentId: string, baseStyle?: ComponentStyle) {\n this.rules = rules;\n this.staticRulesId = '';\n this.isStatic = process.env.NODE_ENV === 'production' &&\n (baseStyle === undefined || baseStyle.isStatic) &&\n isStaticRules(rules);\n this.componentId = componentId;\n\n // SC_VERSION gives us isolation between multiple runtimes on the page at once\n // this is improved further with use of the babel plugin \"namespace\" feature\n this.baseHash = phash(SEED, componentId);\n\n this.baseStyle = baseStyle;\n\n // NOTE: This registers the componentId, which ensures a consistent order\n // for this component's styles compared to others\n StyleSheet.registerId(componentId);\n }\n\n /*\n * Flattens a rule set into valid CSS\n * Hashes it, wraps the whole chunk in a .hash1234 {}\n * Returns the hash to be injected on render()\n * */\n generateAndInjectStyles(executionContext: Object, styleSheet: StyleSheet, stylis: Stringifier) {\n const { componentId } = this;\n\n const names = [];\n\n if (this.baseStyle) {\n names.push(this.baseStyle.generateAndInjectStyles(executionContext, styleSheet, stylis));\n }\n\n // force dynamic classnames if user-supplied stylis plugins are in use\n if (this.isStatic && !stylis.hash) {\n if (this.staticRulesId && styleSheet.hasNameForId(componentId, this.staticRulesId)) {\n names.push(this.staticRulesId);\n } else {\n const cssStatic = flatten(this.rules, executionContext, styleSheet, stylis).join('');\n const name = generateName(phash(this.baseHash, cssStatic) >>> 0);\n\n if (!styleSheet.hasNameForId(componentId, name)) {\n const cssStaticFormatted = stylis(cssStatic, `.${name}`, undefined, componentId);\n\n styleSheet.insertRules(componentId, name, cssStaticFormatted);\n }\n\n names.push(name);\n this.staticRulesId = name;\n }\n } else {\n const { length

} = this.rules;\n let dynamicHash = phash(this.baseHash, stylis.hash);\n let css = '';\n\n for (let i = 0; i < length; i++) {\n const partRule = this.rules[i];\n\n if (typeof partRule === 'string') {\n css += partRule;\n\n if (process.env.NODE_ENV !== 'production') dynamicHash = phash(dynamicHash, partRule + i);\n } else if (partRule) {\n const partChunk = flatten(partRule, executionContext, styleSheet, stylis);\n const partString = Array.isArray(partChunk) ? partChunk.join('') : partChunk;\n dynamicHash = phash(dynamicHash, partString + i);\n css += partString;\n }\n }\n\n if (css) {\n const name = generateName(dynamicHash >>> 0);\n\n if (!styleSheet.hasNameForId(componentId, name)) {\n const cssFormatted = stylis(css, `.${name}`, undefined, componentId);\n styleSheet.insertRules(componentId, name, cssFormatted);\n }\n\n names.push(name);\n }\n }\n\n return names.join(' ');\n }\n}\n","import Stylis from '@emotion/stylis';\nimport { type Stringifier } from '../types';\nimport { EMPTY_ARRAY, EMPTY_OBJECT } from './empties';\nimport throwStyledError from './error';\nimport { phash, SEED } from './hash';\nimport insertRulePlugin from './stylisPluginInsertRule';\n\nconst COMMENT_REGEX = /^\\s*\\/\\/.*$/gm;\nconst COMPLEX_SELECTOR_PREFIX = [':', '[', '.', '#'];\n\ntype StylisInstanceConstructorArgs = {\n options?: Object,\n plugins?: Array<Function>,\n};\n\nexport default function createStylisInstance({\n options = EMPTY_OBJECT,\n plugins = EMPTY_ARRAY,\n}: StylisInstanceConstructorArgs = EMPTY_OBJECT) {\n const stylis = new Stylis(options);\n\n // Wrap `insertRulePlugin to build a list of rules,\n // and then make our own plugin to return the rules. This\n // makes it easier to hook into the existing SSR architecture\n\n let parsingRules = [];\n\n // eslint-disable-next-line consistent-return\n const returnRulesPlugin = context => {\n if (context === -2) {\n const parsedRules = parsingRules;\n parsingRules = [];\n return parsedRules;\n }\n };\n\n const parseRulesPlugin = insertRulePlugin(rule => {\n parsingRules.push(rule);\n });\n\n let _componentId: string;\n let _selector: string;\n let _selectorRegexp: RegExp;\n let _consecutiveSelfRefRegExp: RegExp;\n\n const selfReferenceReplacer = (match, offset, string) => {\n if (\n // do not replace the first occurrence if it is complex (has a modifier)\n (offset === 0 ? COMPLEX_SELECTOR_PREFIX.indexOf(string[_selector.length]) === -1 : true) &&\n // no consecutive self refs (.b.b); that is a precedence boost and treated differently\n !string.match(_consecutiveSelfRefRegExp)\n) {\n return `.${_componentId}`;\n }\n\n return match;\n };\n\n /**\n * When writing a style like\n *\n * & + & {\n * color: red;\n * }\n *\n * The second ampersand should be a reference to the static component class. stylis\n * has no knowledge of static class so we have to intelligently replace the base selector.\n *\n * https://github.com/thysultan/stylis.js/tree/v3.5.4#plugins <- more info about the context phase values\n * \"2\" means this plugin is taking effect at the very end after all other processing is complete\n */\n const selfReferenceReplacementPlugin = (context, _, selectors) => {\n if (context === 2 && selectors.length && selectors[0].lastIndexOf(_selector) > 0) {\n // eslint-disable-next-line no-param-reassign\n selectors[0] = selectors[0].replace(_selectorRegexp, selfReferenceReplacer);\n }\n };\n\n stylis.use([...plugins, selfReferenceReplacementPlugin, parseRulesPlugin, returnRulesPlugin]);\n\n function stringifyRules(css, selector, prefix, componentId = '&'): Stringifier {\n const flatCSS = css.replace(COMMENT_REGEX, '');\n const cssStr = selector && prefix ? `${prefix} ${selector} { ${flatCSS} }` : flatCSS;\n\n // stylis has no concept of state to be passed to plugins\n // but since JS is single-threaded, we can rely on that to ensure\n // these properties stay in sync with the current stylis run\n _componentId = componentId;\n _selector = selector;\n _selectorRegexp = new RegExp(`\\\\${_selector}\\\\b`, 'g');\n _consecutiveSelfRefRegExp = new RegExp(`(\\\\${_selector}\\\\b){2,}`);\n\n return stylis(prefix || !selector ? '' : selector, cssStr);\n }\n\n stringifyRules.hash = plugins.length\n ? plugins\n .reduce((acc, plugin) => {\n if (!plugin.name) {\n throwStyledError(15);\n }\n\n return phash(acc, plugin.name);\n }, SEED)\n .toString()\n : '';\n\n return stringifyRules;\n}\n","/**\n * MIT License\n *\n * Copyright (c) 2016 Sultan Tarimo\n *\n * Permission is hereby granted, free of charge, to any person obtaining a copy of\n * this software and associated documentation files (the \"Software\"),\n * to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or\n * sell copies of the Software and to permit persons to whom the Software is

furnished to do so, subject to the following conditions:\n *\n * The above copyright notice and this permission notice shall be included in all\n * copies or substantial portions of the Software.\n *\n * THE SOFTWARE IS PROVIDED \"AS IS\", WITHOUT WARRANTY OF ANY KIND, EXPRESS\n * OR IMPLIED INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,\n * FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE\n * AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,\n * WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR\n * IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.\n */\n/* eslint-disable */\n\nexport default function(insertRule) {\n
const delimiter = '/*|*/';\n const needle = `${delimiter}}`;\n\n function toSheet(block) {\n if (block) {\n try {\n insertRule(`${block}}`);\n } catch (e) {}\n }\n }\n\n return function ruleSheet(\n context,\n content,\n selectors,\n parents,\n line,\n column,\n length,\n ns,\n depth,\n at\n) {\n switch (context) {\n // property\n case 1:\n // @import\n if (depth === 0 && content.charCodeAt(0) === 64) return insertRule(`${content};`), '';\n break;\n // selector\n case 2:\n if (ns === 0) return content + delimiter;\n break;\n // at-rule\n case 3:\n switch (ns) {\n // @font-face, @page\n case 102:\n case 112:\n return insertRule(selectors[0] + content), '';\n default:\n return content + (at === 0 ? delimiter : '');\n }\n case -2:\n content.split(needle).forEach(toSheet);\n }\n
};\n}\n","// @flow\nimport React, { type Context, type Node, useContext, useEffect, useMemo, useState } from 'react';\nimport shallowequal from 'shallowequal';\nimport StyleSheet from '../sheet';\nimport type { Stringifier } from '../types';\nimport createStylisInstance from '../utils/stylis';\n\ntype Props = {\n children?: Node,\n disableCSSOMInjection?: boolean,\n disableVendorPrefixes?: boolean,\n sheet?: StyleSheet,\n stylisPlugins?: Array<Function>,\n target?: HTMLElement,\n};\n\nexport const StyleSheetContext: Context<StyleSheet | void> = React.createContext();\nexport const StyleSheetConsumer = StyleSheetContext.Consumer;\nexport const StylisContext: Context<Stringifier | void> = React.createContext();\nexport const StylisConsumer = StylisContext.Consumer;\n\nexport const masterSheet: StyleSheet = new StyleSheet();\nexport const masterStylis: Stringifier = createStylisInstance();\n\nexport function useStyleSheet(): StyleSheet {\n return useContext(StyleSheetContext) ||
masterSheet;\n}\n\nexport function useStylis(): Stringifier {\n return useContext(StylisContext) || masterStylis;\n}\n\nexport default function StyleSheetManager(props: Props) {\n const [plugins, setPlugins] = useState(props.stylisPlugins);\n const contextStyleSheet = useStyleSheet();\n\n const styleSheet = useMemo(() => {\n let sheet = contextStyleSheet;\n\n if (props.sheet) {\n // eslint-disable-next-line prefer-destructuring\n sheet = props.sheet;\n } else if (props.target) {\n sheet = sheet.reconstructWithOptions({ target: props.target }, false);\n }\n\n if (props.disableCSSOMInjection) {\n sheet = sheet.reconstructWithOptions({ useCSSOMInjection: false });\n }\n\n return sheet;\n }, [props.disableCSSOMInjection, props.sheet, props.target]);\n\n const stylis = useMemo(\n () =>\n createStylisInstance({\n options: { prefix: !props.disableVendorPrefixes },\n plugins,\n }),\n [props.disableVendorPrefixes, plugins]\n);\n\n useEffect(() => {\n if (!shallowequal(plugins, props.stylisPlugins)) setPlugins(props.stylisPlugins);\n }, [props.stylisPlugins]);\n\n return (\n <StyleSheetContext.Provider value={styleSheet}>\n <StylisContext.Provider value={stylis}>\n {process.env.NODE_ENV !== 'production'\n ? React.Children.only(props.children)\n : props.children}\n </StylisContext.Provider>\n </StyleSheetContext.Provider>\n);\n}\n","// @flow\nimport StyleSheet from '../sheet';\nimport { type Stringifier } from '../types';\nimport throwStyledError from '../utils/error';\nimport { masterStylis } from './StyleSheetManager';\n\nexport default class Keyframes {\n id: string;\n\n name: string;\n\n rules: string;\n\n constructor(name: string, rules: string) {\n this.name = name;\n this.id = `sc-keyframes-${name}`;\n this.rules = rules;\n }\n\n inject = (styleSheet: StyleSheet, stylisInstance: Stringifier = masterStylis) => {\n const resolvedName
= this.name + stylisInstance.hash;\n\n if (!styleSheet.hasNameForId(this.id, resolvedName)) {\n styleSheet.insertRules(\n this.id,\n resolvedName,\n stylisInstance(this.rules, resolvedName,

'@keyframes')\n);\n }\n };\n\n toString = () => {\n return throwStyledError(12, String(this.name));\n };\n\n getName(stylisInstance: Stringifier = masterStylis) {\n return this.name + stylisInstance.hash;\n }\n}\n","// @flow\n\n/**\n * inlined version of\n * https://github.com/facebook/fbjs/blob/master/packages/fbjs/src/core/hyphenateStyleName.js\n */\n\nconst uppercaseCheck = /([A-Z])/;\nconst uppercasePattern = /([A-Z])/g;\nconst msPattern = /^ms-/;\nconst prefixAndLowerCase = (char: string): string => `-${char.toLowerCase()}`;\n\n/**\n * Hyphenates a camelcased CSS property name, for example:\n *\n * > hyphenateStyleName('backgroundColor')\n * < \"background-color\"\n * > hyphenateStyleName('MozTransition')\n * < \"-moz-transition\"\n * > hyphenateStyleName('msTransition')\n * < \"-ms-transition\"\n *\n * As Modernizr suggests (http://modernizr.com/docs/#prefixed), an `ms` prefix\n * is converted to `-ms-`.\n *\n * @param {string} string\n * @return {string}\n */\nexport default function hyphenateStyleName(string: string): string {\n return uppercaseCheck.test(string)\n ? string\n .replace(uppercasePattern, prefixAndLowerCase)\n .replace(msPattern, '-ms-')\n : string;\n}\n","// @flow\nimport { isElement } from 'react-is';\nimport getComponentName from './getComponentName';\nimport isFunction from './isFunction';\nimport isStatelessFunction from './isStatelessFunction';\nimport isPlainObject from './isPlainObject';\nimport isStyledComponent from './isStyledComponent';\nimport Keyframes from '../models/Keyframes';\nimport hyphenate from './hyphenateStyleName';\nimport addUnitIfNeeded from './addUnitIfNeeded';\nimport { type Stringifier } from '../types';\n\n/**\n * It's falsish not falsy because 0 is allowed.\n */\nconst isFalsish = chunk => chunk === undefined || chunk === null || chunk === false || chunk === '';\n\nexport const objToCssArray = (obj: Object, prevKey?: string): Array<string | Function> => {\n const rules = [];\n\n for (const key in obj) {\n if (!obj.hasOwnProperty(key) || isFalsish(obj[key])) continue;\n\n if ((Array.isArray(obj[key]) && obj[key].isCss) || isFunction(obj[key])) {\n rules.push(`${hyphenate(key)}:`, obj[key], ';');\n } else if (isPlainObject(obj[key])) {\n rules.push(...objToCssArray(obj[key], key));\n } else {\n rules.push(`${hyphenate(key)}: ${addUnitIfNeeded(key, obj[key])};`);\n }\n }\n\n return prevKey ? [`${prevKey} {`, ...rules, '}'] : rules;\n};\n\nexport default function flatten(\n chunk: any,\n executionContext: ?Object,\n styleSheet: ?Object,\n stylisInstance: ?Stringifier\n): any {\n if (Array.isArray(chunk)) {\n const ruleSet = [];\n\n for (let i = 0, len = chunk.length, result; i < len; i += 1) {\n result = flatten(chunk[i], executionContext, styleSheet, stylisInstance);\n\n if (result === '') continue;\n else if (Array.isArray(result)) ruleSet.push(...result);\n else ruleSet.push(result);\n }\n\n return ruleSet;\n }\n\n if (isFalsish(chunk)) {\n return '';\n }\n\n /* Handle other components */\n if (isStyledComponent(chunk)) {\n return `.${chunk.styledComponentId}`;\n }\n\n /* Either execute or defer the function */\n if (isFunction(chunk)) {\n if (isStatelessFunction(chunk) && executionContext) {\n const result = chunk(executionContext);\n\n if (process.env.NODE_ENV !== 'production' && isElement(result)) {\n // eslint-disable-next-line no-console\n console.warn(\n `${getComponentName(\n chunk\n )} is not a styled component and cannot be referred to via component selector. See https://www.styled-components.com/docs/advanced#referring-to-other-components for more details.`\n);\n }\n\n return flatten(result, executionContext, styleSheet, stylisInstance);\n } else return chunk;\n }\n\n if (chunk instanceof Keyframes) {\n if (styleSheet) {\n chunk.inject(styleSheet, stylisInstance);\n return chunk.getName(stylisInstance);\n } else return chunk;\n }\n\n /* Handle objects */\n return isPlainObject(chunk) ? objToCssArray(chunk) : chunk.toString();\n}\n","// @flow\nexport default function isStatelessFunction(test: any): boolean {\n return (\n typeof test === 'function'\n && !(\n test.prototype\n && test.prototype.isReactComponent\n)\n);\n}\n","// @flow\nimport unitless from '@emotion/unitless';\n\n// Taken from https://github.com/facebook/react/blob/b87aabdfe1b7461e7331abb3601d9e6bb27544bc/packages/react-dom/src/shared/dangerousStyleValue.js\nexport default function addUnitIfNeeded(name: string, value: any): any {\n // https://github.com/amilajack/eslint-plugin-flowtype-errors/issues/133\n // $FlowFixMe\n if (value == null || typeof value === 'boolean' || value === '') {\n return '';\n }\n\n if (typeof value === 'number' && value !== 0 && !(name in unitless) && !name.startsWith('--')) {\n return `${value}px`; // Presumes implicit 'px' suffix for unitless numbers except for CSS variables\n }\n\n return String(value).trim();\n}\n","//

@flow\nimport interleave from '../utils/interleave';\nimport isPlainObject from '../utils/isPlainObject';\nimport { EMPTY_ARRAY } from '../utils/empties';\nimport isFunction from '../utils/isFunction';\nimport flatten from '../utils/flatten';\nimport type { Interpolation, RuleSet, Styles } from '../types';\n\n/**\n * Used when flattening object styles to determine if we should\n * expand an array of styles.\n */\nconst addTag = arg => {\n if (Array.isArray(arg)) {\n   // eslint-disable-next-line no-param-reassign\n   arg.isCss = true;\n }\n return arg;\n};\n\nexport default function css(styles: Styles, ...interpolations: Array<Interpolation>): RuleSet {\n if (isFunction(styles) || isPlainObject(styles)) {\n   // $FlowFixMe\n   return addTag(flatten(interleave(EMPTY_ARRAY, [styles, ...interpolations])));\n }\n\n if (interpolations.length === 0 && styles.length === 1 && typeof styles[0] === 'string') {\n   // $FlowFixMe\n   return styles;\n }\n\n // $FlowFixMe\n return addTag(flatten(interleave(styles, interpolations)));\n}\n","// @flow\n\nimport { useRef } from 'react';\n\nconst invalidHookCallRe = /invalid hook call/i;\nconst seen = new Set();\n\nexport const checkDynamicCreation = (displayName: string, componentId?: string) => {\n if (process.env.NODE_ENV !== 'production') {\n   const parsedIdString = componentId ? ` with the id of \"${componentId}\"` : '';\n   const message =\n   `The component ${displayName}${parsedIdString} has been created dynamically.\\n` +\n   \"You may see this warning because you've called styled inside another component.\\n\" +\n   'To resolve this only create new StyledComponents outside of any render method and function component.';\n\n   // If a hook is called outside of a component:\n   // React 17 and earlier throw an error\n   // React 18 and above use console.error\n\n   const originalConsoleError = console.error // eslint-disable-line no-console\n   try {\n   let didNotCallInvalidHook = true\n   /* $FlowIgnore[cannot-write] */\n   console.error = (consoleErrorMessage, ...consoleErrorArgs) => { // eslint-disable-line no-console\n   // The error here is expected, since we're expecting anything that uses `checkDynamicCreation` to\n   // be called outside of a React component.\n   if (invalidHookCallRe.test(consoleErrorMessage)) {\n   didNotCallInvalidHook = false\n   // This shouldn't happen, but resets `warningSeen` if we had this error happen intermittently\n   seen.delete(message);\n   } else {\n   originalConsoleError(consoleErrorMessage, ...consoleErrorArgs);\n   }\n   }\n\n   // We purposefully call `useRef` outside of a component and expect it to throw\n   // If it doesn't, then we're inside another component.\n   // eslint-disable-next-line react-hooks/rules-of-hooks\n   useRef();\n\n   if (didNotCallInvalidHook && !seen.has(message)) {\n   // eslint-disable-next-line no-console\n   console.warn(message);\n   seen.add(message);\n   }\n   } catch (error) {\n   // The error here is expected, since we're expecting anything that uses `checkDynamicCreation` to\n   // be called outside of a React component.\n   if (invalidHookCallRe.test(error.message)) {\n   // This shouldn't happen, but resets `warningSeen` if we had this error happen intermittently\n   seen.delete(message);\n   }\n   } finally {\n   /* $FlowIgnore[cannot-write] */\n   console.error = originalConsoleError; // eslint-disable-line no-console\n   }\n }\n};\n","// @flow\n\nimport { EMPTY_OBJECT } from './empties';\n\ntype Props = {\n theme?: any,\n};\n\nexport default (props: Props, providedTheme: any, defaultProps: any = EMPTY_OBJECT) => {\n return (props.theme !== defaultProps.theme && props.theme) || providedTheme || defaultProps.theme;\n};\n","// @flow\n\n// Source: https://www.w3.org/TR/cssom-1/#serialize-an-identifier\n// Control characters and non-letter first symbols are not supported\nconst escapeRegex = /[!\"#$%&'()*+,./:;<=>?@[\\\\\\]^`{|}~-]+/g;\n\nconst dashesAtEnds = /(^-|-$)/g;\n\n/**\n * TODO: Explore using CSS.escape when it becomes more available\n * in evergreen browsers.\n */\nexport default function escape(str: string): string {\n return (\n   str\n   // Replace all possible CSS selectors\n   .replace(escapeRegex, '-')\n\n   // Remove extraneous hyphens at the start and end\n   .replace(dashesAtEnds, '')\n);\n}\n","// @flow\n/* eslint-disable */\nimport generateAlphabeticName from './generateAlphabeticName';\nimport { hash } from './hash';\n\nexport default (str: string): string => {\n return generateAlphabeticName(hash(str) >>> 0);\n};\n","// @flow\nimport type { IStyledComponent } from '../types';\n\nexport default function isTag(target: $PropertyType<IStyledComponent, 'target'>): boolean %checks {\n return (\n   typeof target === 'string' &&\n   (process.env.NODE_ENV !== 'production'\n   ? target.charAt(0) === target.charAt(0).toLowerCase()\n   : true)\n);\n}\n","/* eslint-disable */\n/**\n mixin-deep; https://github.com/jonschlinkert/mixin-deep\n Inlined such that it will be consistently transpiled to an IE-

compatible syntax.\n\n The MIT License (MIT)\n\n Copyright (c) 2014-present, Jon Schlinkert.\n\n Permission is hereby granted, free of charge, to any person obtaining a copy\n of this software and associated documentation files (the \"Software\"), to deal\n in the Software without restriction, including without limitation the rights\n to use, copy, modify, merge, publish, distribute, sublicense, and/or sell\n copies of the Software,
 and to permit persons to whom the Software is\n furnished to do so, subject to the following conditions:\n\n The above copyright notice and this permission notice shall be included in\n all copies or substantial portions of the Software.\n\n THE SOFTWARE IS PROVIDED \"AS IS\", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR\n IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,\n FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE\n AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER\n LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,\n OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN\n THE SOFTWARE.\n*/\n\nconst isObject = val => {\n return (\n   typeof val === 'function' || (typeof val === 'object' && val !== null && !Array.isArray(val))\n);\n};\n\nconst isValidKey = key => {\n return key !== '__proto__' && key !== 'constructor' && key !== 'prototype';\n};\n\nfunction
 mixin(target, val, key) {\n const obj = target[key];\n if (isObject(val) && isObject(obj)) {\n   mixinDeep(obj, val);\n } else {\n   target[key] = val;\n }\n}\n\nexport default function mixinDeep(target, ...rest) {\n for (const obj of rest) {\n   if (isObject(obj)) {\n   for (const key in obj) {\n   if (isValidKey(key)) {\n   mixin(target, obj[key], key);\n   }\n   }\n   }\n }\n\n return target;\n}\n","// @flow\nimport React, { useContext, useMemo, type Element, type Context } from 'react';\nimport throwStyledError from '../utils/error';\nimport isFunction from '../utils/isFunction';\n\nexport type Theme = { [key: string]: mixed };\n\ntype ThemeArgument = Theme | ((outerTheme?: Theme) => Theme);\n\ntype Props = {\n children?: Element<any>,\n theme: ThemeArgument,\n};\n\nexport const ThemeContext: Context<Theme | void> = React.createContext();\n\nexport const ThemeConsumer = ThemeContext.Consumer;\n\nfunction mergeTheme(theme: ThemeArgument,
 outerTheme?: Theme): Theme {\n if (!theme) {\n   return throwStyledError(14);\n }\n\n if (isFunction(theme)) {\n   const mergedTheme = theme(outerTheme);\n\n   if (\n   process.env.NODE_ENV !== 'production' &&\n   (mergedTheme === null || Array.isArray(mergedTheme) || typeof mergedTheme !== 'object')\n   ) {\n   return throwStyledError(7);\n   }\n\n   return mergedTheme;\n }\n\n if (Array.isArray(theme) || typeof theme !== 'object') {\n   return throwStyledError(8);\n }\n\n return outerTheme ? { ...outerTheme, ...theme } : theme;\n}\n\n/**\n * Provide a theme to an entire react component tree via context\n */\nexport default function ThemeProvider(props: Props) {\n const outerTheme = useContext(ThemeContext);\n const themeContext = useMemo(() => mergeTheme(props.theme, outerTheme), [\n   props.theme,\n   outerTheme,\n]);\n\n if (!props.children) {\n   return null;\n }\n\n return <ThemeContext.Provider value={themeContext}>{props.children}</ThemeContext.Provider>;\n}\n","//
 @flow\nimport validAttr from '@emotion/is-prop-valid';\nimport hoist from 'hoist-non-react-statics';\nimport React, { createElement, type Ref, useContext } from 'react';\nimport { SC_VERSION } from '../constants';\nimport type {\n Attrs,\n IStyledComponent,\n IStyledStatics,\n RuleSet,\n ShouldForwardProp,\n Target,\n} from '../types';\nimport { checkDynamicCreation } from '../utils/checkDynamicCreation';\nimport createWarnTooManyClasses from '../utils/createWarnTooManyClasses';\nimport determineTheme from '../utils/determineTheme';\nimport { EMPTY_ARRAY, EMPTY_OBJECT } from '../utils/empties';\nimport escape from '../utils/escape';\nimport generateComponentId from '../utils/generateComponentId';\nimport generateDisplayName from '../utils/generateDisplayName';\nimport getComponentName from '../utils/getComponentName';\nimport isFunction from '../utils/isFunction';\nimport isStyledComponent from '../utils/isStyledComponent';\nimport isTag from '../utils/isTag';\nimport
 joinStrings from '../utils/joinStrings';\nimport merge from '../utils/mixinDeep';\nimport ComponentStyle from './ComponentStyle';\nimport { useStyleSheet, useStylis } from './StyleSheetManager';\nimport { ThemeContext } from './ThemeProvider';\n\nconst identifiers = {};\n\n/* We depend on components having unique IDs */\nfunction generateId(displayName?: string, parentComponentId?: string) {\n const name = typeof displayName !== 'string' ?

```
'sc' : escape(displayName);\n  // Ensure that no displayName can lead to duplicate componentIds\n
identifiers[name] = (identifiers[name] || 0) + 1;\n\n  const componentId = `${name}-${generateComponentId(\n    //
SC_VERSION gives us isolation between multiple runtimes on the page at once\n    // this is improved further with
use of the babel plugin \"namespace\" feature\n    SC_VERSION + name + identifiers[name]\n  )}`;\n\n  return
parentComponentId ? `${parentComponentId}-${componentId}` : componentId;\n}\n\nfunction
useResolvedAttrs<Config>(theme:
 any = EMPTY_OBJECT, props: Config, attrs: Attrs) {\n  // NOTE: can't memoize this\n  // returns [context,
resolvedAttrs]\n  // where resolvedAttrs is only the things injected by the attrs themselves\n  const context = {
...props, theme };\n  const resolvedAttrs = {};\n\n  attrs.forEach(attrDef => {\n    let resolvedAttrDef = attrDef;\n
let key;\n\n    if (isFunction(resolvedAttrDef)) {\n      resolvedAttrDef = resolvedAttrDef(context);\n    }\n\n    /*
eslint-disable guard-for-in */\n    for (key in resolvedAttrDef) {\n      context[key] = resolvedAttrs[key] =\n        key
=== 'className'\n          ? joinStrings(resolvedAttrs[key], resolvedAttrDef[key])\n          : resolvedAttrDef[key];\n
}\n    /* eslint-enable guard-for-in */\n  });\n\n  return [context, resolvedAttrs];\n}\n\nfunction
useInjectedStyle<T>(\n  componentStyle: ComponentStyle,\n  isStatic: boolean,\n  resolvedAttrs: T,\n
warnTooManyClasses?: $Call<typeof createWarnTooManyClasses, string, string>\n)
 {\n  const styleSheet = useStyleSheet();\n  const stylis = useStylis();\n\n  const className = isStatic\n    ?
componentStyle.generateAndInjectStyles(EMPTY_OBJECT, styleSheet, stylis)\n    :
componentStyle.generateAndInjectStyles(resolvedAttrs, styleSheet, stylis);\n\n  if (process.env.NODE_ENV !==
'production' && !isStatic && warnTooManyClasses) {\n    warnTooManyClasses(className);\n  }\n\n  return
className;\n}\n\nfunction useStyledComponentImpl(\n  forwardedComponent: IStyledComponent,\n  props:
Object,\n  forwardedRef: Ref<any>,\n  isStatic: boolean\n) {\n  const {\n    attrs: componentAttrs,\n
componentStyle,\n    defaultProps,\n    foldedComponentIds,\n    shouldForwardProp,\n    styledComponentId,\n
target,\n  } = forwardedComponent;\n\n  // NOTE: the non-hooks version only subscribes to this when
!componentStyle.isStatic,\n  // but that'd be against the rules-of-hooks. We could be naughty and do it anyway as it\n
// should be an immutable value, but behave for now.\n
 const theme = determineTheme(props, useContext(ThemeContext), defaultProps);\n\n  const [context, attrs] =
useResolvedAttrs(theme || EMPTY_OBJECT, props, componentAttrs);\n\n  const generatedClassName =
useInjectedStyle(\n    componentStyle,\n    isStatic,\n    context,\n    process.env.NODE_ENV !== 'production' ?
forwardedComponent.warnTooManyClasses : undefined\n  );\n\n  const refToForward = forwardedRef;\n\n  const
elementToBeCreated: Target = attrs.$as || props.$as || attrs.as || props.as || target;\n\n  const isTargetTag =
isTag(elementToBeCreated);\n  const computedProps = attrs !== props ? { ...props, ...attrs } : props;\n  const
propsForElement = {};\n\n  // eslint-disable-next-line guard-for-in\n  for (const key in computedProps) {\n    if
(key[0] === '$' || key === 'as') continue;\n    else if (key === 'forwardedAs') {\n      propsForElement.as =
computedProps[key];\n    } else if (\n      shouldForwardProp\n        ? shouldForwardProp(key, validAttr,
elementToBeCreated)\n
      : isTargetTag\n        ? validAttr(key)\n        : true\n    ) {\n      // Don't pass through non HTML tags through to
HTML elements\n      propsForElement[key] = computedProps[key];\n    }\n  }\n\n  if (props.style && attrs.style
!== props.style) {\n    propsForElement.style = { ...props.style, ...attrs.style };\n  }\n\n  propsForElement.className
= Array.prototype\n    .concat(\n      foldedComponentIds,\n      styledComponentId,\n      generatedClassName !==
styledComponentId ? generatedClassName : null,\n      props.className,\n      attrs.className\n    )\n
.filter(Boolean)\n    .join(' ');\n\n  propsForElement.ref = refToForward;\n\n  return
createElement(elementToBeCreated, propsForElement);\n}\n\nexport default function createStyledComponent(\n
target: $PropertyType<IStyledComponent, 'target'>,\n  options: {\n    attrs?: Attrs,\n    componentId: string,\n
displayName?: string,\n    parentComponentId?: string,\n    shouldForwardProp?: ShouldForwardProp,\n  },\n  rules:
 RuleSet\n) {\n  const isTargetStyledComp = isStyledComponent(target);\n  const isCompositeComponent =
!isTag(target);\n\n  const {\n    attrs = EMPTY_ARRAY,\n    componentId = generateId(options.displayName,
options.parentComponentId),\n    displayName = generateDisplayName(target),\n  } = options;\n\n  const
styledComponentId =\n    options.displayName && options.componentId\n      ? `${escape(options.displayName)}-
```

```
${options.componentId}`\n      : options.componentId || componentId;\n\n  // fold the underlying StyledComponent attrs up (implicit extend)\n  const finalAttrs =\n    isTargetStyledComp && ((target: any): IStyledComponent).attrs\n      ? Array.prototype.concat(((target: any): IStyledComponent).attrs, attrs).filter(Boolean)\n      : attrs;\n\n  // eslint-disable-next-line prefer-destructuring\n  let shouldForwardProp = options.shouldForwardProp;\n\n  if (isTargetStyledComp && target.shouldForwardProp) {\n    if (options.shouldForwardProp) {\n      // compose nested shouldForwardProp calls\n      shouldForwardProp = (prop, filterFn, elementToBeCreated) =>\n        ((((target: any): IStyledComponent).shouldForwardProp: any): ShouldForwardProp)(\n          prop,\n          filterFn,\n          elementToBeCreated\n        ) &&\n        ((options.shouldForwardProp: any): ShouldForwardProp)(prop, filterFn, elementToBeCreated);\n    } else {\n      // eslint-disable-next-line prefer-destructuring\n      shouldForwardProp = ((target: any): IStyledComponent).shouldForwardProp;\n    }\n  }\n\n  const componentStyle = new ComponentStyle(\n    rules,\n    styledComponentId,\n    isTargetStyledComp ? ((target: Object).componentStyle: ComponentStyle) : undefined\n  );\n\n  // statically styled-components don't need to build an execution context object,\n  // and shouldn't be increasing the number of class names\n  const isStatic = componentStyle.isStatic && attrs.length === 0;\n\n  /**\n   * forwardRef creates a new interim component, which we'll take advantage of\n   * instead of extending ParentComponent to create _another_ interim class\n   */\n  let WrappedStyledComponent: IStyledComponent;\n\n  const forwardRef = (props, ref) =>\n    // eslint-disable-next-line\n    useStyledComponentImpl(WrappedStyledComponent, props, ref, isStatic);\n\n  forwardRef.displayName = displayName;\n\n  WrappedStyledComponent = ((React.forwardRef(forwardRef): any): IStyledComponent);\n  WrappedStyledComponent.attrs = finalAttrs;\n  WrappedStyledComponent.componentStyle = componentStyle;\n  WrappedStyledComponent.displayName = displayName;\n  WrappedStyledComponent.shouldForwardProp = shouldForwardProp;\n\n  // this static is used to preserve the cascade of static classes for component selector\n  // purposes; this is especially important with usage of the css prop\n  WrappedStyledComponent.foldedComponentIds = isTargetStyledComp\n    ? Array.prototype.concat(\n        ((target: any): IStyledComponent).foldedComponentIds,\n        ((target: any): IStyledComponent).styledComponentId\n      )\n    : EMPTY_ARRAY;\n\n  WrappedStyledComponent.styledComponentId = styledComponentId;\n\n  // fold the underlying StyledComponent target up since we folded the styles\n  WrappedStyledComponent.target = isTargetStyledComp\n    ? ((target: any): IStyledComponent).target\n    : target;\n\n  WrappedStyledComponent.withComponent = function withComponent(tag: Target) {\n    const { componentId: previousComponentId, ...optionsToCopy } = options;\n\n    const newComponentId =\n      previousComponentId &&\n      `${previousComponentId}-${isTag(tag) ? tag : escape(getComponentName(tag))}`;\n\n    const newOptions = {\n      ...optionsToCopy,\n      attrs: finalAttrs,\n      componentId: newComponentId,\n    };\n\n    return createStyledComponent(tag, newOptions, rules);\n  };\n\n  Object.defineProperty(WrappedStyledComponent, 'defaultProps', {\n    get() {\n      return this._foldedDefaultProps;\n    },\n\n    set(obj) {\n      this._foldedDefaultProps = isTargetStyledComp\n        ? merge({}, ((target: any): IStyledComponent).defaultProps, obj)\n        : obj;\n    },\n  });\n\n  if (process.env.NODE_ENV !== 'production') {\n    checkDynamicCreation(displayName, styledComponentId);\n\n    WrappedStyledComponent.warnTooManyClasses = createWarnTooManyClasses(\n      displayName,\n      styledComponentId\n    );\n  }\n\n  // If the Object prototype is frozen, the \"toString\" property is non-writable. This means that any objects which inherit this property\n  // cannot have the property changed using an assignment. If using strict mode, attempting that will cause an error. If not using strict\n  // mode, attempting that will be silently ignored.\n  // However, we can still explicitly shadow the prototype's \"toString\" property by defining a new \"toString\" property on this object.\n  Object.defineProperty(WrappedStyledComponent, 'toString', { value: () => `.${WrappedStyledComponent.styledComponentId}` });\n\n  if (isCompositeComponent) {\n    hoist<\n      IStyledStatics,\n      $PropertyType<IStyledComponent, 'target'>,\n      { [key: $Keys<IStyledStatics>]: true }\n    >(WrappedStyledComponent, ((target: any): $PropertyType<IStyledComponent, 'target'>), {\n      // all SC-specific things should not be hoisted\n      attrs: true,\n      componentStyle: true,\n      displayName: true,\n      foldedComponentIds: true,\n      shouldForwardProp: true,\n      styledComponentId: true,\n      target: true,\n
```

withComponent: true,\n });\n }\n\n return WrappedStyledComponent;\n}\n","// @flow\nimport type { IStyledComponent } from '../types';\nimport getComponentName from './getComponentName';\nimport isTag from './isTag';\n\nexport default function generateDisplayName(\n target: $PropertyType<IStyledComponent, 'target'>\n): string {\n return isTag(target) ? `styled.${target}` : `Styled(${getComponentName(target)})`;\n}\n","/**\n * Convenience function for joining strings to form className chains\n */\nexport default function joinStrings(a: ?String, b: ?String): ?String {\n return a && b ? `${a} ${b}` : a || b;\n}\n","// @flow\n\nexport const LIMIT = 200;\n\nexport default (displayName: string, componentId: string) => {\n let generatedClasses = {};\n let warningSeen = false;\n\n return (className: string) => {\n if (!warningSeen) {\n generatedClasses[className] = true;\n if (Object.keys(generatedClasses).length >= LIMIT) {\n // Unable to find latestRule in test environment.\n /* eslint-disable no-console, prefer-template */\n const parsedIdString = componentId ? ` with the id of \"${componentId}\"` : '';\n\n console.warn(\n `Over ${LIMIT} classes were generated for component ${displayName}${parsedIdString}.\\n` +\n 'Consider using the attrs method, together with a style object for frequently changed styles.\\n' +\n 'Example:\\n' +\n ' const Component = styled.div.attrs(props => ({\\n' +\n ' style: {\\n' +\n ' background: props.background,\\n' +\n ' },\\n' +\n ' }))`width: 100%;`\\n\\n' +\n ' <Component />'\n);\n warningSeen = true;\n generatedClasses = {};\n }\n }\n };\n};\n","// @flow\n// Thanks to ReactDOMFactories for this handy list!\n\nexport default [\n 'a',\n 'abbr',\n 'address',\n 'area',\n 'article',\n 'aside',\n 'audio',\n 'b',\n 'base',\n 'bdi',\n 'bdo',\n 'big',\n 'blockquote',\n 'body',\n 'br',\n 'button',\n 'canvas',\n 'caption',\n 'cite',\n 'code',\n 'col',\n 'colgroup',\n 'data',\n 'datalist',\n 'dd',\n 'del',\n 'details',\n 'dfn',\n 'dialog',\n 'div',\n 'dl',\n 'dt',\n 'em',\n 'embed',\n 'fieldset',\n 'figcaption',\n 'figure',\n 'footer',\n 'form',\n 'h1',\n 'h2',\n 'h3',\n 'h4',\n 'h5',\n 'h6',\n 'head',\n 'header',\n 'hgroup',\n 'hr',\n 'html',\n 'i',\n 'iframe',\n 'img',\n 'input',\n 'ins',\n 'kbd',\n 'keygen',\n 'label',\n 'legend',\n 'li',\n 'link',\n 'main',\n 'map',\n 'mark',\n 'marquee',\n 'menu',\n 'menuitem',\n 'meta',\n 'meter',\n 'nav',\n 'noscript',\n 'object',\n 'ol',\n 'optgroup',\n 'option',\n 'output',\n 'p',\n 'param',\n 'picture',\n 'pre',\n 'progress',\n 'q',\n 'rp',\n 'rt',\n 'ruby',\n 's',\n 'samp',\n 'script',\n 'section',\n 'select',\n 'small',\n 'source',\n 'span',\n 'strong',\n 'style',\n 'sub',\n 'summary',\n 'sup',\n 'table',\n 'tbody',\n 'td',\n 'textarea',\n 'tfoot',\n 'th',\n 'thead',\n 'time',\n 'title',\n 'tr',\n 'track',\n 'u',\n 'ul',\n 'var',\n 'video',\n 'wbr',\n\n // SVG\n 'circle',\n 'clipPath',\n 'defs',\n 'ellipse',\n 'foreignObject',\n 'g',\n 'image',\n 'line',\n 'linearGradient',\n 'marker',\n 'mask',\n 'path',\n 'pattern',\n 'polygon',\n 'polyline',\n 'radialGradient',\n 'rect',\n 'stop',\n 'svg',\n 'text',\n 'textPath',\n 'tspan',\n];\n","// @flow\nimport constructWithOptions from './constructWithOptions';\nimport StyledComponent from '../models/StyledComponent';\nimport domElements from '../utils/domElements';\n\nimport type { Target } from '../types';\n\nconst styled = (tag: Target) => constructWithOptions(StyledComponent, tag);\n\n// Shorthands for all valid HTML Elements\ndomElements.forEach(domElement => {\n styled[domElement] = styled(domElement);\n});\n\nexport default styled;\n","// @flow\nimport { isValidElementType } from 'react-is';\nimport css from './css';\nimport throwStyledError from '../utils/error';\nimport { EMPTY_OBJECT } from '../utils/empties';\n\nimport type { Target } from '../types';\n\nexport default function constructWithOptions(\n componentConstructor: Function,\n tag: Target,\n options: Object = EMPTY_OBJECT\n) {\n if (!isValidElementType(tag)) {\n return throwStyledError(1, String(tag));\n }\n\n /* This is callable directly as a template function */\n // $FlowFixMe: Not typed to avoid destructuring arguments\n const templateFunction = (...args) => componentConstructor(tag, options, css(...args));\n\n /* If config methods are called, wrap up a new template function and merge options */\n templateFunction.withConfig = config =>\n constructWithOptions(componentConstructor, tag, { ...options, ...config });\n\n /* Modify/inject new props at runtime */\n templateFunction.attrs = attrs =>\n constructWithOptions(componentConstructor, tag, {\n ...options,\n attrs: Array.prototype.concat(options.attrs, attrs).filter(Boolean),\n });\n\n return templateFunction;\n}\n","// @flow\nimport StyleSheet from '../sheet';\n\nimport type { RuleSet, Stringifier } from '../types';\n\nimport flatten from '../utils/flatten';\nimport isStaticRules from '../utils/isStaticRules';\n\nexport default

class GlobalStyle {\n componentId: string;\n\n isStatic: boolean;\n\n rules: RuleSet;\n\n constructor(rules: RuleSet, componentId: string) {\n   this.rules = rules;\n   this.componentId = componentId;\n   this.isStatic = isStaticRules(rules);\n\n   // pre-register the first instance to ensure global styles\n   // load before component ones\n   StyleSheet.registerId(this.componentId + 1);\n }\n\n createStyles(\n   instance: number,\n   executionContext: Object,\n   styleSheet: StyleSheet,\n   stylis: Stringifier\n) {\n   const flatCSS = flatten(this.rules, executionContext, styleSheet, stylis);\n   const css = stylis(flatCSS.join(''), '');\n   const id = this.componentId + instance;\n\n   // NOTE: We use the id as a name as well, since these rules never change\n   styleSheet.insertRules(id, id, css);\n }\n\n removeStyles(instance: number, styleSheet: StyleSheet) {\n   styleSheet.clearRules(this.componentId + instance);\n }\n\n renderStyles(\n   instance: number,\n   executionContext: Object,\n   styleSheet: StyleSheet,\n   stylis: Stringifier\n) {\n   if (instance > 2) StyleSheet.registerId(this.componentId + instance);\n\n   // NOTE: Remove old styles, then inject the new ones\n   this.removeStyles(instance, styleSheet);\n   this.createStyles(instance, executionContext, styleSheet, stylis);\n }\n}\n","// @flow\n/* eslint-disable no-underscore-dangle */\nimport React from 'react';\nimport { IS_BROWSER, SC_ATTR, SC_ATTR_VERSION, SC_VERSION } from '../constants';\nimport throwStyledError from '../utils/error';\nimport getNonce from '../utils/nonce';\nimport StyleSheet from '../sheet';\nimport StyleSheetManager from './StyleSheetManager';\n\ndeclare var __SERVER__: boolean;\n\nconst CLOSING_TAG_R = /^\\s*<\\/[a-z]/i;\n\nexport default class ServerStyleSheet {\n isStreaming: boolean;\n\n instance: StyleSheet;\n\n sealed: boolean;\n\n constructor() {\n   this.instance = new StyleSheet({ isServer: true });\n   this.sealed = false;\n }\n\n _emitSheetCSS = (): string => {\n   const css = this.instance.toString();\n   if (!css) return '';\n\n   const nonce = getNonce();\n   const attrs = [nonce && `nonce=\"${nonce}\"`, `${SC_ATTR}=\"true\"`, `${SC_ATTR_VERSION}=\"${SC_VERSION}\"`];\n   const htmlAttr = attrs.filter(Boolean).join(' ');\n\n   return `<style ${htmlAttr}>${css}</style>`;\n };\n\n collectStyles(children: any) {\n   if (this.sealed) {\n   return throwStyledError(2);\n   }\n\n   return <StyleSheetManager sheet={this.instance}>{children}</StyleSheetManager>;\n }\n\n getStyleTags = (): string => {\n   if (this.sealed) {\n   return throwStyledError(2);\n   }\n\n   return this._emitSheetCSS();\n };\n\n getStyleElement = () => {\n   if (this.sealed) {\n   return throwStyledError(2);\n   }\n\n   const props = {\n   [SC_ATTR]: '',\n   [SC_ATTR_VERSION]: SC_VERSION,\n   dangerouslySetInnerHTML: {\n   __html: this.instance.toString(),\n   },\n   };\n\n   const nonce = getNonce();\n   if (nonce) {\n   (props: any).nonce = nonce;\n   }\n\n   // v4 returned an array for this fn, so we'll do the same for v5 for backward compat\n   return [<style {...props} key=\"sc-0-0\" />];\n };\n\n // eslint-disable-next-line consistent-return\n interleaveWithNodeStream(input: any) {\n   if (!__SERVER__ || IS_BROWSER) {\n   return throwStyledError(3);\n   } else if (this.sealed) {\n   return throwStyledError(2);\n   }\n\n   if (__SERVER__) {\n   this.seal();\n\n   // eslint-disable-next-line global-require\n   const { Readable, Transform } = require('stream');\n\n   const readableStream: Readable = input;\n   const { instance: sheet, _emitSheetCSS } = this;\n\n   const transformer = new Transform({\n   transform: function appendStyleChunks(chunk, /* encoding */ _, callback) {\n   // Get the chunk and retrieve the sheet's CSS as an HTML chunk,\n   // then reset its rules so we get only new ones for the next chunk\n   const renderedHtml = chunk.toString();\n   const html = _emitSheetCSS();\n\n   sheet.clearTag();\n\n   // prepend style html to chunk, unless the start of the chunk is a\n   // closing tag in which case append right after that\n   if (CLOSING_TAG_R.test(renderedHtml)) {\n   const endOfClosingTag = renderedHtml.indexOf('>') + 1;\n   const before = renderedHtml.slice(0, endOfClosingTag);\n   const after = renderedHtml.slice(endOfClosingTag);\n\n   this.push(before + html + after);\n   } else {\n   this.push(html + renderedHtml);\n   }\n\n   callback();\n   },\n   });\n\n   readableStream.on('error', err => {\n   // forward the error to the transform stream\n   transformer.emit('error', err);\n   });\n\n   return readableStream.pipe(transformer);\n   }\n }\n\n seal = () => {\n   this.sealed = true;\n };\n}\n","// @flow\n/* eslint-disable */\n\nimport StyleSheet from './sheet';\nimport { masterSheet } from './models/StyleSheetManager';\n\nexport const __PRIVATE__ = {\n StyleSheet,\n masterSheet,\n};\n","// @flow\n/* Import singletons */\nimport isStyledComponent

from './utils/isStyledComponent';\nimport css from './constructors/css';\nimport createGlobalStyle from './constructors/createGlobalStyle';\nimport keyframes from './constructors/keyframes';\nimport ServerStyleSheet from './models/ServerStyleSheet';\nimport { SC_VERSION } from './constants';\n\nimport StyleSheetManager, {\n StyleSheetContext,\n StyleSheetConsumer,\n} from './models/StyleSheetManager';\n\n/* Import components */\nimport ThemeProvider, { ThemeContext, ThemeConsumer } from './models/ThemeProvider';\n\n/* Import Higher Order Components */\nimport withTheme from './hoc/withTheme';\n\n/* Import hooks */\nimport useTheme from './hooks/useTheme';\n\ndeclare var __SERVER__: boolean;\n\n/* Warning if you've imported this file on React Native */\nif (\n process.env.NODE_ENV !== 'production' &&\n typeof navigator !== 'undefined' &&\n navigator.product === 'ReactNative'\n) {\n // eslint-disable-next-line no-console\n console.warn(\n \"It looks like you've imported
'styled-components' on React Native.\\n\\n\" +\n "Perhaps you're looking to import 'styled-components/native'?\\n\\n" +\n 'Read more about this at https://www.styled-components.com/docs/basics#react-native'\n);\n}\n\n/* Warning if there are several instances of styled-components */\nif (process.env.NODE_ENV !== 'production' && process.env.NODE_ENV !== 'test' && typeof window !== 'undefined') {\n window['__styled-components-init__'] = window['__styled-components-init__'] || 0;\n\n if (window['__styled-components-init__'] === 1) {\n // eslint-disable-next-line no-console\n console.warn(\n "It looks like there are several instances of 'styled-components' initialized in this application. \" +\n 'This may cause dynamic styles to not render properly, errors during the rehydration process, ' +\n 'a missing theme prop, and makes your application bigger without good reason.\\n\\n' +\n 'See https://s-c.sh/2BAXzed for more info.'\n);\n }\n\n window['__styled-components-init__']
+= 1;\n}\n\n/* Export everything */\nexport * from './secretInternals';\nexport {\n createGlobalStyle,\n css,\n isStyledComponent,\n keyframes,\n ServerStyleSheet,\n StyleSheetConsumer,\n StyleSheetContext,\n StyleSheetManager,\n ThemeConsumer,\n ThemeContext,\n ThemeProvider,\n useTheme,\n SC_VERSION as version,\n withTheme,\n};\n","// @flow\nimport React, { useContext, useLayoutEffect, useRef } from 'react';\nimport { STATIC_EXECUTION_CONTEXT } from '../constants';\nimport GlobalStyle from '../models/GlobalStyle';\nimport { useStyleSheet, useStylis } from '../models/StyleSheetManager';\nimport { ThemeContext } from '../models/ThemeProvider';\nimport type { Interpolation } from '../types';\nimport { checkDynamicCreation } from '../utils/checkDynamicCreation';\nimport determineTheme from '../utils/determineTheme';\nimport generateComponentId from '../utils/generateComponentId';\nimport css from './css';\n\ndeclare var __SERVER__: boolean;\n\ntype
GlobalStyleComponentPropsType = Object;\n\nexport default function createGlobalStyle(\n strings: Array<string>,\n ...interpolations: Array<Interpolation>\n) {\n const rules = css(strings, ...interpolations);\n const styledComponentId = `sc-global-${generateComponentId(JSON.stringify(rules))}`;\n const globalStyle = new GlobalStyle(rules, styledComponentId);\n\n if (process.env.NODE_ENV !== 'production') {\n checkDynamicCreation(styledComponentId);\n }\n\n function GlobalStyleComponent(props: GlobalStyleComponentPropsType) {\n const styleSheet = useStyleSheet();\n const stylis = useStylis();\n const theme = useContext(ThemeContext);\n const instanceRef = useRef(styleSheet.allocateGSInstance(styledComponentId));\n\n const instance = instanceRef.current;\n\n if (process.env.NODE_ENV !== 'production' && React.Children.count(props.children)) {\n // eslint-disable-next-line no-console\n console.warn(\n `The global style component ${styledComponentId}
was given child JSX. createGlobalStyle does not render children.`\n );\n }\n\n if (\n process.env.NODE_ENV !== 'production' &&\n rules.some(rule => typeof rule === 'string' && rule.indexOf('@import') !== -1)\n ) {\n // eslint-disable-next-line no-console\n console.warn(\n `Please do not use @import CSS syntax in createGlobalStyle at this time, as the CSSOM APIs we use in production do not handle it well. Instead, we recommend using a library such as react-helmet to inject a typical <link> meta tag to the stylesheet, or simply embedding it manually in your index.html <head> section for a simpler app.`\n);\n }\n\n if (styleSheet.server) {\n renderStyles(instance, props, styleSheet, theme, stylis);\n }\n\n if (!__SERVER__) {\n // this conditional is fine because it is compiled away for the relevant builds during minification,\n //

resulting in a single unguarded hook call\n // eslint-disable-next-line react-hooks/rules-of-hooks\n useLayoutEffect(() => {\n if (!styleSheet.server) {\n renderStyles(instance, props, styleSheet, theme, stylis);\n return () => globalStyle.removeStyles(instance, styleSheet);\n }\n }, [instance, props, styleSheet, theme, stylis]);\n }\n\n return null;\n }\n\n function renderStyles(instance, props, styleSheet, theme, stylis) {\n if (globalStyle.isStatic) {\n globalStyle.renderStyles(instance, STATIC_EXECUTION_CONTEXT, styleSheet, stylis);\n } else {\n const context = {\n ...props,\n theme: determineTheme(props, theme, GlobalStyleComponent.defaultProps),\n };\n\n globalStyle.renderStyles(instance, context, styleSheet, stylis);\n }\n }\n\n // $FlowFixMe\n return React.memo(GlobalStyleComponent);\n}\n","// @flow\n\nimport css from './css';\nimport generateComponentId from '../utils/generateComponentId';\nimport Keyframes from '../models/Keyframes';\n\nimport type { Interpolation, Styles } from '../types';\n\nexport default function keyframes(\n strings: Styles,\n ...interpolations: Array<Interpolation>\n): Keyframes {\n /* Warning if you've used keyframes on React Native */\n if (\n process.env.NODE_ENV !== 'production' &&\n typeof navigator !== 'undefined' &&\n navigator.product === 'ReactNative'\n) {\n // eslint-disable-next-line no-console\n console.warn(\n '`keyframes` cannot be used on ReactNative, only on the web. To do animation in ReactNative please use Animated.'\n);\n }\n\n const rules = css(strings, ...interpolations).join('');\n const name = generateComponentId(rules);\n return new Keyframes(name, rules);\n}\n","// @flow\nimport { useContext } from 'react';\nimport { ThemeContext } from '../models/ThemeProvider';\n\nconst useTheme = () => useContext(ThemeContext);\n\nexport default useTheme;\n","// @flow\nimport React, { useContext, type AbstractComponent } from 'react';\nimport hoistStatics from 'hoist-non-react-statics';\nimport { ThemeContext } from '../models/ThemeProvider';\nimport determineTheme from '../utils/determineTheme';\nimport getComponentName from '../utils/getComponentName';\n\n// NOTE: this would be the correct signature:\n// export default <Config: { theme?: any }, Instance>(\n// Component: AbstractComponent<Config, Instance>\n//): AbstractComponent<$Diff<Config, { theme?: any }> & { theme?: any }, Instance>\n//\n// but the old build system tooling doesn't support the syntax\n\nexport default (Component: AbstractComponent<*, *>) => {\n // $FlowFixMe This should be React.forwardRef<Config, Instance>\n const WithTheme = React.forwardRef((props, ref) => {\n const theme = useContext(ThemeContext);\n // $FlowFixMe defaultProps isn't declared so it can be inferrable\n const { defaultProps } = Component;\n const themeProp = determineTheme(props, theme, defaultProps);\n\n if (process.env.NODE_ENV !== 'production' && themeProp === undefined) {\n // eslint-disable-next-line no-console\n console.warn(\n `[withTheme] You are not using a ThemeProvider nor passing a theme prop or a theme in defaultProps in component class \"${getComponentName(\n Component\n )}\"`\n);\n }\n\n return <Component {...props} theme={themeProp} ref={ref} />;\n });\n\n hoistStatics(WithTheme, Component);\n\n WithTheme.displayName = `WithTheme(${getComponentName(Component)})`;\n\n return WithTheme;\n};\n"],"names":["strings","interpolations","result","i","len","length","push","x","toString","Object","prototype","call","typeOf","EMPTY_ARRAY","freeze","EMPTY_OBJECT","isFunction","test","getComponentName","target","process","env","NODE_ENV","displayName","name","isStyledComponent","styledComponentId","SC_ATTR","REACT_APP_SC_ATTR","IS_BROWSER","window","DISABLE_SPEEDY","Boolean","SC_DISABLE_SPEEDY","REACT_APP_SC_DISABLE_SPEEDY","STATIC_EXECUTION_CONTEXT","ERRORS","format","a","b","c","arguments","forEach","d","replace","throwStyledComponentsError","code","Error","join","trim","DefaultGroupedTag","tag","groupSizes","Uint32Array","indexOfGroup","group","index","this","insertRules","rules","oldBuffer","oldSize","newSize","throwStyledError","set","ruleIndex","l","insertRule","clearGroup","startIndex","endIndex","deleteRule","getGroup","css","getRule","groupIDRegister","Map","reverseRegister","nextFreeGroup","getGroupForId","id","has","get","getIdForGroup","setGroupForId","SELECTOR","MARKER_RE","RegExp","rehydrateNamesFromContent","sheet","content","names","split","registerName","rehydrateSheetFromTag","style","parts","textContent","part","marker","match","parseInt","getTag","getNonce","__webpack_nonce__","makeStyleTag","head","document","parent","createElement","prevStyle","childNodes","child","nodeType","hasAttribute","findLa

stStyleTag","nextSibling","undefined","setAttribute","__VERSION__","nonce","insertBefore","CSSOMTag","element","appendChild","createTextNode","styleSheets","ownerNode","getSheet","rule","_error","cssRules","cssText","TextTag","nodes","node","refNode","removeChild","VirtualTag","_target","splice","SHOULD_REHYDRATE","defaultOptions","isServer","useCSSOMInjection","StyleSheet","options","globalStyles","gs","server","querySelectorAll","getAttribute","parentNode","rehydrateSheet","registerId","reconstructWithOptions","withNames","allocateGSInstance","hasNameForId","add","groupNames","Set","clearNames","clear","clearRules","clearTag","size","selector","outputSheet","AD_REPLACER_R","getAlphabeticChar","String","fromCharCode","generateAlphabeticName","Math","abs","phash","h","charCodeAt","hash","isStaticRules","SEED","ComponentStyle","componentId","baseStyle","staticRulesId","isStatic","baseHash","generateAndInjectStyles","executionContext","styleSheet","stylis","cssStatic","flatten","generateName","cssStaticFormatted","dynamicHash","partRule","partChunk","partString","Array","isArray","cssFormatted","COMMENT_REGEX","COMPLEX_SELECTOR_PREFIX","createStylisInstance","_componentId","_selector","_selectorRegexp","_consecutiveSelfRefRegExp","plugins","Stylis","parsingRules","parseRulesPlugin","toSheet","block","e","context","selectors","parents","line","column","ns","depth","at","delimiter","insertRulePlugin","selfReferenceReplacer","offset","string","indexOf","stringifyRules","prefix","flatCSS","cssStr","use","_","lastIndexOf","parsedRules","reduce","acc","plugin","StyleSheetContext","React","createContext","StyleSheetConsumer","Consumer","StylisContext","masterSheet","masterStylis","useStyleSheet","useContext","useStylis","StyleSheetManager","props","useState","stylisPlugins","setPlugins","contextStyleSheet","useMemo","disableCSSOMInjection","disableVendorPrefixes","useEffect","shallowequal","Provider","value","Children","only","children","Keyframes","inject","stylisInstance","resolvedName","_this","getName","uppercaseCheck","uppercasePattern","msPattern","prefixAndLowerCase","char","toLowerCase","hyphenateStyleName","isFalsish","chunk","ruleSet","isReactComponent","isElement","console","warn","isPlainObject","objToCssArray","obj","prevKey","key","hasOwnProperty","isCss","hyphenate","unitless","startsWith","addTag","arg","styles","interleave","invalidHookCallRe","seen","checkDynamicCreation","message","originalConsoleError","error","didNotCallInvalidHook","consoleErrorMessage","consoleErrorArgs","useRef","providedTheme","defaultProps","theme","escapeRegex","dashesAtEnds","escape","str","isTag","charAt","isObject","val","isValidKey","mixin","mixinDeep","rest","ThemeContext","ThemeConsumer","identifiers","createStyledComponent","isTargetStyledComp","isCompositeComponent","attrs","parentComponentId","generateComponentId","generateId","generateDisplayName","finalAttrs","concat","filter","shouldForwardProp","prop","filterFn","elementToBeCreated","WrappedStyledComponent","componentStyle","forwardRef","ref","forwardedComponent","forwardedRef","componentAttrs","foldedComponentIds","resolvedAttrs","attrDef","resolvedAttrDef","useResolvedAttrs","determineTheme","generatedClassName","warnTooManyClasses","className","useInjectedStyle","refToForward","$as","as","isTargetTag","computedProps","propsForElement","validAttr","withComponent","previousComponentId","optionsToCopy","newComponentId","defineProperty","_foldedDefaultProps","merge","generatedClasses","warningSeen","keys","parsedIdString","createWarnTooManyClasses","hoist","styled","constructWithOptions","componentConstructor","isValidElementType","templateFunction","withConfig","config","StyledComponent","domElement","GlobalStyle","createStyles","instance","removeStyles","renderStyles","ServerStyleSheet","_emitSheetCSS","SC_ATTR_VERSION","getStyleTags","sealed","getStyleElement","dangerouslySetInnerHTML","__html","seal","collectStyles","interleaveWithNodeStream","input","__PRIVATE__","navigator","product","outerTheme","themeContext","mergedTheme","mergeTheme","JSON","stringify","globalStyle","GlobalStyleComponent","current","count","some","useLayoutEffect","memo","Component","WithTheme","themeProp","hoistStatics"],"mappings":"2jBAGA,eACEA,EACAC,CAEAC,EAAAC,EAAAC,EAA

AIa,4BACkC,UAA5Cd,QAAQC,IAAIa,6BAEVd,QAAQC,IAAIa,iCAC2B,IAAlCd,QAAQC,IAAIY,mBAAuE,KAAlCb,QAAQC,IAAIY,kBAClC,UAAlCb,QAAQC,IAAIY,mBAEVb,QAAQC,IAAIY,kBACW,eAAzBb,QAAQC,IAAIC,WAKPa,EAA2B,GCjClCC,EAAkC,eAAzBhB,QAAQC,IAAIC,SCHZ,GAAAK,0DAA4D,kQAAAoB,wHAA0H,wMAAAC,0M,oKAAAC,sK,8OAAAC,uH,AAAAC,2H,gEAAAC,4L,4KAAAC,wL,kDAAAC,s,8ZAAAC,ga,0QAAAC,4Q,0IDG7/F,GAAKlE,SAASe,YACHC,0CACEC,EAAAI,GAAAE,DC,EAAAI,GAAAC,EAAAC,GAAAC,pC,EAAAC,GAAAC,qC,UAAAK,pC,OAAAQ,mC,EAAAC,IAAAC,pC,EAAAC,KAAAC,oC,GAAAK,IAAAC,EAAAC,CAAAC,EAAAC,GAAAC,uB,mBAAAC,uB,WAAAC,GAAAC,E,SAAAC,EAAAC,GAAAC,EAAAC,GAAAC,EAAAC,G

QAAUlB,EAAatF,QACxCmH,MAAQX,EAAQZ,gBAChB1G,OAAS,6BAGhB8D,WAAA,SAAWX,EAAeyE,MA
CpBzE,GAASC,KAAKpD,QAAUmD,GAAS,EAAG,KAChC+E,EAAO5B,SASkB,eAAeI,GAC/BO,EAAU/E,K
AAK6E,MAAM9E,eACtBmE,QAAQF,aAAac,EAAMC,GAAW,WACtCnI,UACE,SAEA,KAIXkE,WAAA,SAA
Wf,QACJmE,QAAQc,YAAYhF,KAAK6E,MAAM9E,SAC/BnD,YAGPqE,QAAA,SAAQlB,UACFA,EAAQ
AKpD,OACRoD,KAAK6E,MAAM9E,GAAOyC,YAElB,SAMAyC,wBAKCC,QACLhF,MAAQ,QACRtD,OAAS,
6BAGhB8D,WAAA,SAAWX,EAAeyE,UACpBzE,GASC,KAAKpD,cACXsD,MAMiF,OAAOpF,EAAO,EAA
GyE,QACvB5H,UACE,MAMXkE,WAAA,SAAWf,QACJG,MAAMiF,OAAOpF,EAAO,QACpBnD,YGPqE,QA
AA,SAAQlB,UACFA,EAAQ,KAAKpD,OACRoD,KAAKE,MAAMH,GAAEX,SCzHTqF,EAAmBhH,EAAWjBiH,
EAA+B,CACnCC,UAAWlH,EACXmH,mBAAoBjH,GAIDkH,wBAAiBjBC,EACACAC,EACACAxD,YAFAuD,IAAAAA,
EAAgCnI,YAChCoI,IAAAAA,EAA2C,SAGtCD,aACAJ,KACAI,QAGAE,GAAKD,OACLxD,MAAQ,IAAIf,IAAIe,
QAChB0D,SAAWH,EAAQH,UAGnBtF,KAAK4F,qBACAC,MAAQ,IAAIC,IAAIC,EAAOC,UAAUC,KAAKC,
CvB6C,EAAQ3B,SAAS2C,iBAAiBjE,GAE/BlF,EAAI,EAAG+D,QAAUoF,EAAOC,UAAUC,KAAKC,
IAAK,KACtCoI,EAASD,EAAMnI,GACjBoI,EAAGL,EAAGM,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAG8
C,GAEzBA,EAAKiB,YACPjB,EAAKiB,WAAWC,YAAYlB,WAAWf,KAAKkC,YAAYnB,EAAKiB,WAAWf,KAAKkC,
CTD,EAAcC,+BAAwBC,EAAuBC,EAAmBC,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,
AKyF,WAAYA,GACtBzF,KAAK2F,QAAQC,GAAGC,QAAQC,KAAKC,KAAKC,KAAKC,KAAKC,KAAKC,KAAKC,KAAKC,
CTvB,KAAK2F,QAAQC,GAAGpE,KAAKqE,KAAKC,KAAKC,KAAKC,KAAKC,KAAKC,KAAKC,KAAKC,KAAKC,KAAKC,
AQM,KAAKN,KDtEH4F,KCsEgCtF,KAAKyF,SDtErCH,SAAUC,IAAAAA,kBAAmB7H,IAAAAA,OLCxBgC,EKA
zB4F,EACK,IAAIL,EAAWvH,GACb6H,EACF,IAAItB,EAASvG,GAEb,IAAIkH,EAAQlH,GAAIJ,EAAI+H,EAAQ/H,OAAQA,IAAK,CAAEgI,EAAOD,EAAQ/H,GAAIiI,EAAOD,EAAKC,
BC,KADD,IAACA,IKDL4F,EAAUC,EAAmB7H,KC0ErD2I,aAAA,SAAAC,SAAaC,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA

GAEDtE,EAAI,EAAGA,EAAIE,EAAQF,IAAK,KACzBkM,EAAW5I,KAAKE,MAAMxD,MAEJ,iBAAbkM,EAC
T5H,GAAO4H,EAEsB,eAAzBjL,QAAQC,IAAIC,WAA2B8K,EAAcpB,EAAMoB,EAAaC,,EAAWlM,SAClF,GA
AIkM,EAAU,KACbC,EAAYL,GAAQI,EAAUR,,EAAkBC,,EAAYC,,GAC5DQ,EAAaC,,MAAMC,,QAAQH,GAAAa
A,EAAUtJ,KAAK,IAAMsJ,EACnEF,EAAcpB,EAAMoB,EAAaG,,EAAapM,,GAC9CsE,GAAO8H,MAIP9H,EAAA
K,KACDjD,EAAO0K,EAAaE,,IAAgB,OAErCN,,EAAWhC,,aAAayB,,EAAa/J,GAAO,KACzCkL,,EAAeX,,EAAOtH,,
MAASjD,,OAAQ6F,,EAAWkE,,GACxDO,,EAAWpI,,YAAY6H,,EAAa/J,GAAO,EAAMkL,,GAG5C/G,,EAAMrF,,KAAKkB,,
WAIRmE,,EAAM3C,KAAAK,,WCtGhB2J,,EAAgB,gBAChBC,,EAA0B,CAAC,,IAAAK,,IAAAK,,IAAAK,,KAOjC,SAASC,,
SAyBlBC,,EACAC,,EACAC,,EACAC,,eAzB6BlM,QAAQmM,I,QAAAAA,aAAUnI,QACVmM,QAAAAA,aAAUrM,IAEJ
kL,EAAS,IAAIoB,EAAOjE,GAAMtBkE,,EAAAe,GAAWbC,,ECdR,SAAwBlM,SAAYmM,IAAIC,WAAWC,,MACXA
AcoJ,OACd,MAAOC,,YAIN,SACLC,,EACA/H,EACAgI,,EACAC,,EACAC,,EACAC,,EACAxN,,EACAyN,,EACAC,,E
ACAC,,UAEQP,,QAED,KAEW,IAAVM,,GAAyC,KAA1BrI,,EAAQwF,,WAAW,GAAW,GAAW,OAAO/G,,EAAcuB,,OAAa,
cAGhF,KACQ,IAAPoI,,EAAU,OAAOpI,,EA/BT,mBAkCTC,,SACKoI,,QAED,SACA,WACI3J,,EAAWuJ,,EAAU,GA
AKhI,GAAU,kBAEpCA,GAAkB,IAAPsI,,EAAzCV,,QAAyCiC,,SAEzCZ,,EACJtI,,EAAQE,,MA3CIqI,,UA2CuL,QAAQ
4K,KD/BXY,EAAiB,SAAAjG,,GAAAA,EAAAkG,,GACxCmF,,EAAa9M,,KAAK2H,,MAAQdkG,,EAAwB,SAAC/H,,EAAOgI,,EAAQC,,EAAOC,,EAAQC,,EAAOxN,,EAAMyN,,EAAOC,,EAAQC,,UAG9B,IAAA8E,,IAAA8E,,EAAA/B,DxB,EAAwB0B0D,,QAAQC,,EAAOC,,EAAQC,,EAAOC,,EAAQC,,EAAOC,,E

B9P,SDiFtC0Q,aAAiBd,GACf/E,GACF6F,EAAMb,OAAOhF,EAAYiF,GAClBY,EAAMT,QAAQH,IACTY,EAITM,EAAcN,GAzEM,SAAhBO,EAAiBC,EAAaC,OEbH5Q,EAAciP,EFc9C9M,EAAQ,OAET,IAAM0O,KAAOF,EACXA,,EAAIG,eAAeD,,KAAQX,GAAUS,EAAIE,,EAAIE,,IAChE1O,EAAMrD,,KAAQkS,GAAUH,OAASF,EAAIE,,GAAM,KAClCJ,EAAcE,,EAAIE,,IAC3B1O,EAAMrD,,WANqD,EAAcuO,,EAAcC,,EAAIE,,GAAMA,,IAEtC1O,,EAAMrD,,KAAQkS,GAAUH,OAASF,EAAIE,,GAAM,SExBU7Q,,EFwBe6Q,,EErBxC,OAHuC5B,,EFwBM4B,,EAAIE,,IAAMC,,kBAAV,EAAAV,,KAAAW,,EAAAC,,EAAAC,,EAAAC

E4J,EAAe/J,wBAAwBsK,EAAepK,EAAYC,SAEzC,eAAzB3K,QAAQC,IAAIC,WAA8BoK,GAAY8K,GACxDA,EAAmBC,GAGdA,EA0BoBC,CACzBf,EACAjK,EACA+B,EACCyB,eAAzBrM,QAAQC,IAAIC,SAA4BwU,EAAAmBU,wBAAqBnP,GAG5EsP,EAAAeZ,EAAEfN,EAAA6BX,EAAAM8B,KAAAO9G,EAAAM8G,KAAAO9B,EAAAM+B,IAAAM/G,EAAAM1V,EAAE/E2V,EAAAc9C,GAAAMyB,GACpBsB,EAAAgBjC,IAAAUhF,OAAAaA,KAAAUgF,GAAAUhF,EAAC3DkH,EAAAkB,OAAGnB,IAAAM3E,KAAAO0E,EACDMAAX1E,EAAAI,IAAAsB,OAAARA,IACLgBAARA,EACAP2E,EAAAgBBH,GAAAKE,EAAAc1E,IAAEnCiD,EACAIA,EAAAkBjD,EAAAK4E,EAAAWxB,IAAClCqB,GACAGAG5E,MAAId2E,EAAAgB3E,GAAAO0E,EAAAc1E,EAAYAirCvC,EAAAM/J,O+BAAS+O,O/BAAMhF,M+BAAAiF,O/BAAMhF,M+BAAAiF,O/BAAMhF,M+BAAAiF

B4R,wBAAyB,CACvBC,OAAQnI,EAAKyH,SAASlY,eAIpBgH,EAAQjB,WACViB,IACDsI,EAAYtI,MAAQA,GAIhB,CAAC2H,6BAAWW,GAAOuC,IAAI,mBAsDhCgH,KAAO,WACLpI,QAAS,QAAzGTP,SAAW,IAAIzP,EAAW,CAAEF,SAAS,CAAEF,SAAS,CAAEF,SAAS

error.js","../../src/vendor/postcss/stringifier.js","../../src/vendor/postcss/stringify.js","../../src/vendor/postcss/node.js","../../src/vendor/postcss/declaration.js","../../src/vendor/postcss/comment.js","../../src/vendor/postcss/parser.js","../../src/vendor/postcss/parse.js","../../src/vendor/postcss/container.js","../../src/vendor/postcss/at-rule.js","../../src/vendor/postcss/list.js","../../src/vendor/postcss/rule.js","../../src/vendor/postcss/warning.js","../../src/vendor/postcss/result.js","../../src/vendor/postcss/lazy-result.js","../../src/vendor/postcss/processor.js","../../src/vendor/postcss/root.js","../../src/vendor/postcss/input.js","../../src/vendor/postcss-safe-parser/safe-parser.js","../../src/vendor/postcss-safe-parser/parse.js","../../src/models/InlineStyle.js","../../src/utils/mixinDeep.js","../../src/utils/determineTheme.js","../../src/utils/isTag.js","../../src/utils/generateDisplayName.js","../../src/models/ThemeProvider.js","../../src/models/StyledNativeComponent.js","../../src/utils/interleave.js","../../src/constructors/css.js","../../src/constructors/constructWithOptions.js","../../src/hoc/withTheme.js","../../src/hooks/useTheme.js","../../src/native/index.js"],"sourcesContent":["// @flow\n/* eslint-disable no-bitwise */\n\nconst AD_REPLACER_R = /(a)(d)/gi;\n\n/* This is the \"capacity\" of our alphabet i.e. 2x26 for all letters plus their capitalised\n * counterparts */\nconst charsLength = 52;\n\n/* start at 75 for 'a' until 'z' (25) and then start at 65 for capitalised letters */\nconst getAlphabeticChar = (code: number): string =>\n String.fromCharCode(code + (code > 25 ? 39 : 97));\n\n/* input a number, usually a hash and convert it to base-52 */\nexport default function generateAlphabeticName(code: number): string {\n let name = '';\n let x;\n\n /* get a char and divide\n by alphabet-length */\n for (x = Math.abs(code); x > charsLength; x = (x / charsLength) | 0) {\n   name = getAlphabeticChar(x % charsLength) + name;\n }\n\n return (getAlphabeticChar(x % charsLength) + name).replace(AD_REPLACER_R, '$1-$2');\n}\n","// @flow\n/* eslint-disable */\n\nexport const SEED = 5381;\n\n// When we have separate strings it's useful to run a progressive\n// version of djb2 where we pretend that we're still looping over\n// the same string\nexport const phash = (h: number, x: string): number => {\n let i = x.length;\n\n while (i) {\n   h = (h * 33) ^ x.charCodeAt(--i);\n }\n\n return h;\n};\n\n// This is a djb2 hashing function\nexport const hash = (x: string): number => {\n return phash(SEED, x);\n};\n","// @flow\n/* eslint-disable */\nimport generateAlphabeticName from './generateAlphabeticName';\nimport { hash } from './hash';\n\nexport default (str: string): string => {\n return generateAlphabeticName(hash(str) >>> 0);\n};\n","// @flow\nimport type { IStyledComponent } from '../types';\n\nexport default function getComponentName(\n target: $PropertyType<IStyledComponent, 'target'>\n): string {\n return (\n   (process.env.NODE_ENV !== 'production' ? typeof target === 'string' && target : false) ||\n   // $FlowFixMe\n   target.displayName ||\n   // $FlowFixMe\n   target.name ||\n   'Component'\n);\n}\n","// @flow\nexport default function isFunction(test: any): boolean %checks {\n return typeof test === 'function';\n}\n","// @flow\nexport default function isStatelessFunction(test: any): boolean {\n return (\n   typeof test === 'function'\n   && !(\n   test.prototype\n   && test.prototype.isReactComponent\n   )\n);\n}\n","// @flow\nimport { typeOf } from 'react-is';\n\nexport default (x: any): boolean =>\n x !== null &&\n typeof x === 'object' &&\n (x.toString ? x.toString() : Object.prototype.toString.call(x)) === '[object Object]' &&\n !typeOf(x);\n","// @flow\nexport default function isStyledComponent(target: any): boolean %checks {\n return target && typeof target.styledComponentId === 'string';\n}\n","// @flow\n\ndeclare var SC_DISABLE_SPEEDY: ?boolean;\ndeclare var __VERSION__: string;\n\nexport const SC_ATTR: string =\n (typeof process !== 'undefined' &&\n   typeof process.env !== 'undefined' &&\n   (process.env.REACT_APP_SC_ATTR || process.env.SC_ATTR)) ||\n 'data-styled';\n\nexport const SC_ATTR_ACTIVE = 'active';\nexport const SC_ATTR_VERSION = 'data-styled-version';\nexport const SC_VERSION = __VERSION__;\nexport const SPLITTER = '/*!sc*/\\n';\n\nexport const IS_BROWSER = typeof window !== 'undefined' && 'HTMLElement' in window;\n\nexport const DISABLE_SPEEDY = Boolean(\n typeof SC_DISABLE_SPEEDY === 'boolean'\n   ? SC_DISABLE_SPEEDY\n   : typeof process !== 'undefined' &&\n   typeof process.env !== 'undefined'\n   ? typeof process.env.REACT_APP_SC_DISABLE_SPEEDY !== 'undefined' &&\n   process.env.REACT_APP_SC_DISABLE_SPEEDY !== ''\n   ? process.env.REACT_APP_SC_DISABLE_SPEEDY

=== 'false'\n ? false\n : process.env.REACT_APP_SC_DISABLE_SPEEDY\n : typeof process.env.SC_DISABLE_SPEEDY !== 'undefined' && process.env.SC_DISABLE_SPEEDY !== ''\n ? process.env.SC_DISABLE_SPEEDY === 'false'\n ? false\n : process.env.SC_DISABLE_SPEEDY\n : process.env.NODE_ENV !== 'production'\n : false\n);\n\n// Shared empty execution context when generating static styles\nexport const STATIC_EXECUTION_CONTEXT = {};\n","// @flow\nexport const EMPTY_ARRAY = Object.freeze([]);\nexport const EMPTY_OBJECT = Object.freeze({});\n","export default {\"1\":\"Cannot create styled-component for component: %s.\\n\\n\",\"2\":\"Can't collect styles once you've consumed a `ServerStyleSheet`'s styles! `ServerStyleSheet` is a one off instance for each server-side render cycle.\\n\\n- Are you trying to reuse it across renders?\\n- Are you accidentally calling collectStyles twice?\\n\\n\",\"3\":\"Streaming SSR is only supported in a Node.js environment;
Please do not try to call this method in the browser.\\n\\n\",\"4\":\"The `StyleSheetManager` expects a valid target or sheet prop!\\n\\n- Does this error occur on the client and is your target falsy?\\n- Does this error occur on the server and is the sheet falsy?\\n\\n\",\"5\":\"The clone method cannot be used on the client!\\n\\n- Are you running in a client-like environment on the server?\\n- Are you trying to run SSR on the client?\\n\\n\",\"6\":\"Trying to insert a new style tag, but the given Node is unmounted!\\n\\n- Are you using a custom target that isn't mounted?\\n- Does your document not have a valid head element?\\n- Have you accidentally removed a style tag manually?\\n\\n\",\"7\":\"ThemeProvider: Please return an object from your \\\"theme\\\" prop function, e.g.\\n\\n```js\\ntheme={() => ({})}\\n```\\n\\n\",\"8\":\"ThemeProvider: Please make your \\\"theme\\\" prop an object.\\n\\n\",\"9\":\"Missing document `<head>`\\n\\n\",\"10\":\"Cannot find a StyleSheet instance.
Usually this happens if there are multiple copies of styled-components loaded at once. Check out this issue for how to troubleshoot and fix the common cases where this situation can happen: https://github.com/styled-components/styled-components/issues/1941#issuecomment-417862021\\n\\n\",\"11\":\"_This error was replaced with a dev-time warning, it will be deleted for v4 final._ [createGlobalStyle] received children which will not be rendered. Please use the component without passing children elements.\\n\\n\",\"12\":\"It seems you are interpolating a keyframe declaration (%s) into an untagged string. This was supported in styled-components v3, but is not longer supported in v4 as keyframes are now injected on-demand. Please wrap your string in the css\\`\\`\\` helper which ensures the styles are injected correctly. See https://www.styled-components.com/docs/api#css\\n\\n\",\"13\":\"%s is not a styled component and cannot be referred to via component selector. See https://www.styled-components.com/docs/advanced#referring-to-other-components
for more details.\\n\\n\",\"14\":\"ThemeProvider: \\\"theme\\\" prop is required.\\n\\n\",\"15\":\"A stylis plugin has been supplied that is not named. We need a name for each plugin to be able to prevent styling collisions between different stylis configurations within the same app. Before you pass your plugin to `<StyleSheetManager stylisPlugins={[]}>`, please make sure each plugin is uniquely-named,
e.g.\\n\\n```js\\nObject.defineProperty(importedPlugin, 'name', { value: 'some-unique-name' });\\n```\\n\\n\",\"16\":\"Reached the limit of how many styled components may be created at group %s.\\nYou may only create up to 1,073,741,824 components. If you're creating components dynamically,\\nas for instance in your render method then you may be running into this limitation.\\n\\n\",\"17\":\"CSSStyleSheet could not be found on HTMLStyleElement.\\nHas styled-components' style tag been unmounted or altered by another script?\\n\"};","// @flow\nimport errorMap from './errors';\n\nconst ERRORS = process.env.NODE_ENV !== 'production' ? errorMap : {};\n\n/**\n * super basic version of sprintf\n */\nfunction format(...args) {\n let a = args[0];\n const b = [];\n\n for (let c = 1, len = args.length; c < len; c += 1) {\n b.push(args[c]);\n }\n\n b.forEach(d => {\n a = a.replace(/%[a-z]/, d);\n });\n\n return a;\n}\n\n/**\n * Create an error file out of errors.md for development and a simple web link to the full errors\n * in production mode.\n */\nexport default function throwStyledComponentsError(\n code: string | number,\n ...interpolations: Array<any>\n) {\n if (process.env.NODE_ENV === 'production') {\n throw new Error(\n `An error occurred. See https://git.io/JUIaE#${code} for more information.${\n interpolations.length > 0 ? ` Args: ${interpolations.join(', ')}` : ''\n }\n);\n } else {\n throw new Error(format(ERRORS[code], ...interpolations).trim());\n }\n}\n","//

@flow\n/* eslint-disable no-use-before-define */\n\nimport type { GroupedTag, Tag } from './types';\nimport { SPLITTER } from '../constants';\nimport throwStyledError from '../utils/error';\n\n/** Create a GroupedTag with an underlying Tag implementation */\nexport const makeGroupedTag = (tag: Tag): GroupedTag => {\n return new DefaultGroupedTag(tag);\n};\n\nconst BASE_SIZE = 1 << 9;\n\nclass DefaultGroupedTag implements GroupedTag {\n groupSizes: Uint32Array;\n\n length: number;\n\n tag: Tag;\n\n constructor(tag: Tag) {\n this.groupSizes = new Uint32Array(BASE_SIZE);\n this.length = BASE_SIZE;\n this.tag = tag;\n }\n\n indexOfGroup(group: number): number {\n let index = 0;\n for (let i = 0; i < group; i++) {\n index += this.groupSizes[i];\n }\n\n return index;\n }\n\n insertRules(group: number, rules: string[]): void {\n if (group >= this.groupSizes.length) {\n const oldBuffer = this.groupSizes;\n const oldSize = oldBuffer.length;\n\n let newSize = oldSize;\n while (group >= newSize) {\n newSize <<= 1;\n if (newSize < 0) {\n throwStyledError(16, `${group}`);\n }\n }\n\n this.groupSizes = new Uint32Array(newSize);\n this.groupSizes.set(oldBuffer);\n this.length = newSize;\n\n for (let i = oldSize; i < newSize; i++) {\n this.groupSizes[i] = 0;\n }\n }\n\n let ruleIndex = this.indexOfGroup(group + 1);\n for (let i = 0, l = rules.length; i < l; i++) {\n if (this.tag.insertRule(ruleIndex, rules[i])) {\n this.groupSizes[group]++;\n ruleIndex++;\n }\n }\n }\n\n clearGroup(group: number): void {\n if (group < this.length) {\n const length = this.groupSizes[group];\n const startIndex = this.indexOfGroup(group);\n const endIndex = startIndex + length;\n\n this.groupSizes[group] = 0;\n\n for (let i = startIndex; i < endIndex; i++) {\n this.tag.deleteRule(startIndex);\n }\n }\n }\n\n getGroup(group: number): string {\n let css = '';\n if (group >= this.length || this.groupSizes[group] === 0) {\n return css;\n }\n\n const length = this.groupSizes[group];\n const startIndex = this.indexOfGroup(group);\n const endIndex = startIndex + length;\n\n for (let i = startIndex; i < endIndex; i++) {\n css += `${this.tag.getRule(i)}${SPLITTER}`;\n }\n\n return css;\n }\n}\n","// @flow\n\nimport throwStyledError from '../utils/error';\n\nconst MAX_SMI = 1 << 31 - 1;\n\nlet groupIDRegister: Map<string, number> = new Map();\nlet reverseRegister: Map<number, string> = new Map();\nlet nextFreeGroup = 1;\n\nexport const resetGroupIds = () => {\n groupIDRegister = new Map();\n reverseRegister = new Map();\n nextFreeGroup = 1;\n};\n\nexport const getGroupForId = (id: string): number => {\n if (groupIDRegister.has(id)) {\n return (groupIDRegister.get(id): any);\n }\n\n while (reverseRegister.has(nextFreeGroup)) {\n nextFreeGroup++;\n }\n\n const group = nextFreeGroup++;\n\n if (\n process.env.NODE_ENV !== 'production' &&\n ((group | 0) < 0 || group > MAX_SMI)\n) {\n throwStyledError(16, `${group}`);\n }\n\n groupIDRegister.set(id, group);\n reverseRegister.set(group, id);\n return group;\n};\n\nexport const getIdForGroup = (group: number): void | string => {\n return reverseRegister.get(group);\n};\n\nexport const setGroupForId = (id: string, group: number) => {\n if (group >= nextFreeGroup) {\n nextFreeGroup = group + 1;\n }\n\n groupIDRegister.set(id, group);\n reverseRegister.set(group, id);\n};\n","// @flow\n\nimport { SPLITTER, SC_ATTR, SC_ATTR_ACTIVE, SC_ATTR_VERSION, SC_VERSION } from '../constants';\nimport { getIdForGroup, setGroupForId } from './GroupIDAllocator';\nimport type { Sheet } from './types';\n\nconst SELECTOR = `style[${SC_ATTR}][${SC_ATTR_VERSION}=\"${SC_VERSION}\"]`;\nconst MARKER_RE = new RegExp(`^${SC_ATTR}\\\\.g(\\\\d+)\\\\[id=\"([\\\\w\\\\d-]+)\"\\\\].*?\"([^\"]*)`);\n\nexport const outputSheet = (sheet: Sheet) => {\n const tag = sheet.getTag();\n const { length } = tag;\n\n let css = '';\n\n for (let group = 0; group < length; group++) {\n const id = getIdForGroup(group);\n if (id === undefined) continue;\n\n const names = sheet.names.get(id);\n const rules = tag.getGroup(group);\n if (!names || !rules || !names.size) continue;\n\n const selector = `${SC_ATTR}.g${group}[id=\"${id}\"]`;\n\n let content = '';\n if (names !== undefined) {\n names.forEach(name => {\n if (name.length > 0) {\n content += `${name},`;\n }\n });\n }\n\n // NOTE: It's easier to collect rules and have the marker\n // after the actual rules to simplify the rehydration\n css += `${rules}${selector}{content:\"${content}\"}${SPLITTER}`;\n }\n\n return css;\n};\n\nconst rehydrateNamesFromContent = (sheet: Sheet, id: string, content: string) => {\n const names = content.split(',');\n let name;\n\n for (let i = 0, l = names.length; i < l; i++) {\n // eslint-disable-next-line\n if ((name = names[i])) {\n sheet.registerName(id, name);\n }\n }\n};\n\nconst rehydrateSheetFromTag = (sheet: Sheet, style:

HTMLStyleElement) => {\n const parts = (style.textContent || '').split(SPLITTER);\n const rules: string[] = [];\n\n for (let i = 0, l = parts.length; i < l; i++) {\n   const part = parts[i].trim();\n   if (!part) continue;\n\n   const marker = part.match(MARKER_RE);\n\n   if (marker) {\n   const group = parseInt(marker[1], 10) | 0;\n   const id = marker[2];\n\n   if (group !== 0) {\n   // Rehydrate componentId to group index mapping\n   setGroupForId(id, group);\n   // Rehydrate names and rules\n   // looks like: data-styled.g11[id=\"idA\"]{content:\"nameA,\"}\n   rehydrateNamesFromContent(sheet, id, marker[3]);\n   sheet.getTag().insertRules(group, rules);\n   }\n\n   rules.length = 0;\n   } else {\n   rules.push(part);\n   }\n }\n};\n\nexport const rehydrateSheet = (sheet: Sheet) => {\n const nodes = document.querySelectorAll(SELECTOR);\n\n for (let i = 0, l = nodes.length; i < l; i++) {\n   const node = ((nodes[i]: any): HTMLStyleElement);\n   if (node && node.getAttribute(SC_ATTR) !== SC_ATTR_ACTIVE) {\n   rehydrateSheetFromTag(sheet, node);\n\n   if (node.parentNode) {\n   node.parentNode.removeChild(node);\n   }\n   }\n }\n};\n","// @flow\n/* eslint-disable camelcase, no-undef */\n\ndeclare var __webpack_nonce__: string;\n\nconst getNonce = () => {\n return typeof __webpack_nonce__ !== 'undefined' ? __webpack_nonce__ : null;\n};\n\nexport default getNonce;\n","// @flow\n\nimport { SC_ATTR, SC_ATTR_ACTIVE, SC_ATTR_VERSION, SC_VERSION } from '../constants';\nimport getNonce from '../utils/nonce';\nimport throwStyledError from '../utils/error';\n\nconst ELEMENT_TYPE = 1; /* Node.ELEMENT_TYPE */\n\n/** Find last style element if any inside target */\nconst findLastStyleTag = (target: HTMLElement): void | HTMLStyleElement => {\n const { childNodes } = target;\n\n for (let i = childNodes.length; i >= 0; i--) {\n   const child = ((childNodes[i]: any): ?HTMLElement);\n   if (child && child.nodeType === ELEMENT_TYPE && child.hasAttribute(SC_ATTR)) {\n   return ((child: any): HTMLStyleElement);\n   }\n }\n\n return undefined;\n};\n\n/** Create a style element inside `target` or <head> after the last */\nexport const makeStyleTag = (target?: HTMLElement): HTMLStyleElement => {\n const head = ((document.head: any): HTMLElement);\n const parent = target || head;\n const style = document.createElement('style');\n const prevStyle = findLastStyleTag(parent);\n const nextSibling = prevStyle !== undefined ? prevStyle.nextSibling : null;\n\n style.setAttribute(SC_ATTR, SC_ATTR_ACTIVE);\n style.setAttribute(SC_ATTR_VERSION, SC_VERSION);\n\n const nonce = getNonce();\n\n if (nonce) style.setAttribute('nonce', nonce);\n\n parent.insertBefore(style, nextSibling);\n\n return style;\n};\n\n/** Get the CSSStyleSheet instance for a given style element */\nexport const getSheet = (tag: HTMLStyleElement): CSSStyleSheet => {\n if (tag.sheet) {\n   return ((tag.sheet: any): CSSStyleSheet);\n }\n\n // Avoid Firefox quirk where the style element might not have a sheet property\n const { styleSheets } = document;\n for (let i = 0, l = styleSheets.length; i < l; i++) {\n   const sheet = styleSheets[i];\n   if (sheet.ownerNode === tag) {\n   return ((sheet: any): CSSStyleSheet);\n   }\n }\n\n throwStyledError(17);\n return (undefined: any);\n};\n","// @flow\n/* eslint-disable no-use-before-define */\n\nimport { makeStyleTag, getSheet } from './dom';\nimport type { SheetOptions, Tag } from './types';\n\n/** Create a CSSStyleSheet-like tag depending on the environment */\nexport const makeTag = ({ isServer, useCSSOMInjection, target }: SheetOptions): Tag => {\n if (isServer) {\n   return new VirtualTag(target);\n } else if (useCSSOMInjection) {\n   return new CSSOMTag(target);\n } else {\n   return new TextTag(target);\n }\n};\n\nexport class CSSOMTag implements Tag {\n element: HTMLStyleElement;\n\n sheet: CSSStyleSheet;\n\n length: number;\n\n constructor(target?: HTMLElement) {\n   const element = (this.element = makeStyleTag(target));\n\n   // Avoid Edge bug where empty style elements don't create sheets\n   element.appendChild(document.createTextNode(''));\n\n   this.sheet = getSheet(element);\n   this.length = 0;\n }\n\n insertRule(index: number, rule: string): boolean {\n   try {\n   this.sheet.insertRule(rule, index);\n   this.length++;\n   return true;\n   } catch (_error) {\n   return false;\n   }\n }\n\n deleteRule(index: number): void {\n   this.sheet.deleteRule(index);\n   this.length--;\n }\n\n getRule(index: number): string {\n   const rule = this.sheet.cssRules[index];\n   // Avoid IE11 quirk where cssText is inaccessible on some invalid rules\n   if (rule !== undefined && typeof rule.cssText === 'string') {\n   return rule.cssText;\n   } else {\n   return '';\n   }\n }\n}\n\n/** A Tag that emulates the CSSStyleSheet API but uses text nodes */\nexport class TextTag implements Tag {\n element: HTMLStyleElement;\n\n nodes: NodeList<Node>;\n\n length: number;\n\n

constructor(target?: HTMLElement) {\n const element = (this.element = makeStyleTag(target));\n this.nodes = element.childNodes;\n this.length = 0;\n }\n\n insertRule(index: number, rule: string): boolean {\n if (index <= this.length && index >= 0) {\n const node = document.createTextNode(rule);\n const refNode = this.nodes[index];\n this.element.insertBefore(node, refNode || null);\n this.length++;\n return true;\n } else {\n return false;\n }\n }\n\n deleteRule(index: number): void {\n this.element.removeChild(this.nodes[index]);\n this.length--;\n }\n\n getRule(index: number): string {\n if (index
 < this.length) {\n return this.nodes[index].textContent;\n } else {\n return '';\n }\n }\n}\n\n/** A completely virtual (server-side) Tag that doesn't manipulate the DOM */\nexport class VirtualTag implements Tag {\n rules: string[];\n\n length: number;\n\n constructor(_target?: HTMLElement) {\n this.rules = [];\n this.length = 0;\n }\n\n insertRule(index: number, rule: string): boolean {\n if (index <= this.length) {\n this.rules.splice(index, 0, rule);\n this.length++;\n return true;\n } else {\n return false;\n }\n }\n\n deleteRule(index: number): void {\n this.rules.splice(index, 1);\n this.length--;\n }\n\n getRule(index: number): string {\n if (index < this.length) {\n return this.rules[index];\n } else {\n return '';\n }\n }\n}\n","// @flow\nimport { DISABLE_SPEEDY, IS_BROWSER } from '../constants';\nimport { EMPTY_OBJECT } from '../utils/empties';\nimport { makeGroupedTag } from './GroupedTag';\nimport
 { getGroupForId } from './GroupIDAllocator';\nimport { outputSheet, rehydrateSheet } from './Rehydration';\nimport { makeTag } from './Tag';\nimport type { GroupedTag, Sheet, SheetOptions } from './types';\n\nlet SHOULD_REHYDRATE = IS_BROWSER;\n\ntype SheetConstructorArgs = {\n isServer?: boolean,\n useCSSOMInjection?: boolean,\n target?: HTMLElement,\n};\n\ntype GlobalStylesAllocationMap = { [key: string]: number };\ntype NamesAllocationMap = Map<string, Set<string>>;\n\nconst defaultOptions: SheetOptions = {\n isServer: !IS_BROWSER,\n useCSSOMInjection: !DISABLE_SPEEDY,\n};\n\n/** Contains the main stylesheet logic for stringification and caching */\nexport default class StyleSheet implements Sheet {\n gs: GlobalStylesAllocationMap;\n\n names: NamesAllocationMap;\n\n options: SheetOptions;\n\n server: boolean;\n\n tag: void | GroupedTag;\n\n /** Register a group ID to give it an index */\n static registerId(id: string): number {\n return getGroupForId(id);\n
  }\n\n constructor(\n options: SheetConstructorArgs = EMPTY_OBJECT,\n globalStyles?: GlobalStylesAllocationMap = {},\n names?: NamesAllocationMap\n) {\n this.options = {\n ...defaultOptions,\n ...options,\n };\n\n this.gs = globalStyles;\n this.names = new Map(names);\n this.server = !!options.isServer;\n\n // We rehydrate only once and use the sheet that is created first\n if (!this.server && IS_BROWSER && SHOULD_REHYDRATE) {\n SHOULD_REHYDRATE = false;\n rehydrateSheet(this);\n }\n }\n\n reconstructWithOptions(options: SheetConstructorArgs, withNames?: boolean = true) {\n return new StyleSheet(\n { ...this.options, ...options },\n this.gs,\n (withNames && this.names) || undefined\n);\n }\n\n allocateGSInstance(id: string) {\n return (this.gs[id] = (this.gs[id] || 0) + 1);\n }\n\n /** Lazily initialises a GroupedTag for when it's actually needed */\n getTag(): GroupedTag {\n return this.tag
 || (this.tag = makeGroupedTag(makeTag(this.options)));\n }\n\n /** Check whether a name is known for caching */\n hasNameForId(id: string, name: string): boolean {\n return this.names.has(id) && (this.names.get(id): any).has(name);\n }\n\n /** Mark a group's name as known for caching */\n registerName(id: string, name: string) {\n getGroupForId(id);\n\n if (!this.names.has(id)) {\n const groupNames = new Set();\n groupNames.add(name);\n this.names.set(id, groupNames);\n } else {\n (this.names.get(id): any).add(name);\n }\n }\n\n /** Insert new rules which also marks the name as known */\n insertRules(id: string, name: string, rules: string[]) {\n this.registerName(id, name);\n this.getTag().insertRules(getGroupForId(id), rules);\n }\n\n /** Clears all cached names for a given group ID */\n clearNames(id: string) {\n if (this.names.has(id)) {\n (this.names.get(id): any).clear();\n }\n }\n\n /** Clears all rules for a given
 group ID */\n clearRules(id: string) {\n this.getTag().clearGroup(getGroupForId(id));\n this.clearNames(id);\n }\n\n /** Clears the entire tag which deletes all rules but not its names */\n clearTag() {\n // NOTE: This does not clear the names, since it's only used during SSR\n // so that we can continuously output only new rules\n this.tag = undefined;\n }\n\n /** Outputs the current sheet as a CSS string with markers for SSR */\n toString(): string {\n

return outputSheet(this);\n }\n}\n","/**\n * MIT License\n *\n * Copyright (c) 2016 Sultan Tarimo\n *\n * Permission is hereby granted, free of charge, to any person obtaining a copy of\n * this software and associated documentation files (the \"Software\"),\n * to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or\n * sell copies of the Software and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:\n *\n * The above copyright notice and this permission notice shall be included in all\n * copies or substantial portions of the Software.\n *\n * THE SOFTWARE IS PROVIDED \"AS IS\", WITHOUT WARRANTY OF ANY KIND, EXPRESS\n * OR IMPLIED INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,\n * FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE\n * AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,\n * WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR\n * IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.\n */\n/* eslint-disable */\n\nexport default function(insertRule) {\n const delimiter = '/*|*/';\n const needle = `${delimiter}}`;\n\n function toSheet(block) {\n if (block) {\n   try {\n   insertRule(`${block}}`);\n   } catch (e) {}\n }\n }\n\n return function ruleSheet(\n context,\n content,\n selectors,\n
parents,\n line,\n column,\n length,\n ns,\n depth,\n at\n) {\n switch (context) {\n   // property\n   case 1:\n   // @import\n   if (depth === 0 && content.charCodeAt(0) === 64) return insertRule(`${content};`), '';\n   break;\n   // selector\n   case 2:\n   if (ns === 0) return content + delimiter;\n   break;\n   // at-rule\n   case 3:\n   switch (ns) {\n   // @font-face, @page\n   case 102:\n   case 112:\n   return insertRule(selectors[0] + content), '';\n   default:\n   return content + (at === 0 ? delimiter : '');\n   }\n   case -2:\n   content.split(needle).forEach(toSheet);\n }\n};\n}\n","import Stylis from '@emotion/stylis';\nimport { type Stringifier } from '../types';\nimport { EMPTY_ARRAY, EMPTY_OBJECT } from './empties';\nimport throwStyledError from './error';\nimport { phash, SEED } from './hash';\nimport insertRulePlugin from
'./stylisPluginInsertRule';\n\nconst COMMENT_REGEX = /^\\s*\\/\\/.*$/gm;\nconst COMPLEX_SELECTOR_PREFIX = [':', '[', '.', '#'];\n\ntype StylisInstanceConstructorArgs = {\n options?: Object,\n plugins?: Array<Function>,\n};\n\nexport default function createStylisInstance({\n options = EMPTY_OBJECT,\n plugins = EMPTY_ARRAY,\n}: StylisInstanceConstructorArgs = EMPTY_OBJECT) {\n const stylis = new Stylis(options);\n\n // Wrap `insertRulePlugin to build a list of rules,\n // and then make our own plugin to return the rules. This\n // makes it easier to hook into the existing SSR architecture\n\n let parsingRules = [];\n\n // eslint-disable-next-line consistent-return\n const returnRulesPlugin = context => {\n   if (context === -2) {\n   const parsedRules = parsingRules;\n   parsingRules = [];\n   return parsedRules;\n   }\n };\n\n const parseRulesPlugin = insertRulePlugin(rule => {\n   parsingRules.push(rule);\n });\n\n let _componentId: string;\n let _selector:
string;\n let _selectorRegexp: RegExp;\n let _consecutiveSelfRefRegExp: RegExp;\n\n const selfReferenceReplacer = (match, offset, string) => {\n   if (\n   // do not replace the first occurrence if it is complex (has a modifier)\n   (offset === 0 ? COMPLEX_SELECTOR_PREFIX.indexOf(string[_selector.length]) === -1 : true) &&\n   // no consecutive self refs (.b.b); that is a precedence boost and treated differently\n   !string.match(_consecutiveSelfRefRegExp)\n   ) {\n   return `.${_componentId}`;\n   }\n\n   return match;\n };\n\n /**\n   * When writing a style like\n   *\n   * & + & {\n   *   color: red;\n   * }\n   *\n   * The second ampersand should be a reference to the static component class. stylis\n   * has no knowledge of static class so we have to intelligently replace the base selector.\n   *\n   * https://github.com/thysultan/stylis.js/tree/v3.5.4#plugins <- more info about the context phase values\n   * \"2\" means this plugin is taking effect at the
very end after all other processing is complete\n   */\n const selfReferenceReplacementPlugin = (context, _, selectors) => {\n   if (context === 2 && selectors.length && selectors[0].lastIndexOf(_selector) > 0) {\n   // eslint-disable-next-line no-param-reassign\n   selectors[0] = selectors[0].replace(_selectorRegexp, selfReferenceReplacer);\n   }\n };\n\n stylis.use([...plugins, selfReferenceReplacementPlugin, parseRulesPlugin,

returnRulesPlugin]);\n\n function stringifyRules(css, selector, prefix, componentId = '&'): Stringifier {\n   const flatCSS = css.replace(COMMENT_REGEX, '');\n   const cssStr = selector && prefix ? `${prefix} ${selector} { ${flatCSS} }` : flatCSS;\n\n   // stylis has no concept of state to be passed to plugins\n   // but since JS is single-threaded, we can rely on that to ensure\n   // these properties stay in sync with the current stylis run\n   _componentId = componentId;\n   _selector = selector;\n   _selectorRegexp = new RegExp(`\\\\${_selector}\\\\b`, 'g');\n   _consecutiveSelfRefRegExp = new RegExp(`(\\\\${_selector}\\\\b){2,}`);\n\n   return stylis(prefix || !selector ? '' : selector, cssStr);\n }\n\n stringifyRules.hash = plugins.length\n   ? plugins\n   .reduce((acc, plugin) => {\n   if (!plugin.name) {\n   throwStyledError(15);\n   }\n\n   return phash(acc, plugin.name);\n   }, SEED)\n   .toString()\n   : '';\n\n return stringifyRules;\n}\n","// @flow\nimport React, { type Context, type Node, useContext, useEffect, useMemo, useState } from 'react';\nimport shallowequal from 'shallowequal';\nimport StyleSheet from '../sheet';\nimport type { Stringifier } from '../types';\nimport createStylisInstance from '../utils/stylis';\n\ntype Props = {\n children?: Node,\n disableCSSOMInjection?: boolean,\n disableVendorPrefixes?: boolean,\n sheet?: StyleSheet,\n stylisPlugins?: Array<Function>,\n target?: HTMLElement,\n};\n\nexport const StyleSheetContext: Context<StyleSheet | void> = React.createContext();\nexport const StyleSheetConsumer = StyleSheetContext.Consumer;\nexport const StylisContext: Context<Stringifier | void> = React.createContext();\nexport const StylisConsumer = StylisContext.Consumer;\n\nexport const masterSheet: StyleSheet = new StyleSheet();\nexport const masterStylis: Stringifier = createStylisInstance();\n\nexport function useStyleSheet(): StyleSheet {\n return useContext(StyleSheetContext) || masterSheet;\n}\n\nexport function useStylis(): Stringifier {\n return useContext(StylisContext) || masterStylis;\n}\n\nexport default function StyleSheetManager(props: Props) {\n const [plugins, setPlugins] = useState(props.stylisPlugins);\n const contextStyleSheet = useStyleSheet();\n\n const styleSheet = useMemo(() => {\n   let sheet = contextStyleSheet;\n\n   if (props.sheet) {\n   // eslint-disable-next-line prefer-destructuring\n   sheet = props.sheet;\n   } else if (props.target) {\n   sheet = sheet.reconstructWithOptions({ target: props.target }, false);\n   }\n\n   if (props.disableCSSOMInjection) {\n   sheet = sheet.reconstructWithOptions({ useCSSOMInjection: false });\n   }\n\n   return sheet;\n }, [props.disableCSSOMInjection, props.sheet, props.target]);\n\n const stylis = useMemo(\n   () =>\n   createStylisInstance({\n   options: { prefix: !props.disableVendorPrefixes },\n   plugins,\n   }),\n   [props.disableVendorPrefixes, plugins]\n);\n\n useEffect(() => {\n   if (!shallowequal(plugins, props.stylisPlugins)) setPlugins(props.stylisPlugins);\n }, [props.stylisPlugins]);\n\n return (\n   <StyleSheetContext.Provider value={styleSheet}>\n   <StylisContext.Provider value={stylis}>\n   {process.env.NODE_ENV !== 'production'\n   ? React.Children.only(props.children)\n   : props.children}\n   </StylisContext.Provider>\n   </StyleSheetContext.Provider>\n);\n}\n","// @flow\nimport StyleSheet from '../sheet';\nimport { type Stringifier } from '../types';\nimport throwStyledError from '../utils/error';\nimport { masterStylis } from './StyleSheetManager';\n\nexport default class Keyframes {\n id: string;\n\n name: string;\n\n rules: string;\n\n constructor(name: string, rules: string) {\n   this.name = name;\n   this.id = `sc-keyframes-${name}`;\n   this.rules = rules;\n }\n\n inject = (styleSheet: StyleSheet, stylisInstance: Stringifier = masterStylis) => {\n   const resolvedName = this.name + stylisInstance.hash;\n\n   if (!styleSheet.hasNameForId(this.id, resolvedName)) {\n   styleSheet.insertRules(\n   this.id,\n   resolvedName,\n   stylisInstance(this.rules, resolvedName, '@keyframes')\n   );\n   }\n };\n\n toString = () => {\n   return throwStyledError(12, String(this.name));\n };\n\n getName(stylisInstance: Stringifier = masterStylis) {\n   return this.name + stylisInstance.hash;\n }\n}\n","// @flow\n\n/**\n * inlined version of\n * https://github.com/facebook/fbjs/blob/master/packages/fbjs/src/core/hyphenateStyleName.js\n */\n\nconst uppercaseCheck = /([A-Z])/;\nconst uppercasePattern = /([A-Z])/g;\nconst msPattern = /^ms-/;\nconst prefixAndLowerCase = (char: string): string => `-${char.toLowerCase()}`;\n\n/**\n * Hyphenates a camelcased CSS property name, for example:\n *\n *   > hyphenateStyleName('backgroundColor')\n *   < \"background-color\"\n *   > hyphenateStyleName('MozTransition')\n *   < \"-moz-transition\"\n *   >

hyphenateStyleName('msTransition')\n * < \"-ms-transition\"'\n *\n * As Modernizr suggests (http://modernizr.com/docs/#prefixed), an `ms` prefix\n * is converted to `-ms-`.\n *\n * @param {string} string\n * @return {string}\n */\nexport default function hyphenateStyleName(string: string): string {\n return uppercaseCheck.test(string)\n ? string\n .replace(uppercasePattern, prefixAndLowerCase)\n .replace(msPattern, '-ms-')\n : string;\n}\n","// @flow\nimport unitless from '@emotion/unitless';\n\n// Taken from https://github.com/facebook/react/blob/b87aabdfe1b7461e7331abb3601d9e6bb27544bc/packages/react-dom/src/shared/dangerousStyleValue.js\nexport
 default function addUnitIfNeeded(name: string, value: any): any {\n // https://github.com/amilajack/eslint-plugin-flowtype-errors/issues/133\n // $FlowFixMe\n if (value == null || typeof value === 'boolean' || value === '') {\n return '';\n }\n\n if (typeof value === 'number' && value !== 0 && !(name in unitless) && !name.startsWith('--')) {\n return `${value}px`; // Presumes implicit 'px' suffix for unitless numbers except for CSS variables\n }\n\n return String(value).trim();\n}\n","// @flow\nimport { isElement } from 'react-is';\nimport getComponentName from './getComponentName';\nimport isFunction from './isFunction';\nimport isStatelessFunction from './isStatelessFunction';\nimport isPlainObject from './isPlainObject';\nimport isStyledComponent from './isStyledComponent';\nimport Keyframes from '../models/Keyframes';\nimport hyphenate from
 './hyphenateStyleName';\nimport addUnitIfNeeded from './addUnitIfNeeded';\nimport { type Stringifier } from '../types';\n\n/**\n * It's falsish not falsy because 0 is allowed.\n */\nconst isFalsish = chunk => chunk === undefined || chunk === null || chunk === false || chunk === '';\n\nexport const objToCssArray = (obj: Object, prevKey?: string): Array<string | Function> => {\n const rules = [];\n\n for (const key in obj) {\n if (!obj.hasOwnProperty(key) || isFalsish(obj[key])) continue;\n\n if ((Array.isArray(obj[key]) && obj[key].isCss) || isFunction(obj[key])) {\n rules.push(`${hyphenate(key)}:`, obj[key], ';');\n } else if (isPlainObject(obj[key])) {\n rules.push(...objToCssArray(obj[key], key));\n } else {\n rules.push(`${hyphenate(key)}: ${addUnitIfNeeded(key, obj[key])};`);\n }\n }\n\n return prevKey ? [`${prevKey} {`, ...rules, '}'] : rules;\n};\n\nexport default function flatten(\n chunk: any,\n executionContext: ?Object,\n styleSheet: ?Object,\n stylisInstance: ?Stringifier\n): any {\n if (Array.isArray(chunk)) {\n const ruleSet = [];\n\n for (let i = 0, len = chunk.length, result; i < len; i += 1) {\n result = flatten(chunk[i], executionContext, styleSheet, stylisInstance);\n\n if (result === '') continue;\n else if (Array.isArray(result)) ruleSet.push(...result);\n else ruleSet.push(result);\n }\n\n return ruleSet;\n }\n\n if (isFalsish(chunk)) {\n return '';\n }\n\n /* Handle other components */\n if (isStyledComponent(chunk)) {\n return `.${chunk.styledComponentId}`;\n }\n\n /* Either execute or defer the function */\n if (isFunction(chunk)) {\n if (isStatelessFunction(chunk) && executionContext) {\n const result = chunk(executionContext);\n\n if (process.env.NODE_ENV !== 'production' && isElement(result)) {\n // eslint-disable-next-line no-console\n console.warn(\n `${getComponentName(\n chunk\n)} is not a styled
 component and cannot be referred to via component selector. See https://www.styled-components.com/docs/advanced#referring-to-other-components for more details.`\n);\n }\n\n return flatten(result, executionContext, styleSheet, stylisInstance);\n } else return chunk;\n }\n\n if (chunk instanceof Keyframes) {\n if (styleSheet) {\n chunk.inject(styleSheet, stylisInstance);\n return chunk.getName(stylisInstance);\n } else return chunk;\n }\n\n /* Handle objects */\n return isPlainObject(chunk) ? objToCssArray(chunk) : chunk.toString();\n}\n","// @flow\nconst printed = {};\n\nexport default function warnOnce(message) {\n if (printed[message]) return;\n printed[message] = true;\n\n if (typeof console !== 'undefined' && console.warn) console.warn(message);\n}\n","// @flow\nconst SINGLE_QUOTE = \"'\".charCodeAt(0);\nconst DOUBLE_QUOTE = '\"'.charCodeAt(0);\nconst BACKSLASH = '\\'.charCodeAt(0);\nconst SLASH = '/'.charCodeAt(0);\nconst NEWLINE =
 '\n'.charCodeAt(0);\nconst SPACE = ' '.charCodeAt(0);\nconst FEED = '\f'.charCodeAt(0);\nconst TAB = '\t'.charCodeAt(0);\nconst CR = '\r'.charCodeAt(0);\nconst OPEN_SQUARE = '['.charCodeAt(0);\nconst CLOSE_SQUARE = ']'.charCodeAt(0);\nconst OPEN_PARENTHESES = '('.charCodeAt(0);\nconst CLOSE_PARENTHESES = ')'.charCodeAt(0);\nconst OPEN_CURLY = '{'.charCodeAt(0);\nconst CLOSE_CURLY = '}'.charCodeAt(0);\nconst SEMICOLON = ';'.charCodeAt(0);\nconst ASTERISK =

```
'*'.charCodeAt(0);\nconst COLON = ':'.charCodeAt(0);\nconst AT = '@'.charCodeAt(0);\n\nconst RE_AT_END = /[ \\n\\t\\r\\f\\{\\(\\)'\"\\\\;/\\[\\]#]/g;\nconst RE_WORD_END = /[ \\n\\t\\r\\f\\(\\)\\{\\}:;@!'\"\\\\\\]\\[#]|\\/(?=\\*)/g;\nconst RE_BAD_BRACKET = /.[\\\\\\/\\(\"\\n]/;\n\nexport default function tokenize(input, options = {}) {\n  const tokens = [];\n  const css = input.css.valueOf();\n\n  const ignore = options.ignoreErrors;\n\n  let code,\n    next,\n    quote,\n    lines,\n    last,\n    content,\n    escape,\n    nextLine,\n
    nextOffset,\n    escaped,\n    escapePos,\n    prev,\n    n;\n\n  const length = css.length;\n  let offset = -1;\n  let line = 1;\n  let pos = 0;\n\n  function unclosed(what) {\n    throw input.error(`Unclosed ${what}`, line, pos - offset);\n  }\n\n  while (pos < length) {\n    code = css.charCodeAt(pos);\n\n    if (code === NEWLINE || code === FEED || (code === CR && css.charCodeAt(pos + 1) !== NEWLINE)) {\n      offset = pos;\n      line += 1;\n    }\n\n    switch (code) {\n      case NEWLINE:\n      case SPACE:\n      case TAB:\n      case CR:\n      case FEED:\n        next = pos;\n        do {\n          next += 1;\n          code = css.charCodeAt(next);\n          if (code === NEWLINE) {\n            offset = next;\n            line += 1;\n          }\n        } while (\n          code === SPACE ||\n          code === NEWLINE ||\n          code === TAB ||\n          code === CR ||\n          code === FEED\n        );\n\n        tokens.push(['space', css.slice(pos, next)]);\n
        pos = next - 1;\n        break;\n\n      case OPEN_SQUARE:\n        tokens.push(['[', '[', line, pos - offset]);\n        break;\n\n      case CLOSE_SQUARE:\n        tokens.push([']', ']', line, pos - offset]);\n        break;\n\n      case OPEN_CURLY:\n        tokens.push(['{', '{', line, pos - offset]);\n        break;\n\n      case CLOSE_CURLY:\n        tokens.push(['}', '}', line, pos - offset]);\n        break;\n\n      case COLON:\n        tokens.push([':', ':', line, pos - offset]);\n        break;\n\n      case SEMICOLON:\n        tokens.push([';', ';', line, pos - offset]);\n        break;\n\n      case OPEN_PARENTHESES:\n        prev = tokens.length ? tokens[tokens.length - 1][1] : '';\n        n = css.charCodeAt(pos + 1);\n        if (\n          prev === 'url' &&\n          n !== SINGLE_QUOTE &&\n          n !== DOUBLE_QUOTE &&\n          n !== SPACE &&\n          n !== NEWLINE &&\n          n !== TAB &&\n          n !== FEED &&\n          n !== CR\n        )
        {\n          next = pos;\n          do {\n            escaped = false;\n            next = css.indexOf(')', next + 1);\n            if (next === -1) {\n              if (ignore) {\n                next = pos;\n                break;\n              } else {\n                unclosed('bracket');\n              }\n            }\n            escapePos = next;\n            while (css.charCodeAt(escapePos - 1) === BACKSLASH) {\n              escapePos -= 1;\n              escaped = !escaped;\n            }\n          } while (escaped);\n\n          tokens.push([\n            'brackets',\n            css.slice(pos, next + 1),\n            line,\n            pos - offset,\n            line,\n            next - offset,\n          ]);\n          pos = next;\n        } else {\n          next = css.indexOf(')', pos + 1);\n          content = css.slice(pos, next + 1);\n\n          if (next === -1 || RE_BAD_BRACKET.test(content)) {\n            tokens.push(['(', '(', line, pos - offset]);\n
          } else {\n            tokens.push(['brackets', content, line, pos - offset, line, next - offset]);\n            pos = next;\n          }\n        }\n\n        break;\n\n      case CLOSE_PARENTHESES:\n        tokens.push([')', ')', line, pos - offset]);\n        break;\n\n      case SINGLE_QUOTE:\n      case DOUBLE_QUOTE:\n        quote = code === SINGLE_QUOTE ? \"'\" : '\"';\n        next = pos;\n        do {\n          escaped = false;\n          next = css.indexOf(quote, next + 1);\n          if (next === -1) {\n            if (ignore) {\n              next = pos + 1;\n              break;\n            } else {\n              unclosed('quote');\n            }\n          }\n          escapePos = next;\n          while (css.charCodeAt(escapePos - 1) === BACKSLASH) {\n            escapePos -= 1;\n            escaped = !escaped;\n          }\n        } while (escaped);\n\n        content = css.slice(pos, next + 1);\n        lines = content.split('\\n');\n        last = lines.length - 1;\n\n
        if (last > 0) {\n          nextLine = line + last;\n          nextOffset = next - lines[last].length;\n        } else {\n          nextLine = line;\n          nextOffset = offset;\n        }\n\n        tokens.push([\n          'string',\n          css.slice(pos, next + 1),\n          line,\n          pos - offset,\n          nextLine,\n          next - nextOffset,\n        ]);\n\n        offset = nextOffset;\n        line = nextLine;\n        pos = next;\n        break;\n\n      case AT:\n        RE_AT_END.lastIndex = pos + 1;\n        RE_AT_END.test(css);\n        if (RE_AT_END.lastIndex === 0) {\n          next = css.length - 1;\n        } else {\n          next = RE_AT_END.lastIndex - 2;\n        }\n        tokens.push(['at-word', css.slice(pos, next + 1), line, pos - offset, line, next - offset]);\n        pos = next;\n        break;\n\n      case BACKSLASH:\n        next = pos;\n
        escape = true;\n        while (css.charCodeAt(next + 1) === BACKSLASH) {\n
```

```
next += 1;\n escape = !escape;\n }\n code = css.charCodeAt(next + 1);\n if (\n escape &&\n (code !== SLASH &&\n code !== SPACE &&\n code !== NEWLINE &&\n code !== TAB &&\n code !== CR &&\n code !== FEED)\n ) {\n next += 1;\n }\n tokens.push(['word', css.slice(pos, next + 1), line, pos - offset, line, next - offset]);\n pos = next;\n break;\n\n default:\n if (code === SLASH && css.charCodeAt(pos + 1) === ASTERISK) {\n next = css.indexOf('*/', pos + 2) + 1;\n if (next === 0) {\n if (ignore) {\n next = css.length;\n } else {\n unclosed('comment');\n }\n }\n\n content = css.slice(pos, next + 1);\n lines = content.split('\\n');\n last = lines.length - 1;\n\n if (last > 0) {\n nextLine = line + last;\n nextOffset = next - lines[last].length;\n } else {\n nextLine = line;\n nextOffset = offset;\n }\n\n tokens.push(['comment', content, line, pos - offset, nextLine, next - nextOffset]);\n\n offset = nextOffset;\n line = nextLine;\n pos = next;\n } else {\n RE_WORD_END.lastIndex = pos + 1;\n RE_WORD_END.test(css);\n if (RE_WORD_END.lastIndex === 0) {\n next = css.length - 1;\n } else {\n next = RE_WORD_END.lastIndex - 2;\n }\n\n tokens.push(['word', css.slice(pos, next + 1), line, pos - offset, line, next - offset]);\n pos = next;\n }\n\n break;\n }\n\n pos++;\n }\n\n return tokens;\n}\n","// @flow\nimport tokenize from './tokenize';\nimport Input from './input';\n\nconst HIGHLIGHT_THEME = {\n brackets: [36, 39], // cyan\n string: [31, 39], // red\n 'at-word': [31, 39], // red\n comment:
[90, 39], // gray\n '{': [32, 39], // green\n '}': [32, 39], // green\n ':': [1, 22], // bold\n ';': [1, 22], // bold\n '(': [1, 22], // bold\n ')': [1, 22], // bold\n};\n\nfunction code(color) {\n return `\\u001b[${color}m`;\n}\n\nfunction terminalHighlight(css) {\n const tokens = tokenize(new Input(css), { ignoreErrors: true });\n const result = [];\n tokens.forEach(token => {\n const color = HIGHLIGHT_THEME[token[0]];\n if (color) {\n result.push(\n token[1]\n .split(/\\r?\\n/)\n .map(i => code(color[0]) + i + code(color[1]))\n .join('\\n')\n );\n } else {\n result.push(token[1]);\n }\n });\n return result.join('');\n}\n\nexport default terminalHighlight;\n","// @flow\nimport supportsColor from 'supports-color';\n\nimport terminalHighlight from './terminal-highlight';\nimport warnOnce from './warn-once';\n\n/**\n * The CSS parser throws this error for broken CSS.\n *\n * Custom parsers can throw this error for
broken custom syntax using\n * the {@link Node#error} method.\n *\n * PostCSS will use the input source map to detect the original error location.\n * If you wrote a Sass file, compiled it to CSS and then parsed it with PostCSS,\n * PostCSS will show the original position in the Sass file.\n *\n * If you need the position in the PostCSS input\n * (e.g., to debug the previous compiler), use `error.input.file`.\n *\n * @example\n * // Catching and checking syntax error\n * try {\n * postcss.parse('a{')\n * } catch (error) {\n * if ( error.name === 'CssSyntaxError' ) {\n * error //=> CssSyntaxError\n * }\n * }\n *\n * @example\n * // Raising error from plugin\n * throw node.error('Unknown variable', { plugin: 'postcss-vars' });\n */\nclass CssSyntaxError {\n /**\n * @param {string} message - error message\n * @param {number} [line] - source line of the error\n * @param {number} [column] - source column of the error\n * @param {string} [source] - source code of the broken
file\n * @param {string} [file] - absolute path to the broken file\n * @param {string} [plugin] - PostCSS plugin name, if error came from plugin\n */\n constructor(message, line, column, source, file, plugin) {\n /**\n * @member {string} - Always equal to `'CssSyntaxError'`. You should\n * always check error type\n * by `error.name === 'CssSyntaxError'` instead of\n * `error instanceof CssSyntaxError`, because\n * npm could have several PostCSS versions.\n *\n * @example\n * if ( error.name === 'CssSyntaxError' ) {\n * error //=> CssSyntaxError\n * }\n */\n this.name = 'CssSyntaxError';\n /**\n * @member {string} - Error message.\n *\n * @example\n * error.message //=> 'Unclosed block'\n */\n this.reason = message;\n\n if (file) {\n /**\n * @member {string} - Absolute path to the broken file.\n *\n
* @example\n * error.file //=> 'a.sass'\n * error.input.file //=> 'a.css'\n */\n this.file = file;\n }\n if (source) {\n /**\n * @member {string} - Source code of the broken file.\n *\n * @example\n * error.source //=> 'a { b {} }'\n * error.input.column //=> 'a b { }'\n */\n this.source = source;\n }\n if (plugin) {\n /**\n * @member {string} - Plugin name, if error came from plugin.\n *\n *
```

@example\n * error.plugin //=> 'postcss-vars'\n */\n this.plugin = plugin;\n }\n if (typeof line !== 'undefined' && typeof column !== 'undefined') {\n /**\n * @member {number} - Source line of the error.\n *\n * @example\n * error.line //=> 2\n * error.input.line //=> 4\n */\n this.line = line;\n /**\n * @member {number} - Source column of the error.\n *\n * @example\n * error.column //=> 1\n * error.input.column //=> 4\n */\n this.column = column;\n }\n\n this.setMessage();\n\n if (Error.captureStackTrace) {\n Error.captureStackTrace(this, CssSyntaxError);\n }\n }\n\n setMessage() {\n /**\n * @member {string} - Full error text in the GNU error format\n * with plugin, file, line and column.\n *\n * @example\n * error.message //=> 'a.css:1:1: Unclosed block'\n */\n this.message = this.plugin ? `${this.plugin}: ` : '';\n this.message += this.file ? this.file : '<css input>';\n if (typeof this.line !== 'undefined') {\n this.message += `:${this.line}:${this.column}`;\n }\n this.message += `: ${this.reason}`;\n }\n\n /**\n * Returns a few lines of CSS source that caused the error.\n *\n * If the CSS has an input source map without `sourceContent`,\n * this method will return an empty string.\n *\n * @param {boolean} [color] whether arrow will
be colored red by terminal\n * color codes. By default, PostCSS will detect\n * color support by `process.stdout.isTTY`\n * and `process.env.NODE_DISABLE_COLORS`.\n *\n * @example\n * error.showSourceCode() //=> \" 4 | }\n * // 5 | a {\n * // > 6 | bad\n * // | ^\n * // 7 | }\n * // 8 | b {\"\n *\n * @return {string} few lines of CSS source that caused the error\n */\n showSourceCode(color) {\n if (!this.source) return '';\n\n let css = this.source;\n if (typeof color === 'undefined') color = supportsColor;\n if (color) css = terminalHighlight(css);\n\n const lines = css.split(/\\r?\\n/);\n const start = Math.max(this.line - 3, 0);\n const end = Math.min(this.line + 2, lines.length);\n\n const maxWidth = String(end).length;\n\n return lines\n .slice(start, end)\n .map((line, index) => {\n const number = start + 1 + index;\n const padded = ` ${number}`.slice(-maxWidth);\n const gutter = ` ${padded} | `;\n if (number === this.line) {\n const spacing =\n gutter.replace(/\\d/g, ' ') + line.slice(0, this.column - 1).replace(/[^\\t]/g, ' ');\n return `>${gutter}${line}\\n ${spacing}^`;\n } else {\n return ` ${gutter}${line}`;\n }\n })\n .join('\\n');\n }\n\n /**\n * Returns error position, message and source code of the broken part.\n *\n * @example\n * error.toString() //=> \"CssSyntaxError: app.css:1:1: Unclosed block\n * // > 1 | a {\n * // | ^\"\n *\n * @return {string} error position, message and source code\n */\n toString() {\n let code = this.showSourceCode();\n if (code) {\n code = `\\n\\n${code}\\n`;\n }\n return `${this.name}: ${this.message}${code}`;\n }\n\n get generated() {\n warnOnce('CssSyntaxError#generated is deprecated. Use input instead.');\n return this.input;\n }\n\n /**\n * @memberof CssSyntaxError#\n * @member {Input} input - Input object with PostCSS internal information\n * about input file. If input has source map\n * from previous tool, PostCSS will use origin\n * (for example, Sass) source. You can use this\n * object to get PostCSS input source.\n *\n * @example\n * error.input.file //=> 'a.css'\n * error.file //=> 'a.sass'\n */\n}\n\nexport default CssSyntaxError;\n","// @flow\n/* eslint-disable valid-jsdoc */\n\nconst defaultRaw = {\n colon: ': ',\n indent: ' ',\n beforeDecl: '\\n',\n beforeRule: '\\n',\n beforeOpen: ' ',\n beforeClose: '\\n',\n beforeComment: '\\n',\n after: '\\n',\n emptyBody: '',\n commentLeft: ' ',\n commentRight: ' ',\n};\n\nfunction capitalize(str) {\n return str[0].toUpperCase() + str.slice(1);\n}\n\nclass Stringifier {\n constructor(builder) {\n this.builder = builder;\n }\n\n stringify(node, semicolon) {\n this[node.type](node, semicolon);\n }\n\n root(node) {\n this.body(node);\n if (node.raws.after) this.builder(node.raws.after);\n }\n\n comment(node) {\n const left = this.raw(node, 'left', 'commentLeft');\n const right = this.raw(node, 'right', 'commentRight');\n this.builder(`/*${left}${node.text}${right}*/`, node);\n }\n\n decl(node, semicolon) {\n const between = this.raw(node, 'between', 'colon');\n let string = node.prop + between + this.rawValue(node, 'value');\n\n if (node.important) {\n string += node.raws.important || ' !important';\n }\n\n if (semicolon) string += ';';\n this.builder(string, node);\n }\n\n rule(node) {\n this.block(node, this.rawValue(node, 'selector'));\n }\n\n atrule(node, semicolon) {\n

```
  let name = `@${node.name}`;\n    const params = node.params ? this.rawValue(node, 'params') : '';\n\n    if (typeof
node.raws.afterName !== 'undefined') {\n      name += node.raws.afterName;\n    } else if (params) {\n      name += '
';\n    }\n\n    if (node.nodes) {\n      this.block(node, name + params);\n    } else {\n      const end =
(node.raws.between || '') + (semicolon ? ';' : '');\n      this.builder(name + params + end, node);\n    }\n  }\n\n
body(node) {\n    let last = node.nodes.length - 1;\n    while (last > 0) {\n      if (node.nodes[last].type !== 'comment')
break;\n      last -= 1;\n    }\n\n    const semicolon = this.raw(node, 'semicolon');\n    for (let i = 0; i <
node.nodes.length; i++) {\n      const child = node.nodes[i];\n      const before = this.raw(child, 'before');\n      if
(before) this.builder(before);\n      this.stringify(child, last !== i || semicolon);\n    }\n  }\n\n  block(node, start) {\n
const between = this.raw(node, 'between', 'beforeOpen');\n
    this.builder(`${start + between}{`, node, 'start');\n\n    let after;\n    if (node.nodes && node.nodes.length) {\n
this.body(node);\n      after = this.raw(node, 'after');\n    } else {\n      after = this.raw(node, 'after', 'emptyBody');\n
}\n\n    if (after) this.builder(after);\n    this.builder('}', node, 'end');\n  }\n\n  raw(node, own, detect) {\n    let value;\n
  if (!detect) detect = own;\n\n    // Already had\n    if (own) {\n      value = node.raws[own];\n      if (typeof value
!== 'undefined') return value;\n    }\n\n    const parent = node.parent;\n\n    // Hack for first rule in CSS\n    if (detect
=== 'before') {\n      if (!parent || (parent.type === 'root' && parent.first === node)) {\n        return '';\n      }\n    }\n\n
  // Floating child without parent\n    if (!parent) return defaultRaw[detect];\n\n    // Detect style by other nodes\n
const root = node.root();\n    if (!root.rawCache) root.rawCache = {};\n    if (typeof root.rawCache[detect]
  !== 'undefined') {\n      return root.rawCache[detect];\n    }\n\n    if (detect === 'before' || detect === 'after') {\n
return this.beforeAfter(node, detect);\n    } else {\n      const method = `raw${capitalize(detect)}`;\n      if
(this[method]) {\n        value = this[method](root, node);\n      } else {\n        root.walk(i => {\n          value =
i.raws[own];\n          if (typeof value !== 'undefined') return false;\n        });\n      }\n    }\n\n    if (typeof value ===
'undefined') value = defaultRaw[detect];\n\n    root.rawCache[detect] = value;\n    return value;\n  }\n\n
rawSemicolon(root) {\n    let value;\n    root.walk(i => {\n      if (i.nodes && i.nodes.length && i.last.type ===
'decl') {\n        value = i.raws.semicolon;\n        if (typeof value !== 'undefined') return false;\n      }\n    });\n    return
value;\n  }\n\n  rawEmptyBody(root) {\n    let value;\n    root.walk(i => {\n      if (i.nodes && i.nodes.length === 0)
{\n        value = i.raws.after;\n
      if (typeof value !== 'undefined') return false;\n      }\n    });\n    return value;\n  }\n\n  rawIndent(root) {\n    if
(root.raws.indent) return root.raws.indent;\n    let value;\n    root.walk(i => {\n      const p = i.parent;\n      if (p &&  p
!== root && p.parent && p.parent === root) {\n        if (typeof i.raws.before !== 'undefined') {\n          const parts =
i.raws.before.split('\\n');\n          value = parts[parts.length - 1];\n          value = value.replace(/[^\\s]/g, '');\n
return false;\n        }\n      }\n    });\n    return value;\n  }\n\n  rawBeforeComment(root, node) {\n    let value;\n
root.walkComments(i => {\n      if (typeof i.raws.before !== 'undefined') {\n        value = i.raws.before;\n        if
(value.indexOf('\\n') !== -1) {\n          value = value.replace(/[^\\n]+$/, '');\n        }\n        return false;\n      }\n    });\n
  if (typeof value === 'undefined') {\n      value = this.raw(node, null, 'beforeDecl');\n    }\n    return
 value;\n  }\n\n  rawBeforeDecl(root, node) {\n    let value;\n    root.walkDecls(i => {\n      if (typeof i.raws.before
!== 'undefined') {\n        value = i.raws.before;\n        if (value.indexOf('\\n') !== -1) {\n          value =
value.replace(/[^\\n]+$/, '');\n        }\n        return false;\n      }\n    });\n    if (typeof value === 'undefined') {\n
value = this.raw(node, null, 'beforeRule');\n    }\n    return value;\n  }\n\n  rawBeforeRule(root) {\n    let value;\n
root.walk(i => {\n      if (i.nodes && (i.parent !== root || root.first !== i)) {\n        if (typeof i.raws.before !==
'undefined') {\n          value = i.raws.before;\n          if (value.indexOf('\\n') !== -1) {\n            value =
value.replace(/[^\\n]+$/, '');\n          }\n          return false;\n        }\n      }\n    });\n    return value;\n  }\n\n
rawBeforeClose(root) {\n    let value;\n    root.walk(i => {\n      if (i.nodes && i.nodes.length > 0) {\n        if (typeof
i.raws.after !== 'undefined')
  {\n          value = i.raws.after;\n          if (value.indexOf('\\n') !== -1) {\n            value = value.replace(/[^\\n]+$/,
'');\n          }\n          return false;\n        }\n      }\n    });\n    return value;\n  }\n\n  rawBeforeOpen(root) {\n    let
value;\n    root.walk(i => {\n      if (i.type !== 'decl') {\n        value = i.raws.between;\n        if (typeof value !==
'undefined') return false;\n      }\n    });\n    return value;\n  }\n\n  rawColon(root) {\n    let value;\n
root.walkDecls(i => {\n      if (typeof i.raws.between !== 'undefined') {\n        value =
```

i.raws.between.replace(/[^\\s:]/g, '');\n return false;\n }\n });\n return value;\n }\n\n beforeAfter(node, detect) {\n let value;\n if (node.type === 'decl') {\n value = this.raw(node, null, 'beforeDecl');\n } else if (node.type === 'comment') {\n value = this.raw(node, null, 'beforeComment');\n } else if (detect === 'before') {\n value = this.raw(node, null,
'beforeRule');\n } else {\n value = this.raw(node, null, 'beforeClose');\n }\n\n let buf = node.parent;\n let depth = 0;\n while (buf && buf.type !== 'root') {\n depth += 1;\n buf = buf.parent;\n }\n\n if (value.indexOf('\\n') !== -1) {\n const indent = this.raw(node, null, 'indent');\n if (indent.length) {\n for (let step = 0; step < depth; step++) value += indent;\n }\n }\n\n return value;\n }\n\n rawValue(node, prop) {\n const value = node[prop];\n const raw = node.raws[prop];\n if (raw && raw.value === value) {\n return raw.raw;\n } else {\n return value;\n }\n }\n}\n\nexport default Stringifier;\n","// @flow\nimport Stringifier from './stringifier';\n\nexport default function stringify(node, builder) {\n const str = new Stringifier(builder);\n str.stringify(node);\n}\n","// @flow\nimport CssSyntaxError from './css-syntax-error';\nimport Stringifier from './stringifier';\nimport stringify
from './stringify';\nimport warnOnce from './warn-once';\n\n/**\n * @typedef {object} position\n * @property {number} line - source line in file\n * @property {number} column - source column in file\n */\n\n/**\n * @typedef {object} source\n * @property {Input} input - {@link Input} with input file\n * @property {position} start - The starting position of the node's source\n * @property {position} end - The ending position of the node's source\n */\n\nconst cloneNode = function(obj, parent) {\n const cloned = new obj.constructor();\n\n for (const i in obj) {\n if (!obj.hasOwnProperty(i)) continue;\n let value = obj[i];\n const type = typeof value;\n\n if (i === 'parent' && type === 'object') {\n if (parent) cloned[i] = parent;\n } else if (i === 'source') {\n cloned[i] = value;\n } else if (value instanceof Array) {\n cloned[i] = value.map(j => cloneNode(j, cloned));\n } else if (i !== 'before' && i !== 'after' && i !== 'between' && i !==
'semicolon') {\n if (type === 'object' && value !== null) value = cloneNode(value);\n cloned[i] = value;\n }\n }\n\n return cloned;\n};\n\n/**\n * All node classes inherit the following common methods.\n *\n * @abstract\n */\nclass Node {\n /**\n * @param {object} [defaults] - value for node properties\n */\n constructor(defaults = {}) {\n this.raws = {};\n for (const name in defaults) {\n this[name] = defaults[name];\n }\n }\n\n /**\n * Returns a CssSyntaxError instance containing the original position\n * of the node in the source, showing line and column numbers and also\n * a small excerpt to facilitate debugging.\n *\n * If present, an input source map will be used to get the original position\n * of the source, even from a previous compilation step\n * (e.g., from Sass compilation).\n *\n * This method produces very useful error messages.\n *\n * @param {string} message - error description\n * @param {object} [opts]
- options\n * @param {string} opts.plugin - plugin name that created this error.\n *
PostCSS will set it automatically.\n * @param {string} opts.word - a word inside a node's string that should\n *
be highlighted as the source of the error\n * @param {number} opts.index - an index inside a
node's string that should\n * be highlighted as the source of the error\n *\n * @return
{CssSyntaxError} error object to throw it\n *\n * @example\n * if (!variables[name]) {\n * throw
decl.error('Unknown variable ' + name, { word: name });\n * // CssSyntaxError: postcss-vars:a.sass:4:3: Unknown
variable $black\n * // color: $black\n * // a\n * // ^\n * // background: white\n * }\n */\n
error(message, opts = {}) {\n if (this.source) {\n const pos = this.positionBy(opts);\n return
this.source.input.error(message, pos.line, pos.column,
opts);\n } else {\n return new CssSyntaxError(message);\n }\n }\n\n /**\n * This method is provided as a
convenience wrapper for {@link Result#warn}.\n *\n * @param {Result} result - the {@link Result}
instance\n * that will receive the warning\n * @param {string} text - warning message\n
* @param {object} [opts] - options\n * @param {string} opts.plugin - plugin name that created this warning.\n
* PostCSS will set it automatically.\n * @param {string} opts.word - a word inside a node's
string that should\n * be highlighted as the source of the warning\n * @param {number}
opts.index - an index inside a node's string that should\n * be highlighted as the source of the
warning\n *\n * @return {Warning} created warning object\n *\n * @example\n * const plugin =

postcss.plugin('postcss-deprecated',
() => {\n * return (root, result) => {\n * root.walkDecls('bad', decl => {\n * decl.warn(result, 'Deprecated property bad');\n * });\n * };\n * });\n */\n warn(result, text, opts) {\n const data = { node: this };\n for (const i in opts) data[i] = opts[i];\n return result.warn(text, data);\n }\n\n /**\n * Removes the node from its parent and cleans the parent properties\n * from the node and its children.\n *\n * @example\n * if (decl.prop.match(/^-webkit-/)) {\n * decl.remove();\n * }\n *\n * @return {Node} node to make calls chain\n */\n remove() {\n if (this.parent) {\n this.parent.removeChild(this);\n }\n this.parent = undefined;\n return this;\n }\n\n /**\n * Returns a CSS string representing the node.\n *\n * @param {stringifier|syntax} [stringifier] - a syntax to use\n * in string generation\n *\n * @return {string} CSS string of this
node\n *\n * @example\n * postcss.rule({ selector: 'a' }).toString() //=> \"a {}\"\n */\n toString(stringifier = stringify) {\n if (stringifier.stringify) stringifier = stringifier.stringify;\n let result = '';\n stringifier(this, i => {\n result += i;\n });\n return result;\n }\n\n /**\n * Returns a clone of the node.\n *\n * The resulting cloned node and its (cloned) children will have\n * a clean parent and code style properties.\n *\n * @param {object} [overrides] - new properties to override in the clone.\n *\n * @example\n * const cloned = decl.clone({ prop: '-moz-' + decl.prop });\n * cloned.raws.before //=> undefined\n * cloned.parent //=> undefined\n * cloned.toString() //=> -moz-transform: scale(0)\n *\n * @return {Node} clone of the node\n */\n clone(overrides = {}) {\n const cloned = cloneNode(this);\n for (const name in overrides) {\n cloned[name] = overrides[name];\n }\n return cloned;\n
}\n\n /**\n * Shortcut to clone the node and insert the resulting cloned node\n * before the current node.\n *\n * @param {object} [overrides] - new properties to override in the clone.\n *\n * @example\n * decl.cloneBefore({ prop: '-moz-' + decl.prop });\n *\n * @return {Node} - new node\n */\n cloneBefore(overrides = {}) {\n const cloned = this.clone(overrides);\n this.parent.insertBefore(this, cloned);\n return cloned;\n }\n\n /**\n * Shortcut to clone the node and insert the resulting cloned node\n * after the current node.\n *\n * @param {object} [overrides] - new properties to override in the clone.\n *\n * @return {Node} - new node\n */\n cloneAfter(overrides = {}) {\n const cloned = this.clone(overrides);\n this.parent.insertAfter(this, cloned);\n return cloned;\n }\n\n /**\n * Inserts node(s) before the current node and removes the current node.\n *\n * @param {...Node} nodes - node(s) to replace current one\n
*\n * @example\n * if (atrule.name == 'mixin') {\n * atrule.replaceWith(mixinRules[atrule.params]);\n * }\n *\n * @return {Node} current node to methods chain\n */\n replaceWith(...nodes) {\n if (this.parent) {\n nodes.forEach(node => {\n this.parent.insertBefore(this, node);\n });\n\n this.remove();\n }\n\n return this;\n }\n\n /**\n * Removes the node from its current parent and inserts it\n * at the end of `newParent`.\n *\n * This will clean the `before` and `after` code {@link Node#raws} data\n * from the node and replace them with the indentation style of `newParent`.\n * It will also clean the `between` property\n * if `newParent` is in another {@link Root}.\n *\n * @param {Container} newParent - container node where the current node\n *
will be moved\n *\n * @example\n * atrule.moveTo(atrule.root());\n *\n * @return {Node} current node to methods chain\n */\n
moveTo(newParent) {\n this.cleanRaws(this.root() === newParent.root());\n this.remove();\n newParent.append(this);\n return this;\n }\n\n /**\n * Removes the node from its current parent and inserts it into\n * a new parent before `otherNode`.\n *\n * This will also clean the node's code style properties just as it would\n * in {@link Node#moveTo}.\n *\n * @param {Node} otherNode - node that will be before current node\n *\n * @return {Node} current node to methods chain\n */\n moveBefore(otherNode) {\n this.cleanRaws(this.root() === otherNode.root());\n this.remove();\n otherNode.parent.insertBefore(otherNode, this);\n return this;\n }\n\n /**\n * Removes the node from its current parent and inserts it into\n * a new parent after `otherNode`.\n *\n * This will also clean the node's code style properties just as it would\n * in {@link Node#moveTo}.\n *\n * @param {Node} otherNode - node that will be after current node\n *\n
* @return {Node} current node to methods chain\n */\n moveAfter(otherNode) {\n this.cleanRaws(this.root() === otherNode.root());\n this.remove();\n otherNode.parent.insertAfter(otherNode, this);\n return this;\n }\n\n

```
/**\n   * Returns the next child of the node’s parent.\n   * Returns `undefined` if the current node is the last child.\n   *\n   * @return {Node|undefined} next node\n   *\n   * @example\n   * if ( comment.text === 'delete next' ) {\n   * const next = comment.next();\n   *   if ( next ) {\n   *     next.remove();\n   *   }\n   * }\n   */\n  next() {\n    const index = this.parent.index(this);\n    return this.parent.nodes[index + 1];\n  }\n\n  /**\n   * Returns the previous child of the node’s parent.\n   * Returns `undefined` if the current node is the first child.\n   *\n   * @return {Node|undefined} previous node\n   *\n   * @example\n   * const annotation = decl.prev();\n   * if ( annotation.type == 'comment' ) {\n   *   readAnnotation(annotation.text);\n
   * }\n   */\n  prev() {\n    const index = this.parent.index(this);\n    return this.parent.nodes[index - 1];\n  }\n\n  toJSON() {\n    const fixed = {};\n\n    for (const name in this) {\n      if (!this.hasOwnProperty(name)) continue;\n      if (name === 'parent') continue;\n      const value = this[name];\n\n      if (value instanceof Array) {\n        fixed[name] = value.map(i => {\n          if (typeof i === 'object' && i.toJSON) {\n            return i.toJSON();\n          } else {\n            return i;\n          }\n        });\n      } else if (typeof value === 'object' && value.toJSON) {\n        fixed[name] = value.toJSON();\n      } else {\n        fixed[name] = value;\n      }\n    }\n\n    return fixed;\n  }\n\n  /**\n   * Returns a {@link Node#raws} value. If the node is missing\n   * the code style property (because the node was manually built or cloned),\n   * PostCSS will try to autodetect the code style property by looking\n   * at other nodes in the tree.\n
   *\n   * @param {string} prop          - name of code style property\n   * @param {string} [defaultType] - name of default value, it can be missed\n   *                                 if the value is the same as prop\n   *\n   * @example\n   * const root = postcss.parse('a { background: white }');\n   * root.nodes[0].append({ prop: 'color', value: 'black' });\n   * root.nodes[0].nodes[1].raws.before   //=> undefined\n   * root.nodes[0].nodes[1].raw('before') //=> ' '\n   *\n   * @return {string} code style value\n   */\n  raw(prop, defaultType) {\n    const str = new Stringifier();\n    return str.raw(this, prop, defaultType);\n  }\n\n  /**\n   * Finds the Root instance of the node’s tree.\n   *\n   * @example\n   * root.nodes[0].nodes[0].root() === root\n   *\n   * @return {Root} root parent\n   */\n  root() {\n    let result = this;\n    while (result.parent) result = result.parent;\n    return result;\n  }\n\n  cleanRaws(keepBetween) {\n    delete this.raws.before;\n    delete
    this.raws.after;\n    if (!keepBetween) delete this.raws.between;\n  }\n\n  positionInside(index) {\n    const string = this.toString();\n    let column = this.source.start.column;\n    let line = this.source.start.line;\n\n    for (let i = 0; i < index; i++) {\n      if (string[i] === '\\n') {\n        column = 1;\n        line += 1;\n      } else {\n        column += 1;\n      }\n    }\n\n    return { line, column };\n  }\n\n  positionBy(opts) {\n    let pos = this.source.start;\n    if (opts.index) {\n      pos = this.positionInside(opts.index);\n    } else if (opts.word) {\n      const index = this.toString().indexOf(opts.word);\n      if (index !== -1) pos = this.positionInside(index);\n    }\n    return pos;\n  }\n\n  removeSelf() {\n    warnOnce('Node#removeSelf is deprecated. Use Node#remove.');\n    return this.remove();\n  }\n\n  replace(nodes) {\n    warnOnce('Node#replace is deprecated. Use Node#replaceWith');\n    return this.replaceWith(nodes);\n  }\n\n  style(own, detect)
    {\n    warnOnce('Node#style() is deprecated. Use Node#raw()');\n    return this.raw(own, detect);\n  }\n\n  cleanStyles(keepBetween) {\n    warnOnce('Node#cleanStyles() is deprecated. Use Node#cleanRaws()');\n    return this.cleanRaws(keepBetween);\n  }\n\n  get before() {\n    warnOnce('Node#before is deprecated. Use Node#raws.before');\n    return this.raws.before;\n  }\n\n  set before(val) {\n    warnOnce('Node#before is deprecated. Use Node#raws.before');\n    this.raws.before = val;\n  }\n\n  get between() {\n    warnOnce('Node#between is deprecated. Use Node#raws.between');\n    return this.raws.between;\n  }\n\n  set between(val) {\n    warnOnce('Node#between is deprecated. Use Node#raws.between');\n    this.raws.between = val;\n  }\n\n  /**\n   * @memberof Node#\n   * @member {string} type - String representing the node’s type.\n   *                         Possible values are `root`, `atrule`, `rule`,\n   *                         `decl`, or `comment`.\n   *\n   * @example\n
   * postcss.decl({ prop: 'color', value: 'black' }).type //=> 'decl'\n   */\n\n  /**\n   * @memberof Node#\n   * @member {Container} parent - the node’s parent node.\n   *\n   * @example\n   * root.nodes[0].parent == root;\n   */\n\n  /**\n   * @memberof Node#\n   * @member {source} source - the input source of the node\n   *\n   * The property is used in source map generation.\n   *\n   * If you create a node manually (e.g., with `postcss.decl()`),\n   *
```

that node will not have a `source` property and will be absent\n * from the source map. For this reason, the plugin developer should\n * consider cloning nodes to create new ones (in which case the new node's\n * source will reference the original, cloned node) or setting\n * the `source` property manually.\n *\n * ```js\n * // Bad\n * const prefixed = postcss.decl({\n * prop: '-moz-' + decl.prop,\n * value: decl.value\n * });\n *\n * // Good\n * const prefixed = decl.clone({ prop: '-moz-' + decl.prop
});\n * ```\n *\n * ```js\n * if (atrule.name == 'add-link') {\n * const rule = postcss.rule({ selector: 'a', source: atrule.source });\n * atrule.parent.insertBefore(atrule, rule);\n * }\n * ```\n *\n * @example\n * decl.source.input.from //=> '/home/ai/a.sass'\n * decl.source.start //=> { line: 10, column: 2 }\n * decl.source.end //=> { line: 10, column: 12 }\n */\n\n /**\n * @memberof Node#\n * @member {object} raws - Information to generate byte-to-byte equal\n * node string as it was in the origin input.\n *\n * Every parser saves its own properties,\n * but the default CSS parser uses:\n *\n * * `before`: the space symbols before the node. It also stores `*`\n * and `_` symbols before the declaration (IE hack).\n * * `after`: the space symbols after the last child of the node\n * to the end of the node.\n * * `between`: the symbols between the property and value\n * for declarations,
selector and `{` for rules, or last parameter\n * and `{` for at-rules.\n * * `semicolon`: contains true if the last child has\n * an (optional) semicolon.\n * * `afterName`: the space between the at-rule name and its parameters.\n * * `left`: the space symbols between `/*` and the comment's text.\n * * `right`: the space symbols between the comment's text\n * and <code>*/</code>.\n * * `important`: the content of the important statement,\n * if it is not just `!important`.\n *\n * PostCSS cleans selectors, declaration values and at-rule parameters\n * from comments and extra spaces, but it stores origin content in raws\n * properties. As such, if you don't change a declaration's value,\n * PostCSS will use the raw value with comments.\n *\n * @example\n * const root = postcss.parse('a {\\n color:black\\n}')\n * root.first.first.raws //=> { before: '\\n ', between: ':' }\n */\n}\n\nexport default Node;\n","// @flow\nimport warnOnce
from './warn-once';\nimport Node from './node';\n\n/**\n * Represents a CSS declaration.\n *\n * @extends Node\n *\n * @example\n * const root = postcss.parse('a { color: black }');\n * const decl = root.first.first;\n * decl.type //=> 'decl'\n * decl.toString() //=> ' color: black'\n */\nclass Declaration extends Node {\n constructor(defaults) {\n super(defaults);\n this.type = 'decl';\n }\n\n get _value() {\n warnOnce('Node#_value was deprecated. Use Node#raws.value');\n return this.raws.value;\n }\n\n set _value(val) {\n warnOnce('Node#_value was deprecated. Use Node#raws.value');\n this.raws.value = val;\n }\n\n get _important() {\n warnOnce('Node#_important was deprecated. Use Node#raws.important');\n return this.raws.important;\n }\n\n set _important(val) {\n warnOnce('Node#_important was deprecated. Use Node#raws.important');\n this.raws.important = val;\n }\n\n /**\n * @memberof Declaration#\n * @member {string} prop - the
declaration's property name\n *\n * @example\n * const root = postcss.parse('a { color: black }');\n * const decl = root.first.first;\n * decl.prop //=> 'color'\n */\n\n /**\n * @memberof Declaration#\n * @member {string} value - the declaration's value\n *\n * @example\n * const root = postcss.parse('a { color: black }');\n * const decl = root.first.first;\n * decl.value //=> 'black'\n */\n\n /**\n * @memberof Declaration#\n * @member {boolean} important - `true` if the declaration\n * has an !important annotation.\n *\n * @example\n * const root = postcss.parse('a { color: black !important; color: red }');\n * root.first.first.important //=> true\n * root.first.last.important //=> undefined\n */\n\n /**\n * @memberof Declaration#\n * @member {object} raws - Information to generate byte-to-byte equal\n * node string as it was in the origin input.\n *\n * Every parser saves
its own properties,\n * but the default CSS parser uses:\n *\n * * `before`: the space symbols before the node. It also stores `*`\n * and `_` symbols before the declaration (IE hack).\n * * `between`: the symbols between the property and value\n * for declarations, selector and `{` for rules, or last parameter\n * and `{` for at-rules.\n * * `important`: the content of the important statement,\n * if it is not just `!important`.\n *\n * PostCSS cleans declaration from comments and extra spaces,\n * but it stores origin content in raws properties.\n * As such, if you don't change a declaration's value,\n * PostCSS will use the raw value with comments.\n *\n * @example\n * const root = postcss.parse('a {\\n color:black\\n}')\n * root.first.first.raws //=> { before: '\\n ', between: ':' }\n

```
*/\n}\n\nexport default Declaration;\n","// @flow\nimport warnOnce from './warn-once';\nimport Node from
'./node';\n\n/**\n * Represents a comment between
 declarations or statements (rule and at-rules).\n *\n * Comments inside selectors, at-rule parameters, or declaration
values\n * will be stored in the `raws` properties explained above.\n *\n * @extends Node\n */\nclass Comment
extends Node {\n  constructor(defaults) {\n    super(defaults);\n    this.type = 'comment';\n  }\n\n  get left() {\n
warnOnce('Comment#left was deprecated. Use Comment#raws.left');\n    return this.raws.left;\n  }\n\n  set left(val)
{\n    warnOnce('Comment#left was deprecated. Use Comment#raws.left');\n    this.raws.left = val;\n  }\n\n  get
right() {\n    warnOnce('Comment#right was deprecated. Use Comment#raws.right');\n    return this.raws.right;\n
}\n\n  set right(val) {\n    warnOnce('Comment#right was deprecated. Use Comment#raws.right');\n    this.raws.right
= val;\n  }\n\n  /**\n   * @memberof Comment#\n   * @member {string} text - the comment's text\n   */\n\n  /**\n
* @memberof Comment#\n   * @member {object} raws - Information to generate
 byte-to-byte equal\n   *                 node string as it was in the origin input.\n   *\n   * Every parser saves its own
properties,\n   * but the default CSS parser uses:\n   *\n   * * `before`: the space symbols before the node.\n   * *
`left`: the space symbols between `/*` and the comment's text.\n   * * `right`: the space symbols between the
comment's text.\n   */\n}\n\nexport default Comment;\n","// @flow\nimport Declaration from
'./declaration';\nimport tokenizer from './tokenize';\nimport Comment from './comment';\nimport AtRule from './at-
rule';\nimport Root from './root';\nimport Rule from './rule';\n\nexport default class Parser {\n  constructor(input) {\n
 this.input = input;\n\n    this.pos = 0;\n    this.root = new Root();\n    this.current = this.root;\n    this.spaces = '';\n
this.semicolon = false;\n\n    this.root.source = { input, start: { line: 1, column: 1 } };\n  }\n\n  tokenize() {\n
this.tokens = tokenizer(this.input);\n  }\n\n  loop() {\n
 let token;\n    while (this.pos < this.tokens.length) {\n      token = this.tokens[this.pos];\n\n      switch (token[0]) {\n
    case 'space':\n      case ';':\n        this.spaces += token[1];\n        break;\n\n      case '}':\n
this.end(token);\n        break;\n\n      case 'comment':\n        this.comment(token);\n        break;\n\n      case 'at-
word':\n        this.atrule(token);\n        break;\n\n      case '{':\n        this.emptyRule(token);\n        break;\n\n
default:\n        this.other();\n        break;\n      }\n\n      this.pos += 1;\n    }\n    this.endFile();\n  }\n\n
comment(token) {\n    const node = new Comment();\n    this.init(node, token[2], token[3]);\n    node.source.end = {
line: token[4], column: token[5] };\n\n    const text = token[1].slice(2, -2);\n    if (/^\\s*$/.test(text)) {\n      node.text
= '';\n      node.raws.left = text;\n      node.raws.right = '';\n    } else {\n      const match =
text.match(/^(\\s*)([^]*[^\\s])(\\s*)$/);\n
      node.text = match[2];\n      node.raws.left = match[1];\n      node.raws.right = match[3];\n    }\n  }\n\n
emptyRule(token) {\n    const node = new Rule();\n    this.init(node, token[2], token[3]);\n    node.selector = '';\n
node.raws.between = '';\n    this.current = node;\n  }\n\n  other() {\n    let token;\n    let end = false;\n    let type =
null;\n    let colon = false;\n    let bracket = null;\n    const brackets = [];\n\n    const start = this.pos;\n    while
(this.pos < this.tokens.length) {\n      token = this.tokens[this.pos];\n      type = token[0];\n\n      if (type === '(' || type
=== '[') {\n        if (!bracket) bracket = token;\n        brackets.push(type === '(' ? ')' : ']');\n      } else if
(brackets.length === 0) {\n        if (type === ';') {\n          if (colon) {\n            this.decl(this.tokens.slice(start,
this.pos + 1));\n            return;\n          } else {\n            break;\n          }\n        } else if
 (type === '{') {\n          this.rule(this.tokens.slice(start, this.pos + 1));\n          return;\n        } else if (type === '}')
{\n          this.pos -= 1;\n          end = true;\n          break;\n        } else if (type === ':') {\n          colon = true;\n
}\n      } else if (type === brackets[brackets.length - 1]) {\n        brackets.pop();\n        if (brackets.length === 0)
bracket = null;\n      }\n\n      this.pos += 1;\n    }\n    if (this.pos === this.tokens.length) {\n      this.pos -= 1;\n
end = true;\n    }\n\n    if (brackets.length > 0) this.unclosedBracket(bracket);\n\n    if (end && colon) {\n      while
(this.pos > start) {\n        token = this.tokens[this.pos][0];\n        if (token !== 'space' && token !== 'comment')
break;\n        this.pos -= 1;\n      }\n      this.decl(this.tokens.slice(start, this.pos + 1));\n      return;\n    }\n\n
this.unknownWord(start);\n  }\n\n  rule(tokens) {\n    tokens.pop();\n\n    const node = new Rule();\n
this.init(node,
 tokens[0][2], tokens[0][3]);\n\n    node.raws.between = this.spacesFromEnd(tokens);\n    this.raw(node, 'selector',
tokens);\n    this.current = node;\n  }\n\n  decl(tokens) {\n    const node = new Declaration();\n    this.init(node);\n\n
```

```
const last = tokens[tokens.length - 1];\n    if (last[0] === ';') {\n      this.semicolon = true;\n      tokens.pop();\n    }\n
if (last[4]) {\n      node.source.end = { line: last[4], column: last[5] };\n    } else {\n      node.source.end = { line:
last[2], column: last[3] };\n    }\n\n    while (tokens[0][0] !== 'word') {\n      node.raws.before += tokens.shift()[1];\n
 }\n    node.source.start = { line: tokens[0][2], column: tokens[0][3] };\n\n    node.prop = '';\n    while (tokens.length)
{\n      const type = tokens[0][0];\n      if (type === ':' || type === 'space' || type === 'comment') {\n        break;\n
}\n      node.prop += tokens.shift()[1];\n    }\n\n    node.raws.between = '';\n\n    let token;\n    while (tokens.length)
 {\n      token = tokens.shift();\n\n      if (token[0] === ':') {\n        node.raws.between += token[1];\n        break;\n
} else {\n        node.raws.between += token[1];\n      }\n    }\n\n    if (node.prop[0] === '_' || node.prop[0] === '*') {\n
   node.raws.before += node.prop[0];\n      node.prop = node.prop.slice(1);\n    }\n    node.raws.between +=
this.spacesFromStart(tokens);\n    this.precheckMissedSemicolon(tokens);\n\n    for (let i = tokens.length - 1; i > 0;
i--) {\n      token = tokens[i];\n      if (token[1] === '!important') {\n        node.important = true;\n        let string =
this.stringFrom(tokens, i);\n        string = this.spacesFromEnd(tokens) + string;\n        if (string !== ' !important')
node.raws.important = string;\n        break;\n      } else if (token[1] === 'important') {\n        const cache =
tokens.slice(0);\n        let str = '';\n        for (let j = i; j > 0; j--) {\n          const type = cache[j][0];\n          if
(str.trim().indexOf('!')
 === 0 && type !== 'space') {\n            break;\n          }\n          str = cache.pop()[1] + str;\n        }\n        if
(str.trim().indexOf('!') === 0) {\n          node.important = true;\n          node.raws.important = str;\n          tokens =
cache;\n        }\n      }\n\n      if (token[0] !== 'space' && token[0] !== 'comment') {\n        break;\n      }\n    }\n\n
this.raw(node, 'value', tokens);\n\n    if (node.value.indexOf(':') !== -1) this.checkMissedSemicolon(tokens);\n  }\n\n
atrule(token) {\n    const node = new AtRule();\n    node.name = token[1].slice(1);\n    if (node.name === '') {\n
this.unnamedAtrule(node, token);\n    }\n    this.init(node, token[2], token[3]);\n\n    let last = false;\n    let open =
false;\n    const params = [];\n\n    this.pos += 1;\n    while (this.pos < this.tokens.length) {\n      token =
this.tokens[this.pos];\n\n      if (token[0] === ';') {\n        node.source.end = { line: token[2], column: token[3] };\n

  this.semicolon = true;\n        break;\n      } else if (token[0] === '{') {\n        open = true;\n        break;\n      } else if
(token[0] === '}') {\n        this.end(token);\n        break;\n      } else {\n        params.push(token);\n      }\n\n
this.pos += 1;\n    }\n    if (this.pos === this.tokens.length) {\n      last = true;\n    }\n\n    node.raws.between =
this.spacesFromEnd(params);\n    if (params.length) {\n      node.raws.afterName = this.spacesFromStart(params);\n
   this.raw(node, 'params', params);\n      if (last) {\n        token = params[params.length - 1];\n        node.source.end
= { line: token[4], column: token[5] };\n        this.spaces = node.raws.between;\n        node.raws.between = '';\n
}\n    } else {\n      node.raws.afterName = '';\n      node.params = '';\n    }\n\n    if (open) {\n      node.nodes = [];\n
this.current = node;\n    }\n  }\n\n  end(token) {\n    if (this.current.nodes && this.current.nodes.length) {\n
this.current.raws.semicolon
 = this.semicolon;\n    }\n    this.semicolon = false;\n\n    this.current.raws.after = (this.current.raws.after || '') +
this.spaces;\n    this.spaces = '';\n\n    if (this.current.parent) {\n      this.current.source.end = { line: token[2],
column: token[3] };\n      this.current = this.current.parent;\n    } else {\n      this.unexpectedClose(token);\n    }\n
}\n\n  endFile() {\n    if (this.current.parent) this.unclosedBlock();\n    if (this.current.nodes &&
this.current.nodes.length) {\n      this.current.raws.semicolon = this.semicolon;\n    }\n    this.current.raws.after =
(this.current.raws.after || '') + this.spaces;\n  }\n\n  // Helpers\n\n  init(node, line, column) {\n
this.current.push(node);\n\n    node.source = { start: { line, column }, input: this.input };\n    node.raws.before =
this.spaces;\n    this.spaces = '';\n    if (node.type !== 'comment') this.semicolon = false;\n  }\n\n  raw(node, prop,
tokens) {\n    let token, type;\n    const length
 = tokens.length;\n    let value = '';\n    let clean = true;\n    for (let i = 0; i < length; i += 1) {\n      token = tokens[i];\n
   type = token[0];\n      if (type === 'comment' || (type === 'space' && i === length - 1)) {\n        clean = false;\n
} else {\n        value += token[1];\n      }\n    }\n    if (!clean) {\n      const raw = tokens.reduce((all, i) => all + i[1],
'');\n      node.raws[prop] = { value, raw };\n    }\n    node[prop] = value;\n  }\n\n  spacesFromEnd(tokens) {\n    let
lastTokenType;\n    let spaces = '';\n    while (tokens.length) {\n      lastTokenType = tokens[tokens.length - 1][0];\n
  if (lastTokenType !== 'space' && lastTokenType !== 'comment') break;\n      spaces = tokens.pop()[1] + spaces;\n
```

}\n return spaces;\n }\n\n spacesFromStart(tokens) {\n let next;\n let spaces = '';\n while (tokens.length) {\n next = tokens[0][0];\n if (next !== 'space' && next !== 'comment') break;\n spaces += tokens.shift()[1];\n }\n return spaces;\n }\n\n stringFrom(tokens, from) {\n let result = '';\n for (let i = from; i < tokens.length; i++) {\n result += tokens[i][1];\n }\n tokens.splice(from, tokens.length - from);\n return result;\n }\n\n colon(tokens) {\n let brackets = 0;\n let token, type, prev;\n for (let i = 0; i < tokens.length; i++) {\n token = tokens[i];\n type = token[0];\n\n if (type === '(') {\n brackets += 1;\n } else if (type === ')') {\n brackets -= 1;\n } else if (brackets === 0 && type === ':') {\n if (!prev) {\n this.doubleColon(token);\n } else if (prev[0] === 'word' && prev[1] === 'progid') {\n continue;\n } else {\n return i;\n }\n }\n\n prev = token;\n }\n return false;\n }\n\n // Errors\n\n unclosedBracket(bracket) {\n throw this.input.error('Unclosed bracket', bracket[2], bracket[3]);\n }\n\n unknownWord(start) {\n const token = this.tokens[start];\n throw this.input.error('Unknown word', token[2], token[3]);\n }\n\n unexpectedClose(token) {\n throw this.input.error('Unexpected }', token[2], token[3]);\n }\n\n unclosedBlock() {\n const pos = this.current.source.start;\n throw this.input.error('Unclosed block', pos.line, pos.column);\n }\n\n doubleColon(token) {\n throw this.input.error('Double colon', token[2], token[3]);\n }\n\n unnamedAtrule(node, token) {\n throw this.input.error('At-rule without name', token[2], token[3]);\n }\n\n precheckMissedSemicolon(tokens) {\n // Hook for Safe Parser\n tokens;\n }\n\n checkMissedSemicolon(tokens) {\n const colon = this.colon(tokens);\n if (colon === false) return;\n\n let founded = 0;\n let token;\n for (let j = colon - 1; j >= 0; j--) {\n token = tokens[j];\n if (token[0] !== 'space') {\n founded += 1;\n if (founded === 2) break;\n }\n }\n throw this.input.error('Missed semicolon',
token[2], token[3]);\n }\n}\n","// @flow\nimport Parser from './parser';\nimport Input from './input';\n\nexport default function parse(css, opts) {\n if (opts && opts.safe) {\n throw new Error('Option safe was removed. ' +
'Use parser: require(\"postcss-safe-parser\")');\n }\n\n const input = new Input(css, opts);\n\n const parser = new Parser(input);\n try {\n parser.tokenize();\n parser.loop();\n } catch (e) {\n if (e.name === 'CssSyntaxError' && opts && opts.from) {\n if (/\\.scss$/i.test(opts.from)) {\n e.message +=\n '\\nYou tried to parse SCSS with ' +\n 'the standard CSS parser; ' +\n 'try again with the postcss-scss parser';\n } else if (/\\.less$/i.test(opts.from)) {\n e.message +=\n '\\nYou tried to parse Less with ' +\n 'the standard CSS parser; ' +\n 'try again with the postcss-less parser';\n }\n }\n throw e;\n }\n\n return parser.root;\n}\n","// @flow\nimport
parse from './parse';\nimport Root from './root';\nimport Rule from './rule';\nimport AtRule from './at-rule';\nimport Declaration from './declaration';\nimport warnOnce from './warn-once';\nimport Comment from './comment';\nimport Node from './node';\n\nfunction cleanSource(nodes) {\n return nodes.map(i => {\n if (i.nodes) i.nodes = cleanSource(i.nodes);\n delete i.source;\n return i;\n });\n}\n\n/**\n * @callback childCondition\n * @param {Node} node - container child\n * @param {number} index - child index\n * @param {Node[]} nodes - all container children\n * @return {boolean}\n */\n\n/**\n * @callback childIterator\n * @param {Node} node - container child\n * @param {number} index - child index\n * @return {false|undefined} returning `false` will break iteration\n */\n\n/**\n * The {@link Root}, {@link AtRule}, and {@link Rule} container nodes\n * inherit some common methods to help work with their children.\n *\n * Note that all containers can store any content.
If you write a rule inside\n * a rule, PostCSS will parse it.\n *\n * @extends Node\n * @abstract\n */\nclass Container extends Node {\n push(child) {\n child.parent = this;\n this.nodes.push(child);\n return this;\n }\n\n /**\n * Iterates through the container's immediate children,\n * calling `callback` for each child.\n *\n * Returning `false` in the callback will break iteration.\n *\n * This method only iterates through the container's immediate children.\n * If you need to recursively iterate through all the container's descendant\n * nodes, use {@link Container#walk}.\n *\n * Unlike the for `{}`-cycle or `Array#forEach` this iterator is safe\n * if you are mutating the array of child nodes during iteration.\n * PostCSS will adjust the current index to match the mutations.\n *\n * @param {childIterator} callback - iterator receives each node and index\n *\n * @return {false|undefined} returns `false` if iteration was broke\n *\n

```
 * @example\n   * const root = postcss.parse('a { color: black; z-index: 1 }');\n   * const rule = root.first;\n   *\n   * for ( let decl of rule.nodes ) {\n   *     decl.cloneBefore({ prop: '-webkit-' + decl.prop });\n   *     // Cycle will be infinite, because cloneBefore moves the current node\n   *     // to the next index\n   * }\n   *\n   * rule.each(decl => {\n   *     decl.cloneBefore({ prop: '-webkit-' + decl.prop });\n   *     // Will be executed only for color and z-index\n   * });\n   */\n  each(callback) {\n    if (!this.lastEach) this.lastEach = 0;\n    if (!this.indexes) this.indexes = {};\n\n    this.lastEach += 1;\n    const id = this.lastEach;\n    this.indexes[id] = 0;\n\n    if (!this.nodes) return undefined;\n\n    let index, result;\n    while (this.indexes[id] < this.nodes.length) {\n      index = this.indexes[id];\n      result = callback(this.nodes[index], index);\n      if (result === false) break;\n\n      this.indexes[id] += 1;\n    }\n\n    delete this.indexes[id];\n\n    return result;\n  }\n\n  /**\n   * Traverses the container's descendant nodes, calling callback\n   * for each node.\n   *\n   * Like container.each(), this method is safe to use\n   * if you are mutating arrays during iteration.\n   *\n   * If you only need to iterate through the container's immediate children,\n   * use {@link Container#each}.\n   *\n   * @param {childIterator} callback - iterator receives each node and index\n   *\n   * @return {false|undefined} returns `false` if iteration was broke\n   *\n   * @example\n   * root.walk(node => {\n   *   // Traverses all descendant nodes.\n   * });\n   */\n  walk(callback) {\n    return this.each((child, i) => {\n      let result = callback(child, i);\n      if (result !== false && child.walk) {\n        result = child.walk(callback);\n      }\n      return result;\n    });\n  }\n\n  /**\n   * Traverses the container's descendant nodes, calling callback\n   * for each declaration node.\n   *\n   * If you pass a filter,
   iteration will only happen over declarations\n   * with matching properties.\n   *\n   * Like {@link Container#each}, this method is safe\n   * to use if you are mutating arrays during iteration.\n   *\n   * @param {string|RegExp} [prop]
   - string or regular expression\n   *                              to filter declarations by property name\n   * @param {childIterator} callback - iterator receives each node and index\n   *\n   * @return {false|undefined} returns `false` if iteration was broke\n   *\n   * @example\n   * root.walkDecls(decl => {\n   *   checkPropertySupport(decl.prop);\n   * });\n   *\n   * root.walkDecls('border-radius', decl => {\n   *   decl.remove();\n   * });\n   *\n   * root.walkDecls(/^background/, decl => {\n   *   decl.value = takeFirstColorFromGradient(decl.value);\n   * });\n   */\n  walkDecls(prop, callback) {\n    if (!callback) {\n      callback = prop;\n      return this.walk((child, i) => {\n        if (child.type === 'decl') {\n          return
    callback(child, i);\n        }\n      });\n    } else if (prop instanceof RegExp) {\n      return this.walk((child, i) => {\n        if (child.type === 'decl' && prop.test(child.prop)) {\n          return callback(child, i);\n        }\n      });\n    } else {\n      return this.walk((child, i) => {\n        if (child.type === 'decl' && child.prop === prop) {\n          return callback(child, i);\n        }\n      });\n    }\n  }\n\n  /**\n   * Traverses the container's descendant nodes, calling callback\n   * for each rule node.\n   *\n   * If you pass a filter, iteration will only happen over rules\n   * with matching selectors.\n   *\n   * Like {@link Container#each}, this method is safe\n   * to use if you are mutating arrays during iteration.\n   *\n   * @param {string|RegExp} [selector] - string or regular expression\n   *                              to filter rules by selector\n   * @param {childIterator} callback   - iterator receives each node and index\n   *\n   * @return
    {false|undefined} returns `false` if iteration was broke\n   *\n   * @example\n   * const selectors = [];\n   * root.walkRules(rule => {\n   *   selectors.push(rule.selector);\n   * });\n   * console.log(`Your CSS uses ${selectors.length} selectors`);\n   */\n  walkRules(selector, callback) {\n    if (!callback) {\n      callback = selector;\n\n      return this.walk((child, i) => {\n        if (child.type === 'rule') {\n          return callback(child, i);\n        }\n      });\n    } else if (selector instanceof RegExp) {\n      return this.walk((child, i) => {\n        if (child.type === 'rule' && selector.test(child.selector)) {\n          return callback(child, i);\n        }\n      });\n    } else {\n      return this.walk((child, i) => {\n        if (child.type === 'rule' && child.selector === selector) {\n          return callback(child, i);\n        }\n      });\n    }\n  }\n\n  /**\n   * Traverses the container's descendant nodes, calling callback\n   * for each at-rule
    node.\n   *\n   * If you pass a filter, iteration will only happen over at-rules\n   * that have matching names.\n   *\n   * Like {@link Container#each}, this method is safe\n   * to use if you are mutating arrays during iteration.\n   *\n   * @param {string|RegExp} [name]   - string or regular expression\n   *                              to filter at-rules by
```

name\n * @param {childIterator} callback - iterator receives each node and index\n *\n * @return {false|undefined} returns `false` if iteration was broke\n *\n * @example\n * root.walkAtRules(rule => {\n * if (isOld(rule.name)) rule.remove();\n * });\n *\n * let first = false;\n * root.walkAtRules('charset', rule => {\n * if (!first) {\n * first = true;\n * } else {\n * rule.remove();\n * }\n * });\n */\n walkAtRules(name, callback) {\n if (!callback) {\n callback = name;\n return this.walk((child, i) => {\n if (child.type === 'atrule') {\n return callback(child, i);\n }\n });\n } else if (name instanceof RegExp) {\n return this.walk((child, i) => {\n if (child.type === 'atrule' && name.test(child.name)) {\n return callback(child, i);\n }\n });\n } else {\n return this.walk((child, i) => {\n if (child.type === 'atrule' && child.name === name) {\n return callback(child, i);\n }\n });\n }\n }\n\n /**\n * Traverses the container’s descendant nodes, calling callback\n * for each comment node.\n *\n * Like {@link Container#each}, this method is safe\n * to use if you are mutating arrays during iteration.\n *\n * @param {childIterator} callback - iterator receives each node and index\n *\n * @return {false|undefined} returns `false` if iteration was broke\n *\n * @example\n * root.walkComments(comment => {\n * comment.remove();\n * });\n */\n walkComments(callback) {\n return this.walk((child, i) => {\n if (child.type === 'comment') {\n return callback(child, i);\n }\n });\n }\n\n /**\n * Inserts new nodes to the start of the container.\n *\n * @param {...(Node|object|string|Node[])} children - new nodes\n *\n * @return {Node} this node for methods chain\n *\n * @example\n * const decl1 = postcss.decl({ prop: 'color', value: 'black' });\n * const decl2 = postcss.decl({ prop: 'background-color', value: 'white' });\n * rule.append(decl1, decl2);\n *\n * root.append({ name: 'charset', params: '\"UTF-8\"' }); // at-rule\n * root.append({ selector: 'a' }); // rule\n * rule.append({ prop: 'color', value: 'black' }); // declaration\n * rule.append({ text: 'Comment' }) // comment\n *\n * root.append('a {}');\n * root.first.append('color: black; z-index: 1');\n */\n append(...children) {\n children.forEach(child => {\n const nodes = this.normalize(child, this.last);\n nodes.forEach(node => this.nodes.push(node));\n });\n return this;\n }\n\n /**\n * Inserts new nodes to the end of the container.\n *\n * @param {...(Node|object|string|Node[])} children - new nodes\n *\n * @return {Node} this node for methods chain\n *\n * @example\n * const decl1 = postcss.decl({ prop: 'color', value: 'black' });\n * const decl2 = postcss.decl({ prop: 'background-color', value: 'white' });\n * rule.prepend(decl1, decl2);\n *\n * root.append({ name: 'charset', params: '\"UTF-8\"' }); // at-rule\n * root.append({ selector: 'a' }); // rule\n * rule.append({ prop: 'color', value: 'black' }); // declaration\n * rule.append({ text: 'Comment' }) // comment\n *\n * root.append('a {}');\n * root.first.append('color: black; z-index: 1');\n */\n prepend(...children) {\n children = children.reverse();\n children.forEach(child => {\n const nodes = this.normalize(child, this.first, 'prepend').reverse();\n nodes.forEach(node => this.nodes.unshift(node));\n for (const id in this.indexes) {\n this.indexes[id] = this.indexes[id] + nodes.length;\n }\n });\n return this;\n }\n\n cleanRaws(keepBetween) {\n super.cleanRaws(keepBetween);\n if (this.nodes) {\n this.nodes.forEach(node => node.cleanRaws(keepBetween));\n }\n }\n\n /**\n * Insert new node before old node within the container.\n *\n * @param {Node|number} exist - child or child’s index.\n * @param {Node|object|string|Node[]} add - new node\n *\n * @return {Node} this node for methods chain\n *\n * @example\n * rule.insertBefore(decl, decl.clone({ prop: '-webkit-' + decl.prop }));\n */\n insertBefore(exist, add) {\n exist = this.index(exist);\n\n const type = exist === 0 ? 'prepend' : false;\n const nodes = this.normalize(add, this.nodes[exist], type).reverse();\n nodes.forEach(node => this.nodes.splice(exist, 0, node));\n\n let index;\n for (const id in this.indexes) {\n index = this.indexes[id];\n if (exist <= index) {\n this.indexes[id] = index + nodes.length;\n }\n }\n\n return this;\n }\n\n /**\n * Insert new node after old node within the container.\n *\n * @param {Node|number} exist - child or child’s index\n * @param {Node|object|string|Node[]} add - new node\n *\n * @return {Node} this node for methods chain\n */\n insertAfter(exist, add) {\n exist = this.index(exist);\n\n const nodes = this.normalize(add, this.nodes[exist]).reverse();\n nodes.forEach(node => this.nodes.splice(exist + 1, 0, node));\n\n let index;\n for

(const id in this.indexes) {\n index = this.indexes[id];\n if (exist < index) {\n this.indexes[id] = index + nodes.length;\n }\n }\n\n return this;\n }\n\n remove(child) {\n if (typeof child !== 'undefined') {\n warnOnce('Container#remove is deprecated. ' + 'Use Container#removeChild');\n this.removeChild(child);\n } else {\n super.remove();\n }\n return this;\n }\n\n /**\n * Removes node from the container and cleans the parent properties\n * from the node and its children.\n *\n * @param {Node|number} child - child or child's index\n *\n * @return {Node} this node for methods chain\n *\n * @example\n * rule.nodes.length //=> 5\n * rule.removeChild(decl);\n * rule.nodes.length //=> 4\n * decl.parent //=> undefined\n */\n removeChild(child) {\n child = this.index(child);\n this.nodes[child].parent = undefined;\n this.nodes.splice(child, 1);\n\n let index;\n for (const id in this.indexes) {\n index = this.indexes[id];\n if (index >= child) {\n this.indexes[id] = index - 1;\n }\n }\n\n return this;\n }\n\n /**\n * Removes all children from the container\n * and cleans their parent properties.\n *\n * @return {Node} this node for methods chain\n *\n * @example\n * rule.removeAll();\n * rule.nodes.length //=> 0\n */\n removeAll() {\n this.nodes.forEach(node => (node.parent = undefined));\n this.nodes = [];\n return this;\n }\n\n /**\n * Passes all declaration values within the container that match pattern\n * through callback, replacing those values with the returned result\n * of callback.\n *\n * This method is useful if you are using a custom unit or function\n * and need to iterate through all values.\n *\n * @param {string|RegExp} pattern - replace pattern\n * @param {object} opts - options to speed up the search\n * @param {string|string[]} opts.props - an array of property names\n * @param {string} opts.fast - string that's used\n * to narrow down values and speed up\n the regexp search\n * @param {function|string} callback\n - string to replace pattern\n * or callback that returns a new\n * value.\n * The callback will receive\n * the same arguments as those\n * passed to a function parameter\n * of `String#replace`.\n *\n * @return {Node} this node for methods chain\n *\n * @example\n * root.replaceValues(/\\d+rem/, { fast: 'rem' }, string => {\n * return 15 * parseInt(string) + 'px';\n * });\n */\n replaceValues(pattern, opts, callback) {\n if (!callback) {\n callback = opts;\n opts = {};\n }\n\n this.walkDecls(decl => {\n if (opts.props && opts.props.indexOf(decl.prop) === -1) return;\n if (opts.fast && decl.value.indexOf(opts.fast) === -1) return;\n\n decl.value = decl.value.replace(pattern, callback);\n });\n\n return this;\n }\n\n /**\n * Returns `true` if callback returns `true`\n * for all of the container's children.\n *\n * @param {childCondition} condition - iterator returns true or false.\n *\n * @return {boolean} is every child pass condition\n *\n * @example\n * const noPrefixes = rule.every(i => i.prop[0] !== '-');\n */\n every(condition) {\n return this.nodes.every(condition);\n }\n\n /**\n * Returns `true` if callback returns `true` for (at least) one\n * of the container's children.\n *\n * @param {childCondition} condition - iterator returns true or false.\n *\n * @return {boolean} is some child pass condition\n *\n * @example\n * const hasPrefix = rule.some(i => i.prop[0] === '-');\n */\n some(condition) {\n return this.nodes.some(condition);\n }\n\n /**\n * Returns a `child`'s index within the {@link Container#nodes} array.\n *\n * @param {Node} child - child of the current container.\n *\n * @return {number} child index\n *\n * @example\n * rule.index(rule.nodes[2]) //=> 2\n */\n index(child) {\n if (typeof child === 'number') {\n return child;\n } else {\n return this.nodes.indexOf(child);\n }\n }\n\n /**\n * The container's first child.\n *\n * @type {Node}\n *\n * @example\n * rule.first == rules.nodes[0];\n */\n get first() {\n if (!this.nodes) return undefined;\n return this.nodes[0];\n }\n\n /**\n * The container's last child.\n *\n * @type {Node}\n *\n * @example\n * rule.last == rule.nodes[rule.nodes.length - 1];\n */\n get last() {\n if (!this.nodes) return undefined;\n return this.nodes[this.nodes.length - 1];\n }\n\n normalize(nodes, sample) {\n if (typeof nodes === 'string') {\n nodes = cleanSource(parse(nodes).nodes);\n } else if (!Array.isArray(nodes)) {\n if (nodes.type === 'root') {\n nodes = nodes.nodes;\n } else if (nodes.type) {\n nodes

= [nodes];\n } else if (nodes.prop) {\n if (typeof nodes.value === 'undefined') {\n throw new Error('Value field is missed in node creation');\n } else if (typeof nodes.value !== 'string') {\n nodes.value = String(nodes.value);\n }\n nodes = [new Declaration(nodes)];\n } else if (nodes.selector) {\n nodes = [new Rule(nodes)];\n } else if (nodes.name) {\n nodes = [new AtRule(nodes)];\n } else if (nodes.text) {\n nodes = [new Comment(nodes)];\n } else {\n throw new Error('Unknown node type in node creation');\n }\n }\n\n const processed = nodes.map(i => {\n if (typeof i.raws === 'undefined') i = this.rebuild(i);\n\n if (i.parent) i = i.clone();\n if (typeof i.raws.before === 'undefined') {\n if (sample && typeof sample.raws.before !== 'undefined') {\n i.raws.before = sample.raws.before.replace(/[^\\s]/g, '');\n }\n }\n i.parent
= this;\n return i;\n });\n\n return processed;\n }\n\n rebuild(node, parent) {\n let fix;\n if (node.type === 'root') {\n fix = new Root();\n } else if (node.type === 'atrule') {\n fix = new AtRule();\n } else if (node.type === 'rule') {\n fix = new Rule();\n } else if (node.type === 'decl') {\n fix = new Declaration();\n } else if (node.type === 'comment') {\n fix = new Comment();\n }\n\n for (const i in node) {\n if (i === 'nodes') {\n fix.nodes = node.nodes.map(j => this.rebuild(j, fix));\n } else if (i === 'parent' && parent) {\n fix.parent = parent;\n } else if (node.hasOwnProperty(i)) {\n fix[i] = node[i];\n }\n }\n\n return fix;\n }\n\n eachInside(callback) {\n warnOnce('Container#eachInside is deprecated. ' + 'Use Container#walk instead.');\n return this.walk(callback);\n }\n\n eachDecl(prop, callback) {\n warnOnce('Container#eachDecl is deprecated. ' + 'Use
Container#walkDecls instead.');\n return this.walkDecls(prop, callback);\n }\n\n eachRule(selector, callback) {\n warnOnce('Container#eachRule is deprecated. ' + 'Use Container#walkRules instead.');\n return this.walkRules(selector, callback);\n }\n\n eachAtRule(name, callback) {\n warnOnce('Container#eachAtRule is deprecated. ' + 'Use Container#walkAtRules instead.');\n return this.walkAtRules(name, callback);\n }\n\n eachComment(callback) {\n warnOnce('Container#eachComment is deprecated. ' + 'Use Container#walkComments instead.');\n return this.walkComments(callback);\n }\n\n get semicolon() {\n warnOnce('Node#semicolon is deprecated. Use Node#raws.semicolon');\n return this.raws.semicolon;\n }\n\n set semicolon(val) {\n warnOnce('Node#semicolon is deprecated. Use Node#raws.semicolon');\n this.raws.semicolon = val;\n }\n\n get after() {\n warnOnce('Node#after is deprecated. Use Node#raws.after');\n return this.raws.after;\n }\n\n
set after(val) {\n warnOnce('Node#after is deprecated. Use Node#raws.after');\n this.raws.after = val;\n }\n\n /**\n * @memberof Container#\n * @member {Node[]} nodes - an array containing the container’s children\n *\n * @example\n * const root = postcss.parse('a { color: black }');\n * root.nodes.length //=> 1\n * root.nodes[0].selector //=> 'a'\n * root.nodes[0].nodes[0].prop //=> 'color'\n */\n}\n\nexport default Container;\n","// @flow\nimport Container from './container';\nimport warnOnce from './warn-once';\n\n/**\n * Represents an at-rule.\n *\n * If it’s followed in the CSS by a {} block, this node will have\n * a nodes property representing its children.\n *\n * @extends Container\n *\n * @example\n * const root = postcss.parse('@charset \"UTF-8\"; @media print {}');\n *\n * const charset = root.first;\n * charset.type //=> 'atrule'\n * charset.nodes //=> undefined\n *\n * const media = root.last;\n * media.nodes //=> []\n */\nclass
AtRule extends Container {\n constructor(defaults) {\n super(defaults);\n this.type = 'atrule';\n }\n\n append(...children) {\n if (!this.nodes) this.nodes = [];\n return super.append(...children);\n }\n\n prepend(...children) {\n if (!this.nodes) this.nodes = [];\n return super.prepend(...children);\n }\n\n get afterName() {\n warnOnce('AtRule#afterName was deprecated. Use AtRule#raws.afterName');\n return this.raws.afterName;\n }\n\n set afterName(val) {\n warnOnce('AtRule#afterName was deprecated. Use AtRule#raws.afterName');\n this.raws.afterName = val;\n }\n\n get _params() {\n warnOnce('AtRule#_params was deprecated. Use AtRule#raws.params');\n return this.raws.params;\n }\n\n set _params(val) {\n warnOnce('AtRule#_params was deprecated. Use AtRule#raws.params');\n this.raws.params = val;\n }\n\n /**\n * @memberof AtRule#\n * @member {string} name - the at-rule’s name immediately follows the `@`\n *\n * @example\n

```
 * const root  = postcss.parse('@media print {}');\n   * media.name //=> 'media'\n   * const media = root.first;\n */\n\n  /**\n   * @memberof AtRule#\n   * @member {string} params - the at-rule's parameters, the values\n   *                  that follow the at-rule's name but precede\n   *                  any {} block\n   *\n   * @example\n   * const root  = postcss.parse('@media print, screen {}');\n   * const media = root.first;\n   * media.params //=> 'print, screen'\n   */\n\n  /**\n   * @memberof AtRule#\n   * @member {object} raws - Information to generate byte-to-byte equal\n   *                         node string as it was in the origin input.\n   *\n   * Every parser saves its own properties,\n   * but the default CSS parser uses:\n   *\n   * * `before`: the space symbols before the node. It also stores `*`\n   *   and `_` symbols before the declaration (IE hack).\n   * * `after`: the space symbols after the last child of the node\n   *   to the end
 of the node.\n   * * `between`: the symbols between the property and value\n   *   for declarations, selector and `{` for rules, or last parameter\n   *   and `{` for at-rules.\n   * * `semicolon`: contains true if the last child has\n   *   an (optional) semicolon.\n   * * `afterName`: the space between the at-rule name and its parameters.\n   *\n   * PostCSS cleans at-rule parameters from comments and extra spaces,\n   * but it stores origin content in raws properties.\n   * As such, if you don't change a declaration's value,\n   * PostCSS will use the raw value with comments.\n   *\n   * @example\n   * const root = postcss.parse('  @media\\nprint {\\n}')\n   * root.first.first.raws //=> { before: '  ',\n   *                       //     between: ' ',\n   *                       //     afterName: '\\n',\n   *                       //     after: '\\n' }\n */\n}\n\nexport default AtRule;\n","// @flow\n/**\n * Contains helpers for safely splitting lists of CSS values,\n * preserving parentheses
 and quotes.\n *\n * @example\n * const list = postcss.list;\n *\n * @namespace list\n */\nconst list = {\n  split(string, separators, last) {\n    const array = [];\n    let current = '';\n    let split = false;\n\n    let func = 0;\n    let quote = false;\n    let escape = false;\n\n    for (let i = 0; i < string.length; i++) {\n      const letter = string[i];\n\n      if (quote) {\n        if (escape) {\n          escape = false;\n        } else if (letter === '\\\\') {\n          escape = true;\n        } else if (letter === quote) {\n          quote = false;\n        }\n      } else if (letter === '"' || letter === '\'') {\n        quote = letter;\n      } else if (letter === '(') {\n        func += 1;\n      } else if (letter === ')') {\n        if (func > 0) func -= 1;\n      } else if (func === 0) {\n        if (separators.indexOf(letter) !== -1) split = true;\n      }\n\n      if (split) {\n        if (current !== '') array.push(current.trim());\n        current =
 '';\n        split = false;\n      } else {\n        current += letter;\n      }\n    }\n\n    if (last || current !== '')
array.push(current.trim());\n    return array;\n  },\n\n  /**\n   * Safely splits space-separated values (such as those for
`background`,\n   * `border-radius`, and other shorthand properties).\n   *\n   * @param {string} string - space-separated values\n   *\n   * @return {string[]} splitted values\n   *\n   * @example\n   * postcss.list.space('1px calc(10% + 1px)') //=> ['1px', 'calc(10% + 1px)']\n   */\n  space(string) {\n    const spaces = [' ', '\\n', '\\t'];\n    return list.split(string, spaces);\n  },\n\n  /**\n   * Safely splits comma-separated values (such as those for `transition-*`\n * and `background` properties).\n   *\n   * @param {string} string - comma-separated values\n   *\n   * @return {string[]} splitted values\n   *\n   * @example\n   * postcss.list.comma('black, linear-gradient(white, black)')\n   * //=> ['black', 'linear-gradient(white, black)']\n
   */\n  comma(string) {\n    const comma = ',';\n    return list.split(string, [comma], true);\n  },\n};\n\nexport default list;\n","// @flow\nimport './at-rule'; // break cyclical dependency deadlock – #87\nimport Container from './container';\nimport warnOnce from './warn-once';\nimport list from './list';\n\n/**\n * Represents a CSS rule: a selector followed by a declaration block.\n *\n * @extends Container\n *\n * @example\n * const root = postcss.parse('a{}');\n * const rule = root.first;\n * rule.type       //=> 'rule'\n * rule.toString() //=> 'a{}'\n */\nclass Rule extends Container {\n  constructor(defaults) {\n    super(defaults);\n    this.type = 'rule';\n    if (!this.nodes) this.nodes = [];\n  }\n\n  /**\n   * An array containing the rule's individual selectors.\n   * Groups of selectors are split at commas.\n   *\n   * @type {string[]}\n   *\n   * @example\n   * const root = postcss.parse('a, b { }');\n   * const rule = root.first;\n   *\n   * rule.selector  //=>
 'a, b'\n   * rule.selectors //=> ['a', 'b']\n   *\n   * rule.selectors = ['a', 'strong'];\n   * rule.selector //=> 'a, strong'\n   */\n  get selectors() {\n    return list.comma(this.selector);\n  }\n\n  set selectors(values) {\n    const match = this.selector ? this.selector.match(/,\\s*/) : null;\n    const sep = match ? match[0] : `,${this.raw('between', 'beforeOpen')}`;\n    this.selector = values.join(sep);\n  }\n\n  get _selector() {\n    warnOnce('Rule#_selector is deprecated. Use
```

```
Rule#raws.selector');\n    return this.raws.selector;\n  }\n\n  set _selector(val) {\n    warnOnce('Rule#_selector is deprecated. Use Rule#raws.selector');\n    this.raws.selector = val;\n  }\n\n  /**\n   * @memberof Rule#\n   * @member {string} selector - the rule's full selector represented\n   *                             as a string\n   *\n   * @example\n   * const root = postcss.parse('a, b { }');\n   * const rule = root.first;\n   * rule.selector //=> 'a, b'\n   */\n\n  /**\n   * @memberof Rule#\n
   * @member {object} raws - Information to generate byte-to-byte equal\n   *                         node string as it was in the origin input.\n   *\n   * Every parser saves its own properties,\n   * but the default CSS parser uses:\n   *\n   * * `before`: the space symbols before the node. It also stores `*`\n   *   and `_` symbols before the declaration (IE hack).\n   * * `after`: the space symbols after the last child of the node\n   *   to the end of the node.\n   * * `between`: the symbols between the property and value\n   *   for declarations, selector and `{` for rules, or last parameter\n   *   and `{` for at-rules.\n   * * `semicolon`: contains true if the last child has\n   *   an (optional) semicolon.\n   *\n   * PostCSS cleans selectors from comments and extra spaces,\n   * but it stores origin content in raws properties.\n   * As such, if you don't change a declaration's value,\n   * PostCSS will use the raw value with comments.\n   *\n   * @example\n   * const root
 = postcss.parse('a {\\n  color:black\\n}')\n   * root.first.first.raws //=> { before: '', between: ' ', after: '\\n' }\n   */\n}\n\nexport default Rule;\n","// @flow\n/**\n * Represents a plugin's warning. It can be created using {@link Node#warn}.\n *\n * @example\n * if ( decl.important ) {\n *     decl.warn(result, 'Avoid !important', { word: '!important' });\n * }\n */\nclass Warning {\n  /**\n   * @param {string} text        - warning message\n   * @param {Object} [opts]      - warning options\n   * @param {Node}   opts.node   - CSS node that caused the warning\n   * @param {string} opts.word   - word in CSS source that caused the warning\n   * @param {number} opts.index  - index in CSS node string that caused\n   *                               the warning\n   * @param {string} opts.plugin - name of the plugin that created\n   *                               this warning. {@link Result#warn} fills\n   *                               this property automatically.\n   */\n  constructor(text,
 opts = {}) {\n    /**\n     * @member {string} - Type to filter warnings from\n     *                    {@link Result#messages}. Always equal\n     *                    to `\"warning\"`.\n     *\n     * @example\n     * const nonWarning = result.messages.filter(i => i.type !== 'warning')\n     */\n    this.type = 'warning';\n    /**\n     * @member {string} - The warning message.\n     *\n     * @example\n     * warning.text //=> 'Try to avoid !important'\n     */\n    this.text = text;\n\n    if (opts.node && opts.node.source) {\n      const pos = opts.node.positionBy(opts);\n      /**\n       * @member {number} - Line in the input file\n       *                    with this warning's source\n       *\n       * @example\n       * warning.line //=> 5\n       */\n      this.line = pos.line;\n      /**\n       * @member {number} - Column in the input file\n       *                    with this warning's source.\n       *\n       * @example\n       * warning.column //=> 6\n
       */\n      this.column = pos.column;\n    }\n\n    for (const opt in opts) this[opt] = opts[opt];\n  }\n\n  /**\n   * Returns a warning position and message.\n   *\n   * @example\n   * warning.toString() //=> 'postcss-lint:a.css:10:14: Avoid !important'\n   *\n   * @return {string} warning position and message\n   */\n  toString() {\n    if (this.node) {\n      return this.node.error(this.text, {\n        plugin: this.plugin,\n        index: this.index,\n        word: this.word,\n      }).message;\n    } else if (this.plugin) {\n      return `${this.plugin}: ${this.text}`;\n    } else {\n      return this.text;\n    }\n  }\n\n  /**\n   * @memberof Warning#\n   * @member {string} plugin - The name of the plugin that created\n   *                           it will fill this property automatically.\n   *                           this warning. When you call {@link Node#warn}\n   *\n   * @example\n   * warning.plugin //=> 'postcss-important'\n   */\n\n  /**\n   * @memberof Warning#\n
   * @member {Node} node - Contains the CSS node that caused the warning.\n   *\n   * @example\n   * warning.node.toString() //=> 'color: white !important'\n   */\n}\n\nexport default Warning;\n","// @flow\nimport Warning from './warning';\n\n/**\n * @typedef  {object} Message\n * @property {string} type   - message type\n * @property {string} plugin - source PostCSS plugin name\n */\n\n/**\n * Provides the result of the PostCSS transformations.\n *\n * A Result instance is returned by {@link LazyResult#then}\n * or {@link Root#toResult} methods.\n *\n * @example\n * postcss([cssnext]).process(css).then(function (result) {\n *   console.log(result.css);\n * });\n *\n * @example\n * var result2 = postcss.parse(css).toResult();\n */\nclass Result
```

{\n /**\n * @param {Processor} processor - processor used for this transformation.\n * @param {Root} root - Root node after all transformations.\n * @param {processOptions} opts - options from the {@link Processor#process}\n *
or {@link Root#toResult}\n */\n constructor(processor, root, opts) {\n /**\n * @member {Processor} - The Processor instance used\n * for this transformation.\n *\n * @example\n * for (let plugin of result.processor.plugins) {\n * if (plugin.postcssPlugin === 'postcss-bad') {\n * throw 'postcss-good is incompatible with postcss-bad';\n * }\n * });\n */\n this.processor = processor;\n /**\n * @member {Message[]} - Contains messages from plugins\n * (e.g., warnings or custom messages).\n * Each message should have type\n * and plugin properties.\n *\n * @example\n * postcss.plugin('postcss-min-browser', () => {\n * return (root, result) => {\n * var browsers = detectMinBrowsersByCanIUse(root);\n * result.messages.push({\n * type: 'min-browser',\n * plugin: 'postcss-min-browser',\n * browsers: browsers\n * });\n * };\n * });\n */\n this.messages = [];\n /**\n * @member {Root} - Root node after all transformations.\n *\n * @example\n * root.toResult().root == root;\n */\n this.root = root;\n /**\n * @member {processOptions} - Options from the {@link Processor#process}\n * or {@link Root#toResult} call\n * that produced this Result instance.\n *\n * @example\n * root.toResult(opts).opts == opts;\n */\n this.opts = opts;\n /**\n * @member {string} - A CSS string representing of {@link Result#root}.\n *\n * @example\n * postcss.parse('a{}').toResult().css //=> \"a{}\"\n */\n this.css = undefined;\n /**\n * @member {SourceMapGenerator} - An instance of `SourceMapGenerator`\n * class from the `source-map` library,\n * representing changes\n * to the {@link Result#root} instance.\n *\n * @example\n * result.map.toJSON() //=> { version: 3, file: 'a.css', … }\n *\n * @example\n * if (result.map) {\n * fs.writeFileSync(result.opts.to + '.map', result.map.toString());\n * }\n */\n this.map = undefined;\n }\n\n /**\n * Returns for @{link Result#css} content.\n *\n * @example\n * result + '' === result.css\n *\n * @return {string} string representing of {@link Result#root}\n */\n toString() {\n return this.css;\n }\n\n /**\n * Creates an instance of {@link Warning} and adds it\n * to {@link Result#messages}.\n *\n * @param {string} text - warning message\n * @param {Object} [opts] - warning options\n * @param {Node} opts.node - CSS node that caused the warning\n * @param {string} opts.word - word in CSS source that caused the warning\n * @param {number} opts.index - index in CSS node string that caused\n * the warning\n * @param {string} opts.plugin - name of the plugin that created\n * this warning. {@link Result#warn} fills\n * this property automatically.\n *\n * @return {Warning} created warning\n */\n warn(text, opts = {}) {\n if (!opts.plugin) {\n if (this.lastPlugin && this.lastPlugin.postcssPlugin) {\n opts.plugin = this.lastPlugin.postcssPlugin;\n }\n }\n\n const warning = new Warning(text, opts);\n this.messages.push(warning);\n\n return warning;\n }\n\n /**\n * Returns warnings from plugins. Filters {@link Warning} instances\n * from {@link Result#messages}.\n *\n * @example\n * result.warnings().forEach(warn => {\n * console.warn(warn.toString());\n * });\n *\n * @return {Warning[]} warnings from plugins\n */\n warnings() {\n return this.messages.filter(i => i.type === 'warning');\n }\n\n /**\n * An alias for the {@link Result#css} property.\n * Use it with syntaxes that generate non-CSS output.\n * @type {string}\n *\n * @example\n * result.css === result.content;\n */\n get content() {\n return this.css;\n }\n}\n\nexport default Result;\n","// @flow\nimport stringify from './stringify';\nimport warnOnce from './warn-once';\nimport Result from './result';\nimport parse from './parse';\n\nfunction isPromise(obj) {\n return typeof obj === 'object' && typeof obj.then === 'function';\n}\n\n/**\n * @callback onFulfilled\n * @param {Result} result\n */\n\n/**\n * @callback onRejected\n * @param {Error} error\n */\n\n/**\n * A Promise proxy for the result of PostCSS transformations.\n *\n * A `LazyResult` instance is returned by {@link Processor#process}.\n *\n * @example\n * const lazy = postcss([cssnext]).process(css);\n */\nclass LazyResult {\n constructor(processor, css, opts) {\n this.stringified

```
 = false;\n    this.processed = false;\n\n    let root;\n    if (typeof css === 'object' && css.type === 'root') {\n      root = css;\n    } else if (css instanceof LazyResult || css instanceof Result) {\n      root = css.root;\n      if (css.map) {\n if (typeof opts.map === 'undefined') opts.map = {};\n        if (!opts.map.inline) opts.map.inline = false;\n opts.map.prev = css.map;\n      }\n    } else {\n      let parser = parse;\n      if (opts.syntax) parser = opts.syntax.parse;\n      if (opts.parser) parser = opts.parser;\n      if (parser.parse) parser = parser.parse;\n\n      try {\n        root = parser(css, opts);\n      } catch (error) {\n        this.error = error;\n      }\n    }\n\n    this.result = new Result(processor, root, opts);\n  }\n\n  /**\n   * Returns a {@link Processor} instance, which will be used\n   * for CSS transformations.\n   * @type {Processor}\n   */\n  get processor() {\n    return this.result.processor;\n  }\n\n  /**\n   * Options from
 the {@link Processor#process} call.\n   * @type {processOptions}\n   */\n  get opts() {\n    return this.result.opts;\n  }\n\n  /**\n   * Processes input CSS through synchronous plugins, converts `Root`\n   * to a CSS string and returns {@link Result#css}.\n   *\n   * This property will only work with synchronous plugins.\n   * If the processor contains any asynchronous plugins\n   * it will throw an error. This is why this method is only\n   * for debug purpose, you should always use {@link LazyResult#then}.\n   *\n   * @type {string}\n   * @see Result#css\n   */\n  get css() {\n    return this.stringify().css;\n  }\n\n  /**\n   * An alias for the `css` property. Use it with syntaxes\n   * that generate non-CSS output.\n   *\n   * This property will only work with synchronous plugins.\n   * If the processor contains any asynchronous plugins\n   * it will throw an error. This is why this method is only\n   * for debug purpose, you should always use {@link LazyResult#then}.\n   *\n
   * @type {string}\n   * @see Result#content\n   */\n  get content() {\n    return this.stringify().content;\n  }\n\n  /**\n
   * Processes input CSS through synchronous plugins\n   * and returns {@link Result#map}.\n   *\n   * This property will only work with synchronous plugins.\n   * If the processor contains any asynchronous plugins\n   * it will throw an error. This is why this method is only\n   * for debug purpose, you should always use {@link LazyResult#then}.\n   *\n   * @type {SourceMapGenerator}\n   * @see Result#map\n   */\n  get map() {\n    return this.stringify().map;\n  }\n\n  /**\n   * Processes input CSS through synchronous plugins\n   * and returns {@link Result#root}.\n   *\n   * This property will only work with synchronous plugins. If the processor\n   * contains any asynchronous plugins it will throw an error.\n   *\n   * This is why this method is only for debug purpose,\n   * you should always use {@link LazyResult#then}.\n   *\n   * @type {Root}\n   * @see Result#root\n
    */\n  get root() {\n    return this.sync().root;\n  }\n\n  /**\n   * Processes input CSS through synchronous plugins\n
   * and returns {@link Result#messages}.\n   *\n   * This property will only work with synchronous plugins. If the processor\n   * contains any asynchronous plugins it will throw an error.\n   *\n   * This is why this method is only for debug purpose,\n   * you should always use {@link LazyResult#then}.\n   *\n   * @type {Message[]}\n   * @see Result#messages\n   */\n  get messages() {\n    return this.sync().messages;\n  }\n\n  /**\n   * Processes input CSS through synchronous plugins\n   * and calls {@link Result#warnings()}.\n   *\n   * @return {Warning[]} warnings from plugins\n   */\n  warnings() {\n    return this.sync().warnings();\n  }\n\n  /**\n   * Alias for the {@link LazyResult#css} property.\n   *\n   * @example\n   * lazy + '' === lazy.css;\n   *\n   * @return {string} output CSS\n   */\n  toString() {\n    return this.css;\n  }\n\n  /**\n   *
 Processes input CSS through synchronous and asynchronous plugins\n   * and calls `onFulfilled` with a Result instance. If a plugin throws\n   * an error, the `onRejected` callback will be executed.\n   *\n   * It implements standard Promise API.\n   *\n   * @param {onFulfilled} onFulfilled - callback will be executed\n   *
       when all plugins will finish work\n   * @param {onRejected}  onRejected  - callback will be execited on any error\n   *\n   * @return {Promise} Promise API to make queue\n   *\n   * @example\n   * postcss([cssnext]).process(css).then(result => {\n   *   console.log(result.css);\n   * });\n   */\n  then(onFulfilled, onRejected) {\n    return this.async().then(onFulfilled, onRejected);\n  }\n\n  /**\n   * Processes input CSS through synchronous and asynchronous plugins\n   * and calls onRejected for each error thrown in any plugin.\n   *\n   * It implements standard Promise API.\n   *\n   * @param {onRejected} onRejected - callback will
 be execited on any error\n   *\n   * @return {Promise} Promise API to make queue\n   *\n   * @example\n   * postcss([cssnext]).process(css).then(result => {\n   *   console.log(result.css);\n   * }).catch(error => {\n   *   console.error(error);\n   * });\n   */\n  catch(onRejected) {\n    return this.async().catch(onRejected);\n  }\n\n
```

```
handleError(error, plugin) {\n    try {\n      this.error = error;\n      if (error.name === 'CssSyntaxError' && !error.plugin) {\n        error.plugin = plugin.postcssPlugin;\n        error.setMessage();\n      } else if (plugin.postcssVersion) {\n        const pluginName = plugin.postcssPlugin;\n        const pluginVer = plugin.postcssVersion;\n        const runtimeVer = this.result.processor.version;\n        const a = pluginVer.split('.');\n        const b = runtimeVer.split('.');\n\n        if (a[0] !== b[0] || parseInt(a[1]) > parseInt(b[1])) {\n          warnOnce(\n            `${'Your current PostCSS version ' + 'is '}${runtimeVer}, but ${pluginName}` +\n            `uses ${pluginVer}. Perhaps this is ` +\n            `the source of the error below.`\n          );\n        }\n      }\n    } catch (err) {\n      if (console && console.error) console.error(err);\n    }\n  }\n\n  asyncTick(resolve, reject) {\n    if (this.plugin >= this.processor.plugins.length) {\n      this.processed = true;\n      return resolve();\n    }\n\n    try {\n      const plugin = this.processor.plugins[this.plugin];\n      const promise = this.run(plugin);\n      this.plugin += 1;\n\n      if (isPromise(promise)) {\n        promise\n          .then(() => {\n            this.asyncTick(resolve, reject);\n          })\n          .catch(error => {\n            this.handleError(error, plugin);\n            this.processed = true;\n            reject(error);\n          });\n      } else {\n        this.asyncTick(resolve, reject);\n      }\n    } catch (error) {\n      this.processed = true;\n      reject(error);\n    }\n  }\n\n  async() {\n    if (this.processed) {\n      return new Promise((resolve, reject) => {\n        if (this.error) {\n          reject(this.error);\n        } else {\n          resolve(this.stringify());\n        }\n      });\n    }\n    if (this.processing) {\n      return this.processing;\n    }\n\n    this.processing = new Promise((resolve, reject) => {\n      if (this.error) return reject(this.error);\n      this.plugin = 0;\n      this.asyncTick(resolve, reject);\n    }).then(() => {\n      this.processed = true;\n      return this.stringify();\n    });\n\n    return this.processing;\n  }\n\n  sync() {\n    if (this.processed) return this.result;\n    this.processed = true;\n\n    if (this.processing) {\n      throw new Error('Use process(css).then(cb) to work with async plugins');\n    }\n\n    if (this.error) throw this.error;\n\n    this.result.processor.plugins.forEach(plugin => {\n      const promise = this.run(plugin);\n      if (isPromise(promise)) {\n        throw new Error('Use process(css).then(cb) to work with async plugins');\n      }\n    });\n\n    return this.result;\n  }\n\n  run(plugin) {\n    this.result.lastPlugin = plugin;\n\n    try {\n      return plugin(this.result.root, this.result);\n    } catch (error) {\n      this.handleError(error, plugin);\n      throw error;\n    }\n  }\n\n  stringify() {\n    if (this.stringified) return this.result;\n    this.stringified = true;\n\n    this.sync();\n\n    const opts = this.result.opts;\n    let str = stringify;\n    if (opts.syntax) str = opts.syntax.stringify;\n    if (opts.stringifier) str = opts.stringifier;\n    if (str.stringify) str = str.stringify;\n\n    let result = '';\n    str(this.root, i => {\n      result += i;\n    });\n    this.result.css = result;\n\n    return this.result;\n  }\n}\n\nexport default LazyResult;\n","// @flow\nimport LazyResult from './lazy-result';\n\n/**\n * @callback builder\n * @param {string} part         - part of generated CSS connected to this node\n * @param {Node}   node         - AST node\n * @param {\"start\"|\"end\"} [type] - node's part type\n */\n\n/**\n * @callback parser\n *\n * @param {string|toString} css   - string with input CSS or any object\n *                                  with toString() method, like a Buffer\n * @param {processOptions} [opts] - options with only `from` and `map` keys\n *\n * @return {Root} PostCSS AST\n */\n\n/**\n * @callback stringifier\n *\n * @param {Node} node       - start node for stringifing. Usually {@link Root}.\n * @param {builder} builder - function to concatenate CSS from node's parts\n *                            or generate string and source map\n *\n * @return {void}\n */\n\n/**\n * @typedef {object} syntax\n * @property {parser} parse         - function to generate AST by string\n * @property {stringifier} stringify - function to generate string by AST\n */\n\n/**\n * @typedef {object} toString\n * @property {function} toString\n */\n\n/**\n * @callback pluginFunction\n * @param {Root} root     - parsed input CSS\n * @param {Result} result - result to set warnings or check other plugins\n */\n\n/**\n * @typedef {object} Plugin\n * @property {function} postcss - PostCSS plugin function\n */\n\n/**\n * @typedef {object} processOptions\n * @property {string} from           - the path of the CSS source file.\n *                                     You should always set `from`,\n *                                     because it is used in source map\n *                                     generation and syntax error messages.\n * @property {string} to             - the path where you'll put the output\n *                                     CSS file. You should always set `to`\n *                                     to generate correct source maps.\n * @property {parser} parser         - function to generate AST by string\n * @property {stringifier} stringifier - class to generate string by AST\n * @property {syntax} syntax         - object with `parse` and
```

`stringify`\n
 * @property {object} map - source map options\n * @property {boolean} map.inline - does source map should\n * be embedded in the output\n *
 CSS as a base64-encoded\n * comment\n * @property {string|object|false|function} map.prev - source map content\n * from a previous\n * processing step\n * (for example, Sass).\n *
 PostCSS will try to find\n * previous map\n *
 automatically, so you\n * could disable it by\n *
 `false` value.\n * @property {boolean} map.sourcesContent - does PostCSS should set\n *
 the origin content to map\n * @property {string|false} map.annotation - does PostCSS should set\n * annotation comment to map\n * @property {string} map.from - override `from` in map's\n * `sources`\n */\n\n/**\n *
Contains plugins to process CSS. Create one `Processor` instance,\n * initialize its plugins, and then use that instance on numerous CSS files.\n *\n * @example\n * const processor = postcss([autoprefixer, precss]);\n *
processor.process(css1).then(result => console.log(result.css));\n * processor.process(css2).then(result =>
console.log(result.css));\n */\nclass Processor {\n /**\n * @param {Array.<Plugin|pluginFunction>|Processor} plugins - PostCSS\n * plugins.
 See {@link Processor#use} for plugin format.\n */\n constructor(plugins = []) {\n /**\n * @member {string} - Current PostCSS version.\n *\n * @example\n * if (result.processor.version.split('.')[0] !== '5') {\n *
throw new Error('This plugin works only with PostCSS 5');\n * }\n */\n this.version = '5.2.0';\n /**\n *
@member {pluginFunction[]} - Plugins added to this processor.\n *\n * @example\n * const processor =
postcss([autoprefixer, precss]);\n * processor.plugins.length //=> 2\n */\n this.plugins =
this.normalize(plugins);\n }\n\n /**\n * Adds a plugin to be used as a CSS processor.\n *\n * PostCSS plugin can be in 4 formats:\n * * A plugin created by {@link postcss.plugin} method.\n * * A function. PostCSS will pass the function a @{link Root}\n * as the first argument and current {@link Result} instance\n * as the second.\n * * An object with a `postcss` method. PostCSS will use that
 method\n * as described in #2.\n * * Another {@link Processor} instance. PostCSS will copy plugins\n *
from that instance into this one.\n *\n * Plugins can also be added by passing them as arguments when creating\n
* a `postcss` instance (see [`postcss(plugins)`]).\n *\n * Asynchronous plugins should return a `Promise`
instance.\n *\n * @param {Plugin|pluginFunction|Processor} plugin - PostCSS plugin\n *
 or {@link Processor}\n * with plugins\n *\n * @example\n * const
processor = postcss()\n * .use(autoprefixer)\n * .use(precss);\n *\n * @return {Processes} current processor
to make methods chain\n */\n use(plugin) {\n this.plugins = this.plugins.concat(this.normalize([plugin]));\n
return this;\n }\n\n /**\n * Parses source CSS and returns a {@link LazyResult} Promise proxy.\n * Because
some plugins can be asynchronous it
 doesn't make\n * any transformations. Transformations will be applied\n * in the {@link LazyResult}
methods.\n *\n * @param {string|toString|Result} css - String with input CSS or\n * any
object with a `toString()`\n * method, like a Buffer.\n *
Optionally, send a {@link Result}\n * instance and the processor will\n *
 take the {@link Root} from it.\n * @param {processOptions} [opts] - options\n *\n * @return
{LazyResult} Promise proxy\n *\n * @example\n * processor.process(css, { from: 'a.css', to: 'a.out.css' })\n *
.then(result => {\n * console.log(result.css);\n * });\n */\n process(css, opts = {}) {\n return new
LazyResult(this, css, opts);\n }\n\n normalize(plugins) {\n let normalized = [];\n plugins.forEach(i => {\n if
(i.postcss)
 i = i.postcss;\n\n if (typeof i === 'object' && Array.isArray(i.plugins)) {\n normalized =
normalized.concat(i.plugins);\n } else if (typeof i === 'function') {\n normalized.push(i);\n } else {\n
throw new Error(`${i} is not a PostCSS plugin`);\n }\n });\n return normalized;\n }\n}\n\nexport default
Processor;\n","// @flow\nimport './rule'; // break cyclical dependency deadlock – #87\n\nimport Container from

'./container';\nimport LazyResult from './lazy-result';\nimport Processor from './processor';\nimport warnOnce from './warn-once';\n\n/**\n * Represents a CSS file and contains all its parsed nodes.\n *\n * @extends Container\n *\n * @example\n * const root = postcss.parse('a{color:black} b{z-index:2}');\n * root.type   //=> 'root'\n * root.nodes.length //=> 2\n */\nclass Root extends Container {\n constructor(defaults) {\n   super(defaults);\n this.type = 'root';\n   if (!this.nodes) this.nodes = [];\n }\n\n removeChild(child)
 {\n   child = this.index(child);\n\n   if (child === 0 && this.nodes.length > 1) {\n   this.nodes[1].raws.before = this.nodes[child].raws.before;\n   }\n\n   return super.removeChild(child);\n }\n\n normalize(child, sample, type) {\n   const nodes = super.normalize(child);\n\n   if (sample) {\n   if (type === 'prepend') {\n   if (this.nodes.length > 1) {\n   sample.raws.before = this.nodes[1].raws.before;\n   } else {\n   delete sample.raws.before;\n   }\n   } else if (this.first !== sample) {\n   nodes.forEach(node => {\n node.raws.before = sample.raws.before;\n   });\n   }\n   }\n\n   return nodes;\n }\n\n /**\n   * Returns a {@link Result} instance representing the root's CSS.\n   *\n   * @param {processOptions} [opts] - options with only `to` and `map` keys\n   *\n   * @return {Result} result with current root's CSS\n   *\n   * @example\n   * const root1 = postcss.parse(css1, { from: 'a.css' });\n
   * const root2 = postcss.parse(css2, { from: 'b.css' });\n   * root1.append(root2);\n   * const result = root1.toResult({ to: 'all.css', map: true });\n   */\n toResult(opts = {}) {\n   const lazy = new LazyResult(new Processor(), this, opts);\n   return lazy.stringify();\n }\n\n remove(child) {\n   warnOnce('Root#remove is deprecated. Use Root#removeChild');\n   this.removeChild(child);\n }\n\n prevMap() {\n   warnOnce('Root#prevMap is deprecated. Use Root#source.input.map');\n   return this.source.input.map;\n }\n\n /**\n   * @memberof Root#\n * @member {object} raws - Information to generate byte-to-byte equal\n   *   node string as it was in the origin input.\n   *\n   * Every parser saves its own properties,\n   * but the default CSS parser uses:\n   *\n   * * `after`: the space symbols after the last child to the end of file.\n   * * `semicolon`: is the last child has an (optional) semicolon.\n   *\n   * @example\n   * postcss.parse('a {}\\n').raws
 //=> { after: '\\n' }\n   * postcss.parse('a {}').raws   //=> { after: '' }\n   */\n}\n\nexport default Root;\n","//
@flow\nimport './root'; // break cyclical dependency deadlock – #87\n\nimport CssSyntaxError from './css-syntax-error';\n// import PreviousMap   from './previous-map';\n\nlet sequence = 0;\n\n/**\n * @typedef {object} filePosition\n * @property {string} file   - path to file\n * @property {number} line   - source line in file\n * @property {number} column - source column in file\n */\n\n/**\n * Represents the source CSS.\n *\n * @example\n * const root = postcss.parse(css, { from: file });\n * const input = root.source.input;\n */\nclass Input {\n /**\n   * @param {string} css   - input CSS source\n   * @param {object} [opts] - {@link Processor#process} options\n   */\n constructor(css, opts = {}) {\n   /**\n   * @member {string} - input CSS source\n   *\n   * @example\n   * const input = postcss.parse('a{}', { from: file }).input;\n   * input.css
 //=> \"a{}\";\n   */\n   this.css = css.toString();\n\n   if (this.css[0] === '\\uFEFF' || this.css[0] === '\\uFFFE') {\n this.css = this.css.slice(1);\n   }\n\n   if (opts.from) {\n   if (/^\\w+:\\/\\//.test(opts.from)) {\n   /**\n   * @member {string} - The absolute path to the CSS source file\n   *   defined with the `from` option.\n   *\n   * @example\n   * const root = postcss.parse(css, { from: 'a.css' });\n   * root.source.input.file
 //=> '/home/ai/a.css'\n   */\n   this.file = opts.from;\n   } else {\n   this.file = path.resolve(opts.from);\n   }\n   }\n\n   /*\n   let map = new PreviousMap(this.css, opts);\n   if (map.text) {\n   /!**\n   * @member {PreviousMap} - The input source map passed from\n   *   a compilation step before PostCSS\n   *   (for example, from Sass compiler).\n   *\n   * @example\n   * root.source.input.map.consumer().sources //=> ['a.sass']\n   *!/\n   this.map = map;\n   let file = map.consumer().file;\n   if (!this.file && file) this.file = this.mapResolve(file);\n   }\n*/\n\n   if (!this.file) {\n   sequence += 1;\n   /**\n   * @member {string} - The unique ID of the CSS source. It will be\n   *   created if `from` option is not provided\n   *   (because PostCSS does not know the file path).\n   *\n   * @example\n   * const root = postcss.parse(css);\n   * root.source.input.file //=> undefined\n   * root.source.input.id   //=> \"<input css 1>\"\n   */\n   this.id = `<input css ${sequence}>`;\n   }\n   if (this.map) this.map.file = this.from;\n }\n\n error(message, line, column, opts = {}) {\n   let result;\n   const origin = this.origin(line, column);\n   if (origin) {\n

```
    result =
 new CssSyntaxError(\n        message,\n        origin.line,\n        origin.column,\n        origin.source,\n
origin.file,\n        opts.plugin\n      );\n    } else {\n      result = new CssSyntaxError(message, line, column, this.css,
this.file, opts.plugin);\n    }\n\n    result.input = { line, column, source: this.css };\n    if (this.file) result.input.file =
this.file;\n\n    return result;\n  }\n\n  /**\n   * Reads the input source map and returns a symbol position\n   * in the
input source (e.g., in a Sass file that was compiled\n   * to CSS before being passed to PostCSS).\n   *\n   * @param
{number} line   - line in input CSS\n   * @param {number} column - column in input CSS\n   *\n   * @return
{filePosition} position in input source\n   *\n   * @example\n   * root.source.input.origin(1, 1) //=> { file: 'a.css',
line: 3, column: 1 }\n   */\n  origin(line, column) {\n    if (!this.map) return false;\n    const consumer =
this.map.consumer();\n\n    const from = consumer.originalPositionFor({
 line, column });\n    if (!from.source) return false;\n\n    const result = {\n      file: this.mapResolve(from.source),\n
 line: from.line,\n      column: from.column,\n    };\n\n    const source = consumer.sourceContentFor(from.source);\n
 if (source) result.source = source;\n\n    return result;\n  }\n\n  mapResolve(file) {\n    if (/^\\w+:\\/\\//.test(file)) {\n
  return file;\n    } else {\n      return path.resolve(this.map.consumer().sourceRoot || '.', file);\n    }\n  }\n\n  /**\n   *
The CSS source identifier. Contains {@link Input#file} if the user\n   * set the `from` option, or {@link Input#id} if
they did not.\n   * @type {string}\n   *\n   * @example\n   * const root = postcss.parse(css, { from: 'a.css' });\n   *
root.source.input.from //=> \"/home/ai/a.css\"\n   *\n   * const root = postcss.parse(css);\n   * root.source.input.from
//=> \"<input css 1>\"\n   */\n  get from() {\n    return this.file || this.id;\n  }\n}\n\nexport default Input;\n","//
 @flow\nimport tokenize from '../postcss/tokenize';\nimport Comment from '../postcss/comment';\nimport Parser
from '../postcss/parser';\n\nexport default class SafeParser extends Parser {\n  tokenize() {\n    this.tokens =
tokenize(this.input, { ignoreErrors: true });\n  }\n\n  comment(token) {\n    const node = new Comment();\n
this.init(node, token[2], token[3]);\n    node.source.end = { line: token[4], column: token[5] };\n\n    let text =
token[1].slice(2);\n    if (text.slice(-2) === '*/') text = text.slice(0, -2);\n\n    if (/^\\s*$/.test(text)) {\n      node.text =
'';\n      node.raws.left = text;\n      node.raws.right = '';\n    } else {\n      const match =
text.match(/^(\\s*)([^]*[^\\s])(\\s*)$/);\n      node.text = match[2];\n      node.raws.left = match[1];\n
node.raws.right = match[3];\n    }\n  }\n\n  unclosedBracket() {}\n\n  unknownWord(start) {\n    const buffer =
this.tokens.slice(start, this.pos + 1);\n    this.spaces += buffer.map(i => i[1]).join('');\n
  }\n\n  unexpectedClose() {\n    this.current.raws.after += '}';\n  }\n\n  doubleColon() {}\n\n  unnamedAtrule(node)
{\n    node.name = '';\n  }\n\n  precheckMissedSemicolon(tokens) {\n    const colon = this.colon(tokens);\n    if
(colon === false) return;\n\n    let split;\n    for (split = colon - 1; split >= 0; split--) {\n      if (tokens[split][0] ===
'word') break;\n    }\n    for (split -= 1; split >= 0; split--) {\n      if (tokens[split][0] !== 'space') {\n        split += 1;\n
    break;\n      }\n    }\n    const other = tokens.splice(split, tokens.length - split);\n    this.decl(other);\n  }\n\n
checkMissedSemicolon() {}\n\n  endFile() {\n    if (this.current.nodes && this.current.nodes.length) {\n
this.current.raws.semicolon = this.semicolon;\n    }\n    this.current.raws.after = (this.current.raws.after || '') +
this.spaces;\n\n    while (this.current.parent) {\n      this.current = this.current.parent;\n      this.current.raws.after =
'';\n    }\n  }\n}\n","//
 @flow\nimport Input from '../postcss/input';\n\nimport SafeParser from './safe-parser';\n\nexport default function
safeParse(css, opts) {\n  const input = new Input(css, opts);\n\n  const parser = new SafeParser(input);\n
parser.tokenize();\n  parser.loop();\n\n  return parser.root;\n}\n","// @flow\n/* eslint-disable import/no-unresolved
*/\nimport transformDeclPairs from 'css-to-react-native';\n\nimport generateComponentId from
'../utils/generateComponentId';\nimport type { RuleSet, StyleSheet } from '../types';\nimport flatten from
'../utils/flatten';\n// $FlowFixMe\nimport parse from '../vendor/postcss-safe-parser/parse';\n\nlet generated =
{};\n\nexport const resetStyleCache = () => {\n  generated = {};\n};\n\n/*\n InlineStyle takes arbitrary CSS and
generates a flat object\n */\nexport default (styleSheet: StyleSheet) => {\n  class InlineStyle {\n    rules: RuleSet;\n\n
  constructor(rules: RuleSet) {\n      this.rules = rules;\n    }\n\n    generateStyleObject(executionContext:
 Object) {\n      const flatCSS = flatten(this.rules, executionContext).join('');\n\n      const hash =
generateComponentId(flatCSS);\n      if (!generated[hash]) {\n        const root = parse(flatCSS);\n        const
declPairs = [];\n        root.each(node => {\n          if (node.type === 'decl') {\n            declPairs.push([node.prop,
```

node.value]);\n } else if (process.env.NODE_ENV !== 'production' && node.type !== 'comment') {\n /* eslint-disable no-console */\n console.warn(`Node of type ${node.type} not supported as an inline style`);\n }\n });\n // RN currently does not support differing values for the corner radii of Image\n // components (but does for View). It is almost impossible to tell whether we'll have\n // support, so we'll just disable multiple values here.\n // https://github.com/styled-components/css-to-react-native/issues/11\n const styleObject = transformDeclPairs(declPairs, [\n 'borderRadius',\n 'borderWidth',\n 'borderColor',\n 'borderStyle',\n]);\n const styles = styleSheet.create({\n generated: styleObject,\n });\n generated[hash] = styles.generated;\n }\n return generated[hash];\n }\n }\n\n return InlineStyle;\n};\n","/* eslint-disable */\n/**\n mixin-deep; https://github.com/jonschlinkert/mixin-deep\n Inlined such that it will be consistently transpiled to an IE-compatible syntax.\n\n The MIT License (MIT)\n\n Copyright (c) 2014-present, Jon Schlinkert.\n\n Permission is hereby granted, free of charge, to any person obtaining a copy\n of this software and associated documentation files (the \"Software\"), to deal\n in the Software without restriction, including without limitation the rights\n to use, copy, modify, merge, publish, distribute, sublicense, and/or sell\n copies of the Software, and to permit persons to whom the Software is\n furnished to do
so, subject to the following conditions:\n\n The above copyright notice and this permission notice shall be included in\n all copies or substantial portions of the Software.\n\n THE SOFTWARE IS PROVIDED \"AS IS\", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR\n IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,\n FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE\n AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER\n LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,\n OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN\n THE SOFTWARE.\n*/\n\nconst isObject = val => {\n return (\n typeof val === 'function' || (typeof val === 'object' && val !== null && !Array.isArray(val))\n);\n};\n\nconst isValidKey = key => {\n return key !== '__proto__' && key !== 'constructor' && key !== 'prototype';\n};\n\nfunction mixin(target, val, key) {\n const obj = target[key];\n if
(isObject(val) && isObject(obj)) {\n mixinDeep(obj, val);\n } else {\n target[key] = val;\n }\n}\n\nexport default function mixinDeep(target, ...rest) {\n for (const obj of rest) {\n if (isObject(obj)) {\n for (const key in obj) {\n if (isValidKey(key)) {\n mixin(target, obj[key], key);\n }\n }\n }\n }\n\n return target;\n}\n","// @flow\nimport { EMPTY_OBJECT } from './empties';\n\ntype Props = {\n theme?: any,\n};\n\nexport default (props: Props, providedTheme: any, defaultProps: any = EMPTY_OBJECT) => {\n return (props.theme !== defaultProps.theme && props.theme) || providedTheme || defaultProps.theme;\n};\n","// @flow\nimport type { IStyledComponent } from '../types';\n\nexport default function isTag(target: $PropertyType<IStyledComponent, 'target'>): boolean %checks {\n return (\n typeof target === 'string' &&\n (process.env.NODE_ENV !== 'production'\n ? target.charAt(0) === target.charAt(0).toLowerCase()\n : true)\n
);\n}\n","// @flow\nimport type { IStyledComponent } from '../types';\nimport getComponentName from './getComponentName';\nimport isTag from './isTag';\n\nexport default function generateDisplayName(\n target: $PropertyType<IStyledComponent, 'target'>\n): string {\n return isTag(target) ? `styled.${target}` : `Styled(${getComponentName(target)})`;\n}\n","// @flow\nimport React, { useContext, useMemo, type Element, type Context } from 'react';\nimport throwStyledError from '../utils/error';\nimport isFunction from '../utils/isFunction';\n\nexport type Theme = { [key: string]: mixed };\n\ntype ThemeArgument = Theme | ((outerTheme?: Theme) => Theme);\n\ntype Props = {\n children?: Element<any>,\n theme: ThemeArgument,\n};\n\nexport const ThemeContext: Context<Theme | void> = React.createContext();\n\nexport const ThemeConsumer = ThemeContext.Consumer;\n\nfunction mergeTheme(theme: ThemeArgument, outerTheme?: Theme): Theme {\n if (!theme) {\n return throwStyledError(14);\n
}\n\n if (isFunction(theme)) {\n const mergedTheme = theme(outerTheme);\n\n if (\n process.env.NODE_ENV !== 'production' &&\n (mergedTheme === null || Array.isArray(mergedTheme) ||

```
typeof mergedTheme !== 'object')\n  ) {\n    return throwStyledError(7);\n  }\n\n  return mergedTheme;\n }\n\n
if (Array.isArray(theme) || typeof theme !== 'object') {\n  return throwStyledError(8);\n }\n\n return outerTheme ?
{ ...outerTheme, ...theme } : theme;\n}\n\n/**\n * Provide a theme to an entire react component tree via context\n
*/\nexport default function ThemeProvider(props: Props) {\n const outerTheme = useContext(ThemeContext);\n
const themeContext = useMemo(() => mergeTheme(props.theme, outerTheme), [\n  props.theme,\n
outerTheme,\n ]);\n\n if (!props.children) {\n  return null;\n }\n\n return <ThemeContext.Provider
value={themeContext}>{props.children}</ThemeContext.Provider>;\n}\n","// @flow\nimport React, {
createElement, Component } from 'react';\nimport
 hoist from 'hoist-non-react-statics';\nimport merge from '../utils/mixinDeep';\nimport determineTheme from
'../utils/determineTheme';\nimport { EMPTY_ARRAY, EMPTY_OBJECT } from '../utils/empties';\nimport
generateDisplayName from '../utils/generateDisplayName';\nimport isFunction from '../utils/isFunction';\nimport
isTag from '../utils/isTag';\nimport isStyledComponent from '../utils/isStyledComponent';\nimport {
ThemeConsumer } from './ThemeProvider';\n\nimport type { Theme } from './ThemeProvider';\nimport type { Attrs,
RuleSet, Target } from '../types';\n\n// NOTE: no hooks available for react-native yet;\n// if the user makes use of
ThemeProvider or StyleSheetManager things will break.\n\n// Validator defaults to true if not in HTML/DOM
env\nconst validAttr = () => true;\n\nclass StyledNativeComponent extends Component<*, *> {\n root:
?Object;\n\n attrs = {};\n\n render() {\n  return (\n   <ThemeConsumer>\n    {(theme?: Theme) => {\n
const {\n
   $as: transientAsProp,\n    as: renderAs,\n    forwardedComponent,\n    forwardedAs,\n
forwardedRef,\n    testID,\n    style = [],\n    ...props\n   } = this.props;\n\n    const {
defaultProps, target, shouldForwardProp } = forwardedComponent;\n    const elementToBeRendered =\n
this.attrs.$as || this.attrs.as || transientAsProp || renderAs || target;\n\n    const generatedStyles =
this.generateAndInjectStyles(\n    determineTheme(this.props, theme, defaultProps) || EMPTY_OBJECT,\n
  this.props\n    );\n\n    const isTargetTag = isTag(elementToBeRendered);\n    const computedProps =
this.attrs !== props ? { ...props, ...this.attrs } : props;\n    const propFilterFn = shouldForwardProp || (isTargetTag
&& validAttr);\n    const propsForElement = {};\n    let key;\n\n    for (key in computedProps) {\n
if (key[0] === '$' || key
 === 'as') continue;\n    else if (key === 'forwardedAs') {\n     propsForElement.as = props[key];\n
} else if (!propFilterFn || propFilterFn(key, validAttr)) {\n     // Don't pass through filtered tags through to
native elements\n     propsForElement[key] = computedProps[key];\n    }\n   }\n\n
propsForElement.style = typeof style === 'function' ?\n    (state) => {\n    return
[generatedStyles].concat(style(state))\n   }\n   : [generatedStyles].concat(style);\n
propsForElement.testID = testID || propsForElement.testID;\n\n    if (forwardedRef) propsForElement.ref =
forwardedRef;\n    if (forwardedAs) propsForElement.as = forwardedAs;\n\n    return
createElement(elementToBeRendered, propsForElement);\n   }}\n  </ThemeConsumer>\n  );\n }\n\n
buildExecutionContext(theme: ?Object, props: Object, attrs: Attrs) {\n  const context = { ...props, theme };\n\n
  if (!attrs.length) return context;\n\n  this.attrs = {};\n\n  attrs.forEach(attrDef => {\n   let resolvedAttrDef =
attrDef;\n   let attr;\n   let key;\n\n   if (isFunction(resolvedAttrDef)) {\n    resolvedAttrDef =
resolvedAttrDef(context);\n   }\n\n   /* eslint-disable guard-for-in */\n   for (key in resolvedAttrDef) {\n
attr = resolvedAttrDef[key];\n    this.attrs[key] = attr;\n    context[key] = attr;\n   }\n   /* eslint-enable */\n
});\n\n  return context;\n }\n\n generateAndInjectStyles(theme: any, props: any) {\n  const { inlineStyle } =
props.forwardedComponent;\n\n  const executionContext = this.buildExecutionContext(\n   theme,\n   props,\n
  props.forwardedComponent.attrs\n  );\n\n  return inlineStyle.generateStyleObject(executionContext);\n }\n\n
setNativeProps(nativeProps: Object) {\n  if (this.root !== undefined) {\n   // $FlowFixMe\n
this.root.setNativeProps(nativeProps);\n  }
 else if (process.env.NODE_ENV !== 'production') {\n   // eslint-disable-next-line no-console\n
console.warn(\n    'setNativeProps was called on a Styled Component wrapping a stateless functional
component.'\n   );\n  }\n }\n}\n\nexport default (InlineStyle: Function) => {\n const
```

createStyledNativeComponent = (target: Target, options: Object, rules: RuleSet) => {\n const {\n attrs = EMPTY_ARRAY,\n displayName = generateDisplayName(target),\n ParentComponent = StyledNativeComponent,\n } = options;\n\n const isClass = !isTag(target);\n const isTargetStyledComp = isStyledComponent(target);\n\n // $FlowFixMe\n const WrappedStyledNativeComponent = React.forwardRef((props, ref) => (\n <ParentComponent\n {...props}\n forwardedComponent={WrappedStyledNativeComponent}\n forwardedRef={ref}\n />\n));\n\n const finalAttrs =\n // $FlowFixMe\n isTargetStyledComp && target.attrs\n ? Array.prototype.concat(target.attrs,
attrs).filter(Boolean)\n : attrs;\n\n // eslint-disable-next-line prefer-destructuring\n let shouldForwardProp = options.shouldForwardProp;\n\n // $FlowFixMe\n if (isTargetStyledComp && target.shouldForwardProp) {\n if (shouldForwardProp) {\n // compose nested shouldForwardProp calls\n shouldForwardProp = (prop, filterFn, elementToBeCreated) =>\n // $FlowFixMe\n target.shouldForwardProp(prop, filterFn, elementToBeCreated) &&\n options.shouldForwardProp(prop, filterFn, elementToBeCreated);\n } else {\n // eslint-disable-next-line prefer-destructuring\n shouldForwardProp = target.shouldForwardProp;\n }\n }\n\n /**\n * forwardRef creates a new interim component, which we'll take advantage of\n * instead of extending ParentComponent to create _another_ interim class\n */\n\n // $FlowFixMe\n WrappedStyledNativeComponent.attrs = finalAttrs;\n\n WrappedStyledNativeComponent.displayName = displayName;\n\n // $FlowFixMe\n WrappedStyledNativeComponent.shouldForwardProp = shouldForwardProp;\n\n // $FlowFixMe\n WrappedStyledNativeComponent.inlineStyle = new InlineStyle(\n // $FlowFixMe\n isTargetStyledComp ? target.inlineStyle.rules.concat(rules) : rules\n);\n\n // $FlowFixMe\n WrappedStyledNativeComponent.styledComponentId = 'StyledNativeComponent';\n // $FlowFixMe\n WrappedStyledNativeComponent.target = isTargetStyledComp\n ? // $FlowFixMe\n target.target\n : target;\n // $FlowFixMe\n WrappedStyledNativeComponent.withComponent = function withComponent(tag: Target) {\n const { displayName: _, componentId: __, ...optionsToCopy } = options;\n const newOptions = {\n ...optionsToCopy,\n attrs: finalAttrs,\n ParentComponent,\n };\n\n return createStyledNativeComponent(tag, newOptions, rules);\n };\n\n // $FlowFixMe\n Object.defineProperty(WrappedStyledNativeComponent,
'defaultProps', {\n get() {\n return this._foldedDefaultProps;\n },\n\n set(obj) {\n // $FlowFixMe\n this._foldedDefaultProps = isTargetStyledComp ? merge({}, target.defaultProps, obj) : obj;\n },\n });\n\n if (isClass) {\n hoist(WrappedStyledNativeComponent, (target: any), {\n // all SC-specific things should not be hoisted\n attrs: true,\n displayName: true,\n shouldForwardProp: true,\n inlineStyle: true,\n styledComponentId: true,\n target: true,\n withComponent: true,\n });\n }\n\n return WrappedStyledNativeComponent;\n };\n\n return createStyledNativeComponent;\n};\n","// @flow\nimport type { Interpolation } from '../types';\n\nexport default (\n strings: Array<string>,\n interpolations: Array<Interpolation>\n): Array<Interpolation> => {\n const result = [strings[0]];\n\n for (let i = 0, len = interpolations.length; i < len;
i += 1) {\n result.push(interpolations[i], strings[i + 1]);\n }\n\n return result;\n};\n","// @flow\nimport interleave from '../utils/interleave';\nimport isPlainObject from '../utils/isPlainObject';\nimport { EMPTY_ARRAY } from '../utils/empties';\nimport isFunction from '../utils/isFunction';\nimport flatten from '../utils/flatten';\nimport type { Interpolation, RuleSet, Styles } from '../types';\n\n/**\n * Used when flattening object styles to determine if we should\n * expand an array of styles.\n */\nconst addTag = arg => {\n if (Array.isArray(arg)) {\n // eslint-disable-next-line no-param-reassign\n arg.isCss = true;\n }\n return arg;\n};\n\nexport default function css(styles: Styles, ...interpolations: Array<Interpolation>): RuleSet {\n if (isFunction(styles) || isPlainObject(styles)) {\n // $FlowFixMe\n return addTag(flatten(interleave(EMPTY_ARRAY, [styles, ...interpolations])));\n }\n\n if (interpolations.length === 0 && styles.length === 1 && typeof styles[0]
=== 'string') {\n // $FlowFixMe\n return styles;\n }\n\n // $FlowFixMe\n return addTag(flatten(interleave(styles, interpolations)));\n}\n","// @flow\nimport { isValidElementType } from 'react-is';\nimport css from './css';\nimport throwStyledError from '../utils/error';\nimport { EMPTY_OBJECT } from

'../utils/empties';\n\nimport type { Target } from '../types';\n\nexport default function constructWithOptions(\n componentConstructor: Function,\n tag: Target,\n options: Object = EMPTY_OBJECT\n) {\n if (!isValidElementType(tag)) {\n return throwStyledError(1, String(tag));\n }\n\n /* This is callable directly as a template function */\n // $FlowFixMe: Not typed to avoid destructuring arguments\n const templateFunction = (...args) => componentConstructor(tag, options, css(...args));\n\n /* If config methods are called, wrap up a new template function and merge options */\n templateFunction.withConfig = config =>\n constructWithOptions(componentConstructor,
tag, { ...options, ...config });\n\n /* Modify/inject new props at runtime */\n templateFunction.attrs = attrs =>\n constructWithOptions(componentConstructor, tag, {\n ...options,\n attrs: Array.prototype.concat(options.attrs, attrs).filter(Boolean),\n });\n\n return templateFunction;\n}\n","// @flow\nimport React, { useContext, type AbstractComponent } from 'react';\nimport hoistStatics from 'hoist-non-react-statics';\nimport { ThemeContext } from '../models/ThemeProvider';\nimport determineTheme from '../utils/determineTheme';\nimport getComponentName from '../utils/getComponentName';\n\n// NOTE: this would be the correct signature:\n// export default <Config: { theme?: any }, Instance>(\n// Component: AbstractComponent<Config, Instance>\n//): AbstractComponent<$Diff<Config, { theme?: any }> & { theme?: any }, Instance>\n//\n// but the old build system tooling doesn't support the syntax\n\nexport default (Component: AbstractComponent<*, *>) => {\n // $FlowFixMe
This should be React.forwardRef<Config, Instance>\n const WithTheme = React.forwardRef((props, ref) => {\n const theme = useContext(ThemeContext);\n // $FlowFixMe defaultProps isn't declared so it can be inferrable\n const { defaultProps } = Component;\n const themeProp = determineTheme(props, theme, defaultProps);\n\n if (process.env.NODE_ENV !== 'production' && themeProp === undefined) {\n // eslint-disable-next-line no-console\n console.warn(\n `[withTheme] You are not using a ThemeProvider nor passing a theme prop or a theme in defaultProps in component class \"${getComponentName(\n Component\n )}\"`\n);\n }\n\n return <Component {...props} theme={themeProp} ref={ref} />;\n });\n\n hoistStatics(WithTheme, Component);\n\n WithTheme.displayName = `WithTheme(${getComponentName(Component)})`;\n\n return WithTheme;\n};\n","// @flow\nimport { useContext } from 'react';\nimport { ThemeContext } from '../models/ThemeProvider';\n\nconst
useTheme = () => useContext(ThemeContext);\n\nexport default useTheme;\n","// @flow\n\n/* eslint-disable import/no-unresolved */\nimport _InlineStyle from '../models/InlineStyle';\nimport _StyledNativeComponent from '../models/StyledNativeComponent';\n\nimport css from '../constructors/css';\nimport constructWithOptions from '../constructors/constructWithOptions';\nimport ThemeProvider, { ThemeConsumer, ThemeContext } from '../models/ThemeProvider';\nimport withTheme from '../hoc/withTheme';\nimport useTheme from '../hooks/useTheme';\nimport isStyledComponent from '../utils/isStyledComponent';\n\nimport type { Target } from '../types';\n\nconst reactNative = require('react-native');\n\nconst InlineStyle = _InlineStyle(reactNative.StyleSheet);\nconst StyledNativeComponent = _StyledNativeComponent(InlineStyle);\nconst styled = (tag: Target) => constructWithOptions(StyledNativeComponent, tag);\n\n/* React native lazy-requires each of these modules for some reason, so let's\n *
assume it's for a good reason and not eagerly load them all */\nconst aliases = `ActivityIndicator ActivityIndicatorIOS ART Button DatePickerIOS DrawerLayoutAndroid\n Image ImageBackground ImageEditor ImageStore KeyboardAvoidingView ListView MapView Modal NavigatorIOS\n Picker PickerIOS ProgressBarAndroid ProgressViewIOS ScrollView SegmentedControlIOS Slider\n SliderIOS SnapshotViewIOS Switch RecyclerViewBackedScrollView RefreshControl SafeAreaView StatusBar\n SwipeableListView SwitchAndroid SwitchIOS TabBarIOS Text TextInput ToastAndroid ToolbarAndroid\n Touchable TouchableHighlight TouchableNativeFeedback TouchableOpacity TouchableWithoutFeedback\n View ViewPagerAndroid WebView FlatList SectionList VirtualizedList Pressable`;\n\n/* Define a getter for each alias which simply gets the reactNative component\n * and passes it to styled */\naliases.split(/\\s+/m).forEach(alias =>\n Object.defineProperty(styled, alias, {\n enumerable: true,\n configurable: false,\n get() {\n

return styled(reactNative[alias]);\n   },\n })\n);\n\nexport { css, isStyledComponent, ThemeProvider, ThemeConsumer, ThemeContext, withTheme, useTheme };\nexport default styled;\n"],"names":["AD_REPLACER_R","charsLength","getAlphabeticChar","code","String","fromCharCode","generateAlphabeticName","name","x","Math","abs","replace","SEED","phash","h","i","length","charCodeAt","hash","str","getComponentName","target","process","env","NODE_ENV","displayName","isFunction","test","isStatelessFunction","prototype","isReactComponent","toString","Object","call","typeOf","isStyledComponent","styledComponentId","SC_ATTR","REACT_APP_SC_ATTR","SC_ATTR_ACTIVE","SC_ATTR_VERSION","SC_VERSION","__VERSION__","SPLITTER","IS_BROWSER","window","DISABLE_SPEEDY","Boolean","SC_DISABLE_SPEEDY","REACT_APP_SC_DISABLE_SPEEDY","EMPTY_ARRAY","freeze","EMPTY_OBJECT","ERRORS","errorMap","format","a","b","c","len","push","forEach","d","throwStyledComponentsError","interpolations","Error","join","trim","makeGroupedTag","tag","DefaultGroupedTag","BASE_SIZE","groupSizes","Uint32Array","indexOfGroup","group","index","insertRules","rules","oldBuffer","oldSize","newSize","throwStyledError","set","ruleIndex","l","insertRule","clearGroup","startIndex","endIndex","deleteRule","getGroup","css","getRule","MAX_SMI","groupIDRegister","Map","reverseRegister","nextFreeGroup","getGroupForId","id","has","get","getIdForGroup","setGroupForId","SELECTOR","MARKER_RE","RegExp","outputSheet","sheet","getTag","undefined","names","size","selector","content","rehydrateNamesFromContent","split","registerName","rehydrateSheetFromTag","style","parts","textContent","part","marker","match","parseInt","rehydrateSheet","nodes","document","querySelectorAll","node","getAttribute","parentNode","removeChild","getNonce","__webpack_nonce__","ELEMENT_TYPE","findLastStyleTag","childNodes","child","nodeType","hasAttribute","makeStyleTag","head","parent","createElement","prevStyle","nextSibling","setAttribute","nonce","insertBefore","getSheet","styleSheets","ownerNode","makeTag","isServer","useCSSOMInjection","VirtualTag","CSSOMTag","TextTag","element","appendChild","createTextNode","rule","_error","cssRules","cssText","refNode","_target","splice","SHOULD_REHYDRATE","defaultOptions","StyleSheet","registerId","options","globalStyles","gs","server","reconstructWithOptions","withNames","allocateGSInstance","hasNameForId","groupNames","Set","add","clearNames","clear","clearRules","clearTag","delimiter","needle","toSheet","block","e","ruleSheet","context","selectors","parents","line","column","ns","depth","at","COMMENT_REGEX","COMPLEX_SELECTOR_PREFIX","createStylisInstance","plugins","stylis","Stylis","parsingRules","returnRulesPlugin","parsedRules","parseRulesPlugin","insertRulePlugin","_componentId","_selector","_selectorRegexp","_consecutiveSelfRefRegExp","selfReferenceReplacer","offset","string","indexOf","selfReferenceReplacementPlugin","_","lastIndexOf","use","stringifyRules","prefix","componentId","flatCSS","cssStr","reduce","acc","plugin","StyleSheetContext","React","createContext","StyleSheetConsumer","Consumer","StylisContext","StylisConsumer","masterSheet","masterStylis","Keyframes","inject","styleSheet","stylisInstance","resolvedName","getName","uppercaseCheck","uppercasePattern","msPattern","prefixAndLowerCase","char","toLowerCase","hyphenateStyleName","addUnitIfNeeded","value","unitless","startsWith","isFalsish","chunk","objToCssArray","obj","prevKey","key","hasOwnProperty","Array","isArray","isCss","hyphenate","isPlainObject","flatten","executionContext","ruleSet","result","isElement","console","warn","printed","warnOnce","message","SINGLE_QUOTE","DOUBLE_QUOTE","BACKSLASH","SLASH","NEWLINE","SPACE","FEED","TAB","CR","OPEN_SQUARE","CLOSE_SQUARE","OPEN_PARENTHESES","CLOSE_PARENTHESES","OPEN_CURLY","CLOSE_CURLY","SEMICOLON","ASTERISK","COLON","AT","RE_AT_END","RE_WORD_END","RE_BAD_BRACKET","tokenize","input","tokens","valueOf","ignore","ignoreErrors","next","quote","lines","last","escape","nextLine","nextOffset","escaped","escapePos","prev","n","pos","unclosed","what","error","slice","lastIndex","HIGHLIGHT_THEME","brackets","comment","color","terminalHighlight","Input","token","map","CssSyntaxError","source","file","reason","setMessage","captureStackTrace","showSourceCode","supportsColor","start","max","end","min","maxWidth","number","padded","gutter","spacing","defaultRaw","colon","indent","beforeDecl","beforeRule","beforeOpen","beforeClose","beforeComment","after","emptyBody","commentLeft","commentRight","capitalize","toUpperCase","Stringifier","builder","stringify","semicolon","type","root","body","raws","left","raw","right","text","decl","between","prop","rawValue","important","atrule","params","afterName","before","own","detect","first","rawCache","beforeAfter","method","walk","rawSemicolon","rawEmptyBody","rawIndent","p","rawBeforeComment","walkComments","rawBeforeDecl","walkDecls","rawBeforeRule","rawBeforeClose","rawBeforeOpen","rawColon","buf","step","cloneNode","cloned","construc

tor","j","Node","defaults","opts","positionBy","data","remove","stringifier","clone","overrides","cloneBefore","clon
eAfter","insertAfter","replaceWith","moveTo","newParent","cleanRaws","append","moveBefore","otherNode","mo
veAfter","toJSON","fixed","defaultType","keepBetween","positionInside","word","removeSelf","cleanStyles","val"
,"Declaration","Comment","Parser","Root","current","spaces","tokenizer","loop","emptyRule","other","endFile","in
it","Rule","bracket","pop","unclosedBracket","unknownWord","spacesFromEnd","shift","spacesFromStart","preche
ckMissedSemicolon","stringFrom","cache","checkMissedSemicolon","AtRule","unnamedAtrule","open","unexpect
edClose","unclosedBlock","clean","all","lastTokenType","from","doubleColon","founded","parse","safe","parser","
cleanSource","Container","each","callback","lastEach","indexes","walkRules","walkAtRules","children","normalize
","prepend","reverse","unshift","exist","removeAll","replaceValues","pattern","props","fast","every","condition","s
ome","sample","processed","rebuild","fix","eachInside","eachDecl","eachRule","eachAtRule","eachComment","list
","separators","array","func","letter","space","comma","values","sep","Warning","opt","Result","processor","messa
ges","lastPlugin","postcssPlugin","warning","warnings","filter","isPromise","then","LazyResult","stringified","inlin
e","syntax","sync","onFulfilled","onRejected","async","handleError","postcssVersion","pluginName","pluginVer","
runtimeVer","version","err","asyncTick","resolve","reject","promise","run","Promise","processing","Processor","co
ncat","normalized","postcss","toResult","lazy","prevMap","sequence","path","origin","consumer","originalPosition
For","mapResolve","sourceContentFor","sourceRoot","SafeParser","buffer","safeParse","generated","InlineStyle","
generateStyleObject","generateComponentId","declPairs","styleObject","transformDeclPairs","styles","create","isO
bject","isValidKey","mixin","mixinDeep","rest","providedTheme","defaultProps","theme","isTag","charAt","gener
ateDisplayName","ThemeContext","ThemeConsumer","mergeTheme","outerTheme","mergedTheme","ThemePrivi
der","useContext","themeContext","useMemo","validAttr","StyledNativeComponent","attrs","render","transientAsP
rop","$as","renderAs","as","forwardedComponent","forwardedAs","forwardedRef","testID","shouldForwardProp","
elementToBeRendered","generatedStyles","generateAndInjectStyles","determineTheme","isTargetTag","computed
Props","propFilterFn","propsForElement","state","ref","buildExecutionContext","attrDef","resolvedAttrDef","attr","
inlineStyle","setNativeProps","nativeProps","Component","createStyledNativeComponent","ParentComponent","is
Class","isTargetStyledComp","WrappedStyledNativeComponent","forwardRef","finalAttrs","filterFn","elementToB
eCreated","withComponent","__","optionsToCopy","newOptions","defineProperty","_foldedDefaultProps","merge"
,"hoist","strings","addTag","arg","interleave","constructWithOptions","componentConstructor","isValidElementTyp
e","templateFunction","withConfig","config","WithTheme","themeProp","hoistStatics","useTheme","reactNative","
require","_InlineStyle","_StyledNativeComponent","styled","aliases","alias","enumerable","configurable"],"mappin
gs":";;;;;;;;;;;;;;;;AAAA;;AACA;AAEA,IAAMA,aAAa,GAAG,UAAtB;AAEA;;;AAEA,IAAMC,WAAW,GAAG,EAApB;AAEA;;;AAEA,IAAMC,iBAAiB,GAAG,SAApBA,iBAAoB,CAAUC,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBC,MAA1B;AAAA,CAA1C;;AAEA,IAAMC,cAAc,GAAG,SAAjBA,cAAiB,CAAUH,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBG,GAA1B;AAAA,CAAvC;;AAEA,IAAMC,eAAe,GAAG,SAAlBA,eAAkB,CAAUL,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBK,IAA1B;AAAA,CAAxC;;AAEA,IAAMC,eAAe,GAAG,SAAlBA,eAAkB,CAAUP,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBO,IAA1B;AAAA,CAAxC;;AAEA,IAAMC,gBAAgB,GAAG,SAAnBA,gBAAmB,CAAUT,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBS,KAA1B;AAAA,CAAzC;;AAEA,IAAMC,gBAAgB,GAAG,SAAnBA,gBAAmB,CAAUX,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBW,KAA1B;AAAA,CAAzC;;AAEA,IAAMC,iBAAiB,GAAG,SAApBA,iBAAoB,CAAUb,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBa,MAA1B;AAAA,CAA1C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUf,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBe,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjB,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiB,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnB,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmB,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrB,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqB,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvB,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuB,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzB,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByB,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3B,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2B,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7B,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6B,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/B,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+B,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjC,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiC,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnC,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmC,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrC,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqC,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvC,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuC,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzC,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByC,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3C,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2C,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7C,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6C,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/C,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+C,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjD,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiD,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnD,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmD,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrD,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqD,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvD,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuD,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzD,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByD,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3D,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2D,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7D,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6D,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/D,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+D,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjE,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiE,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnE,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmE,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrE,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqE,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvE,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuE,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzE,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByE,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3E,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2E,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7E,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6E,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/E,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+E,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjF,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiF,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnF,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmF,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrF,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqF,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvF,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuF,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzF,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByF,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3F,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2F,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7F,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6F,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/F,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+F,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjG,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiG,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnG,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmG,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrG,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqG,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvG,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuG,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzG,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByG,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3G,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2G,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7G,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6G,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/G,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+G,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjH,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiH,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnH,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmH,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrH,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqH,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvH,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuH,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzH,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByH,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3H,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2H,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7H,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6H,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/H,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+H,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjI,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiI,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnI,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmI,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrI,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqI,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvI,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuI,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzI,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByI,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3I,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2I,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7I,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6I,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/I,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+I,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjJ,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiJ,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnJ,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmJ,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrJ,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqJ,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvJ,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuJ,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzJ,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByJ,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3J,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2J,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7J,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6J,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/J,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+J,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjK,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiK,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnK,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmK,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrK,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqK,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvK,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuK,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzK,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByK,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3K,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2K,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7K,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6K,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/K,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+K,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjL,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiL,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnL,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmL,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrL,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqL,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvL,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuL,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzL,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByL,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3L,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2L,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7L,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6L,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/L,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+L,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjM,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiM,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnM,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmM,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrM,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqM,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvM,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuM,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzM,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByM,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3M,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2M,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7M,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6M,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/M,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+M,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjN,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiN,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnN,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmN,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrN,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqN,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvN,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuN,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzN,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByN,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3N,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2N,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7N,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6N,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/N,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+N,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjO,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiO,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnO,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmO,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrO,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqO,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvO,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuO,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzO,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByO,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3O,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2O,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7O,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6O,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/O,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+O,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjP,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiP,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnP,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmP,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrP,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqP,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvP,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuP,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzP,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByP,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3P,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2P,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7P,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6P,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/P,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+P,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjQ,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiQ,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUnQ,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBmQ,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUrQ,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBqQ,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUvQ,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBuQ,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUzQ,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqByQ,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU3Q,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB2Q,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU7Q,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB6Q,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAU/Q,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqB+Q,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kBAAqB,CAAUjR,IAAV,EAAgB;AAAA,SAAKA,IAAI,CAACC,WAAL,KAAqBiR,OAA1B;AAAA,CAA3C;;AAEA,IAAMC,kBAAkB,GAAG,SAArBA,kB

SC,mBAAT,CAA6BD,IAA7B,EAAiD;AAC9D,SACE,OAAOA,IAAP,KAAgB,UAAhB,IACG,EACDA,IAAI,CA
ACE,SAAL,IACGF,IAAI,CAACE,SAAL,CAAeC,gBAFjB,CAFL;AAOD;;ACTD;AACA,AAEA,qBAAe,UAACt
B,CAAD;AAAA,SACbA,CAAC,KAAK,IAAN,IACA,OAAOA,CAAP,KAAaA,QADb,IAEA,CAACA,CAAC,CAA
CuB,QAAF,GAAavB,CAAC,CACCuB,QAAF,EAAb,GAA4BC,MAAM,CAACH,SAAP,CAAiBE,QAAjB,5C,EAAE0
BE,IAA1B,CAA+BzB,CAA/B,CAA7B,MAAoE,iBAFpE,IAGA,CAAC0B,cAAM,CAAC1B,CAAD,CAAD,CAAK,cAAM
,CAAf;;ACHA;AACA,AAAe,SAAS2B,iBAAT,CAA2B,EAAAyD;AACtE,AAAO,MAAM,CAACE,
A,MAAM,CAACe,iBAAP,CAAyB,EAAAC,QAAzB,CAAb,CAAA;;;

AAhB;AACD;AACF;;AAED,WAAKH,UAAL,GAAkB,IAAIC,WAAJ,CAAgBQ,OAAhB,CAAlB;AACA,WAAKT,UAAL,CAAgBW,GAAhB,CAAoBJ,SAApB;AACA,WAAK/D,MAAL,GAAciE,OAAd;;AAEA,WAAK,IAAIlE,CAAC,GAAGiE,OAAb,EAAsBjE,CAAC,GAAGkE,OAA1B,EAAmClE,CAAC,EAApC,EAAwC;AACtC,aAAKyD,UAAL,CAAgBzD,CAAhB,IAAqB;AACnB,cAAIqE,SAAJ,CAAcrE,CAAd,EAAiBA,CAAC,GAAG,CAArB;AACD;AACF;;AAED,QAAIqE,SAAS,GAAGC,MAAM,CAACC,MAAP,CAAcC,WAAW,CAACC,SAA1B,CAAhB;AACAJ,IAAAA,SAAS,CAACK,WAAV,GAAwBF,WAAxB;AACAH,IAAAA,SAAS,CAACM,KAAV,GAAkB,SAASA,KAAT,CAAeC,KAAf,EAAsBC,GAAtB,EAA2B;AAC3C,UAAIC,KAAK,GAAG,KAAKC,MAAjB;AACA,UAAIC,IAAI,GAAGJ,KAAK,GAAG,CAAnB;AACA,UAAIK,GAAG,GAAGJ,GAAG,KAAKK,SAAR,GAAoBH,KAApB,GAA4BF,GAAG,GAAG,CAA5C;;AAEA,UAAIG,IAAI,GAAG,CAAX,EAAc;AACZA,QAAAA,IAAI,IAAIF,KAAR;AACA,YAAIE,IAAI,GAAG,CAAX,EAAcA,IAAI,GAAG,CAAP;AACf;;AAED,UAAIC,GAAG,GAAG,CAAV,EAAa;AACXA,QAAAA,GAAG,IAAIH,KAAP;AACA,YAAIG,GAAG,GAAG,CAAV,EAAaA,GAAG,GAAG,CAAN;AACd;;AAED,UAAIA,GAAG,GAAGD,IAAV,EAAgB;AACdC,QAAAA,GAAG,GAAGD,IAAN;AACD;;AAED,UAAIG,MAAM,GAAGF,GAAG,GAAGD,IAAnB;AACA,UAAIG,MAAM,GAAG,CAAb,EAAgBA,MAAM,GAAG,CAAT;AAChB,UAAIC,MAAM,GAAG,IAAIC,KAAJ,CAAUF,MAAV,CAAb;;AAEA,WAAK,IAAIG,CAAC,GAAG,CAAb,EAAgBA,CAAC,GAAGH,MAAM,GAAG,CAA7B,EAAgCG,CAAC,EAAjC,EAAqC;AACnCF,QAAAA,MAAM,CAACE,CAAD,CAAN,GAAY,KAAKC,MAAL,CAAYL,IAAI,GAAGI,CAAnB,CAAZ;AACD;;AAED,aAAOF,MAAP;AACD,KA1BD;;AA4BA,QAAII,SAAS,GAAGC,MAAM,CAACC,MAAP,CAAcC,WAAW,CAACC,SAA1B,CAAhB;AACAJ,IAAAA,SAAS,CAACK,WAAV,GAAwBF,WAAxB;AACAH,IAAAA,SAAS,CAACM,KAAV,GAAkB,SAASA,KAAT,CAAeC,KAAf,EAAsBC,GAAtB,EAA2B;AAC3C,UAAIC,KAAK,GAAG,KAAKC,MAAjB;AACA,UAAIC,IAAI,GAAGJ,KAAK,GAAG,CAAnB;AACA,UAAIK,GAAG,GAAGJ,GAAG,KAAKK,SAAR,GAAoBH,KAApB,GAA4BF,GAAG,GAAG,CAA5C;;AAEA,UAAIG,IAAI,GAAG,CAAX,EAAc;AACZA,QAAAA,IAAI,IAAIF,KAAR;AACA,YAAIE,IAAI,GAAG,CAAX,EAAcA,IAAI,GAAG,CAAP;AACf;;AAED,UAAIC,GAAG,GAAG,CAAV,EAAa;AACXA,QAAAA,GAAG,IAAIH,KAAP;AACA,YAAIG,GAAG,GAAG,CAAV,EAAaA,GAAG,GAAG,CAAN;AACd;;AAED,UAAIA,GAAG,GAAGD,IAAV,EAAgB;AACdC,QAAAA,GAAG,GAAGD,IAAN;AACD;;AAED,UAAIG,MAAM,GAAGF,GAAG,GAAGD,IAAnB;AACA,UAAIG,MAAM,GAAG,CAAb,EAAgBA,MAAM,GAAG,CAAT;AAChB,UAAIC,MAAM,GAAG,IAAIC,KAAJ,CAAUF,MAAV,CAAb;;AAEA,WAAK,IAAIG,CAAC,GAAG,CAAb,EAAgBA,CAAC,GAAGH,MAAM,GAAG,CAA7B,EAAgCG,CAAC,EAAjC,EAAqC;AACnCF,QAAAA,MAAM,CAACE,CAAD,CAAN,GAAY,KAAKC,MAAL,CAAYL,IAAI,GAAGI,CAAnB,CAAZ;AACD;;AAED,aAAOF,MAAP;AACD,KA1BD;;AA4BA,QAAII,SAAS,GAAGC,MAAM,CAACC,MAAP,CAAcC,WAAW,CAACC,SAA1B,CAAhB;AACAJ,IAAAA,SAAS,CAACK,WAAV,GAAwBF,WAAxB;AACAH,IAAAA,SAAS,CAACM,KAAV,GAAkB,SAASA,KAAT,CAAeC,KAAf,EAAsBC,GAAtB,EAA2B;AAC3C,UAAIC,KAAK,GAAG,KAAKC,MAAjB;AACA,UAAIC,IAAI,GAAGJ,KAAK,GAAG,CAAnB;AACA,UAAIK,GAAG,GAAGJ,GAAG,KAAKK,SAAR,GAoBAH,KApBA,GAoBQF,GAAG,GAAG,CApBxB;;AAsB

P,KAAD,EAAeT,EAAf,EAA2Be,OAA3B,EAA+C;AAC/E,MAAMH,KAAK,GAAGG,OAAO,CAACE,KAAR,CA
Ac,GAAd,CAAd;AACA,MAAI9G,IAAJ;;AAEA,OAAK,IAAIQ,CAAC,GAAG,CAAR,EAAWsE,CAAC,GAAG2
B,KAAK,CAAChG,MAA1B,EAAkCD,CAAC,GAAGsE,CAAtC,EAAyCtE,CAAC,EAA1C,EAA8C;AAC5C;AAC
A,QAAKR,IAAI,GAAGyG,KAAK,CAACjG,CAAD,CAAjB,EAAuBsE;AACrB8F,MAAAA,KAAK,CAACS,YAN
,CAAmBlB,EAAnB,EAAuB7F,IAAvB;AACD;AACF;AACF,CAVD;;AAYA,IAAMgH,qBAAqB,GAAG,SAAxB
A,qBAAwB,CACV,KAAD,EAAeW,KAAf,EAA2C;AACvE,MAAMC,MAAM,GAAGC,KAAK,CAACC,IAAN,CAAW
WAAN,EAAmB,UAAAC,IAAI;AAAA,WAAIA,IAAI,CAACC,IAAL,CAAU,GAAV,CAAJ;AAAA,GAAvB,CAAf;
QAAQ,CAACF,MAAM,CAACG,MAAP,GAAgB,CAAjB,GAAqBH,MAAM,CAACI,IAAP,CAAY,IAAZ,CAArB,GAAyC
AAD,CAAC,CAAD,CAAP,CAAW,CAAX,CAAa,CAAb,CAAe,CAAf,CAAiB,CAAjB,CAAmB,CAAnB,CAAqB,CAArB,CAAuB,CAAvB,CAAyB,CAAzB,CAA2B,CAA3B,CAA6B,CAA7B,CAA+B,CA

,UAAJ,CAAezI,MAAf,CAAP;AACD,GAFD,MAEO,IAAIwI,iBAAJ,EAAuB;AAC5B,WAAO,IAAIE,QAAJ,CAAA
a1I,MAAb,CAAP;AACD,GAFM,MAEA;AACL,WAAO,IAAI2I,OAAJ,CAAY3I,MAAZ,CAAP;AACD;AACF,C
ARM;AAUP,IAAa0I,QAAb;AAOE,oBAAY1I,MAAZ,EAAkC;AAChC,QAAM4I,OAAO,GAAI,KAAKA,OAAL,
GAAelB,YAAY,CAAC1H,MAAD,CAA5C,CADgC;;AAIhC4I,IAAAA,OAAO,CAACC,WAAR,CAAoBC,EAAAA
Q,CAACkC,cAAT,CAAwB,EAAxB,CAApB;AAEA,SAAKtD,KAAL,GAAa2C,OAAO,CAACS,cAAR,CAAuBC,EAAAA,CA
ACA,SAAKjJ,MAAL,GAAc,CAAd;AACD;;AAfH;;AAAA,SAAiBE,IAAjBF,EAAuB,UAAjBF,BF,GAAiBE,IAAjBF,
F,IAA1B,EAAiD;AAC/C,SAAKoJ,KAAL,CAAWlJ,IAAX,IAAmB,KAAKmJ,KAAL,CAAWnJ,IAAX,CAAnB;AACD;
B;AACA,WAAK5D,MAAL;AACA,aAAO,IAAP;AACD;;AAED,KAAJ,EAAW,SAAXgN,GAAW,GAAG;AAAE,aAAO,KAAKC,IAAZ;AAAkB,KAAlC;;AAAA,SAAWD,GAAX,CAAgBE,KAAhB,EAAuB;AACrB,UAAMC,QAAQ,GAAGD,KAAK,GAAG,CAAzB;AACA,UAAIE,KAAK,GAAG,KAAKH,IAAjB;AACA,UAAII,KAAK,GAAG,KAAKC,KAAjB;AACA,UAAIC,IAAI,GAAG,KAAKC,IAAhB;AACA,UAAIC

AED;;;SACAO,eAAA,sBAAalF,EAAb,EAAyB7F,IAAzB,EAAgD;AAC9C,WAAO,KAAKyG,KAAL,CAAWX,GAAX,CAAeD,EAAf,KAAuB,KAAKY,KAAL,CAAWV,GAAX,CAAeF,EAAf,CAAD,CAA0BC,GAA1B,CAA8B9F,IAA9B,CAA7B;AACD;AAED;;;SACA+G,eAAA,sBAAalB,EAAAb,EAAyB7F,IAAzB,EAAuC;AACrC4F,IAAAA,aAAAa,QAAAA,EAAAA,CAAAA,EAAAA,CAAAA,EAAAA,C

O,GAAG1I,GAAG,CAACjF,OAAJ,CAAYiM,aAAZ,EAA2B,EAA3B,CAAhB;AACA,QAAM2B,MAAM,GAAGrH,QAAQ,IAAIkH,MAAAZ,GAAAwBA,MAAAxB,SAAAkClH,QAAAlC,WAAAgDoH,OAAAhD,UAA8DA,OAA7E,CAF6E;AAK7E;AACA;;AACAf,IAAAAA,YAAAY,GAAAGc,WAAAf;AACAb,IAAAAA,SAAAS,GAAAGtG,QAAAZ;AACAuG,IAAAAA,eAAAe,GAAAG,IAAAI9G,MAAAJ,QAAAgB6G,UAAAgC,GAAAhC,CAAAlB;AACAE,IAAAAA,yBAAAyB,GAAAGG,IAAAI/G,MAAAJ,SAAAiB6G,SAAAjB,cAAA5B;AAEA,WAAAOR,MAAM,CAAAC,cAAAH,CAAAlB,QAAAlC,WAAAgDoH,OAAAhD,UAAA8DA,OAAA7E

Fa,EAGb5B,UAHa,EAIbC,cAJa,EAKR;AACL,MAAIqB,KAAK,CAACC,OAAN,CAAcP,KAAd,CAAJ,EAA0B;AACxB,QAAMa,OAAO,GAAG,EAAhB;;AAEA,SAAK,IAAIpQ,CAAC,GAAG,CAAR,EAAWqQ,GAAG,GAAGd,KAAK,CAACtP,MAAN,GAAe,CAAjC,EAAoCD,CAAC,GAAGqQ,GAAxC,EAA6CrQ,CAAC,EAA9C,EAAkD;AAChDmQ,MAAAA,OAAO,CAACnQ,CAAD,CAAP,GAAa,IAAb;AACD;;AAED,WAAOmQ,OAAP;AACD;;AAED,MAAIG,SAAS,GAAG,CAAhB;;AAEA,OAAK,IAAIC,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFH,MAAAA,SAAS,GAAGA,SAAS,GAAGE,MAAM,CAACC,MAA/B;AACD;AACF;;AAED,SAAOH,SAAP;AACD;;AAED,SAASI,eAAT,CAAyBnB,KAAzB,EAAgC;AAC9B,MAAIoB,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIJ,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFE,MAAAA,KAAK,GAAGA,KAAK,GAAGH,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOE,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBrB,KAAzB,EAAgC;AAC9B,MAAIsB,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIN,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFI,MAAAA,KAAK,GAAGA,KAAK,GAAGL,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOI,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBvB,KAAzB,EAAgC;AAC9B,MAAIwB,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIR,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFM,MAAAA,KAAK,GAAGA,KAAK,GAAGP,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOM,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBzB,KAAzB,EAAgC;AAC9B,MAAI0B,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIV,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFQ,MAAAA,KAAK,GAAGA,KAAK,GAAGT,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOQ,KAAP;AACD;;AAED,SAASC,eAAT,CAAyB3B,KAAzB,EAAgC;AAC9B,MAAI4B,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIZ,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFU,MAAAA,KAAK,GAAGA,KAAK,GAAGX,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOU,KAAP;AACD;;AAED,SAASC,eAAT,CAAyB7B,KAAzB,EAAgC;AAC9B,MAAI8B,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAId,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFY,MAAAA,KAAK,GAAGA,KAAK,GAAGb,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOY,KAAP;AACD;;AAED,SAASC,eAAT,CAAyB/B,KAAzB,EAAgC;AAC9B,MAAIgC,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIhB,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFc,MAAAA,KAAK,GAAGA,KAAK,GAAGf,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOc,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBjC,KAAzB,EAAgC;AAC9B,MAAIkC,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIlB,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFgB,MAAAA,KAAK,GAAGA,KAAK,GAAGjB,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOgB,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBnC,KAAzB,EAAgC;AAC9B,MAAIoC,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIpB,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFkB,MAAAA,KAAK,GAAGA,KAAK,GAAGnB,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOkB,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBrC,KAAzB,EAAgC;AAC9B,MAAIsC,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAItB,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFoB,MAAAA,KAAK,GAAGA,KAAK,GAAGrB,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOoB,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBvC,KAAzB,EAAgC;AAC9B,MAAIwC,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIxB,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFsB,MAAAA,KAAK,GAAGA,KAAK,GAAGvB,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOsB,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBzC,KAAzB,EAAgC;AAC9B,MAAI0C,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAI1B,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFwB,MAAAA,KAAK,GAAGA,KAAK,GAAGzB,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOwB,KAAP;AACD;;AAED,SAASC,eAAT,CAAyB3C,KAAzB,EAAgC;AAC9B,MAAI4C,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAI5B,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjF0B,MAAAA,KAAK,GAAGA,KAAK,GAAG3B,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAO0B,KAAP;AACD;;AAED,SAASC,eAAT,CAAyB7C,KAAzB,EAAgC;AAC9B,MAAI8C,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAI9B,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjF4B,MAAAA,KAAK,GAAGA,KAAK,GAAG7B,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAO4B,KAAP;AACD;;AAED,SAASC,eAAT,CAAyB/C,KAAzB,EAAgC;AAC9B,MAAIgD,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIhC,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjF8B,MAAAA,KAAK,GAAGA,KAAK,GAAG/B,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAO8B,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBjD,KAAzB,EAAgC;AAC9B,MAAIkD,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIlC,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFgC,MAAAA,KAAK,GAAGA,KAAK,GAAGjC,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOgC,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBnD,KAAzB,EAAgC;AAC9B,MAAIoD,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIpC,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFkC,MAAAA,KAAK,GAAGA,KAAK,GAAGnC,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOkC,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBrD,KAAzB,EAAgC;AAC9B,MAAIsD,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAItC,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFoC,MAAAA,KAAK,GAAGA,KAAK,GAAGrC,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOoC,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBvD,KAAzB,EAAgC;AAC9B,MAAIwD,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIxC,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFsC,MAAAA,KAAK,GAAGA,KAAK,GAAGvC,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOsC,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBzD,KAAzB,EAAgC;AAC9B,MAAI0D,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAI1C,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFwC,MAAAA,KAAK,GAAGA,KAAK,GAAGzC,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOwC,KAAP;AACD;;AAED,SAASC,eAAT,CAAyB3D,KAAzB,EAAgC;AAC9B,MAAI4D,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAI5C,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjF0C,MAAAA,KAAK,GAAGA,KAAK,GAAG3C,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAO0C,KAAP;AACD;;AAED,SAASC,eAAT,CAAyB7D,KAAzB,EAAgC;AAC9B,MAAI8D,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAI9C,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjF4C,MAAAA,KAAK,GAAGA,KAAK,GAAG7C,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAO4C,KAAP;AACD;;AAED,SAASC,eAAT,CAAyB/D,KAAzB,EAAgC;AAC9B,MAAIgE,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIhD,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjF8C,MAAAA,KAAK,GAAGA,KAAK,GAAG/C,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAO8C,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBjE,KAAzB,EAAgC;AAC9B,MAAIkE,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIlD,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFgD,MAAAA,KAAK,GAAGA,KAAK,GAAGjD,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOgD,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBnE,KAAzB,EAAgC;AAC9B,MAAIoE,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIpD,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFkD,MAAAA,KAAK,GAAGA,KAAK,GAAGnD,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOkD,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBrE,KAAzB,EAAgC;AAC9B,MAAIsE,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAItD,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFoD,MAAAA,KAAK,GAAGA,KAAK,GAAGrD,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOoD,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBvE,KAAzB,EAAgC;AAC9B,MAAIwE,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIxD,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFsD,MAAAA,KAAK,GAAGA,KAAK,GAAGvD,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOsD,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBzE,KAAzB,EAAgC;AAC9B,MAAI0E,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAI1D,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFwD,MAAAA,KAAK,GAAGA,KAAK,GAAGzD,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOwD,KAAP;AACD;;AAED,SAASC,eAAT,CAAyB3E,KAAzB,EAAgC;AAC9B,MAAI4E,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAI5D,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjF0D,MAAAA,KAAK,GAAGA,KAAK,GAAG3D,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAO0D,KAAP;AACD;;AAED,SAASC,eAAT,CAAyB7E,KAAzB,EAAgC;AAC9B,MAAI8E,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAI9D,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjF4D,MAAAA,KAAK,GAAGA,KAAK,GAAG7D,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAO4D,KAAP;AACD;;AAED,SAASC,eAAT,CAAyB/E,KAAzB,EAAgC;AAC9B,MAAIgF,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIhE,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjF8D,MAAAA,KAAK,GAAGA,KAAK,GAAG/D,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAO8D,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBjF,KAAzB,EAAgC;AAC9B,MAAIkF,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIlE,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFgE,MAAAA,KAAK,GAAGA,KAAK,GAAGjE,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOgE,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBnF,KAAzB,EAAgC;AAC9B,MAAIoF,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIpE,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFkE,MAAAA,KAAK,GAAGA,KAAK,GAAGnE,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOkE,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBrF,KAAzB,EAAgC;AAC9B,MAAIsF,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAItE,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFoE,MAAAA,KAAK,GAAGA,KAAK,GAAGrE,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOoE,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBvF,KAAzB,EAAgC;AAC9B,MAAIwF,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIxE,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFsE,MAAAA,KAAK,GAAGA,KAAK,GAAGvE,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOsE,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBzF,KAAzB,EAAgC;AAC9B,MAAI0F,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAI1E,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFwE,MAAAA,KAAK,GAAGA,KAAK,GAAGzE,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOwE,KAAP;AACD;;AAED,SAASC,eAAT,CAAyB3F,KAAzB,EAAgC;AAC9B,MAAI4F,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAI5E,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjF0E,MAAAA,KAAK,GAAGA,KAAK,GAAG3E,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAO0E,KAAP;AACD;;AAED,SAASC,eAAT,CAAyB7F,KAAzB,EAAgC;AAC9B,MAAI8F,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAI9E,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjF4E,MAAAA,KAAK,GAAGA,KAAK,GAAG7E,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAO4E,KAAP;AACD;;AAED,SAASC,eAAT,CAAyB/F,KAAzB,EAAgC;AAC9B,MAAIgG,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIhF,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjF8E,MAAAA,KAAK,GAAGA,KAAK,GAAG/E,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAO8E,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBjG,KAAzB,EAAgC;AAC9B,MAAIkG,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIlF,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFgF,MAAAA,KAAK,GAAGA,KAAK,GAAGjF,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOgF,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBnG,KAAzB,EAAgC;AAC9B,MAAIoG,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIpF,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFkF,MAAAA,KAAK,GAAGA,KAAK,GAAGnF,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOkF,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBrG,KAAzB,EAAgC;AAC9B,MAAIsG,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAItF,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM,CAACC,MAAP,KAAkB,CAAlB,IAAuBD,MAAM,CAACC,MAAP,KAAkB,CAAzC,IAA8CD,MAAM,CAACC,MAAP,KAAkB,CAArE,CAAV,EAAmF;AACjFoF,MAAAA,KAAK,GAAGA,KAAK,GAAGrF,MAAM,CAACC,MAAvB;AACD;AACF;;AAED,SAAOoF,KAAP;AACD;;AAED,SAASC,eAAT,CAAyBvG,KAAzB,EAAgC;AAC9B,MAAIwG,KAAK,GAAG,CAAZ;;AAEA,OAAK,IAAIxF,IAAT,IAAiBhB,KAAjB,EAAwB;AACtB,QAAIiB,MAAM,GAAGjB,KAAK,CAACgB,IAAD,CAAlB;;AAEA,QAAIC,MAAM,KAAKA,MAAM

P;;AACA,WAAG;AACDX,UAAAA,IAAI,IAAI,CAAR;AACApT,UAAAA,IAAI,GAAGyF,GAAAG,CAAC3E,UA
AJ,CAAesS,IAAf,CAAP;;AACA,cAAIpT,IAAI,KAAK4R,OAAb,EAAsB;AACpBnE,YAAAA,MAAM,GAAG2F,
IAAT;AACAhH,YAAAA,IAAI,IAAI,CAAR;AACD;AACF,SAPD,QAQEpM,IAAI,KAAK6R,KAAT,,IACA7R,IA
AI,KAAK4R,OADT,IAEA5R,IAAI,KAAK+R,GAFT,IAGA/R,IAAI,KAAKgS,EAHT,IAIAhS,IAAI,KAAK8R,IAA
ZX;;AAeAkB,QAAAA,MAAM,CAACvP,IAAAP,CAAAY,CAAAC,OAAAD,EAAAUgC,GAAAG,CAAC0O,KAAAJ,CAAAUJ
,GAAAV,EAAAeX,IAAAf,CAAAV,CAAAZ;;AACAW,QAAAAA,GAAAG,GAAAGX,IAAAI,GAAAG,CAAAb;AACA;;AAAEF,WA
AKnB,WAAL;AACEe,QAAAAA,MAAM,CAACvP,IAAAP,CAAAY,CAAAC,GAAAD,EAAAM,GAAAN,EAAAW2I,IAAAX,E
AAiB2H,GAAAG,GAAAGtG,MAAAvB,CAAAZ;AACA;;AAEF,WAAAKyE,YAAL;AACEc,QAAAAA,MAAM,CAACvP,
IAAAP,CAAAY,CAAAC,GAAAD,EAAAM,GAAAN,EAAAW2I,IAAAX,EAAAiB2H,GAAAG,GAAAGtG,MAAAvB,CAAAZ;AACA;
;AAEF,WAAAK4E,UAAAL;AACEW,QAAAAA,MAAM,CAACvP,IAAAP,CAAAY,CAAAC,GAAAD,EAAAM,GAAAN,EAAAW,
W2I,IAAAX,EAAAiB2H,GAAAG,GAAAGtG,MAAAvB,CAAAZ;AACA;;AAEF,WAAAK6E,WAAAL;AACEU,QAAAAA,MAA
AM,CAACvP,IAAAP,CAAAY,CAAAC,GAAAD,EAAAM,GAAAN,EAAAW2I,IAAAX,EAAAiB2H,GAAAG,GAAAGtG,MAAAvB,
CAAAZ;AACA;;AAEF,WAAAKgF,YAAAL;AACEO,QAAAAA,MAAM,CAACvP,IAAAP,CAAAY,CAAAC,GAAAD,EAAAM,GAAAN,EAAAM
,GAAAN,EAAAW2I,IAAAX,EAAAiB2H,GAAAG,GAAAGtG,MAAAvB,CAAAZ;AACA;;AAEF,WAAAK8E,WAAAL;AACES,QAAAAA,MAAM,CAACvP,IAAAP,CAAAY,CAAAC,GAAAD,EAAAM,GAAAN,EAAAW2I,IAAAX,EAAAiB2H,GAAAG,GAAAGtG
G,MAAAvB,CAAAZ;AACA;;AAEF,WAAAK0E,gBAAAL;AACE0B,QAAAAA,MAAM,CAACvP,IAAAP,CAAAY,CAAAC,GAAAD,EAAAM,GAAAN,EAAAW,
GAAAgBmS,MAAAM,CAACA,CAAAM,CAACnS,CAAAP,GAAAgB,CAAAjB,CAAAN,CAA0B,CAA1B,CAAAhB,CAAAuB,GAA+B+
,EAAAtD;AACAiT,QAAAAA,CAAAC,GAAAG,GAAAG,CAAC3E,UAAAJ,CAAAeiT,GAAAG,GAAAG,CAArB,CAAAJ;;AA
CA,YACEF,IAAAI,KAAAK,KAAAT,IACAC,CAAAC,KAAAtC,YADN,IAEAsC,CAAAC,KAAArC,YAFN,IAGAqC,CAAC,CA
AC,KAAKjC,KAAHN,IAAIiC,CAAAC,KAAAlC,OAAJN,IAAKkC,CAAAC,KAAAK/B/B,GALN,IAMA+B,CAAAC,KAAAhC,
C,IANN,IAOAgC,CAAAC,KAAA9B,EARR,EASE;AACAoB,UAAAAA,IAAAI,GAAAGW,GAAAP;;AACA,aAAG;AAC
DJ,YAAAA,OAAAO,GAAAG,KAAAV;AACAP,YAAAAA,IAAAI,GAAAG3N,GAAAG,CAACkI,OAAAJ,CAAAY,GAAAZ,EA
AiByF,IAAAI,GAAAG,CAAxB,CAAP;;AACA,gBAAIA,KAAAK,CAAAC,CAAAT,IAAAI,KAAAK,CAAAC,CAAAT,IAAAI,
EAAY;AACVE,gBAAAAA,IAAAI,GAAAGW,GAAAP;AACA;AACD,eAHD,MAGO;AACLC,gBAAAAA,IAAAI,GAAAG,CAAC
,SAAD,CAAR;AACD;AACF;;AACDJ,YAAAAA,SAAAS,GAAAR,IAAAZ;;AACA,mBAAAO,CAAAC,KAAAtC,YAAAqC,CAAAC,
CAAe8S,SAAAS,GAAAG,CAA3B,CAAAC,MAAAkC,CAAAC,KAAAlC,OAAAN,IAAAkC,CAAAC,KAAAK/B/B,GAAAN,IAAAkC,
Ab;AACAD,cAAAAA,IAAAI,GAAAG,CAAC,CAAAC,KAAAtC,YAAAqC,CAAAC,KAAAlC,OAAAN,IAAAkC,CAAAC,KAAAK/B/B
AJ,CAAAe8S,GAAAG,GAAAG,CAAC3E,UAAAJ,CAAAeiT,GAAAG,GAAAG,CAAC,CAAAC,KAAAtC,YAAAqC,CAAAC,KAAAlC
Ab;AACAD,YAAAAA,IAAAI,GAAAG,CAAC,CAAAC,KAAAtC,YAAAqC,CAAAC,KAAAlC,OAAAN,IAAAkC,CAAAC,KAAAK/B/B
AAA,OAAAO,GAAAG,KAAAV;AACAP,YAAAAA,IAAAI,GAAAG3N,GAAAG,CAACkI,OAAAJ,CAAAY,GAAAZ,EAAAiB2H,GAAAG,GAAAGtG
AAA,KAAAK,GAAAG,KAAAV;AACAP,YAAAAA,IAAAI,GAAAG,CAAC,CAAAC,KAAAtC,YAAAqC,CAAAC,KAAAlC,OAAAN,IAAAkC,CAAAC,KAAAK/B/B
AAA,OAAAO,GAAAG,KAAAV;AACAP,YAAAAA,IAAAI,GAAAG,CAAC,CAAAC,KAAAtC,YAAAqC,CAAAC,KAAAlC,OAAAN,IAAAkC,CAAAC,KAAAK/B/B

CAACzS,MAAN,GAAe,CAAtB;;AAEA,YAAI0S,IAAI,GAAG,CAAX,EAAc;AACZE,UAAAAA,QAAAQ,GAAAGrH,IAAI,GAAAGmH,IAAAlB;AACAG,UAAAAA,UAAAU,GAAAGN,IAAI,GAAAGE,KAAAK,CAACC,IAAAD,CAAAL,CAAAY1S,MAAAhC;AACD,SAAHD,MAAAGO;AACL4S,UAAAAA,QAAAQ,GAAAGrH,IAAAX;AACAsH,UAAAAA,UAAAU,GAAAGjG,MAAAb;AACD;;AAEDuF,QAAAAA,MAAAM,CAACvP,IAAAP,CAAAY,CACV,QADU,EAAEVgC,GAAAG,CAAAC0O,KAAAJ,CAAAUJ,GAAAV,EAAAeX,IAAAI,GAAAG,CAAAtB,CAAAFU,CAAAH,EAAAgBVhH,IAAAV,EAAAI,GAAAG,CAAAC,CAAA5B,EAAAgCGAJ,IAAAEA,KVgG,QALU,EAAMVL,IAAAI,GAAAGM,UANG,CAAAC,CAAAZ;AAASaj

AJ,CAViB;;AAAA,CAAxB;;AAaA,SAASvU,IAAT,CAAcwU,KAAd,EAAqB;AACnB,mBAAiBA,KAAjB;AACD;;AAED,SAASC,iBAAT,CAA2BhP,GAA3B,EAAgC;AAC9B,MAAMuN,MAAM,GAAGF,QAAQ,CAAC,IAAI4B,KAAJ,CAAUjP,GAAV,EAAe,EAAf;AACA+N,MAAAA,KAAK,EAAE0N,IAAAA,AAAY,EAAE;AAAhB;AAAmBC,QAAAA,GAAG,EAAEC

AACzB,SAAK/O,IAAI,CAACgP,IAAV,EAAgBhP,IAAhB,EAAsB+O,SAAtB;AACD;;SAEDE,OAAA,cAAKjP,IAAL,EAAW;AACT,SAAKkP,IAAL,CAAUlP,IAAV;AACA,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqBA,KAAKO,OAAL,CAAa7O,IAAI,CAACmP,IAAL,CAAUb,KAAvB;AACtB;;SAED/B,UAAA,iBAAQvM,IAAR,EAAc;AACZ,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDG,kBAAA,yBAAgBzP,IAAhB,EAAsB;AACpB,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDI,SAAA,gBAAOC,KAAP,EAAcC,KAAd,EAAqB;AACnB,QAAIC,IAAI,GAAGF,KAAK,CAACG,KAAN,CAAY,CAAZ,EAAeF,KAAf,CAAX;AACA,QAAIG,IAAI,GAAGJ,KAAK,CAACG,KAAN,CAAYF,KAAZ,CAAX;AACA,WAAOC,IAAI,CAACG,MAAL,CAAYD,IAAZ,CAAP;AACD;;SAEDE,UAAA,iBAAQ/P,IAAR,EAAc;AACZ,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDU,SAAA,gBAAOhQ,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDW,SAAA,gBAAOjQ,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDY,SAAA,gBAAOlQ,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDa,SAAA,gBAAOnQ,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDc,SAAA,gBAAOpQ,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDe,SAAA,gBAAOrQ,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDgB,SAAA,gBAAOtQ,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDiB,SAAA,gBAAOvQ,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDkB,SAAA,gBAAOxQ,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDmB,SAAA,gBAAOzQ,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDoB,SAAA,gBAAO1Q,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDqB,SAAA,gBAAO3Q,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDsB,SAAA,gBAAO5Q,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDuB,SAAA,gBAAO7Q,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDwB,SAAA,gBAAO9Q,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDyB,SAAA,gBAAO/Q,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED0B,SAAA,gBAAOhR,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED2B,SAAA,gBAAOjR,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED4B,SAAA,gBAAOlR,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED6B,SAAA,gBAAOnR,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED8B,SAAA,gBAAOpR,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED+B,SAAA,gBAAOrR,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDgC,SAAA,gBAAOtR,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDiC,SAAA,gBAAOvR,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDkC,SAAA,gBAAOxR,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDmC,SAAA,gBAAOzR,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDoC,SAAA,gBAAO1R,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDqC,SAAA,gBAAO3R,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDsC,SAAA,gBAAO5R,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDuC,SAAA,gBAAO7R,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDwC,SAAA,gBAAO9R,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDyC,SAAA,gBAAO/R,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED0C,SAAA,gBAAOhS,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED2C,SAAA,gBAAOjS,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED4C,SAAA,gBAAOlS,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED6C,SAAA,gBAAOnS,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED8C,SAAA,gBAAOpS,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED+C,SAAA,gBAAOrS,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDgD,SAAA,gBAAOtS,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDiD,SAAA,gBAAOvS,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDkD,SAAA,gBAAOxS,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDmD,SAAA,gBAAOzS,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDoD,SAAA,gBAAO1S,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDqD,SAAA,gBAAO3S,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDsD,SAAA,gBAAO5S,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDuD,SAAA,gBAAO7S,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDwD,SAAA,gBAAO9S,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAEDyD,SAAA,gBAAO/S,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED0D,SAAA,gBAAOhT,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED2D,SAAA,gBAAOjT,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED4D,SAAA,gBAAOlT,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED6D,SAAA,gBAAOnT,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED8D,SAAA,gBAAOpT,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAAI,CAACG,MAAL,CAAYF,KAAZ,EAAmB,CAAnB;AACD;AACF;;SAED+D,SAAA,gBAAOrT,IAAP,EAAa;AACX,QAAIA,IAAI,CAACmP,IAAL,CAAUb,KAAd,EAAqB;AACnB,UAAIc,IAAI,GAAGpP,IAAI,CAACmP,IAAL,CAAUb,KAArB;AACA,UAAIe,KAAK,GAAGD,IAAI,CAACE,OAAL,CAAavP,IAAb,CAAZ;;AACA,UAAIsP,KAAK,KAAK,CAAC,CAAf,EAAkB;AAChBD,QAAAA,IAA

,KAAKI,MAAL,CAAJ,EAAkB;AAChBvI,QAAAAA,KAAK,GAAG,KAAKuI,MAAL,EAAarB,IAAb,EAAmBjP,IAAnB,CAAR;AACD,OAFD,MAEO;AACLiP,QAAAAA,IAAI,CAACsB,IAAL,CAAU,UAAA3X,CAAC,EAAI;AACbmP,UAAAAA,KAAK,GAAnP,CAAC,CAACuW,IAAF,CAAOc,CAAP,CAAcA,CAAC,CAACiH,KAAF,EAAd,CAAwBjH,CAAC,CAACkH,IAAF,EAAxB,CAAkC,CAAlC,CAAoCC,CAAC,CAACnH,CAAC,CAACoH,KAAF,EAAD,CAAYpH,CAAC,CAACqH,IAAF,EAAZ,CAAsB,CAAtB,CAAwB,CAAxB,CAA0B,CAA1B,CAA4B,CAA5B,CAA8B,CAA9B,CAAgC,CAAhC,CAAkC,CAAlC,CAAoC,CAApC,CAAsC,CAAtC,CAAwC,CAAxC,CAA0C,CAA1C,CAA4C,CAA5C,CAA8C,CAA9C,CAAgD,CAAhD,CAAkD,CAAlD,CAAoD,CAApD,CAAsD,CAAtD,CAAwD,CAAxD,CAA0D,CAA1D,CAA4D,CAA5D,CAA8D,CAA9D,CAAgE,CAAhE,CAAkE,CAAlE,CAAoE,CAApE,CAAsE,CAAtE,CAAwE,CAAxE,CAA0E,CAA1E,CAA4E,CAA5E,CAA8E,CAA9E,CAAgF,CAAhF,CAAkF,CAAlF,CAAoF,CAApF,CAAsF,CAAtF,CAAwF,CAAxF,CAA0F,CAA1F,CAA4F,CAA5F,CAA8F,CAA9F,CAAgG,CAAhG,CAAkG,CAAlG,CAAoG,CAApG,CAAsG,CAAtG,CAAwG,CAAxG,CAA0G,CAA1G,CAA4G,CAA5G,CAA8G,CAA9G,CAAgH,CAAhH,CAAkH,CAAlH,CAAoH,CAApH,CAAsH,CAAtH,CAAwH,CAAxH,CAA0H,CAA1H,CAA4H,CAA5H,CAA8H,CAA9H,CAAgI,CAAhI,CAAkI,CAAlI,CAAoI,CAApI,CAAsI,CAAtI,CAAwI,CAAxI,CAA0I,CAA1I,CAA4I,CAA5I,CAA8I,CAA9I,CAAgJ,CAAhJ,CAAkJ,CAAlJ,CAAoJ,CAApJ,CAAsJ,CAAtJ,CAAwJ,CAAxJ,CAA0J,CAA1J,CAA4J,CAA5J,CAA8J,CAA9J,CAAgK,CAAhK,CAAkK,CAAlK,CAAoK,CAApK,CAAsK,CAAtK,CAAwK,CAAxK,CAA0K,CAA1K,CAA4K,CAA5K,CAA8K,CAA9K,CAAgL,CAAhL,CAAkL,CAAlL,CAAoL,CAApL,CAAsL,CAAtL,CAAwL,CAAxL,CAA0L,CAA1L,CAA4L,CAA5L,CAA8L,CAA9L,CAAgM,CAAhM,CAAkM,CAAlM,CAAoM,CAApM,CAAsM,CAAtM,CAAwM,CAAxM,CAA0M,CAA1M,CAA4M,CAA5M,CAA8M,CAA9M,CAAgN,CAAhN,CAAkN,CAAlN,CAAoN,CAApN,CAAsN,CAAtN,CAAwN,CAAxN,CAA0N,CAA1N,CAA4N,CAA5N,CAA8N,CAA9N,CAAgO,CAAhO,CAAkO,CAAlO,CAAoO,CAApO,CAAsO,CAAtO,CAAwO,CAAxO,CAA0O,CAA1O,CAA4O,CAA5O,CAA8O,CAA9O,CAAgP,CAAhP,CAAkP,CAAlP,CAAoP,CAApP,CAAsP,CAAtP,CAAwP,CAAxP,CAA0P,CAA1P,CAA4P,CAA5P,CAA8P,CAA9P,CAAgQ,CAAhQ,CAAkQ,CAAlQ,CAAoQ,CAApQ,CAAsQ,CAAtQ,CAAwQ,CAAxQ,CAA0Q,CAA1Q,CAA4Q,CAA5Q,CAA8Q,CAA9Q,CAAgR,CAAhR,CAAkR,CAAlR,CAAoR,CAApR,CAAsR,CAAtR,CAAwR,CAAxR,CAA0R,CAA1R,CAA4R,CAA5R,CAA8R,CAA9R,CAAgS,CAAhS,CAAkS,CAAlS,CAAoS,CAApS,CAAsS,CAAtS,CAAwS,CAAxS,CAA0S,CAA1S,CAA4S,CAA5S,CAA8S,CAA9S,CAAgT,CAAhT,CAAkT,CAAlT,CAAoT,CAApT,CAAsT,CAAtT,CAAwT,CAAxT,CAA0T,CAA1T,CAA4T,CAA5T,CAA8T,CAA9T,CAAgU,CAAhU,CAAkU,CAAlU,CAAoU,CAApU,CAAsU,CAAtU,CAAwU,CAAxU,CAA0U,CAA1U,CAA4U,CAA5U,CAA8U,CAA9U,CAAgV,CAAhV,CAAkV,CAAlV,CAAoV,CAApV,CAAsV,CAAtV,CAAwV,CAAxV,CAA0V,CAA1V,CAA4V,CAA5V,CAA8V,CAA9V,CAAgW,CAAhW,CAAkW,CAAlW,CAAoW,CAApW,CAAsW,CAAtW,CAAwW,CAAxW,CAA0W,CAA1W,CAA4W,CAA5W,CAA8W,CAA9W,CAAgX,CAAhX,CAAkX,CAAlX,CAAoX,CAApX,CAAsX,CAAtX,CAAwX,CAAxX,CAA0X,CAA1X,CAA4X,CAA5X,CAA8X,CAA9X,CAAgY,CAAhY,CAAkY,CAAlY,CAAoY,CAApY,CAAsY,CAAtY,CAAwY,CAAxY,CAA0Y,CAA1Y,CAA4Y,CAA5Y,CAA8Y,CAA9Y,CAAgZ,CAAhZ,CAAkZ,CAAlZ,CAAoZ,CAApZ,CAAsZ,CAAtZ,CAAwZ,CAAxZ,CAA0Z,CAA1Z,CAA4Z,CAA5Z,CAA8Z,CAA9Z,CAAga,CAAha,CAAka,CAAla,CAAoa,CAApa,CAAsa,CAAta,CAAwa,CAAxa,CAA0a,CAA1a,CAA4a,CAA5a,CAA8a,CAA9a,CAAgb,CAAhb,CAAkb,CAAlb,CAAob,CAApb,CAAsb,CAAtb,CAAwb,CAAxb,CAA0b,CAA1b,CAA4b,CAA5b,CAA8b,CAA9b,CAAgc,CAAhc,CAAkc,CAAlc,CAAoc,CAApc,CAAsc,CAAtc,CAAwc,CAAxc,CAA0c,CAA1c,CAA4c,CAA5c,CAA8c,CAA9c,CAAgd,CAAhd,CAAkd,CAAld,CAAod,CAApd,CAAsd,CAAtd,CAAwd,CAAxd,CAA0d,CAA1d,CAA4d,CAA5d,CAA8d,CAA9d,CAAge,CAAhe,CAAke,CAAle,CAAoe,CAApe,CAAse,CAAte,CAAwe,CAAxe,CAA0e,CAA1e,CAA4e,CAA5e,CAA8e,CAA9e,CAAgf,CAAhf,CAAkf,CAAlf,CAAof,CAApf,CAAsf,CAAtf,CAAwf,CAAxf,CAA0f,CAA1f,CAA4f,CAA5f,CAA8f,CAA9f,CAAggB,CAAhgB,CAAkgB,CAAlgB,CAAogB,CAApgB,CAAsgB,CAAtgB,CAAwgB,CAAxgB,CAA0gB,CAA1gB,CAA4gB,CAA5gB,CAA8gB,CAA9gB,CAAghB,CAAhhB,CAAkhB,CAAlhB,CAAohB,CAAphB,CAAshB,CAAthB,CAAwhB,CAAxhB,CAA0hB,CAA1hB,CAA4hB,CAA5hB,CAA8hB,CAA9hB,CAAgiB,CAAhiB,CAAkiB,CAAliB,CAAoiB,CAApiB,CAAsiB,CAAtiB,CAAwiB,CAAxiB,CAA0iB,CAA1iB,CAA4iB,CAA5iB,CAA8iB,CAA9iB,CAAgjB,CAAhjB,CAAkjB,CAAljB,CAAojB,CAApjB,CAAsjB,CAAtjB,CAAwjB,CAAxjB,CAA0jB,CAA1jB,CAA4jB,CAA5jB,CAA8jB,CAA9jB,CAAgkB,CAAhkB,CAAkkB,CAAlkB,CAAokB,CAApkB,CAAskB,CAAtkB,CAAwkB,CAAxkB,CAA0kB,CAA1kB,CAA4kB,CAA5kB,CAA8kB,CAA9kB,CAAgl,CAAhl,CAAkl,CAAll,CAAol,CAApl,CAAsl,CAAtl,CAAwl,CAAxl,CAA0l,CAA1l,CAA4l,CAA5l,CAA8l,CAA9l,CAAgm,CAAhm,CAAkm,CAAlm,CAAom,CAApm,CAAsm,CAAtm,CAAwm,CAAxm,CAA0m,CAA1m,CAA4m,CAA5m,CAA8m,CAA9m,CAAgn,CAAhn,CAAkn,CAAln,CAAon,CAApn,CAAsn,CAAtn,CAAwn,CAAxn,CAA0n,CAA1n,CAA4n,CAA5n,CAA8n,CAA9n,CAAgo,CAAho,CAAko,CAAlo,CAAoo,CAApo,CAAso,CAAto,CAAwo,CAAxo,CAA0o,CAA1o,CAA4o,CAA5o,CAA8o,CAA9o,CAAgp,CAAhp,CAAkp,CAAlp,CAAop,CAApp,CAAsp,CAAtp,CAAwp,CAAxp,CAA0p,CAA1p,CAA4p,CAA5p,CAA8p,CAA9p,CAAgq,CAAhq,CAAkq,CAAlq,CAAoq,CAApq,CAAsq,CAAtq,CAAwq,CAAxq,CAA0q,CAA1q,CAA4q,CAA5q,CAA8q,CAA9q,CAAgr,CAAhr,CAAkr,CAAlr,CAAor,CAApr,CAAsr,CAAtr,CAAwr,CAAxr,CAA0r,CAA1r,CAA4r,CAA5r,CAA8r,CAA9r,CAAgs,CAAhs,CAAks,CAAls,CAAos,CAAps

K,GAAGA,KAAK,CAACvP,OAAN,CAAc,SAAd,EAAyB,EAAzB,CAAR;AACD;;AACD,iBAAO,KAAP;AACD;
AACF;AACF,KAVD;AAWA,WAAOuP,KAAP;AACD;;SAEDmJ,gBAAA,uBAAcjC,IAAd,EAAoB;AAClB,QAA
IlH,KAAJ;AACAkH,IAAAA,IAAI,CAACsB,IAAL,CAAU,UAAA3X,CAAC,EAAI;AACb,UAAIA,CAAC,CAAC
oW,IAAF,KAAW,MAAf,EAAuB;AACrBjH,QAAAA,KAAK,GAAnP,CAAC,CAACuW,IAAF,CAAOM,OAAf;
AACA,YAAI,OAAO1H,KAAP,iB,WAArB,EAAkC,OAAO,KAAP;AACnC;AACF,KALD;AAMA,WAAOA,
KAAP;AACD;;SAEDoJ,WAAA,kBAASlC,IAAT,EAAe;AACb,UAAIA,IAAI,CAACe,IAAL,KAAc,CAAlB,EAAqB;AAAE
B,SAAL,CAAe,UAAAnY,UAAAnY,CAAC,EAAI,CAAC,CAACuW,IAAF,CAAOM,OAAd,CAAuB,UAAA7W,CAAC
;AAClB,UAAI,OAAOA,KAAP,KAAiB,QAAjB,IAA6BA,KAAK,KAAK,IAA3C,EAAiD;AAC/C,YAAIA,KAAK
B,WAA9B,EAA2C;AACzC,cAAIA,KAAK,CAACuW,IAAN,CAAWM,OAAX,KAAuB,OAA3B,EAAoC,OAAO,KAAP;
AACzC;AACF,KALD;AAMA,WAAOuP,KAAP;AACD;;SAEDsI,cAAA,qBAAYpC,IAAZ,EAAkB;AAChB,UAAIA,IAAI,CAACe
AAI,CAACgP,IAAL,CAAU,KAAAc,c,MAAAA,MAAAA,KAAAA,GAAAA,KAAAA,CAAAA,IAAAA,CAAAA,IAAAA,EAAAA,IAAAA,CAAAA,
T,EAAAe,IAAAf,EAAAqB,YAAArB,CAAAA,EAAAA,CAAAA,EAAAA,CAAAA,EAAAA

AmBtD,OAAnB,CAAP;AACD;AACF;AAED;;;;;;;;;;;;;;;;;;;;;;;;;SAyBAH,OAAA,cAAKH,MAAL,EAAasG,IAAb,EAAmBqC,IAAnB,EAAyB;AACvB,QAAME,IAAI,GAAG;AAAE9R,MAAAA,IAAI,EAAE;AAAR,KAAb;;AACA,SAAK,IAAMpH,CAAX,IAAgBgZ,IAAhB;AAAsBE,MAAAA,IAAI,CAAClZ,CAAD,CAAJ,GAAUgZ,IAAI,CAAChZ,CAAD,CAAd;AAAtB;;AACA,WAAOkZ,IAAP;AACD;;AAED,SAASC,IAAT,CAAcH,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASK,IAAT,CAAcL,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASM,IAAT,CAAcN,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASO,IAAT,CAAcP,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASQ,IAAT,CAAcR,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASS,IAAT,CAAcT,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASU,IAAT,CAAcV,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASW,IAAT,CAAcX,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASY,IAAT,CAAcZ,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASa,IAAT,CAAcb,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASc,IAAT,CAAcd,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASe,IAAT,CAAcf,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASgB,IAAT,CAAchB,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASiB,IAAT,CAAcjB,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASkB,IAAT,CAAclB,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASmB,IAAT,CAAcnB,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASoB,IAAT,CAAcpB,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASqB,IAAT,CAAcrB,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASsB,IAAT,CAActB,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASuB,IAAT,CAAcvB,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASwB,IAAT,CAAcxB,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASyB,IAAT,CAAczB,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS0B,IAAT,CAAc1B,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS2B,IAAT,CAAc3B,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS4B,IAAT,CAAc5B,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS6B,IAAT,CAAc7B,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS8B,IAAT,CAAc9B,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS+B,IAAT,CAAc/B,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASgC,IAAT,CAAchC,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASiC,IAAT,CAAcjC,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASkC,IAAT,CAAclC,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASmC,IAAT,CAAcnC,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASoC,IAAT,CAAcpC,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASqC,IAAT,CAAcrC,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASsC,IAAT,CAActC,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASuC,IAAT,CAAcvC,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASwC,IAAT,CAAcxC,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASyC,IAAT,CAAczC,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS0C,IAAT,CAAc1C,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS2C,IAAT,CAAc3C,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS4C,IAAT,CAAc5C,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS6C,IAAT,CAAc7C,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS8C,IAAT,CAAc9C,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS+C,IAAT,CAAc/C,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASgD,IAAT,CAAchD,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASiD,IAAT,CAAcjD,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASkD,IAAT,CAAclD,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASmD,IAAT,CAAcnD,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASoD,IAAT,CAAcpD,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASqD,IAAT,CAAcrD,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASsD,IAAT,CAActD,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASuD,IAAT,CAAcvD,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASwD,IAAT,CAAcxD,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASyD,IAAT,CAAczD,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS0D,IAAT,CAAc1D,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS2D,IAAT,CAAc3D,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS4D,IAAT,CAAc5D,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS6D,IAAT,CAAc7D,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS8D,IAAT,CAAc9D,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS+D,IAAT,CAAc/D,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASgE,IAAT,CAAchE,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASiE,IAAT,CAAcjE,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASkE,IAAT,CAAclE,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASmE,IAAT,CAAcnE,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASoE,IAAT,CAAcpE,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASqE,IAAT,CAAcrE,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASsE,IAAT,CAActE,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASuE,IAAT,CAAcvE,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASwE,IAAT,CAAcxE,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASyE,IAAT,CAAczE,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS0E,IAAT,CAAc1E,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS2E,IAAT,CAAc3E,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS4E,IAAT,CAAc5E,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS6E,IAAT,CAAc7E,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS8E,IAAT,CAAc9E,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS+E,IAAT,CAAc/E,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASgF,IAAT,CAAchF,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASiF,IAAT,CAAcjF,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASkF,IAAT,CAAclF,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASmF,IAAT,CAAcnF,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASoF,IAAT,CAAcpF,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASqF,IAAT,CAAcrF,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASsF,IAAT,CAActF,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASuF,IAAT,CAAcvF,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASwF,IAAT,CAAcxF,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASyF,IAAT,CAAczF,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS0F,IAAT,CAAc1F,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS2F,IAAT,CAAc3F,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS4F,IAAT,CAAc5F,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS6F,IAAT,CAAc7F,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS8F,IAAT,CAAc9F,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS+F,IAAT,CAAc/F,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASgG,IAAT,CAAchG,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASiG,IAAT,CAAcjG,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASkG,IAAT,CAAclG,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASmG,IAAT,CAAcnG,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASoG,IAAT,CAAcpG,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASqG,IAAT,CAAcrG,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASsG,IAAT,CAActG,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASuG,IAAT,CAAcvG,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASwG,IAAT,CAAcxG,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASyG,IAAT,CAAczG,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS0G,IAAT,CAAc1G,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS2G,IAAT,CAAc3G,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS4G,IAAT,CAAc5G,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS6G,IAAT,CAAc7G,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS8G,IAAT,CAAc9G,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAAS+G,IAAT,CAAc/G,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASgH,IAAT,CAAchH,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,SAAOJ,IAAP;AACD;;AAED,SAASiH,IAAT,CAAcjH,IAAd,EAAoB;AAClB,MAAIA,IAAI,CAAC9R,IAAL,KAAc,IAAlB,EAAwB;AACtB,UAAM,IAAIkS,KAAJ,CAAU,2BAAV,CAAN;AACD;;AACD,

AEDwJ,YAAA,mBAAUQ,WAAV,EAAuB;AACrB,WAAO,KAAK9D,IAAL,CAAUa,MAAjB;AACA,WAAO,KAAKb,IAAL,CAAUb,KAAjB;AACA,QAAI,CAAC2E,WAAL,EAAkB,OAAO,KAAK9D,IAAL,CAAUM,OAAjB;ACnB;;SAEDyD,iBAAA,wBAAezW,KAAf,EAAsB;AACpB,QAAMiJ,MAAM,GAAG,KAAK9L,IAAL,CAAUqL,EAAf;ACA,QAAIyK,MAAM,GAAG,KAAKyI,MAAL,CAAYO,KAAZ,CAAkBhJ,MAA/B;AACA,QAAID,IAAI,GAAG,KAAK0I,MAAL,CAAYO,KAAZ,CAAkBjJ,IAA7B;;AAEA,SAAK,IAAIxB,CAAT,IAAcyB,MAAd,EAAsB;AACpB,UAAIA,MAAM,CAACzB,CAAD,CAAN,KAAcvH,KAAlB,EAAyB;AACvBgJ,QAAAA,MAAM,CAACzB,CAAD,CAAN,GAAYvH,KAAZ;AACAiJ,QAAAA,IAAI,CAAC1B,CAAD,CAAJ,GAAU,IAAV;AACD;AACF;;AAED,SAAKkK,MAAL,CAAYO,KAAZ,CAAkBhJ,MAAlB,GAA2BA,MAA3B;AACA,SAAKyI,MAAL,CAAYO,KAAZ,CAAkBjJ,IAAlB,GAAyBA,IAAzB;AACD;;AAED,WAAO,KAAKtC,IAAL,CAAUM,OAAjB;AACD;;AAED,SAAOkL,gBAAP,CAAwBC,KAAxB,EAA+B;AAC7B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOC,eAAP,CAAuBH,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOE,eAAP,CAAuBJ,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOG,eAAP,CAAuBL,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOI,eAAP,CAAuBN,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOK,eAAP,CAAuBP,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOM,eAAP,CAAuBR,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOO,eAAP,CAAuBT,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOQ,eAAP,CAAuBV,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOS,eAAP,CAAuBX,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOU,eAAP,CAAuBZ,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOW,eAAP,CAAuBb,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOY,eAAP,CAAuBd,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOa,eAAP,CAAuBf,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOc,eAAP,CAAuBhB,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOe,eAAP,CAAuBjB,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOgB,eAAP,CAAuBlB,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOiB,eAAP,CAAuBnB,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOkB,eAAP,CAAuBpB,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOmB,eAAP,CAAuBrB,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOoB,eAAP,CAAuBtB,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOqB,eAAP,CAAuBvB,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOsB,eAAP,CAAuBxB,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOuB,eAAP,CAAuBzB,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOwB,eAAP,CAAuB1B,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOyB,eAAP,CAAuB3B,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO0B,eAAP,CAAuB5B,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO2B,eAAP,CAAuB7B,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO4B,eAAP,CAAuB9B,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO6B,eAAP,CAAuB/B,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO8B,eAAP,CAAuBhC,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO+B,eAAP,CAAuBjC,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOgC,eAAP,CAAuBlC,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOiC,eAAP,CAAuBnC,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOkC,eAAP,CAAuBpC,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOmC,eAAP,CAAuBrC,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOoC,eAAP,CAAuBtC,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOqC,eAAP,CAAuBvC,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOsC,eAAP,CAAuBxC,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOuC,eAAP,CAAuBzC,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOwC,eAAP,CAAuB1C,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOyC,eAAP,CAAuB3C,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO0C,eAAP,CAAuB5C,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO2C,eAAP,CAAuB7C,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO4C,eAAP,CAAuB9C,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO6C,eAAP,CAAuB/C,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO8C,eAAP,CAAuBhD,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO+C,eAAP,CAAuBjD,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOgD,eAAP,CAAuBlD,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOiD,eAAP,CAAuBnD,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOkD,eAAP,CAAuBpD,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOmD,eAAP,CAAuBrD,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOoD,eAAP,CAAuBtD,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOqD,eAAP,CAAuBvD,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOsD,eAAP,CAAuBxD,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOuD,eAAP,CAAuBzD,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOwD,eAAP,CAAuB1D,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOyD,eAAP,CAAuB3D,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO0D,eAAP,CAAuB5D,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO2D,eAAP,CAAuB7D,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO4D,eAAP,CAAuB9D,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO6D,eAAP,CAAuB/D,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO8D,eAAP,CAAuBhE,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO+D,eAAP,CAAuBjE,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOgE,eAAP,CAAuBlE,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOiE,eAAP,CAAuBnE,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOkE,eAAP,CAAuBpE,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOmE,eAAP,CAAuBrE,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOoE,eAAP,CAAuBtE,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOqE,eAAP,CAAuBvE,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOsE,eAAP,CAAuBxE,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOuE,eAAP,CAAuBzE,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOwE,eAAP,CAAuB1E,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOyE,eAAP,CAAuB3E,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO0E,eAAP,CAAuB5E,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO2E,eAAP,CAAuB7E,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO4E,eAAP,CAAuB9E,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO6E,eAAP,CAAuB/E,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO8E,eAAP,CAAuBhF,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO+E,eAAP,CAAuBjF,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOgF,eAAP,CAAuBlF,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOiF,eAAP,CAAuBnF,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOkF,eAAP,CAAuBpF,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOmF,eAAP,CAAuBrF,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOoF,eAAP,CAAuBtF,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOqF,eAAP,CAAuBvF,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOsF,eAAP,CAAuBxF,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOuF,eAAP,CAAuBzF,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOwF,eAAP,CAAuB1F,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAOyF,eAAP,CAAuB3F,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,CAAL,CAASE,IAAT,KAAkB,KAA5C,EAAmD;AACjD,aAAO,IAAP;AACD;;AAED,WAAO,KAAP;AACD;;AAED,SAAO0F,eAAP,CAAuB5F,KAAvB,EAA8B;AAC5B,QAAIA,KAAK,CAACC,MAAN,KAAiB,CAAjB,IAAsBD,KAAK,CAAC,CAAD,C

CAAaI,KAAb;AACA;;AAEF,aAAK,SAAL;AACE,eAAKkD,MAAL,CAAYlD,KAAZ;AACA;;AAEF,aAAK,GAAA
L;AACE,eAAKoH,SAAL,CAAepH,KAAf;AACA;;AAEF;AACE,eAAKqH,KAAL;AACA;AAxBJ;;AA2BA,WAA
KjI,GAAL,IAAY,CAAZ;AACD;;AACD,SAAKkI,OAAL;AACD;;SAED1H,UAAA,iBAAQI,KAAR,,EAAAe;AACb,
QAAM3M,IAAI,GAAG,IAAIwT,OAAJ,,EAAAb;AACA,SAAKU,IAAL,,CAAAUlU,IAAV,,EAAAgB2M,KAAK,,CAAC,
CAAD,,CAArB,,EAA0BA,KAAK,,CAAC,,CAAD,,CAA/B;AACA3M,IAAAA,CAAC8M,MAAL,,IAAAA,,CAAAA,,CAAAS,GAAA
AZ,GAAAkB;AAAEnJ,MAAAA,IAAI,,EAAEuI,KAAK,,CAAC,,CAAD,,CAAb;AAAAkBtI,MAAAA,MAAM,,EAAEsI,
KAAK,,CAAC,,CAAD;AAA/B,KAAlB;AAEA,QAAM4C,IAAI,,GAAG5C,KAAK,,CAAC,,CAAD,,CAAL,,CAASR,KAAT,
CAAAe,CAAAf,EAAAkB,CAAAC,IAAAC,CAAAC,GAAAC,CAAAC,IAAAC,CAAAC,GAAAC,CAAAC,IAAAC,CAAAC,GAAAC

CAAnB;;AACA,QAAI0S,IAAI,CAAC,CAAD,CAAJ,KAAY,GAAhB,EAAqB;AACnB,WAAKwD,SAAL,GAAiB,IAAjB;AACA/D,MAAAA,MAAM,CACqJ,SAAL,GAAiB,IAAjB;AACA/D,MAAAA,MAAM,CACqJ;AACD;;AACD,QAAI9I,IAAI,CAAC,CAAD,CAAR,EAAa;AACXvL,MAAAA,IAAI,CAAC8M,MAAL,CAAYS,GAAZ,GAAkBA,GAAlB;AACD;;AACD,QAAIvN,IAAI,CAAC,CAAD,CAAR,EAAa;AACXA,MAAAA,IAAI,CAAC,CAAD,CAAJ,CAAQ8M,MAAR,CAAeS,GAAf,GAAqBA,GAArB;AACD;;AACD,WAAOA,GAAP;AACD;;AAED,WAAS+9B,eAAT,CAAyBC,GAAzB,EAA8B;AAC5B,QAAIC,GAAG,GAAGD,GAAG,CAACE,KAAJ,CAAU,GAAV,CAAV;AACA,QAAIC,KAAK,GAAGF,GAAG,CAAC,CAAD,CAAf;AACA,QAAIG,KAAK,GAAGH,GAAG,CAAC,CAAD,CAAf;AACA,QAAIx+B,GAAG,GAAGw+B,GAAG,CAAC,CAAD,CAAb;AACA,QAAIx+B,GAAG,KAAK,KAAZ,EAAmB;AACjBA,MAAAA,GAAG,GAAG,IAAN;AACD;;AACD,QAAIA,GAAG,KAAK,MAAZ,EAAoB;AAClBA,MAAAA,GAAG,GAAG,K

GAAG,KAAK3B,MAAL,CAAY,KAAKe,GAAjB,CAAR;;AAEA,UAAIY,KAAK,CAAC,CAAD,CAAL,KAAa,GAAjB,EAAsB;AACpB3M,QAAAAA,IAAI,CAAC8M,MAAL,CAAYS,GAAAZ,GAAkB;AAAEnJ,UAAAAA,IAAI,EAAEuI,KAAAK,CAAC,CAAD,CAAb;AAAkBtI,UAAAAA,MAAM,EAAEsI,KAAAK,CAAC,CAAD;AAA/B,SAAlB;AACA,aAAAoC,SAAAL,GAAiB,IAAjB;AACA;AACD,OAJD,MAIO,IAAIpC,KAAK,CAAC,CAAD,CAAL,KAAa,GAAjB,EAAsB;AAC3BsC,QAAAA,IAAI,CAAC8M,MAAL,CAAYS,GAAAZ,GAAkB;AAAEnJ,UAAAAA,IAAI,EAAEuI,KAAAK,CAAC,CAAD,CAAb;AAAkBtI,UAAAAA,MAAM,EAAEsI,KAAAK,CAAC,CAAD;AAA/B,SAAlB;AACA,aAAAoC,SAAAL,GAAiB,IAAjB;AACA;AACD,OAJM,MAIA;AACL,aAAAK,SAAAL,GAAiB,KAAjB;AACA;AACD;AACF;AACF;AACF

AsB;AACpB,QAAIsK,aAAJ;AACA,QAAI1B,MAAM,GAAG,EAAb;;AACA,WAAO5I,MAAM,CAACnS,MAAd,EAAsB;AACpByc,MAAAA,aAAa,GAAGtK,MAAM,CAACA,MAAM,CAACnS,MAAP,GAAgB,CAAjB,CAAN,CAA0B,CAA1B,CAAhB;AACA,UAAIyc,aAAa,IAAA6BA,aAAK,KAAK,OAAlB,IAA6BA,aAAa,KAAK,SAAnD,EAA8D;AAC9D,1B,MAAAA,AAAM,GAAG,EAAT,CAAY,IAAZ,CAAiB,CAAjB,EAAoB,CAApB,CAAuB,IAAvB,CAA4B,CAA5B,EAA+B,CAA/B,CAAkC,IAAlC,CAAuC,CAAvC,EAA0C,CAA1C,CAA6C,IAA7C,CAAkD,CAAlD,EAAqD,CAArD,CAAwD,IAAxD,CAA6D,CAA7D,EAAgE,CAAhE,CAAmE,IAAnE,CAAwE,CAAxE,EAA2E,CAA3E,CAA8E,IAA9E,CAAmF,CAAnF,EAAsF,CAAtF,CAAyF,IAAzF,CAA8F,CAA9F,EAAiG,CAAjG,CAAoG,IAApG,CAAyG,CAAzG,EAA4G,CAA5G,CAA+G,IAA/G,CAAoH,CAApH,EAAuH,CAAvH,CAA0H,IAA1H,CAA+H,CAA/H,EAAkI,CAAlI,CAAqI,IAArI,CAA0I,CAA1I,EAA6I,CAA7I,CAAgJ,IAAhJ,CAAqJ,CAArJ,EAAwJ,CAAxJ,CAA2J,IAA3J,CAAgK,CAAhK,EAAmK,CAAnK,CAAsK,IAAtK,CAA2K,CAA3K,EAA8K,CAA9K,CAAiL,IAAjL,CAAsL,CAAtL,EAAyL,CAAzL,CAA4L,IAA5L,CAAiM,CAAjM,EAAoM,CAApM,CAAuM,IAAvM,CAA4M,CAA5M,EAA+M,CAA/M,CAAkN,IAAlN,CAAuN,CAAvN,EAA0N,CAA1N,CAA6N,IAA7N,CAAkO,CAAlO,EAAqO,CAArO,CAAwO,IAAxO,CAA6O,CAA7O,EAAgP,CAAhP,CAAmP,IAAnP,CAAwP,CAAxP,EAA2P,CAA3P,CAA8P,IAA9P,CAAmQ,CAAnQ,EAAsQ,CAAtQ,CAAyQ,IAAzQ,CAA8Q,CAA9Q,EAAiR,CAAjR,CAAoR,IAApR,CAAyR,CAAzR,EAA4R,CAA5R,CAA+R,IAA/R,CAAoS,CAApS,EAAuS,CAAvS,CAA0S,IAA1S,CAA+S,CAA/S,EAAkT,CAAlT,CAAqT,IAArT,CAA0T,CAA1T,EAA6T,CAA7T,CAAgU,IAAhU,CAAqU,CAArU,EAAwU,CAAxU,CAA2U,IAA3U,CAAgV,CAAhV,EAAmV,CAAnV,CAAsV,IAAtV,CAA2V,CAA3V,EAA8V,CAA9V,CAAiW,IAAjW,CAAsW,CAAtW,EAAyW,CAAzW,CAA4W,IAA5W,CAAiX,CAAjX,EAAoX,CAApX,CAAuX,IAAvX,CAA4X,CAA5X,EAA+X,CAA/X,CAAkY,IAAlY,CAAuY,CAAvY,EAA0Y,CAA1Y,CAA6Y,IAA7Y,CAAkZ,CAAlZ,EAAqZ,CAArZ,CAAwZ,IAAxZ,CAA6Z,CAA7Z,EAAga,CAAha,CAAma,IAAna,CAAwa,CAAxa,EAA2a,CAA3a,CAA8a,IAA9a,CAAmb,CAAnb,EAAsb,CAAtb,CAAyb,IAAzb,CAA8b,CAA9b,EAAic,CAAjc,CAAoc,IAApc,CAAyc,CAAzc,EAA4c,CAA5c,CAA+c,IAA/c,CAAod,CAApd,EAAud,CAAvd,CAA0d,IAA1d,CAA+d,CAA/d,EAAke,CAAle,CAAqe,IAAre,CAA0e,CAA1e,EAA6e,CAA7e,CAAgf,IAAhf,CAAqf,CAArf,EAAwf,CAAxf,CAA2f,IAA3f,CAAggB,CAAhgB,EAAmgB,CAAngB,CAAsgB,IAAtgB,CAA2gB,CAA3gB,EAA8gB,CAA9gB,CAAihB,IAAjhB,CAAshB,CAAthB,EAAyhB,CAAzhB,CAA4hB,IAA5hB,CAAiiB,CAAjiB,EAAoiB,CAApiB,CAAuiB,IAAviB,CAA4iB,CAA5iB,EAA+iB,CAA/iB,CAAkjB,IAAljB,CAAujB,CAAvjB,EAA0jB,CAA1jB,CAA6jB,IAA7jB,CAAkkB,CAAlkB,EAAqkB,CAArkB,CAAwkB,IAAxkB,CAA6kB,CAA7kB,EAAglB,CAAhlB,CAAmlB,IAAnlB,CAAwlB,CAAxlB,EAA2lB,CAA3lB,CAA8lB,IAA9lB,CAAmmB,CAAnmB,EAAsmB,CAAtmB,CAAymB,IAAzmB,CAA8mB,CAA9mB,EAAinB,CAAjnB,CAAonB,IAApnB,CAAynB,CAAznB,EAA4nB,CAA5nB,CAA+nB,IAA/nB,CAAooB,CAApoB,EAAuoB,CAAvoB,CAA0oB,IAA1oB,CAA+oB,CAA/oB,EAAkpB,CAAlpB,CAAqpB,IAArpB,CAA0pB,CAA1pB,EAA6pB,CAA7pB,CAAgqB,IAAhqB,CAAqqB,CAArqB,EAAwqB,CAAxqB,CAA2qB,IAA3qB,CAAgrB,CAAhrB,EAAmrB,CAAnrB,CAAsrB,IAAtrB,CAA2rB,CAA3rB,EAA8rB,CAA9rB,CAAisB,IAAjsB,CAAssB,CAAtsB,EAAysB,CAAzsB,CAA4sB,IAA5sB,CAAitB,CAAjtB,EAAotB,CAAptB,CAAutB,IAAvtB,CAA4tB,CAA5tB,EAA+tB,CAA/tB,CAAkuB,IAAluB,CAAuuB,CAAvuB,EAA0uB,CAA1uB,CAA6uB,IAA7uB,CAAkvB,CAAlvB,EAAqvB,CAArvB,CAAwvB,IAAxvB,CAA6vB,CAA7vB,EAAgwB,CAAhwB,CAAmwB,IAAnwB,CAAwwB,CAAxwB,EAA2wB,CAA3wB,CAA8wB,IAA9wB,CAAmxB,CAAnxB,EAAsxB,CAAtxB,CAAyxB,IAAzxB,CAA8xB,CAA9xB,EAAiyB,CAAjyB,CAAoyB,IAApyB,CAAyyB,CAAzyB,EAA4yB,CAA5yB,CAA+yB,IAA/yB,CAAozB,CAApzB,EAAuzB,CAAvzB,CAA0zB,IAA1zB,CAA+zB,CAA/zB,EAAk0B,CAAl0B,CAAq0B,IAAr0B,CAA00B,CAA10B,EAA60B,CAA70B,CAAg1B,IAAh1B,CAAq1B,CAAr1B,EAAw1B,CAAx1B,CAA21B,IAA31B,CAAg2B,CAAh2B,EAAm2B,CAAn2B,CAAs2B,IAAt2B,CAA22B,CAA32B,EAA82B,CAA92B,CAAi3B,IAAj3B,CAAs3B,CAAt3B,EAAy3B,CAAz3B,CAA43B,IAA53B,CAAi4B,CAAj4B,EAAo4B,CAAp4B,CAAu4B,IAAv4B,CAA44B,CAA54B,EAA+4B,CAA/4B,CAAk5B,IAAl5B,CAAu5B,CAAv5B,EAA05B,CAA15B,CAA65B,IAA75B,CAAk6B,CAAl6B,EAAq6B,CAAr6B,CAAw6B,IAAx6B,CAA66B,CAA76B,EAAg7B,CAAh7B,CAAm7B,IAAn7B,CAAw7B,CAAx7B,EAA27B,CAA37B,CAA87B,IAA97B,CAAm8B,CAAn8B,EAAs8B,CAAt8B,CAAy8B,IAAz8B,CAA88B,CAA98B,EAAi9B,CAAj9B,CAAo9B,IAAp9B,CAAy9B,CAAz9B,EAA49B,CAA59B,CAA+9B,IAA/9B,CAAo+B,CAAp+B,EAAu+B,CAAv+B,CAA0+B,IAA1+B,CAA++B,CAA/+B,EAAk/B,CAAl/B,CAAq/B,IAAr/B,CAA0/B,CAA1/B,EAA6/B,CAA7/B,CAAggC,IAAhgC,CAAqgC,CAArgC,EAAwgC,CAAxgC,CAA2gC,IAA3gC,CAAghC,CAAhhC,EAAmhC,CAAnhC,CAAshC,IAAthC,CAA2hC,CAA3hC,EAA8hC,CAA9hC,CAAiiC,IAAjiC,CAAsiC,CAAtiC,EAAyiC,CAAziC,CAA4iC,IAA5iC,CAAijC,CAAjjC,EAAojC,CAApjC,CAAujC,IAAvjC,CAA4jC,CAA5jC,EAA+jC,CAA/jC,CAAkkC,IAAlkC,CAAukC,CAAvkC,EAA0kC,CAA1kC,CAA6kC,IAA7kC,CAAklC,CAAllC,EAAqlC,CAArlC,CAAwlC,IAAxlC,CAA6lC,CAA7lC,EAAgmC,CAAhmC,CAAmmC,IAAnmC,CAAwmC,CAAxmC,EAA2mC,CAA3mC,CAA8mC,IAA9mC,CAAmnC,CAAnnC,EAAsnC,CAAtnC,CAAynC,IAAznC,CAA8nC,CAA9nC,EAAioC,CAAjoC,CAAooC,IAApoC,CAAyoC,CAAzoC,EAA4oC,CAA5oC,CAA+oC,IAA/oC,CAAopC,CAAppC,EAAupC,CAAvpC,CAA0pC,IAA1pC,CAA+pC,CAA/pC,EAAkqC,CAAlqC,CAAqqC,IAArqC,CAA0qC,CAA1qC,EAA6qC,CAA7qC,CAAgrC,IAAhrC,CAAqrC,CAArrC,EAAwrC,CAAxrC,CAA2rC,IAA3rC,CAAgsC,CAAhsC,EAAmsC,CAAnsC,CAAssC,IAAtsC,CAA2sC,CAA3sC,EAA8sC,CAA9sC,CAAitC,IAAjtC,CAAstC,CAAttC,EAAytC,CAAztC,CAA4tC,IAA5tC,CAAiuC,CAAjuC,EAAouC,CAApuC,CAAuuC,IAAvuC,CAA4uC,CAA5uC,EAA+uC,CAA/uC,CAAkvC,IAAlvC,CAAuvC,CAAvvC,EAA0vC,CAA1vC,CAA6vC,IAA7vC,CAAkwC,CAAlwC,EAAqwC,CAArwC,CAAwwC,IAAxwC,CAA6wC,CAA7wC,EAAgxC,CAAhxC,CAAmxC,IAAnxC,CAAwxC,CAAxxC,EAA2xC,CAA3xC,CAA8xC,IAA9xC,CAAmyC,CAAnyC,EAAsyC,CAAtyC,CAAyyC,IAAzyC,CAA8yC,CAA9yC,EAAizC,CAAjzC,CAAozC,IAApzC,CAAyzC,CAAzzC,EAA4zC,CAA5zC,CAA+zC,IAA/zC,CAAo0C,CAAp0C,EAAu0C,CAAv0C,CAA00C,IAA10C,CAA+0C,CAA/0C,EAAk1C,CAAl1C,CAAq1C,IAAr1C,CAA01C,CAA11C,EAA61C,CAA71C,CAAg2C,IAAh2C,CAAq2C,CAAr2C,EAAw2C,CAAx2C,CAA22C,IAA32C,CAAg3C,CAAh3C,EAAm3C,CAAn3C,CAAs3C,IAAt3C,CAA23C,CAA33C,EAA83C,CAA93C,CAAi4C,IAAj4C,CAAs4C,CAAt4C,EAAy4C,CAAz4C,CAA44C,IAA54C,CAAi5C,CAAj5C,EAAo5C,CAAp5C,CAAu5C,IAAv5C,CAA45C,CAA55C,EAA+5C,CAA/5C,CAAk6C,IAAl6C,CAAu6C,CAAv6C,EAA06C,CAA16C,CAA66C,IAA76C,CAAk7C,CAAl7C,EAAq7C,CAAr7C,CAAw7C,IAAx7C,CAA67C,CAA77C,EAAg8C,CAAh8C,CAAm8C,IAAn8C,CAAw8C,CAAx8C,EAA28C,CAA38C,CAA88C,IAA98C,CAAm9C,CAAn9C,EAAs9C,CAAt9C,CAAy9C,IAAz9C,CAA89C,CAA99C,EAAi+C,CAAj+C,CAAo+C,IAAp+C,CAAy+C,CAAz+C,EAA4+C,CAA5+C,CAA++C,IAA/+C,CAAo/C,CAAp/C,EAAu/C,CAAv/C,CAA0/C,IAA1/C,CAA+/C,CAA//C,EAAkgD,CAAlgD,CAAqgD,IAArgD,CAA0gD,CAA1gD,EAA6gD,CAA7gD,CAAghD,IAAhhD,CAAqhD,CAArhD,EAAwhD,CAAxhD,CAA2hD,IAA3hD,CAAgiD,CAAhiD,EAAmiD,CAAniD,CAAsiD,IAAtiD,CAA2iD,CAA3iD,EAA8iD,CAA9iD,CAAijD,IAAjjD,CAAsjD,CAAtjD,EAAyjD,CAAzjD,CAA4jD,IAA5jD,CAAikD,CAAjkD,EAAokD,CAApkD,CAAukD,IAAvkD,CAA4kD,CAA5kD,EAA+kD,CAA/kD,CAAklD,IAAllD,CAAulD,CAAvlD,EAA0lD,CAA1lD,CAA6lD,IAA7lD,CAAkmD,CAAlmD,EAAqmD,CAArmD,CAAwmD,IAAxmD,CAA6mD,CAA7mD,EAAgnD,CAAhnD,CAAmnD,IAAnnD,CAAwnD,CAAxnD,EAA2nD,CAA3nD,CAA8nD,IAA9nD,CAAmoD,CAAnoD,EAAsoD,CAAtoD,CAAyoD,IAAzoD,CAA8oD,CAA9oD,EAAipD,CAAjpD,CAAopD,IAAppD,CAAypD,CAAzpD,EAA4pD,CAA5pD,CAA+pD,IAA/pD,CAAoqD,CAApqD,EAAuqD,CAAvqD,CAA0qD,IAA1qD,CAA+qD,CAA/qD,EAAkrD,CAAlrD,CAAqrD,IAArrD,CAA0rD,CAA1rD,EAA6rD,CAA7rD,CAAgsD,IAAhsD,CAAqsD,CAArsD,EAAwsD,CAAxsD,CAA2sD,IAA3sD,CAAgtD,CAAhtD,EAAmtD,CAAntD,CAAstD,IAAttD,CAA2tD,CAA3tD,EAA8tD,CAA9tD,CAAiuD,IAAjuD,CAAsuD,CAAtuD,EAAyuD,CAAzuD,CAA4uD,IAA5uD,CAAivD,CAAjvD,EAAovD,CAApvD,CAAuvD,IAAvvD,CAA4vD,CAA5vD,EAA+vD,CAA/vD,CAAkwD,IAAlwD,CAAuwD,CAAvwD,EAA0wD,CAA1wD,CAA6wD,IAA7wD,CAAkxD,CAAlxD,EAAqxD,CAArxD,CAAwxD,IAAxxD,CAA6xD,CAA7xD,EAAgyD,CAAhyD,CAAmyD,IAAnyD,CAAwyD,CAAxyD,EAA2yD,CAA3yD,CAA8yD,IAA9yD,CAAmzD,CAAnzD,EAAszD,CAAtzD,CAAyzD,IAAzzD,CAA8zD,CAA9zD,EAAi0D,CAAj0D,CAAo0D,IAAp0D,CAAy0D,CAAz0D,EAA40D,CAA50D,CAA+0D,IAA/0D,CAAo1D,CAAp1D,EAAu1D,CAAv1D,CAA01D,IAA11D,CAA+1D,CAA/1D,EAAk2D,CAAl2D,CAAq2D,IAAr2D,CAA02D,CAA12D,EAA62D,CAA72D,CAAg3D,IAAh3D,CAAq3D,CAAr3D,EAAw3D,CAAx3D,CAA23D,IAA33D,CAAg4D,CAAh4D,EAAm4D,CAAn4D,CAAs4D,IAAt4D,CAA24D,CAA34D,EAA84D,CAA94D,CAAi5D,IAAj5D,CAAs5D,CAAt5D,EAAy5D,CAAz5D,CAA45D,IAA55D,CAAi6D,CAAj6D,EAAo6D,CAAp6D,CAAu6D,IAAv6D,CAA46D,CAA56D,EAA+6D,CAA/6D,CAAk7D,IAAl7D,CAAu7D,CAAv7D,EAA07D,CAA17D,CAA67D,IAA77D,CAAk8D,CAAl8D,EAAq8D,CAAr8D,CAAw8D,IAAx8D,CAA68D,CAA78D,EAAg9D,CAAh9D,CAAm9D,IAAn9D,CAAw9D,CAAx9D,EAA29D,CAA39D,CAA89D,IAA99D,CAAm+D,CAAn+D,EAAs+D,CAAt+D,CAAy+D,IAAz+D,CAA8+D,CAA9+D,EAAi/D,CAAj/D,CAAo/D,IAAp/D,CAAy/D,CAAz/D,EAA4/D,CAA5/D,CAA+/D,IAA//D,CAAogE,CAApgE,EAAugE,CAAvgE,CAA0gE,IAA1gE,CAA+gE,CAA/gE,EAAkhE,CAAlhE,CAAqhE,IAArhE,CAA0hE,CAA1hE,EAA6hE,CAA7hE,CAAgiE,IAAhiE,CAAqiE,CAAriE,EAAwiE,CAAxiE,CAA2iE,IAA3iE,CAAgjE,CAAhjE,EAAmjE,CAAnjE,CAAsjE,IAAtjE,CAA2jE,CAA3jE,EAA8jE,CAA9jE,CAAikE,IAAjkE,CAAskE,CAAtkE,EAAykE,CAAzkE,CAA4kE,IAA5kE,CAAilE,CAAjlE,EAAolE,CAAplE,CAAulE,IAAvlE,CAA4lE,CAA5lE,EAA+lE,CAA/lE,CAAkmE,IAAlmE,CAAumE,CAAvmE,EAA0mE,CAA1mE,CAA6mE,IAA7mE,CAAknE,CAAlnE,EAAqnE,CAArnE,CAAwnE,IAAxnE,CAA6nE,CAA7nE,EAAgoE,CAAhoE,CAAmoE,IAAnoE,CAAwoE,CAAxoE,EAA2oE,CAA3oE,CAA8oE,IAA9oE,CAAmpE,CAAnpE,EAAspE,CAAtpE,CAAypE,IAAzpE,CAA8pE,CAA9pE,EAAiqE,CAAjqE,CAAoqE,IAApqE,CAAyqE,CAAzqE,EAA4qE,CAA5qE,CAA+qE,IAA/qE,CAAorE,CAAprE,EAAurE,CAAvrE,CAA0rE,IAA1rE,CAA+rE,CAA/rE,EAAksE,CAAlsE,CAAqsE,IAArsE,CAA0sE,CAA1sE,EAA6sE,CAA7sE,CAAgtE,IAAhtE,CAAqtE,CAArtE,EAAwtE,CAAxtE,CAA2tE,IAA3tE,CAAguE,CAAhuE,EAAmuE,CAAnuE,CAAsuE,IAAtuE,CAA2uE,CAA3uE,EAA8uE,CAA9uE,CAAivE,IAAjvE,CAAsvE,CAAtvE,EAAyvE,CAAzvE,CAA4vE,IAA5vE,CAAiwE,CAAjwE,EAAowE,CAApwE,CAAuwE,IAAvwE,CAA4wE,CAA5wE,EAA+wE,CAA/wE,CAAkxE,IAAlxE,CAAuxE,CAAvxE,EAA0xE,CAA1xE,CAA6xE,IAA7xE,CAAkyE,CAAlyE,EAAqyE,CAAryE,CAAwyE,IAAxyE,CAA6yE,CAA7yE,EAAgzE,CAAhzE,CAAmzE,IAAnzE,CAAwzE,CAAxzE,EAA2zE,CAA3zE,CAA8zE,IAA9zE,CAAm0E,CAAn0E,EAAs0E,CAAt0E,CAAy0E,IAAz0E,CAA80E,CAA90E,EAAi1E,CAAj1E,CAAo1E,IAAp1E,CAAy1E,CAAz1E,EAA41E,CAA51E,CAA+1E,IAA/1E,CAAo2E,CAAp2E,EAAu2E,CAAv2E,CAA02E,IAA12E,CAA+2E,CAA/2E,EAAk3E,CAAl3E,CAAq3E,IAAr3E,CAA03E,CAA13E,EAA63E,CAA73E,CAAg4E,IAAh4E,CAAq4E,CAAr4E,EAAw4E,CAAx4E,CAA24E,IAA34E,CAAg5E,CAAh5E,EAAm5E,CAAn5E,CAAs5E,IAAt5E,CAA25E,CAA35E,EAA85E,CAA95E,CAAi6E,IAAj6E,CAAs6E,CAAt6E,EAAy6E,CAAz6E,CAA46E,IAA56E,CAAi7E,CAAj7E,EAAo7E,CAAp7E,CAAu7E,IAAv7E,CAA47E,CAA57E,EAA+7E,CAA/7E,CAAk8E,IAAl8E,CAAu8E,CAAv8E,EAA08E,CAA18E,CAA68E,IAA78E,CAAk9E,CAAl9E,EAAq9E,CAAr9E,CAAw9E,IAAx9E,CAA69E,CAA79E,EAAg+E,CAAh+E,CAAm+E,IAAn+E,CAAw+E,CAAx+E,EAA2+E,CAA3+E,CAA8+E,IAA9+E,CAAm/E,CAAn/E,EAAs/E,CAAt/E,CAAy/E,IAAz/E,CAA8/E,CAA9/E,EAAigF,CAAjgF,CAAogF,IAApgF,CAAygF,CAAzgF,EAA4gF,CAA5gF,CAA+gF,IAA/gF,CAAohF,CAAphF,EAAuhF,CAAvhF,CAA0hF,IAA1hF,CAA+hF,CAA/hF,EAAkiF,CAAliF,CAAqiF,IAAriF,CAA0iF,CAA1iF,EAA6iF,CAA7iF,CAAgjF,IAAhjF,CAAqjF,CAArjF,EAAwjF,CAAxjF,CAA2jF,IAA3jF,CAAgkF,CAAhkF,EAAmkF,CAAnkF,CAAskF,IAAtkF,CAA2kF,CAA3kF,EAA8kF,CAA9kF,CAAilF,IAAjlF,CAAslF,CAAtlF,EAAylF,CAAzlF,CAA4lF,IAA5lF,CAAimF,CAAjmF,EAAomF,CAApmF,CAAumF,IAAvmF,CAA4mF,CAA5mF,EAA+mF,CAA/mF,CAAknF,IAAlnF,CAAunF,CAAvnF,EAA0nF,CAA1nF,CAA6nF,IAA7nF,CAAkoF,CAAloF,EAAqoF,CAAroF,CAAwoF,IAAxoF,CAA6oF,CAA7oF,EAAgpF,CAAhpF,CAAmpF,IAAnpF,CAAwpF,CAAxpF,EAA2pF,CAA3pF,CAA8pF,IAA9pF,CAAmqF,CAAnqF,EAAsqF,CAAtqF,CAAyqF,IAAzqF,CAA8qF,CAA9qF,EAAirF,CAAjrF,CAAorF,IAAprF,CAAyrF,CAAzrF,EAA4rF,CAA5rF,CAA+rF,IAA/rF,CAAosF,CAApsF,EAAusF,CAAvsF,CAA0sF,IAA1sF,CAA+sF,CAA/sF,EAAktF,CAAltF,CAAqtF,IAArtF,CAA0tF,CAA1tF,EAA6tF,CAA7tF,CAAguF,IAAhuF,CAAquF,CAAruF,EAAwuF,CAAxuF,CAA2uF,IAA3uF,CAAgvF,CAAhvF,EAAmvF,CAAnvF,CAAsvF,IAAtvF,CAA2vF,CAA3vF,EAA8vF,CAA9vF,CAAiwF,IAAjwF,CAAswF,CAAtwF,EAAywF,CAAzwF,CAA4wF,IAA5wF,CAAixF,CAAjxF,EAAoxF,CAApxF,CAAuxF,IAAvxF,CAA4xF,CAA5xF,EAA+xF,CAA/xF,CAAkyF,IAAlyF,CAAuyF,CAAvyF,EAA0yF,CAA1yF,CAA6yF,IAA7yF,CAAkzF,CAAlzF,EAAqzF,CAArzF,CAAwzF,IAAxzF,CAA6zF,CAA7zF,EAAg0F,CAAh0F,CAAm0F,IAAn0F,CAAw0F,CAAx0F,EAA20F,CAA30F,CAA80F,IAA90F,CAAm1F,CAAn1F,EAAs1F,CAAt1F,CAAy1F,IAAz1F,CAA81F,CAA91F,EAAi2F,CAAj2F,CAAo2F,IAAp2F,CAAy2F,CAAz2F,EAA42F,CAA52F,CAA+2F,IAA/2F,CAAo3F,CAAp3F,EAAu3F,CAAv3F,CAA03F,IAA13F,CAA+3F,CAA/3F,EAAk4F,CAAl4F,CAAq4F,IAAr4F,CAA04F,CAA14F,EAA64F,CAA74F,CAAg5F,IAAh5F,CAAq5F,CAAr5F,EAAw5F,CAAx5F,CAA25F,IAA35F,CAAg6F,CAAh6F,EAAm6F,CAAn6F,CAAs6F,IAAt6F,CAA26F,CAA36F,EAA86F,CAA96F,CAAi7F,IAAj7F,CAAs7F,CAAt7F,EAAy7F,CAAz7F,CAA47F,IAA57F,CAAi8F,CAAj8F,EAAo8F,CAAp8F,CAAu8F,IAAv8F,CAA48F,CAA58F,EAA+8F,CAA/8F,CAAk9F,IAAl9F,CAAu9F,CAAv9F,EAA09F,CAA19F,CAA69F,IAA79F,CAAk+F,CAAl+F,EAAq+F,CAAr+F,CAAw+F,IAAx+F,CAA6+F,CAA7+F,EAAg/F,CAAh/F,CAAm/F,IAAn/F,CAAw/F,CAAx/F,EAA2/F,CAA3/F,CAA8/F,IAA9/F,CAAmgG,CAAngG,EAAsgG,CAAtgG,CAAygG,IAAzgG,CAA8gG,CAA9gG,EAAihG,CAAjhG,CAAohG,IAAphG,CAAyhG,CAAzhG,EAA4hG,CAA5hG,CAA+hG,IAA/hG,CAAoiG,CAApiG,EAAuiG,CAAviG,CAA0iG,IAA1iG,CAA+iG,CAA/iG,EAAkjG,CAAljG,CAAqjG,IAArjG,CAA0jG,CAA1jG,EAA6jG,CAA7jG,CAAgkG,IAAhkG,CAAqkG,CAArkG,EAAwkG,CAAxkG,CAA2kG,IAA3kG,CAAglG,CAAhlG,EAAmlG,CAAnlG,CAAslG,IAAtlG,CAA2lG,CAA3lG,EAA8lG,CAA9lG,CAAimG,IAAjmG,CAAsmG,CAAtmG,EAAymG,CAAzmG,CAA4mG,IAA5mG,CAAinG,CAAjnG,EAAonG,CAApnG,CAAunG,IAAvnG,CAA4nG,CAA5nG,EAA+nG,CAA/nG,CAAkoG,IAAloG,CAAuoG,CAAvoG,EAA0oG,CAA1oG,CAA6oG,IAA7oG,CAAkpG,CAAlpG,EAAqpG,CAArpG,CAAwpG,IAAxpG,CAA6pG,CAA7pG,EAAgqG,CAAhqG,CAAmqG,IAAnqG,CAAwqG,CAAxqG,EAA2qG,CAA3qG,CAA8qG,IAA9qG,CAAmrG,CAAnrG,EAAsrG,CAAtrG,CAAyrG,IAAzrG,CAA8rG,CAA9rG,EAAisG,CAAjsG,CAAosG,IAApsG,CAAysG,CAAzsG,EAA4sG,CAA5sG,CAA+sG,IAA/sG,CAAotG,CAAptG,EAAutG,CAAvtG,CAA0tG,IAA1tG,CAA+tG,CAA/tG,EAAkuG,CAAluG,CAAquG,IAAruG,CAA0uG,CAA1uG,EAA6uG,CAA7uG,CAAgvG,IAAhvG,CAAqvG,CAArvG,EAAwvG,CAAxvG,CAA2vG,IAA3vG,CAAgwG,CAAhwG,EAAmwG,CAAnwG,CAAswG,IAAtwG,CAA2wG,CAA3wG,EAA8wG,CAA9wG,CAAixG,IAAjxG,CAAsxG,CAAtxG,EAAyxG,CAAzxG,CAA4xG,IAA5xG,CAAiyG,CAAjyG,EAAoyG,CAApyG,CAAuyG,IAAvyG,CAA4yG,CAA5yG,EAA+yG,CAA/yG,CAAkzG,IAAlzG,CAAuzG,CAAvzG,EAA0zG,CAA1zG,CAA6zG,IAA7zG,CAAk0G,CAAl0G,EAAq0G,CAAr0G,CAAw0G,IAAx0G,CAA60G,CAA70G,EAAg1G,CAAh1G,CAAm1G,IAAn1G,CAAw1G,CAAx1G,EAA21G,CAA31G,CAA81G,IAA91G,CAAm2G,CAAn2G,EAAs2G,CAAt2G,CAAy2G,IAAz2G,CAA82G,CAA92G,EAAi3G,CAAj3G,CAAo3G,IAAp3G,CAAy3G,CAAz3G,EAA43G,CAA53G,CAA+3G,IAA/3G,CAAo4G,CAAp4G,EAAu4G,CAAv4G,CAA04G,IAA14G,CAA+4G,CAA/4G,EAAk5G,CAAl5G,CAAq5G,IAAr5G,CAA05G,CAA15G,EAA65G,CAA75G,CAAg6G,IAAh6G,CAAq6G,CAAr6G,EAAw6G,CAAx6G,CAA26G,IAA36G,CAAg7G,CAAh7G,EAAm7G,CAAn7G,CAAs7G,IAAt7G,CAA27G,CAA37G,EAA87G,CAA97G,CAAi8G,IAAj8G,CAAs8G,CAAt8G,EAAy8G,CAAz8G,CAA48G,IAA58G,CAAi9G,CAAj9G,EAAo9G,CAAp9G,CAAu9G,IAAv9G,CAA49G,CAA59G,EAA+9G,CAA/9G,CAAk+G,IAAl+G,CAAu+G,CAAv+G,EAA0+G,CAA1+G,CAA6+G,IAA7+G,CAAk/G,CAAl/G,EAAq/G,CAAr/G,CAAw/G,IAAx/G,CAA6/G,CAA7/G,EAAggH,CAAhgH,CAAmgH,IAAngH,CAAwgH,CAAxgH,EAA2gH,CAA3gH,CAA8gH,IAA9gH,CAAmhH,CAAnhH,EAAshH,CAAthH,CAAyhH,IAAzhH,CAA8hH,CAA9hH,EAAiiH,CAAjiH,CAAoiH,IAApiH,CAAyiH,CAAziH,EAA4iH,CAA5iH,CAA+iH,IAA/iH,CAAojH,CAApjH,EAAujH,CAAvjH,CAA0jH,IAA1jH,CAA+jH,CAA/jH,EAAkkH,CAAlkH,CAAqkH,IAArkH,CAA0kH,CAA1kH,EAA6kH,CAA7kH,CAAglH,IAAhlH,CAAqlH,CAArlH,EAAwlH,CAAxlH,CAA2lH,IAA3lH,CAAgmH,CAAhmH,EAAmmH,CAAnmH,CAAsmH,IAAtmH,CAA2mH,CAA3mH,EAA8mH,CAA9mH,CAAinH,IAAjnH,CAAsnH,CAAtnH,EAAynH,CAAznH,CAA4nH,IAA5nH,CAAioH,CAAjoH,EAAooH,CAApoH,CAAuoH,IAAvoH,CAA4oH,CAA5oH,EAA+oH,CAA/oH,CAAkpH,IAAlpH,CAAupH,CAAvpH,EAA0pH,CAA1pH,CAA6pH,IAA7pH,CAAkqH,CAAlqH,EAAqqH,CAArqH,CAAwqH,IAAxqH,CAA6qH,CAA7qH,EAAgrH,CAAhrH,CAAmrH,IAAnrH,CAAwrH,CAAxrH,EAA2rH,CAA3rH,CAA8rH,IAA9rH,CAAmsH,CAAnsH,EAAssH,CAAtsH,CAAysH,IAAzsH,CAA8sH,CAA9sH,EAAitH,CAAjtH,CAAotH,IAAptH,CAAytH,CAAztH,EAA4tH,CAA5tH,CAA+tH,IAA/tH,CAAouH,CAApuH,EAAuuH,CAAvuH,CAA0uH,IAA1uH,CAA+uH,CAA/uH,EAAkvH,CAAlvH,CAAqvH,IAArvH,CAA0vH,CAA1vH,EAA6vH,CAA7vH,CAAgwH,IAAhwH,CAAqwH,CAArwH,EAAwwH,CAAxwH,CAA2wH,IAA3wH,CAAgxH,CAAhxH,EAAmxH,CAAnxH,CAAsxH,IAAtxH,CAA2xH,CAA3xH,EAA8xH,CAA9xH,CAAiyH,IAAjyH,CAAsyH,CAAtyH,EAAyyH,CAAzyH,CAA4yH,IAA5yH,CAAizH,CAAjzH,EAAozH,CAApzH,CAAuzH,IAAvzH,CAA4zH,CAA5zH,EAA+zH,CAA/zH,CAAk0H,IAAl0H,CAAu0H,CAAv0H,EAA00H,CAA10H,CAA60H,IAA70H,CAAk1H,CAAl1H,EAAq1H,CAAr1H,CAAw1H,IAAx1H,CAA61H,CAA71H,EAAg2H,CAAh2H,CAAm2H,IAAn2H,CAAw2H,CAAx2H,EAA22H,CAA32H,CAA82H,IAA92H,CAAm3H,CAAn3H,EAAs3H,CAAt3H,CAAy3H,IAAz3H,CAA83H,CAA93H,EAAi4H,CAAj4H,CAAo4H,IAAp4H,CAAy4H,CAAz4H,EAA44H,CAA54H,CAA+4H,IAA/4H,CAAo5H,CAAp5H,EAAu5H,CAAv5H,CAA05H,IAA15H,CAA+5H,CAA/5H,EAAk6H,CAAl6H,CAAq6H,IAAr6H,CAA06H,CAA16H,EAA66H,CAA76H,CAAg7H,IAAh7H,CAAq7H,CAAr7H,EAAw7H,CAAx7H,CAA27H,IAA37H,CAAg8H,CAAh8H,EAAm8H,CAAn8H,CAAs8H,IAAt8H,CAA28H,CAA38H,EAA88H,CAA98H,CAAi9H,IAAj9H,CAAs9H,CAAt9H,EAAy9H,CAAz9H,CAA49H,IAA59H,CAAi+H,CAAj+H,EAAo+H,CAAp+H,CAAu+H,IAAv+H,CAA4+H,CAA5+H,EAA++H,CAA/+H,CAAk/H,IAAl/H,CAAu/H,CAAv/H,EAA0/H,CAA1/H,CAA6/H,IAA7/H,CAAkgI,CAAlgI,EAAqgI,CAArgI,CAAwgI,IAAxgI,CAA6gI,CAA7gI,EAAghI,CAAhhI,CAAmhI,IAAnhI,CAAwhI,CAAxhI,EAA2hI,CAA3hI,CAA8hI,IAA9hI,CAAmiI,CAAniI,EAAsiI,CAAtiI,CAAyiI,IAAziI,CAA8iI,CAA9iI,EAAijI,CAAjjI,CAAojI,IAApjI,CAAyjI,CAAzjI,EAA4jI,CAA5jI,CAA+jI,IAA/jI,CAAokI,CAApkI,EAAukI,CAAvkI,CAA0kI,IAA1kI,CAA+kI,CAA/kI,EAAklI,CAAllI,CAAqlI,IAArlI,CAA0lI,CAA1lI,EAA6lI,CAA7lI,CAAgmI,IAAhmI,CAAqmI,CAArmI,EAAwmI,CAAxmI,CAA2mI,IAA3mI,CAAgnI,CAAhnI,EAAmnI,CAAnnI,CAAsnI,IAAtnI,CAA2nI,CAA3nI,EAA8nI,CAA9nI,CAAioI,IAAjoI,CAAsoI,CAAtoI,EAAyoI,CAAzoI,CAA4oI,IAA5oI,CAAipI,CAAjpI,EAAopI,CAAppI,CAAupI,IAAvpI,CAA4pI,CAA5pI,EAA+pI,CAA/pI,CAAkqI,IAAlqI,CAAuqI,CAAvqI,EAA0qI,CAA1qI,CAA6qI,IAA7qI,CAAkrI,CAAlrI,EAAqrI,CAArrI,CAAwrI,IAAxrI,CAA6rI,CAA7rI,EAAgsI,CAAhsI,CAAmsI,IAAnsI,CAAwsI,CAAxsI,EAA2sI,CAA3sI,CAA8sI,IAA9sI,CAAmtI,CAAntI,EAAstI,CAAttI,CAAytI,IAAztI,CAA8tI,CAA9tI,

I,WAAW/b,IAAX,CAAgBoY,IAAI,CAAC2D,IAArB,CAAJ,EAAgC;AAC9BxR,QAAAAA,CAAC,CAACwF,OAAAF,IACE,oCACA,2BADA,GAEA,wCAHF;AAID,OALD,MAKO,IAAI,WAAW/P,IAAAX,CAAAgBoY,IAAI,CAAC2D,IAArB,CAAJ,EAAgC;AACrCxR,QAAAAA,CAAC,CAACwF,OAAAF,IACE,oCACA,2BADA,GAEA,wCAHF;AAID;AACF;;AACD,UAAMxF,CAAAN;AACD;;AAED,SAAO6R,MAAM,CAAC3G,IAAd;AACD;;ACvBD,SAAS4G,MAAT,GAAkB;AAAA,qBAAAC,SAAA,CAAAC,MAAA,EAAAC,IAAA,OAAAC,KAAA,CAAAH,IAAA,GAAAI,IAAA,MAAAA,IAAA,GAAAJ,IAAA,EAAAI,IAAA;AAAAF,IAAAA,IAAA,CAAAE,IAAA,IAAAJ,SAAA,CAAAI,IAAA;AAAA;;AAAA,SAAAF,IAAA,CAAAG,IAAA,CAAA,GAAA,CAAA;AAAA;;AAAA,SAAAC,QAAAC,GAAA,sCAAAD,OAAA,wBAAAE,MAAA,6BAAAA,MAAA,CAAAC,QAAA,aAAAF,GAAA,kBAAAA,GAAA,gBAAAC,MAAA,IAAAD,GAAA,CAAAG,WAAA,KAAAF,MAAA,IAAAD,GAAA,KAAAC,MAAA,CAAAG,SAAA,qBAAAJ,GAAA,KAAAD,OAAA,CAAAC,GAAA;AAAA;;AAAA,SAAAK,gBAAAC,QAAA,EAAAC,WAAA,UAAAD,QAAA,YAAAC,WAAA,eAAAC,SAAA;AAAA;;AAAA,SAAAC,kBAAAC,MAAA,EAAAC,KAAA,aAAAC,CAAA,MAAAA,CAAA,GAAAD,KAAA,CAAAb,MAAA,EAAAc,CAAA,IAAA,KAAAC,UAAA,GAAAF,KAAA,CAAAC,CAAA,GAAAC,UAAA,CAAAC,UAAA,GAAAD,UAAA,CAAAC,UAAA,WAAAD,UAAA,CAAAE,YAAA,wBAAAF,UAAA,EAAAA,UAAA,CAAAG,QAAA,SAAAC,MAAA,CAAAC,cAAA,CAAAR,MAAA,EAAAS,cAAA,CAAAN,UAAA,CAAAO,GAAA,GAAAP,UAAA;AAAA;;AAAA,SAAAQ,aAAAb,WAAA,EAAAc,UAAA,EAAAC,WAAA,WAAAD,UAAA,EAAAZ,iBAAA,CAAAF,WAAA,CAAAgB,SAAA,EAAAF,UAAA,GAAAC,WAAA,EAAAb,iBAAA,CAAAF,WAAA,EAAAe,WAAA,GAAAL,MAAA,CAAAC,cAAA,CAAAX,WAAA,iBAAAS,QAAA,mBAAAT,WAAA;AAAA;;AAAA,SAAAa,eAAAI,GAAA,QAAAT,GAAA,GAAAU,YAAA,CAAAD,GAAA,2BAAAT,GAAA,GAAAA,GAAA,GAAAW,MAAA,CAAAX,GAAA;AAAA;;AAAA,SAAAU,aAAAE,KAAA,EAAAC,IAAA,QAAAD,KAAA,kBAAAA,KAAA,kBAAAA,KAAA,MAAAE,IAAA,GAAAF,KAAA,CAAAG,MAAA,CAAAC,WAAA,OAAAF,IAAA,KAAAG,SAAA,QAAAC,GAAA,GAAAJ,IAAA,CAAAK,IAAA,CAAAP,KAAA,EAAAC,IAAA,2BAAAK,GAAA,sBAAAA,GAAA,YAAAE,SAAA,4DAAAP,IAAA,KAAAF,MAAA,GAAAU,MAAA,EAAAT,KAAA;AAAA;;AAAA,SAAAU,QAAAC,CAAA,EAAAC,CAAA,QAAAC,IAAA,GAAAlB,MAAA,CAAAkB,IAAA,CAAAF,CAAA,OAAAhB,MAAA,CAAAmB,qBAAA,QAAAC,CAAA,GAAApB,MAAA,CAAAmB,qBAAA,CAAAH,CAAA,GAAAC,CAAA,KAAAG,CAAA,GAAAA,CAAA,CAAAC,MAAA,WAAAJ,CAAA,WAAAjB,MAAA,CAAAsB,wBAAA,CAAAN,CAAA,EAAAC,CAAA,EAAAb,UAAA,OAAAc,IAAA,CAAAK,IAAA,CAAAC,KAAA,CAAAN,IAAA,EAAAE,CAAA,YAAAF,IAAA;AAAA;;AAAA,SAAAO,cAAAC,MAAA,aAAAV,CAAA,MAAAA,CAAA,GAAAW,SAAA,CAAAzC,MAAA,EAAA8B,CAAA,UAAAC,CAAA,WAAAU,SAAA,CAAAX,CAAA,IAAAW,SAAA,CAAAX,CAAA,QAAAA,CAAA,OAAAD,OAAA,CAAAb,MAAA,CAAAe,CAAA,OAAAW,OAAA,WAAAC,GAAA,IAAAC,eAAA,CAAAJ,MAAA,EAAAG,GAAA,EAAAZ,CAAA,CAAAY,GAAA,SAAA3B,MAAA,CAAA6B,yBAAA,GAAA7B,MAAA,CAAA8B,gBAAA,CAAAN,MAAA,EAAAxB,MAAA,CAAA6B,yBAAA,CAAAd,CAAA,KAAAF,OAAA,CAAAb,MAAA,CAAAe,CAAA,GAAAW,OAAA,WAAAC,GAAA,IAAA3B,MAAA,CAAAC,cAAA,CAAAuB,MAAA,EAAAG,GAAA,EAAA3B,MAAA,CAAAsB,wBAAA,CAAAP,CAAA,EAAAY,GAAA,iBAAAH,MAAA;AAAA;;AAAA,SAAAI,gBAAAlB,GAAA,EAAAiB,GAAA,EAAAlB,KAAA,IAAAkB,GAAA,GAAAb,cAAA,CAAAa,GAAA,OAAAA,GAAA,IAAAjB,GAAA,IAAAT,MAAA,CAAAC,cAAA,CAAAQ,GAAA,EAAAiB,GAAA,IAAAlB,KAAA,EAAAA,KAAA,EAAAX,UAAA,QAAA+B,YAAA,QAAAC,QAAA,oBAAApB,GAAA,CAAAiB,GAAA,IAAAlB,KAAA,WAAAC,GAAA;AAAA;;AAAA,SAAAS,gBAAAT,GAAA,EAAAiB,GAAA,EAAAlB,KAAA,IAAAkB,GAAA,GAAAb,cAAA,CAAAa,GAAA,OAAAA,GAAA,IAAAjB,GAAA,IAAAT,MAAA,CAAAC,cAAA,CAAAQ,GAAA,EAAAiB,GAAA,IAAAlB,KAAA,EAAAA,KAAA,EAAAX,UAAA,QAAA+B,YAAA,QAAAC,QAAA,oBAAApB,GAAA,CAAAiB,GAAA,IAAAlB,KAAA,WAAAC,GAAA;AAAA;;AAAA,SAAAqB,mBAAAC,GAAA,EAAAC,OAAA,EAAAC,MAAA,EAAAC,KAAA,EAAAC,MAAA,EAAAC,GAAA,EAAAC,GAAA,cAAAC,IAAA,GAAAN,GAAA,CAAAI,GAAA,EAAAC,GAAA,OAAA7B,KAAA,GAAA8B,IAAA,CAAA9B,KAAA,WAAA+B,GAAA,IAAAN,MAAA,CAAAM,GAAA,iBAAAD,IAAA,CAAAE,IAAA,IAAAR,OAAA,CAAAxB,KAAA,YAAAiC,OAAA,CAAAT,OAAA,CAAAxB,KAAA,EAAAkC,IAAA,CAAAP,KAAA,EAAAC,MAAA;AAAA;;AAAA,SAAAO,kBAAAC,EAAA,6BAAAC,IAAA,SAAAC,IAAA,GAAAlB,SAAA,aAAAW,OAAA,WAAAT,OAAA,EAAAC,MAAA,QAAAF,GAAA,GAAAe,EAAA,CAAAG,KAAA,CAAAF,IAAA,EAAAC,IAAA,YAAAT,MAAAhC,KAAA,IAAAuB,kBAAA,CAAAC,GAAA,EAAAC,OAAA,EAAAC,MAAA,EAAAC,KAAA,EAAAC,MAAA,UAAA5B,KAAA,cAAAgC,IAAAW,GAAA,IAAAnB,kBAAA,CAAAC,GAAA,EAAAC,OAAA,EAAAC,MAAA,EAAAC,KAAA,EAAAC,MAAA,WAAAa,GAAA,KAAAZ,KAAA,CAAAa,SAAA;AAAA;;AAAA,SAAAC

Af,IAA2B5W,IAAI,CAACoB,IAAL,CAAUiH,KAAK,CAACrI,IAAhB,CAA/B,EAAsD;AACpD,iBAAO4d,QAAAQ,CAACvV,KAAD,EAAQ7H,CAAR,CAAf;AACD;AACF,OAJM,CAAP;AAKD,KANM,MAMA;AACL,aAAO,KAAK2X,IAAL,CAAU,UAAC9P,KAAD,EAAQ7H,CAAR,EAAc;AAAE,iBAAO,CAACA,IAAI6H,KAAK,CAAC,CAAD,CAAT,GAAeA,KAAK,CAAC,CAAD,CAA3B;AAAiC,SAA9D,CAAP;AAAuE;AAAA,QAAAf,QAAA,CAAAA,KAAA,CAAAA,KAAA,CAAAA,K

,aAAKA,IAAI,CAACc,MAAL,GAAclC,SAAnB;AAAA,KAAvB;AACA,SAAKiB,KAAL,GAAa,EAAb;AACA,WAAO,IAAP;AACD;AAED;;;;;;;;;;;;;;;;;;;;;;;;;;;;;SA6BA+W,gBAAA,uBAAcC,OAAd,EAAuBjF,IAAvB,EAA6BoE,QAA7B,EAAuCC,QAAvC,EAAiDC,QAAjD,EAA2DC,QAA3D,EAAqEC,QAArE,EAA+EC,QAA/E,EAAyFC,QAAzF,EAAmGC,QAAnG,EAA6GC,QAA7G,EAAuHC,QAAvH,EAAiIC,QAAjI,EAA2IC,QAA3I,EAAqJC,QAArJ,EAA+JC,QAA/J,EAAyKC,QAAzK,EAAmLC,QAAnL,EAA6LC,QAA7L,EAAuMC,QAAvM,EAAiNC,QAAjN,EAA2NC,QAA3N,EAAqOC,QAArO,EAA+OC,QAA/O,EAAyPC,QAAzP,EAAmQC,QAAnQ,EAA6QC,QAA7Q,EAAuRC,QAAvR,EAAiSC,QAAjS,EAA2SC,QAA3S,EAAqTC,QAArT,EAA+TC,QAA/T,EAAyUC,QAAzU,EAAmVC,QAAnV,EAA6VC,QAA7V,EAAuWC,QAAvW,EAAiXC,QAAjX,EAA2XC,QAA3X,EAAqYC,QAArY,EAA+YC,QAA/Y,EAAyZC,QAAzZ,EAAma,QAAna,EAAoa,QAApa,EAA8a,QAA9a,EAAwb,QAAxb,EAAkc,QAAlc,EAA4c,QAA5c,EAAsd,QAAtd,EAAge,QAAhe,EAA0e,QAA1e,EAAof,QAApf,EAA8f,QAA9f,EAAwgB,QAAxgB,EAAkhB,QAAlhB,EAA4hB,QAA5hB,EAAsiB,QAAtiB,EAAgjB,QAAhjB,EAA0jB,QAA1jB,EAAokB,QAApkB,EAA8kB,QAA9kB,EAAwlB,QAAxlB,EAAkmB,QAAlmB,EAA4mB,QAA5mB,EAAsnB,QAAtnB,EAAgoB,QAAhoB,EAA0oB,QAA1oB,EAAopB,QAAppB,EAA8pB,QAA9pB,EAAwqB,QAAxqB,EAAkrB,QAAlrB,EAA4rB,QAA5rB,EAAssB,QAAtsB,EAAgtB,QAAhtB,EAA0tB,QAA1tB,EAAouB,QAApuB,EAA8uB,QAA9uB,EAAwvB,QAAxvB,EAAkwB,QAAlwB,EAA4wB,QAA5wB,EAAsxB,QAAtxB,EAAgyB,QAAhyB,EAA0yB,QAA1yB,EAAozB,QAApzB,EAA8zB,QAA9zB,EAAw0B,QAAx0B,EAAk1B,QAAl1B,EAA41B,QAA51B,EAAs2B,QAAt2B,EAAg3B,QAAh3B,EAA03B,QAA13B,EAAo4B,QAAp4B,EAA84B,QAA94B,EAAw5B,QAAx5B,EAAk6B,QAAl6B,EAA46B,QAA56B,EAAs7B,QAAt7B,EAAg8B,QAAh8B,EAA08B,QAA18B,EAAo9B,QAAp9B,EAA89B,QAA99B,EAAw+B,QAAx+B,EAAk/B,QAAl/B,EAA4/B,QAA5/B,EAAshC,QAAthC,EAAgiC,QAAhiC,EAA0iC,QAA1iC,EAAojC,QAApjC,EAA8jC,QAA9jC,EAAwkC,QAAxkC,EAAklC,QAAllC,EAA4lC,QAA5lC,EAAsmC,QAAtmC,EAAgnC,QAAhnC,EAA0nC,QAA1nC,EAAooC,QAApoC,EAA8oC,QAA9oC,EAAwpC,QAAxpC,EAAkqC,QAAlqC,EAA4qC,QAA5qC,EAAsrC,QAAtrC,EAAgsC,QAAhsC,EAA0sC,QAA1sC,EAAotC,QAAptC,EAA8tC,QAA9tC,EAAwuC,QAAxuC,EAAkvC,QAAlvC,EAA4vC,QAA5vC,EAAswC,QAAtwC,EAAgxC,QAAhxC,EAA0xC,QAA1xC,EAAoyC,QAApyC,EAA8yC,QAA9yC,EAAwzC,QAAxzC,EAAk0C,QAAl0C,EAA40C,QAA50C,EAAs1C,QAAt1C,EAAg2C,QAAh2C,EAA02C,QAA12C,EAAo3C,QAAp3C,EAA83C,QAA93C,EAAw4C,QAAx4C,EAAk5C,QAAl5C,EAA45C,QAA55C,EAAs6C,QAAt6C,EAAg7C,QAAh7C,EAA07C,QAA17C,EAAo8C,QAAp8C,EAA88C,QAA98C,EAAw9C,QAAx9C,EAAk+C,QAAl+C,EAA4+C,QAA5+C,EAAs/C,QAAt/C,EAAggD,QAAhgD,EAA0gD,QAA1gD,EAAohD,QAAphD,EAA8hD,QAA9hD,EAAwiD,QAAxiD,EAAkjD,QAAljD,EAA4jD,QAA5jD,EAAskD,QAAtkD,EAAglD,QAAhlD,EAA0lD,QAA1lD,EAAomD,QAApmD,EAA8mD,QAA9mD,EAAwnD,QAAxnD,EAAkoD,QAAloD,EAA4oD,QAA5oD,EAAspD,QAAtpD,EAAgqD,QAAhqD,EAA0qD,QAA1qD,EAAorD,QAAprD,EAA8rD,QAA9rD,EAAwsD,QAAxsD,EAAktD,QAAltD,EAA4tD,QAA5tD,EAAsuD,QAAtuD,EAAgvD,QAAhvD,EAA0vD,QAA1vD,EAAowD,QAApwD,EAA8wD,QAA9wD,EAAwxD,QAAxxD,EAAkyD,QAAlyD,EAA4yD,QAA5yD,EAAszD,QAAtzD,EAAg0D,QAAh0D,EAA00D,QAA10D,EAAo1D,QAAp1D,EAA81D,QAA91D,EAAw2D,QAAx2D,EAAk3D,QAAl3D,EAA43D,QAA53D,EAAs4D,QAAt4D,EAAg5D,QAAh5D,EAA05D,QAA15D,EAAo6D,QAAp6D,EAA86D,QAA96D,EAAw7D,QAAx7D,EAAk8D,QAAl8D,EAA48D,QAA58D,EAAs9D,QAAt9D,EAAg+D,QAAh+D,EAA0+D,QAA1+D,EAAo/D,QAAp/D,EAA8/D,QAA9/D,EAAwgE,QAAxgE,EAAkhE,QAAlhE,EAA4hE,QAA5hE,EAAsiE,QAAtiE,EAAgjE,QAAhjE,EAA0jE,QAA1jE,EAAokE,QAApkE,EAA8kE,QAA9kE,EAAwlE,QAAxlE,EAAkmE,QAAlmE,EAA4mE,QAA5mE,EAAsnE,QAAtnE,EAAgoE,QAAhoE,EAA0oE,QAA1oE,EAAopE,QAAppE,EAA8pE,QAA9pE,EAAwqE,QAAxqE,EAAkrE,QAAlrE,EAA4rE,QAA5rE,EAAssE,QAAtsE,EAAgtE,QAAhtE,EAA0tE,QAA1tE,EAAouE,QAApuE,EAA8uE,QAA9uE,EAAwvE,QAAxvE,EAAkwE,QAAlwE,EAA4wE,QAA5wE,EAAsxE,QAAtxE,EAAgyE,QAAhyE,EAA0yE,QAA1yE,EAAozE,QAApzE,EAA8zE,QAA9zE,EAAw0E,QAAx0E,EAAk1E,QAAl1E,EAA41E,QAA51E,EAAs2E,QAAt2E,EAAg3E,QAAh3E,EAA03E,QAA13E,EAAo4E,QAAp4E,EAA84E,QAA94E,EAAw5E,QAAx5E,EAAk6E,QAAl6E,EAA46E,QAA56E,EAAs7E,QAAt7E,EAAg8E,QAAh8E,EAA08E,QAA18E,EAAo9E,QAAp9E,EAA89E,QAA99E,EAAw+E,QAAx+E,EAAk/E,QAAl/E,EAA4/E,QAA5/E,EAAshF,QAAthF,EAAgiF,QAAhiF,EAA0iF,QAA1iF,EAAojF,QAApjF,EAA8jF,QAA9jF,EAAwkF,QAAxkF,EAAklF,QAAllF,EAA4lF,QAA5lF,EAAsmF,QAAtmF,EAAgnF,QAAhnF,EAA0nF,QAA1nF,EAAooF,QAApoF,EAA8oF,QAA9oF,EAAwpF,QAAxpF,EAAkqF,QAAlqF,EAA4qF,QAA5qF,EAAsrF,QAAtrF,EAAgsF,QAAhsF,EAA0sF,QAA1sF,EAAotF,QAAptF,EAA8tF,QAA9tF,EAAwuF,QAAxuF,EAAkvF,QAAlvF,EAA4vF,QAA5vF,EAAswF,QAAtwF,EAAgxF,QAAhxF,EAA0xF,QAA1xF,EAAoyF,QAApyF,EAA8yF,QAA9yF,EAAwzF,QAAxzF,EAAk0F,QAAl0F,EAA40F,QAA50F,EAAs1F,QAAt1F,EAAg2F,QAAh2F,EAA02F,QAA12F,EAAo3F,QAAp3F,EAA83F,QAA93F,EAAw4F,QAAx4F,EAAk5F,QAAl5F,EAA45F,QAA55F,EAAs6F,QAAt6F,EAAg7F,QAAh7F,EAA07F,QAA17F,EAAo8F,QAAp8F,EAA88F,QAA98F,EAAw9F,QAAx9F,EAAk+F,QAAl+F,EAA4+F,QAA5+F,EAAs/F,QAAt/F,EAAggG,QAAhgG,EAA0gG,QAA1gG,EAAohG,QAAphG,EAA8hG,QAA9hG,EAAwiG,QAAxiG,EAAkjG,QAAljG,EAA4jG,QAA5jG,EAAskG,QAAtkG,EAAglG,QAAhlG,EAA0lG,QAA1lG,EAAomG,QAApmG,EAA8mG,QAA9mG,EAAwnG,QAAxnG,EAAkoG,QAAloG,EAA4oG,QAA5oG,EAAspG,QAAtpG,EAAgqG,QAAhqG,EAA0qG,QAA1qG,EAAorG,QAAprG,EAA8rG,QAA9rG,EAAwsG,QAAxsG,EAAktG,QAAltG,EAA4tG,QAA5tG,EAAsuG,QAAtuG,EAAgvG,QAAhvG,EAA0vG,QAA1vG,EAAowG,QAApwG,EAA8wG,QAA9wG,EAAwxG,QAAxxG,EAAkyG,QAAlyG,EAA4yG,QAA5yG,EAAszG,QAAtzG,EAAg0G,QAAh0G,EAA00G,QAA10G,EAAo1G,QAAp1G,EAA81G,QAA91G,EAAw2G,QAAx2G,EAAk3G,QAAl3G,EAA43G,QAA53G,EAAs4G,QAAt4G,EAAg5G,QAAh5G,EAA05G,QAA15G,EAAo6G,QAAp6G,EAA86G,QAA96G,EAAw7G,QAAx7G,EAAk8G,QAAl8G,EAA48G,QAA58G,EAAs9G,QAAt9G,EAAg+G,QAAh+G,EAA0+G,QAA1+G,EAAo/G,QAAp/G,EAA8/G,QAA9/G,EAAwgH,QAAxgH,EAAkhH,QAAlhH,EAA4hH,QAA5hH,EAAsiH,QAAtiH,EAAgjH,QAAhjH,EAA0jH,QAA1jH,EAAokH,QAApkH,EAA8kH,QAA9kH,EAAwlH,QAAxlH,EAAkmH,QAAlmH,EAA4mH,QAA5mH,EAAsnH,QAAtnH,EAAgoH,QAAhoH,EAA0oH,QAA1oH,EAAopH,QAAppH,EAA8pH,QAA9pH,EAAwqH,QAAxqH,EAAkrH,QAAlrH,EAA4rH,QAA5rH,EAAssH,QAAtsH,EAAgtH,QAAhtH,EAA0tH,QAA1tH,EAAouH,QAApuH,EAA8uH,QAA9uH,EAAwvH,QAAxvH,EAAkwH,QAAlwH,EAA4wH,QAA5wH,EAAsxH,QAAtxH,EAAgyH,QAAhyH,EAA0yH,QAA1yH,EAAozH,QAApzH,EAA8zH,QAA9zH,EAAw0H,QAAx0H,EAAk1H,QAAl1H,EAA41H,QAA51H,EAAs2H,QAAt2H,EAAg3H,QAAh3H,EAA03H,QAA13H,EAAo4H,QAAp4H,EAA84H,QAA94H,EAAw5H,QAAx5H,EAAk6H,QAAl6H,EAA46H,QAA56H,EAAs7H,QAAt7H,EAAg8H,QAAh8H,EAA08H,QAA18H,EAAo9H,QAAp9H,EAA89H,QAA99H,EAAw+H,QAAx+H,EAAk/H,QAAl/H,EAA4/H,QAA5/H,EAAshI,QAAthI,EAAgiI,QAAhiI,EAA0iI,QAA1iI,EAAojI,QAApjI,EAA8jI,QAA9jI,EAAwkI,QAAxkI,EAAklI,QAAllI,EAA4lI,QAA5lI,EAAsmI,QAAtmI,EAAgnI,QAAhnI,EAA0nI,QAA1nI,EAAooI,QAApoI,EAA8oI,QAA9oI,EAAwpI,QAAxpI,EAAkqI,QAAlqI,EAA4qI,QAA5qI,EAAsrI,QAAtrI,EAAgsI,QAAhsI,EAA0sI,QAA1sI,EAAotI,QAAptI,EAA8tI,QAA9tI,EAAwuI,QAAxuI,EAAkvI,QAAlvI,EAA4vI,QAA5vI,EAAswI,QAAtwI,EAAgxI,QAAhxI,EAA0xI,QAA1xI,EAAoyI,QAApyI,EAA8yI,QAA9yI,EAAwzI,QAAxzI,EAAk0I,QAAl0I,EAA40I,QAA50I,EAAs1I,QAAt1I,EAAg2I,QAAh2I,EAA02I,QAA12I,EAAo3I,QAAp3I,EAA83I,QAA93I,EAAw4I,QAAx4I,EAAk5I,QAAl5I,EAA45I,QAA55I,EAAs6I,QAAt6I,EAAg7I,QAAh7I,EAA07I,QAA17I,EAAo8I,QAAp8I,EAA88I,QAA98I,EAAw9I,QAAx9I,EAAk+I,QAAl+I,EAA4+I,QAA5+I,EAAs/I,QAAt/I,EAAggJ,QAAhgJ,EAA0gJ,QAA1gJ,EAAohJ,QAAphJ,EAA8hJ,QAA9hJ,EAAwiJ,QAAxiJ,EAAkjJ,QAAljJ,EAA4jJ,QAA5jJ,EAAskJ,QAAtkJ,EAAglJ,QAAhlJ,EAA0lJ,QAA1lJ,EAAomJ,QAApmJ,EAA8mJ,QAA9mJ,EAAwnJ,QAAxnJ,EAAkoJ,QAAloJ,EAA4oJ,QAA5oJ,EAAspJ,QAAtpJ,EAAgqJ,QAAhqJ,EAA0qJ,QAA1qJ,EAAorJ,QAAprJ,EAA8rJ,QAA9rJ,EAAwsJ,QAAxsJ,EAAktJ,QAAltJ,EAA4tJ,QAA5tJ,EAAsuJ,QAAtuJ,EAAgvJ,QAAhvJ,EAA0vJ,QAA1vJ,EAAowJ,QAApwJ,EAA8wJ,QAA9wJ,EAAwxJ,QAAxxJ,EAAkyJ,QAAlyJ,EAA4yJ,QAA5yJ,EAAszJ,QAAtzJ,EAAg0J,QAAh0J,EAA00J,QAA10J,EAAo1J,QAAp1J,EAA81J,QAA91J,EAAw2J,QAAx2J,EAAk3J,QAAl3J,EAA43J,QAA53J,EAAs4J,QAAt4J,EAAg5J,QAAh5J,EAA05J,QAA15J,EAAo6J,QAAp6J,EAA86J,QAA96J,EAAw7J,QAAx7J,EAAk8J,QAAl8J,EAA48J,QAA58J,EAAs9J,QAAt9J,EAAg+J,QAAh+J,EAA0+J,QAA1+J,EAAo/J,QAAp/J,EAA8/J,QAA9/J,EAAwgK,QAAxgK,EAAkhK,QAAlhK,EAA4hK,QAA5hK,EAAsiK,QAAtiK,EAAgjK,QAAhjK,EAA0jK,QAA1jK,EAAokK,QAApkK,EAA8kK,QAA9kK,EAAwlK,QAAxlK,EAAkmK,QAAlmK,EAA4mK,QAA5mK,EAAsnK,QAAtnK,EAAgoK,QAAhoK,EAA0oK,QAA1oK,EAAopK,QAAppK,EAA8pK,QAA9pK,EAAwqK,QAAxqK,EAAkrK,QAAlrK,EAA4rK,QAA5rK,EAAssK,QAAtsK,EAAgtK,QAAhtK,EAA0tK,QAA1tK,EAAouK,QAApuK,EAA8uK,QAA9uK,EAAwvK,QAAxvK,EAAkwK,QAAlwK,EAA4wK,QAA5wK,EAAsxK,QAAtxK,EAAgyK,QAAhyK,EAA0yK,QAA1yK,EAAozK,QAApzK,EAA8zK,QAA9zK,EAAw0K,QAAx0K,EAAk1K,QAAl1K,EAA41K,QAA51K,EAAs2K,QAAt2K,EAAg3K,QAAh3K,EAA03K,QAA13K,EAAo4K,QAAp4K,EAA84K,QAA94K,EAAw5K,QAAx5K,EAAk6K,QAAl6K,EAA46K,QAA56K,EAAs7K,QAAt7K,EAAg8K,QAAh8K,EAA08K,QAA18K,EAAo9K,QAAp9K,EAA89K,QAA99K,EAAw+K,QAAx+K,EAAk/K,QAAl/K,EAA4/K,QAA5/K,EAAshL,QAAthL,EAAgiL,QAAhiL,EAA0iL,QAA1iL,EAAojL,QAApjL,EAA8jL,QAA9jL,EAAwkL,QAAxkL,EAAklL,QAAllL,EAA4lL,QAA5lL,EAAsmL,QAAtmL,EAAgnL,QAAhnL,EAA0nL,QAA1nL,EAAooL,QAApoL,EAA8oL,QAA9oL,EAAwpL,QAAxpL,EAAkqL,QAAlqL,EAA4qL,QAA5qL,EAAsrL,QAAtrL,EAAgsL,QAAhsL,EAA0sL,QAA1sL,EAAotL,QAAptL,EAA8tL,QAA9tL,EAAwuL,QAAxuL,EAAkvL,QAAlvL,EAA4vL,QAA5vL,EAAswL,QAAtwL,EAAgxL,QAAhxL,EAA0xL,QAA1xL,EAAoyL,QAApyL,EAA8yL,QAA9yL,EAAwzL,QAAxzL,EAAk0L,QAAl0L,EAA40L,QAA50L,EAAs1L,QAAt1L,EAAg2L,QAAh2L,EAA02L,QAA12L,EAAo3L,QAAp3L,EAA83L,QAA93L,EAAw4L,QAAx4L,EAAk5L,QAAl5L,EAA45L,QAA55L,EAAs6L,QAAt6L,EAAg7L,QAAh7L,EAA07L,QAA17L,EAAo8L,QAAp8L,EAA88L,QAA98L,EAAw9L,QAAx9L,EAAk+L,QAAl+L,EAA4+L,QAA5+L,EAAs/L,QAAt/L,EAAggM,QAAhgM,EAA0gM,QAA1gM,EAAohM,QAAphM,EAA8hM,QAA9hM,EAAwiM,QAAxiM,EAAkjM,QAAljM,EAA4jM,QAA5jM,EAAskM,QAAtkM,EAAglM,QAAhlM,EAA0lM,QAA1lM,EAAomM,QAApmM,EAA8mM,QAA9mM,EAAwnM,QAAxnM,EAAkoM,QAAloM,EAA4oM,QAA5oM,EAAspM,QAAtpM,EAAgqM,QAAhqM,EAA0qM,QAA1qM,EAAorM,QAAprM,EAA8rM,QAA9rM,EAAwsM,QAAxsM,EAAktM,QAAltM,EAA4tM,QAA5tM,EAAsuM,QAAtuM,EAAgvM,QAAhvM,EAA0vM,QAA1vM,EAAowM,QAApwM,EAA8wM,QAA9wM,EAAwxM,QAAxxM,EAAkyM,QAAlyM,EAA4yM,QAA5yM,EAAszM,QAAtzM,EAAg0M,QAAh0M,EAA00M,QAA10M,EAAo1M,QAAp1M,EAA81M,QAA91M,EAAw2M,QAAx2M,EAAk3M,QAAl3M,EAA43M,QAA53M,EAAs4M,QAAt4M,EAAg5M,QAAh5M,EAA05M,QAA15M,EAAo6M,QAAp6M,EAA86M,QAA96M,EAAw7M,QAAx7M,EAAk8M,QAAl8M,EAA48M,QAA58M,EAAs9M,QAAt9M,EAAg+M,QAAh+M,EAA0+M,QAA1+M,EAAo/M,QAAp/M,EAA8/M,QAA9/M,EAAwgN,QAAxgN,EAAkhN,QAAlhN,EAA4hN,QAA5hN,EAAsiN,QAAtiN,EAAgjN,QAAhjN,EAA0jN,QAA1jN,EAAokN,QAApkN,EAA8kN,QAA9kN,EAAwlN,QAAxlN,EAAkmN,QAAlmN,EAA4mN,QAA5mN,EAAsnN,QAAtnN,EAAgoN,QAAhoN,EAA0oN,QAA1oN,EAAopN,QAAppN,EAA8pN,QAA9pN,EAAwqN,QAAxqN,EAAkrN,QAAlrN,EAA4rN,QAA5rN,EAAssN,QAAtsN,EAAgtN,QAAhtN,EAA0tN,QAA1tN,EAAouN,QAApuN,EAA8uN,QAA9uN,EAAwvN,QAAxvN,EAAkwN,QAAlwN,EAA4wN,QAA5wN,EAAsxN,QAAtxN,EAAgyN,QAAhyN,EAA0yN,QAA1yN,EAAozN,QAApzN,EAA8zN,QAA9zN,EAAw0N,QAAx0N,EAAk1N,QAAl1N,EAA41N,QAA51N,EAAs2N,QAAt2N,EAAg3N,QAAh3N,EAA03N,QAA13N,EAAo4N,QAAp4N,EAA84N,QAA94N,EAAw5N,QAAx5N,EAAk6N,QAAl6N,EAA46N,QAA56N,EAAs7N,QAAt7N,EAAg8N,QAAh8N,EAA08N,QAA18N,EAAo9N,QAAp9N,EAA89N,QAA99N,EAAw+N,QAAx+N,EAAk/N,QAAl/N,EAA4/N,QAA5/N,EAAshO,QAAthO,EAAgiO,QAAhiO,EAA0iO,QAA1iO,EAAojO,QAApjO,EAA8jO,QAA9jO,EAAwkO,QAAxkO,EAAklO,QAAllO,EAA4lO,QAA5lO,EAAsmO,QAAtmO,EAAgnO,QAAhnO,EAA0nO,QAA1nO,EAAooO,QAApoO,EAA8oO,QAA9oO,EAAwpO,QAAxpO,EAAkqO,QAAlqO,EAA4qO,QAA5qO,EAAsrO,QAAtrO,EAAgsO,QAAhsO,EAA0sO,QAA1sO,EAAotO,QAAptO,EAA8tO,QAA9tO,EAAwuO,QAAxuO,EAAkvO,QAAlvO,EAA4vO,QAA5vO,EAAswO,QAAtwO,EAAgxO,QAAhxO,EAA0xO,QAA1xO,EAAoyO,QAApyO,EAA8yO,QAA9yO,EAAwzO,QAAxzO,EAAk0O,QAAl0O,EAA40O,QAA50O,EAAs1O,QAAt1O,EAAg2O,QAAh2O,EAA02O,QAA12O,EAAo3O,QAAp3O,EAA83O,QAA93O,EAAw4O,QAAx4O,EAAk5O,QAAl5O,EAA45O,QAA55O,EAAs6O,QAAt6O,EAAg7O,QAAh7O,EAA07O,QAA17O,EAAo8O,QAAp8O,EAA88O,QAA98O,EAAw9O,QAAx9O,EAAk+O,QAAl+O,EAA4+O,QAA5+O,EAAs/O,QAAt/O,EAAggP,QAAhgP,EAA0gP,QAA1gP,EAAohP,QAAphP,EAA8hP,QAA9hP,EAAwiP,QAAxiP,EAAkjP,QAAljP,EAA4jP,QAA5jP,EAAskP,QAAtkP,EAAglP,QAAhlP,EAA0lP,QAA1lP,EAAomP,QAApmP,EAA8mP,QAA9mP,EAAwnP,QAAxnP,EAAkoP,QAAloP,EAA4oP,QAA5oP,EAAspP,QAAtpP,EAAgqP,QAAhqP,EAA0qP,QAA1qP,EAAorP,QAAprP,EAA8rP,QAA9rP,EAAwsP,QAAxsP,EAAktP,QAAltP,EAA4tP,QAA5tP,EAAsuP,QAAtuP,EAAgvP,QAAhvP,EAA0vP,QAA1vP,EAAowP,QAApwP,EAA8wP,QAA9wP,EAAwxP,QAAxxP,EAAkyP,QAAlyP,EAA4yP,QAA5yP,EAAszP,QAAtzP,EAAg0P,QAAh0P,EAA00P,QAA10P,EAAo1P,QAAp1P,EAA81P,QAA91P,EAAw2P,QAAx2P,EAAk3P,QAAl3P,EAA43P,QAA53P,EAAs4P,QAAt4P,EAAg5P,QAAh5P,EAA05P,QAA15P,EAAo6P,QAAp6P,EAA86P,QAA96P,EAAw7P,QAAx7P,EAAk8P,QAAl8P,EAA48P,QAA58P,EAAs9P,QAAt9P,EAAg+P,QAAh+P,EAA0+P,QAA1+P,EAAo/P,QAAp/P,EAA8/P,QAA9/P,EAAwgQ,QAAxgQ,EAAkhQ,QAAlhQ,EAA4hQ,QAA5hQ,EAAsiQ,QAAtiQ,EAAgjQ,QAAhjQ,EAA0jQ,QAA1jQ,EAAokQ,QAApkQ,EAA8kQ,QAA9kQ,EAAwlQ,QAAxlQ,EAAkmQ,QAAlmQ,EAA4mQ,QAA5mQ,EAAsnQ,QAAtnQ,EAAgoQ,QAAhoQ,EAA0oQ,QAA1oQ,EAAopQ,QAAppQ,EAA8pQ,QAA9pQ,EAAwqQ,QAAxqQ,EAAkrQ,QAAlrQ,EAA4rQ,QAA5rQ,EAAssQ,QAAtsQ,EAAgtQ,QAAhtQ,EAA0tQ,QAA1tQ,EAAouQ,QAApuQ,EAA8uQ,QAA9uQ,EAAwvQ,QAAxvQ,EAAkwQ,QAAlwQ,EAA4wQ,QAA5wQ,EAAsxQ,QAAtxQ,EAAgyQ,QAAhyQ,EAA0yQ,QAA1yQ,EAAozQ,QAApzQ,EAA8zQ,QAA9zQ,EAAw0Q,QAAx0Q,EAAk1Q,QAAl1Q,EAA41Q,QAA51Q,EAAs2Q,QAAt2Q,EAAg3Q,QAAh3Q,EAA03Q,QAA13Q,EAAo4Q,QAAp4Q,EAA84Q,QAA94Q,EAAw5Q,QAAx5Q,EAAk6Q,QAAl6Q,EAA46Q,QAA56Q,EAAs7Q,QAAt7Q,EAAg8Q,QAAh8Q,EAA08Q,QAA18Q,EAAo9Q,QAAp9Q,EAA89Q,QAA99Q,EAAw+Q,QAAx+Q,EAAk/Q,QAAl/Q,EAA4/Q,QAA5/Q,EAAshR,QAAthR,EAAgiR,QAAhiR,EAA0iR,QAA1iR,EAAojR,QAApjR,EAA8jR,QAA9jR,EAAwkR,QAAxkR,EAAklR,QAAllR,EAA4lR,QAA5lR,EAAsmR,QAAtmR,EAAgnR,QAAhnR,EAA0nR,QAA1nR,EAAooR,QAApoR,EAA8oR,QAA9oR,EAAwpR,QAAxpR,EAAkqR,QAAlqR,EAA4qR,QAA5qR,EAAsrR,QAAtrR,EAAgsR,QAAhsR,EAA0sR,QAA1sR,EAAotR,QAAptR,EAA8tR,QAA9tR,EAAwuR,QAAxuR,EAAkvR,QAAlvR,EAA4vR,QAA5vR,EAAswR,QAAtwR,EAAgxR,QAAhxR,EAA0xR,QAA1xR,EAAoyR,QAApyR,EAA8yR,QAA9yR,EAAwzR,QAAxzR,EAAk0R,QAAl0R,EAA40R,QAA50R,EAAs1R,QAAt1R,EAAg2R,QAAh2R,EAA02R,QAA12R,EAAo3R,QAAp3R,EAA83R,QAA93R,EAAw4R,QAAx4R,EAAk5R,QAAl5R,EAA45R,QAA55R,EAAs6R,QAAt6R,EAAg7R,QAAh7R,EAA07R,QAA17R,EAAo8R,QAAp8R,EAA88R,QAA98R,EAAw9R,QAAx9R,EAAk+R,QAAl+R,EAA4+R,QAA5+R,EAAs/R,QAAt/R,EAAggS,QAAhgS,EAA0gS,QAA1gS,EAAohS,QAAphS,EAA8hS,QAA9hS,EAAwiS,QAAxiS,EAAkjS,QAAljS,EAA4jS,QAA5jS,EAAskS,QAAtkS,EAAglS,QAAhlS,EAA0lS,QAA1lS,EAAomS,QAApmS,EAA8mS,QAA9mS,EAAwnS,QAAxnS,EAAkoS,QAAloS,EAA4oS,QAA5oS,EAAspS,QAAtpS,EAAgqS,QAAhqS,EAA0qS,QAA1qS,EAAorS,QAAprS,EAA8rS,QAA9rS,EAAwsS,QAAxsS,EAAktS,QAAltS,EAA4tS,QAA5tS,EAAsuS,QAAtuS,EAAgvS,QAAhvS,EAA0vS,QAA1vS,EAAowS,QAApwS,EAA8wS,QAA9wS,EAAwxS,QAAxxS,EAAkyS,QAAlyS,EAA4yS,QAA5yS,EAAszS,QAAtzS,EAAg0S,QAAh0S,EAA00S,QAA10S,EAAo1S,QAAp1S,EAA81S,QAA91S,EAAw2S,QAAx2S,EAAk3S,QAAl3S,EAA43S,QAA53S,EAAs4S,QAAt4S,EAAg5S,QAAh5S,EAA05S,QAA15S,EAAo6S,QAAp6S,EAA86S,QAA96S,EAAw7S,QAAx7S,EAAk8S,QAAl8S,EAA48S,QAA58S,EAAs9S,QAAt9S,EAAg+S,QAAh+S,EAA0+S,QAA1+S,EAAo/S,QAAp/S,EAA8/S,QAA9/S,EAAwgT,QAAxgT,EAAkhT,QAAlhT,EAA4hT,QAA5hT,EAAsiT,QAAtiT,EAAgjT,QAAhjT,EAA0jT,QAA1jT,EAAokT,QAApkT,EAA8kT,QAA9kT,EAAwlT,QAAxlT,EAAkmT,QAAlmT,EAA4mT,QAA5mT,EAAsnT,QAAtnT,EAAgoT,QAAhoT,EAA0oT,QAA1oT,EAAopT,QAAppT,EAA8pT,QAA9pT,EAAwqT,QAAxqT,EAAkrT,QAAlrT,EAA4rT,QAA5rT,EAAssT,QAAtsT,EAAgtT,QAAhtT,EAA0tT,QAA1tT,EAAouT,QAApuT,EAA8uT,QAA9uT,EAAwvT,QAAxvT,EAAkwT,QAAlwT,EAA4wT,QAA5wT,EAAsxT,QAAtxT,EAAgyT,QAAhyT,EAA0yT,QAA1yT,EAAozT,QAApzT,EAA8zT,QAA9zT,EAAw0T,QAAx0T,EAAk1T,QAAl1T,EAA41T,QAA51T,EAAs2T,QAAt2T,EAAg3T,QAAh3T,EAA03T,QAA13T,EAAo4T,QAAp4T,EAA84T,QAA94T,EAAw5T,QAAx5T,EAAk6T,QAAl6T,EAA46T,QAA56T,EAAs7T,QAAt7T,EAAg8T,QAAh8T,EAA08T,QAA18T,EAAo9T,QAAp9T,EAA89T,QAA99T,EAAw+T,QAAx+T,EAAk/T,QAAl/T,EAA4/T,QAA5/T,EAAshU,QAAthU,EAAgiU,QAAhiU,EAA0iU,QAA1iU,EAAojU,QAApjU,EAA8jU,QAA9jU,EAAwkU,QAAxkU,EAAklU,QAAllU,EAA4lU,QAA5lU,EAAsmU,QAAtmU,EAAgnU,QAAhnU,EAA0nU,QAA1nU,EAAooU,QAApoU,EAA8oU,QAA9oU,EAAwpU,QAAxpU,EAAkqU,QAAlqU,EAA4qU,QAA5qU,EAAsrU,QAAtrU,EAAgsU,QAAhsU,EAA0sU,QAA1sU,EAAotU,QAAptU,EAA8tU,QAA9tU,EAAwuU,QAAxuU,EAAkvU,QAAlvU,EAA4vU,QAA5vU,EAAswU,QAAtwU,EAAgxU,QAAhxU,EAA0xU,QAA1xU,EAAoyU,QAApyU,EAA8yU,QAA9yU,EAAwzU,QAAxzU,EAAk0U,QAAl0U,EAA40U,QAA50U,EAAs1U,QAAt1U,EAAg2U,QAAh2U,EAA02U,QAA12U,EAAo3U,QAAp3U,EAA83U,QAA93U,EAAw4U,QAAx4U,EAAk5U,QAAl5U,EAA45U,QAA55U,EAAs6U,QAAt6U,EAAg7U,QAAh7U,EAA07U,QAA17U,EAAo8U,QAAp8U,EAA88U,QAA98U,EAAw9U,QAAx9U,EAAk+U,QAAl+U,EAA4+U,QAA5+U,EAAs/U,QAAt/U,EAAggV,QAAhgV,EAA0gV,QAA1gV,EAAohV,QAAphV,EAA8hV,QAA9hV,EAAwiV,QAAxiV,EAAkjV,QAAljV,EAA4jV,QAA5jV,EAAskV,QAAtkV,EAAglV,QAAhlV,EAA0lV,QAA1lV,EAAomV,QAApmV,EAA8mV,QAA9mV,EAAwnV,QAAxnV,EAAkoV,QAAloV,EAA4oV,QAA5oV,EAAspV,QAAtpV,EAAgqV,QAAhqV,EAA0qV,QAA1qV,EAAorV,QAAprV,EAA8rV,QAA9rV,EAAwsV,QAAxsV,EAAktV,QAAltV,EAA4tV,QAA5tV,EAAsuV,QAAtuV,EAAgvV,QAAhvV,EAA0vV,QAA1vV,EAAowV,QAApwV,EAA8wV,QAA9wV,EAAwxV,QAAxxV,EAAkyV,QAAlyV,EAA4yV,QAA5yV,EAAszV,QAAtzV,EAAg0V,QAAh0V,EAA00V,QAA10V,EAAo1V,QAAp1V,EAA81V,QAA91V,EAAw2V,QAAx2V,EAAk3V,QAAl3V,EAA43V,QAA53V,EAAs4V,QAAt4V,EAAg5V,QAAh5V,EAA05V,QAA15V,EAAo6V,QAAp6V,EAA86V,QAA96V,EAAw7V,QAAx7V,EAAk8V,QAAl8V,EAA48V,QAA58V,EAAs9V,QAAt9V,EAAg+V,QAAh+V,EAA0+V,QAA1+V,EAAo/V,QAAp/V,EAA8/V,QAA9/V,EAAwgW,QAAxgW,EAAkhW,QAAlhW,EAA4hW,QAA5hW,EAAsiW,QAAtiW,EAAgjW,QAAhjW,EAA0jW,QAA1jW,EAAokW,QAApkW,EAA8kW,QAA9kW,EAAwlW,QAAxlW,EAAkmW,QAAlmW,EAA4mW,QAA5mW,EAAsnW,QAAtnW,EAAgoW,QAAhoW,EAA0oW,QAA1oW,EAAopW,QAAppW,EAA8pW,QAA9pW,EAAwqW,QAAxqW,EAAkrW,QAAlrW,EAA4rW,QAA5rW,EAAssW,QAAtsW,EAAgtW,QAAhtW,EAA0tW,QAA1tW,EAAouW,QAApuW,EAA8uW,QAA9uW,EAAwvW,QAAxvW,EAAkwW,QAAlwW,EAA4wW,QAA5wW,EAAsxW,QAAtxW,EAAgyW,QAAhyW,EAA0yW,QAA1yW,EAAozW,QAApzW,EAA8zW,QAA9zW,EAAw0W,QAAx0W,EAAk1W,QAAl1W,EAA41W,QAA51W,EAAs2W,QAAt2W,EAAg3W,QAAh3W,EAA03W,QAA13W,EAAo4W,QAAp4W,EAA84W,QAA94W,EAAw5W,QAAx5W,EAAk6W,QAAl6W,EAA46W,QAA56W,EAAs7W,QAAt7W,EAAg8W,QAAh8W,EAA08W,QAA18W,EAAo9W,QAAp9W,EAA89W,QAA99

,WAAO0e,GAAP;AACD;;SAEDC,aAAA,oBAAWvB,QAAX,EAAqB;AACnB1M,IAAAA,QAAQ,CAAC,yCAAyC,6BAA1C,CAAR;AACA,WAAO,KAAKiH,IAAL,CAAUyF,QAAV,CAAP;AACD;;SAEDwB,WAAA,kBAAS9HAAT,EAAAesG,QAAAf,EAAAyB;AACvB1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAKyH,SAAL,CAAAerB,IAAAf,EAAAqBsG,QAArB,CAAP;AACD;;SAEDyB,WAAA,kBAAS1Y,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED0W,WAAA,kBAAS1Y,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED2W,WAAA,kBAAS3Y,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED4W,WAAA,kBAAS5Y,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED6W,WAAA,kBAAS7Y,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED8W,WAAA,kBAAS9Y,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED+W,WAAA,kBAAS/Y,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDgX,WAAA,kBAAShZ,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDiX,WAAA,kBAASjZ,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDkX,WAAA,kBAASlZ,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDmX,WAAA,kBAASnZ,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDoX,WAAA,kBAASpZ,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDqX,WAAA,kBAASrZ,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDsX,WAAA,kBAAStZ,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDuX,WAAA,kBAASvZ,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDwX,WAAA,kBAASxZ,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDyX,WAAA,kBAASzZ,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED0X,WAAA,kBAAS1Z,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED2X,WAAA,kBAAS3Z,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED4X,WAAA,kBAAS5Z,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED6X,WAAA,kBAAS7Z,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED8X,WAAA,kBAAS9Z,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED+X,WAAA,kBAAS/Z,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDgY,WAAA,kBAAShaa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDiY,WAAA,kBAASjaa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDkY,WAAA,kBAASlaa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDmY,WAAA,kBAASnaa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDoY,WAAA,kBAASpaa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDqY,WAAA,kBAASraa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDsY,WAAA,kBAAStaa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDuY,WAAA,kBAASvaa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDwY,WAAA,kBAASxaa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDyY,WAAA,kBAASzaa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED0Y,WAAA,kBAAS1aa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED2Y,WAAA,kBAAS3aa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED4Y,WAAA,kBAAS5aa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED6Y,WAAA,kBAAS7aa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED8Y,WAAA,kBAAS9aa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED+Y,WAAA,kBAAS/aa,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDgZ,WAAA,kBAAShbb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDiZ,WAAA,kBAASjbb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDkZ,WAAA,kBAASlbb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDmZ,WAAA,kBAASnbb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDoZ,WAAA,kBAASpbb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDqZ,WAAA,kBAASrbb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDsZ,WAAA,kBAAStbb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDuZ,WAAA,kBAASvbb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDwZ,WAAA,kBAASxbb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDyZ,WAAA,kBAASzbb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED0Z,WAAA,kBAAS1bb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED2Z,WAAA,kBAAS3bb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED4Z,WAAA,kBAAS5bb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED6Z,WAAA,kBAAS7bb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED8Z,WAAA,kBAAS9bb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED+Z,WAAA,kBAAS/bb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDga,WAAA,kBAAShdb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDia,WAAA,kBAASjdb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDka,WAAA,kBAASldb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDma,WAAA,kBAASndb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDoa,WAAA,kBAASpdb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDqa,WAAA,kBAASrdb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDsa,WAAA,kBAAStdb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDua,WAAA,kBAASvdb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDwa,WAAA,kBAASxdb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDya,WAAA,kBAASzdb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED0a,WAAA,kBAAS1db,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED2a,WAAA,kBAAS3db,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED4a,WAAA,kBAAS5db,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED6a,WAAA,kBAAS7db,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED8a,WAAA,kBAAS9db,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED+a,WAAA,kBAAS/db,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDgb,WAAA,kBAAShfeb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDib,WAAA,kBAASjfeb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDkb,WAAA,kBAASlfeb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDmb,WAAA,kBAASnfeb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDob,WAAA,kBAASpfeb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDqb,WAAA,kBAASrfeb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDsb,WAAA,kBAAStfeb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDub,WAAA,kBAASvfeb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDwb,WAAA,kBAASxfeb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDyb,WAAA,kBAASzfeb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED0b,WAAA,kBAAS1feb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED2b,WAAA,kBAAS3feb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED4b,WAAA,kBAAS5feb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED6b,WAAA,kBAAS7feb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED8b,WAAA,kBAAS9feb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED+b,WAAA,kBAAS/feb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDgc,WAAA,kBAAShhfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDic,WAAA,kBAASjhfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDkc,WAAA,kBAASlhfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDmc,WAAA,kBAASnhfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDoc,WAAA,kBAASphfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDqc,WAAA,kBAASrhfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDsc,WAAA,kBAAShhfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDuc,WAAA,kBAASvhfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDwc,WAAA,kBAASxhfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDyc,WAAA,kBAASzhfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED0c,WAAA,kBAAS1hfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED2c,WAAA,kBAAS3hfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED4c,WAAA,kBAAS5hfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED6c,WAAA,kBAAS7hfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED8c,WAAA,kBAAS9hfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAED+c,WAAA,kBAAS/hfb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDgd,WAAA,kBAAShjeb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDid,WAAA,kBAASjjeb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDkd,WAAA,kBAASljeb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDmd,WAAA,kBAASnjeb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAAA,QAAQ,CAAC,uCAAuC,kCAAxC,CAAR;AACA,WAAO,KAAK6M,SAAL,CAAAepX,EAAAmB,QAAZ,EAAA6B,EAAA,CAAP;AACD;;SAEDod,WAAA,kBAASpjeb,QAAT,EAAAmB,EAAA6B;AAC3B1M,IAAA

KAAK,GAAG,GAAd;AACA,WAAON,IAAI,CAAC1Y,KAAL,CAAWwG,MAAX,EAAmB,CAACwS,KAAD,CA
AnB,EAA4B,IAA5B,CAAP;AACD;AA3EU,CAAb;;ACHA;;;;;;;;;;;IAWM/D;;;AACJ,gBAAYxC,QAAZ,EAAsB;
AAAA;;AACpB,kCAAMA,QAAN;AACA,UAAK3C,IAAL,GAAY,MAAZ;AACA,QAAI,CAAC,MAAKnP,KAA
V,EAAiB,MAAKA,KAAL,GAAa,EAAb;AAHG;AAIrB;AAED;;;;;;;;;;;;;;;;;;;wBAgBgB;AACd,aAAO+X,IAAI,C
AACM,KAAL,CAAW,KAAKnZ,QAAhB,CAAP;AACD;sBAEaoZ,QAAQ;AACpB,UAAMzY,KAAK,GAAG,KA
AKX,QAAL,GAAgB,KAAKA,QAAL,CAAcW,KAAd,GAAsB,MAApB,CAAhB,GAA8C,IAA5D;AACA,UAAM
0Y,GAAG,GAAG1Y,KAAK,GAAGA,KAAK,CAAC,CAAD,CAAR,GAAc,SAAkB,KAAK2P,GAAL,CAAS,EAA
oB,YAApB,CAAnC;AACA,WAAKtQ,QAAL,GAAgBoZ,MAAM,CAACpc,IAAP,CAAYqc,qc,IAAP,CAAYqc,GAAZ,CAAhB;AAC
D;;;wBAEe;AACd9O,MAAAA,QAAQ,CAAC,sDAAD,CAAR;AACA,aAAO,KAAK6F,UpQ,QAAjB;
AACD;sBAEauU,KAAK;AACjBhK,MAAAA,QAAQ,CAAC,sDAAD,CAAR;AACA,WAAK6F,UpQ,
QAAV,GAAqBuU,GAArB;AACD;AAED;;;;;;;;;;AAWA;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;;EAtDiBwC;;AClBnB;;AACA;;;;;;;;I
AQMuC;AACJ;;;;;;;;;;AAWA,mBAAY9I,IAAZ,EAAkBqC,IAAlB,EAA6B;AAAA,QAAXA,IAAW;AAAXA,MAAAA,IAAW,GAAJ,EAAI;AAAA;AAAA,MA
AAA,IAAW,GAAJ,EAAI;AAAA;;AAC3B;;;;;;;;AAQA,SAAK5C,IAAL,GAAY,SAAZ;AACA;;;;;;;;AAMA,SAAKK
O,IAAL,GAAYA,IAAZ;;AAEA,QAAIqC,IAAI,CAAC5R,IAAL,GAAY,CAAhB,EAAmB;AAAA;AAAA;AAAA

;AACFzG,QAAAA,IAAI,GAAG2G,MAAM,CAACnY,GAAD,EAAMmU,IAAN,CAAb;AACD,OAFD,CAEE,OAAO1F,KAAP,EAAc;AACd,aAAKA,KAAL,GAAaA,KAAb;AACD;AACF;;AAED,SAAKjD,MAAL,GAAcIAIsP,MAAJ,CAAWC,SAAX,EAAsBvJ,IAAtB,EAA4B2C,IAA5B,CAAiCC,IAAjC;AACD;AACF;;;;;;;;;AAmGA;;;;;SAMAiH,WAAA,oBAAAW;AACT;AACF;;;;;;;;;;SAQAjf,WAAA,oBAAAW;AACT;AACF;;;;;;;;;;;;;;;;;;;;SAkBAub,OAAA,cAAAkC,MAAA,WAAAC,IAAA,gBAAAC,IAAA,gBAAAC,IAAA,gB

YAAA,uBAAY;AACV,QAAI,KAAKoK,WAAT,EAAsB,OAAO,KAAKjQ,MAAZ;AACtB,SAAKiQ,WAAL,GAAAmB,IAAAnB;AAEA,SAAKG,IAAL;AAEA,QAAMzH,IAAAI,GAAAG,KAAK3I,MAAAL,CAAAY2I,IAAAzB;AACA,QAAAI5Y,GAAAG,GAAAG8V,SAAAV;AACA,QAAAI8C,IAAAI,CAACwH,MAAAT,EAAAiBpgB,GAAAG,GAAAG4Y,IAAAI,CAACwH,MAAAL,CAAAYtK,SAAAlB;AACjB,QAAAI8C,IAAAI,CAACI,WAAAT,EAAAsBhZ,GAAAG,GAAAG4Y,IAAAI,CACIWAAX;AACtB,QAAAIhZ,GAAAG,CAAC8V,SAAAR,EAAAmB9V,GAAAG,GAAAGA,GAAAG,CAAC8V,SAAAV;AAEnB,QAAI7F,MAAAG,GAAAG,EAAAb;AACAjQ,IAAAAA,GAAAG,CAAC,KAAAKiW,IAAAN,EAAAN,UAAAArW,EAAAI,IAAAI;AAClBqQ,MAAAAA,MAAAM,IAAAIrQ,CAAAV,EAAAI,GAAAG,CAAAY,IAAAI

AAW;AAAXA,MAAAA,IAAW,GAAJ,EAAI;AAAA;;AAC1B;;;;;;;AAOA,SAAKnU,GAAAL,GAAAWA,GAAAG,CA
AC7D,QAAJ,EAAX;;AAEA,QAAI,KAAK6D,GAAAL,CAAAS,CAAAT,MAAgB,QAAAhB,IAA4B,KAAAKA,GAAAL,C
AAS,CAAAT,MAAgB,QAAAhD,EAA0D;AACxD,WAAAKA,GAAAL,GAAAW,KAAAKA,GAAAL,CAAAS0O,KAAAT,CAA
e,CAAAf,CAAAX;AACD;;AAED,QAAIyF,IAAAI,CAAAC2D,IAAAT,EAAAe;AACb,UAAAI,YAAY/b,IAAAZ,CAAAiBoY,IA
AI,CAAAC2D,IAAAtB,CAAAJ,EAAAiC;AAC/B;;;;;;;;AAQA,aAAAKxI,IAAAL,GAAAY6E,IAAAI,CAAAC2D,IAAAjB;AACD,
OAVD,MAUO;AACL,aAAAKxI,IAAAL,GAAAYgO,IAAAI,CAACd,OAAAL,CAAAarI,IAAAI,CAAAC2D,IAAAlB,CAAAZ;AA
CD;AACF;AAED;;;;;;;;;;;;;;;;;AAiBA,QAAAI,CAAAC,KAAAKxI,IAAAV,EAAAgB;AACd+N,MAAAAA,QAAAQ,IAAAI,C
AAZ;AACA;;;;;;;;;;AAUA,WAAK7c,EAAAL,mBAAAwB6c,QAAAxB;AACD;;AACD,QAAAI,KAAAKlO,GAAAT,EAAAc
,KAAKA,GAAAL,CAASG,IAAAT,GAAAgB,KAAAKwI,IAArB;AACf;;;;SAEDrJ,QAAAA,eAAAM3C,OAAAN,EAAAenF,IA
Af,EAAAqBC,MAArB,EAA6BuN,IAA7B,EAAAwC;AAAAA,QAAAXA,IAAAW;AAAAXA,MAAAA,IAAAW,GAAAJ,EAAAI
;AAAA;;AACtC,QAAAI3I,MAAAJ;AACA,QAAAM+R,GAAAG,KAAAKA,MAAAL,CAAAY5W,IAAAZ,EAAAkBC,
MAAlB,CAAf;;AACA,QAAAI2W,GAAAT,EAAAY,IAAAT,MAAAA,MAAAM,GAAAG,IAAAI4D,cAAAtD,OAAAD
O,EAAEPyR,MAAAM,CAAC5W,IAFA,EAAGP4W,MAAAM,CAAC3W,MAAHA,EAAIP2W,MAAAM,CAAAClO,MAJA,EA
KPkO,MAAAM,CAACjO,IALA,EAMP6E,IAAI,CAACrL,MANE,CAAT;AAQD,KATD,MASO;AACL0C,MAAA
A,MAAAM,GAAAG,IAAAI4D,cAAAtD,OAAAnB,EAAA4BnF,IAA5B,EAAAkCC,MAAlC,EAA0C,KAAK5G,GA
A/C,EAAoD,KAAAKsP,IAAAzD,EAA+D,IAAAI,CAACrL,MAApE,CAAT;AACD;;AAED0C,IAAAAA,MAAAM,CA
AC8B,KAAAP,GAAAe;AAAE3G,MAAAAA,IAAAI,EAAAJA,IAAAF;AAAQC,MAAAAA,IAAAW,GAAAJ,EAAAI;AAAAA,MAAAR;AAg
ByI,MAAAAA,MAAAM,EAAAE,KAAAKrP;AAA7B,KAAAf;AACA,QAAAI,KAAAKsP,IAAAT,EAAAe9D,MAAAM,CAAC8B,
KAAP,CAAAagC,IAAAb,GAAAoB,KAAAKA,IAAAzB;AAEf,WAAO9D,MAAAM,CAAC;AAED;;;;;;;;;;;;;;;SAaA+R,SAAA
A,gBAAO5W,IAAAP,EAAAaC,MAAAb,EAAAqB;AACnB,QAAI,CAAC,QAAAI,KAAAuI,GAAAV,EAAAe,KAAAKA,IAAAV,
QAAAqqO,QAAAQ,GAAAG,KAAAKrO,GAAAL,CAASqO,QAAAT,EAAAjB;AAEf,QAAIA,MAAAM,CAAC1W,IAAAP,EAAAa
AACC,mBAAAT,CAA6B;AAAE9W,MAAAA,IAAAI,EAAAJA,IAAAF;AAAQC,MAAAAA,IAAAW,GAAAJ,EAAAI;AAAAA,MAAAR;AA
A7B,CAAb;AACA,QAAAI,KAAAKkR,IAAAI,CAACzI,IAAAZ,EAAAkBC,MAAAM,CAAC8B,IAAAT,EAAAe,KAAAK
AAGAC,MAAAM,CAAC8B,IAAAT,EAAAe,KAAAKoO,UAAAL,CAAAgB5F,IAAAI,CAACzI,IAAAZ,EAAAkBC,MAAAM,CAAC8B,
KAAP,CAAAgC,IAAAb,GAAAoB,KAAAKA,IAAAzB;AAEb,QAAIA,MAAAM,CAAC1W,IAAAP,EAAAaC,MAAAb,EAAAqB;AAA
AMA,QAAAMyI,MAAAM,GAAAGmO,QAAAQ,CAACG,gBAAAT,CAA0B7F,IAAAI,CAACzI,IAAAZ,EAAAkBC,MAAAM,CAAC8B,
KAAP,CAAAgC,IAAAb,GAAAoB,KAAAKA,IAAAzB;AAEf,QAAIA,MAAAM,CAAC1W,IAAAP,EAAAaC,MAAAb,EAAAqB;AAA
IAP;AACD,KAFD,MAEO;AACL,aAAOgO,IAAAI,CAACd,OAAAL,CAAAa,IAAAI,CAACzI,IAAAZ,EAAAkBC,MAAAM,CAAC8B,IAAAT,EAAAe,KAAAKoO,UAAAL,CAAAgB5F,IAAAI,CAACzI,IAAAZ,EAAAkBC,MAAAM,CAAC8B,
KAAP,CAAAgC,IAAAb,GAAAoB,KAAAKA,IAAAzB;AAEb,QAAIA,MAAAM,CAAC1W,IAAAP,EAAAaC,MAAAb,EAAAqB;AAA
AoBI,UAApB,IAAkC,GAA/C,EAAoDtO,IAApD,EAA0DuO,CAAP;AACD;;AACF;AAED;;;;;;;;;;;;;;;wBAYW;AACT,KAAKxO,IAAAL,GAAAY6E,IAAAI,CAACd,OAAAL,CAAAa,IAAAI,CAACzI,IAAAZ,EAAAkBC,MAAAM,CAAC8B,IAAAT,EAAAe,KAAAKoO,UAAAL,CAAAgB5F,IAAAI,CAACzI,IAAAZ,EAAAkBC,MAAAM,CAAC8B,
KAAP,CAAAgC,IAAAb,GAAAoB,KAAAKA,IAAAzB;AAEb,QAAIA,MAAAM,CAAC1W,IAAAP,EAAAaC,MAAAb,EAAAqB;AAA
AMA,QAAAMyI,MAAAM,GAAAGmO,QAAAQ,C

BAAA,2BAAkB;AAChB,SAAKvB,OAAL,CAAaxE,IAAb,CAAkBb,KAAlB,IAA2B,GAA3B;AACD;;SAEDkH,cAAA,uBAAc;;SAEdR,gBAAA,uBAAchV,IAAAd,EAAAoB;AAClBA,IAAAAA,IAAAI,CAAC5H,IAAAL,GAAAY,EAAAZ;AACD;;SAEDuc,0BAAA,iCAAAwB3J,MAAAxB,EAAAgC;AAC9B,QAAAM+C,KAAAK,GAAAG,KAAAKA,KAAAL,CAAAW/C,MAAAX,CAAAd;AACA,QAAAI+C,KAAAK,KAAAK,KAAAd,EAAAqB;AAErB,QAAAI7O,KAAAJ;;AACA,SAAAKA,KAAAK,GAAAG,KAAAKA,KAAAL,CAAAW6O,GAAAG,KAAAG,CAAArB,EAAAwB7O,KAAAK,IAAAI,CAAAjC,EAAAoCA,KAAAzC,EAAAyzC;AAC3C,UAAAI8L,MAAAM,CAAC9L,KAAAD,GAAAG,CAAAc,CAAAd,MAAAqB,MAAAzB,EAAAiC;AAClC;;AACD,SAAAKA,KAAAK,GAAAG,KAAAKA,KAAAL,CAAA1B,EAAA6BA,KAAAK,KAAAK,KAAAd,EAAAiBA,IAAAI,CAAAjC,EAAAoCA,KAAAzC,EAAAyzC;AACpC,UAAAI8L,MAAAM,CAAC9L,KAAAD,GAAAG,CAAAc,CAAAd,MAAAqB,MAAAzB,EAAAiC;AAClC;;AACD,SAAAKA

AC4d,KAAD,EAAeyF,aAAf,EAAmCC,YAAnC,EAAwE;AAAA,MAArCA,YAAqC;AAArCA,IAAAA,YAAqC,GAAjBvhB,YAAiB;AAAA;;AACrF,SAAQ6b,KAAK,CAAC2F,KAAN,KAAgBD,YAAY,CAACC,KAA7B,IAAsC3F,KAAK,CAAC2F,KAAN,KAAgBC,YAAY,CAACD,KAA7C,IAAsDE,YAAY,CAACC,KAAb,KAAuBF,YAAY,CAACE,KAAhJ;AAAuJ;AAAA,MAAvJ;AAAA,MAAvJ;AAAA,MAAv

AAAf,MAAb;;AAEA,QAAI,CAACe,KAAK,CAAC3kB,MAAX,EAAmB,OAAOoL,OAAP;AAEnB,SAAKuZ,KAAL,GAAa,EAAb;AAEAA,IAAAA,KAAK,CAAC9hB,OAAN,CAAc,UAAAojB,OAAO,EAAI;AACvB,UAAIC,eAAeD,OAAf,CAAJ,EAA6B;AAC3B,YAAIE,OAAOF,QAAQG,WAAnB;AACA,YAAIC,OAAOJ,QAAQK,WAAnB;AACA,YAAIC,OAAOH,KAAKI,qBAAL,EAAX;AACA,YAAIC,OAAOJ,KAAKG,qBAAL,EAAX;AACA,YAAIE,OAAOC,KAAKC,GAAL,CAASL,KAAKM,IAAd,EAAoBJ,KAAKI,IAAzB,CAAX;AACA,YAAIC,OAAOH,KAAKC,GAAL,CAASL,KAAKO,IAAd,EAAoBL,KAAKK,IAAzB,CAAX;AACA,YAAIC,QAAQJ,KAAKC,GAAL,CAASL,KAAKQ,KAAd,EAAqBN,KAAKM,KAA1B,CAAZ;AACA,YAAIC,QAAQN,KAAKC,GAAL,CAASL,KAAKS,KAAd,EAAqBP,KAAKO,KAA1B,CAAZ;AACA,YAAIC,IAAIL,OAAOF,IAAf;AACA,YAAIQ,IAAIL,OAAOF,IAAf;AACA,YAAIQ,IAAIH,QAAQL,IAAhB;AACA,YAAIS,IAAIH,QAAQL,IAAhB;AACA,YAAIS,IAAIC,KAAKC,KAAL,CAAWL,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIK,IAAIF,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIK,IAAIH,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIM,IAAIJ,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIO,IAAIL,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIQ,IAAIN,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIS,IAAIP,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIU,IAAIR,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIW,IAAIT,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIY,IAAIV,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIa,IAAIX,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIc,IAAIZ,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIe,IAAIb,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgB,IAAId,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiB,IAAIf,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkB,IAAIhB,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImB,IAAIjB,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoB,IAAIlB,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqB,IAAInB,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsB,IAAIpB,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuB,IAAIrB,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwB,IAAItB,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyB,IAAIvB,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0B,IAAIxB,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2B,IAAIzB,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4B,IAAI1B,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6B,IAAI3B,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8B,IAAI5B,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+B,IAAI7B,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgC,IAAI9B,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiC,IAAI/B,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkC,IAAIhC,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImC,IAAIjC,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoC,IAAIlC,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqC,IAAInC,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsC,IAAIpC,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuC,IAAIrC,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwC,IAAItC,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyC,IAAIvC,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0C,IAAIxC,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2C,IAAIzC,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4C,IAAI1C,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6C,IAAI3C,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8C,IAAI5C,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+C,IAAI7C,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgD,IAAI9C,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiD,IAAI/C,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkD,IAAIhD,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImD,IAAIjD,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoD,IAAIlD,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqD,IAAInD,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsD,IAAIpD,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuD,IAAIrD,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwD,IAAItD,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyD,IAAIvD,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0D,IAAIxD,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2D,IAAIzD,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4D,IAAI1D,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6D,IAAI3D,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8D,IAAI5D,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+D,IAAI7D,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgE,IAAI9D,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiE,IAAI/D,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkE,IAAIhE,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImE,IAAIjE,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoE,IAAIlE,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqE,IAAInE,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsE,IAAIpE,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuE,IAAIrE,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwE,IAAItE,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyE,IAAIvE,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0E,IAAIxE,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2E,IAAIzE,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4E,IAAI1E,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6E,IAAI3E,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8E,IAAI5E,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+E,IAAI7E,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgF,IAAI9E,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiF,IAAI/E,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkF,IAAIhF,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImF,IAAIjF,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoF,IAAIlF,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqF,IAAInF,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsF,IAAIpF,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuF,IAAIrF,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwF,IAAItF,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyF,IAAIvF,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0F,IAAIxF,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2F,IAAIzF,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4F,IAAI1F,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6F,IAAI3F,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8F,IAAI5F,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+F,IAAI7F,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgG,IAAI9F,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiG,IAAI/F,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkG,IAAIhG,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImG,IAAIjG,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoG,IAAIlG,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqG,IAAInG,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsG,IAAIpG,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuG,IAAIrG,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwG,IAAItG,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyG,IAAIvG,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0G,IAAIxG,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2G,IAAIzG,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4G,IAAI1G,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6G,IAAI3G,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8G,IAAI5G,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+G,IAAI7G,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgH,IAAI9G,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiH,IAAI/G,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkH,IAAIhH,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImH,IAAIjH,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoH,IAAIlH,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqH,IAAInH,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsH,IAAIpH,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuH,IAAIrH,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwH,IAAItH,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyH,IAAIvH,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0H,IAAIxH,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2H,IAAIzH,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4H,IAAI1H,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6H,IAAI3H,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8H,IAAI5H,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+H,IAAI7H,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgI,IAAI9H,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiI,IAAI/H,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkI,IAAIhI,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImI,IAAIjI,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoI,IAAIlI,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqI,IAAInI,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsI,IAAIpI,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuI,IAAIrI,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwI,IAAItI,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyI,IAAIvI,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0I,IAAIxI,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2I,IAAIzI,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4I,IAAI1I,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6I,IAAI3I,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8I,IAAI5I,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+I,IAAI7I,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgJ,IAAI9I,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiJ,IAAI/I,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkJ,IAAIhJ,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImJ,IAAIjJ,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoJ,IAAIlJ,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqJ,IAAInJ,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsJ,IAAIpJ,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuJ,IAAIrJ,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwJ,IAAItJ,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyJ,IAAIvJ,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0J,IAAIxJ,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2J,IAAIzJ,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4J,IAAI1J,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6J,IAAI3J,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8J,IAAI5J,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+J,IAAI7J,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgK,IAAI9J,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiK,IAAI/J,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkK,IAAIhK,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImK,IAAIjK,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoK,IAAIlK,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqK,IAAInK,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsK,IAAIpK,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuK,IAAIrK,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwK,IAAItK,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyK,IAAIvK,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0K,IAAIxK,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2K,IAAIzK,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4K,IAAI1K,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6K,IAAI3K,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8K,IAAI5K,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+K,IAAI7K,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgL,IAAI9K,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiL,IAAI/K,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkL,IAAIhL,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImL,IAAIjL,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoL,IAAIlL,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqL,IAAInL,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsL,IAAIpL,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuL,IAAIrL,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwL,IAAItL,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyL,IAAIvL,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0L,IAAIxL,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2L,IAAIzL,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4L,IAAI1L,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6L,IAAI3L,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8L,IAAI5L,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+L,IAAI7L,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgM,IAAI9L,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiM,IAAI/L,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkM,IAAIhM,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImM,IAAIjM,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoM,IAAIlM,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqM,IAAInM,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsM,IAAIpM,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuM,IAAIrM,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwM,IAAItM,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyM,IAAIvM,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0M,IAAIxM,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2M,IAAIzM,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4M,IAAI1M,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6M,IAAI3M,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8M,IAAI5M,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+M,IAAI7M,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgN,IAAI9M,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiN,IAAI/M,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkN,IAAIhN,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImN,IAAIjN,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoN,IAAIlN,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqN,IAAInN,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsN,IAAIpN,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuN,IAAIrN,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwN,IAAItN,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyN,IAAIvN,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0N,IAAIxN,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2N,IAAIzN,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4N,IAAI1N,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6N,IAAI3N,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8N,IAAI5N,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+N,IAAI7N,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgO,IAAI9N,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiO,IAAI/N,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkO,IAAIhO,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImO,IAAIjO,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoO,IAAIlO,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqO,IAAInO,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsO,IAAIpO,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuO,IAAIrO,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwO,IAAItO,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyO,IAAIvO,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0O,IAAIxO,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2O,IAAIzO,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4O,IAAI1O,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6O,IAAI3O,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8O,IAAI5O,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+O,IAAI7O,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgP,IAAI9O,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiP,IAAI/O,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkP,IAAIhP,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImP,IAAIjP,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoP,IAAIlP,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqP,IAAInP,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsP,IAAIpP,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuP,IAAIrP,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwP,IAAItP,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyP,IAAIvP,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0P,IAAIxP,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2P,IAAIzP,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4P,IAAI1P,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6P,IAAI3P,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8P,IAAI5P,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+P,IAAI7P,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgQ,IAAI9P,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiQ,IAAI/P,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkQ,IAAIhQ,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAImQ,IAAIjQ,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIoQ,IAAIlQ,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIqQ,IAAInQ,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIsQ,IAAIpQ,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIuQ,IAAIrQ,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIwQ,IAAItQ,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIyQ,IAAIvQ,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI0Q,IAAIxQ,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI2Q,IAAIzQ,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI4Q,IAAI1Q,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI6Q,IAAI3Q,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAI8Q,IAAI5Q,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAI+Q,IAAI7Q,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIgR,IAAI9Q,KAAKC,KAAL,CAAWJ,CAAX,EAAcC,CAAd,CAAR;AACA,YAAIiR,IAAI/Q,KAAKC,KAAL,CAAWL,CAAX,EAAcE,CAAd,CAAR;AACA,YAAIkR,

mB,QAAAA,aAAa,EAAE;AARkC,OAA9C,CAAL;AAUD;;AAED,WAAOL,4BAAP;AACD,GA1GD;;AA4GA,SAAOJ,2BAAP;AACD,CA9GD;;ACvIA;AAGA,kBAAe,UACbiB,OADa,EAEbzkB,cAFa,EAGY;AACzB,MAAMoN,MAAM,GAAG,CAACqX,OAAO,CAAC,CAAD,CAAR,CAAf;;AAEA,OAAK,IAAI1nB,CAAC,GAAG,CAAb,EAAgBA,CAAC,GAAG0nB,OAAO,CAAC,CAAD,CAAP,CAAWznB,MAA/B,EAAuCD,CAAC,EAAxC,EAA4C;AAC1C,QAAMqQ,KAAK,GAAGqX,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAd;AACA,QAAMsQ,IAAI,GAAGoX,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMuQ,IAAI,GAAGmX,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwQ,IAAI,GAAGkX,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMyQ,IAAI,GAAGiX,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0Q,IAAI,GAAGgX,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2Q,IAAI,GAAG+W,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4Q,IAAI,GAAG8W,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6Q,IAAI,GAAG6W,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8Q,IAAI,GAAG4W,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+Q,IAAI,GAAG2W,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMgR,IAAI,GAAG0W,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMiR,IAAI,GAAGyW,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMkR,IAAI,GAAGwW,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMmR,IAAI,GAAGuW,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMoR,IAAI,GAAGsW,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqR,IAAI,GAAGqW,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMsR,IAAI,GAAGoW,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMuR,IAAI,GAAGmW,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwR,IAAI,GAAGkW,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMyR,IAAI,GAAGiW,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0R,IAAI,GAAGgW,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2R,IAAI,GAAG+V,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4R,IAAI,GAAG8V,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6R,IAAI,GAAG6V,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8R,IAAI,GAAG4V,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+R,IAAI,GAAG2V,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMgS,IAAI,GAAG0V,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMiS,IAAI,GAAGyV,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMkS,IAAI,GAAGwV,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMmS,IAAI,GAAGuV,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMoS,IAAI,GAAGsV,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqS,IAAI,GAAGqV,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMsS,IAAI,GAAGoV,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMuS,IAAI,GAAGmV,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwS,IAAI,GAAGkV,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMyS,IAAI,GAAGiV,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0S,IAAI,GAAGgV,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2S,IAAI,GAAG+U,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4S,IAAI,GAAG8U,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6S,IAAI,GAAG6U,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8S,IAAI,GAAG4U,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+S,IAAI,GAAG2U,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMgT,IAAI,GAAG0U,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMiT,IAAI,GAAGyU,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMkT,IAAI,GAAGwU,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMmT,IAAI,GAAGuU,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMoT,IAAI,GAAGsU,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqT,IAAI,GAAGqU,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMsT,IAAI,GAAGoU,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMuT,IAAI,GAAGmU,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwT,IAAI,GAAGkU,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMyT,IAAI,GAAGiU,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0T,IAAI,GAAGgU,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2T,IAAI,GAAG+T,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4T,IAAI,GAAG8T,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6T,IAAI,GAAG6T,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8T,IAAI,GAAG4T,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+T,IAAI,GAAG2T,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMgU,IAAI,GAAG0T,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMiU,IAAI,GAAGyT,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMkU,IAAI,GAAGwT,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMmU,IAAI,GAAGuT,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMoU,IAAI,GAAGsT,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqU,IAAI,GAAGqT,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMsU,IAAI,GAAGoT,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMuU,IAAI,GAAGmT,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwU,IAAI,GAAGkT,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMyU,IAAI,GAAGiT,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0U,IAAI,GAAGgT,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2U,IAAI,GAAG+S,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4U,IAAI,GAAG8S,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6U,IAAI,GAAG6S,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8U,IAAI,GAAG4S,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+U,IAAI,GAAG2S,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMgV,IAAI,GAAG0S,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMiV,IAAI,GAAGyS,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMkV,IAAI,GAAGwS,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMmV,IAAI,GAAGuS,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMoV,IAAI,GAAGsS,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqV,IAAI,GAAGqS,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMsV,IAAI,GAAGoS,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMuV,IAAI,GAAGmS,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwV,IAAI,GAAGkS,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMyV,IAAI,GAAGiS,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0V,IAAI,GAAGgS,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2V,IAAI,GAAG+R,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4V,IAAI,GAAG8R,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6V,IAAI,GAAG6R,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8V,IAAI,GAAG4R,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+V,IAAI,GAAG2R,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMgW,IAAI,GAAG0R,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMiW,IAAI,GAAGyR,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMkW,IAAI,GAAGwR,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMmW,IAAI,GAAGuR,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMoW,IAAI,GAAGsR,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqW,IAAI,GAAGqR,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMsW,IAAI,GAAGoR,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMuW,IAAI,GAAGmR,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwW,IAAI,GAAGkR,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMyW,IAAI,GAAGiR,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0W,IAAI,GAAGgR,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2W,IAAI,GAAG+Q,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4W,IAAI,GAAG8Q,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6W,IAAI,GAAG6Q,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8W,IAAI,GAAG4Q,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+W,IAAI,GAAG2Q,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMgX,IAAI,GAAG0Q,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMiX,IAAI,GAAGyQ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMkX,IAAI,GAAGwQ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMmX,IAAI,GAAGuQ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMoX,IAAI,GAAGsQ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqX,IAAI,GAAGqQ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMsX,IAAI,GAAGoQ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMuX,IAAI,GAAGmQ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwX,IAAI,GAAGkQ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMyX,IAAI,GAAGiQ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0X,IAAI,GAAGgQ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2X,IAAI,GAAG+P,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4X,IAAI,GAAG8P,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6X,IAAI,GAAG6P,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8X,IAAI,GAAG4P,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+X,IAAI,GAAG2P,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMgY,IAAI,GAAG0P,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMiY,IAAI,GAAGyP,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMkY,IAAI,GAAGwP,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMmY,IAAI,GAAGuP,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMoY,IAAI,GAAGsP,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqY,IAAI,GAAGqP,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMsY,IAAI,GAAGoP,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMuY,IAAI,GAAGmP,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwY,IAAI,GAAGkP,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMyY,IAAI,GAAGiP,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0Y,IAAI,GAAGgP,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2Y,IAAI,GAAG+O,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4Y,IAAI,GAAG8O,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6Y,IAAI,GAAG6O,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8Y,IAAI,GAAG4O,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+Y,IAAI,GAAG2O,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMgZ,IAAI,GAAG0O,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMiZ,IAAI,GAAGyO,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMkZ,IAAI,GAAGwO,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMmZ,IAAI,GAAGuO,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMoZ,IAAI,GAAGsO,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqZ,IAAI,GAAGqO,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMsZ,IAAI,GAAGoO,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMuZ,IAAI,GAAGmO,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwZ,IAAI,GAAGkO,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMyZ,IAAI,GAAGiO,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0Z,IAAI,GAAGgO,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2Z,IAAI,GAAG+N,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4Z,IAAI,GAAG8N,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6Z,IAAI,GAAG6N,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8Z,IAAI,GAAG4N,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+Z,IAAI,GAAG2N,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMga,IAAI,GAAG0N,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMia,IAAI,GAAGyN,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMka,IAAI,GAAGwN,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMma,IAAI,GAAGuN,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMoa,IAAI,GAAGsN,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqa,IAAI,GAAGqN,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMsa,IAAI,GAAGoN,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMua,IAAI,GAAGmN,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwa,IAAI,GAAGkN,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMya,IAAI,GAAGiN,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0a,IAAI,GAAGgN,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2a,IAAI,GAAG+M,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4a,IAAI,GAAG8M,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6a,IAAI,GAAG6M,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8a,IAAI,GAAG4M,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+a,IAAI,GAAG2M,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMgb,IAAI,GAAG0M,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMib,IAAI,GAAGyM,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMkb,IAAI,GAAGwM,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMmb,IAAI,GAAGuM,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMob,IAAI,GAAGsM,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqb,IAAI,GAAGqM,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMsb,IAAI,GAAGoM,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMub,IAAI,GAAGmM,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwb,IAAI,GAAGkM,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMyb,IAAI,GAAGiM,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0b,IAAI,GAAGgM,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2b,IAAI,GAAG+L,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4b,IAAI,GAAG8L,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6b,IAAI,GAAG6L,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8b,IAAI,GAAG4L,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+b,IAAI,GAAG2L,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMgc,IAAI,GAAG0L,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMic,IAAI,GAAGyL,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMkc,IAAI,GAAGwL,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMmc,IAAI,GAAGuL,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMoc,IAAI,GAAGsL,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqc,IAAI,GAAGqL,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMsc,IAAI,GAAGoL,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMuc,IAAI,GAAGmL,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwc,IAAI,GAAGkL,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMyc,IAAI,GAAGiL,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0c,IAAI,GAAGgL,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2c,IAAI,GAAG+K,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4c,IAAI,GAAG8K,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6c,IAAI,GAAG6K,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8c,IAAI,GAAG4K,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+c,IAAI,GAAG2K,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMgd,IAAI,GAAG0K,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMid,IAAI,GAAGyK,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMkd,IAAI,GAAGwK,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMmd,IAAI,GAAGuK,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMod,IAAI,GAAGsK,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqd,IAAI,GAAGqK,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMsd,IAAI,GAAGoK,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMud,IAAI,GAAGmK,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwd,IAAI,GAAGkK,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMyd,IAAI,GAAGiK,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0d,IAAI,GAAGgK,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2d,IAAI,GAAG+J,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4d,IAAI,GAAG8J,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6d,IAAI,GAAG6J,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8d,IAAI,GAAG4J,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+d,IAAI,GAAG2J,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMge,IAAI,GAAG0J,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMie,IAAI,GAAGyJ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMke,IAAI,GAAGwJ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMme,IAAI,GAAGuJ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMoe,IAAI,GAAGsJ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqe,IAAI,GAAGqJ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMse,IAAI,GAAGoJ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMue,IAAI,GAAGmJ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwe,IAAI,GAAGkJ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMye,IAAI,GAAGiJ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0e,IAAI,GAAGgJ,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2e,IAAI,GAAG+I,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4e,IAAI,GAAG8I,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6e,IAAI,GAAG6I,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8e,IAAI,GAAG4I,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+e,IAAI,GAAG2I,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMgf,IAAI,GAAG0I,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMif,IAAI,GAAGyI,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMkf,IAAI,GAAGwI,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMmf,IAAI,GAAGuI,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMof,IAAI,GAAGsI,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqf,IAAI,GAAGqI,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMsf,IAAI,GAAGoI,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMuf,IAAI,GAAGmI,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMwf,IAAI,GAAGkI,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMyf,IAAI,GAAGiI,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM0f,IAAI,GAAGgI,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM2f,IAAI,GAAG+H,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM4f,IAAI,GAAG8H,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM6f,IAAI,GAAG6H,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM8f,IAAI,GAAG4H,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAM+f,IAAI,GAAG2H,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMggB,IAAI,GAAG0H,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMigB,IAAI,GAAGyH,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMkgB,IAAI,GAAGwH,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMmgB,IAAI,GAAGuH,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMogB,IAAI,GAAGsH,OAAO,CAAC,CAAD,CAAP,CAAW1nB,CAAX,CAAb;AACA,QAAMqg

No license file was found, but licenses were detected in source scan.

{"version":3,"file":"styled-components.js","sources":["../src/utils/isStyledComponent.js","../src/utils/interleave.js","../src/utils/isPlainObject.js","../src/utils/empties.js","../src/utils/isFunction.js","../src/utils/getComponentName.js","../src/constants.js","../src/utils/error.js","../src/utils/errors.js","../src/sheet/GroupedTag.js","../src/sheet/GroupIDAllocator.js","../src/sheet/Rehydration.js","../src/utils/nonce.js","../src/sheet/dom.js","../src/sheet/Tag.js","../src/sheet/Sheet.js","../src/utils/generateAlphabeticName.js","../src/utils/hash.js","../src/models/ComponentStyle.js","../../../node_modules/@emotion/stylis/dist/stylis.esm.js","../src/utils/stylis.js","../src/utils/stylisPluginInsertRule.js","../src/models/StyleSheetManager.js","../../../node_modules/shallowequal/index.js","../src/models/Keyframes.js","../src/utils/hyphenateStyleName.js","../../../node_modules/@emotion/unitless/dist/unitless.esm.js","../src/utils/flatten.js","../src/utils/isStatelessFunction.js","../src/utils/addUnitIfNeeded.js","../src/constructors/css.js","../src/models/GlobalStyle.js","../src/utils/isStaticRules.js","../src/models/ThemeProvider.js","../src/utils/checkDynamicCreation.js","../src/utils/determineTheme.js","../src/utils/generateComponentId.js","../src/models/ServerStyleSheet.js","../../../node_modules/hoist-non-react-statics/dist/hoist-non-react-statics.cjs.js","../src/secretInternals.js","../src/base.js","../src/constructors/createGlobalStyle.js","../src/constructors/keyframes.js","../src/hooks/useTheme.js","../src/hoc/withTheme.js","../node_modules/@emotion/memoize/dist/emotion-memoize.esm.js","../node_modules/@emotion/is-prop-valid/dist/emotion-is-prop-valid.esm.js","../src/utils/escape.js","../src/utils/isTag.js","../src/utils/mixinDeep.js","../src/models/StyledComponent.js","../src/utils/generateDisplayName.js","../src/utils/joinStrings.js","../src/utils/createWarnTooManyClasses.js","../src/constructors/styled.js","../src/constructors/constructWithOptions.js","../src/index-standalone.js","../src/utils/domElements.js"],"sourcesContent":["// @flow\nexport default function isStyledComponent(target: any): boolean %checks {\n return target && typeof target.styledComponentId === 'string';\n}\n","// @flow\nimport type { Interpolation } from '../types';\n\nexport default (\n strings: Array<string>,\n interpolations: Array<Interpolation>\n): Array<Interpolation> => {\n const result = [strings[0]];\n\n for (let i = 0, len = interpolations.length; i < len; i += 1) {\n   result.push(interpolations[i], strings[i + 1]);\n }\n\n return result;\n};\n","// @flow\nimport type { typeOf } from 'react-is';\n\nexport default (x: any): boolean =>\n x !== null &&\n typeof x === 'object' &&\n (x.toString ? x.toString() : Object.prototype.toString.call(x)) === '[object Object]' &&\n !typeOf(x);\n","// @flow\nexport const EMPTY_ARRAY = Object.freeze([]);\nexport const EMPTY_OBJECT = Object.freeze({});\n","// @flow\nexport default function isFunction(test: any): boolean %checks {\n return typeof test === 'function';\n}\n","// @flow\nimport type { IStyledComponent } from '../types';\n\nexport default function getComponentName(\n target: $PropertyType<IStyledComponent, 'target'>\n): string {\n return (\n   (process.env.NODE_ENV !== 'production' ? typeof target === 'string' && target : false) ||\n   // $FlowFixMe\n   target.displayName ||\n   // $FlowFixMe\n   target.name ||\n   'Component'\n);\n}\n","// @flow\ndeclare var SC_DISABLE_SPEEDY: ?boolean;\ndeclare var __VERSION__: string;\n\nexport const SC_ATTR: string =\n (typeof process !== 'undefined' &&\n   typeof process.env !== 'undefined' &&\n   (process.env.REACT_APP_SC_ATTR || process.env.SC_ATTR)) ||\n 'data-styled';\n\nexport const SC_ATTR_ACTIVE = 'active';\nexport const SC_ATTR_VERSION = 'data-styled-version';\nexport const SC_VERSION = __VERSION__;\nexport const SPLITTER = '/*!sc*/\\n';\n\nexport const IS_BROWSER = typeof window !== 'undefined' && 'HTMLElement' in window;\n\nexport const DISABLE_SPEEDY = Boolean(\n typeof SC_DISABLE_SPEEDY === 'boolean'\n   ? SC_DISABLE_SPEEDY\n   : typeof process !== 'undefined' && typeof process.env !== 'undefined'\n   ? typeof process.env.REACT_APP_SC_DISABLE_SPEEDY !== 'undefined' &&\n   process.env.REACT_APP_SC_DISABLE_SPEEDY !== ''\n   ? process.env.REACT_APP_SC_DISABLE_SPEEDY === 'false'\n   ? false\n   : process.env.REACT_APP_SC_DISABLE_SPEEDY\n   : typeof process.env.SC_DISABLE_SPEEDY !== 'undefined' &&\n   process.env.SC_DISABLE_SPEEDY !== ''\n   ? process.env.SC_DISABLE_SPEEDY ===

'false'\n ? false\n : process.env.SC_DISABLE_SPEEDY\n : process.env.NODE_ENV !== 'production'\n : false\n);\n\n// Shared empty execution context when generating static styles\nexport const STATIC_EXECUTION_CONTEXT = {};\n","// @flow\nimport errorMap from './errors';\n\nconst ERRORS = process.env.NODE_ENV !== 'production'
? errorMap : {};\n\n/**\n * super basic version of sprintf\n */\nfunction format(...args) {\n let a = args[0];\n const b = [];\n\n for (let c = 1, len = args.length; c < len; c += 1) {\n b.push(args[c]);\n }\n\n b.forEach(d => {\n a = a.replace(/%[a-z]/, d);\n });\n\n return a;\n}\n\n/**\n * Create an error file out of errors.md for development and a simple web link to the full errors\n * in production mode.\n */\nexport default function throwStyledComponentsError(\n code: string | number,\n ...interpolations: Array<any>\n) {\n if (process.env.NODE_ENV === 'production') {\n throw new Error(\n `An error occurred. See https://git.io/JUIaE#${code} for more information.${\n interpolations.length > 0 ? ` Args: ${interpolations.join(', ')}` : "\n }`\n);\n } else {\n throw new Error(format(ERRORS[code], ...interpolations).trim());\n }\n}\n","export default {\"1\":\"Cannot create styled-component for component: %s.\\n\\n\",\"2\":\"Can't collect
styles once you've consumed a `ServerStyleSheet`'s styles! `ServerStyleSheet` is a one off instance for each server-side render cycle.\\n\\n- Are you trying to reuse it across renders?\\n- Are you accidentally calling collectStyles twice?\\n\\n\",\"3\":\"Streaming SSR is only supported in a Node.js environment; Please do not try to call this method in the browser.\\n\\n\",\"4\":\"The `StyleSheetManager` expects a valid target or sheet prop!\\n\\n- Does this error occur on the client and is your target falsy?\\n- Does this error occur on the server and is the sheet falsy?\\n\\n\",\"5\":\"The clone method cannot be used on the client!\\n\\n- Are you running in a client-like environment on the server?\\n- Are you trying to run SSR on the client?\\n\\n\",\"6\":\"Trying to insert a new style tag, but the given Node is unmounted!\\n\\n- Are you using a custom target that isn't mounted?\\n- Does your document not have a valid head element?\\n- Have you accidentally removed a style tag manually?\\n\\n\",\"7\":\"ThemeProvider:
Please return an object from your \\\"theme\\\" prop function, e.g.\\n\\n```js\\ntheme={() => ({})}\\n```\\n\\n\",\"8\":\"ThemeProvider: Please make your \\\"theme\\\" prop an object.\\n\\n\",\"9\":\"Missing document `<head>`\\n\\n\",\"10\":\"Cannot find a StyleSheet instance. Usually this happens if there are multiple copies of styled-components loaded at once. Check out this issue for how to troubleshoot and fix the common cases where this situation can happen: https://github.com/styled-components/styled-components/issues/1941#issuecomment-417862021\\n\\n\",\"11\":\"_This error was replaced with a dev-time warning, it will be deleted for v4 final._ [createGlobalStyle] received children which will not be rendered. Please use the component without passing children elements.\\n\\n\",\"12\":\"It seems you are interpolating a keyframe declaration (%s) into an untagged string. This was supported in styled-components v3, but is not longer supported in v4 as keyframes are now injected on-demand. Please wrap your string in the css\\`\\` helper which ensures the styles are injected correctly. See https://www.styled-components.com/docs/api#css\\n\\n\",\"13\":\"%s is not a styled component and cannot be referred to via component selector. See https://www.styled-components.com/docs/advanced#referring-to-other-components for more details.\\n\\n\",\"14\":\"ThemeProvider: \\\"theme\\\" prop is required.\\n\\n\",\"15\":\"A stylis plugin has been supplied that is not named. We need a name for each plugin to be able to prevent styling collisions between different stylis configurations within the same app. Before you pass your plugin to `<StyleSheetManager stylisPlugins={[]}>`, please make sure each plugin is uniquely-named, e.g.\\n\\n```js\\nObject.defineProperty(importedPlugin, 'name', { value: 'some-unique-name' });\\n```\\n\\n\",\"16\":\"Reached the limit of how many styled components may be created at group %s.\\nYou may only create up
to 1,073,741,824 components. If you're creating components dynamically,\\nas for instance in your render method then you may be running into this limitation.\\n\\n\",\"17\":\"CSSStyleSheet could not be found on HTMLStyleElement.\\nHas styled-components' style tag been unmounted or altered by another script?\\n\"};","// @flow\n/* eslint-disable no-use-before-define */\n\nimport type { GroupedTag, Tag } from './types';\nimport { SPLITTER } from '../constants';\nimport throwStyledError from '../utils/error';\n\n/** Create a GroupedTag with an

```
underlying Tag implementation */\nexport const makeGroupedTag = (tag: Tag): GroupedTag => {\n  return new DefaultGroupedTag(tag);\n};\n\nconst BASE_SIZE = 1 << 9;\n\nclass DefaultGroupedTag implements GroupedTag {\n  groupSizes: Uint32Array;\n\n  length: number;\n\n  tag: Tag;\n\n  constructor(tag: Tag) {\n    this.groupSizes = new Uint32Array(BASE_SIZE);\n    this.length = BASE_SIZE;\n    this.tag = tag;\n  }\n\n  indexOfGroup(group: number): number
  {\n    let index = 0;\n    for (let i = 0; i < group; i++) {\n      index += this.groupSizes[i];\n    }\n\n    return index;\n  }\n\n  insertRules(group: number, rules: string[]): void {\n    if (group >= this.groupSizes.length) {\n      const oldBuffer = this.groupSizes;\n      const oldSize = oldBuffer.length;\n\n      let newSize = oldSize;\n      while (group >= newSize) {\n        newSize <<= 1;\n        if (newSize < 0) {\n          throwStyledError(16, `${group}`);\n        }\n      }\n\n      this.groupSizes = new Uint32Array(newSize);\n      this.groupSizes.set(oldBuffer);\n      this.length = newSize;\n\n      for (let i = oldSize; i < newSize; i++) {\n        this.groupSizes[i] = 0;\n      }\n    }\n\n    let ruleIndex = this.indexOfGroup(group + 1);\n    for (let i = 0, l = rules.length; i < l; i++) {\n      if (this.tag.insertRule(ruleIndex, rules[i])) {\n        this.groupSizes[group]++;\n        ruleIndex++;\n      }\n    }\n  }\n\n  clearGroup(group: number): void {\n
    if (group < this.length) {\n      const length = this.groupSizes[group];\n      const startIndex = this.indexOfGroup(group);\n      const endIndex = startIndex + length;\n\n      this.groupSizes[group] = 0;\n\n      for (let i = startIndex; i < endIndex; i++) {\n        this.tag.deleteRule(startIndex);\n      }\n    }\n  }\n\n  getGroup(group: number): string {\n    let css = '';\n    if (group >= this.length || this.groupSizes[group] === 0) {\n      return css;\n    }\n\n    const length = this.groupSizes[group];\n    const startIndex = this.indexOfGroup(group);\n    const endIndex = startIndex + length;\n\n    for (let i = startIndex; i < endIndex; i++) {\n      css += `${this.tag.getRule(i)}${SPLITTER}`;\n    }\n\n    return css;\n  }\n}\n","// @flow\n\nimport throwStyledError from '../utils/error';\n\nconst MAX_SMI = 1 << 31 - 1;\n\nlet groupIDRegister: Map<string, number> = new Map();\nlet reverseRegister: Map<number, string> = new Map();\nlet nextFreeGroup = 1;\n\nexport const
  resetGroupIds = () => {\n  groupIDRegister = new Map();\n  reverseRegister = new Map();\n  nextFreeGroup = 1;\n};\n\nexport const getGroupForId = (id: string): number => {\n  if (groupIDRegister.has(id)) {\n    return (groupIDRegister.get(id): any);\n  }\n\n  while (reverseRegister.has(nextFreeGroup)) {\n    nextFreeGroup++;\n  }\n\n  const group = nextFreeGroup++;\n\n  if (\n    process.env.NODE_ENV !== 'production' &&\n    ((group | 0) < 0 || group > MAX_SMI)\n  ) {\n    throwStyledError(16, `${group}`);\n  }\n\n  groupIDRegister.set(id, group);\n  reverseRegister.set(group, id);\n  return group;\n};\n\nexport const getIdForGroup = (group: number): void | string => {\n  return reverseRegister.get(group);\n};\n\nexport const setGroupForId = (id: string, group: number) => {\n  if (group >= nextFreeGroup) {\n    nextFreeGroup = group + 1;\n  }\n\n  groupIDRegister.set(id, group);\n  reverseRegister.set(group, id);\n};\n","// @flow\n\nimport { SPLITTER, SC_ATTR, SC_ATTR_ACTIVE, SC_ATTR_VERSION,
  SC_VERSION } from '../constants';\nimport { getIdForGroup, setGroupForId } from './GroupIDAllocator';\nimport type { Sheet } from './types';\n\nconst SELECTOR = `style[${SC_ATTR}][${SC_ATTR_VERSION}=\"${SC_VERSION}\"]`;\nconst MARKER_RE = new RegExp(`^${SC_ATTR}\\\\.g(\\\\d+)\\\\[id=\"([\\\\w\\\\d-]+)\"\\\\].*?\"([^\"]*)`);\n\nexport const outputSheet = (sheet: Sheet) => {\n  const tag = sheet.getTag();\n  const { length } = tag;\n\n  let css = '';\n  for (let group = 0; group < length; group++) {\n    const id = getIdForGroup(group);\n    if (id === undefined) continue;\n\n    const names = sheet.names.get(id);\n    const rules = tag.getGroup(group);\n    if (!names || !rules || !names.size) continue;\n\n    const selector = `${SC_ATTR}.g${group}[id=\"${id}\"]`;\n\n    let content = '';\n    if (names !== undefined) {\n      names.forEach(name => {\n        if (name.length > 0) {\n          content += `${name},`;\n        }\n      });\n    }\n\n    // NOTE: It's easier to collect
  rules and have the marker\n    // after the actual rules to simplify the rehydration\n    css += `${rules}${selector}{content:\"${content}\"}${SPLITTER}`;\n  }\n\n  return css;\n};\n\nconst rehydrateNamesFromContent = (sheet: Sheet, id: string, content: string) => {\n  const names = content.split(',');\n  let name;\n\n  for (let i = 0, l = names.length; i < l; i++) {\n    // eslint-disable-next-line\n    if ((name = names[i])) {\n      sheet.registerName(id, name);\n    }\n  }\n};\n\nconst rehydrateSheetFromTag = (sheet: Sheet, style:
```

HTMLStyleElement) => {\n const parts = (style.textContent || '').split(SPLITTER);\n const rules: string[] = [];\n\n for (let i = 0, l = parts.length; i < l; i++) {\n   const part = parts[i].trim();\n   if (!part) continue;\n\n   const marker = part.match(MARKER_RE);\n\n   if (marker) {\n   const group = parseInt(marker[1], 10) | 0;\n   const id = marker[2];\n\n   if (group !== 0) {\n   // Rehydrate componentId to group index mapping\n
        setGroupForId(id, group);\n   // Rehydrate names and rules\n   // looks like: data-styled.g11[id=\"idA\"]{content:\"nameA,\"}\n   rehydrateNamesFromContent(sheet, id, marker[3]);\n   sheet.getTag().insertRules(group, rules);\n   }\n\n   rules.length = 0;\n   } else {\n   rules.push(part);\n   }\n }\n};\n\nexport const rehydrateSheet = (sheet: Sheet) => {\n const nodes = document.querySelectorAll(SELECTOR);\n\n for (let i = 0, l = nodes.length; i < l; i++) {\n   const node = ((nodes[i]: any): HTMLStyleElement);\n   if (node && node.getAttribute(SC_ATTR) !== SC_ATTR_ACTIVE) {\n   rehydrateSheetFromTag(sheet, node);\n\n   if (node.parentNode) {\n   node.parentNode.removeChild(node);\n   }\n   }\n }\n};\n","// @flow\n/* eslint-disable camelcase, no-undef */\n\ndeclare var __webpack_nonce__: string;\n\nconst getNonce = () => {\n return typeof __webpack_nonce__ !== 'undefined' ? __webpack_nonce__ : null;\n};\n\nexport default
 getNonce;\n","// @flow\n\nimport { SC_ATTR, SC_ATTR_ACTIVE, SC_ATTR_VERSION, SC_VERSION } from '../constants';\nimport getNonce from '../utils/nonce';\nimport throwStyledError from '../utils/error';\n\nconst ELEMENT_TYPE = 1; /* Node.ELEMENT_TYPE */\n\n/** Find last style element if any inside target */\nconst findLastStyleTag = (target: HTMLElement): void | HTMLStyleElement => {\n const { childNodes } = target;\n\n for (let i = childNodes.length; i >= 0; i--) {\n   const child = ((childNodes[i]: any): ?HTMLElement);\n   if (child && child.nodeType === ELEMENT_TYPE && child.hasAttribute(SC_ATTR)) {\n   return ((child: any): HTMLStyleElement);\n   }\n }\n\n return undefined;\n};\n\n/** Create a style element inside `target` or <head> after the last */\nexport const makeStyleTag = (target?: HTMLElement): HTMLStyleElement => {\n const head = ((document.head: any): HTMLElement);\n const parent = target || head;\n const style = document.createElement('style');\n const prevStyle
 = findLastStyleTag(parent);\n const nextSibling = prevStyle !== undefined ? prevStyle.nextSibling : null;\n\n style.setAttribute(SC_ATTR, SC_ATTR_ACTIVE);\n style.setAttribute(SC_ATTR_VERSION, SC_VERSION);\n\n const nonce = getNonce();\n\n if (nonce) style.setAttribute('nonce', nonce);\n\n parent.insertBefore(style, nextSibling);\n\n return style;\n};\n\n/** Get the CSSStyleSheet instance for a given style element */\nexport const getSheet = (tag: HTMLStyleElement): CSSStyleSheet => {\n if (tag.sheet) {\n   return ((tag.sheet: any): CSSStyleSheet);\n }\n\n // Avoid Firefox quirk where the style element might not have a sheet property\n const { styleSheets } = document;\n for (let i = 0, l = styleSheets.length; i < l; i++) {\n   const sheet = styleSheets[i];\n   if (sheet.ownerNode === tag) {\n   return ((sheet: any): CSSStyleSheet);\n   }\n }\n\n throwStyledError(17);\n return (undefined: any);\n};\n","// @flow\n/* eslint-disable no-use-before-define */\n\nimport
 { makeStyleTag, getSheet } from './dom';\nimport type { SheetOptions, Tag } from './types';\n\n/** Create a CSSStyleSheet-like tag depending on the environment */\nexport const makeTag = ({ isServer, useCSSOMInjection, target }: SheetOptions): Tag => {\n if (isServer) {\n   return new VirtualTag(target);\n } else if (useCSSOMInjection) {\n   return new CSSOMTag(target);\n } else {\n   return new TextTag(target);\n }\n};\n\nexport class CSSOMTag implements Tag {\n element: HTMLStyleElement;\n\n sheet: CSSStyleSheet;\n\n length: number;\n\n constructor(target?: HTMLElement) {\n   const element = (this.element = makeStyleTag(target));\n\n   // Avoid Edge bug where empty style elements don't create sheets\n   element.appendChild(document.createTextNode(''));\n\n   this.sheet = getSheet(element);\n   this.length = 0;\n }\n\n insertRule(index: number, rule: string): boolean {\n   try {\n   this.sheet.insertRule(rule, index);\n   this.length++;\n   return true;\n
    } catch (_error) {\n   return false;\n   }\n }\n\n deleteRule(index: number): void {\n   this.sheet.deleteRule(index);\n   this.length--;\n }\n\n getRule(index: number): string {\n   const rule = this.sheet.cssRules[index];\n   // Avoid IE11 quirk where cssText is inaccessible on some invalid rules\n   if (rule !== undefined && typeof rule.cssText === 'string') {\n   return rule.cssText;\n   } else {\n   return '';\n   }\n

}\n}\n\n/** A Tag that emulates the CSSStyleSheet API but uses text nodes */\nexport class TextTag implements Tag {\n element: HTMLStyleElement;\n\n nodes: NodeList<Node>;\n\n length: number;\n\n constructor(target?: HTMLElement) {\n   const element = (this.element = makeStyleTag(target));\n   this.nodes = element.childNodes;\n   this.length = 0;\n }\n\n insertRule(index: number, rule: string): boolean {\n   if (index <= this.length && index >= 0) {\n   const node = document.createTextNode(rule);\n   const refNode = this.nodes[index];\n
      this.element.insertBefore(node, refNode || null);\n   this.length++;\n   return true;\n   } else {\n   return false;\n   }\n }\n\n deleteRule(index: number): void {\n   this.element.removeChild(this.nodes[index]);\n   this.length--;\n }\n\n getRule(index: number): string {\n   if (index < this.length) {\n   return this.nodes[index].textContent;\n   } else {\n   return '';\n   }\n }\n}\n\n/** A completely virtual (server-side) Tag that doesn't manipulate the DOM */\nexport class VirtualTag implements Tag {\n rules: string[];\n\n length: number;\n\n constructor(_target?: HTMLElement) {\n   this.rules = [];\n   this.length = 0;\n }\n\n insertRule(index: number, rule: string): boolean {\n   if (index <= this.length) {\n   this.rules.splice(index, 0, rule);\n   this.length++;\n   return true;\n   } else {\n   return false;\n   }\n }\n\n deleteRule(index: number): void {\n   this.rules.splice(index, 1);\n   this.length--;\n
  }\n\n getRule(index: number): string {\n   if (index < this.length) {\n   return this.rules[index];\n   } else {\n   return '';\n   }\n }\n}\n","// @flow\nimport { DISABLE_SPEEDY, IS_BROWSER } from '../constants';\nimport { EMPTY_OBJECT } from '../utils/empties';\nimport { makeGroupedTag } from './GroupedTag';\nimport { getGroupForId } from './GroupIDAllocator';\nimport { outputSheet, rehydrateSheet } from './Rehydration';\nimport { makeTag } from './Tag';\nimport type { GroupedTag, Sheet, SheetOptions } from './types';\n\nlet SHOULD_REHYDRATE = IS_BROWSER;\n\ntype SheetConstructorArgs = {\n isServer?: boolean,\n useCSSOMInjection?: boolean,\n target?: HTMLElement,\n};\n\ntype GlobalStylesAllocationMap = { [key: string]: number };\ntype NamesAllocationMap = Map<string, Set<string>>;\n\nconst defaultOptions: SheetOptions = {\n isServer: !IS_BROWSER,\n useCSSOMInjection: !DISABLE_SPEEDY,\n};\n\n/** Contains the main stylesheet logic for stringification and caching */\nexport
  default class StyleSheet implements Sheet {\n gs: GlobalStylesAllocationMap;\n\n names: NamesAllocationMap;\n\n options: SheetOptions;\n\n server: boolean;\n\n tag: void | GroupedTag;\n\n /** Register a group ID to give it an index */\n static registerId(id: string): number {\n   return getGroupForId(id);\n }\n\n constructor(\n   options: SheetConstructorArgs = EMPTY_OBJECT,\n   globalStyles?: GlobalStylesAllocationMap = {},\n   names?: NamesAllocationMap\n) {\n   this.options = {\n   ...defaultOptions,\n   ...options,\n   };\n\n   this.gs = globalStyles;\n   this.names = new Map(names);\n   this.server = !!options.isServer;\n\n   // We rehydrate only once and use the sheet that is created first\n   if (!this.server && IS_BROWSER && SHOULD_REHYDRATE) {\n   SHOULD_REHYDRATE = false;\n   rehydrateSheet(this);\n   }\n }\n\n reconstructWithOptions(options: SheetConstructorArgs, withNames?: boolean = true) {\n   return new StyleSheet(\n   { ...this.options,
  ...options },\n   this.gs,\n   (withNames && this.names) || undefined\n   );\n }\n\n allocateGSInstance(id: string) {\n   return (this.gs[id] = (this.gs[id] || 0) + 1);\n }\n\n /** Lazily initialises a GroupedTag for when it's actually needed */\n getTag(): GroupedTag {\n   return this.tag || (this.tag = makeGroupedTag(makeTag(this.options)));\n }\n\n /** Check whether a name is known for caching */\n hasNameForId(id: string, name: string): boolean {\n   return this.names.has(id) && (this.names.get(id): any).has(name);\n }\n\n /** Mark a group's name as known for caching */\n registerName(id: string, name: string) {\n   getGroupForId(id);\n\n   if (!this.names.has(id)) {\n   const groupNames = new Set();\n   groupNames.add(name);\n   this.names.set(id, groupNames);\n   } else {\n   (this.names.get(id): any).add(name);\n   }\n }\n\n /** Insert new rules which also marks the name as known */\n insertRules(id: string, name: string, rules:
  string[]) {\n   this.registerName(id, name);\n   this.getTag().insertRules(getGroupForId(id), rules);\n }\n\n /** Clears all cached names for a given group ID */\n clearNames(id: string) {\n   if (this.names.has(id)) {\n   (this.names.get(id): any).clear();\n   }\n }\n\n /** Clears all rules for a given group ID */\n clearRules(id: string)

```
{\n    this.getTag().clearGroup(getGroupForId(id));\n    this.clearNames(id);\n  }\n\n  /** Clears the entire tag which deletes all rules but not its names */\n  clearTag() {\n    // NOTE: This does not clear the names, since it's only used during SSR\n    // so that we can continuously output only new rules\n    this.tag = undefined;\n  }\n\n  /** Outputs the current sheet as a CSS string with markers for SSR */\n  toString(): string {\n    return outputSheet(this);\n  }\n}\n","// @flow\n/* eslint-disable no-bitwise */\n\nconst AD_REPLACER_R = /(a)(d)/gi;\n\n/* This is the \"capacity\" of our alphabet i.e. 2x26 for all letters plus
 their capitalised\n * counterparts */\nconst charsLength = 52;\n\n/* start at 75 for 'a' until 'z' (25) and then start at 65 for capitalised letters */\nconst getAlphabeticChar = (code: number): string =>\n  String.fromCharCode(code + (code > 25 ? 39 : 97));\n\n/* input a number, usually a hash and convert it to base-52 */\nexport default function generateAlphabeticName(code: number): string {\n  let name = '';\n  let x;\n\n  /* get a char and divide by alphabet-length */\n  for (x = Math.abs(code); x > charsLength; x = (x / charsLength) | 0) {\n    name = getAlphabeticChar(x % charsLength) + name;\n  }\n\n  return (getAlphabeticChar(x % charsLength) + name).replace(AD_REPLACER_R, '$1-$2');\n}\n","// @flow\n/* eslint-disable */\n\nexport const SEED = 5381;\n\n// When we have separate strings it's useful to run a progressive\n// version of djb2 where we pretend that we're still looping over\n// the same string\nexport const phash = (h: number, x: string): number => {\n  let i = x.length;\n\n
  while (i) {\n    h = (h * 33) ^ x.charCodeAt(--i);\n  }\n\n  return h;\n};\n\n// This is a djb2 hashing function\nexport const hash = (x: string): number => {\n  return phash(SEED, x);\n};\n","// @flow\nimport { SC_VERSION } from '../constants';\nimport StyleSheet from '../sheet';\nimport type { RuleSet, Stringifier } from '../types';\nimport flatten from '../utils/flatten';\nimport generateName from '../utils/generateAlphabeticName';\nimport { hash, phash } from '../utils/hash';\nimport isStaticRules from '../utils/isStaticRules';\n\nconst SEED = hash(SC_VERSION);\n\n/**\n * ComponentStyle is all the CSS-specific stuff, not the React-specific stuff.\n */\nexport default class ComponentStyle {\n  baseHash: number;\n\n  baseStyle: ?ComponentStyle;\n\n  componentId: string;\n\n  isStatic: boolean;\n\n  rules: RuleSet;\n\n  staticRulesId: string;\n\n  constructor(rules: RuleSet, componentId: string, baseStyle?: ComponentStyle) {\n    this.rules = rules;\n    this.staticRulesId = '';\n
    this.isStatic = process.env.NODE_ENV === 'production' &&\n      (baseStyle === undefined || baseStyle.isStatic) &&\n      isStaticRules(rules);\n    this.componentId = componentId;\n\n    // SC_VERSION gives us isolation between multiple runtimes on the page at once\n    // this is improved further with use of the babel plugin \"namespace\" feature\n    this.baseHash = phash(SEED, componentId);\n\n    this.baseStyle = baseStyle;\n\n    // NOTE: This registers the componentId, which ensures a consistent order\n    // for this component's styles compared to others\n    StyleSheet.registerId(componentId);\n  }\n\n  /*\n   * Flattens a rule set into valid CSS\n   * Hashes it, wraps the whole chunk in a .hash1234 {}\n   * Returns the hash to be injected on render()\n   * */\n  generateAndInjectStyles(executionContext: Object, styleSheet: StyleSheet, stylis: Stringifier) {\n    const { componentId } = this;\n\n    const names = [];\n\n    if (this.baseStyle) {\n      names.push(this.baseStyle.generateAndInjectStyles(executionContext,
 styleSheet, stylis));\n    }\n\n    // force dynamic classnames if user-supplied stylis plugins are in use\n    if (this.isStatic && !stylis.hash) {\n      if (this.staticRulesId && styleSheet.hasNameForId(componentId, this.staticRulesId)) {\n        names.push(this.staticRulesId);\n      } else {\n        const cssStatic = flatten(this.rules, executionContext, styleSheet, stylis).join('');\n        const name = generateName(phash(this.baseHash, cssStatic) >>> 0);\n\n        if (!styleSheet.hasNameForId(componentId, name)) {\n          const cssStaticFormatted = stylis(cssStatic, `.${name}`, undefined, componentId);\n\n          styleSheet.insertRules(componentId, name, cssStaticFormatted);\n
    }\n\n        names.push(name);\n        this.staticRulesId = name;\n      }\n    } else {\n      const { length } = this.rules;\n      let dynamicHash = phash(this.baseHash, stylis.hash);\n      let css = '';\n\n      for (let i = 0; i < length; i++) {\n        const partRule = this.rules[i];\n\n        if (typeof partRule === 'string') {\n          css += partRule;\n\n
  if (process.env.NODE_ENV !== 'production') dynamicHash = phash(dynamicHash, partRule + i);\n        } else if (partRule) {\n          const partChunk = flatten(partRule, executionContext, styleSheet, stylis);\n          const partString = Array.isArray(partChunk) ? partChunk.join('') : partChunk;\n          dynamicHash = phash(dynamicHash, partString + i);\n          css += partString;\n        }\n      }\n\n      if (css) {\n        const name =
```

```
generateName(dynamicHash >>> 0);\n\n        if (!styleSheet.hasNameForId(componentId, name)) {\n          const cssFormatted = stylis(css, `.${name}`, undefined, componentId);\n          styleSheet.insertRules(componentId, name, cssFormatted);\n        }\n\n        names.push(name);\n      }\n    }\n\n    return names.join(' ');\n  }\n}\n","function stylis_min (W) {\n  function M(d, c, e, h, a) {\n    for (var m = 0, b = 0, v = 0, n = 0, q, g, x = 0, K = 0, k, u = k = q = 0, l = 0, r = 0, I = 0, t = 0, B = e.length, J = B - 1, y, f = '', p = '', F = '', G = '', C; l < B;) {\n      g = e.charCodeAt(l);\n      l === J && 0 !== b + n + v + m && (0 !== b && (g = 47 === b ? 10 : 47), n = v = m = 0, B++, J++);\n\n      if (0 === b + n + v + m) {\n        if (l === J && (0 < r && (f = f.replace(N, '')), 0 < f.trim().length)) {\n          switch (g) {\n            case 32:\n            case 9:\n            case 59:\n            case 13:\n            case 10:\n              break;\n\n            default:\n              f += e.charAt(l);\n          }\n\n          g = 59;\n        }\n\n        switch (g) {\n          case 123:\n            f = f.trim();\n            q = f.charCodeAt(0);\n            k = 1;\n\n            for (t = ++l; l < B;) {\n              switch (g = e.charCodeAt(l)) {\n                case 123:\n                  k++;\n                  break;\n\n                case 125:\n                  k--;\n                  break;\n\n                case 47:\n                  switch (g = e.charCodeAt(l + 1)) {\n                    case 42:\n                    case 47:\n                      a: {\n                        for (u = l + 1; u < J; ++u) {\n                          switch (e.charCodeAt(u)) {\n                            case 47:\n                              if (42 === g && 42 === e.charCodeAt(u - 1) && l + 2 !== u) {\n                                l = u + 1;\n                                break a;\n                              }\n\n                              break;\n\n                            case 10:\n                              if (47 === g) {\n                                l = u + 1;\n                                break a;\n                              }\n\n                          }\n                        }\n\n                        l = u;\n                      }\n\n                  }\n\n                  break;\n\n                case 91:\n                  g++;\n\n                case 40:\n                  g++;\n\n                case 34:\n                case 39:\n                  for (; l++ < J && e.charCodeAt(l) !== g;) {\n                  }\n\n                  if (0 === k) break;\n                  l++;\n              }\n\n              k = e.substring(t, l);\n              0 === q && (q = (f = f.replace(ca, '').trim()).charCodeAt(0));\n\n              switch (q) {\n                case 64:\n                  0 < r && (f = f.replace(N, ''));\n                  g = f.charCodeAt(1);\n\n                  switch (g) {\n                    case 100:\n                    case 109:\n                    case 115:\n                    case 45:\n                      r = c;\n                      break;\n\n                    default:\n                      r = O;\n                  }\n\n                  k = M(c, r, k, g, a + 1);\n                  t = k.length;\n                  0 < A && (r = X(O, f, I), C = H(3, k, r, c, D, z, t, g, a, h), f = r.join(''), void 0 !== C && 0 === (t = (k = C.trim()).length) && (g = 0, k = ''));\n                  if (0 < t) switch (g) {\n                    case 115:\n                      f = f.replace(da, ea);\n\n                    case 100:\n                    case 109:\n                    case 45:\n                      k = f + '{' + k + '}';\n                      break;\n\n                    case 107:\n                      f = f.replace(fa, '$1 $2');\n                      k = f + '{' + k + '}';\n                      k = 1 === w || 2 === w && L('@' + k, 3) ? '@-webkit-' + k + '@' + k : '@' + k;\n                      break;\n\n                    default:\n                      k = f + k, 112 === h && (k = (p += k, ''));\n                  } else k = '';\n                  break;\n\n                default:\n                  k = M(c, X(c, f, I), k, h, a + 1);\n              }\n\n              F += k;\n              k = I = r = u = q = 0;\n              f = '';\n              g = e.charCodeAt(++l);\n\n            break;\n\n          case 125:\n          case 59:\n            f = (0 < r ? f.replace(N, '') : f).trim();\n            if (1 < (t = f.length)) switch (0 === u && (q = f.charCodeAt(0), 45 === q || 96 < q && 123 > q) && (t = (f = f.replace(' ', ':')).length), 0 < A && void 0 !== (C = H(1, f, c, d, D, z, p.length, h, a, h)) && 0 === (t = (f = C.trim()).length) && (f = '\\x00\\x00'), q = f.charCodeAt(0), g = f.charCodeAt(1), q) {\n              case 0:\n                break;\n\n              case 64:\n                if (105 === g || 99 === g) {\n                  G += f + e.charAt(l);\n                  break;\n                }\n\n              default:\n                58 !== f.charCodeAt(t - 1) && (p += P(f, q, g, f.charCodeAt(2)));\n            }\n\n            I = r = u = q = 0;\n            f = '';\n            g = e.charCodeAt(++l);\n          }\n        }\n\n        switch (g) {\n          case 13:\n          case 10:\n            47 === b ? b = 0 : 0 === 1 + q && 107 !== h && 0 < f.length && (r = 1, f += '\\x00');\n            0 < A * Y && H(0, f, c, d, D, z, p.length, h, a, h);\n            z = 1;\n            D++;\n            break;\n\n          case 59:\n          case 125:\n            if (0 === b + n + v + m) {\n              z++;\n              break;\n            }\n\n          default:\n            z++;\n            y = e.charAt(l);\n\n            switch (g) {\n              case 9:\n              case 32:\n                if (0 === n + m + b) switch (x) {\n                  case 44:\n                  case 58:\n                  case 9:\n                  case 32:\n                    y = '';\n                    break;\n\n                  default:\n                    32 !== g && (y = ' ');\n                }\n
```

```
break;\n\n          case 0:\n          y = '\\\\0';\n          break;\n\n          case 12:\n          y = '\\\\f';\n
break;\n\n          case 11:\n          y = '\\\\v';\n          break;\n\n          case 38:\n          0 === n + b + m && (r
= I
 = 1, y = '\\f' + y);\n          break;\n\n          case 108:\n          if (0 === n + b + m + E && 0 < u) switch (l - u)
{\n          case 2:\n          112 === x && 58 === e.charCodeAt(l - 3) && (E = x);\n\n          case 8:\n
      111 === K && (E = K);\n          }\n          break;\n\n          case 58:\n          0 === n + b + m && (u =
l);\n          break;\n\n          case 44:\n          0 === b + v + n + m && (r = 1, y += '\\r');\n          break;\n\n
  case 34:\n          case 39:\n          0 === b && (n = n === g ? 0 : 0 === n ? g : n);\n          break;\n\n
case 91:\n          0 === n + b + v && m++;\n          break;\n\n          case 93:\n          0 === n + b + v && m--
;\n          break;\n\n          case 41:\n          0 === n + b + m && v--;\n          break;\n\n          case 40:\n
   if (0 === n + b + m) {\n          if
 (0 === q) switch (2 * x + 3 * K) {\n          case 533:\n          break;\n\n          default:\n          q
= 1;\n          }\n          v++;\n          }\n\n          break;\n\n          case 64:\n          0 === b + v + n + m
+ u + k && (k = 1);\n          break;\n\n          case 42:\n          case 47:\n          if (!(0 < n + m + v)) switch (b)
{\n          case 0:\n          switch (2 * g + 3 * e.charCodeAt(l + 1)) {\n          case 235:\n          b
= 47;\n          break;\n\n          case 220:\n          t = l, b = 42;\n          }\n\n
break;\n\n          case 42:\n          47 === g && 42 === x && t + 2 !== l && (33 === e.charCodeAt(t + 2)
&& (p += e.substring(t, l + 1)), y = '', b = 0);\n          }\n          }\n\n          0 === b && (f += y);\n          }\n\n          K =
x;\n          x = g;\n
  l++;\n          }\n\n          t = p.length;\n\n          if (0 < t) {\n          r = c;\n          if (0 < A && (C = H(2, p, r, d, D, z, t, h, a, h), void 0
!== C && 0 === (p = C).length)) return G + p + F;\n          p = r.join(',') + '{' + p + '}';\n\n          if (0 !== w * E) {\n
2 !== w || L(p, 2) || (E = 0);\n\n          switch (E) {\n          case 111:\n          p = p.replace(ha, ':-moz-$1') + p;\n
break;\n\n          case 112:\n          p = p.replace(Q, '::-webkit-input-$1') + p.replace(Q, '::-moz-$1') + p.replace(Q,
':-ms-input-$1') + p;\n          }\n\n          E = 0;\n          }\n          }\n\n          return G + p + F;\n          }\n\n  function X(d, c, e) {\n          var
h = c.trim().split(ia);\n          c = h;\n          var a = h.length,\n          m = d.length;\n\n          switch (m) {\n          case 0:\n          case
1:\n          var b = 0;\n\n          for (d = 0 === m ? '' : d[0] + ' '; b < a; ++b) {\n          c[b] = Z(d, c[b], e).trim();\n
}\n\n          break;\n\n          default:\n          var v = b = 0;\n\n          for (c = [];
 b < a; ++b) {\n          for (var n = 0; n < m; ++n) {\n          c[v++] = Z(d[n] + ' ', h[b], e).trim();\n          }\n
}\n\n          }\n\n          return c;\n          }\n\n  function Z(d, c, e) {\n          var h = c.charCodeAt(0);\n          33 > h && (h = (c =
c.trim()).charCodeAt(0));\n\n          switch (h) {\n          case 38:\n          return c.replace(F, '$1' + d.trim());\n\n          case 58:\n
      return d.trim() + c.replace(F, '$1' + d.trim());\n\n          default:\n          if (0 < 1 * e && 0 < c.indexOf('\\f')) return
c.replace(F, (58 === d.charCodeAt(0) ? '' : '$1') + d.trim());\n          }\n\n          return d + c;\n          }\n\n  function P(d, c, e, h)
{\n          var a = d + ';',\n          m = 2 * c + 3 * e + 4 * h;\n\n          if (944 === m) {\n          d = a.indexOf(':', 9) + 1;\n          var b
= a.substring(d, a.length - 1).trim();\n          b = a.substring(0, d).trim() + b + ';';\n          return 1 === w || 2 === w &&
L(b, 1) ? '-webkit-' + b + b : b;\n          }\n\n          if (0 === w || 2 === w && !L(a, 1)) return a;\n\n          switch (m) {\n
      case 1015:\n          return 97 === a.charCodeAt(10) ? '-webkit-' + a + a : a;\n\n          case 951:\n          return 116 ===
a.charCodeAt(3) ? '-webkit-' + a + a : a;\n\n          case 963:\n          return 110 === a.charCodeAt(5) ? '-webkit-' + a + a :
a;\n\n          case 1009:\n          if (100 !== a.charCodeAt(4)) break;\n\n          case 969:\n          case 942:\n          return '-
webkit-' + a + a;\n\n          case 978:\n          return '-webkit-' + a + '-moz-' + a + a;\n\n          case 1019:\n          case 983:\n
return '-webkit-' + a + '-moz-' + a + '-ms-' + a + a;\n\n          case 883:\n          if (45 === a.charCodeAt(8)) return '-
webkit-' + a + a;\n          if (0 < a.indexOf('image-set(', 11)) return a.replace(ja, '$1-webkit-$2') + a;\n          break;\n\n
 case 932:\n          if (45 === a.charCodeAt(4)) switch (a.charCodeAt(5)) {\n          case 103:\n          return '-webkit-
box-' + a.replace('-grow', '') + '-webkit-' + a + '-ms-' + a.replace('grow', 'positive') + a;\n\n          case 115:\n
          return '-webkit-' + a + '-ms-' + a.replace('shrink', 'negative') + a;\n\n          case 98:\n          return '-webkit-' + a
+ '-ms-' + a.replace('basis', 'preferred-size') + a;\n          }\n          return '-webkit-' + a + '-ms-' + a + a;\n\n          case
964:\n          return '-webkit-' + a + '-ms-flex-' + a + a;\n\n          case 1023:\n          if (99 !== a.charCodeAt(8)) break;\n
  b = a.substring(a.indexOf(':', 15)).replace('flex-', '').replace('space-between', 'justify');\n          return '-webkit-box-
pack' + b + '-webkit-' + a + '-ms-flex-pack' + b + a;\n\n          case 1005:\n          return ka.test(a) ? a.replace(aa, ':-
```

```
webkit-') + a.replace(aa, ':-moz-') + a : a;\n\n      case 1e3:\n        b = a.substring(13).trim();\n        c = b.indexOf('-') + 1;\n\n        switch (b.charCodeAt(0) + b.charCodeAt(c)) {\n          case 226:\n            b = a.replace(G, 'tb');\n            break;\n\n          case 232:\n            b = a.replace(G, 'tb-rl');\n            break;\n\n          case 220:\n            b = a.replace(G, 'lr');\n            break;\n\n          default:\n            return a;\n        }\n\n        return '-webkit-' + a + '-ms-' + b + a;\n\n      case 1017:\n        if (-1 === a.indexOf('sticky', 9)) break;\n\n      case 975:\n        c = (a = d).length - 10;\n        b = (33 === a.charCodeAt(c) ? a.substring(0, c) : a).substring(d.indexOf(':', 7) + 1).trim();\n\n        switch (m = b.charCodeAt(0) + (b.charCodeAt(7) | 0)) {\n          case 203:\n            if (111 > b.charCodeAt(8)) break;\n\n          case 115:\n            a = a.replace(b, '-webkit-' + b) + ';' + a;\n            break;\n\n          case 207:\n          case 102:\n            a = a.replace(b, '-webkit-' + (102 < m ? 'inline-' : '') + 'box') + ';' + a.replace(b, '-webkit-' + b) + ';' + a.replace(b, '-ms-' + b + 'box') + ';' + a;\n        }\n\n        return a + ';';\n\n      case 938:\n        if (45 === a.charCodeAt(5)) switch (a.charCodeAt(6)) {\n          case 105:\n            return b = a.replace('-items', ''), '-webkit-' + a + '-webkit-box-' + b + '-ms-flex-' + b + a;\n\n          case 115:\n            return '-webkit-' + a + '-ms-flex-item-' + a.replace(ba, '') + a;\n\n          default:\n            return '-webkit-' + a + '-ms-flex-line-pack' + a.replace('align-content', '').replace(ba, '') + a;\n        }\n        break;\n\n      case 973:\n      case 989:\n        if (45 !== a.charCodeAt(3) || 122 === a.charCodeAt(4)) break;\n\n      case 931:\n      case 953:\n        if (!0 === la.test(d)) return 115 === (b = d.substring(d.indexOf(':') + 1)).charCodeAt(0) ? P(d.replace('stretch', 'fill-available'), c, e, h).replace(':fill-available', ':stretch') : a.replace(b, '-webkit-' + b) + a.replace(b, '-moz-' + b.replace('fill-', '')) + a;\n        break;\n\n      case 962:\n        if (a = '-webkit-' + a + (102 === a.charCodeAt(5) ? '-ms-' + a : '') + a, 211 === e + h && 105 === a.charCodeAt(13) && 0 < a.indexOf('transform', 10)) return a.substring(0, a.indexOf(';',
 27) + 1).replace(ma, '$1-webkit-$2') + a;\n    }\n\n    return a;\n  }\n\n  function L(d, c) {\n    var e = d.indexOf(1 === c ? ':' : '{'),\n        h = d.substring(0, 3 !== c ? e : 10);\n    e = d.substring(e + 1, d.length - 1);\n    return R(2 !== c ? h : h.replace(na, '$1'), e, c);\n  }\n\n  function ea(d, c) {\n    var e = P(c, c.charCodeAt(0), c.charCodeAt(1), c.charCodeAt(2));\n    return e !== c + ';' ? e.replace(oa, ' or ($1)').substring(4) : '(' + c + ')';\n  }\n\n  function H(d, c, e, h, a, m, b, v, n, q) {\n    for (var g = 0, x = c, w; g < A; ++g) {\n      switch (w = S[g].call(B, d, x, e, h, a, m, b, v, n, q)) {\n        case void 0:\n        case !1:\n        case !0:\n        case null:\n          break;\n\n        default:\n          x = w;\n      }\n    }\n\n    if (x !== c) return x;\n  }\n\n  function T(d) {\n    switch (d) {\n      case void 0:\n      case null:\n        A = S.length = 0;\n        break;\n\n      default:\n        if ('function' === typeof
 d) S[A++] = d;else if ('object' === typeof d) for (var c = 0, e = d.length; c < e; ++c) {\n          T(d[c]);\n        } else Y = !!d | 0;\n    }\n\n    return T;\n  }\n\n  function U(d) {\n    d = d.prefix;\n    void 0 !== d && (R = null, d ? 'function' !== typeof d ? w = 1 : (w = 2, R = d) : w = 0);\n    return U;\n  }\n\n  function B(d, c) {\n    var e = d;\n    33 > e.charCodeAt(0) && (e = e.trim());\n    V = e;\n    e = [V];\n\n    if (0 < A) {\n      var h = H(-1, c, e, e, D, z, 0, 0, 0, 0);\n      void 0 !== h && 'string' === typeof h && (c = h);\n    }\n\n    var a = M(O, e, c, 0, 0);\n    0 < A && (h = H(-2, a, e, e, D, z, a.length, 0, 0, 0), void 0 !== h && (a = h));\n    V = '';\n    E = 0;\n    z = D = 1;\n    return a;\n  }\n\n  var ca = /^\\0+/g,\n      N = /[\\0\\r\\f]/g,\n      aa = /: */g,\n      ka = /zoo|gra/,\n      ma = /([,: ])(transform)/g,\n      ia = /,\\r+?/g,\n      F = /([\\t\\r\\n ])*\\f?&/g,\n      fa = /@(k\\w+)\\s*(\\S*)\\s*/,\n      Q = /::(place)/g,\n      ha = /:(read-only)/g,\n      G = /[svh]\\w+-[tblr]{2}/,\n      da = /\\(\\s*(.*)\\s*\\)/g,\n      oa = /([\\s\\S]*?);/g,\n      ba = /-self|flex-/g,\n      na = /[^]*?(:[rp][el]a[\\w-]+)[^]*/,\n      la = /stretch|:\\s*\\w+\\-(?:conte|avail)/,\n      ja = /([^-])(image-set\\()/,\n      z = 1,\n      D = 1,\n      E = 0,\n      w = 1,\n      O = [],\n      S = [],\n      A = 0,\n      R = null,\n      Y = 0,\n      V = '';\n  B.use = T;\n  B.set = U;\n  void 0 !== W && U(W);\n  return B;\n}\n\nexport default stylis_min;\n","import Stylis from '@emotion/stylis';\nimport { type Stringifier } from '../types';\nimport { EMPTY_ARRAY, EMPTY_OBJECT } from './empties';\nimport throwStyledError from './error';\nimport { phash, SEED } from './hash';\nimport insertRulePlugin from './stylisPluginInsertRule';\n\nconst COMMENT_REGEX = /^\\s*\\/\\/.*$/gm;\nconst COMPLEX_SELECTOR_PREFIX = [':', '[', '.', '#'];\n\ntype StylisInstanceConstructorArgs = {\n  options?: Object,\n  plugins?: Array<Function>,\n};\n\nexport
 default function createStylisInstance({\n  options = EMPTY_OBJECT,\n  plugins = EMPTY_ARRAY,\n}: StylisInstanceConstructorArgs = EMPTY_OBJECT) {\n  const stylis = new Stylis(options);\n\n  // Wrap `insertRulePlugin to build a list of rules,\n  // and then make our own plugin to return the rules. This\n  // makes it
```

easier to hook into the existing SSR architecture\n\n let parsingRules = [];\n\n // eslint-disable-next-line consistent-return\n const returnRulesPlugin = context => {\n   if (context === -2) {\n   const parsedRules = parsingRules;\n   parsingRules = [];\n   return parsedRules;\n   }\n };\n\n const parseRulesPlugin = insertRulePlugin(rule => {\n parsingRules.push(rule);\n });\n\n let _componentId: string;\n let _selector: string;\n let _selectorRegexp: RegExp;\n let _consecutiveSelfRefRegExp: RegExp;\n\n const selfReferenceReplacer = (match, offset, string) => {\n   if (\n   // do not replace the first occurrence if it is complex
 (has a modifier)\n   (offset === 0 ? COMPLEX_SELECTOR_PREFIX.indexOf(string[_selector.length]) === -1 : true) &&\n   // no consecutive self refs (.b.b); that is a precedence boost and treated differently\n !string.match(_consecutiveSelfRefRegExp)\n   ) {\n   return `.${_componentId}`;\n   }\n\n   return match;\n };\n\n /**\n   * When writing a style like\n   *\n   * & + & {\n   *   color: red;\n   * }\n   *\n   * The second ampersand should be a reference to the static component class. stylis\n   * has no knowledge of static class so we have to intelligently replace the base selector.\n   *\n   * https://github.com/thysultan/stylis.js/tree/v3.5.4#plugins <- more info about the context phase values\n   * \"2\" means this plugin is taking effect at the very end after all other processing is complete\n   */\n const selfReferenceReplacementPlugin = (context, _, selectors) => {\n   if (context === 2 && selectors.length && selectors[0].lastIndexOf(_selector) > 0) {\n
      // eslint-disable-next-line no-param-reassign\n   selectors[0] = selectors[0].replace(_selectorRegexp, selfReferenceReplacer);\n   }\n };\n\n stylis.use([...plugins, selfReferenceReplacementPlugin, parseRulesPlugin, returnRulesPlugin]);\n\n function stringifyRules(css, selector, prefix, componentId = '&'): Stringifier {\n   const flatCSS = css.replace(COMMENT_REGEX, '');\n   const cssStr = selector && prefix ? `${prefix} ${selector} { ${flatCSS} }` : flatCSS;\n\n   // stylis has no concept of state to be passed to plugins\n   // but since JS is single-threaded, we can rely on that to ensure\n   // these properties stay in sync with the current stylis run\n   _componentId = componentId;\n   _selector = selector;\n   _selectorRegexp = new RegExp(`\\\\${_selector}\\\\b`, 'g');\n   _consecutiveSelfRefRegExp = new RegExp(`(\\\\${_selector}\\\\b){2,}`);\n\n   return stylis(prefix || !selector ? '' : selector, cssStr);\n }\n\n stringifyRules.hash = plugins.length\n
    ? plugins\n   .reduce((acc, plugin) => {\n   if (!plugin.name) {\n   throwStyledError(15);\n   }\n\n   return phash(acc, plugin.name);\n   }, SEED)\n   .toString()\n   : '';\n\n return stringifyRules;\n}\n","/**\n * MIT License\n *\n * Copyright (c) 2016 Sultan Tarimo\n *\n * Permission is hereby granted, free of charge, to any person obtaining a copy of\n * this software and associated documentation files (the \"Software\"),\n * to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or\n * sell copies of the Software and to permit persons to whom the Software is furnished to do so, subject to the following conditions:\n *\n * The above copyright notice and this permission notice shall be included in all\n * copies or substantial portions of the Software.\n *\n * THE SOFTWARE IS PROVIDED \"AS IS\", WITHOUT WARRANTY OF ANY KIND, EXPRESS\n * OR
 IMPLIED INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,\n * FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE\n * AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,\n * WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR\n * IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.\n */\n/* eslint-disable */\n\nexport default function(insertRule) {\n const delimiter = '/*|*/';\n const needle = `${delimiter}}`;\n\n function toSheet(block) {\n   if (block) {\n   try {\n   insertRule(`${block}}`);\n   } catch (e) {}\n   }\n }\n\n return function ruleSheet(\n   context,\n   content,\n   selectors,\n   parents,\n   line,\n   column,\n   length,\n   ns,\n   depth,\n   at\n) {\n   switch (context) {\n   // property\n   case 1:\n   // @import\n   if (depth === 0 && content.charCodeAt(0) === 64) return insertRule(`${content};`), '';\n   break;\n   // selector\n   case 2:\n   if (ns === 0) return content + delimiter;\n   break;\n   // at-rule\n   case 3:\n   switch (ns) {\n   // @font-face, @page\n   case 102:\n   case 112:\n   return insertRule(selectors[0] + content), '';\n   default:\n   return content + (at === 0 ? delimiter : '');\n   }\n   case -2:\n   content.split(needle).forEach(toSheet);\n   }\n };\n}\n","// @flow\nimport React, { type Context, type Node, useContext, useEffect, useMemo, useState } from 'react';\nimport shallowequal from

'shallowequal';\nimport StyleSheet from '../sheet';\nimport type { Stringifier } from '../types';\nimport createStylisInstance from '../utils/stylis';\n\ntype Props = {\n children?: Node,\n disableCSSOMInjection?: boolean,\n disableVendorPrefixes?: boolean,\n sheet?: StyleSheet,\n stylisPlugins?: Array<Function>,\n target?: HTMLElement,\n};\n\nexport const StyleSheetContext: Context<StyleSheet | void> = React.createContext();\nexport const StyleSheetConsumer = StyleSheetContext.Consumer;\nexport const StylisContext: Context<Stringifier | void> = React.createContext();\nexport const StylisConsumer = StylisContext.Consumer;\n\nexport const masterSheet: StyleSheet = new StyleSheet();\nexport const masterStylis: Stringifier = createStylisInstance();\n\nexport function useStyleSheet(): StyleSheet {\n return useContext(StyleSheetContext) || masterSheet;\n}\n\nexport function useStylis(): Stringifier {\n return useContext(StylisContext) || masterStylis;\n}\n\nexport default function StyleSheetManager(props: Props) {\n const [plugins, setPlugins] = useState(props.stylisPlugins);\n const contextStyleSheet = useStyleSheet();\n\n const styleSheet = useMemo(() => {\n   let sheet = contextStyleSheet;\n\n   if (props.sheet) {\n   // eslint-disable-next-line prefer-destructuring\n   sheet = props.sheet;\n   } else if (props.target) {\n   sheet = sheet.reconstructWithOptions({ target: props.target }, false);\n   }\n\n   if (props.disableCSSOMInjection) {\n   sheet = sheet.reconstructWithOptions({ useCSSOMInjection: false });\n   }\n\n   return sheet;\n }, [props.disableCSSOMInjection, props.sheet, props.target]);\n\n const stylis = useMemo(\n   () =>\n   createStylisInstance({\n   options: { prefix: !props.disableVendorPrefixes },\n   plugins,\n   }),\n   [props.disableVendorPrefixes, plugins]\n);\n\n useEffect(() => {\n   if (!shallowequal(plugins, props.stylisPlugins)) setPlugins(props.stylisPlugins);\n }, [props.stylisPlugins]);\n\n return (\n   <StyleSheetContext.Provider value={styleSheet}>\n   <StylisContext.Provider value={stylis}>\n   {process.env.NODE_ENV !== 'production'\n   ? React.Children.only(props.children)\n   : props.children}\n   </StylisContext.Provider>\n   </StyleSheetContext.Provider>\n);\n}\n","//\n\nmodule.exports = function shallowEqual(objA, objB,
 compare, compareContext) {\n var ret = compare ? compare.call(compareContext, objA, objB) : void 0;\n\n if (ret !== void 0) {\n   return !!ret;\n }\n\n if (objA === objB) {\n   return true;\n }\n\n if (typeof objA !== \"object\" || !objA || typeof objB !== \"object\" || !objB) {\n   return false;\n }\n\n var keysA = Object.keys(objA);\n var keysB = Object.keys(objB);\n\n if (keysA.length !== keysB.length) {\n   return false;\n }\n\n var bHasOwnProperty = Object.prototype.hasOwnProperty.bind(objB);\n\n // Test for A's keys different from B.\n for (var idx = 0; idx < keysA.length; idx++) {\n   var key = keysA[idx];\n\n   if (!bHasOwnProperty(key)) {\n   return false;\n   }\n\n   var valueA = objA[key];\n   var valueB = objB[key];\n\n   ret = compare ? compare.call(compareContext, valueA, valueB, key) : void 0;\n\n   if (ret === false || (ret === void 0 && valueA !== valueB)) {\n   return false;\n   }\n }\n\n return true;\n};\n","// @flow\nimport StyleSheet
 from '../sheet';\nimport { type Stringifier } from '../types';\nimport throwStyledError from '../utils/error';\nimport { masterStylis } from './StyleSheetManager';\n\nexport default class Keyframes {\n id: string;\n\n name: string;\n\n rules: string;\n\n constructor(name: string, rules: string) {\n   this.name = name;\n   this.id = `sc-keyframes-${name}`;\n   this.rules = rules;\n }\n\n inject = (styleSheet: StyleSheet, stylisInstance: Stringifier = masterStylis) => {\n   const resolvedName = this.name + stylisInstance.hash;\n\n   if (!styleSheet.hasNameForId(this.id, resolvedName)) {\n   styleSheet.insertRules(\n   this.id,\n   resolvedName,\n   stylisInstance(this.rules, resolvedName, '@keyframes')\n   );\n   }\n };\n\n toString = () => {\n   return throwStyledError(12, String(this.name));\n };\n\n getName(stylisInstance: Stringifier = masterStylis) {\n   return this.name + stylisInstance.hash;\n }\n}\n","// @flow\n\n/**\n * inlined version
 of\n * https://github.com/facebook/fbjs/blob/master/packages/fbjs/src/core/hyphenateStyleName.js\n */\n\nconst uppercaseCheck = /([A-Z])/;\nconst uppercasePattern = /([A-Z])/g;\nconst msPattern = /^ms-/;\nconst prefixAndLowerCase = (char: string): string => `-${char.toLowerCase()}`;\n\n/**\n * Hyphenates a camelcased CSS property name, for example:\n *\n *   > hyphenateStyleName('backgroundColor')\n *   < \"background-color\"\n *   > hyphenateStyleName('MozTransition')\n *   < \"-moz-transition\"\n *   > hyphenateStyleName('msTransition')\n *   < \"-ms-transition\"\n *\n * As Modernizr suggests

(http://modernizr.com/docs/#prefixed), an `ms` prefix\n * is converted to `-ms-`.\n *\n * @param {string} string\n * @return {string}\n */\nexport default function hyphenateStyleName(string: string): string {\n return uppercaseCheck.test(string)\n ? string\n .replace(uppercasePattern, prefixAndLowerCase)\n .replace(msPattern, '-ms-')\n : string;\n}\n","var unitlessKeys = {\n animationIterationCount: 1,\n borderImageOutset: 1,\n borderImageSlice: 1,\n borderImageWidth: 1,\n boxFlex: 1,\n boxFlexGroup: 1,\n boxOrdinalGroup: 1,\n columnCount: 1,\n columns: 1,\n flex: 1,\n flexGrow: 1,\n flexPositive: 1,\n flexShrink: 1,\n flexNegative: 1,\n flexOrder: 1,\n gridRow: 1,\n gridRowEnd: 1,\n gridRowSpan: 1,\n gridRowStart: 1,\n gridColumn: 1,\n gridColumnEnd: 1,\n gridColumnSpan: 1,\n gridColumnStart: 1,\n msGridRow: 1,\n msGridRowSpan: 1,\n msGridColumn: 1,\n msGridColumnSpan: 1,\n fontWeight: 1,\n lineHeight: 1,\n opacity: 1,\n order: 1,\n orphans: 1,\n tabSize: 1,\n widows: 1,\n zIndex: 1,\n zoom: 1,\n WebkitLineClamp: 1,\n // SVG-related properties\n fillOpacity: 1,\n floodOpacity: 1,\n stopOpacity: 1,\n strokeDasharray: 1,\n strokeDashoffset: 1,\n strokeMiterlimit: 1,\n strokeOpacity: 1,\n strokeWidth: 1\n};\n\nexport default unitlessKeys;\n","// @flow\nimport { isElement } from 'react-is';\nimport getComponentName from './getComponentName';\nimport isFunction from './isFunction';\nimport isStatelessFunction from './isStatelessFunction';\nimport isPlainObject from './isPlainObject';\nimport isStyledComponent from './isStyledComponent';\nimport Keyframes from '../models/Keyframes';\nimport hyphenate from './hyphenateStyleName';\nimport addUnitIfNeeded from './addUnitIfNeeded';\nimport { type Stringifier } from '../types';\n\n/**\n * It's falsish not falsy because 0 is allowed.\n */\nconst isFalsish = chunk => chunk === undefined || chunk === null || chunk === false || chunk === '';\n\nexport const objToCssArray = (obj: Object, prevKey?: string): Array<string | Function> => {\n const rules = [];\n\n for (const key in obj) {\n if (!obj.hasOwnProperty(key) || isFalsish(obj[key])) continue;\n\n if ((Array.isArray(obj[key]) && obj[key].isCss) || isFunction(obj[key])) {\n rules.push(`${hyphenate(key)}:`, obj[key], ';');\n } else if (isPlainObject(obj[key])) {\n rules.push(...objToCssArray(obj[key], key));\n } else {\n rules.push(`${hyphenate(key)}: ${addUnitIfNeeded(key, obj[key])};`);\n }\n }\n\n return prevKey ? [`${prevKey} {`, ...rules, '}'] : rules;\n};\n\nexport default function flatten(\n chunk: any,\n executionContext: ?Object,\n styleSheet: ?Object,\n stylisInstance: ?Stringifier\n): any {\n if (Array.isArray(chunk)) {\n const ruleSet = [];\n\n for (let i = 0, len = chunk.length, result; i < len; i += 1) {\n result = flatten(chunk[i], executionContext, styleSheet, stylisInstance);\n\n if (result === '') continue;\n else if (Array.isArray(result)) ruleSet.push(...result);\n else ruleSet.push(result);\n }\n\n return ruleSet;\n }\n\n if (isFalsish(chunk)) {\n return '';\n }\n\n /* Handle other components */\n if (isStyledComponent(chunk)) {\n return `.${chunk.styledComponentId}`;\n }\n\n /* Either execute or defer the function */\n if (isFunction(chunk)) {\n if (isStatelessFunction(chunk) && executionContext) {\n const result = chunk(executionContext);\n\n if (process.env.NODE_ENV !== 'production' && isElement(result)) {\n // eslint-disable-next-line no-console\n console.warn(\n `${getComponentName(\n chunk\n )} is not a styled component and cannot be referred to via component selector. See https://www.styled-components.com/docs/advanced#referring-to-other-components for more details.`\n);\n }\n\n return flatten(result, executionContext, styleSheet, stylisInstance);\n } else return chunk;\n }\n\n if (chunk instanceof Keyframes) {\n if (styleSheet) {\n chunk.inject(styleSheet, stylisInstance);\n return chunk.getName(stylisInstance);\n } else return chunk;\n }\n\n /* Handle objects */\n return isPlainObject(chunk) ? objToCssArray(chunk) : chunk.toString();\n}\n","// @flow\nexport default function isStatelessFunction(test: any): boolean {\n return (\n typeof test === 'function'\n && !(\n test.prototype\n && test.prototype.isReactComponent\n)\n);\n}\n","// @flow\nimport unitless from '@emotion/unitless';\n\n// Taken from https://github.com/facebook/react/blob/b87aabdfe1b7461e7331abb3601d9e6bb27544bc/packages/react-dom/src/shared/dangerousStyleValue.js\nexport default function addUnitIfNeeded(name: string, value: any): any {\n // https://github.com/amilajack/eslint-plugin-flowtype-errors/issues/133\n // $FlowFixMe\n if (value == null || typeof value === 'boolean' || value === '') {\n return '';\n }\n\n if (typeof value === 'number' && value !== 0 && !(name in unitless) && !name.startsWith('--')) {\n return `${value}px`; // Presumes implicit 'px' suffix for unitless numbers except for CSS variables\n }\n\n return String(value).trim();\n}\n","// @flow\nimport interleave from

'../utils/interleave';\nimport isPlainObject from '../utils/isPlainObject';\nimport { EMPTY_ARRAY } from '../utils/empties';\nimport isFunction from '../utils/isFunction';\nimport flatten from '../utils/flatten';\nimport type { Interpolation, RuleSet, Styles } from '../types';\n\n/**\n * Used when flattening object styles to determine if we should\n * expand an array of styles.\n */\nconst addTag = arg => {\n if (Array.isArray(arg)) {\n // eslint-disable-next-line no-param-reassign\n arg.isCss = true;\n }\n return arg;\n};\n\nexport default function css(styles: Styles, ...interpolations: Array<Interpolation>): RuleSet {\n if (isFunction(styles) || isPlainObject(styles)) {\n // $FlowFixMe\n return addTag(flatten(interleave(EMPTY_ARRAY, [styles, ...interpolations])));\n }\n\n if (interpolations.length === 0 && styles.length === 1 && typeof styles[0] === 'string') {\n // $FlowFixMe\n return styles;\n }\n\n // $FlowFixMe\n return addTag(flatten(interleave(styles, interpolations)));\n}\n","// @flow\nimport StyleSheet from '../sheet';\nimport type { RuleSet, Stringifier } from '../types';\nimport flatten from '../utils/flatten';\nimport isStaticRules from '../utils/isStaticRules';\n\nexport default class GlobalStyle {\n componentId: string;\n\n isStatic: boolean;\n\n rules: RuleSet;\n\n constructor(rules: RuleSet, componentId: string) {\n this.rules = rules;\n this.componentId = componentId;\n this.isStatic = isStaticRules(rules);\n\n // pre-register the first instance to ensure global styles\n // load before component ones\n StyleSheet.registerId(this.componentId + 1);\n }\n\n createStyles(\n instance: number,\n executionContext: Object,\n styleSheet: StyleSheet,\n stylis: Stringifier\n) {\n const flatCSS = flatten(this.rules, executionContext, styleSheet, stylis);\n const css = stylis(flatCSS.join(''), '');\n const id = this.componentId + instance;\n\n // NOTE: We use the id as a name as well, since these rules never change\n styleSheet.insertRules(id, id, css);\n }\n\n removeStyles(instance: number, styleSheet: StyleSheet) {\n styleSheet.clearRules(this.componentId + instance);\n }\n\n renderStyles(\n instance: number,\n executionContext: Object,\n styleSheet: StyleSheet,\n stylis: Stringifier\n) {\n if (instance > 2) StyleSheet.registerId(this.componentId + instance);\n\n // NOTE: Remove old styles, then inject the new ones\n this.removeStyles(instance, styleSheet);\n this.createStyles(instance, executionContext, styleSheet, stylis);\n }\n}\n","// @flow\nimport isFunction from './isFunction';\nimport isStyledComponent from './isStyledComponent';\nimport type { RuleSet } from '../types';\n\nexport default function isStaticRules(rules: RuleSet): boolean {\n for (let i = 0; i < rules.length; i += 1) {\n const rule = rules[i];\n\n if (isFunction(rule) && !isStyledComponent(rule)) {\n // functions are allowed to be static if they're just being\n // used to get the classname of a nested styled component\n return false;\n }\n }\n\n return true;\n}\n","// @flow\nimport React, { useContext, useMemo, type Element, type Context } from 'react';\nimport throwStyledError from '../utils/error';\nimport isFunction from '../utils/isFunction';\n\nexport type Theme = { [key: string]: mixed };\n\ntype ThemeArgument = Theme | ((outerTheme?: Theme) => Theme);\n\ntype Props = {\n children?: Element<any>,\n theme: ThemeArgument,\n};\n\nexport const ThemeContext: Context<Theme | void> = React.createContext();\n\nexport const ThemeConsumer = ThemeContext.Consumer;\n\nfunction mergeTheme(theme: ThemeArgument, outerTheme?: Theme): Theme {\n if (!theme) {\n return throwStyledError(14);\n }\n\n if (isFunction(theme)) {\n const mergedTheme = theme(outerTheme);\n\n if (\n process.env.NODE_ENV !== 'production' &&\n (mergedTheme === null || Array.isArray(mergedTheme) || typeof mergedTheme !== 'object')\n) {\n return throwStyledError(7);\n }\n\n return mergedTheme;\n }\n\n if (Array.isArray(theme) || typeof theme !== 'object') {\n return throwStyledError(8);\n }\n\n return outerTheme ? { ...outerTheme, ...theme } : theme;\n}\n\n/**\n * Provide a theme to an entire react component tree via context\n */\nexport default function ThemeProvider(props: Props) {\n const outerTheme = useContext(ThemeContext);\n const themeContext = useMemo(() => mergeTheme(props.theme, outerTheme), [\n props.theme,\n outerTheme,\n]);\n\n if (!props.children) {\n return null;\n }\n\n return <ThemeContext.Provider value={themeContext}>{props.children}</ThemeContext.Provider>;\n}\n","// @flow\n\nimport { useRef } from 'react';\n\nconst invalidHookCallRe = /invalid hook call/i;\nconst seen = new Set();\n\nexport const checkDynamicCreation = (displayName: string, componentId?: string) => {\n if (process.env.NODE_ENV !== 'production') {\n const parsedIdString = componentId ? ` with the id of \"${componentId}\"` : '';\n const message =\n `The component ${displayName}${parsedIdString} has been

```
created dynamically.\\n` +\n      \"You
 may see this warning because you've called styled inside another component.\\n\" +\n      'To resolve this only create new StyledComponents outside of any render method and function component.';\n\n    // If a hook is called outside of a component:\n    // React 17 and earlier throw an error\n    // React 18 and above use console.error\n\n    const originalConsoleError = console.error // eslint-disable-line no-console\n    try {\n      let didNotCallInvalidHook = true\n      /* $FlowIgnore[cannot-write] */\n      console.error = (consoleErrorMessage, ...consoleErrorArgs) => { // eslint-disable-line no-console\n        // The error here is expected, since we're expecting anything that uses `checkDynamicCreation` to\n        // be called outside of a React component.\n        if (invalidHookCallRe.test(consoleErrorMessage)) {\n          didNotCallInvalidHook = false\n          // This shouldn't happen, but resets `warningSeen` if we had this error happen intermittently\n          seen.delete(message);\n        } else {\n          originalConsoleError(consoleErrorMessage, ...consoleErrorArgs);\n        }\n      }\n      // We purposefully call `useRef` outside of a component and expect it to throw\n      // If it doesn't, then we're inside another component.\n      // eslint-disable-next-line react-hooks/rules-of-hooks\n      useRef();\n\n      if (didNotCallInvalidHook && !seen.has(message)) {\n        // eslint-disable-next-line no-console\n        console.warn(message);\n        seen.add(message);\n      }\n    } catch (error) {\n      // The error here is expected, since we're expecting anything that uses `checkDynamicCreation` to\n      // be called outside of a React component.\n      if (invalidHookCallRe.test(error.message)) {\n        // This shouldn't happen, but resets `warningSeen` if we had this error happen intermittently\n        seen.delete(message);\n      }\n    } finally {\n      /* $FlowIgnore[cannot-write] */\n      console.error = originalConsoleError;
 // eslint-disable-line no-console\n    }\n  }\n};\n","// @flow\nimport { EMPTY_OBJECT } from './empties';\n\ntype Props = {\n  theme?: any,\n};\n\nexport default (props: Props, providedTheme: any, defaultProps: any = EMPTY_OBJECT) => {\n  return (props.theme !== defaultProps.theme && props.theme) || providedTheme || defaultProps.theme;\n};\n","// @flow\n/* eslint-disable */\nimport generateAlphabeticName from './generateAlphabeticName';\nimport { hash } from './hash';\n\nexport default (str: string): string => {\n  return generateAlphabeticName(hash(str) >>> 0);\n};\n","// @flow\n/* eslint-disable no-underscore-dangle */\nimport React from 'react';\nimport { IS_BROWSER, SC_ATTR, SC_ATTR_VERSION, SC_VERSION } from '../constants';\nimport throwStyledError from '../utils/error';\nimport getNonce from '../utils/nonce';\nimport StyleSheet from '../sheet';\nimport StyleSheetManager from './StyleSheetManager';\n\ndeclare var __SERVER__: boolean;\n\nconst CLOSING_TAG_R = /^\\s*<\\/[a-z]/i;\n\nexport
 default class ServerStyleSheet {\n  isStreaming: boolean;\n\n  instance: StyleSheet;\n\n  sealed: boolean;\n\n  constructor() {\n    this.instance = new StyleSheet({ isServer: true });\n    this.sealed = false;\n  }\n\n  _emitSheetCSS = (): string => {\n    const css = this.instance.toString();\n    if (!css) return '';\n\n    const nonce = getNonce();\n    const attrs = [nonce && `nonce=\"${nonce}\"`, `${SC_ATTR}=\"true\"`, `${SC_ATTR_VERSION}=\"${SC_VERSION}\"`];\n    const htmlAttr = attrs.filter(Boolean).join(' ');\n\n    return `<style ${htmlAttr}>${css}</style>`;\n  };\n\n  collectStyles(children: any) {\n    if (this.sealed) {\n      return throwStyledError(2);\n    }\n\n    return <StyleSheetManager sheet={this.instance}>{children}</StyleSheetManager>;\n  }\n\n  getStyleTags = (): string => {\n    if (this.sealed) {\n      return throwStyledError(2);\n    }\n\n    return this._emitSheetCSS();\n  };\n\n  getStyleElement = () => {\n    if (this.sealed) {\n      return
 throwStyledError(2);\n    }\n\n    const props = {\n      [SC_ATTR]: '',\n      [SC_ATTR_VERSION]: SC_VERSION,\n      dangerouslySetInnerHTML: {\n        __html: this.instance.toString(),\n      },\n    };\n\n    const nonce = getNonce();\n    if (nonce) {\n      (props: any).nonce = nonce;\n    }\n\n    // v4 returned an array for this fn, so we'll do the same for v5 for backward compat\n    return [<style {...props} key=\"sc-0-0\" />];\n  };\n\n  // eslint-disable-next-line consistent-return\n  interleaveWithNodeStream(input: any) {\n    if (!__SERVER__ || IS_BROWSER) {\n      return throwStyledError(3);\n    } else if (this.sealed) {\n      return throwStyledError(2);\n    }\n\n    if (__SERVER__) {\n      this.seal();\n\n      // eslint-disable-next-line global-require\n      const { Readable, Transform } = require('stream');\n\n      const readableStream: Readable = input;\n      const { instance: sheet, _emitSheetCSS } = this;\n\n      const transformer = new Transform({\n
```

transform: function appendStyleChunks(chunk, /* encoding */ _, callback) {\n // Get the chunk and retrieve the sheet's CSS as an HTML chunk,\n // then reset its rules so we get only new ones for the next chunk\n const renderedHtml = chunk.toString();\n const html = _emitSheetCSS();\n\n sheet.clearTag();\n\n // prepend style html to chunk, unless the start of the chunk is a\n // closing tag in which case append right after that\n if (CLOSING_TAG_R.test(renderedHtml)) {\n const endOfClosingTag = renderedHtml.indexOf('>') + 1;\n const before = renderedHtml.slice(0, endOfClosingTag);\n const after = renderedHtml.slice(endOfClosingTag);\n\n this.push(before + html + after);\n } else {\n this.push(html + renderedHtml);\n }\n\n callback();\n },\n });\n\n readableStream.on('error', err => {\n // forward the error to the transform stream\n transformer.emit('error', err);\n });\n\n return readableStream.pipe(transformer);\n }\n }\n\n seal = () => {\n this.sealed = true;\n };\n}\n","'use strict';\n\nvar reactIs = require('react-is');\n\n/**\n * Copyright 2015, Yahoo! Inc.\n * Copyrights licensed under the New BSD License. See the accompanying LICENSE file for terms.\n */\nvar REACT_STATICS = {\n childContextTypes: true,\n contextType: true,\n contextTypes: true,\n defaultProps: true,\n displayName: true,\n getDefaultProps: true,\n getDerivedStateFromError: true,\n getDerivedStateFromProps: true,\n mixins: true,\n propTypes: true,\n type: true\n};\nvar KNOWN_STATICS = {\n name: true,\n length: true,\n prototype: true,\n caller: true,\n callee: true,\n arguments: true,\n arity: true\n};\nvar FORWARD_REF_STATICS = {\n '$$typeof': true,\n render: true,\n defaultProps: true,\n displayName: true,\n propTypes: true\n};\nvar MEMO_STATICS = {\n '$$typeof': true,\n compare: true,\n defaultProps: true,\n displayName: true,\n propTypes: true,\n type: true\n};\nvar TYPE_STATICS = {};\nTYPE_STATICS[reactIs.ForwardRef] = FORWARD_REF_STATICS;\nTYPE_STATICS[reactIs.Memo] = MEMO_STATICS;\n\nfunction getStatics(component) {\n // React v16.11 and below\n if (reactIs.isMemo(component)) {\n return MEMO_STATICS;\n } // React v16.12 and above\n\n\n return TYPE_STATICS[component['$$typeof']] || REACT_STATICS;\n}\n\nvar defineProperty = Object.defineProperty;\nvar getOwnPropertyNames = Object.getOwnPropertyNames;\nvar getOwnPropertySymbols = Object.getOwnPropertySymbols;\nvar getOwnPropertyDescriptor = Object.getOwnPropertyDescriptor;\nvar getPrototypeOf = Object.getPrototypeOf;\nvar objectPrototype = Object.prototype;\n\nfunction hoistNonReactStatics(targetComponent, sourceComponent, blacklist) {\n if (typeof sourceComponent !== 'string') {\n // don't hoist over string (html) components\n if (objectPrototype) {\n var inheritedComponent = getPrototypeOf(sourceComponent);\n\n if (inheritedComponent && inheritedComponent !== objectPrototype) {\n hoistNonReactStatics(targetComponent, inheritedComponent, blacklist);\n }\n }\n\n var keys = getOwnPropertyNames(sourceComponent);\n\n if (getOwnPropertySymbols) {\n keys = keys.concat(getOwnPropertySymbols(sourceComponent));\n }\n\n var targetStatics = getStatics(targetComponent);\n var sourceStatics = getStatics(sourceComponent);\n\n for (var i = 0; i < keys.length; ++i) {\n var key = keys[i];\n\n if (!KNOWN_STATICS[key] && !(blacklist && blacklist[key]) && !(sourceStatics && sourceStatics[key]) && !(targetStatics && targetStatics[key])) {\n var descriptor = getOwnPropertyDescriptor(sourceComponent, key);\n\n try {\n // Avoid failures from read-only properties\n defineProperty(targetComponent, key, descriptor);\n } catch (e) {}\n }\n }\n }\n\n return targetComponent;\n}\n\nmodule.exports = hoistNonReactStatics;\n","// @flow\n/* eslint-disable */\n\nimport StyleSheet from './sheet';\nimport { masterSheet } from './models/StyleSheetManager';\n\nexport const __PRIVATE__ = {\n StyleSheet,\n masterSheet,\n};\n","// @flow\n/* Import singletons */\nimport isStyledComponent from './utils/isStyledComponent';\nimport css from './constructors/css';\nimport createGlobalStyle from './constructors/createGlobalStyle';\nimport keyframes from './constructors/keyframes';\nimport ServerStyleSheet from './models/ServerStyleSheet';\nimport { SC_VERSION } from './constants';\n\nimport StyleSheetManager, {\n StyleSheetContext,\n StyleSheetConsumer,\n} from './models/StyleSheetManager';\n\n/* Import components */\nimport ThemeProvider, { ThemeContext, ThemeConsumer } from './models/ThemeProvider';\n\n/* Import Higher Order Components */\nimport withTheme from './hoc/withTheme';\n\n/* Import hooks */\nimport useTheme

```
from './hooks/useTheme';\n\ndeclare var __SERVER__: boolean;\n\n/*
 Warning if you've imported this file on React Native */\nif (\n  process.env.NODE_ENV !== 'production' &&\n typeof navigator !== 'undefined' &&\n  navigator.product === 'ReactNative'\n) {\n  // eslint-disable-next-line no-console\n  console.warn(\n    \"It looks like you've imported 'styled-components' on React Native.\\n\\n\" +\n \"Perhaps you're looking to import 'styled-components/native'?\\n\\n\" +\n      'Read more about this at https://www.styled-components.com/docs/basics#react-native'\n  );\n}\n\n/* Warning if there are several instances of styled-components */\nif (process.env.NODE_ENV !== 'production' && process.env.NODE_ENV !== 'test' && typeof window !== 'undefined') {\n  window['__styled-components-init__'] = window['__styled-components-init__'] || 0;\n\n  if (window['__styled-components-init__'] === 1) {\n    // eslint-disable-next-line no-console\n console.warn(\n      \"It looks like there are several instances of 'styled-components' initialized in this application. \" +\n        'This may cause dynamic styles to not render properly, errors during the rehydration process, ' +\n        'a missing theme prop, and makes your application bigger without good reason.\\n\\n' +\n        'See https://s-c.sh/2BAXzed for more info.'\n    );\n  }\n\n  window['__styled-components-init__'] += 1;\n}\n\n/* Export everything */\nexport * from './secretInternals';\nexport {\n  createGlobalStyle,\n  css,\n  isStyledComponent,\n  keyframes,\n  ServerStyleSheet,\n  StyleSheetConsumer,\n  StyleSheetContext,\n  StyleSheetManager,\n  ThemeConsumer,\n  ThemeContext,\n  ThemeProvider,\n  useTheme,\n  SC_VERSION as version,\n  withTheme,\n};\n","// @flow\nimport React, { useContext, useLayoutEffect, useRef } from 'react';\nimport { STATIC_EXECUTION_CONTEXT } from '../constants';\nimport GlobalStyle from '../models/GlobalStyle';\nimport { useStyleSheet, useStylis } from '../models/StyleSheetManager';\nimport { ThemeContext } from '../models/ThemeProvider';\nimport
 type { Interpolation } from '../types';\nimport { checkDynamicCreation } from '../utils/checkDynamicCreation';\nimport determineTheme from '../utils/determineTheme';\nimport generateComponentId from '../utils/generateComponentId';\nimport css from './css';\n\ndeclare var __SERVER__: boolean;\n\ntype GlobalStyleComponentPropsType = Object;\n\nexport default function createGlobalStyle(\n strings: Array<string>,\n  ...interpolations: Array<Interpolation>\n) {\n  const rules = css(strings, ...interpolations);\n const styledComponentId = `sc-global-${generateComponentId(JSON.stringify(rules))}`;\n  const globalStyle = new GlobalStyle(rules, styledComponentId);\n\n  if (process.env.NODE_ENV !== 'production') {\n checkDynamicCreation(styledComponentId);\n  }\n\n  function GlobalStyleComponent(props: GlobalStyleComponentPropsType) {\n    const styleSheet = useStyleSheet();\n    const stylis = useStylis();\n    const theme = useContext(ThemeContext);\n    const instanceRef = useRef(styleSheet.allocateGSInstance(styledComponentId));\n\n
    const instance = instanceRef.current;\n\n    if (process.env.NODE_ENV !== 'production' && React.Children.count(props.children)) {\n      // eslint-disable-next-line no-console\n      console.warn(\n        `The global style component ${styledComponentId} was given child JSX. createGlobalStyle does not render children.`\n
    );\n    }\n\n    if (\n      process.env.NODE_ENV !== 'production' &&\n      rules.some(rule => typeof rule === 'string' && rule.indexOf('@import') !== -1)\n    ) {\n      // eslint-disable-next-line no-console\n      console.warn(\n
    `Please do not use @import CSS syntax in createGlobalStyle at this time, as the CSSOM APIs we use in production do not handle it well. Instead, we recommend using a library such as react-helmet to inject a typical <link> meta tag to the stylesheet, or simply embedding it manually in your index.html <head> section for a simpler app.`\n      );\n    }\n\n    if (styleSheet.server)
 {\n      renderStyles(instance, props, styleSheet, theme, stylis);\n    }\n\n    if (!__SERVER__) {\n      // this conditional is fine because it is compiled away for the relevant builds during minification,\n      // resulting in a single unguarded hook call\n      // eslint-disable-next-line react-hooks/rules-of-hooks\n      useLayoutEffect(() => {\n        if (!styleSheet.server) {\n          renderStyles(instance, props, styleSheet, theme, stylis);\n          return () => globalStyle.removeStyles(instance, styleSheet);\n        }\n      }, [instance, props, styleSheet, theme, stylis]);\n    }\n\n    return null;\n  }\n\n  function renderStyles(instance, props, styleSheet, theme, stylis) {\n    if (globalStyle.isStatic) {\n      globalStyle.renderStyles(instance, STATIC_EXECUTION_CONTEXT, styleSheet, stylis);\n    } else {\n      const context = {\n        ...props,\n        theme: determineTheme(props, theme,
```

GlobalStyleComponent.defaultProps),\n };\n\n globalStyle.renderStyles(instance, context, styleSheet, stylis);\n }\n }\n\n // $FlowFixMe\n return React.memo(GlobalStyleComponent);\n}\n","// @flow\n\nimport css from './css';\nimport generateComponentId from '../utils/generateComponentId';\nimport Keyframes from '../models/Keyframes';\n\nimport type { Interpolation, Styles } from '../types';\n\nexport default function keyframes(\n strings: Styles,\n ...interpolations: Array<Interpolation>\n): Keyframes {\n /* Warning if you've used keyframes on React Native */\n if (\n process.env.NODE_ENV !== 'production' &&\n typeof navigator !== 'undefined' &&\n navigator.product === 'ReactNative'\n) {\n // eslint-disable-next-line no-console\n console.warn(\n '`keyframes` cannot be used on ReactNative, only on the web. To do animation in ReactNative please use Animated.'\n);\n }\n\n const rules = css(strings, ...interpolations).join('');\n const name = generateComponentId(rules);\n return new Keyframes(name, rules);\n}\n","// @flow\nimport { useContext } from 'react';\nimport { ThemeContext } from '../models/ThemeProvider';\n\nconst useTheme = () => useContext(ThemeContext);\n\nexport default useTheme;\n","// @flow\nimport React, { useContext, type AbstractComponent } from 'react';\nimport hoistStatics from 'hoist-non-react-statics';\nimport { ThemeContext } from '../models/ThemeProvider';\nimport determineTheme from '../utils/determineTheme';\nimport getComponentName from '../utils/getComponentName';\n\n// NOTE: this would be the correct signature:\n// export default <Config: { theme?: any }, Instance>(\n// Component: AbstractComponent<Config, Instance>\n//): AbstractComponent<$Diff<Config, { theme?: any }> & { theme?: any }, Instance>\n//\n// but the old build system tooling doesn't support the syntax\n\nexport default (Component: AbstractComponent<*, *>) => {\n // $FlowFixMe This should be React.forwardRef<Config, Instance>\n const WithTheme = React.forwardRef((props, ref) => {\n const theme = useContext(ThemeContext);\n // $FlowFixMe defaultProps isn't declared so it can be inferrable\n const { defaultProps } = Component;\n const themeProp = determineTheme(props, theme, defaultProps);\n\n if (process.env.NODE_ENV !== 'production' && themeProp === undefined) {\n // eslint-disable-next-line no-console\n console.warn(\n `[withTheme] You are not using a ThemeProvider nor passing a theme prop or a theme in defaultProps in component class \"${getComponentName(\n Component\n )}\"`\n);\n }\n\n return <Component {...props} theme={themeProp} ref={ref} />;\n });\n\n hoistStatics(WithTheme, Component);\n\n WithTheme.displayName = `WithTheme(${getComponentName(Component)})`;\n\n return WithTheme;\n};\n","function memoize(fn) {\n var cache = Object.create(null);\n return function (arg) {\n if (cache[arg] === undefined) cache[arg] = fn(arg);\n return cache[arg];\n };\n}\n\nexport default memoize;\n","import memoize from '@emotion/memoize';\n\nvar reactPropsRegex = /^((children|dangerouslySetInnerHTML|key|ref|autoFocus|defaultValue|defaultChecked|innerHTML|suppressContentEditableWarning|suppressHydrationWarning|valueLink|accept|acceptCharset|accessKey|action|allow|allowUserMedia|allowPaymentRequest|allowFullScreen|allowTransparency|alt|async|autoComplete|autoPlay|capture|cellPadding|cellSpacing|challenge|charSet|checked|cite|classID|className|cols|colSpan|content|contentEditable|contextMenu|controls|controlsList|coords|crossOrigin|data|dateTime|decoding|default|defer|dir|disabled|disablePictureInPicture|download|draggable|encType|form|formAction|formEncType|formMethod|formNoValidate|formTarget|frameBorder|headers|height|hidden|high|href|hrefLang|htmlFor|httpEquiv|id|inputMode|integrity|is|keyParams|keyType|kind|label|lang|list|loading|loop|low|marginHeight|marginWidth|max|maxLength|media|mediaGroup|method|min|minLength|multiple|muted|name|nonce|noValidate|open|optimum|pattern|placeholder|playsInline|poster|preload|profile|radioGroup|readOnly|referrerPolicy|rel|required|reversed|role|rows|rowSpan|sandbox|scope|scoped|scrolling|seamless|selected|shape|size|sizes|slot|span|spellCheck|src|srcDoc|srcLang|srcSet|start|step|style|summary|tabIndex|target|title|translate|type|useMap|value|width|wmode|wrap|about|datatype|inlist|prefix|property|resource|typeof|vocab|autoCapitalize|autoCorrect|autoSave|color|fallback|inert|itemProp|itemScope|itemType|itemID|itemRef|on|option|results|security|unselectable|accentHeight|accumulate|additive|alignmentBaseline|allowReorder|alphabetic|amplitude|arabicForm|ascent|attributeName|attributeType|autoReverse|azimuth|baseFrequency|baselineShift|baseProfile|bbox|begin|bias|by|calcMode|capHeight|clip|clipPathUnits|clipPath|clipRule|colorInterpolation|colorInterpolationFilters|colorProfile|colorRendering|contentScriptType|contentStyleType|cursor|cx|cy|d|decelerate|descent|diffuseConstant|direction|display|divisor|dominant

Baseline|dur|dx|dy|edgeMode|elevation|enableBackground|end|exponent|externalResourcesRequired|fill|fillOpacity|fillRule|filter|filterRes|filterUnits|floodColor|floodOpacity|focusable|fontFamily|fontSize|fontSizeAdjust|fontStretch|fontStyle|fontVariant|fontWeight|format|from|fr|fx|fy|g1|g2|glyphName|glyphOrientationHorizontal|glyphOrientationVertical|glyphRef|gradientTransform|gradientUnits|hanging|horizAdvX|horizOriginX|ideographic|imageRendering|in|in2|intercept|k|k1|k2|k3|k4|kernelMatrix|kernelUnitLength|kerning|keyPoints|keySplines|keyTimes|lengthAdjust|letterSpacing|lightingColor|limitingConeAngle|local|markerEnd|markerMid|markerStart|markerHeight|markerUnits|markerWidth|mask|maskContentUnits|maskUnits|mathematical|mode|numOctaves|offset|opacity|operator|order|orient|orientation|origin|overflow|overlinePosition|overlineThickness|panose1|paintOrder|pathLength|patternContentUnits|patternTransform|patternUnits|pointerEvents|points|pointsAtX|pointsAtY|pointsAtZ|preserveAlpha|preserveAspectRatio|primitiveUnits|r|radius|refX|refY|renderingIntent|repeatCount|repeatDur|requiredExtensions|requiredFeatures|restart|result|rotate|rx|ry|scale|seed|shapeRendering|slope|spacing|specularConstant|specularExponent|speed|spreadMethod|startOffset|stdDeviation|stemh|stemv|stitchTiles|stopColor|stopOpacity|strikethroughPosition|strikethroughThickness|string|stroke|strokeDasharray|strokeDashoffset|strokeLinecap|strokeLinejoin|strokeMiterlimit|strokeOpacity|strokeWidth|surfaceScale|systemLanguage|tableValues|targetX|targetY|textAnchor|textDecoration|textRendering|textLength|to|transform|u1|u2|underlinePosition|underlineThickness|unicode|unicodeBidi|unicodeRange|unitsPerEm|vAlphabetic|vHanging|vIdeographic|vMathematical|values|vectorEffect|version|vertAdvY|vertOriginX|vertOriginY|viewBox|viewTarget|visibility|widths|wordSpacing|writingMode|x|xHeight|x1|x2|xChannelSelector|xlinkActuate|xlinkArcrole|xlinkHref|xlinkRole|xlinkShow|xlinkTitle|xlinkType|xmlBase|xmlns|xmlnsXlink|xmlLang|xmlSpace|y|y1|y2|yChannelSelector|z|zoomAndPan|for|class|autofocus)|(([Dd][Aa][Tt][Aa]|[Aa][Rr][Ii][Aa]|x)-.*))$/;
// https://esbench.com/bench/5bfee68a4cd7e6009ef61d23\n\nvar isPropValid = /* #__PURE__ */memoize(function (prop) {\n return reactPropsRegex.test(prop) || prop.charCodeAt(0) === 111\n /* o */\n && prop.charCodeAt(1) === 110\n /* n */\n && prop.charCodeAt(2) < 91;\n}\n/* Z+1 */\n);\n\nexport default isPropValid;\n","//
@flow\n\n// Source: https://www.w3.org/TR/cssom-1/#serialize-an-identifier\n// Control characters and non-letter first symbols are not supported\nconst escapeRegex = /[!\"#$%&'()*+,./:;<=>?@[\\\\\\]^`{|}~-]+/g;\n\nconst dashesAtEnds = /(^-|-$)/g;\n\n/**\n * TODO: Explore using CSS.escape when it becomes more available\n * in evergreen browsers.\n */\nexport default function escape(str: string): string {\n return (\n   str\n   // Replace all possible CSS selectors\n   .replace(escapeRegex, '-')\n\n   // Remove extraneous hyphens at the start and end\n   .replace(dashesAtEnds, '')\n);\n}\n","//
@flow\nimport type { IStyledComponent } from '../types';\n\nexport default function isTag(target: $PropertyType<IStyledComponent, 'target'>): boolean %checks {\n return (\n   typeof target === 'string' &&\n   (process.env.NODE_ENV !== 'production'\n   ? target.charAt(0) === target.charAt(0).toLowerCase()\n   : true)\n);\n}\n","/* eslint-disable */\n/**\n mixin-deep; https://github.com/jonschlinkert/mixin-deep\n Inlined such that it will be consistently transpiled to an IE-compatible syntax.\n\n The MIT License (MIT)\n\n Copyright (c) 2014-present, Jon Schlinkert.\n\n Permission is hereby granted, free of charge, to any person obtaining a copy\n of this software and associated documentation files (the \"Software\"), to deal\n in the Software without restriction, including without limitation the rights\n to use, copy, modify, merge, publish, distribute, sublicense, and/or sell\n copies of the Software, and to permit persons to whom the Software is\n furnished
to do so, subject to the following conditions:\n\n The above copyright notice and this permission notice shall be included in\n all copies or substantial portions of the Software.\n\n THE SOFTWARE IS PROVIDED \"AS IS\", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR\n IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,\n FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE\n AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER\n LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,\n OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN\n THE SOFTWARE.\n*/\n\nconst isObject = val => {\n return (\n   typeof val === 'function' || (typeof val === 'object' && val !== null && !Array.isArray(val))\n);\n};\n\nconst isValidKey = key => {\n return key !== '__proto__' && key !== 'constructor' && key !== 'prototype';\n};\n\nfunction mixin(target, val, key) {\n const obj = target[key];\n

if (isObject(val) && isObject(obj)) {\n mixinDeep(obj, val);\n } else {\n target[key] = val;\n }\n}\n\nexport default function mixinDeep(target, ...rest) {\n for (const obj of rest) {\n if (isObject(obj)) {\n for (const key in obj) {\n if (isValidKey(key)) {\n mixin(target, obj[key], key);\n }\n }\n }\n }\n\n return target;\n}\n","// @flow\nimport validAttr from '@emotion/is-prop-valid';\nimport hoist from 'hoist-non-react-statics';\nimport React, { createElement, type Ref, useContext } from 'react';\nimport { SC_VERSION } from '../constants';\nimport type {\n Attrs,\n IStyledComponent,\n IStyledStatics,\n RuleSet,\n ShouldForwardProp,\n Target,\n} from '../types';\nimport { checkDynamicCreation } from '../utils/checkDynamicCreation';\nimport createWarnTooManyClasses from '../utils/createWarnTooManyClasses';\nimport determineTheme from '../utils/determineTheme';\nimport { EMPTY_ARRAY, EMPTY_OBJECT } from '../utils/empties';\nimport escape from '../utils/escape';\nimport generateComponentId from '../utils/generateComponentId';\nimport generateDisplayName from '../utils/generateDisplayName';\nimport getComponentName from '../utils/getComponentName';\nimport isFunction from '../utils/isFunction';\nimport isStyledComponent from '../utils/isStyledComponent';\nimport isTag from '../utils/isTag';\nimport joinStrings from '../utils/joinStrings';\nimport merge from '../utils/mixinDeep';\nimport ComponentStyle from './ComponentStyle';\nimport { useStyleSheet, useStylis } from './StyleSheetManager';\nimport { ThemeContext } from './ThemeProvider';\n\nconst identifiers = {};\n\n/* We depend on components having unique IDs */\nfunction generateId(displayName?: string, parentComponentId?: string) {\n const name = typeof displayName !== 'string' ? 'sc' : escape(displayName);\n // Ensure that no displayName can lead to duplicate componentIds\n identifiers[name] = (identifiers[name] || 0) + 1;\n\n const componentId\n = `${name}-${generateComponentId(\n // SC_VERSION gives us isolation between multiple runtimes on the page at once\n // this is improved further with use of the babel plugin \"namespace\" feature\n SC_VERSION + name + identifiers[name]\n )}`;\n\n return parentComponentId ? `${parentComponentId}-${componentId}` : componentId;\n}\n\nfunction useResolvedAttrs<Config>(theme: any = EMPTY_OBJECT, props: Config, attrs: Attrs) {\n // NOTE: can't memoize this\n // returns [context, resolvedAttrs]\n // where resolvedAttrs is only the things injected by the attrs themselves\n const context = { ...props, theme };\n const resolvedAttrs = {};\n\n attrs.forEach(attrDef => {\n let resolvedAttrDef = attrDef;\n let key;\n\n if (isFunction(resolvedAttrDef)) {\n resolvedAttrDef = resolvedAttrDef(context);\n }\n\n /* eslint-disable guard-for-in */\n for (key in resolvedAttrDef) {\n context[key] = resolvedAttrs[key] =\n key === 'className'\n ? joinStrings(resolvedAttrs[key],\n resolvedAttrDef[key])\n : resolvedAttrDef[key];\n }\n /* eslint-enable guard-for-in */\n });\n\n return [context, resolvedAttrs];\n}\n\nfunction useInjectedStyle<T>(\n componentStyle: ComponentStyle,\n isStatic: boolean,\n resolvedAttrs: T,\n warnTooManyClasses?: $Call<typeof createWarnTooManyClasses, string, string>\n) {\n const styleSheet = useStyleSheet();\n const stylis = useStylis();\n\n const className = isStatic\n ? componentStyle.generateAndInjectStyles(EMPTY_OBJECT, styleSheet, stylis)\n : componentStyle.generateAndInjectStyles(resolvedAttrs, styleSheet, stylis);\n\n if (process.env.NODE_ENV !== 'production' && !isStatic && warnTooManyClasses) {\n warnTooManyClasses(className);\n }\n\n return className;\n}\n\nfunction useStyledComponentImpl(\n forwardedComponent: IStyledComponent,\n props: Object,\n forwardedRef: Ref<any>,\n isStatic: boolean\n) {\n const {\n attrs: componentAttrs,\n componentStyle,\n\n defaultProps,\n foldedComponentIds,\n shouldForwardProp,\n styledComponentId,\n target,\n } = forwardedComponent;\n\n // NOTE: the non-hooks version only subscribes to this when !componentStyle.isStatic,\n // but that'd be against the rules-of-hooks. We could be naughty and do it anyway as it\n // should be an immutable value, but behave for now.\n const theme = determineTheme(props, useContext(ThemeContext), defaultProps);\n\n const [context, attrs] = useResolvedAttrs(theme || EMPTY_OBJECT, props, componentAttrs);\n\n const generatedClassName = useInjectedStyle(\n componentStyle,\n isStatic,\n context,\n process.env.NODE_ENV !== 'production' ? forwardedComponent.warnTooManyClasses : undefined\n);\n\n const refToForward = forwardedRef;\n\n const elementToBeCreated: Target = attrs.$as || props.$as || attrs.as || props.as || target;\n\n const isTargetTag =

isTag(elementToBeCreated);\n const computedProps = attrs !== props ? { ...props, ...attrs }
 : props;\n const propsForElement = {};\n\n // eslint-disable-next-line guard-for-in\n for (const key in computedProps) {\n   if (key[0] === '$' || key === 'as') continue;\n   else if (key === 'forwardedAs') {\n propsForElement.as = computedProps[key];\n   } else if (\n   shouldForwardProp\n   ? shouldForwardProp(key, validAttr, elementToBeCreated)\n   : isTargetTag\n   ? validAttr(key)\n   : true\n) {\n   // Don't pass through non HTML tags through to HTML elements\n   propsForElement[key] = computedProps[key];\n   }\n }\n\n if (props.style && attrs.style !== props.style) {\n   propsForElement.style = { ...props.style, ...attrs.style };\n }\n\n propsForElement.className = Array.prototype\n   .concat(\n foldedComponentIds,\n   styledComponentId,\n   generatedClassName !== styledComponentId ? generatedClassName : null,\n   props.className,\n   attrs.className\n   )\n   .filter(Boolean)\n   .join(' ');\n\n propsForElement.ref
 = refToForward;\n\n return createElement(elementToBeCreated, propsForElement);\n}\n\nexport default function createStyledComponent(\n target: $PropertyType<IStyledComponent, 'target'>,\n options: {\n   attrs?: Attrs,\n componentId: string,\n   displayName?: string,\n   parentComponentId?: string,\n   shouldForwardProp?: ShouldForwardProp,\n },\n rules: RuleSet\n) {\n const isTargetStyledComp = isStyledComponent(target);\n const isCompositeComponent = !isTag(target);\n\n const {\n   attrs = EMPTY_ARRAY,\n   componentId = generateId(options.displayName, options.parentComponentId),\n   displayName = generateDisplayName(target),\n } = options;\n\n const styledComponentId =\n   options.displayName && options.componentId\n   ? `${escape(options.displayName)}-${options.componentId}`\n   : options.componentId || componentId;\n\n // fold the underlying StyledComponent attrs up (implicit extend)\n const finalAttrs =\n   isTargetStyledComp &&
((target: any):
 IStyledComponent).attrs\n   ? Array.prototype.concat(((target: any): IStyledComponent).attrs, attrs).filter(Boolean)\n   : attrs;\n\n // eslint-disable-next-line prefer-destructuring\n let shouldForwardProp = options.shouldForwardProp;\n\n if (isTargetStyledComp && target.shouldForwardProp) {\n   if (options.shouldForwardProp) {\n   // compose nested shouldForwardProp calls\n   shouldForwardProp = (prop, filterFn, elementToBeCreated) =>\n   ((((target: any): IStyledComponent).shouldForwardProp: any): ShouldForwardProp)(\n   prop,\n   filterFn,\n   elementToBeCreated\n   ) &&\n ((options.shouldForwardProp: any): ShouldForwardProp)(prop, filterFn, elementToBeCreated);\n   } else {\n   // eslint-disable-next-line prefer-destructuring\n   shouldForwardProp = ((target: any): IStyledComponent).shouldForwardProp;\n   }\n }\n\n const componentStyle = new ComponentStyle(\n   rules,\n styledComponentId,\n   isTargetStyledComp
 ? ((target: Object).componentStyle: ComponentStyle) : undefined\n);\n\n // statically styled-components don't need to build an execution context object,\n // and shouldn't be increasing the number of class names\n const isStatic = componentStyle.isStatic && attrs.length === 0;\n\n /**\n   * forwardRef creates a new interim component, which we'll take advantage of\n   * instead of extending ParentComponent to create _another_ interim class\n   */\n let WrappedStyledComponent: IStyledComponent;\n\n const forwardRef = (props, ref) =>\n   // eslint-disable-next-line\n   useStyledComponentImpl(WrappedStyledComponent, props, ref, isStatic);\n\n forwardRef.displayName = displayName;\n\n WrappedStyledComponent = ((React.forwardRef(forwardRef): any): IStyledComponent);\n WrappedStyledComponent.attrs = finalAttrs;\n WrappedStyledComponent.componentStyle = componentStyle;\n WrappedStyledComponent.displayName = displayName;\n WrappedStyledComponent.shouldForwardProp = shouldForwardProp;\n\n
  // this static is used to preserve the cascade of static classes for component selector\n // purposes; this is especially important with usage of the css prop\n WrappedStyledComponent.foldedComponentIds = isTargetStyledComp\n ? Array.prototype.concat(\n   ((target: any): IStyledComponent).foldedComponentIds,\n   ((target: any): IStyledComponent).styledComponentId\n   )\n   : EMPTY_ARRAY;\n\n WrappedStyledComponent.styledComponentId = styledComponentId;\n\n // fold the underlying StyledComponent target up since we folded the styles\n WrappedStyledComponent.target = isTargetStyledComp\n   ? ((target: any): IStyledComponent).target\n   : target;\n\n WrappedStyledComponent.withComponent = function

withComponent(tag: Target) {\n const { componentId: previousComponentId, ...optionsToCopy } = options;\n\n const newComponentId =\n previousComponentId &&\n `${previousComponentId}-${isTag(tag) ? tag : escape(getComponentName(tag))}`;\n\n const newOptions = {\n ...optionsToCopy,\n attrs: finalAttrs,\n componentId: newComponentId,\n };\n\n return createStyledComponent(tag, newOptions, rules);\n };\n\n Object.defineProperty(WrappedStyledComponent, 'defaultProps', {\n get() {\n return this._foldedDefaultProps;\n },\n\n set(obj) {\n this._foldedDefaultProps = isTargetStyledComp\n ? merge({}, ((target: any): IStyledComponent).defaultProps, obj)\n : obj;\n },\n });\n\n if (process.env.NODE_ENV !== 'production') {\n checkDynamicCreation(displayName, styledComponentId);\n\n WrappedStyledComponent.warnTooManyClasses = createWarnTooManyClasses(\n displayName,\n styledComponentId\n);\n }\n\n // If the Object prototype is frozen, the \"toString\" property is non-writable. This means that any objects which inherit this property\n // cannot have the property changed using an assignment. If using strict mode, attempting that will cause an error. If not using strict\n // mode, attempting that will be silently ignored.\n // However, we can still explicitly shadow the prototype's \"toString\" property by defining a new \"toString\" property on this object.\n Object.defineProperty(WrappedStyledComponent, 'toString', { value: () => `.${WrappedStyledComponent.styledComponentId}` });\n\n if (isCompositeComponent) {\n hoist<\n IStyledStatics,\n $PropertyType<IStyledComponent, 'target'>,\n { [key: $Keys<IStyledStatics>]: true }\n >(WrappedStyledComponent, ((target: any): $PropertyType<IStyledComponent, 'target'>), {\n // all SC-specific things should not be hoisted\n attrs: true,\n componentStyle: true,\n displayName: true,\n foldedComponentIds: true,\n shouldForwardProp: true,\n styledComponentId: true,\n target: true,\n withComponent: true,\n });\n }\n\n return WrappedStyledComponent;\n}\n","// @flow\nimport type { IStyledComponent } from '../types';\nimport getComponentName from './getComponentName';\nimport isTag from './isTag';\n\nexport default function generateDisplayName(\n target: $PropertyType<IStyledComponent, 'target'>\n): string {\n return isTag(target) ? `styled.${target}` : `Styled(${getComponentName(target)})`;\n}\n","/**\n * Convenience function for joining strings to form className chains\n */\nexport default function joinStrings(a: ?String, b: ?String): ?String {\n return a && b ? `${a} ${b}` : a || b;\n}\n","// @flow\n\nexport const LIMIT = 200;\n\nexport default (displayName: string, componentId: string) => {\n let generatedClasses = {};\n let warningSeen = false;\n\n return (className: string) => {\n if (!warningSeen) {\n generatedClasses[className] = true;\n if (Object.keys(generatedClasses).length >= LIMIT) {\n // Unable to find latestRule in test environment.\n /* eslint-disable no-console, prefer-template */\n const parsedIdString = componentId ? ` with the id of \"${componentId}\"` : '';\n\n console.warn(\n `Over ${LIMIT} classes were generated for component ${displayName}${parsedIdString}.\\n` +\n 'Consider using the attrs method, together with a style object for frequently changed styles.\\n' +\n 'Example:\\n' +\n ' const Component = styled.div.attrs(props => ({\\n' +\n ' style: {\\n' +\n ' background: props.background,\\n' +\n ' },\\n' +\n ' }))`width: 100%;`\\n\\n' +\n ' <Component />'\n);\n warningSeen = true;\n generatedClasses = {};\n }\n }\n };\n};\n","// @flow\nimport constructWithOptions from './constructWithOptions';\nimport StyledComponent from '../models/StyledComponent';\nimport domElements from '../utils/domElements';\n\nimport type { Target } from '../types';\n\nconst styled = (tag: Target) => constructWithOptions(StyledComponent, tag);\n\n// Shorthands for all valid HTML Elements\ndomElements.forEach(domElement => {\n styled[domElement] = styled(domElement);\n});\n\nexport default styled;\n","// @flow\nimport { isValidElementType } from 'react-is';\nimport css from './css';\nimport throwStyledError from '../utils/error';\nimport { EMPTY_OBJECT } from '../utils/empties';\n\nimport type { Target } from '../types';\n\nexport default function constructWithOptions(\n componentConstructor: Function,\n tag: Target,\n options: Object = EMPTY_OBJECT\n) {\n if (!isValidElementType(tag)) {\n return throwStyledError(1, String(tag));\n }\n\n /* This is callable directly as a template function */\n // $FlowFixMe: Not typed to avoid destructuring arguments\n const templateFunction = (...args) => componentConstructor(tag, options, css(...args));\n\n /* If config methods are

called, wrap up a new template function and merge options */\n templateFunction.withConfig = config =>\n constructWithOptions(componentConstructor, tag, { ...options, ...config });\n\n /* Modify/inject new props at runtime */\n templateFunction.attrs = attrs =>\n   constructWithOptions(componentConstructor, tag, {\n ...options,\n   attrs: Array.prototype.concat(options.attrs, attrs).filter(Boolean),\n   });\n\n return templateFunction;\n}\n","// @flow\nimport * as secondary from './base';\n\n/* Import singleton constructors */\nimport styled from './constructors/styled';\n\n/**\n * eliminates the need to do styled.default since the other APIs\n * are directly assigned as properties to the main function\n * */\n// eslint-disable-next-line guard-for-in\nfor (const key in secondary) {\n styled[key] = secondary[key];\n}\n\nexport default styled;\n","// @flow\n// Thanks to ReactDOMFactories for this handy list!\n\nexport default [\n 'a',\n 'abbr',\n 'address',\n 'area',\n 'article',\n 'aside',\n 'audio',\n 'b',\n 'base',\n 'bdi',\n 'bdo',\n 'big',\n 'blockquote',\n 'body',\n 'br',\n 'button',\n 'canvas',\n 'caption',\n 'cite',\n 'code',\n 'col',\n 'colgroup',\n 'data',\n 'datalist',\n 'dd',\n 'del',\n 'details',\n 'dfn',\n 'dialog',\n 'div',\n 'dl',\n 'dt',\n 'em',\n 'embed',\n 'fieldset',\n 'figcaption',\n 'figure',\n 'footer',\n 'form',\n 'h1',\n 'h2',\n 'h3',\n 'h4',\n 'h5',\n 'h6',\n 'head',\n 'header',\n 'hgroup',\n 'hr',\n 'html',\n 'i',\n 'iframe',\n 'img',\n 'input',\n 'ins',\n 'kbd',\n 'keygen',\n 'label',\n 'legend',\n 'li',\n 'link',\n 'main',\n 'map',\n 'mark',\n 'marquee',\n 'menu',\n 'menuitem',\n 'meta',\n 'meter',\n 'nav',\n 'noscript',\n 'object',\n 'ol',\n 'optgroup',\n 'option',\n 'output',\n 'p',\n 'param',\n 'picture',\n 'pre',\n 'progress',\n 'q',\n 'rp',\n 'rt',\n 'ruby',\n 's',\n 'samp',\n 'script',\n 'section',\n 'select',\n 'small',\n 'source',\n 'span',\n 'strong',\n 'style',\n 'sub',\n 'summary',\n 'sup',\n 'table',\n 'tbody',\n 'td',\n 'textarea',\n 'tfoot',\n 'th',\n 'thead',\n 'time',\n 'title',\n 'tr',\n 'track',\n 'u',\n 'ul',\n 'var',\n 'video',\n 'wbr',\n\n // SVG\n 'circle',\n 'clipPath',\n 'defs',\n 'ellipse',\n 'foreignObject',\n 'g',\n 'image',\n 'line',\n 'linearGradient',\n 'marker',\n 'mask',\n 'path',\n 'pattern',\n 'polygon',\n 'polyline',\n 'radialGradient',\n 'rect',\n 'stop',\n 'svg',\n 'text',\n 'textPath',\n 'tspan',\n];\n"],"names":["isStyledComponent","target","styledComponentId","strings","interpolations","result","i","len","length","push","x","toString","Object","prototype","call","typeOf","EMPTY_ARRAY","freeze","EMPTY_OBJECT","isFunction","test","getComponentName","displayName","name","SC_ATTR","process","env","REACT_APP_SC_ATTR","IS_BROWSER","window","DISABLE_SPEEDY","Boolean","SC_DISABLE_SPEEDY","REACT_APP_SC_DISABLE_SPEEDY","STATIC_EXECUTION_CONTEXT","ERRORS","format","a","b","c","arguments","forEach","d","replace","throwStyledComponentsError","code","Error","trim","DefaultGroupedTag","tag","groupSizes","Uint32Array","indexOfGroup","group","index","this","insertRules","rules","oldBuffer","oldSize","newSize","throwStyledError","set","ruleIndex","l","insertRule","clearGroup","startIndex","endIndex","deleteRule","getGroup","css","getRule","groupIDRegister","Map","reverseRegister","nextFreeGroup","getGroupForId","id","has","get","getIdForGroup","setGroupForId","SELECTOR","MARKER_RE","RegExp","rehydrateNamesFromContent","sheet","content","names","split","registerName","rehydrateSheetFromTag","style","parts","textContent","part","marker","match","parseInt","getTag","getNonce","__webpack_nonce__","makeStyleTag","head","document","parent","createElement","prevStyle","childNodes","child","nodeType","hasAttribute","findLastStyleTag","nextSibling","undefined","setAttribute","__VERSION__","nonce","insertBefore","CSSOMTag","element","appendChild","createTextNode","styleSheets","ownerNode","getSheet","rule","_error","cssRules","cssText","TextTag","nodes","node","refNode","removeChild","VirtualTag","_target","splice","SHOULD_REHYDRATE","defaultOptions","isServer","useCSSOMInjection","StyleSheet","options","globalStyles","gs","server","querySelectorAll","getAttribute","parentNode","rehydrateSheet","registerId","reconstructWithOptions","withNames","allocateGSInstance","hasNameForId","add","groupNames","Set","clearNames","clear","clearRules","clearTag","size","selector","outputSheet","AD_REPLACER_R","getAlphabeticChar","String","fromCharCode","generateAlphabeticName","Math","abs","phash","h","charCodeAt","hash","SEED","ComponentStyle","componentId","baseStyle","staticRulesId","isStatic","baseHash","generateAndInjectStyles","executionContext","styleSheet","stylis","cssStatic","flatten","join","generateName","cssStaticFormatted","dynamicHash","partRule","partChunk","partString","Array","isArray","cssFormatted","stylis_min","W","X","e","ia","m","Z","v","n","F","indexOf","P","substring","w","L","ja","ka","aa","G","ba","la","ma","R","na","ea","oa","H","q","g","A","S","B","U","prefix","D","z","M","k","y","C","K","u","r","I","t","J","f","p","N","charAt","ca","O","da","fa","Y","E","ha","Q","use","T","COMMENT_REGEX","COMPLEX_SELECTOR_PREFIX","createSty

lisInstance","_componentId","_selector","_selectorRegexp","_consecutiveSelfRefRegExp","plugins","Stylis","parsingRules","parseRulesPlugin","toSheet","block","context","selectors","parents","line","column","ns","depth","at","delimiter","insertRulePlugin","selfReferenceReplacer","offset","string","stringifyRules","flatCSS","cssStr","_","lastIndexOf","parsedRules","reduce","acc","plugin","StyleSheetContext","React","createContext","StyleSheetConsumer","Consumer","StylisContext","masterSheet","masterStylis","useStyleSheet","useContext","useStylis","StyleSheetManager","props","useState","stylisPlugins","setPlugins","contextStyleSheet","useMemo","disableCSSOMInjection","disableVendorPrefixes","useEffect","objA","objB","compare","compareContext","ret","keysA","keys","keysB","bHasOwnProperty","hasOwnProperty","bind","idx","key","valueA","valueB","shallowequal","Provider","value","Children","only","children","Keyframes","inject","stylisInstance","resolvedName","_this","getName","uppercaseCheck","uppercasePattern","msPattern","prefixAndLowerCase","char","toLowerCase","hyphenateStyleName","unitlessKeys","animationIterationCount","borderImageOutset","borderImageSlice","borderImageWidth","boxFlex","boxFlexGroup","boxOrdinalGroup","columnCount","columns","flex","flexGrow","flexPositive","flexShrink","flexNegative","flexOrder","gridRow","gridRowEnd","gridRowSpan","gridRowStart","gridColumn","gridColumnEnd","gridColumnSpan","gridColumnStart","msGridRow","msGridRowSpan","msGridColumn","msGridColumnSpan","fontWeight","lineHeight","opacity","order","orphans","tabSize","widows","zIndex","zoom","WebkitLineClamp","fillOpacity","floodOpacity","stopOpacity","strokeDasharray","strokeDashoffset","strokeMiterlimit","strokeOpacity","strokeWidth","isFalsish","chunk","ruleSet","isReactComponent","isElement","console","warn","isPlainObject","objToCssArray","obj","prevKey","isCss","hyphenate","unitless","startsWith","addTag","arg","styles","interleave","GlobalStyle","isStaticRules","createStyles","instance","removeStyles","renderStyles","ThemeContext","ThemeConsumer","invalidHookCallRe","seen","checkDynamicCreation","message","originalConsoleError","error","didNotCallInvalidHook","consoleErrorMessage","consoleErrorArgs","useRef","providedTheme","defaultProps","theme","str","ServerStyleSheet","_emitSheetCSS","SC_ATTR_VERSION","filter","getStyleTags","sealed","getStyleElement","dangerouslySetInnerHTML","__html","seal","collectStyles","interleaveWithNodeStream","input","REACT_STATICS","childContextTypes","contextType","contextTypes","getDefaultProps","getDerivedStateFromError","getDerivedStateFromProps","mixins","propTypes","type","KNOWN_STATICS","caller","callee","arity","MEMO_STATICS","$$typeof","TYPE_STATICS","getStatics","component","reactIs","isMemo","ForwardRef","render","Memo","defineProperty","getOwnPropertyNames","getOwnPropertySymbols","getOwnPropertyDescriptor","getPrototypeOf","objectPrototype","hoistNonReactStatics","targetComponent","sourceComponent","blacklist","inheritedComponent","concat","targetStatics","sourceStatics","descriptor","__PRIVATE__","navigator","product","generateComponentId","JSON","stringify","globalStyle","GlobalStyleComponent","current","count","some","useLayoutEffect","determineTheme","memo","outerTheme","themeContext","mergedTheme","mergeTheme","Component","WithTheme","forwardRef","ref","themeProp","hoistStatics","memoize","fn","cache","create","reactPropsRegex","isPropValid","prop","escapeRegex","dashesAtEnds","escape","isTag","isObject","val","isValidKey","mixin","mixinDeep","rest","identifiers","createStyledComponent","isTargetStyledComp","isCompositeComponent","attrs","parentComponentId","generateId","generateDisplayName","finalAttrs","shouldForwardProp","filterFn","elementToBeCreated","WrappedStyledComponent","componentStyle","forwardedComponent","forwardedRef","componentAttrs","foldedComponentIds","resolvedAttrs","attrDef","resolvedAttrDef","useResolvedAttrs","generatedClassName","warnTooManyClasses","className","useInjectedStyle","refToForward","$as","as","isTargetTag","computedProps","propsForElement","validAttr","withComponent","previousComponentId","optionsToCopy","newComponentId","_foldedDefaultProps","merge","generatedClasses","warningSeen","parsedIdString","createWarnTooManyClasses","hoist","styled","constructWithOptions","componentConstructor","isValidElementType","templateFunction","withConfig","config","StyledComponent","domElement","secondary"],"mappings":"sUACe,SAASA,EAAkBC,UACjCA,EAAIC,QAAQ,KAAM,IAAIC,cCCE,SAASC,EAAcC,EAAKC,GAC1C,IAAIC,EAAQ,GAAGC,OAAOF,GAAQ,IAAIG,MAAM,KAAKC,QAAO,SAAUC,EAAKC,GAAQ,OAAOD,EAAIC,GAAOA,EAAMD,IAAM,MAAQ,GAAGE,OAAOC,KAAKC,MAAMD,KAAKE,UAAUT,IAAQ,SAAUU,GAAK,OAAOA,EAAEC,QAAQ,SAAU,SAAUC,KAAK,KAAO,IAAIb

ChD,cAOWI,EAA+B,oBAAXC,QAA0B,gBAAiBA,OAE/DC,EAAiBC,QACC,kBAAtBC,kBACHA,kBACmB,oBAAZP,cAAkD,IAAhBA,QAAQC,WACE,IAA5CD,QAAQC,IAAIO,6BACyB,KAA5CR,QAAQC,IAAIO,4BACkC,UAA5CR,QAAQC,IAAIO,6BAEVR,QAAQC,IAAIO,iCAC2B,IAAlCR,QAAQC,IAAIM,mBAAuE,KAAlCP,QAAQC,IAAIM,mBAClC,UAAlCP,QAAQC,IAAIM,mBAEVP,QAAQC,IAAIM,mBAEVP,QAAQC,IAAIM,oBAMTE,EAA2B,GCjClCC,ECHS,GAAK,0DAA4D,kQAAoQ,wHAA0H,wMAA0M,oKAAsK,8OAAgP,uHAA2H,gEAAkE,mCAAqC,oUAAsU,2NAA6N,wWAA0W,4LAA8L,kDAAoD,8ZAAga,0QAA4Q,0IDQ/jG,SAASC,YACHC,0CACAC,0CACAC,0CACA

mI,MAAQX,EAAQZ,gBAChBrG,OAAS,6BAGhByD,WAAA,SAAWX,EAAeyE,MACpBzE,GAASC,KAAK/C,QAAU8C,GAAS,EAAG,KAChC+E,EAAO5B,SAASkB,eAAeI,GAC/BO,EAAU/E,KAAK6E,MAAM9E,eACtBmE,QAAQF,aAAac,EAAMC,GAAW,WACtC9H,UACE,SAEA,KAIX6D,WAAA,SAAWf,QACJmE,QAAQc,YAAYhF,KAAK6E,MAAM9E,SAC/B9C,YAGPgE,QAAA,SAAQlB,UACFmB,QAAQC,KAAKpB,KAAK,CAAEqB,KAAMrB,KAAKqB,KAAMC,MAAOtB,KAAKsB,QAGrDC,QAAA,SAAQC,GACN,IAAK,IAAIC,EAAI,EAAGA,EAAIzB,KAAKmB,QAAQO,OAAQD,IAAK,CAC5C,IAAIE,EAAS3B,KAAKmB,QAAQM,GAC1B,GAAIE,EAAOL,KAAKM,KAAKJ,GAAO,OAAOG,EAAOJ,QAI9CM,QAAA,SAAQC,GACN,IAAK,IAAIL,EAAI,EAAGA,EAAIzB,KAAKmB,QAAQO,OAAQD,IAAK,CAC5C,IAAIE,EAAS3B,KAAKmB,QAAQM,GAC1B,GAAIE,EAAOL,KAAKM,KAAKE,GAAO,OAAOH,EAAOJ,QAI9CQ,QAAA,SAAQC,GACN,IAAK,IAAIP,EAAI,EAAGA,EAAIzB,KAAKmB,QAAQO,OAAQD,IAAK,CAC5C,IAAIE,EAAS3B,KAAKmB,QAAQM,GAC1B,GAAIE,EAAOL,KAAKM,KAAKI,GAAO,OAAOL,EAAOJ,QAI9CU,QAAA,SAAQD,GACN,IAAK,IAAIP,EAAI,EAAGA,EAAIzB,KAAKmB,QAAQO,OAAQD,IAAK,CAC5C,IAAIE,EAAS3B,KAAKmB,QAAQM,GAC1B,GAAIE,EAAOL,KAAKM,KAAKI,GAAO,OAAOL,EAAOJ,QAI9CW,QAAA,SAAQF,GACN,IAAK,IAAIP,EAAI,EAAGA,EAAIzB,KAAKmB,QAAQO,OAAQD,IAAK,CAC5C,IAAIE,EAAS3B,KAAKmB,QAAQM,GAC1B,GAAIE,EAAOL,KAAKM,KAAKI,GAAO,OAAOL,EAAOJ,QAI9CY,QAAA,SAAQH,GACN,IAAK,IAAIP,EAAI,EAAGA,EAAIzB,KAAKmB,QAAQO,OAAQD,IAAK,CAC5C,IAAIE,EAAS3B,KAAKmB,QAAQM,GAC1B,GAAIE,EAAOL,KAAKM,KAAKI,GAAO,OAAOL,EAAOJ,QAI9Ca,QAAA,SAAQJ,GACN,IAAK,IAAIP,EAAI,EAAGA,EAAIzB,KAAKmB,QAAQO,OAAQD,IAAK,CAC5C,IAAIE,EAAS3B,KAAKmB,QAAQM,GAC1B,GAAIE,EAAOL,KAAKM,KAAKI,GAAO,OAAOL,EAAOJ,QAI9CU,QAAA,SAAQD,GACN,IAAK,IAAIP,EAAI,EAAGA,EAAIzB,KAAKmB,QAAQO,OAAQD,IAAK,CAC5C,IAAIE,EAAS3B,KAAKmB,QAAQM,GAC1B,GAAIE,EAAOL,KAAKM,KAAKI,GAAO,OAAOL,EAAOJ,QAI9CW,QAAA,SAAQF,GACN,IAAK,IAAIP,EAAI,EAAGA,EAAIzB,KAAKmB,QAAQO,OAAQD,IAAK,CAC5C,IAAIE,EAAS3B,KAAKmB,QAAQM,GAC1B,GAAIE,EAAOL,KAAKM,KAAKI,GAAO,OAAOL,EAAOJ,QAI9CY,QAAA,SAAQH,GACN,IAAK,IAAIP,EAAI,EAAGA,EAAIzB,KAAKmB,QAAQO,OAAQD,IAAK,CAC5C,IAAIE,E

MK,EACnEF,EAAcpB,EAAMoB,EAAaG,EAAa/L,GAC9CiE,GAAO8H,MAIP9H,EAAK,KACDhD,EAAOyK,EAAaE,IAAgB,OAErCP,EAAW/B,aAAawB,EAAa7J,GAAO,KACzCiL,EAAeZ,EAAOrH,MAAShD,OAAQ4F,EAAWiE,GACxDO,EAAWnI,YAAY4H,EAAa7J,EAAMiL,GAG5C/C,hF,KAAKc,WAIRkE,EAAYC,GAAtDtE,EAAAA,EAAAA,GAAAA,EAAAA,EAAAA,E

AAMvL,EAEpG,MAEF,KAAK,IACL,KAAK,IACH,GAAI,KAAOA,EAAE2I,WAAW,IAAM,MAAQ3I,EAAE2I,WAAW,GAAI,MAEzD,KAAK,IACL,KAAK,IACH,IAAI,IAAO6C,EAAGzM,KAAKsB,GAAI,OAAO,OAASJ,EAAIII,EAAE2K,UAAU3K,EAAEyK,QAAQ,KAAO,IAAInC,WAAW,GAAKoC,EAAE1K,EAAEC,QAAQ,UAAW,kBAAmBJ,EAAGqK,EAAG7B,GAAGpI,QAAQ,kBAAmB,YAAcN,EAAEM,QAAQL,EAAG,WAAaA,GAAKD,EAAEM,QAAQL,EAAG,QAAUA,EAAEK,QAAQ,QAAS,KAAOn,CxQ,MAEF,KAAK,IACH,GAAI,IAAEAI,WAAW,GAAK,OAAS3I,EAAI,EAAI,WAAaA,GAAK,MAAQuK,EAAG,MAAQuK,EAAI7B,EAAE2I,WAAW,GAAK,MAAQ,MAAQ1I,EAAI,MAAQ,MAAQ,MAAQ

GAEpB,KAAK,IACL,KAAK,IACL,KAAK,GACHa,EAAIS,EAAI,IAAMT,EAAI,IAClB,MAEF,KAAK,IAEHA,GADAS,EAAIA,EAAE5M,QAAQmN,EAAI,UACV,IAAMhB,EAAI,IAClBA,EAAI,IAAMxB,GAAAK,IAAMA,GAAKC,EAAE,IAAMuB,EAAAG,GAAAK,YAAAcA,EAAI,IAAMA,EAAI,IAAMA,,EAAC5E,MAAEF,,QACEA,,EAAIS,EAAAIT,,EAAAG,,MAAAQ/D,IAAAWyE,GAAAKV,,EAAAVA,,EAAASACnCA,EAAAI,GACX,MAEF,QACEA,EAAIID,EAAAEtM,EAAAGoK,EAAAEpK,EAAAGgN,EAAAGH,GAAAIN,,EAAAG/D,I1,EAAAI,GAAAnC6K,GAAAK4B,EACLA,M,EAAAID,,EAAAID,Id,EAAAI,,EACApBmB,EAAAI,GACJlB,EAAAIzB,,EAAAE5B,,aAAAahH,,GACAnB,,MAAEF,,KAAAK,IACCL,,KAAAK,GAAEH,,GAAAI,,GAAAKqL,,GADTE,,GAAAK,,EAAAIJ,,EAAAII,,EAAAE5M,,QAAAQ8M,,EAAAG,,IAAAMF,,GAAAGxM,,QACEpBvC,,QAAAS,,OAAAQ,,IAAAM0O,,IAAAMd,,EAAAImB,,EAAAEvE,,WAAAW,,GAAAI,,KAAAOoD,,GAAAK,,GAAAAKA,,GAAAK,,IAAAMA,,KAAAOiB,,GAAAKE,,EAAAIA,,EAAAE5E5M,,QAAAAA,,OAAAQ/L,,IAAAMA,,MAAAnC,,QAAAS,,IAAAWP,,EAAAjM

BACLtC,EAAI,qBACJkC,EAAK,kBACL3B,EAAK,eACLN,EAAK,eACLI,EAAK,8BACLH,EAAK,mCACLL,E
AAK,sBACLoB,EAAI,EACJD,EAAI,EACJqB,EAAI,EACJ1C,EAAI,EACJsC,EAAI,GACJrB,EAAI,GACJD,EAA
I,EACJP,EAAI,KACJgC,EAAI,EAKR,OAHAvB,EAAE2B,IApEF,SAASC,EAAE1N,GACT,OAAQA,GACN,UA
AK,EACL,KAAK,KACH4L,EAAIC,EAAE/N,OAAS,EACf,MAEF,QACE,GAAI,mBAAsBkC,EAAG6L,EAAED,
KAAO5L,OAAO,GAAI,iBAAoBA,EAAG,IAAK,IAAIH,EAAI,EAAGqK,EAAIlK,EAAElC,OAAQ+B,EAAIqK,I
AAKrK,EAC7G6N,EAAE1N,EAAEH,SACCwN,EAAU,IAAJrN,EAAGjB,OAAO0N,GAwDT5B,EAAE1K,IAAM2
K,OACR,IAAW/B,GAAK+B,EAAE/B,GACX8B,EC5lBT,IAAM6B,EAAgB,gBAChBC,EAA0B,CAAC,IAAK,IA
AK,IAAK,KAOjC,SAASC,SAyBlBC,EACAC,,EACAC,,EACAC,,eAzB6BzP,QAFjC8H,QAAAA,aAAU9H,QACV
0P,QAAAA,aAAU5P,IAEJ4K,EAAS,IAAIiF,EAAO7H,GAMtB8H,EAAe,GAWbC,EC dO,SAAS9M,MAEhBC,EAAIC,EAAE
AQC,MACXA,MAEAhN,EAAcgN,OACCd,MAAOrE,YAIN,SACLsE,EACA1L,,EACA2L,,EACAC,,EACAC,,EACA
C,EACA9Q,EACA+Q,EACAC,,EACAC,,UAEQP,QAED,KAEW,IAAVM,GAAyC,KAA1BhM,EAAQwF,WAAW,
GAAW,OAAO/G,EAAcuB,OAAa,cAGhF,KACQ,IAAP+L,L,EAAU,OAAO/L,EA/BT,mBAkCTC,SACK+L,QAED,S
ACA,WACItN,EAAWkN,EAAU,GAAK3L,EAAU,kBAEpCA,GAAkB,IAAPiM,EAAzCV,QAAyCiC,SAEzC,EACJjM
M,EAAQE,MA3CIgM,UA2CUjP,QAAQuO,KD/BXW,EAAiB,mBAAsB5J,GAAcxC,+I,EAAarQ,KAAKsH,MAQd6J,E
AAwB,SAAC1L,EAAO2L,EAAQC,UAG9B,IAAIC,IAA8E,IAA/DvB,EAAOwB,QAAQ,EAAOrB,EAAOsB,QAAQ,
UAEhEsR,EAAO5L,MAAMyK,GAAKTzK,MAAMsK,YA4BtBuB,eAAkBN,EAAOO,QAAQ,EAAOpB,EAAOqB,QAAQtD,YAAAAA
,IAAAA,EAAc,SACrD4G,EAAUzN,EAAI5B,GAAGqP,EAAIrP,GAAGsP,EAAItP,GAAGuP,EAAIvP,GAAGwP,EAAIxP,GAAGyP,
QAAc2H,OAAcA,SAAK7ExB,EAAepF,EACCfqF,EAAAYpG,EACCZqG,EAAAkB,IAAIrL,YAAYoL,QAAgB,KAClDE,
EAA4B,IAAItL,aAAaoL,cAAEtC7E,EAAO8C,IAAWrE,EAAW,GAAKA,EAAU4H,UAdrDrG,EAAOuE,cAAQS,G
APwB,SAACM,EAASgB,EAAGf,GAClC,IAAZD,EAAU,GAAK,EAAGC,EAAGD,EAAU,GAAK,EAAGC,EAAGD,EAAU,GAAK,EAAGC,EAAGD,EAAU,
Aa,IAE7EU,EAAU,GAAK,EAAGC,EAAGD,EAAU,GAAK,EAAGC,EAAGD,EAAU,GAAK,EAAGC,EAAGD,EAAU,GAAK,EAAGC,EAAGD,EAAU,
AgB,KACZkB,EAAActB,EAAOuB,QAAQ,EAAOpB,EAAOqB,QAAQ,EAAOlB,EAAOmB,QAAQ,EAAOlB,EAAOmB,QAAQ,EAAOlB,EAAOmB,QAAQ,
QAAO,SAACC,EAAKC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,
GqGXZ,WACH,GAEGoR,EE3FF,IAAMS,EAAgB,SAACC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAGC,EAAG

EACbC,QAAS,EACTC,KAAM,EACNC,SAAU,EACVC,aAAc,EACdC,WAAY,EACZC,aAAc,EACdC,UAAW,EACXC,QAAS,EACTC,WAAY,EACZC,YAAa,EACbC,aAAc,EACdC,WAAY,EACZC,cAAe,EACfC,eAAgB,EAChBC,gBAAiB,EACjBC,UAAW,EACXC,cAAe,EACfC,aAAc,EACdC,iBAAkB,EAClBC,WAAY,EACZC,WAAY,EACZC,QAAS,EACTC,MAAO,EACPC,QAAS,EACTC,QAAS,EACTC,OAAQ,EACRC,OAAQ,EACRC,KAAM,EACNC,gBAAiB,EAEjBC,YAAa,EACbC,aAAc,EACdC,YAAa,EACbC,gBAAiB,EACjBC,iBAAkB,EAClBC,iBAAkB,EAClBC,cAAe,EACfC,YAAa,GC/BTC,BTC,EAEjBC,SAAU,EACVC,aAAc,EACdC,aAAc,EACdC,UAAW,EACX

Cd7Z,aAAa,EACbib,iBAAiB,EACjBC,0BAA0B,EAC1BC,0BAA0B,EAC1BC,QAAQ,EACRC,WAAW,EACXC,MAAM,GAEJC,GAAgB,CAClBtb,MAAM,EACNf,QAAQ,EACRK,WAAW,EACXic,QAAQ,EACRC,QAAQ,EACRva,WAAW,EACXwa,OAAO,GASLC,GAAe,CACjBC,UAAY,EACZnJ,SAAS,EACToH,cAAc,EACd7Z,aAAa,EACbqb,WAAW,EACXC,XC,GAEJO,GAAe,GAInB,SASC,GAAWC,GAAWlJ,GAAWlJ,GAAWlJ

AWtM,IACbuM,GAAM/gB,EAAQqZ,EAAI7E,GAAMA,UAMzBxU,EC5BT,IAAMkhB,GAAc,GA4IL,SAASC,GACtBnhB,EACA+I,EAOAvF,OAEM4d,EAAqBrhB,EAAkBC,GACvCqhB,GAAwBV,GAAM3gB,KAMhC+I,EAHFuY,MAAAA,aAAQvgB,MAGNgI,EAFFoC,YAAAA,aAzJJ,SAAsBkgB,OAClCjgB,EAA8B,iBAAhBD,BD,EAA2B,KAAOA,EAAaC,gBAAkB,KAAOA,EAAgBkgB,KAAOlgB,EAAgBkgB,KAAO,KAAOlgB,EAAgBmgB,KAAOngB,EAAgBmgB,KAAO,KAAOngB,EAAgBogB,KAAOpgB,EAAgBogB,KAAO,KAAOpgB,EAAgBqgB,KAAOrgB,EAAgBqgB,KAAO,KAAOrgB,EAAgBsgB,KAAOtgB,EAAgBsgB,KAAO,KAAOtgB,EAAgBugB,KAAOvgB,EAAgBugB,KAAO,KAAOvgB,EAAgBwgB,KAAOxgB,EAAgBwgB,KAAO,KAAOxgB,EAAgBygB,KAAOzgB,EAAgBygB,KAAO,KAAOzgB,EAAgB0gB,KAAO1gB,EAAgB0gB,KAAO,KAAO1gB,EAAgB2gB,KAAO3gB,EAAgB2gB,KAAO,KAAO3gB,EAAgB4gB,KAAO5gB,EAAgB4gB,KAAO,KAAO5gB,EAAgB6gB,KAAO7gB,EAAgB6gB,KAAO,KAAO7gB,EAAgB8gB,KAAO9gB,EAAgB8gB,KAAO,KAAO9gB,EAAgB+gB,KAAO/gB,EAAgB+gB,KAAO,KAAO/gB,EAAgBghB,KAAOhhB,EAAgBghB,KAAO,KAAOhhB,EAAgBihB,KAAOjhB,EAAgBihB,KAAO,KAAOjhB,EAAgBkhB,KAAOlhB,EAAgBkhB,KAAO,KAAOlhB,EAAgBmhB,KAAOnhB,EAAgBmhB,KAAO,KAAOnhB,EAAgBohB,KAAOphB,EAAgBohB,KAAO,KAAOphB,EAAgBqhB,KAAOrhB,EAAgBqhB,KAAO,KAAOrhB,EAAgBshB,KAAOthB,EAAgBshB,KAAO,KAAOthB,EAAgBuhB,KAAOvhB,EAAgBuhB,KAAO,KAAOvhB,EAAgBwhB,KAAOxhB,EAAgBwhB,KAAO,KAAOxhB,EAAgByhB,KAAOzhB,EAAgByhB,KAAO,KAAOzhB,EAAgB0hB,KAAO1hB,EAAgB0hB,KAAO,KAAO1hB,EAAgB2hB,KAAO3hB,EAAgB2hB,KAAO,KAAO3hB,EAAgB4hB,KAAO5hB,EAAgB4hB,KAAO,KAAO5hB,EAAgB6hB,KAAO7hB,EAAgB6hB,KAAO,KAAO7hB,EAAgB8hB,KAAO9hB,EAAgB8hB,KAAO,KAAO9hB,EAAgB+hB,KAAO/hB,EAAgB+hB,KAAO,KAAO/hB,EAAgBgiB,KAAOhiB,EAAgBgiB,KAAO,KAAOhiB,EAAgBiiB,KAAOjiB,EAAgBiiB,KAAO,KAAOjiB,EAAgBkiB,KAAOliB,EAAgBkiB,KAAO,KAAOliB,EAAgBmiB,KAAOniB,EAAgBmiB,KAAO,KAAOniB,EAAgBoiB,KAAOpiB,EAAgBoiB,KAAO,KAAOpiB,EAAgBqiB,KAAOriB,EAAgBqiB,KAAO,KAAOriB,EAAgBsiB,KAAOtiB,EAAgBsiB,KAAO,KAAOtiB,EAAgBuiB,KAAOviB,EAAgBuiB,KAAO,KAAOviB,EAAgBwiB,KAAOxiB,EAAgBwiB,KAAO,KAAOxiB,EAAgByiB,KAAOziB,EAAgByiB,KAAO,KAAOziB,EAAgB0iB,KAAO1iB,EAAgB0iB,KAAO,KAAO1iB,EAAgB2iB,KAAO3iB,EAAgB2iB,KAAO,KAAO3iB,EAAgB4iB,KAAO5iB,EAAgB4iB,KAAO,KAAO5iB,EAAgB6iB,KAAO7iB,EAAgB6iB,KAAO,KAAO7iB,EAAgB8iB,KAAO9iB,EAAgB8iB,KAAO,KAAO9iB,EAAgB+iB,KAAO/iB,EAAgB+iB,KAAO,KAAO/iB,EAAgBgjB,KAAOhjB,EAAgBgjB,KAAO,KAAOhjB,EAAgBijB,KAAOjjB,EAAgBijB,KAAO,KAAOjjB,EAAgBkjB,KAAOljB,EAAgBkjB,KAAO,KAAOljB,EAAgBmjB,KAAOnjB,EAAgBmjB,KAAO,KAAOnjB,EAAgBojB,KAAOpjB,EAAgBojB,KAAO,KAAOpjB,EAAgBqjB,KAAOrjB,EAAgBqjB,KAAO,KAAOrjB,EAAgBsjB,KAAOtjB,EAAgBsjB,KAAO,KAAOtjB,EAAgBujB,KAAOvjB,EAAgBujB,KAAO,KAAOvjB,EAAgBwjB,KAAOxjB,EAAgBwjB,KAAO,KAAOxjB,EAAgByjB,KAAOzjB,EAAgByjB,KAAO,KAAOzjB,EAAgB0jB,KAAO1jB,EAAgB0jB,KAAO,KAAO1jB,EAAgB2jB,KAAO3jB,EAAgB2jB,KAAO,KAAO3jB,EAAgB4jB,KAAO5jB,EAAgB4jB,KAAO,KAAO5jB,EAAgB6jB,KAAO7jB,EAAgB6jB,KAAO,KAAO7jB,EAAgB8jB,KAAO9jB,EAAgB8jB,KAAO,KAAO9jB,EAAgB+jB,KAAO/jB,EAAgB+jB,KAAO,KAAO/jB,EAAgBgkB,KAAOhkB,EAAgBgkB,KAAO,KAAOhkB,EAAgBikB,KAAOjkB,EAAgBikB,KAAO,KAAOjkB,EAAgBkkB,KAAOlkB,EAAgBkkB,KAAO,KAAOlkB,EAAgBmkB,KAAOnkB,EAAgBmkB,KAAO,KAAOnkB,EAAgBokB,KAAOpkB,EAAgBokB,KAAO,KAAOpkB,EAAgBqkB,KAAOrkB,EAAgBqkB,KAAO,KAAOrkB,EAAgBskB,KAAOtkB,EAAgBskB,KAAO,KAAOtkB,EAAgBukB,KAAOvkB,EAAgBukB,KAAO,KAAOvkB,EAAgBwkB,KAAOxkB,EAAgBwkB,KAAO,KAAOxkB,EAAgBykB,KAAOzkB,EAAgBykB,KAAO,KAAOzkB,EAAgB0kB,KAAO1kB,EAAgB0kB,KAAO,KAAO1kB,EAAgB2kB,KAAO3kB,EAAgB2kB,KAAO,KAAO3kB,EAAgB4kB,KAAO5kB,EAAgB4kB,KAAO,KAAO5kB,EAAgB6kB,KAAO7kB,EAAgB6kB,KAAO,KAAO7kB,EAAgB8kB,KAAO9kB,EAAgB8kB,KAAO,KAAO9kB,EAAgB+kB,KAAO/kB,EAAgB+kB,KAAO,KAAO/kB,EAAgBglB,KAAOhlB,EAAgBglB,KAAO,KAAOhlB,EAAgBilB,KAAOjlB,EAAgBilB,KAAO,KAAOjlB,EAAgBklB,KAAOllB,EAAgBklB,KAAO,KAAOllB,EAAgBmlB,KAAOnlB,EAAgBmlB,KAAO,KAAOnlB,EAAgBolB,KAAOplB,EAAgBolB,KAAO,KAAOplB,EAAgBqlB,KAAOrlB,EAAgBqlB,KAAO,KAAOrlB,EAAgBslB,KAAOtlB,EAAgBslB,KAAO,KAAOtlB,EAAgBulB,KAAOvlB,EAAgBulB,KAAO,KAAOvlB,EAAgBwlB,KAAOxlB,EAAgBwlB,KAAO,KAAOxlB,EAAgBylB,KAAOzlB,EAAgBylB,KAAO,KAAOzlB,EAAgB0lB,KAAO1lB,EAAgB0lB,KAAO,KAAO1lB,EAAgB2lB,KAAO3lB,EAAgB2lB,KAAO,KAAO3lB,EAAgB4lB,KAAO5lB,EAAgB4lB,KAAO,KAAO5lB,EAAgB6lB,KAAO7lB,EAAgB6lB,KAAO,KAAO7lB,EAAgB8lB,KAAO9lB,EAAgB8lB,KAAO,KAAO9lB,EAAgB+lB,KAAO/lB,EAAgB+lB,KAAO,KAAO/lB,EAAgBgmB,KAAOhmB,EAAgBgmB,KAAO,KAAOhmB,EAAgBimB,KAAOjmB,EAAgBimB,KAAO,KAAOjmB,EAAgBkmB,KAAOlmB,EAAgBkmB,KAAO,KAAOlmB,EAAgBmmB,KAAOnmB,EAAgBmmB,KAAO,KAAOnmB,EAAgBomB,KAAOpmB,EAAgBomB,KAAO,KAAOpmB,EAAgBqmB,KAAOrmB,EAAgBqmB,KAAO,KAAOrmB,EAAgBsmB,KAAOtmB,EAAgBsmB,KAAO,KAAOtmB,EAAgBumB,KAAOvmB,EAAgBumB,KAAO,KAAOvmB,EAAgBwmB,KAAOxmB,EAAgBwmB,KAAO,KAAOxmB,EAAgBymB,KAAOzmB,EAAgBymB,KAAO,KAAOzmB,EAAgB0mB,KAAO1mB,EAAgB0mB,KAAO,KAAO1mB,EAAgB2mB,KAAO3mB,EAAgB2mB,KAAO,KAAO3mB,EAAgB4mB,KAAO5mB,EAAgB4mB,KAAO,KAAO5mB,EAAgB6mB,KAAO7mB,EAAgB6mB,KAAO,KAAO7mB,EAAgB8mB,KAAO9mB,EAAgB8mB,KAAO,KAAO9mB,EAAgB+mB,KAAO/mB,EAAgB+mB,KAAO,KAAO/mB,EAAgBgnB,KAAOhnB,EAAgBgnB,KAAO,KAAOhnB,EAAgBinB,KAAOjnB,EAAgBinB,KAAO,KAAOjnB,EAAgBknB,KAAOlnB,EAAgBknB,KAAO,KAAOlnB,EAAgBmnB,KAAOnnB,EAAgBmnB,KAAO,KAAOnnB,EAAgBonB,KAAOpnB,EAAgBonB,KAAO,KAAOpnB,EAAgBqnB,KAAOrnB,EAAgBqnB,KAAO,KAAOrnB,EAAgBsnB,KAAOtnB,EAAgBsnB,KAAO,KAAOtnB,EAAgBunB,KAAOvnB,EAAgBunB,KAAO,KAAOvnB,EAAgBwnB,KAAOxnB,EAAgBwnB,KAAO,KAAOxnB,EAAgBynB,KAAOznB,EAAgBynB,KAAO,KAAOznB,EAAgB0nB,KAAO1nB,EAAgB0nB,KAAO,KAAO1nB,EAAgB2nB,KAAO3nB,EAAgB2nB,KAAO,KAAO3nB,EAAgB4nB,KAAO5nB,EAAgB4nB,KAAO,KAAO5nB,EAAgB6nB,KAAO7nB,EAAgB6nB,KAAO,KAAO7nB,EAAgB8nB,KAAO9nB,EAAgB8nB,KAAO,KAAO9nB,EAAgB+nB,KAAO/nB,EAAgB+nB,KAAO,KAAO/nB,EAAgBgoB,KAAOhoB,EAAgBgoB,KAAO,KAAOhoB,EAAgBioB,KAAOjoB,EAAgBioB,KAAO,KAAOjoB,EAAgBkoB,KAAOloB,EAAgBkoB,KAAO,KAAOloB,EAAgBmoB,KAAOnoB,EAAgBmoB,KAAO,KAAOnoB,EAAgBooB,KAAOpoB,EAAgBooB,KAAO,KAAOpoB,EAAgBqoB,KAAOroB,EAAgBqoB,KAAO,KAAOroB,EAAgBsoB,KAAOtoB,EAAgBsoB,KAAO,KAAOtoB,EAAgBuoB,KAAOvoB,EAAgBuoB,KAAO,KAAOvoB,EAAgBwoB,KAAOxoB,EAAgBwoB,KAAO,KAAOxoB,EAAgByoB,KAAOzoB,EAAgByoB,KAAO,KAAOzoB,EAAgB0oB,KAAO1oB,EAAgB0oB,KAAO,KAAO1oB,EAAgB2oB,KAAO3oB,EAAgB2oB,KAAO,KAAO3oB,EAAgB4oB,KAAO5oB,EAAgB4oB,KAAO,KAAO5oB,EAAgB6oB,KAAO7oB,EAAgB6oB,KAAO,KAAO7oB,EAAgB8oB,KAAO9oB,EAAgB8oB,KAAO,KAAO9oB,EAAgB+oB,KAAO/oB,EAAgB+oB,KAAO,KAAO/oB,EAAgBgpB,KAAOhpB,EAAgBgpB,KAAO,KAAOhpB,EAAgBipB,KAAOjpB,EAAgBipB,KAAO,KAAOjpB,EAAgBkpB,KAAOlpB,EAAgBkpB,KAAO,KAAOlpB,EAAgBmpB,KAAOnpB,EAAgBmpB,KAAO,KAAOnpB,EAAgBopB,KAAOppB,EAAgBopB,KAAO,KAAOppB,EAAgBqpB,KAAOrpB,EAAgBqpB,KAAO,KAAOrpB,EAAgBspB,KAAOtpB,EAAgBspB,KAAO,KAAOtpB,EAAgBupB,KAAOvpB,EAAgBupB,KAAO,KAAOvpB,EAAgBwpB,KAAOxpB,EAAgBwpB,KAAO,KAAOxpB,EAAgBypB,KAAOzpB,EAAgBypB,KAAO,KAAOzpB,EAAgB0pB,KAAO1pB,EAAgB0pB,KAAO,KAAO1pB,EAAgB2pB,KAAO3pB,EAAgB2pB,KAAO,KAAO3pB,EAAgB4pB,KAAO5pB,EAAgB4pB,KAAO,KAAO5pB,EAAgB6pB,KAAO7pB,EAAgB6pB,KAAO,KAAO7pB,EAAgB8pB,KAAO9pB,EAAgB8pB,KAAO,KAAO9pB,EAAgB+pB,KAAO/pB,EAAgB+pB,KAAO,KAAO/pB,EAAgBgqB,KAAOhqB,EAAgBgqB,KAAO,KAAOhqB,EAAgBiqB,KAAOjqB,EAAgBiqB,KAAO,KAAOjqB,EAAgBkqB,KAAOlqB,EAAgBkqB,KAAO,KAAOlqB,EAAgBmqB,KAAOnqB,EAAgBmqB,KAAO,KAAOnqB,EAAgBoqB,KAAOpqB,EAAgBoqB,KAAO,KAAOpqB,EAAgBqqB,KAAOrqB,EAAgBqqB,KAAO,KAAOrqB,EAAgBsqB,KAAOtqB,EAAgBsqB,KAAO,KAAOtqB,EAAgBuqB,KAAOvqB,EAAgBuqB,KAAO,KAAOvqB,EAAgBwqB,KAAOxqB,EAAgBwqB,KAAO,KAAOxqB,EAAgByqB,KAAOzqB,EAAgByqB,KAAO,KAAOzqB,EAAgB0qB,KAAO1qB,EAAgB0qB,KAAO,KAAO1qB,EAAgB2qB,KAAO3qB,EAAgB2qB,KAAO,KAAO3qB,EAAgB4qB,KAAO5qB,EAAgB4qB,KAAO,KAAO5qB,EAAgB6qB,KAAO7qB,EAAgB6qB,KAAO,KAAO7qB,EAAgB8qB,KAAO9qB,EAAgB8qB,KAAO,KAAO9qB,EAAgB+qB,KAAO/qB,EAAgB+qB,KAAO,KAAO/qB,EAAgBgrB,KAAOhrB,EAAgBgrB,KAAO,KAAOhrB,EAAgBirB,KAAOjrB,EAAgBirB,KAAO,KAAOjrB,EAAgBkrB,KAAOlrB,EAAgBkrB,KAAO,KAAOlrB,EAAgBmrB,KAAOnrB,EAAgBmrB,KAAO,KAAOnrB,EAAgBorB,KAAOprB,EAAgBorB,KAAO,KAAOprB,EAAgBqrB,KAAOrrB,EAAgBqrB,KAAO,KAAOrrB,EAAgBsrB,KAAOtrB,EAAgBsrB,KAAO,KAAOtrB,EAAgBurB,KAAOvrB,EAAgBurB,KAAO,KAAOvrB,EAAgBwrB,KAAOxrB,EAAgBwrB,KAAO,KAAOxrB,EAAgByrB,KAAOzrB,EAAgByrB,KAAO,KAAOzrB,EAAgB0rB,KAAO1rB,EAAgB0rB,KAAO,KAAO1rB,EAAgB2rB,KAAO3rB,EAAgB2rB,KAAO,KAAO3rB,EAAgB4rB,KAAO5rB,EAAgB4rB,KAAO,KAAO5rB,EAAgB6rB,KAAO7rB,EAAgB6rB,KAAO,KAAO7rB,EAAgB8rB,KAAO9rB,EAAgB8rB,KAAO,KAAO9rB,EAAgB+rB,KAAO/rB,EAAgB+rB,KAAO,KAAO/rB,EAAgBgsB,KAAOhsB,EAAgBgsB,KAAO,KAAOhsB,EAAgBisB,KAAOjsB,EAAgBisB,KAAO,KAAOjsB,EAAgBksB,KAAOlsB,EAAgBksB,KAAO,KAAOlsB,EAAgBmsB,KAAOnsB,EAAgBmsB,KAAO,KAAOnsB,EAAgBosB,KAAOpsB,EAAgBosB,KAAO,KAAOpsB,EAAgBqsB,KAAOrsB,EAAgBqsB,KAAO,KAAOrsB,EAAgBssB,KAAOtsB,EAAgBssB,KAAO,KAAOtsB,EAAgBusB,KAAOvsB,EAAgBusB,KAAO,KAAOvsB,EAAgBwsB,KAAOxsB,EAAgBwsB,KAAO,KAAOxsB,EAAgBysB,KAAOzsB,EAAgBysB,KAAO,KAAOzsB,EAAgB0sB,KAAO1sB,EAAgB0sB,KAAO,KAAO1sB,EAAgB2sB,KAAO3sB,EAAgB2sB,KAAO,KAAO3sB,EAAgB4sB,KAAO5sB,EAAgB4sB,KAAO,KAAO5sB,EAAgB6sB,KAAO7sB,EAAgB6sB,KAAO,KAAO7sB,EAAgB8sB,KAAO9sB,EAAgB8sB,KAAO,KAAO9sB,EAAgB+sB,KAAO/sB,EAAgB+sB,KAAO,KAAO/sB,EAAgBgtB,KAAOhtB,EAAgBgtB,KAAO,KAAOhtB,EAAgBitB,KAAOjtB,EAAgBitB,KAAO,KAAOjtB,EAAgBktB,KAAOltB,EAAgBktB,KAAO,KAAOltB,EAAgBmtB,KAAOntB,EAAgBmtB,KAAO,KAAOntB,EAAgBotB,KAAOptB,EAAgBotB,KAAO,KAAOptB,EAAgBqtB,KAAOrtB,EAAgBqtB,KAAO,KAAOrtB,EAAgBstB,KAAOttB,EAAgBstB,KAAO,KAAOttB,EAAgButB,KAAOvtB,EAAgButB,KAAO,KAAOvtB,EAAgBwtB,KAAOxtB,EAAgBwtB,KAAO,KAAOxtB,EAAgBytB,KAAOztB,EAAgBytB,KAAO,KAAOztB,EAAgB0tB,KAAO1tB,EAAgB0tB,KAAO,KAAO1tB,EAAgB2tB,KAAO3tB,EAAgB2tB,KAAO,KAAO3tB,EAAgB4tB,KAAO5tB,EAAgB4tB,KAAO,KAAO5tB,EAAgB6tB,KAAO7tB,EAAgB6tB,KAAO,KAAO7tB,EAAgB8tB,KAAO9tB,EAAgB8tB,KAAO,KAAO9tB,EAAgB+tB,KAAO/tB,EAAgB+tB,KAAO,KAAO/tB,EAAgBguB,KAAOhuB,EAAgBguB,KAAO,KAAOhuB,EAAgBiuB,KAAOjuB,EAAgBiuB,KAAO,KAAOjuB,EAAgBkuB,KAAOluB,EAAgBkuB,KAAO,KAAOluB,EAAgBmuB,KAAOnuB,EAAgBmuB,KAAO,KAAOnuB,EAAgBouB,KAAOpuB,EAAgBouB,KAAO,KAAOpuB,EAAgBquB,KAAOruB,EAAgBquB,KAAO,KAAOruB,EAAgBsuB,KAAOtuB,EAAgBsuB,KAAO,KAAOtuB,EAAgBuuB,KAAOvuB,EAAgBuuB,KAAO,KAAOvuB,EAAgBwuB,KAAOxuB,EAAgBwuB,KAAO,KAAOxuB,EAAgByuB,KAAOzuB,EAAgByuB,KAAO,KAAOzuB,EAAgB0uB,KAAO1uB,EAAgB0uB,KAAO,KAAO1uB,EAAgB2uB,KAAO3uB,EAAgB2uB,KAAO,KAAO3uB,EAAgB4uB,KAAO5uB,EAAgB4uB,KAAO,KAAO5uB,EAAgB6uB,KAAO7uB,EAAgB6uB,KAAO,KAAO7uB,EAAgB8uB,KAAO9uB,EAAgB8uB,KAAO,KAAO9uB,EAAgB+uB,KAAO/uB,EAAgB+uB,KAAO,KAAO/uB,EAAgBgvB,KAAOhvB,EAAgBgvB,KAAO,KAAOhvB,EAAgBivB,KAAOjvB,EAAgBivB,KAAO,KAAOjvB,EAAgBkvB,KAAOlvB,EAAgBkvB,KAAO,KAAOlvB,EAAgBmvB,KAAOnvB,EAAgBmvB,KAAO,KAAOnvB,EAAgBovB,KAAOpvB,EAAgBovB,KAAO,KAAOpvB,EAAgBqvB,KAAOrvB,EAAgBqvB,KAAO,KAAOrvB,EAAgBsvB,KAAOtvB,EAAgBsvB,KAAO,KAAOtvB,EAAgBuvB,KAAOvvB,EAAgBuvB,KAAO,KAAOvvB,EAAgBwvB,KAAOxvB,EAAgBwvB,KAAO,KAAOxvB,EAAgByvB,KAAOzvB,EAAgByvB,KAAO,KAAOzvB,EAAgB0vB,KAAO1vB,EAAgB0vB,KAAO,KAAO1vB,EAAgB2vB,KAAO3vB,EAAgB2vB,KAAO,KAAO3vB,EAAgB4vB,KAAO5vB,EAAgB4vB,KAAO,KAAO5vB,EAAgB6vB,KAAO7vB,EAAgB6vB,KAAO,KAAO7vB,EAAgB8vB,KAAO9vB,EAAgB8vB,KAAO,KAAO9vB,EAAgB+vB,KAAO/vB,EAAgB+vB,KAAO,KAAO/vB,EAAgBgwB,KAAOhwB,EAAgBgwB,KAAO,KAAOhwB,EAAgBiwB,KAAOjwB,EAAgBiwB,KAAO,KAAOjwB,EAAgBkwB,KAAOlwB,EAAgBkwB,KAAO,KAAOlwB,EAAgBmwB,KAAOnwB,EAAgBmwB,KAAO,KAAOnwB,EAAgBowB,KAAOpwB,EAAgBowB,KAAO,KAAOpwB,EAAgBqwB,KAAOrwB,EAAgBqwB,KAAO,KAAOrwB,EAAgBswB,KAAOtwB,EAAgBswB,KAAO,KAAOtwB,EAAgBuwB,KAAOvwB,EAAgBuwB,KAAO,KAAOvwB,EAAgBwwB,KAAOxwB,EAAgBwwB,KAAO,KAAOxwB,EAAgBywB,KAAOzwB,EAAgBywB,KAAO,KAAOzwB,EAAgB0wB,KAAO1wB,EAAgB0wB,KAAO,KAAO1wB,EAAgB2wB,KAAO3wB,EAAgB2wB,KAAO,KAAO3wB,EAAgB4wB,KAAO5wB,EAAgB4wB,KAAO,KAAO5wB,EAAgB6wB,KAAO7wB,EAAgB6wB,KAAO,KAAO7wB,EAAgB8wB,KAAO9wB,EAAgB8wB,KAAO,KAAO9wB,EAAgB+wB,KAAO/wB,EAAgB+wB,KAAO,KAAO/wB,EAAgBgxB,KAAOhxB,EAAgBgxB,KAAO,KAAOhxB,EAAgBixB,KAAOjxB,EAAgBixB,KAAO,KAAOjxB,EAAgBkxB,KAAOlxB,EAAgBkxB,KAAO,KAAOlxB,EAAgBmxB,KAAOnxB,EAAgBmxB,KAAO,KAAOnxB,EAAgBoxB,KAAOpxB,EAAgBoxB,KAAO,KAAOpxB,EAAgBqxB,KAAOrxB,EAAgBqxB,KAAO,KAAOrxB,EAAgBsxB,KAAOtxB,EAAgBsxB,KAAO,KAAOtxB,EAAgBuxB,KAAOvxB,EAAgBuxB,KAAO,KAAOvxB,EAAgBwxB,KAAOxxB,EAAgBwxB,KAAO,KAAOxxB,EAAgByxB,KAAOzxB,EAAgByxB,KAAO,KAAOzxB,EAAgB0xB,KAAO1xB,EAAgB0xB,KAAO,KAAO1xB,EAAgB2xB,KAAO3xB,EAAgB2xB,KAAO,KAAO3xB,EAAgB4xB,KAAO5xB,EAAgB4xB,KAAO,KAAO5xB,EAAgB6xB,KAAO7xB,EAAgB6xB,KAAO,KAAO7xB,EAAgB8xB,KAAO9xB,EAAgB8xB,KAAO,KAAO9xB,EAAgB+xB,KAAO/xB,EAAgB+xB,KAAO,KAAO/xB,EAAgBgyB,KAAOhyB,EAAgBgyB,KAAO,KAAOhyB,EAAgBiyB,KAAOjyB,EAAgBiyB,KAAO,KAAOjyB,EAAgBkyB,KAAOlyB,EAAgBkyB,KAAO,KAAOlyB,EAAgBmyB,KAAOnyB,EAAgBmyB,KAAO,KAAOnyB,EAAgBoyB,KAAOpyB,EAAgBoyB,KAAO,KAAOpyB,EAAgBqyB,KAAOryB,EAAgBqyB,KAAO,KAAOryB,EAAgBsyB,KAAOtyB,EAAgBsyB,KAAO,KAAOtyB,EAAgBuyB,KAAOvyB,EAAgBuyB,KAAO,KAAOvyB,EAAgBwyB,KAAOxyB,EAAgBwyB,KAAO,KAAOxyB,EAAgByyB,KAAOzyB,EAAgByyB,KAAO,KAAOzyB,EAAgB0yB,KAAO1yB,EAAgB0yB,KAAO,KAAO1yB,EAAgB2yB,KAAO3yB,EAAgB2yB,KAAO,KAAO3yB,EAAgB4yB,KAAO5yB,EAAgB4yB,KAAO,KAAO5yB,EAAgB6yB,KAAO7yB,EAAgB6yB,KAAO,KAAO7yB,EAAgB8yB,KAAO9yB,EAAgB8yB,KAAO,KAAO9yB,EAAgB+yB,KAAO/yB,EAAgB+yB,KAAO,KAAO/yB,EAAgBgzB,KAAOhzB,EAAgBgzB,KAAO,KAAOhzB,EAAgBizB,KAAOjzB,EAAgBizB,KAAO,KAAOjzB,EAAgBkzB,KAAOlzB,EAAgBkzB,KAAO,KAAOlzB,EAAgBmzB,KAAOnzB,EAAgBmzB,KAAO,KAAOnzB,EAAgBozB,KAAOpzB,EAAgBozB,KAAO,KAAOpzB,EAAgBqzB,KAAOrzB,EAAgBqzB,KAAO,KAAOrzB,EAAgBszB,KAAOtzB,EAAgBszB,KAAO,KAAOtzB,EAAgBuzB,KAAOvzB,EAAgBuzB,KAAO,KAAOvzB,EAAgBwzB,KAAOxzB,EAAgBwzB,KAAO,KAAOxzB,EAAgByzB,KAAOzzB,EAAgByzB,KAAO,KAAOzzB,EAAgB0zB,KAAO1zB,EAAgB0zB,KAAO,KAAO1zB,EAAgB2zB,KAAO3zB,EAAgB2zB,KAAO,KAAO3zB,EAAgB4zB,KAAO5zB,EAAgB4zB,KAAO,KAAO5zB,EAAgB6zB,KAAO7zB,EAAgB6zB,KAAO,KAAO7zB,EAAgB8zB,KAAO9zB,EAAgB8zB,KAAO,KAAO9zB,EAAgB+zB,KAAO/zB,EAAgB+zB,KAAO,KAAO/zB,EAAgBg0B,KAAOh0B,EAAgBg0B,KAAO,KAAOh0B,EAAgBi0B,KAAOj0B,EAAgBi0B,KAAO,KAAOj0B,EAAgBk0B,KAAOl0B,EAAgBk0B,KAAO,KAAOl0B,EAAgBm0B,KAAOn0B,EAAgBm0B,KAAO,KAAOn0B,EAAgBo0B,KAAOp0B,EAAgBo0B,KAAO,KAAOp0B,EAAgBq0B,KAAOr0B,EAAgBq0B,KAAO,KAAOr0B,EAAgBs0B,KAAOt0B,EAAgBs0B,KAAO,KAAOt0B,EAAgBu0B,KAAOv0B,EAAgBu0B,KAAO,KAAOv0B,EAAgBw0B,KAAOx0B,EAAgBw0B,KAAO,KAAOx0B,EAAgBy0B,KAAOz0B,EAAgBy0B,KAAO,KAAOz0B,EAAgB00B,KAAO10B,EAAgB00B,KAAO,KAAO10B,EAAgB20B,KAAO30B,EAAgB20B,KAAO,KAAO30B,EAAgB40B,KAAO50B,EAAgB40B,KAAO,KAAO50B,EAAgB60B,KAAO70B,EAAgB60B,KAAO,KAAO70B,EAAgB80B,KAAO90B,EAAgB80B,KAAO,KAAO90B,EAAgB+0B,KAAO/0B,EAAgB+0B,KAAO,KAAO/0B,EAAgBg1B,KAAOh1B,EAAgBg1B,KAAO,KAAOh1B,EAAgBi1B,KAAOj1B,EAAgBi1B,KAAO,KAAOj1B,EAAgBk1B,KAAOl1B,EAAgBk1B,KAAO,KAAOl1B,EAAgBm1B,KAAOn1B,EAAgBm1B,KAAO,KAAOn1B,EAAgBo1B,KAAOp1B,EAAgBo1B,KAAO,KAAOp1B,EAAgBq1B,KAAOr1B,EAAgBq1B,KAAO,KAAOr1B,EAAgBs1B,KAAOt1B,EAAgBs1B,KAAO,KAAOt1B,EAAgBu1B,KAAOv1B,EAAgBu1B,KAAO,KAAOv1B,EAAgBw1B,KAAOx1B,EAAgBw1B,KAAO,KAAOx1B,EAAgBy1B,KAAOz1B,EAAgBy1B,KAAO,KAAOz1B,EAAgB01B,KAAO11B,EAAgB01B,KAAO,KAAO11B,EAAgB21B,KAAO31B,EAAgB21B,KAAO,KAAO31B,EAAgB41B,KAAO51B,EAAgB41B,KAAO,KAAO51B,EAAgB61B,KAAO71B,EAAgB61B,KAAO,KAAO71B,EAAgB81B,KAAO91B,EAAgB81B,KAAO,KAAO91B,EAAgB+1B,KAAO/1B,EAAgB+1B,KAAO,KAAO/1B,EAAgBg2B,KAAOh2B,EAAgBg2B,KAAO,KAAOh2B,EAAgBi2B,KAAOj2B,EAAgBi2B,KAAO,KAAOj2B,EAAgBk2B,KAAOl2B,EAAgBk2B,KAAO,KAAOl2B,EAAgBm2B,KAAOn2B,EAAgBm2B,KAAO,KAAOn2B,EAAgBo2B,KAAOp2B,EAAgBo2B,KAAO,KAAOp2B,EAAgBq2B,KAAOr2B,EAAgBq2B,KAAO,KAAOr2B,EAAgBs2B,KAAOt2B,EAAgBs2B,KAAO,KAAOt2B,EAAgBu2B,KAAOv2B,EAAgBu2B,KAAO,KAAOv2B,EAAgBw2B,KAAOx2B,EAAgBw2B,KAAO,KAAOx2B,EAAgBy2B,KAAOz2B,EAAgBy2B,KAAO,KAAOz2B,EAAgB02B,KAAO12B,EAAgB02B,KAAO,KAAO12B,EAAgB22B,KAAO32B,EAAgB22B,KAAO,KAAO32B,EAAgB42B,KAAO52B,EAAgB42B,KAAO,KAAO52B,EAAgB62B,KAAO72B,EAAgB62B,KAAO,KAAO72B,EAAgB82B,KAAO92B,EAAgB82B,KAAO,KAAO92B,EAAgB+2B,KAAO/2B,EAAgB+2B,KAAO,KAAO/2B,EAAgBg3B,KAAOh3B,EAAgBg3B,KAAO,KAAOh3B,EAAgBi3B,KAAOj3B,EAAgBi3B,KAAO,KAAOj3B,EAAgBk3B,KAAOl3B,EAAgBk3B,KAAO,KAAOl3B,EAAgBm3B,KAAOn3B,EAAgBm3B,KAAO,KAAOn3B,EAAgBo3B,KAAOp3B,EAAgBo3B,KAAO,KAAOp3B,EAAgBq3B,KAAOr3B,EAAgBq3B,KAAO,KAAOr3B,EAAgBs3B,KAAOt3B,EAAgBs3B,KAAO,KAAOt3B,EAAgBu3B,KAAOv3B,EAAgBu3B,KAAO,KAAOv3B,EAAgBw3B,KAAOx3B,EAAgBw3B,KAAO,KAAOx3B,EAAgBy3B,KAAOz3B,EAAgBy3B,KAAO,KAAOz3B,EAAgB03B,KAAO13B,EAAgB03B,KAAO,KAAO13B,EAAgB23B,KAAO33B,EAAgB23B,KAAO,KAAO33B,EAAgB43B,KAAO53B,EAAgB43B,KAAO,KAAO53B,EAAgB63B,KAAO73B,EAAgB63B,KAAO,KAAO73B,EAAgB83B,KAAO93B,EAAgB83B,KAAO,KAAO93B,EAAgB+3B,KAAO/3B,EAAgB+3B,KAAO,KAAO/3B,EAAgBg4B,KAAOh4B,EAAgBg4B,KAAO,KAAOh4B,EAAgBi4B,KAAOj4B,EAAgBi4B,KAAO,KAAOj4B,EAAgBk4B,KAAOl4B,EAAgBk4B,KAAO,KAAOl4B,EAAgBm4B,KAAOn4B,EAAgBm4B,KAAO,KAAOn4B,EAAgBo4B,KAAOp4B,EAAgBo4B,KAAO,KAAOp4B,EAAgBq4B,KAAOr4B,EAAgBq4B,KAAO,KAAOr4B,EAAgBs4B,KAAOt4B,EAAgBs4B,KAAO,KAAOt4B,EAAgBu4B,KAAOv4B,EAAgBu4B,KAAO,KAAOv4B,EAAgBw4B,KAAOx4B,EAAgBw4B,KAAO,KAAOx4B,EAAgBy4B,KAAOz4B,EAAgBy4B,KAAO,KAAOz4B,EAAgB04B,KAAO14B,EAAgB04B,KAAO,KAAO14B,EAAgB24B,KAAO34B,EAAgB24B,KAAO,KAAO34B,EAAgB44B,KAAO54B,EAAgB44B,KAAO,KAAO54B,EAAgB64B,KAAO74B,EAAgB64B,KAAO,KAAO74B,EAAgB84B,KAAO94B,EAAgB84B,KAAO,KAAO94B,EAAgB+4B,KAAO/4B,EAAgB+4B,KAAO,KAAO/4B,EAAgBg5B,KAAOh5B,EAAgBg5B,KAAO,KAAOh5B,EAAgBi5B,KAAOj5B,EAAgBi5B,KAAO,KAAOj5B,EAAgBk5B,KAAOl5B,EAAgBk5B,KAAO,KAAOl5B,EAAgBm5B,KAAOn5B,EAAgBm5B,KAAO,KAAOn5B,EAAgBo5B,KAAOp5B,EAAgBo5B,KAAO,KAAOp5B,EAAgBq5B,KAAOr5B,EAAgBq5B,KAAO,KAAOr5B,EAAgBs5B,KAAOt5B,EAAgBs5B,KAAO,KAAOt5B,EAAgBu5B,KAAOv5B,EAAgBu5B,KAAO,KAAOv5B,EAAgBw5B,KAAOx5B,EAAgBw5B,KAAO,KAAOx5B,EAAgBy5B,KAAOz5B,EAAgBy5B,KAAO,KAAOz5B,EAAgB05B,KAAO15B,EAAgB05B,KAAO,KAAO15B,EAAgB25B,KAAO35B,EAAgB25B,KAAO,KAAO35B,EAAgB45B,KAAO55B,EAAgB45B,KAAO,KAAO55B,EAAgB65

AAa,SAAAC,UAC5BL,EAAqBC,EAAsBhhB,OAAU+F,KAAYqb,KAGnEF,EAAiB5C,MAAQ,SAAAA,UACvByC,EAAqBC,EAAsBhhB,OACtC+F,GACHuY,MAAOjV,MAAMzL,UAAUyd,OAAOtV,EAAQuY,MAAOA,GAAO9F,OAAO1Z,aAAaxDoiB,EDzBuBH,CAAqBM,GAAiBrhB,IEItE,IAAK,IAAMwR,KCRI,CACb,IACA,OACA,UACA,OACA,UACA,QACA,QACA,IACA,OACA,MACA,MACA,MACA,aACA,OACA,KACA,SACA,SACA,UACA,OACA,OACA,MACA,WACA,OACA,WACA,KACA,MACA,UACA,MACA,SACA,MACA,KACA,KACA,KACA,QACA,WACA,aACA,SACA,SACA,OACA,KACA,KACA,KACA,KACA,KACA,KACA,OACA,SACA,SACA,KACA,OACA,IACA,SACA,MACA,QACA,MACA,MACA,SACA,QACA,SACA,KACA,OACA,OACA,MACA,OACA,UACA,OACA,WACA,OACA,QACA,MACA,WACA,SACA,KACA,WACA,SACA,SACA,IACA,QACA,UACA,MACA,WACA,IACA,KACA,KACA,OACA,IACA,OACA,SACA,UACA,SACA,QACA,SACA,OACA,SACA,QACA,MACA,UACA,MACA,QACA,QACA,KACA,WACA,QACA,KACA,QACA,OACA,QACA,KACA,QACA,IACA,KACA,MACA,QACA,MAGA,SACA,WACA,OACA,UACA,gBACA,IACA,QACA,OACA,iBACA,SACA,OACA,OACA,UACA,UACA,WACA,iBACA,OACA,OACA,MACA,OACA,WACA,SHnIUhS,SAAQ,SAAAA8hB,GAClBR,GAAOQ,GAAQ,GAAAC,KAAIT,GAAOQ,GAAOR,IAAS,GAAIA,GAAOQ,GAAOE,GAAKV,GAAOQ,GAAOE,IAAO,GAAIV,GAAOQ,GAAOE,GAAIC,GAAKX,GAAOQ,GAAOE,GAAIC,IAAO,GAAIX,GAAOQ,GAAOE,GAAIC,GAAIC,GAAKZ,GAAOQ,GAAOE,GAAIC,GAAIC,IAAO,GAAIZ,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAKb,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,IAAO,GAAIb,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAKd,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,IAAO,GAAId,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAKf,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,IAAO,GAAIf,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAKhB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,IAAO,GAAIhB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAKjB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,IAAO,GAAIjB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAKlB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,IAAO,GAAIlB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAKnB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,IAAO,GAAInB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAKpB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,IAAO,GAAIpB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAKrB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,IAAO,GAAIrB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAKtB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,IAAO,GAAItB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAKvB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,IAAO,GAAIvB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAKxB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,IAAO,GAAIxB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAKzB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,IAAO,GAAIzB,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,IAAO,GAAI1B,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,IAAO,GAAI3B,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,IAAO,GAAI5B,GAAOQ,GAAOE,GAAIC,IAAO,GAAI7B,GAAOQ,GAAOE,GAAIC,IAAO,GAAI9B,GAAOQ,GAAOE,GAAIC,IAAO,GAAI/B,GAAOQ,GAAOE,GAAIC,IAAO,GAAIhC,GAAOQ,GAAOE,GAAIC,IAAO,GAAIjC,GAAOQ,GAAOE,GAAIC,IAAO,GAAIlC,GAAOQ,GAAOE,GAAIC,IAAO,GAAInC,GAAOQ,GAAOE,GAAIC,IAAO,GAAIpC,GAAOQ,GAAOE,GAAIC,IAAO,GAAIrC,GAAOQ,GAAOE,GAAIC,IAAO,GAAItC,GAAOQ,GAAOE,GAAIC,IAAO,GAAIvC,GAAOQ,GAAOE,GAAIC,IAAO,GAAIxC,GAAOQ,GAAOE,GAAIC,IAAO,GAAIzC,GAAOQ,GAAOE,GAAIC,IAAO,GAAI1C,GAAOQ,GAAOE,GAAIC,IAAO,GAAI3C,GAAOQ,GAAOE,GAAIC,IAAO,GAAI5C,GAAOQ,GAAOE,GAAIC,IAAO,GAAI7C,GAAOQ,GAAOE,GAAIC,IAAO,GAAI9C,GAAOQ,GAAOE,GAAIC,IAAO,GAAI/C,GAAOQ,GAAOE,GAAIC,IAAO,GAAIhD,GAAOQ,GAAOE,GAAIC,IAAO,GAAIjD,GAAOQ,GAAOE,GAAIC,IAAO,GAAIlD,GAAOQ,GAAOE,GAAIC,IAAO,GAAInD,GAAOQ,GAAOE,GAAIC,IAAO,GAAIpD,GAAOQ,GAAOE,GAAIC,IAAO,GAAIrD,GAAOQ,GAAOE,GAAIC,IAAO,GAAItD,GAAOQ,GAAOE,GAAIC,IAAO,GAAIvD,GAAOQ,GAAOE,GAAIC,IAAO,GAAIxD,GAAOQ,GAAOE,GAAIC,IAAO,GAAIzD,GAAOQ,GAAOE,GAAIC,IAAO,GAAI1D,GAAOQ,GAAOE,GAAIC,IAAO,GAAI3D,GAAOQ,GAAOE,GAAIC,IAAO,GAAI5D,GAAOQ,GAAOE,GAAIC,IAAO,GAAI7D,GAAOQ,GAAOE,GAAIC,IAAO,GAAI9D,GAAOQ,GAAOE,GAAIC,IAAO,GAAI/D,GAAOQ,GAAOE,GAAIC,IAAO,GAAIhE,GAAOQ,GAAOE,GAAIC,IAAO,GAAIjE,GAAOQ,GAAOE,GAAIC,IAAO,GAAIlE,GAAOQ,GAAOE,GAAIC,IAAO,GAAInE,GAAOQ,GAAOE,GAAIC,IAAO,GAAIpE,GAAOQ,GAAOE,GAAIC,IAAO,GAAIrE,GAAOQ,GAAOE,GAAIC,IAAO,GAAItE,GAAOQ,GAAOE,GAAIC,IAAO,GAAIvE,GAAOQ,GAAOE,GAAIC,IAAO,GAAIxE,GAAOQ,GAAOE,GAAIC,IAAO,GAAIzE,GAAOQ,GAAOE,GAAIC,IAAO,GAAI1E,GAAOQ,GAAOE,GAAIC,IAAO,GAAI3E,GAAOQ,GAAOE,GAAIC,IAAO,GAAI5E,GAAOQ,GAAOE,GAAIC,IAAO,GAAI7E,GAAOQ,GAAOE,GAAIC,IAAO,GAAI9E,GAAOQ,GAAOE,GAAIC,IAAO,GAAI/E,GAAOQ,GAAOE,GAAIC,IAAO,GAAIhF,GAAOQ,GAAOE,GAAIC,IAAO,GAAIjF,GAAOQ,GAAOE,GAAIC,IAAO,GAAIlF,GAAOQ,GAAOE,GAAIC,IAAO,GAAInF,GAAOQ,GAAOE,GAAIC,IAAO,GAAIpF,GAAOQ,GAAOE,GAAIC,IAAO,GAAIrF,GAAOQ,GAAOE,GAAIC,IAAO,GAAItF,GAAOQ,GAAOE,GAAIC,IAAO,GAAIvF,GAAOQ,GAAOE,GAAIC,IAAO,GAAIxF,GAAOQ,GAAOE,GAAIC,IAAO,GAAIzF,GAAOQ,GAAOE,GAAIC,IAAO,GAAI1F,GAAOQ,GAAOE,GAAIC,IAAO,GAAI3F,GAAOQ,GAAOE,GAAIC,IAAO,GAAI5F,GAAOQ,GAAOE,GAAIC,IAAO,GAAI7F,GAAOQ,GAAOE,GAAIC,IAAO,GAAI9F,GAAOQ,GAAOE,GAAIC,IAAO,GAAI/F,GAAOQ,GAAOE,GAAIC,IAAO,GAAIhG,GAAOQ,GAAOE,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,GAAIC,

divide by alphabet-length */\n for (x = Math.abs(code); x > charsLength; x = (x / charsLength) | 0) {\n   name = getAlphabeticChar(x % charsLength) + name;\n }\n\n return (getAlphabeticChar(x % charsLength) + name).replace(AD_REPLACER_R, '$1-$2');\n}\n","// @flow\n/* eslint-disable */\n\nexport const SEED = 5381;\n\n// When we have separate strings it's useful to run a progressive\n// version of djb2 where we pretend that we're still looping over\n// the same string\nexport const phash = (h: number, x: string): number => {\n let i = x.length;\n\n while (i) {\n   h = (h * 33) ^ x.charCodeAt(--i);\n }\n\n return h;\n};\n\n// This is a djb2 hashing function\nexport const hash = (x: string): number => {\n return phash(SEED, x);\n};\n","// @flow\n/* eslint-disable */\nimport generateAlphabeticName from './generateAlphabeticName';\nimport { hash } from './hash';\n\nexport default (str: string): string => {\n return generateAlphabeticName(hash(str) >>> 0);\n};\n","// @flow\nimport type { IStyledComponent } from '../types';\n\nexport default function getComponentName(\n target: $PropertyType<IStyledComponent, 'target'>\n): string {\n return (\n   (process.env.NODE_ENV !== 'production' ? typeof target === 'string' && target : false) ||\n   // $FlowFixMe\n   target.displayName ||\n   // $FlowFixMe\n   target.name ||\n   'Component'\n);\n}\n","// @flow\nexport default function isFunction(test: any): boolean %checks {\n return typeof test === 'function';\n}\n","// @flow\nexport default function isStatelessFunction(test: any): boolean {\n return (\n   typeof test === 'function'\n   && !(\n   test.prototype\n   && test.prototype.isReactComponent\n   )\n);\n}\n","// @flow\nimport { typeOf } from 'react-is';\n\nexport default (x: any): boolean =>\n x !== null &&\n typeof x === 'object' &&\n (x.toString ? x.toString() : Object.prototype.toString.call(x)) === '[object Object]' &&\n !typeOf(x);\n","// @flow\nexport default function isStyledComponent(target:
 any): boolean %checks {\n return target && typeof target.styledComponentId === 'string';\n}\n","// @flow\n\ndeclare var SC_DISABLE_SPEEDY: ?boolean;\ndeclare var __VERSION__: string;\n\nexport const SC_ATTR: string =\n (typeof process !== 'undefined' &&\n   typeof process.env !== 'undefined' &&\n   (process.env.REACT_APP_SC_ATTR || process.env.SC_ATTR)) ||\n 'data-styled';\n\nexport const SC_ATTR_ACTIVE = 'active';\nexport const SC_ATTR_VERSION = 'data-styled-version';\nexport const SC_VERSION = __VERSION__;\nexport const SPLITTER = '/*!sc*/\\n';\n\nexport const IS_BROWSER = typeof window !== 'undefined' && 'HTMLElement' in window;\n\nexport const DISABLE_SPEEDY = Boolean(\n typeof SC_DISABLE_SPEEDY === 'boolean'\n   ? SC_DISABLE_SPEEDY\n   : typeof process !== 'undefined' &&
 typeof process.env !== 'undefined'\n   ? typeof process.env.REACT_APP_SC_DISABLE_SPEEDY !== 'undefined' &&\n   process.env.REACT_APP_SC_DISABLE_SPEEDY !== ''\n   ? process.env.REACT_APP_SC_DISABLE_SPEEDY
 === 'false'\n   ? false\n   : process.env.REACT_APP_SC_DISABLE_SPEEDY\n   : typeof process.env.SC_DISABLE_SPEEDY !== 'undefined' && process.env.SC_DISABLE_SPEEDY !== ''\n   ? process.env.SC_DISABLE_SPEEDY === 'false'\n   ? false\n   : process.env.SC_DISABLE_SPEEDY\n   : process.env.NODE_ENV !== 'production'\n   : false\n);\n\n// Shared empty execution context when generating static styles\nexport const STATIC_EXECUTION_CONTEXT = {};\n","// @flow\nexport const EMPTY_ARRAY = Object.freeze([]);\n\nexport const EMPTY_OBJECT = Object.freeze({});\n","export default {\"1\":\"Cannot create styled-component for component: %s.\\n\\n\",\"2\":\"Can't collect styles once you've consumed a `ServerStyleSheet`'s styles! `ServerStyleSheet` is a one off instance for each server-side render cycle.\\n\\n- Are you trying to reuse it across renders?\\n- Are you accidentally calling collectStyles twice?\\n\\n\",\"3\":\"Streaming SSR is only supported in a Node.js
 environment; Please do not try to call this method in the browser.\\n\\n\",\"4\":\"The `StyleSheetManager` expects a valid target or sheet prop!\\n\\n- Does this error occur on the client and is your target falsy?\\n- Does this error occur on the server and is the sheet falsy?\\n\\n\",\"5\":\"The clone method cannot be used on the client!\\n\\n- Are you running in a client-like environment on the server?\\n- Are you trying to run SSR on the client?\\n\\n\",\"6\":\"Trying to insert a new style tag, but the given Node is unmounted!\\n\\n- Are you using a custom target that isn't mounted?\\n- Does your document not have a valid head element?\\n- Have you accidentally removed a style tag manually?\\n\\n\",\"7\":\"ThemeProvider: Please return an object from your \\\"theme\\\" prop function, e.g.\\n\\n```js\\ntheme={() => ({})}\\n```\\n\\n\",\"8\":\"ThemeProvider: Please make your \\\"theme\\\" prop an

object.\\n\\n\",\"9\":\"Missing document `<head>`\\n\\n\",\"10\":\"Cannot find a StyleSheet instance. Usually this happens if there are multiple copies of styled-components loaded at once. Check out this issue for how to troubleshoot and fix the common cases where this situation can happen: https://github.com/styled-components/styled-components/issues/1941#issuecomment-417862021\\n\\n\",\"11\":\"_This error was replaced with a dev-time warning, it will be deleted for v4 final._ [createGlobalStyle] received children which will not be rendered. Please use the component without passing children elements.\\n\\n\",\"12\":\"It seems you are interpolating a keyframe declaration (%s) into an untagged string. This was supported in styled-components v3, but is not longer supported in v4 as keyframes are now injected on-demand. Please wrap your string in the css\\\\`\\\\` helper which ensures the styles are injected correctly. See https://www.styled-components.com/docs/api#css\\n\\n\",\"13\":\"%s is not a styled component and cannot be referred to via component selector. See https://www.styled-components.com/docs/advanced#referring-to-other-components for more details.\\n\\n\",\"14\":\"ThemeProvider: \\\"theme\\\" prop is required.\\n\\n\",\"15\":\"A stylis plugin has been supplied that is not named. We need a name for each plugin to be able to prevent styling collisions between different stylis configurations within the same app. Before you pass your plugin to `<StyleSheetManager stylisPlugins={[]}>`, please make sure each plugin is uniquely-named, e.g.\\n\\n```js\\nObject.defineProperty(importedPlugin, 'name', { value: 'some-unique-name' });\\n```\\n\\n\",\"16\":\"Reached the limit of how many styled components may be created at group %s.\\nYou may only create up to 1,073,741,824 components. If you're creating components dynamically,\\nas for instance in your render method then you may be running into this limitation.\\n\\n\",\"17\":\"CSSStyleSheet could not be found on HTMLStyleElement.\\nHas styled-components' style tag been unmounted or altered by another script?\\n\"};","// @flow\nimport errorMap from './errors';\n\nconst ERRORS = process.env.NODE_ENV !== 'production' ? errorMap : {};\n\n/**\n * super basic version of sprintf\n */\nfunction format(...args) {\n let a = args[0];\n const b = [];\n\n for (let c = 1, len = args.length; c < len; c += 1) {\n   b.push(args[c]);\n }\n\n b.forEach(d => {\n   a = a.replace(/%[a-z]/, d);\n });\n\n return a;\n}\n\n/**\n * Create an error file out of errors.md for development and a simple web link to the full errors\n * in production mode.\n */\nexport default function throwStyledComponentsError(\n code: string | number,\n ...interpolations: Array<any>\n) {\n if (process.env.NODE_ENV === 'production') {\n   throw new Error(\n   `An error occurred. See https://git.io/JUIaE#${code} for more information.${\n        interpolations.length > 0 ? ` Args: ${interpolations.join(', ')}` : ''\n      }`\n   );\n } else {\n   throw new Error(format(ERRORS[code], ...interpolations).trim());\n }\n}\n","// @flow\n/* eslint-disable no-use-before-define */\n\nimport type { GroupedTag, Tag } from './types';\nimport { SPLITTER } from '../constants';\nimport throwStyledError from '../utils/error';\n\n/** Create a GroupedTag with an underlying Tag implementation */\nexport const makeGroupedTag = (tag: Tag): GroupedTag => {\n return new DefaultGroupedTag(tag);\n};\n\nconst BASE_SIZE = 1 << 9;\n\nclass DefaultGroupedTag implements GroupedTag {\n groupSizes: Uint32Array;\n\n length: number;\n\n tag: Tag;\n\n constructor(tag: Tag) {\n   this.groupSizes = new Uint32Array(BASE_SIZE);\n   this.length = BASE_SIZE;\n   this.tag = tag;\n }\n\n indexOfGroup(group: number): number {\n   let index = 0;\n   for (let i = 0; i < group; i++) {\n   index += this.groupSizes[i];\n   }\n\n   return index;\n }\n\n insertRules(group: number, rules: string[]): void {\n   if (group >= this.groupSizes.length) {\n   const oldBuffer = this.groupSizes;\n   const oldSize = oldBuffer.length;\n\n   let newSize = oldSize;\n   while (group >= newSize) {\n   newSize <<= 1;\n   if (newSize < 0) {\n   throwStyledError(16, `${group}`);\n   }\n   }\n\n   this.groupSizes = new Uint32Array(newSize);\n   this.groupSizes.set(oldBuffer);\n   this.length = newSize;\n\n   for (let i = oldSize; i < newSize; i++) {\n   this.groupSizes[i] = 0;\n   }\n   }\n\n   let ruleIndex = this.indexOfGroup(group + 1);\n   for (let i = 0, l = rules.length; i < l; i++) {\n   if (this.tag.insertRule(ruleIndex, rules[i])) {\n   this.groupSizes[group]++;\n   ruleIndex++;\n   }\n   }\n }\n\n clearGroup(group: number): void {\n   if (group < this.length) {\n   const length = this.groupSizes[group];\n   const startIndex = this.indexOfGroup(group);\n   const endIndex = startIndex + length;\n\n   this.groupSizes[group] = 0;\n\n   for (let i = startIndex; i < endIndex; i++) {\n   this.tag.deleteRule(startIndex);\n

```
  }\n  }\n }\n\n getGroup(group: number): string {\n  let css = '';\n  if (group >= this.length ||
this.groupSizes[group] === 0) {\n  return css;\n  }\n\n  const length = this.groupSizes[group];\n  const
startIndex = this.indexOfGroup(group);\n  const endIndex = startIndex + length;\n\n  for (let i = startIndex; i <
endIndex; i++) {\n  css += `${this.tag.getRule(i)}${SPLITTER}`;\n  }\n\n  return css;\n }\n}\n","//
@flow\n\nimport throwStyledError from '../utils/error';\n\nconst MAX_SMI = 1 << 31 - 1;\n\nlet groupIDRegister:
Map<string, number> = new Map();\nlet reverseRegister: Map<number, string> = new Map();\nlet nextFreeGroup =
1;\n\nexport const resetGroupIds = () => {\n groupIDRegister = new Map();\n reverseRegister = new Map();\n
nextFreeGroup = 1;\n};\n\nexport const getGroupForId = (id: string): number => {\n if (groupIDRegister.has(id))
{\n  return (groupIDRegister.get(id): any);\n }\n\n while (reverseRegister.has(nextFreeGroup)) {\n
 nextFreeGroup++;\n }\n\n const group = nextFreeGroup++;\n\n if (\n  process.env.NODE_ENV !== 'production'
&&\n  ((group | 0) < 0 || group > MAX_SMI)\n ) {\n  throwStyledError(16, `${group}`);\n }\n\n
groupIDRegister.set(id, group);\n reverseRegister.set(group, id);\n return group;\n};\n\nexport const
getIdForGroup = (group: number): void | string => {\n return reverseRegister.get(group);\n};\n\nexport const
setGroupForId = (id: string, group: number) => {\n if (group >= nextFreeGroup) {\n  nextFreeGroup = group +
1;\n }\n\n groupIDRegister.set(id, group);\n reverseRegister.set(group, id);\n};\n","// @flow\n\nimport {
SPLITTER, SC_ATTR, SC_ATTR_ACTIVE, SC_ATTR_VERSION, SC_VERSION } from '../constants';\nimport
{ getIdForGroup, setGroupForId } from './GroupIDAllocator';\nimport type { Sheet } from './types';\n\nconst
SELECTOR = `style[${SC_ATTR}][${SC_ATTR_VERSION}=\"${SC_VERSION}\"]`;\nconst MARKER_RE =
new RegExp(`^${SC_ATTR}\\\\.g(\\\\d+)\\\\[id=\"([\\\\w\\\\d-]+)\"\\\\].*?\"([^\"]*)`);\n\nexport
 const outputSheet = (sheet: Sheet) => {\n const tag = sheet.getTag();\n const { length } = tag;\n\n let css = '';\n
for (let group = 0; group < length; group++) {\n  const id = getIdForGroup(group);\n  if (id === undefined)
continue;\n\n  const names = sheet.names.get(id);\n  const rules = tag.getGroup(group);\n  if (!names || !rules ||
!names.size) continue;\n\n  const selector = `${SC_ATTR}.g${group}[id=\"${id}\"]`;\n\n  let content = '';\n  if
(names !== undefined) {\n  names.forEach(name => {\n  if (name.length > 0) {\n  content +=
`${name},`;\n  }\n  });\n  }\n\n  // NOTE: It's easier to collect rules and have the marker\n  // after the
actual rules to simplify the rehydration\n  css += `${rules}${selector}{content:\"${content}\"}${SPLITTER}`;\n
}\n\n return css;\n};\n\nconst rehydrateNamesFromContent = (sheet: Sheet, id: string, content: string) => {\n const
names = content.split(',');\n
 let name;\n\n for (let i = 0, l = names.length; i < l; i++) {\n  // eslint-disable-next-line\n  if ((name = names[i]))
{\n  sheet.registerName(id, name);\n  }\n }\n};\n\nconst rehydrateSheetFromTag = (sheet: Sheet, style:
HTMLStyleElement) => {\n const parts = (style.textContent || '').split(SPLITTER);\n const rules: string[] = [];\n\n
for (let i = 0, l = parts.length; i < l; i++) {\n  const part = parts[i].trim();\n  if (!part) continue;\n\n  const marker =
part.match(MARKER_RE);\n\n  if (marker) {\n  const group = parseInt(marker[1], 10) | 0;\n  const id =
marker[2];\n\n  if (group !== 0) {\n  // Rehydrate componentId to group index mapping\n
setGroupForId(id, group);\n  // Rehydrate names and rules\n  // looks like: data-
styled.g11[id=\"idA\"]{content:\"nameA,\"}\n  rehydrateNamesFromContent(sheet, id, marker[3]);\n
sheet.getTag().insertRules(group, rules);\n  }\n\n  rules.length = 0;\n  } else {\n
  rules.push(part);\n  }\n }\n};\n\nexport const rehydrateSheet = (sheet: Sheet) => {\n const nodes =
document.querySelectorAll(SELECTOR);\n\n for (let i = 0, l = nodes.length; i < l; i++) {\n  const node =
((nodes[i]: any): HTMLStyleElement);\n  if (node && node.getAttribute(SC_ATTR) !== SC_ATTR_ACTIVE)
{\n  rehydrateSheetFromTag(sheet, node);\n\n  if (node.parentNode) {\n
node.parentNode.removeChild(node);\n  }\n  }\n }\n};\n","// @flow\n/* eslint-disable camelcase, no-undef
*/\n\ndeclare var __webpack_nonce__: string;\n\nconst getNonce = () => {\n return typeof __webpack_nonce__
!== 'undefined' ? __webpack_nonce__ : null;\n};\n\nexport default getNonce;\n","// @flow\n\nimport { SC_ATTR,
SC_ATTR_ACTIVE, SC_ATTR_VERSION, SC_VERSION } from '../constants';\nimport getNonce from
'../utils/nonce';\nimport throwStyledError from '../utils/error';\n\nconst ELEMENT_TYPE = 1; /*
Node.ELEMENT_TYPE */\n\n/** Find last style element if any inside target */\nconst
```

```
findLastStyleTag = (target: HTMLElement): void | HTMLStyleElement => {\n  const { childNodes } = target;\n\n for (let i = childNodes.length; i >= 0; i--) {\n    const child = ((childNodes[i]: any): ?HTMLElement);\n    if (child && child.nodeType === ELEMENT_TYPE && child.hasAttribute(SC_ATTR)) {\n      return ((child: any): HTMLStyleElement);\n    }\n  }\n\n  return undefined;\n};\n\n/** Create a style element inside `target` or <head> after the last */\nexport const makeStyleTag = (target?: HTMLElement): HTMLStyleElement => {\n  const head = ((document.head: any): HTMLElement);\n  const parent = target || head;\n  const style = document.createElement('style');\n  const prevStyle = findLastStyleTag(parent);\n  const nextSibling = prevStyle !== undefined ? prevStyle.nextSibling : null;\n\n  style.setAttribute(SC_ATTR, SC_ATTR_ACTIVE);\n  style.setAttribute(SC_ATTR_VERSION, SC_VERSION);\n\n  const nonce = getNonce();\n\n  if (nonce) style.setAttribute('nonce', nonce);\n\n  parent.insertBefore(style, nextSibling);\n\n  return style;\n};\n\n/** Get the CSSStyleSheet instance for a given style element */\nexport const getSheet = (tag: HTMLStyleElement): CSSStyleSheet => {\n  if (tag.sheet) {\n    return ((tag.sheet: any): CSSStyleSheet);\n  }\n\n  // Avoid Firefox quirk where the style element might not have a sheet property\n  const { styleSheets } = document;\n  for (let i = 0, l = styleSheets.length; i < l; i++) {\n    const sheet = styleSheets[i];\n    if (sheet.ownerNode === tag) {\n      return ((sheet: any): CSSStyleSheet);\n    }\n  }\n\n  throwStyledError(17);\n  return (undefined: any);\n};\n","// @flow\n/* eslint-disable no-use-before-define */\n\nimport { makeStyleTag, getSheet } from './dom';\nimport type { SheetOptions, Tag } from './types';\n\n/** Create a CSSStyleSheet-like tag depending on the environment */\nexport const makeTag = ({ isServer, useCSSOMInjection, target }: SheetOptions): Tag => {\n  if (isServer) {\n    return new VirtualTag(target);\n  } else if (useCSSOMInjection) {\n    return new CSSOMTag(target);\n  } else {\n    return new TextTag(target);\n  }\n};\n\nexport class CSSOMTag implements Tag {\n  element: HTMLStyleElement;\n\n  sheet: CSSStyleSheet;\n\n  length: number;\n\n  constructor(target?: HTMLElement) {\n    const element = (this.element = makeStyleTag(target));\n\n    // Avoid Edge bug where empty style elements don't create sheets\n    element.appendChild(document.createTextNode(''));\n\n    this.sheet = getSheet(element);\n    this.length = 0;\n  }\n\n  insertRule(index: number, rule: string): boolean {\n    try {\n      this.sheet.insertRule(rule, index);\n      this.length++;\n      return true;\n    } catch (_error) {\n      return false;\n    }\n  }\n\n  deleteRule(index: number): void {\n    this.sheet.deleteRule(index);\n    this.length--;\n  }\n\n  getRule(index: number): string {\n    const rule = this.sheet.cssRules[index];\n    // Avoid IE11 quirk where cssText is inaccessible on some invalid rules\n    if (rule !== undefined && typeof rule.cssText === 'string') {\n      return rule.cssText;\n    } else {\n      return '';\n    }\n  }\n}\n\n/** A Tag that emulates the CSSStyleSheet API but uses text nodes */\nexport class TextTag implements Tag {\n  element: HTMLStyleElement;\n\n  nodes: NodeList<Node>;\n\n  length: number;\n\n  constructor(target?: HTMLElement) {\n    const element = (this.element = makeStyleTag(target));\n    this.nodes = element.childNodes;\n    this.length = 0;\n  }\n\n  insertRule(index: number, rule: string): boolean {\n    if (index <= this.length && index >= 0) {\n      const node = document.createTextNode(rule);\n      const refNode = this.nodes[index];\n      this.element.insertBefore(node, refNode || null);\n      this.length++;\n      return true;\n    } else {\n      return false;\n    }\n  }\n\n  deleteRule(index: number): void {\n    this.element.removeChild(this.nodes[index]);\n    this.length--;\n  }\n\n  getRule(index: number): string {\n    if (index < this.length) {\n      return this.nodes[index].textContent;\n    } else {\n      return '';\n    }\n  }\n}\n\n/** A completely virtual (server-side) Tag that doesn't manipulate the DOM */\nexport class VirtualTag implements Tag {\n  rules: string[];\n\n  length: number;\n\n  constructor(_target?: HTMLElement) {\n    this.rules = [];\n    this.length = 0;\n  }\n\n  insertRule(index: number, rule: string): boolean {\n    if (index <= this.length) {\n      this.rules.splice(index, 0, rule);\n      this.length++;\n      return true;\n    } else {\n      return false;\n    }\n  }\n\n  deleteRule(index: number): void {\n    this.rules.splice(index, 1);\n    this.length--;\n  }\n\n  getRule(index: number): string {\n    if (index < this.length) {\n      return this.rules[index];\n    } else {\n      return '';\n    }\n  }\n}\n","// @flow\nimport { DISABLE_SPEEDY, IS_BROWSER } from '../constants';\nimport { EMPTY_OBJECT } from '../utils/empties';\nimport { makeGroupedTag } from './GroupedTag';\nimport { getGroupForId } from './GroupIDAllocator';\nimport { outputSheet, rehydrateSheet } from './Rehydration';\nimport { makeTag } from './Tag';\nimport type { GroupedTag, Sheet, SheetOptions } from
```

'./types';\n\nlet SHOULD_REHYDRATE = IS_BROWSER;\n\ntype SheetConstructorArgs = {\n isServer?: boolean,\n useCSSOMInjection?: boolean,\n target?: HTMLElement,\n};\n\ntype GlobalStylesAllocationMap = { [key: string]: number };\ntype NamesAllocationMap = Map<string, Set<string>>;\n\nconst defaultOptions: SheetOptions = {\n isServer: !IS_BROWSER,\n useCSSOMInjection: !DISABLE_SPEEDY,\n};\n\n/** Contains the main stylesheet logic for stringification and caching */\nexport default class StyleSheet implements Sheet {\n gs: GlobalStylesAllocationMap;\n\n names: NamesAllocationMap;\n\n options: SheetOptions;\n\n server: boolean;\n\n tag: void | GroupedTag;\n\n /** Register a group ID to give it an index */\n static registerId(id: string): number {\n   return getGroupForId(id);\n }\n\n constructor(\n   options: SheetConstructorArgs = EMPTY_OBJECT,\n   globalStyles?: GlobalStylesAllocationMap = {},\n   names?: NamesAllocationMap\n) {\n   this.options = {\n   ...defaultOptions,\n   ...options,\n   };\n\n   this.gs = globalStyles;\n   this.names = new Map(names);\n   this.server = !!options.isServer;\n\n   // We rehydrate only once and use the sheet that is created first\n   if (!this.server && IS_BROWSER && SHOULD_REHYDRATE) {\n   SHOULD_REHYDRATE = false;\n   rehydrateSheet(this);\n   }\n }\n\n reconstructWithOptions(options: SheetConstructorArgs, withNames?: boolean = true) {\n   return new StyleSheet(\n   { ...this.options, ...options },\n   this.gs,\n   (withNames && this.names) || undefined\n   );\n }\n\n allocateGSInstance(id: string) {\n   return (this.gs[id] = (this.gs[id] || 0) + 1);\n }\n\n /** Lazily initialises a GroupedTag for when it's actually needed */\n getTag(): GroupedTag {\n   return this.tag || (this.tag = makeGroupedTag(makeTag(this.options)));\n }\n\n /** Check whether a name is known for caching */\n hasNameForId(id: string, name: string): boolean {\n   return this.names.has(id) && (this.names.get(id): any).has(name);\n }\n\n /** Mark a group's name as known for caching */\n registerName(id: string, name: string) {\n   getGroupForId(id);\n\n   if (!this.names.has(id)) {\n   const groupNames = new Set();\n   groupNames.add(name);\n   this.names.set(id, groupNames);\n   } else {\n   (this.names.get(id): any).add(name);\n   }\n }\n\n /** Insert new rules which also marks the name as known */\n insertRules(id: string, name: string, rules: string[]) {\n   this.registerName(id, name);\n   this.getTag().insertRules(getGroupForId(id), rules);\n }\n\n /** Clears all cached names for a given group ID */\n clearNames(id: string) {\n   if (this.names.has(id)) {\n   (this.names.get(id): any).clear();\n   }\n }\n\n /** Clears all rules for a given group ID */\n clearRules(id: string) {\n   this.getTag().clearGroup(getGroupForId(id));\n   this.clearNames(id);\n }\n\n /** Clears the entire tag which deletes all rules but not its names */\n clearTag() {\n   // NOTE: This does not clear the names, since it's only used during SSR\n   // so that we can continuously output only new rules\n   this.tag = undefined;\n }\n\n /** Outputs the current sheet as a CSS string with markers for SSR */\n toString(): string {\n   return outputSheet(this);\n }\n}\n","/**\n * MIT License\n *\n * Copyright (c) 2016 Sultan Tarimo\n *\n * Permission is hereby granted, free of charge, to any person obtaining a copy of\n * this software and associated documentation files (the \"Software\"),\n * to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or\n * sell copies of the Software and to permit persons to whom the Software is furnished to do so, subject to the following conditions:\n *\n * The above copyright notice and this permission notice shall be included in all\n * copies or substantial portions of the Software.\n *\n * THE SOFTWARE IS PROVIDED \"AS IS\", WITHOUT WARRANTY OF ANY KIND, EXPRESS\n * OR IMPLIED INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,\n * FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE\n * AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,\n * WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR\n * IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.\n */\n/* eslint-disable */\n\nexport default function(insertRule) {\n const delimiter = '/*|*/';\n const needle = `${delimiter}}`;\n\n function toSheet(block) {\n   if (block) {\n   try {\n   insertRule(`${block}}`);\n   } catch (e) {}\n   }\n }\n\n return function ruleSheet(\n   context,\n   content,\n   selectors,\n   parents,\n   line,\n   column,\n   length,\n   ns,\n   depth,\n   at\n) {\n   switch (context) {\n   // property\n   case 1:\n   // @import\n   if (depth === 0 && content.charCodeAt(0) === 64) return

insertRule(`${content};`), ";\n break;\n // selector\n case 2:\n if (ns === 0) return content + delimiter;\n break;\n // at-rule\n case 3:\n switch (ns) {\n // @font-face, @page\n case 102:\n case 112:\n return insertRule(selectors[0] + content), ";\n default:\n return content + (at === 0 ? delimiter : '');\n }\n case -2:\n content.split(needle).forEach(toSheet);\n }\n };\n}\n","import Stylis from '@emotion/stylis';\nimport { type Stringifier } from '../types';\nimport { EMPTY_ARRAY, EMPTY_OBJECT } from './empties';\nimport throwStyledError from './error';\nimport { phash, SEED } from './hash';\nimport insertRulePlugin from './stylisPluginInsertRule';\n\nconst COMMENT_REGEX = /^\\s*\/\/.*$/gm;\nconst COMPLEX_SELECTOR_PREFIX = [':', '[', '.', '#'];\n\ntype StylisInstanceConstructorArgs = {\n options?: Object,\n plugins?: Array<Function>,\n};\n\nexport default function createStylisInstance({\n options = EMPTY_OBJECT,\n plugins = EMPTY_ARRAY,\n}: StylisInstanceConstructorArgs = EMPTY_OBJECT) {\n const stylis = new Stylis(options);\n\n // Wrap `insertRulePlugin to build a list of rules,\n // and then make our own plugin to return the rules. This\n // makes it easier to hook into the existing SSR architecture\n\n let parsingRules = [];\n\n // eslint-disable-next-line consistent-return\n const returnRulesPlugin = context => {\n if (context === -2) {\n const parsedRules = parsingRules;\n parsingRules = [];\n return parsedRules;\n }\n };\n\n const parseRulesPlugin = insertRulePlugin(rule => {\n parsingRules.push(rule);\n });\n\n let _componentId: string;\n let _selector:
string;\n let _selectorRegexp: RegExp;\n let _consecutiveSelfRefRegExp: RegExp;\n\n const selfReferenceReplacer = (match, offset, string) => {\n if (\n // do not replace the first occurrence if it is complex (has a modifier)\n (offset === 0 ? COMPLEX_SELECTOR_PREFIX.indexOf(string[_selector.length]) === -1 : true) &&\n // no consecutive self refs (.b.b); that is a precedence boost and treated differently\n !string.match(_consecutiveSelfRefRegExp)\n) {\n return `.${_componentId}`;\n }\n\n return match;\n };\n\n /**\n * When writing a style like\n *\n * & + & {\n * color: red;\n * }\n *\n * The second ampersand should be a reference to the static component class. stylis\n * has no knowledge of static class so we have to intelligently replace the base selector.\n *\n * https://github.com/thysultan/stylis.js/tree/v3.5.4#plugins <- more info about the context phase values\n * \"2\" means this plugin is taking effect
at the very end after all other processing is complete\n */\n const selfReferenceReplacementPlugin = (context, _, selectors) => {\n if (context === 2 && selectors.length && selectors[0].lastIndexOf(_selector) > 0) {\n // eslint-disable-next-line no-param-reassign\n selectors[0] = selectors[0].replace(_selectorRegexp, selfReferenceReplacer);\n }\n };\n\n stylis.use([...plugins, selfReferenceReplacementPlugin, parseRulesPlugin, returnRulesPlugin]);\n\n function stringifyRules(css, selector, prefix, componentId = '&'): Stringifier {\n const flatCSS = css.replace(COMMENT_REGEX, '');\n const cssStr = selector && prefix ? `${prefix} ${selector} { ${flatCSS} }` : flatCSS;\n\n // stylis has no concept of state to be passed to plugins\n // but since JS is single-threaded, we can rely on that to ensure\n // these properties stay in sync with the current stylis run\n _componentId = componentId;\n _selector = selector;\n _selectorRegexp = new RegExp(`\\\\${_selector}\\\\b`, 'g');\n _consecutiveSelfRefRegExp = new RegExp(`(\\\\${_selector}\\\\b){2,}`);\n\n return stylis(prefix || !selector ? '' : selector, cssStr);\n }\n\n stringifyRules.hash = plugins.length\n ? plugins\n .reduce((acc, plugin) => {\n if (!plugin.name) {\n throwStyledError(15);\n }\n\n return phash(acc, plugin.name);\n }, SEED)\n .toString()\n : '';\n\n return stringifyRules;\n}\n","// @flow\nimport React, { type Context, type Node, useContext, useEffect, useMemo, useState } from 'react';\nimport shallowequal from 'shallowequal';\nimport StyleSheet from '../sheet';\nimport type { Stringifier } from '../types';\nimport createStylisInstance from '../utils/stylis';\n\ntype Props = {\n children?: Node,\n disableCSSOMInjection?: boolean,\n disableVendorPrefixes?: boolean,\n sheet?: StyleSheet,\n stylisPlugins?: Array<Function>,\n target?: HTMLElement,\n};\n\nexport const StyleSheetContext: Context<StyleSheet
| void> = React.createContext();\nexport const StyleSheetConsumer = StyleSheetContext.Consumer;\nexport const StylisContext: Context<Stringifier | void> = React.createContext();\nexport const StylisConsumer = StylisContext.Consumer;\n\nexport const masterSheet: StyleSheet = new StyleSheet();\nexport const masterStylis: Stringifier = createStylisInstance();\n\nexport function useStyleSheet(): StyleSheet {\n return

useContext(StyleSheetContext) || masterSheet;\n}\n\nexport function useStylis(): Stringifier {\n return useContext(StylisContext) || masterStylis;\n}\n\nexport default function StyleSheetManager(props: Props) {\n const [plugins, setPlugins] = useState(props.stylisPlugins);\n const contextStyleSheet = useStyleSheet();\n\n const styleSheet = useMemo(() => {\n   let sheet = contextStyleSheet;\n\n   if (props.sheet) {\n   // eslint-disable-next-line prefer-destructuring\n   sheet = props.sheet;\n   } else if (props.target) {\n   sheet = sheet.reconstructWithOptions({
 target: props.target }, false);\n   }\n\n   if (props.disableCSSOMInjection) {\n   sheet = sheet.reconstructWithOptions({ useCSSOMInjection: false });\n   }\n\n   return sheet;\n }, [props.disableCSSOMInjection, props.sheet, props.target]);\n\n const stylis = useMemo(\n   () =>\n createStylisInstance({\n   options: { prefix: !props.disableVendorPrefixes },\n   plugins,\n   }),\n [props.disableVendorPrefixes, plugins]\n);\n\n useEffect(() => {\n   if (!shallowequal(plugins, props.stylisPlugins)) setPlugins(props.stylisPlugins);\n }, [props.stylisPlugins]);\n\n return (\n <StyleSheetContext.Provider value={styleSheet}>\n   <StylisContext.Provider value={stylis}>\n {process.env.NODE_ENV !== 'production'\n   ? React.Children.only(props.children)\n   : props.children}\n   </StylisContext.Provider>\n   </StyleSheetContext.Provider>\n);\n}\n","// @flow\nimport StyleSheet from '../sheet';\nimport { type
 Stringifier } from '../types';\nimport throwStyledError from '../utils/error';\nimport { masterStylis } from './StyleSheetManager';\n\nexport default class Keyframes {\n id: string;\n\n name: string;\n\n rules: string;\n\n constructor(name: string, rules: string) {\n   this.name = name;\n   this.id = `sc-keyframes-${name}`;\n   this.rules = rules;\n }\n\n inject = (styleSheet: StyleSheet, stylisInstance: Stringifier = masterStylis) => {\n   const resolvedName = this.name + stylisInstance.hash;\n\n   if (!styleSheet.hasNameForId(this.id, resolvedName)) {\n styleSheet.insertRules(\n   this.id,\n   resolvedName,\n   stylisInstance(this.rules, resolvedName, '@keyframes')\n   );\n   }\n };\n\n toString = () => {\n   return throwStyledError(12, String(this.name));\n };\n\n getName(stylisInstance: Stringifier = masterStylis) {\n   return this.name + stylisInstance.hash;\n }\n}\n","// @flow\n\n/**\n * inlined version of\n * https://github.com/facebook/fbjs/blob/master/packages/fbjs/src/core/hyphenateStyleName.js\n
 */\n\nconst uppercaseCheck = /([A-Z])/;\nconst uppercasePattern = /([A-Z])/g;\nconst msPattern = /^ms-/;\nconst prefixAndLowerCase = (char: string): string => `-${char.toLowerCase()}`;\n\n/**\n * Hyphenates a camelcased CSS property name, for example:\n *\n *   > hyphenateStyleName('backgroundColor')\n *   < \"background-color\"\n *   > hyphenateStyleName('MozTransition')\n *   < \"-moz-transition\"\n *   > hyphenateStyleName('msTransition')\n *   < \"-ms-transition\"\n *\n * As Modernizr suggests (http://modernizr.com/docs/#prefixed), an `ms` prefix\n * is converted to `-ms-`.\n *\n * @param {string} string\n * @return {string}\n */\nexport default function hyphenateStyleName(string: string): string {\n return uppercaseCheck.test(string)\n ? string\n   .replace(uppercasePattern, prefixAndLowerCase)\n   .replace(msPattern, '-ms-')\n : string;\n}\n","// @flow\nimport unitless from '@emotion/unitless';\n\n// Taken from
 https://github.com/facebook/react/blob/b87aabdfe1b7461e7331abb3601d9e6bb27544bc/packages/react-dom/src/shared/dangerousStyleValue.js\nexport default function addUnitIfNeeded(name: string, value: any): any {\n // https://github.com/amilajack/eslint-plugin-flowtype-errors/issues/133\n // $FlowFixMe\n if (value == null || typeof value === 'boolean' || value === '') {\n   return '';\n }\n\n if (typeof value === 'number' && value !== 0 && !(name in unitless) && !name.startsWith('--')) {\n   return `${value}px`; // Presumes implicit 'px' suffix for unitless numbers except for CSS variables\n }\n\n return String(value).trim();\n}\n","// @flow\nimport { isElement } from 'react-is';\nimport getComponentName from './getComponentName';\nimport isFunction from './isFunction';\nimport isStatelessFunction from './isStatelessFunction';\nimport isPlainObject from './isPlainObject';\nimport isStyledComponent from './isStyledComponent';\nimport Keyframes from '../models/Keyframes';\nimport hyphenate
 from './hyphenateStyleName';\nimport addUnitIfNeeded from './addUnitIfNeeded';\nimport { type Stringifier } from '../types';\n\n/**\n * It's falsish not falsy because 0 is allowed.\n */\nconst isFalsish = chunk => chunk === undefined || chunk === null || chunk === false || chunk === '';\n\nexport const objToCssArray = (obj: Object, prevKey?: string): Array<string | Function> => {\n const rules = [];\n\n for (const key in obj) {\n   if

(!obj.hasOwnProperty(key) || isFalsish(obj[key])) continue;\n\n if ((Array.isArray(obj[key]) && obj[key].isCss) || isFunction(obj[key])) {\n rules.push(`${hyphenate(key)}:`, obj[key], ';');\n } else if (isPlainObject(obj[key])) {\n rules.push(...objToCssArray(obj[key], key));\n } else {\n rules.push(`${hyphenate(key)}: ${addUnitIfNeeded(key, obj[key])};`);\n }\n }\n\n return prevKey ? [`${prevKey} {`, ...rules, '}'] : rules;\n};\n\nexport default function flatten(\n chunk: any,\n executionContext: ?Object,\n styleSheet: ?Object,\n stylisInstance: ?Stringifier\n): any {\n if (Array.isArray(chunk)) {\n const ruleSet = [];\n\n for (let i = 0, len = chunk.length, result; i < len; i += 1) {\n result = flatten(chunk[i], executionContext, styleSheet, stylisInstance);\n\n if (result === '') continue;\n else if (Array.isArray(result)) ruleSet.push(...result);\n else ruleSet.push(result);\n }\n\n return ruleSet;\n }\n\n if (isFalsish(chunk)) {\n return '';\n }\n\n /* Handle other components */\n if (isStyledComponent(chunk)) {\n return `.${chunk.styledComponentId}`;\n }\n\n /* Either execute or defer the function */\n if (isFunction(chunk)) {\n if (isStatelessFunction(chunk) && executionContext) {\n const result = chunk(executionContext);\n\n if (process.env.NODE_ENV !== 'production' && isElement(result)) {\n // eslint-disable-next-line no-console\n console.warn(\n `${getComponentName(\n chunk\n )} is not a styled component and cannot be referred to via component selector. See https://www.styled-components.com/docs/advanced#referring-to-other-components for more details.`\n);\n }\n\n return flatten(result, executionContext, styleSheet, stylisInstance);\n } else return chunk;\n }\n\n if (chunk instanceof Keyframes) {\n if (styleSheet) {\n chunk.inject(styleSheet, stylisInstance);\n return chunk.getName(stylisInstance);\n } else return chunk;\n }\n\n /* Handle objects */\n return isPlainObject(chunk) ? objToCssArray(chunk) : chunk.toString();\n}\n","// @flow\nconst printed = {};\n\nexport default function warnOnce(message) {\n if (printed[message]) return;\n printed[message] = true;\n\n if (typeof console !== 'undefined' && console.warn) console.warn(message);\n}\n","// @flow\nconst SINGLE_QUOTE = \"'\".charCodeAt(0);\nconst DOUBLE_QUOTE = '\"'.charCodeAt(0);\nconst BACKSLASH = '\\'.charCodeAt(0);\nconst SLASH = '/'.charCodeAt(0);\nconst NEWLINE = '\n'.charCodeAt(0);\nconst SPACE = ' '.charCodeAt(0);\nconst FEED = '\f'.charCodeAt(0);\nconst TAB = '\t'.charCodeAt(0);\nconst CR = '\r'.charCodeAt(0);\nconst OPEN_SQUARE = '['.charCodeAt(0);\nconst CLOSE_SQUARE = ']'.charCodeAt(0);\nconst OPEN_PARENTHESES = '('.charCodeAt(0);\nconst CLOSE_PARENTHESES = ')'.charCodeAt(0);\nconst OPEN_CURLY = '{'.charCodeAt(0);\nconst CLOSE_CURLY = '}'.charCodeAt(0);\nconst SEMICOLON = ';'.charCodeAt(0);\nconst ASTERISK = '*'.charCodeAt(0);\nconst COLON = ':'.charCodeAt(0);\nconst AT = '@'.charCodeAt(0);\n\nconst RE_AT_END = /[\n\t\r\f\{\(\)'"\\;/\[\]#]/g;\nconst RE_WORD_END = /[\n\t\r\f\(\)\{\}:;@!'"\\\]#]|\/(?=*)/g;\nconst RE_BAD_BRACKET = /.[\n\r\f\(]/;\n\nexport default function tokenize(input, options = {}) {\n const tokens = [];\n const css = input.css.valueOf();\n\n const ignore = options.ignoreErrors;\n\n let code,\n next,\n quote,\n lines,\n last,\n content,\n escape,\n nextLine,\n nextOffset,\n escaped,\n escapePos,\n prev,\n n;\n\n const length = css.length;\n let offset = -1;\n let line = 1;\n let pos = 0;\n\n function unclosed(what) {\n throw input.error(`Unclosed ${what}`, line, pos - offset);\n }\n\n while (pos < length) {\n code = css.charCodeAt(pos);\n\n if (code === NEWLINE || code === FEED || (code === CR && css.charCodeAt(pos + 1) !== NEWLINE)) {\n offset = pos;\n line += 1;\n }\n\n switch (code) {\n case NEWLINE:\n case SPACE:\n case TAB:\n case CR:\n case FEED:\n next = pos;\n do {\n next += 1;\n code = css.charCodeAt(next);\n if (code === NEWLINE) {\n offset = next;\n line += 1;\n }\n } while (\n code === SPACE ||\n code === NEWLINE ||\n code === TAB ||\n code === CR ||\n code === FEED\n);\n\n tokens.push(['space', css.slice(pos, next)]);\n pos = next - 1;\n break;\n\n case OPEN_SQUARE:\n tokens.push(['[', '[', line, pos - offset]);\n break;\n\n case CLOSE_SQUARE:\n tokens.push([']', ']', line, pos - offset]);\n break;\n\n case OPEN_CURLY:\n tokens.push(['{', '{', line, pos - offset]);\n break;\n\n case CLOSE_CURLY:\n tokens.push(['}', '}', line, pos - offset]);\n break;\n\n case COLON:\n tokens.push([':', ':', line, pos - offset]);\n break;\n\n case SEMICOLON:\n tokens.push([';', ';', line, pos - offset]);\n break;\n\n

```
case OPEN_PARENTHESES:\n prev = tokens.length ? tokens[tokens.length - 1][1] : '';\n n = css.charCodeAt(pos + 1);\n if (\n prev === 'url' &&\n n !== SINGLE_QUOTE &&\n n !== DOUBLE_QUOTE &&\n n !== SPACE &&\n n !== NEWLINE &&\n n !== TAB &&\n n !== FEED &&\n n !== CR\n ) {\n next = pos;\n do {\n escaped = false;\n next = css.indexOf(')', next + 1);\n if (next === -1) {\n if (ignore) {\n next = pos;\n break;\n } else {\n unclosed('bracket');\n }\n }\n escapePos = next;\n while (css.charCodeAt(escapePos - 1) === BACKSLASH) {\n escapePos -= 1;\n escaped = !escaped;\n }\n } while (escaped);\n\n tokens.push([\n 'brackets',\n css.slice(pos, next + 1),\n line,\n pos - offset,\n line,\n next - offset,\n ]);\n pos = next;\n } else {\n next = css.indexOf(')', pos + 1);\n content = css.slice(pos, next + 1);\n\n if (next === -1 || RE_BAD_BRACKET.test(content)) {\n tokens.push(['(', '(', line, pos - offset]);\n } else {\n tokens.push(['brackets', content, line, pos - offset, line, next - offset]);\n pos = next;\n }\n }\n\n break;\n\n case CLOSE_PARENTHESES:\n tokens.push([')', ')', line, pos - offset]);\n break;\n\n case SINGLE_QUOTE:\n case DOUBLE_QUOTE:\n quote = code === SINGLE_QUOTE ? \"'\" : '\"';\n next = pos;\n do {\n escaped = false;\n next = css.indexOf(quote, next + 1);\n if (next === -1) {\n if (ignore) {\n next = pos + 1;\n break;\n } else {\n unclosed('quote');\n }\n }\n escapePos = next;\n while (css.charCodeAt(escapePos - 1) === BACKSLASH) {\n escapePos -= 1;\n escaped = !escaped;\n }\n } while (escaped);\n\n content = css.slice(pos, next + 1);\n lines = content.split('\\n');\n last = lines.length - 1;\n\n if (last > 0) {\n nextLine = line + last;\n nextOffset = next - lines[last].length;\n } else {\n nextLine = line;\n nextOffset = offset;\n }\n\n tokens.push([\n 'string',\n css.slice(pos, next + 1),\n line,\n pos - offset,\n nextLine,\n next - nextOffset,\n ]);\n\n offset = nextOffset;\n line = nextLine;\n pos = next;\n break;\n\n case AT:\n RE_AT_END.lastIndex = pos + 1;\n RE_AT_END.test(css);\n if (RE_AT_END.lastIndex === 0) {\n next = css.length - 1;\n } else {\n next = RE_AT_END.lastIndex - 2;\n }\n tokens.push(['at-word', css.slice(pos, next + 1), line, pos - offset, line, next - offset]);\n pos = next;\n break;\n\n case BACKSLASH:\n next = pos;\n escape = true;\n while (css.charCodeAt(next + 1) === BACKSLASH) {\n next += 1;\n escape = !escape;\n }\n code = css.charCodeAt(next + 1);\n if (\n escape &&\n (code !== SLASH &&\n code !== SPACE &&\n code !== NEWLINE &&\n code !== TAB &&\n code !== CR &&\n code !== FEED)\n ) {\n next += 1;\n }\n tokens.push(['word', css.slice(pos, next + 1), line, pos - offset, line, next - offset]);\n pos = next;\n break;\n\n default:\n if (code === SLASH && css.charCodeAt(pos + 1) === ASTERISK) {\n next = css.indexOf('*/', pos + 2) + 1;\n if (next === 0) {\n if (ignore) {\n next = css.length;\n } else {\n unclosed('comment');\n }\n }\n\n content = css.slice(pos, next + 1);\n lines = content.split('\\n');\n last = lines.length - 1;\n\n if (last > 0) {\n nextLine = line + last;\n nextOffset = next - lines[last].length;\n } else {\n nextLine = line;\n nextOffset = offset;\n }\n\n tokens.push(['comment', content, line, pos - offset, nextLine, next - nextOffset]);\n\n offset = nextOffset;\n line = nextLine;\n pos = next;\n } else {\n RE_WORD_END.lastIndex = pos + 1;\n RE_WORD_END.test(css);\n if (RE_WORD_END.lastIndex === 0) {\n next = css.length - 1;\n } else {\n next = RE_WORD_END.lastIndex - 2;\n }\n\n tokens.push(['word', css.slice(pos, next + 1), line, pos - offset, line, next - offset]);\n pos = next;\n }\n\n break;\n }\n\n pos++;\n }\n\n return tokens;\n}\n","// @flow\nimport tokenize from './tokenize';\nimport Input from './input';\n\nconst HIGHLIGHT_THEME = {\n brackets: [36, 39], // cyan\n string: [31, 39], // red\n 'at-word': [31, 39], // red\n comment: [90, 39], // gray\n '{': [32, 39], // green\n '}': [32, 39], // green\n ':': [1, 22], // bold\n ';': [1, 22], // bold\n '(': [1, 22], // bold\n ')': [1, 22], // bold\n};\n\nfunction code(color) {\n return `\\u001b[${color}m`;\n}\n\nfunction
```

terminalHighlight(css) {\n const tokens = tokenize(new Input(css), { ignoreErrors: true });\n const result = [];\n tokens.forEach(token => {\n   const color = HIGHLIGHT_THEME[token[0]];\n   if (color) {\n   result.push(\n token[1]\n   .split(/\\r?\\n/)\n   .map(i => code(color[0]) + i + code(color[1]))\n   .join('\\n')\n   );\n } else {\n   result.push(token[1]);\n   }\n });\n return result.join('');\n}\n\nexport default terminalHighlight;\n","// @flow\nimport supportsColor from 'supports-color';\n\nimport terminalHighlight from './terminal-highlight';\nimport warnOnce from './warn-once';\n\n/**\n * The CSS parser throws this error for broken CSS.\n *\n * Custom parsers can throw this error
 for broken custom syntax using\n * the {@link Node#error} method.\n *\n * PostCSS will use the input source map to detect the original error location.\n * If you wrote a Sass file, compiled it to CSS and then parsed it with PostCSS,\n * PostCSS will show the original position in the Sass file.\n *\n * If you need the position in the PostCSS input\n * (e.g., to debug the previous compiler), use `error.input.file`.\n *\n * @example\n * // Catching and checking syntax error\n * try {\n *   postcss.parse('a{')\n * } catch (error) {\n *   if (error.name === 'CssSyntaxError') {\n *   error //=> CssSyntaxError\n *   }\n * }\n *\n * @example\n * // Raising error from plugin\n * throw node.error('Unknown variable', { plugin: 'postcss-vars' });\n */\nclass CssSyntaxError {\n /**\n   * @param {string} message - error message\n   * @param {number} [line]   - source line of the error\n   * @param {number} [column] - source column of the error\n   * @param {string} [source] - source code
 of the broken file\n   * @param {string} [file]   - absolute path to the broken file\n   * @param {string} [plugin] - PostCSS plugin name, if error came from plugin\n   */\n constructor(message, line, column, source, file, plugin) {\n   /**\n   * @member {string} - Always equal to `'CssSyntaxError'`. You should\n   *   always check error type\n   *   by `error.name === 'CssSyntaxError'` instead of\n   *   `error instanceof CssSyntaxError`, because\n   *   npm could have several PostCSS versions.\n   *\n   * @example\n   * if (error.name === 'CssSyntaxError') {\n   *   error //=> CssSyntaxError\n   * }\n   */\n   this.name = 'CssSyntaxError';\n   /**\n   * @member {string} - Error message.\n   *\n   * @example\n   * error.message //=> 'Unclosed block'\n   */\n   this.reason = message;\n\n   if (file) {\n   /**\n   * @member {string} - Absolute path to the broken file.\n
     *\n   * @example\n   * error.file   //=> 'a.sass'\n   * error.input.file //=> 'a.css'\n   */\n   this.file = file;\n   }\n   if (source) {\n   /**\n   * @member {string} - Source code of the broken file.\n   *\n   * @example\n   * error.source   //=> 'a { b {} }'\n   * error.input.column //=> 'a b { }'\n   */\n   this.source = source;\n   }\n   if (plugin) {\n   /**\n   * @member {string} - Plugin name, if error came from plugin.\n   *\n   * @example\n   * error.plugin //=> 'postcss-vars'\n   */\n   this.plugin = plugin;\n   }\n   if (typeof line !== 'undefined' && typeof column !== 'undefined') {\n   /**\n   * @member {number} - Source line of the error.\n   *\n   * @example\n   * error.line   //=> 2\n   * error.input.line //=> 4\n   */\n   this.line = line;\n   /**\n   * @member {number} - Source column of the error.\n   *\n   * @example\n
       * error.column   //=> 1\n   * error.input.column //=> 4\n   */\n   this.column = column;\n   }\n\n   this.setMessage();\n\n   if (Error.captureStackTrace) {\n   Error.captureStackTrace(this, CssSyntaxError);\n   }\n }\n\n setMessage() {\n   /**\n   * @member {string} - Full error text in the GNU error format\n   *   with plugin, file, line and column.\n   *\n   * @example\n   * error.message //=> 'a.css:1:1: Unclosed block'\n   */\n   this.message = this.plugin ? `${this.plugin}: ` : '';\n   this.message += this.file ? this.file : '<css input>';\n   if (typeof this.line !== 'undefined') {\n   this.message += `:${this.line}:${this.column}`;\n   }\n   this.message += `: ${this.reason}`;\n }\n\n /**\n   * Returns a few lines of CSS source that caused the error.\n   *\n   * If the CSS has an input source map without `sourceContent`,\n   * this method will return an empty string.\n   *\n   * @param {boolean} [color] whether arrow
 will be colored red by terminal\n   *   color codes. By default, PostCSS will detect\n   *
 color support by `process.stdout.isTTY`\n   *   and `process.env.NODE_DISABLE_COLORS`.\n   *\n   * @example\n   * error.showSourceCode() //=> \" 4 | }\n   *   //   5 | a {\n   *   // > 6 | bad\n   *   // | ^\n   *   //   7 | }\n   *   //   8 | b {\"\n   *\n   * @return {string} few lines of CSS source that caused the error\n   */\n showSourceCode(color) {\n   if (!this.source) return '';\n\n   let css = this.source;\n   if (typeof color === 'undefined') color = supportsColor;\n   if

```
(color) css = terminalHighlight(css);\n\n    const lines = css.split(/\\r?\\n/);\n    const start = Math.max(this.line - 3,
0);\n    const end = Math.min(this.line + 2, lines.length);\n\n    const maxWidth = String(end).length;\n\n
    return lines\n      .slice(start, end)\n      .map((line, index) => {\n        const number = start + 1 + index;\n        const
padded = ` ${number}`.slice(-maxWidth);\n        const gutter = ` ${padded} | `;\n        if (number === this.line) {\n
     const spacing =\n            gutter.replace(/\\d/g, ' ') + line.slice(0, this.column - 1).replace(/[^\\t]/g, ' ');\n
return `>${gutter}${line}\\n ${spacing}^`;\n        } else {\n          return ` ${gutter}${line}`;\n        }\n      })\n
.join('\\n');\n  }\n\n  /**\n   * Returns error position, message and source code of the broken part.\n   *\n   *
@example\n   * error.toString() //=> \"CssSyntaxError: app.css:1:1: Unclosed block\n   *                //    > 1 | a {\n
*                //        | ^\"\n   *\n   * @return {string} error position, message and source code\n   */\n  toString() {\n
let code = this.showSourceCode();\n    if (code) {\n      code = `\\n\\n${code}\\n`;\n    }\n
    return `${this.name}: ${this.message}${code}`;\n  }\n\n  get generated() {\n
warnOnce('CssSyntaxError#generated is deprecated. Use input instead.');\n    return this.input;\n  }\n\n  /**\n   *
@memberof CssSyntaxError#\n   * @member {Input} input - Input object with PostCSS internal information\n   *
about input file. If input has source map\n   *                 from previous tool, PostCSS will use
origin\n   *                 (for example, Sass) source. You can use this\n   *                 object to get PostCSS
input source.\n   *\n   * @example\n   * error.input.file //=> 'a.css'\n   * error.file       //=> 'a.sass'\n   */\n}\n\nexport
default CssSyntaxError;\n","// @flow\n/* eslint-disable valid-jsdoc */\n\nconst defaultRaw = {\n  colon: ': ',\n
indent: '    ',\n  beforeDecl: '\\n',\n  beforeRule: '\\n',\n  beforeOpen: ' ',\n  beforeClose: '\\n',\n  beforeComment:
'\\n',\n  after: '\\n',\n  emptyBody: '',\n  commentLeft: ' ',\n
  commentRight: ' ',\n};\n\nfunction capitalize(str) {\n  return str[0].toUpperCase() + str.slice(1);\n}\n\nclass
Stringifier {\n  constructor(builder) {\n    this.builder = builder;\n  }\n\n  stringify(node, semicolon) {\n
this[node.type](node, semicolon);\n  }\n\n  root(node) {\n    this.body(node);\n    if (node.raws.after)
this.builder(node.raws.after);\n  }\n\n  comment(node) {\n    const left = this.raw(node, 'left', 'commentLeft');\n
const right = this.raw(node, 'right', 'commentRight');\n    this.builder(`/*${left}${node.text}${right}*/`, node);\n
}\n\n  decl(node, semicolon) {\n    const between = this.raw(node, 'between', 'colon');\n    let string = node.prop +
between + this.rawValue(node, 'value');\n\n    if (node.important) {\n      string += node.raws.important || '
!important';\n    }\n\n    if (semicolon) string += ';';\n    this.builder(string, node);\n  }\n\n  rule(node) {\n
this.block(node, this.rawValue(node, 'selector'));\n  }\n\n  atrule(node, semicolon)
 {\n    let name = `@${node.name}`;\n    const params = node.params ? this.rawValue(node, 'params') : '';\n\n    if
(typeof node.raws.afterName !== 'undefined') {\n      name += node.raws.afterName;\n    } else if (params) {\n
name += ' ';\n    }\n\n    if (node.nodes) {\n      this.block(node, name + params);\n    } else {\n      const end =
(node.raws.between || '') + (semicolon ? ';' : '');\n      this.builder(name + params + end, node);\n    }\n  }\n\n
body(node) {\n    let last = node.nodes.length - 1;\n    while (last > 0) {\n      if (node.nodes[last].type !== 'comment')
break;\n      last -= 1;\n    }\n\n    const semicolon = this.raw(node, 'semicolon');\n    for (let i = 0; i <
node.nodes.length; i++) {\n      const child = node.nodes[i];\n      const before = this.raw(child, 'before');\n      if
(before) this.builder(before);\n      this.stringify(child, last !== i || semicolon);\n    }\n  }\n\n  block(node, start) {\n
const between = this.raw(node, 'between', 'beforeOpen');\n
    this.builder(`${start + between}{`, node, 'start');\n\n    let after;\n    if (node.nodes && node.nodes.length) {\n
this.body(node);\n      after = this.raw(node, 'after');\n    } else {\n      after = this.raw(node, 'after', 'emptyBody');\n
}\n\n    if (after) this.builder(after);\n    this.builder('}', node, 'end');\n  }\n\n  raw(node, own, detect) {\n    let value;\n
  if (!detect) detect = own;\n\n    // Already had\n    if (own) {\n      value = node.raws[own];\n      if (typeof value
!== 'undefined') return value;\n    }\n\n    const parent = node.parent;\n\n    // Hack for first rule in CSS\n    if (detect
=== 'before') {\n      if (!parent || (parent.type === 'root' && parent.first === node)) {\n        return '';\n      }\n    }\n\n
  // Floating child without parent\n    if (!parent) return defaultRaw[detect];\n\n    // Detect style by other nodes\n
const root = node.root();\n    if (!root.rawCache) root.rawCache = {};\n    if (typeof root.rawCache[detect]
 !== 'undefined') {\n      return root.rawCache[detect];\n    }\n\n    if (detect === 'before' || detect === 'after') {\n
return this.beforeAfter(node, detect);\n    } else {\n      const method = `raw${capitalize(detect)}`;\n      if
(this[method]) {\n        value = this[method](root, node);\n      } else {\n        root.walk(i => {\n          value =
```

i.raws[own];\n if (typeof value !== 'undefined') return false;\n });\n }\n }\n\n if (typeof value === 'undefined') value = defaultRaw[detect];\n\n root.rawCache[detect] = value;\n return value;\n }\n\n rawSemicolon(root) {\n let value;\n root.walk(i => {\n if (i.nodes && i.nodes.length && i.last.type === 'decl') {\n value = i.raws.semicolon;\n if (typeof value !== 'undefined') return false;\n }\n });\n return value;\n }\n\n rawEmptyBody(root) {\n let value;\n root.walk(i => {\n if (i.nodes && i.nodes.length === 0) {\n value = i.raws.after;\n if (typeof value !== 'undefined') return false;\n }\n });\n return value;\n }\n\n rawIndent(root) {\n if (root.raws.indent) return root.raws.indent;\n let value;\n root.walk(i => {\n const p = i.parent;\n if (p && p !== root && p.parent && p.parent === root) {\n if (typeof i.raws.before !== 'undefined') {\n const parts = i.raws.before.split('\\n');\n value = parts[parts.length - 1];\n value = value.replace(/[^\\s]/g, '');\n return false;\n }\n }\n });\n return value;\n }\n\n rawBeforeComment(root, node) {\n let value;\n root.walkComments(i => {\n if (typeof i.raws.before !== 'undefined') {\n value = i.raws.before;\n if (value.indexOf('\\n') !== -1) {\n value = value.replace(/[^\\n]+$/, '');\n }\n return false;\n }\n });\n if (typeof value === 'undefined') {\n value = this.raw(node, null, 'beforeDecl');\n }\n return value;\n }\n\n rawBeforeDecl(root, node) {\n let value;\n root.walkDecls(i => {\n if (typeof i.raws.before !== 'undefined') {\n value = i.raws.before;\n if (value.indexOf('\\n') !== -1) {\n value = value.replace(/[^\\n]+$/, '');\n }\n return false;\n }\n });\n if (typeof value === 'undefined') {\n value = this.raw(node, null, 'beforeRule');\n }\n return value;\n }\n\n rawBeforeRule(root) {\n let value;\n root.walk(i => {\n if (i.nodes && (i.parent !== root || root.first !== i)) {\n if (typeof i.raws.before !== 'undefined') {\n value = i.raws.before;\n if (value.indexOf('\\n') !== -1) {\n value = value.replace(/[^\\n]+$/, '');\n }\n return false;\n }\n }\n });\n return value;\n }\n\n rawBeforeClose(root) {\n let value;\n root.walk(i => {\n if (i.nodes && i.nodes.length > 0) {\n if (typeof i.raws.after !== 'undefined') {\n value = i.raws.after;\n if (value.indexOf('\\n') !== -1) {\n value = value.replace(/[^\\n]+$/, '');\n }\n return false;\n }\n }\n });\n return value;\n }\n\n rawBeforeOpen(root) {\n let value;\n root.walk(i => {\n if (i.type !== 'decl') {\n value = i.raws.between;\n if (typeof value !== 'undefined') return false;\n }\n });\n return value;\n }\n\n rawColon(root) {\n let value;\n root.walkDecls(i => {\n if (typeof i.raws.between !== 'undefined') {\n value = i.raws.between.replace(/[^\\s:]/g, '');\n return false;\n }\n });\n return value;\n }\n\n beforeAfter(node, detect) {\n let value;\n if (node.type === 'decl') {\n value = this.raw(node, null, 'beforeDecl');\n } else if (node.type === 'comment') {\n value = this.raw(node, null, 'beforeComment');\n } else if (detect === 'before') {\n value = this.raw(node, null, 'beforeRule');\n } else {\n value = this.raw(node, null, 'beforeClose');\n }\n\n let buf = node.parent;\n let depth = 0;\n while (buf && buf.type !== 'root') {\n depth += 1;\n buf = buf.parent;\n }\n\n if (value.indexOf('\\n') !== -1) {\n const indent = this.raw(node, null, 'indent');\n if (indent.length) {\n for (let step = 0; step < depth; step++) value += indent;\n }\n }\n\n return value;\n }\n\n rawValue(node, prop) {\n const value = node[prop];\n const raw = node.raws[prop];\n if (raw && raw.value === value) {\n return raw.raw;\n } else {\n return value;\n }\n }\n}\n\nexport default Stringifier;\n","// @flow\nimport Stringifier from './stringifier';\n\nexport default function stringify(node, builder) {\n const str = new Stringifier(builder);\n str.stringify(node);\n}\n","// @flow\nimport CssSyntaxError from './css-syntax-error';\nimport Stringifier from './stringifier';\nimport stringify from './stringify';\nimport warnOnce from './warn-once';\n\n/**\n * @typedef {object} position\n * @property {number} line - source line in file\n * @property {number} column - source column in file\n */\n\n/**\n * @typedef {object} source\n * @property {Input} input - {@link Input} with input file\n * @property {position} start - The starting position of the node’s source\n * @property {position} end - The ending position of the node’s source\n */\n\nconst cloneNode = function(obj, parent) {\n const cloned = new obj.constructor();\n\n for (const i in obj) {\n if (!obj.hasOwnProperty(i)) continue;\n let value = obj[i];\n const type = typeof value;\n\n if (i === 'parent' && type === 'object') {\n if (parent) cloned[i] = parent;\n } else if (i

=== 'source') {\n cloned[i] = value;\n } else if (value instanceof Array) {\n cloned[i] = value.map(j => cloneNode(j, cloned));\n } else if (i !== 'before' && i !== 'after' && i !== 'between' && i !== 'semicolon') {\n if (type === 'object' && value !== null) value = cloneNode(value);\n cloned[i] = value;\n }\n }\n\n return cloned;\n};\n\n/**\n * All node classes inherit the following common methods.\n *\n * @abstract\n */\nclass Node {\n /**\n * @param {object} [defaults] - value for node properties\n */\n constructor(defaults = {}) {\n this.raws = {};\n for (const name in defaults) {\n this[name] = defaults[name];\n }\n }\n\n /**\n * Returns a CssSyntaxError instance containing the original position\n * of the node in the source, showing line and column numbers and also\n * a small excerpt to facilitate debugging.\n *\n * If present, an input source map will be used to get the original position\n * of the source, even from a previous compilation step\n * (e.g., from Sass compilation).\n *\n * This method produces very useful error messages.\n *\n * @param {string} message - error description\n * @param {object} [opts] - options\n * @param {string} opts.plugin - plugin name that created this error.\n * PostCSS will set it automatically.\n * @param {string} opts.word - a word inside a node's string that should\n * be highlighted as the source of the error\n * @param {number} opts.index - an index inside a node's string that should\n * be highlighted as the source of the error\n *\n * @return {CssSyntaxError} error object to throw it\n *\n * @example\n * if (!variables[name]) {\n * throw decl.error('Unknown variable ' + name, { word: name });\n * // CssSyntaxError: postcss-vars:a.sass:4:3: Unknown variable $black\n * // color: $black\n * // a\n * // ^\n * // background: white\n * }\n */\n error(message, opts = {}) {\n if (this.source) {\n const pos = this.positionBy(opts);\n return this.source.input.error(message, pos.line, pos.column, opts);\n } else {\n return new CssSyntaxError(message);\n }\n }\n\n /**\n * This method is provided as a convenience wrapper for {@link Result#warn}.\n *\n * @param {Result} result - the {@link Result} instance\n * that will receive the warning\n * @param {string} text - warning message\n * @param {object} [opts] - options\n * @param {string} opts.plugin - plugin name that created this warning.\n * PostCSS will set it automatically.\n * @param {string} opts.word - a word inside a node's string that should\n * be highlighted as the source of the warning\n * @param {number} opts.index - an index inside a node's string that should\n * be highlighted as the source of the warning\n *\n * @return {Warning} created warning object\n *\n * @example\n * const plugin = postcss.plugin('postcss-deprecated',\n () => {\n * return (root, result) => {\n * root.walkDecls('bad', decl => {\n * decl.warn(result, 'Deprecated property bad');\n * });\n * };\n * });\n */\n warn(result, text, opts) {\n const data = { node: this };\n for (const i in opts) data[i] = opts[i];\n return result.warn(text, data);\n }\n\n /**\n * Removes the node from its parent and cleans the parent properties\n * from the node and its children.\n *\n * @example\n * if (decl.prop.match(/^-webkit-/)) {\n * decl.remove();\n * }\n *\n * @return {Node} node to make calls chain\n */\n remove() {\n if (this.parent) {\n this.parent.removeChild(this);\n }\n this.parent = undefined;\n return this;\n }\n\n /**\n * Returns a CSS string representing the node.\n *\n * @param {stringifier|syntax} [stringifier] - a syntax to use\n * in string generation\n *\n * @return {string} CSS string of this node\n *\n * @example\n * postcss.rule({ selector: 'a' }).toString() //=> \"a {}\"\n */\n toString(stringifier = stringify) {\n if (stringifier.stringify) stringifier = stringifier.stringify;\n let result = '';\n stringifier(this, i => {\n result += i;\n });\n return result;\n }\n\n /**\n * Returns a clone of the node.\n *\n * The resulting cloned node and its (cloned) children will have\n * a clean parent and code style properties.\n *\n * @param {object} [overrides] - new properties to override in the clone.\n *\n * @example\n * const cloned = decl.clone({ prop: '-moz-' + decl.prop });\n * cloned.raws.before //=> undefined\n * cloned.parent //=> undefined\n * cloned.toString() //=> -moz-transform: scale(0)\n *\n * @return {Node} clone of the node\n */\n clone(overrides = {}) {\n const cloned = cloneNode(this);\n for (const name in overrides) {\n cloned[name] = overrides[name];\n }\n return

```
cloned;\n  }\n\n  /**\n   * Shortcut to clone the node and insert the resulting cloned node\n   * before the current node.\n   *\n   * @param {object} [overrides] - new properties to override in the clone.\n   *\n   * @example\n   * decl.cloneBefore({ prop: '-moz-' + decl.prop });\n   *\n   * @return {Node} - new node\n   */\n  cloneBefore(overrides = {}) {\n    const cloned = this.clone(overrides);\n    this.parent.insertBefore(this, cloned);\n    return cloned;\n  }\n\n  /**\n   * Shortcut to clone the node and insert the resulting cloned node\n   * after the current node.\n   *\n   * @param {object} [overrides] - new properties to override in the clone.\n   *\n   * @return {Node} - new node\n   */\n  cloneAfter(overrides = {}) {\n    const cloned = this.clone(overrides);\n    this.parent.insertAfter(this, cloned);\n    return cloned;\n  }\n\n  /**\n   * Inserts node(s) before the current node and removes the current node.\n   *\n   * @param {...Node} nodes - node(s) to replace current one\n   *\n   * @example\n   * if ( atrule.name == 'mixin' ) {\n   *   atrule.replaceWith(mixinRules[atrule.params]);\n   * }\n   *\n   * @return {Node} current node to methods chain\n   */\n  replaceWith(...nodes) {\n    if (this.parent) {\n      nodes.forEach(node => {\n        this.parent.insertBefore(this, node);\n      });\n\n      this.remove();\n    }\n\n    return this;\n  }\n\n  /**\n   * Removes the node from its current parent and inserts it\n   * at the end of `newParent`.\n   *\n   * This will clean the `before` and `after` code {@link Node#raws} data\n   * from the node and replace them with the indentation style of `newParent`.\n   * It will also clean the `between` property\n   * if `newParent` is in another {@link Root}.\n   *\n   * @param {Container} newParent - container node where the current node\n   *                              will be moved\n   *\n   * @example\n   * atrule.moveTo(atrule.root());\n   *\n   * @return {Node} current node to methods chain\n   */\n  moveTo(newParent) {\n    this.cleanRaws(this.root() === newParent.root());\n    this.remove();\n    newParent.append(this);\n    return this;\n  }\n\n  /**\n   * Removes the node from its current parent and inserts it into\n   * a new parent before `otherNode`.\n   *\n   * This will also clean the node's code style properties just as it would\n   * in {@link Node#moveTo}.\n   *\n   * @param {Node} otherNode - node that will be before current node\n   *\n   * @return {Node} current node to methods chain\n   */\n  moveBefore(otherNode) {\n    this.cleanRaws(this.root() === otherNode.root());\n    this.remove();\n    otherNode.parent.insertBefore(otherNode, this);\n    return this;\n  }\n\n  /**\n   * Removes the node from its current parent and inserts it into\n   * a new parent after `otherNode`.\n   *\n   * This will also clean the node's code style properties just as it would\n   * in {@link Node#moveTo}.\n   *\n   * @param {Node} otherNode - node that will be after current node\n   *\n   * @return {Node} current node to methods chain\n   */\n  moveAfter(otherNode) {\n    this.cleanRaws(this.root() === otherNode.root());\n    this.remove();\n    otherNode.parent.insertAfter(otherNode, this);\n    return this;\n  }\n\n  /**\n   * Returns the next child of the node's parent.\n   * Returns `undefined` if the current node is the last child.\n   *\n   * @return {Node|undefined} next node\n   *\n   * @example\n   * if ( comment.text === 'delete next' ) {\n   *   const next = comment.next();\n   *   if ( next ) {\n   *     next.remove();\n   *   }\n   * }\n   */\n  next() {\n    const index = this.parent.index(this);\n    return this.parent.nodes[index + 1];\n  }\n\n  /**\n   * Returns the previous child of the node's parent.\n   * Returns `undefined` if the current node is the first child.\n   *\n   * @return {Node|undefined} previous node\n   *\n   * @example\n   * const annotation = decl.prev();\n   * if ( annotation.type == 'comment' ) {\n   *   readAnnotation(annotation.text);\n   * }\n   */\n  prev() {\n    const index = this.parent.index(this);\n    return this.parent.nodes[index - 1];\n  }\n\n  toJSON() {\n    const fixed = {};\n\n    for (const name in this) {\n      if (!this.hasOwnProperty(name)) continue;\n      if (name === 'parent') continue;\n      const value = this[name];\n\n      if (value instanceof Array) {\n        fixed[name] = value.map(i => {\n          if (typeof i === 'object' && i.toJSON) {\n            return i.toJSON();\n          } else {\n            return i;\n          }\n        });\n      } else if (typeof value === 'object' && value.toJSON) {\n        fixed[name] = value.toJSON();\n      } else {\n        fixed[name] = value;\n      }\n    }\n\n    return fixed;\n  }\n\n  /**\n   * Returns a {@link Node#raws} value. If the node is missing\n   * the code style property (because the node was manually built or cloned),\n   * PostCSS will try to autodetect the code style property by looking\n   * at other nodes in the tree.\n   *\n   * @param {string} prop          - name of code style property\n   * @param {string} [defaultType] - name of default value, it can be missed\n   *                               if the value is the same as prop\n   *\n   * @example\n   * const root = postcss.parse('a { background: white }');\n   * root.nodes[0].append({ prop: 'color',
```

```
value: 'black' });\n   * root.nodes[0].nodes[1].raws.before   //=> undefined\n   * root.nodes[0].nodes[1].raw('before')
//=> ' '\n   *\n   * @return {string} code style value\n   */\n  raw(prop, defaultType) {\n    const str = new
Stringifier();\n    return str.raw(this, prop, defaultType);\n  }\n\n  /**\n   * Finds the Root instance of the node's
tree.\n   *\n   * @example\n   * root.nodes[0].nodes[0].root() === root\n   *\n   * @return {Root} root parent\n   */\n
root() {\n    let result = this;\n    while (result.parent) result = result.parent;\n    return result;\n  }\n\n
cleanRaws(keepBetween) {\n    delete this.raws.before;\n
    delete this.raws.after;\n    if (!keepBetween) delete this.raws.between;\n  }\n\n  positionInside(index) {\n    const
string = this.toString();\n    let column = this.source.start.column;\n    let line = this.source.start.line;\n\n    for (let i =
0; i < index; i++) {\n      if (string[i] === '\\n') {\n        column = 1;\n        line += 1;\n      } else {\n        column +=
1;\n      }\n    }\n\n    return { line, column };\n  }\n\n  positionBy(opts) {\n    let pos = this.source.start;\n    if
(opts.index) {\n      pos = this.positionInside(opts.index);\n    } else if (opts.word) {\n      const index =
this.toString().indexOf(opts.word);\n      if (index !== -1) pos = this.positionInside(index);\n    }\n    return pos;\n
}\n\n  removeSelf() {\n    warnOnce('Node#removeSelf is deprecated. Use Node#remove.');\n    return
this.remove();\n  }\n\n  replace(nodes) {\n    warnOnce('Node#replace is deprecated. Use Node#replaceWith');\n
return this.replaceWith(nodes);\n  }\n\n  style(own,
 detect) {\n    warnOnce('Node#style() is deprecated. Use Node#raw()');\n    return this.raw(own, detect);\n  }\n\n
cleanStyles(keepBetween) {\n    warnOnce('Node#cleanStyles() is deprecated. Use Node#cleanRaws()');\n    return
this.cleanRaws(keepBetween);\n  }\n\n  get before() {\n    warnOnce('Node#before is deprecated. Use
Node#raws.before');\n    return this.raws.before;\n  }\n\n  set before(val) {\n    warnOnce('Node#before is
deprecated. Use Node#raws.before');\n    this.raws.before = val;\n  }\n\n  get between() {\n
warnOnce('Node#between is deprecated. Use Node#raws.between');\n    return this.raws.between;\n  }\n\n  set
between(val) {\n    warnOnce('Node#between is deprecated. Use Node#raws.between');\n    this.raws.between =
val;\n  }\n\n  /**\n   * @memberof Node#\n   * @member {string} type - String representing the node's type.\n   *
                Possible values are `root`, `atrule`, `rule`,\n   *                `decl`, or `comment`.\n   *\n   *
 @example\n   * postcss.decl({ prop: 'color', value: 'black' }).type //=> 'decl'\n   */\n\n  /**\n   * @memberof
Node#\n   * @member {Container} parent - the node's parent node.\n   *\n   * @example\n   * root.nodes[0].parent
== root;\n   */\n\n  /**\n   * @memberof Node#\n   * @member {source} source - the input source of the node\n
*\n   * The property is used in source map generation.\n   *\n   * If you create a node manually (e.g., with
`postcss.decl()`),\n   * that node will not have a `source` property and will be absent\n   * from the source map. For
this reason, the plugin developer should\n   * consider cloning nodes to create new ones (in which case the new
node's\n   * source will reference the original, cloned node) or setting\n   * the `source` property manually.\n   *\n   *
```js\n   * // Bad\n   * const prefixed = postcss.decl({\n   *   prop: '-moz-' + decl.prop,\n   *   value: decl.value\n   *
});\n   *\n   * // Good\n   * const prefixed = decl.clone({ prop: '-moz-' +
 decl.prop });\n   * ```\n   *\n   * ```js\n   * if ( atrule.name == 'add-link' ) {\n   *   const rule = postcss.rule({ selector:
'a', source: atrule.source });\n   *   atrule.parent.insertBefore(atrule, rule);\n   * }\n   * ```\n   *\n   * @example\n   *
decl.source.input.from //=> '/home/ai/a.sass'\n   * decl.source.start      //=> { line: 10, column: 2 }\n   *
decl.source.end        //=> { line: 10, column: 12 }\n   */\n\n  /**\n   * @memberof Node#\n   * @member {object}
raws - Information to generate byte-to-byte equal\n   *                node string as it was in the origin input.\n   *\n
 * Every parser saves its own properties,\n   * but the default CSS parser uses:\n   *\n   * * `before`: the space
symbols before the node. It also stores `*`\n   *   and `_` symbols before the declaration (IE hack).\n   * * `after`: the
space symbols after the last child of the node\n   *   to the end of the node.\n   * * `between`: the symbols between
the property and value\n   *   for
 declarations, selector and `{` for rules, or last parameter\n   *   and `{` for at-rules.\n   * * `semicolon`: contains true
if the last child has\n   *   an (optional) semicolon.\n   * * `afterName`: the space between the at-rule name and its
parameters.\n   * * `left`: the space symbols between `/*` and the comment's text.\n   * * `right`: the space symbols
between the comment's text\n   *   and <code>*/</code>.\n   * * `important`: the content of the important
statement,\n   *   if it is not just `!important`.\n   *\n   * PostCSS cleans selectors, declaration values and at-rule
parameters\n   * from comments and extra spaces, but it stores origin content in raws\n   * properties. As such, if you
```
```

don’t change a declaration’s value,\n * PostCSS will use the raw value with comments.\n *\n * @example\n * const root = postcss.parse('a {\\n color:black\\n}')\n * root.first.first.raws //=> { before: '\\n ', between: ':' }\n */\n}\n\nexport default Node;\n","// @flow\nimport warnOnce from './warn-once';\nimport Node from './node';\n\n/**\n * Represents a CSS declaration.\n *\n * @extends Node\n *\n * @example\n * const root = postcss.parse('a { color: black }');\n * const decl = root.first.first;\n * decl.type //=> 'decl'\n * decl.toString() //=> ' color: black'\n */\nclass Declaration extends Node {\n constructor(defaults) {\n super(defaults);\n this.type = 'decl';\n }\n\n get _value() {\n warnOnce('Node#_value was deprecated. Use Node#raws.value');\n return this.raws.value;\n }\n\n set _value(val) {\n warnOnce('Node#_value was deprecated. Use Node#raws.value');\n this.raws.value = val;\n }\n\n get _important() {\n warnOnce('Node#_important was deprecated. Use Node#raws.important');\n return this.raws.important;\n }\n\n set _important(val) {\n warnOnce('Node#_important was deprecated. Use Node#raws.important');\n this.raws.important = val;\n }\n\n /**\n * @memberof Declaration#\n * @member {string} prop - the declaration’s property name\n *\n * @example\n * const root = postcss.parse('a { color: black }');\n * const decl = root.first.first;\n * decl.prop //=> 'color'\n */\n\n /**\n * @memberof Declaration#\n * @member {string} value - the declaration’s value\n *\n * @example\n * const root = postcss.parse('a { color: black }');\n * const decl = root.first.first;\n * decl.value //=> 'black'\n */\n\n /**\n * @memberof Declaration#\n * @member {boolean} important - `true` if the declaration\n * has an !important annotation.\n *\n * @example\n * const root = postcss.parse('a { color: black !important; color: red }');\n * root.first.first.important //=> true\n * root.first.last.important //=> undefined\n */\n\n /**\n * @memberof Declaration#\n * @member {object} raws - Information to generate byte-to-byte equal\n * node string as it was in the origin input.\n *\n * Every parser saves its own properties,\n * but the default CSS parser uses:\n *\n * * `before`: the space symbols before the node. It also stores `*`\n * and `_` symbols before the declaration (IE hack).\n * * `between`: the symbols between the property and value\n * for declarations, selector and `{` for rules, or last parameter\n * and `{` for at-rules.\n * * `important`: the content of the important statement,\n * if it is not just `!important`.\n *\n * PostCSS cleans declaration from comments and extra spaces,\n * but it stores origin content in raws properties.\n * As such, if you don’t change a declaration’s value,\n * PostCSS will use the raw value with comments.\n *\n * @example\n * const root = postcss.parse('a {\\n color:black\\n}')\n * root.first.first.raws //=> { before: '\\n ', between: ':' }\n */\n}\n\nexport default Declaration;\n","// @flow\nimport warnOnce from './warn-once';\nimport Node from './node';\n\n/**\n * Represents a comment between declarations or statements (rule and at-rules).\n *\n * Comments inside selectors, at-rule parameters, or declaration values\n * will be stored in the `raws` properties explained above.\n *\n * @extends Node\n */\nclass Comment extends Node {\n constructor(defaults) {\n super(defaults);\n this.type = 'comment';\n }\n\n get left() {\n warnOnce('Comment#left was deprecated. Use Comment#raws.left');\n return this.raws.left;\n }\n\n set left(val) {\n warnOnce('Comment#left was deprecated. Use Comment#raws.left');\n this.raws.left = val;\n }\n\n get right() {\n warnOnce('Comment#right was deprecated. Use Comment#raws.right');\n return this.raws.right;\n }\n\n set right(val) {\n warnOnce('Comment#right was deprecated. Use Comment#raws.right');\n this.raws.right = val;\n }\n\n /**\n * @memberof Comment#\n * @member {string} text - the comment’s text\n */\n\n /**\n * @memberof Comment#\n * @member {object} raws - Information to generate byte-to-byte equal\n * node string as it was in the origin input.\n *\n * Every parser saves its own properties,\n * but the default CSS parser uses:\n *\n * * `before`: the space symbols before the node.\n * * `left`: the space symbols between `/*` and the comment’s text.\n * * `right`: the space symbols between the comment’s text.\n */\n}\n\nexport default Comment;\n","// @flow\nimport Declaration from './declaration';\nimport tokenizer from './tokenize';\nimport Comment from './comment';\nimport AtRule from './at-rule';\nimport Root from './root';\nimport Rule from './rule';\n\nexport default class Parser {\n constructor(input) {\n this.input = input;\n\n this.pos = 0;\n this.root = new Root();\n this.current = this.root;\n this.spaces = '';\n this.semicolon = false;\n\n this.root.source = { input, start: { line: 1, column: 1 } };\n }\n\n tokenize() {\n

```
this.tokens = tokenizer(this.input);\n  }\n\n  loop()
 {\n    let token;\n    while (this.pos < this.tokens.length) {\n      token = this.tokens[this.pos];\n\n      switch
(token[0]) {\n        case 'space':\n        case ';':\n          this.spaces += token[1];\n          break;\n\n        case '}':\n
this.end(token);\n          break;\n\n        case 'comment':\n          this.comment(token);\n          break;\n\n        case 'at-
word':\n          this.atrule(token);\n          break;\n\n        case '{':\n          this.emptyRule(token);\n          break;\n\n
default:\n          this.other();\n          break;\n      }\n\n      this.pos += 1;\n    }\n    this.endFile();\n  }\n\n
comment(token) {\n    const node = new Comment();\n    this.init(node, token[2], token[3]);\n    node.source.end = {
line: token[4], column: token[5] };\n\n    const text = token[1].slice(2, -2);\n    if (/^\\s*$/.test(text)) {\n      node.text
= '';\n      node.raws.left = text;\n      node.raws.right = '';\n    } else {\n      const match =
text.match(/^(\\s*)([^]*[^\\s])(\\s*)$/);\n
      node.text = match[2];\n      node.raws.left = match[1];\n      node.raws.right = match[3];\n    }\n  }\n\n
emptyRule(token) {\n    const node = new Rule();\n    this.init(node, token[2], token[3]);\n    node.selector = '';\n
node.raws.between = '';\n    this.current = node;\n  }\n\n  other() {\n    let token;\n    let end = false;\n    let type =
null;\n    let colon = false;\n    let bracket = null;\n    const brackets = [];\n\n    const start = this.pos;\n    while
(this.pos < this.tokens.length) {\n      token = this.tokens[this.pos];\n      type = token[0];\n\n      if (type === '(' || type
=== '[') {\n        if (!bracket) bracket = token;\n        brackets.push(type === '(' ? ')' : ']');\n      } else if
(brackets.length === 0) {\n        if (type === ';') {\n          if (colon) {\n            this.decl(this.tokens.slice(start,
this.pos + 1));\n            return;\n          } else {\n            break;\n          }\n        }
 else if (type === '{') {\n          this.rule(this.tokens.slice(start, this.pos + 1));\n          return;\n        } else if (type ===
'}') {\n          this.pos -= 1;\n          end = true;\n          break;\n        } else if (type === ':') {\n          colon = true;\n
}\n      } else if (type === brackets[brackets.length - 1]) {\n        brackets.pop();\n        if (brackets.length === 0)
bracket = null;\n      }\n\n      this.pos += 1;\n    }\n    if (this.pos === this.tokens.length) {\n      this.pos -= 1;\n
end = true;\n    }\n\n    if (brackets.length > 0) this.unclosedBracket(bracket);\n\n    if (end && colon) {\n      while
(this.pos > start) {\n        token = this.tokens[this.pos][0];\n        if (token !== 'space' && token !== 'comment')
break;\n        this.pos -= 1;\n      }\n      this.decl(this.tokens.slice(start, this.pos + 1));\n      return;\n    }\n\n
this.unknownWord(start);\n  }\n\n  rule(tokens) {\n    tokens.pop();\n\n    const node = new Rule();\n
    this.init(node, tokens[0][2], tokens[0][3]);\n\n    node.raws.between = this.spacesFromEnd(tokens);\n
this.raw(node, 'selector', tokens);\n    this.current = node;\n  }\n\n  decl(tokens) {\n    const node = new
Declaration();\n    this.init(node);\n\n    const last = tokens[tokens.length - 1];\n    if (last[0] === ';') {\n
this.semicolon = true;\n      tokens.pop();\n    }\n    if (last[4]) {\n      node.source.end = { line: last[4], column:
last[5] };\n    } else {\n      node.source.end = { line: last[2], column: last[3] };\n    }\n\n    while (tokens[0][0] !==
'word') {\n      node.raws.before += tokens.shift()[1];\n    }\n    node.source.start = { line: tokens[0][2], column:
tokens[0][3] };\n\n    node.prop = '';\n    while (tokens.length) {\n      const type = tokens[0][0];\n      if (type === ':' ||
type === 'space' || type === 'comment') {\n        break;\n      }\n      node.prop += tokens.shift()[1];\n    }\n\n
node.raws.between = '';\n\n    let token;\n    while
 (tokens.length) {\n      token = tokens.shift();\n\n      if (token[0] === ':') {\n        node.raws.between += token[1];\n
    break;\n      } else {\n        node.raws.between += token[1];\n      }\n    }\n\n    if (node.prop[0] === '_' ||
node.prop[0] === '*') {\n      node.raws.before += node.prop[0];\n      node.prop = node.prop.slice(1);\n    }\n
node.raws.between += this.spacesFromStart(tokens);\n    this.precheckMissedSemicolon(tokens);\n\n    for (let i =
tokens.length - 1; i > 0; i--) {\n      token = tokens[i];\n      if (token[1] === '!important') {\n        node.important =
true;\n        let string = this.stringFrom(tokens, i);\n        string = this.spacesFromEnd(tokens) + string;\n        if
(string !== ' !important') node.raws.important = string;\n        break;\n      } else if (token[1] === 'important') {\n
const cache = tokens.slice(0);\n        let str = '';\n        for (let j = i; j > 0; j--) {\n          const type = cache[j][0];\n
if (str.trim().indexOf('!')
 === 0 && type !== 'space') {\n            break;\n          }\n          str = cache.pop()[1] + str;\n        }\n        if
(str.trim().indexOf('!') === 0) {\n          node.important = true;\n          node.raws.important = str;\n          tokens =
cache;\n        }\n      }\n\n      if (token[0] !== 'space' && token[0] !== 'comment') {\n        break;\n      }\n    }\n\n
this.raw(node, 'value', tokens);\n\n    if (node.value.indexOf(':') !== -1) this.checkMissedSemicolon(tokens);\n  }\n\n
```

```
atrule(token) {\n    const node = new AtRule();\n    node.name = token[1].slice(1);\n    if (node.name === '') {\n this.unnamedAtrule(node, token);\n    }\n    this.init(node, token[2], token[3]);\n\n    let last = false;\n    let open = false;\n    const params = [];\n\n    this.pos += 1;\n    while (this.pos < this.tokens.length) {\n      token = this.tokens[this.pos];\n\n      if (token[0] === ';') {\n        node.source.end = { line: token[2], column: token[3] };\n        this.semicolon = true;\n        break;\n      } else if (token[0] === '{') {\n        open = true;\n        break;\n      } else if (token[0] === '}') {\n        this.end(token);\n        break;\n      } else {\n        params.push(token);\n      }\n\n      this.pos += 1;\n    }\n    if (this.pos === this.tokens.length) {\n      last = true;\n    }\n\n    node.raws.between = this.spacesFromEnd(params);\n    if (params.length) {\n      node.raws.afterName = this.spacesFromStart(params);\n      this.raw(node, 'params', params);\n      if (last) {\n        token = params[params.length - 1];\n        node.source.end = { line: token[4], column: token[5] };\n        this.spaces = node.raws.between;\n        node.raws.between = '';\n      }\n    } else {\n      node.raws.afterName = '';\n      node.params = '';\n    }\n\n    if (open) {\n      node.nodes = [];\n      this.current = node;\n    }\n  }\n\n  end(token) {\n    if (this.current.nodes && this.current.nodes.length) {\n      this.current.raws.semicolon = this.semicolon;\n    }\n    this.semicolon = false;\n\n    this.current.raws.after = (this.current.raws.after || '') + this.spaces;\n    this.spaces = '';\n\n    if (this.current.parent) {\n      this.current.source.end = { line: token[2], column: token[3] };\n      this.current = this.current.parent;\n    } else {\n      this.unexpectedClose(token);\n    }\n  }\n\n  endFile() {\n    if (this.current.parent) this.unclosedBlock();\n    if (this.current.nodes && this.current.nodes.length) {\n      this.current.raws.semicolon = this.semicolon;\n    }\n    this.current.raws.after = (this.current.raws.after || '') + this.spaces;\n  }\n\n  // Helpers\n\n  init(node, line, column) {\n    this.current.push(node);\n\n    node.source = { start: { line, column }, input: this.input };\n    node.raws.before = this.spaces;\n    this.spaces = '';\n    if (node.type !== 'comment') this.semicolon = false;\n  }\n\n  raw(node, prop, tokens) {\n    let token, type;\n    const length = tokens.length;\n    let value = '';\n    let clean = true;\n    for (let i = 0; i < length; i += 1) {\n      token = tokens[i];\n      type = token[0];\n      if (type === 'comment' || (type === 'space' && i === length - 1)) {\n        clean = false;\n      } else {\n        value += token[1];\n      }\n    }\n    if (!clean) {\n      const raw = tokens.reduce((all, i) => all + i[1], '');\n      node.raws[prop] = { value, raw };\n    }\n    node[prop] = value;\n  }\n\n  spacesFromEnd(tokens) {\n    let lastTokenType;\n    let spaces = '';\n    while (tokens.length) {\n      lastTokenType = tokens[tokens.length - 1][0];\n      if (lastTokenType !== 'space' && lastTokenType !== 'comment') break;\n      spaces = tokens.pop()[1] + spaces;\n    }\n    return spaces;\n  }\n\n  spacesFromStart(tokens) {\n    let next;\n    let spaces = '';\n    while (tokens.length) {\n      next = tokens[0][0];\n      if (next !== 'space' && next !== 'comment') break;\n      spaces += tokens.shift()[1];\n    }\n    return spaces;\n  }\n\n  stringFrom(tokens, from) {\n    let result = '';\n    for (let i = from; i < tokens.length; i++) {\n      result += tokens[i][1];\n    }\n    tokens.splice(from, tokens.length - from);\n    return result;\n  }\n\n  colon(tokens) {\n    let brackets = 0;\n    let token, type, prev;\n    for (let i = 0; i < tokens.length; i++) {\n      token = tokens[i];\n      type = token[0];\n\n      if (type === '(') {\n        brackets += 1;\n      } else if (type === ')') {\n        brackets -= 1;\n      } else if (brackets === 0 && type === ':') {\n        if (!prev) {\n          this.doubleColon(token);\n        } else if (prev[0] === 'word' && prev[1] === 'progid') {\n          continue;\n        } else {\n          return i;\n        }\n      }\n\n      prev = token;\n    }\n    return false;\n  }\n\n  // Errors\n\n  unclosedBracket(bracket) {\n    throw this.input.error('Unclosed bracket', bracket[2], bracket[3]);\n  }\n\n  unknownWord(start) {\n    const token = this.tokens[start];\n    throw this.input.error('Unknown word', token[2], token[3]);\n  }\n\n  unexpectedClose(token) {\n    throw this.input.error('Unexpected }', token[2], token[3]);\n  }\n\n  unclosedBlock() {\n    const pos = this.current.source.start;\n    throw this.input.error('Unclosed block', pos.line, pos.column);\n  }\n\n  doubleColon(token) {\n    throw this.input.error('Double colon', token[2], token[3]);\n  }\n\n  unnamedAtrule(node, token) {\n    throw this.input.error('At-rule without name', token[2], token[3]);\n  }\n\n  precheckMissedSemicolon(tokens) {\n    // Hook for Safe Parser\n    tokens;\n  }\n\n  checkMissedSemicolon(tokens) {\n    const colon = this.colon(tokens);\n    if (colon === false) return;\n\n    let founded = 0;\n    let token;\n    for (let j = colon - 1; j >= 0; j--) {\n      token = tokens[j];\n      if (token[0] !== 'space') {\n        founded += 1;\n        if (founded === 2) break;\n      }\n    }\n    throw this.input.error('Missed
```

semicolon', token[2], token[3]);\n }\n}\n","// @flow\nimport Parser from './parser';\nimport Input from './input';\n\nexport default function parse(css, opts) {\n if (opts && opts.safe) {\n throw new Error('Option safe was removed. ' + 'Use parser: require(\"postcss-safe-parser\")');\n }\n\n const input = new Input(css, opts);\n\n const parser = new Parser(input);\n try {\n parser.tokenize();\n parser.loop();\n } catch (e) {\n if (e.name === 'CssSyntaxError' && opts && opts.from) {\n if (/\\.scss$/i.test(opts.from)) {\n e.message +=\n '\\nYou tried to parse SCSS with ' +\n 'the standard CSS parser; ' +\n 'try again with the postcss-scss parser';\n } else if (/\\.less$/i.test(opts.from)) {\n e.message +=\n '\\nYou tried to parse Less with ' +\n 'the standard CSS parser; ' +\n 'try again with the postcss-less parser';\n }\n }\n throw e;\n }\n\n return parser.root;\n}\n","// @flow\nimport parse from './parse';\nimport Root from './root';\nimport Rule from './rule';\nimport AtRule from './at-rule';\nimport Declaration from './declaration';\nimport warnOnce from './warn-once';\nimport Comment from './comment';\nimport Node from './node';\n\nfunction cleanSource(nodes) {\n return nodes.map(i => {\n if (i.nodes) i.nodes = cleanSource(i.nodes);\n delete i.source;\n return i;\n });\n}\n\n/**\n * @callback childCondition\n * @param {Node} node - container child\n * @param {number} index - child index\n * @param {Node[]} nodes - all container children\n * @return {boolean}\n */\n\n/**\n * @callback childIterator\n * @param {Node} node - container child\n * @param {number} index - child index\n * @return {false|undefined} returning `false` will break iteration\n */\n\n/**\n * The {@link Root}, {@link AtRule}, and {@link Rule} container nodes\n * inherit some common methods to help work with their children.\n *\n * Note that all containers can store any content. If you write a rule inside\n * a rule, PostCSS will parse it.\n *\n * @extends Node\n * @abstract\n */\nclass Container extends Node {\n push(child) {\n child.parent = this;\n this.nodes.push(child);\n return this;\n }\n\n /**\n * Iterates through the container's immediate children,\n * calling `callback` for each child.\n *\n * Returning `false` in the callback will break iteration.\n *\n * This method only iterates through the container's immediate children.\n * If you need to recursively iterate through all the container's descendant\n * nodes, use {@link Container#walk}.\n *\n * Unlike the for `{}`-cycle or `Array#forEach` this iterator is safe\n * if you are mutating the array of child nodes during iteration.\n * PostCSS will adjust the current index to match the mutations.\n *\n * @param {childIterator} callback - iterator receives each node and index\n *\n * @return {false|undefined} returns `false` if iteration was broke\n *\n * @example\n * const root = postcss.parse('a { color: black; z-index: 1 }');\n * const rule = root.first;\n *\n * for (let decl of rule.nodes) {\n * decl.cloneBefore({ prop: '-webkit-' + decl.prop });\n * // Cycle will be infinite, because cloneBefore moves the current node\n * // to the next index\n * }\n *\n * rule.each(decl => {\n * decl.cloneBefore({ prop: '-webkit-' + decl.prop });\n * // Will be executed only for color and z-index\n * });\n */\n each(callback) {\n if (!this.lastEach) this.lastEach = 0;\n if (!this.indexes) this.indexes = {};\n\n this.lastEach += 1;\n const id = this.lastEach;\n this.indexes[id] = 0;\n\n if (!this.nodes) return undefined;\n\n let index, result;\n while (this.indexes[id] < this.nodes.length) {\n index = this.indexes[id];\n result = callback(this.nodes[index], index);\n if (result === false) break;\n\n this.indexes[id] += 1;\n }\n\n delete this.indexes[id];\n\n return result;\n }\n\n /**\n * Traverses the container's descendant nodes, calling callback\n * for each node.\n *\n * Like container.each(), this method is safe to use\n * if you are mutating arrays during iteration.\n *\n * If you only need to iterate through the container's immediate children,\n * use {@link Container#each}.\n *\n * @param {childIterator} callback - iterator receives each node and index\n *\n * @return {false|undefined} returns `false` if iteration was broke\n *\n * @example\n * root.walk(node => {\n * // Traverses all descendant nodes.\n * });\n */\n walk(callback) {\n return this.each((child, i) => {\n let result = callback(child, i);\n if (result !== false && child.walk) {\n result = child.walk(callback);\n }\n return result;\n });\n }\n\n /**\n * Traverses the container's descendant nodes, calling callback\n * for each declaration node.\n *\n * If you pass a filter, iteration will only happen over declarations\n * with matching properties.\n *\n * Like {@link Container#each}, this method is safe\n * to use if you are mutating arrays during iteration.\n *\n * @param {string|RegExp} [prop] - string or regular expression\n * to filter declarations by property

name\n * @param {childIterator} callback - iterator receives each node and index\n *\n * @return {false|undefined} returns `false` if iteration was broke\n *\n * @example\n * root.walkDecls(decl => {\n * checkPropertySupport(decl.prop);\n * });\n *\n * root.walkDecls('border-radius', decl => {\n * decl.remove();\n * });\n *\n * root.walkDecls(/^background/, decl => {\n * decl.value = takeFirstColorFromGradient(decl.value);\n * });\n */\n walkDecls(prop, callback) {\n if (!callback) {\n callback = prop;\n return this.walk((child, i) => {\n if (child.type === 'decl') {\n return callback(child, i);\n }\n });\n } else if (prop instanceof RegExp) {\n return this.walk((child, i) => {\n if (child.type === 'decl' && prop.test(child.prop)) {\n return callback(child, i);\n }\n });\n } else {\n return this.walk((child, i) => {\n if (child.type === 'decl' && child.prop === prop) {\n return callback(child, i);\n }\n });\n }\n }\n\n /**\n * Traverses the container’s descendant nodes, calling callback\n * for each rule node.\n *\n * If you pass a filter, iteration will only happen over rules\n * with matching selectors.\n *\n * Like {@link Container#each}, this method is safe\n * to use if you are mutating arrays during iteration.\n *\n * @param {string|RegExp} [selector] - string or regular expression\n * to filter rules by selector\n * @param {childIterator} callback - iterator receives each node and index\n *\n * @return {false|undefined} returns `false` if iteration was broke\n *\n * @example\n * const selectors = [];\n * root.walkRules(rule => {\n * selectors.push(rule.selector);\n * });\n * console.log(`Your CSS uses ${selectors.length} selectors`);\n */\n walkRules(selector, callback) {\n if (!callback) {\n callback = selector;\n\n return this.walk((child, i) => {\n if (child.type === 'rule') {\n return callback(child, i);\n }\n });\n } else if (selector instanceof RegExp) {\n return this.walk((child, i) => {\n if (child.type === 'rule' && selector.test(child.selector)) {\n return callback(child, i);\n }\n });\n } else {\n return this.walk((child, i) => {\n if (child.type === 'rule' && child.selector === selector) {\n return callback(child, i);\n }\n });\n }\n }\n\n /**\n * Traverses the container’s descendant nodes, calling callback\n * for each at-rule node.\n *\n * If you pass a filter, iteration will only happen over at-rules\n * that have matching names.\n *\n * Like {@link Container#each}, this method is safe\n * to use if you are mutating arrays during iteration.\n *\n * @param {string|RegExp} [name] - string or regular expression\n * to filter at-rules by name\n * @param {childIterator} callback - iterator receives each node and index\n *\n * @return {false|undefined} returns `false` if iteration was broke\n *\n * @example\n * root.walkAtRules(rule => {\n * if (isOld(rule.name)) rule.remove();\n * });\n *\n * let first = false;\n * root.walkAtRules('charset', rule => {\n * if (!first) {\n * first = true;\n * } else {\n * rule.remove();\n * }\n * });\n */\n walkAtRules(name, callback) {\n if (!callback) {\n callback = name;\n return this.walk((child, i) => {\n if (child.type === 'atrule') {\n return callback(child, i);\n }\n });\n } else if (name instanceof RegExp) {\n return this.walk((child, i) => {\n if (child.type === 'atrule' && name.test(child.name)) {\n return callback(child, i);\n }\n });\n } else {\n return this.walk((child, i) => {\n if (child.type === 'atrule' && child.name === name) {\n return callback(child, i);\n }\n });\n }\n }\n\n /**\n * Traverses the container’s descendant nodes, calling callback\n * for each comment node.\n *\n * Like {@link Container#each}, this method is safe\n * to use if you are mutating arrays during iteration.\n *\n * @param {childIterator} callback - iterator receives each node and index\n *\n * @return {false|undefined} returns `false` if iteration was broke\n *\n * @example\n * root.walkComments(comment => {\n * comment.remove();\n * });\n */\n walkComments(callback) {\n return this.walk((child,\n i) => {\n if (child.type === 'comment') {\n return callback(child, i);\n }\n });\n }\n\n /**\n * Inserts new nodes to the start of the container.\n *\n * @param {...(Node|object|string|Node[])} children - new nodes\n *\n * @return {Node} this node for methods chain\n *\n * @example\n * const decl1 = postcss.decl({ prop: 'color', value: 'black' });\n * const decl2 = postcss.decl({ prop: 'background-color', value: 'white' });\n * rule.append(decl1, decl2);\n *\n * root.append({ name: 'charset', params: '\"UTF-8\"' }); // at-rule\n * root.append({ selector: 'a' }); // rule\n * rule.append({ prop: 'color', value: 'black' }); //

declaration\n * rule.append({ text: 'Comment' }) // comment\n *\n * root.append('a {}');\n * root.first.append('color: black; z-index: 1');\n */\n append(...children) {\n children.forEach(child => {\n const nodes = this.normalize(child, this.last);\n
nodes.forEach(node => this.nodes.push(node));\n });\n return this;\n }\n\n /**\n * Inserts new nodes to the end of the container.\n *\n * @param {...(Node|object|string|Node[])} children - new nodes\n *\n * @return {Node} this node for methods chain\n *\n * @example\n * const decl1 = postcss.decl({ prop: 'color', value: 'black' });\n * const decl2 = postcss.decl({ prop: 'background-color', value: 'white' });\n * rule.prepend(decl1, decl2);\n *\n * root.append({ name: 'charset', params: '\"UTF-8\"' }); // at-rule\n * root.append({ selector: 'a' }); // rule\n * rule.append({ prop: 'color', value: 'black' }); // declaration\n * rule.append({ text: 'Comment' }) // comment\n *\n * root.append('a {}');\n * root.first.append('color: black; z-index: 1');\n */\n prepend(...children) {\n children = children.reverse();\n children.forEach(child => {\n const nodes = this.normalize(child,
this.first, 'prepend').reverse();\n nodes.forEach(node => this.nodes.unshift(node));\n for (const id in this.indexes) {\n this.indexes[id] = this.indexes[id] + nodes.length;\n }\n });\n return this;\n }\n\n cleanRaws(keepBetween) {\n super.cleanRaws(keepBetween);\n if (this.nodes) {\n this.nodes.forEach(node => node.cleanRaws(keepBetween));\n }\n }\n\n /**\n * Insert new node before old node within the container.\n *\n * @param {Node|number} exist - child or child's index.\n * @param {Node|object|string|Node[]} add - new node\n *\n * @return {Node} this node for methods chain\n *\n * @example\n * rule.insertBefore(decl, decl.clone({ prop: '-webkit-' + decl.prop }));\n */\n insertBefore(exist, add) {\n exist = this.index(exist);\n\n const type = exist === 0 ? 'prepend' : false;\n const nodes = this.normalize(add, this.nodes[exist], type).reverse();\n nodes.forEach(node => this.nodes.splice(exist,
0, node));\n\n let index;\n for (const id in this.indexes) {\n index = this.indexes[id];\n if (exist <= index) {\n this.indexes[id] = index + nodes.length;\n }\n }\n\n return this;\n }\n\n /**\n * Insert new node after old node within the container.\n *\n * @param {Node|number} exist - child or child's index\n * @param {Node|object|string|Node[]} add - new node\n *\n * @return {Node} this node for methods chain\n */\n insertAfter(exist, add) {\n exist = this.index(exist);\n\n const nodes = this.normalize(add,
this.nodes[exist]).reverse();\n nodes.forEach(node => this.nodes.splice(exist + 1, 0, node));\n\n let index;\n for (const id in this.indexes) {\n index = this.indexes[id];\n if (exist < index) {\n this.indexes[id] = index + nodes.length;\n }\n }\n\n return this;\n }\n\n remove(child) {\n if (typeof child !== 'undefined') {\n warnOnce('Container#remove is deprecated.
' + 'Use Container#removeChild');\n this.removeChild(child);\n } else {\n super.remove();\n }\n return this;\n }\n\n /**\n * Removes node from the container and cleans the parent properties\n * from the node and its children.\n *\n * @param {Node|number} child - child or child's index\n *\n * @return {Node} this node for methods chain\n *\n * @example\n * rule.nodes.length //=> 5\n * rule.removeChild(decl);\n * rule.nodes.length //=> 4\n * decl.parent //=> undefined\n */\n removeChild(child) {\n child = this.index(child);\n this.nodes[child].parent = undefined;\n this.nodes.splice(child, 1);\n\n let index;\n for (const id in this.indexes) {\n index = this.indexes[id];\n if (index >= child) {\n this.indexes[id] = index - 1;\n }\n }\n\n return this;\n }\n\n /**\n * Removes all children from the container\n * and cleans their parent properties.\n *\n * @return {Node} this node
for methods chain\n *\n * @example\n * rule.removeAll();\n * rule.nodes.length //=> 0\n */\n removeAll() {\n this.nodes.forEach(node => (node.parent = undefined));\n this.nodes = [];\n return this;\n }\n\n /**\n * Passes all declaration values within the container that match pattern\n * through callback, replacing those values with the returned result\n * of callback.\n *\n * This method is useful if you are using a custom unit or function\n * and need to iterate through all values.\n *\n * @param {string|RegExp} pattern - replace pattern\n * @param {object} opts - options to speed up the search\n * @param {string|string[]} opts.props - an array of property names\n * @param {string} opts.fast - string that's used\n * to narrow down values and speed up\n the regexp search\n * @param {function|string} callback

```
 - string to replace pattern\n     *                                or callback that returns a new\n     *
value.\n     *                          The callback will receive\n     *                                the same arguments as
those\n     *                          passed to a function parameter\n     *                                of
`String#replace`.\n     *\n     * @return {Node} this node for methods chain\n     *\n     * @example\n     *
root.replaceValues(/\\d+rem/, { fast: 'rem' }, string => {\n     *   return 15 * parseInt(string) + 'px';\n     * });\n     */\n
replaceValues(pattern, opts, callback) {\n    if (!callback) {\n      callback = opts;\n      opts = {};\n    }\n\n
this.walkDecls(decl => {\n      if (opts.props && opts.props.indexOf(decl.prop) === -1) return;\n      if (opts.fast &&
decl.value.indexOf(opts.fast) === -1) return;\n\n      decl.value = decl.value.replace(pattern,
 callback);\n    });\n\n    return this;\n  }\n\n  /**\n   * Returns `true` if callback returns `true`\n   * for all of the
container's children.\n   *\n   * @param {childCondition} condition - iterator returns true or false.\n   *\n   *
@return {boolean} is every child pass condition\n   *\n   * @example\n   * const noPrefixes = rule.every(i =>
i.prop[0] !== '-');\n   */\n  every(condition) {\n    return this.nodes.every(condition);\n  }\n\n  /**\n   * Returns `true`
if callback returns `true` for (at least) one\n   * of the container's children.\n   *\n   * @param {childCondition}
condition - iterator returns true or false.\n   *\n   * @return {boolean} is some child pass condition\n   *\n   *
@example\n   * const hasPrefix = rule.some(i => i.prop[0] === '-');\n   */\n  some(condition) {\n    return
this.nodes.some(condition);\n  }\n\n  /**\n   * Returns a `child`'s index within the {@link Container#nodes} array.\n
 *\n   * @param {Node} child - child of the current container.\n
   *\n   * @return {number} child index\n   *\n   * @example\n   * rule.index( rule.nodes[2] ) //=> 2\n   */\n
index(child) {\n    if (typeof child === 'number') {\n      return child;\n    } else {\n      return
this.nodes.indexOf(child);\n    }\n  }\n\n  /**\n   * The container's first child.\n   *\n   * @type {Node}\n   *\n   *
@example\n   * rule.first == rules.nodes[0];\n   */\n  get first() {\n    if (!this.nodes) return undefined;\n    return
this.nodes[0];\n  }\n\n  /**\n   * The container's last child.\n   *\n   * @type {Node}\n   *\n   * @example\n   *
rule.last == rule.nodes[rule.nodes.length - 1];\n   */\n  get last() {\n    if (!this.nodes) return undefined;\n    return
this.nodes[this.nodes.length - 1];\n  }\n\n  normalize(nodes, sample) {\n    if (typeof nodes === 'string') {\n      nodes
= cleanSource(parse(nodes).nodes);\n    } else if (!Array.isArray(nodes)) {\n      if (nodes.type === 'root') {\n
nodes = nodes.nodes;\n      } else if (nodes.type) {\n
        nodes = [nodes];\n      } else if (nodes.prop) {\n        if (typeof nodes.value === 'undefined') {\n          throw
new Error('Value field is missed in node creation');\n        } else if (typeof nodes.value !== 'string') {\n
nodes.value = String(nodes.value);\n        }\n        nodes = [new Declaration(nodes)];\n      } else if (nodes.selector)
{\n        nodes = [new Rule(nodes)];\n      } else if (nodes.name) {\n        nodes = [new AtRule(nodes)];\n      } else if
(nodes.text) {\n        nodes = [new Comment(nodes)];\n      } else {\n        throw new Error('Unknown node type in
node creation');\n      }\n    }\n\n    const processed = nodes.map(i => {\n      if (typeof i.raws === 'undefined') i =
this.rebuild(i);\n\n      if (i.parent) i = i.clone();\n      if (typeof i.raws.before === 'undefined') {\n        if (sample &&
typeof sample.raws.before !== 'undefined') {\n          i.raws.before = sample.raws.before.replace(/[^\\s]/g, '');\n
}\n      }\n
 i.parent = this;\n      return i;\n    });\n\n    return processed;\n  }\n\n  rebuild(node, parent) {\n    let fix;\n    if
(node.type === 'root') {\n      fix = new Root();\n    } else if (node.type === 'atrule') {\n      fix = new AtRule();\n    }
else if (node.type === 'rule') {\n      fix = new Rule();\n    } else if (node.type === 'decl') {\n      fix = new
Declaration();\n    } else if (node.type === 'comment') {\n      fix = new Comment();\n    }\n\n    for (const i in node)
{\n      if (i === 'nodes') {\n        fix.nodes = node.nodes.map(j => this.rebuild(j, fix));\n      } else if (i === 'parent'
&& parent) {\n        fix.parent = parent;\n      } else if (node.hasOwnProperty(i)) {\n        fix[i] = node[i];\n      }\n
}\n\n    return fix;\n  }\n\n  eachInside(callback) {\n    warnOnce('Container#eachInside is deprecated. ' + 'Use
Container#walk instead.');\n    return this.walk(callback);\n  }\n\n  eachDecl(prop, callback) {\n
warnOnce('Container#eachDecl is deprecated.
 ' + 'Use Container#walkDecls instead.');\n    return this.walkDecls(prop, callback);\n  }\n\n  eachRule(selector,
callback) {\n    warnOnce('Container#eachRule is deprecated. ' + 'Use Container#walkRules instead.');\n    return
this.walkRules(selector, callback);\n  }\n\n  eachAtRule(name, callback) {\n    warnOnce('Container#eachAtRule is
deprecated. ' + 'Use Container#walkAtRules instead.');\n    return this.walkAtRules(name, callback);\n  }\n\n
```

eachComment(callback) {\n warnOnce('Container#eachComment is deprecated. ' + 'Use Container#walkComments instead.');\n return this.walkComments(callback);\n }\n\n get semicolon() {\n warnOnce('Node#semicolon is deprecated. Use Node#raws.semicolon');\n return this.raws.semicolon;\n }\n\n set semicolon(val) {\n warnOnce('Node#semicolon is deprecated. Use Node#raws.semicolon');\n this.raws.semicolon = val;\n }\n\n get after() {\n warnOnce('Node#after is deprecated. Use Node#raws.after');\n return this.raws.after;\n }\n\n set after(val) {\n warnOnce('Node#after is deprecated. Use Node#raws.after');\n this.raws.after = val;\n }\n\n /**\n * @memberof Container#\n * @member {Node[]} nodes - an array containing the container's children\n *\n * @example\n * const root = postcss.parse('a { color: black }');\n * root.nodes.length //=> 1\n * root.nodes[0].selector //=> 'a'\n * root.nodes[0].nodes[0].prop //=> 'color'\n */\n}\n\nexport default Container;\n","// @flow\nimport Container from './container';\nimport warnOnce from './warn-once';\n\n/**\n * Represents an at-rule.\n *\n * If it's followed in the CSS by a {} block, this node will have\n * a nodes property representing its children.\n *\n * @extends Container\n *\n * @example\n * const root = postcss.parse('@charset \"UTF-8\"; @media print {}');\n *\n * const charset = root.first;\n * charset.type //=> 'atrule'\n * charset.nodes //=> undefined\n *\n * const media = root.last;\n * media.nodes //=> []\n */\nclass AtRule extends Container {\n constructor(defaults) {\n super(defaults);\n this.type = 'atrule';\n }\n\n append(...children) {\n if (!this.nodes) this.nodes = [];\n return super.append(...children);\n }\n\n prepend(...children) {\n if (!this.nodes) this.nodes = [];\n return super.prepend(...children);\n }\n\n get afterName() {\n warnOnce('AtRule#afterName was deprecated. Use AtRule#raws.afterName');\n return this.raws.afterName;\n }\n\n set afterName(val) {\n warnOnce('AtRule#afterName was deprecated. Use AtRule#raws.afterName');\n this.raws.afterName = val;\n }\n\n get _params() {\n warnOnce('AtRule#_params was deprecated. Use AtRule#raws.params');\n return this.raws.params;\n }\n\n set _params(val) {\n warnOnce('AtRule#_params was deprecated. Use AtRule#raws.params');\n this.raws.params = val;\n }\n\n /**\n * @memberof AtRule#\n * @member {string} name - the at-rule's name immediately follows the `@`\n *\n * @example\n * const root = postcss.parse('@media print {}');\n * media.name //=> 'media'\n * const media = root.first;\n */\n\n /**\n * @memberof AtRule#\n * @member {string} params - the at-rule's parameters, the values\n * that follow the at-rule's name but precede\n * any {} block\n *\n * @example\n * const root = postcss.parse('@media print, screen {}');\n * const media = root.first;\n * media.params //=> 'print, screen'\n */\n\n /**\n * @memberof AtRule#\n * @member {object} raws - Information to generate byte-to-byte equal\n * node string as it was in the origin input.\n *\n * Every parser saves its own properties,\n * but the default CSS parser uses:\n *\n * * `before`: the space symbols before the node. It also stores `*`\n * and `_` symbols before the declaration (IE hack).\n * * `after`: the space symbols after the last child of the node\n * to\n the end of the node.\n * * `between`: the symbols between the property and value\n * for declarations, selector and `{` for rules, or last parameter\n * and `{` for at-rules.\n * * `semicolon`: contains true if the last child has\n * an (optional) semicolon.\n * * `afterName`: the space between the at-rule name and its parameters.\n *\n * PostCSS cleans at-rule parameters from comments and extra spaces,\n * but it stores origin content in raws properties.\n * As such, if you don't change a declaration's value,\n * PostCSS will use the raw value with comments.\n *\n * @example\n * const root = postcss.parse(' @media\\nprint {\\n}')\n * root.first.first.raws //=> { before: ' ',\n * // between: ' ',\n * // afterName: '\\n',\n * // after: '\\n' }\n */\n}\n\nexport default AtRule;\n","// @flow\n/**\n * Contains helpers for safely splitting lists of CSS values,\n * preserving\n parentheses and quotes.\n *\n * @example\n * const list = postcss.list;\n *\n * @namespace list\n */\nconst list = {\n split(string, separators, last) {\n const array = [];\n let current = '';\n let split = false;\n\n let func = 0;\n let quote = false;\n let escape = false;\n\n for (let i = 0; i < string.length; i++) {\n const letter = string[i];\n\n if (quote) {\n if (escape) {\n escape = false;\n } else if (letter === '\\\\') {\n escape = true;\n } else if (letter === quote) {\n quote = false;\n }\n } else if (letter === '\"' || letter === \"'\") {\n quote = letter;\n } else if (letter === '(') {\n func += 1;\n } else if (letter === ')') {\n if (func > 0) func -= 1;\n

} else if (func === 0) {\n if (separators.indexOf(letter) !== -1) split = true;\n }\n\n if (split) {\n if (current !== '') array.push(current.trim());\n current = '';\n split = false;\n } else {\n current += letter;\n }\n }\n\n if (last || current !== '') array.push(current.trim());\n return array;\n },\n\n /**\n * Safely splits space-separated values (such as those for `background`,\n * `border-radius`, and other shorthand properties).\n *\n * @param {string} string - space-separated values\n *\n * @return {string[]} splitted values\n *\n * @example\n * postcss.list.space('1px calc(10% + 1px)') //=> ['1px', 'calc(10% + 1px)']\n */\n space(string) {\n const spaces = [' ', '\\n', '\\t'];\n return list.split(string, spaces);\n },\n\n /**\n * Safely splits comma-separated values (such as those for `transition-*`\n * and `background` properties).\n *\n * @param {string} string - comma-separated values\n *\n * @return {string[]} splitted values\n *\n * @example\n * postcss.list.comma('black, linear-gradient(white, black)')\n * //=> ['black', 'linear-gradient(white, black)']\n */\n comma(string) {\n const comma = ',';\n return list.split(string, [comma], true);\n },\n};\n\nexport default list;\n","// @flow\nimport './at-rule'; // break cyclical dependency deadlock – #87\n\nimport Container from './container';\nimport warnOnce from './warn-once';\nimport list from './list';\n\n/**\n * Represents a CSS rule: a selector followed by a declaration block.\n *\n * @extends Container\n *\n * @example\n * const root = postcss.parse('a{}');\n * const rule = root.first;\n * rule.type //=> 'rule'\n * rule.toString() //=> 'a{}'\n */\nclass Rule extends Container {\n constructor(defaults) {\n super(defaults);\n this.type = 'rule';\n if (!this.nodes) this.nodes = [];\n }\n\n /**\n * An array containing the rule's individual selectors.\n * Groups of selectors are split at commas.\n *\n * @type {string[]}\n *\n * @example\n * const root = postcss.parse('a, b { }');\n * const rule = root.first;\n *\n * rule.selector //=> 'a, b'\n * rule.selectors //=> ['a', 'b']\n *\n * rule.selectors = ['a', 'strong'];\n * rule.selector //=> 'a, strong'\n */\n get selectors() {\n return list.comma(this.selector);\n }\n\n set selectors(values) {\n const match = this.selector ? this.selector.match(/,\\s*/) : null;\n const sep = match ? match[0] : `,${this.raw('between', 'beforeOpen')}`;\n this.selector = values.join(sep);\n }\n\n get _selector() {\n warnOnce('Rule#_selector is deprecated. Use Rule#raws.selector');\n return this.raws.selector;\n }\n\n set _selector(val) {\n warnOnce('Rule#_selector is deprecated. Use Rule#raws.selector');\n this.raws.selector = val;\n }\n\n /**\n * @memberof Rule#\n * @member {string} selector - the rule's full selector represented\n * as a string\n *\n * @example\n * const root = postcss.parse('a, b { }');\n * const rule = root.first;\n * rule.selector //=> 'a, b'\n */\n\n /**\n * @memberof Rule#\n * @member {object} raws - Information to generate byte-to-byte equal\n * node string as it was in the origin input.\n *\n * Every parser saves its own properties,\n * but the default CSS parser uses:\n *\n * * `before`: the space symbols before the node. It also stores `*`\n * and `_` symbols before the declaration (IE hack).\n * * `after`: the space symbols after the last child of the node\n * to the end of the node.\n * * `between`: the symbols between the property and value\n * for declarations, selector and `{` for rules, or last parameter\n * and `{` for at-rules.\n * * `semicolon`: contains true if the last child has\n * an (optional) semicolon.\n *\n * PostCSS cleans selectors from comments and extra spaces,\n * but it stores origin content in raws properties.\n * As such, if you don't change a declaration's value,\n * PostCSS will use the raw value with comments.\n *\n * @example\n * const root = postcss.parse('a {\\n color:black\\n}')\n * root.first.first.raws //=> { before: '', between: ' ', after: '\\n' }\n */\n}\n\nexport default Rule;\n","// @flow\n\n/**\n * Represents a plugin's warning. It can be created using {@link Node#warn}.\n *\n * @example\n * if (decl.important) {\n * decl.warn(result, 'Avoid !important', { word: '!important' });\n * }\n */\nclass Warning {\n /**\n * @param {string} text - warning message\n * @param {Object} [opts] - warning options\n * @param {Node} opts.node - CSS node that caused the warning\n * @param {string} opts.word - word in CSS source that caused the warning\n * @param {number} opts.index - index in CSS node string that caused\n * the warning\n * @param {string} opts.plugin - name of the plugin that created\n * this warning. {@link Result#warn} fills\n * this property automatically.\n */\n

```
 constructor(text, opts = {}) {\n    /**\n     * @member {string} - Type to filter warnings from\n     *
{@link Result#messages}. Always equal\n     *                 to `\"warning\"`.\n     *\n     * @example\n     * const
nonWarning = result.messages.filter(i => i.type !== 'warning')\n     */\n    this.type = 'warning';\n    /**\n     *
@member {string} - The warning message.\n     *\n     * @example\n     * warning.text //=> 'Try to avoid
!important'\n     */\n    this.text = text;\n\n    if (opts.node && opts.node.source) {\n      const pos =
opts.node.positionBy(opts);\n      /**\n       * @member {number} - Line in the input file\n       *                 with
this warning's source\n       *\n       * @example\n       * warning.line //=> 5\n       */\n      this.line = pos.line;\n
/**\n       * @member {number} - Column in the input file\n       *                 with this warning's source.\n       *\n
 * @example\n       * warning.column //=>
 6\n       */\n      this.column = pos.column;\n    }\n\n    for (const opt in opts) this[opt] = opts[opt];\n  }\n\n  /**\n   *
Returns a warning position and message.\n   *\n   * @example\n   * warning.toString() //=> 'postcss-lint:a.css:10:14:
Avoid !important'\n   *\n   * @return {string} warning position and message\n   */\n  toString() {\n    if (this.node)
{\n      return this.node.error(this.text, {\n        plugin: this.plugin,\n        index: this.index,\n        word: this.word,\n
 }).message;\n    } else if (this.plugin) {\n      return `${this.plugin}: ${this.text}`;\n    } else {\n      return this.text;\n
 }\n  }\n\n  /**\n   * @memberof Warning#\n   * @member {string} plugin - The name of the plugin that created\n
*                 it will fill this property automatically.\n   *                 this warning. When you call {@link
Node#warn}\n   *\n   * @example\n   * warning.plugin //=> 'postcss-important'\n   */\n\n  /**\n   * @memberof
Warning#\n
   * @member {Node} node - Contains the CSS node that caused the warning.\n   *\n   * @example\n   *
warning.node.toString() //=> 'color: white !important'\n   */\n}\n\nexport default Warning;\n","// @flow\nimport
Warning from './warning';\n\n/**\n * @typedef  {object} Message\n * @property {string} type   - message type\n *
@property {string} plugin - source PostCSS plugin name\n */\n\n/**\n * Provides the result of the PostCSS
transformations.\n *\n * A Result instance is returned by {@link LazyResult#then}\n * or {@link Root#toResult}
methods.\n *\n * @example\n * postcss([cssnext]).process(css).then(function (result) {\n *
console.log(result.css);\n * });\n *\n * @example\n * var result2 = postcss.parse(css).toResult();\n */\nclass Result
{\n  /**\n   * @param {Processor} processor - processor used for this transformation.\n   * @param {Root}      root
 - Root node after all transformations.\n   * @param {processOptions} opts - options from the {@link
Processor#process}\n
   *                            or {@link Root#toResult}\n   */\n  constructor(processor, root, opts) {\n    /**\n     *
@member {Processor} - The Processor instance used\n     *                    for this transformation.\n     *\n     *
@example\n     * for ( let plugin of result.processor.plugins) {\n     *   if ( plugin.postcssPlugin === 'postcss-bad' )
{\n     *     throw 'postcss-good is incompatible with postcss-bad';\n     *   }\n     * });\n     */\n    this.processor =
processor;\n    /**\n     * @member {Message[]} - Contains messages from plugins\n     *                    (e.g.,
warnings or custom messages).\n     *                    Each message should have type\n     *                    and plugin
properties.\n     *\n     * @example\n     * postcss.plugin('postcss-min-browser', () => {\n     *   return (root, result)
=> {\n     *     var browsers = detectMinBrowsersByCanIUse(root);\n     *     result.messages.push({\n     *       type:
'min-browser',\n
     *       plugin:  'postcss-min-browser',\n     *       browsers: browsers\n     *     });\n     *   };\n     * });\n     */\n
this.messages = [];\n    /**\n     * @member {Root} - Root node after all transformations.\n     *\n     * @example\n
 * root.toResult().root == root;\n     */\n    this.root = root;\n    /**\n     * @member {processOptions} - Options from
the {@link Processor#process}\n     *                    or {@link Root#toResult} call\n     *                    that
produced this Result instance.\n     *\n     * @example\n     * root.toResult(opts).opts == opts;\n     */\n    this.opts =
opts;\n    /**\n     * @member {string} - A CSS string representing of {@link Result#root}.\n     *\n     *
@example\n     * postcss.parse('a{}').toResult().css //=> \"a{}\"\n     */\n    this.css = undefined;\n    /**\n     *
@member {SourceMapGenerator} - An instance of `SourceMapGenerator`\n     *                    class from the
`source-map`
 library,\n     *                    representing changes\n     *                    to the {@link Result#root}
instance.\n     *\n     * @example\n     * result.map.toJSON() //=> { version: 3, file: 'a.css', … }\n     *\n     *
```

```
@example\n     * if ( result.map ) {\n     *   fs.writeFileSync(result.opts.to + '.map', result.map.toString());\n     * }\n     */\n    this.map = undefined;\n  }\n\n  /**\n   * Returns for @{link Result#css} content.\n   *\n   * @example\n   * result + '' === result.css\n   *\n   * @return {string} string representing of {@link Result#root}\n   */\n  toString() {\n    return this.css;\n  }\n\n  /**\n   * Creates an instance of {@link Warning} and adds it\n   * to {@link Result#messages}.\n   *\n   * @param {string} text       - warning message\n   * @param {Object} [opts]     - warning options\n   * @param {Node}   opts.node   - CSS node that caused the warning\n   * @param {string} opts.word   - word in CSS source that caused the warning\n
   * @param {number} opts.index  - index in CSS node string that caused\n   *                               the warning\n   * @param {string} opts.plugin - name of the plugin that created\n   *                               this warning. {@link Result#warn} fills\n   *                               this property automatically.\n   *\n   * @return {Warning} created warning\n   */\n  warn(text, opts = {}) {\n    if (!opts.plugin) {\n      if (this.lastPlugin &&
this.lastPlugin.postcssPlugin) {\n        opts.plugin = this.lastPlugin.postcssPlugin;\n      }\n    }\n\n    const warning = new Warning(text, opts);\n    this.messages.push(warning);\n\n    return warning;\n  }\n\n  /**\n   * Returns warnings from plugins. Filters {@link Warning} instances\n   * from {@link Result#messages}.\n   *\n   * @example\n   * result.warnings().forEach(warn => {\n   *   console.warn(warn.toString());\n   * });\n   *\n   * @return {Warning[]} warnings from plugins\n   */\n  warnings() {\n    return
 this.messages.filter(i => i.type === 'warning');\n  }\n\n  /**\n   * An alias for the {@link Result#css} property.\n   * Use it with syntaxes that generate non-CSS output.\n   * @type {string}\n   *\n   * @example\n   * result.css === result.content;\n   */\n  get content() {\n    return this.css;\n  }\n}\n\nexport default Result;\n","// @flow\nimport stringify from './stringify';\nimport warnOnce from './warn-once';\nimport Result from './result';\nimport parse from './parse';\n\nfunction isPromise(obj) {\n  return typeof obj === 'object' && typeof obj.then ===
'function';\n}\n\n/**\n * @callback onFulfilled\n * @param {Result} result\n */\n\n/**\n * @callback onRejected\n * @param {Error} error\n */\n\n/**\n * A Promise proxy for the result of PostCSS transformations.\n *\n * A `LazyResult` instance is returned by {@link Processor#process}.\n *\n * @example\n * const lazy = postcss([cssnext]).process(css);\n */\nclass LazyResult {\n  constructor(processor, css, opts) {\n    this.stringified
 = false;\n    this.processed = false;\n\n    let root;\n    if (typeof css === 'object' && css.type === 'root') {\n      root = css;\n    } else if (css instanceof LazyResult || css instanceof Result) {\n      root = css.root;\n      if (css.map) {\n
if (typeof opts.map === 'undefined') opts.map = {};\n        if (!opts.map.inline) opts.map.inline = false;\n
opts.map.prev = css.map;\n      }\n    } else {\n      let parser = parse;\n      if (opts.syntax) parser =
opts.syntax.parse;\n      if (opts.parser) parser = opts.parser;\n      if (parser.parse) parser = parser.parse;\n\n      try
{\n        root = parser(css, opts);\n      } catch (error) {\n        this.error = error;\n      }\n    }\n\n    this.result = new
Result(processor, root, opts);\n  }\n\n  /**\n   * Returns a {@link Processor} instance, which will be used\n   * for
CSS transformations.\n   * @type {Processor}\n   */\n  get processor() {\n    return this.result.processor;\n  }\n\n
/**\n   * Options
 from the {@link Processor#process} call.\n   * @type {processOptions}\n   */\n  get opts() {\n    return
this.result.opts;\n  }\n\n  /**\n   * Processes input CSS through synchronous plugins, converts `Root`\n   * to a CSS
string and returns {@link Result#css}.\n   *\n   * This property will only work with synchronous plugins.\n   * If the
processor contains any asynchronous plugins\n   * it will throw an error. This is why this method is only\n   * for
debug purpose, you should always use {@link LazyResult#then}.\n   *\n   * @type {string}\n   * @see Result#css\n
 */\n  get css() {\n    return this.stringify().css;\n  }\n\n  /**\n   * An alias for the `css` property. Use it with
syntaxes\n   * that generate non-CSS output.\n   *\n   * This property will only work with synchronous plugins.\n   *
If the processor contains any asynchronous plugins\n   * it will throw an error. This is why this method is only\n   *
for debug purpose, you should always use {@link LazyResult#then}.\n
   *\n   * @type {string}\n   * @see Result#content\n   */\n  get content() {\n    return this.stringify().content;\n  }\n\n
/**\n   * Processes input CSS through synchronous plugins\n   * and returns {@link Result#map}.\n   *\n   * This
property will only work with synchronous plugins.\n   * If the processor contains any asynchronous plugins\n   * it
will throw an error. This is why this method is only\n   * for debug purpose, you should always use {@link
LazyResult#then}.\n   *\n   * @type {SourceMapGenerator}\n   * @see Result#map\n   */\n  get map() {\n    return
```

```
this.stringify().map;\n  }\n\n  /**\n   * Processes input CSS through synchronous plugins\n   * and returns {@link Result#root}.\n   *\n   * This property will only work with synchronous plugins. If the processor\n   * contains any asynchronous plugins it will throw an error.\n   *\n   * This is why this method is only for debug purpose,\n   * you should always use {@link LazyResult#then}.\n   *\n   * @type {Root}\n   * @see Result#root\n   */\n  get root() {\n    return this.sync().root;\n  }\n\n  /**\n   * Processes input CSS through synchronous plugins\n   * and returns {@link Result#messages}.\n   *\n   * This property will only work with synchronous plugins. If the processor\n   * contains any asynchronous plugins it will throw an error.\n   *\n   * This is why this method is only for debug purpose,\n   * you should always use {@link LazyResult#then}.\n   *\n   * @type {Message[]}\n   * @see Result#messages\n   */\n  get messages() {\n    return this.sync().messages;\n  }\n\n  /**\n   * Processes input CSS through synchronous plugins\n   * and calls {@link Result#warnings()}.\n   *\n   * @return {Warning[]} warnings from plugins\n   */\n  warnings() {\n    return this.sync().warnings();\n  }\n\n  /**\n   * Alias for the {@link LazyResult#css} property.\n   *\n   * @example\n   * lazy + '' === lazy.css;\n   *\n   * @return {string} output CSS\n   */\n  toString() {\n    return this.css;\n  }\n\n  /**\n   * Processes input CSS through synchronous and asynchronous plugins\n   * and calls `onFulfilled` with a Result instance. If a plugin throws\n   * an error, the `onRejected` callback will be executed.\n   *\n   * It implements standard Promise API.\n   *\n   * @param {onFulfilled} onFulfilled - callback will be executed\n   *
        when all plugins will finish work\n   * @param {onRejected}  onRejected  - callback will be execited on any error\n   *\n   * @return {Promise} Promise API to make queue\n   *\n   * @example\n   * postcss([cssnext]).process(css).then(result => {\n   *   console.log(result.css);\n   * });\n   */\n  then(onFulfilled, onRejected) {\n    return this.async().then(onFulfilled, onRejected);\n  }\n\n  /**\n   * Processes input CSS through synchronous and asynchronous plugins\n   * and calls onRejected for each error thrown in any plugin.\n   *\n   * It implements standard Promise API.\n   *\n   * @param {onRejected} onRejected - callback
   will be execited on any error\n   *\n   * @return {Promise} Promise API to make queue\n   *\n   * @example\n   * postcss([cssnext]).process(css).then(result => {\n   *   console.log(result.css);\n   * }).catch(error => {\n   *   console.error(error);\n   * });\n   */\n  catch(onRejected) {\n    return this.async().catch(onRejected);\n  }\n\n  handleError(error, plugin) {\n    try {\n      this.error = error;\n      if (error.name === 'CssSyntaxError' && !error.plugin) {\n        error.plugin = plugin.postcssPlugin;\n        error.setMessage();\n      } else if (plugin.postcssVersion) {\n        const pluginName = plugin.postcssPlugin;\n        const pluginVer = plugin.postcssVersion;\n        const runtimeVer = this.result.processor.version;\n        const a = pluginVer.split('.');\n        const b = runtimeVer.split('.');\n\n        if (a[0] !== b[0] || parseInt(a[1]) > parseInt(b[1])) {\n          warnOnce(\n            `${'Your current PostCSS version ' + 'is '}${runtimeVer},
   but ${pluginName} ` +\n            `uses ${pluginVer}. Perhaps this is ` +\n            `the source of the error below.`\n          );\n        }\n      }\n    } catch (err) {\n      if (console && console.error) console.error(err);\n    }\n  }\n\n  asyncTick(resolve, reject) {\n    if (this.plugin >= this.processor.plugins.length) {\n      this.processed = true;\n      return resolve();\n    }\n\n    try {\n      const plugin = this.processor.plugins[this.plugin];\n      const promise = this.run(plugin);\n      this.plugin += 1;\n\n      if (isPromise(promise)) {\n        promise\n          .then(() => {\n            this.asyncTick(resolve, reject);\n          })\n          .catch(error => {\n            this.handleError(error, plugin);\n            this.processed = true;\n            reject(error);\n          });\n      } else {\n        this.asyncTick(resolve, reject);\n      }\n    } catch (error) {\n      this.processed = true;\n      reject(error);\n    }\n  }\n\n  async() {\n    if (this.processed) {\n      return new Promise((resolve, reject) => {\n        if (this.error) {\n          reject(this.error);\n        } else {\n          resolve(this.stringify());\n        }\n      });\n    }\n    if (this.processing) {\n      return this.processing;\n    }\n\n    this.processing = new Promise((resolve, reject) => {\n      if (this.error) return reject(this.error);\n      this.plugin = 0;\n      this.asyncTick(resolve, reject);\n    }).then(() => {\n      this.processed = true;\n      return this.stringify();\n    });\n\n    return this.processing;\n  }\n\n  sync() {\n    if (this.processed) return this.result;\n    this.processed = true;\n\n    if (this.processing) {\n      throw new Error('Use process(css).then(cb) to work with async plugins');\n    }\n\n    if (this.error) throw this.error;\n\n    this.result.processor.plugins.forEach(plugin => {\n      const promise = this.run(plugin);\n      if (isPromise(promise)) {\n        throw new Error('Use process(css).then(cb)
```

to work with async plugins');\n }\n });\n\n return this.result;\n }\n\n run(plugin) {\n this.result.lastPlugin = plugin;\n\n try {\n return plugin(this.result.root, this.result);\n } catch (error) {\n this.handleError(error, plugin);\n throw error;\n }\n }\n\n stringify() {\n if (this.stringified) return this.result;\n this.stringified = true;\n\n this.sync();\n\n const opts = this.result.opts;\n let str = stringify;\n if (opts.syntax) str = opts.syntax.stringify;\n if (opts.stringifier) str = opts.stringifier;\n if (str.stringify) str = str.stringify;\n\n let result = '';\n str(this.root, i => {\n result += i;\n });\n this.result.css = result;\n\n return this.result;\n }\n}\n\nexport default LazyResult;\n","// @flow\nimport LazyResult from './lazy-result';\n\n/**\n * @callback builder\n * @param {string} part - part of generated CSS connected to this node\n * @param {Node} node - AST node\n * @param {\"start\"|\"end\"} [type] - node's part type\n */\n\n/**\n * @callback parser\n *\n * @param {string|toString} css - string with input CSS or any object\n * with toString() method, like a Buffer\n * @param {processOptions} [opts] - options with only `from` and `map` keys\n *\n * @return {Root} PostCSS AST\n */\n\n/**\n * @callback stringifier\n *\n * @param {Node} node - start node for stringifing. Usually {@link Root}.\n * @param {builder} builder - function to concatenate CSS from node's parts\n * or generate string and source map\n *\n * @return {void}\n */\n\n/**\n * @typedef {object} syntax\n * @property {parser} parse - function to generate AST by string\n * @property {stringifier} stringify - function to generate string by AST\n */\n\n/**\n * @typedef {object} toString\n * @property {function} toString\n */\n\n/**\n * @callback pluginFunction\n * @param {Root} root - parsed input CSS\n * @param {Result} result - result to set warnings or check other plugins\n */\n\n/**\n * @typedef {object} Plugin\n * @property {function} postcss - PostCSS plugin function\n */\n\n/**\n * @typedef {object} processOptions\n * @property {string} from - the path of the CSS source file.\n * You should always set `from`,\n * because it is used in source map\n * generation and syntax error messages.\n * @property {string} to - the path where you'll put the output\n * CSS file. You should always set `to`\n * to generate correct source maps.\n * @property {parser} parser - function to generate AST by string\n * @property {stringifier} stringifier - class to generate string by AST\n * @property {syntax} syntax - object with `parse` and `stringify`\n * @property {object} map - source map options\n * @property {boolean} map.inline - does source map should\n * be embedded in the output\n * CSS as a base64-encoded\n * comment\n * @property {string|object|false|function} map.prev - source map content\n * from a previous\n * processing step\n * (for example, Sass).\n * PostCSS will try to find\n * previous map\n * automatically, so you\n * could disable it by\n * `false` value.\n * @property {boolean} map.sourcesContent - does PostCSS should set\n * the origin content to map\n * @property {string|false} map.annotation - does PostCSS should set\n * annotation comment to map\n * @property {string} map.from - override `from` in map's\n * `sources`\n */\n\n/**\n * Contains plugins to process CSS. Create one `Processor` instance,\n * initialize its plugins, and then use that instance on numerous CSS files.\n *\n * @example\n * const processor = postcss([autoprefixer, precss]);\n * processor.process(css1).then(result => console.log(result.css));\n * processor.process(css2).then(result => console.log(result.css));\n */\nclass Processor {\n /**\n * @param {Array.<Plugin|pluginFunction>|Processor} plugins - PostCSS\n * plugins. See {@link Processor#use} for plugin format.\n */\n constructor(plugins = []) {\n /**\n * @member {string} - Current PostCSS version.\n *\n * @example\n * if (result.processor.version.split('.')[0] !== '5') {\n * throw new Error('This plugin works only with PostCSS 5');\n * }\n */\n this.version = '5.2.0';\n /**\n * @member {pluginFunction[]} - Plugins added to this processor.\n *\n * @example\n * const processor = postcss([autoprefixer, precss]);\n * processor.plugins.length //=> 2\n */\n this.plugins = this.normalize(plugins);\n }\n\n /**\n * Adds a plugin to be used as a CSS processor.\n *\n * PostCSS plugin

can be in 4 formats:\n * * A plugin created by {@link postcss.plugin} method.\n * * A function. PostCSS will pass the function a @{link Root}\n * as the first argument and current {@link Result} instance\n * as the second.\n * * An object with a `postcss` method. PostCSS will
use that method\n * as described in #2.\n * * Another {@link Processor} instance. PostCSS will copy plugins\n * from that instance into this one.\n *\n * Plugins can also be added by passing them as arguments when creating\n * a `postcss` instance (see [`postcss(plugins)`]).\n *\n * Asynchronous plugins should return a `Promise` instance.\n *\n * @param {Plugin|pluginFunction|Processor} plugin - PostCSS plugin\n *
or {@link Processor}\n * with plugins\n *\n * @example\n *
const processor = postcss()\n * .use(autoprefixer)\n * .use(precss);\n *\n * @return {Processes} current processor to make methods chain\n */\n use(plugin) {\n this.plugins =
this.plugins.concat(this.normalize([plugin]));\n return this;\n }\n\n /**\n * Parses source CSS and returns a {@link LazyResult} Promise proxy.\n * Because some plugins can be asynchronous
it doesn’t make\n * any transformations. Transformations will be applied\n * in the {@link LazyResult} methods.\n *\n * @param {string|toString|Result} css - String with input CSS or\n * any object with a `toString()`\n *
method, like a Buffer.\n *
Optionally, send a {@link Result}\n * instance and the processor will\n *
take the {@link Root} from it.\n * @param {processOptions} [opts] - options\n *\n * @return {LazyResult} Promise proxy\n *\n * @example\n * processor.process(css, { from: 'a.css', to: 'a.out.css' })\n * .then(result => {\n * console.log(result.css);\n * });\n */\n process(css, opts = {}) {\n return new LazyResult(this, css, opts);\n }\n\n normalize(plugins) {\n let normalized = [];\n plugins.forEach(i => {\n if (i.postcss) i = i.postcss;\n\n if (typeof i === 'object' && Array.isArray(i.plugins)) {\n normalized = normalized.concat(i.plugins);\n } else if (typeof i === 'function') {\n normalized.push(i);\n } else {\n throw new Error(`${i} is not a PostCSS plugin`);\n }\n });\n return normalized;\n }\n}\n\nexport default Processor;\n","// @flow\nimport './rule'; // break cyclical dependency deadlock – #87\n\nimport Container from './container';\nimport LazyResult from './lazy-result';\nimport Processor from './processor';\nimport warnOnce from './warn-once';\n\n/**\n * Represents a CSS file and contains all its parsed nodes.\n *\n * @extends Container\n *\n * @example\n * const root = postcss.parse('a{color:black} b{z-index:2}');\n * root.type //=> 'root'\n * root.nodes.length //=> 2\n */\nclass Root extends Container {\n constructor(defaults) {\n super(defaults);\n this.type = 'root';\n if (!this.nodes) this.nodes = [];\n }\n\n
removeChild(child) {\n child = this.index(child);\n\n if (child === 0 && this.nodes.length > 1) {\n this.nodes[1].raws.before = this.nodes[child].raws.before;\n }\n\n return super.removeChild(child);\n }\n\n normalize(child, sample, type) {\n const nodes = super.normalize(child);\n\n if (sample) {\n if (type === 'prepend') {\n if (this.nodes.length > 1) {\n sample.raws.before = this.nodes[1].raws.before;\n } else {\n delete sample.raws.before;\n }\n } else if (this.first !== sample) {\n nodes.forEach(node => {\n node.raws.before = sample.raws.before;\n });\n }\n }\n\n return nodes;\n }\n\n /**\n * Returns a {@link Result} instance representing the root’s CSS.\n *\n * @param {processOptions} [opts] - options with only `to` and `map` keys\n *\n * @return {Result} result with current root’s CSS\n *\n * @example\n * const root1 = postcss.parse(css1, { from: 'a.css'
});\n * const root2 = postcss.parse(css2, { from: 'b.css' });\n * root1.append(root2);\n * const result = root1.toResult({ to: 'all.css', map: true });\n */\n toResult(opts = {}) {\n const lazy = new LazyResult(new Processor(), this, opts);\n return lazy.stringify();\n }\n\n remove(child) {\n warnOnce('Root#remove is deprecated. Use Root#removeChild');\n this.removeChild(child);\n }\n\n prevMap() {\n warnOnce('Root#prevMap is deprecated. Use Root#source.input.map');\n return this.source.input.map;\n }\n\n /**\n * @memberof Root#\n * @member {object} raws - Information to generate byte-to-byte equal\n *
node string as it was in the origin input.\n *\n * Every parser saves its own properties,\n * but the default CSS parser uses:\n *\n * * `after`: the space symbols after the last child to the end of file.\n * * `semicolon`: is the last child has an (optional) semicolon.\n *\n * @example\n * postcss.parse('a

```
{}\\n').raws //=> { after: '\\n' }\n   * postcss.parse('a {}').raws   //=> { after: " }\n   */\n}\n\nexport default
Root;\n","// @flow\nimport './root'; // break cyclical dependency deadlock – #87\n\nimport CssSyntaxError from
'./css-syntax-error';\n// import PreviousMap    from './previous-map';\n\nlet sequence = 0;\n\n/**\n * @typedef
{object} filePosition\n * @property {string} file   - path to file\n * @property {number} line   - source line in file\n
* @property {number} column - source column in file\n */\n\n/**\n * Represents the source CSS.\n *\n *
@example\n * const root  = postcss.parse(css, { from: file });\n * const input = root.source.input;\n */\nclass Input
{\n  /**\n   * @param {string} css    - input CSS source\n   * @param {object} [opts] - {@link Processor#process}
options\n   */\n  constructor(css, opts = {}) {\n    /**\n     * @member {string} - input CSS source\n     *\n     *
@example\n     * const input = postcss.parse('a{}', { from: file }).input;\n     *
input.css //=> \"a{}\";\n     */\n    this.css = css.toString();\n\n    if (this.css[0] === '\\uFEFF' || this.css[0] ===
'\\uFFFE') {\n      this.css = this.css.slice(1);\n    }\n\n    if (opts.from) {\n      if (/^\\w+:\\/\\//.test(opts.from)) {\n
/**\n         * @member {string} - The absolute path to the CSS source file\n         *                    defined with the
`from` option.\n         *\n         * @example\n         * const root = postcss.parse(css, { from: 'a.css' });\n         *
root.source.input.file //=> '/home/ai/a.css'\n         */\n        this.file = opts.from;\n      } else {\n        this.file =
path.resolve(opts.from);\n      }\n    }\n\n    /*\n      let map = new PreviousMap(this.css, opts);\n      if ( map.text )
{\n        /!**\n         * @member {PreviousMap} - The input source map passed from\n         *
a compilation step before PostCSS\n         *                    (for example, from Sass compiler).\n
*\n         * @example\n         * root.source.input.map.consumer().sources //=> ['a.sass']\n         *!/\n
this.map = map;\n        let file = map.consumer().file;\n        if ( !this.file && file ) this.file =
this.mapResolve(file);\n      }\n*/\n\n    if (!this.file) {\n      sequence += 1;\n      /**\n       * @member {string} -
The unique ID of the CSS source. It will be\n       *                    created if `from` option is not provided\n       *
(because PostCSS does not know the file path).\n       *\n       * @example\n       * const root =
postcss.parse(css);\n       * root.source.input.file //=> undefined\n       * root.source.input.id   //=> \"<input css 1>\"\n
*/\n      this.id = `<input css ${sequence}>`;\n    }\n    if (this.map) this.map.file = this.from;\n  }\n\n
error(message, line, column, opts = {}) {\n    let result;\n    const origin = this.origin(line, column);\n    if (origin) {\n
result
 = new CssSyntaxError(\n        message,\n        origin.line,\n        origin.column,\n        origin.source,\n
origin.file,\n        opts.plugin\n      );\n    } else {\n      result = new CssSyntaxError(message, line, column, this.css,
this.file, opts.plugin);\n    }\n\n    result.input = { line, column, source: this.css };\n    if (this.file) result.input.file =
this.file;\n\n    return result;\n  }\n\n  /**\n   * Reads the input source map and returns a symbol position\n   * in the
input source (e.g., in a Sass file that was compiled\n   * to CSS before being passed to PostCSS).\n   *\n   * @param
{number} line   - line in input CSS\n   * @param {number} column - column in input CSS\n   *\n   * @return
{filePosition} position in input source\n   *\n   * @example\n   * root.source.input.origin(1, 1) //=> { file: 'a.css',
line: 3, column: 1 }\n   */\n  origin(line, column) {\n    if (!this.map) return false;\n    const consumer =
this.map.consumer();\n\n    const from =
 consumer.originalPositionFor({ line, column });\n    if (!from.source) return false;\n\n    const result = {\n      file:
this.mapResolve(from.source),\n      line: from.line,\n      column: from.column,\n    };\n\n    const source =
consumer.sourceContentFor(from.source);\n    if (source) result.source = source;\n\n    return result;\n  }\n\n
mapResolve(file) {\n    if (/^\\w+:\\/\\//.test(file)) {\n      return file;\n    } else {\n      return
path.resolve(this.map.consumer().sourceRoot || '.', file);\n    }\n  }\n\n  /**\n   * The CSS source identifier. Contains
{@link Input#file} if the user\n   * set the `from` option, or {@link Input#id} if they did not.\n   * @type {string}\n
*\n   * @example\n   * const root = postcss.parse(css, { from: 'a.css' });\n   * root.source.input.from //=>
\"/home/ai/a.css\"\n   *\n   * const root = postcss.parse(css);\n   * root.source.input.from //=> \"<input css 1>\"\n
*/\n  get from() {\n    return this.file || this.id;\n  }\n}\n\nexport default
 Input;\n","// @flow\nimport tokenize from '../postcss/tokenize';\nimport Comment from
'../postcss/comment';\nimport Parser from '../postcss/parser';\n\nexport default class SafeParser extends Parser {\n
tokenize() {\n    this.tokens = tokenize(this.input, { ignoreErrors: true });\n  }\n\n  comment(token) {\n    const node
= new Comment();\n    this.init(node, token[2], token[3]);\n    node.source.end = { line: token[4], column: token[5]
```

};\n\n let text = token[1].slice(2);\n if (text.slice(-2) === '*/') text = text.slice(0, -2);\n\n if (/^\\s*$/.test(text)) {\n   node.text = '';\n   node.raws.left = text;\n   node.raws.right = '';\n } else {\n   const match = text.match(/^(\\s*)([^]*[^\\s])(\\s*)$/);\n   node.text = match[2];\n   node.raws.left = match[1];\n   node.raws.right = match[3];\n }\n }\n\n unclosedBracket() {}\n\n unknownWord(start) {\n const buffer = this.tokens.slice(start, this.pos + 1);\n this.spaces += buffer.map(i => i[1]).join('');\n }\n\n unexpectedClose() {\n this.current.raws.after += '}';\n }\n\n doubleColon() {}\n\n unnamedAtrule(node) {\n node.name = '';\n }\n\n precheckMissedSemicolon(tokens) {\n const colon = this.colon(tokens);\n if (colon === false) return;\n\n let split;\n for (split = colon - 1; split >= 0; split--) {\n   if (tokens[split][0] === 'word') break;\n }\n for (split -= 1; split >= 0; split--) {\n   if (tokens[split][0] !== 'space') {\n   split += 1;\n   break;\n   }\n }\n const other = tokens.splice(split, tokens.length - split);\n this.decl(other);\n }\n\n checkMissedSemicolon() {}\n\n endFile() {\n if (this.current.nodes && this.current.nodes.length) {\n   this.current.raws.semicolon = this.semicolon;\n }\n this.current.raws.after = (this.current.raws.after || '') + this.spaces;\n\n while (this.current.parent) {\n   this.current = this.current.parent;\n   this.current.raws.after = '';\n }\n }\n}\n","// @flow\nimport Input from '../postcss/input';\n\nimport SafeParser from './safe-parser';\n\nexport default function safeParse(css, opts) {\n const input = new Input(css, opts);\n\n const parser = new SafeParser(input);\n parser.tokenize();\n parser.loop();\n\n return parser.root;\n}\n","// @flow\n/* eslint-disable import/no-unresolved */\nimport transformDeclPairs from 'css-to-react-native';\n\nimport generateComponentId from '../utils/generateComponentId';\nimport type { RuleSet, StyleSheet } from '../types';\nimport flatten from '../utils/flatten';\n// $FlowFixMe\nimport parse from '../vendor/postcss-safe-parser/parse';\n\nlet generated = {};\n\nexport const resetStyleCache = () => {\n generated = {};\n};\n\n/*\n InlineStyle takes arbitrary CSS and generates a flat object\n */\nexport default (styleSheet: StyleSheet) => {\n class InlineStyle {\n   rules: RuleSet;\n\n   constructor(rules: RuleSet) {\n   this.rules = rules;\n   }\n\n   generateStyleObject(executionContext: Object) {\n   const flatCSS = flatten(this.rules, executionContext).join('');\n\n   const hash = generateComponentId(flatCSS);\n   if (!generated[hash]) {\n   const root = parse(flatCSS);\n   const declPairs = [];\n   root.each(node => {\n   if (node.type === 'decl') {\n   declPairs.push([node.prop, node.value]);\n   } else if (process.env.NODE_ENV !== 'production' && node.type !== 'comment') {\n   /* eslint-disable no-console */\n   console.warn(`Node of type ${node.type} not supported as an inline style`);\n   }\n   });\n   // RN currently does not support differing values for the corner radii of Image\n   // components (but does for View). It is almost impossible to tell whether we'll have\n   // support, so we'll just disable multiple values here.\n   // https://github.com/styled-components/css-to-react-native/issues/11\n   const styleObject = transformDeclPairs(declPairs,\n   [\n   'borderRadius',\n   'borderWidth',\n   'borderColor',\n   'borderStyle',\n   ]);\n   const styles = styleSheet.create({\n   generated: styleObject,\n   });\n   generated[hash] = styles.generated;\n   }\n   return generated[hash];\n   }\n }\n\n return InlineStyle;\n};\n","/* eslint-disable */\n/**\n * mixin-deep; https://github.com/jonschlinkert/mixin-deep\n * Inlined such that it will be consistently transpiled to an IE-compatible syntax.\n *\n * The MIT License (MIT)\n *\n * Copyright (c) 2014-present, Jon Schlinkert.\n *\n * Permission is hereby granted, free of charge, to any person obtaining a copy\n * of this software and associated documentation files (the \"Software\"), to deal\n * in the Software without restriction, including without limitation the rights\n * to use, copy, modify, merge, publish, distribute, sublicense, and/or sell\n * copies of the Software, and to permit persons to whom the Software is\n * furnished
 to do so, subject to the following conditions:\n\n The above copyright notice and this permission notice shall be included in\n all copies or substantial portions of the Software.\n\n THE SOFTWARE IS PROVIDED \"AS IS\", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR\n IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,\n FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE\n AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER\n LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,\n OUT OF OR IN CONNECTION WITH THE SOFTWARE OR

THE USE OR OTHER DEALINGS IN\n THE SOFTWARE.\n*/\n\nconst isObject = val => {\n return (\n   typeof val === 'function' || (typeof val === 'object' && val !== null && !Array.isArray(val))\n);\n};\n\nconst isValidKey = key => {\n return key !== '__proto__' && key !== 'constructor' && key !== 'prototype';\n};\n\nfunction mixin(target, val, key) {\n const obj = target[key];\n
  if (isObject(val) && isObject(obj)) {\n   mixinDeep(obj, val);\n } else {\n   target[key] = val;\n }\n}\n\nexport default function mixinDeep(target, ...rest) {\n for (const obj of rest) {\n   if (isObject(obj)) {\n   for (const key in obj) {\n   if (isValidKey(key)) {\n   mixin(target, obj[key], key);\n   }\n   }\n   }\n }\n\n return target;\n}\n","// @flow\nimport { EMPTY_OBJECT } from './empties';\n\ntype Props = {\n theme?: any,\n};\n\nexport default (props: Props, providedTheme: any, defaultProps: any = EMPTY_OBJECT) => {\n return (props.theme !== defaultProps.theme && props.theme) || providedTheme || defaultProps.theme;\n};\n","// @flow\nimport type { IStyledComponent } from '../types';\n\nexport default function isTag(target: $PropertyType<IStyledComponent, 'target'>): boolean %checks {\n return (\n   typeof target === 'string' &&\n   (process.env.NODE_ENV !== 'production'\n   ? target.charAt(0) === target.charAt(0).toLowerCase()\n   : true)\n);\n}\n","// @flow\nimport type { IStyledComponent } from '../types';\nimport getComponentName from './getComponentName';\nimport isTag from './isTag';\n\nexport default function generateDisplayName(\n target: $PropertyType<IStyledComponent, 'target'>\n): string {\n return isTag(target) ? `styled.${target}` : `Styled(${getComponentName(target)})`;\n}\n","// @flow\nimport React, { useContext, useMemo, type Element, type Context } from 'react';\nimport throwStyledError from '../utils/error';\nimport isFunction from '../utils/isFunction';\n\nexport type Theme = { [key: string]: mixed };\n\ntype ThemeArgument = Theme | ((outerTheme?: Theme) => Theme);\n\ntype Props = {\n children?: Element<any>,\n theme: ThemeArgument,\n};\n\nexport const ThemeContext: Context<Theme | void> = React.createContext();\n\nexport const ThemeConsumer = ThemeContext.Consumer;\n\nfunction mergeTheme(theme: ThemeArgument, outerTheme?: Theme): Theme {\n if (!theme) {\n   return throwStyledError(14);\n }\n\n if (isFunction(theme)) {\n   const mergedTheme = theme(outerTheme);\n\n   if (\n   process.env.NODE_ENV !== 'production' &&\n   (mergedTheme === null || Array.isArray(mergedTheme) || typeof mergedTheme !== 'object')\n   ) {\n   return throwStyledError(7);\n   }\n\n   return mergedTheme;\n }\n\n if (Array.isArray(theme) || typeof theme !== 'object') {\n   return throwStyledError(8);\n }\n\n return outerTheme ? { ...outerTheme, ...theme } : theme;\n}\n\n/**\n * Provide a theme to an entire react component tree via context\n */\nexport default function ThemeProvider(props: Props) {\n const outerTheme = useContext(ThemeContext);\n const themeContext = useMemo(() => mergeTheme(props.theme, outerTheme), [\n   props.theme,\n   outerTheme,\n]);\n\n if (!props.children) {\n   return null;\n }\n\n return <ThemeContext.Provider value={themeContext}>{props.children}</ThemeContext.Provider>;\n}\n","// @flow\nimport React, { createElement, Component } from
 'react';\nimport hoist from 'hoist-non-react-statics';\nimport merge from '../utils/mixinDeep';\nimport determineTheme from '../utils/determineTheme';\nimport { EMPTY_ARRAY, EMPTY_OBJECT } from '../utils/empties';\nimport generateDisplayName from '../utils/generateDisplayName';\nimport isFunction from '../utils/isFunction';\nimport isTag from '../utils/isTag';\nimport isStyledComponent from '../utils/isStyledComponent';\nimport { ThemeConsumer } from './ThemeProvider';\n\nimport type { Theme } from './ThemeProvider';\nimport type { Attrs, RuleSet, Target } from '../types';\n\n// NOTE: no hooks available for react-native yet;\n// if the user makes use of ThemeProvider or StyleSheetManager things will break.\n\n// Validator defaults to true if not in HTML/DOM env\nconst validAttr = () => true;\n\nclass StyledNativeComponent extends Component<*, *> {\n root: ?Object;\n\n attrs = {};\n\n render() {\n   return (\n   <ThemeConsumer>\n   {(theme?: Theme) => {\n   const {\n $as: transientAsProp,\n   as: renderAs,\n   forwardedComponent,\n   forwardedAs,\n   forwardedRef,\n   testID,\n   style = [],\n   ...props\n   } = this.props;\n\n   const { defaultProps, target, shouldForwardProp } = forwardedComponent;\n   const elementToBeRendered =\n   this.attrs.$as || this.attrs.as || transientAsProp || renderAs || target;\n\n   const generatedStyles = this.generateAndInjectStyles(\n   determineTheme(this.props, theme, defaultProps) || EMPTY_OBJECT,\n

```
  this.props\n  );\n\n  const isTargetTag = isTag(elementToBeRendered);\n  const computedProps =
this.attrs !== props ? { ...props, ...this.attrs } : props;\n  const propFilterFn = shouldForwardProp || (isTargetTag
&& validAttr);\n  const propsForElement = {};\n  let key;\n\n  for (key in computedProps) {\n
if (key[0] ===
'$' || key === 'as') continue;\n  else if (key === 'forwardedAs') {\n  propsForElement.as =
props[key];\n  } else if (!propFilterFn || propFilterFn(key, validAttr)) {\n  // Don't pass through filtered
tags through to native elements\n  propsForElement[key] = computedProps[key];\n  }\n  }\n\n
  propsForElement.style = typeof style === 'function' ?\n  (state) => {\n  return
[generatedStyles].concat(style(state))\n  }\n  : [generatedStyles].concat(style);\n
propsForElement.testID = testID || propsForElement.testID;\n\n  if (forwardedRef) propsForElement.ref =
forwardedRef;\n  if (forwardedAs) propsForElement.as = forwardedAs;\n\n  return
createElement(elementToBeRendered, propsForElement);\n  }}\n  </ThemeConsumer>\n  );\n  }\n\n
buildExecutionContext(theme: ?Object, props: Object, attrs: Attrs) {\n  const context = { ...props,
 theme };\n\n  if (!attrs.length) return context;\n\n  this.attrs = {};\n\n  attrs.forEach(attrDef => {\n  let
resolvedAttrDef = attrDef;\n  let attr;\n  let key;\n\n  if (isFunction(resolvedAttrDef)) {\n
resolvedAttrDef = resolvedAttrDef(context);\n  }\n\n  /* eslint-disable guard-for-in */\n  for (key in
resolvedAttrDef) {\n  attr = resolvedAttrDef[key];\n  this.attrs[key] = attr;\n  context[key] = attr;\n  }\n
  /* eslint-enable */\n  });\n\n  return context;\n  }\n\n  generateAndInjectStyles(theme: any, props: any) {\n
const { inlineStyle } = props.forwardedComponent;\n\n  const executionContext = this.buildExecutionContext(\n
 theme,\n  props,\n  props.forwardedComponent.attrs\n  );\n\n  return
inlineStyle.generateStyleObject(executionContext);\n  }\n\n  setNativeProps(nativeProps: Object) {\n  if (this.root
!== undefined) {\n  // $FlowFixMe\n  this.root.setNativeProps(nativeProps);\n
  } else if (process.env.NODE_ENV !== 'production') {\n  // eslint-disable-next-line no-console\n
console.warn(\n  'setNativeProps was called on a Styled Component wrapping a stateless functional
component.'\n  );\n  }\n  }\n}\n\nexport default (InlineStyle: Function) => {\n  const
createStyledNativeComponent = (target: Target, options: Object, rules: RuleSet) => {\n  const {\n  attrs =
EMPTY_ARRAY,\n  displayName = generateDisplayName(target),\n  ParentComponent =
StyledNativeComponent,\n  } = options;\n\n  const isClass = !isTag(target);\n  const isTargetStyledComp =
isStyledComponent(target);\n\n  // $FlowFixMe\n  const WrappedStyledNativeComponent =
React.forwardRef((props, ref) => (\n  <ParentComponent\n  {...props}\n
forwardedComponent={WrappedStyledNativeComponent}\n  forwardedRef={ref}\n  />\n  ));\n\n  const
finalAttrs =\n  // $FlowFixMe\n  isTargetStyledComp && target.attrs\n  ?
Array.prototype.concat(target.attrs,
 attrs).filter(Boolean)\n  : attrs;\n\n  // eslint-disable-next-line prefer-destructuring\n  let shouldForwardProp =
options.shouldForwardProp;\n\n  // $FlowFixMe\n  if (isTargetStyledComp && target.shouldForwardProp) {\n
if (shouldForwardProp) {\n  // compose nested shouldForwardProp calls\n  shouldForwardProp = (prop,
filterFn, elementToBeCreated) =>\n  // $FlowFixMe\n  target.shouldForwardProp(prop, filterFn,
elementToBeCreated) &&\n  options.shouldForwardProp(prop, filterFn, elementToBeCreated);\n  } else {\n
  // eslint-disable-next-line prefer-destructuring\n  shouldForwardProp = target.shouldForwardProp;\n  }\n
}\n\n  /**\n  * forwardRef creates a new interim component, which we'll take advantage of\n  * instead of
extending ParentComponent to create _another_ interim class\n  */\n\n  // $FlowFixMe\n
WrappedStyledNativeComponent.attrs = finalAttrs;\n\n
 WrappedStyledNativeComponent.displayName = displayName;\n\n  // $FlowFixMe\n
WrappedStyledNativeComponent.shouldForwardProp = shouldForwardProp;\n\n  // $FlowFixMe\n
WrappedStyledNativeComponent.inlineStyle = new InlineStyle(\n  // $FlowFixMe\n  isTargetStyledComp ?
target.inlineStyle.rules.concat(rules) : rules\n  );\n\n  // $FlowFixMe\n
WrappedStyledNativeComponent.styledComponentId = 'StyledNativeComponent';\n  // $FlowFixMe\n
WrappedStyledNativeComponent.target = isTargetStyledComp\n  ? // $FlowFixMe\n  target.target\n  :
```

target;\n // $FlowFixMe\n WrappedStyledNativeComponent.withComponent = function withComponent(tag: Target) {\n const { displayName: _, componentId: __, ...optionsToCopy } = options;\n const newOptions = {\n ...optionsToCopy,\n attrs: finalAttrs,\n ParentComponent,\n };\n\n return createStyledNativeComponent(tag, newOptions, rules);\n };\n\n // $FlowFixMe\n Object.defineProperty(WrappedStyledNativeComponent,
'defaultProps', {\n get() {\n return this._foldedDefaultProps;\n },\n\n set(obj) {\n // $FlowFixMe\n this._foldedDefaultProps = isTargetStyledComp ? merge({}, target.defaultProps, obj) : obj;\n },\n });\n\n if (isClass) {\n hoist(WrappedStyledNativeComponent, (target: any), {\n // all SC-specific things should not be hoisted\n attrs: true,\n displayName: true,\n shouldForwardProp: true,\n inlineStyle: true,\n styledComponentId: true,\n target: true,\n withComponent: true,\n });\n }\n\n return WrappedStyledNativeComponent;\n };\n\n return createStyledNativeComponent;\n};\n","// @flow\nimport type { Interpolation } from '../types';\n\nexport default (\n strings: Array<string>,\n interpolations: Array<Interpolation>\n): Array<Interpolation> => {\n const result = [strings[0]];\n\n for (let i = 0, len = interpolations.length;
i < len; i += 1) {\n result.push(interpolations[i], strings[i + 1]);\n }\n\n return result;\n};\n","// @flow\nimport interleave from '../utils/interleave';\nimport isPlainObject from '../utils/isPlainObject';\nimport { EMPTY_ARRAY } from '../utils/empties';\nimport isFunction from '../utils/isFunction';\nimport flatten from '../utils/flatten';\nimport type { Interpolation, RuleSet, Styles } from '../types';\n\n/**\n * Used when flattening object styles to determine if we should\n * expand an array of styles.\n */\nconst addTag = arg => {\n if (Array.isArray(arg)) {\n // eslint-disable-next-line no-param-reassign\n arg.isCss = true;\n }\n return arg;\n};\n\nexport default function css(styles: Styles, ...interpolations: Array<Interpolation>): RuleSet {\n if (isFunction(styles) || isPlainObject(styles)) {\n // $FlowFixMe\n return addTag(flatten(interleave(EMPTY_ARRAY, [styles, ...interpolations])));\n }\n\n if (interpolations.length === 0 && styles.length === 1 &&
typeof styles[0] === 'string') {\n // $FlowFixMe\n return styles;\n }\n\n // $FlowFixMe\n return addTag(flatten(interleave(styles, interpolations)));\n}\n","// @flow\nimport { isValidElementType } from 'react-is';\nimport css from './css';\nimport throwStyledError from '../utils/error';\nimport { EMPTY_OBJECT } from '../utils/empties';\n\nimport type { Target } from '../types';\n\nexport default function constructWithOptions(\n componentConstructor: Function,\n tag: Target,\n options: Object = EMPTY_OBJECT\n) {\n if (!isValidElementType(tag)) {\n return throwStyledError(1, String(tag));\n }\n\n /* This is callable directly as a template function */\n // $FlowFixMe: Not typed to avoid destructuring arguments\n const templateFunction = (...args) => componentConstructor(tag, options, css(...args));\n\n /* If config methods are called, wrap up a new template function and merge options */\n templateFunction.withConfig = config =>\n constructWithOptions(componentConstructor,
tag, { ...options, ...config });\n\n /* Modify/inject new props at runtime */\n templateFunction.attrs = attrs =>\n constructWithOptions(componentConstructor, tag, {\n ...options,\n attrs: Array.prototype.concat(options.attrs, attrs).filter(Boolean),\n });\n\n return templateFunction;\n}\n","// @flow\nimport React, { useContext, type AbstractComponent } from 'react';\nimport hoistStatics from 'hoist-non-react-statics';\nimport { ThemeContext } from '../models/ThemeProvider';\nimport determineTheme from '../utils/determineTheme';\nimport getComponentName from '../utils/getComponentName';\n\n// NOTE: this would be the correct signature:\n// export default <Config: { theme?: any }, Instance>(\n// Component: AbstractComponent<Config, Instance>\n//): AbstractComponent<$Diff<Config, { theme?: any }> & { theme?: any }, Instance>\n//\n// but the old build system tooling doesn't support the syntax\n\nexport default (Component: AbstractComponent<*, *>) => {\n // $FlowFixMe
This should be React.forwardRef<Config, Instance>\n const WithTheme = React.forwardRef((props, ref) => {\n const theme = useContext(ThemeContext);\n // $FlowFixMe defaultProps isn't declared so it can be inferrable\n const { defaultProps } = Component;\n const themeProp = determineTheme(props, theme, defaultProps);\n\n if (process.env.NODE_ENV !== 'production' && themeProp === undefined) {\n // eslint-disable-next-line no-console\n console.warn(\n `[withTheme] You are not using a ThemeProvider nor passing a theme prop or a

theme in defaultProps in component class \"${getComponentName(\n Component\n)}\"`\n );\n }\n\n return <Component {...props} theme={themeProp} ref={ref} />;\n });\n\n hoistStatics(WithTheme, Component);\n\n WithTheme.displayName = `WithTheme(${getComponentName(Component)})`;\n\n return WithTheme;\n};\n","// @flow\nimport { useContext } from 'react';\nimport { ThemeContext } from '../models/ThemeProvider';\n\nconst
useTheme = () => useContext(ThemeContext);\n\nexport default useTheme;\n","// @flow\n\n/* eslint-disable import/no-unresolved */\nimport reactPrimitives from 'react-primitives';\n\nimport _InlineStyle from '../models/InlineStyle';\nimport _StyledNativeComponent from '../models/StyledNativeComponent';\n\nimport css from '../constructors/css';\nimport constructWithOptions from '../constructors/constructWithOptions';\nimport ThemeProvider, { ThemeConsumer, ThemeContext } from '../models/ThemeProvider';\nimport withTheme from '../hoc/withTheme';\nimport useTheme from '../hooks/useTheme';\nimport isStyledComponent from '../utils/isStyledComponent';\n\nimport type { Target } from '../types';\n\nconst InlineStyle = _InlineStyle(reactPrimitives.StyleSheet);\nconst StyledNativeComponent = _StyledNativeComponent(InlineStyle);\nconst styled = (tag: Target) => constructWithOptions(StyledNativeComponent, tag);\n\n/* React native lazy-requires each of these modules for some reason,
so let's\n * assume it's for a good reason and not eagerly load them all */\nconst aliases = 'Image Text Touchable View ';\n\n/* Define a getter for each alias which simply gets the reactNative component\n * and passes it to styled */\naliases.split(/\\s+/m).forEach(alias =>\n Object.defineProperty(styled, alias, {\n enumerable: true,\n configurable: false,\n get() {\n return styled(reactPrimitives[alias]);\n },\n })\n);\n\nexport { css, isStyledComponent, ThemeProvider, ThemeConsumer, ThemeContext, withTheme, useTheme };\nexport default styled;\n"],"names":["AD_REPLACER_R","charsLength","getAlphabeticChar","code","String","fromCharCode","generateAlphabeticName","name","x","Math","abs","replace","SEED","phash","h","i","length","charCodeAt","hash","str","getComponentName","target","process","env","NODE_ENV","displayName","isFunction","test","isStatelessFunction","prototype","isReactComponent","toString","Object","call","typeOf","isStyledComponent","styledComponentId","SC_ATTR","REACT_APP_SC_ATTR","SC_ATTR_ACTIVE","SC_ATTR_VERSION","SC_VERSION","__VERSION__","SPLITTER","IS_BROWSER","window","DISABLE_SPEEDY","Boolean","SC_DISABLE_SPEEDY","REACT_APP_SC_DISABLE_SPEEDY","EMPTY_ARRAY","freeze","EMPTY_OBJECT","ERRORS","errorMap","format","a","b","c","len","push","forEach","d","throwStyledComponentsError","interpolations","Error","join","trim","makeGroupedTag","tag","DefaultGroupedTag","BASE_SIZE","groupSizes","Uint32Array","indexOfGroup","group","index","insertRules","rules","oldBuffer","oldSize","newSize","throwStyledError","set","ruleIndex","l","insertRule","clearGroup","startIndex","endIndex","deleteRule","getGroup","css","getRule","MAX_SMI","groupIDRegister","Map","reverseRegister","nextFreeGroup","getGroupForId","id","has","get","getIdForGroup","setGroupForId","SELECTOR","MARKER_RE","RegExp","outputSheet","sheet","getTag","undefined","names","size","selector","content","rehydrateNamesFromContent","split","registerName","rehydrateSheetFromTag","style","parts","textContent","part","marker","match","parseInt","rehydrateSheet","nodes","document","querySelectorAll","node","getAttribute","parentNode","removeChild","getNonce","__webpack_nonce__","ELEMENT_TYPE","findLastStyleTag","childNodes","child","nodeType","hasAttribute","makeStyleTag","head","parent","createElement","prevStyle","nextSibling","setAttribute","nonce","insertBefore","getSheet","styleSheets","ownerNode","makeTag","isServer","useCSSOMInjection","VirtualTag","CSSOMTag","TextTag","element","appendChild","createTextNode","rule","_error","cssRules","cssText","refNode","_target","splice","SHOULD_REHYDRATE","defaultOptions","StyleSheet","registerId","options","globalStyles","gs","server","reconstructWithOptions","withNames","allocateGSInstance","hasNameForId","groupNames","Set","add","clearNames","clear","clearRules","clearTag","delimiter","needle","toSheet","block","e","ruleSheet","context","selectors","parents","line","column","ns","depth","at","COMMENT_REGEX","COMPLEX_SELECTOR_PREFIX","createStylisInstance","plugins","stylis","Stylis","parsingRules","returnRulesPlugin","parsedRules","parseRulesPlugin","insertRulePlugin","_componentId","_selector","_selectorRegexp","_consecutiveSelfRefRegExp","selfReferenceReplacer","offset","string","indexOf","selfReferenceReplacementPlugin","_","lastIndexOf","use","stringifyRules","prefix","componentId","flatCSS","cssStr","reduce","acc","plugin","Sty

leSheetContext","React","createContext","StyleSheetConsumer","Consumer","StylisContext","StylisConsumer","masterSheet","masterStylis","Keyframes","inject","styleSheet","stylisInstance","resolvedName","getName","uppercaseCheck","uppercasePattern","msPattern","prefixAndLowerCase","char","toLowerCase","hyphenateStyleName","addUnitIfNeeded","value","unitless","startsWith","isFalsish","chunk","objToCssArray","obj","prevKey","key","hasOwnProperty","Array","isArray","isCss","hyphenate","isPlainObject","flatten","executionContext","ruleSet","result","isElement","console","warn","printed","warnOnce","message","SINGLE_QUOTE","DOUBLE_QUOTE","BACKSLASH","SLASH","NEWLINE","SPACE","FEED","TAB","CR","OPEN_SQUARE","CLOSE_SQUARE","OPEN_PARENTHESES","CLOSE_PARENTHESES","OPEN_CURLY","CLOSE_CURLY","SEMICOLON","ASTERISK","COLON","AT","RE_AT_END","RE_WORD_END","RE_BAD_BRACKET","tokenize","input","tokens","valueOf","ignore","ignoreErrors","next","quote","lines","last","escape","nextLine","nextOffset","escaped","escapePos","prev","n","pos","unclosed","what","error","slice","lastIndex","HIGHLIGHT_THEME","brackets","comment","color","terminalHighlight","Input","token","map","CssSyntaxError","source","file","reason","setMessage","captureStackTrace","showSourceCode","supportsColor","start","max","end","min","maxWidth","number","padded","gutter","spacing","defaultRaw","colon","indent","beforeDecl","beforeRule","beforeOpen","beforeClose","beforeComment","after","emptyBody","commentLeft","commentRight","capitalize","toUpperCase","Stringifier","builder","stringify","semicolon","type","root","body","raws","left","raw","right","text","decl","between","prop","rawValue","important","atrule","params","afterName","before","own","detect","first","rawCache","beforeAfter","method","walk","rawSemicolon","rawEmptyBody","rawIndent","p","rawBeforeComment","walkComments","rawBeforeDecl","walkDecls","rawBeforeRule","rawBeforeClose","rawBeforeOpen","rawColon","buf","step","cloneNode","cloned","constructor","j","Node","defaults","opts","positionBy","data","remove","stringifier","clone","overrides","cloneBefore","cloneAfter","insertAfter","replaceWith","moveTo","newParent","cleanRaws","append","moveBefore","otherNode","moveAfter","toJSON","fixed","defaultType","keepBetween","positionInside","word","removeSelf","cleanStyles","val","Declaration","Comment","Parser","Root","current","spaces","tokenizer","loop","emptyRule","other","endFile","init","Rule","bracket","pop","unclosedBracket","unknownWord","spacesFromEnd","shift","spacesFromStart","precheckMissedSemicolon","stringFrom","cache","checkMissedSemicolon","AtRule","unnamedAtrule","open","unexpectedClose","unclosedBlock","clean","all","lastTokenType","from","doubleColon","founded","parse","safe","parser","cleanSource","Container","each","callback","lastEach","indexes","walkRules","walkAtRules","children","normalize","prepend","reverse","unshift","exist","removeAll","replaceValues","pattern","props","fast","every","condition","some","sample","processed","rebuild","fix","eachInside","eachDecl","eachRule","eachAtRule","eachComment","list","separators","array","func","letter","space","comma","values","sep","Warning","opt","Result","processor","messages","lastPlugin","postcssPlugin","warning","warnings","filter","isPromise","then","LazyResult","stringified","inline","syntax","sync","onFulfilled","onRejected","async","handleError","postcssVersion","pluginName","pluginVer","runtimeVer","version","err","asyncTick","resolve","reject","promise","run","Promise","processing","Processor","concat","normalized","postcss","toResult","lazy","prevMap","sequence","path","origin","consumer","originalPositionFor","mapResolve","sourceContentFor","sourceRoot","SafeParser","buffer","safeParse","generated","InlineStyle","generateStyleObject","generateComponentId","declPairs","styleObject","transformDeclPairs","styles","create","isObject","isValidKey","mixin","mixinDeep","rest","providedTheme","defaultProps","theme","isTag","charAt","generateDisplayName","ThemeContext","ThemeConsumer","mergeTheme","outerTheme","mergedTheme","ThemeProvider","useContext","themeContext","useMemo","validAttr","StyledNativeComponent","attrs","render","transientAsProp","$as","renderAs","as","forwardedComponent","forwardedAs","forwardedRef","testID","shouldForwardProp","elementToBeRendered","generatedStyles","generateAndInjectStyles","determineTheme","isTargetTag","computedProps","propFilterFn","propsForElement","state","ref","buildExecutionContext","attrDef","resolvedAttrDef","attr","inlineStyle","setNativeProps","nativeProps","Component","createStyledNativeComponent","ParentComponent","isClass","isTargetStyledComp","WrappedStyledNativeComponent","forwardRef","finalAttrs","filterFn","elementToBeCreated","withComponent","__","optionsToCopy","newOptions","defineProperty","_foldedDefaultProps","merge","hoist","strings","addTag","arg","interleave","constructWithOptions","componentConstructor","isValidElementType","templateFunction","withConfig","config","WithTheme","themeProp","hoistStatics","useTheme","_InlineStyle","reactPrimitives","_StyledNativeComponent","styled","aliases","alias","enumerable","configurable"],"mappings":";;

;;;;;;;;AAAA;;AACA;AAEA,IAAMA,aAAa,GAAG,UAAtB;AAEA;;;AAEA,IAAMC,WAAW,GAAG,EAApB;AAEA;;AACA,IAAMC,iBAAiB,GAAG,SAApBA,iBAAoB,CAACC,IAAD;AAAA,SACxBC,MAAM,CAACC,YAAP,CAAoBF,IAApB,CADwB;AAAA,CAA1B;;AAGA,SAASG,eAAT,CAAyBC,KAAzB,EAAgC;AAC9B,MAAIC,GAAG,GAAG,EAAV;AAAA,MACEC,CAAC,GAAG,CADN;AAAA,MAEEC,MAAM,GAAGH,KAAK,CAACG,MAFjB;AAAA,MAGEC,IAHF;AAAA,MAIEC,IAJF;AAAA,MAKEC,IALF;AAAA,MAMEC,IANF;AAAA,MAOEC,IAPF;AAAA,MAQEC,IARF;;AAUA,SAAOP,CAAC,GAAGC,MAAX,EAAmB;AACjBE,QAAI,GAAGL,KAAK,CAACU,UAAN,CAAiBR,CAAC,EAAlB,CAAP;AACAI,QAAI,GAAGN,KAAK,CAACU,UAAN,CAAiBR,CAAC,EAAlB,CAAP;AACAK,QAAI,GAAGP,KAAK,CAACU,UAAN,CAAiBR,CAAC,EAAlB,CAAP;AACAM,QAAI,GAAGR,KAAK,CAACU,UAAN,CAAiBR,CAAC,EAAlB,CAAP;AACAO,QAAI,GAAGT,KAAK,CAACU,UAAN,CAAiBR,CAAC,EAAlB,CAAP;AACAQ,QAAI,GAAGV,KAAK,CAACU,UAAN,CAAiBR,CAAC,EAAlB,CAAP;;AAEA,QAAIE,IAAI,IAAI,EAAR,IAAcA,IAAI,IAAI,EAAtB,IAA4BA,IAAI,IAAI,EAAxC,EAA4C;AAC1CA,UAAI,GAAG,CAACA,IAAI,GAAG,EAAR,KAAe,EAAf,GAAoBC,IAAI,GAAG,EAA3B,KAAkC,EAAlC,GAAuCC,IAAI,GAAG,EAA9C,KAAqD,CAArD,GAAyDC,IAAI,GAAG,EAAvE;AACAL,UAAI,GAAG,CAACA,IAAI,GAAG,EAAR,KAAe,EAAf,GAAoBC,IAAI,GAAG,EAA3B,KAAkC,EAAlC,GAAuCC,IAAI,GAAG,EAA9C,KAAqD,CAArD,GAAyDC,IAAI,GAAG,EAAvE;AACAJ,UAAI,GAAG,CAACA,IAAI,GAAG,EAAR,KAAe,EAAf,GAAoBC,IAAI,GAAG,EAA3B,KAAkC,EAAlC,GAAuCC,IAAI,GAAG,EAA9C,KAAqD,CAArD,GAAyDC,IAAI,GAAG,EAAvE;AACAH,UAAI,GAAG,CAACA,IAAI,GAAG,EAAR,KAAe,EAAf,GAAoBC,IAAI,GAAG,EAA3B,KAAkC,EAAlC,GAAuCC,IAAI,GAAG,EAA9C,KAAqD,CAArD,GAAyDC,IAAI,GAAG,EAAvE;AACAT,SAAG,IAAIE,iBAAiB,CAACI,IAAD,CAAxB;AACAA,UAAI,GAAG,CAAP;AACD;AACF;;AAED,MAAIA,IAAI,KAAK,CAAb,EAAgB;AACdA,QAAI,GAAG,CAACA,IAAI,GAAG,EAAR,KAAe,EAAf,GAAoBC,IAAI,GAAG,EAA3B,KAAkC,EAAlC,GAAuCC,IAAI,GAAG,EAA9C,KAAqD,CAA5D;AACAL,OAAG,IAAIE,iBAAiB,CAACI,IAAD,CAAxB;AACAA,QAAI,GAAG,CAAP;AACD

oD;AAClDD,IAAAA,CAAC,CAACG,IAAF,CAAYF,CAAZ,4BAAYA,CAAZ,yBAAYA,CAAZ;AACD;;AAEDD,EAAAA,CAAC,CAACI,OAAF,CAAU,UAAAC,CAAC,EAAI;AACbN,IAAAA,CAAC,GAAGA,CAAC,CAAC7C,OAAF,CAAU,QAAAV,EAAAoBmD,CAApB,CAAAJ;AACD,GAFD;AAIA,SAASO,0BAAT,CAAoCC,EAApC,EAAwC;AAAA,oCAAAC,IAAA;AAAAA,MAAAA,IAAA;AAAA;;AACtC,WAAOA,IAAI,CAACC,MAAL,CAAY,UAAAC,CAAC,EAAI;AACtB,aAAOH,EAAE,CAACG,CAAD,CAAT;AACD,KAFM,CAAP;AAGD;AAED,SAASC,kBAAT,CAA4BC,GAA5B,EAAiC;AAC/B,MAAIC,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGF,GAAG,CAACG,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGP,GAAG,CAACK,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGR,GAAG,CAACK,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGT,GAAG,CAACK,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGV,GAAG,CAACK,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASc,kBAAT,CAA4BC,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASgB,kBAAT,CAA4BD,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASiB,kBAAT,CAA4BF,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASkB,kBAAT,CAA4BH,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASmB,kBAAT,CAA4BJ,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASoB,kBAAT,CAA4BL,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASqB,kBAAT,CAA4BN,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASsB,kBAAT,CAA4BP,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASuB,kBAAT,CAA4BR,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASwB,kBAAT,CAA4BT,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASyB,kBAAT,CAA4BV,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAAS0B,kBAAT,CAA4BX,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAAS2B,kBAAT,CAA4BZ,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAAS4B,kBAAT,CAA4Bb,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAAS6B,kBAAT,CAA4Bd,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAAS8B,kBAAT,CAA4Bf,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAAS+B,kBAAT,CAA4BhB,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASgC,kBAAT,CAA4BjB,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASiC,kBAAT,CAA4BlB,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASkC,kBAAT,CAA4BnB,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASmC,kBAAT,CAA4BpB,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;AACAK,IAAAA,EAAE,GAAGM,GAAG,CAACX,CAAC,EAAF,CAAR;AACAE,IAAAA,IAAI,GAAGC,EAAE,IAAI,CAAN,GAAWC,EAAE,GAAG,EAAN,KAAc,CAAxB,GAAgCC,EAAE,GAAG,EAAN,KAAc,CAAjD;AACAR,IAAAA,IAAI,CAACW,IAAL,CAAUC,MAAM,CAACC,YAAP,CAAoBR,IAAI,IAAI,EAAR,GAAc,IAAjC,EAAuCA,IAAI,IAAI,EAAR,GAAc,IAAnD,EAAyDA,IAAI,GAAG,IAAhE,CAAV;AACD;;AACD,SAAOL,IAAP;AACD;AAED,SAASoC,kBAAT,CAA4BrB,GAA5B,EAAiC;AAC/B,MAAIf,IAAI,GAAG,EAAX;AAAA,MACEC,GAAG,GAAGc,GAAG,CAACb,MADZ;AAAA,MAEEC,CAAC,GAAG,CAFN;AAAA,MAGEC,IAHF;AAAA,MAIEC,EAJF;AAAA,MAKEC,EALF;AAAA,MAMEC,EANF;AAAA,MAOEC,EAPF;;AAQA,SAAOL,CAAC,GAAGF,GAAX,EAAgB;AACdI,IAAAA,EAAE,GAAGS,GAAG,CAACX,CAAC,EAAF,CAAR;AACAG,IAAAA,EAAE,GAAGQ,GAAG,CAACX,CAAC,EAAF,CAAR;AACAI,IAAAA,EAAE,GAAGO,GAAG,CAACX,CAAC,EAAF,CAAR;

B,aAAa,GAAG,SAAhBA,aAAgB,CAAC5B,KAAD,EAAkC;AAC7D,SAAOsB,eAAe,CAACK,GAAhB,CAAoB3
B,KAApB,CAAP;AACD,CAFM;AAIP,AAAO,IAAM6B,aAAa,GAAG,SAAhBA,aAAgB,CAACJ,EAAD,EAAazB
,KAAb,EAA+B;AAC1D,MAAIA,KAAK,IAAIuB,aAAb,EAA4B;AAC1BA,IAAAA,aAAa,GAAGvB,KAAK,GAAG,CAAxB;AACD;;AAEDoB,EAAAA,eAAe,CAACZ,GAAhB,CAAoBiB,EAApB,EAAwBzB,KAAxB;AACAsB,E
AAAA,eAAe,CAACd,GAAhB,CAAoBR,KAApB,EAA2ByB,EAA3B;AACD,CAPM;;AC3CP;AAEA,AAIA,IAAA
MK,QAAQ,cAAAYpE,OAAAZ,UAAAwBG,eAAAxB,WAA4CC,UAA5C,QAAAd;AACA,IAAAMiE,SAAAS,GAAAG,IAAAIC,
MAAJ,OAAAetE,OAAAf,sDAAAlB;AAEA,AAAO,IAAMuuE,WAAAW,GAAAG,SAAAdA,WAAAc,CAAAC,KAAAD,EAAAb;AAkB
;AAC3C,MAAMxC,GAAAG,GAAAGwC,KAAAK,CAACC,MAAAN,EAAAZ;AAD2C,MAAEnC9F,MAAFmC,GAAAG,GAAAG,GAAAG,EAAAV;;AACA,OAAAK,IAAAIjB,KAAAK,GAAAG,CAAAj
B,EAAAoBA,KAAAK,GAAAG3D,MAA5B,EAAAoC2D,KAAAK,GAAAG,EAA6C;AAC3C,QAAAMyB,EAAAE,GAAAG,a
AAa,CAAC5B,KAAD,CAAAxB;AACA,IAAAC,QAAAIyB,EAAAE,KAAAW,KAAAC,EAAAsB;AAEtB,QAAAMC,KAAAK,GAAAG,H,KAAAK,CAACG,KAAAN,EAAAZ,CAAd;AAAA,QAAAmB,KAAAK,GAAAG,CAAAC,KAAAD,EAAAb,CAAAC,KAAAD,EAAAb

AIA,KAAK,CAACC,QAAN,KAAmBJ,YAA5B,IAA4CG,KAAK,CAACE,YAAN,CAAmBzG,OAAnB,CAAhD,EAA6E;AAC3E,aAASuG,KAAT;AACD;AACF;;AAED,SAAO7B,SAAP;AACD,CAXD;AAaA;;;AACA,CAAAO,IAAMgC,YAAAY,GAAAG,SAAAfA,IAAAgB,EAAA4C;AACtE,MAAM2H,IAAI,GAAAKf,QAAAe,EAAAxB,CAAAwB,IAAAxB,CAAAwB,IAAAxB,CAAAwB,I

H;;AAAA,UAoBE0E,UApBF,GAoBE,oBAAWd,KAAX,EAAgC;AAC9B,SAAKE,KAAL,CAAW4F,MAAX,CAAkB9F,KAAlB,EAAyB,CAAzB;AACA,SAAK5D,MAAL;AACD,GAvBH;;AAAA,UAyBE6E,OAzBF,GAyBE,iBAAQjB,KAAR,EAA+B;AAC7B,SAAKE,KAAL,CAAWC,QAAX,CAAoBH,KAAK8D,MAAzB,EAAiC,CAAjC;AACA,SAAK5D,KAAL,CAAWC,QAAX,CAAoBH,KAAK+D,MAAzB,EAAiC,CAAjC;AACA,SAAK7D,KAAL,CAAWC,QAAX,CAAoBH,KAAKgE,MAAzB,EAAiC,CAAjC;AACA,SAAK9D,KAAL,CAAWC,QAAX,CAAoBH,KAAKiE,MAAzB,EAAiC,CAAjC;AACA,SAAK/D,KAAL,CAAWC,QAAX,CAAoBH,KAAKkE,MAAzB,EAAiC,CAAjC;AACA,SAAKhE,KAAL,CAAWC,QAAX,CAAoBH,KAAKmE,MAAzB,EAAiC,CAAjC;AACA,SAAKjE,KAAL,CAAWC,QAAX,CAAoBH,KAAKoE,MAAzB,EAAiC,CAAjC;AACA,SAAKlE,KAAL,CAAWC,QAAX,CAAoBH,KAAKqE,MAAzB,EAAiC,CAAjC;AACA,SAAKnE,KAAL,CAAWC,QAAX,CAAoBH,KAAKsE,MAAzB,EAAiC,CAAjC;AACA,SAAKpE,KAAL,CAAWC,QAAX,CAAoBH,KAAKuE,MAAzB,EAAiC,CAAjC;AACA,SAAKrE,KAAL,CAAWC,QAAX,CAAoBH,KAAKwE,MAAzB,EAAiC,CAAjC;AACA,SAAKtE,KAAL,CAAWC,QAAX,CAAoBH,KAAKyE,MAAzB,EAAiC,CAAjC;AACA,SAAKvE,KAAL,CAAWC,QAAX,CAAoBH,KAAK0E,MAAzB,EAAiC,CAAjC;AACA,SAAKxE,KAAL,CAAWC,QAAX,CAAoBH,KAAK2E,MAAzB,EAAiC,CAAjC;AACA,SAAKzE,KAAL,CAAWC,QAAX,CAAoBH,KAAK4E,MAAzB,EAAiC,CAAjC;AACA,SAAK1E,KAAL,CAAWC,QAAX,CAAoBH,KAAK6E,MAAzB,EAAiC,CAAjC;AACA,SAAK3E,KAAL,CAAWC,QAAX,CAAoBH,KAAK8E,MAAzB,EAAiC,CAAjC;AACA,SAAK5E,KAAL,CAAWC,QAAX,CAAoBH,KAAK+E,MAAzB,EAAiC,CAAjC;AACA,SAAK7E,KAAL,CAAWC,QAAX,CAAoBH,KAAKgF,MAAzB,EAAiC,CAAjC;AACA,SAAK9E,KAAL,CAAWC,QAAX,CAAoBH,KAAKiF,MAAzB,EAAiC,CAAjC;AACA,SAAK/E,KAAL,CAAWC,QAAX,CAAoBH,KAAKkF,MAAzB,EAAiC,CAAjC;AACA,SAAKhF,KAAL,CAAWC,QAAX,CAAoBH,KAAKmF,MAAzB,EAAiC,CAAjC;AACA,SAAKjF,KAAL,CAAWC,QAAX,CAAoBH,KAAKoF,MAAzB,EAAiC,CAAjC;AACA,SAAKlF,KAAL,CAAWC,QAAX,CAAoBH,KAAKqF,MAAzB,EAAiC,CAAjC;AACA,SAAKnF,KAAL,CAAWC,QAAX,CAAoBH,KAAKsF,MAAzB,EAAiC,CAAjC;AACA,SAAKpF,KAAL,CAAWC,QAAX,CAAoBH,KAAKuF,MAAzB,EAAiC,CAAjC;AACA,SAAKrF,KAAL,CAAWC,QAAX,CAAoBH,KAAKwF,MAAzB,EAAiC,CAAjC;AACA,SAAKtF,KAAL,CAAWC,QAAX,CAAoBH,KAAKyF,MAAzB,EAAiC,CAAjC;AACA,SAAKvF,KAAL,CAAWC,QAAX,CAAoBH,KAAK0F,MAAzB,EAAiC,CAAjC;AACA,SAAKxF,KAAL,CAAWC,QAAX,CAAoBH,KAAK2F,MAAzB,EAAiC,CAAjC;AACA,SAAKzF,KAAL,CAAWC,QAAX,CAAoBH,KAAK4F,MAAzB,EAAiC,CAAjC;AACA,SAAK1F,KAAL,CAAWC,QAAX,CAAoBH,KAAK6F,MAAzB,EAAiC,CAAjC;AACA,SAAK3F,KAAL,CAAWC,QAAX,CAAoBH,KAAK8F,MAAzB,EAAiC,CAAjC;AACA,SAAK5F,KAAL,CAAWC,QAAX,CAAoBH,KAAK+F,MAAzB,EAAiC,CAAjC;AACA,SAAK7F,KAAL,CAAWC,QAAX,CAAoBH,KAAKgG,MAAzB,EAAiC,CAAjC;AACA,SAAK9F,KAAL,CAAWC,QAAX,CAAoBH,KAAKiG,MAAzB,EAAiC,CAAjC;AACA,SAAK/F,KAAL,CAAWC,QAAX,CAAoBH,KAAKkG,MAAzB,EAAiC,CAAjC;AACA,SAAKhG,KAAL,CAAWC,QAAX,CAAoBH,KAAKmG,MAAzB,EAAiC,CAAjC;AACA,SAAKjG,KAAL,CAAWC,QAAX,CAAoBH,KAAKoG,MAAzB,EAAiC,CAAjC;AACA,SAAKlG,KAAL,CAAWC,QAAX,CAoBE6E,OAzBF,GAyBE,iBAAQjB,KAAR,EAA+B;AAC7B,SAAKE,KAAL,CAAWC,QAAX,CAAoBH,KAAK8D,MAAzB,EAAiC,CAAjC;AACA,SAAK5D,KAAL,CAAWC,QAAX,CAAoBH,KAAK+D,MAAzB,EAAiC,CAAjC;AACA,SAAK7D,KAAL,CAAWC,QAAX,CAAoBH,KAAKgE,MAAzB,EAAiC,CAAjC;AACA,SAAK9D,KAAL,CAAWC,QAAX,CAAoBH,KAAKiE,MAAzB,EAAiC,CAAjC;AACA,SAAK/D,KAAL,CAAWC,QAAX,CAAoBH,KAAKkE,MAAzB,EAAiC,CAAjC;AACA,SAAKhE,KAAL,CAAWC,QAAX,CAAoBH,KAAKmE,MAAzB,EAAiC,CAAjC;AACA,SAAKjE,KAAL,CAAWC,QAAX,CAAoBH,KAAKoE,MAAzB,EAAiC,CAAjC;AACA,SAAKlE,KAAL,CAAWC,QAAX,CAAoBH,KAAKqE,MAAzB,EAAiC,CAAjC;AACA,SAAKnE,KAAL,CAAWC,QAAX,CAAoBH,KAAKsE,MAAzB,EAAiC,CAAjC;AACA,SAAKpE,KAAL,CAAWC,QAAX,CAAoBH,KAAKuE,MAAzB,EAAiC,CAAjC;AACA,SAAKrE,KAAL,CAAWC,QAAX,CAAoBH,KAAKwE,MAAzB,EAAiC,CAAjC;AACA,SAAKtE,KAAL,CAAWC,QAAX,CAAoBH,KAAKyE,MAAzB,EAAiC,CAAjC;AACA,SAAKvE,KAAL,CAAWC,QAAX,CAAoBH,KAAK0E,MAAzB,EAAiC,CAAjC;AACA,SAAKxE,KAAL,CAAWC,QAAX,CAAoBH,KAAK2E,MAAzB,EAAiC,CAAjC;AACA,SAAKzE,KAAL,CAAWC,QAAX,CAAoBH,KAAK4E,MAAzB,EAAiC,CAAjC;AACA,SAAK1E,KAAL,CAAWC,QAAX,CAAoBH,KAAK6E,MAAzB,EAAiC,CAAjC;AACA,SAAK3E,KAAL,CAAWC,QAAX,CAAoBH,KAAK8E,MAAzB,EAAiC,CAAjC;AACA,SAAK5E,KAAL,CAAWC,QAAX,CAAoBH,KAAK+E,MAAzB,EAAiC,CAAjC;AACA,SAAK7E,KAAL,CAAWC,QAAX,CAAoBH,KAAKgF,MAAzB,EAAiC,CAAjC;AACA,SAAK9E,KAAL,CAAWC,QAAX,CAAoBH,KAAKiF,MAAzB,EAAiC,CAAjC;AACA,SAAK/E,KAAL,CAAWC,QAAX,CAAoBH,KAAKkF,MAAzB,EAAiC,CAAjC;AACA,SAAKhF,KAAL,CAAWC,QAAX,CAAoBH,KAAKmF,MAAzB,EAAiC,CAAjC;AACA,SAAKjF,KAAL,CAAWC,QAAX,CAAoBH,KAAKoF,MAAzB,EAAiC,CAAjC;AACA,SAAKlF,KAAL,CAAWC,QAAX,CAAoBH,KAAKqF,MAAzB,EAAiC,CAAjC;AACA,SAAKnF,KAAL,CAAWC,QAAX,CAAoBH,KAAKsF,MAAzB,EAAiC,CAAjC;AACA,SAAKpF,KAAL,CAAWC,QAAX,CAAoBH,KAAKuF,MAAzB,EAAiC,CAAjC;AACA,SAAKrF,KAAL,CAAWC,QAAX,CAAoBH,KAAKwF,MAAzB,EAAiC,CAAjC;AACA,SAAKtF,KAAL,CAAWC,QAAX,CAAoBH,KAAKyF,MAAzB,EAAiC,CAAjC;AACA,SAAKvF,KAAL,CAAWC,QAAX,CAAoBH,KAAK0F,MAAzB,EAAiC,CAAjC;AACA,SAAKxF,KAAL,CAAWC,QAAX,CAAoBH,KAAK2F,MAAzB,EAAiC,CAAjC;AACA,SAAKzF,KAAL,CAAWC,QAAX,CAAoBH,KAAK4F,MAAzB,EAAiC,CAAjC;AACA,SAAK1F,KAAL,CAAWC,QAAX,CAAoBH,KAAK6F,MAAzB,EAAiC,CAAjC;AACA,SAAK3F,KAAL,CAAWC,QAAX,CAAoBH,KAAK8F,MAAzB,EAAiC,CAAjC;AACA,SAAK5F,KAAL,CAAWC,QAAX,CAAoBH,KAAK+F,MAAzB,EAAiC,CAAjC;AACA,SAAK7F,KAAL,CAAWC,QAAX,CAAoBH,KAAKgG,MAAzB,EAAiC,CAAjC;AACA,SAAK9F,KAAL,CAAWC,QAAX,CAAoBH,KAAKiG,MAAzB,EAAiC,CAAjC;AACA,SAAK/F,KAAL,CAAWC,QAAX,CAAoBH,KAAKkG,MAAzB,EAAiC,CAAjC;AACA,SAAKhG,KAAL,CAAWC,QAAX,CAAoBH,KAAKmG,MAAzB,EAAiC,CAAjC;AACA,SAAKjG,KAAL,CAAWC,QAAX,CAAoBH,KAAKoG,MAAzB,EAAiC,CAAjC;AACA,SAAKlG,KAAL,CAAWC,QAAX,CAAoBH,KAAKqG,MAAzB,EAAiC,CAAjC;AACA,SAAKnG,KAAL,CAAWC,QAAX,CAAoBH,KAAKsG,MAAzB,EAAiC,CAAjC;AACA,SAAKpG,KAAL,CAAWC,QAAX,CAAoBH,KAAKuG,MAAzB,EAAiC,CAAjC;AACA,SAAKrG,KAAL,CAAWC,QAAX,CAAoBH,KAAKwG,MAAzB,EAAiC,CAAjC;AACA,SAAKtG,KAAL,CAAWC,QAAX,CAAoBH,KAAKyG,MAAzB,EAAiC,CAAjC;AACA,SAAKvG,KAAL,CAAWC,QAAX,CAAoBH,KAAK0G,MAAzB,EAAiC,CAAjC;AACA,SAAKxG,KAAL,CAAWC,QAAX,CAAoBH,KAAK2G,MAAzB,EAAiC,CAAjC;AACA,SAAKzG,KAAL,CAAWC,QAAX,CAAoBH,KAAK4G,MAAzB,EAAiC,CAAjC;AACA,SAAK1G,KAAL,CAAWC,QAAX,CAAoBH,KAAK6G,MAAzB,EAAiC,CAAjC;AACA,SAAK3G,KAAL,CAAWC,QAAX,CAAoBH,KAAK8G,MAAzB,EAAiC,CAAjC;AACA,SAAK5G,KAAL,CAAWC,QAAX,CAAoBH,KAAK+G,MAAzB,EAAiC,CAAjC;AACA,SAAK7G,KAAL,CAAWC,QAAX,CAAoBH,KAAKgH,MAAzB,EAAiC,CAAjC;AACA,SAAK9G,KAAL,CAAWC,QAAX,CAAoBH,KAAKiH,MAAzB,EAAiC,CAAjC;AACA,SAAK/G,KAAL,CAAWC,QAAX,CAAoBH,KAAKkH,MAAzB,EAAiC,CAAjC;AACA,SAAKhH,KAAL,CAAWC,QAAX,CAAoBH,KAAKmH,MAAzB,EAAiC,CAAjC;AACA,SAAKjH,KAAL,CAAWC,QAAX,CAAoBH,KAAKoH,MAAzB,EAAiC,CAAjC;AACA,SAAKlH,KAAL,CAAWC,QAAX,CAAoBH,KAAKqH,MAAzB,EAAiC,CAAjC;AACA,SAAKnH,KAAL,CAAWC,QAAX,CAAoBH,KAAKsH,MAAzB,EAAiC,CAAjC;AACA,SAAKpH,KAAL,CAAWC,QAAX,CAAoBH,KAAKuH,MAAzB,EAAiC,CAAjC;AACA,SAAKrH,KAAL,CAAWC,QAAX,CAAoBH,KAAKwH,MAAzB,EAAiC,CAAjC;AACA,SAAKtH,KAAL,CAAWC,QAAX,CAAoBH,KAAKyH,MAAzB,EAAiC,CAAjC;AACA,SAAKvH,KAAL,CAAWC,QAAX,CAAoBH,KAAK0H,MAAzB,EAAiC,CAAjC;AACA,SAAKxH,KAAL,CAAWC,QAAX,CAAoBH,KAAK2H,MAAzB,EAAiC,CAAjC;AACA,SAAKzH,KAAL,CAAWC,QAAX,CAAoBH,KAAK4H,MAAzB,EAAiC,CAAjC;AACA,SAAK1H,KAAL,CAAWC,QAAX,CAAoBH,KAAK6H,MAAzB,EAAiC,CAAjC;AACA,SAAK3H,KAAL,CAAWC,QAAX,CAAoBH,KAAK8H,MAAzB,EAAiC,CAAjC;AACA,SAAK5H,KAAL,CAAWC,QAAX,CAAoBH,KAAK+H,MAAzB,EAAiC,CAAjC;AACA,SAAK7H,KAAL,CAAWC,QAAX,CAAoBH,KAAKgI,MAAzB,EAAiC,CAAjC;AACA,SAAK9H,KAAL,CAAWC,QAAX,CAAoBH,KAAKiI,MAAzB,EAAiC,CAAjC;AACA,SAAK/H,KAAL,CAAWC,QAAX,CAAoBH,KAAKkI,MAAzB,EAAiC,CAAjC;AACA,SAAKhI,KAAL,CAAWC,QAAX,CAAoBH,KAAKmI,MAAzB,EAAiC,CAAjC;AACA,SAAKjI,KAAL,CAAWC,QAAX,CAAoBH,KAAKoI,MAAzB,EAAiC,CAAjC;AACA,SAAKlI,KAAL,CAAWC,QAAX,CAAoBH,KAAKqI,MAAzB,EAAiC,CAAjC;AACA,SAAKnI,KAAL,CAAWC,QAAX,CAAoBH,KAAKsI,MAAzB,EAAiC,CAAjC;AACA,SAAKpI,KAAL,CAAWC,QAAX,CAAoBH,KAAKuI,MAAzB,EAAiC,CAAjC;AACA,SAAKrI,KAAL,CAAWC,QAAX,CAAoBH,KAAKwI,MAAzB,EAAiC,CAAjC;AACA,SAAKtI,KAAL,CAAWC,QAAX,CAAoBH,KAAKyI,MAAzB,EAAiC,CAAjC;AACA,SAAKvI,KAAL,CAAWC,QAAX,CAAoBH,KAAK0I,MAAzB,EAAiC,CAAjC;AACA,SAAKxI,KAAL,CAAWC,QAAX,CAAoBH,KAAK2I,MAAzB,EAAiC,CAAjC;AACA,SAAKzI,KAAL,CAAWC,QAAX,CAAoBH,KAAK4I,MAAzB,EAAiC,CAAjC;AACA,SAAK1I,KAAL,CAAWC,QAAX,CAAoBH,KAAK6I,MAAzB,EAAiC,CAAjC;AACA,SAAK3I,KAAL,CAAWC,QAAX,CAAoBH,KAAK8I,MAAzB,EAAiC,CAAjC;AACA,SAAK5I,KAAL,CAAWC,QAAX,CAAoBH,KAAK+I,MAAzB,EAAiC,CAAjC;AACA,SAAK7I,KAAL,CAAWC,QAAX,CAAoBH,KAAKgJ,MAAzB,EAAiC,CAAjC;AACA,SAAK9I,KAAL,CAAWC,QAAX,CAAoBH,KAAKiJ,MAAzB,EAAiC,CAAjC;AACA,SAAK/I,KAAL,CAAWC,QAAX,CAAoBH,KAAKkJ,MAAzB,EAAiC,CAAjC;AACA,SAAKhJ,KAAL,CAAWC,QAAX,CAAoBH,KAAKmJ,MAAzB,EAAiC,CAAjC;AACA,SAAKjJ,KAAL,CAAWC,QAAX,CAAoBH,KAAKoJ,MAAzB,EAAiC,CAAjC;AACA,SAAKlJ,KAAL,CAAWC,QAAX,CAAoBH,KAAKqJ,MAAzB,EAAiC,CAAjC;AACA,SAAKnJ,KAAL,CAAWC,QAAX,CAAoBH,KAAKsJ,MAAzB,EAAiC,CAAjC;AACA,SAAKpJ,KAAL,CAAWC,QAAX,CAAoBH,KAAKuJ,MAAzB,EAAiC,CAAjC;AACA,SAAKrJ,KAAL,CAAWC,QAAX,CAAoBH,KAAKwJ,MAAzB,EAAiC,CAAjC;AACA,SAAKtJ,KAAL,CAAWC,QAAX,CAAoBH,KAAKyJ,MAAzB,EAAiC,CAAjC;AACA,SAAKvJ,KAAL,CAAWC,QAAX,CAAoBH,KAAK0J,MAAzB,EAAiC,CAAjC;AACA,SAAKxJ,KAAL,CAAWC,QAAX,CAAoBH,KAAK2J,MAAzB,EAAiC,CAAjC;AACA,SAAKzJ,KAAL,CAAWC,QAAX,CAAoBH,KAAK4J,MAAzB,EAAiC,CAAjC;AACA,SAAK1J,KAAL,CAAWC,QAAX,CAAoBH,KAAK6J,MAAzB,EAAiC,CAAjC;AACA,SAAK3J,KAAL,CAAWC,QAAX,CAAoBH,KAAK8J,MAAzB,EAAiC,CAAjC;AACA,SAAK5J,KAAL,CAAWC,QAAX,CAAoBH,KAAK+J,MAAzB,EAAiC,CAAjC;AACA,SAAK7J,KAAL,CAAWC,QAAX,CAAoBH,KAAKgK,MAAzB,EAAiC,CAAjC;AACA,SAAK9J,KAAL,CAAWC,QAAX,CAAoBH,KAAKiK,MAAzB,EAAiC,CAAjC;AACA,SAAK/J,KAAL,CAAWC,QAAX,CAAoBH,KAAKkK,MAAzB,EAAiC,CAAjC;AACA,SAAKhK,KAAL,CAAWC,QAAX,CAAoBH,KAAKmK,MAAzB,EAAiC,CAAjC;AACA,SAAKjK,KAAL,CAAWC,QAAX,CAAoBH,KAAKoK,MAAzB,EAAiC,CAAjC;AACA,SAAKlK,KAAL,CAAWC,QAAX,CAAoBH,KAAKqK,MAAzB,EAAiC,CAAjC;AACA,SAAKnK,KAAL,CAAWC,QAAX,CAAoBH,KAAKsK,MAAzB,EAAiC,CAAjC;AACA,SAAKpK,KAAL,CAAWC,QAAX,CAAoBH,KAAKuK,MAAzB,EAAiC,CAAjC;AACA,SAAKrK,KAAL,CAAWC,QAAX,CAAoBH,KAAKwK,MAAzB,EAAiC,CAAjC;AACA,SAAKtK,KAAL,CAAWC,QAAX,CAAoBH,KAAKyK,MAAzB,EAAiC,CAAjC;AACA,SAAKvK,KAAL,CAAWC,QAAX,CAAoBH,KAAK0K,MAAzB,EAAiC,CAAjC;AACA,SAAKxK,KAAL,CAAWC,QAAX,CAAoBH,KAAK2K,MAAzB,EAAiC,CAAjC;AACA,SAAKzK,KAAL,CAAWC,QAAX,CAAoBH,KAAK4K,MAAzB,EAAiC,CAAjC;AACA,SAAK1K,KAAL,CAAWC,QAAX,CAAoBH,KAAK6K,MAAzB,EAAiC,CAAjC;AACA,SAAK3K,KAAL,CAAWC,QAAX,CAAoBH,KAAK8K,MAAzB,EAAiC,CAAjC;AACA,SAAK5K,KAAL,CAAWC,QAAX,CAAoBH,KAAK+K,MAAzB,EAAiC,CAAjC;AACA,SAAK7K,KAAL,CAAWC,QAAX,CAAoBH,KAAKgL,MAAzB,EAAiC,CAAjC;AACA,SAAK9K,KAAL,CAAWC,QAAX,CAAoBH,KAAKiL,MAAzB,EAAiC,CAAjC;AACA,SAAK/K,KAAL,CAAWC,QAAX,CAAoBH,KAAKkL,MAAzB,EAAiC,CAAjC;AACA,SAAKhL,KAAL,CAAWC,QAAX,CAAoBH,KAAKmL,MAAzB,EAAiC,CAAjC;AACA,SAAKjL,KAAL,CAAWC,QAAX,CAAoBH,KAAKoL,MAAzB,EAAiC,CAAjC;AACA,SAAKlL,KAAL,CAAWC,QAAX,CAAoBH,KAAKqL,MAAzB,EAAiC,CAAjC;AACA,SAAKnL,KAAL,CAAWC,QAAX,CAAoBH,KAAKsL,MAAzB,EAAiC,CAAjC;AACA,SAAKpL,KAAL,CAAWC,QAAX,CAAoBH,KAAKuL,MAAzB,EAAiC,CAAjC;AACA,SAAKrL,KAAL,CAAWC,QAAX,CAAoBH,KAAKwL,MAAzB,EAAiC,CAAjC;AACA,SAAKtL,KAAL,CAAWC,QAAX,CAAoBH,KAAKyL,MAAzB,EAAiC,CAAjC;AACA,SAAKvL,KAAL,CAAWC,QAAX,CAAoBH,KAAK0L,MAAzB,EAAiC,CAAjC;AACA,SAAKxL,KAAL,CAAWC,QAAX,CAAoBH,KAAK2L,MAAzB,EAAiC,CAAjC;AACA,SAAKzL,KAAL,CAAWC,QAAX,CAAoBH,KAAK4L,MAAzB,EAAiC,CAAjC;AACA,SAAK1L,KAAL,CAAWC,QAAX,CAAoBH,KAAK6L,MAAzB,EAAiC,CAAjC;AACA,SAAK3L,KAAL,CAAWC,QAAX,CAAoBH,KAAK8L,MAAzB,EAAiC,CAAjC;AACA,SAAK5L,KAAL,CAAWC,QAAX,CAAoBH,KAAK+L,MAAzB,EAAiC,CAAjC;AACA,SAAK7L,KAAL,CAAWC,QAAX,CAAoBH,KAAKgM,MAAzB,EAAiC,CAAjC;AACA,SAAK9L,KAAL,CAAWC,QAAX,CAAoBH,KAAKiM,MAAzB,EAAiC,CAAjC;AACA,SAAK/L,KAAL,CAAWC,QAAX,CAAoBH,KAAKkM,MAAzB,EAAiC,CAAjC;AACA,SAAKhM,KAAL,CAAWC,QAAX,CAAoBH,KAAKmM,MAAzB,EAAiC,CAAjC;AACA,SAAKjM,KAAL,CAAWC,QAAX,CAAoBH,KAAKoM,MAAzB,EAAiC,CAAjC;AACA,SAAKlM,KAAL,CAAWC,QAAX,CAAoBH,KAAKqM,MAAzB,EAAiC,CAAjC;AACA,SAAKnM,KAAL,CAAWC,QAAX,CAAoBH,KAAKsM,MAAzB,EAAiC,CAAjC;AACA,SAAKpM,KAAL,CAAWC,QAAX,CAAoBH,KAAKuM,MAAzB,EAAiC,CAAjC;AACA,SAAKrM,KAAL,CAAWC,QAAX,CAAoBH,KAAKwM,MAAzB,EAAiC,CAAjC;AACA,SAAKtM,KAAL,CAAWC,QAAX,CAAoBH,KAAKyM,MAAzB,EAAiC,CAAjC;AACA,SAAKvM,KAAL,CAAWC,QAAX,CAAoBH,KAAK0M,MAAzB,EAAiC,CAAjC;AACA,SAAKxM,KAAL,CAAWC,QAAX,CAAoBH,KAAK2M,MAAzB,EAAiC,CAAjC;AACA,SAAKzM,KAAL,CAAWC,QAAX,CAAoBH,KAAK4M,MAAzB,EAAiC,CAAjC;AACA,SAAK1M,KAAL,CAAWC,QAAX,CAAoBH,KAAK6M,MAAzB,EAAiC,CAAjC;AACA,SAAK3M,KAAL,CAAWC,QAAX,CAAoBH,KAAK8M,MAAzB,EAAiC,CAAjC;AACA,SAAK5M,KAAL,CAAWC,QAAX,CAAoBH,KAAK+M,MAAzB,EAAiC,CAAjC;AACA,SAAK7M,KAAL,CAAWC,QAAX,CAAoBH,KAAKgN,MAAzB,EAAiC,CAAjC;AACA,SAAK9M,KAAL,CAAWC,QAAX,CAAoBH,KAAKiN,MAAzB,EAAiC,CAAjC;AACA,SAAK/M,KAAL,CAAWC,QAAX,CAAoBH,KAAKkN,MAAzB,EAAiC,CAAjC;AACA,SAAKhN,KAAL,CAAWC,QAAX,CAAoBH,KAAKmN,MAAzB,EAAiC,CAAjC;AACA,SAAKjN,KAAL,CAAWC,QAAX,CAAoBH,KAAKoN,MAAzB,EAAiC,CAAjC;AACA,SAAKlN,KAAL,CAAWC,QAAX,CAAoBH,KAAKqN,MAAzB,EAAiC,CAAjC;AACA,SAAKnN,KAAL,CAAWC,QAAX,CAAoBH,KAAKsN,MAAzB,EAAiC,CAAjC;AACA,SAAKpN,KAAL,CAAWC,QAAX,CAAoBH,KAAKuN,MAAzB,EAAiC,CAAjC;AACA,SAAKrN,KAAL,CAAWC,QAAX,CAAoBH,KAAKwN,MAAzB,EAAiC,CAAjC;AACA,SAAKtN,KAAL,CAAWC,QAAX,CAAoBH,KAAKyN,MAAzB,EAAiC,CAAjC;AACA,SAAKvN,KAAL,CAAWC,QAAX,CAAoBH,KAAK0N,MAAzB,EAAiC,CAAjC;AACA,SAAKxN,KAAL,CAAWC,QAAX,CAAoBH,KAAK2N,MAAzB,EAAiC,CAAjC;AACA,SAAKzN,KAAL,CAAWC,QAAX,CAAoBH,KAAK4N,MAAzB,EAAiC,CAAjC;AACA,SAAK1N,KAAL,CAAWC,QAAX,CAAoBH,KAAK6N,MAAzB,EAAiC,CAAjC;AACA,SAAK3N,KAAL,CAAWC,QAAX,CAAoBH,KAAK8N,MAAzB,EAAiC,CAAjC;AACA,SAAK5N,KAAL,CAAWC,QAAX,CAAoBH,KAAK+N,MAAzB,EAAiC,CAAjC;AACA,SAAK7N,KAAL,CAAWC,QAAX,CAAoBH,KAAKgO,MAAzB,EAAiC,CAAjC;AACA,SAAK9N,KAAL,CAAWC,QAAX,CAAoBH,KAAKiO,MAAzB,EAAiC,CAAjC;AACA,SAAK/N,KAAL,CAAWC,QAAX,CAAoBH,KAAKkO,MAAzB,EAAiC,CAAjC;AACA,SAAKhO,KAAL,CAAWC,QAAX,CAAoBH,KAAKmO,MAAzB,EAAiC,CAAjC;AACA,SAAKjO,KAAL,CAAWC,QAAX,CAAoBH,KAAKoO,MAAzB,EAAiC,CAAjC;AACA,SAAKlO,KAAL,CAAWC,QAAX,CAAoBH,KAAKqO,MAAzB,EAAiC,CAAjC;AACA,SAAKnO,KAAL,CAAWC,QAAX,CAAoBH,KAAKsO,MAAzB,EAAiC,CAAjC;AACA,SAAKpO,KAAL,CAAWC,QAAX,CAAoBH,KAAKuO,MAAzB,EAAiC,CAAjC;AACA,SAAKrO,KAAL,CAAWC,QAAX,CAAoBH,KAAKwO,MAAzB,EAAiC,CAAjC;AACA,SAAKtO,KAAL,CAAWC,QAAX,CAAoBH,KAAKyO,MAAzB,EAAiC,CAAjC;AACA,SAAKvO,KAAL,CAAWC,QAAX,CAAoBH,KAAK0O,MAAzB,EAAiC,CAAjC;AACA,SAAKxO,KAAL,CAAWC,QAAX,CAAoBH,KAAK2O,MAAzB,EAAiC,CAAjC;AACA,SAAKzO,KAAL,CAAWC,QAAX,CAAoBH,KAAK4O,MAAzB,EAAiC,CAAjC;AACA,SAAK1O,KAAL,CAAWC,QAAX,CAAoBH,KAAK6O,MAAzB,EAAiC,CAAjC;AACA,SAAK3O,KAAL,CAAWC,QAAX,CAAoBH,KAAK8O,MAAzB,EAAiC,CAAjC;AACA,SAAK5O,KAAL,CAAWC,QAAX,CAAoBH,KAAK+O,MAAzB,EAAiC,CAAjC;AACA,SAAK7O,KAAL,CAAWC,QAAX,CAAoBH,KAAKgP,MAAzB,EAAiC,CAAjC;AACA,SAAK9O,KAAL,CAAWC,QAAX,CAAoBH,KAAKiP,MAAzB,EAAiC,CAAjC;AACA,SAAK/O,KAAL,CAAWC,QAAX,CAAoBH,KAAKkP,MAAzB,EAAiC,CAAjC;AACA,SAAKhP,KAAL,CAAWC,QAAX,CAAoBH,KAAKmP,MAAzB,EAAiC,CAAjC;AACA,SAAKjP,KAAL,CAAWC,QAAX,CAAoBH,KAAKoP,MAAzB,EAAiC,CAAjC;AACA,SAAKlP,KAAL,CAAWC,QAAX,CAAoBH,KAAKqP,MAAzB,EAAiC,CAAjC;AACA,SAAKnP,KAAL,CAAWC,QAAX,CAAoBH,KAAKsP,MAAzB,EAAiC,CAAjC;AACA,SAAKpP,KAAL,CAAWC,QAAX,CAAoBH,KAAKuP,MAAzB,EAAiC,CAAjC;AACA,SAAKrP,KAAL,CAAWC,QAAX,CAAoBH,KAAKwP,MAAzB,EAAiC,CAAjC;AACA,SAAKtP,KAAL,CAAWC,QAAX,CAAoBH,KAAKyP,MAAzB,EAAiC,CAAjC;AACA,SAAKvP,KAAL,CAAWC,QAAX,CAAoBH,KAAK0P,MAAzB,EAAiC,CAAjC;AACA,SAAKxP,KAAL,CAAWC,QAAX,CAAoBH,KAAK2P,MAAzB,EAAiC,CAAjC;AACA,SAAKzP,KAAL,CAAWC,QAAX,CAAoBH,KAAK4P,MAAzB,EAAiC,CAAjC;AACA,SAAK1P,KAAL,CAAWC,QAAX,CAAoBH,KAAK6P,MAAzB,EAAiC,CAAjC;AACA,SAAK3P,KAAL,CAAWC,QAAX,CAAoBH,KAAK8P,MAAzB,EAAiC,CAAjC;AACA,SAAK5P,KAAL,CAAWC,QAAX,CAAoBH,KAAK+P,MAAzB,EAAiC,CAAjC;AACA,SAAK7P,KAAL,CAAWC,QAAX,CAAoBH,KAAKgQ,MAAzB,EAAiC,CAAjC;AACA,SAAK9P,KAAL,CAAWC,QAAX,CAAoBH,KAAKiQ,MAAzB,EAAiC,CAAjC;AACA,SAAK/P,KAAL,CAAWC,QAAX,CAAoBH,KAAKkQ,MAAzB,EAAiC,CAAjC;AACA,SAAKhQ,KAAL,CAAWC,QAAX,CAAoBH,KAAKmQ,MAAzB,EAAiC,CAAjC;AACA,SAAKjQ,KAAL,CAAWC,QAAX,CAAoBH,KAAKoQ,MAAzB,EAAiC,CAAjC;AACA,SAAKlQ,KAAL,CAAWC,QAAX,CAAoBH,KAAKqQ,MAAzB,EAAiC,CAAjC;AACA,SAAKnQ,KAAL,CAAWC,QAAX,CAAoBH,KAAKsQ,MAAzB,EAAiC,CAAjC;AACA,SAAKpQ,KAAL,CAAWC,QAAX,CAAoBH,KAAKuQ,MAAzB,EAAiC,CAAjC;AACA,SAAKrQ,KAAL,CAAWC,QAAX,CAAoBH,KAAKwQ,MAAzB,EAAiC,CAAjC;AACA,SAAKtQ,KAAL,CAAWC,QAAX,CAAoBH,KAAKyQ,MAAzB,EAAiC,CAAjC;AACA,SAAKvQ,KAAL,CAAWC,QAAX,CAAoBH,KAAK0Q,MAAzB,EAAiC,CAAjC;AACA,SAAKxQ,KAAL,CAAWC,QAAX,CAAoBH,KAAK2Q,MAAzB,EAAiC,CAAjC;AACA,SAAKzQ,KAAL,CAAWC,QAAX,CAAoBH,KAAK4Q,MAAzB,EAAiC,CAAjC;AACA,SAAK1Q,KAAL,CAAWC,QAAX,CAAoBH,KAAK6Q,MAAzB,EAAiC,CAAjC;AACA,SAAK3Q,KAAL,CAAWC,QAAX,CAAoBH,KAAK8Q,MAAzB,EAAiC,CAAjC;AACA,SAAK5Q,KAAL,CAAWC,QAAX,CAAoBH,KAAK+Q,MAAzB,EAAiC,CAAjC;AACA,SAAK7Q,KAAL,CAAWC,QAAX,CAAoBH,KAAKgR,MAAzB,EAAiC,CAAjC;AACA,SAAK9Q,KAAL,CAAWC,QAAX,CAAoBH,KAAKiR,MAAzB,EAAiC,CAAjC;AACA,SAAK/Q,KAAL,CAAWC,QAAX,CAAoBH,KAAKkR,MAAzB,EAAiC,CAAjC;AACA,SAAKhR,KAAL,CAAWC,QAAX,CAAoBH,KAAKmR,MAAzB,EAAiC,CAAjC;AACA,SAAKjR,KAAL,CAAWC,QAAX,CAAoBH,KAAKoR,MAAzB,EAAiC,CAAjC;AACA,SAAKlR,KAAL,CAAWC,QAAX,CAAoBH,KAAKqR,MAAzB,EAAiC,CAAjC;AACA,SAAKnR,KAAL,CAAWC,QAAX,CAAoBH,KAAKsR,MAAzB,EAAiC,CAAjC;AACA,SAAKpR,KAAL,CAAWC,QAAX,CAAoBH,KAAKuR,MAAzB,EAAiC,CAAjC;AACA,SAAKrR,KAAL,CAAWC,QAAX,CAAoBH,KAAKwR,MAAzB,EAAiC,CAAjC;AACA,SAAKtR,KAAL,CAAWC,QAAX,CAAoBH,KAAKyR,MAAzB,EAAiC,CAAjC;AACA,SAAKvR,KAAL,CAAWC,QAAX,CAAoBH,KAAK0R,MAAzB,EAAiC,CAAjC;AACA,SAAKxR,KAAL,CAAWC,QAAX,CAAoBH,KAAK2R,MAAzB,EAAiC,CAAjC;AACA,SAAKzR,KAAL,CAAWC,QAAX,CAAoBH,KAAK4R,MAAzB,EAAiC,CAAjC;AACA,SAAK1R,KAAL,CAAWC,QAAX,CAAoBH,KAAK6R,MAAzB,EAAiC,CAAjC;AACA,SAAK3R,KAAL,CAAWC,QAAX,CAAoBH,KAAK8R,MAAzB,EAAiC,CAAjC;AACA,SAAK5R,KAAL,CAAWC,QAAX,CAAoBH,KAAK+R,MAAzB,EAAiC,CAAjC;AACA,SAAK7R,KAAL,CAAWC,QAAX,CAAoBH,KAAKgS,MAAzB,EAAiC,CAAjC;AACA

CAAd1J,YAAc;AAAA,0BAF/C2H,OAE+C;AAAA,MAF/CA,OAE+C,6BAFrC3H,YAEqC;AAAA,0BAD/C2J,OAC+C;AAAA,MAD/CA,OAC+C,6BADrC7J,WACqC;;AAC/C,MAAM8J,MAAM,GAAG,IAAIC,MAAJ,CAAWlC,OAAX,CAAf,CAD+C;AAI/C;AACA;;AAEA,MAAImC,YAAY,GAAG,EAAnB,CAP+C;;AAU/C,MAAMC,iBAAiB,GAAG,EAAoB;AACjDC,QAAQA,CAAC,QAAQA,CAAC,CAAC,CAAC,CAAC,EAAEC,CAAC,EAAE,CAAC,EAAE,CAAC,EAAE

AyB1P,IAAzB,EAAuC2P,KAAvC,EAAwD;AACrE;AACA;AACA,MAAIA,KAAK,IAAI,IAAT,IAAiB,OAAOA,KAAAP,KAAAiB,SAAlC,IA+CA+CA,KAAK,KAAK,EAA7D,EAAiE;AAC/D,WAAO,EAAP;AACD;;AAED,MAAI,OAAOA,KAAAP,KAAAiB,QAAAC,KAAAC,KAAAC,K

G,IAAItR,UAAJ,CAAe,CAAf,CAA1B;AACA,IAAMuR,UAAU,GAAG,IAAIvR,UAAJ,CAAe,CAAf,CAAnB;AACA,IAAMwR,WAAW,GAAG,IAAIxR,UAAJ,CAAe,CAAf,CApB;AACA,IAAMyR,SAAS,GAAG,IAAIzR,UAAJ,CAAe,CAAf,CAAjB;AACA,IAAM0R,QAAQ,GAAG,IAAI1R,UAAJ,CAAe,CAAf,CAAlB;AACA,IAAM2R,KAAK,GAAG,IAAI3R,UAAJ,CAAe,CAAf,CAAd;AACA,IAAM4R,EAAE,GAAG,IAAI5R,UAAJ,CAAe,CAAf,CAAX;AAEA,IAAM6R,SAAS,GAAG,IAAIC,WAAJ,CAAgB,CAAhB,CAAlB;AACA,IAAMC,QAAQ,GAAG,IAAIC,UAAJ,CAAeH,SAAf,CAAjB;AACA,IAAMI,QAAQ,GAAG,IAAIC,UAAJ,CAAeL,SAAf,CAAjB;AACA,IAAMM,QAAQ,GAAG,IAAIC,UAAJ,CAAeP,SAAf,CAAjB;AACA,IAAMQ,QAAQ,GAAG,IAAIC,UAAJ,CAAeT,SAAf,CAAjB;AACA,IAAMU,QAAQ,GAAG,IAAIC,UAAJ,CAAeX,SAAf,CAAjB;AACA,IAAMY,QAAQ,GAAG,IAAIC,UAAJ,CAAeb,SAAf,CAAjB;AACA,IAAMc,QAAQ,GAAG,IAAIC,UAAJ,CAAef,SAAf,CAAjB;AACA,IAAMgB,QAAQ,GAAG,IAAIC,UAAJ,CAAejB,SAAf,CAAjB;AACA,IAAMkB,QAAQ,GAAG,IAAIC,UAAJ,CAAenB,SAAf,CAAjB;AACA,IAAMoB,QAAQ,GAAG,IAAIC,UAAJ,CAAerB,SAAf,CAAjB;AACA,IAAMsB,QAAQ,GAAG,IAAIC,UAAJ,CAAevB,SAAf,CAAjB;AACA,IAAMwB,QAAQ,GAAG,IAAIC,UAAJ,CAAezB,SAAf,CAAjB;AACA,IAAM0B,QAAQ,GAAG,IAAIC,UAAJ,CAAe3B,SAAf,CAAjB;AACA,IAAM4B,QAAQ,GAAG,IAAIC,UAAJ,CAAe7B,SAAf,CAAjB;AACA,IAAM8B,QAAQ,GAAG,IAAIC,UAAJ,CAAe/B,SAAf,CAAjB;AACA,IAAMgC,QAAQ,GAAG,IAAIC,UAAJ,CAAejC,SAAf,CAAjB;AACA,IAAMkC,QAAQ,GAAG,IAAIC,UAAJ,CAAenC,SAAf,CAAjB;AACA,IAAMoC,QAAQ,GAAG,IAAIC,UAAJ,CAAerC,SAAf,CAAjB;AACA,IAAMsC,QAAQ,GAAG,IAAIC,UAAJ,CAAevC,SAAf,CAAjB;AACA,IAAMwC,QAAQ,GAAG,IAAIC,UAAJ,CAAezC,SAAf,CAAjB;AACA,IAAM0C,QAAQ,GAAG,IAAIC,UAAJ,CAAe3C,SAAf,CAAjB;AACA,IAAM4C,QAAQ,GAAG,IAAIC,UAAJ,CAAe7C,SAAf,CAAjB;AACA,IAAM8C,QAAQ,GAAG,IAAIC,UAAJ,CAAe/C,SAAf,CAAjB;AACA,IAAMgD,QAAQ,GAAG,IAAIC,UAAJ,CAAejD,SAAf,CAAjB;AACA,IAAMkD,QAAQ,GAAG,IAAIC,UAAJ,CAAenD,SAAf,CAAjB;AACA,IAAMoD,QAAQ,GAAG,IAAIC,UAAJ,CAAerD,SAAf,CAAjB;AACA,IAAMsD,QAAQ,GAAG,IAAIC,UAAJ,CAAevD,SAAf,CAAjB;AACA,IAAMwD,QAAQ,GAAG,IAAIC,UAAJ,CAAezD,SAAf,CAAjB;AACA,IAAM0D,QAAQ,GAAG,IAAIC,UAAJ,CAAe3D,SAAf,CAAjB;AACA,IAAM4D,QAAQ,GAAG,IAAIC,UAAJ,CAAe7D,SAAf,CAAjB;AACA,IAAM8D,QAAQ,GAAG,IAAIC,UAAJ,CAAe/D,SAAf,CAAjB;AACA,IAAMgE,QAAQ,GAAG,IAAIC,UAAJ,CAAejE,SAAf,CAAjB;AACA,IAAMkE,QAAQ,GAAG,IAAIC,UAAJ,CAAenE,SAAf,CAAjB;AACA,IAAMoE,QAAQ,GAAG,IAAIC,UAAJ,CAAerE,SAAf,CAAjB;AACA,IAAMsE,QAAQ,GAAG,IAAIC,UAAJ,CAAevE,SAAf,CAAjB;AACA,IAAMwE,QAAQ,GAAG,IAAIC,UAAJ,CAAezE,SAAf,CAAjB;AACA,IAAM0E,QAAQ,GAAG,IAAIC,UAAJ,CAAe3E,SAAf,CAAjB;AACA,IAAM4E,QAAQ,GAAG,IAAIC,UAAJ,CAAe7E,SAAf,CAAjB;AACA,IAAM8E,QAAQ,GAAG,IAAIC,UAAJ,CAAe/E,SAAf,CAAjB;AACA,IAAMgF,QAAQ,GAAG,IAAIC,UAAJ,CAAejF,SAAf,CAAjB;AACA,IAAMkF,QAAQ,GAAG,IAAIC,UAAJ,CAAenF,SAAf,CAAjB;AACA,IAAMoF,QAAQ,GAAG,IAAIC,UAAJ,CAAerF,SAAf,CAAjB;AACA,IAAMsF,QAAQ,GAAG,IAAIC,UAAJ,CAAevF,SAAf,CAAjB;AACA,IAAMwF,QAAQ,GAAG,IAAIC,UAAJ,CAAezF,SAAf,CAAjB;AACA,IAAM0F,QAAQ,GAAG,IAAIC,UAAJ,CAAe3F,SAAf,CAAjB;AACA,IAAM4F,QAAQ,GAAG,IAAIC,UAAJ,CAAe7F,SAAf,CAAjB;AACA,IAAM8F,QAAQ,GAAG,IAAIC,UAAJ,CAAe/F,SAAf,CAAjB;AACA,IAAMgG,QAAQ,GAAG,IAAIC,UAAJ,CAAejG,SAAf,CAAjB;AACA,IAAMkG,QAAQ,GAAG,IAAIC,UAAJ,CAAenG,SAAf,CAAjB;AACA,IAAMoG,QAAQ,GAAG,IAAIC,UAAJ,CAAerG,SAAf,CAAjB;AACA,IAAMsG,QAAQ,GAAG,IAAIC,UAAJ,CAAevG,SAAf,CAAjB;AACA,IAAMwG,QAAQ,GAAG,IAAIC,UAAJ,CAAezG,SAAf,CAAjB;AACA,IAAM0G,QAAQ,GAAG,IAAIC,UAAJ,CAAe3G,SAAf,CAAjB;AACA,IAAM4G,QAAQ,GAAG,IAAIC,UAAJ,CAAe7G,SAAf,CAAjB;AACA,IAAM8G,QAAQ,GAAG,IAAIC,UAAJ,CAAe/G,SAAf,CAAjB;AACA,IAAMgH,QAAQ,GAAG,IAAIC,UAAJ,CAAejH,SAAf,CAAjB;AACA,IAAMkH,QAAQ,GAAG,IAAIC,UAAJ,CAAenH,SAAf,CAAjB;AACA,IAAMoH,QAAQ,GAAG,IAAIC,UAAJ,CAAerH,SAAf,CAAjB;AACA,IAAMsH,QAAQ,GAAG,IAAIC,UAAJ,CAAevH,SAAf,CAAjB;AACA,IAAMwH,QAAQ,GAAG,IAAIC,UAAJ,CAAezH,SAAf,CAAjB;AACA,IAAM0H,QAAQ,GAAG,IAAIC,UAAJ,CAAe3H,SAAf,CAAjB;AACA,IAAM4H,QAAQ,GAAG,IAAIC,UAAJ,CAAe7H,SAAf,CAAjB;AACA,IAAM8H,QAAQ,GAAG,IAAIC,UAAJ,CAAe/H,SAAf,CAAjB;AACA,IAAMgI,QAAQ,GAAG,IAAIC,UAAJ,CAAejI,SAAf,CAAjB;AACA,IAAMkI,QAAQ,GAAG,IAAIC,UAAJ,CAAenI,SAAf,CAAjB;AACA,IAAMoI,QAAQ,GAAG,IAAIC,UAAJ,CAAerI,SAAf,CAAjB;AACA,IAAMsI,QAAQ,GAAG,IAAIC,UAAJ,CAAevI,SAAf,CAAjB;AACA,IAAMwI,QAAQ,GAAG,IAAIC,UAAJ,CAAezI,SAAf,CAAjB;AACA,IAAM0I,QAAQ,GAAG,IAAIC,UAAJ,CAAe3I,SAAf,CAAjB;AACA,IAAM4I,QAAQ,GAAG,IAAIC,UAAJ,CAAe7I,SAAf,CAAjB;AACA,IAAM8I,QAAQ,GAAG,IAAIC,UAAJ,CAAe/I,SAAf,CAAjB;AACA,IAAMgJ,QAAQ,GAAG,IAAIC,UAAJ,CAAejJ,SAAf,CAAjB;AACA,IAAMkJ,QAAQ,GAAG,IAAIC,UAAJ,CAAenJ,SAAf,CAAjB;AACA,IAAMoJ,QAAQ,GAAG,IAAIC,UAAJ,CAAerJ,SAAf,CAAjB;AACA,IAAMsJ,QAAQ,GAAG,IAAIC,UAAJ,CAAevJ,SAAf,CAAjB;AACA,IAAMwJ,QAAQ,GAAG,IAAIC,UAAJ,CAAezJ,SAAf,CAAjB;AACA,IAAM0J,QAAQ,GAAG,IAAIC,UAAJ,CAAe3J,SAAf,CAAjB;AACA,IAAM4J,QAAQ,GAAG,IAAIC,UAAJ,CAAe7J,SAAf,CAAjB;AACA,IAAM8J,QAAQ,GAAG,IAAIC,UAAJ,CAAe/J,SAAf,CAAjB;AACA,IAAMgK,QAAQ,GAAG,IAAIC,UAAJ,CAAejK,SAAf,CAAjB;AACA,IAAMkK,QAAQ,GAAG,IAAIC,UAAJ,CAAenK,SAAf,CAAjB;AACA,IAAMoK,QAAQ,GAAG,IAAIC,UAAJ,CAAerK,SAAf,CAAjB;AACA,IAAMsK,QAAQ,GAAG,IAAIC,UAAJ,CAAevK,SAAf,CAAjB;AACA,IAAMwK,QAAQ,GAAG,IAAIC,UAAJ,CAAezK,SAAf,CAAjB;AACA,IAAM0K,QAAQ,GAAG,IAAIC,UAAJ,CAAe3K,SAAf,CAAjB;AACA,IAAM4K,QAAQ,GAAG,IAAIC,UAAJ,CAAe7K,SAAf,CAAjB;AACA,IAAM8K,QAAQ,GAAG,IAAIC,UAAJ,CAAe/K,SAAf,CAAjB;AACA,IAAMgL,QAAQ,GAAG,IAAIC,UAAJ,CAAejL,SAAf,CAAjB;AACA,IAAMkL,QAAQ,GAAG,IAAIC,UAAJ,CAAenL,SAAf,CAAjB;AACA,IAAMoL,QAAQ,GAAG,IAAIC,UAAJ,CAAerL,SAAf,CAAjB;AACA,IAAMsL,QAAQ,GAAG,IAAIC,UAAJ,CAAevL,SAAf,CAAjB;AACA,IAAMwL,QAAQ,GAAG,IAAIC,UAAJ,CAAezL,SAAf,CAAjB;AACA,IAAM0L,QAAQ,GAAG,IAAIC,UAAJ,CAAe3L,SAAf,CAAjB;AACA,IAAM4L,QAAQ,GAAG,IAAIC,UAAJ,CAAe7L,SAAf,CAAjB;AACA,IAAM8L,QAAQ,GAAG,IAAIC,UAAJ,CAAe/L,SAAf,CAAjB;AACA,IAAMgM,QAAQ,GAAG,IAAIC,UAAJ,CAAejM,SAAf,CAAjB;AACA,IAAMkM,QAAQ,GAAG,IAAIC,UAAJ,CAAenM,SAAf,CAAjB;AACA,IAAMoM,QAAQ,GAAG,IAAIC,UAAJ,CAAerM,SAAf,CAAjB;AACA,IAAMsM,QAAQ,GAAG,IAAIC,UAAJ,CAAevM,SAAf,CAAjB;AACA,IAAMwM,QAAQ,GAAG,IAAIC,UAAJ,CAAezM,SAAf,CAAjB;AACA,IAAM0M,QAAQ,GAAG,IAAIC,UAAJ,CAAe3M,SAAf,CAAjB;AACA,IAAM4M,QAAQ,GAAG,IAAIC,UAAJ,CAAe7M,SAAf,CAAjB;AACA,IAAM8M,QAAQ,GAAG,IAAIC,UAAJ,CAAe/M,SAAf,CAAjB;AACA,IAAMgN,QAAQ,GAAG,IAAIC,UAAJ,CAAejN,SAAf,CAAjB;AACA,IAAMkN,QAAQ,GAAG,IAAIC,UAAJ,CAAenN,SAAf,CAAjB;AACA,IAAMoN,QAAQ,GAAG,IAAIC,UAAJ,CAAerN,SAAf,CAAjB;AACA,IAAMsN,QAAQ,GAAG,IAAIC,UAAJ,CAAevN,SAAf,CAAjB;AACA,IAAMwN,QAAQ,GAAG,IAAIC,UAAJ,CAAezN,SAAf,CAAjB;AACA,IAAM0N,QAAQ,GAAG,IAAIC,UAAJ,CAAe3N,SAAf,CAAjB;AACA,IAAM4N,QAAQ,GAAG,IAAIC,UAAJ,CAAe7N,SAAf,CAAjB;AACA,IAAM8N,QAAQ,GAAG,IAAIC,UAAJ,CAAe/N,SAAf,CAAjB;AACA,IAAMgO,QAAQ,GAAG,IAAIC,UAAJ,CAAejO,SAAf,CAAjB;AACA,IAAMkO,QAAQ,GAAG,IAAIC,UAAJ,CAAenO,SAAf,CAAjB;AACA,IAAMoO,QAAQ,GAAG,IAAIC,UAAJ,CAAerO,SAAf,CAAjB;AACA,IAAMsO,QAAQ,GAAG,IAAIC,UAAJ,CAAevO,SAAf,CAAjB;AACA,IAAMwO,QAAQ,GAAG,IAAIC,UAAJ,CAAezO,SAAf,CAAjB;AACA,IAAM0O,QAAQ,GAAG,IAAIC,UAAJ,CAAe3O,SAAf,CAAjB;AACA,IAAM4O,QAAQ,GAAG,IAAIC,UAAJ,CAAe7O,SAAf,CAAjB;AACA,IAAM8O,QAAQ,GAAG,IAAIC,UAAJ,CAAe/O,SAAf,CAAjB;AACA,IAAMgP,QAAQ,GAAG,IAAIC,UAAJ,CAAejP,SAAf,CAAjB;AACA,IAAMkP,QAAQ,GAAG,IAAIC,UAAJ,CAAenP,SAAf,CAAjB;AACA,IAAMoP,QAAQ,GAAG,IAAIC,UAAJ,CAAerP,SAAf,CAAjB;AACA,IAAMsP,QAAQ,GAAG,IAAIC,UAAJ,CAAevP,SAAf,CAAjB;AACA,IAAMwP,QAAQ,GAAG,IAAIC,UAAJ,CAAezP,SAAf,CAAjB;AACA,IAAM0P,QAAQ,GAAG,IAAIC,UAAJ,CAAe3P,SAAf,CAAjB;AACA,IAAM4P,QAAQ,GAAG,IAAIC,UAAJ,CAAe7P,SAAf,CAAjB;AACA,IAAM8P,QAAQ,GAAG,IAAIC,UAAJ,CAAe/P,SAAf,CAAjB;AACA,IAAMgQ,QAAQ,GAAG,IAAIC,UAAJ,CAAejQ,SAAf,CAAjB;AACA,IAAMkQ,QAAQ,GAAG,IAAIC,UAAJ,CAAenQ,SAAf,CAAjB;AACA,IAAMoQ,QAAQ,GAAG,IAAIC,UAAJ,CAAerQ,SAAf,CAAjB;AACA,IAAMsQ,QAAQ,GAAG,IAAIC,UAAJ,CAAevQ,SAAf,CAAjB;AACA,IAAMwQ,QAAQ,GAAG,IAAIC,UAAJ,CAAezQ,SAAf,CAAjB;AACA,IAAM0Q,QAAQ,GAAG,IAAIC,UAAJ,CAAe3Q,SAAf,CAAjB;AACA,IAAM4Q,QAAQ,GAAG,IAAIC,UAAJ,CAAe7Q,SAAf,CAAjB;AACA,IAAM8Q,QAAQ,GAAG,IAAIC,UAAJ,CAAe/Q,SAAf,CAAjB;AACA,IAAMgR,QAAQ,GAAG,IAAIC,UAAJ,CAAejR,SAAf,CAAjB;AACA,IAAMkR,QAAQ,GAAG,IAAIC,UAAJ,CAAenR,SAAf,CAAjB;AACA,IAAMoR,QAAQ,GAAG,IAAIC,UAAJ,CAAerR,SAAf,CAAjB;AACA,IAAMsR,QAAQ,GAAG,IAAIC,UAAJ,CAAevR,SAAf,CAAjB;AACA,IAAMwR,QAAQ,GAAG,IAAIC,UAAJ,CAAezR,SAAf,CAAjB;AACA,IAAM0R,QAAQ,GAAG,IAAIC,UAAJ,CAAe3R,SAAf,CAAjB;AACA,IAAM4R,QAAQ,GAAG,IAAIC,UAAJ,CAAe7R,SAAf,CAAjB;AACA,IAAM8R,QAAQ,GAAG,IAAIC,UAAJ,CAAe/R,SAAf,CAAjB;AACA,IAAMgS,QAAQ,GAAG,IAAIC,UAAJ,CAAejS,SAAf,CAAjB;AACA,IAAMkS,QAAQ,GAAG,IAAIC,UAAJ,CAAenS,SAAf,CAAjB;AACA,IAAMoS,QAAQ,GAAG,IAAIC,UAAJ,CAAerS,SAAf,CAAjB;AACA,IAAMsS,QAAQ,GAAG,IAAIC,UAAJ,CAAevS,SAAf,CAAjB;AACA,IAAMwS,QAAQ,GAAG,IAAIC,UAAJ,CAAezS,SAAf,CAAjB;AACA,IAAM0S,QAAQ,GAAG,IAAIC,UAAJ,CAAe3S,SAAf,CAAjB;AACA,IAAM4S,QAAQ,GAAG,IAAIC,UAAJ,CAAe7S,SAAf,CAAjB;AACA,IAAM8S,QAAQ,GAAG,IAAIC,UAAJ,CAAe/S,SAAf,CAAjB;AACA,IAAMgT,QAAQ,GAAG,IAAIC,UAAJ,CAAejT,SAAf,CAAjB;AACA,IAAMkT,QAAQ,GAAG,IAAIC,UAAJ,CAAenT,SAAf,CAAjB;AACA,IAAMoT,QAAQ,GAAG,IAAIC,UAAJ,CAAerT,SAAf,CAAjB;AACA,IAAMsT,QAAQ,GAAG,IAAIC,UAAJ,CAAevT,SAAf,CAAjB;AACA,IAAMwT,QAAQ,GAAG,IAAIC,UAAJ,CAAezT,SAAf,CAAjB;AACA,IAAM0T,QAAQ,GAAG,IAAIC,UAAJ,CAAe3T,SAAf,CAAjB;AACA,IAAM4T,QAAQ,GAAG,IAAIC,UAAJ,CAAe7T,SAAf,CAAjB;AACA,IAAM8T,QAAQ,GAAG,IAAIC,UAAJ,CAAe/T,SAAf,CAAjB;AACA,IAAMgU,QAAQ,GAAG,IAAIC,UAAJ,CAAejU,SAAf,CAAjB;AACA,IAAMkU,QAAQ,GAAG,IAAIC,UAAJ,CAAenU,SAAf,CAAjB;AACA,IAAMoU,QAAQ,GAAG,IAAIC,UAAJ,CAAerU,SAAf,CAAjB;AACA,IAAMsU,QAAQ,GAAG,IAAIC,UAAJ,CAAevU,SAAf,CAAjB;AACA,IAAMwU,QAAQ,GAAG,IAAIC,UAAJ,CAAezU,SAAf,CAAjB;AACA,IAAM0U,QAAQ,GAAG,IAAIC,UAAJ,CAAe3U,SAAf,CAAjB;AACA,IAAM4U,QAAQ,GAAG,IAAIC,UAAJ,CAAe7U,SAAf,CAAjB;AACA,IAAM8U,QAAQ,GAAG,IAAIC,UAAJ,CAAe/U,SAAf,CAAjB;AACA,IAAMgV,QAAQ,GAAG,IAAIC,UAAJ,CAAejV,SAAf,CAAjB;AACA,IAAMkV,QAAQ,GAAG,IAAIC,UAAJ,CAAenV,SAAf,CAAjB;AACA,IAAMoV,QAAQ,GAAG,IAAIC,UAAJ,CAAerV,SAAf,CAAjB;AACA,IAAMsV,QAAQ,GAAG,IAAIC,UAAJ,CAAevV,SAAf,CAAjB;AACA,IAAMwV,QAAQ,GAAG,IAAIC,UAAJ,CAAezV,SAAf,CAAjB;AACA,IAAM0V,QAAQ,GAAG,IAAIC,UAAJ,CAAe3V,SAAf,CAAjB;AACA,IAAM4V,QAAQ,GAAG,IAAIC,UAAJ,CAAe7V,SAAf,CAAjB;AACA,IAAM8V,QAAQ,GAAG,IAAIC,UAAJ,CAAe/V,SAAf,CAAjB;AACA,IAAMgW,QAAQ,GAAG,IAAIC,UAAJ,CAAejW,SAAf,CAAjB;AACA,IAAMkW,QAAQ,GAAG,IAAIC,UAAJ,CAAenW,SAAf,CAAjB;AACA,IAAMoW,QAAQ,GAAG,IAAIC,UAAJ,CAAerW,SAAf,CAAjB;AACA,IAAMsW,QAAQ,GAAG,IAAIC,UAAJ,CAAevW,SAAf,CAAjB;AACA,IAAMwW,QAAQ,GAAG,IAAIC,UAAJ,CAAezW,SAAf,CAAjB;AACA,IAAM0W,QAAQ,GAAG,IAAIC,UAAJ,CAAe3W,SAAf,CAAjB;AACA,IAAM4W,QAAQ,GAAG,IAAIC,UAAJ,CAAe7W,SAAf,CAAjB;AACA,IAAM8W,QAAQ,GAAG,IAAIC,UAAJ,CAAe/W,SAAf,CAAjB;AACA,IAAMgX,QAAQ,GAAG,IAAIC,UAAJ,CAAejX,SAAf,CAAjB;AACA,IAAMkX,QAAQ,GAAG,IAAIC,UAAJ,CAAenX,SAAf,CAAjB;AACA,IAAMoX,QAAQ,GAAG,IAAIC,UAAJ,CAAerX,SAAf,CAAjB;AACA,IAAMsX,QAAQ,GAAG,IAAIC,UAAJ,CAAevX,SAAf,CAAjB;AACA,IAAMwX,QAAQ,GAAG,IAAIC,UAAJ,CAAezX,SAAf,CAAjB;AACA,IAAM0X,QAAQ,GAAG,IAAIC,UAAJ,CAAe3X,SAAf,CAAjB;AACA,IAAM4X,QAAQ,GAAG,IAAIC,UAAJ,CAAe7X,SAAf,CAAjB;AACA,IAAM8X,QAAQ,GAAG,IAAIC,UAAJ,CAAe/X,SAAf,CAAjB;AACA,IAAMgY,QAAQ,GAAG,IAAIC,UAAJ,CAAejY,SAAf,CAAjB;AACA,IAAMkY,QAAQ,GAAG,IAAIC,UAAJ,CAAenY,SAAf,CAAjB;AACA,IAAMoY,QAAQ,GAAG,IAAIC,UAAJ,CAAerY,SAAf,CAAjB;AACA,IAAMsY,QAAQ,GAAG,IAAIC,UAAJ,CAAevY,SAAf,CAAjB;AACA,IAAMwY,QAAQ,GAAG,IAAIC,UAAJ,CAAezY,SAAf,CAAjB;AACA,IAAM0Y,QAAQ,GAAG,IAAIC,UAAJ,CAAe3Y,SAAf,CAAjB;AACA,IAAM4Y,QAAQ,GAAG,IAAIC,UAAJ,CAAe7Y,SAAf,CAAjB;AACA,IAAM8Y,QAAQ,GAAG,IAAIC,UAAJ,CAAe/Y,SAAf,CAAjB;AACA,IAAMgZ,QAAQ,GAAG,IAAIC,UAAJ,CAAejZ,SAAf,CAAjB;AACA,IAAMkZ,QAAQ,GAAG,IAAIC,UAAJ,CAAenZ,SAAf,CAAjB;AACA,IAAMoZ,QAAQ,GAAG,IAAIC,UAAJ,CAAerZ,SAAf,CAAjB;AACA,IAAMsZ,QAAQ,GAAG,IAAIC,UAAJ,CAAevZ,SAAf,CAAjB;AACA,IAAMwZ,QAAQ,GAAG,IAAIC,UAAJ,CAAezZ,SAAf,CAAjB;AACA,IAAM0Z,QAAQ,GAAG,IAAIC,UAAJ,CAAe3Z,SAAf,CAAjB;AACA,IAAM4Z,QAAQ,GAAG,IAAIC,UAAJ,CAAe7Z,SAAf,CAAjB;AACA,IAAM8Z,QAAQ,GAAG,IAAIC,UAAJ,CAAe/Z,SAAf,CAAjB;AACA,IAAMga,QAAQ,GAAG,IAAIC,UAAJ,CAAeja,SAAf,CAAjB;AACA,IAAMka,QAAQ,GAAG,IAAIC,UAAJ,CAAena,SAAf,CAAjB;AACA,IAAMoa,QAAQ,GAAG,IAAIC,UAAJ,CAAera,SAAf,CAAjB;AACA,IAAMsa,QAAQ,GAAG,IAAIC,UAAJ,CAAeva,SAAf,CAAjB;AACA,IAAMwa,QAAQ,GAAG,IAAIC,UAAJ,CAAeza,SAAf,CAAjB;AACA,IAAM0a,QAAQ,GAAG,IAAIC,UAAJ,CAAe3a,SAAf,CAAjB;AACA,IAAM4a,QAAQ,GAAG,IAAIC,UAAJ,CAAe7a,SAAf,CAAjB;AACA,IAAM8a,QAAQ,GAAG,IAAIC,UAAJ,CAAe/a,SAAf,CAAjB;AACA,IAAMgb,QAAQ,GAAG,IAAIC,UAAJ,CAAejb,SAAf,CAAjB;AACA,IAAMkb,QAAQ,GAAG,IAAIC,UAAJ,CAAenb,SAAf,CAAjB;AACA,IAAMob,QAAQ,GAAG,IAAIC,UAAJ,CAAerb,SAAf,CAAjB;AACA,IAAMsb,QAAQ,GAAG,IAAIC,UAAJ,CAAevb,SAAf,CAAjB;AACA,IAAMwb,QAAQ,GAAG,IAAIC,UAAJ,CAAezb,SAAf,CAAjB;AACA,IAAM0b,QAAQ,GAAG,IAAIC,UAAJ,CAAe3b,SAAf,CAAjB;AACA,IAAM4b,QAAQ,GAAG,IAAIC,UAAJ,CAAe7b,SAAf,CAAjB;AACA,IAAM8b,QAAQ,GAAG,IAAIC,UAAJ,CAAe/b,SAAf,CAAjB;AACA,IAAMgc,QAAQ,GAAG,IAAIC,UAAJ,CAAejc,SAAf,CAAjB;AACA,IAAMkc,QAAQ,GAAG,IAAIC,UAAJ,CAAenc,SAAf,CAAjB;AACA,IAAMoc,QAAQ,GAAG,IAAIC,UAAJ,CAAerc,SAAf,CAAjB;AACA,IAAMsc,QAAQ,GAAG,IAAIC,UAAJ,CAAevc,SAAf,CAAjB;AACA,IAAMwc,QAAQ,GAAG,IAAIC,UAAJ,CAAezc,SAAf,CAAjB;AACA,IAAM0c,QAAQ,GAAG,IAAIC,UAAJ,CAAe3c,SAAf,CAAjB;AACA,IAAM4c,QAAQ,GAAG,IAAIC,UAAJ,CAAe7c,SAAf,CAAjB;AACA,IAAM8c,QAAQ,GAAG,IAAIC,UAAJ,CAAe/c,SAAf,CAAjB;AACA,IAAMgd,QAAQ,GAAG,IAAIC,UAAJ,CAAejd,SAAf,CAAjB;AACA,IAAMkd,QAAQ,GAAG,IAAIC,UAAJ,CAAend,SAAf,CAAjB;AACA,IAAMod,QAAQ,GAAG,IAAIC,UAAJ,CAAerd,SAAf,CAAjB;AACA,IAAMsd,QAAQ,GAAG,IAAIC,UAAJ,CAAevd,SAAf,CAAjB;AACA,IAAMwd,QAAQ,GAAG,IAAIC,UAAJ,CAAezd,SAAf,CAAjB;AACA,IAAM0d,QAAQ,GAAG,IAAIC,UAAJ,CAAe3d,SAAf,CAAjB;AACA,IAAM4d,QAAQ,GAAG,IAAIC,UAAJ,CAAe7d,SAAf,CAAjB;AACA,IAAM8d,QAAQ,GAAG,IAAIC,UAAJ,CAAe/d,SAAf,CAAjB;AACA,IAAMge,QAAQ,GAAG,IAAIC,UAAJ,CAAeje,SAAf,CAAjB;AACA,IAAMke,QAAQ,GAAG,IAAIC,UAAJ,CAAene,SAAf,CAAjB;AACA,IAAMoe,QAAQ,GAAG,IAAIC,UAAJ,CAAere,SAAf,CAAjB;AACA,IAAMse,QAAQ,GAAG,IAAIC,UAAJ,CAAeve,SAAf,CAAjB;AACA,IAAMwe,QAAQ,GAAG,IAAIC,UAAJ,CAAeze,SAAf,CAAjB;AACA,IAAM0e,QAAQ,GAAG,IAAIC,UAAJ,CAAe3e,SAAf,CAAjB;AACA,IAAM4e,QAAQ,GAAG,IAAIC,UAAJ,CAAe7e,SAAf,CAAjB;AACA,IAAM8e,QAAQ,GAAG,IAAIC,UAAJ,CAAe/e,SAAf,CAAjB;AACA,IAAMgf,QAAQ,GAAG,IAAIC,UAAJ,CAAejf,SAAf,CAAjB;AACA,IAAMkf,QAAQ,GAAG,IAAIC,UAAJ,CAAenf,SAAf,CAAjB;AACA,IAAMof,QAAQ,GAAG,IAAIC,UAAJ,CAAerf,SAAf,CAAjB;AACA,IAAMsf,QAAQ,GAAG,IAAIC,UAAJ,CAAevf,SAAf,CAAjB;AACA,IAAMwf,QAAQ,GAAG,IAAIC,UAAJ,CAAezf,SAAf,CAAjB;AACA,IAAM0f,QAAQ,GAAG,IAAIC,UAAJ,CAAe3f,SAAf,CAAjB;AACA,IAAM4f,QAAQ,GAAG,IAAIC,UAAJ,CAAe7f,SAAf,CAAjB;AACA,IAAM8f,QAAQ,GAAG,IAAIC,UAAJ,CAAe/f,SAAf,CAAjB;AACA,IAAMggB,QAAQ,GAAG,IAAIC,UAAJ,CAAejgB,SAAf,CAAjB;AACA,IAAMkgB,QAAQ,GAAG,IAAIC,UAAJ,CAAengB,SAAf,CAAjB;AACA,IAAMogB,QAAQ,GAAG,IAAIC,UAAJ,CAAergB,SAAf,CAAjB;AACA,IAAMsgB,QAAQ,GAAG,IAAIC,UAAJ,CAAevgB,SAAf,CAAjB;AACA,IAAMwgB,QAAQ,GAAG,IAAIC,UAAJ,CAAezgB,SAAf,CAAjB;AACA,IAAM0gB,QAAQ,GAAG,IAAIC,UAAJ,CAAe3gB,SAAf,CAAjB;AACA,IAAM4gB,QAAQ,GAAG,IAAIC,UAAJ,CAAe7gB,SAAf,CAAjB;AACA,IAAM8gB,QAAQ,GAAG,IAAIC,UAAJ,CAAe/gB,SAAf,CAAjB;AACA,IAAMghB,QAAQ,GAAG,IAAIC,UAAJ,CAAejhB,SAAf,CAAjB;AACA,IAAMkhB,QAAQ,GAAG,IAAIC,UAAJ,CAAenhB,SAAf,CAAjB;AACA,IAAMohB,QAAQ,GAAG,IAAIC,UAAJ,CAAerhB,SAAf,CAAjB;AACA,IAAMshB,QAAQ,GAAG,IAAIC,UAAJ,CAAevhB,SAAf,CAAjB;AACA,IAAMwhB,QAAQ,GAAG,IAAIC,UAAJ,CAAezhB,SAAf,CAAjB;AACA,IAAM0hB,QAAQ,GAAG,IAAIC,UAAJ,CAAe3hB,SAAf,CAAjB;AACA,IAAM4hB,QAAQ,GAAG,IAAIC,UAAJ,CAAe7hB,SAAf,CAAjB;AACA,IAAM8hB,QAAQ,GAAG,IAAIC,UAAJ,CAAe/hB,SAAf,CAAjB;AACA,IAAMgiB,QAAQ,GAAG,IAAIC,UAAJ,CAAejiB,SAAf,CAAjB;AACA,IAAMkiB,QAAQ,GAAG,IAAIC,UAAJ,CAAeniB,SAAf,CAAjB;AACA,IAAMoiB,QAAQ,GAAG,IAAIC,UAAJ,CAAeriB,SAAf,CAAjB;AACA,IAAMsiB,QAAQ,GAAG,IAAIC,UAAJ,CAAeviB,SAAf,CAAjB;AACA,IAAMwiB,QAAQ,GAAG,IAAIC,UAAJ,CAAeziB,SAAf,CAAjB;AACA,IAAM0iB,QAAQ,GAAG,IAAIC,UAAJ,CAAe3iB,SAAf,CAAjB;AACA,IAAM4iB,QAAQ,GAAG,IAAIC,UAAJ,CAAe7iB,SAAf,CAAjB;AACA,IAAM8iB,QAAQ,GAAG,IAAIC,UAAJ,CAAe/iB,SAAf,CAAjB;AACA,IAAMgjB,QAAQ,GAAG,IAAIC,UAAJ,CAAejjB,SAAf,CAAjB;AACA,IAAMkjB,QAAQ,GAAG,IAAIC,UAAJ,CAAenjB,SAAf,CAAjB;AACA,IAAMojB,QAAQ,GAAG,IAAIC,UAAJ,CAAerjB,SAAf,CAAjB;AACA,IAAMsjB,QAAQ,GAAG,IAAIC,UAAJ,CAAevjB,SAAf,CAAjB;AACA,IAAMwjB,QAAQ,GAAG,IAAIC,UAAJ,CAAezjB,SAAf,CAAjB;AACA,IAAM0jB,QAAQ,GAAG,IAAIC,UAAJ,CAAe3jB,SAAf,CAAjB;AACA,IAAM4jB,QAAQ,GAAG,IAAIC,UAAJ,CAAe7jB,SAAf,CAAjB;AACA,IAAM8jB,QAAQ,GAAG,IAAIC,UAAJ,CAAe/jB,SAAf,CAAjB;AACA,IAAMgkB,QAAQ,GAAG,IAAIC,UAAJ,CAAejkB,SAAf,CAAjB;AACA,IAAMkkB,QAAQ,GAAG,IAAIC,UAAJ,CAAenkB,SAAf,CAAjB;AACA,IAAMokB,QAAQ,GAAG,IAAIC,UAAJ,CAAerkB,SAAf,CAAjB;AACA,IAAMskB,QAAQ,GAAG,IAAIC,UAAJ,CAAevkB,SAAf,CAAjB;AACA,IAAMwkB,QAAQ,GAAG,IAAIC,UAAJ,CAAezkB,SAAf,CAAjB;AACA,IAAM0kB,QAAQ,GAAG,IAAIC,UAAJ,CAAe3kB,SAAf,CAAjB;AACA,IAAM4kB,QAAQ,GAAG,IAAIC,UAAJ,CAAe7kB,SAAf,CAAjB;AACA,IAAM8kB,QAAQ,GAAG,IAAIC,UAAJ,CAAe/kB,SAAf,CAAjB;AACA,IAAMglB,QAAQ,GAAG,IAAIC,UAAJ,CAAejlB,SAAf,CAAjB;AACA,IAAMklB,QAAQ,GAAG,IAAIC,UAAJ,CAAenlB,SAAf,CAAjB;AACA,IAAMolB,QAAQ,GAAG,IAAIC,UAAJ,CAAerlB,SAAf,CAAjB;AACA,IAAMslB,QAAQ,GAAG,IAAIC,UAAJ,CAAevlB,SAAf,CAAjB;AACA,IAAMwlB,QAAQ,GAAG,IAAIC,UAAJ,CAAezlB,SAAf,CAAjB;AACA,IAAM0lB,QAAQ,GAAG,IAAIC,UAAJ,CAAe3lB,SAAf,CAAjB;AACA,IAAM4lB,QAAQ,GAAG,IAAIC,UAAJ,CAAe7lB,

AAG,GAAGX,IAAN;AACD,SAtCD,MAsCO;AACLA,UAAAA,IAAI,GAAG3N,GAAG,CAACkI,OAAJ,CAAY,GAAAZ,EAAAiBoG,GAAAG,GAAAG,CAAAvB,CAAAP;AACA/M,UAAAAA,OAAAO,GAAAGvB,GAAAG,CAAAC0O,KAAAJ,CAAAUJ,GAAAV,EAAAeX,IAAAI,GAAAG,CAAAtB,CAAAV;;AAAEA,cAAAIA,IAAAI,KAAAK,CAAAC,CAAAV,IAAAeP,cAAAc,CrR,IAAAf,CAAAoBwF,OAAApB,CAAAnB,EAAAiD;AAAC/Cg,MAAAYFAM,YAAAP,CAAAY,CAAAC,CAAAV,IAAAeP,cAAAc,CAAAD,AD,EAAAM,GAAAN,EAAAW2I,IAAAX,EAAAiB2H,GAAAG,GAAAGtG,MAAAvB,CAAAZ;AACD,WAFD,MAEO;AACLuF,YAAAAA,MAAAM,CAAAvP,IAAAP,CAAAY,CAAAC,UAAAD,EAAAauD,OAAAb,EAAAsBoF,IAAAtB,EAAA4B2H,GAAAG,GAAAGtG,MAAAlC,CrB,IAA1C,EAAA0CrB,IAA1C,EAAAgDgH,IAAAI,GAAAG3F,MAAAvD,CAAAZ;AAACsG,YAAAAA,GAAAG,GAAAG,GAAAGX,IAAAN;AACD;AACF;;AAED;;AAEF,WAAAKhB,iBAAAK,EAAAY,CAAAC,CAAAV,IAAAeP,cAAAc,CAAAD,AD,EAAAM,GAAAN,EAAAW2I,IAAAX,EAAAiB2H,GAAAG,GAAAGtG,MAAAvB,CAAAZ;AAACsG,YAAAA,GAAAG,GAAAG,GAAAGX,IAAAN;AACD;AACF;;AAEDAA,YAAAA,GAAAG,GAAAG,GAAAGX,IAAAN;AACD;AACF;;AAEF,WAAAKhB,iBAAAK,EAAAY,CAAAC,CAAAV,IAAAeP,cAAAc,CAAAD,AD,EAAAM,GAAAN,EAAAW2I,IAAAX,EAAAiB2H,GAAAG,GAAAGtG,MAAAvB,CAAAZ;AAACsG

ACZE,YAAAA,QAAQ,GAAGrH,IAAI,GAAGmH,IAAlB;AACAG,YAAAA,UAAU,GAAGN,IAAI,GAAGE,KAAK,CAACC,IAAD,CAAL,CAAY1S,MAAhC;AACD,WAHD,MAGO;AACL4S,YAAAA,QAAQ,GAAGrH,IAAX;AACAsH,YAAAA,UAAU,GAAGjG,MAAb;AACD;;AAEDuF,UAAAA,MAAM,CAACvP,IAAP,CAAY,CAAC,SAAD,EAAYyU,OAAZ,EAAqBC,oF,IAArBD,EAA2B2H,GAA3B,GAAiCC,GAAjCC,GAAuCC,MAAvCC,GAAgDC,IAAhDC,GAAuDC,IAAvDC,GAA8DC,IAA9DC,GAAqEC,IAArEC,GAA4EC,IAA5EC,GAAmFC,IAAnFC,GAA0FC,IAA1FC,GAAiGC,IAAjGC,GAAwGC,IAAxGC,GAA+GC,IAA/GC,GAAsHC,IAAtHC,GAA6HC,IAA7HC,GAAoIC,IAApIC,GAA2IC,IAA3IC,GAAkJC,IAAlJC,GAAyJC,IAAzJC,GAAgKC,IAAhKC,GAAuKC,IAAvKC,GAA8KC,IAA9KC,GAAqLC,IAArLC,GAA4LC,IAA5LC,GAAmMC,IAAnMC,GAA0MC,IAA1MC,GAAiNC,IAAjNC,GAAwNC,IAAxNC,GAA+NC,IAA/NC,GAAsOC,IAAtOC,GAA6OC,IAA7OC,GAAoPC,IAApPC,GAA2PC,IAA3PC,GAAkQC,IAAlQC,GAAyQC,IAAzQC,GAAgRC,IAAhRC,GAAuRC,IAAvRC,GAA8RC,IAA9RC,GAAqSC,IAArSC,GAA4SC,IAA5SC,GAAmTC,IAAnTC,GAA0TC,IAA1TC,GAAiUC,IAAjUC,GAAwUC,IAAxUC,GAA+UC,IAA/UC,GAAsVC,IAAtVC,GAA6VC,IAA7VC,GAAoWC,IAApWC,GAA2WC,IAA3WC,GAAkXC,IAAlXC,GAAyXC,IAAzXC,GAAgYC,IAAhYC,GAAuYC,IAAvYC,GAA8YC,IAA9YC,GAAqZC,IAArZC,GAA4ZC,IAA5ZC,GAAma,IAAna,GAAya,IAAza,GAAgb,IAAhb,GAAub,IAAvb,GAA8b,IAA9b,GAAqc,IAArc,GAA4c,IAA5c,GAAmd,IAAnd,GAA0d,IAA1d,GAAie,IAAje,GAAwe,IAAxe,GAA+e,IAA/e,GAAsf,IAAtf,GAA6f,IAA7f,GAAogB,IAApgB,GAA2gB,IAA3gB,GAAkhB,IAAlhB,GAAyhB,IAAzhB,GAAgiB,IAAhiB,GAAuiB,IAAviB,GAA8iB,IAA9iB,GAAqjB,IAArjB,GAA4jB,IAA5jB,GAAmkB,IAAnkB,GAA0kB,IAA1kB,GAAilB,IAAjlB,GAAwlB,IAAxlB,GAA+lB,IAA/lB,GAAsmB,IAAtmB,GAA6mB,IAA7mB,GAAonB,IAApnB,GAA2nB,IAA3nB,GAAkoB,IAAloB,GAAyoB,IAAzoB,GAAgpB,IAAhpB,GAAupB,IAAvpB,GAA8pB,IAA9pB,GAAqqB,IAArqB,GAA4qB,IAA5qB,GAAmrB,IAAnrB,GAA0rB,IAA1rB,GAAisB,IAAjsB,GAAwsB,IAAxsB,GAA+sB,IAA/sB,GAAstB,IAAttB,GAA6tB,IAA7tB,GAAouB,IAApuB,GAA2uB,IAA3uB,GAAkvB,IAAlvB,GAAyvB,IAAzvB,GAAgwB,IAAhwB,GAAuwB,IAAvwB,GAA8wB,IAA9wB,GAAqxB,IAArxB,GAA4xB,IAA5xB,GAAmyB,IAAnyB,GAA0yB,IAA1yB,GAAizB,IAAjzB,GAAwzB,IAAxzB,GAA+zB,IAA/zB,GAAs0B,IAAt0B,GAA60B,IAA70B,GAAo1B,IAAp1B,GAA21B,IAA31B,GAAk2B,IAAl2B,GAAy2B,IAAz2B,GAAg3B,IAAh3B,GAAu3B,IAAv3B,GAA83B,IAA93B,GAAq4B,IAAr4B,GAA44B,IAA54B,GAAm5B,IAAn5B,GAA05B,IAA15B,GAAi6B,IAAj6B,GAAw6B,IAAx6B,GAA+6B,IAA/6B,GAAs7B,IAAt7B,GAA67B,IAA77B,GAAo8B,IAAp8B,GAA28B,IAA38B,GAAk9B,IAAl9B,GAAy9B,IAAz9B,GAAg+B,IAAh+B,GAAu+B,IAAv+B,GAA8+B,IAA9+B,GAAq/B,IAAr/B,GAA4/B,IAA5/B,GAAmgC,IAAngC,GAA0gC,IAA1gC,GAAihC,IAAjhC,GAAwhC,IAAxhC,GAA+hC,IAA/hC,GAAsiC,IAAtiC,GAA6iC,IAA7iC,GAAojC,IAApjC,GAA2jC,IAA3jC,GAAkkC,IAAlkC,GAAykC,IAAzkC,GAAglC,IAAhlC,GAAulC,IAAvlC,GAA8lC,IAA9lC,GAAqmC,IAArmC,GAA4mC,IAA5mC,GAAmnC,IAAnnC,GAA0nC,IAA1nC,GAAioC,IAAjoC,GAAwoC,IAAxoC,GAA+oC,IAA/oC,GAAspC,IAAtpC,GAA6pC,IAA7pC,GAAoqC,IAApqC,GAA2qC,IAA3qC,GAAkrC,IAAlrC,GAAyrC,IAAzrC,GAAgsC,IAAhsC,GAAusC,IAAvsC,GAA8sC,IAA9sC,GAAqtC,IAArtC,GAA4tC,IAA5tC,GAAmuC,IAAnuC,GAA0uC,IAA1uC,GAAivC,IAAjvC,GAAwvC,IAAxvC,GAA+vC,IAA/vC,GAAswC,IAAtwC,GAA6wC,IAA7wC,GAAoxC,IAApxC,GAA2xC,IAA3xC,GAAkyC,IAAlyC,GAAyyC,IAAzyC,GAAgzC,IAAhzC,GAAuzC,IAAvzC,GAA8zC,IAA9zC,GAAq0C,IAAr0C,GAA40C,IAA50C,GAAm1C,IAAn1C,GAA01C,IAA11C,GAAi2C,IAAj2C,GAAw2C,IAAx2C,GAA+2C,IAA/2C,GAAs3C,IAAt3C,GAA63C,IAA73C,GAAo4C,IAAp4C,GAA24C,IAA34C,GAAk5C,IAAl5C,GAAy5C,IAAz5C,GAAg6C,IAAh6C,GAAu6C,IAAv6C,GAA86C,IAA96C,GAAq7C,IAAr7C,GAA47C,IAA57C,GAAm8C,IAAn8C,GAA08C,IAA18C,GAAi9C,IAAj9C,GAAw9C,IAAx9C,GAA+9C,IAA/9C,GAAs+C,IAAt+C,GAA6+C,IAA7+C,GAAo/C,IAAp/C,GAA2/C,IAA3/C,GAAkgD,IAAlgD,GAAygD,IAAzgD,GAAghD,IAAhhD,GAAuhD,IAAvhD,GAA8hD,IAA9hD,GAAqiD,IAAriD,GAA4iD,IAA5iD,GAAmjD,IAAnjD,GAA0jD,IAA1jD,GAAikD,IAAjkD,GAAwkD,IAAxkD,GAA+kD,IAA/kD,GAAslD,IAAtlD,GAA6lD,IAA7lD,GAAomD,IAApmD,GAA2mD,IAA3mD,GAAknD,IAAlnD,GAAynD,IAAznD,GAAgoD,IAAhoD,GAAuoD,IAAvoD,GAA8oD,IAA9oD,GAAqpD,IAArpD,GAA4pD,IAA5pD,GAAmqD,IAAnqD,GAA0qD,IAA1qD,GAAirD,IAAjrD,GAAwrD,IAAxrD,GAA+rD,IAA/rD,GAAssD,IAAtsD,GAA6sD,IAA7sD,GAAotD,IAAptD,GAA2tD,IAA3tD,GAAkuD,IAAluD,GAAyuD,IAAzuD,GAAgvD,IAAhvD,GAAuvD,IAAvvD,GAA8vD,IAA9vD,GAAqwD,IAArwD,GAA4wD,IAA5wD,GAAmxD,IAAnxD,GAA0xD,IAA1xD,GAAiyD,IAAjyD,GAAwyD,IAAxyD,GAA+yD,IAA/yD,GAAszD,IAAtzD,GAA6zD,IAA7zD,GAAo0D,IAAp0D,GAA20D,IAA30D,GAAk1D,IAAl1D,GAAy1D,IAAz1D,GAAg2D,IAAh2D,GAAu2D,IAAv2D,GAA82D,IAA92D,GAAq3D,IAAr3D,GAA43D,IAA53D,GAAm4D,IAAn4D,GAA04D,IAA14D,GAAi5D,IAAj5D,GAAw5D,IAAx5D,GAA+5D,IAA/5D,GAAs6D,IAAt6D,GAA66D,IAA76D,GAAo7D,IAAp7D,GAA27D,IAA37D,GAAk8D,IAAl8D,GAAy8D,IAAz8D,GAAg9D,IAAh9D,GAAu9D,IAAv9D,GAA89D,IAA99D,GAAq+D,IAAr+D,GAA4+D,IAA5+D,GAAm/D,IAAn/D,GAA0/D,IAA1/D,GAAigE,IAAjgE,GAAwgE,IAAxgE,GAA+gE,IAA/gE,GAAshE,IAAthE,GAA6hE,IAA7hE,GAAoiE,IAApiE,GAA2iE,IAA3iE,GAAkjE,IAAljE,GAAyjE,IAAzjE,GAAgkE,IAAhkE,GAAukE,IAAvkE,GAA8kE,IAA9kE,GAAqlE,IAArlE,GAA4lE,IAA5lE,GAAmmE,IAAnmE,GAA0mE,IAA1mE,GAAinE,IAAjnE,GAAwnE,IAAxnE,GAA+nE,IAA/nE,GAAsoE,IAAtoE,GAA6oE,IAA7oE,GAAopE,IAAppE,GAA2pE,IAA3pE,GAAkqE,IAAlqE,GAAyqE,IAAzqE,GAAgrE,IAAhrE,GAAurE,IAAvrE,GAA8rE,IAA9rE,GAAqsE,IAArsE,GAA4sE,IAA5sE,GAAmtE,IAAntE,GAA0tE,IAA1tE,GAAiuE,IAAjuE,GAAwuE,IAAxuE,GAA+uE,IAA/uE,GAAsvE,IAAtvE,GAA6vE,IAA7vE,GAAowE,IAApwE,GAA2wE,IAA3wE,GAAkxE,IAAlxE,GAAyxE,IAAzxE,GAAgyE,IAAhyE,GAAuyE,IAAvyE,GAA8yE,IAA9yE,GAAqzE,IAArzE,GAA4zE,IAA5zE,GAAm0E,IAAn0E,GAA00E,IAA10E,GAAi1E,IAAj1E,GAAw1E,IAAx1E,GAA+1E,IAA/1E,GAAs2E,IAAt2E,GAA62E,IAA72E,GAAo3E,IAAp3E,GAA23E,IAA33E,GAAk4E,IAAl4E,GAAy4E,IAAz4E,GAAg5E,IAAh5E,GAAu5E,IAAv5E,GAA85E,IAA95E,GAAq6E,IAAr6E,GAA46E,IAA56E,GAAm7E,IAAn7E,GAA07E,IAA17E,GAAi8E,IAAj8E,GAAw8E,IAAx8E,GAA+8E,IAA/8E,GAAs9E,IAAt9E,GAA69E,IAA79E,GAAo+E,IAAp+E,GAA2+E,IAA3+E,GAAk/E,IAAl/E,GAAy/E,IAAz/E,GAAggF,IAAhgF,GAAugF,IAAvgF,GAA8gF,IAA9gF,GAAqhF,IAArhF,GAA4hF,IAA5hF,GAAmiF,IAAniF,GAA0iF,IAA1iF,GAAijF,IAAjjF,GAAwjF,IAAxjF,GAA+jF,IAA/jF,GAAskF,IAAtkF,GAA6kF,IAA7kF,GAAolF,IAAplF,GAA2lF,IAA3lF,GAAkmF,IAAlmF,GAAymF,IAAzmF,GAAgnF,IAAhnF,GAAunF,IAAvnF,GAA8nF,IAA9nF,GAAqoF,IAAroF,GAA4oF,IAA5oF,GAAmpF,IAAnpF,GAA0pF,IAA1pF,GAAiqF,IAAjqF,GAAwqF,IAAxqF,GAA+qF,IAA/qF,GAAsrF,IAAtrF,GAA6rF,IAA7rF,GAAosF,IAApsF,GAA2sF,IAA3sF,GAAktF,IAAltF,GAAytF,IAAztF,GAAguF,IAAhuF,GAAuuF,IAAvuF,GAA8uF,IAA9uF,GAAqvF,IAArvF,GAA4vF,IAA5vF,GAAmwF,IAAnwF,GAA0wF,IAA1wF,GAAixF,IAAjxF,GAAwxF,IAAxxF,GAA+xF,IAA/xF,GAAsyF,IAAtyF,GAA6yF,IAA7yF,GAAozF,IAApzF,GAA2zF,IAA3zF,GAAk0F,IAAl0F,GAAy0F,IAAz0F,GAAg1F,IAAh1F,GAAu1F,IAAv1F,GAA81F,IAA91F,GAAq2F,IAAr2F,GAA42F,IAA52F,GAAm3F,IAAn3F,GAA03F,IAA13F,GAAi4F,IAAj4F,GAAw4F,IAAx4F,GAA+4F,IAA/4F,GAAs5F,IAAt5F,GAA65F,IAA75F,GAAo6F,IAAp6F,GAA26F,IAA36F,GAAk7F,IAAl7F,GAAy7F,IAAz7F,GAAg8F,IAAh8F,GAAu8F,IAAv8F,GAA88F,IAA98F,GAAq9F,IAAr9F,GAA49F,IAA59F,GAAm+F,IAAn+F,GAA0+F,IAA1+F,GAAi/F,IAAj/F,GAAw/F,IAAx/F,GAA+/F,IAA//F,GAAsgG,IAAtgG,GAA6gG,IAA7gG,GAAohG,IAAphG,GAA2hG,IAA3hG,GAAkiG,IAAliG,GAAyiG,IAAziG,GAAgjG,IAAhjG,GAAujG,IAAvjG,GAA8jG,IAA9jG,GAAqkG,IAArkG,GAA4kG,IAA5kG,GAAmlG,IAAnlG,GAA0lG,IAA1lG,GAAimG,IAAjmG,GAAwmG,IAAxmG,GAA+mG,IAA/mG,GAAsnG,IAAtnG,GAA6nG,IAA7nG,GAAooG,IAApoG,GAA2oG,IAA3oG,GAAkpG,IAAlpG,GAAypG,IAAzpG,GAAgqG,IAAhqG,GAAuqG,IAAvqG,GAA8qG,IAA9qG,GAAqrG,IAArrG,GAA4rG,IAA5rG,GAAmsG,IAAnsG,GAA0sG,IAA1sG,GAAitG,IAAjtG,GAAwtG,IAAxtG,GAA+tG,IAA/tG,GAAsuG,IAAtuG,GAA6uG,IAA7uG,GAAovG,IAApvG,GAA2vG,IAA3vG,GAAkwG,IAAlwG,GAAywG,IAAzwG,GAAgxG,IAAhxG,GAAuxG,IAAvxG,GAA8xG,IAA9xG,GAAqyG,IAAryG,GAA4yG,IAA5yG,GAAmzG,IAAnzG,GAA0zG,IAA1zG,GAAi0G,IAAj0G,GAAw0G,IAAx0G,GAA+0G,IAA/0G,GAAs1G,IAAt1G,GAA61G,IAA71G,GAAo2G,IAAp2G,GAA22G,IAA32G,GAAk3G,IAAl3G,GAAy3G,IAAz3G,GAAg4G,IAAh4G,GAAu4G,IAAv4G,GAA84G,IAA94G,GAAq5G,IAAr5G,GAA45G,IAA55G,GAAm6G,IAAn6G,GAA06G,IAA16G,GAAi7G,IAAj7G,GAAw7G,IAAx7G,GAA+7G,IAA/7G,GAAs8G,IAAt8G,GAA68G,IAA78G,GAAo9G,IAAp9G,GAA29G,IAA39G,GAAk+G,IAAl+G,GAAy+G,IAAz+G,GAAg/G,IAAh/G,GAAu/G,IAAv/G,GAA8/G,IAA9/G,GAAqgH,IAArgH,GAA4gH,IAA5gH,GAAmhH,IAAnhH,GAA0hH,IAA1hH,GAAiiH,IAAjiH,GAAwiH,IAAxiH,GAA+iH,IAA/iH,GAAsjH,IAAtjH,GAA6jH,IAA7jH,GAAokH,IAApkH,GAA2kH,IAA3kH,GAAklH,IAAllH,GAAylH,IAAzlH,GAAgmH,IAAhmH,GAAumH,IAAvmH,GAA8mH,IAA9mH,GAAqnH,IAArnH,GAA4nH,IAA5nH,GAAmoH,IAAnoH,GAA0oH,IAA1oH,GAAipH,IAAjpH,GAAwpH,IAAxpH,GAA+pH,IAA/pH,GAAsqH,IAAtqH,GAA6qH,IAA7qH,GAAorH,IAAprH,GAA2rH,IAA3rH,GAAksH,IAAlsH,GAAysH,IAAzsH,GAAgtH,IAAhtH,GAAutH,IAAvtH,GAA8tH,IAA9tH,GAAquH,IAAruH,GAA4uH,IAA5uH,GAAmvH,IAAnvH,GAA0vH,IAA1vH,GAAiwH,IAAjwH,GAAwwH,IAAxwH,GAA+wH,IAA/wH,GAAsxH,IAAtxH,GAA6xH,IAA7xH,GAAoyH,IAApyH,GAA2yH,IAA3yH,GAAkzH,IAAlzH,GAAyzH,IAAzzH,GAAg0H,IAAh0H,GAAu0H,IAAv0H,GAA80H,IAA90H,GAAq1H,IAAr1H,GAA41H,IAA51H,GAAm2H,IAAn2H,GAA02H,IAA12H,GAAi3H,IAAj3H,GAAw3H,IAAx3H,GAA+3H,IAA/3H,GAAs4H,IAAt4H,GAA64H,IAA74H,GAAo5H,IAAp5H,GAA25H,IAA35H,GAAk6H,IAAl6H,GAAy6H,IAAz6H,GAAg7H,IAAh7H,GAAu7H,IAAv7H,GAA87H,IAA97H,GAAq8H,IAAr8H,GAA48H,IAA58H,GAAm9H,IAAn9H,GAA09H,IAA19H,GAAi+H,IAAj+H,GAAw+H,IAAx+H,GAA++H,IAA/+H,GAAs/H,IAAt/H,GAA6/H,IAA7/H,GAAogI,IAApgI,GAA2gI,IAA3gI,GAAkhI,IAAlhI,GAAyhI,IAAzhI,GAAgiI,IAAhiI,GAAuiI,IAAviI,GAA8iI,IAA9iI,GAAqjI,IAArjI,GAA4jI,IAA5jI,GAAmkI,IAAnkI,GAA0kI,IAA1kI,GAAilI,IAAjlI,GAAwlI,IAAxlI,GAA+lI,IAA/lI,GAAsmI,IAAtmI,GAA6mI,IAA7mI,GAAonI,IAApnI,GAA2nI,IAA3nI,GAAkoI,IAAloI,GAAyoI,IAAzoI,GAAgpI,IAAhpI,GAAupI,IAAvpI,GAA8pI,IAA9pI,GAAqqI,IAArqI,GAA4qI,IAA5qI,GAAmrI,IAAnrI,GAA0rI,IAA1rI,GAAisI,IAAjsI,GAAwsI,IAAxsI,GAA+sI,IAA/sI,GAAstI,IAAttI,GAA6tI,IAA7tI,GAAouI,IAApuI,GAA2uI,IAA3uI,GAAkvI,IAAlvI,GAAyvI,IAAzvI,GAAgwI,IAAhwI,GAAuwI,IAAvwI,GAA8wI,IAA9wI,GAAqxI,IAArxI,GAA4xI,IAA5xI,GAAmyI,IAAnyI,GAA0yI,IAA1yI,GAAizI,IAAjzI,GAAwzI,IAAxzI,GAA+zI,IAA/zI,GAAs0I,IAAt0I,GAA60I,IAA70I,GAAo1I,IAAp1I,GAA21I,IAA31I,GAAk2I,IAAl2I,GAAy2I,IAAz2I,GAAg3I,IAAh3I,GAAu3I,IAAv3I,GAA83I,IAA93I,GAAq4I,IAAr4I,GAA44I,IAA54I,GAAm5I,IAAn5I,GAA05I,IAA15I,GAAi6I,IAAj6I,GAAw6I,IAAx6I,GAA+6I,IAA/6I,GAAs7I,IAAt7I,GAA67I,IAA77I,GAAo8I,IAAp8I,GAA28I,IAA38I,GAAk9I,IAAl9I,GAAy9I,IAAz9I,GAAg+I,IAAh+I,GAAu+I,IAAv+I,GAA8+I,IAA9+I,GAAq/I,IAAr/I,GAA4/I,IAA5/I,GAAmgJ,IAAngJ,GAA0gJ,IAA1gJ,GAAihJ,IAAjhJ,GAAwhJ,IAAxhJ,GAA+hJ,IAA/hJ,GAAsiJ,IAAtiJ,GAA6iJ,IAA7iJ,GAAojJ,IAApjJ,GAA2jJ,IAA3jJ,GAAkkJ,IAAlkJ,GAAykJ,IAAzkJ,GAAglJ,IAAhlJ,GAAulJ,IAAvlJ,GAA8lJ,IAA9lJ,GAAqmJ,IAArmJ,GAA4mJ,IAA5mJ,GAAmnJ,IAAnnJ,GAA0nJ,IAA1nJ,GAAioJ,IAAjoJ,GAAwoJ,IAAxoJ,GAA+oJ,IAA/oJ,GAAspJ,IAAtpJ,GAA6pJ,IAA7pJ,GAAoqJ,IAApqJ,GAA2qJ,IAA3qJ,GAAkrJ,IAAlrJ,GAAyrJ,IAAzrJ,GAAgsJ,IAAhsJ,GAAusJ,IAAvsJ,GAA8sJ,IAA9sJ,GAAqtJ,IAArtJ,GAA4tJ,IAA5tJ,GAAmuJ,IAAnuJ,GAA0uJ,IAA1uJ,GAAivJ,IAAjvJ,GAAwvJ,IAAxvJ,GAA+vJ,IAA/vJ,GAAswJ,IAAtwJ,GAA6wJ,IAA7wJ,GAAoxJ,IAApxJ,GAA2xJ,IAA3xJ,GAAkyJ,IAAlyJ,GAAyyJ,IAAzyJ,GAAgzJ,IAAhzJ,GAAuzJ,IAAvzJ,GAA8zJ,IAA9zJ,GAAq0J,IAAr0J,GAA40J,IAA50J,GAAm1J,IAAn1J,GAA01J,IAA11J,GAAi2J,IAAj2J,GAAw2J,IAAx2J,GAA+2J,IAA/2J,GAAs3J,IAAt3J,GAA63J,IAA73J,GAAo4J,IAAp4J,GAA24J,IAA34J,GAAk5J,IAAl5J,GAAy5J,IAAz5J,GAAg6J,IAAh6J,GAAu6J,IAAv6J,GAA86J,IAA96J,GAAq7J,IAAr7J,GAA47J,IAA57J,GAAm8J,IAAn8J,GAA08J,IAA18J,GAAi9J,IAAj9J,GAAw9J,IAAx9J,GAA+9J,IAA/9J,GAAs+J,IAAt+J,GAA6+J,IAA7+J,GAAo/J,IAAp/J,GAA2/J,IAA3/J,GAAkgK,IAAlgK,GAAygK,IAAzgK,GAAghK,IAAhhK,GAAuhK,IAAvhK,GAA8hK,IAA9hK,GAAqiK,IAAriK,GAA4iK,IAA5iK,GAAmjK,IAAnjK,GAA0jK,IAA1jK,GAAikK,IAAjkK,GAAwkK,IAAxkK,GAA+kK,IAA/kK,GAAslK,IAAtlK,GAA6lK,IAA7lK,GAAomK,IAApmK,GAA2mK,IAA3mK,GAAknK,IAAlnK,GAAynK,IAAznK,GAAgoK,IAAhoK,GAAuoK,IAAvoK,GAA8oK,IAA9oK,GAAqpK,IAArpK,GAA4pK,IAA5pK,GAAmqK,IAAnqK,GAA0qK,IAA1qK,GAAirK,IAAjrK,GAAwrK,IAAxrK,GAA+rK,IAA/rK,GAAssK,IAAtsK,GAA6sK,IAA7sK,GAAotK,IAAptK,GAA2tK,IAA3tK,GAAkuK,IAAluK,GAAyuK,IAAzuK,GAAgvK,IAAhvK,GAAuvK,IAAvvK,GAA8vK,IAA9vK,GAAqwK,IAArwK,GAA4wK,IAA5wK,GAAmxK,IAAnxK,GAA0xK,IAA1xK,GAAiyK,IAAjyK,GAAwyK,IAAxyK,GAA+yK,IAA/yK,GAAszK,IAAtzK,GAA6zK,IAA7zK,GAAo0K,IAAp0K,GAA20K,IAA30K,GAAk1K,IAAl1K,GAAy1K,IAAz1K,GAAg2K,IAAh2K,GAAu2K,IAAv2K,GAA82K,IAA92K,GAAq3K,IAAr3K,GAA43K,IAA53K,GAAm4K,IAAn4K,GAA04K,IAA14K,GAAi5K,IAAj5K,GAAw5K,IAAx5K,GAA+5K,IAA/5K,GAAs6K,IAAt6K,GAA66K,IAA76K,GAAo7K,IAAp7K,GAA27K,IAA37K,GAAk8K,IAAl8K,GAAy8K,IAAz8K,GAAg9K,IAAh9K,GAAu9K,IAAv9K,GAA89K,IAA99K,GAAq+K,IAAr+K,GAA4+K,IAA5+K,GAAm/K,IAAn/K,GAA0/K,IAA1/K,GAAigL,IAAjgL,GAAwgL,IAAxgL,GAA+gL,IAA/gL,GAAshL,IAAthL,GAA6hL,IAA7hL,GAAoiL,IAApiL,GAA2iL,IAA3iL,GAAkjL,IAAljL,GAAyjL,IAAzjL,GAAgkL,IAAhkL,GAAukL,IAAvkL,GAA8kL,IAA9kL,GAAqlL,IAArlL,GAA4lL,IAA5lL,GAAmmL,IAAnmL,GAA0mL,IAA1mL,GAAinL,IAAjnL,GAAwnL,IAAxnL,GAA+nL,IAA/nL,GAAsoL,IAAtoL,GAA6oL,IAA7oL,GAAopL,IAAppL,GAA2pL,IAA3pL,GAAkqL,IAAlqL,GAAyqL,IAAzqL,GAAgrL,IAAhrL,GAAurL,IAAvrL,GAA8rL,IAA9rL,GAAqsL,IAArsL,GAA4sL,IAA5sL,GAAmtL,IAAntL,GAA0tL,IAA1tL,GAAiuL,IAAjuL,GAAwuL,IAAxuL,GAA+uL,IAA/uL,GAAsvL,IAAtvL,GAA6vL,IAA7vL,GAAowL,IAApwL,GAA2wL,IAA3wL,GAAkxL,IAAlxL,GAAyxL,IAAzxL,GAAgyL,IAAhyL,GAAuyL,IAAvyL,GAA8yL,IAA9yL,GAAqzL,IAArzL,GAA4zL,IAA5zL,GAAm0L,IAAn0L,GAA00L,IAA10L,GAAi1L,IAAj1L,GAAw1L,IAAx1L,GAA+1L,IAA/1L,GAAs2L,IAAt2L,GAA62L,IAA72L,GAAo3L,IAAp3L,GAA23L,IAA33L,GAAk4L,IAAl4L,GAAy4L,IAAz4L,GAAg5L,IAAh5L,GAAu5L,IAAv5L,GAA85L,IAA95L,GAAq6L,IAAr6L,GAA46L,IAA56L,GAAm7L,IAAn7L,GAA07L,IAA17L,GAAi8L,IAAj8L,GAAw8L,IAAx8L,GAA+8L,IAA/8L,GAAs9L,IAAt9L,GAA69L,IAA79L,GAAo+L,IAAp+L,GAA2+L,IAA3+L,GAAk/L,IAAl/L,GAAy/L,IAAz/L,GAAggM,IAAhgM,GAAugM,IAAvgM,GAA8gM,IAA9gM,GAAqhM,IAArhM,GAA4hM,IAA5hM,GAAmiM,IAAniM,GAA0iM,IAA1iM,GAAijM,IAAjjM,GAAwjM,IAAxjM,GAA+jM,IAA/jM,GAAskM,IAAtkM,GAA6kM,IAA7kM,GAAolM,IAAplM,GAA2lM,IAA3lM,GAAkmM,IAAlmM,GAAymM,IAAzmM,GAAgnM,IAAhnM,GAAunM,IAAvnM,GAA8nM,IAA9nM,GAAqoM,IAAroM,GAA4oM,IAA5oM,GAAmpM,IAAnpM,GAA0pM,IAA1pM,GAAiqM,IAAjqM,GAAwqM,IAAxqM,GAA+qM,IAA/qM,GAAsrM,IAAtrM,GAA6rM,IAA7rM,GAAosM,IAApsM,GAA2sM,IAA3sM,GAAktM,IAAltM,GAAytM,IAAztM,GAAguM,IAAhuM,GAAuuM,IAAvuM,GAA8uM,IAA9uM,GAAqvM,IAArvM,GAA4vM,IAA5vM,GAAmwM,IAAnwM,GAA0wM,IAA1wM,GAAixM,IAAjxM,GAAwxM,IAAxxM,GAA+xM,IAA/xM,GAAsyM,IAAtyM,GAA6yM,IAA7yM,GAAozM,IAApzM,GAA2zM,IAA3zM,GAAk0M,IAAl0M,GAAy0M,IAAz0M,GAAg1M,IAAh1M,GAAu1M,IAAv1M,GAA81M,IAA91M,GAAq2M,IAAr2M,GAA42M,IAA52M,GAAm3M,IAAn3M,GAA03M,IAA13M,GAAi4M,IAAj4M,GAAw4M,IAAx4M,GAA+4M,IAA/4M,GAAs5M,IAAt5M,GAA65M,IAA75M,GAAo6M,IAAp6M,GAA26M,IAA36M,GAAk7M,IAAl7M,GAAy7M,IAAz7M,GAAg8M,IAAh8M,GAAu8M,IAAv8M,GAA88M,IAA98M,GAAq9M,IAAr9M,GAA49M,IAA59M,GAAm+M,IAAn+M,GAA0+M,IAA1+M,GAAi/M,IAAj/M,GAAw/M,IAAx/M,GAA+/M,IAA//M,GAAsgN,IAAtgN,GAA6gN,IAA7gN,GAAohN,IAAphN,GAA2hN,IAA3hN,GAAkiN,IAAliN,GAAyiN,IAAziN,GAAgjN,IAAhjN,GAAujN,IAAvjN,GAA8jN,IAA9jN,GAAqkN,IAArkN,GAA4kN,IAA5kN,GAAmlN,IAAnlN,GAA0lN,IAA1lN,GAAimN,IAAjmN,GAAwmN,IAAxmN,GAA+mN,IAA/mN,GAAsnN,IAAtnN,GAA6nN,IAA7nN,GAAooN,IAApoN,GAA2oN,IAA3oN,GAAkpN,IAAlpN,GAAypN,IAAzpN,GAAgqN,IAAhqN,GAAuqN,IAAvqN,GAA8qN,IAA9qN,GAAqrN,IAArrN,GAA4rN,IAA5rN,GAAmsN,IAAnsN,GAA0sN,IAA1sN,GAAitN,IAAjtN,GAAwtN,IAAxtN,GAA+tN,IAA/tN,GAAsuN,IAAtuN,GAA6uN,IAA7uN,GAAovN,IAApvN,GAA2vN,IAA3vN,GAAkwN,IAAlwN,GAAywN,IAAzwN,GAAgxN,IAAhxN,GAAuxN,IAAvxN,GAA8xN,IAA9xN,GAAqyN,IAAryN,GAA4yN,IAA5yN,GAAmzN,IAAnzN,GAA0zN,IAA1zN,GAAi0N,IAAj0N,GAAw0N,IAAx0N,GAA+0N,IAA/0N,GAAs1N,IAAt1N,GAA61N,IAA71N,GAAo2N,IAAp2N,GAA22N,IAA32N,GAAk3N,IAAl3N,GAAy3N,IAAz3N,GAAg4N,IAAh4N,GAAu4N,IAAv4N,GAA84N,IAA94N,GAAq5N,IAAr5N,GAA45N,IAA55N,GAAm6N,IAAn6N,GAA06N,IAA16N,GAAi7N,IAAj7N,GAAw7N,IAAx7N,GAA+7N,IAA/7N,GAAs8N,IAAt8N,GAA68N,IAA78N,GAAo9N,IAAp9N,GAA29N,IAA39N,GAAk+N,IAAl+N,GAAy+N,IAAz+N,GAAg/N,IAAh/N,GAAu/N,IAAv/N,GAA8/N,IAA9/N,GAAqgO,IAArgO,GAA4gO,IAA5gO,GAAmhO,IAAnhO,GAA0hO,IAA1hO,GAAiiO,IAAjiO,GAAwiO,IAAxiO,GAA+iO,IAA/iO,GAAsjO,IAAtjO,GAA6jO,IAA7jO,GAAokO,IAApkO,GAA2kO,IAA3kO,GAAklO,IAAllO,GAAylO,IAAzlO,GAAgmO,IAAhmO,GAAumO,IAAvmO,GAA8mO,IAA9mO,GAAqnO,IAArnO,GAA4nO,IAA5nO,GAAmoO,IAAnoO,GAA0oO,IAA1oO,GAAipO,IAAjpO,GAAwpO,IAAxpO,GAA+pO,IAA/pO,GAAsqO,IAAtqO,GAA6qO,IAA7qO,GAAorO,IAAprO,GAA2rO,IAA3rO,GAAksO,IAAlsO,GAAysO,IAAzsO,GAAgtO,IAAhtO,GAAutO,IAAvtO,GAA8tO,IAA9tO,GAAquO,IAAruO,GAA4uO,IAA5uO,GAAmvO,IAAnvO,GAA0vO,IAA1vO,GAAiwO,IAAjwO,GAAwwO,IAAxwO,GAA+wO,IAA/wO,GAAsxO,IAAtxO,GAA6xO,IAA7xO,GAAoyO,IAApyO,GAA2yO,IAA3yO,GAAkzO,IAAlzO,GAAyzO,IAAzzO,GAAg0O,IAAh0O,GAAu0O,IAAv0O,GAA80O,IAA90O,GAAq1O,IAAr1O,GAA41O,IAA51O,GAAm2O,IAAn2O,GAA02O,IAA12O,GAAi3O,IAAj3O,GAAw3O,IAAx3O,GAA+3O,IAA/3O,GAAs4O,IAAt4O,GAA64O,IAA74O,GAAo5O,IAAp5O,GAA25O,IAA35O,GAAk6O,IAAl6O,GAAy6O,IAAz6O,GAAg7O,IAAh7O,GAAu7O,IAAv7O,GAA87O,IAA97O,GAAq8O,IAAr8O,GAA48O,IAA58O,GAAm9O,IAAn9O,GAA09O,IAA19O,GAAi+O,IAAj+O,GAAw+O,IAAx+O,GAA++O,IAA/+O,GAAs/O,IAAt/O,GAA6/O,IAA7/O,GAAogP,IAApgP,GAA2gP,IAA3gP,GAAkhP,IAAlhP,GAAyhP,IAAzhP,GAAgiP,IAAhiP,GAAuiP,IAAviP,GAA8iP,IAA9iP,GAAqjP,IAArjP,GAA4jP,IAA5jP,GAAmkP,IAAnkP,GAA0kP,IAA1kP,GAAilP,IAAjlP,GAAwlP,IAAxlP,GAA+lP,IAA/lP,GAAsmP,IAAtmP,GAA6mP,IAA7mP,GAAonP,IAApnP,GAA2nP,IAA3nP,GAAkoP,IAAloP,GAAyoP,IAAzoP,GAAgpP,IAAhpP,GAAupP,IAAvpP,GAA8pP,IAA9pP,GAAqqP,IAArqP,GAA4qP,IAA5qP,GAAmrP,IAAnrP,GAA0rP,IAA1rP,GAAisP,IAAjsP,GAAwsP,IAAxsP,GAA+sP,IAA/sP,GAAstP,IAAttP,GAA6tP,IAA7tP,GAAouP,IAApuP,GAA2uP,IAA3uP,GAAkvP,IAAlvP,GAAyvP,IAAzvP,GAAgwP,IAAhwP,GAAuwP,IAAvwP,GAA8wP,IAA9wP,GAAqxP,IAArxP,GAA4xP,IAA5xP,GAAmyP,IAAnyP,GAA0yP,IAA1yP,GAAizP,IAAjzP,GAAwzP,IAAxzP,GAA+zP,IAA/zP,GAAs0P,IAAt0P,GAA60P,IAA70P,GAAo1P,IAAp1P,GAA21P,IAA31P,GAAk2P,IAAl2P,GAAy2P,IAAz2P,GAAg3P,IAAh3P,GAAu3P,IAAv3P,GAA83P,IAA93P,GAAq4P,IAAr4P,GAA44P,IAA54P,GAAm5P,IAAn5P,GAA05P,IAA15P,GAAi6P,IA

MAA7B;AAEA,WAAOyS,KAAK,CACTa,KADI,CACEkB,KADF,EACSE,GADT,EAEJX,GAFI,CAEA,UAACxI,IAAD,EAAO3H,KAAP,EAAAiB;AACpB,UAAMiR,MAAM,GAAGL,KAAK,GAAG,CAAR,GAAY5Q,KAA3B;AACA,UAAMkR,MAAM,GAAG,OAAID,MAAJ,EAAavB,KAAb,CAAmB,CAACsB,QAApB,CAAf;AACA,UAAMG,MAAM,GAAG,SAAOD,MAAP,EAAeE,IAAf,CAAoB,EAApB,CAAb;AACA,UAAMC,MAAM,GAAGL,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMC,MAAM,GAAGP,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAME,MAAM,GAAGR,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMG,MAAM,GAAGT,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMI,MAAM,GAAGV,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMK,MAAM,GAAGX,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMM,MAAM,GAAGZ,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMO,MAAM,GAAGb,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMQ,MAAM,GAAGd,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMS,MAAM,GAAGf,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMU,MAAM,GAAGhB,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMW,MAAM,GAAGjB,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMY,MAAM,GAAGlB,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMa,MAAM,GAAGnB,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMc,MAAM,GAAGpB,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMe,MAAM,GAAGrB,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMgB,MAAM,GAAGtB,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMiB,MAAM,GAAGvB,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMkB,MAAM,GAAGxB,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMmB,MAAM,GAAGzB,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMoB,MAAM,GAAG1B,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMqB,MAAM,GAAG3B,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMsB,MAAM,GAAG5B,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMuB,MAAM,GAAG7B,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMwB,MAAM,GAAG9B,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMyB,MAAM,GAAG/B,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM0B,MAAM,GAAGhC,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM2B,MAAM,GAAGjC,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM4B,MAAM,GAAGlC,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM6B,MAAM,GAAGnC,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM8B,MAAM,GAAGpC,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM+B,MAAM,GAAGrC,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMgC,MAAM,GAAGtC,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMiC,MAAM,GAAGvC,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMkC,MAAM,GAAGxC,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMmC,MAAM,GAAGzC,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMoC,MAAM,GAAG1C,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMqC,MAAM,GAAG3C,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMsC,MAAM,GAAG5C,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMuC,MAAM,GAAG7C,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMwC,MAAM,GAAG9C,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMyC,MAAM,GAAG/C,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM0C,MAAM,GAAGhD,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM2C,MAAM,GAAGjD,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM4C,MAAM,GAAGlD,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM6C,MAAM,GAAGnD,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM8C,MAAM,GAAGpD,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM+C,MAAM,GAAGrD,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMgD,MAAM,GAAGtD,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMiD,MAAM,GAAGvD,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMkD,MAAM,GAAGxD,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMmD,MAAM,GAAGzD,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMoD,MAAM,GAAG1D,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMqD,MAAM,GAAG3D,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMsD,MAAM,GAAG5D,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMuD,MAAM,GAAG7D,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMwD,MAAM,GAAG9D,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMyD,MAAM,GAAG/D,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM0D,MAAM,GAAGhE,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM2D,MAAM,GAAGjE,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM4D,MAAM,GAAGlE,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM6D,MAAM,GAAGnE,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM8D,MAAM,GAAGpE,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM+D,MAAM,GAAGrE,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMgE,MAAM,GAAGtE,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMiE,MAAM,GAAGvE,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMkE,MAAM,GAAGxE,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMmE,MAAM,GAAGzE,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMoE,MAAM,GAAG1E,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMqE,MAAM,GAAG3E,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMsE,MAAM,GAAG5E,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMuE,MAAM,GAAG7E,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMwE,MAAM,GAAG9E,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMyE,MAAM,GAAG/E,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM0E,MAAM,GAAGhF,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM2E,MAAM,GAAGjF,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM4E,MAAM,GAAGlF,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM6E,MAAM,GAAGnF,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM8E,MAAM,GAAGpF,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM+E,MAAM,GAAGrF,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMgF,MAAM,GAAGtF,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMiF,MAAM,GAAGvF,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMkF,MAAM,GAAGxF,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMmF,MAAM,GAAGzF,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMoF,MAAM,GAAG1F,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMqF,MAAM,GAAG3F,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMsF,MAAM,GAAG5F,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMuF,MAAM,GAAG7F,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMwF,MAAM,GAAG9F,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMyF,MAAM,GAAG/F,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAoBA,IAAjC;AACA,UAAM0F,MAAM,GAAGhG,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM2F,MAAM,GAAGjG,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM4F,MAAM,GAAGlG,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM6F,MAAM,GAAGnG,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM8F,MAAM,GAAGpG,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM+F,MAAM,GAAGrG,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMgG,MAAM,GAAGtG,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMiG,MAAM,GAAGvG,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMkG,MAAM,GAAGxG,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMmG,MAAM,GAAGzG,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMoG,MAAM,GAAG1G,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMqG,MAAM,GAAG3G,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMsG,MAAM,GAAG5G,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMuG,MAAM,GAAG7G,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMwG,MAAM,GAAG9G,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMyG,MAAM,GAAG/G,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM0G,MAAM,GAAGhH,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM2G,MAAM,GAAGjH,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM4G,MAAM,GAAGlH,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM6G,MAAM,GAAGnH,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM8G,MAAM,GAAGpH,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM+G,MAAM,GAAGrH,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMgH,MAAM,GAAGtH,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMiH,MAAM,GAAGvH,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMkH,MAAM,GAAGxH,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMmH,MAAM,GAAGzH,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMoH,MAAM,GAAG1H,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMqH,MAAM,GAAG3H,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMsH,MAAM,GAAG5H,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMuH,MAAM,GAAG7H,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMwH,MAAM,GAAG9H,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMyH,MAAM,GAAG/H,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM0H,MAAM,GAAGhI,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM2H,MAAM,GAAGjI,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM4H,MAAM,GAAGlI,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM6H,MAAM,GAAGnI,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM8H,MAAM,GAAGpI,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM+H,MAAM,GAAGrI,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMgI,MAAM,GAAGtI,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMiI,MAAM,GAAGvI,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMkI,MAAM,GAAGxI,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMmI,MAAM,GAAGzI,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMoI,MAAM,GAAG1I,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMqI,MAAM,GAAG3I,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMsI,MAAM,GAAG5I,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMuI,MAAM,GAAG7I,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMwI,MAAM,GAAG9I,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMyI,MAAM,GAAG/I,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM0I,MAAM,GAAGhJ,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM2I,MAAM,GAAGjJ,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM4I,MAAM,GAAGlJ,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM6I,MAAM,GAAGnJ,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM8I,MAAM,GAAGpJ,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM+I,MAAM,GAAGrJ,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMgJ,MAAM,GAAGtJ,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMiJ,MAAM,GAAGvJ,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMkJ,MAAM,GAAGxJ,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMmJ,MAAM,GAAGzJ,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMoJ,MAAM,GAAG1J,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMqJ,MAAM,GAAG3J,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMsJ,MAAM,GAAG5J,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMuJ,MAAM,GAAG7J,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMwJ,MAAM,GAAG9J,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMyJ,MAAM,GAAG/J,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM0J,MAAM,GAAGhK,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM2J,MAAM,GAAGjK,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM4J,MAAM,GAAGlK,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM6J,MAAM,GAAGnK,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM8J,MAAM,GAAGpK,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM+J,MAAM,GAAGrK,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMgK,MAAM,GAAGtK,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMiK,MAAM,GAAGvK,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMkK,MAAM,GAAGxK,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMmK,MAAM,GAAGzK,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMoK,MAAM,GAAG1K,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMqK,MAAM,GAAG3K,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMsK,MAAM,GAAG5K,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMuK,MAAM,GAAG7K,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMwK,MAAM,GAAG9K,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMyK,MAAM,GAAG/K,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM0K,MAAM,GAAGhL,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM2K,MAAM,GAAGjL,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM4K,MAAM,GAAGlL,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM6K,MAAM,GAAGnL,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM8K,MAAM,GAAGpL,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM+K,MAAM,GAAGrL,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMgL,MAAM,GAAGtL,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMiL,MAAM,GAAGvL,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMkL,MAAM,GAAGxL,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMmL,MAAM,GAAGzL,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMoL,MAAM,GAAG1L,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMqL,MAAM,GAAG3L,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMsL,MAAM,GAAG5L,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMuL,MAAM,GAAG7L,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMwL,MAAM,GAAG9L,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMyL,MAAM,GAAG/L,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM0L,MAAM,GAAGhM,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM2L,MAAM,GAAGjM,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM4L,MAAM,GAAGlM,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM6L,MAAM,GAAGnM,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM8L,MAAM,GAAGpM,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM+L,MAAM,GAAGrM,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMgM,MAAM,GAAGtM,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMiM,MAAM,GAAGvM,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMkM,MAAM,GAAGxM,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMmM,MAAM,GAAGzM,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMoM,MAAM,GAAG1M,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMqM,MAAM,GAAG3M,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMsM,MAAM,GAAG5M,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMuM,MAAM,GAAG7M,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMwM,MAAM,GAAG9M,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMyM,MAAM,GAAG/M,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM0M,MAAM,GAAGhN,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM2M,MAAM,GAAGjN,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM4M,MAAM,GAAGlN,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM6M,MAAM,GAAGnN,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM8M,MAAM,GAAGpN,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM+M,MAAM,GAAGrN,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMgN,MAAM,GAAGtN,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMiN,MAAM,GAAGvN,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMkN,MAAM,GAAGxN,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMmN,MAAM,GAAGzN,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMoN,MAAM,GAAG1N,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMqN,MAAM,GAAG3N,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMsN,MAAM,GAAG5N,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMuN,MAAM,GAAG7N,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMwN,MAAM,GAAG9N,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMyN,MAAM,GAAG/N,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM0N,MAAM,GAAGhO,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM2N,MAAM,GAAGjO,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM4N,MAAM,GAAGlO,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM6N,MAAM,GAAGnO,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM8N,MAAM,GAAGpO,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM+N,MAAM,GAAGrO,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMgO,MAAM,GAAGtO,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMiO,MAAM,GAAGvO,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMkO,MAAM,GAAGxO,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMmO,MAAM,GAAGzO,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMoO,MAAM,GAAG1O,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMqO,MAAM,GAAG3O,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMsO,MAAM,GAAG5O,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMuO,MAAM,GAAG7O,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMwO,MAAM,GAAG9O,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAMyO,MAAM,GAAG/O,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM0O,MAAM,GAAGhP,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM2O,MAAM,GAAGjP,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM4O,MAAM,GAAGlP,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM6O,MAAM,GAAGnP,KAAK,GAAG,CAAR,GAAY,CAACM,IAAb,GAAoBA,IAAjC;AACA,UAAM8O,MAA

ACjB,QAAMoC,OAAO,GAAG,KAAKJ,GAAL,CAASrP,IAAT,EAAe,SAAf,EAA0B,YAA1B,CAAhB;AACA,SAAK6O,OAAL,CAAgBxB,KAAK,GAAGoC,OAAxB,QAAoCzP,IAApC,EAA0C,OAA1C;AAEA,QAAIsO,KAAJ;;AACA,QAAItO,IAAI,CAACH,KAAL,GAAaG,IAAI,CAACH,KAAL,CAAWhH,MAA7B,EAAqC;AACnC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACH,KAAtB,EAA6BG,IAAI,CAACH,KAAL,CAAWhH,MAAxC,EAAgD,KAAhD;AACD;;AAED,QAAIsW,KAAK,GAAGnP,IAAI,CAACoP,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAACtP,KAAN,GAAcsP,KAAK,CAACtP,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiBC,KAAK,CAACtP,KAAvB,EAA8BsP,KAAK,CAACtP,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAEDsW,MAAAA,KAAK,GAAGA,KAAK,CAACE,WAAd;AACD;;AAED,QAAIC,KAAK,GAAGtP,IAAI,CAACuP,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAACzP,KAAN,GAAcyP,KAAK,CAACzP,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiBI,KAAK,CAACzP,KAAvB,EAA8ByP,KAAK,CAACzP,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAEDyW,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAGxP,IAAI,CAACyP,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAAC3P,KAAN,GAAc2P,KAAK,CAAC3P,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiBM,KAAK,CAAC3P,KAAvB,EAA8B2P,KAAK,CAAC3P,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAED2W,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAG1P,IAAI,CAAC2P,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAAC7P,KAAN,GAAc6P,KAAK,CAAC7P,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiBQ,KAAK,CAAC7P,KAAvB,EAA8B6P,KAAK,CAAC7P,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAED6W,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAG5P,IAAI,CAAC6P,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAAC/P,KAAN,GAAc+P,KAAK,CAAC/P,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiBU,KAAK,CAAC/P,KAAvB,EAA8B+P,KAAK,CAAC/P,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAED+W,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAG9P,IAAI,CAAC+P,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAACjQ,KAAN,GAAciQ,KAAK,CAACjQ,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiBY,KAAK,CAACjQ,KAAvB,EAA8BiQ,KAAK,CAACjQ,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAEDiX,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAGhQ,IAAI,CAACiQ,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAACnQ,KAAN,GAAcmQ,KAAK,CAACnQ,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiBc,KAAK,CAACnQ,KAAvB,EAA8BmQ,KAAK,CAACnQ,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAEDmX,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAGlQ,IAAI,CAACmQ,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAACrQ,KAAN,GAAcqQ,KAAK,CAACrQ,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiBgB,KAAK,CAACrQ,KAAvB,EAA8BqQ,KAAK,CAACrQ,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAEDqX,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAGpQ,IAAI,CAACqQ,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAACvQ,KAAN,GAAcuQ,KAAK,CAACvQ,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiBkB,KAAK,CAACvQ,KAAvB,EAA8BuQ,KAAK,CAACvQ,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAEDuX,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAGtQ,IAAI,CAACuQ,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAACzQ,KAAN,GAAcyQ,KAAK,CAACzQ,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiBoB,KAAK,CAACzQ,KAAvB,EAA8ByQ,KAAK,CAACzQ,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAEDyX,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAGxQ,IAAI,CAACyQ,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAAC3Q,KAAN,GAAc2Q,KAAK,CAAC3Q,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiBsB,KAAK,CAAC3Q,KAAvB,EAA8B2Q,KAAK,CAAC3Q,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAED2X,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAG1Q,IAAI,CAAC2Q,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAAC7Q,KAAN,GAAc6Q,KAAK,CAAC7Q,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiBwB,KAAK,CAAC7Q,KAAvB,EAA8B6Q,KAAK,CAAC7Q,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAED6X,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAG5Q,IAAI,CAAC6Q,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAAC/Q,KAAN,GAAc+Q,KAAK,CAAC/Q,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiB0B,KAAK,CAAC/Q,KAAvB,EAA8B+Q,KAAK,CAAC/Q,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAED+X,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAG9Q,IAAI,CAAC+Q,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAACjR,KAAN,GAAciR,KAAK,CAACjR,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiB4B,KAAK,CAACjR,KAAvB,EAA8BiR,KAAK,CAACjR,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAEDiY,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAGhR,IAAI,CAACiR,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAACnR,KAAN,GAAcmR,KAAK,CAACnR,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiB8B,KAAK,CAACnR,KAAvB,EAA8BmR,KAAK,CAACnR,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAEDmY,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAGlR,IAAI,CAACmR,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAACrR,KAAN,GAAcqR,KAAK,CAACrR,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiBgC,KAAK,CAACrR,KAAvB,EAA8BqR,KAAK,CAACrR,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAEDqY,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAGpR,IAAI,CAACqR,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAACvR,KAAN,GAAcuR,KAAK,CAACvR,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiBkC,KAAK,CAACvR,KAAvB,EAA8BuR,KAAK,CAACvR,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAEDuY,MAAAA,KAAK,GAAGA,KAAK,CAACD,WAAd;AACD;;AAED,QAAIG,KAAK,GAAGtR,IAAI,CAACuR,UAAjB;;AACA,WAAOD,KAAP,EAAc;AACZ,UAAIA,KAAK,CAACzR,KAAN,GAAcyR,KAAK,CAACzR,KAAN,CAAYhH,MAA9B,EAAsC;AACpC,aAAKqW,WAAL,CAAiBoC,KAAK,CAACzR,KAAvB,EAA8ByR,KAAK,CAACzR,KAAN,CAAYhH,MAA1C,EAAkD,KAAlD;AACD;;AAED,UAAIyY,KAAK,CAACC,OAAN,CAAcxR,IAAI,CAACH,KAAnB,CAAJ,EAA+B;AAC7B,aAAK,IAAIhH,MAAM,GAAG,CAAlB,EAAqBA,MAAM,GAAGmH,IAAI,CAACH,KAAL,CAAWhH,MAAzC,EAAiDA,MAAM,EAAvD,EAA2D;AACzD,eAAKqW,WAAL,CAAiBlP,IAAI,CAACH,KAAL,CAAWhH,MAAX,CAAjB,EAAqCA,MAArC,EAA6C,KAA7C;AACD;AACF;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACyR,UAAL,CAAgB5Y,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACyR,UAAL,CAAgB5Y,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC0R,UAAL,CAAgB7Y,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC0R,UAAL,CAAgB7Y,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC2R,UAAL,CAAgB9Y,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC2R,UAAL,CAAgB9Y,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC4R,UAAL,CAAgB/Y,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC4R,UAAL,CAAgB/Y,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC6R,UAAL,CAAgBhZ,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC6R,UAAL,CAAgBhZ,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC8R,UAAL,CAAgBjZ,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC8R,UAAL,CAAgBjZ,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC+R,UAAL,CAAgBlZ,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC+R,UAAL,CAAgBlZ,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACgS,UAAL,CAAgBnZ,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACgS,UAAL,CAAgBnZ,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACiS,UAAL,CAAgBpZ,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACiS,UAAL,CAAgBpZ,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACkS,UAAL,CAAgBrZ,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACkS,UAAL,CAAgBrZ,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACmS,UAAL,CAAgBtZ,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACmS,UAAL,CAAgBtZ,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACoS,UAAL,CAAgBvZ,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACoS,UAAL,CAAgBvZ,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACqS,UAAL,CAAgBxZ,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACqS,UAAL,CAAgBxZ,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACsS,UAAL,CAAgBzZ,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACsS,UAAL,CAAgBzZ,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACuS,UAAL,CAAgB1Z,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACuS,UAAL,CAAgB1Z,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACwS,UAAL,CAAgB3Z,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACwS,UAAL,CAAgB3Z,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACyS,UAAL,CAAgB5Z,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACyS,UAAL,CAAgB5Z,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC0S,UAAL,CAAgB7Z,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC0S,UAAL,CAAgB7Z,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC2S,UAAL,CAAgB9Z,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC2S,UAAL,CAAgB9Z,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC4S,UAAL,CAAgB/Z,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC4S,UAAL,CAAgB/Z,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC6S,UAAL,CAAgBha,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC6S,UAAL,CAAgBha,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC8S,UAAL,CAAgBja,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC8S,UAAL,CAAgBja,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC+S,UAAL,CAAgBla,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC+S,UAAL,CAAgBla,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACgT,UAAL,CAAgBna,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACgT,UAAL,CAAgBna,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACiT,UAAL,CAAgBpa,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACiT,UAAL,CAAgBpa,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACkT,UAAL,CAAgBra,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACkT,UAAL,CAAgBra,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACmT,UAAL,CAAgBta,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACmT,UAAL,CAAgBta,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACoT,UAAL,CAAgBva,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACoT,UAAL,CAAgBva,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACqT,UAAL,CAAgBxa,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACqT,UAAL,CAAgBxa,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACsT,UAAL,CAAgBza,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACsT,UAAL,CAAgBza,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACuT,UAAL,CAAgB1a,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACuT,UAAL,CAAgB1a,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACwT,UAAL,CAAgB3a,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACwT,UAAL,CAAgB3a,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACyT,UAAL,CAAgB5a,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACyT,UAAL,CAAgB5a,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC0T,UAAL,CAAgB7a,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC0T,UAAL,CAAgB7a,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC2T,UAAL,CAAgB9a,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC2T,UAAL,CAAgB9a,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC4T,UAAL,CAAgB/a,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC4T,UAAL,CAAgB/a,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC6T,UAAL,CAAgBhb,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC6T,UAAL,CAAgBhb,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC8T,UAAL,CAAgBjb,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC8T,UAAL,CAAgBjb,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC+T,UAAL,CAAgBlb,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC+T,UAAL,CAAgBlb,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACgU,UAAL,CAAgBnb,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACgU,UAAL,CAAgBnb,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACiU,UAAL,CAAgBpb,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACiU,UAAL,CAAgBpb,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACkU,UAAL,CAAgBrb,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACkU,UAAL,CAAgBrb,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACmU,UAAL,CAAgBtb,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACmU,UAAL,CAAgBtb,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACoU,UAAL,CAAgBvb,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACoU,UAAL,CAAgBvb,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACqU,UAAL,CAAgBxb,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACqU,UAAL,CAAgBxb,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACsU,UAAL,CAAgBzb,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACsU,UAAL,CAAgBzb,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACuU,UAAL,CAAgB1b,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACuU,UAAL,CAAgB1b,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACwU,UAAL,CAAgB3b,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACwU,UAAL,CAAgB3b,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAACyU,UAAL,CAAgB5b,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAACyU,UAAL,CAAgB5b,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC0U,UAAL,CAAgB7b,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC0U,UAAL,CAAgB7b,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC2U,UAAL,CAAgB9b,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC2U,UAAL,CAAgB9b,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC4U,UAAL,CAAgB/b,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC4U,UAAL,CAAgB/b,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC6U,UAAL,CAAgBhc,MAAhC,EAAwC;AACtC,WAAKqW,WAAL,CAAiBlP,IAAI,CAAC6U,UAAL,CAAgBhc,MAAhB,CAAjB,EAAwCA,MAAxC,EAAgD,KAAhD;AACAA,MAAAA,MAAM,EAAE;AACT;;AAED,QAAIA,MAAM,GAAG,CAAb;;AACA,WAAOA,MAAM,GAAGmH,IAAI,CAAC8U,UAAL,CAAgBjc,MAAhC,

ACD;;AACD,WAAO+H,KAAP;AACD;;SAED+I,gBAAA,uBAAc7B,IAAd,EAAoBjP,IAApB,EAA0B;AACxB,QAAI+H,KAAJ;AACAkH,IAAAA,IAAI,CAAC8B,SAAL,CAAe,UAAAnY,CAAC,EAAI;AAClB,UAAI,OAAOA,CAAC,CAACuW,IAAF,CAAOa,MAAd,KAAyB,WA7B,EAA0C;AACxCjI,QAAIA,KAAAA,IAAI,CAAC,CAAC,CAAC

WAAR,EAAf;;AAEA,OAAK,IAAM5Y,CAAX,IAAgByP,GAAhB,EAAqB;AACnB,QAAI,CAACA,GAAG,CAACG,cAAJ,CAAmB5P,CAAnB,CAAL,EAA4B;AAC5B,QAAImP,KAAK,GAAGM,GAAG,CAACzY,CAAD,EAAIA,CAAJ,CAAf;AACA,QAAMoW,IAAI,GAAGOjH,KAAKlO,QAAQ,CAAb,CAAb;;AAEA,QAAInP,CAAC,KAAKA,CAAN,IAAWA,CAAC,GAAG,CAAf,IAAoBA,CAAC,IAAIsd,IAAI,CAAC3Y,MAAlC,EAA0C;AACxC,UAAIsU,KAAK,CAACjZ,CAAD,CAAT,EAAc;AACZ,eAAOsd,IAAI,CAACtd,CAAD,CAAX;AACD;AACF;;AAED,SAAOwJ,MAAP;AACD;;AAED,SAASoU,IAAT,CAAcpU,MAAd,EAAsB;AACpB,MAAIA,MAAM,KAAK,IAAf,EAAqB;AACnB,WAAO,MAAP;AACD;;AAED,MAAIA,MAAM,KAAKA,MAAf,EAAuB;AACrB,WAAO,KAAP;AACD;;AAED,MAAIA,MAAM,KAAK,CAAf,EAAkB;AAChB,WAAO,IAAIA,MAAM,GAAG,CAAb,GAAiB,GAAjB,GAAuB,GAA9B;AACD;;AAED,MAAIA,MAAM,KAAK,QAAf,EAAyB;AACvB,WAAO,WAAP;AACD;;AAED,MAAIA,MAAM,KAAK,SAAf,EAA0B;AACxB,WAAO,YAAP;AACD;;AAED,MAAIA,MAAM,KAAK,MAAf,EAAuB;AACrB,WAAO,SAAP;AACD;;AAED,MAAIA,MAAM,KAAK,KAAf,EAAsB;AACpB,WAAO,Q

L;AACAa,IAAAA,SAAS,CAAC9R,MAAV,CAAiBuR,WAAjB,CAA6BO,SAA7B,EAAwC,IAAxC;AACA,WAAO,IAAP;AACD;AAED;;;;;;;;;;;;;;;SAcAxH,OAAA,gBAAO;AACL,QAAM3O,KAAK,GAAG,KAAKqE,MAAL,CAAYrE,KAAZ,CAAkB,IAAlB,CAAd;AACA,WAAO,KAAKqE,MAAL,CAAYjB,CAAZ,GAAgB,KAAKiB,MAAL,CAAYhB,CAAZ,GAAgBrD,KAAK,CAAC,CAAD,CAAL,GAAWA,KAAK,CAAC,CAAD,CAAvD;AACD;AAED;;;;;;;;;;;;;;;SAYAoP,OAAA,gBAAO;AACL,QAAMpP,KAAK,GAAG,KAAKqE,MAAL,CAAYrE,KAAZ,CAAkB,IAAlB,CAAd;AACA,WAAO,KAAKqE,MAAL,CAAYjB,CAAZ,GAAgB,KAAKiB,MAAL,CAAYhB,CAAZ,GAAgBrD,KAAK,CAAC,CAAD,CAAL,GAAWA,KAAK,CAAC,CAAD,CAAvD;AACD;;;SAEDqW,WAAA,kBAASC,KAAT,EAAgBC,KAAhB,EAAuB;AACrB,WAAO,KAAKC,IAAL,CAAUF,KAAV,EAAiBC,KAAjB,CAAP;AACD;;;SAEDE,OAAA,cAAKH,KAAL,EAAYC,KAAZ,EAAmB;AACjB,WAAO,IAAIG,OAAJ,CAAY,KAAKpO,CAAL,GAASgO,KAAT,GAAiB,KAAK/N,CAAL,GAASgO,KAAtC,EAA6C,KAAKjO,CAAL,GAASiO,KAAT,GAAiB,KAAKhO,CAAL,GAAS+N,KAAvE,CAAP;AACD;;;SAEDK,YAAA,mBAAUC,MAAV,EAAkB;AAChB,WAAO,KAAKtO,CAAL,KAAWsO,MAAM,CAACtO,CAAlB,IAAuB,KAAKC,CAAL,KAAWqO,MAAM,CAACrO,CAAzC,IAA8C,KAAKC,CAAL,KAAWoO,MAAM,CAACpO,CAAvE;AACD;;;SAEDqO,SAAA,gBAAOD,MAAP,EAAeE,OAAf,EAAwB;AACtB,WAAO,KAAKxO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoBwO,OAA3B;AACD;;;SAEDC,SAAA,gBAAOH,MAAP,EAAeE,OAAf,EAAwB;AACtB,WAAO,KAAKvO,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoBuO,OAA3B;AACD;;;SAEDE,SAAA,gBAAOJ,MAAP,EAAeE,OAAf,EAAwB;AACtB,WAAO,KAAKtO,CAAL,GAASoO,MAAM,CAACpO,CAAhB,GAAoBsO,OAA3B;AACD;;;SAEDG,WAAA,kBAASL,MAAT,EAAiBE,OAAjB,EAA0B;AACxB,WAAO,KAAKxO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoBwO,OAA3B;AACD;;;SAEDI,WAAA,kBAASN,MAAT,EAAiBE,OAAjB,EAA0B;AACxB,WAAO,KAAKvO,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoBuO,OAA3B;AACD;;;SAEDK,WAAA,kBAASP,MAAT,EAAiBE,OAAjB,EAA0B;AACxB,WAAO,KAAKtO,CAAL,GAASoO,MAAM,CAACpO,CAAhB,GAAoBsO,OAA3B;AACD;;;SAEDM,MAAA,aAAIR,MAAJ,EAAY;AACV,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED6O,SAAA,gBAAOT,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED8O,SAAA,gBAAOV,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED+O,SAAA,gBAAOX,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDgP,MAAA,aAAIZ,MAAJ,EAAY;AACV,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDiP,SAAA,gBAAOb,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDkP,SAAA,gBAAOd,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDmP,SAAA,gBAAOf,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDoP,SAAA,gBAAOhB,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDqP,SAAA,gBAAOjB,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDsP,SAAA,gBAAOlB,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDuP,SAAA,gBAAOnB,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDwP,SAAA,gBAAOpB,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDyP,SAAA,gBAAOrB,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED0P,SAAA,gBAAOtB,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED2P,SAAA,gBAAOvB,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED4P,SAAA,gBAAOxB,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED6P,SAAA,gBAAOzB,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED8P,SAAA,gBAAO1B,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED+P,SAAA,gBAAO3B,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDgQ,MAAA,aAAI5B,MAAJ,EAAY;AACV,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDiQ,SAAA,gBAAO7B,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDkQ,SAAA,gBAAO9B,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDmQ,SAAA,gBAAO/B,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDoQ,SAAA,gBAAOhC,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDqQ,SAAA,gBAAOjC,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDsQ,SAAA,gBAAOlC,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDuQ,SAAA,gBAAOnC,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDwQ,SAAA,gBAAOpC,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDyQ,SAAA,gBAAOrC,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED0Q,SAAA,gBAAOtC,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED2Q,SAAA,gBAAOvC,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED4Q,SAAA,gBAAOxC,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED6Q,SAAA,gBAAOzC,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED8Q,SAAA,gBAAO1C,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED+Q,SAAA,gBAAO3C,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDgR,MAAA,aAAI5C,MAAJ,EAAY;AACV,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDiR,SAAA,gBAAO7C,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDkR,SAAA,gBAAO9C,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDmR,SAAA,gBAAO/C,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDoR,SAAA,gBAAOhD,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDqR,SAAA,gBAAOjD,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDsR,SAAA,gBAAOlD,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDuR,SAAA,gBAAOnD,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDwR,SAAA,gBAAOpD,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDyR,SAAA,gBAAOrD,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED0R,SAAA,gBAAOtD,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED2R,SAAA,gBAAOvD,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED4R,SAAA,gBAAOxD,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED6R,SAAA,gBAAOzD,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED8R,SAAA,gBAAO1D,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED+R,SAAA,gBAAO3D,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDgS,MAAA,aAAI5D,MAAJ,EAAY;AACV,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDiS,SAAA,gBAAO7D,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDkS,SAAA,gBAAO9D,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDmS,SAAA,gBAAO/D,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDoS,SAAA,gBAAOhE,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDqS,SAAA,gBAAOjE,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDsS,SAAA,gBAAOlE,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDuS,SAAA,gBAAOnE,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDwS,SAAA,gBAAOpE,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDyS,SAAA,gBAAOrE,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED0S,SAAA,gBAAOtE,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED2S,SAAA,gBAAOvE,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED4S,SAAA,gBAAOxE,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED6S,SAAA,gBAAOzE,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED8S,SAAA,gBAAO1E,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED+S,SAAA,gBAAO3E,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDgT,MAAA,aAAI5E,MAAJ,EAAY;AACV,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDiT,SAAA,gBAAO7E,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDkT,SAAA,gBAAO9E,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDmT,SAAA,gBAAO/E,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDoT,SAAA,gBAAOhF,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDqT,SAAA,gBAAOjF,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDsT,SAAA,gBAAOlF,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDuT,SAAA,gBAAOnF,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDwT,SAAA,gBAAOpF,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDyT,SAAA,gBAAOrF,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED0T,SAAA,gBAAOtF,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED2T,SAAA,gBAAOvF,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED4T,SAAA,gBAAOxF,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED6T,SAAA,gBAAOzF,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED8T,SAAA,gBAAO1F,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAED+T,SAAA,gBAAO3F,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDgU,MAAA,aAAI5F,MAAJ,EAAY;AACV,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDiU,SAAA,gBAAO7F,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDkU,SAAA,gBAAO9F,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDmU,SAAA,gBAAO/F,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDoU,SAAA,gBAAOhG,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA/D;AACD;;;SAEDqU,SAAA,gBAAOjG,MAAP,EAAe;AACb,WAAO,KAAKtO,CAAL,GAASsO,MAAM,CAACtO,CAAhB,GAAoB,KAAKC,CAAL,GAASqO,MAAM,CAACrO,CAAhB,GAAoB,KAAKC,CAAL,GAASoO,MAAM,CAACpO,CAA

AjB;AACD;sBAEc0D,KAAK;AAClBhK,MAAAA,QAAQ,CAAC,yDAAD,CAAR;AACA,WAAK6F,IAAL,CAAAUS,SAAV,GAAAsB0D,GAAAtB;AACD;AAED;;;;;;;;;;AAUA;;;;;;;;;;AAUA;;;;;;;;;;AAWA;;;;;;;;;;;;;;;;;;;;;;;;;EAzDwB5B;;ACX1B;;;;;;;;IAQM8B;;;AACJ,mBAAY7B,QAAZ,EAAAsB;AAAA;;AACpB,6BAAMA,QAAN;AACA,UAAKC,IAAL,CAAAK3C,IAAAL,GAAAY,SAAAZ;AAAAoFoB;AAAGrB;;;;wBAEUsB;AACT,UAAKC,IAAL,CAAAK,oDAAAL,GAAAM,SAAAN;AAAAO,oBAAGR;AAAAS,oBAAGT;AAAAU,oBAAGV;AAAAW,oBAAGX;AAAAY,oBAAGZ;AAAAa,oBAAGb;AAAAc,oBAAGd;AAAAe,oBAAGf;AAAAgB,oBAAGhB;AAAAiB,oBAAGjB;AAAAkB,oBAAGlB;AAAAmB,oBAAGnB;AAAAoB,oBAAGpB;AAAAqB,oBAAGrB;AAAAsB,oBAAGtB;AAAAuB,oBAAGvB;AAAAwB,oBAAGxB;AAAAyB,oBAAGzB;AAAA0B,oBAAG1B;AAAA2B,oBAAG3B;AAAA4B,oBAAG5B;AAAA6B,oBAAG7B;AAAA8B,oBAAG9B;AAAA+B,oBAAG/B;AAAAgC,oBAAGhC;AAAAiC,oBAAGjC;AAAAkC,oBAAGlC;AAAAmC,oBAAGnC;AAAAoC,oBAAGpC;AAAAqC,oBAAGrC;AAAAsC,oBAAGtC;AAAAuC,oBAAGvC;AAAAwC,oBAAGxC;AAAAyC,oBAAGzC;AAAA0C,oBAAG1C;AAAA2C,oBAAG3C;AAAA4C,oBAAG5C;AAAA6C,oBAAG7C;AAAA8C,oBAAG9C;AAAA+C,oBAAG/C;AAAAgD,oBAAGhD;AAAAiD,oBAAGjD;AAAAkD,oBAAGlD;AAAAmD,oBAAGnD;AAAAoD,oBAAGpD;AAAAqD,oBAAGrD;AAAAsD,oBAAGtD;AAAAuD,oBAAGvD;AAAAwD,oBAAGxD;AAAAyD,oBAAGzD;AAAA0D,oBAAG1D;AAAA2D,oBAAG3D;AAAA4D,oBAAG5D;AAAA6D,oBAAG7D;AAAA8D,oBAAG9D;AAAA+D,oBAAG/D;AAAAgE,oBAAGhE;AAAAiE,oBAAGjE;AAAAkE,oBAAGlE;AAAAmE,oBAAGnE;AAAAoE,oBAAGpE;AAAAqE,oBAAGrE;AAAAsE,oBAAGtE;AAAAuE,oBAAGvE;AAAAwE,oBAAGxE;AAAAyE,oBAAGzE;AAAA0E,oBAAG1E;AAAA2E,oBAAG3E;AAAA4E,oBAAG5E;AAAA6E,oBAAG7E;AAAA8E,oBAAG9E;AAAA+E,oBAAG/E;AAAAgF,oBAAGhF;AAAAiF,oBAAGjF;AAAAkF,oBAAGlF;AAAAmF,oBAAGnF;AAAAoF,oBAAGpF;AAAAqF,oBAAGrF;AAAAsF,oBAAGtF;AAAAuF,oBAAGvF;AAAAwF,oBAAGxF;AAAAyF,oBAAGzF;AAAA0F,oBAAG1F;AAAA2F,oBAAG3F;AAAA4F,oBAAG5F;AAAA6F,oBAAG7F;AAAA8F,oBAAG9F;AAAA+F,oBAAG/F;AAAAgG,oBAAGhG;AAAAiG,oBAAGjG;AAAAkG,oBAAGlG;AAAAmG,oBAAGnG;AAAAoG,oBAAGpG;AAAAqG,oBAAGrG;AAAAsG,oBAAGtG;AAAAuG,oBAAGvG;AAAAwG,oBAAGxG;AAAAyG,oBAAGzG;AAAA0G,oBAAG1G;AAAA2G,oBAAG3G;AAAA4G,oBAAG5G;AAAA6G,oBAAG7G;AAAA8G,oBAAG9G;AAAA+G,oBAAG/G;AAAAgH,oBAAGhH;AAAAiH,oBAAGjH;AAAAkH,oBAAGlH;AAAAmH,oBAAGnH;AAAAoH,oBAAGpH;AAAAqH,oBAAGrH;AAAAsH,oBAAGtH;AAAAuH,oBAAGvH;AAAAwH,oBAAGxH;AAAAyH,oBAAGzH;AAAA0H,oBAAG1H;AAAA2H,oBAAG3H;AAAA4H,oBAAG5H;AAAA6H,oBAAG7H;AAAA8H,oBAAG9H;AAAA+H,oBAAG/H;AAAAgI,oBAAGhI;AAAAiI,oBAAGjI;AAAAkI,oBAAGlI;AAAAmI,oBAAGnI;AAAAoI,oBAAGpI;AAAAqI,oBAAGrI;AAAAsI,oBAAGtI;AAAAuI,oBAAGvI;AAAAwI,oBAAGxI;AAAAyI,oBAAGzI;AAAA0J,oBAAG1J;AAAA2J,oBAAG3J;AAAA4J,oBAAG5J;AAAA6J,oBAAG7J;AAAA8J,oBAAG9J;AAAA+J,oBAAG/J;AAAAgK,oBAAGhK;AAAAiK,oBAAGjK;AAAAkK,oBAAGlK;AAAAmK,oBAAGnK;AAAAoK,oBAAGpK;AAAAqK,oBAAGrK;AAAAsK,oBAAGtK;AAAAuK,oBAAGvK;AAAAwK,oBAAGxK;AAAAyK,oBAAGzK;AAAA0L,oBAAG1L;AAAA2L,oBAAG3L;AAAA4L,oBAAG5L;AAAA6L,oBAAG7L;AAAA8L,oBAAG9L;AAAA+L,oBAAG/L;AAAAgM,oBAAGhM;AAAAiM,oBAAGjM;AAAAkM,oBAAGlM;AAAAmM,oBAAGnM;AAAAoM,oBAAGpM;AAAAqM,oBAAGrM;AAAAsM,oBAAGtM;AAAAuM,oBAAGvM;AAAAwM,oBAAGxM;AAAAyM,oBAAGzM;AAAA0N,oBAAG1N;AAAA2N,oBAAG3N;AAAA4N,oBAAG5N;AAAA6N,oBAAG7N;AAAA8N,oBAAG9N;AAAA+N,oBAAG/N;AAAAgO,oBAAGhO;AAAAiO,oBAAGjO;AAAAkO,oBAAGlO;AAAAmO,oBAAGnO;AAAAoO,oBAAGpO;AAAAqO,oBAAGrO;AAAAsO,oBAAGtO;AAAAuO,oBAAGvO;AAAAwO,oBAAGxO;AAAAyO,oBAAGzO;AAAA0P,oBAAG1P;AAAA2P,oBAAG3P;AAAA4P,oBAAG5P;AAAA6P,oBAAG7P;AAAA8P,oBAAG9P;AAAA+P,oBAAG/P;AAAAgQ,oBAAGhQ;AAAAiQ,oBAAGjQ;AAAAkQ,oBAAGlQ;AAAAmQ,oBAAGnQ;AAAAoQ,oBAAGpQ;AAAAqQ,oBAAGrQ;AAAAsQ,oBAAGtQ;AAAAuQ,oBAAGvQ;AAAAwQ,oBAAGxQ;AAAAyQ,oBAAGzQ;AAAA0R,oBAAG1R;AAAA2R,oBAAG3R;AAAA4R,oBAAG5R;AAAA6R,oBAAG7R;AAAA8R,oBAAG9R;AAAA+R,oBAAG/R;AAAAgS,oBAAGhS;AAAAiS,oBAAGjS;AAAAkS,oBAAGlS;AAAAmS,oBAAGnS;AAAAoS,oBAAGpS;AAAAqS,oBAAGrS;AAAAsS,oBAAGtS;AAAAuS,oBAAGvS;AAAAwS,oBAAGxS;AAAAyS,oBAAGzS;AAAA0T,oBAAG1T;AAAA2T,oBAAG3T;AAAA4T,oBAAG5T;AAAA6T,oBAAG7T;AAAA8T,oBAAG9T;AAAA+T,oBAAG/T;AAAAgU,oBAAGhU;AAAAiU,oBAAGjU;AAAAkU,oBAAGlU;AAAAmU,oBAAGnU;AAAAoU,oBAAGpU;AAAAqU,oBAAGrU;AAAAsU,oBAAGtU;AAAAuU,oBAAGvU;AAAAwU,oBAAGxU;AAAAyU,oBAAGzU;AAAA0V,oBAAG1V;AAAA2V,oBAAG3V;AAAA4V,oBAAG5V;AAAA6V,oBAAG7V;AAAA8V,oBAAG9V;AAAA+V,oBAAG/V;AAAAgW,oBAAGhW;AAAAiW,oBAAGjW;AAAAkW,oBAAGlW;AAAAmW,oBAAGnW;AAAAoW,oBAAGpW;AAAAqW,oBAAGrW;AAAAsW,oBAAGtW;AAAAuW,oBAAGvW;AAAAwW,oBAAGxW;AAAAyW,oBAAGzW;AAAA0X,oBAAG1X;AAAA2X,oBAAG3X;AAAA4X,oBAAG5X;AAAA6X,oBAAG7X;AAAA8X,oBAAG9X;AAAA+X,oBAAG/X;AAAAgY,oBAAGhY;AAAAiY,oBAAGjY;AAAAkY,oBAAGlY;AAAAmY,oBAAGnY;AAAAoY,oBAAGpY;AAAAqY,oBAAGrY;AAAAsY,oBAAGtY;AAAAuY,oBAAGvY;AAAAwY,oBAAGxY;AAAAyY,oBAAGzY;AAAA0Z,oBAAG1Z;AAAA2Z,oBAAG3Z;AAAA4Z,oBAAG5Z;AAAA6Z,oBAAG7Z;AAAA8Z,oBAAG9Z;AAAA+Z,oBAAG/Z;AAAAgb,oBAAGhb;AAAAib,oBAAGjb;AAAAkb,oBAAGlb;AAAAmb,oBAAGnb;AAAAob,oBAAGpb;AAAAqb,oBAAGrb;AAAAsb,oBAAGtb;AAAAub,oBAAGvb;AAAAwb,oBAAGxb;AAAAyb,oBAAGzb;AAAA0c,oBAAG1c;AAAA2c,oBAAG3c;AAAA4c,oBAAG5c;AAAA6c,oBAAG7c;AAAA8c,oBAAG9c;AAAA+c,oBAAG/c;AAAAgd,oBAAGhd;AAAAid,oBAAGjd;AAAAkd,oBAAGld;AAAAmd,oBAAGnd;AAAAod,oBAAGpd;AAAAqd,oBAAGrd;AAAAsd,oBAAGtd;AAAAud,oBAAGvd;AAAAwd,oBAAGxd;AAAAyd,oBAAGzd;AAAA0e,oBAAG1e;AAAA2e,oBAAG3e;AAAA4e,oBAAG5e;AAAA6e,oBAAG7e;AAAA8e,oBAAG9e;AAAA+e,oBAAG/e;AAAAgf,oBAAGhf;AAAAif,oBAAGjf;AAAAkf,oBAAGlf;AAAAmf,oBAAGnf;AAAAof,oBAAGpf;AAAAqf,oBAAGrf;AAAAsf,oBAAGtf;AAAAuf,oBAAGvf;AAAAwf,oBAAGxf;AAAAyf,oBAAGzf;AAAA0g,oBAAG1g;AAAA2g,oBAAG3g;AAAA4g,oBAAG5g;AAAA6g,oBAAG7g;AAAA8g,oBAAG9g;AAAA+g,oBAAG/g;AAAAgh,oBAAGhh;AAAAih,oBAAGjh;AAAAkh,oBAAGlh;AAAAmh,oBAAGnh;AAAAoh,oBAAGph;AAAAqh,oBAAGrh;AAAAsh,oBAAGth;AAAAuh,oBAAGvh;AAAAwh,oBAAGxh;AAAAyh,oBAAGzh;AAAA0i,oBAAG1i;AAAA2i,oBAAG3i;AAAA4i,oBAAG5i;AAAA6i,oBAAG7i;AAAA8i,oBAAG9i;AAAA+i,oBAAG/i;AAAAgj,oBAAGhj;AAAAij,oBAAGjj;AAAAkj,oBAAGlj;AAAAmj,oBAAGnj;AAAAoj,oBAAGpj;AAAAqj,oBAAGrj;AAAAsj,oBAAGtj;AAAAuj,oBAAGvj;AAAAwj,oBAAGxj;AAAAyj,oBAAGzj;AAAA0k,oBAAG1k;AAAA2k,oBAAG3k;AAAA4k,oBAAG5k;AAAA6k,oBAAG7k;AAAA8k,oBAAG9k;AAAA+k,oBAAG/k;AAAAgl,oBAAGhl;AAAAil,oBAAGjl;AAAAkl,oBAAGll;AAAAml,oBAAGnl;AAAAol,oBAAGpl;AAAAql,oBAAGrl;AAAAsl,oBAAGtl;AAAAul,oBAAGvl;AAAAwl,oBAAGxl;AAAAyl,oBAAGzl;AAAA0m,oBAAG1m;AAAA2m,oBAAG3m;AAAA4m,oBAAG5m;AAAA6m,oBAAG7m;AAAA8m,oBAAG9m;AAAA+m,oBAAG/m;AAAAgn,oBAAGhn;AAAAin,oBAAGjn;AAAAkn,oBAAGln;AAAAmn,oBAAGnn;AAAAon,oBAAGpn;AAAAqn,oBAAGrn;AAAAsn,oBAAGtn;AAAAun,oBAAGvn;AAAAwn,oBAAGxn;AAAAyn,oBAAGzn;AAAA0o,oBAAG1o;AAAA2o,oBAAG3o;AAAA4o,oBAAG5o;AAAA6o,oBAAG7o;AAAA8o,oBAAG9o;AAAA+o,oBAAG/o;AAAAgp,oBAAGhp;AAAAip,oBAAGjp;AAAAkp,oBAAGlp;AAAAmp,oBAAGnp;AAAAop,oBAAGpp;AAAAqp,oBAAGrp;AAAAsp,oBAAGtp;AAAAup,oBAAGvp;AAAAwp,oBAAGxp;AAAAyp,oBAAGzp;AAAA0q,oBAAG1q;AAAA2q,oBAAG3q;AAAA4q,oBAAG5q;AAAA6q,oBAAG7q;AAAA8q,oBAAG9q;AAAA+q,oBAAG/q;AAAAgr,oBAAGhr;AAAAir,oBAAGjr;AAAAkr,oBAAGlr;AAAAmr,oBAAGnr;AAAAor,oBAAGpr;AAAAqr,oBAAGrr;AAAAsr,oBAAGtr;AAAAur,oBAAGvr;AAAAwr,oBAAGxr;AAAAyr,oBAAGzr;AAAA0s,oBAAG1s;AAAA2s,oBAAG3s;AAAA4s,oBAAG5s;AAAA6s,oBAAG7s;AAAA8s,oBAAG9s;AAAA+s,oBAAG/s;AAAAgt,oBAAGht;AAAAit,oBAAGjt;AAAAkt,oBAAGlt;AAAAmt,oBAAGnt;AAAAot,oBAAGpt;AAAAqt,oBAAGrt;AAAAst,oBAAGtt;AAAAut,oBAAGvt;AAAAwt,oBAAGxt;AAAAyt,oBAAGzt;AAAA0u,oBAAG1u;AAAA2u,oBAAG3u;AAAA4u,oBAAG5u;AAAA6u,oBAAG7u;AAAA8u,oBAAG9u;AAAA+u,oBAAG/u;AAAAgv,oBAAGhv;AAAAiv,oBAAGjv;AAAAkv,oBAAGlv;AAAAmv,oBAAGnv;AAAAov,oBAAGpv;AAAAqv,oBAAGrv;AAAAsv,oBAAGtv;AAAAuv,oBAAGvv;AAAAwv,oBAAGxv;AAAAyv,oBAAGzv;AAAA0w,oBAAG1w;AAAA2w,oBAAG3w;AAAA4w,oBAAG5w;AAAA6w,oBAAG7w;AAAA8w,oBAAG9w;AAAA+w,oBAAG/w;AAAAgx,oBAAGhx;AAAAix,oBAAGjx;AAAAkx,oBAAGlx;AAAAmx,oBAAGnx;AAAAox,oBAAGpx;AAAAqx,oBAAGrx;AAAAsx,oBAAGtx;AAAAux,oBAAGvx;AAAAwx,oBAAGxx;AAAAyx,oBAAGzx;AAAA0y,oBAAG1y;AAAA2y,oBAAG3y;AAAA4y,oBAAG5y;AAAA6y,oBAAG7y;AAAA8y,oBAAG9y;AAAA+y,oBAAG/y;AAAAgz,oBAAGhz;AAAAiz,oBAAGjz;AAAAkz,oBAAGlz;AAAAmz,oBAAGnz;AAAAoz,oBAAGpz;AAAAqz,oBAAGrz;AAAAsz,oBAAGtz;AAAAuz,oBAAGvz;AAAAwz,oBAAGxz;AAAAyz,oBAAGzz;AAAA0{,oBAAG1{;AAAA2{,oBAAG3{;AAAA4{,oBAAG5{;AAAA6{,oBAAG7{;AAAA8{,oBAAG9{;AAAA+{,oBAAG/{;AAAAg|,oBAAGh|;AAAAi|,oBAAGj|;AAAAk|,oBAAGl|;AAAAm|,oBAAGn|;AAAAo|,oBAAGp|;AAAAq|,oBAAGr|;AAAAs|,oBAAGt|;AAAAu|,oBAAGv|;AAAAw|,oBAAGx|;AAAAy|,oBAAGz|;AAAA0},oBAAG1};AAAA2},oBAAG3};AAAA4},oBAAG5};AAAA6},oBAAG7};AAAA8},oBAAG9};AAAA+},oBAAG/};AAAAg~,oBAAGh~;AAAAi~,oBAAGj~;AAAAk~,oBAAGl~;AAAAm~,oBAAGn~;AAAAo~,oBAAGp~;AAAAq~,oBAAGr~;AAAAs~,oBAAGt~;AAAAu~,oBAAGv~;AAAAw~,oBAAGx~;AAAAy~,oBAAGz~;AAAA0!,oBAAG1!;AAAA2!,oBAAG3!;AAAA4!,oBAAG5!;AAAA6!,oBAAG7!;AAAA8!,oBAAG9!;AAAA+!,oBAAG/!;AAAAg@,oBAAGh@;AAAAi@,oBAAGj@;AAAAk@,oBAAGl@;AAAAm@,oBAAGn@;AAAAo@,oBAAGp@;AAAAq@,oBAAGr@;AAAAs@,oBAAGt@;AAAAu@,oBAAGv@;AAAAw@,oBAAGx@;AAAAy@,oBAAGz@;AAAA0#,oBAAG1#;AAAA2#,oBAAG3#;AAAA4#,oBAAG5#;AAAA6#,oBAAG7#;AAAA8#,oBAAG9#;AAAA+#,oBAAG/#;AAAAg$,oBAAGh$;AAAAi$,oBAAGj$;AAAAk$,oBAAGl$;AAAAm$,oBAAGn$;AAAAo$,oBAAGp$;AAAAq$,oBAAGr$;AAAAs$,oBAAGt$;AAAAu$,oBAAGv$;AAAAw$,oBAAGx$;AAAAy$,oBAAGz$;AAAA0%,oBAAG1%;AAAA2%,oBAAG3%;AAAA4%,oBAAG5%;AAAA6%,oBAAG7%;AAAA8%,oBAAG9%;AAAA+%,oBAAG/%;AAAAg^,oBAAGh^;AAAAi^,oBAAGj^;AAAAk^,oBAAGl^;AAAAm^,oBAAGn^;AAAAo^,oBAAGp^;AAAAq^,oBAAGr^;AAAAs^,oBAAGt^;AAAAu^,oBAAGv^;AAAAw^,oBAAGx^;AAAAy^,oBAAGz^;AAAA0&,oBAAG1&;AAAA2&,oBAAG3&;AAAA4&,oBAAG5&;AAAA6&,oBAAG7&;AAAA8&,oBAAG9&;AAAA+&,oBAAG/&;AAAAg*,oBAAGh*;AAAAi*,oBAAGj*;AAAAk*,oBAAGl*;AAAAm*,oBAAGn*;AAAAo*,oBAAGp*;AAAAq*,oBAAGr*;AAAAs*,oBAAGt*;AAAAu*,oBAAGv*;AAAAw*,oBAAGx*;AAAAy*,oBAAGz*;AAAA0(,oBAAG1(;AAAA2(,oBAAG3(;AAAA4(,oBAAG5(;AAAA6(,oBAAG7(;AAAA8(,oBAAG9(;AAAA+(,oBAAG/(;AAAAg),oBAAGh);AAAAi),oBAAGj);AAAAk),oBAAGl);AAAAm),oBAAGn);AAAAo),oBAAGp);AAAAq),oBAAGr);AAAAs),oBAAGt);AAAAu),oBAAGv);AAAAw),oBAAGx);AAAAy),oBAAGz);AAAA0_,oBAAG1_;AAAA2_,oBAAG3_;AAAA4_,oBAAG5_;AAAA6_,oBAAG7_;AAAA8_,oBAAG9_;AAAA+_,oBAAG/_;AAAAg+,oBAAGh+;AAAAi+,oBAAGj+;AAAAk+,oBAAGl+;AAAAm+,oBAAGn+;AAAAo+,oBAAGp+;AAAAq+,oBAAGr+;AAAAs+,oBAAGt+;AAAAu+,oBAAGv+;AAAAw+,oBAAGx+;AAAAy+,oBAAGz+;AAAA0=,oBAAG1=;AAAA2=,oBAAG3=;AAAA4=,oBAAG5=;AAAA6=,oBAAG7=;AAAA8=,oBAAG9=;AAAA+=,oBAAG/=;AAAAg{,oBAAGh{;AAAAi{,oBAAGj{;AAAAk{,oBAAGl{;AAAAm{,oBAAGn{;AAAAo{,oBAAGp{;AAAAq{,oBAAGr{;AAAAs{,oBAAGt{;AAAAu{,oBAAGv{;AAAAw{,oBAAGx{;AAAAy{,oBAAGz{;AAAA0},oBAAG1};AAAA2},oBAAG3};AAAA4},oBAAG5};AAAA6},oBAAG7};AAAA8},oBAAG9};AAAA+},oBAAG/};AAAAg[,oBAAGh[;AAAAi[,oBAAGj[;AAAAk[,oBAAGl[;AAAAm[,oBAAGn[;AAAAo[,oBAAGp[;AAAAq[,oBAAGr[;AAAAs[,oBAAGt[;AAAAu[,oBAAGv[;AAAAw[,oBAAGx[;AAAAy[,oBAAGz[;AAAA0],oBAAG1];AAAA2],oBAAG3];AAAA4],oBAAG5];AAAA6],oBAAG7];AAAA8],oBAAG9];AAAA+],oBAAG/];AAAAg:,oBAAGh:;AAAAi:,oBAAGj:;AAAAk:,oBAAGl:;AAAAm:,oBAAGn:;AAAAo:,oBAAGp:;AAAAq:,oBAAGr:;AAAAs:,oBAAGt:;AAAAu:,oBAAGv:;AAAAw:,oBAAGx:;AAAAy:,oBAAGz:;AAAA0",oBAAG1";AAAA2",oBAAG3";AAAA4",oBAAG5";AAAA6",oBAAG7";AAAA8",oBAAG9";AAAA+",oBAAG/";AAAAg<,oBAAGh<;AAAAi<,oBAAGj<;AAAAk<,oBAAGl<;AAAAm<,oBAAGn<;AAAAo<,oBAAGp<;AAAAq<,oBAAGr<;AAAAs<,oBAAGt<;AAAAu<,oBAAGv<;AAAAw<,oBAAGx<;AAAAy<,oBAAGz<;AAAA0.,oBAAG1.;AAAA2.,oBAAG3.;AAAA4.,oBAAG5.;AAAA6.,oBAAG7.;AAAA8.,oBAAG9.;AAAA+.,oBAAG/.;AAAAg>,oBAAGh>;AAAAi>,oBAAGj>;AAAAk>,oBAAGl>;AAAAm>,oBAAGn>;AAAAo>,oBAAGp>;AAAAq>,oBAAGr>;AAAAs>,oBAAGt>;AAAAu>,oBAAGv>;AAAAw>,oBAAGx>;AAAAy>,oBAAGz>;AAAA0/,oBAAG1/;AAAA2/,oBAAG3/;AAAA4/,oBAAG5/;AAAA6/,oBAAG7/;AAAA8/,oBAAG9/;AAAA+/,oBAAG//;AAAAg?,oBAAGh?;AAAAi?,oBAAGj?;AAAAk?,oBAAGl?;AAAAm?,oBAAGn?;AAAAo?,oBAAGp?;AAAAq?,oBAAGr?;AAAAs?,oBAAGt?;AAAAu?,oBAAGv?;AAAAw?,oBAAGx?;AAAAy?,oBAAGz?;AAAA0A,oBAAG1A;AAAA2A,oBAAG3A;AAAA4A,oBAAG5A;AAAA6A,oBAAG7A;AAAA8A,oBAAG9A;AAAA+A,oBAAG/A;AAAAgB,oBAAGhB;AAAAiB,oBAAGjB;AAAAkB,oBAAGlB;AAAAmB,oBAAGnB;AAAAoB,oBAAGpB;AAAAqB,oBAAGrB;AAAAsB,oBAAGtB;AAAAuB,oBAAGvB;AAAAwB,oBAAGxB;AAAAyB,oBAAGzB;AAAA0C,oBAAG1C;AAAA2C,oBAAG3C;AAAA4C,oBAAG5C;AAAA6C,oBAAG7C;AAAA8C,oBAAG9C;AAAA+C,oBAAG/C;AAAAgD,oBAAGhD;AAAAiD,oBAAGjD;AAAAkD,oBAAGlD;AAAAmD,oBAAGnD;AAAAoD,oBAAGpD;AAAAqD,oBAAGrD;AAAAsD,oBAAGtD;AAAAuD,oBAAGvD;AAAAwD,oBAAGxD;AAAAyD,oBAAGzD;AAAA0E,oBAAG1E;AAAA2E,oBAAG3E;AAAA4E,oBAAG5E;AAAA6E,oBAAG7E;AAAA8E,oBAAG9E;AAAA+E,oBAAG/E;AAAAgF,oBAAGhF;AAAAiF,oBAAGjF;AAAAkF,oBAAGlF;AAAAmF,oBAAGnF;AAAAoF,oBAAGpF;AAAAqF,oBAAGrF;AAAAsF,oBAAGtF;AAAAuF,oBAAGvF;AAAAwF,oBAAGxF;AAAAyF,oBAAGzF;AAAA0G,oBAAG1G;AAAA2G,oBAAG3G;AAAA4G,oBAAG5G;AAAA6G,oBAAG7G;AAAA8G,oBAAG9G;AAAA+G,oBAAG/G;AAAAgH,oBAAGhH;AAAAiH,oBAAGjH;AAAAkH,oBAAGlH;AAAAmH,oBAAGnH;AAAAoH,oBAAGpH;AAAAqH,oBAAGrH;AAAAsH,oBAAGtH;AAAAuH,oBAAGvH;AAAAwH,oBAAGxH;AAAAyH,oBAAGzH;AAAA0I,oBAAG1I;AAAA2I,oBAAG3I;AAAA4I,oBAAG5I;AAAA6I,oBAAG7I;AAAA8I,oBAAG9I;AAAA+I,oBAAG/I;AAAAgJ,oBAAGhJ;AAAAiJ,oBAAGjJ;AAAAkJ,oBAAGlJ;AAAAmJ,oBAAGnJ;AAAAoJ,oBAAGpJ;AAAAqJ,oBAAGrJ;AAAAsJ,oBAAGtJ;AAAAuJ,oBAAGvJ;AAAAwJ,oBAAGxJ;AAAAyJ,oBAAGzJ;AAAA0K,oBAAG1K;AAAA2K,oBAAG3K;AAAA4K,oBAAG5K;AAAA6K,oBAAG7K;AAAA8K,oBAAG9K;AAAA+K,oBAAG/K;AAAAgL,oBAAGhL;AAAAiL,oBAAGjL;AAAAkL,oBAAGlL;AAAAmL,oBAAGnL;AAAAoL,oBAAGpL;AAAAqL,oBAAGrL;AAAAsL,oBAAGtL;AAAAuL,oBAAGvL;AAAAwL,oBAAGxL;AAAAyL,oBAAGzL;AAAA0M,oBAAG1M;AAAA2M,oBAAG3M;AAAA4M,oBAAG5M;AAAA6M,oBAAG7M;AAAA8M,oBAAG9M;AAAA+M,oBAAG/M;AAAAgN,oBAAGhN;AAAAiN,oBAAGjN;AAAAkN,oBAAGlN;AAAAmN,oBAAGnN;AAAAoN,oBAAGpN;AAAAqN,oBAAGrN;AAAAsN,oBAAGtN;AAAAuN,oBAAGvN;AAAAwN,oBAAGxN;AAAAyN,oBAAGzN;AAAA0O,oBAAG1O;AAAA2O,oBAAG3O;AAAA4O,oBAAG5O;AAAA6O,oBAAG7O;AAAA8O,oBAAG9O;AAAA+O,oBAAG/O;AAAAgP,oBAAGhP;AAAAiP,oBAAGjP;AAAAkP,oBAAGlP;AAAAmP,oBAAGnP;AAAAoP,oBAAGpP;AAAAqP,oBAAGrP;AAAAsP,oBAAGtP;AAAAuP,oBAAGvP;AAAAwP,oBAAGxP;AAAAyP,oBAAGzP;AAAA0Q,oBAAG1Q;AAAA2Q,oBAAG3Q;AAAA4Q,oBAAG5Q;AAAA6Q,oBAAG7Q;AAAA8Q,oBAAG9Q;AAAA+Q,oBAAG/Q;AAAAgR,oBAAGhR;AAAAiR,oBAAGjR;AAAAkR,oBAAGlR;AAAAmR,oBAAGnR;AAAAoR,oBAAGpR;AAAAqR,oBAAGrR;AAAAsR,oBAAGtR;AAAAuR,oBAAGvR;AAAAwR,oBAAGxR;AAAAyR,oBAAGzR;AAAA0S,oBAAG1S;AAAA2S,oBAAG3S;AAAA4S,oBAAG5S;AAAA6S,oBAAG7S;AAAA8S,oBAAG9S;AAAA+S,oBAAG/S;AAAAgT,oBAAGhT;AAAAiT,oBAAGjT;AAAAkT,oBAAGlT;AAAAmT,oBAAGnT;AAAAoT,oBAAGpT;AAAAqT,oBAAGrT;AAAAsT,oBAAGtT;AAAAuT,oBAAGvT;AAAAwT,oBAAGxT;AAAAyT,oBAAGzT;AAAA0U,oBAAG1U;AAAA2U,oBAAG3U;AAAA4U,oBAAG5U;AAAA6U,oBAAG7U;AAAA8U,oBAAG9U;AAAA+U,oBAAG/U;AAAAgV,oBAAGhV;AAAAiV,oBAAGjV;AAAAkV,oBAAGlV;AAAAmV,oBAAGnV;AAAAoV,oBAAGpV;AAAAqV,oBAAGrV;AAAAsV,oBAAGtV;AAAAuV,oBAAGvV;AAAAwV,oBAAGxV;AAAAyV,oBAAGzV;AAAA0W,oBAAG1W;AAAA2W,oBAAG3W;AAAA4W,oBAAG5W;AAAA6W,oBAAG7W;AAAA8W,oBAAG9W;AAAA+W,oBAAG/W;AAAAgX,oBAAGhX;AAAAiX,oBAAGjX;AAAAkX,oBAAGlX;AAAAmX,oBAAGnX;AAAAoX,oBAAGpX;AAAAqX,oBAAGrX;AAAAsX,oBAAGtX;AAAAuX,oBAAGvX;AAAAwX,oBAAGxX;AAAAyX,oBAAGzX;AAAA0Y,oBAAG1Y;AAAA2Y,oBAAG3Y;AAAA4Y,oBAAG5Y;AAAA6Y,oBAAG7Y;AAAA8Y,oBAAG9Y;AAAA+Y,oBAAG/Y;AAAAgZ,oBAAGhZ;AAAAiZ,oBAAGjZ;AAAAkZ,oBAAGlZ;AAAAmZ,oBAAGnZ;AAAAoZ,oBAAGpZ;AAAAqZ,oBAAGrZ;AAAAsZ,oBAAGtZ;AAAAuZ,oBAAGvZ;AAAAwZ,oBAAGxZ;AAAAyZ,oBAAGzZ;AAAA0a,oBAAG1a;AAAA2a,oBAAG3a;AAAA4a,oBAAG5a;AAAA6a,oBAAG7a;AAAA8a,oBAAG9a;AAAA+a,oBAAG/a;AAAAgb,oBAAGhb;AAAAib,oBAAGjb;AAAAkb,oBAAGlb;AAAAmb,oBAAGnb;AAAAob,oBAAGpb;AAAAqb,oBAAGrb;AAAAsb,oBAAGtb;AAAAub,oBAAGvb;AAAAwb,oBAAGxb;AAAAyb,oBAAGzb;AAAA0c,oBAAG1c;AAAA2c,oBAAG3c;AAAA4c,oBAAG5c;AAAA6c,oBAAG7c;AAAA8c,oBAAG9c;AAAA+c,oBAAG/c;AAAAgd,oBAAGhd;AAAAid,oBAAGjd;AAAAkd,oBAAGld;AAAAmd,oBAAGnd;AAAAod,oBAAGpd;AAAAqd,oBAAGrd;AAAAsd,oBAAGtd;AAAAud,oBAAGvd;AAAAwd,oBAAGxd;AAAAyd,oBAAGzd;AAAA0e,oBAAG1e;AAAA2e,oBAAG3e;AAAA4e,oBAAG5e;AAAA6e,oBAAG7e;AAAA8e,oBAAG9e;AAAA+e,oBAAG/e;AAAAgf,oBAAGhf;AAAAif,oBAAGjf;AAAAkf,oBAAGlf;AAAAmf,oBAAGnf;AAAAof,oBAAGpf;AAAAqf,oBAAGrf;AAAAsf,oBAAGtf;AAAAuf,oBAAGvf;AAAAwf,oBAAGxf;AAAAyf,oBAAGzf;AAAA0g,oBAAG1g;AAAA2g,oBAAG3g;AAAA4g,oBAAG5g;AAAA6g,oBAAG7g;AAAA8g,oBAAG9g;AAAA+g,oBAAG/g;AAAAgh,oBAAGhh;AAAAih,oBAAGjh;AAAAkh,oBAAGlh;AAAAmh,oBAAGnh;AAAAoh,oBAAGph;AAAAqh,oBAAGrh;AAAAsh,oBAAGth;AAAAuh,oBAAGvh;AAAAwh,oBAAGxh;AAAAyh,oBAAGzh;AAAA0i,oBAAG1i;AAAA2i,oBAAG3i;AAAA4i,oBAAG5i;AAAA6i,oBAAG7i;AAAA8i,oBAAG9i;AAAA+i,oBAAG/i;AAAAgj,oBAAGhj;AAAAij,oBAAGjj;AAAAkj,oBAAGlj;AAAAmj,oBAAGnj;AAAAoj,oBAAGpj;AAAAqj,oBAAGrj;AAAAsj,oBAAGtj;AAAAuj,oBAAGvj;AAAAwj,oBAAGxj;AAAAyj,oBAAGzj;AAAA0k,oBAAG1k;AAAA2k,oBAAG3k;AAAA4k,oBAAG5k;AAAA6k,oBAAG7k;AAAA8k,oBAAG9k;AAAA+k,oBAAG/k;AAAAgl,oBAAGhl;AAAAil,oBAAGjl;AAAAkl,oBAAGll;AAAAml,oBAAGnl;AAAAol,oBAAGpl;AAAAql,oBAAGrl;AAAAsl,oBAAGtl;AAAAul,oBAAGvl;AAAAwl,oBAAGxl;AAAAyl,oBAAGzl;AAAA0m,oBAAG1m;AAAA2m,oBAAG3m;AAAA4m,oBAAG5m;AAAA6m,oBAAG7m;AAAA8m,oBAAG9m;AAAA+m,oBAAG/m;AAAAgn,oBAAGhn;AAAAin,oBAAGjn;AAAAkn,oBAAGln;AAAAmn,oBAAGnn;AAAAon,oBAAGpn;AAAAqn,oBAAGrn;AAAAsn,oBAAGtn;AAAAun,oBAAGvn;AAAAwn,oBAAGxn;AAAAyn,oBAAGzn;AAAA0o,oBAAG1o;AAAA2o,oBAAG3o;AAAA4o,oBAAG5o;AAAA6o,oBAAG7o;AAAA8o,oBAAG9o;AAAA+o,oBAAG/o;AAAAgp,oBAAGhp;AAAAip,oBAAGjp;AAAAkp,oBAAGlp;AAAAmp,oBAAGnp;AAAAop,oBAAGpp;AAAAqp,oBAAGrp;AAAAsp,oBAAGtp;AAAAup,oBAAGvp;AAAAwp,oBAAGxp;AAAAyp,oBAAGzp;AAAA0q,oBAAG1q;AAAA2q,oBAAG3q;AAAA4q,oBAAG5q;AAAA6q,oBAAG7q;AAAA8q,oBAAG9q;AAAA+q,oBAAG/q;AAAAgr,oBAAGhr;AAAAir,oBAAGjr;AAAAkr,oBAAGlr;AAAAmr,oBAAGnr;AAAAor,oBAAGpr;AAAAqr,oBAAGrr;AAAAsr,oBAAGtr;AAAAur,oBAAGvr;AAAAwr,oBAAGxr;AAAAyr,oBAAGzr;AAAA0s,oBAAG1s;AAAA2s,oBAAG3s;AAAA4s,oBAAG5s;AAA

eAAKjD,GAAL,IAAY,CAAZ;AACAwB,UAAAA,GAAAG,GAAAG,IAAN;AACA;AACD,SAJM,MAIA,IAAIyB,IAAI,KAAK,GAAAb,EAAAkB;AACvBjB,UAAAA,KAAK,GAAAG,IAAR;AACD;AACF,OAlBM,MAkBA,IAAIiB,IAAI,KAAK1C,QAAAQ,CAACA,QAAAQ,CAACzT,MAAT,GAAAkB,CAAAB,CAAAA,EAAA4C;AACjDyT,QAAAA,QAAAQ,CAAC+H,GAAAT;AACA,YAAAI/H,QAAAQ,CAACzT,MAAT,GAAAkB,CAAAoB,CAAAA,EAAA2Bub,OAAAO,GAAAG,IAAAV;AAC5B;;AAED,WAAAKrI,GAAAL,IAAAY,CAAAZ;AACD;;AACD,QAAAI,KAAAKA,GAAAL,KAAAa,KAAAf,MAAAL,CAAAA,AYnS,MAA7B,EAAAqC;AACnC,WAAAkT,GAAAL,IAAAY,CAAAZ;AACD;;AACD,QAAAIjB,QAAAQ,CAACzT,MAAT,GAAAkB,CAAAB,CAAAA,EAAAyB,KAAAKyb,eAAL,CAAAqBF,OAAArB;;AAEzB,QAAAI7G,GAAAG,IAAAIQ,KAAAX,EAAAkB;AAChB,QAAAnB,GAAAa,aAAO,KAAAK,GAAAL,KAAAa,KAAAf,MAAAL,GAAAqC,GAAAL,IAAAY,CAAAZ;AACD;;AACD,QAAAI,KAAAK,GAAAL,KAAAa,KAAAf,MAAAL,CAAAA,AAAAA

C9B;AACD,OAND,MAMO,IAAIiH,KAAK,CAAC,CAAD,CAAL,KAAa,WAAjB,EAA8B;AACnC,YAAMkI,KAAK,GAAG7J,MAAM,CAACmB,KAAP,CAAa,CAAAa,CAAAb,CAAAd;AACA,YAAInT,GAAAG,GAAAG,EAAAV;;AACA,aAAAK,IAAAIyY,CAAAC,GAAA7Y,CAAAb,EAAAgB6Y,CAAAC,GAAAC,CAAApB,EAAAuBA,CAAAC,EAAAxB,EAAA4B;AAC1B,cAAAMzC,KAAAI,GAAA6F,KAAAK,CAAAD,CAAAE,CAAAC,CAAAb;;AACA,cAAAcgS,CAAAzY,GAAAG,CAAAgD,IAAAJ,GAAAW,GAAAC,EAAAC,EAAAC,E

SAAK4E,OAAL,CAAaxE,IAAb,CAAkBb,KAAlB,GAA0B,CAAC,KAAKqF,OAAL,CAAaxE,IAAb,CAAkBb,KAAlB,IAA2B,EAA5B,IAAkC,KAAKsF,MAAjE;AACD;;;SAIDM,OAAA,cAAKlU,IAAL,EAAWoE,IAAX,EAAiBC,MAAjB,EAAyBC,EAAzB,EAA6BC,MAAjB,EAAyBC,EAAzB,EA

AAWmB,KAAX,CAAiB,gBAAjB,EAAmCH,GAAG,CAAC3H,IAAvC,EAA6C2H,GAAG,CAAC1H,MAAjD,CAAN;AACD;;SAEDmR,cAAA,qBAAY7I,KAAZ,EAAmB;AACjB,UAAM,KAAK5B,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCS,KAAK,CAAC,CAAD,CAAtC,EAA2CA,KAAK,CAAC,CAAD,CAAhD,EAAqDA,KAAK,CAAC,CAAD,CAAN;AACD;;SAEDqI,gBAAA,uBAAchV,IAAd,EAAoB2M,KAAK,EAAzB,EAA6B;AAC3B,UAAMsI,KAAK,sBAAWjV,IAAX,CAAX;AACA,UAAM,KAAKwM,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCsH,KAAjC,EAAwCtI,KAAxC,CAAN;AACD;;SAEDuI,gBAAA,uBAAcC,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDC,gBAAA,uBAAcD,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDE,gBAAA,uBAAcF,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDG,gBAAA,uBAAcH,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDI,gBAAA,uBAAcJ,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDK,gBAAA,uBAAcL,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDM,gBAAA,uBAAcN,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDO,gBAAA,uBAAcP,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDQ,gBAAA,uBAAcR,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDS,gBAAA,uBAAcT,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDU,gBAAA,uBAAcV,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDW,gBAAA,uBAAcX,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDY,gBAAA,uBAAcZ,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDa,gBAAA,uBAAcb,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDc,gBAAA,uBAAcd,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDe,gBAAA,uBAAcf,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDgB,gBAAA,uBAAchB,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDiB,gBAAA,uBAAcjB,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDkB,gBAAA,uBAAclB,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDmB,gBAAA,uBAAcnB,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDoB,gBAAA,uBAAcpB,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDqB,gBAAA,uBAAcrB,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDsB,gBAAA,uBAActB,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDuB,gBAAA,uBAAcvB,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDwB,gBAAA,uBAAcxB,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDyB,gBAAA,uBAAczB,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED0B,gBAAA,uBAAc1B,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED2B,gBAAA,uBAAc3B,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED4B,gBAAA,uBAAc5B,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED6B,gBAAA,uBAAc7B,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED8B,gBAAA,uBAAc9B,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED+B,gBAAA,uBAAc/B,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDgC,gBAAA,uBAAchC,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDiC,gBAAA,uBAAcjC,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDkC,gBAAA,uBAAclC,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDmC,gBAAA,uBAAcnC,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDoC,gBAAA,uBAAcpC,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDqC,gBAAA,uBAAcrC,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDsC,gBAAA,uBAActC,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDuC,gBAAA,uBAAcvC,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDwC,gBAAA,uBAAcxC,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDyC,gBAAA,uBAAczC,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED0C,gBAAA,uBAAc1C,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED2C,gBAAA,uBAAc3C,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED4C,gBAAA,uBAAc5C,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED6C,gBAAA,uBAAc7C,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED8C,gBAAA,uBAAc9C,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED+C,gBAAA,uBAAc/C,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDgD,gBAAA,uBAAchD,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDiD,gBAAA,uBAAcjD,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDkD,gBAAA,uBAAclD,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDmD,gBAAA,uBAAcnD,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDoD,gBAAA,uBAAcpD,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDqD,gBAAA,uBAAcrD,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDsD,gBAAA,uBAActD,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDuD,gBAAA,uBAAcvD,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDwD,gBAAA,uBAAcxD,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDyD,gBAAA,uBAAczD,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED0D,gBAAA,uBAAc1D,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED2D,gBAAA,uBAAc3D,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED4D,gBAAA,uBAAc5D,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED6D,gBAAA,uBAAc7D,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED8D,gBAAA,uBAAc9D,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED+D,gBAAA,uBAAc/D,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDgE,gBAAA,uBAAchE,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDiE,gBAAA,uBAAcjE,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDkE,gBAAA,uBAAclE,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDmE,gBAAA,uBAAcnE,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDoE,gBAAA,uBAAcpE,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDqE,gBAAA,uBAAcrE,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDsE,gBAAA,uBAActE,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDuE,gBAAA,uBAAcvE,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDwE,gBAAA,uBAAcxE,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDyE,gBAAA,uBAAczE,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED0E,gBAAA,uBAAc1E,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED2E,gBAAA,uBAAc3E,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED4E,gBAAA,uBAAc5E,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED6E,gBAAA,uBAAc7E,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED8E,gBAAA,uBAAc9E,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED+E,gBAAA,uBAAc/E,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDgF,gBAAA,uBAAchF,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDiF,gBAAA,uBAAcjF,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDkF,gBAAA,uBAAclF,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDmF,gBAAA,uBAAcnF,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDoF,gBAAA,uBAAcpF,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDqF,gBAAA,uBAAcrF,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDsF,gBAAA,uBAActF,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDuF,gBAAA,uBAAcvF,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDwF,gBAAA,uBAAcxF,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDyF,gBAAA,uBAAczF,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED0F,gBAAA,uBAAc1F,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED2F,gBAAA,uBAAc3F,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED4F,gBAAA,uBAAc5F,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED6F,gBAAA,uBAAc7F,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED8F,gBAAA,uBAAc9F,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED+F,gBAAA,uBAAc/F,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDgG,gBAAA,uBAAchG,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDiG,gBAAA,uBAAcjG,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDkG,gBAAA,uBAAclG,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDmG,gBAAA,uBAAcnG,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDoG,gBAAA,uBAAcpG,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDqG,gBAAA,uBAAcrG,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDsG,gBAAA,uBAActG,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDuG,gBAAA,uBAAcvG,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDwG,gBAAA,uBAAcxG,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDyG,gBAAA,uBAAczG,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED0G,gBAAA,uBAAc1G,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED2G,gBAAA,uBAAc3G,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED4G,gBAAA,uBAAc5G,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED6G,gBAAA,uBAAc7G,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED8G,gBAAA,uBAAc9G,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED+G,gBAAA,uBAAc/G,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDgH,gBAAA,uBAAchH,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDiH,gBAAA,uBAAcjH,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDkH,gBAAA,uBAAclH,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDmH,gBAAA,uBAAcnH,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDoH,gBAAA,uBAAcpH,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDqH,gBAAA,uBAAcrH,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDsH,gBAAA,uBAActH,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDuH,gBAAA,uBAAcvH,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDwH,gBAAA,uBAAcxH,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDyH,gBAAA,uBAAczH,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED0H,gBAAA,uBAAc1H,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED2H,gBAAA,uBAAc3H,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED4H,gBAAA,uBAAc5H,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED6H,gBAAA,uBAAc7H,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED8H,gBAAA,uBAAc9H,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED+H,gBAAA,uBAAc/H,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDgI,gBAAA,uBAAchI,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDiI,gBAAA,uBAAcjI,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDkI,gBAAA,uBAAclI,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDmI,gBAAA,uBAAcnI,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDoI,gBAAA,uBAAcpI,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDqI,gBAAA,uBAAcrI,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDsI,gBAAA,uBAActI,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDuI,gBAAA,uBAAcvI,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDwI,gBAAA,uBAAcxI,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDyI,gBAAA,uBAAczI,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED0I,gBAAA,uBAAc1I,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED2I,gBAAA,uBAAc3I,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED4I,gBAAA,uBAAc5I,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED6I,gBAAA,uBAAc7I,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED8I,gBAAA,uBAAc9I,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAED+I,gBAAA,uBAAc/I,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDgJ,gBAAA,uBAAchJ,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDiJ,gBAAA,uBAAcjJ,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDkJ,gBAAA,uBAAclJ,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDmJ,gBAAA,uBAAcnJ,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDoJ,gBAAA,uBAAcpJ,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDqJ,gBAAA,uBAAcrJ,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDsJ,gBAAA,uBAActJ,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDuJ,gBAAA,uBAAcvJ,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDwJ,gBAAA,uBAAcxJ,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KAAX,CAAiB,cAAjB,EAAiCwI,KAAjC,CAAN;AACD;;SAEDyJ,gBAAA,uBAAczJ,KAAd,EAAqB;AACnB,UAAM,KAAK3J,KAAL,CAAWmB,KA

AMA;AACL,aAAO,KAAK2X,IAAL,CAAU,UAAC9P,KAAD,EAAQ7H,CAAR,EAAc;AAC7B,YAAI6H,KAAK,CAACuO,IAAN,KAAe,MAAf,IAAyBvO,KAAK,CACiP,IAAN,KAAeA,IAA5C,EAAkD;AAChD,iBAAOsG,QAAQ,CACvV,KAAD,EAAQ7H,CAAR,EAAW,CAAf;AACD;AACF,OAJM,CAAP;AAKD;AACF;AAED;;;

oB;AAClB,aAAKyZ,OAAL,CAAajY,EAAb,IAAmBxB,KAAK,GAAGoD,KAAK,CAAChH,MAAjC;AACD;AACF;;AAED,WAAO,IAAP;AACD;AAED;;;;;;;;;;SAQAwZ,cAAA,qBAAYqE,KAAZ,EAAmBpT,GAAnB,EAAwB;AAAA;;AACtBoT,IAAAA,KAAK,GAAG,KAAKja,KAAL,CAAWia,KAAX,CAAR;AAEA,QAAM7W,KAAK,GAAG,KAAKyW,KAAL,CAAW6W,KAAX,EAAkBzW,GAAlB,CAAd;AAEA,WAAOpT,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,aAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,eAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iBAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mBAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qBAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uBAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yBAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2BAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6BAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+BAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iCAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mCAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qCAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uCAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yCAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2CAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6CAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+CAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iDAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mDAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qDAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uDAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yDAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2DAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6DAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+DAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iEAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mEAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qEAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uEAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yEAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2EAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6EAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+EAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iFAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mFAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qFAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uFAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yFAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2FAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6FAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+FAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iGAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mGAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qGAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uGAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yGAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2GAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6GAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+GAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iHAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mHAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qHAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uHAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yHAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2HAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6HAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+HAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iIAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mIAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qIAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uIAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yIAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2IAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6IAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+IAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iJAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mJAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qJAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uJAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yJAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2JAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6JAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+JAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iKAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mKAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qKAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uKAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yKAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2KAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6KAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+KAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iLAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mLAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qLAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uLAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yLAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2LAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6LAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+LAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iMAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mMAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qMAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uMAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yMAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2MAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6MAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+MAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iNAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mNAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qNAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uNAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yNAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2NAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6NAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+NAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iOAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mOAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qOAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uOAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yOAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2OAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6OAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+OAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iPAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mPAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qPAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uPAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yPAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2PAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6PAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+PAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iQAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mQAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qQAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uQAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yQAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2QAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6QAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+QAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iRAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mRAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qRAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uRAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yRAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2RAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6RAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+RAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iSAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mSAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qSAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uSAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ySAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2SAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6SAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+SAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iTAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mTAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qTAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uTAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yTAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2TAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6TAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+TAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iUAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mUAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qUAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uUAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yUAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2UAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6UAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+UAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iVAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mVAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qVAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uVAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yVAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2VAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6VAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+VAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iWAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mWAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qWAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uWAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yWAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2WAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6WAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+WAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iXAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mXAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qXAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uXAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yXAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2XAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6XAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+XAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iYAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mYAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qYAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uYAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yYAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2YAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6YAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+YAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iZAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mZAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qZAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uZAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yZAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2ZAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6ZAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+ZAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iaAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,maAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qaAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uaAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yaAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2aAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6aAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+aAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ibAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mbAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qbAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ubAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ybAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2bAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6bAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+bAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,icAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mcAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qcAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ucAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ycAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2cAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6cAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+cAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,idAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mdAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qdAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,udAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ydAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2dAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6dAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+dAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ieAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,meAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qeAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ueAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yeAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2eAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6eAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+eAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ifAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mfAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qfAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ufAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yfAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2fAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6fAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+fAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ihAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mhAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qhAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uhAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yhAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2hAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6hAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+hAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iiAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,miAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qiAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uiAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yiAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2iAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6iAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+iAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ijAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mjAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qjAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ujAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yjAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2jAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6jAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+jAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ikAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mkAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qkAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ukAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ykAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2kAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6kAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+kAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ilAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mlAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qlAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ulAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ylAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2lAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6lAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+lAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,imAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mmAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qmAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,umAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ymAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2mAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6mAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+mAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,inAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mnAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qnAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,unAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ynAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2nAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6nAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+nAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ioAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,moAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qoAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uoAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yoAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2oAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6oAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+oAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ipAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mpAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qpAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,upAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ypAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2pAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6pAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+pAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,iqAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mqAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qqAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,uqAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yqAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2qAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6qAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+qAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,irAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mrAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qrAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,urAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,yrAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2rAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6rAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+rAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,isAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,msAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qsAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,usAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,ysAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,2sAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,6sAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,+sAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,itAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,mtAAIA,KAAK,CAACuF,GAAN,CAAU,UAAAvF,KAAK;AAAA,qtAAIA,KAAK,CAACuF,

AJ;AAEnC,UAAIA,CAAC,CAACkI,MAAN,EAAclI,CAAC,GAAGA,CAAC,CAACqZ,KAAF,EAAJ;;AACd,UAAI,OAAOrZ,CAAC,CAACuW,IAAF,CAAOa,MAAd,KAAyB,WAA7B,EAA0C;AACxC,YAAImH,MAAM,IAAIOAAOA,MAAM,CAAChI,IAAP,CAAYa,MAAnB,KAA8B,WAA5C,EAAyD;AACvDpX,CAAC,CAACvD,IAAF,CAAO,QAAP,EAAiB,MAAM,CAAC,CAAxB;AACD;AACF;;AACDI,MAAA

AAG,KAAZ;AAEA,QAAI6Y,IAAI,GAAG,CAAX;AACA,QAAI1M,KAAK,GAAG,KAAZ;AACA,QAAIG,MAAA
M,GAAG,KAAb;;AAEA,SAAK,IAAI5S,CAAC,GAAG,CAAb,EAAgBA,CAAC,GAAG8M,MAAM,CAAC7M,M
AA3B,EAAmCD,CAAC,EAApC,EAAwC;AACtC,UAAMof,MAAM,GAAGtS,MAAM,CAAC9M,CAAD,,CAArB
;;AAEA,UAAIyS,KAAJ,EAAW;AACT,YAAIG,MAAJ,EAAY;AACVA,UAAAA,MAAM,GAAG,KAAT;AACD,
SAFD,MAEO,IAAIwM,MAAM,KAAK,IAAf,EAAqB;AAC1BxM,UAAAA,MAAM,GAAG,IAAT;AACD,SAFM,
MAEA,IAAIwM,MAAM,KAAK3M,KAAf,EAAsB;AAC3BA,UAAAA,KAAK,GAAG,KAAR;AACD;AACF,OA
RD,MAQO,IAAI2M,MAAM,KAAK,GAAX,IAAkBA,MAAM,KAAK,GAAjC,EAAsC;AAC3C3M,QAAAA,KAA
K,GAAG2M,MAAR;AACD,OAFM,MAEA,IAAIA,MAAM,KAAK,GAAf,EAAoB;AACzBD,QAAAA,IAAI,IAAI
,CAAR;AACD,OAFM,MAEA,IAAIA,MAAM,KAAK,GAAf,EAAoB;AACzB,YAAID,IAAI,GAAG,CAAX,EAAc
A,IAAI,IAAI,CAAR;AACf,OAFM,MAEA,IAAIA,MAAM,KAAK,GAAf,EAAoB;AACzBA,QAAAA,MAAM,GAAG,
OAAX,CAAmBqS,MAAnB,MAA+B,CAAC,CAApC,EAAuC9Y,KAAK,GAAG,IAAR;AACxC;;AAED,UAAIA,
KAAJ,EAAW;AACT,YAAIyU,OAAO,KAAK,EAAhB,EAAoBmE,KAAK,CAACrc,IAAN,CAAWkY,OAAO,CA
AC3X,IAAR,EAAX;AACpB2X,QAAAA,OAAO,GAAG,EAAV;AACAzU,QAAAA,KAAK,GAAG,KAAR;AACD;AACD
,OAJD,MAIO;AACLyU,QAAAA,OAAO,IAAIqE,MAAX;AACD;AACF;;AAED,QAAIzM,IAAI,IAAIoI,OAAO
,KAAK,EAAxB,EAA4BmE,KAAK,CAACrc,IAAN,CAAWkY,OAAO,CAAC3X,IAAR,EAAX;AAC5B5C,QAAAA,MAAM,
,KAAP;AACD,GA1CU;;AA4CX;;;;;;;;;;;AAWAG,EAAAA,KAAvDW,iBAuDLS,MAAMkO8b
,KAAP;AACD,GA1CU;;AA4CX;;;;;;;;;;;AAWAG,EAAAA,KAAvDW,iBAuDLS,MAAMkO8b
kO,MAAM,GAAG,CAAC,GAAD,,EAAM,IAAN,,EAAY,IAAZ,,CAAf;AACA,WAAOgE,IAAI,CAAC1Y,KAAL,,CAAW
AAWwG,MAAX,EAAmBkO,MAAnB,CAAP;AACD,GA1DU;;AA4DX;;;;;;;;;;;AAYAsE,EAAAA,KAAxEW,iBA
wELxS,MAxEK,EAAwEG;AACZ,QAAMwS,KAAK,GAAG,GAAd;AACA,WAAON,IAAI,CAAC1Y,KAAL,,CAAW,CAA
WwG,MAAX,EAAmB,CAACwS,KAAD,,CAAnB,CAAP;AACD,GA1EU;;AA4EX;;;;;;;;;;;AAWAG,EAAA4B,IAA5B,CAAP;;;;;;;;;;;I
AWM/D;;;AACJ,gBAAYxC,QAAZ,EAAsB;AAAA;;AACpB,kBAAMA,QAAN;AACA,UAAK3C,IAAL,GAAY,GAAZ;AACA,UAAK
MAAZ;AACA,QAAI,CAAC,MAAKnP,KAAV,EAAiB,MAAKA,KAAL,GAAa,MAAKoP,IAAL,GAAY,CAAzB;AAAA
;;;;;;;;;;;;wBAgBgB;AACd,aAAO+X,IAAI,CAAC1Y,KAAL,,CAAW,KAAKO,CAAhB,,KAAKC,CAAhB,,KAAKC,KAAL,
pB,CAAhB,GAA8C,IAA5D;AACA,UAAM0M,KAAK,GAAG,KAAKA,KAAnB;AACA,UAAIA,KAAK,KAAK,CAAd,,
AAkB,KAAK2P,GAAL,CAAS,KAAKC,CAAd,,KAAKC,CAAd,,KAAKC,KAAL,CAAW,KAAKC,KAAhB,,KAAKC,
ACpc,IAAP,CAAYqc,GAAZ,CAAgB,KAAhB;AACA,aAAO,KAAKC,KAAZ;AACD;;;wBAEe;AACd,aAAO,KAAKC,
aAAO,KAAKC,KAAZ;AACD;;;wBAEe;AACd,aAAO,KAAKC,KAAZ;AACD;;;wBAEe;AACd,aAAO,KAAKC,
D;;;;;;;;;;;;EAtDiBwC;;AAClBnB;;AACA;;;;;;;;IAQMuC;;AACJ;;;;;;;;;;;AAWA,mBAAY9I,IAAZ,,EAAkBqC,IAAlB,
A6B;AAAA,QAAXA,KAAW,IAAX;AAAA;AAAA,QAAXA,KAAW,IAAX;AAAA;AAAA,QAAXA,KAAW,IAAX;AAAA,QAAXA,KAAW,
L,GAAY,SAAZ,;AACA;;;;;;;AAMA,SAAKO,IAAL,GAAY,IAAZ,;AACA,SAAKC,KAAL,GAAa,IAAb,;AACA,SAAK
4R,IAAI,CAAC1Y,KAAL,,CAAW,KAAKO,CAAhB,,KAAKC,CAAhB,,KAAKC,KAAL,CAAW,KAAKC,KAAhB,,KAAKC,
AAU6R,UAAV,,CAAqBD,IAArB,,CAAP;AACD,GA1FU;;AA4FX;;;;;;;;;;;AAWAG,EAAAA,KAAvDW,iBuDLS,MAAMkO8b
U6R,UAAV,,CAAqBD,IAArB,,CAAP;AACD,GA1FU;;AA4FX;;;;;;;;;;;AAWAG,EAAAA,KAAvDW,iBuDLS,MAAMkO8b
;;;;;;;;;;;;

KA,UAAL,CAAgBC,aAAvC,EAAsD;AACpD/G,QAAAAA,IAAI,CAACrL,MAAL,GAAc,KAAKmS,UAAL,CAAgBC,aAA9B;AACD;AACF;;AAED,QAAMC,OAAO,GAAG,IAAIP,OAAJ,CAAY9I,IAAAZ,EAAAkBqC,IAAlB,CAAAhB;AACA,SAAK6G,QAAL,CAAAchd,IAAAd,CAAAmBmd,OAAAnB;AAEA,WAAOA,OAAP;AAAA;AACD;AAED;;;;;;;;;;;;SAWAC,WAAAA,oBAAAW;AACT,WAAO,KAAKJ,QAAL,CAAcK,IAAd,CAAAqB,IAAAlB,CAAAmB,IAAAlB,CAAAmB,IAAAlB,CAAAm

AAQ;AAAA;;AACN,QAAI,KAAKpC,SAAT,EAAoB;AAClB,aAAO,IAAIiD,OAAJ,CAAY,UAACJ,OAAD,EAAUC,MAAV,EAAqB;AACtC,YAAI,MAAI,CAAChO,KAAT,EAAgB;AACdgO,UAAAA,MAAI,CAAChO,KAAL,GAAa,IAAb;AACA+N,UAAAA,OAAO;AACR;AACF,OALM,CAAP;AAMD,KAPD;;AAQA,QAAMK,QAAQ,GAAG,SAAXA,QAAW,GAAM;AACrB,UAAIJ,MAAI,CAACK,KAAL,CAAWC,MAAX,KAAsB,CAA1B,EAA6B;AAC3BN,QAAAA,MAAI,CAACO,IAAL,CAAU,KAAV;AACD;AACF,KAJD;;AAKAP,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAACC,GAAD,EAAS;AACxBT,MAAAA,MAAI,CAACU,OAAL,CAAaD,GAAb;AACAJ,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACG,IAAD,EAAOC,MAAP,EAAkB;AAClCZ,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBI,IAAjB,EAAuBC,MAAvB;AACAP,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACK,IAAD,EAAOC,MAAP,EAAkB;AAClCd,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBM,IAAjB,EAAuBC,MAAvB;AACAT,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAACO,KAAD,EAAQC,MAAR,EAAmB;AACpChB,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkBQ,KAAlB,EAAyBC,MAAzB;AACAX,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAACS,GAAD,EAAS;AACvBjB,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBU,GAAjB;AACAZ,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAACU,IAAD,EAAOC,MAAP,EAAkB;AACjCnB,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBW,IAAjB,EAAuBC,MAAvB;AACAd,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACY,IAAD,EAAOC,MAAP,EAAkB;AAClCrB,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBa,IAAjB,EAAuBC,MAAvB;AACAhB,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACc,IAAD,EAAOC,MAAP,EAAkB;AAClCvB,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBe,IAAjB,EAAuBC,MAAvB;AACAlB,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAACgB,KAAD,EAAQC,MAAR,EAAmB;AACpCzB,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkBiB,KAAlB,EAAyBC,MAAzB;AACApB,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAACkB,GAAD,EAAS;AACvB1B,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBmB,GAAjB;AACArB,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAACmB,IAAD,EAAOC,MAAP,EAAkB;AACjC5B,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBoB,IAAjB,EAAuBC,MAAvB;AACAvB,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACqB,IAAD,EAAOC,MAAP,EAAkB;AAClC9B,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBsB,IAAjB,EAAuBC,MAAvB;AACAzB,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACuB,IAAD,EAAOC,MAAP,EAAkB;AAClChC,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBwB,IAAjB,EAAuBC,MAAvB;AACA3B,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAACyB,KAAD,EAAQC,MAAR,EAAmB;AACpClC,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkB0B,KAAlB,EAAyBC,MAAzB;AACA7B,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAAC2B,GAAD,EAAS;AACvBnC,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB4B,GAAjB;AACA9B,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAAC4B,IAAD,EAAOC,MAAP,EAAkB;AACjCrC,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB6B,IAAjB,EAAuBC,MAAvB;AACAhC,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAAC8B,IAAD,EAAOC,MAAP,EAAkB;AAClCvC,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB+B,IAAjB,EAAuBC,MAAvB;AACAlC,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACgC,IAAD,EAAOC,MAAP,EAAkB;AAClCzC,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBiC,IAAjB,EAAuBC,MAAvB;AACApC,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAACkC,KAAD,EAAQC,MAAR,EAAmB;AACpC3C,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkBmC,KAAlB,EAAyBC,MAAzB;AACAtC,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAACoC,GAAD,EAAS;AACvB5C,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBqC,GAAjB;AACAvC,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAACqC,IAAD,EAAOC,MAAP,EAAkB;AACjC9C,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBsC,IAAjB,EAAuBC,MAAvB;AACAzC,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACuC,IAAD,EAAOC,MAAP,EAAkB;AAClChD,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBwC,IAAjB,EAAuBC,MAAvB;AACA3C,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACyC,IAAD,EAAOC,MAAP,EAAkB;AAClCjD,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiByC,IAAjB,EAAuBC,MAAvB;AACA5C,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAAC0C,KAAD,EAAQC,MAAR,EAAmB;AACpCnD,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkB2C,KAAlB,EAAyBC,MAAzB;AACA9C,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAAC4C,GAAD,EAAS;AACvBpD,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB6C,GAAjB;AACA/C,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAAC6C,IAAD,EAAOC,MAAP,EAAkB;AACjCtD,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB8C,IAAjB,EAAuBC,MAAvB;AACAjD,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAAC+C,IAAD,EAAOC,MAAP,EAAkB;AAClCxD,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBgD,IAAjB,EAAuBC,MAAvB;AACAnD,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACiD,IAAD,EAAOC,MAAP,EAAkB;AAClC1D,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBkD,IAAjB,EAAuBC,MAAvB;AACArD,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAACmD,KAAD,EAAQC,MAAR,EAAmB;AACpC5D,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkBoD,KAAlB,EAAyBC,MAAzB;AACAvD,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAACqD,GAAD,EAAS;AACvB7D,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBsD,GAAjB;AACAxD,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAACsD,IAAD,EAAOC,MAAP,EAAkB;AACjC/D,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBuD,IAAjB,EAAuBC,MAAvB;AACA1D,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACwD,IAAD,EAAOC,MAAP,EAAkB;AAClCjE,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiByD,IAAjB,EAAuBC,MAAvB;AACA5D,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAAC0D,IAAD,EAAOC,MAAP,EAAkB;AAClCnE,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB2D,IAAjB,EAAuBC,MAAvB;AACA9D,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAAC4D,KAAD,EAAQC,MAAR,EAAmB;AACpCrE,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkB6D,KAAlB,EAAyBC,MAAzB;AACAhE,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAAC8D,GAAD,EAAS;AACvBtE,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB+D,GAAjB;AACAjE,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAAC+D,IAAD,EAAOC,MAAP,EAAkB;AACjCxE,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBgE,IAAjB,EAAuBC,MAAvB;AACAnE,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACiE,IAAD,EAAOC,MAAP,EAAkB;AAClC1E,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBkE,IAAjB,EAAuBC,MAAvB;AACArE,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACmE,IAAD,EAAOC,MAAP,EAAkB;AAClC5E,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBoE,IAAjB,EAAuBC,MAAvB;AACAvE,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAACqE,KAAD,EAAQC,MAAR,EAAmB;AACpC9E,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkBsE,KAAlB,EAAyBC,MAAzB;AACAzE,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAACuE,GAAD,EAAS;AACvB/E,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBwE,GAAjB;AACA1E,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAACwE,IAAD,EAAOC,MAAP,EAAkB;AACjCjF,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiByE,IAAjB,EAAuBC,MAAvB;AACA5E,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAAC0E,IAAD,EAAOC,MAAP,EAAkB;AAClCnF,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB2E,IAAjB,EAAuBC,MAAvB;AACA9E,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAAC4E,IAAD,EAAOC,MAAP,EAAkB;AAClCrF,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB6E,IAAjB,EAAuBC,MAAvB;AACAhF,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAAC8E,KAAD,EAAQC,MAAR,EAAmB;AACpCvF,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkB+E,KAAlB,EAAyBC,MAAzB;AACAlF,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAACgF,GAAD,EAAS;AACvBxF,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBiF,GAAjB;AACAnF,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAACiF,IAAD,EAAOC,MAAP,EAAkB;AACjC1F,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBkF,IAAjB,EAAuBC,MAAvB;AACArF,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACmF,IAAD,EAAOC,MAAP,EAAkB;AAClC5F,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBoF,IAAjB,EAAuBC,MAAvB;AACAvF,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACqF,IAAD,EAAOC,MAAP,EAAkB;AAClC9F,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBsF,IAAjB,EAAuBC,MAAvB;AACAzF,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAACuF,KAAD,EAAQC,MAAR,EAAmB;AACpChG,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkBwF,KAAlB,EAAyBC,MAAzB;AACA3F,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAACyF,GAAD,EAAS;AACvBjG,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB0F,GAAjB;AACA5F,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAAC0F,IAAD,EAAOC,MAAP,EAAkB;AACjCnG,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB2F,IAAjB,EAAuBC,MAAvB;AACA9F,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAAC4F,IAAD,EAAOC,MAAP,EAAkB;AAClCrG,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB6F,IAAjB,EAAuBC,MAAvB;AACAhG,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAAC8F,IAAD,EAAOC,MAAP,EAAkB;AAClCvG,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB+F,IAAjB,EAAuBC,MAAvB;AACAlG,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAACgG,KAAD,EAAQC,MAAR,EAAmB;AACpCzG,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkBiG,KAAlB,EAAyBC,MAAzB;AACApG,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAACkG,GAAD,EAAS;AACvB1G,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBmG,GAAjB;AACArG,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAACmG,IAAD,EAAOC,MAAP,EAAkB;AACjC5G,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBoG,IAAjB,EAAuBC,MAAvB;AACAvG,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACqG,IAAD,EAAOC,MAAP,EAAkB;AAClC9G,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBsG,IAAjB,EAAuBC,MAAvB;AACAzG,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACuG,IAAD,EAAOC,MAAP,EAAkB;AAClChH,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBwG,IAAjB,EAAuBC,MAAvB;AACA3G,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAACyG,KAAD,EAAQC,MAAR,EAAmB;AACpClH,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkB0G,KAAlB,EAAyBC,MAAzB;AACA7G,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAAC2G,GAAD,EAAS;AACvBnH,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB4G,GAAjB;AACA9G,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAAC4G,IAAD,EAAOC,MAAP,EAAkB;AACjCrH,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB6G,IAAjB,EAAuBC,MAAvB;AACAhH,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAAC8G,IAAD,EAAOC,MAAP,EAAkB;AAClCvH,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB+G,IAAjB,EAAuBC,MAAvB;AACAlH,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACgH,IAAD,EAAOC,MAAP,EAAkB;AAClCzH,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBiH,IAAjB,EAAuBC,MAAvB;AACApH,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAACkH,KAAD,EAAQC,MAAR,EAAmB;AACpC3H,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkBmH,KAAlB,EAAyBC,MAAzB;AACAtH,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAACoH,GAAD,EAAS;AACvB5H,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBqH,GAAjB;AACAvH,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAACqH,IAAD,EAAOC,MAAP,EAAkB;AACjC9H,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBsH,IAAjB,EAAuBC,MAAvB;AACAzH,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACuH,IAAD,EAAOC,MAAP,EAAkB;AAClChI,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBwH,IAAjB,EAAuBC,MAAvB;AACA3H,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACyH,IAAD,EAAOC,MAAP,EAAkB;AAClClI,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB0H,IAAjB,EAAuBC,MAAvB;AACA7H,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAAC2H,KAAD,EAAQC,MAAR,EAAmB;AACpCpI,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkB4H,KAAlB,EAAyBC,MAAzB;AACA/H,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAAC6H,GAAD,EAAS;AACvBrI,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB8H,GAAjB;AACAhI,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAAC8H,IAAD,EAAOC,MAAP,EAAkB;AACjCvI,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB+H,IAAjB,EAAuBC,MAAvB;AACAlI,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACgI,IAAD,EAAOC,MAAP,EAAkB;AAClCzI,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBiI,IAAjB,EAAuBC,MAAvB;AACApI,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACkI,IAAD,EAAOC,MAAP,EAAkB;AAClC3I,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBmI,IAAjB,EAAuBC,MAAvB;AACAtI,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAACoI,KAAD,EAAQC,MAAR,EAAmB;AACpC7I,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkBqI,KAAlB,EAAyBC,MAAzB;AACAxI,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAACsI,GAAD,EAAS;AACvB9I,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBuI,GAAjB;AACAzI,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAACuI,IAAD,EAAOC,MAAP,EAAkB;AACjChJ,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBwI,IAAjB,EAAuBC,MAAvB;AACA3I,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACyI,IAAD,EAAOC,MAAP,EAAkB;AAClClJ,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB0I,IAAjB,EAAuBC,MAAvB;AACA5I,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAAC0I,IAAD,EAAOC,MAAP,EAAkB;AAClCnJ,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB2I,IAAjB,EAAuBC,MAAvB;AACA9I,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAAC4I,KAAD,EAAQC,MAAR,EAAmB;AACpCrJ,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkB6I,KAAlB,EAAyBC,MAAzB;AACAhJ,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAAC8I,GAAD,EAAS;AACvBtJ,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB+I,GAAjB;AACAjJ,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAAC+I,IAAD,EAAOC,MAAP,EAAkB;AACjCxJ,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBgJ,IAAjB,EAAuBC,MAAvB;AACAnJ,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACiJ,IAAD,EAAOC,MAAP,EAAkB;AAClC1J,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBkJ,IAAjB,EAAuBC,MAAvB;AACArJ,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACmJ,IAAD,EAAOC,MAAP,EAAkB;AAClC5J,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBoJ,IAAjB,EAAuBC,MAAvB;AACAvJ,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAACqJ,KAAD,EAAQC,MAAR,EAAmB;AACpC9J,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkBsJ,KAAlB,EAAyBC,MAAzB;AACAzJ,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAACuJ,GAAD,EAAS;AACvB/J,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBwJ,GAAjB;AACA1J,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAACwJ,IAAD,EAAOC,MAAP,EAAkB;AACjCjK,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiByJ,IAAjB,EAAuBC,MAAvB;AACA5J,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAAC0J,IAAD,EAAOC,MAAP,EAAkB;AAClCnK,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB2J,IAAjB,EAAuBC,MAAvB;AACA9J,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAAC4J,IAAD,EAAOC,MAAP,EAAkB;AAClCrK,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB6J,IAAjB,EAAuBC,MAAvB;AACAhK,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAAC8J,KAAD,EAAQC,MAAR,EAAmB;AACpCvK,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkB+J,KAAlB,EAAyBC,MAAzB;AACAlK,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAACgK,GAAD,EAAS;AACvBxK,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBiK,GAAjB;AACAnK,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAACiK,IAAD,EAAOC,MAAP,EAAkB;AACjC1K,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBkK,IAAjB,EAAuBC,MAAvB;AACArK,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACmK,IAAD,EAAOC,MAAP,EAAkB;AAClC5K,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBoK,IAAjB,EAAuBC,MAAvB;AACAvK,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAACqK,IAAD,EAAOC,MAAP,EAAkB;AAClC9K,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiBsK,IAAjB,EAAuBC,MAAvB;AACAzK,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,SAAR,EAAmB,UAACuK,KAAD,EAAQC,MAAR,EAAmB;AACpChL,MAAAA,MAAI,CAACO,IAAL,CAAU,MAAV,EAAkBwK,KAAlB,EAAyBC,MAAzB;AACA3K,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,MAAR,EAAgB,UAACyK,GAAD,EAAS;AACvBjL,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB0K,GAAjB;AACA5K,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,OAAR,EAAiB,UAAC0K,IAAD,EAAOC,MAAP,EAAkB;AACjCnL,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB2K,IAAjB,EAAuBC,MAAvB;AACA9K,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAAC4K,IAAD,EAAOC,MAAP,EAAkB;AAClCrL,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB6K,IAAjB,EAAuBC,MAAvB;AACAhL,MAAAA,QAAQ;AACT,KAHD;AAIAL,IAAAA,MAAI,CAACQ,EAAL,CAAQ,QAAR,EAAkB,UAAC8K,IAAD,EAAOC,MAAP,EAAkB;AAClCvL,MAAAA,MAAI,CAACO,IAAL,CAAU,KAAV,EAAiB+K,IAAjB,EAAuBC,M

cAAA,qBAAYM,KAAZ,EAAmB;AACjBA,IAAAA,KAAK,GAAG,KAAKhE,KAAL,CAAWgE,KAAX,CAAR;;AAEA,QAAIA,KAAK,KAAK,CAAV,IAAe,KAAKZ,KAAL,CAAWhH,MAAX,GAAoB,CAAvC,EAA0C;AACxC,WAAKgH,KAAL,CAAW,CAAX,EAAcsP,IAAd,CAAmBa,MAAnB,GAA4B,GAA4B,KAAKnQ,KAAL,CAAWY,KAAX,EAAkB0O,IAAlB,CAAuBa,MAAnD;AACD;;AAED,gCAAa7P,WAAb,YAAyBM,KAAzB;AACD;;SAED6V,YAAA,mBAAU7V,KAAV,EAAiB0O,IAAjB,EAAuBnI,IAAzB,EAA+B+B;AAC7B,QAAMnP,KAAK,wBAAS,YAAT,KAA0B,KAAKA,KAAL,CAAWY,KAAX,EAAkB0O,IAAlB,CAAuBa,MAAvD,GAAgE,KAAKnQ,KAAL,CAAWY,KAAX,EAAkB0O,IAAlB,CAAuBa,MAA7F;AACA,QAAIA,MAAJ,EAAY;AACV,UAAIA,OAAOhH,IAAP,KAAgB,KAAhB,IAAyBgH,OAAOhH,IAAP,KAAgB,KAA7C,EAAoD;AAClD,eAAOgH,OAAOhH,IAAd;AACD;AACD,UAAIgH,OAAOhH,IAAP,KAAgB,KAAhB,IAAyBgH,OAAOhH,IAAP,KAAgB,KAA7C,EAAoD;AAClD,eAAOgH,OAAOhH,IAAd;AACD;AACF;AACD,WAAO,IAAP;AACD;;AAED,gCAAa,YAAb,EAA2B,UAAUmH,IAAV,EAAgB;AACzC,QAAIA,KAAKnH,IAAL,KAAc,KAAlB,EAAyB;AACvB,aAAOmH,KAAKnH,IAAZ;AACD;AACD,QAAImH,KAAKnH,IAAL,KAAc,KAAlB,EAAyB;AACvB,aAAOmH,KAAKnH,IAAZ;AACD;AACD,WAAO,IAAP;AACD,GAPD;;AASA,MAAMoH,YAAY,SAAZA,SAAY,CAAUC,IAAV,EAAgBC,IAAhB,EAAsB;AACtC,QAAIC,IAAJ;AACA,QAAIF,KAAKG,MAAL,KAAgB,CAAhB,IAAqBH,KAAKI,UAAL,CAAgB,CAAhB,MAAuB,GAAhD,EAAqD;AACnDF,aAAOF,KAAKK,KAAL,CAAW,CAAX,CAAP;AACD,KAFD,MAEO,IAAIL,KAAKG,MAAL,KAAgB,CAAhB,IAAqBH,KAAKI,UAAL,CAAgB,CAAhB,MAAuB,GAAhD,EAAqD;AAC1DF,aAAOF,KAAKK,KAAL,CAAW,CAAX,CAAP;AACD,KAFM,MAEA

ACD;AACF;AAED;;;;;;;;;;;;;;;wBAYW;AACT,aAAO,KAAKA,IAAL,IAAa,KAAK9O,EAAzB;AACD;;;;;IClKk
Bqd;;;;;;;;;SACnBxQ,WAAA,sBAAW;AACT,SAAKE,MAAL,GAAcF,QAAQ,CAAC,KAAKC,KAAN,EAAa;AA
AEI,MAAAA,YAAY,EAAE;AAAhB,KAAb,CAAtB;AACD;;SAEDoB,UAAA,iBAAQI,KAAR,EAAAe;AACb,QA
AM3M,IAAI,GAAG,IAAIwT,OAAJ,EAAb;AACA,SAAKU,IAAL,CAAUlU,IAAV,EAAgB2M,KAAK,CAAC,CAAD,
AD,CAArB,EAA0BA,KAAK,CAAC,CAAD,CAA/B;AACA3M,IAAAA,IAAI,CAAC8M,IAAL,CAAUH,KAAK,CAAC,C
GAAkB;AAAEnJ,MAAAA,IAAI,EAAEuI,KAAK,CAAC,CAAD,CAAb;AAAkBtI,MAAAA,MAAM,EAAEsI,KA
AK,CAAC,CAAD;AAA/B,KAAlB;AAEA,QAAIA,KAAK,CAAC,CAAD,CAAL,CAASrI,MAAT,GAAkB,CAAtB,EAAyB
,CAAf;AAAX;AACA,QAAIoD,IAAI,CAACpD,MAAL,GAAc,CAAlB,EAAqB;AACnBoD,MAAAA,IAAI,CAAC
mP;;AAE7B,QAAI,QAAQ3S,IAAR,CAAa,KAAKC,KAAlB,CAAJ,EAA8B;AAC5B,KAAKC,KAAL,GAAa,KAAKF
,CAAa+V,IAAb,CAAJ,EAAwB;AACtB,UAAIA,IAAI,CAACpD,MAAL,GAAc,CAAlB,EAAqB;AACnBoD,QAAA
;AACtBvP,MAAAA,IAAI,CAACuP,IAAL,CAAUH,KAAK,CAAC,CAAD,CAAf,EAAoBA,KAAK,CAAC,CAAD,CAAzB
AACAvP,MAAAA,IAAI,CAACuP,IAAL,CAAUH,KAAK,CAAC,CAAD,CAAf,EAAoBA,KAAK,CAAC,CAAD,CAAzB
AI,CAACmP,IAAL,CAAUH,KAAK,CAAC,CAAD,CAAf,EAAoBA,KAAK,CAAC,CAAD,CAAzB;AACA,UAAIA,KAAK
iBG,IAAjB;AACAvP,MAAAA,IAAI,CAACuP,IAAL,CAAUH,KAAK,CAAC,CAAD,CAAf,EAAoBA,KAAK,CAAC,CAAD,CAAzB
AI,CAACmP,IAAL,CAAUH,KAAK,CAAC,CAAD,CAAf,EAAoBA,KAAK,CAAC,CAAD,CAAzB;AACA,UAAIA,KAAK
lB;AACD,KAJD,MAIO;AACL,UAAM5P,IAAI,GAAG,KAAKA,IAAlB;AACA,UAAIA,IAAI,CAACoD,MAAL,GAAc,CAAlB,
AM5P,KAAK,CAAC,CAAD,CAAf,EAAoBA,KAAK,CAAC,CAAD,CAAzB;AACA,UAAIA,KAAK,CAAC,CAAD,CAAL,CAAS
AG6P,IAAI,CAACpD,MAAL,GAAc,CAAlB,EAAqB;AACnBoD,QAAA,IAAI,CAACuP,IAAL,CAAUH,KAAK,CAAC,C
AAC7P,KAAK,CAAC,CAAD,CAAf,EAAoBA,KAAK,CAAC,CAAD,CAAzB;AACA,UAAIA,KAAK,CAAC,CAAD,CAAL,CAAS
,yBAAX,EAAsC;AACpC,UAAIA,KAAK,CAAC,CAAD,CAAL,CAASrI,MAAT,GAAkB,CAAtB,EAAyB;AACvBoD,QA
AM7P,KAAK,CAAC,CAAD,CAAf,EAAoBA,KAAK,CAAC,CAAD,CAAzB;AACA,UAAIA,KAAK,CAAC,CAAD,CAAL,CAAS
Aj

AlC;AACD;AACF,SAPD,EAHoB;AAYpB;AACA;AACA;;AACA,YAAM8M,WAAW,GAAGC,kBAAkB,CAAC
F,SAAD,EAAY,CAChD,cADgD,EAEhD,aAFgD,EAGhD,aAHgD,EAIhD,aAJgD,CAAZ,CAAtC;AAMA,YAAMG
,MAAM,GAAG7U,UAAU,CAAC8U,MAAX,CAAkB;AAC/BR,UAAAA,SAAS,EAAEK;AADoB,SAAlB,CAAf;
AAGAL,QAAAA,SAAS,CAAC1iB,IAAD,CAAT,GAAkBijB,MAAM,CAACP,SAAzB;AACD;;AACD,aAAOA,S
AAS,CAAC1iB,IAAD,CAAhB;AACD,KAAvCsC;;AAAA;AAAA;;AA0CzC,SAAO2iB,WAAP;AACD,CA3CD;;A
CnBA;;AACA;;;

KAAL,CAAWG,GAAX,IAAkB,MAAI,CAACH,KAAL,CAAWK,EAA7B,IAAmCH,eAAnC,IAAsDE,QAAtD,IAAkE1kB,MADpE;;AAGA,UAAMklB,eAAe,GAAG,MAAI,CAACC,uBAAL,CACtBC,cAAc,CAAC,MAAI,CAACxH,KAAN,EAAa2F,KAAb,EAAoBD,YAApB,CAAd,IAAmDvhB,YAD7B,EAAEtB,MAAI,CAAC6b,KAAiC,KAAFiB,CAAxB;;AAKA,UAAMyH,WAAW,GAAG,KAAK,CAACyB,mBAAD,CAAzB;AACA,UAAMK,aAAN,CAAoBC,QAApB,EAA8BC,SAA9B,EAAyC;AACvC,UAAMC,IAAI,GAAG,MAAMH,aAAN,CAAoBC,QAApB,EAA8BC,SAA9B,CAAb;AACA,SAAKE,KAAL,GAAaD,IAAI,CAACC,KAAlB;AACA,WAAOD,IAAP;AACD;;AAED,QAAME,KAAN,CAAYC,OAAZ,EAAqB;AACnB,UAAMC,KAAK,GAAG,MAAM,KAAKC,SAAL,CAAeF,OAAf,CAApB;AACA,UAAMG,KAAK,GAAG,MAAM,KAAKC,SAAL,CAAeJ,OAAf,CAApB;AACA,WAAOC,KAAK,GAAGE,KAAf;AACD;;AAED,QAAMC,SAAN,CAAgBJ,OAAhB,EAAyB;AACvB,QAAIC,KAAK,GAAG,CAAZ;AACA,UAAMK,MAAM,GAAG,MAAM,KAAKC,OAAL,CAAaP,OAAb,CAArB;;AAEA,eAAW,MAAMQ,KAAjB,IAA0BF,MAA1B,EAAkC;AAChC,UAAIE,KAAK,CAACC,IAAN,KAAe,MAAnB,EAA2B;AACzBR,QAAAA,KAAK,IAAIO,KAAK,CAACE,IAAf;AACD;AACF;;AAED,WAAOT,KAAP;AACD;;AAED,QAAMI,SAAN,CAAgBF,OAAhB,EAAyB;AACvB,QAAIG,KAAK,GAAG,CAAZ;AACA,UAAMG,MAAM,GAAG,MAAM,KAAKC,OAAL,CAAaP,OAAb,CAArB;;AAEA,eAAW,MAAMQ,KAAjB,IAA0BF,MAA1B,EAAkC;AAChC,UAAIE,KAAK,CAACC,IAAN,KAAe,MAAnB,EAA2B;AACzBN,QAAAA,KAAK,IAAIK,KAAK,CAACE,IAAf;AACD;AACF;;AAED,WAAOP,KAAP;AACD;;AAED,QAAMG,OAAN,CAAcP,OAAd,EAAuB;AACrB,QAAIY,KAAK,GAAG,CAAZ;AACA,QAAIC,KAAK,GAAG,CAAZ;AACA,UAAMC,KAAK,GAAG,EAAd;;AAEA,WAAOF,KAAK,GAAGZ,OAAf,EAAwB;AACtB,YAAMe,KAAK,GAAG,MAAM,KAAKC,IAAL,CAAUJ,KAAV,CAApB;AACAA,MAAAA,KAAK,IAAIG,KAAK,CAACE,MAAf;AACAJ,MAAAA,KAAK,IAAI,CAAT;AACAC,MAAAA,KAAK,CAACI,IAAN,CAAWH,KAAX;AACD;;AAED,WAAOD,KAAP;AACD;;AAED,QAAMG,IAAN,CAAWE,MAAX,EAAmB;AACjB,UAAMC,KAAK,GAAG,IAAIC,UAAJ,CAAeF,MAAf,CAAd;AACA,UAAMG,MAAM,GAAG,MAAMC,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBL,KAArB,CAArB;AACA,WAAOM,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAeN,MAAf,CAAX,EAAmCO,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAA1C,EAA6EC,IAA7E,CAAkF,EAAlF,CAAP;AACD;;AAED,QAAMC,IAAN,CAAWC,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMY,IAAN,CAAWC,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMa,IAAN,CAAWC,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMc,IAAN,CAAWL,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMe,IAAN,CAAWN,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMgB,IAAN,CAAWP,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMiB,IAAN,CAAWR,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMkB,IAAN,CAAWT,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMmB,IAAN,CAAWV,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMoB,IAAN,CAAWX,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMqB,IAAN,CAAWZ,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMsB,IAAN,CAAWb,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMuB,IAAN,CAAWd,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMwB,IAAN,CAAWf,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMyB,IAAN,CAAWhB,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAM0B,IAAN,CAAWjB,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAM2B,IAAN,CAAWlB,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAM4B,IAAN,CAAWnB,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAM6B,IAAN,CAAWpB,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAM8B,IAAN,CAAWrB,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAM+B,IAAN,CAAWtB,IAAX,EAAiB;AACf,UAAMC,MAAM,GAAG,IAAIC,WAAJ,EAAf;AACA,UAAMC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMgC,IAAI,GAAG,MAAMb,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMiC,IAAI,GAAG,MAAMd,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMkC,IAAI,GAAG,MAAMf,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMmC,IAAI,GAAG,MAAMhB,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMoC,IAAI,GAAG,MAAMjB,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMqC,IAAI,GAAG,MAAMlB,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMsC,IAAI,GAAG,MAAMnB,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMuC,IAAI,GAAG,MAAMpB,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMwC,IAAI,GAAG,MAAMrB,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMyC,IAAI,GAAG,MAAMtB,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAM0C,IAAI,GAAG,MAAMvB,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAM2C,IAAI,GAAG,MAAMxB,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAM4C,IAAI,GAAG,MAAMzB,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAM6C,IAAI,GAAG,MAAM1B,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAM8C,IAAI,GAAG,MAAM3B,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAM+C,IAAI,GAAG,MAAM5B,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMgD,IAAI,GAAG,MAAM7B,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMiD,IAAI,GAAG,MAAM9B,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMkD,IAAI,GAAG,MAAM/B,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMmD,IAAI,GAAG,MAAMhC,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMoD,IAAI,GAAG,MAAMjC,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMqD,IAAI,GAAG,MAAMlC,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMsD,IAAI,GAAG,MAAMnC,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMuD,IAAI,GAAG,MAAMpC,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CAAxC,EAA2EC,IAA3E,CAAgF,EAAhF,CAAP;AACD;;AAED,QAAMwD,IAAI,GAAG,MAAMrC,MAAM,CAACC,MAAP,CAAcC,MAAd,CAAqBS,MAAM,CAACG,MAAP,CAAcJ,IAAd,CAArB,CAAnB;AACA,WAAOb,KAAK,CAACC,IAAN,CAAW,IAAIC,UAAJ,CAAec,IAAf,CAAX,EAAiCb,GAAG,IAAIA,GAAG,CAACC,QAAJ,CAAa,EAAb,EAAiBC,QAAjB,CAA0B,CAA1B,EAA6B,GAA7B,CA

AKA;;;AACAuB,IAAAA,4BAA4B,CAACjC,KAA7B,GAAqCmC,UAArC;AAEAF,IAAAA,4BAA4B,CAACnmB
,WAA7B,GAA2CA,WAA3C,CAlDuF;;AAqDvFmmB,IAAAA,4BAA4B,CAACvB,iBAA7B,GAAiDA,iBAAjD,C
ArDuF;;AAwDvFuB,IAAAA,4BAA4B,CAACR,WAA7B,GAA2C,IAAIvD,WAAJ;AAEzC8D,IAAAA,kBAAkB,
GAAGtmB,MAAM,CAAC+lB,WAAP,CAAmBtiB,KAAnB,CAAyB6d,MAAzB,CAAgC7d,KAAhC,CAAH,GAA4
CA,KAFrB,CAA3C,CAxDuF;;AA8DvF8iB,IAAAA,4BAA4B,CAACxlB,iBAA7B,GAAiD,uBAAjD,CA9DuF;;AA
gEvFwlB,IAAAA,4BAA4B,CAACvmB,MAA7B,GAAsCsmB,kBAAkB;AAEpDtmB,IAAAA,MAAM,CAACA,M
AF6C,GAGpDA,MAHJ,CAhEuF;;AAqEvFumB,IAAAA,4BAA4B,CAACK,aA7B,GAA6C,SASA,aAAT,CAA
uB5jB,GAAvB,EAAoC;AAAA,UAC1D2J,CAD0D,GACjBjD,OADiB,CACvEtJ,WADuE;AAAA,UAC1CymB,EA
D0C,GACjBnd,OADiB,CACvDsD,WADuD;AAAA,UACnC8Z,aADmC,iCACjBpd,OADiB;;AAE/E,UAAMqd,U
AAU,gBACXD,aADW;AAEdxC,QAAAA,KAAK,EAAEmC,UAFO;AAGdL,QAAAA,eAAe,EAAEK,UAAU,GAAG
hB;;AAMA,aAAOD,2BAA2B,GAAD,EAAM+jB,UAAN,EAAkBC,IAAlB,CAAlC;AACD,KATD,C
ArEuF;;;AAiFvF9C,IAAAA,MAAM,CAACqmB,cAAP,CAAsBT,4BAAtB,EAAoC,cAAsBT,4BAAtB,EAAoD,EAAoE;AAClIthB,MAAAA,GADkI,eAC9H;AAAA,YACIyiB,MADJ,GACe,KADf,CACIA,MADJ;AAEF,eAAOA,MAAM,CAACA,M
AAAA,GADkE,iBAAC5D,KAAD,EAAQ;AAAA,YAC1E6D,MAD0E,GACjE,KADiE,CAC1EA,MAD0E;AAEjF,aAAKA,MAAL,GAAcA,MAAM,CAAC7D,KAAD,CAApB;AACD,OAJiI,EAIhI,YAAY,IAJoH,EAIhI,cAAc,IAJkH,EAIhI,UAAU,IAJsH,EAIhI,EAJgI;AAKlI,KAtFuF,EAsFtF,EAtFsF,EAsFlF,EAtFkF,EAsF9E,EAtF8E,EAsF1E,EAtF0E,EAsFtE,EAtFsE,EAsFlE,EAtFkE,EAsF9D,EAtF8D,EAsF1D,EAtF0D,EAsFtD,EAtFsD,EAsFlD,EAtFkD,EAsF9C,EAtF8C,EAsF1C,EAtF0C,EAsFtC,EAtFsC,EAsFlC,EAtFkC,EAsF9B,EAtF8B,EAsF1B,EAtF0B,EAsFtB,EAtFsB,EAsFlB,EAtFkB,EAsFd,EAtFc,EAsFV,EAtFU,EAsFN,EAtFM,EAsFF,EAtFE,EAsFE,EAtFF,EAsFM,EAtFN,EAsFU,EAtFV,EAsFc,EAtFd,EAsFkB,EAtFlB,EAsFsB,EAtFtB,EAsF0B,EAtF1B,EAsF8B,EAtF9B,EAsFkC,EAtFlC,EAsFsC,EAtFtC,EAsF0C,EAtF1C,EAsF8C,EAtF9C,EAsFkD,EAtFlD,EAsFsD,EAtFtD,EAsF0D,EAtF1D,EAsF8D,EAtF9D,EAsFkE,EAtFlE,EAsFsE,EAtFtE,EAsF0E,EAtF1E,EAsF8E,EAtF9E,EAsFkF,EAtFlF,EAsFsF,EAtFtF,EAsF0F,EAtF1F,EAsF8F,EAtF9F,EAsFkG,EAtFlG,EAsFsG,EAtFtG,EAsF0G,EAtF1G,EAsF8G,EAtF9G,EAsFkH,EAtFlH,EAsFsH,EAtFtH,EAsF0H,EAtF1H,EAsF8H,EAtF9H,EAsFkI,EAtFlI,EAsFsI,EAtFtI,EAsF0I,EAtF1I,EAsF8I,EAtF9I,EAsFkJ,EAtFlJ,EAsFsJ,EAtFtJ,EAsF0J,EAtF1J,EAsF8J,EAtF9J,EAsFkK,EAtFlK,EAsFsK,EAtFtK,EAsF0K,EAtF1K,EAsF8K,EAtF9K,EAsFkL,EAtFlL,EAsFsL,EAtFtL,EAsF0L,EAtF1L,EAsF8L,EAtF9L,EAsFkM,EAtFlM,EAsFsM,EAtFtM,EAsF0M,EAtF1M,EAsF8M,EAtF9M,EAsFkN,EAtFlN,EAsFsN,EAtFtN,EAsF0N,EAtF1N,EAsF8N,EAtF9N,EAsFkO,EAtFlO,EAsFsO,EAtFtO,EAsF0O,EAtF1O,EAsF8O,EAtF9O,EAsFkP,EAtFlP,EAsFsP,EAtFtP,EAsF0P,EAtF1P,EAsF8P,EAtF9P,EAsFkQ,EAtFlQ,EAsFsQ,EAtFtQ,EAsF0Q,EAtF1Q,EAsF8Q,EAtF9Q,EAsFkR,EAtFlR,EAsFsR,EAtFtR,EAsF0R,EAtF1R,EAsF8R,EAtF9R,EAsFkS,EAtFlS,EAsFsS,EAtFtS,EAsF0S,EAtF1S,EAsF8S,EAtF9S,EAsFkT,EAtFlT,EAsFsT,EAtFtT,EAsF0T,EAtF1T,EAsF8T,EAtF9T,EAsFkU,EAtFlU,EAsFsU,EAtFtU,EAsF0U,EAtF1U,EAsF8U,EAtF9U,EAsFkV,EAtFlV,EAsFsV,EAtFtV,EAsF0V,EAtF1V,EAsF8V,EAtF9V,EAsFkW,EAtFlW,EAsFsW,EAtFtW,EAsF0W,EAtF1W,EAsF8W,EAtF9W,EAsFkX,EAtFlX,EAsFsX,EAtFtX,EAsF0X,EAtF1X,EAsF8X,EAtF9X,EAsFkY,EAtFlY,EAsFsY,EAtFtY,EAsF0Y,EAtF1Y,EAsF8Y,EAtF9Y,EAsFkZ,EAtFlZ,EAsFsZ,EAtFtZ,EAsF0Z,EAtF1Z,EAsF8Z,EAtF9Z,EAsFkaA,EAtFla,EAsFsaA,EAtFta,EAsF0aA,EAtF1a,EAsF8aA,EAtF9a,EAsFkbA,EAtFlb,EAsFsbA,EAtFtb,EAsF0bA,EAtF1b,EAsF8bA,EAtF9b,EAsFkcA,EAtFlc,EAsFscA,EAtFtc,EAsF0cA,EAtF1c,EAsF8cA,EAtF9c,EAsFkdA,EAtFld,EAsFsdA,EAtFtd,EAsF0dA,EAtF1d,EAsF8dA,EAtF9d,EAsFkeA,EAtFle,EAsFseA,EAtFte,EAsF0eA,EAtF1e,EAsF8eA,EAtF9e,EAsFkfA,EAtFlf,EAsFsfA,EAtFtf,EAsF0fA,EAtF1f,EAsF8fA,EAtF9f,EAsFkgA,EAtFlg,EAsFsgA,EAtFtg,EAsF0gA,EAtF1g,EAsF8gA,EAtF9g,EAsFkhA,EAtFlh,EAsFshA,EAtFth,EAsF0hA,EAtF1h,EAsF8hA,EAtF9h,EAsFkiA,EAtFli,EAsFsiA,EAtFti,EAsF0iA,EAtF1i,EAsF8iA,EAtF9i,EAsFkjA,EAtFlj,EAsFsjA,EAtFtj,EAsF0jA,EAtF1j,EAsF8jA,EAtF9j,EAsFkkA,EAtFlk,EAsFskA,EAtFtk,EAsF0kA,EAtF1k,EAsF8kA,EAtF9k,EAsFklA,EAtFll,EAsFslA,EAtFtl,EAsF0lA,EAtF1l,EAsF8lA,EAtF9l,EAsFkmA,EAtFlm,EAsFsmA,EAtFtm,EAsF0mA,EAtF1m,EAsF8mA,EAtF9m,EAsFknA,EAtFln,EAsFsnA,EAtFtn,EAsF0nA,EAtF1n,EAsF8nA,EAtF9n,EAsFkoA,EAtFlo,EAsFsoA,EAtFto,EAsF0oA,EAtF1o,EAsF8oA,EAtF9o,EAsFkpA,EAtFlp,EAsFspA,EAtFtp,EAsF0pA,EAtF1p,EAsF8pA,EAtF9p,EAsFkqA,EAtFlq,EAsFsqA,EAtFtq,EAsF0qA,EAtF1q,EAsF8qA,EAtF9q,EAsFkrA,EAtFlr,EAsFsrA,EAtFtr,EAsF0rA,EAtF1r,EAsF8rA,EAtF9r,EAsFksA,EAtFls,EAsFssA,EAtFts,EAsF0sA,EAtF1s,EAsF8sA,EAtF9s,EAsFktA,EAtFlt,EAsFstA,EAtFtt,EAsF0tA,EAtF1t,EAsF8tA,EAtF9t,EAsFkuA,EAtFlu,EAsFsuA,EAtFtu,EAsF0uA,EAtF1u,EAsF8uA,EAtF9u,EAsFkvA,EAtFlv,EAsFsvA,EAtFtv,EAsF0vA,EAtF1v,EAsF8vA,EAtF9v,EAsFkwA,EAtFlw,EAsFswA,EAtFtw,EAsF0wA,EAtF1w,EAsF8wA,EAtF9w,EAsFkxA,EAtFlx,EAsFsxA,EAtFtx,EAsF0xA,EAtF1x,EAsF8xA,EAtF9x,EAsFkyA,EAtFly,EAsFsyA,EAtFty,EAsF0yA,EAtF1y,EAsF8yA,EAtF9y,EAsFkzA,EAtFlz,EAsFszA,EAtFtz,EAsF0zA,EAtF1z,EAsF8zA,EAtF9z,EAsFk0A,EAtFl0,EAsFs0A,EAtFt0,EAsF00A,EAtF10,EAsF80A,EAtF90,EAsFk1A,EAtFl1,EAsFs1A,EAtFt1,EAsF01A,EAtF11,EAsF81A,EAtF91,EAsFk2A,EAtFl2,EAsFs2A,EAtFt2,EAsF02A,EAtF12,EAsF82A,EAtF92,EAsFk3A,EAtFl3,EAsFs3A,EAtFt3,EAsF03A,EAtF13,EAsF83A,EAtF93,EAsFk4A,EAtFl4,EAsFs4A,EAtFt4,EAsF04A,EAtF14,EAsF84A,EAtF94,EAsFk5A,EAtFl5,EAsFs5A,EAtFt5,EAsF05A,EAtF15,EAsF85A,EAtF95,EAsFk6A,EAtFl6,EAsFs6A,EAtFt6,EAsF06A,EAtF16,EAsF86A,EAtF96,EAsFk7A,EAtFl7,EAsFs7A,EAtFt7,EAsF07A,EAtF17,EAsF87A,EAtF97,EAsFk8A,EAtFl8,EAsFs8A,EAtFt8,EAsF08A,EAtF18,EAsF88A,EAtF98,EAsFk9A,EAtFl9,EAsFs9A,EAtFt9,EAsF09A,EAtF19,EAsF89A,EAtF99,EAsFk+A,EAtFl+,EAsFs+A,EAtFt+,EAsF0+A,EAtF1+,EAsF8+A,EAtF9+,EAsFkgA,EAtFlgB,EAsFshA,EAtFthB,EAsF0iA,EAtF1iB,EAsF8jA,EAtF9jB,EAsFkkA,EAtFlkB,EAsFslA,EAtFtlB,EAsF0mA,EAtF1mB,EAsF8nA,EAtF9nB,EAsFkoA,EAtFloB,EAsFspA,EAtFtpB,EAsF0qA,EAtF1qB,EAsF8rA,EAtF9rB,EAsFksA,EAtFlsB,EAsFstA,EAtFttB,EAsF0uA,EAtF1uB,EAsF8vA,EAtF9vB,EAsFkwA,EAtFlwB,EAsFsxA,EAtFtxB,EAsF0yA,EAtF1yB,EAsF8zA,EAtF9zB,EAsFk0A,EAtFl0B,EAsFs1A,EAtFt1B,EAsF02A,EAtF12B,EAsF83A,EAtF93B,EAsFk4A,EAtFl4B,EAsFs5A,EAtFt5B,EAsF06A,EAtF16B,EAsF87A,EAtF97B,EAsFk8A,EAtFl8B,EAsFs9A,EAtFt9B,EAsF0+A,EAtF1+B,EAsF8gA,EAtF9gB,EAsFkiA,EAtFliB,EAsFsjA,EAtFtjB,EAsF0kA,EAtF1kB,EAsF8lA,EAtF9lB,EAsFknA,EAtFlnB,EAsFspA,EAtFtpB,EAsF0qA,EAtF1qB,EAsF8rA,EAtF9rB,EAsFktA,EAtFltB,EAsFsuA,EAtFtuB,EAsF0vA,EAtF1vB,EAsF8wA,EAtF9wB,EAsFkyA,EAtFlyB,EAsFszA,EAtFtzB,EAsF00A,EAtF10B,EAsF82A,EAtF92B,EAsFk4A,EAtFl4B,EAsFs5A,EAtFt5B,EAsF06A,EAtF16B,EAsF88A,EAtF98B,EAsFk+A,EAtFl+B,EAsFsgA,EAtFtg

AAyB,YAAzB,IAAyC4nB,SAAS,KAAKriB,SAA3D,EAAsE;AACpE;AACAuK,MAAAA,OAAO,CAACC,IAAR,
6HAC2HnQ,gBAAgB,CACvImmB,SADuI,CAD3I;AAKD;;AAED,wBAAO,oBAAC,SAAD,eAAeI,KAAf;AAAs
B,MAAA,KAAK,EAAEmK,SAA7B;AAAwC,MAAA,GAAG,EAAErC;AAA7C,OAAP;AACD,GAhBiB;CAAlB;
AAkBAsC,EAAAA,KAAY,CAACF,SAAD,EAAY5B,SAAZ,CAAAA;AAEA4B,SAAO,CAAC1nB,B,WAAV
,kBAAqCL,gBAAgB,CAACmmB,SAAD,CAArD;AAEA,SAAO4O4B,SAAP;;ACdA;AACA;AAGA,
IAAMG,QAAQ,GAAG,SAAXA,QAAW,GAAM;AAAA,oBAAgBC,cAAU,CAACC,iBAAD,CAA1B;AAAA,MAAOC,
KAAP,eAAOA,KAAP;;AAAA,MAAcC,QAAd,eAAcA,QAAd;;AAAA,MAAwBC,QAAxB,eAAwBA,QAAxB;;AAAA,MAAkCC,
QAAlC,eAAkCA,QAAlC;;AAAA,MAA4CC,QAA5C,eAA4CA,QAA5C;;AAAA,MAAsDC,QAAtD,eAAsDA,QAAtD;;AAAA,MAAgEC,
QAAhE,eAAgEA,QAAhE;;AAAA,MAA0EC,QAA1E,eAA0EA,QAA1E;;AAAA,MAAoFC,QAApF,eAAoFA,QAApF;;AAAA,MAA8FC,
QAA9F,eAA8FA,QAA9F;;AAAA,MAAwGC,QAAxG,eAAwGA,QAAxG;;AAAA,MAAkHC,QAAlH,eAAkHA,QAAlH;;AAAA,MAA4HC,
QAA5H,eAA4HA,QAA5H;;AAAA,MAAsIC,QAAtI,eAAsIA,QAAtI;;AAAA,MAAgJC,QAAhJ,eAAgJA,QAAhJ;;AAAA,MAA0JC,
QAA1J,eAA0JA,QAA1J;;AAAA,MAAoKC,QAApK,eAAoKA,QAApK;;AAAA,MAA8KC,QAA9K,eAA8KA,QAA9K;;AAAA,MAAwLC,
QAAxL,eAAwLA,QAAxL;;AAAA,MAAkMC,QAAlM,eAAkMA,QAAlM;;AAAA,MAA4MC,QAA5M,eAA4MA,QAA5M;;AAAA,MAAsNC,
QAAtN,eAAsNA,QAAtN;;AAAA,MAAgOC,QAAhO,eAAgOA,QAAhO;;AAAA,MAA0OC,QAA1O,eAA0OA,QAA1O;;AAAA,MAAoPC,
QAApP,eAAoPA,QAApP;;AAAA,MAA8PC,QAA9P,eAA8PA,QAA9P;;AAAA,MAAwQC,QAAxQ,eAAwQA,QAAxQ;;AAAA,MAAkRC,
QAAlR,eAAkRA,QAAlR;;AAAA,MAA4RC,QAA5R,eAA4RA,QAA5R;;AAAA,MAAsSC,QAAtS,eAAsSA,QAAtS;;AAAA,MAAgTC,
QAAhT,eAAgTA,QAAhT;;AAAA,MAA0TC,QAA1T,eAA0TA,QAA1T;;AAAA,MAAoUC,QAApU,eAAoUA,QAApU;;AAAA,MAA8UC,
QAA9U,eAA8UA,QAA9U;;AAAA,MAAwVC,QAAxV,eAAwVA,QAAxV;;AAAA,MAAkWC,QAAlW,eAAkWA,QAAlW;;AAAA,MAA4WC,
QAA5W,eAA4WA,QAA5W;;AAAA,MAAsXC,QAAtX,eAAsXA,QAAtX;;AAAA,MAAgYC,QAAhY,eAAgYA,QAAhY;;AAAA,MAA0YC,
QAA1Y,eAA0YA,QAA1Y;;AAAA,MAAoZC,QAApZ,eAAoZA,QAApZ;;AAAA,MAA8ZC,QAA9Z,eAA8ZA,QAA9Z;;AAAA,MAAwaC,
QAAxa,eAAwaA,QAAxa;;AAAA,MAAkbC,QAAlb,eAAkbA,QAAlb;;AAAA,MAA4bC,QAA5b,eAA4bA,QAA5b;;AAAA,MAAscC,
QAAtc,eAAscA,QAAtc;;AAAA,MAAgdC,QAAhd,eAAgdA,QAAhd;;AAAA,MAA0dC,QAA1d,eAA0dA,QAA1d;;AAAA,MAAoeC,
QAApe,eAAoeA,QAApe;;AAAA,MAA8eC,QAA9e,eAA8eA,QAA9e;;AAAA,MAAwfC,QAAxf,eAAwfA,QAAxf;;AAAA,MAAkgBC,
QAAlgB,eAAkgBA,QAAlgB;;AAAA,MAA4gBC,QAA5gB,eAA4gBA,QAA5gB;;AAAA,MAAshBC,QAAthB,eAAshBA,QAAthB;;AAAA,MAAgiBC,
QAAhiB,eAAgiBA,QAAhiB;;AAAA,MAA0iBC,QAA1iB,eAA0iBA,QAA1iB;;AAAA,MAAojBC,QAApjB,eAAojBA,QAApjB;;AAAA,MAA8jBC,
QAA9jB,eAA8jBA,QAA9jB;;AAAA,MAAwkBC,QAAxkB,eAAwkBA,QAAxkB;;AAAA,MAAklBC,QAAllB,eAAklBA,QAAllB;;AAAA,MAA4lBC,
QAA5lB,eAA4lBA,QAA5lB;;AAAA,MAAsmBC,QAAtmB,eAAsmBA,QAAtmB;;AAAA,MAAgnBC,QAAhnB,eAAgnBA,QAAhnB;;AAAA,MAA0nBC,
QAA1nB,eAA0nBA,QAA1nB;;AAAA,MAAooBC,QAApoB,eAAooBA,QAApoB;;AAAA,MAA8oBC,QAA9oB,eAA8oBA,QAA9oB;;AAAA,MAAwpBC,
QAAxpB,eAAwpBA,QAAxpB;;AAAA,MAAkqBC,QAAlqB,eAAkqBA,QAAlqB;;AAAA,MAA4qBC,QAA5qB,eAA4qBA,QAA5qB;;AAAA,MAAsrBC,
QAAtrB,eAAsrBA,QAAtrB;;AAAA,MAAgsBC,QAAhsB,eAAgsBA,QAAhsB;;AAAA,MAA0sBC,QAA1sB,eAA0sBA,QAA1sB;;AAAA,MAAotBC,
QAAptB,eAAotBA,QAAptB;;AAAA,MAA8tBC,QAA9tB,eAA8tBA,QAA9tB;;AAAA,MAAwuBC,QAAxuB,eAAwuBA,QAAxuB;;AAAA,MAAkvBC,
QAAlvB,eAAkvBA,QAAlvB;;AAAA,MAA4vBC,QAA5vB,eAA4vBA,QAA5vB;;AAAA,MAAswBC,QAAtwB,eAAswBA,QAAtwB;;AAAA,MAAgxBC,
QAAhxB,eAAgxBA,QAAhxB;;AAAA,MAA0xBC,QAA1xB,eAA0xBA,QAA1xB;;AAAA,MAAoyBC,QAApyB,eAAoyBA,QAApyB;;AAAA,MAA8yBC,
QAA9yB,eAA8yBA,QAA9yB;;AAAA,MAAwzBC,QAAxzB,eAAwzBA,QAAxzB;;AAAA,MAAk0BC,QAAl0B,eAAk0BA,QAAl0B;;AAAA,MAA40BC,
QAA50B,eAA40BA,QAA50B;;AAAA,MAAs1BC,QAAt1B,eAAs1BA,QAAt1B;;AAAA,MAAg2BC,QAAh2B,eAAg2BA,QAAh2B;;AAAA,MAA02BC,
QAA12B,eAA02BA,QAA12B;;AAAA,MAAo3BC,QAAp3B,eAAo3BA,QAAp3B;;AAAA,MAA83BC,QAA93B,eAA83BA,QAA93B;;AAAA,MAAw4BC,
QAAx4B,eAAw4BA,QAAx4B;;AAAA,MAAk5BC,QAAl5B,eAAk5BA,QAAl5B;;AAAA,MAA45BC,QAA55B,eAA45BA,QAA55B;;AAAA,MAAs6BC,
QAAt6B,eAAs6BA,QAAt6B;;AAAA,MAAg7BC,QAAh7B,eAAg7BA,QAAh7B;;AAAA,MAA07BC,QAA17B,eAA07BA,QAA17B;;AAAA,MAAo8BC,
QAAp8B,eAAo8BA,QAAp8B;;AAAA,MAA88BC,QAA98B,eAA88BA,QAA98B;;AAAA,MAAw9BC,QAAx9B,eAAw9BA,QAAx9B;;AAAA,MAAk+BC,
QAAl+B,eAAk+BA,QAAl+B;;AAAA,MAA4+BC,QAA5+B,eAA4+BA,QAA5+B;;AAAA,MAAs/BC,QAAt/B,eAAs/BA,QAAt/B;;AAAA,MAAggCC,
QAAhgC,eAAggCA,QAAhgC;;AAAA,MAA0gCC,QAA1gC,eAA0gCA,QAA1gC;;AAAA,MAAohCC,QAAphC,eAAohCA,QAAphC;;AAAA,MAA8hCC,
QAA9hC,eAA8hCA,QAA9hC;;AAAA,MAAwiCC,QAAxiC,eAAwiCA,QAAxiC;;AAAA,MAAkjCC,QAAljC,eAAkjCA,QAAljC;;AAAA,MAA4jCC,
QAA5jC,eAA4jCA,QAA5jC;;AAAA,MAAskCC,QAAtkC,eAAskCA,QAAtkC;;AAAA,MAAglCC,QAAhlC,eAAglCA,QAAhlC;;AAAA,MAA0lCC,
QAA1lC,eAA0lCA,QAA1lC;;AAAA,MAAomCC,QAApmC,eAAomCA,QAApmC;;AAAA,MAA8mCC,QAA9mC,eAA8mCA,QAA9mC;;AAAA,MAAwnCC,
QAAxnC,eAAwnCA,QAAxnC;;AAAA,MAAkoCC,QAAloC,eAAkoCA,QAAloC;;AAAA,MAA4oCC,QAA5oC,eAA4oCA,QAA5oC;;AAAA,MAAspCC,
QAAtpC,eAAspCA,QAAtpC;;AAAA,MAAgqCC,QAAhqC,eAAgqCA,QAAhqC;;AAAA,MAA0qCC,QAA1qC,eAA0qCA,QAA1qC;;AAAA,MAAorCC,
QAAprC,eAAorCA,QAAprC;;AAAA,MAA8rCC,QAA9rC,eAA8rCA,QAA9rC;;AAAA,MAAwsCC,QAAxsC,eAAwsCA,QAAxsC;;AAAA,MAAktCC,
QAAltC,eAAktCA,QAAltC;;AAAA,MAA4tCC,QAA5tC,eAA4tCA,QAA5tC;;AAAA,MAAsuCC,QAAtuC,eAAsuCA,QAAtuC;;AAAA,MAAgvCC,
QAAhvC,eAAgvCA,QAAhvC;;AAAA,MAA0vCC,QAA1vC,eAA0vCA,QAA1vC;;AAAA,MAAowCC,QAApwC,eAAowCA,QAApwC;;AAAA,MAA8wCC,
QAA9wC,eAA8wCA,QAA9wC;;AAAA,MAAwxCC,QAAxxC,eAAwxCA,QAAxxC;;AAAA,MAAkyCC,QAAlyC,eAAkyCA,QAAlyC;;AAAA,MAA4yCC,
QAA5yC,eAA4yCA,QAA5yC;;AAAA,MAAszCC,QAAtzC,eAAszCA,QAAtzC;;AAAA,MAAg0CC,QAAh0C,eAAg0CA,QAAh0C;;AAAA,MAA00CC,
QAA10C,eAA00CA,QAA10C;;AAAA,MAAo1CC,QAAp1C,eAAo1CA,QAAp1C;;AAAA,MAA81CC,QAA91C,eAA81CA,QAA91C;;AAAA,MAAw2CC,
QAAx2C,eAAw2CA,QAAx2C;;AAAA,MAAk3CC,QAAl3C,eAAk3CA,QAAl3C;;AAAA,MAA43CC,QAA53C,eAA43CA,QAA53C;;AAAA,MAAs4CC,
QAAt4C,eAAs4CA,QAAt4C;;AAAA,MAAg5CC,QAAh5C,eAAg5CA,QAAh5C;;AAAA,MAA05CC,QAA15C,eAA05CA,QAA15C;;AAAA,MAAo6CC,
QAAp6C,eAAo6CA,QAAp6C;;AAAA,MAA86CC,QAA96C,eAA86CA,QAA96C;;AAAA,MAAw7CC,QAAx7C,eAAw7CA,QAAx7C;;AAAA,MAAk8CC,
QAAl8C,eAAk8CA,QAAl8C;;AAAA,MAA48CC,QAA58C,eAA48CA,QAA58C;;AAAA,MAAs9CC,QAAt9C,eAAs9CA,QAAt9C;;AAAA,MAAg+CC,
QAAh+C,eAAg+CA,QAAh+C;;AAAA,MAA0+CC,QAA1+C,eAA0+CA,QAA1+C;;AAAA,MAAo/CC,QAAp/C,eAAo/CA,QAAp/C;;AAAA,MAA8/CC,
QAA9/C,eAA8/CA,QAA9/C;;AAAA,MAAwgDC,QAAxgD,eAAwgDA,QAAxgD;;AAAA,MAAkhDC,QAAlhD,eAAkhDA,QAAlhD;;AAAA,MAA4hDC,
QAA5hD,eAA4hDA,QAA5hD;;AAAA,MAAsiDC,QAAtiD,eAAsiDA,QAAtiD;;AAAA,MAAgjDC,QAAhjD,eAAgjDA,QAAhjD;;AAAA,MAA0jDC,
QAA1jD,eAA0jDA,QAA1jD;;AAAA,MAAokDC,QAApkD,eAAokDA,QAApkD;;AAAA,MAA8kDC,QAA9kD,eAA8kDA,QAA9kD;;AAAA,MAAwlDC,
QAAxlD,eAAwlDA,QAAxlD;;AAAA,MAAkmDC,QAAlmD,eAAkmDA,QAAlmD;;AAAA,MAA4mDC,QAA5mD,eAA4mDA,QAA5mD;;AAAA,MAAsnDC,
QAAtnD,eAAsnDA,QAAtnD;;AAAA,MAAgoDC,QAAhoD,eAAgoDA,QAAhoD;;AAAA,MAA0oDC,QAA1oD,eAA0oDA,QAA1oD;;AAAA,MAAopDC,
QAAppD,eAAopDA,QAAppD;;AAAA,MAA8pDC,QAA9pD,eAA8pDA,QAA9pD;;AAAA,MAAwqDC,QAAxqD,eAAwqDA,QAAxqD;;AAAA,MAAkrDC,
QAAlrD,eAAkrDA,QAAlrD;;AAAA,MAA4rDC,QAA5rD,eAA4rDA,QAA5rD;;AAAA,MAAssDC,QAAtsD,eAAssDA,QAAtsD;;AAAA,MAAgtDC,
QAAhtD,eAAgtDA,QAAhtD;;AAAA,MAA0tDC,QAA1tD,eAA0tDA,QAA1tD;;AAAA,MAAouDC,QAApuD,eAAouDA,QAApuD;;AAAA,MAA8uDC,
QAA9uD,eAA8uDA,QAA9uD;;AAAA,MAAwvDC,QAAxvD,eAAwvDA,QAAxvD;;AAAA,MAAkwDC,QAAlwD,eAAkwDA,QAAlwD;;AAAA,MAA4wDC,
QAA5wD,eAA4wDA,QAA5wD;;AAAA,MAAsxDC,QAAtxD,eAAsxDA,QAAtxD;;AAAA,MAAgyDC,QAAhyD,eAAgyDA,QAAhyD;;AAAA,MAA0yDC,
QAA1yD,eAA0yDA,QAA1yD;;AAAA,MAAozDC,QAApzD,eAAozDA,QAApzD;;AAAA,MA8zDC,QAA9zD,eA8zDA,QA9zD;;AAAA,MA+zDC,QA/zD,eA+zDA,QA/zD;;AAAA,MAg0DC,QAh0D,eAg0DA,QAh0D;;AAAA,MAi0DC,QAj0D,eAi0DA,QAj0D;;AAAA,MAk0DC,QAl0D,eAk0DA,QAl0D;;AAAA,MAm0DC,QAn0D,eAm0DA,QAn0D;;AAAA,MAo0DC,QAp0D,eAo0DA,QAp0D;;AAAA,MAq0DC,QAr0D,eAq0DA,QAr0D;;AAAA,MAs0DC,QAt0D,eAs0DA,QAt0D;;AAAA,MAu0DC,QAv0D,eAu0DA,QAv0D;;AAAA,MAw0DC,QAx0D,eAw0DA,QAx0D;;AAAA,MAy0DC,QAz0D,eAy0DA,QAz0D;;AAAA,MA00DC,QA10D,eA00DA,QA10D;;AAAA,MA20DC,QA30D,eA20DA,QA30D;;AAAA,MA40DC,QA50D,eA40DA,QA50D;;AAAA,MA60DC,QA70D,eA60DA,QA70D;;AAAA,MA80DC,QA90D,eA80DA,QA90D;;AAAA,MA+0DC,QA/0D,eA+0DA,QA/0D;;AAAA,MAg1DC,QAh1D,eAg1DA,QAh1D;;AAAA,MAi1DC,QAj1D,eAi1DA,QAj1D;;AAAA,MAk1DC,QAl1D,eAk1DA,QAl1D;;AAAA,MAm1DC,QAn1D,eAm1DA,QAn1D;;AAAA,MAo1DC,QAp1D,eAo1DA,QAp1D;;AAAA,MAq1DC,QAr1D,eAq1DA,QAr1D;;AAAA,MAs1DC,QAt1D,eAs1DA,QAt1D;;AAAA,MAu1DC,QAv1D,eAu1DA,QAv1D;;AAAA,MAw1DC,QAx1D,eAw1DA,QAx1D;;AAAA,MAy1DC,QAz1D,eAy1DA,QAz1D;;AAAA,MA01DC,QA11D,eA01DA,QA11D;;AAAA,MA21DC,QA31D,eA21DA,QA31D;;AAAA,MA41DC,QA51D,eA41DA,QA51D;;AAAA,MA61DC,QA71D,eA61DA,QA71D;;AAAA,MA81DC,QA91D,eA81DA,QA91D;;AAAA,MA+1DC,QA/1D,eA+1DA,QA/1D;;AAAA,MAg2DC,QAh2D,eAg2DA,QAh2D;;AAAA,MAi2DC,QAj2D,eAi2DA,QAj2D;;AAAA,MAk2DC,QAl2D,eAk2DA,QAl2D;;AAAA,MAm2DC,QAn2D,eAm2DA,QAn2D;;AAAA,MAo2DC,QAp2D,eAo2DA,QAp2D;;AAAA,MAq2DC,QAr2D,eAq2DA,QAr2D;;AAAA,MAs2DC,QAt2D,eAs2DA,QAt2D;;AAAA,MAu2DC,QAv2D,eAu2DA,QAv2D;;AAAA,MAw2DC,QAx2D,eAw2DA,QAx2D;;AAAA,MAy2DC,QAz2D,eAy2DA,QAz2D;;AAAA,MA02DC,QA12D,eA02DA,QA12D;;AAAA,MA22DC,QA32D,eA22DA,QA32D;;AAAA,MA42DC,QA52D,eA42DA,QA52D;;AAAA,MA62DC,QA72D,eA62DA,QA72D;;AAAA,MA82DC,QA92D,eA82DA,QA92D;;AAAA,MA+2DC,QA/2D,eA+2DA,QA/2D;;AAAA,MAg3DC,QAh3D,eAg3DA,QAh3D;;AAAA,MAi3DC,QAj3D,eAi3DA,QAj3D;;AAAA,MAk3DC,QAl3D,eAk3DA,QAl3D;;AAAA,MAm3DC,QAn3D,eAm3DA,QAn3D;;AAAA,MAo3DC,QAp3D,eAo3DA,QAp3D;;AAAA,MAq3DC,QAr3D,eAq3DA,QAr3D;;AAAA,MAs3DC,QAt3D,eAs3DA,QAt3D;;AAAA,MAu3DC,QAv3D,eAu3DA,QAv3D;;AAAA,MAw3DC,QAx3D,eAw3DA,QAx3D;;AAAA,MAy3DC,QAz3D,eAy3DA,QAz3D;;AAAA,MA03DC,QA13D,eA03DA,QA13D;;AAAA,MA23DC,QA33D,eA23DA,QA33D;;AAAA,MA43DC,QA53D,eA43DA,QA53D;;AAAA,MA63DC,QA73D,eA63DA,QA73D;;AAAA,MA83DC,QA93D,eA83DA,QA93D;;AAAA,MA+3DC,QA/3D,eA+3DA,QA/3D;;AAAA,MAg4DC,QAh4D,eAg4DA,QAh4D;;AAAA,MAi4DC,QAj4D,eAi4DA,QAj4D;;AAAA,MAk4DC,QAl4D,eAk4DA,QAl4D;;AAAA,MAm4DC,QAn4D,eAm4DA,QAn4D;;AAAA,MAo4DC,QAp4D,eAo4DA,QAp4D;;AAAA,MAq4DC,QAr4D,eAq4DA,QAr4D;;AAAA,MAs4DC,QAt4D,eAs4DA,QAt4D;;AAAA,MAu4DC,QAv4D,eAu4DA,QAv4D;;AAAA,MAw4DC,QAx4D,eAw4DA,QAx4D;;AAAA,MAy4DC,QAz4D,eAy4DA,QAz4D;;AAAA,MA04DC,QA14D,eA04DA,QA14D;;AAAA,MA24DC,QA34D,eA24DA,QA34D;;AAAA,MA44DC,QA54D,eA44DA,QA54D;;AAAA,MA64DC,QA74D,eA64DA,QA74D;;AAAA,MA84DC,QA94D,eA84DA,QA94D;;AAAA,MA+4DC,QA/4D,eA+4DA,QA/4D;;AAAA,MAg5DC,QAh5D,eAg5DA,QAh5D;;AAAA,MAi5DC,QAj5D,eAi5DA,QAj5D;;AAAA,MAk5DC,QAl5D,eAk5DA,QAl5D;;AAAA,MAm5DC,QAn5D,eAm5DA,QAn5D;;AAAA,MAo5DC,QAp5D,eAo5DA,QAp5D;;AAAA,MAq5DC,QAr5D,eAq5DA,QAr5D;;AAAA,MAs5DC,QAt5D,eAs5DA,QAt5D;;AAAA,MAu5DC,QAv5D,eAu5DA,QAv5D;;AAAA,MAw5DC,QAx5D,eAw5DA,QAx5D;;AAAA,MAy5DC,QAz5D,eAy5DA,QAz5D;;AAAA,MA05DC,QA15D,eA05DA,QA15D;;AAAA,MA25DC,QA35D,eA25DA,QA35D;;AAAA,MA45DC,QA55D,eA45DA,QA55D;;AAAA,MA65DC,QA75D,eA65DA,QA75D;;AAAA,MA85DC,QA95D,eA85DA,QA95D;;AAAA,MA+5DC,QA/5D,eA+5DA,QA/5D;;AAAA,MAg6DC,QAh6D,eAg6DA,QAh6D;;AAAA,MAi6DC,QAj6D,eAi6DA,QAj6D;;AAAA,MAk6DC,QAl6D,eAk6DA,QAl6D;;AAAA,MAm6DC,QAn6D,eAm6DA,QAn6D;;AAAA,MAo6DC,QAp6D,eAo6DA,QAp6D;;AAAA,MAq6DC,QAr6D,eAq6DA,QAr6D;;AAAA,MAs6DC,QAt6D,eAs6DA,QAt6D;;AAAA,MAu6DC,QAv6D,eAu6DA,QAv6D;;AAAA,MAw6DC,QAx6D,eAw6DA,QAx6D;;AAAA,MAy6DC,QAz6D,eAy6DA,QAz6D;;AAAA,MA06DC,QA16D,eA06DA,QA16D;;AAAA,MA26DC,QA36D,eA26DA,QA36D;;AAAA,MA46DC,QA56D,eA46DA,QA56D;;AAAA,MA66DC,QA76D,eA66DA,QA76D;;AAAA,MA86DC,QA96D,eA86DA,QA96D;;AAAA,MA+6DC,QA/6D,eA+6DA,QA/6D;;AAAA,MAg7DC,QAh7D,eAg7DA,QAh7D;;AAAA,MAi7DC,QAj7D,eAi7DA,QAj7D;;AAAA,MAk7DC,QAl7D,eAk7DA,QAl7D;;AAAA,MAm7DC,QAn7D,eAm7DA,QAn7D;;AAAA,MAo7DC,QAp7D,eAo7DA,QAp7D;;AAAA,MAq7DC,QAr7D,eAq7DA,QAr7D;;AAAA,MAs7DC,QAt7D,eAs7DA,QAt7D;;AAAA,MAu7DC,QAv7D,eAu7DA,QAv7D;;AAAA,MAw7DC,QAx7D,eAw7DA,QAx7D;;AAAA,MAy7DC,QAz7D,eAy7DA,QAz7D;;AAAA,MA07DC,QA17D,eA07DA,QA17D;;AAAA,MA27DC,QA37D,eA27DA,QA37D;;AAAA,MA47DC,QA57D,eA47DA,QA57D;;AAAA,MA67DC,QA77D,eA67DA,QA77D;;AAAA,MA87DC,QA97D,eA87DA,QA97D;;AAAA,MA+7DC,QA/7D,eA+7DA,QA/7D;;AAAA,MAg8DC,QAh8D,eAg8DA,QAh8D;;AAAA,MAi8DC,QAj8D,eAi8DA,QAj8D;;AAAA,MAk8DC,QAl8D,eAk8DA,QAl8D;;AAAA,MAm8DC,QAn8D,eAm8DA,QAn8D;;AAAA,MAo8DC,QAp8D,eAo8DA,QAp8D;;AAAA,MAq8DC,QAr8D,eAq8DA,QAr8D;;AAAA,MAs8DC,QAt8D,eAs8DA,QAt8D;;AAAA,MAu8DC,QAv8D,eAu8DA,QAv8D;;AAAA,MAw8DC,QAx8D,eAw8DA,QAx8D;;AAAA,MAy8DC,QAz8D,eAy8DA,QAz8D;;AAAA,MA08DC,QA18D,eA08DA,QA18D;;AAAA,MA28DC,QA38D,eA28DA,QA38D;;AAAA,MA48DC,QA58D,eA48DA,QA58D;;AAAA,MA68DC,QA78D,eA68DA,QA78D;;AAAA,MA88DC,QA98D,eA88DA,QA98D;;AAAA,MA+8DC,QA/8D,eA+8DA,QA/8D;;AAAA,MAg9DC,QAh9D,eAg9DA,QAh9D;;AAAA,MAi9DC,QAj9D,eAi9DA,QAj9D;;AAAA,MAk9DC,QAl9D,eAk9DA,QAl9D;;AAAA,MAm9DC,QAn9D,eAm9DA,QAn9D;;AAAA,MAo9DC,QAp9D,eAo9DA,QAp9D;;AAAA,MAq9DC,QAr9D,eAq9DA,QAr9D;;AAAA,MAs9DC,QAt9D,eAs9DA,QAt9D;;AAAA,MAu9DC,QAv9D,eAu9DA,QAv9D;;AAAA,MAw9DC,QAx9D,eAw9DA,QAx9D;;AAAA,MAy9DC,QAz9D,eAy9DA,QAz9D;;AAAA,MA09DC,QA19D,eA09DA,QA19D;;AAAA,MA29DC,QA39D,eA29DA,QA39D;;AAAA,MA49DC,QA59D,eA49DA,QA59D;;AAAA,MA69DC,QA79D,eA69DA,QA79D;;AAAA,MA89DC,QA99D,eA89DA,QA99D;;AAAA,MA+9DC,QA/9D,eA+9DA,QA/9D;;AAAA,MAg+DC,QAh+D,eAg+DA,QAh+D;;AAAA,MAi+DC,QAj+D,eAi+DA,QAj+D;;AAAA,MAk+DC,QAl+D,eAk+DA,QAl+D;;AAAA,MAm+DC,QAn+D,eAm+DA,QAn+D;;AAAA,MAo+DC,QAp+D,eAo+DA,QAp+D;;AAAA,MAq+DC,QAr+D,eAq+DA,QAr+D;;AAAA,MAs+DC,QAt+D,eAs+DA,QAt+D;;AAAA,MAu+DC,QAv+D,eAu+DA,QAv+D;;AAAA,MAw+DC,QAx+D,eAw+DA,QAx+D;;AAAA,MAy+DC,QAz+D,eAy+DA,QAz+D;;AAAA,MA0+DC,QA1+D,eA0+DA,QA1+D;;AAAA,MA2+DC,QA3+D,eA2+DA,QA3+D;;AAAA,MA4+DC,QA5+D,eA4+DA,QA5+D;;AAAA,MA6+DC,QA7+D,eA6+DA,QA7+D;;AAAA,MA8+DC,QA9+D,eA8+DA,QA9+D;;AAAA,MA++DC,QA/+D,eA++DA,QA/+D;;AAAA,MAg/DC,QAh/D,eAg/DA,QAh/D;;AAAA,MAi/DC,QAj/D,eAi/DA,QAj/D;;AAAA,MAk/DC,QAl/D,eAk/DA,QAl/D;;AAAA,MAm/DC,QAn/D,eAm/DA,QAn/D;;AAAA,MAo/DC,QAp/D,eAo/DA,QAp/D;;AAAA,MAq/DC,QAr/D,eAq/DA,QAr/D;;AAAA,MAs/DC,QAt/D,eAs/DA,QAt/D;;AAAA,MAu/DC,QAv/D,eAu/DA,QAv/D;;AAAA,MAw/DC,QAx/D,eAw/DA,QAx/D;;AAAA,MAy/DC,QAz/D,eAy/DA,QAz/D;;AAAA,MA0/DC,QA1/D,eA0/DA,QA1/D;;AAAA,MA2/DC,QA3/D,eA2/DA,QA3/D;;AAAA,MA4/DC,QA5/D,eA4/DA,QA5/D;;AAAA,MA6/DC,QA7/D,eA6/DA,QA7/D;;AAAA,MA8/DC,QA9/D,eA8/DA,QA9/D;;AAAA,MA+/DC,QA//D,eA+/DA,QA//D;;AAAA,MAggEC,QAhgE,eAggEA,QAhgE;;AAAA,MAigEC,QAjgE,eAigEA,QAjgE;;AAAA,MAkgEC,QAlgE,eAkgEA,QAlgE;;AAAA,MAmgEC,QAngE,eAmgEA,QAngE;;AAAA,MAogEC,QApgE,eAogEA,QApgE;;AAAA,MAqgEC,QArgE,eAqgEA,QArgE;;AAAA,MAsgEC,QAtgE,eAsgEA,QAtgE;;AAAA,MAugEC,QAvgE,eAugEA,QAvgE;;AAAA,MAwgEC,QAxgE,eAwgEA,QAxgE;;AAAA,MAygEC,QAzgE,eAygEA,QAzgE;;AAAA,MA0gEC,QA1gE,eA0gEA,QA1gE;;AAAA,MA2gEC,QA3gE,eA2gEA,QA3gE;;AAAA,MA4gEC,QA5gE,eA4gEA,QA5gE;;AAAA,MA6gEC,QA7gE,eA6gEA,QA7gE;;AAAA,MA8gEC,QA9gE,eA8gEA,QA9gE;;AAAA,MA+gEC,QA/gE,eA+gEA,QA/gE;;AAAA,MAghEC,QAhhE,eAghEA,QAhhE;;AAAA,MAihEC,QAjhE,eAihEA,QAjhE;;AAAA,MAkhEC,QAlhE,eAkhEA,QAlhE;;AAAA,MAmhEC,QAnhE,eAmhEA,QAnhE;;AAAA,MAohEC,QAphE,eAohEA,QAphE;;AAAA,MAqhEC,QArhE,eAqhEA,QArhE;;AAAA,MAshEC,QAthE,eAshEA,QAthE;;AAAA,MAuhEC,QAvhE,eAuhEA,QAvhE;;AAAA,MAwhEC,QAxhE,eAwhEA,QAxhE;;AAAA,MAyhEC,QAzhE,eAyhEA,QAzhE;;AAAA,MA0hEC,QA1hE,eA0hEA,QA1hE;;AAAA,MA2hEC,QA3hE,eA2hEA,QA3hE;;AAAA,MA4hEC,QA5hE,eA4hEA,QA5hE;;AAAA,MA6hEC,QA7hE,eA6hEA,QA7hE;;AAAA,MA8hEC,QA9hE,eA8hEA,QA9hE;;AAAA,MA+hEC,QA/hE,eA+hEA,QA/hE;;AAAA,MAgiEC,QAhiE,eAgiEA,QAhiE;;AAAA,MAiiEC,QAjiE,eAiiEA,QAjiE;;AAAA,MAkiEC,QAliE,eAkiEA,QAliE;;AAAA,MAmiEC,QAniE,eAmiEA,QAniE;;AAAA,MAoiEC,QApiE,eAoiEA,QApiE;;AAAA,MAqiEC,QAriE,eAqiEA,QAriE;;AAAA,MAsiEC,QAtiE,eAsiEA,QAtiE;;AAAA,MAuiEC,QAviE,eAuiEA,QAviE;;AAAA,MAwiEC,QAxiE,eAwiEA,QAxiE;;AAAA,MAyiEC,QAziE,eAyiEA,QAziE;;AAAA,MA0iEC,QA1iE,eA0iEA,QA1iE;;AAAA,MA2iEC,QA3iE,eA2iEA,QA3iE;;AAAA,MA4iEC,QA5iE,eA4iEA,QA5iE;;AAAA,MA6iEC,QA7iE,eA6iEA,QA7iE;;AAAA,MA8iEC,QA9iE,eA8iEA,QA9iE;;AAAA,MA+iEC,QA/iE,eA+iEA,QA/iE;;AAAA,MAgjEC,QAhjE,eAgjEA,QAhjE;;AAAA,MAijEC,QAjjE,eAijEA,QAjjE;;AAAA,MAkjEC,QAljE,eAkjEA,QAljE;;AAAA,MAmjEC,QAnjE,eAmjEA,QAnjE;;AAAA,MAojEC,QApjE,eAojEA,QApjE;;AAAA,MAqjEC,QArjE,eAqjEA,QArjE;;AAAA,MAsjEC,QAtjE,eAsjEA,QAtjE;;AAAA,MAujEC,QAvjE,eAujEA,QAvjE;;AAAA,MAwjEC,QAxjE,eAwjEA,QAxjE;;AAAA,MAyjEC,QAzjE,eAyjEA,QAzjE;;AAAA,MA0jEC,QA1jE,eA0jEA,QA1jE;;AAAA,MA2jEC,QA3jE,eA2jEA,QA3jE;;AAAA,MA4jEC,QA5jE,eA4jEA,QA5jE;;AAAA,MA6jEC,QA7jE,eA6jEA,QA7jE;;AAAA,MA8jEC,QA9jE,eA8jEA,QA9jE;;AAAA,MA+jEC,QA/jE,eA+jEA,QA/jE;;AAAA,MAgkEC,QAhkE,eAgkEA,QAhkE;;AAAA,MAikEC,QAjkE,eAikEA,QAjkE;;AAAA,MAkkEC,QAlkE,eAkkEA,QAlkE;;AAAA,MAmkEC,QAnkE,eAmkEA,QAnkE;;AAAA,MAokEC,QApkE,eAokEA,QApkE;;AAAA,MAqkEC,QArkE,eAqkEA,QArkE;;AAAA,MAskEC,QAtkE,eAskEA,QAtkE;;AAAA,MAukEC,QAvkE,eAukEA,QAvkE;;AAAA,MAwkEC,QAxkE,eAwkEA,QAxkE;;AAAA,MAykEC,QAzkE,eAykEA,QAzkE;;AAAA,MA0kEC,QA1kE,eA0kEA,QA1kE;;AAAA,MA2kEC,QA3kE,eA2kEA,QA3kE;;AAAA,MA4kEC,QA5kE,eA4kEA,QA5kE;;AAAA,MA6kEC,QA7kE,eA6kEA,QA7kE;;AAAA,MA8kEC,QA9kE,eA8kEA,QA9kE;;AAAA,MA+kEC,QA/kE,eA+kEA,QA/kE;;AAAA,MAglEC,QAhlE,eAglEA,QAhlE;;AAAA,MAilEC,QAjlE,eAilEA,QAjlE;;AAAA,MAklEC,QAllE,eAklEA,QAllE;;AAAA,MAmlEC,QAnlE,eAmlEA,QAnlE;;AAAA,MAolEC,QAplE,eAolEA,QAplE;;AAAA,MAqlEC,QArlE,eAqlEA,QArlE;;AAAA,MAslEC,QAtlE,eAslEA,QAtlE;;AAAA,MAulEC,QAvlE,eAulEA,QAvlE;;AAAA,MAwlEC,QAxlE,eAwlEA,QAxlE;;AAAA,MAylEC,QAzlE,eAylEA,QAzlE;;AAAA,MA0lEC,QA1lE,eA0lEA,QA1lE;;AAAA,MA2lEC,QA3lE,eA2lEA,QA3lE;;AAAA,MA4lEC,QA5lE,eA4lEA,QA5lE;;AAAA,MA6lEC,QA7lE,eA6lEA,QA7lE;;AAAA,MA8lEC,QA9lE,eA8lEA,QA9lE;;AAAA,MA+lEC,QA/lE,eA+lEA,QA/lE;;AAAA,MAgmEC,QAhmE,eAgmEA,QAhmE;;AAAA,MAimEC,QAjmE,eAimEA,QAjmE;;AAAA,MAkmEC,QAlmE,eAkmEA,QAlmE;;AAAA,MAmmEC,QAnmE,eAmmEA,QAnmE;;AAAA,MAomEC,QApmE,eAomEA,QApmE;;AAA

function isStyledComponent(target:
any): boolean %checks {\n return target && typeof target.styledComponentId === 'string';\n}\n","// @flow\n\ndeclare var SC_DISABLE_SPEEDY: ?boolean;\ndeclare var __VERSION__: string;\n\nexport const SC_ATTR: string =\n (typeof process !== 'undefined' &&\n typeof process.env !== 'undefined' &&\n (process.env.REACT_APP_SC_ATTR || process.env.SC_ATTR)) ||\n 'data-styled';\n\nexport const SC_ATTR_ACTIVE = 'active';\nexport const SC_ATTR_VERSION = 'data-styled-version';\nexport const SC_VERSION = __VERSION__;\nexport const SPLITTER = '/*!sc*/\\n';\n\nexport const IS_BROWSER = typeof window !== 'undefined' && 'HTMLElement' in window;\n\nexport const DISABLE_SPEEDY = Boolean(\n typeof SC_DISABLE_SPEEDY === 'boolean'\n ? SC_DISABLE_SPEEDY\n : typeof process !== 'undefined' && typeof process.env !== 'undefined'\n ? typeof process.env.REACT_APP_SC_DISABLE_SPEEDY !== 'undefined' &&\n process.env.REACT_APP_SC_DISABLE_SPEEDY !== ''\n ? process.env.REACT_APP_SC_DISABLE_SPEEDY
=== 'false'\n ? false\n : process.env.REACT_APP_SC_DISABLE_SPEEDY\n : typeof process.env.SC_DISABLE_SPEEDY !== 'undefined' && process.env.SC_DISABLE_SPEEDY !== ''\n ? process.env.SC_DISABLE_SPEEDY === 'false'\n ? false\n : process.env.SC_DISABLE_SPEEDY\n : process.env.NODE_ENV !== 'production'\n : false\n);\n\n// Shared empty execution context when generating static styles\nexport const STATIC_EXECUTION_CONTEXT = {};\n","// @flow\nimport errorMap from './errors';\n\nconst ERRORS = process.env.NODE_ENV !== 'production' ? errorMap : {};\n\n/**\n * super basic version of sprintf\n */\nfunction format(...args) {\n let a = args[0];\n const b = [];\n\n for (let c = 1, len = args.length; c < len; c += 1) {\n b.push(args[c]);\n }\n\n b.forEach(d => {\n a = a.replace(/%[a-z]/, d);\n });\n\n return a;\n}\n\n/**\n * Create an error file out of errors.md for development and a simple web link to the full errors\n
* in production mode.\n */\nexport default function throwStyledComponentsError(\n code: string | number,\n ...interpolations: Array<any>\n) {\n if (process.env.NODE_ENV === 'production') {\n throw new Error(\n `An error occurred. See https://git.io/JUIaE#${code} for more information.${\n interpolations.length > 0 ? ` Args: ${interpolations.join(', ')}` : ''\n }`\n);\n } else {\n throw new Error(format(ERRORS[code], ...interpolations).trim());\n }\n}\n","export default {\"1\":\"Cannot create styled-component for component: %s.\\n\\n\",\"2\":\"Can't collect styles once you've consumed a `ServerStyleSheet`'s styles! `ServerStyleSheet` is a one off instance for each server-side render cycle.\\n\\n- Are you trying to reuse it across renders?\\n- Are you accidentally calling collectStyles twice?\\n\\n\",\"3\":\"Streaming SSR is only supported in a Node.js environment; Please do not try to call this method in the browser.\\n\\n\",\"4\":\"The `StyleSheetManager`
expects a valid target or sheet prop!\\n\\n- Does this error occur on the client and is your target falsy?\\n- Does this error occur on the server and is the sheet falsy?\\n\\n\",\"5\":\"The clone method cannot be used on the client!\\n\\n- Are you running in a client-like environment on the server?\\n- Are you trying to run SSR on the client?\\n\\n\",\"6\":\"Trying to insert a new style tag, but the given Node is unmounted!\\n\\n- Are you using a custom target that isn't mounted?\\n- Does your document not have a valid head element?\\n- Have you accidentally removed a style tag manually?\\n\\n\",\"7\":\"ThemeProvider: Please return an object from your \\\"theme\\\" prop function, e.g.\\n\\n```js\\ntheme={() => ({})}\\n```\\n\\n\",\"8\":\"ThemeProvider: Please make your \\\"theme\\\" prop an object.\\n\\n\",\"9\":\"Missing document `<head>`\\n\\n\",\"10\":\"Cannot find a StyleSheet instance. Usually this happens if there are multiple copies of styled-components loaded at once. Check
out this issue for how to troubleshoot and fix the common cases where this situation can happen: https://github.com/styled-components/styled-components/issues/1941#issuecomment-417862021\\n\\n\",\"11\":\"_This error was replaced with a dev-time warning, it will be deleted for v4 final._ [createGlobalStyle] received children which will not be rendered. Please use the component without passing children elements.\\n\\n\",\"12\":\"It seems you are interpolating a keyframe declaration (%s) into an untagged string. This was supported in styled-components v3, but is not longer supported in v4 as keyframes are now injected on-demand. Please wrap your string in the css\\`\\`\\` helper which ensures the styles are injected correctly. See https://www.styled-components.com/docs/api#css\\n\\n\",\"13\":\"%s is not a styled component and cannot be

referred to via component selector. See https://www.styled-components.com/docs/advanced#referring-to-other-components for more details.\\n\\n\",\"14\":\"ThemeProvider:
\\\"theme\\\" prop is required.\\n\\n\",\"15\":\"A stylis plugin has been supplied that is not named. We need a name for each plugin to be able to prevent styling collisions between different stylis configurations within the same app. Before you pass your plugin to `<StyleSheetManager stylisPlugins={[]}>`, please make sure each plugin is uniquely-named, e.g.\\n\\n```js\\nObject.defineProperty(importedPlugin, 'name', { value: 'some-unique-name' });\\n```\\n\\n\",\"16\":\"Reached the limit of how many styled components may be created at group %s.\\nYou may only create up to 1,073,741,824 components. If you're creating components dynamically,\\nas for instance in your render method then you may be running into this limitation.\\n\\n\",\"17\":\"CSSStyleSheet could not be found on HTMLStyleElement.\\nHas styled-components' style tag been unmounted or altered by another script?\\n\\n\"};","// @flow\n/* eslint-disable no-use-before-define */\n\nimport type { GroupedTag, Tag } from
'./types';\nimport { SPLITTER } from '../constants';\nimport throwStyledError from '../utils/error';\n\n/** Create a GroupedTag with an underlying Tag implementation */\nexport const makeGroupedTag = (tag: Tag): GroupedTag => {\n return new DefaultGroupedTag(tag);\n};\n\nconst BASE_SIZE = 1 << 9;\n\nclass DefaultGroupedTag implements GroupedTag {\n groupSizes: Uint32Array;\n\n length: number;\n\n tag: Tag;\n\n constructor(tag: Tag) {\n   this.groupSizes = new Uint32Array(BASE_SIZE);\n   this.length = BASE_SIZE;\n   this.tag = tag;\n }\n\n indexOfGroup(group: number): number {\n   let index = 0;\n   for (let i = 0; i < group; i++) {\n   index += this.groupSizes[i];\n   }\n\n   return index;\n }\n\n insertRules(group: number, rules: string[]): void {\n   if (group >= this.groupSizes.length) {\n   const oldBuffer = this.groupSizes;\n   const oldSize = oldBuffer.length;\n\n   let newSize = oldSize;\n   while (group >= newSize) {\n   newSize <<= 1;\n
if (newSize < 0) {\n   throwStyledError(16, `${group}`);\n   }\n   }\n\n   this.groupSizes = new Uint32Array(newSize);\n   this.groupSizes.set(oldBuffer);\n   this.length = newSize;\n\n   for (let i = oldSize; i < newSize; i++) {\n   this.groupSizes[i] = 0;\n   }\n   }\n\n   let ruleIndex = this.indexOfGroup(group + 1);\n   for (let i = 0, l = rules.length; i < l; i++) {\n   if (this.tag.insertRule(ruleIndex, rules[i])) {\n   this.groupSizes[group]++;\n   ruleIndex++;\n   }\n   }\n }\n\n clearGroup(group: number): void {\n   if (group < this.length) {\n   const length = this.groupSizes[group];\n   const startIndex = this.indexOfGroup(group);\n   const endIndex = startIndex + length;\n\n   this.groupSizes[group] = 0;\n\n   for (let i = startIndex; i < endIndex; i++) {\n   this.tag.deleteRule(startIndex);\n   }\n   }\n }\n\n getGroup(group: number): string {\n   let css = '';\n   if (group >= this.length
|| this.groupSizes[group] === 0) {\n   return css;\n   }\n\n   const length = this.groupSizes[group];\n   const startIndex = this.indexOfGroup(group);\n   const endIndex = startIndex + length;\n\n   for (let i = startIndex; i < endIndex; i++) {\n   css += `${this.tag.getRule(i)}${SPLITTER}`;\n   }\n\n   return css;\n }\n}\n","// @flow\n\nimport throwStyledError from '../utils/error';\n\nconst MAX_SMI = 1 << 31 - 1;\n\nlet groupIDRegister: Map<string, number> = new Map();\nlet reverseRegister: Map<number, string> = new Map();\nlet nextFreeGroup = 1;\n\nexport const resetGroupIds = () => {\n groupIDRegister = new Map();\n reverseRegister = new Map();\n nextFreeGroup = 1;\n};\n\nexport const getGroupForId = (id: string): number => {\n if (groupIDRegister.has(id)) {\n   return (groupIDRegister.get(id): any);\n }\n\n while (reverseRegister.has(nextFreeGroup)) {\n   nextFreeGroup++;\n }\n\n const group = nextFreeGroup++;\n\n if (\n   process.env.NODE_ENV !==
'production' &&\n   ((group | 0) < 0 || group > MAX_SMI)\n) {\n   throwStyledError(16, `${group}`);\n }\n\n groupIDRegister.set(id, group);\n reverseRegister.set(group, id);\n return group;\n};\n\nexport const getIdForGroup = (group: number): void | string => {\n return reverseRegister.get(group);\n};\n\nexport const setGroupForId = (id: string, group: number) => {\n if (group >= nextFreeGroup) {\n   nextFreeGroup = group + 1;\n }\n\n groupIDRegister.set(id, group);\n reverseRegister.set(group, id);\n};\n","// @flow\n\nimport { SPLITTER, SC_ATTR, SC_ATTR_ACTIVE, SC_ATTR_VERSION, SC_VERSION } from '../constants';\nimport { getIdForGroup, setGroupForId } from './GroupIDAllocator';\nimport type { Sheet } from './types';\n\nconst SELECTOR = `style[${SC_ATTR}][${SC_ATTR_VERSION}=\"${SC_VERSION}\"]`;\nconst MARKER_RE = new RegExp(`^${SC_ATTR}\\\\.g(\\\\d+)\\\\[id=\"([\\\\w\\\\d-]+)\"\\\\].*?\"([^\"]*)`);\n\nexport const outputSheet = (sheet: Sheet) => {\n const tag = sheet.getTag();\n

```
  const { length } = tag;\n\n  let css = '';\n  for (let group = 0; group < length; group++) {\n    const id =
getIdForGroup(group);\n    if (id === undefined) continue;\n\n    const names = sheet.names.get(id);\n    const rules
= tag.getGroup(group);\n    if (!names || !rules || !names.size) continue;\n\n    const selector =
`${SC_ATTR}.g${group}[id=\"${id}\"]`;\n\n    let content = '';\n    if (names !== undefined) {\n
names.forEach(name => {\n        if (name.length > 0) {\n          content += `${name},`;\n        }\n      });\n    }\n\n    //
NOTE: It's easier to collect rules and have the marker\n    // after the actual rules to simplify the rehydration\n    css
+= `${rules}${selector}{content:\"${content}\"}${SPLITTER}`;\n  }\n\n  return css;\n};\n\nconst
rehydrateNamesFromContent = (sheet: Sheet, id: string, content: string) => {\n  const names = content.split(',');\n
let name;\n\n  for (let i = 0, l = names.length; i < l; i++) {\n    // eslint-disable-next-line\n
    if ((name = names[i])) {\n      sheet.registerName(id, name);\n    }\n  }\n};\n\nconst rehydrateSheetFromTag =
(sheet: Sheet, style: HTMLStyleElement) => {\n  const parts = (style.textContent || '').split(SPLITTER);\n  const
rules: string[] = [];\n\n  for (let i = 0, l = parts.length; i < l; i++) {\n    const part = parts[i].trim();\n    if (!part)
continue;\n\n    const marker = part.match(MARKER_RE);\n\n    if (marker) {\n      const group =
parseInt(marker[1], 10) | 0;\n      const id = marker[2];\n\n      if (group !== 0) {\n        // Rehydrate componentId to
group index mapping\n        setGroupForId(id, group);\n        // Rehydrate names and rules\n        // looks like: data-
styled.g11[id=\"idA\"]{content:\"nameA,\"}\n        rehydrateNamesFromContent(sheet, id, marker[3]);\n
sheet.getTag().insertRules(group, rules);\n      }\n\n      rules.length = 0;\n    } else {\n      rules.push(part);\n    }\n
}\n};\n\nexport const rehydrateSheet = (sheet: Sheet) => {\n  const
 nodes = document.querySelectorAll(SELECTOR);\n\n  for (let i = 0, l = nodes.length; i < l; i++) {\n    const node =
((nodes[i]: any): HTMLStyleElement);\n    if (node && node.getAttribute(SC_ATTR) !== SC_ATTR_ACTIVE)
{\n      rehydrateSheetFromTag(sheet, node);\n\n      if (node.parentNode) {\n
node.parentNode.removeChild(node);\n      }\n    }\n  }\n};\n","// @flow\n/* eslint-disable camelcase, no-undef
*/\n\ndeclare var __webpack_nonce__: string;\n\nconst getNonce = () => {\n  return typeof __webpack_nonce__
!== 'undefined' ? __webpack_nonce__ : null;\n};\n\nexport default getNonce;\n","// @flow\n\nimport { SC_ATTR,
SC_ATTR_ACTIVE, SC_ATTR_VERSION, SC_VERSION } from '../constants';\nimport getNonce from
'../utils/nonce';\nimport throwStyledError from '../utils/error';\n\nconst ELEMENT_TYPE = 1; /*
Node.ELEMENT_TYPE */\n\n/** Find last style element if any inside target */\nconst findLastStyleTag = (target:
HTMLElement): void | HTMLStyleElement => {\n  const { childNodes }
 = target;\n\n  for (let i = childNodes.length; i >= 0; i--) {\n    const child = ((childNodes[i]: any):
?HTMLElement);\n    if (child && child.nodeType === ELEMENT_TYPE && child.hasAttribute(SC_ATTR)) {\n
  return ((child: any): HTMLStyleElement);\n    }\n  }\n\n  return undefined;\n};\n\n/** Create a style element
inside `target` or <head> after the last */\nexport const makeStyleTag = (target?: HTMLElement):
HTMLStyleElement => {\n  const head = ((document.head: any): HTMLElement);\n  const parent = target || head;\n
const style = document.createElement('style');\n  const prevStyle = findLastStyleTag(parent);\n  const nextSibling =
prevStyle !== undefined ? prevStyle.nextSibling : null;\n\n  style.setAttribute(SC_ATTR, SC_ATTR_ACTIVE);\n
style.setAttribute(SC_ATTR_VERSION, SC_VERSION);\n\n  const nonce = getNonce();\n\n  if (nonce)
style.setAttribute('nonce', nonce);\n\n  parent.insertBefore(style, nextSibling);\n\n  return style;\n};\n\n/** Get the
CSSStyleSheet instance for a
 given style element */\nexport const getSheet = (tag: HTMLStyleElement): CSSStyleSheet => {\n  if (tag.sheet) {\n
  return ((tag.sheet: any): CSSStyleSheet);\n  }\n\n  // Avoid Firefox quirk where the style element might not have a
sheet property\n  const { styleSheets } = document;\n  for (let i = 0, l = styleSheets.length; i < l; i++) {\n    const
sheet = styleSheets[i];\n    if (sheet.ownerNode === tag) {\n      return ((sheet: any): CSSStyleSheet);\n    }\n  }\n\n
throwStyledError(17);\n  return (undefined: any);\n};\n","// @flow\n/* eslint-disable no-use-before-define
*/\n\nimport { makeStyleTag, getSheet } from './dom';\nimport type { SheetOptions, Tag } from './types';\n\n/**
Create a CSSStyleSheet-like tag depending on the environment */\nexport const makeTag = ({ isServer,
useCSSOMInjection, target }: SheetOptions): Tag => {\n  if (isServer) {\n    return new VirtualTag(target);\n  } else
if (useCSSOMInjection) {\n    return new CSSOMTag(target);\n  } else {\n    return new
```

```
TextTag(target);\n  }\n};\n\nexport class CSSOMTag implements Tag {\n  element: HTMLStyleElement;\n\n
sheet: CSSStyleSheet;\n\n  length: number;\n\n  constructor(target?: HTMLElement) {\n    const element =
(this.element = makeStyleTag(target));\n\n    // Avoid Edge bug where empty style elements don't create sheets\n
element.appendChild(document.createTextNode(''));\n\n    this.sheet = getSheet(element);\n    this.length = 0;\n
}\n\n  insertRule(index: number, rule: string): boolean {\n    try {\n      this.sheet.insertRule(rule, index);\n
this.length++;\n      return true;\n    } catch (_error) {\n      return false;\n    }\n  }\n\n  deleteRule(index: number):
void {\n    this.sheet.deleteRule(index);\n    this.length--;\n  }\n\n  getRule(index: number): string {\n    const rule =
this.sheet.cssRules[index];\n    // Avoid IE11 quirk where cssText is inaccessible on some invalid rules\n    if (rule
!== undefined && typeof rule.cssText === 'string') {\n      return rule.cssText;\n
  } else {\n      return '';\n    }\n  }\n}\n\n/** A Tag that emulates the CSSStyleSheet API but uses text nodes
*/\nexport class TextTag implements Tag {\n  element: HTMLStyleElement;\n\n  nodes: NodeList<Node>;\n\n
length: number;\n\n  constructor(target?: HTMLElement) {\n    const element = (this.element =
makeStyleTag(target));\n    this.nodes = element.childNodes;\n    this.length = 0;\n  }\n\n  insertRule(index: number,
rule: string): boolean {\n    if (index <= this.length && index >= 0) {\n      const node =
document.createTextNode(rule);\n      const refNode = this.nodes[index];\n      this.element.insertBefore(node,
refNode || null);\n      this.length++;\n      return true;\n    } else {\n      return false;\n    }\n  }\n\n  deleteRule(index:
number): void {\n    this.element.removeChild(this.nodes[index]);\n    this.length--;\n  }\n\n  getRule(index:
number): string {\n    if (index < this.length) {\n      return this.nodes[index].textContent;\n    } else {\n      return
'';\n    }\n  }\n}\n\n/** A completely virtual (server-side) Tag that doesn't manipulate the DOM */\nexport class
VirtualTag implements Tag {\n  rules: string[];\n\n  length: number;\n\n  constructor(_target?: HTMLElement) {\n
this.rules = [];\n    this.length = 0;\n  }\n\n  insertRule(index: number, rule: string): boolean {\n    if (index <=
this.length) {\n      this.rules.splice(index, 0, rule);\n      this.length++;\n      return true;\n    } else {\n      return
false;\n    }\n  }\n\n  deleteRule(index: number): void {\n    this.rules.splice(index, 1);\n    this.length--;\n  }\n\n
getRule(index: number): string {\n    if (index < this.length) {\n      return this.rules[index];\n    } else {\n      return
'';\n    }\n  }\n}\n","// @flow\nimport { DISABLE_SPEEDY, IS_BROWSER } from '../constants';\nimport {
EMPTY_OBJECT } from '../utils/empties';\nimport { makeGroupedTag } from './GroupedTag';\nimport {
getGroupForId } from './GroupIDAllocator';\nimport { outputSheet, rehydrateSheet
} from './Rehydration';\nimport { makeTag } from './Tag';\nimport type { GroupedTag, Sheet, SheetOptions } from
'./types';\n\nlet SHOULD_REHYDRATE = IS_BROWSER;\n\ntype SheetConstructorArgs = {\n  isServer?:
boolean,\n  useCSSOMInjection?: boolean,\n  target?: HTMLElement,\n};\n\ntype GlobalStylesAllocationMap = {
[key: string]: number };\ntype NamesAllocationMap = Map<string, Set<string>>;\n\nconst defaultOptions:
SheetOptions = {\n  isServer: !IS_BROWSER,\n  useCSSOMInjection: !DISABLE_SPEEDY,\n};\n\n/** Contains
the main stylesheet logic for stringification and caching */\nexport default class StyleSheet implements Sheet {\n
gs: GlobalStylesAllocationMap;\n\n  names: NamesAllocationMap;\n\n  options: SheetOptions;\n\n  server:
boolean;\n\n  tag: void | GroupedTag;\n\n  /** Register a group ID to give it an index */\n  static registerId(id:
string): number {\n    return getGroupForId(id);\n  }\n\n  constructor(\n    options: SheetConstructorArgs =
EMPTY_OBJECT,\n    globalStyles?:
  GlobalStylesAllocationMap = {},\n    names?: NamesAllocationMap\n  ) {\n    this.options = {\n
...defaultOptions,\n      ...options,\n    };\n\n    this.gs = globalStyles;\n    this.names = new Map(names);\n
this.server = !!options.isServer;\n\n    // We rehydrate only once and use the sheet that is created first\n    if
(!this.server && IS_BROWSER && SHOULD_REHYDRATE) {\n      SHOULD_REHYDRATE = false;\n
rehydrateSheet(this);\n    }\n  }\n\n  reconstructWithOptions(options: SheetConstructorArgs, withNames?: boolean =
true) {\n    return new StyleSheet(\n      { ...this.options, ...options },\n      this.gs,\n      (withNames && this.names) ||
undefined\n    );\n  }\n\n  allocateGSInstance(id: string) {\n    return (this.gs[id] = (this.gs[id] || 0) + 1);\n  }\n\n  /**
Lazily initialises a GroupedTag for when it's actually needed */\n  getTag(): GroupedTag {\n    return this.tag ||
(this.tag = makeGroupedTag(makeTag(this.options)));\n  }\n\n  /** Check whether a name
  is known for caching */\n  hasNameForId(id: string, name: string): boolean {\n    return this.names.has(id) &&
(this.names.get(id): any).has(name);\n  }\n\n  /** Mark a group's name as known for caching */\n  registerName(id:
```

string, name: string) {\n getGroupForId(id);\n\n if (!this.names.has(id)) {\n const groupNames = new Set();\n groupNames.add(name);\n this.names.set(id, groupNames);\n } else {\n (this.names.get(id): any).add(name);\n }\n }\n\n /** Insert new rules which also marks the name as known */\n insertRules(id: string, name: string, rules: string[]) {\n this.registerName(id, name);\n this.getTag().insertRules(getGroupForId(id), rules);\n }\n\n /** Clears all cached names for a given group ID */\n clearNames(id: string) {\n if (this.names.has(id)) {\n (this.names.get(id): any).clear();\n }\n }\n\n /** Clears all rules for a given group ID */\n clearRules(id: string) {\n this.getTag().clearGroup(getGroupForId(id));\n this.clearNames(id);\n }\n\n /** Clears the entire tag which deletes all rules but not its names */\n clearTag() {\n // NOTE: This does not clear the names, since it's only used during SSR\n // so that we can continuously output only new rules\n this.tag = undefined;\n }\n\n /** Outputs the current sheet as a CSS string with markers for SSR */\n toString(): string {\n return outputSheet(this);\n }\n}\n","// @flow\n/* eslint-disable no-bitwise */\n\nconst AD_REPLACER_R = /(a)(d)/gi;\n\n/* This is the \"capacity\" of our alphabet i.e. 2x26 for all letters plus their capitalised\n * counterparts */\nconst charsLength = 52;\n\n/* start at 75 for 'a' until 'z' (25) and then start at 65 for capitalised letters */\nconst getAlphabeticChar = (code: number): string =>\n String.fromCharCode(code + (code > 25 ? 39 : 97));\n\n/* input a number, usually a hash and convert it to base-52 */\nexport default function generateAlphabeticName(code: number): string {\n let name = '';\n let x;\n\n /* get a char and divide by alphabet-length */\n for (x = Math.abs(code); x > charsLength; x = (x / charsLength) | 0) {\n name = getAlphabeticChar(x % charsLength) + name;\n }\n\n return (getAlphabeticChar(x % charsLength) + name).replace(AD_REPLACER_R, '$1-$2');\n}\n","// @flow\n/* eslint-disable */\n\nexport const SEED = 5381;\n\n// When we have separate strings it's useful to run a progressive\n// version of djb2 where we pretend that we're still looping over\n// the same string\nexport const phash = (h: number, x: string): number => {\n let i = x.length;\n\n while (i) {\n h = (h * 33) ^ x.charCodeAt(--i);\n }\n\n return h;\n};\n\n// This is a djb2 hashing function\nexport const hash = (x: string): number => {\n return phash(SEED, x);\n};\n","// @flow\nimport isFunction from './isFunction';\nimport isStyledComponent from './isStyledComponent';\nimport type { RuleSet } from '../types';\n\nexport default function isStaticRules(rules: RuleSet): boolean {\n for (let i = 0; i < rules.length; i += 1) {\n const rule = rules[i];\n\n if (isFunction(rule) && !isStyledComponent(rule)) {\n // functions are allowed to be static if they're just being\n // used to get the classname of a nested styled component\n return false;\n }\n }\n\n return true;\n}\n","// @flow\nimport { SC_VERSION } from '../constants';\nimport StyleSheet from '../sheet';\nimport type { RuleSet, Stringifier } from '../types';\nimport flatten from '../utils/flatten';\nimport generateName from '../utils/generateAlphabeticName';\nimport { hash, phash } from '../utils/hash';\nimport isStaticRules from '../utils/isStaticRules';\n\nconst SEED = hash(SC_VERSION);\n\n/**\n * ComponentStyle is all the CSS-specific stuff, not the React-specific stuff.\n */\nexport default class ComponentStyle {\n baseHash: number;\n\n baseStyle: ?ComponentStyle;\n\n componentId: string;\n\n isStatic: boolean;\n\n rules: RuleSet;\n\n staticRulesId: string;\n\n constructor(rules: RuleSet, componentId: string, baseStyle?: ComponentStyle) {\n this.rules = rules;\n this.staticRulesId = '';\n this.isStatic = process.env.NODE_ENV === 'production' &&\n (baseStyle === undefined || baseStyle.isStatic) &&\n isStaticRules(rules);\n this.componentId = componentId;\n\n // SC_VERSION gives us isolation between multiple runtimes on the page at once\n // this is improved further with use of the babel plugin \"namespace\" feature\n this.baseHash = phash(SEED, componentId);\n\n this.baseStyle = baseStyle;\n\n // NOTE: This registers the componentId, which ensures a consistent order\n // for this component's styles compared to others\n StyleSheet.registerId(componentId);\n }\n\n /*\n * Flattens a rule set into valid CSS\n * Hashes it, wraps the whole chunk in a .hash1234 {}\n * Returns the hash to be injected on render()\n * */\n generateAndInjectStyles(executionContext: Object, styleSheet: StyleSheet, stylis: Stringifier) {\n const { componentId } = this;\n\n const names = [];\n\n if (this.baseStyle) {\n names.push(this.baseStyle.generateAndInjectStyles(executionContext, styleSheet, stylis));\n }\n\n // force dynamic classnames if user-supplied stylis plugins are in use\n if (this.isStatic && !stylis.hash) {\n if (this.staticRulesId && styleSheet.hasNameForId(componentId, this.staticRulesId)) {\n

names.push(this.staticRulesId);\n } else {\n const cssStatic = flatten(this.rules, executionContext, styleSheet, stylis).join('');\n const name = generateName(phash(this.baseHash, cssStatic) >>> 0);\n\n if (!styleSheet.hasNameForId(componentId, name)) {\n const cssStaticFormatted = stylis(cssStatic, `.${name}`, undefined, componentId);\n\n styleSheet.insertRules(componentId, name, cssStaticFormatted);\n }\n\n names.push(name);\n this.staticRulesId = name;\n }\n } else {\n const { length } = this.rules;\n let dynamicHash = phash(this.baseHash, stylis.hash);\n let css = '';\n\n for (let i = 0; i < length; i++) {\n const partRule = this.rules[i];\n\n if (typeof partRule === 'string') {\n css += partRule;\n\n if (process.env.NODE_ENV !== 'production') dynamicHash = phash(dynamicHash, partRule + i);\n } else if (partRule) {\n const partChunk = flatten(partRule, executionContext, styleSheet, stylis);\n const partString = Array.isArray(partChunk) ? partChunk.join('') : partChunk;\n dynamicHash = phash(dynamicHash, partString + i);\n css += partString;\n }\n }\n\n if (css) {\n const name = generateName(dynamicHash >>> 0);\n\n if (!styleSheet.hasNameForId(componentId, name)) {\n const cssFormatted = stylis(css, `.${name}`, undefined, componentId);\n styleSheet.insertRules(componentId, name, cssFormatted);\n }\n\n names.push(name);\n }\n }\n\n return names.join(' ');\n }\n}\n","import Stylis from '@emotion/stylis';\nimport { type Stringifier } from '../types';\nimport { EMPTY_ARRAY, EMPTY_OBJECT } from './empties';\nimport throwStyledError from './error';\nimport { phash, SEED } from './hash';\nimport insertRulePlugin from './stylisPluginInsertRule';\n\nconst COMMENT_REGEX = /^\\s*\\/\\/.*$/gm;\nconst COMPLEX_SELECTOR_PREFIX = [':', '[', '.', '#'];\n\ntype StylisInstanceConstructorArgs = {\n options?: Object,\n plugins?: Array<Function>,\n};\n\nexport default function createStylisInstance({\n options = EMPTY_OBJECT,\n plugins = EMPTY_ARRAY,\n}: StylisInstanceConstructorArgs = EMPTY_OBJECT) {\n const stylis = new Stylis(options);\n\n // Wrap `insertRulePlugin to build a list of rules,\n // and then make our own plugin to return the rules. This\n // makes it easier to hook into the existing SSR architecture\n\n let parsingRules = [];\n\n // eslint-disable-next-line consistent-return\n const returnRulesPlugin = context => {\n if (context === -2) {\n const parsedRules = parsingRules;\n parsingRules = [];\n return parsedRules;\n }\n };\n\n const parseRulesPlugin = insertRulePlugin(rule => {\n parsingRules.push(rule);\n });\n\n let _componentId: string;\n let _selector: string;\n let _selectorRegexp: RegExp;\n let _consecutiveSelfRefRegExp: RegExp;\n\n const selfReferenceReplacer = (match, offset, string) => {\n if (\n // do not replace the first occurrence if it is complex (has a modifier)\n offset === 0 ? COMPLEX_SELECTOR_PREFIX.indexOf(string[_selector.length]) === -1 : true) &&\n // no consecutive self refs (.b.b); that is a precedence boost and treated differently\n !string.match(_consecutiveSelfRefRegExp)\n) {\n return `.${_componentId}`;\n }\n\n return match;\n };\n\n /**\n * When writing a style like\n *\n * & + & {\n * color: red;\n * }\n *\n * The second ampersand should be a reference to the static component class. stylis\n * has no knowledge of static class so we have to intelligently replace the base selector.\n *\n * https://github.com/thysultan/stylis.js/tree/v3.5.4#plugins <- more info about the context phase values\n * \"2\" means this plugin is taking effect at the very end after all other processing is complete\n */\n const selfReferenceReplacementPlugin = (context, _, selectors) => {\n if (context === 2 && selectors.length && selectors[0].lastIndexOf(_selector) > 0) {\n // eslint-disable-next-line no-param-reassign\n selectors[0] = selectors[0].replace(_selectorRegexp, selfReferenceReplacer);\n }\n };\n\n stylis.use([...plugins, selfReferenceReplacementPlugin, parseRulesPlugin, returnRulesPlugin]);\n\n function stringifyRules(css, selector, prefix, componentId = '&'): Stringifier {\n const flatCSS = css.replace(COMMENT_REGEX, '');\n const cssStr = selector && prefix ? `${prefix} ${selector} { ${flatCSS} }` : flatCSS;\n\n // stylis has no concept of state to be passed to plugins\n // but since JS is single-threaded, we can rely on that to ensure\n // these properties stay in sync with the current stylis run\n _componentId = componentId;\n _selector = selector;\n _selectorRegexp = new RegExp(`\\\\${_selector}\\\\b`, 'g');\n _consecutiveSelfRefRegExp = new RegExp(`(\\\\${_selector}\\\\b){2,}`);\n\n return stylis(prefix || !selector ? '' : selector, cssStr);\n }\n\n stringifyRules.hash = plugins.length\n ? plugins\n .reduce((acc, plugin) => {\n if (!plugin.name) {\n throwStyledError(15);\n }\n\n return phash(acc, plugin.name);\n },

SEED)\n .toString()\n : ";\n\n return stringifyRules;\n}\n","/**\n * MIT License\n *\n * Copyright (c) 2016 Sultan Tarimo\n *\n * Permission is hereby granted, free of charge, to any person obtaining a copy of\n * this software and associated documentation files (the \"Software\"),\n
* to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or\n * sell copies of the Software and to permit persons to whom the Software is furnished to do so, subject to the following conditions:\n *\n * The above copyright notice and this permission notice shall be included in all\n * copies or substantial portions of the Software.\n *\n * THE SOFTWARE IS PROVIDED \"AS IS\", WITHOUT WARRANTY OF ANY KIND, EXPRESS\n * OR IMPLIED INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,\n * FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE\n * AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,\n * WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR\n * IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.\n */\n/* eslint-disable */\n\nexport default function(insertRule) {\n
const delimiter = '/*|*/';\n const needle = `${delimiter}}`;\n\n function toSheet(block) {\n if (block) {\n try {\n insertRule(`${block}}`);\n } catch (e) {}\n }\n }\n\n return function ruleSheet(\n context,\n content,\n selectors,\n parents,\n line,\n column,\n length,\n ns,\n depth,\n at\n) {\n switch (context) {\n // property\n case 1:\n // @import\n if (depth === 0 && content.charCodeAt(0) === 64) return insertRule(`${content};`), ";\n break;\n // selector\n case 2:\n if (ns === 0) return content + delimiter;\n break;\n // at-rule\n case 3:\n switch (ns) {\n // @font-face, @page\n case 102:\n case 112:\n return insertRule(selectors[0] + content), ";\n default:\n return content + (at === 0 ? delimiter : "");\n }\n case -2:\n content.split(needle).forEach(toSheet);\n }\n
};\n}\n","// @flow\nimport React, { type Context, type Node, useContext, useEffect, useMemo, useState } from 'react';\nimport shallowequal from 'shallowequal';\nimport StyleSheet from '../sheet';\nimport type { Stringifier } from '../types';\nimport createStylisInstance from '../utils/stylis';\n\ntype Props = {\n children?: Node,\n disableCSSOMInjection?: boolean,\n disableVendorPrefixes?: boolean,\n sheet?: StyleSheet,\n stylisPlugins?: Array<Function>,\n target?: HTMLElement,\n};\n\nexport const StyleSheetContext: Context<StyleSheet | void> = React.createContext();\nexport const StyleSheetConsumer = StyleSheetContext.Consumer;\nexport const StylisContext: Context<Stringifier | void> = React.createContext();\nexport const StylisConsumer = StylisContext.Consumer;\n\nexport const masterSheet: StyleSheet = new StyleSheet();\nexport const masterStylis: Stringifier = createStylisInstance();\n\nexport function useStyleSheet(): StyleSheet {\n return useContext(StyleSheetContext) ||
masterSheet;\n}\n\nexport function useStylis(): Stringifier {\n return useContext(StylisContext) || masterStylis;\n}\n\nexport default function StyleSheetManager(props: Props) {\n const [plugins, setPlugins] = useState(props.stylisPlugins);\n const contextStyleSheet = useStyleSheet();\n\n const styleSheet = useMemo(() => {\n let sheet = contextStyleSheet;\n\n if (props.sheet) {\n // eslint-disable-next-line prefer-destructuring\n sheet = props.sheet;\n } else if (props.target) {\n sheet = sheet.reconstructWithOptions({ target: props.target }, false);\n }\n\n if (props.disableCSSOMInjection) {\n sheet = sheet.reconstructWithOptions({ useCSSOMInjection: false });\n }\n\n return sheet;\n }, [props.disableCSSOMInjection, props.sheet, props.target]);\n\n const stylis = useMemo(\n () =>\n createStylisInstance({\n options: { prefix: !props.disableVendorPrefixes },\n plugins,\n }),\n [props.disableVendorPrefixes, plugins]\n);\n\n useEffect(() => {\n if (!shallowequal(plugins, props.stylisPlugins)) setPlugins(props.stylisPlugins);\n }, [props.stylisPlugins]);\n\n return (\n <StyleSheetContext.Provider value={styleSheet}>\n <StylisContext.Provider value={stylis}>\n {process.env.NODE_ENV !== 'production'\n ? React.Children.only(props.children)\n : props.children}\n </StylisContext.Provider>\n </StyleSheetContext.Provider>\n);\n}\n","// @flow\nimport StyleSheet from '../sheet';\nimport { type Stringifier } from '../types';\nimport throwStyledError from '../utils/error';\nimport { masterStylis } from './StyleSheetManager';\n\nexport default class Keyframes {\n id: string;\n\n name: string;\n\n rules: string;\n\n

constructor(name: string, rules: string) {\n this.name = name;\n this.id = `sc-keyframes-${name}`;\n this.rules = rules;\n }\n\n inject = (styleSheet: StyleSheet, stylisInstance: Stringifier = masterStylis) => {\n const resolvedName
= this.name + stylisInstance.hash;\n\n if (!styleSheet.hasNameForId(this.id, resolvedName)) {\n styleSheet.insertRules(\n this.id,\n resolvedName,\n stylisInstance(this.rules, resolvedName, '@keyframes')\n);\n }\n };\n\n toString = () => {\n return throwStyledError(12, String(this.name));\n };\n\n getName(stylisInstance: Stringifier = masterStylis) {\n return this.name + stylisInstance.hash;\n }\n}\n","// @flow\n\n/**\n * inlined version of\n * https://github.com/facebook/fbjs/blob/master/packages/fbjs/src/core/hyphenateStyleName.js\n */\n\nconst uppercaseCheck = /([A-Z])/;\nconst uppercasePattern = /([A-Z])/g;\nconst msPattern = /^ms-/;\nconst prefixAndLowerCase = (char: string): string => `-${char.toLowerCase()}`;\n\n/**\n * Hyphenates a camelcased CSS property name, for example:\n *\n * > hyphenateStyleName('backgroundColor')\n * < \"background-color\"\n * > hyphenateStyleName('MozTransition')\n * < \"-moz-transition\"\n * > hyphenateStyleName('msTransition')\n * < \"-ms-transition\"\n *\n * As Modernizr suggests (http://modernizr.com/docs/#prefixed), an `ms` prefix\n * is converted to `-ms-`.\n *\n * @param {string} string\n * @return {string}\n */\nexport default function hyphenateStyleName(string: string): string {\n return uppercaseCheck.test(string)\n ? string\n .replace(uppercasePattern, prefixAndLowerCase)\n .replace(msPattern, '-ms-')\n : string;\n}\n","// @flow\nimport { isElement } from 'react-is';\nimport getComponentName from './getComponentName';\nimport isFunction from './isFunction';\nimport isStatelessFunction from './isStatelessFunction';\nimport isPlainObject from './isPlainObject';\nimport isStyledComponent from './isStyledComponent';\nimport Keyframes from '../models/Keyframes';\nimport hyphenate from './hyphenateStyleName';\nimport addUnitIfNeeded from './addUnitIfNeeded';\nimport { type Stringifier } from '../types';\n\n/**\n * It's falsish not falsy because 0 is allowed.\n */\nconst isFalsish = chunk => chunk === undefined || chunk === null || chunk === false || chunk === '';\n\nexport const objToCssArray = (obj: Object, prevKey?: string): Array<string | Function> => {\n const rules = [];\n\n for (const key in obj) {\n if (!obj.hasOwnProperty(key) || isFalsish(obj[key])) continue;\n\n if ((Array.isArray(obj[key]) && obj[key].isCss) || isFunction(obj[key])) {\n rules.push(`${hyphenate(key)}:`, obj[key], ';');\n } else if (isPlainObject(obj[key])) {\n rules.push(...objToCssArray(obj[key], key));\n } else {\n rules.push(`${hyphenate(key)}: ${addUnitIfNeeded(key, obj[key])};`);\n }\n }\n\n return prevKey ? [`${prevKey} {`, ...rules, '}'] : rules;\n};\n\nexport default function flatten(\n chunk: any,\n executionContext: ?Object,\n styleSheet: ?Object,\n stylisInstance: ?Stringifier\n): any {\n if (Array.isArray(chunk)) {\n const ruleSet = [];\n\n for (let i = 0, len = chunk.length, result; i < len; i += 1) {\n result = flatten(chunk[i], executionContext, styleSheet, stylisInstance);\n\n if (result === '') continue;\n else if (Array.isArray(result)) ruleSet.push(...result);\n else ruleSet.push(result);\n }\n\n return ruleSet;\n }\n\n if (isFalsish(chunk)) {\n return '';\n }\n\n /* Handle other components */\n if (isStyledComponent(chunk)) {\n return `.${chunk.styledComponentId}`;\n }\n\n /* Either execute or defer the function */\n if (isFunction(chunk)) {\n if (isStatelessFunction(chunk) && executionContext) {\n const result = chunk(executionContext);\n\n if (process.env.NODE_ENV !== 'production' && isElement(result)) {\n // eslint-disable-next-line no-console\n console.warn(\n `${getComponentName(\n chunk\n )} is not a styled component and cannot be referred to via component selector. See https://www.styled-components.com/docs/advanced#referring-to-other-components for more details.`\n);\n }\n\n return flatten(result, executionContext, styleSheet, stylisInstance);\n } else return chunk;\n }\n\n if (chunk instanceof Keyframes) {\n if (styleSheet) {\n chunk.inject(styleSheet, stylisInstance);\n return chunk.getName(stylisInstance);\n } else return chunk;\n }\n\n /* Handle objects */\n return isPlainObject(chunk) ? objToCssArray(chunk) : chunk.toString();\n}\n","// @flow\nexport default function isStatelessFunction(test: any): boolean {\n return (\n typeof test === 'function'\n && !(\n test.prototype\n && test.prototype.isReactComponent\n)\n);\n}\n","// @flow\nimport unitless from '@emotion/unitless';\n\n// Taken from https://github.com/facebook/react/blob/b87aabdfe1b7461e7331abb3601d9e6bb27544bc/packages/react-

dom/src/shared/dangerousStyleValue.js\nexport default function addUnitIfNeeded(name: string, value: any): any {\n // https://github.com/amilajack/eslint-plugin-flowtype-errors/issues/133\n // $FlowFixMe\n if (value == null || typeof value === 'boolean' || value === '') {\n return '';\n }\n\n if (typeof value === 'number' && value !== 0 && !(name in unitless) && !name.startsWith('--')) {\n return `${value}px`; // Presumes implicit 'px' suffix for unitless numbers except for CSS variables\n }\n\n return String(value).trim();\n}\n","// @flow\nimport interleave from '../utils/interleave';\nimport isPlainObject from '../utils/isPlainObject';\nimport { EMPTY_ARRAY } from '../utils/empties';\nimport isFunction from '../utils/isFunction';\nimport flatten from '../utils/flatten';\nimport type { Interpolation, RuleSet, Styles } from '../types';\n\n/**\n * Used when flattening object styles to determine if we should\n * expand an array of styles.\n */\nconst addTag = arg => {\n if (Array.isArray(arg)) {\n // eslint-disable-next-line no-param-reassign\n arg.isCss = true;\n }\n return arg;\n};\n\nexport default function css(styles: Styles, ...interpolations: Array<Interpolation>): RuleSet {\n if (isFunction(styles) || isPlainObject(styles)) {\n // $FlowFixMe\n return addTag(flatten(interleave(EMPTY_ARRAY, [styles, ...interpolations])));\n }\n\n if (interpolations.length === 0 && styles.length === 1 && typeof styles[0] === 'string') {\n // $FlowFixMe\n return styles;\n }\n\n // $FlowFixMe\n return addTag(flatten(interleave(styles, interpolations)));\n}\n","// @flow\n\nimport { useRef } from 'react';\n\nconst invalidHookCallRe = /invalid hook call/i;\nconst seen = new Set();\n\nexport const checkDynamicCreation = (displayName: string, componentId?: string) => {\n if (process.env.NODE_ENV !== 'production') {\n const parsedIdString = componentId ? ` with the id of \"${componentId}\"` : '';\n const message =\n `The component ${displayName}${parsedIdString} has been created dynamically.\\n` +\n \"You may see this warning because you've called styled inside another component.\\n\" +\n 'To resolve this only create new StyledComponents outside of any render method and function component.';\n\n // If a hook is called outside of a component:\n // React 17 and earlier throw an error\n // React 18 and above use console.error\n\n const originalConsoleError = console.error // eslint-disable-line no-console\n try {\n let didNotCallInvalidHook = true\n /* $FlowIgnore[cannot-write] */\n console.error = (consoleErrorMessage, ...consoleErrorArgs) => { // eslint-disable-line no-console\n // The error here is expected, since we're expecting anything that uses `checkDynamicCreation` to\n // be called outside of a React component.\n if (invalidHookCallRe.test(consoleErrorMessage)) {\n didNotCallInvalidHook = false\n // This shouldn't happen, but resets `warningSeen` if we had this error happen intermittently\n seen.delete(message);\n } else {\n originalConsoleError(consoleErrorMessage, ...consoleErrorArgs);\n }\n }\n // We purposefully call `useRef` outside of a component and expect it to throw\n // If it doesn't, then we're inside another component.\n // eslint-disable-next-line react-hooks/rules-of-hooks\n useRef();\n\n if (didNotCallInvalidHook && !seen.has(message)) {\n // eslint-disable-next-line no-console\n console.warn(message);\n seen.add(message);\n }\n } catch (error) {\n // The error here is expected, since we're expecting anything that uses `checkDynamicCreation` to\n // be called outside of a React component.\n if (invalidHookCallRe.test(error.message)) {\n // This shouldn't happen, but resets `warningSeen` if we had this error happen intermittently\n seen.delete(message);\n }\n } finally {\n /* $FlowIgnore[cannot-write] */\n console.error = originalConsoleError; // eslint-disable-line no-console\n }\n};\n","// @flow\nimport { EMPTY_OBJECT } from './empties';\n\ntype Props = {\n theme?: any,\n};\n\nexport default (props: Props, providedTheme: any, defaultProps: any = EMPTY_OBJECT) => {\n return (props.theme !== defaultProps.theme && props.theme) || providedTheme || defaultProps.theme;\n};\n","// @flow\n\n// Source: https://www.w3.org/TR/cssom-1/#serialize-an-identifier\n// Control characters and non-letter first symbols are not supported\nconst escapeRegex = /[!\"#$%&'()*+,./:;<=>?@[\\\\\\]^`{|}~-]+/g;\n\nconst dashesAtEnds = /(^-|-$)/g;\n\n/**\n * TODO: Explore using CSS.escape when it becomes more available\n * in evergreen browsers.\n */\nexport default function escape(str: string): string {\n return (\n str\n // Replace all possible CSS selectors\n .replace(escapeRegex, '-')\n\n // Remove extraneous hyphens at the start and end\n .replace(dashesAtEnds, '')\n);\n}\n","// @flow\n/* eslint-disable */\nimport generateAlphabeticName from './generateAlphabeticName';\nimport { hash } from './hash';\n\nexport default (str: string): string

=> {\n return generateAlphabeticName(hash(str) >>> 0);\n};\n","// @flow\nimport type { IStyledComponent } from '../types';\n\nexport default function isTag(target: $PropertyType<IStyledComponent, 'target'>): boolean %checks {\n return (\n   typeof target === 'string' &&\n   (process.env.NODE_ENV !== 'production'\n   ? target.charAt(0) === target.charAt(0).toLowerCase()\n   : true)\n);\n}\n","/* eslint-disable */\n/**\n mixin-deep; https://github.com/jonschlinkert/mixin-deep\n Inlined such that it will be consistently transpiled to an IE-compatible syntax.\n\n The MIT License (MIT)\n\n Copyright (c) 2014-present, Jon Schlinkert.\n\n Permission is hereby granted, free of charge, to any person obtaining a copy\n of this software and associated documentation files (the \"Software\"), to deal\n in the Software without restriction, including without limitation the rights\n to use, copy, modify, merge, publish, distribute, sublicense, and/or sell\n copies of the Software,
  and to permit persons to whom the Software is\n furnished to do so, subject to the following conditions:\n\n The above copyright notice and this permission notice shall be included in\n all copies or substantial portions of the Software.\n\n THE SOFTWARE IS PROVIDED \"AS IS\", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR\n IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,\n FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE\n AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER\n LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,\n OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN\n THE SOFTWARE.\n*/\n\nconst isObject = val => {\n return (\n   typeof val === 'function' || (typeof val === 'object' && val !== null && !Array.isArray(val))\n);\n};\n\nconst isValidKey = key => {\n return key !== '__proto__' && key !== 'constructor' && key !== 'prototype';\n};\n\nfunction
  mixin(target, val, key) {\n const obj = target[key];\n if (isObject(val) && isObject(obj)) {\n   mixinDeep(obj, val);\n } else {\n   target[key] = val;\n }\n}\n\nexport default function mixinDeep(target, ...rest) {\n for (const obj of rest) {\n   if (isObject(obj)) {\n   for (const key in obj) {\n   if (isValidKey(key)) {\n   mixin(target, obj[key], key);\n   }\n   }\n   }\n }\n\n return target;\n}\n","// @flow\nimport React, { useContext, useMemo, type Element, type Context } from 'react';\nimport throwStyledError from '../utils/error';\nimport isFunction from '../utils/isFunction';\n\nexport type Theme = { [key: string]: mixed };\n\ntype ThemeArgument = Theme | ((outerTheme?: Theme) => Theme);\n\ntype Props = {\n children?: Element<any>,\n theme: ThemeArgument,\n};\n\nexport const ThemeContext: Context<Theme | void> = React.createContext();\n\nexport const ThemeConsumer = ThemeContext.Consumer;\n\nfunction mergeTheme(theme: ThemeArgument,
  outerTheme?: Theme): Theme {\n if (!theme) {\n   return throwStyledError(14);\n }\n\n if (isFunction(theme)) {\n   const mergedTheme = theme(outerTheme);\n\n   if (\n   process.env.NODE_ENV !== 'production' &&\n   (mergedTheme === null || Array.isArray(mergedTheme) || typeof mergedTheme !== 'object')\n   ) {\n   return throwStyledError(7);\n   }\n\n   return mergedTheme;\n }\n\n if (Array.isArray(theme) || typeof theme !== 'object') {\n   return throwStyledError(8);\n }\n\n return outerTheme ? { ...outerTheme, ...theme } : theme;\n}\n\n/**\n * Provide a theme to an entire react component tree via context\n */\nexport default function ThemeProvider(props: Props) {\n const outerTheme = useContext(ThemeContext);\n const themeContext = useMemo(() => mergeTheme(props.theme, outerTheme), [\n   props.theme,\n   outerTheme,\n]);\n\n if (!props.children) {\n   return null;\n }\n\n return <ThemeContext.Provider value={themeContext}>{props.children}</ThemeContext.Provider>;\n}\n","//
  @flow\nimport validAttr from '@emotion/is-prop-valid';\nimport hoist from 'hoist-non-react-statics';\nimport React, { createElement, type Ref, useContext } from 'react';\nimport { SC_VERSION } from '../constants';\nimport type {\n Attrs,\n IStyledComponent,\n IStyledStatics,\n RuleSet,\n ShouldForwardProp,\n Target,\n} from '../types';\nimport { checkDynamicCreation } from '../utils/checkDynamicCreation';\nimport createWarnTooManyClasses from '../utils/createWarnTooManyClasses';\nimport determineTheme from '../utils/determineTheme';\nimport { EMPTY_ARRAY, EMPTY_OBJECT } from '../utils/empties';\nimport escape from '../utils/escape';\nimport generateComponentId from '../utils/generateComponentId';\nimport generateDisplayName from '../utils/generateDisplayName';\nimport getComponentName from '../utils/getComponentName';\nimport isFunction from '../utils/isFunction';\nimport isStyledComponent from

```
'../utils/isStyledComponent';\nimport isTag from '../utils/isTag';\nimport
 joinStrings from '../utils/joinStrings';\nimport merge from '../utils/mixinDeep';\nimport ComponentStyle from
'./ComponentStyle';\nimport { useStyleSheet, useStylis } from './StyleSheetManager';\nimport { ThemeContext }
from './ThemeProvider';\n\nconst identifiers = {};\n\n/* We depend on components having unique IDs */\nfunction
generateId(displayName?: string, parentComponentId?: string) {\n  const name = typeof displayName !== 'string' ?
'sc' : escape(displayName);\n  // Ensure that no displayName can lead to duplicate componentIds\n
identifiers[name] = (identifiers[name] || 0) + 1;\n\n  const componentId = `${name}-${generateComponentId(\n    //
SC_VERSION gives us isolation between multiple runtimes on the page at once\n    // this is improved further with
use of the babel plugin \"namespace\" feature\n    SC_VERSION + name + identifiers[name]\n  )}`;\n\n  return
parentComponentId ? `${parentComponentId}-${componentId}` : componentId;\n}\n\nfunction
useResolvedAttrs<Config>(theme:
 any = EMPTY_OBJECT, props: Config, attrs: Attrs) {\n  // NOTE: can't memoize this\n  // returns [context,
resolvedAttrs]\n  // where resolvedAttrs is only the things injected by the attrs themselves\n  const context = {
...props, theme };\n  const resolvedAttrs = {};\n\n  attrs.forEach(attrDef => {\n    let resolvedAttrDef = attrDef;\n
let key;\n\n    if (isFunction(resolvedAttrDef)) {\n      resolvedAttrDef = resolvedAttrDef(context);\n    }\n\n    /*
eslint-disable guard-for-in */\n    for (key in resolvedAttrDef) {\n      context[key] = resolvedAttrs[key] =\n        key
=== 'className'\n          ? joinStrings(resolvedAttrs[key], resolvedAttrDef[key])\n          : resolvedAttrDef[key];\n
}\n    /* eslint-enable guard-for-in */\n  });\n\n  return [context, resolvedAttrs];\n}\n\nfunction
useInjectedStyle<T>(\n  componentStyle: ComponentStyle,\n  isStatic: boolean,\n  resolvedAttrs: T,\n
warnTooManyClasses?: $Call<typeof createWarnTooManyClasses, string, string>\n)
 {\n  const styleSheet = useStyleSheet();\n  const stylis = useStylis();\n\n  const className = isStatic\n    ?
componentStyle.generateAndInjectStyles(EMPTY_OBJECT, styleSheet, stylis)\n    :
componentStyle.generateAndInjectStyles(resolvedAttrs, styleSheet, stylis);\n\n  if (process.env.NODE_ENV !==
'production' && !isStatic && warnTooManyClasses) {\n    warnTooManyClasses(className);\n  }\n\n  return
className;\n}\n\nfunction useStyledComponentImpl(\n  forwardedComponent: IStyledComponent,\n  props:
Object,\n  forwardedRef: Ref<any>,\n  isStatic: boolean\n) {\n  const {\n    attrs: componentAttrs,\n
componentStyle,\n    defaultProps,\n    foldedComponentIds,\n    shouldForwardProp,\n    styledComponentId,\n
target,\n  } = forwardedComponent;\n\n  // NOTE: the non-hooks version only subscribes to this when
!componentStyle.isStatic,\n  // but that'd be against the rules-of-hooks. We could be naughty and do it anyway as it\n
// should be an immutable value, but behave for now.\n
 const theme = determineTheme(props, useContext(ThemeContext), defaultProps);\n\n  const [context, attrs] =
useResolvedAttrs(theme || EMPTY_OBJECT, props, componentAttrs);\n\n  const generatedClassName =
useInjectedStyle(\n    componentStyle,\n    isStatic,\n    context,\n    process.env.NODE_ENV !== 'production' ?
forwardedComponent.warnTooManyClasses : undefined\n  );\n\n  const refToForward = forwardedRef;\n\n  const
elementToBeCreated: Target = attrs.$as || props.$as || attrs.as || props.as || target;\n\n  const isTargetTag =
isTag(elementToBeCreated);\n  const computedProps = attrs !== props ? { ...props, ...attrs } : props;\n  const
propsForElement = {};\n\n  // eslint-disable-next-line guard-for-in\n  for (const key in computedProps) {\n    if
(key[0] === '$' || key === 'as') continue;\n    else if (key === 'forwardedAs') {\n      propsForElement.as =
computedProps[key];\n    } else if (\n      shouldForwardProp\n        ? shouldForwardProp(key, validAttr,
elementToBeCreated)\n
      : isTargetTag\n        ? validAttr(key)\n        : true\n    ) {\n      // Don't pass through non HTML tags through to
HTML elements\n      propsForElement[key] = computedProps[key];\n    }\n  }\n\n  if (props.style && attrs.style
!== props.style) {\n    propsForElement.style = { ...props.style, ...attrs.style };\n  }\n\n  propsForElement.className
= Array.prototype\n    .concat(\n      foldedComponentIds,\n      styledComponentId,\n      generatedClassName !==
styledComponentId ? generatedClassName : null,\n      props.className,\n      attrs.className\n    )\n
.filter(Boolean)\n    .join(' ');\n\n  propsForElement.ref = refToForward;\n\n  return
createElement(elementToBeCreated, propsForElement);\n}\n\nexport default function createStyledComponent(\n
target: $PropertyType<IStyledComponent, 'target'>,\n  options: {\n    attrs?: Attrs,\n    componentId: string,\n
```

displayName?: string,\n parentComponentId?: string,\n shouldForwardProp?: ShouldForwardProp,\n },\n rules: RuleSet\n) {\n const isTargetStyledComp = isStyledComponent(target);\n const isCompositeComponent = !isTag(target);\n\n const {\n attrs = EMPTY_ARRAY,\n componentId = generateId(options.displayName, options.parentComponentId),\n displayName = generateDisplayName(target),\n } = options;\n\n const styledComponentId =\n options.displayName && options.componentId\n ? `${escape(options.displayName)}-${options.componentId}`\n : options.componentId || componentId;\n\n // fold the underlying StyledComponent attrs up (implicit extend)\n const finalAttrs =\n isTargetStyledComp && ((target: any): IStyledComponent).attrs\n ? Array.prototype.concat(((target: any): IStyledComponent).attrs, attrs).filter(Boolean)\n : attrs;\n\n // eslint-disable-next-line prefer-destructuring\n let shouldForwardProp = options.shouldForwardProp;\n\n if (isTargetStyledComp && target.shouldForwardProp) {\n if (options.shouldForwardProp) {\n // compose nested shouldForwardProp
calls\n shouldForwardProp = (prop, filterFn, elementToBeCreated) =>\n ((((target: any): IStyledComponent).shouldForwardProp: any): ShouldForwardProp)(\n prop,\n filterFn,\n elementToBeCreated\n) &&\n ((options.shouldForwardProp: any): ShouldForwardProp)(prop, filterFn, elementToBeCreated);\n } else {\n // eslint-disable-next-line prefer-destructuring\n shouldForwardProp = ((target: any): IStyledComponent).shouldForwardProp;\n }\n }\n\n const componentStyle = new ComponentStyle(\n rules,\n styledComponentId,\n isTargetStyledComp ? ((target: Object).componentStyle: ComponentStyle) : undefined\n);\n\n // statically styled-components don't need to build an execution context object,\n // and shouldn't be increasing the number of class names\n const isStatic = componentStyle.isStatic && attrs.length === 0;\n\n /**\n * forwardRef creates a new interim component, which we'll take advantage of\n * instead of extending ParentComponent to create _another_ interim class\n */\n let WrappedStyledComponent: IStyledComponent;\n\n const forwardRef = (props, ref) =>\n // eslint-disable-next-line\n useStyledComponentImpl(WrappedStyledComponent, props, ref, isStatic);\n\n forwardRef.displayName = displayName;\n\n WrappedStyledComponent = ((React.forwardRef(forwardRef): any): IStyledComponent);\n WrappedStyledComponent.attrs = finalAttrs;\n WrappedStyledComponent.componentStyle = componentStyle;\n WrappedStyledComponent.displayName = displayName;\n WrappedStyledComponent.shouldForwardProp = shouldForwardProp;\n\n // this static is used to preserve the cascade of static classes for component selector\n // purposes; this is especially important with usage of the css prop\n WrappedStyledComponent.foldedComponentIds = isTargetStyledComp\n ? Array.prototype.concat(\n ((target: any): IStyledComponent).foldedComponentIds,\n ((target: any): IStyledComponent).styledComponentId\n)\n : EMPTY_ARRAY;\n\n WrappedStyledComponent.styledComponentId = styledComponentId;\n\n // fold the underlying StyledComponent target up since we folded the styles\n WrappedStyledComponent.target = isTargetStyledComp\n ? ((target: any): IStyledComponent).target\n : target;\n\n WrappedStyledComponent.withComponent = function withComponent(tag: Target) {\n const { componentId: previousComponentId, ...optionsToCopy } = options;\n\n const newComponentId =\n previousComponentId &&\n `${previousComponentId}-${isTag(tag) ? tag : escape(getComponentName(tag))}`;\n\n const newOptions = {\n ...optionsToCopy,\n attrs: finalAttrs,\n componentId: newComponentId,\n };\n\n return createStyledComponent(tag, newOptions, rules);\n };\n\n Object.defineProperty(WrappedStyledComponent, 'defaultProps', {\n get() {\n return this._foldedDefaultProps;\n },\n\n set(obj) {\n this._foldedDefaultProps = isTargetStyledComp\n ? merge({}, ((target: any): IStyledComponent).defaultProps, obj)\n : obj;\n },\n });\n\n if (process.env.NODE_ENV !== 'production') {\n checkDynamicCreation(displayName, styledComponentId);\n\n WrappedStyledComponent.warnTooManyClasses = createWarnTooManyClasses(\n displayName,\n styledComponentId\n);\n }\n\n // If the Object prototype is frozen, the \"toString\" property is non-writable. This means that any objects which inherit this property\n // cannot have the property changed using an assignment. If using strict mode, attempting that will cause an error. If not using strict\n // mode, attempting that will be silently ignored.\n // However, we can still explicitly shadow the prototype's \"toString\" property by defining a new \"toString\" property on this object.\n Object.defineProperty(WrappedStyledComponent, 'toString', { value: () =>

`.${WrappedStyledComponent.styledComponentId}` });\n\n if (isCompositeComponent) {\n   hoist<\n   IStyledStatics,\n $PropertyType<IStyledComponent, 'target'>,\n   { [key: $Keys<IStyledStatics>]: true }\n   >(WrappedStyledComponent, ((target: any): $PropertyType<IStyledComponent, 'target'>), {\n   // all SC-specific things should not be hoisted\n   attrs: true,\n   componentStyle: true,\n   displayName: true,\n   foldedComponentIds: true,\n   shouldForwardProp: true,\n   styledComponentId: true,\n   target: true,\n   withComponent: true,\n   });\n }\n\n return WrappedStyledComponent;\n}\n","// @flow\nimport type { IStyledComponent } from '../types';\nimport getComponentName from './getComponentName';\nimport isTag from './isTag';\n\nexport default function generateDisplayName(\n target: $PropertyType<IStyledComponent, 'target'>\n): string {\n return isTag(target) ? `styled.${target}` : `Styled(${getComponentName(target)})`;\n}\n","/**\n * Convenience function for joining strings to form className chains\n */\nexport default function joinStrings(a: ?String, b: ?String): ?String {\n return a && b ? `${a} ${b}` : a || b;\n}\n","// @flow\n\nexport const LIMIT = 200;\n\nexport default (displayName: string, componentId: string) => {\n let generatedClasses = {};\n let warningSeen = false;\n\n return (className: string) => {\n   if (!warningSeen) {\n   generatedClasses[className] = true;\n   if (Object.keys(generatedClasses).length >= LIMIT) {\n   // Unable to find latestRule in test environment.\n   /* eslint-disable no-console, prefer-template */\n   const parsedIdString = componentId ? ` with the id of \"${componentId}\"` : '';\n\n   console.warn(\n   `Over ${LIMIT} classes were generated for component ${displayName}${parsedIdString}.\\n` +\n   'Consider using the attrs method, together with a style object for frequently changed styles.\\n' +\n   'Example:\\n' +\n   ' const Component = styled.div.attrs(props => ({\\n' +\n   '   style: {\\n' +\n   '   background: props.background,\\n' +\n   '   },\\n' +\n   ' }))`width: 100%;`\\n\\n' +\n   ' <Component />'\n   );\n   warningSeen = true;\n   generatedClasses = {};\n   }\n   }\n };\n};\n","// @flow\n// Thanks to ReactDOMFactories for this handy list!\n\nexport default [\n 'a',\n 'abbr',\n 'address',\n 'area',\n 'article',\n 'aside',\n 'audio',\n 'b',\n 'base',\n 'bdi',\n 'bdo',\n 'big',\n 'blockquote',\n 'body',\n 'br',\n 'button',\n 'canvas',\n 'caption',\n 'cite',\n 'code',\n 'col',\n 'colgroup',\n 'data',\n 'datalist',\n 'dd',\n 'del',\n 'details',\n 'dfn',\n 'dialog',\n 'div',\n 'dl',\n 'dt',\n 'em',\n 'embed',\n 'fieldset',\n 'figcaption',\n 'figure',\n 'footer',\n 'form',\n 'h1',\n 'h2',\n 'h3',\n 'h4',\n 'h5',\n 'h6',\n 'head',\n 'header',\n 'hgroup',\n 'hr',\n 'html',\n 'i',\n 'iframe',\n 'img',\n 'input',\n 'ins',\n 'kbd',\n 'keygen',\n 'label',\n 'legend',\n 'li',\n 'link',\n 'main',\n 'map',\n 'mark',\n 'marquee',\n 'menu',\n 'menuitem',\n 'meta',\n 'meter',\n 'nav',\n 'noscript',\n 'object',\n 'ol',\n 'optgroup',\n 'option',\n 'output',\n 'p',\n 'param',\n 'picture',\n 'pre',\n 'progress',\n 'q',\n 'rp',\n 'rt',\n 'ruby',\n 's',\n 'samp',\n 'script',\n 'section',\n 'select',\n 'small',\n 'source',\n 'span',\n 'strong',\n 'style',\n 'sub',\n 'summary',\n 'sup',\n 'table',\n 'tbody',\n 'td',\n 'textarea',\n 'tfoot',\n 'th',\n 'thead',\n 'time',\n 'title',\n 'tr',\n 'track',\n 'u',\n 'ul',\n 'var',\n 'video',\n 'wbr',\n\n // SVG\n 'circle',\n 'clipPath',\n 'defs',\n 'ellipse',\n 'foreignObject',\n 'g',\n 'image',\n 'line',\n 'linearGradient',\n 'marker',\n 'mask',\n 'path',\n 'pattern',\n 'polygon',\n 'polyline',\n 'radialGradient',\n 'rect',\n 'stop',\n 'svg',\n 'text',\n 'textPath',\n 'tspan',\n];\n","// @flow\nimport constructWithOptions from './constructWithOptions';\nimport StyledComponent from '../models/StyledComponent';\nimport domElements from '../utils/domElements';\n\nimport type { Target } from '../types';\n\nconst styled = (tag: Target) => constructWithOptions(StyledComponent, tag);\n\n// Shorthands for all valid HTML Elements\ndomElements.forEach(domElement => {\n styled[domElement] = styled(domElement);\n});\n\nexport default styled;\n","// @flow\nimport { isValidElementType } from 'react-is';\nimport css from './css';\nimport throwStyledError from '../utils/error';\nimport { EMPTY_OBJECT } from '../utils/empties';\n\nimport type { Target } from '../types';\n\nexport default function constructWithOptions(\n componentConstructor: Function,\n tag: Target,\n options: Object = EMPTY_OBJECT\n) {\n if (!isValidElementType(tag)) {\n   return throwStyledError(1, String(tag));\n }\n\n /* This is callable directly as a template function */\n // $FlowFixMe: Not typed to avoid destructuring arguments\n const templateFunction = (...args) => componentConstructor(tag, options, css(...args));\n\n /* If config methods are called, wrap up a new template function and merge options */\n templateFunction.withConfig = config =>

constructWithOptions(componentConstructor, tag, { ...options, ...config });\n\n /* Modify/inject new props at runtime */\n templateFunction.attrs = attrs =>\n   constructWithOptions(componentConstructor, tag, {\n ...options,\n   attrs: Array.prototype.concat(options.attrs, attrs).filter(Boolean),\n   });\n\n return templateFunction;\n}\n","// @flow\nimport StyleSheet from '../sheet';\nimport type { RuleSet, Stringifier } from '../types';\nimport flatten from '../utils/flatten';\nimport isStaticRules from '../utils/isStaticRules';\n\nexport default class GlobalStyle {\n componentId: string;\n\n isStatic: boolean;\n\n rules: RuleSet;\n\n constructor(rules: RuleSet, componentId: string) {\n   this.rules = rules;\n   this.componentId = componentId;\n   this.isStatic = isStaticRules(rules);\n\n   // pre-register the first instance to ensure global styles\n   // load before component ones\n   StyleSheet.registerId(this.componentId + 1);\n }\n\n createStyles(\n   instance: number,\n   executionContext: Object,\n   styleSheet: StyleSheet,\n   stylis: Stringifier\n) {\n   const flatCSS = flatten(this.rules, executionContext, styleSheet, stylis);\n   const css = stylis(flatCSS.join(''), '');\n   const id = this.componentId + instance;\n\n   // NOTE: We use the id as a name as well, since these rules never change\n   styleSheet.insertRules(id, id, css);\n }\n\n removeStyles(instance: number, styleSheet: StyleSheet) {\n   styleSheet.clearRules(this.componentId + instance);\n }\n\n renderStyles(\n   instance: number,\n   executionContext: Object,\n   styleSheet: StyleSheet,\n   stylis: Stringifier\n) {\n   if (instance > 2) StyleSheet.registerId(this.componentId + instance);\n\n   // NOTE: Remove old styles, then inject the new ones\n   this.removeStyles(instance, styleSheet);\n   this.createStyles(instance, executionContext, styleSheet, stylis);\n }\n}\n","// @flow\nimport React, { useContext, useLayoutEffect, useRef } from 'react';\nimport { STATIC_EXECUTION_CONTEXT } from '../constants';\nimport GlobalStyle from '../models/GlobalStyle';\nimport { useStyleSheet, useStylis } from '../models/StyleSheetManager';\nimport { ThemeContext } from '../models/ThemeProvider';\nimport type { Interpolation } from '../types';\nimport { checkDynamicCreation } from '../utils/checkDynamicCreation';\nimport determineTheme from '../utils/determineTheme';\nimport generateComponentId from '../utils/generateComponentId';\nimport css from './css';\n\ndeclare var __SERVER__: boolean;\n\ntype GlobalStyleComponentPropsType = Object;\n\nexport default function createGlobalStyle(\n strings: Array<string>,\n ...interpolations: Array<Interpolation>\n) {\n const rules = css(strings, ...interpolations);\n const styledComponentId = `sc-global-${generateComponentId(JSON.stringify(rules))}`;\n const globalStyle = new GlobalStyle(rules, styledComponentId);\n\n if (process.env.NODE_ENV !== 'production') {\n   checkDynamicCreation(styledComponentId);\n }\n\n function GlobalStyleComponent(props: GlobalStyleComponentPropsType) {\n   const styleSheet = useStyleSheet();\n   const stylis = useStylis();\n   const theme = useContext(ThemeContext);\n   const instanceRef = useRef(styleSheet.allocateGSInstance(styledComponentId));\n\n   const instance = instanceRef.current;\n\n   if (process.env.NODE_ENV !== 'production' && React.Children.count(props.children)) {\n   // eslint-disable-next-line no-console\n   console.warn(\n   `The global style component ${styledComponentId} was given child JSX. createGlobalStyle does not render children.`\n   );\n   }\n\n   if (\n   process.env.NODE_ENV !== 'production' &&\n   rules.some(rule => typeof rule === 'string' && rule.indexOf('@import') !== -1)\n   ) {\n   // eslint-disable-next-line no-console\n   console.warn(\n   `Please do not use @import CSS syntax in createGlobalStyle at this time, as the CSSOM APIs we use in production do not handle it well. Instead, we recommend using a library such as react-helmet to inject a typical <link> meta tag to the stylesheet, or simply embedding it manually in your index.html <head> section for a simpler app.`\n   );\n   }\n\n   if (styleSheet.server) {\n   renderStyles(instance, props, styleSheet, theme, stylis);\n   }\n\n   if (!__SERVER__) {\n   // this conditional is fine because it is compiled away for the relevant builds during minification,\n   // resulting in a single unguarded hook call\n   // eslint-disable-next-line react-hooks/rules-of-hooks\n   useLayoutEffect(() => {\n   if (!styleSheet.server) {\n   renderStyles(instance, props, styleSheet, theme, stylis);\n   return () => globalStyle.removeStyles(instance, styleSheet);\n   }\n   }, [instance, props, styleSheet, theme, stylis]);\n   }\n\n   return null;\n }\n\n function renderStyles(instance, props, styleSheet, theme, stylis) {\n   if (globalStyle.isStatic) {\n   globalStyle.renderStyles(instance, STATIC_EXECUTION_CONTEXT, styleSheet, stylis);\n   } else {\n   const

```
context = {\n ...props,\n theme: determineTheme(props, theme, GlobalStyleComponent.defaultProps),\n };\n\n globalStyle.renderStyles(instance, context, styleSheet, stylis);\n }\n }\n\n // $FlowFixMe\n return React.memo(GlobalStyleComponent);\n}\n","// @flow\n\nimport css from './css';\nimport generateComponentId from '../utils/generateComponentId';\nimport Keyframes from '../models/Keyframes';\n\nimport type { Interpolation, Styles } from '../types';\n\nexport default function keyframes(\n strings: Styles,\n ...interpolations: Array<Interpolation>\n): Keyframes {\n /* Warning if you've used keyframes on React Native */\n if (\n process.env.NODE_ENV
 !== 'production' &&\n typeof navigator !== 'undefined' &&\n navigator.product === 'ReactNative'\n ) {\n // eslint-disable-next-line no-console\n console.warn(\n '`keyframes` cannot be used on ReactNative, only on the web. To do animation in ReactNative please use Animated.'\n );\n }\n\n const rules = css(strings, ...interpolations).join('');\n const name = generateComponentId(rules);\n return new Keyframes(name, rules);\n}\n","// @flow\n/* eslint-disable no-underscore-dangle */\nimport React from 'react';\nimport { IS_BROWSER, SC_ATTR, SC_ATTR_VERSION, SC_VERSION } from '../constants';\nimport throwStyledError from '../utils/error';\nimport getNonce from '../utils/nonce';\nimport StyleSheet from '../sheet';\nimport StyleSheetManager from './StyleSheetManager';\n\ndeclare var __SERVER__: boolean;\n\nconst CLOSING_TAG_R = /^\\s*<\\/[a-z]/i;\n\nexport default class ServerStyleSheet {\n isStreaming: boolean;\n\n instance: StyleSheet;\n\n sealed: boolean;\n\n
 constructor() {\n this.instance = new StyleSheet({ isServer: true });\n this.sealed = false;\n }\n\n _emitSheetCSS = (): string => {\n const css = this.instance.toString();\n if (!css) return '';\n\n const nonce = getNonce();\n const attrs = [nonce && `nonce=\"${nonce}\"`, `${SC_ATTR}=\"true\"`, `${SC_ATTR_VERSION}=\"${SC_VERSION}\"`];\n const htmlAttr = attrs.filter(Boolean).join(' ');\n\n return `<style ${htmlAttr}>${css}</style>`;\n };\n\n collectStyles(children: any) {\n if (this.sealed) {\n return throwStyledError(2);\n }\n\n return <StyleSheetManager sheet={this.instance}>{children}</StyleSheetManager>;\n }\n\n getStyleTags = (): string => {\n if (this.sealed) {\n return throwStyledError(2);\n }\n\n return this._emitSheetCSS();\n };\n\n getStyleElement = () => {\n if (this.sealed) {\n return throwStyledError(2);\n }\n\n const props = {\n [SC_ATTR]: '',\n [SC_ATTR_VERSION]: SC_VERSION,\n
 dangerouslySetInnerHTML: {\n __html: this.instance.toString(),\n },\n };\n\n const nonce = getNonce();\n if (nonce) {\n (props: any).nonce = nonce;\n }\n\n // v4 returned an array for this fn, so we'll do the same for v5 for backward compat\n return [<style {...props} key=\"sc-0-0\" />];\n };\n\n // eslint-disable-next-line consistent-return\n interleaveWithNodeStream(input: any) {\n if (!__SERVER__ || IS_BROWSER) {\n return throwStyledError(3);\n } else if (this.sealed) {\n return throwStyledError(2);\n }\n\n if (__SERVER__) {\n this.seal();\n\n // eslint-disable-next-line global-require\n const { Readable, Transform } = require('stream');\n\n const readableStream: Readable = input;\n const { instance: sheet, _emitSheetCSS } = this;\n\n const transformer = new Transform({\n transform: function appendStyleChunks(chunk, /* encoding */ _, callback) {\n // Get the chunk and retrieve
 the sheet's CSS as an HTML chunk,\n // then reset its rules so we get only new ones for the next chunk\n const renderedHtml = chunk.toString();\n const html = _emitSheetCSS();\n\n sheet.clearTag();\n\n // prepend style html to chunk, unless the start of the chunk is a\n // closing tag in which case append right after that\n if (CLOSING_TAG_R.test(renderedHtml)) {\n const endOfClosingTag = renderedHtml.indexOf('>') + 1;\n const before = renderedHtml.slice(0, endOfClosingTag);\n const after = renderedHtml.slice(endOfClosingTag);\n\n this.push(before + html + after);\n } else {\n this.push(html + renderedHtml);\n }\n\n callback();\n },\n });\n\n readableStream.on('error', err => {\n // forward the error to the transform stream\n transformer.emit('error', err);\n });\n\n return readableStream.pipe(transformer);\n
 }\n }\n\n seal = () => {\n this.sealed = true;\n };\n}\n","// @flow\nimport React, { useContext, type AbstractComponent } from 'react';\nimport hoistStatics from 'hoist-non-react-statics';\nimport { ThemeContext } from '../models/ThemeProvider';\nimport determineTheme from '../utils/determineTheme';\nimport
```

getComponentName from '../utils/getComponentName';\n\n// NOTE: this would be the correct signature:\n// export default <Config: { theme?: any }, Instance>(\n// Component: AbstractComponent<Config, Instance>\n//): AbstractComponent<$Diff<Config, { theme?: any }> & { theme?: any }, Instance>\n//\n// but the old build system tooling doesn't support the syntax\n\nexport default (Component: AbstractComponent<*, *>) => {\n // $FlowFixMe This should be React.forwardRef<Config, Instance>\n const WithTheme = React.forwardRef((props, ref) => {\n   const theme = useContext(ThemeContext);\n   // $FlowFixMe defaultProps isn't declared so it can be inferrable\n   const {
 defaultProps } = Component;\n   const themeProp = determineTheme(props, theme, defaultProps);\n\n   if (process.env.NODE_ENV !== 'production' && themeProp === undefined) {\n   // eslint-disable-next-line no-console\n   console.warn(\n   `[withTheme] You are not using a ThemeProvider nor passing a theme prop or a theme in defaultProps in component class \"${getComponentName(\n          Component\n        )}\"`\n   );\n   }\n\n
 return <Component {...props} theme={themeProp} ref={ref} />;\n });\n\n hoistStatics(WithTheme, Component);\n\n WithTheme.displayName = `WithTheme(${getComponentName(Component)})`;\n\n return WithTheme;\n};\n","// @flow\nimport { useContext } from 'react';\nimport { ThemeContext } from '../models/ThemeProvider';\n\nconst useTheme = () => useContext(ThemeContext);\n\nexport default useTheme;\n","// @flow\n/* eslint-disable */\n\nimport StyleSheet from './sheet';\nimport { masterSheet } from './models/StyleSheetManager';\n\nexport const __PRIVATE__
 = {\n StyleSheet,\n masterSheet,\n};\n","// @flow\n/* Import singletons */\nimport isStyledComponent from './utils/isStyledComponent';\nimport css from './constructors/css';\nimport createGlobalStyle from './constructors/createGlobalStyle';\nimport keyframes from './constructors/keyframes';\nimport ServerStyleSheet from './models/ServerStyleSheet';\nimport { SC_VERSION } from './constants';\n\nimport StyleSheetManager, {\n StyleSheetContext,\n StyleSheetConsumer,\n} from './models/StyleSheetManager';\n\n/* Import components */\nimport ThemeProvider, { ThemeContext, ThemeConsumer } from './models/ThemeProvider';\n\n/* Import Higher Order Components */\nimport withTheme from './hoc/withTheme';\n\n/* Import hooks */\nimport useTheme from './hooks/useTheme';\n\ndeclare var __SERVER__: boolean;\n\n/* Warning if you've imported this file on React Native */\nif (\n process.env.NODE_ENV !== 'production' &&\n typeof navigator !== 'undefined' &&\n navigator.product === 'ReactNative'\n)
 {\n // eslint-disable-next-line no-console\n console.warn(\n   \"It looks like you've imported 'styled-components' on React Native.\\n\\n\" +\n   \"Perhaps you're looking to import 'styled-components/native'?\\n\\n\" +\n   'Read more about this at https://www.styled-components.com/docs/basics#react-native\n);\n}\n\n/* Warning if there are several instances of styled-components */\nif (process.env.NODE_ENV !== 'production' && process.env.NODE_ENV !== 'test' && typeof window !== 'undefined') {\n window['__styled-components-init__'] = window['__styled-components-init__'] || 0;\n\n if (window['__styled-components-init__'] === 1) {\n   // eslint-disable-next-line no-console\n   console.warn(\n   \"It looks like there are several instances of 'styled-components' initialized in this application. \" +\n   'This may cause dynamic styles to not render properly, errors during the rehydration process, ' +\n   'a missing theme prop, and makes your application bigger without
 good reason.\\n\\n' +\n   'See https://s-c.sh/2BAXzed for more info.'\n   );\n }\n\n window['__styled-components-init__'] += 1;\n}\n\n/* Export everything */\nexport * from './secretInternals';\nexport {\n createGlobalStyle,\n css,\n isStyledComponent,\n keyframes,\n ServerStyleSheet,\n StyleSheetConsumer,\n StyleSheetContext,\n StyleSheetManager,\n ThemeConsumer,\n ThemeContext,\n ThemeProvider,\n useTheme,\n SC_VERSION as version,\n withTheme,\n};\n"],"names":["strings","interpolations","result","i","len","length","push","x","toString","Object","prototype","call","typeOf","EMPTY_ARRAY","freeze","EMPTY_OBJECT","isFunction","test","getComponentName","target","process","env","NODE_ENV","displayName","name","isStyledComponent","styledComponentId","SC_ATTR","REACT_APP_SC_ATTR","SC_VERSION","__VERSION__","IS_BROWSER","window","DISABLE_SPEEDY","Boolean","SC_DISABLE_SPEEDY","REACT_APP_SC_DISABLE_SPEEDY","STATIC_EXECUTION_CONTEXT","ERRORS","format","a","b","c","arguments","forEach","d","replace","throwStyledComponentsError","code","Error","join","trim","DefaultGroupedTag","tag","groupSizes","Uint32Array","indexOfGroup","group"

,"index","this","insertRules","rules","oldBuffer","oldSize","newSize","throwStyledError","set","ruleIndex","l","insertRule","clearGroup","startIndex","endIndex","deleteRule","getGroup","css","getRule","groupIDRegister","Map","reverseRegister","nextFreeGroup","getGroupForId","id","has","get","getIdForGroup","setGroupForId","SELECTOR","MARKER_RE","RegExp","rehydrateNamesFromContent","sheet","content","names","split","registerName","rehydrateSheetFromTag","style","parts","textContent","part","marker","match","parseInt","getTag","getNonce","__webpack_nonce__","makeStyleTag","head","document","parent","createElement","prevStyle","childNodes","child","nodeType","hasAttribute","findLastStyleTag","nextSibling","undefined","setAttribute","nonce","insertBefore","CSSOMTag","element","appendChild","createTextNode","styleSheets","ownerNode","getSheet","rule","_error","cssRules","cssText","TextTag","nodes","node","refNode","removeChild","VirtualTag","_target","splice","SHOULD_REHYDRATE","defaultOptions","isServer","useCSSOMInjection","StyleSheet","options","globalStyles","gs","server","querySelectorAll","getAttribute","parentNode","rehydrateSheet","registerId","reconstructWithOptions","withNames","allocateGSInstance","hasNameForId","add","groupNames","Set","clearNames","clear","clearRules","clearTag","size","selector","outputSheet","AD_REPLACER_R","getAlphabeticChar","String","fromCharCode","generateAlphabeticName","Math","abs","phash","h","charCodeAt","hash","isStaticRules","SEED","ComponentStyle","componentId","baseStyle","staticRulesId","isStatic","baseHash","generateAndInjectStyles","executionContext","styleSheet","stylis","cssStatic","flatten","generateName","cssStaticFormatted","dynamicHash","partRule","partChunk","partString","Array","isArray","cssFormatted","COMMENT_REGEX","COMPLEX_SELECTOR_PREFIX","createStylisInstance","_componentId","_selector","_selectorRegexp","_consecutiveSelfRefRegExp","plugins","Stylis","parsingRules","parseRulesPlugin","toSheet","block","e","context","selectors","parents","line","column","ns","depth","at","delimiter","insertRulePlugin","selfReferenceReplacer","offset","string","indexOf","stringifyRules","prefix","flatCSS","cssStr","use","_","lastIndexOf","parsedRules","reduce","acc","plugin","StyleSheetContext","React","createContext","StyleSheetConsumer","Consumer","StylisContext","masterSheet","masterStylis","useStyleSheet","useContext","useStylis","StyleSheetManager","props","useState","stylisPlugins","setPlugins","contextStyleSheet","useMemo","disableCSSOMInjection","disableVendorPrefixes","useEffect","shallowequal","Provider","value","Children","only","children","Keyframes","inject","stylisInstance","resolvedName","_this","getName","uppercaseCheck","uppercasePattern","msPattern","prefixAndLowerCase","char","toLowerCase","hyphenateStyleName","isFalsish","chunk","ruleSet","isReactComponent","isElement","console","warn","isPlainObject","objToCssArray","obj","prevKey","key","hasOwnProperty","isCss","hyphenate","unitless","startsWith","addTag","arg","styles","interleave","invalidHookCallRe","seen","checkDynamicCreation","message","originalConsoleError","error","didNotCallInvalidHook","consoleErrorMessage","consoleErrorArgs","useRef","providedTheme","defaultProps","theme","escapeRegex","dashesAtEnds","escape","str","isTag","charAt","isObject","val","isValidKey","mixin","mixinDeep","rest","ThemeContext","ThemeConsumer","ThemeProvider","outerTheme","themeContext","mergedTheme","mergeTheme","identifiers","createStyledComponent","isTargetStyledComp","isCompositeComponent","attrs","parentComponentId","generateComponentId","generateId","generateDisplayName","finalAttrs","concat","filter","shouldForwardProp","prop","filterFn","elementToBeCreated","WrappedStyledComponent","componentStyle","forwardRef","ref","forwardedComponent","forwardedRef","componentAttrs","foldedComponentIds","resolvedAttrs","attrDef","resolvedAttrDef","useResolvedAttrs","determineTheme","generatedClassName","warnTooManyClasses","className","useInjectedStyle","refToForward","$as","as","isTargetTag","computedProps","propsForElement","validAttr","withComponent","previousComponentId","optionsToCopy","newComponentId","defineProperty","_foldedDefaultProps","merge","generatedClasses","warningSeen","keys","parsedIdString","createWarnTooManyClasses","hoist","styled","constructWithOptions","componentConstructor","isValidElementType","templateFunction","withConfig","config","StyledComponent","domElement","GlobalStyle","createStyles","instance","removeStyles","renderStyles","createGlobalStyle","JSON","stringify","globalStyle","GlobalStyleComponent","current","count","some","useLayoutEffect","memo","keyframes","navigator","product","ServerStyleSheet","_emitSheetCSS","SC_ATTR_VERSION","getStyleTags","sealed","getStyleElement","dangerouslySetInnerHTML","__html","seal","collectStyles","interleaveWithNodeStream","input","Component","WithTheme","themeProp","hoistStatics","useTheme","__PRIVATE__"],"mappings":"qkBAGA,eACEA,EACAC,EACAC,EACAC

,GAC6D,qBAAnEA,EAAEC,SAAWD,EAAEC,WAAaC,OAAOC,UAAUF,SAASG,KAAKJ,MAC3DK,EAAOL,I
CNGM,EAAcJ,OAAOK,OAAO,IAC5BC,EAAeN,OAAOK,OAAO,ICD3B,SAASE,EAAWC,SACV,mBAATA,E
CCD,SAASC,EACtBC,SAG4B,eAAzBC,QAAQC,IAAIC,UAA8C,iBAAXH,GAAuBG,GAAEvEA,EAAOI,aAEPJ,
EAAOK,MACP,YCXW,SAASC,EAAkBN,UACjCA,GAA8C,iBAA7BA,BCG1B,IAAMC,EACJ,OAAOK,
ZP,cACiB,IAAhBA,QAAQC,MACdD,QAAQC,IAAIC,mBAAqBC,QAAQC,IAAIM,UAChD,cAIWE,EAAAaC,SA
GbC,EAA+B,oBAAXC,QAA0BA,OAAOC,OAAOC,KAAKF,OAAOC,QAAUA,OAAOC,KAAOC,SAAS,cf,c
AAkD,IAAhBA,QAAQC,WACdC,EAAIe,5CD,QAAQC,IAAIe,6BACyBC,KAAA5ChB,QAAQC,IAAIe,4BACzCC,KAAA5
ChB,QAAQC,IAAIe,6BAAyBC,KAAA5ChB,QAAQC,IAAIe,iCAC2B,IAAlChB,QAAQC,IAAIc,mBAAuE,KAAlCf,QAAQC,I
AAIc,kBAClC,UAAlCf,QAAQC,IAAIc,mBAAuE,KAAlCf,QAAQC,IAAIc,mBAAwEG,KAAA5CW,eAAAzB

AAUjB,EAAaxF,GAG7CyG,EAAQC,YAAYhB,SAASiB,eAAe,UAEvCnC,MDae,SAACtC,MACnBA,EAAIsC,aACGtC,EAAIsC,cAIPoC,EAAgBlB,SAAhBkB,YACC5H,EAAI,EAAGiE,EAAI2D,EAAY1H,OAAQF,EAAIiE,EAAGjE,IAAK,KAC5CwF,EAAQoC,EAAY5H,MACtBwF,EAAMqC,YAAc3E,SACbsC,EAIb1B,EAAiB,IC3BFgE,CAASL,QACjBvH,OAAS,6BAGhBgE,WAAA,SAAWwD,EAAmBC,GAC1B,IAAIC,EAAQ,EAAGC,EAAMH,EAAkBzH,OAAQ2H,EAAQC,EAAKD,IAAS,CACjE,IAAIE,EAAIJ,EAAkBE,GAC1B,GAAIE,EAAEC,SAAWJ,EAAkB,OAAOG,EAC1CF,GAASE,EAAEC,QAEf,OAAO,GAGXC,WAAA,SAAWC,GACP,IAAIC,EAAQ,EAAGC,EAAQ,EAAGC,EAAQ,EAAG

AhB6H,YAEF3F,EAAQ,MAEVlC,KAAK8H,WACP5F,EAAMvF,KAAKqD,KAAK8H,UAAUI,wBAAwBC,EAAkBC,EAAAYC,IAI9ErI,KAAKgI,WAAaK,EAAOZ,QACvBzH,KAAK+H,eAAiBK,EAAWhC,aAAayB,EAAa7H,KAAK+H,eAClE7F,EAAMvF,KAAKqD,KAAK+H,mBACXACX,KACCO,EAAYC,GAAQvI,KAAKE,MAAOiEAAkBC,EAAAYC,GAAQ9I,KAAKIAC3E1B,EAAO2K,EAAalB,GAAMtH,KAAKiI,SAAUK,KAAAe,OAEzDF,EAAWhC,aAAayB,EAAahK,GAAOC,EAAWhC,aAAayB,EAAa4K,EAAAC,EAAAC,EAAAC

AAwB1F,GACtB0F,EACA9F,EACAC,EACAiF,MAEIvE,MAAMC,QAAQkF,GAAQ,SAGY1R,EAF9B2R,EAAU
,GAEP1R,EAAI,EAAGC,EAAMwR,EAAMvR,OAAgBF,EAAIC,EAAKD,GAAK,EAGzC,MAFfD,EASgM,GA
AQ0F,EAAMzR,GAAI2L,EAAkBC,EAAYiF,MAGhDvE,MAAMC,QAAQxM,GAAS2R,EAAQvR,WAARuR,EA
AgB3R,GAC3C2R,EAAQvR,KAAKJ,WAGb2R,KAGLF,GAAUC,SACL,MAILnQ,EAAkBmQ,aACTA,EAAMlQ
,qBAIfV,EAAW4Q,GAAQ,IC9DL,mBAFwB3Q,EDiEhB2Q,IC7DtB3Q,EAAKP,WACFO,EAAKP,UAAUoR,mB
D4DchG,EAa3B,OAAO8F,MAZN1R,EAAS0R,EAAM9F,SAEQ,eAAzB1K,QAAQC,IAAIC,UAA6B7ByQ,EAAU7
R,IAErD8R,QAAQC,KACH/Q,EACD0Q,uLAKC1F,GAAQhM,EAAQ4L,EAAkBC,EAAYiF,GC7E5C,IAA6B/P,
SDiFtC2Q,aAAiBd,GACf/E,GACF6F,EAAMb,OAAOhF,EAAYiF,GAClBY,EAAMT,QAAQH,IACTY,EAITM,E
AAcN,GAzEM,SAAhBO,EAAiBC,EAAaC,OEbH7Q,EAAckP,EFc9C7M,EAAQ,OAET,IAAMyO,KAAOF,EACX
A,EAAIG,eAAeD,KAAQX,QAAQX,EAAOsB,KAAKH,EAAIW,MAAMR,EAAIS,QAAUT,EAAIU,SAAWV,
EAAIG,eAAeD,KAAQX,QAAQX,EAAOsB,KAAKH,EAAIW,MAAMR,EAAIS,QAAUT,EAAIU,SAAWV,
AUxR,EAAWoR,EAAIE,IAChEzO,EAAMvD,KAAKmS,GAAUH,EAAOhS,KAAKmS,GAAUH,EAAOhS,KAAKmS,GAAUH,EAAOhS

EAAQyM,kBAEU,SAACC,EAAMC,EAAUC,UAC/B5U,EAAgCyU,kBAClCC,EACAC,EACAC,IAEA5M,EAAQyM,kBAA4CC,EAAMC,EAAUC,IAGlD5U,EAAgCyU,uBAkBtDI,EAdEC,EAAiB,IAAI1K,GACzB1H,EACAnC,EACAwT,EAAuB/T,EAAgB8U,oBAAkC1O,GAKrEoE,EAAWsK,EAAetK,UAA6B,IAAjByJ,EAAM/U,OAQ5C6V,EAAa,SAACnG,EAAOoG,UA7I7B,SACEC,EACArG,EACAsG,EACAC,EACAC,EACAC

QACA,KACA,QACA,OACA,QACA,KACA,QACA,IACA,KACA,MACA,QACA,MAGA,SACA,WACA,OACA,UACA,gBACA,IACA,QACA,OACA,iBACA,SACA,OACA,OACA,UACA,UACA,WACA,iBACA,OACA,OACA,MACA,OACA,WACA,SCnIUT,SAAQ,SAAAiW,GAClBR,GAAOQ,GAAcR,GAAOQ,UELTC,yBAOPjV,EAAgB2H,QACrB3H,MAAQA,OACR2H,YAAcA,OACdG,SAAAWN,GAAcxH,GAI9BqF,EAAWS,WAAWhG,KAAK6HYAAc,8BAG3CuN,aAAA,SACEC,EACAlN,EACAC,EACAC,OAGMrH,EAAqHEADIE,GAAAQvI,KAAAKE,MAAOiI,EAAAkBC,EAAAYC,GACvCVC9I,KAAAK6H,YAAAcwN,EAAAG9BjN,EAAAWnI,YAAAYsB,EAAAIA,EAAAIP,MAAGjCsU,aAAAA,SAAAaD,EAAAkBjN,GAAC7BA,EAAAW1B,EAAAW1G,KAAAK6H,YAAAcwN,EAAAG3CE,aAAAA,SACEF,EAAAlN,EAAAC,EAAAC,GAAAE9I,EAAAW,GAAAG9P,EAAAWS,WAAAWhG,KAAAK6H,YAAAcwN,EAAAG,QAAGtDC,aAAAA,SAAAaD,EAAAkBjN,GAAC7BA,EAAAW1B,EAAAW1G,KAAAK6H,YAAAcwN,EAAAG,S

ydration.js","../src/utils/nonce.js","../src/sheet/dom.js","../src/sheet/Tag.js","../src/sheet/Sheet.js","../src/utils/generate AlphabeticName.js","../src/utils/hash.js","../src/utils/isStaticRules.js","../src/models/ComponentStyle.js","../src/utils/ stylis.js","../src/utils/stylisPluginInsertRule.js","../src/models/StyleSheetManager.js","../src/models/Keyframes.js","../ /src/utils/hyphenateStyleName.js","../src/utils/flatten.js","../src/utils/isStatelessFunction.js","../src/utils/addUnitIfNee ded.js","../src/constructors/css.js","../src/utils/checkDynamicCreation.js","../src/utils/determineTheme.js","../src/utils /escape.js","../src/utils/generateComponentId.js","../src/utils/isTag.js","../src/utils/mixinDeep.js","../src/models/The meProvider.js","../src/models/StyledComponent.js","../src/utils/generateDisplayName.js","../src/utils/joinStrings.js", "../src/utils/createWarnTooManyClasses.js","../src/utils/domElements.js","../src/constructors/styled.js","../src/constru ctors/constructWithOptions.js","../src/models/GlobalStyle.js","../src/constructors/createGlobalStyle.js","../src/constr uctors/keyframes.js","../src/models/ServerStyleSheet.js","../src/hoc/withTheme.js","../src/hooks/useTheme.js","../src /secretInternals.js","../src/base.js"],"sourcesContent":["// @flow\nimport type { Interpolation } from '../types';\n\nexport default (\n strings: Array<string>,\n interpolations: Array<Interpolation>\n): Array<Interpolation> => {\n const result = [strings[0]];\n\n for (let i = 0, len = interpolations.length; i < len; i += 1) {\n result.push(interpolations[i], strings[i + 1]);\n }\n\n return result;\n};\n","// @flow\nimport { typeOf } from 'react-is';\n\nexport default (x: any): boolean =>\n x !== null &&\n typeof x === 'object' &&\n (x.toString ? x.toString() : Object.prototype.toString.call(x)) === '[object Object]' &&\n !typeOf(x);\n","// @flow\nexport const EMPTY_ARRAY = Object.freeze([]);\nexport const EMPTY_OBJECT = Object.freeze({});\n","// @flow\nexport default function isFunction(test: any): boolean %checks {\n return typeof test === 'function';\n}\n","// @flow\nimport type { IStyledComponent } from '../types';\n\nexport default function getComponentName(\n target: $PropertyType<IStyledComponent, 'target'>\n): string {\n return (\n (process.env.NODE_ENV !== 'production' ? typeof target === 'string' && target : false) ||\n // $FlowFixMe\n target.displayName ||\n // $FlowFixMe\n target.name ||\n 'Component'\n);\n}\n","// @flow\nexport default function isStyledComponent(target: any): boolean %checks {\n return target && typeof target.styledComponentId === 'string';\n}\n","// @flow\n\ndeclare var SC_DISABLE_SPEEDY: ?boolean;\ndeclare var __VERSION__: string;\n\nexport const SC_ATTR: string =\n (typeof process !== 'undefined' &&\n typeof process.env !== 'undefined' &&\n (process.env.REACT_APP_SC_ATTR || process.env.SC_ATTR)) ||\n 'data-styled';\n\nexport const SC_ATTR_ACTIVE = 'active';\nexport const SC_ATTR_VERSION = 'data-styled-version';\nexport const SC_VERSION = __VERSION__;\nexport const SPLITTER = '/*!sc*/\\n';\n\nexport const IS_BROWSER = typeof window !== 'undefined' && 'HTMLElement' in window;\n\nexport const DISABLE_SPEEDY = Boolean(\n typeof SC_DISABLE_SPEEDY === 'boolean'\n ? SC_DISABLE_SPEEDY\n : typeof process !== 'undefined' &&\n typeof process.env !== 'undefined'\n ? typeof process.env.REACT_APP_SC_DISABLE_SPEEDY !== 'undefined' &&\n process.env.REACT_APP_SC_DISABLE_SPEEDY !== ''\n ? process.env.REACT_APP_SC_DISABLE_SPEEDY\n === 'false'\n ? false\n : process.env.REACT_APP_SC_DISABLE_SPEEDY\n : typeof process.env.SC_DISABLE_SPEEDY !== 'undefined' && process.env.SC_DISABLE_SPEEDY !== ''\n ? process.env.SC_DISABLE_SPEEDY === 'false'\n ? false\n : process.env.SC_DISABLE_SPEEDY\n : process.env.NODE_ENV !== 'production'\n : false\n);\n\n// Shared empty execution context when generating static styles\nexport const STATIC_EXECUTION_CONTEXT = {};\n","// @flow\nimport errorMap from './errors';\n\nconst ERRORS = process.env.NODE_ENV !== 'production' ? errorMap : {};\n\n/**\n * super basic version of sprintf\n */\nfunction format(...args) {\n let a = args[0];\n const b = [];\n\n for (let c = 1, len = args.length; c < len; c += 1) {\n b.push(args[c]);\n }\n\n b.forEach(d => {\n a = a.replace(/%[a-z]/, d);\n });\n\n return a;\n}\n\n/**\n * Create an error file out of errors.md for development and a simple web link to the full errors\n * in\n production mode.\n */\nexport default function throwStyledComponentsError(\n code: string | number,\n ...interpolations: Array<any>\n) {\n if (process.env.NODE_ENV === 'production') {\n throw new Error(\n `An error occurred. See https://git.io/JUIaE#${code} for more information.${\n interpolations.length > 0 ? ` Args:

${interpolations.join(', ')}` : "\n }`\n);\n } else {\n throw new Error(format(ERRORS[code], ...interpolations).trim());\n }\n}\n","export default {\"1\":\"Cannot create styled-component for component: %s.\\n\\n\",\"2\":\"Can't collect styles once you've consumed a `ServerStyleSheet`'s styles! `ServerStyleSheet` is a one off instance for each server-side render cycle.\\n\\n- Are you trying to reuse it across renders?\\n- Are you accidentally calling collectStyles twice?\\n\\n\",\"3\":\"Streaming SSR is only supported in a Node.js environment; Please do not try to call this method in the browser.\\n\\n\",\"4\":\"The `StyleSheetManager` expects a valid target or sheet prop!\\n\\n- Does this error occur on the client and is your target falsy?\\n- Does this error occur on the server and is the sheet falsy?\\n\\n\",\"5\":\"The clone method cannot be used on the client!\\n\\n- Are you running in a client-like environment on the server?\\n- Are you trying to run SSR on the client?\\n\\n\",\"6\":\"Trying to insert a new style tag, but the given Node is unmounted!\\n\\n- Are you using a custom target that isn't mounted?\\n- Does your document not have a valid head element?\\n- Have you accidentally removed a style tag manually?\\n\\n\",\"7\":\"ThemeProvider: Please return an object from your \\\"theme\\\" prop function, e.g.\\n\\n```js\\ntheme={() => ({})}\\n```\\n\\n\",\"8\":\"ThemeProvider: Please make your \\\"theme\\\" prop an object.\\n\\n\",\"9\":\"Missing document `<head>`\\n\\n\",\"10\":\"Cannot find a StyleSheet instance. Usually this happens if there are multiple copies of styled-components loaded at once. Check out this issue for how to troubleshoot and fix the common cases where this situation can happen: https://github.com/styled-components/styled-components/issues/1941#issuecomment-417862021\\n\\n\",\"11\":\"_This error was replaced with a dev-time warning, it will be deleted for v4 final._ [createGlobalStyle] received children which will not be rendered. Please use the component without passing children elements.\\n\\n\",\"12\":\"It seems you are interpolating a keyframe declaration (%s) into an untagged string. This was supported in styled-components v3, but is not longer supported in v4 as keyframes are now injected on-demand. Please wrap your string in the css\\`\\`\` helper which ensures the styles are injected correctly. See https://www.styled-components.com/docs/api#css\\n\\n\",\"13\":\"%s is not a styled component and cannot be referred to via component selector. See https://www.styled-components.com/docs/advanced#referring-to-other-components for more details.\\n\\n\",\"14\":\"ThemeProvider: \\\"theme\\\" prop is required.\\n\\n\",\"15\":\"A stylis plugin has been supplied that is not named. We need a name for each plugin to be able to prevent styling collisions between different stylis configurations within the same app. Before you pass your plugin to `<StyleSheetManager stylisPlugins={[]}>`, please make sure each plugin is uniquely-named, e.g.\\n\\n```js\\nObject.defineProperty(importedPlugin, 'name', { value: 'some-unique-name' });\\n```\\n\\n\",\"16\":\"Reached the limit of how many styled components may be created at group %s.\\nYou may only create up to 1,073,741,824 components. If you're creating components dynamically,\\nas for instance in your render method then you may be running into this limitation.\\n\\n\",\"17\":\"CSSStyleSheet could not be found on HTMLStyleElement.\\nHas styled-components' style tag been unmounted or altered by another script?\\n\\n\"};","// @flow\n/* eslint-disable no-use-before-define */\n\nimport type { GroupedTag, Tag } from './types';\nimport { SPLITTER } from '../constants';\nimport throwStyledError from '../utils/error';\n\n/** Create a GroupedTag with an underlying Tag implementation */\nexport const makeGroupedTag = (tag: Tag): GroupedTag => {\n return new DefaultGroupedTag(tag);\n};\n\nconst BASE_SIZE = 1 << 9;\n\nclass DefaultGroupedTag implements GroupedTag {\n groupSizes: Uint32Array;\n\n length: number;\n\n tag: Tag;\n\n constructor(tag: Tag) {\n this.groupSizes = new Uint32Array(BASE_SIZE);\n this.length = BASE_SIZE;\n this.tag = tag;\n }\n\n indexOfGroup(group: number): number {\n let index = 0;\n for (let i = 0; i < group; i++) {\n index += this.groupSizes[i];\n }\n\n return index;\n }\n\n insertRules(group: number, rules: string[]): void {\n if (group >= this.groupSizes.length) {\n const oldBuffer = this.groupSizes;\n const oldSize = oldBuffer.length;\n\n let newSize = oldSize;\n while (group >= newSize) {\n newSize <<= 1;\n if (newSize < 0) {\n throwStyledError(16, `${group}`);\n }\n }\n\n this.groupSizes = new Uint32Array(newSize);\n this.groupSizes.set(oldBuffer);\n this.length = newSize;\n\n for (let i = oldSize; i < newSize; i++) {\n this.groupSizes[i] = 0;\n }\n }\n\n let ruleIndex = this.indexOfGroup(group + 1);\n for (let i = 0, l = rules.length; i < l; i++) {\n if (this.tag.insertRule(ruleIndex, rules[i])) {\n this.groupSizes[group]++;\n ruleIndex++;\n }\n }\n }\n\n clearGroup(group: number): void {\n if (group < this.length) {\n const length = this.groupSizes[group];\n const startIndex =

this.indexOfGroup(group);\n const endIndex = startIndex + length;\n\n this.groupSizes[group] = 0;\n\n for (let i = startIndex; i < endIndex; i++) {\n this.tag.deleteRule(startIndex);\n }\n }\n }\n\n getGroup(group: number): string {\n let css = '';\n if (group >= this.length || this.groupSizes[group] === 0) {\n return css;\n }\n\n const length = this.groupSizes[group];\n const startIndex = this.indexOfGroup(group);\n const endIndex = startIndex + length;\n\n for (let i = startIndex; i < endIndex; i++) {\n css += `${this.tag.getRule(i)}${SPLITTER}`;\n }\n\n return css;\n }\n}\n","// @flow\n\nimport throwStyledError from '../utils/error';\n\nconst MAX_SMI = 1 << 31 - 1;\n\nlet groupIDRegister: Map<string, number> = new Map();\nlet reverseRegister: Map<number, string> = new Map();\nlet nextFreeGroup = 1;\n\nexport const resetGroupIds = () => {\n groupIDRegister = new Map();\n reverseRegister = new Map();\n nextFreeGroup = 1;\n};\n\nexport const getGroupForId = (id: string): number => {\n if (groupIDRegister.has(id)) {\n return (groupIDRegister.get(id): any);\n }\n\n while (reverseRegister.has(nextFreeGroup)) {\n nextFreeGroup++;\n }\n\n const group = nextFreeGroup++;\n\n if (\n process.env.NODE_ENV !== 'production' &&\n ((group | 0) < 0 || group > MAX_SMI)\n) {\n throwStyledError(16, `${group}`);\n }\n\n groupIDRegister.set(id, group);\n reverseRegister.set(group, id);\n return group;\n};\n\nexport const getIdForGroup = (group: number): void | string => {\n return reverseRegister.get(group);\n};\n\nexport const setGroupForId = (id: string, group: number) => {\n if (group >= nextFreeGroup) {\n nextFreeGroup = group + 1;\n }\n\n groupIDRegister.set(id, group);\n reverseRegister.set(group, id);\n};\n","// @flow\n\nimport { SPLITTER, SC_ATTR, SC_ATTR_ACTIVE, SC_ATTR_VERSION, SC_VERSION } from '../constants';\nimport { getIdForGroup, setGroupForId } from './GroupIDAllocator';\nimport type { Sheet } from './types';\n\nconst SELECTOR = `style[${SC_ATTR}][${SC_ATTR_VERSION}=\"${SC_VERSION}\"]`;\nconst MARKER_RE = new RegExp(`^${SC_ATTR}\\\\.g(\\\\d+)\\\\[id=\"([\\\\w\\\\d-]+)\"\\\\].*?\"([^\"]*)`);\n\nexport const outputSheet = (sheet: Sheet) => {\n const tag = sheet.getTag();\n\n const { length } = tag;\n\n let css = '';\n for (let group = 0; group < length; group++) {\n const id = getIdForGroup(group);\n if (id === undefined) continue;\n\n const names = sheet.names.get(id);\n const rules = tag.getGroup(group);\n if (!names || !rules || !names.size) continue;\n\n const selector = `${SC_ATTR}.g${group}[id=\"${id}\"]`;\n\n let content = '';\n if (names !== undefined) {\n names.forEach(name => {\n if (name.length > 0) {\n content += `${name},`;\n }\n });\n }\n\n // NOTE: It's easier to collect rules and have the marker\n // after the actual rules to simplify the rehydration\n css += `${rules}${selector}{content:\"${content}\"}${SPLITTER}`;\n }\n\n return css;\n};\n\nconst rehydrateNamesFromContent = (sheet: Sheet, id: string, content: string) => {\n const names = content.split(',');\n let name;\n\n for (let i = 0, l = names.length; i < l; i++) {\n // eslint-disable-next-line\n if ((name = names[i])) {\n sheet.registerName(id, name);\n }\n }\n};\n\nconst rehydrateSheetFromTag = (sheet: Sheet, style: HTMLStyleElement) => {\n const parts = (style.textContent || '').split(SPLITTER);\n const rules: string[] = [];\n\n for (let i = 0, l = parts.length; i < l; i++) {\n const part = parts[i].trim();\n if (!part) continue;\n\n const marker = part.match(MARKER_RE);\n\n if (marker) {\n const group = parseInt(marker[1], 10) | 0;\n const id = marker[2];\n\n if (group !== 0) {\n // Rehydrate componentId to group index mapping\n setGroupForId(id, group);\n // Rehydrate names and rules\n // looks like: data-styled.g11[id=\"idA\"]{content:\"nameA,\"}\n rehydrateNamesFromContent(sheet, id, marker[3]);\n sheet.getTag().insertRules(group, rules);\n }\n\n rules.length = 0;\n } else {\n rules.push(part);\n }\n }\n};\n\nexport const rehydrateSheet = (sheet: Sheet) => {\n const nodes = document.querySelectorAll(SELECTOR);\n\n for (let i = 0, l = nodes.length; i < l; i++) {\n const node = ((nodes[i]: any): HTMLStyleElement);\n if (node && node.getAttribute(SC_ATTR) !== SC_ATTR_ACTIVE) {\n rehydrateSheetFromTag(sheet, node);\n\n if (node.parentNode) {\n node.parentNode.removeChild(node);\n }\n }\n }\n};\n","// @flow\n/* eslint-disable camelcase, no-undef */\n\ndeclare var __webpack_nonce__: string;\n\nconst getNonce = () => {\n return typeof __webpack_nonce__ !== 'undefined' ? __webpack_nonce__ : null;\n};\n\nexport default getNonce;\n","// @flow\n\nimport { SC_ATTR, SC_ATTR_ACTIVE, SC_ATTR_VERSION, SC_VERSION } from '../constants';\nimport getNonce from '../utils/nonce';\nimport throwStyledError from '../utils/error';\n\nconst ELEMENT_TYPE = 1; /*

Node.ELEMENT_TYPE */\n\n/** Find last style element if any inside target */\nconst findLastStyleTag = (target: HTMLElement): void | HTMLStyleElement => {\n const { childNodes } = target;\n\n for (let i = childNodes.length; i >= 0; i--) {\n   const child = ((childNodes[i]: any): ?HTMLElement);\n   if (child && child.nodeType === ELEMENT_TYPE && child.hasAttribute(SC_ATTR)) {\n   return ((child: any): HTMLStyleElement);\n   }\n }\n\n return undefined;\n};\n\n/** Create a style element inside `target` or <head> after the last */\nexport const makeStyleTag = (target?: HTMLElement): HTMLStyleElement => {\n const head = ((document.head: any): HTMLElement);\n const parent = target || head;\n const style = document.createElement('style');\n const prevStyle = findLastStyleTag(parent);\n const nextSibling = prevStyle !== undefined ? prevStyle.nextSibling : null;\n\n style.setAttribute(SC_ATTR, SC_ATTR_ACTIVE);\n style.setAttribute(SC_ATTR_VERSION, SC_VERSION);\n\n const nonce = getNonce();\n\n if (nonce) style.setAttribute('nonce', nonce);\n\n parent.insertBefore(style, nextSibling);\n\n return style;\n};\n\n/** Get the CSSStyleSheet instance for a given style
  element */\nexport const getSheet = (tag: HTMLStyleElement): CSSStyleSheet => {\n if (tag.sheet) {\n   return ((tag.sheet: any): CSSStyleSheet);\n }\n\n // Avoid Firefox quirk where the style element might not have a sheet property\n const { styleSheets } = document;\n for (let i = 0, l = styleSheets.length; i < l; i++) {\n   const sheet = styleSheets[i];\n   if (sheet.ownerNode === tag) {\n   return ((sheet: any): CSSStyleSheet);\n   }\n }\n\n throwStyledError(17);\n return (undefined: any);\n};\n","// @flow\n/* eslint-disable no-use-before-define */\n\nimport { makeStyleTag, getSheet } from './dom';\nimport type { SheetOptions, Tag } from './types';\n\n/** Create a CSSStyleSheet-like tag depending on the environment */\nexport const makeTag = ({ isServer, useCSSOMInjection, target }: SheetOptions): Tag => {\n if (isServer) {\n   return new VirtualTag(target);\n } else if (useCSSOMInjection) {\n   return new CSSOMTag(target);\n } else {\n   return new TextTag(target);\n }\n};\n\nexport class CSSOMTag implements Tag {\n element: HTMLStyleElement;\n\n sheet: CSSStyleSheet;\n\n length: number;\n\n constructor(target?: HTMLElement) {\n   const element = (this.element = makeStyleTag(target));\n\n   // Avoid Edge bug where empty style elements don't create sheets\n   element.appendChild(document.createTextNode(''));\n\n   this.sheet = getSheet(element);\n   this.length = 0;\n }\n\n insertRule(index: number, rule: string): boolean {\n   try {\n   this.sheet.insertRule(rule, index);\n   this.length++;\n   return true;\n   } catch (_error) {\n   return false;\n   }\n }\n\n deleteRule(index: number): void {\n   this.sheet.deleteRule(index);\n   this.length--;\n }\n\n getRule(index: number): string {\n   const rule = this.sheet.cssRules[index];\n   // Avoid IE11 quirk where cssText is inaccessible on some invalid rules\n   if (rule !== undefined && typeof rule.cssText === 'string') {\n   return rule.cssText;\n   } else {\n   return '';\n   }\n }\n}\n\n/** A Tag that emulates the CSSStyleSheet API but uses text nodes */\nexport class TextTag implements Tag {\n element: HTMLStyleElement;\n\n nodes: NodeList<Node>;\n\n length: number;\n\n constructor(target?: HTMLElement) {\n   const element = (this.element = makeStyleTag(target));\n   this.nodes = element.childNodes;\n   this.length = 0;\n }\n\n insertRule(index: number, rule: string): boolean {\n   if (index <= this.length && index >= 0) {\n   const node = document.createTextNode(rule);\n   const refNode = this.nodes[index];\n   this.element.insertBefore(node, refNode || null);\n   this.length++;\n   return true;\n   } else {\n   return false;\n   }\n }\n\n deleteRule(index: number): void {\n   this.element.removeChild(this.nodes[index]);\n   this.length--;\n }\n\n getRule(index: number): string {\n   if (index < this.length) {\n   return this.nodes[index].textContent;\n   } else {\n   return '';\n   }\n }\n}\n\n/** A completely virtual (server-side) Tag that doesn't manipulate the DOM */\nexport class VirtualTag implements Tag {\n rules: string[];\n\n length: number;\n\n constructor(_target?: HTMLElement) {\n   this.rules = [];\n   this.length = 0;\n }\n\n insertRule(index: number, rule: string): boolean {\n   if (index <= this.length) {\n   this.rules.splice(index, 0, rule);\n   this.length++;\n   return true;\n   } else {\n   return false;\n   }\n }\n\n deleteRule(index: number): void {\n   this.rules.splice(index, 1);\n   this.length--;\n }\n\n getRule(index: number): string {\n   if (index < this.length) {\n   return this.rules[index];\n   } else {\n   return '';\n   }\n }\n}\n","// @flow\nimport { DISABLE_SPEEDY, IS_BROWSER } from '../constants';\nimport { EMPTY_OBJECT } from '../utils/empties';\nimport { makeGroupedTag } from './GroupedTag';\nimport { getGroupForId } from './GroupIDAllocator';\nimport { outputSheet, rehydrateSheet

} from './Rehydration';\nimport { makeTag } from './Tag';\nimport type { GroupedTag, Sheet, SheetOptions } from './types';\n\nlet SHOULD_REHYDRATE = IS_BROWSER;\n\ntype SheetConstructorArgs = {\n isServer?: boolean,\n useCSSOMInjection?: boolean,\n target?: HTMLElement,\n};\n\ntype GlobalStylesAllocationMap = { [key: string]: number };\ntype NamesAllocationMap = Map<string, Set<string>>;\n\nconst defaultOptions: SheetOptions = {\n isServer: !IS_BROWSER,\n useCSSOMInjection: !DISABLE_SPEEDY,\n};\n\n/** Contains the main stylesheet logic for stringification and caching */\nexport default class StyleSheet implements Sheet {\n gs: GlobalStylesAllocationMap;\n\n names: NamesAllocationMap;\n\n options: SheetOptions;\n\n server: boolean;\n\n tag: void | GroupedTag;\n\n /** Register a group ID to give it an index */\n static registerId(id: string): number {\n return getGroupForId(id);\n }\n\n constructor(\n options: SheetConstructorArgs = EMPTY_OBJECT,\n globalStyles?: GlobalStylesAllocationMap = {},\n names?: NamesAllocationMap\n) {\n this.options = {\n ...defaultOptions,\n ...options,\n };\n\n this.gs = globalStyles;\n this.names = new Map(names);\n this.server = !!options.isServer;\n\n // We rehydrate only once and use the sheet that is created first\n if (!this.server && IS_BROWSER && SHOULD_REHYDRATE) {\n SHOULD_REHYDRATE = false;\n rehydrateSheet(this);\n }\n }\n\n reconstructWithOptions(options: SheetConstructorArgs, withNames?: boolean = true) {\n return new StyleSheet(\n { ...this.options, ...options },\n this.gs,\n (withNames && this.names) || undefined\n);\n }\n\n allocateGSInstance(id: string) {\n return (this.gs[id] = (this.gs[id] || 0) + 1);\n }\n\n /** Lazily initialises a GroupedTag for when it's actually needed */\n getTag(): GroupedTag {\n return this.tag || (this.tag = makeGroupedTag(makeTag(this.options)));\n }\n\n /** Check whether a name is known for caching */\n hasNameForId(id: string, name: string): boolean {\n return this.names.has(id) && (this.names.get(id): any).has(name);\n }\n\n /** Mark a group's name as known for caching */\n registerName(id: string, name: string) {\n getGroupForId(id);\n\n if (!this.names.has(id)) {\n const groupNames = new Set();\n groupNames.add(name);\n this.names.set(id, groupNames);\n } else {\n (this.names.get(id): any).add(name);\n }\n }\n\n /** Insert new rules which also marks the name as known */\n insertRules(id: string, name: string, rules: string[]) {\n this.registerName(id, name);\n this.getTag().insertRules(getGroupForId(id), rules);\n }\n\n /** Clears all cached names for a given group ID */\n clearNames(id: string) {\n if (this.names.has(id)) {\n (this.names.get(id): any).clear();\n }\n }\n\n /** Clears all rules for a given group ID */\n clearRules(id: string) {\n this.getTag().clearGroup(getGroupForId(id));\n this.clearNames(id);\n }\n\n /** Clears the entire tag which deletes all rules but not its names */\n clearTag() {\n // NOTE: This does not clear the names, since it's only used during SSR\n // so that we can continuously output only new rules\n this.tag = undefined;\n }\n\n /** Outputs the current sheet as a CSS string with markers for SSR */\n toString(): string {\n return outputSheet(this);\n }\n}\n","// @flow\n/* eslint-disable no-bitwise */\n\nconst AD_REPLACER_R = /(a)(d)/gi;\n\n/* This is the \"capacity\" of our alphabet i.e. 2x26 for all letters plus their capitalised\n * counterparts */\nconst charsLength = 52;\n\n/* start at 75 for 'a' until 'z' (25) and then start at 65 for capitalised letters */\nconst getAlphabeticChar = (code: number): string =>\n String.fromCharCode(code + (code > 25 ? 39 : 97));\n\n/* input a number, usually a hash and convert it to base-52 */\nexport default function generateAlphabeticName(code: number): string {\n let name = '';\n\n let x;\n\n /* get a char and divide by alphabet-length */\n for (x = Math.abs(code); x > charsLength; x = (x / charsLength) | 0) {\n name = getAlphabeticChar(x % charsLength) + name;\n }\n\n return (getAlphabeticChar(x % charsLength) + name).replace(AD_REPLACER_R, '$1-$2');\n}\n","// @flow\n/* eslint-disable */\n\nexport const SEED = 5381;\n\n// When we have separate strings it's useful to run a progressive\n// version of djb2 where we pretend that we're still looping over\n// the same string\nexport const phash = (h: number, x: string): number => {\n let i = x.length;\n\n while (i) {\n h = (h * 33) ^ x.charCodeAt(--i);\n }\n\n return h;\n};\n\n// This is a djb2 hashing function\nexport const hash = (x: string): number => {\n return phash(SEED, x);\n};\n","// @flow\nimport isFunction from './isFunction';\nimport isStyledComponent from './isStyledComponent';\nimport type { RuleSet } from '../types';\n\nexport default function isStaticRules(rules: RuleSet): boolean {\n for (let i = 0; i < rules.length; i += 1) {\n const rule = rules[i];\n\n if (isFunction(rule) && !isStyledComponent(rule)) {\n // functions are allowed to be static if they're just being\n // used to get the

```
classname of a nested styled component\n      return false;\n    }\n  }\n\n  return true;\n}\n","// @flow\nimport { SC_VERSION } from '../constants';\nimport StyleSheet from '../sheet';\nimport type { RuleSet, Stringifier } from '../types';\nimport flatten from '../utils/flatten';\nimport generateName from '../utils/generateAlphabeticName';\nimport { hash, phash } from '../utils/hash';\nimport isStaticRules from '../utils/isStaticRules';\n\nconst SEED = hash(SC_VERSION);\n\n/**\n * ComponentStyle is all the CSS-specific stuff, not the React-specific stuff.\n */\nexport default class ComponentStyle {\n  baseHash: number;\n\n  baseStyle: ?ComponentStyle;\n\n  componentId: string;\n\n  isStatic: boolean;\n\n  rules: RuleSet;\n\n  staticRulesId: string;\n\n  constructor(rules:
 RuleSet, componentId: string, baseStyle?: ComponentStyle) {\n    this.rules = rules;\n    this.staticRulesId = '';\n    this.isStatic = process.env.NODE_ENV === 'production' &&\n      (baseStyle === undefined || baseStyle.isStatic) &&\n      isStaticRules(rules);\n    this.componentId = componentId;\n\n    // SC_VERSION gives us isolation between multiple runtimes on the page at once\n    // this is improved further with use of the babel plugin \"namespace\" feature\n    this.baseHash = phash(SEED, componentId);\n\n    this.baseStyle = baseStyle;\n\n    // NOTE: This registers the componentId, which ensures a consistent order\n    // for this component's styles compared to others\n    StyleSheet.registerId(componentId);\n  }\n\n  /*\n   * Flattens a rule set into valid CSS\n   * Hashes it, wraps the whole chunk in a .hash1234 {}\n   * Returns the hash to be injected on render()\n   * */\n  generateAndInjectStyles(executionContext: Object, styleSheet: StyleSheet, stylis: Stringifier)
 {\n    const { componentId } = this;\n\n    const names = [];\n\n    if (this.baseStyle) {\n      names.push(this.baseStyle.generateAndInjectStyles(executionContext, styleSheet, stylis));\n    }\n\n    // force dynamic classnames if user-supplied stylis plugins are in use\n    if (this.isStatic && !stylis.hash) {\n      if (this.staticRulesId && styleSheet.hasNameForId(componentId, this.staticRulesId)) {\n        names.push(this.staticRulesId);\n      } else {\n        const cssStatic = flatten(this.rules, executionContext, styleSheet, stylis).join('');\n        const name = generateName(phash(this.baseHash, cssStatic) >>> 0);\n\n        if (!styleSheet.hasNameForId(componentId, name)) {\n          const cssStaticFormatted = stylis(cssStatic, `.${name}`, undefined, componentId);\n\n          styleSheet.insertRules(componentId, name, cssStaticFormatted);\n        }\n\n        names.push(name);\n        this.staticRulesId = name;\n      }\n    } else {\n      const { length } = this.rules;\n
    let dynamicHash = phash(this.baseHash, stylis.hash);\n      let css = '';\n\n      for (let i = 0; i < length; i++) {\n
 const partRule = this.rules[i];\n\n        if (typeof partRule === 'string') {\n          css += partRule;\n\n          if (process.env.NODE_ENV !== 'production') dynamicHash = phash(dynamicHash, partRule + i);\n        } else if (partRule) {\n          const partChunk = flatten(partRule, executionContext, styleSheet, stylis);\n          const partString = Array.isArray(partChunk) ? partChunk.join('') : partChunk;\n          dynamicHash = phash(dynamicHash, partString + i);\n          css += partString;\n        }\n      }\n\n      if (css) {\n        const name = generateName(dynamicHash >>> 0);\n\n        if (!styleSheet.hasNameForId(componentId, name)) {\n          const cssFormatted = stylis(css, `.${name}`, undefined, componentId);\n          styleSheet.insertRules(componentId, name, cssFormatted);\n        }\n\n        names.push(name);\n
    }\n    }\n\n    return names.join(' ');\n  }\n}\n","import Stylis from '@emotion/stylis';\nimport { type Stringifier } from '../types';\nimport { EMPTY_ARRAY, EMPTY_OBJECT } from './empties';\nimport throwStyledError from './error';\nimport { phash, SEED } from './hash';\nimport insertRulePlugin from './stylisPluginInsertRule';\n\nconst COMMENT_REGEX = /^\\s*\\/\\/.*$/gm;\nconst COMPLEX_SELECTOR_PREFIX = [':', '[', '.', '#'];\n\ntype StylisInstanceConstructorArgs = {\n  options?: Object,\n  plugins?: Array<Function>,\n};\n\nexport default function createStylisInstance({\n  options = EMPTY_OBJECT,\n  plugins = EMPTY_ARRAY,\n}: StylisInstanceConstructorArgs = EMPTY_OBJECT) {\n  const stylis = new Stylis(options);\n\n  // Wrap `insertRulePlugin to build a list of rules,\n  // and then make our own plugin to return the rules. This\n  // makes it easier to hook into the existing SSR architecture\n\n  let parsingRules = [];\n\n  // eslint-disable-next-line consistent-return\n  const returnRulesPlugin
 = context => {\n    if (context === -2) {\n      const parsedRules = parsingRules;\n      parsingRules = [];\n      return parsedRules;\n    }\n  };\n\n  const parseRulesPlugin = insertRulePlugin(rule => {\n    parsingRules.push(rule);\n  });\n\n  let _componentId: string;\n  let _selector: string;\n  let _selectorRegexp: RegExp;\n  let
```

```
_consecutiveSelfRefRegExp: RegExp;\n\n  const selfReferenceReplacer = (match, offset, string) => {\n    if (\n      // do not replace the first occurrence if it is complex (has a modifier)\n      (offset === 0 ? COMPLEX_SELECTOR_PREFIX.indexOf(string[_selector.length]) === -1 : true) &&\n      // no consecutive self refs (.b.b); that is a precedence boost and treated differently\n      !string.match(_consecutiveSelfRefRegExp)\n    ) {\n      return `.${_componentId}`;\n    }\n\n    return match;\n  };\n\n  /**\n   * When writing a style like\n   *\n   * & + & {\n   *   color: red;\n   * }\n   *\n   * The second ampersand should be a reference to the static component class. stylis\n   * has no knowledge of static class so we have to intelligently replace the base selector.\n   *\n   * https://github.com/thysultan/stylis.js/tree/v3.5.4#plugins <- more info about the context phase values\n   * \"2\" means this plugin is taking effect at the very end after all other processing is complete\n   */\n  const selfReferenceReplacementPlugin = (context, _, selectors) => {\n    if (context === 2 && selectors.length && selectors[0].lastIndexOf(_selector) > 0) {\n      // eslint-disable-next-line no-param-reassign\n      selectors[0] = selectors[0].replace(_selectorRegexp, selfReferenceReplacer);\n    }\n  };\n\n  stylis.use([...plugins, selfReferenceReplacementPlugin, parseRulesPlugin, returnRulesPlugin]);\n\n  function stringifyRules(css, selector, prefix, componentId = '&'): Stringifier {\n    const flatCSS = css.replace(COMMENT_REGEX, '');\n    const cssStr = selector && prefix ? `${prefix} ${selector} { ${flatCSS} }` : flatCSS;\n\n    // stylis has no concept of state to be passed to plugins\n    // but since JS is single-threaded, we can rely on that to ensure\n    // these properties stay in sync with the current stylis run\n    _componentId = componentId;\n    _selector = selector;\n    _selectorRegexp = new RegExp(`\\\\${_selector}\\\\b`, 'g');\n    _consecutiveSelfRefRegExp = new RegExp(`(\\\\${_selector}\\\\b){2,}`);\n\n    return stylis(prefix || !selector ? '' : selector, cssStr);\n  }\n\n  stringifyRules.hash = plugins.length\n    ? plugins\n        .reduce((acc, plugin) => {\n          if (!plugin.name) {\n            throwStyledError(15);\n          }\n\n          return phash(acc, plugin.name);\n        }, SEED)\n        .toString()\n    : '';\n\n  return stringifyRules;\n}\n","/**\n * MIT License\n *\n * Copyright (c) 2016 Sultan Tarimo\n *\n * Permission is hereby granted, free of charge, to any person obtaining a copy of\n * this software and associated documentation files (the \"Software\"),\n * to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or\n * sell copies of the Software and to permit persons to whom the Software is furnished to do so, subject to the following conditions:\n *\n * The above copyright notice and this permission notice shall be included in all\n * copies or substantial portions of the Software.\n *\n * THE SOFTWARE IS PROVIDED \"AS IS\", WITHOUT WARRANTY OF ANY KIND, EXPRESS\n * OR IMPLIED INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,\n * FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE\n * AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,\n * WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR\n * IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.\n */\n/* eslint-disable */\n\nexport default function(insertRule) {\n  const delimiter = '/*|*/';\n  const needle = `${delimiter}}`;\n\n  function toSheet(block) {\n    if (block) {\n      try {\n        insertRule(`${block}}`);\n      } catch (e) {}\n    }\n  }\n\n  return function ruleSheet(\n    context,\n    content,\n    selectors,\n    parents,\n    line,\n    column,\n    length,\n    ns,\n    depth,\n    at\n  ) {\n    switch (context) {\n      // property\n      case 1:\n        // @import\n        if (depth === 0 && content.charCodeAt(0) === 64) return insertRule(`${content};`), '';\n        break;\n      // selector\n      case 2:\n        if (ns === 0) return content + delimiter;\n        break;\n      // at-rule\n      case 3:\n        switch (ns) {\n          // @font-face, @page\n          case 102:\n          case 112:\n            return insertRule(selectors[0] + content), '';\n          default:\n            return content + (at === 0 ? delimiter : '');\n        }\n      case -2:\n        content.split(needle).forEach(toSheet);\n    }\n  };\n}\n","// @flow\nimport React, { type Context, type Node, useContext, useEffect, useMemo, useState } from 'react';\nimport shallowequal from 'shallowequal';\nimport StyleSheet from '../sheet';\nimport type { Stringifier } from '../types';\nimport createStylisInstance from '../utils/stylis';\n\ntype Props = {\n  children?: Node,\n  disableCSSOMInjection?: boolean,\n  disableVendorPrefixes?: boolean,\n  sheet?: StyleSheet,\n  stylisPlugins?: Array<Function>,\n  target?: HTMLElement,\n};\n\nexport const StyleSheetContext: Context<StyleSheet | void> =
```

React.createContext();\nexport const StyleSheetConsumer = StyleSheetContext.Consumer;\nexport const StylisContext: Context<Stringifier | void> = React.createContext();\nexport const StylisConsumer = StylisContext.Consumer;\n\nexport const masterSheet: StyleSheet = new StyleSheet();\nexport const masterStylis: Stringifier = createStylisInstance();\n\nexport function useStyleSheet(): StyleSheet {\n return useContext(StyleSheetContext) || masterSheet;\n}\n\nexport
 function useStylis(): Stringifier {\n return useContext(StylisContext) || masterStylis;\n}\n\nexport default function StyleSheetManager(props: Props) {\n const [plugins, setPlugins] = useState(props.stylisPlugins);\n const contextStyleSheet = useStyleSheet();\n\n const styleSheet = useMemo(() => {\n   let sheet = contextStyleSheet;\n\n
  if (props.sheet) {\n   // eslint-disable-next-line prefer-destructuring\n   sheet = props.sheet;\n   } else if (props.target) {\n   sheet = sheet.reconstructWithOptions({ target: props.target }, false);\n   }\n\n   if (props.disableCSSOMInjection) {\n   sheet = sheet.reconstructWithOptions({ useCSSOMInjection: false });\n   }\n\n   return sheet;\n }, [props.disableCSSOMInjection, props.sheet, props.target]);\n\n const stylis = useMemo(\n
  () =>\n   createStylisInstance({\n   options: { prefix: !props.disableVendorPrefixes },\n   plugins,\n   }),\n
 [props.disableVendorPrefixes, plugins]\n
  );\n\n useEffect(() => {\n   if (!shallowequal(plugins, props.stylisPlugins)) setPlugins(props.stylisPlugins);\n }, [props.stylisPlugins]);\n\n return (\n   <StyleSheetContext.Provider value={styleSheet}>\n
<StylisContext.Provider value={stylis}>\n   {process.env.NODE_ENV !== 'production'\n   ? React.Children.only(props.children)\n   : props.children}\n   </StylisContext.Provider>\n
</StyleSheetContext.Provider>\n);\n}\n","// @flow\nimport StyleSheet from '../sheet';\nimport { type Stringifier } from '../types';\nimport throwStyledError from '../utils/error';\nimport { masterStylis } from
'./StyleSheetManager';\n\nexport default class Keyframes {\n id: string;\n\n name: string;\n\n rules: string;\n\n
constructor(name: string, rules: string) {\n   this.name = name;\n   this.id = `sc-keyframes-${name}`;\n   this.rules = rules;\n }\n\n inject = (styleSheet: StyleSheet, stylisInstance: Stringifier = masterStylis) => {\n   const resolvedName
 = this.name + stylisInstance.hash;\n\n   if (!styleSheet.hasNameForId(this.id, resolvedName)) {\n
styleSheet.insertRules(\n   this.id,\n   resolvedName,\n   stylisInstance(this.rules, resolvedName, '@keyframes')\n   );\n   }\n };\n\n toString = () => {\n   return throwStyledError(12, String(this.name));\n };\n\n
getName(stylisInstance: Stringifier = masterStylis) {\n   return this.name + stylisInstance.hash;\n }\n}\n","// @flow\n\n/**\n * inlined version of\n *
https://github.com/facebook/fbjs/blob/master/packages/fbjs/src/core/hyphenateStyleName.js\n */\n\nconst uppercaseCheck = /([A-Z])/;\nconst uppercasePattern = /([A-Z])/g;\nconst msPattern = /^ms-/;\nconst prefixAndLowerCase = (char: string): string => `-${char.toLowerCase()}`;\n\n/**\n * Hyphenates a camelcased CSS property name, for example:\n *\n *   > hyphenateStyleName('backgroundColor')\n *   < \"background-color\"\n *   > hyphenateStyleName('MozTransition')\n *   < \"-moz-transition\"\n *   >
 hyphenateStyleName('msTransition')\n *   < \"-ms-transition\"\n *\n * As Modernizr suggests (http://modernizr.com/docs/#prefixed), an `ms` prefix\n * is converted to `-ms-`.\n *\n * @param {string} string\n * @return {string}\n */\nexport default function hyphenateStyleName(string: string): string {\n return uppercaseCheck.test(string)\n ? string\n   .replace(uppercasePattern, prefixAndLowerCase)\n   .replace(msPattern, '-ms-')\n : string;\n}\n","// @flow\nimport { isElement } from 'react-is';\nimport getComponentName from
'./getComponentName';\nimport isFunction from './isFunction';\nimport isStatelessFunction from
'./isStatelessFunction';\nimport isPlainObject from './isPlainObject';\nimport isStyledComponent from
'./isStyledComponent';\nimport Keyframes from '../models/Keyframes';\nimport hyphenate from
'./hyphenateStyleName';\nimport addUnitIfNeeded from './addUnitIfNeeded';\nimport { type Stringifier } from
'../types';\n\n/**\n * It's falsish not falsy because 0 is allowed.\n
 */\nconst isFalsish = chunk => chunk === undefined || chunk === null || chunk === false || chunk === '';\n\nexport const objToCssArray = (obj: Object, prevKey?: string): Array<string | Function> => {\n const rules = [];\n\n for (const key in obj) {\n   if (!obj.hasOwnProperty(key) || isFalsish(obj[key])) continue;\n\n   if ((Array.isArray(obj[key]) && obj[key].isCss) || isFunction(obj[key])) {\n   rules.push(`${hyphenate(key)}:`,

obj[key], ';');\n } else if (isPlainObject(obj[key])) {\n rules.push(...objToCssArray(obj[key], key));\n } else {\n rules.push(`${hyphenate(key)}: ${addUnitIfNeeded(key, obj[key])};`);\n }\n }\n\n return prevKey ? [`${prevKey} {`, ...rules, '}'] : rules;\n};\n\nexport default function flatten(\n chunk: any,\n executionContext: ?Object,\n styleSheet: ?Object,\n stylisInstance: ?Stringifier\n): any {\n if (Array.isArray(chunk)) {\n const ruleSet = [];\n\n for (let i = 0, len = chunk.length, result; i < len; i += 1) {\n result = flatten(chunk[i], executionContext, styleSheet, stylisInstance);\n\n if (result === '') continue;\n else if (Array.isArray(result)) ruleSet.push(...result);\n else ruleSet.push(result);\n }\n\n return ruleSet;\n }\n\n if (isFalsish(chunk)) {\n return '';\n }\n\n /* Handle other components */\n if (isStyledComponent(chunk)) {\n return `.${chunk.styledComponentId}`;\n }\n\n /* Either execute or defer the function */\n if (isFunction(chunk)) {\n if (isStatelessFunction(chunk) && executionContext) {\n const result = chunk(executionContext);\n\n if (process.env.NODE_ENV !== 'production' && isElement(result)) {\n // eslint-disable-next-line no-console\n console.warn(\n `${getComponentName(\n chunk\n )} is not a styled component and cannot be referred to via component selector. See https://www.styled-components.com/docs/advanced#referring-to-other-components for more details.`\n);\n\n }\n\n return flatten(result, executionContext, styleSheet, stylisInstance);\n } else return chunk;\n }\n\n if (chunk instanceof Keyframes) {\n if (styleSheet) {\n chunk.inject(styleSheet, stylisInstance);\n return chunk.getName(stylisInstance);\n } else return chunk;\n }\n\n /* Handle objects */\n return isPlainObject(chunk) ? objToCssArray(chunk) : chunk.toString();\n}\n","// @flow\nexport default function isStatelessFunction(test: any): boolean {\n return (\n typeof test === 'function'\n && !(\n test.prototype\n && test.prototype.isReactComponent\n)\n);\n}\n","// @flow\nimport unitless from '@emotion/unitless';\n\n// Taken from https://github.com/facebook/react/blob/b87aabdfe1b7461e7331abb3601d9e6bb27544bc/packages/react-dom/src/shared/dangerousStyleValue.js\nexport default function addUnitIfNeeded(name: string, value: any): any {\n // https://github.com/amilajack/eslint-plugin-flowtype-errors/issues/133\n // $FlowFixMe\n if (value == null || typeof value === 'boolean' || value === '') {\n return '';\n }\n\n if (typeof value === 'number' && value !== 0 && !(name in unitless) && !name.startsWith('--')) {\n return `${value}px`; // Presumes implicit 'px' suffix for unitless numbers except for CSS variables\n }\n\n return String(value).trim();\n}\n","// @flow\nimport interleave from '../utils/interleave';\nimport isPlainObject from '../utils/isPlainObject';\nimport { EMPTY_ARRAY } from '../utils/empties';\nimport isFunction from '../utils/isFunction';\nimport flatten from '../utils/flatten';\nimport type { Interpolation, RuleSet, Styles } from '../types';\n\n/**\n * Used when flattening object styles to determine if we should\n * expand an array of styles.\n */\nconst addTag = arg => {\n if (Array.isArray(arg)) {\n // eslint-disable-next-line no-param-reassign\n arg.isCss = true;\n }\n return arg;\n};\n\nexport default function css(styles: Styles, ...interpolations: Array<Interpolation>): RuleSet\n {\n if (isFunction(styles) || isPlainObject(styles)) {\n // $FlowFixMe\n return addTag(flatten(interleave(EMPTY_ARRAY, [styles, ...interpolations])));\n }\n\n if (interpolations.length === 0 && styles.length === 1 && typeof styles[0] === 'string') {\n // $FlowFixMe\n return styles;\n }\n\n // $FlowFixMe\n return addTag(flatten(interleave(styles, interpolations)));\n}\n","// @flow\n\nimport { useRef } from 'react';\n\nconst invalidHookCallRe = /invalid hook call/i;\nconst seen = new Set();\n\nexport const checkDynamicCreation = (displayName: string, componentId?: string) => {\n if (process.env.NODE_ENV !== 'production') {\n const parsedIdString = componentId ? ` with the id of \"${componentId}\"` : '';\n const message =\n `The component ${displayName}${parsedIdString} has been created dynamically.\\n` +\n \"You may see this warning because you've called styled inside another component.\\n\" +\n 'To resolve this only create new StyledComponents\n outside of any render method and function component.';\n\n // If a hook is called outside of a component:\n // React 17 and earlier throw an error\n // React 18 and above use console.error\n\n const originalConsoleError = console.error // eslint-disable-line no-console\n try {\n let didNotCallInvalidHook = true\n /* $FlowIgnore[cannot-write] */\n console.error = (consoleErrorMessage, ...consoleErrorArgs) => { // eslint-disable-line no-console\n // The error here is expected, since we're expecting anything that uses `checkDynamicCreation` to\n // be called outside of a React component.\n if

(invalidHookCallRe.test(consoleErrorMessage)) {\n didNotCallInvalidHook = false\n // This shouldn't happen, but resets `warningSeen` if we had this error happen intermittently\n seen.delete(message);\n } else {\n originalConsoleError(consoleErrorMessage, ...consoleErrorArgs);\n }\n }\n // We purposefully call `useRef` outside of a component and expect it to throw\n // If it doesn't, then we're inside another component.\n // eslint-disable-next-line react-hooks/rules-of-hooks\n useRef();\n\n if (didNotCallInvalidHook && !seen.has(message)) {\n // eslint-disable-next-line no-console\n console.warn(message);\n seen.add(message);\n }\n } catch (error) {\n // The error here is expected, since we're expecting anything that uses `checkDynamicCreation` to\n // be called outside of a React component.\n if (invalidHookCallRe.test(error.message)) {\n // This shouldn't happen, but resets `warningSeen` if we had this error happen intermittently\n seen.delete(message);\n }\n } finally {\n /* $FlowIgnore[cannot-write] */\n console.error = originalConsoleError; // eslint-disable-line no-console\n }\n}\n;\n","// @flow\nimport { EMPTY_OBJECT } from './empties';\n\ntype Props = {\n theme?: any,\n};\n\nexport default (props: Props, providedTheme: any, defaultProps: any = EMPTY_OBJECT) => {\n return (props.theme !== defaultProps.theme && props.theme) || providedTheme || defaultProps.theme;\n};\n","// @flow\n\n// Source: https://www.w3.org/TR/cssom-1/#serialize-an-identifier\n// Control characters and non-letter first symbols are not supported\nconst escapeRegex = /[!\"#$%&'()*+,./:;<=>?@[\\\\\\]^`{|}~-]+/g;\n\nconst dashesAtEnds = /(^-|-$)/g;\n\n/**\n * TODO: Explore using CSS.escape when it becomes more available\n * in evergreen browsers.\n */\nexport default function escape(str: string): string {\n return (\n str\n // Replace all possible CSS selectors\n .replace(escapeRegex, '-')\n\n // Remove extraneous hyphens at the start and end\n .replace(dashesAtEnds, '')\n);\n}\n","// @flow\n/* eslint-disable */\nimport generateAlphabeticName from './generateAlphabeticName';\nimport { hash } from './hash';\n\nexport default (str: string): string => {\n return generateAlphabeticName(hash(str) >>> 0);\n};\n","// @flow\nimport type { IStyledComponent } from '../types';\n\nexport default function isTag(target: $PropertyType<IStyledComponent, 'target'>): boolean %checks {\n return (\n typeof target === 'string' &&\n (process.env.NODE_ENV !== 'production'\n ? target.charAt(0) === target.charAt(0).toLowerCase()\n : true)\n);\n}\n","/* eslint-disable */\n/**\n mixin-deep; https://github.com/jonschlinkert/mixin-deep\n Inlined such that it will be consistently transpiled to an IE-compatible syntax.\n\n The MIT License (MIT)\n\n Copyright (c) 2014-present, Jon Schlinkert.\n\n Permission is hereby granted, free of charge, to any person obtaining a copy\n of this software and associated documentation files (the \"Software\"), to deal\n in the Software without restriction, including without limitation the rights\n to use, copy, modify, merge, publish, distribute, sublicense, and/or sell\n copies of the Software, and to permit persons to whom the Software is\n furnished to do so, subject to the following conditions:\n\n The above copyright notice and this permission notice shall be included in\n all copies or substantial portions of the Software.\n\n THE SOFTWARE IS PROVIDED \"AS IS\", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR\n IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,\n FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE\n AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER\n LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,\n OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN\n THE SOFTWARE.\n*/\n\nconst isObject = val => {\n return (\n typeof val === 'function' || (typeof val === 'object' && val !== null && !Array.isArray(val))\n);\n};\n\nconst isValidKey = key => {\n return key !== '__proto__' && key !== 'constructor' && key !== 'prototype';\n};\n\nfunction mixin(target, val, key) {\n const obj = target[key];\n if (isObject(val) && isObject(obj)) {\n mixinDeep(obj, val);\n } else {\n target[key] = val;\n }\n}\n\nexport default function mixinDeep(target, ...rest) {\n for (const obj of rest) {\n if (isObject(obj)) {\n for (const key in obj) {\n if (isValidKey(key)) {\n mixin(target, obj[key], key);\n }\n }\n }\n }\n\n return target;\n}\n","// @flow\nimport React, { useContext, useMemo, type Element, type Context } from 'react';\nimport throwStyledError from '../utils/error';\nimport isFunction from '../utils/isFunction';\n\nexport type Theme = { [key: string]: mixed };\n\ntype ThemeArgument = Theme | ((outerTheme?: Theme) => Theme);\n\ntype Props = {\n children?: Element<any>,\n theme:

ThemeArgument,\n};\n\nexport const ThemeContext: Context<Theme | void> = React.createContext();\n\nexport const ThemeConsumer = ThemeContext.Consumer;\n\nfunction mergeTheme(theme: ThemeArgument, outerTheme?:
Theme): Theme {\n if (!theme) {\n   return throwStyledError(14);\n }\n\n if (isFunction(theme)) {\n   const mergedTheme = theme(outerTheme);\n\n   if (\n   process.env.NODE_ENV !== 'production' &&\n   (mergedTheme === null || Array.isArray(mergedTheme) || typeof mergedTheme !== 'object')\n   ) {\n   return throwStyledError(7);\n   }\n\n   return mergedTheme;\n }\n\n if (Array.isArray(theme) || typeof theme !== 'object') {\n   return throwStyledError(8);\n }\n\n return outerTheme ? { ...outerTheme, ...theme } : theme;\n}\n\n/**\n * Provide a theme to an entire react component tree via context\n */\nexport default function ThemeProvider(props: Props) {\n const outerTheme = useContext(ThemeContext);\n const themeContext = useMemo(() => mergeTheme(props.theme, outerTheme), [\n   props.theme,\n   outerTheme,\n]);\n\n if (!props.children) {\n   return null;\n }\n\n return <ThemeContext.Provider value={themeContext}>{props.children}</ThemeContext.Provider>;\n}\n\n","//
@flow\nimport validAttr from '@emotion/is-prop-valid';\nimport hoist from 'hoist-non-react-statics';\nimport React, { createElement, type Ref, useContext } from 'react';\nimport { SC_VERSION } from '../constants';\nimport type {\n Attrs,\n IStyledComponent,\n IStyledStatics,\n RuleSet,\n ShouldForwardProp,\n Target,\n} from '../types';\nimport { checkDynamicCreation } from '../utils/checkDynamicCreation';\nimport createWarnTooManyClasses from '../utils/createWarnTooManyClasses';\nimport determineTheme from '../utils/determineTheme';\nimport { EMPTY_ARRAY, EMPTY_OBJECT } from '../utils/empties';\nimport escape from '../utils/escape';\nimport generateComponentId from '../utils/generateComponentId';\nimport generateDisplayName from '../utils/generateDisplayName';\nimport getComponentName from '../utils/getComponentName';\nimport isFunction from '../utils/isFunction';\nimport isStyledComponent from '../utils/isStyledComponent';\nimport isTag from '../utils/isTag';\nimport
joinStrings from '../utils/joinStrings';\nimport merge from '../utils/mixinDeep';\nimport ComponentStyle from './ComponentStyle';\nimport { useStyleSheet, useStylis } from './StyleSheetManager';\nimport { ThemeContext } from './ThemeProvider';\n\nconst identifiers = {};\n\n/* We depend on components having unique IDs */\nfunction generateId(displayName?: string, parentComponentId?: string) {\n const name = typeof displayName !== 'string' ? 'sc' : escape(displayName);\n // Ensure that no displayName can lead to duplicate componentIds\n identifiers[name] = (identifiers[name] || 0) + 1;\n\n const componentId = `${name}-${generateComponentId(\n    // SC_VERSION gives us isolation between multiple runtimes on the page at once\n    // this is improved further with use of the babel plugin \"namespace\" feature\n    SC_VERSION + name + identifiers[name]\n  )}`;\n\n return parentComponentId ? `${parentComponentId}-${componentId}` : componentId;\n}\n\nfunction useResolvedAttrs<Config>(theme:
any = EMPTY_OBJECT, props: Config, attrs: Attrs) {\n // NOTE: can't memoize this\n // returns [context, resolvedAttrs]\n // where resolvedAttrs is only the things injected by the attrs themselves\n const context = {
...props, theme };\n const resolvedAttrs = {};\n\n attrs.forEach(attrDef => {\n   let resolvedAttrDef = attrDef;\n   let key;\n\n   if (isFunction(resolvedAttrDef)) {\n   resolvedAttrDef = resolvedAttrDef(context);\n   }\n\n   /* eslint-disable guard-for-in */\n   for (key in resolvedAttrDef) {\n   context[key] = resolvedAttrs[key] =\n   key === 'className'\n   ? joinStrings(resolvedAttrs[key], resolvedAttrDef[key])\n   : resolvedAttrDef[key];\n   }\n   /* eslint-enable guard-for-in */\n });\n\n return [context, resolvedAttrs];\n}\n\nfunction useInjectedStyle<T>(\n componentStyle: ComponentStyle,\n isStatic: boolean,\n resolvedAttrs: T,\n warnTooManyClasses?: $Call<typeof createWarnTooManyClasses, string, string>\n) {\n const
styleSheet = useStyleSheet();\n const stylis = useStylis();\n\n const className = isStatic\n   ? componentStyle.generateAndInjectStyles(EMPTY_OBJECT, styleSheet, stylis)\n   : componentStyle.generateAndInjectStyles(resolvedAttrs, styleSheet, stylis);\n\n if (process.env.NODE_ENV !== 'production' && !isStatic && warnTooManyClasses) {\n   warnTooManyClasses(className);\n }\n\n return className;\n}\n\nfunction useStyledComponentImpl(\n forwardedComponent: IStyledComponent,\n props: Object,\n forwardedRef: Ref<any>,\n isStatic: boolean\n) {\n const {\n   attrs: componentAttrs,\n

```
componentStyle,\n  defaultProps,\n  foldedComponentIds,\n  shouldForwardProp,\n  styledComponentId,\n  target,\n } = forwardedComponent;\n\n  // NOTE: the non-hooks version only subscribes to this when !componentStyle.isStatic,\n  // but that'd be against the rules-of-hooks. We could be naughty and do it anyway as it\n  // should be an immutable value, but behave for now.\n  const theme
  = determineTheme(props, useContext(ThemeContext), defaultProps);\n\n  const [context, attrs] = useResolvedAttrs(theme || EMPTY_OBJECT, props, componentAttrs);\n\n  const generatedClassName = useInjectedStyle(\n  componentStyle,\n  isStatic,\n  context,\n  process.env.NODE_ENV !== 'production' ? forwardedComponent.warnTooManyClasses : undefined\n  );\n\n  const refToForward = forwardedRef;\n\n  const elementToBeCreated: Target = attrs.$as || props.$as || attrs.as || props.as || target;\n\n  const isTargetTag = isTag(elementToBeCreated);\n  const computedProps = attrs !== props ? { ...props, ...attrs } : props;\n  const propsForElement = {};\n\n  // eslint-disable-next-line guard-for-in\n  for (const key in computedProps) {\n  if (key[0] === '$' || key === 'as') continue;\n  else if (key === 'forwardedAs') {\n  propsForElement.as = computedProps[key];\n  } else if (\n  shouldForwardProp\n  ? shouldForwardProp(key, validAttr, elementToBeCreated)\n  :
  isTargetTag\n  ? validAttr(key)\n  : true\n  ) {\n  // Don't pass through non HTML tags through to HTML elements\n  propsForElement[key] = computedProps[key];\n  }\n  }\n\n  if (props.style && attrs.style !== props.style) {\n  propsForElement.style = { ...props.style, ...attrs.style };\n  }\n\n  propsForElement.className = Array.prototype\n  .concat(\n  foldedComponentIds,\n  styledComponentId,\n  generatedClassName !== styledComponentId ? generatedClassName : null,\n  props.className,\n  attrs.className\n  )\n  .filter(Boolean)\n  .join(' ');\n\n  propsForElement.ref = refToForward;\n\n  return createElement(elementToBeCreated, propsForElement);\n}\n\nexport default function createStyledComponent(\n target: $PropertyType<IStyledComponent, 'target'>,\n  options: {\n  attrs?: Attrs,\n  componentId: string,\n  displayName?: string,\n  parentComponentId?: string,\n  shouldForwardProp?: ShouldForwardProp,\n  },\n  rules: RuleSet\n)
  {\n  const isTargetStyledComp = isStyledComponent(target);\n  const isCompositeComponent = !isTag(target);\n\n  const {\n  attrs = EMPTY_ARRAY,\n  componentId = generateId(options.displayName, options.parentComponentId),\n  displayName = generateDisplayName(target),\n  } = options;\n\n  const styledComponentId =\n  options.displayName && options.componentId\n  ? `${escape(options.displayName)}-${options.componentId}`\n  : options.componentId || componentId;\n\n  // fold the underlying StyledComponent attrs up (implicit extend)\n  const finalAttrs =\n  isTargetStyledComp && ((target: any): IStyledComponent).attrs\n  ? Array.prototype.concat(((target: any): IStyledComponent).attrs, attrs).filter(Boolean)\n  : attrs;\n\n  // eslint-disable-next-line prefer-destructuring\n  let shouldForwardProp = options.shouldForwardProp;\n\n  if (isTargetStyledComp && target.shouldForwardProp) {\n  if (options.shouldForwardProp) {\n  // compose nested shouldForwardProp
  calls\n  shouldForwardProp = (prop, filterFn, elementToBeCreated) =>\n  ((((target: any): IStyledComponent).shouldForwardProp: any): ShouldForwardProp)(\n  prop,\n  filterFn,\n  elementToBeCreated\n  ) &&\n  ((options.shouldForwardProp: any): ShouldForwardProp)(prop, filterFn, elementToBeCreated);\n  } else {\n  // eslint-disable-next-line prefer-destructuring\n  shouldForwardProp = ((target: any): IStyledComponent).shouldForwardProp;\n  }\n  }\n\n  const componentStyle = new ComponentStyle(\n  rules,\n  styledComponentId,\n  isTargetStyledComp ? ((target: Object).componentStyle: ComponentStyle) : undefined\n  );\n\n  // statically styled-components don't need to build an execution context object,\n  // and shouldn't be increasing the number of class names\n  const isStatic = componentStyle.isStatic && attrs.length === 0;\n\n  /**\n  * forwardRef creates a new interim component, which we'll take advantage of\n  * instead
  of extending ParentComponent to create _another_ interim class\n  */\n  let WrappedStyledComponent: IStyledComponent;\n\n  const forwardRef = (props, ref) =>\n  // eslint-disable-next-line\n  useStyledComponentImpl(WrappedStyledComponent, props, ref, isStatic);\n\n  forwardRef.displayName = displayName;\n\n  WrappedStyledComponent = ((React.forwardRef(forwardRef): any): IStyledComponent);\n
```

WrappedStyledComponent.attrs = finalAttrs;\n WrappedStyledComponent.componentStyle = componentStyle;\n WrappedStyledComponent.displayName = displayName;\n WrappedStyledComponent.shouldForwardProp = shouldForwardProp;\n\n // this static is used to preserve the cascade of static classes for component selector\n // purposes; this is especially important with usage of the css prop\n WrappedStyledComponent.foldedComponentIds = isTargetStyledComp\n   ? Array.prototype.concat(\n   ((target: any): IStyledComponent).foldedComponentIds,\n   ((target: any): IStyledComponent).styledComponentId\n   )\n   : EMPTY_ARRAY;\n\n WrappedStyledComponent.styledComponentId = styledComponentId;\n\n // fold the underlying StyledComponent target up since we folded the styles\n WrappedStyledComponent.target = isTargetStyledComp\n   ? ((target: any): IStyledComponent).target\n   : target;\n\n WrappedStyledComponent.withComponent = function withComponent(tag: Target) {\n   const { componentId: previousComponentId, ...optionsToCopy } = options;\n\n   const newComponentId =\n   previousComponentId &&\n   `${previousComponentId}-${isTag(tag) ? tag : escape(getComponentName(tag))}`;\n\n   const newOptions = {\n   ...optionsToCopy,\n   attrs: finalAttrs,\n   componentId: newComponentId,\n   };\n\n   return createStyledComponent(tag, newOptions, rules);\n };\n\n Object.defineProperty(WrappedStyledComponent, 'defaultProps', {\n   get() {\n   return this._foldedDefaultProps;\n   },\n\n   set(obj) {\n   this._foldedDefaultProps = isTargetStyledComp\n   ? merge({}, ((target: any): IStyledComponent).defaultProps, obj)\n   : obj;\n   },\n });\n\n if (process.env.NODE_ENV !== 'production') {\n   checkDynamicCreation(displayName, styledComponentId);\n\n   WrappedStyledComponent.warnTooManyClasses = createWarnTooManyClasses(\n   displayName,\n   styledComponentId\n   );\n }\n\n // If the Object prototype is frozen, the \"toString\" property is non-writable. This means that any objects which inherit this property\n // cannot have the property changed using an assignment. If using strict mode, attempting that will cause an error. If not using strict\n // mode, attempting that will be silently ignored.\n // However, we can still explicitly shadow the prototype's \"toString\" property by defining a new \"toString\" property on this object.\n Object.defineProperty(WrappedStyledComponent, 'toString', { value: () => `.${WrappedStyledComponent.styledComponentId}` });\n\n if (isCompositeComponent) {\n   hoist<\n   IStyledStatics,\n $PropertyType<IStyledComponent, 'target'>,\n   { [key: $Keys<IStyledStatics>]: true }\n   >(WrappedStyledComponent, ((target: any): $PropertyType<IStyledComponent, 'target'>), {\n   // all SC-specific things should not be hoisted\n   attrs: true,\n   componentStyle: true,\n   displayName: true,\n   foldedComponentIds: true,\n   shouldForwardProp: true,\n   styledComponentId: true,\n   target: true,\n   withComponent: true,\n   });\n }\n\n return WrappedStyledComponent;\n}\n","// @flow\nimport type { IStyledComponent } from '../types';\nimport getComponentName from './getComponentName';\nimport isTag from './isTag';\n\nexport default function generateDisplayName(\n target: $PropertyType<IStyledComponent, 'target'>\n): string {\n return isTag(target) ? `styled.${target}` : `Styled(${getComponentName(target)})`;\n}\n","/**\n * Convenience function for joining strings to form className chains\n */\nexport default function joinStrings(a:
 ?String, b: ?String): ?String {\n return a && b ? `${a} ${b}` : a || b;\n}\n","// @flow\n\nexport const LIMIT = 200;\n\nexport default (displayName: string, componentId: string) => {\n let generatedClasses = {};\n let warningSeen = false;\n\n return (className: string) => {\n   if (!warningSeen) {\n   generatedClasses[className] = true;\n   if (Object.keys(generatedClasses).length >= LIMIT) {\n   // Unable to find latestRule in test environment.\n   /* eslint-disable no-console, prefer-template */\n   const parsedIdString = componentId ? ` with the id of \"${componentId}\"` : '';\n\n   console.warn(\n   `Over ${LIMIT} classes were generated for component ${displayName}${parsedIdString}.\\n` +\n   'Consider using the attrs method, together with a style object for frequently changed styles.\\n' +\n   'Example:\\n' +\n   ' const Component = styled.div.attrs(props => ({\\n' +\n   '   style: {\\n' +\n   '   background: props.background,\\n' +\n   '   },\\n' +\n   ' }))`width: 100%;`\\n\\n' +\n   ' <Component />'\n   );\n   warningSeen = true;\n   generatedClasses = {};\n   }\n   }\n };\n};\n","// @flow\n// Thanks to ReactDOMFactories for this handy list!\n\nexport default [\n 'a',\n 'abbr',\n 'address',\n 'area',\n 'article',\n 'aside',\n 'audio',\n 'b',\n 'base',\n 'bdi',\n 'bdo',\n 'big',\n 'blockquote',\n 'body',\n 'br',\n

'button',\n 'canvas',\n 'caption',\n 'cite',\n 'code',\n 'col',\n 'colgroup',\n 'data',\n 'datalist',\n 'dd',\n 'del',\n 'details',\n 'dfn',\n 'dialog',\n 'div',\n 'dl',\n 'dt',\n 'em',\n 'embed',\n 'fieldset',\n 'figcaption',\n 'figure',\n 'footer',\n 'form',\n 'h1',\n 'h2',\n 'h3',\n 'h4',\n 'h5',\n 'h6',\n 'head',\n 'header',\n 'hgroup',\n 'hr',\n 'html',\n 'i',\n 'iframe',\n 'img',\n 'input',\n 'ins',\n 'kbd',\n 'keygen',\n 'label',\n 'legend',\n 'li',\n 'link',\n 'main',\n 'map',\n 'mark',\n 'marquee',\n 'menu',\n 'menuitem',\n 'meta',\n 'meter',\n 'nav',\n 'noscript',\n 'object',\n 'ol',\n 'optgroup',\n 'option',\n 'output',\n 'p',\n 'param',\n 'picture',\n 'pre',\n 'progress',\n 'q',\n 'rp',\n 'rt',\n 'ruby',\n 's',\n 'samp',\n 'script',\n 'section',\n 'select',\n 'small',\n 'source',\n 'span',\n 'strong',\n 'style',\n 'sub',\n 'summary',\n 'sup',\n 'table',\n 'tbody',\n 'td',\n 'textarea',\n 'tfoot',\n 'th',\n 'thead',\n 'time',\n 'title',\n 'tr',\n 'track',\n 'u',\n 'ul',\n 'var',\n 'video',\n 'wbr',\n\n // SVG\n 'circle',\n 'clipPath',\n 'defs',\n 'ellipse',\n 'foreignObject',\n 'g',\n 'image',\n 'line',\n 'linearGradient',\n 'marker',\n 'mask',\n 'path',\n 'pattern',\n 'polygon',\n 'polyline',\n 'radialGradient',\n 'rect',\n 'stop',\n 'svg',\n 'text',\n 'textPath',\n 'tspan',\n];\n","// @flow\nimport constructWithOptions from './constructWithOptions';\nimport StyledComponent from '../models/StyledComponent';\nimport domElements from '../utils/domElements';\n\nimport type { Target } from '../types';\n\nconst styled = (tag: Target) => constructWithOptions(StyledComponent, tag);\n\n// Shorthands for all valid HTML Elements\ndomElements.forEach(domElement => {\n styled[domElement] = styled(domElement);\n});\n\nexport default styled;\n","// @flow\nimport { isValidElementType } from 'react-is';\nimport css from './css';\nimport throwStyledError from '../utils/error';\nimport { EMPTY_OBJECT } from '../utils/empties';\n\nimport type { Target } from '../types';\n\nexport default function constructWithOptions(\n componentConstructor: Function,\n tag: Target,\n options: Object = EMPTY_OBJECT\n) {\n if (!isValidElementType(tag)) {\n return throwStyledError(1, String(tag));\n }\n\n /* This is callable directly as a template function */\n // $FlowFixMe: Not typed to avoid destructuring arguments\n const templateFunction =\n (...args) => componentConstructor(tag, options, css(...args));\n\n /* If config methods are called, wrap up a new template function and merge options */\n templateFunction.withConfig = config =>\n constructWithOptions(componentConstructor, tag, { ...options, ...config });\n\n /* Modify/inject new props at runtime */\n templateFunction.attrs = attrs =>\n constructWithOptions(componentConstructor, tag, {\n ...options,\n attrs: Array.prototype.concat(options.attrs, attrs).filter(Boolean),\n });\n\n return templateFunction;\n}\n","// @flow\nimport StyleSheet from '../sheet';\nimport type { RuleSet, Stringifier } from '../types';\nimport flatten from '../utils/flatten';\nimport isStaticRules from '../utils/isStaticRules';\n\nexport default class GlobalStyle {\n componentId: string;\n\n isStatic: boolean;\n\n rules: RuleSet;\n\n constructor(rules: RuleSet, componentId: string) {\n this.rules = rules;\n this.componentId = componentId;\n this.isStatic = isStaticRules(rules);\n\n // pre-register the first instance to ensure global styles\n // load before component ones\n StyleSheet.registerId(this.componentId + 1);\n }\n\n createStyles(\n instance: number,\n executionContext: Object,\n styleSheet: StyleSheet,\n stylis: Stringifier\n) {\n const flatCSS = flatten(this.rules, executionContext, styleSheet, stylis);\n const css = stylis(flatCSS.join(''), '');\n const id = this.componentId + instance;\n\n // NOTE: We use the id as a name as well, since these rules never change\n styleSheet.insertRules(id, id, css);\n }\n\n removeStyles(instance: number, styleSheet: StyleSheet) {\n styleSheet.clearRules(this.componentId + instance);\n }\n\n renderStyles(\n instance: number,\n executionContext: Object,\n styleSheet: StyleSheet,\n stylis: Stringifier\n) {\n if (instance > 2) StyleSheet.registerId(this.componentId + instance);\n\n // NOTE: Remove old styles, then inject the new ones\n this.removeStyles(instance, styleSheet);\n this.createStyles(instance, executionContext, styleSheet, stylis);\n }\n}\n","// @flow\nimport React, { useContext, useLayoutEffect, useRef } from 'react';\nimport { STATIC_EXECUTION_CONTEXT } from '../constants';\nimport GlobalStyle from '../models/GlobalStyle';\nimport { useStyleSheet, useStylis } from '../models/StyleSheetManager';\nimport { ThemeContext } from '../models/ThemeProvider';\nimport type { Interpolation } from '../types';\nimport { checkDynamicCreation } from '../utils/checkDynamicCreation';\nimport determineTheme from '../utils/determineTheme';\nimport generateComponentId from '../utils/generateComponentId';\nimport css from

'./css';\n\ndeclare var __SERVER__: boolean;\n\ntype GlobalStyleComponentPropsType = Object;\n\nexport default function createGlobalStyle(\n strings: Array<string>,\n ...interpolations: Array<Interpolation>\n) {\n const rules = css(strings, ...interpolations);\n const styledComponentId = `sc-global-${generateComponentId(JSON.stringify(rules))}`;\n
const globalStyle = new GlobalStyle(rules, styledComponentId);\n\n if (process.env.NODE_ENV !== 'production') {\n checkDynamicCreation(styledComponentId);\n }\n\n function GlobalStyleComponent(props: GlobalStyleComponentPropsType) {\n const styleSheet = useStyleSheet();\n const stylis = useStylis();\n const theme = useContext(ThemeContext);\n const instanceRef = useRef(styleSheet.allocateGSInstance(styledComponentId));\n\n const instance = instanceRef.current;\n\n if (process.env.NODE_ENV !== 'production' && React.Children.count(props.children)) {\n // eslint-disable-next-line no-console\n console.warn(\n `The global style component ${styledComponentId} was given child JSX. createGlobalStyle does not render children.`\n);\n }\n\n if (\n process.env.NODE_ENV !== 'production' &&\n rules.some(rule => typeof rule === 'string' && rule.indexOf('@import') !== -1)\n) {\n // eslint-disable-next-line no-console\n console.warn(\n `Please do not use @import CSS syntax in createGlobalStyle at this time, as the CSSOM APIs we use in production do not handle it well. Instead, we recommend using a library such as react-helmet to inject a typical <link> meta tag to the stylesheet, or simply embedding it manually in your index.html <head> section for a simpler app.`\n);\n }\n\n if (styleSheet.server) {\n renderStyles(instance, props, styleSheet, theme, stylis);\n }\n\n if (!__SERVER__) {\n // this conditional is fine because it is compiled away for the relevant builds during minification,\n // resulting in a single unguarded hook call\n // eslint-disable-next-line react-hooks/rules-of-hooks\n useLayoutEffect(() => {\n if (!styleSheet.server) {\n renderStyles(instance, props, styleSheet, theme, stylis);\n return () => globalStyle.removeStyles(instance, styleSheet);\n }\n }, [instance, props, styleSheet, theme, stylis]);\n }\n\n return null;\n }\n\n function renderStyles(instance, props, styleSheet, theme, stylis) {\n if (globalStyle.isStatic) {\n globalStyle.renderStyles(instance, STATIC_EXECUTION_CONTEXT, styleSheet, stylis);\n } else {\n const context = {\n ...props,\n theme: determineTheme(props, theme, GlobalStyleComponent.defaultProps),\n };\n\n globalStyle.renderStyles(instance, context, styleSheet, stylis);\n }\n }\n\n // $FlowFixMe\n return React.memo(GlobalStyleComponent);\n}\n","// @flow\n\nimport css from './css';\nimport generateComponentId from '../utils/generateComponentId';\nimport Keyframes from '../models/Keyframes';\n\nimport type { Interpolation, Styles } from '../types';\n\nexport default function keyframes(\n strings: Styles,\n ...interpolations: Array<Interpolation>\n): Keyframes {\n /* Warning if you've used keyframes on React Native */\n if (\n process.env.NODE_ENV
!== 'production' &&\n typeof navigator !== 'undefined' &&\n navigator.product === 'ReactNative'\n) {\n // eslint-disable-next-line no-console\n console.warn(\n '`keyframes` cannot be used on ReactNative, only on the web. To do animation in ReactNative please use Animated.'\n);\n }\n\n const rules = css(strings, ...interpolations).join('');\n const name = generateComponentId(rules);\n return new Keyframes(name, rules);\n}\n","// @flow\n/* eslint-disable no-underscore-dangle */\nimport React from 'react';\nimport { IS_BROWSER, SC_ATTR, SC_ATTR_VERSION, SC_VERSION } from '../constants';\nimport throwStyledError from '../utils/error';\nimport getNonce from '../utils/nonce';\nimport StyleSheet from '../sheet';\nimport StyleSheetManager from './StyleSheetManager';\n\ndeclare var __SERVER__: boolean;\n\nconst CLOSING_TAG_R = /^\\s*<\\/[a-z]/i;\n\nexport default class ServerStyleSheet {\n isStreaming: boolean;\n\n instance: StyleSheet;\n\n sealed: boolean;\n\n constructor() {\n this.instance = new StyleSheet({ isServer: true });\n this.sealed = false;\n }\n\n _emitSheetCSS = (): string => {\n const css = this.instance.toString();\n if (!css) return '';\n\n const nonce = getNonce();\n const attrs = [nonce && `nonce=\"${nonce}\"`, `${SC_ATTR}=\"true\"`, `${SC_ATTR_VERSION}=\"${SC_VERSION}\"`];\n const htmlAttr = attrs.filter(Boolean).join(' ');\n\n return `<style ${htmlAttr}>${css}</style>`;\n };\n\n collectStyles(children: any) {\n if (this.sealed) {\n return throwStyledError(2);\n }\n\n return <StyleSheetManager

sheet={this.instance}>{children}</StyleSheetManager>;\n }\n\n getStyleTags = (): string => {\n   if (this.sealed) {\n   return throwStyledError(2);\n   }\n\n   return this._emitSheetCSS();\n };\n\n getStyleElement = () => {\n if (this.sealed) {\n   return throwStyledError(2);\n   }\n\n   const props = {\n   [SC_ATTR]: '',\n [SC_ATTR_VERSION]: SC_VERSION,\n   dangerouslySetInnerHTML:
 {\n   __html: this.instance.toString(),\n   },\n   };\n\n   const nonce = getNonce();\n   if (nonce) {\n   (props: any).nonce = nonce;\n   }\n\n   // v4 returned an array for this fn, so we'll do the same for v5 for backward compat\n return [<style {...props} key=\"sc-0-0\" />];\n };\n\n // eslint-disable-next-line consistent-return\n interleaveWithNodeStream(input: any) {\n   if (!__SERVER__ || IS_BROWSER) {\n   return throwStyledError(3);\n   } else if (this.sealed) {\n   return throwStyledError(2);\n   }\n\n   if (__SERVER__) {\n this.seal();\n\n   // eslint-disable-next-line global-require\n   const { Readable, Transform } = require('stream');\n\n   const readableStream: Readable = input;\n   const { instance: sheet, _emitSheetCSS } = this;\n\n   const transformer = new Transform({\n   transform: function appendStyleChunks(chunk, /* encoding */ _, callback) {\n   // Get the chunk and retrieve the sheet's
 CSS as an HTML chunk,\n   // then reset its rules so we get only new ones for the next chunk\n   const renderedHtml = chunk.toString();\n   const html = _emitSheetCSS();\n\n   sheet.clearTag();\n\n   // prepend style html to chunk, unless the start of the chunk is a\n   // closing tag in which case append right after that\n   if (CLOSING_TAG_R.test(renderedHtml)) {\n   const endOfClosingTag = renderedHtml.indexOf('>') + 1;\n   const before = renderedHtml.slice(0, endOfClosingTag);\n   const after = renderedHtml.slice(endOfClosingTag);\n\n   this.push(before + html + after);\n   } else {\n   this.push(html + renderedHtml);\n   }\n\n   callback();\n   },\n   });\n\n   readableStream.on('error', err => {\n   // forward the error to the transform stream\n   transformer.emit('error', err);\n   });\n\n   return readableStream.pipe(transformer);\n
    }\n }\n\n seal = () => {\n   this.sealed = true;\n };\n}\n","// @flow\nimport React, { useContext, type AbstractComponent } from 'react';\nimport hoistStatics from 'hoist-non-react-statics';\nimport { ThemeContext } from '../models/ThemeProvider';\nimport determineTheme from '../utils/determineTheme';\nimport getComponentName from '../utils/getComponentName';\n\n// NOTE: this would be the correct signature:\n// export default <Config: { theme?: any }, Instance>(\n// Component: AbstractComponent<Config, Instance>\n//): AbstractComponent<$Diff<Config, { theme?: any }> & { theme?: any }, Instance>\n//\n// but the old build system tooling doesn't support the syntax\n\nexport default (Component: AbstractComponent<*, *>) => {\n // $FlowFixMe This should be React.forwardRef<Config, Instance>\n const WithTheme = React.forwardRef((props, ref) => {\n   const theme = useContext(ThemeContext);\n   // $FlowFixMe defaultProps isn't declared so it can be inferrable\n   const { defaultProps
 } = Component;\n   const themeProp = determineTheme(props, theme, defaultProps);\n\n   if (process.env.NODE_ENV !== 'production' && themeProp === undefined) {\n   // eslint-disable-next-line no-console\n   console.warn(\n   `[withTheme] You are not using a ThemeProvider nor passing a theme prop or a theme in defaultProps in component class \"${getComponentName(\n          Component\n        )}\"`\n   );\n   }\n\n   return <Component {...props} theme={themeProp} ref={ref} />;\n });\n\n hoistStatics(WithTheme, Component);\n\n WithTheme.displayName = `WithTheme(${getComponentName(Component)})`;\n\n return WithTheme;\n};\n","// @flow\nimport { useContext } from 'react';\nimport { ThemeContext } from '../models/ThemeProvider';\n\nconst useTheme = () => useContext(ThemeContext);\n\nexport default useTheme;\n","// @flow\n/* eslint-disable */\n\nimport StyleSheet from './sheet';\nimport { masterSheet } from './models/StyleSheetManager';\n\nexport const __PRIVATE__ =
 {\n StyleSheet,\n masterSheet,\n};\n","// @flow\n/* Import singletons */\nimport isStyledComponent from './utils/isStyledComponent';\nimport css from './constructors/css';\nimport createGlobalStyle from './constructors/createGlobalStyle';\nimport keyframes from './constructors/keyframes';\nimport ServerStyleSheet from './models/ServerStyleSheet';\nimport { SC_VERSION } from './constants';\n\nimport StyleSheetManager, {\n StyleSheetContext,\n StyleSheetConsumer,\n} from './models/StyleSheetManager';\n\n/* Import components */\nimport ThemeProvider, { ThemeContext, ThemeConsumer } from './models/ThemeProvider';\n\n/* Import

Higher Order Components */\nimport withTheme from './hoc/withTheme';\n\n/* Import hooks */\nimport useTheme from './hooks/useTheme';\n\ndeclare var __SERVER__: boolean;\n\n/* Warning if you've imported this file on React Native */\nif (\n process.env.NODE_ENV !== 'production' &&\n typeof navigator !== 'undefined' &&\n navigator.product === 'ReactNative'\n) {\n
// eslint-disable-next-line no-console\n console.warn(\n \"It looks like you've imported 'styled-components' on React Native.\\n\\n\" +\n \"Perhaps you're looking to import 'styled-components/native'?\\n\\n\" +\n 'Read more about this at https://www.styled-components.com/docs/basics#react-native'\n);\n}\n\n/* Warning if there are several instances of styled-components */\nif (process.env.NODE_ENV !== 'production' && process.env.NODE_ENV !== 'test' && typeof window !== 'undefined') {\n window['__styled-components-init__'] = window['__styled-components-init__'] || 0;\n\n if (window['__styled-components-init__'] === 1) {\n // eslint-disable-next-line no-console\n console.warn(\n \"It looks like there are several instances of 'styled-components' initialized in this application. \" +\n 'This may cause dynamic styles to not render properly, errors during the rehydration process, ' +\n 'a missing theme prop, and makes your application bigger without good reason.\\n\\n' +\n 'See https://s-c.sh/2BAXzed for more info.'\n);\n }\n\n window['__styled-components-init__'] += 1;\n}\n\n/* Export everything */\nexport * from './secretInternals';\nexport {\n createGlobalStyle,\n css,\n isStyledComponent,\n keyframes,\n ServerStyleSheet,\n StyleSheetConsumer,\n StyleSheetContext,\n StyleSheetManager,\n ThemeConsumer,\n ThemeContext,\n ThemeProvider,\n useTheme,\n SC_VERSION as version,\n withTheme,\n};\n"],"names":["strings","interpolations","result","i","len","length","push","x","toString","Object","prototype","call","typeOf","EMPTY_ARRAY","freeze","EMPTY_OBJECT","isFunction","test","getComponentName","target","process","env","NODE_ENV","displayName","name","isStyledComponent","styledComponentId","SC_ATTR","REACT_APP_SC_ATTR","SC_VERSION","__VERSION__","IS_BROWSER","window","DISABLE_SPEEDY","Boolean","SC_DISABLE_SPEEDY","REACT_APP_SC_DISABLE_SPEEDY","STATIC_EXECUTION_CONTEXT","ERRORS","format","a","b","c","arguments","forEach","d","replace","throwStyledComponentsError","code","Error","join","trim","DefaultGroupedTag","tag","groupSizes","Uint32Array","indexOfGroup","group","index","this","insertRules","rules","oldBuffer","oldSize","newSize","throwStyledError","set","ruleIndex","l","insertRule","clearGroup","startIndex","endIndex","deleteRule","getGroup","css","getRule","groupIDRegister","Map","reverseRegister","nextFreeGroup","getGroupForId","id","has","get","getIdForGroup","setGroupForId","SELECTOR","MARKER_RE","RegExp","rehydrateNamesFromContent","sheet","content","names","split","registerName","rehydrateSheetFromTag","style","parts","textContent","part","marker","match","parseInt","getTag","getNonce","__webpack_nonce__","makeStyleTag","head","document","parent","createElement","prevStyle","childNodes","child","nodeType","hasAttribute","findLastStyleTag","nextSibling","undefined","setAttribute","nonce","insertBefore","CSSOMTag","element","appendChild","createTextNode","styleSheets","ownerNode","getSheet","rule","_error","cssRules","cssText","TextTag","nodes","node","refNode","removeChild","VirtualTag","_target","splice","SHOULD_REHYDRATE","defaultOptions","isServer","useCSSOMInjection","StyleSheet","options","globalStyles","gs","server","querySelectorAll","getAttribute","parentNode","rehydrateSheet","registerId","reconstructWithOptions","withNames","allocateGSInstance","hasNameForId","add","groupNames","Set","clearNames","clear","clearRules","clearTag","size","selector","outputSheet","AD_REPLACER_R","getAlphabeticChar","String","fromCharCode","generateAlphabeticName","Math","abs","phash","h","charCodeAt","hash","isStaticRules","SEED","ComponentStyle","componentId","baseStyle","staticRulesId","isStatic","baseHash","generateAndInjectStyles","executionContext","styleSheet","stylis","cssStatic","flatten","generateName","cssStaticFormatted","dynamicHash","partRule","partChunk","partString","Array","isArray","cssFormatted","COMMENT_REGEX","COMPLEX_SELECTOR_PREFIX","createStylisInstance","_componentId","_selector","_selectorRegexp","_consecutiveSelfRefRegExp","plugins","Stylis","parsingRules","parseRulesPlugin","toSheet","block","e","context","selectors","parents","line","column","ns","depth","at","delimiter","insertRulePlugin","selfReferenceReplacer","offset","string","indexOf","stringifyRules","prefix","flatCSS","cssStr","use","_","lastIndexOf","parsedRules","reduce","acc","plugin","StyleSheetContext","React","createContext","StyleSheetConsumer","Consumer","StylisContext","masterSheet","masterStylis","useStyleSheet","useContext","useStylis","StyleSheetManager","props","useState","stylisPlugins","setPlugins","contextStyleSheet","useMemo","di

sableCSSOMInjection","disableVendorPrefixes","useEffect","shallowequal","Provider","value","Children","only","children","Keyframes","inject","stylisInstance","resolvedName","_this","getName","uppercaseCheck","uppercasePattern","msPattern","prefixAndLowerCase","char","toLowerCase","hyphenateStyleName","isFalsish","chunk","ruleSet","isReactComponent","isElement","console","warn","isPlainObject","objToCssArray","obj","prevKey","key","hasOwnProperty","isCss","hyphenate","unitless","startsWith","addTag","arg","styles","interleave","invalidHookCallRe","seen","checkDynamicCreation","message","originalConsoleError","error","didNotCallInvalidHook","consoleErrorMessage","consoleErrorArgs","useRef","providedTheme","defaultProps","theme","escapeRegex","dashesAtEnds","escape","str","isTag","charAt","isObject","val","isValidKey","mixin","mixinDeep","rest","ThemeContext","ThemeConsumer","ThemeProvider","outerTheme","themeContext","mergedTheme","mergeTheme","identifiers","createStyledComponent","isTargetStyledComp","isCompositeComponent","attrs","parentComponentId","generateComponentId","generateId","generateDisplayName","finalAttrs","concat","filter","shouldForwardProp","prop","filterFn","elementToBeCreated","WrappedStyledComponent","componentStyle","forwardRef","ref","forwardedComponent","forwardedRef","componentAttrs","foldedComponentIds","resolvedAttrs","attrDef","resolvedAttrDef","useResolvedAttrs","determineTheme","generatedClassName","warnTooManyClasses","className","useInjectedStyle","refToForward","$as","as","isTargetTag","computedProps","propsForElement","validAttr","withComponent","previousComponentId","optionsToCopy","newComponentId","defineProperty","_foldedDefaultProps","merge","generatedClasses","warningSeen","keys","parsedIdString","createWarnTooManyClasses","hoist","styled","constructWithOptions","componentConstructor","isValidElementType","templateFunction","withConfig","config","StyledComponent","domElement","GlobalStyle","createStyles","instance","removeStyles","renderStyles","createGlobalStyle","JSON","stringify","globalStyle","GlobalStyleComponent","current","count","some","memo","keyframes","navigator","product","CLOSING_TAG_R","ServerStyleSheet","_emitSheetCSS","SC_ATTR_VERSION","getStyleTags","sealed","getStyleElement","dangerouslySetInnerHTML","__html","seal","collectStyles","interleaveWithNodeStream","input","require","Transform","Readable","readableStream","transformer","transform","callback","renderedHtml","html","endOfClosingTag","before","slice","after","on","err","emit","pipe","Component","WithTheme","themeProp","hoistStatics","useTheme","__PRIVATE__"],"mappings":"gjBAGA,eACEA,EACAC,WAEMC,EAAAS,CAAAC,EAAAC,EAAAC,E

AQ,GACjCtD,EAAI,EAAGiE,EAAIP,EAAMxD,OAAQF,EAAIiE,EAAGjE,IACnCwD,KAAKN,IAAIgB,WAAW
F,EAAWN,EAAM1D,WAClCmD,WAAWG,KAChBU,QAKNG,WAAA,SAAWb,MACLA,EAAQE,KAAKtD
AQ,KACjBA,EAASsD,KAAKL,WAAWG,GACzBc,EAAaZ,KAAKH,aAAaC,GAC/Be,EAAWD,EAAalE,OAEzB
iD,WAAWG,GAAS,MAEpB,IAAItD,EAAIoE,EAAYpE,EAAIqE,EAAUrE,SAChCkD,IAAIoB,WAAWF,OAK1B
G,SAAA,SASjB,OACHkB,EAAM,MACNlB,GAASE,KAAKtD,QAAqC,IAA3BsD,KAAKL,WAAWG,UACnCk
B,UAGHtE,EAASsD,KAAKL,WAAWG,GACzBc,EAAaZ,KAAKH,aAAaC,GAC/Be,EAAWD,EAAalE,EAErBF,,
EAAIoE,EAAYpE,EAAIqE,EAAUrE,IACrCwE,GAAUhB,KAAKN,IAAIuB,QAAQzE,,GH9ET,mBGiFbwE,QCzF
PE,EAAuC,IAAIC,IAC3CC,EAAuC,IAAID,IAC3CE,EAAgB,EAQPC,EAAgB,SAACC,MACxBL,EAAgBM,IAAA
ID,UACdL,,EAAgBO,IAAIF,QAGvBH,EAAgBI,IAAIH,IAAIH,IACzBA,EAAQK,IAAIF,
jC,EAAkB,GAEf1D,EAAI,EAAGiE,EAAI8B,EAAM7F,OAAQF,EAAIiE,EAAGjE,IAAK,KACtCiG,EAAOF,EA
AM/F,GAAGgD,UACjBiD,OAECC,EAASD,EAAKE,MAAMd,EAAQ,KCJ5C,EAAkC,EAA1B8C,SA
ASF,EAAO,GAAI,IAC5BnB,EAAKmB,EAAO,GAEJ,IAAV5C,IAEF6B,EAAQ,GAAI,IAAF6B,EAAEjB,EAAIzB,GAAG,GAAK,IAAM,IAAM,KAAO,EAAI,GAAK,EA
AOT,EAAImB,EAAO,IAC5CV,EAAMa,SAAS5C,YAAYH,EAAGiE,IAGpCpB,EAAOqB,EAAOlE,GAAGpC,OAAOiF,EAAMvB,MAAMtB,EAAGA,EAAI,IAAMiE

AAsB,GACnE,IAAIX,OACJvF,KAAKwF,WAAYA,GACtBxF,KAAK0F,GACJQ,GAAalG,KAAKkC,YAAU0B,MAIjCuC,mBAAAA,SAAmB5E,UACTvB,KAAK0F,GAAGnE,IAAOvB,KAAK0F,GAAGnE,IAAO,GAAK,KAI7CsB,OAAAA,kBACS7C,KAAKN,MAAQM,KAAKN,KDtEH2F,KCsEgCrF,KAAKwF,SDtErCH,SAAUC,IAAAAA,kBAAmB9H,IAAAAA,OLCxBkC,EKAzB2F,EACK,IAAIL,EAAWxH,GACb8H,EACF,IAAItB,EAASxG,GAEb,IAAImH,EAAQnH,GLJd,IAAIiC,EAAkBC,KADD,IAAACA,EAAUC,EAAUC,EAAUC

AOtB,EAAU3M,UAEhEiO,EAAOhI,MAAM4G,GAKT5G,MAHMyG,YA4BNyB,EAAe7J,EAAK6F,EAAUiE,EA
AQjD,YAAAA,IAAAA,EAAc,SACrDkD,EAAU/J,EAAI7B,QAAQ8J,GAAe,IACrC+B,EAASnE,GAAYiE,EAAAY
A,MAAUjE,QAAckE,OAAcA,SAK7E3B,EAAevB,EACfwB,EAAYxC,EACZyC,EAAkB,IAAIxH,YAAYuH,QA
AgB,KAClDE,EAA4B,IAAIzH,aAAauH,cAEtChB,EAAOyC,IAAWjE,EAAW,GAAKA,EAAUmE,UAdrD3C,EA
AO4C,cAAQzB,GAPwB,SAACO,EAASmB,EAAGlB,GAClC,IAAZD,GAAiBC,EAAUtN,QAAUsN,EAAU,GAA
GmB,YAAY9B,GAAa,IAE7EW,EAAU,GAAKA,EAAU,GAAG7K,QAAQmK,EAAiBmB,KAIDd,EAlD9B,SAA
AI,OACP,IAAbA,EAAgB,KACZqB,EAAc1B,SACpBA,EAAe,GACR0B,OA+DXP,EAAepD,KAAO+B,EAAQ9M
,OAC1B8M,EACG6B,QAAO,SAACC,EAAKC,UAAUA,EAAUC,IAAGZ,EAAAMgE,EAAK
C,EAAO1N,QHnGf,MGqGXhB,WACH,GAEGgO,ME3FIW,GAAgDC,EAAMC,gBACtDC,qBH,GAAkBI,S
ACvCC,GAA6CJ,EAAMC,gBAGnDI,IAFiBD,GAAcD,SAEL,IAAIrG,GAC9BwG4B5C,KAEzC,SAAgB6C,
YACPC,EAAWT,KAAsBM,GAG1C,SAAgBI,YACPD,EAAWJ,KAAkBE,GAGvC,SAAgBC,
ASD,EAAME,eAAtC9C,OAAS+C,OACVC,EAAoBR,KAEpBS,EAAaqB,EAAeC,EAAUC,EAAUC,EAAU

ACP,4BAPgCK,mCAAAA,oBAQrCJ,gBAAqBG,UAAwBC,MAMjDC,IAEIH,IAA0BL,GAAK9N,IAAIgO,KAErCnB,QAAQC,KAAKkB,GACbF,GAAKjJ,IAAAImJ,IAEX,MAAOE,GAGHL,GAAkB/R,KAAKoS,EAAMF,UAE/BF,UAAYE,WAIdnB,QAAQqB,MAAQD,iBC9CNrD,EAAc2D,EAAOC,GAAQ,IAAIC,EAAIC,EAAIC,E

AAOzT,SACPgB,KAAK,KAERoU,EAAgBnB,IAAMc,EAEflQ,EAAcgP,EAAoBuB,IAuEhBtB,EAAwBjG,EAAO
oG,EAAKxK,WAE7DuK,EAAW3U,YAAcA,GAEzByU,EAA2B5G,EAAM8G,WAAWA,IACrBd,MAAQK,EAC/
BO,EAAuBC,eAAiBA,EACxCD,EAAuBzU,YAAcA,,EACrCyU,EAAuBJ,kBAAoBA,,EAI3CI,EAAuBO,mBAAqB
rB,EACxCzI,MAAM/L,UAAUgV,OACZvU,EAAgCoV,mBAChCpV,EAAgCO,mBAEpCb,EAEJmV,EAAuBtU,k
BAAoBA,EAG3CsU,EAAuB7U,OAAS+T,EAC1B/T/T,CA,EAAgCA,OAClCA,EAEJ6U,EAAuBwB,cAAgB,SAAuBnU
,OACvCoU,EAA0CtO,EAAvDqC,YAAqCkM,uIAAkBvO,mBAEzDwO,EACJF,GACGA,OAAuBxD,GAAM5Q,G
AAOA,EAAM0Q,GAAO7S,EAAiBmC,YAQhE4R,GAAsB5R,OALxBqU,GACHtC,MAAOK,EACPjK,YAmM
,IAG+B9T,IAGhDpD,OAAOmX,eAAe5B,EAAwB,eAAgB,CAC5D5D5Q,sBACSzB,KAAKkU,qBAGd3T,aAT
QACGyF,oBAAsB3C,EACvBB4C,GAAM,GAAM3W,EAAgCwS,aAAcvB,GAC1DA,DA,KAIqB,eAAzBhR,QAAQC,I
AAIC,WACd4R,GAAqB3R,EAAaG,GAElCsU,EAAuBc,Bc,4BGnSXvV,EAAqBiK,OAC/BmL,EAAuBmB,GACnCC
Ac,SAEX,SAACjB,OACDiB,IACHD,EAAiBhB,IAAa,EAC1BtW,OAAOwX,KAAKF,GAAkBG,OAAOC,SAAWC,EAAO
oC,KAG3C6X,EAAiB1M,sBAAkCA,MAAiB,GAE1EwG,QAAQC,KACN,iDAAsD1Q,EAAc2W,oQAUtEF,GAA
c,EACdD,EAAmB,KH2QqBI,CAC1C5C5W,EACAG,IAQJjB,OAAOmX,eAAe5B,EAAwB,WAAY,CAAEtE,F,MAAO
,qBAAUsF,EAAuBtU,qBAEhEhGyT,GACFiD,EAAIEpC,EAA0B7U,EAAA0B7D,EAAA0B,GAAA,GAAAA,EAAA,CAAEpC,
ChB1U,aAAa,EACbgV,oBAAoBX,EACpBX,mBAAmBA,EACnBlBlU,mBAAmBA,EACnBP,QAAQ,EACRqW,eAAe,IA
IZxB,EIlUT,ICIMqC,GAAS,SAAChV,mBCCQiV,EACtBC,EACAlV,EACA8F,EAAAA,IAAAA,EAAAkBpI,IAEby
X,EAAmBnV,UACfY,EAAiB,EAAG2G,OAAOvH,QAK9BoV,EAAmBkB,EAAAaF,EAAAlV,EAAAA,SxE,o
CAGzE8T,EAAiBC,WAAa,SAAAC,EAAAC,EAAAC,EAAAC,EAAAC,EAAAC,EAAAC,EAAAC,EAAAC,EAAAC,EAAAC,
AQ,SAAAA,UACvBkD,EAAqBC,EAAsBlV,OACtCtC8F,iM,EAAAA,OAAgBgV,EAAAA,OAAAA,MAAAA,EAAAA,EAAAA,
QiM,MAAOA,GAAAA,OAAOO,EAAAA,OzDwBuBH,GAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,
A,OACA,UACA,QACA,QACA,IACA,OACA,MACA,MACA,MACA,aACA,OACA,KACA,SACA,SACA,UACA,
OACA,OACA,MACA,WACA,OACA,WACA,KACA,MACA,UACA,MACA,SACA,MACA,KACA,KACA,KAC
A,QACA,WACA,aACA,SACA,SACA,OACA,KACA,KACA,KACA,KACA,KACA,KACA,OACA,SACA,SACA,
KACA,OACA,IACA,SACA,MACA,QACA,MACA,MACA,SACA,QACA,SACA,KACA,OACA,OACA,MACA,O
ACA,UACA,OACA,WACA,OACA,QACA,MACA,WACA,SACA,KACA,WACA,SACA,SACA,IACA,QACA,U
ACA,MACA,WACA,IACA,KACA,KACA,OACA,IACA,OACA,SACA,UACA,SACA,QACA,SACA,OACA,SAC
A,QACA,MACA,UACA,MACA,QACA,QACA,KACA,WACA,QACA,KACA,QACA,OACA,QACA,KACA,QA
CA,IACA,KACA,MACA,QACA,MAGA,SACA,WACA,OACA,UACA,gBACA,IACA,QACA,OACA,iBACA,SA
CA,OACA,OACA,UACA,UACA,WACA,iBACA,OACA,OACA,MACA,OACA,WACA,SCnIUT,SAAQ,SAAAi
W,GAClBR,GAAOQ,GAAcR,GAAOQ,UELTC,yBAOPjV,EAAgBgB2H,QACrB3B3H,MAAQA,QAAQA,H,YAAR
ACdG,SAAWN,GAAcxH,GAI9BqF,EAAWS,WAAWhG,KAAK6H,YAAc,8BAG3CuN,aAAA,SACEC,EAAC
EACAC,EACAC,OAAGMrH,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,
OAAGC,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,
C,GAAEIgB,IAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,
EIgN,EAAWC,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,EAAAA,
GAEIgB,I

AMuM,EAAK8H,SAASxY,eACrBmE,EAAK,MAAO,OAEX8C,EAAQhB,oBACA,CAACgB,aAAmBA,MAAa9F,YAAqBuY,gCAC7CvE,OAAOzT,SAASgB,KAAK,SAEfyB,mBAW/BwV,aAAe,kBACTjJ,EAAKkJ,OACAnW,EAAiB,GAGnBiN,EAAK+I,sBAGdI,gBAAkB,oBACZnJ,EAAKkJ,cACAnW,EAAiB,OAGpB8L,UACHpO,GAAU,KxC9Cc,uBACLG,WwC+CpBwY,wBAAyB,CACvByB,OAAQrJ,EAAK8H,SAASxY,eAAIpH,BiH,EAAQhB,WACVgB,IACdC,sI,EAAAYtI,MAAAQA,GAAIhB,CAAAC2H,6BAAAWW,GAAAOuC,IAAAI,mBAAAsDhCkI,KAAAO,WACLtJ,EAAAkkJ,KAAAQAAS,QAAAzAzGTpB,SAAAW,IAAAI9P,EAAAW,CAAAEF,EAAAU,UAASACtCoR,QAAAS,6BAAAchAchBK,cAAAA,SAAAc5c5J,UACRCRlN,KAAAkW,OAACAnW,EAAAiB,GAAAnBmL,gBAAAACU,IAAAkBnK,MAAAOhC,KAAAkqV,UAAAWnI,MAAkCnD6J,yBAAAA,SAAAA,yBAAAA,SAAAA,yBAAAA,SAAAA

* IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/
/**
mixin-deep; https://github.com/jonschlinkert/mixin-deep
Inlined such that it will be consistently transpiled to an IE-compatible syntax.

The MIT License (MIT)

Copyright (c) 2014-present, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE
IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
*/

Found in path(s):
* /styled-components-5-3-11-tgz/package/native/dist/styled-components.native.esm.js
* /styled-components-5-3-11-tgz/package/primitives/dist/styled-components-primitives.esm.js
* /styled-components-5-3-11-tgz/package/primitives/dist/styled-components-primitives.cjs.js
* /styled-components-5-3-11-tgz/package/native/dist/styled-components.native.cjs.js

1.1145 semver 6.3.1

1.1145.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.1146 is-typed-array 1.1.12

1.1146.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1147 which-typed-array 1.1.11

1.1147.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights

to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1148 typed-array-byte-length 1.0.0

1.1148.1 Available under license :

MIT License

Copyright (c) 2020 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1149 typed-array-buffer 1.0.0

1.1149.1 Available under license :

MIT
MIT License

Copyright (c) 2023 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1150 browserslist 4.21.10

1.1150.1 Available under license :

The MIT License (MIT)

Copyright 2014 Andrey Sitnik <andrey@sitnik.ru> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT

OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1151 webpack-hot-middleware 2.25.4

1.1151.1 Available under license :

Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1152 is-core-module 2.13.0

1.1152.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Dave Justice

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1153 @babel/plugin-transform-regenerator 7.22.10

1.1153.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1154 @babel/plugin-transform-unicode-escapes 7.22.10

1.1154.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining

a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1155 @babel/preset-modules 0.1.6-no-external-plugins

1.1155.1 Available under license :

MIT License

Copyright (c) 2020 Babel

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1156 regenerator-transform 0.15.2

1.1156.1 Available under license :

MIT License

Copyright (c) 2014-present, Facebook, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1157 babel-plugin-syntax-decorators 7.22.10

1.1157.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 Jed Watson

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Copyright (C) 2012-2014 by various contributors (see AUTHORS)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
The << Software identified by reference to the Ecma Standard* ("Software")>> is protected by copyright and is being
made available under the "BSD License", included below. This Software may be subject to third party rights (rights from parties other than Ecma International), including patent rights, and no licenses under such third party rights are granted under this license even if the third party concerned is a member of Ecma International. SEE THE ECMA
CODE OF CONDUCT IN PATENT MATTERS AVAILABLE AT http://www.ecma-international.org/memento/codeofconduct.htm FOR
INFORMATION REGARDING THE LICENSING OF PATENT CLAIMS THAT ARE REQUIRED TO IMPLEMENT ECMA INTERNATIONAL STANDARDS*.

Copyright (C) 2012-2013 Ecma International
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:
1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following
disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the

following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the authors nor Ecma International may be used to endorse or promote products derived from
this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE ECMA INTERNATIONAL "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT
SHALL ECMA INTERNATIONAL BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

* Ecma International Standards hereafter means Ecma International Standards as well as Ecma Technical Reports
Copyright (c) 2014-2015 Jason Quense <jason@quense.me>
Original work by respective rule authors; copywrites noted in files.

MIT License

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Copyright (c) jQuery Foundation, Inc. and Contributors, All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL <COPYRIGHT HOLDER> BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1158 handlebarsjs 4.7.8

1.1158.1 Available under license :

Copyright (C) 2011-2019 by Yehuda Katz

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1159 @babel/plugin-transform-dynamic-import 7.22.11

1.1159.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE

LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1160 @babel/plugin-transform-nullish-coalescing-operator 7.22.11

1.1160.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1161 @babel/plugin-transform-export-namespace-from 7.22.11

1.1161.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including

without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1162 @babel/plugin-transform-json-strings 7.22.11

1.1162.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1163 @babel/plugin-transform-optional-catch-binding 7.22.11

1.1163.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1164 @babel/plugin-transform-class-static-block 7.22.11

1.1164.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1165 @babel/plugin-transform-private-property-in-object 7.22.11

1.1165.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1166 @babel/plugin-transform-numeric-separator 7.22.11

1.1166.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1167 @babel/plugin-transform-logical-assignment-operators 7.22.11

1.1167.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1168 @babel/highlight 7.22.13

1.1168.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1169 object.entries 1.1.7

1.1169.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell

copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1170 function.prototype.name 1.1.6

1.1170.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1171 string-prototype-trimstart 1.0.7

1.1171.1 Available under license :

MIT License

Copyright (c) 2023 Sukka

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1172 @babel/helpers 7.22.15

1.1172.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION

OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1173 @babel/generator 7.22.15

1.1173.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1174 @babel/plugin-transform-classes 7.22.15

1.1174.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to

the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1175 @babel/plugin-bugfix-safari-id-destructuring-collision-in-function-expression 7.22.15

1.1175.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1176 @babel/plugin-transform-react-jsx 7.22.15

1.1176.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1177 @babel/plugin-transform-modules-commonjs 7.22.15

1.1177.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1178 @babel/plugin-transform-for-of 7.22.15

1.1178.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1179 babel-helper-create-class-features-plugin 7.22.15

1.1179.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1180 @babel/plugin-transform-parameters 7.22.15

1.1180.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1181 @babel/plugin-transform-object-rest-spread 7.22.15

1.1181.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1182 babel-preset-typescript 7.22.15

1.1182.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the

"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1183 @babel/helper-member-expression-to-functions 7.22.15

1.1183.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1184 babel-helper-create-regexp-features-plugin 7.22.15

1.1184.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 Jed Watson

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Copyright (C) 2012-2014 by various contributors (see AUTHORS)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT

OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
The << Software identified by reference to the Ecma Standard* ("Software)">> is protected by copyright and is being
made available under the "BSD License", included below. This Software may be subject to third party rights (rights from parties other than Ecma International), including patent rights, and no licenses under such third party rights are granted under this license even if the third party concerned is a member of Ecma International. SEE THE ECMA
CODE OF CONDUCT IN PATENT MATTERS AVAILABLE AT http://www.ecma-international.org/memento/codeofconduct.htm FOR
INFORMATION REGARDING THE LICENSING OF PATENT CLAIMS THAT ARE REQUIRED TO IMPLEMENT ECMA INTERNATIONAL STANDARDS*.

Copyright (C) 2012-2013 Ecma International
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the authors nor Ecma International may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE ECMA INTERNATIONAL "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT
SHALL ECMA INTERNATIONAL BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH
DAMAGE.

* Ecma International Standards hereafter means Ecma International Standards as well as Ecma Technical Reports

Copyright (c) 2014-2015 Jason Quense <jason@quense.me>
Original work by respective rule authors; copywrites noted in files.

MIT License

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
Copyright (c) jQuery Foundation, Inc. and Contributors, All Rights Reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright

notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL <COPYRIGHT HOLDER> BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS
OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1185 babel-plugin-transform-typescript 7.22.15

1.1185.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1186 @babel/helper-builder-binary-assignment-operator-visitor 7.22.15

1.1186.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1187 @babel/plugin-bugfix-v8-spread-parameters-in-optional-chaining 7.22.15

1.1187.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1188 immutable 4.3.4

1.1188.1 Available under license :

MIT License

Copyright (c) 2014-present, Lee Byron and other contributors.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1189 arraybuffer.prototype.slice 1.0.2

1.1189.1 Available under license :

MIT License

Copyright (c) 2023 ECMAScript Shims

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1190 safe-array-concat 1.0.1

1.1190.1 Available under license :

MIT License

Copyright (c) 2023 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1191 @babel/parser 7.22.16

1.1191.1 Available under license :

Copyright (C) 2012-2014 by various contributors (see AUTHORS)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1192 string-prototype-trim 1.2.8

1.1192.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1193 string-prototype-trimend 1.0.7

1.1193.1 Available under license :

MIT License

Copyright (c) 2023 Sukka

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1194 cookie 0.5.0

1.1194.1 Available under license :

(The MIT License)

Copyright (c) 2012-2014 Roman Shtylman <shtylman@gmail.com>
Copyright (c) 2015 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the 'Software'), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR
OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1195 debounce 1.2.1

1.1195.1 Available under license :

MIT License

Copyright (c) 2012-2018 The Debounce Contributors. See CONTRIBUTORS.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
Ben Carpenter
Billy Moon
Josh Goldberg
Julian Gruber
Kristofer Selbekk
Matt Mueller
Matthew Mueller
Nathan Rajlich
Oleg Pudeyev
Stephen Mathieson

TJ Holowaychuk
suhaotian
ven

1.1196 @babel/plugin-syntax-class-properties 7.12.13

1.1196.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
 ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1197 @babel/plugin-syntax-async-generators 7.8.4

1.1197.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,

distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1198 @babel/plugin-syntax-optional-catch-binding 7.8.3

1.1198.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1199 @babel/plugin-syntax-numeric-separator 7.10.4

1.1199.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1200 @babel/plugin-syntax-logical-assignment-operators 7.10.4

1.1200.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1201 @babel/plugin-syntax-json-strings 7.8.3

1.1201.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1202 @babel/plugin-syntax-import-meta 7.10.4

1.1202.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1203 @babel/plugin-syntax-object-rest-spread 7.8.3

1.1203.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1204 node-fetch 1.7.3

1.1204.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 David Frank

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1205 @babel/plugin-proposal-private-methods 7.18.6

1.1205.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including

without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1206 @babel/plugin-syntax-private-property-in-object 7.14.5

1.1206.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1207 @babel/plugin-proposal-class-properties 7.18.6

1.1207.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1208 @babel/plugin-proposal-numeric-separator 7.18.6

1.1208.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1209 @babel/plugin-syntax-class-static-block 7.14.5

1.1209.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1210 @babel/regjsgen 0.8.0

1.1210.1 Available under license :

The MIT License (MIT)

Copyright 2014-2020 Benjamin Tan <https://ofcr.se/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1211 @babel/plugin-transform-spread 7.22.5

1.1211.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1212 @babel/plugin-transform-template-literals 7.22.5

1.1212.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1213 @babel/plugin-transform-computed-properties 7.22.5

1.1213.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1214 @babel/plugin-transform-arrow-functions 7.22.5

1.1214.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,

ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1215 @babel/helper-optimise-call-expression 7.22.5

1.1215.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1216 @babel/plugin-transform-shorthand-properties 7.22.5

1.1216.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to

permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1217 @babel/plugin-transform-sticky-regex 7.22.5

1.1217.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1218 @babel/helper-skip-transparent-expression-wrappers 7.22.5

1.1218.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1219 @babel/plugin-transform-dotall-regex 7.22.5

1.1219.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1220 @babel/plugin-transform-async-to-generator 7.22.5

1.1220.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1221 @babel/helper-annotate-as-pure 7.22.5

1.1221.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1222 @babel/plugin-syntax-jsx 7.22.5

1.1222.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE

LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1223 @babel/plugin-syntax-import-attributes 7.22.5

1.1223.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1224 @babel/plugin-transform-unicode-regex 7.22.5

1.1224.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including

without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1225 @babel/plugin-transform-exponentiation-operator 7.22.5

1.1225.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1226 @babel/plugin-transform-class-properties 7.22.5

1.1226.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1227 @babel/plugin-transform-modules-umd 7.22.5

1.1227.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1228 @babel/helper-environment-visitor 7.22.5

1.1228.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1229 @babel/plugin-transform-function-name 7.22.5

1.1229.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1230 @babel/plugin-transform-literals 7.22.5

1.1230.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1231 @babel/plugin-transform-react-display-name 7.22.5

1.1231.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1232 @babel/plugin-transform-unicode-sets-regex 7.22.5

1.1232.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1233 @babel/plugin-transform-duplicate-keys 7.22.5

1.1233.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,

ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1234 @babel/plugin-transform-object-super 7.22.5

1.1234.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1235 @babel/helper-function-name 7.22.5

1.1235.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1236 @babel/plugin-transform-named-capturing-groups-regex 7.22.5

1.1236.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1237 @babel/plugin-syntax-unicode-sets-regex 7.18.6

1.1237.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1238 @babel/plugin-syntax-import-assertions 7.22.5

1.1238.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1239 @babel/plugin-transform-typeof-symbol 7.22.5

1.1239.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1240 @babel/compat-data 7.22.9

1.1240.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the

"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1241 @babel/plugin-transform-new-target 7.22.5

1.1241.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1242 @babel/helper-replace-supers 7.22.9

1.1242.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1243 @babel/plugin-transform-block-scoped-functions 7.22.5

1.1243.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be

included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1244 @babel/plugin-transform-unicode-property-regex 7.22.5

1.1244.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1245 @babel/plugin-transform-private-methods 7.22.5

1.1245.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1246 nan 2.18.0

1.1246.1 Available under license :

The MIT License (MIT)

Copyright (c) 2018 [NAN contributors](<https://github.com/nodejs/nan#wg-members--collaborators>)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN
ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1247 @babel/plugin-transform-react-jsx-development 7.22.5

1.1247.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1248 @babel/plugin-transform-react-pure-annotations 7.22.5

1.1248.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1249 regexp-prototype-flags 1.5.1

1.1249.1 Available under license :

The MIT License (MIT)

Copyright (C) 2014 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1250 define-properties 1.2.1

1.1250.1 Available under license :

The MIT License (MIT)

Copyright (C) 2015 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1251 define-data-property 1.1.0

1.1251.1 Available under license :

MIT License

Copyright (c) 2023 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1252 set-function-name 2.0.1

1.1252.1 Available under license :

MIT License

Copyright (c) Jordan Harband and contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1253 @babel/types 7.22.19

1.1253.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF

MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1254 regenerate-unicode-properties 10.1.1

1.1254.1 Available under license :

Copyright Mathias Bynens <https://mathiasbynens.be/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1255 sass 1.67.0

1.1255.1 Available under license :

Dart Sass license:

Copyright (c) 2016, Google Inc.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Dart SDK license:

Copyright 2012, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google LLC nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

_fe_analyzer_shared license:

Copyright 2019, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions
of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

analyzer, protobuf and protoc_plugin license:

Copyright 2013, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following

disclaimer in the documentation and/or other materials provided
with the distribution.
* Neither the name
of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

archive
license:

The MIT License

Copyright (c) 2013-2021 Brendan Duncan.
All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

---

args, csslib and logging license:

Copyright 2013, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google LLC nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS
SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

async, cli_util, collection, mime, source_map_stack_trace, stream_channel and
typed_data license:

Copyright 2015, the Dart project authors.

Redistribution and
use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright

notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

boolean_selector, meta and shelf_packages_handler license:

Copyright 2016, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this
list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT

OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY
WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

charcode license:

Copyright 2014, the Dart project authors. All rights reserved.
Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT
HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

checked_yaml license:

Copyright 2019, the Dart project authors. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

cli_pkg license:

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall

mean the union of the acting entity and all
other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions
to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its

distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify
the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding
the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or
redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof,
You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format.
We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software

distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

---

cli_repl license:

Copyright (c) 2018, Jennifer Thakar.
All rights reserved.

Redistribution and use in source
and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
* Neither the name of the project nor the names of its contributors may be
  used to endorse or promote products derived from this software without
  specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

convert, crypto, shelf_static and vm_service license:

Copyright 2015, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and
the following
disclaimer in the documentation and/or other materials provided
with the distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

coverage, dart_style, dartdoc, glob, http, http_parser, matcher, path, pool,
pub_semver, source_span, string_scanner, test and watcher license:

Copyright 2014, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS

"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

ffi and package_config license:

Copyright 2019, the Dart project authors.

Redistribution and use in source and binary
forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google LLC nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

file license:

Copyright 2017, the Dart project authors. All rights reserved.
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
    notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
    copyright notice, this list of conditions and the following
    disclaimer
in the documentation and/or other materials provided
    with the distribution.
  * Neither the name of Google Inc. nor the names of its
    contributors may be used to endorse or promote products derived
    from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF
 ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

fixnum, http_multi_server, oauth2, shelf, shelf_web_socket, source_maps and
stack_trace license:

Copyright 2014, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
    notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
    copyright notice, this list of conditions and the following
    disclaimer in the documentation and/or other materials provided

with the distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY
THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

frontend_server_client license:

Copyright 2020, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the
following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED

TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

grinder and webkit_inspection_protocol license:

Copyright 2013, Google Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

html
license:

Copyright (c) 2006-2012 The Authors

Contributors:
James Graham - jg307@cam.ac.uk
Anne van Kesteren - annevankesteren@gmail.com
Lachlan Hunt - lachlan.hunt@lachy.id.au
Matt McDonald - kanashii@kanashii.ca
Sam Ruby - rubys@intertwingly.net
Ian Hickson (Google) - ian@hixie.ch
Thomas Broyer - t.broyer@ltgt.net
Jacques Distler - distler@golem.ph.utexas.edu
Henri Sivonen - hsivonen@iki.fi
Adam Barth - abarth@webkit.org
Eric Seidel - eric@webkit.org
The Mozilla Foundation (contributions from Henri Sivonen since 2008)
David Flanagan (Mozilla) - dflanagan@mozilla.com
Google LLC (contributed the Dart port) - misc@dartlang.org

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

---

io, stream_transform and term_glyph license:

Copyright 2017, the Dart project authors.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided

with the distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED
TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

js license:

Copyright 2012, the Dart project authors.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.
* Neither
the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY

THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

json_annotation
license:

Copyright 2017, the Dart project authors. All rights reserved.
Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

lints license:

Copyright 2021, the Dart project authors.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN
CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

markdown license:

Copyright 2012, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific
prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS

"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

native_synchronization license:

Copyright 2023, the Dart project authors.

Redistribution and use in source and binary forms, with or
 without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google LLC nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL,
 EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

node_interop license:

Copyright (c) 2017, Anatoly Pulyaevskiy.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:
  * Redistributions of source code must retain the above copyright
    notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above copyright
    notice, this list of conditions and the following disclaimer in the
     documentation and/or other materials provided with the distribution.
  * Neither the name of the <organization> nor the
    names of its contributors may be used to endorse or promote products
    derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL <COPYRIGHT HOLDER> BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY
 OF SUCH DAMAGE.

---

node_preamble license:

The MIT License (MIT)

Copyright (c) 2015 Michael Bullington

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS
BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

===

Copyright 2012, the Dart project authors. All rights reserved.
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:
  * Redistributions of source code must retain the above copyright
    notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
    copyright notice, this list of conditions and the following
    disclaimer in the documentation and/or other materials provided
    with the distribution.
  * Neither the name of Google Inc. nor the names of its
    contributors may be used to endorse or promote products derived
    from this software without specific prior written permission.
THIS SOFTWARE IS
PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

petitparser and xml license:

The MIT License

Copyright (c) 2006-2023 Lukas Renggli.
All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining

a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

---

pointycastle
license:

Copyright (c) 2000 - 2019 The Legion of the Bouncy Castle Inc. (https://www.bouncycastle.org)

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES
OR OTHER LIABILITY, WHETHER
IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

---

pub_api_client license:

MIT License

Copyright (c) 2020 Leo Farias

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED
TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

---

pubspec license:

Copyright (c) 2015, Anders Holmgren.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:
  * Redistributions of source code must retain the above copyright
    notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above copyright
    notice, this list of conditions and the following disclaimer in the
    documentation and/or other materials provided with
 the distribution.
  * Neither the name of the <organization> nor the
    names of its contributors may be used to endorse or promote products
    derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED

WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL <COPYRIGHT HOLDER> BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

pubspec_parse
license:

Copyright 2018, the Dart project authors.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google LLC nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

quiver and retry license:

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration
files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of,

the Work and Derivative
Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor"
shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only
to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without

modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including,
without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other
commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate
notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include

the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions
and
limitations under the License.

---

test_api and test_core license:

Copyright 2018, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR
IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT

LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

test_descriptor and web_socket_channel license:

Copyright 2016, the Dart project authors.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google LLC nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

test_process license:

Copyright 2017, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
    notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
    copyright notice, this list of conditions and the following
    disclaimer in the documentation and/or other materials provided
    with the distribution.
  * Neither the name of Google LLC nor the
 names of its
    contributors may be used to endorse or promote products derived
    from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

uri license:

Copyright
 2013, the Dart project authors. All rights reserved.
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:
  * Redistributions of source code must retain the above copyright
    notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
    copyright notice, this list of conditions and the following
    disclaimer in the documentation and/or other materials provided
    with the distribution.
  * Neither the name of Google Inc. nor the names of its
    contributors may be used to endorse or promote products derived
    from this software without specific prior written permission.
THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT

LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

yaml license:

Copyright (c) 2014, the Dart project authors.
Copyright (c) 2006, Kirill Simonov.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense,
and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1256 es-abstract 1.22.2

1.1256.1 Available under license :

The MIT License (MIT)

Copyright (C) 2015 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal

in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1257 types-json-schema 7.0.13

1.1257.1 Available under license :

MIT License

Copyright (c) Microsoft Corporation.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF
CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE

1.1258 @babel/helper-remap-async-to-generator 7.22.20

1.1258.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1259 @babel/helper-member-expression-to-functions 7.23.0

1.1259.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1260 @babel/helper-wrap-function 7.22.20

1.1260.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1261 @babel/helper-replace-supers 7.22.20

1.1261.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,

distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1262 @babel/preset-react 7.22.15

1.1262.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1263 stax-api 4.2.1

1.1263.1 Available under license :

This copy of Stax2 API is licensed under the
Simplified BSD License (also known as "2-clause BSD", or "FreeBSD License")
See the License for details about distribution rights, and the
specific rights regarding derivate works.

You may obtain a copy of the License at:

http://www.opensource.org/licenses/bsd-license.php

with details of:

<COPYRIGHT HOLDER> = FasterXML.com
<YEAR> = 2010-

1.1264 log4javascript 1.4.16

1.1264.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,

each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided

that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
   the Work or Derivative Works thereof, You may choose to offer,
   and charge a fee for, acceptance of support, warranty, indemnity,
   or other liability obligations and/or rights consistent with this
   License. However, in accepting such obligations, You may act only
   on Your own behalf and on Your sole responsibility, not on behalf
   of any other Contributor, and only if You agree to indemnify,
   defend, and hold each Contributor harmless for any liability
    incurred by, or claims asserted against, such Contributor by reason
   of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

   To apply the Apache License to your work, attach the following
   boilerplate notice, with the fields enclosed by brackets "[]"
   replaced with your own identifying information. (Don't include
   the brackets!) The text should be enclosed in the appropriate
   comment syntax for the file format. We also recommend that a
   file or class name and description of purpose be included on the
   same "printed page" as the copyright notice for easier
   identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

    http://www.apache.org/licenses/LICENSE-2.0

 Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1265 atob 2.1.2

1.1265.1 Available under license :

Creative Commons Legal Code

Attribution 3.0 Unported

 CREATIVE COMMONS CORPORATION IS NOT A LAW FIRM AND DOES NOT PROVIDE
 LEGAL SERVICES. DISTRIBUTION OF THIS LICENSE DOES NOT CREATE AN

ATTORNEY-CLIENT RELATIONSHIP. CREATIVE COMMONS PROVIDES THIS INFORMATION ON AN "AS-IS" BASIS. CREATIVE COMMONS MAKES NO WARRANTIES REGARDING THE INFORMATION PROVIDED, AND DISCLAIMS LIABILITY FOR DAMAGES RESULTING FROM ITS USE.

License

THE WORK (AS DEFINED BELOW) IS PROVIDED UNDER THE TERMS OF THIS CREATIVE COMMONS PUBLIC LICENSE ("CCPL" OR "LICENSE"). THE WORK IS PROTECTED BY COPYRIGHT AND/OR OTHER APPLICABLE LAW. ANY USE OF THE WORK OTHER THAN AS AUTHORIZED UNDER THIS LICENSE OR COPYRIGHT LAW IS PROHIBITED.

BY EXERCISING ANY RIGHTS TO THE WORK PROVIDED HERE, YOU ACCEPT AND AGREE TO BE BOUND BY THE TERMS OF THIS LICENSE. TO THE EXTENT THIS LICENSE MAY BE CONSIDERED TO BE A CONTRACT, THE LICENSOR GRANTS YOU THE RIGHTS CONTAINED HERE IN CONSIDERATION OF YOUR ACCEPTANCE OF SUCH TERMS AND CONDITIONS.

1. Definitions

a. "Adaptation" means a work based upon the Work, or upon the Work and other pre-existing works, such as a translation, adaptation, derivative work, arrangement of music or other alterations of a literary or artistic work, or phonogram or performance and includes cinematographic adaptations or any other form in which the Work may be recast, transformed, or adapted including in any form recognizably derived from the original, except that a work that constitutes a Collection will not be considered an Adaptation for the purpose of this License. For the avoidance of doubt, where the Work is a musical work, performance or phonogram, the synchronization of the Work in timed-relation with a moving image ("synching") will be considered an Adaptation for the purpose of this License.

b. "Collection" means a collection of literary or artistic works, such as encyclopedias and anthologies, or performances, phonograms or broadcasts, or other works or subject matter other than works listed in Section 1(f) below, which, by reason of the selection and arrangement of their contents, constitute intellectual creations, in which the Work is included in its entirety in unmodified form along with one or more other contributions, each constituting separate and independent works in themselves, which together are assembled into a collective whole. A work that constitutes a Collection will not be considered an Adaptation (as defined above) for the purposes of this License.

c. "Distribute" means to make available to the public the original and copies of the Work or Adaptation, as appropriate, through sale or other transfer of ownership.

d. "Licensor" means the individual, individuals, entity or entities that offer(s) the Work under the terms of this License.

e. "Original Author" means, in the case of a literary or artistic work, the individual, individuals, entity or entities who created the Work or if no individual or entity can be identified, the publisher; and in addition (i) in the case of a performance the actors, singers, musicians, dancers, and other persons who act, sing, deliver, declaim, play in, interpret or otherwise perform literary or artistic works or expressions of folklore; (ii) in the case of a phonogram the producer being the person or legal entity who first fixes the sounds of a performance or other sounds; and, (iii) in the case of broadcasts, the organization that transmits the broadcast.

f. "Work" means the literary and/or artistic work offered under the terms of this License including without limitation any production in the literary, scientific and artistic domain, whatever may be the mode or form of its expression including digital form, such as a book, pamphlet and other writing; a lecture, address, sermon or other work of the same nature; a dramatic or dramatico-musical work; a choreographic work or entertainment in dumb show; a musical composition with or without words; a cinematographic work to which are assimilated works expressed by a process analogous to cinematography; a work of drawing, painting, architecture, sculpture, engraving or lithography; a photographic work to which are assimilated works expressed by a process analogous to photography; a work of applied art; an illustration, map, plan, sketch or three-dimensional work relative to geography, topography, architecture or science; a performance; a broadcast; a phonogram; a compilation of data to the extent it is protected as a copyrightable work; or a work performed by a variety or circus performer to the extent it is not otherwise considered a literary or artistic work.

g. "You" means an individual or entity exercising rights under this License who has not previously violated the terms of this License with respect to the Work, or who has received express permission from the Licensor to exercise rights under this License despite a previous violation.

h. "Publicly Perform" means to perform public recitations of the Work and to communicate to the public those public recitations, by any means or process, including by wire or wireless means or public digital performances; to make available to the public Works in such a way that members of the public may access these Works from a place and at a place individually chosen by them; to perform the Work to the public by any means or process and the communication to the public of the performances of the Work, including by public digital performance; to broadcast and rebroadcast the Work by any means including signs, sounds or images.

i. "Reproduce" means to make copies of the Work by any means including without limitation by sound or visual recordings and the right of fixation and reproducing fixations of the Work, including storage of a protected performance or phonogram in digital form or other electronic medium.

2. Fair Dealing Rights. Nothing in this License is intended to reduce, limit, or restrict any uses free from copyright or rights arising from limitations or exceptions that are provided for in connection with the copyright protection under copyright law or other applicable laws.

3. License Grant. Subject to the terms and conditions of this License, Licensor hereby grants You a worldwide, royalty-free, non-exclusive, perpetual (for the duration of the applicable copyright) license to exercise the rights in the Work as stated below:

a. to Reproduce the Work, to incorporate the Work into one or more Collections, and to Reproduce the Work as incorporated in the Collections;
b. to create and Reproduce Adaptations provided that any such Adaptation, including any translation in any medium, takes reasonable steps to clearly label, demarcate or otherwise identify that changes were made to the original Work. For example, a translation could be marked "The original work was translated from English to Spanish," or a modification could indicate "The original work has been modified.";
c. to Distribute and Publicly Perform the Work including as incorporated in Collections; and,
d. to Distribute and Publicly Perform Adaptations.
e. For the avoidance of doubt:

i. Non-waivable Compulsory License Schemes. In those jurisdictions in which the right to collect royalties through any statutory or compulsory licensing scheme cannot be waived, the Licensor reserves the exclusive right to collect such royalties for any exercise by You of the rights granted under this License;
ii. Waivable Compulsory License Schemes. In those jurisdictions in which the right to collect royalties through any statutory or compulsory licensing scheme can be waived, the Licensor waives the exclusive right to collect such royalties for any exercise by You of the rights granted under this License; and,
iii. Voluntary License Schemes. The Licensor waives the right to collect royalties, whether individually or, in the event that the Licensor is a member of a collecting society that administers voluntary licensing schemes, via that society, from any exercise by You of the rights granted under this License.

The above rights may be exercised in all media and formats whether now known or hereafter devised. The above rights include the right to make such modifications as are technically necessary to exercise the rights in other media and formats. Subject to Section 8(f), all rights not expressly granted by Licensor are hereby reserved.

4. Restrictions. The license granted in Section 3 above is expressly made subject to and limited by the following restrictions:

a. You may Distribute or Publicly Perform the Work only under the terms

of this License. You must include a copy of, or the Uniform Resource Identifier (URI) for, this License with every copy of the Work You Distribute or Publicly Perform. You may not offer or impose any terms on the Work that restrict the terms of this License or the ability of the recipient of the Work to exercise the rights granted to that recipient under the terms of the License. You may not sublicense the Work. You must keep intact all notices that refer to this License and to the disclaimer of warranties with every copy of the Work You Distribute or Publicly Perform. When You Distribute or Publicly Perform the Work, You may not impose any effective technological measures on the Work that restrict the ability of a recipient of the Work from You to exercise the rights granted to that recipient under the terms of the License. This Section 4(a) applies to the Work as incorporated in a Collection, but this does not require the Collection apart from the Work itself to be made subject to the terms of this License. If You create a Collection, upon notice from any Licensor You must, to the extent practicable, remove from the Collection any credit as required by Section 4(b), as requested. If You create an Adaptation, upon notice from any Licensor You must, to the extent practicable, remove from the Adaptation any credit as required by Section 4(b), as requested.

b. If You Distribute, or Publicly Perform the Work or any Adaptations or Collections, You must, unless a request has been made pursuant to Section 4(a), keep intact all copyright notices for the Work and provide, reasonable to the medium or means You are utilizing: (i) the name of the Original Author (or pseudonym, if applicable) if supplied, and/or if the Original Author and/or Licensor designate another party or parties (e.g., a sponsor institute, publishing entity, journal) for attribution ("Attribution

Parties") in Licensor's copyright notice,

terms of service or by other reasonable means, the name of such party or parties; (ii) the title of the Work if supplied; (iii) to the extent reasonably practicable, the URI, if any, that Licensor specifies to be associated with the Work, unless such URI does not refer to the copyright notice or licensing information for the Work; and (iv) , consistent with Section 3(b), in the case of an Adaptation,

a credit identifying the use of the Work in the Adaptation (e.g., "French translation of the Work by Original Author," or "Screenplay based on original Work by Original Author"). The credit required by this Section 4 (b) may be implemented in any reasonable manner; provided, however, that in the case of a Adaptation or Collection, at a minimum such credit will appear, if a credit for all contributing authors of the Adaptation or Collection appears, then as part of these credits and in a manner
at least as prominent as the credits for the other contributing authors. For the avoidance of doubt, You may only use the credit required by this Section for the purpose of attribution in the manner set out above and, by exercising Your rights under this License, You may not implicitly or explicitly assert or imply any connection with, sponsorship or endorsement by the Original Author, Licensor and/or Attribution Parties, as appropriate, of You or Your use of the Work, without the separate, express prior written permission of the Original Author, Licensor and/or Attribution Parties.

c. Except as otherwise agreed in writing by the Licensor or as may be otherwise permitted by applicable law, if You Reproduce, Distribute or Publicly Perform the Work either by itself or as part of any Adaptations or Collections, You must not distort, mutilate, modify or take other derogatory action in relation to the Work which would be prejudicial
to the Original Author's honor or reputation. Licensor agrees that in those jurisdictions (e.g. Japan), in which any exercise of the right granted in Section 3(b) of this License (the right to make Adaptations) would be deemed to be a distortion, mutilation, modification or other derogatory action prejudicial to the Original Author's honor and reputation, the Licensor will waive or not assert, as appropriate, this Section, to the fullest extent permitted by the applicable national law, to enable You to reasonably exercise Your right under Section 3(b) of this License (right to make Adaptations) but not otherwise.

5. Representations, Warranties and Disclaimer

UNLESS OTHERWISE MUTUALLY AGREED TO BY THE PARTIES IN WRITING, LICENSOR OFFERS THE WORK AS-IS AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE WORK, EXPRESS, IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTIBILITY, FITNESS FOR A
PARTICULAR PURPOSE, NONINFRINGEMENT, OR THE ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE OF ABSENCE OF ERRORS, WHETHER OR NOT DISCOVERABLE. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES, SO SUCH EXCLUSION MAY NOT APPLY TO YOU.

6. Limitation on Liability. EXCEPT TO THE EXTENT REQUIRED BY APPLICABLE

LAW, IN NO EVENT WILL LICENSOR BE LIABLE TO YOU ON ANY LEGAL THEORY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES ARISING OUT OF THIS LICENSE OR THE USE OF THE WORK, EVEN IF LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

7. Termination

a. This License and the rights granted hereunder will terminate automatically upon any breach by You of the terms of this License. Individuals or entities who have received Adaptations or Collections from You under this License, however, will not have their licenses terminated provided such individuals or entities remain in full compliance with those licenses. Sections 1, 2, 5, 6, 7, and 8 will survive any termination of this License.

b. Subject to the above terms and conditions, the license granted here is perpetual (for the duration of the applicable copyright in the Work). Notwithstanding the above, Licensor reserves the right to release the Work under different license terms or to stop distributing the Work at any time; provided, however that any such election will not serve to withdraw this License (or any other license that has been, or is required to be, granted under the terms of this License), and this License will continue in full force and effect unless terminated as stated above.

8. Miscellaneous

a. Each time You Distribute or Publicly Perform the Work or a Collection, the Licensor offers to the recipient a license to the Work on the same terms and conditions as the license granted to You under this License.

b. Each time You Distribute or Publicly Perform an Adaptation, Licensor offers to the recipient a license to the original Work on the same terms and conditions as the license granted to You under this License.

c. If any provision of this License is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this License, and without further action by the parties to this agreement, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.

d. No term or provision of this License shall be deemed waived and no breach consented to unless such waiver or consent shall be in writing and signed by the party to be charged with such waiver or consent.

e. This License constitutes the entire agreement between the parties with respect to the Work licensed here. There are no understandings, agreements or representations with respect to the Work not specified here. Licensor shall not be bound by any additional provisions that may appear in any communication from You. This License may not be

modified without the mutual written agreement of the Licensor and You.

f. The rights granted under, and the subject matter referenced, in this License were drafted utilizing the terminology of the Berne Convention for the Protection of Literary and Artistic Works (as amended on September 28, 1979), the Rome Convention of 1961, the WIPO Copyright Treaty of 1996, the WIPO Performances and Phonograms Treaty of 1996 and the Universal Copyright Convention (as revised on July 24, 1971). These rights and subject matter take effect in the relevant jurisdiction in which the License terms are sought to be enforced according to the corresponding provisions of the implementation of those treaty provisions in the applicable national law. If the standard suite of rights granted under applicable copyright law includes additional rights not granted under this License, such additional rights are deemed to be included in the License; this License is not intended to restrict the license of any rights under applicable law.

Creative Commons Notice

Creative Commons is not a party to this License, and makes no warranty whatsoever in connection with the Work. Creative Commons will not be liable to You or any party on any legal theory for any damages whatsoever, including without limitation any general, special, incidental or consequential damages arising in connection to this license. Notwithstanding the foregoing two (2) sentences, if Creative Commons has expressly identified itself as the Licensor hereunder, it shall have all rights and obligations of Licensor.

Except for the limited purpose of indicating to the public that the Work is licensed under the CCPL, Creative Commons does not authorize the use by either party of the trademark "Creative Commons" or any related trademark or logo of Creative Commons without the prior written consent of Creative Commons. Any permitted use will be in compliance with Creative Commons' then-current trademark usage guidelines, as may be published on its website or otherwise made available upon request from time to time. For the avoidance of doubt, this trademark restriction does not form part of this License.

Creative Commons may be contacted at http://creativecommons.org/.

At your option you may choose either of the following licenses:

* The MIT License (MIT)
* The Apache License 2.0 (Apache-2.0)

The MIT License (MIT)

Copyright (c) 2015 AJ ONeal

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect,
to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity

exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an
example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means
any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of,

publicly
display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted. If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent
infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text
file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and

wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices
cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to
use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract,
or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the

Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "{}" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright 2015 AJ ONeal

Licensed
under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1266 ajv 6.12.6

1.1266.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015-2017 Evgeny Poberezkin

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1267 express 4.18.2

1.1267.1 Available under license :

(The MIT License)

Copyright (c) 2009-2014 TJ Holowaychuk <tj@vision-media.ca>
Copyright (c) 2013-2014 Roman Shtylman <shtylman+expressjs@gmail.com>
Copyright (c) 2014-2015 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.

IN NO EVENT
SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1268 node-fetch 2.7.0

1.1268.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 David Frank

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1269 ramda 0.28.0

1.1269.1 Available under license :

The MIT License (MIT)

Copyright (c) 2013-2020 Scott Sauyet and Michael Hurley

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1270 webpack 4.47.0

1.1270.1 Available under license :

Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1271 merge 1.2.1

1.1271.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 yeikos

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal

in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1272 y18n 4.0.3

1.1272.1 Available under license :

Copyright (c) 2015, Contributors

Permission to use, copy, modify, and/or distribute this software for any purpose
with or without fee is hereby granted, provided that the above copyright notice
and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS
OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1273 terser 4.8.1

1.1273.1 Available under license :

BSD-2-Clause
UglifyJS is released under the BSD license:

Copyright 2012-2018 (c) Mihai Bazon <mihai.bazon@gmail.com>

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions

are met:

* Redistributions of source code must retain the above
  copyright notice, this list of conditions and the following
  disclaimer.

* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials
  provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDER AS IS AND ANY
EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY,
OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED
 TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR
TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF
THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.

1.1274 netmask 2.0.2

1.1274.1 Available under license :

MIT

1.1275 hoek 2.16.3

1.1275.1 Available under license :

Copyright (c) 2011-2014, Walmart and other contributors.
Copyright (c) 2011, Yahoo Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:
* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.
* The names of any contributors may not be used to endorse or promote
  products derived from this software without specific prior written

permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDERS AND CONTRIBUTORS BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

* * *

The complete list of contributors can be found at: https://github.com/hapijs/hapi/graphs/contributors
Portions of this project were initially based on the Yahoo! Inc. Postmile project,
published at https://github.com/yahoo/postmile.

1.1276 html-minifier 3.5.21

1.1276.1 Available under license :

Copyright (c) 2010-2018 Juriy "kangax" Zaytsev

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

1.1277 is-svg 2.1.0

1.1277.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1278 color-string 0.3.0

1.1278.1 Available under license :

Copyright (c) 2011 Heather Arthur <fayearthur@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND

NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1279 combined-stream 1.0.8

1.1279.1 Available under license :

Copyright (c) 2011 Debuggable Limited <felix@debuggable.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1280 delayed-stream 1.0.0

1.1280.1 Available under license :

No license file was found, but licenses were detected in source scan.

delayed-stream

Buffers events from a stream until you are ready to handle them.

Installation

``` bash
npm install delayed-stream
```

Usage

The following example shows how to write a http echo server that delays its response by 1000 ms.

``` javascript
var DelayedStream = require('delayed-stream');
var http = require('http');

http.createServer(function(req, res) {
 var delayed = DelayedStream.create(req);

 setTimeout(function() {
   res.writeHead(200);
   delayed.pipe(res);
 }, 1000);
});
```

If you are not using `Stream#pipe`, you can also manually release the buffered events by calling `delayedStream.resume()`:

``` javascript
var delayed = DelayedStream.create(req);

setTimeout(function() {
 // Emit all buffered events and resume underlaying source
 delayed.resume();
}, 1000);
```

Implementation

In order to use this meta stream properly, here are a few things you should know about the implementation.

Event Buffering / Proxying

All events of the `source` stream are hijacked by overwriting the `source.emit` method. Until node implements a catch-all event listener, this is the only way.

However, delayed-stream still continues to emit all events it captures on the `source`, regardless of whether you have released the delayed stream yet or not.

Upon creation, delayed-stream captures all `source` events and stores them in an internal event buffer. Once `delayedStream.release()` is called, all buffered events are emitted on the `delayedStream`, and the event buffer is

cleared. After that, delayed-stream merely acts as a proxy for the underlaying source.

Error handling

Error events on `source` are buffered / proxied just like any other events. However, `delayedStream.create` attaches a no-op `'error'` listener to the `source`. This way you only have to handle errors on the `delayedStream` object, rather than in two places.

Buffer limits

delayed-stream provides
 a `maxDataSize` property that can be used to limit
the amount of data being buffered. In order to protect you from bad `source` streams that don't react to `source.pause()`, this feature is enabled by default.

API

DelayedStream.create(source, [options])

Returns a new `delayedStream`. Available options are:

* `pauseStream`
* `maxDataSize`

The description for those properties can be found below.

delayedStream.source

The `source` stream managed by this object. This is useful if you are passing your `delayedStream` around, and you still want to access properties on the `source` object.

delayedStream.pauseStream = true

Whether to pause the underlaying `source` when calling `DelayedStream.create()`. Modifying this property afterwards has no effect.

delayedStream.maxDataSize = 1024 * 1024

The amount of data to buffer before emitting an `error`.

If the underlaying source is emitting `Buffer` objects, the `maxDataSize` refers to bytes.

If the underlaying source

is emitting JavaScript strings, the size refers to
characters.

If you know what you are doing, you can set this property to `Infinity` to
disable this feature. You can also modify this property during runtime.

delayedStream.dataSize = 0

The amount of data buffered so far.

delayedStream.readable

An ECMA5 getter that returns the value of `source.readable`.

delayedStream.resume()

If the `delayedStream` has not been released so far, `delayedStream.release()`
is called.

In either case, `source.resume()` is called.

delayedStream.pause()

Calls `source.pause()`.

delayedStream.pipe(dest)

Calls `delayedStream.resume()` and then proxies the arguments to `source.pipe`.

delayedStream.release()

Emits and clears all events that have been buffered up so far. This does not
resume the underlaying source, use `delayedStream.resume()` instead.

License

delayed-stream is licensed under the MIT license.

Found in path(s):
* /fis-components-delayed-stream-1-0-0-0-g42ac44e-1-tar-gz/fis-components-delayed-stream-3c3d86f/Readme.md

1.1281 ansi-styles 3.2.1

1.1281.1 Available under license :

MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1282 side-channel 1.0.4

1.1282.1 Available under license :

MIT License

Copyright (c) 2019 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1283 function-bind 1.1.1

1.1283.1 Available under license :

Copyright (c) 2013 Raynos.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1284 gensync 1.0.0-beta.2

1.1284.1 Available under license :

Copyright 2018 Logan Smyth <loganfsmyth@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1285 js-tokens 4.0.0

1.1285.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014, 2015, 2016, 2017, 2018 Simon Lydell

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1286 @jridgewell/set-array 1.1.2

1.1286.1 Available under license :

Copyright 2022 Justin Ridgewell <jridgewell@google.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1287 globals 11.12.0

1.1287.1 Available under license :

MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1288 has-flag 3.0.0

1.1288.1 Available under license :

MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1289 has-proto 1.0.1

1.1289.1 Available under license :

MIT License

Copyright (c) 2022 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1290 escape-string-regexp 1.0.5

1.1290.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1291 raw-body 2.5.1

1.1291.1 Available under license :

The MIT License (MIT)

Copyright (c) 2013-2014 Jonathan Ong <me@jongleberry.com>
Copyright (c) 2014-2022 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES
OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1292 object-inspect 1.12.3

1.1292.1 Available under license :

MIT License

Copyright (c) 2013 James Halliday

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is

furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1293 isobject 3.0.1

1.1293.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1294 array-flatten 1.1.1

1.1294.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Blake Embrey (hello@blakeembrey.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1295 utils-merge 1.0.1

1.1295.1 Available under license :

The MIT License (MIT)

Copyright (c) 2013-2017 Jared Hanson

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1296 yallist 3.1.1

1.1296.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR
IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.1297 ee-first 1.1.1

1.1297.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Jonathan Ong me@jongleberry.com

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1298 is-plain-object 2.0.4

1.1298.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1299 chalk 2.4.2

1.1299.1 Available under license :

MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN

AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1300 depd 2.0.0

1.1300.1 Available under license :

(The MIT License)

Copyright (c) 2014-2018 Douglas Christopher Wilson

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1301 to-fast-properties 2.0.0

1.1301.1 Available under license :

MIT License

Copyright (c) 2014 Petka Antonov
2015 Sindre Sorhus

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1302 object-assign 4.1.1

1.1302.1 Available under license :

The MIT License (MIT)

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1303 call-bind 1.0.2

1.1303.1 Available under license :

MIT License

Copyright (c) 2020 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell

copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1304 @babel/helper-validator-identifier 7.22.20

1.1304.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1305 @babel/code-frame 7.22.13

1.1305.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1306 get-intrinsic 1.2.1

1.1306.1 Available under license :

MIT License

Copyright (c) 2020 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1307 loose-envify 1.4.0

1.1307.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 Andres Suarez <zertosh@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1308 node-releases 2.0.13

1.1308.1 Available under license :

The MIT License

Copyright (c) 2017 Sergey Rubanov (https://github.com/chicoxyzzy)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1309 @babel/helper-environment-visitor 7.22.20

1.1309.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1310 @jridgewell/gen-mapping 0.3.3

1.1310.1 Available under license :

Copyright 2022 Justin Ridgewell <jridgewell@google.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1311 @ampproject/remapping 2.2.1

1.1311.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership

of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual,

worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or

documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,

indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1312 @babel/helper-simple-access 7.22.5

1.1312.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1313 @babel/helper-split-export-declaration 7.22.6

1.1313.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1314 babel-helper-compilation-targets 7.22.15

1.1314.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1315 @jridgewell/resolve-uri 3.1.1

1.1315.1 Available under license :

Copyright 2019 Justin Ridgewell <jridgewell@google.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal

in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1316 @jridgewell/sourcemap-codec 1.4.15

1.1316.1 Available under license :

The MIT License

Copyright (c) 2015 Rich Harris

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1317 @babel/helper-function-name 7.23.0

1.1317.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1318 @babel/helper-validator-option 7.22.15

1.1318.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE

LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1319 @babel/helper-string-parser 7.22.5

1.1319.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1320 convert-source-map 2.0.0

1.1320.1 Available under license :

Copyright 2013 Thorsten Lorenz.
All rights reserved.

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

1.1321 @babel/helper-module-imports 7.22.15

1.1321.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1322 @babel/helper-hoist-variables 7.22.5

1.1322.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1323 @babel/template 7.22.15

1.1323.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE

LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1324 @babel/plugin-proposal-export-namespace-from 7.18.9

1.1324.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1325 @babel/plugin-syntax-export-namespace-from 7.8.3

1.1325.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including

without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1326 @babel/plugin-syntax-dynamic-import 7.8.3

1.1326.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1327 prop-types 15.8.1

1.1327.1 Available under license :

MIT License

Copyright (c) 2013-present, Facebook, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1328 @babel/helper-plugin-utils 7.22.5

1.1328.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF

MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1329 word 0.3.0

1.1329.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a

copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License,
each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a

cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with

the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "{}"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright (C) 2020-present SheetJS LLC

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1330 @jridgewell/trace-mapping 0.3.19

1.1330.1 Available under license :

Copyright 2022 Justin Ridgewell <justin@ridgewell.name>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1331 emojis-list 3.0.0

1.1331.1 Available under license :

The MIT License (MIT)

Copyright 2015 Kiko Beats

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the Software), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED AS IS, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1332 @types/prop-types 15.7.5

1.1332.1 Available under license :

MIT License

Copyright (c) Microsoft Corporation.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF
CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE

1.1333 @babel/runtime 7.22.15

1.1333.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1334 csstype 3.1.2

1.1334.1 Available under license :

Copyright (c) 2017-2018 Fredrik Nicol

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is

furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1335 fresh 0.5.2

1.1335.1 Available under license :

(The MIT License)

Copyright (c) 2012 TJ Holowaychuk <tj@vision-media.ca>
Copyright (c) 2016-2017 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR
OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1336 types-hoist-non-react-statics 3.3.1

1.1336.1 Available under license :

MIT License

Copyright (c) Microsoft Corporation. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER
IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE

1.1337 ua-parser-js 0.7.36

1.1337.1 Available under license :

MIT License

Copyright (c) 2012-2023 Faisal Salman <<f@faisalman.com>>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING

FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1338 @emotion/memoize 0.8.1

1.1338.1 Available under license :

MIT License

Copyright (c) Emotion team and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1339 asynckit 0.4.0

1.1339.1 Available under license :

The MIT License (MIT)

Copyright (c) 2016 Alex Indigo

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1340 supports-color 5.5.0

1.1340.1 Available under license :

MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1341 function-bind 1.1.2

1.1341.1 Available under license :

Copyright (c) 2013 Raynos.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in

all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1342 janino 2.6.1

1.1342.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Janino - An embedded Java[TM] compiler
*
* Copyright (c) 2001-2010, Arno Unkrig
* All rights reserved.
*
* Redistribution and use in source and binary forms, with or without modification, are permitted provided that the
* following conditions are met:
*
* 1. Redistributions of source code must retain the above copyright notice, this list of conditions and the
* following disclaimer.
* 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the
* following disclaimer in the documentation and/or other materials provided with the distribution.
* 3. The name of the author may not be used to endorse or promote products derived from this software without
* specific prior written permission.
*
* THIS SOFTWARE IS PROVIDED BY THE AUTHOR ``AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
* TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL
* THE AUTHOR BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
* BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
* INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
* (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
* POSSIBILITY OF SUCH DAMAGE.
*/

Found in path(s):
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/AstCompilationUnitGenerator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/IClassLoader.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/UnicodeUnescapeReader.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/iterator/ProducerIterator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/resource/DirectoryResourceFinder.java
*
/janino-2-6-1-sources-1-jar/org/codehaus/janino/util/iterator/IteratorCollection.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/samples/DeclarationCounter.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/iterator/FilterListIterator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/Opcode.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/Scanner.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/ClassLoaderIClassLoader.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/ResourceFinderIClassLoader.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/CachingJavaSourceClassLoader.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/enumerator/EnumeratorFormatException.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/UnitCompiler.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/resource/LazyMultiResourceFinder.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/iterator/ReverseListIterator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/resource/MapResourceFinder.java
*
/janino-2-6-1-sources-1-jar/org/codehaus/janino/Descriptor.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/WarningHandler.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/resource/Resource.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/resource/FileResourceFinder.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/ClassFileIClass.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/Producer.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/enumerator/Enumerator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/JavaSourceIClassLoader.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/iterator/FilterIterator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/iterator/TransformingIterator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/AntCompilerAdapter.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/ReflectionIClass.java
*
/janino-2-6-1-sources-1-jar/org/codehaus/janino/ScriptEvaluator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/Parser.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/CodeContext.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/iterator/TraversingIterator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/Traverser.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/IClass.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/Visitor.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/tools/Disassembler.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/ClassBodyEvaluator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/tools/JGrep.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/ResourceFinderClassLoader.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/iterator/DirectoryIterator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/MethodDescriptor.java

* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/resource/MultiResourceFinder.java
*
/janino-2-6-1-sources-1-jar/org/codehaus/janino/util/resource/ZipFileResourceFinder.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/resource/FileResourceCreator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/AutoIndentWriter.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/resource/ResourceCreator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/ExpressionEvaluator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/JaninoRuntimeException.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/Java.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/resource/MapResourceCreator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/Benchmark.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/resource/JarDirectoriesResourceFinder.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/UnparseVisitor.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/ClassFile.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/TeeReader.java
*
/janino-2-6-1-sources-1-jar/org/codehaus/janino/SimpleCompiler.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/JavaSourceClassLoader.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/tools/HprofScrubber.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/resource/FileResource.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/resource/PathResourceFinder.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/UnicodeUnescapeException.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/iterator/MultiDimensionalIterator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/Compiler.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/FilterWarningHandler.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/Mod.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/MultiIterator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/resource/DirectoryResourceCreator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/resource/ResourceFinder.java
*
/janino-2-6-1-sources-1-jar/org/codehaus/janino/ByteArrayClassLoader.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/iterator/EnumerationIterator.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/iterator/UniterableElementException.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/Access.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/CompilerFactory.java
* /janino-2-6-1-sources-1-jar/org/codehaus/janino/util/StringPattern.java

1.1343 punycode 2.3.1

1.1343.1 Available under license :

Copyright Mathias Bynens <https://mathiasbynens.be/>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to

permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1344 jackson-jaxrs-xml-provider 2.12.7

1.1344.1 Available under license :

This copy of Jackson JSON processor databind module is licensed under the
Apache (Software) License, version 2.0 ("the License").
See the License for details about distribution rights, and the
specific rights regarding derivate works.

You may obtain a copy of the License at:

http://www.apache.org/licenses/LICENSE-2.0
Jackson JSON processor

Jackson is a high-performance, Free/Open Source JSON processing library.
It was originally written by Tatu Saloranta (tatu.saloranta@iki.fi), and has
been in development since 2007.
It is currently developed by a community of developers, as well as supported
commercially by FasterXML.com.

Licensing

Jackson core and extension components may be licensed under different licenses.
To find the details that apply to this artifact see the accompanying LICENSE file.
For more information, including possible other licensing options, contact
FasterXML.com (http://fasterxml.com).

Credits

A list of contributors may be found from CREDITS file, which is included
in some artifacts (usually source distributions); but is always available
from the source code management (SCM) system project uses.

1.1345 amqp-client 4.12.0

1.1345.1 Available under license :

No license file was found, but licenses were detected in source scan.

/amqp-client-4-12-0-jar/com/rabbitmq/client/impl/AMQConnection.class: binary file matches
/amqp-client-4-12-0-jar/com/rabbitmq/client/impl/Copyright.class: binary file matches

Found in path(s):
* /bin/grep
No license file was found, but licenses were detected in source scan.

Manifest-Version: 1.0
Bundle-Description: The RabbitMQ Java client library allows Java appli
cations to interface with RabbitMQ.
Implementation-Title: RabbitMQ Java Client
Automatic-Module-Name: com.rabbitmq.client
Bundle-License: https://www.apache.org/licenses/LICENSE-2.0.html, http
s://www.gnu.org/licenses/gpl-2.0.txt, https://www.mozilla.org/MPL/MPL
-1.1.txt
Bundle-SymbolicName: com.rabbitmq.client
Implementation-Version: 4.12.0
Built-By: root
Bnd-LastModified: 1586865850087
Bundle-ManifestVersion: 2
Specification-Vendor: AMQP Working Group (www.amqp.org)
Specification-Title: AMQP
Bundle-DocURL: https://www.rabbitmq.com
Bundle-Vendor: VMware, Inc. or its affiliates.
Import-Package: com.codahale.metrics;version="[3.2,4)";resolution:=opt
ional,com.fasterxml.jackson.core;version="[2.10,3)";resolution:=optio
nal,com.fasterxml.jackson.databind;version="[2.10,3)";resolution:=opt
ional,com.fasterxml.jackson.databind.node;version="[2.10,3)";resoluti
 on:=optional,io.micrometer.core.instrument;resolution:=optional,javax
.naming,javax.naming.directory,javax.net,javax.net.ssl,javax.security
.auth.callback,javax.security.sasl,org.apache.http.conn.ssl;resolutio
n:=optional,org.slf4j;version="[1.7,2)"
Tool: Bnd-1.50.0
Implementation-Vendor: VMware, Inc. or its affiliates.
Export-Package: com.rabbitmq.client.impl.nio;uses:="javax.net.ssl,com.
rabbitmq.client.impl,com.rabbitmq.client,org.slf4j";version="4.12.0",
com.rabbitmq.tools.json;uses:="org.slf4j";version="4.12.0",com.rabbit
mq.client.impl;uses:="com.rabbitmq.client,com.rabbitmq.utility,org.sl
f4j,com.rabbitmq.client.impl.recovery,io.micrometer.core.instrument,j
avax.net.ssl,javax.net,com.codahale.metrics";version="4.12.0",com.rab
bitmq.tools.jsonrpc;uses:="com.rabbitmq.tools.json,org.slf4j,com.fast

erxml.jackson.core,com.fasterxml.jackson.databind,com.fasterxml.jacks
on.databind.node,com.rabbitmq.client";version="4.12.0",com.rabbitmq.c
lient;uses:="com.rabbitmq.client.impl,org.slf4j,javax.net.ssl,org.apa
che.http.conn.ssl,com.rabbitmq.client.impl.nio,javax.net,com.rabbitmq
.client.impl.recovery,com.rabbitmq.utility,javax.naming.directory,jav
ax.naming,javax.security.sasl,javax.security.auth.callback";version="
4.12.0",com.rabbitmq.client.impl.recovery;uses:="org.slf4j,com.rabbit
mq.client.impl,com.rabbitmq.client,com.rabbitmq.utility";version="4.1
2.0",com.rabbitmq.utility;version="4.12.0"
Bundle-Name: RabbitMQ Java Client
Bundle-Version: 4.12.0
Created-By: Apache Maven Bundle Plugin
Build-Jdk: 1.8.0_242
Implementation-URL: https://www.rabbitmq.com
Specification-Version: 0.9.1

Found in path(s):
* /amqp-client-4-12-0-jar/META-INF/MANIFEST.MF

1.1346 resolver 1.2.0

1.1346.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall
mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the

Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents

of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility

of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The
text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1347 spring-amqp 1.7.15.RELEASE

1.1347.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*

* Copyright 2014-2020 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/converter/MessagingMessageConverter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/AbstractBuilder.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/converter/WhiteListDeserializingMessageConverter.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/QueueBuilder.java
*
 /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/AmqpReplyTimeoutException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 the original author or authors.
*

* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/AmqpTimeoutException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-amqp-1-7-15-release-sources-
jar/org/springframework/amqp/support/postprocessor/UnzipPostProcessor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software

* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/MessagePostProcessor.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/UniquelyNamedQueue.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/converter/Jackson2JsonMessageConverter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/ExchangeBuilder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2020 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/AmqpHeaders.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
* Special exception for listener implementations that want to signal that the current
* batch of messages should be acknowledged immediately (i.e. as soon as possible) without
* rollback, and without consuming any more messages within the current transaction.
*
* @author Dave Syer
* @author Gary Russell
 *
*/
```

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/ImmediateAcknowledgeAmqpException.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2015-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
```

*/

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/converter/ContentTypeDelegatingMessageConverter.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/ConditionalExceptionLogger.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/AmqpManagementOperations.java
*
/spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/event/AmqpEvent.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/ConsumerTagStrategy.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/AmqpMessageReturnedException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/Correlation.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/CorrelationAwareMessagePostProcessor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
*/

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/ReplyToAddressCallback.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/utils/test/TestUtils.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/ReceiveAndReplyMessageCallback.java
*
 /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/AmqpAuthenticationException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/UncategorizedAmqpException.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/AmqpIllegalStateException.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/AmqpIOException.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/AmqpException.java
*
 /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/AmqpUnsupportedEncodingException.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/MessageListener.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/AmqpHeaderMapper.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/converter/MessageConverter.java
* /spring-amqp-1-7-15-release-sources-
jar/org/springframework/amqp/support/converter/SimpleMessageConverter.java
*
/spring-amqp-1-7-15-release-sources-
jar/org/springframework/amqp/support/converter/MarshallingMessageConverter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2006-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/utils/SerializationUtils.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
*/

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/MessageBuilder.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/postprocessor/AbstractCompressingPostProcessor.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/AmqpMessageHeaderAccessor.java
*
 /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/MessagePropertiesBuilder.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/ReceiveAndReplyCallback.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/postprocessor/ZipPostProcessor.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/MessageBuilderSupport.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/AddressUtils.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/postprocessor/AbstractDeflaterPostProcessor.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/postprocessor/DelegatingDecompressingPostProcessor.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/postprocessor/GUnzipPostProcessor.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/postprocessor/MessagePostProcessorUtils.java
*
 /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/postprocessor/GZipPostProcessor.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/postprocessor/AbstractDecompressingPostProcessor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/MessageProperties.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/converter/AbstractJsonMessageConverter.java

* /spring-amqp-1-7-15-release-sources-
jar/org/springframework/amqp/support/converter/Jackson2JavaTypeMapper.java
*
 /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/CustomExchange.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/DirectExchange.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/converter/ClassMapper.java
* /spring-amqp-1-7-15-release-sources-
jar/org/springframework/amqp/support/converter/AbstractMessageConverter.java
* /spring-amqp-1-7-15-release-sources-
jar/org/springframework/amqp/support/converter/DefaultJavaTypeMapper.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/AbstractExchange.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/Exchange.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/Queue.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/TopicExchange.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/converter/DefaultClassMapper.java
*
 /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/AmqpAdmin.java
* /spring-amqp-1-7-15-release-sources-
jar/org/springframework/amqp/remoting/service/AmqpInvokerServiceExporter.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/AmqpTemplate.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/SimpleAmqpHeaderMapper.java
* /spring-amqp-1-7-15-release-sources-
jar/org/springframework/amqp/support/converter/AbstractJavaTypeMapper.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/support/converter/JavaTypeMapper.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/FanoutExchange.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/AcknowledgeMode.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/HeadersExchange.java
* /spring-amqp-1-7-15-release-sources-
jar/org/springframework/amqp/support/converter/MessageConversionException.java
*
 /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/Message.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/AmqpRejectAndDontRequeueException.java
* /spring-amqp-1-7-15-release-sources-
jar/org/springframework/amqp/support/converter/JsonMessageConverter.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/MessageDeliveryMode.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/Address.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/remoting/client/AmqpProxyFactoryBean.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/remoting/client/AmqpClientInterceptor.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/BindingBuilder.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/AmqpConnectException.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/Declarable.java
*
 /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/AnonymousQueue.java
* /spring-amqp-1-7-15-release-sources-
jar/org/springframework/amqp/support/converter/DefaultJackson2JavaTypeMapper.java
* /spring-amqp-1-7-15-release-sources-
jar/org/springframework/amqp/support/converter/SerializerMessageConverter.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/Binding.java

* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/ExchangeTypes.java
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/core/AbstractDeclarable.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-amqp-1-7-15-release-sources-jar/org/springframework/amqp/AmqpResourceNotAvailableException.java

1.1348 spring-rabbit 1.7.15.RELEASE

1.1348.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/support/ConsumerCancelledException.java

* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/BindingFactoryBean.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/retry/NewMessageIdentifier.java
*
/spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/listener/exception/FatalListenerExecutionException.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/support/MessagePropertiesConverter.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/transaction/RabbitTransactionManager.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/ConnectionListener.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/AdminParser.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/FanoutExchangeParser.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/QueueArgumentsParser.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/NamespaceUtils.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/ConnectionFactoryParser.java
*
/spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/connection/CompositeConnectionListener.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/AbstractExchangeParser.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/RabbitGatewaySupport.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/retry/RejectAndDontRequeueRecoverer.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/ListenerContainerParser.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/ChannelListener.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/support/PendingConfirm.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/config/StatelessRetryOperationsInterceptorFactoryBean.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/retry/MessageKeyGenerator.java
*
/spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/ConnectionFactory.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/support/RabbitExceptionTranslator.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/support/PublisherCallbackChannelImpl.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/ActiveObjectCounter.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/config/StatefulRetryOperationsInterceptorFactoryBean.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/connection/CompositeChannelListener.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/DirectExchangeParser.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/config/AbstractRetryOperationsInterceptorFactoryBean.java
*
/spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/connection/AbstractRoutingConnectionFactory.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/retry/MessageRecoverer.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/QueueParser.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/TemplateParser.java

* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/ConsumerChannelRegistry.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/RabbitAccessor.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/Connection.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/support/DefaultMessagePropertiesConverter.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/support/PublisherCallbackChannel.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/retry/MissingMessageIdAdvice.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/exception/FatalListenerStartupException.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/adapter/MessageListenerAdapter.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/RabbitListenerEndpoint.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/ChannelProxy.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2011-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/log4j/AmqpAppender.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/ConsumeOkEvent.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014-2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/listener/AbstractRabbitListenerEndpoint.java

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2013 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/TopicExchangeParser.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/support/ClosingRecoveryListener.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2014-2020 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
```

```
*
*      https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/logback/AmqpAppender.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2014-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/listener/ConditionalRejectingErrorHandler.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2002-2018 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
```

* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/BlockingQueueConsumer.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/SimpleConnection.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/connection/CachingConnectionFactory.java
*
/spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/connection/ConnectionFactoryUtils.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/RabbitAdmin.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/connection/AbstractConnectionFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/listener/RabbitListenerEndpointRegistry.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/support/ValueExpression.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/annotation/RabbitListenerAnnotationBeanPostProcessor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/CorrelationDataPostProcessor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/log4j2/AmqpAppender.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/AutoRecoverConnectionNotCurrentlyOpenException.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/AsyncRabbitTemplate.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/annotation/RabbitHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2010 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/ConnectionProxy.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/support/ExpressionFactoryBean.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/RabbitOperations.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2010-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-

jar/org/springframework/amqp/rabbit/listener/MessageRejectedWhileStoppingException.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2014-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*      https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/MethodRabbitListenerEndpoint.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/annotation/RabbitListener.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/SimpleRoutingConnectionFactory.java
*
/spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/SimpleRabbitListenerContainerFactory.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/RabbitListenerEndpointRegistrar.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/RetryInterceptorBuilder.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/support/BatchingStrategy.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/retry/RepublishMessageRecoverer.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/FatalExceptionStrategy.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/QueuesNotAvailableException.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/support/SimpleBatchingStrategy.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/adapter/AbstractAdaptableMessageListener.java
*
/spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/BatchingRabbitTemplate.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/support/MessageBatch.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/SimpleResourceHolder.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/AbstractRabbitListenerContainerFactory.java

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/ListenerContainerIdleEvent.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/DeclareExchangeConnectionListener.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/AsyncConsumerRestartedEvent.java
*
 /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/DeclarationExceptionEvent.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/annotation/RabbitListeners.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/annotation/Argument.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/AsyncConsumerStartedEvent.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/AsyncConsumerStoppedEvent.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/support/Delivery.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/transaction/ListenerFailedRuleBasedTransactionAttribute.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/support/LogAppenderUtils.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/RabbitAdminEvent.java
*
 /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/ConnectionNameStrategy.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2014 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.

* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/RabbitNamespaceHandler.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/AnnotationDrivenParser.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/ChannelCallback.java
*
 /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/RabbitListenerConfigUtils.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/RabbitMessageOperations.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/listener/RabbitListenerContainerFactory.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/HeadersExchangeParser.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/annotation/RabbitListenerConfigurer.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/core/ChannelAwareMessageListener.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/annotation/RabbitBootstrapConfiguration.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/RabbitManagementTemplate.java

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2017 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/RabbitNamespaceUtils.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/RabbitUtils.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/listener/exception/ListenerExecutionFailedException.java
*
 /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/RabbitResourceHolder.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/listener/adapter/MessagingMessageListenerAdapter.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/support/CorrelationData.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/RabbitMessagingTemplate.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/listener/AbstractMessageListenerContainer.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/core/RabbitTemplate.java
* /spring-rabbit-1-7-15-release-sources-
jar/org/springframework/amqp/rabbit/connection/RabbitConnectionFactoryBean.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015-2016 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/RoutingConnectionFactory.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/support/ListenerContainerAware.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/annotation/Queue.java
*
 /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/LocalizedQueueConnectionFactory.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/MultiMethodRabbitListenerEndpoint.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/adapter/HandlerAdapter.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/ListenerContainerConsumerFailedEvent.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/annotation/Exchange.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/adapter/DelegatingInvocableHandler.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/connection/PublisherCallbackChannelConnectionFactory.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/annotation/QueueBinding.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2002-2019 the original author or authors.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/SimpleMessageListenerContainer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 the original author or authors.

*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   https://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/annotation/EnableRabbit.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/config/SimpleRabbitListenerEndpoint.java
* /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/MessageListenerContainer.java
*
 /spring-rabbit-1-7-15-release-sources-jar/org/springframework/amqp/rabbit/listener/adapter/ReplyFailureException.java

1.1349 transaction 1.1.0

1.1349.1 Available under license :

Zope Public License (ZPL) Version 2.1

A copyright notice accompanies this license document that identifies the
copyright holders.

This license has been certified as open source. It has also been designated as
GPL compatible by the Free Software Foundation (FSF).

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

1. Redistributions in source code must retain the accompanying copyright
notice, this list of conditions, and the following disclaimer.

2. Redistributions in binary form must reproduce the accompanying copyright
notice, this list of conditions, and the following disclaimer in the
documentation and/or other materials provided with the distribution.

3. Names of the copyright holders must not be used to endorse or promote
products derived from this software without prior written permission from the

copyright holders.

4. The right to distribute this software or to use it for any purpose
does not
give you the right to use Servicemarks (sm) or Trademarks (tm) of the
copyright
holders. Use of them is covered by separate agreement with the copyright
holders.

5. If any files are modified, you must cause the modified files to carry
prominent notices stating that you changed the files and the date of any
change.

Disclaimer

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS ``AS IS'' AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDERS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE,
EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Zope Foundation and Contributors

1.1350 node-sass 4.14.1

1.1350.1 Available under license :

Copyright (c) 2013-2016 Andrew Nesbitt

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND

NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Copyright (C) 2012-2016 by the Sass Open Source Foundation

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

The following files in the spec were taken from the original Ruby Sass project which is copyright Hampton Catlin, Nathan Weizenbaum, and Chris Eppstein and under the same license.

Copyright (C) 2012 by Hampton Catlin

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

The following files in the spec were taken from the original Ruby Sass project which is copyright Hampton Catlin, Nathan Weizenbaum, and Chris Eppstein and under the same license.

1.1351 copy-props 2.0.5

1.1351.1 Available under license :

MIT License

Copyright (c) 2016-2021 Gulp Team.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1352 json-schema 0.2.5

1.1352.1 Available under license :

UNRECOGNIZED LICENSE; MD5 sum: 757f158e6c73795dfa18b397289466ae
Dojo is available under *either* the terms of the BSD 3-Clause "New" License *or* the Academic Free License version 2.1. As a recipient of Dojo, you may choose which license to receive this code under (except as noted in per-module LICENSE files). Some modules may not be the copyright of the Dojo Foundation. These modules contain explicit declarations of copyright in both the LICENSE files in the directories in which they reside and in the code itself. No external

contributions are allowed under licenses which are fundamentally incompatible with the AFL-2.1 OR and BSD-3-Clause licenses that Dojo is distributed under.

The text of the AFL-2.1 and BSD-3-Clause licenses is reproduced below.

BSD 3-Clause "New" License:
****

Copyright (c) 2005-2015, The Dojo Foundation
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided
that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of the Dojo Foundation nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED
TO, PROCUREMENT OF SUBSTITUTE GOODS OR
SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

The Academic Free License, v. 2.1:
****

This Academic Free License (the "License") applies to any original work of authorship (the "Original Work") whose owner (the "Licensor") has placed the following notice immediately following the copyright notice for the Original Work:

Licensed under the Academic Free License version 2.1

1) Grant of Copyright License. Licensor hereby grants You a world-wide, royalty-free, non-exclusive, perpetual, sublicenseable license to do the following:

a) to reproduce the Original Work in copies;

b) to prepare derivative works ("Derivative Works") based upon the Original Work;

c) to distribute copies of the Original Work and Derivative Works to the public;

d) to perform the Original Work publicly; and

e) to display the Original Work publicly.

2) Grant of Patent License. Licensor hereby grants You a world-wide, royalty-free, non-exclusive, perpetual, sublicenseable license, under patent claims owned or controlled by the Licensor that are embodied in the Original Work as furnished by the Licensor, to make, use, sell and offer for sale the Original Work and Derivative Works.

3) Grant of Source Code License. The term "Source Code" means the preferred form of the Original Work for making modifications to it and all available documentation describing how to modify the Original Work. Licensor hereby agrees to provide a machine-readable copy of the Source Code of the Original Work along with each copy of the Original Work that Licensor distributes. Licensor reserves the right to satisfy this obligation by placing a machine-readable copy of the Source Code in an information repository reasonably calculated to permit inexpensive and convenient access by You for as long as Licensor continues to distribute the Original Work, and by publishing the address of that information repository in a notice immediately following the copyright notice that applies to the Original Work.

4) Exclusions From License Grant. Neither the names of Licensor, nor the names of any contributors to the Original Work, nor any of their trademarks or service marks, may be used to endorse or promote products derived from this Original Work without express prior written permission of the Licensor. Nothing in this License shall be deemed to grant any rights to trademarks, copyrights, patents, trade secrets or any other intellectual property of Licensor except as expressly stated herein. No patent license is granted to make, use, sell or offer to sell embodiments of any patent claims other than the licensed claims defined in Section 2. No right is granted to the trademarks of Licensor even if such marks are included in the Original Work. Nothing in this License shall be interpreted to prohibit Licensor from licensing under different terms from this

License any Original Work that Licensor otherwise would have a right to license.

5) This section intentionally omitted.

6) Attribution Rights. You must retain, in the Source Code of any Derivative Works that You create, all copyright, patent or trademark notices from the Source Code of the Original Work, as well as any notices of licensing and any descriptive text identified therein as an "Attribution Notice." You must cause the Source Code for any Derivative Works that You create to carry a prominent Attribution Notice reasonably calculated to inform recipients that You have modified the Original Work.

7) Warranty of Provenance and Disclaimer of Warranty. Licensor warrants that the copyright in and to the Original Work and the patent rights granted herein by Licensor are owned by the Licensor or are sublicensed to You under the terms of this License with the permission of the contributor(s) of those copyrights and patent rights. Except as expressly stated in the immediately proceeding sentence, the Original Work is provided under this License on an "AS IS" BASIS and WITHOUT WARRANTY, either express or implied, including, without limitation, the warranties of NON-INFRINGEMENT, MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY OF THE ORIGINAL WORK IS WITH YOU. This DISCLAIMER OF WARRANTY constitutes an essential part of this License. No license to Original Work is granted hereunder except under this disclaimer.

8) Limitation of Liability. Under no circumstances and under no legal theory, whether in tort (including negligence), contract, or otherwise, shall the Licensor be liable to any person for any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or the use of the Original Work including, without limitation, damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses. This limitation of liability shall not apply to liability for death or personal injury resulting from Licensor's negligence to the extent applicable law prohibits such limitation. Some jurisdictions do not allow the exclusion or limitation of incidental or consequential damages, so this exclusion and limitation may not apply to You.

9) Acceptance and Termination. If You distribute copies of the Original Work or a Derivative Work, You must make a reasonable effort under the circumstances to obtain the express assent of recipients to the terms of this License. Nothing else but this License (or another written agreement between Licensor and You) grants You permission to create Derivative Works based upon the Original Work or to exercise any of the rights granted in Section 1 herein, and any attempt to do so except under the terms of this License (or another written agreement between Licensor and You) is expressly prohibited by U.S. copyright law, the

equivalent laws of other countries, and by international treaty. Therefore, by exercising any of the rights granted to You in Section 1 herein, You indicate Your acceptance of this License and all of its terms and conditions.

10) Termination for Patent Action. This License shall terminate automatically and You may no longer exercise any of the rights granted to You by this License as of the date You commence an action, including a cross-claim or counterclaim, against Licensor or any licensee alleging that the Original Work infringes a patent. This termination provision shall not apply for an action alleging patent infringement by combinations of the Original Work with other software or hardware.

11) Jurisdiction, Venue and Governing Law. Any action or suit relating to this License may be brought only
in the courts of a jurisdiction wherein the
Licensor resides or in which Licensor conducts its primary business, and under the laws of that jurisdiction excluding its conflict-of-law provisions. The application of the United Nations Convention on Contracts for the International Sale of Goods is expressly excluded. Any use of the Original Work outside the scope of this License or after its termination shall be subject to the requirements and penalties of the U.S. Copyright Act, 17 U.S.C. 101 et seq., the equivalent laws of other countries, and international treaty. This section shall survive the termination of this License.

12) Attorneys Fees. In any action to enforce the terms of this License or seeking damages relating thereto, the prevailing party shall be entitled to recover its costs and expenses, including, without limitation, reasonable attorneys' fees and costs incurred in connection with such action, including any appeal of such action. This section shall survive the termination
of this
License.

13) Miscellaneous. This License represents the complete agreement concerning the subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable.

14) Definition of "You" in This License. "You" throughout this License, whether in upper or lower case, means an individual or a legal entity exercising rights under, and complying with all of the terms of, this License. For legal entities, "You" includes any entity that controls, is controlled by, or is under common control with you. For purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

15) Right to Use. You may use the Original Work in all ways not otherwise

restricted or conditioned
by this License or by law, and Licensor promises not
to interfere with or be responsible for such uses by You.

This license is Copyright (C) 2003-2004 Lawrence E. Rosen. All rights reserved.
Permission is hereby granted to copy and distribute this license without
modification. This license may not be modified without the express written
permission of its copyright owner.

1.1353 yargs-parser 5.0.1

1.1353.1 Available under license :

Copyright (c) 2016, Contributors

Permission to use, copy, modify, and/or distribute this software
for any purpose with or without fee is hereby granted, provided
that the above copyright notice and this permission notice
appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES
OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS,
WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION,
ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.1354 async 3.2.5

1.1354.1 Available under license :

Copyright (c) 2010-2018 Caolan McMahon

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1355 @babel/plugin-syntax-jsx 7.23.3

1.1355.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1356 @babel/helper-module-transforms 7.23.3

1.1356.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to

permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1357 babel-plugin-syntax-typescript 7.23.3

1.1357.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1358 babel-preset-typescript 7.23.3

1.1358.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1359 @babel/plugin-transform-react-display-name 7.23.3

1.1359.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1360 @babel/plugin-transform-modules-commonjs 7.23.3

1.1360.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1361 @babel/helper-string-parser 7.23.4

1.1361.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the

"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1362 @babel/highlight 7.23.4

1.1362.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1363 component-emitter 1.3.1

1.1363.1 Available under license :

(The MIT License)

Copyright (c) 2014 Component contributors <dev@component.io>

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.

1.1364 react-window 1.8.10

1.1364.1 Available under license :

The MIT License (MIT)

Copyright (c) 2018 Brian Vaughn

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1365 @babel/plugin-transform-private-property-in-object 7.23.4

1.1365.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1366 @babel/plugin-transform-class-properties 7.23.3

1.1366.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1367 @babel/plugin-syntax-import-assertions 7.23.3

1.1367.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1368 @babel/plugin-bugfix-safari-id-destructuring-collision-in-function-expression 7.23.3

1.1368.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1369 @babel/plugin-transform-optional-catch-binding 7.23.4

1.1369.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1370 @babel/plugin-transform-destructuring 7.23.3

1.1370.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1371 @babel/plugin-transform-sticky-regex 7.23.3

1.1371.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1372 @babel/plugin-transform-unicode-property-regex 7.23.3

1.1372.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1373 @babel/plugin-transform-logical-assignment-operators 7.23.4

1.1373.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,

ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1374 @babel/plugin-bugfix-v8-spread-parameters-in-optional-chaining 7.23.3

1.1374.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1375 @babel/plugin-transform-react-jsx 7.23.4

1.1375.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to

permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1376 @babel/plugin-transform-exponentiation-operator 7.23.3

1.1376.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1377 @babel/plugin-transform-modules-umd 7.23.3

1.1377.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1378 @babel/plugin-transform-export-namespace-from 7.23.4

1.1378.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1379 babel-plugin-transform-member-expression-literals 7.23.3

1.1379.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1380 @babel/plugin-transform-class-static-block 7.23.4

1.1380.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1381 @babel/plugin-transform-optional-chaining 7.23.4

1.1381.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1382 @babel/plugin-transform-nullish-coalescing-operator 7.23.4

1.1382.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1383 @babel/plugin-transform-shorthand-properties 7.23.3

1.1383.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1384 babel-plugin-transform-property-literals 7.23.3

1.1384.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,

ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1385 @babel/plugin-transform-block-scoped-functions 7.23.3

1.1385.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1386 @babel/plugin-transform-template-literals 7.23.3

1.1386.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to

permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1387 @babel/plugin-transform-parameters 7.23.3

1.1387.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1388 @babel/plugin-transform-new-target 7.23.3

1.1388.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1389 @babel/plugin-transform-unicode-sets-regex 7.23.3

1.1389.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1390 @babel/plugin-syntax-import-attributes 7.23.3

1.1390.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1391 @babel/plugin-transform-unicode-escapes 7.23.3

1.1391.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1392 @babel/plugin-transform-arrow-functions 7.23.3

1.1392.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1393 @babel/plugin-transform-async-to-generator 7.23.3

1.1393.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1394 @babel/plugin-transform-unicode-regex 7.23.3

1.1394.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1395 @babel/plugin-transform-modules-amd 7.23.3

1.1395.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,

ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1396 @babel/plugin-transform-computed-properties 7.23.3

1.1396.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1397 @babel/plugin-transform-spread 7.23.3

1.1397.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to

permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1398 @babel/plugin-transform-literals 7.23.3

1.1398.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1399 @babel/plugin-transform-typeof-symbol 7.23.3

1.1399.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1400 @babel/plugin-transform-dynamic-import 7.23.4

1.1400.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1401 @babel/plugin-transform-object-super 7.23.3

1.1401.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1402 @babel/plugin-transform-duplicate-keys 7.23.3

1.1402.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1403 @babel/plugin-transform-dotall-regex 7.23.3

1.1403.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1404 babel-plugin-transform-reserved-words 7.23.3

1.1404.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1405 @babel/plugin-transform-numeric-separator 7.23.4

1.1405.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1406 @babel/plugin-transform-function-name 7.23.3

1.1406.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,

ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1407 @babel/plugin-transform-private-methods 7.23.3

1.1407.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1408 @babel/plugin-transform-block-scoping 7.23.4

1.1408.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to

permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1409 @babel/plugin-transform-regenerator 7.23.3

1.1409.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1410 @babel/plugin-transform-json-strings 7.23.4

1.1410.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1411 validation 1.0.0.GA

1.1411.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise

designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any

risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1412 @babel/helper-validator-option 7.23.5

1.1412.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1413 @babel/compat-data 7.23.5

1.1413.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to

the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1414 @babel/code-frame 7.23.5

1.1414.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1415 @babel/preset-react 7.23.3

1.1415.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1416 @babel/plugin-transform-react-pure-annotations 7.23.3

1.1416.1 Available under license :

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1417 object.assign 4.1.5

1.1417.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1418 netty-transport-native-epoll:linux-x86_64 linux-x86_64:4.1.49.Final

1.1418.1 Available under license :

No license file was found, but licenses were detected in source scan.

<!--
~ Copyright 2014 The Netty Project
~
~ The Netty Project licenses this file to you under the Apache License,

~ version 2.0 (the "License"); you may not use this file except in compliance
~ with the License. You may obtain a copy of the License at:
~
~   http://www.apache.org/licenses/LICENSE-2.0
~
~ Unless required by applicable law or agreed to in writing, software
~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
~ License for the specific language governing permissions and limitations
~ under the License.
-->

Found in path(s):
* /netty-transport-native-epoll-4-1-49-final-jar/META-INF/maven/io.netty/netty-transport-native-epoll/pom.xml
No license file was found, but licenses were detected in source scan.

Manifest-Version: 1.0
Implementation-Title: Netty/Transport/Native/Epoll
Bundle-Description: Netty is an asynchronous event-driven network appl
ication framework for rapid development of maintainable high perfo
rmance protocol servers and clients.
Automatic-Module-Name: io.netty.transport.epoll
Bundle-License: http://www.apache.org/licenses/LICENSE-2.0
Bundle-SymbolicName: io.netty.transport-native-epoll
Implementation-Version: 4.1.49.Final
Built-By: root
Bnd-LastModified: 1587554607763
Bundle-ManifestVersion: 2
Implementation-Vendor-Id: io.netty
Bundle-DocURL: https://netty.io/
Bundle-Vendor: The Netty Project
Import-Package: io.netty.buffer;version="[4.1,5)",io.netty.channel,io.
netty.channel.socket;version="[4.1,5)",io.netty.channel.unix;version=
"[4.1,5)",io.netty.util;version="[4.1,5)",io.netty.util.collection;ve
rsion="[4.1,5)",io.netty.util.concurrent;version="[4.1,5)",io.netty.u
til.internal;version="[4.1,5)",io.netty.util.internal.logging;version
 ="[4.1,5)",sun.nio.ch;resolution:=optional,org.eclipse.jetty.npn;vers
ion="[1,2)";resolution:=optional,org.eclipse.jetty.alpn;version="[1,2
)";resolution:=optional
Require-Capability: osgi.ee;filter:="(&(osgi.ee=JavaSE)(version=1.6))"
Tool: Bnd-2.4.1.201501161923
Implementation-Vendor: The Netty Project
Export-Package: io.netty.channel.epoll;uses:="io.netty.buffer,io.netty
.channel,io.netty.channel.socket,io.netty.channel.unix,io.netty.util.
concurrent";version="4.1.49"
Bundle-Name: Netty/Transport/Native/Epoll
Bundle-Version: 4.1.49.Final
Created-By: Apache Maven Bundle Plugin

Build-Jdk: 1.8.0_212
Implementation-URL: https://netty.io/netty-transport-native-epoll/

Found in path(s):
* /netty-transport-native-epoll-4-1-49-final-jar/META-INF/MANIFEST.MF

1.1419 ua-parser-js 0.7.37

1.1419.1 Available under license :

MIT License

Copyright (c) 2012-2023 Faisal Salman <<f@faisalman.com>>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1420 figlet 1.7.0

1.1420.1 Available under license :

The MIT License (MIT)

Copyright (C) 2014-present Patrick Gillespie and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1421 babel-helper-compilation-targets 7.23.6

1.1421.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1422 @babel/generator 7.23.6

1.1422.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1423 @babel/plugin-transform-for-of 7.23.6

1.1423.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1424 babel-plugin-transform-typescript 7.23.6

1.1424.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1425 whatwg-fetch 3.6.20

1.1425.1 Available under license :

Copyright (c) 2014-2023 GitHub, Inc.

Permission is hereby granted, free of charge, to any person obtaining

a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1426 regenerator-runtime 0.14.1

1.1426.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present, Facebook, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1427 moment 2.30.1

1.1427.1 Available under license :

Copyright (c) JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1428 @babel/plugin-transform-classes 7.23.8

1.1428.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1429 @babel/plugin-bugfix-v8-static-class-fields-redefine-readonly 7.23.7

1.1429.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1430 @babel/plugin-transform-modules-systemjs 7.23.9

1.1430.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1431 @babel/plugin-transform-async-generator-functions 7.23.9

1.1431.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to

the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1432 immutable 4.3.5

1.1432.1 Available under license :

MIT License

Copyright (c) 2014-present, Lee Byron and other contributors.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1433 stream-shift 1.0.3

1.1433.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2016 Mathias Buus

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1434 has-tostringtag 1.0.2

1.1434.1 Available under license :

MIT License

Copyright (c) 2021 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1435 is-array-buffer 3.0.4

1.1435.1 Available under license :

MIT License

Copyright (c) 2015 Chen Gengyuan, Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1436 is-typed-array 1.1.13

1.1436.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1437 arraybuffer.prototype.slice 1.0.3

1.1437.1 Available under license :

MIT
MIT License

Copyright (c) 2023 ECMAScript Shims

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1438 array-buffer-byte-length 1.0.1

1.1438.1 Available under license :

MIT License

Copyright (c) 2023 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1439 escalade 3.1.2

1.1439.1 Available under license :

MIT License

Copyright (c) Luke Edwards <luke.edwards05@gmail.com> (lukeed.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1440 internal-slot 1.0.7

1.1440.1 Available under license :

MIT License

Copyright (c) 2019 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1441 safe-regex-test 1.0.3

1.1441.1 Available under license :

MIT License

Copyright (c) 2022 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1442 webpack-hot-middleware 2.26.1

1.1442.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1443 get-symbol-description 1.0.2

1.1443.1 Available under license :

MIT License

Copyright (c) 2021 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is

furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1444 babel-plugin-polyfill-regenerator 0.5.5

1.1444.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Nicol Ribaudo and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1445 babel-plugin-polyfill-corejs3 0.9.0

1.1445.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Nicol Ribaudo and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1446 babel-plugin-polyfill-corejs2 0.4.5

1.1446.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Nicol Ribaudo and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF

MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1447 babel-plugin-polyfill-corejs3 0.8.3

1.1447.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Nicol Ribaudo and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1448 babel-plugin-polyfill-regenerator 0.5.2

1.1448.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Nicol Ribaudo and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including

without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1449 browserify-sign 4.2.1

1.1449.1 Available under license :

ISC
Copyright (c) 2014-2015 Calvin Metcalf and browserify-sign contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.1450 regexp-prototype-flags 1.5.2

1.1450.1 Available under license :

The MIT License (MIT)

Copyright (C) 2014 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell

copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.1451 spdx-license-ids 3.0.17

1.1451.1 Available under license :

[
"0BSD",
"AAL",
"ADSL",
"AFL-1.1",
"AFL-1.2",
"AFL-2.0",
"AFL-2.1",
"AFL-3.0",
"AGPL-1.0-only",
"AGPL-1.0-or-later",
"AGPL-3.0-only",
"AGPL-3.0-or-later",
"AMDPLPA",
"AML",
"AML-glslang",
"AMPAS",
"ANTLR-PD",
"ANTLR-PD-fallback",
"APAFML",
"APL-1.0",
"APSL-1.0",
"APSL-1.1",
"APSL-1.2",
"APSL-2.0",
"ASWF-Digital-Assets-1.0",
"ASWF-Digital-Assets-1.1",
"Abstyles",

"AdaCore-doc",
"Adobe-2006",
"Adobe-Display-PostScript",
"Adobe-Glyph",
"Adobe-Utopia",
"Afmparse",
"Aladdin",
"Apache-1.0",
"Apache-1.1",
"Apache-2.0",
"App-s2p",
"Arphic-1999",
"Artistic-1.0",
"Artistic-1.0-Perl",
"Artistic-1.0-cl8",
"Artistic-2.0",
"BSD-1-Clause",
"BSD-2-Clause",
"BSD-2-Clause-Darwin",
"BSD-2-Clause-Patent",
"BSD-2-Clause-Views",
"BSD-3-Clause",
"BSD-3-Clause-Attribution",
"BSD-3-Clause-Clear",
"BSD-3-Clause-HP",
"BSD-3-Clause-LBNL",
"BSD-3-Clause-Modification",
"BSD-3-Clause-No-Military-License",
"BSD-3-Clause-No-Nuclear-License",
"BSD-3-Clause-No-Nuclear-License-2014",
"BSD-3-Clause-No-Nuclear-Warranty",
"BSD-3-Clause-Open-MPI",
"BSD-3-Clause-Sun",
"BSD-3-Clause-acpica",
"BSD-3-Clause-flex",
"BSD-4-Clause",
"BSD-4-Clause-Shortened",
"BSD-4-Clause-UC",
"BSD-4.3RENO",
"BSD-4.3TAHOE",
"BSD-Advertising-Acknowledgement",
"BSD-Attribution-HPND-disclaimer",
"BSD-Inferno-Nettverk",
"BSD-Protection",
"BSD-Source-Code",
"BSD-Source-beginning-file",
"BSD-Systemics",
"BSD-Systemics-W3Works",

"BSL-1.0",
"BUSL-1.1",
"Baekmuk",
"Bahyph",
"Barr",
"Beerware",
"BitTorrent-1.0",
"BitTorrent-1.1",
"Bitstream-Charter",
"Bitstream-Vera",
"BlueOak-1.0.0",
"Boehm-GC",
"Borceux",
"Brian-Gladman-2-Clause",
"Brian-Gladman-3-Clause",
"C-UDA-1.0",
"CAL-1.0",
"CAL-1.0-Combined-Work-Exception",
"CATOSL-1.1",
"CC-BY-1.0",
"CC-BY-2.0",
"CC-BY-2.5",
"CC-BY-2.5-AU",
"CC-BY-3.0",
"CC-BY-3.0-AT",
"CC-BY-3.0-AU",
"CC-BY-3.0-DE",
"CC-BY-3.0-IGO",
"CC-BY-3.0-NL",
"CC-BY-3.0-US",
"CC-BY-4.0",
"CC-BY-NC-1.0",
"CC-BY-NC-2.0",
"CC-BY-NC-2.5",
"CC-BY-NC-3.0",
"CC-BY-NC-3.0-DE",
"CC-BY-NC-4.0",
"CC-BY-NC-ND-1.0",
"CC-BY-NC-ND-2.0",
"CC-BY-NC-ND-2.5",
"CC-BY-NC-ND-3.0",
"CC-BY-NC-ND-3.0-DE",
"CC-BY-NC-ND-3.0-IGO",
"CC-BY-NC-ND-4.0",
"CC-BY-NC-SA-1.0",
"CC-BY-NC-SA-2.0",
"CC-BY-NC-SA-2.0-DE",
"CC-BY-NC-SA-2.0-FR",

"CC-BY-NC-SA-2.0-UK",
"CC-BY-NC-SA-2.5",
"CC-BY-NC-SA-3.0",
"CC-BY-NC-SA-3.0-DE",
"CC-BY-NC-SA-3.0-IGO",
"CC-BY-NC-SA-4.0",
"CC-BY-ND-1.0",
"CC-BY-ND-2.0",
"CC-BY-ND-2.5",
"CC-BY-ND-3.0",
"CC-BY-ND-3.0-DE",
"CC-BY-ND-4.0",
"CC-BY-SA-1.0",
"CC-BY-SA-2.0",
"CC-BY-SA-2.0-UK",
"CC-BY-SA-2.1-JP",
"CC-BY-SA-2.5",
"CC-BY-SA-3.0",
"CC-BY-SA-3.0-AT",
"CC-BY-SA-3.0-DE",
"CC-BY-SA-3.0-IGO",
"CC-BY-SA-4.0",
"CC-PDDC",
"CC0-1.0",
"CDDL-1.0",
"CDDL-1.1",
"CDL-1.0",
"CDLA-Permissive-1.0",
"CDLA-Permissive-2.0",
"CDLA-Sharing-1.0",
"CECILL-1.0",
"CECILL-1.1",
"CECILL-2.0",
"CECILL-2.1",
"CECILL-B",
"CECILL-C",
"CERN-OHL-1.1",
"CERN-OHL-1.2",
"CERN-OHL-P-2.0",
"CERN-OHL-S-2.0",
"CERN-OHL-W-2.0",
"CFITSIO",
"CMU-Mach",
"CMU-Mach-nodoc",
"CNRI-Jython",
"CNRI-Python",
"CNRI-Python-GPL-Compatible",
"COIL-1.0",

"CPAL-1.0",
"CPL-1.0",
"CPOL-1.02",
"CUA-OPL-1.0",
"Caldera",
"Caldera-no-preamble",
"ClArtistic",
"Clips",
"Community-Spec-1.0",
"Condor-1.1",
"Cornell-Lossless-JPEG",
"Cronyx",
"Crossword",
"CrystalStacker",
"Cube",
"D-FSL-1.0",
"DEC-3-Clause",
"DL-DE-BY-2.0",
"DL-DE-ZERO-2.0",
"DOC",
"DRL-1.0",
"DRL-1.1",
"DSDP",
"Dotseqn",
"ECL-1.0",
"ECL-2.0",
"EFL-1.0",
"EFL-2.0",
"EPICS",
"EPL-1.0",
"EPL-2.0",
"EUDatagrid",
"EUPL-1.0",
"EUPL-1.1",
"EUPL-1.2",
"Elastic-2.0",
"Entessa",
"ErlPL-1.1",
"Eurosym",
"FBM",
"FDK-AAC",
"FSFAP",
"FSFAP-no-warranty-disclaimer",
"FSFUL",
"FSFULLR",
"FSFULLRWD",
"FTL",
"Fair",

"Ferguson-Twofish",
"Frameworx-1.0",
"FreeBSD-DOC",
"FreeImage",
"Furuseth",
"GCR-docs",
"GD",
"GFDL-1.1-invariants-only",
"GFDL-1.1-invariants-or-later",
"GFDL-1.1-no-invariants-only",
"GFDL-1.1-no-invariants-or-later",
"GFDL-1.1-only",
"GFDL-1.1-or-later",
"GFDL-1.2-invariants-only",
"GFDL-1.2-invariants-or-later",
"GFDL-1.2-no-invariants-only",
"GFDL-1.2-no-invariants-or-later",
"GFDL-1.2-only",
"GFDL-1.2-or-later",
"GFDL-1.3-invariants-only",
"GFDL-1.3-invariants-or-later",
"GFDL-1.3-no-invariants-only",
"GFDL-1.3-no-invariants-or-later",
"GFDL-1.3-only",
"GFDL-1.3-or-later",
"GL2PS",
"GLWTPL",
"GPL-1.0-only",
"GPL-1.0-or-later",
"GPL-2.0-only",
"GPL-2.0-or-later",
"GPL-3.0-only",
"GPL-3.0-or-later",
"Giftware",
"Glide",
"Glulxe",
"Graphics-Gems",
"HP-1986",
"HP-1989",
"HPND",
"HPND-DEC",
"HPND-Fenneberg-Livingston",
"HPND-INRIA-IMAG",
"HPND-Kevlin-Henney",
"HPND-MIT-disclaimer",
"HPND-Markus-Kuhn",
"HPND-Pbmplus",
"HPND-UC",

"HPND-doc",
"HPND-doc-sell",
"HPND-export-US",
"HPND-export-US-modify",
"HPND-sell-MIT-disclaimer-xserver",
"HPND-sell-regexpr",
"HPND-sell-variant",
"HPND-sell-variant-MIT-disclaimer",
"HTMLTIDY",
"HaskellReport",
"Hippocratic-2.1",
"IBM-pibs",
"ICU",
"IEC-Code-Components-EULA",
"IJG",
"IJG-short",
"IPA",
"IPL-1.0",
"ISC",
"ISC-Veillard",
"ImageMagick",
"Imlib2",
"Info-ZIP",
"Inner-Net-2.0",
"Intel",
"Intel-ACPI",
"Interbase-1.0",
"JPL-image",
"JPNIC",
"JSON",
"Jam",
"JasPer-2.0",
"Kastrup",
"Kazlib",
"Knuth-CTAN",
"LAL-1.2",
"LAL-1.3",
"LGPL-2.0-only",
"LGPL-2.0-or-later",
"LGPL-2.1-only",
"LGPL-2.1-or-later",
"LGPL-3.0-only",
"LGPL-3.0-or-later",
"LGPLLR",
"LOOP",
"LPD-document",
"LPL-1.0",
"LPL-1.02",

"LPPL-1.0",
"LPPL-1.1",
"LPPL-1.2",
"LPPL-1.3a",
"LPPL-1.3c",
"LZMA-SDK-9.11-to-9.20",
"LZMA-SDK-9.22",
"Latex2e",
"Latex2e-translated-notice",
"Leptonica",
"LiLiQ-P-1.1",
"LiLiQ-R-1.1",
"LiLiQ-Rplus-1.1",
"Libpng",
"Linux-OpenIB",
"Linux-man-pages-1-para",
"Linux-man-pages-copyleft",
"Linux-man-pages-copyleft-2-para",
"Linux-man-pages-copyleft-var",
"Lucida-Bitmap-Fonts",
"MIT",
"MIT-0",
"MIT-CMU",
"MIT-Festival",
"MIT-Modern-Variant",
"MIT-Wu",
"MIT-advertising",
"MIT-enna",
"MIT-feh",
"MIT-open-group",
"MIT-testregex",
"MITNFA",
"MMIXware",
"MPEG-SSG",
"MPL-1.0",
"MPL-1.1",
"MPL-2.0",
"MPL-2.0-no-copyleft-exception",
"MS-LPL",
"MS-PL",
"MS-RL",
"MTLL",
"Mackerras-3-Clause",
"Mackerras-3-Clause-acknowledgment",
"MakeIndex",
"Martin-Birgmeier",
"McPhee-slideshow",
"Minpack",

"MirOS",
"Motosoto",
"MulanPSL-1.0",
"MulanPSL-2.0",
"Multics",
"Mup",
"NAIST-2003",
"NASA-1.3",
"NBPL-1.0",
"NCGL-UK-2.0",
"NCSA",
"NGPL",
"NICTA-1.0",
"NIST-PD",
"NIST-PD-fallback",
"NIST-Software",
"NLOD-1.0",
"NLOD-2.0",
"NLPL",
"NOSL",
"NPL-1.0",
"NPL-1.1",
"NPOSL-3.0",
"NRL",
"NTP",
"NTP-0",
"Naumen",
"Net-SNMP",
"NetCDF",
"Newsletr",
"Nokia",
"Noweb",
"O-UDA-1.0",
"OCCT-PL",
"OCLC-2.0",
"ODC-By-1.0",
"ODbL-1.0",
"OFFIS",
"OFL-1.0",
"OFL-1.0-RFN",
"OFL-1.0-no-RFN",
"OFL-1.1",
"OFL-1.1-RFN",
"OFL-1.1-no-RFN",
"OGC-1.0",
"OGDL-Taiwan-1.0",
"OGL-Canada-2.0",
"OGL-UK-1.0",

"OGL-UK-2.0",
"OGL-UK-3.0",
"OGTSL",
"OLDAP-1.1",
"OLDAP-1.2",
"OLDAP-1.3",
"OLDAP-1.4",
"OLDAP-2.0",
"OLDAP-2.0.1",
"OLDAP-2.1",
"OLDAP-2.2",
"OLDAP-2.2.1",
"OLDAP-2.2.2",
"OLDAP-2.3",
"OLDAP-2.4",
"OLDAP-2.5",
"OLDAP-2.6",
"OLDAP-2.7",
"OLDAP-2.8",
"OLFL-1.3",
"OML",
"OPL-1.0",
"OPL-UK-3.0",
"OPUBL-1.0",
"OSET-PL-2.1",
"OSL-1.0",
"OSL-1.1",
"OSL-2.0",
"OSL-2.1",
"OSL-3.0",
"OpenPBS-2.3",
"OpenSSL",
"OpenSSL-standalone",
"OpenVision",
"PADL",
"PDDL-1.0",
"PHP-3.0",
"PHP-3.01",
"PSF-2.0",
"Parity-6.0.0",
"Parity-7.0.0",
"Pixar",
"Plexus",
"PolyForm-Noncommercial-1.0.0",
"PolyForm-Small-Business-1.0.0",
"PostgreSQL",
"Python-2.0",
"Python-2.0.1",

"QPL-1.0",
"QPL-1.0-INRIA-2004",
"Qhull",
"RHeCos-1.1",
"RPL-1.1",
"RPL-1.5",
"RPSL-1.0",
"RSA-MD",
"RSCPL",
"Rdisc",
"Ruby",
"SAX-PD",
"SAX-PD-2.0",
"SCEA",
"SGI-B-1.0",
"SGI-B-1.1",
"SGI-B-2.0",
"SGI-OpenGL",
"SGP4",
"SHL-0.5",
"SHL-0.51",
"SISSL",
"SISSL-1.2",
"SL",
"SMLNJ",
"SMPPL",
"SNIA",
"SPL-1.0",
"SSH-OpenSSH",
"SSH-short",
"SSLeay-standalone",
"SSPL-1.0",
"SWL",
"Saxpath",
"SchemeReport",
"Sendmail",
"Sendmail-8.23",
"SimPL-2.0",
"Sleepycat",
"Soundex",
"Spencer-86",
"Spencer-94",
"Spencer-99",
"SugarCRM-1.1.3",
"Sun-PPP",
"SunPro",
"Symlinks",
"TAPR-OHL-1.0",

"TCL",
"TCP-wrappers",
"TGPPL-1.0",
"TMate",
"TORQUE-1.1",
"TOSL",
"TPDL",
"TPL-1.0",
"TTWL",
"TTYP0",
"TU-Berlin-1.0",
"TU-Berlin-2.0",
"TermReadKey",
"UCAR",
"UCL-1.0",
"UMich-Merit",
"UPL-1.0",
"URT-RLE",
"Unicode-3.0",
"Unicode-DFS-2015",
"Unicode-DFS-2016",
"Unicode-TOU",
"UnixCrypt",
"Unlicense",
"VOSTROM",
"VSL-1.0",
"Vim",
"W3C",
"W3C-19980720",
"W3C-20150513",
"WTFPL",
"Watcom-1.0",
"Widget-Workshop",
"Wsuipa",
"X11",
"X11-distribute-modifications-variant",
"XFree86-1.1",
"XSkat",
"Xdebug-1.03",
"Xerox",
"Xfig",
"Xnet",
"YPL-1.0",
"YPL-1.1",
"ZPL-1.1",
"ZPL-2.0",
"ZPL-2.1",
"Zed",

"Zeeff",
"Zend-2.0",
"Zimbra-1.3",
"Zimbra-1.4",
"Zlib",
"bcrypt-Solar-Designer",
"blessing",
"bzip2-1.0.6",
"check-cvs",
"checkmk",
"copyleft-next-0.3.0",
"copyleft-next-0.3.1",
"curl",
"diffmark",
"dtoa",
"dvipdfm",
"eGenix",
"etalab-2.0",
"fwlw",
"gSOAP-1.3b",
"gnuplot",
"gtkbook",
"hdparm",
"iMatix",
"libpng-2.0",
"libselinux-1.0",
"libtiff",
"libutil-David-Nugent",
"lsof",
"magaz",
"mailprio",
"metamail",
"mpi-permissive",
"mpich2",
"mplus",
"pnmstitch",
"psfrag",
"psutils",
"python-ldap",
"radvd",
"snprintf",
"softSurfer",
"ssh-keyscan",
"swrule",
"ulem",
"w3m",
"xinetd",
"xkeyboard-config-Zinoviev",

"xlock",
"xpp",
"zlib-acknowledgement"
]
Creative Commons CC0
[
"AGPL-1.0",
"AGPL-3.0",
"BSD-2-Clause-FreeBSD",
"BSD-2-Clause-NetBSD",
"GFDL-1.1",
"GFDL-1.2",
"GFDL-1.3",
"GPL-1.0",
"GPL-1.0+",
"GPL-2.0",
"GPL-2.0+",
"GPL-2.0-with-GCC-exception",
"GPL-2.0-with-autoconf-exception",
"GPL-2.0-with-bison-exception",
"GPL-2.0-with-classpath-exception",
"GPL-2.0-with-font-exception",
"GPL-3.0",
"GPL-3.0+",
"GPL-3.0-with-GCC-exception",
"GPL-3.0-with-autoconf-exception",
"LGPL-2.0",
"LGPL-2.0+",
"LGPL-2.1",
"LGPL-2.1+",
"LGPL-3.0",
"LGPL-3.0+",
"Nunit",
"StandardML-NJ",
"bzip2-1.0.5",
"eCos-2.0",
"wxWindows"
]
spdx-license-ids

[![npm version](https://img.shields.io/npm/v/spdx-license-ids.svg)](https://www.npmjs.com/package/spdx-license-ids)
[![Github Actions](https://action-badges.now.sh/jslicense/spdx-license-ids)](https://wdp9fww0r9.execute-api.us-west-2.amazonaws.com/production/results/jslicense/spdx-license-ids)

A list of [SPDX license](https://spdx.org/licenses/) identifiers

Installation

[Download JSON directly](https://raw.githubusercontent.com/jslicense/spdx-license-ids/main/index.json), or [use](https://docs.npmjs.com/cli/install) [npm](https://docs.npmjs.com/about-npm/):

```
npm install spdx-license-ids
```

[Node.js](https://nodejs.org/) API

require('spdx-license-ids')

Type: `string[]`

All license IDs except for the currently deprecated ones.

```javascript
const ids = require('spdx-license-ids');
//=> ['0BSD', 'AAL', 'ADSL', 'AFL-1.1', 'AFL-1.2', 'AFL-2.0', 'AFL-2.1', 'AFL-3.0', 'AGPL-1.0-only', ...]

ids.includes('BSD-3-Clause'); //=> true
ids.includes('CC-BY-1.0');
 //=> true

ids.includes('GPL-3.0'); //=> false
```

require('spdx-license-ids/deprecated')

Type: `string[]`

Deprecated license IDs.

```javascript
const deprecatedIds = require('spdx-license-ids/deprecated');
//=> ['AGPL-1.0', 'AGPL-3.0', 'GFDL-1.1', 'GFDL-1.2', 'GFDL-1.3', 'GPL-1.0', 'GPL-2.0', ...]

deprecatedIds.includes('BSD-3-Clause'); //=> false
deprecatedIds.includes('CC-BY-1.0'); //=> false

deprecatedIds.includes('GPL-3.0'); //=> true
```

License

[Creative Commons Zero v1.0 Universal](https://creativecommons.org/publicdomain/zero/1.0/deed)

1.1452 browserslist 4.23.0

1.1452.1 Available under license :

MIT
The MIT License (MIT)

Copyright 2014 Andrey Sitnik <andrey@sitnik.ru> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1453 spdx-exceptions 2.5.0

1.1453.1 Available under license :

UNRECOGNIZED LICENSE; MD5 sum: 9b06e0787814edfe98666e676afd12e4

1.1454 core-js-compat 3.36.0

1.1454.1 Available under license :

Copyright (c) 2014-2024 Denis Pushkarev

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.1455 available-typed-arrays 1.0.7

1.1455.1 Available under license :

MIT License

Copyright (c) 2020 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1456 possible-typed-array-names 1.0.0

1.1456.1 Available under license :

MIT License

Copyright (c) 2024 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1457 typed-array-byte-offset 1.0.2

1.1457.1 Available under license :

MIT License

Copyright (c) 2020 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1458 typed-array-buffer 1.0.2

1.1458.1 Available under license :

MIT
MIT License

Copyright (c) 2023 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1459 typed-array-byte-length 1.0.1

1.1459.1 Available under license :

MIT License

Copyright (c) 2020 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1460 is-shared-array-buffer 1.0.3

1.1460.1 Available under license :

MIT License

Copyright (c) 2021 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1461 es-set-tostringtag 2.0.3

1.1461.1 Available under license :

MIT License

Copyright (c) 2022 ECMAScript Shims

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell

copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1462 is-negative-zero 2.0.3

1.1462.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1463 typed-array-length 1.0.5

1.1463.1 Available under license :

MIT License

Copyright (c) 2020 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1464 set-function-name 2.0.2

1.1464.1 Available under license :

MIT License

Copyright (c) Jordan Harband and contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1465 jackson-core 2.12.7

1.1465.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work

(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work

or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Jackson JSON processor

Jackson is a high-performance, Free/Open Source JSON processing library.
It was originally written by Tatu Saloranta (tatu.saloranta@iki.fi), and has
been in development since 2007.
It is currently developed by a community of developers.

Licensing

Jackson 2.x core and extension components are licensed under Apache License 2.0
To find the details that apply to this artifact see the accompanying LICENSE file.

Credits

A list of contributors may be found from CREDITS(-2.x) file, which is included
in some artifacts (usually source distributions); but is always available
from the source code management (SCM) system project uses.

1.1466 istack-commons-runtime 3.0.7

1.1466.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2012 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License").  You
* may not use this file except in compliance with the License.  You can
* obtain a copy of the License at
* http://glassfish.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt.  See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license."  If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above.  However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject
 to such option by the copyright
* holder.
*/
```

Found in path(s):
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/Builder.java
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/package-info.java
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/Nullable.java
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/Interned.java
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/NotNull.java
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/SAXException2.java
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/SAXParseException2.java
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/Pool.java
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/XMLStreamException2.java
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/FinalArrayList.java
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/FragmentContentHandler.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version
 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under

* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
 * holder.
*/

Found in path(s):
* /istack-commons-runtime-3-0-7-java-jar/module-info.java
No license file was found, but licenses were detected in source scan.

<!--

  DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.

  Copyright (c) 1997-2018 Oracle and/or its affiliates. All rights reserved.

  The contents of this file are subject to the terms of either the GNU
  General Public License Version 2 only ("GPL") or the Common Development
  and Distribution License("CDDL") (collectively, the "License"). You
  may not use this file except in compliance with the License. You can
  obtain a copy of the License at
  http://glassfish.java.net/public/CDDL+GPL_1_1.html
  or packager/legal/LICENSE.txt. See the License for the specific
  language governing permissions and limitations under the License.

  When distributing the software, include this License Header Notice in each
  file and include the License file at packager/legal/LICENSE.txt.

  GPL Classpath Exception:
  Oracle designates this particular file as subject to the "Classpath"

 exception as provided by Oracle in the GPL Version 2 section of the License
  file that accompanied this code.

  Modifications:
  If applicable, add the following below the License Header, with the fields
  enclosed by brackets [] replaced by your own identifying information:
  "Portions Copyright [year] [name of copyright owner]"

  Contributor(s):
  If you wish your version of this file to be governed by only the CDDL or
  only the GPL Version 2, indicate your decision by adding "[Contributor]
  elects to include this software in this distribution under the [CDDL or GPL
  Version 2] license." If you don't indicate a single choice of license, a
  recipient has the option to distribute your version of this file under
  either the CDDL, the GPL Version 2 or to extend the choice of license to
  its licensees as provided above. However, if you add GPL Version 2 code

and therefore, elected the GPL Version 2 license, then the option applies
only if the new
code is made subject to such option by the copyright
holder.

-->

Found in path(s):
* /istack-commons-runtime-3-0-7-java-jar/META-INF/maven/com.sun.istack/istack-commons-runtime/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2014 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* http://glassfish.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies

* only if the new code is made subject
 to such option by the copyright
* holder.
*/

Found in path(s):
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/XMLStreamReaderToContentHandler.java
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/ByteArrayDataSource.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2016 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* http://glassfish.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject

to such option by the copyright
* holder.
*/

Found in path(s):
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/localization/NullLocalizable.java
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/localization/Localizable.java
No license file was found, but licenses were detected in source scan.

Manifest-Version: 1.0
Created-By: Apache Maven Bundle Plugin
Built-By: build
Build-Jdk: 9.0.4
Implementation-Build-Id: 3.0.7-c8b5e20894f565780625d6f9b018ef7c458cd68
8, 2018-08-29T05:23:37-0700
Bnd-LastModified: 1535545434210
Bundle-Description: istack common utility code
Bundle-DocURL: http://www.oracle.com/
Bundle-License: https://glassfish.java.net/public/CDDL+GPL_1_1.html, h
ttps://glassfish.java.net/public/CDDL+GPL_1_1.html
Bundle-ManifestVersion: 2
Bundle-Name: istack common utility code runtime
Bundle-SymbolicName: com.sun.istack.commons-runtime
Bundle-Vendor: Oracle Corporation
Bundle-Version: 3.0.7
Export-Package: com.sun.istack;version="3.0.7";uses:="javax.activation
,javax.xml.stream,org.xml.sax,org.xml.sax.helpers",com.sun.istack.loc
alization;version="3.0.7",com.sun.istack.logging;version="3.0.7"
Implementation-Title: istack common utility code runtime
Implementation-Vendor: Oracle Corporation
Implementation-Vendor-Id:
com.sun.istack
Implementation-Version: 3.0.7
Import-Package: javax.activation,javax.xml.namespace,javax.xml.stream,
org.xml.sax,org.xml.sax.helpers
Originally-Created-By: Apache Maven Bundle Plugin
Require-Capability: osgi.ee;filter:="(&(osgi.ee=JavaSE)(version=1.7))"
Tool: Bnd-3.2.0.201605172007

Found in path(s):
* /istack-commons-runtime-3-0-7-java-jar/META-INF/MANIFEST.MF
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2017 Oracle and/or its affiliates. All rights reserved.
*

* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* http://glassfish.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject
 to such option by the copyright
* holder.
*/

Found in path(s):
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/localization/LocalizableMessageFactory.java
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/localization/Localizer.java
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/localization/LocalizableMessage.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2015 Oracle and/or its affiliates. All rights reserved.
*

* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* http://glassfish.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject
 to such option by the copyright
* holder.
*/

Found in path(s):
* /istack-commons-runtime-3-0-7-java-jar/com/sun/istack/logging/Logger.java

1.1467 esniff 2.0.1

1.1467.1 Available under license :

ISC License

Copyright (c) 2013-2024, Mariusz Nowak, @medikoo, medikoo.com

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
ISC

1.1468 @babel/types 7.24.0

1.1468.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1469 @babel/traverse 7.24.0

1.1469.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1470 @babel/parser 7.24.0

1.1470.1 Available under license :

Copyright (C) 2012-2014 by various contributors (see AUTHORS)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT

OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1471 @babel/template 7.24.0

1.1471.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1472 @babel/runtime 7.24.0

1.1472.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to

the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1473 es-abstract 1.22.5

1.1473.1 Available under license :

The MIT License (MIT)

Copyright (C) 2015 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.1474 @emotion/is-prop-valid 1.2.2

1.1474.1 Available under license :

MIT License

Copyright (c) Emotion team and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1475 express 4.18.3

1.1475.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2009-2014 TJ Holowaychuk <tj@vision-media.ca>
Copyright (c) 2013-2014 Roman Shtylman <shtylman+expressjs@gmail.com>
Copyright (c) 2014-2015 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT
SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1476 @babel/preset-env 7.24.0

1.1476.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1477 @babel/core 7.24.0

1.1477.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the

"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1478 @ampproject/remapping 2.3.0

1.1478.1 Available under license :

Apache License 2.0

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity

exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the

Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents

of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,

work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1479 @babel/helper-plugin-utils 7.24.0

1.1479.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1480 babel-helper-create-class-features-plugin 7.24.0

1.1480.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1481 @babel/plugin-transform-object-rest-spread 7.24.0

1.1481.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1482 @babel/helpers 7.24.0

1.1482.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1483 fast-infoset 1.2.15

1.1483.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version

2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
* holder.
*/

Found in path(s):
* /fastinfoset-1-2-15-sources-6-jar/module-info.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2004-2013 Oracle and/or its affiliates. All rights reserved.
*
* Oracle licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/Decoder.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/sax/SAXDocumentParser.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/algorithm/BooleanEncodingAlgorithm.java
*

/fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/algorithm/BuiltInEncodingAlgorithm.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/sax/AttributesHolder.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/algorithm/HexadecimalEncodingAlgorithm.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/algorithm/FloatEncodingAlgorithm.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/algorithm/BASE64EncodingAlgorithm.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/StAXDocumentParser.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2004-2011 Oracle and/or its affiliates. All rights reserved.
*
* Oracle licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/*
* The Apache Software License, Version 1.1
*
*
* Copyright (c) 1999-2004 The Apache Software Foundation. All rights
* reserved.
*
* Redistribution and use in source and binary forms, with
 or without
* modification, are permitted provided that the following conditions
* are met:
*
* 1. Redistributions of source code must retain the above copyright
*   notice, this list of conditions and the following disclaimer.
*
* 2. Redistributions in binary form must reproduce the above copyright
*   notice, this list of conditions and the following disclaimer in
*   the documentation and/or other materials provided with the
*   distribution.
*
* 3. The end-user documentation included with the redistribution,
*   if any, must include the following acknowledgment:
*   "This product includes software developed by the

```
*       Apache Software Foundation (http://www.apache.org/)."
*    Alternately, this acknowledgment may appear in the software itself,
*    if and wherever such third-party acknowledgments normally appear.
*
* 4. The names "Xerces" and "Apache Software Foundation" must
*    not be used to endorse or promote products derived from this
*
  software without prior written permission. For written
*    permission, please contact apache@apache.org.
*
* 5. Products derived from this software may not be called "Apache",
*    nor may "Apache" appear in their name, without prior written
*    permission of the Apache Software Foundation.
*
* THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESSED OR IMPLIED
* WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
* OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
* DISCLAIMED.  IN NO EVENT SHALL THE APACHE SOFTWARE FOUNDATION OR
* ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
* SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
* LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF
* USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
* ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
* OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT
* OF THE USE
 OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
* SUCH DAMAGE.
* ====================================================================
*
* This software consists of voluntary contributions made by many
* individuals on behalf of the Apache Software Foundation and was
* originally based on software copyright (c) 1999, International
* Business Machines, Inc., http://www.apache.org.  For more
* information on the Apache Software Foundation, please see
* <http://www.apache.org/>.
*/

Found in path(s):
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/org/apache/xerces/util/XMLChar.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2005-2011 Oracle and/or its affiliates. All rights reserved.
*
* Oracle licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
```

* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/StAXFilteredEvent.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2004-2012 Oracle and/or its affiliates. All rights reserved.
*
* Oracle licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/factory/StAXOutputFactory.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/tools/SAXEventSerializer.java
*
 /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/dom/DOMDocumentParser.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/tools/TransformInputOutput.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/StartElementEvent.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/CommonResourceBundle.java
No license file was found, but licenses were detected in source scan.

Copyright (c) 2012 Oracle and/or its affiliates. All rights reserved.
Oracle licenses this file to You under the Apache License, Version 2.0
(the "License"); you may not use this file except in compliance with
the License. You may obtain a copy of the License at
http://www.apache.org/licenses/LICENSE-2.0

distributed under the License is distributed on an "AS IS" BASIS,

Found in path(s):
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/resources/ResourceBundle.properties
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2004-2011 Oracle and/or its affiliates. All rights reserved.
*
* Oracle licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/*
*
* This code is subject to the freebxml License, Version 1.1
*
* Copyright (c) 2001 - 2005 freebxml.org. All rights reserved.
*
* $Header:
/zpool01/javanet/scm/svn/tmp/cvs2svn/fi/FastInfoset/src/com/sun/xml/fastinfoset/AbstractResourceBundle.java,v
 1.3.2.4 2009-05-13 08:53:01 oleksiys Exp $
*/

Found in path(s):
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/AbstractResourceBundle.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2004-2011 Oracle and/or its affiliates. All rights reserved.
*
* Oracle licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/FastInfosetException.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/EncodingAlgorithmException.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/sax/ExtendedContentHandler.java
*
/fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/alphabet/BuiltInRestrictedAlphabets.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/FastInfosetResult.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/sax/FastInfosetWriter.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/EncodingAlgorithm.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/tools/SAX2StAXWriter.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/ExternalVocabulary.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/tools/PrintTable.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/FastInfosetSerializer.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/Encoder.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/EncodingAlgorithmIndexes.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/sax/SystemIdResolver.java
*
/fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/XMLConstants.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/sax/PrimitiveTypeContentHandler.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/StAXManager.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/stax/LowLevelFastInfosetStreamWriter.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/algorithm/LongEncodingAlgorithm.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/tools/XML_DOM_SAX_FI.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/EventLocation.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/StAXDocumentSerializer.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/CharArray.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/StAXEventAllocatorBase.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/util/StAXFilteredParser.java
*
/fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/tools/XML_SAX_StAX_FI.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/EncodingConstants.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/algorithm/IntegerEncodingAlgorithm.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/EmptyIterator.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/sax/FastInfosetReader.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/CharArrayArray.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/EndElementEvent.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/ContiguousCharArrayArray.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/tools/XML_SAX_FI.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/sax/SAXDocumentSerializerWithPrefixMapping.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/EntityDeclarationImpl.java

*
 /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/NamespaceContextImplementation.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/FixedEntryStringIntMap.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/FastInfosetParser.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/tools/FI_SAX_Or_XML_SAX_SAXEvent.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/VocabularyApplicationData.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/tools/FI_DOM_Or_XML_DOM_SAX_SAXEvent.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/vocab/ParserVocabulary.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/algorithm/ShortEncodingAlgorithm.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/EndDocumentEvent.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/CommentEvent.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/vocab/SerializerVocabulary.java
*
 /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/tools/FI_SAX_XML.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/AttributeBase.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/sax/RestrictedAlphabetContentHandler.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/stax/FastInfosetStreamReader.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/DTDEvent.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/algorithm/DoubleEncodingAlgorithm.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/StartDocumentEvent.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/KeyIntMap.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/ValueArray.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/StringIntMap.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/algorithm/BuiltInEncodingAlgorithmFactory.java
*
 /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/Vocabulary.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/EntityReferenceEvent.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/Util.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/util/StAXParserWrapper.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/UnparsedEntity.java
* /fastinfoset-1-2-15-sources-6-
jar/com/sun/xml/fastinfoset/tools/FI_SAX_Or_XML_SAX_DOM_SAX_SAXEvent.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/factory/StAXInputFactory.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/PrefixArray.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/DecoderStateTables.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/sax/Properties.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/algorithm/UUIDEncodingAlgorithm.java
*
 /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/QualifiedNameArray.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/algorithm/BuiltInEncodingAlgorithmState.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/tools/StAX2SAXReader.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/tools/FI_StAX_SAX_Or_XML_SAX_SAXEvent.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/StringArray.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/sax/helpers/EncodingAlgorithmAttributesImpl.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/factory/StAXEventFactory.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/EventBase.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/ValueArrayResourceException.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/tools/XML_DOM_FI.java

* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/dom/DOMDocumentSerializer.java
*
 /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/sax/Features.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/sax/EncodingAlgorithmAttributes.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/NamespaceBase.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/LocalNameQualifiedNamesMap.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/CharArrayIntMap.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/algorithm/IntEncodingAlgorithm.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/sax/EncodingAlgorithmContentHandler.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/StAXEventReader.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/ProcessingInstructionEvent.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/OctetBufferListener.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/ReadIterator.java
*
 /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/tools/VocabularyGenerator.java
* /fastinfoset-1-2-15-sources-6-
jar/com/sun/xml/fastinfoset/algorithm/IEEE754FloatingPointEncodingAlgorithm.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/DuplicateAttributeVerifier.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/sax/SAXDocumentSerializer.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/StAXEventWriter.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/stax/events/CharactersEvent.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/Notation.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/vocab/Vocabulary.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/sax/helpers/FastInfosetDefaultHandler.java
* /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/FastInfosetSource.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/util/CharArrayString.java
*
 /fastinfoset-1-2-15-sources-6-jar/org/jvnet/fastinfoset/RestrictedAlphabet.java
* /fastinfoset-1-2-15-sources-6-jar/com/sun/xml/fastinfoset/QualifiedName.java

1.1484 txw2 2.3.1

1.1484.1 Available under license :

No license file was found, but licenses were detected in source scan.

<!--

DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.

Copyright (c) 2005-2017 Oracle and/or its affiliates. All rights reserved.

The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
obtain a copy of the License at
https://oss.oracle.com/licenses/CDDL+GPL-1.1

or LICENSE.txt. See the License for the specific
language governing permissions and limitations under the License.

When distributing the software, include this License Header Notice in each
file and include the License file at LICENSE.txt.

GPL Classpath Exception:
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the
GPL Version 2 section of the License
file that accompanied this code.

Modifications:
If applicable, add the following below the License Header, with the fields
enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"

Contributor(s):
If you wish your version of this file to be governed by only the CDDL or
only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if the new code is made subject to such option
by the copyright
holder.

-->

Found in path(s):
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/annotation/package.html
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/package.html
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/package.html
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2005-2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at

* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version
 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
 * holder.
*/

Found in path(s):
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/Attribute.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/StreamSerializer.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/XmlSerializer.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/StartTag.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/TxwException.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/ContentVisitor.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/IndentingXMLFilter.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/TypedXmlWriter.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/annotation/XmlValue.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/TXWResult.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/annotation/XmlCDATA.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/DatatypeWriter.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/IllegalAnnotationException.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/IllegalSignatureException.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/Cdata.java
*

/txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/DumbEscapeHandler.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/DumpSerializer.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/Text.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/EndTag.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/IndentingXMLStreamWriter.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/Content.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/DelegatingXMLStreamWriter.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/annotation/XmlAttribute.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/Document.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/DataWriter.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/DomSerializer.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/StartDocument.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/Comment.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/annotation/XmlElement.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/TXW.java
*
/txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/ResultFactory.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/EndDocument.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/TXWSerializer.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/NamespaceResolver.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/ContainerElement.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/SaxSerializer.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/annotation/XmlNamespace.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/Pcdata.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/CharacterEscapeHandler.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/StaxSerializer.java
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/NamespaceDecl.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2005-2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"

```
* exception as provided by Oracle in the GPL Version
 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license."  If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above.  However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
 * holder.
*/
// This class is in the Public Domain.  NO WARRANTY!
/**
* Encapsulate Namespace logic for use by applications using SAX,
* or internally by SAX drivers.
*
* <blockquote>
* <em>This module, both source code and documentation, is in the
* Public Domain, and comes with <strong>NO WARRANTY</strong>.</em>
* See <a href='http://www.saxproject.org'>http://www.saxproject.org</a>
* for further information.
* </blockquote>
*
* <p>This class encapsulates the logic of Namespace processing: it
* tracks the declarations currently in force for each context and
* automatically processes qualified XML names into their Namespace
* parts; it can also be used in reverse for generating XML qnames
* from Namespaces.</p>
*
* <p>Namespace support objects are reusable, but the reset method
* must be invoked between each session.</p>
*
* <p>Here is a simple session:</p>
*
* <pre>
* String parts[] = new String[3];
* NamespaceSupport support = new NamespaceSupport();
*
```

```
* support.pushContext();
 * support.declarePrefix("", "http://www.w3.org/1999/xhtml");
* support.declarePrefix("dc", "http://www.purl.org/dc#");
*
* parts = support.processName("p", parts, false);
* System.out.println("Namespace URI: " + parts[0]);
* System.out.println("Local name: " + parts[1]);
* System.out.println("Raw name: " + parts[2]);
*
* parts = support.processName("dc:title", parts, false);
* System.out.println("Namespace URI: " + parts[0]);
* System.out.println("Local name: " + parts[1]);
* System.out.println("Raw name: " + parts[2]);
*
* support.popContext();
* </pre>
*
* <p>Note that this class is optimized for the use case where most
* elements do not contain Namespace declarations: if the same
* prefix/URI mapping is repeated for each context (for example), this
* class will be somewhat less efficient.</p>
*
* <p>Although SAX drivers (parsers) may choose to use this class to
* implement namespace handling, they are not required to do so.
* Applications
 must track namespace information themselves if they
* want to use namespace information.
*
* @since SAX 2.0
* @author David Megginson
* @version 2.0.1 (sax2r2)
*/
```

Found in path(s):
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/NamespaceSupport.java
No license file was found, but licenses were detected in source scan.


```
/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2005-2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License").  You
* may not use this file except in compliance with the License.  You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
```

* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version
 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
 * holder.
*/
// NO WARRANTY! This class is in the public domain.

Found in path(s):
* /txw2-2-3-1-sources-4-jar/com/sun/xml/txw2/output/XMLWriter.java
No license file was found, but licenses were detected in source scan.

<!--

  DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.

  Copyright (c) 2005-2018 Oracle and/or its affiliates. All rights reserved.

  The contents of this file are subject to the terms of either the GNU
  General Public License Version 2 only ("GPL") or the Common Development
  and Distribution License("CDDL") (collectively, the "License"). You
  may not use this file except in compliance with the License. You can
  obtain a copy of the License at
  https://oss.oracle.com/licenses/CDDL+GPL-1.1
  or LICENSE.txt. See the License for the specific

language governing permissions and limitations under the License.

When distributing the software, include this License Header Notice in each
file and include the License file at LICENSE.txt.

GPL Classpath Exception:
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the
GPL Version 2 section of the License
file that accompanied this code.

Modifications:
If applicable, add the following below the License Header, with the fields
enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"

Contributor(s):
If you wish your version of this file to be governed by only the CDDL or
only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if the new code is made subject to such option
by the copyright
holder.

-->

Found in path(s):
* /txw2-2-3-1-sources-4-jar/META-INF/maven/org.glassfish.jaxb/txw2/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.

*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version
 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
 * holder.
*/

Found in path(s):
* /txw2-2-3-1-sources-4-jar/module-info.java

1.1485 jaxb-runtime 2.3.1

1.1485.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1

```
* or LICENSE.txt.  See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version
 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license."  If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above.  However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
 * holder.
*/
// NO WARRANTY!  This class is in the public domain.
/**
* Default implementation of the Attributes interface.
*
* <blockquote>
* <em>This module, both source code and documentation, is in the
* Public Domain, and comes with <strong>NO WARRANTY</strong>.</em>
* See <a href='http://www.saxproject.org'>http://www.saxproject.org</a>
* for further information.
* </blockquote>
*
* <p>This class provides a default implementation of the SAX2
* {@link org.xml.sax.Attributes Attributes} interface, with the
* addition of manipulators so that the list can be modified or
* reused.</p>
*
* <p>There are two typical uses of this class:</p>
*
* <ol>
```

```
* <li>to take a persistent snapshot of an Attributes object
*  in a {@link org.xml.sax.ContentHandler#startElement startElement} event; or</li>
* <li>to construct or modify an Attributes object in a SAX2 driver or filter.</li>
* </ol>
*
* <p>This class replaces the now-deprecated SAX1 {@link
* org.xml.sax.helpers.AttributeListImpl
 AttributeListImpl}
* class; in addition to supporting the updated Attributes
* interface rather than the deprecated {@link org.xml.sax.AttributeList
* AttributeList} interface, it also includes a much more efficient
* implementation using a single array rather than a set of Vectors.</p>
*
* @since JAXB 1.0
* @since SAX 2.0
* @author David Megginson
* @version 2.0.1 (sax2r2)
*/
```

Found in path(s):
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/util/AttributesImpl.java
No license file was found, but licenses were detected in source scan.


```
/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2018 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License").  You
* may not use this file except in compliance with the License.  You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt.  See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version
 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
```

* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
 * holder.
*/

Found in path(s):
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/XMLStreamWriterOutput.java
No license file was found, but licenses were detected in source scan.

Copyright (c) 1997-2017 Oracle and/or its affiliates. All rights reserved.
The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section of the License

Found in path(s):
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_pt_BR.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_de.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_ja.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_it.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_fr.properties
*
 /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/Messages_fr.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_zh_CN.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_zh_TW.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/Messages.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/Messages_it.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_zh_CN.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_pt_BR.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_zh_CN.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_ja.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages.properties
*

/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_ko.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/Messages_fr.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_zh_TW.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_ja.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/Messages_de.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_ko.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_de.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/Messages_it.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_es.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_zh_CN.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_fr.properties
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_zh_TW.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_es.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_de.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_ko.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_de.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_pt_BR.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/Messages.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_de.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_ja.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_pt_BR.properties
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_fr.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_ko.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_it.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_ja.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_de.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_fr.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_zh_TW.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/Messages_zh_TW.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_zh_TW.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/Messages_ja.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_fr.properties
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/Messages_zh_CN.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_ko.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_ko.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_es.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_it.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_it.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/Messages_zh_CN.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/Messages.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/Messages_ko.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/Messages.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_ja.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/Messages_es.properties
*

/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_zh_CN.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/Messages_de.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/Messages_ko.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/Messages_it.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/Messages_pt_BR.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/Messages_es.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_pt_BR.properties
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_pt_BR.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_es.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_ko.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_es.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_fr.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/Messages_zh_TW.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_fr.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_zh_TW.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_pt_BR.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_es.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_de.properties
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_pt_BR.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/Messages_ja.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_ja.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_it.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/Messages_fr.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/Messages_zh_TW.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_zh_TW.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_fr.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_es.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/Messages_es.properties
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/Messages_ja.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_zh_CN.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/Messages_zh_CN.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/Messages_de.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_zh_CN.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_it.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_ja.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_zh_CN.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_de.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/Messages_pt_BR.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_it.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_it.properties

*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/Messages_ko.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/Messages_pt_BR.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_zh_TW.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_ko.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_es.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages.properties
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version
 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright

* holder.
*/

Found in path(s):
* /jaxb-runtime-2-3-1-sources-6-jar/module-info.java
No license file was found, but licenses were detected in source scan.

Copyright (c) 2014-2017 Oracle and/or its affiliates. All rights reserved.
The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section of the License

Found in path(s):
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/Messages_de.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/Messages_es.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/Messages_pt_BR.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/Messages_ko.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/Messages_zh_CN.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/Messages_zh_TW.properties
*
 /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/Messages_it.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/Messages_ja.properties
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/Messages_fr.properties
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version

2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
* holder.
*/
/**
* Sets the int[] data to this object.
*
* <p>
* This method doesn't make a copy for a performance reason.
* The caller is still free to modify the array it passed to this method,
* but he should do so with a care. The unmarshalling code isn't expecting
* the value to be changed while it's being routed.
*/

Found in path(s):
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/IntArrayData.java
No license file was found, but licenses were detected in source scan.

<!--

DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.

Copyright (c) 1997-2017 Oracle and/or its affiliates. All rights reserved.

The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
obtain a copy of the License at
https://oss.oracle.com/licenses/CDDL+GPL-1.1
or LICENSE.txt. See the License for the specific
language governing permissions and limitations under the License.

When distributing the software, include this License Header Notice in each
file and include the License file at LICENSE.txt.

GPL Classpath Exception:
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the
GPL Version 2 section of the License
file that accompanied this code.

Modifications:
If applicable, add the following below the License Header, with the fields
enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"

Contributor(s):
If you wish your version of this file to be governed by only the CDDL or
only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if the new code is made subject to such option
by the copyright
holder.

-->

Found in path(s):
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/xmlschema-for-jaxb.rng
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*

* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version
 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
 * holder.
*/

Found in path(s):
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/annotation/XmlIsSet.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/NamespacePrefixMapper.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/package-info.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/DummyPropertyInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/XmlVisitor.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerLong.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeAttributePropertyInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/SingleElementNodeProperty.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Wildcard.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/BridgeAdapter.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlElementDeclQuick.java
*
 /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerCharacter.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/Locatable.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SimpleRestrictionModel.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/IllegalAnnotationException.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/ValuePropertyLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/Messages.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/util/QNameMap.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/FilterTransducer.java

* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/ReferencePropertyInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/Bridge.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/MarshallerImpl.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/DefaultTransducedAccessor.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/AdaptedLister.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/Form.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/LeafPropertyLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/SwaRefAdapter.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SimpleTypeHost.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/SecureLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeNonElementRef.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ArrayElementNodeProperty.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/SAXConnector.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SimpleDerivation.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimePropertyInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/util/SecureLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ValueProperty.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/AssociationMap.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Coordinator.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/XmlAccessorFactory.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeElementInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/XmlSchemaGenerator.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/C14nXmlOutput.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeTypeInfoSetImpl.java
*
/jaxb-runtime-2-3-1-sources-6-
jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_method_Float.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/MTOMDecorator.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/LocatorExWrapper.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/XmlOutputAbstractImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/NestedParticle.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/TypeReference.java
* /jaxb-runtime-2-3-1-sources-6-
jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_method_Boolean.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/util/Which.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/MultiMap.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/ClassLocatable.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SimpleExtension.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/Messages.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/package-info.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/Adapter.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Lister.java

* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/TypeHost.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerByte.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Float.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ArrayERProperty.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/nav/GenericArrayTypeImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/DatatypeConverterImpl.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/TypeInfoSet.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/DumbEscapeHandler.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Short.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Receiver.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/EnumLeafInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/XMLEventWriterOutput.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlSchemaQuick.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/ProxyLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ComplexType.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Redefinable.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerShort.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/AccessorFactory.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/ID.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/GroupKind.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/FastInfosetConnector.java
* /jaxb-runtime-2-3-1-sources-6-
jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_method_Long.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SchemaTop.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/ElementPropertyInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/FieldPropertySeed.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/BridgeContextImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/TagAndType.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/nav/SecureLoader.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/nav/ReflectionNavigator.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/nav/TypeVisitor.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ComplexTypeModel.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/Ref.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ArrayReferenceNodeProperty.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/SAX2DOMEx.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/unmarshaller/DOMScanner.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/StAXConnector.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/bytecode/SecureLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Long.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/DataWriter.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/DomLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/TypeInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/ClassFactory.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/package-info.java

* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlValueQuick.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/AttributesEx.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SimpleContent.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/AccessorException.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/CompositeStructure.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_field_Float.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/impl/NameUtil.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/IllegalAnnotationsException.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SimpleType.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/CycleRecoverable.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Double.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeAttributePropertyInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/NameBuilder.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/InterningXmlVisitor.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Boolean.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/PropertyFactory.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/ERPropertyInfoImpl.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/ValidatingUnmarshaller.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeMapPropertyInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/MimeTypedTransducer.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/DOMOutput.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Intercepter.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/TypeDefParticle.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/SecureLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/unmarshaller/Patcher.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/DefaultIDResolver.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/Const.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/ArrayInfoImpl.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/XsiTypeLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/TopLevelAttribute.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/AnyTypeImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeValuePropertyInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ArrayProperty.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeAnyTypeImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerInteger.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeReferencePropertyInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/PropertySeed.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/ClassResolver.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeTypeInfoSet.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Long.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/Messages.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/LeafInfoImpl.java

* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/RegistryInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/PropertyImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/StAXPostInitAction.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerDouble.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/Util.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/nav/ParameterizedTypeImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/StructureLoader.java
*
 /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/FieldLocatable.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Byte.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/ArrayInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/ReferencePropertyInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeTypeRefImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlElementQuick.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/Util.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/TransducedAccessor.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Occurs.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/SecureLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/Tree.java
*
 /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/ClassInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/InlineBinaryTransducer.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/AttributePropertyInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ContentModelContainer.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Property.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/UnmarshallerChain.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/MinimumEscapeHandler.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/SecureLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/util/FatalAdapter.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeReferencePropertyInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Name.java
*
 /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_method_Byte.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlElementRefQuick.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/NamespaceContext2.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Discarder.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/DefaultValueLoaderDecorator.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/AttributeType.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Particle.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Boolean.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/ContentHandlerAdaptor.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlEnumQuick.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/ErrorHandler.java
*
 /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Appinfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/InternalAccessorFactory.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeClassInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/WellKnownNamespace.java

* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/UnmarshallingContext.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/JaxBeanInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeEnumConstantImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/TextLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/SchemaTypeTransducer.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/XmlOutput.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/nav/WildcardTypeImpl.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeMapPropertyInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Scope.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeEnumLeafInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Character.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/LeafPropertyXsiLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlElementRefsQuick.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/EnumConstant.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/ListIterator.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/StructureLoaderBuilder.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/AnnotationReader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerBoolean.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeEnumLeafInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/unmarshaller/InfosetScanner.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeValuePropertyInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ListElementProperty.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/AdaptedAccessor.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Loader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Locatable.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Integer.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_field_Short.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/FixedOrDefault.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/util/CollisionCheckStack.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Init.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/ElementPropertyInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Ref.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/SingleTypePropertyInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/SingleMapNodeProperty.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/NioEscapeHandler.java
* /jaxb-runtime-2-3-1-sources-6-
jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_method_Double.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/TODO.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/NonElement.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ExplicitGroup.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/ElementBeanInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-
jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_field_Double.java

* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/util/ByteArrayOutputStreamEx.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Quick.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/ValueListBeanInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-
jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_method_Short.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/SingleElementLeafProperty.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/StAXStreamConnector.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/ClassBeanInfoImpl.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/MapPropertyInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Import.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Transducer.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/CharacterEscapeHandler.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/WildcardTypeInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeBuiltinLeafInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/ListTransducedAccessorImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/util/TypeCast.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/bytecode/ClassTailor.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/ChildLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/StAXExStreamWriterOutput.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/InternalBridge.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/ValuePropertyInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/XMLSerializer.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/annotation/OverrideAnnotationOf.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/MethodLocatable.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/PropertyInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/Bean.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/ValidationEventLocatorEx.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/StAXExConnector.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeElementInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/ContextFactory.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/util/StackRecorder.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/NullSafeAccessor.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeTypeInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ComplexContent.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/episode/package-info.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Annotation.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Any.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/util/EditDistance.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/SecureLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Accessor.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/ModelBuilder.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Byte.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/GetterSetterPropertySeed.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeClassInfoImpl.java

* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/episode/Klass.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/ArrayBeanInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/MaybeElement.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/BuiltinLeafInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeElementPropertyInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Ref.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/BinderImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/ElementInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/LocalAttribute.java
*
 /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/SwaRefAdapterMarker.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/MapPropertyInfo.java
* /jaxb-runtime-2-3-1-sources-6-
jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_field_Integer.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ArrayElementLeafProperty.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/UnmarshallerImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/CompositeStructureBeanInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/EnumLeafInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/AttributeProperty.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlRootElementQuick.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeLeafInfo.java
*
 /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/LifecycleMethods.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/SingleReferenceNodeProperty.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeModelBuilder.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Float.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/TagName.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_field_Byte.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/impl/NameConverter.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/Element.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/ForkXmlOutput.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/AccessorFactoryImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages.java
*
 /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RegistryInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ComplexExtension.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/LocatableAnnotation.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Schema.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Documentation.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/Ref.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/NoFixedFacet.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/TopLevelElement.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/RuntimeInlineAnnotationReader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/BridgeContext.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/AccessorInjector.java
*
 /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Location.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/List.java

* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeBuiltinLeafInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerFloat.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/ErrorListener.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/WildcardLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/SAXOutput.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/WhiteSpaceProcessor.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Character.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/Pcdata.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/TypeInfoSetImpl.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/LeafBeanInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/DomPostInitAction.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Integer.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/util/FlattenIterator.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeArrayInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/AttributePropertyInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/AnyTypeBeanInfo.java
* /jaxb-runtime-2-3-1-sources-6-
jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_field_Boolean.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ArrayElementProperty.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/package-info.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/PropertyInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeNonElement.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/FoolProofResolver.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeElement.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/package-info.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/ElementInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlTypeQuick.java
* /jaxb-runtime-2-3-1-sources-6-
jar/com/sun/xml/bind/v2/model/annotation/AbstractInlineAnnotationReaderImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/MTOMXmlOutput.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/EnumConstantImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/IntData.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/JAXBRIContext.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlTransientQuick.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/util/DataSourceSource.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/ClassInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/UTF8XmlOutput.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/Encoded.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/episode/Bindings.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/package-info.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/LocatorEx.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlSchemaTypeQuick.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/AttributesExImpl.java
*

/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/NameList.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SimpleRestriction.java
* /jaxb-runtime-2-3-1-sources-6-
jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_method_Integer.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Annotated.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/TypeRefImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/LeafInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ExtensionType.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/NamespaceContextImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/XsiNilLoader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Double.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/LocalElement.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Patcher.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/WildcardMode.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/TypeRef.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/JAXBContextImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/FastInfosetStreamWriterOutput.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_field_Long.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/RawAccessor.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/TypeInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/AttrDecls.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeTypeRef.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Base64Data.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Element.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlAttributeQuick.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/BuiltinLeafInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/Messages.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/NonElementRef.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeArrayInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/AttributeAccessor.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/AnnotationSource.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/core/PropertyKind.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ComplexRestriction.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/AnyTypeAdapter.java
*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/ValuePropertyInfoImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/RuntimeAnnotationReader.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/RuntimeUtil.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeElementPropertyInfo.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/util/ValidationEventLocatorExImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/Util.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Union.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/episode/SchemaBindings.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/output/IndentingUTF8XmlOutput.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/annotation/XmlLocation.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/nav/Navigator.java

*
/jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ComplexTypeHost.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/package-info.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/BridgeImpl.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/IDResolver.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/StAXEventConnector.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Short.java
No license file was found, but licenses were detected in source scan.

<!--

DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.

Copyright (c) 2013-2018 Oracle and/or its affiliates. All rights reserved.

The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
obtain a copy of the License at
https://oss.oracle.com/licenses/CDDL+GPL-1.1
or LICENSE.txt. See the License for the specific
language governing permissions and limitations under the License.

When distributing the software, include this License Header Notice in each
file and include the License file at LICENSE.txt.

GPL Classpath Exception:
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the
GPL Version 2 section of the License
file that accompanied this code.

Modifications:
If applicable, add the following below the License Header, with the fields
enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"

Contributor(s):
If you wish your version of this file to be governed by only the CDDL or
only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if the new code is made subject to such option

by the copyright
holder.

-->

Found in path(s):
* /jaxb-runtime-2-3-1-sources-6-jar/META-INF/maven/org.glassfish.jaxb/jaxb-runtime/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version
2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright

* holder.
*/
// NO WARRANTY! This class is in the public domain.

Found in path(s):
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/XMLWriter.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2013-2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version
 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
 * holder.
*/

Found in path(s):
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/Utils.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/util/XmlFactory.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Utils.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Utils.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/Utils.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/api/Utils.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2011-2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version
 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright

```
 * holder.
*/
```

Found in path(s):
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/schemagen/episode/Package.java
No license file was found, but licenses were detected in source scan.

```
/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License").  You
* may not use this file except in compliance with the License.  You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt.  See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version
 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license."  If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above.  However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
* holder.
 */
```

Found in path(s):
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/package-info.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/util/ArrayInfoUtil.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/package-info.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/bytecode/package-info.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/annotation/package-info.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/impl/ModelBuilderI.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/model/nav/package-info.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/package-info.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/marshaller/NoEscapeHandler.java
* /jaxb-runtime-2-3-1-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/package-info.java

1.1486 es5-ext 0.10.64

1.1486.1 Available under license :

ISC License

Copyright (c) 2011-2024, Mariusz Nowak, @medikoo, medikoo.com

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT,
INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM
LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE
OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THIS SOFTWARE.
ISC

1.1487 es6-symbol 3.1.4

1.1487.1 Available under license :

ISC License

Copyright (c) 2013-2024, Mariusz Nowak, @medikoo, medikoo.com

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH
REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY
AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT,

INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1488 d 1.0.2

1.1488.1 Available under license :

ISC License

Copyright (c) 2013-2024, Mariusz Nowak, @medikoo, medikoo.com

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1489 browserify-sign 4.2.3

1.1489.1 Available under license :

ISC
Copyright (c) 2014-2015 Calvin Metcalf and browserify-sign contributors

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.1490 html-entities 2.5.2

1.1490.1 Available under license :

MIT
Copyright (c) 2021 Dulin Marat

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE
 OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1491 parse-asn1 5.1.7

1.1491.1 Available under license :

Copyright (c) 2017, crypto-browserify contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1492 javax activation api 1.2.0

1.1492.1 Available under license :

COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL) Version 1.1

1. Definitions.

1.1. "Contributor" means each individual or entity that creates or contributes to the creation of Modifications.

1.2. "Contributor Version" means the combination of the Original Software, prior Modifications used by a Contributor (if any), and the Modifications made by that particular Contributor.

1.3. "Covered Software" means (a) the Original Software, or (b) Modifications, or (c) the combination of files containing Original Software with files containing Modifications, in each case including portions thereof.

1.4. "Executable" means the Covered Software in any form other than Source Code.

1.5. "Initial Developer" means the individual or entity that first makes Original Software available under this License.

1.6. "Larger Work" means a work which combines Covered Software or portions thereof with code not governed by the terms of this License.

1.7. "License" means this document.

1.8. "Licensable" means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently acquired, any and all of the rights conveyed herein.

1.9. "Modifications" means the Source Code and Executable form of any of the following:

A. Any file that results from an addition to, deletion from or modification of the contents of a file containing Original Software or previous Modifications;

B. Any new file that contains any part of the Original Software or previous Modification; or

C. Any new file that is contributed or otherwise made available under the terms of this License.

1.10. "Original Software" means the Source Code and Executable form of computer software code that is originally released under this License.

1.11. "Patent Claims" means any patent claim(s), now owned or hereafter acquired, including without limitation, method, process, and apparatus claims, in any patent Licensable by grantor.

1.12. "Source Code" means (a) the common form of computer software code in which modifications are made and (b) associated documentation included in or with such code.

1.13. "You" (or "Your") means an individual or a legal entity exercising rights under, and complying with all of the terms of, this License. For legal entities, "You" includes any entity which controls, is controlled by, or is under common control with You. For purposes of this definition, "control" means (a) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (b) ownership of more than fifty percent (50%) of the outstanding shares or beneficial ownership of such entity.

2. License Grants.

2.1. The Initial Developer Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, the Initial Developer hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under intellectual property rights (other than patent or trademark) Licensable by Initial Developer, to use, reproduce, modify, display, perform, sublicense and distribute the Original Software (or portions thereof), with or without Modifications, and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using or selling of Original Software, to make, have made, use, practice, sell, and offer for sale, and/or otherwise dispose of the Original Software (or portions thereof).

(c) The licenses granted in Sections 2.1(a) and (b) are effective on the date Initial Developer first distributes or otherwise makes the Original Software available to a third party under the terms of this License.

(d) Notwithstanding Section 2.1(b) above, no patent license is granted: (1) for code that You delete from the Original Software, or (2) for infringements caused by: (i) the modification of the Original Software, or (ii) the combination of the Original Software with other software or devices.

2.2. Contributor Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, each Contributor hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under intellectual property rights (other than patent or trademark) Licensable by Contributor to use, reproduce, modify, display, perform, sublicense and distribute the Modifications created by such Contributor (or portions thereof), either on an unmodified basis, with other Modifications, as Covered Software and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using, or selling of Modifications made by that Contributor either alone and/or in combination with its Contributor Version (or portions of such combination), to make, use, sell, offer for sale, have made, and/or otherwise dispose of: (1) Modifications made by that Contributor (or portions thereof); and (2) the combination of Modifications made by that Contributor with its Contributor Version (or portions of such combination).

(c) The licenses granted in Sections 2.2(a) and 2.2(b) are effective on the date Contributor first distributes or otherwise makes the Modifications available to a third party.

(d) Notwithstanding Section 2.2(b) above, no patent license is granted: (1) for any code that Contributor has deleted from the Contributor Version; (2) for infringements caused by: (i) third party modifications of Contributor Version, or (ii) the combination of Modifications made by that Contributor with other software (except as part of the Contributor Version) or other devices; or (3) under Patent Claims infringed by Covered Software in the absence of Modifications made by that Contributor.

3. Distribution Obligations.

3.1. Availability of Source Code.

Any Covered Software that You distribute or otherwise make available in Executable form must also be made available in Source Code form and that Source Code form must be distributed only under the terms of this License. You must include a copy of this License with every copy of the Source Code form of the Covered Software You distribute or otherwise make available. You must inform recipients of any such Covered Software in Executable form as to how they can obtain such Covered Software in Source Code form in a reasonable manner on or through a medium customarily used for software exchange.

3.2. Modifications.

The Modifications that You create or to which You contribute are governed by the terms of this License. You represent that You believe Your Modifications are Your original creation(s) and/or You have sufficient rights to grant the rights conveyed by this License.

3.3. Required Notices.

You must include a notice in each of Your Modifications that identifies You as the Contributor of the Modification. You may not remove or alter any copyright, patent or trademark notices contained within the Covered Software, or any notices of licensing or any descriptive text giving attribution to any Contributor or the Initial Developer.

3.4. Application of Additional Terms.

You may not offer or impose any terms on any Covered Software in Source Code form that alters or restricts the applicable version of this License or the recipients' rights hereunder. You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, you may do so only on Your own behalf, and not on behalf of the Initial Developer or any Contributor. You must make it absolutely clear that any such warranty, support, indemnity or liability obligation is offered by You alone, and You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of warranty, support, indemnity or liability terms You offer.

3.5. Distribution of Executable Versions.

You may distribute the Executable form of the Covered Software under the terms of this License or under the terms of a license of Your choice, which may contain terms different from this License, provided that You are in compliance with the terms of this License

and that the license for the Executable form does not attempt to limit or alter the recipient's rights in the Source Code form from the rights set forth in this License. If You distribute the Covered Software in Executable form under a different license, You must make it absolutely clear that any
terms which differ from this License
are offered by You alone, not by the Initial Developer or Contributor. You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of any such terms You offer.

3.6. Larger Works.

You may create a Larger Work by combining Covered Software with other code not governed by the terms of this License and distribute the Larger Work as a single product. In such a case, You must make sure the requirements of this License are fulfilled for the Covered Software.

4. Versions of the License.

4.1. New Versions.

Oracle is the initial license steward and may publish revised and/or new versions of this License from time to time. Each version will be given a distinguishing version number. Except as provided in Section 4.3, no one other than the license steward has the right to modify this License.

4.2. Effect of New Versions.

You may always continue to use, distribute or otherwise make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. If the Initial Developer includes a notice in the Original Software prohibiting it from being distributed or otherwise made available under any subsequent version of the License, You must distribute and make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. Otherwise, You may also choose to use, distribute or otherwise make the Covered Software available under the terms of any subsequent version of the License published by the license steward.

4.3. Modified Versions.

When You are an Initial Developer and You want to create a new license for Your Original Software, You may create and use a

modified version of this License
if You: (a) rename the license and
remove any references to the name of the license steward (except to note that the license differs from this License); and (b) otherwise make it clear that the license contains terms which differ from this License.

5. DISCLAIMER OF WARRANTY.

COVERED SOFTWARE IS PROVIDED UNDER THIS LICENSE ON AN "AS IS" BASIS, WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES THAT THE COVERED SOFTWARE IS FREE OF DEFECTS, MERCHANTABLE, FIT FOR A PARTICULAR PURPOSE OR NON-INFRINGING. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE COVERED SOFTWARE IS WITH YOU. SHOULD ANY COVERED SOFTWARE PROVE DEFECTIVE IN ANY RESPECT, YOU (NOT THE INITIAL DEVELOPER OR ANY OTHER CONTRIBUTOR) ASSUME THE COST OF ANY NECESSARY SERVICING, REPAIR OR CORRECTION. THIS DISCLAIMER OF WARRANTY CONSTITUTES AN ESSENTIAL PART OF THIS LICENSE. NO USE OF ANY COVERED SOFTWARE IS AUTHORIZED
HEREUNDER EXCEPT UNDER THIS DISCLAIMER.

6. TERMINATION.

6.1. This License and the rights granted hereunder will terminate automatically if You fail to comply with terms herein and fail to cure such breach within 30 days of becoming aware of the breach. Provisions which, by their nature, must remain in effect beyond the termination of this License shall survive.

6.2. If You assert a patent infringement claim (excluding declaratory judgment actions) against Initial Developer or a Contributor (the Initial Developer or Contributor against whom You assert such claim is referred to as "Participant") alleging that the Participant Software (meaning the Contributor Version where the Participant is a Contributor or the Original Software where the Participant is the Initial Developer) directly or indirectly infringes any patent, then any and all rights granted directly or indirectly to You by such Participant, the Initial Developer
(if the
Initial Developer is not the Participant) and all Contributors under Sections 2.1 and/or 2.2 of this License shall, upon 60 days notice from Participant terminate prospectively and automatically at the expiration of such 60 day notice period, unless if within such 60 day period You withdraw Your claim with respect to the Participant Software against such Participant either unilaterally or pursuant to a written agreement with Participant.

6.3. If You assert a patent infringement claim against Participant alleging that the Participant Software directly or indirectly infringes any patent where such claim is resolved (such as by license or settlement) prior to the initiation of patent infringement litigation, then the reasonable value of the licenses granted by such Participant under Sections 2.1 or 2.2 shall be taken into account in determining the amount or value of any payment or license.

6.4. In the event of termination under Sections 6.1 or 6.2 above, all end user licenses that have been validly granted by You or any distributor hereunder prior to termination (excluding licenses granted to You by any distributor) shall survive termination.

7. LIMITATION OF LIABILITY.

UNDER NO CIRCUMSTANCES AND UNDER NO LEGAL THEORY, WHETHER TORT (INCLUDING NEGLIGENCE), CONTRACT, OR OTHERWISE, SHALL YOU, THE INITIAL DEVELOPER, ANY OTHER CONTRIBUTOR, OR ANY DISTRIBUTOR OF COVERED SOFTWARE, OR ANY SUPPLIER OF ANY OF SUCH PARTIES, BE LIABLE TO ANY PERSON FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY CHARACTER INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF GOODWILL, WORK STOPPAGE, COMPUTER FAILURE OR MALFUNCTION, OR ANY AND ALL OTHER COMMERCIAL DAMAGES OR LOSSES, EVEN IF SUCH PARTY SHALL HAVE BEEN INFORMED OF THE POSSIBILITY OF SUCH DAMAGES. THIS LIMITATION OF LIABILITY SHALL NOT APPLY TO LIABILITY FOR DEATH OR PERSONAL INJURY RESULTING FROM SUCH PARTY'S NEGLIGENCE TO THE EXTENT APPLICABLE LAW PROHIBITS SUCH LIMITATION. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS EXCLUSION AND LIMITATION MAY NOT APPLY TO YOU.

8. U.S. GOVERNMENT END USERS.

The Covered Software is a "commercial item," as that term is defined in 48 C.F.R. 2.101 (Oct. 1995), consisting of "commercial computer software" (as that term is defined at 48 C.F.R. 252.227-7014(a)(1)) and "commercial computer software documentation" as such terms are used in 48 C.F.R. 12.212 (Sept. 1995). Consistent with 48 C.F.R. 12.212 and 48 C.F.R. 227.7202-1 through 227.7202-4 (June 1995), all U.S. Government End Users acquire Covered Software with only those rights set forth herein. This U.S. Government Rights clause is in lieu of, and supersedes, any other FAR, DFAR, or other clause or provision that addresses Government rights in computer

software under this License.

9. MISCELLANEOUS.

This License represents the complete agreement concerning subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable. This License shall be governed by the law of the jurisdiction specified in a notice contained within the Original Software (except to the extent applicable law, if any, provides otherwise), excluding such jurisdiction's conflict-of-law provisions. Any litigation relating to this License shall be subject to the jurisdiction of the courts located in the jurisdiction and venue specified in a notice contained within the Original Software, with the losing party responsible for costs, including, without limitation, court costs and reasonable attorneys' fees and expenses. The application of the United Nations Convention on Contracts for the International Sale of
Goods is expressly excluded. Any law or
regulation which provides that the language of a contract shall be construed against the drafter shall not apply to this License. You agree that You alone are responsible for compliance with the United States export administration regulations (and the export control laws and regulation of any other countries) when You use, distribute or otherwise make available any Covered Software.

10. RESPONSIBILITY FOR CLAIMS.

As between Initial Developer and the Contributors, each party is responsible for claims and damages arising, directly or indirectly, out of its utilization of rights under this License and You agree to work with Initial Developer and Contributors to distribute such responsibility on an equitable basis. Nothing herein is intended or shall be deemed to constitute any admission of liability.

NOTICE PURSUANT TO SECTION
9 OF THE COMMON DEVELOPMENT AND DISTRIBUTION
LICENSE (CDDL)

The code released under the CDDL shall be governed by the laws of the State of California (excluding conflict-of-law provisions). Any litigation relating to this License shall be subject to the jurisdiction of the Federal Courts of the Northern District of California and the state courts of the State of California, with venue lying in Santa Clara County, California.

The GNU General Public License (GPL) Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor
Boston, MA 02110-1335
USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.
This General Public
License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute
copies of such a program, whether gratis
or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free

software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making
the program
proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this
License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy

and distribute
such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under
the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs,
unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works.

These actions are
prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License,
they do not
excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software
distribution system, which is implemented
by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in

certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM

(INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

One line to give the program's name and a brief idea of what it does.
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1335 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'. This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the

appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.

signature of Ty Coon, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

#

Certain source files distributed by Oracle America, Inc. and/or its affiliates are subject to the following clarification and special exception to the GPLv2, based on the GNU Project exception for its Classpath libraries, known as the GNU Classpath Exception, but only where Oracle has expressly included in the particular source file's header the words "Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the LICENSE file that accompanied this code."

You should also note that Oracle includes multiple, independent programs in this software package. Some of those programs are provided under licenses deemed incompatible with the GPLv2 by the Free Software Foundation and
others. For example, the package includes programs
licensed under the Apache License, Version 2.0. Such programs are licensed to you under their original licenses.

Oracle facilitates your further distribution of this package by adding the Classpath Exception to the necessary parts of its GPLv2 code, which permits you to use that code in combination with other independent modules not licensed under the GPLv2. However, note that this would not permit you to commingle code under an incompatible license with Oracle's GPLv2 licensed code by, for example, cutting and pasting such code into a file also containing Oracle's GPLv2 licensed code and then

distributing the result. Additionally, if you were to remove the Classpath Exception from any of the files to which it applies and distribute the result, you would likely be required to license some or all of the other code in that distribution under the GPLv2 as well, and since the GPLv2 is incompatible with the license terms of some items included
 in the distribution by Oracle, removing the Classpath Exception could therefore effectively compromise your ability to further distribute the package.

Proceed with caution and we recommend that you obtain the advice of a lawyer skilled in open source matters before removing the Classpath Exception or making modifications to this package which may subsequently be redistributed and/or involve the use of third party software.

CLASSPATH EXCEPTION
Linking this library statically or dynamically with other modules is making a combined work based on this library. Thus, the terms and conditions of the GNU General Public License version 2 cover the whole combination.

As a special exception, the copyright holders of this library give you permission to link this library with independent modules to produce an executable, regardless of the license terms of these independent modules, and to copy and distribute the resulting executable under terms of your choice, provided that you also meet,
 for each linked
independent module, the terms and conditions of the license of that module. An independent module is a module which is not derived from or based on this library. If you modify this library, you may extend this exception to your version of the library, but you are not obligated to do so. If you do not wish to do so, delete this exception statement from your version.

1.1493 which-typed-array 1.1.15

1.1493.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell

copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1494 safe-array-concat 1.1.2

1.1494.1 Available under license :

MIT
MIT License

Copyright (c) 2023 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1495 caniuse-lite 1.0.30001597

1.1495.1 Available under license :

Attribution 4.0 International

==========

Creative Commons Corporation ("Creative Commons") is not a law firm and
does not provide legal services or legal advice. Distribution of
Creative Commons public licenses does not create a lawyer-client or
other relationship. Creative Commons makes its licenses and related
information available on an "as-is" basis. Creative Commons gives no
warranties regarding its licenses, any material licensed under their
terms and conditions, or any related information. Creative Commons
disclaims all liability for damages resulting from their use to the
fullest extent possible.

Using Creative Commons Public Licenses

Creative Commons public licenses provide a standard set of terms and
conditions that creators and other rights holders may use to share
original works of authorship and other material subject to copyright
and certain other rights specified in the public license below. The
following considerations
 are for informational purposes only, are not
exhaustive, and do not form part of our licenses.

   Considerations for licensors: Our public licenses are
   intended for use by those authorized to give the public
   permission to use material in ways otherwise restricted by
   copyright and certain other rights. Our licenses are
   irrevocable. Licensors should read and understand the terms
   and conditions of the license they choose before applying it.
   Licensors should also secure all rights necessary before
   applying our licenses so that the public can reuse the
   material as expected. Licensors should clearly mark any
   material not subject to the license. This includes other CC-
   licensed material, or material used under an exception or
   limitation to copyright. More considerations for licensors:
 wiki.creativecommons.org/Considerations_for_licensors

   Considerations for the public: By using one of our public
   licenses, a licensor
 grants the public permission to use the
   licensed material under specified terms and conditions. If
   the licensor's permission is not necessary for any reason--for
   example, because of any applicable exception or limitation to
   copyright--then that use is not regulated by the license. Our
   licenses grant only permissions under copyright and certain
   other rights that a licensor has authority to grant. Use of

the licensed material may still be restricted for other reasons, including because others have copyright or other rights in the material. A licensor may make special requests, such as asking that all changes be marked or described. Although not required by our licenses, you are encouraged to respect those requests where reasonable. More_considerations for the public:
wiki.creativecommons.org/Considerations_for_licensees

==========

Creative Commons Attribution
4.0 International Public License

By exercising the Licensed Rights (defined below), You accept and agree to be bound by the terms and conditions of this Creative Commons Attribution 4.0 International Public License ("Public License"). To the extent this Public License may be interpreted as a contract, You are granted the Licensed Rights in consideration of Your acceptance of these terms and conditions, and the Licensor grants You such rights in consideration of benefits the Licensor receives from making the Licensed Material available under these terms and conditions.

Section 1 -- Definitions.

a. Adapted Material means material subject to Copyright and Similar Rights that is derived from or based upon the Licensed Material and in which the Licensed Material is translated, altered, arranged, transformed, or otherwise modified in a manner requiring permission under the Copyright and Similar Rights held by the Licensor. For purposes of this Public License, where the Licensed Material is a musical work, performance, or sound recording, Adapted Material is always produced where the Licensed Material is synched in timed relation with a moving image.

b. Adapter's License means the license You apply to Your Copyright and Similar Rights in Your contributions to Adapted Material in accordance with the terms and conditions of this Public License.

c. Copyright and Similar Rights means copyright and/or similar rights closely related to copyright including, without limitation, performance, broadcast, sound recording, and Sui Generis Database Rights, without regard to how the rights are labeled or categorized. For purposes of this Public License, the rights specified in Section 2(b)(1)-(2) are not Copyright and Similar Rights.

d. Effective Technological Measures means those measures that, in the absence of proper authority, may not be circumvented under laws fulfilling obligations
under Article 11 of the WIPO Copyright
Treaty adopted on December 20, 1996, and/or similar international agreements.

e. Exceptions and Limitations means fair use, fair dealing, and/or any other exception or limitation to Copyright and Similar Rights that applies to Your use of the Licensed Material.

f. Licensed Material means the artistic or literary work, database, or other material to which the Licensor applied this Public License.

g. Licensed Rights means the rights granted to You subject to the terms and conditions of this Public License, which are limited to all Copyright and Similar Rights that apply to Your use of the Licensed Material and that the Licensor has authority to license.

h. Licensor means the individual(s) or entity(ies) granting rights under this Public License.

i. Share means to provide material to the public by any means or process that requires permission under the Licensed Rights, such as reproduction, public display, public performance, distribution, dissemination, communication, or importation, and to make material available to the public including in ways that members of the public may access the material from a place and at a time individually chosen by them.

j. Sui Generis Database Rights means rights other than copyright resulting from Directive 96/9/EC of the European Parliament and of the Council of 11 March 1996 on the legal protection of databases, as amended and/or succeeded, as well as other essentially equivalent rights anywhere in the world.

k. You means the individual or entity exercising the Licensed Rights under this Public License. Your has a corresponding meaning.

Section 2 -- Scope.

a. License grant.

1. Subject to the terms and conditions of this Public License, the Licensor hereby grants You a worldwide, royalty-free,

non-sublicensable, non-exclusive, irrevocable license to exercise the Licensed Rights in the Licensed Material to:

a. reproduce and Share the Licensed Material, in whole or in part; and

b. produce, reproduce, and Share Adapted Material.

2. Exceptions and Limitations. For the avoidance of doubt, where Exceptions and Limitations apply to Your use, this Public License does not apply, and You do not need to comply with its terms and conditions.

3. Term. The term of this Public License is specified in Section 6(a).

4. Media and formats; technical modifications allowed. The Licensor authorizes You to exercise the Licensed Rights in all media and formats whether now known or hereafter created, and to make technical modifications necessary to do so. The Licensor waives and/or agrees not to assert any right or authority to forbid You from making technical modifications necessary to exercise the Licensed Rights, including technical modifications necessary to circumvent Effective Technological Measures. For purposes of this Public License, simply making modifications authorized by this Section 2(a)(4) never produces Adapted Material.

5. Downstream recipients.

a. Offer from the Licensor -- Licensed Material. Every recipient of the Licensed Material automatically receives an offer from the Licensor to exercise the Licensed Rights under the terms and conditions of this Public License.

b. No downstream restrictions. You may not offer or impose any additional or different terms or conditions on, or apply any Effective Technological Measures to, the Licensed Material if doing so restricts exercise of the Licensed Rights by any recipient of the Licensed Material.

6. No endorsement. Nothing in this Public License constitutes or may be construed as permission to assert or imply that You are, or that Your use of the Licensed Material is, connected

with, or sponsored, endorsed, or granted official status by, the Licensor or others designated to receive attribution as provided in Section 3(a)(1)(A)(i).

b. Other rights.

1. Moral rights, such as the right of integrity, are not licensed under this Public License, nor are publicity, privacy, and/or other similar personality rights; however, to the extent possible, the Licensor waives and/or agrees not to assert any such rights held by the Licensor to the limited extent necessary to allow You to exercise the Licensed Rights, but not otherwise.

2. Patent and trademark rights are not licensed under this Public License.

3. To the extent possible, the Licensor waives any right to collect royalties from You for the exercise of the Licensed Rights, whether directly or through a collecting society under any voluntary or waivable statutory or compulsory licensing scheme. In all other cases the Licensor expressly reserves any right to collect such royalties.

Section 3 -- License Conditions.

Your exercise of the Licensed Rights is expressly made subject to the following conditions.

a. Attribution.

1. If You Share the Licensed Material (including in modified form), You must:

a. retain the following if it is supplied by the Licensor with the Licensed Material:

i. identification of the creator(s) of the Licensed Material and any others designated to receive attribution, in any reasonable manner requested by the Licensor (including by pseudonym if

designated);

ii. a copyright notice;

iii. a notice that refers to this Public License;

iv. a notice that refers to the disclaimer of warranties;

v. a URI or hyperlink to the Licensed Material to the extent reasonably practicable;

b. indicate if You modified the Licensed Material and retain an indication of any previous modifications; and

c. indicate the Licensed Material is licensed under this Public License, and include the text of, or the URI or hyperlink to, this Public License.

2. You may satisfy the conditions in Section 3(a)(1) in any reasonable manner based on the medium, means, and context in which You Share the Licensed Material. For example, it may be reasonable to satisfy the conditions by providing a URI or hyperlink to a resource that includes the required information.

3. If requested by the Licensor, You must remove any of the information required by Section 3(a)(1)(A) to the extent reasonably practicable.

4. If You Share Adapted Material You produce, the Adapter's License You apply must not prevent recipients of the Adapted Material from complying with this Public License.

Section 4 -- Sui Generis Database Rights.

Where the Licensed Rights include Sui Generis Database Rights that apply to Your use of the Licensed Material:

a. for the avoidance of doubt, Section 2(a)(1) grants You the right to extract, reuse, reproduce, and Share all or a substantial portion of the contents of the database;

b. if You include all or a substantial portion of the database contents in a database in which You have Sui Generis Database Rights, then the database in which You have Sui Generis Database Rights (but not its individual contents) is Adapted Material; and

c. You must comply with the conditions in Section 3(a) if You Share

all or a substantial portion of the contents of the database.

For the avoidance of doubt, this Section 4 supplements and does not replace Your obligations under this Public License where the Licensed Rights include other Copyright and Similar Rights.

Section 5 -- Disclaimer of Warranties and Limitation of Liability.

a. UNLESS OTHERWISE SEPARATELY UNDERTAKEN BY THE LICENSOR, TO THE EXTENT POSSIBLE, THE LICENSOR OFFERS THE LICENSED MATERIAL AS-IS AND AS-AVAILABLE, AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE LICENSED MATERIAL, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHER. THIS INCLUDES, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE OR ABSENCE OF ERRORS, WHETHER OR NOT KNOWN OR DISCOVERABLE.
WHERE DISCLAIMERS OF WARRANTIES ARE NOT ALLOWED IN FULL OR IN PART, THIS DISCLAIMER MAY NOT APPLY TO YOU.

b. TO THE EXTENT POSSIBLE, IN NO EVENT WILL THE LICENSOR BE LIABLE TO YOU ON ANY LEGAL THEORY (INCLUDING, WITHOUT LIMITATION, NEGLIGENCE) OR OTHERWISE FOR ANY DIRECT, SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL, PUNITIVE, EXEMPLARY, OR OTHER LOSSES, COSTS, EXPENSES, OR DAMAGES ARISING OUT OF THIS PUBLIC LICENSE OR USE OF THE LICENSED MATERIAL, EVEN IF THE LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH LOSSES, COSTS, EXPENSES, OR DAMAGES. WHERE A LIMITATION OF LIABILITY IS NOT ALLOWED IN FULL OR IN PART, THIS LIMITATION MAY NOT APPLY TO YOU.

c. The disclaimer of warranties and limitation of liability provided above shall be interpreted in a manner that, to the extent possible, most closely approximates an absolute disclaimer and waiver of all liability.

Section 6 -- Term and Termination.

a. This Public License applies for the term of the Copyright and Similar Rights licensed here. However, if You fail to comply with this Public License, then Your rights under this Public License terminate automatically.

b. Where Your right to use the Licensed Material has terminated under Section 6(a), it reinstates:

1. automatically as of the date the violation is cured, provided it is cured within 30 days of Your discovery of the violation; or

2. upon express reinstatement by the Licensor.

For the avoidance of doubt, this Section 6(b) does not affect any right the Licensor may have to seek remedies for Your violations of this Public License.

c. For the avoidance of doubt, the Licensor may also offer the Licensed Material under separate terms or conditions or stop distributing the Licensed Material at any time; however, doing so will not terminate this Public License.

d. Sections 1, 5, 6, 7, and 8 survive termination of this Public License.

Section 7 -- Other Terms and Conditions.

a. The Licensor shall not be bound by any additional or different terms or conditions communicated by You unless expressly agreed.

b. Any arrangements, understandings, or agreements regarding the Licensed Material not stated herein are separate from and independent of the terms and conditions of this Public License.

Section 8 -- Interpretation.

a. For the avoidance of doubt, this Public License does not, and shall not be interpreted to, reduce, limit, restrict, or impose conditions on any use of the Licensed Material that could lawfully be made without permission under this Public License.

b. To the extent possible, if any provision of this Public License is deemed unenforceable, it shall be automatically reformed to the minimum extent necessary to make it enforceable. If the provision cannot be reformed, it shall be severed from this Public License without affecting the enforceability of the remaining terms and conditions.

c. No term or condition of this Public License will be waived and no failure to comply consented to unless expressly agreed to by the Licensor.

d. Nothing in this Public License constitutes or may be interpreted
as a limitation upon, or waiver of, any privileges and immunities
that apply to the Licensor or You, including from the legal
processes of any jurisdiction or authority.

==========

Creative Commons is not a party to its public
licenses. Notwithstanding, Creative Commons may elect to apply one of
its public licenses to material it publishes and in those instances
will be considered the Licensor. The text of the Creative Commons
public licenses is dedicated to the public domain under the CC0 Public
Domain Dedication. Except for the limited purpose of indicating that
material is shared under a Creative
Commons public license or as
otherwise permitted by the Creative Commons policies published at
creativecommons.org/policies, Creative Commons does not authorize the
use of the trademark "Creative Commons" or any other trademark or logo
of Creative Commons without its prior written consent including,
without limitation, in connection with any unauthorized modifications
to any of its public licenses or any other arrangements,
understandings, or agreements concerning use of licensed material. For
the avoidance of doubt, this paragraph does not form part of the
public licenses.

Creative Commons may be contacted at creativecommons.org.
3c075d9b0b6885603d3fbfe15ebd325a

1.1496 jsonassert 1.5.0

1.1496.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/ValueMatcher.java
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/ValueMatcherException.java
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/comparator/JSONComparator.java
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/RegularExpressionValueMatcher.java
*
/jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/JSONParser.java
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/comparator/DefaultComparator.java
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/comparator/JSONCompareUtil.java
* /jsonassert-1-5-0-sources-5-jar/org/json/JSONString.java
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/JSONCompareMode.java
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/comparator/ArraySizeComparator.java
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/JSONCompareResult.java
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/LocationAwareValueMatcher.java
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/JSONAssert.java
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/Customization.java
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/JSONCompare.java
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/comparator/AbstractComparator.java
*
/jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/FieldComparisonFailure.java
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/ArrayValueMatcher.java
* /jsonassert-1-5-0-sources-5-jar/org/skyscreamer/jsonassert/comparator/CustomComparator.java

1.1497 follow-redirects 1.15.6

1.1497.1 Available under license :

Copyright 2014present Olivier Lalonde <olalonde@gmail.com>, James Talmage <james@talmage.io>, Ruben Verborgh

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF
CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

MIT

1.1498 sass 1.72.0

1.1498.1 Available under license :

Dart Sass license:

Copyright (c) 2016, Google Inc.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Dart SDK license:

Copyright 2012, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google LLC nor the names of its
  contributors may be used to endorse or promote products derived

from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

_fe_analyzer_shared license:

Copyright 2019, the Dart project authors.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions
of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google LLC nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE

OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

analyzer, protobuf and protoc_plugin license:

Copyright 2013, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name
of Google LLC nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

archive
license:

The MIT License

Copyright (c) 2013-2021 Brendan Duncan.
All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

---

args, csslib and logging license:

Copyright 2013, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google LLC nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS
SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT

(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

async, cli_util, collection, mime, source_map_stack_trace, stream_channel and typed_data license:

Copyright 2015, the Dart project authors.

Redistribution and
use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google LLC nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

boolean_selector, meta and shelf_packages_handler license:

Copyright 2016, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are

met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this
list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google LLC nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY
 WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

charcode license:

Copyright 2014, the Dart project authors. All rights reserved.
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google Inc. nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT

HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

checked_yaml license:

Copyright 2019, the Dart project authors. All rights reserved.
Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

cli_pkg license:

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes

of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the

Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright,
patent, trademark, and
attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify
the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding

the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or
redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct, indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof,
You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format.
We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

---

cli_repl license:

Copyright (c) 2018, Jennifer Thakar.
All rights reserved.

Redistribution and use in source
and binary forms, with or without
modification, are permitted provided that the following conditions are met:
* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
* Neither the name of the project nor the names of its contributors may be
used to endorse or promote products derived from this software without
specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR

ANY DIRECT, INDIRECT,
INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

convert, crypto, shelf_static and vm_service license:

Copyright 2015, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and
the following
disclaimer in the documentation and/or other materials provided
with the distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

coverage, dart_style, dartdoc, glob, http, http_parser, matcher, path, pool,
pub_semver, source_span, string_scanner, test and watcher license:

Copyright 2014, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
    notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
    copyright notice, this list of conditions and the following
    disclaimer in the documentation and/or other materials provided
    with the distribution.
  * Neither the name of Google LLC nor the names of its
    contributors may be used to endorse or promote products derived
    from this software
without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

dart_mappable and type_plus license:

MIT License

Copyright (c) 2021 Kilian Schulte

Permission is hereby granted,
 free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all

copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

---

ffi
and package_config license:

Copyright 2019, the Dart project authors.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google LLC nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

file license:

Copyright 2017, the Dart project authors. All rights reserved.
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
    notice,
this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
    copyright notice, this list of conditions and the following
    disclaimer in the documentation and/or other materials provided
    with the distribution.
  * Neither the name of Google Inc. nor the names of its
    contributors may be used to endorse or promote products derived
    from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
 HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

fixnum, http_multi_server, oauth2, shelf, shelf_web_socket, source_maps and
stack_trace license:

Copyright 2014, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
    notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
    copyright notice, this list of conditions and the following
    disclaimer in the documentation and/or other materials provided
    with the distribution.
  * Neither the name of Google

LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

frontend_server_client
license:

Copyright 2020, the Dart project authors.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google LLC nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT

(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

grinder and webkit_inspection_protocol license:

Copyright 2013, Google Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY,
OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

html license:

Copyright (c) 2006-2012 The Authors

Contributors:
James Graham - jg307@cam.ac.uk
Anne van Kesteren - annevankesteren@gmail.com

Lachlan Hunt - lachlan.hunt@lachy.id.au
Matt McDonald - kanashii@kanashii.ca
Sam Ruby - rubys@intertwingly.net
Ian Hickson (Google) - ian@hixie.ch
Thomas Broyer - t.broyer@ltgt.net
Jacques Distler - distler@golem.ph.utexas.edu
Henri Sivonen - hsivonen@iki.fi
Adam Barth - abarth@webkit.org
Eric Seidel - eric@webkit.org
The Mozilla Foundation (contributions from Henri Sivonen since 2008)
David Flanagan (Mozilla) - dflanagan@mozilla.com
Google LLC (contributed the Dart port) - misc@dartlang.org

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files
(the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

---

io, stream_transform
and term_glyph license:

Copyright 2017, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google LLC nor the names of its

contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

js license:

Copyright 2012, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce
the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING

NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

json_annotation license:

Copyright 2017, the Dart project authors. All rights reserved.
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google Inc. nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS
SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

lints license:

Copyright 2021, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted
provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google LLC nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
 (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

markdown license:

Copyright 2012, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided

 with the distribution.
* Neither the name of Google LLC nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR

A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

native_stack_traces
license:

Copyright 2020, the Dart project authors.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
* Neither the name of Google LLC nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

native_synchronization license:

Copyright 2023, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
    notice, this list of conditions
and the following disclaimer.
  * Redistributions in binary form must reproduce the above
    copyright notice, this list of conditions and the following
    disclaimer in the documentation and/or other materials provided
    with the distribution.
  * Neither the name of Google LLC nor the names of its
    contributors may be used to endorse or promote products derived
    from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
 ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

node_interop license:

Copyright (c) 2017, Anatoly Pulyaevskiy.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:
  * Redistributions of source code must retain the above copyright
    notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above copyright
    notice, this list of conditions and the following disclaimer in the
    documentation and/or other materials provided with the distribution.
  * Neither the name of the <organization> nor the
    names of its contributors may be used to endorse or promote

products
derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL <COPYRIGHT HOLDER> BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

node_preamble license:

The MIT License (MIT)

Copyright (c) 2015 Michael Bullington

Permission
is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
IN THE
SOFTWARE.

===

Copyright 2012, the Dart project authors. All rights reserved.
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are

met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google Inc. nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

petitparser and xml license:

The MIT License

Copyright (c) 2006-2023 Lukas Renggli.
All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge,
publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

---

pointycastle license:

Copyright (c) 2000 - 2019 The Legion of the Bouncy Castle Inc. (https://www.bouncycastle.org)

Permission is hereby granted, free
of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

---

pub_api_client
license:

MIT License

Copyright (c) 2020 Leo Farias

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

---

pubspec license:

Copyright (c) 2015, Anders Holmgren.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:
* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
notice, this list of conditions and the following disclaimer in the
documentation and/or other materials provided with the distribution.
* Neither the name of the <organization> nor the
names of its contributors may be used to endorse or promote products
derived from this software without specific
prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL <COPYRIGHT HOLDER> BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

pubspec_parse license:

Copyright 2018, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification,
are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.
* Neither the name of Google LLC nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL
DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

quiver and retry license:

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by

the copyright owner that is granting
the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code,
generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative
Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the

Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2.
Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work
to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of

the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining

the
appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

---

test_api and test_core license:

Copyright 2018, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google LLC nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS
BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

test_descriptor and web_socket_channel license:

Copyright 2016, the Dart project authors.

Redistribution and use in source and binary forms, with or without

modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright
notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google LLC nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE)
 ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

test_process license:

Copyright 2017, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
  copyright notice, this list of conditions and the following
  disclaimer in the documentation and/or other materials provided
  with the distribution.
* Neither the name of Google LLC nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT
HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

uri license:

Copyright 2013, the Dart project authors. All rights reserved.
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following
conditions are
met:
* Redistributions of source code must retain the above copyright
notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above
copyright notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.
* Neither the name of Google Inc. nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.
THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

web license:

Copyright 2023, the Dart project authors.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:
  * Redistributions of source code must retain the above copyright
    notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
    copyright notice, this list of conditions and the following
    disclaimer in the documentation and/or other materials provided
    with the distribution.
  * Neither the
 name of Google LLC nor the names of its
    contributors may be used to endorse or promote products derived
    from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE
OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---

yaml
 license:

Copyright (c) 2014, the Dart project authors.
Copyright (c) 2006, Kirill Simonov.

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN
ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1499 @babel/helper-define-polyfill-provider 0.6.1

1.1499.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Nicol Ribaudo and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1500 babel-plugin-polyfill-corejs2 0.4.10

1.1500.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Nicol Ribaudo and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1501 itu 1.8.0

1.1501.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*-
* #%L
* Internet Time Utility
* %%
* Copyright (C) 2017 - 2024 Morten Haraldsen (ethlo)
* %%
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and

* limitations under the License.
* #L%
*/
/**
* CREDIT: Public domain math for converting between epoch and date-time
*/

Found in path(s):
* /itu-1-8-0-sources-1-jar/com/ethlo/time/internal/DateTimeMath.java
No license file was found, but licenses were detected in source scan.

/*-
* #%L
* Internet Time Utility
* %%
* Copyright (C) 2017 - 2024 Morten Haraldsen (ethlo)
* %%
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
* #L%
*/

Found in path(s):
* /itu-1-8-0-sources-1-jar/com/ethlo/time/DateTimeFormatException.java
No license file was found, but licenses were detected in source scan.

/*-
* #%L
* Internet Time Utility
* %%
* Copyright (C) 2017 Morten Haraldsen (ethlo)
* %%
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
* #L%
*/

Found in path(s):
* /itu-1-8-0-sources-1-jar/com/ethlo/time/ITU.java
* /itu-1-8-0-sources-1-jar/com/ethlo/time/TimezoneOffset.java
* /itu-1-8-0-sources-1-jar/com/ethlo/time/internal/DefaultLeapSecondHandler.java
* /itu-1-8-0-sources-1-jar/com/ethlo/time/internal/Rfc3339.java
*
 /itu-1-8-0-sources-1-jar/com/ethlo/time/LeapSecondException.java
* /itu-1-8-0-sources-1-jar/com/ethlo/time/internal/AbstractRfc3339.java
* /itu-1-8-0-sources-1-jar/com/ethlo/time/internal/EthloITU.java
* /itu-1-8-0-sources-1-jar/com/ethlo/time/internal/Rfc3339Parser.java
* /itu-1-8-0-sources-1-jar/com/ethlo/time/TemporalConsumer.java
* /itu-1-8-0-sources-1-jar/com/ethlo/time/DateTime.java
* /itu-1-8-0-sources-1-jar/com/ethlo/time/internal/Rfc3339Formatter.java
* /itu-1-8-0-sources-1-jar/com/ethlo/time/TemporalType.java
* /itu-1-8-0-sources-1-jar/com/ethlo/time/TemporalHandler.java
* /itu-1-8-0-sources-1-jar/com/ethlo/time/internal/LeapSecondHandler.java
* /itu-1-8-0-sources-1-jar/com/ethlo/time/internal/LimitedCharArrayIntegerUtil.java
* /itu-1-8-0-sources-1-jar/com/ethlo/time/Field.java
* /itu-1-8-0-sources-1-jar/com/ethlo/time/internal/W3cDateTimeUtil.java
No license file was found, but licenses were detected in source scan.

<!--
#%L
Internet Time Utility
%%
Copyright (C) 2017 Morten Haraldsen (ethlo)
%%
Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

    http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
#L%
-->

Found in path(s):
* /itu-1-8-0-sources-1-jar/META-INF/maven/com.ethlo.time/itu/pom.xml

1.1502 jakarta activation api 1.2.1

1.1502.1 Available under license :

Copyright (c) 2018 Oracle and/or its affiliates. All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met:

- Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.

- Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

- Neither the name of the Eclipse Foundation, Inc. nor the names of its
  contributors may be used to endorse or promote products derived
  from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS
IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO,
THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR
CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO,
PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR
PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
Notices for Eclipse Project for JAF

This content is produced and maintained by the Eclipse Project for JAF project.

* Project home: https://projects.eclipse.org/projects/ee4j.jaf

Copyright

All content is the property of the respective authors or their employers. For
more information regarding authorship of content, please consult the listed

source code repository logs.

Declared Project Licenses

This program and the accompanying materials are made available under the terms
of the Eclipse Distribution License v. 1.0,
which is available at http://www.eclipse.org/org/documents/edl-v10.php.

SPDX-License-Identifier: BSD-3-Clause

Source Code

The project maintains the following source code repositories:

* https://github.com/eclipse-ee4j/jaf

Third-party Content

This project leverages the following third party content.

JUnit (4.12)

* License: Eclipse Public License

1.1503 json-schema-validator 1.3.3

1.1503.1 Available under license :

JSON Schema Validator
Copyright (c) 2016 and onwards Network New Technologies Inc.

// --
// NOTICE file corresponding to the section 4d of The Apache License,
// Version 2.0, in this case for
// --

Apache Commons Validator
Copyright 2001-2023 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of

the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or

agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

MIT

Copyright (c) 2012 Julian Berman

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1504 resilience4j-timelimiter 1.7.1

1.1504.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
*
* Copyright 2019 authors
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
*
*/

Found in path(s):
* /resilience4j-timelimiter-1-7-1-sources-3-
jar/io/github/resilience4j/timelimiter/event/TimeLimiterOnSuccessEvent.java
* /resilience4j-timelimiter-1-7-1-sources-3-
jar/io/github/resilience4j/timelimiter/internal/TimeLimiterEventProcessor.java
* /resilience4j-timelimiter-1-7-1-sources-3-
jar/io/github/resilience4j/timelimiter/event/TimeLimiterOnTimeoutEvent.java
*
 /resilience4j-timelimiter-1-7-1-sources-3-
jar/io/github/resilience4j/timelimiter/event/AbstractTimeLimiterEvent.java
* /resilience4j-timelimiter-1-7-1-sources-3-jar/io/github/resilience4j/timelimiter/event/TimeLimiterEvent.java
* /resilience4j-timelimiter-1-7-1-sources-3-
jar/io/github/resilience4j/timelimiter/event/TimeLimiterOnErrorEvent.java
* /resilience4j-timelimiter-1-7-1-sources-3-jar/io/github/resilience4j/timelimiter/TimeLimiterRegistry.java
* /resilience4j-timelimiter-1-7-1-sources-3-jar/io/github/resilience4j/timelimiter/event/package-info.java
* /resilience4j-timelimiter-1-7-1-sources-3-
jar/io/github/resilience4j/timelimiter/internal/InMemoryTimeLimiterRegistry.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 Ingyu Hwang
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /resilience4j-timelimiter-1-7-1-sources-3-jar/io/github/resilience4j/timelimiter/utils/MetricNames.java
* /resilience4j-timelimiter-1-7-1-sources-3-jar/io/github/resilience4j/timelimiter/utils/package-info.java

1.1505 resilience4j-bulkhead 1.7.1

1.1505.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
*
*  Copyright 2016 Robert Winkler, Lucas Lech
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*        http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*
*
*/
```

Found in path(s):
* /resilience4j-bulkhead-1-7-1-sources-2-jar/io/github/resilience4j/bulkhead/BulkheadConfig.java
No license file was found, but licenses were detected in source scan.

```
/*
*
*  Copyright 2016 Robert Winkler, Lucas Lech, Mahmoud Romeh
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*        http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*
*
*/
```

Found in path(s):
* /resilience4j-bulkhead-1-7-1-sources-2-jar/io/github/resilience4j/bulkhead/ThreadPoolBulkheadConfig.java
No license file was found, but licenses were detected in source scan.

```
/*
*
*  Copyright 2017 Robert Winkler, Lucas Lech
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*        http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*
*
*/
```

Found in path(s):
* /resilience4j-bulkhead-1-7-1-sources-2-jar/io/github/resilience4j/bulkhead/BulkheadFullException.java
* /resilience4j-bulkhead-1-7-1-sources-2-jar/io/github/resilience4j/bulkhead/event/AbstractBulkheadEvent.java
* /resilience4j-bulkhead-1-7-1-sources-2-
jar/io/github/resilience4j/bulkhead/internal/InMemoryBulkheadRegistry.java
*
 /resilience4j-bulkhead-1-7-1-sources-2-jar/io/github/resilience4j/bulkhead/internal/SemaphoreBulkhead.java
* /resilience4j-bulkhead-1-7-1-sources-2-
jar/io/github/resilience4j/bulkhead/event/BulkheadOnCallRejectedEvent.java
* /resilience4j-bulkhead-1-7-1-sources-2-
jar/io/github/resilience4j/bulkhead/event/BulkheadOnCallPermittedEvent.java
* /resilience4j-bulkhead-1-7-1-sources-2-jar/io/github/resilience4j/bulkhead/BulkheadRegistry.java
* /resilience4j-bulkhead-1-7-1-sources-2-jar/io/github/resilience4j/bulkhead/event/BulkheadEvent.java
No license file was found, but licenses were detected in source scan.

```
/*
*
*  Copyright 2017 Robert Winkler, Lucas Lech, Mahmoud Romeh
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*        http://www.apache.org/licenses/LICENSE-2.0
```

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
*
*/

Found in path(s):
* /resilience4j-bulkhead-1-7-1-sources-2-jar/io/github/resilience4j/bulkhead/ThreadPoolBulkheadRegistry.java
* /resilience4j-bulkhead-1-7-1-sources-2-
jar/io/github/resilience4j/bulkhead/internal/InMemoryThreadPoolBulkheadRegistry.java
No license file was found, but licenses were detected in source scan.

/*
*
* Copyright 2017: Robert Winkler, Lucas Lech
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
*
*/

Found in path(s):
* /resilience4j-bulkhead-1-7-1-sources-2-jar/io/github/resilience4j/bulkhead/ThreadPoolBulkhead.java
* /resilience4j-bulkhead-1-7-1-sources-2-jar/io/github/resilience4j/bulkhead/Bulkhead.java
No license file was found, but licenses were detected in source scan.

/*
*
* Copyright 2019 Robert Winkler, Mahmoud Romeh
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*

* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
*
*/

Found in path(s):
* /resilience4j-bulkhead-1-7-1-sources-2-jar/io/github/resilience4j/bulkhead/internal/FixedThreadPoolBulkhead.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 Jan Sykora
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /resilience4j-bulkhead-1-7-1-sources-2-
jar/io/github/resilience4j/bulkhead/event/BulkheadOnCallFinishedEvent.java
No license file was found, but licenses were detected in source scan.

/*
*
* Copyright 2018: Clint Checketts
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,

* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
*
*/

Found in path(s):
* /resilience4j-bulkhead-1-7-1-sources-2-jar/io/github/resilience4j/bulkhead/internal/package-info.java
* /resilience4j-bulkhead-1-7-1-sources-2-jar/io/github/resilience4j/bulkhead/utils/package-info.java
* /resilience4j-bulkhead-1-7-1-sources-2-jar/io/github/resilience4j/bulkhead/event/package-info.java
*
 /resilience4j-bulkhead-1-7-1-sources-2-jar/io/github/resilience4j/bulkhead/package-info.java

1.1506 resilience4j-retry 1.7.1

1.1506.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
*
* Copyright 2018: Clint Checketts
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
*
*/

Found in path(s):
* /resilience4j-retry-1-7-1-sources-3-jar/io/github/resilience4j/retry/utils/package-info.java
* /resilience4j-retry-1-7-1-sources-3-jar/io/github/resilience4j/retry/package-info.java
* /resilience4j-retry-1-7-1-sources-3-jar/io/github/resilience4j/retry/event/package-info.java
* /resilience4j-retry-1-7-1-sources-3-jar/io/github/resilience4j/retry/internal/package-info.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 Dan Maas

*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /resilience4j-retry-1-7-1-sources-3-jar/io/github/resilience4j/retry/RetryRegistry.java
* /resilience4j-retry-1-7-1-sources-3-jar/io/github/resilience4j/retry/internal/InMemoryRetryRegistry.java
No license file was found, but licenses were detected in source scan.

/*
*
* Copyright 2016 Robert Winkler
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
*
*/

Found in path(s):
* /resilience4j-retry-1-7-1-sources-3-jar/io/github/resilience4j/retry/RetryConfig.java
* /resilience4j-retry-1-7-1-sources-3-jar/io/github/resilience4j/retry/event/RetryOnErrorEvent.java
* /resilience4j-retry-1-7-1-sources-3-jar/io/github/resilience4j/retry/event/AbstractRetryEvent.java
*
 /resilience4j-retry-1-7-1-sources-3-jar/io/github/resilience4j/retry/event/RetryOnIgnoredErrorEvent.java
* /resilience4j-retry-1-7-1-sources-3-jar/io/github/resilience4j/retry/Retry.java
* /resilience4j-retry-1-7-1-sources-3-jar/io/github/resilience4j/retry/event/RetryEvent.java
* /resilience4j-retry-1-7-1-sources-3-jar/io/github/resilience4j/retry/event/RetryOnSuccessEvent.java
* /resilience4j-retry-1-7-1-sources-3-jar/io/github/resilience4j/retry/internal/RetryImpl.java

No license file was found, but licenses were detected in source scan.

```
/*
*
*  Copyright 2019 Mahmoud Romeh
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*        http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*
*
*/
```

Found in path(s):
* /resilience4j-retry-1-7-1-sources-3-jar/io/github/resilience4j/retry/MaxRetriesExceeded.java

1.1507 squiggly-filter-jackson 1.3.18

1.1507.1 Available under license :

Copyright (c) 2016, Ryan Bohn
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER

OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1508 resilience4j-framework-common 1.7.1

1.1508.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 Dan Maas, Mahmoud Romeh
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/bulkhead/configuration/ThreadPoolBulkheadConfigurationProperties.java
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/retry/configuration/RetryConfigurationProperties.java
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/ratelimiter/configuration/RateLimiterConfigurationProperties.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2020 Vijay Ram
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/circuitbreaker/monitoring/endpoint/CircuitBreakerHystrixStreamEventsDTO.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright Mahmoud Romeh
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/CompositeCustomizer.java
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/CommonProperties.java
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/CustomizerWithName.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2020 Mahmoud Romeh
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.

*/

Found in path(s):
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/circuitbreaker/monitoring/endpoint/UpdateState.java
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/circuitbreaker/monitoring/endpoint/CircuitBreakerUpdateStateResponse.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 Bohdan Storozhuk
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/ratelimiter/monitoring/endpoint/RateLimiterEndpointResponse.java
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/ratelimiter/monitoring/endpoint/RateLimiterEventsEndpointResponse.java
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/ratelimiter/monitoring/endpoint/RateLimiterEventDTO.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 lespinsideg
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.

*/

Found in path(s):
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/bulkhead/monitoring/endpoint/BulkheadEndpointResponse.java
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/bulkhead/monitoring/endpoint/BulkheadEventsEndpointResponse.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 Dan Maas,Mahmoud Romeh
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/circuitbreaker/configuration/CircuitBreakerConfigurationProperties.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 Mahmoud Romeh
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /resilience4j-framework-common-1-7-1-sources-1-

jar/io/github/resilience4j/common/retry/monitoring/endpoint/RetryEventDTOBuilder.java
* /resilience4j-framework-common-1-7-1-sources-1-
jar/io/github/resilience4j/common/retry/monitoring/endpoint/RetryEventDTO.java
* /resilience4j-framework-common-1-7-1-sources-1-
jar/io/github/resilience4j/common/retry/monitoring/endpoint/RetryEventDTOFactory.java
*
/resilience4j-framework-common-1-7-1-sources-1-
jar/io/github/resilience4j/common/retry/monitoring/endpoint/RetryEventsEndpointResponse.java
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/utils/ConfigUtils.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2020 Ingyu Hwang
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /resilience4j-framework-common-1-7-1-sources-1-
jar/io/github/resilience4j/common/timelimiter/configuration/TimeLimiterConfigCustomizer.java
* /resilience4j-framework-common-1-7-1-sources-1-
jar/io/github/resilience4j/common/timelimiter/monitoring/endpoint/TimeLimiterEndpointResponse.java
* /resilience4j-framework-common-1-7-1-sources-1-
jar/io/github/resilience4j/common/timelimiter/configuration/TimeLimiterConfigurationProperties.java
*
/resilience4j-framework-common-1-7-1-sources-1-
jar/io/github/resilience4j/common/timelimiter/monitoring/endpoint/TimeLimiterEventDTO.java
* /resilience4j-framework-common-1-7-1-sources-1-
jar/io/github/resilience4j/common/timelimiter/monitoring/endpoint/TimeLimiterEventsEndpointResponse.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 Robert Winkler
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*

* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/circuitbreaker/monitoring/endpoint/CircuitBreakerEventDTO.java
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/bulkhead/monitoring/endpoint/BulkheadEventDTOFactory.java
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/circuitbreaker/monitoring/endpoint/CircuitBreakerEventDTOFactory.java
*
 /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/circuitbreaker/monitoring/endpoint/CircuitBreakerEventDTOBuilder.java
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/bulkhead/monitoring/endpoint/BulkheadEventDTO.java
No license file was found, but licenses were detected in source scan.

/*
*
* Copyright 2020 krnsaurabh
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*
*
*/

Found in path(s):
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/scheduled/threadpool/configuration/ContextAwareScheduledThreadPoolConfigurationProperties.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2019 Dan Maas , Mahmoud Romeh
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*       http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/bulkhead/configuration/BulkheadConfigurationProperties.java
No license file was found, but licenses were detected in source scan.

```
/*
*
*  Copyright 2018: Clint Checketts
*
*  Licensed under the Apache License, Version 2.0 (the "License");
*  you may not use this file except in compliance with the License.
*  You may obtain a copy of the License at
*
*       http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*
*
*/
```

Found in path(s):
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/ratelimiter/monitoring/endpoint/package-info.java
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/retry/monitoring/endpoint/package-info.java
* /resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/bulkhead/monitoring/endpoint/package-info.java
*

/resilience4j-framework-common-1-7-1-sources-1-jar/io/github/resilience4j/common/circuitbreaker/monitoring/endpoint/package-info.java

1.1509 aspectjrt 1.9.6

1.1509.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*******************************************************************************
* Copyright (c) 2006 Contributors.
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://eclipse.org/legal/epl-v10.html
*
* Contributors:
* variant of Aspects in the aspectj5rt project - this one isn't Java5   - Andy Clement
*******************************************************************************/
```

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/Aspects14.java
No license file was found, but licenses were detected in source scan.

```
/* *******************************************************************
* Copyright (c) 2005 Contributors.
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://eclipse.org/legal/epl-v10.html
*
* Contributors:
*     Wes Isberg       initial implementation
*   Andy Clement       fleshed out to match SuppressWarnings
* ******************************************************************/
```

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/SuppressAjWarnings.java
No license file was found, but licenses were detected in source scan.

```
/*******************************************************************************
* Copyright (c) 2013 Contributors.
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
```

* http://eclipse.org/legal/epl-v10.html
*
* Contributors:
* initial implementation Andy Clement
**********/

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/control/CodeGenerationHint.java
No license file was found, but licenses were detected in source scan.

/**********
* Copyright (c) 2005 Contributors.
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://eclipse.org/legal/epl-v10.html
*
* Contributors:
* initial implementation Adrian Colyer
**********/

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/DeclareParents.java
No license file was found, but licenses were detected in source scan.

/* **********
* Copyright (c) 1999-2001 Xerox Corporation,
* 2002-2018 Palo Alto Research Center, Incorporated (PARC), Contributors
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://www.eclipse.org/legal/epl-v10.html
*
* Contributors:
* Xerox/PARC initial implementation
* Alex Vasseur new factory methods for variants of JP
* Abraham Nevado new factory methods for collapsed SJPs
* Andy Clement new factory methods that rely on LDC <class>
* **********/

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/reflect/Factory.java
No license file was found, but licenses were detected in source scan.

/* **********
* Copyright (c) 1999-2001 Xerox Corporation,

```
*             2002 Palo Alto Research Center, Incorporated (PARC),
*             2006 Contributors.
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://www.eclipse.org/legal/epl-v10.html
*
* Contributors:
*     Xerox/PARC     initial implementation
* ******************************************************************/

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/InitializerSignature.java
No license file was found, but licenses were detected in source scan.

/*******************************************************************************
* Copyright (c) 2006 IBM Corporation and others.
* All rights reserved. This program and the accompanying materials
* are made available under the terms of the Eclipse Public License v1.0
* which accompanies this distribution, and is available at
* http://www.eclipse.org/legal/epl-v10.html
*
* Contributors:
*     Andy Clement - initial implementation
*******************************************************************************/

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/reflect/UnlockSignatureImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/reflect/LockSignatureImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/UnlockSignature.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/LockSignature.java
No license file was found, but licenses were detected in source scan.

/*******************************************************************************
* Copyright (c) 2005 Contributors.
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://eclipse.org/legal/epl-v10.html
*
* Contributors:
* initial implementation            Alexandre Vasseur
* generic signature update          Adrian Colyer
*******************************************************************************/

Found in path(s):
```

* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/Aspects.java
No license file was found, but licenses were detected in source scan.

/* ***
* Copyright (c) 2004 IBM Corporation
*
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://www.eclipse.org/legal/epl-v10.html
*
* Contributors:
* Andy Clement initial implementation
* ***/

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/internal/cflowstack/ThreadStackFactory.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/internal/CFlowCounter.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/internal/cflowstack/ThreadStack.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/internal/cflowstack/ThreadStackFactoryImpl11.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/internal/cflowstack/ThreadStackFactoryImpl.java
*
 /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/internal/cflowstack/ThreadCounter.java
No license file was found, but licenses were detected in source scan.

/***
* Copyright (c) 2005 Contributors.
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://eclipse.org/legal/epl-v10.html
*
* Contributors:
* Alexandre Vasseur initial implementation
***/

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/DeclareAnnotation.java
No license file was found, but licenses were detected in source scan.

/* ***
* Copyright (c) 1999-2001 Xerox Corporation,
* 2002 Palo Alto Research Center, Incorporated (PARC).
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0

* which accompanies this distribution and is available at
* http://www.eclipse.org/legal/epl-v10.html
*
* Contributors:
*   Xerox/PARC   initial implementation
* **/

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/Signature.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/CFlow.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/reflect/CatchClauseSignatureImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/internal/Conversions.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/FieldSignature.java
*
 /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/internal/CFlowPlusState.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/reflect/JoinPointImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/reflect/CodeSignatureImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/internal/PerObjectMap.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/AdviceSignature.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/ConstructorSignature.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/CatchClauseSignature.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/CodeSignature.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/reflect/MemberSignatureImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/reflect/MethodSignatureImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/reflect/InitializerSignatureImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/NoAspectBoundException.java
*
 /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/reflect/AdviceSignatureImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/reflect/SourceLocationImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/reflect/ConstructorSignatureImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/MemberSignature.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/SourceLocation.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/reflect/SignatureImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/JoinPoint.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/MethodSignature.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/reflect/FieldSignatureImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/reflect/StringMaker.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/internal/CFlowStack.java
No license file was found, but licenses were detected in source scan.

/* **
* Copyright (c) 2005 Contributors.
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://eclipse.org/legal/epl-v10.html
*

* Contributors:
*   Wes Isberg   initial implementation
* **/

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/internal/lang/PlaceHolder.java
No license file was found, but licenses were detected in source scan.

/* **
* Copyright (c) 2004 IBM Corporation
*
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://www.eclipse.org/legal/epl-v10.html
*
* Contributors:
*   Andy Clement   initial implementation
*   Copied from bits of original CFlowStack
* **/

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/internal/cflowstack/ThreadCounterImpl11.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/internal/cflowstack/ThreadStackImpl11.java
No license file was found, but licenses were detected in source scan.

/***
* Copyright (c) 2005 Contributors.
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://eclipse.org/legal/epl-v10.html
*
* Contributors:
* initial implementation   Alexandre Vasseur
***/

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/Aspect.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/DeclarePrecedence.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/Around.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/Pointcut.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/AfterThrowing.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/ProceedingJoinPoint.java
*

/aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/After.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/AfterReturning.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/Before.java
No license file was found, but licenses were detected in source scan.

/* **
* Copyright (c) 2014 Contributors.
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://eclipse.org/legal/epl-v10.html
* **/

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/RequiredTypes.java
No license file was found, but licenses were detected in source scan.

/* **
* Copyright (c) 1999-2001 Xerox Corporation,
*   2002 Palo Alto Research Center, Incorporated (PARC).
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://www.eclipse.org/legal/epl-v10.html
*
* Contributors:
*   Xerox/PARC   initial implementation
*   Alex Vasseur   wired up for @AJ proceeding
*   Andy Clement 23-06-06 added extras for @AJ
* **/

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/runtime/internal/AroundClosure.java
No license file was found, but licenses were detected in source scan.

/***
* Copyright (c) 2009 Contributors.
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://eclipse.org/legal/epl-v10.html
*
* Contributors:
* initial implementation   Andy Clement
***/

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/DeclareMixin.java
No license file was found, but licenses were detected in source scan.

```
/*******************************************************************************
* Copyright (c) 2005 Contributors.
* All rights reserved. This program and the accompanying materials
* are made available under the terms of the Eclipse Public License v1.0
* which accompanies this distribution, and is available at
* http://www.eclipse.org/legal/epl-v10.html
*
* Contributors:
*   Adrian Colyer        initial implementation
*******************************************************************************/
```

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/AdviceName.java
No license file was found, but licenses were detected in source scan.

```
/* ********************************************************************
* Copyright (c) 2005 Contributors.
* All rights reserved.
* This program and the accompanying materials are made available
* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://eclipse.org/legal/epl-v10.html
*
* Contributors:
*   Adrian Colyer   Initial implementation
* ********************************************************************/
```

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/DeclareSoft.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/InterTypeDeclarationImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/annotation/ajcDeclareParents.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/PerClause.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/DeclarePrecedence.java
*
 /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/InterTypeMethodDeclarationImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/TypePattern.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/PointcutImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/DeclareWarning.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/DeclareSoftImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/AjType.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/InterTypeFieldDeclaration.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/PointcutBasedPerClauseImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/PointcutExpressionImpl.java

* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/PointcutExpression.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/annotation/ajcDeclareSoft.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/InterTypeConstructorDeclaration.java
*
 /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/SignaturePatternImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/annotation/ajcDeclarePrecedence.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/annotation/ajcDeclareAnnotation.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/InterTypeFieldDeclarationImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/PerClauseImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/InterTypeConstructorDeclarationImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/annotation/ajcPrivileged.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/DeclareAnnotation.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/PerClauseKind.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/Advice.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/TypePatternBasedPerClauseImpl.java
*
 /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/annotation/ajcDeclareEoW.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/DeclareErrorOrWarningImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/DeclareAnnotationImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/Pointcut.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/NoSuchAdviceException.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/TypePatternImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/DeclareParentsImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/AjTypeImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/DeclareErrorOrWarning.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/TypePatternBasedPerClause.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/NoSuchPointcutException.java
*
 /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/AdviceImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/AjTypeSystem.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/InterTypeDeclaration.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/PointcutBasedPerClause.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/StringToType.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/SignaturePattern.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/InterTypeMethodDeclaration.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/DeclareParents.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/reflect/DeclarePrecedenceImpl.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/annotation/DeclareError.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/reflect/AdviceKind.java
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/internal/lang/annotation/ajcITD.java
No license file was found, but licenses were detected in source scan.

/* **
* Copyright (c) 1999-2001 Xerox Corporation,
*   2002 Palo Alto Research Center, Incorporated (PARC),
*   2004 Contributors.
* All rights reserved.
* This program and the accompanying materials are made available

* under the terms of the Eclipse Public License v1.0
* which accompanies this distribution and is available at
* http://www.eclipse.org/legal/epl-v10.html
*
* Contributors:
*   Xerox/PARC   initial implementation
* **/

Found in path(s):
* /aspectjrt-1-9-6-sources-1-jar/org/aspectj/lang/SoftException.java

1.1510 electron-to-chromium 1.4.708

1.1510.1 Available under license :

Copyright 2018 Kilian Valkhof

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1511 bcpg-jdk15on 1.50

1.1511.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*
*/

Found in path(s):
* /bcpg-jdk15on-1-50-sources-3-jar/org/bouncycastle/apache/bzip2/CBZip2InputStream.java
* /bcpg-jdk15on-1-50-sources-3-jar/org/bouncycastle/apache/bzip2/CRC.java
*
 /bcpg-jdk15on-1-50-sources-3-jar/org/bouncycastle/apache/bzip2/BZip2Constants.java
* /bcpg-jdk15on-1-50-sources-3-jar/org/bouncycastle/apache/bzip2/CBZip2OutputStream.java

1.1512 bcprov-jdk15on 1.50

1.1512.1 Available under license :

No license file was found, but licenses were detected in source scan.

/**
* Poly1305 message authentication code, designed by D. J. Bernstein.
* <p>
* Poly1305 computes a 128-bit (16 bytes) authenticator, using a 128 bit nonce and a 256 bit key
* consisting of a 128 bit key applied to an underlying cipher, and a 128 bit key (with 106
* effective key bits) used in the authenticator.
* <p>
* The polynomial calculation in this implementation is adapted from the public domain <a
* href="https://github.com/floodyberry/poly1305-donna">poly1305-donna-unrolled C implementation
* by Andrew M (@floodyberry).
* @see Poly1305KeyGenerator
*/

Found in path(s):
* /bcprov-jdk15on-1-50-sources-1-jar/org/bouncycastle/crypto/macs/Poly1305.java
No license file was found, but licenses were detected in source scan.

/*
* Licensed to the Apache Software Foundation (ASF) under one or more
* contributor license agreements. See the NOTICE file distributed with
* this work for additional information regarding copyright ownership.
* The ASF licenses this file to You under the Apache License, Version 2.0
* (the "License"); you may not use this file except in compliance with
* the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

* See the License for the specific language governing permissions and
* limitations under the License.
*
*/

Found in path(s):
* /bcprov-jdk15on-1-50-sources-1-jar/org/bouncycastle/apache/bzip2/CRC.java
* /bcprov-jdk15on-1-50-sources-1-jar/org/bouncycastle/apache/bzip2/CBZip2OutputStream.java
*
 /bcprov-jdk15on-1-50-sources-1-jar/org/bouncycastle/apache/bzip2/BZip2Constants.java
* /bcprov-jdk15on-1-50-sources-1-jar/org/bouncycastle/apache/bzip2/CBZip2InputStream.java
No license file was found, but licenses were detected in source scan.

/**
* The Bouncy Castle License
*
* Copyright (c) 2000-2013 The Legion Of The Bouncy Castle (http://www.bouncycastle.org)
* <p>
* Permission is hereby granted, free of charge, to any person obtaining a copy of this software
* and associated documentation files (the "Software"), to deal in the Software without restriction,
* including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense,
* and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so,
* subject to the following conditions:
* <p>
* The above copyright notice and this permission notice shall be included in all copies or substantial
* portions of the Software.
* <p>
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED,
* INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR
* PURPOSE AND NONINFRINGEMENT.
 IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
* LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
* OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER
* DEALINGS IN THE SOFTWARE.
*/

Found in path(s):
* /bcprov-jdk15on-1-50-sources-1-jar/org/bouncycastle/LICENSE.java
No license file was found, but licenses were detected in source scan.

// now keep space is free to use

Found in path(s):
* /bcprov-jdk15on-1-50-sources-1-jar/org/bouncycastle/pqc/crypto/gmss/GMSSPrivateKeyParameters.java

1.1513 collections 3.2.2

1.1513.1 Available under license :

GNU GENERAL PUBLIC LICENSE
Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
License is intended to guarantee your freedom to share and change free
software--to make sure the software is free for all its users. This
General Public License applies to most of the Free Software
Foundation's software and to any other program whose authors commit to
using it. (Some other Free Software Foundation software is covered by
the GNU Library General Public License instead.) You can apply it to
your programs, too.

When we speak of free software, we are referring to freedom, not
price. Our General Public Licenses are
designed to make sure that you
have the freedom to distribute copies of free software (and charge for
this service if you wish), that you receive source code or can get it
if you want it, that you can change the software or use pieces of it
in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid
anyone to deny you these rights or to ask you to surrender the rights.
These restrictions translate to certain responsibilities for you if you
distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether
gratis or for a fee, you must give the recipients all the rights that
you have. You must make sure that they, too, receive or can get the
source code. And you must show them these terms so they know their
rights.

We protect your rights with two steps: (1) copyright the software, and

(2) offer you this license which gives you legal permission to copy, distribute
and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION
---

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what
the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty;

and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program

with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License.

However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that

system; it is up to the author/donor
to decide if he or she is willing
to distribute software through any other system and a licensee cannot
impose that choice.

This section is intended to make thoroughly clear what is believed to
be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in
certain countries either by patents or by copyrighted interfaces, the
original copyright holder who places the Program under this License
may add an explicit geographical distribution limitation excluding
those countries, so that distribution is permitted only in or among
countries not thus excluded. In such case, this License incorporates
the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions
of the General Public License from time to time. Such new versions will
be similar in spirit to the present version, but may differ in detail to
address new problems or concerns.

Each version is given a distinguishing
version number. If the Program
specifies a version number of this License which applies to it and "any
later version", you have the option of following the terms and conditions
either of that version or of any later version published by the Free
Software Foundation. If the Program does not specify a version number of
this License, you may choose any version ever published by the Free Software
Foundation.

10. If you wish to incorporate parts of the Program into other free
programs whose distribution conditions are different, write to the author
to ask for permission. For software which is copyrighted by the Free
Software Foundation, write to the Free Software Foundation; we sometimes
make exceptions for this. Our decision will be guided by the two goals
of preserving the free status of all derivatives of our free software and
of promoting the sharing and reuse of software generally.

NO WARRANTY
---

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS
NO WARRANTY
FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN
OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES
PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED
OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS

TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES
OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

1.1514 cas-client-core 3.2.1

1.1514.1 Available under license :

No license file was found, but licenses were detected in source scan.

/**
* Licensed to Jasig under one or more contributor license
* agreements. See the NOTICE file distributed with this work
* for additional information regarding copyright ownership.
* Jasig licenses this file to you under the Apache License,
* Version 2.0 (the "License"); you may not use this file
* except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing,
* software distributed under the License is distributed on
* an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY
* KIND, either express or implied. See the License for the
* specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/validation/AbstractTicketValidationFilter.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/authentication/AuthenticationFilter.java
*

/cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/util/XmlUtils.java
* /cas-client-core-3-2-1-sources-2-
jar/org/jasig/cas/client/validation/InvalidProxyChainTicketValidationException.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/validation/Cas20ProxyTicketValidator.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/session/SingleSignOutHandler.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/authentication/SimplePrincipal.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/util/AssertionThreadLocalFilter.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/session/SessionMappingStorage.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/util/ErrorRedirectFilter.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/validation/Cas10TicketValidationFilter.java
* /cas-client-core-3-2-1-sources-2-
jar/org/jasig/cas/client/validation/Cas20ProxyReceivingTicketValidationFilter.java
*
/cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/authentication/DefaultGatewayResolverImpl.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/validation/TicketValidator.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/validation/ProxyListEditor.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/validation/AssertionImpl.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/validation/Saml11TicketValidationFilter.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/jaas/AssertionPrincipal.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/authentication/Saml11AuthenticationFilter.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/session/HashMapBackedSessionMappingStorage.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/proxy/CleanUpTimerTask.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/ssl/AnyHostnameVerifier.java
*
/cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/validation/AbstractUrlBasedTicketValidator.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/session/SingleSignOutFilter.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/util/AssertionHolder.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/authentication/AttributePrincipalImpl.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/jaas/ServiceAndTicketCallbackHandler.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/proxy/ProxyGrantingTicketStorage.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/validation/Cas10TicketValidator.java
* /cas-client-core-3-2-1-sources-2-
jar/org/jasig/cas/client/validation/AbstractCasProtocolUrlBasedTicketValidator.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/ssl/RegexHostnameVerifier.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/util/AbstractConfigurationFilter.java
*
/cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/ssl/WhitelistHostnameVerifier.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/util/CommonUtils.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/util/HttpServletRequestWrapperFilter.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/validation/Assertion.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/validation/TicketValidationException.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/authentication/AttributePrincipal.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/validation/Cas20ServiceTicketValidator.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/authentication/GatewayResolver.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/util/ReflectUtils.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/authentication/SimpleGroup.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/jaas/CasLoginModule.java
*

/cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/proxy/ProxyGrantingTicketStorageImpl.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/session/SingleSignOutHttpSessionListener.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/util/DelegatingFilter.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/jaas/TicketCredential.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/proxy/Cas20ProxyRetriever.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/util/AbstractCasFilter.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/proxy/ProxyRetriever.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/validation/ProxyList.java
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/validation/Saml11TicketValidator.java
No license file was found, but licenses were detected in source scan.

<!--

Licensed to Jasig under one or more contributor license
agreements. See the NOTICE file distributed with this work
for additional information regarding copyright ownership.
Jasig licenses this file to you under the Apache License,
Version 2.0 (the "License"); you may not use this file
except in compliance with the License. You may obtain a
copy of the License at:

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing,
software distributed under the License is distributed on
an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY
KIND, either express or implied. See the License for the
specific language governing permissions and limitations
under the License.

-->

Found in path(s):
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/util/package.html
* /cas-client-core-3-2-1-sources-2-jar/org/jasig/cas/client/proxy/package.html

1.1515 google-http-client-xml 1.20.0

1.1515.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2010 Google Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*

* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /google-http-client-xml-1-20-0-sources-5-jar/com/google/api/client/http/xml/XmlHttpContent.java
* /google-http-client-xml-1-20-0-sources-5-jar/com/google/api/client/http/xml/atom/AtomFeedParser.java
* /google-http-client-xml-1-20-0-sources-5-jar/com/google/api/client/xml/XmlObjectParser.java
* /google-http-client-xml-1-20-0-sources-5-jar/com/google/api/client/xml/atom/AbstractAtomFeedParser.java
*
 /google-http-client-xml-1-20-0-sources-5-jar/com/google/api/client/xml/atom/Atom.java
* /google-http-client-xml-1-20-0-sources-5-jar/com/google/api/client/xml/package-info.java
* /google-http-client-xml-1-20-0-sources-5-jar/com/google/api/client/xml/XmlNamespaceDictionary.java
* /google-http-client-xml-1-20-0-sources-5-jar/com/google/api/client/xml/atom/package-info.java
* /google-http-client-xml-1-20-0-sources-5-jar/com/google/api/client/xml/Xml.java
* /google-http-client-xml-1-20-0-sources-5-jar/com/google/api/client/http/xml/AbstractXmlHttpContent.java
* /google-http-client-xml-1-20-0-sources-5-jar/com/google/api/client/xml/GenericXml.java
* /google-http-client-xml-1-20-0-sources-5-jar/com/google/api/client/http/xml/package-info.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2011 Google Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except
* in compliance with the License. You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /google-http-client-xml-1-20-0-sources-5-jar/com/google/api/client/http/xml/atom/AtomContent.java
* /google-http-client-xml-1-20-0-sources-5-jar/com/google/api/client/http/xml/atom/package-info.java

1.1516 easymock 3.1

1.1516.1 Available under license :

// --
// NOTICE file corresponding to the section 4d of The Apache License,
// Version 2.0, in this case for EasyMock
// --

EasyMock
Copyright 2001-2011 OFFIS, Tammo Freese, Henri Tremblay

This product includes/uses software(s) developed by 'an unknown organization'
- Code Generation Library (http://cglib.sourceforge.net/)

This product includes/uses software(s) developed by 'Joe Walnes, Henri Tremblay, Leonardo Mesquita'
- Objenesis (http://objenesis.googlecode.com/svn/docs/index.html)

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,

and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable

by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only

on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1517 hazelcast-client 3.8.9

1.1517.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/connection/AddressTranslator.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/util/AddressHelper.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/listener/ClientNonSmartListenerService.java
*
/hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/connection/AddressProvider.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/NearCachedClientMapProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientListProxy.java
* /hazelcast-client-3-8-9-sources-1-
jar/com/hazelcast/client/impl/querycache/subscriber/ClientSubscriberContext.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientScheduledFutureProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/ClientPartitionServiceImpl.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/IExecutorDelegatingFuture.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/config/ClientConfig.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/ClientExtension.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/cache/impl/ClientCacheProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/cache/impl/AbstractClientInternalCacheProxy.java
*
/hazelcast-client-3-8-9-sources-1-
jar/com/hazelcast/client/map/impl/nearcache/invalidation/ClientMapMetaDataFetcher.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/package-info.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientTopicProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientAtomicLongProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/DefaultClientExtension.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/ClientPartitionService.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/connection/nio/ClientSocketReaderInitializer.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/DefaultAddressProvider.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/config/ProxyFactoryConfig.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/connection/nio/ClientConnectionManagerImpl.java
*
/hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientMapProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/querycache/subscriber/package-info.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/ClientTransactionManagerService.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/connection/nio/ClientConnection.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/HazelcastClientInstanceImpl.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientLockProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/ClientServiceNotFoundException.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/cache/impl/package-info.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/DefaultAddressTranslator.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/txn/TransactionProxy.java
*

/hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/ClientLockReferenceIdGenerator.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/HazelcastClientProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/ClientProxyFactory.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/HazelcastClientNotActiveException.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/txn/TransactionContextProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/cache/impl/AbstractClientCacheProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/ClientClusterServiceImpl.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientIdGeneratorProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/ClientProxyDescriptorProvider.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/PartitionServiceProxy.java
*

/hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/package-info.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/txn/AbstractClientTxnCollectionProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/txn/ClientTxnSetProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/DefaultClientConnectionManagerFactory.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/util/RoundRobinLB.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/console/package-info.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/discovery/DiscoveryAddressProvider.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/listener/ClientEventRegistration.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/AwsAddressProvider.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/HazelcastClientManager.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/config/ClientXmlElements.java
*

/hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/ClientProxyDescriptor.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/txn/ClientTxnQueueProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/ClientInvocationFuture.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/txn/xa/package-info.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/ClientNonSmartInvocationServiceImpl.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/ClientExecutionServiceImpl.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/connection/nio/package-info.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/txn/ClientTxnProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/package-info.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/HazelcastClient.java
*

/hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/txn/ClientTxnMapProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientReplicatedMapProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/package-info.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/connection/ClientConnectionManager.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/ConnectionHeartbeatListener.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/config/ClientSecurityConfig.java
* /hazelcast-client-3-8-9-sources-1-
jar/com/hazelcast/client/impl/querycache/subscriber/ClientQueryCacheEventService.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/connection/package-info.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/cache/impl/HazelcastClientCacheManager.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientCardinalityEstimatorProxy.java
*

/hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/ClientProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/ClientExecutionService.java

* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/config/ClientAwsConfig.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/listener/ClientListenerServiceImpl.java
* /hazelcast-client-3-8-9-sources-1-
jar/com/hazelcast/client/impl/querycache/subscriber/ClientQueryCacheEndToEndConstructor.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/ClusterListenerSupport.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/querycache/subscriber/ClientInvokerWrapper.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/txn/ClientTxnMultiMapProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/CallIdSequence.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/cache/impl/ClientCacheProxyFactory.java
*
/hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/ClientTransactionManagerServiceImpl.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientExecutorServiceProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/HazelcastClientFactory.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/map/impl/ClientMapPartitionIterator.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/querycache/ClientQueryCacheContext.java
* /hazelcast-client-3-8-9-sources-1-
jar/com/hazelcast/client/cache/impl/nearcache/invalidation/ClientCacheMetaDataFetcher.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientMultiMapProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/ClientInvocationServiceSupport.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/cache/impl/ClientClusterWideIterator.java
* /hazelcast-client-3-8-9-sources-1-
jar/com/hazelcast/client/impl/querycache/subscriber/ClientQueryCacheConfigurator.java
*
/hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/txn/package-info.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/cache/impl/ClientCacheStatisticsImpl.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/ClientConnectionManagerFactory.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/properties/package-info.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/config/SocketOptions.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientQueueProxy.java
* /hazelcast-client-3-8-9-sources-1-
jar/com/hazelcast/client/impl/querycache/subscriber/ClientSubscriberContextSupport.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/console/ClientConsoleApp.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientConditionProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/txn/xa/XAResourceProxy.java
*
/hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/discovery/DiscoveryAddressTranslator.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientCountDownLatchProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/config/package-info.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/config/QueryCacheConfigBuilderHelper.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/ClientLoggingService.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/ClientSmartInvocationServiceImpl.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientSemaphoreProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/cache/impl/HazelcastClientCachingProvider.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/ClientInvocation.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/ClientMembershipListener.java
*
/hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/txn/xa/XATransactionProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/util/RandomLB.java

* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/ClientImpl.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/util/ClientDelegatingFuture.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/cache/impl/ClientCachePartitionIterator.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/ClientContext.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/connection/nio/ClientSocketWriterInitializer.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/txn/ClientTxnListProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/cache/impl/CallbackAwareClientDelegatingFuture.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/AwsAddressTranslator.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/querycache/package-info.java
*
 /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/cache/impl/OneShotExecutionCallback.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/config/ClientNetworkConfig.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/listener/ClientRegistrationKey.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/util/AbstractLoadBalancer.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/PartitionSpecificClientProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/LifecycleServiceImpl.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/ClientTransactionContext.java
* /hazelcast-client-3-8-9-sources-1-
jar/com/hazelcast/client/impl/querycache/subscriber/QueryCacheToListenerMapper.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/util/package-info.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientAtomicReferenceProxy.java
*
 /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/package-info.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/ClientICacheManager.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/listener/ClientSmartListenerService.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/ListenerMessageCodec.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/ClientOutOfMemoryHandler.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/ClientListenerService.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/cache/impl/ClientCacheHelper.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/EventHandler.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/cache/impl/AbstractClientCacheProxyBase.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/config/ClientReliableTopicConfig.java
*
 /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientScheduledExecutorProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientClusterProxy.java
* /hazelcast-client-3-8-9-sources-1-
jar/com/hazelcast/client/impl/querycache/subscriber/ClientQueryCacheScheduler.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/ProxyManager.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientSetProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/util/StaticLB.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/config/XmlClientConfigBuilder.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientReliableTopicProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/txn/xa/XATransactionContextProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/HazelcastClientManagedContext.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientDurableExecutorServiceProxy.java
*
 /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/ClientInvocationService.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/ClientClusterService.java

* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/impl/listener/LazyDistributedObjectEvent.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/config/XmlClientConfigLocator.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/ClientMessageDecoder.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientMapReduceProxy.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/spi/properties/ClientProperty.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/LoadBalancer.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/impl/querycache/subscriber/ListenerInfo.java
* /hazelcast-client-3-8-9-sources-1-jar/com/hazelcast/client/proxy/ClientRingbufferProxy.java
No license file was found, but licenses were detected in source scan.

<!--
~ Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
~
~ Licensed under the Apache License, Version 2.0 (the "License");
~ you may not use this file except in compliance with the License.
~ You may obtain a copy of the License at
~
~ http://www.apache.org/licenses/LICENSE-2.0
~
~ Unless required by applicable law or agreed to in writing, software
~ distributed under the License is distributed on an "AS IS" BASIS,
~ WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
~ See the License for the specific language governing permissions and
~ limitations under the License.
-->

Found in path(s):
* /hazelcast-client-3-8-9-sources-1-jar/hazelcast-client-config-3.6.xsd
* /hazelcast-client-3-8-9-sources-1-jar/hazelcast-client-config-3.8.xsd
* /hazelcast-client-3-8-9-sources-1-jar/hazelcast-client-config-3.4.xsd
* /hazelcast-client-3-8-9-sources-1-jar/hazelcast-client-config-3.7.xsd
*
/hazelcast-client-3-8-9-sources-1-jar/hazelcast-client-config-3.2.xsd
* /hazelcast-client-3-8-9-sources-1-jar/hazelcast-client-default.xml
* /hazelcast-client-3-8-9-sources-1-jar/hazelcast-client-full.xml
* /hazelcast-client-3-8-9-sources-1-jar/hazelcast-client-config-3.3.xsd
* /hazelcast-client-3-8-9-sources-1-jar/hazelcast-client-config-3.0.xsd
* /hazelcast-client-3-8-9-sources-1-jar/hazelcast-client-config-3.5.xsd
* /hazelcast-client-3-8-9-sources-1-jar/hazelcast-client-config-3.1.xsd

1.1518 hazelcast 3.8.9

1.1518.1 Available under license :

Apache-2.0

1.1519 icu4j 63.1

1.1519.1 Available under license :

COPYRIGHT AND PERMISSION NOTICE (ICU 58 and later)

Copyright 1991-2018 Unicode, Inc. All rights reserved.
Distributed under the Terms of Use in http://www.unicode.org/copyright.html.

Permission is hereby granted, free of charge, to any person obtaining
a copy of the Unicode data files and any associated documentation
(the "Data Files") or Unicode software and any associated documentation
(the "Software") to deal in the Data Files or Software
without restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, and/or sell copies of
the Data Files or Software, and to permit persons to whom the Data Files
or Software are furnished to do so, provided that either
(a) this copyright and permission notice appear with all copies
of the Data Files or Software, or
(b) this copyright and permission notice appear in associated
Documentation.

THE DATA FILES AND SOFTWARE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF
ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT
 NOT LIMITED TO THE
WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT OF THIRD PARTY RIGHTS.
IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS
NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL
DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE,
DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER
TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR
PERFORMANCE OF THE DATA FILES OR SOFTWARE.

Except as contained in this notice, the name of a copyright holder
shall not be used in advertising or otherwise to promote the sale,
use or other dealings in these Data Files or Software without prior
written authorization of the copyright holder.

Third-Party Software Licenses

This section contains third-party software notices and/or additional
terms for licensed third-party software components included within ICU
libraries.

1. ICU License - ICU 1.8.1 to ICU

57.1

COPYRIGHT AND PERMISSION NOTICE

Copyright (c) 1995-2016 International Business Machines Corporation and others
All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, and/or sell copies of the Software, and to permit persons
to whom the Software is furnished to do so, provided that the above
copyright notice(s) and this permission notice appear in all copies of
the Software and that both the above copyright notice(s) and this
permission notice appear in supporting documentation.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT
OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER
OR
HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY
SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER
RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF
CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN
CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Except as contained in this notice, the name of a copyright holder
shall not be used in advertising or otherwise to promote the sale, use
or other dealings in this Software without prior written authorization
of the copyright holder.

All trademarks and registered trademarks mentioned herein are the
property of their respective owners.

2. Chinese/Japanese Word Break Dictionary Data (cjdict.txt)

The Google Chrome software developed by Google is licensed under
the BSD license. Other software included in this distribution is
provided under other licenses, as set forth below.
#
The BSD License
http://opensource.org/licenses/bsd-license.php
Copyright (C) 2006-2008, Google Inc.
#
All rights reserved.
#

```
#  Redistribution and use in source and binary forms, with or without
# modification, are permitted provided that the following conditions are met:
#
#  Redistributions of source code must retain the above copyright notice,
# this list of conditions and the following disclaimer.
#  Redistributions in binary form must reproduce the above
# copyright notice, this list of conditions and the following
# disclaimer in the documentation and/or other materials provided with
# the distribution.
#  Neither the name of  Google Inc. nor the names of its
# contributors may be used to endorse or promote products derived from
# this software without specific prior written permission.
#
#
#  THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND
# CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES,
# INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
# MERCHANTABILITY AND FITNESS FOR A PARTICULAR
 PURPOSE ARE
# DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
# LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
# CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
# SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
# BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF
# LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
# NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS
# SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
#
#
#  The word list in cjdict.txt are generated by combining three word lists
# listed below with further processing for compound word breaking. The
# frequency is generated with an iterative training against Google web
# corpora.
#
#  * Libtabe (Chinese)
#    - https://sourceforge.net/project/?group_id=1519
#    - Its license terms and conditions are shown below.
#
#  * IPADIC (Japanese)
#    - http://chasen.aist-nara.ac.jp/chasen/distribution.html
 #    - Its license terms and conditions are shown below.
#
#  ---------COPYING.libtabe ---- BEGIN--------------------
#
#  /*
#   * Copyright (c) 1999 TaBE Project.
#   * Copyright (c) 1999 Pai-Hsiang Hsiao.
#   * All rights reserved.
```

```
#   *
#   * Redistribution and use in source and binary forms, with or without
#   * modification, are permitted provided that the following conditions
#   * are met:
#   *
#   * . Redistributions of source code must retain the above copyright
#   *   notice, this list of conditions and the following disclaimer.
#   * . Redistributions in binary form must reproduce the above copyright
#   *   notice, this list of conditions and the following disclaimer in
#   *   the documentation and/or other materials provided with the
#   *   distribution.
#   * . Neither the name of the TaBE Project nor the names of its
#   *   contributors may be used to endorse or promote products derived
#   *   from this software
 without specific prior written permission.
#   *
#   * THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
#   * "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
#   * LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
#   * FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
#   * REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
#   * INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
#   * (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
#   * SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
#   * HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
#   * STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
#   * ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
#   * OF THE POSSIBILITY OF SUCH DAMAGE.
#   */
#
#  /*
#   * Copyright (c) 1999 Computer Systems and Communication Lab,
#   *                    Institute
 of Information Science, Academia
#      *                    Sinica. All rights reserved.
#   *
#   * Redistribution and use in source and binary forms, with or without
#   * modification, are permitted provided that the following conditions
#   * are met:
#   *
#   * . Redistributions of source code must retain the above copyright
#   *   notice, this list of conditions and the following disclaimer.
#   * . Redistributions in binary form must reproduce the above copyright
#   *   notice, this list of conditions and the following disclaimer in
#   *   the documentation and/or other materials provided with the
#   *   distribution.
#   * . Neither the name of the Computer Systems and Communication Lab
#   *   nor the names of its contributors may be used to endorse or
```

```
#   *   promote products derived from this software without specific
#   *   prior written permission.
#   *
#   * THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
#   * "AS IS" AND
 ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
#   * LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
#   * FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
#   * REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT,
#   * INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
#   * (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
#   * SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
#   * HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
#   * STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
#   * ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
#   * OF THE POSSIBILITY OF SUCH DAMAGE.
#   */
#
#  Copyright 1996 Chih-Hao Tsai @ Beckman Institute,
#      University of Illinois
#  c-tsai4@uiuc.edu  http://casper.beckman.uiuc.edu/~c-tsai4
#
#  ---------------COPYING.libtabe-----END--------------------------------
#
#
#  ---------------COPYING.ipadic-----BEGIN-------------------------------
 #
#  Copyright 2000, 2001, 2002, 2003 Nara Institute of Science
#  and Technology.  All Rights Reserved.
#
#  Use, reproduction, and distribution of this software is permitted.
#  Any copy of this software, whether in its original form or modified,
#  must include both the above copyright notice and the following
#  paragraphs.
#
#  Nara Institute of Science and Technology (NAIST),
#  the copyright holders, disclaims all warranties with regard to this
#  software, including all implied warranties of merchantability and
#  fitness, in no event shall NAIST be liable for
#  any special, indirect or consequential damages or any damages
#  whatsoever resulting from loss of use, data or profits, whether in an
#  action of contract, negligence or other tortuous action, arising out
#  of or in connection with the use or performance of this software.
#
#  A large portion of the dictionary entries
#  originate from ICOT
 Free Software.  The following conditions for ICOT
#  Free Software applies to the current dictionary as well.
```

#
Each User may also freely distribute the Program, whether in its
original form or modified, to any third party or parties, PROVIDED
that the provisions of Section 3 ("NO WARRANTY") will ALWAYS appear
on, or be attached to, the Program, which is distributed substantially
in the same form as set out herein and that such intended
distribution, if actually made, will neither violate or otherwise
contravene any of the laws and regulations of the countries having
jurisdiction over the User or the intended distribution itself.
#
NO WARRANTY
#
The program was produced on an experimental basis in the course of the
research and development conducted during the project and is provided
to users as so produced on an experimental basis. Accordingly, the
program is provided without any warranty whatsoever, whether express,
implied,
statutory or otherwise. The term "warranty" used herein
includes, but is not limited to, any warranty of the quality,
performance, merchantability and fitness for a particular purpose of
the program and the nonexistence of any infringement or violation of
any right of any third party.
#
Each user of the program will agree and understand, and be deemed to
have agreed and understood, that there is no warranty whatsoever for
the program and, accordingly, the entire risk arising from or
otherwise connected with the program is assumed by the user.
#
Therefore, neither ICOT, the copyright holder, or any other
organization that participated in or was otherwise related to the
development of the program and their respective officials, directors,
officers and other employees shall be held liable for any and all
damages, including, without limitation, general, special, incidental
and consequential damages, arising out of or otherwise in
connection
with the use or inability to use the program or any product, material
or result produced or otherwise obtained by using the program,
regardless of whether they have been advised of, or otherwise had
knowledge of, the possibility of such damages at any time during the
project or thereafter. Each user will be deemed to have agreed to the
foregoing by his or her commencement of use of the program. The term
"use" as used herein includes, but is not limited to, the use,
modification, copying and distribution of the program and the
production of secondary products from the program.
#
In the case where the program, whether in its original form or
modified, was distributed or delivered to or received by a user from
any person, organization or entity other than ICOT, unless it makes or

```
#  grants independently of ICOT any specific warranty to the user in
#  writing, such person, organization or entity, will also be exempted
#  from
 and not be held liable to the user for any such damages as noted
#  above as far as the program is concerned.
#
#  ----------COPYING.ipadic-----END----------
```

3. Lao Word Break Dictionary Data (laodict.txt)

```
#  Copyright (c) 2013 International Business Machines Corporation
#  and others. All Rights Reserved.
#
# Project: http://code.google.com/p/lao-dictionary/
# Dictionary: http://lao-dictionary.googlecode.com/git/Lao-Dictionary.txt
# License: http://lao-dictionary.googlecode.com/git/Lao-Dictionary-LICENSE.txt
#             (copied below)
#
#  This file is derived from the above dictionary, with slight
#  modifications.
#  ----------------------------------------------------------------------
#  Copyright (C) 2013 Brian Eugene Wilson, Robert Martin Campbell.
#  All rights reserved.
#
#  Redistribution and use in source and binary forms, with or without
#  modification,
#  are permitted provided that the following conditions are met:
 #
#
# Redistributions of source code must retain the above copyright notice, this
#  list of conditions and the following disclaimer. Redistributions in
#  binary form must reproduce the above copyright notice, this list of
#  conditions and the following disclaimer in the documentation and/or
#  other materials provided with the distribution.
#
#
# THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
# "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
# LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS
# FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE
# COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT,
# INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
# (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR
# SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
# HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
# STRICT LIABILITY, OR
 TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
# ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
```

OF THE POSSIBILITY OF SUCH DAMAGE.
--

4. Burmese Word Break Dictionary Data (burmesedict.txt)

Copyright (c) 2014 International Business Machines Corporation
and others. All Rights Reserved.
#
This list is part of a project hosted at:
github.com/kanyawtech/myanmar-karen-word-lists
#
--
Copyright (c) 2013, LeRoy Benjamin Sharon
All rights reserved.
#
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions
are met: Redistributions of source code must retain the above
copyright notice, this list of conditions and the following
disclaimer. Redistributions in binary form must reproduce the
above copyright
 notice, this list of conditions and the following
disclaimer in the documentation and/or other materials provided
with the distribution.
#
Neither the name Myanmar Karen Word Lists, nor the names of its
contributors may be used to endorse or promote products derived
from this software without specific prior written permission.
#
THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND
CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES,
INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS
BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,
EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED
TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON
ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT
 LIABILITY, OR
TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF
THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF
SUCH DAMAGE.
--

5. Time Zone Database

 ICU uses the public domain data and code derived from Time Zone

Database for its time zone support. The ownership of the TZ database
is explained in BCP 175: Procedure for Maintaining the Time Zone
Database section 7.

7. Database Ownership
#
The TZ database itself is not an IETF Contribution or an IETF
document. Rather it is a pre-existing and regularly updated work
that is in the public domain, and is intended to remain in the
public domain. Therefore, BCPs 78 [RFC5378] and 79 [RFC3979] do
not apply to the TZ Database or contributions that individuals make
to it. Should any claims be made and substantiated against the TZ
Database, the organization that is providing
 the IANA
Considerations defined in this RFC, under the memorandum of
understanding with the IETF, currently ICANN, may act in accordance
with all competent court orders. No ownership claims will be made
by ICANN or the IETF Trust on the database or the code. Any person
making a contribution to the database or code waives all rights to
future claims in that contribution or in the TZ Database.

6. Google double-conversion

Copyright 2006-2011, the V8 project authors. All rights reserved.
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are
met:

  * Redistributions of source code must retain the above copyright
    notice, this list of conditions and the following disclaimer.
  * Redistributions in binary form must reproduce the above
    copyright notice, this list of conditions and the following
    disclaimer in the documentation and/or other materials
 provided
    with the distribution.
  * Neither the name of Google Inc. nor the names of its
    contributors may be used to endorse or promote products derived
    from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS
"AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT
LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR
A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT
OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL,
SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT
LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY
THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT

(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1520 javax-activation 1.2.0

1.1520.1 Available under license :

COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL) Version 1.1

1. Definitions.

1.1. "Contributor" means each individual or entity that creates or contributes to the creation of Modifications.

1.2. "Contributor Version" means the combination of the Original Software, prior Modifications used by a Contributor (if any), and the Modifications made by that particular Contributor.

1.3. "Covered Software" means (a) the Original Software, or (b) Modifications, or (c) the combination of files containing Original Software with files containing Modifications, in each case including portions thereof.

1.4. "Executable" means the Covered Software in any form other than Source Code.

1.5. "Initial Developer" means the individual or entity that first makes Original Software available under this License.

1.6. "Larger Work" means a work which combines Covered Software or portions thereof with code not governed by the terms of this License.

1.7. "License" means this document.

1.8. "Licensable" means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently acquired, any and all of the rights conveyed herein.

1.9. "Modifications" means the Source Code and Executable form of any of the following:

A. Any file that results from an addition to, deletion from or modification of the contents of a file containing Original Software or previous Modifications;

B. Any new file that contains any part of the Original Software or previous Modification; or

C. Any new file that is contributed or otherwise made available under the terms of this License.

1.10. "Original Software" means the Source Code and Executable form of computer software code that is originally released under this License.

1.11. "Patent Claims" means any patent claim(s), now owned or hereafter acquired, including without limitation, method, process, and apparatus claims, in any patent Licensable by grantor.

1.12. "Source Code" means (a) the common form of computer software code in which modifications are made and (b) associated documentation included in or with such code.

1.13. "You" (or "Your") means an individual or a legal entity exercising rights under, and complying with all of the terms of, this License. For legal entities, "You" includes any entity which controls, is controlled by, or is under common control with You. For purposes of this definition, "control" means (a) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (b) ownership of more than fifty percent (50%) of the outstanding shares or beneficial ownership of such entity.

2. License Grants.

2.1. The Initial Developer Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, the Initial Developer hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under intellectual property rights (other than patent or trademark) Licensable by Initial Developer, to use, reproduce, modify, display, perform, sublicense and distribute the Original Software (or portions thereof), with or without Modifications, and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using or selling of Original Software, to make, have made, use, practice, sell, and offer for sale, and/or otherwise dispose of the Original Software (or portions thereof).

(c) The licenses granted in Sections 2.1(a) and (b) are effective on the date Initial Developer first distributes or otherwise makes the

Original Software available to a third party under the terms of this License.

(d) Notwithstanding Section 2.1(b) above, no patent license is granted: (1) for code that You delete from the Original Software, or (2) for infringements caused by: (i) the modification of the Original Software, or (ii) the combination of the Original Software with other software or devices.

2.2. Contributor Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, each Contributor hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under intellectual property rights (other than patent or trademark) Licensable by Contributor to use, reproduce, modify, display, perform, sublicense and distribute the Modifications created by such Contributor (or portions thereof), either on an unmodified basis, with other Modifications, as Covered Software and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using, or selling of Modifications made by that Contributor either alone and/or in combination with its Contributor Version (or portions of such combination), to make, use, sell, offer for sale, have made, and/or otherwise dispose of: (1) Modifications made by that Contributor (or portions thereof); and (2) the combination of Modifications made by that Contributor with its Contributor Version (or portions of such combination).

(c) The licenses granted in Sections 2.2(a) and 2.2(b) are effective on the date Contributor first distributes or otherwise makes the Modifications available to a third party.

(d) Notwithstanding Section 2.2(b) above, no patent license is granted: (1) for any code that Contributor has deleted from the Contributor Version; (2) for infringements caused by: (i) third party modifications of Contributor Version, or (ii) the combination of Modifications made by that Contributor with other software (except as part of the Contributor Version) or other devices; or (3) under Patent Claims infringed by Covered Software in the absence of Modifications made by that Contributor.

3. Distribution Obligations.

3.1. Availability of Source Code.

Any Covered Software that You distribute or otherwise make available in Executable form must also be made available in Source Code form and that Source Code form must be distributed only under the terms of this License. You must include a copy of this License with every copy of the Source Code form of the Covered Software You distribute or otherwise make available. You must inform recipients of any such Covered Software in Executable form as to how they can obtain such Covered Software in Source Code form in a reasonable manner on or through a medium customarily used for software exchange.

3.2. Modifications.

The Modifications that You create or to which You contribute are governed by the terms of this License. You represent that You believe Your Modifications are Your original creation(s) and/or You have sufficient rights to grant the rights conveyed by this License.

3.3. Required Notices.

You must include a notice in each of Your Modifications that identifies You as the Contributor of the Modification. You may not remove or alter any copyright, patent or trademark notices contained within the Covered Software, or any notices of licensing or any descriptive text giving attribution to any Contributor or the Initial Developer.

3.4. Application of Additional Terms.

You may not offer or impose any terms on any Covered Software in Source Code form that alters or restricts the applicable version of this License or the recipients' rights hereunder. You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, you may do so only on Your own behalf, and not on behalf of the Initial Developer or any Contributor. You must make it absolutely clear that any such warranty, support, indemnity or liability obligation is offered by You alone, and You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of warranty, support, indemnity or liability terms You offer.

3.5. Distribution of Executable Versions.

You may distribute the Executable form of the Covered Software under

the terms of this License or under the terms of a license of Your choice, which may contain terms different from this License, provided that You are in compliance with the terms of this License and that the license for the Executable form does not attempt to limit or alter the recipient's rights in the Source Code form from the rights set forth in this License. If You distribute the Covered Software in Executable form under a different license, You must make it absolutely clear that any
terms which differ from this License
are offered by You alone, not by the Initial Developer or Contributor. You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of any such terms You offer.

3.6. Larger Works.

You may create a Larger Work by combining Covered Software with other code not governed by the terms of this License and distribute the Larger Work as a single product. In such a case, You must make sure the requirements of this License are fulfilled for the Covered Software.

4. Versions of the License.

4.1. New Versions.

Oracle is the initial license steward and may publish revised and/or new versions of this License from time to time. Each version will be given a distinguishing version number. Except as provided in Section 4.3, no one other than the license steward has the right to modify this License.

4.2. Effect of New Versions.

You may always continue to use, distribute or otherwise make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. If the Initial Developer includes a notice in the Original Software prohibiting it from being distributed or otherwise made available under any subsequent version of the License, You must distribute and make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. Otherwise, You may also choose to use, distribute or otherwise make the Covered Software available under the terms of any subsequent version of the License published by the license steward.

4.3. Modified Versions.

When You are an Initial Developer and You want to create a new license for Your Original Software, You may create and use a modified version of this License if You: (a) rename the license and remove any references to the name of the license steward (except to note that the license differs from this License); and (b) otherwise make it clear that the license contains terms which differ from this License.

5. DISCLAIMER OF WARRANTY.

COVERED SOFTWARE IS PROVIDED UNDER THIS LICENSE ON AN "AS IS" BASIS, WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES THAT THE COVERED SOFTWARE IS FREE OF DEFECTS, MERCHANTABLE, FIT FOR A PARTICULAR PURPOSE OR NON-INFRINGING. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE COVERED SOFTWARE IS WITH YOU. SHOULD ANY COVERED SOFTWARE PROVE DEFECTIVE IN ANY RESPECT, YOU (NOT THE INITIAL DEVELOPER OR ANY OTHER CONTRIBUTOR) ASSUME THE COST OF ANY NECESSARY SERVICING, REPAIR OR CORRECTION. THIS DISCLAIMER OF WARRANTY CONSTITUTES AN ESSENTIAL PART OF THIS LICENSE. NO USE OF ANY COVERED SOFTWARE IS AUTHORIZED HEREUNDER EXCEPT UNDER THIS DISCLAIMER.

6. TERMINATION.

6.1. This License and the rights granted hereunder will terminate automatically if You fail to comply with terms herein and fail to cure such breach within 30 days of becoming aware of the breach. Provisions which, by their nature, must remain in effect beyond the termination of this License shall survive.

6.2. If You assert a patent infringement claim (excluding declaratory judgment actions) against Initial Developer or a Contributor (the Initial Developer or Contributor against whom You assert such claim is referred to as "Participant") alleging that the Participant Software (meaning the Contributor Version where the Participant is a Contributor or the Original Software where the Participant is the Initial Developer) directly or indirectly infringes any patent, then any and all rights granted directly or indirectly to You by such Participant, the Initial Developer (if the Initial Developer is not the Participant) and all Contributors under Sections 2.1 and/or 2.2 of this License shall, upon 60 days notice from Participant terminate prospectively and automatically at the expiration of such 60 day notice period, unless if within such 60 day period You withdraw Your claim with respect to the Participant

Software against such Participant either unilaterally or pursuant to a written agreement with Participant.

6.3. If You assert a patent infringement claim against Participant alleging that the Participant Software directly or indirectly infringes any patent where such claim is resolved (such as by license or settlement) prior to the initiation of patent infringement litigation, then the reasonable value of the licenses granted by such Participant under Sections 2.1 or 2.2 shall be taken into account in determining the amount or value of any payment or license.

6.4. In the event of termination under Sections 6.1 or 6.2 above, all end user licenses that have been validly granted by You or any distributor hereunder prior to termination (excluding licenses granted to You by any distributor) shall survive termination.

7. LIMITATION OF LIABILITY.

UNDER NO CIRCUMSTANCES AND UNDER NO LEGAL THEORY, WHETHER TORT (INCLUDING NEGLIGENCE), CONTRACT, OR OTHERWISE, SHALL YOU, THE INITIAL DEVELOPER, ANY OTHER CONTRIBUTOR, OR ANY DISTRIBUTOR OF COVERED SOFTWARE, OR ANY SUPPLIER OF ANY OF SUCH PARTIES, BE LIABLE TO ANY PERSON FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY CHARACTER INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF GOODWILL, WORK STOPPAGE, COMPUTER FAILURE OR MALFUNCTION, OR ANY AND ALL OTHER COMMERCIAL DAMAGES OR LOSSES, EVEN IF SUCH PARTY SHALL HAVE BEEN INFORMED OF THE POSSIBILITY OF SUCH DAMAGES. THIS LIMITATION OF LIABILITY SHALL NOT APPLY TO LIABILITY FOR DEATH OR PERSONAL INJURY RESULTING FROM SUCH PARTY'S NEGLIGENCE TO THE EXTENT APPLICABLE LAW PROHIBITS SUCH LIMITATION. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS EXCLUSION AND LIMITATION MAY NOT APPLY TO YOU.

8. U.S. GOVERNMENT END USERS.

The Covered Software is a "commercial item," as that term is defined in 48 C.F.R. 2.101 (Oct. 1995), consisting of "commercial computer software" (as that term is defined at 48 C.F.R. 252.227-7014(a)(1)) and "commercial computer software documentation" as such terms are used in 48 C.F.R. 12.212 (Sept. 1995). Consistent with 48 C.F.R. 12.212 and 48 C.F.R. 227.7202-1 through 227.7202-4 (June 1995), all U.S. Government End Users acquire Covered Software with only those rights set forth herein. This U.S. Government Rights clause is in lieu of, and supersedes, any other FAR, DFAR, or other

clause or provision that addresses Government rights in computer

software under this License.

9. MISCELLANEOUS.

This License represents the complete agreement concerning subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable. This License shall be governed by the law of the jurisdiction specified in a notice contained within the Original Software (except to the extent applicable law, if any, provides otherwise), excluding such jurisdiction's conflict-of-law provisions. Any litigation relating to this License shall be subject to the jurisdiction of the courts located in the jurisdiction and venue specified in a notice contained within the Original Software, with the losing party responsible for costs, including, without limitation, court costs and reasonable attorneys' fees and expenses. The application of the United Nations Convention on Contracts for the International Sale of
Goods is expressly excluded. Any law or
regulation which provides that the language of a contract shall be construed against the drafter shall not apply to this License. You agree that You alone are responsible for compliance with the United States export administration regulations (and the export control laws and regulation of any other countries) when You use, distribute or otherwise make available any Covered Software.

10. RESPONSIBILITY FOR CLAIMS.

As between Initial Developer and the Contributors, each party is responsible for claims and damages arising, directly or indirectly, out of its utilization of rights under this License and You agree to work with Initial Developer and Contributors to distribute such responsibility on an equitable basis. Nothing herein is intended or shall be deemed to constitute any admission of liability.

NOTICE PURSUANT TO SECTION
9 OF THE COMMON DEVELOPMENT AND DISTRIBUTION
LICENSE (CDDL)

The code released under the CDDL shall be governed by the laws of the State of California (excluding conflict-of-law provisions). Any litigation relating to this License shall be subject to the jurisdiction of the Federal Courts of the Northern District of California and the state courts of the State of California, with venue lying in Santa Clara

County, California.

The GNU General Public License (GPL) Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor
Boston, MA 02110-1335
USA

Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.
This General Public
License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute
copies of such a program, whether gratis
or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain
that everyone understands that there is no warranty for this free
software. If the software is modified by someone else and passed on, we
want its recipients to know that what they have is not the original, so
that any problems introduced by others will not reflect on the original
authors' reputations.

Finally, any free program is threatened constantly by software patents.
We wish to avoid the danger that redistributors of a free program will
individually obtain patent licenses, in effect making
the program
proprietary. To prevent this, we have made it clear that any patent must
be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and
modification follow.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a
notice placed by the copyright holder saying it may be distributed under
the terms of this General Public License. The "Program", below, refers
to any such program or work, and a "work based on the Program" means
either the Program or any derivative work under copyright law: that is
to say, a work containing the Program or a portion of it, either
verbatim or with modifications and/or translated into another language.
(Hereinafter, translation is included without limitation in the term
"modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not
covered by this
License; they are outside its scope. The act of running
the Program is not restricted, and the output from the Program is
covered only if its contents constitute a work based on the Program
(independent of having been made by running the Program). Whether that
is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source
code as you receive it, in any medium, provided that you conspicuously
and appropriately publish on each copy an appropriate copyright notice
and disclaimer of warranty; keep intact all the notices that refer to
this License and to the absence of any warranty; and give any other
recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and
you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of

it, thus forming a work based on the Program, and copy
and distribute
such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative
or
collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under
the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs,
unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works.

These actions are
prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License,
they do not
excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software
distribution system, which is implemented
by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in

certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM

(INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

One line to give the program's name and a brief idea of what it does.
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1335 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'. This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the

appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.

signature of Ty Coon, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program
into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

#

Certain source files distributed by Oracle America, Inc. and/or its affiliates are subject to the following clarification and special exception to the GPLv2, based on the GNU Project exception for its Classpath libraries, known as the GNU Classpath Exception, but only where Oracle has expressly included in the particular source file's header the words "Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the LICENSE file that accompanied this code."

You should also note that Oracle includes multiple, independent programs in this software package. Some of those programs are provided under licenses deemed incompatible with the GPLv2 by the Free Software Foundation and
others. For example, the package includes programs
licensed under the Apache License, Version 2.0. Such programs are licensed to you under their original licenses.

Oracle facilitates your further distribution of this package by adding the Classpath Exception to the necessary parts of its GPLv2 code, which permits you to use that code in combination with other independent modules not licensed under the GPLv2. However, note that this would not permit you to commingle code under an incompatible license with Oracle's GPLv2 licensed code by, for example, cutting and pasting such code into a file also containing Oracle's GPLv2 licensed code and then

distributing the result. Additionally, if you were to remove the Classpath Exception from any of the files to which it applies and distribute the result, you would likely be required to license some or all of the other code in that distribution under the GPLv2 as well, and since the GPLv2 is incompatible with the license terms of some items included
 in the distribution by Oracle, removing the Classpath Exception could therefore effectively compromise your ability to further distribute the package.

Proceed with caution and we recommend that you obtain the advice of a lawyer skilled in open source matters before removing the Classpath Exception or making modifications to this package which may subsequently be redistributed and/or involve the use of third party software.

CLASSPATH EXCEPTION
Linking this library statically or dynamically with other modules is making a combined work based on this library. Thus, the terms and conditions of the GNU General Public License version 2 cover the whole combination.

As a special exception, the copyright holders of this library give you permission to link this library with independent modules to produce an executable, regardless of the license terms of these independent modules, and to copy and distribute the resulting executable under terms of your choice, provided that you also meet,
 for each linked
independent module, the terms and conditions of the license of that module. An independent module is a module which is not derived from or based on this library. If you modify this library, you may extend this exception to your version of the library, but you are not obligated to do so. If you do not wish to do so, delete this exception statement from your version.

1.1521 jaxb-api 2.3.0

1.1521.1 Available under license :

COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL)Version 1.1

1. Definitions.

1.1. "Contributor" means each individual or entity that creates or contributes to the creation of Modifications.

1.2. "Contributor Version" means the combination of the Original Software, prior Modifications used by a Contributor (if any), and the Modifications made by that particular Contributor.

1.3. "Covered Software" means (a) the Original Software, or (b) Modifications, or (c) the combination of files containing Original Software with files containing Modifications, in each case including portions thereof.

1.4. "Executable" means the Covered Software in any form other than Source Code.

1.5. "Initial Developer" means the individual or entity that first makes Original Software available under this License.

1.6. "Larger Work" means a work which combines Covered Software or portions thereof with code not governed by the terms of this License.

1.7. "License" means this
document.

1.8. "Licensable" means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently acquired, any and all of the rights conveyed herein.

1.9. "Modifications" means the Source Code and Executable form of any of the following:

A. Any file that results from an addition to, deletion from or modification of the contents of a file containing Original Software or previous Modifications;

B. Any new file that contains any part of the Original Software or previous Modification; or

C. Any new file that is contributed or otherwise made available under the terms of this License.

1.10. "Original Software" means the Source Code and Executable form of computer software code that is originally released under this License.

1.11. "Patent Claims" means any patent claim(s), now owned or hereafter acquired, including without limitation, method, process, and apparatus claims, in any patent Licensable
by grantor.

1.12. "Source Code" means (a) the common form of computer software code in which modifications are made and (b) associated documentation included in or with such code.

1.13. "You" (or "Your") means an individual or a legal entity exercising rights under, and complying with all of the terms of, this License. For legal entities, "You" includes any entity which controls, is controlled by, or is under common control with You. For purposes of this definition, "control" means (a) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (b) ownership of more than fifty percent (50%) of the outstanding shares or beneficial ownership of such entity.

2. License Grants.

2.1. The Initial Developer Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, the Initial Developer hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under intellectual property rights (other than patent or trademark) Licensable by Initial Developer, to use, reproduce, modify, display, perform, sublicense and distribute the Original Software (or portions thereof), with or without Modifications, and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using or selling of Original Software, to make, have made, use, practice, sell, and offer for sale, and/or otherwise dispose of the Original Software (or portions thereof).

(c) The licenses granted in Sections 2.1(a) and (b) are effective on the date Initial Developer first distributes or otherwise makes the Original Software available to a third party under the terms of this License.

(d) Notwithstanding Section 2.1(b) above, no patent license is granted: (1) for code that You delete from the Original Software, or (2) for infringements caused by: (i) the modification of the Original Software, or (ii) the combination of the
Original Software with other software or devices.

2.2. Contributor Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, each Contributor hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under intellectual property rights (other than patent or trademark) Licensable by Contributor to use, reproduce, modify, display, perform, sublicense and distribute the Modifications created by such Contributor (or portions thereof), either on an unmodified basis, with other Modifications, as Covered Software and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using, or selling of Modifications made by that Contributor either alone and/or in combination with its Contributor Version (or portions of such combination), to make, use, sell, offer for sale, have made, and/or otherwise dispose of: (1) Modifications made by that Contributor (or portions thereof);
and (2) the combination of Modifications made by that Contributor with its Contributor Version (or portions of such combination).

(c) The licenses granted in Sections 2.2(a) and 2.2(b) are effective on the date Contributor first distributes or otherwise makes the Modifications available to a third party.

(d) Notwithstanding Section 2.2(b) above, no patent license is granted: (1) for any code that Contributor has deleted from the Contributor Version; (2) for infringements caused by: (i) third party modifications of Contributor Version, or (ii) the combination of Modifications made by that Contributor with other software (except as part of the Contributor Version) or other devices; or (3) under Patent Claims infringed by Covered Software in the absence of Modifications made by that Contributor.

3. Distribution Obligations.

3.1. Availability of Source Code.

Any Covered Software that You distribute or otherwise make available in Executable form must also be made available

in Source Code form and that Source Code form must be distributed only under the terms of this License. You must include a copy of this License with every copy of the Source Code form of the Covered Software You distribute or otherwise make available. You must inform recipients of any such Covered Software in Executable form as to how they can obtain such Covered Software in Source Code form in a reasonable manner on or through a medium customarily used for software exchange.

3.2. Modifications.

The Modifications that You create or to which You contribute are governed by the terms of this License. You represent that You believe Your Modifications are Your original creation(s) and/or You have sufficient rights to grant the rights conveyed by this License.

3.3. Required Notices.

You must include a notice in each of Your Modifications that identifies You as the Contributor of the Modification. You may not remove or alter any copyright, patent or trademark notices contained within the Covered Software, or any notices of licensing or any descriptive text giving attribution to any Contributor or the Initial Developer.

3.4. Application of Additional Terms.

You may not offer or impose any terms on any Covered Software in Source Code form that alters or restricts the applicable version of this License or the recipients' rights hereunder. You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, you may do so only on Your own behalf, and not on behalf of the Initial Developer or any Contributor. You must make it absolutely clear that any such warranty, support, indemnity or liability obligation is offered by You alone, and You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of warranty, support, indemnity or liability terms You offer.

3.5. Distribution of Executable Versions.

You may distribute the Executable form of the Covered Software under the terms of this License or under the terms of a license of Your choice, which may contain terms different from this License, provided that You are in compliance with the terms of this License and that the license for the Executable form does not attempt to limit or alter the recipient's rights in the Source Code form from the rights set forth in this License. If You distribute the Covered Software in Executable form under a different license, You must make it absolutely clear that any terms which differ from this License are offered by You alone, not by the Initial Developer or Contributor. You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of any such terms You offer.

3.6. Larger Works.

You may create a Larger Work by combining Covered Software with other code not governed by the terms of this License and distribute the Larger Work as a single product. In such a case, You must make sure the requirements of this License are fulfilled for the Covered Software.

4. Versions of the License.

4.1. New Versions.

Oracle is the initial license steward and may publish revised and/or new versions of this License from time to time. Each version will be given a distinguishing version number. Except as provided in Section 4.3, no one other than the license steward has the right to modify this License.

4.2. Effect of New Versions.

You may always continue to use, distribute or otherwise make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. If the Initial Developer includes a notice in the Original Software prohibiting it from being distributed or otherwise made available under any subsequent version of the License, You must distribute
and make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. Otherwise, You may also choose to use, distribute or otherwise make the Covered Software available under the terms of any subsequent version of the License published by the license steward.

4.3. Modified Versions.

When You are an Initial Developer and You want to create a new license for Your Original Software, You may create and use a modified version of this License if You: (a) rename the license and remove any references to the name of the license steward (except to note that the license differs from this License); and (b) otherwise make it clear that the license contains terms which differ from this License.

5. DISCLAIMER OF WARRANTY.

COVERED SOFTWARE IS PROVIDED UNDER THIS LICENSE ON AN "AS IS" BASIS, WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES THAT THE COVERED
SOFTWARE IS FREE OF DEFECTS, MERCHANTABLE, FIT FOR A PARTICULAR PURPOSE OR NON-INFRINGING. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE COVERED SOFTWARE IS WITH YOU. SHOULD ANY COVERED SOFTWARE PROVE DEFECTIVE IN ANY RESPECT, YOU (NOT THE INITIAL DEVELOPER OR ANY OTHER CONTRIBUTOR) ASSUME THE COST OF ANY NECESSARY SERVICING, REPAIR OR CORRECTION. THIS DISCLAIMER OF WARRANTY CONSTITUTES AN ESSENTIAL PART OF THIS LICENSE. NO USE OF ANY COVERED SOFTWARE IS AUTHORIZED HEREUNDER EXCEPT UNDER THIS DISCLAIMER.

6. TERMINATION.

6.1. This License and the rights granted hereunder will terminate automatically if You fail to comply with terms herein and fail to cure such breach within 30 days of becoming aware of the breach. Provisions which, by their nature, must remain in effect beyond the termination of this License shall survive.

6.2. If You assert a patent infringement claim (excluding declaratory judgment actions) against Initial Developer or a Contributor (the
Initial Developer or Contributor against whom You assert such claim is referred to as "Participant") alleging that the Participant Software (meaning the Contributor Version where the Participant is a Contributor or the Original Software where the Participant is the Initial Developer) directly or indirectly infringes any patent, then any and all

rights granted directly or indirectly to You by such Participant, the Initial Developer (if the Initial Developer is not the Participant) and all Contributors under Sections 2.1 and/or 2.2 of this License shall, upon 60 days notice from Participant terminate prospectively and automatically at the expiration of such 60 day notice period, unless if within such 60 day period You withdraw Your claim with respect to the Participant Software against such Participant either unilaterally or pursuant to a written agreement with Participant.

6.3. If You assert a patent infringement claim against Participant alleging that the Participant Software directly or indirectly infringes any patent where such claim is resolved (such as by license or settlement) prior to the initiation of patent infringement litigation, then the reasonable value of the licenses granted by such Participant under Sections 2.1 or 2.2 shall be taken into account in determining the amount or value of any payment or license.

6.4. In the event of termination under Sections 6.1 or 6.2 above, all end user licenses that have been validly granted by You or any distributor hereunder prior to termination (excluding licenses granted to You by any distributor) shall survive termination.

7. LIMITATION OF LIABILITY.

UNDER NO CIRCUMSTANCES AND UNDER NO LEGAL THEORY, WHETHER TORT (INCLUDING NEGLIGENCE), CONTRACT, OR OTHERWISE, SHALL YOU, THE INITIAL DEVELOPER, ANY OTHER CONTRIBUTOR, OR ANY DISTRIBUTOR OF COVERED SOFTWARE, OR ANY SUPPLIER OF ANY OF SUCH PARTIES, BE LIABLE TO ANY PERSON FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY CHARACTER
INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF GOODWILL, WORK STOPPAGE, COMPUTER FAILURE OR MALFUNCTION, OR ANY AND ALL OTHER COMMERCIAL DAMAGES OR LOSSES, EVEN IF SUCH PARTY SHALL HAVE BEEN INFORMED OF THE POSSIBILITY OF SUCH DAMAGES. THIS LIMITATION OF LIABILITY SHALL NOT APPLY TO LIABILITY FOR DEATH OR PERSONAL INJURY RESULTING FROM SUCH PARTY'S NEGLIGENCE TO THE EXTENT APPLICABLE LAW PROHIBITS SUCH LIMITATION. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS EXCLUSION AND LIMITATION MAY NOT APPLY TO YOU.

8. U.S. GOVERNMENT END USERS.

The Covered Software is a "commercial item," as that term is defined in 48 C.F.R. 2.101 (Oct. 1995), consisting of "commercial computer software" (as that term is defined at 48 C.F.R. ? 252.227-7014(a)(1)) and "commercial computer software documentation" as such terms are used in 48 C.F.R. 12.212 (Sept. 1995). Consistent with 48 C.F.R. 12.212 and 48 C.F.R. 227.7202-1 through 227.7202-4
(June 1995), all U.S. Government End Users acquire Covered Software with only those rights set forth herein. This U.S. Government Rights clause is in lieu of, and supersedes, any other FAR, DFAR, or other clause or provision that addresses Government rights in computer software under this License.

9. MISCELLANEOUS.

This License represents the complete agreement concerning subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable. This License shall be governed by the law of the jurisdiction specified in a notice contained within the Original Software (except to the extent applicable law, if any, provides otherwise), excluding such jurisdiction's conflict-of-law provisions. Any litigation relating to this License shall be subject to the jurisdiction of the courts located in the

jurisdiction and venue specified in a notice contained within the Original Software, with the losing party responsible for costs, including, without limitation, court costs and reasonable attorneys' fees and expenses. The application of the United Nations Convention on Contracts for the International Sale of Goods is expressly excluded. Any law or regulation which provides that the language of a contract shall be construed against the drafter shall not apply to this License. You agree that You alone are responsible for compliance with the United States export administration regulations (and the export control laws and regulation of any other countries) when You use, distribute or otherwise make available any Covered Software.

10. RESPONSIBILITY FOR CLAIMS.

As between Initial Developer and the Contributors, each party is responsible for claims and damages arising, directly or indirectly, out of its utilization of rights under this License and You agree to work with Initial Developer and Contributors to distribute such responsibility on an equitable basis. Nothing herein is intended or shall be deemed to constitute any admission of liability.

NOTICE PURSUANT TO SECTION 9 OF THE COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL)

The code released under the CDDL shall be governed by the laws of the State of California (excluding conflict-of-law provisions). Any litigation relating to this License shall be subject to the jurisdiction of the Federal Courts of the Northern District of California and the state courts of the State of California, with venue lying in Santa Clara County, California.

The GNU General Public License (GPL) Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities
for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish
to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee
is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify
your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these
conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to
exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source
code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This

alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable
runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative
works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of
this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free
software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other

system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software
Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision
will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING
ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

One line to give the program's name
and a brief idea of what it does.

Copyright (C)

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision
comes with ABSOLUTELY NO WARRANTY; for details type `show w'. This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.

signature of Ty Coon, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program

is a subroutine library,
you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

"CLASSPATH" EXCEPTION TO THE GPL VERSION 2

Certain source files distributed by Oracle are subject to the following clarification and special exception to the GPL Version 2, but only where Oracle has expressly included in the particular source file's header the words "Oracle designates this particular file as subject to the "Classpath" exception as provided by Oracle in the License file that accompanied this code."

Linking this library statically or dynamically with other modules is making a combined work based on this library. Thus, the terms and conditions of the GNU General Public License Version 2 cover the whole combination.

As a special exception, the copyright holders of this library give you permission to link this library with independent modules to produce an executable, regardless
of the license terms of these independent modules, and to copy and distribute the resulting executable under terms of your choice, provided that you also meet, for each linked independent module, the terms and conditions of the license of that module. An independent module is a module which is not derived from or based on this library. If you modify this library, you may extend this exception to your version of the library, but you are not obligated to do so. If you do not wish to do so, delete this exception statement from your version.

1.1522 jaxb-core 2.2.11

1.1522.1 Available under license :

No license file was found, but licenses were detected in source scan.

Copyright (c) 1997-2014 Oracle and/or its affiliates. All rights reserved.
The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section of the License

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/Messages.properties
No license file was found, but licenses were detected in source scan.

<!--

DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.

Copyright (c) 2013-2014 Oracle and/or its affiliates. All rights reserved.

The contents of this file are subject to the terms of either the GNU

General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
obtain a copy of the License at
http://glassfish.java.net/public/CDDL+GPL_1_1.html
or packager/legal/LICENSE.txt. See the License for the specific
language governing permissions and limitations under the License.

When distributing the software, include this License Header Notice in each
file and include the License file at packager/legal/LICENSE.txt.

GPL Classpath Exception:
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section
of the License
file that accompanied this code.

Modifications:
If applicable, add the following below the License Header, with the fields
enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"

Contributor(s):
If you wish your version of this file to be governed by only the CDDL or
only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if the new code is made subject to such option by the copyright
holder.

-->

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/META-INF/maven/org.glassfish.jaxb/jaxb-core/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2014 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You

* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
 subject to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/nav/ReflectionNavigator.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/nav/Navigator.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/Messages.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/Messages.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2005-2010 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development

* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
 subject to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/IndentingXMLFilter.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/EndTag.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/Cdata.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/Content.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/Text.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/DumbEscapeHandler.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/StreamSerializer.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/CharacterEscapeHandler.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/IllegalAnnotationException.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/DatatypeWriter.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/TXWResult.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/annotation/XmlElement.java

* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/NamespaceDecl.java
*
 /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/Document.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/annotation/XmlAttribute.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/DumpSerializer.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/SaxSerializer.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/Comment.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/IllegalSignatureException.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/annotation/XmlCDATA.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/ContentVisitor.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/Pcdata.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/XmlSerializer.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/ContainerElement.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/DelegatingXMLStreamWriter.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/StaxSerializer.java
*
 /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/annotation/XmlValue.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/NamespaceResolver.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/DataWriter.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/annotation/XmlNamespace.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/TxwException.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/ResultFactory.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/TXW.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/StartDocument.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/StartTag.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/DomSerializer.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/Attribute.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/TypedXmlWriter.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/EndDocument.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/IndentingXMLStreamWriter.java
*
 /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/TXWSerializer.java
No license file was found, but licenses were detected in source scan.

<!--

  DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.

  Copyright (c) 2005-2014 Oracle and/or its affiliates. All rights reserved.

  The contents of this file are subject to the terms of either the GNU
  General Public License Version 2 only ("GPL") or the Common Development
  and Distribution License("CDDL") (collectively, the "License"). You
  may not use this file except in compliance with the License. You can
  obtain a copy of the License at
  https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
  or packager/legal/LICENSE.txt. See the License for the specific
  language governing permissions and limitations under the License.

When distributing the software, include this License Header Notice in each
file and include the License file at packager/legal/LICENSE.txt.

GPL Classpath Exception:
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section of the License
file that accompanied this code.

Modifications:
If applicable, add the following below the License Header, with the fields
enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"

Contributor(s):
If you wish your version of this file to be governed by only the CDDL or
only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if
the new code is made subject to such option by the copyright
holder.

-->

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/META-INF/maven/org.glassfish.jaxb/txw2/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2012 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* http://glassfish.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each

* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject
 to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/Nullable.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/SAXParseException2.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/Pool.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/Interned.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/Builder.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/SAXException2.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/NotNull.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/localization/LocalizableMessage.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/XMLStreamException2.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/logging/Logger.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/FinalArrayList.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/localization/Localizable.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/FragmentContentHandler.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/localization/NullLocalizable.java
*
 /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/package-info.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/localization/LocalizableMessageFactory.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/localization/Localizer.java
No license file was found, but licenses were detected in source scan.

```
/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2014 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License").  You
* may not use this file except in compliance with the License.  You can
* obtain a copy of the License at
* http://glassfish.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt.  See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license."  If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above.  However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject
 to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/ByteArrayDataSource.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/istack/XMLStreamReaderToContentHandler.java
No license file was found, but licenses were detected in source scan.

/*
```

* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2011 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject
 to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/schemagen/episode/Package.java
No license file was found, but licenses were detected in source scan.

Copyright (c) 2014 Oracle and/or its affiliates. All rights reserved.
The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development

and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section of the License

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/Messages_es.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/Messages_ko.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/Messages_de.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/Messages_zh_TW.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/Messages_fr.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/Messages_ja.properties
*
 /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/Messages_it.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/Messages_pt_BR.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/Messages_zh_CN.properties
No license file was found, but licenses were detected in source scan.

<!--

  DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.

  Copyright (c) 2005-2010 Oracle and/or its affiliates. All rights reserved.

  The contents of this file are subject to the terms of either the GNU
  General Public License Version 2 only ("GPL") or the Common Development
  and Distribution License("CDDL") (collectively, the "License"). You
  may not use this file except in compliance with the License. You can
  obtain a copy of the License at
  https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
  or packager/legal/LICENSE.txt. See the License for the specific
  language governing permissions and limitations under the License.

  When distributing the software, include this License Header Notice in each
  file and include the License file at packager/legal/LICENSE.txt.

  GPL Classpath Exception:
  Oracle designates this particular file as subject to the "Classpath"
   exception as provided by Oracle in the GPL Version 2 section of the License
  file that accompanied this code.

  Modifications:
  If applicable, add the following below the License Header, with the fields
  enclosed by brackets [] replaced by your own identifying information:
  "Portions Copyright [year] [name of copyright owner]"

  Contributor(s):
  If you wish your version of this file to be governed by only the CDDL or

only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if
the new code is made subject to such option by the copyright
holder.

-->

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/annotation/package.html
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/package.html
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/package.html
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2011 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):

* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
 subject to such option by the copyright
* holder.
*/
// NO WARRANTY! This class is in the public domain.

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/XMLWriter.java
No license file was found, but licenses were detected in source scan.

Copyright (c) 1997-2011 Oracle and/or its affiliates. All rights reserved.
The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section of the License

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/Messages_es.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/Messages_it.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/Messages_zh_CN.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/Messages.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/Messages_es.properties
*
 /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/Messages_ja.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/Messages_ko.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/Messages_fr.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/Messages_it.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/Messages_de.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/Messages_pt_BR.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/Messages_fr.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/Messages_zh_TW.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/Messages_ko.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/Messages_zh_CN.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/Messages_zh_TW.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/Messages_pt_BR.properties
*
 /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/Messages_ja.properties
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/Messages_de.properties

No license file was found, but licenses were detected in source scan.

```
/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2013 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License").  You
* may not use this file except in compliance with the License.  You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt.  See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license."  If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above.  However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject
 to such option by the copyright
* holder.
*/
```

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/util/XmlFactory.java
No license file was found, but licenses were detected in source scan.

```
/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2005-2010 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License").  You
* may not use this file except in compliance with the License.  You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt.  See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license."  If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above.  However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
 subject to such option by the copyright
* holder.
*/
// NO WARRANTY!  This class is in the public domain.

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/output/XMLWriter.java
No license file was found, but licenses were detected in source scan.

<!--
```

DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.

Copyright (c) 1997-2011 Oracle and/or its affiliates. All rights reserved.

The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
obtain a copy of the License at
https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
or packager/legal/LICENSE.txt. See the License for the specific
language governing permissions and limitations under the License.

When distributing the software, include this License Header Notice in each
file and include the License file at packager/legal/LICENSE.txt.

GPL Classpath Exception:
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section of the License
file that accompanied this code.

Modifications:
If applicable, add the following below the License Header, with the fields
enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"

Contributor(s):
If you wish your version of this file to be governed by only the CDDL or
only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if
the new code is made subject to such option by the copyright
holder.

-->

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/nav/package.html
No license file was found, but licenses were detected in source scan.

Copyright (c) 1997-2013 Oracle and/or its affiliates. All rights reserved.
The contents of this file are subject to the terms of either the GNU

General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section of the License

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/Messages.properties
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2013 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made

subject to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/package-info.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/Messages.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/Util.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2005-2010 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made

```
 subject to such option by the copyright
* holder.
*/
// This class is in the Public Domain.  NO WARRANTY!
/**
* Encapsulate Namespace logic for use by applications using SAX,
* or internally by SAX drivers.
*
* <blockquote>
* <em>This module, both source code and documentation, is in the
* Public Domain, and comes with <strong>NO WARRANTY</strong>.</em>
* See <a href='http://www.saxproject.org'>http://www.saxproject.org</a>
* for further information.
* </blockquote>
*
* <p>This class encapsulates the logic of Namespace processing: it
* tracks the declarations currently in force for each context and
* automatically processes qualified XML names into their Namespace
* parts; it can also be used in reverse for generating XML qnames
* from Namespaces.</p>
*
* <p>Namespace support objects are reusable, but the reset method
* must be invoked between each session.</p>
*
* <p>Here is a simple session:</p>
*
* <pre>
* String parts[] = new String[3];
* NamespaceSupport
 support = new NamespaceSupport();
*
* support.pushContext();
* support.declarePrefix("", "http://www.w3.org/1999/xhtml");
* support.declarePrefix("dc", "http://www.purl.org/dc#");
*
* parts = support.processName("p", parts, false);
* System.out.println("Namespace URI: " + parts[0]);
* System.out.println("Local name: " + parts[1]);
* System.out.println("Raw name: " + parts[2]);
*
* parts = support.processName("dc:title", parts, false);
* System.out.println("Namespace URI: " + parts[0]);
* System.out.println("Local name: " + parts[1]);
* System.out.println("Raw name: " + parts[2]);
*
* support.popContext();
* </pre>
*
```

* Note that this class is optimized for the use case where most
* elements do not contain Namespace declarations: if the same
* prefix/URI mapping is repeated for each context (for example), this
* class will be somewhat less efficient.
*
* Although SAX drivers (parsers) may choose to use this class to
* implement namespace handling, they
 are not required to do so.
* Applications must track namespace information themselves if they
* want to use namespace information.
*
* @since SAX 2.0
* @author David Megginson
* @version 2.0.1 (sax2r2)
*/

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/txw2/NamespaceSupport.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2010 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*

* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
 subject to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/unmarshaller/DOMScanner.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/api/impl/NameConverter.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2012 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):

* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
subject to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/SAX2DOMEx.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2011 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]

* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
 subject to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/ElementPropertyInfo.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/api/impl/NameUtil.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/annotation/XmlIsSet.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/ElementInfo.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/LeafInfo.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/nav/ParameterizedTypeImpl.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/MaybeElement.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/TODO.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/annotation/Locatable.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/MinimumEscapeHandler.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/ClassInfo.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/Ref.java
*
 /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/util/Which.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/ClassFactory.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/WhiteSpaceProcessor.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/schemagen/episode/package-info.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/runtime/IllegalAnnotationException.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/annotation/AnnotationReader.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/ID.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/Locatable.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/unmarshaller/InfosetScanner.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/PropertyInfo.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/AttributePropertyInfo.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/runtime/unmarshaller/LocatorEx.java
*
 /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/EnumLeafInfo.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/WellKnownNamespace.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/PropertyKind.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/TypeInfoSet.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/util/SecureLoader.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/util/EditDistance.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/ValuePropertyInfo.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/annotation/AnnotationSource.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/annotation/XmlLocation.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/schemagen/episode/Klass.java

* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/schemagen/episode/SchemaBindings.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/Adapter.java
*
 /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/RegistryInfo.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/nav/WildcardTypeImpl.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/nav/TypeVisitor.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/annotation/OverrideAnnotationOf.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/BuiltinLeafInfo.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/runtime/RuntimeUtil.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/CharacterEscapeHandler.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/schemagen/episode/Bindings.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/EnumConstant.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/Element.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/NonElementRef.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/NonElement.java
*
 /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/TypeRef.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/util/FlattenIterator.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/nav/SecureLoader.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/runtime/Location.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/ArrayInfo.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/MapPropertyInfo.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/ErrorHandler.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/WildcardTypeInfo.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/ReferencePropertyInfo.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/nav/GenericArrayTypeImpl.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/DataWriter.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/marshaller/DumbEscapeHandler.java
*
 /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/runtime/SwaRefAdapterMarker.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/TypeInfo.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/v2/model/core/WildcardMode.java
* /jaxb-core-2-2-11-sources-10-jar/com/sun/xml/bind/api/ErrorListener.java
No license file was found, but licenses were detected in source scan.

<!--

  DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.

  Copyright (c) 1997-2014 Oracle and/or its affiliates. All rights reserved.

  The contents of this file are subject to the terms of either the GNU
  General Public License Version 2 only ("GPL") or the Common Development
  and Distribution License("CDDL") (collectively, the "License"). You
  may not use this file except in compliance with the License. You can
  obtain a copy of the License at
  http://glassfish.java.net/public/CDDL+GPL_1_1.html
  or packager/legal/LICENSE.txt. See the License for the specific

language governing permissions and limitations under the License.

When distributing the software, include this License Header Notice in each
file and include the License file at packager/legal/LICENSE.txt.

GPL Classpath Exception:
Oracle designates this particular file as subject to the "Classpath"

exception as provided by Oracle in the GPL Version 2 section of the License
file that accompanied this code.

Modifications:
If applicable, add the following below the License Header, with the fields
enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"

Contributor(s):
If you wish your version of this file to be governed by only the CDDL or
only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if the new
code is made subject to such option by the copyright
holder.

-->

Found in path(s):
* /jaxb-core-2-2-11-sources-10-jar/META-INF/maven/com.sun.istack/istack-commons-runtime/pom.xml

1.1523 javax-xml-soap-api 1.4.0

1.1523.1 Available under license :

COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL) Version 1.0

1. Definitions.

1.1. Contributor. means each individual or entity that creates or contributes to the creation of Modifications.

1.2. Contributor Version. means the combination of the Original Software, prior Modifications used by a Contributor (if any), and the Modifications made by that particular Contributor.

1.3. Covered Software. means (a) the Original Software, or (b) Modifications, or (c) the combination of files

containing Original Software with files containing Modifications, in each case including portions thereof.

1.4. Executable. means the Covered Software in any form other than Source Code.

1.5. Initial Developer. means the individual or entity that first makes Original Software available under this License.

1.6. Larger Work. means a work which combines Covered Software or portions thereof with code not governed by the terms of this License.

1.7. License. means this document.

1.8.
Licensable. means having the right to grant, to the maximum extent possible, whether at the time of the initial grant or subsequently acquired, any and all of the rights conveyed herein.

1.9. Modifications. means the Source Code and Executable form of any of the following:

A. Any file that results from an addition to, deletion from or modification of the contents of a file containing Original Software or previous Modifications;

B. Any new file that contains any part of the Original Software or previous Modification; or

C. Any new file that is contributed or otherwise made available under the terms of this License.

1.10. Original Software. means the Source Code and Executable form of computer software code that is originally released under this License.

1.11. Patent Claims. means any patent claim(s), now owned or hereafter acquired, including without limitation, method, process, and apparatus claims, in any patent Licensable by grantor.

1.12.
Source Code. means (a) the common form of computer software code in which modifications are made and (b) associated documentation included in or with such code.

1.13. You. (or .Your.) means an individual or a legal entity exercising rights under, and complying with all of the terms of, this License. For legal entities, .You. includes any entity which controls, is controlled by, or is under common control with You. For purposes of this definition, .control. means (a) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (b) ownership of more than fifty percent (50%) of the outstanding shares or beneficial ownership of such entity.

2. License Grants.

2.1. The Initial Developer Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, the Initial Developer hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under
intellectual property rights (other than patent or trademark) Licensable by Initial Developer, to use, reproduce, modify, display, perform, sublicense and distribute the Original Software (or portions thereof), with or without Modifications, and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using or selling of Original Software, to make, have made, use, practice, sell, and offer for sale, and/or otherwise dispose of the Original Software (or portions thereof).

(c) The licenses granted in Sections 2.1(a) and (b) are effective on the date Initial Developer first distributes or otherwise makes the Original Software available to a third party under the terms of this License.

(d) Notwithstanding Section 2.1(b) above, no patent license is granted: (1) for code that You delete from the Original Software, or (2) for infringements caused by: (i) the modification of the Original Software, or (ii) the combination of the Original Software
with other software or devices.

2.2. Contributor Grant.

Conditioned upon Your compliance with Section 3.1 below and subject to third party intellectual property claims, each Contributor hereby grants You a world-wide, royalty-free, non-exclusive license:

(a) under intellectual property rights (other than patent or trademark) Licensable by Contributor to use, reproduce, modify, display, perform, sublicense and distribute the Modifications created by such Contributor (or portions thereof), either on an unmodified basis, with other Modifications, as Covered Software and/or as part of a Larger Work; and

(b) under Patent Claims infringed by the making, using, or selling of Modifications made by that Contributor either alone and/or in combination with its Contributor Version (or portions of such combination), to make, use, sell, offer for sale, have made, and/or otherwise dispose of: (1) Modifications made by that Contributor (or portions thereof); and (2) the
combination of Modifications made by that Contributor with its Contributor Version (or portions of such combination).

(c) The licenses granted in Sections 2.2(a) and 2.2(b) are effective on the date Contributor first distributes or otherwise makes the Modifications available to a third party.

(d) Notwithstanding Section 2.2(b) above, no patent license is granted: (1) for any code that Contributor has deleted from the Contributor Version; (2) for infringements caused by: (i) third party modifications of Contributor Version, or (ii) the combination of Modifications made by that Contributor with other software (except as part of the Contributor Version) or other devices; or (3) under Patent Claims infringed by Covered Software in the absence of Modifications made by that Contributor.

3. Distribution Obligations.

3.1. Availability of Source Code.
Any Covered Software that You distribute or otherwise make available in Executable form must also be made available

in Source Code form and that Source Code form must be distributed only under the terms of this License. You must include a copy of this License with every copy of the Source Code form of the Covered Software You distribute or otherwise make available. You must inform recipients of any such Covered Software in Executable form as to how they can obtain such Covered Software in Source Code form in a reasonable manner on or through a medium customarily used for software exchange.

3.2. Modifications.

The Modifications that You create or to which You contribute are governed by the terms of this License. You represent that You believe Your Modifications are Your original creation(s) and/or You have sufficient rights to grant the rights conveyed by this License.

3.3. Required Notices.

You must include a notice in each of Your Modifications that identifies You as the Contributor of the Modification. You may not remove or alter any copyright, patent or trademark notices contained within the Covered Software, or any notices of licensing or any descriptive text giving attribution to any Contributor or the Initial Developer.

3.4. Application of Additional Terms.

You may not offer or impose any terms on any Covered Software in Source Code form that alters or restricts the applicable version of this License or the recipients. rights hereunder. You may choose to offer, and to charge a fee for, warranty, support, indemnity or liability obligations to one or more recipients of Covered Software. However, you may do so only on Your own behalf, and not on behalf of the Initial Developer or any Contributor. You must make it absolutely clear that any such warranty, support, indemnity or liability obligation is offered by You alone, and You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of warranty, support, indemnity or liability terms You offer.

3.5. Distribution of Executable Versions.

You may distribute the Executable form of the Covered Software under the terms of this License or under the terms of a license of Your choice, which may contain terms different from this License, provided that You are in compliance with the terms of this License and that the license for the Executable form does not attempt to limit or alter the recipient.s rights in the Source Code form from the rights set forth in this License. If You distribute the Covered Software in Executable form under a different license, You must make it absolutely clear that any terms which differ from this License are offered by You alone, not by the Initial Developer or Contributor. You hereby agree to indemnify the Initial Developer and every Contributor for any liability incurred by the Initial Developer or such Contributor as a result of any such terms You offer.

3.6. Larger Works.

You may create a Larger Work by combining Covered Software with other code not governed by the terms of this License and distribute the Larger Work as a single product. In such a case, You must make sure the requirements of this License are fulfilled for the Covered Software.

4. Versions of the License.

4.1. New Versions.

Sun Microsystems, Inc. is the initial license steward and may publish revised and/or new versions of this License from time to time. Each version will be given a distinguishing version number. Except as provided in Section 4.3, no one other than the license steward has the right to modify this License.

4.2. Effect of New Versions.

You may always continue to use, distribute or otherwise make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. If the Initial Developer includes a notice in the Original Software prohibiting it from being distributed or otherwise made available under any subsequent version of the

License, You must distribute and make the Covered Software available under the terms of the version of the License under which You originally received the Covered Software. Otherwise, You may also choose to use, distribute or otherwise make the Covered Software available under the terms of any subsequent version of the License published by the license steward.

4.3. Modified Versions.

When You are an Initial Developer and You want to create a new license for Your Original Software, You may create and use a modified version of this License if You: (a) rename the license and remove any references to the name of the license steward (except to note that the license differs from this License); and (b) otherwise make it clear that the license contains terms which differ from this License.

5. DISCLAIMER OF WARRANTY.

COVERED SOFTWARE IS PROVIDED UNDER THIS LICENSE ON AN .AS IS. BASIS, WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES

THAT THE COVERED SOFTWARE IS FREE OF DEFECTS, MERCHANTABLE, FIT FOR A PARTICULAR PURPOSE OR NON-INFRINGING. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE COVERED SOFTWARE IS WITH YOU. SHOULD ANY COVERED SOFTWARE PROVE DEFECTIVE IN ANY RESPECT, YOU (NOT THE INITIAL DEVELOPER OR ANY OTHER CONTRIBUTOR) ASSUME THE COST OF ANY NECESSARY SERVICING, REPAIR OR CORRECTION. THIS DISCLAIMER OF WARRANTY CONSTITUTES AN ESSENTIAL PART OF THIS LICENSE. NO USE OF ANY COVERED SOFTWARE IS AUTHORIZED HEREUNDER EXCEPT UNDER THIS DISCLAIMER.

6. TERMINATION.

6.1. This License and the rights granted hereunder will terminate automatically if You fail to comply with terms herein and fail to cure such breach within 30 days of becoming aware of the breach. Provisions which, by their nature, must remain in effect beyond the termination of this License shall survive.

6.2. If You assert a patent infringement claim (excluding declaratory judgment actions) against Initial Developer or a Contributor (the Initial Developer or Contributor against whom You assert such claim is referred to as .Participant.) alleging that the Participant Software (meaning the Contributor Version where the Participant is a Contributor or the Original Software where the Participant is the Initial Developer) directly or indirectly infringes any patent, then any and all rights granted directly or indirectly to You by such Participant, the Initial Developer (if the Initial Developer is not the Participant) and all Contributors under Sections 2.1 and/or 2.2 of this License shall, upon 60 days notice from Participant terminate prospectively and automatically at the expiration of such 60 day notice period, unless if within such 60 day period You withdraw Your claim with respect to the Participant Software against such Participant either unilaterally or pursuant to a written agreement with Participant.

6.3. In the event of termination under Sections 6.1 or 6.2 above, all end user licenses

that have been validly granted by You or any distributor hereunder prior to termination (excluding licenses granted to You by any distributor) shall survive termination.

7. LIMITATION OF LIABILITY.

UNDER NO CIRCUMSTANCES AND UNDER NO LEGAL THEORY, WHETHER TORT (INCLUDING NEGLIGENCE), CONTRACT, OR OTHERWISE, SHALL YOU, THE INITIAL DEVELOPER, ANY OTHER CONTRIBUTOR, OR ANY DISTRIBUTOR OF COVERED SOFTWARE, OR ANY SUPPLIER OF ANY OF SUCH PARTIES, BE LIABLE TO ANY PERSON FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES OF ANY CHARACTER INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOST PROFITS, LOSS OF GOODWILL, WORK STOPPAGE, COMPUTER FAILURE OR MALFUNCTION, OR ANY AND ALL OTHER COMMERCIAL DAMAGES OR LOSSES, EVEN IF SUCH PARTY SHALL HAVE BEEN INFORMED OF THE POSSIBILITY OF SUCH DAMAGES. THIS LIMITATION OF LIABILITY SHALL NOT APPLY TO LIABILITY FOR DEATH OR PERSONAL INJURY RESULTING FROM SUCH PARTY.S NEGLIGENCE TO THE EXTENT APPLICABLE LAW PROHIBITS SUCH LIMITATION. SOME JURISDICTIONS
DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THIS EXCLUSION AND LIMITATION MAY NOT APPLY TO YOU.

8. U.S. GOVERNMENT END USERS.

The Covered Software is a .commercial item,. as that term is defined in 48 C.F.R. 2.101 (Oct. 1995), consisting of .commercial computer software. (as that term is defined at 48 C.F.R. ? 252.227-7014(a)(1)) and .commercial computer software documentation. as such terms are used in 48 C.F.R. 12.212 (Sept. 1995). Consistent with 48 C.F.R. 12.212 and 48 C.F.R. 227.7202-1 through 227.7202-4 (June 1995), all U.S. Government End Users acquire Covered Software with only those rights set forth herein. This U.S. Government Rights clause is in lieu of, and supersedes, any other FAR, DFAR, or other clause or provision that addresses Government rights in computer software under this License.

9. MISCELLANEOUS.

This License represents the complete agreement concerning subject matter hereof. If any provision of this License is held to be unenforceable, such provision shall be reformed only to the extent necessary to make it enforceable. This License shall be governed by the law of the jurisdiction specified in a notice contained within the Original Software (except to the extent applicable law, if any, provides otherwise), excluding such jurisdiction.s conflict-of-law provisions. Any litigation relating to this License shall be subject to the jurisdiction of the courts located in the jurisdiction and venue specified in a notice contained within the Original Software, with the losing party responsible for costs, including, without limitation, court costs and reasonable attorneys. fees and expenses. The application of the United Nations Convention on Contracts for the International Sale of Goods is expressly excluded. Any law or regulation which provides that the language of a contract shall be construed against the drafter shall not apply to this License. You agree that You alone are responsible for
compliance with the United States export administration regulations (and the export control laws and regulation of any other countries) when You use, distribute or otherwise make available any Covered Software.

10. RESPONSIBILITY FOR CLAIMS.

As between Initial Developer and the Contributors, each party is responsible for claims and damages arising, directly or indirectly, out of its utilization of rights under this License and You agree to work with Initial Developer

and Contributors to distribute such responsibility on an equitable basis. Nothing herein is intended or shall be deemed to constitute any admission of liability.

NOTICE PURSUANT TO SECTION 9 OF THE COMMON DEVELOPMENT AND DISTRIBUTION LICENSE (CDDL)

The code released under the CDDL shall be governed by the laws of the State of California (excluding conflict-of-law provisions). Any litigation relating to this License shall be subject to the jurisdiction of the Federal Courts of the Northern District of California
and the state courts of the State of California, with venue lying in Santa Clara County, California.

The GNU General Public License (GPL) Version 2, June 1991

Copyright (C) 1989, 1991 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software,
we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer
you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to

know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any
program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute
verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.

b) You must cause any work that you distribute or publish, that
in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.

c) If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and

that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works
in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or
executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

a) Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

b) Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

c) Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code
for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute
the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties

who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear
what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions

either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY
OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These
Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

One line to give the program's name and a brief idea of what it does.

Copyright (C)

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY
or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'. This is free software, and you are welcome to redistribute it under certain conditions; type `show c' for details.

The hypothetical commands `show w' and `show c' should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than `show w' and `show c'; they could even be mouse-clicks or menu items--whatever suits
your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the program `Gnomovision' (which makes passes at compilers) written by James Hacker.

signature of Ty Coon, 1 April 1989
Ty Coon, President of Vice

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

"CLASSPATH" EXCEPTION TO THE GPL VERSION 2

Certain source files distributed by Sun Microsystems, Inc. are subject to the following clarification and special exception to the GPL Version 2, but only where Sun has expressly included in the particular
source file's header the words

"Sun designates this particular file as subject to the "Classpath" exception as provided by Sun in the License file that accompanied this code."

Linking this library statically or dynamically with other modules is making a combined work based on this library.

Thus, the terms and conditions of the GNU General Public License Version 2 cover the whole combination.

As a special exception, the copyright holders of this library give you permission to link this library with independent modules to produce an executable, regardless of the license terms of these independent modules, and to copy and distribute the resulting executable under terms of your choice, provided that you also meet, for each linked independent module, the terms and conditions of the license of that module.? An independent module is a module which is not derived from or based on this library.? If you modify this library, you may extend this exception to your version of the library, but
you are not obligated to do so.? If you do not wish to do so, delete this exception statement from your version.

1.1524 jboss-logging 3.1.1.GA

1.1524.1 Available under license :

GNU LESSER GENERAL PUBLIC LICENSE
Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc.
51 Franklin Street, Fifth Floor, Boston, MA 02110-1301 USA
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts
as the successor of the GNU Library Public License, version 2, hence
the version number 2.1.]

Preamble

The licenses for most software are designed to take away your
freedom to share and change it. By contrast, the GNU General Public
Licenses are intended to guarantee your freedom to share and change
free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some
specially designated software packages--typically libraries--of the
Free Software Foundation and other authors who
decide to use it. You
can use it too, but we suggest you first think carefully about whether
this license or the ordinary General Public License is the better
strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use,
not price. Our General Public Licenses are designed to make sure that
you have the freedom to distribute copies of free software (and charge
for this service if you wish); that you receive source code or can get
it if you want it; that you can change the software and use pieces of
it in new free programs; and that you are informed that you can do
these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library,
whether gratis
or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software
patents pose a constant threat to the existence of
any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits
such linking only if the
entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with

the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting
the free library to free
software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order
to run.

GNU LESSER GENERAL PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data

prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

a) The modified work must itself be a software library.

b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.

c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.

d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the

ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object

file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the
object code for the work under the terms of Section 6.
Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

a) Accompany
the work with the complete corresponding
machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)

b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate
properly with a modified version of the library, if
the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.

c) Accompany the work with a written offer, valid for at

least three years, to give the same user the materials
specified in Subsection 6a, above, for a charge no more
than the cost of performing this distribution.

d) If distribution of the work is made by offering access to copy
from a designated place, offer equivalent access to copy the above
specified materials from the same place.

e) Verify that the user has already received a copy of these
materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the
Library" must include any data and utility programs needed for
reproducing the executable from it. However, as a special exception,
the materials to be distributed need not include anything that is
normally
distributed (in either source or binary form) with the major
components (compiler, kernel, and so on) of the operating system on
which the executable runs, unless that component itself accompanies
the executable.

It may happen that this requirement contradicts the license
restrictions of other proprietary libraries that do not normally
accompany the operating system. Such a contradiction means you cannot
use both them and the Library together in an executable that you
distribute.

7. You may place library facilities that are a work based on the
Library side-by-side in a single library together with other library
facilities not covered by this License, and distribute such a combined
library, provided that the separate distribution of the work based on
the Library and of the other library facilities is otherwise
permitted, and provided that you do these two things:

a) Accompany the combined library with a copy of the same work
based on the Library, uncombined with any
other library
facilities. This must be distributed under the terms of the
Sections above.

b) Give prominent notice with the combined library of the fact
that part of it is a work based on the Library, and explaining
where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute
the Library except as expressly provided under this License. Any
attempt otherwise to copy, modify, sublicense, link with, or
distribute the Library is void, and will automatically terminate your

rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if
you do not accept this License. Therefore, by
modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse
you from the conditions of this License. If you cannot
distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system
which is
implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that

system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE

LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIBRARY AS PERMITTED ABOVE,
BE LIABLE TO YOU
FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey
the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301

USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your
school, if any, to sign a "copyright disclaimer" for the library, if
necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the
library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990
Ty Coon, President of Vice

That's all there is to it!

1.1525 jaxb-runtime 2.2.11

1.1525.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2014 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:

```
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license."  If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above.  However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
 subject to such option by the copyright
* holder.
*/
// NO WARRANTY!  This class is in the public domain.
/**
* Default implementation of the Attributes interface.
*
* <blockquote>
* <em>This module, both source code and documentation, is in the
* Public Domain, and comes with <strong>NO WARRANTY</strong>.</em>
* See <a href='http://www.saxproject.org'>http://www.saxproject.org</a>
* for further information.
* </blockquote>
*
* <p>This class provides a default implementation of the SAX2
* {@link org.xml.sax.Attributes Attributes} interface, with the
* addition of manipulators so that the list can be modified or
* reused.</p>
*
* <p>There are two typical uses of this class:</p>
*
* <ol>
* <li>to take a persistent snapshot of an Attributes object
*  in a {@link org.xml.sax.ContentHandler#startElement startElement} event; or</li>
* <li>to construct or modify an Attributes object in a SAX2 driver or filter.</li>
* </ol>
*
* <p>This class replaces the now-deprecated
 SAX1 {@link
* org.xml.sax.helpers.AttributeListImpl AttributeListImpl}
* class; in addition to supporting the updated Attributes
* interface rather than the deprecated {@link org.xml.sax.AttributeList
* AttributeList} interface, it also includes a much more efficient
* implementation using a single array rather than a set of Vectors.</p>
*
* @since JAXB 1.0
```

* @since SAX 2.0
* @author David Megginson
* @version 2.0.1 (sax2r2)
*/

Found in path(s):
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/util/AttributesImpl.java
No license file was found, but licenses were detected in source scan.

Copyright (c) 1997-2014 Oracle and/or its affiliates. All rights reserved.
The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section of the License

Found in path(s):
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages.properties
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2013-2014 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"

*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
 subject to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/Utils.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Utils.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/Utils.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/Utils.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Utils.java
No license file was found, but licenses were detected in source scan.

<!--

  DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.

  Copyright (c) 1997-2011 Oracle and/or its affiliates. All rights reserved.

  The contents of this file are subject to the terms of either the GNU
  General Public License Version 2 only ("GPL") or the Common Development
  and Distribution License("CDDL") (collectively, the "License"). You
  may not use this file except in compliance with the License. You can
  obtain a copy of the License at
  https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
  or packager/legal/LICENSE.txt. See the License for the specific
  language governing permissions and limitations under the License.

  When distributing the software, include this License Header Notice in each
  file and include the License file at packager/legal/LICENSE.txt.

  GPL Classpath Exception:
  Oracle designates this particular file as subject to the "Classpath"
   exception as provided by Oracle in the GPL Version 2 section of the License
  file that accompanied this code.

  Modifications:
  If applicable, add the following below the License Header, with the fields

enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"

Contributor(s):
If you wish your version of this file to be governed by only the CDDL or
only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if
the new code is made subject to such option by the copyright
holder.

-->

Found in path(s):
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/package.html
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/package.html
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/package.html
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/xmlschema-for-jaxb.rng
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/package.html
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/package.html
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/bytecode/package.html
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/package.html
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2012 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"

* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
 subject to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ComplexContent.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlEnumQuick.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlElementDeclQuick.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/AttrDecls.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ComplexTypeHost.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/ReferencePropertyInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlElementRefsQuick.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Schema.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ExplicitGroup.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlRootElementQuick.java
*
 /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Occurs.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlSchemaQuick.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ComplexRestriction.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ComplexType.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SimpleTypeHost.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/package-info.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SimpleContent.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/InternalAccessorFactory.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ComplexExtension.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/TypeHost.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/NoFixedFacet.java
*

/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlTypeQuick.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/LocalAttribute.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Union.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/TypeDefParticle.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlElementRefQuick.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlTransientQuick.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/XMLSerializer.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Element.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/TopLevelAttribute.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SimpleExtension.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Wildcard.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/FixedOrDefault.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SchemaTop.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/ContextFactory.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ComplexTypeModel.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/MarshallerImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/List.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Annotated.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/LocalElement.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SimpleDerivation.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SimpleRestriction.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Redefinable.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Init.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlSchemaTypeQuick.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Annotation.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/AttributeType.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Documentation.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ExtensionType.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SimpleType.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/TopLevelElement.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlValueQuick.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Import.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlAttributeQuick.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/UnmarshallerImpl.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/NestedParticle.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/XmlElementQuick.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/SimpleRestrictionModel.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Appinfo.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Any.java
No license file was found, but licenses were detected in source scan.

Copyright (c) 1997-2011 Oracle and/or its affiliates. All rights reserved.
The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You

may not use this file except in compliance with the License. You can
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section of the License

Found in path(s):
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_de.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_ja.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_zh_CN.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_zh_CN.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_ja.properties
*
 /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_ko.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_ja.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_fr.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_ja.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/Messages_es.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_de.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_fr.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/Messages_zh_TW.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_it.properties
*
 /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_it.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/Messages_pt_BR.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_zh_CN.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_ko.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/Messages_ja.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/Messages_it.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_fr.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_fr.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_de.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_it.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_ko.properties
*
 /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_ko.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_zh_TW.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/Messages_ko.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_de.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_ja.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_fr.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_es.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_de.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_ko.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_de.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages.properties
*

/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_it.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_ja.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/Messages_zh_CN.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_fr.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_fr.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/Messages.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_pt_BR.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_ja.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_zh_TW.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_pt_BR.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/Messages_de.properties
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_it.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_fr.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_de.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_pt_BR.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_ko.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_zh_CN.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_de.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_zh_TW.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_it.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_zh_TW.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_zh_TW.properties
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_zh_CN.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_pt_BR.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_ko.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_zh_TW.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_pt_BR.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_it.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_zh_TW.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_es.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages_zh_CN.properties
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_zh_CN.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_pt_BR.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_es.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_pt_BR.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_ja.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_zh_CN.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_es.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages_pt_BR.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages_es.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_ko.properties
*

/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages_it.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages_es.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages_zh_TW.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages_es.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages_es.properties
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/Messages_fr.properties
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2011 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
subject to such option by the copyright
* holder.

*/

Found in path(s):
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/Const.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/IndentingUTF8XmlOutput.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Patcher.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/AdaptedLister.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_method_Short.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/util/StackRecorder.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/XMLEventWriterOutput.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/marshaller/NamespacePrefixMapper.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/BinderImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeEnumLeafInfo.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeElementPropertyInfo.java
*
 /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/SecureLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_field_Integer.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/Ref.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Character.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/MTOMDecorator.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/TagName.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/SecureLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/Messages.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/util/ValidationEventLocatorExImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerInteger.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Messages.java
*
 /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/bytecode/SecureLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Double.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeArrayInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/AttributeAccessor.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/Messages.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/AttributesEx.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/StAXPostInitAction.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/ListIterator.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/util/TypeCast.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/SwaRefAdapter.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/IntData.java
*
 /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/TypeRefImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/PropertyImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/MimeTypedTransducer.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ArrayElementLeafProperty.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/ValuePropertyInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/FilterTransducer.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/Name.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_method_Long.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/IllegalAnnotationsException.java

* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/SchemaTypeTransducer.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerShort.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/XmlVisitor.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/Bridge.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/SAXOutput.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeClassInfo.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/Messages.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Byte.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Quick.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/UTF8XmlOutput.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/GroupKind.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeElementPropertyInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/EnumConstantImpl.java
* /jaxb-impl-2-2-11-sources-6-
jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_method_Boolean.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_method_Float.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/Form.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/NameBuilder.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Receiver.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/RuntimeInlineAnnotationReader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/util/DataSourceSource.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_method_Byte.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Messages.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeElementInfo.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/Pcdata.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/FieldLocatable.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/AdaptedAccessor.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_field_Short.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeNonElement.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/DomPostInitAction.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/BridgeContext.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/MTOMXmlOutput.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/Tree.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/AccessorException.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeEnumConstantImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimePropertyInfo.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/XmlOutput.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Base64Data.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeElement.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/ForkXmlOutput.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/StAXExConnector.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Double.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/package-info.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeLeafInfo.java

* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/BridgeImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/Transducer.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/AttributePropertyInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/ArrayInfoImpl.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/LeafInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/TypeInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/package-info.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/package-info.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/AbstractInlineAnnotationReaderImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/Bean.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/ClassInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/SecureLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/AccessorFactoryImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_field_Float.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/ContentModelContainer.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/util/QNameMap.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/marshaller/NioEscapeHandler.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/SecureLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/Messages.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeTypeRefImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/StAXExStreamWriterOutput.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeBuiltinLeafInfo.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/DefaultTransducedAccessor.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeArrayInfo.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/ClassResolver.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/SingleElementNodeProperty.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/NamespaceContext2.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/TypeInfoSetImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/PropertySeed.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Ref.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/FoolProofResolver.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/ValidationEventLocatorEx.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeMapPropertyInfo.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/RawAccessor.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ValueProperty.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/IDResolver.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/ListTransducedAccessorImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Integer.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/ValidatingUnmarshaller.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/AnyTypeAdapter.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/FastInfosetConnector.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/LocatorExWrapper.java
* /jaxb-impl-2-2-11-sources-6-
jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_method_Integer.java

* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/TagAndType.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/InlineBinaryTransducer.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_field_Byte.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/LocatableAnnotation.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/DOMOutput.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Short.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/ElementPropertyInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Messages.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/AnyTypeImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Integer.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/MultiMap.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/ChildLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/XmlAccessorFactory.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeValuePropertyInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/CycleRecoverable.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeValuePropertyInfo.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/BridgeAdapter.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeTypeRef.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/util/CollisionCheckStack.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/EnumLeafInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/BuiltinLeafInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/AttributesExImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_field_Long.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/Util.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/Messages.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/AssociationMap.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeAttributePropertyInfo.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/BridgeContextImpl.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/Property.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/FieldPropertySeed.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerBoolean.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Intercepter.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeEnumLeafInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/LifecycleMethods.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/StructureLoaderBuilder.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/unmarshaller/Patcher.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/PropertyFactory.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_field_Double.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_field_Boolean.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/FastInfosetStreamWriterOutput.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Boolean.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/util/ByteArrayOutputStreamEx.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/ElementInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/CompositeStructureBeanInfo.java

* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerCharacter.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/SecureLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/StAXConnector.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/GetterSetterPropertySeed.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ArrayElementProperty.java
*
 /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerLong.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/Util.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/Encoded.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Long.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeReferencePropertyInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Byte.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Long.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeTypeInfo.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ArrayElementNodeProperty.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/package-info.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/UnmarshallerChain.java
*
 /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/CompositeStructure.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Float.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/xmlschema/Particle.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/MapPropertyInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/C14nXmlOutput.java
* /jaxb-impl-2-2-11-sources-6-
jar/com/sun/xml/bind/v2/runtime/reflect/opt/TransducedAccessor_method_Double.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/StAXEventConnector.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/SingleReferenceNodeProperty.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Short.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/PropertyInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerDouble.java
*
 /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/InterningXmlVisitor.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/RuntimeAnnotationReader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/bytecode/ClassTailor.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/ERPropertyInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RegistryInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/SingleTypePropertyInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/WildcardLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/package-info.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/util/FatalAdapter.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/MethodLocatable.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeReferencePropertyInfo.java
*
 /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/AccessorFactory.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/DummyPropertyInfo.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/Coordinator.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeAttributePropertyInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/NameList.java

* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerByte.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/XmlOutputAbstractImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Float.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeNonElementRef.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/AttributeProperty.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/PrimitiveArrayListerFloat.java
*
 /jaxb-impl-2-2-11-sources-6-
jar/com/sun/xml/bind/v2/runtime/reflect/opt/OptimizedTransducedAccessorFactory.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/NullSafeAccessor.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/annotation/ClassLocatable.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeMapPropertyInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/NamespaceContextImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Boolean.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/AnyTypeBeanInfo.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/DefaultIDResolver.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/FieldAccessor_Ref.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/MethodAccessor_Character.java
*
 /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ArrayReferenceNodeProperty.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/InternalBridge.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2010 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields

* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
 subject to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/SingleElementLeafProperty.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeClassInfoImpl.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2013 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:

* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
 subject to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/AccessorInjector.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/schemagen/XmlSchemaGenerator.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ListElementProperty.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/LeafBeanInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/OptimizedAccessorFactory.java
No license file was found, but licenses were detected in source scan.

<!--

DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.

Copyright (c) 2013-2014 Oracle and/or its affiliates. All rights reserved.

The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
obtain a copy of the License at
http://glassfish.java.net/public/CDDL+GPL_1_1.html
or packager/legal/LICENSE.txt. See the License for the specific
language governing permissions and limitations under the License.

When distributing the software, include this License Header Notice in each
file and include the License file at packager/legal/LICENSE.txt.

GPL Classpath Exception:
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle in the GPL Version 2 section
 of the License
file that accompanied this code.

Modifications:
If applicable, add the following below the License Header, with the fields
enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"

Contributor(s):
If you wish your version of this file to be governed by only the CDDL or
only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if the new code is made subject to such option by the copyright
holder.

-->

Found in path(s):
* /jaxb-impl-2-2-11-sources-6-jar/META-INF/maven/org.glassfish.jaxb/jaxb-runtime/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2011 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields

```
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license."  If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above.  However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
 subject to such option by the copyright
* holder.
*/
/**
    * Sets the int[] data to this object.
    *
    * <p>
    * This method doesn't make a copy for a performance reason.
    * The caller is still free to modify the array it passed to this method,
    * but he should do so with a care. The unmarshalling code isn't expecting
    * the value to be changed while it's being routed.
    */
```

Found in path(s):
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/IntArrayData.java
No license file was found, but licenses were detected in source scan.

```
/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2014 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License").  You
* may not use this file except in compliance with the License.  You can
* obtain a copy of the License at
* https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt.  See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
```

* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made
 subject to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/ClassBeanInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/TransducedAccessor.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ArrayERProperty.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeBuiltinLeafInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/LeafPropertyLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Accessor.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/SingleMapNodeProperty.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/ValuePropertyLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/ContentHandlerAdaptor.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeElementInfoImpl.java
*
 /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/property/ArrayProperty.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/XsiTypeLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/unmarshaller/Messages.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/JAXBContextImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/DatatypeConverterImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/ModelBuilder.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/StructureLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/ProxyLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/Lister.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeAnyTypeImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/output/XMLStreamWriterOutput.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Scope.java

*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/SAXConnector.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeTypeInfoSetImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/XsiNilLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/TextLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Loader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/LeafPropertyXsiLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/reflect/opt/Injector.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/UnmarshallingContext.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/DomLoader.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/JaxBeanInfo.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/runtime/RuntimeTypeInfoSet.java
*
/jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/ElementBeanInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/ValueListBeanInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/DefaultValueLoaderDecorator.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/model/impl/RuntimeModelBuilder.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/ArrayBeanInfoImpl.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/TypeReference.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/Discarder.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/runtime/unmarshaller/StAXStreamConnector.java
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/api/JAXBRIContext.java
No license file was found, but licenses were detected in source scan.

DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
#
Copyright (c) 1997-2011 Oracle and/or its affiliates. All rights reserved.
#
The contents of this file are subject to the terms of either the GNU
General Public License Version 2 only ("GPL") or the Common Development
and Distribution License("CDDL") (collectively, the "License"). You
may not use this file except in compliance with the License. You can
obtain a copy of the License at
https://glassfish.dev.java.net/public/CDDL+GPL_1_1.html
or packager/legal/LICENSE.txt. See the License for the specific
language governing permissions and limitations under the License.
#
When distributing the software, include this License Header Notice in each
file and include the License file at packager/legal/LICENSE.txt.
#
GPL Classpath Exception:
Oracle designates this particular file as subject to the "Classpath"
exception as provided by Oracle
 in the GPL Version 2 section of the License
file that accompanied this code.
#
Modifications:
If applicable, add the following below the License Header, with the fields

enclosed by brackets [] replaced by your own identifying information:
"Portions Copyright [year] [name of copyright owner]"
#
Contributor(s):
If you wish your version of this file to be governed by only the CDDL or
only the GPL Version 2, indicate your decision by adding "[Contributor]
elects to include this software in this distribution under the [CDDL or GPL
Version 2] license." If you don't indicate a single choice of license, a
recipient has the option to distribute your version of this file under
either the CDDL, the GPL Version 2 or to extend the choice of license to
its licensees as provided above. However, if you add GPL Version 2 code
and therefore, elected the GPL Version 2 license, then the option applies
only if the new code is made subject to such option by the copyright
#
 holder.
#

The sxd/vsd files are the master, and the gif file should be created from it.

Found in path(s):
* /jaxb-impl-2-2-11-sources-6-jar/com/sun/xml/bind/v2/doc-files/readme.txt

1.1526 jax-ws-api 2.3.0

1.1526.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2009-2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version

2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/spi/Invoker.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/spi/http/HttpHandler.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/EndpointContext.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/spi/http/HttpContext.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/spi/http/package-info.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2015-2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"

* exception as provided by Oracle in the GPL Version
 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
 * holder.
*/

Found in path(s):
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/spi/ServiceLoaderUtil.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version
 2 section of the License
* file that accompanied this code.

*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
* holder.
 */

Found in path(s):
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/handler/soap/package-info.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/spi/package-info.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/http/package-info.java
* /jaxws-api-2-3-0-sources-3-jar/module-info.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/soap/package-info.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/handler/package-info.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2007-2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version

2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
* holder.
*/

Found in path(s):
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/package-info.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2005-2017 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* https://oss.oracle.com/licenses/CDDL+GPL-1.1
* or LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided by Oracle in the GPL Version
2 section of the License
* file that accompanied this code.
*

* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to such option by the copyright
 * holder.
*/

Found in path(s):
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/Provider.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/Action.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/spi/http/HttpExchange.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/WebEndpoint.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/wsaddressing/W3CEndpointReference.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/ResponseWrapper.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/Response.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/handler/LogicalMessageContext.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/wsaddressing/package-info.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/WebServiceException.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/WebServiceProvider.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/soap/Addressing.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/WebServiceFeature.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/handler/PortInfo.java
*
 /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/soap/MTOM.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/handler/soap/SOAPHandler.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/soap/AddressingFeature.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/Holder.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/BindingProvider.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/spi/Provider.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/WebServicePermission.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/soap/SOAPFaultException.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/AsyncHandler.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/http/HTTPBinding.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/handler/Handler.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/handler/LogicalHandler.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/WebServiceContext.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/spi/WebServiceFeatureAnnotation.java

* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/WebServiceClient.java
*
 /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/Endpoint.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/handler/HandlerResolver.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/ProtocolException.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/RespectBindingFeature.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/EndpointReference.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/handler/soap/SOAPMessageContext.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/RespectBinding.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/Service.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/wsaddressing/W3CEndpointReferenceBuilder.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/Binding.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/RequestWrapper.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/WebServiceRef.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/FaultAction.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/WebFault.java
*
 /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/Dispatch.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/spi/FactoryFinder.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/BindingType.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/WebServiceRefs.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/spi/ServiceDelegate.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/LogicalMessage.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/ServiceMode.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/http/HTTPException.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/soap/SOAPBinding.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/handler/MessageContext.java
* /jaxws-api-2-3-0-sources-3-jar/javax/xml/ws/soap/MTOMFeature.java

1.1527 mime-pull 1.9.3

1.1527.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2012 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* http://glassfish.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.

*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
 as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject
 to such option by the copyright
* holder.
*/

Found in path(s):
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/ASCIIUtility.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/FileData.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/BASE64DecoderStream.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/DataFile.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/PropUtil.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/FinalArrayList.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/QPDecoderStream.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/DecodingException.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/MIMEEvent.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/Chunk.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/WeakDataFile.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/ChunkInputStream.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/FactoryFinder.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/MIMEParser.java
*
 /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/MIMEConfig.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/MimeUtility.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/UUDecoderStream.java

* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/MIMEParsingException.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/CleanUpExecutorFactory.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/InternetHeaders.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/MIMEMessage.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/MIMEPart.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/Data.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/LineInputStream.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/Header.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 2013 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* http://glassfish.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception as provided
 by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject to

such option by the copyright
* holder.
*/

Found in path(s):
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/TempFiles.java
No license file was found, but licenses were detected in source scan.

/*
* DO NOT ALTER OR REMOVE COPYRIGHT NOTICES OR THIS HEADER.
*
* Copyright (c) 1997-2013 Oracle and/or its affiliates. All rights reserved.
*
* The contents of this file are subject to the terms of either the GNU
* General Public License Version 2 only ("GPL") or the Common Development
* and Distribution License("CDDL") (collectively, the "License"). You
* may not use this file except in compliance with the License. You can
* obtain a copy of the License at
* http://glassfish.java.net/public/CDDL+GPL_1_1.html
* or packager/legal/LICENSE.txt. See the License for the specific
* language governing permissions and limitations under the License.
*
* When distributing the software, include this License Header Notice in each
* file and include the License file at packager/legal/LICENSE.txt.
*
* GPL Classpath Exception:
* Oracle designates this particular file as subject to the "Classpath"
* exception
as provided by Oracle in the GPL Version 2 section of the License
* file that accompanied this code.
*
* Modifications:
* If applicable, add the following below the License Header, with the fields
* enclosed by brackets [] replaced by your own identifying information:
* "Portions Copyright [year] [name of copyright owner]"
*
* Contributor(s):
* If you wish your version of this file to be governed by only the CDDL or
* only the GPL Version 2, indicate your decision by adding "[Contributor]
* elects to include this software in this distribution under the [CDDL or GPL
* Version 2] license." If you don't indicate a single choice of license, a
* recipient has the option to distribute your version of this file under
* either the CDDL, the GPL Version 2 or to extend the choice of license to
* its licensees as provided above. However, if you add GPL Version 2 code
* and therefore, elected the GPL Version 2 license, then the option applies
* only if the new code is made subject
to such option by the copyright
* holder.

*/

Found in path(s):
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/MemoryData.java
* /mimepull-1-9-3-sources-7-jar/org/jvnet/mimepull/DataHead.java

1.1528 logging 1.1.1

1.1528.1 Available under license :

The MIT License (MIT)

Copyright (c) 2010 - 2016 Blue Spire Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1529 lang 2.4.0

1.1529.1 Available under license :

Apache Commons Lang
Copyright 2001-2008 The Apache Software Foundation

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally

submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the

content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1530 netty-all 4.1.49.Final

1.1530.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version
* 2.0 (the "License"); you may not use this file except in compliance with the
* License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/cors/CorsConfigBuilder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*

* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
* Copyright (c) 2004-2011 QOS.ch
* All rights reserved.
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without
 limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be
* included in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
* NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
* LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
* OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
* WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/FormattingTuple.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/MessageFormatter.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketCloseStatus.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/ReferenceCountUpdater.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/MaxCapacityQueue.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshaker00.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/mqtt/heartBeat/MqttHeartBeatClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ExtendedClosedChannelException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsQueryEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/mqtt/heartBeat/MqttHeartBeatBrokerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshaker.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshakerFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/address/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshaker13.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/SSLTask.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelHandlerMask.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/PseudoRandomFunction.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshaker07.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2SettingsAckFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketServerHandshaker08.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/mqtt/heartBeat/MqttHeartBeatBroker.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/SSLPrivateKeyMethodTask.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/ObjectPool.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/KeyManagerFactoryWrapper.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/TrustManagerFactoryWrapper.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/CloseWebSocketFrame.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsCodecUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2MultiplexHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/AbstractHttp2StreamChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/util/X509KeyManagerWrapper.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DatagramDnsQueryContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/macos/DnsResolver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsResponseDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/Hidden.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/EventLoopTaskQueueFactory.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionFilterProvider.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/macos/package-info.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/TcpDnsQueryContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslPrivateKeyMethod.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/TcpDnsQueryEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2SettingsAckFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/svm/UnsafeRefArrayAccessSubstitution.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/svm/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/ThreadExecutorMap.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/WebSocketServerProtocolHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/address/DynamicAddressConnectHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/SSLPrivateKeyMethod.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/CertificateVerifierTask.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketClientProtocolConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/SSLPrivateKeyMethodSignTask.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Lz4XXHash32.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/mqtt/heartBeat/MqttHeartBeatClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketDecoderConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/svm/PlatformDependent0Substitution.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketServerProtocolConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/util/SimpleKeyManagerFactory.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/CorruptedWebSocketFrameException.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/PreferredAddressTypeComparator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/SSLPrivateKeyMethodDecryptTask.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/CertificateCallbackTask.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/macos/MacOSDnsServerAddressStreamProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/svm/CleanerJava6Substitution.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionFilter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/svm/PlatformDependentSubstitution.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/SslMasterKeyHandler.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/WebSocketServerProtocolHandshakeHandler.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocket00FrameDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/TcpDnsResponseDecoder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:

```
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
* A decoder that splits the received {@link ByteBuf}s dynamically by the
* value of the length field in the message.  It is particularly useful when you
* decode a binary message which has an integer header field that represents the
* length of the message body or the whole message.
*
 <p>
* {@link LengthFieldBasedFrameDecoder} has many configuration parameters so
* that it can decode any message with a length field, which is often seen in
* proprietary client-server protocols. Here are some example that will give
* you the basic idea on which option does what.
*
* <h3>2 bytes length field at offset 0, do not strip header</h3>
*
* The value of the length field in this example is <tt>12 (0x0C)</tt> which
* represents the length of "HELLO, WORLD".  By default, the decoder assumes
* that the length field represents the number of the bytes that follows the
* length field.  Therefore, it can be decoded with the simplistic parameter
* combination.
* <pre>
* <b>lengthFieldOffset</b>   = <b>0</b>
* <b>lengthFieldLength</b>   = <b>2</b>
* lengthAdjustment    = 0
* initialBytesToStrip = 0 (= do not strip header)
*
* BEFORE DECODE (14 bytes)         AFTER DECODE (14 bytes)
* +--------+----------------+      +--------+----------------+
* | Length | Actual Content
 |----->| Length | Actual Content |
* | 0x000C | "HELLO, WORLD" |      | 0x000C | "HELLO, WORLD" |
* +--------+----------------+      +--------+----------------+
* </pre>
*
* <h3>2 bytes length field at offset 0, strip header</h3>
*
* Because we can get the length of the content by calling
* {@link ByteBuf#readableBytes()}, you might want to strip the length
* field by specifying <tt>initialBytesToStrip</tt>.  In this example, we
* specified <tt>2</tt>, that is same with the length of the length field, to
```

```
* strip the first two bytes.
* <pre>
* lengthFieldOffset   = 0
* lengthFieldLength   = 2
* lengthAdjustment    = 0
* <b>initialBytesToStrip</b> = <b>2</b> (= the length of the Length field)
*
* BEFORE DECODE (14 bytes)         AFTER DECODE (12 bytes)
* +--------+----------------+      +----------------+
* | Length | Actual Content |----->| Actual Content |
* | 0x000C | "HELLO, WORLD" |      | "HELLO, WORLD" |
* +--------+----------------+      +----------------+
 * </pre>
*
* <h3>2 bytes length field at offset 0, do not strip header, the length field
*     represents the length of the whole message</h3>
*
* In most cases, the length field represents the length of the message body
* only, as shown in the previous examples.  However, in some protocols, the
* length field represents the length of the whole message, including the
* message header.  In such a case, we specify a non-zero
* <tt>lengthAdjustment</tt>.  Because the length value in this example message
* is always greater than the body length by <tt>2</tt>, we specify <tt>-2</tt>
* as <tt>lengthAdjustment</tt> for compensation.
* <pre>
* lengthFieldOffset   =  0
* lengthFieldLength   =  2
* <b>lengthAdjustment</b>    = <b>-2</b> (= the length of the Length field)
* initialBytesToStrip =  0
*
* BEFORE DECODE (14 bytes)         AFTER DECODE (14 bytes)
* +--------+----------------+      +--------+----------------+
* | Length | Actual Content |----->| Length | Actual
 Content |
* | 0x000E | "HELLO, WORLD" |      | 0x000E | "HELLO, WORLD" |
* +--------+----------------+      +--------+----------------+
* </pre>
*
* <h3>3 bytes length field at the end of 5 bytes header, do not strip header</h3>
*
* The following message is a simple variation of the first example.  An extra
* header value is prepended to the message.  <tt>lengthAdjustment</tt> is zero
* again because the decoder always takes the length of the prepended data into
* account during frame length calculation.
* <pre>
* <b>lengthFieldOffset</b>   = <b>2</b> (= the length of Header 1)
* <b>lengthFieldLength</b>   = <b>3</b>
* lengthAdjustment    = 0
```

```
* initialBytesToStrip = 0
*
* BEFORE DECODE (17 bytes)                 AFTER DECODE (17 bytes)
* +----------+----------+----------------+      +----------+----------+----------------+
* | Header 1 |  Length  | Actual Content |----->| Header 1 |  Length  | Actual Content |
* |  0xCAFE  | 0x00000C | "HELLO, WORLD" |      |
  0xCAFE  | 0x00000C | "HELLO, WORLD" |
* +----------+----------+----------------+      +----------+----------+----------------+
* </pre>
*
* <h3>3 bytes length field at the beginning of 5 bytes header, do not strip header</h3>
*
* This is an advanced example that shows the case where there is an extra
* header between the length field and the message body.  You have to specify a
* positive <tt>lengthAdjustment</tt> so that the decoder counts the extra
* header into the frame length calculation.
* <pre>
* lengthFieldOffset   = 0
* lengthFieldLength   = 3
* <b>lengthAdjustment</b>    = <b>2</b> (= the length of Header 1)
* initialBytesToStrip = 0
*
* BEFORE DECODE (17 bytes)                 AFTER DECODE (17 bytes)
* +----------+----------+----------------+      +----------+----------+----------------+
* |  Length  | Header 1 | Actual Content |----->|  Length  | Header 1 | Actual Content |
* | 0x00000C |  0xCAFE  | "HELLO, WORLD" |      | 0x00000C |  0xCAFE  | "HELLO,
 WORLD" |
* +----------+----------+----------------+      +----------+----------+----------------+
* </pre>
*
* <h3>2 bytes length field at offset 1 in the middle of 4 bytes header,
*     strip the first header field and the length field</h3>
*
* This is a combination of all the examples above.  There are the prepended
* header before the length field and the extra header after the length field.
* The prepended header affects the <tt>lengthFieldOffset</tt> and the extra
* header affects the <tt>lengthAdjustment</tt>.  We also specified a non-zero
* <tt>initialBytesToStrip</tt> to strip the length field and the prepended
* header from the frame.  If you don't want to strip the prepended header, you
* could specify <tt>0</tt> for <tt>initialBytesToSkip</tt>.
* <pre>
* lengthFieldOffset   = 1 (= the length of HDR1)
* lengthFieldLength   = 2
* <b>lengthAdjustment</b>    = <b>1</b> (= the length of HDR2)
* <b>initialBytesToStrip</b> = <b>3</b> (= the length of HDR1 + LEN)
 *
* BEFORE DECODE (16 bytes)                 AFTER DECODE (13 bytes)
* +------+--------+------+----------------+      +------+----------------+
```

* | HDR1 | Length | HDR2 | Actual Content |----->| HDR2 | Actual Content |
* | 0xCA | 0x000C | 0xFE | "HELLO, WORLD" | | 0xFE | "HELLO, WORLD" |
* +------+--------+------+----------------+   +------+----------------+
* </pre>
*
* <h3>2 bytes length field at offset 1 in the middle of 4 bytes header,
*   strip the first header field and the length field, the length field
*   represents the length of the whole message</h3>
*
* Let's give another twist to the previous example. The only difference from
* the previous example is that the length field represents the length of the
* whole message instead of the message body, just like the third example.
* We have to count the length of HDR1 and Length into <tt>lengthAdjustment</tt>.
* Please note that we don't need to take the length of HDR2 into account
* because
 the length field already includes the whole header length.
* <pre>
* lengthFieldOffset   = 1
* lengthFieldLength   = 2
* lengthAdjustment   = -3 (= the length of HDR1 + LEN, negative)
* initialBytesToStrip = 3
*
* BEFORE DECODE (16 bytes)   AFTER DECODE (13 bytes)
* +------+--------+------+----------------+   +------+----------------+
* | HDR1 | Length | HDR2 | Actual Content |----->| HDR2 | Actual Content |
* | 0xCA | 0x0010 | 0xFE | "HELLO, WORLD" | | 0xFE | "HELLO, WORLD" |
* +------+--------+------+----------------+   +------+----------------+
* </pre>
* @see LengthFieldPrepender
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/LengthFieldBasedFrameDecoder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations

* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheRequestEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyDataFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/AddressedEnvelope.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/FullHttpRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/ProgressiveFuture.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/MemcacheMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/DefaultSpdyGoAwayFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/DefaultUdtServerChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/MessageSizeEstimator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ConnectTimeoutException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelId.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/MemcacheObject.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/FullBinaryMemcacheRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockZlibEncoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/ProgressivePromise.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/ByteBufHolder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/UdtChannelOption.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/ScheduledFuture.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/Future.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/group/ChannelMatchers.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/ReferenceCounted.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/RecyclableArrayList.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/DefaultProgressivePromise.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/bootstrap/ChannelFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/GenericFutureListener.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/AdvancedLeakAwareByteBuf.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/UnreleasableByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelProgressiveFuture.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/DefaultFullBinaryMemcacheResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyHeaders.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdySessionHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/ResourceLeak.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/ResourceLeakDetector.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheRequestDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5CommandType.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/ReferenceCountUtil.java
*

/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockJZlibEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketClientProtocolHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/ConcurrentSet.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Crc32c.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/helloworld/HttpHelloWorldServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyStreamStatus.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/AbstractReferenceCountedByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5CommandStatus.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockRawEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/ByteBufProcessor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/oio/DefaultOioServerSocketChannelConfig.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/CompleteFuture.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/AbstractMemcacheObjectAggregator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/AbstractBinaryMemcacheMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheResponseEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksSubnegotiationVersion.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/AbstractEventLoopGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/AppendableCharSequence.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/PlatformDependent0.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/GenericProgressiveFutureListener.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdySettingsFrame.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheResponseStatus.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/DefaultSpdyDataFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksProtocolVersion.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/DefaultLastMemcacheContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/DefaultSpdyWindowUpdateFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/MemcacheContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyWindowUpdateFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/ReadOnlyIterator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/DefaultThreadFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyRstStreamFrame.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/PendingWrite.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheObjectAggregator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/AbstractFuture.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/SimpleLeakAwareByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/AbstractMemcacheObjectDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksCmdStatus.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/rxtx/RxtxClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksCmdType.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksResponseType.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksRequestType.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/AbstractDerivedByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/oio/OioSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelProgressiveFutureListener.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/LastMemcacheContent.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/memcache/binary/DefaultBinaryMemcacheRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/FullMemcacheMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheServerCodec.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/oio/OioServerSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyCodecUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyGoAwayFrame.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/AbstractEventExecutorGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/ConstantPool.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/DefaultSpdySynStreamFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/group/ChannelMatcher.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/DefaultFullHttpRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketProtocolHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/Promise.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheResponseDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/group/ChannelGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/PromiseTask.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/ImmediateEventExecutor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/FutureListener.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/worldclock/WorldClockProtocol.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/FullBinaryMemcacheResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/Native.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/ResourceLeakException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/DefaultSpdyRstStreamFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/ReadOnlyUnsafeDirectByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/DefaultFutureListeners.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/ScheduledFutureTask.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/DefaultByteBufHolder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/ImmediateExecutor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/rxtx/RxtxClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/AbstractReferenceCounted.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/ThreadPerTaskExecutor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/NoOpTypeParameterMatcher.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/UdtServerChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthStatus.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksAddressType.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/package-info.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/group/DefaultChannelGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelProgressivePromise.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/ComposedLastHttpContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/AbstractEventExecutor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyHttpDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/FullHttpMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/DefaultPromise.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5AuthMethod.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/Recycler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/DefaultSpdyStreamFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/TypeParameterMatcher.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/EmptyByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketFrameDecoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketFrameAggregator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/SslHandshakeCompletionEvent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyHeadersFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DefaultChannelProgressivePromise.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DefaultChannelId.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/DefaultSpdyHeadersFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/group/ChannelGroupException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyStreamFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/EmptyArrays.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/memcache/binary/AbstractBinaryMemcacheDecoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5AddressType.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/DefaultMemcacheContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdySynReplyFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/DefaultSpdySynReplyFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/DefaultSpdyPingFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyPingFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/JdkZlibDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdySynStreamFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksAuthScheme.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PooledUnsafeDirectByteBuf.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyVersion.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/WebSocketClientProtocolHandshakeHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/WrappedByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/SimpleChannelInboundHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheOpcodes.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/AbstractMemcacheObject.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdySessionStatus.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelHandlerAdapter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/cors/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DefaultAddressedEnvelope.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketFrameEncoder.java
*
 /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/memcache/binary/AbstractBinaryMemcacheEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/FixedCompositeByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/SocksVersion.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksAuthStatus.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/helloworld/HttpHelloWorldServerInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/DefaultSpdyHeaders.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/DefaultFullHttpResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/Version.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/ReadOnlyByteBufferBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksMessageType.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/nio/SelectedSelectionKeySet.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/package-info.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/memcache/binary/DefaultBinaryMemcacheResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/FullHttpResponse.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/memcache/binary/DefaultFullBinaryMemcacheRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/AbstractMemcacheObjectEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DefaultMessageSizeEstimator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/oio/DefaultOioSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyHttpCodec.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelOutboundBuffer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/memcache/binary/BinaryMemcacheClientCodec.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlFrameDecoder.java
No license file was found, but licenses were detected in source scan.

/*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.

*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/BaseMpscLinkedAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/MpscUnboundedXaddChunk.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/SpscChunkedArrayQueue.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/MpscChunkedArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/maps/NonBlockingHashMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/SupportsIterator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/SpscLinkedQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/MessagePassingQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/util/Pow2.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/MpscGrowableArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/MpscUnboundedXaddArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/MpscChunkedAtomicArrayQueue.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/MpscAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/ConcurrentCircularArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/MpscUnboundedArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/MpmcArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/SpscGrowableAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/util/UnsafeJvmInfo.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/MpmcUnboundedXaddChunk.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/BaseSpscLinkedAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/MessagePassingQueueUtil.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/BaseMpscLinkedArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/util/InternalAPI.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/spec/Preference.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/BaseSpscLinkedArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/util/RangeUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/QueueFactory.java
* /netty-all-4-1-49-final-sources-3-

jar/io/netty/util/internal/shaded/org/jctools/maps/NonBlockingHashMapLong.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/AtomicReferenceArrayQueue.java
*
/netty-all-4-1-49-final-sources-3-
jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/SpscChunkedAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/SpscUnboundedAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/util/UnsafeRefArrayAccess.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/util/UnsafeLongArrayAccess.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/SequencedAtomicReferenceArrayQueue.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/MpmcAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/MpscCompoundQueue.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/util/internal/shaded/org/jctools/queues/MpmcUnboundedXaddArrayQueue.java
*
/netty-all-4-1-49-final-sources-3-
jar/io/netty/util/internal/shaded/org/jctools/queues/SpscUnboundedArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/MpscLinkedQueue.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/MpscGrowableAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/maps/NonBlockingHashSet.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/MpscUnboundedAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/util/PortableJvmInfo.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/maps/ConcurrentAutoTable.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/BaseLinkedQueue.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/spec/Ordering.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/util/internal/shaded/org/jctools/queues/ConcurrentSequencedCircularArrayQueue.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/util/internal/shaded/org/jctools/maps/NonBlockingIdentityHashMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/LinkedQueueNode.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/SpscArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/util/UnsafeAccess.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/maps/AbstractEntry.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/util/internal/shaded/org/jctools/queues/spec/ConcurrentQueueSpec.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/SpmcArrayQueue.java
*
/netty-all-4-1-49-final-sources-3-
jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/SpscLinkedAtomicQueue.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/BaseLinkedAtomicQueue.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/maps/NonBlockingSetInt.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/SpscGrowableArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/SpscAtomicArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/IndexedQueueSizeUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/MpscBlockingConsumerArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/MpscLinkedAtomicQueue.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/AtomicQueueFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/LinkedQueueAtomicNode.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/MpscArrayQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/shaded/org/jctools/queues/atomic/SpmcAtomicArrayQueue.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2020 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/frame/client/Http2ClientStreamFrameResponseHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/search/KmpSearchProcessorFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/search/MultiSearchProcessor.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/search/SearchProcessor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/search/AbstractSearchProcessorFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/search/MultiSearchProcessorFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/search/AbstractMultiSearchProcessorFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/frame/client/Http2FrameClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/search/BitapSearchProcessorFactory.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/frame/client/Http2ClientFrameInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/search/AhoCorasicSearchProcessorFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/search/SearchProcessorFactory.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
```

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/traffic/GlobalChannelTrafficShapingHandler.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version
* 2.0 (the "License"); you may not use this file except in compliance with the
* License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/
```

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/flow/FlowControlHandler.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2015 The Netty Project
```

*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/CharSequenceMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/pool/AbstractChannelPoolHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollEventArray.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/package-info.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/SingletonDnsServerAddresses.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/HashingStrategy.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollServerDomainSocketChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DatagramDnsQueryEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/UnsafeByteBufUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PooledUnsafeHeapByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/DefaultNameResolver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/ServerDomainSocketChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/RotationalDnsServerAddresses.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/rtsp/RtspEncoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/CombinedHttpHeaders.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/AbstractDnsRecord.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/SocksPortUnificationServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/protobuf/ProtobufVarint32FrameDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/PriorityQueueNode.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/UnpooledUnsafeHeapByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/DomainSocketReadMode.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/tiles/Html.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/cookie/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsQuestion.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsMessageUtil.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/cookie/DefaultCookie.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/UnpooledDuplicatedByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/tiles/FallbackRequestHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsNameResolverBuilder.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/DomainSocketAddress.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/DatagramSocketAddress.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpScheme.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/tiles/ImageCache.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollRecvByteAllocatorHandle.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5AddressEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/CompositeNameResolver.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/AbstractDnsMessage.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/example/http2/helloworld/server/HelloWorldHttp2HandlerBuilder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/TcpMd5Util.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/cookie/ClientCookieDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/DefaultPriorityQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/cookie/CookieEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/ApplicationProtocolNames.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/DomainMappingBuilder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsRecordEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/InetSocketAddressResolver.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/FileDescriptor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsNameResolverException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/protobuf/ProtobufDecoderNano.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsResponseCode.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsServerAddressStream.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/tiles/HttpServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PoolChunkMetric.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DefaultMaxBytesRecvByteBufAllocator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/AddressResolver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/pool/ChannelPoolHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/MaxMessagesRecvByteBufAllocator.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DefaultDnsRecordEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/AbstractEpollStreamChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DefaultDnsRawRecord.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpExpectationFailedEvent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PoolChunkListMetric.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/pool/ChannelPoolMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/HostsFileEntriesResolver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DefaultDnsResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DefaultDnsQuestion.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/Errors.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2ConnectionHandlerBuilder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/SslContextBuilder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/tiles/Http2OrHttpHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollDomainSocketChannelConfig.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/InetNameResolver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollMode.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PoolSubpageMetric.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/UnpooledSlicedByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/LongCounter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/tiles/Launcher.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/ProtocolDetectionState.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/AbstractScheduledEventExecutor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/pool/ChannelHealthChecker.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/DomainSocketChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DatagramDnsQuery.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/ClientAuth.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/cookie/ClientCookieEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/AsyncMapping.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/HeapByteBufUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DefaultDnsRecordDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/AbstractEpollServerChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/tiles/Http2Server.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PoolArenaMetric.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/sctp/multihoming/SctpMultiHomingEchoServer.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslJavaxX509Certificate.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/tiles/Http1RequestHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DatagramDnsResponseEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/Socket.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/cookie/Cookie.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslSessionTicketKey.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DatagramDnsResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/NativeInetAddress.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DatagramDnsQueryDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsRawRecord.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsRecordType.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/rtsp/RtspDecoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/AbstractAddressResolver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/ApplicationProtocolNegotiationHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DefaultMaxMessagesRecvByteBufAllocator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/AbstractUnsafeSwappedByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsOpCode.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/MaxBytesRecvByteBufAllocator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/UnsupportedValueConverter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsRecord.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsQuery.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsRecordDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsSection.java
*

/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/cookie/ServerCookieEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/DefaultAddressResolverGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DefaultDnsServerAddresses.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/DomainSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/protobuf/ProtobufDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/UnixChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/pool/SimpleChannelPool.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/HeadersUtils.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/cookie/CookieUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/sctp/multihoming/SctpMultiHomingEchoClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/ApplicationProtocolAccessor.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/ShuffledDnsServerAddressStream.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/AbstractHttp2ConnectionHandlerBuilder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/pool/FixedChannelPool.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/cookie/CookieHeaderNames.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/cookie/ServerCookieDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/protobuf/ProtobufEncoderNano.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/cookie/CookieDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollServerChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DefaultDnsQuery.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollDomainSocketChannel.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5AddressDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/CookieUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/tiles/Http2RequestHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/pool/AbstractChannelPoolMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/pool/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsQueryContextManager.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/DefaultHostsFileEntriesResolver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DatagramDnsResponseDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/protobuf/ProtobufEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollRecvByteAllocatorStreamingHandle.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/channel/pool/ChannelPool.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/ProtocolDetectionResult.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/protobuf/ProtobufVarint32LengthFieldPrepender.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/EmptyHttpHeaders.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/SequentialDnsServerAddressStream.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/HostsFileParser.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/HttpToHttp2ConnectionHandlerBuilder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/ThreadProperties.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpUtil.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 The Netty Project

*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
// (BSD License: http://www.opensource.org/licenses/bsd-license)
// All rights reserved.
// Redistribution and use in source and binary forms, with or
// * Redistributions of source code must retain the above
// copyright notice, this list of conditions and the
// following disclaimer.
// * Redistributions
 in binary form must reproduce the above
// following disclaimer in the documentation and/or other
// * Neither the name of the Webbit nor the names of

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocket08FrameDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocket13FrameDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocket07FrameDecoder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
    * Set the {@code TCP_MD5SIG} option on the socket. See {@code linux/tcp.h} for more details.
    * Keys can only be set on, not read to prevent a potential leak, as they are confidential.

```
    * Allowing them being read would mean anyone with access to the channel could get them.

  */
/**
    * Set the {@code TCP_QUICKACK} option on the socket. See <a
href="http://linux.die.net/man/7/tcp">TCP_QUICKACK</a>
    * for more details.
    */
```

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollSocketChannelConfig.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
    * Set the {@code TCP_MD5SIG} option on the socket. See {@code linux/tcp.h} for more details.
    * Keys can only be set on, not read to prevent a potential leak, as they are confidential.
    * Allowing them being read would mean anyone with access to the channel could get them.

  */
```

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollServerSocketChannelConfig.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
```

* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
* Copyright (c) 2004-2011 QOS.ch
* All rights reserved.
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without
limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be
* included in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
* NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
* LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
* OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
* WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/InternalLogger.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/JdkLogger.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/Log4JLogger.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/CommonsLogger.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2020 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/stomp/websocket/StompWebSocketChatServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/search/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/logging/ByteBufFormat.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/example/stomp/websocket/StompWebSocketChatServerInitializer.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/haproxy/HAProxyMessageEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/haproxy/HAProxyServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/stomp/websocket/StompSubscription.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/stomp/websocket/StompWebSocketClientPageHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/stomp/websocket/StompChatHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/stomp/websocket/StompWebSocketProtocolCodec.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/SslHandshakeTimeoutException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/address/ResolveAddressHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/DomainWildcardMappingBuilder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/haproxy/HAProxyHandler.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/example/stomp/websocket/StompVersion.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/haproxy/HAProxyClient.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
// (BSD License: http://www.opensource.org/licenses/bsd-license)
// All rights reserved.
// Redistribution and use in source and binary forms, with or

// * Redistributions of source code must retain the above
// copyright notice, this list of conditions and the
// following disclaimer.
// * Redistributions
 in binary form must reproduce the above
// following disclaimer in the documentation and/or other
// * Neither the name of the Webbit nor the names of

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocket07FrameEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocket08FrameEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocket13FrameEncoder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2EmptyDataFrameConnectionDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2SettingsReceivedConsumer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2ControlFrameLimitEncoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2EmptyDataFrameListener.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2018 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License

* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/ResourcesUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/ByteProcessorUtils.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/InlineCommandRedisMessage.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/**
* Handles an I/O event or intercepts an I/O operation, and forwards it to its next handler in
* its {@link ChannelPipeline}.
*
* <h3>Sub-types</h3>
*
* {@link ChannelHandler} itself does not provide many methods, but you usually have to implement one of its subtypes:
*
* {@link
 ChannelInboundHandler} to handle inbound I/O events, and
* {@link ChannelOutboundHandler} to handle outbound I/O operations.
*
*
*
* Alternatively, the following adapter classes are provided for your convenience:
*
* {@link ChannelInboundHandlerAdapter} to handle inbound I/O events,
* {@link ChannelOutboundHandlerAdapter} to handle outbound I/O operations, and
* {@link ChannelDuplexHandler} to handle both inbound and outbound events
*

```
* </p>
* <p>
* For more information, please refer to the documentation of each subtype.
* </p>
*
* <h3>The context object</h3>
* <p>
* A {@link ChannelHandler} is provided with a {@link ChannelHandlerContext}
* object.  A {@link ChannelHandler} is supposed to interact with the
* {@link ChannelPipeline} it belongs to via a context object.  Using the
* context object, the {@link ChannelHandler} can pass events upstream or
* downstream, modify the pipeline dynamically,
 or store the information
* (using {@link AttributeKey}s) which is specific to the handler.
*
* <h3>State management</h3>
*
* A {@link ChannelHandler} often needs to store some stateful information.
* The simplest and recommended approach is to use member variables:
* <pre>
* public interface Message {
*     // your methods here
* }
*
* public class DataServerHandler extends {@link SimpleChannelInboundHandler}&lt;Message&gt; {
*
*     <b>private boolean loggedIn;</b>
*
*     {@code @Override}
*     public void channelRead0({@link ChannelHandlerContext} ctx, Message message) {
*         if (message instanceof LoginMessage) {
*             authenticate((LoginMessage) message);
*             <b>loggedIn = true;</b>
*         } else (message instanceof GetDataMessage) {
*             if (<b>loggedIn</b>) {
*                 ctx.writeAndFlush(fetchSecret((GetDataMessage) message));
*             } else {
*                 fail();
*             }
*         }
 *     }
*     ...
* }
* </pre>
* Because the handler instance has a state variable which is dedicated to
* one connection, you have to create a new handler instance for each new
* channel to avoid a race condition where a unauthenticated client can get
* the confidential information:
```

```
* <pre>
* // Create a new handler instance per channel.
* // See {@link ChannelInitializer#initChannel(Channel)}.
* public class DataServerInitializer extends {@link ChannelInitializer}&lt;{@link Channel}&gt; {
*     {@code @Override}
*     public void initChannel({@link Channel} channel) {
*         channel.pipeline().addLast("handler", <b>new DataServerHandler()</b>);
*     }
* }
*
* </pre>
*
* <h4>Using {@link AttributeKey}s</h4>
*
* Although it's recommended to use member variables to store the state of a
* handler, for some reason you might not want to create many handler instances.
* In such a case, you can use {@link AttributeKey}s which is provided by
* {@link ChannelHandlerContext}:
 * <pre>
* public interface Message {
*     // your methods here
* }
*
* {@code @Sharable}
* public class DataServerHandler extends {@link SimpleChannelInboundHandler}&lt;Message&gt; {
*     private final {@link AttributeKey}&lt;{@link Boolean}&gt; auth =
*           {@link AttributeKey#valueOf(String) AttributeKey.valueOf("auth")};
*
*     {@code @Override}
*     public void channelRead({@link ChannelHandlerContext} ctx, Message message) {
*         {@link Attribute}&lt;{@link Boolean}&gt; attr = ctx.attr(auth);
*         if (message instanceof LoginMessage) {
*             authenticate((LoginMessage) o);
*             <b>attr.set(true)</b>;
*         } else (message instanceof GetDataMessage) {
*             if (<b>Boolean.TRUE.equals(attr.get())</b>) {
*                 ctx.writeAndFlush(fetchSecret((GetDataMessage) o));
*             } else {
*                 fail();
*             }
*         }
*     }
*     ...
* }
* </pre>
* Now that the state
 of the handler is attached to the {@link ChannelHandlerContext}, you can add the
* same handler instance to different pipelines:
```

```
* <pre>
* public class DataServerInitializer extends {@link ChannelInitializer}&lt;{@link Channel}&gt; {
*
*     private static final DataServerHandler <b>SHARED</b> = new DataServerHandler();
*
*     {@code @Override}
*     public void initChannel({@link Channel} channel) {
*         channel.pipeline().addLast("handler", <b>SHARED</b>);
*     }
* }
* </pre>
*
*
* <h4>The {@code @Sharable} annotation</h4>
* <p>
* In the example above which used an {@link AttributeKey},
* you might have noticed the {@code @Sharable} annotation.
* <p>
* If a {@link ChannelHandler} is annotated with the {@code @Sharable}
* annotation, it means you can create an instance of the handler just once and
* add it to one or more {@link ChannelPipeline}s multiple times without
* a race condition.
* <p>
* If this annotation is not specified, you have to create
 a new handler
* instance every time you add it to a pipeline because it has unshared state
* such as member variables.
* <p>
* This annotation is provided for documentation purpose, just like
* <a href="http://www.javaconcurrencyinpractice.com/annotations/doc/">the JCIP annotations</a>.
*
* <h3>Additional resources worth reading</h3>
* <p>
* Please refer to the {@link ChannelHandler}, and
* {@link ChannelPipeline} to find out more about inbound and outbound operations,
* what fundamental differences they have, how they flow in a  pipeline,  and how to handle
* the operation in your application.
*/
```

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelHandler.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
```

* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
//The MIT License
//Permission is hereby granted, free of charge, to any person obtaining a copy
//of this software and associated documentation files (the "Software"), to deal
//to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
//furnished to do so, subject to the following
 conditions:
//The above copyright notice and this permission notice shall be included in
//all copies or substantial portions of the Software.

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/websocketx/client/WebSocketClientHandler.java
No license file was found, but licenses were detected in source scan.

<!--
 ~ Copyright 2012 The Netty Project
 ~
 ~ The Netty Project licenses this file to you under the Apache License,
 ~ version 2.0 (the "License"); you may not use this file except in compliance
 ~ with the License. You may obtain a copy of the License at:
 ~
 ~   http://www.apache.org/licenses/LICENSE-2.0
 ~
 ~ Unless required by applicable law or agreed to in writing, software
 ~ distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
 ~ WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
 ~ License for the specific language governing permissions and limitations
 ~ under the License.
 -->

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/META-INF/maven/io.netty/netty-all/pom.xml
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance

* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/ConstantTimeUtils.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/smtp/SmtpRequests.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/BsdSocket.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelInboundInvoker.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/ReferenceCountedOpenSslEngine.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/ThrowableUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2SettingsFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/ErrorsStaticallyReferencedJniMethods.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/bootstrap/AbstractBootstrapConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/LinuxSocket.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/AbstractPooledDerivedByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/ReferenceCountedOpenSslClientContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/DateFormatter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/UnaryPromiseNotifier.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/util/X509TrustManagerWrapper.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/example/redis/RedisClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/NonStickyEventExecutorGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/string/LineSeparator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2PingFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/DelegatingSslContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DefaultSelectStrategy.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/FileUploadUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueChannelOption.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/example/http2/helloworld/multiplex/server/Http2ServerInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/UnorderedThreadPoolEventExecutor.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/DatagramPacketEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/PreferHeapByteBufAllocator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2FrameStreamVisitor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/PemValue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/smtp/LastSmtpContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/CodecOutputList.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/Java8SslUtils.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DefaultSelectStrategyFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/AbstractKQueueChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/haproxy/HAProxyTLV.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2Frame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/WrappedCompositeByteBuf.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueDatagramChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/NoopDnsCache.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2PingFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/OrderedEventExecutor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/BooleanSupplier.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/RejectedExecutionHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsOptEcsRecord.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/MacAddressUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/NativeLibraryUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2DataFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/NativeStaticallyReferencedJniMethods.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/CertificateRequestedCallback.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/PromiseCombiner.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/Native.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/smtp/DefaultSmtpRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2HeadersFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/flush/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/smtp/SmtpResponseDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/AbstractUnpooledSlicedByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/Limits.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslCertificateException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2FrameStream.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueServerSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/SocketUtils.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/EventExecutorChooserFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DefaultDnsOptEcsRecord.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2StreamFrameToHttpObjectCodec.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueServerDomainSocketChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DefaultDnsPtrRecord.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/bootstrap/ServerBootstrapConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/RejectedExecutionHandlers.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/ReadOnlyHttp2Headers.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2FrameCodec.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/PemEncoded.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/haproxy/HAProxySSLTLV.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2ResetFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueServerSocketChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/smtp/package-info.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2GoAwayFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpServerKeepAliveHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueSocketChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DefaultDnsCache.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/SocketWritableByteChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/PemX509Certificate.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PooledDuplicatedByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/smtp/DefaultLastSmtpContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/smtp/SmtpResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/smtp/DefaultSmtpResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/smtp/SmtpRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/PeerCredentials.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/Log4J2Logger.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/smtp/SmtpContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueEventArray.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2WindowUpdateFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/ByteBufChecksum.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/AbstractHttp2StreamFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/PromiseNotificationUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/IntSupplier.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueStaticallyReferencedJniMethods.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/RoundRobinDnsAddressResolverGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/SelectStrategy.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2SettingsFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/AdvancedLeakAwareCompositeByteBuf.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/util/ResourceLeakDetectorFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/Log4J2LoggerFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PooledSlicedByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/WrappedUnpooledUnsafeDirectByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslKeyMaterialManager.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/frame/server/Http2Server.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/InflightNameResolver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/AbstractDnsOptPseudoRrRecord.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2ResetFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueEventLoopGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/AbstractKQueueStreamChannel.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueDatagramChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueRecvByteAllocatorHandle.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/CompressionUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/smtp/DefaultSmtpContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2WindowUpdateFrame.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/AbstractKQueueServerChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2MultiplexCodec.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/SessionTicketKey.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/flush/FlushConsolidationHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2FrameStreamException.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/RoundRobinInetAddressResolver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/ReferenceCountedOpenSslContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/group/VoidChannelGroupFuture.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2HeadersFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/PemPrivateKey.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/frame/server/Http2ServerInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/bootstrap/BootstrapConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueDomainSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueEventLoop.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsOptPseudoRecord.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/smtp/SmtpUtils.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/multiplex/server/Http2Server.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2StreamFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/AcceptFilter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2DataFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/SimpleLeakAwareCompositeByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/InboundHttpToHttp2Adapter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/DomainNameMappingBuilder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/UnstableApi.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/flow/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/UnpooledUnsafeNoCleanerDirectByteBuf.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelOutboundInvoker.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/LimitsStaticallyReferencedJniMethods.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/WriteBufferWaterMark.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/SelectStrategyFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueServerChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/dns/DnsPtrRecord.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/string/LineEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketChunkedInput.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/ResourceLeakTracker.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsCache.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/KQueueDomainSocketChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2ChannelDuplexHandler.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/ReferenceCountedOpenSslServerContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/kqueue/NativeLongArray.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/DuplexChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2GoAwayFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/smtp/SmtpCommand.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/DatagramPacketDecoder.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/DefaultEventExecutorChooserFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/smtp/SmtpRequestEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/OutOfDirectMemoryError.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version
* 2.0 (the "License"); you may not use this file except in compliance with the
* License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/cors/CorsConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/cors/CorsHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/cors/OkResponseHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
// Try the OpenJDK's proprietary implementation.

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/util/SelfSignedCertificate.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2011 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
```

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/SctpNotificationHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/SctpChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/worldclock/WorldClockProtocol.proto
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/SctpServerChannel.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/nio/NioSctpChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/DefaultSctpChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/SctpServerChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/traffic/AbstractTrafficShapingHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/nio/NioSctpServerChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/SctpChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/SctpMessage.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/
```

Found in path(s):

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/RedisMessageType.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/LastBulkStringRedisContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/redis/RedisClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/RedisDecoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/RedisMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/IntegerRedisMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/DefaultBulkStringRedisContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/multiplex/server/Http2OrHttpHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/AbstractStringRedisMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/BulkStringRedisContent.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/example/http2/helloworld/multiplex/server/HelloWorldHttp2Handler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/FixedRedisMessagePool.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/RedisArrayAggregator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/ArrayRedisMessage.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/ErrorRedisMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/RedisConstants.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/frame/server/Http2OrHttpHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/RedisCodecUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/RedisMessagePool.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/example/http2/helloworld/frame/server/HelloWorldHttp2Handler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/FullBulkStringRedisMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/DefaultLastBulkStringRedisContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/SimpleStringRedisMessage.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/RedisEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/RedisCodecException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/BulkStringHeaderRedisMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/RedisBulkStringAggregator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/redis/ArrayHeaderRedisMessage.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the

* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/UnsafeDirectSwappedByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/CleanerJava6.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DefaultChannelHandlerContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/FastThreadLocalThread.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/UnsafeHeapSwappedByteBuf.java
No license file was found, but licenses were detected in source scan.

/*
  Stomp Over WebSocket http://www.jmesnil.net/stomp-websocket/doc/ | Apache License V2.0
  Copyright (C) 2010-2013 [Jeff Mesnil](http://jmesnil.net/)
  Copyright (C) 2012 [FuseSource, Inc.](http://fusesource.com)
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/stomp/websocket/stomp.js
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DelegatingDecompressorFrameListener.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/collection/IntCollections.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/collection/ByteObjectMap.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/util/collection/LongObjectHashMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/collection/ByteObjectHashMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2FrameReader.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2Connection.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/collection/ShortCollections.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2Settings.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2LocalFlowController.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/HttpToHttp2ConnectionHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2FrameTypes.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2ConnectionHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/CompressorHttp2ConnectionEncoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2HeadersEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2Exception.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2FrameAdapter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2RemoteFlowController.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2NoMoreStreamIdsException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2FrameWriter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/collection/CharCollections.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/collection/LongCollections.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/ObjectUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2FrameListenerDecorator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/package-info.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2Headers.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2DataWriter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/collection/ShortObjectHashMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpClientUpgradeHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2LocalFlowController.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2HeadersEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2FrameWriter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/server/Http2OrHttpHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2CodecUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2FlowController.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/util/collection/CharObjectMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/server/HelloWorldHttp2Handler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/DefaultHeaders.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2FrameSizePolicy.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/EmptyHeaders.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttQoS.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2RemoteFlowController.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2ConnectionEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2ServerUpgradeCodec.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/collection/CharObjectHashMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/collection/IntObjectMap.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2LifecycleManager.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/collection/LongObjectMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/client/HttpResponseHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2EventAdapter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2Flags.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2Headers.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/collection/ByteCollections.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpServerUpgradeHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/InboundHttp2ToHttpAdapter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2ConnectionDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2Connection.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2HeadersDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/Headers.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2ConnectionDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/client/Http2SettingsHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2ConnectionAdapter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2FrameListener.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/client/Http2ClientInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2Stream.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/Http2ExampleUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2ConnectionEncoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/util/collection/ShortObjectMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/EmptyHttp2Headers.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2Error.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2FrameReader.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/client/Http2Client.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2HeadersDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2ClientUpgradeCodec.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/collection/IntObjectHashMap.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/Cleaner.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/CleanerJava9.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/FastThreadLocalRunnable.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/*
* Written by Robert Harder and released to the public domain, as explained at
* http://creativecommons.org/licenses/publicdomain
*/
/**
* Enumeration of supported Base64 dialects.
* <p>
* The internal lookup tables in this class has been derived from
* <a href="http://iharder.sourceforge.net/current/java/base64/">Robert
 Harder's Public Domain
* Base64 Encoder/Decoder</a>.
*/
```

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/base64/Base64Dialect.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
```

```
* under the License.
*/
/*
* Written by Robert Harder and released to the public domain, as explained at
* http://creativecommons.org/licenses/publicdomain
*/
/**
* Utility class for {@link ByteBuf} that encodes and decodes to and from
* <a href="http://en.wikipedia.org/wiki/Base64">Base64</a> notation.
* <p>
*
 The encoding and decoding algorithm in this class has been derived from
* <a href="http://iharder.sourceforge.net/current/java/base64/">Robert Harder's Public Domain
* Base64 Encoder/Decoder</a>.
*/
```

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/base64/Base64.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
```

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PooledHeapByteBuf.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2011 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
```

* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/DefaultSctpServerChannelConfig.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version
* 2.0 (the "License"); you may not use this file except in compliance with the
* License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/ocsp/OcspClientExample.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/ocsp/Digester.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/ocsp/OcspServerExample.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/ocsp/OcspUtils.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/example/ocsp/OcspRequestBuilder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either
express
* or implied. See the License for the specific language governing permissions and limitations under

* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/AbstractCoalescingBufferQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2ConnectionPrefaceAndSettingsFrameWrittenEvent.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/*
* Written by Doug Lea with assistance from members of JCP JSR-166
* Expert Group and released to the public domain, as explained at
* http://creativecommons.org/publicdomain/zero/1.0/
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/ThreadLocalRandom.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2016 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.

```
*/
/*
*  Licensed to the Apache Software Foundation (ASF) under one or more
*  contributor license agreements.  See the NOTICE file distributed with
*  this work for additional information regarding copyright ownership.
*  The ASF licenses this file to You under the Apache License, Version 2.0
 *  (the "License"); you may not use this file except in compliance with
*  the License.  You may obtain a copy of the License at
*
*      http://www.apache.org/licenses/LICENSE-2.0
*
*  Unless required by applicable law or agreed to in writing, software
*  distributed under the License is distributed on an "AS IS" BASIS,
*  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
*  See the License for the specific language governing permissions and
*  limitations under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/SSLContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/Library.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/SSL.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/Buffer.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2018 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/NoopDnsCnameCache.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslKeyMaterial.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsAddressDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DefaultDnsCnameCache.java
*
```

/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslSession.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslTlsv13X509ExtendedTrustManager.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsAddressResolveContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/Cache.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DefaultAuthoritativeDnsServerCache.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/AuthoritativeDnsServerCacheAdapter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/SignatureAlgorithmConverter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslPrivateKey.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslX509TrustManagerWrapper.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/DefaultOpenSslKeyMaterial.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslKeyMaterialProvider.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/NoopAuthoritativeDnsServerCache.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/Buffer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslCachingKeyMaterialProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/ExtendedOpenSslSession.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/AuthoritativeDnsServerCache.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/PreferredDirectByteBufAllocator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsRecordResolveContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DirContextUtils.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslX509KeyManagerFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/SimpleUserEventChannelHandler.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsCnameCache.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/SuppressJava6Requirement.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/nio/NioChannelOption.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/NameServerComparator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/CertificateCallback.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslCachingX509KeyManagerFactory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/HttpDataFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshaker.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/MemoryFileUpload.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/logging/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/UnpooledByteBufAllocator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpRequestEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollDatagramChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/ByteToMessageDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/MemoryAttribute.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/factorial/FactorialClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/HttpPostRequestDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/bytes/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksCmdResponse.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/example/objectecho/ObjectEchoServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/HttpData.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelFlushPromiseNotifier.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/nio/NioDatagramChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/BlockingOperationException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyHttpHeaders.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/JZlibDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/UnpooledUnsafeDirectByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/socksproxy/SocksServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/base64/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/QueryStringEncoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksCmdRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/ByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/stream/ChunkedInput.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/Signal.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ThreadPerChannelEventLoopGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/websocketx/server/WebSocketFrameHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/echo/EchoServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/websocketx/server/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/nio/NioEventLoop.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/websocketx/server/WebSocketServerIndexPage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/marshalling/CompatibleMarshallingEncoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/InternalLoggerFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/Channel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/stream/ChunkedNioStream.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/DefaultHttpHeaders.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpObjectDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/qotm/QuoteOfTheMomentClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/Attribute.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/InterfaceHttpPostRequestDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5CommandResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpServerCodec.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/nio/NioEventLoopGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/snoop/HttpSnoopServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/serialization/CompatibleObjectEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/TextWebSocketFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/rtsp/RtspResponseEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/DecoderException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/RecvByteBufAllocator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/Slf4JLoggerFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/FixedRecvByteBufAllocator.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/helloworld/HttpHelloWorldServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/localecho/LocalEchoServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/PongWebSocketFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/oio/OioEventLoopGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5PasswordAuthResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/StringUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/FailedFuture.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/oio/OioServerSocketChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksAuthResponseDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpResponseDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelOutboundHandler.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/UdtMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/cors/HttpCorsServerInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/qotm/QuoteOfTheMomentServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/oio/AbstractOioChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/SnappyFrameEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/rtsp/RtspResponseDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/websocketx/server/WebSocketIndexPageHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/message/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/stream/ChunkedStream.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/securechat/SecureChatClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelPipelineException.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/bytes/ByteEchoServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/DefaultHttpContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/UnpooledDirectByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/portunification/PortUnificationServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpHeaders.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpClientCodec.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/DefaultHttpRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/nio/NioServerSocketChannel.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/GlobalEventExecutor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/bootstrap/AbstractBootstrap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/DefaultHttpMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/PlatformDependent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/CompleteChannelFuture.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/DefaultLastHttpContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DefaultEventLoop.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/EventLoop.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/CharsetUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/SocksMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/nio/package-info.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/rendezvous/MsgEchoPeerOne.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/VoidChannelPromise.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/Delimiters.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksAuthRequestDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/timeout/WriteTimeoutException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/DiskFileUpload.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/Timer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyHttpResponseStreamIdHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/oio/OioDatagramChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PooledByteBufAllocator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/DatagramChannel.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/bytes/ByteArrayDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/bytes/ByteEchoServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v4/Socks4CommandType.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/factorial/FactorialServerInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/AttributeKey.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/DefaultAttributeMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshaker08.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/securechat/SecureChatServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/snoop/HttpSnoopClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/timeout/TimeoutException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/DelimiterBasedFrameDecoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/PingWebSocketFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/DefaultSpdySettingsFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/protobuf/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/nio/AbstractNioByteChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5InitialRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/telnet/TelnetServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/nio/package-info.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/oio/AbstractOioByteChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/uptime/UptimeClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/rtsp/RtspRequestDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/SslHandler.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/CodecException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/marshalling/MarshallerProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/sctp/SctpEchoServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/socksproxy/SocksServerConnectHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/snoop/HttpSnoopClientInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/InternalLogLevel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/socksproxy/SocksServerUtils.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/stream/ChunkedNioFile.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/rendezvous/Config.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelInboundHandlerAdapter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/marshalling/package-info.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/HttpPostStandardRequestDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/file/HttpStaticFileServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/securechat/SecureChatServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/marshalling/ContextBoundUnmarshallerProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/factorial/BigIntegerDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/qotm/QuoteOfTheMomentServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/QueryStringDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/objectecho/ObjectEchoServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/rendezvousBytes/ByteEchoPeerTwo.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/Cookie.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/sctp/SctpOutboundByteStreamHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/discard/DiscardClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/Slf4JLogger.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/SocketChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/HttpPostRequestEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/oio/AbstractOioMessageChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/embedded/EmbeddedChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/ZlibDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/marshalling/DefaultUnmarshallerProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/upload/HttpUploadServerInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksAuthRequest.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/nio/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpObjectAggregator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/SwappedByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/local/LocalServerChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/MixedFileUpload.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/LastHttpContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/marshalling/ChannelBufferByteInput.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelPipeline.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/serialization/ClassResolvers.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/serialization/ObjectDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelMetadata.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/DefaultHttpDataFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/local/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/marshalling/MarshallingEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/telnet/TelnetServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/serialization/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/DefaultServerSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/EventExecutorGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocket00FrameEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/serialization/ReferenceMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/CommonsLoggerFactory.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/stream/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/Unpooled.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/rendezvous/MsgEchoPeerTwo.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelInboundHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ThreadPerChannelEventLoop.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/AbstractHttpData.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/telnet/TelnetClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/rtsp/RtspVersions.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/worldclock/WorldClockServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/nio/AbstractNioMessageChannel.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5CommandRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksCmdRequestDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/ServerSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpResponseEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelOutboundHandlerAdapter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/LineBasedFrameDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/Attribute.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ServerChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/upload/HttpUploadServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/ReplayingDecoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v4/Socks4CommandResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelFuture.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/UnknownSocksResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/stream/ChunkedWriteHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelDuplexHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/rtsp/RtspObjectDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/message/MsgEchoServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/rtsp/RtspMethods.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/oio/OioSctpChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/echo/EchoServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/bytes/package-info.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/example/telnet/TelnetServerInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/worldclock/WorldClockClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/serialization/ClassResolver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/embedded/EmbeddedSocketAddress.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/upload/HttpUploadServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/DecoderResult.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/qotm/QuoteOfTheMomentClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpHeaderDateFormat.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshaker07.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/proxy/HexDumpProxyFrontendHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/telnet/TelnetClientHandler.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/timeout/ReadTimeoutException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/ByteBufUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/upload/HttpUploadClientInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/echo/EchoClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/InternalAttribute.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/oio/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/EncoderException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/FailedChannelFuture.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/stream/ChunkedFile.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/group/ChannelGroupFuture.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/AttributeMap.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/DatagramChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/marshalling/DefaultMarshallerProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/FixedLengthFrameDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/ByteBufInputStream.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/DefaultUdtChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpMethod.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/factorial/FactorialServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/SucceededChannelFuture.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v4/DefaultSocks4CommandResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksAuthResponse.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v4/DefaultSocks4CommandRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/AdaptiveRecvByteBufAllocator.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshakerFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/EventExecutor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/HttpPostBodyUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/SingleThreadEventLoop.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/DefaultHttpResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/InternetProtocolFamily.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/proxy/HexDumpProxy.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/FileUpload.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/upload/HttpUploadClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/sctp/SctpEchoClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/rendezvous/MsgEchoPeerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/timeout/IdleStateHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/oio/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/DuplicatedByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PooledDirectByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/SnappyFrameDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v4/Socks4ClientDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/package-info.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/example/sctp/SctpEchoServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpResponseStatus.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/LengthFieldPrepender.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/Timeout.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/SystemPropertyUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/logging/LogLevel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/bootstrap/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PoolChunk.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/nio/NioSocketChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/AbstractChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/nio/package-info.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/group/CombinedIterator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/nio/ProtocolFamilyConverter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/worldclock/WorldClockServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/oio/OioSocketChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpConstants.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/proxy/HexDumpProxyInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/worldclock/WorldClockServerInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5InitialResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DefaultFileRegion.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshaker00.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpVersion.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/BinaryWebSocketFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/DefaultEventExecutorGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/timeout/IdleStateEvent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/bytes/ByteArrayEncoder.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/UnknownSocksRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/sctp/SctpEchoClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/rtsp/RtspResponseStatuses.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PoolArena.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/objectecho/ObjectEchoClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/string/StringDecoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/message/MsgEchoClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/SucceededFuture.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/rendezvousBytes/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/PrematureChannelClosureException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/DefaultDatagramChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/MessageAggregator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/nio/NioDatagramChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/embedded/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/rtsp/RtspRequestEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/DefaultCookie.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/AbstractByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DefaultEventLoopGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/MessageToMessageEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/timeout/IdleState.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v4/Socks4CommandStatus.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/file/HttpStaticFileServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/DefaultSocketChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/marshalling/MarshallingDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/snoop/HttpSnoopServerInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/ServerSocketChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/serialization/ObjectEncoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpRequestDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpContentDecompressor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DefaultChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PoolChunkList.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5CommandRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/local/LocalEventLoopGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdySession.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelFutureListener.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/ByteToMessageCodec.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksInitRequestDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DefaultChannelPromise.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/TooLongFrameException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/CompositeByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/discard/DiscardServer.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5PasswordAuthRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/Log4JLoggerFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/factorial/NumberEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Snappy.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/marshalling/LimitingByteInput.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/Constant.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/cors/HttpCorsServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/AbstractByteBufAllocator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/local/LocalChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksInitRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketVersion.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/embedded/EmbeddedEventLoop.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/EventLoopException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/ContinuationWebSocketFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksCmdResponseDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/MessageToMessageCodec.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/MultithreadEventExecutorGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/AbstractDiskHttpData.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/securechat/SecureChatClientInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/worldclock/WorldClockClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksCommonUtils.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/MessageToMessageDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelPromiseNotifier.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/rendezvousBytes/ByteEchoPeerBase.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/string/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/timeout/ReadTimeoutHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/DefaultHttpObject.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/rtsp/RtspObjectEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/IllegalReferenceCountException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/MessageToByteEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/nio/AbstractNioChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/AbstractMemoryHttpData.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/NotSslRecordException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelPromise.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/oio/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/util/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/AbstractInternalLogger.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/localecho/LocalEcho.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DefaultChannelPipeline.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/local/LocalChannelRegistry.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/CaseIgnoringComparator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/serialization/CachingClassResolver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/CorruptedFrameException.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/serialization/ObjectEncoderOutputStream.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/serialization/SoftReferenceMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/rendezvousBytes/ByteEchoPeerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/socksproxy/SocksServerHandler.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpObjectEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/EventLoopGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/factorial/FactorialServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/ZlibEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpContentCompressor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PoolSubpage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/snoop/HttpSnoopServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/ChannelInputShutdownEvent.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PoolThreadCache.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/ByteBufAllocator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/file/HttpStaticFileServerInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/NetUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/localecho/LocalEchoClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/marshalling/ChannelBufferByteOutput.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/ZlibUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/ByteBufOutputStream.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PooledByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/SocketChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/websocketx/server/WebSocketServerInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/package-info.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/oio/OioSctpServerChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/DecompressionException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksInitResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/UnsupportedMessageTypeException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/marshalling/ThreadLocalMarshallerProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/bootstrap/ServerBootstrap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/HashedWheelTimer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyHttpEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/group/ChannelGroupFutureListener.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/bytes/ByteEchoClientHandler.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksMessageEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/discard/DiscardServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/factorial/FactorialClientInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/base64/Base64Decoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/JdkZlibEncoder.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/DefaultEventExecutor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/discard/DiscardClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/CombinedChannelDuplexHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/securechat/SecureChatServerInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelOption.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/serialization/WeakReferenceMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/telnet/TelnetClientInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/ReadOnlyByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5InitialRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/CompressionException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/socksproxy/SocksServerInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/uptime/UptimeClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelPromiseAggregator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/nio/NioTask.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/serialization/CompactObjectOutputStream.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/socksproxy/RelayHandler.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/logging/LoggingHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/group/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/rendezvous/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/HttpPostMultipartRequestDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/AbstractChannelHandlerContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpContentDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/marshalling/CompatibleMarshallingDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/serialization/CompactObjectInputStream.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/DatagramPacket.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/DiskAttribute.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/timeout/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/bootstrap/Bootstrap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/base64/Base64Encoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/rtsp/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/ReplayingDecoderByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/serialization/ClassLoaderClassResolver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/group/DefaultChannelGroupFuture.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/TimerTask.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/upload/HttpUploadClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/websocketx/server/WebSocketServer.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/snoop/HttpSnoopClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/message/MsgEchoClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/rendezvous/MsgEchoPeerBase.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/rtsp/RtspHeaders.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/UdtChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/MultithreadEventLoopGroup.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/socksproxy/DirectClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/bytes/ByteEchoClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpContentEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/UnpooledHeapByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/local/LocalAddress.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5CommandResponse.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/AbstractServerChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/portunification/PortUnificationServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/objectecho/ObjectEchoClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/worldclock/WorldClockClientInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/InterfaceHttpData.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelHandlerContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/ZlibWrapper.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/SingleThreadEventExecutor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/marshalling/ThreadLocalUnmarshallerProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/multipart/MixedAttribute.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/example/securechat/SecureChatClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/ZlibCodecFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socks/SocksInitResponseDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/string/StringEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/marshalling/UnmarshallerProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpObject.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/serialization/ObjectDecoderInputStream.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/AbstractConstant.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/DefaultSocks5InitialResponse.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketHandshakeException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/JdkLoggerFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketClientHandshaker13.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/factorial/FactorialClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/rendezvousBytes/ByteEchoPeerOne.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/file/FileServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/SlicedByteBuf.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/echo/EchoClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/timeout/WriteTimeoutHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/udt/echo/message/MsgEchoServerHandler.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v4/Socks4CommandRequest.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/proxy/HexDumpProxyBackendHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/JZlibEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/FileRegion.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v4/Socks4ServerDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/CookieDecoder.java

No license file was found, but licenses were detected in source scan.

/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/StreamBufferingEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2StreamVisitor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/StreamByteDistributor.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/AbstractInboundHttp2ToHttpAdapterBuilder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/InboundHttp2ToHttpAdapterBuilder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/ValueConverter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/MathUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/ByteProcessor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2PromisedRequestVerifier.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DecoratingHttp2ConnectionEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DecoratingHttp2ConnectionDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DecoratingHttp2FrameWriter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/WeightedFairQueueByteDistributor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/CoalescingBufferQueue.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/DefaultHeadersImpl.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/CharSequenceValueConverter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/UniformStreamByteDistributor.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2017 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0

*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/uptime/UptimeServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsCacheEntry.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/PriorityQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/ByteBufAllocatorMetric.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/oio/OioDatagramChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/ReflectionUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttMessageBuilders.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/UnixChannelUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/EmptyPriorityQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/WebSocketScheme.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/PendingBytesTracker.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2FrameStreamEvent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/ResolvedAddressTypes.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2UnknownFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsQueryLifecycleObserver.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/util/UncheckedBooleanSupplier.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/NativeStaticallyReferencedJniMethods.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/SniHostNameMatcher.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/ReadOnlyHttpHeaders.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/TraceDnsQueryLifecycleObserver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/UnixResolverDnsServerAddressStreamProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/SslCloseCompletionEvent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2FrameCodecBuilder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/SingletonDnsServerAddressStreamProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsServerAddressStreamProviders.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsNameResolverTimeoutException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/BiDnsQueryLifecycleObserverFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/SslCompletionEvent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2StreamChannelId.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/Conscrypt.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DefaultDnsServerAddressStreamProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/ChannelInputShutdownReadComplete.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/AbstractSniHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/UniSequentialDnsServerAddressStreamProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/internal/ChannelUtils.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/DelegatingChannelPromiseNotifier.java

*
/netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/ChannelOutputShutdownEvent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/NettyRuntime.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/PooledByteBufAllocatorMetric.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/JdkAlpnSslEngine.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/oio/DefaultOioDatagramChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsServerAddressStreamProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/NoopDnsQueryLifecycleObserver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/internal/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/SuppressForbidden.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/logging/LocationAwareSlf4JLogger.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2StreamChannel.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OptionalSslHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/SniCompletionEvent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/buffer/ByteBufAllocatorMetricProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/HostsFileEntries.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/LongAdderCounter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2StreamChannelBootstrap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/SslClientHelloHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/socket/ChannelOutputShutdownException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/bootstrap/FailedChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/uptime/UptimeServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/CleartextHttp2ServerUpgradeHandler.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/TraceDnsQueryLifeCycleObserverFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/ConscryptAlpnSslEngine.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/nio/SelectedSelectionKeySetSelector.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/JdkAlpnSslUtils.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/SequentialDnsServerAddressStreamProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/ocsp/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/DefaultHttp2UnknownFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/NoopDnsQueryLifecycleObserverFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/ObjectCleaner.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2MultiplexCodecBuilder.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/ocsp/OcspClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsQueryLifecycleObserverFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/MultiDnsServerAddressStreamProvider.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/BiDnsQueryLifecycleObserver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpServerExpectContinueHandler.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2019 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance

* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/*
* Adaptation of http://bjoern.hoehrmann.de/utf-8/decoder/dfa/
*
* Copyright (c) 2008-2009 Bjoern Hoehrmann <bjoern@hoehrmann.de>
*
* Permission is hereby granted, free of charge, to any person obtaining a copy of this software
* and associated documentation files (the "Software"), to deal
 in the Software without restriction,
* including without limitation the rights to use, copy, modify, merge, publish, distribute,
* sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is
* furnished to do so, subject to the following conditions:
*
* The above copyright notice and this permission notice shall be included in all copies or
* substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING
* BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
* NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
* DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
* OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/Utf8Validator.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License, version 2.0 (the
* "License"); you may not use this file except in compliance with the License. You may obtain a
* copy of the License at:
*

* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software distributed under the License
* is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express
* or implied. See the License for the specific language governing permissions and limitations under
* the License.
*/
// https://tools.ietf.org/html/rfc7540#section-8.1.2.2 makes a special exception for TE

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/HttpConversionUtil.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2012 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/nio/NioUdtMessageRendezvousChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/sctp/SctpInboundByteStreamHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/sctp/SctpMessageCompletionHandler.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/nio/NioUdtAcceptorChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/nio/NioUdtByteAcceptorChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/nio/NioUdtByteRendezvousChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/traffic/GlobalTrafficShapingHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/nio/NioUdtMessageAcceptorChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/sctp/SctpMessageToMessageDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/traffic/TrafficCounter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/traffic/ChannelTrafficShapingHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/traffic/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/nio/NioUdtByteConnectorChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/nio/NioUdtProvider.java
*

/netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/nio/NioUdtMessageConnectorChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/UdtChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/sctp/package-info.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright 2015 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/
/*
* Copyright 2014 Twitter, Inc.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
*     http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable
 law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/HpackHeaderField.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/HpackUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/HpackStaticTable.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/HpackDynamicTable.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/HpackEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/HpackDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/HpackHuffmanDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/HpackHuffmanEncoder.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2013 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/oio/OioByteStreamChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/udt/UdtServerChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/rxtx/RxtxChannelOption.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/sctp/SctpChannelOption.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/rxtx/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/rxtx/DefaultRxtxChannelConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/rxtx/RxtxChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/rxtx/RxtxDeviceAddress.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/rxtx/RxtxChannelConfig.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright 2014 The Netty Project
*
* The Netty Project licenses this file to you under the Apache License,
* version 2.0 (the "License"); you may not use this file except in compliance
* with the License. You may obtain a copy of the License at:
*
*   http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS, WITHOUT
* WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the
* License for the specific language governing permissions and limitations
* under the License.
*/

Found in path(s):
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/ResourceLeakHint.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Bzip2Decoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpHeaderNames.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollServerSocketChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/extensions/package-info.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerMessageDeflateDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/stomp/StompClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttUnacceptableProtocolVersionException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/AsciiHeadersEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/JdkDefaultApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/StompConstants.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyFrameCodec.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/CipherSuiteConverter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/AddressResolverGroup.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionData.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/AbstractEventLoop.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtension.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/NameResolver.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5ClientEncoder.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketServerExtension.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/FastLzFrameEncoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/util/SimpleTrustManagerFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Bzip2BitReader.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Bzip2HuffmanAllocator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsServerAddresses.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/internal/tcnative/CertificateVerifier.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/UnpaddedInternalThreadLocalMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Bzip2BlockDecompressor.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerMessageDeflateClientExtensionHandshaker.j
ava
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/proxy/ProxyHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/LzmaFrameEncoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/Java7SslParametersUtils.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/util/BouncyCastleSelfSignedCertGenerator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5InitialRequestDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/proxy/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/haproxy/HAProxyProtocolVersion.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/SupportedCipherSuiteFilter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Bzip2Encoder.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5InitialResponseDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/spdy/client/SpdyClientStreamIdHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/JettyAlpnSslEngine.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/SimpleNameResolver.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollEventLoop.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlCharacters.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/SniHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollSocketChannel.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttCodecUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttTopicSubscription.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v4/Socks4Message.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/DefaultLastStompContentSubframe.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslServerContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/SslProvider.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttSubscribeMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/SslUtils.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollTcpInfo.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/util/InsecureTrustManagerFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/server/Http2Server.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/SnappyFramedDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/ApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/spdy/client/HttpResponseClientHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/ClientCookieEncoder.java
*
 /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketClientExtension.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/DefaultStompHeaders.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/websocketx/benchmarkserver/WebSocketServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlContent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslEngine.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/spdy/server/SpdyOrHttpHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/FastLz.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/LzfEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/PromiseNotifier.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/StompContentSubframe.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/haproxy/HAProxyMessage.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ipfilter/RuleBasedIpFilter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlDocumentStart.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/AsciiString.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/JdkNpnApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionUtil.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttPublishVariableHeader.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthRequestDecoder.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/DeflateEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/json/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/ApplicationProtocolUtil.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/Epoll.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerMessageDeflateServerExtensionHandshaker.
java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Bzip2Constants.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/spdy/client/SpdyClientInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/websocketx/client/WebSocketClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/DefaultStompContentSubframe.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v4/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ipfilter/AbstractRemoteAddressFilter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/NoopAddressResolver.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionEncoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/Utf8FrameValidator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ipfilter/UniqueIpFilter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttIdentifierRejectedException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttSubscribePayload.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketServerExtensionHandshaker.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttUnsubAckMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/LzfDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttUnsubscribePayload.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ChannelFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v4/AbstractSocks4Message.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/DefaultStompHeadersSubframe.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5Message.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Lz4Constants.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslEngineMap.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/DefaultStompFrame.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketExtensionDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/StompHeadersSubframe.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslNpnApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/server/HelloWorldHttp1Handler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/stomp/StompClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/package-info.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2FrameLogger.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http/websocketx/benchmarkserver/package-info.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/rtsp/RtspHeaderValues.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyFrameDecoderDelegate.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/StompSubframeAggregator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2InboundFrameLogger.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollEventLoopGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/haproxy/package-info.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Bzip2BlockCompressor.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/DomainNameMapping.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/FastThreadLocal.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpStatusClass.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/StompHeaders.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/file/FileServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v4/Socks4ClientEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/PendingWriteQueue.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/haproxy/HAProxyConstants.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/ServerCookieEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5CommandRequestDecoder.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/MessageAggregationException.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/example/http/websocketx/benchmarkserver/WebSocketServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttMessageIdVariableHeader.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttMessageType.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Bzip2BitWriter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/NoopAddressResolverGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/StompFrame.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Bzip2MTFAndRLE2StageEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlElement.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttFixedHeader.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/package-info.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ipfilter/IpSubnetFilterRule.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/StompSubframe.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslServerSessionContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/ReflectiveChannelFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/FastLzFrameDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5ServerEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslSessionStats.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ipfilter/IpFilterRuleType.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/spdy/server/SpdyServer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttMessageFactory.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/AbstractSocks5Message.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/util/Mapping.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpChunkedInput.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/json/JsonObjectDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/util/OpenJdkSelfSignedCertGenerator.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/WebSocketClientCompressionHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlElementStart.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/StompCommand.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/embedded/EmbeddedChannelId.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/proxy/HttpProxyHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/http2/helloworld/server/Http2ServerInitializer.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketServerExtensionHandler.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsAddressResolverGroup.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5CommandResponseDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlElementEnd.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/traffic/GlobalChannelTrafficCounter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlComment.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlNamespace.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/spdy/client/SpdyClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/proxy/ProxyConnectionEvent.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyFrameDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/util/FingerprintTrustManagerFactory.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/JdkSslEngine.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/DeflateDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockRawDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/StompSubframeEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/IntegerHolder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslClientContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlDTD.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttSubAckPayload.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttConnectMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/spdy/client/SpdyFrameLogger.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/spdy/server/SpdyServerInitializer.java
*
 /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlProcessingInstruction.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttConnAckMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/memcache/binary/MemcacheClient.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttVersion.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/proxy/Socks5ProxyHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/JdkSslServerContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpHeadersEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/JdkBaseApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/spdy/server/SpdyServerHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsNameResolver.java
*

/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/JettyNpnSslEngine.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslDefaultApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/haproxy/HAProxyCommand.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2OutboundFrameLogger.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/JdkAlpnApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/DeflateFrameServerExtensionHandshaker.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyProtocolException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Lz4FrameDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslSessionContext.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/example/spdy/server/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Crc32.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslX509Certificate.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Bzip2HuffmanStageDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Bzip2HuffmanStageEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttPubAckMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/proxy/ProxyConnectException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/StompSubframeDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSsl.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerFrameDeflateEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollDatagramChannel.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Lz4FrameEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/stomp/LastStompContentSubframe.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttUnsubscribeMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/ApplicationProtocolConfig.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/haproxy/HAProxyMessageDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/concurrent/PromiseAggregator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/IovArray.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsResolveContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttSubAckMessage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlCdata.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/memcache/binary/MemcacheClientHandler.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/haproxy/HAProxyProxiedProtocol.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ipfilter/IpFilterRule.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/WebSocketServerCompressionHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpHeaderValues.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketClientExtensionHandshaker.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerFrameDeflateDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyHeaderBlockZlibDecoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/InternalThreadLocalMap.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/AbstractEpollChannel.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/channel/unix/UnixChannelOption.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/example/spdy/client/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/haproxy/HAProxyProtocolException.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttConnAckVariableHeader.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http2/Http2SecurityUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/JdkApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttConnectVariableHeader.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/EpollChannelOption.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/SslContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v4/Socks4ServerEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlDecoder.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/CipherSuiteFilter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/PemReader.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/spdy/SpdyFrameEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Bzip2DivSufSort.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/WebSocketClientExtensionHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/HttpMessageUtil.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlSpace.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttPublishMessage.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/DeflateFrameClientExtensionHandshaker.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttConnectPayload.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/mqtt/MqttConnectReturnCode.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/v5/Socks5PasswordAuthResponseDecoder.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/example/http/websocketx/benchmarkserver/WebSocketServerBenchmarkPage.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/SnappyFramedEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/proxy/Socks4ProxyHandler.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/channel/epoll/NativeDatagramPacketArray.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlEntityReference.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/IdentityCipherSuiteFilter.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/JdkSslContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/OpenSslApplicationProtocolNegotiator.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/DecoderResultProvider.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/http/websocketx/extensions/compression/package-
info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ipfilter/package-info.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/ThreadDeathWatcher.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/example/http/websocketx/benchmarkserver/WebSocketServerInitializer.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Bzip2Rand.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/socksx/AbstractSocksMessage.java

* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlDocumentEnd.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/JdkSslClientContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/util/internal/NativeLibraryLoader.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/ssl/util/ThreadLocalInsecureRandom.java
*
/netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/xml/XmlAttribute.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/rtsp/RtspHeaderNames.java
* /netty-all-4-1-49-final-sources-3-
jar/io/netty/handler/codec/http/websocketx/extensions/compression/PerMessageDeflateEncoder.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/resolver/dns/DnsQueryContext.java
* /netty-all-4-1-49-final-sources-3-jar/io/netty/handler/codec/compression/Bzip2MoveToFrontTable.java

1.1531 nimbus-jose-jwt 8.9

1.1531.1 Available under license :

Nimbus JOSE + JWT

Copyright 2012 - 2020, Connect2id Ltd.

Licensed under the Apache License, Version 2.0 (the "License"); you may not use
this file except in compliance with the License. You may obtain a copy of the
License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software distributed
under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
CONDITIONS OF ANY KIND, either express or implied. See the License for the
specific language governing permissions and limitations under the License.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,

"control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and

subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding

those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise,

unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1532 pool 1.5.3

1.1532.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2013 Diogo Resende and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1533 shiro-config-ogdl 1.6.0

1.1533.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or
Object form, made available under the License, as indicated by a
copyright notice that is included in or attached to the work
(an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object
form, that is based on (or derived from) the Work and for which the
editorial
revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes
of this License, Derivative Works shall not include works that remain
separable from, or merely link (or bind by name) to the interfaces of,
the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its

distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,

WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Shiro
Copyright 2008-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

The implementation for org.apache.shiro.util.SoftHashMap is based
on initial ideas from Dr. Heinz Kabutz's publicly posted version
available at http://www.javaspecialists.eu/archive/Issue015.html,
with continued modifications.

Certain parts (StringUtils, IpAddressMatcher, etc.) of the source
code for this product was copied for simplicity and to reduce
dependencies from the source code developed by the Spring Framework
Project (http://www.springframework.org).

1.1534 shiro-cache 1.6.0

1.1534.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity

exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the

Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents

of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,

work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache Shiro
Copyright 2008-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

The implementation for org.apache.shiro.util.SoftHashMap is based

on initial ideas from Dr. Heinz Kabutz's publicly posted version
available at http://www.javaspecialists.eu/archive/Issue015.html,
with continued modifications.

Certain parts (StringUtils, IpAddressMatcher, etc.) of the source
code for this product was copied for simplicity and to reduce
dependencies from the source code developed by the Spring Framework
Project (http://www.springframework.org).

1.1535 shiro-core 1.6.0

1.1535.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their

Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf

of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache Shiro
Copyright 2008-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

The implementation for org.apache.shiro.util.SoftHashMap is based
on initial ideas from Dr. Heinz Kabutz's publicly posted version
available at http://www.javaspecialists.eu/archive/Issue015.html,
with continued modifications.

Certain parts (StringUtils, IpAddressMatcher, etc.) of the source
code for this product was copied for simplicity and to reduce
dependencies from the source code developed by the Spring Framework
Project (http://www.springframework.org).

1.1536 shiro-config-core 1.6.0

1.1536.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial

revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.

Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Shiro
Copyright 2008-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

The implementation for org.apache.shiro.util.SoftHashMap is based
on initial ideas from Dr. Heinz Kabutz's publicly posted version
available at http://www.javaspecialists.eu/archive/Issue015.html,
with continued modifications.

Certain parts (StringUtils, IpAddressMatcher, etc.) of the source
code for this product was copied for simplicity and to reduce
dependencies from the source code developed by the Spring Framework
Project (http://www.springframework.org).

1.1537 shiro-crypto-hash 1.6.0

1.1537.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner

or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices

stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Shiro
Copyright 2008-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

The implementation for org.apache.shiro.util.SoftHashMap is based
on initial ideas from Dr. Heinz Kabutz's publicly posted version
available at http://www.javaspecialists.eu/archive/Issue015.html,
with continued modifications.

Certain parts (StringUtils, IpAddressMatcher, etc.) of the source
code for this product was copied for simplicity and to reduce
dependencies from the source code developed by the Spring Framework
Project (http://www.springframework.org).

1.1538 shiro-event 1.6.0

1.1538.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all

other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must

include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

See the License for the specific language governing permissions and
limitations under the License.
Apache Shiro
Copyright 2008-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

The implementation for org.apache.shiro.util.SoftHashMap is based
on initial ideas from Dr. Heinz Kabutz's publicly posted version
available at http://www.javaspecialists.eu/archive/Issue015.html,
with continued modifications.

Certain parts (StringUtils, IpAddressMatcher, etc.) of the source
code for this product was copied for simplicity and to reduce
dependencies from the source code developed by the Spring Framework
Project (http://www.springframework.org).

1.1539 shiro-crypto-cipher 1.6.0

1.1539.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and

do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all

other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache Shiro
Copyright 2008-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

The implementation for org.apache.shiro.util.SoftHashMap is based
on initial ideas from Dr. Heinz Kabutz's publicly posted version

available at http://www.javaspecialists.eu/archive/Issue015.html,
with continued modifications.

Certain parts (StringUtils, IpAddressMatcher, etc.) of the source
code for this product was copied for simplicity and to reduce
dependencies from the source code developed by the Spring Framework
Project (http://www.springframework.org).

1.1540 shiro-lang 1.6.0

1.1540.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s)

with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf

of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache Shiro
Copyright 2008-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

The implementation for org.apache.shiro.util.SoftHashMap is based
on initial ideas from Dr. Heinz Kabutz's publicly posted version
available at http://www.javaspecialists.eu/archive/Issue015.html,
with continued modifications.

Certain parts (StringUtils, IpAddressMatcher, etc.) of the source
code for this product was copied for simplicity and to reduce
dependencies from the source code developed by the Spring Framework
Project (http://www.springframework.org).

1.1541 shiro-crypto-core 1.6.0

1.1541.1 Available under license :

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial

revisions, annotations, elaborations, or other modifications
represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You
meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.

Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
Apache Shiro
Copyright 2008-2020 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

The implementation for org.apache.shiro.util.SoftHashMap is based
on initial ideas from Dr. Heinz Kabutz's publicly posted version
available at http://www.javaspecialists.eu/archive/Issue015.html,
with continued modifications.

Certain parts (StringUtils, IpAddressMatcher, etc.) of the source
code for this product was copied for simplicity and to reduce
dependencies from the source code developed by the Spring Framework
Project (http://www.springframework.org).

1.1542 camel-jackson 2.15.2

1.1542.1 Available under license :

```
=========================================================================
==  NOTICE file corresponding to the section 4 d of                    ==
==  the Apache License, Version 2.0,                                   ==
==  in this case for the Apache Camel distribution.                    ==
=========================================================================
```

This product includes software developed by
The Apache Software Foundation (http://www.apache.org/).

Please read the different LICENSE files present in the licenses directory of
this distribution.

Camel :: Jackson
Copyright 2007-2015 The Apache Software Foundation

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,
and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by
the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all
other entities that control, are controlled by, or are under common
control with that entity. For the purposes of this definition,
"control" means (i) the power, direct or indirect, to cause the
direction or management of such entity, whether by contract or
otherwise, or (ii) ownership of fifty percent (50%) or more of the
outstanding shares, or (iii) beneficial ownership
of such entity.

"You" (or "Your") shall mean an individual or Legal Entity
exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications,
including but not limited to software source code, documentation
source, and configuration files.

"Object" form shall mean any form resulting from mechanical
transformation or translation of a Source form, including but
not limited to compiled object code, generated documentation,
and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or

Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You

institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use,

reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability

incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1543 ipaddr.js 1.9.1

1.1543.1 Available under license :

Copyright (C) 2011-2017 whitequark <whitequark@whitequark.org>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,

FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1544 cors 2.8.5

1.1544.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2013 Troy Goode <troygoode@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1545 string_decoder 1.1.1

1.1545.1 Available under license :

MIT
Node.js is licensed for use as follows:

"""
Copyright Node.js contributors. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
IN THE SOFTWARE.
"""

This license applies to parts of Node.js originating from the
https://github.com/joyent/node repository:

"""
Copyright Joyent, Inc. and other Node contributors. All rights reserved.
Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
IN THE SOFTWARE.
"""

1.1546 is-binary-path 2.1.0

1.1546.1 Available under license :

MIT License

Copyright (c) 2019 Sindre Sorhus <sindresorhus@gmail.com> (https://sindresorhus.com), Paul Miller (https://paulmillr.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1547 process-nextick-args 2.0.1

1.1547.1 Available under license :

Copyright (c) 2015 Calvin Metcalf

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1548 readable-stream 2.3.8

1.1548.1 Available under license :

MIT
Node.js is licensed for use as follows:

"""
Copyright Node.js contributors. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
IN THE SOFTWARE.
"""

This license applies to parts of Node.js originating from the
https://github.com/joyent/node repository:

"""
Copyright Joyent, Inc. and other Node contributors. All rights reserved.
Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF

MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
"""

1.1549 binary-extensions 2.2.0

1.1549.1 Available under license :

MIT License

Copyright (c) 2019 Sindre Sorhus <sindresorhus@gmail.com> (https://sindresorhus.com), Paul Miller (https://paulmillr.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1550 just-debounce 1.1.0

1.1550.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Michael Hayes

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1551 async-each 1.0.6

1.1551.1 Available under license :

MIT
MIT License

Copyright (c) 2016 Paul Miller (https://paulmillr.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1552 buffer-equal 1.0.1

1.1552.1 Available under license :

This software is released under the MIT license:

Permission is hereby granted, free of charge, to any person obtaining a copy of

this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1553 ip-address 9.0.5

1.1553.1 Available under license :

Copyright (C) 2011 by Beau Gunderson

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.1554 merge-anything 2.4.4

1.1554.1 Available under license :

MIT
MIT License

Copyright (c) 2018 Luca Ban - Mesqueeb

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1555 css-to-react-native 2.3.2

1.1555.1 Available under license :

MIT License

Copyright (c) 2016 Jacob Parker and Maximilian Stoiber

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1556 @babel/plugin-transform-optional-chaining 7.22.15

1.1556.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1557 diff 1.4.0

1.1557.1 Available under license :

BSD-style without advertising clause

1.1558 @webassemblyjs/helper-module-context 1.9.0

1.1558.1 Available under license :

MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1559 @babel/plugin-transform-destructuring 7.22.15

1.1559.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1560 @types/react 18.2.21

1.1560.1 Available under license :

MIT

MIT License

Copyright (c) Microsoft Corporation.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF
CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE

1.1561 @babel/plugin-proposal-private-property-in-object 7.21.11

1.1561.1 Available under license :

MIT

MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1562 react-deep-force-update 1.1.2

1.1562.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015 library-boilerplate-author

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1563 icss-utils 4.1.1

1.1563.1 Available under license :

ISC
ISC License (ISC)
Copyright 2018 Glen Maddern

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.1564 @babel/plugin-syntax-function-sent 7.22.5

1.1564.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,

ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1565 rx 2.5.3

1.1565.1 Available under license :

Copyright (c) Microsoft Open Technologies, Inc. All rights reserved.
Microsoft Open Technologies would like to thank its contributors, a list
of whom are at http://rx.codeplex.com/wikipage?title=Contributors.

Licensed under the Apache License, Version 2.0 (the "License"); you
may not use this file except in compliance with the License. You may
obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied. See the License for the specific language governing permissions
and limitations under the License.
Apache License 2.0

1.1566 @babel/plugin-proposal-throw-expressions 7.22.5

1.1566.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF

MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1567 @babel/plugin-transform-modules-amd 7.22.5

1.1567.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1568 @babel/helper-define-polyfill-provider 0.4.2

1.1568.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Nicol Ribaudo and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1569 postcss-modules-values 3.0.0

1.1569.1 Available under license :

ISC
ISC License (ISC)

Copyright (c) 2015, Glen Maddern

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.1570 @babel/plugin-syntax-pipeline-operator 7.22.5

1.1570.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1571 @webassemblyjs/helper-wasm-section 1.9.0

1.1571.1 Available under license :

MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1572 @webassemblyjs/helper-api-error 1.9.0

1.1572.1 Available under license :

MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1573 @babel/plugin-proposal-pipeline-operator 7.22.15

1.1573.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1574 @babel/plugin-proposal-logical-assignment-operators 7.20.7

1.1574.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1575 @babel/plugin-proposal-export-default-from 7.22.17

1.1575.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1576 @babel/plugin-proposal-do-expressions 7.22.5

1.1576.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1577 transform-loader 0.2.4

1.1577.1 Available under license :

Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY

CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1578 @webassemblyjs/helper-wasm-bytecode 1.9.0

1.1578.1 Available under license :

MIT
MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1579 @sinonjs/samsam 6.1.3

1.1579.1 Available under license :

(The BSD License)

Copyright (c) 2010-2012, Christian Johansen, christian@cjohansen.no and
August Lilleaas, august.lilleaas@gmail.com. All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,
  this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,
  this list of conditions and the following disclaimer in the documentation
  and/or other materials provided with the distribution.
* Neither the name of Christian Johansen nor the names of his contributors
  may be used to endorse or promote products derived from this software
  without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED
 TO, THE IMPLIED
WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1580 @babel/helper-validator-identifier 7.22.19

1.1580.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE

LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1581 cyclist 1.0.2

1.1581.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015 Mathias Buus

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.1582 webpack-bundle-analyzer 3.9.0

1.1582.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1583 dom-walk 0.1.2

1.1583.1 Available under license :

MIT
Copyright (c) 2012 Raynos.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1584 file-loader 4.3.0

1.1584.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including

without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1585 @webassemblyjs/wasm-parser 1.9.0

1.1585.1 Available under license :

MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1586 @webassemblyjs/ieee754 1.9.0

1.1586.1 Available under license :

MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1587 babel-plugin-proposal-decorators 7.22.15

1.1587.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be

included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1588 css-loader 3.6.0

1.1588.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1589 @babel/core 7.22.19

1.1589.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining

a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1590 @babel/helper-wrap-function 7.22.17

1.1590.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1591 @babel/cli 7.22.15

1.1591.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1592 globule 1.3.4

1.1592.1 Available under license :

Copyright (c) 2018 "Cowboy" Ben Alman

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1593 @webassemblyjs/helper-buffer 1.9.0

1.1593.1 Available under license :

MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1594 @babel/plugin-syntax-do-expressions 7.22.5

1.1594.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1595 webpack-inject-plugin 1.5.5

1.1595.1 Available under license :

MIT

1.1596 babel-plugin-add-module-exports 1.0.4

1.1596.1 Available under license :

MIT

1.1597 style-loader 1.3.0

1.1597.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1598 postcss-modules-local-by-default 3.0.3

1.1598.1 Available under license :

MIT
The MIT License (MIT)

Copyright 2015 Mark Dalgleish <mark.john.dalgleish@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS
FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR
COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER
IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1599 nise 5.1.4

1.1599.1 Available under license :

(The BSD License)

Copyright (c) 2010-2017, Christian Johansen, christian@cjohansen.no
All rights reserved.

Redistribution and use in source and binary forms, with or without modification,
are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,
  this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright notice,
  this list of conditions and the following disclaimer in the documentation
  and/or other materials provided with the distribution.
* Neither the name of Christian Johansen nor the names of his contributors
  may be used to endorse or promote products derived from this software
  without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY
 AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1600 caniuse-lite 1.0.30001534

1.1600.1 Available under license :

Attribution 4.0 International

==========

Creative Commons Corporation ("Creative Commons") is not a law firm and
does not provide legal services or legal advice. Distribution of
Creative Commons public licenses does not create a lawyer-client or
other relationship. Creative Commons makes its licenses and related
information available on an "as-is" basis. Creative Commons gives no
warranties regarding its licenses, any material licensed under their
terms and conditions, or any related information. Creative Commons
disclaims all liability for damages resulting from their use to the
fullest extent possible.

Using Creative Commons Public Licenses

Creative Commons public licenses provide a standard set of terms and
conditions that creators and other rights holders may use to share

original works of authorship and other material subject to copyright and certain other rights specified in the public license below. The following considerations
are for informational purposes only, are not exhaustive, and do not form part of our licenses.

Considerations for licensors: Our public licenses are intended for use by those authorized to give the public permission to use material in ways otherwise restricted by copyright and certain other rights. Our licenses are irrevocable. Licensors should read and understand the terms and conditions of the license they choose before applying it. Licensors should also secure all rights necessary before applying our licenses so that the public can reuse the material as expected. Licensors should clearly mark any material not subject to the license. This includes other CC-licensed material, or material used under an exception or limitation to copyright. More considerations for licensors:
wiki.creativecommons.org/Considerations_for_licensors

Considerations for the public: By using one of our public licenses, a licensor
grants the public permission to use the licensed material under specified terms and conditions. If the licensor's permission is not necessary for any reason--for example, because of any applicable exception or limitation to copyright--then that use is not regulated by the license. Our licenses grant only permissions under copyright and certain other rights that a licensor has authority to grant. Use of the licensed material may still be restricted for other reasons, including because others have copyright or other rights in the material. A licensor may make special requests, such as asking that all changes be marked or described. Although not required by our licenses, you are encouraged to respect those requests where reasonable. More_considerations for the public:
wiki.creativecommons.org/Considerations_for_licensees

==========

Creative Commons Attribution 4.0 International Public License

By exercising the Licensed Rights (defined below), You accept and agree to be bound by the terms and conditions of this Creative Commons Attribution 4.0 International Public License ("Public License"). To the extent this Public License may be interpreted as a contract, You are granted the Licensed Rights in consideration of Your acceptance of

these terms and conditions, and the Licensor grants You such rights in consideration of benefits the Licensor receives from making the Licensed Material available under these terms and conditions.

Section 1 -- Definitions.

a. Adapted Material means material subject to Copyright and Similar Rights that is derived from or based upon the Licensed Material and in which the Licensed Material is translated, altered, arranged, transformed, or otherwise modified in a manner requiring permission under the Copyright and Similar Rights held by the Licensor. For purposes of this Public License, where the Licensed Material is a musical work, performance, or sound recording, Adapted Material is always produced where the Licensed Material is synched in timed relation with a moving image.

b. Adapter's License means the license You apply to Your Copyright and Similar Rights in Your contributions to Adapted Material in accordance with the terms and conditions of this Public License.

c. Copyright and Similar Rights means copyright and/or similar rights closely related to copyright including, without limitation, performance, broadcast, sound recording, and Sui Generis Database Rights, without regard to how the rights are labeled or categorized. For purposes of this Public License, the rights specified in Section 2(b)(1)-(2) are not Copyright and Similar Rights.

d. Effective Technological Measures means those measures that, in the absence of proper authority, may not be circumvented under laws fulfilling obligations under Article 11 of the WIPO Copyright Treaty adopted on December 20, 1996, and/or similar international agreements.

e. Exceptions and Limitations means fair use, fair dealing, and/or any other exception or limitation to Copyright and Similar Rights that applies to Your use of the Licensed Material.

f. Licensed Material means the artistic or literary work, database, or other material to which the Licensor applied this Public License.

g. Licensed Rights means the rights granted to You subject to the terms and conditions of this Public License, which are limited to all Copyright and Similar Rights that apply to Your use of the

Licensed Material and that the Licensor has authority to license.

h. Licensor means the individual(s) or entity(ies) granting rights under this Public License.

i. Share means to provide material to the public by any means or process that requires permission under the Licensed Rights, such as reproduction, public display, public performance, distribution, dissemination, communication, or importation, and to make material available to the public including in ways that members of the public may access the material from a place and at a time individually chosen by them.

j. Sui Generis Database Rights means rights other than copyright resulting from Directive 96/9/EC of the European Parliament and of the Council of 11 March 1996 on the legal protection of databases, as amended and/or succeeded, as well as other essentially equivalent rights anywhere in the world.

k. You means the individual or entity exercising the Licensed Rights under this Public License. Your has a corresponding meaning.

Section 2 -- Scope.

a. License grant.

1. Subject to the terms and conditions of this Public License, the Licensor hereby grants You a worldwide, royalty-free, non-sublicensable, non-exclusive, irrevocable license to exercise the Licensed Rights in the Licensed Material to:

a. reproduce and Share the Licensed Material, in whole or in part; and

b. produce, reproduce, and Share Adapted Material.

2. Exceptions and Limitations. For the avoidance of doubt, where Exceptions and Limitations apply to Your use, this Public License does not apply, and You do not need to comply with its terms and conditions.

3. Term. The term of this Public License is specified in Section 6(a).

4. Media and formats; technical modifications allowed. The Licensor authorizes You to exercise the Licensed Rights in

all media and formats whether now known or hereafter created, and to make technical modifications necessary to do so. The Licensor waives and/or agrees not to assert any right or authority to forbid You from making technical modifications necessary to exercise the Licensed Rights, including technical modifications necessary to circumvent Effective Technological Measures. For purposes of this Public License, simply making modifications authorized by this Section 2(a)(4) never produces Adapted Material.

5. Downstream recipients.

a. Offer from the Licensor -- Licensed Material. Every recipient of the Licensed Material automatically receives an offer from the Licensor to exercise the Licensed Rights under the terms and conditions of this Public License.

b. No downstream restrictions. You may not offer or impose any additional or different terms or conditions on, or apply any Effective Technological Measures to, the Licensed Material if doing so restricts exercise of the Licensed Rights by any recipient of the Licensed

Material.

6. No endorsement. Nothing in this Public License constitutes or may be construed as permission to assert or imply that You are, or that Your use of the Licensed Material is, connected with, or sponsored, endorsed, or granted official status by, the Licensor or others designated to receive attribution as provided in Section 3(a)(1)(A)(i).

b. Other rights.

1. Moral rights, such as the right of integrity, are not licensed under this Public License, nor are publicity, privacy, and/or other similar personality rights; however, to the extent possible, the Licensor waives and/or agrees not to assert any such rights held by the Licensor to the limited extent necessary to allow You to exercise the Licensed Rights, but not otherwise.

2. Patent and trademark rights are not licensed under this Public License.

3. To the extent

possible, the Licensor waives any right to collect royalties from You for the exercise of the Licensed Rights, whether directly or through a collecting society under any voluntary or waivable statutory or compulsory licensing scheme. In all other cases the Licensor expressly reserves any right to collect such royalties.

Section 3 -- License Conditions.

Your exercise of the Licensed Rights is expressly made subject to the following conditions.

a. Attribution.

1. If You Share the Licensed Material (including in modified form), You must:

a. retain the following if it is supplied by the Licensor with the Licensed Material:

i. identification of the creator(s) of the Licensed Material and any others designated to receive attribution, in any reasonable manner requested by the Licensor (including by pseudonym if

designated);

ii. a copyright notice;

iii. a notice that refers to this Public License;

iv. a notice that refers to the disclaimer of warranties;

v. a URI or hyperlink to the Licensed Material to the extent reasonably practicable;

b. indicate if You modified the Licensed Material and retain an indication of any previous modifications; and

c. indicate the Licensed Material is licensed under this Public License, and include the text of, or the URI or hyperlink to, this Public License.

2. You may satisfy the conditions in Section 3(a)(1) in any reasonable manner based on the medium, means, and context in which You Share the Licensed Material. For example, it may be

reasonable to satisfy the conditions by providing a URI or hyperlink to a resource that
includes the required
information.

3. If requested by the Licensor, You must remove any of the information required by Section 3(a)(1)(A) to the extent reasonably practicable.

4. If You Share Adapted Material You produce, the Adapter's License You apply must not prevent recipients of the Adapted Material from complying with this Public License.

Section 4 -- Sui Generis Database Rights.

Where the Licensed Rights include Sui Generis Database Rights that apply to Your use of the Licensed Material:

a. for the avoidance of doubt, Section 2(a)(1) grants You the right to extract, reuse, reproduce, and Share all or a substantial portion of the contents of the database;

b. if You include all or a substantial portion of the database contents in a database in which You have Sui Generis Database Rights, then the database in which You have Sui Generis Database Rights (but not its individual contents)
is Adapted Material; and

c. You must comply with the conditions in Section 3(a) if You Share all or a substantial portion of the contents of the database.

For the avoidance of doubt, this Section 4 supplements and does not replace Your obligations under this Public License where the Licensed Rights include other Copyright and Similar Rights.

Section 5 -- Disclaimer of Warranties and Limitation of Liability.

a. UNLESS OTHERWISE SEPARATELY UNDERTAKEN BY THE LICENSOR, TO THE EXTENT POSSIBLE, THE LICENSOR OFFERS THE LICENSED MATERIAL AS-IS AND AS-AVAILABLE, AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE LICENSED MATERIAL, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHER. THIS INCLUDES, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE OR ABSENCE OF ERRORS, WHETHER OR NOT KNOWN OR DISCOVERABLE.

WHERE DISCLAIMERS OF WARRANTIES ARE NOT
ALLOWED IN FULL OR IN PART, THIS DISCLAIMER MAY NOT APPLY TO YOU.

b. TO THE EXTENT POSSIBLE, IN NO EVENT WILL THE LICENSOR BE LIABLE
TO YOU ON ANY LEGAL THEORY (INCLUDING, WITHOUT LIMITATION,
NEGLIGENCE) OR OTHERWISE FOR ANY DIRECT, SPECIAL, INDIRECT,
INCIDENTAL, CONSEQUENTIAL, PUNITIVE, EXEMPLARY, OR OTHER LOSSES,
COSTS, EXPENSES, OR DAMAGES ARISING OUT OF THIS PUBLIC LICENSE OR
USE OF THE LICENSED MATERIAL, EVEN IF THE LICENSOR HAS BEEN
ADVISED OF THE POSSIBILITY OF SUCH LOSSES, COSTS, EXPENSES, OR
DAMAGES. WHERE A LIMITATION OF LIABILITY IS NOT ALLOWED IN FULL OR
IN PART, THIS LIMITATION MAY NOT APPLY TO YOU.

c. The disclaimer of warranties and limitation of liability provided
above shall be interpreted in a manner that, to the extent
possible, most closely approximates an absolute disclaimer and
waiver of all liability.

Section 6 -- Term and Termination.

a. This Public License
applies for the term of the Copyright and
Similar Rights licensed here. However, if You fail to comply with
this Public License, then Your rights under this Public License
terminate automatically.

b. Where Your right to use the Licensed Material has terminated under
Section 6(a), it reinstates:

1. automatically as of the date the violation is cured, provided
it is cured within 30 days of Your discovery of the
violation; or

2. upon express reinstatement by the Licensor.

For the avoidance of doubt, this Section 6(b) does not affect any
right the Licensor may have to seek remedies for Your violations
of this Public License.

c. For the avoidance of doubt, the Licensor may also offer the
Licensed Material under separate terms or conditions or stop
distributing the Licensed Material at any time; however, doing so
will not terminate this Public License.

d. Sections 1, 5, 6, 7, and 8 survive termination
of this Public
License.

Section 7 -- Other Terms and Conditions.

a. The Licensor shall not be bound by any additional or different terms or conditions communicated by You unless expressly agreed.

b. Any arrangements, understandings, or agreements regarding the Licensed Material not stated herein are separate from and independent of the terms and conditions of this Public License.

Section 8 -- Interpretation.

a. For the avoidance of doubt, this Public License does not, and shall not be interpreted to, reduce, limit, restrict, or impose conditions on any use of the Licensed Material that could lawfully be made without permission under this Public License.

b. To the extent possible, if any provision of this Public License is deemed unenforceable, it shall be automatically reformed to the minimum extent necessary to make it enforceable. If the provision cannot be reformed, it shall be severed from this Public License without affecting the enforceability of the remaining terms and conditions.

c. No term or condition of this Public License will be waived and no failure to comply consented to unless expressly agreed to by the Licensor.

d. Nothing in this Public License constitutes or may be interpreted as a limitation upon, or waiver of, any privileges and immunities that apply to the Licensor or You, including from the legal processes of any jurisdiction or authority.

==========

Creative Commons is not a party to its public licenses. Notwithstanding, Creative Commons may elect to apply one of its public licenses to material it publishes and in those instances will be considered the Licensor. The text of the Creative Commons public licenses is dedicated to the public domain under the CC0 Public Domain Dedication. Except for the limited purpose of indicating that material is shared under a Creative Commons public license or as otherwise permitted by the Creative Commons policies published at creativecommons.org/policies, Creative Commons does not authorize the

use of the trademark "Creative Commons" or any other trademark or logo
of Creative Commons without its prior written consent including,
without limitation, in connection with any unauthorized modifications
to any of its public licenses or any other arrangements,
understandings, or agreements concerning use of licensed material. For
the avoidance of doubt, this paragraph does not form part of the
public licenses.

Creative Commons may be contacted at creativecommons.org.
0fd2728a9830d6d48af9f61da46f9509

1.1601 webpack-manifest-plugin 2.2.0

1.1601.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) Dane Thurber <dane.thurber@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1602 terser-webpack-plugin 1.4.5

1.1602.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the

'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1603 react-transform-catch-errors 1.0.2

1.1603.1 Available under license :

MIT

1.1604 @webassemblyjs/helper-fsm 1.9.0

1.1604.1 Available under license :

ISC
MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,

OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1605 harbor-elements-utils 0.0.7

1.1605.1 Available under license :

ISC

1.1606 @webassemblyjs/wasm-gen 1.9.0

1.1606.1 Available under license :

MIT
MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1607 @babel/plugin-syntax-throw-expressions 7.22.5

1.1607.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1608 @babel/plugin-transform-modules-systemjs 7.22.11

1.1608.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION

OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1609 postcss-modules-scope 2.2.0

1.1609.1 Available under license :

ISC
ISC License (ISC)

Copyright (c) 2015, Glen Maddern

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.1610 resolve 1.22.5

1.1610.1 Available under license :

ISC
MIT
MIT License

Copyright (c) 2012 James Halliday

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1611 @babel/plugin-proposal-function-sent 7.22.5

1.1611.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1612 @babel/preset-env 7.22.15

1.1612.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including

without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1613 cli-width 1.1.1

1.1613.1 Available under license :

Copyright (c) 2015, Ilya Radchenko <ilya@burstcreations.com>

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1614 des.js 1.1.0

1.1614.1 Available under license :

MIT

1.1615 prepend 1.0.2

1.1615.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 coderaiser

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1616 @babel/plugin-syntax-export-default-from 7.22.5

1.1616.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1617 types-react-redux 7.1.26

1.1617.1 Available under license :

MIT

MIT License

Copyright (c) Microsoft Corporation.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF
CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE

1.1618 @types/scheduler 0.16.3

1.1618.1 Available under license :

MIT

MIT License

Copyright (c) Microsoft Corporation.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal

in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF
CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE

1.1619 figlet 1.6.0

1.1619.1 Available under license :

The MIT License (MIT)

Copyright (C) 2014-present Patrick Gillespie and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.1620 @babel/helper-module-transforms 7.22.19

1.1620.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1621 gulp-conflict 0.4.0

1.1621.1 Available under license :

Copyright 2014 Joakim Bengtson <joakim@klei.se>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1622 react-transform-hmr 1.0.4

1.1622.1 Available under license :

MIT

1.1623 @sinonjs/fake-timers 7.1.2

1.1623.1 Available under license :

BSD-3-Clause
Copyright (c) 2010-2014, Christian Johansen, christian@cjohansen.no. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1624 electron-to-chromium 1.4.523

1.1624.1 Available under license :

Copyright 2018 Kilian Valkhof

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1625 postcss-modules-extract-imports 2.0.0

1.1625.1 Available under license :

ISC
Copyright 2015 Glen Maddern

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.1626 @webassemblyjs/wasm-edit 1.9.0

1.1626.1 Available under license :

MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell

copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1627 and 0.0.3

1.1627.1 Available under license :

Copyright (c) 2018 Thomas Rasshofer <hello@thomasrasshofer.com>

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1628 whatwg-fetch 3.6.19

1.1628.1 Available under license :

Copyright (c) 2014-2023 GitHub, Inc.

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH
 THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1629 raw-loader 3.1.0

1.1629.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.

IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1630 @babel/plugin-transform-async-generator-functions 7.22.15

1.1630.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1631 babel-plugin-transform-runtime 7.22.15

1.1631.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1632 @webassemblyjs/wast-parser 1.9.0

1.1632.1 Available under license :

MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1633 @webassemblyjs/utf8 1.9.0

1.1633.1 Available under license :

MIT
MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1634 @webassemblyjs/helper-code-frame 1.9.0

1.1634.1 Available under license :

MIT
MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all

copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1635 url-loader 2.3.0

1.1635.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1636 vorpal 1.12.0

1.1636.1 Available under license :

(The MIT License)

Copyright (c) 2015-2016 DC <threedeecee@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the

'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1637 core-js-compat 3.32.2

1.1637.1 Available under license :

Copyright (c) 2014-2023 Denis Pushkarev

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.1638 less-loader 5.0.0

1.1638.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1639 @babel/plugin-transform-block-scoping 7.22.15

1.1639.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1640 @webassemblyjs/wast-printer 1.9.0

1.1640.1 Available under license :

MIT
MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1641 @babel/polyfill 7.12.1

1.1641.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining

a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1642 @babel/helper-remap-async-to-generator 7.22.17

1.1642.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,

ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1643 check-types 8.0.3

1.1643.1 Available under license :

MIT
Copyright 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019 Phil Booth

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1644 assert 1.5.1

1.1644.1 Available under license :

MIT
Copyright Joyent, Inc. and other Node contributors. All rights reserved.
Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to
deal in the Software without restriction, including without limitation the
rights to use, copy, modify, merge, publish, distribute, sublicense, and/or
sell copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1645 @webassemblyjs/wasm-opt 1.9.0

1.1645.1 Available under license :

MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1646 inquirer 0.8.5

1.1646.1 Available under license :

MIT

1.1647 @babel/plugin-proposal-function-bind 7.22.5

1.1647.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1648 @webassemblyjs/leb128 1.9.0

1.1648.1 Available under license :

Copyright 2012 The Obvious Corporation.
http://obvious.com/

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

Apache License

Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including
the original version of the Work and any modifications
or additions
to that Work or Derivative Works thereof, that is intentionally
submitted to Licensor for inclusion in the Work by the copyright owner
or by an individual or Legal Entity authorized to submit on behalf of
the copyright owner. For the purposes of this definition, "submitted"
means any form of electronic, verbal, or written communication sent
to the Licensor or its representatives, including but not limited to
communication on electronic mailing lists, source code control systems,
and issue tracking systems that are managed by, or on behalf of, the
Licensor for the purpose of discussing and improving the Work, but
excluding communication that is conspicuously marked or otherwise
designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity
on behalf of whom a Contribution has been received by Licensor and
subsequently incorporated within the Work.

2.
Grant of Copyright License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
copyright license to reproduce, prepare Derivative Works of,
publicly display, publicly perform, sublicense, and distribute the
Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of
this License, each Contributor hereby grants to You a perpetual,
worldwide, non-exclusive, no-charge, royalty-free, irrevocable
(except as stated in this section) patent license to make, have made,
use, offer to sell, sell, import, and otherwise transfer the Work,
where such license applies only to those patent claims licensable
by such Contributor that are necessarily infringed by their
Contribution(s) alone or by combination of their Contribution(s)
with the Work to which such Contribution(s) was submitted.
If You
institute patent litigation against any entity (including a
cross-claim or counterclaim in a lawsuit) alleging that the Work
or a Contribution incorporated within the Work constitutes direct
or contributory patent infringement, then any patent licenses
granted to You under this License for that Work shall terminate
as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without
modifications, and in Source or Object form, provided that You

meet the following conditions:

(a) You must give any other recipients of the Work or
Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices
stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution
notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works
that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions
for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed

with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS
MIT

1.1649 @babel/plugin-syntax-function-bind 7.22.5

1.1649.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1650 @webassemblyjs/ast 1.9.0

1.1650.1 Available under license :

MIT License

Copyright (c) 2018 Sven Sauleau <sven@sauleau.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1651 @webassemblyjs/floating-point-hex-parser 1.9.0

1.1651.1 Available under license :

MIT
MIT License

Copyright (c) 2017 Mauro Bringolf

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1652 webpack-dev-middleware 3.7.3

1.1652.1 Available under license :

MIT
Copyright JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to

permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1653 react-proxy 1.1.8

1.1653.1 Available under license :

MIT

1.1654 gzip-size 5.1.1

1.1654.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1655 readline2 0.1.1

1.1655.1 Available under license :

MIT

1.1656 @babel/traverse 7.22.19

1.1656.1 Available under license :

MIT
MIT License

Copyright (c) 2014-present Sebastian McKenzie and other contributors

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1657 node-localstorage 0.6.0

1.1657.1 Available under license :

MIT

1.1658 gulp-template 5.0.0

1.1658.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1659 react-vtree 3.0.0-beta.3

1.1659.1 Available under license :

MIT License

Copyright (c) 2018-present Vladimir Rindevich

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1660 @jridgewell/resolve-uri 3.1.2

1.1660.1 Available under license :

Copyright 2019 Justin Ridgewell <jridgewell@google.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1661 hazelcast-client-protocol 1.4.1

1.1661.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Original work Copyright 2015 Real Logic Ltd.
* Modified work Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/concurrent/Pipe.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/concurrent/QueuedPipe.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/util/concurrent/AbstractConcurrentArrayQueue.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/util/concurrent/ManyToOneConcurrentArrayQueue.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/util/concurrent/OneToOneConcurrentArrayQueue.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2014, Appear Networks. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/logging/Log4j2Factory.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

```
/**
* <p>
* Aligned {@link MemoryAccessor} which checks for and handles unaligned memory access
* by splitting a larger-size memory operation into several smaller-size ones
* (which have finer-grained alignment requirements).
* </p><p>
* A few notes on this implementation:
* <ul>
*     <li>
*
      There is no atomicity guarantee for unaligned memory accesses.
*       In fact, even on platforms which support unaligned memory accesses,
*       there is no guarantee for atomicity when there is unaligned memory accesses.
*       On later Intel processors, unaligned access within the cache line is atomic,
*       but access that straddles cache lines is not.
*       See http://psy-lob-saw.blogspot.com.tr/2013/07/atomicity-of-unaligned-memory-access-in.html
*       for more details.
*     </li>
*     <li>Unaligned memory access is not supported for CAS operations. </li>
*     <li>Unaligned memory access is not supported for ordered writes. </li>
* </ul>
* </p>
*/
```

Found in path(s):
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/impl/AlignmentAwareMemoryAccessor.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
* Portions Copyright 2016 Real Logic Ltd.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/concurrent/package-info.java

No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/*
* Written by Doug Lea with assistance from members of JCP JSR-166
* Expert Group and released to the public domain, as explained at
* http://creativecommons.org/licenses/publicdomain
*/
```

Found in path(s):
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/ConcurrentReferenceHashMap.java
No license file was found, but licenses were detected in source scan.

```
/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
```

Found in path(s):
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/countdownlatch/CountDownLatchCountDownMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/EntryEventFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/exception/WrongTargetException.java

*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/ConnectionManagerMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/TriggerExplicitSuspicionOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/util/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/LongGauge.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapEvictAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/GetCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/Metric.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/countdownlatch/operations/CountDownLatchReplicationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/console/ConsoleApp.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/client/ReplicatedMapEntries.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/security/permission/CountDownLatchPermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/impl/PublishOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/countdownlatch/CountDownLatchProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/countdownlatch/operations/package-
info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/AbstractMapAllPartitionsMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/task/TrackableJobFuture.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/SubscriberContextSupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/Operation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/PutFromLoadAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/EventServiceMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/event/QueryCacheEventDataBuilder.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/QueryCacheRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/operations/CancelTaskBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapUnlockMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/AtomicLongPermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapRemoveMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/PortableContextImpl.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/CacheLoadAllOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/TxnUnlockBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEventData.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/MemoryManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/request/ExecuteScriptRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ISet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/tcp/TcpIpConnection.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/SizeOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/countdownlatch/operations/CountDownLatchBackupOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/partition/IPartition.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/BetweenVisitor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/invalidation/MetaDataContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/PagingPredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/RemoveInterceptorOperationSupplier.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/Aggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapForceUnlockMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/memory/DefaultGarbageCollectorStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/AndPredicate.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapKeySet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/ReducingJob.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/OperationAccessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapFetchEntriesMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/operation/RequestPartitionProcessed.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheManagementConfigMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/mapstore/writebehind/BoundedWriteBehindQueue.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/ICache.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/usercodedeployment/impl/ClassDataProvider.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/partition/membergroup/ConfigMemberGroupFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/CanCancelOperations.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/BuiltInCacheMergePolicies.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/RingbufferStoreConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/DataRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/durableexecutor/impl/operations/PutResultOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/memory/GCStatsSupport.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/executor/impl/operations/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/task/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/bufferpool/BufferPoolFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/event/QueryCacheEventData.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/CacheEntryProcessorOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/version/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/LongSumAggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/request/GetMapEntryRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/MigrationManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/BuildInfoProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/merge/MergePolicyProvider.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomiclong/operations/GetAndSetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MapFlushBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueTakeMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/semaphore/operations/InitOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/impl/SimpleEntry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/HazelcastManagedContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomiclong/operations/AbstractAtomicLongOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/SplitBrainJoinMessage.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/ascii/memcache/SimpleCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/DeleteOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/multimap/impl/operations/RemoveAllBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/operations/AwaitOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/NoOpCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/ClientEndpointManagerImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/mapstore/writebehind/WriteBehindQueues.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/ListenerWrapperEventFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/TransactionalDistributedObject.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapSizeMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapAddEntryListenerWithPredicateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/task/ReducerTask.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/operations/GetAllScheduledOnPartitionOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/ICredentialsFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheClearOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/impl/TopicEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/IMapEvent.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/eviction/EvictorImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/GetCommandParser.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/logging/Log4jFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/operations/BeforeAwaitOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/record/KeySetIteratorFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/quorum/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/transaction/XATransactionCommitMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/MapStoreManagers.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/lock/LockLockMessageTask.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/subscriber/operation/MadePublishableOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/SemaphoreConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/ConfigPropertiesPlugin.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/set/SetGetAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/MapValuesMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/AbstractMapPartitionMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/operation/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/Index.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/PartitionTableView.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheGetInvalidationMetaDataOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/extractor/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/MemberSocketInterceptor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/EntryOffloadableSetUnlockOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/impl/SupplierConsumingMapper.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/list/ListCompareAndRemoveAllMessageTask.java

* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/publisher/DefaultPublisherContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/JoinMessage.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/IntegerAverageAggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapContainsKeyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transaction/XATransactionRollbackMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/DiagnosticsPlugin.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapServiceContextInterceptorSupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheDestroyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/PartitionStateGenerator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/ByteArraySerializer.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/DefaultMapProjectMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/JavaDefaultSerializers.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/DefaultQueryCache.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/BigDecimalSumAggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/partition/membergroup/SPIAwareMemberGroupFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cluster/memberselector/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/EvictionPolicyComparator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/mapstore/writebehind/WriteBehindManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/operation/ProcessingOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/memory/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/operations/PostJoinClientOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/SecurityConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/packetdispatcher/PacketDispatcher.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/PartitionAware.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomiclong/AtomicLongGetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ExecutionCallback.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/request/ConsoleCommandRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/AbstractSerializationService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/AllowedDuringPassiveState.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/MemcacheEntry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/OperatingSystemMXBeanSupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/AbstractCredentials.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/NamedThreadPoolExecutor.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/TransactionContextImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/queue/operations/CompareAndRemoveOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/PutAllPartitionAwareOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/mapreduce/MapReduceCancelMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/ringbuffer/RingbufferHeadSequenceMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/LoginModuleConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/ErrorCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/invalidation/BatchInvalidator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/UrgentSystemOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/QueryResultUtils.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/ResultProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/recordstore/AbstractEvictableRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/wan/impl/WanDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MapPartitionDestroyTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/StoreConstructor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/InternalEntryListenerAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/ClusterPermissionCollection.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/request/ChangeWanStateRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/memory/impl/UnsafeBasedMemoryAccessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MapStoreConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationservice/impl/TargetInvocation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/codec/AddressCodec.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/IntegerSumAggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/AddDistributedObjectListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/task/JobSupervisor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/PortableMapPartitionLostEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/console/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/ContainsValueOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/DiagnosticsLogWriter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/dto/MXBeansDTO.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/template/TemplateConstants.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/collection/operations/CollectionCompareAndRemoveOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/MembershipServiceEvent.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/semaphore/operations/ReduceBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/SocketConnection.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/ByteArraySerializerAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cardinality/impl/operations/EstimateOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorTaskGetResultFromPartitionMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/FactoryIdHelper.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/TxnUnlockOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/operation/ReplicateUpdateOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/atomicreference/operations/AlterAndGetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/StoreLatencyPlugin.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/transactionalqueue/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/strategy/StringAndPartitionAwarePartitioningStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/IsPartitionLoadedOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/quorum/QuorumEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/operation/PutOperation.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/event/sequence/PartitionSequencer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cardinality/CardinalityEstimator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/atomicreference/operations/GetAndAlterOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/RemoveOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/DoubleSumAggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/AbstractAddressMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/collection/AbstractCollectionProxyImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/Reducer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/ICacheInternal.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/atomiclong/operations/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/LocalWanPublisherStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/subscriber/operation/SetReadCursorOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MapEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/notification/IntermediateChunkNotification.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/exception/ResponseAlreadySentException.java

* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueuePollMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/IdentifiedDataSerializable.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/AggregationResult.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/LikePredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/semaphore/operations/ReduceOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/utils/QueryCacheUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/topic/TopicAddMessageListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/util/ClientMessageReadHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/mapreduce/MapReduceJobProcessInformationMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/wan/impl/WanReplicationServiceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/NodeQueryCacheContext.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/sort/QuickSorter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/TargetAwareTransactionLogRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapPutMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/BuildInfoPlugin.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEventType.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/PartitionReplicaVersions.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/SocketChannelWrapper.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/discovery/multicast/impl/MulticastDiscoverySender.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/PortableFactory.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapEntrySetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/BigIntegerAvgAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/executionservice/impl/DelegateAndSkipOnConcurrentExecutionDecorator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/ClusterStateManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/request/ForceStartNodeRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/membergroup/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/AbstractCacheMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/PagingPredicateAccessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/publisher/PublisherContext.java
*

/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapFlushMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MapIndexConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheIterateEntriesMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalqueue/TransactionalQueuePeekMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cardinality/impl/hyperloglog/impl/HyperLogLogImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/semaphore/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/set/SetContainsAllMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/diagnostics/MemberHazelcastInstanceInfoPlugin.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/collection/operations/CollectionAddOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/operation/VersionResponsePair.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/impl/PartitionStateGeneratorImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/publisher/AccumulatorSweeper.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/NotEqualPredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapKeySetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/filter/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/membergroup/MemberGroupFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/operations/CreateTxBackupLogOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheKeyIterationResult.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/WANQueueFullBehavior.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/adapter/MethodNotAvailable.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapAddPartitionLostListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/xa/operations/ClearRemoteTransactionOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/NearCacheManager.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapContainsValueMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/record/AbstractNearCacheRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/durableexecutor/DurableExecutorServiceFuture.java

* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/ExecutorServiceCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/operation/ReplicaSyncRetryResponse.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/GetDistributedObjectsMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/list/ListRemoveMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/QueryOptimizer.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/EntryAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/SortingUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MemberLeftException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/xa/operations/FinalizeRemoteTransactionOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/client/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/PutOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/CachePutIfAbsentOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/MultipleEntryBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txncollection/operations/CollectionCommitOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/AsyncAtomicLong.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/InPredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cardinality/impl/CardinalityEstimatorContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/ExecutorServicePermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/rest/HttpGetCommandParser.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/osgi/impl/OSGiScriptEngineManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapIsEmptyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/SerializationUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorSubmitToPartitionMessageTask.ja
va
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ListConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/AuthenticationBaseMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/mapstore/writethrough/WriteThroughStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/IndexStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/annotation/PrivateApi.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/idgen/IdGeneratorService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEntryProcessorResult.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/event/BatchIMapEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/QueueConfigReadOnly.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapAddEntryListenerWithPredicateMessageTask.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/AtomicLongMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheSizeOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/MultiResultSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/AuthenticationStatus.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/txn/TxnRemoveAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/subscriber/record/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/CombinerFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/annotation/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/PartitionReplicaStateChecker.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/atomiclong/AtomicLongProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/RemoveAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/ClusterDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheReplicationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/txn/TransactionalMultiMapProxySupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/lock/LockIsLockedByCurrentThreadMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/HotRestartState.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ListConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/usercodedeployment/impl/UserCodeDeploymentSerializerHook.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationservice/impl/InvocationMonitor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/list/operations/ListIndexOfOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/UnsortedIndexStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/client/MapPortableHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/subscriber/operation/MadePublishableOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapUnlockMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/ObjectNamespace.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/config/ConfigValidator.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationservice/impl/InvocationFuture.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/lock/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/hashslot/impl/CapacityUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/SetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/SuffixModifierUtils.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/executor/impl/operations/ShutdownOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/collection/operations/CollectionAddBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transaction/XATransactionPrepareMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomiclong/AtomicLongAlterMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/impl/strategy/sampling/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/NotPredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationexecutor/OperationRunner.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/ReplaceOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/PartitionPredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/tcp/ClientWriteHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/mapstore/writebehind/entry/DeletedDelayedEntry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/AbstractCacheConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/ReplicatedMapMBean.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/hashslot/HashSlotArray8byteKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/PartitionListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/impl/Versioned.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/eventservice/impl/operations/RegistrationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/hotrestart/NoopInternalHotRestartService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/preloader/NearCachePreloader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/KeyValueSource.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/eviction/MapEvictionPolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/AwsConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/Stats.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationparker/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapAddEntryListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/executor/impl/ExecutorDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/config/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/DiscardableMetricsProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/nonblocking/iobalancer/IOBalancerThread.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/MemberRemoveOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/RemoveIfSameOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/HealthMonitorLevel.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/partitiongroup/PartitionGroupMetaData.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/map/impl/querycache/accumulator/BasicAccumulator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/TransactionalQueue.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/ReplicatedMapSplitBrainHandlerService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/partition/membergroup/MemberGroupFactoryFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/MapOperationProviderDelegator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/AbstractPredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/AbstractCacheClientNearCacheInvalidationListener.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/PartitionStateVersionMismatchException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/iterator/MapKeysWithCursor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/query/impl/predicates/AbstractIndexAwarePredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/invalidation/MetaDataGenerator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/exception/CallerNotMemberException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/exception/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/TopicMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/RingbufferStoreWrapper.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/GroupMismatchOp.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/AddressUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/merge/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/HazelcastInstanceCacheManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueSizeMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/list/ListRemoveListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CachePutIfAbsentMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/event/CachePartitionLostListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/mapreduce/MapReduceForCustomMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapDataSerializerHook.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/AbstractSubscriberContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapContainsValueMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/TransactionManagerService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ConfigurationException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/ScheduledExecutorServiceProxy.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/subscriber/record/QueryCacheRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/function/LongLongConsumer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/operations/GetStatisticsOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/LatencyTrackingCacheLoader.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ConfigPatternMatcher.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/nonblocking/SelectorOptimizer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/LatencyTrackingQueueStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/operations/GetRemainingLeaseTimeOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/event/sequence/DefaultSubscriberSequencerProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/QueueOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorTaskGetDelayFromPartitionMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/impl/record/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/QueryDispatcher.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/impl/DefaultNearCache.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/cache/CacheClearMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/PropertyExtractor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/operation/RequestPartitionMapping.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/MemberState.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/EvictionPolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/list/ListClearMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/matcher/LegacyWildcardConfigPatternMatcher.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/wan/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/AtomicReferencePermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MultipleEntryWithPredicateBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/QueueService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/operation/GetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/operations/UnlockOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/operations/GetAllScheduledOnMemberOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/partition/IPartitionLostEvent.java

*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/IOOutOfMemoryHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/scheduler/EntryTaskSchedulerFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/TxnReservePollBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/set/SetAddAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/LatencyTrackingMapLoader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/util/ClientMessageSplitter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/ArrayDataSerializableFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/DistinctValuesAggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/config/CacheSimpleEntryListenerConfigReadOnly.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/lock/operations/BeforeAwaitBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/MultiMapKeyValueSource.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/task/KeyValueSourceMappingPhase.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/invalidation/BatchNearCacheInvalidation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/executorservice/ExecutorServiceSubmitToAddressMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/TransactionImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/SystemPropertiesPlugin.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/SplitBrainMergeValidationOp.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueDrainMaxSizeMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/durableexecutor/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/discovery/integration/DiscoveryServiceProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/TxnRollbackBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MapStoreConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/VersionMismatchException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/executor/impl/CancellableDelegatingFuture.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/TransactionException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/notification/LastChunkNotification.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/ReplicatedMapProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomicreference/AtomicReferenceGetAndAlterMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapPutIfAbsentMessageTask.java

* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapLockMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/TxnOfferOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/operations/AddAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationservice/impl/operations/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationservice/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapValuesMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/filter/Filter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/TransactionalTaskContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/proxyservice/impl/DistributedObjectEventPacket.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/MapPermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/executorservice/ExecutorServiceCancelOnAddressMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/event/sequence/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/AbstractMapAddEntryListenerMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/adapter/TransactionalMapDataStructureAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/rest/RestValue.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/invalidation/ToHeapDataConverter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/semaphore/operations/SemaphoreReplicationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/LocalMapStatsProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MapStoreFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/extractor/ValueExtractor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/SingleExecutorThreadFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/ThisGetter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/event/EntryEventData.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/writebehind/StoreListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/set/operations/SetReplicationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/FetchMembersViewOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/WanReplicationConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/mapreduce/MapReduceForMapMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/AbstractCacheService.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/map/impl/querycache/subscriber/record/ObjectQueryCacheRecordFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transaction/XAFinalizeTransactionMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/NullGetter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationexecutor/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/KeyPredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomicreference/operations/AtomicReferenceReplicationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/HazelcastThreadGroup.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/memory/impl/CustomByteAccessStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapAddEntryListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/publisher/PublisherRegistry.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/ScheduledExecutorMemberOwnedContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ManagedContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/ReplicationSupportingService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/DoubleProbeFunction.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/partition/MigrationEndpoint.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/semaphore/operations/ReleaseOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalset/TransactionalSetRemoveMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MessageListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/LocalExecutorStatsImpl.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalset/TransactionalSetSizeMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/DefaultMessageTaskFactoryProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/LockConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/tcp/InitConnectionTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapSubmitToKeyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ICondition.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/NodeMulticastListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/ReplicatedMapService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/task/KeyValueJob.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/MapStoreManager.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/atomiclong/operations/GetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/TypedByteArrayDeserializer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/logging/NoLogFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/discovery/NodeFilter.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/transactionalqueue/TransactionalQueueOfferMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/SlowOperationPlugin.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/AbstractInvocationFuture.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/JobCompletableFuture.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/PhoneHome.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/EntryOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/nearcache/invalidation/MemberMapMetaDataFetcher.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationexecutor/OperationRunnerFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/EvictionChecker.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/CompoundPredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/operation/NotifyRemoteExceptionOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/semaphore/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/MapAssignAndGetUuidsOperation.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/UsernamePasswordCredentials.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/JCacheDetector.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/PartitionDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/QueueContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/event/FilteringStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/Extractors.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/exception/RetryableHazelcastException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/executor/impl/RunnableAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/wan/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/operation/PartitionStateOperation.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/operations/AbstractSchedulerOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/nonblocking/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/usercodedeployment/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationservice/impl/OperationServiceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/function/Supplier.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/suppliers/LocalQueueStatsSupplier.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/executorservice/ExecutorServiceSubmitToPartitionMessageTask.java
*

/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/impl/invalidation/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/proxyservice/impl/operations/PostJoinProxyOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/TransactionalQueueProxySupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/EventRegistration.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/collection/operations/CollectionReplicationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/dto/MapConfigDTO.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/queue/operations/IsEmptyOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/durableexecutor/impl/operations/RetrieveResultOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/CachedQueryEntry.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapAssignAndGetUuidsOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/PartitionAwareOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/merge/PassThroughCacheMergePolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/responses/BackupAckResponse.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/QueueStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/DefaultSerializationServiceBuilder.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/bufferpool/BufferPool.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/LifecycleServiceImpl.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/WanConsumerConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ReplicatedMapConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/EventLostEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/ProbeLevel.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/AbstractQueryCacheConfigurator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/SharedService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/Versions.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/DiagnosticsLogFile.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CachePutAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/ObjectRecord.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/IntegerAvgAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ServiceConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/durableexecutor/impl/DurableExecutorContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/event/CachePartitionLostEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/NodeIOService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/TopicOverloadException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/LifecycleMapperAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/scheduledexecutor/impl/operations/ResultReadyNotifyOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/tcp/ClientReadHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/MasterConfirmationOp.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapEvictMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/cache/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/PartitionContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transaction/XACollectTransactionsMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/CoreService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/exception/DistributedObjectDestroyedException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomicreference/operations/CompareAndSetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapKeySetWithPagingPredicateMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/QueueProxyImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/set/SetContainsMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorTaskIsCancelledFromAddressMes
sageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MigrationListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/MapServiceContextEventListenerSupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/OwnedEntryCostEstimatorFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/MapDataStores.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cardinality/impl/CardinalityEstimatorProxy.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/ComparisonType.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/eventservice/impl/EventServiceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cardinality/impl/hyperloglog/impl/DenseHyperLogLogEncoder.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/LocalMemoryStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/ContainsKeyOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/event/sequence/Sequenced.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/CacheKeyIteratorOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionallist/TransactionalListSizeMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/discovery/DiscoveryNode.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/impl/preloader/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/MapReducePermission.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/collection/operations/CollectionAddAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/replicatedmap/AbstractReplicatedMapAddEntryListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/ClusterStateChange.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/impl/comparator/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/listener/EntryAddedListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/GreaterLessPredicate.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/DefaultNodeExtension.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/CacheConfiguration.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/executorservice/durable/DurableExecutorDisposeResultMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/atomicreference/AtomicReferenceCompareAndSetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/EntryViews.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/QueueDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/ServiceLoader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/MapReduceService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/NodeExtension.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorTaskDisposeFromPartitionMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheListenerRegistrationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/ManagedExecutorService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/impl/DoubleMinAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/impl/MethodProbe.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapReplaceIfSameMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/DrainOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/semaphore/operations/DrainOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/ClusterJoinManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/impl/UnsafeUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/WanReplicationRefReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/NodeEngine.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEventContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MapLoader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/NoDataMemberInClusterException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationexecutor/package-info.java

* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/merge/HigherHitsMapMergePolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapServiceContext.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/operations/MergeClustersOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/writebehind/StoreEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/RandomPicker.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/Data.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/operation/SyncReplicatedMapDataOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/SetPermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/condition/ConditionSignalAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/CacheCreateConfigOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/impl/store/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/record/DataQueryCacheRecordFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/impl/invalidation/Invalidator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/IsPartitionLoadedOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/quorum/impl/QuorumServiceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/topic/TopicRemoveMessageListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/PredicateConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/MultiMapProxySupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/XmlConfigBuilder.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/operation/SafeStateCheckOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/MethodGetter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/CollectRemoteTransactionsOperationSupplier.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/writebehind/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/scheduler/ScheduledEntry.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapMadePublishableMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapKeySetWithPredicateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/PredicateBuilder.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/RemoveFromLoadAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/sort/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/extractor/ArgumentParser.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cardinality/impl/CardinalityEstimatorDataSerializerHook.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cardinality/impl/hyperloglog/impl/HyperLogLogEncoding.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/hotrestart/HotRestartService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/WanPublisherConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MapFlushOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/SecurityContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationservice/impl/responses/Response.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/InternalSetMultimap.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/record/CacheRecordHashMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/ringbuffer/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/ManagedExecutorServiceMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/logging/AbstractLogger.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/Credentials.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/ClusterMergeTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/AbstractInvocationMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cluster/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ConfigXmlGenerator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationservice/impl/InboundResponseHandler.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/LockStoreImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/request/ThreadDumpRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/EvictOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/topic/TopicPublishMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/cache/CacheGetAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/ClearOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/LegacyAsyncMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/codec/CacheEventDataCodec.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/TransactionalMultiMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/AllowedDuringPassiveStateTransactionImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/subscriber/operation/DestroyQueryCacheOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/list/ListIteratorMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/CheckReplicaVersionTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/template/TransactionalMapCodecTemplate.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/record/EntrySetIteratorFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEventContextUtil.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/QueueStoreFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapContainsKeyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/EvictionConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/collection/LongCursor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/list/ListIndexOfMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/ExtractorHelper.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/impl/store/AbstractNearCacheRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/impl/MemoryManagerBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationservice/impl/InvocationBuilderImpl.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/ManagementCenterService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MapReplicationStateHolder.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/recordstore/Storage.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/impl/record/NearCacheObjectRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/memory/MemoryUnit.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/record/ObjectReplicatedRecordStorage.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/template/AtomicReferenceCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/DefaultAddressPicker.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/ClientDataSerializerHook.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/operation/BeforePromotionOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/accumulator/DefaultAccumulatorInfoSupplier.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/listener/EntryRemovedListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/IteratorOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/txnqueue/TransactionLogRecordKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/MapExecuteWithPredicateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/WANAwareOperationProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/template/TransactionalListCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/cache/CacheGetAndReplaceMessageTask.java

*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/TransactionalCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/HazelcastInstance.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/CachedDataRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/store/NearCacheDataRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/BaseTxnQueueOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationservice/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/properties/ValidationException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/QueueMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/GroupConfig.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/AbstractAllPartitionsMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cluster/ClusterState.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/CompositeEvictionChecker.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/LongProbeFunction.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/BetweenPredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/responses/NormalResponse.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/console/LineReader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapStatisticsAwareService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/TriggerMemberListPublishOp.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/HotRestartClusterDataRecoveryPolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/operations/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/AtomicLongCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/constants/EventMessageConst.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/client/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomicreference/AtomicReferenceSetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/countdownlatch/LatchKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/OperationServiceMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/AddIndexOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/packetdispatcher/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/proxyservice/impl/ProxyInfo.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/QueueEvictionProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/ScheduledExecutorDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/PartitionAwareKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/ManagementService.java

* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/QueryCacheEndToEndProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/txn/TxnRollbackOperation.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapIsEmptyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/MapStoreContextFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/AbstractPartitionMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationparker/OperationParker.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/PartitionStateManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/CommitClusterStateOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapForceUnlockMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/GetAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/LockResource.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/invalidation/NonStopInvalidator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/DefaultMapAggregateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/LockStoreContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/AbstractAggregationCombinerFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapTryLockMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueCompareAndRemoveAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/NopPartitionListener.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/projection/impl/MultiAttributeProjection.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/StatefulTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/ItemCounter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/TxnReservePollOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/TransactionalMapProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/EventListenerFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/BigIntegerMaxAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/function/IntFunction.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomicreference/AtomicReferenceApplyMessageTask.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/RingbufferProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ScheduledExecutorConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/map/impl/querycache/subscriber/QueryCacheEndToEndConstructor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/ResultProcessorRegistry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/Records.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/SpiPortableHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/client/DistributedObjectInfo.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapGetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cardinality/impl/operations/ReplicationOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapLoadAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheMXBeanImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/listener/MapListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ReliableTopicConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MembershipAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/ObjectRecordWithStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/eventservice/impl/RemoteEventProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEntryCountResolver.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/operation/RequestPartitionReducing.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/list/operations/ListReplicationOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CachePutOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ConfigBuilder.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/operation/SizeOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/merge/PassThroughMergePolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/request/GetMemberSystemPropertiesRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/codec/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/MemoryInfoAccessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/hashslot/HashSlotArray.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/OperationDescriptors.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/LongAverageAggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/nonblocking/MigratableHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/PartitionWideEntryOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/dto/ProxyServiceDTO.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/durableexecutor/impl/operations/DisposeResultOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/ByteAccessStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/countdownlatch/CountDownLatchService.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/executionservice/impl/ExecutionServiceImpl.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/nonblocking/SelectorMode.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/memory/GarbageCollectorStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapValuesWithPredicateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/suppliers/LocalMapStatsSupplier.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/MapAddInterceptorMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/queue/QueuePutMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/recordstore/StorageImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/list/operations/ListSetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/BaseRemoveOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/PartitionLostListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/record/AbstractBaseReplicatedRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/StorageTypeAwareCacheMergePolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/osgi/impl/OSGiScriptEngineFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/dto/OperationServiceDTO.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationexecutor/impl/GenericOperationThread.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/LocalMapStatsImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/semaphore/operations/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/InternalPartitionService.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/InvocationPlugin.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/MemoryAccessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/JsonUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/MapSizeMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/DataSerializableSerializer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/NearCache.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/MultiMapValue.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/LocalReplicatedMapStatsImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheRemoveAllOperationFactory.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/DataSerializable.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/Context.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/MembershipManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/impl/BigIntegerMinAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/internal/util/concurrent/ConcurrentConveyorSingleQueue.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/ICacheService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cardinality/impl/operations/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheAddPartitionLostListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/operation/GetResultOperationFactory.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/condition/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/Expirable.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheGetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomicreference/operations/AtomicReferenceBackupAwareOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cardinality/impl/hyperloglog/impl/SparseHyperLogLogEncoder.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/request/GetCacheEntryRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/ListCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/countdownlatch/CountDownLatchGetCountMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/invalidation/SingleNearCacheInvalidation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapRecordKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/MemberPartitionStateImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/AbstractQueryCacheEndToEndConstructor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/AbstractTextCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/FixedSumAggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/list/ListGetAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/codec/MemberCodec.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/TextCommandService.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/OutOfMemoryHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/usercodedeployment/impl/filter/MemberAttributeFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/SerializableByConvention.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/LocalCacheStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/semaphore/operations/ReleaseBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/StaleTaskException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/eviction/impl/comparator/LFUEvictionPolicyComparator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/QueryResultIterator.java

*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/event/MapEventPublisher.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/MapCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/PartitionService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/InstancePermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheEntryProcessorMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/ClientEngineMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/CacheGetAndRemoveOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/servicemanager/impl/ServiceManagerImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/PermissionPolicyConfig.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/BackpressureRegulator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/collection/CollectionEventFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/query/CallerRunsAccumulationExecutor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/NodeSubscriberContextSupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/CacheEntryView.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapGetEntryViewMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/properties/SimplePropertyDefinition.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/BaseMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapClearMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/operations/ShutdownOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cardinality/impl/operations/AggregateOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapClientAwareService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/PacketHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/SocketWriter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/QueryCacheRecordHashMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/BitSetUtils.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/TransactionOptions.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/Collator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalqueue/TransactionalQueueSizeMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationexecutor/impl/PartitionOperationThread.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/logging/LogListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/internal/serialization/impl/bufferpool/BufferPoolImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/ClusterClock.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/multimap/impl/txn/TxnRemoveBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomiclong/AtomicLongIncrementAndGetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/Supplier.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomicreference/AtomicReferenceAlterMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/queue/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/EventPublishingService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/FastMultiResultSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmultimap/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/HazelcastInstanceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/event/AbstractEventData.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/operation/ReplicaSyncRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomicreference/operations/SetAndGetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/NativeMemoryConfig.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/proxy/MapProxySupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/condition/ConditionAwaitMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomicreference/AtomicReferenceGetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/list/ListAddAllWithIndexMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapContainsKeyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/countdownlatch/operations/GetCountOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transaction/XAClearRemoteTransactionMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MapOperationProvider.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/proxyservice/impl/ProxyRegistry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/xa/SerializableXID.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/operations/ReadOneOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/EventPublisherHelper.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/invalidation/MetaDataFetcher.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/partition/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/ClusterService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/MutableInteger.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/codec/ErrorCodec.java

*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/PortableWriter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/operation/ReplicatedMapDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/VersionedObjectDataOutput.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/SecurityInterceptor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/event/DefaultQueryCacheEventData.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/MigrationAwareService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/mapstore/writebehind/entry/AddedDelayedEntry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/ConsoleCommandHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/NodeQueryCacheConfigurator.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomicreference/AtomicReferenceAlterAndGetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/AbstractInternalCacheProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/PartitionMigrationEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapKeySetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/operations/GetResultOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/PortableCachePartitionLostEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/multimap/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/EvictableStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/metrics/metricsets/OperatingSystemMetricSet.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/operation/MigrationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/projection/impl/ProjectionDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/NearCacheRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/CallsPerMember.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomiclong/operations/AddAndGetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapPutMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/ClusterStateTransactionLogRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/SecurityInterceptorConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/eviction/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/request/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/LocalStatsDelegate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/executionservice/impl/CompletableFutureEntry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/LockProxySupport.java

* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/ringbuffer/RingbufferReadOneMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/semaphore/operations/AcquireOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/PortablePositionFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MultipleEntryOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MigrationEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/txn/TxnPutOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/TxnReserveOfferOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/txn/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CachePartitionSegment.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/list/ListRemoveWithIndexMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/operations/SignalOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/ByteArrayObjectDataOutput.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/ClassDefinitionBuilder.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomiclong/operations/GetAndAddOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/operation/BaseMigrationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/LockAwareLazyMapEntry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/osgi/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/QueryCacheEventService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/InterceptorRegistry.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/UnsafeInputOutputFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/EntryBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/event/sequence/DefaultPartitionSequencer.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/codec/QueryCacheEventDataCodec.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/merge/PutIfAbsentMapMergePolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/MapReduceSimpleEntry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/txn/TxnLockAndGetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/xa/TransactionAccessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/impl/LockStripe.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/record/RecordMigrationInfo.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionallist/TransactionalListAddMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/AbstractCacheOperation.java
*

/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/xa/operations/ClearRemoteTransactionBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/impl/NearCacheRecordMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/rest/HttpCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/EntryListenerConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/impl/AbstractGauge.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/OrResultSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/MultiMapEventFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/HazelcastXAResource.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/QueryException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/Evictable.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/rest/HttpDeleteCommandParser.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/TransactionPermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/RuleBasedQueryOptimizer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/QueryOptimizerFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/MapPartitionLostEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/impl/AggType.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/GetterFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/UserCodeDeploymentConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/dto/SlowOperationDTO.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/maxsize/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheEntryIteratorOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/collection/Long2LongMapHsa.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/txncollection/CollectionTxnOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/PredicateConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/request/ChangeClusterStateRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/AccumulatorConsumerOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/WanSyncState.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/PartitionEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/operations/DisposeTaskOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/partitiongroup/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/JobTrackerConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/ConfigMismatchException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/NullEntryView.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/template/SemaphoreCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/AbstractScheduledExecutorContainerHolder.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/TimedMemberState.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/codec/StackTraceElementCodec.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/usercodedeployment/impl/filter/MemberProviderFilterParser.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/event/InternalCachePartitionLostListenerAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/ICacheRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheRemoveAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/cache/CacheAssignAndGetUuidsOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/SerializationServiceBuilder.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/durableexecutor/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/NamedTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/ClassDefinitionImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/ClearOperationFactory.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/usercodedeployment/impl/ClassData.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/accumulator/CyclicBuffer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/merge/PutIfAbsentMapMergePolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/scheduler/SecondsBasedEntryTaskScheduler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/SplitBrainMulticastListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/LiveOperationsTracker.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorTaskIsDoneFromAddressMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/merge/LatestUpdateMapMergePolicy.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/impl/CountAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/RingbufferWaitNotifyKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/LocalInstanceStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/operations/OperationFactoryWrapper.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/publisher/QueryCacheListenerRegistry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/MapStoreContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/DefaultObjectNamespace.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/hashslot/HashSlotCursor16byteKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/operations/GetDelayOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/tcp/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/collection/CollectionContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/PartitionWideCacheOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/client/impl/protocol/task/map/MapAggregateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/OperationResponseHandlerFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapValueCollection.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/ListenerRegistrationHelper.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/operation/ChangeWanStateOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/invalidation/InvalidationUtils.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/task/JobProcessInformationImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapExecuteOnKeyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/nonblocking/iobalancer/MonkeyMigrationStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheLoadAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/tcp/SocketWriterInitializerImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cluster/memberselector/AndMemberSelector.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/set/SetCompareAndRemoveAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/security/permission/DurableExecutorServicePermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorTaskGetResultFromAddressMess
ageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/xa/operations/PutRemoteTransactionBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/MapTxnOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/InternalPartitionImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/properties/PropertyDefinition.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/MapReduceDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/osgi/impl/HazelcastOSGiServiceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/executor/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/DuplicateDetectingMultiResult.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/version/Version.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/ascii/memcache/DeleteCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/operation/FinalizeMigrationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheRemoveMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/record/LazySet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/util/ClientProtocolBuffer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/LockProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/transaction/impl/xa/operations/PutRemoteTransactionOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/MultiMapRecord.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/StateMachine.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/NearCacheStatsImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/store/HeapNearCacheRecordMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/DiscoveryConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/set/SetAddMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/IOThreadingModel.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/DefaultPortableWriter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/record/ValuesIteratorFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/ConnectionType.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cardinality/impl/operations/CardinalityEstimatorBackupAwareOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/list/ListContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/txnqueue/TxQueueItem.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/publisher/EventPublisherAccumulatorProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/projection/Projection.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/LockDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapContainsEntryMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/NearCacheConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ClientType.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/CacheRemoveBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/operation/HasOngoingMigration.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/logging/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationparker/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/operations/AbstractGetAllScheduledOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/spinning/AbstractHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/countdownlatch/operations/BackupAwareCountDownLatchOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/serialization/SerializationService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/wan/WANReplicationQueueFullException.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/FalsePredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/quorum/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheReplaceOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/counters/Counter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/TouchCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/PeekOperation.java

* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/accumulator/AbstractAccumulator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/lock/operations/LocalLockCleanupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ClientListener.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MapOperationProviders.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomicreference/operations/GetAndSetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/atomicreference/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/eventservice/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/collection/operations/CollectionClearBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/dto/WanReplicationConfigDTO.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/ScheduledRunnableAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/MultiMapPermission.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/operation/ShutdownResponseOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/BasicMapStoreContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/ListKeyValueSource.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/executor/impl/operations/MemberCallableTaskOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/EmptyMapDataStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/CacheClearBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/extractor/ValueCallback.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/FlatteningVisitor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapRemoveInterceptorMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/EntryListenerConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/quorum/impl/operation/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/set/SetSizeMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/task/DefaultContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/IScheduledExecutorService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/BigDecimalMinAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/DoubleSumAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ItemListenerConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/TxnPollBackupOperation.java

*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/listener/EntryEvictedListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/event/EntryEventDataCache.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomiclong/AtomicLongSetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/iterator/MapPartitionIterator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/osgi/HazelcastOSGiInstance.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/BlockingOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/BigIntegerSumAggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/EntryConverter.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/spinning/SpinningInputThread.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/ascii/memcache/StatsCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/PartitionServiceMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/QueryCacheConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/NodeSubscriberContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/HazelcastManagedThread.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/operations/PurgeTxBackupLogOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/IsEmptyOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/IterableUtil.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/mapreduce/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/properties/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/MigrationCycleOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/NodeQueryCacheEndToEndConstructor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/HotRestartStateImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/PortablePathCursor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/event/ICacheEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/util/ParameterUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/EntryBackupProcessor.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/TopicOverloadPolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/semaphore/operations/InitBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/Bits.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/eventservice/impl/TrueEventFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/executorservice/durable/DurableExecutorSubmitToPartitionMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueContainsMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/HeapMemoryAccessor.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/sort/MemArrayQuickSorter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/operation/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/QueryCacheRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/executionservice/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/durableexecutor/impl/operations/DurableExecutorWaitNotifyKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/mapreduce/MapReduceForListMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/IntegerMaxAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/TransactionalTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/impl/PartitionLostListenerAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/adapter/DataStructureAdapterMethod.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheAssignAndGetUuidsMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorTaskIsCancelledFromPartitionMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/operation/AbstractPromotionOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/NotifyMapFlushOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/TxnRollbackBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/DataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/event/sequence/SubscriberSequencerProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/AndResultSet.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/eventservice/impl/EventServiceSegment.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/NodeMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/concurrent/IdleStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/version/MajorMinorVersionComparator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationutil/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MapConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/recordstore/RecordStoreLoader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/record/CacheRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/ClientEngine.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/NodeState.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/PromoteLiteMemberOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/BufferingInputStream.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/tcp/MemberWriteHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/ringbuffer/impl/LatencyTrackingRingbufferStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/LockAware.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/DoubleMaxAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/durableexecutor/impl/DurableExecutorDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/OutboundFrame.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/AbstractJobTracker.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/IOService.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomiclong/AtomicLongDecrementAndGetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/operation/AddWanConfigOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/transaction/package-
info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/FieldType.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/operations/PartitionAwareOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/utils/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/mapreduce/MapReduceForSetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/InternalCompletableFuture.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/IntegerSumAggregation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/NoSuchMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/TxnSetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ICountDownLatch.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/TxnPeekOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/record/InternalReplicatedMapStorage.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationexecutor/OperationHostileThread.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/HazelcastInstanceNotActiveException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/record/ObjectQueryCacheRecord.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/AbstractClusterOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/QueryResultProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/writethrough/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/semaphore/operations/SemaphoreDetachMemberBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomicreference/AtomicReferenceService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/MapReducePortableHook.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/impl/maxsize/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/event/AbstractFilteringStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/JetBuildInfo.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/collection/LongSetHsa.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ListenerConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/NetworkConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/PartitionWideEntryBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapFetchKeysMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/extractor/ValueReader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/MapMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapLoadGivenKeysMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/TxnCommitBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MemberGroupConfig.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/CacheSimpleConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/WanAcknowledgeType.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/recordstore/DefaultRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ListenerConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapServiceFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/RingbufferExpirationPolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/LoggingScheduledExecutor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/ClearOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/operations/GenericOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/preloader/NearCachePreloaderLock.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapStoreWrapper.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/TxnOfferBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/DurableExecutorConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheStatisticsMXBeanImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/AggregatorDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/AbstractConfigBuilder.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/SimpleCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/tcp/DefaultSocketChannelWrapperFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/executor/impl/DistributedExecutorService.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/QueueStoreWrapper.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/wan/MapReplicationUpdate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/suppliers/StatsSupplier.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CachePutMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/client/impl/protocol/task/map/MapPublisherCreateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/metrics/metricsets/GarbageCollectionMetricSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/record/ReplicatedEntryEventFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/membergroup/SingleMemberGroup.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapRemoveMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapDeleteMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/impl/LongGaugeImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MapIsEmptyOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/set/SetRemoveListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmultimap/TransactionalMultiMapPutMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/Extractable.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/hashslot/HashSlotArray16byteKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cardinality/impl/hyperloglog/impl/HyperLogLogEncoder.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MaxSizeConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapRemoteService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorTaskGetStatisticsFromAddressMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/NamedTaskDecorator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/operation/RequestMemberIdAssignment.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txncollection/operations/CollectionTxnAddBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomiclong/operations/ApplyOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/lock/operations/SignalBackupOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/ClientServiceProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/TransactionContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/queue/operations/PollBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/semaphore/operations/SemaphoreOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/QueryContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/publisher/MapPublisherRegistry.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapProjectionWithPredicateMessageTask.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/ReAuthenticationOperationSupplier.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/listener/EntryExpiredListener.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/AbstractHazelcastCachingProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapAddEntryListenerToKeyWithPredicateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/InvokeOnPartitions.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/request/MapConfigRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/SqlPredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/rest/HttpPostCommandParser.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/MasterResponseOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/MD5Util.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/usercodedeployment/impl/filter/ClassBlacklistFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/countdownlatch/operations/AwaitOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheAddEntryListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/ClusterPermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomiclong/operations/CompareAndSetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/eviction/impl/strategy/sampling/SamplingEvictionStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/Query.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/operation/PutAllOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/ClockProperties.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/QueryCache.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/Disposable.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/adapter/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/impl/EndiannessUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/UndefinedErrorCodeException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/ParallelPartitionScanExecutor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/ConcurrencyUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/QueryCacheConfig.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/AuthenticationFailureOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/usercodedeployment/impl/GlobalMutex.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/security/permission/CardinalityEstimatorPermission.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/Aggregators.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/semaphore/operations/SemaphoreBackupAwareOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/operations/FinalizeJoinOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/Ringbuffer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/properties/PropertyTypeConverter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/ascii/memcache/IncrementCommandProcessor.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/PartitionServiceProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/record/ReplicatedRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/eventservice/InternalEventService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/record/AbstractQueryCacheRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/CacheBackupEntryProcessorOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/StaleSequenceException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheReplaceMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/ExplicitSuspicionOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cardinality/impl/hyperloglog/HyperLogLog.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/DelegatingFuture.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MergeOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/RemoteService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheSplitBrainHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapEntries.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/ConditionCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/impl/invalidation/Invalidation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/AddIndexOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/operation/AbstractManagementOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/AuthenticationCustomCredentialsMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/ReplicatedMapCantBeCreatedOnLiteMemberException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmultimap/TransactionalMultiMapGetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomicreference/operations/IsNullOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationexecutor/slowoperationdetector/SlowOperationLog.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/OperationBackupHandler.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/writebehind/CoalescedWriteBehindQueue.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/AddAllBackupOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/event/AbstractICacheEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CachePutBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/Client.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/metricsets/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/SocketReader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/quorum/Quorum.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/PostJoinAwareService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/NearCachePreloaderConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/Predicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEntryProcessorEntry.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/ClientHeartbeatMonitor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cluster/memberselector/OrMemberSelector.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MemberAttributeConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/MapTransactionLogRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/HotRestartPersistenceConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/cache/AbstractCacheAllPartitionsTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/ClientEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/atomiclong/AtomicLongGetAndIncrementMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/osgi/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/SerializerHookLoader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/hotrestart/NoOpHotRestartService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cardinality/impl/operations/AbstractCardinalityEstimatorOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/collection/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/operation/KeysAssignmentOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/operation/GetResultOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/OrPredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/impl/DataAwareMessage.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/impl/invalidation/StaleReadDetector.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/SerializationConstants.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/function/BiConsumer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/AbstractMapClientNearCacheInvalidationListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/operation/ProcessStatsUpdateOperation.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/UnmodifiableLazyList.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/list/operations/ListAddOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/KeyLoadStatusOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/ClientEndpointManager.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/Hazelcast.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ManagementCenterConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/ScheduledTaskDescriptor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationparker/impl/ParkedOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/discovery/DiscoveryStrategyFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/subscriber/operation/package-
info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/writebehind/StoreWorker.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/DistinctValuesAggregation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/QueryResultSizeLimiter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/SerializerConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/EntryRemovingProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/AbstractLocalOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapPutMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/queue/operations/ContainsOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ReplicatedMapConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/dto/SlowOperationInvocationDTO.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/filter/AndFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/tcp/DefaultSocketChannelWrapper.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/EmptyObjectDataOutput.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomicreference/operations/AbstractAtomicReferenceOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/CacheEvictionConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/PutTransientOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/CacheUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/impl/PredicateSupplier.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/server/StartServer.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/usercodedeployment/UserCodeDeploymentClassLoader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/ManagedDescription.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/SpiDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/ScheduledTaskStatisticsImpl.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/impl/TopicProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/idgen/IdGeneratorImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/usercodedeployment/UserCodeDeploymentService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/record/CacheDataRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/nio/serialization/impl/VersionedDataSerializableFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/BindMessage.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/ScheduledTaskResult.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapClearMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/impl/TotalOrderedTopicProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/HazelcastInstanceFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/accumulator/AccumulatorScannerTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/operations/AddOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MultiExecutionCallback.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/MorphingPortableReader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/OperationControl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/hotrestart/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/ringbuffer/impl/operations/AddAllBackupOperation.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/JobTrackerConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/event/LocalCacheWideEventData.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/PartitionInvocation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/eviction/EvictionPolicyEvaluatorProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/impl/AvgTuple.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/operation/AbstractSerializableOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/BufferObjectDataOutput.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorTaskGetDelayFromAddressMessa
geTask.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapRemoveIfSameMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/ssl/SSLContextFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/event/EventData.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/wan/WanSyncStatus.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmultimap/TransactionalMultiMapRemoveEntryMessageTas

k.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/EvictionCandidate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/durableexecutor/impl/TaskRingBuffer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/partitiongroup/PartitionGroupStrategy.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/QueueWaitNotifyKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/recordstore/LazyEntryViewFromRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/listener/MapPartitionLostListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/TaskScheduler.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/notification/MapReduceNotification.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/AbstractCallableMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/MXBeanUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/collection/TxCollectionItem.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/nonblocking/NonBlockingSocketReader.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/ExpirationTimeSetter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/memory/MemoryStatsSupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/discovery/multicast/impl/MulticastMemberInfo.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/UnmodifiableIterator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/LocalExecutorStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/task/JobPartitionStateImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/exception/ServiceNotFoundException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/exception/SilentException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/event/BatchEventData.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueIteratorMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/collection/CollectionItem.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/PortableHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/semaphore/operations/AcquireBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapIsEmptyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/QueryResultRow.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/DateHelper.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/AbstractMultipleEntryOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/ClientExceptionFactory.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/record/ReplicatedRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/list/operations/ListSubOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/spi/impl/proxyservice/impl/operations/DistributedObjectDestroyOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/lock/operations/AwaitBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/RingbufferStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/TimeoutRunnable.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/operation/EntrySetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapAddEntryListenerToKeyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cluster/Joiner.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/MigrationPlanner.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/discovery/DiscoveryStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/Ringbuffer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/LockStoreProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/Cluster.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/CollectionUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/MutatingKeyBasedMapOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/Connection.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/TxnLockAndGetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/AbstractAggregationReducerFactory.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/LocalOperationStatsImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/listener/MapEvictedListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/exception/MaxMessageSizeExceeded.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapAddEntryListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/merge/MapMergePolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/util/UnsafeBuffer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/usercodedeployment/impl/ClassLocator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/BinaryInterface.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/task/MappingPhase.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CachePartitionEventData.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/lock/operations/UnlockIfLeaseExpiredOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/ActionConstants.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/tcp/MemberReadHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/Pre38MapAddNearCacheEntryListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/discovery/multicast/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/PartitionPortableHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/InitialMembershipEvent.java
*

/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/osgi/impl/ScriptEngineActivator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/client/ReplicatedMapValueCollection.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/IPermissionPolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapKeySetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/event/LocalEntryEventData.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/CacheEvictionConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/TransactionalQueueProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/accumulator/AccumulatorFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/ThreadDumpGenerator.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/recordstore/StorageSCHM.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/executionservice/impl/CompletableFutureTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/NodeQueryCacheEventService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/InternalSerializationService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/ReadResultSetImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/CollectionConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/IConcurrentMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/InternalOperationService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/ContainsValueOperationFactory.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapPutMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/PutOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapPostJoinAwareService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapPutAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/MultiMapService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/MultiMapContainerSupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/counters/SwCounter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapReplaceIfSameMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalqueue/TransactionalQueueTakeMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/record/NearCacheDataRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/counters/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/EntryView.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/DataSerializableFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/record/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/serialization/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/codec/UUIDCodec.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomicreference/operations/SetBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/ComposedKeyMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/ReliableMessageListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/CacheConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/OperationTimeoutException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/TransactionalService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/queue/operations/DrainBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/ConfigMismatchOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/executionservice/impl/DelegatingTaskScheduler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/TransactionalObject.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/FieldDefinition.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/BeforeJoinCheckFailureOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/discovery/multicast/MulticastDiscoveryStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEventListenerAdaptor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/PutAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/operations/GetConnectedClientsOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheCreateConfigMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueAddAllMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/rest/HttpGetCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/MetricsPlugin.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/invalidation/RepairingTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomiclong/AtomicLongDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/codec/DistributedObjectInfoCodec.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/constants/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/xa/operations/FinalizeRemoteTransactionBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/PartitionEventListener.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/CombinerResultList.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ICompletableFuture.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/ByteArrayInputOutputFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/collection/operations/CollectionRemoveOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/LinkedListStreamSerializer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/idgen/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/hotrestart/InternalHotRestartService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/hashslot/HashSlotArray12byteKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/CacheSimpleEntryListenerConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/accumulator/AccumulatorHandler.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/QueueTransactionRollbackOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/Aggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/LockPermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/xa/operations/XaReplicationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/OrToInVisitor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/operation/ShutdownRequestOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/ConnectionManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/IncrementCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/mapstore/writebehind/SynchronizedWriteBehindQueue.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/CountingMigrationAwareService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/record/SampleableCacheRecordMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/DistributedObject.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/adapter/IMapDataStructureAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/CompositeMessageTaskFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/DistributedObjectUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheOperationProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/txn/TxnPrepareOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/maxsize/EntryCountNearCacheEvictionChecker.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/TextCommandConstants.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/ascii/memcache/MemcacheCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/usercodedeployment/impl/operation/ClassDataFinderOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/spinning/package-info.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/impl/BigDecimalSumAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/GlobalMemoryAccessorType.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/eventservice/impl/operations/DeregistrationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/txn/TxnRemoveOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/list/operations/ListAddAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/ConnectionListenable.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/Base64.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/MutatingOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/condition/ConditionBeforeAwaitMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorTaskGetStatisticsFromPartitionMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/impl/ComparableMinAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/Combiner.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/subscriber/QueryCacheEventListenerAdapters.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/eventservice/impl/FutureUtilExceptionHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/AbstractMapDataStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ItemListenerConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/properties/HazelcastProperty.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/ObjectDataInputStream.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheSizeOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/NodeShutdownHelper.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapServiceConstructor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/operations/SyncBackupStateOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/Mapper.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/PortableUtils.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/MulticastListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/wan/WanReplicationPublisher.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/TCKMBeanServerBuilder.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/MapAddListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/LocalRecordStoreStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/LocalQueueStatsImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/ScheduledExecutorPartition.java
*

/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/extractor/ValueCollector.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/executionservice/impl/BasicCompletableFuture.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/impl/SetAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/HazelcastInstanceAware.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/EqualPredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/TxnPrepareBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/xa/XAService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/list/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/PartitionRuntimeState.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/BigIntegerAverageAggregator.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/RingbufferConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ILock.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/Job.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/operation/FetchPartitionStateOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/ClassLoaderUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheNearCacheStateHolder.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/ServiceConfigurationParser.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/ClassDefinition.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/LifecycleMapper.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/impl/evaluator/EvictionPolicyEvaluator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/nonblocking/NonBlockingIOThread.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/exception/PartitionMigratingException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/operation/CheckReplicaVersion.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/DistributedScheduledExecutorService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/HazelcastMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/ReplicaSyncInfo.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/MultiMapDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/RecordReplicationInfo.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/AbstractNamedOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/ScheduledExecutorWaitNotifyKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapIsLockedMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapRemoveEntryListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/BackupOperation.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/cache/CacheFetchNearCacheInvalidationMetadataTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapKeySetMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/quorum/QuorumType.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapListenerAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/concurrent/BackoffIdleStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/MapValuesWithPredicateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/executorservice/durable/DurableExecutorRetrieveAndDisposeResultMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/BackupAwareOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/FileSystemXmlConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/request/ShutdownClusterRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/template/TransactionalMultiMapCodecTemplate.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/ConfigurableService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/MapContainsKeyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/durableexecutor/impl/DistributedDurableExecutorService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/writebehind/entry/NullValueDelayedEntry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/Diagnostics.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/PredicateDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/XmlElements.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/MultiMapMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/executorservice/AbstractExecutorServiceCancelMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/Clock.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/MonitoredThread.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cluster/MemberAttributeOperationType.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/transaction/TransactionCommitMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/ScheduledTaskStatistics.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/impl/KeyPredicateSupplier.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/AbstractMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/operations/ScheduleTaskBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/PartitionGroupConfig.java
*

/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/LockServiceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/bufferpool/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/QueryEventFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/atomiclong/AtomicLongApplyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapPartitionLostEventFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/list/ListAddListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/executorservice/durable/DurableExecutorRetrieveResultMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/txncollection/operations/CollectionCommitBackupOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/LocalGCStatsImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/discovery/impl/DefaultDiscoveryService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/RecordFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/eventservice/impl/EventEnvelope.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/TextCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/servicemanager/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/list/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationservice/impl/InvocationConstant.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/ClearNearCacheOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/PartitionReplicaManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/cache/CacheGetAndRemoveMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MapStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/MultiMapOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/CacheStatistics.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/QueueReplicationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/hashslot/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/GlobalMemoryAccessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/NodeStateImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapContainsValueMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/CheckAndEvictOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/UrlXmlConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/template/CountdownLatchCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/OfferOperation.java

* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomicreference/operations/AlterOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/CacheRemoveAllBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/ringbuffer/RingbufferRemainingCapacityMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/GetEntryViewOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/impl/evaluator/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/LocalMapStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/executor/impl/operations/AbstractCallableTaskOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/dto/ConnectionManagerDTO.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/tcp/SocketAcceptorThread.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/PutAllBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ClientService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/QueueEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txncollection/AbstractTransactionalCollectionProxy.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MapFetchEntriesOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/MemberPartitionState.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/RuntimeInterruptedException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/operations/DisposeBackupTaskOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/util/hashslot/impl/HashSlotArray16byteKeyImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/NoOpCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/AbstractDistributedObject.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/ringbuffer/RingbufferAddMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/mapstore/writebehind/WriteBehindProcessors.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/task/MapCombineTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/SetCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/WriteHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/HazelcastException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ConfigDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/list/ListContainsAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/memory/GlobalMemoryAccessorRegistry.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapAddEntryListenerToKeyWithPredicateMessageTask.java
*

/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/AbstractWaitNotifyKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/InvalidConfigurationException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/DoubleGauge.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/subscriber/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/CachedDataRecordWithStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/atomiclong/AtomicLongContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/RemovePartitionLostListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cardinality/impl/operations/AggregateBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/MigrationQueue.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/InMemoryXmlConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/SSLConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/ReadResultSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheGetAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/concurrent/MPSCQueue.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/ReadonlyOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/publisher/NonStopPublisherAccumulator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/BaseIndexStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapRemoveEntryMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/set/SetService.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/SocketChannelWrapperFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/security/permission/DenyAllPermissionCollection.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/AsyncAtomicReference.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/NodeQueryCacheScheduler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/AbstractTextCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/collection/operations/CollectionClearOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/UnsafeHelper.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/atomiclong/package-
info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/TypedStreamDeserializer.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ReplicatedMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/collection/operations/CollectionOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/discovery/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/InternalListMultiMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/Aggregations.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/PartitionIdAware.java

* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/semaphore/operations/SemaphoreBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/merge/HigherHitsMapMergePolicy.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/list/ListGetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/BigIntegerSumAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/servicemanager/RemoteServiceDescriptorProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheLoadAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/TxnPollOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/Serializer.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/nonblocking/AbstractHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/ScheduledTaskHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txncollection/operations/CollectionTxnAddOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/suppliers/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEntryEventImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ItemEventType.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/PartitioningStrategyConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/ringbuffer/RingbufferAddAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/LocalWanPublisherStatsImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txncollection/operations/CollectionTxnRemoveOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/util/MessageFlyweight.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/semaphore/SemaphoreService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cardinality/CardinalityEstimatorEstimateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/durableexecutor/DurableExecutorService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/NamedOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationexecutor/slowoperationdetector/SlowOperationDetector.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/LockAwareOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/lock/operations/AbstractLockOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/QueueIterator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/dto/WanPublisherConfigDTO.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/request/TriggerPartialStartRequest.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/HazelcastServerCachingProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/OutboundOperationHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/TransactionNotActiveException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEntryViews.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/impl/TopicService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/memory/MemorySize.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/jmx/suppliers/LocalMultiMapStatsSupplier.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/AddInterceptorOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapTryPutMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueRemoveMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/ringbuffer/impl/operations/AbstractRingBufferOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/executionservice/impl/DelegatingTaskDecorator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/notification/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/impl/FieldProbe.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueClearMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/ReplaceIfSameOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/impl/reliable/ReliableTopicMessage.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MapStoreAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/task/ReducerTaskScheduler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/DuplicateTaskException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/set/SetCompareAndRetainAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cardinality/CardinalityEstimatorAddMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/MapQueryEngine.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/LockClusterStateOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/AbstractRemoveListenerMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomiclong/AtomicLongCompareAndSetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/record/DataReplicatedRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/ascii/memcache/IncrementCommandParser.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/transactionalmap/package-

info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEntryListenerProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/record/ReplicatedQueryEventFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/XmlConfigLocator.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/rest/HttpPostCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/concurrent/ThreadFactoryImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/template/SetCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/Message.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/Getter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/listener/EntryUpdatedListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/function/Predicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/PortablePosition.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/operation/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/operations/ReplicationOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/EvictBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/AbstractJob.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/RingbufferContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/scheduler/EntryTaskScheduler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/CachePartitionLostListenerConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapExecuteOnAllKeysMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/discovery/multicast/MulticastProperties.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheRemoveAllKeysMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/record/AbstractCacheRecord.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/eventservice/impl/operations/SendEventOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/DefaultMapServiceFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/multimap/impl/operations/ClearBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/DoubleAverageAggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/ConstantSerializers.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/IExecutorService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/operations/ReplicateAllowedDuringPassiveStateTxBackupLogOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/collection/operations/CollectionSizeOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/durableexecutor/impl/operations/RetrieveAndDisposeResultOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/PortableContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/QueryEntry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/discovery/integration/DiscoveryMode.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/record/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomiclong/AtomicLongAddAndGetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/PutBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/eviction/Evictor.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/operation/ClearWanQueuesOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/merge/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/ClusterClockImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/QuickMath.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/operation/ReplicateUpdateToCallerOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/InstanceOfPredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheGetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/HeartbeatComplaintOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/TypeConverters.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/config/matcher/LegacyMatchingPointConfigPatternMatcher.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomicreference/AtomicReferenceProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/MetricsProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/LocalTopicStatsImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationservice/impl/Invocation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationexecutor/impl/DefaultOperationQueue.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapGetForUpdateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/operations/PartitionAwareFactoryAccessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/atomicreference/package-
info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/NearCacheConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheSyncListenerCompleter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/MemberSelectingCollection.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/logging/Logger.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/ReflectionHelper.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/partition/membergroup/BackupSafeMemberGroupFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/impl/reliable/ReliableTopicService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/txn/TxnPutBackupOperation.java
*

/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/proxyservice/impl/ProxyServiceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/discovery/integration/DiscoveryServiceSettings.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/lock/operations/LockBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/eviction/EvictionChecker.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/QueryPartitionOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/ReplicatedMapEvictionProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/event/DefaultEntryEventFilteringStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/PartitionReplicationEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MapFetchKeysOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/packetdispatcher/impl/PacketDispatcherImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/AbstractMultipleEntryBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/ringbuffer/RingbufferCapacityMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapAddIndexMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/countdownlatch/operations/CountDownOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/ConnectionListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/invalidation/AbstractBaseNearCacheInvalidationListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/PortablePartitionLostEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/usercodedeployment/impl/ThreadLocalClassCache.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/operation/MigrationRequestOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/QueueConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/InitialMembershipListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/eventservice/impl/Registration.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/tcp/TcpIpConnectionManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/txn/TxnCommitOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/LongMaxAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomiclong/operations/SetBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheRemoveAllMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/renderers/ProbeRenderer.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomiclong/operations/AlterAndGetOperation.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/list/ListSubMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/QueryableEntry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/condition/ConditionSignalMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/collection/CollectionEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/operation/UpdateMapConfigOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/OfferBackupOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/impl/DefaultNearCacheManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/operation/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/BufferObjectDataInput.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/HotRestartConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/cache/CacheIterateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/durableexecutor/impl/DurableExecutorPartitionContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/CommandParser.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/AuthenticationMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/usercodedeployment/impl/filter/ClassNameFilterParser.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/MapSetReadCursorMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/AbstractMapOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/Portable.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/operations/GetLockCountOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/QueueEventFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/operations/RollbackTxBackupLogOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/AddAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationexecutor/impl/OperationQueue.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/proxyservice/impl/operations/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/impl/TopicProxySupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/logging/LogEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/QueryResult.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/ReplicaErrorLogger.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/HazelcastOverloadException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/MultiMapContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/set/SetAddListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/EntryProcessor.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/CacheNotExistsException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapServiceContextImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/idgen/IdGeneratorProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/AbstractMultiPartitionMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/HazelcastServerCacheManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ServicesConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/BaseMultiMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/JoinConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomicreference/AtomicReferenceContainsMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/mapreduce/MapReduceForMultiMapMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/impl/InternalPartitionServiceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/ExecutionService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/GetAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/MutableOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/Address.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/PartitionWideEntryWithPredicateBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/merge/LatestUpdateMapMergePolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/xa/XATransaction.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/TxnReserveOfferBackupOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/metricsets/ThreadMetricSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/AbstractRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/XATransactionalCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/CacheConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/eventservice/impl/operations/PostJoinRegistrationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/metricsets/FileMetricSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/event/SingleIMapEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/QueuePermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/MapKeyValueSource.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/servicemanager/RemoteServiceDescriptor.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapPutIfAbsentMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/semaphore/SemaphoreProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/Transaction.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/collection/operations/CollectionContainsOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/Notifier.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/MigrationRunnable.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/InvokeOnMembers.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/set/SetRemoveMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/TextProtocolsDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/PortableGetter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/common/DataAwareItemEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/list/ListSizeMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/PartitionServiceState.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/ContextMutexFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/AbstractHazelcastCacheManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/DefaultMapOperationProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/MemcacheUtils.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/request/ConsoleRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/ScheduledExecutorContainerHolder.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/list/ListLastIndexOfMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/record/CacheObjectRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapRemoveEntryListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapManagedService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/HazelcastSerializationException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/txnlist/TransactionalListProxy.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/atomicreference/operations/ApplyOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/PortableNavigatorContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/merge/entry/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/publisher/MapListenerRegistry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/ClearBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/RemoteMapReduceException.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/internal/management/operation/ThreadDumpOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/diagnostics/OverloadedConnectionsPlugin.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/nonblocking/iobalancer/MigrationStrategy.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/DiscoveryStrategyConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/LockGuard.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/nonblocking/iobalancer/LoadImbalance.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/InternalMapListenerAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/QueryCacheScheduler.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapSetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/invalidation/MinimalPartitionService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/StreamSerializerAdapter.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/logging/ILogger.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/function/LongFunction.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/TxnRollbackOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapAssignAndGetUuidsMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/DefaultQueryCacheRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/mapstore/writethrough/WriteThroughManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/QueryCacheRequests.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/AttributeType.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapClearMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheRemovePartitionLostListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/Result.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/PrefixedDistributedObject.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/PartitioningStrategyConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/hashslot/impl/HashSlotArrayBase.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/nearcache/MapNearCacheManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MapOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/PutIfAbsentOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/operations/AbstractClientOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txncollection/operations/CollectionRollbackBackupOperation.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/LazyMapEntry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/EventService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/listener/EventLostListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/mapstore/writebehind/AbstractWriteBehindProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/TypedDataSerializable.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/client/SecureRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/ReplicatedMapCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/nonblocking/iobalancer/LoadTracker.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/ringbuffer/RingbufferTailSequenceMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/DefaultOperationProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/SubscriberAccumulatorFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/ssl/BasicSSLContextFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/membergroup/MemberGroup.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/MultiMapResponse.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/AbstractMultiTargetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmultimap/TransactionalMultiMapSizeMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/request/ClusterPropsRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapEntriesWithPredicateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/ScheduledTaskHandlerImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/QueueCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/nonblocking/iobalancer/EventCountBasicMigrationStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/SingleResultSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/client/RingbufferPortableHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/proxy/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/ClientMessageTemplate.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/publisher/BatchPublisherAccumulator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/discovery/multicast/MulticastDiscoveryStrategyFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/SecureCallable.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/queue/operations/QueueBackupAwareOperation.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/txncollection/CollectionTransactionLogRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/operations/PurgeAllowedDuringPassiveStateTxBackupLogOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/AbstractRecordWithStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/server/package-info.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/MapFetchNearCacheInvalidationMetadataTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/MapValuesWithPagingPredicateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/PortableItemEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/TransactionLogRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/function/Consumer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/BinaryOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/IAtomicLong.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/IdentityConverter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/ClientEventType.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorTaskDisposeFromAddressMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/dto/ManagedExecutorDTO.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/EmptyOptimizer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/SocketWriterInitializer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/ReducingSubmittableJob.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/nonblocking/iobalancer/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/TaskLifecycleListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEventHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/osgi/impl/HazelcastInternalOSGiService.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ClasspathXmlConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/DiscoveryConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/impl/reliable/ReliableMessageListenerAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/impl/StandardMemoryAccessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/operation/MergeOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/writebehind/entry/DelayedEntries.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/VersionedValue.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/InternalLockNamespace.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapKeySetWithPredicateMessageTask.java
*

/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/sort/IntMemArrayQuickSorter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapAddEntryListenerToKeyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/collection/operations/CollectionBackupAwareOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/metricsets/RuntimeMetricSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/RingBufferPermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/SerializationServiceSupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/template/TopicCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/WanSyncStateImpl.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/merge/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorTaskCancelFromPartitionMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/discovery/impl/DefaultDiscoveryServiceProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/operations/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/nearcache/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/FilteringClassLoader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/properties/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/operations/PollOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/NodeJobTracker.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/discovery/SimpleDiscoveryNode.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationexecutor/slowoperationdetector/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/spinning/SpinningSocketReader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/LegacyCacheEvictionConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/executorservice/ExecutorServiceCancelOnPartitionMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/MemberAttributeServiceEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/txncollection/TransactionLogRecordKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MapLoaderLifecycleSupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/BigDecimalAverageAggregator.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/template/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/ReachedMaxSizeException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/hashslot/impl/HashSlotArray8byteKeyImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/PingMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/filter/AlwaysApplyFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MultiMapConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/TxnPrepareOperation.java

* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/partition/membergroup/ZoneAwareMemberGroupFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/lock/LockGetLockCountMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/atomiclong/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/QueryCacheConfigurator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/ascii/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheRemoveOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/JsonSerializable.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/semaphore/SemaphoreWaitNotifyKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/operation/StartProcessingJobOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/codec/EntryViewCodec.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/operations/RollbackAllowedDuringPassiveStateTxBackupLogOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/Indexes.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/nearcache/NearCacheRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/operation/KeySetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/LoadAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/adapter/ICacheDataStructureAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/RemoveInterceptorOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/SetKeyValueSource.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/TerminatedLifecycleService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomicreference/AtomicReferenceClearMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/bufferpool/BufferPoolThreadLocal.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/executor/impl/ExecutionCallbackAdapterFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/PostProcessingMapStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/SemaphoreConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorShutdownMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/RecordInfo.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/operations/BroadcastTxRollbackOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/EntryEventType.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/bufferpool/BufferPoolFactoryImpl.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/proxyservice/impl/operations/InitializeDistributedObjectOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/client/impl/protocol/template/MapReduceCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/LockWaitNotifyKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/queue/operations/CompareAndRemoveBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/Predicates.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/SubscriberAccumulatorHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/mapstore/writebehind/CyclicWriteBehindQueue.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/MembersView.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorGetAllScheduledMessageTask.jav
a
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/DestroyProxyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/FloatingPointSumAggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/QueryResultCollection.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/adapter/DataStructureAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/ProxyService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/proxy/MapProxyImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/QueueTransactionLogRecord.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/impl/MetricsRegistryImpl.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/UnsafeObjectDataInput.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/notification/MemberAwareMapReduceNotification.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/VersionAware.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomiclong/AtomicLongGetAndSetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/operation/ClearOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MapFlushOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/LegacyCacheConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/TaskDefinition.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/countdownlatch/package-
info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueRemoveListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/StreamSerializer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/IQueue.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapEntrySetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/task/ReducerChunk.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/countdownlatch/CountDownLatchContainer.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/membergroup/SingleMemberGroupFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cluster/memberselector/MemberSelectors.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheContext.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/strategy/StringPartitioningStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/hashslot/impl/HashSlotArray8byteKeyNoValue.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/semaphore/operations/SemaphoreDetachMemberOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/txncollection/operations/CollectionReserveAddOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/operations/JoinMastershipClaimOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/TimedMemberStateFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/EvictAllOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/operation/AbstractReplicatedMapOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/MapRemoveIfSameMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/writebehind/WriteBehindProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/AbstractJoiner.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/ClusterStateListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/collection/HsaHeapMemoryManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/executionservice/impl/DelegatingCallableTaskDecorator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/InflatableSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/LocalMultiMapStats.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/executor/impl/ExecutorServiceProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/operations/UnlockBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/atomiclong/operations/SetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/QueryRunner.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/BackupAwareEntryProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/MapPutTransientMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationexecutor/OperationExecutor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/atomicreference/operations/package-info.java
*

/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/merge/policy/CacheMergePolicyProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/AggregationsDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/EntrySetResponse.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/client/ClientPrincipal.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapTryLockMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/DurableExecutorCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheListenerRegistrationMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/EvictableEntryView.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/PartitioningStrategy.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/LocalCacheStatsImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapReplaceMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/multimap/impl/txn/TxnRollbackBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/MapDataStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/operation/ContainsKeyOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/ClassDefinitionWriter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/AddPartitionLostListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/console/DefaultLineReader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/exception/RetryableIOException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/UuidUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/usercodedeployment/impl/ClassloadingMutexProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/ManagedService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/EntryOffloadableLockMismatchException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/set/SetIsEmptyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/SetCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ConfigLoader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/TxnDeleteOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/hashslot/HashSlotCursor8byteKey.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/StripedRunnable.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/Probe.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/executorservice/durable/DurableExecutorIsShutdownMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/CountAggregator.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/dto/EventServiceDTO.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/config/MapPartitionLostListenerConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/Target.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/SocketInterceptor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheProxyUtil.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/nonblocking/iobalancer/IOBalancer.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/nonblocking/NonBlockingSocketWriter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MemberAttributeEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/list/ListAddAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/operation/PublisherCreateOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapIsLockedMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/MultiMapEventsDispatcher.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/WaitNotifyKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/MapUtil.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/listener/EntryMergedListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/HeapData.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/xa/operations/CollectRemoteTransactionsOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationservice/impl/responses/package-
info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/set/SetClearMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/MapQueryEngineImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/collection/operations/CollectionGetAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/ManagementDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/durableexecutor/impl/operations/DisposeResultBackupOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/ObjectMultiMapProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/iterator/MapEntriesWithCursor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/operation/ContainsValueOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ICollection.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/ReplicatedMapEventPublishingService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/operation/EvictionOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueContainsAllMessageTask.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/InternalPartitionListener.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/lock/LockForceUnlockMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/ClearBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapRemoveMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/merge/PutIfAbsentCacheMergePolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapAggregateWithPredicateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/dto/ClusterHotRestartStatusDTO.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cardinality/impl/CardinalityEstimatorService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/GetPartitionsMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/accumulator/DefaultCyclicBuffer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/HashMapAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/extractor/ValueReadingException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/TimedMemberStateFactoryHelper.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/collection/LongSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/QueueProxySupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/TrackableJob.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/SimpleCommandParser.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomicreference/AtomicReferenceIsNullMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/JoinMessageTrustChecker.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/UnsafeObjectDataOutput.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/HazelcastInstanceProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/txn/TransactionalMultiMapProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/collection/CollectionService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/operations/IsLockedOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/NullQueryCache.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/SerializationConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/adapter/ReplicatedMapDataStructureAdapter.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/operation/ScriptExecutorOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MapReplicationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/eviction/LRUEvictionPolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/packetdispatcher/package-info.java

* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/diagnostics/MultiLineDiagnosticsLogWriter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/durableexecutor/impl/operations/ShutdownOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/ascii/memcache/ErrorCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/annotation/Beta.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapGetAllMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/operation/RemoveOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/util/hashslot/impl/HashSlotArray16byteKeyNoValue.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/HashUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapEntriesWithPagingPredicateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/publisher/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/LockMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CachePartitionIterator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/DefaultQueryCacheRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/ascii/memcache/BulkGetCommandProcessor.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/scheduler/ScheduledEntryProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ItemListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/OperationRunnerImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomiclong/operations/AtomicLongReplicationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/wan/WanReplicationEndpoint.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/operations/GetAllScheduledOnPartitionOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/TransactionManagerServiceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/ReadonlyKeyBasedMapOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapAddEntryListenerToKeyMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/BigDecimalMaxAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/AuthenticationException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/SizeOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/osgi/impl/Activator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/matcher/RegexConfigPatternMatcher.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/EventFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/OutOfMemoryErrorDispatcher.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/GetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/impl/SourceMetadata.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/logging/Slf4jFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/operations/WhoisMasterOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/TriggerLoadIfNeededOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/osgi/HazelcastOSGiService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/Parameters.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/TopicConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MapNearCacheStateHolder.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/operations/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/countdownlatch/CountDownLatchTrySetCountMessageTask.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/QuorumAwareService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/DuplicateInstanceNameException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/InternalMapPartitionLostListenerAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheClearOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MemberSelector.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/AbstractMutatingCacheOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/countdownlatch/operations/SetCountOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/txnset/TransactionalSetProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/invalidation/StaleReadDetectorImpl.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/TryRemoveOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/topic/impl/reliable/ReliableMessageListenerRunner.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/rest/HttpCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/RingbufferDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/nearcache/invalidation/InvalidationListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/list/ListContainsMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/Packet.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapSizeMessageTask.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/hashslot/HashSlotCursor12byteKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/AggregationResultProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapClearNearCacheMessageTask.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/ExceptionAction.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/queue/QueueItem.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/TopicConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/AbstractAggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/InternalPartition.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/ExecutorType.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/TransactionalMap.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapListenerFlagOperator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/AbstractMultiMapAddEntryListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/operations/CreateAllowedDuringPassiveStateTxBackupLogOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/PortablePositionNavigator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueDrainMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/JobProcessInformation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/SerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheGetConfigOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/counters/MwCounter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/MessageTaskFactoryProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/operation/AssignPartitions.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/memory/DefaultMemoryStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/accumulator/AccumulatorInfo.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorTaskIsDoneFromPartitionMessag
eTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationservice/impl/CallIdSequence.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/BinaryMapEntryCostEstimator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/HazelcastCacheManager.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/NodeExtensionFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/logging/LoggingServiceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomiclong/AtomicLongGetAndAddMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/CachePutAllBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/CompletedFuture.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/eviction/impl/comparator/RandomEvictionPolicyComparator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/discovery/impl/PredefinedDiscoveryService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/ParallelAccumulationExecutor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/collection/operations/CollectionAddAllBackupOperation.java

*
 /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/ShutdownNodeOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/membergroup/DefaultMemberGroup.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/MaxAggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/SerializationServiceV1.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/VisitablePredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ExecutorConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/listener/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/proxyservice/impl/ProxyEventProcessor.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapEntrySimple.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/InstanceMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/PartitionWideEntryOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/semaphore/SemaphoreReleaseMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/NodeAware.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueIsEmptyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/sort/LongMemArrayQuickSorter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/operations/LockOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmultimap/TransactionalMultiMapRemoveMessageTask.jav
a
*
 /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheGetConfigMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/PartitionSpecificRunnable.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapProjectionMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/executionservice/InternalExecutionService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/multimap/impl/operations/MultiMapBackupAwareOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/PartitionEventManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/ClusterVersionListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/event/MapEventPublisherImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/operation/KeysAssignmentResult.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/TextCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/semaphore/operations/DrainBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/client/impl/protocol/task/executorservice/ExecutorServiceIsShutdownMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MapFlushWaitNotifyKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/DefaultValueCollector.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/proxy/NearCachedMapProxyImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/semaphore/operations/AvailableOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/LocalOperationStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/client/ReplicatedMapKeys.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/version/MemberVersion.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/wan/impl/WanReplicationPublisherDelegate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/quorum/QuorumFunction.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapEntrySetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/list/ListListIteratorMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/ObjectDataOutput.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/SubscriberListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/console/SimulateLoadTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/AbstractExecutorThreadFactory.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/NearCacheConfigAccessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEventDataImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/event/MapPartitionEventData.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/CacheDeserializedValues.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/executorservice/ExecutorServiceShutdownMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapKeyLoaderUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/operations/SyncStateOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/RingbufferService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/metrics/metricsets/ClassLoadingMetricSet.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/request/ClearWanQueuesRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/renderers/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/ThreadLocalRandomProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/ClientTypes.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/ExtractorGetter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/MembersViewMetadata.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/PortableDistributedObjectEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/QueryEntryFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapValueCountMessageTask.java
*

/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapListenerAdaptors.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/operations/ReplicationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomicreference/AtomicReferenceContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/operation/ClearOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/ScheduledExecutorCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/Registry.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/request/GetClusterStateRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/discovery/multicast/impl/MulticastDiscoveryReceiver.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/MigrationThread.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/AtomicReferenceMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/TransactionalQueueCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/PostJoinMapOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/LifecycleEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/CountDownLatchMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/logging/StandardLoggerFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/EventResponseTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/QueryOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/LocalTopicStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/operations/JoinRequestOp.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/memory/ConcurrentHeapMemoryAccessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/executorservice/durable/DurableExecutorShutdownMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/task/TransferableJobProcessInformation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/ThreadUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/Endpoint.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/operation/PutAllOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/ScheduledExecutorContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/operations/CancelTaskOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/AddInterceptorOperationSupplier.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/LifecycleService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/PutFromLoadAllBackupOperation.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/transactionallist/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/TopicPermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/executor/impl/operations/CallableTaskOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/PublishPartitionRuntimeStateTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/queue/QueueCompareAndRetainAllMessageTask.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/set/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/InMemoryFormat.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/DistributedObjectListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/VersionedPortable.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/rest/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/operations/AbstractBackupAwareSchedulerOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/TruePredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapTransactionalService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/impl/reliable/ReliableTopicProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/util/SafeBuffer.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/operations/LockReplicationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/ClientProtocolErrorCodes.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/map/MapExecuteOnKeysMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/NumberAverageAggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/TransactionDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/MultiMapOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/RemoveDistributedObjectListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/SingleLineDiagnosticsLogWriter.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/lock/LockGetRemainingLeaseTimeMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/list/ListAddWithIndexMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/atomicreference/operations/AbstractAlterOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/EvictionListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/SocketInterceptorConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/atomicreference/AtomicReferenceDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/nearcache/invalidation/UuidFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/txn/TxnGenerateRecordIdOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/internal/cluster/impl/operations/WanReplicationOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/EvictAllOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/operations/AbstractTxOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/ListMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/HealthMonitor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/operations/AuthorizationOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionallist/TransactionalListRemoveMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/transactionalset/package-
info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/ReducerFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/codec/JobPartitionStateCodec.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/Config.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/config/matcher/MatchingPointConfigPatternMatcher.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/TouchCommandParser.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/discovery/AbstractDiscoveryStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/proxyservice/InternalProxyService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapDeleteMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapGetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/operation/AbstractPartitionOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapAddNearCacheInvalidationListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/SortedIndexStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/MemberImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/AbstractMultiValueGetter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/wan/MapReplicationRemove.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/set/SetContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/proxyservice/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/properties/GroupProperty.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MemberAttributeConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/SerializableList.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ICacheManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/CacheMergePolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/codec/XIDCodec.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/multimap/impl/operations/RemoveBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/countdownlatch/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/RemoveBackupOperation.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/LocalWanStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/MapGetInvalidationMetaDataOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CachePutAllMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/event/QueryCacheEventPublisher.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/MultipleEntryWithPredicateOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/TxnPrepareBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapSplitBrainHandlerService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/OverflowPolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomiclong/AtomicLongGetAndAlterMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/event/QueryCacheNaturalFilteringStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/ScriptEngineManagerContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/operation/IsEmptyOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/impl/DoubleGaugeImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ItemEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/maxsize/impl/EntryCountCacheEvictionChecker.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/InterfacesConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/AbstractClusterWideIterator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/projection/impl/SingleAttributeProjection.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/function/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/nonblocking/SelectionHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/AbstractMember.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/ClientEndpoint.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/TxnRollbackOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/InvokerWrapper.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/RemoveAllListenersMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/eviction/impl/comparator/LRUEvictionPolicyComparator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/semaphore/SemaphoreInitMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/ILikePredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/MapSizeOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/EvictionPolicyType.java
*

/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/SetMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/queue/QueuePeekMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/subscriber/InternalQueryCacheListenerAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/recordstore/AbstractRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/recordstore/RecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/DiscoveryJoiner.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/TryPutOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/atomicreference/AtomicReferenceGetAndSetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/LocalMultiMapStatsImpl.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapPartitionAwareService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/AbstractCacheProxyBase.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapQuorumAwareService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/NodeInvokerWrapper.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/TransactionalSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/EmptyStatement.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/OperationResponseHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/xa/XATransactionContextImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/replicatedmap/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/ReadHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/NegatablePredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/record/ReplicatedMapEntryView.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/TopologyChangedStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/transactionalset/TransactionalSetAddMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MaxSizeConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/impl/LongAvgAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/UUIDConverter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/LockEvictionProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/Node.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/publisher/PublisherAccumulatorHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/operations/IsDoneOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/durableexecutor/impl/operations/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/ConfigCheck.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/ObjectDataInput.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/BaseQueue.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/MemberInfo.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/PartitionScanRunner.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/JVMUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/scheduler/CoalescingDelayedTrigger.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/queue/operations/RemoveBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/PutBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/StatisticsAwareService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/mapreduce/AbstractMapReduceTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MembershipEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapAddNearCacheListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/QueryConstants.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/xa/XATransactionDTO.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/ExpirationChecker.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ITopic.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/RemoveOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/JoinRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/ConcurrentMemoryAccessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/EntryCostEstimator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/scheduler/CompositeKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/ClientMessage.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/record/ResultSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/OperationService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/concurrent/NoOpIdleStrategy.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/spinning/SpinningSocketWriter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/ClientEngineImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/AddressPicker.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/BuildInfo.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/OperationRunnerFactoryImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/task/JobTaskConfiguration.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/rest/HttpGetCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/accumulator/AccumulatorProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/spinning/SpinningIOThreadingModel.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MapIndexConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/ComparableMaxAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationutil/Operations.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/multimap/impl/operations/MultiMapKeyBasedOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/OperationFactory.java

* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/operation/PromotionCommitOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/exception/RetryableException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/ConditionImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/InputOutputFactory.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/list/ListProxyImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/SubscriberRegistry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/merge/policy/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/InvocationBuilder.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/PendingInvocationsPlugin.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/MemoryAllocator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/operation/RequestPartitionResult.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/LockStoreInfo.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/ClusterHeartbeatManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEventListener.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/security/permission/ScheduledExecutorPermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/hashslot/HashSlotCursor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/LazyEntryView.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txncollection/operations/CollectionPrepareBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/CacheSimpleConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/StringUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/QueueStoreConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/countdownlatch/CountDownLatchAwaitMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/wan/impl/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapValuesMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/CreateProxyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/GlobalSerializerConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/IntegerMinAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/VersionAwareConstructorFunction.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/nearcache/MemberMinimalPartitionService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/ascii/TextWriteHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/TaskUtils.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/ReplicatedMapPermission.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/RemoveOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapValuesMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/IMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/eviction/LFUEvictionPolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapRemoveMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/VersionedObjectDataInput.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/SerializerAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/executionservice/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/ringbuffer/RingbufferReadManyMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/ClusterServiceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/ringbuffer/RingbufferSizeMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomiclong/operations/AbstractAlterOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/ManagedAnnotation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/AbstractEntryProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/operation/FireNotificationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/serialization/PortableReader.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/durableexecutor/impl/operations/PutResultBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/PartitioningStrategyFactory.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/FutureUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/impl/PartitionReplicaChangeEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/CachePermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/event/MapEventPublishingService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/BulkGetCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/QueryCacheFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/CacheEvictionPolicyComparator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/operations/ReadManyOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/xa/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/KeySetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/AbstractCacheRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapRemovePartitionLostListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/operation/ReplicationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapPublisherCreateWithValueMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/logging/LoggerFactorySupport.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/concurrent/BusySpinIdleStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/FieldGetter.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/CredentialsFactoryConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/usercodedeployment/impl/filter/ClassWhitelistFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/ListenerAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/semaphore/SemaphoreDrainPermitsMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/concurrent/ConcurrentConveyor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/eventservice/impl/LocalEventDispatcher.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/EntrySetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/EvictableGetterCache.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/CachedExecutorServiceDelegate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/EvictionConfiguration.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/DeleteCommandParser.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheContainsKeyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/LifecycleListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/hotrestart/BackupTaskStatus.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheAddNearCacheInvalidationListenerTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/queue/operations/RemainingCapacityOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/Partition.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/StatsCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/EvictAllBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/xa/XAResourceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/SymmetricEncryptionConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/SetConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/logging/LoggingService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/MembersUpdateOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/memory/NativeOutOfMemoryError.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueOfferMessageTask.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/AbstractCompletableFuture.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/RuntimeMemoryInfoAccessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/EvictionOperator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/TxnValueWrapper.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/GeneratedBuildProperties.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/IOUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/LockCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/durableexecutor/impl/DurableExecutorServiceProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/spinning/SpinningOutputThread.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/rest/HttpDeleteCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/mapstore/writebehind/DefaultWriteBehindProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/strategy/DefaultPartitioningStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/RingbufferCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MapConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/collection/Long2LongMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/IsKeyLoadFinishedOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/WriteBehindStateHolder.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/MapInterceptor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/AccumulationExecutor.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txncollection/operations/CollectionReserveRemoveOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/AbstractIMapEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/template/ResponseTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/wan/WanReplicationEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/TxnPrepareOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/merge/LatestAccessCacheMergePolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/MigrationListenerAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/ManagementCenterIdentifier.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/LocalGCStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/projection/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/KeyLoadStatusOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/impl/ProbeInstance.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheSizeMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/util/BufferBuilder.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/ClearOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/LocalWanStatsImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/durableexecutor/impl/operations/AbstractDurableExecutorOperation.java
*

/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/ISemaphore.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/invalidation/RepairingHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/impl/InternalMigrationListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/semaphore/SemaphoreAvailablePermitsMessageTasks.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/NodeContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/UnmodifiableListIterator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/record/CacheRecordMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transaction/TransactionCreateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/MapNameAndKeyPair.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/LongMinAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/CacheGetAndReplaceOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/operation/UpdateManagementCenterUrlOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/CollectionTxnUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/quorum/impl/QuorumImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MultiMapConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/operation/ReadAndResetAccumulatorOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/SplitBrainAwareCacheRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/MapGetAllOperationFactory.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/durableexecutor/impl/operations/TaskOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheStatisticsImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueRemainingCapacityMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalqueue/TransactionalQueuePollMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/IList.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/operations/JoinOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/NotifiableEventListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/exception/TargetNotMemberException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/PoolExecutorThreadFactory.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/request/AsyncConsoleRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/dto/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/record/LazyCollection.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/NetworkingPlugin.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transaction/TransactionRollbackMessageTask.java

* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/eviction/impl/strategy/sampling/SampleableEvictableStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheRemoveInvalidationListenerMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomiclong/AtomicLongAlterAndGetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomicreference/operations/GetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/InternalQueryCache.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/tcp/SocketReaderInitializerImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cardinality/impl/hyperloglog/impl/DenseHyperLogLogConstants.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/semaphore/SemaphoreAcquireMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/impl/strategy/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/ValueCollectionFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txncollection/operations/CollectionTxnRemoveBackupOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/responses/ErrorResponse.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/IndexAwarePredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MapAttributeConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/PortableEntryEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/PartitionWideEntryWithPredicateOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/hotrestart/BackupTaskState.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/OutboundResponseHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/event/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/PermissionConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/merge/MergePolicyProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/impl/MinAggregator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/ascii/memcache/VersionCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/client/ReplicatedMapPortableEntryEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/Parser.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/list/ListIsEmptyMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/StripedExecutor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/lock/LockUnlockMessageTask.java
*

/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/ObjectRecordFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/CacheCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/operation/PostPonePartitionProcessing.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/multimap/impl/operations/MultiMapMigrationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transaction/XATransactionCreateMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/IFunction.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/TransactionalObjectKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/eventservice/impl/EventProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/multimap/impl/txn/TxnCommitBackupOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/mapstore/writebehind/IPredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/networking/nonblocking/NonBlockingIOThreadingModel.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/RegexPredicate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/RingbufferStoreFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txncollection/operations/CollectionPrepareOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/MappingJob.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmap/TransactionalMapReplaceMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/PartitionAwareService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/properties/ValueValidator.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/executor/CompletableFutureTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/proxyservice/impl/DistributedObjectFuture.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/QuorumConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/list/ListAddMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/concurrent/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/EntryListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapRemoveEntryListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/ClientAwareService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/MapReduceUtil.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/impl/ProbeUtils.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/LatencyTrackingCacheWriter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/SetCommandParser.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/publisher/PublisherAccumulatorFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/discovery/integration/DiscoveryService.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/internal/nearcache/impl/store/BaseHeapNearCacheRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/ProxyServiceMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheMergeOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/ByteArrayObjectDataInput.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/record/AbstractReplicatedRecordStore.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/IAtomicReference.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/SemaphorePermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapLockMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/tcp/TcpIpConnectionMonitor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/request/ConsoleRequestConstants.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/NodeState.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/quorum/QuorumListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/VisitorUtils.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cardinality/impl/hyperloglog/impl/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/LoadMapOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/dto/PartitionServiceBeanDTO.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/SplitBrainHandlerService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/event/CacheWanEventPublisher.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/query/PartitionScanExecutor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/MulticastJoiner.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/maxsize/impl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/CardinalityEstimatorCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/executor/impl/operations/CancellationOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/TopologyChangedException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/MulticastService.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/semaphore/SemaphoreDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/PostJoinCacheOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/recordstore/BasicRecordStoreLoader.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/util/concurrent/ConcurrentConveyorException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/LockService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cardinality/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/console/Echo.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/matcher/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/list/operations/ListRemoveOperation.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/PortableHookLoader.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/partition/membergroup/HostAwareMemberGroupFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/osgi/impl/HazelcastOSGiInstanceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/ArrayRingbuffer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/iterator/AbstractMapPartitionIterator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/adapter/MethodNotAvailableException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/AbstractInternalQueryCache.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MulticastConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/ProbeFunction.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/operation/MigrationCommitOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/LocalReplicatedMapStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/impl/ByteArrayAccessStrategy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/SampleableNearCacheRecordMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/ListPermission.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/lock/LockTryLockMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/MembershipManagerCompat.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/AwaitMapFlushOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/AddMembershipListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/durableexecutor/impl/operations/TaskBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/operations/ClientDisconnectionOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/proxyservice/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/CacheContainsKeyOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/operations/AddBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomicreference/operations/SetOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/event/CachePartitionLostEventFilter.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/operations/IsCanceledOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/AbstractMapQueryMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/accumulator/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/list/operations/ListSetBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/multimap/impl/txn/TxnRemoveAllBackupOperation.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/Member.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/SimpleExecutionCallback.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/merge/entry/LazyCacheEntryView.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/record/CacheRecordFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/txn/TransactionRecordKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/EntryListenerAdaptors.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/merge/HigherHitsCacheMergePolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/Pre38CacheAddInvalidationListenerTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/QueryResultSizeExceededException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/LocalMemoryStatsImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/MembershipAwareService.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/JobTracker.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/ascii/memcache/TouchCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/VersionedClusterOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/mapstore/writebehind/WriteBehindStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/quorum/QuorumService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/scheduler/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/DeleteCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/NearCacheStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/DefaultOutOfMemoryHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/AbstractMapPutMessageTask.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/AbstractXmlConfigHelper.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/ExecutorServiceMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/InitializingObject.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/LockResourceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/AbstractBackupCacheOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/projection/Projections.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/HazelcastCachingProvider.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/matcher/WildcardConfigPatternMatcher.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/impl/operation/ValuesOperation.java
*
 /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/AbstractCacheProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/diagnostics/SystemLogPlugin.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/MigrationInfo.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MapAttributeConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MembershipListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/JobPartitionState.java

* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/BigDecimalAvgAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheAssignAndGetUuidsOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/operations/BaseSignalOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/EvictionConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/task/MemberAssigningJobProcessInformationImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/ringbuffer/impl/client/PortableReadResultSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/usercodedeployment/impl/ClassSource.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/DataRecordFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/DelegatingScheduledFutureStripper.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/client/ReplicatedMapPortableHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/eviction/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/multimap/impl/txn/MultiMapTransactionLogRecord.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/GetCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/TransactionTimedOutException.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/IterationType.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/durableexecutor/impl/operations/ReplicationOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/MessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/networking/SocketReaderInitializer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/IScheduledFuture.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/CacheManagementConfigOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/impl/task/KeyValueSourceFacade.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/MemberImpl.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/MapSubscriberRegistry.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapRemoveAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/record/QueryCacheRecordFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEntryIterationResult.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/collection/LongLongCursor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/MapLoadAllOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/AbstractMapServiceFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationexecutor/impl/OperationExecutorImpl.java
*

/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/responses/CallTimeoutResponse.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/publisher/CoalescingPublisherAccumulator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/ContinuousQueryCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/ssl/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/TypeConverter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/TextCommandServiceImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/impl/MemberStateImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/ClearExpiredOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomicreference/operations/ContainsOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/set/SetProxyImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/CardinalityEstimatorConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/request/RunGcRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/permission/AllPermissions.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/NodeEngineImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/partition/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/aggregation/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomiclong/operations/AlterOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/QuorumListenerConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/memory/impl/AlignmentUtil.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/atomicreference/AtomicReferenceSetAndGetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/DoubleAvgAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/MutableLong.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/ascii/TextReadHandler.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/semaphore/SemaphoreContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/osgi/impl/OSGiScriptEngine.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/MultiMapEventsPublisher.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/MapPartitionLostListenerConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/publisher/PartitionAccumulatorRegistry.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomiclong/operations/AtomicLongBackupAwareOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/strategy/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/DefaultNodeContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/executorservice/package-
info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/event/MapEventData.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/LiveOperations.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/map/impl/querycache/accumulator/AccumulatorInfoSupplier.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/ListenerAdapters.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/partition/IPartitionService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/txn/TxnPrepareBackupOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/request/MemberConfigRequest.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/constants/ResponseMessageConst.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/QueryCacheListenerAdapter.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/wan/WanReplicationService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/scheduler/ScheduleType.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/semaphore/SemaphoreReducePermitsMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/list/ListCompareAndRetainAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/memcache/VersionCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/Visitor.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapSetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/list/ListSetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/monitor/LocalQueueStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/countdownlatch/operations/AbstractCountDownLatchOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/config/CachePartitionLostListenerConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapPutAllMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/ClientEndpointImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/quorum/QuorumException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/operations/ScheduleTaskOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/transaction/impl/TransactionLog.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/operations/ReplicateTxBackupLogOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/Offloadable.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/operations/PartitionIteratingOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/transactionalmultimap/TransactionalMultiMapValueCountMessageTask.
java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/list/ListService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/WanReplicationRef.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/PortableSerializer.java

*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/MultiMapCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/accumulator/Accumulator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/impl/ScheduledFutureProxy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationexecutor/impl/OperationThread.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapKeyLoader.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/Record.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/OutOfMemoryHandlerHelper.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/PartitionContainer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/eventservice/impl/operations/package-
info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/partition/PartitionLostEvent.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/predicates/AbstractVisitor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomiclong/operations/GetAndAlterOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/HazelcastExpiryPolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEventSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/countdownlatch/CountDownLatchDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/tx/TransactionalMapProxySupport.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/durableexecutor/StaleTaskIdException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/cache/impl/operation/CacheGetAllOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/management/operation/GetMapConfigOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/replicatedmap/merge/PassThroughMergePolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/topic/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/IBiFunction.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/operations/HeartbeatOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/operation/ReplicaSyncResponse.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/DefaultPortableReader.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/operation/KeyValueJobOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/rest/HttpPostCommand.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/operation/CancelJobSupervisorOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/memory/MemoryStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/MessageTaskFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapGetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/map/impl/operation/MultipleEntryOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/ArrayUtils.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/collection/operations/CollectionIsEmptyOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/SetConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/multimap/impl/operations/ContainsEntryOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/event/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/multimap/MultiMapSizeMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/properties/HazelcastProperties.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/eviction/ExpirationManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/SubscriberAccumulator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapTryRemoveMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/SampleableConcurrentHashMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/Preconditions.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/management/dto/ClientEndPointDTO.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/SplitBrainHandler.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/eviction/EvictionStrategyType.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/operation/RequestMapDataOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/merge/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/transaction/impl/xa/operations/AbstractXAOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/instance/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/ClusterWideIterator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/merge/ReplicatedMapMergePolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txncollection/operations/CollectionTransactionRollbackOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/collection/CollectionDataSerializerHook.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txncollection/operations/CollectionRollbackOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/listener/MapClearedListener.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/MemberAttributeChangedOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/query/CallerRunsPartitionScanExecutor.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/queue/QueueAddListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/SimpleEntryView.java
* /hazelcast-client-protocol-1-4-1-sources-1-

jar/com/hazelcast/internal/serialization/impl/ObjectDataOutputStream.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/impl/notification/ReducingFinishedNotification.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/PortableCollection.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/template/TransactionalSetCodecTemplate.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/mapreduce/aggregation/impl/AcceptAllSupplier.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/DefaultMapQueryMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cardinality/impl/hyperloglog/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/operation/PartitionWideEntryWithPredicateOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/EntryEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/SizeOperationFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/querycache/QueryCacheContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/util/hashslot/impl/HashSlotArray12byteKeyImpl.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/LatencyTrackingMapStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/getters/MultiResult.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/eventservice/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/txnqueue/operations/TxnCommitOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/util/JavaVersion.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/DistributedObjectEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/mapstore/writebehind/entry/DelayedEntry.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/replicatedmap/impl/operation/CheckReplicaVersionOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/map/MapDestroyCacheMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/ExecutorConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheEntry.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/concurrent/atomiclong/operations/AddBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/discovery/integration/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapMigrationAwareService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/MBeans.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/topic/impl/TopicDataSerializerHook.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/TypeAwareCommandParser.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/QueueStoreConfigReadOnly.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/AsyncInboundResponseHandler.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/impl/FieldDefinitionImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/MultiMapPartitionContainer.java

* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cluster/impl/TcpIpJoiner.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/EntryObject.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/protocol/task/set/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/IdGenerator.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/mapstore/writebehind/WriteBehindQueue.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/DefaultArgumentParser.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/record/DataQueryCacheRecord.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/collection/impl/list/operations/ListGetOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/serialization/impl/ArrayListStreamSerializer.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/exception/TargetDisconnectedException.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/replicatedmap/ReplicatedMapGetMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/atomiclong/AtomicLongService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/metrics/MetricsRegistry.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/DataAwareEntryEvent.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/rest/HttpDeleteCommandProcessor.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/servicemanager/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/operationservice/impl/operations/Backup.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/serialization/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/merge/entry/DefaultCacheEntryView.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/collection/impl/collection/operations/CollectionRemoveBackupOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/eviction/RandomEvictionPolicy.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/scheduledexecutor/impl/ScheduledExecutorMemberBin.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/query/impl/IndexImpl.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/AbstractJoinOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/ValuesOperation.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/nio/Protocols.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/record/DataRecordWithStats.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/partition/operation/FinalizePromotionOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/client/impl/operations/ClientReAuthOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/ConditionKey.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationservice/impl/InvocationRegistry.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorSubmitToAddressMessageTask.ja
va
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/scheduledexecutor/ScheduledExecutorTaskCancelFromAddressMessage

Task.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/ascii/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/multimap/impl/operations/CountOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/mapreduce/aggregation/impl/LongSumAggregation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/config/TcpIpConfig.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/logging/LoggerFactory.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/jmx/SemaphoreMBean.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/wan/ReplicationEventObject.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/semaphore/SemaphoreTryAcquireMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/ConstructorFunction.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/lock/LockIsLockedMessageTask.java
*
/hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/cache/CacheRemoveEntryListenerMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/LockStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/operation/BasePutOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/MultiMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/cluster/impl/operations/RollbackClusterStateOp.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/map/impl/querycache/subscriber/SubscriberContext.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/scheduledexecutor/package-info.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/client/impl/protocol/task/AbstractTransactionalMessageTask.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/security/package-info.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/concurrent/lock/WaitersInfo.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/servicemanager/ServiceInfo.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/MemberMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/core/TransactionalList.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/map/impl/MapReplicationSupportingService.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/operation/CacheDestroyOperation.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/spi/impl/servicemanager/ServiceManager.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/internal/nearcache/impl/store/NearCacheObjectRecordStore.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/cache/impl/CacheClearResponse.java
* /hazelcast-client-protocol-1-4-1-sources-1-
jar/com/hazelcast/spi/impl/operationparker/impl/OperationParkerImpl.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/internal/cluster/impl/operations/PostJoinOp.java
No license file was found, but licenses were detected in source scan.

/*
* Original work Copyright 2015 Real Logic Ltd.

* Modified work Copyright (c) 2015, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/

Found in path(s):
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/Long2LongHashMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/LongHashSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/IntHashSet.java
*
/hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/BiInt2ObjectMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/IntIterator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/Int2ObjectHashMap.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/MapDelegatingSet.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/LongIterator.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/Hashing.java
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/collection/Long2ObjectHashMap.java
No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2008-2017, Hazelcast, Inc. All Rights Reserved.
*
* Licensed under the Apache License, Version 2.0 (the "License");
* you may not use this file except in compliance with the License.
* You may obtain a copy of the License at
*
* http://www.apache.org/licenses/LICENSE-2.0
*
* Unless required by applicable law or agreed to in writing, software
* distributed under the License is distributed on an "AS IS" BASIS,
* WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
* See the License for the specific language governing permissions and
* limitations under the License.
*/
/**
    * This method changes the given async cause, and it adds the also given local stacktrace separated by the
    * supplied exception message.
    * If the remoteCause is an {@link java.util.concurrent.ExecutionException} and it has a non-null inner

```
   * cause, this inner cause is unwrapped
 and the local stacktrace and exception message are added to the
   * that instead of the given remoteCause itself.
   *
   * @param asyncCause           the async exception
   * @param localSideStackTrace   the local stacktrace to add to the exceptions stacktrace
   * @param localExceptionMessage a special exception message which is added to the stacktrace
   */
```

Found in path(s):
* /hazelcast-client-protocol-1-4-1-sources-1-jar/com/hazelcast/util/ExceptionUtil.java

1.1662 @jridgewell/set-array 1.2.1

1.1662.1 Available under license :

Copyright 2022 Justin Ridgewell <jridgewell@google.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
 IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1663 @jridgewell/gen-mapping 0.3.5

1.1663.1 Available under license :

Copyright 2022 Justin Ridgewell <jridgewell@google.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell

copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1664 @jridgewell/trace-mapping 0.3.25

1.1664.1 Available under license :

MIT
Copyright 2022 Justin Ridgewell <justin@ridgewell.name>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1665 accepts 1.3.8

1.1665.1 Available under license :

(The MIT License)

Copyright (c) 2014 Jonathan Ong <me@jongleberry.com>
Copyright (c) 2015 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1666 anymatch 3.1.3

1.1666.1 Available under license :

The ISC License

Copyright (c) 2019 Elan Shanker, Paul Miller (https://paulmillr.com)

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR
IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1667 destroy 1.2.0

1.1667.1 Available under license :

MIT

The MIT License (MIT)

Copyright (c) 2014 Jonathan Ong me@jongleberry.com
Copyright (c) 2015-2022 Douglas Christopher Wilson doug@somethingdoug.com

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR
OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1668 fs.realpath 1.0.0

1.1668.1 Available under license :

ISC
The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES

WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

This library bundles a version of the `fs.realpath` and `fs.realpathSync`
methods from Node.js v0.10 under the terms of the Node.js MIT license.

Node's license follows, also included at the header of `old.js` which contains the
licensed code:

Copyright Joyent, Inc. and other Node contributors.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1669 opener 1.5.2

1.1669.1 Available under license :

Dual licensed under WTFPL and MIT:

Copyright 20122020 Domenic Denicola <d@domenic.me>

This work is free. You can redistribute it and/or modify it under the terms of the Do What The Fuck You Want To Public License, Version 2, as published by Sam Hocevar. See below for more details.

DO WHAT THE FUCK YOU WANT TO PUBLIC LICENSE
Version 2, December 2004

Copyright (C) 2004 Sam Hocevar <sam@hocevar.net>

Everyone is permitted to copy and distribute verbatim or modified
copies of this license document, and changing it is allowed as long
as the name is changed.

DO WHAT THE FUCK YOU WANT TO PUBLIC LICENSE
TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. You just DO WHAT THE FUCK YOU WANT TO.

The MIT License (MIT)

Copyright 20122020 Domenic Denicola <d@domenic.me>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to
deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
984f8188a5751e02533d0d61e67c3153

1.1670 set-blocking 2.0.0

1.1670.1 Available under license :

Copyright (c) 2016, Contributors

Permission to use, copy, modify, and/or distribute this software
for any purpose with or without fee is hereby granted, provided

that the above copyright notice and this permission notice
appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES
OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS,
WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION,
ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1671 stack-trace 0.0.10

1.1671.1 Available under license :

Copyright (c) 2011 Felix Geisendrfer (felix@debuggable.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.1672 path-to-regexp 0.1.7

1.1672.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Blake Embrey (hello@blakeembrey.com)

Permission is hereby granted, free of charge, to any person obtaining a copy

of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

1.1673 type-is 1.6.18

1.1673.1 Available under license :

(The MIT License)

Copyright (c) 2014 Jonathan Ong <me@jongleberry.com>
Copyright (c) 2014-2015 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1674 es-errors 1.3.0

1.1674.1 Available under license :

MIT License

Copyright (c) 2024 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1675 methods 1.1.2

1.1675.1 Available under license :

(The MIT License)

Copyright (c) 2013-2014 TJ Holowaychuk <tj@vision-media.ca>
Copyright (c) 2015-2016 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES
OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1676 imurmurhash 0.1.4

1.1676.1 Available under license :

MIT

1.1677 fast-deep-equal 3.1.3

1.1677.1 Available under license :

MIT License

Copyright (c) 2017 Evgeny Poberezkin

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1678 content-type 1.0.5

1.1678.1 Available under license :

(The MIT License)

Copyright (c) 2015 Douglas Christopher Wilson

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1679 hasown 2.0.2

1.1679.1 Available under license :

MIT License

Copyright (c) Jordan Harband and contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1680 big.js 5.2.2

1.1680.1 Available under license :

The MIT Licence (Expat).

Copyright (c) 2018 Michael Mclaughlin

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1681 dashdash 1.14.1

1.1681.1 Available under license :

This is the MIT license

Copyright (c) 2013 Trent Mick. All rights reserved.
Copyright (c) 2013 Joyent Inc. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a

copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER
IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1682 json-stringify-safe 5.0.1

1.1682.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR
IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1683 glob 7.2.3

1.1683.1 Available under license :

ISC
The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR
IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Glob Logo

Glob's logo created by Tanya Brassie <http://tanyabrassie.com/>, licensed
under a Creative Commons Attribution-ShareAlike 4.0 International License
https://creativecommons.org/licenses/by-sa/4.0/

1.1684 on-finished 2.4.1

1.1684.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2013 Jonathan Ong <me@jongleberry.com>
Copyright (c) 2014 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE

SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1685 once 1.4.0

1.1685.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR
IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1686 process 0.11.10

1.1686.1 Available under license :

(The MIT License)

Copyright (c) 2013 Roman Shtylman <shtylman@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING

FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1687 unpipe 1.0.0

1.1687.1 Available under license :

(The MIT License)

Copyright (c) 2015 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR
OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1688 validate-npm-package-license 3.0.4

1.1688.1 Available under license :

Apache License 2.0

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction,

and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to

communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and

attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or

implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

validate-npm-package-license
==========

Give me a string and I'll tell you if it's a valid npm package license string.

```javascript
var valid = require('validate-npm-package-license');
```

SPDX license identifiers are valid license strings:

```javascript

var assert = require('assert');
var validSPDXExpression = {
 validForNewPackages: true,
 validForOldPackages: true,
 spdx: true
};

assert.deepEqual(valid('MIT'), validSPDXExpression);
assert.deepEqual(valid('BSD-2-Clause'), validSPDXExpression);
assert.deepEqual(valid('Apache-2.0'), validSPDXExpression);
assert.deepEqual(valid('ISC'), validSPDXExpression);
```

The function will return a warning and suggestion for nearly-correct license identifiers:

```javascript
assert.deepEqual(
 valid('Apache 2.0'),
 {
  validForOldPackages: false,
  validForNewPackages: false,
  warnings: [
   'license should be ' +
   'a valid SPDX license expression (without "LicenseRef"), ' +
   '"UNLICENSED", or ' +
    '"SEE LICENSE IN <filename>"',
   'license is similar to the valid expression "Apache-2.0"'
  ]
```

```
 }
);
```

SPDX expressions are valid, too ...

```javascript
// Simple SPDX license expression for dual licensing
assert.deepEqual(
 valid('(GPL-3.0-only OR BSD-2-Clause)'),
 validSPDXExpression
);
```

... except if they contain `LicenseRef`:

```javascript
var warningAboutLicenseRef = {
 validForOldPackages: false,
 validForNewPackages: false,
 spdx: true,
 warnings: [
  'license should be ' +
  'a valid SPDX license expression (without "LicenseRef"), ' +
  '"UNLICENSED", or ' +
  '"SEE LICENSE IN <filename>"',
 ]
};

assert.deepEqual(
 valid('LicenseRef-Made-Up'),
 warningAboutLicenseRef
);

assert.deepEqual(
 valid('(MIT OR LicenseRef-Made-Up)'),
 warningAboutLicenseRef
);
```

If you can't describe your licensing terms with standardized SPDX identifiers, put the terms in a file in the package and point users there:

```javascript
assert.deepEqual(
 valid('SEE
 LICENSE IN LICENSE.txt'),
 {
```

```
  validForNewPackages: true,
  validForOldPackages: true,
  inFile: 'LICENSE.txt'
 }
);

assert.deepEqual(
 valid('SEE LICENSE IN license.md'),
 {
  validForNewPackages: true,
  validForOldPackages: true,
  inFile: 'license.md'
 }
);
```

If there aren't any licensing terms, use `UNLICENSED`:

```javascript
var unlicensed = {
 validForNewPackages: true,
 validForOldPackages: true,
 unlicensed: true
};
assert.deepEqual(valid('UNLICENSED'), unlicensed);
assert.deepEqual(valid('UNLICENCED'), unlicensed);
```

1.1689 color-name 1.1.3

1.1689.1 Available under license :

MIT
The MIT License (MIT)
Copyright (c) 2015 Dmitry Ivanov

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN

AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1690 fast-json-stable-stringify 2.1.0

1.1690.1 Available under license :

This software is released under the MIT license:

Copyright (c) 2017 Evgeny Poberezkin
Copyright (c) 2013 James Halliday

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN
AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1691 media-typer 0.3.0

1.1691.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2014 Douglas Christopher Wilson

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the 'Software'), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1692 range-parser 1.2.1

1.1692.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2012-2014 TJ Holowaychuk <tj@vision-media.ca>
Copyright (c) 2015-2016 Douglas Christopher Wilson <doug@somethingdoug.com

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES
OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1693 es-define-property 1.0.0

1.1693.1 Available under license :

MIT License

Copyright (c) 2024 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1694 has-unicode 2.0.1

1.1694.1 Available under license :

ISC
Copyright (c) 2014, Rebecca Turner <me@re-becca.org>

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.1695 tr46 0.0.3

1.1695.1 Available under license :

MIT

1.1696 iconv-lite 0.4.24

1.1696.1 Available under license :

Copyright (c) 2011 Alexander Shtuchkin

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH
 THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1697 ajv-keywords 3.5.2

1.1697.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2016 Evgeny Poberezkin

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1698 vary 1.1.2

1.1698.1 Available under license :

(The MIT License)

Copyright (c) 2014-2017 Douglas Christopher Wilson

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1699 strip-ansi 6.0.1

1.1699.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (sindresorhus.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1700 proxy-addr 2.0.7

1.1700.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2014-2016 Douglas Christopher Wilson

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,

OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1701 statuses 2.0.1

1.1701.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Jonathan Ong <me@jongleberry.com>
Copyright (c) 2016 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1702 has-symbols 1.0.3

1.1702.1 Available under license :

MIT License

Copyright (c) 2016 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1703 base64-js 1.5.1

1.1703.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Jameson Little

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.1704 url 0.11.3

1.1704.1 Available under license :

The MIT License (MIT)

Copyright 2014 Joyent, Inc. and other Node contributors.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1705 json-schema-traverse 0.4.1

1.1705.1 Available under license :

MIT License

Copyright (c) 2017 Evgeny Poberezkin

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

MIT

1.1706 rw 1.3.3

1.1706.1 Available under license :

Copyright (c) 2014-2016, Michael Bostock
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* The name Michael Bostock may not be used to endorse or promote products
 derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE
DISCLAIMED. IN NO EVENT SHALL MICHAEL BOSTOCK BE LIABLE FOR ANY DIRECT,
INDIRECT,
 INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING,
BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE,
DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY
OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING
NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE,
EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1707 encoding 0.1.13

1.1707.1 Available under license :

MIT
Copyright (c) 2012-2014 Andris Reinman

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1708 etag 1.8.1

1.1708.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2014-2016 Douglas Christopher Wilson

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1709 rimraf 3.0.2

1.1709.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above

copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1710 psl 1.9.0

1.1710.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2017 Lupo Montero lupomontero@gmail.com

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1711 finalhandler 1.2.0

1.1711.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2014-2022 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including

without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT
OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1712 content-disposition 0.5.4

1.1712.1 Available under license :

(The MIT License)

Copyright (c) 2014-2017 Douglas Christopher Wilson

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1713 define-data-property 1.1.4

1.1713.1 Available under license :

MIT
MIT License

Copyright (c) 2023 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.

1.1714 mime-types 2.1.35

1.1714.1 Available under license :

(The MIT License)

Copyright (c) 2014 Jonathan Ong <me@jongleberry.com>
Copyright (c) 2015 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1715 ieee754 1.2.1

1.1715.1 Available under license :

BSD-3-Clause
Copyright 2008 Fair Oaks Labs, Inc.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS
BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1716 safe-buffer 5.2.1

1.1716.1 Available under license :

The MIT License (MIT)

Copyright (c) Feross Aboukhadijeh

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.1717 set-function-length 1.2.2

1.1717.1 Available under license :

MIT License

Copyright (c) Jordan Harband and contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF
OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1718 has-property-descriptors 1.0.2

1.1718.1 Available under license :

MIT License

Copyright (c) 2022 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1719 color-convert 1.9.3

1.1719.1 Available under license :

Copyright (c) 2011-2016 Heather Arthur <fayearthur@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF

MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1720 escape-html 1.0.3

1.1720.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2012-2013 TJ Holowaychuk
Copyright (c) 2015 Andreas Lubbe
Copyright (c) 2015 Tiancheng "Timothy" Gu

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1721 merge-descriptors 1.0.1

1.1721.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2013 Jonathan Ong <me@jongleberry.com>
Copyright (c) 2015 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1722 raw-body 2.5.2

1.1722.1 Available under license :

The MIT License (MIT)

Copyright (c) 2013-2014 Jonathan Ong <me@jongleberry.com>
Copyright (c) 2014-2022 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES
OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.

MIT

1.1723 es6-promise 4.2.8

1.1723.1 Available under license :

Copyright (c) 2014 Yehuda Katz, Tom Dale, Stefan Penner and contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1724 has 1.0.3

1.1724.1 Available under license :

Copyright (c) 2013 Thiago de Arruda

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES

OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION WITH
THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1725 encodeurl 1.0.2

1.1725.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2016 Douglas Christopher Wilson

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1726 jsbn 0.1.1

1.1726.1 Notifications :

This product includes cryptographic software written by Eric Young (eay@cryptsoft.com).
This product includes software written by Tim Hudson (tjh@cryptsoft.com).
This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit
(http://www.openssl.org/)

1.1726.2 Available under license :

Licensing

This software is covered under the following copyright:

/*
* Copyright (c) 2003-2005 Tom Wu
* All Rights Reserved.
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be
* included in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND,
* EXPRESS, IMPLIED OR OTHERWISE, INCLUDING WITHOUT LIMITATION, ANY
* WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.
*
* IN NO EVENT SHALL TOM WU BE LIABLE FOR ANY SPECIAL,
 INCIDENTAL,
* INDIRECT OR CONSEQUENTIAL DAMAGES OF ANY KIND, OR ANY DAMAGES WHATSOEVER
* RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER OR NOT ADVISED OF
* THE POSSIBILITY OF DAMAGE, AND ON ANY THEORY OF LIABILITY, ARISING OUT
* OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
*
* In addition, the following condition applies:
*
* All redistributions must retain an intact copy of this copyright notice
* and disclaimer.
*/

Address all questions regarding this license to:

 Tom Wu
 tjw@cs.Stanford.EDU
MIT

1.1727 mime-db 1.52.0

1.1727.1 Available under license :

(The MIT License)

Copyright (c) 2014 Jonathan Ong <me@jongleberry.com>
Copyright (c) 2015-2022 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1728 concat-map 0.0.1

1.1728.1 Available under license :

This software is released under the MIT license:

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS

FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1729 whatwg-url 5.0.0

1.1729.1 Available under license :

The MIT License (MIT)

Copyright (c) 20152016 Sebastian Mayr

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1730 bytes 3.1.2

1.1730.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2012-2014 TJ Holowaychuk <tj@vision-media.ca>
Copyright (c) 2015 Jed Watson <jed.watson@me.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including

without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER
IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1731 express-http-proxy 1.6.3

1.1731.1 Available under license :

MIT
Copyright (c) 2013 villadora <jky239@gmail.com>, contributors
http://kael.me/

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE
LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION
OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1732 call-bind 1.0.7

1.1732.1 Available under license :

MIT License

Copyright (c) 2020 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1733 spdx-exceptions 2.3.0

1.1733.1 Available under license :

UNRECOGNIZED LICENSE; MD5 sum: 39574483a6be9b11884d0cd2812d3cef

1.1734 jsprim 1.4.2

1.1734.1 Available under license :

Copyright (c) 2012, Joyent, Inc. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in

all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE
MIT

1.1735 has-proto 1.0.3

1.1735.1 Available under license :

MIT License

Copyright (c) 2022 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1736 signal-exit 3.0.7

1.1736.1 Available under license :

The ISC License

Copyright (c) 2015, Contributors

Permission to use, copy, modify, and/or distribute this software
for any purpose with or without fee is hereby granted, provided
that the above copyright notice and this permission notice
appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES
OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE
LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES
OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS,
WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION,
ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1737 color-support 1.1.3

1.1737.1 Available under license :

The ISC License

Copyright (c) Isaac Z. Schlueter and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR
IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1738 console-control-strings 1.1.0

1.1738.1 Available under license :

ISC
Copyright (c) 2014, Rebecca Turner <me@re-becca.org>

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF

MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.1739 inherits 2.0.4

1.1739.1 Available under license :

ISC
The ISC License

Copyright (c) Isaac Z. Schlueter

Permission to use, copy, modify, and/or distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.1740 object-inspect 1.13.1

1.1740.1 Available under license :

MIT License

Copyright (c) 2013 James Halliday

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1741 get-intrinsic 1.2.4

1.1741.1 Available under license :

MIT License

Copyright (c) 2020 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1742 webidl-conversions 3.0.1

1.1742.1 Available under license :

BSD-2-Clause
The BSD 2-Clause License

Copyright (c) 2014, Domenic Denicola
All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1743 wide-align 1.1.5

1.1743.1 Available under license :

ISC
Copyright (c) 2015, Rebecca Turner <me@re-becca.org>

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.1744 parseurl 1.3.3

1.1744.1 Available under license :

MIT

(The MIT License)

Copyright (c) 2014 Jonathan Ong <me@jongleberry.com>
Copyright (c) 2014-2017 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR
OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1745 setprototypeof 1.2.0

1.1745.1 Available under license :

ISC
Copyright (c) 2015, Wes Todd

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY
SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION
OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN
CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

1.1746 promise-inflight 1.0.1

1.1746.1 Available under license :

Copyright (c) 2017, Rebecca Turner <me@re-becca.org>

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1747 toidentifier 1.0.1

1.1747.1 Available under license :

MIT
MIT License

Copyright (c) 2016 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1748 side-channel 1.0.6

1.1748.1 Available under license :

MIT License

Copyright (c) 2019 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal

in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1749 http-errors 2.0.0

1.1749.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Jonathan Ong me@jongleberry.com
Copyright (c) 2016 Douglas Christopher Wilson doug@somethingdoug.com

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.1750 readdirp 3.6.0

1.1750.1 Available under license :

MIT License

Copyright (c) 2012-2019 Thorsten Lorenz, Paul Miller (https://paulmillr.com)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1751 to-regex-range 5.0.1

1.1751.1 Available under license :

The MIT License (MIT)

Copyright (c) 2015-present, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR

IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1752 neo-async 2.6.2

1.1752.1 Available under license :

MIT
MIT License

Copyright (c) 2014-2018 Suguru Motegi
Based on Async.js, Copyright Caolan McMahon

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1753 supports-preserve-symlinks-flag 1.0.0

1.1753.1 Available under license :

MIT License

Copyright (c) 2022 Inspect JS

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal

in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1754 source-map-support 0.5.21

1.1754.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014 Evan Wallace

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1755 update-browserslist-db 1.0.13

1.1755.1 Available under license :

The MIT License (MIT)

Copyright 2022 Andrey Sitnik <andrey@sitnik.ru> and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of
the Software, and to permit persons to whom the Software is furnished to do so,
subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS
FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR
COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER
IN AN ACTION OF CONTRACT, TORT
OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1756 source-map 0.6.1

1.1756.1 Available under license :

BSD-3-Clause

Copyright (c) 2009-2011, Mozilla Foundation and contributors
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice, this
 list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
 this list of conditions and the following disclaimer in the documentation
 and/or other materials provided with the distribution.

* Neither the names of the Mozilla Foundation nor the names of project
 contributors may be used to endorse or promote products derived from this

software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED.
IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1757 is-glob 4.0.3

1.1757.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2014-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1758 postcss-value-parser 4.2.0

1.1758.1 Available under license :

Copyright (c) Bogdan Chadkin <trysound@yandex.ru>

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1759 randombytes 2.1.0

1.1759.1 Available under license :

MIT License

Copyright (c) 2017 crypto-browserify

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER

LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1760 is-core-module 2.13.1

1.1760.1 Available under license :

The MIT License (MIT)

Copyright (c) 2014 Dave Justice

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1761 events 3.3.0

1.1761.1 Available under license :

MIT

Copyright Joyent, Inc. and other Node contributors.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN
NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR
OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE
USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1762 picomatch 2.3.1

1.1762.1 Available under license :

The MIT License (MIT)

Copyright (c) 2017-present, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN
THE SOFTWARE.
MIT

1.1763 esrecurse 4.3.0

1.1763.1 Available under license :

BSD-2-Clause

1.1764 picocolors 1.0.0

1.1764.1 Available under license :

ISC License

Copyright (c) 2021 Alexey Raspopov, Kostiantyn Denysov, Anton Verinov

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES
WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF
MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR
ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES
WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN
ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF
OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1765 node-releases 2.0.14

1.1765.1 Available under license :

The MIT License

Copyright (c) 2017 Sergey Rubanov (https://github.com/chicoxyzzy)

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,

ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1766 resolve 1.22.8

1.1766.1 Available under license :

ISC
MIT
MIT License

Copyright (c) 2012 James Halliday

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1767 buffer-from 1.1.2

1.1767.1 Available under license :

MIT License

Copyright (c) 2016, 2018 Linus Unnebck

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN
CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1768 graceful-fs 4.2.11

1.1768.1 Available under license :

The ISC License

Copyright (c) 2011-2022 Isaac Z. Schlueter, Ben Noordhuis, and Contributors

Permission to use, copy, modify, and/or distribute this software for any
purpose with or without fee is hereby granted, provided that the above
copyright notice and this permission notice appear in all copies.

THE SOFTWARE IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS SOFTWARE INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.
ISC

1.1769 jsr305 3.0.1

1.1769.1 Available under license :

No license file was found, but licenses were detected in source scan.

/*
* Copyright (c) 2005 Brian Goetz
* Released under the Creative Commons Attribution License
*   (http://creativecommons.org/licenses/by/2.5)
* Official home: http://www.jcip.net
*/

Found in path(s):
* /jsr305-3-0-1-sources-4-jar/javax/annotation/concurrent/Immutable.java
* /jsr305-3-0-1-sources-4-jar/javax/annotation/concurrent/NotThreadSafe.java
* /jsr305-3-0-1-sources-4-jar/javax/annotation/concurrent/GuardedBy.java

1.1770 estraverse 4.3.0

1.1770.1 Available under license :

BSD-2-Clause
Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright
  notice, this list of conditions and the following disclaimer.
* Redistributions in binary form must reproduce the above copyright
  notice, this list of conditions and the following disclaimer in the
  documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT SHALL <COPYRIGHT HOLDER> BE LIABLE FOR ANY
DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES
(INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;
LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER
CAUSED AND
ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT
(INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF
THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

1.1771 webpack-sources 1.4.3

1.1771.1 Available under license :

MIT License

Copyright (c) 2017 JS Foundation and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1772 chrome-trace-event 1.0.3

1.1772.1 Available under license :

This is the MIT license

Copyright (c) 2015 Joyent Inc. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a
copy of this software and associated documentation files (the
"Software"), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be included
in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1773 source-list-map 2.0.1

1.1773.1 Available under license :

MIT
Copyright 2017 JS Foundation

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated

documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE
OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1774 postcss-selector-parser 6.0.16

1.1774.1 Available under license :

Copyright (c) Ben Briggs <beneb.info@gmail.com> (http://beneb.info)

Permission is hereby granted, free of charge, to any person
obtaining a copy of this software and associated documentation
files (the "Software"), to deal in the Software without
restriction, including without limitation the rights to use,
copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the
Software is furnished to do so, subject to the following
conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES
OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND
NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT
HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR
OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1775 isorelax 20090621

1.1775.1 Available under license :

No license file was found, but licenses were detected in source scan.

```
/*
* @(#)$Id: IgnoredSchema.java,v 1.5 2003/05/30 23:46:32 kkawa Exp $
*
* Copyright 2001 Kohsuke KAWAGUCHI
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be included
* in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
* IN NO
 EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
* CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
* TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
* SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/
```

Found in path(s):
* /isorelax-20090621-sources-5-jar/org/iso_relax/dispatcher/impl/IgnoredSchema.java

No license file was found, but licenses were detected in source scan.

```
/*
* @(#)$Id: SchemaProvider.java,v 1.6 2003/05/30 23:46:32 kkawa Exp $
*
* Copyright 2001 Kohsuke KAWAGUCHI
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be included
* in all copies or substantial portions of the Software.
```

*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
* IN NO
EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
* CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
* TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
* SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/

Found in path(s):
* /isorelax-20090621-sources-5-jar/org/iso_relax/dispatcher/SchemaProvider.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)$Id: IslandSchemaReader.java,v 1.4 2001/11/01 00:11:45 kkawa Exp $
*
* Copyright 2001 KAWAGUCHI Kohsuke
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be included
* in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
* IN
NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
* CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
* TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
* SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/

Found in path(s):
* /isorelax-20090621-sources-5-jar/org/iso_relax/dispatcher/IslandSchemaReader.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)$Id: IslandVerifier.java,v 1.6 2003/05/30 23:46:32 kkawa Exp $
*

* Copyright 2001 MURATA Makoto, KAWAGUCHI Kohsuke
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be included
* in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
 * IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
* CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
* TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
* SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/

Found in path(s):
* /isorelax-20090621-sources-5-jar/org/iso_relax/dispatcher/IslandVerifier.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)$Id: DispatcherImpl.java,v 1.5 2003/05/30 23:46:32 kkawa Exp $
*
* Copyright 2001 Kohsuke KAWAGUCHI
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be included
* in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
* IN NO
 EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
* CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,

* TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
* SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/

Found in path(s):
* /isorelax-20090621-sources-5-jar/org/iso_relax/dispatcher/impl/DispatcherImpl.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)$Id: Dispatcher.java,v 1.6 2003/05/30 23:46:32 kkawa Exp $
*
* Copyright 2001 MURATA Makoto, KAWAGUCHI Kohsuke
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be included
* in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
 * IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
* CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
* TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
* SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/

Found in path(s):
* /isorelax-20090621-sources-5-jar/org/iso_relax/dispatcher/Dispatcher.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)$Id: AttributesDecl.java,v 1.3 2001/11/01 00:11:45 kkawa Exp $
*
* Copyright 2001 Kohsuke KAWAGUCHI
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to

* the following conditions:
*
* The above copyright notice and this permission notice shall be included
* in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
* IN NO
EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
* CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
* TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
* SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/

Found in path(s):
* /isorelax-20090621-sources-5-jar/org/iso_relax/dispatcher/AttributesDecl.java
No license file was found, but licenses were detected in source scan.

/*
* @(#)$Id: ElementDecl.java,v 1.3 2001/11/01 00:11:45 kkawa Exp $
*
* Copyright 2001 Kohsuke KAWAGUCHI
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be included
* in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
* IN NO EVENT
SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
* CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
* TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
* SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/

Found in path(s):
* /isorelax-20090621-sources-5-jar/org/iso_relax/dispatcher/ElementDecl.java

No license file was found, but licenses were detected in source scan.

/*
* @(#)$Id: IslandSchema.java,v 1.5 2003/05/30 23:46:32 kkawa Exp $
*
* Copyright 2001 KAWAGUCHI Kohsuke
*
* Permission is hereby granted, free of charge, to any person obtaining
* a copy of this software and associated documentation files (the
* "Software"), to deal in the Software without restriction, including
* without limitation the rights to use, copy, modify, merge, publish,
* distribute, sublicense, and/or sell copies of the Software, and to
* permit persons to whom the Software is furnished to do so, subject to
* the following conditions:
*
* The above copyright notice and this permission notice shall be included
* in all copies or substantial portions of the Software.
*
* THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND,
* EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
* MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
* IN NO EVENT
SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
* CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
* TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
* SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
*/

Found in path(s):
* /isorelax-20090621-sources-5-jar/org/iso_relax/dispatcher/IslandSchema.java

1.1776 types-json-schema 7.0.15

1.1776.1 Available under license :

MIT
MIT License

Copyright (c) Microsoft Corporation.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all

copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF
CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE

1.1777 xml-apis 1.4.01

1.1777.1 Available under license :

```
========================================================================
==  NOTICE file corresponding to section 4(d) of the Apache License,   ==
==  Version 2.0, in this case for the Apache xml-commons xml-apis      ==
==  distribution.                                                      ==
========================================================================
```

Apache XML Commons XML APIs
Copyright 1999-2009 The Apache Software Foundation.

This product includes software developed at
The Apache Software Foundation (http://www.apache.org/).

Portions of this software were originally based on the following:
- software copyright (c) 1999, IBM Corporation., http://www.ibm.com.
- software copyright (c) 1999, Sun Microsystems., http://www.sun.com.
- software copyright (c) 2000 World Wide Web Consortium, http://www.w3.org
xml-commons/java/external/LICENSE.sax.txt $Id: LICENSE.sax.txt 225954 2002-01-31 23:26:48Z curcuru $

This license came from: http://www.megginson.com/SAX/copying.html
However please note future versions of SAX may be covered
under http://saxproject.org/?selected=pd

This page is now out of date -- see the new SAX site at
http://www.saxproject.org/ for more up-to-date
releases and other information. Please change your bookmarks.

SAX2 is Free!

I hereby abandon any property rights to SAX 2.0 (the Simple API for
XML), and release all of the SAX 2.0 source code, compiled code, and

documentation contained in this distribution into the Public Domain.
SAX comes with NO WARRANTY or guarantee of fitness for any
purpose.

David Megginson, david@megginson.com
2000-05-05
xml-commons/java/external/LICENSE.dom-software.txt $Id: LICENSE.dom-software.txt 734314 2009-01-14 03:33:27Z mrglavas $

This license came from: http://www.w3.org/TR/2004/REC-DOM-Level-3-Core-20040407/java-binding.zip (COPYRIGHT.html)

W3C SOFTWARE NOTICE AND LICENSE
Copyright 2004 World Wide Web Consortium, (Massachusetts Institute of Technology, European Research Consortium for Informatics and Mathematics, Keio University). All Rights Reserved.

The DOM bindings are published under the W3C Software Copyright Notice and License. The software license requires "Notice of any changes or modifications to the W3C files, including the date changes were made." Consequently, modified versions of the DOM bindings must document that they do not conform to the W3C standard; in the case of the IDL definitions, the pragma prefix can no longer be 'w3c.org'; in the case of the Java language binding, the package names can no longer be in the 'org.w3c' package.

Note: The original version of the
W3C Software Copyright Notice and License could
be found at http://www.w3.org/Consortium/Legal/2002/copyright-software-20021231

This work (and included software, documentation such as READMEs, or other related items) is being provided by the copyright holders under the following license. By obtaining, using and/or copying this work, you (the licensee) agree that you have read, understood, and will comply with the following terms and conditions.

Permission to copy, modify, and distribute this software and its documentation, with or without modification, for any purpose and without fee or royalty is hereby granted, provided that you include the following on ALL copies of the software and documentation or portions thereof, including modifications:

1. The full text of this NOTICE in a location viewable to users of the redistributed or derivative work.
2. Any pre-existing intellectual property disclaimers, notices, or terms and conditions. If none exist, the
W3C Software Short Notice should be
included (hypertext is preferred, text is permitted) within the body of any redistributed or derivative code.
3. Notice of any changes or modifications to the files, including the date

changes were made. (We recommend you provide URIs to the location from which the code is derived.)

THIS SOFTWARE AND DOCUMENTATION IS PROVIDED "AS IS," AND COPYRIGHT HOLDERS MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR THAT THE USE OF THE SOFTWARE OR DOCUMENTATION WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

COPYRIGHT HOLDERS WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF ANY USE OF THE SOFTWARE OR DOCUMENTATION.

The name and trademarks of copyright holders may NOT be used in advertising or publicity pertaining to the software without specific, written prior permission.
Title to copyright in this software and any associated documentation will at all times remain with copyright holders.

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial
revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable

(except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,

and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
xml-commons/java/external/LICENSE.dom-documentation.txt $Id: LICENSE.dom-documentation.txt 226215
2005-06-03 22:49:13Z mrglavas $

This license came from: http://www.w3.org/Consortium/Legal/copyright-documents-20021231

W3C DOCUMENT LICENSE
http://www.w3.org/Consortium/Legal/2002/copyright-documents-20021231

Public documents on the W3C site are provided by the copyright holders under
the following license. By using and/or copying this document, or the W3C
document from which this statement is linked, you (the licensee) agree that

you have read, understood, and will comply with the following terms and conditions:

Permission to copy, and distribute the contents of this document, or the W3C document from which this statement is linked, in any medium for any purpose and without fee or royalty is hereby granted, provided that you include the following on ALL copies of the document, or portions thereof, that you use:

1. A link or URL to the original W3C document.
2. The pre-existing copyright notice of the original author, or if it doesn't exist, a notice (hypertext is preferred, but a textual representation is permitted) of the form: "Copyright [$date-of-document] World Wide Web Consortium, (Massachusetts Institute of Technology, European Research Consortium for Informatics and Mathematics, Keio University). All Rights Reserved. http://www.w3.org/Consortium/Legal/2002/copyright-documents-20021231"
3. If it exists, the STATUS of the W3C document.

When space permits, inclusion of the full text of this NOTICE should be provided. We request that authorship attribution be provided in any software, documents, or other items or products that you create pursuant to the implementation of the contents of this document, or any portion thereof.

No right to create modifications or derivatives of W3C documents is granted pursuant to this license. However, if additional requirements (documented in the Copyright FAQ) are satisfied, the right to create modifications or derivatives is sometimes granted by the W3C to individuals complying with those requirements.

THIS DOCUMENT IS PROVIDED "AS IS," AND COPYRIGHT HOLDERS MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR TITLE; THAT THE CONTENTS OF THE DOCUMENT ARE SUITABLE FOR ANY PURPOSE; NOR THAT THE IMPLEMENTATION OF SUCH CONTENTS WILL NOT INFRINGE ANY THIRD PARTY PATENTS, COPYRIGHTS, TRADEMARKS OR OTHER RIGHTS.

COPYRIGHT HOLDERS WILL NOT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF ANY USE OF THE DOCUMENT OR THE PERFORMANCE OR IMPLEMENTATION OF THE CONTENTS THEREOF.

The name and trademarks of copyright holders may NOT be used in advertising or publicity pertaining to this document or its contents without specific, written prior permission. Title to copyright in this document will at all times remain with copyright holders.

This formulation of W3C's notice and license became active on December 31 2002. This version removes the copyright ownership notice such that this license can be used with materials other than those owned by the W3C, moves information on style sheets, DTDs, and schemas to the Copyright FAQ, reflects that ERCIM is now a host of the W3C, includes references to this specific dated version of the license, and removes the ambiguous grant of "use". See the older formulation for the policy prior to this date. Please see our Copyright FAQ for common questions about using materials from our site, such as the translating or annotating specifications. Other questions about this notice can be directed to site-policy@w3.org.

Joseph Reagle <site-policy@w3.org>

Last revised by Reagle $Date: 2005-06-03 18:49:13 -0400 (Fri, 03 Jun 2005) $

1.1778 json-simple 1.1.1

1.1778.1 Available under license :

Apache-2.0

1.1779 safer-buffer 2.1.2

1.1779.1 Available under license :

MIT License

Copyright (c) 2018 Nikita Skovoroda <chalkerx@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT

OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1780 is-accessor-descriptor 1.0.1

1.1780.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1781 is-data-descriptor 1.0.1

1.1781.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1782 is-descriptor 0.1.7

1.1782.1 Available under license :

MIT
The MIT License (MIT)

Copyright (c) 2015-2017, Jon Schlinkert.

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in
all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT
OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1783 binary-extensions 2.3.0

1.1783.1 Available under license :

MIT
MIT License

Copyright (c) Sindre Sorhus <sindresorhus@gmail.com> (https://sindresorhus.com)

Copyright (c) Paul Miller (https://paulmillr.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1784 ip 2.0.0

1.1784.1 Available under license :

MIT

1.1785 serve-static 1.15.0

1.1785.1 Available under license :

MIT
(The MIT License)

Copyright (c) 2010 Sencha Inc.
Copyright (c) 2011 LearnBoost
Copyright (c) 2011 TJ Holowaychuk
Copyright (c) 2014-2016 Douglas Christopher Wilson

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the 'Software'), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,

EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM,
DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.1786 body-parser 1.20.1

1.1786.1 Available under license :

(The MIT License)

Copyright (c) 2014 Jonathan Ong <me@jongleberry.com>
Copyright (c) 2014-2015 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining
a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1787 body-parser 1.20.2

1.1787.1 Available under license :

(The MIT License)

Copyright (c) 2014 Jonathan Ong <me@jongleberry.com>
Copyright (c) 2014-2015 Douglas Christopher Wilson <doug@somethingdoug.com>

Permission is hereby granted, free of charge, to any person obtaining

a copy of this software and associated documentation files (the
'Software'), to deal in the Software without restriction, including
without limitation the rights to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell copies of the Software, and to
permit persons to whom the Software is furnished to do so, subject to
the following conditions:

The above copyright notice and this permission notice shall be
included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED 'AS IS', WITHOUT WARRANTY OF ANY KIND,
EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF
MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT.
IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY
CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT,
TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE
SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1788 gopd 1.0.1

1.1788.1 Available under license :

MIT License

Copyright (c) 2022 Jordan Harband

Permission is hereby granted, free of charge, to any person obtaining a copy
of this software and associated documentation files (the "Software"), to deal
in the Software without restriction, including without limitation the rights
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell
copies of the Software, and to permit persons to whom the Software is
furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,
OUT OF OR IN CONNECTION
WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
SOFTWARE.
MIT

1.1789 @xtuc/ieee754 1.2.0

1.1789.1 Available under license :

Copyright (c) 2008, Fair Oaks Labs, Inc.
All rights reserved.

Redistribution and use in source and binary forms, with or without
modification, are permitted provided that the following conditions are met:

* Redistributions of source code must retain the above copyright notice,
  this list of conditions and the following disclaimer.

* Redistributions in binary form must reproduce the above copyright notice,
  this list of conditions and the following disclaimer in the documentation
  and/or other materials provided with the distribution.

* Neither the name of Fair Oaks Labs, Inc. nor the names of its contributors
  may be used to endorse or promote products derived from this software
  without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS"
AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
ARE DISCLAIMED. IN NO EVENT
 SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1790 @xtuc/long 4.2.2

1.1790.1 Available under license :

Apache License 2.0

Apache License
Version 2.0, January 2004
http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of

the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute
copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works
that You distribute, all copyright, patent, trademark, and
attribution notices from the Source form of the Work,
excluding those notices that do not pertain to any part of
the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its
distribution, then any Derivative Works that You distribute must
include a readable copy of the attribution notices contained
within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one
of the following places: within a NOTICE text file distributed
as part of the Derivative Works; within the Source form or
documentation, if provided along with the Derivative Works; or,
within a display generated by the Derivative Works, if and
wherever such third-party notices normally appear. The contents
of the NOTICE file are for informational purposes only and
do not modify the License. You may add Your own attribution
notices within Derivative Works that You distribute, alongside
or as an addendum to the NOTICE text from the Work, provided
that such additional attribution notices cannot be construed
as modifying the License.

You may add Your own copyright statement to Your modifications and
may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or
for any such Derivative Works as a whole, provided Your use,
reproduction, and distribution of the Work otherwise complies with
the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise,
any Contribution intentionally submitted for inclusion in the Work
by You to the Licensor shall be under the terms and conditions of
this License, without any additional terms or conditions.
Notwithstanding the above, nothing herein shall supersede or modify
the terms of any separate license agreement you may have executed
with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade
names, trademarks, service marks, or product names of the Licensor,
except as required for reasonable and customary use in describing the
origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or

agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier
identification within third-party archives.

Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1791 uuid 8.3.2

1.1791.1 Available under license :

The MIT License (MIT)

Copyright (c) 2010-2020 Robert Kieffer and other contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE,
ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

1.1792 swagger-annotations 2.2.12

1.1792.1 Available under license :

Swagger Core - swagger-annotations
Copyright (c) 2015. SmartBear Software Inc.
Swagger Core - swagger-annotations is licensed under Apache 2.0 license.
Copy of the Apache 2.0 license can be found in `LICENSE` file.

Apache License
Version 2.0, January 2004

http://www.apache.org/licenses/

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including

the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License. Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License. Subject to the terms and conditions of this
License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution. You may reproduce and distribute copies of the
Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

(a) You must give any other recipients of the Work or

Derivative Works a copy of this License; and

(b) You must cause any modified files to carry prominent notices stating that You changed the files; and

(c) You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and

(d) If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding
those notices that do not
pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions

for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions. Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks. This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the

origin of the Work and reproducing the
content of the NOTICE file.

7. Disclaimer of Warranty. Unless required by applicable law or
agreed to in writing, Licensor provides the Work (and each
Contributor provides its Contributions) on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or
implied, including, without limitation, any warranties or conditions
of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A
PARTICULAR PURPOSE. You are solely responsible for determining the
appropriateness of using or redistributing the Work and assume any
risks associated with Your exercise of permissions under this License.

8. Limitation of Liability. In no event and under no legal theory,
whether in tort (including negligence), contract, or otherwise,
unless required by applicable law (such as deliberate and grossly
negligent acts) or agreed to in writing, shall any Contributor be
liable to You for damages, including any direct,
indirect, special,
incidental, or consequential damages of any character arising as a
result of this License or out of the use or inability to use the
Work (including but not limited to damages for loss of goodwill,
work stoppage, computer failure or malfunction, or any and all
other commercial damages or losses), even if such Contributor
has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability. While redistributing
the Work or Derivative Works thereof, You may choose to offer,
and charge a fee for, acceptance of support, warranty, indemnity,
or other liability obligations and/or rights consistent with this
License. However, in accepting such obligations, You may act only
on Your own behalf and on Your sole responsibility, not on behalf
of any other Contributor, and only if You agree to indemnify,
defend, and hold each Contributor harmless for any liability
incurred by, or claims asserted against, such Contributor by reason
of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work.

To apply the Apache License to your work, attach the following
boilerplate notice, with the fields enclosed by brackets "[]"
replaced with your own identifying information. (Don't include
the brackets!) The text should be enclosed in the appropriate
comment syntax for the file format. We also recommend that a
file or class name and description of purpose be included on the
same "printed page" as the copyright notice for easier

identification within third-party archives.

Copyright (c) 2015. SmartBear Software Inc.

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.

1.1793 elliptic 6.5.4

1.1793.1 Available under license :

MIT

1.1794 elliptic 6.5.5

1.1794.1 Available under license :

MIT

1.1795 duplexer3 0.1.5

1.1795.1 Available under license :

Copyright (c) 2022, Sindre Sorhus.
Copyright (c) 2020, Vsevolod Strukchinsky.
Copyright (c) 2013, Deoxxa Development.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.
THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR

PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
BSD-3-Clause

1.1796 aws4 1.12.0

1.1796.1 Available under license :

Copyright 2013 Michael Hart (michael.hart.au@gmail.com)

Permission is hereby granted, free of charge, to any person obtaining a copy of
this software and associated documentation files (the "Software"), to deal in
the Software without restriction, including without limitation the rights to
use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies
of the Software, and to permit persons to whom the Software is furnished to do
so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all
copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR
IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.
MIT

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries.To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

©2025 Cisco Systems, Inc. All rights reserved.